Biblioteca de códigos

Exemplos de código do SDK da AWS

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Exemplos de código do SDK da AWS: Biblioteca de códigos

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

As marcas comerciais e imagens comerciais da Amazon não podem ser usadas no contexto de nenhum produto ou serviço que não seja da Amazon, nem de qualquer maneira que possa gerar confusão entre clientes ou que deprecie ou desprestigie a Amazon. Todas as outras marcas comerciais que não pertencem à Amazon pertencem a seus respectivos proprietários, que podem ou não ser afiliados, patrocinados pela Amazon ou ter conexão com ela.

Table of Contents

..... xii
O que é a biblioteca de exemplos de código? 1
Como trabalhar com AWS SDKs 1
Exemplos de código por serviço 3
ACM 6
Ações 7
Cenários 37
API Gateway 46
Ações 48
Cenários 89
Exemplos entre serviços 97
API de gerenciamento do API Gateway 106
Ações 107
Application Auto Scaling 109
Ações 110
Application Recovery Controller 119
Ações 120
Audit Manager 126
Cenários 127
Aurora 140
Ações 149
Cenários 349
Exemplos entre serviços 518
Auto Scaling 523
Ações 533
Cenários 634
AWS Batch 893
Ações 894
Amazon Bedrock 896
Ações 902
Cenários 911
Amazon Bedrock Runtime 912
Ações 916
Cenários 983

Agentes do Amazon Bedrock 993
Ações 994
Cenários 1007
Agentes do Amazon Bedrock Runtime 1021
Ações 1021
Cenários 1023
AWS CloudFormation 1025
Exemplos entre serviços 1025
CloudFront 1026
Ações 1027
Cenários 1076
CloudTrail 1080
Ações 1080
CloudWatch 1086
Ações 1092
Cenários 1229
CloudWatch Eventos 1314
Ações 1315
CloudWatch Registros 1328
Ações 1329
Cenários 1378
Exemplos entre serviços 1385
CodeBuild 1386
Ações 1386
Amazon Cognito Identity 1393
Ações 1394
Exemplos entre serviços 1408
Provedor de identidade do Amazon Cognito 1410
Ações 1417
Cenários 1519
Amazon Cognito Sync 1582
Ações 1582
Amazon Comprehend 1584
Ações 1586
Cenários 1656
Exemplos entre serviços 1680

AWS Config 1689
Ações 1690
Device Farm 1698
Cenários 1698
DynamoDB 1709
Ações 1718
Cenários 2060
Exemplos entre serviços 2357
Amazon EBS 2374
Ações 2375
Amazon EC2 2378
Ações 2390
Cenários 2697
Amazon ECR 2945
Ações 2946
Amazon ECS 2950
Ações 2952
Cenários 2997
Amazon EKS 3005
Ações 3005
Elastic Beanstalk 3010
Ações 3011
Elastic Load Balancing 3017
Ações 3021
Cenários 3077
MediaStore 3238
Ações 3239
Amazon EMR 3255
Ações 3256
Cenários 3273
OpenSearch Serviço 3277
Ações 3277
EventBridge 3289
Ações 3294
Cenários 3347
Exemplos entre serviços 3428

Previsão 3431
Ações 3431
AWS Glue 3446
Ações 3454
Cenários 3575
HealthImaging 3683
Ações 3689
Cenários 3798
IAM 3837
Ações 3849
Cenários 4276
AWS IoT 4629
Ações 4631
Cenários 4656
AWS IoT data 4671
Ações 4672
Amazon Keyspaces 4676
Ações 4682
Cenários 4725
Kinesis 4786
Ações 4787
Cenários 4832
Exemplos sem servidor 4836
Firehose 4858
Ações 4858
AWS KMS 4861
Ações 4862
Cenários 4978
Lambda 4988
Ações 4997
Cenários 5082
Exemplos sem servidor 5195
Exemplos entre serviços 5252
Amazon Lex 5272
Exemplos entre serviços 5273
Lookout for Vision 5274

Ações 5277
Cenários 5304
Serviço Gerenciado para Apache Flink 5319
Ações 5321
Gerador de dados 5337
MediaConvert 5350
Ações 5352
MediaLive 5409
Ações 5410
MediaPackage 5411
Ações 5411
Migration Hub 5416
Ações 5417
Organizações 5431
Ações 5432
Amazon Personalize 5466
Ações 5468
Eventos do Amazon Personalize 5517
Ações 5518
Runtime do Amazon Personalize 5525
Ações 5526
Amazon Pinpoint 5534
Ações 5535
API de SMS e voz do Amazon Pinpoint 5614
Ações 5615
Amazon Polly 5623
Ações 5625
Cenários 5666
Exemplos entre serviços 5667
QLDB 5674
Ações 5675
Amazon RDS 5679
Ações 5688
Cenários 5804
Exemplos sem servidor 5901
Exemplos entre serviços 5903

Serviços de dados do Amazon RDS 5907
Ações 5908
Exemplos entre serviços 5910
Amazon Redshift 5915
Ações 5916
Exemplos entre serviços 5934
Amazon Rekognition 5935
Ações 5937
Cenários 6090
Exemplos entre serviços 6158
route 53 6171
Ações 6171
Registro de domínio do Route 53 6173
Ações 6180
Cenários 6210
Amazon S3 6242
Ações 6254
Cenários 6595
Exemplos sem servidor 6788
Exemplos entre serviços 6797
S3 Glacier 6813
Ações 6815
Cenários 6872
SageMaker 6884
Ações 6890
Cenários 6929
Secrets Manager 7027
Ações 7028
Exemplos entre serviços 7069
Amazon SES 7070
Ações 7072
Cenários 7184
Exemplos entre serviços 7209
API v2 do Amazon SES 7225
Ações 7225
Amazon SNS 7236

Ações 7248
Cenários 7435
Exemplos sem servidor 7523
Exemplos entre serviços 7532
Amazon SQS 7545
Ações 7556
Cenários 7683
Exemplos sem servidor 7765
Exemplos entre serviços 7781
Step Functions 7786
Ações 7792
Cenários 7842
Exemplos entre serviços 7892
AWS STS 7894
Ações 7895
Cenários 7914
AWS Support 7931
Ações 7940
Cenários 7998
Systems Manager 8055
Ações 8056
Amazon Textract 8077
Ações 8078
Cenários 8114
Exemplos entre serviços 8117
Amazon Transcribe 8125
Ações 8127
Cenários 8199
Exemplos entre serviços 8220
Amazon Translate 8222
Ações 8224
Cenários 8241
Exemplos entre serviços 8244
Amazon WorkDocs 8254
Ações 8254
Exemplos de código por SDK 8259

AWS SDK for .NET 8260
Ações e cenários 8260
Exemplos entre serviços 9521
AWS CLI com script Bash 9525
Ações e cenários 9525
SDK for C++ 9690
Ações e cenários 9691
Exemplos entre serviços 10236
SDK for Go V2 10238
Ações e cenários 10238
SDK para JavaScript (v2) 10563
Ações e cenários 10564
Exemplos entre serviços 10733
SDK para JavaScript (v3) 10734
Ações e cenários 10735
Exemplos entre serviços 11478
SDK para Java 2.x 11492
Ações e cenários 11492
Exemplos entre serviços 12885
SDK for Kotlin 12893
Ações e cenários 12894
Exemplos entre serviços 13332
SDK para PHP 13336
Ações e cenários 13337
Exemplos entre serviços 13495
SDK para Python (Boto3) 13497
Ações e cenários 13497
Exemplos entre serviços 14850
SDK for Ruby 14859
Ações e cenários 14859
Exemplos entre serviços 15146
SDK for Rust 15147
Ações e cenários 15147
Exemplos entre serviços 15550
SDK para SAP ABAP 15552
Ações e cenários 15553

SDK for Swift 15685
Ações e cenários 15686

Há mais exemplos de AWS SDK disponíveis no repositório AWSDoc SDK Examples GitHub .

As traduções são geradas por tradução automática. Em caso de conflito entre o conteúdo da tradução e da versão original em inglês, a versão em inglês prevalecerá.

O que é a biblioteca de exemplos de código?

A biblioteca de exemplos de código é uma coleção de exemplos de código que mostram como usar os kits de desenvolvimento de software (SDKs) da AWS com a AWS.

Os exemplos são organizados por AWS service (Serviço da AWS) e por SDK da AWS. Os mesmos exemplos podem ser encontrados em cada seção.

- Exemplos de código por serviço – Uma lista de Serviços da AWS que contém exemplos de como usar cada serviço com SDKs da AWS. Use esta seção se você souber qual serviço deseja usar.
- Exemplos de código por SDK – Uma lista de SDKs da AWS que contém exemplos de como usar Serviços da AWS com cada SDKs. Use esta seção se você souber qual SDK deseja usar.

Em cada seção, os exemplos são divididos nas seguintes categorias:

- Ações são trechos de código que mostram como chamar funções de serviço individuais.
- Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.
- Exemplos entre serviços são aplicativos de amostra que funcionam em diversos serviços da AWS.

Todos os exemplos nessa biblioteca também podem ser encontrados no repositório do GitHub de exemplos de código da AWS. O repositório do GitHub também contém instruções sobre como configurar, executar e testar os exemplos.

Usar o Serviços da AWS com um SDK da AWS

Os kits de desenvolvimento de software (SDKs) da AWS estão disponíveis para muitas linguagens de programação populares. Cada SDK fornece uma API, exemplos de código e documentação que facilitam a criação de aplicações em seu idioma preferido pelos desenvolvedores.

Documentação do SDK	Exemplos de código
AWS SDK for C++	Exemplos de código do AWS SDK for C++
AWS SDK for Go	Exemplos de código do AWS SDK for Go

Documentação do SDK	Exemplos de código
AWS SDK for Java	Exemplos de código do AWS SDK for Java
AWS SDK for JavaScript	Exemplos de código do AWS SDK for JavaScript
AWS SDK para Kotlin	Exemplos de código do AWS SDK para Kotlin
AWS SDK for .NET	Exemplos de código do AWS SDK for .NET
AWS SDK for PHP	Exemplos de código do AWS SDK for PHP
AWS SDK for Python (Boto3)	Exemplos de código do AWS SDK for Python (Boto3)
AWS SDK for Ruby	Exemplos de código do AWS SDK for Ruby
AWS SDK para Rust	Exemplos de código do AWS SDK para Rust
SDK da AWS para SAP ABAP	Exemplos de código do SDK da AWS para SAP ABAP
AWS SDK for Swift	Exemplos de código do AWS SDK for Swift

Exemplo de disponibilidade

Você não consegue encontrar o que precisa? Solicite um código de exemplo no link Fornecer feedback na parte inferior desta página.

Exemplos de código por serviço usando SDKs da AWS

Os exemplos de código a seguir mostram como usar Serviços da AWS com um kit de desenvolvimento de software (SDK) da AWS. Esta seção é organizada por AWS service (Serviço da AWS).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- AWSCentro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Exemplos de código para o ACM usando SDKs da AWS
- Exemplos de código para o API Gateway usando SDKs da AWS
- Exemplos de código para API de gerenciamento do API Gateway usando SDKs da AWS
- Exemplos de códigos para o Application Auto Scaling usando SDK da AWS
- Exemplos de código para o Application Recovery Controller usando SDKs da AWS
- Exemplos de código para o Secrets Manager usando SDKs da AWS
- Exemplos de código para o Aurora usando AWS SDKs
- Exemplos de código para Auto Scaling usando SDKs da AWS
- Exemplos de código para o AWS Batch usando AWS SDKs
- Exemplos de código para o Amazon Bedrock usando SDKs da AWS
- Exemplos de código para o Amazon Bedrock Runtime usando SDKs da AWS
- Exemplos de código para agentes do Amazon Bedrock usando SDKs AWS

- Exemplos de código para agentes do Amazon Bedrock Runtime usando SDKs AWS
- Exemplos de código para o AWS CloudFormation usando AWS SDKs
- Exemplos de código para CloudFront usar AWS SDKs
- Exemplos de código para CloudTrail usar AWS SDKs
- Exemplos de código para CloudWatch usar AWS SDKs
- Exemplos de código para CloudWatch eventos usando AWS SDKs
- Exemplos de código para CloudWatch registros usando AWS SDKs
- Exemplos de código para CodeBuild usar AWS SDKs
- Exemplos de código do Amazon Cognito Identity usando AWS SDKs
- Exemplos de código do Amazon Cognito Identity Provider usando AWS SDKs
- Exemplos de código do Amazon Cognito Sync usando AWS SDKs
- Exemplos de código do Amazon Comprehend usando SDKs da AWS
- Exemplos de código para o AWS Config usando AWS SDKs
- Exemplos de código para Device Farm usando SDKs da AWS
- Exemplos de código do DynamoDB usando AWS SDKs
- Exemplos de código para o Amazon EBS usando SDKs da AWS
- Exemplos de código para o Amazon EC2 usando AWS SDKs
- Exemplos de código para o Amazon ECR usando SDKs da AWS
- Exemplos de código para o Amazon ECS usando SDKs da AWS
- Exemplos de código para o Amazon EKS usando SDKs da AWS
- Exemplos de código para o Elastic Beanstalk usando SDKs AWS
- Exemplos de código para o Elastic Load Balancing usando SDKs da AWS
- Exemplos de código para MediaStore usar AWS SDKs
- Exemplos de código para o Amazon EMR usando SDKs da AWS
- Exemplos de código para OpenSearch serviço usando AWS SDKs
- Exemplos de código para EventBridge usar AWS SDKs
- Exemplos de código para o Forecast usando SDKs da AWS
- Exemplos de código para o AWS Glue usando AWS SDKs
- Exemplos de código para HealthImaging usar AWS SDKs
- Exemplos de código para o IAM usando AWS SDKs

- Exemplos de código para o AWS IoT usando AWS SDKs
- Exemplos de código para o AWS IoT data usando AWS SDKs
- Exemplos de código para o Amazon Keyspaces usando SDKs da AWS
- Exemplos de código para o IAM usando AWS SDKs
- Exemplos de código para Firehose usando SDKs AWS
- Exemplos de código para o AWS KMS usando AWS SDKs
- Exemplos de código do Lambda usando AWS SDKs
- Exemplos de código para o Amazon Lex usando SDKs da AWS
- Exemplos de código para o Lookout for Vision usando SDKs da AWS
- Exemplos de código para o Managed Service for Apache Flink usando SDKs da AWS
- Exemplos de código para MediaConvert usar AWS SDKs
- Exemplos de código para MediaLive usar AWS SDKs
- Exemplos de código para MediaPackage usar AWS SDKs
- Exemplos de código para o Migration Hub usando SDKs da AWS
- Exemplos de código para o Organizations usando SDKs da AWS
- Exemplos de código para o Amazon Personalize usando SDKs da AWS
- Exemplos de códigos para o Amazon Personalize Events usando SDKs da AWS
- Exemplos de código para o Amazon Personalize Runtime usando SDKs da AWS
- Exemplos de código para o Amazon Pinpoint usando AWS SDKs
- Exemplos de código para a API de SMS e voz do Amazon Pinpoint usando AWS SDKs
- Exemplos de código do Amazon Polly usando SDKs da AWS
- Exemplos de código para o QLDB usando SDKs da AWS
- Exemplos de código para o Amazon RDS usando AWS SDKs
- Exemplos de código para o Amazon RDS usando AWS SDKs
- Exemplos de código para o Amazon Redshift usando SDKs da AWS
- Exemplos de código para o Amazon Rekognition usando SDKs da AWS
- Exemplos de código para o Route 53 usando SDKs da AWS
- Exemplos de código para registro de domínios do Route 53 usando SDKs da AWS
- Exemplos de código do Amazon S3 usando SDKs da AWS
- Exemplos de código do S3 Glacier usando AWS SDKs

- Exemplos de código para SageMaker usar AWS SDKs
- Exemplos de código para o Secrets Manager usando SDKs da AWS
- Exemplos de código para o Amazon SES usando SDKs da AWS
- Exemplos de código para a API v2 do Amazon SES usando AWS SDKs
- Exemplos de código para o Amazon SNS usando AWS SDKs
- Exemplos de código para Amazon SQS usando SDKs da AWS
- Exemplos de código para Step Functions usando SDKs da AWS
- Exemplos de código para o AWS STS usando AWS SDKs
- Exemplos de código para o AWS Support usando AWS SDKs
- Exemplos de código para o Systems Manager usando SDKs da AWS
- Exemplos de código para o Amazon Textract usando SDKs da AWS
- Exemplos de código do Amazon S3 usando AWS SDKs
- Exemplos de código para o Amazon Translate usando SDKs da AWS
- Exemplos de código para a Amazon WorkDocs usando AWS SDKs

Exemplos de código para o ACM usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Certificate Manager (ACM) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do ACM – Mais informações sobre o ACM.
- Referência da API do ACM – Detalhes sobre todas as ações do ACM disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o ACM usando SDKs da AWS
  - Adicionar tags a um certificado do ACM usando um SDK da AWS
  - Exclua um certificado do ACM usando um SDK da AWS
  - Descrever um certificado do ACM usando um SDK da AWS
  - Obtenha um certificado do ACM usando um SDK da AWS
  - Importar um certificado do ACM usando um SDK da AWS
  - Listar certificados do ACM usando um SDK da AWS
  - Listar tags para um certificado do ACM usando um SDK da AWS
  - Remover tags de um certificado do ACM usando um SDK da AWS
  - Solicitar validação de um certificado do ACM usando um SDK da AWS
  - Reenviar e-mail de validação para um certificado do ACM usando um SDK da AWS
- Cenários para o ACM usando SDKs da AWS
  - Gerenciar certificados do ACM usando um SDK da AWS

Ações para o ACM usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Certificate Manager (ACM) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o ACM usando SDKs da AWS.

Exemplos

- Adicionar tags a um certificado do ACM usando um SDK da AWS
- Exclua um certificado do ACM usando um SDK da AWS
- Descrever um certificado do ACM usando um SDK da AWS
- Obtenha um certificado do ACM usando um SDK da AWS
- Importar um certificado do ACM usando um SDK da AWS
- Listar certificados do ACM usando um SDK da AWS
- Listar tags para um certificado do ACM usando um SDK da AWS
- Remover tags de um certificado do ACM usando um SDK da AWS
- Solicitar validação de um certificado do ACM usando um SDK da AWS

- Reenviar e-mail de validação para um certificado do ACM usando um SDK da AWS

Adicionar tags a um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar tags aos certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como adicionar tags a um certificado do ACM existente

O comando `add-tags-to-certificate` a seguir adiciona duas tags ao certificado especificado. Use um espaço para separar várias tags:

```
aws acm add-tags-to-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012 --
tags Key=Admin,Value=Alice Key=Purpose,Value=Website
```

- Para obter detalhes da API, consulte AddTagsToCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
```

```
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def add_tags(self, certificate_arn, tags):
        """
        Adds tags to a certificate. Tags are key-value pairs that contain custom
        metadata.

        :param certificate_arn: The ARN of the certificate.
        :param tags: A dictionary of key-value tags to add to the certificate.
        """
        try:
            self.acm_client.add_tags_to_certificate(
                CertificateArn=certificate_arn,
                Tags=[{"Key": key, "Value": value} for key, value in
tags.items()],
            )
            logger.info("Added %s tags to certificate %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't add tags to certificate %s.",
certificate_arn)
            raise
```

- Para obter detalhes da API, consulte a AddTagsToCertificateReferência da API AWSSDK for Python (Boto3).

Exclua um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como excluir um certificado do ACM da sua conta

O seguinte comando `delete-certificate` exclui o certificado com o ARN especificado:

```
aws acm delete-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012
```

- Para obter detalhes da API, consulte DeleteCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def remove(self, certificate_arn):
        """
        Removes a certificate.
```

```
        :param certificate_arn: The ARN of the certificate to remove.
        """
        try:
            self.acm_client.delete_certificate(CertificateArn=certificate_arn)
            logger.info("Removed certificate %s.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't remove certificate %s.", certificate_arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteCertificateReferência da API AWSSDK for Python (Boto3).

Descrever um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever certificados ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.CertificateManager;
using Amazon.CertificateManager.Model;
```

```
namespace DescribeCertificate
{
    class DescribeCertificate
    {
        // The following example retrieves and displays the metadata for a
        // certificate using the AWS Certificate Manager (ACM) service.

        // Specify your AWS Region (an example Region is shown).
        private static readonly RegionEndpoint ACMRegion =
 RegionEndpoint.USEast1;
        private static AmazonCertificateManagerClient _client;

        static void Main(string[] args)
        {
            _client = new
 Amazon.CertificateManager.AmazonCertificateManagerClient(ACMRegion);

            var describeCertificateReq = new DescribeCertificateRequest();
            // The ARN used here is just an example. Replace it with the ARN of
            // a certificate that exists on your account.
            describeCertificateReq.CertificateArn =
                "arn:aws:acm:us-
east-1:123456789012:certificate/8cfd7dae-9b6a-2d07-92bc-1c309EXAMPLE";

            var certificateDetailResp =
                DescribeCertificateResponseAsync(client: _client, request:
 describeCertificateReq);
            var certificateDetail = certificateDetailResp.Result.Certificate;

            if (certificateDetail is not null)
            {
                DisplayCertificateDetails(certificateDetail);
            }
        }

        /// <summary>
        /// Displays detailed metadata about a certificate retrieved
        /// using the ACM service.
        /// </summary>
        /// <param name="certificateDetail">The object that contains details
        /// returned from the call to DescribeCertificateAsync.</param>
        static void DisplayCertificateDetails(CertificateDetail
 certificateDetail)
        {
```

```
            Console.WriteLine("\nCertificate Details: ");
            Console.WriteLine($"Certificate Domain:
{certificateDetail.DomainName}");
            Console.WriteLine($"Certificate Arn:
{certificateDetail.CertificateArn}");
            Console.WriteLine($"Certificate Subject:
{certificateDetail.Subject}");
            Console.WriteLine($"Certificate Status: {certificateDetail.Status}");
            foreach (var san in certificateDetail.SubjectAlternativeNames)
            {
                Console.WriteLine($"Certificate SubjectAlternativeName: {san}");
            }
        }

        /// <summary>
        /// Retrieves the metadata associated with the ACM service certificate.
        /// </summary>
        /// <param name="client">An AmazonCertificateManagerClient object
        /// used to call DescribeCertificateResponse.</param>
        /// <param name="request">The DescribeCertificateRequest object that
        /// will be passed to the method call.</param>
        /// <returns></returns>
        static async Task<DescribeCertificateResponse>
DescribeCertificateResponseAsync(
            AmazonCertificateManagerClient client, DescribeCertificateRequest
request)
        {
            var response = new DescribeCertificateResponse();

            try
            {
                response = await client.DescribeCertificateAsync(request);
            }
            catch (InvalidArnException)
            {
                Console.WriteLine($"Error: The ARN specified is invalid.");
            }
            catch (ResourceNotFoundException)
            {
                Console.WriteLine($"Error: The specified certificate could not be
found.");
            }

            return response;
```

```
        }
    }

}
```

- Para obter detalhes da API, consulte DescribeCertificatea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como recuperar os campos contidos em um certificado do ACM

O seguinte comando `describe-certificate` recupera todos os campos do certificado com o ARN especificado:

```
aws acm describe-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012
```

Uma saída semelhante à seguinte é exibida:

```
{
  "Certificate": {
    "CertificateArn":
 "arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012",
    "CreatedAt": 1446835267.0,
    "DomainName": "www.example.com",
    "DomainValidationOptions": [
      {
        "DomainName": "www.example.com",
        "ValidationDomain": "www.example.com",
        "ValidationEmails": [
          "hostmaster@example.com",
          "admin@example.com",
          "owner@example.com.whoisprivacyservice.org",
          "tech@example.com.whoisprivacyservice.org",
          "admin@example.com.whoisprivacyservice.org",
          "postmaster@example.com",
```

```
          "webmaster@example.com",
          "administrator@example.com"
        ]
      },
      {
        "DomainName": "www.example.net",
        "ValidationDomain": "www.example.net",
        "ValidationEmails": [
          "postmaster@example.net",
          "admin@example.net",
          "owner@example.net.whoisprivacyservice.org",
          "tech@example.net.whoisprivacyservice.org",
          "admin@example.net.whoisprivacyservice.org",
          "hostmaster@example.net",
          "administrator@example.net",
          "webmaster@example.net"
        ]
      }
    ],
    "InUseBy": [],
    "IssuedAt": 1446835815.0,
    "Issuer": "Amazon",
    "KeyAlgorithm": "RSA-2048",
    "NotAfter": 1478433600.0,
    "NotBefore": 1446768000.0,
    "Serial": "0f:ac:b0:a3:8d:ea:65:52:2d:7d:01:3a:39:36:db:d6",
    "SignatureAlgorithm": "SHA256WITHRSA",
    "Status": "ISSUED",
    "Subject": "CN=www.example.com",
    "SubjectAlternativeNames": [
      "www.example.com",
      "www.example.net"
    ]
  }
}
```

- Para obter detalhes da API, consulte DescribeCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def describe(self, certificate_arn):
        """
        Gets certificate metadata.

        :param certificate_arn: The Amazon Resource Name (ARN) of the
 certificate.
        :return: Metadata about the certificate.
        """
        try:
            response = self.acm_client.describe_certificate(
                CertificateArn=certificate_arn
            )
            certificate = response["Certificate"]
            logger.info(
                "Got metadata for certificate for domain %s.",
 certificate["DomainName"]
            )
        except ClientError:
            logger.exception("Couldn't get data for certificate %s.",
 certificate_arn)
```

```
            raise
        else:
            return certificate
```

- Para obter detalhes da API, consulte a DescribeCertificateReferência da API AWSSDK for Python (Boto3).

Obtenha um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como obter certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como recuperar um certificado do ACM

O seguinte comando `get-certificate` recupera o certificado para o ARN especificado e a cadeia de certificados:

```
aws acm get-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012
```

Uma saída semelhante à seguinte é exibida:


```
{
  "Certificate": "-----BEGIN CERTIFICATE-----
MIICiTCCAfICCQD6m7oRw0uXOjANBgkqhkiG9w0BAQUFADCBiDELMAkGA1UEBhMC
VVMxCzAJBgNVBAgTAldBMRAwDgYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6
b24xFDASBgNVBAsTC0lBTSBDb25zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAd
BgkqhkiG9w0BCQEWEG5vb25lQGFtYXpvbi5jb20wHhcNMTEwNDI1MjA0NTIxWhcN
MTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgTAldBMRAwDgYD
VQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAsTC0lBTSBDb25z
b2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQEWEG5vb25lQGFt
```

```
YXpvbi5jb20wgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAMaK0dn+a4GmWIWJ
21uUSfwfEvySWtC2XADZ4nB+BLYgVIk60CpiwsZ3G93vUEIO3IyNoH/f0wYK8m9T
rDHudUZg3qX4waLG5M43q7Wgc/MbQITxOUSQv7c7ugFFDzQGBzZswY6786m86gpE
Ibb3OhjZnzcvQAaRHhdlQWIMm2nrAgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCu4
nUhVVxYUntneD9+h8Mg9q6q+auNKyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0Fkb
FFBjvSfpJIlJ00zbhNYS5f6GuoEDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjSTb
NYiytVbZPQUQ5Yaxu2jXnimvw3rrszlaEXAMPLE=
-----END CERTIFICATE-----",

  "CertificateChain": "-----BEGIN CERTIFICATE-----
MIICiTCCAfICCQD6m7oRw0uXOjANBgkqhkiG9w0BAQUFADCBiDELMAkGA1UEBhMC
VVMxCzAJBgNVBAgTAldBMRAwDgYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6
b24xFDASBgNVBAsTC0lBTSBDb25zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAd
BgkqhkiG9w0BCQEWEG5vb25lQGFtYXpvbi5jb20wHhcNMTEwNDI1MjA0NTIxWhcN
MTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgTAldBMRAwDgYD
VQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAsTC0lBTSBDb25z
b2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQEWEG5vb25lQGFt
YXpvbi5jb20wgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAMaK0dn+a4GmWIWJ
21uUSfwfEvySWtC2XADZ4nB+BLYgVIk60CpiwsZ3G93vUEIO3IyNoH/f0wYK8m9T
rDHudUZg3qX4waLG5M43q7Wgc/MbQITxOUSQv7c7ugFFDzQGBzZswY6786m86gpE
Ibb3OhjZnzcvQAaRHhdlQWIMm2nrAgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCu4
nUhVVxYUntneD9+h8Mg9q6q+auNKyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0Fkb
FFBjvSfpJIlJ00zbhNYS5f6GuoEDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjSTb
NYiytVbZPQUQ5Yaxu2jXnimvw3rrszlaEXAMPLE=
-----END CERTIFICATE-----",
"-----BEGIN CERTIFICATE-----
MIICiTCCAfICCQD6m7oRw0uXOjANBgkqhkiG9w0BAQUFADCBiDELMAkGA1UEBhMC
VVMxCzAJBgNVBAgTAldBMRAwDgYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6
b24xFDASBgNVBAsTC0lBTSBDb25zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAd
BgkqhkiG9w0BCQEWEG5vb25lQGFtYXpvbi5jb20wHhcNMTEwNDI1MjA0NTIxWhcN
MTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgTAldBMRAwDgYD
VQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAsTC0lBTSBDb25z
b2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQEWEG5vb25lQGFt
YXpvbi5jb20wgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAMaK0dn+a4GmWIWJ
21uUSfwfEvySWtC2XADZ4nB+BLYgVIk60CpiwsZ3G93vUEIO3IyNoH/f0wYK8m9T
rDHudUZg3qX4waLG5M43q7Wgc/MbQITxOUSQv7c7ugFFDzQGBzZswY6786m86gpE
Ibb3OhjZnzcvQAaRHhdlQWIMm2nrAgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCu4
nUhVVxYUntneD9+h8Mg9q6q+auNKyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0Fkb
FFBjvSfpJIlJ00zbhNYS5f6GuoEDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjSTb
NYiytVbZPQUQ5Yaxu2jXnimvw3rrszlaEXAMPLE=
-----END CERTIFICATE-----",
"-----BEGIN CERTIFICATE-----
MIICiTCCAfICCQD6m7oRw0uXOjANBgkqhkiG9w0BAQUFADCBiDELMAkGA1UEBhMC
VVMxCzAJBgNVBAgTAldBMRAwDgYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6
```

```
b24xFDASBgNVBAsTC0lBTSBDb25zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAd
BgkqhkiG9w0BCQEWEG5vb25lQGFtYXpvbi5jb20wHhcNMTEwNDI1MjA0NTIxWhcN
MTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgTAldBMRAwDgYD
VQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAsTC0lBTSBDb25z
b2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQEWEG5vb25lQGFt
YXpvbi5jb20wgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAMaK0dn+a4GmWIWJ
21uUSfwfEvySWtC2XADZ4nB+BLYgVIk60CpiwsZ3G93vUEIO3IyNoH/f0wYK8m9T
rDHudUZg3qX4waLG5M43q7Wgc/MbQITxOUSQv7c7ugFFDzQGBzZswY6786m86gpE
Ibb3OhjZnzcvQAaRHhdlQWIMm2nrAgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCu4
nUhVVxYUntneD9+h8Mg9q6q+auNKyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0Fkb
FFBjvSfpJIlJ00zbhNYS5f6GuoEDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjSTb
NYiytVbZPQUQ5Yaxu2jXnimvw3rrszlaEXAMPLE=
-----END CERTIFICATE-----"
}
```


- Para obter detalhes da API, consulte GetCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def get(self, certificate_arn):
        """
        Gets the body and certificate chain of a certificate.
```

```
        :param certificate_arn: The ARN of the certificate.
        :return: The body and chain of a certificate.
        """
        try:
            response =
self.acm_client.get_certificate(CertificateArn=certificate_arn)
            logger.info("Got certificate %s and its chain.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't get certificate %s.", certificate_arn)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetCertificateReferência da API AWSSDK for Python (Boto3).

Importar um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como importar certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como importar um certificado para o ACM.

O comando `import-certificate` a seguir importa um certificado para o ACM. Substitua os nomes dos arquivos pelos seus próprios:

```
aws acm import-certificate --certificate file://Certificate.pem --certificate-
chain file://CertificateChain.pem --private-key file://PrivateKey.pem
```

- Para obter detalhes da API, consulte ImportCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def import_certificate(self, certificate_body, private_key):
        """
        Imports a self-signed certificate to ACM.

        :param certificate_body: The body of the certificate, in PEM format.
        :param private_key: The unencrypted private key of the certificate, in
 PEM
                            format.
        :return: The ARN of the imported certificate.
        """
        try:
            response = self.acm_client.import_certificate(
                Certificate=certificate_body, PrivateKey=private_key
            )
            certificate_arn = response["CertificateArn"]
            logger.info("Imported certificate.")
```

```
        except ClientError:
            logger.exception("Couldn't import certificate.")
            raise
        else:
            return certificate_arn
```

- Para obter detalhes da API, consulte a ImportCertificateReferência da API AWSSDK for Python (Boto3).

Listar certificados do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como listar certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.CertificateManager;
using Amazon.CertificateManager.Model;

namespace ListCertificates
{
    // The following example retrieves and displays a list of the
```

```
    // certificates defined for the default account using the AWS
    // Certificate Manager (ACM) service.
    class ListCertificates
    {
        // Specify your AWS Region (an example Region is shown).

        private static readonly RegionEndpoint ACMRegion =
RegionEndpoint.USEast1;
        private static AmazonCertificateManagerClient _client;

        static void Main(string[] args)
        {
            _client = new AmazonCertificateManagerClient(ACMRegion);
            var certificateList = ListCertificatesResponseAsync(client: _client);

            Console.WriteLine("Certificate Summary List\n");

            foreach (var certificate in
certificateList.Result.CertificateSummaryList)
            {
                Console.WriteLine($"Certificate Domain:
{certificate.DomainName}");
                Console.WriteLine($"Certificate ARN:
{certificate.CertificateArn}\n");
            }
        }

        /// <summary>
        /// Retrieves a list of the certificates defined in this Region.
        /// </summary>
        /// <param name="client">The ACM client object passed to the
        /// ListCertificateResAsync method call.</param>
        /// <param name="request"></param>
        /// <returns>The ListCertificatesResponse.</returns>
        static async Task<ListCertificatesResponse>
ListCertificatesResponseAsync(
            AmazonCertificateManagerClient client)
        {
            var request = new ListCertificatesRequest();

            var response = await client.ListCertificatesAsync(request);
            return response;
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte ListCertificatesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os certificados do ACM em uma conta da AWS

O seguinte comando `list-certificates` lista os ARNs dos certificados na conta:

```
aws acm list-certificates
```

O comando anterior produz uma saída semelhante à seguinte:

```
{
    "CertificateSummaryList": [
        {
            "CertificateArn":
 "arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012",
            "DomainName": "www.example.com"
        },
        {
            "CertificateArn": "arn:aws:acm:region:account:certificate/aaaaaaaa-
bbbb-cccc-dddd-eeeeeeeeeeee",
            "DomainName": "www.example.net"
        }
    ]
}
```

Você pode decidir quantos certificados deseja exibir sempre que chamar `list-certificates`. Por exemplo, se você tem quatro certificados e deseja exibir apenas dois por vez, defina o argumento `max-items` como 2, conforme o seguinte exemplo:

```
aws acm list-certificates --max-items 2
```

Dois ARNs de certificado e um valor `NextToken` serão exibidos:

```
"CertificateSummaryList": [
  {
    "CertificateArn": "arn:aws:acm:region:account: \
            certificate/12345678-1234-1234-1234-123456789012",
    "DomainName": "www.example.com"
  },
  {
    "CertificateArn": "arn:aws:acm:region:account: \
             certificate/aaaaaaaa-bbbb-cccc-dddd-eeeeeeeeeeee",
    "DomainName": "www.example.net"
  }
  ],
    "NextToken": "9f4d9f69-275a-41fe-b58e-2b837bd9ba48"
```

Para exibir os próximos dois certificados em sua conta, defina o valor `NextToken` na próxima chamada:

```
aws acm list-certificates --max-items 2 --next-token 9f4d9f69-275a-41fe-
b58e-2b837bd9ba48
```

É possível filtrar a saída usando o argumento `certificate-statuses`. O seguinte comando exibe certificados com o status PENDING_VALIDATION:

```
aws acm list-certificates --certificate-statuses PENDING_VALIDATION
```

Também é possível filtrar a saída usando o argumento `includes`. O comando a seguir exibe os certificados filtrados nas propriedades a seguir. Os certificados a serem exibidos:

```
- Specify that the RSA algorithm and a 2048 bit key are used to generate key
 pairs.
- Contain a Key Usage extension that specifies that the certificates can be used
 to create digital signatures.
- Contain an Extended Key Usage extension that specifies that the certificates
 can be used for code signing.

aws acm list-certificates --max-items 10 --includes
 extendedKeyUsage=CODE_SIGNING,keyUsage=DIGITAL_SIGNATURE,keyTypes=RSA_2048
```

- Para obter detalhes da API, consulte ListCertificatesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def list(
        self,
        max_items,
        statuses=None,
        key_usage=None,
        extended_key_usage=None,
        key_types=None,
    ):
        """
        Lists the certificates for the current account.

        :param max_items: The maximum number of certificates to list.
        :param statuses: Filters the results to the specified statuses. If None,
 all
                         certificates are included.
        :param key_usage: Filters the results to the specified key usages. If
 None,
                          all key usages are included.
        :param extended_key_usage: Filters the results to the specified extended
 key
```

```
                                    usages. If None, all extended key usages are
                                    included.
        :param key_types: Filters the results to the specified key types. If
None, all
                          key types are included.
        :return: The list of certificates.
        """
        try:
            kwargs = {"MaxItems": max_items}
            if statuses is not None:
                kwargs["CertificateStatuses"] = statuses
            includes = {}
            if key_usage is not None:
                includes["keyUsage"] = key_usage
            if extended_key_usage is not None:
                includes["extendedKeyUsage"] = extended_key_usage
            if key_types is not None:
                includes["keyTypes"] = key_types
            if includes:
                kwargs["Includes"] = includes
            response = self.acm_client.list_certificates(**kwargs)
            certificates = response["CertificateSummaryList"]
            logger.info("Got %s certificates.", len(certificates))
        except ClientError:
            logger.exception("Couldn't get certificates.")
            raise
        else:
            return certificates
```

- Para obter detalhes da API, consulte a ListCertificatesReferência da API AWSSDK for Python (Boto3).

Listar tags para um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como listar tags para certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como listar as tags aplicadas a um certificado do ACM

O seguinte comando `list-tags-for-certificate` lista as tags aplicadas a um certificado na conta:

```
aws acm list-tags-for-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012
```

O comando anterior produz uma saída semelhante à seguinte:

```
{
  "Tags": [
      {
          "Value": "Website",
          "Key": "Purpose"
      },
      {
          "Value": "Alice",
          "Key": "Admin"
      }
  ]
}
```

- Para obter detalhes da API, consulte ListTagsForCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
```

```
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def list_tags(self, certificate_arn):
        """
        Lists the tags attached to a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The dictionary of certificate tags.
        """
        try:
            response = self.acm_client.list_tags_for_certificate(
                CertificateArn=certificate_arn
            )
            tags = {tag["Key"]: tag["Value"] for tag in response["Tags"]}
            logger.info("Got %s tags for certificates %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't get tags for certificate %s.",
certificate_arn)
            raise
        else:
            return tags
```

- Para obter detalhes da API, consulte a ListTagsForCertificateReferência da API AWSSDK for Python (Boto3).

Remover tags de um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como remover tags de certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como remover uma tag de um certificado do ACM

O comando `remove-tags-from-certificate` a seguir remove duas tags do certificado especificado. Use um espaço para separar várias tags:

```
aws acm remove-tags-from-certificate --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012 --
tags Key=Admin,Value=Alice Key=Purpose,Value=Website
```

- Para obter detalhes da API, consulte RemoveTagsFromCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
```

```
        """
        self.acm_client = acm_client


    def remove_tags(self, certificate_arn, tags):
        """
        Removes tags from a certificate. If the value of a tag is specified, the
tag is
        removed only when the value matches the value of the certificate's tag.
        Otherwise, the tag is removed regardless of its value.

        :param certificate_arn: The ARN of the certificate.
        :param tags: The dictionary of tags to remove.
        """
        try:
            cert_tags = []
            for key, value in tags.items():
                tag = {"Key": key}
                if value is not None:
                    tag["Value"] = value
                cert_tags.append(tag)
            self.acm_client.remove_tags_from_certificate(
                CertificateArn=certificate_arn, Tags=cert_tags
            )
            logger.info(
                "Removed %s tags from certificate %s.", len(tags),
certificate_arn
            )
        except ClientError:
            logger.exception(
                "Couldn't remove tags from certificate %s.", certificate_arn
            )
            raise
```

- Para obter detalhes da API, consulte a RemoveTagsFromCertificateReferência da API AWSSDK for Python (Boto3).

Solicitar validação de um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como solicitar a validação de certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como solicitar um novo certificado do ACM

O seguinte comando `request-certificate` solicita um novo certificado para o domínio www.example.com usando a validação de DNS:

```
aws acm request-certificate --domain-name www.example.com --validation-method DNS
```

Você pode inserir um token de idempotência para distinguir entre chamadas para `request-certificate`:

```
aws acm request-certificate --domain-name www.example.com --validation-method DNS
 --idempotency-token 91adc45q
```

Você pode inserir um ou mais nomes alternativos de assunto para solicitar um certificado que protegerá mais de um domínio do apex:

```
aws acm request-certificate --domain-name example.com --validation-method DNS --
idempotency-token 91adc45q --subject-alternative-names www.example.net
```

Você pode inserir um nome alternativo que também pode ser usado para acessar seu site:

```
aws acm request-certificate --domain-name example.com --validation-method DNS --
idempotency-token 91adc45q --subject-alternative-names www.example.com
```

Você pode usar um asterisco (*) como um caractere curinga para criar um certificado para vários subdomínios no mesmo domínio:

```
aws acm request-certificate --domain-name example.com --validation-method DNS --
idempotency-token 91adc45q --subject-alternative-names *.example.com
```

Você também pode inserir vários nomes alternativos:

```
aws acm request-certificate --domain-name example.com --validation-method DNS --
subject-alternative-names b.example.com c.example.com d.example.com
```

Se você estiver usando e-mail para validação, poderá inserir as opções de validação de domínio para especificar o domínio para o qual o e-mail de validação será enviado:

```
aws acm request-certificate --domain-name example.com --validation-method
 EMAIL --subject-alternative-names www.example.com --domain-validation-options
 DomainName=example.com,ValidationDomain=example.com
```

O seguinte comando desativa o registro em log de transparência do certificado ao solicitar um novo certificado:

```
aws acm request-certificate --domain-name www.example.com --validation-method DNS
 --options CertificateTransparencyLoggingPreference=DISABLED --idempotency-token
 184627
```

- Para obter detalhes da API, consulte RequestCertificateem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
```

```
        self.acm_client = acm_client


    def request_validation(
        self, domain, alternate_domains, method, validation_domains=None
    ):
        """
        Starts a validation request that results in a new certificate being
issued
        by ACM. DNS validation requires that you add CNAME records to your DNS
        provider. Email validation sends email to a list of email addresses that
        are associated with the domain.

        For more information, see _Issuing and managing certificates_ in the ACM
        user guide.
            https://docs.aws.amazon.com/acm/latest/userguide/gs.html

        :param domain: The primary domain to associate with the certificate.
        :param alternate_domains: Subject Alternate Names (SANs) for the
certificate.
        :param method: The validation method, either DNS or EMAIL.
        :param validation_domains: Alternate domains to use for email validation,
when
                                   the email domain differs from the primary
domain of
                                   the certificate.
        :return: The ARN of the requested certificate.
        """
        try:
            kwargs = {
                "DomainName": domain,
                "ValidationMethod": method,
                "SubjectAlternativeNames": alternate_domains,
            }
            if validation_domains is not None:
                kwargs["DomainValidationOptions"] = [
                    {"DomainName": key, "ValidationDomain": value}
                    for key, value in validation_domains.items()
                ]
            response = self.acm_client.request_certificate(**kwargs)
            certificate_arn = response["CertificateArn"]
            logger.info(
                "Requested %s validation for domain %s. Certificate ARN is %s.",
                method,
```

```
                domain,
                certificate_arn,
            )
        except ClientError:
            logger.exception(
                "Request for %s validation of domain %s failed.", method, domain
            )
            raise
        else:
            return certificate_arn
```

- Para obter detalhes da API, consulte a RequestCertificateReferência da API AWSSDK for Python (Boto3).

Reenviar e-mail de validação para um certificado do ACM usando um SDK da AWS

Os exemplos de código a seguir mostram como reenviar um e-mail de validação de certificados do ACM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar certificados

CLI

AWS CLI

Como reenviar o e-mail de validação para a solicitação de certificado do ACM

O seguinte `resend-validation-email` comando instrui a autoridade de certificação da Amazon a enviar e-mails de validação para os endereços apropriados:

```
aws acm resend-validation-email --certificate-arn
 arn:aws:acm:region:account:certificate/12345678-1234-1234-1234-123456789012 --
domain www.example.com --validation-domain example.com
```

- Para obter detalhes da API, consulte ResendValidationEmailem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def resend_validation_email(self, certificate_arn, domain,
 validation_domain):
        """
        Request that validation email is sent again, for a certificate that was
        previously requested with email validation.

        :param certificate_arn: The ARN of the certificate.
        :param domain: The primary domain of the certificate.
        :param validation_domain: Alternate domain to use for determining email
                                  addresses to use for validation.
        """
        try:
            self.acm_client.resend_validation_email(
                CertificateArn=certificate_arn,
                Domain=domain,
                ValidationDomain=validation_domain,
            )
            logger.info(
                "Validation email resent to validation domain %s.",
 validation_domain
```

```
            )
        except ClientError:
            logger.exception(
                "Couldn't resend validation email to %s.", validation_domain
            )
            raise
```

- Para obter detalhes da API, consulte a ResendValidationEmailReferência da API AWSSDK for Python (Boto3).

Cenários para o ACM usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Certificate Manager (ACM) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Gerenciar certificados do ACM usando um SDK da AWS

Gerenciar certificados do ACM usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Solicitar um certificado do ACM.
- Importar um certificado auto-assinado.
- Listar e descrever certificados.
- Remover certificados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as operações do ACM.

```
import logging
from pprint import pprint

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def request_validation(
        self, domain, alternate_domains, method, validation_domains=None
    ):
        """
        Starts a validation request that results in a new certificate being
 issued
        by ACM. DNS validation requires that you add CNAME records to your DNS
        provider. Email validation sends email to a list of email addresses that
        are associated with the domain.
```

```
        For more information, see _Issuing and managing certificates_ in the ACM
        user guide.
            https://docs.aws.amazon.com/acm/latest/userguide/gs.html

        :param domain: The primary domain to associate with the certificate.
        :param alternate_domains: Subject Alternate Names (SANs) for the
certificate.
        :param method: The validation method, either DNS or EMAIL.
        :param validation_domains: Alternate domains to use for email validation,
when
                                   the email domain differs from the primary
domain of
                                   the certificate.
        :return: The ARN of the requested certificate.
        """
        try:
            kwargs = {
                "DomainName": domain,
                "ValidationMethod": method,
                "SubjectAlternativeNames": alternate_domains,
            }
            if validation_domains is not None:
                kwargs["DomainValidationOptions"] = [
                    {"DomainName": key, "ValidationDomain": value}
                    for key, value in validation_domains.items()
                ]
            response = self.acm_client.request_certificate(**kwargs)
            certificate_arn = response["CertificateArn"]
            logger.info(
                "Requested %s validation for domain %s. Certificate ARN is %s.",
                method,
                domain,
                certificate_arn,
            )
        except ClientError:
            logger.exception(
                "Request for %s validation of domain %s failed.", method, domain
            )
            raise
        else:
            return certificate_arn


    def import_certificate(self, certificate_body, private_key):
```

```
        """
        Imports a self-signed certificate to ACM.

        :param certificate_body: The body of the certificate, in PEM format.
        :param private_key: The unencrypted private key of the certificate, in
PEM
                            format.
        :return: The ARN of the imported certificate.
        """
        try:
            response = self.acm_client.import_certificate(
                Certificate=certificate_body, PrivateKey=private_key
            )
            certificate_arn = response["CertificateArn"]
            logger.info("Imported certificate.")
        except ClientError:
            logger.exception("Couldn't import certificate.")
            raise
        else:
            return certificate_arn


    def list(
        self,
        max_items,
        statuses=None,
        key_usage=None,
        extended_key_usage=None,
        key_types=None,
    ):
        """
        Lists the certificates for the current account.

        :param max_items: The maximum number of certificates to list.
        :param statuses: Filters the results to the specified statuses. If None,
all
                         certificates are included.
        :param key_usage: Filters the results to the specified key usages. If
None,
                          all key usages are included.
        :param extended_key_usage: Filters the results to the specified extended
key
                                   usages. If None, all extended key usages are
                                   included.
```

```
        :param key_types: Filters the results to the specified key types. If
None, all
                          key types are included.
        :return: The list of certificates.
        """
        try:
            kwargs = {"MaxItems": max_items}
            if statuses is not None:
                kwargs["CertificateStatuses"] = statuses
            includes = {}
            if key_usage is not None:
                includes["keyUsage"] = key_usage
            if extended_key_usage is not None:
                includes["extendedKeyUsage"] = extended_key_usage
            if key_types is not None:
                includes["keyTypes"] = key_types
            if includes:
                kwargs["Includes"] = includes
            response = self.acm_client.list_certificates(**kwargs)
            certificates = response["CertificateSummaryList"]
            logger.info("Got %s certificates.", len(certificates))
        except ClientError:
            logger.exception("Couldn't get certificates.")
            raise
        else:
            return certificates


    def describe(self, certificate_arn):
        """
        Gets certificate metadata.

        :param certificate_arn: The Amazon Resource Name (ARN) of the
certificate.
        :return: Metadata about the certificate.
        """
        try:
            response = self.acm_client.describe_certificate(
                CertificateArn=certificate_arn
            )
            certificate = response["Certificate"]
            logger.info(
                "Got metadata for certificate for domain %s.",
certificate["DomainName"]
```

```
            )
        except ClientError:
            logger.exception("Couldn't get data for certificate %s.",
certificate_arn)
            raise
        else:
            return certificate


    def get(self, certificate_arn):
        """
        Gets the body and certificate chain of a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The body and chain of a certificate.
        """
        try:
            response =
self.acm_client.get_certificate(CertificateArn=certificate_arn)
            logger.info("Got certificate %s and its chain.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't get certificate %s.", certificate_arn)
            raise
        else:
            return response


    def add_tags(self, certificate_arn, tags):
        """
        Adds tags to a certificate. Tags are key-value pairs that contain custom
        metadata.

        :param certificate_arn: The ARN of the certificate.
        :param tags: A dictionary of key-value tags to add to the certificate.
        """
        try:
            self.acm_client.add_tags_to_certificate(
                CertificateArn=certificate_arn,
                Tags=[{"Key": key, "Value": value} for key, value in
tags.items()],
            )
            logger.info("Added %s tags to certificate %s.", len(tags),
certificate_arn)
        except ClientError:
```

```
            logger.exception("Couldn't add tags to certificate %s.",
certificate_arn)
            raise


    def list_tags(self, certificate_arn):
        """
        Lists the tags attached to a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The dictionary of certificate tags.
        """
        try:
            response = self.acm_client.list_tags_for_certificate(
                CertificateArn=certificate_arn
            )
            tags = {tag["Key"]: tag["Value"] for tag in response["Tags"]}
            logger.info("Got %s tags for certificates %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't get tags for certificate %s.",
certificate_arn)
            raise
        else:
            return tags


    def remove_tags(self, certificate_arn, tags):
        """
        Removes tags from a certificate. If the value of a tag is specified, the
tag is
        removed only when the value matches the value of the certificate's tag.
        Otherwise, the tag is removed regardless of its value.

        :param certificate_arn: The ARN of the certificate.
        :param tags: The dictionary of tags to remove.
        """
        try:
            cert_tags = []
            for key, value in tags.items():
                tag = {"Key": key}
                if value is not None:
                    tag["Value"] = value
                cert_tags.append(tag)
```

```
            self.acm_client.remove_tags_from_certificate(
                CertificateArn=certificate_arn, Tags=cert_tags
            )
            logger.info(
                "Removed %s tags from certificate %s.", len(tags),
 certificate_arn
            )
        except ClientError:
            logger.exception(
                "Couldn't remove tags from certificate %s.", certificate_arn
            )
            raise


    def remove(self, certificate_arn):
        """
        Removes a certificate.

        :param certificate_arn: The ARN of the certificate to remove.
        """
        try:
            self.acm_client.delete_certificate(CertificateArn=certificate_arn)
            logger.info("Removed certificate %s.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't remove certificate %s.", certificate_arn)
            raise
```

Usar a classe wrapper para gerenciar certificados para uma conta.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the AWS Certificate Manager (ACM) demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    acm_certificate = AcmCertificate(boto3.client("acm"))
    domain = "example.com"
    sub_domains = [f"{sub}.{domain}" for sub in ["test", "dev"]]
    print(f"Request a certificate for {domain}.")
```

```
    certificate_arn = acm_certificate.request_validation(domain, sub_domains,
"DNS")
    print(f"Started validation, got certificate ARN: {certificate_arn}.")

    import_cert_arn = None
    cert_file_name = input(
        "Enter the file name for a self-signed certificate in PEM format. "
        "This certificate will be imported to ACM. Press Enter to skip: "
    )
    if cert_file_name:
        pk_file_name = input(
            "Enter the file name for the unencrypted private key of the
certificate. "
            "This file must also be in PEM format: "
        )
        if pk_file_name:
            with open(cert_file_name, "rb") as cert_file:
                import_cert = cert_file.read()
            with open(pk_file_name, "rb") as pk_file:
                import_pk = pk_file.read()
            import_cert_arn = acm_certificate.import_certificate(import_cert,
import_pk)
            print(f"Certificate imported, got ARN: {import_cert_arn}")
        else:
            print("No private key file entered. Skipping certificate import.")
    else:
        print("Skipping self-signed certificate import.")

    print("Getting the first 10 issued certificates.")
    certificates = acm_certificate.list(10, statuses=["ISSUED"])
    print(f"Found {len(certificates)} issued certificates.")

    print(f"Getting metadata for certificate {certificate_arn}")
    cert_metadata = acm_certificate.describe(certificate_arn)
    pprint(cert_metadata)

    if import_cert_arn is not None:
        print(f"Getting certificate for imported certificate {import_cert_arn}")
        import_cert_data = acm_certificate.get(import_cert_arn)
        pprint(import_cert_data)

    print(f"Adding tags to certificate {certificate_arn}.")
    acm_certificate.add_tags(certificate_arn, {"purpose": "acm demo", "color":
"green"})
```

```
    tags = acm_certificate.list_tags(certificate_arn)
    print(f"Found tags: {tags}")
    acm_certificate.remove_tags(certificate_arn, {key: None for key in tags})
    print("Removed tags.")

    print("Removing certificates added during the demo.")
    acm_certificate.remove(certificate_arn)
    if import_cert_arn is not None:
        acm_certificate.remove(import_cert_arn)

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AddTagsToCertificate
  - DeleteCertificate
  - DescribeCertificate
  - GetCertificate
  - ImportCertificate
  - ListCertificates
  - ListTagsForCertificate
  - RemoveTagsFromCertificate
  - RequestCertificate
  - ResendValidationEmail

Exemplos de código para o API Gateway usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon API Gateway com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do API Gateway – Mais informações sobre o API Gateway.
- Referência da API do API Gateway – Detalhes sobre todas as ações disponíveis do API Gateway.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o API Gateway usando SDKs da AWS
  - Adicione uma resposta de um serviço da AWS integrado a um método do API Gateway usando um SDK da AWS
  - Adicione um método HTTP a um recurso REST do API Gateway usando um SDK da AWS
  - Adicione uma resposta HTTP a um recurso REST do API Gateway usando um SDK da AWS
  - Implante uma API REST do API Gateway usando um SDK da AWS
  - Crie um recurso REST do API Gateway usando um SDK da AWS
  - Exclua uma API REST do API Gateway usando um SDK da AWS
  - Exclua uma implantação do API Gateway usando um SDK da AWS
  - Implante uma API REST do API Gateway usando um SDK da AWS
  - Obtenha recursos REST do API Gateway usando um SDK da AWS
  - Obtenha o mapeamento do caminho base para um nome de domínio personalizado no API Gateway
  - Integre um método do API Gateway a um serviço da AWS usando um SDK da AWS
  - Liste APIs REST do API Gateway usando um SDK da AWS
  - Liste o mapeamento do caminho base para um nome de domínio personalizado no API Gateway
  - Atualize o mapeamento do caminho base para um nome de domínio personalizado no API Gateway
- Cenários para o API Gateway usando SDKs da AWS

- Crie e implante uma API REST usando um SDK da AWS
- Exemplos de entre serviços para API Gateway usando SDKs AWS
  - Criar uma API REST do API Gateway para monitorar dados da COVID-19
  - Criar uma API REST de biblioteca de empréstimos
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Criar uma aplicação de chat websocket com o API Gateway
  - Usar o API Gateway para invocar uma função do Lambda

Ações para o API Gateway usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon API Gateway com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o API Gateway usando SDKs da AWS.

Exemplos

- Adicione uma resposta de um serviço da AWS integrado a um método do API Gateway usando um SDK da AWS
- Adicione um método HTTP a um recurso REST do API Gateway usando um SDK da AWS
- Adicione uma resposta HTTP a um recurso REST do API Gateway usando um SDK da AWS
- Implante uma API REST do API Gateway usando um SDK da AWS
- Crie um recurso REST do API Gateway usando um SDK da AWS
- Exclua uma API REST do API Gateway usando um SDK da AWS
- Exclua uma implantação do API Gateway usando um SDK da AWS
- Implante uma API REST do API Gateway usando um SDK da AWS
- Obtenha recursos REST do API Gateway usando um SDK da AWS
- Obtenha o mapeamento do caminho base para um nome de domínio personalizado no API Gateway
- Integre um método do API Gateway a um serviço da AWS usando um SDK da AWS
- Liste APIs REST do API Gateway usando um SDK da AWS

- Liste o mapeamento do caminho base para um nome de domínio personalizado no API Gateway
- Atualize o mapeamento do caminho base para um nome de domínio personalizado no API Gateway

Adicione uma resposta de um serviço da AWS integrado a um método do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar uma resposta de um serviço da AWS integrado a um método do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar uma resposta de integração como a resposta padrão com um modelo de mapeamento definido

Comando:

```
aws apigateway put-integration-response --rest-api-id 1234123412 --resource-id
 a1b2c3 --http-method GET --status-code 200 --selection-pattern "" --response-
templates '{"application/json": "{\"json\": \"template\"}"}'
```

Como criar uma resposta de integração com um regex de 400 e um valor de cabeçalho definido de forma estática

Comando:

```
aws apigateway put-integration-response --rest-api-id 1234123412 --resource-id
 a1b2c3 --http-method GET --status-code 400 --selection-pattern 400 --response-
parameters '{"method.response.header.custom-header": "'"'"'custom-value'"'"'"}'
```

- Para obter detalhes da API, consulte PutIntegrationResponseem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The
 integration
        method is backed by an AWS service, such as Amazon DynamoDB.
```

```
        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated
with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as
POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate
REST
                                 elements, such as query parameters, to the
request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
```

```
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json":
 json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutIntegrationResponseReferência da API AWSSDK for Python (Boto3).

Adicione um método HTTP a um recurso REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar um método HTTP a um recurso REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar um método para um recurso em uma API sem autorização, sem chave de API e com um cabeçalho de solicitação de método personalizado

Comando:

```
aws apigateway put-method --rest-api-id 1234123412 --resource-id a1b2c3 --http-
method PUT --authorization-type "NONE" --no-api-key-required --request-parameters
 "method.request.header.custom-header=false"
```

- Para obter detalhes da API, consulte PutMethodem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
```

```
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The
integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated
with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as
POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate
REST
```

```
                                elements, such as query parameters, to the
request
                                body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json":
json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
```

```
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutMethodReferência da API AWSSDK for Python (Boto3).

Adicione uma resposta HTTP a um recurso REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar uma resposta HTTP a um recurso REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar uma resposta de método de acordo com o código de status especificado com um cabeçalho de resposta de método personalizado

Comando:

```
aws apigateway put-method-response --rest-api-id 1234123412 --resource-
id a1b2c3 --http-method GET --status-code 400 --response-parameters
 "method.response.header.custom-header=false"
```

- Para obter detalhes da API, consulte PutMethodResponseem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None
```

```
    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The
integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated
with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as
POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate
REST
                                 elements, such as query parameters, to the
request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
```

```
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json":
json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
```

```
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutMethodResponseReferência da API AWSSDK for Python (Boto3).

Implante uma API REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma API REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar uma API

Comando:

```
aws apigateway create-rest-api --name 'My First API' --description 'This is my
 first API'
```

Como criar uma API duplicada a partir de uma API existente

Comando:

```
aws apigateway create-rest-api --name 'Copy of My First API' --description 'This
 is a copy of my first API' --clone-from 1234123412
```

- Para obter detalhes da API, consulte CreateRestApiem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createAPI(ApiGatewayClient apiGateway, String restApiId,
String restApiName) {

       try {
           CreateRestApiRequest request = CreateRestApiRequest.builder()
                   .cloneFrom(restApiId)
                   .description("Created using the Gateway Java API")
                   .name(restApiName)
                   .build();

           CreateRestApiResponse response = apiGateway.createRestApi(request);
           System.out.println("The id of the new api is " + response.id());
           return response.id();

       } catch (ApiGatewayException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateRestApia Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root
 resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used
 in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
```

```
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
            raise

        try:
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
            raise ValueError from err

        return self.api_id
```

- Para obter detalhes da API, consulte a CreateRestApiReferência da API AWSSDK for Python (Boto3).

Crie um recurso REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um recurso REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar um recurso em uma API

Comando:

```
aws apigateway create-resource --rest-api-id 1234123412 --parent-id a1b2c3 --
path-part 'new-resource'
```

- Para obter detalhes da API, consulte CreateResourceem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_rest_resource(self, parent_id, resource_path):
        """
        Adds a resource to a REST API.

        :param parent_id: The ID of the parent resource.
        :param resource_path: The path of the new resource, relative to the
 parent.
        :return: The ID of the new resource.
```

```
        """
        try:
            result = self.apig_client.create_resource(
                restApiId=self.api_id, parentId=parent_id, pathPart=resource_path
            )
            resource_id = result["id"]
            logger.info("Created resource %s.", resource_path)
        except ClientError:
            logger.exception("Couldn't create resource %s.", resource_path)
            raise
        else:
            return resource_id
```

- Para obter detalhes da API, consulte a CreateResourceReferência da API AWSSDK for Python (Boto3).

Exclua uma API REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma API REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como excluir uma API

Comando:

```
aws apigateway delete-rest-api --rest-api-id 1234123412
```

- Para obter detalhes da API, consulte DeleteRestApiem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void deleteAPI(ApiGatewayClient apiGateway, String restApiId) {

    try {
        DeleteRestApiRequest request = DeleteRestApiRequest.builder()
                .restApiId(restApiId)
                .build();

        apiGateway.deleteRestApi(request);
        System.out.println("The API was successfully deleted");

    } catch (ApiGatewayException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}
```

- Para obter detalhes da API, consulte DeleteRestApia Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def delete_rest_api(self):
        """
        Deletes a REST API, including all of its resources and configuration.
        """
        try:
            self.apig_client.delete_rest_api(restApiId=self.api_id)
            logger.info("Deleted REST API %s.", self.api_id)
            self.api_id = None
        except ClientError:
            logger.exception("Couldn't delete REST API %s.", self.api_id)
            raise
```

- Para obter detalhes da API, consulte a DeleteRestApiReferência da API AWSSDK for Python (Boto3).

Exclua uma implantação do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma implantação.

CLI

AWS CLI

Como excluir uma implantação em uma API

Comando:

```
aws apigateway delete-deployment --rest-api-id 1234123412 --deployment-id a1b2c3
```

- Para obter detalhes da API, consulte DeleteDeploymentem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteSpecificDeployment(ApiGatewayClient apiGateway,
String restApiId, String deploymentId) {

       try {
           DeleteDeploymentRequest request = DeleteDeploymentRequest.builder()
                   .restApiId(restApiId)
                   .deploymentId(deploymentId)
                   .build();

           apiGateway.deleteDeployment(request);
           System.out.println("Deployment was deleted");

       } catch (ApiGatewayException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteDeploymenta Referência AWS SDK for Java 2.x da API.

Implante uma API REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como implantar uma API REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como implantar os recursos configurados de uma API em um novo estágio

Comando:

```
aws apigateway create-deployment --rest-api-id 1234123412 --stage-name dev --
stage-description 'Development Stage' --description 'First deployment to the dev
 stage'
```

Como implantar os recursos configurados de uma API em um estágio existente

Comando:

```
aws apigateway create-deployment --rest-api-id 1234123412 --stage-name dev --
description 'Second deployment to the dev stage'
```

Como implantar os recursos configurados de uma API em um estágio existente com variáveis de estágio

aws apigateway create-deployment -- rest-api-id 1234123412 --stage-name dev -- description 'Terceira implantação no estágio de desenvolvimento' --variables key='value', otherKey='otherValue'

- Para obter detalhes da API, consulte CreateDeploymentem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createNewDeployment(ApiGatewayClient apiGateway, String
restApiId, String stageName) {

       try {
           CreateDeploymentRequest request = CreateDeploymentRequest.builder()
                   .restApiId(restApiId)
                   .description("Created using the AWS API Gateway Java API")
                   .stageName(stageName)
                   .build();

           CreateDeploymentResponse response =
apiGateway.createDeployment(request);
           System.out.println("The id of the deployment is " + response.id());
           return response.id();

       } catch (ApiGatewayException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateDeploymenta Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def deploy_api(self, stage_name):
        """
        Deploys a REST API. After a REST API is deployed, it can be called from
 any
        REST client, such as the Python Requests package or Postman.

        :param stage_name: The stage of the API to deploy, such as 'test'.
        :return: The base URL of the deployed REST API.
        """
        try:
            self.apig_client.create_deployment(
                restApiId=self.api_id, stageName=stage_name
            )
            self.stage = stage_name
            logger.info("Deployed stage %s.", stage_name)
```

```
        except ClientError:
            logger.exception("Couldn't deploy stage %s.", stage_name)
            raise
        else:
            return self.api_url()



    def api_url(self, resource=None):
        """
        Builds the REST API URL from its parts.

        :param resource: The resource path to append to the base URL.
        :return: The REST URL to the specified resource.
        """
        url = (
            f"https://{self.api_id}.execute-api.
{self.apig_client.meta.region_name}"
            f".amazonaws.com/{self.stage}"
        )
        if resource is not None:
            url = f"{url}/{resource}"
        return url
```

- Para obter detalhes da API, consulte a CreateDeploymentReferência da API AWSSDK for Python (Boto3).

Obtenha recursos REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como obter recursos REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como obter uma lista de recursos para uma API REST

Comando:

```
aws apigateway get-resources --rest-api-id 1234123412
```

Saída:

```
{
    "items": [
        {
            "path": "/resource/subresource",
            "resourceMethods": {
                "POST": {}
            },
            "id": "024ace",
            "pathPart": "subresource",
            "parentId": "ai5b02"
        }
    ]
}
```

- Para obter detalhes da API, consulte GetResourcesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
```

```
    Encapsulates Amazon API Gateway functions that are used to create a REST API
that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root
resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used
in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
            raise

        try:
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
```

```
            raise ValueError from err

        return self.api_id
```

- Para obter detalhes da API, consulte a GetResourcesReferência da API AWSSDK for Python (Boto3).

Obtenha o mapeamento do caminho base para um nome de domínio personalizado no API Gateway

Os exemplos de código a seguir mostram como obter um mapeamento de caminho base do API Gateway.

CLI

AWS CLI

Como obter o mapeamento de caminho base para um nome de domínio personalizado

Comando:

```
aws apigateway get-base-path-mapping --domain-name subdomain.domain.tld --base-
path v1
```

Saída:

```
{
    "basePath": "v1",
    "restApiId": "1234w4321e",
    "stage": "api"
}
```

- Para obter detalhes da API, consulte GetBasePathMappingem Referência de AWS CLI Comandos.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 * Purpose: Gets the base path mapping for a custom domain name in
 * Amazon API Gateway.
 *
 * Prerequisites: A custom domain name in API Gateway. For more information,
 * see "Custom Domain Names" in the Amazon API Gateway Developer Guide.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $basePath: The base path name that callers must provide as part of the
 *   URL after the domain name.
 * - $domainName: The custom domain name for the base path mapping.
 *
 * Returns: The base path mapping, if available; otherwise, the error message.
 * /////////////////////////////////////////////////////////////////////////// */

function getBasePathMapping($apiGatewayClient, $basePath, $domainName)
{
    try {
        $result = $apiGatewayClient->getBasePathMapping([
            'basePath' => $basePath,
            'domainName' => $domainName,
        ]);
        return 'The base path mapping\'s effective URI is: ' .
            $result['@metadata']['effectiveUri'];
```

```
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function getsTheBasePathMapping()
{
    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo getBasePathMapping($apiGatewayClient, '(none)', 'example.com');
}

// Uncomment the following line to run this code in an AWS account.
// getsTheBasePathMapping();
```

- Para obter detalhes da API, consulte GetBasePathMappinga Referência AWS SDK for PHP da API.

Integre um método do API Gateway a um serviço da AWS usando um SDK da AWS

Os exemplos de código a seguir mostram como integrar um método do API Gateway a um serviço da AWS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como criar uma solicitação de integração MOCK

Comando:

```
aws apigateway put-integration --rest-api-id 1234123412 --resource-id a1b2c3
 --http-method GET --type MOCK --request-templates '{ "application/json":
 "{\"statusCode\": 200}" }'
```

Como criar uma solicitação de integração HTTP

Comando:

```
aws apigateway put-integration --rest-api-id 1234123412 --resource-id a1b2c3
 --http-method GET --type HTTP --integration-http-method GET --uri 'https://
domain.tld/path'
```

Como criar uma solicitação de integração da AWS com um endpoint da função do Lambda

Comando:

```
aws apigateway put-integration --rest-api-id 1234123412 --resource-id
 a1b2c3 --http-method GET --type AWS --integration-http-method POST
 --uri 'arn:aws:apigateway:us-west-2:lambda:path/2015-03-31/functions/
arn:aws:lambda:us-west-2:123412341234:function:function_name/invocations'
```

- Para obter detalhes da API, consulte PutIntegrationem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """
```

```
    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The
integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated
with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as
POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate
REST
                                 elements, such as query parameters, to the
request
                                 body format required by the service.
        """
```

```
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json":
json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
```

```
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutIntegrationReferência da API AWSSDK for Python (Boto3).

Liste APIs REST do API Gateway usando um SDK da AWS

Os exemplos de código a seguir mostram como listar APIs REST do API Gateway.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e implantar uma API REST

CLI

AWS CLI

Como obter uma lista de APIs REST

Comando:

```
aws apigateway get-rest-apis
```

Saída:

```
{
    "items": [
        {
            "createdDate": 1438884790,
            "id": "12s44z21rb",
            "name": "My First API"
        }
    ]
}
```

- Para obter detalhes da API, consulte GetRestApisem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def get_rest_api_id(self, api_name):
        """
```

```
        Gets the ID of a REST API from its name by searching the list of REST
APIs
        for the current account. Because names need not be unique, this returns
only
        the first API with the specified name.

        :param api_name: The name of the API to look up.
        :return: The ID of the specified API.
        """
        try:
            rest_api = None
            paginator = self.apig_client.get_paginator("get_rest_apis")
            for page in paginator.paginate():
                rest_api = next(
                    (item for item in page["items"] if item["name"] == api_name),
None
                )
                if rest_api is not None:
                    break
            self.api_id = rest_api["id"]
            logger.info("Found ID %s for API %s.", rest_api["id"], api_name)
        except ClientError:
            logger.exception("Couldn't find ID for API %s.", api_name)
            raise
        else:
            return rest_api["id"]
```

- Para obter detalhes da API, consulte a GetRestApisReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exibir as APIs REST do Amazon Gateway na região.

```
async fn show_apis(client: &Client) -> Result<(), Error> {
    let resp = client.get_rest_apis().send().await?;

    for api in resp.items() {
        println!("ID:          {}", api.id().unwrap_or_default());
        println!("Name:        {}", api.name().unwrap_or_default());
        println!("Description: {}", api.description().unwrap_or_default());
        println!("Version:     {}", api.version().unwrap_or_default());
        println!(
            "Created:     {}",
            api.created_date().unwrap().to_chrono_utc()?
        );
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetRestApisreferência da API AWS SDK for Rust.

Liste o mapeamento do caminho base para um nome de domínio personalizado no API Gateway

O exemplo de código a seguir mostra como listar um mapeamento de caminho de base do API Gateway.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';
```

```
use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 * Purpose: Lists the base path mapping for a custom domain name in
 * Amazon API Gateway.
 *
 * Prerequisites: A custom domain name in API Gateway. For more information,
 * see "Custom Domain Names" in the Amazon API Gateway Developer Guide.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $domainName: The custom domain name for the base path mappings.
 *
 * Returns: Information about the base path mappings, if available;
 * otherwise, the error message.
 * /////////////////////////////////////////////////////////////////////////// */

function listBasePathMappings($apiGatewayClient, $domainName)
{
    try {
        $result = $apiGatewayClient->getBasePathMappings([
            'domainName' => $domainName
        ]);
        return 'The base path mapping(s) effective URI is: ' .
            $result['@metadata']['effectiveUri'];
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function listTheBasePathMappings()
{
    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo listBasePathMappings($apiGatewayClient, 'example.com');
}
```

```
// Uncomment the following line to run this code in an AWS account.
// listTheBasePathMappings();
```

- Para obter detalhes da API, consulte ListBasePathMappingsa Referência AWS SDK for PHP da API.

Atualize o mapeamento do caminho base para um nome de domínio personalizado no API Gateway

Os exemplos de código a seguir mostram como atualizar um mapeamento de caminho base do API Gateway.

CLI

AWS CLI

Como alterar o caminho base de um nome de domínio personalizado

Comando:

```
aws apigateway update-base-path-mapping --domain-name api.domain.tld --base-path
 prod --patch-operations op='replace',path='/basePath',value='v1'
```

Saída:

```
{
    "basePath": "v1",
    "restApiId": "1234123412",
    "stage": "api"
}
```

- Para obter detalhes da API, consulte UpdateBasePathMappingem Referência de AWS CLI Comandos.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 *
 * Purpose: Updates the base path mapping for a custom domain name
 * in Amazon API Gateway.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $basePath: The base path name that callers must provide as part of the
 *   URL after the domain name.
 * - $domainName: The custom domain name for the base path mapping.
 * - $patchOperations: The base path update operations to apply.
 *
 * Returns: Information about the updated base path mapping, if available;
 * otherwise, the error message.
 * ////////////////////////////////////////////////////////////////////////// */

function updateBasePathMapping(
    $apiGatewayClient,
    $basePath,
    $domainName,
    $patchOperations
) {
    try {
        $result = $apiGatewayClient->updateBasePathMapping([
            'basePath' => $basePath,
```

```
            'domainName' => $domainName,
            'patchOperations' => $patchOperations
        ]);
        return 'The updated base path\'s URI is: ' .
            $result['@metadata']['effectiveUri'];
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function updateTheBasePathMapping()
{
    $patchOperations = array([
        'op' => 'replace',
        'path' => '/stage',
        'value' => 'stage2'
    ]);

    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo updateBasePathMapping(
        $apiGatewayClient,
        '(none)',
        'example.com',
        $patchOperations
    );
}

// Uncomment the following line to run this code in an AWS account.
// updateTheBasePathMapping();
```

- Para obter detalhes da API, consulte UpdateBasePathMappinga Referência AWS SDK for PHP da API.

Cenários para o API Gateway usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon API Gateway com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie e implante uma API REST usando um SDK da AWS

Crie e implante uma API REST usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Criar uma API REST atendida pelo API Gateway.
- Adicionar recursos à API REST para representar um perfil de usuário.
- Adicione métodos de integração para que a API REST use uma tabela do DynamoDB para armazenar dados de perfil de usuário.
- Envie solicitações HTTP para a API REST para adicionar e recuperar perfis de usuário.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as operações do API Gateway.

```
import argparse
import json
import logging
from pprint import pprint
```

```
import boto3
from botocore.exceptions import ClientError
import requests

logger = logging.getLogger(__name__)


class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root
 resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used
 in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
            raise

        try:
```

```
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
            raise ValueError from err

        return self.api_id


    def add_rest_resource(self, parent_id, resource_path):
        """
        Adds a resource to a REST API.

        :param parent_id: The ID of the parent resource.
        :param resource_path: The path of the new resource, relative to the
parent.
        :return: The ID of the new resource.
        """
        try:
            result = self.apig_client.create_resource(
                restApiId=self.api_id, parentId=parent_id, pathPart=resource_path
            )
            resource_id = result["id"]
            logger.info("Created resource %s.", resource_path)
        except ClientError:
            logger.exception("Couldn't create resource %s.", resource_path)
            raise
        else:
            return resource_id


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
```

```
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The
integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated
with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as
POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate
REST
                                 elements, such as query parameters, to the
request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
```

```
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json":
json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise


    def deploy_api(self, stage_name):
```

```
        """
        Deploys a REST API. After a REST API is deployed, it can be called from
 any
        REST client, such as the Python Requests package or Postman.

        :param stage_name: The stage of the API to deploy, such as 'test'.
        :return: The base URL of the deployed REST API.
        """
        try:
            self.apig_client.create_deployment(
                restApiId=self.api_id, stageName=stage_name
            )
            self.stage = stage_name
            logger.info("Deployed stage %s.", stage_name)
        except ClientError:
            logger.exception("Couldn't deploy stage %s.", stage_name)
            raise
        else:
            return self.api_url()



    def api_url(self, resource=None):
        """
        Builds the REST API URL from its parts.

        :param resource: The resource path to append to the base URL.
        :return: The REST URL to the specified resource.
        """
        url = (
            f"https://{self.api_id}.execute-api.
{self.apig_client.meta.region_name}"
            f".amazonaws.com/{self.stage}"
        )
        if resource is not None:
            url = f"{url}/{resource}"
        return url
```

Implantar uma API REST e chamá–la com o pacote Requests.

```
def usage_demo(table_name, role_name, rest_api_name):
```

```
    """
    Demonstrates how to used API Gateway to create and deploy a REST API, and how
    to use the Requests package to call it.

    :param table_name: The name of the demo DynamoDB table.
    :param role_name: The name of the demo role that grants API Gateway
permission to
                      call DynamoDB.
    :param rest_api_name: The name of the demo REST API created by the demo.
    """
    gateway = ApiGatewayToService(boto3.client("apigateway"))
    role = boto3.resource("iam").Role(role_name)

    print("Creating REST API in API Gateway.")
    gateway.create_rest_api(rest_api_name)

    print("Adding resources to the REST API.")
    profiles_id = gateway.add_rest_resource(gateway.root_id, "profiles")
    username_id = gateway.add_rest_resource(profiles_id, "{username}")

    # The DynamoDB service requires that all integration requests use POST.
    print("Adding integration methods to read and write profiles in Amazon
DynamoDB.")
    gateway.add_integration_method(
        profiles_id,
        "GET",
        "dynamodb",
        "Scan",
        "POST",
        role.arn,
        {"TableName": table_name},
    )
    gateway.add_integration_method(
        profiles_id,
        "POST",
        "dynamodb",
        "PutItem",
        "POST",
        role.arn,
        {
            "TableName": table_name,
            "Item": {
                "username": {"S": "$input.path('$.username')"},
                "name": {"S": "$input.path('$.name')"},
```

```
                "title": {"S": "$input.path('$.title')"},
            },
        },
    )
    gateway.add_integration_method(
        username_id,
        "GET",
        "dynamodb",
        "GetItem",
        "POST",
        role.arn,
        {
            "TableName": table_name,
            "Key": {"username": {"S": "$method.request.path.username"}},
        },
    )

    stage = "test"
    print(f"Deploying the {stage} stage.")
    gateway.deploy_api(stage)

    profiles_url = gateway.api_url("profiles")
    print(
        f"Using the Requests package to post some people to the profiles REST API
at "
        f"{profiles_url}."
    )
    requests.post(
        profiles_url,
        json={"username": "will", "name": "William Shakespeare", "title":
"playwright"},
    )
    requests.post(
        profiles_url,
        json={
            "username": "ludwig",
            "name": "Ludwig van Beethoven",
            "title": "composer",
        },
    )
    requests.post(
        profiles_url,
        json={"username": "jane", "name": "Jane Austen", "title": "author"},
    )
```

```
    print("Getting the list of profiles from the REST API.")
    profiles = requests.get(profiles_url).json()
    pprint(profiles)
    print(f"Getting just the profile for username 'jane' (URL: {profiles_url}/
jane).")
    jane = requests.get(f"{profiles_url}/jane").json()
    pprint(jane)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDeployment
  - CreateResource
  - CreateRestApi
  - DeleteRestApi
  - GetResources
  - GetRestApis
  - PutIntegration
  - PutIntegrationResponse
  - PutMethod
  - PutMethodResponse

Exemplos de entre serviços para API Gateway usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon API Gateway com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma API REST do API Gateway para monitorar dados da COVID-19
- Criar uma API REST de biblioteca de empréstimos

- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação de chat websocket com o API Gateway
- Usar o API Gateway para invocar uma função do Lambda

Criar uma API REST do API Gateway para monitorar dados da COVID-19

O exemplo de código a seguir mostra como criar uma API REST que simula um sistema para monitorar casos diários de COVID-19 nos Estados Unidos, usando dados fictícios.

Python

SDK para Python (Boto3)

Mostra como usar o AWS Chalice com o AWS SDK for Python (Boto3) para criar uma API REST sem servidor que usa o Amazon API Gateway, o AWS Lambda e o Amazon DynamoDB. O exemplo de código a seguir simula um sistema que monitora casos diários de COVID-19 nos Estados Unidos, usando dados fictícios. Aprenda como:

- Usar o AWS Chalice para definir rotas nas funções do Lambda que são chamadas para lidar com solicitações REST provenientes do API Gateway.
- Usar as funções do Lambda para recuperar e armazenar dados em uma tabela do DynamoDB para atender a solicitações REST.
- Definir recursos de função de segurança e estrutura de tabela em um modelo do AWS CloudFormation.
- Use AWS Chalice e CloudFormation para empacotar e implantar todos os recursos necessários.
- Use CloudFormation para limpar todos os recursos criados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- AWS CloudFormation
- DynamoDB
- Lambda

Criar uma API REST de biblioteca de empréstimos

O exemplo de código abaixo mostra como criar uma biblioteca de empréstimos na qual os clientes possam pegar e devolver livros emprestados usando uma API REST com suporte por um banco de dados do Amazon Aurora.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com a API do Amazon Relational Database Service (Amazon RDS) e o AWS Chalice a fim de criar uma API REST com suporte por um banco de dados do Amazon Aurora. O serviço da Web é uma tecnologia sem servidor e representa uma biblioteca de empréstimos simples, na qual os clientes podem pegar e devolver livros emprestados. Aprenda como:

- Crie e gerencie um cluster de banco de dados Aurora com tecnologia sem servidor.
- Utilize o AWS Secrets Manager para gerenciar credenciais de bancos de dados.
- Implemente uma camada de armazenamento de dados que use o Amazon RDS para mover dados para dentro e fora do banco de dados.
- Use o AWS Chalice para implantar uma API REST com tecnologia sem servidor no Amazon API Gateway e no AWS Lambda.
- Use o pacote Requests para enviar solicitações ao serviço Web.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Aurora
- Lambda
- Secrets Manager

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação de chat websocket com o API Gateway

O exemplo de código a seguir mostra como criar uma aplicação de chat que é atendido por uma API de Websocket criada no Amazon API Gateway.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon API Gateway V2 para criar uma API de Websocket que se integra ao AWS Lambda e ao Amazon DynamoDB.

- Crie uma API de Websocket atendida pelo API Gateway.
- Defina um manipulador do Lambda que armazena conexões no DynamoDB e publica mensagens para outros participantes do chat.
- Conecte-se à aplicação de chat websocket e envie mensagens com o pacote Websockets.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda

Usar o API Gateway para invocar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma função do AWS Lambda invocada pelo Amazon API Gateway que envia mensagens de texto de aniversário.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar uma AWS Lambda função usando a API de tempo de JavaScript execução do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Python

SDK para Python (Boto3)

Este exemplo mostra como criar e usar uma API REST do Amazon API Gateway cujo alvo é uma função do AWS Lambda. O manipulador do Lambda mostra como rotear com base em métodos HTTP; como obter dados da string de consulta, do cabeçalho e do corpo e como retornar uma resposta JSON.

- Implante uma função do Lambda.
- Crie uma API REST do API Gateway.
- Crie um recurso REST cujo alvo seja a função do Lambda.
- Conceda permissão para que o API Gateway possa invocar a função do Lambda.
- Use o pacote Requests para enviar solicitações à API REST.
- Limpe todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Lambda

Exemplos de código para API de gerenciamento do API Gateway usando SDKs da AWS

Os exemplos de código a seguir mostram como usar a Amazon API Gateway Management do Amazon SES com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor da API de gerenciamento do API Gateway — Mais informações sobre a API de gerenciamento do API Gateway.
- Referência da API da API de gerenciamento do API Gateway – Detalhes sobre todas as ações disponíveis da API de gerenciamento do API Gateway.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para a API de gerenciamento do API Gateway usando SDKs da AWS
  - Envie os dados fornecidos para a conexão especificada usando um SDK da AWS

Ações para a API de gerenciamento do API Gateway usando SDKs da AWS

Os exemplos de código a seguir mostram como usar a API de gerenciamento do Amazon API Gateway com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Envie os dados fornecidos para a conexão especificada usando um SDK da AWS

Envie os dados fornecidos para a conexão especificada usando um SDK da AWS

Os exemplos de código a seguir mostram como enviar dados para uma conexão.

CLI

AWS CLI

Para enviar dados para uma WebSocket conexão

O `post-to-connection` exemplo a seguir envia uma mensagem para um cliente conectado à WebSocket API especificada.

```
aws apigatewaymanagementapi post-to-connection \
    --connection-id L0SM9cOFvHcCIhw= \
    --data "Hello from API Gateway!" \
    --endpoint-url https://aabbccddee.execute-api.us-west-2.amazonaws.com/prod
```

Este comando não produz saída.

Para obter mais informações, consulte Usar os comandos @connections em seu serviço de backend no Guia do desenvolvedor do Amazon API Gateway.

- Para obter detalhes da API, consulte PostToConnectionem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn send_data(
    client: &aws_sdk_apigatewaymanagement::Client,
    con_id: &str,
    data: &str,
) -> Result<(), aws_sdk_apigatewaymanagement::Error> {
    client
        .post_to_connection()
        .connection_id(con_id)
        .data(Blob::new(data))
        .send()
        .await?;

    Ok(())
}
```

```
    let endpoint_url = format!(
        "https://{api_id}.execute-api.{region}.amazonaws.com/{stage}",
        api_id = api_id,
        region = region,
        stage = stage
    );

    let shared_config =
aws_config::from_env().region(region_provider).load().await;
    let api_management_config = config::Builder::from(&shared_config)
        .endpoint_url(endpoint_url)
        .build();
    let client = Client::from_conf(api_management_config);
```

- Para obter detalhes da API, consulte a PostToConnectionreferência da API AWS SDK for Rust.

Exemplos de códigos para o Application Auto Scaling usando SDK da AWS

Os exemplos de código a seguir mostram como usar o Application Auto Scaling com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Application Auto Scaling: mais informações sobre o Application Auto Scaling.
- Referência da API Application Auto Scaling — Detalhes sobre todas as ações disponíveis do Application Auto Scaling.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para Application Auto Scaling usando SDKs da AWS
  - Descreva as políticas de escalabilidade do Application Auto Scaling usando um SDK da AWS
  - Desativar um recurso que é escalado usando um SDK do Application Auto Scaling
  - Registre um recurso para escalar usando um SDK do Application Auto Scaling

Ações para Application Auto Scaling usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Application Auto Scaling com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Descreva as políticas de escalabilidade do Application Auto Scaling usando um SDK da AWS
- Desativar um recurso que é escalado usando um SDK do Application Auto Scaling
- Registre um recurso para escalar usando um SDK do Application Auto Scaling

Descreva as políticas de escalabilidade do Application Auto Scaling usando um SDK da AWS

O exemplo de código a seguir mostra como descrever as políticas de escalabilidade do Application Auto Scaling para um determinado namespace de serviço.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_policies(client: &Client) -> Result<(), Error> {
    let response = client
        .describe_scaling_policies()
        .service_namespace(ServiceNamespace::Ec2)
        .send()
```

```
        .await?;
    println!("Auto Scaling Policies:");
    for policy in response.scaling_policies() {
        println!("{:?}\n", policy);
    }
    println!("Next token: {:?}", response.next_token());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeScalingPoliciesreferência da API AWS SDK for Rust.

Desativar um recurso que é escalado usando um SDK do Application Auto Scaling

O exemplo de código a seguir mostra como desativar um recurso do Application Auto Scaling.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.applicationautoscaling.ApplicationAutoScalingClient;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ApplicationAutoScalingExcep
import
 software.amazon.awssdk.services.applicationautoscaling.model.DeleteScalingPolicyRequest;
import
 software.amazon.awssdk.services.applicationautoscaling.model.DeregisterScalableTargetReq
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRequ
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsResp
```

```
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRequ
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesResp
import
 software.amazon.awssdk.services.applicationautoscaling.model.ScalableDimension;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ServiceNamespace;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DisableDynamoDBAutoscaling {
    public static void main(String[] args) {
        final String usage = """

            Usage:
               <tableId> <policyName>\s

            Where:
               tableId - The table Id value (for example, table/Music).\s
               policyName - The name of the policy (for example, $Music5-scaling-
policy).

            """;
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        ApplicationAutoScalingClient appAutoScalingClient =
 ApplicationAutoScalingClient.builder()
            .region(Region.US_EAST_1)
            .build();

        ServiceNamespace ns = ServiceNamespace.DYNAMODB;
```

```
        ScalableDimension tableWCUs =
ScalableDimension.DYNAMODB_TABLE_WRITE_CAPACITY_UNITS;
        String tableId = args[0];
        String policyName = args[1];

        deletePolicy(appAutoScalingClient, policyName, tableWCUs, ns, tableId);
        verifyScalingPolicies(appAutoScalingClient, tableId, ns, tableWCUs);
        deregisterScalableTarget(appAutoScalingClient, tableId, ns, tableWCUs);
        verifyTarget(appAutoScalingClient, tableId, ns, tableWCUs);
    }

    public static void deletePolicy(ApplicationAutoScalingClient
appAutoScalingClient, String policyName, ScalableDimension tableWCUs,
ServiceNamespace ns, String tableId) {
        try {
            DeleteScalingPolicyRequest delSPRequest =
DeleteScalingPolicyRequest.builder()
                .policyName(policyName)
                .scalableDimension(tableWCUs)
                .serviceNamespace(ns)
                .resourceId(tableId)
                .build();

            appAutoScalingClient.deleteScalingPolicy(delSPRequest);
            System.out.println(policyName +" was deleted successfully.");

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    // Verify that the scaling policy was deleted
    public static void verifyScalingPolicies(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
tableWCUs) {
        DescribeScalingPoliciesRequest dscRequest =
DescribeScalingPoliciesRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceId(tableId)
            .build();

        DescribeScalingPoliciesResponse response =
appAutoScalingClient.describeScalingPolicies(dscRequest);
```

```
        System.out.println("DescribeScalableTargets result: ");
        System.out.println(response);
    }

    public static void deregisterScalableTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
 tableWCUs) {
        try {
            DeregisterScalableTargetRequest targetRequest =
 DeregisterScalableTargetRequest.builder()
                .scalableDimension(tableWCUs)
                .serviceNamespace(ns)
                .resourceId(tableId)
                .build();

            appAutoScalingClient.deregisterScalableTarget(targetRequest);
            System.out.println("The scalable target was deregistered.");

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    public static void verifyTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
 tableWCUs) {
        DescribeScalableTargetsRequest dscRequest =
 DescribeScalableTargetsRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceIds(tableId)
            .build();

        DescribeScalableTargetsResponse response =
 appAutoScalingClient.describeScalableTargets(dscRequest);
        System.out.println("DescribeScalableTargets result: ");
        System.out.println(response);
    }
}
```

- Para obter detalhes da API, consulte DeleteScalingPolicya Referência AWS SDK for Java 2.x da API.

Registre um recurso para escalar usando um SDK do Application Auto Scaling

O exemplo de código a seguir mostra como registrar um recurso do Application Auto Scaling.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.applicationautoscaling.ApplicationAutoScalingClient;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ApplicationAutoScalingExcep
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRequ
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsResp
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRequ
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesResp
import software.amazon.awssdk.services.applicationautoscaling.model.PolicyType;
import
 software.amazon.awssdk.services.applicationautoscaling.model.PredefinedMetricSpecificati
import
 software.amazon.awssdk.services.applicationautoscaling.model.PutScalingPolicyRequest;
import
 software.amazon.awssdk.services.applicationautoscaling.model.RegisterScalableTargetReque
import
 software.amazon.awssdk.services.applicationautoscaling.model.ScalingPolicy;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ServiceNamespace;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ScalableDimension;
import software.amazon.awssdk.services.applicationautoscaling.model.MetricType;
```

```
import
 software.amazon.awssdk.services.applicationautoscaling.model.TargetTrackingScalingPolicy
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class EnableDynamoDBAutoscaling {
    public static void main(String[] args) {
        final String usage = """

            Usage:
               <tableId> <roleARN> <policyName>\s

            Where:
               tableId - The table Id value (for example, table/Music).
               roleARN - The ARN of the role that has ApplicationAutoScaling
 permissions.
               policyName - The name of the policy to create.

            """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        System.out.println("This example registers an Amazon DynamoDB table,
 which is the resource to scale.");
        String tableId = args[0];
        String roleARN = args[1];
        String policyName = args[2];
        ServiceNamespace ns = ServiceNamespace.DYNAMODB;
        ScalableDimension tableWCUs =
 ScalableDimension.DYNAMODB_TABLE_WRITE_CAPACITY_UNITS;
        ApplicationAutoScalingClient appAutoScalingClient =
 ApplicationAutoScalingClient.builder()
            .region(Region.US_EAST_1)
```

```
            .build();

        registerScalableTarget(appAutoScalingClient, tableId, roleARN, ns,
 tableWCUs);
        verifyTarget(appAutoScalingClient, tableId, ns, tableWCUs);
        configureScalingPolicy(appAutoScalingClient, tableId, ns, tableWCUs,
 policyName);
    }

    public static void registerScalableTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, String roleARN, ServiceNamespace ns,
 ScalableDimension tableWCUs) {
        try {
            RegisterScalableTargetRequest targetRequest =
 RegisterScalableTargetRequest.builder()
                .serviceNamespace(ns)
                .scalableDimension(tableWCUs)
                .resourceId(tableId)
                .roleARN(roleARN)
                .minCapacity(5)
                .maxCapacity(10)
                .build();

            appAutoScalingClient.registerScalableTarget(targetRequest);
            System.out.println("You have registered " + tableId);

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    // Verify that the target was created.
    public static void verifyTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
 tableWCUs) {
        DescribeScalableTargetsRequest dscRequest =
 DescribeScalableTargetsRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceIds(tableId)
            .build();

        DescribeScalableTargetsResponse response =
 appAutoScalingClient.describeScalableTargets(dscRequest);
```

```
        System.out.println("DescribeScalableTargets result: ");
        System.out.println(response);
    }

    // Configure a scaling policy.
    public static void configureScalingPolicy(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
tableWCUs, String policyName) {
        // Check if the policy exists before creating a new one.
        DescribeScalingPoliciesResponse describeScalingPoliciesResponse =
appAutoScalingClient.describeScalingPolicies(DescribeScalingPoliciesRequest.builder()
            .serviceNamespace(ns)
            .resourceId(tableId)
            .scalableDimension(tableWCUs)
            .build());

        if (!describeScalingPoliciesResponse.scalingPolicies().isEmpty()) {
            // If policies exist, consider updating an existing policy instead of
creating a new one.
            System.out.println("Policy already exists. Consider updating it
instead.");
            List<ScalingPolicy> polList =
describeScalingPoliciesResponse.scalingPolicies();
            for (ScalingPolicy pol : polList) {
                System.out.println("Policy name:" +pol.policyName());
            }
        } else {
            // If no policies exist, proceed with creating a new policy.
            PredefinedMetricSpecification specification =
PredefinedMetricSpecification.builder()

.predefinedMetricType(MetricType.DYNAMO_DB_WRITE_CAPACITY_UTILIZATION)
                .build();

            TargetTrackingScalingPolicyConfiguration policyConfiguration =
TargetTrackingScalingPolicyConfiguration.builder()
                .predefinedMetricSpecification(specification)
                .targetValue(50.0)
                .scaleInCooldown(60)
                .scaleOutCooldown(60)
                .build();

            PutScalingPolicyRequest putScalingPolicyRequest =
PutScalingPolicyRequest.builder()
```

```
                .targetTrackingScalingPolicyConfiguration(policyConfiguration)
                .serviceNamespace(ns)
                .scalableDimension(tableWCUs)
                .resourceId(tableId)
                .policyName(policyName)
                .policyType(PolicyType.TARGET_TRACKING_SCALING)
                .build();

            try {
                appAutoScalingClient.putScalingPolicy(putScalingPolicyRequest);
                System.out.println("You have successfully created a scaling
 policy for an Application Auto Scaling scalable target");
            } catch (ApplicationAutoScalingException e) {
                System.err.println("Error: " +
 e.awsErrorDetails().errorMessage());
            }
        }
    }
}
```

- Para obter detalhes da API, consulte RegisterScalableTargeta Referência AWS SDK for Java 2.x da API.

Exemplos de código para o Application Recovery Controller usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Route 53 com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Application Recovery Controller – Mais informações sobre o Application Recovery Controller.
- Referência da API do Application Recovery Controller – Detalhes sobre todas as ações disponíveis do Application Recovery Controller.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Controlador de recuperação de aplicações usando AWS SDKs
  - Obter o estado de um Controlador de recuperação de aplicações usando um AWS SDK.
  - Atualize o estado de um controle de roteamento do Application Recovery Controller usando um SDK da AWS

Ações para o Controlador de recuperação de aplicações usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Route 53 Application Recovery Controller com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Obter o estado de um Controlador de recuperação de aplicações usando um AWS SDK.
- Atualize o estado de um controle de roteamento do Application Recovery Controller usando um SDK da AWS

Obter o estado de um Controlador de recuperação de aplicações usando um AWS SDK.

Os exemplos de código a seguir mostram como obter o estado de um controle de roteamento do Application Recovery Controller.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static GetRoutingControlStateResponse
 getRoutingControlState(List<ClusterEndpoint> clusterEndpoints,
            String routingControlArn) {
        // As a best practice, we recommend choosing a random cluster endpoint to
 get or
        // set routing control states.
        // For more information, see
        // https://docs.aws.amazon.com/r53recovery/latest/dg/route53-arc-best-
practices.html#route53-arc-best-practices.regional
        Collections.shuffle(clusterEndpoints);
        for (ClusterEndpoint clusterEndpoint : clusterEndpoints) {
            try {
                System.out.println(clusterEndpoint);
                Route53RecoveryClusterClient client =
 Route53RecoveryClusterClient.builder()
                        .endpointOverride(URI.create(clusterEndpoint.endpoint()))
                        .region(Region.of(clusterEndpoint.region())).build();
                return client.getRoutingControlState(
                        GetRoutingControlStateRequest.builder()
                                .routingControlArn(routingControlArn).build());
            } catch (Exception exception) {
                System.out.println(exception);
            }
        }
        return null;
    }
```

- Para obter detalhes da API, consulte GetRoutingControlStatea Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def create_recovery_client(cluster_endpoint):
    """
    Creates a Boto3 Route 53 Application Recovery Controller client for the
 specified
    cluster endpoint URL and AWS Region.

    :param cluster_endpoint: The cluster endpoint URL and Region.
    :return: The Boto3 client.
    """
    return boto3.client(
        "route53-recovery-cluster",
        endpoint_url=cluster_endpoint["Endpoint"],
        region_name=cluster_endpoint["Region"],
    )



def get_routing_control_state(routing_control_arn, cluster_endpoints):
    """
    Gets the state of a routing control. Cluster endpoints are tried in
    sequence until the first successful response is received.

    :param routing_control_arn: The ARN of the routing control to look up.
    :param cluster_endpoints: The list of cluster endpoints to query.
    :return: The routing control state response.
    """

    # As a best practice, we recommend choosing a random cluster endpoint to get
 or set routing control states.
```

```
    # For more information, see https://docs.aws.amazon.com/r53recovery/latest/
dg/route53-arc-best-practices.html#route53-arc-best-practices.regional
    random.shuffle(cluster_endpoints)
    for cluster_endpoint in cluster_endpoints:
        try:
            recovery_client = create_recovery_client(cluster_endpoint)
            response = recovery_client.get_routing_control_state(
                RoutingControlArn=routing_control_arn
            )
            return response
        except Exception as error:
            print(error)
            raise error
```

- Para obter detalhes da API, consulte a GetRoutingControlStateReferência da API AWSSDK for Python (Boto3).

Atualize o estado de um controle de roteamento do Application Recovery Controller usando um SDK da AWS

Os exemplos de código a seguir mostram como atualizar o estado de um controle de roteamento do Application Recovery Controller.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static UpdateRoutingControlStateResponse
updateRoutingControlState(List<ClusterEndpoint> clusterEndpoints,
            String routingControlArn,
            String routingControlState) {
```

```
        // As a best practice, we recommend choosing a random cluster endpoint to
 get or
        // set routing control states.
        // For more information, see
        // https://docs.aws.amazon.com/r53recovery/latest/dg/route53-arc-best-
practices.html#route53-arc-best-practices.regional
        Collections.shuffle(clusterEndpoints);
        for (ClusterEndpoint clusterEndpoint : clusterEndpoints) {
            try {
                System.out.println(clusterEndpoint);
                Route53RecoveryClusterClient client =
 Route53RecoveryClusterClient.builder()
                        .endpointOverride(URI.create(clusterEndpoint.endpoint()))
                        .region(Region.of(clusterEndpoint.region()))
                        .build();
                return client.updateRoutingControlState(
                        UpdateRoutingControlStateRequest.builder()

 .routingControlArn(routingControlArn).routingControlState(routingControlState).build());
            } catch (Exception exception) {
                System.out.println(exception);
            }
        }
        return null;
    }
```

- Para obter detalhes da API, consulte UpdateRoutingControlStateа Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3
```

```
def create_recovery_client(cluster_endpoint):
    """
    Creates a Boto3 Route 53 Application Recovery Controller client for the
 specified
    cluster endpoint URL and AWS Region.

    :param cluster_endpoint: The cluster endpoint URL and Region.
    :return: The Boto3 client.
    """
    return boto3.client(
        "route53-recovery-cluster",
        endpoint_url=cluster_endpoint["Endpoint"],
        region_name=cluster_endpoint["Region"],
    )



def update_routing_control_state(
    routing_control_arn, cluster_endpoints, routing_control_state
):
    """
    Updates the state of a routing control. Cluster endpoints are tried in
    sequence until the first successful response is received.

    :param routing_control_arn: The ARN of the routing control to update the
 state for.
    :param cluster_endpoints: The list of cluster endpoints to try.
    :param routing_control_state: The new routing control state.
    :return: The routing control update response.
    """

    # As a best practice, we recommend choosing a random cluster endpoint to get
 or set routing control states.
    # For more information, see https://docs.aws.amazon.com/r53recovery/latest/
dg/route53-arc-best-practices.html#route53-arc-best-practices.regional
    random.shuffle(cluster_endpoints)
    for cluster_endpoint in cluster_endpoints:
        try:
            recovery_client = create_recovery_client(cluster_endpoint)
            response = recovery_client.update_routing_control_state(
                RoutingControlArn=routing_control_arn,
                RoutingControlState=routing_control_state,
```

```
            )
            return response
        except Exception as error:
            print(error)
```

- Para obter detalhes da API, consulte a UpdateRoutingControlStateReferência da API AWSSDK for Python (Boto3).

Exemplos de código para o Secrets Manager usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Audit Manager com um kit de desenvolvimento de software (SDK) da AWS.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Audit Manager – Mais informações sobre o Audit Manager.
- Referência da API do Audit Manager – Detalhes sobre todas as ações disponíveis do Audit Manager.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Cenários para o Audit Manager usando SDKs da AWS
  - Crie uma estrutura personalizada do Audit Manager a partir de um pacote de conformidade do AWS Config usando um SDK da AWS
  - Crie uma estrutura personalizada do Audit Manager que contenha os controles do Security Hub usando um SDK da AWS.

- Crie um relatório de avaliação do Audit Manager que contenha um dia de evidências usando um SDK da AWS

Cenários para o Audit Manager usando SDKs da AWS

Exemplos de código que mostram como usar AWS Audit Manager com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie uma estrutura personalizada do Audit Manager a partir de um pacote de conformidade do AWS Config usando um SDK da AWS
- Crie uma estrutura personalizada do Audit Manager que contenha os controles do Security Hub usando um SDK da AWS.
- Crie um relatório de avaliação do Audit Manager que contenha um dia de evidências usando um SDK da AWS

Crie uma estrutura personalizada do Audit Manager a partir de um pacote de conformidade do AWS Config usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Obter uma lista de pacotes de conformidade do AWS Config.
- Criar um controle personalizado do Audit Manager para cada regra gerenciada em um pacote de conformidade.
- Criar uma estrutura personalizada do Audit Manager que contenha os controles.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class ConformancePack:
    def __init__(self, config_client, auditmanager_client):
        self.config_client = config_client
        self.auditmanager_client = auditmanager_client

    def get_conformance_pack(self):
        """
        Return a selected conformance pack from the list of conformance packs.

        :return: selected conformance pack
        """
        try:
            conformance_packs = self.config_client.describe_conformance_packs()
            print(
                "Number of conformance packs fetched: ",
                len(conformance_packs.get("ConformancePackDetails")),
            )
            print("Fetched the following conformance packs: ")
            all_cpack_names = {
                cp["ConformancePackName"]
                for cp in conformance_packs.get("ConformancePackDetails")
            }
            for pack in all_cpack_names:
                print(f"\t{pack}")
            cpack_name = input(
```

```
                "Provide ConformancePackName that you want to create a custom "
                "framework for: "
            )
            if cpack_name not in all_cpack_names:
                print(f"{cpack_name} is not in the list of conformance packs!")
                print(
                    "Provide a conformance pack name from the available list of "
                    "conformance packs."
                )
                raise Exception("Invalid conformance pack")
            print("-" * 88)
        except ClientError:
            logger.exception("Couldn't select conformance pack.")
            raise
        else:
            return cpack_name

    def create_custom_controls(self, cpack_name):
        """
        Create custom controls for all managed AWS Config rules in a conformance
pack.

        :param cpack_name: The name of the conformance pack to create controls
for.
        :return: The list of custom control IDs.
        """
        try:
            rules_in_pack =
self.config_client.describe_conformance_pack_compliance(
                ConformancePackName=cpack_name
            )
            print(
                "Number of rules in the conformance pack: ",
                len(rules_in_pack.get("ConformancePackRuleComplianceList")),
            )
            for rule in rules_in_pack.get("ConformancePackRuleComplianceList"):
                print(f"\t{rule.get('ConfigRuleName')}")
            print("-" * 88)
            print(
                "Creating a custom control for each rule and a custom framework "
                "consisting of these rules in Audit Manager."
            )
            am_controls = []
            for rule in rules_in_pack.get("ConformancePackRuleComplianceList"):
```

```
                config_rule = self.config_client.describe_config_rules(
                    ConfigRuleNames=[rule.get("ConfigRuleName")]
                )
                source_id = (
                    config_rule.get("ConfigRules")[0]
                    .get("Source", {})
                    .get("SourceIdentifier")
                )
                custom_control = self.auditmanager_client.create_control(
                    name="Config-" + rule.get("ConfigRuleName"),
                    controlMappingSources=[
                        {
                            "sourceName": "ConfigRule",
                            "sourceSetUpOption": "System_Controls_Mapping",
                            "sourceType": "AWS_Config",
                            "sourceKeyword": {
                                "keywordInputType": "SELECT_FROM_LIST",
                                "keywordValue": source_id,
                            },
                        }
                    ],
                ).get("control", {})
                am_controls.append({"id": custom_control.get("id")})
            print("Successfully created a control for each config rule.")
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom controls.")
            raise
        else:
            return am_controls

    def create_custom_framework(self, cpack_name, am_control_ids):
        """
        Create a custom Audit Manager framework from a selected AWS Config
conformance
        pack.

        :param cpack_name: The name of the conformance pack to create a framework
from.
        :param am_control_ids: The IDs of the custom controls created from the
                               conformance pack.
        """
        try:
            print("Creating custom framework...")
```

```
            custom_framework =
 self.auditmanager_client.create_assessment_framework(
                name="Config-Conformance-pack-" + cpack_name,
                controlSets=[{"name": cpack_name, "controls": am_control_ids}],
            )
            print(
                f"Successfully created the custom framework: ",
                f"{custom_framework.get('framework').get('name')}: ",
                f"{custom_framework.get('framework').get('id')}",
            )
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom framework.")
            raise


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager custom framework demo!")
    print("-" * 88)
    print(
        "You can use this sample to select a conformance pack from AWS Config and
 "
        "use AWS Audit Manager to create a custom control for all the managed "
        "rules under the conformance pack. A custom framework is also created "
        "with these controls."
    )
    print("-" * 88)
    conf_pack = ConformancePack(boto3.client("config"),
 boto3.client("auditmanager"))
    cpack_name = conf_pack.get_conformance_pack()
    am_controls = conf_pack.create_custom_controls(cpack_name)
    conf_pack.create_custom_framework(cpack_name, am_controls)


if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAssessmentFramework

- CreateControl

Crie uma estrutura personalizada do Audit Manager que contenha os controles do Security Hub usando um SDK da AWS.

O código de exemplo a seguir mostra como:

- Obter uma lista de todos os controles padrão que têm o Security Hub como fonte de dados.
- Criar uma estrutura personalizada do Audit Manager que contenha os controles.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class SecurityHub:
    def __init__(self, auditmanager_client):
        self.auditmanager_client = auditmanager_client

    def get_sechub_controls(self):
        """
        Gets the list of controls that use Security Hub as their data source.

        :return: The list of Security Hub controls.
        """
        print("-" * 88)
        next_token = None
        page = 1
```

```
        sechub_control_list = []
        while True:
            print("Page [" + str(page) + "]")
            if next_token is None:
                control_list = self.auditmanager_client.list_controls(
                    controlType="Standard", maxResults=100
                )
            else:
                control_list = self.auditmanager_client.list_controls(
                    controlType="Standard", nextToken=next_token, maxResults=100
                )
            print("Total controls found:",
len(control_list.get("controlMetadataList")))
            for control in control_list.get("controlMetadataList"):
                control_details = self.auditmanager_client.get_control(
                    controlId=control.get("id")
                ).get("control", {})
                if "AWS Security Hub" in control_details.get("controlSources"):
                    sechub_control_list.append({"id": control_details.get("id")})
            next_token = control_list.get("nextToken")
            if not next_token:
                break
            page += 1
        print("Number of Security Hub controls found: ",
len(sechub_control_list))
        return sechub_control_list

    def create_custom_framework(self, am_controls):
        """
        Create a custom framework with a list of controls.

        :param am_controls: The list of controls to include in the framework.
        """
        try:
            print("Creating custom framework...")
            custom_framework =
self.auditmanager_client.create_assessment_framework(
                name="All Security Hub Controls Framework",
                controlSets=[{"name": "Security-Hub", "controls": am_controls}],
            )
            print(
                f"Successfully created the custom framework: "
                f"{custom_framework.get('framework').get('name')}: "
                f"{custom_framework.get('framework').get('id')}"
```

```
            )
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom framework.")
            raise


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager Security Hub demo!")
    print("-" * 88)
    print(" This script creates a custom framework with all Security Hub
 controls.")
    print("-" * 88)
    sechub = SecurityHub(boto3.client("auditmanager"))
    am_controls = sechub.get_sechub_controls()
    sechub.create_custom_framework(am_controls)


if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAssessmentFramework
  - GetControl
  - ListControls

Crie um relatório de avaliação do Audit Manager que contenha um dia de evidências usando um SDK da AWS

O exemplo de código a seguir mostra como criar um relatório de avaliação do Audit Manager que contenha um dia de evidência.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import dateutil.parser
import logging
import time
import urllib.request
import uuid
import boto3
from botocore.exceptions import ClientError


logger = logging.getLogger(__name__)


class AuditReport:
    def __init__(self, auditmanager_client):
        self.auditmanager_client = auditmanager_client

    def get_input(self):
        print("-" * 40)
        try:
            assessment_id = input("Provide assessment id [uuid]: ").lower()
            try:
                assessment_uuid = uuid.UUID(assessment_id)
            except ValueError:
                logger.error("Assessment Id is not a valid UUID: %s",
 assessment_id)
                raise
            evidence_folder = input("Provide evidence date [yyyy-mm-dd]: ")
            try:
                evidence_date = dateutil.parser.parse(evidence_folder).date()
            except ValueError:
                logger.error("Invalid date : %s", evidence_folder)
                raise
```

```
            try:
                self.auditmanager_client.get_assessment(
                    assessmentId=str(assessment_uuid)
                )
            except ClientError:
                logger.exception("Couldn't get assessment %s.", assessment_uuid)
                raise
        except (ValueError, ClientError):
            return None, None
        else:
            return assessment_uuid, evidence_date

    def clear_staging(self, assessment_uuid, evidence_date):
        """
        Find all the evidence in the report and clear it.
        """
        next_token = None
        page = 1
        interested_folder_id_list = []
        while True:
            print(f"Page [{page}]")
            if next_token is None:
                folder_list = (
                    self.auditmanager_client.get_evidence_folders_by_assessment(
                        assessmentId=str(assessment_uuid), maxResults=1000
                    )
                )
            else:
                folder_list = (
                    self.auditmanager_client.get_evidence_folders_by_assessment(
                        assessmentId=str(assessment_uuid),
                        nextToken=next_token,
                        maxResults=1000,
                    )
                )
            folders = folder_list.get("evidenceFolders")
            print(f"Got {len(folders)} folders.")
            for folder in folders:
                folder_id = folder.get("id")
                if folder.get("name") == str(evidence_date):
                    interested_folder_id_list.append(folder_id)
                if folder.get("assessmentReportSelectionCount") == folder.get(
                    "totalEvidence"
                ):
```

```
                    print(
                        f"Removing folder from report selection :
{folder.get('name')} "
                        f"{folder_id} {folder.get('controlId')}"
                    )

self.auditmanager_client.disassociate_assessment_report_evidence_folder(
                        assessmentId=str(assessment_uuid),
evidenceFolderId=folder_id
                    )
                elif folder.get("assessmentReportSelectionCount") > 0:
                    # Get all evidence in the folder and
                    # add selected evidence in the selected_evidence_list.
                    evidence_list = (
                        self.auditmanager_client.get_evidence_by_evidence_folder(
                            assessmentId=str(assessment_uuid),
                            controlSetId=folder_id,
                            evidenceFolderId=folder_id,
                            maxResults=1000,
                        )
                    )
                    selected_evidence_list = []
                    for evidence in evidence_list.get("evidence"):
                        if evidence.get("assessmentReportSelection") == "Yes":
                            selected_evidence_list.append(evidence.get("id"))
                    print(
                        f"Removing evidence report selection :
{folder.get('name')} "
                        f"{len(selected_evidence_list)}"
                    )

self.auditmanager_client.batch_disassociate_assessment_report_evidence(
                        assessmentId=str(assessment_uuid),
                        evidenceFolderId=folder_id,
                        evidenceIds=selected_evidence_list,
                    )
            next_token = folder_list.get("nextToken")
            if not next_token:
                break
            page += 1
        return interested_folder_id_list

    def add_folder_to_staging(self, assessment_uuid, folder_id_list):
        print(f"Adding folders to report : {folder_id_list}")
```

```
        for folder in folder_id_list:
            self.auditmanager_client.associate_assessment_report_evidence_folder(
                assessmentId=str(assessment_uuid), evidenceFolderId=folder
            )

    def get_report(self, assessment_uuid):
        report = self.auditmanager_client.create_assessment_report(
            name="ReportViaScript",
            description="testing",
            assessmentId=str(assessment_uuid),
        )
        if self._is_report_generated(report.get("assessmentReport").get("id")):
            report_url = self.auditmanager_client.get_assessment_report_url(
                assessmentReportId=report.get("assessmentReport").get("id"),
                assessmentId=str(assessment_uuid),
            )
            print(report_url.get("preSignedUrl"))
            urllib.request.urlretrieve(
                report_url.get("preSignedUrl").get("link"),
                report_url.get("preSignedUrl").get("hyperlinkName"),
            )
            print(
                f"Report saved as
{report_url.get('preSignedUrl').get('hyperlinkName')}."
            )
        else:
            print("Report generation did not finish in 15 minutes.")
            print(
                "Failed to download report. Go to the console and manually
download "
                "the report."
            )

    def _is_report_generated(self, assessment_report_id):
        max_wait_time = 0
        while max_wait_time < 900:
            print(f"Checking status of the report {assessment_report_id}")
            report_list =
self.auditmanager_client.list_assessment_reports(maxResults=1)
            if (
                report_list.get("assessmentReports")[0].get("id")
                == assessment_report_id
                and report_list.get("assessmentReports")[0].get("status") ==
"COMPLETE"
```

```
            ):
                return True
            print("Sleeping for 5 seconds...")
            time.sleep(5)
            max_wait_time += 5


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager samples demo!")
    print("-" * 88)
    print(
        "This script creates an assessment report for an assessment with all the
 "
        "evidence collected on the provided date."
    )
    print("-" * 88)

    report = AuditReport(boto3.client("auditmanager"))
    assessment_uuid, evidence_date = report.get_input()
    if assessment_uuid is not None and evidence_date is not None:
        folder_id_list = report.clear_staging(assessment_uuid, evidence_date)
        report.add_folder_to_staging(assessment_uuid, folder_id_list)
        report.get_report(assessment_uuid)


if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AssociateAssessmentReportEvidenceFolder
  - BatchDisassociateAssessmentReportEvidence
  - CreateAssessmentReport
  - DisassociateAssessmentReportEvidenceFolder
  - GetAssessment
  - GetAssessmentReportUrl
  - GetEvidenceByEvidenceFolder
  - GetEvidenceFoldersByAssessment

- ListAssessmentReports

Exemplos de código para o Aurora usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Aurora com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do Aurora – Mais informações sobre o Aurora.
- Referência da API do Aurora – Detalhes sobre todas as ações disponíveis do Aurora.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
using Amazon.RDS;
using Amazon.RDS.Model;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;

namespace AuroraActions;

public static class HelloAurora
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the
        // Amazon Relational Database Service (Amazon RDS).
        // Use your AWS profile name, or leave it blank to use the default
 profile.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRDS>()
            ).Build();

        // Now the client is available for injection. Fetching it directly here
 for example purposes only.
        var rdsClient = host.Services.GetRequiredService<IAmazonRDS>();

        // You can use await and any of the async methods to get a response.
        var response = await rdsClient.DescribeDBClustersAsync(new
 DescribeDBClustersRequest { IncludeShared = true });
        Console.WriteLine($"Hello Amazon RDS Aurora! Let's list some clusters in
 this account:");
        foreach (var cluster in response.DBClusters)
        {
            Console.WriteLine($"\tCluster: database: {cluster.DatabaseName}
 identifier: {cluster.DBClusterIdentifier}.");
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_aurora")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.
```

```
    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                    # and set the proper subdirectory to the
 executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_aurora.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_aurora.cpp.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBClustersRequest.h>
#include <iostream>

/*
 *  A "Hello Aurora" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client
 *  and describes the Amazon Aurora (Aurora) clusters.
 *
 *  main function
 *
 *  Usage: 'hello_aurora'
 *
 */
int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
        Aws::RDS::RDSClient rdsClient(clientConfig);

        Aws::String marker; // Used for pagination.
        std::vector<Aws::String> clusterIds;
        do {
            Aws::RDS::Model::DescribeDBClustersRequest request;

            Aws::RDS::Model::DescribeDBClustersOutcome outcome =
                    rdsClient.DescribeDBClusters(request);

            if (outcome.IsSuccess()) {
                for (auto &cluster: outcome.GetResult().GetDBClusters()) {
                    clusterIds.push_back(cluster.GetDBClusterIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
                result = 1;
                std::cerr << "Error with Aurora::GDescribeDBClusters. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!marker.empty());

        std::cout << clusterIds.size() << " Aurora clusters found." << std::endl;
        for (auto &clusterId: clusterIds) {
            std::cout << "  clusterId " << clusterId << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/rds"
)

// main uses the AWS SDK for Go V2 to create an Amazon Aurora client and list up
 to 20
// DB clusters in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 auroraClient := rds.NewFromConfig(sdkConfig)
 const maxClusters = 20
 fmt.Printf("Let's list up to %v DB clusters.\n", maxClusters)
 output, err := auroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{MaxRecords: aws.Int32(maxClusters)})
 if err != nil {
  fmt.Printf("Couldn't list DB clusters: %v\n", err)
```

```
  return
 }
 if len(output.DBClusters) == 0 {
  fmt.Println("No DB clusters found.")
 } else {
  for _, cluster := range output.DBClusters {
   fmt.Printf("DB cluster %v has database %v.\n", *cluster.DBClusterIdentifier,
    *cluster.DatabaseName)
  }
 }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.paginators.DescribeDBClustersIterable;

public class DescribeDbClusters {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeClusters(rdsClient);
        rdsClient.close();
    }
```

```
    public static void describeClusters(RdsClient rdsClient) {
        DescribeDBClustersIterable clustersIterable =
 rdsClient.describeDBClustersPaginator();
        clustersIterable.stream()
                .flatMap(r -> r.dbClusters().stream())
                .forEach(cluster -> System.out
                        .println("Database name: " + cluster.databaseName() + "
 Arn = " + cluster.dbClusterArn()));
    }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Java 2.x.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
use aws_sdk_rds::Client;

#[derive(Debug)]
struct Error(String);
impl std::fmt::Display for Error {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        write!(f, "{}", self.0)
    }
}
impl std::error::Error for Error {}

#[tokio::main]
async fn main() -> Result<(), Error> {
```

```
    tracing_subscriber::fmt::init();
    let sdk_config = aws_config::from_env().load().await;
    let client = Client::new(&sdk_config);

    let describe_db_clusters_output = client
        .describe_db_clusters()
        .send()
        .await
        .map_err(|e| Error(e.to_string()))?;
    println!(
        "Found {} clusters:",
        describe_db_clusters_output.db_clusters().len()
    );
    for cluster in describe_db_clusters_output.db_clusters() {
        let name = cluster.database_name().unwrap_or("Unknown");
        let engine = cluster.engine().unwrap_or("Unknown");
        let id = cluster.db_cluster_identifier().unwrap_or("Unknown");
        let class = cluster.db_cluster_instance_class().unwrap_or("Unknown");
        println!("\tDatabase: {name}",);
        println!("\t  Engine: {engine}",);
        println!("\t      ID: {id}",);
        println!("\tInstance: {class}",);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK para Rust.

Exemplos de código

- Ações para o Aurora usando AWS SDKs
  - Criar um cluster de bancos de dados Aurora utilizando um AWS SDK
  - Criar um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK
  - Criar um snapshot de cluster de bancos de dados do Aurora usando um AWS SDK
  - Criar uma instância de bancos de dados em um cluster de banco de dados do Aurora usando um AWS SDK
  - Excluir um cluster de bancos de dados do Aurora usando um AWS SDK

- Excluir um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK
- Excluir uma instância de banco de dados do Aurora usando um AWS SDK
- Descrever os grupos de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK
- Descrever snapshots de cluster de bancos de dados do Aurora usando um AWS SDK
- Descrever os clusters de banco de dados do Aurora usando um AWS SDK
- Descrever as instâncias de banco de dados do Aurora usando um AWS SDK
- Descrever as versões de mecanismo de banco de dados do Aurora usando um AWS SDK
- Descrever as opções de instâncias de banco de dados do Aurora usando um AWS SDK
- Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK
- Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK
- Cenários para o Aurora usando AWS SDKs
  - Começar a usar os clusters de banco de dados do Aurora usando um AWS SDK
- Exemplos entre serviços para o Aurora usando AWS SDKs
  - Criar uma API REST de biblioteca de empréstimos
  - Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Ações para o Aurora usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Aurora com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Aurora usando AWS SDKs.

Exemplos

- Criar um cluster de bancos de dados Aurora utilizando um AWS SDK
- Criar um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK
- Criar um snapshot de cluster de bancos de dados do Aurora usando um AWS SDK
- Criar uma instância de bancos de dados em um cluster de banco de dados do Aurora usando um AWS SDK

- Excluir um cluster de bancos de dados do Aurora usando um AWS SDK
- Excluir um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK
- Excluir uma instância de banco de dados do Aurora usando um AWS SDK
- Descrever os grupos de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK
- Descrever snapshots de cluster de bancos de dados do Aurora usando um AWS SDK
- Descrever os clusters de banco de dados do Aurora usando um AWS SDK
- Descrever as instâncias de banco de dados do Aurora usando um AWS SDK
- Descrever as versões de mecanismo de banco de dados do Aurora usando um AWS SDK
- Descrever as opções de instâncias de banco de dados do Aurora usando um AWS SDK
- Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK
- Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK

Criar um cluster de bancos de dados Aurora utilizando um AWS SDK

Os exemplos de código a seguir mostram como criar um cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
/// <summary>
```

```
    /// Create a new cluster and database.
    /// </summary>
    /// <param name="dbName">The name of the new database.</param>
    /// <param name="clusterIdentifier">The identifier of the cluster.</param>
    /// <param name="parameterGroupName">The name of the parameter group.</param>
    /// <param name="dbEngine">The engine to use for the new cluster.</param>
    /// <param name="dbEngineVersion">The version of the engine to use.</param>
    /// <param name="adminName">The admin username.</param>
    /// <param name="adminPassword">The primary admin password.</param>
    /// <returns>The cluster object.</returns>
    public async Task<DBCluster> CreateDBClusterWithAdminAsync(
        string dbName,
        string clusterIdentifier,
        string parameterGroupName,
        string dbEngine,
        string dbEngineVersion,
        string adminName,
        string adminPassword)
    {
        var request = new CreateDBClusterRequest
        {
            DatabaseName = dbName,
            DBClusterIdentifier = clusterIdentifier,
            DBClusterParameterGroupName = parameterGroupName,
            Engine = dbEngine,
            EngineVersion = dbEngineVersion,
            MasterUsername = adminName,
            MasterUserPassword = adminPassword,
        };

        var response = await _amazonRDS.CreateDBClusterAsync(request);
        return response.DBCluster;
    }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBClusterRequest request;
    request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
    request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
    request.SetEngine(engineName);
    request.SetEngineVersion(engineVersionName);
    request.SetMasterUsername(administratorName);
    request.SetMasterUserPassword(administratorPassword);

    Aws::RDS::Model::CreateDBClusterOutcome outcome =
            client.CreateDBCluster(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB cluster creation has started."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::CreateDBCluster. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateDbCluster creates a DB cluster that is configured to use the specified
 parameter group.
// The newly created DB cluster contains a database that uses the specified
 engine and
// engine version.
func (clusters *DbClusters) CreateDbCluster(clusterName string,
 parameterGroupName string,
 dbName string, dbEngine string, dbEngineVersion string, adminName string,
 adminPassword string) (
 *types.DBCluster, error) {

 output, err := clusters.AuroraClient.CreateDBCluster(context.TODO(),
 &rds.CreateDBClusterInput{
  DBClusterIdentifier:         aws.String(clusterName),
  Engine:                      aws.String(dbEngine),
  DBClusterParameterGroupName: aws.String(parameterGroupName),
  DatabaseName:                aws.String(dbName),
  EngineVersion:               aws.String(dbEngineVersion),
  MasterUserPassword:          aws.String(adminPassword),
  MasterUsername:              aws.String(adminName),
 })
 if err != nil {
  log.Printf("Couldn't create DB cluster %v: %v\n", clusterName, err)
  return nil, err
 } else {
```

```
  return output.DBCluster, err
 }
}
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static String createDBCluster(RdsClient rdsClient, String
dbParameterGroupFamily, String dbName,
           String dbClusterIdentifier, String userName, String password) {
       try {
           CreateDbClusterRequest clusterRequest =
CreateDbClusterRequest.builder()
                   .databaseName(dbName)
                   .dbClusterIdentifier(dbClusterIdentifier)
                   .dbClusterParameterGroupName(dbParameterGroupFamily)
                   .engine("aurora-mysql")
                   .masterUsername(userName)
                   .masterUserPassword(password)
                   .build();

           CreateDbClusterResponse response =
rdsClient.createDBCluster(clusterRequest);
           return response.dbCluster().dbClusterArn();

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
```

```
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBCluster(dbParameterGroupFamilyVal: String?, dbName: String?,
 dbClusterIdentifierVal: String?, userName: String?, password: String?): String?
 {
    val clusterRequest = CreateDbClusterRequest {
        databaseName = dbName
        dbClusterIdentifier = dbClusterIdentifierVal
        dbClusterParameterGroupName = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
        masterUsername = userName
        masterUserPassword = password
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbCluster(clusterRequest)
        return response.dbCluster?.dbClusterArn
    }
}
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_db_cluster(
        self,
        cluster_name,
        parameter_group_name,
        db_name,
        db_engine,
        db_engine_version,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB cluster that is configured to use the specified parameter
 group.
```

```
        The newly created DB cluster contains a database that uses the specified
engine and
        engine version.

        :param cluster_name: The name of the DB cluster to create.
        :param parameter_group_name: The name of the parameter group to associate
with
                                     the DB cluster.
        :param db_name: The name of the database to create.
        :param db_engine: The database engine of the database that is created,
such as MySql.
        :param db_engine_version: The version of the database engine.
        :param admin_name: The user name of the database administrator.
        :param admin_password: The password of the database administrator.
        :return: The newly created DB cluster.
        """
        try:
            response = self.rds_client.create_db_cluster(
                DatabaseName=db_name,
                DBClusterIdentifier=cluster_name,
                DBClusterParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            cluster = response["DBCluster"]
        except ClientError as err:
            logger.error(
                "Couldn't create database %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return cluster
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql
database and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine
and engine version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql',
EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
for DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(),
ScenarioError> {
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
```

```
            )
            .await;
        if let Err(err) = create_db_cluster {
            return Err(ScenarioError::new(
                "Failed to create DB Cluster with cluster group",
                &err,
            ));
        }

        self.db_cluster_identifier = create_db_cluster
            .unwrap()
            .db_cluster
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
```

```
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for
ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() ==
Some("Available"));
```

```
            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn create_db_cluster(
        &self,
        name: &str,
        parameter_group: &str,
        engine: &str,
        version: &str,
        username: &str,
        password: SecretString,
    ) -> Result<CreateDbClusterOutput, SdkError<CreateDBClusterError>> {
        self.inner
            .create_db_cluster()
            .db_cluster_identifier(name)
            .db_cluster_parameter_group_name(parameter_group)
            .engine(engine)
```

```
            .engine_version(version)
            .master_username(username)
            .master_user_password(password.expose_secret())
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
```

```
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
```

```
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));
```

```
    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message
 == "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message
 == "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
```

```
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message
 == "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
```

```
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

.db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        })
```

```
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
```

```
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CreateFunction na Referência da API do AWS SDK para Rust.

Criar um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como criar um grupo de parâmetros de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a custom cluster parameter group.
    /// </summary>
    /// <param name="parameterGroupFamily">The family of the parameter group.</
param>
    /// <param name="groupName">The name for the new parameter group.</param>
    /// <param name="description">A description for the new parameter group.</
param>
    /// <returns>The new parameter group object.</returns>
    public async Task<DBClusterParameterGroup>
 CreateCustomClusterParameterGroupAsync(
```

```
        string parameterGroupFamily,
        string groupName,
        string description)
    {
        var request = new CreateDBClusterParameterGroupRequest
        {
            DBParameterGroupFamily = parameterGroupFamily,
            DBClusterParameterGroupName = groupName,
            Description = description,
        };

        var response = await
_amazonRDS.CreateDBClusterParameterGroupAsync(request);
        return response.DBClusterParameterGroup;
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example cluster parameter group.");
```

```
        Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
                client.CreateDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully
 created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateParameterGroup creates a DB cluster parameter group that is based on the
 specified
// parameter group family.
func (clusters *DbClusters) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
```

```
 *types.DBClusterParameterGroup, error) {

 output, err :=
 clusters.AuroraClient.CreateDBClusterParameterGroup(context.TODO(),
  &rds.CreateDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   DBParameterGroupFamily:      aws.String(parameterGroupFamily),
   Description:                 aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBClusterParameterGroup, err
 }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDBClusterParameterGroup(RdsClient rdsClient, String
dbClusterGroupName,
           String dbParameterGroupFamily) {
       try {
           CreateDbClusterParameterGroupRequest groupRequest =
CreateDbClusterParameterGroupRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .description("Created by using the AWS SDK for Java")
```

```
                    .build();

            CreateDbClusterParameterGroupResponse response =
 rdsClient.createDBClusterParameterGroup(groupRequest);
            System.out.println("The group name is " +
 response.dbClusterParameterGroup().dbClusterParameterGroupName());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBClusterParameterGroup(dbClusterGroupNameVal: String?,
 dbParameterGroupFamilyVal: String?) {
    val groupRequest = CreateDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dbClusterGroupNameVal
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterParameterGroup(groupRequest)
        println("The group name is
 ${response.dbClusterParameterGroup?.dbClusterParameterGroupName}")
    }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB cluster parameter group that is based on the specified
 parameter group
        family.
```

```
        :param parameter_group_name: The name of the newly created parameter
group.
        :param parameter_group_family: The family that is used as the basis of
the new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API CreateDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Select an engine family and create a custom DB cluster parameter group.
rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
   pub async fn set_engine(&mut self, engine: &str, version: &str) -> Result<(),
ScenarioError> {
       self.engine_family = Some(engine.to_string());
       self.engine_version = Some(version.to_string());
       let create_db_cluster_parameter_group = self
           .rds
           .create_db_cluster_parameter_group(
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION,
               engine,
           )
           .await;

       match create_db_cluster_parameter_group {
           Ok(CreateDbClusterParameterGroupOutput {
               db_cluster_parameter_group: None,
               ..
           }) => {
               return Err(ScenarioError::with(
                   "CreateDBClusterParameterGroup had empty response",
               ));
           }
           Err(error) => {
               if error.code() == Some("DBParameterGroupAlreadyExists") {
                   info!("Cluster Parameter Group already exists, nothing to
do");
               } else {
                   return Err(ScenarioError::new(
                       "Could not create Cluster Parameter Group",
                       &error,
                   ));
               }
           }
           _ => {
               info!("Created Cluster Parameter Group");
           }
       }

       Ok(())
   }
```

```
    pub async fn create_db_cluster_parameter_group(
        &self,
        name: &str,
        description: &str,
        family: &str,
    ) -> Result<CreateDbClusterParameterGroupOutput,
 SdkError<CreateDBClusterParameterGroupError>>
    {
        self.inner
            .create_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .description(description)
            .db_parameter_group_family(family)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_set_engine() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert_eq!(set_engine, Ok(()));
    assert_eq!(Some("aurora-mysql"), scenario.engine_family.as_deref());
    assert_eq!(Some("aurora-mysql8.0"), scenario.engine_version.as_deref());
}
```

```
#[tokio::test]
async fn test_scenario_set_engine_not_create() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _|
 Ok(CreateDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert!(set_engine.is_err());
}

#[tokio::test]
async fn test_scenario_set_engine_param_group_exists() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .withf(|_, _, _| true)
        .return_once(|_, _, _| {
            Err(SdkError::service_error(

 CreateDBClusterParameterGroupError::DbParameterGroupAlreadyExistsFault(
                    DbParameterGroupAlreadyExistsFault::builder().build(),
                ),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
```

```
    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert!(set_engine.is_err());
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Criar um snapshot de cluster de bancos de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como criar um snapshot de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a snapshot of a cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBClusterSnapshot>
CreateClusterSnapshotByIdentifierAsync(string dbClusterIdentifier, string
snapshotIdentifier)
    {
```

```
        var response = await _amazonRDS.CreateDBClusterSnapshotAsync(
            new CreateDBClusterSnapshotRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBClusterSnapshotIdentifier = snapshotIdentifier,
            });

        return response.DBClusterSnapshot;
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
            request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                    client.CreateDBClusterSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
```

```
            else {
                std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
 client);
                return false;
            }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateClusterSnapshot creates a snapshot of a DB cluster.
func (clusters *DbClusters) CreateClusterSnapshot(clusterName string,
 snapshotName string) (
 *types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.CreateDBClusterSnapshot(context.TODO(),
 &rds.CreateDBClusterSnapshotInput{
  DBClusterIdentifier:         aws.String(clusterName),
  DBClusterSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
```

```
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBClusterSnapshot, nil
 }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDBClusterSnapshot(RdsClient rdsClient, String
dbInstanceClusterIdentifier,
           String dbSnapshotIdentifier) {
       try {
           CreateDbClusterSnapshotRequest snapshotRequest =
CreateDbClusterSnapshotRequest.builder()
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                   .build();

           CreateDbClusterSnapshotResponse response =
rdsClient.createDBClusterSnapshot(snapshotRequest);
           System.out.println("The Snapshot ARN is " +
response.dbClusterSnapshot().dbClusterSnapshotArn());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
```

```
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBClusterSnapshot(dbInstanceClusterIdentifier: String?,
 dbSnapshotIdentifier: String?) {
    val snapshotRequest = CreateDbClusterSnapshotRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterSnapshot(snapshotRequest)
        println("The Snapshot ARN is
 ${response.dbClusterSnapshot?.dbClusterSnapshotArn}")
    }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_cluster_snapshot(self, snapshot_id, cluster_id):
        """
        Creates a snapshot of a DB cluster.

        :param snapshot_id: The ID to give the created snapshot.
        :param cluster_id: The DB cluster to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_cluster_snapshot(
                DBClusterSnapshotIdentifier=snapshot_id,
 DBClusterIdentifier=cluster_id
            )
```

```
            snapshot = response["DBClusterSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                cluster_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte Referência da API CreateDB ClusterSnapshot no AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql
database and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine
and engine version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql',
EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
for DBInstanceStatus == 'available'.
```

```
   pub async fn start_cluster_and_instance(&mut self) -> Result<(),
ScenarioError> {
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
           return Err(ScenarioError::new(
               "Failed to create DB Cluster with cluster group",
               &err,
           ));
       }

       self.db_cluster_identifier = create_db_cluster
           .unwrap()
           .db_cluster
           .and_then(|c| c.db_cluster_identifier);

       if self.db_cluster_identifier.is_none() {
           return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
       }

       info!(
           "Started a db cluster: {}",
           self.db_cluster_identifier
               .as_deref()
               .unwrap_or("Missing ARN")
       );
```

```
        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for
ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
```

```
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() ==
Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }
```

```
        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn snapshot_cluster(
        &self,
        db_cluster_identifier: &str,
        snapshot_name: &str,
    ) -> Result<CreateDbClusterSnapshotOutput,
 SdkError<CreateDBClusterSnapshotError>> {
        self.inner
            .create_db_cluster_snapshot()
            .db_cluster_identifier(db_cluster_identifier)
            .db_cluster_snapshot_identifier(snapshot_name)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
```

```
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
```

```
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
```

```
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message
 == "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message
 == "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message
 == "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
```

```
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

.db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
```

```
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
```

```
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na referência da API AWSSDK for Rust.

Criar uma instância de bancos de dados em um cluster de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma instância de banco de dados em um cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
```

```
    /// Create an Amazon Relational Database Service (Amazon RDS) DB instance
    /// with a particular set of properties. Use the action
DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstanceInClusterAsync(
        string dbClusterIdentifier,
        string dbInstanceIdentifier,
        string dbEngine,
        string dbEngineVersion,
        string instanceClass)
    {
        // When creating the instance within a cluster, do not specify the name
or size.
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateInstanceInCluster creates a database instance in an existing DB cluster.
 The first database that is
// created defaults to a read-write DB instance.
func (clusters *DbClusters) CreateInstanceInCluster(clusterName string,
 instanceName string,
 dbEngine string, dbInstanceClass string) (*types.DBInstance, error) {
 output, err := clusters.AuroraClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBClusterIdentifier:  aws.String(clusterName),
  Engine:               aws.String(dbEngine),
  DBInstanceClass:      aws.String(dbInstanceClass),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static String createDBInstanceCluster(RdsClient rdsClient,
           String dbInstanceIdentifier,
           String dbInstanceClusterIdentifier,
           String instanceClass) {
       try {
           CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .engine("aurora-mysql")
                   .dbInstanceClass(instanceClass)
                   .build();

           CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
           System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
           return response.dbInstance().dbInstanceArn();

       } catch (RdsException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBInstanceCluster(dbInstanceIdentifierVal: String?,
 dbInstanceClusterIdentifierVal: String?, instanceClassVal: String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbClusterIdentifier = dbInstanceClusterIdentifierVal
        engine = "aurora-mysql"
        dbInstanceClass = instanceClassVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_instance_in_cluster(
        self, instance_id, cluster_id, db_engine, instance_class
    ):
        """
        Creates a database instance in an existing DB cluster. The first database
 that is
        created defaults to a read-write DB instance.

        :param instance_id: The ID to give the newly created DB instance.
        :param cluster_id: The ID of the DB cluster where the DB instance is
 created.
        :param db_engine: The database engine of a database to create in the DB
 instance.
                          This must be compatible with the configured parameter
 group
                          of the DB cluster.
        :param instance_class: The DB instance class for the newly created DB
 instance.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBInstanceIdentifier=instance_id,
                DBClusterIdentifier=cluster_id,
```

```
                Engine=db_engine,
                DBInstanceClass=instance_class,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql
database and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine
and engine version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql',
EngineVersion=).
```

```
   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
for DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(),
ScenarioError> {
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
           return Err(ScenarioError::new(
               "Failed to create DB Cluster with cluster group",
               &err,
           ));
       }

       self.db_cluster_identifier = create_db_cluster
           .unwrap()
           .db_cluster
           .and_then(|c| c.db_cluster_identifier);

       if self.db_cluster_identifier.is_none() {
           return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
       }

       info!(
           "Started a db cluster: {}",
           self.db_cluster_identifier
               .as_deref()
```

```
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for
ready");
                continue;
            }

            let instance = self
```

```
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() ==
Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
```

```
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn create_db_instance(
        &self,
        cluster_name: &str,
        instance_name: &str,
        instance_class: &str,
        engine: &str,
    ) -> Result<CreateDbInstanceOutput, SdkError<CreateDBInstanceError>> {
        self.inner
            .create_db_instance()
            .db_cluster_identifier(cluster_name)
            .db_instance_identifier(instance_name)
            .db_instance_class(instance_class)
            .engine(engine)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
```

```
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
```

```
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
```

```
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message
 == "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message
 == "Created DB Cluster missing Identifier");
```

```
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
```

```
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message
 == "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
```

```
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
```

```
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CreateFunction na Referência da API do AWS SDK para Rust.

Excluir um cluster de bancos de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Delete a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>DB cluster object.</returns>
    public async Task<DBCluster> DeleteDBClusterByIdentifierAsync(string
dbClusterIdentifier)
    {
        var response = await _amazonRDS.DeleteDBClusterAsync(
            new DeleteDBClusterRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                SkipFinalSnapshot = true
            });

        return response.DBCluster;
    }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);

            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteDbCluster deletes a DB cluster without keeping a final snapshot.
func (clusters *DbClusters) DeleteDbCluster(clusterName string) error {
 _, err := clusters.AuroraClient.DeleteDBCluster(context.TODO(),
 &rds.DeleteDBClusterInput{
  DBClusterIdentifier: aws.String(clusterName),
  SkipFinalSnapshot:   true,
 })
 if err != nil {
  log.Printf("Couldn't delete DB cluster %v: %v\n", clusterName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void deleteCluster(RdsClient rdsClient, String
dbInstanceClusterIdentifier) {
       try {
           DeleteDbClusterRequest deleteDbClusterRequest =
DeleteDbClusterRequest.builder()
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .skipFinalSnapshot(true)
                   .build();

           rdsClient.deleteDBCluster(deleteDbClusterRequest);
           System.out.println(dbInstanceClusterIdentifier + " was deleted!");

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteCluster(dbInstanceClusterIdentifier: String) {
    val deleteDbClusterRequest = DeleteDbClusterRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        rdsClient.deleteDbCluster(deleteDbClusterRequest)
        println("$dbInstanceClusterIdentifier was deleted!")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
```

```
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_cluster(self, cluster_name):
        """
        Deletes a DB cluster.

        :param cluster_name: The name of the DB cluster to delete.
        """
        try:
            self.rds_client.delete_db_cluster(
                DBClusterIdentifier=cluster_name, SkipFinalSnapshot=True
            )
            logger.info("Deleted DB cluster %s.", cluster_name)
        except ClientError:
            logger.exception("Couldn't delete DB cluster %s.", cluster_name)
            raise
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
```

```
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances =
self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in
{status}");
                        continue;
```

```
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
```

```
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster parameter group.
rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }
```

```
        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_cluster(
        &self,
        cluster_identifier: &str,
    ) -> Result<DeleteDbClusterOutput, SdkError<DeleteDBClusterError>> {
        self.inner
            .delete_db_cluster()
            .db_cluster_identifier(cluster_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
```

```
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
```

```
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
```

```
                    "describe db instances error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));
```

```
    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
 message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
 message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte ExcluirDBCluster na AWS Referência da API SDK para Rust.

Excluir um grupo de parâmetros de cluster de bancos de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a particular parameter group by name.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteClusterParameterGroupByNameAsync(string
groupName)
    {
        var request = new DeleteDBClusterParameterGroupRequest
        {
            DBClusterParameterGroupName = groupName,
        };

        var response = await
_amazonRDS.DeleteDBClusterParameterGroupAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for .NET Referência da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
    request.SetDBClusterParameterGroupName(parameterGroupName);

    Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
            client.DeleteDBClusterParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully deleted."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        result = false;
    }
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for C ++ Referência da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteParameterGroup deletes the named DB cluster parameter group.
func (clusters *DbClusters) DeleteParameterGroup(parameterGroupName string) error
 {
 _, err := clusters.AuroraClient.DeleteDBClusterParameterGroup(context.TODO(),
  &rds.DeleteDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for Go Referência da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteDBClusterGroup(RdsClient rdsClient, String
dbClusterGroupName, String clusterDBARN)
           throws InterruptedException {
       try {
           boolean isDataDel = false;
           boolean didFind;
           String instanceARN;

           // Make sure that the database has been deleted.
           while (!isDataDel) {
               DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
               List<DBInstance> instanceList = response.dbInstances();
               int listSize = instanceList.size();
               didFind = false;
               int index = 1;
               for (DBInstance instance : instanceList) {
                   instanceARN = instance.dbInstanceArn();
                   if (instanceARN.compareTo(clusterDBARN) == 0) {
                       System.out.println(clusterDBARN + " still exists");
                       didFind = true;
                   }
                   if ((index == listSize) && (!didFind)) {
                       // Went through the entire list and did not find the
database ARN.
                       isDataDel = true;
                   }
                   Thread.sleep(sleepTime * 1000);
                   index++;
               }
           }
```

```
            DeleteDbClusterParameterGroupRequest clusterParameterGroupRequest =
 DeleteDbClusterParameterGroupRequest
                    .builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .build();


 rdsClient.deleteDBClusterParameterGroup(clusterParameterGroupRequest);
            System.out.println(dbClusterGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for Java 2.x Referência da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
@Throws(InterruptedException::class)
suspend fun deleteDBClusterGroup(dbClusterGroupName: String, clusterDBARN:
 String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
```

```
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
            isDataDel = false
            didFind = false
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(clusterDBARN) == 0) {
                        println("$clusterDBARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database ARN.
                        isDataDel = true
                    }
                    delay(slTime * 1000)
                    index++
                }
            }
        }
        val clusterParameterGroupRequest = DeleteDbClusterParameterGroupRequest {
            dbClusterParameterGroupName = dbClusterGroupName
        }

        rdsClient.deleteDbClusterParameterGroup(clusterParameterGroupRequest)
        println("$dbClusterGroupName was deleted.")
    }
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup no AWSSDK para referência da API Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            response = self.rds_client.delete_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API DeleteDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
```

```
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances =
self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
```

```
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
```

```
                    Some(status) => {
                        info!("Attempting to delete but clusters is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster parameter group.
rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_cluster_parameter_group(
        &self,
```

```
        name: &str,
    ) -> Result<DeleteDbClusterParameterGroupOutput,
 SdkError<DeleteDBClusterParameterGroupError>>
    {
        self.inner
            .delete_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
```

```
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
Describe Cluster
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
```

```
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );
```

```
    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
 message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
 message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Excluir uma instância de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma instância de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstanceByIdentifierAsync(string
dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
parameter group."
                        << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteInstance deletes a DB instance.
func (clusters *DbClusters) DeleteInstance(instanceName string) error {
 _, err := clusters.AuroraClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
       try {
           DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .deleteAutomatedBackups(true)
                   .skipFinalSnapshot(true)
                   .build();

           DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
           System.out.println("The status of the database is " +
response.dbInstance().dbInstanceStatus());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDBInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""
```

```
    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances =
self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
```

```
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
```

```
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
```

```
        }

        // Delete the DB cluster parameter group.
 rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DeleteDbInstanceOutput, SdkError<DeleteDBInstanceError>> {
        self.inner
            .delete_db_instance()
            .db_instance_identifier(instance_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }

#[tokio::test]
```

```
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
```

```
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
```

```
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
```

```
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte ExcluirInstânciaDB na AWS Referência da API SDK para Rust.

Descrever os grupos de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever grupos de parâmetros de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the description of a DB cluster parameter group by name.
```

```
    /// </summary>
    /// <param name="name">The name of the DB parameter group to describe.</
param>
    /// <returns>The parameter group description.</returns>
    public async Task<DBClusterParameterGroup?>
 DescribeCustomDBClusterParameterGroupAsync(string name)
    {
        var response = await _amazonRDS.DescribeDBClusterParameterGroupsAsync(
            new DescribeDBClusterParameterGroupsRequest()
            {
                DBClusterParameterGroupName = name
            });
        return response.DBClusterParameterGroups.FirstOrDefault();
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);
```

```
        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
 std::endl;
            dbParameterGroupFamily =
 outcome.GetResult().GetDBClusterParameterGroups()
[0].GetDBParameterGroupFamily();
        }

        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetParameterGroup gets a DB cluster parameter group by name.
func (clusters *DbClusters) GetParameterGroup(parameterGroupName string) (
 *types.DBClusterParameterGroup, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterParameterGroups(
```

```
  context.TODO(), &rds.DescribeDBClusterParameterGroupsInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBClusterParameterGroups[0], err
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameterGroups(RdsClient rdsClient,
String dbClusterGroupName) {
       try {
           DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .maxRecords(20)
                   .build();
```

```
            List<DBClusterParameterGroup> groups =
 rdsClient.describeDBClusterParameterGroups(groupsRequest)
                    .dbClusterParameterGroups();
            for (DBClusterParameterGroup group : groups) {
                System.out.println("The group name is " +
 group.dbClusterParameterGroupName());
                System.out.println("The group ARN is " +
 group.dbClusterParameterGroupArn());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameterGroups(dbClusterGroupName: String?) {
    val groupsRequest = DescribeDbClusterParameterGroupsRequest {
        dbClusterParameterGroupName = dbClusterGroupName
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbClusterParameterGroups(groupsRequest)
        response.dbClusterParameterGroups?.forEach { group ->
            println("The group name is ${group.dbClusterParameterGroupName}")
            println("The group ARN is ${group.dbClusterParameterGroupArn}")
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB cluster parameter group.
```

```
        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The requested parameter group.
        """
        try:
            response = self.rds_client.describe_db_cluster_parameter_groups(
                DBClusterParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBClusterParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups na Referência da API AWSSDK for Python (Boto3).

Descrever snapshots de cluster de bancos de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever snapshots de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Return a list of DB snapshots for a particular DB cluster.
   /// </summary>
   /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
   /// <returns>List of DB snapshots.</returns>
   public async Task<List<DBClusterSnapshot>>
DescribeDBClusterSnapshotsByIdentifierAsync(string dbClusterIdentifier)
   {
       var results = new List<DBClusterSnapshot>();

       DescribeDBClusterSnapshotsResponse response;
       DescribeDBClusterSnapshotsRequest request = new
DescribeDBClusterSnapshotsRequest
       {
           DBClusterIdentifier = dbClusterIdentifier
       };
       // Get the full list if there are multiple pages.
       do
       {
           response = await _amazonRDS.DescribeDBClusterSnapshotsAsync(request);
           results.AddRange(response.DBClusterSnapshots);
           request.Marker = response.Marker;
       }
       while (response.Marker is not null);
       return results;
   }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetClusterSnapshot gets a DB cluster snapshot.
func (clusters *DbClusters) GetClusterSnapshot(snapshotName string)
 (*types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterSnapshots(context.TODO(),
  &rds.DescribeDBClusterSnapshotsInput{
   DBClusterSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBClusterSnapshots[0], nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void waitForSnapshotReady(RdsClient rdsClient, String
dbSnapshotIdentifier,
           String dbInstanceClusterIdentifier) {
       try {
           boolean snapshotReady = false;
           String snapshotReadyStr;
           System.out.println("Waiting for the snapshot to become available.");

           DescribeDbClusterSnapshotsRequest snapshotsRequest =
DescribeDbClusterSnapshotsRequest.builder()
                   .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .build();

           while (!snapshotReady) {
               DescribeDbClusterSnapshotsResponse response =
rdsClient.describeDBClusterSnapshots(snapshotsRequest);
               List<DBClusterSnapshot> snapshotList =
response.dbClusterSnapshots();
               for (DBClusterSnapshot snapshot : snapshotList) {
                   snapshotReadyStr = snapshot.status();
                   if (snapshotReadyStr.contains("available")) {
                       snapshotReady = true;
                   } else {
                       System.out.println(".");
                       Thread.sleep(sleepTime * 5000);
                   }
               }
           }

           System.out.println("The Snapshot is available!");
```

```
        } catch (RdsException | InterruptedException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitSnapshotReady(dbSnapshotIdentifier: String?,
 dbInstanceClusterIdentifier: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbClusterSnapshotsRequest {
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
        dbClusterIdentifier = dbInstanceClusterIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!snapshotReady) {
            val response = rdsClient.describeDbClusterSnapshots(snapshotsRequest)
            val snapshotList = response.dbClusterSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
                    } else {
```

```
                        println(".")
                        delay(slTime * 5000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)
```

```
    def get_cluster_snapshot(self, snapshot_id):
        """
        Gets a DB cluster snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_cluster_snapshots(
                DBClusterSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBClusterSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get DB cluster snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots na Referência da API AWSSDK for Python (Boto3).

Descrever os clusters de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever clusters de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   /// <summary>
   /// Returns a list of DB clusters.
   /// </summary>
   /// <param name="dbInstanceIdentifier">Optional name of a specific DB
cluster.</param>
   /// <returns>List of DB clusters.</returns>
   public async Task<List<DBCluster>> DescribeDBClustersPagedAsync(string?
dbClusterIdentifier = null)
   {
       var results = new List<DBCluster>();

       DescribeDBClustersResponse response;
       DescribeDBClustersRequest request = new DescribeDBClustersRequest
       {
           DBClusterIdentifier = dbClusterIdentifier
       };
       // Get the full list if there are multiple pages.
       do
       {
           response = await _amazonRDS.DescribeDBClustersAsync(request);
           results.AddRange(response.DBClusters);
           request.Marker = response.Marker;
       }
       while (response.Marker is not null);
       return results;
   }
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
                  << outcome.GetError().GetMessage()
```

```
                    << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetDbCluster gets data about an Aurora DB cluster.
func (clusters *DbClusters) GetDbCluster(clusterName string) (*types.DBCluster,
 error) {
 output, err := clusters.AuroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{
   DBClusterIdentifier: aws.String(clusterName),
  })
 if err != nil {
```

```
  var notFoundError *types.DBClusterNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB cluster %v does not exist.\n", clusterName)
   err = nil
  } else {
   log.Printf("Couldn't get DB cluster %v: %v\n", clusterName, err)
  }
  return nil, err
 } else {
  return &output.DBClusters[0], err
 }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
       try {
           DescribeDbClusterParametersRequest dbParameterGroupsRequest;
           if (flag == 0) {
               dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                       .dbClusterParameterGroupName(dbCLusterGroupName)
                       .build();
           } else {
               dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                       .dbClusterParameterGroupName(dbCLusterGroupName)
```

```
                        .source("user")
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset
or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") ==
0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is
 ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
```

```
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_cluster(self, cluster_name):
        """
        Gets data about an Aurora DB cluster.
```

```
        :param cluster_name: The name of the DB cluster to retrieve.
        :return: The retrieved DB cluster.
        """
        try:
            response = self.rds_client.describe_db_clusters(
                DBClusterIdentifier=cluster_name
            )
            cluster = response["DBClusters"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBClusterNotFoundFault":
                logger.info("Cluster %s does not exist.", cluster_name)
            else:
                logger.error(
                    "Couldn't verify the existence of DB cluster %s. Here's why:
%s: %s",
                    cluster_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return cluster
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
```

```
   // Create an Aurora DB cluster database cluster that contains a MySql
database and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine
and engine version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql',
EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
for DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(),
ScenarioError> {
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
           return Err(ScenarioError::new(
               "Failed to create DB Cluster with cluster group",
               &err,
           ));
       }

       self.db_cluster_identifier = create_db_cluster
           .unwrap()
           .db_cluster
           .and_then(|c| c.db_cluster_identifier);

       if self.db_cluster_identifier.is_none() {
```

```
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;
```

```
            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for
ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() ==
Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }
```

```
            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn describe_db_clusters(
        &self,
        id: &str,
    ) -> Result<DescribeDbClustersOutput, SdkError<DescribeDBClustersError>> {
        self.inner
            .describe_db_clusters()
            .db_cluster_identifier(id)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
```

```
.db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
```

```
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
```

```
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message
 == "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));
```

```
    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message
 == "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
```

```
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message
 == "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
```

```
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()
```

```
 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DescreverDBClusters na AWS Referência da API SDK para Rust.

Descrever as instâncias de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever instâncias de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstancesPagedAsync(string?
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance
 &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
```

```
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetInstance gets data about a DB instance.
func (clusters *DbClusters) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := clusters.AuroraClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
```

```
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Waits until the database instance is available.
   public static void waitForInstanceReady(RdsClient rdsClient, String
dbClusterIdentifier) {
       boolean instanceReady = false;
       String instanceReadyStr;
       System.out.println("Waiting for instance to become available.");
       try {
           DescribeDbClustersRequest instanceRequest =
DescribeDbClustersRequest.builder()
                   .dbClusterIdentifier(dbClusterIdentifier)
                   .build();
```

```
            while (!instanceReady) {
                DescribeDbClustersResponse response =
 rdsClient.describeDBClusters(instanceRequest);
                List<DBCluster> clusterList = response.dbClusters();
                for (DBCluster cluster : clusterList) {
                    instanceReadyStr = cluster.status();
                    if (instanceReadyStr.contains("available")) {
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database cluster is available!");

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitDBAuroraInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")
    val instanceRequest = DescribeDbInstancesRequest {
```

```
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    var endpoint = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            response.dbInstances?.forEach { instance ->
                instanceReadyStr = instance.dbInstanceStatus.toString()
                if (instanceReadyStr.contains("available")) {
                    endpoint = instance.endpoint?.address.toString()
                    instanceReady = true
                } else {
                    print(".")
                    delay(sleepTime * 1000)
                }
            }
        }
    }
    println("Database instance is available! The connection endpoint is
 $endpoint")
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
```

```
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances =
self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
```

```
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
```

```
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
```

```
        }

        // Delete the DB cluster parameter group.
 rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn describe_db_instances(
        &self,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner.describe_db_instances().send().await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
```

```
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
```

```
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
```

```
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
```

```
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
Describe Instances
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DescreverInstânciasDB na AWS Referência da API SDK para Rust.

Descrever as versões de mecanismo de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram as versões de mecanismo de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">The name of the engine.</param>
    /// <param name="parameterGroupFamily">Optional parameter group family
 name.</param>
    /// <returns>A list of DBEngineVersions.</returns>
```

```
    public async Task<List<DBEngineVersion>>
 DescribeDBEngineVersionsForEngineAsync(string engine,
        string? parameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = parameterGroupFamily
            });
        return response.DBEngineVersions;
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
```

```
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (clusters *DbClusters) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := clusters.AuroraClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDBEngines(RdsClient rdsClient) {
       try {
           DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                   .engine("aurora-mysql")
                   .defaultOnly(true)
                   .maxRecords(20)
                   .build();

           DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
           List<DBEngineVersion> engines = response.dbEngineVersions();

           // Get all DBEngineVersion objects.
           for (DBEngineVersion engineOb : engines) {
               System.out.println("The name of the DB parameter group family for
the database engine is "
                       + engineOb.dbParameterGroupFamily());
               System.out.println("The name of the database engine " +
engineOb.engine());
               System.out.println("The version number of the database engine " +
engineOb.engineVersion());
           }

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get a list of allowed engine versions.
suspend fun getAllowedClusterEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        response.dbEngineVersions?.forEach { dbEngine ->
            println("The engine version is ${dbEngine.engineVersion}")
            println("The engine description is ${dbEngine.dbEngineDescription}")
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned
 list of
                                        engine versions to those that are
 compatible with
                                        this parameter group family.
        :return: The list of database engine versions.
        """
```

```
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na Referência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get available engine families for Aurora MySql.
rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
   pub async fn get_engines(&self) -> Result<HashMap<String, Vec<String>>,
ScenarioError> {
       let describe_db_engine_versions =
self.rds.describe_db_engine_versions(DB_ENGINE).await;
       trace!(versions=?describe_db_engine_versions, "full list of versions");
```

```
        if let Err(err) = describe_db_engine_versions {
            return Err(ScenarioError::new(
                "Failed to retrieve DB Engine Versions",
                &err,
            ));
        };

        let version_count = describe_db_engine_versions
            .as_ref()
            .map(|o| o.db_engine_versions().len())
            .unwrap_or_default();
        info!(version_count, "got list of versions");

        // Create a map of engine families to their available versions.
        let mut versions = HashMap::<String, Vec<String>>::new();
        describe_db_engine_versions
            .unwrap()
            .db_engine_versions()
            .iter()
            .filter_map(
                |v| match (&v.db_parameter_group_family, &v.engine_version) {
                    (Some(family), Some(version)) => Some((family.clone(),
version.clone())),
                    _ => None,
                },
            )
            .for_each(|(family, version)|
versions.entry(family).or_default().push(version));

        Ok(versions)
    }

    pub async fn describe_db_engine_versions(
        &self,
        engine: &str,
    ) -> Result<DescribeDbEngineVersionsOutput,
SdkError<DescribeDBEngineVersionsError>> {
        self.inner
            .describe_db_engine_versions()
            .engine(engine)
            .send()
            .await
    }
```

```
#[tokio::test]
async fn test_scenario_get_engines() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Ok(DescribeDbEngineVersionsOutput::builder()
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1a")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1b")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f2")
                        .engine_version("f2a")
                        .build(),
                )
                .db_engine_versions(DbEngineVersion::builder().build())
                .build())
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;

    assert_eq!(
        versions_map,
        Ok(HashMap::from([
            ("f1".into(), vec!["f1a".into(), "f1b".into()]),
            ("f2".into(), vec!["f2a".into()])
        ]))
    );
}
```

```
#[tokio::test]
async fn test_scenario_get_engines_failed() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBEngineVersionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_engine_versions error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;
    assert_matches!(
        versions_map,
        Err(ScenarioError { message, context: _ }) if message == "Failed to
 retrieve DB Engine Versions"
    );
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na referência da API AWSSDK for Rust.

Descrever as opções de instâncias de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever as opções de instâncias de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Get a list of orderable DB instance options for a specific
   /// engine and engine version.
   /// </summary>
   /// <param name="engine">Name of the engine.</param>
   /// <param name="engineVersion">Version of the engine.</param>
   /// <returns>List of OrderableDBInstanceOptions.</returns>
   public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptionsPagedAsync(string engine, string
engineVersion)
   {
       // Use a paginator to get a list of DB instance options.
       var results = new List<OrderableDBInstanceOption>();
       var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
           new DescribeOrderableDBInstanceOptionsRequest()
           {
               Engine = engine,
               EngineVersion = engineVersion,
           });
       // Get the entire list using the paginator.
       await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
       {
           results.Add(instanceOptions);
       }
       return results;
   }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for .NET API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
```

```
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption>
 &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option:
 options) {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                instanceClasses.push_back(instanceClass);
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions.
 "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine
 are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for C++ API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (clusters *DbClusters) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instances []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(clusters.AuroraClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instances: %v\n", err)
   break
  } else {
   instances = append(instances, output.OrderableDBInstanceOptions...)
  }
 }
```

```
 return instances, err
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Go API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .engine("aurora-mysql")
                    .defaultOnly(true)
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
engineOb.engine());
                System.out.println("The version number of the database engine " +
engineOb.engineVersion());
            }
```

```
        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Java 2.x API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_orderable_instances(self, db_engine, db_engine_version):
```

```
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by
the DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts
```

- Para obter detalhes da API, consulte DescribeOrderableReferência da API DB InstanceOptions in AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   pub async fn get_instance_classes(&self) -> Result<Vec<String>,
ScenarioError> {
       let describe_orderable_db_instance_options_items = self
           .rds
           .describe_orderable_db_instance_options(
               DB_ENGINE,
               self.engine_version
                   .as_ref()
                   .expect("engine version for db instance options")
                   .as_str(),
           )
           .await;

       describe_orderable_db_instance_options_items
           .map(|options| {
               options
                   .iter()
                   .map(|o|
o.db_instance_class().unwrap_or_default().to_string())
                   .collect::<Vec<String>>()
           })
           .map_err(|err| ScenarioError::new("Could not get available instance
classes", &err))
   }

   pub async fn describe_orderable_db_instance_options(
       &self,
       engine: &str,
       engine_version: &str,
   ) -> Result<Vec<OrderableDbInstanceOption>,
SdkError<DescribeOrderableDBInstanceOptionsError>>
   {
```

```
        self.inner
            .describe_orderable_db_instance_options()
            .engine(engine)
            .engine_version(engine_version)
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
    }

#[tokio::test]
async fn test_scenario_get_instance_classes() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Ok(vec![
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t1")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t2")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t3")
                    .build(),
            ])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario
        .set_engine("aurora-mysql", "aurora-mysql8.0")
```

```
        .await
        .expect("set engine");

    let instance_classes = scenario.get_instance_classes().await;

    assert_eq!(
        instance_classes,
        Ok(vec!["t1".into(), "t2".into(), "t3".into()])
    );
}

#[tokio::test]
async fn test_scenario_get_instance_classes_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Err(SdkError::service_error(

 DescribeOrderableDBInstanceOptionsError::unhandled(Box::new(Error::new(
                   ErrorKind::Other,
                   "describe_orderable_db_instance_options_error",
               ))),
               Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_family = Some("aurora-mysql".into());
    scenario.engine_version = Some("aurora-mysql8.0".into());

    let instance_classes = scenario.get_instance_classes().await;

    assert_matches!(
        instance_classes,
        Err(ScenarioError {message, context: _}) if message == "Could not get
 available instance classes"
    );
}
```

- Para obter detalhes da API, consulte a referência da API DescribeOrderableDB InstanceOptions in AWS SDK for Rust.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como descrever parâmetros de um grupo de parâmetros de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the cluster parameters in a parameter group.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <param name="source">The optional name of the source filter.</param>
    /// <returns>The collection of parameters.</returns>
    public async Task<List<Parameter>>
DescribeDBClusterParametersInGroupAsync(string groupName, string? source = null)
    {
        var paramList = new List<Parameter>();

        DescribeDBClusterParametersResponse response;
        var request = new DescribeDBClusterParametersRequest
        {
            DBClusterParameterGroupName = groupName,
            Source = source,
```

```
        };

        // Get the full list if there are multiple pages.
        do
        {
            response = await
 _amazonRDS.DescribeDBClusterParametersAsync(request);
            paramList.AddRange(response.Parameters);

            request.Marker = response.Marker;
        }
        while (response.Marker is not null);

        return paramList;
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBCLusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
```

```
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBCLusterParameters(const Aws::String
 &parameterGroupName,
                                             const Aws::String &namePrefix,
                                             const Aws::String &source,

 Aws::Vector<Aws::RDS::Model::Parameter> &parametersResult,
                                             const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
```

```
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetParameters gets the parameters that are contained in a DB cluster parameter
 group.
func (clusters *DbClusters) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBClusterParametersOutput
 var params []types.Parameter
 var err error
```

```
 parameterPaginator :=
 rds.NewDescribeDBClusterParametersPaginator(clusters.AuroraClient,
  &rds.DescribeDBClusterParametersInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Source:                      aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get paramaeters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
       try {
           DescribeDbClusterParametersRequest dbParameterGroupsRequest;
           if (flag == 0) {
               dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                       .dbClusterParameterGroupName(dbCLusterGroupName)
```

```
                        .build();
            } else {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset
or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") ==
0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is
 ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB cluster parameter group.
```

```
        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this
prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBClusterParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator =
self.rds_client.get_paginator("describe_db_cluster_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na Referência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get the parameter group. rds.DescribeDbClusterParameterGroups
   // Get parameters in the group. This is a long list so you will have to
paginate. Find the auto_increment_offset and auto_increment_increment parameters
(by ParameterName). rds.DescribeDbClusterParameters
   // Parse the ParameterName, Description, and AllowedValues values and display
them.
   pub async fn cluster_parameters(&self) ->
Result<Vec<AuroraScenarioParameter>, ScenarioError> {
       let parameters_output = self
           .rds
           .describe_db_cluster_parameters(DB_CLUSTER_PARAMETER_GROUP_NAME)
           .await;

       if let Err(err) = parameters_output {
           return Err(ScenarioError::new(
               format!("Failed to retrieve parameters for
{DB_CLUSTER_PARAMETER_GROUP_NAME}"),
               &err,
           ));
       }

       let parameters = parameters_output
           .unwrap()
           .into_iter()
           .flat_map(|p| p.parameters.unwrap_or_default().into_iter())
           .filter(|p|
FILTER_PARAMETER_NAMES.contains(p.parameter_name().unwrap_or_default()))
           .map(AuroraScenarioParameter::from)
           .collect::<Vec<_>>();

       Ok(parameters)
   }
```

```
    pub async fn describe_db_cluster_parameters(
        &self,
        name: &str,
    ) -> Result<Vec<DescribeDbClusterParametersOutput>,
 SdkError<DescribeDBClusterParametersError>>
    {
        self.inner
            .describe_db_cluster_parameters()
            .db_cluster_parameter_group_name(name)
            .into_paginator()
            .send()
            .try_collect()
            .await
    }

#[tokio::test]
async fn test_scenario_cluster_parameters() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Ok(vec![DescribeDbClusterParametersOutput::builder()
                .parameters(Parameter::builder().parameter_name("a").build())
                .parameters(Parameter::builder().parameter_name("b").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("c").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("d").build())
                .build()])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
```

```
    let params = scenario.cluster_parameters().await.expect("cluster params");
    let names: Vec<String> = params.into_iter().map(|p| p.name).collect();
    assert_eq!(
        names,
        vec!["auto_increment_offset", "auto_increment_increment"]
    );
}

#[tokio::test]
async fn test_scenario_cluster_parameters_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBClusterParametersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_cluster_parameters_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let params = scenario.cluster_parameters().await;
    assert_matches!(params, Err(ScenarioError { message, context: _ }) if message
 == "Failed to retrieve parameters for RustSDKCodeExamplesDBParameterGroup");
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na referência da API AWSSDK for Rust.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar os parâmetros de um grupo de parâmetros de cluster de banco de dados do Aurora.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar clusters de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Modify the specified integer parameters with new values from user input.
    /// </summary>
    /// <param name="groupName">The group name for the parameters.</param>
    /// <param name="parameters">The list of integer parameters to modify.</
param>
    /// <param name="newValue">Optional int value to set for parameters.</param>
    /// <returns>The name of the group that was modified.</returns>
    public async Task<string> ModifyIntegerParametersInGroupAsync(string
 groupName, List<Parameter> parameters, int newValue = 0)
    {
        foreach (var p in parameters)
        {
            if (p.IsModifiable && p.DataType == "integer")
            {
                while (newValue == 0)
                {
                    Console.WriteLine(
                        $"Enter a new value for {p.ParameterName} from the
 allowed values {p.AllowedValues} ");
```

```
                    var choice = Console.ReadLine();
                    int.TryParse(choice, out newValue);
                }

                p.ParameterValue = newValue.ToString();
            }
        }

        var request = new ModifyDBClusterParameterGroupRequest
        {
            Parameters = parameters,
            DBClusterParameterGroupName = groupName,
        };

        var result = await
_amazonRDS.ModifyDBClusterParameterGroupAsync(request);
        return result.DBClusterParameterGroupName;
    }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
```

```
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
                client.ModifyDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully
 modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// UpdateParameters updates parameters in a named DB cluster parameter group.
func (clusters *DbClusters) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
```

```
 _, err := clusters.AuroraClient.ModifyDBClusterParameterGroup(context.TODO(),
  &rds.ModifyDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Parameters:                  params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameterGroups(RdsClient rdsClient,
String dbClusterGroupName) {
       try {
           DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .maxRecords(20)
                   .build();

           List<DBClusterParameterGroup> groups =
rdsClient.describeDBClusterParameterGroups(groupsRequest)
                   .dbClusterParameterGroups();
           for (DBClusterParameterGroup group : groups) {
```

```
                System.out.println("The group name is " +
 group.dbClusterParameterGroupName());
                System.out.println("The group ARN is " +
 group.dbClusterParameterGroupArn());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Modify the auto_increment_offset parameter.
suspend fun modifyDBClusterParas(dClusterGroupName: String?) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.fromValue("immediate")
        parameterValue = "5"
    }

    val paraList = ArrayList<Parameter>()
    paraList.add(parameter1)
    val groupRequest = ModifyDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dClusterGroupName
        parameters = paraList
    }
```

```
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbClusterParameterGroup(groupRequest)
        println("The parameter group ${response.dbClusterParameterGroupName} was
 successfully modified")
    }
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na referência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def update_parameters(self, parameter_group_name, update_parameters):
```

```
        """
        Updates parameters in a custom DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                Parameters=update_parameters,
            )
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API ModifyDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Modify both the auto_increment_offset and auto_increment_increment
parameters in one call in the custom parameter group. Set their ParameterValue
fields to a new allowable value. rds.ModifyDbClusterParameterGroup.
```

```
    pub async fn update_auto_increment(
        &self,
        offset: u8,
        increment: u8,
    ) -> Result<(), ScenarioError> {
        let modify_db_cluster_parameter_group = self
            .rds
            .modify_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value(format!("{offset}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value(format!("{increment}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ],
            )
            .await;

        if let Err(error) = modify_db_cluster_parameter_group {
            return Err(ScenarioError::new(
                "Failed to modify cluster parameter group",
                &error,
            ));
        }

        Ok(())
    }

    pub async fn modify_db_cluster_parameter_group(
        &self,
        name: &str,
        parameters: Vec<Parameter>,
    ) -> Result<ModifyDbClusterParameterGroupOutput,
SdkError<ModifyDBClusterParameterGroupError>>
    {
        self.inner
            .modify_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
```

```
            .set_parameters(Some(parameters))
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_update_auto_increment() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .withf(|name, params| {
            assert_eq!(name, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(
                params,
                &vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value("10")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value("20")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ]
            );
            true
        })
        .return_once(|_, _|
 Ok(ModifyDbClusterParameterGroupOutput::builder().build()));

    let scenario = AuroraScenario::new(mock_rds);

    scenario
        .update_auto_increment(10, 20)
        .await
        .expect("update auto increment");
}

#[tokio::test]
async fn test_scenario_update_auto_increment_error() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .return_once(|_, _| {
            Err(SdkError::service_error(

 ModifyDBClusterParameterGroupError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "modify_db_cluster_parameter_group_error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let update = scenario.update_auto_increment(10, 20).await;
    assert_matches!(update, Err(ScenarioError { message, context: _}) if message
 == "Failed to modify cluster parameter group");
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Cenários para o Aurora usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Aurora com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Começar a usar os clusters de banco de dados do Aurora usando um AWS SDK

Começar a usar os clusters de banco de dados do Aurora usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
using Amazon.RDS;
using Amazon.RDS.Model;
using AuroraActions;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;
using Microsoft.Extensions.Logging;
using Microsoft.Extensions.Logging.Console;
using Microsoft.Extensions.Logging.Debug;

namespace AuroraScenario;

/// <summary>
/// Scenario for Amazon Aurora examples.
/// </summary>
public class AuroraScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks:
```

```
   1.  Return a list of the available DB engine families for Aurora MySql using
the DescribeDBEngineVersionsAsync method.
   2.  Select an engine family and create a custom DB cluster parameter group
using the CreateDBClusterParameterGroupAsync method.
   3.  Get the parameter group using the DescribeDBClusterParameterGroupsAsync
method.
   4.  Get some parameters in the group using the
DescribeDBClusterParametersAsync method.
   5.  Parse and display some parameters in the group.
   6.  Modify the auto_increment_offset and auto_increment_increment parameters
       using the ModifyDBClusterParameterGroupAsync method.
   7.  Get and display the updated parameters using the
DescribeDBClusterParametersAsync method with a source of "user".
   8.  Get a list of allowed engine versions using the
DescribeDBEngineVersionsAsync method.
   9.  Create an Aurora DB cluster that contains a MySql database and uses the
parameter group.
       using the CreateDBClusterAsync method.
   10. Wait for the DB cluster to be ready using the DescribeDBClustersAsync
method.
   11. Display and select from a list of instance classes available for the
selected engine and version
       using the paginated DescribeOrderableDBInstanceOptions method.
   12. Create a database instance in the cluster using the CreateDBInstanceAsync
method.
   13. Wait for the DB instance to be ready using the DescribeDBInstances
method.
   14. Display the connection endpoint string for the new DB cluster.
   15. Create a snapshot of the DB cluster using the
CreateDBClusterSnapshotAsync method.
   16. Wait for DB snapshot to be ready using the
DescribeDBClusterSnapshotsAsync method.
   17. Delete the DB instance using the DeleteDBInstanceAsync method.
   18. Delete the DB cluster using the DeleteDBClusterAsync method.
   19. Wait for DB cluster to be deleted using the DescribeDBClustersAsync
methods.
   20. Delete the cluster parameter group using the
DeleteDBClusterParameterGroupAsync.
   */

   private static readonly string sepBar = new('-', 80);
   private static AuroraWrapper auroraWrapper = null!;
   private static ILogger logger = null!;
   private static readonly string engine = "aurora-mysql";
```

```
    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon Relational Database Service
(Amazon RDS).
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRDS>()
                    .AddTransient<AuroraWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder =>
        {
            builder.AddConsole();
        }).CreateLogger<AuroraScenario>();

        auroraWrapper = host.Services.GetRequiredService<AuroraWrapper>();

        Console.WriteLine(sepBar);
        Console.WriteLine(
            "Welcome to the Amazon Aurora: get started with DB clusters
example.");
        Console.WriteLine(sepBar);

        DBClusterParameterGroup parameterGroup = null!;
        DBCluster? newCluster = null;
        DBInstance? newInstance = null;

        try
        {
            var parameterGroupFamily = await ChooseParameterGroupFamilyAsync();

            parameterGroup = await
CreateDBParameterGroupAsync(parameterGroupFamily);

            var parameters = await
DescribeParametersInGroupAsync(parameterGroup.DBClusterParameterGroupName,
```

```
                new List<string> { "auto_increment_offset",
"auto_increment_increment" });

            await
ModifyParametersAsync(parameterGroup.DBClusterParameterGroupName, parameters);

            await
DescribeUserSourceParameters(parameterGroup.DBClusterParameterGroupName);

            var engineVersionChoice = await
ChooseDBEngineVersionAsync(parameterGroupFamily);

            var newClusterIdentifier = "Example-Cluster-" + DateTime.Now.Ticks;

            newCluster = await CreateNewCluster
            (
                parameterGroup,
                engine,
                engineVersionChoice.EngineVersion,
                newClusterIdentifier
            );

            var instanceClassChoice = await ChooseDBInstanceClass(engine,
engineVersionChoice.EngineVersion);

            var newInstanceIdentifier = "Example-Instance-" + DateTime.Now.Ticks;

            newInstance = await CreateNewInstance(
                newClusterIdentifier,
                engine,
                engineVersionChoice.EngineVersion,
                instanceClassChoice.DBInstanceClass,
                newInstanceIdentifier
            );

            DisplayConnectionString(newCluster!);
            await CreateSnapshot(newCluster!);
            await CleanupResources(newInstance, newCluster, parameterGroup);

            Console.WriteLine("Scenario complete.");
            Console.WriteLine(sepBar);
        }
        catch (Exception ex)
```

```
        {
            await CleanupResources(newInstance, newCluster, parameterGroup);
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// Choose the Aurora DB parameter group family from a list of available
options.
    /// </summary>
    /// <returns>The selected parameter group family.</returns>
    public static async Task<string> ChooseParameterGroupFamilyAsync()
    {
        Console.WriteLine(sepBar);
        // 1. Get a list of available engines.
        var engines = await
auroraWrapper.DescribeDBEngineVersionsForEngineAsync(engine);

        Console.WriteLine($"1. The following is a list of available DB parameter
group families for engine {engine}:");

        var parameterGroupFamilies =
            engines.GroupBy(e => e.DBParameterGroupFamily).ToList();
        for (var i = 1; i <= parameterGroupFamilies.Count; i++)
        {
            var parameterGroupFamily = parameterGroupFamilies[i - 1];
            // List the available parameter group families.
            Console.WriteLine(
                $"\t{i}. Family: {parameterGroupFamily.Key}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > parameterGroupFamilies.Count)
        {
            Console.WriteLine("2. Select an available DB parameter group family
by entering a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        var parameterGroupFamilyChoice = parameterGroupFamilies[choiceNumber -
1];
        Console.WriteLine(sepBar);
        return parameterGroupFamilyChoice.Key;
    }
```

```
    /// <summary>
    /// Create and get information on a DB parameter group.
    /// </summary>
    /// <param name="dbParameterGroupFamily">The DBParameterGroupFamily for the
 new DB parameter group.</param>
    /// <returns>The new DBParameterGroup.</returns>
    public static async Task<DBClusterParameterGroup>
 CreateDBParameterGroupAsync(string dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"2. Create new DB parameter group with family
 {dbParameterGroupFamily}:");

        var parameterGroup = await
 auroraWrapper.CreateCustomClusterParameterGroupAsync(
            dbParameterGroupFamily,
            "ExampleParameterGroup-" + DateTime.Now.Ticks,
            "New example parameter group");

        var groupInfo =
            await
 auroraWrapper.DescribeCustomDBClusterParameterGroupAsync(parameterGroup.DBClusterParamet

        Console.WriteLine(
            $"3. New DB parameter group created: \n\t{groupInfo?.Description}, \n
\tARN {groupInfo?.DBClusterParameterGroupName}");
        Console.WriteLine(sepBar);
        return parameterGroup;
    }

    /// <summary>
    /// Get and describe parameters from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">The name of the DBParameterGroup.</
param>
    /// <param name="parameterNames">Optional specific names of parameters to
 describe.</param>
    /// <returns>The list of requested parameters.</returns>
    public static async Task<List<Parameter>>
 DescribeParametersInGroupAsync(string parameterGroupName, List<string>?
 parameterNames = null)
    {
        Console.WriteLine(sepBar);
```

```
        Console.WriteLine("4. Get some parameters from the group.");
        Console.WriteLine(sepBar);

        var parameters =
            await
auroraWrapper.DescribeDBClusterParametersInGroupAsync(parameterGroupName);

        var matchingParameters =
            parameters.Where(p => parameterNames == null ||
parameterNames.Contains(p.ParameterName)).ToList();

        Console.WriteLine("5. Parameter information:");
        matchingParameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);

        return matchingParameters;
    }

    /// <summary>
    /// Modify a parameter from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameters">The parameters to modify.</param>
    /// <returns>Async task.</returns>
    public static async Task ModifyParametersAsync(string parameterGroupName,
List<Parameter> parameters)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("6. Modify some parameters in the group.");

        await
auroraWrapper.ModifyIntegerParametersInGroupAsync(parameterGroupName,
parameters);

        Console.WriteLine(sepBar);
    }

    /// <summary>
```

```
    /// Describe the user source parameters in the group.
    /// </summary>
    /// <param name="parameterGroupName">The name of the DBParameterGroup.</
param>
    /// <returns>Async task.</returns>
    public static async Task DescribeUserSourceParameters(string
 parameterGroupName)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("7. Describe updated user source parameters in the
 group.");

        var parameters =
            await
 auroraWrapper.DescribeDBClusterParametersInGroupAsync(parameterGroupName,
 "user");

        parameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Choose a DB engine version.
    /// </summary>
    /// <param name="dbParameterGroupFamily">DB parameter group family for engine
 choice.</param>
    /// <returns>The selected engine version.</returns>
    public static async Task<DBEngineVersion> ChooseDBEngineVersionAsync(string
 dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed engines.
        var allowedEngines =
            await auroraWrapper.DescribeDBEngineVersionsForEngineAsync(engine,
 dbParameterGroupFamily);

        Console.WriteLine($"Available DB engine versions for parameter group
 family {dbParameterGroupFamily}:");
```

```
        int i = 1;
        foreach (var version in allowedEngines)
        {
            Console.WriteLine(
                $"\t{i}. Engine: {version.Engine} Version
 {version.EngineVersion}.");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedEngines.Count)
        {
            Console.WriteLine("8. Select an available DB engine version by
 entering a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var engineChoice = allowedEngines[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return engineChoice;
    }

    /// <summary>
    /// Create a new RDS DB cluster.
    /// </summary>
    /// <param name="parameterGroup">Parameter group to use for the DB cluster.</
param>
    /// <param name="engineName">Engine to use for the DB cluster.</param>
    /// <param name="engineVersion">Engine version to use for the DB cluster.</
param>
    /// <param name="clusterIdentifier">Cluster identifier to use for the DB
 cluster.</param>
    /// <returns>The new DB cluster.</returns>
    public static async Task<DBCluster?> CreateNewCluster(DBClusterParameterGroup
 parameterGroup,
        string engineName, string engineVersion, string clusterIdentifier)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"9. Create a new DB cluster with identifier
 {clusterIdentifier}.");

        DBCluster newCluster;
        var clusters = await auroraWrapper.DescribeDBClustersPagedAsync();
```

```
        var isClusterCreated = clusters.Any(i => i.DBClusterIdentifier ==
clusterIdentifier);

        if (isClusterCreated)
        {
            Console.WriteLine("Cluster already created.");
            newCluster = clusters.First(i => i.DBClusterIdentifier ==
clusterIdentifier);
        }
        else
        {
            Console.WriteLine("Enter an admin username:");
            var username = Console.ReadLine();

            Console.WriteLine("Enter an admin password:");
            var password = Console.ReadLine();

            newCluster = await auroraWrapper.CreateDBClusterWithAdminAsync(
                "ExampleDatabase",
                clusterIdentifier,
                parameterGroup.DBClusterParameterGroupName,
                engineName,
                engineVersion,
                username!,
                password!
            );

            Console.WriteLine("10. Waiting for DB cluster to be ready...");
            while (newCluster.Status != "available")
            {
                Console.Write(".");
                Thread.Sleep(5000);
                clusters = await
auroraWrapper.DescribeDBClustersPagedAsync(clusterIdentifier);
                newCluster = clusters.First();
            }
        }

        Console.WriteLine(sepBar);
        return newCluster;
    }

    /// <summary>
    /// Choose a DB instance class for a particular engine and engine version.
```

```
    /// </summary>
    /// <param name="engine">DB engine for DB instance choice.</param>
    /// <param name="engineVersion">DB engine version for DB instance choice.</
param>
    /// <returns>The selected orderable DB instance option.</returns>
    public static async Task<OrderableDBInstanceOption>
 ChooseDBInstanceClass(string engine, string engineVersion)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed DB instance classes.
        var allowedInstances =
            await
 auroraWrapper.DescribeOrderableDBInstanceOptionsPagedAsync(engine,
 engineVersion);

        Console.WriteLine($"Available DB instance classes for engine {engine} and
 version {engineVersion}:");
        int i = 1;


        foreach (var instance in allowedInstances)
        {
            Console.WriteLine(
                $"\t{i}. Instance class: {instance.DBInstanceClass} (storage type
 {instance.StorageType})");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedInstances.Count)
        {
            Console.WriteLine("11. Select an available DB instance class by
 entering a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var instanceChoice = allowedInstances[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return instanceChoice;
    }

    /// <summary>
    /// Create a new DB instance.
```

```
    /// </summary>
    /// <param name="engineName">Engine to use for the DB instance.</param>
    /// <param name="engineVersion">Engine version to use for the DB instance.</
param>
    /// <param name="instanceClass">Instance class to use for the DB instance.</
param>
    /// <param name="instanceIdentifier">Instance identifier to use for the DB
 instance.</param>
    /// <returns>The new DB instance.</returns>
    public static async Task<DBInstance?> CreateNewInstance(
        string clusterIdentifier,
        string engineName,
        string engineVersion,
        string instanceClass,
        string instanceIdentifier)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"12. Create a new DB instance with identifier
 {instanceIdentifier}.");
        bool isInstanceReady = false;
        DBInstance newInstance;
        var instances = await auroraWrapper.DescribeDBInstancesPagedAsync();
        isInstanceReady = instances.FirstOrDefault(i =>
            i.DBInstanceIdentifier == instanceIdentifier)?.DBInstanceStatus ==
 "available";

        if (isInstanceReady)
        {
            Console.WriteLine("Instance already created.");
            newInstance = instances.First(i => i.DBInstanceIdentifier ==
 instanceIdentifier);
        }
        else
        {

            newInstance = await auroraWrapper.CreateDBInstanceInClusterAsync(
                clusterIdentifier,
                instanceIdentifier,
                engineName,
                engineVersion,
                instanceClass
            );

            Console.WriteLine("13. Waiting for DB instance to be ready...");
```

```
            while (!isInstanceReady)
            {
                Console.Write(".");
                Thread.Sleep(5000);
                instances = await
 auroraWrapper.DescribeDBInstancesPagedAsync(instanceIdentifier);
                isInstanceReady = instances.FirstOrDefault()?.DBInstanceStatus ==
 "available";
                newInstance = instances.First();
            }
        }

        Console.WriteLine(sepBar);
        return newInstance;
    }

    /// <summary>
    /// Display a connection string for an Amazon RDS DB cluster.
    /// </summary>
    /// <param name="cluster">The DB cluster to use to get a connection string.</
param>
    public static void DisplayConnectionString(DBCluster cluster)
    {
        Console.WriteLine(sepBar);
        // Display the connection string.
        Console.WriteLine("14. New DB cluster connection string: ");
        Console.WriteLine(
            $"\n{engine} -h {cluster.Endpoint} -P {cluster.Port} "
            + $"-u {cluster.MasterUsername} -p [YOUR PASSWORD]\n");

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Create a snapshot from an Amazon RDS DB cluster.
    /// </summary>
    /// <param name="cluster">DB cluster to use when creating a snapshot.</param>
    /// <returns>The snapshot object.</returns>
    public static async Task<DBClusterSnapshot> CreateSnapshot(DBCluster cluster)
    {
        Console.WriteLine(sepBar);
        // Create a snapshot.
        Console.WriteLine($"15. Creating snapshot from DB cluster
 {cluster.DBClusterIdentifier}.");
```

```
        var snapshot = await
auroraWrapper.CreateClusterSnapshotByIdentifierAsync(
            cluster.DBClusterIdentifier,
            "ExampleSnapshot-" + DateTime.Now.Ticks);

        // Wait for the snapshot to be available.
        bool isSnapshotReady = false;

        Console.WriteLine($"16. Waiting for snapshot to be ready...");
        while (!isSnapshotReady)
        {
            Console.Write(".");
            Thread.Sleep(5000);
            var snapshots =
                await
auroraWrapper.DescribeDBClusterSnapshotsByIdentifierAsync(cluster.DBClusterIdentifier);
            isSnapshotReady = snapshots.FirstOrDefault()?.Status == "available";
            snapshot = snapshots.First();
        }

        Console.WriteLine(
            $"Snapshot {snapshot.DBClusterSnapshotIdentifier} status is
{snapshot.Status}.");
        Console.WriteLine(sepBar);
        return snapshot;
    }

    /// <summary>
    /// Clean up resources from the scenario.
    /// </summary>
    /// <param name="newInstance">The instance to clean up.</param>
    /// <param name="newCluster">The cluster to clean up.</param>
    /// <param name="parameterGroup">The parameter group to clean up.</param>
    /// <returns>Async Task.</returns>
    private static async Task CleanupResources(
        DBInstance? newInstance,
        DBCluster? newCluster,
        DBClusterParameterGroup? parameterGroup)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        if (newInstance is not null && GetYesNoResponse($"\tClean up instance
{newInstance.DBInstanceIdentifier}? (y/n)"))
```

```
        {
            // Delete the DB instance.
            Console.WriteLine($"17. Deleting the DB instance
{newInstance.DBInstanceIdentifier}.");
            await
auroraWrapper.DeleteDBInstanceByIdentifierAsync(newInstance.DBInstanceIdentifier);
        }

        if (newCluster is not null && GetYesNoResponse($"\tClean up cluster
{newCluster.DBClusterIdentifier}? (y/n)"))
        {
            // Delete the DB cluster.
            Console.WriteLine($"18. Deleting the DB cluster
{newCluster.DBClusterIdentifier}.");
            await
auroraWrapper.DeleteDBClusterByIdentifierAsync(newCluster.DBClusterIdentifier);

            // Wait for the DB cluster to delete.
            Console.WriteLine($"19. Waiting for the DB cluster to delete...");
            bool isClusterDeleted = false;

            while (!isClusterDeleted)
            {
                Console.Write(".");
                Thread.Sleep(5000);
                var cluster = await auroraWrapper.DescribeDBClustersPagedAsync();
                isClusterDeleted = cluster.All(i => i.DBClusterIdentifier !=
newCluster.DBClusterIdentifier);
            }

            Console.WriteLine("DB cluster deleted.");
        }

        if (parameterGroup is not null && GetYesNoResponse($"\tClean up parameter
group? (y/n)"))
        {
            Console.WriteLine($"20. Deleting the DB parameter group
{parameterGroup.DBClusterParameterGroupName}.");
            await
auroraWrapper.DeleteClusterParameterGroupByNameAsync(parameterGroup.DBClusterParameterGr
            Console.WriteLine("Parameter group deleted.");
        }

        Console.WriteLine(new string('-', 80));
```

```
    }

    /// <summary>
    /// Get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
```

Métodos de encapsulamento que são chamados pelo cenário para gerenciar as ações do Aurora.

```
using Amazon.RDS;
using Amazon.RDS.Model;

namespace AuroraActions;

/// <summary>
/// Wrapper for the Amazon Aurora cluster client operations.
/// </summary>
public class AuroraWrapper
{
    private readonly IAmazonRDS _amazonRDS;
    public AuroraWrapper(IAmazonRDS amazonRDS)
    {
        _amazonRDS = amazonRDS;
    }

    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">The name of the engine.</param>
```

```
    /// <param name="parameterGroupFamily">Optional parameter group family
 name.</param>
    /// <returns>A list of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>>
 DescribeDBEngineVersionsForEngineAsync(string engine,
        string? parameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = parameterGroupFamily
            });
        return response.DBEngineVersions;
    }

    /// <summary>
    /// Create a custom cluster parameter group.
    /// </summary>
    /// <param name="parameterGroupFamily">The family of the parameter group.</
param>
    /// <param name="groupName">The name for the new parameter group.</param>
    /// <param name="description">A description for the new parameter group.</
param>
    /// <returns>The new parameter group object.</returns>
    public async Task<DBClusterParameterGroup>
 CreateCustomClusterParameterGroupAsync(
        string parameterGroupFamily,
        string groupName,
        string description)
    {
        var request = new CreateDBClusterParameterGroupRequest
        {
            DBParameterGroupFamily = parameterGroupFamily,
            DBClusterParameterGroupName = groupName,
            Description = description,
        };

        var response = await
 _amazonRDS.CreateDBClusterParameterGroupAsync(request);
        return response.DBClusterParameterGroup;
    }

    /// <summary>
```

```
    /// Describe the cluster parameters in a parameter group.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <param name="source">The optional name of the source filter.</param>
    /// <returns>The collection of parameters.</returns>
    public async Task<List<Parameter>>
 DescribeDBClusterParametersInGroupAsync(string groupName, string? source = null)
    {
        var paramList = new List<Parameter>();

        DescribeDBClusterParametersResponse response;
        var request = new DescribeDBClusterParametersRequest
        {
            DBClusterParameterGroupName = groupName,
            Source = source,
        };

        // Get the full list if there are multiple pages.
        do
        {
            response = await
 _amazonRDS.DescribeDBClusterParametersAsync(request);
            paramList.AddRange(response.Parameters);

            request.Marker = response.Marker;
        }
        while (response.Marker is not null);

        return paramList;
    }

    /// <summary>
    /// Get the description of a DB cluster parameter group by name.
    /// </summary>
    /// <param name="name">The name of the DB parameter group to describe.</
param>
    /// <returns>The parameter group description.</returns>
    public async Task<DBClusterParameterGroup?>
 DescribeCustomDBClusterParameterGroupAsync(string name)
    {
        var response = await _amazonRDS.DescribeDBClusterParameterGroupsAsync(
            new DescribeDBClusterParameterGroupsRequest()
            {
                DBClusterParameterGroupName = name
```

```
            });
        return response.DBClusterParameterGroups.FirstOrDefault();
    }

    /// <summary>
    /// Modify the specified integer parameters with new values from user input.
    /// </summary>
    /// <param name="groupName">The group name for the parameters.</param>
    /// <param name="parameters">The list of integer parameters to modify.</
param>
    /// <param name="newValue">Optional int value to set for parameters.</param>
    /// <returns>The name of the group that was modified.</returns>
    public async Task<string> ModifyIntegerParametersInGroupAsync(string
 groupName, List<Parameter> parameters, int newValue = 0)
    {
        foreach (var p in parameters)
        {
            if (p.IsModifiable && p.DataType == "integer")
            {
                while (newValue == 0)
                {
                    Console.WriteLine(
                        $"Enter a new value for {p.ParameterName} from the
 allowed values {p.AllowedValues} ");

                    var choice = Console.ReadLine();
                    int.TryParse(choice, out newValue);
                }

                p.ParameterValue = newValue.ToString();
            }
        }

        var request = new ModifyDBClusterParameterGroupRequest
        {
            Parameters = parameters,
            DBClusterParameterGroupName = groupName,
        };

        var result = await
 _amazonRDS.ModifyDBClusterParameterGroupAsync(request);
        return result.DBClusterParameterGroupName;
    }
```

```
    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
    public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptionsPagedAsync(string engine, string
engineVersion)
    {
        // Use a paginator to get a list of DB instance options.
        var results = new List<OrderableDBInstanceOption>();
        var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
            new DescribeOrderableDBInstanceOptionsRequest()
            {
                Engine = engine,
                EngineVersion = engineVersion,
            });
        // Get the entire list using the paginator.
        await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
        {
            results.Add(instanceOptions);
        }
        return results;
    }

    /// <summary>
    /// Delete a particular parameter group by name.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteClusterParameterGroupByNameAsync(string
groupName)
    {
        var request = new DeleteDBClusterParameterGroupRequest
        {
            DBClusterParameterGroupName = groupName,
        };
```

```
        var response = await
_amazonRDS.DeleteDBClusterParameterGroupAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Create a new cluster and database.
    /// </summary>
    /// <param name="dbName">The name of the new database.</param>
    /// <param name="clusterIdentifier">The identifier of the cluster.</param>
    /// <param name="parameterGroupName">The name of the parameter group.</param>
    /// <param name="dbEngine">The engine to use for the new cluster.</param>
    /// <param name="dbEngineVersion">The version of the engine to use.</param>
    /// <param name="adminName">The admin username.</param>
    /// <param name="adminPassword">The primary admin password.</param>
    /// <returns>The cluster object.</returns>
    public async Task<DBCluster> CreateDBClusterWithAdminAsync(
        string dbName,
        string clusterIdentifier,
        string parameterGroupName,
        string dbEngine,
        string dbEngineVersion,
        string adminName,
        string adminPassword)
    {
        var request = new CreateDBClusterRequest
        {
            DatabaseName = dbName,
            DBClusterIdentifier = clusterIdentifier,
            DBClusterParameterGroupName = parameterGroupName,
            Engine = dbEngine,
            EngineVersion = dbEngineVersion,
            MasterUsername = adminName,
            MasterUserPassword = adminPassword,
        };

        var response = await _amazonRDS.CreateDBClusterAsync(request);
        return response.DBCluster;
    }

    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
```

```
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstancesPagedAsync(string?
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }

    /// <summary>
    /// Returns a list of DB clusters.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
cluster.</param>
    /// <returns>List of DB clusters.</returns>
    public async Task<List<DBCluster>> DescribeDBClustersPagedAsync(string?
dbClusterIdentifier = null)
    {
        var results = new List<DBCluster>();

        DescribeDBClustersResponse response;
        DescribeDBClustersRequest request = new DescribeDBClustersRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClustersAsync(request);
            results.AddRange(response.DBClusters);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
```

```
        return results;
    }

    /// <summary>
    /// Create an Amazon Relational Database Service (Amazon RDS) DB instance
    /// with a particular set of properties. Use the action
DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstanceInClusterAsync(
        string dbClusterIdentifier,
        string dbInstanceIdentifier,
        string dbEngine,
        string dbEngineVersion,
        string instanceClass)
    {
        // When creating the instance within a cluster, do not specify the name
or size.
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass
            });

        return response.DBInstance;
    }

    /// <summary>
    /// Create a snapshot of a cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
```

```
    public async Task<DBClusterSnapshot>
CreateClusterSnapshotByIdentifierAsync(string dbClusterIdentifier, string
snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBClusterSnapshotAsync(
            new CreateDBClusterSnapshotRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBClusterSnapshotIdentifier = snapshotIdentifier,
            });

        return response.DBClusterSnapshot;
    }

    /// <summary>
    /// Return a list of DB snapshots for a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBClusterSnapshot>>
DescribeDBClusterSnapshotsByIdentifierAsync(string dbClusterIdentifier)
    {
        var results = new List<DBClusterSnapshot>();

        DescribeDBClusterSnapshotsResponse response;
        DescribeDBClusterSnapshotsRequest request = new
DescribeDBClusterSnapshotsRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClusterSnapshotsAsync(request);
            results.AddRange(response.DBClusterSnapshots);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
        return results;
    }

    /// <summary>
    /// Delete a particular DB cluster.
    /// </summary>
```

```
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>DB cluster object.</returns>
    public async Task<DBCluster> DeleteDBClusterByIdentifierAsync(string
 dbClusterIdentifier)
    {
        var response = await _amazonRDS.DeleteDBClusterAsync(
            new DeleteDBClusterRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                SkipFinalSnapshot = true
            });

        return response.DBCluster;
    }

    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstanceByIdentifierAsync(string
 dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance

- DeleteDBCluster
- Banco de dados excluído ClusterParameterGroup
- DeleteDBInstance
- Descreva o DB ClusterParameterGroups
- Descreva o DB ClusterParameters
- Descreva o DB ClusterSnapshots
- DescribeDBClusters
- Descreva o DB EngineVersions
- DescribeDBInstances
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ClusterParameterGroup

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon Aurora DB cluster and demonstrates several
 operations
//! on that cluster.
/*!
 \sa gettingStartedWithDBClusters()
 \param clientConfiguration: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::gettingStartedWithDBClusters(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);
```

```
    printAsterisksLine();
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon
 Aurora)"
              << std::endl;
    std::cout << "get started with DB clusters demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB cluster parameter group named '" <<
              CLUSTER_PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB cluster parameter group already exists.
        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
 std::endl;
            dbParameterGroupFamily =
 outcome.GetResult().GetDBClusterParameterGroups()
[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' does not exist." <<
 std::endl;
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!parameterGroupFound) {
```

```
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available parameter group families for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
        }

        std::cout << "Getting available parameter group families for " <<
DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family <<
std::endl;
            }
        }

        int choice = askQuestionForIntRange("Which family do you want to use? ",
1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB cluster parameter group.
        Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example cluster parameter group.");

        Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
                client.CreateDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully
created."
                      << std::endl;
        }
        else {
```

```
            std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your cluster parameter
group."
              << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB cluster parameter group.
    if (!getDBClusterParameters(CLUSTER_PARAMETER_GROUP_NAME,
AUTO_INCREMENT_PREFIX,
                                NO_SOURCE,
                                autoIncrementParameters,
                                client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;

    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value between ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
```

```
                updateParameters.push_back(autoIncParameter);

            }
            else {
                std::cerr << "Error parsing " <<
autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the DB cluster parameter
group.
        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
                client.ModifyDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully
modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a
source of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the DB cluster parameter group.
    if (!getDBClusterParameters(CLUSTER_PARAMETER_GROUP_NAME, NO_NAME_PREFIX,
"user",
                                userParameters,
                                client)) {
```

```
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB Cluster." << std::endl;

    Aws::RDS::Model::DBCluster dbCluster;
    // 7.  Check if the DB cluster already exists.
    if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::String engineVersionName;
    Aws::String engineName;
    if (dbCluster.DBClusterIdentifierHasBeenSet()) {
        std::cout << "The DB cluster already exists." << std::endl;
        engineVersionName = dbCluster.GetEngineVersion();
        engineName = dbCluster.GetEngine();

    }
    else {
        std::cout << "Let's create a DB cluster." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters):
");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of engine versions for the parameter group family.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily,
engineVersions,
                                 client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }
```

```
        std::cout << "The available engines for your parameter group family are:"
                  << std::endl;

        int index = 1;
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion:
engineVersions) {
            std::cout << "  " << index << ": " <<
engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ",
1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion =
engineVersions[choice -
                                                                                1];

        engineName = engineVersion.GetEngine();
        engineVersionName = engineVersion.GetEngineVersion();
        std::cout << "Creating a DB cluster named '" << DB_CLUSTER_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
                  << "The DB cluster is configured to use your custom cluster
parameter group '"
                  << CLUSTER_PARAMETER_GROUP_NAME << "', and \n"
                  << "selected engine version " <<
engineVersion.GetEngineVersion()
                  << ".\nThis typically takes several minutes." << std::endl;

        Aws::RDS::Model::CreateDBClusterRequest request;
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetEngine(engineName);
        request.SetEngineVersion(engineVersionName);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBClusterOutcome outcome =
                client.CreateDBCluster(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster creation has started."
```

```
                    << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBCluster. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }
    }

    std::cout << "Waiting for the DB cluster to become available." << std::endl;

    int counter = 0;
    // 11. Wait for the DB cluster to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for cluster to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }

        dbCluster = Aws::RDS::Model::DBCluster();
        if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB cluster status is '"
                      << dbCluster.GetStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbCluster.GetStatus() != "available");

    if (dbCluster.GetStatus() == "available") {
        std::cout << "The DB cluster has been created." << std::endl;
    }
```

```
    printAsterisksLine();
    Aws::RDS::Model::DBInstance dbInstance;
    // 11.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER, "",
                         client);
        return false;
    }

    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;

        Aws::String dbInstanceClass;
        // 12.  Get a list of instance classes.
        if (!chooseDBInstanceClass(engineName,
                                   engineVersionName,
                                   dbInstanceClass,
                                   client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
 "",
                             client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' with selected DB instance class '" << dbInstanceClass
                  << "'.\nThis typically takes several minutes." << std::endl;

        // 13. Create a DB instance.
        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
```

```
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }
    }

    std::cout << "Waiting for the DB instance to become available." << std::endl;

    counter = 0;
    // 14. Wait for the DB instance to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");
```

```
   if (dbInstance.GetDBInstanceStatus() == "available") {
       std::cout << "The DB instance has been created." << std::endl;
   }

   // 15. Display the connection string that can be used to connect a 'mysql'
shell to the database.
   displayConnection(dbCluster);

   printAsterisksLine();

   if (askYesNoQuestion(
           "Do you want to create a snapshot of your DB cluster (y/n)? ")) {
       Aws::String snapshotID(DB_CLUSTER_IDENTIFIER + "-" +
                              Aws::String(Aws::Utils::UUID::RandomUUID()));
       {
           std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
           std::cout << "This typically takes a few minutes." << std::endl;

           // 16. Create a snapshot of the DB cluster. (CreateDBClusterSnapshot)
           Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
           request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
           request.SetDBClusterSnapshotIdentifier(snapshotID);

           Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                   client.CreateDBClusterSnapshot(request);

           if (outcome.IsSuccess()) {
               std::cout << "Snapshot creation has started."
                         << std::endl;
           }
           else {
               std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                         << outcome.GetError().GetMessage()
                         << std::endl;
               cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
               return false;
           }
       }
```

```
        std::cout << "Waiting for the snapshot to become available." <<
std::endl;

        Aws::RDS::Model::DBClusterSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            // 17. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");
```

```
        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB cluster, DB instance, and parameter
 group (y/n)? ")) {
        result = cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                  DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
                                  client);
    }

    return result;
}

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
```

```
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}


//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBCLusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBCLusterParameters(const Aws::String
 &parameterGroupName,
                                            const Aws::String &namePrefix,
                                            const Aws::String &source,

 Aws::Vector<Aws::RDS::Model::Parameter> &parametersResult,
                                            const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
```

```
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,
```

```
 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}


//! Routine which gets a DB instance description.
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance
 &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
```

```
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
```

```
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption>
 &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option:
 options) {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                instanceClasses.push_back(instanceClass);
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions.
 "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine
 are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
```

```
*/
bool AwsDoc::Aurora::cleanUpResources(const Aws::String &parameterGroupName,
                                      const Aws::String &dbClusterIdentifier,
                                      const Aws::String &dbInstanceIdentifier,
                                      const Aws::RDS::RDSClient &client) {
    bool result = true;
    bool instanceDeleting = false;
    bool clusterDeleting = false;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 18. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
 parameter group."
                        << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    if (!dbClusterIdentifier.empty()) {
        {
            // 19. Delete the DB cluster.
            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);
```

```
            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }
    int counter = 0;

    while (clusterDeleting || instanceDeleting) {
        // 20. Wait for the DB cluster and instance to be deleted.
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 800) {
            std::cerr << "Wait for instance to delete timed out ofter " <<
counter
                      << " seconds." << std::endl;
            return false;
        }

        Aws::RDS::Model::DBInstance dbInstance = Aws::RDS::Model::DBInstance();
        if (instanceDeleting) {
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }
            instanceDeleting = dbInstance.DBInstanceIdentifierHasBeenSet();
        }

        Aws::RDS::Model::DBCluster dbCluster = Aws::RDS::Model::DBCluster();
        if (clusterDeleting) {
```

```
            if (!describeDBCluster(dbClusterIdentifier, dbCluster, client)) {
                return false;
            }

            clusterDeleting = dbCluster.DBClusterIdentifierHasBeenSet();
        }

        if ((counter % 20) == 0) {
            if (instanceDeleting) {
                std::cout << "Current DB instance status is '"
                          << dbInstance.GetDBInstanceStatus() << "." <<
std::endl;
            }

            if (clusterDeleting) {
                std::cout << "Current DB cluster status is '"
                          << dbCluster.GetStatus() << "." << std::endl;
            }
        }
    }

    if (!parameterGroupName.empty()) {
        // 21. Delete the DB cluster parameter group.
        Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
                client.DeleteDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// GetStartedClusters is an interactive example that shows you how to use the AWS
 SDK for Go
```

```
// with Amazon Aurora to do the following:
//
// 1. Create a custom DB cluster parameter group and set parameter values.
// 2. Create an Aurora DB cluster that is configured to use the parameter group.
// 3. Create a DB instance in the DB cluster that contains a database.
// 4. Take a snapshot of the DB cluster.
// 5. Delete the DB instance, DB cluster, and parameter group.
type GetStartedClusters struct {
 sdkConfig  aws.Config
 dbClusters actions.DbClusters
 questioner demotools.IQuestioner
 helper     IScenarioHelper
 isTestRun  bool
}

// NewGetStartedClusters constructs a GetStartedClusters instance from a
 configuration.
// It uses the specified config to get an Amazon Relational Database Service
 (Amazon RDS)
// client and create wrappers for the actions used in the scenario.
func NewGetStartedClusters(sdkConfig aws.Config, questioner
 demotools.IQuestioner,
 helper IScenarioHelper) GetStartedClusters {
 auroraClient := rds.NewFromConfig(sdkConfig)
 return GetStartedClusters{
  sdkConfig:  sdkConfig,
  dbClusters: actions.DbClusters{AuroraClient: auroraClient},
  questioner: questioner,
  helper:     helper,
 }
}

// Run runs the interactive scenario.
func (scenario GetStartedClusters) Run(dbEngine string, parameterGroupName
 string,
 clusterName string, dbName string) {
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon Aurora DB Cluster demo.")
```

```
 log.Println(strings.Repeat("-", 88))

 parameterGroup := scenario.CreateParameterGroup(dbEngine, parameterGroupName)
 scenario.SetUserParameters(parameterGroupName)
 cluster := scenario.CreateCluster(clusterName, dbEngine, dbName, parameterGroup)
 scenario.helper.Pause(5)
 dbInstance := scenario.CreateInstance(cluster)
 scenario.DisplayConnection(cluster)
 scenario.CreateSnapshot(clusterName)
 scenario.Cleanup(dbInstance, cluster, parameterGroup)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateParameterGroup shows how to get available engine versions for a
 specified
// database engine and create a DB cluster parameter group that is compatible
 with a
// selected engine family.
func (scenario GetStartedClusters) CreateParameterGroup(dbEngine string,
 parameterGroupName string) *types.DBClusterParameterGroup {

 log.Printf("Checking for an existing DB cluster parameter group named %v.\n",
  parameterGroupName)
 parameterGroup, err := scenario.dbClusters.GetParameterGroup(parameterGroupName)
 if err != nil {
  panic(err)
 }
 if parameterGroup == nil {
  log.Printf("Getting available database engine versions for %v.\n", dbEngine)
  engineVersions, err := scenario.dbClusters.GetEngineVersions(dbEngine, "")
  if err != nil {
   panic(err)
  }

  familySet := map[string]struct{}{}
  for _, family := range engineVersions {
   familySet[*family.DBParameterGroupFamily] = struct{}{}
  }
  var families []string
  for family := range familySet {
   families = append(families, family)
```

```
  }
  sort.Strings(families)
  familyIndex := scenario.questioner.AskChoice("Which family do you want to use?
\n", families)
  log.Println("Creating a DB cluster parameter group.")
  _, err = scenario.dbClusters.CreateParameterGroup(
   parameterGroupName, families[familyIndex], "Example parameter group.")
  if err != nil {
   panic(err)
  }
  parameterGroup, err = scenario.dbClusters.GetParameterGroup(parameterGroupName)
  if err != nil {
   panic(err)
  }
 }
 log.Printf("Parameter group %v:\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tName: %v\n", *parameterGroup.DBClusterParameterGroupName)
 log.Printf("\tARN: %v\n", *parameterGroup.DBClusterParameterGroupArn)
 log.Printf("\tFamily: %v\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tDescription: %v\n", *parameterGroup.Description)
 log.Println(strings.Repeat("-", 88))
 return parameterGroup

}

// SetUserParameters shows how to get the parameters contained in a custom
 parameter
// group and update some of the parameter values in the group.
func (scenario GetStartedClusters) SetUserParameters(parameterGroupName string) {
 log.Println("Let's set some parameter values in your parameter group.")
 dbParameters, err := scenario.dbClusters.GetParameters(parameterGroupName, "")
 if err != nil {
  panic(err)
 }
 var updateParams []types.Parameter
 for _, dbParam := range dbParameters {
  if strings.HasPrefix(*dbParam.ParameterName, "auto_increment") &&
   dbParam.IsModifiable && *dbParam.DataType == "integer" {
   log.Printf("The %v parameter is described as:\n\t%v",
    *dbParam.ParameterName, *dbParam.Description)
   rangeSplit := strings.Split(*dbParam.AllowedValues, "-")
   lower, _ := strconv.Atoi(rangeSplit[0])
   upper, _ := strconv.Atoi(rangeSplit[1])
   newValue := scenario.questioner.AskInt(
```

```
    fmt.Sprintf("Enter a value between %v and %v:", lower, upper),
    demotools.InIntRange{Lower: lower, Upper: upper})
   dbParam.ParameterValue = aws.String(strconv.Itoa(newValue))
   updateParams = append(updateParams, dbParam)
  }
 }
 err = scenario.dbClusters.UpdateParameters(parameterGroupName, updateParams)
 if err != nil {
  panic(err)
 }
 log.Println("You can get a list of parameters you've set by specifying a source
 of 'user'.")
 userParameters, err := scenario.dbClusters.GetParameters(parameterGroupName,
 "user")
 if err != nil {
  panic(err)
 }
 log.Println("Here are the parameters you've set:")
 for _, param := range userParameters {
  log.Printf("\t%v: %v\n", *param.ParameterName, *param.ParameterValue)
 }
 log.Println(strings.Repeat("-", 88))
}

// CreateCluster shows how to create an Aurora DB cluster that contains a
 database
// of a specified type. The database is also configured to use a custom DB
 cluster
// parameter group.
func (scenario GetStartedClusters) CreateCluster(clusterName string, dbEngine
 string,
 dbName string, parameterGroup *types.DBClusterParameterGroup) *types.DBCluster {

 log.Println("Checking for an existing DB cluster.")
 cluster, err := scenario.dbClusters.GetDbCluster(clusterName)
 if err != nil {
  panic(err)
 }
 if cluster == nil {
  adminUsername := scenario.questioner.Ask(
   "Enter an administrator user name for the database: ", demotools.NotEmpty{})
  adminPassword := scenario.questioner.Ask(
   "Enter a password for the administrator (at least 8 characters): ",
 demotools.NotEmpty{})
```

```
  engineVersions, err := scenario.dbClusters.GetEngineVersions(dbEngine,
 *parameterGroup.DBParameterGroupFamily)
  if err != nil {
   panic(err)
  }
  var engineChoices []string
  for _, engine := range engineVersions {
   engineChoices = append(engineChoices, *engine.EngineVersion)
  }
  log.Println("The available engines for your parameter group are:")
  engineIndex := scenario.questioner.AskChoice("Which engine do you want to use?
\n", engineChoices)
  log.Printf("Creating DB cluster %v and database %v.\n", clusterName, dbName)
  log.Printf("The DB cluster is configured to use\nyour custom parameter group %v
\n",
   *parameterGroup.DBClusterParameterGroupName)
  log.Printf("and selected engine %v.\n", engineChoices[engineIndex])
  log.Println("This typically takes several minutes.")
  cluster, err = scenario.dbClusters.CreateDbCluster(
   clusterName, *parameterGroup.DBClusterParameterGroupName, dbName, dbEngine,
   engineChoices[engineIndex], adminUsername, adminPassword)
  if err != nil {
   panic(err)
  }
  for *cluster.Status != "available" {
   scenario.helper.Pause(30)
   cluster, err = scenario.dbClusters.GetDbCluster(clusterName)
   if err != nil {
    panic(err)
   }
   log.Println("Cluster created and available.")
  }
 }
 log.Println("Cluster data:")
 log.Printf("\tDBClusterIdentifier: %v\n", *cluster.DBClusterIdentifier)
 log.Printf("\tARN: %v\n", *cluster.DBClusterArn)
 log.Printf("\tStatus: %v\n", *cluster.Status)
 log.Printf("\tEngine: %v\n", *cluster.Engine)
 log.Printf("\tEngine version: %v\n", *cluster.EngineVersion)
 log.Printf("\tDBClusterParameterGroup: %v\n", *cluster.DBClusterParameterGroup)
 log.Printf("\tEngineMode: %v\n", *cluster.EngineMode)
 log.Println(strings.Repeat("-", 88))
 return cluster
}
```

```
// CreateInstance shows how to create a DB instance in an existing Aurora DB
 cluster.
// A new DB cluster contains no DB instances, so you must add one. The first DB
 instance
// that is added to a DB cluster defaults to a read-write DB instance.
func (scenario GetStartedClusters) CreateInstance(cluster *types.DBCluster)
 *types.DBInstance {
 log.Println("Checking for an existing database instance.")
 dbInstance, err := scenario.dbClusters.GetInstance(*cluster.DBClusterIdentifier)
 if err != nil {
  panic(err)
 }
 if dbInstance == nil {
  log.Println("Let's create a database instance in your DB cluster.")
  log.Println("First, choose a DB instance type:")
  instOpts, err := scenario.dbClusters.GetOrderableInstances(
   *cluster.Engine, *cluster.EngineVersion)
  if err != nil {
   panic(err)
  }
  var instChoices []string
  for _, opt := range instOpts {
   instChoices = append(instChoices, *opt.DBInstanceClass)
  }
  instIndex := scenario.questioner.AskChoice(
   "Which DB instance class do you want to use?\n", instChoices)
  log.Println("Creating a database instance. This typically takes several
 minutes.")
  dbInstance, err = scenario.dbClusters.CreateInstanceInCluster(
   *cluster.DBClusterIdentifier, *cluster.DBClusterIdentifier, *cluster.Engine,
   instChoices[instIndex])
  if err != nil {
   panic(err)
  }
  for *dbInstance.DBInstanceStatus != "available" {
   scenario.helper.Pause(30)
   dbInstance, err =
 scenario.dbClusters.GetInstance(*cluster.DBClusterIdentifier)
   if err != nil {
    panic(err)
   }
  }
 }
```

```
 log.Println("Instance data:")
 log.Printf("\tDBInstanceIdentifier: %v\n", *dbInstance.DBInstanceIdentifier)
 log.Printf("\tARN: %v\n", *dbInstance.DBInstanceArn)
 log.Printf("\tStatus: %v\n", *dbInstance.DBInstanceStatus)
 log.Printf("\tEngine: %v\n", *dbInstance.Engine)
 log.Printf("\tEngine version: %v\n", *dbInstance.EngineVersion)
 log.Println(strings.Repeat("-", 88))
 return dbInstance
}

// DisplayConnection displays connection information about an Aurora DB cluster
 and tips
// on how to connect to it.
func (scenario GetStartedClusters) DisplayConnection(cluster *types.DBCluster) {
 log.Println(
  "You can now connect to your database using your favorite MySql client.\n" +
   "One way to connect is by using the 'mysql' shell on an Amazon EC2 instance\n"
 +
   "that is running in the same VPC as your database cluster. Pass the endpoint,
\n" +
   "port, and administrator user name to 'mysql' and enter your password\n" +
   "when prompted:")
 log.Printf("\n\tmysql -h %v -P %v -u %v -p\n",
  *cluster.Endpoint, *cluster.Port, *cluster.MasterUsername)
 log.Println("For more information, see the User Guide for Aurora:\n" +
  "\thttps://docs.aws.amazon.com/AmazonRDS/latest/AuroraUserGuide/
CHAP_GettingStartedAurora.CreatingConnecting.Aurora.html#CHAP_GettingStartedAurora.Aurora
 log.Println(strings.Repeat("-", 88))
}

// CreateSnapshot shows how to create a DB cluster snapshot and wait until it's
 available.
func (scenario GetStartedClusters) CreateSnapshot(clusterName string) {
 if scenario.questioner.AskBool(
  "Do you want to create a snapshot of your DB cluster (y/n)? ", "y") {
  snapshotId := fmt.Sprintf("%v-%v", clusterName, scenario.helper.UniqueId())
  log.Printf("Creating a snapshot named %v. This typically takes a few minutes.
\n", snapshotId)
  snapshot, err := scenario.dbClusters.CreateClusterSnapshot(clusterName,
 snapshotId)
  if err != nil {
   panic(err)
  }
  for *snapshot.Status != "available" {
```

```
    scenario.helper.Pause(30)
    snapshot, err = scenario.dbClusters.GetClusterSnapshot(snapshotId)
    if err != nil {
     panic(err)
    }
   }
   log.Println("Snapshot data:")
   log.Printf("\tDBClusterSnapshotIdentifier: %v\n",
  *snapshot.DBClusterSnapshotIdentifier)
   log.Printf("\tARN: %v\n", *snapshot.DBClusterSnapshotArn)
   log.Printf("\tStatus: %v\n", *snapshot.Status)
   log.Printf("\tEngine: %v\n", *snapshot.Engine)
   log.Printf("\tEngine version: %v\n", *snapshot.EngineVersion)
   log.Printf("\tDBClusterIdentifier: %v\n", *snapshot.DBClusterIdentifier)
   log.Printf("\tSnapshotCreateTime: %v\n", *snapshot.SnapshotCreateTime)
   log.Println(strings.Repeat("-", 88))
  }
 }

 // Cleanup shows how to clean up a DB instance, DB cluster, and DB cluster
  parameter group.
 // Before the DB cluster parameter group can be deleted, all associated DB
  instances and
 // DB clusters must first be deleted.
 func (scenario GetStartedClusters) Cleanup(dbInstance *types.DBInstance, cluster
  *types.DBCluster,
  parameterGroup *types.DBClusterParameterGroup) {

  if scenario.questioner.AskBool(
   "\nDo you want to delete the database instance, DB cluster, and parameter group
  (y/n)? ", "y") {
   log.Printf("Deleting database instance %v.\n",
  *dbInstance.DBInstanceIdentifier)
   err := scenario.dbClusters.DeleteInstance(*dbInstance.DBInstanceIdentifier)
   if err != nil {
    panic(err)
   }
   log.Printf("Deleting database cluster %v.\n", *cluster.DBClusterIdentifier)
   err = scenario.dbClusters.DeleteDbCluster(*cluster.DBClusterIdentifier)
   if err != nil {
    panic(err)
   }
   log.Println(
```

```
    "Waiting for the DB instance and DB cluster to delete. This typically takes
 several minutes.")
  for dbInstance != nil || cluster != nil {
   scenario.helper.Pause(30)
   if dbInstance != nil {
    dbInstance, err =
 scenario.dbClusters.GetInstance(*dbInstance.DBInstanceIdentifier)
    if err != nil {
     panic(err)
    }
   }
   if cluster != nil {
    cluster, err = scenario.dbClusters.GetDbCluster(*cluster.DBClusterIdentifier)
    if err != nil {
     panic(err)
    }
   }
  }
  log.Printf("Deleting parameter group %v.",
 *parameterGroup.DBClusterParameterGroupName)
  err =
 scenario.dbClusters.DeleteParameterGroup(*parameterGroup.DBClusterParameterGroupName)
  if err != nil {
   panic(err)
  }
 }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Aurora.

```
type DbClusters struct {
 AuroraClient *rds.Client
}


// GetParameterGroup gets a DB cluster parameter group by name.
func (clusters *DbClusters) GetParameterGroup(parameterGroupName string) (
 *types.DBClusterParameterGroup, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterParameterGroups(
  context.TODO(), &rds.DescribeDBClusterParameterGroupsInput{
```

```
    DBClusterParameterGroupName: aws.String(parameterGroupName),
   })
  if err != nil {
   var notFoundError *types.DBParameterGroupNotFoundFault
   if errors.As(err, &notFoundError) {
    log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
    err = nil
   } else {
    log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
   }
   return nil, err
  } else {
   return &output.DBClusterParameterGroups[0], err
  }
 }


 // CreateParameterGroup creates a DB cluster parameter group that is based on the
  specified
 // parameter group family.
 func (clusters *DbClusters) CreateParameterGroup(
  parameterGroupName string, parameterGroupFamily string, description string) (
  *types.DBClusterParameterGroup, error) {

  output, err :=
  clusters.AuroraClient.CreateDBClusterParameterGroup(context.TODO(),
   &rds.CreateDBClusterParameterGroupInput{
    DBClusterParameterGroupName: aws.String(parameterGroupName),
    DBParameterGroupFamily:      aws.String(parameterGroupFamily),
    Description:                 aws.String(description),
   })
  if err != nil {
   log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
   return nil, err
  } else {
   return output.DBClusterParameterGroup, err
  }
 }



 // DeleteParameterGroup deletes the named DB cluster parameter group.
 func (clusters *DbClusters) DeleteParameterGroup(parameterGroupName string) error
  {
```

```
 _, err := clusters.AuroraClient.DeleteDBClusterParameterGroup(context.TODO(),
  &rds.DeleteDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// GetParameters gets the parameters that are contained in a DB cluster parameter
 group.
func (clusters *DbClusters) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBClusterParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator :=
 rds.NewDescribeDBClusterParametersPaginator(clusters.AuroraClient,
  &rds.DescribeDBClusterParametersInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Source:                      aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get paramaeters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}



// UpdateParameters updates parameters in a named DB cluster parameter group.
```

```
func (clusters *DbClusters) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := clusters.AuroraClient.ModifyDBClusterParameterGroup(context.TODO(),
  &rds.ModifyDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Parameters:                  params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// GetDbCluster gets data about an Aurora DB cluster.
func (clusters *DbClusters) GetDbCluster(clusterName string) (*types.DBCluster,
 error) {
 output, err := clusters.AuroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{
   DBClusterIdentifier: aws.String(clusterName),
  })
 if err != nil {
  var notFoundError *types.DBClusterNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB cluster %v does not exist.\n", clusterName)
   err = nil
  } else {
   log.Printf("Couldn't get DB cluster %v: %v\n", clusterName, err)
  }
  return nil, err
 } else {
  return &output.DBClusters[0], err
 }
}



// CreateDbCluster creates a DB cluster that is configured to use the specified
 parameter group.
// The newly created DB cluster contains a database that uses the specified
 engine and
```

```
// engine version.
func (clusters *DbClusters) CreateDbCluster(clusterName string,
 parameterGroupName string,
 dbName string, dbEngine string, dbEngineVersion string, adminName string,
 adminPassword string) (
 *types.DBCluster, error) {

 output, err := clusters.AuroraClient.CreateDBCluster(context.TODO(),
 &rds.CreateDBClusterInput{
  DBClusterIdentifier:         aws.String(clusterName),
  Engine:                      aws.String(dbEngine),
  DBClusterParameterGroupName: aws.String(parameterGroupName),
  DatabaseName:                aws.String(dbName),
  EngineVersion:               aws.String(dbEngineVersion),
  MasterUserPassword:          aws.String(adminPassword),
  MasterUsername:              aws.String(adminName),
 })
 if err != nil {
  log.Printf("Couldn't create DB cluster %v: %v\n", clusterName, err)
  return nil, err
 } else {
  return output.DBCluster, err
 }
}



// DeleteDbCluster deletes a DB cluster without keeping a final snapshot.
func (clusters *DbClusters) DeleteDbCluster(clusterName string) error {
 _, err := clusters.AuroraClient.DeleteDBCluster(context.TODO(),
 &rds.DeleteDBClusterInput{
  DBClusterIdentifier: aws.String(clusterName),
  SkipFinalSnapshot:   true,
 })
 if err != nil {
  log.Printf("Couldn't delete DB cluster %v: %v\n", clusterName, err)
  return err
 } else {
  return nil
 }
}
```

```
// CreateClusterSnapshot creates a snapshot of a DB cluster.
func (clusters *DbClusters) CreateClusterSnapshot(clusterName string,
 snapshotName string) (
 *types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.CreateDBClusterSnapshot(context.TODO(),
 &rds.CreateDBClusterSnapshotInput{
  DBClusterIdentifier:         aws.String(clusterName),
  DBClusterSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBClusterSnapshot, nil
 }
}



// GetClusterSnapshot gets a DB cluster snapshot.
func (clusters *DbClusters) GetClusterSnapshot(snapshotName string)
 (*types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterSnapshots(context.TODO(),
  &rds.DescribeDBClusterSnapshotsInput{
   DBClusterSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBClusterSnapshots[0], nil
 }
}



// CreateInstanceInCluster creates a database instance in an existing DB cluster.
 The first database that is
// created defaults to a read-write DB instance.
func (clusters *DbClusters) CreateInstanceInCluster(clusterName string,
 instanceName string,
 dbEngine string, dbInstanceClass string) (*types.DBInstance, error) {
 output, err := clusters.AuroraClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
```

```
  DBInstanceIdentifier: aws.String(instanceName),
  DBClusterIdentifier:  aws.String(clusterName),
  Engine:               aws.String(dbEngine),
  DBInstanceClass:      aws.String(dbInstanceClass),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}



// GetInstance gets data about a DB instance.
func (clusters *DbClusters) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := clusters.AuroraClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}



// DeleteInstance deletes a DB instance.
func (clusters *DbClusters) DeleteInstance(instanceName string) error {
 _, err := clusters.AuroraClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
```

```
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (clusters *DbClusters) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := clusters.AuroraClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (clusters *DbClusters) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instances []types.OrderableDBInstanceOption
 var err error
```

```
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(clusters.AuroraClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instances: %v\n", err)
   break
  } else {
   instances = append(instances, output.OrderableDBInstanceOptions...)
  }
 }
 return instances, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For details, see:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 * This Java example performs the following tasks:
 *
 * 1. Gets available engine families for Amazon Aurora MySQL-Compatible Edition
 * by calling the DescribeDbEngineVersions(Engine='aurora-mysql') method.
 * 2. Selects an engine family and creates a custom DB cluster parameter group
 * by invoking the describeDBClusterParameters method.
 * 3. Gets the parameter groups by invoking the describeDBClusterParameterGroups
 * method.
 * 4. Gets parameters in the group by invoking the describeDBClusterParameters
 * method.
 * 5. Modifies the auto_increment_offset parameter by invoking the
 * modifyDbClusterParameterGroupRequest method.
 * 6. Gets and displays the updated parameters.
 * 7. Gets a list of allowed engine versions by invoking the
 * describeDbEngineVersions method.
 * 8. Creates an Aurora DB cluster database cluster that contains a MySQL
```

```
 * database.
 * 9. Waits for DB instance to be ready.
 * 10. Gets a list of instance classes available for the selected engine.
 * 11. Creates a database instance in the cluster.
 * 12. Waits for DB instance to be ready.
 * 13. Creates a snapshot.
 * 14. Waits for DB snapshot to be ready.
 * 15. Deletes the DB cluster.
 * 16. Deletes the DB cluster group.
 */
public class AuroraScenario {
    public static long sleepTime = 20;
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = "\n" +
                "Usage:\n" +
                "    <dbClusterGroupName> <dbParameterGroupFamily>
 <dbInstanceClusterIdentifier> <dbInstanceIdentifier> <dbName>
 <dbSnapshotIdentifier><secretName>"
                +
                "Where:\n" +
                "    dbClusterGroupName - The name of the DB cluster parameter
 group. \n" +
                "    dbParameterGroupFamily - The DB cluster parameter group
 family name (for example, aurora-mysql5.7). \n"
                +
                "    dbInstanceClusterIdentifier - The instance cluster
 identifier value.\n" +
                "    dbInstanceIdentifier - The database instance identifier.\n"
 +
                "    dbName - The database name.\n" +
                "    dbSnapshotIdentifier - The snapshot identifier.\n" +
                "    secretName - The name of the AWS Secrets Manager secret that
 contains the database credentials\"\n";
        ;

        if (args.length != 7) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbClusterGroupName = args[0];
```

```
        String dbParameterGroupFamily = args[1];
        String dbInstanceClusterIdentifier = args[2];
        String dbInstanceIdentifier = args[3];
        String dbName = args[4];
        String dbSnapshotIdentifier = args[5];
        String secretName = args[6];

        // Retrieve the database credentials using AWS Secrets Manager.
        Gson gson = new Gson();
        User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
User.class);
        String username = user.getUsername();
        String userPassword = user.getPassword();

        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Aurora example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Return a list of the available DB engines");
        describeDBEngines(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a custom parameter group");
        createDBClusterParameterGroup(rdsClient, dbClusterGroupName,
dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get the parameter group");
        describeDbClusterParameterGroups(rdsClient, dbClusterGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get the parameters in the group");
        describeDbClusterParameters(rdsClient, dbClusterGroupName, 0);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("5. Modify the auto_increment_offset parameter");
        modifyDBClusterParas(rdsClient, dbClusterGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Display the updated parameter value");
        describeDbClusterParameters(rdsClient, dbClusterGroupName, -1);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of allowed engine versions");
        getAllowedEngines(rdsClient, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Create an Aurora DB cluster database");
        String arnClusterVal = createDBCluster(rdsClient, dbClusterGroupName,
dbName, dbInstanceClusterIdentifier,
                username, userPassword);
        System.out.println("The ARN of the cluster is " + arnClusterVal);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Wait for DB instance to be ready");
        waitForInstanceReady(rdsClient, dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a list of instance classes available for the
selected engine");
        String instanceClass = getListInstanceClasses(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Create a database instance in the cluster.");
        String clusterDBARN = createDBInstanceCluster(rdsClient,
dbInstanceIdentifier, dbInstanceClusterIdentifier,
                instanceClass);
        System.out.println("The ARN of the database is " + clusterDBARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Wait for DB instance to be ready");
```

```
        waitDBInstanceReady(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Create a snapshot");
        createDBClusterSnapshot(rdsClient, dbInstanceClusterIdentifier,
dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Wait for DB snapshot to be ready");
        waitForSnapshotReady(rdsClient, dbSnapshotIdentifier,
dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Delete the DB instance");
        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Delete the DB cluster");
        deleteCluster(rdsClient, dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete the DB cluster group");
        deleteDBClusterGroup(rdsClient, dbClusterGroupName, clusterDBARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);
        rdsClient.close();
    }

    private static SecretsManagerClient getSecretClient() {
        Region region = Region.US_WEST_2;
        return SecretsManagerClient.builder()
                .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
                .build();
    }
```

```
   private static String getSecretValues(String secretName) {
       SecretsManagerClient secretClient = getSecretClient();
       GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
               .secretId(secretName)
               .build();

       GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
       return valueResponse.secretString();
   }

   public static void deleteDBClusterGroup(RdsClient rdsClient, String
dbClusterGroupName, String clusterDBARN)
           throws InterruptedException {
       try {
           boolean isDataDel = false;
           boolean didFind;
           String instanceARN;

           // Make sure that the database has been deleted.
           while (!isDataDel) {
               DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
               List<DBInstance> instanceList = response.dbInstances();
               int listSize = instanceList.size();
               didFind = false;
               int index = 1;
               for (DBInstance instance : instanceList) {
                   instanceARN = instance.dbInstanceArn();
                   if (instanceARN.compareTo(clusterDBARN) == 0) {
                       System.out.println(clusterDBARN + " still exists");
                       didFind = true;
                   }
                   if ((index == listSize) && (!didFind)) {
                       // Went through the entire list and did not find the
database ARN.
                       isDataDel = true;
                   }
                   Thread.sleep(sleepTime * 1000);
                   index++;
               }
           }
```

```
            DeleteDbClusterParameterGroupRequest clusterParameterGroupRequest =
DeleteDbClusterParameterGroupRequest
                    .builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .build();


rdsClient.deleteDBClusterParameterGroup(clusterParameterGroupRequest);
            System.out.println(dbClusterGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void deleteCluster(RdsClient rdsClient, String
dbInstanceClusterIdentifier) {
        try {
            DeleteDbClusterRequest deleteDbClusterRequest =
DeleteDbClusterRequest.builder()
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .skipFinalSnapshot(true)
                    .build();

            rdsClient.deleteDBCluster(deleteDbClusterRequest);
            System.out.println(dbInstanceClusterIdentifier + " was deleted!");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
        try {
            DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .deleteAutomatedBackups(true)
                    .skipFinalSnapshot(true)
                    .build();
```

```
            DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
            System.out.println("The status of the database is " +
response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void waitForSnapshotReady(RdsClient rdsClient, String
dbSnapshotIdentifier,
            String dbInstanceClusterIdentifier) {
        try {
            boolean snapshotReady = false;
            String snapshotReadyStr;
            System.out.println("Waiting for the snapshot to become available.");

            DescribeDbClusterSnapshotsRequest snapshotsRequest =
DescribeDbClusterSnapshotsRequest.builder()
                    .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .build();

            while (!snapshotReady) {
                DescribeDbClusterSnapshotsResponse response =
rdsClient.describeDBClusterSnapshots(snapshotsRequest);
                List<DBClusterSnapshot> snapshotList =
response.dbClusterSnapshots();
                for (DBClusterSnapshot snapshot : snapshotList) {
                    snapshotReadyStr = snapshot.status();
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true;
                    } else {
                        System.out.println(".");
                        Thread.sleep(sleepTime * 5000);
                    }
                }
            }

            System.out.println("The Snapshot is available!");

        } catch (RdsException | InterruptedException e) {
```

```
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void createDBClusterSnapshot(RdsClient rdsClient, String
dbInstanceClusterIdentifier,
            String dbSnapshotIdentifier) {
        try {
            CreateDbClusterSnapshotRequest snapshotRequest =
CreateDbClusterSnapshotRequest.builder()
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                    .build();

            CreateDbClusterSnapshotResponse response =
rdsClient.createDBClusterSnapshot(snapshotRequest);
            System.out.println("The Snapshot ARN is " +
response.dbClusterSnapshot().dbClusterSnapshotArn());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void waitDBInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            String endpoint = "";
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
```

```
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint().address();
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database instance is available! The connection
endpoint is " + endpoint);

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String createDBInstanceCluster(RdsClient rdsClient,
            String dbInstanceIdentifier,
            String dbInstanceClusterIdentifier,
            String instanceClass) {
        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .engine("aurora-mysql")
                    .dbInstanceClass(instanceClass)
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
            return response.dbInstance().dbInstanceArn();

        } catch (RdsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

```
   public static String getListInstanceClasses(RdsClient rdsClient) {
       try {
           DescribeOrderableDbInstanceOptionsRequest optionsRequest =
DescribeOrderableDbInstanceOptionsRequest
                   .builder()
                   .engine("aurora-mysql")
                   .maxRecords(20)
                   .build();

           DescribeOrderableDbInstanceOptionsResponse response = rdsClient
                   .describeOrderableDBInstanceOptions(optionsRequest);
           List<OrderableDBInstanceOption> instanceOptions =
response.orderableDBInstanceOptions();
           String instanceClass = "";
           for (OrderableDBInstanceOption instanceOption : instanceOptions) {
               instanceClass = instanceOption.dbInstanceClass();
               System.out.println("The instance class is " +
instanceOption.dbInstanceClass());
               System.out.println("The engine version is " +
instanceOption.engineVersion());
           }
           return instanceClass;

       } catch (RdsException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
       return "";
   }

   // Waits until the database instance is available.
   public static void waitForInstanceReady(RdsClient rdsClient, String
dbClusterIdentifier) {
       boolean instanceReady = false;
       String instanceReadyStr;
       System.out.println("Waiting for instance to become available.");
       try {
           DescribeDbClustersRequest instanceRequest =
DescribeDbClustersRequest.builder()
                   .dbClusterIdentifier(dbClusterIdentifier)
                   .build();

           while (!instanceReady) {
```

```
                DescribeDbClustersResponse response =
rdsClient.describeDBClusters(instanceRequest);
                List<DBCluster> clusterList = response.dbClusters();
                for (DBCluster cluster : clusterList) {
                    instanceReadyStr = cluster.status();
                    if (instanceReadyStr.contains("available")) {
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database cluster is available!");

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String createDBCluster(RdsClient rdsClient, String
dbParameterGroupFamily, String dbName,
            String dbClusterIdentifier, String userName, String password) {
        try {
            CreateDbClusterRequest clusterRequest =
CreateDbClusterRequest.builder()
                    .databaseName(dbName)
                    .dbClusterIdentifier(dbClusterIdentifier)
                    .dbClusterParameterGroupName(dbParameterGroupFamily)
                    .engine("aurora-mysql")
                    .masterUsername(userName)
                    .masterUserPassword(password)
                    .build();

            CreateDbClusterResponse response =
rdsClient.createDBCluster(clusterRequest);
            return response.dbCluster().dbClusterArn();

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
```

```
    }

    // Get a list of allowed engine versions.
    public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
        try {
            DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .engine("aurora-mysql")
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
            List<DBEngineVersion> dbEngines = response.dbEngineVersions();
            for (DBEngineVersion dbEngine : dbEngines) {
                System.out.println("The engine version is " +
dbEngine.engineVersion());
                System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Modify the auto_increment_offset parameter.
    public static void modifyDBClusterParas(RdsClient rdsClient, String
dClusterGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
            paraList.add(parameter1);
            ModifyDbClusterParameterGroupRequest groupRequest =
ModifyDbClusterParameterGroupRequest.builder()
                    .dbClusterParameterGroupName(dClusterGroupName)
                    .parameters(paraList)
```

```
                    .build();

            ModifyDbClusterParameterGroupResponse response =
rdsClient.modifyDBClusterParameterGroup(groupRequest);
            System.out.println(
                    "The parameter group " +
response.dbClusterParameterGroupName() + " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
        try {
            DescribeDbClusterParametersRequest dbParameterGroupsRequest;
            if (flag == 0) {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset
or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") ==
0)) {
                    System.out.println("*** The parameter name is  " + paraName);
```

```
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDbClusterParameterGroups(RdsClient rdsClient,
String dbClusterGroupName) {
        try {
            DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .maxRecords(20)
                    .build();

            List<DBClusterParameterGroup> groups =
rdsClient.describeDBClusterParameterGroups(groupsRequest)
                    .dbClusterParameterGroups();
            for (DBClusterParameterGroup group : groups) {
                System.out.println("The group name is " +
group.dbClusterParameterGroupName());
                System.out.println("The group ARN is " +
group.dbClusterParameterGroupArn());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void createDBClusterParameterGroup(RdsClient rdsClient, String
dbClusterGroupName,
```

```
            String dbParameterGroupFamily) {
        try {
            CreateDbClusterParameterGroupRequest groupRequest =
CreateDbClusterParameterGroupRequest.builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .description("Created by using the AWS SDK for Java")
                    .build();

            CreateDbClusterParameterGroupResponse response =
rdsClient.createDBClusterParameterGroup(groupRequest);
            System.out.println("The group name is " +
response.dbClusterParameterGroup().dbClusterParameterGroupName());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .engine("aurora-mysql")
                    .defaultOnly(true)
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
engineOb.engine());
                System.out.println("The version number of the database engine " +
engineOb.engineVersion());
            }
```

```
        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
 including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

This example requires an AWS Secrets Manager secret that contains the database
 credentials. If you do not create a
secret, this example will not work. For more details, see:

https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html

This Kotlin example performs the following tasks:

1. Returns a list of the available DB engines.
2. Creates a custom DB parameter group.
3. Gets the parameter groups.
4. Gets the parameters in the group.
5. Modifies the auto_increment_increment parameter.
6. Displays the updated parameter value.
7. Gets a list of allowed engine versions.
8. Creates an Aurora DB cluster database.
9. Waits for DB instance to be ready.
10. Gets a list of instance classes available for the selected engine.
11. Creates a database instance in the cluster.
12. Waits for the database instance in the cluster to be ready.
13. Creates a snapshot.
14. Waits for DB snapshot to be ready.
15. Deletes the DB instance.
16. Deletes the DB cluster.
17. Deletes the DB cluster group.
 */

var slTime: Long = 20
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <dbClusterGroupName> <dbParameterGroupFamily>
 <dbInstanceClusterIdentifier> <dbName> <dbSnapshotIdentifier> <secretName>
        Where:
```

```
            dbClusterGroupName - The database group name.
            dbParameterGroupFamily - The database parameter group name.
            dbInstanceClusterIdentifier - The database instance identifier.
            dbName -  The database name.
            dbSnapshotIdentifier - The snapshot identifier.
            secretName - The name of the AWS Secrets Manager secret that contains
the database credentials.
    """

    if (args.size != 7) {
        println(usage)
        exitProcess(1)
    }

    val dbClusterGroupName = args[0]
    val dbParameterGroupFamily = args[1]
    val dbInstanceClusterIdentifier = args[2]
    val dbInstanceIdentifier = args[3]
    val dbName = args[4]
    val dbSnapshotIdentifier = args[5]
    val secretName = args[6]

    val gson = Gson()
    val user = gson.fromJson(getSecretValues(secretName).toString(),
User::class.java)
    val username = user.username
    val userPassword = user.password

    println("1. Return a list of the available DB engines")
    describeAuroraDBEngines()

    println("2. Create a custom parameter group")
    createDBClusterParameterGroup(dbClusterGroupName, dbParameterGroupFamily)

    println("3. Get the parameter group")
    describeDbClusterParameterGroups(dbClusterGroupName)

    println("4. Get the parameters in the group")
    describeDbClusterParameters(dbClusterGroupName, 0)

    println("5. Modify the auto_increment_offset parameter")
    modifyDBClusterParas(dbClusterGroupName)

    println("6. Display the updated parameter value")
```

```
    describeDbClusterParameters(dbClusterGroupName, -1)

    println("7. Get a list of allowed engine versions")
    getAllowedClusterEngines(dbParameterGroupFamily)

    println("8. Create an Aurora DB cluster database")
    val arnClusterVal = createDBCluster(dbClusterGroupName, dbName,
 dbInstanceClusterIdentifier, username, userPassword)
    println("The ARN of the cluster is $arnClusterVal")

    println("9. Wait for DB instance to be ready")
    waitForClusterInstanceReady(dbInstanceClusterIdentifier)

    println("10. Get a list of instance classes available for the selected
 engine")
    val instanceClass = getListInstanceClasses()

    println("11. Create a database instance in the cluster.")
    val clusterDBARN = createDBInstanceCluster(dbInstanceIdentifier,
 dbInstanceClusterIdentifier, instanceClass)
    println("The ARN of the database is $clusterDBARN")

    println("12. Wait for DB instance to be ready")
    waitDBAuroraInstanceReady(dbInstanceIdentifier)

    println("13. Create a snapshot")
    createDBClusterSnapshot(dbInstanceClusterIdentifier, dbSnapshotIdentifier)

    println("14. Wait for DB snapshot to be ready")
    waitSnapshotReady(dbSnapshotIdentifier, dbInstanceClusterIdentifier)

    println("15. Delete the DB instance")
    deleteDBInstance(dbInstanceIdentifier)

    println("16. Delete the DB cluster")
    deleteCluster(dbInstanceClusterIdentifier)

    println("17. Delete the DB cluster group")
    if (clusterDBARN != null) {
        deleteDBClusterGroup(dbClusterGroupName, clusterDBARN)
    }
    println("The Scenario has successfully completed.")
}
```

```
@Throws(InterruptedException::class)
suspend fun deleteDBClusterGroup(dbClusterGroupName: String, clusterDBARN:
 String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
            isDataDel = false
            didFind = false
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(clusterDBARN) == 0) {
                        println("$clusterDBARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database ARN.
                        isDataDel = true
                    }
                    delay(slTime * 1000)
                    index++
                }
            }
        }
        val clusterParameterGroupRequest = DeleteDbClusterParameterGroupRequest {
            dbClusterParameterGroupName = dbClusterGroupName
        }

        rdsClient.deleteDbClusterParameterGroup(clusterParameterGroupRequest)
        println("$dbClusterGroupName was deleted.")
    }
}

suspend fun deleteCluster(dbInstanceClusterIdentifier: String) {
    val deleteDbClusterRequest = DeleteDbClusterRequest {
```

```
        dbClusterIdentifier = dbInstanceClusterIdentifier
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        rdsClient.deleteDbCluster(deleteDbClusterRequest)
        println("$dbInstanceClusterIdentifier was deleted!")
    }
}

suspend fun deleteDBInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}

suspend fun waitSnapshotReady(dbSnapshotIdentifier: String?,
 dbInstanceClusterIdentifier: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbClusterSnapshotsRequest {
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
        dbClusterIdentifier = dbInstanceClusterIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!snapshotReady) {
            val response = rdsClient.describeDbClusterSnapshots(snapshotsRequest)
            val snapshotList = response.dbClusterSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
```

```
                    } else {
                        println(".")
                        delay(slTime * 5000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}

suspend fun createDBClusterSnapshot(dbInstanceClusterIdentifier: String?,
 dbSnapshotIdentifier: String?) {
    val snapshotRequest = CreateDbClusterSnapshotRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterSnapshot(snapshotRequest)
        println("The Snapshot ARN is
 ${response.dbClusterSnapshot?.dbClusterSnapshotArn}")
    }
}

suspend fun waitDBAuroraInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")
    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    var endpoint = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            response.dbInstances?.forEach { instance ->
                instanceReadyStr = instance.dbInstanceStatus.toString()
                if (instanceReadyStr.contains("available")) {
                    endpoint = instance.endpoint?.address.toString()
                    instanceReady = true
                } else {
                    print(".")
```

```
                    delay(sleepTime * 1000)
                }
            }
        }
    }
    println("Database instance is available! The connection endpoint is
 $endpoint")
}

suspend fun createDBInstanceCluster(dbInstanceIdentifierVal: String?,
 dbInstanceClusterIdentifierVal: String?, instanceClassVal: String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbClusterIdentifier = dbInstanceClusterIdentifierVal
        engine = "aurora-mysql"
        dbInstanceClass = instanceClassVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}

suspend fun getListInstanceClasses(): String {
    val optionsRequest = DescribeOrderableDbInstanceOptionsRequest {
        engine = "aurora-mysql"
        maxRecords = 20
    }
    var instanceClass = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeOrderableDbInstanceOptions(optionsRequest)
        response.orderableDbInstanceOptions?.forEach { instanceOption ->
            instanceClass = instanceOption.dbInstanceClass.toString()
            println("The instance class is ${instanceOption.dbInstanceClass}")
            println("The engine version is ${instanceOption.engineVersion}")
        }
    }
    return instanceClass
}

// Waits until the database instance is available.
```

```
suspend fun waitForClusterInstanceReady(dbClusterIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbClustersRequest {
        dbClusterIdentifier = dbClusterIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbClusters(instanceRequest)
            response.dbClusters?.forEach { cluster ->
                instanceReadyStr = cluster.status.toString()
                if (instanceReadyStr.contains("available")) {
                    instanceReady = true
                } else {
                    print(".")
                    delay(sleepTime * 1000)
                }
            }
        }
    }
    println("Database cluster is available!")
}

suspend fun createDBCluster(dbParameterGroupFamilyVal: String?, dbName: String?,
 dbClusterIdentifierVal: String?, userName: String?, password: String?): String?
 {
    val clusterRequest = CreateDbClusterRequest {
        databaseName = dbName
        dbClusterIdentifier = dbClusterIdentifierVal
        dbClusterParameterGroupName = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
        masterUsername = userName
        masterUserPassword = password
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbCluster(clusterRequest)
        return response.dbCluster?.dbClusterArn
    }
}
```

```
// Get a list of allowed engine versions.
suspend fun getAllowedClusterEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        response.dbEngineVersions?.forEach { dbEngine ->
            println("The engine version is ${dbEngine.engineVersion}")
            println("The engine description is ${dbEngine.dbEngineDescription}")
        }
    }
}

// Modify the auto_increment_offset parameter.
suspend fun modifyDBClusterParas(dClusterGroupName: String?) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.fromValue("immediate")
        parameterValue = "5"
    }

    val paraList = ArrayList<Parameter>()
    paraList.add(parameter1)
    val groupRequest = ModifyDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dClusterGroupName
        parameters = paraList
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbClusterParameterGroup(groupRequest)
        println("The parameter group ${response.dbClusterParameterGroupName} was
 successfully modified")
    }
}

suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
```

```
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is
 ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
        }
    }
}

suspend fun describeDbClusterParameterGroups(dbClusterGroupName: String?) {
    val groupsRequest = DescribeDbClusterParameterGroupsRequest {
        dbClusterParameterGroupName = dbClusterGroupName
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbClusterParameterGroups(groupsRequest)
        response.dbClusterParameterGroups?.forEach { group ->
            println("The group name is ${group.dbClusterParameterGroupName}")
            println("The group ARN is ${group.dbClusterParameterGroupArn}")
        }
    }
}
```

```
suspend fun createDBClusterParameterGroup(dbClusterGroupNameVal: String?,
 dbParameterGroupFamilyVal: String?) {
    val groupRequest = CreateDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dbClusterGroupNameVal
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterParameterGroup(groupRequest)
        println("The group name is
 ${response.dbClusterParameterGroup?.dbClusterParameterGroupName}")
    }
}

suspend fun describeAuroraDBEngines() {
    val engineVersionsRequest = DescribeDbEngineVersionsRequest {
        engine = "aurora-mysql"
        defaultOnly = true
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(engineVersionsRequest)
        response.dbEngineVersions?.forEach { engineOb ->
            println("The name of the DB parameter group family for the database
 engine is ${engineOb.dbParameterGroupFamily}")
            println("The name of the database engine ${engineOb.engine}")
            println("The version number of the database engine
 ${engineOb.engineVersion}")
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot

- CreateDBInstance
- DeleteDBCluster
- Banco de dados excluído ClusterParameterGroup
- DeleteDBInstance
- Descreva o DB ClusterParameterGroups
- Descreva o DB ClusterParameters
- Descreva o DB ClusterSnapshots
- DescribeDBClusters
- Descreva o DB EngineVersions
- DescribeDBInstances
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ClusterParameterGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class AuroraClusterScenario:
    """Runs a scenario that shows how to get started using Aurora DB clusters."""

    def __init__(self, aurora_wrapper):
        """
        :param aurora_wrapper: An object that wraps Aurora DB cluster actions.
        """
        self.aurora_wrapper = aurora_wrapper

    def create_parameter_group(self, db_engine, parameter_group_name):
        """
```

```
        Shows how to get available engine versions for a specified database
engine and
        create a DB cluster parameter group that is compatible with a selected
engine family.

        :param db_engine: The database engine to use as a basis.
        :param parameter_group_name: The name given to the newly created
parameter group.
        :return: The newly created parameter group.
        """
        print(
            f"Checking for an existing DB cluster parameter group named
{parameter_group_name}."
        )
        parameter_group =
self.aurora_wrapper.get_parameter_group(parameter_group_name)
        if parameter_group is None:
            print(f"Getting available database engine versions for {db_engine}.")
            engine_versions = self.aurora_wrapper.get_engine_versions(db_engine)
            families = list({ver["DBParameterGroupFamily"] for ver in
engine_versions})
            family_index = q.choose("Which family do you want to use? ",
families)
            print(f"Creating a DB cluster parameter group.")
            self.aurora_wrapper.create_parameter_group(
                parameter_group_name, families[family_index], "Example parameter
group."
            )
            parameter_group = self.aurora_wrapper.get_parameter_group(
                parameter_group_name
            )
        print(f"Parameter group
{parameter_group['DBClusterParameterGroupName']}:")
        pp(parameter_group)
        print("-" * 88)
        return parameter_group

    def set_user_parameters(self, parameter_group_name):
        """
        Shows how to get the parameters contained in a custom parameter group and
        update some of the parameter values in the group.

        :param parameter_group_name: The name of the parameter group to query and
modify.
```

```
        """
        print("Let's set some parameter values in your parameter group.")
        auto_inc_parameters = self.aurora_wrapper.get_parameters(
            parameter_group_name, name_prefix="auto_increment"
        )
        update_params = []
        for auto_inc in auto_inc_parameters:
            if auto_inc["IsModifiable"] and auto_inc["DataType"] == "integer":
                print(f"The {auto_inc['ParameterName']} parameter is described
as:")
                print(f"\t{auto_inc['Description']}")
                param_range = auto_inc["AllowedValues"].split("-")
                auto_inc["ParameterValue"] = str(
                    q.ask(
                        f"Enter a value between {param_range[0]} and
{param_range[1]}: ",
                        q.is_int,
                        q.in_range(int(param_range[0]), int(param_range[1])),
                    )
                )
                update_params.append(auto_inc)
        self.aurora_wrapper.update_parameters(parameter_group_name,
update_params)
        print(
            "You can get a list of parameters you've set by specifying a source
of 'user'."
        )
        user_parameters = self.aurora_wrapper.get_parameters(
            parameter_group_name, source="user"
        )
        pp(user_parameters)
        print("-" * 88)

    def create_cluster(self, cluster_name, db_engine, db_name, parameter_group):
        """
        Shows how to create an Aurora DB cluster that contains a database of a
specified
        type. The database is also configured to use a custom DB cluster
parameter group.

        :param cluster_name: The name given to the newly created DB cluster.
        :param db_engine: The engine of the created database.
        :param db_name: The name given to the created database.
```

```
        :param parameter_group: The parameter group that is associated with the
DB cluster.
        :return: The newly created DB cluster.
        """
        print("Checking for an existing DB cluster.")
        cluster = self.aurora_wrapper.get_db_cluster(cluster_name)
        if cluster is None:
            admin_username = q.ask(
                "Enter an administrator user name for the database: ",
q.non_empty
            )
            admin_password = q.ask(
                "Enter a password for the administrator (at least 8 characters):
",
                q.non_empty,
            )
            engine_versions = self.aurora_wrapper.get_engine_versions(
                db_engine, parameter_group["DBParameterGroupFamily"]
            )
            engine_choices = [ver["EngineVersion"] for ver in engine_versions]
            print("The available engines for your parameter group are:")
            engine_index = q.choose("Which engine do you want to use? ",
engine_choices)
            print(
                f"Creating DB cluster {cluster_name} and database {db_name}.\n"
                f"The DB cluster is configured to use\n"
                f"your custom parameter group
{parameter_group['DBClusterParameterGroupName']}\n"
                f"and selected engine {engine_choices[engine_index]}.\n"
                f"This typically takes several minutes."
            )
            cluster = self.aurora_wrapper.create_db_cluster(
                cluster_name,
                parameter_group["DBClusterParameterGroupName"],
                db_name,
                db_engine,
                engine_choices[engine_index],
                admin_username,
                admin_password,
            )
            while cluster.get("Status") != "available":
                wait(30)
                cluster = self.aurora_wrapper.get_db_cluster(cluster_name)
            print("Cluster created and available.\n")
```

```
        print("Cluster data:")
        pp(cluster)
        print("-" * 88)
        return cluster

    def create_instance(self, cluster):
        """
        Shows how to create a DB instance in an existing Aurora DB cluster. A new
DB cluster
        contains no DB instances, so you must add one. The first DB instance that
is added
        to a DB cluster defaults to a read-write DB instance.

        :param cluster: The DB cluster where the DB instance is added.
        :return: The newly created DB instance.
        """
        print("Checking for an existing database instance.")
        cluster_name = cluster["DBClusterIdentifier"]
        db_inst = self.aurora_wrapper.get_db_instance(cluster_name)
        if db_inst is None:
            print("Let's create a database instance in your DB cluster.")
            print("First, choose a DB instance type:")
            inst_opts = self.aurora_wrapper.get_orderable_instances(
                cluster["Engine"], cluster["EngineVersion"]
            )
            inst_choices = list({opt["DBInstanceClass"] for opt in inst_opts})
            inst_index = q.choose(
                "Which DB instance class do you want to use? ", inst_choices
            )
            print(
                f"Creating a database instance. This typically takes several
minutes."
            )
            db_inst = self.aurora_wrapper.create_instance_in_cluster(
                cluster_name, cluster_name, cluster["Engine"],
inst_choices[inst_index]
            )
            while db_inst.get("DBInstanceStatus") != "available":
                wait(30)
                db_inst = self.aurora_wrapper.get_db_instance(cluster_name)
        print("Instance data:")
        pp(db_inst)
        print("-" * 88)
        return db_inst
```

```
    @staticmethod
    def display_connection(cluster):
        """
        Displays connection information about an Aurora DB cluster and tips on
 how to
        connect to it.

        :param cluster: The DB cluster to display.
        """
        print(
            "You can now connect to your database using your favorite MySql
 client.\n"
            "One way to connect is by using the 'mysql' shell on an Amazon EC2
 instance\n"
            "that is running in the same VPC as your database cluster. Pass the
 endpoint,\n"
            "port, and administrator user name to 'mysql' and enter your password
\n"
            "when prompted:\n"
        )
        print(
            f"\n\tmysql -h {cluster['Endpoint']} -P {cluster['Port']} -u
 {cluster['MasterUsername']} -p\n"
        )
        print(
            "For more information, see the User Guide for Aurora:\n"
            "\thttps://docs.aws.amazon.com/AmazonRDS/latest/AuroraUserGuide/
CHAP_GettingStartedAurora.CreatingConnecting.Aurora.html#CHAP_GettingStartedAurora.Aurora
        )
        print("-" * 88)

    def create_snapshot(self, cluster_name):
        """
        Shows how to create a DB cluster snapshot and wait until it's available.

        :param cluster_name: The name of a DB cluster to snapshot.
        """
        if q.ask(
            "Do you want to create a snapshot of your DB cluster (y/n)? ",
 q.is_yesno
        ):
            snapshot_id = f"{cluster_name}-{uuid.uuid4()}"
            print(
```

```
                f"Creating a snapshot named {snapshot_id}. This typically takes a
few minutes."
            )
            snapshot = self.aurora_wrapper.create_cluster_snapshot(
                snapshot_id, cluster_name
            )
            while snapshot.get("Status") != "available":
                wait(30)
                snapshot = self.aurora_wrapper.get_cluster_snapshot(snapshot_id)
            pp(snapshot)
            print("-" * 88)

    def cleanup(self, db_inst, cluster, parameter_group):
        """
        Shows how to clean up a DB instance, DB cluster, and DB cluster parameter
group.
        Before the DB cluster parameter group can be deleted, all associated DB
instances and
        DB clusters must first be deleted.

        :param db_inst: The DB instance to delete.
        :param cluster: The DB cluster to delete.
        :param parameter_group: The DB cluster parameter group to delete.
        """
        cluster_name = cluster["DBClusterIdentifier"]
        parameter_group_name = parameter_group["DBClusterParameterGroupName"]
        if q.ask(
            "\nDo you want to delete the database instance, DB cluster, and
parameter "
            "group (y/n)? ",
            q.is_yesno,
        ):
            print(f"Deleting database instance
{db_inst['DBInstanceIdentifier']}.")

self.aurora_wrapper.delete_db_instance(db_inst["DBInstanceIdentifier"])
            print(f"Deleting database cluster {cluster_name}.")
            self.aurora_wrapper.delete_db_cluster(cluster_name)
            print(
                "Waiting for the DB instance and DB cluster to delete.\n"
                "This typically takes several minutes."
            )
            while db_inst is not None or cluster is not None:
                wait(30)
```

```
                if db_inst is not None:
                    db_inst = self.aurora_wrapper.get_db_instance(
                        db_inst["DBInstanceIdentifier"]
                    )
                if cluster is not None:
                    cluster = self.aurora_wrapper.get_db_cluster(
                        cluster["DBClusterIdentifier"]
                    )
            print(f"Deleting parameter group {parameter_group_name}.")
            self.aurora_wrapper.delete_parameter_group(parameter_group_name)

    def run_scenario(self, db_engine, parameter_group_name, cluster_name,
 db_name):
        print("-" * 88)
        print(
            "Welcome to the Amazon Relational Database Service (Amazon RDS) get
 started\n"
            "with Aurora DB clusters demo."
        )
        print("-" * 88)

        parameter_group = self.create_parameter_group(db_engine,
 parameter_group_name)
        self.set_user_parameters(parameter_group_name)
        cluster = self.create_cluster(cluster_name, db_engine, db_name,
 parameter_group)
        wait(5)
        db_inst = self.create_instance(cluster)
        self.display_connection(cluster)
        self.create_snapshot(cluster_name)
        self.cleanup(db_inst, cluster, parameter_group)

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    try:
        scenario = AuroraClusterScenario(AuroraWrapper.from_client())
        scenario.run_scenario(
            "aurora-mysql",
            "doc-example-cluster-parameter-group",
            "doc-example-aurora",
```

```
            "docexampledb",
        )
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Aurora.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon
 RDS) client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The requested parameter group.
        """
        try:
            response = self.rds_client.describe_db_cluster_parameter_groups(
                DBClusterParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBClusterParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
 parameter_group_name)
```

```
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB cluster parameter group that is based on the specified
parameter group
        family.

        :param parameter_group_name: The name of the newly created parameter
group.
        :param parameter_group_family: The family that is used as the basis of
the new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

```
    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            response = self.rds_client.delete_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this
prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBClusterParameterGroupName": parameter_group_name}
            if source is not None:
```

```
                kwargs["Source"] = source
            parameters = []
            paginator =
self.rds_client.get_paginator("describe_db_cluster_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                Parameters=update_parameters,
            )
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
```

```
            return response


    def get_db_cluster(self, cluster_name):
        """
        Gets data about an Aurora DB cluster.

        :param cluster_name: The name of the DB cluster to retrieve.
        :return: The retrieved DB cluster.
        """
        try:
            response = self.rds_client.describe_db_clusters(
                DBClusterIdentifier=cluster_name
            )
            cluster = response["DBClusters"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBClusterNotFoundFault":
                logger.info("Cluster %s does not exist.", cluster_name)
            else:
                logger.error(
                    "Couldn't verify the existence of DB cluster %s. Here's why:
%s: %s",
                    cluster_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return cluster


    def create_db_cluster(
        self,
        cluster_name,
        parameter_group_name,
        db_name,
        db_engine,
        db_engine_version,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB cluster that is configured to use the specified parameter
group.
```

```
        The newly created DB cluster contains a database that uses the specified
engine and
        engine version.

        :param cluster_name: The name of the DB cluster to create.
        :param parameter_group_name: The name of the parameter group to associate
with
                                     the DB cluster.
        :param db_name: The name of the database to create.
        :param db_engine: The database engine of the database that is created,
such as MySql.
        :param db_engine_version: The version of the database engine.
        :param admin_name: The user name of the database administrator.
        :param admin_password: The password of the database administrator.
        :return: The newly created DB cluster.
        """
        try:
            response = self.rds_client.create_db_cluster(
                DatabaseName=db_name,
                DBClusterIdentifier=cluster_name,
                DBClusterParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            cluster = response["DBCluster"]
        except ClientError as err:
            logger.error(
                "Couldn't create database %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return cluster


    def delete_db_cluster(self, cluster_name):
        """
        Deletes a DB cluster.

        :param cluster_name: The name of the DB cluster to delete.
```

```
        """
        try:
            self.rds_client.delete_db_cluster(
                DBClusterIdentifier=cluster_name, SkipFinalSnapshot=True
            )
            logger.info("Deleted DB cluster %s.", cluster_name)
        except ClientError:
            logger.exception("Couldn't delete DB cluster %s.", cluster_name)
            raise


    def create_cluster_snapshot(self, snapshot_id, cluster_id):
        """
        Creates a snapshot of a DB cluster.

        :param snapshot_id: The ID to give the created snapshot.
        :param cluster_id: The DB cluster to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_cluster_snapshot(
                DBClusterSnapshotIdentifier=snapshot_id,
DBClusterIdentifier=cluster_id
            )
            snapshot = response["DBClusterSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                cluster_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def get_cluster_snapshot(self, snapshot_id):
        """
        Gets a DB cluster snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
```

```
        try:
            response = self.rds_client.describe_db_cluster_snapshots(
                DBClusterSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBClusterSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get DB cluster snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def create_instance_in_cluster(
        self, instance_id, cluster_id, db_engine, instance_class
    ):
        """
        Creates a database instance in an existing DB cluster. The first database
that is
        created defaults to a read-write DB instance.

        :param instance_id: The ID to give the newly created DB instance.
        :param cluster_id: The ID of the DB cluster where the DB instance is
created.
        :param db_engine: The database engine of a database to create in the DB
instance.
                          This must be compatible with the configured parameter
group
                          of the DB cluster.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBInstanceIdentifier=instance_id,
                DBClusterIdentifier=cluster_id,
                Engine=db_engine,
                DBInstanceClass=instance_class,
            )
```

```
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned
list of
                                       engine versions to those that are
compatible with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions
```

```
    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by
the DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
```

```
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma biblioteca contendo as funções específicas para o cenário do Aurora.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use phf::{phf_set, Set};
use secrecy::SecretString;
```

```
use std::{collections::HashMap, fmt::Display, time::Duration};

use aws_sdk_rds::{
    error::ProvideErrorMetadata,

 operation::create_db_cluster_parameter_group::CreateDbClusterParameterGroupOutput,
    types::{DbCluster, DbClusterParameterGroup, DbClusterSnapshot, DbInstance,
 Parameter},
};
use sdk_examples_test_utils::waiter::Waiter;
use tracing::{info, trace, warn};

const DB_ENGINE: &str = "aurora-mysql";
const DB_CLUSTER_PARAMETER_GROUP_NAME: &str =
 "RustSDKCodeExamplesDBParameterGroup";
const DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION: &str =
    "Parameter Group created by Rust SDK Code Example";
const DB_CLUSTER_IDENTIFIER: &str = "RustSDKCodeExamplesDBCluster";
const DB_INSTANCE_IDENTIFIER: &str = "RustSDKCodeExamplesDBInstance";

static FILTER_PARAMETER_NAMES: Set<&'static str> = phf_set! {
    "auto_increment_offset",
    "auto_increment_increment",
};

#[derive(Debug, PartialEq, Eq)]
struct MetadataError {
    message: Option<String>,
    code: Option<String>,
}

impl MetadataError {
    fn from(err: &dyn ProvideErrorMetadata) -> Self {
        MetadataError {
            message: err.message().map(String::from),
            code: err.code().map(String::from),
        }
    }
}

impl Display for MetadataError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        let display = match (&self.message, &self.code) {
            (None, None) => "Unknown".to_string(),
```

```
            (None, Some(code)) => format!("({code})"),
            (Some(message), None) => message.to_string(),
            (Some(message), Some(code)) => format!("{message} ({code})"),
        };
        write!(f, "{display}")
    }
}

#[derive(Debug, PartialEq, Eq)]
pub struct ScenarioError {
    message: String,
    context: Option<MetadataError>,
}

impl ScenarioError {
    pub fn with(message: impl Into<String>) -> Self {
        ScenarioError {
            message: message.into(),
            context: None,
        }
    }

    pub fn new(message: impl Into<String>, err: &dyn ProvideErrorMetadata) ->
 Self {
        ScenarioError {
            message: message.into(),
            context: Some(MetadataError::from(err)),
        }
    }
}

impl std::error::Error for ScenarioError {}
impl Display for ScenarioError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        match &self.context {
            Some(c) => write!(f, "{}: {}", self.message, c),
            None => write!(f, "{}", self.message),
        }
    }
}

// Parse the ParameterName, Description, and AllowedValues values and display
 them.
#[derive(Debug)]
```

```
pub struct AuroraScenarioParameter {
    name: String,
    allowed_values: String,
    current_value: String,
}

impl Display for AuroraScenarioParameter {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        write!(
            f,
            "{}: {} (allowed: {})",
            self.name, self.current_value, self.allowed_values
        )
    }
}

impl From<aws_sdk_rds::types::Parameter> for AuroraScenarioParameter {
    fn from(value: aws_sdk_rds::types::Parameter) -> Self {
        AuroraScenarioParameter {
            name: value.parameter_name.unwrap_or_default(),
            allowed_values: value.allowed_values.unwrap_or_default(),
            current_value: value.parameter_value.unwrap_or_default(),
        }
    }
}

pub struct AuroraScenario {
    rds: crate::rds::Rds,
    engine_family: Option<String>,
    engine_version: Option<String>,
    instance_class: Option<String>,
    db_cluster_parameter_group: Option<DbClusterParameterGroup>,
    db_cluster_identifier: Option<String>,
    db_instance_identifier: Option<String>,
    username: Option<String>,
    password: Option<SecretString>,
}

impl AuroraScenario {
    pub fn new(client: crate::rds::Rds) -> Self {
        AuroraScenario {
            rds: client,
            engine_family: None,
            engine_version: None,
```

```
            instance_class: None,
            db_cluster_parameter_group: None,
            db_cluster_identifier: None,
            db_instance_identifier: None,
            username: None,
            password: None,
        }
    }

    // snippet-start:[rust.aurora.get_engines.usage]
    // Get available engine families for Aurora MySql.
rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
    pub async fn get_engines(&self) -> Result<HashMap<String, Vec<String>>,
ScenarioError> {
        let describe_db_engine_versions =
self.rds.describe_db_engine_versions(DB_ENGINE).await;
        trace!(versions=?describe_db_engine_versions, "full list of versions");

        if let Err(err) = describe_db_engine_versions {
            return Err(ScenarioError::new(
                "Failed to retrieve DB Engine Versions",
                &err,
            ));
        };

        let version_count = describe_db_engine_versions
            .as_ref()
            .map(|o| o.db_engine_versions().len())
            .unwrap_or_default();
        info!(version_count, "got list of versions");

        // Create a map of engine families to their available versions.
        let mut versions = HashMap::<String, Vec<String>>::new();
        describe_db_engine_versions
            .unwrap()
            .db_engine_versions()
            .iter()
            .filter_map(
                |v| match (&v.db_parameter_group_family, &v.engine_version) {
                    (Some(family), Some(version)) => Some((family.clone(),
version.clone())),
                    _ => None,
                },
```

```
            )
            .for_each(|(family, version)|
versions.entry(family).or_default().push(version));

        Ok(versions)
    }
    // snippet-end:[rust.aurora.get_engines.usage]

    // snippet-start:[rust.aurora.get_instance_classes.usage]
    pub async fn get_instance_classes(&self) -> Result<Vec<String>,
ScenarioError> {
        let describe_orderable_db_instance_options_items = self
            .rds
            .describe_orderable_db_instance_options(
                DB_ENGINE,
                self.engine_version
                    .as_ref()
                    .expect("engine version for db instance options")
                    .as_str(),
            )
            .await;

        describe_orderable_db_instance_options_items
            .map(|options| {
                options
                    .iter()
                    .map(|o|
o.db_instance_class().unwrap_or_default().to_string())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Could not get available instance
classes", &err))
    }
    // snippet-end:[rust.aurora.get_instance_classes.usage]

    // snippet-start:[rust.aurora.set_engine.usage]
    // Select an engine family and create a custom DB cluster parameter group.
rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
    pub async fn set_engine(&mut self, engine: &str, version: &str) -> Result<(),
ScenarioError> {
        self.engine_family = Some(engine.to_string());
        self.engine_version = Some(version.to_string());
        let create_db_cluster_parameter_group = self
            .rds
```

```
            .create_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION,
                engine,
            )
            .await;

        match create_db_cluster_parameter_group {
            Ok(CreateDbClusterParameterGroupOutput {
                db_cluster_parameter_group: None,
                ..
            }) => {
                return Err(ScenarioError::with(
                    "CreateDBClusterParameterGroup had empty response",
                ));
            }
            Err(error) => {
                if error.code() == Some("DBParameterGroupAlreadyExists") {
                    info!("Cluster Parameter Group already exists, nothing to
do");
                } else {
                    return Err(ScenarioError::new(
                        "Could not create Cluster Parameter Group",
                        &error,
                    ));
                }
            }
            _ => {
                info!("Created Cluster Parameter Group");
            }
        }

        Ok(())
    }
    // snippet-end:[rust.aurora.set_engine.usage]

    pub fn set_instance_class(&mut self, instance_class: Option<String>) {
        self.instance_class = instance_class;
    }

    pub fn set_login(&mut self, username: Option<String>, password:
Option<SecretString>) {
        self.username = username;
        self.password = password;
```

```
    }

    pub async fn connection_string(&self) -> Result<String, ScenarioError> {
        let cluster = self.get_cluster().await?;
        let endpoint = cluster.endpoint().unwrap_or_default();
        let port = cluster.port().unwrap_or_default();
        let username = cluster.master_username().unwrap_or_default();
        Ok(format!("mysql -h {endpoint} -P {port} -u {username} -p"))
    }

    // snippet-start:[rust.aurora.get_cluster.usage]
    pub async fn get_cluster(&self) -> Result<DbCluster, ScenarioError> {
        let describe_db_clusters_output = self
            .rds
            .describe_db_clusters(
                self.db_cluster_identifier
                    .as_ref()
                    .expect("cluster identifier")
                    .as_str(),
            )
            .await;
        if let Err(err) = describe_db_clusters_output {
            return Err(ScenarioError::new("Failed to get cluster", &err));
        }

        let db_cluster = describe_db_clusters_output
            .unwrap()
            .db_clusters
            .and_then(|output| output.first().cloned());

        db_cluster.ok_or_else(|| ScenarioError::with("Did not find the cluster"))
    }
    // snippet-end:[rust.aurora.get_cluster.usage]

    // snippet-start:[rust.aurora.cluster_parameters.usage]
    // Get the parameter group. rds.DescribeDbClusterParameterGroups
    // Get parameters in the group. This is a long list so you will have to
 paginate. Find the auto_increment_offset and auto_increment_increment parameters
 (by ParameterName). rds.DescribeDbClusterParameters
    // Parse the ParameterName, Description, and AllowedValues values and display
 them.
    pub async fn cluster_parameters(&self) ->
 Result<Vec<AuroraScenarioParameter>, ScenarioError> {
        let parameters_output = self
```

```
            .rds
            .describe_db_cluster_parameters(DB_CLUSTER_PARAMETER_GROUP_NAME)
            .await;

        if let Err(err) = parameters_output {
            return Err(ScenarioError::new(
                format!("Failed to retrieve parameters for
{DB_CLUSTER_PARAMETER_GROUP_NAME}"),
                &err,
            ));
        }

        let parameters = parameters_output
            .unwrap()
            .into_iter()
            .flat_map(|p| p.parameters.unwrap_or_default().into_iter())
            .filter(|p|
FILTER_PARAMETER_NAMES.contains(p.parameter_name().unwrap_or_default()))
            .map(AuroraScenarioParameter::from)
            .collect::<Vec<_>>();

        Ok(parameters)
    }
    // snippet-end:[rust.aurora.cluster_parameters.usage]

    // snippet-start:[rust.aurora.update_auto_increment.usage]
    // Modify both the auto_increment_offset and auto_increment_increment
parameters in one call in the custom parameter group. Set their ParameterValue
fields to a new allowable value. rds.ModifyDbClusterParameterGroup.
    pub async fn update_auto_increment(
        &self,
        offset: u8,
        increment: u8,
    ) -> Result<(), ScenarioError> {
        let modify_db_cluster_parameter_group = self
            .rds
            .modify_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value(format!("{offset}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
```

```
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value(format!("{increment}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ],
            )
            .await;

        if let Err(error) = modify_db_cluster_parameter_group {
            return Err(ScenarioError::new(
                "Failed to modify cluster parameter group",
                &error,
            ));
        }

        Ok(())
    }
    // snippet-end:[rust.aurora.update_auto_increment.usage]

    // snippet-start:[rust.aurora.start_cluster_and_instance.usage]
    // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
    // Create an Aurora DB cluster database cluster that contains a MySql
database and uses the parameter group you created.
    // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
    // Get a list of instance classes available for the selected engine
and engine version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql',
EngineVersion=).

    // Create a database instance in the cluster.
    // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
for DBInstanceStatus == 'available'.
    pub async fn start_cluster_and_instance(&mut self) -> Result<(),
ScenarioError> {
        if self.password.is_none() {
            return Err(ScenarioError::with(
                "Must set Secret Password before starting a cluster",
            ));
        }
        let create_db_cluster = self
            .rds
```

```
            .create_db_cluster(
                DB_CLUSTER_IDENTIFIER,
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_ENGINE,
                self.engine_version.as_deref().expect("engine version"),
                self.username.as_deref().expect("username"),
                self.password
                    .replace(SecretString::new("".to_string()))
                    .expect("password"),
            )
            .await;
        if let Err(err) = create_db_cluster {
            return Err(ScenarioError::new(
                "Failed to create DB Cluster with cluster group",
                &err,
            ));
        }

        self.db_cluster_identifier = create_db_cluster
            .unwrap()
            .db_cluster
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
```

```
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for
ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
```

```
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() ==
Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }
    // snippet-end:[rust.aurora.start_cluster_and_instance.usage]

    // snippet-start:[rust.aurora.snapshot.usage]
    // Create a snapshot of the DB cluster. rds.CreateDbClusterSnapshot.
    // Wait for the snapshot to create. rds.DescribeDbClusterSnapshots until
Status == 'available'.
```

```
   pub async fn snapshot(&self, name: &str) -> Result<DbClusterSnapshot,
ScenarioError> {
       let id = self.db_cluster_identifier.as_deref().unwrap_or_default();
       let snapshot = self
           .rds
           .snapshot_cluster(id, format!("{id}_{name}").as_str())
           .await;
       match snapshot {
           Ok(output) => match output.db_cluster_snapshot {
               Some(snapshot) => Ok(snapshot),
               None => Err(ScenarioError::with("Missing Snapshot")),
           },
           Err(err) => Err(ScenarioError::new("Failed to create snapshot",
&err)),
       }
   }
   // snippet-end:[rust.aurora.snapshot.usage]

   // snippet-start:[rust.aurora.clean_up.usage]
   pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
       let mut clean_up_errors: Vec<ScenarioError> = vec![];

       // Delete the instance. rds.DeleteDbInstance.
       let delete_db_instance = self
           .rds
           .delete_db_instance(
               self.db_instance_identifier
                   .as_deref()
                   .expect("instance identifier"),
           )
           .await;
       if let Err(err) = delete_db_instance {
           let identifier = self
               .db_instance_identifier
               .as_deref()
               .unwrap_or("Missing Instance Identifier");
           let message = format!("failed to delete db instance {identifier}");
           clean_up_errors.push(ScenarioError::new(message, &err));
       } else {
           // Wait for the instance to delete
           let waiter = Waiter::default();
           while waiter.sleep().await.is_ok() {
               let describe_db_instances =
self.rds.describe_db_instances().await;
```

```
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;
```

```
        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in
{status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
```

```
                    }
                }
            }
        }

        // Delete the DB cluster parameter group.
 rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }
    // snippet-end:[rust.aurora.clean_up.usage]
}

#[cfg(test)]
pub mod tests;
```

Testes da biblioteca usando automocks em torno do wrapper do RDS Client.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
```

```
// SPDX-License-Identifier: Apache-2.0

use crate::rds::MockRdsImpl;

use super::*;

use std::io::{Error, ErrorKind};

use assert_matches::assert_matches;
use aws_sdk_rds::{
    error::SdkError,
    operation::{
        create_db_cluster::{CreateDBClusterError, CreateDbClusterOutput},
        create_db_cluster_parameter_group::CreateDBClusterParameterGroupError,
        create_db_cluster_snapshot::{CreateDBClusterSnapshotError,
 CreateDbClusterSnapshotOutput},
        create_db_instance::{CreateDBInstanceError, CreateDbInstanceOutput},
        delete_db_cluster::DeleteDbClusterOutput,
        delete_db_cluster_parameter_group::DeleteDbClusterParameterGroupOutput,
        delete_db_instance::DeleteDbInstanceOutput,
        describe_db_cluster_endpoints::DescribeDbClusterEndpointsOutput,
        describe_db_cluster_parameters::{
            DescribeDBClusterParametersError, DescribeDbClusterParametersOutput,
        },
        describe_db_clusters::{DescribeDBClustersError,
 DescribeDbClustersOutput},
        describe_db_engine_versions::{
            DescribeDBEngineVersionsError, DescribeDbEngineVersionsOutput,
        },
        describe_db_instances::{DescribeDBInstancesError,
 DescribeDbInstancesOutput},

 describe_orderable_db_instance_options::DescribeOrderableDBInstanceOptionsError,
        modify_db_cluster_parameter_group::{
            ModifyDBClusterParameterGroupError,
 ModifyDbClusterParameterGroupOutput,
        },
    },
    types::{
        error::DbParameterGroupAlreadyExistsFault, DbClusterEndpoint,
 DbEngineVersion,
        OrderableDbInstanceOption,
    },
};
```

```
use aws_smithy_runtime_api::http::{Response, StatusCode};
use aws_smithy_types::body::SdkBody;
use mockall::predicate::eq;
use secrecy::ExposeSecret;

// snippet-start:[rust.aurora.set_engine.test]
#[tokio::test]
async fn test_scenario_set_engine() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert_eq!(set_engine, Ok(()));
    assert_eq!(Some("aurora-mysql"), scenario.engine_family.as_deref());
    assert_eq!(Some("aurora-mysql8.0"), scenario.engine_version.as_deref());
}

#[tokio::test]
async fn test_scenario_set_engine_not_create() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
```

```
        )
        .return_once(|_, _, _|
 Ok(CreateDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert!(set_engine.is_err());
}

#[tokio::test]
async fn test_scenario_set_engine_param_group_exists() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .withf(|_, _, _| true)
        .return_once(|_, _, _| {
            Err(SdkError::service_error(

 CreateDBClusterParameterGroupError::DbParameterGroupAlreadyExistsFault(
                    DbParameterGroupAlreadyExistsFault::builder().build(),
                ),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-
mysql8.0").await;

    assert!(set_engine.is_err());
}
// snippet-end:[rust.aurora.set_engine.test]

// snippet-start:[rust.aurora.get_engines.test]
#[tokio::test]
async fn test_scenario_get_engines() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Ok(DescribeDbEngineVersionsOutput::builder()
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1a")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1b")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f2")
                        .engine_version("f2a")
                        .build(),
                )
                .db_engine_versions(DbEngineVersion::builder().build())
                .build())
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;

    assert_eq!(
        versions_map,
        Ok(HashMap::from([
            ("f1".into(), vec!["f1a".into(), "f1b".into()]),
            ("f2".into(), vec!["f2a".into()])
        ]))
    );
}

#[tokio::test]
async fn test_scenario_get_engines_failed() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBEngineVersionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_engine_versions error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;
    assert_matches!(
        versions_map,
        Err(ScenarioError { message, context: _ }) if message == "Failed to
 retrieve DB Engine Versions"
    );
}
// snippet-end:[rust.aurora.get_engines.test]

// snippet-start:[rust.aurora.get_instance_classes.test]
#[tokio::test]
async fn test_scenario_get_instance_classes() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Ok(vec![
```

```
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t1")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t2")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t3")
                    .build(),
            ])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario
        .set_engine("aurora-mysql", "aurora-mysql8.0")
        .await
        .expect("set engine");

    let instance_classes = scenario.get_instance_classes().await;

    assert_eq!(
        instance_classes,
        Ok(vec!["t1".into(), "t2".into(), "t3".into()])
    );
}

#[tokio::test]
async fn test_scenario_get_instance_classes_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Err(SdkError::service_error(

 DescribeOrderableDBInstanceOptionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_orderable_db_instance_options_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });
```

```
    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_family = Some("aurora-mysql".into());
    scenario.engine_version = Some("aurora-mysql8.0".into());

    let instance_classes = scenario.get_instance_classes().await;

    assert_matches!(
        instance_classes,
        Err(ScenarioError {message, context: _}) if message == "Could not get
 available instance classes"
    );
}
// snippet-end:[rust.aurora.get_instance_classes.test]

// snippet-start:[rust.aurora.get_cluster.test]
#[tokio::test]
async fn test_scenario_get_cluster() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;

    assert!(cluster.is_ok());
}

#[tokio::test]
async fn test_scenario_get_cluster_missing_cluster() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()
```

```
 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| Ok(DescribeDbClustersOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;

    assert_matches!(cluster, Err(ScenarioError { message, context: _ }) if
 message == "Did not find the cluster");
}

#[tokio::test]
async fn test_scenario_get_cluster_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_clusters_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });
```

```
    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;

    assert_matches!(cluster, Err(ScenarioError { message, context: _ }) if
 message == "Failed to get cluster");
}
// snippet-end:[rust.aurora.get_cluster.test]

#[tokio::test]
async fn test_scenario_connection_string() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .endpoint("test_endpoint")
                        .port(3306)
                        .master_username("test_username")
                        .build(),
                )
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let connection_string = scenario.connection_string().await;

    assert_eq!(
        connection_string,
        Ok("mysql -h test_endpoint -P 3306 -u test_username -p".into())
    );
}

// snippet-start:[rust.aurora.cluster_parameters.test]
#[tokio::test]
async fn test_scenario_cluster_parameters() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Ok(vec![DescribeDbClusterParametersOutput::builder()
                .parameters(Parameter::builder().parameter_name("a").build())
                .parameters(Parameter::builder().parameter_name("b").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("c").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("d").build())
                .build()])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());

    let params = scenario.cluster_parameters().await.expect("cluster params");
    let names: Vec<String> = params.into_iter().map(|p| p.name).collect();
    assert_eq!(
        names,
        vec!["auto_increment_offset", "auto_increment_increment"]
    );
}

#[tokio::test]
async fn test_scenario_cluster_parameters_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBClusterParametersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
```

```
                    "describe_db_cluster_parameters_error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let params = scenario.cluster_parameters().await;
    assert_matches!(params, Err(ScenarioError { message, context: _ }) if message
 == "Failed to retrieve parameters for RustSDKCodeExamplesDBParameterGroup");
}
// snippet-end:[rust.aurora.cluster_parameters.test]

// snippet-start:[rust.aurora.update_auto_increment.test]
#[tokio::test]
async fn test_scenario_update_auto_increment() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .withf(|name, params| {
            assert_eq!(name, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(
                params,
                &vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value("10")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value("20")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ]
            );
            true
        })
        .return_once(|_, _|
 Ok(ModifyDbClusterParameterGroupOutput::builder().build()));
```

```
    let scenario = AuroraScenario::new(mock_rds);

    scenario
        .update_auto_increment(10, 20)
        .await
        .expect("update auto increment");
}

#[tokio::test]
async fn test_scenario_update_auto_increment_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .return_once(|_, _| {
            Err(SdkError::service_error(

 ModifyDBClusterParameterGroupError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "modify_db_cluster_parameter_group_error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let update = scenario.update_auto_increment(10, 20).await;
    assert_matches!(update, Err(ScenarioError { message, context: _}) if message
 == "Failed to modify cluster parameter group");
}
// snippet-end:[rust.aurora.update_auto_increment.test]

// snippet-start:[rust.aurora.start_cluster_and_instance.test]
#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
```

```
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

.db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });
```

```
    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
```

```
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message
 == "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
```

```
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message
 == "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
```

```
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message
 == "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()

 .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
```

```
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()

.db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
```

```
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
// snippet-end:[rust.aurora.start_cluster_and_instance.test]

// snippet-start:[rust.aurora.clean_up.test]
#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
```

```
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
```

```
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
 Describe Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
```

```
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
```

```
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
Describe Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first
Describe Cluster
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second
 Describe Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
// snippet-end:[rust.aurora.clean_up.test]

// snippet-start:[rust.aurora.snapshot.test]
#[tokio::test]
async fn test_scenario_snapshot() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _| {
            Ok(CreateDbClusterSnapshotOutput::builder()
                .db_cluster_snapshot(
                    DbClusterSnapshot::builder()
                        .db_cluster_identifier("MockCluster")

 .db_cluster_snapshot_identifier("MockCluster_MockSnapshot")
                        .build(),
                )
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
    assert!(create_snapshot.is_ok());
}

#[tokio::test]
async fn test_scenario_snapshot_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _| {
            Err(SdkError::service_error(
```

```
                CreateDBClusterSnapshotError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create snapshot error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(),
 SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
    assert_matches!(create_snapshot, Err(ScenarioError { message, context: _}) if
 message == "Failed to create snapshot");
}

#[tokio::test]
async fn test_scenario_snapshot_invalid() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _|
 Ok(CreateDbClusterSnapshotOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
    assert_matches!(create_snapshot, Err(ScenarioError { message, context: _}) if
 message == "Missing Snapshot");
}
// snippet-end:[rust.aurora.snapshot.test]
```

Um binário para executar o cenário do início ao fim usando o inquiridor para que o usuário possa tomar algumas decisões.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::fmt::Display;
```

```
use anyhow::anyhow;
use aurora_code_examples::{
    aurora_scenario::{AuroraScenario, ScenarioError},
    rds::Rds as RdsClient,
};
use aws_sdk_rds::Client;
use inquire::{validator::StringValidator, CustomUserError};
use secrecy::SecretString;
use tracing::warn;

#[derive(Default, Debug)]
struct Warnings(Vec<String>);

impl Warnings {
    fn new() -> Self {
        Warnings(Vec::with_capacity(5))
    }

    fn push(&mut self, warning: &str, error: ScenarioError) {
        let formatted = format!("{warning}: {error}");
        warn!("{formatted}");
        self.0.push(formatted);
    }

    fn is_empty(&self) -> bool {
        self.0.is_empty()
    }
}

impl Display for Warnings {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "Warnings:")?;
        for warning in &self.0 {
            writeln!(f, "{: >4}- {warning}", "")?;
        }
        Ok(())
    }
}

fn select(
    prompt: &str,
    choices: Vec<String>,
    error_message: &str,
```

```
) -> Result<String, anyhow::Error> {
    inquire::Select::new(prompt, choices)
        .prompt()
        .map_err(|error| anyhow!("{error_message}: {error}"))
}

// Prepare the Aurora Scenario. Prompt for several settings that are optional to
 the Scenario, but that the user should choose for the demo.
// This includes the engine, engine version, and instance class.
async fn prepare_scenario(rds: RdsClient) -> Result<AuroraScenario,
 anyhow::Error> {
    let mut scenario = AuroraScenario::new(rds);

    // Get available engine families for Aurora MySql.
 rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
 'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
    let available_engines = scenario.get_engines().await;
    if let Err(error) = available_engines {
        return Err(anyhow!("Failed to get available engines: {}", error));
    }
    let available_engines = available_engines.unwrap();

    // Select an engine family and create a custom DB cluster parameter group.
 rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
    let engine = select(
        "Select an Aurora engine family",
        available_engines.keys().cloned().collect::<Vec<String>>(),
        "Invalid engine selection",
    )?;

    let version = select(
        format!("Select an Aurora engine version for {engine}").as_str(),
        available_engines.get(&engine).cloned().unwrap_or_default(),
        "Invalid engine version selection",
    )?;

    let set_engine = scenario.set_engine(engine.as_str(),
 version.as_str()).await;
    if let Err(error) = set_engine {
        return Err(anyhow!("Could not set engine: {}", error));
    }

    let instance_classes = scenario.get_instance_classes().await;
    match instance_classes {
```

```
        Ok(classes) => {
            let instance_class = select(
                format!("Select an Aurora instance class for {engine}").as_str(),
                classes,
                "Invalid instance class selection",
            )?;
            scenario.set_instance_class(Some(instance_class))
        }
        Err(err) => return Err(anyhow!("Failed to get instance classes for
 engine: {err}")),
    }

    Ok(scenario)
}

// Prepare the cluster, creating a custom parameter group overriding some group
 parameters based on user input.
async fn prepare_cluster(scenario: &mut AuroraScenario, warnings: &mut Warnings)
 -> Result<(), ()> {
    show_parameters(scenario, warnings).await;

    let offset = prompt_number_or_default(warnings, "auto_increment_offset", 5);
    let increment = prompt_number_or_default(warnings,
 "auto_increment_increment", 3);

    // Modify both the auto_increment_offset and auto_increment_increment
 parameters in one call in the custom parameter group. Set their ParameterValue
 fields to a new allowable value. rds.ModifyDbClusterParameterGroup.
    let update_auto_increment = scenario.update_auto_increment(offset,
 increment).await;

    if let Err(error) = update_auto_increment {
        warnings.push("Failed to update auto increment", error);
        return Err(());
    }

    // Get and display the updated parameters. Specify Source of 'user' to get
 just the modified parameters. rds.DescribeDbClusterParameters(Source='user')
    show_parameters(scenario, warnings).await;

    let username = inquire::Text::new("Username for the database (default
 'testuser')")
        .with_default("testuser")
        .with_initial_value("testuser")
```

```
        .prompt();

    if let Err(error) = username {
        warnings.push(
            "Failed to get username, using default",
            ScenarioError::with(format!("Error from inquirer: {error}")),
        );
        return Err(());
    }
    let username = username.unwrap();

    let password = inquire::Text::new("Password for the database (minimum 8
 characters)")
        .with_validator(|i: &str| {
            if i.len() >= 8 {
                Ok(inquire::validator::Validation::Valid)
            } else {
                Ok(inquire::validator::Validation::Invalid(
                    "Password must be at least 8 characters".into(),
                ))
            }
        })
        .prompt();

    let password: Option<SecretString> = match password {
        Ok(password) => Some(SecretString::from(password)),
        Err(error) => {
            warnings.push(
                "Failed to get password, using none (and not starting a DB)",
                ScenarioError::with(format!("Error from inquirer: {error}")),
            );
            return Err(());
        }
    };

    scenario.set_login(Some(username), password);

    Ok(())
}

// Start a single instance in the cluster,
async fn run_instance(scenario: &mut AuroraScenario) -> Result<(), ScenarioError>
 {
```

```
    // Create an Aurora DB cluster database cluster that contains a MySql
 database and uses the parameter group you created.
    // Create a database instance in the cluster.
    // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check
 for DBInstanceStatus == 'available'.
    scenario.start_cluster_and_instance().await?;

    let connection_string = scenario.connection_string().await?;

    println!("Database ready: {connection_string}",);

    let _ = inquire::Text::new("Use the database with the connection string. When
 you're finished, press enter key to continue.").prompt();

    // Create a snapshot of the DB cluster. rds.CreateDbClusterSnapshot.
    // Wait for the snapshot to create. rds.DescribeDbClusterSnapshots until
 Status == 'available'.
    let snapshot_name = inquire::Text::new("Provide a name for the snapshot")
        .prompt()
        .unwrap_or(String::from("ScenarioRun"));
    let snapshot = scenario.snapshot(snapshot_name.as_str()).await?;
    println!(
        "Snapshot is available: {}",
        snapshot.db_cluster_snapshot_arn().unwrap_or("Missing ARN")
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), anyhow::Error> {
    tracing_subscriber::fmt::init();
    let sdk_config = aws_config::from_env().load().await;
    let client = Client::new(&sdk_config);
    let rds = RdsClient::new(client);
    let mut scenario = prepare_scenario(rds).await?;

    // At this point, the scenario has things in AWS and needs to get cleaned up.
    let mut warnings = Warnings::new();

    if prepare_cluster(&mut scenario, &mut warnings).await.is_ok() {
        println!("Configured database cluster, starting an instance.");
        if let Err(err) = run_instance(&mut scenario).await {
            warnings.push("Problem running instance", err);
```

```
        }
    }

    // Clean up the instance, cluster, and parameter group, waiting for the
 instance and cluster to delete before moving on.
    let clean_up = scenario.clean_up().await;
    if let Err(errors) = clean_up {
        for error in errors {
            warnings.push("Problem cleaning up scenario", error);
        }
    }

    if warnings.is_empty() {
        Ok(())
    } else {
        println!("There were problems running the scenario:");
        println!("{warnings}");
        Err(anyhow!("There were problems running the scenario"))
    }
}

#[derive(Clone)]
struct U8Validator {}
impl StringValidator for U8Validator {
    fn validate(&self, input: &str) -> Result<inquire::validator::Validation,
 CustomUserError> {
        if input.parse::<u8>().is_err() {
            Ok(inquire::validator::Validation::Invalid(
                "Can't parse input as number".into(),
            ))
        } else {
            Ok(inquire::validator::Validation::Valid)
        }
    }
}

async fn show_parameters(scenario: &AuroraScenario, warnings: &mut Warnings) {
    let parameters = scenario.cluster_parameters().await;

    match parameters {
        Ok(parameters) => {
            println!("Current parameters");
            for parameter in parameters {
                println!("\t{parameter}");
```

```
            }
        }
        Err(error) => warnings.push("Could not find cluster parameters", error),
    }
}

fn prompt_number_or_default(warnings: &mut Warnings, name: &str, default: u8) ->
 u8 {
    let input = inquire::Text::new(format!("Updated {name}:").as_str())
        .with_validator(U8Validator {})
        .prompt();

    match input {
        Ok(increment) => match increment.parse::<u8>() {
            Ok(increment) => increment,
            Err(error) => {
                warnings.push(
                    format!("Invalid updated {name} (using {default}
 instead)").as_str(),
                    ScenarioError::with(format!("{error}")),
                );
                default
            }
        },
        Err(error) => {
            warnings.push(
                format!("Invalid updated {name} (using {default}
 instead)").as_str(),
                ScenarioError::with(format!("{error}")),
            );
            default
        }
    }
}
```

Um wrapper do serviço Amazon RDS que permite automocking para testes.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use aws_sdk_rds::{
    error::SdkError,
```

```
    operation::{
        create_db_cluster::{CreateDBClusterError, CreateDbClusterOutput},
        create_db_cluster_parameter_group::CreateDBClusterParameterGroupError,
        create_db_cluster_parameter_group::CreateDbClusterParameterGroupOutput,
        create_db_cluster_snapshot::{CreateDBClusterSnapshotError,
 CreateDbClusterSnapshotOutput},
        create_db_instance::{CreateDBInstanceError, CreateDbInstanceOutput},
        delete_db_cluster::{DeleteDBClusterError, DeleteDbClusterOutput},
        delete_db_cluster_parameter_group::{
            DeleteDBClusterParameterGroupError,
 DeleteDbClusterParameterGroupOutput,
        },
        delete_db_instance::{DeleteDBInstanceError, DeleteDbInstanceOutput},
        describe_db_cluster_endpoints::{
            DescribeDBClusterEndpointsError, DescribeDbClusterEndpointsOutput,
        },
        describe_db_cluster_parameters::{
            DescribeDBClusterParametersError, DescribeDbClusterParametersOutput,
        },
        describe_db_clusters::{DescribeDBClustersError,
 DescribeDbClustersOutput},
        describe_db_engine_versions::{
            DescribeDBEngineVersionsError, DescribeDbEngineVersionsOutput,
        },
        describe_db_instances::{DescribeDBInstancesError,
 DescribeDbInstancesOutput},

 describe_orderable_db_instance_options::DescribeOrderableDBInstanceOptionsError,
        modify_db_cluster_parameter_group::{
            ModifyDBClusterParameterGroupError,
 ModifyDbClusterParameterGroupOutput,
        },
    },
    types::{OrderableDbInstanceOption, Parameter},
    Client as RdsClient,
};
use secrecy::{ExposeSecret, SecretString};

#[cfg(test)]
use mockall::automock;

#[cfg(test)]
pub use MockRdsImpl as Rds;
#[cfg(not(test))]
```

```
pub use RdsImpl as Rds;

pub struct RdsImpl {
    pub inner: RdsClient,
}

#[cfg_attr(test, automock)]
impl RdsImpl {
    pub fn new(inner: RdsClient) -> Self {
        RdsImpl { inner }
    }

    // snippet-start:[rust.aurora.describe_db_engine_versions.wrapper]
    pub async fn describe_db_engine_versions(
        &self,
        engine: &str,
    ) -> Result<DescribeDbEngineVersionsOutput,
 SdkError<DescribeDBEngineVersionsError>> {
        self.inner
            .describe_db_engine_versions()
            .engine(engine)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_engine_versions.wrapper]

    // snippet-start:[rust.aurora.describe_orderable_db_instance_options.wrapper]
    pub async fn describe_orderable_db_instance_options(
        &self,
        engine: &str,
        engine_version: &str,
    ) -> Result<Vec<OrderableDbInstanceOption>,
 SdkError<DescribeOrderableDBInstanceOptionsError>>
    {
        self.inner
            .describe_orderable_db_instance_options()
            .engine(engine)
            .engine_version(engine_version)
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
    }
```

```
    // snippet-end:[rust.aurora.describe_orderable_db_instance_options.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster_parameter_group.wrapper]
    pub async fn create_db_cluster_parameter_group(
        &self,
        name: &str,
        description: &str,
        family: &str,
    ) -> Result<CreateDbClusterParameterGroupOutput,
SdkError<CreateDBClusterParameterGroupError>>
    {
        self.inner
            .create_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .description(description)
            .db_parameter_group_family(family)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_cluster_parameter_group.wrapper]

    // snippet-start:[rust.aurora.describe_db_clusters.wrapper]
    pub async fn describe_db_clusters(
        &self,
        id: &str,
    ) -> Result<DescribeDbClustersOutput, SdkError<DescribeDBClustersError>> {
        self.inner
            .describe_db_clusters()
            .db_cluster_identifier(id)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_clusters.wrapper]

    // snippet-start:[rust.aurora.describe_db_cluster_parameters.wrapper]
    pub async fn describe_db_cluster_parameters(
        &self,
        name: &str,
    ) -> Result<Vec<DescribeDbClusterParametersOutput>,
SdkError<DescribeDBClusterParametersError>>
    {
        self.inner
            .describe_db_cluster_parameters()
            .db_cluster_parameter_group_name(name)
```

```
            .into_paginator()
            .send()
            .try_collect()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_cluster_parameters.wrapper]

    // snippet-start:[rust.aurora.modify_db_cluster_parameter_group.wrapper]
    pub async fn modify_db_cluster_parameter_group(
        &self,
        name: &str,
        parameters: Vec<Parameter>,
    ) -> Result<ModifyDbClusterParameterGroupOutput,
SdkError<ModifyDBClusterParameterGroupError>>
    {
        self.inner
            .modify_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .set_parameters(Some(parameters))
            .send()
            .await
    }
    // snippet-end:[rust.aurora.modify_db_cluster_parameter_group.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster.wrapper]
    pub async fn create_db_cluster(
        &self,
        name: &str,
        parameter_group: &str,
        engine: &str,
        version: &str,
        username: &str,
        password: SecretString,
    ) -> Result<CreateDbClusterOutput, SdkError<CreateDBClusterError>> {
        self.inner
            .create_db_cluster()
            .db_cluster_identifier(name)
            .db_cluster_parameter_group_name(parameter_group)
            .engine(engine)
            .engine_version(version)
            .master_username(username)
            .master_user_password(password.expose_secret())
            .send()
            .await
```

```
    }
    // snippet-end:[rust.aurora.create_db_cluster.wrapper]

    // snippet-start:[rust.aurora.create_db_instance.wrapper]
    pub async fn create_db_instance(
        &self,
        cluster_name: &str,
        instance_name: &str,
        instance_class: &str,
        engine: &str,
    ) -> Result<CreateDbInstanceOutput, SdkError<CreateDBInstanceError>> {
        self.inner
            .create_db_instance()
            .db_cluster_identifier(cluster_name)
            .db_instance_identifier(instance_name)
            .db_instance_class(instance_class)
            .engine(engine)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_instance.wrapper]

    // snippet-start:[rust.aurora.describe_db_instance.wrapper]
    pub async fn describe_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner
            .describe_db_instances()
            .db_instance_identifier(instance_identifier)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_instance.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster_snapshot.wrapper]
    pub async fn snapshot_cluster(
        &self,
        db_cluster_identifier: &str,
        snapshot_name: &str,
    ) -> Result<CreateDbClusterSnapshotOutput,
SdkError<CreateDBClusterSnapshotError>> {
        self.inner
            .create_db_cluster_snapshot()
```

```
            .db_cluster_identifier(db_cluster_identifier)
            .db_cluster_snapshot_identifier(snapshot_name)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_cluster_snapshot.wrapper]

    // snippet-start:[rust.aurora.describe_db_instances.wrapper]
    pub async fn describe_db_instances(
        &self,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner.describe_db_instances().send().await
    }
    // snippet-end:[rust.aurora.describe_db_instances.wrapper]

    // snippet-start:[rust.aurora.describe_db_cluster_endpoints.wrapper]
    pub async fn describe_db_cluster_endpoints(
        &self,
        cluster_identifier: &str,
    ) -> Result<DescribeDbClusterEndpointsOutput,
SdkError<DescribeDBClusterEndpointsError>> {
        self.inner
            .describe_db_cluster_endpoints()
            .db_cluster_identifier(cluster_identifier)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_cluster_endpoints.wrapper]

    // snippet-start:[rust.aurora.delete_db_instance.wrapper]
    pub async fn delete_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DeleteDbInstanceOutput, SdkError<DeleteDBInstanceError>> {
        self.inner
            .delete_db_instance()
            .db_instance_identifier(instance_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.delete_db_instance.wrapper]

    // snippet-start:[rust.aurora.delete_db_cluster.wrapper]
```

```
    pub async fn delete_db_cluster(
        &self,
        cluster_identifier: &str,
    ) -> Result<DeleteDbClusterOutput, SdkError<DeleteDBClusterError>> {
        self.inner
            .delete_db_cluster()
            .db_cluster_identifier(cluster_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.delete_db_cluster.wrapper]

    // snippet-start:[rust.aurora.delete_db_cluster_parameter_group.wrapper]
    pub async fn delete_db_cluster_parameter_group(
        &self,
        name: &str,
    ) -> Result<DeleteDbClusterParameterGroupOutput,
 SdkError<DeleteDBClusterParameterGroupError>>
    {
        self.inner
            .delete_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.delete_db_cluster_parameter_group.wrapper]
}
```

O Cargo.toml com dependências usadas neste cenário.

```
[package]
name = "aurora-code-examples"
authors = [
  "David Souther <dpsouth@amazon.com>",
]
edition = "2021"
version = "0.1.0"

# See more keys and their definitions at https://doc.rust-lang.org/cargo/
reference/manifest.html
```

```
[dependencies]
anyhow = "1.0.75"
assert_matches = "1.5.0"
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-smithy-types = { version = "1.0.1" }
aws-smithy-runtime-api = { version = "1.0.1" }
aws-sdk-rds = { version = "1.3.0" }
inquire = "0.6.2"
mockall = "0.11.4"
phf = { version = "0.11.2", features = ["std", "macros"] }
sdk-examples-test-utils = { path = "../../test-utils" }
secrecy = "0.8.0"
tokio = { version = "1.20.1", features = ["full", "test-util"] }
tracing = "0.1.37"
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Exemplos entre serviços para o Aurora usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Aurora com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma API REST de biblioteca de empréstimos
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Criar uma API REST de biblioteca de empréstimos

O exemplo de código abaixo mostra como criar uma biblioteca de empréstimos na qual os clientes possam pegar e devolver livros emprestados usando uma API REST com suporte por um banco de dados do Amazon Aurora.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com a API do Amazon Relational Database Service (Amazon RDS) e o AWS Chalice a fim de criar uma API REST com suporte por um banco de dados do Amazon Aurora. O serviço da Web é uma tecnologia sem servidor e representa uma biblioteca de empréstimos simples, na qual os clientes podem pegar e devolver livros emprestados. Aprenda como:

- Crie e gerencie um cluster de banco de dados Aurora com tecnologia sem servidor.
- Utilize o AWS Secrets Manager para gerenciar credenciais de bancos de dados.
- Implemente uma camada de armazenamento de dados que use o Amazon RDS para mover dados para dentro e fora do banco de dados.
- Use o AWS Chalice para implantar uma API REST com tecnologia sem servidor no Amazon API Gateway e no AWS Lambda.
- Use o pacote Requests para enviar solicitações ao serviço Web.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Aurora
- Lambda
- Secrets Manager

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia os itens de trabalho em um banco de dados do Amazon Aurora Sem Servidor e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar o AWS SDK for .NET para desenvolver uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end .NET RESTful.

- Integre uma aplicação Web do React com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Aurora.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

C++

SDK for C++

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Aurora Sem Servidor.

Para obter o código-fonte completo e instruções sobre como configurar uma API REST C++ que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Java

SDK para Java 2.x

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Para obter o código-fonte completo e instruções sobre como configurar e executar um exemplo que usa a API JDBC, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript (v3) para criar uma aplicação Web que rastreia itens de trabalho em um banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end Node.js Express.

- Integre uma aplicação Web React.js com Serviços da AWS.
- Liste, adicione e atualize itens em uma tabela do Aurora.
- Use o Amazon SES para enviar um relatório por e-mail dos itens de trabalho filtrados.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS

- Serviços de dados do Amazon RDS
- Amazon SES

PHP

SDK para PHP

Mostra como usar o AWS SDK for PHP para construir uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon RDS e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end construído com React.js para interagir com um back-end PHP RESTful.

- Integre uma aplicação Web React.js com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Amazon RDS.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar um serviço REST que rastreia itens de trabalho no banco de dados do Amazon Aurora Sem Servidor e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa o framework da Web do Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST do Flask que se integre a Serviços da AWS.

- Leia, grave e atualize itens de trabalho armazenados em um banco de dados do Aurora Sem Servidor.
- Crie um segredo do AWS Secrets Manager que contenha credenciais do banco de dados e use-o a fim de autenticar chamadas para o banco de dados.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Exemplos de código para Auto Scaling usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EC2 Auto Scaling com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Auto Scaling – Mais informações sobre o Auto Scaling.
- Referência da API do Auto Scaling – Detalhes sobre todas as ações disponíveis do Auto Scaling.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace AutoScalingActions;

using Amazon.AutoScaling;

public class HelloAutoScaling
{
    /// <summary>
    /// Hello Amazon EC2 Auto Scaling. List EC2 Auto Scaling groups.
    /// </summary>
    /// <param name="args"></param>
    /// <returns>Async Task.</returns>
    static async Task Main(string[] args)
    {
        var client = new AmazonAutoScalingClient();

        Console.WriteLine("Welcome to Amazon EC2 Auto Scaling.");
        Console.WriteLine("Let's get a description of your Auto Scaling
 groups.");

        var response = await client.DescribeAutoScalingGroupsAsync();

        response.AutoScalingGroups.ForEach(autoScalingGroup =>
        {

 Console.WriteLine($"{autoScalingGroup.AutoScalingGroupName}\t{autoScalingGroup.Availabil
        });
```

```
        if (response.AutoScalingGroups.Count == 0)
        {
            Console.WriteLine("Sorry, you don't have any Amazon EC2 Auto Scaling
 groups.");
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS autoscaling)

# Set this project's name.
project("hello_autoscaling")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})
```

```
if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                       # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_autoscaling.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem ola_autoscalling.cpp.

```
#include <aws/core/Aws.h>
#include <aws/autoscaling/AutoScalingClient.h>
#include <aws/autoscaling/model/DescribeAutoScalingGroupsRequest.h>
#include <iostream>

/*
 *  A "Hello Autoscaling" starter application which initializes an Amazon EC2
 Auto Scaling client and describes the
 *  Amazon EC2 Auto Scaling groups.
 *
 *  main function
```

```
 *
 *  Usage: 'hello_autoscaling'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::AutoScaling::AutoScalingClient autoscalingClient(clientConfig);

        std::vector<Aws::String> groupNames;
        Aws::String nextToken; // Used for pagination.

        do {

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
                    autoscalingClient.DescribeAutoScalingGroups(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup>
 &autoScalingGroups =
                        outcome.GetResult().GetAutoScalingGroups();
                for (auto &group: autoScalingGroups) {
                    groupNames.push_back(group.GetAutoScalingGroupName());
                }
                nextToken = outcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups.
 "
                          << outcome.GetError().GetMessage()
                          << std::endl;
```

```
                result = 1;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "Found " << groupNames.size() << " AutoScaling groups." <<
 std::endl;
        for (auto &groupName: groupNames) {
            std::cout << "AutoScaling group: " << groupName << std::endl;
        }

    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingGroup;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import java.util.List;

/**
 * Before running this SDK for Java (v2) code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeAutoScalingGroups {
    public static void main(String[] args) throws InterruptedException {
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        describeGroups(autoScalingClient);
    }

    public static void describeGroups(AutoScalingClient autoScalingClient) {
        DescribeAutoScalingGroupsResponse response =
 autoScalingClient.describeAutoScalingGroups();
        List<AutoScalingGroup> groups = response.autoScalingGroups();
        groups.forEach(group -> {
            System.out.println("Group Name: " + group.autoScalingGroupName());
            System.out.println("Group ARN: " + group.autoScalingGroupARN());
        });
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for Java 2.x da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function helloService()
    {
        $autoScalingClient = new AutoScalingClient([
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ]);

        $groups = $autoScalingClient->describeAutoScalingGroups([]);
        var_dump($groups);
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_autoscaling(autoscaling_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon EC2 Auto Scaling
 client and list
    some of the Auto Scaling groups in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param auto-scaling_client: A Boto3 Amazon EC2 Auto Scaling client object.
    """
    print(
```

```
        "Hello, Amazon EC2 Auto Scaling! Let's list up to ten of you Auto Scaling
 groups:"
    )
    response = autoscaling_client.describe_auto_scaling_groups()
    groups = response.get("AutoScalingGroups", [])
    if groups:
        for group in groups:
            print(f"\t{group['AutoScalingGroupName']}:
 {group['AvailabilityZones']}")
    else:
        print("There are no Auto Scaling groups in your account.")


if __name__ == "__main__":
    hello_autoscaling(boto3.client("autoscaling"))
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_groups(client: &Client) -> Result<(), Error> {
    let resp = client.describe_auto_scaling_groups().send().await?;

    println!("Groups:");

    let groups = resp.auto_scaling_groups();

    for group in groups {
        println!(
            "Name:  {}",
            group.auto_scaling_group_name().unwrap_or("Unknown")
```

```
        );
        println!(
            "Arn:   {}",
            group.auto_scaling_group_arn().unwrap_or("unknown"),
        );
        println!("Zones: {:?}", group.availability_zones(),);
        println!();
    }

    println!("Found {} group(s)", groups.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWS SDK for Rust.

Exemplos de código

- Ações para o Auto Scaling usando SDKs da AWS
  - Anexe um grupo de destino ELB a um grupo do Auto Scaling usando um SDK da AWS
  - Criar um grupo do Auto Scaling usando um SDK da AWS
  - Excluir um grupo do Auto Scaling usando um SDK da AWS
  - Desativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS
  - Ativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS
  - Obtenha informações sobre grupos do Auto Scaling usando um SDK da AWS
  - Obtenha informações sobre instâncias do Auto Scaling usando um SDK da AWS
  - Obtenha informações sobre atividades do Auto Scaling usando um SDK da AWS
  - Defina a capacidade desejada de um grupo do Auto Scaling usando um SDK da AWS
  - Encerre uma instância em um grupo do Auto Scaling usando um SDK da AWS
  - Atualizar um grupo do Auto Scaling usando um SDK AWS
- Cenários para Auto Scaling usando SDKs da AWS
  - Criar e gerenciar um serviço resiliente usando um AWS SDK
  - Gerencie grupos e instâncias do Auto Scaling usando um SDK da AWS

Ações para o Auto Scaling usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EC2 Auto Scaling com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para Auto Scaling usando SDKs da AWS.

Exemplos

- Anexe um grupo de destino ELB a um grupo do Auto Scaling usando um SDK da AWS
- Criar um grupo do Auto Scaling usando um SDK da AWS
- Excluir um grupo do Auto Scaling usando um SDK da AWS
- Desativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS
- Ativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS
- Obtenha informações sobre grupos do Auto Scaling usando um SDK da AWS
- Obtenha informações sobre instâncias do Auto Scaling usando um SDK da AWS
- Obtenha informações sobre atividades do Auto Scaling usando um SDK da AWS
- Defina a capacidade desejada de um grupo do Auto Scaling usando um SDK da AWS
- Encerre uma instância em um grupo do Auto Scaling usando um SDK da AWS
- Atualizar um grupo do Auto Scaling usando um SDK AWS

Anexe um grupo de destino ELB a um grupo do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como anexar um grupo destino do ELB a um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName,
 string targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
```

- Para obter detalhes da API, consulte AttachLoadBalancerTargetGroupsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como anexar um grupo de destino a um grupo do Auto Scaling

Este exemplo anexa o grupo de destino especificado ao grupo do Auto Scaling especificado.

```
aws autoscaling attach-load-balancer-target-groups \
    --auto-scaling-group-name my-asg \
    --target-group-arns arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Este comando não produz saída.

Para obter mais informações, consulte Elastic Load Balancing e o Auto Scaling do Amazon EC2 no Guia do usuário do Auto Scaling do Amazon EC2.

- Para obter detalhes da API, consulte AttachLoadBalancerTargetGroupsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new AutoScalingClient({});
await client.send(
  new AttachLoadBalancerTargetGroupsCommand({
    AutoScalingGroupName: NAMES.autoScalingGroupName,
    TargetGroupARNs: [state.targetGroupArn],
  }),
);
```

- Para obter detalhes da API, consulte AttachLoadBalancerTargetGroupsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
```

```
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group
%s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )
```

- Para obter detalhes da API, consulte a AttachLoadBalancerTargetGroupsReferência da API AWSSDK for Python (Boto3).

Criar um grupo do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create a new Amazon EC2 Auto Scaling group.
/// </summary>
/// <param name="groupName">The name to use for the new Auto Scaling
/// group.</param>
/// <param name="launchTemplateName">The name of the Amazon EC2 Auto Scaling
/// launch template to use to create instances in the group.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> CreateAutoScalingGroupAsync(
    string groupName,
    string launchTemplateName,
    string availabilityZone)
{
    var templateSpecification = new LaunchTemplateSpecification
    {
        LaunchTemplateName = launchTemplateName,
```

```
        };

        var zoneList = new List<string>
            {
                availabilityZone,
            };

        var request = new CreateAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            AvailabilityZones = zoneList,
            LaunchTemplate = templateSpecification,
            MaxSize = 6,
            MinSize = 1
        };

        var response = await
_amazonAutoScaling.CreateAutoScalingGroupAsync(request);
        Console.WriteLine($"{groupName} Auto Scaling Group created");
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        Aws::Vector<Aws::String> availabilityGroupZones;
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already
exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Exemplo 1: como criar um grupo do Auto Scaling

O exemplo de `create-auto-scaling-group` a seguir cria um grupo do Auto Scaling em sub-redes de várias zonas de disponibilidade de uma região. As instâncias são executadas com a versão padrão do modelo de execução especificado. Observe que os padrões são usados na maioria das outras configurações, como nas políticas de encerramento e na configuração de verificação de integridade.

```
aws autoscaling create-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-template LaunchTemplateId=lt-1234567890abcde12 \
    --min-size 1 \
    --max-size 5 \
    --vpc-zone-identifier "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
```

Este comando não produz saída.

Para obter mais informações, consulte Grupos do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 2: como anexar o Application Load Balancer, o Network Load Balancer ou o Gateway Load Balancer

Este exemplo especifica o ARN de um grupo de destino para um balanceador de carga compatível com o tráfego esperado. O tipo de verificação de integridade especifica o `ELB`. Desta forma, quando o Elastic Load Balancing reportar uma instância como não íntegra, o grupo do Auto Scaling a substitui. O comando também define um período de carência de `600` segundos para a verificação de integridade. O período de carência ajuda a evitar o encerramento prematuro de instâncias recém-iniciadas.

```
aws autoscaling create-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-template LaunchTemplateId=lt-1234567890abcde12 \
    --target-group-arns arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/943f017f100becff \
    --health-check-type ELB \
    --health-check-grace-period 600 \
    --min-size 1 \
```

```
    --max-size 5 \
    --vpc-zone-identifier "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
```

Este comando não produz saída.

Para obter mais informações, consulte Elastic Load Balancing e o Auto Scaling do Amazon EC2 no Guia do usuário do Auto Scaling do Amazon EC2.

Exemplo 3: como especificar um grupo de posicionamento e usar a versão mais recente do modelo de execução

Este exemplo executa instâncias em um grupo de posicionamento dentro de uma única zona de disponibilidade. Isso pode ser útil para grupos de baixa latência com workloads de HPC. Esse exemplo também especifica o tamanho mínimo e máximo e a capacidade desejada do grupo.

```
aws autoscaling create-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-template LaunchTemplateId=lt-1234567890abcde12,Version='$Latest' \
    --min-size 1 \
    --max-size 5 \
    --desired-capacity 3 \
    --placement-group my-placement-group \
    --vpc-zone-identifier "subnet-6194ea3b"
```

Este comando não produz saída.

Para obter mais informações, consulte Grupos de posicionamento no Guia do usuário para instâncias do Linux do Amazon EC2.

Exemplo 4: como especificar um grupo do Auto Scaling de instância única e usar uma versão específica para iniciar o modelo

Este exemplo cria um grupo do Auto Scaling com capacidade mínima e máxima definida como 1 para impor que uma apenas instância seja executada. O comando também especifica a v1 de um modelo de execução no qual o ID de um ENI existente é especificado. Ao usar um modelo de execução que especifica um ENI existente para eth0, é necessário especificar uma zona de disponibilidade para o grupo do Auto Scaling que corresponda à interface de rede, mas sem especificar um ID de sub-rede na solicitação.

```
aws autoscaling create-auto-scaling-group \
```

```
    --auto-scaling-group-name my-asg-single-instance \
    --launch-template LaunchTemplateName=my-template-for-auto-scaling,Version='1'
 \
    --min-size 1 \
    --max-size 1 \
    --availability-zones us-west-2a
```

Este comando não produz saída.

Para obter mais informações, consulte Grupos do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 5: como especificar uma política de encerramento diferente

Este exemplo cria um grupo do Auto Scaling usando uma configuração de execução e define a política de encerramento para encerrar as instâncias mais antigas primeiro. O comando também aplica uma tag ao grupo e suas instâncias, com uma chave `Role` e valor de `WebServer`.

```
aws autoscaling create-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-configuration-name my-lc \
    --min-size 1 \
    --max-size 5 \
    --termination-policies "OldestInstance" \
    --tags "ResourceId=my-asg,ResourceType=auto-scaling-
group,Key=Role,Value=WebServer,PropagateAtLaunch=true" \
    --vpc-zone-identifier "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
```

Este comando não produz saída.

Para obter mais informações, consulte Trabalhar com políticas de término do Amazon EC2 Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 6: como especificar um gancho do ciclo de vida de lançamento

Este exemplo a seguir cria um grupo do Auto Scaling com um gancho do ciclo de vida que oferece suporte a uma ação personalizada na inicialização da instância.

```
aws autoscaling create-auto-scaling-group \
    --cli-input-json file://~/config.json
```

Conteúdo do arquivo `config.json`:

```
{
    "AutoScalingGroupName": "my-asg",
    "LaunchTemplate": {
        "LaunchTemplateId": "lt-1234567890abcde12"
    },
    "LifecycleHookSpecificationList": [{
        "LifecycleHookName": "my-launch-hook",
        "LifecycleTransition": "autoscaling:EC2_INSTANCE_LAUNCHING",
        "NotificationTargetARN": "arn:aws:sqs:us-west-2:123456789012:my-sqs-
queue",
        "RoleARN": "arn:aws:iam::123456789012:role/my-notification-role",
        "NotificationMetadata": "SQS message metadata",
        "HeartbeatTimeout": 4800,
        "DefaultResult": "ABANDON"
    }],
    "MinSize": 1,
    "MaxSize": 5,
    "VPCZoneIdentifier": "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782",
    "Tags": [{
        "ResourceType": "auto-scaling-group",
        "ResourceId": "my-asg",
        "PropagateAtLaunch": true,
        "Value": "test",
        "Key": "environment"
    }]
}
```

Este comando não produz saída.

Para obter mais informações, consulte Ganchos do ciclo de vida do Amazon EC2 Auto Scaling no Manual do usuário do Amazon EC2 Auto Scaling.

Exemplo 7: como especificar um gancho do ciclo de vida de encerramento

Este exemplo a seguir cria um grupo do Auto Scaling com um gancho do ciclo de vida que oferece suporte a uma ação personalizada no encerramento da instância.

```
aws autoscaling create-auto-scaling-group \
    --cli-input-json file://~/config.json
```

Conteúdo de `config.json`:

```
{
    "AutoScalingGroupName": "my-asg",
    "LaunchTemplate": {
        "LaunchTemplateId": "lt-1234567890abcde12"
    },
    "LifecycleHookSpecificationList": [{
        "LifecycleHookName": "my-termination-hook",
        "LifecycleTransition": "autoscaling:EC2_INSTANCE_TERMINATING",
        "HeartbeatTimeout": 120,
        "DefaultResult": "CONTINUE"
    }],
    "MinSize": 1,
    "MaxSize": 5,
    "TargetGroupARNs": [
        "arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067"
    ],
    "VPCZoneIdentifier": "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
}
```

Este comando não produz saída.

Para obter mais informações, consulte Ganchos do ciclo de vida do Amazon EC2 Auto Scaling no Manual do usuário do Amazon EC2 Auto Scaling.

Exemplo 8: como especificar uma política de encerramento personalizada

Este exemplo cria um grupo do Auto Scaling que especifica uma política de encerramento da função do Lambda personalizada que diz ao Amazon EC2 Auto Scaling quais instâncias podem ser encerradas com segurança em escala.

```
aws autoscaling create-auto-scaling-group \
    --auto-scaling-group-name my-asg-single-instance \
    --launch-template LaunchTemplateName=my-template-for-auto-scaling \
    --min-size 1 \
    --max-size 5 \
    --termination-policies "arn:aws:lambda:us-
west-2:123456789012:function:HelloFunction:prod" \
    --vpc-zone-identifier "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
```

Este comando não produz saída.

Para obter mais informações, consulte Criar uma política de término personalizada com o Lambda no Guia do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte CreateAutoScalingGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import
 software.amazon.awssdk.services.autoscaling.model.CreateAutoScalingGroupRequest;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsRequest;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import
 software.amazon.awssdk.services.autoscaling.model.LaunchTemplateSpecification;
import software.amazon.awssdk.services.autoscaling.waiters.AutoScalingWaiter;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateAutoScalingGroup {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <groupName> <launchTemplateName> <serviceLinkedRoleARN>
<vpcZoneId>

                Where:
                    groupName - The name of the Auto Scaling group.
                    launchTemplateName - The name of the launch template.\s
                    vpcZoneId - A subnet Id for a virtual private cloud (VPC)
where instances in the Auto Scaling group can be created.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        String launchTemplateName = args[1];
        String vpcZoneId = args[2];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createAutoScalingGroup(autoScalingClient, groupName, launchTemplateName,
vpcZoneId);
        autoScalingClient.close();
    }

    public static void createAutoScalingGroup(AutoScalingClient
autoScalingClient,
            String groupName,
            String launchTemplateName,
            String vpcZoneId) {

        try {
            AutoScalingWaiter waiter = autoScalingClient.waiter();
            LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                    .launchTemplateName(launchTemplateName)
                    .build();

            CreateAutoScalingGroupRequest request =
CreateAutoScalingGroupRequest.builder()
```

```
                    .autoScalingGroupName(groupName)
                    .availabilityZones("us-east-1a")
                    .launchTemplate(templateSpecification)
                    .maxSize(1)
                    .minSize(1)
                    .vpcZoneIdentifier(vpcZoneId)
                    .build();

            autoScalingClient.createAutoScalingGroup(request);
            DescribeAutoScalingGroupsRequest groupsRequest =
 DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
 waiter
                    .waitUntilGroupExists(groupsRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Auto Scaling Group created");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createAutoScalingGroup(groupName: String, launchTemplateNameVal:
 String, serviceLinkedRoleARNVal: String, vpcZoneIdVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val request = CreateAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        availabilityZones = listOf("us-east-1a")
        launchTemplate = templateSpecification
        maxSize = 1
        minSize = 1
        vpcZoneIdentifier = vpcZoneIdVal
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
    }

    // This object is required for the waiter call.
    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.createAutoScalingGroup(request)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("$groupName was created!")
    }
}
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function createAutoScalingGroup(
        $autoScalingGroupName,
        $availabilityZones,
        $minSize,
        $maxSize,
        $launchTemplateId
    ) {
        return $this->autoScalingClient->createAutoScalingGroup([
            'AutoScalingGroupName' => $autoScalingGroupName,
            'AvailabilityZones' => $availabilityZones,
            'MinSize' => $minSize,
            'MaxSize' => $maxSize,
            'LaunchTemplate' => [
                'LaunchTemplateId' => $launchTemplateId,
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client
```

```
    def create_group(
        self, group_name, group_zones, launch_template_name, min_size, max_size
    ):
        """
        Creates an Auto Scaling group.

        :param group_name: The name to give to the group.
        :param group_zones: The Availability Zones in which instances can be
created.
        :param launch_template_name: The name of an existing Amazon EC2 launch
template.
                                     The launch template specifies the
configuration of
                                     instances that are created by auto scaling
activities.
        :param min_size: The minimum number of active instances in the group.
        :param max_size: The maximum number of active instances in the group.
        """
        try:
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=group_name,
                AvailabilityZones=group_zones,
                LaunchTemplate={
                    "LaunchTemplateName": launch_template_name,
                    "Version": "$Default",
                },
                MinSize=min_size,
                MaxSize=max_size,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn create_group(client: &Client, name: &str, id: &str) -> Result<(), Error>
 {
    client
        .create_auto_scaling_group()
        .auto_scaling_group_name(name)
        .instance_id(id)
        .min_size(1)
        .max_size(5)
        .send()
        .await?;

    println!("Created AutoScaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupreferência da API AWS SDK for Rust.

Excluir um grupo do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar o tamanho mínimo de um grupo do Auto Scaling para zero, encerrar todas as instâncias no grupo e excluir o grupo.

```
    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await
_amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for
{instanceId}. Waiting...");
                Thread.Sleep(10000);
            }
        }
```

```
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string
groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
```

```
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }
```

```
    /// <summary>
    /// Delete an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAutoScalingGroupAsync(
        string groupName)
    {
        var deleteAutoScalingGroupRequest = new DeleteAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            ForceDelete = true,
        };
```

```
        var response = await
_amazonAutoScaling.DeleteAutoScalingGroupAsync(deleteAutoScalingGroupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully deleted {groupName}");
            return true;
        }

        Console.WriteLine($"Couldn't delete {groupName}.");
        return false;
    }
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

            Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);

            Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
                    autoScalingClient.DeleteAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
```

```
                std::cout << "Auto Scaling group '" << groupName << "' was
 deleted."
                          << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Exemplo 1: como excluir o grupo do Auto Scaling especificado

Este exemplo exclui o grupo do Auto Scaling especificado.

```
aws autoscaling delete-auto-scaling-group \
    --auto-scaling-group-name my-asg
```

Este comando não produz saída.

Para obter mais informações, consulte Excluir infraestrutura do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 2: como forçar a exclusão do grupo do Auto Scaling especificado

Use a opção `--force-delete` para excluir o grupo do Auto Scaling sem precisar esperar que as instâncias do grupo sejam encerradas.

```
aws autoscaling delete-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --force-delete
```

Este comando não produz saída.

Para obter mais informações, consulte Excluir infraestrutura do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte DeleteAutoScalingGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import
 software.amazon.awssdk.services.autoscaling.model.DeleteAutoScalingGroupRequest;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteAutoScalingGroup {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <groupName>

                Where:
                    groupName - The name of the Auto Scaling group.
```

```
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteAutoScalingGroup(autoScalingClient, groupName);
        autoScalingClient.close();
    }

    public static void deleteAutoScalingGroup(AutoScalingClient
 autoScalingClient, String groupName) {
        try {
            DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
 DeleteAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .forceDelete(true)
                    .build();


 autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
            System.out.println("You successfully deleted " + groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSpecificAutoScalingGroup(groupName: String) {
    val deleteAutoScalingGroupRequest = DeleteAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        forceDelete = true
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest)
        println("You successfully deleted $groupName")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function deleteAutoScalingGroup($autoScalingGroupName)
    {
        return $this->autoScalingClient->deleteAutoScalingGroup([
```

```
            'AutoScalingGroupName' => $autoScalingGroupName,
            'ForceDelete' => true,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar o tamanho mínimo de um grupo do Auto Scaling para zero, encerrar todas as instâncias no grupo e excluir o grupo.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
```

```
        :param ami_param: The Systems Manager parameter used to look up the AMI
that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
```

```
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] ==
"ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling
group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
```

```
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn delete_group(client: &Client, name: &str, force: bool) -> Result<(),
 Error> {
    client
        .delete_auto_scaling_group()
        .auto_scaling_group_name(name)
        .set_force_delete(if force { Some(true) } else { None })
        .send()
        .await?;

    println!("Deleted Auto Scaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupreferência da API AWS SDK for Rust.

Desativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS

Os exemplos de código a seguir mostram como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Disable the collection of metric data for an Amazon EC2 Auto Scaling
    /// group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DisableMetricsCollectionAsync(string groupName)
    {
        var request = new DisableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
        };

        var response = await
_amazonAutoScaling.DisableMetricsCollectionAsync(request);
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
                autoScalingClient.DisableMetricsCollection(request);

        if (outcome.IsSuccess()) {
            std::cout << "Metrics collection has been disabled." << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Como desabilitar a coleta de métricas de um grupo do Auto Scaling

Este exemplo desativa a coleta da métrica `GroupDesiredCapacity` do grupo do Auto Scaling especificado.

```
aws autoscaling disable-metrics-collection \
    --auto-scaling-group-name my-asg \
    --metrics GroupDesiredCapacity
```

Este comando não produz saída.

Para obter mais informações, consulte CloudWatch Métricas de monitoramento para seus grupos e instâncias do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte DisableMetricsCollectionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void disableMetricsCollection(AutoScalingClient
autoScalingClient, String groupName) {
       try {
           DisableMetricsCollectionRequest disableMetricsCollectionRequest =
DisableMetricsCollectionRequest.builder()
                   .autoScalingGroupName(groupName)
```

```
                    .metrics("GroupMaxSize")
                    .build();


 autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest);
            System.out.println("The disable metrics collection operation was
 successful");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableMetricsCollection(groupName: String) {
    val disableMetricsCollectionRequest = DisableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->

 autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest)
        println("The disable metrics collection operation was successful")
    }
}
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function disableMetricsCollection($autoScalingGroupName)
    {
        return $this->autoScalingClient->disableMetricsCollection([
            'AutoScalingGroupName' => $autoScalingGroupName,
        ]);
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
```

```
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def disable_metrics(self, group_name):
        """
        Stops CloudWatch metric collection for the Auto Scaling group.

        :param group_name: The name of the group.
        """
        try:
            self.autoscaling_client.disable_metrics_collection(
                AutoScalingGroupName=group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't disable metrics %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        // If this fails it's fine, just means there are extra cloudwatch metrics
events for the scale-down.
```

```
        let _ = self
            .autoscaling
            .disable_metrics_collection()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionreferência da API AWS SDK for Rust.

Ativar a coleta de CloudWatch métricas para um grupo do Auto Scaling usando um SDK AWS

Os exemplos de código a seguir mostram como habilitar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Enable the collection of metric data for an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> EnableMetricsCollectionAsync(string groupName)
    {
        var listMetrics = new List<string>
```

```
            {
                "GroupMaxSize",
            };

        var collectionRequest = new EnableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
            Metrics = listMetrics,
            Granularity = "1Minute",
        };

        var response = await
_amazonAutoScaling.EnableMetricsCollectionAsync(collectionRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        request.AddMetrics("GroupMinSize");
```

```
        request.AddMetrics("GroupMaxSize");
        request.AddMetrics("GroupDesiredCapacity");
        request.AddMetrics("GroupInServiceInstances");
        request.AddMetrics("GroupTotalInstances");
        request.SetGranularity("1Minute");

        Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
                autoScalingClient.EnableMetricsCollection(request);
        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling metrics have been enabled."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como habilitar a coleta de métricas do grupo do Auto Scaling

Este exemplo habilita a coleta de dados do grupo do Auto Scaling especificado.

```
aws autoscaling enable-metrics-collection \
    --auto-scaling-group-name my-asg \
    --granularity "1Minute"
```

Este comando não produz saída.

Para obter mais informações, consulte CloudWatch Métricas de monitoramento para seus grupos e instâncias do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 2: como coletar dados da métrica especificada de um grupo de Auto Scaling

Use a opção `--metrics` para coletar dados de uma métrica específica.

```
aws autoscaling enable-metrics-collection \
    --auto-scaling-group-name my-asg \
    --metrics GroupDesiredCapacity --granularity "1Minute"
```

Este comando não produz saída.

Para obter mais informações, consulte CloudWatch Métricas de monitoramento para seus grupos e instâncias do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte EnableMetricsCollectionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void enableMetricsCollection(AutoScalingClient
autoScalingClient, String groupName) {
       try {
           EnableMetricsCollectionRequest collectionRequest =
EnableMetricsCollectionRequest.builder()
                   .autoScalingGroupName(groupName)
                   .metrics("GroupMaxSize")
                   .granularity("1Minute")
                   .build();

           autoScalingClient.enableMetricsCollection(collectionRequest);
           System.out.println("The enable metrics collection operation was
successful");

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableMetricsCollection(groupName: String?) {
    val collectionRequest = EnableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
        granularity = "1Minute"
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.enableMetricsCollection(collectionRequest)
        println("The enable metrics collection operation was successful")
    }
}
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function enableMetricsCollection($autoScalingGroupName, $granularity)
    {
        return $this->autoScalingClient->enableMetricsCollection([
            'AutoScalingGroupName' => $autoScalingGroupName,
            'Granularity' => $granularity,
        ]);
    }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
```

```
        self.autoscaling_client = autoscaling_client


    def enable_metrics(self, group_name, metrics):
        """
        Enables CloudWatch metric collection for Amazon EC2 Auto Scaling
activities.

        :param group_name: The name of the group to enable.
        :param metrics: A list of metrics to collect.
        """
        try:
            self.autoscaling_client.enable_metrics_collection(
                AutoScalingGroupName=group_name, Metrics=metrics,
Granularity="1Minute"
            )
        except ClientError as err:
            logger.error(
                "Couldn't enable metrics on %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let enable_metrics_collection = autoscaling
```

```
            .enable_metrics_collection()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .granularity("1Minute")
            .set_metrics(Some(vec![
                String::from("GroupMinSize"),
                String::from("GroupMaxSize"),
                String::from("GroupDesiredCapacity"),
                String::from("GroupInServiceInstances"),
                String::from("GroupTotalInstances"),
            ]))
            .send()
            .await;
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionreferência da API AWS SDK for Rust.

Obtenha informações sobre grupos do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como obter informações sobre grupos do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
```

```
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
                    instanceIds.Add(instance.InstanceId);
                });
            }
        });

        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;

        return instanceDetails;
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
Aws::Vector<Aws::String> groupNames;
groupNames.push_back(groupName);
request.SetAutoScalingGroupNames(groupNames);

Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
        client.DescribeAutoScalingGroups(request);

if (outcome.IsSuccess()) {
    autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
}
else {
    std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
              << outcome.GetError().GetMessage()
              << std::endl;
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como descrever o grupo do Auto Scaling especificado

Este exemplo descreve o grupo do Auto Scaling especificado.

```
aws autoscaling describe-auto-scaling-groups \
    --auto-scaling-group-name my-asg
```

Saída:

```
{
    "AutoScalingGroups": [
        {
            "AutoScalingGroupName": "my-asg",
            "AutoScalingGroupARN": "arn:aws:autoscaling:us-
west-2:123456789012:autoScalingGroup:930d940e-891e-4781-
a11a-7b0acd480f03:autoScalingGroupName/my-asg",
            "LaunchTemplate": {
                "LaunchTemplateName": "my-launch-template",
                "Version": "1",
                "LaunchTemplateId": "lt-1234567890abcde12"
            },
            "MinSize": 0,
            "MaxSize": 1,
            "DesiredCapacity": 1,
            "DefaultCooldown": 300,
            "AvailabilityZones": [
                "us-west-2a",
                "us-west-2b",
                "us-west-2c"
            ],
            "LoadBalancerNames": [],
            "TargetGroupARNs": [],
            "HealthCheckType": "EC2",
            "HealthCheckGracePeriod": 0,
            "Instances": [
                {
                    "InstanceId": "i-06905f55584de02da",
                    "InstanceType": "t2.micro",
                    "AvailabilityZone": "us-west-2a",
```

```
                    "HealthStatus": "Healthy",
                    "LifecycleState": "InService",
                    "ProtectedFromScaleIn": false,
                    "LaunchTemplate": {
                        "LaunchTemplateName": "my-launch-template",
                        "Version": "1",
                        "LaunchTemplateId": "lt-1234567890abcde12"
                    }
                }
            ],
            "CreatedTime": "2020-10-28T02:39:22.152Z",
            "VPCZoneIdentifier": "subnet-5ea0c127,subnet-6194ea3b,subnet-
c934b782",
            "SuspendedProcesses": [],
            "EnabledMetrics": [],
            "Tags": [],
            "TerminationPolicies": [
                "Default"
            ],
            "NewInstancesProtectedFromScaleIn": false,
            "ServiceLinkedRoleARN":"arn"
        }
    ]
}
```

Exemplo 2: como descrever os primeiros 100 grupos do Auto Scaling especificados

Este exemplo descreve os grupos do Auto Scaling especificados. Ele permite especificar até cem nomes de grupos.

```
aws autoscaling describe-auto-scaling-groups \
    --max-items 100 \
    --auto-scaling-group-name "group1" "group2" "group3" "group4"
```

Consulte um exemplo de saída no exemplo 1.

Exemplo 3: como descrever um grupo do Auto Scaling na região especificada

Este exemplo descreve até 75 grupos do Auto Scaling na região especificada.

```
aws autoscaling describe-auto-scaling-groups \
    --max-items 75 \
    --region us-east-1
```

Consulte um exemplo de saída no exemplo 1.

Exemplo 4: como descrever o número especificado do grupo do Auto Scaling

Use a opção `--max-items` para retornar um número específico de grupos do Auto Scaling.

```
aws autoscaling describe-auto-scaling-groups \
    --max-items 1
```

Consulte um exemplo de saída no exemplo 1.

Se a saída incluir um campo `NextToken`, há mais grupos. Para obter os grupos adicionais, use o valor desse campo com a opção `--starting-token` em uma chamada subsequente da seguinte maneira.

```
aws autoscaling describe-auto-scaling-groups --starting-token Z3M3LMPEXAMPLE
```

Consulte um exemplo de saída no exemplo 1.

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingGroup;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsRequest;
import software.amazon.awssdk.services.autoscaling.model.Instance;
```

```
import java.util.List;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeAutoScalingInstances {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <groupName>

                Where:
                    groupName - The name of the Auto Scaling group.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String instanceId = getAutoScaling(autoScalingClient, groupName);
        System.out.println(instanceId);
        autoScalingClient.close();
    }

    public static String getAutoScaling(AutoScalingClient autoScalingClient,
 String groupName) {
        try {
            String instanceId = "";
            DescribeAutoScalingGroupsRequest scalingGroupsRequest =
 DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
```

```
                    .build();

            DescribeAutoScalingGroupsResponse response = autoScalingClient
                    .describeAutoScalingGroups(scalingGroupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("The group name is " +
 group.autoScalingGroupName());
                System.out.println("The group ARN is " +
 group.autoScalingGroupARN());

                List<Instance> instances = group.instances();
                for (Instance instance : instances) {
                    instanceId = instance.instanceId();
                }
            }
            return instanceId;
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAutoScalingGroups(groupName: String) {
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
```

```
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")
            group.instances?.forEach { instance ->
                println("The instance id is ${instance.instanceId}")
                println("The lifecycle state is " + instance.lifecycleState)
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function describeAutoScalingGroups($autoScalingGroupNames)
    {
        return $this->autoScalingClient->describeAutoScalingGroups([
            'AutoScalingGroupNames' => $autoScalingGroupNames
        ]);
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def describe_group(self, group_name):
        """
        Gets information about an Auto Scaling group.

        :param group_name: The name of the group to look up.
        :return: Information about the group, if found.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[group_name]
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            groups = response.get("AutoScalingGroups", [])
            return groups[0] if len(groups) > 0 else None
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_groups(client: &Client) -> Result<(), Error> {
    let resp = client.describe_auto_scaling_groups().send().await?;

    println!("Groups:");

    let groups = resp.auto_scaling_groups();

    for group in groups {
        println!(
            "Name:  {}",
            group.auto_scaling_group_name().unwrap_or("Unknown")
        );
        println!(
            "Arn:   {}",
            group.auto_scaling_group_arn().unwrap_or("unknown"),
        );
        println!("Zones: {:?}", group.availability_zones(),);
        println!();
    }

    println!("Found {} group(s)", groups.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWS SDK for Rust.

Obtenha informações sobre instâncias do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como obter informações sobre instâncias do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
```

```
                    instanceIds.Add(instance.InstanceId);
                });
            }
        });

        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
_amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;

        return instanceDetails;
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);
```

```
        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const
 Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
 &instancesDetails =
                   outcome.GetResult().GetAutoScalingInstances();

        }
        else {
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como descrever uma ou mais instâncias

Este exemplo descreve a instância especificada.

```
aws autoscaling describe-auto-scaling-instances \
    --instance-ids i-06905f55584de02da
```

Saída:

```
{
    "AutoScalingInstances": [
        {
            "InstanceId": "i-06905f55584de02da",
            "InstanceType": "t2.micro",
            "AutoScalingGroupName": "my-asg",
            "AvailabilityZone": "us-west-2b",
```

```
            "LifecycleState": "InService",
            "HealthStatus": "HEALTHY",
            "ProtectedFromScaleIn": false,
            "LaunchTemplate": {
                "LaunchTemplateId": "lt-1234567890abcde12",
                "LaunchTemplateName": "my-launch-template",
                "Version": "1"
            }
        }
    ]
}
```

Exemplo 2: como descrever uma ou mais instâncias

Este exemplo usa a opção `--max-items` para especificar quantas instâncias devem ser retornadas pela chamada.

```
aws autoscaling describe-auto-scaling-instances --max-items 1
```

Se a saída incluir um campo `NextToken`, há mais instâncias. Para obter as instâncias adicionais, use o valor desse campo com a opção `--starting-token` em uma chamada subsequente da seguinte maneira.

```
aws autoscaling describe-auto-scaling-instances --starting-token Z3M3LMPEXAMPLE
```

Saída:

```
{
    "AutoScalingInstances": [
        {
            "InstanceId": "i-06905f55584de02da",
            "InstanceType": "t2.micro",
            "AutoScalingGroupName": "my-asg",
            "AvailabilityZone": "us-west-2b",
            "LifecycleState": "InService",
            "HealthStatus": "HEALTHY",
            "ProtectedFromScaleIn": false,
            "LaunchTemplate": {
                "LaunchTemplateId": "lt-1234567890abcde12",
                "LaunchTemplateName": "my-launch-template",
                "Version": "1"
            }
```

```
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeAutoScalingInstance(AutoScalingClient
autoScalingClient, String id) {
       try {
           DescribeAutoScalingInstancesRequest
describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest
                   .builder()
                   .instanceIds(id)
                   .build();

           DescribeAutoScalingInstancesResponse response = autoScalingClient

.describeAutoScalingInstances(describeAutoScalingInstancesRequest);
           List<AutoScalingInstanceDetails> instances =
response.autoScalingInstances();
           for (AutoScalingInstanceDetails instance : instances) {
               System.out.println("The instance lifecycle state is: " +
instance.lifecycleState());
           }

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAutoScalingInstance(id: String) {
    val describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest
 {
        instanceIds = listOf(id)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingInstances(describeAutoScalingInstancesRequest)
        response.autoScalingInstances?.forEach { group ->
            println("The instance lifecycle state is: ${group.lifecycleState}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function describeAutoScalingInstances($instanceIds)
    {
        return $this->autoScalingClient->describeAutoScalingInstances([
            'InstanceIds' => $instanceIds
        ]);
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client
```

```
    def describe_instances(self, instance_ids):
        """
        Gets information about instances.

        :param instance_ids: A list of instance IDs to look up.
        :return: Information about instances, or an empty list if none are found.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_instances(
                InstanceIds=instance_ids
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe instances %s. Here's why: %s: %s",
                instance_ids,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["AutoScalingInstances"]
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn list_instances(&self) -> Result<Vec<String>, ScenarioError> {
```

```
        // The direct way to list instances is by using
 DescribeAutoScalingGroup's instances property. However, this returns a
 Vec<Instance>, as opposed to a Vec<AutoScalingInstanceDetails>.
        // Ok(self.get_group().await?.instances.unwrap_or_default().map(|
i| i.instance_id.clone().unwrap_or_default()).filter(|id| !
id.is_empty()).collect())

        // Alternatively, and for the sake of example,
 DescribeAutoScalingInstances returns a list that can be filtered by the client.
        self.autoscaling
            .describe_auto_scaling_instances()
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
            .map(|items| {
                items
                    .into_iter()
                    .filter(|i| {
                        i.auto_scaling_group_name.as_deref()
                            == Some(self.auto_scaling_group_name.as_str())
                    })
                    .map(|i| i.instance_id.unwrap_or_default())
                    .filter(|id| !id.is_empty())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Failed to get list of auto scaling
 instances", &err))
    }
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesreferência da API AWS SDK for Rust.

Obtenha informações sobre atividades do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como obter informações sobre atividades do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a list of the Amazon EC2 Auto Scaling activities for an
    /// Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling activities.</returns>
    public async Task<List<Amazon.AutoScaling.Model.Activity>>
 DescribeScalingActivitiesAsync(
        string groupName)
    {
        var scalingActivitiesRequest = new DescribeScalingActivitiesRequest
        {
            AutoScalingGroupName = groupName,
            MaxRecords = 10,
        };

        var response = await
 _amazonAutoScaling.DescribeScalingActivitiesAsync(scalingActivitiesRequest);
        return response.Activities;
    }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                autoScalingClient.DescribeScalingActivities(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                    outcome.GetResult().GetActivities();
            std::cout << "Found " << activities.size() << " activities." <<
std::endl;
            std::cout << "Activities are ordered with the most recent first."
                      << std::endl;
            for (const Aws::AutoScaling::Model::Activity &activity: activities) {
                std::cout << activity.GetDescription() << std::endl;
                std::cout << activity.GetDetails() << std::endl;
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Exemplo 1: como descrever as ações de escalabilidade do grupo especificado

Este exemplo descreve as ações de escalabilidade do grupo do Auto Scaling especificado.

```
aws autoscaling describe-scaling-activities \
    --auto-scaling-group-name my-asg
```

Saída:

```
{
    "Activities": [
        {
            "ActivityId": "f9f2d65b-f1f2-43e7-b46d-d86756459699",
            "Description": "Launching a new EC2 instance: i-0d44425630326060f",
            "AutoScalingGroupName": "my-asg",
            "Cause": "At 2020-10-30T19:35:51Z a user request update of
 AutoScalingGroup constraints to min: 0, max: 16, desired: 16 changing the
 desired capacity from 0 to 16.  At 2020-10-30T19:36:07Z an instance was started
 in response to a difference between desired and actual capacity, increasing the
 capacity from 0 to 16.",
            "StartTime": "2020-10-30T19:36:09.766Z",
            "EndTime": "2020-10-30T19:36:41Z",
            "StatusCode": "Successful",
            "Progress": 100,
            "Details": "{\"Subnet ID\":\"subnet-5ea0c127\",\"Availability Zone\":
\"us-west-2b\"}"
        }
    ]
}
```

Para mais informações, consulte Verificar uma ação de escalabilidade para um grupo do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 2: como descrever as ações de escalabilidade de um grupo excluído

Adicione a opção `--include-deleted-groups` para descrever as ações de escalabilidade depois que o grupo do Auto Scaling for excluído.

```
aws autoscaling describe-scaling-activities \
    --auto-scaling-group-name my-asg \
    --include-deleted-groups
```

Saída:

```
{
    "Activities": [
        {
            "ActivityId": "e1f5de0e-f93e-1417-34ac-092a76fba220",
            "Description": "Launching a new EC2 instance.  Status Reason: Your
 Spot request price of 0.001 is lower than the minimum required Spot request
 fulfillment price of 0.0031. Launching EC2 instance failed.",
            "AutoScalingGroupName": "my-asg",
            "Cause": "At 2021-01-13T20:47:24Z a user request update of
 AutoScalingGroup constraints to min: 1, max: 5, desired: 3 changing the desired
 capacity from 0 to 3.  At 2021-01-13T20:47:27Z an instance was started in
 response to a difference between desired and actual capacity, increasing the
 capacity from 0 to 3.",
            "StartTime": "2021-01-13T20:47:30.094Z",
            "EndTime": "2021-01-13T20:47:30Z",
            "StatusCode": "Failed",
            "StatusMessage": "Your Spot request price of 0.001 is lower than
 the minimum required Spot request fulfillment price of 0.0031. Launching EC2
 instance failed.",
            "Progress": 100,
            "Details": "{\"Subnet ID\":\"subnet-5ea0c127\",\"Availability Zone\":
\"us-west-2b\"}",
            "AutoScalingGroupState": "Deleted",
            "AutoScalingGroupARN": "arn:aws:autoscaling:us-
west-2:123456789012:autoScalingGroup:283179a2-
f3ce-423d-93f6-66bb518232f7:autoScalingGroupName/my-asg"
        }
    ]
}
```

Para obter mais informações, consulte Solucionar problemas do Amazon EC2 Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 3: como descrever um número especificado de ações de escalabilidade

Use a opção `--max-items` para retornar um número específico de ações.

```
aws autoscaling describe-scaling-activities \
    --max-items 1
```

Saída:

```
{
    "Activities": [
        {
            "ActivityId": "f9f2d65b-f1f2-43e7-b46d-d86756459699",
            "Description": "Launching a new EC2 instance: i-0d44425630326060f",
            "AutoScalingGroupName": "my-asg",
            "Cause": "At 2020-10-30T19:35:51Z a user request update of
 AutoScalingGroup constraints to min: 0, max: 16, desired: 16 changing the
 desired capacity from 0 to 16.  At 2020-10-30T19:36:07Z an instance was started
 in response to a difference between desired and actual capacity, increasing the
 capacity from 0 to 16.",
            "StartTime": "2020-10-30T19:36:09.766Z",
            "EndTime": "2020-10-30T19:36:41Z",
            "StatusCode": "Successful",
            "Progress": 100,
            "Details": "{\"Subnet ID\":\"subnet-5ea0c127\",\"Availability Zone\":
\"us-west-2b\"}"
        }
    ]
}
```

Se a saída incluir um campo `NextToken`, há mais ações. Para obter as ações adicionais, use o valor desse campo com a opção `--starting-token` em uma chamada subsequente da seguinte maneira.

```
aws autoscaling describe-scaling-activities \
    --starting-token Z3M3LMPEXAMPLE
```

Para mais informações, consulte Verificar uma ação de escalabilidade para um grupo do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte DescribeScalingActivitiesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeScalingActivities(AutoScalingClient
autoScalingClient, String groupName) {
       try {
           DescribeScalingActivitiesRequest scalingActivitiesRequest =
DescribeScalingActivitiesRequest.builder()
                   .autoScalingGroupName(groupName)
                   .maxRecords(10)
                   .build();

           DescribeScalingActivitiesResponse response = autoScalingClient
                   .describeScalingActivities(scalingActivitiesRequest);
           List<Activity> activities = response.activities();
           for (Activity activity : activities) {
               System.out.println("The activity Id is " +
activity.activityId());
               System.out.println("The activity details are " +
activity.details());
           }

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAutoScalingGroups(groupName: String) {
    val groupsReques = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
        maxRecords = 10
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response = autoScalingClient.describeAutoScalingGroups(groupsReques)
        response.autoScalingGroups?.forEach { group ->
            println("The service to use for the health checks:
 ${group.healthCheckType}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function describeScalingActivities($autoScalingGroupName)
```

```
    {
        return $this->autoScalingClient->describeScalingActivities([
            'AutoScalingGroupName' => $autoScalingGroupName,
        ]);
    }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def describe_scaling_activities(self, group_name):
        """
        Gets information about scaling activities for the group. Scaling
 activities
        are things like instances stopping or starting in response to user
 requests
        or capacity changes.

        :param group_name: The name of the group to look up.
        :return: The list of scaling activities for the group, ordered with the
 most
```

```
                recent activity first.
        """
        try:
            response = self.autoscaling_client.describe_scaling_activities(
                AutoScalingGroupName=group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe scaling activities %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Activities"]
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn describe_scenario(&self) -> AutoScalingScenarioDescription {
        let group = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await
            .map(|s| {
                s.auto_scaling_groups()
```

```
                    .iter()
                    .map(|s| {
                        format!(
                            "{}: {}",
                            s.auto_scaling_group_name().unwrap_or("Unknown"),
                            s.status().unwrap_or("Unknown")
                        )
                    })
                    .collect::<Vec<String>>()
            })
            .map_err(|e| {
                ScenarioError::new("Failed to describe auto scaling groups for
scenario", &e)
            });

        let instances = self
            .list_instances()
            .await
            .map_err(|e| anyhow!("There was an error listing instances: {e}",));

        // 10. DescribeScalingActivities: list the scaling activities that have
occurred for the group so far.
        //   Bonus: use CloudWatch API to get and show some metrics collected for
the group.
        //   CW.ListMetrics with Namespace='AWS/AutoScaling' and
Dimensions=[{'Name': 'AutoScalingGroupName', 'Value': }]
        //   CW.GetMetricStatistics with Statistics='Sum'. Start and End times
must be in UTC!
        let activities = self
            .autoscaling
            .describe_scaling_activities()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .into_paginator()
            .items()
            .send()
            .collect::<Result<Vec<_>, _>>()
            .await
            .map_err(|e| {
                anyhow!(
                    "There was an error retrieving scaling activities: {}",
                    DisplayErrorContext(&e)
                )
            });
```

```
        AutoScalingScenarioDescription {
            group,
            instances,
            activities,
        }
    }
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesreferência da API AWS SDK for Rust.

Defina a capacidade desejada de um grupo do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como definir a capacidade desejada de um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Set the desired capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="desiredCapacity">The desired capacity for the Auto
    /// Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SetDesiredCapacityAsync(
        string groupName,
```

```
        int desiredCapacity)
    {
        var capacityRequest = new SetDesiredCapacityRequest
        {
            AutoScalingGroupName = groupName,
            DesiredCapacity = desiredCapacity,
        };

        var response = await
_amazonAutoScaling.SetDesiredCapacityAsync(capacityRequest);
        Console.WriteLine($"You have set the DesiredCapacity to
{desiredCapacity}.");

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetDesiredCapacity(2);
```

```
        Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
                autoScalingClient.SetDesiredCapacity(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como definir a capacidade desejada para um grupo do Auto Scaling

Este exemplo define a capacidade desejada para o grupo do Auto Scaling especificado.

```
aws autoscaling set-desired-capacity \
    --auto-scaling-group-name my-asg \
    --desired-capacity 2 \
    --honor-cooldown
```

Esse comando retornará à solicitação, se houver êxito.

- Para obter detalhes da API, consulte SetDesiredCapacityem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void setDesiredCapacity(AutoScalingClient autoScalingClient,
 String groupName) {
        try {
            SetDesiredCapacityRequest capacityRequest =
 SetDesiredCapacityRequest.builder()
                    .autoScalingGroupName(groupName)
                    .desiredCapacity(2)
                    .build();

            autoScalingClient.setDesiredCapacity(capacityRequest);
            System.out.println("You have set the DesiredCapacity to 2");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setDesiredCapacity(groupName: String) {
    val capacityRequest = SetDesiredCapacityRequest {
        autoScalingGroupName = groupName
        desiredCapacity = 2
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.setDesiredCapacity(capacityRequest)
        println("You set the DesiredCapacity to 2")
```

```
    }
}
```

- Para obter detalhes da API, consulte a SetDesiredCapacityreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function setDesiredCapacity($autoScalingGroupName, $desiredCapacity)
    {
        return $this->autoScalingClient->setDesiredCapacity([
            'AutoScalingGroupName' => $autoScalingGroupName,
            'DesiredCapacity' => $desiredCapacity,
        ]);
    }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def set_desired_capacity(self, group_name, capacity):
        """
        Sets the desired capacity of the group. Amazon EC2 Auto Scaling tries to
 keep the
        number of running instances equal to the desired capacity.

        :param group_name: The name of the group to update.
        :param capacity: The desired number of running instances.
        """
        try:
            self.autoscaling_client.set_desired_capacity(
                AutoScalingGroupName=group_name,
                DesiredCapacity=capacity,
                HonorCooldown=False,
            )
        except ClientError as err:
            logger.error(
                "Couldn't set desired capacity %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a SetDesiredCapacityReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   pub async fn scale_desired_capacity(&self, capacity: i32) -> Result<(),
ScenarioError> {
       // 7. SetDesiredCapacity: set desired capacity to 2.
       //   Wait for a second instance to launch.
       let update_group = self
           .autoscaling
           .set_desired_capacity()
           .auto_scaling_group_name(self.auto_scaling_group_name.clone())
           .desired_capacity(capacity)
           .send()
           .await;
       if let Err(err) = update_group {
           return Err(ScenarioError::new(
               format!("Failed to update group to desired capacity
({capacity}))").as_str(),
               &err,
           ));
       }
       Ok(())
   }
```

- Para obter detalhes da API, consulte a SetDesiredCapacityreferência da API AWS SDK for Rust.

Encerre uma instância em um grupo do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como encerrar uma instância em um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Terminate all instances in the Auto Scaling group in preparation for
    /// deleting the group.
    /// </summary>
    /// <param name="instanceId">The instance Id of the instance to terminate.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> TerminateInstanceInAutoScalingGroupAsync(
        string instanceId)
    {
        var request = new TerminateInstanceInAutoScalingGroupRequest
        {
            InstanceId = instanceId,
            ShouldDecrementDesiredCapacity = false,
        };

        var response = await
 _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You have terminated the instance: {instanceId}");
            return true;
        }
```

```
        Console.WriteLine($"Could not terminate {instanceId}");
        return false;
    }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest
request;
        request.SetInstanceId(instanceIDs[instanceNumber - 1]);
        request.SetShouldDecrementDesiredCapacity(false);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome
outcome =
                autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Waiting for EC2 instance with ID '"
                      << instanceIDs[instanceNumber - 1] << "' to terminate..."
                      << std::endl;
        }
        else {
```

```
            std::cerr << "Error with
 AutoScaling::TerminateInstanceInAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como encerrar uma instância em um grupo do Auto Scaling

Este exemplo encerra a instância especificada do grupo do Auto Scaling especificado sem atualizar o tamanho do grupo. O Amazon EC2 Auto Scaling executa uma instância de substituição após o encerramento da instância especificada.

```
aws autoscaling terminate-instance-in-auto-scaling-group \
    --instance-id i-061c63c5eb45f0416 \
    --no-should-decrement-desired-capacity
```

Saída:

```
{
    "Activities": [
        {
            "ActivityId": "8c35d601-793c-400c-fcd0-f64a27530df7",
            "AutoScalingGroupName": "my-asg",
            "Description": "Terminating EC2 instance: i-061c63c5eb45f0416",
            "Cause": "",
            "StartTime": "2020-10-31T20:34:25.680Z",
            "StatusCode": "InProgress",
            "Progress": 0,
            "Details": "{\"Subnet ID\":\"subnet-6194ea3b\",\"Availability Zone\":
\"us-west-2c\"}"
        }
    ]
```

```
}
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void terminateInstanceInAutoScalingGroup(AutoScalingClient
autoScalingClient, String instanceId) {
       try {
           TerminateInstanceInAutoScalingGroupRequest request =
TerminateInstanceInAutoScalingGroupRequest.builder()
                   .instanceId(instanceId)
                   .shouldDecrementDesiredCapacity(false)
                   .build();

           autoScalingClient.terminateInstanceInAutoScalingGroup(request);
           System.out.println("You have terminated instance " + instanceId);

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun terminateInstanceInAutoScalingGroup(instanceIdVal: String) {
    val request = TerminateInstanceInAutoScalingGroupRequest {
        instanceId = instanceIdVal
        shouldDecrementDesiredCapacity = false
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.terminateInstanceInAutoScalingGroup(request)
        println("You have terminated instance $instanceIdVal")
    }
}
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function terminateInstanceInAutoScalingGroup(
        $instanceId,
        $shouldDecrementDesiredCapacity = true,
        $attempts = 0
```

```
    ) {
        try {
            return $this->autoScalingClient-
>terminateInstanceInAutoScalingGroup([
                'InstanceId' => $instanceId,
                'ShouldDecrementDesiredCapacity' =>
 $shouldDecrementDesiredCapacity,
            ]);
        } catch (AutoScalingException $exception) {
            if ($exception->getAwsErrorCode() == "ScalingActivityInProgress" &&
 $attempts < 5) {
                error_log("Cannot terminate an instance while it is still
 pending. Waiting then trying again.");
                sleep(5 * (1 + $attempts));
                return $this->terminateInstanceInAutoScalingGroup(
                    $instanceId,
                    $shouldDecrementDesiredCapacity,
                    ++$attempts
                );
            } else {
                throw $exception;
            }
        }
    }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""
```

```
    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def terminate_instance(self, instance_id, decrease_capacity):
        """
        Stops an instance.

        :param instance_id: The ID of the instance to stop.
        :param decrease_capacity: Specifies whether to decrease the desired
capacity
                                  of the group. When passing True for this
parameter,
                                  you can stop an instance without having a
replacement
                                  instance start when the desired capacity
threshold is
                                  crossed.
        :return: The scaling activity that occurs in response to this action.
        """
        try:
            response =
self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id,
ShouldDecrementDesiredCapacity=decrease_capacity
            )
        except ClientError as err:
            logger.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Activity"]
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn terminate_some_instance(&self) -> Result<(), ScenarioError> {
    // Retrieve a list of instances in the auto scaling group.
    let auto_scaling_group = self.get_group().await?;
    let instances = auto_scaling_group.instances();
    // Or use other logic to find an instance to terminate.
    let instance = instances.first();
    if let Some(instance) = instance {
        let instance_id = if let Some(instance_id) = instance.instance_id() {
            instance_id
        } else {
            return Err(ScenarioError::with("Missing instance id"));
        };
        let termination = self
            .ec2
            .terminate_instances()
            .instance_ids(instance_id)
            .send()
            .await;
        if let Err(err) = termination {
            Err(ScenarioError::new(
                "There was a problem terminating an instance",
                &err,
            ))
        } else {
            Ok(())
        }
    } else {
        Err(ScenarioError::with("There was no instance to terminate"))
```

```
        }
    }

    async fn get_group(&self) -> Result<AutoScalingGroup, ScenarioError> {
        let describe_auto_scaling_groups = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await;

        if let Err(err) = describe_auto_scaling_groups {
            return Err(ScenarioError::new(
                format!(
                    "Failed to get status of autoscaling group {}",
                    self.auto_scaling_group_name.clone()
                )
                .as_str(),
                &err,
            ));
        }

        let describe_auto_scaling_groups_output =
describe_auto_scaling_groups.unwrap();
        let auto_scaling_groups =
describe_auto_scaling_groups_output.auto_scaling_groups();
        let auto_scaling_group = auto_scaling_groups.first();

        if auto_scaling_group.is_none() {
            return Err(ScenarioError::with(format!(
                "Could not find autoscaling group {}",
                self.auto_scaling_group_name.clone()
            )));
        }

        Ok(auto_scaling_group.unwrap().clone())
    }
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupreferência da API AWS SDK for Rust.

Atualizar um grupo do Auto Scaling usando um SDK AWS

Os exemplos de código a seguir mostram como atualizar a configuração para um grupo do Auto Scaling.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Gerenciar grupos e instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <param name="maxSize">The maximum number of instances that can be
    /// created for the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        int maxSize)
    {
        var templateSpecification = new LaunchTemplateSpecification
        {
            LaunchTemplateName = launchTemplateName,
        };

        var groupRequest = new UpdateAutoScalingGroupRequest
```

```
        {
            MaxSize = maxSize,
            AutoScalingGroupName = groupName,
            LaunchTemplate = templateSpecification,
        };

        var response = await
_amazonAutoScaling.UpdateAutoScalingGroupAsync(groupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully updated the Auto Scaling group
{groupName}.");
            return true;
        }
        else
        {
            return false;
        }
    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);
```

```
        Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetMaxSize(3);

        Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                autoScalingClient.UpdateAutoScalingGroup(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Exemplo 1: como atualizar os limites de tamanho de um grupo do Auto Scaling

Este exemplo atualiza o grupo do Auto Scaling especificado com um tamanho mínimo de 2 e máximo de 10.

```
aws autoscaling update-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --min-size 2 \
    --max-size 10
```

Este comando não produz saída.

Para obter mais informações, consulte Definir limites de escalabilidade para seu grupo do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 2: como adicionar verificações de integridade do Elastic Load Balancing e especificar quais zonas de disponibilidade e sub-redes usar

Este exemplo atualiza o grupo do Auto Scaling especificado para adicionar verificações de integridade do Elastic Load Balancing. Esse comando também atualiza o valor de `--vpc-zone-identifier` com uma lista de IDs de sub-rede em várias zonas de disponibilidade.

```
aws autoscaling update-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --health-check-type ELB \
    --health-check-grace-period 600 \
    --vpc-zone-identifier "subnet-5ea0c127,subnet-6194ea3b,subnet-c934b782"
```

Este comando não produz saída.

Para obter mais informações, consulte Elastic Load Balancing e o Auto Scaling do Amazon EC2 no Guia do usuário do Auto Scaling do Amazon EC2.

Exemplo 3: como atualizar o grupo de posicionamento e a política de encerramento

Este exemplo atualiza o grupo de posicionamento e a política de encerramento que devem ser usados.

```
aws autoscaling update-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --placement-group my-placement-group \
    --termination-policies "OldestInstance"
```

Este comando não produz saída.

Para obter mais informações, consulte Grupos do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling.

Exemplo 4: como usar a versão mais recente do modelo de execução

Este exemplo atualiza o grupo do Auto Scaling especificado para que use a versão mais recente do modelo de execução especificado.

```
aws autoscaling update-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-template LaunchTemplateId=lt-1234567890abcde12,Version='$Latest'
```

Este comando não produz saída.

Para obter mais informações, consulte Modelos de execução no Manual do usuário do Amazon EC2 Auto Scaling.

Exemplo 5: como usar uma versão específica do modelo de execução

Este exemplo atualiza o grupo do Auto Scaling especificado para que use uma versão específica do modelo de execução em vez da versão mais recente ou padrão.

```
aws autoscaling update-auto-scaling-group \
    --auto-scaling-group-name my-asg \
    --launch-template LaunchTemplateName=my-template-for-auto-scaling,Version='2'
```

Este comando não produz saída.

Para obter mais informações, consulte Modelos de execução no Manual do usuário do Amazon EC2 Auto Scaling.

Exemplo 6: como definir uma política de instâncias mistas e habilitar o rebalanceamento de capacidade

Este exemplo atualiza o grupo do Auto Scaling especificado para que use uma política de instâncias mistas e permita o rebalanceamento de capacidade. Essa estrutura permite especificar grupos com capacidades spot e sob demanda e usar modelos de execução diferentes para arquiteturas diferentes.

```
aws autoscaling update-auto-scaling-group \
    --cli-input-json file://~/config.json
```

Conteúdo de `config.json`:

```
{
    "AutoScalingGroupName": "my-asg",
    "CapacityRebalance": true,
    "MixedInstancesPolicy": {
        "LaunchTemplate": {
            "LaunchTemplateSpecification": {
                "LaunchTemplateName": "my-launch-template-for-x86",
                "Version": "$Latest"
            },
            "Overrides": [
```

```
                {
                    "InstanceType": "c6g.large",
                    "LaunchTemplateSpecification": {
                        "LaunchTemplateName": "my-launch-template-for-arm",
                        "Version": "$Latest"
                    }
                },
                {
                    "InstanceType": "c5.large"
                },
                {
                    "InstanceType": "c5a.large"
                }
            ]
        },
        "InstancesDistribution": {
            "OnDemandPercentageAboveBaseCapacity": 50,
            "SpotAllocationStrategy": "capacity-optimized"
        }
    }
}
```

Este comando não produz saída.

Para obter mais informações, consulte Grupos de Auto Scaling com vários tipos de instância e opções de compra no Manual do usuário do Amazon EC2 Auto Scaling.

- Para obter detalhes da API, consulte UpdateAutoScalingGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void updateAutoScalingGroup(AutoScalingClient
 autoScalingClient, String groupName,
```

```
            String launchTemplateName) {
        try {
            AutoScalingWaiter waiter = autoScalingClient.waiter();
            LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                    .launchTemplateName(launchTemplateName)
                    .build();

            UpdateAutoScalingGroupRequest groupRequest =
UpdateAutoScalingGroupRequest.builder()
                    .maxSize(3)
                    .autoScalingGroupName(groupName)
                    .launchTemplate(templateSpecification)
                    .build();

            autoScalingClient.updateAutoScalingGroup(groupRequest);
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                    .waitUntilGroupInService(groupsRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("You successfully updated the auto scaling group
" + groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateAutoScalingGroup(groupName: String, launchTemplateNameVal:
 String, serviceLinkedRoleARNVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val groupRequest = UpdateAutoScalingGroupRequest {
        maxSize = 3
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
        autoScalingGroupName = groupName
        launchTemplate = templateSpecification
    }

    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.updateAutoScalingGroup(groupRequest)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("You successfully updated the Auto Scaling group  $groupName")
    }
}
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function updateAutoScalingGroup($autoScalingGroupName, $args)
{
    if (array_key_exists('MaxSize', $args)) {
        $maxSize = ['MaxSize' => $args['MaxSize']];
    } else {
        $maxSize = [];
    }
    if (array_key_exists('MinSize', $args)) {
        $minSize = ['MinSize' => $args['MinSize']];
    } else {
        $minSize = [];
    }
    $parameters = ['AutoScalingGroupName' => $autoScalingGroupName];
    $parameters = array_merge($parameters, $minSize, $maxSize);
    return $this->autoScalingClient->updateAutoScalingGroup($parameters);
}
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def update_group(self, group_name, **kwargs):
        """
        Updates an Auto Scaling group.

        :param group_name: The name of the group to update.
        :param kwargs: Keyword arguments to pass through to the service.
        """
        try:
            self.autoscaling_client.update_auto_scaling_group(
                AutoScalingGroupName=group_name, **kwargs
            )
        except ClientError as err:
            logger.error(
                "Couldn't update group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn update_group(client: &Client, name: &str, size: i32) -> Result<(),
 Error> {
    client
        .update_auto_scaling_group()
        .auto_scaling_group_name(name)
        .max_size(size)
        .send()
        .await?;

    println!("Updated AutoScaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupreferência da API AWS SDK for Rust.

Cenários para Auto Scaling usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EC2 Auto Scaling com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar e gerenciar um serviço resiliente usando um AWS SDK
- Gerencie grupos e instâncias do Auto Scaling usando um SDK da AWS

Criar e gerenciar um serviço resiliente usando um AWS SDK

Os exemplos de código a seguir mostram como criar um serviço da Web com carga balanceada que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
static async Task Main(string[] args)
{
    _configuration = new ConfigurationBuilder()
        .SetBasePath(Directory.GetCurrentDirectory())
        .AddJsonFile("settings.json") // Load settings from .json file.
        .AddJsonFile("settings.local.json",
            true) // Optionally, load local settings.
        .Build();
```

```
        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));
```

```
            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper =
host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
```

```
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several
AWS resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server.");
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
```

```
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs
'server_startup_script.sh' when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the
`server.py` script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and
Systems Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3,
_autoScalerWrapper.GroupName, zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or
continue with the demo.\n");
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the
demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
_autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
        var targetGroup = await
_elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGro
protocol, port, defaultVpc.VpcId);

        await
_elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.Lo
subnetIds, targetGroup);
        await
_autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
_elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper
        var loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
that the port is open...");
```

```
            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port,
 ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for
 your default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management
 Console.\n");

                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound traffic from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port,
 ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
 ipString);
                }
            }
```

```
            loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();
```

```
        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite
of these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service
fails, the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
"static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
checks are still shallow.");
        if (interactive)
            await DemoActionChoices();
```

```
        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
_smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile
that contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo,
a deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
```

```
        Console.WriteLine("the deep health check is only for ELB routing and not
for Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the
Auto Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load
balancer can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two
for the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by
an auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler
start a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a
successful recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the
load balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance
typically takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
instance is running and healthy.");
```

```
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
checks mean all instances report as unhealthy.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBal
```

```
            await
 _elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGr
            await
 _autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupNa
            await
 _autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
 _autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
 _recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you
 might incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
```

```
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
```

```
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with
 a specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
 granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to
 the role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
                                         "\"Effect\": \"Allow\"," +
                                         "\"Principal\": {" +
                                         "\"Service\": [" +
                                             "\"ec2.amazonaws.com\"" +
                                         "]" +
                                         "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                                    "}]" +
                                "}";
```

```
        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
```

```
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await
_amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
```

```
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
```

```
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
 Scaling.
    /// The launch template specifies a Bash script in its user data field that
 runs after
    /// the instance is started. This script installs the Python packages and
 starts a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
 run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to
 create and attach to the profile.</param>
    /// <returns>The template object.</returns>
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
 startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName,
 _instanceRoleName, _instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
```

```
                        new

 LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2
 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
```

```
                    LaunchTemplate =
                        new
Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with
size {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
```

```
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
 List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }
```

```
    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the
role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await
_amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }
```

```
            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
 name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
 _amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
 instanceId)
    {
        var response = await
 _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
```

```
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
```

```
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await
_amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
```

```
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for
{instanceId}. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }
```

```
    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string
groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
```

```
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the
 calling computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
 instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP
 address while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
 ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
                        portIsOpen = true;
                    }
                }
```

```
                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be
open to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0),
or to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
```

```
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName,
 string targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
```

```
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
```

```
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }
```

```
    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened
 times and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</
param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer
 exists.</param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
 subnets
    /// and forwards requests to the specified target group.
    /// </summary>
```

```
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
           {
               var describeResponse =
                   await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                       new DescribeLoadBalancersRequest()
                       {
                           Names = new List<string>() { name }
                       });

               var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

               loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
           }
           catch (LoadBalancerNotFoundException)
           {
               loadBalancerReady = false;
           }
           Thread.Sleep(10000);
       }
       // Create the listener.
       await _amazonElasticLoadBalancingV2.CreateListenerAsync(
```

```
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
```

```
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
```

```
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await
 _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn =
 targetArn });
                Console.WriteLine($"Deleted load balancing target group
 {groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books,
 movies, and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
```

```
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
_amazonDynamoDb.DescribeTableAsync(request);
```

```
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await
 File.ReadAllTextAsync(recommendationsPath);
        var records =

 JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
```

```
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement
 _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-
architecture-table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";

    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;
```

```
    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups

- CreateAutoScalingGroup
- CreateInstanceProfile
- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-
prof-bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;
```

```
   public static final String DASHES = new String(new char[80]).replace("\0",
"-");

   public static void main(String[] args) throws IOException,
InterruptedException {
       Scanner in = new Scanner(System.in);
       Database database = new Database();
       AutoScaler autoScaler = new AutoScaler();
       LoadBalancer loadBalancer = new LoadBalancer();

       System.out.println(DASHES);
       System.out.println("Welcome to the demonstration of How to Build and
Manage a Resilient Service!");
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("A - SETUP THE RESOURCES");
       System.out.println("Press Enter when you're ready to start deploying
resources.");
       in.nextLine();
       deploy(loadBalancer);
       System.out.println(DASHES);
       System.out.println(DASHES);
       System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       demo(loadBalancer);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("C - DELETE THE RESOURCES");
       System.out.println("""
               This concludes the demo of how to build and manage a resilient
service.
               To keep things tidy and to avoid unwanted charges on your
account, we can clean up all AWS resources
               that were created for this demo.
               """);

       System.out.println("\n Do you want to delete the resources (y/n)? ");
       String userInput = in.nextLine().trim().toLowerCase(); // Capture user
input

       if (userInput.equals("y")) {
```

```
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }

    private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
        Scanner in = new Scanner(System.in);
        System.out.println(
                """
                        For this demo, we'll use the AWS SDK for Java (v2) to
create several AWS resources
                        to set up a load-balanced web service endpoint and
explore some ways to make it resilient
                        against various kinds of failures.

                        Some of the resources create by this demo are:
```

```
                        \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                        \t* An EC2 launch template that defines EC2 instances
that each contain a Python web server.
                        \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                        \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                        """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
               run a web server, such as Apache, with least-privileged
credentials.

               The template also defines an IAM policy that each instance uses
to assume a role that grants
               permissions to access the DynamoDB recommendation table and
Systems Manager parameters
               that control the flow of the demo.
               """);

       LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
       templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the
demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load
balancer. The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
```

```
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets,
targetGroupArn, lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul =
loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(),
StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group
for your default VPC must
                            allow access from this computer. You can either add
it automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
```

```
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security
group are configured correctly and that");
            System.out.println("you can successfully make a GET request to the
load balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
```

```
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and
shows how using a resilient
                        architecture can keep the web service running in spite
of these failures.

                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager
parameter named self.param_helper.table.
                        To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.
                       """);
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       System.out.println(
               """
                        \nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                       Instead of failing when the recommendation service fails,
the web service can return a static response.
                       While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                       """);
       paramHelper.put(paramHelper.failureResponse, "static");

       System.out.println("""
               Now, sending a GET request to the load balancer endpoint returns
a static response.
```

```
                The service still reports as healthy because health checks are
still shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance
id value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId =
autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " +
profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);
```

```
        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on
for recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto
Scaling instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the
load balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an
auto scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start
a new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
```

```
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load
balancing rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance
is running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);

        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
```

```
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode =
response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load
balancer targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
```

```
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
 target.target().id(),
                                    target.target().port(),
 target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the
 health check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value
 between 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;
```

```
    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance
is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
```

```
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile
is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure
'newInstanceProfileName' is a valid IAM Instance Profile
                                              // name.
                .build();

        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();

        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
```

```
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with
 profile %s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
 waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
 getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
 informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
```

```
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress)
{
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);

            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
```

```
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request =
DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
```

```
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network,
you
     * must instead specify a prefix list ID. You can also temporarily open the
port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();
```

```
            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse =
getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup :
securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " +
secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " +
ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to
be open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                        } else {
                            break;
```

```
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
```

```
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
               .builder()
               .build();

       DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
       List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
               .collect(Collectors.toList());

       String availabilityZones = String.join(",", availabilityZoneNames);
       LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
               .launchTemplateName(templateName)
               .version("$Default")
               .build();

       String[] zones = availabilityZones.split(",");
       CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
               .launchTemplate(specification)
               .availabilityZones(zones)
               .maxSize(groupSize)
               .minSize(groupSize)
               .autoScalingGroupName(autoScalingGroupName)
               .build();

       try {
           getAutoScalingClient().createAutoScalingGroup(groupRequest);

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
       return zones;
   }
```

```
    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability
Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response =
getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
```

```
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
InstanceProfile) {
```

```
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to
 the policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM
 role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
 DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }
```

```
        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
 ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
 iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
 listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
 RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance
 profile " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
 DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
```

```
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String
targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()

.targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
```

```
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()

.loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load
balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws
IOException, InterruptedException {
        boolean success = false;
        int retries = 3;
```

```
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how
instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId,
String targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
```

```
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }

    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
    public String createLoadBalancer(List<Subnet> subnetIds, String
targetGroupARN, String lbName, int port,
            String protocol) {
        try {
            List<String> subnetIdStrings = subnetIds.stream()
                    .map(Subnet::subnetId)
                    .collect(Collectors.toList());

            CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                    .subnets(subnetIdStrings)
                    .name(lbName)
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
```

```
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
 become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
 loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
 CreateListenerRequest.builder()

 .loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " +
 e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended,
 such
```

```
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException
{
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
```

```
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");

            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws
IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable =
enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);
```

```
            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-
response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
```

```
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
```

```
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
```

```
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
```

```
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item']
[] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
```

```
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
```

```
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
```

```
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
```

```
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
```

```
        LaunchTemplate: {
          LaunchTemplateName: NAMES.launchTemplateName,
          Version: "$Default",
        },
        MinSize: 3,
        MaxSize: 3,
      }),
    ),
  );
}),
new ScenarioOutput(
  "createdAutoScalingGroup",
  /**
   * @param {{ availabilityZoneNames: string[] }} state
   */
  (state) =>
    MESSAGES.createdAutoScalingGroup
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
      .replace(
        "${AVAILABILITY_ZONE_NAMES}",
        state.availabilityZoneNames.join(", "),
      ),
),
new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
  type: "confirm",
}),
new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
new ScenarioAction("getVpc", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
  const client = new EC2Client({});
  const { Vpcs } = await client.send(
    new DescribeVpcsCommand({
      Filters: [{ Name: "is-default", Values: ["true"] }],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
  state.defaultVpc = Vpcs[0].VpcId;
}),
new ScenarioOutput("gotVpc", (state) =>
  MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
),
new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
new ScenarioAction("getSubnets", async (state) => {
```

```
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
```

```
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
```

```
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
```

```
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup}} state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
```

```
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
```

```
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
```

```
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
```

```
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
```

```
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
```

```
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
```

```
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
```

```
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-
scaling').Instance }} state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
```

```
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation}} state
     */
    (state) =>
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
```

```
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
```

```
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
```

```
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
```

```
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";
```

```
import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
```

```
    new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
    new ScenarioAction(
      "abort",
      (state) => state.destroy === false && process.exit(),
    ),
    new ScenarioAction("deleteTable", async (c) => {
      try {
        const client = new DynamoDBClient({});
        await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
      } catch (e) {
        c.deleteTableError = e;
      }
    }),
    new ScenarioOutput("deleteTableResult", (state) => {
      if (state.deleteTableError) {
        console.error(state.deleteTableError);
        return MESSAGES.deleteTableError.replace(
          "${TABLE_NAME}",
          NAMES.tableName,
        );
      } else {
        return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
      }
    }),
    new ScenarioAction("deleteKeyPair", async (state) => {
      try {
        const client = new EC2Client({});
        await client.send(
          new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
        );
        unlinkSync(`${NAMES.keyPairName}.pem`);
      } catch (e) {
        state.deleteKeyPairError = e;
      }
    }),
    new ScenarioOutput("deleteKeyPairResult", (state) => {
      if (state.deleteKeyPairError) {
        console.error(state.deleteKeyPairError);
        return MESSAGES.deleteKeyPairError.replace(
          "${KEY_PAIR_NAME}",
          NAMES.keyPairName,
        );
      } else {
        return MESSAGES.deletedKeyPair.replace(
```

```
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
```

```
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
```

```
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
```

```
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
```

```
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
```

```
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
```

```
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
```

```
    }),
    new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
      if (state.detachSsmOnlyCustomRolePolicyError) {
        console.error(state.detachSsmOnlyCustomRolePolicyError);
        return MESSAGES.detachSsmOnlyCustomRolePolicyError
          .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
          .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
      } else {
        return MESSAGES.detachedSsmOnlyCustomRolePolicy
          .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
          .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
      }
    }),
    new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
      try {
        const iamClient = new IAMClient({});
        await iamClient.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.ssmOnlyRoleName,
            PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
          }),
        );
      } catch (e) {
        state.detachSsmOnlyAWSRolePolicyError = e;
      }
    }),
    new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
      if (state.detachSsmOnlyAWSRolePolicyError) {
        console.error(state.detachSsmOnlyAWSRolePolicyError);
        return MESSAGES.detachSsmOnlyAWSRolePolicyError
          .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
          .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
      } else {
        return MESSAGES.detachedSsmOnlyAWSRolePolicy
          .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
          .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
      }
    }),
    new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
      try {
        const iamClient = new IAMClient({});
        await iamClient.send(
          new DeleteInstanceProfileCommand({
            InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
```

```
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
```

```
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
      return policy;
    }
  }
}
```

```
/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
        }),
      ),
    );
  }
```

```
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers

- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"
```

```
        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server."
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
'{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
```

```
            f"For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged
credentials.\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
            f"Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or
continue with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load
balancer provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
```

```
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port
 is open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for
 your default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.
\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
```

```
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging
 from your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
                "Couldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                "manually verifying that your VPC and security group are
 configured correctly and that\n"
                "you can successfully make a GET request to the load balancer
 endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
 following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
```

```
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health
check to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts
of the system\n"
            "to create situations where the web service fails, and shows how
using a resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)
```

```
        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations
by querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't
check for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with
a somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns
a static response.\n"
            f"The service still reports as healthy because health checks are
still shallow.\n"
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
```

```
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a
profile that contains\n"
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto
Scaling instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.\n"
        )
        print(
```

```
            "By implementing deep health checks, the load balancer can detect
when one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
            "\nBecause the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
starting, sending a GET\n"
            "request to the web service continues to get a successful
recommendation response because\n"
            "the load balancer routes requests to the healthy instances. After
the replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
running and healthy.\n"
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean
all instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
```

```
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient
 service.\n"
            "To keep things tidy and to avoid unwanted charges on your account,
 we can clean up all AWS resources\n"
            "that were created for this demo."
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ",
 q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you
 might incur unexpected charges."
            )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
```

```
        help="The action to take for the demo. When 'all' is specified, resources
are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM
policies and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
Service!"
    )
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer,
param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
"destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)
```

```
if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
```

```
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are
created by this class.
        """
        as_client = boto3.client("autoscaling")
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is
assumed by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.
```

```
        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as
AmazonSSMManagedInstanceCore to grant
                                     use of Systems Manager to send commands to
the instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
```

```
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
```

```
                    "Instance profile %s already exists, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to
role\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response =
self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.
```

```
        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
instance_id)
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the
role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )
```

```
    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.

        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.",
self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
```

```
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling. The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts
a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a
permissions policy
                                     to create and attach to the instance
profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
```

```
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template
{self.launch_template_name}: {err}."
                )
        return template


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
```

```
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template
{self.launch_template_name}: {err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones


    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
```

```
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group
{self.group_name}: {err}"
            )
```

```
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance
is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group
%s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] ==
"ScalingActivityInProgress"
                ):
```

```
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling
 group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
```

```
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress
from this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
```

```
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to
either this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
```

```
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port}
from {ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""
```

```
    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by
this class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint
```

```
    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group
specifies how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened
times and
        lower thresholds. In production, you might want to decrease the
sensitivity of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
```

```
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to
do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
```

```
        :param target_group: An existing target group that is added as a listener
to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
```

```
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
```

```
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint,
 retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets:
 {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books,
 movies,
    and songs.
    """
```

```
    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended,
such as
        Book or Movie, and a range key named 'ItemId' that, combined with the
MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5,
"WriteCapacityUnits": 5},
            )
            log.info("Creating table %s...", self.table_name)
```

```
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name,
data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}:
{err}"
            )

    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
```

```
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.",
 self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters
 to drive
    the demonstration of resilient architecture, such as failure of a dependency
 or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)
```

```
    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when
a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup

- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Gerencie grupos e instâncias do Auto Scaling usando um SDK da AWS

Os exemplos de código a seguir mostram como:

- Crie um grupo do Amazon EC2 Auto Scaling com um modelo de execução e zonas de disponibilidade, e obtenha informações sobre instâncias em execução.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
global using Amazon.AutoScaling;
global using Amazon.AutoScaling.Model;
global using Amazon.CloudWatch;
global using AutoScalingActions;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;



using Amazon.EC2;
using Microsoft.Extensions.Configuration;
using Host = Microsoft.Extensions.Hosting.Host;

namespace AutoScalingBasics;

public class AutoScalingBasics
{

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EC2 Auto Scaling, Amazon
        // CloudWatch, and Amazon EC2.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
```

```
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonAutoScaling>()
                .AddAWSService<IAmazonCloudWatch>()
                .AddAWSService<IAmazonEC2>()
                .AddTransient<AutoScalingWrapper>()
                .AddTransient<CloudWatchWrapper>()
                .AddTransient<EC2Wrapper>()
                .AddTransient<UIWrapper>()
            )
            .Build();


        var autoScalingWrapper =
host.Services.GetRequiredService<AutoScalingWrapper>();
        var cloudWatchWrapper =
host.Services.GetRequiredService<CloudWatchWrapper>();
        var ec2Wrapper = host.Services.GetRequiredService<EC2Wrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var imageId = configuration["ImageId"];
        var instanceType = configuration["InstanceType"];
        var launchTemplateName = configuration["LaunchTemplateName"];

        launchTemplateName += Guid.NewGuid().ToString();

        // The name of the Auto Scaling group.
        var groupName = configuration["GroupName"];

        uiWrapper.DisplayTitle("Auto Scaling Basics");
        uiWrapper.DisplayAutoScalingBasicsDescription();

        // Create the launch template and save the template Id to use when
deleting the
        // launch template at the end of the application.
        var launchTemplateId = await
ec2Wrapper.CreateLaunchTemplateAsync(imageId!, instanceType!,
launchTemplateName);
```

```
        // Confirm that the template was created by asking for a description of
it.
        await ec2Wrapper.DescribeLaunchTemplateAsync(launchTemplateName);

        uiWrapper.PressEnter();

        var availabilityZones = await ec2Wrapper.ListAvailabilityZonesAsync();

        Console.WriteLine($"Creating an Auto Scaling group named {groupName}.");
        await autoScalingWrapper.CreateAutoScalingGroupAsync(
            groupName!,
            launchTemplateName,
            availabilityZones.First().ZoneName);

        // Keep checking the details of the new group until its lifecycle state
        // is "InService".
        Console.WriteLine($"Waiting for the Auto Scaling group to be active.");

        List<AutoScalingInstanceDetails> instanceDetails;

        do
        {
            instanceDetails = await
autoScalingWrapper.DescribeAutoScalingInstancesAsync(groupName!);
        }
        while (instanceDetails.Count <= 0);

        Console.WriteLine($"Auto scaling group {groupName} successfully
created.");
        Console.WriteLine($"{instanceDetails.Count} instances were created for
the group.");

        // Display the details of the Auto Scaling group.
        instanceDetails.ForEach(detail =>
        {
            Console.WriteLine($"Group name: {detail.AutoScalingGroupName}");
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Metrics collection");
        Console.WriteLine($"Enable metrics collection for {groupName}");
        await autoScalingWrapper.EnableMetricsCollectionAsync(groupName!);
```

```
        // Show the metrics that are collected for the group.

        // Update the maximum size of the group to three instances.
        Console.WriteLine("--- Update the Auto Scaling group to increase max size
to 3 ---");
        int maxSize = 3;
        await autoScalingWrapper.UpdateAutoScalingGroupAsync(groupName!,
launchTemplateName, maxSize);

        Console.WriteLine("--- Describe all Auto Scaling groups to show the
current state of the group ---");
        var groups = await
autoScalingWrapper.DescribeAutoScalingGroupsAsync(groupName!);

        uiWrapper.DisplayGroupDetails(groups!);

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Describe account limits");
        await autoScalingWrapper.DescribeAccountLimitsAsync();

        uiWrapper.WaitABit(60, "Waiting for the resources to be ready.");

        uiWrapper.DisplayTitle("Set desired capacity");
        int desiredCapacity = 2;
        await autoScalingWrapper.SetDesiredCapacityAsync(groupName!,
desiredCapacity);

        Console.WriteLine("Get the two instance Id values");

        // Empty the group before getting the details again.
        groups!.Clear();
        groups = await
autoScalingWrapper.DescribeAutoScalingGroupsAsync(groupName!);
        if (groups is not null)
        {
            foreach (AutoScalingGroup group in groups)
            {
                Console.WriteLine($"The group name is
{group.AutoScalingGroupName}");
                Console.WriteLine($"The group ARN is
{group.AutoScalingGroupARN}");
                var instances = group.Instances;
```

```
                foreach (Amazon.AutoScaling.Model.Instance instance in instances)
                {
                    Console.WriteLine($"The instance id is
{instance.InstanceId}");
                    Console.WriteLine($"The lifecycle state is
{instance.LifecycleState}");
                }
            }
        }

        uiWrapper.DisplayTitle("Scaling Activities");
        Console.WriteLine("Let's list the scaling activities that have occurred
for the group.");
        var activities = await
autoScalingWrapper.DescribeScalingActivitiesAsync(groupName!);
        if (activities is not null)
        {
            activities.ForEach(activity =>
            {
                Console.WriteLine($"The activity Id is {activity.ActivityId}");
                Console.WriteLine($"The activity details are
{activity.Details}");
            });
        }

        // Display the Amazon CloudWatch metrics that have been collected.
        var metrics = await
cloudWatchWrapper.GetCloudWatchMetricsAsync(groupName!);
        Console.WriteLine($"Metrics collected for {groupName}:");
        metrics.ForEach(metric =>
        {
            Console.Write($"Metric name: {metric.MetricName}\t");
            Console.WriteLine($"Namespace: {metric.Namespace}");
        });

        var dataPoints = await
cloudWatchWrapper.GetMetricStatisticsAsync(groupName!);
        Console.WriteLine("Details for the metrics collected:");
        dataPoints.ForEach(detail =>
        {
            Console.WriteLine(detail);
        });

        // Disable metrics collection.
```

```
        Console.WriteLine("Disabling the collection of metrics for
{groupName}.");
        var success = await
autoScalingWrapper.DisableMetricsCollectionAsync(groupName!);

        if (success)
        {
            Console.WriteLine($"Successfully stopped metrics collection for
{groupName}.");
        }
        else
        {
            Console.WriteLine($"Could not stop metrics collection for
{groupName}.");
        }

        // Terminate all instances in the group.
        uiWrapper.DisplayTitle("Terminating Auto Scaling instances");
        Console.WriteLine("Now terminating all instances in the Auto Scaling
group.");

        if (groups is not null)
        {
            groups.ForEach(group =>
            {
                // Only delete instances in the AutoScaling group we created.
                if (group.AutoScalingGroupName == groupName)
                {
                    group.Instances.ForEach(async instance =>
                    {
                        await
autoScalingWrapper.TerminateInstanceInAutoScalingGroupAsync(instance.InstanceId);
                    });
                }
            });
        }

        // After all instances are terminated, delete the group.
        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("Deleting the Auto Scaling group.");
        await autoScalingWrapper.DeleteAutoScalingGroupAsync(groupName!);

        // Delete the launch template.
```

```
        var deletedLaunchTemplateName = await
 ec2Wrapper.DeleteLaunchTemplateAsync(launchTemplateId);

        if (deletedLaunchTemplateName == launchTemplateName)
        {
            Console.WriteLine("Successfully deleted the launch template.");
        }

        Console.WriteLine("The demo is now concluded.");
    }
}


namespace AutoScalingBasics;

/// <summary>
/// A class to provide user interface methods for the EC2 AutoScaling Basics
/// scenario.
/// </summary>
public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Describe the steps in the EC2 AutoScaling Basics scenario.
    /// </summary>
    public void DisplayAutoScalingBasicsDescription()
    {
        Console.WriteLine("This code example performs the following
 operations:");
        Console.WriteLine(" 1. Creates an Amazon EC2 launch template.");
        Console.WriteLine(" 2. Creates an Auto Scaling group.");
        Console.WriteLine(" 3. Shows the details of the new Auto Scaling group");
        Console.WriteLine("    to show that only one instance was created.");
        Console.WriteLine(" 4. Enables metrics collection.");
        Console.WriteLine(" 5. Updates the Auto Scaling group to increase the");
        Console.WriteLine("    capacity to three.");
        Console.WriteLine(" 6. Describes Auto Scaling groups again to show the");
        Console.WriteLine("    current state of the group.");
        Console.WriteLine(" 7. Changes the desired capacity of the Auto
 Scaling");
        Console.WriteLine("    group to use an additional instance.");
        Console.WriteLine(" 8. Shows that there are now instances in the
 group.");
```

```
        Console.WriteLine(" 9. Lists the scaling activities that have occurred
 for the group.");
        Console.WriteLine("10. Displays the Amazon CloudWatch metrics that
 have");
        Console.WriteLine("    been collected.");
        Console.WriteLine("11. Disables metrics collection.");
        Console.WriteLine("12. Terminates all instances in the Auto Scaling
 group.");
        Console.WriteLine("13. Deletes the Auto Scaling group.");
        Console.WriteLine("14. Deletes the Amazon EC2 launch template.");
        PressEnter();
    }

    /// <summary>
    /// Display information about the Amazon Ec2 AutoScaling groups passed
    /// in the list of AutoScalingGroup objects.
    /// </summary>
    /// <param name="groups">A list of AutoScalingGroup objects.</param>
    public void DisplayGroupDetails(List<AutoScalingGroup> groups)
    {
        if (groups is null)
            return;

        groups.ForEach(group =>
        {
            Console.WriteLine($"Group name:\t{group.AutoScalingGroupName}");
            Console.WriteLine($"Group created:\t{group.CreatedTime}");
            Console.WriteLine($"Maximum number of instances:\t{group.MaxSize}");
            Console.WriteLine($"Desired number of instances:
\t{group.DesiredCapacity}");
        });
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
```

```
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar modelos e métricas de execução. Essas funções incluem Auto Scaling, Amazon EC2 e ações. CloudWatch

```
namespace AutoScalingActions;

using Amazon.AutoScaling;
using Amazon.AutoScaling.Model;

/// <summary>
/// A class that includes methods to perform Amazon EC2 Auto Scaling
/// actions.
/// </summary>
public class AutoScalingWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;

    /// <summary>
    /// Constructor for the AutoScalingWrapper class.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected Amazon EC2 Auto Scaling
 client.</param>
    public AutoScalingWrapper(IAmazonAutoScaling amazonAutoScaling)
    {
        _amazonAutoScaling = amazonAutoScaling;
    }


    /// <summary>
    /// Create a new Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name to use for the new Auto Scaling
    /// group.</param>
    /// <param name="launchTemplateName">The name of the Amazon EC2 Auto Scaling
    /// launch template to use to create instances in the group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        string availabilityZone)
    {
        var templateSpecification = new LaunchTemplateSpecification
        {
```

```
            LaunchTemplateName = launchTemplateName,
        };

        var zoneList = new List<string>
            {
                availabilityZone,
            };

        var request = new CreateAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            AvailabilityZones = zoneList,
            LaunchTemplate = templateSpecification,
            MaxSize = 6,
            MinSize = 1
        };

        var response = await
_amazonAutoScaling.CreateAutoScalingGroupAsync(request);
        Console.WriteLine($"{groupName} Auto Scaling Group created");
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }



    /// <summary>
    /// Retrieve information about Amazon EC2 Auto Scaling quotas to the
    /// active AWS account.
    /// </summary>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DescribeAccountLimitsAsync()
    {
        var response = await _amazonAutoScaling.DescribeAccountLimitsAsync();
        Console.WriteLine("The maximum number of Auto Scaling groups is " +
response.MaxNumberOfAutoScalingGroups);
        Console.WriteLine("The current number of Auto Scaling groups is " +
response.NumberOfAutoScalingGroups);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }



    /// <summary>
    /// Retrieve a list of the Amazon EC2 Auto Scaling activities for an
```

```
    /// Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling activities.</returns>
    public async Task<List<Amazon.AutoScaling.Model.Activity>>
 DescribeScalingActivitiesAsync(
        string groupName)
    {
        var scalingActivitiesRequest = new DescribeScalingActivitiesRequest
        {
            AutoScalingGroupName = groupName,
            MaxRecords = 10,
        };

        var response = await
 _amazonAutoScaling.DescribeScalingActivitiesAsync(scalingActivitiesRequest);
        return response.Activities;
    }



    /// <summary>
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
                    instanceIds.Add(instance.InstanceId);
                });
            }
        });
```

```
        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;

        return instanceDetails;
    }



    /// <summary>
    /// Retrieve a list of information about Amazon EC2 Auto Scaling groups.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling groups.</returns>
    public async Task<List<AutoScalingGroup>?> DescribeAutoScalingGroupsAsync(
        string groupName)
    {
        var groupList = new List<string>
            {
                groupName,
            };

        var request = new DescribeAutoScalingGroupsRequest
        {
            AutoScalingGroupNames = groupList,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingGroupsAsync(request);
        var groups = response.AutoScalingGroups;

        return groups;
    }


    /// <summary>
```

```
    /// Delete an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAutoScalingGroupAsync(
        string groupName)
    {
        var deleteAutoScalingGroupRequest = new DeleteAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            ForceDelete = true,
        };

        var response = await
 _amazonAutoScaling.DeleteAutoScalingGroupAsync(deleteAutoScalingGroupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully deleted {groupName}");
            return true;
        }

        Console.WriteLine($"Couldn't delete {groupName}.");
        return false;
    }


    /// <summary>
    /// Disable the collection of metric data for an Amazon EC2 Auto Scaling
    /// group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DisableMetricsCollectionAsync(string groupName)
    {
        var request = new DisableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
        };

        var response = await
 _amazonAutoScaling.DisableMetricsCollectionAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
```

```
    }


    /// <summary>
    /// Enable the collection of metric data for an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> EnableMetricsCollectionAsync(string groupName)
    {
        var listMetrics = new List<string>
            {
                "GroupMaxSize",
            };

        var collectionRequest = new EnableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
            Metrics = listMetrics,
            Granularity = "1Minute",
        };

        var response = await
_amazonAutoScaling.EnableMetricsCollectionAsync(collectionRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Set the desired capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="desiredCapacity">The desired capacity for the Auto
    /// Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SetDesiredCapacityAsync(
        string groupName,
        int desiredCapacity)
    {
        var capacityRequest = new SetDesiredCapacityRequest
        {
            AutoScalingGroupName = groupName,
            DesiredCapacity = desiredCapacity,
        };
```

```
        var response = await
 _amazonAutoScaling.SetDesiredCapacityAsync(capacityRequest);
        Console.WriteLine($"You have set the DesiredCapacity to
 {desiredCapacity}.");

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Terminate all instances in the Auto Scaling group in preparation for
    /// deleting the group.
    /// </summary>
    /// <param name="instanceId">The instance Id of the instance to terminate.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> TerminateInstanceInAutoScalingGroupAsync(
        string instanceId)
    {
        var request = new TerminateInstanceInAutoScalingGroupRequest
        {
            InstanceId = instanceId,
            ShouldDecrementDesiredCapacity = false,
        };

        var response = await
 _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You have terminated the instance: {instanceId}");
            return true;
        }

        Console.WriteLine($"Could not terminate {instanceId}");
        return false;
    }


    /// <summary>
    /// Update the capacity of an Auto Scaling group.
    /// </summary>
```

```
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <param name="maxSize">The maximum number of instances that can be
    /// created for the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        int maxSize)
    {
        var templateSpecification = new LaunchTemplateSpecification
        {
            LaunchTemplateName = launchTemplateName,
        };

        var groupRequest = new UpdateAutoScalingGroupRequest
        {
            MaxSize = maxSize,
            AutoScalingGroupName = groupName,
            LaunchTemplate = templateSpecification,
        };

        var response = await
 _amazonAutoScaling.UpdateAutoScalingGroupAsync(groupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully updated the Auto Scaling group
 {groupName}.");
            return true;
        }
        else
        {
            return false;
        }
    }

}


namespace AutoScalingActions;

using Amazon.EC2;
using Amazon.EC2.Model;
```

```
public class EC2Wrapper
{
    private readonly IAmazonEC2 _amazonEc2;

    /// <summary>
    /// Constructor for the EC2Wrapper class.
    /// </summary>
    /// <param name="amazonEc2">The injected Amazon EC2 client.</param>
    public EC2Wrapper(IAmazonEC2 amazonEc2)
    {
        _amazonEc2 = amazonEc2;
    }

    /// <summary>
    /// Create a new Amazon EC2 launch template.
    /// </summary>
    /// <param name="imageId">The image Id to use for instances launched
    /// using the Amazon EC2 launch template.</param>
    /// <param name="instanceType">The type of EC2 instances to create.</param>
    /// <param name="launchTemplateName">The name of the launch template.</param>
    /// <returns>Returns the TemplateID of the new launch template.</returns>
    public async Task<string> CreateLaunchTemplateAsync(
        string imageId,
        string instanceType,
        string launchTemplateName)
    {
        var request = new CreateLaunchTemplateRequest
        {
            LaunchTemplateData = new RequestLaunchTemplateData
            {
                ImageId = imageId,
                InstanceType = instanceType,
            },
            LaunchTemplateName = launchTemplateName,
        };

        var response = await _amazonEc2.CreateLaunchTemplateAsync(request);

        return response.LaunchTemplate.LaunchTemplateId;
    }

    /// <summary>
    /// Delete an Amazon EC2 launch template.
```

```
    /// </summary>
    /// <param name="launchTemplateId">The TemplateId of the launch template to
    /// delete.</param>
    /// <returns>The name of the EC2 launch template that was deleted.</returns>
    public async Task<string> DeleteLaunchTemplateAsync(string launchTemplateId)
    {
        var request = new DeleteLaunchTemplateRequest
        {
            LaunchTemplateId = launchTemplateId,
        };

        var response = await _amazonEc2.DeleteLaunchTemplateAsync(request);
        return response.LaunchTemplate.LaunchTemplateName;
    }

    /// <summary>
    /// Retrieve information about an EC2 launch template.
    /// </summary>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DescribeLaunchTemplateAsync(string
 launchTemplateName)
    {
        var request = new DescribeLaunchTemplatesRequest
        {
            LaunchTemplateNames = new List<string> { launchTemplateName, },
        };

        var response = await _amazonEc2.DescribeLaunchTemplatesAsync(request);

        if (response.LaunchTemplates is not null)
        {
            response.LaunchTemplates.ForEach(template =>
            {
                Console.Write($"{template.LaunchTemplateName}\t");
                Console.WriteLine(template.LaunchTemplateId);
            });

            return true;
        }

        return false;
```

```
    }

    /// <summary>
    /// Retrieve the availability zones for the current region.
    /// </summary>
    /// <returns>A collection of availability zones.</returns>
    public async Task<List<AvailabilityZone>> ListAvailabilityZonesAsync()
    {
        var response = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());

        return response.AvailabilityZones;
    }
}


namespace AutoScalingActions;

using Amazon.CloudWatch;
using Amazon.CloudWatch.Model;

/// <summary>
/// Contains methods to access Amazon CloudWatch metrics for the
/// Amazon EC2 Auto Scaling basics scenario.
/// </summary>
public class CloudWatchWrapper
{
    private readonly IAmazonCloudWatch _amazonCloudWatch;

    /// <summary>
    /// Constructor for the CloudWatchWrapper.
    /// </summary>
    /// <param name="amazonCloudWatch">The injected CloudWatch client.</param>
    public CloudWatchWrapper(IAmazonCloudWatch amazonCloudWatch)
    {
        _amazonCloudWatch = amazonCloudWatch;
    }

    /// <summary>
    /// Retrieve the metrics information collection for the Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A list of Metrics collected for the Auto Scaling group.</
returns>
```

```
    public async Task<List<Amazon.CloudWatch.Model.Metric>>
 GetCloudWatchMetricsAsync(string groupName)
    {
        var filter = new DimensionFilter
        {
            Name = "AutoScalingGroupName",
            Value = $"{groupName}",
        };

        var request = new ListMetricsRequest
        {
            MetricName = "AutoScalingGroupName",
            Dimensions = new List<DimensionFilter> { filter },
            Namespace = "AWS/AutoScaling",
        };

        var response = await _amazonCloudWatch.ListMetricsAsync(request);

        return response.Metrics;
    }

    /// <summary>
    /// Retrieve the metric data collected for an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of data points.</returns>
    public async Task<List<Datapoint>> GetMetricStatisticsAsync(string groupName)
    {
        var metricDimensions = new List<Dimension>
            {
                new Dimension
                {
                    Name = "AutoScalingGroupName",
                    Value = $"{groupName}",
                },
            };

        // The start time will be yesterday.
        var startTime = DateTime.UtcNow.AddDays(-1);

        var request = new GetMetricStatisticsRequest
        {
            MetricName = "AutoScalingGroupName",
```

```
            Dimensions = metricDimensions,
            Namespace = "AWS/AutoScaling",
            Period = 60, // 60 seconds.
            Statistics = new List<string>() { "Minimum" },
            StartTimeUtc = startTime,
            EndTimeUtc = DateTime.UtcNow,
        };

        var response = await _amazonCloudWatch.GetMetricStatisticsAsync(request);

        return response.Datapoints;
    }

}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Routine which demonstrates using an Auto Scaling group
//! to manage Amazon EC2 instances.
/*!
  \sa groupsAndInstancesScenario()
  \param clientConfig: AWS client configuration.
  \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::groupsAndInstancesScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::String templateName;
    Aws::EC2::EC2Client ec2Client(clientConfig);

    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;
    std::cout
            << "Welcome to the Amazon Elastic Compute Cloud (Amazon EC2) Auto
 Scaling "
            << "demo for managing groups and instances." << std::endl;
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " \n"
              << std::endl;

    std::cout << "This example requires an EC2 launch template." << std::endl;
    if (askYesNoQuestion(
            "Would you like to use an existing EC2 launch template (y/n)?  ")) {

        // 1. Specify the name of an existing EC2 launch template.
        templateName = askQuestion(
                "Enter the name of the existing EC2 launch template.  ");

        Aws::EC2::Model::DescribeLaunchTemplatesRequest request;
        request.AddLaunchTemplateNames(templateName);
        Aws::EC2::Model::DescribeLaunchTemplatesOutcome outcome =
```

```
                ec2Client.DescribeLaunchTemplates(request);

        if (outcome.IsSuccess()) {
            std::cout << "Validated the EC2 launch template '" << templateName
                      << "' exists by calling DescribeLaunchTemplate." <<
std::endl;
        }
        else {
            std::cerr << "Error validating the existence of the launch template.
"
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }
    else { // 2.  Or create a new EC2 launch template.
        templateName = askQuestion("Enter the name for a new EC2 launch template:
");

        Aws::EC2::Model::CreateLaunchTemplateRequest request;
        request.SetLaunchTemplateName(templateName);

        Aws::EC2::Model::RequestLaunchTemplateData requestLaunchTemplateData;

requestLaunchTemplateData.SetInstanceType(EC2_LAUNCH_TEMPLATE_INSTANCE_TYPE);
        requestLaunchTemplateData.SetImageId(EC2_LAUNCH_TEMPLATE_IMAGE_ID);

        request.SetLaunchTemplateData(requestLaunchTemplateData);

        Aws::EC2::Model::CreateLaunchTemplateOutcome outcome =
                ec2Client.CreateLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "The EC2 launch template '" << templateName << " was
created."
                      << std::endl;
        }
        else if (outcome.GetError().GetExceptionName() ==
                 "InvalidLaunchTemplateName.AlreadyExistsException") {
            std::cout << "The EC2 template '" << templateName << "' already
exists"
                      << std::endl;
        }
        else {
            std::cerr << "Error with EC2::CreateLaunchTemplate. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;
        }
    }
    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);
    std::cout << "Let's create an Auto Scaling group." << std::endl;
    Aws::String groupName = askQuestion(
            "Enter a name for the Auto Scaling group:  ");
    // 3. Retrieve a list of EC2 Availability Zones.
    Aws::Vector<Aws::EC2::Model::AvailabilityZone> availabilityZones;
    {
        Aws::EC2::Model::DescribeAvailabilityZonesRequest request;

        Aws::EC2::Model::DescribeAvailabilityZonesOutcome outcome =
                ec2Client.DescribeAvailabilityZones(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "EC2 instances can be created in the following
Availability Zones:"
                    << std::endl;

            availabilityZones = outcome.GetResult().GetAvailabilityZones();
            for (size_t i = 0; i < availabilityZones.size(); ++i) {
                std::cout << "   " << i + 1 << ".  "
                          << availabilityZones[i].GetZoneName() << std::endl;
            }
        }
        else {
            std::cerr << "Error with EC2::DescribeAvailabilityZones. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    int availabilityZoneChoice = askQuestionForIntRange(
            "Choose an Availability Zone:  ", 1,
            static_cast<int>(availabilityZones.size()));
    // 4. Create an Auto Scaling group with the specified Availability Zone.
    {
        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
```

```
        Aws::Vector<Aws::String> availabilityGroupZones;
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already
exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        std::cout << "Here is the Auto Scaling group description." << std::endl;
        if (!autoScalingGroups.empty()) {
            logAutoScalingGroupInfo(autoScalingGroups);
        }
    }
    else {
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
```

```
        return false;
    }

    std::cout
            << "Waiting for the EC2 instance in the Auto Scaling group to become
active..."
            << std::endl;
    if (!waitForInstances(groupName, autoScalingGroups, autoScalingClient)) {
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
        return false;
    }

    bool enableMetrics = askYesNoQuestion(
            "Do you want to collect metrics about the A"
            "Auto Scaling group during this demo (y/n)?  ");
    // 7. Optionally enable metrics collection for the Auto Scaling group.
    if (enableMetrics) {
        Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        request.AddMetrics("GroupMinSize");
        request.AddMetrics("GroupMaxSize");
        request.AddMetrics("GroupDesiredCapacity");
        request.AddMetrics("GroupInServiceInstances");
        request.AddMetrics("GroupTotalInstances");
        request.SetGranularity("1Minute");

        Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
                autoScalingClient.EnableMetricsCollection(request);
        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling metrics have been enabled."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
            return false;
        }
    }
```

```
   std::cout << "Let's update the maximum number of EC2 instances in '" <<
groupName <<
             "' from 1 to 3." << std::endl;
   askQuestion("Press enter to continue:  ", alwaysTrueTest);
   // 8. Update the Auto Scaling group, setting a new maximum size.
   {
       Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
       request.SetAutoScalingGroupName(groupName);
       request.SetMaxSize(3);

       Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
               autoScalingClient.UpdateAutoScalingGroup(request);

       if (!outcome.IsSuccess()) {
           std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
           return false;
       }
   }

   if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                          autoScalingClient)) {
       if (!autoScalingGroups.empty()) {
           const auto &instances = autoScalingGroups[0].GetInstances();
           std::cout
                   << "The group still has one running EC2 instance, but it can
have up to 3.\n"
                   << std::endl;
           logAutoScalingGroupInfo(autoScalingGroups);
       }
       else {
           std::cerr
                   << "No EC2 launch groups were retrieved from DescribeGroup
request."
                   << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
           return false;
       }
   }
```

```
   std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) <<
"\n"
             << std::endl;
   std::cout << "Let's update the desired capacity in '" << groupName <<
             "' from 1 to 2." << std::endl;
   askQuestion("Press enter to continue:  ", alwaysTrueTest);
   //  9. Update the Auto Scaling group, setting a new desired capacity.
   {
       Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
       request.SetAutoScalingGroupName(groupName);
       request.SetDesiredCapacity(2);

       Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
               autoScalingClient.SetDesiredCapacity(request);

       if (!outcome.IsSuccess()) {
           std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
           return false;
       }
   }

   if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                          autoScalingClient)) {
       if (!autoScalingGroups.empty()) {
           std::cout
                   << "Here is the current state of the group." << std::endl;
           logAutoScalingGroupInfo(autoScalingGroups);
       }
       else {
           std::cerr
                   << "No EC2 launch groups were retrieved from DescribeGroup
request."
                   << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
           return false;
       }
   }

   std::cout << "Waiting for the new EC2 instance to start..." << std::endl;
```

```
   waitForInstances(groupName, autoScalingGroups, autoScalingClient);

   std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) <<
"\n"
             << std::endl;

   std::cout << "Let's terminate one of the EC2 instances in " << groupName <<
"."
             << std::endl;
   std::cout << "Because the desired capacity is 2, another EC2 instance will
start "
             << "to replace the terminated EC2 instance."
             << std::endl;
   std::cout << "The currently running EC2 instances are:" << std::endl;

   if (autoScalingGroups.empty()) {
       std::cerr << "Error describing groups. No groups returned." << std::endl;
       cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
       return false;
   }

   int instanceNumber = 1;
   Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
           autoScalingGroups[0].GetInstances());
   for (const Aws::String &instanceID: instanceIDs) {
       std::cout << "   " << instanceNumber << ". " << instanceID << std::endl;
       ++instanceNumber;
   }

   instanceNumber = askQuestionForIntRange("Which EC2 instance do you want to
stop? ",
                                           1,

static_cast<int>(instanceIDs.size()));

   // 10. Terminate an EC2 instance in the Auto Scaling group.
   {
       Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest
request;
       request.SetInstanceId(instanceIDs[instanceNumber - 1]);
       request.SetShouldDecrementDesiredCapacity(false);

       Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome
outcome =
```

```
                autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Waiting for EC2 instance with ID '"
                      << instanceIDs[instanceNumber - 1] << "' to terminate..."
                      << std::endl;
        }
        else {
            std::cerr << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
            return false;
        }
    }

    waitForInstances(groupName, autoScalingGroups, autoScalingClient);

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) <<
"\n"
              << std::endl;
    std::cout << "Let's get a report of scaling activities for EC2 launch group
'"
              << groupName << "'."
              << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    // 11. Get a description of activities for the Auto Scaling group.
    {
        Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                autoScalingClient.DescribeScalingActivities(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                    outcome.GetResult().GetActivities();
            std::cout << "Found " << activities.size() << " activities." <<
std::endl;
            std::cout << "Activities are ordered with the most recent first."
                      << std::endl;
            for (const Aws::AutoScaling::Model::Activity &activity: activities) {
```

```
                std::cout << activity.GetDescription() << std::endl;
                std::cout << activity.GetDetails() << std::endl;
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
            return false;
        }
    }

    if (enableMetrics) {
        if (!logAutoScalingMetrics(groupName, clientConfig)) {
            cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
            return false;
        }
    }

    std::cout << "Let's  clean up." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);

    // 13. Disable metrics collection if enabled.
    if (enableMetrics) {
        Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
                autoScalingClient.DisableMetricsCollection(request);

        if (outcome.IsSuccess()) {
            std::cout << "Metrics collection has been disabled." << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
            return false;
        }
```

```
    }

    return cleanupResources(groupName, templateName, autoScalingClient,
 ec2Client);
}

//! Routine which waits for EC2 instances in an Auto Scaling group to
//! complete startup or shutdown.
/*!
 \sa waitForInstances()
 \param groupName: An Auto Scaling group name.
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::waitForInstances(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroups,
                                            const
 Aws::AutoScaling::AutoScalingClient &client) {
    bool ready = false;
    const std::vector<Aws::String> READY_STATES = {"InService", "Terminated"};

    int count = 0;
    int desiredCapacity = 0;
    std::this_thread::sleep_for(std::chrono::seconds(4));
    while (!ready) {
        if (WAIT_FOR_INSTANCES_TIMEOUT < count) {
            std::cerr << "Wait for instance timed out." << std::endl;
            return false;
        }

        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++count;
        if (!describeGroup(groupName, autoScalingGroups, client)) {
            return false;
        }
        Aws::Vector<Aws::String> instanceIDs;
        if (!autoScalingGroups.empty()) {
            instanceIDs =
 instancesToInstanceIDs(autoScalingGroups[0].GetInstances());
            desiredCapacity = autoScalingGroups[0].GetDesiredCapacity();
        }
```

```
        if (instanceIDs.empty()) {
            if (desiredCapacity == 0) {
                break;
            }
            else {
                if ((count % 5) == 0) {
                    std::cout << "No instance IDs returned for group." <<
std::endl;
                }

                continue;
            }
        }

        // 6.  Check lifecycle state of the instances using
DescribeAutoScalingInstances.
        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const
Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
&instancesDetails =
                    outcome.GetResult().GetAutoScalingInstances();
            ready = instancesDetails.size() >= desiredCapacity;
            for (const Aws::AutoScaling::Model::AutoScalingInstanceDetails
&details: instancesDetails) {
                if (!stringInVector(details.GetLifecycleState(), READY_STATES)) {
                    ready = false;
                    break;
                }
            }
            // Log the status while waiting.
            if (((count % 5) == 1) || ready) {
                logInstancesLifecycleState(instancesDetails);
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
```

```
            return false;
        }
    }

    if (!describeGroup(groupName, autoScalingGroups, client)) {
        return false;
    }

    return true;
}

//! Routine to cleanup resources created in 'groupsAndInstancesScenario'.
/*!
 \sa cleanupResources()
 \param groupName: Optional Auto Scaling group name.
 \param templateName: Optional EC2 launch template name.
 \param autoScalingClient: 'AutoScalingClient' instance.
 \param ec2Client: 'EC2Client' instance.
\return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::cleanupResources(const Aws::String &groupName,
                                           const Aws::String &templateName,
                                           const
 Aws::AutoScaling::AutoScalingClient &autoScalingClient,
                                           const Aws::EC2::EC2Client &ec2Client)
 {
    bool result = true;

    // 14. Delete the Auto Scaling group.
    if (!groupName.empty() &&
        (askYesNoQuestion(
                Aws::String("Delete the Auto Scaling group '") + groupName +
                "'  (y/n)?"))) {
        {
            Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);
            request.SetMinSize(0);
            request.SetDesiredCapacity(0);

            Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                    autoScalingClient.UpdateAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout
```

```
                        << "The minimum size and desired capacity of the Auto
Scaling group "
                        << "was set to zero before terminating the instances."
                        << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                          << outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
        }

        Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
        if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                               autoScalingClient)) {
            if (!autoScalingGroups.empty()) {
                Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
                        autoScalingGroups[0].GetInstances());
                for (const Aws::String &instanceID: instanceIDs) {

Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
                    request.SetInstanceId(instanceID);
                    request.SetShouldDecrementDesiredCapacity(true);


Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome =

autoScalingClient.TerminateInstanceInAutoScalingGroup(
                                     request);

                    if (outcome.IsSuccess()) {
                        std::cout << "Initiating termination of EC2 instance '"
                                  << instanceID << "'." << std::endl;
                    }
                    else {
                        std::cerr
                                << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                                << outcome.GetError().GetMessage() << std::endl;
                        result = false;
                    }
                }
            }
```

```
            std::cout
                    << "Waiting for the EC2 instances to terminate before
deleting the "
                    << "Auto Scaling group..." << std::endl;
            waitForInstances(groupName, autoScalingGroups, autoScalingClient);
        }

        {
            Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);

            Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
                    autoScalingClient.DeleteAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout << "Auto Scaling group '" << groupName << "' was
deleted."
                          << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    // 15. Delete the EC2 launch template.
    if (!templateName.empty() && (askYesNoQuestion(
            Aws::String("Delete the EC2 launch template '") + templateName +
            "' (y/n)?"))) {
        Aws::EC2::Model::DeleteLaunchTemplateRequest request;
        request.SetLaunchTemplateName(templateName);

        Aws::EC2::Model::DeleteLaunchTemplateOutcome outcome =
                ec2Client.DeleteLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "EC2 launch template '" << templateName << "' was
deleted."
                      << std::endl;
        }
        else {
```

```
            std::cerr << "Error with EC2::DeleteLaunchTemplate. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Routine which retrieves Auto Scaling group descriptions.
/*!
 \sa describeGroup()
 \param groupName: An Auto Scaling group name.
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::describeGroup(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroup,
                                         const Aws::AutoScaling::AutoScalingClient
 &client) {
    // 5. Retrieve a description of the Auto Scaling group.
    Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
    Aws::Vector<Aws::String> groupNames;
    groupNames.push_back(groupName);
    request.SetAutoScalingGroupNames(groupNames);

    Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
            client.DescribeAutoScalingGroups(request);

    if (outcome.IsSuccess()) {
        autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
    }
    else {
        std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * In addition, create a launch template. For more information, see the
 * following topic:
 *
```

```
 * https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-
templates.html#create-launch-template
 *
 * This code example performs the following operations:
 * 1. Creates an Auto Scaling group using an AutoScalingWaiter.
 * 2. Gets a specific Auto Scaling group and returns an instance Id value.
 * 3. Describes Auto Scaling with the Id value.
 * 4. Enables metrics collection.
 * 5. Update an Auto Scaling group.
 * 6. Describes Account details.
 * 7. Describe account details"
 * 8. Updates an Auto Scaling group to use an additional instance.
 * 9. Gets the specific Auto Scaling group and gets the number of instances.
 * 10. List the scaling activities that have occurred for the group.
 * 11. Terminates an instance in the Auto Scaling group.
 * 12. Stops the metrics collection.
 * 13. Deletes the Auto Scaling group.
 */

public class AutoScalingScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <groupName> <launchTemplateName> <vpcZoneId>

                Where:
                    groupName - The name of the Auto Scaling group.
                    launchTemplateName - The name of the launch template.\s
                    vpcZoneId - A subnet Id for a virtual private cloud (VPC)
 where instances in the Auto Scaling group can be created.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        String launchTemplateName = args[1];
        String vpcZoneId = args[2];
```

```
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon EC2 Auto Scaling example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an Auto Scaling group named " + groupName);
        createAutoScalingGroup(autoScalingClient, groupName, launchTemplateName,
vpcZoneId);
        System.out.println(
                "Wait 1 min for the resources, including the instance. Otherwise,
an empty instance Id is returned");
        Thread.sleep(60000);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Get Auto Scale group Id value");
        String instanceId = getSpecificAutoScalingGroups(autoScalingClient,
groupName);
        if (instanceId.compareTo("") == 0) {
            System.out.println("Error - no instance Id value");
            System.exit(1);
        } else {
            System.out.println("The instance Id value is " + instanceId);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Describe Auto Scaling with the Id value " +
instanceId);
        describeAutoScalingInstance(autoScalingClient, instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Enable metrics collection " + instanceId);
        enableMetricsCollection(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("5. Update an Auto Scaling group to update max size to
3");
        updateAutoScalingGroup(autoScalingClient, groupName, launchTemplateName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Describe Auto Scaling groups");
        describeAutoScalingGroups(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Describe account details");
        describeAccountLimits(autoScalingClient);
        System.out.println(
                "Wait 1 min for the resources, including the instance. Otherwise,
an empty instance Id is returned");
        Thread.sleep(60000);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Set desired capacity to 2");
        setDesiredCapacity(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get the two instance Id values and state");
        getSpecificAutoScalingGroups(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. List the scaling activities that have occurred
for the group");
        describeScalingActivities(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Terminate an instance in the Auto Scaling
group");
        terminateInstanceInAutoScalingGroup(autoScalingClient, instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Stop the metrics collection");
        disableMetricsCollection(autoScalingClient, groupName);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Delete the Auto Scaling group");
        deleteAutoScalingGroup(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);

        autoScalingClient.close();
    }

    public static void describeScalingActivities(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DescribeScalingActivitiesRequest scalingActivitiesRequest =
DescribeScalingActivitiesRequest.builder()
                    .autoScalingGroupName(groupName)
                    .maxRecords(10)
                    .build();

            DescribeScalingActivitiesResponse response = autoScalingClient
                    .describeScalingActivities(scalingActivitiesRequest);
            List<Activity> activities = response.activities();
            for (Activity activity : activities) {
                System.out.println("The activity Id is " +
activity.activityId());
                System.out.println("The activity details are " +
activity.details());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void setDesiredCapacity(AutoScalingClient autoScalingClient,
String groupName) {
        try {
            SetDesiredCapacityRequest capacityRequest =
SetDesiredCapacityRequest.builder()
```

```
                    .autoScalingGroupName(groupName)
                    .desiredCapacity(2)
                    .build();

            autoScalingClient.setDesiredCapacity(capacityRequest);
            System.out.println("You have set the DesiredCapacity to 2");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createAutoScalingGroup(AutoScalingClient
autoScalingClient,
            String groupName,
            String launchTemplateName,
            String vpcZoneId) {
        try {
            AutoScalingWaiter waiter = autoScalingClient.waiter();
            LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                    .launchTemplateName(launchTemplateName)
                    .build();

            CreateAutoScalingGroupRequest request =
CreateAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .availabilityZones("us-east-1a")
                    .launchTemplate(templateSpecification)
                    .maxSize(1)
                    .minSize(1)
                    .vpcZoneIdentifier(vpcZoneId)
                    .build();

            autoScalingClient.createAutoScalingGroup(request);
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                    .waitUntilGroupExists(groupsRequest);
```

```
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Auto Scaling Group created");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void describeAutoScalingInstance(AutoScalingClient
autoScalingClient, String id) {
        try {
            DescribeAutoScalingInstancesRequest
describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest
                    .builder()
                    .instanceIds(id)
                    .build();

            DescribeAutoScalingInstancesResponse response = autoScalingClient

.describeAutoScalingInstances(describeAutoScalingInstancesRequest);
            List<AutoScalingInstanceDetails> instances =
response.autoScalingInstances();
            for (AutoScalingInstanceDetails instance : instances) {
                System.out.println("The instance lifecycle state is: " +
instance.lifecycleState());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void describeAutoScalingGroups(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .maxRecords(10)
                    .build();
```

```
            DescribeAutoScalingGroupsResponse response =
autoScalingClient.describeAutoScalingGroups(groupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("*** The service to use for the health checks:
" + group.healthCheckType());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String getSpecificAutoScalingGroups(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            String instanceId = "";
            DescribeAutoScalingGroupsRequest scalingGroupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            DescribeAutoScalingGroupsResponse response = autoScalingClient
                    .describeAutoScalingGroups(scalingGroupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("The group name is " +
group.autoScalingGroupName());
                System.out.println("The group ARN is " +
group.autoScalingGroupARN());
                List<Instance> instances = group.instances();

                for (Instance instance : instances) {
                    instanceId = instance.instanceId();
                    System.out.println("The instance id is " + instanceId);
                    System.out.println("The lifecycle state is " +
instance.lifecycleState());
                }
            }

            return instanceId;
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        return "";
    }

    public static void enableMetricsCollection(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            EnableMetricsCollectionRequest collectionRequest =
EnableMetricsCollectionRequest.builder()
                    .autoScalingGroupName(groupName)
                    .metrics("GroupMaxSize")
                    .granularity("1Minute")
                    .build();

            autoScalingClient.enableMetricsCollection(collectionRequest);
            System.out.println("The enable metrics collection operation was
successful");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void disableMetricsCollection(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DisableMetricsCollectionRequest disableMetricsCollectionRequest =
DisableMetricsCollectionRequest.builder()
                    .autoScalingGroupName(groupName)
                    .metrics("GroupMaxSize")
                    .build();


autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest);
            System.out.println("The disable metrics collection operation was
successful");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static void describeAccountLimits(AutoScalingClient autoScalingClient)
{
       try {
           DescribeAccountLimitsResponse response =
autoScalingClient.describeAccountLimits();
           System.out.println("The max number of auto scaling groups is " +
response.maxNumberOfAutoScalingGroups());
           System.out.println("The current number of auto scaling groups is " +
response.numberOfAutoScalingGroups());

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void updateAutoScalingGroup(AutoScalingClient
autoScalingClient, String groupName,
           String launchTemplateName) {
       try {
           AutoScalingWaiter waiter = autoScalingClient.waiter();
           LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                   .launchTemplateName(launchTemplateName)
                   .build();

           UpdateAutoScalingGroupRequest groupRequest =
UpdateAutoScalingGroupRequest.builder()
                   .maxSize(3)
                   .autoScalingGroupName(groupName)
                   .launchTemplate(templateSpecification)
                   .build();

           autoScalingClient.updateAutoScalingGroup(groupRequest);
           DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                   .autoScalingGroupNames(groupName)
                   .build();

           WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                   .waitUntilGroupInService(groupsRequest);
           waiterResponse.matched().response().ifPresent(System.out::println);
```

```
            System.out.println("You successfully updated the auto scaling group
" + groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void terminateInstanceInAutoScalingGroup(AutoScalingClient
autoScalingClient, String instanceId) {
        try {
            TerminateInstanceInAutoScalingGroupRequest request =
TerminateInstanceInAutoScalingGroupRequest.builder()
                    .instanceId(instanceId)
                    .shouldDecrementDesiredCapacity(false)
                    .build();

            autoScalingClient.terminateInstanceInAutoScalingGroup(request);
            System.out.println("You have terminated instance " + instanceId);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteAutoScalingGroup(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .forceDelete(true)
                    .build();


autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
            System.out.println("You successfully deleted " + groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <groupName> <launchTemplateName> <serviceLinkedRoleARN> <vpcZoneId>

    Where:
        groupName - The name of the Auto Scaling group.
        launchTemplateName - The name of the launch template.
        serviceLinkedRoleARN - The Amazon Resource Name (ARN) of the service-
linked role that the Auto Scaling group uses.
```

```
        vpcZoneId - A subnet Id for a virtual private cloud (VPC) where instances
in the Auto Scaling group can be created.
    """

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val groupName = args[0]
    val launchTemplateName = args[1]
    val serviceLinkedRoleARN = args[2]
    val vpcZoneId = args[3]

    println("**** Create an Auto Scaling group named $groupName")
    createAutoScalingGroup(groupName, launchTemplateName, serviceLinkedRoleARN,
vpcZoneId)

    println("Wait 1 min for the resources, including the instance. Otherwise, an
empty instance Id is returned")
    delay(60000)

    val instanceId = getSpecificAutoScaling(groupName)
    if (instanceId.compareTo("") == 0) {
        println("Error - no instance Id value")
        exitProcess(1)
    } else {
        println("The instance Id value is $instanceId")
    }

    println("**** Describe Auto Scaling with the Id value $instanceId")
    describeAutoScalingInstance(instanceId)

    println("**** Enable metrics collection $instanceId")
    enableMetricsCollection(groupName)

    println("**** Update an Auto Scaling group to maximum size of 3")
    updateAutoScalingGroup(groupName, launchTemplateName, serviceLinkedRoleARN)

    println("**** Describe all Auto Scaling groups to show the current state of
the groups")
    describeAutoScalingGroups(groupName)

    println("**** Describe account details")
```

```
    describeAccountLimits()

    println("Wait 1 min for the resources, including the instance. Otherwise, an
 empty instance Id is returned")
    delay(60000)

    println("**** Set desired capacity to 2")
    setDesiredCapacity(groupName)

    println("**** Get the two instance Id values and state")
    getAutoScalingGroups(groupName)

    println("**** List the scaling activities that have occurred for the group")
    describeScalingActivities(groupName)

    println("**** Terminate an instance in the Auto Scaling group")
    terminateInstanceInAutoScalingGroup(instanceId)

    println("**** Stop the metrics collection")
    disableMetricsCollection(groupName)

    println("**** Delete the Auto Scaling group")
    deleteSpecificAutoScalingGroup(groupName)
}

suspend fun describeAutoScalingGroups(groupName: String) {
    val groupsReques = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
        maxRecords = 10
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response = autoScalingClient.describeAutoScalingGroups(groupsReques)
        response.autoScalingGroups?.forEach { group ->
            println("The service to use for the health checks:
 ${group.healthCheckType}")
        }
    }
}

suspend fun disableMetricsCollection(groupName: String) {
    val disableMetricsCollectionRequest = DisableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
```

```
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->

 autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest)
        println("The disable metrics collection operation was successful")
    }
}

suspend fun describeScalingActivities(groupName: String?) {
    val scalingActivitiesRequest = DescribeScalingActivitiesRequest {
        autoScalingGroupName = groupName
        maxRecords = 10
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeScalingActivities(scalingActivitiesRequest)
        response.activities?.forEach { activity ->
            println("The activity Id is ${activity.activityId}")
            println("The activity details are ${activity.details}")
        }
    }
}

suspend fun getAutoScalingGroups(groupName: String) {
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")
            group.instances?.forEach { instance ->
                println("The instance id is ${instance.instanceId}")
                println("The lifecycle state is " + instance.lifecycleState)
            }
        }
    }
}
```

```
suspend fun setDesiredCapacity(groupName: String) {
    val capacityRequest = SetDesiredCapacityRequest {
        autoScalingGroupName = groupName
        desiredCapacity = 2
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.setDesiredCapacity(capacityRequest)
        println("You set the DesiredCapacity to 2")
    }
}

suspend fun updateAutoScalingGroup(groupName: String, launchTemplateNameVal:
 String, serviceLinkedRoleARNVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val groupRequest = UpdateAutoScalingGroupRequest {
        maxSize = 3
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
        autoScalingGroupName = groupName
        launchTemplate = templateSpecification
    }

    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.updateAutoScalingGroup(groupRequest)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("You successfully updated the Auto Scaling group  $groupName")
    }
}

suspend fun createAutoScalingGroup(groupName: String, launchTemplateNameVal:
 String, serviceLinkedRoleARNVal: String, vpcZoneIdVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val request = CreateAutoScalingGroupRequest {
        autoScalingGroupName = groupName
```

```
        availabilityZones = listOf("us-east-1a")
        launchTemplate = templateSpecification
        maxSize = 1
        minSize = 1
        vpcZoneIdentifier = vpcZoneIdVal
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
    }

    // This object is required for the waiter call.
    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.createAutoScalingGroup(request)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("$groupName was created!")
    }
}

suspend fun describeAutoScalingInstance(id: String) {
    val describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest
 {
        instanceIds = listOf(id)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingInstances(describeAutoScalingInstancesRequest)
        response.autoScalingInstances?.forEach { group ->
            println("The instance lifecycle state is: ${group.lifecycleState}")
        }
    }
}

suspend fun enableMetricsCollection(groupName: String?) {
    val collectionRequest = EnableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
        granularity = "1Minute"
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.enableMetricsCollection(collectionRequest)
```

```
        println("The enable metrics collection operation was successful")
    }
}

suspend fun getSpecificAutoScaling(groupName: String): String {
    var instanceId = ""
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")

            group.instances?.forEach { instance ->
                instanceId = instance.instanceId.toString()
            }
        }
    }
    return instanceId
}

suspend fun describeAccountLimits() {
    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAccountLimits(DescribeAccountLimitsRequest {})
        println("The max number of Auto Scaling groups is
 ${response.maxNumberOfAutoScalingGroups}")
        println("The current number of Auto Scaling groups is
 ${response.numberOfAutoScalingGroups}")
    }
}

suspend fun terminateInstanceInAutoScalingGroup(instanceIdVal: String) {
    val request = TerminateInstanceInAutoScalingGroupRequest {
        instanceId = instanceIdVal
        shouldDecrementDesiredCapacity = false
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.terminateInstanceInAutoScalingGroup(request)
```

```
        println("You have terminated instance $instanceIdVal")
    }
}

suspend fun deleteSpecificAutoScalingGroup(groupName: String) {
    val deleteAutoScalingGroupRequest = DeleteAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        forceDelete = true
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest)
        println("You successfully deleted $groupName")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace AutoScaling;

use Aws\AutoScaling\AutoScalingClient;
use Aws\CloudWatch\CloudWatchClient;
use Aws\Ec2\Ec2Client;
use AwsUtilities\AWSServiceClass;
use AwsUtilities\RunnableExample;

class GettingStartedWithAutoScaling implements RunnableExample
{
    protected Ec2Client $ec2Client;
    protected AutoScalingClient $autoScalingClient;
    protected AutoScalingService $autoScalingService;
    protected CloudWatchClient $cloudWatchClient;
    protected string $templateName;
    protected string $autoScalingGroupName;
    protected array $role;

    public function runExample()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon EC2 Auto Scaling getting started demo using
 PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();
```

```
        $this->autoScalingClient = new AutoScalingClient($clientArgs);
        $this->autoScalingService = new AutoScalingService($this-
>autoScalingClient);
        $this->cloudWatchClient = new CloudWatchClient($clientArgs);

        AWSServiceClass::$waitTime = 5;
        AWSServiceClass::$maxWaitAttempts = 20;

        /**
         * Step 0: Create an EC2 launch template that you'll use to create an
 Auto Scaling group.
         */
        $this->ec2Client = new EC2Client($clientArgs);
        $this->templateName = "example_launch_template_$uniqid";
        $instanceType = "t1.micro";
        $amiId = "ami-0ca285d4c2cda3300";
        $launchTemplate = $this->ec2Client->createLaunchTemplate(
            [
            'LaunchTemplateName' => $this->templateName,
            'LaunchTemplateData' => [
                'InstanceType' => $instanceType,
                'ImageId' => $amiId,
            ]
            ]
        );

        /**
         * Step 1: CreateAutoScalingGroup: pass it the launch template you
 created in step 0.
         */
        $availabilityZones[] = $this->ec2Client->describeAvailabilityZones([])
['AvailabilityZones'][1]['ZoneName'];

        $this->autoScalingGroupName = "demoAutoScalingGroupName_$uniqid";
        $minSize = 1;
        $maxSize = 1;
        $launchTemplateId = $launchTemplate['LaunchTemplate']
['LaunchTemplateId'];
        $this->autoScalingService->createAutoScalingGroup(
            $this->autoScalingGroupName,
            $availabilityZones,
            $minSize,
            $maxSize,
```

```
            $launchTemplateId
        );

        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        $autoScalingGroup = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);

        /**
         * Step 2: DescribeAutoScalingInstances: show that one instance has
 launched.
         */
        $instanceIds = [$autoScalingGroup['AutoScalingGroups'][0]['Instances'][0]
['InstanceId']];
        $instances = $this->autoScalingService-
>describeAutoScalingInstances($instanceIds);
        echo "The Auto Scaling group {$this->autoScalingGroupName} was created
 successfully.\n";
        echo count($instances['AutoScalingInstances']) . " instances were created
 for the group.\n";
        echo $autoScalingGroup['AutoScalingGroups'][0]['MaxSize'] . " is the max
 number of instances for the group.\n";

        /**
         * Step 3: EnableMetricsCollection: enable all metrics or a subset.
         */
        $this->autoScalingService->enableMetricsCollection($this-
>autoScalingGroupName, "1Minute");

        /**
         * Step 4: UpdateAutoScalingGroup: update max size to 3.
         */
        echo "Updating the max number of instances to 3.\n";
        $this->autoScalingService->updateAutoScalingGroup($this-
>autoScalingGroupName, ['MaxSize' => 3]);

        /**
         * Step 5: DescribeAutoScalingGroups: show the current state of the
 group.
         */
        $autoScalingGroup = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
        echo $autoScalingGroup['AutoScalingGroups'][0]['MaxSize'];
        echo " is the updated max number of instances for the group.\n";
```

```
        $limits = $this->autoScalingService->describeAccountLimits();
        echo "Here are your account limits:\n";
        echo "MaxNumberOfAutoScalingGroups:
 {$limits['MaxNumberOfAutoScalingGroups']}\n";
        echo "MaxNumberOfLaunchConfigurations:
 {$limits['MaxNumberOfLaunchConfigurations']}\n";
        echo "NumberOfAutoScalingGroups:
 {$limits['NumberOfAutoScalingGroups']}\n";
        echo "NumberOfLaunchConfigurations:
 {$limits['NumberOfLaunchConfigurations']}\n";

        /**
         * Step 6: SetDesiredCapacity: set desired capacity to 2.
         */
        $this->autoScalingService->setDesiredCapacity($this-
>autoScalingGroupName, 2);
        sleep(10); // Wait for the group to start processing the request.
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);

        /**
         * Step 7: DescribeAutoScalingInstances: show that two instances are
 launched.
         */
        $autoScalingGroups = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
        foreach ($autoScalingGroups['AutoScalingGroups'] as $autoScalingGroup) {
            echo "There is a group named:
 {$autoScalingGroup['AutoScalingGroupName']}";
            echo "with an ARN of {$autoScalingGroup['AutoScalingGroupARN']}.\n";
            foreach ($autoScalingGroup['Instances'] as $instance) {
                echo "{$autoScalingGroup['AutoScalingGroupName']} has an instance
 with id of: ";
                echo "{$instance['InstanceId']} and a lifecycle state of:
 {$instance['LifecycleState']}.\n";
            }
        }

        /**
         * Step 8: TerminateInstanceInAutoScalingGroup: terminate one of the
 instances in the group.
         */
```

```
        $this->autoScalingService-
>terminateInstanceInAutoScalingGroup($instance['InstanceId'], false);
        do {
            sleep(10);
            $instances = $this->autoScalingService-
>describeAutoScalingInstances([$instance['InstanceId']]);
        } while (count($instances['AutoScalingInstances']) > 0);
        do {
            sleep(10);
            $autoScalingGroups = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
            $instances = $autoScalingGroups['AutoScalingGroups'][0]['Instances'];
        } while (count($instances) < 2);
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        foreach ($autoScalingGroups['AutoScalingGroups'] as $autoScalingGroup) {
            echo "There is a group named:
 {$autoScalingGroup['AutoScalingGroupName']}";
            echo "with an ARN of {$autoScalingGroup['AutoScalingGroupARN']}.\n";
            foreach ($autoScalingGroup['Instances'] as $instance) {
                echo "{$autoScalingGroup['AutoScalingGroupName']} has an instance
 with id of: ";
                echo "{$instance['InstanceId']} and a lifecycle state of:
 {$instance['LifecycleState']}.\n";
            }
        }

        /**
         * Step 9: DescribeScalingActivities: list the scaling activities that
 have occurred for the group so far.
         */
        $activities = $this->autoScalingService-
>describeScalingActivities($autoScalingGroup['AutoScalingGroupName']);
        echo "We found " . count($activities['Activities']) . " activities.\n";
        foreach ($activities['Activities'] as $activity) {
            echo "{$activity['ActivityId']} - {$activity['StartTime']} -
 {$activity['Description']}\n";
        }

        /**
         * Step 10: Use the Amazon CloudWatch API to get and show some metrics
 collected for the group.
         */
        $metricsNamespace = 'AWS/AutoScaling';
```

```
        $metricsDimensions = [
            [
                'Name' => 'AutoScalingGroupName',
                'Value' => $autoScalingGroup['AutoScalingGroupName'],
            ],
        ];
        $metrics = $this->cloudWatchClient->listMetrics(
            [
            'Dimensions' => $metricsDimensions,
            'Namespace' => $metricsNamespace,
            ]
        );
        foreach ($metrics['Metrics'] as $metric) {
            $timespan = 5;
            if ($metric['MetricName'] != 'GroupTotalCapacity' &&
$metric['MetricName'] != 'GroupMaxSize') {
                continue;
            }
            echo "Over the last $timespan minutes, {$metric['MetricName']}
recorded:\n";
            $stats = $this->cloudWatchClient->getMetricStatistics(
                [
                'Dimensions' => $metricsDimensions,
                'EndTime' => time(),
                'StartTime' => time() - (5 * 60),
                'MetricName' => $metric['MetricName'],
                'Namespace' => $metricsNamespace,
                'Period' => 60,
                'Statistics' => ['Sum'],
                ]
            );
            foreach ($stats['Datapoints'] as $stat) {
                echo "{$stat['Timestamp']}: {$stat['Sum']}\n";
            }
        }

        return $instances;
    }

    public function cleanUp()
    {
        /**
         * Step 11: DisableMetricsCollection: disable all metrics.
         */
```

```
        $this->autoScalingService->disableMetricsCollection($this-
>autoScalingGroupName);

        /**
         * Step 12: DeleteAutoScalingGroup: to delete the group you must stop all
 instances.
         * - UpdateAutoScalingGroup with MinSize=0
         * - TerminateInstanceInAutoScalingGroup for each instance,
         *     specify ShouldDecrementDesiredCapacity=True. Wait for instances to
 stop.
         * - Now you can delete the group.
         */
        $this->autoScalingService->updateAutoScalingGroup($this-
>autoScalingGroupName, ['MinSize' => 0]);
        $this->autoScalingService->terminateAllInstancesInAutoScalingGroup($this-
>autoScalingGroupName);
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        $this->autoScalingService->deleteAutoScalingGroup($this-
>autoScalingGroupName);

        /**
         * Step 13: Delete launch template.
         */
        $this->ec2Client->deleteLaunchTemplate(
            [
            'LaunchTemplateName' => $this->templateName,
            ]
        );
    }

    public function helloService()
    {
        $autoScalingClient = new AutoScalingClient([
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ]);

        $groups = $autoScalingClient->describeAutoScalingGroups([]);
        var_dump($groups);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
def run_scenario(as_wrapper, svc_helper):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print(
        "Welcome to the Amazon EC2 Auto Scaling demo for managing groups and
 instances."
    )
    print("-" * 88)
```

```
    print(
        "This example requires a launch template that specifies how to create\n"
        "EC2 instances. You can use an existing template or create a new one."
    )
    template_name = q.ask(
        "Enter the name of an existing launch template or press Enter to create a
new one: "
    )
    template = None
    if template_name:
        template = svc_helper.get_template(template_name)
    if template is None:
        inst_type = "t1.micro"
        ami_id = "ami-0ca285d4c2cda3300"
        print("Let's create a launch template with the following
specifications:")
        print(f"\tInstanceType: {inst_type}")
        print(f"\tAMI ID: {ami_id}")
        template_name = q.ask("Enter a name for the template: ", q.non_empty)
        template = svc_helper.create_template(template_name, inst_type, ami_id)
    print("-" * 88)

    print("Let's create an Auto Scaling group.")
    group_name = q.ask("Enter a name for the group: ", q.non_empty)
    zones = svc_helper.get_availability_zones()
    print("EC2 instances can be created in the following Availability Zones:")
    for index, zone in enumerate(zones):
        print(f"\t{index+1}. {zone}")
    print(f"\t{len(zones)+1}. All zones")
    zone_sel = q.ask(
        "Which zone do you want to use? ", q.is_int, q.in_range(1, len(zones) +
1)
    )
    group_zones = [zones[zone_sel - 1]] if zone_sel <= len(zones) else zones
    print(f"Creating group {group_name}...")
    as_wrapper.create_group(group_name, group_zones, template_name, 1, 1)
    wait(10)
    group = as_wrapper.describe_group(group_name)
    print("Created group:")
    pp(group)
    print("Waiting for instance to start...")
    wait_for_group(group_name, as_wrapper)
    print("-" * 88)
```

```
    use_metrics = q.ask(
        "Do you want to collect metrics about Amazon EC2 Auto Scaling during this
demo (y/n)? ",
        q.is_yesno,
    )
    if use_metrics:
        as_wrapper.enable_metrics(
            group_name,
            [
                "GroupMinSize",
                "GroupMaxSize",
                "GroupDesiredCapacity",
                "GroupInServiceInstances",
                "GroupTotalInstances",
            ],
        )
        print(f"Metrics enabled for {group_name}.")
    print("-" * 88)

    print(f"Let's update the maximum number of instances in {group_name} from 1
to 3.")
    q.ask("Press Enter when you're ready.")
    as_wrapper.update_group(group_name, MaxSize=3)
    group = as_wrapper.describe_group(group_name)
    print("The group still has one running instance, but can have up to three:")
    print_simplified_group(group)
    print("-" * 88)

    print(f"Let's update the desired capacity of {group_name} from 1 to 2.")
    q.ask("Press Enter when you're ready.")
    as_wrapper.set_desired_capacity(group_name, 2)
    wait(10)
    group = as_wrapper.describe_group(group_name)
    print("Here's the current state of the group:")
    print_simplified_group(group)
    print("-" * 88)
    print("Waiting for the new instance to start...")
    instance_ids = wait_for_group(group_name, as_wrapper)
    print("-" * 88)

    print(f"Let's terminate one of the instances in {group_name}.")
    print("Because the desired capacity is 2, another instance will start.")
    print("The currently running instances are:")
    for index, inst_id in enumerate(instance_ids):
```

```
        print(f"\t{index+1}. {inst_id}")
    inst_sel = q.ask(
        "Which instance do you want to stop? ",
        q.is_int,
        q.in_range(1, len(instance_ids) + 1),
    )
    print(f"Stopping {instance_ids[inst_sel-1]}...")
    as_wrapper.terminate_instance(instance_ids[inst_sel - 1], False)
    wait(10)
    group = as_wrapper.describe_group(group_name)
    print(f"Here's the state of {group_name}:")
    print_simplified_group(group)
    print("Waiting for the scaling activities to complete...")
    wait_for_group(group_name, as_wrapper)
    print("-" * 88)

    print(f"Let's get a report of scaling activities for {group_name}.")
    q.ask("Press Enter when you're ready.")
    activities = as_wrapper.describe_scaling_activities(group_name)
    print(
        f"Found {len(activities)} activities.\n"
        f"Activities are ordered with the most recent one first:"
    )
    for act in activities:
        pp(act)
    print("-" * 88)

    if use_metrics:
        print("Let's look at CloudWatch metrics.")
        metric_namespace = "AWS/AutoScaling"
        metric_dimensions = [{"Name": "AutoScalingGroupName", "Value":
 group_name}]
        print(f"The following metrics are enabled for {group_name}:")
        done = False
        while not done:
            metrics = svc_helper.get_metrics(metric_namespace, metric_dimensions)
            for index, metric in enumerate(metrics):
                print(f"\t{index+1}. {metric.name}")
            print(f"\t{len(metrics)+1}. None")
            metric_sel = q.ask(
                "Which metric do you want to see? ",
                q.is_int,
                q.in_range(1, len(metrics) + 1),
            )
```

```
            if metric_sel < len(metrics) + 1:
                span = 5
                metric = metrics[metric_sel - 1]
                print(f"Over the last {span} minutes, {metric.name} recorded:")
                # CloudWatch metric times are in the UTC+0 time zone.
                now = datetime.now(timezone.utc)
                metric_data = svc_helper.get_metric_statistics(
                    metric_dimensions, metric, now - timedelta(minutes=span), now
                )
                pp(metric_data)
                if not q.ask("Do you want to see another metric (y/n)? ",
q.is_yesno):
                    done = True
            else:
                done = True

    print(f"Let's clean up.")
    q.ask("Press Enter when you're ready.")
    if use_metrics:
        print(f"Stopping metrics collection for {group_name}.")
        as_wrapper.disable_metrics(group_name)

    print(
        "You must terminate all instances in the group before you can delete the
group."
    )
    print("Set minimum size to 0.")
    as_wrapper.update_group(group_name, MinSize=0)
    group = as_wrapper.describe_group(group_name)
    instance_ids = [inst["InstanceId"] for inst in group["Instances"]]
    for inst_id in instance_ids:
        print(f"Stopping {inst_id}.")
        as_wrapper.terminate_instance(inst_id, True)
    print("Waiting for instances to stop...")
    wait_for_instances(instance_ids, as_wrapper)
    print(f"Deleting {group_name}.")
    as_wrapper.delete_group(group_name)
    print("-" * 88)

    if template is not None:
        if q.ask(
            f"Do you want to delete launch template {template_name} used in this
demo (y/n)? "
        ):
```

```
            svc_helper.delete_template(template_name)
            print("Template deleted.")

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        wrapper = AutoScalingWrapper(boto3.client("autoscaling"))
        helper = ServiceHelper(boto3.client("ec2"), boto3.resource("cloudwatch"))
        run_scenario(wrapper, helper)
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

Definir as funções que são chamadas pelo cenário para gerenciar modelos e métricas de lançamento. Essas funções envolvem o Amazon EC2 e CloudWatch as ações.

```
class ServiceHelper:
    """Encapsulates Amazon EC2 and CloudWatch actions for the example."""

    def __init__(self, ec2_client, cloudwatch_resource):
        """
        :param ec2_client: A Boto3 Amazon EC2 client.
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.ec2_client = ec2_client
        self.cloudwatch_resource = cloudwatch_resource

    def get_template(self, template_name):
        """
        Gets a launch template. Launch templates specify configuration for
 instances
        that are launched by Amazon EC2 Auto Scaling.

        :param template_name: The name of the template to look up.
        :return: The template, if it exists.
        """
        try:
            response = self.ec2_client.describe_launch_templates(
                LaunchTemplateNames=[template_name]
            )
```

```
            template = response["LaunchTemplates"][0]
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                logger.warning("Launch template %s does not exist.",
template_name)
            else:
                logger.error(
                    "Couldn't verify launch template %s. Here's why: %s: %s",
                    template_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return template

    def create_template(self, template_name, inst_type, ami_id):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling.

        :param template_name: The name to give to the template.
        :param inst_type: The type of the instance, such as t1.micro.
        :param ami_id: The ID of the Amazon Machine Image (AMI) to use when
creating
                       an instance.
        :return: Information about the newly created template.
        """
        try:
            response = self.ec2_client.create_launch_template(
                LaunchTemplateName=template_name,
                LaunchTemplateData={"InstanceType": inst_type, "ImageId":
ami_id},
            )
            template = response["LaunchTemplate"]
        except ClientError as err:
            logger.error(
                "Couldn't create launch template %s. Here's why: %s: %s",
                template_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return template

    def delete_template(self, template_name):
        """
        Deletes a launch template.

        :param template_name: The name of the template to delete.
        """
        try:

self.ec2_client.delete_launch_template(LaunchTemplateName=template_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete launch template %s. Here's why: %s: %s",
                template_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            logger.error(
                "Couldn't get availability zones. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return zones

    def get_metrics(self, namespace, dimensions):
```

```
        """
        Gets a list of CloudWatch metrics filtered by namespace and dimensions.

        :param namespace: The namespace of the metrics to look up.
        :param dimensions: The dimensions of the metrics to look up.
        :return: The list of metrics.
        """
        try:
            metrics = list(
                self.cloudwatch_resource.metrics.filter(
                    Namespace=namespace, Dimensions=dimensions
                )
            )
        except ClientError as err:
            logger.error(
                "Couldn't get metrics for %s, %s. Here's why: %s: %s",
                namespace,
                dimensions,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return metrics

    @staticmethod
    def get_metric_statistics(dimensions, metric, start, end):
        """
        Gets statistics for a CloudWatch metric within a specified time span.

        :param dimensions: The dimensions of the metric.
        :param metric: The metric to look up.
        :param start: The start of the time span for retrieved metrics.
        :param end: The end of the time span for retrieved metrics.
        :return: The list of data points found for the specified metric.
        """
        try:
            response = metric.get_statistics(
                Dimensions=dimensions,
                StartTime=start,
                EndTime=end,
                Period=60,
                Statistics=["Sum"],
            )
```

```
            data = response["Datapoints"]
        except ClientError as err:
            logger.error(
                "Couldn't get statistics for metric %s. Here's why: %s: %s",
                metric.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return data


def print_simplified_group(group):
    """
    Prints a subset of data for an Auto Scaling group.
    """
    print(group["AutoScalingGroupName"])
    print(f"\tLaunch template: {group['LaunchTemplate']['LaunchTemplateName']}")
    print(
        f"\tMin: {group['MinSize']}, Max: {group['MaxSize']}, Desired:
 {group['DesiredCapacity']}"
    )
    if group["Instances"]:
        print(f"\tInstances:")
        for inst in group["Instances"]:
            print(f"\t\t{inst['InstanceId']}: {inst['LifecycleState']}")


def wait_for_group(group_name, as_wrapper):
    """
    Waits for instances to start or stop in an Auto Scaling group.
    Prints the data for each instance after scaling activities are complete.
    """
    group = as_wrapper.describe_group(group_name)
    instance_ids = [i["InstanceId"] for i in group["Instances"]]
    return wait_for_instances(instance_ids, as_wrapper)


def wait_for_instances(instance_ids, as_wrapper):
    """
    Waits for instances to start or stop in an Auto Scaling group.
    Prints the data for each instance after scaling activities are complete.
    """
```

```
    ready = False
    instances = []
    while not ready:
        instances = as_wrapper.describe_instances(instance_ids) if instance_ids
else []
        if all([x["LifecycleState"] in ["Terminated", "InService"] for x in
instances]):
            ready = True
        else:
            wait(10)
    if instances:
        print(
            f"Here are the details of the instance{'s' if len(instances) > 1 else
''}:"
        )
        for instance in instances:
            pp(instance)
    return instance_ids
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
[package]
name = "autoscaling-code-examples"
version = "0.1.0"
authors = ["Doug Schwartz <dougsch@amazon.com>", "David Souther
 <dpsouth@amazon.com>"]
edition = "2021"

# See more keys and their definitions at https://doc.rust-lang.org/cargo/
reference/manifest.html

[dependencies]
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-sdk-autoscaling = { version = "1.3.0" }
aws-sdk-ec2 = { version = "1.3.0" }
aws-types = { version = "1.0.1" }
tokio = { version = "1.20.1", features = ["full"] }
clap = { version = "~4.4", features = ["derive"] }
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
anyhow = "1.0.75"
tracing = "0.1.37"
tokio-stream = "0.1.14"

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::{collections::BTreeSet, fmt::Display};

use anyhow::anyhow;
use autoscaling_code_examples::scenario::{AutoScalingScenario, ScenarioError};
use tracing::{info, warn};

async fn show_scenario_description(scenario: &AutoScalingScenario, event: &str) {
```

```
    let description = scenario.describe_scenario().await;
    info!("DescribeAutoScalingInstances: {event}\n{description}");
}

#[derive(Default, Debug)]
struct Warnings(Vec<String>);

impl Warnings {
    pub fn push(&mut self, warning: &str, error: ScenarioError) {
        let formatted = format!("{warning}: {error}");
        warn!("{formatted}");
        self.0.push(formatted);
    }

    pub fn is_empty(&self) -> bool {
        self.0.is_empty()
    }
}

impl Display for Warnings {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "Warnings:")?;
        for warning in &self.0 {
            writeln!(f, "{: >4}- {warning}", "")?;
        }
        Ok(())
    }
}

#[tokio::main]
async fn main() -> Result<(), anyhow::Error> {
    tracing_subscriber::fmt::init();

    let shared_config = aws_config::from_env().load().await;

    let mut warnings = Warnings::default();

    // 1. Create an EC2 launch template that you'll use to create an auto scaling
 group. Bonus: use SDK with EC2.CreateLaunchTemplate to create the launch
 template.
    // 2. CreateAutoScalingGroup: pass it the launch template you created in step
 0. Give it min/max of 1 instance.
    // 4. EnableMetricsCollection: enable all metrics or a subset.
```

```
    let scenario = match
AutoScalingScenario::prepare_scenario(&shared_config).await {
        Ok(scenario) => scenario,
        Err(errs) => {
            let err_str = errs
                .into_iter()
                .map(|e| e.to_string())
                .collect::<Vec<String>>()
                .join(", ");
            return Err(anyhow!("Failed to initialize scenario: {err_str}"));
        }
    };

    info!("Prepared autoscaling scenario:\n{scenario}");

    let stable = scenario.wait_for_stable(1).await;
    if let Err(err) = stable {
        warnings.push(
            "There was a problem while waiting for group to be stable",
            err,
        );
    }

    // 3. DescribeAutoScalingInstances: show that one instance has launched.
    show_scenario_description(
        &scenario,
        "show that the group was created and one instance has launched",
    )
    .await;

    // 5. UpdateAutoScalingGroup: update max size to 3.
    let scale_max_size = scenario.scale_max_size(3).await;
    if let Err(err) = scale_max_size {
        warnings.push("There was a problem scaling max size", err);
    }

    // 6. DescribeAutoScalingGroups: the current state of the group
    show_scenario_description(
        &scenario,
        "show the current state of the group after setting max size",
    )
    .await;

    // 7. SetDesiredCapacity: set desired capacity to 2.
```

```
    let scale_desired_capacity = scenario.scale_desired_capacity(2).await;
    if let Err(err) = scale_desired_capacity {
        warnings.push("There was a problem setting desired capacity", err);
    }

    //   Wait for a second instance to launch.
    let stable = scenario.wait_for_stable(2).await;
    if let Err(err) = stable {
        warnings.push(
            "There was a problem while waiting for group to be stable",
            err,
        );
    }

    // 8. DescribeAutoScalingInstances: show that two instances are launched.
    show_scenario_description(
        &scenario,
        "show that two instances are launched after setting desired capacity",
    )
    .await;

    let ids_before = scenario
        .list_instances()
        .await
        .map(|v| v.into_iter().collect::<BTreeSet<_>>())
        .unwrap_or_default();

    // 9. TerminateInstanceInAutoScalingGroup: terminate one of the instances in
 the group.
    let terminate_some_instance = scenario.terminate_some_instance().await;
    if let Err(err) = terminate_some_instance {
        warnings.push("There was a problem replacing an instance", err);
    }

    let wait_after_terminate = scenario.wait_for_stable(1).await;
    if let Err(err) = wait_after_terminate {
        warnings.push(
            "There was a problem waiting after terminating an instance",
            err,
        );
    }

    let wait_scale_up_after_terminate = scenario.wait_for_stable(2).await;
    if let Err(err) = wait_scale_up_after_terminate {
```

```
        warnings.push(
            "There was a problem waiting for scale up after terminating an
instance",
            err,
        );
    }

    let ids_after = scenario
        .list_instances()
        .await
        .map(|v| v.into_iter().collect::<BTreeSet<_>>())
        .unwrap_or_default();

    let difference = ids_after.intersection(&ids_before).count();
    if !(difference == 1 && ids_before.len() == 2 && ids_after.len() == 2) {
        warnings.push(
            "Before and after set not different",
            ScenarioError::with(format!("{difference}")),
        );
    }

    // 10. DescribeScalingActivities: list the scaling activities that have
occurred for the group so far.
    show_scenario_description(
        &scenario,
        "list the scaling activities that have occurred for the group so far",
    )
    .await;

    // 11. DisableMetricsCollection
    let scale_group = scenario.scale_group_to_zero().await;
    if let Err(err) = scale_group {
        warnings.push("There was a problem scaling the group to 0", err);
    }
    show_scenario_description(&scenario, "Scenario scaled to 0").await;

    // 12. DeleteAutoScalingGroup (to delete the group you must stop all
instances):
    // 13. Delete LaunchTemplate.
    let clean_scenario = scenario.clean_scenario().await;
    if let Err(errs) = clean_scenario {
        for err in errs {
            warnings.push("There was a problem cleaning the scenario", err);
        }
```

```
    } else {
        info!("The scenario has been cleaned up!");
    }

    if warnings.is_empty() {
        Ok(())
    } else {
        Err(anyhow!(
            "There were warnings during scenario execution:\n{warnings}"
        ))
    }
}

pub mod scenario;

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::{
    error::Error,
    fmt::{Debug, Display},
    time::{Duration, SystemTime},
};

use anyhow::anyhow;
use aws_config::SdkConfig;
use aws_sdk_autoscaling::{
    error::{DisplayErrorContext, ProvideErrorMetadata},
    types::{Activity, AutoScalingGroup, LaunchTemplateSpecification},
};
use aws_sdk_ec2::types::RequestLaunchTemplateData;
use tracing::trace;

const LAUNCH_TEMPLATE_NAME: &str =
 "SDK_Code_Examples_EC2_Autoscaling_template_from_Rust_SDK";
const AUTOSCALING_GROUP_NAME: &str =
 "SDK_Code_Examples_EC2_Autoscaling_Group_from_Rust_SDK";
const MAX_WAIT: Duration = Duration::from_secs(5 * 60); // Wait at most 25
 seconds.
const WAIT_TIME: Duration = Duration::from_millis(500); // Wait half a second at
 a time.

struct Waiter {
    start: SystemTime,
```

```
    max: Duration,
}

impl Waiter {
    fn new() -> Self {
        Waiter {
            start: SystemTime::now(),
            max: MAX_WAIT,
        }
    }

    async fn sleep(&self) -> Result<(), ScenarioError> {
        if SystemTime::now()
            .duration_since(self.start)
            .unwrap_or(Duration::MAX)
            > self.max
        {
            Err(ScenarioError::with(
                "Exceeded maximum wait duration for stable group",
            ))
        } else {
            tokio::time::sleep(WAIT_TIME).await;
            Ok(())
        }
    }
}

pub struct AutoScalingScenario {
    ec2: aws_sdk_ec2::Client,
    autoscaling: aws_sdk_autoscaling::Client,
    launch_template_arn: String,
    auto_scaling_group_name: String,
}

impl Display for AutoScalingScenario {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        f.write_fmt(format_args!(
            "\tLaunch Template ID: {}\n",
            self.launch_template_arn
        ))?;
        f.write_fmt(format_args!(
            "\tScaling Group Name: {}\n",
            self.auto_scaling_group_name
        ))?;
```

```
        Ok(())
    }
}

pub struct AutoScalingScenarioDescription {
    group: Result<Vec<String>, ScenarioError>,
    instances: Result<Vec<String>, anyhow::Error>,
    activities: Result<Vec<Activity>, anyhow::Error>,
}

impl Display for AutoScalingScenarioDescription {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "\t      Group status:")?;
        match &self.group {
            Ok(groups) => {
                for status in groups {
                    writeln!(f, "\t\t- {status}")?;
                }
            }
            Err(e) => writeln!(f, "\t\t! - {e}")?,
        }
        writeln!(f, "\t         Instances:")?;
        match &self.instances {
            Ok(instances) => {
                for instance in instances {
                    writeln!(f, "\t\t- {instance}")?;
                }
            }
            Err(e) => writeln!(f, "\t\t! {e}")?,
        }

        writeln!(f, "\t        Activities:")?;
        match &self.activities {
            Ok(activities) => {
                for activity in activities {
                    writeln!(
                        f,
                        "\t\t- {} Progress: {}% Status: {:?} End: {:?}",
                        activity.cause().unwrap_or("Unknown"),
                        activity.progress.unwrap_or(-1),
                        activity.status_code(),
                        // activity.status_message().unwrap_or_default()
                        activity.end_time(),
```

```
                    )?;
                }
            }
            Err(e) => writeln!(f, "\t\t! {e}")?,
        }

        Ok(())
    }
}

#[derive(Debug)]
struct MetadataError {
    message: Option<String>,
    code: Option<String>,
}

impl MetadataError {
    fn from(err: &dyn ProvideErrorMetadata) -> Self {
        MetadataError {
            message: err.message().map(|s| s.to_string()),
            code: err.code().map(|s| s.to_string()),
        }
    }
}

impl Display for MetadataError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        let display = match (&self.message, &self.code) {
            (None, None) => "Unknown".to_string(),
            (None, Some(code)) => format!("({code})"),
            (Some(message), None) => message.to_string(),
            (Some(message), Some(code)) => format!("{message} ({code})"),
        };
        write!(f, "{display}")
    }
}

#[derive(Debug)]
pub struct ScenarioError {
    message: String,
    context: Option<MetadataError>,
}

impl ScenarioError {
```

```
    pub fn with(message: impl Into<String>) -> Self {
        ScenarioError {
            message: message.into(),
            context: None,
        }
    }

    pub fn new(message: impl Into<String>, err: &dyn ProvideErrorMetadata) ->
 Self {
        ScenarioError {
            message: message.into(),
            context: Some(MetadataError::from(err)),
        }
    }
}

impl Error for ScenarioError {
    // While `Error` can capture `source` information about the underlying error,
 for this example
    // the ScenarioError captures the underlying information in MetadataError and
 treats it as a
    // single Error from this Crate. In other contexts, it may be appropriate to
 model the error
    // as including the SdkError as its source.
}
impl Display for ScenarioError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        match &self.context {
            Some(c) => write!(f, "{}: {}", self.message, c),
            None => write!(f, "{}", self.message),
        }
    }
}

impl AutoScalingScenario {
    pub async fn prepare_scenario(sdk_config: &SdkConfig) -> Result<Self,
 Vec<ScenarioError>> {
        let ec2 = aws_sdk_ec2::Client::new(sdk_config);
        let autoscaling = aws_sdk_autoscaling::Client::new(sdk_config);

        let auto_scaling_group_name = String::from(AUTOSCALING_GROUP_NAME);

        // Before creating any resources, prepare the list of AZs
        let availablity_zones = ec2.describe_availability_zones().send().await;
```

```
        if let Err(err) = availablity_zones {
            return Err(vec![ScenarioError::new("Failed to find AZs", &err)]);
        }

        let availability_zones: Vec<String> = availablity_zones
            .unwrap()
            .availability_zones
            .unwrap_or_default()
            .iter()
            .take(3)
            .map(|z| z.zone_name.clone().unwrap())
            .collect();

        // 1. Create an EC2 launch template that you'll use to create an auto
scaling group. Bonus: use SDK with EC2.CreateLaunchTemplate to create the launch
template.
        //   * Recommended: InstanceType='t1.micro',
ImageId='ami-0ca285d4c2cda3300'
        let create_launch_template = ec2
            .create_launch_template()
            .launch_template_name(LAUNCH_TEMPLATE_NAME)
            .launch_template_data(
                RequestLaunchTemplateData::builder()
                    .instance_type(aws_sdk_ec2::types::InstanceType::T1Micro)
                    .image_id("ami-0ca285d4c2cda3300")
                    .build(),
            )
            .send()
            .await
            .map_err(|err| vec![ScenarioError::new("Failed to create launch
template", &err)])?;

        let launch_template_arn = match create_launch_template.launch_template {
            Some(launch_template) =>
launch_template.launch_template_id.unwrap_or_default(),
            None => {
                // Try to delete the launch template
                let _ = ec2
                    .delete_launch_template()
                    .launch_template_name(LAUNCH_TEMPLATE_NAME)
                    .send()
                    .await;
                return Err(vec![ScenarioError::with("Failed to load launch
template")]);
```

```
            }
        };

        // 2. CreateAutoScalingGroup: pass it the launch template you created in
step 0. Give it min/max of 1 instance.
        //   You can use EC2.describe_availability_zones() to get a list of AZs
(you have to specify an AZ when you create the group).
        //   Wait for instance to launch. Use a waiter if you have one, otherwise
DescribeAutoScalingInstances until LifecycleState='InService'
        if let Err(err) = autoscaling
            .create_auto_scaling_group()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .launch_template(
                LaunchTemplateSpecification::builder()
                    .launch_template_id(launch_template_arn.clone())
                    .version("$Latest")
                    .build(),
            )
            .max_size(1)
            .min_size(1)
            .set_availability_zones(Some(availability_zones))
            .send()
            .await
        {
            let mut errs = vec![ScenarioError::new(
                "Failed to create autoscaling group",
                &err,
            )];

            if let Err(err) = autoscaling
                .delete_auto_scaling_group()
                .auto_scaling_group_name(auto_scaling_group_name.as_str())
                .send()
                .await
            {
                errs.push(ScenarioError::new(
                    "Failed to clean up autoscaling group",
                    &err,
                ));
            }

            if let Err(err) = ec2
                .delete_launch_template()
                .launch_template_id(launch_template_arn.clone())
```

```
                .send()
                .await
            {
                errs.push(ScenarioError::new(
                    "Failed to clean up launch template",
                    &err,
                ));
            }
            return Err(errs);
        }

        let scenario = AutoScalingScenario {
            ec2,
            autoscaling: autoscaling.clone(), // Clients are cheap so cloning
here to prevent a move is ok.
            auto_scaling_group_name: auto_scaling_group_name.clone(),
            launch_template_arn,
        };

        // snippet-start:[rust.auto-scaling.scenario.enable_metrics_collection]
        let enable_metrics_collection = autoscaling
            .enable_metrics_collection()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .granularity("1Minute")
            .set_metrics(Some(vec![
                String::from("GroupMinSize"),
                String::from("GroupMaxSize"),
                String::from("GroupDesiredCapacity"),
                String::from("GroupInServiceInstances"),
                String::from("GroupTotalInstances"),
            ]))
            .send()
            .await;
        // snippet-end:[rust.auto-scaling.scenario.enable_metrics_collection]

        match enable_metrics_collection {
            Ok(_) => Ok(scenario),
            Err(err) => {
                scenario.clean_scenario().await?;
                Err(vec![ScenarioError::new(
                    "Failed to enable metrics collections for group",
                    &err,
                )])
            }
```

```
        }
    }

    pub async fn clean_scenario(self) -> Result<(), Vec<ScenarioError>> {
        let _ = self.wait_for_no_scaling().await;
        let delete_group = self
            .autoscaling
            .delete_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;

        // 14. Delete LaunchTemplate.
        let delete_launch_template = self
            .ec2
            .delete_launch_template()
            .launch_template_id(self.launch_template_arn.clone())
            .send()
            .await;

        let early_exit = match (delete_group, delete_launch_template) {
            (Ok(_), Ok(_)) => Ok(()),
            (Ok(_), Err(e)) => Err(vec![ScenarioError::new(
                "There was an error cleaning the launch template",
                &e,
            )]),
            (Err(e), Ok(_)) => Err(vec![ScenarioError::new(
                "There was an error cleaning the scale group",
                &e,
            )]),
            (Err(e1), Err(e2)) => Err(vec![
                ScenarioError::new("Multiple error cleaning the scenario Scale
Group", &e1),
                ScenarioError::new("Multiple error cleaning the scenario Launch
Template", &e2),
            ]),
        };

        if early_exit.is_err() {
            early_exit
        } else {
            // Wait for delete_group to finish
            let waiter = Waiter::new();
            let mut errors = Vec::<ScenarioError>::new();
```

```
            while errors.len() < 3 {
                if let Err(e) = waiter.sleep().await {
                    errors.push(e);
                    continue;
                }
                let describe_group = self
                    .autoscaling
                    .describe_auto_scaling_groups()

.auto_scaling_group_names(self.auto_scaling_group_name.clone())
                    .send()
                    .await;
                match describe_group {
                    Ok(group) => match group.auto_scaling_groups().first() {
                        Some(group) => {
                            if group.status() != Some("Delete in progress") {
                                errors.push(ScenarioError::with(format!(
                                    "Group in an unknown state while deleting:
{}",
                                    group.status().unwrap_or("unknown error")
                                )));
                                return Err(errors);
                            }
                        }
                        None => return Ok(()),
                    },
                    Err(err) => {
                        errors.push(ScenarioError::new("Failed to describe
autoscaling group during cleanup 3 times, last error", &err));
                    }
                }
                if errors.len() > 3 {
                    return Err(errors);
                }
            }
            Err(vec![ScenarioError::with(
                "Exited cleanup wait loop without retuning success or failing
after three rounds",
            )])
        }
    }

    // snippet-start:[rust.auto-scaling.scenario.describe_scenario]
    pub async fn describe_scenario(&self) -> AutoScalingScenarioDescription {
```

```
        let group = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await
            .map(|s| {
                s.auto_scaling_groups()
                    .iter()
                    .map(|s| {
                        format!(
                            "{}: {}",
                            s.auto_scaling_group_name().unwrap_or("Unknown"),
                            s.status().unwrap_or("Unknown")
                        )
                    })
                    .collect::<Vec<String>>()
            })
            .map_err(|e| {
                ScenarioError::new("Failed to describe auto scaling groups for
scenario", &e)
            });

        let instances = self
            .list_instances()
            .await
            .map_err(|e| anyhow!("There was an error listing instances: {e}",));

        // 10. DescribeScalingActivities: list the scaling activities that have
occurred for the group so far.
        //   Bonus: use CloudWatch API to get and show some metrics collected for
the group.
        //   CW.ListMetrics with Namespace='AWS/AutoScaling' and
Dimensions=[{'Name': 'AutoScalingGroupName', 'Value': }]
        //   CW.GetMetricStatistics with Statistics='Sum'. Start and End times
must be in UTC!
        let activities = self
            .autoscaling
            .describe_scaling_activities()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .into_paginator()
            .items()
            .send()
            .collect::<Result<Vec<_>, _>>()
```

```
            .await
            .map_err(|e| {
                anyhow!(
                    "There was an error retrieving scaling activities: {}",
                    DisplayErrorContext(&e)
                )
            });

        AutoScalingScenarioDescription {
            group,
            instances,
            activities,
        }
    }
    // snippet-end:[rust.auto-scaling.scenario.describe_scenario]

    // snippet-start:[rust.auto-scaling.scenario.get_group]
    async fn get_group(&self) -> Result<AutoScalingGroup, ScenarioError> {
        let describe_auto_scaling_groups = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await;

        if let Err(err) = describe_auto_scaling_groups {
            return Err(ScenarioError::new(
                format!(
                    "Failed to get status of autoscaling group {}",
                    self.auto_scaling_group_name.clone()
                )
                .as_str(),
                &err,
            ));
        }

        let describe_auto_scaling_groups_output =
describe_auto_scaling_groups.unwrap();
        let auto_scaling_groups =
describe_auto_scaling_groups_output.auto_scaling_groups();
        let auto_scaling_group = auto_scaling_groups.first();

        if auto_scaling_group.is_none() {
            return Err(ScenarioError::with(format!(
```

```
                "Could not find autoscaling group {}",
                self.auto_scaling_group_name.clone()
            )));
        }

        Ok(auto_scaling_group.unwrap().clone())
    }
    // snippet-end:[rust.auto-scaling.scenario.get_group]

    pub async fn wait_for_no_scaling(&self) -> Result<(), ScenarioError> {
        let waiter = Waiter::new();
        let mut scaling = true;
        while scaling {
            waiter.sleep().await?;
            let describe_activities = self
                .autoscaling
                .describe_scaling_activities()
                .auto_scaling_group_name(self.auto_scaling_group_name.clone())
                .send()
                .await
                .map_err(|e| {
                    ScenarioError::new("Failed to get autoscaling activities for
group", &e)
                })?;
            let activities = describe_activities.activities();
            trace!(
                "Waiting for no scaling found {} activities",
                activities.len()
            );
            scaling = activities.iter().any(|a| a.progress() < Some(100));
        }
        Ok(())
    }

    pub async fn wait_for_stable(&self, size: usize) -> Result<(), ScenarioError>
{
        self.wait_for_no_scaling().await?;

        let mut group = self.get_group().await?;
        let mut count = count_group_instances(&group);

        let waiter = Waiter::new();
        while count != size {
            trace!("Waiting for stable {size} (current: {count})");
```

```
            waiter.sleep().await?;
            group = self.get_group().await?;
            count = count_group_instances(&group);
        }

        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.list_instances]
    pub async fn list_instances(&self) -> Result<Vec<String>, ScenarioError> {
        // The direct way to list instances is by using
 DescribeAutoScalingGroup's instances property. However, this returns a
 Vec<Instance>, as opposed to a Vec<AutoScalingInstanceDetails>.
        // Ok(self.get_group().await?.instances.unwrap_or_default().map(|
i| i.instance_id.clone().unwrap_or_default()).filter(|id| !
id.is_empty()).collect())

        // Alternatively, and for the sake of example,
 DescribeAutoScalingInstances returns a list that can be filtered by the client.
        self.autoscaling
            .describe_auto_scaling_instances()
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
            .map(|items| {
                items
                    .into_iter()
                    .filter(|i| {
                        i.auto_scaling_group_name.as_deref()
                            == Some(self.auto_scaling_group_name.as_str())
                    })
                    .map(|i| i.instance_id.unwrap_or_default())
                    .filter(|id| !id.is_empty())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Failed to get list of auto scaling
 instances", &err))
    }
    // snippet-end:[rust.auto-scaling.scenario.list_instances]

    pub async fn scale_min_size(&self, size: i32) -> Result<(), ScenarioError> {
        let update_group = self
```

```
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .min_size(size)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failer to update group to min size ({size}))").as_str(),
                &err,
            ));
        }
        Ok(())
    }

    pub async fn scale_max_size(&self, size: i32) -> Result<(), ScenarioError> {
        // 5. UpdateAutoScalingGroup: update max size to 3.
        let update_group = self
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .max_size(size)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failed to update group to max size ({size})").as_str(),
                &err,
            ));
        }
        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.scale_desired_capacity]
    pub async fn scale_desired_capacity(&self, capacity: i32) -> Result<(),
ScenarioError> {
        // 7. SetDesiredCapacity: set desired capacity to 2.
        //   Wait for a second instance to launch.
        let update_group = self
            .autoscaling
            .set_desired_capacity()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .desired_capacity(capacity)
            .send()
```

```
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failed to update group to desired capacity
({capacity}))").as_str(),
                &err,
            ));
        }
        Ok(())
    }
    // snippet-end:[rust.auto-scaling.scenario.scale_desired_capacity]

    pub async fn scale_group_to_zero(&self) -> Result<(), ScenarioError> {
        // snippet-start:[rust.auto-scaling.scenario.disable_metrics_collection]
        // If this fails it's fine, just means there are extra cloudwatch metrics
events for the scale-down.
        let _ = self
            .autoscaling
            .disable_metrics_collection()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;
        // snippet-end:[rust.auto-scaling.scenario.disable_metrics_collection]

        // 12. DeleteAutoScalingGroup (to delete the group you must stop all
instances):
        //   UpdateAutoScalingGroup with MinSize=0
        let update_group = self
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .min_size(0)
            .desired_capacity(0)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                "Failed to update group for scaling down&",
                &err,
            ));
        }

        let stable = self.wait_for_stable(0).await;
        if let Err(err) = stable {
```

```
            return Err(ScenarioError::with(format!(
                "Error while waiting for group to be stable on scale down: {err}"
            )));
        }

        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.terminate_some_instance]
    pub async fn terminate_some_instance(&self) -> Result<(), ScenarioError> {
        // Retrieve a list of instances in the auto scaling group.
        let auto_scaling_group = self.get_group().await?;
        let instances = auto_scaling_group.instances();
        // Or use other logic to find an instance to terminate.
        let instance = instances.first();
        if let Some(instance) = instance {
            let instance_id = if let Some(instance_id) = instance.instance_id() {
                instance_id
            } else {
                return Err(ScenarioError::with("Missing instance id"));
            };
            let termination = self
                .ec2
                .terminate_instances()
                .instance_ids(instance_id)
                .send()
                .await;
            if let Err(err) = termination {
                Err(ScenarioError::new(
                    "There was a problem terminating an instance",
                    &err,
                ))
            } else {
                Ok(())
            }
        } else {
            Err(ScenarioError::with("There was no instance to terminate"))
        }
    }
    // snippet-end:[rust.auto-scaling.scenario.terminate_some_instance]
}

fn count_group_instances(group: &AutoScalingGroup) -> usize {
    group.instances.as_ref().map(|i| i.len()).unwrap_or(0)
```

```
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos de código para o AWS Batch usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Batch com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do AWS Batch – Mais informações sobre o AWS Batch.
- Referência da API do AWS Batch – Detalhes sobre todas as ações disponíveis do AWS Batch.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o AWS Batch usando AWS SDKs
  - Descreva um ou mais ambientes de computação do AWS Batch usando um SDK da AWS

Ações para o AWS Batch usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Batch com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Descreva um ou mais ambientes de computação do AWS Batch usando um SDK da AWS

Descreva um ou mais ambientes de computação do AWS Batch usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um ou mais ambientes de computação AWS Batch.

CLI

AWS CLI

Como descrever um ambiente de computação

Este exemplo descreve o ambiente OnDemand computacional P2.

Comando:

```
aws batch describe-compute-environments --compute-environments P2OnDemand
```

Saída:

```
{
    "computeEnvironments": [
        {
            "status": "VALID",
            "serviceRole": "arn:aws:iam::012345678910:role/AWSBatchServiceRole",
            "computeEnvironmentArn": "arn:aws:batch:us-
east-1:012345678910:compute-environment/P2OnDemand",
            "computeResources": {
                "subnets": [
```

```
                    "subnet-220c0e0a",
                    "subnet-1a95556d",
                    "subnet-978f6dce"
                ],
                "tags": {
                    "Name": "Batch Instance - P2OnDemand"
                },
                "desiredvCpus": 48,
                "minvCpus": 0,
                "instanceTypes": [
                    "p2"
                ],
                "securityGroupIds": [
                    "sg-cf5093b2"
                ],
                "instanceRole": "ecsInstanceRole",
                "maxvCpus": 128,
                "type": "EC2",
                "ec2KeyPair": "id_rsa"
            },
            "statusReason": "ComputeEnvironment Healthy",
            "ecsClusterArn": "arn:aws:ecs:us-east-1:012345678910:cluster/
P2OnDemand_Batch_2c06f29d-d1fe-3a49-879d-42394c86effc",
            "state": "ENABLED",
            "computeEnvironmentName": "P2OnDemand",
            "type": "MANAGED"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeComputeEnvironmentsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_envs(client: &Client) -> Result<(), Error> {
    let rsp = client.describe_compute_environments().send().await?;

    let compute_envs = rsp.compute_environments();
    println!("Found {} compute environments:", compute_envs.len());
    for env in compute_envs {
        let arn = env.compute_environment_arn();
        let name = env.compute_environment_name();

        println!("  Name: {}", name.unwrap_or("Unknown"));
        println!("  ARN:  {}", arn.unwrap_or("Unknown"));
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeComputeEnvironmentsreferência da API AWS SDK for Rust.

Exemplos de código para o Amazon Bedrock usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Amazon Bedrock – Mais informações sobre o Amazon Bedrock.
- Referência da API do Amazon Bedrock — Detalhes sobre todas as ações disponíveis do Amazon Bedrock.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon Bedrock

Os exemplos de código a seguir mostram como começar a usar o Amazon Bedrock.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon;
using Amazon.Bedrock;
using Amazon.Bedrock.Model;

namespace ListFoundationModelsExample
{
    /// <summary>
    /// This example shows how to list foundation models.
    /// </summary>
    internal class HelloBedrock
    {
        /// <summary>
        /// Main method to call the ListFoundationModelsAsync method.
        /// </summary>
        /// <param name="args"> The command line arguments. </param>
        static async Task Main(string[] args)
        {
            // Specify a region endpoint where Amazon Bedrock is available.
 For a list of supported region see https://docs.aws.amazon.com/bedrock/latest/
userguide/what-is-bedrock.html#bedrock-regions
```

```
            AmazonBedrockClient bedrockClient = new(RegionEndpoint.USWest2);

            await ListFoundationModelsAsync(bedrockClient);

        }


        /// <summary>
        /// List foundation models.
        /// </summary>
        /// <param name="bedrockClient"> The Amazon Bedrock client. </param>
        private static async Task ListFoundationModelsAsync(AmazonBedrockClient
bedrockClient)
        {
            Console.WriteLine("List foundation models with no filter");

            try
            {
                ListFoundationModelsResponse response = await
bedrockClient.ListFoundationModelsAsync(new ListFoundationModelsRequest()
                {
                });

                if (response?.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    foreach (var fm in response.ModelSummaries)
                    {
                        WriteToConsole(fm);
                    }
                }
                else
                {
                    Console.WriteLine("Something wrong happened");
                }
            }
            catch (AmazonBedrockException e)
            {
                Console.WriteLine(e.Message);
            }
        }


        /// <summary>
        /// Write the foundation model summary to console.
```

```
        /// </summary>
        /// <param name="foundationModel"> The foundation model summary to write
 to console. </param>
        private static void WriteToConsole(FoundationModelSummary
 foundationModel)
        {
            Console.WriteLine($"{foundationModel.ModelId}, Customization:
 {String.Join(", ", foundationModel.CustomizationsSupported)}, Stream:
 {foundationModel.ResponseStreamingSupported}, Input: {String.Join(",
 ", foundationModel.InputModalities)}, Output: {String.Join(", ",
 foundationModel.OutputModalities)}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for .NET da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/bedrock"
)

const region = "us-east-1"
```

```
// main uses the AWS SDK for Go (v2) to create an Amazon Bedrock client and
// list the available foundation models in your account and the chosen region.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
    sdkConfig, err := config.LoadDefaultConfig(context.TODO(),
 config.WithRegion(region))
    if err != nil {
        fmt.Println("Couldn't load default configuration. Have you set up your
 AWS account?")
        fmt.Println(err)
        return
    }
    bedrockClient := bedrock.NewFromConfig(sdkConfig)
    result, err := bedrockClient.ListFoundationModels(context.TODO(),
 &bedrock.ListFoundationModelsInput{})
    if err != nil {
  fmt.Printf("Couldn't list foundation models. Here's why: %v\n", err)
  return
    }
    if len(result.ModelSummaries) == 0 {
    fmt.Println("There are no foundation models.")}
    for _, modelSummary := range result.ModelSummaries {
        fmt.Println(*modelSummary.ModelId)
    }
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { fileURLToPath } from 'url';

import { BedrockClient, ListFoundationModelsCommand } from '@aws-sdk/client-
bedrock';

const REGION = 'us-east-1';
const client = new BedrockClient({ region: REGION });

export const main = async () => {
    const command = new ListFoundationModelsCommand({});

    const response = await client.send(command);
    const models = response.modelSummaries;

    console.log('Listing the available Bedrock foundation models:');

    for (let model of models) {
        console.log('='.repeat(42));
        console.log(` Model: ${model.modelId}`);
        console.log('-'.repeat(42));
        console.log(` Name: ${model.modelName}`);
        console.log(` Provider: ${model.providerName}`);
        console.log(` Model ARN: ${model.modelArn}`);
        console.log(` Input modalities: ${model.inputModalities}`);
        console.log(` Output modalities: ${model.outputModalities}`);
        console.log(` Supported customizations:
 ${model.customizationsSupported}`);
        console.log(` Supported inference types:
 ${model.inferenceTypesSupported}`);
        console.log(` Lifecycle status: ${model.modelLifecycle.status}`);
        console.log('='.repeat(42) + '\n');
    }

    const active = models.filter(m => m.modelLifecycle.status ===
 'ACTIVE').length;
    const legacy = models.filter(m => m.modelLifecycle.status ===
 'LEGACY').length;

    console.log(`There are ${active} active and ${legacy} legacy foundation
 models in ${REGION}.`);
```

```
    return response;
};

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    await main();
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for JavaScript da API.

Exemplos de código

- Ações para o Amazon Bedrock Runtime usando SDKs da AWS
  - Obter detalhes sobre um modelo de base do Amazon Bedrock usando um SDK da AWS
  - Liste os modelos de base disponíveis do Amazon Bedrock usando um SDK da AWS
- Cenários para o Amazon Bedrock usando SDKs AWS
  - Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Ações para o Amazon Bedrock Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon Bedrock usando SDKs AWS.

Exemplos

- Obter detalhes sobre um modelo de base do Amazon Bedrock usando um SDK da AWS
- Liste os modelos de base disponíveis do Amazon Bedrock usando um SDK da AWS

Obter detalhes sobre um modelo de base do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como obter detalhes de um modelo de base do Amazon Bedrock.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Veja detalhes sobre um modelo de base.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { fileURLToPath } from 'url';

import { BedrockClient, GetFoundationModelCommand } from '@aws-sdk/client-
bedrock';

/**
 * Get details about an Amazon Bedrock foundation model.
 *
 * @return {FoundationModelDetails} - The list of available bedrock foundation
 models.
 */
export const getFoundationModel = async () => {
    const client = new BedrockClient();

    const command = new GetFoundationModelCommand({
        modelIdentifier: 'amazon.titan-embed-text-v1'
    });

    const response = await client.send(command);

    return response.modelDetails;
```

```
};

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const model = await getFoundationModel();
    console.log(model);
}
```

- Para obter detalhes da API, consulte GetFoundationModela Referência AWS SDK for JavaScript da API.

Liste os modelos de base disponíveis do Amazon Bedrock usando um SDK da AWS

Os exemplos de código a seguir mostram como listar modelos de base disponíveis do Amazon Bedrock.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base Bedrock disponíveis.

```
        /// <summary>
        /// List foundation models.
        /// </summary>
        /// <param name="bedrockClient"> The Amazon Bedrock client. </param>
        private static async Task ListFoundationModelsAsync(AmazonBedrockClient
 bedrockClient)
        {
            Console.WriteLine("List foundation models with no filter");

            try
            {
```

```
                ListFoundationModelsResponse response = await
bedrockClient.ListFoundationModelsAsync(new ListFoundationModelsRequest()
                {
                });

                if (response?.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    foreach (var fm in response.ModelSummaries)
                    {
                        WriteToConsole(fm);
                    }
                }
                else
                {
                    Console.WriteLine("Something wrong happened");
                }
            }
            catch (AmazonBedrockException e)
            {
                Console.WriteLine(e.Message);
            }
        }
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for .NET da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base Bedrock disponíveis.

```
// FoundationModelWrapper encapsulates Amazon Bedrock actions used in the
 examples.
// It contains a Bedrock service client that is used to perform foundation model
 actions.
type FoundationModelWrapper struct {
 BedrockClient *bedrock.Client
}



// ListPolicies lists Bedrock foundation models that you can use.
func (wrapper FoundationModelWrapper) ListFoundationModels()
 ([]types.FoundationModelSummary, error) {

    var models []types.FoundationModelSummary

    result, err := wrapper.BedrockClient.ListFoundationModels(context.TODO(),
 &bedrock.ListFoundationModelsInput{})

    if err != nil {
        log.Printf("Couldn't list foundation models. Here's why: %v\n", err)
    } else {
        models = result.ModelSummaries
    }
    return models, err
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
    public static void listFoundationModels(BedrockClient bedrockClient) {

        try {
            ListFoundationModelsRequest request =
ListFoundationModelsRequest.builder().build();

            ListFoundationModelsResponse response =
bedrockClient.listFoundationModels(request);

            List<FoundationModelSummary> models = response.modelSummaries();

            for (FoundationModelSummary model : models) {
                System.out.println("Model ID: " + model.modelId());
                System.out.println("Provider: " + model.providerName());
                System.out.println("Name:     " + model.modelName());
                System.out.println();
            }

        } catch (BedrockException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { fileURLToPath } from 'url';

import { BedrockClient, ListFoundationModelsCommand } from '@aws-sdk/client-
bedrock';

/**
 * List the available Amazon Bedrock foundation models.
 *
 * @return {FoundationModelSummary[]} - The list of available bedrock foundation
 models.
 */
export const listFoundationModels = async () => {
    const client = new BedrockClient();

    const input = {
        // byProvider: 'STRING_VALUE',
        // byCustomizationType: 'FINE_TUNING' || 'CONTINUED_PRE_TRAINING',
        // byOutputModality: 'TEXT' || 'IMAGE' || 'EMBEDDING',
        // byInferenceType: 'ON_DEMAND' || 'PROVISIONED',
    };

    const command = new ListFoundationModelsCommand(input);

    const response = await client.send(command);

    return response.modelSummaries;
}

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const models = await listFoundationModels();
    console.log(models);
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
suspend fun listFoundationModels(): List<FoundationModelSummary>? {
    BedrockClient { region = "us-east-1" }.use { bedrockClient ->
        val response =
 bedrockClient.listFoundationModels(ListFoundationModelsRequest {})
        response.modelSummaries?.forEach { model ->
            println("========================================")
            println(" Model ID: ${model.modelId}")
            println("----------------------------------------")
            println(" Name: ${model.modelName}")
            println(" Provider: ${model.providerName}")
            println(" Input modalities: ${model.inputModalities}")
            println(" Output modalities: ${model.outputModalities}")
            println(" Supported customizations:
 ${model.customizationsSupported}")
            println(" Supported inference types:
 ${model.inferenceTypesSupported}")
            println("----------------------------------------\n")
        }
        return response.modelSummaries
    }
}
```

- Para obter detalhes da API, consulte a ListFoundationModelsreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
public function listFoundationModels()
{
    $result = $this->bedrockClient->listFoundationModels();
    return $result;
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
def list_foundation_models(self):
    """
    List the available Amazon Bedrock foundation models.

    :return: The list of available bedrock foundation models.
    """
```

```
        try:
            response = self.bedrock_client.list_foundation_models()
            models = response["modelSummaries"]
            logger.info("Got %s foundation models.", len(models))
        except ClientError:
            logger.error("Couldn't list foundation models.")
            raise
        else:
            return models
```

- Para obter detalhes da API, consulte a ListFoundationModelsReferência da API AWSSDK for Python (Boto3).

Cenários para o Amazon Bedrock usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

Python

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de código para o Amazon Bedrock Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock Runtime com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Amazon Bedrock Runtime – Mais informações sobre o Amazon Bedrock Runtime.
- Referência da API do Amazon Bedrock Runtime — Detalhes sobre todas as ações disponíveis do Amazon Bedrock Runtime.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon Bedrock

O exemplo de código a seguir mostra como começar a usar o Amazon Bedrock.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "encoding/json"
 "flag"
 "fmt"
 "log"
 "os"
```

```
 "strings"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/bedrockruntime"
)

// Each model provider defines their own individual request and response formats.
// For the format, ranges, and default values for the different models, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters.html

type ClaudeRequest struct {
 Prompt            string `json:"prompt"`
 MaxTokensToSample int    `json:"max_tokens_to_sample"`
 // Omitting optional request parameters
}

type ClaudeResponse struct {
 Completion string `json:"completion"`
}

// main uses the AWS SDK for Go (v2) to create an Amazon Bedrock Runtime client
// and invokes Anthropic Claude 2 inside your account and the chosen region.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {

 region := flag.String("region", "us-east-1", "The AWS region")
 flag.Parse()

 fmt.Printf("Using AWS region: %s\n", *region)

 sdkConfig, err := config.LoadDefaultConfig(context.Background(),
 config.WithRegion(*region))
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }

 client := bedrockruntime.NewFromConfig(sdkConfig)

 modelId := "anthropic.claude-v2"
```

```
 prompt := "Hello, how are you today?"

 // Anthropic Claude requires you to enclose the prompt as follows:
 prefix := "Human: "
 postfix := "\n\nAssistant:"
 wrappedPrompt := prefix + prompt + postfix

 request := ClaudeRequest{
  Prompt:            wrappedPrompt,
  MaxTokensToSample: 200,
 }

 body, err := json.Marshal(request)
 if err != nil {
  log.Panicln("Couldn't marshal the request: ", err)
 }

 result, err := client.InvokeModel(context.Background(),
 &bedrockruntime.InvokeModelInput{
  ModelId:     aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body:        body,
 })

 if err != nil {
  errMsg := err.Error()
  if strings.Contains(errMsg, "no such host") {
   fmt.Printf("Error: The Bedrock service is not available in the selected
 region. Please double-check the service availability for your region at https://
aws.amazon.com/about-aws/global-infrastructure/regional-product-services/.\n")
  } else if strings.Contains(errMsg, "Could not resolve the foundation model") {
   fmt.Printf("Error: Could not resolve the foundation model from model
 identifier: \"%v\". Please verify that the requested model exists and is
 accessible within the specified region.\n", modelId)
  } else {
   fmt.Printf("Error: Couldn't invoke Anthropic Claude. Here's why: %v\n", err)
  }
  os.Exit(1)
 }

 var response ClaudeResponse

 err = json.Unmarshal(result.Body, &response)
```

```
 if err != nil {
  log.Fatal("failed to unmarshal", err)
 }
 fmt.Println("Prompt:\n", prompt)
 fmt.Println("Response from Anthropic Claude:\n", response.Completion)
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Exemplos de código

- Ações para o Amazon Bedrock Runtime usando SDKs da AWS
  - Invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens
  - Invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para geração de imagens
  - Invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto
  - Invoque o modelo Amazon Titan Text G1 no Amazon Bedrock para geração de texto
  - Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto
  - Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta
  - Invoque o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto
- Cenários para o Amazon Bedrock Runtime usando SDKs da AWS
  - Crie um aplicativo de amostra que ofereça playgrounds para interagir com os modelos de base do Amazon Bedrock usando um SDK da AWS
  - Invocar vários grandes modelos de linguagem (LLMs) no Amazon Bedrock
  - Invocar vários modelos de base no Amazon Bedrock
  - Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Ações para o Amazon Bedrock Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock Runtime com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon Bedrock Runtime usando SDKs da AWS.

Exemplos

- Invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens
- Invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para geração de imagens
- Invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto
- Invoque o modelo Amazon Titan Text G1 no Amazon Bedrock para geração de texto
- Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto
- Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta
- Invoque o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto

Invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens

Os exemplos de código a seguir mostram como invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
type TitanImageRequest struct {
    TaskType              string                `json:"taskType"`
    TextToImageParams     TextToImageParams     `json:"textToImageParams"`
    ImageGenerationConfig ImageGenerationConfig `json:"imageGenerationConfig"`
}
type TextToImageParams struct {
    Text string `json:"text"`
}
type ImageGenerationConfig struct {
    NumberOfImages int     `json:"numberOfImages"`
    Quality        string  `json:"quality"`
    CfgScale       float64 `json:"cfgScale"`
    Height         int     `json:"height"`
    Width          int     `json:"width"`
    Seed           int64   `json:"seed"`
}

type TitanImageResponse struct {
    Images []string `json:"images"`
}

// Invokes the Titan Image model to create an image using the input provided
// in the request body.
func (wrapper InvokeModelWrapper) InvokeTitanImage(prompt string, seed int64)
 (string, error) {
    modelId := "amazon.titan-image-generator-v1"

    body, err := json.Marshal(TitanImageRequest {
        TaskType: "TEXT_IMAGE",
        TextToImageParams: TextToImageParams {
            Text: prompt,
        },
        ImageGenerationConfig: ImageGenerationConfig {
            NumberOfImages: 1,
            Quality: "standard",
            CfgScale: 8.0,
            Height: 512,
            Width: 512,
            Seed: seed,
        },
    })
```

```
    if err != nil { log.Fatal("failed to marshal", err) }

    output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
        ModelId: aws.String(modelId),
        ContentType: aws.String("application/json"),
        Body: body,
    })

    if err != nil { ProcessError(err, modelId) }

    var response TitanImageResponse
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

    base64ImageData := response.Images[0]

    return base64ImageData, nil

}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Image Generator G1 do Amazon Titan de forma assíncrona para gerar imagens.

```
    /**
     * Invokes the Amazon Titan image generation model to create an image using
 the
```

```
     * input
     * provided in the request body.
     *
     * @param prompt The prompt that you want Amazon Titan to use for image
     *               generation.
     * @param seed   The random noise seed for image generation (Range: 0 to
     *               2147483647).
     * @return A Base64-encoded string representing the generated image.
     */
    public static String invokeTitanImage(String prompt, long seed) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Titan Image models
 refer to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-
         * image.html
         */
        String titanImageModelId = "amazon.titan-image-generator-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        var textToImageParams = new JSONObject().put("text", prompt);

        var imageGenerationConfig = new JSONObject()
                .put("numberOfImages", 1)
                .put("quality", "standard")
                .put("cfgScale", 8.0)
                .put("height", 512)
                .put("width", 512)
                .put("seed", seed);

        JSONObject payload = new JSONObject()
                .put("taskType", "TEXT_IMAGE")
                .put("textToImageParams", textToImageParams)
                .put("imageGenerationConfig", imageGenerationConfig);

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload.toString()))
                .modelId(titanImageModelId)
```

```
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " +
exception);
                    }
                });

        String base64ImageData = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            base64ImageData = responseBody
                    .getJSONArray("images")
                    .getString(0);

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return base64ImageData;
    }
```

Invoque o modelo Image Generator G1 do Amazon Titan para gerar imagens.

```
        /**
         * Invokes the Amazon Titan image generation model to create an image
using the
         * input
         * provided in the request body.
         *
         * @param prompt The prompt that you want Amazon Titan to use for image
         *               generation.
```

```
         * @param seed   The random noise seed for image generation (Range: 0 to
         *               2147483647).
         * @return A Base64-encoded string representing the generated image.
         */
        public static String invokeTitanImage(String prompt, long seed) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Titan Image
 models refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-titan-
                 * image.html
                 */
                String titanImageModelId = "amazon.titan-image-generator-v1";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                var textToImageParams = new JSONObject().put("text", prompt);

                var imageGenerationConfig = new JSONObject()
                                .put("numberOfImages", 1)
                                .put("quality", "standard")
                                .put("cfgScale", 8.0)
                                .put("height", 512)
                                .put("width", 512)
                                .put("seed", seed);

                JSONObject payload = new JSONObject()
                                .put("taskType", "TEXT_IMAGE")
                                .put("textToImageParams", textToImageParams)
                                .put("imageGenerationConfig",
 imageGenerationConfig);

                InvokeModelRequest request = InvokeModelRequest.builder()

 .body(SdkBytes.fromUtf8String(payload.toString()))
                                .modelId(titanImageModelId)
                                .contentType("application/json")
                                .accept("application/json")
```

```
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());

                String base64ImageData = responseBody
                                .getJSONArray("images")
                                .getString(0);

                return base64ImageData;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
    public function invokeTitanImage(string $prompt, int $seed)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for Titan Image models refer
 to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-image.html

        $base64_image_data = "";
```

```
        try {
            $modelId = 'amazon.titan-image-generator-v1';

            $request = json_encode([
                'taskType' => 'TEXT_IMAGE',
                'textToImageParams' => [
                    'text' => $prompt
                ],
                'imageGenerationConfig' => [
                    'numberOfImages' => 1,
                    'quality' => 'standard',
                    'cfgScale' => 8.0,
                    'height' => 512,
                    'width' => 512,
                    'seed' => $seed
                ]
            ]);

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => $request,
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $base64_image_data = $response_body->images[0];
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $base64_image_data;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
    def invoke_titan_image(self, prompt, seed):
        """
        Invokes the Titan Image model to create an image using the input provided
 in the request body.

        :param prompt: The prompt that you want Amazon Titan to use for image
 generation.
        :param seed: Random noise seed (range: 0 to 2147483647)
        :return: Base64-encoded inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Titan Image models
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-titan-image.html

            request = json.dumps(
                {
                    "taskType": "TEXT_IMAGE",
                    "textToImageParams": {"text": prompt},
                    "imageGenerationConfig": {
                        "numberOfImages": 1,
                        "quality": "standard",
                        "cfgScale": 8.0,
                        "height": 512,
                        "width": 512,
                        "seed": seed,
                    },
```

```
            }
        )

        response = self.bedrock_runtime_client.invoke_model(
            modelId="amazon.titan-image-generator-v1", body=request
        )

        response_body = json.loads(response["body"].read())
        base64_image_data = response_body["images"][0]

        return base64_image_data

    except ClientError:
        logger.error("Couldn't invoke Titan Image generator")
        raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para geração de imagens

Os exemplos de código a seguir mostram como invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para a geração de imagens.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai de forma assíncrona para gerar imagens.

```
    /**
     * Asynchronously invokes the Stability.ai Stable Diffusion XL model to
 create
     * an image based on the provided input.
     *
     * @param prompt      The prompt that guides the Stable Diffusion model.
     * @param seed        The random noise seed for image generation (use 0 or
 omit
     *                    for a random seed).
     * @param stylePreset The style preset to guide the image model towards a
     *                    specific style.
     * @return A Base64-encoded string representing the generated image.
     */
    public static String invokeStableDiffusion(String prompt, long seed, String
 stylePreset) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and available style_presets of Stable
 Diffusion
         * models refer to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
stability-diffusion.html
         */

        String stableDiffusionModelId = "stability.stable-diffusion-xl";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
```

```
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        JSONArray wrappedPrompt = new JSONArray().put(new
JSONObject().put("text", prompt));
        JSONObject payload = new JSONObject()
                .put("text_prompts", wrappedPrompt)
                .put("seed", seed);

        if (stylePreset != null && !stylePreset.isEmpty()) {
            payload.put("style_preset", stylePreset);
        }

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload.toString()))
                .modelId(stableDiffusionModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " +
exception);
                    }
                });

        String base64ImageData = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            base64ImageData = responseBody
                    .getJSONArray("artifacts")
                    .getJSONObject(0)
                    .getString("base64");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
```

```
        }

        return base64ImageData;
    }
```

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
        /**
         * Invokes the Stability.ai Stable Diffusion XL model to create an image
 based
         * on the provided input.
         *
         * @param prompt      The prompt that guides the Stable Diffusion model.
         * @param seed        The random noise seed for image generation (use 0
 or omit
         *                    for a random seed).
         * @param stylePreset The style preset to guide the image model towards a
         *                    specific style.
         * @return A Base64-encoded string representing the generated image.
         */
        public static String invokeStableDiffusion(String prompt, long seed,
 String stylePreset) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and available style_presets of Stable
 Diffusion
                 * models refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-stability-diffusion.html
                 */

                String stableDiffusionModelId = "stability.stable-diffusion-xl";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                JSONArray wrappedPrompt = new JSONArray().put(new
 JSONObject().put("text", prompt));
```

```
                JSONObject payload = new JSONObject()
                                .put("text_prompts", wrappedPrompt)
                                .put("seed", seed);

                if (!(stylePreset == null || stylePreset.isEmpty())) {
                        payload.put("style_preset", stylePreset);
                }

                InvokeModelRequest request = InvokeModelRequest.builder()

.body(SdkBytes.fromUtf8String(payload.toString()))
                                .modelId(stableDiffusionModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
JSONObject(response.body().asUtf8String());

                String base64ImageData = responseBody
                                .getJSONArray("artifacts")
                                .getJSONObject(0)
                                .getString("base64");

                return base64ImageData;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    public function invokeStableDiffusion(string $prompt, int $seed, string
 $style_preset)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and available style_presets of Stable Diffusion
 models refer to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
stability-diffusion.html

        $base64_image_data = "";

        try {
            $modelId = 'stability.stable-diffusion-xl';

            $body = [
                'text_prompts' => [
                    ['text' => $prompt]
                ],
                'seed' => $seed,
                'cfg_scale' => 10,
                'steps' => 30
            ];

            if ($style_preset) {
                $body['style_preset'] = $style_preset;
            }

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
```

```
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $base64_image_data = $response_body->artifacts[0]->base64;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $base64_image_data;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    def invoke_stable_diffusion(self, prompt, seed, style_preset=None):
        """
        Invokes the Stability.ai Stable Diffusion XL model to create an image
using
        the input provided in the request body.

        :param prompt: The prompt that you want Stable Diffusion  to use for
image generation.
        :param seed: Random noise seed (omit this option or use 0 for a random
seed)
        :param style_preset: Pass in a style preset to guide the image model
towards
                                a particular style.
        :return: Base64-encoded inference response from the model.
```

```
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and available style_presets of Stable
 Diffusion models refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-stability-diffusion.html

            body = {
                "text_prompts": [{"text": prompt}],
                "seed": seed,
                "cfg_scale": 10,
                "steps": 30,
            }

            if style_preset:
                body["style_preset"] = style_preset

            response = self.bedrock_runtime_client.invoke_model(
                modelId="stability.stable-diffusion-xl", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            base64_image_data = response_body["artifacts"][0]["base64"]

            return base64_image_data

        except ClientError:
            logger.error("Couldn't invoke Stable Diffusion XL")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    "Stable Diffusion Input Parameters should be in a format like this:
*   {
*     "text_prompts": [
*       {"text":"Draw a dolphin with a mustache"},
*       {"text":"Make it photorealistic"}
*     ],
*     "cfg_scale":10,
*     "seed":0,
*     "steps":50
*   }
    TYPES: BEGIN OF prompt_ts,
             text TYPE /aws1/rt_shape_string,
           END OF prompt_ts.

    DATA: BEGIN OF ls_input,
            text_prompts TYPE STANDARD TABLE OF prompt_ts,
            cfg_scale    TYPE /aws1/rt_shape_integer,
            seed         TYPE /aws1/rt_shape_integer,
            steps        TYPE /aws1/rt_shape_integer,
          END OF ls_input.

    APPEND VALUE prompt_ts( text = iv_prompt ) TO ls_input-text_prompts.
    ls_input-cfg_scale = 10.
    ls_input-seed = 0. "or better, choose a random integer.
    ls_input-steps = 50.

    DATA(lv_json) = /ui2/cl_json=>serialize(
      data = ls_input
                 pretty_name   = /ui2/cl_json=>pretty_mode-low_case ).

    TRY.
```

```
        DATA(lo_response) = lo_bdr->invokemodel(
          iv_body = /aws1/cl_rt_util=>string_to_xstring( lv_json )
          iv_modelid = 'stability.stable-diffusion-xl-v0'
          iv_accept = 'application/json'
          iv_contenttype = 'application/json' ).

        "Stable Diffusion Result Format:
*       {
*         "result": "success",
*         "artifacts": [
*           {
*             "seed": 0,
*             "base64": "iVBORw0KGgoAAAANSUhEUgAAAgAAA....
*             "finishReason": "SUCCESS"
*           }
*         ]
*       }
        TYPES: BEGIN OF artifact_ts,
                 seed         TYPE /aws1/rt_shape_integer,
                 base64       TYPE /aws1/rt_shape_string,
                 finishreason TYPE /aws1/rt_shape_string,
               END OF artifact_ts.

        DATA: BEGIN OF ls_response,
                result    TYPE /aws1/rt_shape_string,
                artifacts TYPE STANDARD TABLE OF artifact_ts,
              END OF ls_response.

        /ui2/cl_json=>deserialize(
          EXPORTING jsonx = lo_response->get_body( )
                    pretty_name = /ui2/cl_json=>pretty_mode-camel_case
          CHANGING  data  = ls_response ).
        IF ls_response-artifacts IS NOT INITIAL.
          DATA(lv_image) =
 cl_http_utility=>if_http_utility~decode_x_base64( ls_response-artifacts[ 1 ]-
base64 ).
        ENDIF.
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

Invoque o modelo básico Stability.ai Stable Diffusion XL para gerar imagens usando o cliente de alto nível L2.

```
    TRY.
        DATA(lo_bdr_l2_sd) = /aws1/
cl_bdr_l2_factory=>create_stable_diffusion_10( lo_bdr ).
      " iv_prompt contains a prompt like 'Show me a picture of a unicorn reading
 an enterprise financial report'.
        DATA(lv_image) = lo_bdr_l2_sd->text_to_image( iv_prompt ).
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

- Para obter detalhes da API, consulte a InvokeModelreferência da API AWS SDK for SAP ABAP.

Invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto

Os exemplos de código a seguir mostram como invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base Jurassic-2 da AI21 Labs.

```
        /// <summary>
        /// Asynchronously invokes the AI21 Labs Jurassic-2 model to run an
 inference based on the provided input.
        /// </summary>
        /// <param name="prompt">The prompt that you want Claude to complete.</
param>
        /// <returns>The inference response from the model</returns>
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
        /// For the format, ranges, and default values for AI21 Labs Jurassic-2,
 refer to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-jurassic2.html
        /// </remarks>
        public static async Task<string> InvokeJurassic2Async(string prompt)
        {
            string jurassic2ModelId = "ai21.j2-mid-v1";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", prompt },
                { "maxTokens", 200 },
                { "temperature", 0.5 }
            }.ToJsonString();

            string generatedText = "";
            try
```

```
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
InvokeModelRequest()
                {
                    ModelId = jurassic2ModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body)
                        .Result?["completions"]?
                        .AsArray()[0]?["data"]?
                        .AsObject()["text"]?.GetValue<string>() ?? "";
                }
                else
                {
                    Console.WriteLine("InvokeModelAsync failed with status code "
+ response.HttpStatusCode);
                }
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for AI21 Labs Jurassic-2, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html

type Jurassic2Request struct {
 Prompt      string   `json:"prompt"`
 MaxTokens   int      `json:"maxTokens,omitempty"`
 Temperature float64  `json:"temperature,omitempty"`
}

type Jurassic2Response struct {
    Completions []Completion `json:"completions"`
}
type Completion struct {
    Data Data `json:"data"`
}
type Data struct {
    Text string `json:"text"`
}

// Invokes AI21 Labs Jurassic-2 on Amazon Bedrock to run an inference using the
 input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeJurassic2(prompt string) (string, error)
 {
    modelId := "ai21.j2-mid-v1"

 body, err := json.Marshal(Jurassic2Request {
  Prompt:            prompt,
  MaxTokens:      200,
  Temperature:       0.5,
 })

 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
```

```
 })

 if err != nil { ProcessError(err, modelId) }

 var response Jurassic2Response
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

 return response.Completions[0].Data.Text, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base Jurassic-2 da AI21 Labs de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the AI21 Labs Jurassic-2 model to run an inference
     * based on the provided input.
     *
     * @param prompt The prompt that you want Jurassic to complete.
     * @return The inference response generated by the model.
     */
    public static String invokeJurassic2(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Anthropic Claude, refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
```

```
         */

        String jurassic2ModelId = "ai21.j2-mid-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", prompt)
                .put("temperature", 0.5)
                .put("maxTokens", 200)
                .toString();

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(jurassic2ModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " +
exception);
                    }
                });

        String generatedText = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            generatedText = responseBody
                    .getJSONArray("completions")
                    .getJSONObject(0)
                    .getJSONObject("data")
                    .getString("text");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
```

```
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
        /**
         * Invokes the AI21 Labs Jurassic-2 model to run an inference based on
 the
         * provided input.
         *
         * @param prompt The prompt for Jurassic to complete.
         * @return The generated response.
         */
        public static String invokeJurassic2(String prompt) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for AI21 Labs
 Jurassic-2, refer
                 * to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-jurassic2.html
                 */

                String jurassic2ModelId = "ai21.j2-mid-v1";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", prompt)
                                .put("temperature", 0.5)
                                .put("maxTokens", 200)
                                .toString();
```

```
                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(jurassic2ModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());

                String generatedText = responseBody
                                .getJSONArray("completions")
                                .getJSONObject(0)
                                .getJSONObject("data")
                                .getString("text");

                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";
```

```
import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} Data
 * @property {string} text
 *
 * @typedef {Object} Completion
 * @property {Data} data
 *
 * @typedef {Object} ResponseBody
 * @property {Completion[]} completions
 */

/**
 * Invokes the AI21 Labs Jurassic-2 large-language model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Jurassic-2 to complete.
 * @returns {string} The inference response (completion) from the model.
 */
export const invokeJurassic2 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'ai21.j2-mid-v1';

    /* The different model providers have individual request and response
 formats.
     * For the format, ranges, and default values for AI21 Labs Jurassic-2, refer
 to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html
     */
    const payload = {
        prompt,
        maxTokens: 500,
        temperature: 0.5,
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
```

```
        modelId,
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.completions[0].data.text;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: AI21 Labs Jurassic-2');
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeJurassic2(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
    public function invokeJurassic2($prompt)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for AI21 Labs Jurassic-2,
 refer to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html

        $completion = "";

        try {
            $modelId = 'ai21.j2-mid-v1';

            $body = [
                'prompt' => $prompt,
                'temperature' => 0.5,
                'maxTokens' => 200,
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->completions[0]->data->text;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
    def invoke_jurassic2(self, prompt):
        """
        Invokes the AI21 Labs Jurassic-2 large-language model to run an inference
        using the input provided in the request body.

        :param prompt: The prompt that you want Jurassic-2 to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for AI21 Labs
 Jurassic-2, refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-jurassic2.html

            body = {
                "prompt": prompt,
                "temperature": 0.5,
                "maxTokens": 200,
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="ai21.j2-mid-v1", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            completion = response_body["completions"][0]["data"]["text"]

            return completion
```

```
        except ClientError:
            logger.error("Couldn't invoke Jurassic-2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Invoque o modelo Amazon Titan Text G1 no Amazon Bedrock para geração de texto

O exemplo de código a seguir mostra como invocar o modelo Amazon Titan Text G1 no Amazon Bedrock para geração de texto.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo básico Amazon Titan Text G1 para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";
```

```
/**
 * @typedef {Object} ResponseBody
 * @property {Object[]} results
 */

/**
 * Invokes the Titan Text G1 - Express model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Titan Text Express to
 complete.
 * @returns {object[]} The inference response (results) from the model.
 */
export const invokeTitanTextExpressV1 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'amazon.titan-text-express-v1';

    /* The different model providers have individual request and response
 formats.
     * For the format, ranges, and default values for Titan text, refer to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-text.html
     */
    const textGenerationConfig = {
        maxTokenCount: 4096,
        stopSequences: [],
        temperature: 0,
        topP: 1,
    };

    const payload = {
        inputText: prompt,
        textGenerationConfig,
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
    });
```

```
    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);
        return responseBody.results

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = `Meeting transcript: Miguel: Hi Brant, I want to discuss the
 workstream
    for our new product launch Brant: Sure Miguel, is there anything in
 particular you want
    to discuss? Miguel: Yes, I want to talk about how users enter into the
 product.
    Brant: Ok, in that case let me add in Namita. Namita: Hey everyone
    Brant: Hi Namita, Miguel wants to discuss how users enter into the product.
    Miguel: its too complicated and we should remove friction.
    for example, why do I need to fill out additional forms?
    I also find it difficult to find where to access the product
    when I first land on the landing page. Brant: I would also add that
    I think there are too many steps. Namita: Ok, I can work on the
    landing page to make the product more discoverable but brant
    can you work on the additonal forms? Brant: Yes but I would need
    to work with James from another team as he needs to unblock the sign up
 workflow.
    Miguel can you document any other concerns so that I can discuss with James
 only once?
    Miguel: Sure.
    From the meeting transcript above, Create a list of action items for each
 person.`;

    console.log('\nModel: Titan Text Express v1');
    console.log(`Prompt: ${prompt}`);

    const results = await invokeTitanTextExpressV1(prompt);
    console.log('Completion:');
    for (const result of results) {
```

```
        console.log(result.outputText);
    }
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto

Os exemplos de código a seguir mostram como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base Claude 2 da Anthropic para gerar texto.

```
        /// <summary>
        /// Asynchronously invokes the Anthropic Claude 2 model to run an
 inference based on the provided input.
        /// </summary>
        /// <param name="prompt">The prompt that you want Claude to complete.</
param>
        /// <returns>The inference response from the model</returns>
```

```
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
        /// For the format, ranges, and default values for Anthropic Claude,
 refer to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html
        /// </remarks>
        public static async Task<string> InvokeClaudeAsync(string prompt)
        {
            string claudeModelId = "anthropic.claude-v2";

            // Claude requires you to enclose the prompt as follows:
            string enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", enclosedPrompt },
                { "max_tokens_to_sample", 200 },
                { "temperature", 0.5 },
                { "stop_sequences", new JsonArray("\n\nHuman:") }
            }.ToJsonString();

            string generatedText = "";
            try
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
 InvokeModelRequest()
                {
                    ModelId = claudeModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body).Result?
["completion"]?.GetValue<string>() ?? "";
                }
                else
                {
```

```
                    Console.WriteLine("InvokeModelAsync failed with status code "
 + response.HttpStatusCode);
                }
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for Anthropic Claude, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html

type ClaudeRequest struct {
 Prompt            string   `json:"prompt"`
 MaxTokensToSample int      `json:"max_tokens_to_sample"`
 Temperature       float64  `json:"temperature,omitempty"`
 StopSequences     []string `json:"stop_sequences,omitempty"`
}

type ClaudeResponse struct {
 Completion string `json:"completion"`
```

```
}

// Invokes Anthropic Claude on Amazon Bedrock to run an inference using the input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeClaude(prompt string) (string, error) {
    modelId := "anthropic.claude-v2"

 // Anthropic Claude requires enclosing the prompt as follows:
 enclosedPrompt := "Human: " + prompt + "\n\nAssistant:"

 body, err := json.Marshal(ClaudeRequest {
  Prompt:            enclosedPrompt,
  MaxTokensToSample: 200,
  Temperature:       0.5,
  StopSequences:     []string{"\n\nHuman:"},
 })

 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
 })

 if err != nil { ProcessError(err, modelId) }

 var response ClaudeResponse
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

 return response.Completion, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base Claude 2 da Anthropic de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the Anthropic Claude 2 model to run an inference
 based
     * on the provided input.
     *
     * @param prompt The prompt that you want Claude to complete.
     * @return The inference response from the model.
     */
    public static String invokeClaude(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Anthropic Claude, refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
         */

        String claudeModelId = "anthropic.claude-v2";

        // Claude requires you to enclose the prompt as follows:
        String enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", enclosedPrompt)
                .put("max_tokens_to_sample", 200)
```

```
                .put("temperature", 0.5)
                .put("stop_sequences", List.of("\n\nHuman:"))
                .toString();

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(claudeModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " +
exception);
                    }
                });

        String generatedText = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            generatedText = responseBody.getString("completion");
        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
        /**
         * Invokes the Anthropic Claude 2 model to run an inference based on the
         * provided input.
         *
```

```
         * @param prompt The prompt for Claude to complete.
         * @return The generated response.
         */
        public static String invokeClaude(String prompt) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Anthropic
 Claude, refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html
                 */

                String claudeModelId = "anthropic.claude-v2";

                // Claude requires you to enclose the prompt as follows:
                String enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", enclosedPrompt)
                                .put("max_tokens_to_sample", 200)
                                .put("temperature", 0.5)
                                .put("stop_sequences", List.of("\n\nHuman:"))
                                .toString();

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(claudeModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());

                String generatedText = responseBody.getString("completion");
```

```
                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} ResponseBody
 * @property {string} completion
 */

/**
 * Invokes the Anthropic Claude 2 model to run an inference using the input
 * provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Claude to complete.
 * @returns {string} The inference response (completion) from the model.
 */
export const invokeClaude = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );
```

```
    const modelId = 'anthropic.claude-v2';

    /* Claude requires you to enclose the prompt as follows: */
    const enclosedPrompt = `Human: ${prompt}\n\nAssistant:`;

    /* The different model providers have individual request and response
 formats.
     * For the format, ranges, and default values for Anthropic Claude, refer to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
     */
    const payload = {
        prompt: enclosedPrompt,
        max_tokens_to_sample: 500,
        temperature: 0.5,
        stop_sequences: [ '\n\nHuman:' ],
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.completion;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: Anthropic Claude v2');
```

```
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeClaude(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
    public function invokeClaude($prompt)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for Anthropic Claude, refer
 to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html

        $completion = "";

        try {
            $modelId = 'anthropic.claude-v2';

            # Claude requires you to enclose the prompt as follows:
            $prompt = "\n\nHuman: {$prompt}\n\nAssistant:";
```

```
            $body = [
                'prompt' => $prompt,
                'max_tokens_to_sample' => 200,
                'temperature' => 0.5,
                'stop_sequences' => ["\n\nHuman:"],
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->completion;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
    def invoke_claude(self, prompt):
        """
        Invokes the Anthropic Claude 2 model to run an inference using the input
        provided in the request body.
```

```
        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Anthropic Claude,
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html

            # Claude requires you to enclose the prompt as follows:
            enclosed_prompt = "Human: " + prompt + "\n\nAssistant:"

            body = {
                "prompt": enclosed_prompt,
                "max_tokens_to_sample": 200,
                "temperature": 0.5,
                "stop_sequences": ["\n\nHuman:"],
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="anthropic.claude-v2", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            completion = response_body["completion"]

            return completion

        except ClientError:
            logger.error("Couldn't invoke Anthropic Claude")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto. Este exemplo usa recursos de /US2/CL_JSON que podem não estar disponíveis em algumas versões. NetWeaver

```
    "Claude V2 Input Parameters should be in a format like this:
*   {
*     "prompt":"\n\nHuman:\\nTell me a joke\n\nAssistant:\n",
*     "max_tokens_to_sample":2048,
*     "temperature":0.5,
*     "top_k":250,
*     "top_p":1.0,
*     "stop_sequences":[]
*   }

    DATA: BEGIN OF ls_input,
            prompt               TYPE string,
            max_tokens_to_sample TYPE /aws1/rt_shape_integer,
            temperature          TYPE /aws1/rt_shape_float,
            top_k                TYPE /aws1/rt_shape_integer,
            top_p                TYPE /aws1/rt_shape_float,
            stop_sequences       TYPE /aws1/rt_stringtab,
          END OF ls_input.

    "Leave ls_input-stop_sequences empty.
    ls_input-prompt = |\n\nHuman:\\n{ iv_prompt }\n\nAssistant:\n|.
    ls_input-max_tokens_to_sample = 2048.
    ls_input-temperature = '0.5'.
    ls_input-top_k = 250.
    ls_input-top_p = 1.

    "Serialize into JSON with /ui2/cl_json -- this assumes SAP_UI is installed.
    DATA(lv_json) = /ui2/cl_json=>serialize(
      data = ls_input
```

```
                pretty_name   = /ui2/cl_json=>pretty_mode-low_case ).

    TRY.
        DATA(lo_response) = lo_bdr->invokemodel(
          iv_body = /aws1/cl_rt_util=>string_to_xstring( lv_json )
          iv_modelid = 'anthropic.claude-v2'
          iv_accept = 'application/json'
          iv_contenttype = 'application/json' ).

        "Claude V2 Response format will be:
*       {
*         "completion": "Knock Knock...",
*         "stop_reason": "stop_sequence"
*       }
        DATA: BEGIN OF ls_response,
                completion  TYPE string,
                stop_reason TYPE string,
              END OF ls_response.

        /ui2/cl_json=>deserialize(
          EXPORTING jsonx = lo_response->get_body( )
                    pretty_name = /ui2/cl_json=>pretty_mode-camel_case
          CHANGING  data  = ls_response ).

        DATA(lv_answer) = ls_response-completion.
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

Invoque o modelo básico Anthropic Claude 2 para gerar texto usando o cliente de alto nível L2.

```
    TRY.
        DATA(lo_bdr_l2_claude) = /aws1/
cl_bdr_l2_factory=>create_claude_2( lo_bdr ).
        " iv_prompt can contain a prompt like 'tell me a joke about Java
 programmers'.
        DATA(lv_answer) = lo_bdr_l2_claude->prompt_for_text( iv_prompt ).
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
```

```
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

- Para obter detalhes da API, consulte a InvokeModelreferência da API AWS SDK for SAP ABAP.

Invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta

Os exemplos de código a seguir mostram como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com um fluxo de resposta.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Invocar vários modelos de base no Amazon Bedrock

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
// Each model provider defines their own individual request and response formats.
// For the format, ranges, and default values for the different models, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters.html

type Request struct {
 Prompt            string  `json:"prompt"`
```

```
 MaxTokensToSample int     `json:"max_tokens_to_sample"`
 Temperature       float64 `json:"temperature,omitempty"`
}

type Response struct {
 Completion string `json:"completion"`
}

// Invokes Anthropic Claude on Amazon Bedrock to run an inference and
 asynchronously
// process the response stream.

func (wrapper InvokeModelWithResponseStreamWrapper)
 InvokeModelWithResponseStream(prompt string) (string, error) {

 modelId := "anthropic.claude-v2"

 // Anthropic Claude requires you to enclose the prompt as follows:
 prefix := "Human: "
 postfix := "\n\nAssistant:"
 prompt = prefix + prompt + postfix

 request := ClaudeRequest{
  Prompt:            prompt,
  MaxTokensToSample: 200,
  Temperature:       0.5,
  StopSequences:     []string{"\n\nHuman:"},
 }

 body, err := json.Marshal(request)
 if err != nil {
  log.Panicln("Couldn't marshal the request: ", err)
 }

 output, err :=
 wrapper.BedrockRuntimeClient.InvokeModelWithResponseStream(context.Background(),
 &bedrockruntime.InvokeModelWithResponseStreamInput{
  Body:        body,
  ModelId:     aws.String(modelId),
  ContentType: aws.String("application/json"),
 })

 if err != nil {
  errMsg := err.Error()
```

```
  if strings.Contains(errMsg, "no such host") {
   log.Printf("The Bedrock service is not available in the selected region.
 Please double-check the service availability for your region at https://
aws.amazon.com/about-aws/global-infrastructure/regional-product-services/.\n")
  } else if strings.Contains(errMsg, "Could not resolve the foundation model") {
   log.Printf("Could not resolve the foundation model from model identifier: \"%v
\". Please verify that the requested model exists and is accessible within the
 specified region.\n", modelId)
  } else {
   log.Printf("Couldn't invoke Anthropic Claude. Here's why: %v\n", err)
  }
 }

 resp, err := processStreamingOutput(output, func(ctx context.Context, part
 []byte) error {
  fmt.Print(string(part))
  return nil
 })

 if err != nil {
  log.Fatal("streaming output processing error: ", err)
 }

 return resp.Completion, nil

}

type StreamingOutputHandler func(ctx context.Context, part []byte) error

func processStreamingOutput(output
 *bedrockruntime.InvokeModelWithResponseStreamOutput, handler
 StreamingOutputHandler) (Response, error) {

 var combinedResult string
 resp := Response{}

 for event := range output.GetStream().Events() {
  switch v := event.(type) {
  case *types.ResponseStreamMemberChunk:

   //fmt.Println("payload", string(v.Value.Bytes))

   var resp Response
   err := json.NewDecoder(bytes.NewReader(v.Value.Bytes)).Decode(&resp)
```

```
    if err != nil {
     return resp, err
    }

    err = handler(context.Background(), []byte(resp.Completion))
    if err != nil {
     return resp, err
    }

    combinedResult += resp.Completion

   case *types.UnknownUnionMember:
    fmt.Println("unknown tag:", v.Tag)

   default:
    fmt.Println("union is nil or unknown type")
   }
  }

  resp.Completion = combinedResult

  return resp, nil
 }
```

- Para obter detalhes da API, consulte InvokeModelWithResponseStreama Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
        /**
```

```
        * Invokes the Anthropic Claude 2 model and processes the response
stream.
        *
        * @param prompt The prompt for Claude to complete.
        * @param silent Suppress console output of the individual response
stream
        *               chunks.
        * @return The generated response.
        */
       public static String invokeClaude(String prompt, boolean silent) {

               BedrockRuntimeAsyncClient client =
BedrockRuntimeAsyncClient.builder()
                               .region(Region.US_EAST_1)

.credentialsProvider(ProfileCredentialsProvider.create())
                               .build();

               var finalCompletion = new AtomicReference<>("");

               var payload = new JSONObject()
                               .put("prompt", "Human: " + prompt + "
Assistant:")
                               .put("temperature", 0.8)
                               .put("max_tokens_to_sample", 300)
                               .toString();

               var request = InvokeModelWithResponseStreamRequest.builder()
                               .body(SdkBytes.fromUtf8String(payload))
                               .modelId("anthropic.claude-v2")
                               .contentType("application/json")
                               .accept("application/json")
                               .build();

               var visitor =
InvokeModelWithResponseStreamResponseHandler.Visitor.builder()
                               .onChunk(chunk -> {
                                       var json = new
JSONObject(chunk.bytes().asUtf8String());
                                       var completion =
json.getString("completion");
                                       finalCompletion.set(finalCompletion.get()
+ completion);
                                       if (!silent) {
```

```
                                                System.out.print(completion);
                                        }
                                })
                                .build();

                var handler =
 InvokeModelWithResponseStreamResponseHandler.builder()
                                .onEventStream(stream -> stream.subscribe(event -
> event.accept(visitor)))
                                .onComplete(() -> {
                                })
                                .onError(e -> System.out.println("\n\nError: " +
 e.getMessage()))
                                .build();

                client.invokeModelWithResponseStream(request, handler).join();

                return finalCompletion.get();
        }
```

- Para obter detalhes da API, consulte InvokeModelWithResponseStreama Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
    async def invoke_model_with_response_stream(self, prompt):
        """
        Invokes the Anthropic Claude 2 model to run an inference and process the
 response stream.
```

```
        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Anthropic Claude,
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html

            # Claude requires you to enclose the prompt as follows:
            enclosed_prompt = "Human: " + prompt + "\n\nAssistant:"

            body = {
                "prompt": enclosed_prompt,
                "max_tokens_to_sample": 1024,
                "temperature": 0.5,
                "stop_sequences": ["\n\nHuman:"],
            }

            response =
 self.bedrock_runtime_client.invoke_model_with_response_stream(
                modelId="anthropic.claude-v2", body=json.dumps(body)
            )

            for event in response.get("body"):
                chunk = json.loads(event["chunk"]["bytes"])["completion"]
                yield chunk

        except ClientError:
            logger.error("Couldn't invoke Anthropic Claude v2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelWithResponseStreamReferência da API AWSSDK for Python (Boto3).

Invoque o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto

Os exemplos de código a seguir mostram como invocar o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Invocar vários modelos de base no Amazon Bedrock
- Invocar vários LLMs no Amazon Bedrock

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base da Meta Llama 2 para gerar texto.

```
        /// <summary>
        /// Asynchronously invokes the Meta Llama 2 Chat model to run an
 inference based on the provided input.
        /// </summary>
        /// <param name="prompt">The prompt that you want Llama 2 to complete.</
param>
        /// <returns>The inference response from the model</returns>
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
        /// For the format, ranges, and default values for Meta Llama 2 Chat,
 refer to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-meta.html
        /// </remarks>
        public static async Task<string> InvokeLlama2Async(string prompt)
        {
```

```
            string llama2ModelId = "meta.llama2-13b-chat-v1";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", prompt },
                { "max_gen_len", 512 },
                { "temperature", 0.5 },
                { "top_p", 0.9 }
            }.ToJsonString();

            string generatedText = "";
            try
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
InvokeModelRequest()
                {
                    ModelId = llama2ModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body)
                        .Result?["generation"]?.GetValue<string>() ?? "";
                }
                else
                {
                    Console.WriteLine("InvokeModelAsync failed with status code "
+ response.HttpStatusCode);
                }
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for Meta Llama 2 Chat, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html

type Llama2Request struct {
 Prompt            string   `json:"prompt"`
 MaxGenLength    int      `json:"max_gen_len,omitempty"`
 Temperature       float64  `json:"temperature,omitempty"`
}

type Llama2Response struct {
 Generation string `json:"generation"`
}

// Invokes Meta Llama 2 Chat on Amazon Bedrock to run an inference using the
 input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeLlama2(prompt string) (string, error) {
    modelId := "meta.llama2-13b-chat-v1"

 body, err := json.Marshal(Llama2Request {
  Prompt:            prompt,
  MaxGenLength:    512,
  Temperature:       0.5,
 })
```

```
 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
 })

 if err != nil { ProcessError(err, modelId) }

 var response Llama2Response
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }



 return response.Generation, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base do Llama 2 Chat da Meta de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the Meta Llama 2 Chat model to run an inference
based
     * on the provided input.
     *
     * @param prompt The prompt that you want Llama 2 to complete.
```

```
     * @return The inference response generated by the model.
     */
    public static String invokeLlama2(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Meta Llama 2 Chat,
 refer to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.
         * html
         */

        String llama2ModelId = "meta.llama2-13b-chat-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", prompt)
                .put("max_gen_len", 512)
                .put("temperature", 0.5)
                .put("top_p", 0.9)
                .toString();

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(llama2ModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
 client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " +
 exception);
                    }
                });

        String generatedText = "";
```

```
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());
            generatedText = responseBody.getString("generation");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invoque o modelo base do Llama 2 Chat da Meta para gerar texto.

```
        /**
         * Invokes the Meta Llama 2 Chat model to run an inference based on the
 provided
         * input.
         *
         * @param prompt The prompt for Llama 2 to complete.
         * @return The generated response.
         */
        public static String invokeLlama2(String prompt) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Meta Llama 2
 Chat, refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-meta.
                 * html
                 */

                String llama2ModelId = "meta.llama2-13b-chat-v1";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)
```

```
.credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", prompt)
                                .put("max_gen_len", 512)
                                .put("temperature", 0.5)
                                .put("top_p", 0.9)
                                .toString();

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(llama2ModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
JSONObject(response.body().asUtf8String());

                String generatedText = responseBody.getString("generation");

                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} ResponseBody
 * @property {generation} text
 */

/**
 * Invokes the Meta Llama 2 Chat model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Llama-2 to complete.
 * @returns {string} The inference response (generation) from the model.
 */
export const invokeLlama2 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'meta.llama2-13b-chat-v1';

    /* The different model providers have individual request and response
 formats.
     * For the format, ranges, and default values for Meta Llama 2 Chat, refer
 to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html
     */
    const payload = {
        prompt,
        temperature: 0.5,
        top_p: 0.9,
        max_gen_len: 512,
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
```

```
        accept: 'application/json',
        modelId,
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.generation;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: Meta Llama 2 Chat');
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeLlama2(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
    public function invokeLlama2($prompt)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for Meta Llama 2 Chat, refer
 to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html

        $completion = "";

        try {
            $modelId = 'meta.llama2-13b-chat-v1';

            $body = [
                'prompt' => $prompt,
                'temperature' => 0.5,
                'max_gen_len' => 512,
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->generation;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
```

```
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
    def invoke_llama2(self, prompt):
        """
        Invokes the Meta Llama 2 large-language model to run an inference
        using the input provided in the request body.

        :param prompt: The prompt that you want Llama 2 to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Meta Llama 2 Chat,
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-meta.html

            body = {
                "prompt": prompt,
                "temperature": 0.5,
                "top_p": 0.9,
                "max_gen_len": 512,
```

```
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="meta.llama2-13b-chat-v1", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            completion = response_body["generation"]

            return completion

        except ClientError:
            logger.error("Couldn't invoke Llama 2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Cenários para o Amazon Bedrock Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Bedrock Runtime com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie um aplicativo de amostra que ofereça playgrounds para interagir com os modelos de base do Amazon Bedrock usando um SDK da AWS
- Invocar vários grandes modelos de linguagem (LLMs) no Amazon Bedrock
- Invocar vários modelos de base no Amazon Bedrock
- Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Crie um aplicativo de amostra que ofereça playgrounds para interagir com os modelos de base do Amazon Bedrock usando um SDK da AWS

Os exemplos de código a seguir mostram como criar playgrounds para interagir com os modelos da base do Amazon Bedrock em diferentes modalidades.

.NET

AWS SDK for .NET

O .NET Foundation Model (FM) Playground é um aplicativo de amostra do .NET MAUI Blazor que mostra como usar o Amazon Bedrock a partir do código C#. Este exemplo mostra como os desenvolvedores.NET e C# podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de bate-papo.
- Um playground de bate-papo por voz.
- Um playground de imagens.

O exemplo também lista e exibe os modelos básicos para acesso e suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Tempo de execução do Amazon Bedrock

Java

SDK para Java 2.x

O modelo de base (FM) Java Playground é um aplicativo de amostra do Spring Boot que mostra como usar o Amazon Bedrock com Java. Este exemplo mostra como os desenvolvedores Java podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de conversa.

- Um playground de imagens.

O exemplo também lista e exibe os modelos de base aos quais tem-se acesso, junto com suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Tempo de execução do Amazon Bedrock

Python

SDK para Python (Boto3)

O modelo de base (FM) Python Playground é um aplicativo de amostra em Python/FastAPI que mostra como usar o Amazon Bedrock com Python. Este exemplo mostra como os desenvolvedores Python podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de conversa.
- Um playground de imagens.

O exemplo também lista e exibe os modelos de base aos quais tem-se acesso, junto com suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock Runtime

Invocar vários grandes modelos de linguagem (LLMs) no Amazon Bedrock

O exemplo de código a seguir mostra como invocar vários large-language-models (LLMs) no Amazon Bedrock.

- Gere texto com Claude da Anthropic.
- Gere texto com o AI21 Labs Jurassic-2.
- Gere texto com o Chat Llama 2 da Meta.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque vários LLMs no Amazon Bedrock.

```
namespace BedrockRuntime;

class GettingStartedWithBedrockRuntime
{
    protected BedrockRuntimeService $bedrockRuntimeService;

    public function runExample()
    {
        echo "\n";
        echo
 "----------------------------------------------------------------------\n";
        echo "Welcome to the Amazon Bedrock Runtime getting started demo using
 PHP!\n";
        echo
 "----------------------------------------------------------------------\n";

        $clientArgs = [
            'region' => 'us-east-1',
            'version' => 'latest',
            'profile' => 'default',
        ];

        $bedrockRuntimeService = new BedrockRuntimeService($clientArgs);

        $prompt = 'In one paragraph, who are you?';

        echo "\nPrompt: " . $prompt;

        echo "\n\nAnthropic Claude:";
        echo $bedrockRuntimeService->invokeClaude($prompt);
```

```
        echo "\n\nAI21 Labs Jurassic-2: ";
        echo $bedrockRuntimeService->invokeJurassic2($prompt);

        echo "\n\nMeta Llama 2 Chat: ";
        echo $bedrockRuntimeService->invokeLlama2($prompt);

        echo
 "\n----------------------------------------------------------------------\n";

        $image_prompt = 'stylized picture of a cute old steampunk robot';

        echo "\nImage prompt: " . $image_prompt;

        echo "\n\nStability.ai Stable Diffusion XL:\n";
        $diffusionSeed = rand(0, 4294967295);
        $style_preset = 'photographic';
        $base64 = $bedrockRuntimeService->invokeStableDiffusion($image_prompt,
 $diffusionSeed, $style_preset);
        $image_path = $this->saveImage($base64, 'stability.stable-diffusion-xl');
        echo "The generated images have been saved to $image_path";

        echo "\n\nAmazon Titan Image Generation:\n";
        $titanSeed = rand(0, 2147483647);
        $base64 = $bedrockRuntimeService->invokeTitanImage($image_prompt,
 $titanSeed);
        $image_path = $this->saveImage($base64, 'amazon.titan-image-generator-
v1');
        echo "The generated images have been saved to $image_path";
    }

    private function saveImage($base64_image_data, $model_id): string
    {
        $output_dir = "output";

        if (!file_exists($output_dir)) {
            mkdir($output_dir);
        }

        $i = 1;
        while (file_exists("$output_dir/$model_id" . '_' . "$i.png")) {
            $i++;
        }

        $image_data = base64_decode($base64_image_data);
```

```
        $file_path = "$output_dir/$model_id" . '_' . "$i.png";

        $file = fopen($file_path, 'wb');
        fwrite($file, $image_data);
        fclose($file);

        return $file_path;
    }
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Invocar vários modelos de base no Amazon Bedrock

O exemplo de código a seguir mostra como invocar vários modelos de base no Amazon Bedrock.

- Gere texto com Claude da Anthropic.
- Gere texto com o AI21 Labs Jurassic-2.
- Gere texto com o Chat Llama 2 da Meta.
- Processe o fluxo de resposta do Claude da Anthropic de forma assíncrona.
- Gere uma imagem com o Amazon Titan Image Generator.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque vários modelos de base no Amazon Bedrock.

```
// InvokeModelsScenario demonstrates how to use the Amazon Bedrock Runtime client
```

```
// to invoke various foundation models for text and image generation
//
// 1. Generate text with Anthropic Claude 2
// 2. Generate text with AI21 Labs Jurassic-2
// 3. Generate text with Meta Llama 2 Chat
// 4. Generate text and asynchronously process the response stream with Anthropic
 Claude 2
// 5. Generate and image with the Amazon Titan image generation model
type InvokeModelsScenario struct {
 sdkConfig             aws.Config
 invokeModelWrapper    actions.InvokeModelWrapper
 responseStreamWrapper actions.InvokeModelWithResponseStreamWrapper
 questioner            demotools.IQuestioner
}

// NewInvokeModelsScenario constructs an InvokeModelsScenario instance from a
 configuration.
// It uses the specified config to get a Bedrock Runtime client and create
 wrappers for the
// actions used in the scenario.
func NewInvokeModelsScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner) InvokeModelsScenario {
 client := bedrockruntime.NewFromConfig(sdkConfig)
 return InvokeModelsScenario{
  sdkConfig:             sdkConfig,
  invokeModelWrapper:    actions.InvokeModelWrapper{BedrockRuntimeClient:
 client},
  responseStreamWrapper:
 actions.InvokeModelWithResponseStreamWrapper{BedrockRuntimeClient: client},
  questioner:            questioner,
 }
}

// Runs the interactive scenario.
func (scenario InvokeModelsScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo: %v\n", r)
  }
 }()

 log.Println(strings.Repeat("=", 77))
 log.Println("Welcome to the Amazon Bedrock Runtime model invocation demo.")
 log.Println(strings.Repeat("=", 77))
```

```
 log.Printf("First, let's invoke a few large-language models using the
 synchronous client:\n\n")

 text2textPrompt := "In one paragraph, who are you?"

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Claude with prompt: %v\n", text2textPrompt)
 scenario.InvokeClaude(text2textPrompt)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Jurassic-2 with prompt: %v\n", text2textPrompt)
 scenario.InvokeJurassic2(text2textPrompt)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Llama2 with prompt: %v\n", text2textPrompt)
 scenario.InvokeLlama2(text2textPrompt)

 log.Println(strings.Repeat("=", 77))
 log.Printf("Now, let's invoke Claude with the asynchronous client and process
 the response stream:\n\n")

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Claude with prompt: %v\n", text2textPrompt)
 scenario.InvokeWithResponseStream(text2textPrompt)

 log.Println(strings.Repeat("=", 77))
 log.Printf("Now, let's create an image with the Amazon Titan image generation
 model:\n\n")

 text2ImagePrompt := "stylized picture of a cute old steampunk robot"
 seed := rand.Int63n(2147483648)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Amazon Titan with prompt: %v\n", text2ImagePrompt)
 scenario.InvokeTitanImage(text2ImagePrompt, seed)

 log.Println(strings.Repeat("=", 77))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("=", 77))
}

func (scenario InvokeModelsScenario) InvokeClaude(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeClaude(prompt)
```

```
 if err != nil {
  panic(err)
 }
 log.Printf("\nClaude     : %v\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeJurassic2(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeJurassic2(prompt)
 if err != nil {
  panic(err)
 }
 log.Printf("\nJurassic-2 : %v\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeLlama2(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeLlama2(prompt)
 if err != nil {
  panic(err)
 }
 log.Printf("\nLlama 2    : %v\n\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeWithResponseStream(prompt string) {
 log.Println("\nClaude with response stream:")
 _, err := scenario.responseStreamWrapper.InvokeModelWithResponseStream(prompt)
 if err != nil {
  panic(err)
 }
 log.Println()
}

func (scenario InvokeModelsScenario) InvokeTitanImage(prompt string, seed int64)
 {
 base64ImageData, err := scenario.invokeModelWrapper.InvokeTitanImage(prompt,
 seed)
 if err != nil {
  panic(err)
 }
 imagePath := saveImage(base64ImageData, "amazon.titan-image-generator-v1")
 fmt.Printf("The generated image has been saved to %s\n", imagePath)
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - InvokeModel
  - InvokeModelWithResponseStream

Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

Python

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de código para agentes do Amazon Bedrock usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock com um kit de desenvolvimento AWS de software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Agents for Amazon Bedrock — Mais informações sobre Agents for Amazon Bedrock.
- Referência da API Agents for Amazon Bedrock — Detalhes sobre todas as ações disponíveis de Agents for Amazon Bedrock.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para agentes do Amazon Bedrock usando SDKs AWS
  - Criar um agente do Amazon Bedrock usando um SDK da AWS

- Criar um grupo de ações do agente do Amazon Bedrock usando um SDK da AWS
- Criar um alias de agente do Amazon Bedrock usando um SDK da AWS
- Excluir um agente do Amazon Bedrock usando um SDK da AWS
- Excluir um alias de agente do Amazon Bedrock usando um SDK da AWS
- Obter informações sobre um usuário do Amazon Bedrock usando um SDK da AWS
- Listar os grupos de ação de um agente do Amazon Bedrock usando um SDK da AWS
- Listar os agentes do Amazon Bedrock pertencentes a uma conta usando um SDK da AWS
- Listar as bases de conhecimento associadas a um agente do Amazon Bedrock usando um SDK da AWS
- Preparar um agente do Amazon Bedrock usando um SDK da AWS

- Cenários para agentes do Amazon Bedrock usando SDKs AWS
  - Um end-to-end exemplo mostrando como criar e invocar agentes do Amazon Bedrock usando um SDK AWS
  - Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Ações para agentes do Amazon Bedrock usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para agentes do Amazon Bedrock usando SDKs AWS.

Exemplos

- Criar um agente do Amazon Bedrock usando um SDK da AWS
- Criar um grupo de ações do agente do Amazon Bedrock usando um SDK da AWS
- Criar um alias de agente do Amazon Bedrock usando um SDK da AWS
- Excluir um agente do Amazon Bedrock usando um SDK da AWS
- Excluir um alias de agente do Amazon Bedrock usando um SDK da AWS
- Obter informações sobre um usuário do Amazon Bedrock usando um SDK da AWS
- Listar os grupos de ação de um agente do Amazon Bedrock usando um SDK da AWS
- Listar os agentes do Amazon Bedrock pertencentes a uma conta usando um SDK da AWS

- Listar as bases de conhecimento associadas a um agente do Amazon Bedrock usando um SDK da AWS
- Preparar um agente do Amazon Bedrock usando um SDK da AWS

Criar um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como criar um agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um agente do .

```
    def create_agent(self, agent_name, foundation_model, role_arn, instruction):
        """
        Creates an agent that orchestrates interactions between foundation
models,
        data sources, software applications, user conversations, and APIs to
carry
        out tasks to help customers.

        :param agent_name: A name for the agent.
        :param foundation_model: The foundation model to be used for
orchestration by the agent.
        :param role_arn: The ARN of the IAM role with permissions needed by the
agent.
        :param instruction: Instructions that tell the agent what it should do
and how it should
```

```
                                interact with users.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """
        try:
            response = self.client.create_agent(
                agentName=agent_name,
                foundationModel=foundation_model,
                agentResourceRoleArn=role_arn,
                instruction=instruction,
            )
        except ClientError as e:
            logger.error(f"Error: Couldn't create agent. Here's why: {e}")
            raise
        else:
            return response["agent"]
```

- Para obter detalhes da API, consulte a CreateAgentReferência da API AWSSDK for Python (Boto3).

Criar um grupo de ações do agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como criar um grupo de ações do agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um grupo de ação do agente.

```
    def create_agent_action_group(
        self, name, description, agent_id, agent_version, function_arn,
api_schema
    ):
        """
        Creates an action group for an agent. An action group defines a set of
actions that an
        agent should carry out for the customer.

        :param name: The name to give the action group.
        :param description: The description of the action group.
        :param agent_id: The unique identifier of the agent for which to create
the action group.
        :param agent_version: The version of the agent for which to create the
action group.
        :param function_arn: The ARN of the Lambda function containing the
business logic that is
                                carried out upon invoking the action.
        :param api_schema: Contains the OpenAPI schema for the action group.
        :return: Details about the action group that was created.
        """
        try:
            response = self.client.create_agent_action_group(
                actionGroupName=name,
                description=description,
                agentId=agent_id,
                agentVersion=agent_version,
                actionGroupExecutor={"lambda": function_arn},
                apiSchema={"payload": api_schema},
            )
            agent_action_group = response["agentActionGroup"]
        except ClientError as e:
            logger.error(f"Error: Couldn't create agent action group. Here's why:
{e}")
            raise
        else:
            return agent_action_group
```

- Para obter detalhes da API, consulte a CreateAgentActionGroupReferência da API AWSSDK for Python (Boto3).

Criar um alias de agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como criar um alias de agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um alias de agente.

```
    def create_agent_alias(self, name, agent_id):
        """
        Creates an alias of an agent that can be used to deploy the agent.

        :param name: The name of the alias.
        :param agent_id: The unique identifier of the agent.
        :return: Details about the alias that was created.
        """
        try:
            response = self.client.create_agent_alias(
                agentAliasName=name, agentId=agent_id
            )
            agent_alias = response["agentAlias"]
        except ClientError as e:
            logger.error(f"Couldn't create agent alias. {e}")
            raise
```

```
        else:
            return agent_alias
```

- Para obter detalhes da API, consulte a CreateAgentAliasReferência da API AWSSDK for Python (Boto3).

Excluir um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um agente.

```
    def delete_agent(self, agent_id):
        """
        Deletes an Amazon Bedrock agent.

        :param agent_id: The unique identifier of the agent to delete.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """

        try:
            response = self.client.delete_agent(
```

```
                agentId=agent_id, skipResourceInUseCheck=False
            )
        except ClientError as e:
            logger.error(f"Couldn't delete agent. {e}")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteAgentReferência da API AWSSDK for Python (Boto3).

Excluir um alias de agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um alias de agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um alias de agente.

```
    def delete_agent_alias(self, agent_id, agent_alias_id):
        """
        Deletes an alias of an Amazon Bedrock agent.

        :param agent_id: The unique identifier of the agent that the alias
belongs to.
```

```
        :param agent_alias_id: The unique identifier of the alias to delete.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """

        try:
            response = self.client.delete_agent_alias(
                agentId=agent_id, agentAliasId=agent_alias_id
            )
        except ClientError as e:
            logger.error(f"Couldn't delete agent alias. {e}")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteAgentAliasReferência da API AWSSDK for Python (Boto3).

Obter informações sobre um usuário do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como obter informações sobre um agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um agente.

```
    def get_agent(self, agent_id, log_error=True):
        """
        Gets information about an agent.

        :param agent_id: The unique identifier of the agent.
        :param log_error: Whether to log any errors that occur when getting the
agent.
                          If True, errors will be logged to the logger. If False,
errors
                          will still be raised, but not logged.
        :return: The information about the requested agent.
        """

        try:
            response = self.client.get_agent(agentId=agent_id)
            agent = response["agent"]
        except ClientError as e:
            if log_error:
                logger.error(f"Couldn't get agent {agent_id}. {e}")
            raise
        else:
            return agent
```

- Para obter detalhes da API, consulte a GetAgentReferência da API AWSSDK for Python (Boto3).

Listar os grupos de ação de um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como listar os grupos de ação de um agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os grupos de ação de um agente.

```
    def list_agent_action_groups(self, agent_id, agent_version):
        """
        List the action groups for a version of an Amazon Bedrock Agent.

        :param agent_id: The unique identifier of the agent.
        :param agent_version: The version of the agent.
        :return: The list of action group summaries for the version of the agent.
        """

        try:
            action_groups = []

            paginator = self.client.get_paginator("list_agent_action_groups")
            for page in paginator.paginate(
                agentId=agent_id,
                agentVersion=agent_version,
                PaginationConfig={"PageSize": 10},
            ):
                action_groups.extend(page["actionGroupSummaries"])

        except ClientError as e:
            logger.error(f"Couldn't list action groups. {e}")
            raise
        else:
            return action_groups
```

- Para obter detalhes da API, consulte a ListAgentActionGroupsReferência da API AWSSDK for Python (Boto3).

Listar os agentes do Amazon Bedrock pertencentes a uma conta usando um SDK da AWS

O exemplo de código a seguir mostra como listar os agentes do Amazon Bedrock que pertencem a uma conta.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os agentes que pertencem a uma conta.

```
    def list_agents(self):
        """
        List the available Amazon Bedrock Agents.

        :return: The list of available bedrock agents.
        """

        try:
            all_agents = []

            paginator = self.client.get_paginator("list_agents")
            for page in paginator.paginate(PaginationConfig={"PageSize": 10}):
                all_agents.extend(page["agentSummaries"])

        except ClientError as e:
            logger.error(f"Couldn't list agents. {e}")
            raise
        else:
```

```
            return all_agents
```

- Para obter detalhes da API, consulte a ListAgentsReferência da API AWSSDK for Python (Boto3).

Listar as bases de conhecimento associadas a um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como listar as bases de conhecimento associadas a um agente do Amazon Bedrock.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as bases de conhecimento associadas a um agente.

```
    def list_agent_knowledge_bases(self, agent_id, agent_version):
        """
        List the knowledge bases associated with a version of an Amazon Bedrock
Agent.

        :param agent_id: The unique identifier of the agent.
        :param agent_version: The version of the agent.
        :return: The list of knowledge base summaries for the version of the
agent.
```

```
        """

        try:
            knowledge_bases = []

            paginator = self.client.get_paginator("list_agent_knowledge_bases")
            for page in paginator.paginate(
                agentId=agent_id,
                agentVersion=agent_version,
                PaginationConfig={"PageSize": 10},
            ):
                knowledge_bases.extend(page["agentKnowledgeBaseSummaries"])

        except ClientError as e:
            logger.error(f"Couldn't list knowledge bases. {e}")
            raise
        else:
            return knowledge_bases
```

- Para obter detalhes da API, consulte a ListAgentKnowledgeBasesReferência da API AWSSDK for Python (Boto3).

Preparar um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como preparar um agente do Amazon Bedrock para testes internos.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e invocar um agente

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Prepare um agente para testes internos.

```
    def prepare_agent(self, agent_id):
        """
        Creates a DRAFT version of the agent that can be used for internal
testing.

        :param agent_id: The unique identifier of the agent to prepare.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """
        try:
            prepared_agent_details = self.client.prepare_agent(agentId=agent_id)
        except ClientError as e:
            logger.error(f"Couldn't prepare agent. {e}")
            raise
        else:
            return prepared_agent_details
```

- Para obter detalhes da API, consulte a PrepareAgentReferência da API AWSSDK for Python (Boto3).

Cenários para agentes do Amazon Bedrock usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Um end-to-end exemplo mostrando como criar e invocar agentes do Amazon Bedrock usando um SDK AWS
- Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Um end-to-end exemplo mostrando como criar e invocar agentes do Amazon Bedrock usando um SDK AWS

O código de exemplo a seguir mostra como:

- Crie um perfil de execução para o agente.
- Crie o agente e implante uma versão de RASCUNHO.
- Crie uma função do Lambda que implante os recursos do agente.
- Crie um grupo de ação que conecte o agente à função do Lambda.
- Implante o agente totalmente configurado.
- Invoque o agente com prompts fornecidos pelo usuário.
- Exclua todos os recursos criados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e invoque um agente.

```
REGION = "us-east-1"
ROLE_POLICY_NAME = "agent_permissions"
```

```
class BedrockAgentScenarioWrapper:
    """Runs a scenario that shows how to get started using Agents for Amazon
 Bedrock."""

    def __init__(
        self, bedrock_agent_client, runtime_client, lambda_client, iam_resource,
 postfix
    ):
        self.iam_resource = iam_resource
        self.lambda_client = lambda_client
        self.bedrock_agent_runtime_client = runtime_client
        self.postfix = postfix

        self.bedrock_wrapper = BedrockAgentWrapper(bedrock_agent_client)

        self.agent = None
        self.agent_alias = None
        self.agent_role = None
        self.prepared_agent_details = None
        self.lambda_role = None
        self.lambda_function = None

    def run_scenario(self):
        print("=" * 88)
        print("Welcome to the Amazon Bedrock Agents demo.")
        print("=" * 88)

        # Query input from user
        print("Let's start with creating an agent:")
        print("-" * 40)
        name, foundation_model = self._request_name_and_model_from_user()
        print("-" * 40)

        # Create an execution role for the agent
        self.agent_role = self._create_agent_role(foundation_model)

        # Create the agent
        self.agent = self._create_agent(name, foundation_model)

        # Prepare a DRAFT version of the agent
        self.prepared_agent_details = self._prepare_agent()

        # Create the agent's Lambda function
        self.lambda_function = self._create_lambda_function()
```

```
        # Configure permissions for the agent to invoke the Lambda function
        self._allow_agent_to_invoke_function()
        self._let_function_accept_invocations_from_agent()

        # Create an action group to connect the agent with the Lambda function
        self._create_agent_action_group()

        # If the agent has been modified or any components have been added,
prepare the agent again
        components = [self._get_agent()]
        components += self._get_agent_action_groups()
        components += self._get_agent_knowledge_bases()

        latest_update = max(component["updatedAt"] for component in components)
        if latest_update > self.prepared_agent_details["preparedAt"]:
            self.prepared_agent_details = self._prepare_agent()

        # Create an agent alias
        self.agent_alias = self._create_agent_alias()

        # Test the agent
        self._chat_with_agent(self.agent_alias)

        print("=" * 88)
        print("Thanks for running the demo!\n")

        if q.ask("Do you want to delete the created resources? [y/N] ",
q.is_yesno):
            self._delete_resources()
            print("=" * 88)
            print(
                "All demo resources have been deleted. Thanks again for running
the demo!"
            )
        else:
            self._list_resources()
            print("=" * 88)
            print("Thanks again for running the demo!")

    def _request_name_and_model_from_user(self):
        existing_agent_names = [
            agent["agentName"] for agent in self.bedrock_wrapper.list_agents()
        ]
```

```
        while True:
            name = q.ask("Enter an agent name: ", self.is_valid_agent_name)
            if name.lower() not in [n.lower() for n in existing_agent_names]:
                break
            print(
                f"Agent {name} conflicts with an existing agent. Please use a
different name."
            )

        models = ["anthropic.claude-instant-v1", "anthropic.claude-v2"]
        model_id = models[
            q.choose("Which foundation model would you like to use? ", models)
        ]

        return name, model_id

    def _create_agent_role(self, model_id):
        role_name = f"AmazonBedrockExecutionRoleForAgents_{self.postfix}"
        model_arn = f"arn:aws:bedrock:{REGION}::foundation-model/{model_id}*"

        print("Creating an an execution role for the agent...")

        try:
            role = self.iam_resource.create_role(
                RoleName=role_name,
                AssumeRolePolicyDocument=json.dumps(
                    {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
                                "Principal": {"Service":
"bedrock.amazonaws.com"},
                                "Action": "sts:AssumeRole",
                            }
                        ],
                    }
                ),
            )

            role.Policy(ROLE_POLICY_NAME).put(
                PolicyDocument=json.dumps(
                    {
```

```
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
                                "Action": "bedrock:InvokeModel",
                                "Resource": model_arn,
                            }
                        ],
                    }
                )
            )
        except ClientError as e:
            logger.error(f"Couldn't create role {role_name}. Here's why: {e}")
            raise

        return role

    def _create_agent(self, name, model_id):
        print("Creating the agent...")

        instruction = """
            You are a friendly chat bot. You have access to a function called
that returns
            information about the current date and time. When responding with
date or time,
            please make sure to add the timezone UTC.
            """
        agent = self.bedrock_wrapper.create_agent(
            agent_name=name,
            foundation_model=model_id,
            instruction=instruction,
            role_arn=self.agent_role.arn,
        )
        self._wait_for_agent_status(agent["agentId"], "NOT_PREPARED")

        return agent

    def _prepare_agent(self):
        print("Preparing the agent...")

        agent_id = self.agent["agentId"]
        prepared_agent_details = self.bedrock_wrapper.prepare_agent(agent_id)
        self._wait_for_agent_status(agent_id, "PREPARED")
```

```
        return prepared_agent_details

    def _create_lambda_function(self):
        print("Creating the Lambda function...")

        function_name = f"AmazonBedrockExampleFunction_{self.postfix}"

        self.lambda_role = self._create_lambda_role()

        try:
            deployment_package = self._create_deployment_package(function_name)

            lambda_function = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="Lambda function for Amazon Bedrock example",
                Runtime="python3.11",
                Role=self.lambda_role.arn,
                Handler=f"{function_name}.lambda_handler",
                Code={"ZipFile": deployment_package},
                Publish=True,
            )

            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)

        except ClientError as e:
            logger.error(
                f"Couldn't create Lambda function {function_name}. Here's why:
{e}"
            )
            raise

        return lambda_function

    def _create_lambda_role(self):
        print("Creating an execution role for the Lambda function...")

        role_name = f"AmazonBedrockExecutionRoleForLambda_{self.postfix}"

        try:
            role = self.iam_resource.create_role(
                RoleName=role_name,
                AssumeRolePolicyDocument=json.dumps(
                    {
```

```
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
                                "Principal": {"Service": "lambda.amazonaws.com"},
                                "Action": "sts:AssumeRole",
                            }
                        ],
                    }
                ),
            )
            role.attach_policy(
                PolicyArn="arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole"
            )
            print(f"Created role {role_name}")
        except ClientError as e:
            logger.error(f"Couldn't create role {role_name}. Here's why: {e}")
            raise

        print("Waiting for the execution role to be fully propagated...")
        wait(10)

        return role

    def _allow_agent_to_invoke_function(self):
        policy = self.iam_resource.RolePolicy(
            self.agent_role.role_name, ROLE_POLICY_NAME
        )
        doc = policy.policy_document
        doc["Statement"].append(
            {
                "Effect": "Allow",
                "Action": "lambda:InvokeFunction",
                "Resource": self.lambda_function["FunctionArn"],
            }
        )

 self.agent_role.Policy(ROLE_POLICY_NAME).put(PolicyDocument=json.dumps(doc))

    def _let_function_accept_invocations_from_agent(self):
        try:
            self.lambda_client.add_permission(
                FunctionName=self.lambda_function["FunctionName"],
```

```
                SourceArn=self.agent["agentArn"],
                StatementId="BedrockAccess",
                Action="lambda:InvokeFunction",
                Principal="bedrock.amazonaws.com",
            )
        except ClientError as e:
            logger.error(
                f"Couldn't grant Bedrock permission to invoke the Lambda
function. Here's why: {e}"
            )
            raise

    def _create_agent_action_group(self):
        print("Creating an action group for the agent...")

        try:
            with open("./scenario_resources/api_schema.yaml") as file:
                self.bedrock_wrapper.create_agent_action_group(
                    name="current_date_and_time",
                    description="Gets the current date and time.",
                    agent_id=self.agent["agentId"],
                    agent_version=self.prepared_agent_details["agentVersion"],
                    function_arn=self.lambda_function["FunctionArn"],
                    api_schema=json.dumps(yaml.safe_load(file)),
                )
        except ClientError as e:
            logger.error(f"Couldn't create agent action group. Here's why: {e}")
            raise

    def _get_agent(self):
        return self.bedrock_wrapper.get_agent(self.agent["agentId"])

    def _get_agent_action_groups(self):
        return self.bedrock_wrapper.list_agent_action_groups(
            self.agent["agentId"], self.prepared_agent_details["agentVersion"]
        )

    def _get_agent_knowledge_bases(self):
        return self.bedrock_wrapper.list_agent_knowledge_bases(
            self.agent["agentId"], self.prepared_agent_details["agentVersion"]
        )

    def _create_agent_alias(self):
        print("Creating an agent alias...")
```

```
        agent_alias_name = "test_agent_alias"
        agent_alias = self.bedrock_wrapper.create_agent_alias(
            agent_alias_name, self.agent["agentId"]
        )

        self._wait_for_agent_status(self.agent["agentId"], "PREPARED")

        return agent_alias

    def _wait_for_agent_status(self, agent_id, status):
        while self.bedrock_wrapper.get_agent(agent_id)["agentStatus"] != status:
            wait(2)

    def _chat_with_agent(self, agent_alias):
        print("-" * 88)
        print("The agent is ready to chat.")
        print("Try asking for the date or time. Type 'exit' to quit.")

        # Create a unique session ID for the conversation
        session_id = uuid.uuid4().hex

        while True:
            prompt = q.ask("Prompt: ", q.non_empty)

            if prompt == "exit":
                break

            response = asyncio.run(self._invoke_agent(agent_alias, prompt,
session_id))

            print(f"Agent: {response}")

    async def _invoke_agent(self, agent_alias, prompt, session_id):
        response = self.bedrock_agent_runtime_client.invoke_agent(
            agentId=self.agent["agentId"],
            agentAliasId=agent_alias["agentAliasId"],
            sessionId=session_id,
            inputText=prompt,
        )

        completion = ""

        for event in response.get("completion"):
```

```
            chunk = event["chunk"]
            completion += chunk["bytes"].decode()

        return completion

    def _delete_resources(self):
        if self.agent:
            agent_id = self.agent["agentId"]

            if self.agent_alias:
                agent_alias_id = self.agent_alias["agentAliasId"]
                print("Deleting agent alias...")
                self.bedrock_wrapper.delete_agent_alias(agent_id, agent_alias_id)

            print("Deleting agent...")
            agent_status = self.bedrock_wrapper.delete_agent(agent_id)
["agentStatus"]
            while agent_status == "DELETING":
                wait(5)
                try:
                    agent_status = self.bedrock_wrapper.get_agent(
                        agent_id, log_error=False
                    )["agentStatus"]
                except ClientError as err:
                    if err.response["Error"]["Code"] ==
 "ResourceNotFoundException":
                        agent_status = "DELETED"

        if self.lambda_function:
            name = self.lambda_function["FunctionName"]
            print(f"Deleting function '{name}'...")
            self.lambda_client.delete_function(FunctionName=name)

        if self.agent_role:
            print(f"Deleting role '{self.agent_role.role_name}'...")
            self.agent_role.Policy(ROLE_POLICY_NAME).delete()
            self.agent_role.delete()

        if self.lambda_role:
            print(f"Deleting role '{self.lambda_role.role_name}'...")
            for policy in self.lambda_role.attached_policies.all():
                policy.detach_role(RoleName=self.lambda_role.role_name)
            self.lambda_role.delete()
```

```
    def _list_resources(self):
        print("-" * 40)
        print(f"Here is the list of created resources in '{REGION}'.")
        print("Make sure you delete them once you're done to avoid unnecessary
 costs.")
        if self.agent:
            print(f"Bedrock Agent:   {self.agent['agentName']}")
        if self.lambda_function:
            print(f"Lambda function: {self.lambda_function['FunctionName']}")
        if self.agent_role:
            print(f"IAM role:        {self.agent_role.role_name}")
        if self.lambda_role:
            print(f"IAM role:        {self.lambda_role.role_name}")

    @staticmethod
    def is_valid_agent_name(answer):
        valid_regex = r"^[a-zA-Z0-9_-]{1,100}$"
        return (
            answer
            if answer and len(answer) <= 100 and re.match(valid_regex, answer)
            else None,
            "I need a name for the agent, please. Valid characters are a-z, A-Z,
 0-9, _ (underscore) and - (hyphen).",
        )

    @staticmethod
    def _create_deployment_package(function_name):
        buffer = io.BytesIO()
        with zipfile.ZipFile(buffer, "w") as zipped:
            zipped.write(
                "./scenario_resources/lambda_function.py", f"{function_name}.py"
            )
        buffer.seek(0)
        return buffer.read()


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    postfix = "".join(
        random.choice(string.ascii_lowercase + "0123456789") for _ in range(8)
    )
    scenario = BedrockAgentScenarioWrapper(
        bedrock_agent_client=boto3.client(
```

```
            service_name="bedrock-agent", region_name=REGION
        ),
        runtime_client=boto3.client(
            service_name="bedrock-agent-runtime", region_name=REGION
        ),
        lambda_client=boto3.client(service_name="lambda", region_name=REGION),
        iam_resource=boto3.resource("iam"),
        postfix=postfix,
    )
    try:
        scenario.run_scenario()
    except Exception as e:
        logging.exception(f"Something went wrong with the demo. Here's what:
{e}")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAgent
  - CreateAgentActionGroup
  - CreateAgentAlias
  - DeleteAgent
  - DeleteAgentAlias
  - GetAgent
  - ListAgentActionGroups
  - ListAgentKnowledgeBases
  - ListAgents
  - PrepareAgent

Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

Python

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de código para agentes do Amazon Bedrock Runtime usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock Runtime com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Agents for Amazon Bedrock Runtime — Mais informações sobre Agents for Amazon Bedrock Runtime.
- Referência da API Agents for Amazon Bedrock Runtime — Detalhes sobre todas as ações disponíveis de Agents for Amazon Bedrock Runtime.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para agentes do Amazon Bedrock Runtime usando SDKs AWS
  - Invocar um agente do Amazon Bedrock usando um SDK da AWS
- Cenários para agentes do Amazon Bedrock Runtime usando SDKs AWS
  - Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Ações para agentes do Amazon Bedrock Runtime usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock Runtime com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para agentes do Amazon Bedrock Runtime usando SDKs AWS.

Exemplos

- Invocar um agente do Amazon Bedrock usando um SDK da AWS

Invocar um agente do Amazon Bedrock usando um SDK da AWS

O exemplo de código a seguir mostra como invocar um agente do Amazon Bedrock.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque um agente.

```
    def invoke_agent(self, agent_id, agent_alias_id, session_id, prompt):
        """
        Sends a prompt for the agent to process and respond to.

        :param agent_id: The unique identifier of the agent to use.
        :param agent_alias_id: The alias of the agent to use.
        :param session_id: The unique identifier of the session. Use the same
value across requests
                           to continue the same conversation.
        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            response = self.agents_runtime_client.invoke_agent(
                agentId=agent_id,
                agentAliasId=agent_alias_id,
                sessionId=session_id,
```

```
                inputText=prompt,
            )

            completion = ""

            for event in response.get("completion"):
                chunk = event["chunk"]
                completion = completion + chunk["bytes"].decode()

        except ClientError as e:
            logger.error(f"Couldn't invoke agent. {e}")
            raise

        return completion
```

- Para obter detalhes da API, consulte a InvokeAgentReferência da API AWSSDK for Python (Boto3).

Cenários para agentes do Amazon Bedrock Runtime usando SDKs AWS

Os exemplos de código a seguir mostram como usar Agents for Amazon Bedrock Runtime com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

Python

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de código para o AWS CloudFormation usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS CloudFormation com um kit de desenvolvimento de software (SDK) da AWS.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do AWS CloudFormation – Mais informações sobre o AWS CloudFormation.
- Referência da API do AWS CloudFormation – Detalhes sobre todas as ações disponíveis do AWS CloudFormation.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Exemplos para AWS CloudFormation entre serviços usando AWS SDKs
  - Criar uma API REST do API Gateway para monitorar dados da COVID-19

Exemplos para AWS CloudFormation entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS CloudFormation com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma API REST do API Gateway para monitorar dados da COVID-19

Criar uma API REST do API Gateway para monitorar dados da COVID-19

O exemplo de código a seguir mostra como criar uma API REST que simula um sistema para monitorar casos diários de COVID-19 nos Estados Unidos, usando dados fictícios.

Python

SDK para Python (Boto3)

Mostra como usar o AWS Chalice com o AWS SDK for Python (Boto3) para criar uma API REST sem servidor que usa o Amazon API Gateway, o AWS Lambda e o Amazon DynamoDB. O exemplo de código a seguir simula um sistema que monitora casos diários de COVID-19 nos Estados Unidos, usando dados fictícios. Aprenda como:

- Usar o AWS Chalice para definir rotas nas funções do Lambda que são chamadas para lidar com solicitações REST provenientes do API Gateway.
- Usar as funções do Lambda para recuperar e armazenar dados em uma tabela do DynamoDB para atender a solicitações REST.
- Definir recursos de função de segurança e estrutura de tabela em um modelo do AWS CloudFormation.
- Use AWS Chalice e CloudFormation para empacotar e implantar todos os recursos necessários.
- Use CloudFormation para limpar todos os recursos criados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- AWS CloudFormation
- DynamoDB
- Lambda

Exemplos de código para CloudFront usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudFront com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- CloudFront Guia do desenvolvedor — Mais informações sobre CloudFront.
- CloudFront Referência da API — Detalhes sobre todas as CloudFront ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para CloudFront usar AWS SDKs
  - Crie uma CloudFront distribuição usando um AWS SDK
  - Crie uma CloudFront função usando um AWS SDK
  - Crie um grupo-chave para CloudFront usar um AWS SDK
  - Excluir uma CloudFront distribuição usando o AWS SDK
  - Excluir recursos de CloudFront assinatura usando o AWS SDK
  - Obtenha a configuração de CloudFront distribuição usando um AWS SDK
  - Listar CloudFront distribuições usando um SDK AWS
  - Atualizar uma CloudFront distribuição usando um AWS SDK
  - Faça upload de uma chave pública para CloudFront usar um AWS SDK
- Cenários para CloudFront usar AWS SDKs
  - Crie URLs e cookies assinados usando um SDK da AWS

Ações para CloudFront usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudFront com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para CloudFront usar AWS SDKs.

Exemplos

- Crie uma CloudFront distribuição usando um AWS SDK
- Crie uma CloudFront função usando um AWS SDK
- Crie um grupo-chave para CloudFront usar um AWS SDK
- Excluir uma CloudFront distribuição usando o AWS SDK
- Excluir recursos de CloudFront assinatura usando o AWS SDK
- Obtenha a configuração de CloudFront distribuição usando um AWS SDK
- Listar CloudFront distribuições usando um SDK AWS
- Atualizar uma CloudFront distribuição usando um AWS SDK
- Faça upload de uma chave pública para CloudFront usar um AWS SDK

Crie uma CloudFront distribuição usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma CloudFront distribuição.

CLI

AWS CLI

Para criar uma CloudFront distribuição

O exemplo a seguir cria uma distribuição para um bucket do S3 chamado `awsexamplebucket` e também especifica `index.html` como o objeto raiz padrão, usando argumentos de linha de comando:

```
aws cloudfront create-distribution \
    --origin-domain-name awsexamplebucket.s3.amazonaws.com \
    --default-root-object index.html
```

Em vez de usar argumentos de linha de comando, forneça a configuração de distribuição em um arquivo JSON, conforme mostrado no seguinte exemplo:

```
aws cloudfront create-distribution \
```

```
    --distribution-config file://dist-config.json
```

O arquivo `dist-config.json` é um documento JSON na pasta atual que contém o seguinte:

```
{
    "CallerReference": "cli-example",
    "Aliases": {
        "Quantity": 0
    },
    "DefaultRootObject": "index.html",
    "Origins": {
        "Quantity": 1,
        "Items": [
            {
                "Id": "awsexamplebucket.s3.amazonaws.com-cli-example",
                "DomainName": "awsexamplebucket.s3.amazonaws.com",
                "OriginPath": "",
                "CustomHeaders": {
                    "Quantity": 0
                },
                "S3OriginConfig": {
                    "OriginAccessIdentity": ""
                }
            }
        ]
    },
    "OriginGroups": {
        "Quantity": 0
    },
    "DefaultCacheBehavior": {
        "TargetOriginId": "awsexamplebucket.s3.amazonaws.com-cli-example",
        "ForwardedValues": {
            "QueryString": false,
            "Cookies": {
                "Forward": "none"
            },
            "Headers": {
                "Quantity": 0
            },
            "QueryStringCacheKeys": {
                "Quantity": 0
            }
```

```
        },
        "TrustedSigners": {
            "Enabled": false,
            "Quantity": 0
        },
        "ViewerProtocolPolicy": "allow-all",
        "MinTTL": 0,
        "AllowedMethods": {
            "Quantity": 2,
            "Items": [
                "HEAD",
                "GET"
            ],
            "CachedMethods": {
                "Quantity": 2,
                "Items": [
                    "HEAD",
                    "GET"
                ]
            }
        },
        "SmoothStreaming": false,
        "DefaultTTL": 86400,
        "MaxTTL": 31536000,
        "Compress": false,
        "LambdaFunctionAssociations": {
            "Quantity": 0
        },
        "FieldLevelEncryptionId": ""
    },
    "CacheBehaviors": {
        "Quantity": 0
    },
    "CustomErrorResponses": {
        "Quantity": 0
    },
    "Comment": "",
    "Logging": {
        "Enabled": false,
        "IncludeCookies": false,
        "Bucket": "",
        "Prefix": ""
    },
    "PriceClass": "PriceClass_All",
```

```
    "Enabled": true,
    "ViewerCertificate": {
        "CloudFrontDefaultCertificate": true,
        "MinimumProtocolVersion": "TLSv1",
        "CertificateSource": "cloudfront"
    },
    "Restrictions": {
        "GeoRestriction": {
            "RestrictionType": "none",
            "Quantity": 0
        }
    },
    "WebACLId": "",
    "HttpVersion": "http2",
    "IsIPV6Enabled": true
}
```

Se você fornecer as informações de distribuição com um argumento de linha de comando ou um arquivo JSON, a saída será a mesma:

```
{
    "Location": "https://cloudfront.amazonaws.com/2019-03-26/distribution/
EMLARXS9EXAMPLE",
    "ETag": "E9LHASXEXAMPLE",
    "Distribution": {
        "Id": "EMLARXS9EXAMPLE",
        "ARN": "arn:aws:cloudfront::123456789012:distribution/EMLARXS9EXAMPLE",
        "Status": "InProgress",
        "LastModifiedTime": "2019-11-22T00:55:15.705Z",
        "InProgressInvalidationBatches": 0,
        "DomainName": "d111111abcdef8.cloudfront.net",
        "ActiveTrustedSigners": {
            "Enabled": false,
            "Quantity": 0
        },
        "DistributionConfig": {
            "CallerReference": "cli-example",
            "Aliases": {
                "Quantity": 0
            },
            "DefaultRootObject": "index.html",
            "Origins": {
                "Quantity": 1,
```

```
                "Items": [
                    {
                        "Id": "awsexamplebucket.s3.amazonaws.com-cli-example",
                        "DomainName": "awsexamplebucket.s3.amazonaws.com",
                        "OriginPath": "",
                        "CustomHeaders": {
                            "Quantity": 0
                        },
                        "S3OriginConfig": {
                            "OriginAccessIdentity": ""
                        }
                    }
                ]
            },
            "OriginGroups": {
                "Quantity": 0
            },
            "DefaultCacheBehavior": {
                "TargetOriginId": "awsexamplebucket.s3.amazonaws.com-cli-
example",
                "ForwardedValues": {
                    "QueryString": false,
                    "Cookies": {
                        "Forward": "none"
                    },
                    "Headers": {
                        "Quantity": 0
                    },
                    "QueryStringCacheKeys": {
                        "Quantity": 0
                    }
                },
                "TrustedSigners": {
                    "Enabled": false,
                    "Quantity": 0
                },
                "ViewerProtocolPolicy": "allow-all",
                "MinTTL": 0,
                "AllowedMethods": {
                    "Quantity": 2,
                    "Items": [
                        "HEAD",
                        "GET"
                    ],
```

```
                "CachedMethods": {
                    "Quantity": 2,
                    "Items": [
                        "HEAD",
                        "GET"
                    ]
                }
            },
            "SmoothStreaming": false,
            "DefaultTTL": 86400,
            "MaxTTL": 31536000,
            "Compress": false,
            "LambdaFunctionAssociations": {
                "Quantity": 0
            },
            "FieldLevelEncryptionId": ""
        },
        "CacheBehaviors": {
            "Quantity": 0
        },
        "CustomErrorResponses": {
            "Quantity": 0
        },
        "Comment": "",
        "Logging": {
            "Enabled": false,
            "IncludeCookies": false,
            "Bucket": "",
            "Prefix": ""
        },
        "PriceClass": "PriceClass_All",
        "Enabled": true,
        "ViewerCertificate": {
            "CloudFrontDefaultCertificate": true,
            "MinimumProtocolVersion": "TLSv1",
            "CertificateSource": "cloudfront"
        },
        "Restrictions": {
            "GeoRestriction": {
                "RestrictionType": "none",
                "Quantity": 0
            }
        },
        "WebACLId": "",
```

```
            "HttpVersion": "http2",
            "IsIPV6Enabled": true
        }
    }
}
```

- Para obter detalhes da API, consulte CreateDistributionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo a seguir usa um bucket do Amazon Simple Storage Service (Amazon S3) como origem de conteúdo.

Depois de criar a distribuição, o código cria um CloudFrontWaiterpara esperar até que a distribuição seja implantada antes de retornar a distribuição

.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.internal.waiters.ResponseOrException;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import
 software.amazon.awssdk.services.cloudfront.model.CreateDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.Distribution;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.ItemSelection;
import software.amazon.awssdk.services.cloudfront.model.Method;
import software.amazon.awssdk.services.cloudfront.model.ViewerProtocolPolicy;
import software.amazon.awssdk.services.cloudfront.waiters.CloudFrontWaiter;
import software.amazon.awssdk.services.s3.S3Client;
```

```
import java.time.Instant;

public class CreateDistribution {

        private static final Logger logger =
 LoggerFactory.getLogger(CreateDistribution.class);

        public static Distribution createDistribution(CloudFrontClient
 cloudFrontClient, S3Client s3Client,
                        final String bucketName, final String keyGroupId, final
 String originAccessControlId) {

                final String region = s3Client.headBucket(b ->
 b.bucket(bucketName)).sdkHttpResponse().headers()
                                .get("x-amz-bucket-region").get(0);
                final String originDomain = bucketName + ".s3." + region +
 ".amazonaws.com";
                String originId = originDomain; // Use the originDomain value for
 the originId.

                // The service API requires some deprecated methods, such as
                // DefaultCacheBehavior.Builder#minTTL and #forwardedValue.
                CreateDistributionResponse createDistResponse =
 cloudFrontClient.createDistribution(builder -> builder
                                .distributionConfig(b1 -> b1
                                                .origins(b2 -> b2
                                                                .quantity(1)
                                                                .items(b3 -> b3

 .domainName(originDomain)

 .id(originId)

 .s3OriginConfig(builder4 -> builder4

               .originAccessIdentity(

                               ""))

 .originAccessControlId(

               originAccessControlId)))
                                                .defaultCacheBehavior(b2 -> b2
```

```
.viewerProtocolPolicy(ViewerProtocolPolicy.ALLOW_ALL)

.targetOriginId(originId)
                                                                .minTTL(200L)

.forwardedValues(b5 -> b5

.cookies(cp -> cp

              .forward(ItemSelection.NONE))

.queryString(true))

.trustedKeyGroups(b3 -> b3

.quantity(1)

.items(keyGroupId)

.enabled(true))

.allowedMethods(b4 -> b4

.quantity(2)

.items(Method.HEAD, Method.GET)

.cachedMethods(b5 -> b5

              .quantity(2)

              .items(Method.HEAD,

                             Method.GET))))
                                                .cacheBehaviors(b -> b
                                                                .quantity(1)
                                                                .items(b2 -> b2

.pathPattern("/index.html")

.viewerProtocolPolicy(

              ViewerProtocolPolicy.ALLOW_ALL)
```

```
.targetOriginId(originId)

.trustedKeyGroups(b3 -> b3

              .quantity(1)

              .items(keyGroupId)

              .enabled(true))

.minTTL(200L)

.forwardedValues(b4 -> b4

              .cookies(cp -> cp

                              .forward(ItemSelection.NONE))

              .queryString(true))

.allowedMethods(b5 -> b5.quantity(2)

              .items(Method.HEAD,

                             Method.GET)

              .cachedMethods(b6 -> b6

                              .quantity(2)

                              .items(Method.HEAD,

                                             Method.GET)))))
                                              .enabled(true)
                                              .comment("Distribution built with
java")

.callerReference(Instant.now().toString())));

               final Distribution distribution =
createDistResponse.distribution();
               logger.info("Distribution created. DomainName: [{}]  Id: [{}]",
distribution.domainName(),
```

```
                                distribution.id());
                logger.info("Waiting for distribution to be deployed ...");
                try (CloudFrontWaiter cfWaiter =
 CloudFrontWaiter.builder().client(cloudFrontClient).build()) {
                        ResponseOrException<GetDistributionResponse>
 responseOrException = cfWaiter
                                        .waitUntilDistributionDeployed(builder ->
 builder.id(distribution.id()))
                                        .matched();
                        responseOrException.response()
                                        .orElseThrow(() -> new
 RuntimeException("Distribution not created"));
                        logger.info("Distribution deployed. DomainName: [{}]  Id:
 [{}]", distribution.domainName(),
                                        distribution.id());
                }
                return distribution;
        }
}
```

- Para obter detalhes da API, consulte CreateDistributiona Referência AWS SDK for Java 2.x da API.

Crie uma CloudFront função usando um AWS SDK

O exemplo de código a seguir mostra como criar uma CloudFront função da Amazon.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
```

```
import software.amazon.awssdk.services.cloudfront.model.CloudFrontException;
import software.amazon.awssdk.services.cloudfront.model.CreateFunctionRequest;
import software.amazon.awssdk.services.cloudfront.model.CreateFunctionResponse;
import software.amazon.awssdk.services.cloudfront.model.FunctionConfig;
import software.amazon.awssdk.services.cloudfront.model.FunctionRuntime;

import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateFunction {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName> <filePath>

                Where:
                    functionName - The name of the function to create.\s
                    filePath - The path to a file that contains the application
 logic for the function.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
        String functionName = args[0];
        String filePath = args[1];
        CloudFrontClient cloudFrontClient = CloudFrontClient.builder()
                .region(Region.AWS_GLOBAL)
                .build();
```

```
        String funArn = createNewFunction(cloudFrontClient, functionName,
 filePath);
        System.out.println("The function ARN is " + funArn);
        cloudFrontClient.close();
    }

    public static String createNewFunction(CloudFrontClient cloudFrontClient,
 String functionName, String filePath) {
        try {
            InputStream fileIs = new FileInputStream(filePath);
            SdkBytes functionCode = SdkBytes.fromInputStream(fileIs);

            FunctionConfig config = FunctionConfig.builder()
                    .comment("Created by using the CloudFront Java API")
                    .runtime(FunctionRuntime.CLOUDFRONT_JS_1_0)
                    .build();

            CreateFunctionRequest functionRequest =
 CreateFunctionRequest.builder()
                    .name(functionName)
                    .functionCode(functionCode)
                    .functionConfig(config)
                    .build();

            CreateFunctionResponse response =
 cloudFrontClient.createFunction(functionRequest);
            return response.functionSummary().functionMetadata().functionARN();

        } catch (CloudFrontException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Java 2.x da API.

Crie um grupo-chave para CloudFront usar um AWS SDK

O exemplo de código a seguir mostra como criar um grupo de chaves que você pode usar com URLs e cookies assinados.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Um grupo de chaves exige pelo menos uma chave pública usada para verificar URLs ou cookies assinados.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;

import java.util.UUID;

public class CreateKeyGroup {
    private static final Logger logger =
 LoggerFactory.getLogger(CreateKeyGroup.class);

    public static String createKeyGroup(CloudFrontClient cloudFrontClient, String
 publicKeyId) {
        String keyGroupId = cloudFrontClient.createKeyGroup(b ->
 b.keyGroupConfig(c -> c
                .items(publicKeyId)
                .name("JavaKeyGroup" + UUID.randomUUID())))
                .keyGroup().id();
        logger.info("KeyGroup created with ID: [{}]", keyGroupId);
        return keyGroupId;
    }
}
```

- Para obter detalhes da API, consulte CreateKeyGroupa Referência AWS SDK for Java 2.x da API.

Excluir uma CloudFront distribuição usando o AWS SDK

Os exemplos de código a seguir mostram como excluir uma CloudFront distribuição.

CLI

AWS CLI

Para excluir uma CloudFront distribuição

O exemplo a seguir exclui a CloudFront distribuição com o `IDEDFDVBD6EXAMPLE`. Você deve desabilitar uma distribuição antes de exclui-la. Use o comando update-distribution para desabilitar uma distribuição. Para obter mais informações, consulte exemplos do comando update-distribution.

Uma distribuição pode ser excluída depois de ser desabilitada. Para excluir uma distribuição, use a opção `--if-match` para fornecer o `ETag` da distribuição. Para obter o`ETag`, use o comando get-distribution ouget-distribution-config .

```
aws cloudfront delete-distribution \
    --id EDFDVBD6EXAMPLE \
    --if-match E2QWRUHEXAMPLE
```

Quando bem-sucedido, este comando não tem saída.

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - DeleteDistribution
  - UpdateDistribution

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo de código a seguir atualiza uma distribuição para desabilitada, usa um agente de espera que aguarda a implantação da alteração e, em seguida, exclui a distribuição.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.internal.waiters.ResponseOrException;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import
 software.amazon.awssdk.services.cloudfront.model.DeleteDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.DistributionConfig;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
import software.amazon.awssdk.services.cloudfront.waiters.CloudFrontWaiter;

public class DeleteDistribution {
        private static final Logger logger =
 LoggerFactory.getLogger(DeleteDistribution.class);

        public static void deleteDistribution(final CloudFrontClient
 cloudFrontClient, final String distributionId) {
                // First, disable the distribution by updating it.
                GetDistributionResponse response =
 cloudFrontClient.getDistribution(b -> b
                                .id(distributionId));
                String etag = response.eTag();
                DistributionConfig distConfig =
 response.distribution().distributionConfig();

                cloudFrontClient.updateDistribution(builder -> builder
                                .id(distributionId)
                                .distributionConfig(builder1 -> builder1

 .cacheBehaviors(distConfig.cacheBehaviors())
```

```
.defaultCacheBehavior(distConfig.defaultCacheBehavior())
                                                .enabled(false)
                                                .origins(distConfig.origins())
                                                .comment(distConfig.comment())

.callerReference(distConfig.callerReference())

.defaultCacheBehavior(distConfig.defaultCacheBehavior())

.priceClass(distConfig.priceClass())
                                                .aliases(distConfig.aliases())
                                                .logging(distConfig.logging())

.defaultRootObject(distConfig.defaultRootObject())

.customErrorResponses(distConfig.customErrorResponses())

.httpVersion(distConfig.httpVersion())

.isIPV6Enabled(distConfig.isIPV6Enabled())

.restrictions(distConfig.restrictions())

.viewerCertificate(distConfig.viewerCertificate())
                                                .webACLId(distConfig.webACLId())

.originGroups(distConfig.originGroups()))
                               .ifMatch(etag));

               logger.info("Distribution [{}] is DISABLED, waiting for
deployment before deleting ...",
                               distributionId);
               GetDistributionResponse distributionResponse;
               try (CloudFrontWaiter cfWaiter =
CloudFrontWaiter.builder().client(cloudFrontClient).build()) {
                       ResponseOrException<GetDistributionResponse>
responseOrException = cfWaiter
                                       .waitUntilDistributionDeployed(builder ->
builder.id(distributionId)).matched();
                       distributionResponse = responseOrException.response()
                                       .orElseThrow(() -> new
RuntimeException("Could not disable distribution"));
               }
```

```
                DeleteDistributionResponse deleteDistributionResponse =
 cloudFrontClient
                                .deleteDistribution(builder -> builder
                                                .id(distributionId)

 .ifMatch(distributionResponse.eTag()));
                if (deleteDistributionResponse.sdkHttpResponse().isSuccessful())
 {
                        logger.info("Distribution [{}] DELETED", distributionId);
                }
        }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteDistribution
  - UpdateDistribution

Excluir recursos de CloudFront assinatura usando o AWS SDK

O exemplo de código a seguir mostra como excluir recursos que são usados para obter acesso a conteúdo restrito em um bucket do Amazon Simple Storage Service (Amazon S3).

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.DeleteKeyGroupResponse;
```

```
import
 software.amazon.awssdk.services.cloudfront.model.DeleteOriginAccessControlResponse;
import software.amazon.awssdk.services.cloudfront.model.DeletePublicKeyResponse;
import software.amazon.awssdk.services.cloudfront.model.GetKeyGroupResponse;
import
 software.amazon.awssdk.services.cloudfront.model.GetOriginAccessControlResponse;
import software.amazon.awssdk.services.cloudfront.model.GetPublicKeyResponse;

public class DeleteSigningResources {
    private static final Logger logger =
 LoggerFactory.getLogger(DeleteSigningResources.class);

    public static void deleteOriginAccessControl(final CloudFrontClient
 cloudFrontClient,
            final String originAccessControlId) {
        GetOriginAccessControlResponse getResponse = cloudFrontClient
                .getOriginAccessControl(b -> b.id(originAccessControlId));
        DeleteOriginAccessControlResponse deleteResponse =
 cloudFrontClient.deleteOriginAccessControl(builder -> builder
                .id(originAccessControlId)
                .ifMatch(getResponse.eTag()));
        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Origin Access Control [{}]",
 originAccessControlId);
        }
    }

    public static void deleteKeyGroup(final CloudFrontClient cloudFrontClient,
 final String keyGroupId) {

        GetKeyGroupResponse getResponse = cloudFrontClient.getKeyGroup(b ->
 b.id(keyGroupId));
        DeleteKeyGroupResponse deleteResponse =
 cloudFrontClient.deleteKeyGroup(builder -> builder
                .id(keyGroupId)
                .ifMatch(getResponse.eTag()));
        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Key Group [{}]", keyGroupId);
        }
    }

    public static void deletePublicKey(final CloudFrontClient cloudFrontClient,
 final String publicKeyId) {
```

```
        GetPublicKeyResponse getResponse = cloudFrontClient.getPublicKey(b ->
 b.id(publicKeyId));

        DeletePublicKeyResponse deleteResponse =
 cloudFrontClient.deletePublicKey(builder -> builder
                .id(publicKeyId)
                .ifMatch(getResponse.eTag()));

        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Public Key [{}]", publicKeyId);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteKeyGroup
  - DeleteOriginAccessControl
  - DeletePublicKey

Obtenha a configuração de CloudFront distribuição usando um AWS SDK

Os exemplos de código a seguir mostram como obter a configuração de CloudFront distribuição da Amazon.

CLI

AWS CLI

Para obter uma configuração CloudFront de distribuição

O exemplo a seguir obtém metadados sobre a CloudFront distribuição com o `IDEDFDVBD6EXAMPLE`, incluindo seu`ETag`. O ID de distribuição é retornado nos comandos create-distribution e list-distributions.

```
aws cloudfront get-distribution-config --id EDFDVBD6EXAMPLE
```

Saída:

```
{
    "ETag": "E2QWRUHEXAMPLE",
    "DistributionConfig": {
        "CallerReference": "cli-example",
        "Aliases": {
            "Quantity": 0
        },
        "DefaultRootObject": "index.html",
        "Origins": {
            "Quantity": 1,
            "Items": [
                {
                    "Id": "awsexamplebucket.s3.amazonaws.com-cli-example",
                    "DomainName": "awsexamplebucket.s3.amazonaws.com",
                    "OriginPath": "",
                    "CustomHeaders": {
                        "Quantity": 0
                    },
                    "S3OriginConfig": {
                        "OriginAccessIdentity": ""
                    }
                }
            ]
        },
        "OriginGroups": {
            "Quantity": 0
        },
        "DefaultCacheBehavior": {
            "TargetOriginId": "awsexamplebucket.s3.amazonaws.com-cli-example",
            "ForwardedValues": {
                "QueryString": false,
                "Cookies": {
                    "Forward": "none"
                },
                "Headers": {
                    "Quantity": 0
                },
                "QueryStringCacheKeys": {
                    "Quantity": 0
                }
            },
            "TrustedSigners": {
                "Enabled": false,
```

```
                "Quantity": 0
            },
            "ViewerProtocolPolicy": "allow-all",
            "MinTTL": 0,
            "AllowedMethods": {
                "Quantity": 2,
                "Items": [
                    "HEAD",
                    "GET"
                ],
                "CachedMethods": {
                    "Quantity": 2,
                    "Items": [
                        "HEAD",
                        "GET"
                    ]
                }
            },
            "SmoothStreaming": false,
            "DefaultTTL": 86400,
            "MaxTTL": 31536000,
            "Compress": false,
            "LambdaFunctionAssociations": {
                "Quantity": 0
            },
            "FieldLevelEncryptionId": ""
        },
        "CacheBehaviors": {
            "Quantity": 0
        },
        "CustomErrorResponses": {
            "Quantity": 0
        },
        "Comment": "",
        "Logging": {
            "Enabled": false,
            "IncludeCookies": false,
            "Bucket": "",
            "Prefix": ""
        },
        "PriceClass": "PriceClass_All",
        "Enabled": true,
        "ViewerCertificate": {
            "CloudFrontDefaultCertificate": true,
```

```
            "MinimumProtocolVersion": "TLSv1",
            "CertificateSource": "cloudfront"
        },
        "Restrictions": {
            "GeoRestriction": {
                "RestrictionType": "none",
                "Quantity": 0
            }
        },
        "WebACLId": "",
        "HttpVersion": "http2",
        "IsIPV6Enabled": true
    }
}
```

- Para obter detalhes da API, consulte GetDistributionConfigem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""

    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client


    def update_distribution(self):
        distribution_id = input(
            "This script updates the comment for a CloudFront distribution.\n"
```

```
            "Enter a CloudFront distribution ID: "
        )

        distribution_config_response =
self.cloudfront_client.get_distribution_config(
            Id=distribution_id
        )
        distribution_config = distribution_config_response["DistributionConfig"]
        distribution_etag = distribution_config_response["ETag"]

        distribution_config["Comment"] = input(
            f"\nThe current comment for distribution {distribution_id} is "
            f"'{distribution_config['Comment']}'.\n"
            f"Enter a new comment: "
        )
        self.cloudfront_client.update_distribution(
            DistributionConfig=distribution_config,
            Id=distribution_id,
            IfMatch=distribution_etag,
        )
        print("Done!")
```

- Para obter detalhes da API, consulte a GetDistributionConfigReferência da API AWSSDK for Python (Boto3).

Listar CloudFront distribuições usando um SDK AWS

Os exemplos de código a seguir mostram como listar as CloudFront distribuições da Amazon.

CLI

AWS CLI

Para listar CloudFront distribuições

O exemplo a seguir obtém uma lista das CloudFront distribuições em sua AWS conta:

```
aws cloudfront list-distributions
```

Saída:

```
{
    "DistributionList": {
        "Items": [
            {
                "Id": "EMLARXS9EXAMPLE",
                "ARN": "arn:aws:cloudfront::123456789012:distribution/
EMLARXS9EXAMPLE",
                "Status": "InProgress",
                "LastModifiedTime": "2019-11-22T00:55:15.705Z",
                "InProgressInvalidationBatches": 0,
                "DomainName": "d111111abcdef8.cloudfront.net",
                "ActiveTrustedSigners": {
                    "Enabled": false,
                    "Quantity": 0
                },
                "DistributionConfig": {
                    "CallerReference": "cli-example",
                    "Aliases": {
                        "Quantity": 0
                    },
                    "DefaultRootObject": "index.html",
                    "Origins": {
                        "Quantity": 1,
                        "Items": [
                            {
                                "Id": "awsexamplebucket.s3.amazonaws.com-cli-
example",
                                "DomainName":
 "awsexamplebucket.s3.amazonaws.com",
                                "OriginPath": "",
                                "CustomHeaders": {
                                    "Quantity": 0
                                },
                                "S3OriginConfig": {
                                    "OriginAccessIdentity": ""
                                }
                            }
                        ]
                    },
                    "OriginGroups": {
                        "Quantity": 0
                    },
```

```
                    "DefaultCacheBehavior": {
                        "TargetOriginId": "awsexamplebucket.s3.amazonaws.com-cli-
example",
                        "ForwardedValues": {
                            "QueryString": false,
                            "Cookies": {
                                "Forward": "none"
                            },
                            "Headers": {
                                "Quantity": 0
                            },
                            "QueryStringCacheKeys": {
                                "Quantity": 0
                            }
                        },
                        "TrustedSigners": {
                            "Enabled": false,
                            "Quantity": 0
                        },
                        "ViewerProtocolPolicy": "allow-all",
                        "MinTTL": 0,
                        "AllowedMethods": {
                            "Quantity": 2,
                            "Items": [
                                "HEAD",
                                "GET"
                            ],
                            "CachedMethods": {
                                "Quantity": 2,
                                "Items": [
                                    "HEAD",
                                    "GET"
                                ]
                            }
                        },
                        "SmoothStreaming": false,
                        "DefaultTTL": 86400,
                        "MaxTTL": 31536000,
                        "Compress": false,
                        "LambdaFunctionAssociations": {
                            "Quantity": 0
                        },
                        "FieldLevelEncryptionId": ""
                    },
```

```
                    "CacheBehaviors": {
                        "Quantity": 0
                    },
                    "CustomErrorResponses": {
                        "Quantity": 0
                    },
                    "Comment": "",
                    "Logging": {
                        "Enabled": false,
                        "IncludeCookies": false,
                        "Bucket": "",
                        "Prefix": ""
                    },
                    "PriceClass": "PriceClass_All",
                    "Enabled": true,
                    "ViewerCertificate": {
                        "CloudFrontDefaultCertificate": true,
                        "MinimumProtocolVersion": "TLSv1",
                        "CertificateSource": "cloudfront"
                    },
                    "Restrictions": {
                        "GeoRestriction": {
                            "RestrictionType": "none",
                            "Quantity": 0
                        }
                    },
                    "WebACLId": "",
                    "HttpVersion": "http2",
                    "IsIPV6Enabled": true
                }
            },
            {
                "Id": "EDFDVBD6EXAMPLE",
                "ARN": "arn:aws:cloudfront::123456789012:distribution/
EDFDVBD6EXAMPLE",
                "Status": "InProgress",
                "LastModifiedTime": "2019-12-04T23:35:41.433Z",
                "InProgressInvalidationBatches": 0,
                "DomainName": "d930174dauwrn8.cloudfront.net",
                "ActiveTrustedSigners": {
                    "Enabled": false,
                    "Quantity": 0
                },
                "DistributionConfig": {
```

```
                    "CallerReference": "cli-example",
                    "Aliases": {
                        "Quantity": 0
                    },
                    "DefaultRootObject": "index.html",
                    "Origins": {
                        "Quantity": 1,
                        "Items": [
                            {
                                "Id": "awsexamplebucket1.s3.amazonaws.com-cli-
example",
                                "DomainName":
 "awsexamplebucket1.s3.amazonaws.com",
                                "OriginPath": "",
                                "CustomHeaders": {
                                    "Quantity": 0
                                },
                                "S3OriginConfig": {
                                    "OriginAccessIdentity": ""
                                }
                            }
                        ]
                    },
                    "OriginGroups": {
                        "Quantity": 0
                    },
                    "DefaultCacheBehavior": {
                        "TargetOriginId": "awsexamplebucket1.s3.amazonaws.com-
cli-example",
                        "ForwardedValues": {
                            "QueryString": false,
                            "Cookies": {
                                "Forward": "none"
                            },
                            "Headers": {
                                "Quantity": 0
                            },
                            "QueryStringCacheKeys": {
                                "Quantity": 0
                            }
                        },
                        "TrustedSigners": {
                            "Enabled": false,
                            "Quantity": 0
```

```
                    },
                    "ViewerProtocolPolicy": "allow-all",
                    "MinTTL": 0,
                    "AllowedMethods": {
                        "Quantity": 2,
                        "Items": [
                            "HEAD",
                            "GET"
                        ],
                        "CachedMethods": {
                            "Quantity": 2,
                            "Items": [
                                "HEAD",
                                "GET"
                            ]
                        }
                    },
                    "SmoothStreaming": false,
                    "DefaultTTL": 86400,
                    "MaxTTL": 31536000,
                    "Compress": false,
                    "LambdaFunctionAssociations": {
                        "Quantity": 0
                    },
                    "FieldLevelEncryptionId": ""
                },
                "CacheBehaviors": {
                    "Quantity": 0
                },
                "CustomErrorResponses": {
                    "Quantity": 0
                },
                "Comment": "",
                "Logging": {
                    "Enabled": false,
                    "IncludeCookies": false,
                    "Bucket": "",
                    "Prefix": ""
                },
                "PriceClass": "PriceClass_All",
                "Enabled": true,
                "ViewerCertificate": {
                    "CloudFrontDefaultCertificate": true,
                    "MinimumProtocolVersion": "TLSv1",
```

```
                        "CertificateSource": "cloudfront"
                    },
                    "Restrictions": {
                        "GeoRestriction": {
                            "RestrictionType": "none",
                            "Quantity": 0
                        }
                    },
                    "WebACLId": "",
                    "HttpVersion": "http2",
                    "IsIPV6Enabled": true
                }
            },
            {
                "Id": "E1X5IZQEXAMPLE",
                "ARN": "arn:aws:cloudfront::123456789012:distribution/
E1X5IZQEXAMPLE",
                "Status": "Deployed",
                "LastModifiedTime": "2019-11-06T21:31:48.864Z",
                "DomainName": "d2e04y12345678.cloudfront.net",
                "Aliases": {
                    "Quantity": 0
                },
                "Origins": {
                    "Quantity": 1,
                    "Items": [
                        {
                            "Id": "awsexamplebucket2",
                            "DomainName": "awsexamplebucket2.s3.us-
west-2.amazonaws.com",
                            "OriginPath": "",
                            "CustomHeaders": {
                                "Quantity": 0
                            },
                            "S3OriginConfig": {
                                "OriginAccessIdentity": ""
                            }
                        }
                    ]
                },
                "OriginGroups": {
                    "Quantity": 0
                },
                "DefaultCacheBehavior": {
```

```
                    "TargetOriginId": "awsexamplebucket2",
                    "ForwardedValues": {
                        "QueryString": false,
                        "Cookies": {
                            "Forward": "none"
                        },
                        "Headers": {
                            "Quantity": 0
                        },
                        "QueryStringCacheKeys": {
                            "Quantity": 0
                        }
                    },
                    "TrustedSigners": {
                        "Enabled": false,
                        "Quantity": 0
                    },
                    "ViewerProtocolPolicy": "allow-all",
                    "MinTTL": 0,
                    "AllowedMethods": {
                        "Quantity": 2,
                        "Items": [
                            "HEAD",
                            "GET"
                        ],
                        "CachedMethods": {
                            "Quantity": 2,
                            "Items": [
                                "HEAD",
                                "GET"
                            ]
                        }
                    },
                    "SmoothStreaming": false,
                    "DefaultTTL": 86400,
                    "MaxTTL": 31536000,
                    "Compress": false,
                    "LambdaFunctionAssociations": {
                        "Quantity": 0
                    },
                    "FieldLevelEncryptionId": ""
                },
                "CacheBehaviors": {
                    "Quantity": 0
```

```
                },
                "CustomErrorResponses": {
                    "Quantity": 0
                },
                "Comment": "",
                "PriceClass": "PriceClass_All",
                "Enabled": true,
                "ViewerCertificate": {
                    "CloudFrontDefaultCertificate": true,
                    "MinimumProtocolVersion": "TLSv1",
                    "CertificateSource": "cloudfront"
                },
                "Restrictions": {
                    "GeoRestriction": {
                        "RestrictionType": "none",
                        "Quantity": 0
                    }
                },
                "WebACLId": "",
                "HttpVersion": "HTTP1_1",
                "IsIPV6Enabled": true
            }
        ]
    }
}
```

- Para obter detalhes da API, consulte ListDistributionsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""
```

```
    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client


    def list_distributions(self):
        print("CloudFront distributions:\n")
        distributions = self.cloudfront_client.list_distributions()
        if distributions["DistributionList"]["Quantity"] > 0:
            for distribution in distributions["DistributionList"]["Items"]:
                print(f"Domain: {distribution['DomainName']}")
                print(f"Distribution Id: {distribution['Id']}")
                print(
                    f"Certificate Source: "
                    f"{distribution['ViewerCertificate']['CertificateSource']}"
                )
                if distribution["ViewerCertificate"]["CertificateSource"] ==
 "acm":
                    print(
                        f"Certificate: {distribution['ViewerCertificate']
['Certificate']}"
                    )
                print("")
        else:
            print("No CloudFront distributions detected.")
```

- Para obter detalhes da API, consulte a ListDistributionsReferência da API AWSSDK for Python (Boto3).

Atualizar uma CloudFront distribuição usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar uma CloudFront distribuição da Amazon.

CLI

AWS CLI

Para atualizar o objeto raiz padrão de uma CloudFront distribuição

O exemplo a seguir atualiza o objeto raiz padrão `index.html` para a CloudFront distribuição com o IDEDFDVBD6EXAMPLE:

```
aws cloudfront update-distribution --id EDFDVBD6EXAMPLE \
    --default-root-object index.html
```

Saída:

```
{
    "ETag": "E2QWRUHEXAMPLE",
    "Distribution": {
        "Id": "EDFDVBD6EXAMPLE",
        "ARN": "arn:aws:cloudfront::123456789012:distribution/EDFDVBD6EXAMPLE",
        "Status": "InProgress",
        "LastModifiedTime": "2019-12-06T18:55:39.870Z",
        "InProgressInvalidationBatches": 0,
        "DomainName": "d111111abcdef8.cloudfront.net",
        "ActiveTrustedSigners": {
            "Enabled": false,
            "Quantity": 0
        },
        "DistributionConfig": {
            "CallerReference": "6b10378d-49be-4c4b-a642-419ccaf8f3b5",
            "Aliases": {
                "Quantity": 0
            },
            "DefaultRootObject": "index.html",
            "Origins": {
                "Quantity": 1,
                "Items": [
                    {
                        "Id": "example-website",
                        "DomainName": "www.example.com",
                        "OriginPath": "",
                        "CustomHeaders": {
                            "Quantity": 0
                        },
                        "CustomOriginConfig": {
                            "HTTPPort": 80,
                            "HTTPSPort": 443,
                            "OriginProtocolPolicy": "match-viewer",
                            "OriginSslProtocols": {
                                "Quantity": 2,
```

```
                                "Items": [
                                    "SSLv3",
                                    "TLSv1"
                                ]
                            },
                            "OriginReadTimeout": 30,
                            "OriginKeepaliveTimeout": 5
                        }
                    }
                ]
            },
            "OriginGroups": {
                "Quantity": 0
            },
            "DefaultCacheBehavior": {
                "TargetOriginId": "example-website",
                "ForwardedValues": {
                    "QueryString": false,
                    "Cookies": {
                        "Forward": "none"
                    },
                    "Headers": {
                        "Quantity": 1,
                        "Items": [
                            "*"
                        ]
                    },
                    "QueryStringCacheKeys": {
                        "Quantity": 0
                    }
                },
                "TrustedSigners": {
                    "Enabled": false,
                    "Quantity": 0
                },
                "ViewerProtocolPolicy": "allow-all",
                "MinTTL": 0,
                "AllowedMethods": {
                    "Quantity": 2,
                    "Items": [
                        "HEAD",
                        "GET"
                    ],
                    "CachedMethods": {
```

```
                        "Quantity": 2,
                        "Items": [
                            "HEAD",
                            "GET"
                        ]
                    }
                },
                "SmoothStreaming": false,
                "DefaultTTL": 86400,
                "MaxTTL": 31536000,
                "Compress": false,
                "LambdaFunctionAssociations": {
                    "Quantity": 0
                },
                "FieldLevelEncryptionId": ""
            },
            "CacheBehaviors": {
                "Quantity": 0
            },
            "CustomErrorResponses": {
                "Quantity": 0
            },
            "Comment": "",
            "Logging": {
                "Enabled": false,
                "IncludeCookies": false,
                "Bucket": "",
                "Prefix": ""
            },
            "PriceClass": "PriceClass_All",
            "Enabled": true,
            "ViewerCertificate": {
                "CloudFrontDefaultCertificate": true,
                "MinimumProtocolVersion": "TLSv1",
                "CertificateSource": "cloudfront"
            },
            "Restrictions": {
                "GeoRestriction": {
                    "RestrictionType": "none",
                    "Quantity": 0
                }
            },
            "WebACLId": "",
            "HttpVersion": "http1.1",
```

```
            "IsIPV6Enabled": true
        }
    }
}
```

Para atualizar uma CloudFront distribuição

O exemplo a seguir desativa a CloudFront distribuição com o ID `EMLARXS9EXAMPLE` fornecendo a configuração de distribuição em um arquivo JSON chamado. `dist-config-disable.json` Para atualizar uma distribuição, use a opção `--if-match` para fornecer o `ETag` da distribuição. Para obter o`ETag`, use o comando get-distribution ouget-distribution-config .

Depois de usar o exemplo a seguir para desabilitar uma distribuição, use o comando delete-distribution para exclui-la.

```
aws cloudfront update-distribution \
    --id EMLARXS9EXAMPLE \
    --if-match E2QWRUHEXAMPLE \
    --distribution-config file://dist-config-disable.json
```

O arquivo `dist-config-disable.json` é um documento JSON na pasta atual que contém o seguinte. Observe que o campo `Enabled` está definido como `false`:

```
{
    "CallerReference": "cli-1574382155-496510",
    "Aliases": {
        "Quantity": 0
    },
    "DefaultRootObject": "index.html",
    "Origins": {
        "Quantity": 1,
        "Items": [
            {
                "Id": "awsexamplebucket.s3.amazonaws.com-1574382155-273939",
                "DomainName": "awsexamplebucket.s3.amazonaws.com",
                "OriginPath": "",
                "CustomHeaders": {
                    "Quantity": 0
                },
                "S3OriginConfig": {
                    "OriginAccessIdentity": ""
```

```
                }
            }
        ]
    },
    "OriginGroups": {
        "Quantity": 0
    },
    "DefaultCacheBehavior": {
        "TargetOriginId": "awsexamplebucket.s3.amazonaws.com-1574382155-273939",
        "ForwardedValues": {
            "QueryString": false,
            "Cookies": {
                "Forward": "none"
            },
            "Headers": {
                "Quantity": 0
            },
            "QueryStringCacheKeys": {
                "Quantity": 0
            }
        },
        "TrustedSigners": {
            "Enabled": false,
            "Quantity": 0
        },
        "ViewerProtocolPolicy": "allow-all",
        "MinTTL": 0,
        "AllowedMethods": {
            "Quantity": 2,
            "Items": [
                "HEAD",
                "GET"
            ],
            "CachedMethods": {
                "Quantity": 2,
                "Items": [
                    "HEAD",
                    "GET"
                ]
            }
        },
        "SmoothStreaming": false,
        "DefaultTTL": 86400,
        "MaxTTL": 31536000,
```

```
        "Compress": false,
        "LambdaFunctionAssociations": {
            "Quantity": 0
        },
        "FieldLevelEncryptionId": ""
    },
    "CacheBehaviors": {
        "Quantity": 0
    },
    "CustomErrorResponses": {
        "Quantity": 0
    },
    "Comment": "",
    "Logging": {
        "Enabled": false,
        "IncludeCookies": false,
        "Bucket": "",
        "Prefix": ""
    },
    "PriceClass": "PriceClass_All",
    "Enabled": false,
    "ViewerCertificate": {
        "CloudFrontDefaultCertificate": true,
        "MinimumProtocolVersion": "TLSv1",
        "CertificateSource": "cloudfront"
    },
    "Restrictions": {
        "GeoRestriction": {
            "RestrictionType": "none",
            "Quantity": 0
        }
    },
    "WebACLId": "",
    "HttpVersion": "http2",
    "IsIPV6Enabled": true
}
```

Saída:

```
{
    "ETag": "E9LHASXEXAMPLE",
    "Distribution": {
        "Id": "EMLARXS9EXAMPLE",
```

```
        "ARN": "arn:aws:cloudfront::123456789012:distribution/EMLARXS9EXAMPLE",
        "Status": "InProgress",
        "LastModifiedTime": "2019-12-06T18:32:35.553Z",
        "InProgressInvalidationBatches": 0,
        "DomainName": "d111111abcdef8.cloudfront.net",
        "ActiveTrustedSigners": {
            "Enabled": false,
            "Quantity": 0
        },
        "DistributionConfig": {
            "CallerReference": "cli-1574382155-496510",
            "Aliases": {
                "Quantity": 0
            },
            "DefaultRootObject": "index.html",
            "Origins": {
                "Quantity": 1,
                "Items": [
                    {
                        "Id":
 "awsexamplebucket.s3.amazonaws.com-1574382155-273939",
                        "DomainName": "awsexamplebucket.s3.amazonaws.com",
                        "OriginPath": "",
                        "CustomHeaders": {
                            "Quantity": 0
                        },
                        "S3OriginConfig": {
                            "OriginAccessIdentity": ""
                        }
                    }
                ]
            },
            "OriginGroups": {
                "Quantity": 0
            },
            "DefaultCacheBehavior": {
                "TargetOriginId":
 "awsexamplebucket.s3.amazonaws.com-1574382155-273939",
                "ForwardedValues": {
                    "QueryString": false,
                    "Cookies": {
                        "Forward": "none"
                    },
                    "Headers": {
```

```
                        "Quantity": 0
                    },
                    "QueryStringCacheKeys": {
                        "Quantity": 0
                    }
                },
                "TrustedSigners": {
                    "Enabled": false,
                    "Quantity": 0
                },
                "ViewerProtocolPolicy": "allow-all",
                "MinTTL": 0,
                "AllowedMethods": {
                    "Quantity": 2,
                    "Items": [
                        "HEAD",
                        "GET"
                    ],
                    "CachedMethods": {
                        "Quantity": 2,
                        "Items": [
                            "HEAD",
                            "GET"
                        ]
                    }
                },
                "SmoothStreaming": false,
                "DefaultTTL": 86400,
                "MaxTTL": 31536000,
                "Compress": false,
                "LambdaFunctionAssociations": {
                    "Quantity": 0
                },
                "FieldLevelEncryptionId": ""
            },
            "CacheBehaviors": {
                "Quantity": 0
            },
            "CustomErrorResponses": {
                "Quantity": 0
            },
            "Comment": "",
            "Logging": {
                "Enabled": false,
```

```
                "IncludeCookies": false,
                "Bucket": "",
                "Prefix": ""
            },
            "PriceClass": "PriceClass_All",
            "Enabled": false,
            "ViewerCertificate": {
                "CloudFrontDefaultCertificate": true,
                "MinimumProtocolVersion": "TLSv1",
                "CertificateSource": "cloudfront"
            },
            "Restrictions": {
                "GeoRestriction": {
                    "RestrictionType": "none",
                    "Quantity": 0
                }
            },
            "WebACLId": "",
            "HttpVersion": "http2",
            "IsIPV6Enabled": true
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateDistributionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionRequest;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
```

```
import software.amazon.awssdk.services.cloudfront.model.Distribution;
import software.amazon.awssdk.services.cloudfront.model.DistributionConfig;
import
 software.amazon.awssdk.services.cloudfront.model.UpdateDistributionRequest;
import software.amazon.awssdk.services.cloudfront.model.CloudFrontException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ModifyDistribution {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <id>\s

                Where:
                    id - the id value of the distribution.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String id = args[0];
        CloudFrontClient cloudFrontClient = CloudFrontClient.builder()
                .region(Region.AWS_GLOBAL)
                .build();

        modDistribution(cloudFrontClient, id);
        cloudFrontClient.close();
    }

    public static void modDistribution(CloudFrontClient cloudFrontClient, String
 idVal) {
        try {
            // Get the Distribution to modify.
```

```
            GetDistributionRequest disRequest = GetDistributionRequest.builder()
                    .id(idVal)
                    .build();

            GetDistributionResponse response =
cloudFrontClient.getDistribution(disRequest);
            Distribution disObject = response.distribution();
            DistributionConfig config = disObject.distributionConfig();

            // Create a new DistributionConfig object and add new values to
comment and
            // aliases
            DistributionConfig config1 = DistributionConfig.builder()
                    .aliases(config.aliases()) // You can pass in new values here
                    .comment("New Comment")
                    .cacheBehaviors(config.cacheBehaviors())
                    .priceClass(config.priceClass())
                    .defaultCacheBehavior(config.defaultCacheBehavior())
                    .enabled(config.enabled())
                    .callerReference(config.callerReference())
                    .logging(config.logging())
                    .originGroups(config.originGroups())
                    .origins(config.origins())
                    .restrictions(config.restrictions())
                    .defaultRootObject(config.defaultRootObject())
                    .webACLId(config.webACLId())
                    .httpVersion(config.httpVersion())
                    .viewerCertificate(config.viewerCertificate())
                    .customErrorResponses(config.customErrorResponses())
                    .build();

            UpdateDistributionRequest updateDistributionRequest =
UpdateDistributionRequest.builder()
                    .distributionConfig(config1)
                    .id(disObject.id())
                    .ifMatch(response.eTag())
                    .build();

            cloudFrontClient.updateDistribution(updateDistributionRequest);

        } catch (CloudFrontException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte UpdateDistributiona Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""

    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client


    def update_distribution(self):
        distribution_id = input(
            "This script updates the comment for a CloudFront distribution.\n"
            "Enter a CloudFront distribution ID: "
        )

        distribution_config_response =
 self.cloudfront_client.get_distribution_config(
            Id=distribution_id
        )
        distribution_config = distribution_config_response["DistributionConfig"]
        distribution_etag = distribution_config_response["ETag"]

        distribution_config["Comment"] = input(
```

```
            f"\nThe current comment for distribution {distribution_id} is "
            f"'{distribution_config['Comment']}'.\n"
            f"Enter a new comment: "
        )
        self.cloudfront_client.update_distribution(
            DistributionConfig=distribution_config,
            Id=distribution_id,
            IfMatch=distribution_etag,
        )
        print("Done!")
```

- Para obter detalhes da API, consulte a UpdateDistributionReferência da API AWSSDK for Python (Boto3).

Faça upload de uma chave pública para CloudFront usar um AWS SDK

Os exemplos de código a seguir mostram como fazer o upload de uma chave pública.

CLI

AWS CLI

Para criar uma chave CloudFront pública

O exemplo a seguir cria uma chave CloudFront pública fornecendo os parâmetros em um arquivo JSON chamado`pub-key-config.json`. Antes de usar esse comando, você deve ter uma chave pública codificada em PEM. Para obter mais informações, consulte Criar um par de chaves RSA no Amazon CloudFront Developer Guide.

```
aws cloudfront create-public-key \
    --public-key-config file://pub-key-config.json
```

O arquivo `pub-key-config.json` é um documento JSON na pasta atual que contém o seguinte. Observe que a chave pública é codificada no formato PEM.

```
{
    "CallerReference": "cli-example",
```

```
    "Name": "ExampleKey",
    "EncodedKey": "-----BEGIN PUBLIC KEY-----
\nMIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAxPMbCA2Ks0lnd7IR+3pw
\nwd3H/7jPGwj8bLUmore7bX+oeGpZ6QmLAe/1UOWcmZX2u70dYcSIzB1ofZtcn4cJ
\nenHBAzO3ohBY/L1tQGJfS2A+omnN6H16VZE1JCK8XSJyfze7MDLcUyHZETdxuvRb
\nA9X343/vMAuQPnhinFJ8Wdy8YBXSPpy7r95ylUQd9LfYTBzVZYG2tSesplcOkjM3\n2Uu
+oMWxQAw1NINnSLPinMVsutJy6ZqlV3McWNWe4T+STGtWhrPNqJEn45sIcCx4\nq
+kGZ2NQ0FyIyT2eiLKOX5Rgb/a36E/aMk4VoDsaenBQgG7WLTnstb9sr7MIhS6A\nrwIDAQAB\n-----
END PUBLIC KEY-----\n",
    "Comment": "example public key"
}
```

Saída:

```
{
    "Location": "https://cloudfront.amazonaws.com/2019-03-26/public-key/
KDFB19YGCR002",
    "ETag": "E2QWRUHEXAMPLE",
    "PublicKey": {
        "Id": "KDFB19YGCR002",
        "CreatedTime": "2019-12-05T18:51:43.781Z",
        "PublicKeyConfig": {
            "CallerReference": "cli-example",
            "Name": "ExampleKey",
            "EncodedKey": "-----BEGIN PUBLIC KEY-----
\nMIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAxPMbCA2Ks0lnd7IR+3pw
\nwd3H/7jPGwj8bLUmore7bX+oeGpZ6QmLAe/1UOWcmZX2u70dYcSIzB1ofZtcn4cJ
\nenHBAzO3ohBY/L1tQGJfS2A+omnN6H16VZE1JCK8XSJyfze7MDLcUyHZETdxuvRb
\nA9X343/vMAuQPnhinFJ8Wdy8YBXSPpy7r95ylUQd9LfYTBzVZYG2tSesplcOkjM3\n2Uu
+oMWxQAw1NINnSLPinMVsutJy6ZqlV3McWNWe4T+STGtWhrPNqJEn45sIcCx4\nq
+kGZ2NQ0FyIyT2eiLKOX5Rgb/a36E/aMk4VoDsaenBQgG7WLTnstb9sr7MIhS6A\nrwIDAQAB\n-----
END PUBLIC KEY-----\n",
            "Comment": "example public key"
        }
    }
}
```

- Para obter detalhes da API, consulte CreatePublicKeyem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo de código a seguir lê uma chave pública e a carrega na Amazon CloudFront.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.CreatePublicKeyResponse;
import software.amazon.awssdk.utils.IoUtils;

import java.io.IOException;
import java.io.InputStream;
import java.util.UUID;

public class CreatePublicKey {
    private static final Logger logger =
 LoggerFactory.getLogger(CreatePublicKey.class);

    public static String createPublicKey(CloudFrontClient cloudFrontClient,
 String publicKeyFileName) {
        try (InputStream is =
 CreatePublicKey.class.getClassLoader().getResourceAsStream(publicKeyFileName)) {
            String publicKeyString = IoUtils.toUtf8String(is);
            CreatePublicKeyResponse createPublicKeyResponse = cloudFrontClient
                    .createPublicKey(b -> b.publicKeyConfig(c -> c
                            .name("JavaCreatedPublicKey" + UUID.randomUUID())
                            .encodedKey(publicKeyString)
                            .callerReference(UUID.randomUUID().toString())));
            String createdPublicKeyId = createPublicKeyResponse.publicKey().id();
            logger.info("Public key created with id: [{}]", createdPublicKeyId);
            return createdPublicKeyId;

        } catch (IOException e) {
            throw new RuntimeException(e);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte CreatePublicKeya Referência AWS SDK for Java 2.x da API.

Cenários para CloudFront usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudFront com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie URLs e cookies assinados usando um SDK da AWS

Crie URLs e cookies assinados usando um SDK da AWS

O exemplo de código a seguir mostra como criar URLs e cookies assinados que permitem acesso a recursos restritos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use a CannedSignerRequestclasse para assinar URLs ou cookies com uma política predefinida.

```
import software.amazon.awssdk.services.cloudfront.model.CannedSignerRequest;
```

```
import java.net.URL;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.temporal.ChronoUnit;

public class CreateCannedPolicyRequest {

    public static CannedSignerRequest createRequestForCannedPolicy(String
 distributionDomainName,
            String fileNameToUpload,
            String privateKeyFullPath, String publicKeyId) throws Exception {
        String protocol = "https";
        String resourcePath = "/" + fileNameToUpload;

        String cloudFrontUrl = new URL(protocol, distributionDomainName,
 resourcePath).toString();
        Instant expirationDate = Instant.now().plus(7, ChronoUnit.DAYS);
        Path path = Paths.get(privateKeyFullPath);

        return CannedSignerRequest.builder()
                .resourceUrl(cloudFrontUrl)
                .privateKey(path)
                .keyPairId(publicKeyId)
                .expirationDate(expirationDate)
                .build();
    }
}
```

Use a CustomSignerRequestclasse para assinar URLs ou cookies com uma política personalizada. O `activeDate` e `ipRange` são métodos opcionais.

```
import software.amazon.awssdk.services.cloudfront.model.CustomSignerRequest;

import java.net.URL;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.temporal.ChronoUnit;

public class CreateCustomPolicyRequest {
```

```
    public static CustomSignerRequest createRequestForCustomPolicy(String
 distributionDomainName,
            String fileNameToUpload,
            String privateKeyFullPath, String publicKeyId) throws Exception {
        String protocol = "https";
        String resourcePath = "/" + fileNameToUpload;

        String cloudFrontUrl = new URL(protocol, distributionDomainName,
 resourcePath).toString();
        Instant expireDate = Instant.now().plus(7, ChronoUnit.DAYS);
        // URL will be accessible tomorrow using the signed URL.
        Instant activeDate = Instant.now().plus(1, ChronoUnit.DAYS);
        Path path = Paths.get(privateKeyFullPath);

        return CustomSignerRequest.builder()
                .resourceUrl(cloudFrontUrl)
                .privateKey(path)
                .keyPairId(publicKeyId)
                .expirationDate(expireDate)
                .activeDate(activeDate) // Optional.
                // .ipRange("192.168.0.1/24") // Optional.
                .build();
    }
}
```

O exemplo a seguir demonstra o uso da CloudFrontUtilitiesclasse para produzir cookies e URLs assinados. Veja este exemplo de código em GitHub.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontUtilities;
import software.amazon.awssdk.services.cloudfront.cookie.CookiesForCannedPolicy;
import software.amazon.awssdk.services.cloudfront.cookie.CookiesForCustomPolicy;
import software.amazon.awssdk.services.cloudfront.model.CannedSignerRequest;
import software.amazon.awssdk.services.cloudfront.model.CustomSignerRequest;
import software.amazon.awssdk.services.cloudfront.url.SignedUrl;

public class SigningUtilities {
    private static final Logger logger =
 LoggerFactory.getLogger(SigningUtilities.class);
    private static final CloudFrontUtilities cloudFrontUtilities =
 CloudFrontUtilities.create();
```

```
    public static SignedUrl signUrlForCannedPolicy(CannedSignerRequest
 cannedSignerRequest) {
        SignedUrl signedUrl =
 cloudFrontUtilities.getSignedUrlWithCannedPolicy(cannedSignerRequest);
        logger.info("Signed URL: [{}]", signedUrl.url());
        return signedUrl;
    }

    public static SignedUrl signUrlForCustomPolicy(CustomSignerRequest
 customSignerRequest) {
        SignedUrl signedUrl =
 cloudFrontUtilities.getSignedUrlWithCustomPolicy(customSignerRequest);
        logger.info("Signed URL: [{}]", signedUrl.url());
        return signedUrl;
    }

    public static CookiesForCannedPolicy
 getCookiesForCannedPolicy(CannedSignerRequest cannedSignerRequest) {
        CookiesForCannedPolicy cookiesForCannedPolicy = cloudFrontUtilities
                .getCookiesForCannedPolicy(cannedSignerRequest);
        logger.info("Cookie EXPIRES header [{}]",
 cookiesForCannedPolicy.expiresHeaderValue());
        logger.info("Cookie KEYPAIR header [{}]",
 cookiesForCannedPolicy.keyPairIdHeaderValue());
        logger.info("Cookie SIGNATURE header [{}]",
 cookiesForCannedPolicy.signatureHeaderValue());
        return cookiesForCannedPolicy;
    }

    public static CookiesForCustomPolicy
 getCookiesForCustomPolicy(CustomSignerRequest customSignerRequest) {
        CookiesForCustomPolicy cookiesForCustomPolicy = cloudFrontUtilities
                .getCookiesForCustomPolicy(customSignerRequest);
        logger.info("Cookie POLICY header [{}]",
 cookiesForCustomPolicy.policyHeaderValue());
        logger.info("Cookie KEYPAIR header [{}]",
 cookiesForCustomPolicy.keyPairIdHeaderValue());
        logger.info("Cookie SIGNATURE header [{}]",
 cookiesForCustomPolicy.signatureHeaderValue());
        return cookiesForCustomPolicy;
    }
}
```

- Para obter detalhes da API, consulte CloudFrontUtilitiesa Referência AWS SDK for Java 2.x da API.

Exemplos de código para CloudTrail usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS CloudTrail com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- CloudTrail Guia do desenvolvedor — Mais informações sobre CloudTrail.
- CloudTrail Referência da API — Detalhes sobre todas as CloudTrail ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para CloudTrail usar AWS SDKs
  - Crie uma CloudTrail trilha usando um AWS SDK
  - Excluir uma CloudTrail trilha usando um AWS SDK
  - Listar eventos de CloudTrail trilha usando um AWS SDK
  - Listar CloudTrail trilhas usando um AWS SDK

Ações para CloudTrail usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS CloudTrail com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie uma CloudTrail trilha usando um AWS SDK
- Excluir uma CloudTrail trilha usando um AWS SDK
- Listar eventos de CloudTrail trilha usando um AWS SDK
- Listar CloudTrail trilhas usando um AWS SDK

Crie uma CloudTrail trilha usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma AWS CloudTrail trilha.

CLI

AWS CLI

Para criar uma trilha

O `create-trail` comando a seguir cria uma trilha multirregional chamada `Trail1` e especifica um bucket do S3:

```
aws cloudtrail create-trail --name Trail1 --s3-bucket-name my-bucket --is-multi-
region-trail
```

Saída:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "Trail1",
  "TrailARN": "arn:aws:cloudtrail:us-west-2:123456789012:trail/Trail1",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "S3BucketName": "my-bucket"
}
```

- Para obter detalhes da API, consulte CreateTrailem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail" # v2: require 'aws-sdk'
require "aws-sdk-s3"
require "aws-sdk-sts"

def create_trail_example(s3_client, sts_client, cloudtrail_client, trail_name,
 bucket_name)

  resp = sts_client.get_caller_identity({})
  account_id = resp.account

  # Attach policy to an Amazon Simple Storage Service (S3) bucket.
  s3_client.create_bucket(bucket: bucket_name)
  begin
    policy = {
      "Version" => "2012-10-17",
      "Statement" => [
        {
          "Sid" => "AWSCloudTrailAclCheck20150319",
          "Effect" => "Allow",
          "Principal" => {
            "Service" => "cloudtrail.amazonaws.com"
          },
          "Action" => "s3:GetBucketAcl",
          "Resource" => "arn:aws:s3:::#{bucket_name}"
        },
        {
          "Sid" => "AWSCloudTrailWrite20150319",
          "Effect" => "Allow",
          "Principal" => {
            "Service" => "cloudtrail.amazonaws.com"
          },
          "Action" => "s3:PutObject",
```

```
          "Resource" => "arn:aws:s3:::#{bucket_name}/AWSLogs/#{account_id}/*",
          "Condition" => {
            "StringEquals" => {
              "s3:x-amz-acl" => "bucket-owner-full-control"
            }
          }
        }
      ]
    }.to_json

    s3_client.put_bucket_policy(
      bucket: bucket_name,
      policy: policy
    )
    puts "Successfully added policy to bucket #{bucket_name}"
  end

  begin
    cloudtrail_client.create_trail({
                                     name: trail_name, # required
                                     s3_bucket_name: bucket_name # required
                                   })

    puts "Successfully created trail: #{trail_name}."
  rescue StandardError => e
    puts "Got error trying to create trail #{trail_name}:\n #{e}"
    puts e
    exit 1
  end
```

- Para obter detalhes da API, consulte CreateTrail a Referência AWS SDK for Ruby da API.

Excluir uma CloudTrail trilha usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma AWS CloudTrail trilha.

CLI

AWS CLI

Para excluir uma trilha

O `delete-trail` comando a seguir exclui uma trilha chamada`Trail1`:

```
aws cloudtrail delete-trail --name Trail1
```

- Para obter detalhes da API, consulte DeleteTrailem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  client.delete_trail({
                        name: trail_name # required
                      })
  puts "Successfully deleted trail: " + trail_name
rescue StandardError => err
  puts "Got error trying to delete trail: " + trail_name + ":"
  puts err
  exit 1
end
```

- Para obter detalhes da API, consulte DeleteTraila Referência AWS SDK for Ruby da API.

Listar eventos de CloudTrail trilha usando um AWS SDK

O exemplo de código a seguir mostra como listar eventos de AWS CloudTrail trilha.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail" # v2: require 'aws-sdk'

# @param [Object] client
def lookup_events_example(client)
  resp = client.lookup_events
  puts "Found #{resp.events.count} events:"
  resp.events.each do |e|
    puts "Event name:   #{e.event_name}"
    puts "Event ID:     #{e.event_id}"
    puts "Event time:   #{e.event_time}"
    puts "Resources:"

    e.resources.each do |r|
      puts "  Name:       #{r.resource_name}"
      puts "  Type:       #{r.resource_type}"
      puts ""
    end
  end
end
```

- Para obter detalhes da API, consulte LookupEventsa Referência AWS SDK for Ruby da API.

Listar CloudTrail trilhas usando um AWS SDK

O exemplo de código a seguir mostra como listar AWS CloudTrail trilhas.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail"  # v2: require 'aws-sdk'

def describe_trails_example(client)
  resp = client.describe_trails({})
  puts "Found #{resp.trail_list.count} trail(s)."

  resp.trail_list.each do |trail|
    puts "Name:           " + trail.name
    puts "S3 bucket name: " + trail.s3_bucket_name
    puts
  end
```

- Para obter detalhes da API, consulte ListTrailsa Referência AWS SDK for Ruby da API.

Exemplos de código para CloudWatch usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudWatch com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- CloudWatch Guia do usuário — Mais informações sobre CloudWatch.

- CloudWatch Referência da API — Detalhes sobre todas as CloudWatch ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá CloudWatch

O exemplo de código a seguir mostra como começar a usar o CloudWatch.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.CloudWatch;
using Amazon.CloudWatch.Model;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;

namespace CloudWatchActions;

public static class HelloCloudWatch
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon CloudWatch service.
        // Use your AWS profile name, or leave it blank to use the default
 profile.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonCloudWatch>()
            ).Build();
```

```
        // Now the client is available for injection.
        var cloudWatchClient =
host.Services.GetRequiredService<IAmazonCloudWatch>();

        // You can use await and any of the async methods to get a response.
        var metricNamespace = "AWS/Billing";
        var response = await cloudWatchClient.ListMetricsAsync(new
ListMetricsRequest
        {
            Namespace = metricNamespace
        });
        Console.WriteLine($"Hello Amazon CloudWatch! Following are some metrics
available in the {metricNamespace} namespace:");
        Console.WriteLine();
        foreach (var metric in response.Metrics.Take(5))
        {
            Console.WriteLine($"\tMetric: {metric.MetricName}");
            Console.WriteLine($"\tNamespace: {metric.Namespace}");
            Console.WriteLine($"\tDimensions: {string.Join(", ",
metric.Dimensions.Select(m => $"{m.Name}:{m.Value}"))}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
```

```
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.paginators.ListMetricsIterable;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloService {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <namespace>\s

                Where:
                  namespace - The namespace to filter against (for example, AWS/
EC2).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String namespace = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        listMets(cw, namespace);
        cw.close();
    }

    public static void listMets(CloudWatchClient cw, String namespace) {
        try {
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();
```

```
            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> System.out.println(" Retrieved metric is:
 " + metrics.metricName()));

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
           <namespace>
        Where:
           namespace - The namespace to filter against (for example, AWS/EC2).
    """
```

```
    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val namespace = args[0]
    listAllMets(namespace)
}

suspend fun listAllMets(namespaceVal: String?) {
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listMetricsPaginated(request)
            .transform { it.metrics?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name is ${obj.metricName}")
                println("Namespace is ${obj.namespace}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações para CloudWatch usar AWS SDKs
  - Crie um CloudWatch painel
  - Crie um alarme CloudWatch métrico usando um AWS SDK
  - Crie um detector de CloudWatch anomalias
  - Excluir CloudWatch alarmes usando um SDK AWS
  - Excluir um detector de CloudWatch anomalias usando um SDK AWS
  - Excluir CloudWatch painéis usando um SDK AWS
  - Descrever o histórico de CloudWatch alarmes usando um AWS SDK
  - Descrever CloudWatch os alarmes usando um SDK AWS
  - Descrever CloudWatch os alarmes para uma métrica usando um SDK AWS

- Descreva os detectores de CloudWatch anomalias usando um SDK AWS
- Desative as ações de CloudWatch alarme usando um AWS SDK
- Ativar ações de CloudWatch alarme usando um AWS SDK
- Obtenha uma imagem de dados CloudWatch métricos
- Obtenha os detalhes de um CloudWatch painel
- Obtenha valores de dados CloudWatch métricos
- Obtenha estatísticas CloudWatch métricas usando um AWS SDK
- Listar CloudWatch painéis
- Listar CloudWatch métricas usando um AWS SDK
- Coloque um conjunto de dados em uma CloudWatch métrica usando um AWS SDK
- Coloque dados em uma CloudWatch métrica usando um AWS SDK
- Cenários para CloudWatch usar AWS SDKs
  - Comece a usar CloudWatch alarmes usando um SDK AWS
  - Comece a usar CloudWatch métricas, painéis e alarmes usando um SDK AWS
  - Gerencie CloudWatch métricas e alarmes usando um SDK AWS

Ações para CloudWatch usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudWatch com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para CloudWatch usar AWS SDKs.

Exemplos

- Crie um CloudWatch painel
- Crie um alarme CloudWatch métrico usando um AWS SDK
- Crie um detector de CloudWatch anomalias
- Excluir CloudWatch alarmes usando um SDK AWS
- Excluir um detector de CloudWatch anomalias usando um SDK AWS
- Excluir CloudWatch painéis usando um SDK AWS
- Descrever o histórico de CloudWatch alarmes usando um AWS SDK

- Descrever CloudWatch os alarmes usando um SDK AWS
- Descrever CloudWatch os alarmes para uma métrica usando um SDK AWS
- Descreva os detectores de CloudWatch anomalias usando um SDK AWS
- Desative as ações de CloudWatch alarme usando um AWS SDK
- Ativar ações de CloudWatch alarme usando um AWS SDK
- Obtenha uma imagem de dados CloudWatch métricos
- Obtenha os detalhes de um CloudWatch painel
- Obtenha valores de dados CloudWatch métricos
- Obtenha estatísticas CloudWatch métricas usando um AWS SDK
- Listar CloudWatch painéis
- Listar CloudWatch métricas usando um AWS SDK
- Coloque um conjunto de dados em uma CloudWatch métrica usando um AWS SDK
- Coloque dados em uma CloudWatch métrica usando um AWS SDK

Crie um CloudWatch painel

Os exemplos de código a seguir mostram como criar um CloudWatch painel da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
```

```
    /// Set up a dashboard using a call to the wrapper class.
    /// </summary>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A list of validation messages.</returns>
    private static async Task<List<DashboardValidationMessage>> SetupDashboard(
        string customMetricNamespace, string customMetricName, string
dashboardName)
    {
        // Get the dashboard model from configuration.
        var newDashboard = new DashboardModel();
        _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);

        // Add a new metric to the dashboard.
        newDashboard.Widgets.Add(new Widget
        {
            Height = 8,
            Width = 8,
            Y = 8,
            X = 0,
            Type = "metric",
            Properties = new Properties
            {
                Metrics = new List<List<object>>
                    { new() { customMetricNamespace, customMetricName } },
                View = "timeSeries",
                Region = "us-east-1",
                Stat = "Sum",
                Period = 86400,
                YAxis = new YAxis { Left = new Left { Min = 0, Max = 100 } },
                Title = "Custom Metric Widget",
                LiveData = true,
                Sparkline = true,
                Trend = true,
                Stacked = false,
                SetPeriodToTimeRange = false
            }
        });

        var newDashboardString = JsonSerializer.Serialize(newDashboard,
            new JsonSerializerOptions
            { DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull });
        var validationMessages =
```

```
            await _cloudWatchWrapper.PutDashboard(dashboardName,
 newDashboardString);

        return validationMessages;
    }

    /// <summary>
    /// Wrapper to create or add to a dashboard with metrics.
    /// </summary>
    /// <param name="dashboardName">The name for the dashboard.</param>
    /// <param name="dashboardBody">The metric data in JSON for the dashboard.</
param>
    /// <returns>A list of validation messages for the dashboard.</returns>
    public async Task<List<DashboardValidationMessage>> PutDashboard(string
 dashboardName,
        string dashboardBody)
    {
        // Updating a dashboard replaces all contents.
        // Best practice is to include a text widget indicating this dashboard
 was created programmatically.
        var dashboardResponse = await _amazonCloudWatch.PutDashboardAsync(
            new PutDashboardRequest()
            {
                DashboardName = dashboardName,
                DashboardBody = dashboardBody
            });

        return dashboardResponse.DashboardValidationMessages;
    }
```

- Para obter detalhes da API, consulte PutDashboarda Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDashboardWithMetrics(CloudWatchClient cw, String
dashboardName, String fileName) {
       try {
           PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                   .dashboardName(dashboardName)
                   .dashboardBody(readFileAsString(fileName))
                   .build();

           PutDashboardResponse response = cw.putDashboard(dashboardRequest);
           System.out.println(dashboardName + " was successfully created.");
           List<DashboardValidationMessage> messages =
response.dashboardValidationMessages();
           if (messages.isEmpty()) {
               System.out.println("There are no messages in the new Dashboard");
           } else {
               for (DashboardValidationMessage message : messages) {
                   System.out.println("Message is: " + message.message());
               }
           }

       } catch (CloudWatchException | IOException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte PutDashboarda Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDashboardWithMetrics(dashboardNameVal: String, fileNameVal:
 String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully created.")
        val messages = response.dashboardValidationMessages
        if (messages != null) {
            if (messages.isEmpty()) {
                println("There are no messages in the new Dashboard")
            } else {
                for (message in messages) {
                    println("Message is: ${message.message}")
                }
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a PutDashboardreferência da API AWSSDK for Kotlin.

Crie um alarme CloudWatch métrico usando um AWS SDK

Os exemplos de código a seguir mostram como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar alarmes
- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Add a metric alarm to send an email when the metric passes a threshold.
   /// </summary>
   /// <param name="alarmDescription">A description of the alarm.</param>
   /// <param name="alarmName">The name for the alarm.</param>
   /// <param name="comparison">The type of comparison to use.</param>
   /// <param name="metricName">The name of the metric for the alarm.</param>
   /// <param name="metricNamespace">The namespace of the metric.</param>
   /// <param name="threshold">The threshold value for the alarm.</param>
   /// <param name="alarmActions">Optional actions to execute when in an alarm
state.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> PutMetricEmailAlarm(string alarmDescription, string
alarmName, ComparisonOperator comparison,
       string metricName, string metricNamespace, double threshold, List<string>
alarmActions = null!)
   {
       try
       {
           var putEmailAlarmResponse = await
_amazonCloudWatch.PutMetricAlarmAsync(
               new PutMetricAlarmRequest()
               {
                   AlarmActions = alarmActions,
```

```
                    AlarmDescription = alarmDescription,
                    AlarmName = alarmName,
                    ComparisonOperator = comparison,
                    Threshold = threshold,
                    Namespace = metricNamespace,
                    MetricName = metricName,
                    EvaluationPeriods = 1,
                    Period = 10,
                    Statistic = new Statistic("Maximum"),
                    DatapointsToAlarm = 1,
                    TreatMissingData = "ignore"
                });
            return putEmailAlarmResponse.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (LimitExceededException lex)
        {
            _logger.LogError(lex, $"Unable to add alarm {alarmName}. Alarm quota
 has already been reached.");
        }

        return false;
    }

    /// <summary>
    /// Add specific email actions to a list of action strings for a CloudWatch
 alarm.
    /// </summary>
    /// <param name="accountId">The AccountId for the alarm.</param>
    /// <param name="region">The region for the alarm.</param>
    /// <param name="emailTopicName">An Amazon Simple Notification Service (SNS)
 topic for the alarm email.</param>
    /// <param name="alarmActions">Optional list of existing alarm actions to
 append to.</param>
    /// <returns>A list of string actions for an alarm.</returns>
    public List<string> AddEmailAlarmAction(string accountId, string region,
        string emailTopicName, List<string>? alarmActions = null)
    {
        alarmActions ??= new List<string>();
        var snsAlarmAction = $"arn:aws:sns:{region}:{accountId}:
{emailTopicName}";
        alarmActions.Add(snsAlarmAction);
        return alarmActions;
    }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Crie o alarme para vigiar a métrica.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::PutMetricAlarmRequest request;
        request.SetAlarmName(alarm_name);
        request.SetComparisonOperator(
            Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
        request.SetEvaluationPeriods(1);
        request.SetMetricName("CPUUtilization");
        request.SetNamespace("AWS/EC2");
        request.SetPeriod(60);
        request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
        request.SetThreshold(70.0);
        request.SetActionsEnabled(false);
        request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
        request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);

        Aws::CloudWatch::Model::Dimension dimension;
```

```
        dimension.SetName("InstanceId");
        dimension.SetValue(instanceId);

        request.AddDimensions(dimension);

        auto outcome = cw.PutMetricAlarm(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como enviar uma mensagem de e-mail do Amazon Simple Notification Service quando a utilização da CPU exceder 70%

O seguinte exemplo usa o comando `put-metric-alarm` para enviar uma mensagem de e-mail do Amazon Simple Notification Service quando a utilização da CPU excede 70%:

```
aws cloudwatch put-metric-alarm --alarm-name cpu-mon --alarm-description "Alarm
 when CPU exceeds 70 percent" --metric-name CPUUtilization --namespace AWS/
EC2 --statistic Average --period 300 --threshold 70 --comparison-operator
 GreaterThanThreshold  --dimensions "Name=InstanceId,Value=i-12345678" --
evaluation-periods 2 --alarm-actions arn:aws:sns:us-east-1:111122223333:MyTopic
 --unit Percent
```

Esse comando retornará à solicitação, se houver êxito. Se já existir um alarme com o mesmo nome, ele será substituído pelo novo alarme.

Como especificar diversas dimensões

O exemplo apresentado a seguir ilustra como especificar diversas dimensões. Cada dimensão é especificada como um par de nome/valor, com uma vírgula entre o nome e o valor. As diversas dimensões são separadas por um espaço:

```
aws cloudwatch put-metric-alarm --alarm-name "Default_Test_Alarm3" --alarm-
description "The default example alarm" --namespace "CW EXAMPLE METRICS" --
metric-name Default_Test --statistic Average --period 60 --evaluation-periods 3
 --threshold 50 --comparison-operator GreaterThanOrEqualToThreshold --dimensions
 Name=key1,Value=value1 Name=key2,Value=value2
```

- Para obter detalhes da API, consulte PutMetricAlarmem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            String alarmName = rootNode.findValue("exampleAlarmName").asText();
            String emailTopic = rootNode.findValue("emailTopic").asText();
            String accountId = rootNode.findValue("accountId").asText();
            String region = rootNode.findValue("region").asText();

            // Create a List for alarm actions.
            List<String> alarmActions = new ArrayList<>();
```

```
            alarmActions.add("arn:aws:sns:" + region + ":" + accountId + ":" +
emailTopic);
            PutMetricAlarmRequest alarmRequest = PutMetricAlarmRequest.builder()
                    .alarmActions(alarmActions)
                    .alarmDescription("Example metric alarm")
                    .alarmName(alarmName)

.comparisonOperator(ComparisonOperator.GREATER_THAN_OR_EQUAL_TO_THRESHOLD)
                    .threshold(100.00)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .evaluationPeriods(1)
                    .period(10)
                    .statistic("Maximum")
                    .datapointsToAlarm(1)
                    .treatMissingData("ignore")
                    .build();

            cw.putMetricAlarm(alarmRequest);
            System.out.println(alarmName + " was successfully created!");
            return alarmName;

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricAlarmCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  // This alarm triggers when CPUUtilization exceeds 70% for one minute.
  const command = new PutMetricAlarmCommand({
    AlarmName: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
    ComparisonOperator: "GreaterThanThreshold",
    EvaluationPeriods: 1,
    MetricName: "CPUUtilization",
    Namespace: "AWS/EC2",
    Period: 60,
    Statistic: "Average",
    Threshold: 70.0,
    ActionsEnabled: false,
    AlarmDescription: "Alarm when server CPU exceeds 70%",
    Dimensions: [
      {
        Name: "InstanceId",
        Value: process.env.EC2_INSTANCE_ID, // Set the value of EC_INSTANCE_ID to
 the Id of an existing Amazon EC2 instance.
      },
    ],
    Unit: "Percent",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";
```

```
export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: false,
  AlarmDescription: "Alarm when server CPU exceeds 70%",
  Dimensions: [
    {
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
```

```
};

cw.putMetricAlarm(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putMetricAlarm(alarmNameVal: String, instanceIdVal: String) {

    val dimensionOb = Dimension {
        name = "InstanceId"
        value = instanceIdVal
    }

    val request = PutMetricAlarmRequest {
        alarmName = alarmNameVal
        comparisonOperator = ComparisonOperator.GreaterThanThreshold
        evaluationPeriods = 1
        metricName = "CPUUtilization"
        namespace = "AWS/EC2"
        period = 60
        statistic = Statistic.fromValue("Average")
```

```
        threshold = 70.0
        actionsEnabled = false
        alarmDescription = "An Alarm created by the Kotlin SDK when server CPU
 utilization exceeds 70%"
        unit = StandardUnit.fromValue("Seconds")
        dimensions = listOf(dimensionOb)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricAlarm(request)
        println("Successfully created an alarm with name $alarmNameVal")
    }
}
```

- Para obter detalhes da API, consulte a PutMetricAlarmreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def create_metric_alarm(
        self,
        metric_namespace,
```

```
        metric_name,
        alarm_name,
        stat_type,
        period,
        eval_periods,
        threshold,
        comparison_op,
    ):
        """
        Creates an alarm that watches a metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :param alarm_name: The name of the alarm.
        :param stat_type: The type of statistic the alarm watches.
        :param period: The period in which metric data are grouped to calculate
                       statistics.
        :param eval_periods: The number of periods that the metric must be over
the
                             alarm threshold before the alarm is set into an
alarmed
                             state.
        :param threshold: The threshold value to compare against the metric
statistic.
        :param comparison_op: The comparison operation used to compare the
threshold
                              against the metric.
        :return: The newly created alarm.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace,
metric_name)
            alarm = metric.put_alarm(
                AlarmName=alarm_name,
                Statistic=stat_type,
                Period=period,
                EvaluationPeriods=eval_periods,
                Threshold=threshold,
                ComparisonOperator=comparison_op,
            )
            logger.info(
                "Added alarm %s to track metric %s.%s.",
                alarm_name,
                metric_namespace,
```

```
                metric_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't add alarm %s to metric %s.%s",
                alarm_name,
                metric_namespace,
                metric_name,
            )
            raise
        else:
            return alarm
```

- Para obter detalhes da API, consulte a PutMetricAlarmReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates or updates an alarm in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param alarm_name [String] The name of the alarm.
# @param alarm_description [String] A description about the alarm.
# @param metric_name [String] The name of the metric associated with the alarm.
# @param alarm_actions [Array] A list of Strings representing the
#   Amazon Resource Names (ARNs) to execute when the alarm transitions to the
#   ALARM state.
# @param namespace [String] The namespace for the metric to alarm on.
# @param statistic [String] The statistic for the metric.
# @param dimensions [Array] A list of dimensions for the metric, specified as
```

```
#   Aws::CloudWatch::Types::Dimension.
# @param period [Integer] The number of seconds before re-evaluating the metric.
# @param unit [String] The unit of measure for the statistic.
# @param evaluation_periods [Integer] The number of periods over which data is
#   compared to the specified threshold.
# @param theshold [Float] The value against which the specified statistic is
 compared.
# @param comparison_operator [String] The arithmetic operation to use when
#   comparing the specified statistic and threshold.
# @return [Boolean] true if the alarm was created or updated; otherwise, false.
# @example
#   exit 1 unless alarm_created_or_updated?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'ObjectsInBucket',
#     'Objects exist in this bucket for more than 1 day.',
#     'NumberOfObjects',
#     ['arn:aws:sns:us-east-1:111111111111:Default_CloudWatch_Alarms_Topic'],
#     'AWS/S3',
#     'Average',
#     [
#       {
#         name: 'BucketName',
#         value: 'doc-example-bucket'
#       },
#       {
#         name: 'StorageType',
#         value: 'AllStorageTypes'
#       }
#     ],
#     86_400,
#     'Count',
#     1,
#     1,
#     'GreaterThanThreshold'
#   )
def alarm_created_or_updated?(
  cloudwatch_client,
  alarm_name,
  alarm_description,
  metric_name,
  alarm_actions,
  namespace,
  statistic,
  dimensions,
```

```
  period,
  unit,
  evaluation_periods,
  threshold,
  comparison_operator
)
  cloudwatch_client.put_metric_alarm(
    alarm_name: alarm_name,
    alarm_description: alarm_description,
    metric_name: metric_name,
    alarm_actions: alarm_actions,
    namespace: namespace,
    statistic: statistic,
    dimensions: dimensions,
    period: period,
    unit: unit,
    evaluation_periods: evaluation_periods,
    threshold: threshold,
    comparison_operator: comparison_operator
  )
  return true
rescue StandardError => e
  puts "Error creating alarm: #{e.message}"
  return false
end
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        lo_cwt->putmetricalarm(
          iv_alarmname                 = iv_alarm_name
          iv_comparisonoperator        = iv_comparison_operator
          iv_evaluationperiods         = iv_evaluation_periods
          iv_metricname                = iv_metric_name
          iv_namespace                 = iv_namespace
          iv_statistic                 = iv_statistic
          iv_threshold                 = iv_threshold
          iv_actionsenabled            = iv_actions_enabled
          iv_alarmdescription          = iv_alarm_description
          iv_unit                      = iv_unit
          iv_period                    = iv_period
          it_dimensions                = it_dimensions
        ).
        MESSAGE 'Alarm created.' TYPE 'I'.
      CATCH /aws1/cx_cwtlimitexceededfault.
        MESSAGE 'The request processing has exceeded the limit' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutMetricAlarmreferência da API AWS SDK for SAP ABAP.

Crie um detector de CloudWatch anomalias

Os exemplos de código a seguir mostram como criar um detector de CloudWatch anomalias na Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Add an anomaly detector for a single metric.
   /// </summary>
   /// <param name="anomalyDetector">A single metric anomaly detector.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> PutAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
   {
       var putAlarmDetectorResult = await
_amazonCloudWatch.PutAnomalyDetectorAsync(
           new PutAnomalyDetectorRequest()
           {
               SingleMetricAnomalyDetector = anomalyDetector
           });

       return putAlarmDetectorResult.HttpStatusCode == HttpStatusCode.OK;
   }
```

- Para obter detalhes da API, consulte PutAnomalyDetectora Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void addAnomalyDetector(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            PutAnomalyDetectorRequest anomalyDetectorRequest =
PutAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.putAnomalyDetector(anomalyDetectorRequest);
            System.out.println("Added anomaly detector for metric " +
customMetricName + ".");

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutAnomalyDetectora Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAnomalyDetector(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val anomalyDetectorRequest = PutAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putAnomalyDetector(anomalyDetectorRequest)
        println("Added anomaly detector for metric $customMetricName.")
    }
}
```

- Para obter detalhes da API, consulte a PutAnomalyDetectorreferência da API AWSSDK for Kotlin.

Excluir CloudWatch alarmes usando um SDK AWS

Os exemplos de código a seguir mostram como excluir os CloudWatch alarmes da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar alarmes
- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete a list of alarms from CloudWatch.
/// </summary>
/// <param name="alarmNames">A list of names of alarms to delete.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteAlarms(List<string> alarmNames)
{
    var deleteAlarmsResult = await _amazonCloudWatch.DeleteAlarmsAsync(
        new DeleteAlarmsRequest()
        {
            AlarmNames = alarmNames
        });

    return deleteAlarmsResult.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DeleteAlarmsRequest.h>
#include <iostream>
```

Exclua o alarme.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DeleteAlarmsRequest request;
        request.AddAlarmNames(alarm_name);

        auto outcome = cw.DeleteAlarms(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to delete CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully deleted CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir um alarme

O exemplo a seguir usa o `delete-alarms` comando para excluir o CloudWatch alarme da Amazon chamado “myalarm”:

```
aws cloudwatch delete-alarms --alarm-names myalarm
```

Saída:

```
This command returns to the prompt if successful.
```

- Para obter detalhes da API, consulte DeleteAlarmsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.DeleteAlarmsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class DeleteAlarm {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <alarmName>

                Where:
                  alarmName - An alarm name to delete (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarmName = args[0];
        Region region = Region.US_EAST_2;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        deleteCWAlarm(cw, alarmName);
        cw.close();
    }

    public static void deleteCWAlarm(CloudWatchClient cw, String alarmName) {
        try {
            DeleteAlarmsRequest request = DeleteAlarmsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.deleteAlarms(request);
            System.out.printf("Successfully deleted alarm %s", alarmName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DeleteAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteAlarmsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmNames: ["Web_Server_CPU_Utilization"],
};

cw.deleteAlarms(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteAlarm(alarmNameVal: String) {
    val request = DeleteAlarmsRequest {
        alarmNames = listOf(alarmNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAlarms(request)
        println("Successfully deleted alarm $alarmNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAlarmsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
```

```
        """
        self.cloudwatch_resource = cloudwatch_resource


    def delete_metric_alarms(self, metric_namespace, metric_name):
        """
        Deletes all of the alarms that are currently watching the specified
metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace,
metric_name)
            metric.alarms.delete()
            logger.info(
                "Deleted alarms for metric %s.%s.", metric_namespace, metric_name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete alarms for metric %s.%s.",
                metric_namespace,
                metric_name,
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteAlarmsReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_cwt->deletealarms(
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarms deleted.' TYPE 'I'.
      CATCH /aws1/cx_cwtresourcenotfound .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteAlarmsreferência da API AWS SDK for SAP ABAP.

Excluir um detector de CloudWatch anomalias usando um SDK AWS

Os exemplos de código a seguir mostram como excluir um detector de CloudWatch anomalias da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a single metric anomaly detector.
    /// </summary>
    /// <param name="anomalyDetector">The anomaly detector to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
```

```
    {
        var deleteAnomalyDetectorResponse = await
_amazonCloudWatch.DeleteAnomalyDetectorAsync(
            new DeleteAnomalyDetectorRequest()
            {
                SingleMetricAnomalyDetector = anomalyDetector
            });

        return deleteAnomalyDetectorResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteAnomalyDetectora Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteAnomalyDetector(CloudWatchClient cw, String
fileName) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();

           SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                   .metricName(customMetricName)
```

```
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            DeleteAnomalyDetectorRequest request =
 DeleteAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.deleteAnomalyDetector(request);
            System.out.println("Successfully deleted the Anomaly Detector.");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
```

- Para obter detalhes da API, consulte DeleteAnomalyDetectora Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteAnomalyDetector(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
```

```
    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val request = DeleteAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAnomalyDetector(request)
        println("Successfully deleted the Anomaly Detector.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAnomalyDetectorreferência da API AWSSDK for Kotlin.

Excluir CloudWatch painéis usando um SDK AWS

Os exemplos de código a seguir mostram como excluir CloudWatch painéis da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a list of CloudWatch dashboards.
    /// </summary>
    /// <param name="dashboardNames">List of dashboard names to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDashboards(List<string> dashboardNames)
    {
        var deleteDashboardsResponse = await
_amazonCloudWatch.DeleteDashboardsAsync(
            new DeleteDashboardsRequest()
            {
                DashboardNames = dashboardNames
            });

        return deleteDashboardsResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDashboardsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteDashboard(CloudWatchClient cw, String dashboardName)
{
        try {
            DeleteDashboardsRequest dashboardsRequest =
DeleteDashboardsRequest.builder()
                    .dashboardNames(dashboardName)
                    .build();
            cw.deleteDashboards(dashboardsRequest);
            System.out.println(dashboardName + " was successfully deleted.");
```

```
        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDashboardsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDashboard(dashboardName: String) {
    val dashboardsRequest = DeleteDashboardsRequest {
        dashboardNames = listOf(dashboardName)
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteDashboards(dashboardsRequest)
        println("$dashboardName was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteDashboardsreferência da API AWSSDK for Kotlin.

Descrever o histórico de CloudWatch alarmes usando um AWS SDK

Os exemplos de código a seguir mostram como descrever um histórico de CloudWatch alarmes da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the history of an alarm for a number of days in the past.
    /// </summary>
    /// <param name="alarmName">The name of the alarm.</param>
    /// <param name="historyDays">The number of days in the past.</param>
    /// <returns>The list of alarm history data.</returns>
    public async Task<List<AlarmHistoryItem>> DescribeAlarmHistory(string
alarmName, int historyDays)
    {
        List<AlarmHistoryItem> alarmHistory = new List<AlarmHistoryItem>();
        var paginatedAlarmHistory =
_amazonCloudWatch.Paginators.DescribeAlarmHistory(
            new DescribeAlarmHistoryRequest()
            {
                AlarmName = alarmName,
                EndDateUtc = DateTime.UtcNow,
                HistoryItemType = HistoryItemType.StateUpdate,
                StartDateUtc = DateTime.UtcNow.AddDays(-historyDays)
            });

        await foreach (var data in paginatedAlarmHistory.AlarmHistoryItems)
        {
            alarmHistory.Add(data);
        }
        return alarmHistory;
    }
```

- Para obter detalhes da API, consulte DescribeAlarmHistorya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como recuperar o histórico para um alarme

O exemplo a seguir usa o `describe-alarm-history` comando para recuperar o histórico do CloudWatch alarme da Amazon chamado “myalarm”:

```
aws cloudwatch describe-alarm-history --alarm-name "myalarm" --history-item-type
 StateUpdate
```

Saída:

```
{
    "AlarmHistoryItems": [
        {
            "Timestamp": "2014-04-09T18:59:06.442Z",
            "HistoryItemType": "StateUpdate",
            "AlarmName": "myalarm",
            "HistoryData": "{\"version\":\"1.0\",\"oldState\":{\"stateValue
\":\"ALARM\",\"stateReason\":\"testing purposes\"},\"newState\":{\"stateValue
\":\"OK\",\"stateReason\":\"Threshold Crossed: 2 datapoints were not
 greater than the threshold (70.0). The most recent datapoints: [38.958,
 40.292].\",\"stateReasonData\":{\"version\":\"1.0\",\"queryDate\":
\"2014-04-09T18:59:06.419+0000\",\"startDate\":\"2014-04-09T18:44:00.000+0000\",
\"statistic\":\"Average\",\"period\":300,\"recentDatapoints\":[38.958,40.292],
\"threshold\":70.0}}}",
            "HistorySummary": "Alarm updated from ALARM to OK"
        },
        {
            "Timestamp": "2014-04-09T18:59:05.805Z",
            "HistoryItemType": "StateUpdate",
            "AlarmName": "myalarm",
            "HistoryData": "{\"version\":\"1.0\",\"oldState\":{\"stateValue
\":\"OK\",\"stateReason\":\"Threshold Crossed: 2 datapoints were
 not greater than the threshold (70.0). The most recent datapoints:
```

```
 [38.839999999999996, 39.714].\",\"stateReasonData\":{\"version\":
\"1.0\",\"queryDate\":\"2014-03-11T22:45:41.569+0000\",\"startDate\":
\"2014-03-11T22:30:00.000+0000\",\"statistic\":\"Average\",\"period\":300,
\"recentDatapoints\":[38.839999999999996,39.714],\"threshold\":70.0}},\"newState
\":{\"stateValue\":\"ALARM\",\"stateReason\":\"testing purposes\"}}",
            "HistorySummary": "Alarm updated from OK to ALARM"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAlarmHistoryem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAlarmHistory(CloudWatchClient cw, String fileName,
String date) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String alarmName = rootNode.findValue("exampleAlarmName").asText();

           Instant start = Instant.parse(date);
           Instant endDate = Instant.now();
           DescribeAlarmHistoryRequest historyRequest =
DescribeAlarmHistoryRequest.builder()
                   .startDate(start)
                   .endDate(endDate)
                   .alarmName(alarmName)
                   .historyItemType(HistoryItemType.ACTION)
```

```
                    .build();

            DescribeAlarmHistoryResponse response =
 cw.describeAlarmHistory(historyRequest);
            List<AlarmHistoryItem> historyItems = response.alarmHistoryItems();
            if (historyItems.isEmpty()) {
                System.out.println("No alarm history data found for " + alarmName
 + ".");
            } else {
                for (AlarmHistoryItem item : historyItems) {
                    System.out.println("History summary: " +
 item.historySummary());
                    System.out.println("Time stamp: " + item.timestamp());
                }
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAlarmHistorya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAlarmHistory(fileName: String, date: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
```

```
    val start = Instant.parse(date)
    val endDateVal = Instant.now()

    val historyRequest = DescribeAlarmHistoryRequest {
        startDate = aws.smithy.kotlin.runtime.time.Instant(start)
        endDate = aws.smithy.kotlin.runtime.time.Instant(endDateVal)
        alarmName = alarmNameVal
        historyItemType = HistoryItemType.Action
    }

    CloudWatchClient { credentialsProvider = EnvironmentCredentialsProvider();
 region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarmHistory(historyRequest)
        val historyItems = response.alarmHistoryItems
        if (historyItems != null) {
            if (historyItems.isEmpty()) {
                println("No alarm history data found for $alarmNameVal.")
            } else {
                for (item in historyItems) {
                    println("History summary ${item.historySummary}")
                    println("Time stamp: ${item.timestamp}")
                }
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmHistoryreferência da API AWSSDK for Kotlin.

Descrever CloudWatch os alarmes usando um SDK AWS

Os exemplos de código a seguir mostram como descrever os CloudWatch alarmes da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar alarmes
- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Describe the current alarms, optionally filtered by state.
   /// </summary>
   /// <param name="stateValue">Optional filter for alarm state.</param>
   /// <returns>The list of alarm data.</returns>
   public async Task<List<MetricAlarm>> DescribeAlarms(StateValue? stateValue =
null)
   {
       List<MetricAlarm> alarms = new List<MetricAlarm>();
       var paginatedDescribeAlarms =
_amazonCloudWatch.Paginators.DescribeAlarms(
           new DescribeAlarmsRequest()
           {
               StateValue = stateValue
           });

       await foreach (var data in paginatedDescribeAlarms.MetricAlarms)
       {
           alarms.Add(data);
       }
       return alarms;
   }
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar informações sobre um alarme

O seguinte exemplo usa o comando `describe-alarms` para fornecer informações sobre o alarme denominado “myalarm”:

```
aws cloudwatch describe-alarms --alarm-names "myalarm"
```

Saída:

```
{
    "MetricAlarms": [
        {
            "EvaluationPeriods": 2,
            "AlarmArn": "arn:aws:cloudwatch:us-
east-1:123456789012:alarm:myalarm",
            "StateUpdatedTimestamp": "2014-04-09T18:59:06.442Z",
            "AlarmConfigurationUpdatedTimestamp": "2012-12-27T00:49:54.032Z",
            "ComparisonOperator": "GreaterThanThreshold",
            "AlarmActions": [
                "arn:aws:sns:us-east-1:123456789012:myHighCpuAlarm"
            ],
            "Namespace": "AWS/EC2",
            "AlarmDescription": "CPU usage exceeds 70 percent",
            "StateReasonData": "{\"version\":\"1.0\",\"queryDate\":
\"2014-04-09T18:59:06.419+0000\",\"startDate\":\"2014-04-09T18:44:00.000+0000\",
\"statistic\":\"Average\",\"period\":300,\"recentDatapoints\":[38.958,40.292],
\"threshold\":70.0}",
            "Period": 300,
            "StateValue": "OK",
            "Threshold": 70.0,
            "AlarmName": "myalarm",
            "Dimensions": [
                {
                    "Name": "InstanceId",
                    "Value": "i-0c986c72"
                }
            ],
            "Statistic": "Average",
```

```
            "StateReason": "Threshold Crossed: 2 datapoints were not greater than
 the threshold (70.0). The most recent datapoints: [38.958, 40.292].",
            "InsufficientDataActions": [],
            "OKActions": [],
            "ActionsEnabled": true,
            "MetricName": "CPUUtilization"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAlarmsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeAlarms(CloudWatchClient cw) {
        try {
            List<AlarmType> typeList = new ArrayList<>();
            typeList.add(AlarmType.METRIC_ALARM);

            DescribeAlarmsRequest alarmsRequest = DescribeAlarmsRequest.builder()
                    .alarmTypes(typeList)
                    .maxRecords(10)
                    .build();

            DescribeAlarmsResponse response = cw.describeAlarms(alarmsRequest);
            List<MetricAlarm> alarmList = response.metricAlarms();
            for (MetricAlarm alarm : alarmList) {
                System.out.println("Alarm name: " + alarm.alarmName());
                System.out.println("Alarm description: " +
 alarm.alarmDescription());
            }
        } catch (CloudWatchException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAlarms() {
    val typeList = ArrayList<AlarmType>()
    typeList.add(AlarmType.MetricAlarm)
    val alarmsRequest = DescribeAlarmsRequest {
        alarmTypes = typeList
        maxRecords = 10
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarms(alarmsRequest)
        response.metricAlarms?.forEach { alarm ->
            println("Alarm name: ${alarm.alarmName}")
            println("Alarm description: ${alarm.alarmDescription}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmsreferência da API AWSSDK for Kotlin.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudwatch"

# Lists the names of available Amazon CloudWatch alarms.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @example
#   list_alarms(Aws::CloudWatch::Client.new(region: 'us-east-1'))
def list_alarms(cloudwatch_client)
  response = cloudwatch_client.describe_alarms
  if response.metric_alarms.count.positive?
    response.metric_alarms.each do |alarm|
      puts alarm.alarm_name
    end
  else
    puts "No alarms found."
  end
rescue StandardError => e
  puts "Error getting information about alarms: #{e.message}"
end
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_cwt->describealarms(                " oo_result is
 returned for testing purposes. "
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarms retrieved.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAlarmsreferência da API AWS SDK for SAP ABAP.

Descrever CloudWatch os alarmes para uma métrica usando um SDK AWS

Os exemplos de código a seguir mostram como descrever os CloudWatch alarmes da Amazon para uma métrica.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the current alarms for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarmsForMetric(string
metricNamespace, string metricName)
    {
        var alarmsResult = await _amazonCloudWatch.DescribeAlarmsForMetricAsync(
            new DescribeAlarmsForMetricRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName
            });

        return alarmsResult.MetricAlarms;
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DescribeAlarmsRequest.h>
#include <aws/monitoring/model/DescribeAlarmsResult.h>
#include <iomanip>
#include <iostream>
```

Descreva os alarmes.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DescribeAlarmsRequest request;
        request.SetMaxRecords(1);

        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.DescribeAlarms(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to describe CloudWatch alarms:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left <<
                    std::setw(32) << "Name" <<
```

```
                    std::setw(64) << "Arn" <<
                    std::setw(64) << "Description" <<
                    std::setw(20) << "LastUpdated" <<
                    std::endl;
                header = true;
            }

            const auto &alarms = outcome.GetResult().GetMetricAlarms();
            for (const auto &alarm : alarms)
            {
                std::cout << std::left <<
                    std::setw(32) << alarm.GetAlarmName() <<
                    std::setw(64) << alarm.GetAlarmArn() <<
                    std::setw(64) << alarm.GetAlarmDescription() <<
                    std::setw(20) <<
                    alarm.GetAlarmConfigurationUpdatedTimestamp().ToGmtString(
                        SIMPLE_DATE_FORMAT_STR) <<
                    std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Como exibir informações sobre os alarmes associados a uma métrica

O seguinte exemplo usa o comando `describe-alarms-for-metric` para exibir informações sobre quaisquer alarmes associados à métrica CPUUtilization do Amazon EC2 e à instância com o ID i-0c986c72.:

```
aws cloudwatch describe-alarms-for-metric --metric-name CPUUtilization --
namespace AWS/EC2 --dimensions Name=InstanceId,Value=i-0c986c72
```

Saída:

```
{
    "MetricAlarms": [
        {
            "EvaluationPeriods": 10,
            "AlarmArn": "arn:aws:cloudwatch:us-
east-1:111122223333:alarm:myHighCpuAlarm2",
            "StateUpdatedTimestamp": "2013-10-30T03:03:51.479Z",
            "AlarmConfigurationUpdatedTimestamp": "2013-10-30T03:03:50.865Z",
            "ComparisonOperator": "GreaterThanOrEqualToThreshold",
            "AlarmActions": [
                "arn:aws:sns:us-east-1:111122223333:NotifyMe"
            ],
            "Namespace": "AWS/EC2",
            "AlarmDescription": "CPU usage exceeds 70 percent",
            "StateReasonData": "{\"version\":\"1.0\",\"queryDate\":
\"2013-10-30T03:03:51.479+0000\",\"startDate\":\"2013-10-30T02:08:00.000+0000\",
\"statistic\":\"Average\",\"period\":300,\"recentDatapoints\":
[40.698,39.612,42.432,39.796,38.816,42.28,42.854,40.088,40.760000000000005,41.316],
\"threshold\":70.0}",
            "Period": 300,
            "StateValue": "OK",
            "Threshold": 70.0,
            "AlarmName": "myHighCpuAlarm2",
            "Dimensions": [
                {
                    "Name": "InstanceId",
                    "Value": "i-0c986c72"
                }
            ],
            "Statistic": "Average",
            "StateReason": "Threshold Crossed: 10 datapoints were not
 greater than or equal to the threshold (70.0). The most recent datapoints:
 [40.760000000000005, 41.316].",
            "InsufficientDataActions": [],
            "OKActions": [],
            "ActionsEnabled": true,
            "MetricName": "CPUUtilization"
        },
        {
            "EvaluationPeriods": 2,
            "AlarmArn": "arn:aws:cloudwatch:us-
east-1:111122223333:alarm:myHighCpuAlarm",
```

```
            "StateUpdatedTimestamp": "2014-04-09T18:59:06.442Z",
            "AlarmConfigurationUpdatedTimestamp": "2014-04-09T22:26:05.958Z",
            "ComparisonOperator": "GreaterThanThreshold",
            "AlarmActions": [
                "arn:aws:sns:us-east-1:111122223333:HighCPUAlarm"
            ],
            "Namespace": "AWS/EC2",
            "AlarmDescription": "CPU usage exceeds 70 percent",
            "StateReasonData": "{\"version\":\"1.0\",\"queryDate\":
\"2014-04-09T18:59:06.419+0000\",\"startDate\":\"2014-04-09T18:44:00.000+0000\",
\"statistic\":\"Average\",\"period\":300,\"recentDatapoints\":[38.958,40.292],
\"threshold\":70.0}",
            "Period": 300,
            "StateValue": "OK",
            "Threshold": 70.0,
            "AlarmName": "myHighCpuAlarm",
            "Dimensions": [
                {
                    "Name": "InstanceId",
                    "Value": "i-0c986c72"
                }
            ],
            "Statistic": "Average",
            "StateReason": "Threshold Crossed: 2 datapoints were not greater than
 the threshold (70.0). The most recent datapoints: [38.958, 40.292].",
            "InsufficientDataActions": [],
            "OKActions": [],
            "ActionsEnabled": false,
            "MetricName": "CPUUtilization"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetricem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkForMetricAlarm(CloudWatchClient cw, String fileName)
{
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();
           boolean hasAlarm = false;
           int retries = 10;

           DescribeAlarmsForMetricRequest metricRequest =
DescribeAlarmsForMetricRequest.builder()
                   .metricName(customMetricName)
                   .namespace(customMetricNamespace)
                   .build();

           while (!hasAlarm && retries > 0) {
               DescribeAlarmsForMetricResponse response =
cw.describeAlarmsForMetric(metricRequest);
               hasAlarm = response.hasMetricAlarms();
               retries--;
               Thread.sleep(20000);
               System.out.println(".");
           }
           if (!hasAlarm)
               System.out.println("No Alarm state found for " + customMetricName
+ " after 10 retries.");
```

```
            else
                System.out.println("Alarm state found for " + customMetricName +
 ".");

        } catch (CloudWatchException | IOException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DescribeAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DescribeAlarmsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.describeAlarms({ StateValue: "INSUFFICIENT_DATA" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    // List the names of all current alarms in the console
    data.MetricAlarms.forEach(function (item, index, array) {
      console.log(item.AlarmName);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkForMetricAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    var hasAlarm = false
    var retries = 10

    val metricRequest = DescribeAlarmsForMetricRequest {
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        while (!hasAlarm && retries > 0) {
            val response = cwClient.describeAlarmsForMetric(metricRequest)
            if (response.metricAlarms?.count()!! > 0) {
                hasAlarm = true
            }
            retries--
            delay(20000)
            println(".")
        }
```

```
        if (!hasAlarm) println("No Alarm state found for $customMetricName after
 10 retries.") else println("Alarm state found for $customMetricName.")
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmsForMetricreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def get_metric_alarms(self, metric_namespace, metric_name):
        """
        Gets the alarms that are currently watching the specified metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :returns: An iterator that yields the alarms.
        """
        metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
        alarm_iter = metric.alarms.all()
        logger.info("Got alarms for metric %s.%s.", metric_namespace,
 metric_name)
```

```
        return alarm_iter
```

- Para obter detalhes da API, consulte a DescribeAlarmsForMetricReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @example
#   describe_metric_alarms(Aws::CloudWatch::Client.new(region: 'us-east-1'))
def describe_metric_alarms(cloudwatch_client)
  response = cloudwatch_client.describe_alarms

  if response.metric_alarms.count.positive?
    response.metric_alarms.each do |alarm|
      puts "-" * 16
      puts "Name:           " + alarm.alarm_name
      puts "State value:    " + alarm.state_value
      puts "State reason:   " + alarm.state_reason
      puts "Metric:         " + alarm.metric_name
      puts "Namespace:      " + alarm.namespace
      puts "Statistic:      " + alarm.statistic
      puts "Period:         " + alarm.period.to_s
      puts "Unit:           " + alarm.unit.to_s
      puts "Eval. periods:  " + alarm.evaluation_periods.to_s
      puts "Threshold:      " + alarm.threshold.to_s
      puts "Comp. operator: " + alarm.comparison_operator
```

```
      if alarm.key?(:ok_actions) && alarm.ok_actions.count.positive?
        puts "OK actions:"
        alarm.ok_actions.each do |a|
          puts "  " + a
        end
      end

      if alarm.key?(:alarm_actions) && alarm.alarm_actions.count.positive?
        puts "Alarm actions:"
        alarm.alarm_actions.each do |a|
          puts "  " + a
        end
      end

      if alarm.key?(:insufficient_data_actions) &&
          alarm.insufficient_data_actions.count.positive?
        puts "Insufficient data actions:"
        alarm.insufficient_data_actions.each do |a|
          puts "  " + a
        end
      end

      puts "Dimensions:"
      if alarm.key?(:dimensions) && alarm.dimensions.count.positive?
        alarm.dimensions.each do |d|
          puts "  Name: " + d.name + ", Value: " + d.value
        end
      else
        puts "  None for this alarm."
      end
    end
  else
    puts "No alarms found."
  end
rescue StandardError => e
  puts "Error getting information about alarms: #{e.message}"
end

# Example usage:
def run_me
  region = ""

  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
```

```
    puts "Usage:   ruby cw-ruby-example-show-alarms.rb REGION"
    puts "Example: ruby cw-ruby-example-show-alarms.rb us-east-1"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    region = "us-east-1"
  # Otherwise, use the values as specified at the command prompt.
  else
    region = ARGV[0]
  end

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)
  puts "Available alarms:"
  describe_metric_alarms(cloudwatch_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for Ruby da API.

Descreva os detectores de CloudWatch anomalias usando um SDK AWS

Os exemplos de código a seguir mostram como descrever os detectores de CloudWatch anomalias da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe anomaly detectors for a metric and namespace.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The metric of the anomaly detectors.</param>
    /// <returns>The list of detectors.</returns>
    public async Task<List<AnomalyDetector>> DescribeAnomalyDetectors(string
metricNamespace, string metricName)
    {
        List<AnomalyDetector> detectors = new List<AnomalyDetector>();
        var paginatedDescribeAnomalyDetectors =
_amazonCloudWatch.Paginators.DescribeAnomalyDetectors(
            new DescribeAnomalyDetectorsRequest()
            {
                MetricName = metricName,
                Namespace = metricNamespace
            });

        await foreach (var data in
paginatedDescribeAnomalyDetectors.AnomalyDetectors)
        {
            detectors.Add(data);
        }

        return detectors;
    }
```

- Para obter detalhes da API, consulte DescribeAnomalyDetectorsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeAnomalyDetectors(CloudWatchClient cw, String
fileName) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();
           DescribeAnomalyDetectorsRequest detectorsRequest =
DescribeAnomalyDetectorsRequest.builder()
                   .maxResults(10)
                   .metricName(customMetricName)
                   .namespace(customMetricNamespace)
                   .build();

           DescribeAnomalyDetectorsResponse response =
cw.describeAnomalyDetectors(detectorsRequest);
           List<AnomalyDetector> anomalyDetectorList =
response.anomalyDetectors();
           for (AnomalyDetector detector : anomalyDetectorList) {
               System.out.println("Metric name: " +
detector.singleMetricAnomalyDetector().metricName());
               System.out.println("State: " + detector.stateValue());
           }

       } catch (CloudWatchException | IOException e) {
           System.err.println(e.getMessage());
           System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte DescribeAnomalyDetectorsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAnomalyDetectors(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val detectorsRequest = DescribeAnomalyDetectorsRequest {
        maxResults = 10
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAnomalyDetectors(detectorsRequest)
        response.anomalyDetectors?.forEach { detector ->
            println("Metric name:
 ${detector.singleMetricAnomalyDetector?.metricName}")
            println("State: ${detector.stateValue}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAnomalyDetectorsreferência da API AWSSDK for Kotlin.

Desative as ações de CloudWatch alarme usando um AWS SDK

Os exemplos de código a seguir mostram como desativar as ações de CloudWatch alarme da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Disable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DisableAlarmActions(List<string> alarmNames)
    {
        var disableAlarmActionsResult = await
_amazonCloudWatch.DisableAlarmActionsAsync(
            new DisableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return disableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DisableAlarmActionsRequest.h>
#include <iostream>
```

Desabilite as ações de alarme.

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::DisableAlarmActionsRequest
 disableAlarmActionsRequest;
        disableAlarmActionsRequest.AddAlarmNames(alarm_name);

        auto disableAlarmActionsOutcome =
 cw.DisableAlarmActions(disableAlarmActionsRequest);
        if (!disableAlarmActionsOutcome.IsSuccess())
        {
            std::cout << "Failed to disable actions for alarm " << alarm_name <<
                ": " << disableAlarmActionsOutcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
```

```
            std::cout << "Successfully disabled actions for alarm " <<
                alarm_name << std::endl;
        }
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como desabilitar ações para um alarme

O seguinte exemplo usa o comando `disable-alarm-actions` para desabilitar todas as ações para o alarme denominado “myalarm”:

```
aws cloudwatch disable-alarm-actions --alarm-names myalarm
```

Esse comando retornará à solicitação, se houver êxito.

- Para obter detalhes da API, consulte DisableAlarmActionsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import
 software.amazon.awssdk.services.cloudwatch.model.DisableAlarmActionsRequest;

/**
```

```
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DisableAlarmActions {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <alarmName>

                Where:
                  alarmName - An alarm name to disable (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarmName = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        disableActions(cw, alarmName);
        cw.close();
    }

    public static void disableActions(CloudWatchClient cw, String alarmName) {
        try {
            DisableAlarmActionsRequest request =
 DisableAlarmActionsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.disableAlarmActions(request);
            System.out.printf("Successfully disabled actions on alarm %s",
 alarmName);
```

```
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DisableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DisableAlarmActionsCommand({
    AlarmNames: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.disableAlarmActions(
  { AlarmNames: ["Web_Server_CPU_Utilization"] },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
```

```
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableActions(alarmName: String) {

    val request = DisableAlarmActionsRequest {
        alarmNames = listOf(alarmName)
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.disableAlarmActions(request)
        println("Successfully disabled actions on alarm $alarmName")
    }
}
```

- Para obter detalhes da API, consulte a DisableAlarmActionsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def enable_alarm_actions(self, alarm_name, enable):
        """
        Enables or disables actions on the specified alarm. Alarm actions can be
        used to send notifications or automate responses when an alarm enters a
        particular state.

        :param alarm_name: The name of the alarm.
        :param enable: When True, actions are enabled for the alarm. Otherwise,
 they
                       disabled.
        """
        try:
            alarm = self.cloudwatch_resource.Alarm(alarm_name)
            if enable:
                alarm.enable_actions()
            else:
                alarm.disable_actions()
            logger.info(
                "%s actions for alarm %s.",
                "Enabled" if enable else "Disabled",
                alarm_name,
            )
```

```
        except ClientError:
            logger.exception(
                "Couldn't %s actions alarm %s.",
                "enable" if enable else "disable",
                alarm_name,
            )
            raise
```

- Para obter detalhes da API, consulte a DisableAlarmActionsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Disables an alarm in Amazon CloudWatch.
#
# Prerequisites.
#
# - The alarm to disable.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param alarm_name [String] The name of the alarm to disable.
# @return [Boolean] true if the alarm was disabled; otherwise, false.
# @example
#   exit 1 unless alarm_actions_disabled?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'ObjectsInBucket'
#   )
def alarm_actions_disabled?(cloudwatch_client, alarm_name)
  cloudwatch_client.disable_alarm_actions(alarm_names: [alarm_name])
  return true
```

```
rescue StandardError => e
  puts "Error disabling alarm actions: #{e.message}"
  return false
end

# Example usage:
def run_me
  alarm_name = "ObjectsInBucket"
  alarm_description = "Objects exist in this bucket for more than 1 day."
  metric_name = "NumberOfObjects"
  # Notify this Amazon Simple Notification Service (Amazon SNS) topic when
  # the alarm transitions to the ALARM state.
  alarm_actions = ["arn:aws:sns:us-
east-1:111111111111:Default_CloudWatch_Alarms_Topic"]
  namespace = "AWS/S3"
  statistic = "Average"
  dimensions = [
    {
      name: "BucketName",
      value: "doc-example-bucket"
    },
    {
      name: "StorageType",
      value: "AllStorageTypes"
    }
  ]
  period = 86_400 # Daily (24 hours * 60 minutes * 60 seconds = 86400 seconds).
  unit = "Count"
  evaluation_periods = 1 # More than one day.
  threshold = 1 # One object.
  comparison_operator = "GreaterThanThreshold" # More than one object.
  # Replace us-west-2 with the AWS Region you're using for Amazon CloudWatch.
  region = "us-east-1"

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)

  if alarm_created_or_updated?(
    cloudwatch_client,
    alarm_name,
    alarm_description,
    metric_name,
    alarm_actions,
    namespace,
    statistic,
```

```
    dimensions,
    period,
    unit,
    evaluation_periods,
    threshold,
    comparison_operator
  )
    puts "Alarm '#{alarm_name}' created or updated."
  else
    puts "Could not create or update alarm '#{alarm_name}'."
  end

  if alarm_actions_disabled?(cloudwatch_client, alarm_name)
    puts "Alarm '#{alarm_name}' disabled."
  else
    puts "Could not disable alarm '#{alarm_name}'."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Disables actions on the specified alarm. "
    TRY.
        lo_cwt->disablealarmactions(
          it_alarmnames = it_alarm_names
        ).
```

```
        MESSAGE 'Alarm actions disabled.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DisableAlarmActionsreferência da API AWS SDK for SAP ABAP.

Ativar ações de CloudWatch alarme usando um AWS SDK

Os exemplos de código a seguir mostram como ativar as ações de CloudWatch alarme da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Enable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableAlarmActions(List<string> alarmNames)
    {
        var enableAlarmActionsResult = await
_amazonCloudWatch.EnableAlarmActionsAsync(
            new EnableAlarmActionsRequest()
```

```
            {
                AlarmNames = alarmNames
            });

        return enableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/EnableAlarmActionsRequest.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Habilite as ações de alarme.

```
    Aws::CloudWatch::CloudWatchClient cw;
    Aws::CloudWatch::Model::PutMetricAlarmRequest request;
    request.SetAlarmName(alarm_name);
    request.SetComparisonOperator(
        Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
    request.SetEvaluationPeriods(1);
    request.SetMetricName("CPUUtilization");
    request.SetNamespace("AWS/EC2");
    request.SetPeriod(60);
```

```
    request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
    request.SetThreshold(70.0);
    request.SetActionsEnabled(false);
    request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
    request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);
    request.AddAlarmActions(actionArn);

    Aws::CloudWatch::Model::Dimension dimension;
    dimension.SetName("InstanceId");
    dimension.SetValue(instanceId);
    request.AddDimensions(dimension);

    auto outcome = cw.PutMetricAlarm(request);
    if (!outcome.IsSuccess())
    {
        std::cout << "Failed to create CloudWatch alarm:" <<
            outcome.GetError().GetMessage() << std::endl;
        return;
    }

    Aws::CloudWatch::Model::EnableAlarmActionsRequest enable_request;
    enable_request.AddAlarmNames(alarm_name);

    auto enable_outcome = cw.EnableAlarmActions(enable_request);
    if (!enable_outcome.IsSuccess())
    {
        std::cout << "Failed to enable alarm actions:" <<
            enable_outcome.GetError().GetMessage() << std::endl;
        return;
    }

    std::cout << "Successfully created alarm " << alarm_name <<
        " and enabled actions on it." << std::endl;
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como habilitar todas as ações para um alarme

O seguinte exemplo usa o comando `enable-alarm-actions` para habilitar todas as ações para o alarme denominado “myalarm”:

```
aws cloudwatch enable-alarm-actions --alarm-names myalarm
```

Esse comando retornará à solicitação, se houver êxito.

- Para obter detalhes da API, consulte EnableAlarmActionsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import
 software.amazon.awssdk.services.cloudwatch.model.EnableAlarmActionsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class EnableAlarmActions {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <alarmName>
```

```
                Where:
                  alarmName - An alarm name to enable (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarm = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        enableActions(cw, alarm);
        cw.close();
    }

    public static void enableActions(CloudWatchClient cw, String alarm) {
        try {
            EnableAlarmActionsRequest request =
 EnableAlarmActionsRequest.builder()
                    .alarmNames(alarm)
                    .build();

            cw.enableAlarmActions(request);
            System.out.printf("Successfully enabled actions on alarm %s", alarm);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EnableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new EnableAlarmActionsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: true,
  AlarmActions: ["ACTION_ARN"],
  AlarmDescription: "Alarm when server CPU exceeds 70%",
  Dimensions: [
    {
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
};

cw.putMetricAlarm(params, function (err, data) {
```

```
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Alarm action added", data);
    var paramsEnableAlarmAction = {
      AlarmNames: [params.AlarmName],
    };
    cw.enableAlarmActions(paramsEnableAlarmAction, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Alarm action enabled", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableActions(alarm: String) {

    val request = EnableAlarmActionsRequest {
        alarmNames = listOf(alarm)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.enableAlarmActions(request)
```

```
        println("Successfully enabled actions on alarm $alarm")
    }
}
```

- Para obter detalhes da API, consulte a EnableAlarmActionsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def enable_alarm_actions(self, alarm_name, enable):
        """
        Enables or disables actions on the specified alarm. Alarm actions can be
        used to send notifications or automate responses when an alarm enters a
        particular state.

        :param alarm_name: The name of the alarm.
        :param enable: When True, actions are enabled for the alarm. Otherwise,
 they
                       disabled.
        """
        try:
            alarm = self.cloudwatch_resource.Alarm(alarm_name)
```

```
            if enable:
                alarm.enable_actions()
            else:
                alarm.disable_actions()
            logger.info(
                "%s actions for alarm %s.",
                "Enabled" if enable else "Disabled",
                alarm_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't %s actions alarm %s.",
                "enable" if enable else "disable",
                alarm_name,
            )
            raise
```

- Para obter detalhes da API, consulte a EnableAlarmActionsReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Enable actions on the specified alarm."
    TRY.
        lo_cwt->enablealarmactions(
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarm actions enabled.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
```

```
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a EnableAlarmActionsreferência da API AWS SDK for SAP ABAP.

Obtenha uma imagem de dados CloudWatch métricos

Os exemplos de código a seguir mostram como obter uma imagem de dados CloudWatch métricos da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get an image for a metric graphed over time.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metric">The name of the metric.</param>
    /// <param name="stat">The name of the stat to chart.</param>
    /// <param name="period">The period to use for the chart.</param>
    /// <returns>A memory stream for the chart image.</returns>
    public async Task<MemoryStream> GetTimeSeriesMetricImage(string
metricNamespace, string metric, string stat, int period)
    {
```

```
        var metricImageWidget = new
        {
            title = "Example Metric Graph",
            view = "timeSeries",
            stacked = false,
            period = period,
            width = 1400,
            height = 600,
            metrics = new List<List<object>>
                { new() { metricNamespace, metric, new { stat } } }
        };

        var metricImageWidgetString =
JsonSerializer.Serialize(metricImageWidget);
        var imageResponse = await _amazonCloudWatch.GetMetricWidgetImageAsync(
            new GetMetricWidgetImageRequest()
            {
                MetricWidget = metricImageWidgetString
            });

        return imageResponse.MetricWidgetImage;
    }

    /// <summary>
    /// Save a metric image to a file.
    /// </summary>
    /// <param name="memoryStream">The MemoryStream for the metric image.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The path to the file.</returns>
    public string SaveMetricImage(MemoryStream memoryStream, string metricName)
    {
        var metricFileName = $"{metricName}_{DateTime.Now.Ticks}.png";
        using var sr = new StreamReader(memoryStream);
        // Writes the memory stream to a file.
        File.WriteAllBytes(metricFileName, memoryStream.ToArray());
        var filePath = Path.Join(AppDomain.CurrentDomain.BaseDirectory,
            metricFileName);
        return filePath;
    }
```

- Para obter detalhes da API, consulte GetMetricWidgetImagea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAndOpenMetricImage(CloudWatchClient cw, String
fileName) {
       System.out.println("Getting Image data for custom metric.");
       try {
           String myJSON = "{\n" +
                   "  \"title\": \"Example Metric Graph\",\n" +
                   "  \"view\": \"timeSeries\",\n" +
                   "  \"stacked \": false,\n" +
                   "  \"period\": 10,\n" +
                   "  \"width\": 1400,\n" +
                   "  \"height\": 600,\n" +
                   "  \"metrics\": [\n" +
                   "    [\n" +
                   "      \"AWS/Billing\",\n" +
                   "      \"EstimatedCharges\",\n" +
                   "      \"Currency\",\n" +
                   "      \"USD\"\n" +
                   "    ]\n" +
                   "  ]\n" +
                   "}";

           GetMetricWidgetImageRequest imageRequest =
GetMetricWidgetImageRequest.builder()
                   .metricWidget(myJSON)
                   .build();

           GetMetricWidgetImageResponse response =
cw.getMetricWidgetImage(imageRequest);
           SdkBytes sdkBytes = response.metricWidgetImage();
           byte[] bytes = sdkBytes.asByteArray();
           File outputFile = new File(fileName);
```

```
            try (FileOutputStream outputStream = new
 FileOutputStream(outputFile)) {
                outputStream.write(bytes);
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetMetricWidgetImagea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAndOpenMetricImage(fileName: String) {
    println("Getting Image data for custom metric.")
    val myJSON = """{
        "title": "Example Metric Graph",
        "view": "timeSeries",
        "stacked ": false,
        "period": 10,
        "width": 1400,
        "height": 600,
        "metrics": [
            [
            "AWS/Billing",
            "EstimatedCharges",
            "Currency",
            "USD"
            ]
```

```
        ]
        }"""

    val imageRequest = GetMetricWidgetImageRequest {
        metricWidget = myJSON
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricWidgetImage(imageRequest)
        val bytes = response.metricWidgetImage
        if (bytes != null) {
            File(fileName).writeBytes(bytes)
        }
    }
    println("You have successfully written data to $fileName")
}
```

- Para obter detalhes da API, consulte a GetMetricWidgetImagereferência da API AWSSDK for Kotlin.

Obtenha os detalhes de um CloudWatch painel

O exemplo de código a seguir mostra como obter detalhes CloudWatch do painel da Amazon.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information on a dashboard.
    /// </summary>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A JSON object with dashboard information.</returns>
    public async Task<string> GetDashboard(string dashboardName)
```

```
    {
        var dashboardResponse = await _amazonCloudWatch.GetDashboardAsync(
            new GetDashboardRequest()
            {
                DashboardName = dashboardName
            });

        return dashboardResponse.DashboardBody;
    }
```

- Para obter detalhes da API, consulte GetDashboarda Referência AWS SDK for .NET da API.

Obtenha valores de dados CloudWatch métricos

Os exemplos de código a seguir mostram como obter dados CloudWatch métricos da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar métricas, painéis e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get data for CloudWatch metrics.
    /// </summary>
    /// <param name="minutesOfData">The number of minutes of data to include.</
param>
```

```
    /// <param name="useDescendingTime">True to return the data descending by
 time.</param>
    /// <param name="endDateUtc">The end date for the data, in UTC.</param>
    /// <param name="maxDataPoints">The maximum data points to include.</param>
    /// <param name="dataQueries">Optional data queries to include.</param>
    /// <returns>A list of the requested metric data.</returns>
    public async Task<List<MetricDataResult>> GetMetricData(int minutesOfData,
 bool useDescendingTime, DateTime? endDateUtc = null,
        int maxDataPoints = 0, List<MetricDataQuery>? dataQueries = null)
    {
        var metricData = new List<MetricDataResult>();
        // If no end time is provided, use the current time for the end time.
        endDateUtc ??= DateTime.UtcNow;
        var timeZoneOffset =
 TimeZoneInfo.Local.GetUtcOffset(endDateUtc.Value.ToLocalTime());
        var startTimeUtc = endDateUtc.Value.AddMinutes(-minutesOfData);
        // The timezone string should be in the format +0000, so use the timezone
 offset to format it correctly.
        var timeZoneString = $"{timeZoneOffset.Hours:D2}
{timeZoneOffset.Minutes:D2}";
        var paginatedMetricData = _amazonCloudWatch.Paginators.GetMetricData(
            new GetMetricDataRequest()
            {
                StartTimeUtc = startTimeUtc,
                EndTimeUtc = endDateUtc.Value,
                LabelOptions = new LabelOptions { Timezone = timeZoneString },
                ScanBy = useDescendingTime ? ScanBy.TimestampDescending :
 ScanBy.TimestampAscending,
                MaxDatapoints = maxDataPoints,
                MetricDataQueries = dataQueries,
            });

        await foreach (var data in paginatedMetricData.MetricDataResults)
        {
            metricData.Add(data);
        }
        return metricData;
    }
```

- Para obter detalhes da API, consulte GetMetricDataa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getCustomMetricData(CloudWatchClient cw, String fileName)
{
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();

           // Set the date.
           Instant nowDate = Instant.now();

           long hours = 1;
           long minutes = 30;
           Instant date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(minutes,
                   ChronoUnit.MINUTES);

           Metric met = Metric.builder()
                   .metricName(customMetricName)
                   .namespace(customMetricNamespace)
                   .build();

           MetricStat metStat = MetricStat.builder()
                   .stat("Maximum")
                   .period(1)
                   .metric(met)
                   .build();
```

```
            MetricDataQuery dataQUery = MetricDataQuery.builder()
                    .metricStat(metStat)
                    .id("foo2")
                    .returnData(true)
                    .build();

            List<MetricDataQuery> dq = new ArrayList<>();
            dq.add(dataQUery);

            GetMetricDataRequest getMetReq = GetMetricDataRequest.builder()
                    .maxDatapoints(10)
                    .scanBy(ScanBy.TIMESTAMP_DESCENDING)
                    .startTime(nowDate)
                    .endTime(date2)
                    .metricDataQueries(dq)
                    .build();

            GetMetricDataResponse response = cw.getMetricData(getMetReq);
            List<MetricDataResult> data = response.metricDataResults();
            for (MetricDataResult item : data) {
                System.out.println("The label is " + item.label());
                System.out.println("The status code is " +
item.statusCode().toString());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetMetricDataa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getCustomMetricData(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set the date.
    val nowDate = Instant.now()
    val hours: Long = 1
    val minutes: Long = 30
    val date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(
        minutes,
        ChronoUnit.MINUTES
    )

    val met = Metric {
        metricName = customMetricName
        namespace = customMetricNamespace
    }

    val metStat = MetricStat {
        stat = "Maximum"
        period = 1
        metric = met
    }

    val dataQUery = MetricDataQuery {
        metricStat = metStat
        id = "foo2"
        returnData = true
```

```
    }

    val dq = ArrayList<MetricDataQuery>()
    dq.add(dataQUery)
    val getMetReq = GetMetricDataRequest {
        maxDatapoints = 10
        scanBy = ScanBy.TimestampDescending
        startTime = aws.smithy.kotlin.runtime.time.Instant(nowDate)
        endTime = aws.smithy.kotlin.runtime.time.Instant(date2)
        metricDataQueries = dq
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricData(getMetReq)
        response.metricDataResults?.forEach { item ->
            println("The label is ${item.label}")
            println("The status code is ${item.statusCode}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetMetricDatareferência da API AWSSDK for Kotlin.

Obtenha estatísticas CloudWatch métricas usando um AWS SDK

Os exemplos de código a seguir mostram como obter estatísticas CloudWatch métricas da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get billing statistics using a call to a wrapper class.
    /// </summary>
    /// <returns>A collection of billing statistics.</returns>
    private static async Task<List<Datapoint>> SetupBillingStatistics()
    {
        // Make a request for EstimatedCharges with a period of one day for the
past seven days.
        var billingStatistics = await _cloudWatchWrapper.GetMetricStatistics(
            "AWS/Billing",
            "EstimatedCharges",
            new List<string>() { "Maximum" },
            new List<Dimension>() { new Dimension { Name = "Currency", Value =
"USD" } },
            7,
            86400);

        billingStatistics = billingStatistics.OrderBy(n => n.Timestamp).ToList();

        return billingStatistics;
    }

    /// <summary>
    /// Wrapper to get statistics for a specific CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <param name="statistics">The list of statistics to include.</param>
    /// <param name="dimensions">The list of dimensions to include.</param>
    /// <param name="days">The number of days in the past to include.</param>
    /// <param name="period">The period for the data.</param>
    /// <returns>A list of DataPoint objects for the statistics.</returns>
```

```
    public async Task<List<Datapoint>> GetMetricStatistics(string
 metricNamespace,
        string metricName, List<string> statistics, List<Dimension> dimensions,
 int days, int period)
    {
        var metricStatistics = await _amazonCloudWatch.GetMetricStatisticsAsync(
            new GetMetricStatisticsRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName,
                Dimensions = dimensions,
                Statistics = statistics,
                StartTimeUtc = DateTime.UtcNow.AddDays(-days),
                EndTimeUtc = DateTime.UtcNow,
                Period = period
            });

        return metricStatistics.Datapoints;
    }
```

- Para obter detalhes da API, consulte GetMetricStatisticsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como obter a utilização da CPU por instância do EC2

O exemplo apresentado a seguir usa o comando `get-metric-statistics` para obter a utilização da CPU para uma instância do EC2 com o ID i-abcdef.

```
aws cloudwatch get-metric-statistics --metric-name CPUUtilization --start-time
 2014-04-08T23:18:00Z --end-time 2014-04-09T23:18:00Z --period 3600 --namespace
 AWS/EC2 --statistics Maximum --dimensions Name=InstanceId,Value=i-abcdef
```

Saída:

```
{
    "Datapoints": [
        {
```

```
            "Timestamp": "2014-04-09T11:18:00Z",
            "Maximum": 44.79,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T20:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T19:18:00Z",
            "Maximum": 50.85,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T09:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T03:18:00Z",
            "Maximum": 76.84,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T21:18:00Z",
            "Maximum": 48.96,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T14:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T08:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T16:18:00Z",
            "Maximum": 45.55,
            "Unit": "Percent"
        },
```

```
        {
            "Timestamp": "2014-04-09T06:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T13:18:00Z",
            "Maximum": 45.08,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T05:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T18:18:00Z",
            "Maximum": 46.88,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T17:18:00Z",
            "Maximum": 52.08,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T07:18:00Z",
            "Maximum": 47.92,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T02:18:00Z",
            "Maximum": 51.23,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T12:18:00Z",
            "Maximum": 47.67,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-08T23:18:00Z",
            "Maximum": 46.88,
            "Unit": "Percent"
```

```
        },
        {
            "Timestamp": "2014-04-09T10:18:00Z",
            "Maximum": 51.91,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T04:18:00Z",
            "Maximum": 47.13,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T15:18:00Z",
            "Maximum": 48.96,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T00:18:00Z",
            "Maximum": 48.16,
            "Unit": "Percent"
        },
        {
            "Timestamp": "2014-04-09T01:18:00Z",
            "Maximum": 49.18,
            "Unit": "Percent"
        }
    ],
    "Label": "CPUUtilization"
}
```

Especificação para diversas dimensões

O exemplo apresentado a seguir ilustra como especificar diversas dimensões. Cada dimensão é especificada como um par de nome/valor, com uma vírgula entre o nome e o valor. As diversas dimensões são separadas por um espaço. Se uma única métrica incluir diversas dimensões, você deverá especificar um valor para cada dimensão definida.

Para obter mais exemplos de uso do `get-metric-statistics` comando, consulte Obter estatísticas para uma métrica no Amazon CloudWatch Developer Guide.

```
aws cloudwatch get-metric-statistics --metric-name Buffers --
namespace MyNameSpace --dimensions Name=InstanceID,Value=i-abcdef
```

```
Name=InstanceType,Value=m1.small --start-time 2016-10-15T04:00:00Z --end-time
2016-10-19T07:00:00Z --statistics Average --period 60
```

- Para obter detalhes da API, consulte GetMetricStatisticsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAndDisplayMetricStatistics(CloudWatchClient cw, String
nameSpace, String metVal,
           String metricOption, String date, Dimension myDimension) {
       try {
           Instant start = Instant.parse(date);
           Instant endDate = Instant.now();

           GetMetricStatisticsRequest statisticsRequest =
GetMetricStatisticsRequest.builder()
                   .endTime(endDate)
                   .startTime(start)
                   .dimensions(myDimension)
                   .metricName(metVal)
                   .namespace(nameSpace)
                   .period(86400)
                   .statistics(Statistic.fromValue(metricOption))
                   .build();

           GetMetricStatisticsResponse response =
cw.getMetricStatistics(statisticsRequest);
           List<Datapoint> data = response.datapoints();
           if (!data.isEmpty()) {
               for (Datapoint datapoint : data) {
                   System.out
```

```
                            .println("Timestamp: " + datapoint.timestamp() + "
 Maximum value: " + datapoint.maximum());
                }
            } else {
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetMetricStatisticsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAndDisplayMetricStatistics(nameSpaceVal: String, metVal: String,
 metricOption: String, date: String, myDimension: Dimension) {
    val start = Instant.parse(date)
    val endDate = Instant.now()
    val statisticsRequest = GetMetricStatisticsRequest {
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        dimensions = listOf(myDimension)
        metricName = metVal
        namespace = nameSpaceVal
        period = 86400
        statistics = listOf(Statistic.fromValue(metricOption))
    }
```

```
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data = response.datapoints
        if (data != null) {
            if (data.isNotEmpty()) {
                for (datapoint in data) {
                    println("Timestamp: ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a GetMetricStatisticsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource
```

```
    def get_metric_statistics(self, namespace, name, start, end, period,
stat_types):
        """
        Gets statistics for a metric within a specified time span. Metrics are
grouped
        into the specified period.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param start: The UTC start time of the time span to retrieve.
        :param end: The UTC end time of the time span to retrieve.
        :param period: The period, in seconds, in which to group metrics. The
period
                       must match the granularity of the metric, which depends on
                       the metric's age. For example, metrics that are older than
                       three hours have a one-minute granularity, so the period
must
                       be at least 60 and must be a multiple of 60.
        :param stat_types: The type of statistics to retrieve, such as average
value
                           or maximum value.
        :return: The retrieved statistics for the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            stats = metric.get_statistics(
                StartTime=start, EndTime=end, Period=period,
Statistics=stat_types
            )
            logger.info(
                "Got %s statistics for %s.", len(stats["Datapoints"]),
stats["Label"]
            )
        except ClientError:
            logger.exception("Couldn't get statistics for %s.%s.", namespace,
name)
            raise
        else:
            return stats
```

- Para obter detalhes da API, consulte a GetMetricStatisticsReferência da API AWSSDK for Python (Boto3).

Listar CloudWatch painéis

Os exemplos de código a seguir mostram como listar os CloudWatch painéis da Amazon.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of dashboards.
/// </summary>
/// <returns>A list of DashboardEntry objects.</returns>
public async Task<List<DashboardEntry>> ListDashboards()
{
    var results = new List<DashboardEntry>();
    var paginateDashboards = _amazonCloudWatch.Paginators.ListDashboards(
        new ListDashboardsRequest());
    // Get the entire list using the paginator.
    await foreach (var data in paginateDashboards.DashboardEntries)
    {
        results.Add(data);
    }

    return results;
}
```

- Para obter detalhes da API, consulte ListDashboardsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listDashboards(CloudWatchClient cw) {
        try {
            ListDashboardsIterable listRes = cw.listDashboardsPaginator();
            listRes.stream()
                    .flatMap(r -> r.dashboardEntries().stream())
                    .forEach(entry -> {
                        System.out.println("Dashboard name is: " +
entry.dashboardName());
                        System.out.println("Dashboard ARN is: " +
entry.dashboardArn());
                    });

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListDashboardsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDashboards() {
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listDashboardsPaginated({})
            .transform { it.dashboardEntries?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name is ${obj.dashboardName}")
                println("Dashboard ARN is ${obj.dashboardArn}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListDashboardsreferência da API AWSSDK for Kotlin.

Listar CloudWatch métricas usando um AWS SDK

Os exemplos de código a seguir mostram como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List metrics available, optionally within a namespace.
    /// </summary>
```

```
    /// <param name="metricNamespace">Optional CloudWatch namespace to use when
listing metrics.</param>
    /// <param name="filter">Optional dimension filter.</param>
    /// <param name="metricName">Optional metric name filter.</param>
    /// <returns>The list of metrics.</returns>
    public async Task<List<Metric>> ListMetrics(string? metricNamespace = null,
DimensionFilter? filter = null, string? metricName = null)
    {
        var results = new List<Metric>();
        var paginateMetrics = _amazonCloudWatch.Paginators.ListMetrics(
            new ListMetricsRequest
            {
                Namespace = metricNamespace,
                Dimensions = filter != null ? new List<DimensionFilter>
{ filter } : null,
                MetricName = metricName
            });
        // Get the entire list using the paginator.
        await foreach (var metric in paginateMetrics.Metrics)
        {
            results.Add(metric);
        }

        return results;
    }
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
```

```
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/ListMetricsRequest.h>
#include <aws/monitoring/model/ListMetricsResult.h>
#include <iomanip>
#include <iostream>
```

Liste as métricas.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::ListMetricsRequest request;

        if (argc > 1)
        {
            request.SetMetricName(argv[1]);
        }

        if (argc > 2)
        {
            request.SetNamespace(argv[2]);
        }

        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.ListMetrics(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to list CloudWatch metrics:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left << std::setw(48) << "MetricName" <<
                    std::setw(32) << "Namespace" << "DimensionNameValuePairs" <<
                    std::endl;
                header = true;
            }

            const auto &metrics = outcome.GetResult().GetMetrics();
```

```
            for (const auto &metric : metrics)
            {
                std::cout << std::left << std::setw(48) <<
                    metric.GetMetricName() << std::setw(32) <<
                    metric.GetNamespace();
                const auto &dimensions = metric.GetDimensions();
                for (auto iter = dimensions.cbegin();
                    iter != dimensions.cend(); ++iter)
                {
                    const auto &dimkv = *iter;
                    std::cout << dimkv.GetName() << " = " << dimkv.GetValue();
                    if (iter + 1 != dimensions.cend())
                    {
                        std::cout << ", ";
                    }
                }
                std::cout << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar as métricas do Amazon SNS

O exemplo apresentado a seguir para `list-metrics` exibe as métricas do Amazon SNS.

```
aws cloudwatch list-metrics \
    --namespace "AWS/SNS"
```

Saída:

```
{
    "Metrics": [
        {
```

```
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "NotifyMe"
                }
            ],
            "MetricName": "PublishSize"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "CFO"
                }
            ],
            "MetricName": "PublishSize"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "NotifyMe"
                }
            ],
            "MetricName": "NumberOfNotificationsFailed"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "NotifyMe"
                }
            ],
            "MetricName": "NumberOfNotificationsDelivered"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
```

```
                    "Value": "NotifyMe"
                }
            ],
            "MetricName": "NumberOfMessagesPublished"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "CFO"
                }
            ],
            "MetricName": "NumberOfMessagesPublished"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "CFO"
                }
            ],
            "MetricName": "NumberOfNotificationsDelivered"
        },
        {
            "Namespace": "AWS/SNS",
            "Dimensions": [
                {
                    "Name": "TopicName",
                    "Value": "CFO"
                }
            ],
            "MetricName": "NumberOfNotificationsFailed"
        }
    ]
}
```

- Para obter detalhes da API, consulte ListMetricsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Metric;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListMetrics {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <namespace>\s

                Where:
                  namespace - The namespace to filter against (for example, AWS/
EC2).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String namespace = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        listMets(cw, namespace);
        cw.close();
    }

    public static void listMets(CloudWatchClient cw, String namespace) {
        boolean done = false;
        String nextToken = null;

        try {
            while (!done) {

                ListMetricsResponse response;
                if (nextToken == null) {
                    ListMetricsRequest request = ListMetricsRequest.builder()
                            .namespace(namespace)
                            .build();

                    response = cw.listMetrics(request);
                } else {
                    ListMetricsRequest request = ListMetricsRequest.builder()
                            .namespace(namespace)
                            .nextToken(nextToken)
                            .build();

                    response = cw.listMetrics(request);
                }

                for (Metric metric : response.metrics()) {
                    System.out.printf("Retrieved metric %s",
metric.metricName());
                    System.out.println();
                }

                if (response.nextToken() == null) {
                    done = true;
                } else {
                    nextToken = response.nextToken();
```

```
                }
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListMetricsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

export const main = () => {
  // Use the AWS console to see available namespaces and metric names. Custom
 metrics can also be created.
  // https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
viewing_metrics_with_cloudwatch.html
  const command = new ListMetricsCommand({
    Dimensions: [
      {
        Name: "LogGroupName",
      },
    ],
    MetricName: "IncomingLogEvents",
    Namespace: "AWS/Logs",
  });
```

```
  return client.send(command);
};
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  Dimensions: [
    {
      Name: "LogGroupName" /* required */,
    },
  ],
  MetricName: "IncomingLogEvents",
  Namespace: "AWS/Logs",
};
```

```
cw.listMetrics(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Metrics", JSON.stringify(data.Metrics));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listMets(namespaceVal: String?): ArrayList<String>? {
    val metList = ArrayList<String>()
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val reponse = cwClient.listMetrics(request)
        reponse.metrics?.forEach { metrics ->
            val data = metrics.metricName
            if (!metList.contains(data)) {
                metList.add(data!!)
            }
        }
    }
    return metList
}
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def list_metrics(self, namespace, name, recent=False):
        """
        Gets the metrics within a namespace that have the specified name.
        If the metric has no dimensions, a single metric is returned.
        Otherwise, metrics for all dimensions are returned.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param recent: When True, only metrics that have been active in the last
                       three hours are returned.
        :return: An iterator that yields the retrieved metrics.
        """
        try:
            kwargs = {"Namespace": namespace, "MetricName": name}
            if recent:
                kwargs["RecentlyActive"] = "PT3H"  # List past 3 hours only
            metric_iter = self.cloudwatch_resource.metrics.filter(**kwargs)
            logger.info("Got metrics for %s.%s.", namespace, name)
```

```
        except ClientError:
            logger.exception("Couldn't get metrics for %s.%s.", namespace, name)
            raise
        else:
            return metric_iter
```

- Para obter detalhes da API, consulte a ListMetricsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists available metrics for a metric namespace in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param metric_namespace [String] The namespace of the metric.
# @example
#   list_metrics_for_namespace(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'SITE/TRAFFIC'
#   )
def list_metrics_for_namespace(cloudwatch_client, metric_namespace)
  response = cloudwatch_client.list_metrics(namespace: metric_namespace)

  if response.metrics.count.positive?
    response.metrics.each do |metric|
      puts "  Metric name: #{metric.metric_name}"
      if metric.dimensions.count.positive?
        puts "    Dimensions:"
        metric.dimensions.each do |dimension|
          puts "      Name: #{dimension.name}, Value: #{dimension.value}"
```

```
        end
      else
        puts "No dimensions found."
      end
    end
  else
    puts "No metrics found for namespace '#{metric_namespace}'. " \
      "Note that it could take up to 15 minutes for recently-added metrics " \
      "to become available."
  end
end

# Example usage:
def run_me
  metric_namespace = "SITE/TRAFFIC"
  # Replace us-west-2 with the AWS Region you're using for Amazon CloudWatch.
  region = "us-east-1"

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)

  # Add three datapoints.
  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
    "UniqueVisitors",
    "SiteName",
    "example.com",
    5_885.0,
    "Count"
  )

  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
    "UniqueVisits",
    "SiteName",
    "example.com",
    8_628.0,
    "Count"
  )

  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
```

```
    "PageViews",
    "PageURL",
    "example.html",
    18_057.0,
    "Count"
  )

  puts "Metrics for namespace '#{metric_namespace}':"
  list_metrics_for_namespace(cloudwatch_client, metric_namespace)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "The following list-metrics example displays the metrics for Amazon
CloudWatch."
   TRY.
       oo_result = lo_cwt->listmetrics(            " oo_result is returned for
testing purposes. "
         iv_namespace = iv_namespace
       ).
       DATA(lt_metrics) = oo_result->get_metrics( ).
       MESSAGE 'Metrics retrieved.' TYPE 'I'.
     CATCH /aws1/cx_cwtinvparamvalueex .
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWS SDK for SAP ABAP.

Coloque um conjunto de dados em uma CloudWatch métrica usando um AWS SDK

O exemplo de código a seguir mostra como colocar um conjunto de dados em uma CloudWatch métrica da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

Python

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data_set(self, namespace, name, timestamp, unit, data_set):
        """
        Sends a set of data to CloudWatch for a metric. All of the data in the
 set
        have the same timestamp and unit.
```

```
        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param timestamp: The UTC timestamp for the metric.
        :param unit: The unit of the metric.
        :param data_set: The set of data to send. This set is a dictionary that
                         contains a list of values and a list of corresponding
counts.
                         The value and count lists must be the same length.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[
                    {
                        "MetricName": name,
                        "Timestamp": timestamp,
                        "Values": data_set["values"],
                        "Counts": data_set["counts"],
                        "Unit": unit,
                    }
                ],
            )
            logger.info("Put data set for metric %s.%s.", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data set for metric %s.%s.",
namespace, name)
            raise
```

- Para obter detalhes da API, consulte a PutMetricDataReferência da API AWSSDK for Python (Boto3).

Coloque dados em uma CloudWatch métrica usando um AWS SDK

Os exemplos de código a seguir mostram como publicar pontos de dados métricos na Amazon CloudWatch.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Começar a usar métricas, painéis e alarmes
- Gerencie métricas e alarmes

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add some metric data using a call to a wrapper class.
    /// </summary>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <returns></returns>
    private static async Task<List<MetricDatum>> PutRandomMetricData(string
customMetricName,
        string customMetricNamespace)
    {
        List<MetricDatum> customData = new List<MetricDatum>();
        Random rnd = new Random();

        // Add 10 random values up to 100, starting with a timestamp 15 minutes
in the past.
        var utcNowMinus15 = DateTime.UtcNow.AddMinutes(-15);
        for (int i = 0; i < 10; i++)
        {
            var metricValue = rnd.Next(0, 100);
            customData.Add(
                new MetricDatum
                {
                    MetricName = customMetricName,
                    Value = metricValue,
                    TimestampUtc = utcNowMinus15.AddMinutes(i)
                }
            );
```

```
        }

        await _cloudWatchWrapper.PutMetricData(customMetricNamespace,
customData);
        return customData;
    }

    /// <summary>
    /// Wrapper to add metric data to a CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricData">A data object for the metric data.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricData(string metricNamespace,
        List<MetricDatum> metricData)
    {
        var putDataResponse = await _amazonCloudWatch.PutMetricDataAsync(
            new PutMetricDataRequest()
            {
                MetricData = metricData,
                Namespace = metricNamespace,
            });

        return putDataResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
```

```
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricDataRequest.h>
#include <iostream>
```

Insira dados na métrica.

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("UNIQUE_PAGES");
        dimension.SetValue("URLS");

        Aws::CloudWatch::Model::MetricDatum datum;
        datum.SetMetricName("PAGES_VISITED");
        datum.SetUnit(Aws::CloudWatch::Model::StandardUnit::None);
        datum.SetValue(data_point);
        datum.AddDimensions(dimension);

        Aws::CloudWatch::Model::PutMetricDataRequest request;
        request.SetNamespace("SITE/TRAFFIC");
        request.AddMetricData(datum);

        auto outcome = cw.PutMetricData(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to put sample metric data:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully put sample metric data" << std::endl;
        }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para publicar uma métrica personalizada na Amazon CloudWatch

O exemplo a seguir usa o `put-metric-data` comando para publicar uma métrica personalizada na Amazon CloudWatch:

```
aws cloudwatch put-metric-data --namespace "Usage Metrics" --metric-data file:// metric.json
```

Os valores da própria métrica estão armazenados no arquivo em JSON, `metric.json`.

Veja o conteúdo desse arquivo:

```
[
  {
    "MetricName": "New Posts",
    "Timestamp": "Wednesday, June 12, 2013 8:28:20 PM",
    "Value": 0.50,
    "Unit": "Count"
  }
]
```

Para obter mais informações, consulte Publicação de métricas personalizadas no Amazon CloudWatch Developer Guide.

Como especificar diversas dimensões

O exemplo apresentado a seguir ilustra como especificar diversas dimensões. Cada dimensão é especificada como um par de nome/valor. As diversas dimensões são separadas por uma vírgula.

```
aws cloudwatch put-metric-data --metric-name Buffers --namespace
 MyNameSpace --unit Bytes --value 231434333 --dimensions
 InstanceID=1-23456789,InstanceType=m1.small
```

- Para obter detalhes da API, consulte PutMetricDataem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void addMetricDataForAlarm(CloudWatchClient cw, String
fileName) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new
File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();

           // Set an Instant object.
           String time =
ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
           Instant instant = Instant.parse(time);

           MetricDatum datum = MetricDatum.builder()
                   .metricName(customMetricName)
                   .unit(StandardUnit.NONE)
                   .value(1001.00)
                   .timestamp(instant)
                   .build();

           MetricDatum datum2 = MetricDatum.builder()
                   .metricName(customMetricName)
                   .unit(StandardUnit.NONE)
                   .value(1002.00)
                   .timestamp(instant)
                   .build();
```

```
            List<MetricDatum> metricDataList = new ArrayList<>();
            metricDataList.add(datum);
            metricDataList.add(datum2);

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace(customMetricNamespace)
                    .metricData(metricDataList)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric " +
 customMetricName);

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricDataCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  // See https://docs.aws.amazon.com/AmazonCloudWatch/latest/APIReference/
API_PutMetricData.html#API_PutMetricData_RequestParameters
```

```
  // and https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
publishingMetrics.html
  // for more information about the parameters in this command.
  const command = new PutMetricDataCommand({
    MetricData: [
      {
        MetricName: "PAGES_VISITED",
        Dimensions: [
          {
            Name: "UNIQUE_PAGES",
            Value: "URLS",
          },
        ],
        Unit: "None",
        Value: 1.0,
      },
    ],
    Namespace: "SITE/TRAFFIC",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

// Create parameters JSON for putMetricData
var params = {
  MetricData: [
    {
      MetricName: "PAGES_VISITED",
      Dimensions: [
        {
          Name: "UNIQUE_PAGES",
          Value: "URLS",
        },
      ],
      Unit: "None",
      Value: 1.0,
    },
  ],
  Namespace: "SITE/TRAFFIC",
};

cw.putMetricData(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", JSON.stringify(data));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addMetricDataForAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1001.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val datum2 = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1002.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }
```

```
    val metricDataList = ArrayList<MetricDatum>()
    metricDataList.add(datum)
    metricDataList.add(datum2)

    val request = PutMetricDataRequest {
        namespace = customMetricNamespace
        metricData = metricDataList
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric $customMetricName")
    }
}
```

- Para obter detalhes da API, consulte a PutMetricDatareferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data(self, namespace, name, value, unit):
        """
        Sends a single data value to CloudWatch for a metric. This metric is
 given
```

```
        a timestamp of the current UTC time.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param value: The value of the metric.
        :param unit: The unit of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[{"MetricName": name, "Value": value, "Unit": unit}],
            )
            logger.info("Put data for metric %s.%s", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data for metric %s.%s", namespace,
 name)
            raise
```

- Para obter detalhes da API, consulte a PutMetricDataReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudwatch"

# Adds a datapoint to a metric in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param metric_namespace [String] The namespace of the metric to add the
```

```
#   datapoint to.
# @param metric_name [String] The name of the metric to add the datapoint to.
# @param dimension_name [String] The name of the dimension to add the
#   datapoint to.
# @param dimension_value [String] The value of the dimension to add the
#   datapoint to.
# @param metric_value [Float] The value of the datapoint.
# @param metric_unit [String] The unit of measurement for the datapoint.
# @return [Boolean]
# @example
#   exit 1 unless datapoint_added_to_metric?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'SITE/TRAFFIC',
#     'UniqueVisitors',
#     'SiteName',
#     'example.com',
#     5_885.0,
#     'Count'
#   )
def datapoint_added_to_metric?(
  cloudwatch_client,
  metric_namespace,
  metric_name,
  dimension_name,
  dimension_value,
  metric_value,
  metric_unit
)
  cloudwatch_client.put_metric_data(
    namespace: metric_namespace,
    metric_data: [
      {
        metric_name: metric_name,
        dimensions: [
          {
            name: dimension_name,
            value: dimension_value
          }
        ],
        value: metric_value,
        unit: metric_unit
      }
    ]
  )
```

```
  puts "Added data about '#{metric_name}' to namespace " \
    "'#{metric_namespace}'."
  return true
rescue StandardError => e
  puts "Error adding data about '#{metric_name}' to namespace " \
    "'#{metric_namespace}': #{e.message}"
  return false
end
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for Ruby da API.

Cenários para CloudWatch usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon CloudWatch com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar CloudWatch alarmes usando um SDK AWS
- Comece a usar CloudWatch métricas, painéis e alarmes usando um SDK AWS
- Gerencie CloudWatch métricas e alarmes usando um SDK AWS

Comece a usar CloudWatch alarmes usando um SDK AWS

O código de exemplo a seguir mostra como:

- Crie um alarme.
- Desabilite ações de alarme.
- Descreva um alarme.
- Exclua um alarme.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
DATA lt_alarmnames TYPE /aws1/cl_cwtalarmnames_w=>tt_alarmnames.
DATA lo_alarmname TYPE REF TO /aws1/cl_cwtalarmnames_w.

"Create an alarm"
TRY.
    lo_cwt->putmetricalarm(
      iv_alarmname                = iv_alarm_name
      iv_comparisonoperator       = iv_comparison_operator
      iv_evaluationperiods        = iv_evaluation_periods
      iv_metricname               = iv_metric_name
      iv_namespace                = iv_namespace
      iv_statistic                = iv_statistic
      iv_threshold                = iv_threshold
      iv_actionsenabled           = iv_actions_enabled
      iv_alarmdescription         = iv_alarm_description
      iv_unit                     = iv_unit
      iv_period                   = iv_period
      it_dimensions               = it_dimensions
    ).
    MESSAGE 'Alarm created' TYPE 'I'.
  CATCH /aws1/cx_cwtlimitexceededfault.
    MESSAGE 'The request processing has exceeded the limit' TYPE 'E'.
ENDTRY.

"Create an ABAP internal table for the created alarm."
CREATE OBJECT lo_alarmname EXPORTING iv_value = iv_alarm_name.
INSERT lo_alarmname INTO TABLE lt_alarmnames.

"Disable alarm actions."
TRY.
    lo_cwt->disablealarmactions(
```

```
          it_alarmnames               = lt_alarmnames
        ).
        MESSAGE 'Alarm actions disabled' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_disablealarm_exception).
        DATA(lv_disablealarm_error) = |"{ lo_disablealarm_exception-
>av_err_code }" - { lo_disablealarm_exception->av_err_msg }|.
        MESSAGE lv_disablealarm_error TYPE 'E'.
    ENDTRY.

    "Describe alarm using the same ABAP internal table."
    TRY.
        oo_result = lo_cwt->describealarms(                       " oo_result is
 returned for testing purpose "
          it_alarmnames               = lt_alarmnames
        ).
        MESSAGE 'Alarms retrieved' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_describealarms_exception).
        DATA(lv_describealarms_error) = |"{ lo_describealarms_exception-
>av_err_code }" - { lo_describealarms_exception->av_err_msg }|.
        MESSAGE lv_describealarms_error TYPE 'E'.
    ENDTRY.

    "Delete alarm."
    TRY.
        lo_cwt->deletealarms(
          it_alarmnames = lt_alarmnames
        ).
        MESSAGE 'Alarms deleted' TYPE 'I'.
      CATCH /aws1/cx_cwtresourcenotfound .
        MESSAGE 'Resource being access is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DeleteAlarms
  - DescribeAlarms
  - DisableAlarmActions
  - PutMetricAlarm

Comece a usar CloudWatch métricas, painéis e alarmes usando um SDK AWS

Os exemplos de código a seguir mostram como:

- Listar CloudWatch namespaces e métricas.
- Obtenha estatísticas para uma métrica e para faturamento estimado.
- Crie e atualize um painel.
- Crie e adicione dados a uma métrica.
- Crie e acione um alarme e, em seguida, visualize o histórico de alarmes.
- Crie um detector de anomalias.
- Obtenha uma imagem de métrica e, em seguida, limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public class CloudWatchScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    To enable billing metrics and statistics for this example, make sure billing
 alerts are enabled for your account:
    https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics

    This .NET example performs the following tasks:
        1. List and select a CloudWatch namespace.
        2. List and select a CloudWatch metric.
        3. Get statistics for a CloudWatch metric.
```

```
        4. Get estimated billing statistics for the last week.
        5. Create a new CloudWatch dashboard with two metrics.
        6. List current CloudWatch dashboards.
        7. Create a CloudWatch custom metric and add metric data.
        8. Add the custom metric to the dashboard.
        9. Create a CloudWatch alarm for the custom metric.
       10. Describe current CloudWatch alarms.
       11. Get recent data for the custom metric.
       12. Add data to the custom metric to trigger the alarm.
       13. Wait for an alarm state.
       14. Get history for the CloudWatch alarm.
       15. Add an anomaly detector.
       16. Describe current anomaly detectors.
       17. Get and display a metric image.
       18. Clean up resources.
   */

   private static ILogger logger = null!;
   private static CloudWatchWrapper _cloudWatchWrapper = null!;
   private static IConfiguration _configuration = null!;
   private static readonly List<string> _statTypes = new List<string>
{ "SampleCount", "Average", "Sum", "Minimum", "Maximum" };
   private static SingleMetricAnomalyDetector? anomalyDetector = null!;

   static async Task Main(string[] args)
   {
       // Set up dependency injection for the Amazon service.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
           .ConfigureServices((_, services) =>
           services.AddAWSService<IAmazonCloudWatch>()
           .AddTransient<CloudWatchWrapper>()
       )
       .Build();

       _configuration = new ConfigurationBuilder()
           .SetBasePath(Directory.GetCurrentDirectory())
           .AddJsonFile("settings.json") // Load settings from .json file.
           .AddJsonFile("settings.local.json",
```

```
                true) // Optionally, load local settings.
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<CloudWatchScenario>();

        _cloudWatchWrapper =
host.Services.GetRequiredService<CloudWatchWrapper>();

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon CloudWatch example scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            var selectedNamespace = await SelectNamespace();
            var selectedMetric = await SelectMetric(selectedNamespace);
            await GetAndDisplayMetricStatistics(selectedNamespace,
selectedMetric);
            await GetAndDisplayEstimatedBilling();
            await CreateDashboardWithMetrics();
            await ListDashboards();
            await CreateNewCustomMetric();
            await AddMetricToDashboard();
            await CreateMetricAlarm();
            await DescribeAlarms();
            await GetCustomMetricData();
            await AddMetricDataForAlarm();
            await CheckForMetricAlarm();
            await GetAlarmHistory();
            anomalyDetector = await AddAnomalyDetector();
            await DescribeAnomalyDetectors();
            await GetAndOpenMetricImage();
            await CleanupResources();
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
            await CleanupResources();
        }

    }

    /// <summary>
```

```
    /// Select a namespace.
    /// </summary>
    /// <returns>The selected namespace.</returns>
    private static async Task<string> SelectNamespace()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. Select a CloudWatch Namespace from a list of
Namespaces.");
        var metrics = await _cloudWatchWrapper.ListMetrics();
        // Get a distinct list of namespaces.
        var namespaces = metrics.Select(m => m.Namespace).Distinct().ToList();
        for (int i = 0; i < namespaces.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {namespaces[i]}");
        }

        var namespaceChoiceNumber = 0;
        while (namespaceChoiceNumber < 1 || namespaceChoiceNumber >
namespaces.Count)
        {
            Console.WriteLine(
                "Select a namespace by entering a number from the preceding
list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out namespaceChoiceNumber);
        }

        var selectedNamespace = namespaces[namespaceChoiceNumber - 1];

        Console.WriteLine(new string('-', 80));

        return selectedNamespace;
    }

    /// <summary>
    /// Select a metric from a namespace.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <returns>The metric name.</returns>
    private static async Task<Metric> SelectMetric(string metricNamespace)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"2. Select a CloudWatch metric from a namespace.");
```

```
        var namespaceMetrics = await
_cloudWatchWrapper.ListMetrics(metricNamespace);

        for (int i = 0; i < namespaceMetrics.Count && i < 15; i++)
        {
            var dimensionsWithValues = namespaceMetrics[i].Dimensions
                .Where(d => !string.Equals("None", d.Value));
            Console.WriteLine($"\t{i + 1}. {namespaceMetrics[i].MetricName} " +
                              $"{string.Join(", :", dimensionsWithValues.Select(d
=> d.Value))}");
        }

        var metricChoiceNumber = 0;
        while (metricChoiceNumber < 1 || metricChoiceNumber >
namespaceMetrics.Count)
        {
            Console.WriteLine(
                "Select a metric by entering a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out metricChoiceNumber);
        }

        var selectedMetric = namespaceMetrics[metricChoiceNumber - 1];

        Console.WriteLine(new string('-', 80));

        return selectedMetric;
    }

    /// <summary>
    /// Get and display metric statistics for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task GetAndDisplayMetricStatistics(string
metricNamespace, Metric metric)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. Get CloudWatch metric statistics for the last
day.");

        for (int i = 0; i < _statTypes.Count; i++)
        {
```

```
            Console.WriteLine($"\t{i + 1}. {_statTypes[i]}");
        }

        var statisticChoiceNumber = 0;
        while (statisticChoiceNumber < 1 || statisticChoiceNumber >
_statTypes.Count)
        {
            Console.WriteLine(
                "Select a metric statistic by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out statisticChoiceNumber);
        }

        var selectedStatistic = _statTypes[statisticChoiceNumber - 1];
        var statisticsList = new List<string> { selectedStatistic };

        var metricStatistics = await
_cloudWatchWrapper.GetMetricStatistics(metricNamespace, metric.MetricName,
statisticsList, metric.Dimensions, 1, 60);

        if (!metricStatistics.Any())
        {
            Console.WriteLine($"No {selectedStatistic} statistics found for
{metric} in namespace {metricNamespace}.");
        }

        metricStatistics = metricStatistics.OrderBy(s => s.Timestamp).ToList();
        for (int i = 0; i < metricStatistics.Count && i < 10; i++)
        {
            var metricStat = metricStatistics[i];
            var statValue =
metricStat.GetType().GetProperty(selectedStatistic)!.GetValue(metricStat, null);
            Console.WriteLine($"\t{i + 1}. Timestamp
{metricStatistics[i].Timestamp:G} {selectedStatistic}: {statValue}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get and display estimated billing statistics.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
```

```
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task GetAndDisplayEstimatedBilling()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. Get CloudWatch estimated billing for the last
week.");

        var billingStatistics = await SetupBillingStatistics();

        for (int i = 0; i < billingStatistics.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. Timestamp
{billingStatistics[i].Timestamp:G} : {billingStatistics[i].Maximum}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get billing statistics using a call to a wrapper class.
    /// </summary>
    /// <returns>A collection of billing statistics.</returns>
    private static async Task<List<Datapoint>> SetupBillingStatistics()
    {
        // Make a request for EstimatedCharges with a period of one day for the
past seven days.
        var billingStatistics = await _cloudWatchWrapper.GetMetricStatistics(
            "AWS/Billing",
            "EstimatedCharges",
            new List<string>() { "Maximum" },
            new List<Dimension>() { new Dimension { Name = "Currency", Value =
"USD" } },
            7,
            86400);

        billingStatistics = billingStatistics.OrderBy(n => n.Timestamp).ToList();

        return billingStatistics;
    }

    /// <summary>
    /// Create a dashboard with metrics.
    /// </summary>
```

```
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task CreateDashboardWithMetrics()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"5. Create a new CloudWatch dashboard with metrics.");
        var dashboardName = _configuration["dashboardName"];
        var newDashboard = new DashboardModel();
        _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);
        var newDashboardString = JsonSerializer.Serialize(
            newDashboard,
            new JsonSerializerOptions
            {
                DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull
            });
        var validationMessages =
            await _cloudWatchWrapper.PutDashboard(dashboardName,
newDashboardString);

        Console.WriteLine(validationMessages.Any() ? $"\tValidation messages:" :
null);
        for (int i = 0; i < validationMessages.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {validationMessages[i].Message}");
        }
        Console.WriteLine($"\tDashboard {dashboardName} was created.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List dashboards.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDashboards()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. List the CloudWatch dashboards in the current
account.");

        var dashboards = await _cloudWatchWrapper.ListDashboards();

        for (int i = 0; i < dashboards.Count; i++)
        {
```

```
            Console.WriteLine($"\t{i + 1}. {dashboards[i].DashboardName}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create and add data for a new custom metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateNewCustomMetric()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Create and add data for a new custom metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var customData = await PutRandomMetricData(customMetricName,
customMetricNamespace);

        var valuesString = string.Join(',', customData.Select(d => d.Value));
        Console.WriteLine($"\tAdded metric values for for metric
{customMetricName}: \n\t{valuesString}");

        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// Add some metric data using a call to a wrapper class.
    /// </summary>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <returns></returns>
    private static async Task<List<MetricDatum>> PutRandomMetricData(string
customMetricName,
        string customMetricNamespace)
    {
        List<MetricDatum> customData = new List<MetricDatum>();
        Random rnd = new Random();

        // Add 10 random values up to 100, starting with a timestamp 15 minutes
in the past.
```

```
        var utcNowMinus15 = DateTime.UtcNow.AddMinutes(-15);
        for (int i = 0; i < 10; i++)
        {
            var metricValue = rnd.Next(0, 100);
            customData.Add(
                new MetricDatum
                {
                    MetricName = customMetricName,
                    Value = metricValue,
                    TimestampUtc = utcNowMinus15.AddMinutes(i)
                }
            );
        }

        await _cloudWatchWrapper.PutMetricData(customMetricNamespace,
customData);
        return customData;
    }

    /// <summary>
    /// Add the custom metric to the dashboard.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task AddMetricToDashboard()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. Add the new custom metric to the dashboard.");

        var dashboardName = _configuration["dashboardName"];

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var validationMessages = await SetupDashboard(customMetricNamespace,
customMetricName, dashboardName);

        Console.WriteLine(validationMessages.Any() ? $"\tValidation messages:" :
null);
        for (int i = 0; i < validationMessages.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {validationMessages[i].Message}");
        }
        Console.WriteLine($"\tDashboard {dashboardName} updated with metric
{customMetricName}.");
```

```
        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// Set up a dashboard using a call to the wrapper class.
    /// </summary>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A list of validation messages.</returns>
    private static async Task<List<DashboardValidationMessage>> SetupDashboard(
        string customMetricNamespace, string customMetricName, string
 dashboardName)
    {
        // Get the dashboard model from configuration.
        var newDashboard = new DashboardModel();
        _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);

        // Add a new metric to the dashboard.
        newDashboard.Widgets.Add(new Widget
        {
            Height = 8,
            Width = 8,
            Y = 8,
            X = 0,
            Type = "metric",
            Properties = new Properties
            {
                Metrics = new List<List<object>>
                    { new() { customMetricNamespace, customMetricName } },
                View = "timeSeries",
                Region = "us-east-1",
                Stat = "Sum",
                Period = 86400,
                YAxis = new YAxis { Left = new Left { Min = 0, Max = 100 } },
                Title = "Custom Metric Widget",
                LiveData = true,
                Sparkline = true,
                Trend = true,
                Stacked = false,
                SetPeriodToTimeRange = false
            }
        });
```

```
        var newDashboardString = JsonSerializer.Serialize(newDashboard,
            new JsonSerializerOptions
            { DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull });
        var validationMessages =
            await _cloudWatchWrapper.PutDashboard(dashboardName,
newDashboardString);

        return validationMessages;
    }

    /// <summary>
    /// Create a CloudWatch alarm for the new metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateMetricAlarm()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Create a CloudWatch alarm for the new metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var alarmName = _configuration["exampleAlarmName"];
        var accountId = _configuration["accountId"];
        var region = _configuration["region"];
        var emailTopic = _configuration["emailTopic"];
        var alarmActions = new List<string>();

        if (GetYesNoResponse(
                $"\tAdd an email action for topic {emailTopic} to alarm
{alarmName}? (y/n)"))
        {
            _cloudWatchWrapper.AddEmailAlarmAction(accountId, region, emailTopic,
alarmActions);
        }

        await _cloudWatchWrapper.PutMetricEmailAlarm(
            "Example metric alarm",
            alarmName,
            ComparisonOperator.GreaterThanOrEqualToThreshold,
            customMetricName,
            customMetricNamespace,
            100,
```

```
            alarmActions);

        Console.WriteLine($"\tAlarm {alarmName} added for metric
{customMetricName}.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Describe Alarms.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeAlarms()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Describe CloudWatch alarms in the current
account.");

        var alarms = await _cloudWatchWrapper.DescribeAlarms();
        alarms = alarms.OrderByDescending(a => a.StateUpdatedTimestamp).ToList();

        for (int i = 0; i < alarms.Count && i < 10; i++)
        {
            var alarm = alarms[i];
            Console.WriteLine($"\t{i + 1}. {alarm.AlarmName}");
            Console.WriteLine($"\tState: {alarm.StateValue} for
{alarm.MetricName} {alarm.ComparisonOperator} {alarm.Threshold}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get the recent data for the metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetCustomMetricData()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"11. Get current data for new custom metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var accountId = _configuration["accountId"];
```

```
        var query = new List<MetricDataQuery>
        {
            new MetricDataQuery
            {
                AccountId = accountId,
                Id = "m1",
                Label = "Custom Metric Data",
                MetricStat = new MetricStat
                {
                    Metric = new Metric
                    {
                        MetricName = customMetricName,
                        Namespace = customMetricNamespace,
                    },
                    Period = 1,
                    Stat = "Maximum"
                }
            }
        };

        var metricData = await _cloudWatchWrapper.GetMetricData(
            20,
            true,
            DateTime.UtcNow.AddMinutes(1),
            20,
            query);

        for (int i = 0; i < metricData.Count; i++)
        {
            for (int j = 0; j < metricData[i].Values.Count; j++)
            {
                Console.WriteLine(
                    $"\tTimestamp {metricData[i].Timestamps[j]:G} Value:
{metricData[i].Values[j]}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add metric data to trigger an alarm.
    /// </summary>
    /// <returns>Async task.</returns>
```

```
    private static async Task AddMetricDataForAlarm()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"12. Add metric data to the custom metric to trigger
an alarm.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var nowUtc = DateTime.UtcNow;
        List<MetricDatum> customData = new List<MetricDatum>
        {
            new MetricDatum
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc.AddMinutes(-2)
            },
            new MetricDatum
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc.AddMinutes(-1)
            },
            new MetricDatum
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc
            }
        };
        var valuesString = string.Join(',', customData.Select(d => d.Value));
        Console.WriteLine($"\tAdded metric values for for metric
{customMetricName}: \n\t{valuesString}");
        await _cloudWatchWrapper.PutMetricData(customMetricNamespace,
customData);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check for a metric alarm using the DescribeAlarmsForMetric action.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckForMetricAlarm()
```

```
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"13. Checking for an alarm state.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var hasAlarm = false;
        var retries = 10;
        while (!hasAlarm && retries > 0)
        {
            var alarms = await
_cloudWatchWrapper.DescribeAlarmsForMetric(customMetricNamespace,
customMetricName);
            hasAlarm = alarms.Any(a => a.StateValue == StateValue.ALARM);
            retries--;
            Thread.Sleep(20000);
        }

        Console.WriteLine(hasAlarm
            ? $"\tAlarm state found for {customMetricName}."
            : $"\tNo Alarm state found for {customMetricName} after 10
retries.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get history for an alarm.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetAlarmHistory()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"14. Get alarm history.");

        var exampleAlarmName = _configuration["exampleAlarmName"];

        var alarmHistory = await
_cloudWatchWrapper.DescribeAlarmHistory(exampleAlarmName, 2);

        for (int i = 0; i < alarmHistory.Count; i++)
        {
            var history = alarmHistory[i];
```

```
            Console.WriteLine($"\t{i + 1}. {history.HistorySummary}, time
{history.Timestamp:g}");
        }
        if (!alarmHistory.Any())
        {
            Console.WriteLine($"\tNo alarm history data found for
{exampleAlarmName}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add an anomaly detector.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<SingleMetricAnomalyDetector> AddAnomalyDetector()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"15. Add an anomaly detector.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var detector = new SingleMetricAnomalyDetector
        {
            MetricName = customMetricName,
            Namespace = customMetricNamespace,
            Stat = "Maximum"
        };
        await _cloudWatchWrapper.PutAnomalyDetector(detector);
        Console.WriteLine($"\tAdded anomaly detector for metric
{customMetricName}.");

        Console.WriteLine(new string('-', 80));
        return detector;
    }

    /// <summary>
    /// Describe anomaly detectors.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeAnomalyDetectors()
    {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"16. Describe anomaly detectors in the current
account.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var detectors = await
_cloudWatchWrapper.DescribeAnomalyDetectors(customMetricNamespace,
customMetricName);

        for (int i = 0; i < detectors.Count; i++)
        {
            var detector = detectors[i];
            Console.WriteLine($"\t{i + 1}.
{detector.SingleMetricAnomalyDetector.MetricName}, state
{detector.StateValue}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Fetch and open a metrics image for a CloudWatch metric and namespace.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetAndOpenMetricImage()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("17. Get a metric image from CloudWatch.");

        Console.WriteLine($"\tGetting Image data for custom metric.");
        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var memoryStream = await
_cloudWatchWrapper.GetTimeSeriesMetricImage(customMetricNamespace,
customMetricName, "Maximum", 10);
        var file = _cloudWatchWrapper.SaveMetricImage(memoryStream,
"MetricImages");

        ProcessStartInfo info = new ProcessStartInfo();

        Console.WriteLine($"\tFile saved as {Path.GetFileName(file)}.");
```

```
        Console.WriteLine($"\tPress enter to open the image.");
        Console.ReadLine();
        info.FileName = Path.Combine("ms-photos://", file);
        info.UseShellExecute = true;
        info.CreateNoWindow = true;
        info.Verb = string.Empty;

        Process.Start(info);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up created resources.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"18. Clean up resources.");

        var dashboardName = _configuration["dashboardName"];
        if (GetYesNoResponse($"\tDelete dashboard {dashboardName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting dashboard.");
            var dashboardList = new List<string> { dashboardName };
            await _cloudWatchWrapper.DeleteDashboards(dashboardList);
        }

        var alarmName = _configuration["exampleAlarmName"];
        if (GetYesNoResponse($"\tDelete alarm {alarmName}? (y/n)"))
        {
            Console.WriteLine($"\tCleaning up alarms.");
            var alarms = new List<string> { alarmName };
            await _cloudWatchWrapper.DeleteAlarms(alarms);
        }

        if (GetYesNoResponse($"\tDelete anomaly detector? (y/n)") &&
anomalyDetector != null)
        {
            Console.WriteLine($"\tCleaning up anomaly detector.");
```

```
            await _cloudWatchWrapper.DeleteAnomalyDetector(
                anomalyDetector);
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

Métodos de embalagem usados pelo cenário para CloudWatch ações.

```
/// <summary>
/// Wrapper class for Amazon CloudWatch methods.
/// </summary>
public class CloudWatchWrapper
{
    private readonly IAmazonCloudWatch _amazonCloudWatch;
    private readonly ILogger<CloudWatchWrapper> _logger;

    /// <summary>
    /// Constructor for the CloudWatch wrapper.
    /// </summary>
    /// <param name="amazonCloudWatch">The injected CloudWatch client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public CloudWatchWrapper(IAmazonCloudWatch amazonCloudWatch,
 ILogger<CloudWatchWrapper> logger)
```

```
    {
        _logger = logger;
        _amazonCloudWatch = amazonCloudWatch;
    }

    /// <summary>
    /// List metrics available, optionally within a namespace.
    /// </summary>
    /// <param name="metricNamespace">Optional CloudWatch namespace to use when
listing metrics.</param>
    /// <param name="filter">Optional dimension filter.</param>
    /// <param name="metricName">Optional metric name filter.</param>
    /// <returns>The list of metrics.</returns>
    public async Task<List<Metric>> ListMetrics(string? metricNamespace = null,
DimensionFilter? filter = null, string? metricName = null)
    {
        var results = new List<Metric>();
        var paginateMetrics = _amazonCloudWatch.Paginators.ListMetrics(
            new ListMetricsRequest
            {
                Namespace = metricNamespace,
                Dimensions = filter != null ? new List<DimensionFilter>
{ filter } : null,
                MetricName = metricName
            });
        // Get the entire list using the paginator.
        await foreach (var metric in paginateMetrics.Metrics)
        {
            results.Add(metric);
        }

        return results;
    }

    /// <summary>
    /// Wrapper to get statistics for a specific CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <param name="statistics">The list of statistics to include.</param>
    /// <param name="dimensions">The list of dimensions to include.</param>
    /// <param name="days">The number of days in the past to include.</param>
    /// <param name="period">The period for the data.</param>
    /// <returns>A list of DataPoint objects for the statistics.</returns>
```

```
    public async Task<List<Datapoint>> GetMetricStatistics(string
 metricNamespace,
        string metricName, List<string> statistics, List<Dimension> dimensions,
 int days, int period)
    {
        var metricStatistics = await _amazonCloudWatch.GetMetricStatisticsAsync(
            new GetMetricStatisticsRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName,
                Dimensions = dimensions,
                Statistics = statistics,
                StartTimeUtc = DateTime.UtcNow.AddDays(-days),
                EndTimeUtc = DateTime.UtcNow,
                Period = period
            });

        return metricStatistics.Datapoints;
    }

    /// <summary>
    /// Wrapper to create or add to a dashboard with metrics.
    /// </summary>
    /// <param name="dashboardName">The name for the dashboard.</param>
    /// <param name="dashboardBody">The metric data in JSON for the dashboard.</
param>
    /// <returns>A list of validation messages for the dashboard.</returns>
    public async Task<List<DashboardValidationMessage>> PutDashboard(string
 dashboardName,
        string dashboardBody)
    {
        // Updating a dashboard replaces all contents.
        // Best practice is to include a text widget indicating this dashboard
 was created programmatically.
        var dashboardResponse = await _amazonCloudWatch.PutDashboardAsync(
            new PutDashboardRequest()
            {
                DashboardName = dashboardName,
                DashboardBody = dashboardBody
            });

        return dashboardResponse.DashboardValidationMessages;
    }
```

```
    /// <summary>
    /// Get information on a dashboard.
    /// </summary>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A JSON object with dashboard information.</returns>
    public async Task<string> GetDashboard(string dashboardName)
    {
        var dashboardResponse = await _amazonCloudWatch.GetDashboardAsync(
            new GetDashboardRequest()
            {
                DashboardName = dashboardName
            });

        return dashboardResponse.DashboardBody;
    }


    /// <summary>
    /// Get a list of dashboards.
    /// </summary>
    /// <returns>A list of DashboardEntry objects.</returns>
    public async Task<List<DashboardEntry>> ListDashboards()
    {
        var results = new List<DashboardEntry>();
        var paginateDashboards = _amazonCloudWatch.Paginators.ListDashboards(
            new ListDashboardsRequest());
        // Get the entire list using the paginator.
        await foreach (var data in paginateDashboards.DashboardEntries)
        {
            results.Add(data);
        }

        return results;
    }

    /// <summary>
    /// Wrapper to add metric data to a CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricData">A data object for the metric data.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricData(string metricNamespace,
        List<MetricDatum> metricData)
```

```
    {
        var putDataResponse = await _amazonCloudWatch.PutMetricDataAsync(
            new PutMetricDataRequest()
            {
                MetricData = metricData,
                Namespace = metricNamespace,
            });

        return putDataResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Get an image for a metric graphed over time.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metric">The name of the metric.</param>
    /// <param name="stat">The name of the stat to chart.</param>
    /// <param name="period">The period to use for the chart.</param>
    /// <returns>A memory stream for the chart image.</returns>
    public async Task<MemoryStream> GetTimeSeriesMetricImage(string
 metricNamespace, string metric, string stat, int period)
    {
        var metricImageWidget = new
        {
            title = "Example Metric Graph",
            view = "timeSeries",
            stacked = false,
            period = period,
            width = 1400,
            height = 600,
            metrics = new List<List<object>>
                { new() { metricNamespace, metric, new { stat } } }
        };

        var metricImageWidgetString =
 JsonSerializer.Serialize(metricImageWidget);
        var imageResponse = await _amazonCloudWatch.GetMetricWidgetImageAsync(
            new GetMetricWidgetImageRequest()
            {
                MetricWidget = metricImageWidgetString
            });

        return imageResponse.MetricWidgetImage;
    }
```

```
    /// <summary>
    /// Save a metric image to a file.
    /// </summary>
    /// <param name="memoryStream">The MemoryStream for the metric image.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The path to the file.</returns>
    public string SaveMetricImage(MemoryStream memoryStream, string metricName)
    {
        var metricFileName = $"{metricName}_{DateTime.Now.Ticks}.png";
        using var sr = new StreamReader(memoryStream);
        // Writes the memory stream to a file.
        File.WriteAllBytes(metricFileName, memoryStream.ToArray());
        var filePath = Path.Join(AppDomain.CurrentDomain.BaseDirectory,
            metricFileName);
        return filePath;
    }

    /// <summary>
    /// Get data for CloudWatch metrics.
    /// </summary>
    /// <param name="minutesOfData">The number of minutes of data to include.</
param>
    /// <param name="useDescendingTime">True to return the data descending by
 time.</param>
    /// <param name="endDateUtc">The end date for the data, in UTC.</param>
    /// <param name="maxDataPoints">The maximum data points to include.</param>
    /// <param name="dataQueries">Optional data queries to include.</param>
    /// <returns>A list of the requested metric data.</returns>
    public async Task<List<MetricDataResult>> GetMetricData(int minutesOfData,
 bool useDescendingTime, DateTime? endDateUtc = null,
        int maxDataPoints = 0, List<MetricDataQuery>? dataQueries = null)
    {
        var metricData = new List<MetricDataResult>();
        // If no end time is provided, use the current time for the end time.
        endDateUtc ??= DateTime.UtcNow;
        var timeZoneOffset =
 TimeZoneInfo.Local.GetUtcOffset(endDateUtc.Value.ToLocalTime());
        var startTimeUtc = endDateUtc.Value.AddMinutes(-minutesOfData);
        // The timezone string should be in the format +0000, so use the timezone
 offset to format it correctly.
        var timeZoneString = $"{timeZoneOffset.Hours:D2}
{timeZoneOffset.Minutes:D2}";
        var paginatedMetricData = _amazonCloudWatch.Paginators.GetMetricData(
```

```
            new GetMetricDataRequest()
            {
                StartTimeUtc = startTimeUtc,
                EndTimeUtc = endDateUtc.Value,
                LabelOptions = new LabelOptions { Timezone = timeZoneString },
                ScanBy = useDescendingTime ? ScanBy.TimestampDescending :
ScanBy.TimestampAscending,
                MaxDatapoints = maxDataPoints,
                MetricDataQueries = dataQueries,
            });

        await foreach (var data in paginatedMetricData.MetricDataResults)
        {
            metricData.Add(data);
        }
        return metricData;
    }

    /// <summary>
    /// Add a metric alarm to send an email when the metric passes a threshold.
    /// </summary>
    /// <param name="alarmDescription">A description of the alarm.</param>
    /// <param name="alarmName">The name for the alarm.</param>
    /// <param name="comparison">The type of comparison to use.</param>
    /// <param name="metricName">The name of the metric for the alarm.</param>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="threshold">The threshold value for the alarm.</param>
    /// <param name="alarmActions">Optional actions to execute when in an alarm
state.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricEmailAlarm(string alarmDescription, string
alarmName, ComparisonOperator comparison,
        string metricName, string metricNamespace, double threshold, List<string>
alarmActions = null!)
    {
        try
        {
            var putEmailAlarmResponse = await
_amazonCloudWatch.PutMetricAlarmAsync(
                new PutMetricAlarmRequest()
                {
                    AlarmActions = alarmActions,
                    AlarmDescription = alarmDescription,
                    AlarmName = alarmName,
```

```
                    ComparisonOperator = comparison,
                    Threshold = threshold,
                    Namespace = metricNamespace,
                    MetricName = metricName,
                    EvaluationPeriods = 1,
                    Period = 10,
                    Statistic = new Statistic("Maximum"),
                    DatapointsToAlarm = 1,
                    TreatMissingData = "ignore"
                });
            return putEmailAlarmResponse.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (LimitExceededException lex)
        {
            _logger.LogError(lex, $"Unable to add alarm {alarmName}. Alarm quota
 has already been reached.");
        }

        return false;
    }

    /// <summary>
    /// Add specific email actions to a list of action strings for a CloudWatch
 alarm.
    /// </summary>
    /// <param name="accountId">The AccountId for the alarm.</param>
    /// <param name="region">The region for the alarm.</param>
    /// <param name="emailTopicName">An Amazon Simple Notification Service (SNS)
 topic for the alarm email.</param>
    /// <param name="alarmActions">Optional list of existing alarm actions to
 append to.</param>
    /// <returns>A list of string actions for an alarm.</returns>
    public List<string> AddEmailAlarmAction(string accountId, string region,
        string emailTopicName, List<string>? alarmActions = null)
    {
        alarmActions ??= new List<string>();
        var snsAlarmAction = $"arn:aws:sns:{region}:{accountId}:
{emailTopicName}";
        alarmActions.Add(snsAlarmAction);
        return alarmActions;
    }

    /// <summary>
    /// Describe the current alarms, optionally filtered by state.
```

```
    /// </summary>
    /// <param name="stateValue">Optional filter for alarm state.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarms(StateValue? stateValue =
null)
    {
        List<MetricAlarm> alarms = new List<MetricAlarm>();
        var paginatedDescribeAlarms =
_amazonCloudWatch.Paginators.DescribeAlarms(
            new DescribeAlarmsRequest()
            {
                StateValue = stateValue
            });

        await foreach (var data in paginatedDescribeAlarms.MetricAlarms)
        {
            alarms.Add(data);
        }
        return alarms;
    }

    /// <summary>
    /// Describe the current alarms for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarmsForMetric(string
metricNamespace, string metricName)
    {
        var alarmsResult = await _amazonCloudWatch.DescribeAlarmsForMetricAsync(
            new DescribeAlarmsForMetricRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName
            });

        return alarmsResult.MetricAlarms;
    }

    /// <summary>
    /// Describe the history of an alarm for a number of days in the past.
    /// </summary>
    /// <param name="alarmName">The name of the alarm.</param>
```

```
    /// <param name="historyDays">The number of days in the past.</param>
    /// <returns>The list of alarm history data.</returns>
    public async Task<List<AlarmHistoryItem>> DescribeAlarmHistory(string
alarmName, int historyDays)
    {
        List<AlarmHistoryItem> alarmHistory = new List<AlarmHistoryItem>();
        var paginatedAlarmHistory =
_amazonCloudWatch.Paginators.DescribeAlarmHistory(
            new DescribeAlarmHistoryRequest()
            {
                AlarmName = alarmName,
                EndDateUtc = DateTime.UtcNow,
                HistoryItemType = HistoryItemType.StateUpdate,
                StartDateUtc = DateTime.UtcNow.AddDays(-historyDays)
            });

        await foreach (var data in paginatedAlarmHistory.AlarmHistoryItems)
        {
            alarmHistory.Add(data);
        }
        return alarmHistory;
    }

    /// <summary>
    /// Delete a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAlarms(List<string> alarmNames)
    {
        var deleteAlarmsResult = await _amazonCloudWatch.DeleteAlarmsAsync(
            new DeleteAlarmsRequest()
            {
                AlarmNames = alarmNames
            });

        return deleteAlarmsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Disable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
```

```
    public async Task<bool> DisableAlarmActions(List<string> alarmNames)
    {
        var disableAlarmActionsResult = await
_amazonCloudWatch.DisableAlarmActionsAsync(
            new DisableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return disableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Enable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableAlarmActions(List<string> alarmNames)
    {
        var enableAlarmActionsResult = await
_amazonCloudWatch.EnableAlarmActionsAsync(
            new EnableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return enableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Add an anomaly detector for a single metric.
    /// </summary>
    /// <param name="anomalyDetector">A single metric anomaly detector.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
    {
        var putAlarmDetectorResult = await
_amazonCloudWatch.PutAnomalyDetectorAsync(
            new PutAnomalyDetectorRequest()
            {
                SingleMetricAnomalyDetector = anomalyDetector
            });
```

```
        return putAlarmDetectorResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Describe anomaly detectors for a metric and namespace.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The metric of the anomaly detectors.</param>
    /// <returns>The list of detectors.</returns>
    public async Task<List<AnomalyDetector>> DescribeAnomalyDetectors(string
metricNamespace, string metricName)
    {
        List<AnomalyDetector> detectors = new List<AnomalyDetector>();
        var paginatedDescribeAnomalyDetectors =
_amazonCloudWatch.Paginators.DescribeAnomalyDetectors(
            new DescribeAnomalyDetectorsRequest()
            {
                MetricName = metricName,
                Namespace = metricNamespace
            });

        await foreach (var data in
paginatedDescribeAnomalyDetectors.AnomalyDetectors)
        {
            detectors.Add(data);
        }

        return detectors;
    }

    /// <summary>
    /// Delete a single metric anomaly detector.
    /// </summary>
    /// <param name="anomalyDetector">The anomaly detector to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
    {
        var deleteAnomalyDetectorResponse = await
_amazonCloudWatch.DeleteAnomalyDetectorAsync(
            new DeleteAnomalyDetectorRequest()
            {
                SingleMetricAnomalyDetector = anomalyDetector
            });
```

```
        return deleteAnomalyDetectorResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete a list of CloudWatch dashboards.
    /// </summary>
    /// <param name="dashboardNames">List of dashboard names to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDashboards(List<string> dashboardNames)
    {
        var deleteDashboardsResponse = await
 _amazonCloudWatch.DeleteDashboardsAsync(
            new DeleteDashboardsRequest()
            {
                DashboardNames = dashboardNames
            });

        return deleteDashboardsResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric
  - DescribeAnomalyDetectors
  - GetMetricData
  - GetMetricStatistics
  - GetMetricWidgetImage
  - ListMetrics
  - PutAnomalyDetector
  - PutDashboard

- PutMetricAlarm
- PutMetricData

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import com.fasterxml.jackson.core.JsonFactory;
import com.fasterxml.jackson.core.JsonParser;
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.AlarmHistoryItem;
import software.amazon.awssdk.services.cloudwatch.model.AlarmType;
import software.amazon.awssdk.services.cloudwatch.model.AnomalyDetector;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.ComparisonOperator;
import
 software.amazon.awssdk.services.cloudwatch.model.DashboardValidationMessage;
import software.amazon.awssdk.services.cloudwatch.model.Datapoint;
import software.amazon.awssdk.services.cloudwatch.model.DeleteAlarmsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DeleteAnomalyDetectorRequest;
import software.amazon.awssdk.services.cloudwatch.model.DeleteDashboardsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmHistoryRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmHistoryResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsForMetricRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsForMetricResponse;
import software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsRequest;
```

```
import software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAnomalyDetectorsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAnomalyDetectorsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Dimension;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricDataRequest;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricDataResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.GetMetricStatisticsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.GetMetricStatisticsResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.GetMetricWidgetImageRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.GetMetricWidgetImageResponse;
import software.amazon.awssdk.services.cloudwatch.model.HistoryItemType;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Metric;
import software.amazon.awssdk.services.cloudwatch.model.MetricAlarm;
import software.amazon.awssdk.services.cloudwatch.model.MetricDataQuery;
import software.amazon.awssdk.services.cloudwatch.model.MetricDataResult;
import software.amazon.awssdk.services.cloudwatch.model.MetricDatum;
import software.amazon.awssdk.services.cloudwatch.model.MetricStat;
import
 software.amazon.awssdk.services.cloudwatch.model.PutAnomalyDetectorRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutDashboardRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutDashboardResponse;
import software.amazon.awssdk.services.cloudwatch.model.PutMetricAlarmRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutMetricDataRequest;
import software.amazon.awssdk.services.cloudwatch.model.ScanBy;
import
 software.amazon.awssdk.services.cloudwatch.model.SingleMetricAnomalyDetector;
import software.amazon.awssdk.services.cloudwatch.model.StandardUnit;
import software.amazon.awssdk.services.cloudwatch.model.Statistic;
import
 software.amazon.awssdk.services.cloudwatch.paginators.ListDashboardsIterable;
import software.amazon.awssdk.services.cloudwatch.paginators.ListMetricsIterable;
import java.io.BufferedReader;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.InputStreamReader;
```

```
import java.nio.file.Files;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.ZoneOffset;
import java.time.ZonedDateTime;
import java.time.format.DateTimeFormatter;
import java.time.temporal.ChronoUnit;
import java.util.ArrayList;
import java.util.List;
import java.util.Scanner;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To enable billing metrics and statistics for this example, make sure billing
 * alerts are enabled for your account:
 * https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics
 *
 * This Java code example performs the following tasks:
 *
 * 1. List available namespaces from Amazon CloudWatch.
 * 2. List available metrics within the selected Namespace.
 * 3. Get statistics for the selected metric over the last day.
 * 4. Get CloudWatch estimated billing for the last week.
 * 5. Create a new CloudWatch dashboard with metrics.
 * 6. List dashboards using a paginator.
 * 7. Create a new custom metric by adding data for it.
 * 8. Add the custom metric to the dashboard.
 * 9. Create an alarm for the custom metric.
 * 10. Describe current alarms.
 * 11. Get current data for the new custom metric.
 * 12. Push data into the custom metric to trigger the alarm.
 * 13. Check the alarm state using the action DescribeAlarmsForMetric.
 * 14. Get alarm history for the new alarm.
 * 15. Add an anomaly detector for the custom metric.
 * 16. Describe current anomaly detectors.
 * 17. Get a metric image for the custom metric.
```

```
 * 18. Clean up the Amazon CloudWatch resources.
 */
public class CloudWatchScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                  <myDate> <costDateWeek> <dashboardName> <dashboardJson>
 <dashboardAdd> <settings> <metricImage> \s

                Where:
                  myDate - The start date to use to get metric statistics. (For
 example, 2023-01-11T18:35:24.00Z.)\s
                  costDateWeek - The start date to use to get AWS/Billinget
 statistics. (For example, 2023-01-11T18:35:24.00Z.)\s
                  dashboardName - The name of the dashboard to create.\s
                  dashboardJson - The location of a JSON file to use to create a
 dashboard. (See Readme file.)\s
                  dashboardAdd - The location of a JSON file to use to update a
 dashboard. (See Readme file.)\s
                  settings - The location of a JSON file from which various
 values are read. (See Readme file.)\s
                  metricImage - The location of a BMP file that is used to create
 a graph.\s
                """;

        if (args.length != 7) {
            System.out.println(usage);
            System.exit(1);
        }

        Region region = Region.US_EAST_1;
        String myDate = args[0];
        String costDateWeek = args[1];
        String dashboardName = args[2];
        String dashboardJson = args[3];
        String dashboardAdd = args[4];
        String settings = args[5];
        String metricImage = args[6];

        Double dataPoint = Double.parseDouble("10.0");
```

```
        Scanner sc = new Scanner(System.in);
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon CloudWatch example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "1. List at least five available unique namespaces from Amazon
CloudWatch. Select one from the list.");
        ArrayList<String> list = listNameSpaces(cw);
        for (int z = 0; z < 5; z++) {
            int index = z + 1;
            System.out.println("    " + index + ". " + list.get(z));
        }

        String selectedNamespace = "";
        String selectedMetrics = "";
        int num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            selectedNamespace = list.get(num - 1);
        } else {
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + selectedNamespace);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. List available metrics within the selected
namespace and select one from the list.");
        ArrayList<String> metList = listMets(cw, selectedNamespace);
        for (int z = 0; z < 5; z++) {
            int index = z + 1;
            System.out.println("    " + index + ". " + metList.get(z));
        }
        num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            selectedMetrics = metList.get(num - 1);
        } else {
```

```
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + selectedMetrics);
        Dimension myDimension = getSpecificMet(cw, selectedNamespace);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get statistics for the selected metric over the
 last day.");
        String metricOption = "";
        ArrayList<String> statTypes = new ArrayList<>();
        statTypes.add("SampleCount");
        statTypes.add("Average");
        statTypes.add("Sum");
        statTypes.add("Minimum");
        statTypes.add("Maximum");

        for (int t = 0; t < 5; t++) {
            System.out.println("    " + (t + 1) + ". " + statTypes.get(t));
        }
        System.out.println("Select a metric statistic by entering a number from
 the preceding list:");
        num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            metricOption = statTypes.get(num - 1);
        } else {
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + metricOption);
        getAndDisplayMetricStatistics(cw, selectedNamespace, selectedMetrics,
 metricOption, myDate, myDimension);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get CloudWatch estimated billing for the last
 week.");
        getMetricStatistics(cw, costDateWeek);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create a new CloudWatch dashboard with metrics.");
        createDashboardWithMetrics(cw, dashboardName, dashboardJson);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. List dashboards using a paginator.");
        listDashboards(cw);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Create a new custom metric by adding data to
it.");
        createNewCustomMetric(cw, dataPoint);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Add an additional metric to the dashboard.");
        addMetricToDashboard(cw, dashboardAdd, dashboardName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Create an alarm for the custom metric.");
        String alarmName = createAlarm(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Describe ten current alarms.");
        describeAlarms(cw);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Get current data for new custom metric.");
        getCustomMetricData(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Push data into the custom metric to trigger the
alarm.");
        addMetricDataForAlarm(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Check the alarm state using the action
DescribeAlarmsForMetric.");
        checkForMetricAlarm(cw, settings);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("14. Get alarm history for the new alarm.");
        getAlarmHistory(cw, settings, myDate);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Add an anomaly detector for the custom metric.");
        addAnomalyDetector(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Describe current anomaly detectors.");
        describeAnomalyDetectors(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Get a metric image for the custom metric.");
        getAndOpenMetricImage(cw, metricImage);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Clean up the Amazon CloudWatch resources.");
        deleteDashboard(cw, dashboardName);
        deleteCWAlarm(cw, alarmName);
        deleteAnomalyDetector(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Amazon CloudWatch example scenario is
complete.");
        System.out.println(DASHES);
        cw.close();
    }

    public static void deleteAnomalyDetector(CloudWatchClient cw, String
fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
```

```
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            DeleteAnomalyDetectorRequest request =
DeleteAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.deleteAnomalyDetector(request);
            System.out.println("Successfully deleted the Anomaly Detector.");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException e) {
            e.printStackTrace();
        }
    }

    public static void deleteCWAlarm(CloudWatchClient cw, String alarmName) {
        try {
            DeleteAlarmsRequest request = DeleteAlarmsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.deleteAlarms(request);
            System.out.println("Successfully deleted alarm " + alarmName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static void deleteDashboard(CloudWatchClient cw, String dashboardName)
{
       try {
           DeleteDashboardsRequest dashboardsRequest =
DeleteDashboardsRequest.builder()
                   .dashboardNames(dashboardName)
                   .build();
           cw.deleteDashboards(dashboardsRequest);
           System.out.println(dashboardName + " was successfully deleted.");

       } catch (CloudWatchException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }

   public static void getAndOpenMetricImage(CloudWatchClient cw, String
fileName) {
       System.out.println("Getting Image data for custom metric.");
       try {
           String myJSON = "{\n" +
                   "  \"title\": \"Example Metric Graph\",\n" +
                   "  \"view\": \"timeSeries\",\n" +
                   "  \"stacked \": false,\n" +
                   "  \"period\": 10,\n" +
                   "  \"width\": 1400,\n" +
                   "  \"height\": 600,\n" +
                   "  \"metrics\": [\n" +
                   "    [\n" +
                   "      \"AWS/Billing\",\n" +
                   "      \"EstimatedCharges\",\n" +
                   "      \"Currency\",\n" +
                   "      \"USD\"\n" +
                   "    ]\n" +
                   "  ]\n" +
                   "}";

           GetMetricWidgetImageRequest imageRequest =
GetMetricWidgetImageRequest.builder()
                   .metricWidget(myJSON)
                   .build();

           GetMetricWidgetImageResponse response =
cw.getMetricWidgetImage(imageRequest);
```

```
            SdkBytes sdkBytes = response.metricWidgetImage();
            byte[] bytes = sdkBytes.asByteArray();
            File outputFile = new File(fileName);
            try (FileOutputStream outputStream = new
FileOutputStream(outputFile)) {
                outputStream.write(bytes);
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void describeAnomalyDetectors(CloudWatchClient cw, String
fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            DescribeAnomalyDetectorsRequest detectorsRequest =
DescribeAnomalyDetectorsRequest.builder()
                    .maxResults(10)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            DescribeAnomalyDetectorsResponse response =
cw.describeAnomalyDetectors(detectorsRequest);
            List<AnomalyDetector> anomalyDetectorList =
response.anomalyDetectors();
            for (AnomalyDetector detector : anomalyDetectorList) {
                System.out.println("Metric name: " +
detector.singleMetricAnomalyDetector().metricName());
                System.out.println("State: " + detector.stateValue());
            }

        } catch (CloudWatchException | IOException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void addAnomalyDetector(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            PutAnomalyDetectorRequest anomalyDetectorRequest =
PutAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.putAnomalyDetector(anomalyDetectorRequest);
            System.out.println("Added anomaly detector for metric " +
customMetricName + ".");

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getAlarmHistory(CloudWatchClient cw, String fileName,
String date) {
        try {
            // Read values from the JSON file.
```

```
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String alarmName = rootNode.findValue("exampleAlarmName").asText();

            Instant start = Instant.parse(date);
            Instant endDate = Instant.now();
            DescribeAlarmHistoryRequest historyRequest =
DescribeAlarmHistoryRequest.builder()
                    .startDate(start)
                    .endDate(endDate)
                    .alarmName(alarmName)
                    .historyItemType(HistoryItemType.ACTION)
                    .build();

            DescribeAlarmHistoryResponse response =
cw.describeAlarmHistory(historyRequest);
            List<AlarmHistoryItem> historyItems = response.alarmHistoryItems();
            if (historyItems.isEmpty()) {
                System.out.println("No alarm history data found for " + alarmName
+ ".");
            } else {
                for (AlarmHistoryItem item : historyItems) {
                    System.out.println("History summary: " +
item.historySummary());
                    System.out.println("Time stamp: " + item.timestamp());
                }
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void checkForMetricAlarm(CloudWatchClient cw, String fileName)
{
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
```

```
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            boolean hasAlarm = false;
            int retries = 10;

            DescribeAlarmsForMetricRequest metricRequest =
DescribeAlarmsForMetricRequest.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            while (!hasAlarm && retries > 0) {
                DescribeAlarmsForMetricResponse response =
cw.describeAlarmsForMetric(metricRequest);
                hasAlarm = response.hasMetricAlarms();
                retries--;
                Thread.sleep(20000);
                System.out.println(".");
            }
            if (!hasAlarm)
                System.out.println("No Alarm state found for " + customMetricName
+ " after 10 retries.");
            else
                System.out.println("Alarm state found for " + customMetricName +
".");

        } catch (CloudWatchException | IOException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void addMetricDataForAlarm(CloudWatchClient cw, String
fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
```

```
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set an Instant object.
            String time =
ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
            Instant instant = Instant.parse(time);

            MetricDatum datum = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1001.00)
                    .timestamp(instant)
                    .build();

            MetricDatum datum2 = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1002.00)
                    .timestamp(instant)
                    .build();

            List<MetricDatum> metricDataList = new ArrayList<>();
            metricDataList.add(datum);
            metricDataList.add(datum2);

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace(customMetricNamespace)
                    .metricData(metricDataList)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric " +
customMetricName);

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getCustomMetricData(CloudWatchClient cw, String fileName)
{
        try {
```

```
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set the date.
            Instant nowDate = Instant.now();

            long hours = 1;
            long minutes = 30;
            Instant date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(minutes,
                    ChronoUnit.MINUTES);

            Metric met = Metric.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            MetricStat metStat = MetricStat.builder()
                    .stat("Maximum")
                    .period(1)
                    .metric(met)
                    .build();

            MetricDataQuery dataQUery = MetricDataQuery.builder()
                    .metricStat(metStat)
                    .id("foo2")
                    .returnData(true)
                    .build();

            List<MetricDataQuery> dq = new ArrayList<>();
            dq.add(dataQUery);

            GetMetricDataRequest getMetReq = GetMetricDataRequest.builder()
                    .maxDatapoints(10)
                    .scanBy(ScanBy.TIMESTAMP_DESCENDING)
                    .startTime(nowDate)
                    .endTime(date2)
                    .metricDataQueries(dq)
```

```
                    .build();

            GetMetricDataResponse response = cw.getMetricData(getMetReq);
            List<MetricDataResult> data = response.metricDataResults();
            for (MetricDataResult item : data) {
                System.out.println("The label is " + item.label());
                System.out.println("The status code is " +
item.statusCode().toString());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void describeAlarms(CloudWatchClient cw) {
        try {
            List<AlarmType> typeList = new ArrayList<>();
            typeList.add(AlarmType.METRIC_ALARM);

            DescribeAlarmsRequest alarmsRequest = DescribeAlarmsRequest.builder()
                    .alarmTypes(typeList)
                    .maxRecords(10)
                    .build();

            DescribeAlarmsResponse response = cw.describeAlarms(alarmsRequest);
            List<MetricAlarm> alarmList = response.metricAlarms();
            for (MetricAlarm alarm : alarmList) {
                System.out.println("Alarm name: " + alarm.alarmName());
                System.out.println("Alarm description: " +
alarm.alarmDescription());
            }
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new
File(fileName));
```

```
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            String alarmName = rootNode.findValue("exampleAlarmName").asText();
            String emailTopic = rootNode.findValue("emailTopic").asText();
            String accountId = rootNode.findValue("accountId").asText();
            String region = rootNode.findValue("region").asText();

            // Create a List for alarm actions.
            List<String> alarmActions = new ArrayList<>();
            alarmActions.add("arn:aws:sns:" + region + ":" + accountId + ":" +
emailTopic);
            PutMetricAlarmRequest alarmRequest = PutMetricAlarmRequest.builder()
                    .alarmActions(alarmActions)
                    .alarmDescription("Example metric alarm")
                    .alarmName(alarmName)

.comparisonOperator(ComparisonOperator.GREATER_THAN_OR_EQUAL_TO_THRESHOLD)
                    .threshold(100.00)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .evaluationPeriods(1)
                    .period(10)
                    .statistic("Maximum")
                    .datapointsToAlarm(1)
                    .treatMissingData("ignore")
                    .build();

            cw.putMetricAlarm(alarmRequest);
            System.out.println(alarmName + " was successfully created!");
            return alarmName;

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void addMetricToDashboard(CloudWatchClient cw, String fileName,
String dashboardName) {
```

```
        try {
            PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                    .dashboardName(dashboardName)
                    .dashboardBody(readFileAsString(fileName))
                    .build();

            cw.putDashboard(dashboardRequest);
            System.out.println(dashboardName + " was successfully updated.");

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void createNewCustomMetric(CloudWatchClient cw, Double
 dataPoint) {
        try {
            Dimension dimension = Dimension.builder()
                    .name("UNIQUE_PAGES")
                    .value("URLS")
                    .build();

            // Set an Instant object.
            String time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
            Instant instant = Instant.parse(time);

            MetricDatum datum = MetricDatum.builder()
                    .metricName("PAGES_VISITED")
                    .unit(StandardUnit.NONE)
                    .value(dataPoint)
                    .timestamp(instant)
                    .dimensions(dimension)
                    .build();

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace("SITE/TRAFFIC")
                    .metricData(datum)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric
 PAGES_VISITED");
```

```
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listDashboards(CloudWatchClient cw) {
        try {
            ListDashboardsIterable listRes = cw.listDashboardsPaginator();
            listRes.stream()
                    .flatMap(r -> r.dashboardEntries().stream())
                    .forEach(entry -> {
                        System.out.println("Dashboard name is: " +
entry.dashboardName());
                        System.out.println("Dashboard ARN is: " +
entry.dashboardArn());
                    });

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createDashboardWithMetrics(CloudWatchClient cw, String
dashboardName, String fileName) {
        try {
            PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                    .dashboardName(dashboardName)
                    .dashboardBody(readFileAsString(fileName))
                    .build();

            PutDashboardResponse response = cw.putDashboard(dashboardRequest);
            System.out.println(dashboardName + " was successfully created.");
            List<DashboardValidationMessage> messages =
response.dashboardValidationMessages();
            if (messages.isEmpty()) {
                System.out.println("There are no messages in the new Dashboard");
            } else {
                for (DashboardValidationMessage message : messages) {
                    System.out.println("Message is: " + message.message());
                }
            }
```

```
        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String readFileAsString(String file) throws IOException {
        return new String(Files.readAllBytes(Paths.get(file)));
    }

    public static void getMetricStatistics(CloudWatchClient cw, String
costDateWeek) {
        try {
            Instant start = Instant.parse(costDateWeek);
            Instant endDate = Instant.now();
            Dimension dimension = Dimension.builder()
                    .name("Currency")
                    .value("USD")
                    .build();

            List<Dimension> dimensionList = new ArrayList<>();
            dimensionList.add(dimension);
            GetMetricStatisticsRequest statisticsRequest =
GetMetricStatisticsRequest.builder()
                    .metricName("EstimatedCharges")
                    .namespace("AWS/Billing")
                    .dimensions(dimensionList)
                    .statistics(Statistic.MAXIMUM)
                    .startTime(start)
                    .endTime(endDate)
                    .period(86400)
                    .build();

            GetMetricStatisticsResponse response =
cw.getMetricStatistics(statisticsRequest);
            List<Datapoint> data = response.datapoints();
            if (!data.isEmpty()) {
                for (Datapoint datapoint : data) {
                    System.out
                            .println("Timestamp: " + datapoint.timestamp() + "
Maximum value: " + datapoint.maximum());
                }
            } else {
```

```
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getAndDisplayMetricStatistics(CloudWatchClient cw, String
 nameSpace, String metVal,
            String metricOption, String date, Dimension myDimension) {
        try {
            Instant start = Instant.parse(date);
            Instant endDate = Instant.now();

            GetMetricStatisticsRequest statisticsRequest =
 GetMetricStatisticsRequest.builder()
                    .endTime(endDate)
                    .startTime(start)
                    .dimensions(myDimension)
                    .metricName(metVal)
                    .namespace(nameSpace)
                    .period(86400)
                    .statistics(Statistic.fromValue(metricOption))
                    .build();

            GetMetricStatisticsResponse response =
 cw.getMetricStatistics(statisticsRequest);
            List<Datapoint> data = response.datapoints();
            if (!data.isEmpty()) {
                for (Datapoint datapoint : data) {
                    System.out
                            .println("Timestamp: " + datapoint.timestamp() + "
 Maximum value: " + datapoint.maximum());
                }
            } else {
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }

    public static Dimension getSpecificMet(CloudWatchClient cw, String namespace)
 {
        try {
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();

            ListMetricsResponse response = cw.listMetrics(request);
            List<Metric> myList = response.metrics();
            Metric metric = myList.get(0);
            return metric.dimensions().get(0);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static ArrayList<String> listMets(CloudWatchClient cw, String
 namespace) {
        try {
            ArrayList<String> metList = new ArrayList<>();
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();

            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> metList.add(metrics.metricName()));

            return metList;

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static ArrayList<String> listNameSpaces(CloudWatchClient cw) {
```

```
        try {
            ArrayList<String> nameSpaceList = new ArrayList<>();
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .build();

            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> {
                        String data = metrics.namespace();
                        if (!nameSpaceList.contains(data)) {
                            nameSpaceList.add(data);
                        }
                    });

            return nameSpaceList;
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric
  - DescribeAnomalyDetectors
  - GetMetricData
  - GetMetricStatistics
  - GetMetricWidgetImage
  - ListMetrics

- PutAnomalyDetector
- PutDashboard
- PutMetricAlarm
- PutMetricData

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 To enable billing metrics and statistics for this example, make sure billing
 alerts are enabled for your account:
 https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics

 This Kotlin code example performs the following tasks:

 1. List available namespaces from Amazon CloudWatch. Select a namespace from the
 list.
 2. List available metrics within the selected namespace.
 3. Get statistics for the selected metric over the last day.
 4. Get CloudWatch estimated billing for the last week.
 5. Create a new CloudWatch dashboard with metrics.
 6. List dashboards using a paginator.
 7. Create a new custom metric by adding data for it.
 8. Add the custom metric to the dashboard.
 9. Create an alarm for the custom metric.
 10. Describe current alarms.
```

```
 11. Get current data for the new custom metric.
 12. Push data into the custom metric to trigger the alarm.
 13. Check the alarm state using the action DescribeAlarmsForMetric.
 14. Get alarm history for the new alarm.
 15. Add an anomaly detector for the custom metric.
 16. Describe current anomaly detectors.
 17. Get a metric image for the custom metric.
 18. Clean up the Amazon CloudWatch resources.
 */

val DASHES: String? = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <myDate> <costDateWeek> <dashboardName> <dashboardJson>
 <dashboardAdd> <settings> <metricImage>

        Where:
            myDate - The start date to use to get metric statistics. (For
 example, 2023-01-11T18:35:24.00Z.)
            costDateWeek - The start date to use to get AWS Billing and Cost
 Management statistics. (For example, 2023-01-11T18:35:24.00Z.)
            dashboardName - The name of the dashboard to create.
            dashboardJson - The location of a JSON file to use to create a
 dashboard. (See Readme file.)
            dashboardAdd - The location of a JSON file to use to update a
 dashboard. (See Readme file.)
            settings - The location of a JSON file from which various values are
 read. (See Readme file.)
            metricImage - The location of a BMP file that is used to create a
 graph.
    """

    if (args.size != 7) {
        println(usage)
        System.exit(1)
    }

    val myDate = args[0]
    val costDateWeek = args[1]
    val dashboardName = args[2]
    val dashboardJson = args[3]
    val dashboardAdd = args[4]
    val settings = args[5]
```

```
    var metricImage = args[6]
    val dataPoint = "10.0".toDouble()
    val inOb = Scanner(System.`in`)

    println(DASHES)
    println("Welcome to the Amazon CloudWatch example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. List at least five available unique namespaces from Amazon
 CloudWatch. Select a CloudWatch namespace from the list.")
    val list: ArrayList<String> = listNameSpaces()
    for (z in 0..4) {
        println("    ${z + 1}. ${list[z]}")
    }

    var selectedNamespace: String
    var selectedMetrics = ""
    var num = inOb.nextLine().toInt()
    println("You selected $num")

    if (1 <= num && num <= 5) {
        selectedNamespace = list[num - 1]
    } else {
        println("You did not select a valid option.")
        exitProcess(1)
    }
    println("You selected $selectedNamespace")
    println(DASHES)

    println(DASHES)
    println("2. List available metrics within the selected namespace and select
 one from the list.")
    val metList = listMets(selectedNamespace)
    for (z in 0..4) {
        println("    ${ z + 1}. ${metList?.get(z)}")
    }
    num = inOb.nextLine().toInt()
    if (1 <= num && num <= 5) {
        selectedMetrics = metList!![num - 1]
    } else {
        println("You did not select a valid option.")
        System.exit(1)
    }
```

```
    println("You selected $selectedMetrics")
    val myDimension = getSpecificMet(selectedNamespace)
    if (myDimension == null) {
        println("Error - Dimension is null")
        exitProcess(1)
    }
    println(DASHES)

    println(DASHES)
    println("3. Get statistics for the selected metric over the last day.")
    val metricOption: String
    val statTypes = ArrayList<String>()
    statTypes.add("SampleCount")
    statTypes.add("Average")
    statTypes.add("Sum")
    statTypes.add("Minimum")
    statTypes.add("Maximum")

    for (t in 0..4) {
        println("    ${t + 1}. ${statTypes[t]}")
    }
    println("Select a metric statistic by entering a number from the preceding
list:")
    num = inOb.nextLine().toInt()
    if (1 <= num && num <= 5) {
        metricOption = statTypes[num - 1]
    } else {
        println("You did not select a valid option.")
        exitProcess(1)
    }
    println("You selected $metricOption")
    getAndDisplayMetricStatistics(selectedNamespace, selectedMetrics,
metricOption, myDate, myDimension)
    println(DASHES)

    println(DASHES)
    println("4. Get CloudWatch estimated billing for the last week.")
    getMetricStatistics(costDateWeek)
    println(DASHES)

    println(DASHES)
    println("5. Create a new CloudWatch dashboard with metrics.")
    createDashboardWithMetrics(dashboardName, dashboardJson)
    println(DASHES)
```

```
    println(DASHES)
    println("6. List dashboards using a paginator.")
    listDashboards()
    println(DASHES)

    println(DASHES)
    println("7. Create a new custom metric by adding data to it.")
    createNewCustomMetric(dataPoint)
    println(DASHES)

    println(DASHES)
    println("8. Add an additional metric to the dashboard.")
    addMetricToDashboard(dashboardAdd, dashboardName)
    println(DASHES)

    println(DASHES)
    println("9. Create an alarm for the custom metric.")
    val alarmName: String = createAlarm(settings)
    println(DASHES)

    println(DASHES)
    println("10. Describe 10 current alarms.")
    describeAlarms()
    println(DASHES)

    println(DASHES)
    println("11. Get current data for the new custom metric.")
    getCustomMetricData(settings)
    println(DASHES)

    println(DASHES)
    println("12. Push data into the custom metric to trigger the alarm.")
    addMetricDataForAlarm(settings)
    println(DASHES)

    println(DASHES)
    println("13. Check the alarm state using the action
 DescribeAlarmsForMetric.")
    checkForMetricAlarm(settings)
    println(DASHES)

    println(DASHES)
    println("14. Get alarm history for the new alarm.")
```

```
    getAlarmHistory(settings, myDate)
    println(DASHES)

    println(DASHES)
    println("15. Add an anomaly detector for the custom metric.")
    addAnomalyDetector(settings)
    println(DASHES)

    println(DASHES)
    println("16. Describe current anomaly detectors.")
    describeAnomalyDetectors(settings)
    println(DASHES)

    println(DASHES)
    println("17. Get a metric image for the custom metric.")
    getAndOpenMetricImage(metricImage)
    println(DASHES)

    println(DASHES)
    println("18. Clean up the Amazon CloudWatch resources.")
    deleteDashboard(dashboardName)
    deleteAlarm(alarmName)
    deleteAnomalyDetector(settings)
    println(DASHES)

    println(DASHES)
    println("The Amazon CloudWatch example scenario is complete.")
    println(DASHES)
}

suspend fun deleteAnomalyDetector(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }
```

```
    val request = DeleteAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAnomalyDetector(request)
        println("Successfully deleted the Anomaly Detector.")
    }
}

suspend fun deleteAlarm(alarmNameVal: String) {
    val request = DeleteAlarmsRequest {
        alarmNames = listOf(alarmNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAlarms(request)
        println("Successfully deleted alarm $alarmNameVal")
    }
}

suspend fun deleteDashboard(dashboardName: String) {
    val dashboardsRequest = DeleteDashboardsRequest {
        dashboardNames = listOf(dashboardName)
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteDashboards(dashboardsRequest)
        println("$dashboardName was successfully deleted.")
    }
}

suspend fun getAndOpenMetricImage(fileName: String) {
    println("Getting Image data for custom metric.")
    val myJSON = """{
        "title": "Example Metric Graph",
        "view": "timeSeries",
        "stacked ": false,
        "period": 10,
        "width": 1400,
        "height": 600,
        "metrics": [
            [
            "AWS/Billing",
            "EstimatedCharges",
```

```
            "Currency",
            "USD"
            ]
        ]
        }"""

    val imageRequest = GetMetricWidgetImageRequest {
        metricWidget = myJSON
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricWidgetImage(imageRequest)
        val bytes = response.metricWidgetImage
        if (bytes != null) {
            File(fileName).writeBytes(bytes)
        }
    }
    println("You have successfully written data to $fileName")
}

suspend fun describeAnomalyDetectors(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val detectorsRequest = DescribeAnomalyDetectorsRequest {
        maxResults = 10
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAnomalyDetectors(detectorsRequest)
        response.anomalyDetectors?.forEach { detector ->
            println("Metric name:
 ${detector.singleMetricAnomalyDetector?.metricName}")
            println("State: ${detector.stateValue}")
        }
    }
}

suspend fun addAnomalyDetector(fileName: String?) {
```

```
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val anomalyDetectorRequest = PutAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putAnomalyDetector(anomalyDetectorRequest)
        println("Added anomaly detector for metric $customMetricName.")
    }
}

suspend fun getAlarmHistory(fileName: String, date: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
    val start = Instant.parse(date)
    val endDateVal = Instant.now()

    val historyRequest = DescribeAlarmHistoryRequest {
        startDate = aws.smithy.kotlin.runtime.time.Instant(start)
        endDate = aws.smithy.kotlin.runtime.time.Instant(endDateVal)
        alarmName = alarmNameVal
        historyItemType = HistoryItemType.Action
    }

    CloudWatchClient { credentialsProvider = EnvironmentCredentialsProvider();
 region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarmHistory(historyRequest)
        val historyItems = response.alarmHistoryItems
        if (historyItems != null) {
            if (historyItems.isEmpty()) {
```

```
                println("No alarm history data found for $alarmNameVal.")
            } else {
                for (item in historyItems) {
                    println("History summary ${item.historySummary}")
                    println("Time stamp: ${item.timestamp}")
                }
            }
        }
    }
}

suspend fun checkForMetricAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    var hasAlarm = false
    var retries = 10

    val metricRequest = DescribeAlarmsForMetricRequest {
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        while (!hasAlarm && retries > 0) {
            val response = cwClient.describeAlarmsForMetric(metricRequest)
            if (response.metricAlarms?.count()!! > 0) {
                hasAlarm = true
            }
            retries--
            delay(20000)
            println(".")
        }
        if (!hasAlarm) println("No Alarm state found for $customMetricName after
 10 retries.") else println("Alarm state found for $customMetricName.")
    }
}

suspend fun addMetricDataForAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
```

```
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1001.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val datum2 = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1002.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val metricDataList = ArrayList<MetricDatum>()
    metricDataList.add(datum)
    metricDataList.add(datum2)

    val request = PutMetricDataRequest {
        namespace = customMetricNamespace
        metricData = metricDataList
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric $customMetricName")
    }
}

suspend fun getCustomMetricData(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
```

```
    // Set the date.
    val nowDate = Instant.now()
    val hours: Long = 1
    val minutes: Long = 30
    val date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(
        minutes,
        ChronoUnit.MINUTES
    )

    val met = Metric {
        metricName = customMetricName
        namespace = customMetricNamespace
    }

    val metStat = MetricStat {
        stat = "Maximum"
        period = 1
        metric = met
    }

    val dataQUery = MetricDataQuery {
        metricStat = metStat
        id = "foo2"
        returnData = true
    }

    val dq = ArrayList<MetricDataQuery>()
    dq.add(dataQUery)
    val getMetReq = GetMetricDataRequest {
        maxDatapoints = 10
        scanBy = ScanBy.TimestampDescending
        startTime = aws.smithy.kotlin.runtime.time.Instant(nowDate)
        endTime = aws.smithy.kotlin.runtime.time.Instant(date2)
        metricDataQueries = dq
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricData(getMetReq)
        response.metricDataResults?.forEach { item ->
            println("The label is ${item.label}")
            println("The status code is ${item.statusCode}")
        }
    }
```

```
}

suspend fun describeAlarms() {
    val typeList = ArrayList<AlarmType>()
    typeList.add(AlarmType.MetricAlarm)
    val alarmsRequest = DescribeAlarmsRequest {
        alarmTypes = typeList
        maxRecords = 10
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarms(alarmsRequest)
        response.metricAlarms?.forEach { alarm ->
            println("Alarm name: ${alarm.alarmName}")
            println("Alarm description: ${alarm.alarmDescription}")
        }
    }
}

suspend fun createAlarm(fileName: String): String {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode: JsonNode = ObjectMapper().readTree(parser)
    val customMetricNamespace =
 rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
    val emailTopic = rootNode.findValue("emailTopic").asText()
    val accountId = rootNode.findValue("accountId").asText()
    val region2 = rootNode.findValue("region").asText()

    // Create a List for alarm actions.
    val alarmActionObs: MutableList<String> = ArrayList()
    alarmActionObs.add("arn:aws:sns:$region2:$accountId:$emailTopic")
    val alarmRequest = PutMetricAlarmRequest {
        alarmActions = alarmActionObs
        alarmDescription = "Example metric alarm"
        alarmName = alarmNameVal
        comparisonOperator = ComparisonOperator.GreaterThanOrEqualToThreshold
        threshold = 100.00
        metricName = customMetricName
        namespace = customMetricNamespace
        evaluationPeriods = 1
        period = 10
```

```
        statistic = Statistic.Maximum
        datapointsToAlarm = 1
        treatMissingData = "ignore"
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricAlarm(alarmRequest)
        println("$alarmNameVal was successfully created!")
        return alarmNameVal
    }
}

suspend fun addMetricToDashboard(fileNameVal: String, dashboardNameVal: String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully updated.")
    }
}

suspend fun createNewCustomMetric(dataPoint: Double) {
    val dimension = Dimension {
        name = "UNIQUE_PAGES"
        value = "URLS"
    }

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = "PAGES_VISITED"
        unit = StandardUnit.None
        value = dataPoint
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
        dimensions = listOf(dimension)
    }

    val request = PutMetricDataRequest {
        namespace = "SITE/TRAFFIC"
```

```
        metricData = listOf(datum)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric PAGES_VISITED")
    }
}

suspend fun listDashboards() {
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listDashboardsPaginated({})
            .transform { it.dashboardEntries?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name is ${obj.dashboardName}")
                println("Dashboard ARN is ${obj.dashboardArn}")
            }
    }
}

suspend fun createDashboardWithMetrics(dashboardNameVal: String, fileNameVal:
 String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully created.")
        val messages = response.dashboardValidationMessages
        if (messages != null) {
            if (messages.isEmpty()) {
                println("There are no messages in the new Dashboard")
            } else {
                for (message in messages) {
                    println("Message is: ${message.message}")
                }
            }
        }
    }
}

fun readFileAsString(file: String): String {
```

```
    return String(Files.readAllBytes(Paths.get(file)))
}

suspend fun getMetricStatistics(costDateWeek: String?) {
    val start = Instant.parse(costDateWeek)
    val endDate = Instant.now()
    val dimension = Dimension {
        name = "Currency"
        value = "USD"
    }

    val dimensionList: MutableList<Dimension> = ArrayList()
    dimensionList.add(dimension)

    val statisticsRequest = GetMetricStatisticsRequest {
        metricName = "EstimatedCharges"
        namespace = "AWS/Billing"
        dimensions = dimensionList
        statistics = listOf(Statistic.Maximum)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        period = 86400
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data: List<Datapoint>? = response.datapoints
        if (data != null) {
            if (!data.isEmpty()) {
                for (datapoint in data) {
                    println("Timestamp:  ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}

suspend fun getAndDisplayMetricStatistics(nameSpaceVal: String, metVal: String,
 metricOption: String, date: String, myDimension: Dimension) {
    val start = Instant.parse(date)
    val endDate = Instant.now()
    val statisticsRequest = GetMetricStatisticsRequest {
```

```
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        dimensions = listOf(myDimension)
        metricName = metVal
        namespace = nameSpaceVal
        period = 86400
        statistics = listOf(Statistic.fromValue(metricOption))
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data = response.datapoints
        if (data != null) {
            if (data.isNotEmpty()) {
                for (datapoint in data) {
                    println("Timestamp: ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}

suspend fun listMets(namespaceVal: String?): ArrayList<String>? {
    val metList = ArrayList<String>()
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val reponse = cwClient.listMetrics(request)
        reponse.metrics?.forEach { metrics ->
            val data = metrics.metricName
            if (!metList.contains(data)) {
                metList.add(data!!)
            }
        }
    }
    return metList
}

suspend fun getSpecificMet(namespaceVal: String?): Dimension? {
    val request = ListMetricsRequest {
```

```
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.listMetrics(request)
        val myList = response.metrics
        if (myList != null) {
            return myList[0].dimensions?.get(0)
        }
    }
    return null
}

suspend fun listNameSpaces(): ArrayList<String> {
    val nameSpaceList = ArrayList<String>()
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.listMetrics(ListMetricsRequest {})
        response.metrics?.forEach { metrics ->
            val data = metrics.namespace
            if (!nameSpaceList.contains(data)) {
                nameSpaceList.add(data!!)
            }
        }
    }
    return nameSpaceList
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric
  - DescribeAnomalyDetectors
  - GetMetricData
  - GetMetricStatistics
  - GetMetricWidgetImage

- ListMetrics
- PutAnomalyDetector
- PutDashboard
- PutMetricAlarm
- PutMetricData

Gerencie CloudWatch métricas e alarmes usando um SDK AWS

O código de exemplo a seguir mostra como:

- Crie um alarme para observar uma CloudWatch métrica.
- Inserir dados em uma métrica e acionar o alarme.
- Obtenha dados do alarme.
- Exclua o alarme.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as CloudWatch operações.

```
from datetime import datetime, timedelta
import logging
from pprint import pprint
import random
import time
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
```

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data_set(self, namespace, name, timestamp, unit, data_set):
        """
        Sends a set of data to CloudWatch for a metric. All of the data in the
 set
        have the same timestamp and unit.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param timestamp: The UTC timestamp for the metric.
        :param unit: The unit of the metric.
        :param data_set: The set of data to send. This set is a dictionary that
                         contains a list of values and a list of corresponding
 counts.
                         The value and count lists must be the same length.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[
                    {
                        "MetricName": name,
                        "Timestamp": timestamp,
                        "Values": data_set["values"],
                        "Counts": data_set["counts"],
                        "Unit": unit,
                    }
                ],
            )
            logger.info("Put data set for metric %s.%s.", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data set for metric %s.%s.",
 namespace, name)
            raise
```

```
    def create_metric_alarm(
        self,
        metric_namespace,
        metric_name,
        alarm_name,
        stat_type,
        period,
        eval_periods,
        threshold,
        comparison_op,
    ):
        """
        Creates an alarm that watches a metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :param alarm_name: The name of the alarm.
        :param stat_type: The type of statistic the alarm watches.
        :param period: The period in which metric data are grouped to calculate
                       statistics.
        :param eval_periods: The number of periods that the metric must be over
the
                             alarm threshold before the alarm is set into an
alarmed
                             state.
        :param threshold: The threshold value to compare against the metric
statistic.
        :param comparison_op: The comparison operation used to compare the
threshold
                              against the metric.
        :return: The newly created alarm.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace,
metric_name)
            alarm = metric.put_alarm(
                AlarmName=alarm_name,
                Statistic=stat_type,
                Period=period,
                EvaluationPeriods=eval_periods,
                Threshold=threshold,
                ComparisonOperator=comparison_op,
```

```
            )
            logger.info(
                "Added alarm %s to track metric %s.%s.",
                alarm_name,
                metric_namespace,
                metric_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't add alarm %s to metric %s.%s",
                alarm_name,
                metric_namespace,
                metric_name,
            )
            raise
        else:
            return alarm


    def put_metric_data(self, namespace, name, value, unit):
        """
        Sends a single data value to CloudWatch for a metric. This metric is
given
        a timestamp of the current UTC time.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param value: The value of the metric.
        :param unit: The unit of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[{"MetricName": name, "Value": value, "Unit": unit}],
            )
            logger.info("Put data for metric %s.%s", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data for metric %s.%s", namespace,
name)
            raise
```

```
    def get_metric_statistics(self, namespace, name, start, end, period,
stat_types):
        """
        Gets statistics for a metric within a specified time span. Metrics are
grouped
        into the specified period.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param start: The UTC start time of the time span to retrieve.
        :param end: The UTC end time of the time span to retrieve.
        :param period: The period, in seconds, in which to group metrics. The
period
                       must match the granularity of the metric, which depends on
                       the metric's age. For example, metrics that are older than
                       three hours have a one-minute granularity, so the period
must
                       be at least 60 and must be a multiple of 60.
        :param stat_types: The type of statistics to retrieve, such as average
value
                           or maximum value.
        :return: The retrieved statistics for the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            stats = metric.get_statistics(
                StartTime=start, EndTime=end, Period=period,
Statistics=stat_types
            )
            logger.info(
                "Got %s statistics for %s.", len(stats["Datapoints"]),
stats["Label"]
            )
        except ClientError:
            logger.exception("Couldn't get statistics for %s.%s.", namespace,
name)
            raise
        else:
            return stats


    def get_metric_alarms(self, metric_namespace, metric_name):
        """
        Gets the alarms that are currently watching the specified metric.
```

```
        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :returns: An iterator that yields the alarms.
        """
        metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
        alarm_iter = metric.alarms.all()
        logger.info("Got alarms for metric %s.%s.", metric_namespace,
metric_name)
        return alarm_iter


    def delete_metric_alarms(self, metric_namespace, metric_name):
        """
        Deletes all of the alarms that are currently watching the specified
metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace,
metric_name)
            metric.alarms.delete()
            logger.info(
                "Deleted alarms for metric %s.%s.", metric_namespace, metric_name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete alarms for metric %s.%s.",
                metric_namespace,
                metric_name,
            )
            raise
```

Use a classe criada para colocar dados em uma métrica, acionar um alarme que observa a métrica e obter dados do alarme.

```
def usage_demo():
    print("-" * 88)
```

```
    print("Welcome to the Amazon CloudWatch metrics and alarms demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    cw_wrapper = CloudWatchWrapper(boto3.resource("cloudwatch"))

    minutes = 20
    metric_namespace = "doc-example-metric"
    metric_name = "page_views"
    start = datetime.utcnow() - timedelta(minutes=minutes)
    print(
        f"Putting data into metric {metric_namespace}.{metric_name} spanning the
"
        f"last {minutes} minutes."
    )
    for offset in range(0, minutes):
        stamp = start + timedelta(minutes=offset)
        cw_wrapper.put_metric_data_set(
            metric_namespace,
            metric_name,
            stamp,
            "Count",
            {
                "values": [
                    random.randint(bound, bound * 2)
                    for bound in range(offset + 1, offset + 11)
                ],
                "counts": [random.randint(1, offset + 1) for _ in range(10)],
            },
        )

    alarm_name = "high_page_views"
    period = 60
    eval_periods = 2
    print(f"Creating alarm {alarm_name} for metric {metric_name}.")
    alarm = cw_wrapper.create_metric_alarm(
        metric_namespace,
        metric_name,
        alarm_name,
        "Maximum",
        period,
        eval_periods,
        100,
```

```
        "GreaterThanThreshold",
    )
    print(f"Alarm ARN is {alarm.alarm_arn}.")
    print(f"Current alarm state is: {alarm.state_value}.")

    print(
        f"Sending data to trigger the alarm. This requires data over the
threshold "
        f"for {eval_periods} periods of {period} seconds each."
    )
    while alarm.state_value == "INSUFFICIENT_DATA":
        print("Sending data for the metric.")
        cw_wrapper.put_metric_data(
            metric_namespace, metric_name, random.randint(100, 200), "Count"
        )
        alarm.load()
        print(f"Current alarm state is: {alarm.state_value}.")
        if alarm.state_value == "INSUFFICIENT_DATA":
            print(f"Waiting for {period} seconds...")
            time.sleep(period)
        else:
            print("Wait for a minute for eventual consistency of metric data.")
            time.sleep(period)
            if alarm.state_value == "OK":
                alarm.load()
                print(f"Current alarm state is: {alarm.state_value}.")

    print(
        f"Getting data for metric {metric_namespace}.{metric_name} during
timespan "
        f"of {start} to {datetime.utcnow()} (times are UTC)."
    )
    stats = cw_wrapper.get_metric_statistics(
        metric_namespace,
        metric_name,
        start,
        datetime.utcnow(),
        60,
        ["Average", "Minimum", "Maximum"],
    )
    print(
        f"Got {len(stats['Datapoints'])} data points for metric "
        f"{metric_namespace}.{metric_name}."
    )
```

```
    pprint(sorted(stats["Datapoints"], key=lambda x: x["Timestamp"]))

    print(f"Getting alarms for metric {metric_name}.")
    alarms = cw_wrapper.get_metric_alarms(metric_namespace, metric_name)
    for alarm in alarms:
        print(f"Alarm {alarm.name} is currently in state {alarm.state_value}.")

    print(f"Deleting alarms for metric {metric_name}.")
    cw_wrapper.delete_metric_alarms(metric_namespace, metric_name)

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeleteAlarms
  - DescribeAlarmsForMetric
  - DisableAlarmActions
  - EnableAlarmActions
  - GetMetricStatistics
  - ListMetrics
  - PutMetricAlarm
  - PutMetricData

Exemplos de código para CloudWatch eventos usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Events com um kit AWS de desenvolvimento de software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- CloudWatch Guia do usuário de eventos — Mais informações sobre CloudWatch eventos.
- CloudWatch Referência da API de eventos — Detalhes sobre todas as ações de CloudWatch eventos disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para CloudWatch eventos usando AWS SDKs
  - Adicionar um destino usando um AWS SDK
  - Crie uma regra de CloudWatch eventos agendados usando um AWS SDK
  - Envie CloudWatch eventos de eventos usando um AWS SDK

Ações para CloudWatch eventos usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Events com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos

- Adicionar um destino usando um AWS SDK
- Crie uma regra de CloudWatch eventos agendados usando um AWS SDK
- Envie CloudWatch eventos de eventos usando um AWS SDK

Adicionar um destino usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar um alvo a um evento da Amazon CloudWatch Events.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutTargetsRequest;
import software.amazon.awssdk.services.cloudwatchevents.model.Target;

/**
 * To run this Java V2 code example, ensure that you have setup your development
 * environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutTargets {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <ruleName> <functionArn> <targetId>\s

                Where:
                  ruleName - A rule name (for example, myrule).
                  functionArn - An AWS Lambda function ARN (for example,
 arn:aws:lambda:us-west-2:xxxxxx047983:function:lamda1).
                  targetId - A target id value.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String ruleName = args[0];
        String functionArn = args[1];
        String targetId = args[2];
        CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
                .build();

        putCWTargets(cwe, ruleName, functionArn, targetId);
        cwe.close();
    }

    public static void putCWTargets(CloudWatchEventsClient cwe, String ruleName,
 String functionArn, String targetId) {
        try {
            Target target = Target.builder()
                    .arn(functionArn)
                    .id(targetId)
                    .build();

            PutTargetsRequest request = PutTargetsRequest.builder()
                    .targets(target)
                    .rule(ruleName)
                    .build();

            cwe.putTargets(request);
            System.out.printf(
                    "Successfully created CloudWatch events target for rule %s",
                    ruleName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutTargetsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutTargetsCommand({
    // The name of the Amazon CloudWatch Events rule.
    Rule: process.env.CLOUDWATCH_EVENTS_RULE,

    // The targets to add to the rule.
    Targets: [
      {
        Arn: process.env.CLOUDWATCH_EVENTS_TARGET_ARN,
        // The ID of the target. Choose a unique ID for each target.
        Id: process.env.CLOUDWATCH_EVENTS_TARGET_ID,
      },
    ],
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myCloudWatchEventsTarget",
    },
  ],
};

cwevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
```

```
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Crie uma regra de CloudWatch eventos agendados usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma regra programada do Amazon CloudWatch Events.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutRuleRequest;
import software.amazon.awssdk.services.cloudwatchevents.model.PutRuleResponse;
import software.amazon.awssdk.services.cloudwatchevents.model.RuleState;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutRule {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                  <ruleName> roleArn>\s

                Where:
                  ruleName - A rule name (for example, myrule).
                  roleArn - A role ARN value (for example,
arn:aws:iam::xxxxxx047983:user/MyUser).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String ruleName = args[0];
        String roleArn = args[1];
        CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
                .build();

        putCWRule(cwe, ruleName, roleArn);
        cwe.close();
    }

    public static void putCWRule(CloudWatchEventsClient cwe, String ruleName,
String roleArn) {
        try {
            PutRuleRequest request = PutRuleRequest.builder()
                    .name(ruleName)
                    .roleArn(roleArn)
                    .scheduleExpression("rate(5 minutes)")
                    .state(RuleState.ENABLED)
                    .build();

            PutRuleResponse response = cwe.putRule(request);
            System.out.printf(
                    "Successfully created CloudWatch events rule %s with arn %s",
                    roleArn, response.ruleArn());

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutRuleCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  // Request parameters for PutRule.
  // https://docs.aws.amazon.com/eventbridge/latest/APIReference/
API_PutRule.html#API_PutRule_RequestParameters
  const command = new PutRuleCommand({
    Name: process.env.CLOUDWATCH_EVENTS_RULE,

    // The event pattern for the rule.
    //  Example: {"source": ["my.app"]}
    EventPattern: process.env.CLOUDWATCH_EVENTS_RULE_PATTERN,

    // The state of the rule. Valid values: ENABLED, DISABLED
    State: "ENABLED",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

cwevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
```

```
    console.log("Success", data.RuleArn);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Envie CloudWatch eventos de eventos usando um AWS SDK

Os exemplos de código a seguir mostram como enviar CloudWatch eventos da Amazon Events.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutEventsRequest;
import
 software.amazon.awssdk.services.cloudwatchevents.model.PutEventsRequestEntry;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutEvents {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                   <resourceArn>

                Where:
                   resourceArn - An Amazon Resource Name (ARN) related to the
events.
                """;

       if (args.length != 1) {
           System.out.println(usage);
           System.exit(1);
       }

       String resourceArn = args[0];
       CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
               .build();

       putCWEvents(cwe, resourceArn);
       cwe.close();
   }

   public static void putCWEvents(CloudWatchEventsClient cwe, String
resourceArn) {
       try {
           final String EVENT_DETAILS = "{ \"key1\": \"value1\", \"key2\":
\"value2\" }";

           PutEventsRequestEntry requestEntry = PutEventsRequestEntry.builder()
                   .detail(EVENT_DETAILS)
                   .detailType("sampleSubmitted")
                   .resources(resourceArn)
                   .source("aws-sdk-java-cloudwatch-example")
                   .build();

           PutEventsRequest request = PutEventsRequest.builder()
                   .entries(requestEntry)
                   .build();

           cwe.putEvents(request);
           System.out.println("Successfully put CloudWatch event");

       } catch (CloudWatchException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutEventsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutEventsCommand({
    // The list of events to send to Amazon CloudWatch Events.
    Entries: [
      {
        // The name of the application or service that is sending the event.
        Source: "my.app",

        // The name of the event that is being sent.
        DetailType: "My Custom Event",

        // The data that is sent with the event.
        Detail: JSON.stringify({ timeOfEvent: new Date().toISOString() }),
      },
    ],
  });

  try {
    return await client.send(command);
```

```
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
```

```
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
    },
  ],
};

cwevents.putEvents(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

Exemplos de código para CloudWatch registros usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Logs com um kit AWS de desenvolvimento de software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- CloudWatch Guia do usuário de registros — Mais informações sobre CloudWatch registros.
- CloudWatch Referência da API de registros — detalhes sobre todas as ações de CloudWatch registros disponíveis.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para CloudWatch registros usando AWS SDKs
  - Associe uma AWS KMS chave a um grupo de CloudWatch registros de registros usando um AWS SDK
  - Cancelar uma tarefa de exportação de CloudWatch registros usando um AWS SDK
  - Crie um grupo CloudWatch de registros de registros usando um AWS SDK
  - Crie um stream CloudWatch de registros de registros usando um AWS SDK
  - Crie um filtro de assinatura do CloudWatch Logs usando um AWS SDK
  - Crie uma tarefa CloudWatch de exportação de registros usando um AWS SDK
  - Excluir um grupo de CloudWatch registros de registros usando um AWS SDK
  - Excluir um filtro CloudWatch de assinatura do Logs usando um AWS SDK
  - Descrever CloudWatch os filtros de assinatura do Logs usando um AWS SDK
  - Descrever CloudWatch as tarefas de exportação de registros usando um AWS SDK
  - Descrever grupos de CloudWatch registros usando um AWS SDK
  - Obtenha os resultados de uma consulta de CloudWatch registros usando um AWS SDK
  - Iniciar uma sessão do Live Tail usando um SDK da AWS
  - Iniciar uma consulta de CloudWatch registros usando um AWS SDK
- Cenários para CloudWatch registros usando AWS SDKs
  - Use CloudWatch Logs para executar uma consulta grande
- Exemplos de vários serviços para CloudWatch registros usando AWS SDKs
  - Usar eventos programados para chamar uma função do Lambda

Ações para CloudWatch registros usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Logs com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para CloudWatch registros usando AWS SDKs.

Exemplos

- Associe uma AWS KMS chave a um grupo de CloudWatch registros de registros usando um AWS SDK
- Cancelar uma tarefa de exportação de CloudWatch registros usando um AWS SDK
- Crie um grupo CloudWatch de registros de registros usando um AWS SDK
- Crie um stream CloudWatch de registros de registros usando um AWS SDK
- Crie um filtro de assinatura do CloudWatch Logs usando um AWS SDK
- Crie uma tarefa CloudWatch de exportação de registros usando um AWS SDK
- Excluir um grupo de CloudWatch registros de registros usando um AWS SDK
- Excluir um filtro CloudWatch de assinatura do Logs usando um AWS SDK
- Descrever CloudWatch os filtros de assinatura do Logs usando um AWS SDK
- Descrever CloudWatch as tarefas de exportação de registros usando um AWS SDK
- Descrever grupos de CloudWatch registros usando um AWS SDK
- Obtenha os resultados de uma consulta de CloudWatch registros usando um AWS SDK
- Iniciar uma sessão do Live Tail usando um SDK da AWS
- Iniciar uma consulta de CloudWatch registros usando um AWS SDK

Associe uma AWS KMS chave a um grupo de CloudWatch registros de registros usando um AWS SDK

O exemplo de código a seguir mostra como associar uma AWS KMS chave a um grupo de CloudWatch registros de registros existente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.CloudWatchLogs;
    using Amazon.CloudWatchLogs.Model;

    /// <summary>
    /// Shows how to associate an AWS Key Management Service (AWS KMS) key with
    /// an Amazon CloudWatch Logs log group.
    /// </summary>
    public class AssociateKmsKey
    {
        public static async Task Main()
        {
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();

            string kmsKeyId = "arn:aws:kms:us-west-2:<account-
number>:key/7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";
            string groupName = "cloudwatchlogs-example-loggroup";

            var request = new AssociateKmsKeyRequest
            {
                KmsKeyId = kmsKeyId,
                LogGroupName = groupName,
            };

            var response = await client.AssociateKmsKeyAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
```

```
            {
                Console.WriteLine($"Successfully associated KMS key ID:
{kmsKeyId} with log group: {groupName}.");
            }
            else
            {
                Console.WriteLine("Could not make the association between:
{kmsKeyId} and {groupName}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte AssociateKmsKeya Referência AWS SDK for .NET da API.

Cancelar uma tarefa de exportação de CloudWatch registros usando um AWS SDK

O exemplo de código a seguir mostra como cancelar uma tarefa existente de exportação de CloudWatch registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to cancel an Amazon CloudWatch Logs export task.
/// </summary>
public class CancelExportTask
```

```
    {
        public static async Task Main()
        {
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();
            string taskId = "exampleTaskId";

            var request = new CancelExportTaskRequest
            {
                TaskId = taskId,
            };

            var response = await client.CancelExportTaskAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{taskId} successfully canceled.");
            }
            else
            {
                Console.WriteLine($"{taskId} could not be canceled.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CancelExportTaska Referência AWS SDK for .NET da API.

Crie um grupo CloudWatch de registros de registros usando um AWS SDK

Os exemplos de código a seguir mostram como criar um novo grupo de CloudWatch registros de registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to create an Amazon CloudWatch Logs log group.
/// </summary>
public class CreateLogGroup
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();

        string logGroupName = "cloudwatchlogs-example-loggroup";

        var request = new CreateLogGroupRequest
        {
            LogGroupName = logGroupName,
        };

        var response = await client.CreateLogGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"Successfully create log group with ID:
{logGroupName}.");
        }
```

```
            else
            {
                Console.WriteLine("Could not create log group.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateLogGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando cria um grupo de logs chamado `my-logs`:

```
aws logs create-log-group --log-group-name my-logs
```

- Para obter detalhes da API, consulte CreateLogGroupem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateLogGroupCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new CreateLogGroupCommand({
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
```

```
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte CreateLogGroupa Referência AWS SDK for JavaScript da API.

Crie um stream CloudWatch de registros de registros usando um AWS SDK

Os exemplos de código a seguir mostram como criar um novo stream de CloudWatch registros de registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.CloudWatchLogs;
    using Amazon.CloudWatchLogs.Model;

    /// <summary>
    /// Shows how to create an Amazon CloudWatch Logs stream for a CloudWatch
    /// log group.
    /// </summary>
    public class CreateLogStream
    {
```

```
        public static async Task Main()
        {
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();
            string logGroupName = "cloudwatchlogs-example-loggroup";
            string logStreamName = "cloudwatchlogs-example-logstream";

            var request = new CreateLogStreamRequest
            {
                LogGroupName = logGroupName,
                LogStreamName = logStreamName,
            };

            var response = await client.CreateLogStreamAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{logStreamName} successfully created for
 {logGroupName}.");
            }
            else
            {
                Console.WriteLine("Could not create stream.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateLogStreama Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando cria um fluxo de logs `20150601` no grupo de logs `my-logs`:

```
aws logs create-log-stream --log-group-name my-logs --log-stream-name 20150601
```

- Para obter detalhes da API, consulte CreateLogStreamem Referência de AWS CLI Comandos.

Crie um filtro de assinatura do CloudWatch Logs usando um AWS SDK

Os exemplos de código a seguir mostram como criar um filtro de assinatura do Amazon CloudWatch Logs.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/PutSubscriptionFilterRequest.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Crie o filtro de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::PutSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetFilterPattern(filter_pattern);
        request.SetLogGroupName(log_group);
        request.SetDestinationArn(dest_arn);
        auto outcome = cwl.PutSubscriptionFilter(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch logs subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
```

```
        }
        else
        {
            std::cout << "Successfully created CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.CloudWatchLogsException;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.PutSubscriptionFilterRequest;

/**
 * Before running this code example, you need to grant permission to CloudWatch
 * Logs the right to execute your Lambda function.
 * To perform this task, you can use this CLI command:
 *
 * aws lambda add-permission --function-name "lamda1" --statement-id "lamda1"
 * --principal "logs.us-west-2.amazonaws.com" --action "lambda:InvokeFunction"
 * --source-arn "arn:aws:logs:us-west-2:111111111111:log-group:testgroup:*"
 * --source-account "111111111111"
 *
 * Make sure you replace the function name with your function name and replace
 * '111111111111' with your account details.
 * For more information, see "Subscription Filters with AWS Lambda" in the
```

```
 * Amazon CloudWatch Logs Guide.
 *
 *
 * Also, before running this Java V2 code example,set up your development
 * environment,including your credentials.
 *
 * For more information,see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 */

public class PutSubscriptionFilter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <filter> <pattern> <logGroup> <functionArn>\s

                Where:
                  filter - A filter name (for example, myfilter).
                  pattern - A filter pattern (for example, ERROR).
                  logGroup - A log group name (testgroup).
                  functionArn - An AWS Lambda function ARN (for example,
 arn:aws:lambda:us-west-2:111111111111:function:lambda1) .
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String filter = args[0];
        String pattern = args[1];
        String logGroup = args[2];
        String functionArn = args[3];
        Region region = Region.US_WEST_2;
        CloudWatchLogsClient cwl = CloudWatchLogsClient.builder()
                .region(region)
                .build();

        putSubFilters(cwl, filter, pattern, logGroup, functionArn);
        cwl.close();
```

```
    }

    public static void putSubFilters(CloudWatchLogsClient cwl,
            String filter,
            String pattern,
            String logGroup,
            String functionArn) {

        try {
            PutSubscriptionFilterRequest request =
 PutSubscriptionFilterRequest.builder()
                    .filterName(filter)
                    .filterPattern(pattern)
                    .logGroupName(logGroup)
                    .destinationArn(functionArn)
                    .build();

            cwl.putSubscriptionFilter(request);
            System.out.printf(
                    "Successfully created CloudWatch logs subscription filter
 %s",
                    filter);

        } catch (CloudWatchLogsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { PutSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutSubscriptionFilterCommand({
    // An ARN of a same-account Kinesis stream, Kinesis Firehose
    // delivery stream, or Lambda function.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
SubscriptionFilters.html
    destinationArn: process.env.CLOUDWATCH_LOGS_DESTINATION_ARN,

    // A name for the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,

    // A filter pattern for subscribing to a filtered stream of log events.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
FilterAndPatternSyntax.html
    filterPattern: process.env.CLOUDWATCH_LOGS_FILTER_PATTERN,

    // The name of the log group. Messages in this group matching the filter
 pattern
    // will be sent to the destination ARN.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  destinationArn: "LAMBDA_FUNCTION_ARN",
  filterName: "FILTER_NAME",
  filterPattern: "ERROR",
  logGroupName: "LOG_GROUP",
};

cwl.putSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Crie uma tarefa CloudWatch de exportação de registros usando um AWS SDK

O exemplo de código a seguir mostra como criar uma nova tarefa de exportação de CloudWatch registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to create an Export Task to export the contents of the Amazon
/// CloudWatch Logs to the specified Amazon Simple Storage Service (Amazon
S3)
/// bucket.
/// </summary>
public class CreateExportTask
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();
        string taskName = "export-task-example";
        string logGroupName = "cloudwatchlogs-example-loggroup";
        string destination = "doc-example-bucket";
        var fromTime = 1437584472382;
        var toTime = 1437584472833;

        var request = new CreateExportTaskRequest
```

```
            {
                From = fromTime,
                To = toTime,
                TaskName = taskName,
                LogGroupName = logGroupName,
                Destination = destination,
            };

            var response = await client.CreateExportTaskAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"The task, {taskName} with ID: " +
                                  $"{response.TaskId} has been created
successfully.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateExportTaska Referência AWS SDK for .NET da API.

Excluir um grupo de CloudWatch registros de registros usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um grupo de CloudWatch registros de registros existente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
```

```
    using Amazon.CloudWatchLogs;
    using Amazon.CloudWatchLogs.Model;

    /// <summary>
    /// Uses the Amazon CloudWatch Logs Service to delete an existing
    /// CloudWatch Logs log group.
    /// </summary>
    public class DeleteLogGroup
    {
        public static async Task Main()
        {
            var client = new AmazonCloudWatchLogsClient();
            string logGroupName = "cloudwatchlogs-example-loggroup";

            var request = new DeleteLogGroupRequest
            {
                LogGroupName = logGroupName,
            };

            var response = await client.DeleteLogGroupAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully deleted CloudWatch log group,
 {logGroupName}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteLogGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando exclui um grupo de logs chamado `my-logs`:

```
aws logs delete-log-group --log-group-name my-logs
```

- Para obter detalhes da API, consulte DeleteLogGroupem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteLogGroupCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteLogGroupCommand({
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DeleteLogGroupa Referência AWS SDK for JavaScript da API.

Excluir um filtro CloudWatch de assinatura do Logs usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um filtro de assinatura do Amazon CloudWatch Logs.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DeleteSubscriptionFilterRequest.h>
#include <iostream>
```

Excluir o filtro de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DeleteSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetLogGroupName(log_group);

        auto outcome = cwl.DeleteSubscriptionFilter(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Failed to delete CloudWatch log subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        } else {
            std::cout << "Successfully deleted CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DeleteSubscriptionFilterRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteSubscriptionFilter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <filter> <logGroup>

                Where:
                  filter - The name of the subscription filter (for example,
 MyFilter).
                  logGroup - The name of the log group. (for example, testgroup).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String filter = args[0];
        String logGroup = args[1];
        CloudWatchLogsClient logs = CloudWatchLogsClient.builder()
                .build();

        deleteSubFilter(logs, filter, logGroup);
        logs.close();
    }

    public static void deleteSubFilter(CloudWatchLogsClient logs, String filter,
 String logGroup) {
        try {
            DeleteSubscriptionFilterRequest request =
 DeleteSubscriptionFilterRequest.builder()
                    .filterName(filter)
                    .logGroupName(logGroup)
                    .build();

            logs.deleteSubscriptionFilter(request);
            System.out.printf("Successfully deleted CloudWatch logs subscription
 filter %s", filter);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-
logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteSubscriptionFilterCommand({
    // The name of the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
```

```
  filterName: "FILTER",
  logGroupName: "LOG_GROUP",
};

cwl.deleteSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSubFilter(filter: String?, logGroup: String?) {

    val request = DeleteSubscriptionFilterRequest {
        filterName = filter
        logGroupName = logGroup
    }

    CloudWatchLogsClient { region = "us-west-2" }.use { logs ->
        logs.deleteSubscriptionFilter(request)
        println("Successfully deleted CloudWatch logs subscription filter named
 $filter")
    }
}
```

- Para obter detalhes da API, consulte a DeleteSubscriptionFilterreferência da API AWSSDK for Kotlin.

Descrever CloudWatch os filtros de assinatura do Logs usando um AWS SDK

Os exemplos de código a seguir mostram como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

C++

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DescribeSubscriptionFiltersRequest.h>
#include <aws/logs/model/DescribeSubscriptionFiltersResult.h>
#include <iostream>
#include <iomanip>
```

Liste os filtros de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DescribeSubscriptionFiltersRequest request;
        request.SetLogGroupName(log_group);
        request.SetLimit(1);

        bool done = false;
        bool header = false;
```

```
        while (!done) {
            auto outcome = cwl.DescribeSubscriptionFilters(
                    request);
            if (!outcome.IsSuccess()) {
                std::cout << "Failed to describe CloudWatch subscription filters
"
                    << "for log group " << log_group << ": " <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header) {
                std::cout << std::left << std::setw(32) << "Name" <<
                    std::setw(64) << "FilterPattern" << std::setw(64) <<
                    "DestinationArn" << std::endl;
                header = true;
            }

            const auto &filters = outcome.GetResult().GetSubscriptionFilters();
            for (const auto &filter : filters) {
                std::cout << std::left << std::setw(32) <<
                    filter.GetFilterName() << std::setw(64) <<
                    filter.GetFilterPattern() << std::setw(64) <<
                    filter.GetDestinationArn() << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DescribeSubscriptionFiltersRequest;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DescribeSubscriptionFiltersResponse
import software.amazon.awssdk.services.cloudwatchlogs.model.SubscriptionFilter;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeSubscriptionFilters {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                  <logGroup>

                Where:
                  logGroup - A log group name (for example, myloggroup).
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String logGroup = args[0];
        CloudWatchLogsClient logs = CloudWatchLogsClient.builder()
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        describeFilters(logs, logGroup);
        logs.close();
    }

    public static void describeFilters(CloudWatchLogsClient logs, String
logGroup) {
        try {
            boolean done = false;
            String newToken = null;

            while (!done) {
                DescribeSubscriptionFiltersResponse response;
                if (newToken == null) {
                    DescribeSubscriptionFiltersRequest request =
DescribeSubscriptionFiltersRequest.builder()
                            .logGroupName(logGroup)
                            .limit(1).build();

                    response = logs.describeSubscriptionFilters(request);
                } else {
                    DescribeSubscriptionFiltersRequest request =
DescribeSubscriptionFiltersRequest.builder()
                            .nextToken(newToken)
                            .logGroupName(logGroup)
                            .limit(1).build();
                    response = logs.describeSubscriptionFilters(request);
                }

                for (SubscriptionFilter filter : response.subscriptionFilters())
{
                    System.out.printf("Retrieved filter with name %s, " +
"pattern %s " + "and destination arn %s",
                            filter.filterName(),
                            filter.filterPattern(),
                            filter.destinationArn());
                }
```

```
                if (response.nextToken() == null) {
                    done = true;
                } else {
                    newToken = response.nextToken();
                }
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.printf("Done");
    }
}
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSubscriptionFiltersCommand } from "@aws-sdk/client-cloudwatch-
logs";
import { client } from "../libs/client.js";

const run = async () => {
  // This will return a list of all subscription filters in your account
  // matching the log group name.
  const command = new DescribeSubscriptionFiltersCommand({
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
    limit: 1,
  });
```

```
  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  logGroupName: "GROUP_NAME",
  limit: 5,
};

cwl.describeSubscriptionFilters(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.subscriptionFilters);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeFilters(logGroup: String) {

    val request = DescribeSubscriptionFiltersRequest {
        logGroupName = logGroup
        limit = 1
    }

    CloudWatchLogsClient { region = "us-west-2" }.use { cwlClient ->
        val response = cwlClient.describeSubscriptionFilters(request)
        response.subscriptionFilters?.forEach { filter ->
            println("Retrieved filter with name  ${filter.filterName} pattern
 ${filter.filterPattern} and destination ${filter.destinationArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSubscriptionFiltersreferência da API AWSSDK for Kotlin.

Descrever CloudWatch as tarefas de exportação de registros usando um AWS SDK

O exemplo de código a seguir mostra como descrever CloudWatch as tarefas de exportação de registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to retrieve a list of information about Amazon CloudWatch
/// Logs export tasks.
/// </summary>
public class DescribeExportTasks
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();

        var request = new DescribeExportTasksRequest
        {
            Limit = 5,
        };

        var response = new DescribeExportTasksResponse();

        do
```

```
            {
                response = await client.DescribeExportTasksAsync(request);
                response.ExportTasks.ForEach(t =>
                {
                    Console.WriteLine($"{t.TaskName} with ID: {t.TaskId} has
status: {t.Status}");
                });
            }
            while (response.NextToken is not null);
        }
    }
```

- Para obter detalhes da API, consulte DescribeExportTasksa Referência AWS SDK for .NET da API.

Descrever grupos de CloudWatch registros usando um AWS SDK

Os exemplos de código a seguir mostram como descrever grupos de CloudWatch registros de registros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Retrieves information about existing Amazon CloudWatch Logs log groups
/// and displays the information on the console.
/// </summary>
```

```
    public class DescribeLogGroups
    {
        public static async Task Main()
        {
            // Creates a CloudWatch Logs client using the default
            // user. If you need to work with resources in another
            // AWS Region than the one defined for the default user,
            // pass the AWS Region as a parameter to the client constructor.
            var client = new AmazonCloudWatchLogsClient();

            bool done = false;
            string newToken = null;

            var request = new DescribeLogGroupsRequest
            {
                Limit = 5,
            };

            DescribeLogGroupsResponse response;

            do
            {
                if (newToken is not null)
                {
                    request.NextToken = newToken;
                }

                response = await client.DescribeLogGroupsAsync(request);

                response.LogGroups.ForEach(lg =>
                {
                    Console.WriteLine($"{lg.LogGroupName} is associated with the
key: {lg.KmsKeyId}.");
                    Console.WriteLine($"Created on:
{lg.CreationTime.Date.Date}");
                    Console.WriteLine($"Date for this group will be stored for:
{lg.RetentionInDays} days.\n");
                });

                if (response.NextToken is null)
                {
                    done = true;
                }
                else
```

```
                {
                    newToken = response.NextToken;
                }
            }
            while (!done);
        }
    }
```

- Para obter detalhes da API, consulte DescribeLogGroupsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando descreve um grupo de logs chamado `my-logs`:

```
aws logs describe-log-groups --log-group-name-prefix my-logs
```

Saída:

```
{
    "logGroups": [
        {
            "storedBytes": 0,
            "metricFilterCount": 0,
            "creationTime": 1433189500783,
            "logGroupName": "my-logs",
            "retentionInDays": 5,
            "arn": "arn:aws:logs:us-west-2:0123456789012:log-group:my-logs:*"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeLogGroupsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateDescribeLogGroups,
  CloudWatchLogsClient,
} from "@aws-sdk/client-cloudwatch-logs";

const client = new CloudWatchLogsClient({});

export const main = async () => {
  const paginatedLogGroups = paginateDescribeLogGroups({ client }, {});
  const logGroups = [];

  for await (const page of paginatedLogGroups) {
    if (page.logGroups && page.logGroups.every((lg) => !!lg)) {
      logGroups.push(...page.logGroups);
    }
  }

  console.log(logGroups);
  return logGroups;
};
```

- Para obter detalhes da API, consulte DescribeLogGroupsa Referência AWS SDK for JavaScript da API.

Obtenha os resultados de uma consulta de CloudWatch registros usando um AWS SDK

O exemplo de código a seguir mostra como obter os resultados de uma consulta.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Executar uma consulta grande

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Simple wrapper for the GetQueryResultsCommand.
 * @param {string} queryId
 */
_getQueryResults(queryId) {
  return this.client.send(new GetQueryResultsCommand({ queryId }));
}
```

- Para obter detalhes da API, consulte GetQueryResultsa Referência AWS SDK for JavaScript da API.

Iniciar uma sessão do Live Tail usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

.NET

AWS SDK for .NET

Inclua os arquivos necessários.

```
using Amazon;
using Amazon.CloudWatchLogs;
```

```
using Amazon.CloudWatchLogs.Model;
```

Inicie a sessão do Live Tail.

```
            var client = new AmazonCloudWatchLogsClient();
            var request = new StartLiveTailRequest
            {
                LogGroupIdentifiers = logGroupIdentifiers,
                LogStreamNames = logStreamNames,
                LogEventFilterPattern = filterPattern,
            };

            var response = await client.StartLiveTailAsync(request);

            // Catch if request fails
            if (response.HttpStatusCode != System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine("Failed to start live tail session");
                return;
            }
```

Você pode lidar com os eventos da sessão do Live Tail de duas maneiras:

```
            /* Method 1
            * 1). Asynchronously loop through the event stream
            * 2). Set a timer to dispose the stream and stop the Live Tail
 session at the end.
            */
            var eventStream = response.ResponseStream;
            var task = Task.Run(() =>
            {
                foreach (var item in eventStream)
                {
                    if (item is LiveTailSessionUpdate liveTailSessionUpdate)
                    {
                        foreach (var sessionResult in
 liveTailSessionUpdate.SessionResults)
                        {
                            Console.WriteLine("Message : {0}",
 sessionResult.Message);
                        }
```

```
                    }
                    if (item is LiveTailSessionStart)
                    {
                        Console.WriteLine("Live Tail session started");
                    }
                    // On-stream exceptions are processed here
                    if (item is CloudWatchLogsEventStreamException)
                    {
                        Console.WriteLine($"ERROR: {item}");
                    }
                }
            });
            // Close the stream to stop the session after a timeout
            if (!task.Wait(TimeSpan.FromSeconds(10))){
                eventStream.Dispose();
                Console.WriteLine("End of line");
            }
```

```
            /* Method 2
            * 1). Add event handlers to each event variable
            * 2). Start processing the stream and wait for a timeout using
AutoResetEvent
            */
            AutoResetEvent endEvent = new AutoResetEvent(false);
            var eventStream = response.ResponseStream;
            using (eventStream) // automatically disposes the stream to stop the
session after execution finishes
            {
                eventStream.SessionStartReceived += (sender, e) =>
                {
                    Console.WriteLine("LiveTail session started");
                };
                eventStream.SessionUpdateReceived += (sender, e) =>
                {
                    foreach (LiveTailSessionLogEvent logEvent in
e.EventStreamEvent.SessionResults){
                        Console.WriteLine("Message: {0}", logEvent.Message);
                    }
                };
                // On-stream exceptions are captured here
                eventStream.ExceptionReceived += (sender, e) =>
                {
```

```
                    Console.WriteLine($"ERROR:
 {e.EventStreamException.Message}");
                };

                eventStream.StartProcessing();
                // Stream events for this amount of time.
                endEvent.WaitOne(TimeSpan.FromSeconds(10));
                Console.WriteLine("End of line");
            }
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for .NET da API.

Go

SDK for Go V2

Inclua os arquivos necessários.

```
import (
 "context"
 "log"
 "time"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/cloudwatchlogs"
 "github.com/aws/aws-sdk-go-v2/service/cloudwatchlogs/types"
)
```

Gerencie os eventos da sessão do Live Tail.

```
func handleEventStreamAsync(stream *cloudwatchlogs.StartLiveTailEventStream) {
 eventsChan := stream.Events()
 for {
  event := <-eventsChan
  switch e := event.(type) {
  case *types.StartLiveTailResponseStreamMemberSessionStart:
   log.Println("Received SessionStart event")
  case *types.StartLiveTailResponseStreamMemberSessionUpdate:
   for _, logEvent := range e.Value.SessionResults {
    log.Println(*logEvent.Message)
```

```
    }
   default:
    // Handle on-stream exceptions
    if err := stream.Err(); err != nil {
     log.Fatalf("Error occured during streaming: %v", err)
    } else if event == nil {
     log.Println("Stream is Closed")
     return
    } else {
     log.Fatalf("Unknown event type: %T", e)
    }
   }
  }
 }
```

Inicie a sessão do Live Tail.

```
cfg, err := config.LoadDefaultConfig(context.TODO())
if err != nil {
 panic("configuration error, " + err.Error())
}
client := cloudwatchlogs.NewFromConfig(cfg)

request := &cloudwatchlogs.StartLiveTailInput{
 LogGroupIdentifiers:   logGroupIdentifiers,
 LogStreamNames:        logStreamNames,
 LogEventFilterPattern: logEventFilterPattern,
}

response, err := client.StartLiveTail(context.TODO(), request)
// Handle pre-stream Exceptions
if err != nil {
 log.Fatalf("Failed to start streaming: %v", err)
}

// Start a Goroutine to handle events over stream
stream := response.GetStream()
go handleEventStreamAsync(stream)
```

Interrompa a sessão do Live Tail após um período decorrido.

```
// Close the stream (which ends the session) after a timeout
time.Sleep(10 * time.Second)
stream.Close()
log.Println("Event stream closed")
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

Inclua os arquivos necessários.

```
import io.reactivex.FlowableSubscriber;
import io.reactivex.annotations.NonNull;
import org.reactivestreams.Subscription;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsAsyncClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionLogEvent;
import software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionStart;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionUpdate;
import software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailRequest;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailResponseHandler;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.CloudWatchLogsException;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailResponseStream;

import java.util.Date;
import java.util.List;
import java.util.concurrent.atomic.AtomicReference;
```

Gerencie os eventos da sessão do Live Tail.

```
    private static StartLiveTailResponseHandler
 getStartLiveTailResponseStreamHandler(
            AtomicReference<Subscription> subscriptionAtomicReference) {
```

```
        return StartLiveTailResponseHandler.builder()
            .onResponse(r -> System.out.println("Received initial response"))
            .onError(throwable -> {
                CloudWatchLogsException e = (CloudWatchLogsException)
throwable.getCause();
                System.err.println(e.awsErrorDetails().errorMessage());
                System.exit(1);
            })
            .subscriber(() -> new FlowableSubscriber<>() {
                @Override
                public void onSubscribe(@NonNull Subscription s) {
                    subscriptionAtomicReference.set(s);
                    s.request(Long.MAX_VALUE);
                }

                @Override
                public void onNext(StartLiveTailResponseStream event) {
                    if (event instanceof LiveTailSessionStart) {
                        LiveTailSessionStart sessionStart =
(LiveTailSessionStart) event;
                        System.out.println(sessionStart);
                    } else if (event instanceof LiveTailSessionUpdate) {
                        LiveTailSessionUpdate sessionUpdate =
(LiveTailSessionUpdate) event;
                        List<LiveTailSessionLogEvent> logEvents =
sessionUpdate.sessionResults();
                        logEvents.forEach(e -> {
                            long timestamp = e.timestamp();
                            Date date = new Date(timestamp);
                            System.out.println("[" + date + "] " + e.message());
                        });
                    } else {
                        throw CloudWatchLogsException.builder().message("Unknown
event type").build();
                    }
                }

                @Override
                public void onError(Throwable throwable) {
                    System.out.println(throwable.getMessage());
                    System.exit(1);
                }

                @Override
```

```
                public void onComplete() {
                    System.out.println("Completed Streaming Session");
                }
            })
            .build();
    }
```

Inicie a sessão do Live Tail.

```
        CloudWatchLogsAsyncClient cloudWatchLogsAsyncClient =
                CloudWatchLogsAsyncClient.builder()
                    .credentialsProvider(ProfileCredentialsProvider.create())
                    .build();

        StartLiveTailRequest request =
                StartLiveTailRequest.builder()
                    .logGroupIdentifiers(logGroupIdentifiers)
                    .logStreamNames(logStreamNames)
                    .logEventFilterPattern(logEventFilterPattern)
                    .build();

        /* Create a reference to store the subscription */
        final AtomicReference<Subscription> subscriptionAtomicReference = new
 AtomicReference<>(null);

        cloudWatchLogsAsyncClient.startLiveTail(request,
 getStartLiveTailResponseStreamHandler(subscriptionAtomicReference));
```

Interrompa a sessão do Live Tail após um período decorrido.

```
        /* Set a timeout for the session and cancel the subscription. This will:
         * 1). Close the stream
         * 2). Stop the Live Tail session
         */
        try {
            Thread.sleep(10000);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        if (subscriptionAtomicReference.get() != null) {
            subscriptionAtomicReference.get().cancel();
```

```
            System.out.println("Subscription to stream closed");
        }
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

Inclua os arquivos necessários.

```
import { CloudWatchLogsClient, StartLiveTailCommand } from "@aws-sdk/client-
cloudwatch-logs";
```

Gerencie os eventos da sessão do Live Tail.

```
async function handleResponseAsync(response) {
    try {
      for await (const event of response.responseStream) {
        if (event.sessionStart !== undefined) {
          console.log(event.sessionStart);
        } else if (event.sessionUpdate !== undefined) {
          for (const logEvent of event.sessionUpdate.sessionResults) {
            const timestamp = logEvent.timestamp;
            const date = new Date(timestamp);
            console.log("[" + date + "] " + logEvent.message);
          }
        } else {
            console.error("Unknown event type");
        }
      }
    } catch (err) {
        // On-stream exceptions are captured here
        console.error(err)
    }
}
```

Inicie a sessão do Live Tail.

```
    const client = new CloudWatchLogsClient();

    const command = new StartLiveTailCommand({
        logGroupIdentifiers: logGroupIdentifiers,
        logStreamNames: logStreamNames,
        logEventFilterPattern: filterPattern
    });
    try{
        const response = await client.send(command);
        handleResponseAsync(response);
    } catch (err){
        // Pre-stream exceptions are captured here
        console.log(err);
    }
```

Interrompa a sessão do Live Tail após um período decorrido.

```
    /* Set a timeout to close the client. This will stop the Live Tail session.
 */
    setTimeout(function() {
        console.log("Client timeout");
        client.destroy();
      }, 10000);
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

Inclua os arquivos necessários.

```
import aws.sdk.kotlin.services.cloudwatchlogs.CloudWatchLogsClient
import aws.sdk.kotlin.services.cloudwatchlogs.model.StartLiveTailRequest
import aws.sdk.kotlin.services.cloudwatchlogs.model.StartLiveTailResponseStream
import kotlinx.coroutines.flow.takeWhile
```

Inicie a sessão do Live Tail.

```
    val client = CloudWatchLogsClient.fromEnvironment()

    val request = StartLiveTailRequest {
        logGroupIdentifiers = logGroupIdentifiersVal
        logStreamNames = logStreamNamesVal
        logEventFilterPattern = logEventFilterPatternVal
    }

    val startTime = System.currentTimeMillis()

    try {
        client.startLiveTail(request) { response ->
            val stream = response.responseStream
            if (stream != null) {
                /* Set a timeout to unsubcribe from the flow. This will:
                * 1). Close the stream
                * 2). Stop the Live Tail session
                */
                stream.takeWhile { System.currentTimeMillis() - startTime <
10000 }.collect { value ->
                    if (value is StartLiveTailResponseStream.SessionStart) {
                        println(value.asSessionStart())
                    } else if (value is
StartLiveTailResponseStream.SessionUpdate) {
                        for (e in value.asSessionUpdate().sessionResults!!) {
                            println(e)
                        }
                    } else {
                        throw IllegalArgumentException("Unknown event type")
                    }
                }
            } else {
                throw IllegalArgumentException("No response stream")
            }
        }
    } catch (e: Exception) {
        println("Exception occurred during StartLiveTail: $e")
        System.exit(1)
    }
```

- Para obter detalhes da API, consulte a StartLiveTailreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

Inclua os arquivos necessários.

```
import boto3
import time
from datetime import datetime
```

Inicie a sessão do Live Tail.

```
    # Initialize the client
    client = boto3.client('logs')

    start_time = time.time()

    try:
        response = client.start_live_tail(
            logGroupIdentifiers=log_group_identifiers,
            logStreamNames=log_streams,
            logEventFilterPattern=filter_pattern
        )
        event_stream = response['responseStream']
        # Handle the events streamed back in the response
        for event in event_stream:
            # Set a timeout to close the stream.
            # This will end the Live Tail session.
            if (time.time() - start_time >= 10):
                event_stream.close()
                break
            # Handle when session is started
            if 'sessionStart' in event:
                session_start_event = event['sessionStart']
                print(session_start_event)
            # Handle when log event is given in a session update
            elif 'sessionUpdate' in event:
                log_events = event['sessionUpdate']['sessionResults']
                for log_event in log_events:
```

```
                    print('[{date}]
{log}'.format(date=datetime.fromtimestamp(log_event['timestamp']/1000),log=log_event['me
            else:
                # On-stream exceptions are captured here
                raise RuntimeError(str(event))
    except Exception as e:
        print(e)
```

- Para obter detalhes da API, consulte a StartLiveTailReferência da API AWSSDK for Python (Boto3).

Iniciar uma consulta de CloudWatch registros usando um AWS SDK

O exemplo de código a seguir mostra como iniciar uma consulta.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Executar uma consulta grande

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Wrapper for the StartQueryCommand. Uses a static query string
 * for consistency.
 * @param {[Date, Date]} dateRange
 * @param {number} maxLogs
 * @returns {Promise<{ queryId: string }>}
 */
async _startQuery([startDate, endDate], maxLogs = 10000) {
  try {
```

```
      return await this.client.send(
        new StartQueryCommand({
          logGroupNames: this.logGroupNames,
          queryString: "fields @timestamp, @message | sort @timestamp asc",
          startTime: startDate.valueOf(),
          endTime: endDate.valueOf(),
          limit: maxLogs,
        }),
      );
    } catch (err) {
      /** @type {string} */
      const message = err.message;
      if (message.startsWith("Query's end date and time")) {
        // This error indicates that the query's start or end date occur
        // before the log group was created.
        throw new DateOutOfBoundsError(message);
      }

      throw err;
    }
  }
```

- Para obter detalhes da API, consulte StartQuerya Referência AWS SDK for JavaScript da API.

Cenários para CloudWatch registros usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Logs com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Use CloudWatch Logs para executar uma consulta grande

Use CloudWatch Logs para executar uma consulta grande

O exemplo de código a seguir mostra como usar o CloudWatch Logs para consultar mais de 10.000 registros.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { CloudWatchLogsClient } from "@aws-sdk/client-cloudwatch-logs";
import { CloudWatchQuery } from "./cloud-watch-query.js";

console.log("Starting a recursive query...");

if (!process.env.QUERY_START_DATE || !process.env.QUERY_END_DATE) {
  throw new Error(
    "QUERY_START_DATE and QUERY_END_DATE environment variables are required.",
  );
}

const cloudWatchQuery = new CloudWatchQuery(new CloudWatchLogsClient({}), {
  logGroupNames: ["/workflows/cloudwatch-logs/large-query"],
  dateRange: [
    new Date(parseInt(process.env.QUERY_START_DATE)),
    new Date(parseInt(process.env.QUERY_END_DATE)),
  ],
});

await cloudWatchQuery.run();

console.log(
```

```
  `Queries finished in ${cloudWatchQuery.secondsElapsed} seconds.\nTotal logs
 found: ${cloudWatchQuery.results.length}`,
);
```

Essa é uma classe que divide as consultas em várias etapas, se necessário.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import {
  StartQueryCommand,
  GetQueryResultsCommand,
} from "@aws-sdk/client-cloudwatch-logs";
import { splitDateRange } from "@aws-sdk-examples/libs/utils/util-date.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

class DateOutOfBoundsError extends Error {}

export class CloudWatchQuery {
  /**
   * Run a query for all CloudWatch Logs within a certain date range.
   * CloudWatch logs return a max of 10,000 results. This class
   * performs a binary search across all of the logs in the provided
   * date range if a query returns the maximum number of results.
   *
   * @param {import('@aws-sdk/client-cloudwatch-logs').CloudWatchLogsClient}
 client
   * @param {{ logGroupNames: string[], dateRange: [Date, Date], queryConfig:
 { limit: number } }} config
   */
  constructor(client, { logGroupNames, dateRange, queryConfig }) {
    this.client = client;
    /**
     * All log groups are queried.
     */
    this.logGroupNames = logGroupNames;

    /**
     * The inclusive date range that is queried.
     */
    this.dateRange = dateRange;

    /**
```

```
     * CloudWatch Logs never returns more than 10,000 logs.
     */
    this.limit = queryConfig?.limit ?? 10000;

    /**
     * @type {import("@aws-sdk/client-cloudwatch-logs").ResultField[][]}
     */
    this.results = [];
  }

  /**
   * Run the query.
   */
  async run() {
    this.secondsElapsed = 0;
    const start = new Date();
    this.results = await this._largeQuery(this.dateRange);
    const end = new Date();
    this.secondsElapsed = (end - start) / 1000;
    return this.results;
  }

  /**
   * Recursively query for logs.
   * @param {[Date, Date]} dateRange
   * @returns {Promise<import("@aws-sdk/client-cloudwatch-logs").ResultField[]
[]>}
   */
  async _largeQuery(dateRange) {
    const logs = await this._query(dateRange, this.limit);

    console.log(
      `Query date range: ${dateRange
        .map((d) => d.toISOString())
        .join(" to ")}. Found ${logs.length} logs.`,
    );

    if (logs.length < this.limit) {
      return logs;
    }

    const lastLogDate = this._getLastLogDate(logs);
    const offsetLastLogDate = new Date(lastLogDate);
    offsetLastLogDate.setMilliseconds(lastLogDate.getMilliseconds() + 1);
```

```
    const subDateRange = [offsetLastLogDate, dateRange[1]];
    const [r1, r2] = splitDateRange(subDateRange);
    const results = await Promise.all([
      this._largeQuery(r1),
      this._largeQuery(r2),
    ]);
    return [logs, ...results].flat();
  }

  /**
   * Find the most recent log in a list of logs.
   * @param {import("@aws-sdk/client-cloudwatch-logs").ResultField[][]} logs
   */
  _getLastLogDate(logs) {
    const timestamps = logs
      .map(
        (log) =>
          log.find((fieldMeta) => fieldMeta.field === "@timestamp")?.value,
      )
      .filter((t) => !!t)
      .map((t) => `${t}Z`)
      .sort();

    if (!timestamps.length) {
      throw new Error("No timestamp found in logs.");
    }

    return new Date(timestamps[timestamps.length - 1]);
  }

  // snippet-start:[javascript.v3.cloudwatch-logs.actions.GetQueryResults]
  /**
   * Simple wrapper for the GetQueryResultsCommand.
   * @param {string} queryId
   */
  _getQueryResults(queryId) {
    return this.client.send(new GetQueryResultsCommand({ queryId }));
  }
  // snippet-end:[javascript.v3.cloudwatch-logs.actions.GetQueryResults]

  /**
   * Starts a query and waits for it to complete.
   * @param {[Date, Date]} dateRange
   * @param {number} maxLogs
```

```
 */
async _query(dateRange, maxLogs) {
  try {
    const { queryId } = await this._startQuery(dateRange, maxLogs);
    const { results } = await this._waitUntilQueryDone(queryId);
    return results ?? [];
  } catch (err) {
    /**
     * This error is thrown when StartQuery returns an error indicating
     * that the query's start or end date occur before the log group was
     * created.
     */
    if (err instanceof DateOutOfBoundsError) {
      return [];
    } else {
      throw err;
    }
  }
}

// snippet-start:[javascript.v3.cloudwatch-logs.actions.StartQuery]
/**
 * Wrapper for the StartQueryCommand. Uses a static query string
 * for consistency.
 * @param {[Date, Date]} dateRange
 * @param {number} maxLogs
 * @returns {Promise<{ queryId: string }>}
 */
async _startQuery([startDate, endDate], maxLogs = 10000) {
  try {
    return await this.client.send(
      new StartQueryCommand({
        logGroupNames: this.logGroupNames,
        queryString: "fields @timestamp, @message | sort @timestamp asc",
        startTime: startDate.valueOf(),
        endTime: endDate.valueOf(),
        limit: maxLogs,
      }),
    );
  } catch (err) {
    /** @type {string} */
    const message = err.message;
    if (message.startsWith("Query's end date and time")) {
      // This error indicates that the query's start or end date occur
```

```
        // before the log group was created.
        throw new DateOutOfBoundsError(message);
      }

      throw err;
    }
  }
  // snippet-end:[javascript.v3.cloudwatch-logs.actions.StartQuery]

  /**
   * Call GetQueryResultsCommand until the query is done.
   * @param {string} queryId
   */
  _waitUntilQueryDone(queryId) {
    const getResults = async () => {
      const results = await this._getQueryResults(queryId);
      const queryDone = [
        "Complete",
        "Failed",
        "Cancelled",
        "Timeout",
        "Unknown",
      ].includes(results.status);

      return { queryDone, results };
    };

    return retry(
      { intervalInMs: 1000, maxRetries: 60, quiet: true },
      async () => {
        const { queryDone, results } = await getResults();
        if (!queryDone) {
          throw new Error("Query not done.");
        }

        return results;
      },
    );
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - GetQueryResults
  - StartQuery

Exemplos de vários serviços para CloudWatch registros usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon CloudWatch Logs com AWS SDKs. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Usar eventos programados para chamar uma função do Lambda

Usar eventos programados para chamar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma AWS Lambda função invocada por um evento EventBridge agendado pela Amazon.

Python

SDK para Python (Boto3)

Este exemplo mostra como registrar uma AWS Lambda função como alvo de um EventBridge evento programado da Amazon. O manipulador do Lambda grava uma mensagem amigável e os dados completos do evento no Amazon CloudWatch Logs para recuperação posterior.

- Implanta uma função do Lambda
- Cria um evento EventBridge agendado e torna a função Lambda o alvo.
- Concede permissão para permitir a EventBridge invocação da função Lambda.
- Imprime os dados mais recentes do CloudWatch Logs para mostrar o resultado das invocações programadas.
- Limpa todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- CloudWatch Registros
- EventBridge
- Lambda

Exemplos de código para CodeBuild usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS CodeBuild com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- CodeBuild Guia do usuário — Mais informações sobre CodeBuild.
- CodeBuild Referência da API — Detalhes sobre todas as CodeBuild ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para CodeBuild usar AWS SDKs
  - Crie um CodeBuild projeto

Ações para CodeBuild usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS CodeBuild com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um CodeBuild projeto

Crie um CodeBuild projeto

Os exemplos de código a seguir mostram como criar um CodeBuild projeto.

CLI

AWS CLI

Exemplo 1: Para criar um projeto de AWS CodeBuild construção

O `create-project` exemplo a seguir cria um projeto de CodeBuild compilação usando arquivos de origem de um bucket do S3

```
aws codebuild create-project \
    --name "my-demo-project" \
    --source "{\"type\": \"S3\",\"location\": \"codebuild-us-west-2-123456789012-
input-bucket/my-source.zip\"}" \
    --artifacts {"\"type\": \"S3\",\"location\": \"codebuild-us-
west-2-123456789012-output-bucket\""} \
    --environment "{\"type\": \"LINUX_CONTAINER\",\"image\": \"aws/codebuild/
standard:1.0\",\"computeType\": \"BUILD_GENERAL1_SMALL\"}" \
    --service-role "arn:aws:iam::123456789012:role/service-role/my-codebuild-
service-role"
```

Saída:

```
{
    "project": {
        "arn": "arn:aws:codebuild:us-west-2:123456789012:project/my-demo-
project",
        "name": "my-cli-demo-project",
        "encryptionKey": "arn:aws:kms:us-west-2:123456789012:alias/aws/s3",
        "serviceRole": "arn:aws:iam::123456789012:role/service-role/my-codebuild-
service-role",
        "lastModified": 1556839783.274,
        "badge": {
            "badgeEnabled": false
        },
        "queuedTimeoutInMinutes": 480,
        "environment": {
            "image": "aws/codebuild/standard:1.0",
            "computeType": "BUILD_GENERAL1_SMALL",
```

```
            "type": "LINUX_CONTAINER",
            "imagePullCredentialsType": "CODEBUILD",
            "privilegedMode": false,
            "environmentVariables": []
        },
        "artifacts": {
            "location": "codebuild-us-west-2-123456789012-output-bucket",
            "name": "my-cli-demo-project",
            "namespaceType": "NONE",
            "type": "S3",
            "packaging": "NONE",
            "encryptionDisabled": false
        },
        "source": {
            "type": "S3",
            "location": "codebuild-us-west-2-123456789012-input-bucket/my-
source.zip",
            "insecureSsl": false
        },
        "timeoutInMinutes": 60,
        "cache": {
            "type": "NO_CACHE"
        },
        "created": 1556839783.274
    }
}
```

Exemplo 2: Para criar um projeto de AWS CodeBuild construção usando um arquivo de entrada JSON para os parâmetros

O `create-project` exemplo a seguir cria um projeto de CodeBuild construção passando todos os parâmetros necessários em um arquivo de entrada JSON. Crie o modelo do arquivo de entrada executando o comando somente com o `--generate-cli-skeleton parameter`.

```
aws codebuild create-project --cli-input-json file://create-project.json
```

O arquivo de entrada JSON `create-project.json` contém o seguinte conteúdo:

```
{
    "name": "codebuild-demo-project",
    "source": {
```

```
        "type": "S3",
        "location": "codebuild-region-ID-account-ID-input-bucket/MessageUtil.zip"
    },
    "artifacts": {
        "type": "S3",
        "location": "codebuild-region-ID-account-ID-output-bucket"
    },
    "environment": {
        "type": "LINUX_CONTAINER",
        "image": "aws/codebuild/standard:1.0",
        "computeType": "BUILD_GENERAL1_SMALL"
    },
    "serviceRole": "serviceIAMRole"
}
```

Saída:

```
{
    "project": {
        "name": "codebuild-demo-project",
        "serviceRole": "serviceIAMRole",
        "tags": [],
        "artifacts": {
            "packaging": "NONE",
            "type": "S3",
            "location": "codebuild-region-ID-account-ID-output-bucket",
            "name": "message-util.zip"
        },
        "lastModified": 1472661575.244,
        "timeoutInMinutes": 60,
        "created": 1472661575.244,
        "environment": {
            "computeType": "BUILD_GENERAL1_SMALL",
            "image": "aws/codebuild/standard:1.0",
            "type": "LINUX_CONTAINER",
            "environmentVariables": []
        },
        "source": {
            "type": "S3",
            "location": "codebuild-region-ID-account-ID-input-bucket/
MessageUtil.zip"
        },
        "encryptionKey": "arn:aws:kms:region-ID:account-ID:alias/aws/s3",
```

```
        "arn": "arn:aws:codebuild:region-ID:account-ID:project/codebuild-demo-
project"
    }
}
```

Para obter mais informações, consulte Criar um projeto de compilação (AWSCLI) no Guia do AWS CodeBuild usuário.

- Para obter detalhes da API, consulte CreateProjectem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um projeto.

```
import {
  ArtifactsType,
  CodeBuildClient,
  ComputeType,
  CreateProjectCommand,
  EnvironmentType,
  SourceType,
} from "@aws-sdk/client-codebuild";

// Create the AWS CodeBuild project.
export const createProject = async (
  projectName = "MyCodeBuilder",
  roleArn = "arn:aws:iam::xxxxxxxxxxxx:role/CodeBuildAdmin",
  buildOutputBucket = "xxxx",
  githubUrl = "https://...",
) => {
  const codeBuildClient = new CodeBuildClient({});

  const response = await codeBuildClient.send(
    new CreateProjectCommand({
```

```
      artifacts: {
        // The destination of the build artifacts.
        type: ArtifactsType.S3,
        location: buildOutputBucket,
      },
      // Information about the build environment. The combination of
 "computeType" and "type" determines the
      // requirements for the environment such as CPU, memory, and disk space.
      environment: {
        // Build environment compute types.
        // https://docs.aws.amazon.com/codebuild/latest/userguide/build-env-ref-
compute-types.html
        computeType: ComputeType.BUILD_GENERAL1_SMALL,
        // Docker image identifier.
        // See https://docs.aws.amazon.com/codebuild/latest/userguide/build-env-
ref-available.html
        image: "aws/codebuild/standard:7.0",
        // Build environment type.
        type: EnvironmentType.LINUX_CONTAINER,
      },
      name: projectName,
      // A role ARN with permission to create a CodeBuild project, write to the
 artifact location, and write CloudWatch logs.
      serviceRole: roleArn,
      source: {
        // The type of repository that contains the source code to be built.
        type: SourceType.GITHUB,
        // The location of the repository that contains the source code to be
 built.
        location: githubUrl,
      },
    }),
  );
  console.log(response);
  //   {
  //     '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: 'b428b244-777b-49a6-a48d-5dffedced8e7',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //     },
  //     project: {
```

```
  //       arn: 'arn:aws:codebuild:us-east-1:xxxxxxxxxxxx:project/MyCodeBuilder',
  //       artifacts: {
  //         encryptionDisabled: false,
  //         location: 'xxxxxx-xxxxxxx-xxxxxx',
  //         name: 'MyCodeBuilder',
  //         namespaceType: 'NONE',
  //         packaging: 'NONE',
  //         type: 'S3'
  //       },
  //       badge: { badgeEnabled: false },
  //       cache: { type: 'NO_CACHE' },
  //       created: 2023-08-18T14:46:48.979Z,
  //       encryptionKey: 'arn:aws:kms:us-east-1:xxxxxxxxxxxx:alias/aws/s3',
  //       environment: {
  //         computeType: 'BUILD_GENERAL1_SMALL',
  //         environmentVariables: [],
  //         image: 'aws/codebuild/standard:7.0',
  //         imagePullCredentialsType: 'CODEBUILD',
  //         privilegedMode: false,
  //         type: 'LINUX_CONTAINER'
  //       },
  //       lastModified: 2023-08-18T14:46:48.979Z,
  //       name: 'MyCodeBuilder',
  //       projectVisibility: 'PRIVATE',
  //       queuedTimeoutInMinutes: 480,
  //       serviceRole: 'arn:aws:iam::xxxxxxxxxxxx:role/CodeBuildAdmin',
  //       source: {
  //         insecureSsl: false,
  //         location: 'https://...',
  //         reportBuildStatus: false,
  //         type: 'GITHUB'
  //       },
  //       timeoutInMinutes: 60
  //     }
  //   }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateProjecta Referência AWS SDK for JavaScript da API.

Exemplos de código do Amazon Cognito Identity usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, você pode ver as ações contextualizadas em seus devidos cenários e exemplos de serviços cruzados.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Cognito Identity – Mais informações sobre o Amazon Cognito Identity.
- Referência da API Amazon Cognito Identity – Detalhes sobre todas as ações disponíveis do Amazon Cognito Identity.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Cognito Identity usando AWS SDKs
  - Como criar um grupo de identidades do Amazon Cognito
  - Excluir um banco de identidades do Amazon Cognito
  - Obter credenciais de uma identidade do Amazon Cognito usando um SDK da AWS
  - Listar bancos de identidades do Amazon Cognito
- Exemplos do Amazon Cognito Identity entre serviços usando AWS SDKs
  - Criar uma aplicação Amazon Transcribe
  - Criar uma aplicação de exploração do Amazon Textract

Ações do Amazon Cognito Identity usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Como criar um grupo de identidades do Amazon Cognito
- Excluir um banco de identidades do Amazon Cognito
- Obter credenciais de uma identidade do Amazon Cognito usando um SDK da AWS
- Listar bancos de identidades do Amazon Cognito

Como criar um grupo de identidades do Amazon Cognito

Os exemplos de código a seguir mostram como criar um banco de identidades do Amazon Cognito.

CLI

AWS CLI

Como criar um banco de identidades com o provedor de banco de identidades Cognito

Este exemplo cria um grupo de identidades chamado MyIdentityPool. Ele tem um provedor de banco de identidades Cognito. Identidades não autenticadas não são permitidas.

Comando:

```
aws cognito-identity create-identity-pool --identity-pool-name
 MyIdentityPool --no-allow-unauthenticated-identities --cognito-
identity-providers ProviderName="cognito-idp.us-west-2.amazonaws.com/us-
west-2_aaaaaaaaa",ClientId="3n4b5urk1ft4fl3mg5e62d9ado",ServerSideTokenCheck=false
```

Saída:

```
{
  "IdentityPoolId": "us-west-2:11111111-1111-1111-1111-111111111111",
  "IdentityPoolName": "MyIdentityPool",
  "AllowUnauthenticatedIdentities": false,
  "CognitoIdentityProviders": [
      {
```

```
            "ProviderName": "cognito-idp.us-west-2.amazonaws.com/us-
west-2_111111111",
            "ClientId": "3n4b5urk1ft4fl3mg5e62d9ado",
            "ServerSideTokenCheck": false
        }
    ]
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - CreateIdentityPool
  - ListIdentityPools

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.CreateIdentityPoolRequest;
import
 software.amazon.awssdk.services.cognitoidentity.model.CreateIdentityPoolResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 */
public class CreateIdentityPool {
    public static void main(String[] args) {
        final String usage = """
                Usage:
                    <identityPoolName>\s

                Where:
                    identityPoolName - The name to give your identity pool.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String identityPoolName = args[0];
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String identityPoolId = createIdPool(cognitoClient, identityPoolName);
        System.out.println("Unity pool ID " + identityPoolId);
        cognitoClient.close();
    }

    public static String createIdPool(CognitoIdentityClient cognitoClient, String
 identityPoolName) {
        try {
            CreateIdentityPoolRequest poolRequest =
 CreateIdentityPoolRequest.builder()
                    .allowUnauthenticatedIdentities(false)
                    .identityPoolName(identityPoolName)
                    .build();

            CreateIdentityPoolResponse response =
 cognitoClient.createIdentityPool(poolRequest);
            return response.identityPoolId();

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
```

```
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateIdentityPool
  - ListIdentityPools

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um grupo de identidades.

```
    /// Create a new identity pool and return its ID.
    ///
    /// - Parameters:
    ///     - name: The name to give the new identity pool.
    ///
    /// - Returns: A string containing the newly created pool's ID, or `nil`
    ///   if an error occurred.
    ///
    func createIdentityPool(name: String) async throws -> String? {
        let cognitoInputCall = CreateIdentityPoolInput(developerProviderName:
"com.exampleco.CognitoIdentityDemo",
                                                       identityPoolName: name)
```

```
        let result = try await cognitoIdentityClient.createIdentityPool(input:
cognitoInputCall)
        guard let poolId = result.identityPoolId else {
            return nil
        }

        return poolId
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CreateIdentityPool
  - ListIdentityPools

Excluir um banco de identidades do Amazon Cognito

Os exemplos de código a seguir mostram como excluir um banco de identidades do Amazon Cognito.

CLI

AWS CLI

Como excluir um banco de identidades

O exemplo `delete-identity-pool` a seguir exclui o banco de identidades especificado.

Comando:

```
aws cognito-identity delete-identity-pool \
    --identity-pool-id "us-west-2:11111111-1111-1111-1111-111111111111"
```

Este comando não produz saída.

- Para obter detalhes da API, consulte DeleteIdentityPoolem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.awscore.exception.AwsServiceException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.DeleteIdentityPoolRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteIdentityPool {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <identityPoolId>\s

                Where:
                    identityPoolId - The Id value of your identity pool.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String identityPoold = args[0];
        CognitoIdentityClient cognitoIdClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        deleteIdPool(cognitoIdClient, identityPoold);
        cognitoIdClient.close();
    }

    public static void deleteIdPool(CognitoIdentityClient cognitoIdClient, String
 identityPoold) {
        try {

            DeleteIdentityPoolRequest identityPoolRequest =
 DeleteIdentityPoolRequest.builder()
                    .identityPoolId(identityPoold)
                    .build();

            cognitoIdClient.deleteIdentityPool(identityPoolRequest);
            System.out.println("Done");

        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteIdentityPoola Referência AWS SDK for Java 2.x da API.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o grupo de identidades especificado.

```
/// Delete the specified identity pool.
///
/// - Parameters:
///   - id: The ID of the identity pool to delete.
///
func deleteIdentityPool(id: String) async throws {
    let input = DeleteIdentityPoolInput(
        identityPoolId: id
    )

    _ = try await cognitoIdentityClient.deleteIdentityPool(input: input)
}
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte DeleteIdentityPoola referência da API AWS SDK for Swift.

Obter credenciais de uma identidade do Amazon Cognito usando um SDK da AWS

O exemplo de código a seguir mostra como obter credenciais para uma identidade do Amazon Cognito.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.GetCredentialsForIdentityRequest;
import
 software.amazon.awssdk.services.cognitoidentity.model.GetCredentialsForIdentityResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetIdentityCredentials {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <identityId>\s

            Where:
                identityId - The Id of an existing identity in the format
 REGION:GUID.
            """;

        if (args.length != 1) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String identityId = args[0];
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        getCredsForIdentity(cognitoClient, identityId);
        cognitoClient.close();
    }

    public static void getCredsForIdentity(CognitoIdentityClient cognitoClient,
 String identityId) {
        try {
            GetCredentialsForIdentityRequest getCredentialsForIdentityRequest =
 GetCredentialsForIdentityRequest
                    .builder()
                    .identityId(identityId)
                    .build();

            GetCredentialsForIdentityResponse response = cognitoClient
                    .getCredentialsForIdentity(getCredentialsForIdentityRequest);
            System.out.println(
                    "Identity ID " + response.identityId() + ", Access key ID " +
 response.credentials().accessKeyId());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetCredentialsForIdentitya Referência AWS SDK for Java 2.x da API.

Listar bancos de identidades do Amazon Cognito

Os exemplos de código a seguir mostram como obter uma lista de bancos de identidades do Amazon Cognito.

CLI

AWS CLI

Como listar bancos de identidades

Este exemplo lista bancos de identidades. Há no máximo vinte identidades listadas.

Comando:

```
aws cognito-identity list-identity-pools --max-results 20
```

Saída:

```
{
  "IdentityPools": [
      {
          "IdentityPoolId": "us-west-2:11111111-1111-1111-1111-111111111111",
          "IdentityPoolName": "MyIdentityPool"
      },
      {
          "IdentityPoolId": "us-west-2:11111111-1111-1111-1111-111111111111",
          "IdentityPoolName": "AnotherIdentityPool"
      },
      {
          "IdentityPoolId": "us-west-2:11111111-1111-1111-1111-111111111111",
          "IdentityPoolName": "IdentityPoolRegionA"
      }
  ]
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - CreateIdentityPool
  - ListIdentityPools

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.ListIdentityPoolsRequest;
import
 software.amazon.awssdk.services.cognitoidentity.model.ListIdentityPoolsResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListIdentityPools {
    public static void main(String[] args) {
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listIdPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listIdPools(CognitoIdentityClient cognitoClient) {
        try {
            ListIdentityPoolsRequest poolsRequest =
 ListIdentityPoolsRequest.builder()
```

```
                    .maxResults(15)
                    .build();

            ListIdentityPoolsResponse response =
 cognitoClient.listIdentityPools(poolsRequest);
            response.identityPools().forEach(pool -> {
                System.out.println("Pool ID: " + pool.identityPoolId());
                System.out.println("Pool name: " + pool.identityPoolName());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateIdentityPool
  - ListIdentityPools

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Encontre o ID de um grupo de identidades com seu nome.

```
    /// Return the ID of the identity pool with the specified name.
    ///
    /// - Parameters:
    ///   - name: The name of the identity pool whose ID should be returned.
    ///
    /// - Returns: A string containing the ID of the specified identity pool
    ///   or `nil` on error or if not found.
    ///
    func getIdentityPoolID(name: String) async throws -> String? {
        var token: String? = nil

        // Iterate over the identity pools until a match is found.

        repeat {
            /// `token` is a value returned by `ListIdentityPools()` if the
            /// returned list of identity pools is only a partial list. You
            /// use the `token` to tell Amazon Cognito that you want to
            /// continue where you left off previously. If you specify `nil`
            /// or you don't provide the token, Amazon Cognito will start at
            /// the beginning.

            let listPoolsInput = ListIdentityPoolsInput(maxResults: 25,
nextToken: token)

            /// Read pages of identity pools from Cognito until one is found
            /// whose name matches the one specified in the `name` parameter.
            /// Return the matching pool's ID. Each time we ask for the next
            /// page of identity pools, we pass in the token given by the
            /// previous page.

            let output = try await cognitoIdentityClient.listIdentityPools(input:
listPoolsInput)

            if let identityPools = output.identityPools {
                for pool in identityPools {
                    if pool.identityPoolName == name {
                        return pool.identityPoolId!
                    }
                }
            }

            token = output.nextToken
        } while token != nil
```

```
        return nil
    }
```

Obtenha o ID de um grupo de identidades existente ou crie-o se ainda não existir.

```
    /// Return the ID of the identity pool with the specified name.
    ///
    /// - Parameters:
    ///   - name: The name of the identity pool whose ID should be returned
    ///
    /// - Returns: A string containing the ID of the specified identity pool.
    ///   Returns `nil` if there's an error or if the pool isn't found.
    ///
    public func getOrCreateIdentityPoolID(name: String) async throws -> String? {
        // See if the pool already exists. If it doesn't, create it.

        guard let poolId = try await self.getIdentityPoolID(name: name) else {
            return try await self.createIdentityPool(name: name)
        }

        return poolId
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CreateIdentityPool
  - ListIdentityPools

Exemplos do Amazon Cognito Identity entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação Amazon Transcribe
- Criar uma aplicação de exploração do Amazon Textract

Criar uma aplicação Amazon Transcribe

O exemplo de código a seguir mostra como usar o Amazon Transcribe para transcrever e exibir gravações de voz no navegador.

JavaScript

SDK para JavaScript (v3)

Crie uma aplicação que use o Amazon Transcribe para transcrever e exibir gravações de voz no navegador. A aplicação usa dois buckets do Amazon Simple Storage Service (Amazon S3), um para hospedar o código da aplicação e outro para armazenar transcrições. A aplicação usa um grupo de usuários do Amazon Cognito para autenticar seus usuários. Os usuários autenticados têm permissões do AWS Identity and Access Management (IAM) para acessar os serviços da AWS necessários.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon Transcribe

Criar uma aplicação de exploração do Amazon Textract

Os exemplos de código a seguir mostram como explorar a saída do Amazon Textract por meio de uma aplicação interativa.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Exemplos de código do Amazon Cognito Identity Provider usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity Provider com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Amazon Cognito Identity Provider – Mais informações sobre o Amazon Cognito Identity Provider.
- Referência da API do Amazon Cognito Identity Provider – Detalhes sobre todas as ações disponíveis do Amazon Cognito Identity Provider.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon Cognito

Os exemplos de código a seguir mostram como começar a usar o Amazon Cognito.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS cognito-idp)

# Set this project's name.
project("hello_cognito")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
```

```
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                       # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_cognito.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_cognito.cpp.

```
#include <aws/core/Aws.h>
#include <aws/cognito-idp/CognitoIdentityProviderClient.h>
#include <aws/cognito-idp/model/ListUserPoolsRequest.h>
#include <iostream>

/*
```

```
 *  A "Hello Cognito" starter application which initializes an Amazon Cognito
 client and lists the Amazon Cognito
 *  user pools.
 *
 *  main function
 *
 *  Usage: 'hello_cognito'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 cognitoClient(clientConfig);

        Aws::String nextToken; // Used for pagination.
        std::vector<Aws::String> userPools;

        do {
            Aws::CognitoIdentityProvider::Model::ListUserPoolsRequest
 listUserPoolsRequest;
            if (!nextToken.empty()) {
                listUserPoolsRequest.SetNextToken(nextToken);
            }

            Aws::CognitoIdentityProvider::Model::ListUserPoolsOutcome
 listUserPoolsOutcome =
                    cognitoClient.ListUserPools(listUserPoolsRequest);

            if (listUserPoolsOutcome.IsSuccess()) {
                for (auto &userPool:
 listUserPoolsOutcome.GetResult().GetUserPools()) {

                    userPools.push_back(userPool.GetName());
                }
```

```
                nextToken = listUserPoolsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "ListUserPools error: " <<
 listUserPoolsOutcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }


        } while (!nextToken.empty());
        std::cout << userPools.size() << " user pools found." << std::endl;
        for (auto &userPool: userPools) {
            std::cout << "   user pool: " << userPool << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsResponse;
```

```
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListUserPools {
    public static void main(String[] args) {
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUserPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listAllUserPools(CognitoIdentityProviderClient
 cognitoClient) {
        try {
            ListUserPoolsRequest request = ListUserPoolsRequest.builder()
                    .maxResults(10)
                    .build();

            ListUserPoolsResponse response =
 cognitoClient.listUserPools(request);
            response.userPools().forEach(userpool -> {
                System.out.println("User pool " + userpool.name() + ", User ID "
 + userpool.id());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateListUserPools,
  CognitoIdentityProviderClient,
} from "@aws-sdk/client-cognito-identity-provider";

const client = new CognitoIdentityProviderClient({});

export const helloCognito = async () => {
  const paginator = paginateListUserPools({ client }, {});

  const userPoolNames = [];

  for await (const page of paginator) {
    const names = page.UserPools.map((pool) => pool.Name);
    userPoolNames.push(...names);
  }

  console.log("User pool names: ");
  console.log(userPoolNames.join("\n"));
  return userPoolNames;
};
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for JavaScript da API.

Exemplos de código

- Ações do Amazon Cognito Identity Provider usando AWS SDKs
  - Confirmar um usuário do Amazon Cognito usando um AWS SDK
  - Confirme um dispositivo de MFA para rastreamento pelo Amazon Cognito usando um AWS SDK
  - Criar um grupo de usuários do Amazon Cognito usando um SDK da AWS
  - Criar um aplicativo cliente do grupo de usuários do Amazon Cognito usando um SDK da AWS
  - Excluir um usuário do Amazon Cognito usando um AWS SDK
  - Obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito usando um AWS SDK
  - Ter informações sobre um usuário do Amazon Cognito usando um AWS SDK
  - Listar os grupos de usuários do Amazon Cognito usando um AWS SDK
  - Listar os usuários do Amazon Cognito usando um AWS SDK
  - Reenviar um código de confirmação do Amazon Cognito usando um AWS SDK
  - Responder aos desafios de autenticação SRP do Amazon Cognito usando um AWS SDK
  - Responder a um desafio de autenticação do Amazon Cognito usando um AWS SDK
  - Inscrever um usuário no Amazon Cognito usando um AWS SDK
  - Iniciar a autenticação usando um SDK da AWS
  - Iniciar a autenticação com o Amazon Cognito e as credenciais de administrador usando um AWS SDK
  - Verificar uma aplicação de MFA com um usuário do Amazon Cognito usando um AWS SDK
- Cenários do Amazon Cognito Identity Provider usando AWS SDKs
  - Inscrever um usuário em um grupo de usuários do Amazon Cognito que exija MFA usando um AWS SDK

Ações do Amazon Cognito Identity Provider usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity Provider com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon Cognito Identity Provider usando AWS SDKs.

Exemplos

- Confirmar um usuário do Amazon Cognito usando um AWS SDK
- Confirme um dispositivo de MFA para rastreamento pelo Amazon Cognito usando um AWS SDK
- Criar um grupo de usuários do Amazon Cognito usando um SDK da AWS
- Criar um aplicativo cliente do grupo de usuários do Amazon Cognito usando um SDK da AWS
- Excluir um usuário do Amazon Cognito usando um AWS SDK
- Obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito usando um AWS SDK
- Ter informações sobre um usuário do Amazon Cognito usando um AWS SDK
- Listar os grupos de usuários do Amazon Cognito usando um AWS SDK
- Listar os usuários do Amazon Cognito usando um AWS SDK
- Reenviar um código de confirmação do Amazon Cognito usando um AWS SDK
- Responder aos desafios de autenticação SRP do Amazon Cognito usando um AWS SDK
- Responder a um desafio de autenticação do Amazon Cognito usando um AWS SDK
- Inscrever um usuário no Amazon Cognito usando um AWS SDK
- Iniciar a autenticação usando um SDK da AWS
- Iniciar a autenticação com o Amazon Cognito e as credenciais de administrador usando um AWS SDK
- Verificar uma aplicação de MFA com um usuário do Amazon Cognito usando um AWS SDK

Confirmar um usuário do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como confirmar um usuário do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Confirm that the user has signed up.
    /// </summary>
    /// <param name="clientId">The Id of this application.</param>
    /// <param name="code">The confirmation code sent to the user.</param>
    /// <param name="userName">The username.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> ConfirmSignupAsync(string clientId, string code,
string userName)
    {
        var signUpRequest = new ConfirmSignUpRequest
        {
            ClientId = clientId,
            ConfirmationCode = code,
            Username = userName,
        };

        var response = await _cognitoService.ConfirmSignUpAsync(signUpRequest);
        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            Console.WriteLine($"{userName} was confirmed");
            return true;
        }
        return false;
    }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
        request.SetClientId(clientID);
        request.SetConfirmationCode(confirmationCode);
        request.SetUsername(userName);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como confirmar a inscrição

Este exemplo confirma a inscrição para o nome de usuário diego@example.com.

Comando:

```
aws cognito-idp confirm-sign-up --client-id 3n4b5urk1ft4fl3mg5e62d9ado --
username=diego@example.com --confirmation-code CONF_CODE
```

- Para obter detalhes da API, consulte ConfirmSignUpem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void confirmSignUp(CognitoIdentityProviderClient
identityProviderClient, String clientId, String code,
           String userName) {
       try {
           ConfirmSignUpRequest signUpRequest = ConfirmSignUpRequest.builder()
                   .clientId(clientId)
                   .confirmationCode(code)
                   .username(userName)
                   .build();

           identityProviderClient.confirmSignUp(signUpRequest);
           System.out.println(userName + " was confirmed");

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const confirmSignUp = ({ clientId, username, code }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ConfirmSignUpCommand({
    ClientId: clientId,
    Username: username,
    ConfirmationCode: code,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun confirmSignUp(clientIdVal: String?, codeVal: String?, userNameVal:
 String?) {
    val signUpRequest = ConfirmSignUpRequest {
        clientId = clientIdVal
        confirmationCode = codeVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.confirmSignUp(signUpRequest)
        println("$userNameVal  was confirmed")
    }
}
```

- Para obter detalhes da API, consulte a ConfirmSignUpreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""
```

```
    def __init__(self, cognito_idp_client, user_pool_id, client_id,
client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def confirm_user_sign_up(self, user_name, confirmation_code):
        """
        Confirms a previously created user. A user must be confirmed before they
        can sign in to Amazon Cognito.

        :param user_name: The name of the user to confirm.
        :param confirmation_code: The confirmation code sent to the user's
registered
                                  email address.
        :return: True when the confirmation succeeds.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "ConfirmationCode": confirmation_code,
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            self.cognito_idp_client.confirm_sign_up(**kwargs)
        except ClientError as err:
            logger.error(
                "Couldn't confirm sign up for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
        else:
            return True
```

- Para obter detalhes da API, consulte a ConfirmSignUpReferência da API AWSSDK for Python (Boto3).

Confirme um dispositivo de MFA para rastreamento pelo Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como confirmar um dispositivo de MFA para rastreamento pelo Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiates and confirms tracking of the device.
    /// </summary>
    /// <param name="accessToken">The user's access token.</param>
    /// <param name="deviceKey">The key of the device from Amazon Cognito.</
param>
    /// <param name="deviceName">The device name.</param>
    /// <returns></returns>
    public async Task<bool> ConfirmDeviceAsync(string accessToken, string
 deviceKey, string deviceName)
```

```
    {
        var request = new ConfirmDeviceRequest
        {
            AccessToken = accessToken,
            DeviceKey = deviceKey,
            DeviceName = deviceName
        };

        var response = await _cognitoService.ConfirmDeviceAsync(request);
        return response.UserConfirmationNecessary;
    }
```

- Para obter detalhes da API, consulte ConfirmDevicea Referência AWS SDK for .NET da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const confirmDevice = ({ deviceKey, accessToken, passwordVerifier, salt }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ConfirmDeviceCommand({
    DeviceKey: deviceKey,
    AccessToken: accessToken,
    DeviceSecretVerifierConfig: {
      PasswordVerifier: passwordVerifier,
      Salt: salt,
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ConfirmDeviceA Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def confirm_mfa_device(
        self,
        user_name,
        device_key,
        device_group_key,
        device_password,
        access_token,
```

```
        aws_srp,
    ):
        """
        Confirms an MFA device to be tracked by Amazon Cognito. When a device is
        tracked, its key and password can be used to sign in without requiring a
new
        MFA code from the MFA application.

        :param user_name: The user that is associated with the device.
        :param device_key: The key of the device, returned by Amazon Cognito.
        :param device_group_key: The group key of the device, returned by Amazon
Cognito.
        :param device_password: The password that is associated with the device.
        :param access_token: The user's access token.
        :param aws_srp: A class that helps with Secure Remote Password (SRP)
                        calculations. The scenario associated with this example
uses
                        the warrant package.
        :return: True when the user must confirm the device. Otherwise, False.
When
                 False, the device is automatically confirmed and tracked.
        """
        srp_helper = aws_srp.AWSSRP(
            username=user_name,
            password=device_password,
            pool_id="_",
            client_id=self.client_id,
            client_secret=None,
            client=self.cognito_idp_client,
        )
        device_and_pw = f"{device_group_key}{device_key}:{device_password}"
        device_and_pw_hash = aws_srp.hash_sha256(device_and_pw.encode("utf-8"))
        salt = aws_srp.pad_hex(aws_srp.get_random(16))
        x_value = aws_srp.hex_to_long(aws_srp.hex_hash(salt +
device_and_pw_hash))
        verifier = aws_srp.pad_hex(pow(srp_helper.val_g, x_value,
srp_helper.big_n))
        device_secret_verifier_config = {
            "PasswordVerifier": base64.standard_b64encode(
                bytearray.fromhex(verifier)
            ).decode("utf-8"),
            "Salt":
base64.standard_b64encode(bytearray.fromhex(salt)).decode("utf-8"),
        }
```

```
        try:
            response = self.cognito_idp_client.confirm_device(
                AccessToken=access_token,
                DeviceKey=device_key,
                DeviceSecretVerifierConfig=device_secret_verifier_config,
            )
            user_confirm = response["UserConfirmationNecessary"]
        except ClientError as err:
            logger.error(
                "Couldn't confirm mfa device %s. Here's why: %s: %s",
                device_key,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return user_confirm
```

- Para obter detalhes da API, consulte a ConfirmDeviceReferência da API AWSSDK for Python (Boto3).

Criar um grupo de usuários do Amazon Cognito usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um grupo de usuários do Amazon Cognito.

CLI

AWS CLI

Como criar um grupo de usuários minimamente configurado

Este exemplo cria um grupo de usuários chamado MyUserPool usando valores padrão. Não há clientes de aplicações nem atributos obrigatórios. A MFA e a segurança avançada estão desabilitadas.

Comando:

```
aws cognito-idp create-user-pool --pool-name MyUserPool
```

Saída:

```
{
  "UserPool": {
      "SchemaAttributes": [
          {
              "Name": "sub",
              "StringAttributeConstraints": {
                  "MinLength": "1",
                  "MaxLength": "2048"
              },
              "DeveloperOnlyAttribute": false,
              "Required": true,
              "AttributeDataType": "String",
              "Mutable": false
          },
          {
              "Name": "name",
              "StringAttributeConstraints": {
                  "MinLength": "0",
                  "MaxLength": "2048"
              },
              "DeveloperOnlyAttribute": false,
              "Required": false,
              "AttributeDataType": "String",
              "Mutable": true
          },
          {
              "Name": "given_name",
              "StringAttributeConstraints": {
                  "MinLength": "0",
                  "MaxLength": "2048"
              },
              "DeveloperOnlyAttribute": false,
              "Required": false,
              "AttributeDataType": "String",
              "Mutable": true
          },
          {
              "Name": "family_name",
              "StringAttributeConstraints": {
                  "MinLength": "0",
                  "MaxLength": "2048"
              },
              "DeveloperOnlyAttribute": false,
```

```
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "middle_name",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "nickname",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "preferred_username",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "profile",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
```

```
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "picture",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "website",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "email",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "AttributeDataType": "Boolean",
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "Name": "email_verified",
                "Mutable": true
            },
```

```
            {
                "Name": "gender",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "birthdate",
                "StringAttributeConstraints": {
                    "MinLength": "10",
                    "MaxLength": "10"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "zoneinfo",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "locale",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
```

```
            {
                "Name": "phone_number",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "AttributeDataType": "Boolean",
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "Name": "phone_number_verified",
                "Mutable": true
            },
            {
                "Name": "address",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "updated_at",
                "NumberAttributeConstraints": {
                    "MinValue": "0"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "Number",
                "Mutable": true
            }
        ],
        "MfaConfiguration": "OFF",
        "Name": "MyUserPool",
        "LastModifiedDate": 1547833345.777,
        "AdminCreateUserConfig": {
```

```
            "UnusedAccountValidityDays": 7,
            "AllowAdminCreateUserOnly": false
        },
        "EmailConfiguration": {},
        "Policies": {
            "PasswordPolicy": {
                "RequireLowercase": true,
                "RequireSymbols": true,
                "RequireNumbers": true,
                "MinimumLength": 8,
                "RequireUppercase": true
            }
        },
        "CreationDate": 1547833345.777,
        "EstimatedNumberOfUsers": 0,
        "Id": "us-west-2_aaaaaaaaa",
        "LambdaConfig": {}
    }
}
```

Como criar um grupo de usuários com dois atributos obrigatórios

Este exemplo cria um grupo de usuários MyUserPool. O grupo é configurado para aceitar e-mail como um atributo de nome de usuário. Ele também define o endereço de origem do e-mail como um endereço validado com o Amazon Simple Email Service.

Comando:

```
aws cognito-idp create-user-pool --pool-name MyUserPool --username-
attributes "email" --email-configuration=SourceArn="arn:aws:ses:us-
east-1:111111111111:identity/
jane@example.com",ReplyToEmailAddress="jane@example.com"
```

Saída:

```
{
  "UserPool": {
      "SchemaAttributes": [
          {
              "Name": "sub",
              "StringAttributeConstraints": {
                  "MinLength": "1",
                  "MaxLength": "2048"
```

```
            },
            "DeveloperOnlyAttribute": false,
            "Required": true,
            "AttributeDataType": "String",
            "Mutable": false
        },
        {
            "Name": "name",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "given_name",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "family_name",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "middle_name",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
```

```
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "nickname",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "preferred_username",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "profile",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "picture",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
```

```
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "website",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "Name": "email",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
            "Mutable": true
        },
        {
            "AttributeDataType": "Boolean",
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "Name": "email_verified",
            "Mutable": true
        },
        {
            "Name": "gender",
            "StringAttributeConstraints": {
                "MinLength": "0",
                "MaxLength": "2048"
            },
            "DeveloperOnlyAttribute": false,
            "Required": false,
            "AttributeDataType": "String",
```

```
                "Mutable": true
            },
            {
                "Name": "birthdate",
                "StringAttributeConstraints": {
                    "MinLength": "10",
                    "MaxLength": "10"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "zoneinfo",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "locale",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "phone_number",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
```

```
                "Mutable": true
            },
            {
                "AttributeDataType": "Boolean",
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "Name": "phone_number_verified",
                "Mutable": true
            },
            {
                "Name": "address",
                "StringAttributeConstraints": {
                    "MinLength": "0",
                    "MaxLength": "2048"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "String",
                "Mutable": true
            },
            {
                "Name": "updated_at",
                "NumberAttributeConstraints": {
                    "MinValue": "0"
                },
                "DeveloperOnlyAttribute": false,
                "Required": false,
                "AttributeDataType": "Number",
                "Mutable": true
            }
        ],
        "MfaConfiguration": "OFF",
        "Name": "MyUserPool",
        "LastModifiedDate": 1547837788.189,
        "AdminCreateUserConfig": {
            "UnusedAccountValidityDays": 7,
            "AllowAdminCreateUserOnly": false
        },
        "EmailConfiguration": {
            "ReplyToEmailAddress": "jane@example.com",
            "SourceArn": "arn:aws:ses:us-east-1:111111111111:identity/
jane@example.com"
        },
        "Policies": {
```

```
            "PasswordPolicy": {
                "RequireLowercase": true,
                "RequireSymbols": true,
                "RequireNumbers": true,
                "MinimumLength": 8,
                "RequireUppercase": true
            }
        },
        "UsernameAttributes": [
            "email"
        ],
        "CreationDate": 1547837788.189,
        "EstimatedNumberOfUsers": 0,
        "Id": "us-west-2_aaaaaaaaa",
        "LambdaConfig": {}
    }
}
```

- Para obter detalhes da API, consulte CreateUserPoolem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolResponse;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateUserPool {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <userPoolName>\s

                Where:
                    userPoolName - The name to give your user pool when it's
 created.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userPoolName = args[0];
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String id = createPool(cognitoClient, userPoolName);
        System.out.println("User pool ID: " + id);
        cognitoClient.close();
    }

    public static String createPool(CognitoIdentityProviderClient cognitoClient,
 String userPoolName) {
        try {
            CreateUserPoolRequest request = CreateUserPoolRequest.builder()
                    .poolName(userPoolName)
                    .build();
```

```
            CreateUserPoolResponse response =
 cognitoClient.createUserPool(request);
            return response.userPool().id();

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateUserPoola Referência AWS SDK for Java 2.x da API.

Criar um aplicativo cliente do grupo de usuários do Amazon Cognito usando um SDK da AWS

O exemplo de código a seguir mostra como criar um cliente da aplicação do grupo de usuários do Amazon Cognito.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolClientReques
```

```
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolClientRespon

/**
 * A user pool client app is an application that authenticates with Amazon
 * Cognito user pools.
 * When you create a user pool, you can configure app clients that allow mobile
 * or web applications
 * to call API operations to authenticate users, manage user attributes and
 * profiles,
 * and implement sign-up and sign-in flows.
 *
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateUserPoolClient {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <clientName> <userPoolId>\s

                Where:
                    clientName - The name for the user pool client to create.
                    userPoolId - The ID for the user pool.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clientName = args[0];
        String userPoolId = args[1];
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createPoolClient(cognitoClient, clientName, userPoolId);
```

```
        cognitoClient.close();
    }

    public static void createPoolClient(CognitoIdentityProviderClient
 cognitoClient, String clientName,
            String userPoolId) {
        try {
            CreateUserPoolClientRequest request =
 CreateUserPoolClientRequest.builder()
                    .clientName(clientName)
                    .userPoolId(userPoolId)
                    .build();

            CreateUserPoolClientResponse response =
 cognitoClient.createUserPoolClient(request);
            System.out.println("User pool " +
 response.userPoolClient().clientName() + " created. ID: "
                    + response.userPoolClient().clientId());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateUserPoolClienta Referência AWS SDK for Java 2.x da API.

Excluir um usuário do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um usuário do Amazon Cognito.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
        request.SetAccessToken(accessToken);

        Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
                client.DeleteUser(request);

        if (outcome.IsSuccess()) {
            std::cout << "The user " << userName << " was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir um usuário

Este exemplo exclui um usuário.

Comando:

```
aws cognito-idp delete-user --access-token ACCESS_TOKEN
```

- Para obter detalhes da API, consulte DeleteUserem Referência de AWS CLI Comandos.

Obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get an MFA token to authenticate the user with the authenticator.
    /// </summary>
    /// <param name="session">The session name.</param>
    /// <returns>The session name.</returns>
    public async Task<string> AssociateSoftwareTokenAsync(string session)
    {
        var softwareTokenRequest = new AssociateSoftwareTokenRequest
        {
            Session = session,
        };
```

```
        var tokenResponse = await
_cognitoService.AssociateSoftwareTokenAsync(softwareTokenRequest);
        var secretCode = tokenResponse.SecretCode;

        Console.WriteLine($"Use the following secret code to set up the
authenticator: {secretCode}");

        return tokenResponse.Session;
    }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest
request;
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome
outcome =
                client.AssociateSoftwareToken(request);
```

```
        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for
 example Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::AssociateSoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for C ++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String getSecretForAppMFA(CognitoIdentityProviderClient
 identityProviderClient, String session) {
        AssociateSoftwareTokenRequest softwareTokenRequest =
 AssociateSoftwareTokenRequest.builder()
                .session(session)
                .build();

        AssociateSoftwareTokenResponse tokenResponse = identityProviderClient
                .associateSoftwareToken(softwareTokenRequest);
        String secretCode = tokenResponse.secretCode();
        System.out.println("Enter this token into Google Authenticator");
        System.out.println(secretCode);
        return tokenResponse.session();
    }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const associateSoftwareToken = (session) => {
  const client = new CognitoIdentityProviderClient({});
  const command = new AssociateSoftwareTokenCommand({
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSecretForAppMFA(sessionVal: String?): String? {
    val softwareTokenRequest = AssociateSoftwareTokenRequest {
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val tokenResponse =
 identityProviderClient.associateSoftwareToken(softwareTokenRequest)
        val secretCode = tokenResponse.secretCode
        println("Enter this token into Google Authenticator")
        println(secretCode)
        return tokenResponse.session
    }
}
```

- Para obter detalhes da API, consulte a AssociateSoftwareTokenreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def get_mfa_secret(self, session):
        """
        Gets a token that can be used to associate an MFA application with the
 user.

        :param session: Session information returned from a previous call to
 initiate
                        authentication.
        :return: An MFA token that can be used to set up an MFA application.
        """
        try:
            response =
 self.cognito_idp_client.associate_software_token(Session=session)
```

```
        except ClientError as err:
            logger.error(
                "Couldn't get MFA secret. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response
```

- Para obter detalhes da API, consulte a AssociateSoftwareTokenReferência da API AWSSDK for Python (Boto3).

Ter informações sobre um usuário do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como ter informações sobre um usuário do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the specified user from an Amazon Cognito user pool with
administrator access.
    /// </summary>
```

```
    /// <param name="userName">The name of the user.</param>
    /// <param name="poolId">The Id of the Amazon Cognito user pool.</param>
    /// <returns>Async task.</returns>
    public async Task<UserStatusType> GetAdminUserAsync(string userName, string
poolId)
    {
        AdminGetUserRequest userRequest = new AdminGetUserRequest
        {
            Username = userName,
            UserPoolId = poolId,
        };

        var response = await _cognitoService.AdminGetUserAsync(userRequest);

        Console.WriteLine($"User status {response.UserStatus}");
        return response.UserStatus;
    }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
```

```
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);

    Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
            client.AdminGetUser(request);

    if (outcome.IsSuccess()) {
        std::cout << "The status for " << userName << " is " <<

 Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                        outcome.GetResult().GetUserStatus()) << std::endl;
        std::cout << "Enabled is " << outcome.GetResult().GetEnabled() <<
 std::endl;
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter um usuário

Este exemplo obtém informações sobre o nome de usuário jane@example.com.

Comando:

```
aws cognito-idp admin-get-user --user-pool-id us-west-2_aaaaaaaaa --username
 jane@example.com
```

Saída:

```
{
  "Username": "4320de44-2322-4620-999b-5e2e1c8df013",
  "Enabled": true,
  "UserStatus": "FORCE_CHANGE_PASSWORD",
```

```
  "UserCreateDate": 1548108509.537,
  "UserAttributes": [
      {
          "Name": "sub",
          "Value": "4320de44-2322-4620-999b-5e2e1c8df013"
      },
      {
          "Name": "email_verified",
          "Value": "true"
      },
      {
          "Name": "phone_number_verified",
          "Value": "true"
      },
      {
          "Name": "phone_number",
          "Value": "+01115551212"
      },
      {
          "Name": "email",
          "Value": "jane@example.com"
      }
  ],
  "UserLastModifiedDate": 1548108509.537
}
```

- Para obter detalhes da API, consulte AdminGetUserem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getAdminUser(CognitoIdentityProviderClient
identityProviderClient, String userName,
            String poolId) {
        try {
```

```
            AdminGetUserRequest userRequest = AdminGetUserRequest.builder()
                    .username(userName)
                    .userPoolId(poolId)
                    .build();

            AdminGetUserResponse response =
 identityProviderClient.adminGetUser(userRequest);
            System.out.println("User status " + response.userStatusAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminGetUser = ({ userPoolId, username }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new AdminGetUserCommand({
    UserPoolId: userPoolId,
    Username: username,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAdminUser(userNameVal: String?, poolIdVal: String?) {
    val userRequest = AdminGetUserRequest {
        username = userNameVal
        userPoolId = poolIdVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminGetUser(userRequest)
        println("User status ${response.userStatus}")
    }
}
```

- Para obter detalhes da API, consulte a AdminGetUserreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon
 Cognito
        to send an email to the specified email address. The email contains a
 code that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
 whether
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
        :param password: The password for the new user.
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
```

```
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name,
response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return confirmed
```

- Para obter detalhes da API, consulte a AdminGetUserReferência da API AWSSDK for Python (Boto3).

Listar os grupos de usuários do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como listar os grupos de usuários do Amazon Cognito.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Amazon Cognito user pools for an account.
    /// </summary>
    /// <returns>A list of UserPoolDescriptionType objects.</returns>
    public async Task<List<UserPoolDescriptionType>> ListUserPoolsAsync()
    {
        var userPools = new List<UserPoolDescriptionType>();

        var userPoolsPaginator = _cognitoService.Paginators.ListUserPools(new
ListUserPoolsRequest());

        await foreach (var response in userPoolsPaginator.Responses)
        {
            userPools.AddRange(response.UserPools);
        }

        return userPools;
    }
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar grupos de usuários

Este exemplo lista até vinte grupos de usuários.

Comando:

```
aws cognito-idp list-user-pools --max-results 20
```

Saída:

```
{
  "UserPools": [
      {
         "CreationDate": 1547763720.822,
         "LastModifiedDate": 1547763720.822,
         "LambdaConfig": {},
         "Id": "us-west-2_aaaaaaaaa",
         "Name": "MyUserPool"
      }
  ]
}
```

- Para obter detalhes da API, consulte ListUserPoolsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsRequest;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListUserPools {
    public static void main(String[] args) {
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUserPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listAllUserPools(CognitoIdentityProviderClient
 cognitoClient) {
        try {
            ListUserPoolsRequest request = ListUserPoolsRequest.builder()
                    .maxResults(10)
                    .build();

            ListUserPoolsResponse response =
 cognitoClient.listUserPools(request);
            response.userPools().forEach(userpool -> {
                System.out.println("User pool " + userpool.name() + ", User ID "
 + userpool.id());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_pools(client: &Client) -> Result<(), Error> {
    let response = client.list_user_pools().max_results(10).send().await?;
    let pools = response.user_pools();
    println!("User pools:");
    for pool in pools {
        println!("  ID:              {}", pool.id().unwrap_or_default());
        println!("  Name:            {}", pool.name().unwrap_or_default());
        println!("  Lambda Config:   {:?}", pool.lambda_config().unwrap());
        println!(
            "  Last modified:   {}",
            pool.last_modified_date().unwrap().to_chrono_utc()?
        );
        println!(
            "  Creation date:   {:?}",
            pool.creation_date().unwrap().to_chrono_utc()
        );
        println!();
    }
    println!("Next token: {}", response.next_token().unwrap_or_default());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListUserPoolsreferência da API AWS SDK for Rust.

Listar os usuários do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como listar usuários do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of users for the Amazon Cognito user pool.
/// </summary>
/// <param name="userPoolId">The user pool ID.</param>
/// <returns>A list of users.</returns>
public async Task<List<UserType>> ListUsersAsync(string userPoolId)
{
    var request = new ListUsersRequest
    {
        UserPoolId = userPoolId
    };

    var users = new List<UserType>();

    var usersPaginator = _cognitoService.Paginators.ListUsers(request);
    await foreach (var response in usersPaginator.Responses)
    {
        users.AddRange(response.Users);
    }

    return users;
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar usuários

Este exemplo lista até vinte usuários.

Comando:

```
aws cognito-idp list-users --user-pool-id us-west-2_aaaaaaaaa --limit 20
```

Saída:

```
{
  "Users": [
      {
          "Username": "22704aa3-fc10-479a-97eb-2af5806bd327",
          "Enabled": true,
          "UserStatus": "FORCE_CHANGE_PASSWORD",
          "UserCreateDate": 1548089817.683,
          "UserLastModifiedDate": 1548089817.683,
          "Attributes": [
              {
                  "Name": "sub",
                  "Value": "22704aa3-fc10-479a-97eb-2af5806bd327"
              },
              {
                  "Name": "email_verified",
                  "Value": "true"
              },
              {
                  "Name": "email",
                  "Value": "mary@example.com"
              }
          ]
      }
  ]
}
```

- Para obter detalhes da API, consulte ListUsersem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUsersRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUsersResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListUsers {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <userPoolId>\s

                Where:
                    userPoolId - The ID given to your user pool when it's
 created.
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userPoolId = args[0];
        CognitoIdentityProviderClient cognitoClient =
CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUsers(cognitoClient, userPoolId);
        listUsersFilter(cognitoClient, userPoolId);
        cognitoClient.close();
    }

    public static void listAllUsers(CognitoIdentityProviderClient cognitoClient,
String userPoolId) {
        try {
            ListUsersRequest usersRequest = ListUsersRequest.builder()
                    .userPoolId(userPoolId)
                    .build();

            ListUsersResponse response = cognitoClient.listUsers(usersRequest);
            response.users().forEach(user -> {
                System.out.println("User " + user.username() + " Status " +
user.userStatus() + " Created "
                        + user.userCreateDate());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Shows how to list users by using a filter.
    public static void listUsersFilter(CognitoIdentityProviderClient
cognitoClient, String userPoolId) {

        try {
            String filter = "email = \"tblue@noserver.com\"";
            ListUsersRequest usersRequest = ListUsersRequest.builder()
                    .userPoolId(userPoolId)
```

```
                    .filter(filter)
                    .build();

            ListUsersResponse response = cognitoClient.listUsers(usersRequest);
            response.users().forEach(user -> {
                System.out.println("User with filter applied " + user.username()
 + " Status " + user.userStatus()
                        + " Created " + user.userCreateDate());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listUsers = ({ userPoolId }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ListUsersCommand({
    UserPoolId: userPoolId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllUsers(userPoolId: String) {

    val request = ListUsersRequest {
        this.userPoolId = userPoolId
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use { cognitoClient ->
        val response = cognitoClient.listUsers(request)
        response.users?.forEach { user ->
            println("The user name is ${user.username}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def list_users(self):
        """
        Returns a list of the users in the current user pool.

        :return: The list of users.
        """
        try:
            response =
 self.cognito_idp_client.list_users(UserPoolId=self.user_pool_id)
            users = response["Users"]
        except ClientError as err:
            logger.error(
                "Couldn't list users for %s. Here's why: %s: %s",
                self.user_pool_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return users
```

- Para obter detalhes da API, consulte a ListUsersReferência da API AWSSDK for Python (Boto3).

Reenviar um código de confirmação do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como reenviar um código de confirmação do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Send a new confirmation code to a user.
    /// </summary>
    /// <param name="clientId">The Id of the client application.</param>
    /// <param name="userName">The username of user who will receive the code.</
param>
    /// <returns>The delivery details.</returns>
    public async Task<CodeDeliveryDetailsType> ResendConfirmationCodeAsync(string
 clientId, string userName)
    {
        var codeRequest = new ResendConfirmationCodeRequest
        {
            ClientId = clientId,
            Username = userName,
        };
```

```
        var response = await
_cognitoService.ResendConfirmationCodeAsync(codeRequest);

        Console.WriteLine($"Method of delivery is
{response.CodeDeliveryDetails.DeliveryMedium}");

        return response.CodeDeliveryDetails;
    }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest
request;
        request.SetUsername(userName);
        request.SetClientId(clientID);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome
outcome =
                client.ResendConfirmationCode(request);

        if (outcome.IsSuccess()) {
```

```
            std::cout
                    << "CognitoIdentityProvider::ResendConfirmationCode was
 successful."
                    << std::endl;
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::ResendConfirmationCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como reenviar um código de confirmação

O exemplo `resend-confirmation-code` a seguir envia um código de confirmação ao usuário `jane`.

```
aws cognito-idp resend-confirmation-code \
    --client-id 12a3b456c7de890f11g123hijk \
    --username jane
```

Saída:

```
{
    "CodeDeliveryDetails": {
        "Destination": "j***@e***.com",
        "DeliveryMedium": "EMAIL",
        "AttributeName": "email"
    }
}
```

Para obter mais informações, consulte Como cadastrar e confirmar contas de usuários no Guia do desenvolvedor do Amazon Cognito.

- Para obter detalhes da API, consulte ResendConfirmationCodeem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void resendConfirmationCode(CognitoIdentityProviderClient
identityProviderClient, String clientId,
           String userName) {
       try {
           ResendConfirmationCodeRequest codeRequest =
ResendConfirmationCodeRequest.builder()
                   .clientId(clientId)
                   .username(userName)
                   .build();

           ResendConfirmationCodeResponse response =
identityProviderClient.resendConfirmationCode(codeRequest);
           System.out.println("Method of delivery is " +
response.codeDeliveryDetails().deliveryMediumAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const resendConfirmationCode = ({ clientId, username }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ResendConfirmationCodeCommand({
    ClientId: clientId,
    Username: username,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun resendConfirmationCode(clientIdVal: String?, userNameVal: String?) {
    val codeRequest = ResendConfirmationCodeRequest {
        clientId = clientIdVal
        username = userNameVal
    }
```

```
    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.resendConfirmationCode(codeRequest)
        println("Method of delivery is " +
 (response.codeDeliveryDetails?.deliveryMedium))
    }
}
```

- Para obter detalhes da API, consulte a ResendConfirmationCodereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret
```

```
    def resend_confirmation(self, user_name):
        """
        Prompts Amazon Cognito to resend an email with a new confirmation code.

        :param user_name: The name of the user who will receive the email.
        :return: Delivery information about where the email is sent.
        """
        try:
            kwargs = {"ClientId": self.client_id, "Username": user_name}
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.resend_confirmation_code(**kwargs)
            delivery = response["CodeDeliveryDetails"]
        except ClientError as err:
            logger.error(
                "Couldn't resend confirmation to %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return delivery
```

- Para obter detalhes da API, consulte a ResendConfirmationCodeReferência da API AWSSDK for Python (Boto3).

Responder aos desafios de autenticação SRP do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como responder aos desafios de autenticação SRP do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

CLI

AWS CLI

Como responder a um desafio de autorização

Este exemplo responde a um desafio de autorização iniciado com initiate-auth. É uma resposta ao desafio NEW_PASSWORD_REQUIRED. Ele define uma senha para o usuário jane@example.com.

Comando:

```
aws cognito-idp respond-to-auth-challenge --client-id 3n4b5urk1ft4fl3mg5e62d9ado
 --challenge-name NEW_PASSWORD_REQUIRED --challenge-responses
 USERNAME=jane@example.com,NEW_PASSWORD="password" --session "SESSION_TOKEN"
```

Saída:

```
{
  "ChallengeParameters": {},
  "AuthenticationResult": {
      "AccessToken": "ACCESS_TOKEN",
      "ExpiresIn": 3600,
      "TokenType": "Bearer",
      "RefreshToken": "REFRESH_TOKEN",
      "IdToken": "ID_TOKEN",
      "NewDeviceMetadata": {
          "DeviceKey": "us-west-2_fec070d2-fa88-424a-8ec8-b26d7198eb23",
          "DeviceGroupKey": "-wt2ha1Zd"
      }
  }
}
```

- Para obter detalhes da API, consulte RespondToAuthChallengeem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const respondToAuthChallenge = ({
  clientId,
  username,
  session,
  userPoolId,
  code,
}) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new RespondToAuthChallengeCommand({
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: code,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte RespondToAuthChallengea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça login com um dispositivo rastreado. Para concluir o login, o cliente deve responder corretamente aos desafios de Secure Remote Password (SRP).

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
        """
```

```
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
        with a tracked device lets a user sign in without entering a new MFA
 code.

        Signing in with a tracked device requires that the client respond to the
 SRP
        protocol. The scenario associated with this example uses the warrant
 package
        to help with SRP calculations.

        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains
 an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
```

```
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
{response_init['ChallengeName']}."
                )

            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier =
self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

- Para obter detalhes da API, consulte a RespondToAuthChallengeReferência da API AWSSDK for Python (Boto3).

Responder a um desafio de autenticação do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como responder a um desafio de autenticação do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Respond to an admin authentication challenge.
/// </summary>
/// <param name="userName">The name of the user.</param>
/// <param name="clientId">The client ID.</param>
/// <param name="mfaCode">The multi-factor authentication code.</param>
/// <param name="session">The current application session.</param>
/// <param name="clientId">The user pool ID.</param>
/// <returns>The result of the authentication response.</returns>
public async Task<AuthenticationResultType> AdminRespondToAuthChallengeAsync(
    string userName,
    string clientId,
    string mfaCode,
    string session,
    string userPoolId)
{
    Console.WriteLine("SOFTWARE_TOKEN_MFA challenge is generated");
```

```
        var challengeResponses = new Dictionary<string, string>();
        challengeResponses.Add("USERNAME", userName);
        challengeResponses.Add("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

        var respondToAuthChallengeRequest = new
AdminRespondToAuthChallengeRequest
        {
            ChallengeName = ChallengeNameType.SOFTWARE_TOKEN_MFA,
            ClientId = clientId,
            ChallengeResponses = challengeResponses,
            Session = session,
            UserPoolId = userPoolId,
        };

        var response = await
_cognitoService.AdminRespondToAuthChallengeAsync(respondToAuthChallengeRequest);
        Console.WriteLine($"Response to Authentication
{response.AuthenticationResult.TokenType}");
        return response.AuthenticationResult;
    }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
       request.AddChallengeResponses("USERNAME", userName);
       request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
       request.SetChallengeName(

Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
       request.SetClientId(clientID);
       request.SetUserPoolId(userPoolID);
       request.SetSession(session);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
               client.AdminRespondToAuthChallenge(request);

       if (outcome.IsSuccess()) {
           std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                     << std::endl;

           accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Respond to an authentication challenge.
   public static void adminRespondToAuthChallenge(CognitoIdentityProviderClient
identityProviderClient,
           String userName, String clientId, String mfaCode, String session) {
       System.out.println("SOFTWARE_TOKEN_MFA challenge is generated");
       Map<String, String> challengeResponses = new HashMap<>();

       challengeResponses.put("USERNAME", userName);
       challengeResponses.put("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

       AdminRespondToAuthChallengeRequest respondToAuthChallengeRequest =
AdminRespondToAuthChallengeRequest.builder()
               .challengeName(ChallengeNameType.SOFTWARE_TOKEN_MFA)
               .clientId(clientId)
               .challengeResponses(challengeResponses)
               .session(session)
               .build();

       AdminRespondToAuthChallengeResponse respondToAuthChallengeResult =
identityProviderClient
               .adminRespondToAuthChallenge(respondToAuthChallengeRequest);

System.out.println("respondToAuthChallengeResult.getAuthenticationResult()"
               + respondToAuthChallengeResult.authenticationResult());
   }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminRespondToAuthChallenge = ({
  userPoolId,
  clientId,
  username,
  totp,
  session,
}) => {
  const client = new CognitoIdentityProviderClient({});
  const command = new AdminRespondToAuthChallengeCommand({
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: totp,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Respond to an authentication challenge.
suspend fun adminRespondToAuthChallenge(userName: String, clientIdVal: String?,
 mfaCode: String, sessionVal: String?) {
    println("SOFTWARE_TOKEN_MFA challenge is generated")
    val challengeResponsesOb = mutableMapOf<String, String>()
    challengeResponsesOb["USERNAME"] = userName
    challengeResponsesOb["SOFTWARE_TOKEN_MFA_CODE"] = mfaCode

    val adminRespondToAuthChallengeRequest = AdminRespondToAuthChallengeRequest {
        challengeName = ChallengeNameType.SoftwareTokenMfa
        clientId = clientIdVal
        challengeResponses = challengeResponsesOb
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val respondToAuthChallengeResult =
 identityProviderClient.adminRespondToAuthChallenge(adminRespondToAuthChallengeRequest)
        println("respondToAuthChallengeResult.getAuthenticationResult()
 ${respondToAuthChallengeResult.authenticationResult}")
    }
}
```

- Para obter detalhes da API, consulte a AdminRespondToAuthChallengereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Responda a um desafio de MFA fornecendo um código gerado por uma aplicação de MFA associada.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def respond_to_mfa_challenge(self, user_name, session, mfa_code):
        """
        Responds to a challenge for an MFA code. This completes the second step
 of
        a two-factor sign-in. When sign-in is successful, it returns an access
 token
        that can be used to get AWS credentials from Amazon Cognito.

        :param user_name: The name of the user who is signing in.
```

```
        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :param mfa_code: A code generated by the associated MFA application.
        :return: The result of the authentication. When successful, this contains
an
                 access token for the user.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "ChallengeName": "SOFTWARE_TOKEN_MFA",
                "Session": session,
                "ChallengeResponses": {
                    "USERNAME": user_name,
                    "SOFTWARE_TOKEN_MFA_CODE": mfa_code,
                },
            }
            if self.client_secret is not None:
                kwargs["ChallengeResponses"]["SECRET_HASH"] = self._secret_hash(
                    user_name
                )
            response =
self.cognito_idp_client.admin_respond_to_auth_challenge(**kwargs)
            auth_result = response["AuthenticationResult"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "ExpiredCodeException":
                logger.warning(
                    "Your MFA code has expired or has been used already. You
might have "
                    "to wait a few seconds until your app shows you a new code."
                )
            else:
                logger.error(
                    "Couldn't respond to mfa challenge for %s. Here's why: %s:
%s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return auth_result
```

- Para obter detalhes da API, consulte a AdminRespondToAuthChallengeReferência da API AWSSDK for Python (Boto3).

Inscrever um usuário no Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como inscrever um usuário no Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Sign up a new user.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The username to use.</param>
    /// <param name="password">The user's password.</param>
    /// <param name="email">The email address of the user.</param>
    /// <returns>A Boolean value indicating whether the user was confirmed.</
returns>
    public async Task<bool> SignUpAsync(string clientId, string userName, string
 password, string email)
    {
        var userAttrs = new AttributeType
        {
            Name = "email",
```

```
            Value = email,
        };

        var userAttrsList = new List<AttributeType>();

        userAttrsList.Add(userAttrs);

        var signUpRequest = new SignUpRequest
        {
            UserAttributes = userAttrsList,
            Username = userName,
            ClientId = clientId,
            Password = password
        };

        var response = await _cognitoService.SignUpAsync(signUpRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::SignUpRequest request;
        request.AddUserAttributes(
```

```
                Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                        "email").WithValue(email));
        request.SetUsername(userName);
        request.SetPassword(password);
        request.SetClientId(clientID);
        Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
                client.SignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "The signup request for " << userName << " was
successful."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==

Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
            std::cout
                    << "The username already exists. Please enter a different
username."
                    << std::endl;
            userExists = true;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como inscrever um usuário

Este exemplo inscreve jane@example.com.

Comando:

```
aws cognito-idp sign-up --client-id 3n4b5urk1ft4fl3mg5e62d9ado --
username jane@example.com --password PASSWORD --user-attributes
 Name="email",Value="jane@example.com" Name="name",Value="Jane"
```

Saída:

```
{
  "UserConfirmed": false,
  "UserSub": "e04d60a6-45dc-441c-a40b-e25a787d4862"
}
```

- Para obter detalhes da API, consulte SignUpem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void signUp(CognitoIdentityProviderClient
 identityProviderClient, String clientId, String userName,
            String password, String email) {
        AttributeType userAttrs = AttributeType.builder()
                .name("email")
                .value(email)
                .build();

        List<AttributeType> userAttrsList = new ArrayList<>();
        userAttrsList.add(userAttrs);
        try {
            SignUpRequest signUpRequest = SignUpRequest.builder()
                    .userAttributes(userAttrsList)
                    .username(userName)
                    .clientId(clientId)
                    .password(password)
                    .build();
```

```
            identityProviderClient.signUp(signUpRequest);
            System.out.println("User has been signed up ");

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const signUp = ({ clientId, username, password, email }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new SignUpCommand({
    ClientId: clientId,
    Username: username,
    Password: password,
    UserAttributes: [{ Name: "email", Value: email }],
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun signUp(clientIdVal: String?, userNameVal: String?, passwordVal:
 String?, emailVal: String?) {
    val userAttrs = AttributeType {
        name = "email"
        value = emailVal
    }

    val userAttrsList = mutableListOf<AttributeType>()
    userAttrsList.add(userAttrs)
    val signUpRequest = SignUpRequest {
        userAttributes = userAttrsList
        username = userNameVal
        clientId = clientIdVal
        password = passwordVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.signUp(signUpRequest)
        println("User has been signed up")
    }
}
```

- Para obter detalhes da API, consulte a SignUpreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon
 Cognito
        to send an email to the specified email address. The email contains a
 code that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
 whether
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
```

```
        :param password: The password for the new user.
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name,
response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return confirmed
```

- Para obter detalhes da API, consulte a SignUpReferência da API AWSSDK for Python (Boto3).

Iniciar a autenticação usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar a autenticação com o Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate authorization.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The name of the user who is authenticating.</
param>
    /// <param name="password">The password for the user who is authenticating.</
param>
    /// <returns>The response from the initiate auth request.</returns>
    public async Task<InitiateAuthResponse> InitiateAuthAsync(string clientId,
 string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var authRequest = new InitiateAuthRequest

        {
            ClientId = clientId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.USER_PASSWORD_AUTH,
```

```
        };

        var response = await _cognitoService.InitiateAuthAsync(authRequest);
        Console.WriteLine($"Result Challenge is : {response.ChallengeName}");

        return response;
    }
```

- Para obter detalhes da API, consulte InitiateAuth a Referência AWS SDK for .NET da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const initiateAuth = ({ username, password, clientId }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new InitiateAuthCommand({
    AuthFlow: AuthFlowType.USER_PASSWORD_AUTH,
    AuthParameters: {
      USERNAME: username,
      PASSWORD: password,
    },
    ClientId: clientId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte InitiateAuth a Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo mostra como iniciar a autenticação com um dispositivo rastreado. Para concluir o login, o cliente deve responder corretamente aos desafios de Secure Remote Password (SRP).

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
```

```
        """
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
        with a tracked device lets a user sign in without entering a new MFA
 code.

        Signing in with a tracked device requires that the client respond to the
 SRP
        protocol. The scenario associated with this example uses the warrant
 package
        to help with SRP calculations.

        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains
 an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
```

```
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
{response_init['ChallengeName']}."
                )

            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier =
self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

- Para obter detalhes da API, consulte a InitiateAuthReferência da API AWSSDK for Python (Boto3).

Iniciar a autenticação com o Amazon Cognito e as credenciais de administrador usando um AWS SDK

Os exemplos de código a seguir mostram como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate an admin auth request.
    /// </summary>
    /// <param name="clientId">The client ID to use.</param>
    /// <param name="userPoolId">The ID of the user pool.</param>
    /// <param name="userName">The username to authenticate.</param>
    /// <param name="password">The user's password.</param>
    /// <returns>The session to use in challenge-response.</returns>
    public async Task<string> AdminInitiateAuthAsync(string clientId, string
 userPoolId, string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
```

```
        authParameters.Add("PASSWORD", password);

        var request = new AdminInitiateAuthRequest
        {
            ClientId = clientId,
            UserPoolId = userPoolId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.AdminInitiateAuthAsync(request);
        return response.Session;
    }
```

- Para obter detalhes da API, consulte AdminInitiateAutha Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
    request.SetClientId(clientID);
    request.SetUserPoolId(userPoolID);
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(
```

```
Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);


   Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
           client.AdminInitiateAuth(request);

   if (outcome.IsSuccess()) {
       std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
       sessionResult = outcome.GetResult().GetSession();
   }
   else {
       std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                 << outcome.GetError().GetMessage()
                 << std::endl;
   }
```

- Para obter detalhes da API, consulte AdminInitiateAutha Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como iniciar a autorização

Este exemplo inicia a autorização usando o fluxo ADMIN_NO_SRP_AUTH para o nome de usuário jane@example.com

O cliente deve ter a API de login para autenticação baseada em servidor (ADMIN_NO_SRP_AUTH) habilitada.

Use as informações da sessão no valor de retorno para chamar admin-respond-to-auth -challenge.

Comando:

```
aws cognito-idp admin-initiate-auth --user-pool-id us-west-2_aaaaaaaaa --client-
id 3n4b5urk1ft4fl3mg5e62d9ado --auth-flow ADMIN_NO_SRP_AUTH --auth-parameters
 USERNAME=jane@example.com,PASSWORD=password
```

Saída:

```
{
  "ChallengeName": "NEW_PASSWORD_REQUIRED",
  "Session": "SESSION",
  "ChallengeParameters": {
      "USER_ID_FOR_SRP": "84514837-dcbc-4af1-abff-f3c109334894",
      "requiredAttributes": "[]",
      "userAttributes": "{\"email_verified\":\"true\",\"phone_number_verified\":
\"true\",\"phone_number\":\"+01xxx5550100\",\"email\":\"jane@example.com\"}"
  }
}
```

- Para obter detalhes da API, consulte AdminInitiateAuthem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static AdminInitiateAuthResponse
initiateAuth(CognitoIdentityProviderClient identityProviderClient,
           String clientId, String userName, String password, String userPoolId)
{
       try {
           Map<String, String> authParameters = new HashMap<>();
           authParameters.put("USERNAME", userName);
           authParameters.put("PASSWORD", password);

           AdminInitiateAuthRequest authRequest =
AdminInitiateAuthRequest.builder()
                   .clientId(clientId)
                   .userPoolId(userPoolId)
                   .authParameters(authParameters)
                   .authFlow(AuthFlowType.ADMIN_USER_PASSWORD_AUTH)
```

```
                    .build();

            AdminInitiateAuthResponse response =
 identityProviderClient.adminInitiateAuth(authRequest);
            System.out.println("Result Challenge is : " +
 response.challengeName());
            return response;

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }
```

- Para obter detalhes da API, consulte AdminInitiateAutha Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminInitiateAuth = ({ clientId, userPoolId, username, password }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new AdminInitiateAuthCommand({
    ClientId: clientId,
    UserPoolId: userPoolId,
    AuthFlow: AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
    AuthParameters: { USERNAME: username, PASSWORD: password },
  });

  return client.send(command);
```

```
};
```

- Para obter detalhes da API, consulte AdminInitiateAutha Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkAuthMethod(clientIdVal: String, userNameVal: String,
 passwordVal: String, userPoolIdVal: String): AdminInitiateAuthResponse {
    val authParas = mutableMapOf<String, String>()
    authParas["USERNAME"] = userNameVal
    authParas["PASSWORD"] = passwordVal

    val authRequest = AdminInitiateAuthRequest {
        clientId = clientIdVal
        userPoolId = userPoolIdVal
        authParameters = authParas
        authFlow = AuthFlowType.AdminUserPasswordAuth
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminInitiateAuth(authRequest)
        println("Result Challenge is ${response.challengeName}")
        return response
    }
}
```

- Para obter detalhes da API, consulte a AdminInitiateAuthreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def start_sign_in(self, user_name, password):
        """
        Starts the sign-in process for a user by using administrator credentials.
        This method of signing in is appropriate for code running on a secure
 server.

        If the user pool is configured to require MFA and this is the first sign-
in
        for the user, Amazon Cognito returns a challenge response to set up an
        MFA application. When this occurs, this function gets an MFA secret from
        Amazon Cognito and returns it to the caller.

        :param user_name: The name of the user to sign in.
```

```
        :param password: The user's password.
        :return: The result of the sign-in attempt. When sign-in is successful,
this
                 returns an access token that can be used to get AWS credentials.
Otherwise,
                 Amazon Cognito returns a challenge to set up an MFA application,
                 or a challenge to enter an MFA code from a registered MFA
application.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "AuthFlow": "ADMIN_USER_PASSWORD_AUTH",
                "AuthParameters": {"USERNAME": user_name, "PASSWORD": password},
            }
            if self.client_secret is not None:
                kwargs["AuthParameters"]["SECRET_HASH"] =
self._secret_hash(user_name)
            response = self.cognito_idp_client.admin_initiate_auth(**kwargs)
            challenge_name = response.get("ChallengeName", None)
            if challenge_name == "MFA_SETUP":
                if (
                    "SOFTWARE_TOKEN_MFA"
                    in response["ChallengeParameters"]["MFAS_CAN_SETUP"]
                ):
                    response.update(self.get_mfa_secret(response["Session"]))
                else:
                    raise RuntimeError(
                        "The user pool requires MFA setup, but the user pool is
not "
                        "configured for TOTP MFA. This example requires TOTP
MFA."
                    )
        except ClientError as err:
            logger.error(
                "Couldn't start sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
```

```
            return response
```

- Para obter detalhes da API, consulte a AdminInitiateAuthReferência da API AWSSDK for Python (Boto3).

Verificar uma aplicação de MFA com um usuário do Amazon Cognito usando um AWS SDK

Os exemplos de código a seguir mostram como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Inscrever um usuário em um grupo de usuários que exija MFA

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Verify the TOTP and register for MFA.
   /// </summary>
   /// <param name="session">The name of the session.</param>
   /// <param name="code">The MFA code.</param>
   /// <returns>The status of the software token.</returns>
   public async Task<VerifySoftwareTokenResponseType>
VerifySoftwareTokenAsync(string session, string code)
   {
       var tokenRequest = new VerifySoftwareTokenRequest
       {
           UserCode = code,
```

```
            Session = session,
        };

        var verifyResponse = await
_cognitoService.VerifySoftwareTokenAsync(tokenRequest);

        return verifyResponse.Status;
    }
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout << "Verification of the code was successful."
                      << std::endl;
```

```
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Verify the TOTP and register for MFA.
    public static void verifyTOTP(CognitoIdentityProviderClient
identityProviderClient, String session, String code) {
        try {
            VerifySoftwareTokenRequest tokenRequest =
VerifySoftwareTokenRequest.builder()
                    .userCode(code)
                    .session(session)
                    .build();

            VerifySoftwareTokenResponse verifyResponse =
identityProviderClient.verifySoftwareToken(tokenRequest);
            System.out.println("The status of the token is " +
verifyResponse.statusAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const verifySoftwareToken = (totp) => {
  const client = new CognitoIdentityProviderClient({});

  // The 'Session' is provided in the response to 'AssociateSoftwareToken'.
  const session = process.env.SESSION;

  if (!session) {
    throw new Error(
      "Missing a valid Session. Did you run 'admin-initiate-auth'?",
    );
  }

  const command = new VerifySoftwareTokenCommand({
    Session: session,
    UserCode: totp,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Verify the TOTP and register for MFA.
suspend fun verifyTOTP(sessionVal: String?, codeVal: String?) {
    val tokenRequest = VerifySoftwareTokenRequest {
        userCode = codeVal
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val verifyResponse =
 identityProviderClient.verifySoftwareToken(tokenRequest)
        println("The status of the token is ${verifyResponse.status}")
    }
}
```

- Para obter detalhes da API, consulte a VerifySoftwareTokenreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
```

```
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def verify_mfa(self, session, user_code):
        """
        Verify a new MFA application that is associated with a user.

        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :param user_code: A code generated by the associated MFA application.
        :return: Status that indicates whether the MFA application is verified.
        """
        try:
            response = self.cognito_idp_client.verify_software_token(
                Session=session, UserCode=user_code
            )
        except ClientError as err:
            logger.error(
                "Couldn't verify MFA. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response
```

- Para obter detalhes da API, consulte a VerifySoftwareTokenReferência da API AWSSDK for Python (Boto3).

Cenários do Amazon Cognito Identity Provider usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Identity Provider com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Inscrever um usuário em um grupo de usuários do Amazon Cognito que exija MFA usando um AWS SDK

Inscrever um usuário em um grupo de usuários do Amazon Cognito que exija MFA usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace CognitoBasics;

public class CognitoBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Cognito.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonCognitoIdentityProvider>()
            .AddTransient<CognitoWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<CognitoBasics>();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var cognitoWrapper = host.Services.GetRequiredService<CognitoWrapper>();

        Console.WriteLine(new string('-', 80));
        UiMethods.DisplayOverview();
        Console.WriteLine(new string('-', 80));

        // clientId - The app client Id value that you get from the AWS CDK
 script.
        var clientId = configuration["ClientId"]; // "*** REPLACE WITH CLIENT ID
 VALUE FROM CDK SCRIPT";
```

```
        // poolId - The pool Id that you get from the AWS CDK script.
        var poolId = configuration["PoolId"]!; // "*** REPLACE WITH POOL ID VALUE
FROM CDK SCRIPT";
        var userName = configuration["UserName"];
        var password = configuration["Password"];
        var email = configuration["Email"];

        // If the username wasn't set in the configuration file,
        // get it from the user now.
        if (userName is null)
        {
            do
            {
                Console.Write("Username: ");
                userName = Console.ReadLine();
            }
            while (string.IsNullOrEmpty(userName));
        }
        Console.WriteLine($"\nUsername: {userName}");

        // If the password wasn't set in the configuration file,
        // get it from the user now.
        if (password is null)
        {
            do
            {
                Console.Write("Password: ");
                password = Console.ReadLine();
            }
            while (string.IsNullOrEmpty(password));
        }

        // If the email address wasn't set in the configuration file,
        // get it from the user now.
        if (email is null)
        {
            do
            {
                Console.Write("Email: ");
                email = Console.ReadLine();
            } while (string.IsNullOrEmpty(email));
        }

        // Now sign up the user.
```

```
        Console.WriteLine($"\nSigning up {userName} with email address:
{email}");
        await cognitoWrapper.SignUpAsync(clientId, userName, password, email);

        // Add the user to the user pool.
        Console.WriteLine($"Adding {userName} to the user pool");
        await cognitoWrapper.GetAdminUserAsync(userName, poolId);

        UiMethods.DisplayTitle("Get confirmation code");
        Console.WriteLine($"Conformation code sent to {userName}.");
        Console.Write("Would you like to send a new code? (Y/N) ");
        var answer = Console.ReadLine();

        if (answer!.ToLower() == "y")
        {
            await cognitoWrapper.ResendConfirmationCodeAsync(clientId, userName);
            Console.WriteLine("Sending a new confirmation code");
        }

        Console.Write("Enter confirmation code (from Email): ");
        var code = Console.ReadLine();

        await cognitoWrapper.ConfirmSignupAsync(clientId, code, userName);

        UiMethods.DisplayTitle("Checking status");
        Console.WriteLine($"Rechecking the status of {userName} in the user
pool");
        await cognitoWrapper.GetAdminUserAsync(userName, poolId);

        Console.WriteLine($"Setting up authenticator for {userName} in the user
pool");
        var setupResponse = await cognitoWrapper.InitiateAuthAsync(clientId,
userName, password);

        var setupSession = await
cognitoWrapper.AssociateSoftwareTokenAsync(setupResponse.Session);
        Console.Write("Enter the 6-digit code displayed in Google Authenticator:
");
        var setupCode = Console.ReadLine();

        var setupResult = await
cognitoWrapper.VerifySoftwareTokenAsync(setupSession, setupCode);
        Console.WriteLine($"Setup status: {setupResult}");
```

```
        Console.WriteLine($"Now logging in {userName} in the user pool");
        var authSession = await cognitoWrapper.AdminInitiateAuthAsync(clientId,
 poolId, userName, password);

        Console.Write("Enter a new 6-digit code displayed in Google
 Authenticator: ");
        var authCode = Console.ReadLine();

        var authResult = await
 cognitoWrapper.AdminRespondToAuthChallengeAsync(userName, clientId, authCode,
 authSession, poolId);
        Console.WriteLine($"Authenticated and received access token:
 {authResult.AccessToken}");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Cognito scenario is complete.");
        Console.WriteLine(new string('-', 80));
    }
}


using System.Net;

namespace CognitoActions;

/// <summary>
/// Methods to perform Amazon Cognito Identity Provider actions.
/// </summary>
public class CognitoWrapper
{
    private readonly IAmazonCognitoIdentityProvider _cognitoService;

    /// <summary>
    /// Constructor for the wrapper class containing Amazon Cognito actions.
    /// </summary>
    /// <param name="cognitoService">The Amazon Cognito client object.</param>
    public CognitoWrapper(IAmazonCognitoIdentityProvider cognitoService)
    {
        _cognitoService = cognitoService;
    }

    /// <summary>
    /// List the Amazon Cognito user pools for an account.
    /// </summary>
```

```
    /// <returns>A list of UserPoolDescriptionType objects.</returns>
    public async Task<List<UserPoolDescriptionType>> ListUserPoolsAsync()
    {
        var userPools = new List<UserPoolDescriptionType>();

        var userPoolsPaginator = _cognitoService.Paginators.ListUserPools(new
ListUserPoolsRequest());

        await foreach (var response in userPoolsPaginator.Responses)
        {
            userPools.AddRange(response.UserPools);
        }

        return userPools;
    }


    /// <summary>
    /// Get a list of users for the Amazon Cognito user pool.
    /// </summary>
    /// <param name="userPoolId">The user pool ID.</param>
    /// <returns>A list of users.</returns>
    public async Task<List<UserType>> ListUsersAsync(string userPoolId)
    {
        var request = new ListUsersRequest
        {
            UserPoolId = userPoolId
        };

        var users = new List<UserType>();

        var usersPaginator = _cognitoService.Paginators.ListUsers(request);
        await foreach (var response in usersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }


    /// <summary>
    /// Respond to an admin authentication challenge.
    /// </summary>
```

```
    /// <param name="userName">The name of the user.</param>
    /// <param name="clientId">The client ID.</param>
    /// <param name="mfaCode">The multi-factor authentication code.</param>
    /// <param name="session">The current application session.</param>
    /// <param name="clientId">The user pool ID.</param>
    /// <returns>The result of the authentication response.</returns>
    public async Task<AuthenticationResultType> AdminRespondToAuthChallengeAsync(
        string userName,
        string clientId,
        string mfaCode,
        string session,
        string userPoolId)
    {
        Console.WriteLine("SOFTWARE_TOKEN_MFA challenge is generated");

        var challengeResponses = new Dictionary<string, string>();
        challengeResponses.Add("USERNAME", userName);
        challengeResponses.Add("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

        var respondToAuthChallengeRequest = new
AdminRespondToAuthChallengeRequest
        {
            ChallengeName = ChallengeNameType.SOFTWARE_TOKEN_MFA,
            ClientId = clientId,
            ChallengeResponses = challengeResponses,
            Session = session,
            UserPoolId = userPoolId,
        };

        var response = await
_cognitoService.AdminRespondToAuthChallengeAsync(respondToAuthChallengeRequest);
        Console.WriteLine($"Response to Authentication
{response.AuthenticationResult.TokenType}");
        return response.AuthenticationResult;
    }


    /// <summary>
    /// Verify the TOTP and register for MFA.
    /// </summary>
    /// <param name="session">The name of the session.</param>
    /// <param name="code">The MFA code.</param>
    /// <returns>The status of the software token.</returns>
```

```
   public async Task<VerifySoftwareTokenResponseType>
VerifySoftwareTokenAsync(string session, string code)
   {
       var tokenRequest = new VerifySoftwareTokenRequest
       {
           UserCode = code,
           Session = session,
       };

       var verifyResponse = await
_cognitoService.VerifySoftwareTokenAsync(tokenRequest);

       return verifyResponse.Status;
   }


   /// <summary>
   /// Get an MFA token to authenticate the user with the authenticator.
   /// </summary>
   /// <param name="session">The session name.</param>
   /// <returns>The session name.</returns>
   public async Task<string> AssociateSoftwareTokenAsync(string session)
   {
       var softwareTokenRequest = new AssociateSoftwareTokenRequest
       {
           Session = session,
       };

       var tokenResponse = await
_cognitoService.AssociateSoftwareTokenAsync(softwareTokenRequest);
       var secretCode = tokenResponse.SecretCode;

       Console.WriteLine($"Use the following secret code to set up the
authenticator: {secretCode}");

       return tokenResponse.Session;
   }


   /// <summary>
   /// Initiate an admin auth request.
   /// </summary>
   /// <param name="clientId">The client ID to use.</param>
   /// <param name="userPoolId">The ID of the user pool.</param>
```

```
    /// <param name="userName">The username to authenticate.</param>
    /// <param name="password">The user's password.</param>
    /// <returns>The session to use in challenge-response.</returns>
    public async Task<string> AdminInitiateAuthAsync(string clientId, string
 userPoolId, string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var request = new AdminInitiateAuthRequest
        {
            ClientId = clientId,
            UserPoolId = userPoolId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.AdminInitiateAuthAsync(request);
        return response.Session;
    }

    /// <summary>
    /// Initiate authorization.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The name of the user who is authenticating.</
param>
    /// <param name="password">The password for the user who is authenticating.</
param>
    /// <returns>The response from the initiate auth request.</returns>
    public async Task<InitiateAuthResponse> InitiateAuthAsync(string clientId,
 string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var authRequest = new InitiateAuthRequest

        {
            ClientId = clientId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.USER_PASSWORD_AUTH,
```

```
        };

        var response = await _cognitoService.InitiateAuthAsync(authRequest);
        Console.WriteLine($"Result Challenge is : {response.ChallengeName}");

        return response;
    }

    /// <summary>
    /// Confirm that the user has signed up.
    /// </summary>
    /// <param name="clientId">The Id of this application.</param>
    /// <param name="code">The confirmation code sent to the user.</param>
    /// <param name="userName">The username.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> ConfirmSignupAsync(string clientId, string code,
 string userName)
    {
        var signUpRequest = new ConfirmSignUpRequest
        {
            ClientId = clientId,
            ConfirmationCode = code,
            Username = userName,
        };

        var response = await _cognitoService.ConfirmSignUpAsync(signUpRequest);
        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            Console.WriteLine($"{userName} was confirmed");
            return true;
        }
        return false;
    }


    /// <summary>
    /// Initiates and confirms tracking of the device.
    /// </summary>
    /// <param name="accessToken">The user's access token.</param>
    /// <param name="deviceKey">The key of the device from Amazon Cognito.</
param>
    /// <param name="deviceName">The device name.</param>
    /// <returns></returns>
```

```
    public async Task<bool> ConfirmDeviceAsync(string accessToken, string
 deviceKey, string deviceName)
    {
        var request = new ConfirmDeviceRequest
        {
            AccessToken = accessToken,
            DeviceKey = deviceKey,
            DeviceName = deviceName
        };

        var response = await _cognitoService.ConfirmDeviceAsync(request);
        return response.UserConfirmationNecessary;
    }


    /// <summary>
    /// Send a new confirmation code to a user.
    /// </summary>
    /// <param name="clientId">The Id of the client application.</param>
    /// <param name="userName">The username of user who will receive the code.</
param>
    /// <returns>The delivery details.</returns>
    public async Task<CodeDeliveryDetailsType> ResendConfirmationCodeAsync(string
 clientId, string userName)
    {
        var codeRequest = new ResendConfirmationCodeRequest
        {
            ClientId = clientId,
            Username = userName,
        };

        var response = await
 _cognitoService.ResendConfirmationCodeAsync(codeRequest);

        Console.WriteLine($"Method of delivery is
 {response.CodeDeliveryDetails.DeliveryMedium}");

        return response.CodeDeliveryDetails;
    }


    /// <summary>
    /// Get the specified user from an Amazon Cognito user pool with
 administrator access.
```

```
    /// </summary>
    /// <param name="userName">The name of the user.</param>
    /// <param name="poolId">The Id of the Amazon Cognito user pool.</param>
    /// <returns>Async task.</returns>
    public async Task<UserStatusType> GetAdminUserAsync(string userName, string
 poolId)
    {
        AdminGetUserRequest userRequest = new AdminGetUserRequest
        {
            Username = userName,
            UserPoolId = poolId,
        };

        var response = await _cognitoService.AdminGetUserAsync(userRequest);

        Console.WriteLine($"User status {response.UserStatus}");
        return response.UserStatus;
    }


    /// <summary>
    /// Sign up a new user.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The username to use.</param>
    /// <param name="password">The user's password.</param>
    /// <param name="email">The email address of the user.</param>
    /// <returns>A Boolean value indicating whether the user was confirmed.</
returns>
    public async Task<bool> SignUpAsync(string clientId, string userName, string
 password, string email)
    {
        var userAttrs = new AttributeType
        {
            Name = "email",
            Value = email,
        };

        var userAttrsList = new List<AttributeType>();

        userAttrsList.Add(userAttrs);

        var signUpRequest = new SignUpRequest
        {
```

```
            UserAttributes = userAttrsList,
            Username = userName,
            ClientId = clientId,
            Password = password
        };

        var response = await _cognitoService.SignUpAsync(signUpRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Scenario that adds a user to an Amazon Cognito user pool.
/*!
  \sa gettingStartedWithUserPools()
  \param clientID: Client ID associated with an Amazon Cognito user pool.
  \param userPoolID: An Amazon Cognito user pool ID.
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
 */
bool AwsDoc::Cognito::gettingStartedWithUserPools(const Aws::String &clientID,
                                                  const Aws::String &userPoolID,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    printAsterisksLine();
    std::cout
            << "Welcome to the Amazon Cognito example scenario."
            << std::endl;
    printAsterisksLine();

    std::cout
            << "This scenario will add a user to an Amazon Cognito user pool."
            << std::endl;
    const Aws::String userName = askQuestion("Enter a new username: ");
    const Aws::String password = askQuestion("Enter a new password: ");
    const Aws::String email = askQuestion("Enter a valid email for the user: ");

    std::cout << "Signing up " << userName << std::endl;
```

```
   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);
   bool userExists = false;
   do {
       // 1. Add a user with a username, password, and email address.
       Aws::CognitoIdentityProvider::Model::SignUpRequest request;
       request.AddUserAttributes(
               Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                       "email").WithValue(email));
       request.SetUsername(userName);
       request.SetPassword(password);
       request.SetClientId(clientID);
       Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
               client.SignUp(request);

       if (outcome.IsSuccess()) {
           std::cout << "The signup request for " << userName << " was
successful."
                     << std::endl;
       }
       else if (outcome.GetError().GetErrorType() ==

Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
           std::cout
                   << "The username already exists. Please enter a different
username."
                   << std::endl;
           userExists = true;
       }
       else {
           std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
   } while (userExists);

   printAsterisksLine();
   std::cout << "Retrieving status of " << userName << " in the user pool."
             << std::endl;
   // 2. Confirm that the user was added to the user pool.
   if (!checkAdminUserStatus(userName, userPoolID, client)) {
       return false;
   }
```

```
   std::cout << "A confirmation code was sent to " << email << "." << std::endl;

   bool resend = askYesNoQuestion("Would you like to send a new code? (y/n) ");
   if (resend) {
       // Request a resend of the confirmation code to the email address.
(ResendConfirmationCode)
       Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest
request;
       request.SetUsername(userName);
       request.SetClientId(clientID);

       Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome
outcome =
               client.ResendConfirmationCode(request);

       if (outcome.IsSuccess()) {
           std::cout
                   << "CognitoIdentityProvider::ResendConfirmationCode was
successful."
                   << std::endl;
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::ResendConfirmationCode. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
   }

   printAsterisksLine();

   {
       // 4. Send the confirmation code that's received in the email.
(ConfirmSignUp)
       const Aws::String confirmationCode = askQuestion(
               "Enter the confirmation code that was emailed: ");
       Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
       request.SetClientId(clientID);
       request.SetConfirmationCode(confirmationCode);
       request.SetUsername(userName);

       Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
```

```
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "Rechecking the status of " << userName << " in the user pool."
              << std::endl;
    if (!checkAdminUserStatus(userName, userPoolID, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout << "Initiating authorization using the username and password."
              << std::endl;

    Aws::String session;
    // 5. Initiate authorization with username and password. (AdminInitiateAuth)
    if (!adminInitiateAuthorization(clientID, userPoolID,  userName, password,
 session, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout
            << "Starting setup of time-based one-time password (TOTP) multi-
factor authentication (MFA)."
            << std::endl;

    {
        // 6. Request a setup key for one-time password (TOTP)
        //    multi-factor authentication (MFA). (AssociateSoftwareToken)
        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest
 request;
```

```
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome
 outcome =
                client.AssociateSoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for
 example Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::AssociateSoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
    askQuestion("Type enter to continue...", alwaysTrueTest);

    printAsterisksLine();

    {
        Aws::String userCode = askQuestion(
                "Enter the 6 digit code displayed in the authenticator app: ");

        //  7. Send the MFA code copied from an authenticator app.
 (VerifySoftwareToken)
        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
```

```
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout << "Verification of the code was successful."
                      << std::endl;
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "You have completed the MFA authentication setup." << std::endl;
    std::cout << "Now, sign in." << std::endl;

    // 8. Initiate authorization again with username and password.
(AdminInitiateAuth)
    if (!adminInitiateAuthorization(clientID, userPoolID, userName, password,
session, client)) {
        return false;
    }

    Aws::String accessToken;
    {
        Aws::String mfaCode = askQuestion(
                "Re-enter the 6 digit code displayed in the authenticator app:
");

        // 9. Send a new MFA code copied from an authenticator app.
(AdminRespondToAuthChallenge)
        Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
        request.AddChallengeResponses("USERNAME", userName);
        request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
        request.SetChallengeName(
```

```
Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
       request.SetClientId(clientID);
       request.SetUserPoolId(userPoolID);
       request.SetSession(session);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
               client.AdminRespondToAuthChallenge(request);

       if (outcome.IsSuccess()) {
           std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                     << std::endl;

           accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }

       std::cout << "You have successfully added a user to Amazon Cognito."
                 << std::endl;
   }

   if (askYesNoQuestion("Would you like to delete the user that you just added?
(y/n) ")) {
       // 10. Delete the user that you just added. (DeleteUser)
       Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
       request.SetAccessToken(accessToken);

       Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
               client.DeleteUser(request);

       if (outcome.IsSuccess()) {
           std::cout << "The user " << userName << " was deleted."
                     << std::endl;
       }
```

```
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    return true;
}

//! Routine which checks the user status in an Amazon Cognito user pool.
/*!
 \sa checkAdminUserStatus()
 \param userName: A username.
 \param userPoolID: An Amazon Cognito user pool ID.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::checkAdminUserStatus(const Aws::String &userName,
                                           const Aws::String &userPoolID,
                                           const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);

    Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
            client.AdminGetUser(request);

    if (outcome.IsSuccess()) {
        std::cout << "The status for " << userName << " is " <<

 Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                         outcome.GetResult().GetUserStatus()) << std::endl;
        std::cout << "Enabled is " << outcome.GetResult().GetEnabled() <<
 std::endl;
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which starts authorization of an Amazon Cognito user.
//! This routine requires administrator credentials.
/*!
 \sa adminInitiateAuthorization()
 \param clientID: Client ID of tracked device.
 \param userPoolID: An Amazon Cognito user pool ID.
 \param userName: A username.
 \param password: A password.
 \param sessionResult: String to receive a session token.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::adminInitiateAuthorization(const Aws::String &clientID,
                                                 const Aws::String &userPoolID,
                                                 const Aws::String &userName,
                                                 const Aws::String &password,
                                                 Aws::String &sessionResult,
                                                 const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
    request.SetClientId(clientID);
    request.SetUserPoolId(userPoolID);
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(

 Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);


    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
            client.AdminInitiateAuth(request);

    if (outcome.IsSuccess()) {
        std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
        sessionResult = outcome.GetResult().GetSession();
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminGetUserRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminGetUserResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminInitiateAuthRequest;
```

```
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminInitiateAuthResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminRespondToAuthChalleng
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminRespondToAuthChalleng
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AssociateSoftwareTokenRequ
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AssociateSoftwareTokenResp
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AttributeType;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AuthFlowType;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ChallengeNameType;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExc
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ConfirmSignUpRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ResendConfirmationCodeRequ
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ResendConfirmationCodeResp
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.SignUpRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.VerifySoftwareTokenRequest
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.VerifySoftwareTokenRespons
import java.security.InvalidKeyException;
import java.security.NoSuchAlgorithmException;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;
import java.util.Scanner;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * TIP: To set up the required user pool, run the AWS Cloud Development Kit (AWS
 * CDK) script provided in this GitHub repo at
 * resources/cdk/cognito_scenario_user_pool_with_mfa.
 *
 * This code example performs the following operations:
 *
 * 1. Invokes the signUp method to sign up a user.
 * 2. Invokes the adminGetUser method to get the user's confirmation status.
 * 3. Invokes the ResendConfirmationCode method if the user requested another
 * code.
 * 4. Invokes the confirmSignUp method.
 * 5. Invokes the AdminInitiateAuth to sign in. This results in being prompted
 * to set up TOTP (time-based one-time password). (The response is
 * “ChallengeName”: “MFA_SETUP”).
 * 6. Invokes the AssociateSoftwareToken method to generate a TOTP MFA private
 * key. This can be used with Google Authenticator.
 * 7. Invokes the VerifySoftwareToken method to verify the TOTP and register for
 * MFA.
 * 8. Invokes the AdminInitiateAuth to sign in again. This results in being
 * prompted to submit a TOTP (Response: “ChallengeName”: “SOFTWARE_TOKEN_MFA”).
 * 9. Invokes the AdminRespondToAuthChallenge to get back a token.
 */

public class CognitoMVP {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws NoSuchAlgorithmException,
 InvalidKeyException {
        final String usage = """

                Usage:
                    <clientId> <poolId>

                Where:
                    clientId - The app client Id value that you can get from the
 AWS CDK script.
                    poolId - The pool Id that you can get from the AWS CDK
 script.\s
                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clientId = args[0];
        String poolId = args[1];
        CognitoIdentityProviderClient identityProviderClient =
CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Cognito example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Enter your user name");
        Scanner in = new Scanner(System.in);
        String userName = in.nextLine();

        System.out.println("*** Enter your password");
        String password = in.nextLine();

        System.out.println("*** Enter your email");
        String email = in.nextLine();

        System.out.println("1. Signing up " + userName);
        signUp(identityProviderClient, clientId, userName, password, email);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Getting " + userName + " in the user pool");
        getAdminUser(identityProviderClient, userName, poolId);

        System.out
                .println("*** Conformation code sent to " + userName + ". Would
you like to send a new code? (Yes/No)");
        System.out.println(DASHES);

        System.out.println(DASHES);
        String ans = in.nextLine();

        if (ans.compareTo("Yes") == 0) {
```

```
            resendConfirmationCode(identityProviderClient, clientId, userName);
            System.out.println("3. Sending a new confirmation code");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Enter confirmation code that was emailed");
        String code = in.nextLine();
        confirmSignUp(identityProviderClient, clientId, code, userName);
        System.out.println("Rechecking the status of " + userName + " in the user
pool");
        getAdminUser(identityProviderClient, userName, poolId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Invokes the initiateAuth to sign in");
        AdminInitiateAuthResponse authResponse =
initiateAuth(identityProviderClient, clientId, userName, password,
                poolId);
        String mySession = authResponse.session();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Invokes the AssociateSoftwareToken method to
generate a TOTP key");
        String newSession = getSecretForAppMFA(identityProviderClient,
mySession);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Enter the 6-digit code displayed in Google
Authenticator");
        String myCode = in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Verify the TOTP and register for MFA");
        verifyTOTP(identityProviderClient, newSession, myCode);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Re-enter a 6-digit code displayed in Google
Authenticator");
        String mfaCode = in.nextLine();
```

```
        AdminInitiateAuthResponse authResponse1 =
initiateAuth(identityProviderClient, clientId, userName, password,
                poolId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9.  Invokes the AdminRespondToAuthChallenge");
        String session2 = authResponse1.session();
        adminRespondToAuthChallenge(identityProviderClient, userName, clientId,
mfaCode, session2);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("All Amazon Cognito operations were successfully
performed");
        System.out.println(DASHES);
    }

    // Respond to an authentication challenge.
    public static void adminRespondToAuthChallenge(CognitoIdentityProviderClient
identityProviderClient,
            String userName, String clientId, String mfaCode, String session) {
        System.out.println("SOFTWARE_TOKEN_MFA challenge is generated");
        Map<String, String> challengeResponses = new HashMap<>();

        challengeResponses.put("USERNAME", userName);
        challengeResponses.put("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

        AdminRespondToAuthChallengeRequest respondToAuthChallengeRequest =
AdminRespondToAuthChallengeRequest.builder()
                .challengeName(ChallengeNameType.SOFTWARE_TOKEN_MFA)
                .clientId(clientId)
                .challengeResponses(challengeResponses)
                .session(session)
                .build();

        AdminRespondToAuthChallengeResponse respondToAuthChallengeResult =
identityProviderClient
                .adminRespondToAuthChallenge(respondToAuthChallengeRequest);

System.out.println("respondToAuthChallengeResult.getAuthenticationResult()"
                + respondToAuthChallengeResult.authenticationResult());
    }
```

```
   // Verify the TOTP and register for MFA.
   public static void verifyTOTP(CognitoIdentityProviderClient
identityProviderClient, String session, String code) {
       try {
           VerifySoftwareTokenRequest tokenRequest =
VerifySoftwareTokenRequest.builder()
                   .userCode(code)
                   .session(session)
                   .build();

           VerifySoftwareTokenResponse verifyResponse =
identityProviderClient.verifySoftwareToken(tokenRequest);
           System.out.println("The status of the token is " +
verifyResponse.statusAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static AdminInitiateAuthResponse
initiateAuth(CognitoIdentityProviderClient identityProviderClient,
           String clientId, String userName, String password, String userPoolId)
{
       try {
           Map<String, String> authParameters = new HashMap<>();
           authParameters.put("USERNAME", userName);
           authParameters.put("PASSWORD", password);

           AdminInitiateAuthRequest authRequest =
AdminInitiateAuthRequest.builder()
                   .clientId(clientId)
                   .userPoolId(userPoolId)
                   .authParameters(authParameters)
                   .authFlow(AuthFlowType.ADMIN_USER_PASSWORD_AUTH)
                   .build();

           AdminInitiateAuthResponse response =
identityProviderClient.adminInitiateAuth(authRequest);
           System.out.println("Result Challenge is : " +
response.challengeName());
           return response;
```

```
        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }

    public static String getSecretForAppMFA(CognitoIdentityProviderClient
identityProviderClient, String session) {
        AssociateSoftwareTokenRequest softwareTokenRequest =
AssociateSoftwareTokenRequest.builder()
                .session(session)
                .build();

        AssociateSoftwareTokenResponse tokenResponse = identityProviderClient
                .associateSoftwareToken(softwareTokenRequest);
        String secretCode = tokenResponse.secretCode();
        System.out.println("Enter this token into Google Authenticator");
        System.out.println(secretCode);
        return tokenResponse.session();
    }

    public static void confirmSignUp(CognitoIdentityProviderClient
identityProviderClient, String clientId, String code,
            String userName) {
        try {
            ConfirmSignUpRequest signUpRequest = ConfirmSignUpRequest.builder()
                    .clientId(clientId)
                    .confirmationCode(code)
                    .username(userName)
                    .build();

            identityProviderClient.confirmSignUp(signUpRequest);
            System.out.println(userName + " was confirmed");

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void resendConfirmationCode(CognitoIdentityProviderClient
identityProviderClient, String clientId,
```

```
            String userName) {
        try {
            ResendConfirmationCodeRequest codeRequest =
ResendConfirmationCodeRequest.builder()
                    .clientId(clientId)
                    .username(userName)
                    .build();

            ResendConfirmationCodeResponse response =
identityProviderClient.resendConfirmationCode(codeRequest);
            System.out.println("Method of delivery is " +
response.codeDeliveryDetails().deliveryMediumAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void signUp(CognitoIdentityProviderClient
identityProviderClient, String clientId, String userName,
            String password, String email) {
        AttributeType userAttrs = AttributeType.builder()
                .name("email")
                .value(email)
                .build();

        List<AttributeType> userAttrsList = new ArrayList<>();
        userAttrsList.add(userAttrs);
        try {
            SignUpRequest signUpRequest = SignUpRequest.builder()
                    .userAttributes(userAttrsList)
                    .username(userName)
                    .clientId(clientId)
                    .password(password)
                    .build();

            identityProviderClient.signUp(signUpRequest);
            System.out.println("User has been signed up ");

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void getAdminUser(CognitoIdentityProviderClient
 identityProviderClient, String userName,
            String poolId) {
        try {
            AdminGetUserRequest userRequest = AdminGetUserRequest.builder()
                    .username(userName)
                    .userPoolId(poolId)
                    .build();

            AdminGetUserResponse response =
 identityProviderClient.adminGetUser(userRequest);
            System.out.println("User status " + response.userStatusAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Para obter a melhor experiência, clone o GitHub repositório e execute este exemplo. O código a seguir representa uma amostra da aplicação de exemplo completa.

```
import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { signUp } from "../../../actions/sign-up.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getSecondValuesFromEntries } from "@aws-sdk-examples/libs/utils/util-
csv.js";

const validateClient = (clientId) => {
  if (!clientId) {
    throw new Error(
      `App client id is missing. Did you run 'create-user-pool'?`,
    );
  }
};

const validateUser = (username, password, email) => {
  if (!(username && password && email)) {
    throw new Error(
      `Username, password, and email must be provided as arguments to the 'sign-
up' command.`,
    );
  }
};

const signUpHandler = async (commands) => {
  const [_, username, password, email] = commands;

  try {
    validateUser(username, password, email);
    /**
```

```
     * @type {string[]}
     */
    const values = getSecondValuesFromEntries(FILE_USER_POOLS);
    const clientId = values[0];
    validateClient(clientId);
    log(`Signing up.`);
    await signUp({ clientId, username, password, email });
    log(`Signed up. A confirmation email has been sent to: ${email}.`);
    log(`Run 'confirm-sign-up ${username} <code>' to confirm your account.`);
  } catch (err) {
    log(err);
  }
};

export { signUpHandler };

const signUp = ({ clientId, username, password, email }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new SignUpCommand({
    ClientId: clientId,
    Username: username,
    Password: password,
    UserAttributes: [{ Name: "email", Value: email }],
  });

  return client.send(command);
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { confirmSignUp } from "../../../actions/confirm-sign-up.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getSecondValuesFromEntries } from "@aws-sdk-examples/libs/utils/util-
csv.js";

const validateClient = (clientId) => {
  if (!clientId) {
    throw new Error(
      `App client id is missing. Did you run 'create-user-pool'?`,
    );
  }
};

const validateUser = (username) => {
```

```
  if (!username) {
    throw new Error(
      `Username name is missing. It must be provided as an argument to the
 'confirm-sign-up' command.`,
    );
  }
};

const validateCode = (code) => {
  if (!code) {
    throw new Error(
      `Verification code is missing. It must be provided as an argument to the
 'confirm-sign-up' command.`,
    );
  }
};

const confirmSignUpHandler = async (commands) => {
  const [_, username, code] = commands;

  try {
    validateUser(username);
    validateCode(code);
    /**
     * @type {string[]}
     */
    const values = getSecondValuesFromEntries(FILE_USER_POOLS);
    const clientId = values[0];
    validateClient(clientId);
    log(`Confirming user.`);
    await confirmSignUp({ clientId, username, code });
    log(
      `User confirmed. Run 'admin-initiate-auth ${username} <password>' to sign
 in.`,
    );
  } catch (err) {
    log(err);
  }
};

export { confirmSignUpHandler };

const confirmSignUp = ({ clientId, username, code }) => {
  const client = new CognitoIdentityProviderClient({});
```

```
  const command = new ConfirmSignUpCommand({
    ClientId: clientId,
    Username: username,
    ConfirmationCode: code,
  });

  return client.send(command);
};

import qrcode from "qrcode-terminal";
import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { adminInitiateAuth } from "../../../actions/admin-initiate-auth.js";
import { associateSoftwareToken } from "../../../actions/associate-software-
token.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getFirstEntry } from "@aws-sdk-examples/libs/utils/util-csv.js";

const handleMfaSetup = async (session, username) => {
  const { SecretCode, Session } = await associateSoftwareToken(session);

  // Store the Session for use with 'VerifySoftwareToken'.
  process.env.SESSION = Session;

  console.log(
    "Scan this code in your preferred authenticator app, then run 'verify-
software-token' to finish the setup.",
  );
  qrcode.generate(
    `otpauth://totp/${username}?secret=${SecretCode}`,
    { small: true },
    console.log,
  );
};

const handleSoftwareTokenMfa = (session) => {
  // Store the Session for use with 'AdminRespondToAuthChallenge'.
  process.env.SESSION = session;
};

const validateClient = (id) => {
  if (!id) {
    throw new Error(
      `User pool client id is missing. Did you run 'create-user-pool'?`,
```

```
    );
  }
};

const validateId = (id) => {
  if (!id) {
    throw new Error(`User pool id is missing. Did you run 'create-user-pool'?`);
  }
};

const validateUser = (username, password) => {
  if (!(username && password)) {
    throw new Error(
      `Username and password must be provided as arguments to the 'admin-
initiate-auth' command.`,
    );
  }
};

const adminInitiateAuthHandler = async (commands) => {
  const [_, username, password] = commands;

  try {
    validateUser(username, password);

    const [userPoolId, clientId] = getFirstEntry(FILE_USER_POOLS);
    validateId(userPoolId);
    validateClient(clientId);

    log("Signing in.");
    const { ChallengeName, Session } = await adminInitiateAuth({
      clientId,
      userPoolId,
      username,
      password,
    });

    if (ChallengeName === "MFA_SETUP") {
      log("MFA setup is required.");
      return handleMfaSetup(Session, username);
    }

    if (ChallengeName === "SOFTWARE_TOKEN_MFA") {
      handleSoftwareTokenMfa(Session);
```

```
      log(`Run 'admin-respond-to-auth-challenge ${username} <totp>'`);
    }
  } catch (err) {
    log(err);
  }
};

export { adminInitiateAuthHandler };

const adminInitiateAuth = ({ clientId, userPoolId, username, password }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new AdminInitiateAuthCommand({
    ClientId: clientId,
    UserPoolId: userPoolId,
    AuthFlow: AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
    AuthParameters: { USERNAME: username, PASSWORD: password },
  });

  return client.send(command);
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { adminRespondToAuthChallenge } from "../../../actions/admin-respond-to-
auth-challenge.js";
import { getFirstEntry } from "@aws-sdk-examples/libs/utils/util-csv.js";
import { FILE_USER_POOLS } from "./constants.js";

const verifyUsername = (username) => {
  if (!username) {
    throw new Error(
      `Username is missing. It must be provided as an argument to the 'admin-
respond-to-auth-challenge' command.`,
    );
  }
};

const verifyTotp = (totp) => {
  if (!totp) {
    throw new Error(
      `Time-based one-time password (TOTP) is missing. It must be provided as an
 argument to the 'admin-respond-to-auth-challenge' command.`,
    );
  }
```

```
};

const storeAccessToken = (token) => {
  process.env.AccessToken = token;
};

const adminRespondToAuthChallengeHandler = async (commands) => {
  const [_, username, totp] = commands;

  try {
    verifyUsername(username);
    verifyTotp(totp);

    const [userPoolId, clientId] = getFirstEntry(FILE_USER_POOLS);
    const session = process.env.SESSION;

    const { AuthenticationResult } = await adminRespondToAuthChallenge({
      clientId,
      userPoolId,
      username,
      totp,
      session,
    });

    storeAccessToken(AuthenticationResult.AccessToken);

    log("Successfully authenticated.");
  } catch (err) {
    log(err);
  }
};

export { adminRespondToAuthChallengeHandler };

const respondToAuthChallenge = ({
  clientId,
  username,
  session,
  userPoolId,
  code,
}) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new RespondToAuthChallengeCommand({
```

```
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: code,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { verifySoftwareToken } from "../../../actions/verify-software-token.js";

const validateTotp = (totp) => {
  if (!totp) {
    throw new Error(
      `Time-based one-time password (TOTP) must be provided to the 'validate-
software-token' command.`,
    );
  }
};
const verifySoftwareTokenHandler = async (commands) => {
  const [_, totp] = commands;

  try {
    validateTotp(totp);

    log("Verifying TOTP.");
    await verifySoftwareToken(totp);
    log("TOTP Verified. Run 'admin-initiate-auth' again to sign-in.");
  } catch (err) {
    console.log(err);
  }
};

export { verifySoftwareTokenHandler };

const verifySoftwareToken = (totp) => {
  const client = new CognitoIdentityProviderClient({});

  // The 'Session' is provided in the response to 'AssociateSoftwareToken'.
```

```
  const session = process.env.SESSION;

  if (!session) {
    throw new Error(
      "Missing a valid Session. Did you run 'admin-initiate-auth'?",
    );
  }

  const command = new VerifySoftwareTokenCommand({
    Session: session,
    UserCode: totp,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 TIP: To set up the required user pool, run the AWS Cloud Development
 Kit (AWS CDK) script provided in this GitHub repo at resources/cdk/
cognito_scenario_user_pool_with_mfa.

 This code example performs the following operations:

 1. Invokes the signUp method to sign up a user.
 2. Invokes the adminGetUser method to get the user's confirmation status.
 3. Invokes the ResendConfirmationCode method if the user requested another code.
 4. Invokes the confirmSignUp method.
 5. Invokes the initiateAuth to sign in. This results in being prompted to
 set up TOTP (time-based one-time password). (The response is “ChallengeName”:
 “MFA_SETUP”).
 6. Invokes the AssociateSoftwareToken method to generate a TOTP MFA private key.
 This can be used with Google Authenticator.
 7. Invokes the VerifySoftwareToken method to verify the TOTP and register for
 MFA.
 8. Invokes the AdminInitiateAuth to sign in again. This results in being
 prompted to submit a TOTP (Response: “ChallengeName”: “SOFTWARE_TOKEN_MFA”).
 9. Invokes the AdminRespondToAuthChallenge to get back a token.
 */

suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
```

```
            <clientId> <poolId>
        Where:
            clientId - The app client Id value that you can get from the AWS CDK
script.
            poolId - The pool Id that you can get from the AWS CDK script.
    """

    if (args.size != 2) {
        println(usage)
        exitProcess(1)
    }

    val clientId = args[0]
    val poolId = args[1]

    // Use the console to get data from the user.
    println("*** Enter your use name")
    val inOb = Scanner(System.`in`)
    val userName = inOb.nextLine()
    println(userName)

    println("*** Enter your password")
    val password: String = inOb.nextLine()

    println("*** Enter your email")
    val email = inOb.nextLine()

    println("*** Signing up $userName")
    signUp(clientId, userName, password, email)

    println("*** Getting $userName in the user pool")
    getAdminUser(userName, poolId)

    println("*** Conformation code sent to $userName. Would you like to send a
new code? (Yes/No)")
    val ans = inOb.nextLine()

    if (ans.compareTo("Yes") == 0) {
        println("*** Sending a new confirmation code")
        resendConfirmationCode(clientId, userName)
    }
    println("*** Enter the confirmation code that was emailed")
    val code = inOb.nextLine()
    confirmSignUp(clientId, code, userName)
```

```
    println("*** Rechecking the status of $userName in the user pool")
    getAdminUser(userName, poolId)

    val authResponse = checkAuthMethod(clientId, userName, password, poolId)
    val mySession = authResponse.session
    val newSession = getSecretForAppMFA(mySession)
    println("*** Enter the 6-digit code displayed in Google Authenticator")
    val myCode = inOb.nextLine()

    // Verify the TOTP and register for MFA.
    verifyTOTP(newSession, myCode)
    println("*** Re-enter a 6-digit code displayed in Google Authenticator")
    val mfaCode: String = inOb.nextLine()
    val authResponse1 = checkAuthMethod(clientId, userName, password, poolId)
    val session2 = authResponse1.session
    adminRespondToAuthChallenge(userName, clientId, mfaCode, session2)
}

suspend fun checkAuthMethod(clientIdVal: String, userNameVal: String,
 passwordVal: String, userPoolIdVal: String): AdminInitiateAuthResponse {
    val authParas = mutableMapOf<String, String>()
    authParas["USERNAME"] = userNameVal
    authParas["PASSWORD"] = passwordVal

    val authRequest = AdminInitiateAuthRequest {
        clientId = clientIdVal
        userPoolId = userPoolIdVal
        authParameters = authParas
        authFlow = AuthFlowType.AdminUserPasswordAuth
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminInitiateAuth(authRequest)
        println("Result Challenge is ${response.challengeName}")
        return response
    }
}

suspend fun resendConfirmationCode(clientIdVal: String?, userNameVal: String?) {
    val codeRequest = ResendConfirmationCodeRequest {
        clientId = clientIdVal
        username = userNameVal
```

```
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.resendConfirmationCode(codeRequest)
        println("Method of delivery is " +
 (response.codeDeliveryDetails?.deliveryMedium))
    }
}

// Respond to an authentication challenge.
suspend fun adminRespondToAuthChallenge(userName: String, clientIdVal: String?,
 mfaCode: String, sessionVal: String?) {
    println("SOFTWARE_TOKEN_MFA challenge is generated")
    val challengeResponsesOb = mutableMapOf<String, String>()
    challengeResponsesOb["USERNAME"] = userName
    challengeResponsesOb["SOFTWARE_TOKEN_MFA_CODE"] = mfaCode

    val adminRespondToAuthChallengeRequest = AdminRespondToAuthChallengeRequest {
        challengeName = ChallengeNameType.SoftwareTokenMfa
        clientId = clientIdVal
        challengeResponses = challengeResponsesOb
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val respondToAuthChallengeResult =
 identityProviderClient.adminRespondToAuthChallenge(adminRespondToAuthChallengeRequest)
        println("respondToAuthChallengeResult.getAuthenticationResult()
 ${respondToAuthChallengeResult.authenticationResult}")
    }
}

// Verify the TOTP and register for MFA.
suspend fun verifyTOTP(sessionVal: String?, codeVal: String?) {
    val tokenRequest = VerifySoftwareTokenRequest {
        userCode = codeVal
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
```

```
        val verifyResponse =
 identityProviderClient.verifySoftwareToken(tokenRequest)
        println("The status of the token is ${verifyResponse.status}")
    }
}

suspend fun getSecretForAppMFA(sessionVal: String?): String? {
    val softwareTokenRequest = AssociateSoftwareTokenRequest {
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val tokenResponse =
 identityProviderClient.associateSoftwareToken(softwareTokenRequest)
        val secretCode = tokenResponse.secretCode
        println("Enter this token into Google Authenticator")
        println(secretCode)
        return tokenResponse.session
    }
}

suspend fun confirmSignUp(clientIdVal: String?, codeVal: String?, userNameVal:
 String?) {
    val signUpRequest = ConfirmSignUpRequest {
        clientId = clientIdVal
        confirmationCode = codeVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.confirmSignUp(signUpRequest)
        println("$userNameVal  was confirmed")
    }
}

suspend fun getAdminUser(userNameVal: String?, poolIdVal: String?) {
    val userRequest = AdminGetUserRequest {
        username = userNameVal
        userPoolId = poolIdVal
    }
```

```
    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminGetUser(userRequest)
        println("User status ${response.userStatus}")
    }
}

suspend fun signUp(clientIdVal: String?, userNameVal: String?, passwordVal:
 String?, emailVal: String?) {
    val userAttrs = AttributeType {
        name = "email"
        value = emailVal
    }

    val userAttrsList = mutableListOf<AttributeType>()
    userAttrsList.add(userAttrs)
    val signUpRequest = SignUpRequest {
        userAttributes = userAttrsList
        username = userNameVal
        clientId = clientIdVal
        password = passwordVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.signUp(signUpRequest)
        println("User has been signed up")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth

- ListUsers
- ResendConfirmationCode
- RespondToAuthChallenge
- SignUp
- VerifySoftwareToken

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do Amazon Cognito usadas no cenário.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider
 client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def _secret_hash(self, user_name):
        """
        Calculates a secret hash from a user name and a client secret.
```

```
        :param user_name: The user name to use when calculating the hash.
        :return: The secret hash.
        """
        key = self.client_secret.encode()
        msg = bytes(user_name + self.client_id, "utf-8")
        secret_hash = base64.b64encode(
            hmac.new(key, msg, digestmod=hashlib.sha256).digest()
        ).decode()
        logger.info("Made secret hash for %s: %s.", user_name, secret_hash)
        return secret_hash

    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon
Cognito
        to send an email to the specified email address. The email contains a
code that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
whether
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
        :param password: The password for the new user.
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
```

```
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name,
response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return confirmed


    def resend_confirmation(self, user_name):
        """
        Prompts Amazon Cognito to resend an email with a new confirmation code.

        :param user_name: The name of the user who will receive the email.
        :return: Delivery information about where the email is sent.
        """
        try:
            kwargs = {"ClientId": self.client_id, "Username": user_name}
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.resend_confirmation_code(**kwargs)
            delivery = response["CodeDeliveryDetails"]
        except ClientError as err:
            logger.error(
                "Couldn't resend confirmation to %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return delivery


    def confirm_user_sign_up(self, user_name, confirmation_code):
```

```
        """
        Confirms a previously created user. A user must be confirmed before they
        can sign in to Amazon Cognito.

        :param user_name: The name of the user to confirm.
        :param confirmation_code: The confirmation code sent to the user's
registered
                                  email address.
        :return: True when the confirmation succeeds.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "ConfirmationCode": confirmation_code,
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            self.cognito_idp_client.confirm_sign_up(**kwargs)
        except ClientError as err:
            logger.error(
                "Couldn't confirm sign up for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return True


    def list_users(self):
        """
        Returns a list of the users in the current user pool.

        :return: The list of users.
        """
        try:
            response =
self.cognito_idp_client.list_users(UserPoolId=self.user_pool_id)
            users = response["Users"]
        except ClientError as err:
            logger.error(
                "Couldn't list users for %s. Here's why: %s: %s",
```

```
                self.user_pool_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return users


    def start_sign_in(self, user_name, password):
        """
        Starts the sign-in process for a user by using administrator credentials.
        This method of signing in is appropriate for code running on a secure
 server.

        If the user pool is configured to require MFA and this is the first sign-
in
        for the user, Amazon Cognito returns a challenge response to set up an
        MFA application. When this occurs, this function gets an MFA secret from
        Amazon Cognito and returns it to the caller.

        :param user_name: The name of the user to sign in.
        :param password: The user's password.
        :return: The result of the sign-in attempt. When sign-in is successful,
 this
                 returns an access token that can be used to get AWS credentials.
 Otherwise,
                 Amazon Cognito returns a challenge to set up an MFA application,
                 or a challenge to enter an MFA code from a registered MFA
 application.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "AuthFlow": "ADMIN_USER_PASSWORD_AUTH",
                "AuthParameters": {"USERNAME": user_name, "PASSWORD": password},
            }
            if self.client_secret is not None:
                kwargs["AuthParameters"]["SECRET_HASH"] =
 self._secret_hash(user_name)
            response = self.cognito_idp_client.admin_initiate_auth(**kwargs)
            challenge_name = response.get("ChallengeName", None)
            if challenge_name == "MFA_SETUP":
```

```
                if (
                    "SOFTWARE_TOKEN_MFA"
                    in response["ChallengeParameters"]["MFAS_CAN_SETUP"]
                ):
                    response.update(self.get_mfa_secret(response["Session"]))
                else:
                    raise RuntimeError(
                        "The user pool requires MFA setup, but the user pool is
not "
                        "configured for TOTP MFA. This example requires TOTP
MFA."
                    )
        except ClientError as err:
            logger.error(
                "Couldn't start sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response


    def get_mfa_secret(self, session):
        """
        Gets a token that can be used to associate an MFA application with the
user.

        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :return: An MFA token that can be used to set up an MFA application.
        """
        try:
            response =
self.cognito_idp_client.associate_software_token(Session=session)
        except ClientError as err:
            logger.error(
                "Couldn't get MFA secret. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response


    def verify_mfa(self, session, user_code):
        """
        Verify a new MFA application that is associated with a user.

        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :param user_code: A code generated by the associated MFA application.
        :return: Status that indicates whether the MFA application is verified.
        """
        try:
            response = self.cognito_idp_client.verify_software_token(
                Session=session, UserCode=user_code
            )
        except ClientError as err:
            logger.error(
                "Couldn't verify MFA. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response


    def respond_to_mfa_challenge(self, user_name, session, mfa_code):
        """
        Responds to a challenge for an MFA code. This completes the second step
of
        a two-factor sign-in. When sign-in is successful, it returns an access
token
        that can be used to get AWS credentials from Amazon Cognito.

        :param user_name: The name of the user who is signing in.
        :param session: Session information returned from a previous call to
initiate
                        authentication.
```

```
        :param mfa_code: A code generated by the associated MFA application.
        :return: The result of the authentication. When successful, this contains
an
                 access token for the user.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "ChallengeName": "SOFTWARE_TOKEN_MFA",
                "Session": session,
                "ChallengeResponses": {
                    "USERNAME": user_name,
                    "SOFTWARE_TOKEN_MFA_CODE": mfa_code,
                },
            }
            if self.client_secret is not None:
                kwargs["ChallengeResponses"]["SECRET_HASH"] = self._secret_hash(
                    user_name
                )
            response =
self.cognito_idp_client.admin_respond_to_auth_challenge(**kwargs)
            auth_result = response["AuthenticationResult"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "ExpiredCodeException":
                logger.warning(
                    "Your MFA code has expired or has been used already. You
might have "
                    "to wait a few seconds until your app shows you a new code."
                )
            else:
                logger.error(
                    "Couldn't respond to mfa challenge for %s. Here's why: %s:
%s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return auth_result


    def confirm_mfa_device(
```

```
        self,
        user_name,
        device_key,
        device_group_key,
        device_password,
        access_token,
        aws_srp,
    ):
        """
        Confirms an MFA device to be tracked by Amazon Cognito. When a device is
        tracked, its key and password can be used to sign in without requiring a
new
        MFA code from the MFA application.

        :param user_name: The user that is associated with the device.
        :param device_key: The key of the device, returned by Amazon Cognito.
        :param device_group_key: The group key of the device, returned by Amazon
Cognito.
        :param device_password: The password that is associated with the device.
        :param access_token: The user's access token.
        :param aws_srp: A class that helps with Secure Remote Password (SRP)
                        calculations. The scenario associated with this example
uses
                        the warrant package.
        :return: True when the user must confirm the device. Otherwise, False.
When
                 False, the device is automatically confirmed and tracked.
        """
        srp_helper = aws_srp.AWSSRP(
            username=user_name,
            password=device_password,
            pool_id="_",
            client_id=self.client_id,
            client_secret=None,
            client=self.cognito_idp_client,
        )
        device_and_pw = f"{device_group_key}{device_key}:{device_password}"
        device_and_pw_hash = aws_srp.hash_sha256(device_and_pw.encode("utf-8"))
        salt = aws_srp.pad_hex(aws_srp.get_random(16))
        x_value = aws_srp.hex_to_long(aws_srp.hex_hash(salt +
device_and_pw_hash))
        verifier = aws_srp.pad_hex(pow(srp_helper.val_g, x_value,
srp_helper.big_n))
        device_secret_verifier_config = {
```

```
            "PasswordVerifier": base64.standard_b64encode(
                bytearray.fromhex(verifier)
            ).decode("utf-8"),
            "Salt":
base64.standard_b64encode(bytearray.fromhex(salt)).decode("utf-8"),
        }
        try:
            response = self.cognito_idp_client.confirm_device(
                AccessToken=access_token,
                DeviceKey=device_key,
                DeviceSecretVerifierConfig=device_secret_verifier_config,
            )
            user_confirm = response["UserConfirmationNecessary"]
        except ClientError as err:
            logger.error(
                "Couldn't confirm mfa device %s. Here's why: %s: %s",
                device_key,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return user_confirm


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
        """
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
        with a tracked device lets a user sign in without entering a new MFA
code.

        Signing in with a tracked device requires that the client respond to the
SRP
        protocol. The scenario associated with this example uses the warrant
package
        to help with SRP calculations.
```

```
        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains
 an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
 {response_init['ChallengeName']}."
                )

            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
```

```
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
 user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier =
 self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

Crie uma classe que execute o cenário. Este exemplo também registra um dispositivo de MFA a ser rastreado pelo Amazon Cognito e mostra como fazer login com uma senha e informações do dispositivo rastreado. Isso evita a necessidade de inserir um novo código de MFA.

```
def run_scenario(cognito_idp_client, user_pool_id, client_id):
```

```
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon Cognito user signup with MFA demo.")
    print("-" * 88)

    cog_wrapper = CognitoIdentityProviderWrapper(
        cognito_idp_client, user_pool_id, client_id
    )

    user_name = q.ask("Let's sign up a new user. Enter a user name: ",
q.non_empty)
    password = q.ask("Enter a password for the user: ", q.non_empty)
    email = q.ask("Enter a valid email address that you own: ", q.non_empty)
    confirmed = cog_wrapper.sign_up_user(user_name, password, email)
    while not confirmed:
        print(
            f"User {user_name} requires confirmation. Check {email} for "
            f"a verification code."
        )
        confirmation_code = q.ask("Enter the confirmation code from the email: ")
        if not confirmation_code:
            if q.ask("Do you need another confirmation code (y/n)? ",
q.is_yesno):
                delivery = cog_wrapper.resend_confirmation(user_name)
                print(
                    f"Confirmation code sent by {delivery['DeliveryMedium']} "
                    f"to {delivery['Destination']}."
                )
        else:
            confirmed = cog_wrapper.confirm_user_sign_up(user_name,
confirmation_code)
    print(f"User {user_name} is confirmed and ready to use.")
    print("-" * 88)

    print("Let's get a list of users in the user pool.")
    q.ask("Press Enter when you're ready.")
    users = cog_wrapper.list_users()
    if users:
        print(f"Found {len(users)} users:")
        pp(users)
    else:
        print("No users found.")
    print("-" * 88)
```

```
    print("Let's sign in and get an access token.")
    auth_tokens = None
    challenge = "ADMIN_USER_PASSWORD_AUTH"
    response = {}
    while challenge is not None:
        if challenge == "ADMIN_USER_PASSWORD_AUTH":
            response = cog_wrapper.start_sign_in(user_name, password)
            challenge = response["ChallengeName"]
        elif response["ChallengeName"] == "MFA_SETUP":
            print("First, we need to set up an MFA application.")
            qr_img = qrcode.make(
                f"otpauth://totp/{user_name}?secret={response['SecretCode']}"
            )
            qr_img.save("qr.png")
            q.ask(
                "Press Enter to see a QR code on your screen. Scan it into an MFA
"
                "application, such as Google Authenticator."
            )
            webbrowser.open("qr.png")
            mfa_code = q.ask(
                "Enter the verification code from your MFA application: ",
q.non_empty
            )
            response = cog_wrapper.verify_mfa(response["Session"], mfa_code)
            print(f"MFA device setup {response['Status']}")
            print("Now that an MFA application is set up, let's sign in again.")
            print(
                "You might have to wait a few seconds for a new MFA code to
appear in "
                "your MFA application."
            )
            challenge = "ADMIN_USER_PASSWORD_AUTH"
        elif response["ChallengeName"] == "SOFTWARE_TOKEN_MFA":
            auth_tokens = None
            while auth_tokens is None:
                mfa_code = q.ask(
                    "Enter a verification code from your MFA application: ",
q.non_empty
                )
                auth_tokens = cog_wrapper.respond_to_mfa_challenge(
                    user_name, response["Session"], mfa_code
                )
```

```
            print(f"You're signed in as {user_name}.")
            print("Here's your access token:")
            pp(auth_tokens["AccessToken"])
            print("And your device information:")
            pp(auth_tokens["NewDeviceMetadata"])
            challenge = None
        else:
            raise Exception(f"Got unexpected challenge
 {response['ChallengeName']}")
    print("-" * 88)

    device_group_key = auth_tokens["NewDeviceMetadata"]["DeviceGroupKey"]
    device_key = auth_tokens["NewDeviceMetadata"]["DeviceKey"]
    device_password = base64.standard_b64encode(os.urandom(40)).decode("utf-8")

    print("Let's confirm your MFA device so you don't have re-enter MFA tokens
 for it.")
    q.ask("Press Enter when you're ready.")
    cog_wrapper.confirm_mfa_device(
        user_name,
        device_key,
        device_group_key,
        device_password,
        auth_tokens["AccessToken"],
        aws_srp,
    )
    print(f"Your device {device_key} is confirmed.")
    print("-" * 88)

    print(
        f"Now let's sign in as {user_name} from your confirmed device
 {device_key}.\n"
        f"Because this device is tracked by Amazon Cognito, you won't have to re-
enter an MFA code."
    )
    q.ask("Press Enter when ready.")
    auth_tokens = cog_wrapper.sign_in_with_tracked_device(
        user_name, password, device_key, device_group_key, device_password,
 aws_srp
    )
    print("You're signed in. Your access token is:")
    pp(auth_tokens["AccessToken"])
    print("-" * 88)
```

```
    print("Don't forget to delete your user pool when you're done with this
 example.")
    print("\nThanks for watching!")
    print("-" * 88)


def main():
    parser = argparse.ArgumentParser(
        description="Shows how to sign up a new user with Amazon Cognito and
 associate "
        "the user with an MFA application for multi-factor authentication."
    )
    parser.add_argument(
        "user_pool_id", help="The ID of the user pool to use for the example."
    )
    parser.add_argument(
        "client_id", help="The ID of the client application to use for the
 example."
    )
    args = parser.parse_args()
    try:
        run_scenario(boto3.client("cognito-idp"), args.user_pool_id,
 args.client_id)
    except Exception:
        logging.exception("Something went wrong with the demo.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth

- ListUsers
- ResendConfirmationCode
- RespondToAuthChallenge
- SignUp
- VerifySoftwareToken

Exemplos de código do Amazon Cognito Sync usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Sync com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon Cognito Sync – Mais informações sobre o Amazon Cognito Sync.
- Referência da API Amazon Cognito Sync – Detalhes sobre todas as ações disponíveis do Amazon Cognito Sync.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Cognito Sync usando AWS SDKs
  - Ter uma lista de grupos de identidades registrados no Amazon Cognito usando um AWS SDK

Ações do Amazon Cognito Sync usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Cognito Sync com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Ter uma lista de grupos de identidades registrados no Amazon Cognito usando um AWS SDK

Ter uma lista de grupos de identidades registrados no Amazon Cognito usando um AWS SDK

O exemplo de código a seguir mostra como ter uma lista de identidades do Amazon Cognito.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_pools(client: &Client) -> Result<(), Error> {
    let response = client
        .list_identity_pool_usage()
        .max_results(10)
        .send()
        .await?;

    let pools = response.identity_pool_usages();
    println!("Identity pools:");

    for pool in pools {
        println!(
            "  Identity pool ID:    {}",
            pool.identity_pool_id().unwrap_or_default()
        );
        println!(
            "  Data storage:        {}",
            pool.data_storage().unwrap_or_default()
        );
        println!(
            "  Sync sessions count: {}",
            pool.sync_sessions_count().unwrap_or_default()
        );
```

```
        println!(
            "  Last modified:       {}",
            pool.last_modified_date().unwrap().to_chrono_utc()?
        );
        println!();
    }

    println!("Next token: {}", response.next_token().unwrap_or_default());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListIdentityPoolUsagereferência da API AWS SDK for Rust.

Exemplos de código do Amazon Comprehend usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Comprehend com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Comprehend – Mais informações sobre o Amazon Comprehend.
- Referência da API do Amazon Comprehend – Detalhes sobre todas as ações disponíveis do Amazon Comprehend.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.

- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Comprehend usando SDKs da AWS
  - Crie um classificador de documentos do Amazon Comprehend usando um SDK da AWS
  - Excluir um classificador de documentos do Amazon Comprehend usando um SDK da AWS
  - Descreva uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS
  - Descreva um classificador de documentos do Amazon Comprehend usando um SDK da AWS
  - Descreva uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS
  - Detecte entidades em um documento com o Amazon Comprehend usando um SDK da AWS
  - Detecte frases-chave em um documento com o Amazon Comprehend usando um SDK da AWS
  - Detecte informações de identificação pessoal em um documento com o Amazon Comprehend usando um SDK da AWS
  - Detecte elementos sintáticos de um documento com o Amazon Comprehend usando um SDK da AWS
  - Detecte a linguagem dominante em um documento com o Amazon Comprehend usando um SDK da AWS
  - Detecte o sentimento de um documento com o Amazon Comprehend usando um SDK da AWS
  - Liste tarefas de classificação de documentos do Amazon Comprehend usando um SDK da AWS
  - Liste os classificadores de documentos do Amazon Comprehend usando um SDK da AWS
  - Liste tarefas de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS
  - Inicie uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS
  - Inicie uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS
- Cenários do Amazon Comprehend usando SDKs da AWS
  - Detecte elementos do documento com o Amazon Comprehend e um SDK da AWS
  - Execute uma tarefa de modelagem de tópicos do Amazon Comprehend em dados de amostra usando um SDK da AWS

- Treine um classificador Amazon Comprehend personalizado e classifique documentos usando um SDK da AWS
- Exemplos entre serviços do Amazon Comprehend usando SDKs da AWS
  - Criar uma aplicação de transmissão do Amazon Transcribe
  - Crie um chatbot do Amazon Lex para engajar os visitantes do seu site
  - Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
  - Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
  - Detectar entidades em texto extraído de uma imagem usando um AWS SDK

Ações do Amazon Comprehend usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Comprehend com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon Comprehend usando SDKs da AWS.

Exemplos

- Crie um classificador de documentos do Amazon Comprehend usando um SDK da AWS
- Excluir um classificador de documentos do Amazon Comprehend usando um SDK da AWS
- Descreva uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS
- Descreva um classificador de documentos do Amazon Comprehend usando um SDK da AWS
- Descreva uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS
- Detecte entidades em um documento com o Amazon Comprehend usando um SDK da AWS
- Detecte frases-chave em um documento com o Amazon Comprehend usando um SDK da AWS
- Detecte informações de identificação pessoal em um documento com o Amazon Comprehend usando um SDK da AWS
- Detecte elementos sintáticos de um documento com o Amazon Comprehend usando um SDK da AWS
- Detecte a linguagem dominante em um documento com o Amazon Comprehend usando um SDK da AWS

- Detecte o sentimento de um documento com o Amazon Comprehend usando um SDK da AWS
- Liste tarefas de classificação de documentos do Amazon Comprehend usando um SDK da AWS
- Liste os classificadores de documentos do Amazon Comprehend usando um SDK da AWS
- Liste tarefas de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS
- Inicie uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS
- Inicie uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS

Crie um classificador de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um classificador de documentos do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para criar um classificador de documentos para categorizar documentos

O exemplo de `create-document-classifier` a seguir inicia o processo de treinamento para um modelo de classificador de documentos. O arquivo de dados de treinamento, `training.csv`, está localizado na tag `--input-data-config`. `training.csv` é um documento de duas colunas em que os rótulos ou classificações são fornecidos na primeira coluna e os documentos são fornecidos na segunda coluna.

```
aws comprehend create-document-classifier \
    --document-classifier-name example-classifier \
    --data-access-arn arn:aws:comprehend:us-west-2:111122223333:pii-entities-
detection-job/123456abcdeb0e11022f22a11EXAMPLE \
    --input-data-config "S3Uri=s3://DOC-EXAMPLE-BUCKET/" \
    --language-code en
```

Saída:

```
{
    "DocumentClassifierArn": "arn:aws:comprehend:us-west-2:111122223333:document-
classifier/example-classifier"
}
```

Para obter mais informações, consulte Classificação personalizada no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte CreateDocumentClassifierem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import
 software.amazon.awssdk.services.comprehend.model.CreateDocumentClassifierRequest;
import
 software.amazon.awssdk.services.comprehend.model.CreateDocumentClassifierResponse;
import
 software.amazon.awssdk.services.comprehend.model.DocumentClassifierInputDataConfig;

/**
 * Before running this code example, you can setup the necessary resources, such
 * as the CSV file and IAM Roles, by following this document:
 * https://aws.amazon.com/blogs/machine-learning/building-a-custom-classifier-
using-amazon-comprehend/
 *
 * Also, set up your development environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DocumentClassifierDemo {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <dataAccessRoleArn> <s3Uri> <documentClassifierName>

                Where:
                  dataAccessRoleArn - The ARN value of the role used for this
 operation.
                  s3Uri - The Amazon S3 bucket that contains the CSV file.
                  documentClassifierName - The name of the document classifier.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String dataAccessRoleArn = args[0];
        String s3Uri = args[1];
        String documentClassifierName = args[2];

        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        createDocumentClassifier(comClient, dataAccessRoleArn, s3Uri,
 documentClassifierName);
        comClient.close();
    }

    public static void createDocumentClassifier(ComprehendClient comClient,
 String dataAccessRoleArn, String s3Uri,
            String documentClassifierName) {
        try {
            DocumentClassifierInputDataConfig config =
 DocumentClassifierInputDataConfig.builder()
                    .s3Uri(s3Uri)
```

```
                    .build();

            CreateDocumentClassifierRequest createDocumentClassifierRequest =
 CreateDocumentClassifierRequest.builder()
                    .documentClassifierName(documentClassifierName)
                    .dataAccessRoleArn(dataAccessRoleArn)
                    .languageCode("en")
                    .inputDataConfig(config)
                    .build();

            CreateDocumentClassifierResponse createDocumentClassifierResult =
 comClient
                    .createDocumentClassifier(createDocumentClassifierRequest);
            String documentClassifierArn =
 createDocumentClassifierResult.documentClassifierArn();
            System.out.println("Document Classifier ARN: " +
 documentClassifierArn);

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateDocumentClassifiera Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""
```

```
    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def create(
        self,
        name,
        language_code,
        training_bucket,
        training_key,
        data_access_role_arn,
        mode,
    ):
        """
        Creates a custom classifier. After the classifier is created, it
immediately
        starts training on the data found in the specified Amazon S3 bucket.
Training
        can take 30 minutes or longer. The `describe_document_classifier`
function
        can be used to get training status and returns a status of TRAINED when
the
        classifier is ready to use.

        :param name: The name of the classifier.
        :param language_code: The language the classifier can operate on.
        :param training_bucket: The Amazon S3 bucket that contains the training
data.
        :param training_key: The prefix used to find training data in the
training
                             bucket. If multiple objects have the same prefix,
all
                             of them are used.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
that
                                     grants Comprehend permission to read from
the
                                     training bucket.
        :return: The ARN of the newly created classifier.
```

```
        """
        try:
            response = self.comprehend_client.create_document_classifier(
                DocumentClassifierName=name,
                LanguageCode=language_code,
                InputDataConfig={"S3Uri": f"s3://{training_bucket}/
{training_key}"},
                DataAccessRoleArn=data_access_role_arn,
                Mode=mode.value,
            )
            self.classifier_arn = response["DocumentClassifierArn"]
            logger.info("Started classifier creation. Arn is: %s.",
 self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't create classifier %s.", name)
            raise
        else:
            return self.classifier_arn
```

- Para obter detalhes da API, consulte a CreateDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Excluir um classificador de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um classificador de documentos do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para excluir um classificador de documentos personalizado

O exemplo de `delete-document-classifier` a seguir exclui um modelo de classificador de documentos personalizado.

```
aws comprehend delete-document-classifier \
    --document-classifier-arn arn:aws:comprehend:us-west-2:111122223333:document-classifier/example-classifer-1
```

Este comando não produz saída.

Para obter mais informações, consulte Gerenciar endpoints do Amazon Comprehend no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DeleteDocumentClassifierem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def delete(self):
        """
        Deletes the classifier.
        """
        try:
```

```
            self.comprehend_client.delete_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            logger.info("Deleted classifier %s.", self.classifier_arn)
            self.classifier_arn = None
        except ClientError:
            logger.exception("Couldn't deleted classifier %s.",
self.classifier_arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Descreva uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma trabalho de classificação de documentos do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para descrever um trabalho de classificação de documentos

O exemplo de `describe-document-classification-job` a seguir obtém as propriedades de um trabalho assíncrono de classificação de documentos.

```
aws comprehend describe-document-classification-job \
    --job-id 123456abcdeb0e11022f22a11EXAMPLE
```

Saída:

```
{
```

```
    "DocumentClassificationJobProperties": {
        "JobId": "123456abcdeb0e11022f22a11EXAMPLE",
        "JobArn": "arn:aws:comprehend:us-west-2:111122223333:document-
classification-job/123456abcdeb0e11022f22a11EXAMPLE",
        "JobName": "exampleclassificationjob",
        "JobStatus": "COMPLETED",
        "SubmitTime": "2023-06-14T17:09:51.788000+00:00",
        "EndTime": "2023-06-14T17:15:58.582000+00:00",
        "DocumentClassifierArn": "arn:aws:comprehend:us-
west-2:111122223333:document-classifier/mymodel/version/1",
        "InputDataConfig": {
            "S3Uri": "s3://DOC-EXAMPLE-BUCKET/jobdata/",
            "InputFormat": "ONE_DOC_PER_LINE"
        },
        "OutputDataConfig": {
            "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
testfolder/111122223333-CLN-123456abcdeb0e11022f22a11EXAMPLE/output/
output.tar.gz"
        },
        "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-servicerole"
    }
}
```

Para obter mais informações, consulte Classificação personalizada no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DescribeDocumentClassificationJobem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""
```

```
    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def describe_job(self, job_id):
        """
        Gets metadata about a classification job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response =
self.comprehend_client.describe_document_classification_job(
                JobId=job_id
            )
            job = response["DocumentClassificationJobProperties"]
            logger.info("Got classification job %s.", job["JobName"])
        except ClientError:
            logger.exception("Couldn't get classification job %s.", job_id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a DescribeDocumentClassificationJobReferência da API AWSSDK for Python (Boto3).

Descreva um classificador de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um classificador de documento do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para descrever um classificador de documentos

O exemplo de `describe-document-classifier` a seguir obtém as propriedades de um modelo de classificador de documentos personalizado.

```
aws comprehend describe-document-classifier \
    --document-classifier-arn arn:aws:comprehend:us-west-2:111122223333:document-classifier/example-classifier-1
```

Saída:

```
{
    "DocumentClassifierProperties": {
        "DocumentClassifierArn": "arn:aws:comprehend:us-west-2:111122223333:document-classifier/example-classifier-1",
        "LanguageCode": "en",
        "Status": "TRAINED",
        "SubmitTime": "2023-06-13T19:04:15.735000+00:00",
        "EndTime": "2023-06-13T19:42:31.752000+00:00",
        "TrainingStartTime": "2023-06-13T19:08:20.114000+00:00",
        "TrainingEndTime": "2023-06-13T19:41:35.080000+00:00",
        "InputDataConfig": {
            "DataFormat": "COMPREHEND_CSV",
            "S3Uri": "s3://DOC-EXAMPLE-BUCKET/trainingdata"
        },
        "OutputDataConfig": {},
        "ClassifierMetadata": {
            "NumberOfLabels": 3,
            "NumberOfTrainedDocuments": 5016,
            "NumberOfTestDocuments": 557,
            "EvaluationMetrics": {
                "Accuracy": 0.9856,
                "Precision": 0.9919,
                "Recall": 0.9459,
                "F1Score": 0.9673,
                "MicroPrecision": 0.9856,
```

```
                "MicroRecall": 0.9856,
                "MicroF1Score": 0.9856,
                "HammingLoss": 0.0144
            }
        },
        "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role",
        "Mode": "MULTI_CLASS"
    }
}
```

Para obter mais informações, consulte Criação e gerenciamento de modelos personalizados no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DescribeDocumentClassifierem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def describe(self, classifier_arn=None):
        """
        Gets metadata about a custom classifier, including its current status.
```

```
        :param classifier_arn: The ARN of the classifier to look up.
        :return: Metadata about the classifier.
        """
        if classifier_arn is not None:
            self.classifier_arn = classifier_arn
        try:
            response = self.comprehend_client.describe_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            classifier = response["DocumentClassifierProperties"]
            logger.info("Got classifier %s.", self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't get classifier %s.", self.classifier_arn)
            raise
        else:
            return classifier
```

- Para obter detalhes da API, consulte a DescribeDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Descreva uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um trabalho de modelagem de tópico do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Execute um trabalho de modelagem de tópicos em dados de amostra

CLI

AWS CLI

Para descrever um trabalho de detecção de tópicos

O exemplo de `describe-topics-detection-job` a seguir obtém as propriedades de um trabalho assíncrono de detecção de tópicos.

```
aws comprehend describe-topics-detection-job \
    --job-id 123456abcdeb0e11022f22a11EXAMPLE
```

Saída:

```
{
    "TopicsDetectionJobProperties": {
        "JobId": "123456abcdeb0e11022f22a11EXAMPLE",
        "JobArn": "arn:aws:comprehend:us-west-2:111122223333:topics-detection-
job/123456abcdeb0e11022f22a11EXAMPLE",
        "JobName": "example_topics_detection",
        "JobStatus": "IN_PROGRESS",
        "SubmitTime": "2023-06-09T18:44:43.414000+00:00",
        "InputDataConfig": {
            "S3Uri": "s3://DOC-EXAMPLE-BUCKET",
            "InputFormat": "ONE_DOC_PER_LINE"
        },
        "OutputDataConfig": {
            "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
testfolder/111122223333-TOPICS-123456abcdeb0e11022f22a11EXAMPLE/output/
output.tar.gz"
        },
        "NumberOfTopics": 10,
        "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-examplerole"
    }
}
```

Para obter mais informações, consulte Análise assíncrona para insights do Amazon Comprehend no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DescribeTopicsDetectionJobem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def describe_job(self, job_id):
        """
        Gets metadata about a topic modeling job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_topics_detection_job(
                JobId=job_id
            )
            job = response["TopicsDetectionJobProperties"]
            logger.info("Got topic detection job %s.", job_id)
        except ClientError:
            logger.exception("Couldn't get topic detection job %s.", job_id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a DescribeTopicsDetectionJobReferência da API AWSSDK for Python (Boto3).

Detecte entidades em um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar entidades em um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use the AmazonComprehend service detect any
/// entities in submitted text.
/// </summary>
public static class DetectEntities
{
    /// <summary>
    /// The main method calls the DetectEntitiesAsync method to find any
    /// entities in the sample code.
    /// </summary>
    public static async Task Main()
```

```
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new AmazonComprehendClient();

            Console.WriteLine("Calling DetectEntities\n");
            var detectEntitiesRequest = new DetectEntitiesRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
            var detectEntitiesResponse = await
 comprehendClient.DetectEntitiesAsync(detectEntitiesRequest);

            foreach (var e in detectEntitiesResponse.Entities)
            {
                Console.WriteLine($"Text: {e.Text}, Type: {e.Type}, Score:
 {e.Score}, BeginOffset: {e.BeginOffset}, EndOffset: {e.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectEntiesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar entidades nomeadas no texto de entrada

O exemplo de `detect-entities` a seguir analisa o texto de entrada e retorna as entidades nomeadas. A pontuação de confiança do modelo pré-treinado também é gerada para cada previsão.

```
aws comprehend detect-entities \
    --language-code en \
    --text "Hello Zhang Wei, I am John. Your AnyCompany Financial Services, LLC
 credit card \
```

```
   account 1111-XXXX-1111-XXXX has a minimum payment of $24.53 that is due by
 July 31st. Based on your autopay settings, \
   we will withdraw your payment on the due date from your bank account number
 XXXXXX1111 with the routing number XXXXX0000. \
   Customer feedback for Sunshine Spa, 123 Main St, Anywhere. Send comments to
 Alice at AnySpa@example.com."
```

Saída:

```
{
    "Entities": [
        {
            "Score": 0.9994556307792664,
            "Type": "PERSON",
            "Text": "Zhang Wei",
            "BeginOffset": 6,
            "EndOffset": 15
        },
        {
            "Score": 0.9981022477149963,
            "Type": "PERSON",
            "Text": "John",
            "BeginOffset": 22,
            "EndOffset": 26
        },
        {
            "Score": 0.9986887574195862,
            "Type": "ORGANIZATION",
            "Text": "AnyCompany Financial Services, LLC",
            "BeginOffset": 33,
            "EndOffset": 67
        },
        {
            "Score": 0.9959119558334351,
            "Type": "OTHER",
            "Text": "1111-XXXX-1111-XXXX",
            "BeginOffset": 88,
            "EndOffset": 107
        },
        {
            "Score": 0.9708039164543152,
            "Type": "QUANTITY",
            "Text": ".53",
```

```
            "BeginOffset": 133,
            "EndOffset": 136
        },
        {
            "Score": 0.9987268447875977,
            "Type": "DATE",
            "Text": "July 31st",
            "BeginOffset": 152,
            "EndOffset": 161
        },
        {
            "Score": 0.9858865737915039,
            "Type": "OTHER",
            "Text": "XXXXXX1111",
            "BeginOffset": 271,
            "EndOffset": 281
        },
        {
            "Score": 0.9700471758842468,
            "Type": "OTHER",
            "Text": "XXXXX0000",
            "BeginOffset": 306,
            "EndOffset": 315
        },
        {
            "Score": 0.9591118693351746,
            "Type": "ORGANIZATION",
            "Text": "Sunshine Spa",
            "BeginOffset": 340,
            "EndOffset": 352
        },
        {
            "Score": 0.9797496795654297,
            "Type": "LOCATION",
            "Text": "123 Main St",
            "BeginOffset": 354,
            "EndOffset": 365
        },
        {
            "Score": 0.994929313659668,
            "Type": "PERSON",
            "Text": "Alice",
            "BeginOffset": 394,
            "EndOffset": 399
```

```
        },
        {
            "Score": 0.9949769377708435,
            "Type": "OTHER",
            "Text": "AnySpa@example.com",
            "BeginOffset": 403,
            "EndOffset": 418
        }
    ]
}
```

Para obter mais informações, consulte Entidades no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DetectEntiticsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.DetectEntitiesRequest;
import software.amazon.awssdk.services.comprehend.model.DetectEntitiesResponse;
import software.amazon.awssdk.services.comprehend.model.Entity;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 */
public class DetectEntities {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectEntities");
        detectAllEntities(comClient, text);
        comClient.close();
    }

    public static void detectAllEntities(ComprehendClient comClient, String text)
 {
        try {
            DetectEntitiesRequest detectEntitiesRequest =
 DetectEntitiesRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectEntitiesResponse detectEntitiesResult =
 comClient.detectEntities(detectEntitiesRequest);
            List<Entity> entList = detectEntitiesResult.entities();
            for (Entity entity : entList) {
                System.out.println("Entity text is " + entity.text());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectEntiesa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_entities(self, text, language_code):
        """
        Detects entities in a document. Entities can be things like people and
 places
        or other common terms.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
            logger.info("Detected %s entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect entities.")
            raise
        else:
            return entities
```

- Para obter detalhes da API, consulte a DetectEntitiesReferência da API AWSSDK for Python (Boto3).

Detecte frases-chave em um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar frases-chave em um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use the Amazon Comprehend service to
/// search text for key phrases.
/// </summary>
public static class DetectKeyPhrase
{
    /// <summary>
    /// This method calls the Amazon Comprehend method DetectKeyPhrasesAsync
```

```
        /// to detect any key phrases in the sample text.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            // Call DetectKeyPhrases API
            Console.WriteLine("Calling DetectKeyPhrases");
            var detectKeyPhrasesRequest = new DetectKeyPhrasesRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
            var detectKeyPhrasesResponse = await
comprehendClient.DetectKeyPhrasesAsync(detectKeyPhrasesRequest);
            foreach (var kp in detectKeyPhrasesResponse.KeyPhrases)
            {
                Console.WriteLine($"Text: {kp.Text}, Score: {kp.Score},
BeginOffset: {kp.BeginOffset}, EndOffset: {kp.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectKeyPhrasesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar frases-chave no texto de entrada

O exemplo de `detect-key-phrases` a seguir analisa o texto de entrada e identifica as principais frases nominais. A pontuação de confiança do modelo pré-treinado também é gerada para cada previsão.

```
aws comprehend detect-key-phrases \
    --language-code en \
    --text "Hello Zhang Wei, I am John. Your AnyCompany Financial Services, LLC
 credit card \
        account 1111-XXXX-1111-XXXX has a minimum payment of $24.53 that is due
 by July 31st. Based on your autopay settings, \
        we will withdraw your payment on the due date from your bank account
 number XXXXXX1111 with the routing number XXXXX0000. \
        Customer feedback for Sunshine Spa, 123 Main St, Anywhere. Send comments
 to Alice at AnySpa@example.com."
```

Saída:

```
{
    "KeyPhrases": [
        {
            "Score": 0.8996376395225525,
            "Text": "Zhang Wei",
            "BeginOffset": 6,
            "EndOffset": 15
        },
        {
            "Score": 0.9992469549179077,
            "Text": "John",
            "BeginOffset": 22,
            "EndOffset": 26
        },
        {
            "Score": 0.988385021686554,
            "Text": "Your AnyCompany Financial Services",
            "BeginOffset": 28,
            "EndOffset": 62
        },
        {
            "Score": 0.8740853071212769,
            "Text": "LLC credit card account 1111-XXXX-1111-XXXX",
            "BeginOffset": 64,
            "EndOffset": 107
        },
        {
            "Score": 0.9999437928199768,
            "Text": "a minimum payment",
            "BeginOffset": 112,
```

```
            "EndOffset": 129
        },
        {
            "Score": 0.9998900890350342,
            "Text": ".53",
            "BeginOffset": 133,
            "EndOffset": 136
        },
        {
            "Score": 0.9979453086853027,
            "Text": "July 31st",
            "BeginOffset": 152,
            "EndOffset": 161
        },
        {
            "Score": 0.9983011484146118,
            "Text": "your autopay settings",
            "BeginOffset": 172,
            "EndOffset": 193
        },
        {
            "Score": 0.9996572136878967,
            "Text": "your payment",
            "BeginOffset": 211,
            "EndOffset": 223
        },
        {
            "Score": 0.9995037317276001,
            "Text": "the due date",
            "BeginOffset": 227,
            "EndOffset": 239
        },
        {
            "Score": 0.9702621698379517,
            "Text": "your bank account number XXXXXX1111",
            "BeginOffset": 245,
            "EndOffset": 280
        },
        {
            "Score": 0.9179925918579102,
            "Text": "the routing number XXXXX0000.Customer feedback",
            "BeginOffset": 286,
            "EndOffset": 332
        },
```

```
        {
            "Score": 0.9978160858154297,
            "Text": "Sunshine Spa",
            "BeginOffset": 337,
            "EndOffset": 349
        },
        {
            "Score": 0.9706913232803345,
            "Text": "123 Main St",
            "BeginOffset": 351,
            "EndOffset": 362
        },
        {
            "Score": 0.9941995143890381,
            "Text": "comments",
            "BeginOffset": 379,
            "EndOffset": 387
        },
        {
            "Score": 0.9759287238121033,
            "Text": "Alice",
            "BeginOffset": 391,
            "EndOffset": 396
        },
        {
            "Score": 0.8376792669296265,
            "Text": "AnySpa@example.com",
            "BeginOffset": 400,
            "EndOffset": 415
        }
    ]
}
```

Para obter mais informações, consulte Frases-chave no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DetectKeyPhrasesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.DetectKeyPhrasesRequest;
import software.amazon.awssdk.services.comprehend.model.DetectKeyPhrasesResponse;
import software.amazon.awssdk.services.comprehend.model.KeyPhrase;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectKeyPhrases {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectKeyPhrases");
        detectAllKeyPhrases(comClient, text);
        comClient.close();
    }
```

```
    public static void detectAllKeyPhrases(ComprehendClient comClient, String
 text) {
        try {
            DetectKeyPhrasesRequest detectKeyPhrasesRequest =
 DetectKeyPhrasesRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectKeyPhrasesResponse detectKeyPhrasesResult =
 comClient.detectKeyPhrases(detectKeyPhrasesRequest);
            List<KeyPhrase> phraseList = detectKeyPhrasesResult.keyPhrases();
            for (KeyPhrase keyPhrase : phraseList) {
                System.out.println("Key phrase text is " + keyPhrase.text());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectKeyPhrasesa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""
```

```
    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_key_phrases(self, text, language_code):
        """
        Detects key phrases in a document. A key phrase is typically a noun and
its
        modifiers.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of key phrases along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_key_phrases(
                Text=text, LanguageCode=language_code
            )
            phrases = response["KeyPhrases"]
            logger.info("Detected %s phrases.", len(phrases))
        except ClientError:
            logger.exception("Couldn't detect phrases.")
            raise
        else:
            return phrases
```

- Para obter detalhes da API, consulte a DetectKeyPhrasesReferência da API AWSSDK for Python (Boto3).

Detecte informações de identificação pessoal em um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar informações de identificação pessoal (PII) em um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use the Amazon Comprehend service to find
/// personally identifiable information (PII) within text submitted to the
/// DetectPiiEntitiesAsync method.
/// </summary>
public class DetectingPII
{
    /// <summary>
    /// This method calls the DetectPiiEntitiesAsync method to locate any
    /// personally dientifiable information within the supplied text.
    /// </summary>
    public static async Task Main()
    {
        var comprehendClient = new AmazonComprehendClient();
        var text = @"Hello Paul Santos. The latest statement for your
                    credit card account 1111-0000-1111-0000 was
                    mailed to 123 Any Street, Seattle, WA 98109.";

        var request = new DetectPiiEntitiesRequest
        {
            Text = text,
            LanguageCode = "EN",
        };
```

```
            var response = await
 comprehendClient.DetectPiiEntitiesAsync(request);

            if (response.Entities.Count > 0)
            {
                foreach (var entity in response.Entities)
                {
                    var entityValue = text.Substring(entity.BeginOffset,
 entity.EndOffset - entity.BeginOffset);
                    Console.WriteLine($"{entity.Type}: {entityValue}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectPiiEntitiesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar entidades PII no texto de entrada

O exemplo de `detect-pii-entities` a seguir analisa o texto de entrada e identifica entidades que contêm informações de identificação pessoal (PII). A pontuação de confiança do modelo pré-treinado também é gerada para cada previsão.

```
aws comprehend detect-pii-entities \
    --language-code en \
    --text "Hello Zhang Wei, I am John. Your AnyCompany Financial Services, LLC
 credit card \
        account 1111-XXXX-1111-XXXX has a minimum payment of $24.53 that is due
 by July 31st. Based on your autopay settings, \
        we will withdraw your payment on the due date from your bank account
 number XXXXXX1111 with the routing number XXXXX0000. \
        Customer feedback for Sunshine Spa, 123 Main St, Anywhere. Send comments
 to Alice at AnySpa@example.com."
```

Saída:

```
{
    "Entities": [
        {
            "Score": 0.9998322129249573,
            "Type": "NAME",
            "BeginOffset": 6,
            "EndOffset": 15
        },
        {
            "Score": 0.9998878240585327,
            "Type": "NAME",
            "BeginOffset": 22,
            "EndOffset": 26
        },
        {
            "Score": 0.9994089603424072,
            "Type": "CREDIT_DEBIT_NUMBER",
            "BeginOffset": 88,
            "EndOffset": 107
        },
        {
            "Score": 0.9999760985374451,
            "Type": "DATE_TIME",
            "BeginOffset": 152,
            "EndOffset": 161
        },
        {
            "Score": 0.9999449253082275,
            "Type": "BANK_ACCOUNT_NUMBER",
            "BeginOffset": 271,
            "EndOffset": 281
        },
        {
            "Score": 0.9999847412109375,
            "Type": "BANK_ROUTING",
            "BeginOffset": 306,
            "EndOffset": 315
        },
        {
            "Score": 0.999925434589386,
            "Type": "ADDRESS",
            "BeginOffset": 354,
            "EndOffset": 365
```

```
        },
        {
            "Score": 0.9989161491394043,
            "Type": "NAME",
            "BeginOffset": 394,
            "EndOffset": 399
        },
        {
            "Score": 0.9994171857833862,
            "Type": "EMAIL",
            "BeginOffset": 403,
            "EndOffset": 418
        }
    ]
}
```

Para obter mais informações, consulte Informações de identificação pessoal (PII) no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DetectPiiEntiesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
```

```
    def detect_pii(self, text, language_code):
        """
        Detects personally identifiable information (PII) in a document. PII can
be
        things like names, account numbers, or addresses.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of PII entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_pii_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
            logger.info("Detected %s PII entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect PII entities.")
            raise
        else:
            return entities
```

- Para obter detalhes da API, consulte a DetectPiiEntitiesReferência da API AWSSDK for Python (Boto3).

Detecte elementos sintáticos de um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar elementos sintáticos de um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use Amazon Comprehend to detect syntax
/// elements by calling the DetectSyntaxAsync method.
/// </summary>
public class DetectingSyntax
{
    /// <summary>
    /// This method calls DetectSynaxAsync to identify the syntax elements
    /// in the sample text.
    /// </summary>
    public static async Task Main()
    {
        string text = "It is raining today in Seattle";

        var comprehendClient = new AmazonComprehendClient();

        // Call DetectSyntax API
        Console.WriteLine("Calling DetectSyntaxAsync\n");
        var detectSyntaxRequest = new DetectSyntaxRequest()
        {
            Text = text,
            LanguageCode = "en",
        };
        DetectSyntaxResponse detectSyntaxResponse = await
comprehendClient.DetectSyntaxAsync(detectSyntaxRequest);
        foreach (SyntaxToken s in detectSyntaxResponse.SyntaxTokens)
        {
```

```
                Console.WriteLine($"Text: {s.Text}, PartOfSpeech:
 {s.PartOfSpeech.Tag}, BeginOffset: {s.BeginOffset}, EndOffset: {s.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectSyntaxa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar as partes da fala em um texto de entrada

O exemplo de `detect-syntax` a seguir analisa a sintaxe do texto de entrada e retorna as diferentes partes da fala. A pontuação de confiança do modelo pré-treinado também é gerada para cada previsão.

```
aws comprehend detect-syntax \
    --language-code en \
    --text "It is a beautiful day in Seattle."
```

Saída:

```
{
    "SyntaxTokens": [
        {
            "TokenId": 1,
            "Text": "It",
            "BeginOffset": 0,
            "EndOffset": 2,
            "PartOfSpeech": {
                "Tag": "PRON",
                "Score": 0.9999740719795227
            }
        },
        {
            "TokenId": 2,
```

```
            "Text": "is",
            "BeginOffset": 3,
            "EndOffset": 5,
            "PartOfSpeech": {
                "Tag": "VERB",
                "Score": 0.999901294708252
            }
        },
        {
            "TokenId": 3,
            "Text": "a",
            "BeginOffset": 6,
            "EndOffset": 7,
            "PartOfSpeech": {
                "Tag": "DET",
                "Score": 0.9999938607215881
            }
        },
        {
            "TokenId": 4,
            "Text": "beautiful",
            "BeginOffset": 8,
            "EndOffset": 17,
            "PartOfSpeech": {
                "Tag": "ADJ",
                "Score": 0.9987351894378662
            }
        },
        {
            "TokenId": 5,
            "Text": "day",
            "BeginOffset": 18,
            "EndOffset": 21,
            "PartOfSpeech": {
                "Tag": "NOUN",
                "Score": 0.9999796748161316
            }
        },
        {
            "TokenId": 6,
            "Text": "in",
            "BeginOffset": 22,
            "EndOffset": 24,
            "PartOfSpeech": {
```

```
                "Tag": "ADP",
                "Score": 0.9998047947883606
            }
        },
        {
            "TokenId": 7,
            "Text": "Seattle",
            "BeginOffset": 25,
            "EndOffset": 32,
            "PartOfSpeech": {
                "Tag": "PROPN",
                "Score": 0.9940530061721802
            }
        }
    ]
}
```

Para obter mais informações, consulte Análise de sintaxe no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DetectSyntaxem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import software.amazon.awssdk.services.comprehend.model.DetectSyntaxRequest;
import software.amazon.awssdk.services.comprehend.model.DetectSyntaxResponse;
import software.amazon.awssdk.services.comprehend.model.SyntaxToken;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectSyntax {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectSyntax");
        detectAllSyntax(comClient, text);
        comClient.close();
    }

    public static void detectAllSyntax(ComprehendClient comClient, String text) {
        try {
            DetectSyntaxRequest detectSyntaxRequest =
 DetectSyntaxRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectSyntaxResponse detectSyntaxResult =
 comClient.detectSyntax(detectSyntaxRequest);
            List<SyntaxToken> syntaxTokens = detectSyntaxResult.syntaxTokens();
            for (SyntaxToken token : syntaxTokens) {
                System.out.println("Language is " + token.text());
                System.out.println("Part of speech is " +
 token.partOfSpeech().tagAsString());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte DetectSyntaxa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_syntax(self, text, language_code):
        """
        Detects syntactical elements of a document. Syntax tokens are portions of
        text along with their use as parts of speech, such as nouns, verbs, and
        interjections.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of syntax tokens along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_syntax(
                Text=text, LanguageCode=language_code
            )
```

```
            tokens = response["SyntaxTokens"]
            logger.info("Detected %s syntax tokens.", len(tokens))
        except ClientError:
            logger.exception("Couldn't detect syntax.")
            raise
        else:
            return tokens
```

- Para obter detalhes da API, consulte a DetectSyntaxReferência da API AWSSDK for Python (Boto3).

Detecte a linguagem dominante em um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar a linguagem dominante em um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;
```

```
    /// <summary>
    /// This example calls the Amazon Comprehend service to determine the
    /// dominant language.
    /// </summary>
    public static class DetectDominantLanguage
    {
        /// <summary>
        /// Calls Amazon Comprehend to determine the dominant language used in
        /// the sample text.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle.";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            Console.WriteLine("Calling DetectDominantLanguage\n");
            var detectDominantLanguageRequest = new
DetectDominantLanguageRequest()
            {
                Text = text,
            };

            var detectDominantLanguageResponse = await
comprehendClient.DetectDominantLanguageAsync(detectDominantLanguageRequest);
            foreach (var dl in detectDominantLanguageResponse.Languages)
            {
                Console.WriteLine($"Language Code: {dl.LanguageCode}, Score:
{dl.Score}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectDominantLanguagea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar o idioma dominante do texto de entrada

O `detect-dominant-language` a seguir analisa o texto de entrada e identifica o idioma dominante. A pontuação de confiança do modelo pré-treinado também é gerada.

```
aws comprehend detect-dominant-language \
    --text "It is a beautiful day in Seattle."
```

Saída:

```
{
    "Languages": [
        {
            "LanguageCode": "en",
            "Score": 0.9877256155014038
        }
    ]
}
```

Para obter mais informações, consulte Idioma dominante no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte DetectDominantLanguageem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
```

```
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import
 software.amazon.awssdk.services.comprehend.model.DetectDominantLanguageRequest;
import
 software.amazon.awssdk.services.comprehend.model.DetectDominantLanguageResponse;
import software.amazon.awssdk.services.comprehend.model.DominantLanguage;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectLanguage {
    public static void main(String[] args) {
        // Specify French text - "It is raining today in Seattle".
        String text = "Il pleut aujourd'hui à Seattle";
        Region region = Region.US_EAST_1;

        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectDominantLanguage");
        detectTheDominantLanguage(comClient, text);
        comClient.close();
    }

    public static void detectTheDominantLanguage(ComprehendClient comClient,
 String text) {
        try {
            DetectDominantLanguageRequest request =
 DetectDominantLanguageRequest.builder()
                    .text(text)
                    .build();

            DetectDominantLanguageResponse resp =
 comClient.detectDominantLanguage(request);
            List<DominantLanguage> allLanList = resp.languages();
            for (DominantLanguage lang : allLanList) {
```

```
                System.out.println("Language is " + lang.languageCode());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectDominantLanguagea Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_languages(self, text):
        """
        Detects languages used in a document.

        :param text: The document to inspect.
        :return: The list of languages along with their confidence scores.
        """
```

```
        try:
            response = self.comprehend_client.detect_dominant_language(Text=text)
            languages = response["Languages"]
            logger.info("Detected %s languages.", len(languages))
        except ClientError:
            logger.exception("Couldn't detect languages.")
            raise
        else:
            return languages
```

- Para obter detalhes da API, consulte a DetectDominantLanguageReferência da API AWSSDK for Python (Boto3).

Detecte o sentimento de um documento com o Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar o sentimento de um documento com o Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Detectar elementos do documento

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
```

```
    using Amazon.Comprehend.Model;

    /// <summary>
    /// This example shows how to detect the overall sentiment of the supplied
    /// text using the Amazon Comprehend service.
    /// </summary>
    public static class DetectSentiment
    {
        /// <summary>
        /// This method calls the DetetectSentimentAsync method to analyze the
        /// supplied text and determine the overal sentiment.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            // Call DetectKeyPhrases API
            Console.WriteLine("Calling DetectSentiment");
            var detectSentimentRequest = new DetectSentimentRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
            var detectSentimentResponse = await
comprehendClient.DetectSentimentAsync(detectSentimentRequest);
            Console.WriteLine($"Sentiment: {detectSentimentResponse.Sentiment}");
            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectSentimenta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para detectar o sentimento de um texto de entrada

O exemplo de `detect-sentiment` a seguir analisa o texto de entrada e retorna uma inferência do sentimento predominante (`POSITIVE`, `NEUTRAL`, `MIXED` ou `NEGATIVE`).

```
aws comprehend detect-sentiment \
    --language-code en \
    --text "It is a beautiful day in Seattle"
```

Saída:

```
{
    "Sentiment": "POSITIVE",
    "SentimentScore": {
        "Positive": 0.9976957440376282,
        "Negative": 9.653854067437351e-05,
        "Neutral": 0.002169104292988777,
        "Mixed": 3.857641786453314e-05
    }
}
```

Para obter mais informações, consulte Sentimento no Guia do desenvolvedor do Amazon Comprehend

- Para obter detalhes da API, consulte DetectSentimentem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import software.amazon.awssdk.services.comprehend.model.DetectSentimentRequest;
import software.amazon.awssdk.services.comprehend.model.DetectSentimentResponse;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectSentiment {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectSentiment");
        detectSentiments(comClient, text);
        comClient.close();
    }

    public static void detectSentiments(ComprehendClient comClient, String text)
 {
        try {
            DetectSentimentRequest detectSentimentRequest =
 DetectSentimentRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectSentimentResponse detectSentimentResult =
 comClient.detectSentiment(detectSentimentRequest);
            System.out.println("The Neutral value is " +
 detectSentimentResult.sentimentScore().neutral());

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte DetectSentimenta Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_sentiment(self, text, language_code):
        """
        Detects the overall sentiment expressed in a document. Sentiment can
        be positive, negative, neutral, or a mixture.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The sentiments along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_sentiment(
                Text=text, LanguageCode=language_code
            )
            logger.info("Detected primary sentiment %s.", response["Sentiment"])
        except ClientError:
```

```
            logger.exception("Couldn't detect sentiment.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DetectSentimentReferência da API AWSSDK for Python (Boto3).

Liste tarefas de classificação de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como listar tarefas de classificação de documento do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para listar trabalhos de classificação de documento

O exemplo de `list-document-classification-jobs` a seguir lista todos os trabalhos de classificação de documentos.

```
aws comprehend list-document-classification-jobs
```

Saída:

```
{
    "DocumentClassificationJobPropertiesList": [
        {
            "JobId": "123456abcdeb0e11022f22a11EXAMPLE",
            "JobArn": "arn:aws:comprehend:us-west-2:1234567890101:document-
classification-job/123456abcdeb0e11022f22a11EXAMPLE",
            "JobName": "exampleclassificationjob",
```

```
            "JobStatus": "COMPLETED",
            "SubmitTime": "2023-06-14T17:09:51.788000+00:00",
            "EndTime": "2023-06-14T17:15:58.582000+00:00",
            "DocumentClassifierArn": "arn:aws:comprehend:us-
west-2:1234567890101:document-classifier/mymodel/version/12",
            "InputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET/jobdata/",
                "InputFormat": "ONE_DOC_PER_LINE"
            },
            "OutputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
thefolder/1234567890101-CLN-e758dd56b824aa717ceab551f11749fb/output/
output.tar.gz"
            },
            "DataAccessRoleArn": "arn:aws:iam::1234567890101:role/service-role/
AmazonComprehendServiceRole-example-role"
        },
        {
            "JobId": "123456abcdeb0e11022f22a1EXAMPLE2",
            "JobArn": "arn:aws:comprehend:us-west-2:1234567890101:document-
classification-job/123456abcdeb0e11022f22a1EXAMPLE2",
            "JobName": "exampleclassificationjob2",
            "JobStatus": "COMPLETED",
            "SubmitTime": "2023-06-14T17:22:39.829000+00:00",
            "EndTime": "2023-06-14T17:28:46.107000+00:00",
            "DocumentClassifierArn": "arn:aws:comprehend:us-
west-2:1234567890101:document-classifier/mymodel/version/12",
            "InputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET/jobdata/",
                "InputFormat": "ONE_DOC_PER_LINE"
            },
            "OutputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
thefolder/1234567890101-CLN-123456abcdeb0e11022f22a1EXAMPLE2/output/
output.tar.gz"
            },
            "DataAccessRoleArn": "arn:aws:iam::1234567890101:role/service-role/
AmazonComprehendServiceRole-example-role"
        }
    ]
}
```

Para obter mais informações, consulte Classificação personalizada no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte ListDocumentClassificationJobsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def list_jobs(self):
        """
        Lists the classification jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_document_classification_jobs()
            jobs = response["DocumentClassificationJobPropertiesList"]
            logger.info("Got %s document classification jobs.", len(jobs))
        except ClientError:
            logger.exception(
                "Couldn't get document classification jobs.",
            )
            raise
```

```
        else:
            return jobs
```

- Para obter detalhes da API, consulte a ListDocumentClassificationJobsReferência da API AWSSDK for Python (Boto3).

Liste os classificadores de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os classificadores de documento do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para listar todos os classificadores de documentos

O exemplo de `list-document-classifiers` a seguir lista todos os modelos de classificadores de documentos treinados e em treinamento.

```
aws comprehend list-document-classifiers
```

Saída:

```
{
    "DocumentClassifierPropertiesList": [
        {
            "DocumentClassifierArn": "arn:aws:comprehend:us-
west-2:111122223333:document-classifier/exampleclassifier1",
            "LanguageCode": "en",
            "Status": "TRAINED",
            "SubmitTime": "2023-06-13T19:04:15.735000+00:00",
```

```
            "EndTime": "2023-06-13T19:42:31.752000+00:00",
            "TrainingStartTime": "2023-06-13T19:08:20.114000+00:00",
            "TrainingEndTime": "2023-06-13T19:41:35.080000+00:00",
            "InputDataConfig": {
                "DataFormat": "COMPREHEND_CSV",
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET/trainingdata"
            },
            "OutputDataConfig": {},
            "ClassifierMetadata": {
                "NumberOfLabels": 3,
                "NumberOfTrainedDocuments": 5016,
                "NumberOfTestDocuments": 557,
                "EvaluationMetrics": {
                    "Accuracy": 0.9856,
                    "Precision": 0.9919,
                    "Recall": 0.9459,
                    "F1Score": 0.9673,
                    "MicroPrecision": 0.9856,
                    "MicroRecall": 0.9856,
                    "MicroF1Score": 0.9856,
                    "HammingLoss": 0.0144
                }
            },
            "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-testorle",
            "Mode": "MULTI_CLASS"
        },
        {
            "DocumentClassifierArn": "arn:aws:comprehend:us-
west-2:111122223333:document-classifier/exampleclassifier2",
            "LanguageCode": "en",
            "Status": "TRAINING",
            "SubmitTime": "2023-06-13T21:20:28.690000+00:00",
            "InputDataConfig": {
                "DataFormat": "COMPREHEND_CSV",
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET/trainingdata"
            },
            "OutputDataConfig": {},
            "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-testorle",
            "Mode": "MULTI_CLASS"
        }
    ]
```

```
}
```

Para obter mais informações, consulte Criação e gerenciamento de modelos personalizados no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte ListDocumentClassifiersem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def list(self):
        """
        Lists custom classifiers for the current account.

        :return: The list of classifiers.
        """
        try:
            response = self.comprehend_client.list_document_classifiers()
            classifiers = response["DocumentClassifierPropertiesList"]
            logger.info("Got %s classifiers.", len(classifiers))
        except ClientError:
            logger.exception(
                "Couldn't get classifiers.",
```

```
            )
            raise
        else:
            return classifiers
```

- Para obter detalhes da API, consulte a ListDocumentClassifiersReferência da API AWSSDK for Python (Boto3).

Liste tarefas de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como listar trabalhos de modelagem de tópico do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Execute um trabalho de modelagem de tópicos em dados de amostra

CLI

AWS CLI

Para listar todos os trabalhos de detecção de tópicos

O exemplo de `list-topics-detection-jobs` a seguir lista todos os trabalhos de detecção de tópicos assíncronos em andamento e concluídos.

```
aws comprehend list-topics-detection-jobs
```

Saída:

```
{
    "TopicsDetectionJobPropertiesList": [
        {
            "JobId": "123456abcdeb0e11022f22a11EXAMPLE",
            "JobArn": "arn:aws:comprehend:us-west-2:111122223333:topics-
detection-job/123456abcdeb0e11022f22a11EXAMPLE",
            "JobName" "topic-analysis-1"
```

```
            "JobStatus": "IN_PROGRESS",
            "SubmitTime": "2023-06-09T18:40:35.384000+00:00",
            "EndTime": "2023-06-09T18:46:41.936000+00:00",
            "InputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET",
                "InputFormat": "ONE_DOC_PER_LINE"
            },
            "OutputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
thefolder/111122223333-TOPICS-123456abcdeb0e11022f22a11EXAMPLE/output/
output.tar.gz"
            },
            "NumberOfTopics": 10,
            "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role"
        },
        {
            "JobId": "123456abcdeb0e11022f22a1EXAMPLE2",
            "JobArn": "arn:aws:comprehend:us-west-2:111122223333:topics-
detection-job/123456abcdeb0e11022f22a1EXAMPLE2",
            "JobName": "topic-analysis-2",
            "JobStatus": "COMPLETED",
            "SubmitTime": "2023-06-09T18:44:43.414000+00:00",
            "EndTime": "2023-06-09T18:50:50.872000+00:00",
            "InputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET",
                "InputFormat": "ONE_DOC_PER_LINE"
            },
            "OutputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
thefolder/111122223333-TOPICS-123456abcdeb0e11022f22a1EXAMPLE2/output/
output.tar.gz"
            },
            "NumberOfTopics": 10,
            "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role"
        },
        {
            "JobId": "123456abcdeb0e11022f22a1EXAMPLE3",
            "JobArn": "arn:aws:comprehend:us-west-2:111122223333:topics-
detection-job/123456abcdeb0e11022f22a1EXAMPLE3",
            "JobName": "topic-analysis-2",
            "JobStatus": "IN_PROGRESS",
            "SubmitTime": "2023-06-09T18:50:56.737000+00:00",
```

```
            "InputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-BUCKET",
                "InputFormat": "ONE_DOC_PER_LINE"
            },
            "OutputDataConfig": {
                "S3Uri": "s3://DOC-EXAMPLE-DESTINATION-BUCKET/
thefolder/111122223333-TOPICS-123456abcdeb0e11022f22a1EXAMPLE3/output/
output.tar.gz"
            },
            "NumberOfTopics": 10,
            "DataAccessRoleArn": "arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role"
        }
    ]
}
```

Para obter mais informações, consulte Análise assíncrona para insights do Amazon Comprehend no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte ListTopicsDetectionJobsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
```

```
    def list_jobs(self):
        """
        Lists topic modeling jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_topics_detection_jobs()
            jobs = response["TopicsDetectionJobPropertiesList"]
            logger.info("Got %s topic detection jobs.", len(jobs))
        except ClientError:
            logger.exception("Couldn't get topic detection jobs.")
            raise
        else:
            return jobs
```

- Para obter detalhes da API, consulte a ListTopicsDetectionJobsReferência da API AWSSDK for Python (Boto3).

Inicie uma tarefa de classificação de documentos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar uma tarefa de classificação de documento do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Treine um classificador personalizado e classifique documentos

CLI

AWS CLI

Para iniciar um trabalho de classificação de documento

O exemplo de `start-document-classification-job` a seguir inicia um trabalho de classificação de documentos com um modelo personalizado em todos os arquivos no

endereço especificado pela tag `--input-data-config`. Neste exemplo, o bucket do S3 de entrada contém `SampleSMStext1.txt`, `SampleSMStext2.txt` e `SampleSMStext3.txt`. O modelo foi previamente treinado na classificação de documentos de mensagens de spam e não spam, ou “ham”, e mensagens SMS. Quando o trabalho é concluído, `output.tar.gz` é colocado no local especificado pela tag `--output-data-config`. `output.tar.gz` contém `predictions.jsonl`, que lista a classificação de cada documento. A saída Json é impressa em uma linha por arquivo, mas foi formatada aqui para facilitar a leitura.

```
aws comprehend start-document-classification-job \
    --job-name exampleclassificationjob \
    --input-data-config "S3Uri=s3://DOC-EXAMPLE-BUCKET-INPUT/jobdata/" \
    --output-data-config "S3Uri=s3://DOC-EXAMPLE-DESTINATION-BUCKET/testfolder/"
 \
    --data-access-role-arn arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role \
    --document-classifier-arn arn:aws:comprehend:us-west-2:111122223333:document-
classifier/mymodel/version/12
```

Conteúdo de `SampleSMStext1.txt`:

```
"CONGRATULATIONS! TXT 2155550100 to win $5000"
```

Conteúdo de `SampleSMStext2.txt`:

```
"Hi, when do you want me to pick you up from practice?"
```

Conteúdo de `SampleSMStext3.txt`:

```
"Plz send bank account # to 2155550100 to claim prize!!"
```

Saída:

```
{
    "JobId": "e758dd56b824aa717ceab551fEXAMPLE",
    "JobArn": "arn:aws:comprehend:us-west-2:111122223333:document-classification-
job/e758dd56b824aa717ceab551fEXAMPLE",
    "JobStatus": "SUBMITTED"
}
```

Conteúdo de `predictions.jsonl`:

```
{"File": "SampleSMSText1.txt", "Line": "0", "Classes": [{"Name": "spam", "Score":
 0.9999}, {"Name": "ham", "Score": 0.0001}]}
{"File": "SampleSMStext2.txt", "Line": "0", "Classes": [{"Name": "ham", "Score":
 0.9994}, {"Name": "spam", "Score": 0.0006}]}
{"File": "SampleSMSText3.txt", "Line": "0", "Classes": [{"Name": "spam", "Score":
 0.9999}, {"Name": "ham", "Score": 0.0001}]}
```

Para obter mais informações, consulte Classificação personalizada no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte StartDocumentClassificationJobem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
```

```
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a classification job. The classifier must be trained or the job
        will fail. Input is read from the specified Amazon S3 input bucket and
        written to the specified output bucket. Output data is stored in a tar
        archive compressed in gzip format. The job runs asynchronously, so you
can
        call `describe_document_classification_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: The Amazon S3 bucket that contains input data.
        :param input_key: The prefix used to find input data in the input
                          bucket. If multiple objects have the same prefix, all
                          of them are used.
        :param input_format: The format of the input data, either one document
per
                             file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
that
                                     grants Comprehend permission to read from
the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_document_classification_job(
                DocumentClassifierArn=self.classifier_arn,
                JobName=job_name,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
                DataAccessRoleArn=data_access_role_arn,
            )
            logger.info(
                "Document classification job %s is %s.", job_name,
response["JobStatus"]
            )
```

```
        except ClientError:
            logger.exception("Couldn't start classification job %s.", job_name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartDocumentClassificationJobReferência da API AWSSDK for Python (Boto3).

Inicie uma tarefa de modelagem de tópicos do Amazon Comprehend usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar um trabalho de modelagem de tópicos do Amazon Comprehend.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Execute um trabalho de modelagem de tópicos em dados de amostra

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example scans the documents in an Amazon Simple Storage Service
/// (Amazon S3) bucket and analyzes it for topics. The results are stored
```

```
    /// in another bucket and then the resulting job properties are displayed
    /// on the screen. This example was created using the AWS SDK for .NEt
    /// version 3.7 and .NET Core version 5.0.
    /// </summary>
    public static class TopicModeling
    {
        /// <summary>
        /// This methos calls a topic detection job by calling the Amazon
        /// Comprehend StartTopicsDetectionJobRequest.
        /// </summary>
        public static async Task Main()
        {
            var comprehendClient = new AmazonComprehendClient();

            string inputS3Uri = "s3://input bucket/input path";
            InputFormat inputDocFormat = InputFormat.ONE_DOC_PER_FILE;
            string outputS3Uri = "s3://output bucket/output path";
            string dataAccessRoleArn = "arn:aws:iam::account ID:role/data access
role";
            int numberOfTopics = 10;

            var startTopicsDetectionJobRequest = new
StartTopicsDetectionJobRequest()
            {
                InputDataConfig = new InputDataConfig()
                {
                    S3Uri = inputS3Uri,
                    InputFormat = inputDocFormat,
                },
                OutputDataConfig = new OutputDataConfig()
                {
                    S3Uri = outputS3Uri,
                },
                DataAccessRoleArn = dataAccessRoleArn,
                NumberOfTopics = numberOfTopics,
            };

            var startTopicsDetectionJobResponse = await
comprehendClient.StartTopicsDetectionJobAsync(startTopicsDetectionJobRequest);

            var jobId = startTopicsDetectionJobResponse.JobId;
            Console.WriteLine("JobId: " + jobId);
```

```
            var describeTopicsDetectionJobRequest = new
DescribeTopicsDetectionJobRequest()
            {
                JobId = jobId,
            };

            var describeTopicsDetectionJobResponse = await
comprehendClient.DescribeTopicsDetectionJobAsync(describeTopicsDetectionJobRequest);

PrintJobProperties(describeTopicsDetectionJobResponse.TopicsDetectionJobProperties);

            var listTopicsDetectionJobsResponse = await
comprehendClient.ListTopicsDetectionJobsAsync(new
ListTopicsDetectionJobsRequest());
            foreach (var props in
listTopicsDetectionJobsResponse.TopicsDetectionJobPropertiesList)
            {
                PrintJobProperties(props);
            }
        }

        /// <summary>
        /// This method is a helper method that displays the job properties
        /// from the call to StartTopicsDetectionJobRequest.
        /// </summary>
        /// <param name="props">A list of properties from the call to
        /// StartTopicsDetectionJobRequest.</param>
        private static void PrintJobProperties(TopicsDetectionJobProperties
props)
        {
            Console.WriteLine($"JobId: {props.JobId}, JobName: {props.JobName},
JobStatus: {props.JobStatus}");
            Console.WriteLine($"NumberOfTopics:
{props.NumberOfTopics}\nInputS3Uri: {props.InputDataConfig.S3Uri}");
            Console.WriteLine($"InputFormat: {props.InputDataConfig.InputFormat},
OutputS3Uri: {props.OutputDataConfig.S3Uri}");
        }
    }
```

- Para obter detalhes da API, consulte StartTopicsDetectionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para iniciar um trabalho de análise de detecção de tópicos

O exemplo de `start-topics-detection-job` a seguir inicia um trabalho assíncrono de detecção de tópicos para todos os arquivos localizados no endereço especificado pela tag `--input-data-config`. Quando o trabalho é concluído, a pasta, `output`, é colocada no local especificado pela tag `--ouput-data-config`. `output` contém topic-terms.csv e doc-topics.csv. O primeiro arquivo de saída, topic-terms.csv, é uma lista de tópicos na coleção. Para cada tópico, a lista inclui por padrão os principais termos por tópico de acordo com seu peso. O segundo arquivo, `doc-topics.csv`, lista os documentos associados a um tópico e a proporção do documento relacionada ao tópico.

```
aws comprehend start-topics-detection-job \
    --job-name example_topics_detection_job \
    --language-code en \
    --input-data-config "S3Uri=s3://DOC-EXAMPLE-BUCKET/" \
    --output-data-config "S3Uri=s3://DOC-EXAMPLE-DESTINATION-BUCKET/testfolder/"
 \
    --data-access-role-arn arn:aws:iam::111122223333:role/service-role/
AmazonComprehendServiceRole-example-role \
    --language-code en
```

Saída:

```
{
    "JobId": "123456abcdeb0e11022f22a11EXAMPLE",
    "JobArn": "arn:aws:comprehend:us-west-2:111122223333:key-phrases-detection-
job/123456abcdeb0e11022f22a11EXAMPLE",
    "JobStatus": "SUBMITTED"
}
```

Para obter mais informações, consulte Modelagem de tópicos no Guia do desenvolvedor do Amazon Comprehend.

- Para obter detalhes da API, consulte StartTopicsDetectionJobem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a topic modeling job. Input is read from the specified Amazon S3
        input bucket and written to the specified output bucket. Output data is
 stored
        in a tar archive compressed in gzip format. The job runs asynchronously,
 so you
        can call `describe_topics_detection_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: An Amazon S3 bucket that contains job input.
        :param input_key: The prefix used to find input data in the input
```

```
                                bucket. If multiple objects have the same prefix,
all
                                of them are used.
        :param input_format: The format of the input data, either one document
per
                                file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
that
                                        grants Comprehend permission to read from
the
                                        input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_topics_detection_job(
                JobName=job_name,
                DataAccessRoleArn=data_access_role_arn,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
            )
            logger.info("Started topic modeling job %s.", response["JobId"])
        except ClientError:
            logger.exception("Couldn't start topic modeling job.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartTopicsDetectionJobReferência da API AWSSDK for Python (Boto3).

Cenários do Amazon Comprehend usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Comprehend com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Detecte elementos do documento com o Amazon Comprehend e um SDK da AWS
- Execute uma tarefa de modelagem de tópicos do Amazon Comprehend em dados de amostra usando um SDK da AWS
- Treine um classificador Amazon Comprehend personalizado e classifique documentos usando um SDK da AWS

Detecte elementos do documento com o Amazon Comprehend e um SDK da AWS

O código de exemplo a seguir mostra como:

- Detectar idiomas, entidades e frases-chave em um documento.
- Detectar informações de identificação pessoal (PII) em um documento.
- Detectar o sentimento em um documento.
- Detectar elementos de sintaxe em um documento.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as ações do Amazon Comprehend.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
```

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_languages(self, text):
        """
        Detects languages used in a document.

        :param text: The document to inspect.
        :return: The list of languages along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_dominant_language(Text=text)
            languages = response["Languages"]
            logger.info("Detected %s languages.", len(languages))
        except ClientError:
            logger.exception("Couldn't detect languages.")
            raise
        else:
            return languages


    def detect_entities(self, text, language_code):
        """
        Detects entities in a document. Entities can be things like people and
 places
        or other common terms.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
            logger.info("Detected %s entities.", len(entities))
```

```
        except ClientError:
            logger.exception("Couldn't detect entities.")
            raise
        else:
            return entities


    def detect_key_phrases(self, text, language_code):
        """
        Detects key phrases in a document. A key phrase is typically a noun and
its
        modifiers.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of key phrases along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_key_phrases(
                Text=text, LanguageCode=language_code
            )
            phrases = response["KeyPhrases"]
            logger.info("Detected %s phrases.", len(phrases))
        except ClientError:
            logger.exception("Couldn't detect phrases.")
            raise
        else:
            return phrases


    def detect_pii(self, text, language_code):
        """
        Detects personally identifiable information (PII) in a document. PII can
be
        things like names, account numbers, or addresses.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of PII entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_pii_entities(
                Text=text, LanguageCode=language_code
            )
```

```
            entities = response["Entities"]
            logger.info("Detected %s PII entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect PII entities.")
            raise
        else:
            return entities


    def detect_sentiment(self, text, language_code):
        """
        Detects the overall sentiment expressed in a document. Sentiment can
        be positive, negative, neutral, or a mixture.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The sentiments along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_sentiment(
                Text=text, LanguageCode=language_code
            )
            logger.info("Detected primary sentiment %s.", response["Sentiment"])
        except ClientError:
            logger.exception("Couldn't detect sentiment.")
            raise
        else:
            return response


    def detect_syntax(self, text, language_code):
        """
        Detects syntactical elements of a document. Syntax tokens are portions of
        text along with their use as parts of speech, such as nouns, verbs, and
        interjections.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of syntax tokens along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_syntax(
                Text=text, LanguageCode=language_code
            )
```

```
            tokens = response["SyntaxTokens"]
            logger.info("Detected %s syntax tokens.", len(tokens))
        except ClientError:
            logger.exception("Couldn't detect syntax.")
            raise
        else:
            return tokens
```

Chamar funções na classe wrapper para detectar entidades, frases e mais em um documento.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend detection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    comp_detect = ComprehendDetect(boto3.client("comprehend"))
    with open("detect_sample.txt") as sample_file:
        sample_text = sample_file.read()

    demo_size = 3

    print("Sample text used for this demo:")
    print("-" * 88)
    print(sample_text)
    print("-" * 88)

    print("Detecting languages.")
    languages = comp_detect.detect_languages(sample_text)
    pprint(languages)
    lang_code = languages[0]["LanguageCode"]

    print("Detecting entities.")
    entities = comp_detect.detect_entities(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(entities[:demo_size])

    print("Detecting key phrases.")
    phrases = comp_detect.detect_key_phrases(sample_text, lang_code)
```

```
    print(f"The first {demo_size} are:")
    pprint(phrases[:demo_size])

    print("Detecting personally identifiable information (PII).")
    pii_entities = comp_detect.detect_pii(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(pii_entities[:demo_size])

    print("Detecting sentiment.")
    sentiment = comp_detect.detect_sentiment(sample_text, lang_code)
    print(f"Sentiment: {sentiment['Sentiment']}")
    print("SentimentScore:")
    pprint(sentiment["SentimentScore"])

    print("Detecting syntax elements.")
    syntax_tokens = comp_detect.detect_syntax(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(syntax_tokens[:demo_size])

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DetectDominantLanguage
  - DetectEntities
  - DetectKeyPhrases
  - DetectPiiEntities
  - DetectSentiment
  - DetectSyntax

Execute uma tarefa de modelagem de tópicos do Amazon Comprehend em dados de amostra usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Executar um trabalho de modelagem de tópico do Amazon Comprehend em dados de amostra.
- Obter informações sobre o trabalho.
- Extrair dados de saída do trabalho no Amazon S3.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe wrapper para chamar as ações de modelagem de tópico do Amazon Comprehend.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a topic modeling job. Input is read from the specified Amazon S3
        input bucket and written to the specified output bucket. Output data is
 stored
```

```
        in a tar archive compressed in gzip format. The job runs asynchronously,
so you
        can call `describe_topics_detection_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: An Amazon S3 bucket that contains job input.
        :param input_key: The prefix used to find input data in the input
                            bucket. If multiple objects have the same prefix,
all
                            of them are used.
        :param input_format: The format of the input data, either one document
per
                            file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
that
                                     grants Comprehend permission to read from
the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_topics_detection_job(
                JobName=job_name,
                DataAccessRoleArn=data_access_role_arn,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
            )
            logger.info("Started topic modeling job %s.", response["JobId"])
        except ClientError:
            logger.exception("Couldn't start topic modeling job.")
            raise
        else:
            return response


    def describe_job(self, job_id):
        """
        Gets metadata about a topic modeling job.
```

```
        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_topics_detection_job(
                JobId=job_id
            )
            job = response["TopicsDetectionJobProperties"]
            logger.info("Got topic detection job %s.", job_id)
        except ClientError:
            logger.exception("Couldn't get topic detection job %s.", job_id)
            raise
        else:
            return job


    def list_jobs(self):
        """
        Lists topic modeling jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_topics_detection_jobs()
            jobs = response["TopicsDetectionJobPropertiesList"]
            logger.info("Got %s topic detection jobs.", len(jobs))
        except ClientError:
            logger.exception("Couldn't get topic detection jobs.")
            raise
        else:
            return jobs
```

Usar a classe wrapper para executar um trabalho de modelagem de tópico e obter dados dela.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend topic modeling demo!")
    print("-" * 88)
```

```
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    input_prefix = "input/"
    output_prefix = "output/"
    demo_resources = ComprehendDemoResources(
        boto3.resource("s3"), boto3.resource("iam")
    )
    topic_modeler = ComprehendTopicModeler(boto3.client("comprehend"))

    print("Setting up storage and security resources needed for the demo.")
    demo_resources.setup("comprehend-topic-modeler-demo")
    print("Copying sample data from public bucket into input bucket.")
    demo_resources.bucket.copy(
        {"Bucket": "public-sample-us-west-2", "Key": "TopicModeling/Sample.txt"},
        f"{input_prefix}sample.txt",
    )

    print("Starting topic modeling job on sample data.")
    job_info = topic_modeler.start_job(
        "demo-topic-modeling-job",
        demo_resources.bucket.name,
        input_prefix,
        JobInputFormat.per_line,
        demo_resources.bucket.name,
        output_prefix,
        demo_resources.data_access_role.arn,
    )

    print(
        f"Waiting for job {job_info['JobId']} to complete. This typically takes "
        f"20 - 30 minutes."
    )
    job_waiter = JobCompleteWaiter(topic_modeler.comprehend_client)
    job_waiter.wait(job_info["JobId"])

    job = topic_modeler.describe_job(job_info["JobId"])
    print(f"Job {job['JobId']} complete:")
    pprint(job)

    print(
        f"Getting job output data from the output Amazon S3 bucket: "
        f"{job['OutputDataConfig']['S3Uri']}."
    )
    job_output = demo_resources.extract_job_output(job)
```

```
    lines = 10
    print(f"First {lines} lines of document topics output:")
    pprint(job_output["doc-topics.csv"]["data"][:lines])
    print(f"First {lines} lines of terms output:")
    pprint(job_output["topic-terms.csv"]["data"][:lines])

    print("Cleaning up resources created for the demo.")
    demo_resources.cleanup()

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DescribeTopicsDetectionJob
  - ListTopicsDetectionJobs
  - StartTopicsDetectionJob

Treine um classificador Amazon Comprehend personalizado e classifique documentos usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Criar um classificador de múltiplos rótulos do Amazon Comprehend.
- Treinar o classificador em dados de amostra.
- Executar um trabalho de classificação em um segundo conjunto de dados.
- Extrair dados de saída da tarefa do Amazon S3.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe wrapper para chamar as ações do classificador de documento Amazon Comprehend.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def create(
        self,
        name,
        language_code,
        training_bucket,
        training_key,
        data_access_role_arn,
        mode,
    ):
        """
        Creates a custom classifier. After the classifier is created, it
 immediately
        starts training on the data found in the specified Amazon S3 bucket.
 Training
        can take 30 minutes or longer. The `describe_document_classifier`
 function
        can be used to get training status and returns a status of TRAINED when
 the
```

```
        classifier is ready to use.

        :param name: The name of the classifier.
        :param language_code: The language the classifier can operate on.
        :param training_bucket: The Amazon S3 bucket that contains the training
 data.
        :param training_key: The prefix used to find training data in the
 training
                             bucket. If multiple objects have the same prefix,
 all
                             of them are used.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
 that
                                     grants Comprehend permission to read from
 the
                                     training bucket.
        :return: The ARN of the newly created classifier.
        """
        try:
            response = self.comprehend_client.create_document_classifier(
                DocumentClassifierName=name,
                LanguageCode=language_code,
                InputDataConfig={"S3Uri": f"s3://{training_bucket}/
{training_key}"},
                DataAccessRoleArn=data_access_role_arn,
                Mode=mode.value,
            )
            self.classifier_arn = response["DocumentClassifierArn"]
            logger.info("Started classifier creation. Arn is: %s.",
 self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't create classifier %s.", name)
            raise
        else:
            return self.classifier_arn


    def describe(self, classifier_arn=None):
        """
        Gets metadata about a custom classifier, including its current status.

        :param classifier_arn: The ARN of the classifier to look up.
        :return: Metadata about the classifier.
        """
```

```
        if classifier_arn is not None:
            self.classifier_arn = classifier_arn
        try:
            response = self.comprehend_client.describe_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            classifier = response["DocumentClassifierProperties"]
            logger.info("Got classifier %s.", self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't get classifier %s.", self.classifier_arn)
            raise
        else:
            return classifier


    def list(self):
        """
        Lists custom classifiers for the current account.

        :return: The list of classifiers.
        """
        try:
            response = self.comprehend_client.list_document_classifiers()
            classifiers = response["DocumentClassifierPropertiesList"]
            logger.info("Got %s classifiers.", len(classifiers))
        except ClientError:
            logger.exception(
                "Couldn't get classifiers.",
            )
            raise
        else:
            return classifiers


    def delete(self):
        """
        Deletes the classifier.
        """
        try:
            self.comprehend_client.delete_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            logger.info("Deleted classifier %s.", self.classifier_arn)
            self.classifier_arn = None
```

```
        except ClientError:
            logger.exception("Couldn't deleted classifier %s.",
self.classifier_arn)
            raise


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a classification job. The classifier must be trained or the job
        will fail. Input is read from the specified Amazon S3 input bucket and
        written to the specified output bucket. Output data is stored in a tar
        archive compressed in gzip format. The job runs asynchronously, so you
can
        call `describe_document_classification_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: The Amazon S3 bucket that contains input data.
        :param input_key: The prefix used to find input data in the input
                          bucket. If multiple objects have the same prefix, all
                          of them are used.
        :param input_format: The format of the input data, either one document
per
                             file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role
that
                                     grants Comprehend permission to read from
the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_document_classification_job(
```

```
                DocumentClassifierArn=self.classifier_arn,
                JobName=job_name,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
                DataAccessRoleArn=data_access_role_arn,
            )
            logger.info(
                "Document classification job %s is %s.", job_name,
response["JobStatus"]
            )
        except ClientError:
            logger.exception("Couldn't start classification job %s.", job_name)
            raise
        else:
            return response


    def describe_job(self, job_id):
        """
        Gets metadata about a classification job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response =
self.comprehend_client.describe_document_classification_job(
                JobId=job_id
            )
            job = response["DocumentClassificationJobProperties"]
            logger.info("Got classification job %s.", job["JobName"])
        except ClientError:
            logger.exception("Couldn't get classification job %s.", job_id)
            raise
        else:
            return job


    def list_jobs(self):
        """
        Lists the classification jobs for the current account.
```

```
        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_document_classification_jobs()
            jobs = response["DocumentClassificationJobPropertiesList"]
            logger.info("Got %s document classification jobs.", len(jobs))
        except ClientError:
            logger.exception(
                "Couldn't get document classification jobs.",
            )
            raise
        else:
            return jobs
```

Criar uma classe que execute o cenário.

```
class ClassifierDemo:
    """
    Encapsulates functions used to run the demonstration.
    """

    def __init__(self, demo_resources):
        """
        :param demo_resources: A ComprehendDemoResources class that manages
 resources
                               for the demonstration.
        """
        self.demo_resources = demo_resources
        self.training_prefix = "training/"
        self.input_prefix = "input/"
        self.input_format = JobInputFormat.per_line
        self.output_prefix = "output/"

    def setup(self):
        """Creates AWS resources used by the demo."""
        self.demo_resources.setup("comprehend-classifier-demo")

    def cleanup(self):
        """Deletes AWS resources used by the demo."""
```

```
        self.demo_resources.cleanup()

    @staticmethod
    def _sanitize_text(text):
        """Removes characters that cause errors for the document parser."""
        return text.replace("\r", " ").replace("\n", " ").replace(",", ";")

    @staticmethod
    def _get_issues(query, issue_count):
        """
        Gets issues from GitHub using the specified query parameters.

        :param query: The query string used to request issues from the GitHub
 API.
        :param issue_count: The number of issues to retrieve.
        :return: The list of issues retrieved from GitHub.
        """
        issues = []
        logger.info("Requesting issues from %s?%s.", GITHUB_SEARCH_URL, query)
        response = requests.get(f"{GITHUB_SEARCH_URL}?
{query}&per_page={issue_count}")
        if response.status_code == 200:
            issue_page = response.json()["items"]
            logger.info("Got %s issues.", len(issue_page))
            issues = [
                {
                    "title": ClassifierDemo._sanitize_text(issue["title"]),
                    "body": ClassifierDemo._sanitize_text(issue["body"]),
                    "labels": {label["name"] for label in issue["labels"]},
                }
                for issue in issue_page
            ]
        else:
            logger.error(
                "GitHub returned error code %s with message %s.",
                response.status_code,
                response.json(),
            )
        logger.info("Found %s issues.", len(issues))
        return issues

    def get_training_issues(self, training_labels):
        """
        Gets issues used for training the custom classifier. Training issues are
```

```
        closed issues from the Boto3 repo that have known labels. Comprehend
        requires a minimum of ten training issues per label.

        :param training_labels: The issue labels to use for training.
        :return: The set of issues used for training.
        """
        issues = []
        per_label_count = 15
        for label in training_labels:
            issues += self._get_issues(
                f"q=type:issue+repo:boto/boto3+state:closed+label:{label}",
                per_label_count,
            )
            for issue in issues:
                issue["labels"] = issue["labels"].intersection(training_labels)
        return issues

    def get_input_issues(self, training_labels):
        """
        Gets input issues from GitHub. For demonstration purposes, input issues
        are open issues from the Boto3 repo with known labels, though in practice
        any issue could be submitted to the classifier for labeling.

        :param training_labels: The set of labels to query for.
        :return: The set of issues used for input.
        """
        issues = []
        per_label_count = 5
        for label in training_labels:
            issues += self._get_issues(
                f"q=type:issue+repo:boto/boto3+state:open+label:{label}",
                per_label_count,
            )
        return issues

    def upload_issue_data(self, issues, training=False):
        """
        Uploads issue data to an Amazon S3 bucket, either for training or for
input.
        The data is first put into the format expected by Comprehend. For
training,
        the set of pipe-delimited labels is prepended to each document. For
        input, labels are not sent.
```

```
        :param issues: The set of issues to upload to Amazon S3.
        :param training: Indicates whether the issue data is used for training or
                         input.
        """
        try:
            obj_key = (
                self.training_prefix if training else self.input_prefix
            ) + "issues.txt"
            if training:
                issue_strings = [
                    f"{'|'.join(issue['labels'])},{issue['title']}
{issue['body']}"
                    for issue in issues
                ]
            else:
                issue_strings = [
                    f"{issue['title']} {issue['body']}" for issue in issues
                ]
            issue_bytes = BytesIO("\n".join(issue_strings).encode("utf-8"))
            self.demo_resources.bucket.upload_fileobj(issue_bytes, obj_key)
            logger.info(
                "Uploaded data as %s to bucket %s.",
                obj_key,
                self.demo_resources.bucket.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload data to bucket %s.",
self.demo_resources.bucket.name
            )
            raise

    def extract_job_output(self, job):
        """Extracts job output from Amazon S3."""
        return self.demo_resources.extract_job_output(job)

    @staticmethod
    def reconcile_job_output(input_issues, output_dict):
        """
        Reconciles job output with the list of input issues. Because the input
issues
        have known labels, these can be compared with the labels added by the
        classifier to judge the accuracy of the output.
```

```
        :param input_issues: The list of issues used as input.
        :param output_dict: The dictionary of data that is output by the
 classifier.
        :return: The list of reconciled input and output data.
        """
        reconciled = []
        for archive in output_dict.values():
            for line in archive["data"]:
                in_line = int(line["Line"])
                in_labels = input_issues[in_line]["labels"]
                out_labels = {
                    label["Name"]
                    for label in line["Labels"]
                    if float(label["Score"]) > 0.3
                }
                reconciled.append(
                    f"{line['File']}, line {in_line} has labels {in_labels}.\n"
                    f"\tClassifier assigned {out_labels}."
                )
        logger.info("Reconciled input and output labels.")
        return reconciled
```

Treine um classificador em um conjunto de GitHub problemas com rótulos conhecidos e, em seguida, envie um segundo conjunto de GitHub problemas ao classificador para que eles possam ser rotulados.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend custom document classifier demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    comp_demo = ClassifierDemo(
        ComprehendDemoResources(boto3.resource("s3"), boto3.resource("iam"))
    )
    comp_classifier = ComprehendClassifier(boto3.client("comprehend"))
    classifier_trained_waiter = ClassifierTrainedWaiter(
        comp_classifier.comprehend_client
    )
```

```
    training_labels = {"bug", "feature-request", "dynamodb", "s3"}

    print("Setting up storage and security resources needed for the demo.")
    comp_demo.setup()

    print("Getting training data from GitHub and uploading it to Amazon S3.")
    training_issues = comp_demo.get_training_issues(training_labels)
    comp_demo.upload_issue_data(training_issues, True)

    classifier_name = "doc-example-classifier"
    print(f"Creating document classifier {classifier_name}.")
    comp_classifier.create(
        classifier_name,
        "en",
        comp_demo.demo_resources.bucket.name,
        comp_demo.training_prefix,
        comp_demo.demo_resources.data_access_role.arn,
        ClassifierMode.multi_label,
    )
    print(
        f"Waiting until {classifier_name} is trained. This typically takes "
        f"30-40 minutes."
    )
    classifier_trained_waiter.wait(comp_classifier.classifier_arn)

    print(f"Classifier {classifier_name} is trained:")
    pprint(comp_classifier.describe())

    print("Getting input data from GitHub and uploading it to Amazon S3.")
    input_issues = comp_demo.get_input_issues(training_labels)
    comp_demo.upload_issue_data(input_issues)

    print("Starting classification job on input data.")
    job_info = comp_classifier.start_job(
        "issue_classification_job",
        comp_demo.demo_resources.bucket.name,
        comp_demo.input_prefix,
        comp_demo.input_format,
        comp_demo.demo_resources.bucket.name,
        comp_demo.output_prefix,
        comp_demo.demo_resources.data_access_role.arn,
    )
    print(f"Waiting for job {job_info['JobId']} to complete.")
    job_waiter = JobCompleteWaiter(comp_classifier.comprehend_client)
```

```
    job_waiter.wait(job_info["JobId"])

    job = comp_classifier.describe_job(job_info["JobId"])
    print(f"Job {job['JobId']} complete:")
    pprint(job)

    print(
        f"Getting job output data from Amazon S3: "
        f"{job['OutputDataConfig']['S3Uri']}."
    )
    job_output = comp_demo.extract_job_output(job)
    print("Job output:")
    pprint(job_output)

    print("Reconciling job output with labels from GitHub:")
    reconciled_output = comp_demo.reconcile_job_output(input_issues, job_output)
    print(*reconciled_output, sep="\n")

    answer = input(f"Do you want to delete the classifier {classifier_name} (y/
n)? ")
    if answer.lower() == "y":
        print(f"Deleting {classifier_name}.")
        comp_classifier.delete()

    print("Cleaning up resources created for the demo.")
    comp_demo.cleanup()

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDocumentClassifier
  - DeleteDocumentClassifier
  - DescribeDocumentClassificationJob
  - DescribeDocumentClassifier
  - ListDocumentClassificationJobs
  - ListDocumentClassifiers

- StartDocumentClassificationJob

Exemplos entre serviços do Amazon Comprehend usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Comprehend com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de transmissão do Amazon Transcribe
- Crie um chatbot do Amazon Lex para engajar os visitantes do seu site
- Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
- Detectar entidades em texto extraído de uma imagem usando um AWS SDK

Criar uma aplicação de transmissão do Amazon Transcribe

O exemplo de código a seguir mostra como construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Transcribe para construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SES
- Amazon Transcribe

- Amazon Translate

Crie um chatbot do Amazon Lex para engajar os visitantes do seu site

Os exemplos de código a seguir mostram como criar um chatbot para engajar os visitantes do seu site.

Java

SDK para Java 2.x

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, consulte o exemplo completo Construir um chatbot Amazon Lex no guia do desenvolvedor de AWS SDK for JavaScript.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS

Os exemplos de código a seguir mostram como criar uma aplicação de mensagens usando o Amazon SQS.

Java

SDK para Java 2.x

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Kotlin

SDK for Kotlin

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Os exemplos de código a seguir mostram como criar uma aplicação que analisa os cartões de comentários dos clientes, os traduz do idioma original, determina seus sentimentos e gera um arquivo de áudio do texto traduzido.

.NET

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Java

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.

- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";

/**
```

```
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );

  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);

  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";

/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
 */
```

```
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
    VoiceId: "Ruth",
```

```
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});

  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });
```

```
  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Ruby

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract

- Amazon Translate

Detectar entidades em texto extraído de uma imagem usando um AWS SDK

O exemplo de código a seguir mostra como usar o Amazon Comprehend para detectar entidades em texto extraído pelo Amazon Textract de uma imagem armazenada no Amazon S3.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) em um bloco de anotações Jupyter para detectar entidades em texto extraído de uma imagem. Este exemplo usa o Amazon Textract para extrair texto de uma imagem armazenada no Amazon Simple Storage Service (Amazon S3) e no Amazon Comprehend para detectar entidades no texto extraído.

Este exemplo é um bloco de anotações Jupyter e deve ser executado em um ambiente que possa hospedar blocos de anotações. Para obter instruções sobre como executar o exemplo usando a Amazon SageMaker, consulte as instruções em TextractAndComprehendNotebook.ipynb.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon S3
- Amazon Textract

Exemplos de código para o AWS Config usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Config com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do AWS Config – Mais informações sobre o AWS Config.
- Referência da API do AWS Config – Detalhes sobre todas as ações disponíveis do AWS Config.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o AWS Config usando AWS SDKs
  - Excluir uma regra do AWS Config usando um AWS SDK
  - Descrever casos do AWS Config usando um AWS SDK
  - Insira uma regra do AWS Config usando um AWS SDK

Ações para o AWS Config usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Config com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Excluir uma regra do AWS Config usando um AWS SDK
- Descrever casos do AWS Config usando um AWS SDK
- Insira uma regra do AWS Config usando um AWS SDK

Excluir uma regra do AWS Config usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma regra do AWS Config.

CLI

AWS CLI

Como excluir uma regra do AWS Config

O seguinte comando exclui uma regra do AWS Config chamada `MyConfigRule`:

```
aws configservice delete-config-rule --config-rule-name MyConfigRule
```

- Para obter detalhes da API, consulte DeleteConfigRuleem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def delete_config_rule(self, rule_name):
        """
        Delete the specified rule.

        :param rule_name: The name of the rule to delete.
        """
        try:
            self.config_client.delete_config_rule(ConfigRuleName=rule_name)
            logger.info("Deleted rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't delete rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteConfigRuleReferência da API AWSSDK for Python (Boto3).

Descrever casos do AWS Config usando um AWS SDK

Os exemplos de código a seguir mostram como descrever as regras do AWS Config.

CLI

AWS CLI

Como obter detalhes de uma regra do AWS Config

O seguinte comando retorna detalhes de uma regra do AWS Config chamada `InstanceTypesAreT2micro`:

```
aws configservice describe-config-rules --config-rule-names
 InstanceTypesAreT2micro
```

Saída:

```
{
    "ConfigRules": [
        {
            "ConfigRuleState": "ACTIVE",
            "Description": "Evaluates whether EC2 instances are the t2.micro
 type.",
            "ConfigRuleName": "InstanceTypesAreT2micro",
            "ConfigRuleArn": "arn:aws:config:us-east-1:123456789012:config-rule/
config-rule-abcdef",
            "Source": {
                "Owner": "CUSTOM_LAMBDA",
                "SourceIdentifier": "arn:aws:lambda:us-
east-1:123456789012:function:InstanceTypeCheck",
                "SourceDetails": [
                    {
                        "EventSource": "aws.config",
                        "MessageType": "ConfigurationItemChangeNotification"
                    }
                ]
```

```
            },
            "InputParameters": "{\"desiredInstanceType\":\"t2.micro\"}",
            "Scope": {
                "ComplianceResourceTypes": [
                    "AWS::EC2::Instance"
                ]
            },
            "ConfigRuleId": "config-rule-abcdef"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeConfigRulesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def describe_config_rule(self, rule_name):
        """
        Gets data for the specified rule.
```

```
        :param rule_name: The name of the rule to retrieve.
        :return: The rule data.
        """
        try:
            response = self.config_client.describe_config_rules(
                ConfigRuleNames=[rule_name]
            )
            rule = response["ConfigRules"]
            logger.info("Got data for rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't get data for rule %s.", rule_name)
            raise
        else:
            return rule
```

- Para obter detalhes da API, consulte a DescribeConfigRulesReferência da API AWSSDK for Python (Boto3).

Insira uma regra do AWS Config usando um AWS SDK

Os exemplos de código a seguir mostram como inserir uma regra do AWS Config.

CLI

AWS CLI

Como adicionar uma regra gerenciada do AWS Config

O seguinte comando fornece o código JSON para adicionar uma regra gerenciada do AWS Config:

```
aws configservice put-config-rule --config-rule file://
RequiredTagsForEC2Instances.json
```

`RequiredTagsForEC2Instances.json` é um arquivo JSON que contém a configuração da regra:

```
{
  "ConfigRuleName": "RequiredTagsForEC2Instances",
```

```
  "Description": "Checks whether the CostCenter and Owner tags are applied to EC2
 instances.",
  "Scope": {
    "ComplianceResourceTypes": [
      "AWS::EC2::Instance"
    ]
  },
  "Source": {
    "Owner": "AWS",
    "SourceIdentifier": "REQUIRED_TAGS"
  },
  "InputParameters": "{\"tag1Key\":\"CostCenter\",\"tag2Key\":\"Owner\"}"
}
```

Esse código JSON limita o escopo do atributo `ComplianceResourceTypes` aos recursos do tipo `AWS::EC2::Instance`. Desta forma, o AWS Config avaliará somente instâncias do EC2 em relação à regra. Como a regra é uma regra gerenciada, o atributo `Owner` é definido como `AWS` e o atributo `SourceIdentifier` é definido como o identificador da regra, `REQUIRED_TAGS`. Para o atributo `InputParameters`, as chaves de tag exigidas pela regra, `CostCenter` e `Owner` são especificados.

Se o comando for bem-sucedido, o AWS Config não retornará nenhuma saída. Para verificar a configuração da regra, execute o describe-config-rules comando e especifique o nome da regra.

Como adicionar uma regra do Config gerenciada pelo cliente

O seguinte comando fornece o código JSON para adicionar uma regra do Config gerenciada pelo cliente:

```
aws configservice put-config-rule --config-rule file://
InstanceTypesAreT2micro.json
```

`InstanceTypesAreT2micro.json` é um arquivo JSON que contém a configuração da regra:

```
{
  "ConfigRuleName": "InstanceTypesAreT2micro",
  "Description": "Evaluates whether EC2 instances are the t2.micro type.",
  "Scope": {
    "ComplianceResourceTypes": [
      "AWS::EC2::Instance"
```

```
    ]
  },
  "Source": {
    "Owner": "CUSTOM_LAMBDA",
    "SourceIdentifier": "arn:aws:lambda:us-
east-1:123456789012:function:InstanceTypeCheck",
    "SourceDetails": [
      {
        "EventSource": "aws.config",
        "MessageType": "ConfigurationItemChangeNotification"
      }
    ]
  },
  "InputParameters": "{\"desiredInstanceType\":\"t2.micro\"}"
}
```

Esse código JSON limita o escopo do atributo `ComplianceResourceTypes` aos recursos do tipo `AWS::EC2::Instance`. Desta forma, o AWS Config avaliará somente instâncias do EC2 em relação à regra. Como essa é uma regra gerenciada pelo cliente, o atributo `Owner` é definido como `CUSTOM_LAMBDA` e o atributo `SourceIdentifier` é definido como o ARN da função do AWS Lambda. O `SourceDetails` objeto é obrigatório. Os parâmetros especificados para o atributo `InputParameters` são passados para a função do AWS Lambda quando o AWS Config o invoca para avaliar os recursos em relação à regra.

Se o comando for bem-sucedido, o AWS Config não retornará nenhuma saída. Para verificar a configuração da regra, execute o describe-config-rules comando e especifique o nome da regra.

- Para obter detalhes da API, consulte PutConfigRuleem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
```

```
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def put_config_rule(self, rule_name):
        """
        Sets a configuration rule that prohibits making Amazon S3 buckets
publicly
        readable.

        :param rule_name: The name to give the rule.
        """
        try:
            self.config_client.put_config_rule(
                ConfigRule={
                    "ConfigRuleName": rule_name,
                    "Description": "S3 Public Read Prohibited Bucket Rule",
                    "Scope": {
                        "ComplianceResourceTypes": [
                            "AWS::S3::Bucket",
                        ],
                    },
                    "Source": {
                        "Owner": "AWS",
                        "SourceIdentifier": "S3_BUCKET_PUBLIC_READ_PROHIBITED",
                    },
                    "InputParameters": "{}",
                    "ConfigRuleState": "ACTIVE",
                }
            )
            logger.info("Created configuration rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't create configuration rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a PutConfigRuleReferência da API AWSSDK for Python (Boto3).

Exemplos de código para Device Farm usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Device Farm com um kit de desenvolvimento de software (SDK) da AWS.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Device Farm — Mais informações sobre o Device Farm.
- Referência da API Device Farm — Detalhes sobre todas as ações disponíveis do Device Farm.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Cenários para Device Farm usando SDKs da AWS
  - Execute testes de navegador com o Device Farm e faça capturas de tela usando um SDK da AWS
  - Faça upload e teste pacotes de dispositivos móveis com o Device Farm usando um SDK da AWS

Cenários para Device Farm usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Device Farm com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Execute testes de navegador com o Device Farm e faça capturas de tela usando um SDK da AWS
- Faça upload e teste pacotes de dispositivos móveis com o Device Farm usando um SDK da AWS

Execute testes de navegador com o Device Farm e faça capturas de tela usando um SDK da AWS

O exemplo de código a seguir mostra como executar testes de navegador com o Device Farm e fazer capturas de tela.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use o PyTest Selenium para navegar até sites específicos, fazer capturas de tela e comparar o conteúdo real do site com o conteúdo esperado.

```
import datetime
import os
import subprocess
import boto3
import pytest
from selenium import webdriver
from selenium.webdriver import DesiredCapabilities
from selenium.webdriver.common.by import By
from selenium.webdriver.common.keys import Keys
from selenium.webdriver.support import expected_conditions
from selenium.webdriver.support.wait import WebDriverWait


def get_git_hash():
    """
    Get the short Git hash of the current commit of the repository
    """
    try:
        return (
```

```
            subprocess.check_output(["git", "rev-parse", "--short", "HEAD"])
            .decode("utf-8")
            .strip()
        )
    except:
        return "norepo"


class TestHelloSuite:
    """
    Our test suite.

    This style of test suite allows us to use setup_method and teardown_method.

    """

    def save_screenshot(self, name):
        self.driver.save_screenshot(os.path.join(self.screenshot_path, name))

    def setup_method(self, method):
        """
        Set up a test.

        This makes sure that the session for an individual test is ready.

        The AWS credentials are read from the default ~/.aws/credentials or from
 the
        command line by setting the AWS_ACCESS_KEY_ID and AWS_SECRET_KEY
 environment
        variables.

        The project Amazon Resource Name (ARN) is determined by the PROJECT_ARN
        environment variable.
        """
        devicefarm_client = boto3.client("devicefarm")
        project_arn = os.environ.get("PROJECT_ARN", None)
        if project_arn is None:
            raise ValueError("Must set PROJECT_ARN")
        # Request a driver hub URL for the Selenium client
        testgrid_url_response = devicefarm_client.create_test_grid_url(
            projectArn=project_arn, expiresInSeconds=300
        )
```

```
        # We want a directory to save our files into. We're going to make a
 directory
        # in the current directory that holds our results.
        self.screenshot_path = os.path.join(
            ".", "results", get_git_hash() + "-" +
 (datetime.date.today().isoformat())
        )
        if not os.path.exists(self.screenshot_path):
            os.makedirs(self.screenshot_path, exist_ok=True)

        # We want a Firefox instance on Windows
        desired_cap = DesiredCapabilities.FIREFOX
        desired_cap["platform"] = "windows"
        desired_cap["BrowserVersion"] = "latest"

        # Configure the webdriver with the appropriate remote endpoint.
        self.driver = webdriver.Remote(testgrid_url_response["url"], desired_cap)

        #
        # Auto-Tagging
        #

        # In order to get the Session ARN, we need to look up the session by the
        # Project ARN and session ID (from the driver).
        testgrid_session_arn_response = devicefarm_client.get_test_grid_session(
            projectArn=project_arn, sessionId=self.driver.session_id
        )

        # Save the session's ARN so we can tag the session.
        self.session_arn = testgrid_session_arn_response["testGridSession"]
["arn"]

        # In order to tag it, we're going to use the resourcegroupstaggingapi
 client to
        # add a tag to the session ARN that we just got.
        tag_client = boto3.client("resourcegroupstaggingapi")
        tag_client.tag_resources(
            ResourceARNList=[self.session_arn],
            Tags={"TestSuite": f"testsuite {method.__name__}", "GitId":
 get_git_hash()},
        )

    def teardown_method(self, method):
        """
```

```
        Clean up resources used by each method.
        """
        # End the Selenium session so we're off the clock.
        self.driver.quit()

    @pytest.mark.parametrize(
        "query,leading",
        [
            pytest.param(
                "Seattle",
                "Seattle (/si#ætəl/ (listen) see-AT-əl) is a seaport city on the
West Coast of the United States.",
            ),
            pytest.param(
                "Selenium",
                "Selenium is a chemical element with the symbol Se and atomic
number 34.",
            ),
            pytest.param(
                "Amazon Locker",
                "Amazon Locker is a self-service package delivery service offered
by online retailer Amazon.",
            ),
            pytest.param(
                "Kootenai Falls",
                "Kootenai Falls is a waterfall on the Kootenay River located in
Lincoln County, Montana, just off U.S. Route 2.",
            ),
            pytest.param(
                "Dorayaki",
                "Dorayaki (####, ####, ####, ####) is a type of Japanese
confection.",
            ),
            pytest.param("Robot Face", "<|°_°|> (also known as Robot Face or
Robot)"),
        ],
    )
    def test_first_paragraph_text(self, query, leading):
        """
        This test looks at the first paragraph of a page on Wikipedia, comparing
it to
        a known leading sentence.
```

```
        If the leading sentence matches, the test passes. A screenshot is taken
before
        the final assertion is made, letting us debug if something isn't right.
        """
        # Open the main page of Wikipedia
        self.driver.get("https://en.wikipedia.org/wiki/Main_Page")
        # Find the search box, enter a query, and press enter
        search_input = self.driver.find_element(By.ID, "searchInput")
        search_input.click()
        search_input.send_keys(query)
        search_input.send_keys(Keys.ENTER)
        # Wait for the search box to go stale -- This means we've navigated
fully.
        WebDriverWait(self.driver, 5).until(
            expected_conditions.staleness_of(search_input)
        )
        # Get the leading paragraph of the article.
        lead = leading.lower()
        # Find the element...
        lead_para = self.driver.find_element(
            By.XPATH, "//div[@class='mw-parser-output']//p[not(@class)]"
        )
        # ... and copy out its text.
        our_text = lead_para.text.lower()
        our_text = our_text[: len(lead)]
        # Take a screenshot and compare the strings.
        self.save_screenshot(f"leadingpara_{query}.png")
        assert our_text.startswith(lead)

    @pytest.mark.parametrize(
        "query,expected",
        [
            pytest.param("Automation Testing", "Test Automation"),
            pytest.param("DevOps", "DevOps"),
            pytest.param("Jackdaws Love My Big Sphinx Of Quartz", "Pangram"),
            pytest.param("EarthBound", "EarthBound"),
            pytest.param("Covered Bridges Today", "Covered Bridges Today"),
            pytest.param("Kurt Godel", "Kurt Gödel"),
            pytest.param("N//ng language", "N#ng language"),
            pytest.param(
                "Who the Frick Is Jackson Pollock?", "Who the $&% Is Jackson
Pollock?"
            ),
        ],
```

```
    )
    def test_redirect_titles(self, query, expected):
        """
        A test comparing pages we expect to (or not to) redirect on Wikipedia.

        This test checks to see that the page ("query") redirects (or doesn't) to
the
        "expected" page title. Several of these are common synonyms
("Jackdaws...")
        while others are because of characters untypable by most keyboards ("N#ng
language")

        A screenshot is taken just before the final assertion is made to aid in
        debugging and verification.
        """
        # Open the main page of Wikipedia
        self.driver.get("https://en.wikipedia.org/wiki/Main_Page")
        # Find the search box, enter some text into it, and send an enter key.
        search_input = self.driver.find_element(By.ID, "searchInput")
        search_input.click()
        search_input.send_keys(query)
        search_input.send_keys(Keys.ENTER)
        # wait until the page has rolled over -- once the search input handle is
stale,
        # the browser has navigated.
        WebDriverWait(self.driver, 5).until(
            expected_conditions.staleness_of(search_input)
        )
        # Get the first heading & take a screenshot
        our_text = self.driver.find_element(By.ID, "firstHeading").text.lower()
        self.save_screenshot(f"redirect_{query}.png")
        # did it match?
        assert our_text == expected.lower()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTestGridUrl
  - GetTestGridSession

Faça upload e teste pacotes de dispositivos móveis com o Device Farm usando um SDK da AWS

O exemplo de código a seguir mostra como fazer upload e testar pacotes de dispositivos móveis com o Device Farm.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Fazer upload de aplicativos Android compilados e pacotes de teste para o Device Farm, iniciar um teste, aguardar a conclusão do teste e relatar os resultados.

```
import boto3
import os
import requests
import string
import random
import datetime
import time

# Update this dict with your own values before you run the example:
config = {
    # This is our app under test.
    "appFilePath": "app-debug.apk",
    "projectArn": "arn:aws:devicefarm:us-west-2:111222333444:project:581f5703-
e040-4ac9-b7ae-0ba007bfb8e6",
    # Since we care about the most popular devices, we'll use a curated pool.
    "testSpecArn": "arn:aws:devicefarm:us-west-2::upload:20fcf771-eae3-4137-
aa76-92e17fb3131b",
    "poolArn": "arn:aws:devicefarm:us-
west-2::devicepool:4a869d91-6f17-491f-9a95-0a601aee2406",
    "namePrefix": "MyAppTest",
    # This is our test package. This tutorial won't go into how to make these.
    "testPackage": "tests.zip",
}
```

```
client = boto3.client("devicefarm")

unique = (
    config["namePrefix"]
    + "-"
    + (datetime.date.today().isoformat())
    + ("".join(random.sample(string.ascii_letters, 8)))
)

print(
    f"The unique identifier for this run is '{unique}'. All uploads will be
 prefixed "
    f"with this."
)


def upload_df_file(filename, type_, mime="application/octet-stream"):
    upload_response = client.create_upload(
        projectArn=config["projectArn"],
        name=unique + "_" + os.path.basename(filename),
        type=type_,
        contentType=mime,
    )
    upload_arn = upload_response["upload"]["arn"]
    # Extract the URL of the upload and use Requests to upload it.
    upload_url = upload_response["upload"]["url"]
    with open(filename, "rb") as file_stream:
        print(
            f"Uploading {filename} to Device Farm as "
            f"{upload_response['upload']['name']}... ",
            end="",
        )
        put_req = requests.put(
            upload_url, data=file_stream, headers={"content-type": mime}
        )
        print(" done")
        if not put_req.ok:
            raise Exception(f"Couldn't upload. Requests says: {put_req.reason}")
    started = datetime.datetime.now()
    while True:
        print(
            f"Upload of {filename} in state {upload_response['upload']['status']}
 "
```

```
            f"after " + str(datetime.datetime.now() - started)
        )
        if upload_response["upload"]["status"] == "FAILED":
            raise Exception(
                f"The upload failed processing. Device Farm says the reason is:
 \n"
                f"{+upload_response['upload']['message']}"
            )
        if upload_response["upload"]["status"] == "SUCCEEDED":
            break
        time.sleep(5)
        upload_response = client.get_upload(arn=upload_arn)
    print("")
    return upload_arn


our_upload_arn = upload_df_file(config["appFilePath"], "ANDROID_APP")
our_test_package_arn = upload_df_file(
    config["testPackage"], "APPIUM_PYTHON_TEST_PACKAGE"
)
print(our_upload_arn, our_test_package_arn)

response = client.schedule_run(
    projectArn=config["projectArn"],
    appArn=our_upload_arn,
    devicePoolArn=config["poolArn"],
    name=unique,
    test={
        "type": "APPIUM_PYTHON",
        "testSpecArn": config["testSpecArn"],
        "testPackageArn": our_test_package_arn,
    },
)
run_arn = response["run"]["arn"]
start_time = datetime.datetime.now()
print(f"Run {unique} is scheduled as arn {run_arn} ")

state = "UNKNOWN"
try:
    while True:
        response = client.get_run(arn=run_arn)
        state = response["run"]["status"]
        if state == "COMPLETED" or state == "ERRORED":
            break
```

```
        else:
            print(
                f" Run {unique} in state {state}, total "
                f"time {datetime.datetime.now() - start_time}"
            )
            time.sleep(10)
except:
    client.stop_run(arn=run_arn)
    exit(1)

print(f"Tests finished in state {state} after {datetime.datetime.now() -
 start_time}")
# Pull all the logs.
jobs_response = client.list_jobs(arn=run_arn)
# Save the output somewhere, using the unique value.
save_path = os.path.join(os.getcwd(), "results", unique)
os.mkdir(save_path)
# Save the last run information.
for job in jobs_response["jobs"]:
    job_name = job["name"]
    os.makedirs(os.path.join(save_path, job_name), exist_ok=True)
    # Get each suite within the job.
    suites = client.list_suites(arn=job["arn"])["suites"]
    for suite in suites:
        for test in client.list_tests(arn=suite["arn"])["tests"]:
            # Get the artifacts.
            for artifact_type in ["FILE", "SCREENSHOT", "LOG"]:
                artifacts = client.list_artifacts(type=artifact_type,
 arn=test["arn"])[
                    "artifacts"
                ]
                for artifact in artifacts:
                    # Replace `:` because it has a special meaning in Windows &
 macOS.
                    path_to = os.path.join(
                        save_path,
                        job_name,
                        suite["name"],
                        test["name"].replace(":", "_"),
                    )
                    os.makedirs(path_to, exist_ok=True)
                    filename = (
                        artifact["type"]
                        + "_"
```

```
                        + artifact["name"]
                        + "."
                        + artifact["extension"]
                    )
                    artifact_save_path = os.path.join(path_to, filename)
                    print(f"Downloading {artifact_save_path}")
                    with open(artifact_save_path, "wb") as fn:
                        with requests.get(
                            artifact["url"], allow_redirects=True
                        ) as request:
                            fn.write(request.content)
print("Finished")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateUpload
  - GetRun
  - GetUpload
  - ListArtifacts
  - ListJobs
  - ListSuites
  - ListTests
  - ScheduleRun
  - StopRun

Exemplos de código do DynamoDB usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon DynamoDB com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do DynamoDB – Mais informações sobre o DynamoDB.
- Referência da API do DynamoDB – Detalhes sobre todas as ações disponíveis do DynamoDB.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, DynamoDB

O exemplo de código a seguir mostra como começar a usar o DynamoDB.

.NET

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;

namespace DynamoDB_Actions;

public static class HelloDynamoDB
{
    static async Task Main(string[] args)
    {
        var dynamoDbClient = new AmazonDynamoDBClient();
```

```
        Console.WriteLine($"Hello Amazon Dynamo DB! Following are some of your
 tables:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five tables.
        var response = await dynamoDbClient.ListTablesAsync(
            new ListTablesRequest()
            {
                Limit = 5
            });

        foreach (var table in response.TableNames)
        {
            Console.WriteLine($"\tTable: {table}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS dynamodb)
```

```
# Set this project's name.
project("hello_dynamodb")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_dynamodb.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_dynamodb.cpp.

```
#include <aws/core/Aws.h>
```

```
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/ListTablesRequest.h>
#include <iostream>

/*
 *  A "Hello DynamoDB" starter application which initializes an Amazon DynamoDB
 (DynamoDB) client and lists the
 *  DynamoDB tables.
 *
 *  main function
 *
 *  Usage: 'hello_dynamodb'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.

    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::DynamoDB::DynamoDBClient dynamodbClient(clientConfig);
        Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
        listTablesRequest.SetLimit(50);
        do {
            const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamodbClient.ListTables(
                    listTablesRequest);
            if (!outcome.IsSuccess()) {
                std::cout << "Error: " << outcome.GetError().GetMessage() <<
 std::endl;
                result = 1;
                break;
            }

            for (const auto &tableName: outcome.GetResult().GetTableNames()) {
                std::cout << tableName << std::endl;
            }
```

```
            listTablesRequest.SetExclusiveStartTableName(
                    outcome.GetResult().GetLastEvaluatedTableName());

        } while (!listTablesRequest.GetExclusiveStartTableName().empty());
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ListTablesRequest;
import software.amazon.awssdk.services.dynamodb.model.ListTablesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListTables {
```

```
    public static void main(String[] args) {
        System.out.println("Listing your Amazon DynamoDB tables:\n");
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
        listAllTables(ddb);
        ddb.close();
    }

    public static void listAllTables(DynamoDbClient ddb) {
        boolean moreTables = true;
        String lastName = null;

        while (moreTables) {
            try {
                ListTablesResponse response = null;
                if (lastName == null) {
                    ListTablesRequest request =
 ListTablesRequest.builder().build();
                    response = ddb.listTables(request);
                } else {
                    ListTablesRequest request = ListTablesRequest.builder()
                            .exclusiveStartTableName(lastName).build();
                    response = ddb.listTables(request);
                }

                List<String> tableNames = response.tableNames();
                if (tableNames.size() > 0) {
                    for (String curName : tableNames) {
                        System.out.format("* %s\n", curName);
                    }
                } else {
                    System.out.println("No tables found!");
                    System.exit(0);
                }

                lastName = response.lastEvaluatedTableName();
                if (lastName == null) {
                    moreTables = false;
                }

            } catch (DynamoDbException e) {
                System.err.println(e.getMessage());
```

```
                System.exit(1);
            }
        }
        System.out.println("\nDone!");
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListTablesCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new ListTablesCommand({});

  const response = await client.send(command);
  console.log(response.TableNames.join("\n"));
  return response;
};
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

Exemplos de código

- Ações do DynamoDB usando AWS SDKs
  - Criar uma tabela no DynamoDB usando um AWS SDK

- Excluir uma tabela do DynamoDB usando um AWS SDK
- Excluir um item de uma tabela do DynamoDB usando um AWS SDK
- Obter um lote de itens do DynamoDB usando um AWS SDK
- Obter um item de uma tabela do DynamoDB usando um AWS SDK
- Obter informações sobre uma tabela do DynamoDB
- Listar tabelas do DynamoDB usando um AWS SDK
- Colocar um item em uma tabela do DynamoDB usando um AWS SDK
- Consultar uma tabela no DynamoDB usando um AWS SDK
- Executar uma instrução PartiQL em uma tabela do DynamoDB usando um AWSSDK
- Executar lotes de instruções PartiQL em uma tabela do DynamoDB usando um AWS SDK
- Verificar uma tabela no DynamoDB usando um AWS SDK
- Atualizar um item em uma tabela do DynamoDB usando um AWS SDK
- Gravar um lote de itens do DynamoDB usando um AWS SDK

- Cenários do DynamoDB usando AWS SDKs
  - Acelerar as leituras do DynamoDB com o DAX usando um AWS SDK
  - Conceitos básicos de tabelas, itens e consultas do DynamoDB usando um AWS SDK
  - Consultar uma tabela do DynamoDB usando lotes de instruções PartiQL e um AWS SDK
  - Consultar uma tabela do DynamoDB usando o PartiQL e um AWS SDK
  - Usar um modelo de documento para o DynamoDB usando um AWS SDK
  - Usar um modelo de persistência de objetos de alto nível para o DynamoDB usando um AWS SDK
- Exemplos do DynamoDB entre serviços usando AWS SDKs
  - Criar uma aplicação para enviar dados para uma tabela do DynamoDB
  - Criar uma API REST do API Gateway para monitorar dados da COVID-19
  - Criar uma aplicação de mensageiro com o Step Functions
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Criar uma aplicação Web para monitorar dados do DynamoDB
  - Criar uma aplicação de chat websocket com o API Gateway
  - Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
  - Chamar uma função do Lambda em um navegador

- Salvar o EXIF e outras informações de imagem usando um AWS SDK
- Usar o API Gateway para invocar uma função do Lambda
- Usar Step Functions para invocar funções do Lambda
- Usar eventos programados para chamar uma função do Lambda

Ações do DynamoDB usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon DynamoDB com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do DynamoDB usando AWS SDKs.

Exemplos

- Criar uma tabela no DynamoDB usando um AWS SDK
- Excluir uma tabela do DynamoDB usando um AWS SDK
- Excluir um item de uma tabela do DynamoDB usando um AWS SDK
- Obter um lote de itens do DynamoDB usando um AWS SDK
- Obter um item de uma tabela do DynamoDB usando um AWS SDK
- Obter informações sobre uma tabela do DynamoDB
- Listar tabelas do DynamoDB usando um AWS SDK
- Colocar um item em uma tabela do DynamoDB usando um AWS SDK
- Consultar uma tabela no DynamoDB usando um AWS SDK
- Executar uma instrução PartiQL em uma tabela do DynamoDB usando um AWSSDK
- Executar lotes de instruções PartiQL em uma tabela do DynamoDB usando um AWS SDK
- Verificar uma tabela no DynamoDB usando um AWS SDK
- Atualizar um item em uma tabela do DynamoDB usando um AWS SDK
- Gravar um lote de itens do DynamoDB usando um AWS SDK

Criar uma tabela no DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX
- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Creates a new Amazon DynamoDB table and then waits for the new
        /// table to become active.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="tableName">The name of the table to create.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
 client, string tableName)
        {
            var response = await client.CreateTableAsync(new CreateTableRequest
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                {
                    new AttributeDefinition
                    {
                        AttributeName = "title",
                        AttributeType = ScalarAttributeType.S,
                    },
                    new AttributeDefinition
                    {
```

```
                        AttributeName = "year",
                        AttributeType = ScalarAttributeType.N,
                    },
                },
                KeySchema = new List<KeySchemaElement>()
                {
                    new KeySchemaElement
                    {
                        AttributeName = "year",
                        KeyType = KeyType.HASH,
                    },
                    new KeySchemaElement
                    {
                        AttributeName = "title",
                        KeyType = KeyType.RANGE,
                    },
                },
                ProvisionedThroughput = new ProvisionedThroughput
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5,
                },
            });

            // Wait until the table is ACTIVE and then report success.
            Console.Write("Waiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = response.TableDescription.TableName,
            };

            TableStatus status;

            int sleepDuration = 2000;

            do
            {
                System.Threading.Thread.Sleep(sleepDuration);

                var describeTableResponse = await
client.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;
```

```
                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_create_table
#
# This function creates an Amazon DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to create.
#       -a attribute_definitions -- JSON file path of a list of attributes and
 their types.
#       -k key_schema -- JSON file path of a list of attributes and their key
 types.
#       -p provisioned_throughput -- Provisioned throughput settings for the
 table.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_create_table() {
  local table_name attribute_definitions key_schema provisioned_throughput
 response
```

```
 local option OPTARG # Required to use getopts command in a function.

 ######################################
 # Function usage explanation
 ######################################
 function usage() {
   echo "function dynamodb_create_table"
   echo "Creates an Amazon DynamoDB table."
   echo " -n table_name  -- The name of the table to create."
   echo " -a attribute_definitions -- JSON file path of a list of attributes and
their types."
   echo " -k key_schema -- JSON file path of a list of attributes and their key
types."
   echo " -p provisioned_throughput -- Provisioned throughput settings for the
table."
   echo ""
 }

 # Retrieve the calling parameters.
 while getopts "n:a:k:p:h" option; do
   case "${option}" in
     n) table_name="${OPTARG}" ;;
     a) attribute_definitions="${OPTARG}" ;;
     k) key_schema="${OPTARG}" ;;
     p) provisioned_throughput="${OPTARG}" ;;
     h)
       usage
       return 0
       ;;
     \?)
       echo "Invalid parameter"
       usage
       return 1
       ;;
   esac
 done
 export OPTIND=1

 if [[ -z "$table_name" ]]; then
   errecho "ERROR: You must provide a table name with the -n parameter."
   usage
   return 1
 fi
```

```
  if [[ -z "$attribute_definitions" ]]; then
    errecho "ERROR: You must provide an attribute definitions json file path the
 -a parameter."
    usage
    return 1
  fi

  if [[ -z "$key_schema" ]]; then
    errecho "ERROR: You must provide a key schema json file path the -k
 parameter."
    usage
    return 1
  fi

  if [[ -z "$provisioned_throughput" ]]; then
    errecho "ERROR: You must provide a provisioned throughput json file path the
 -p parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    attribute_definitions:   $attribute_definitions"
  iecho "    key_schema:   $key_schema"
  iecho "    provisioned_throughput:   $provisioned_throughput"
  iecho ""

  response=$(aws dynamodb create-table \
    --table-name "$table_name" \
    --attribute-definitions file://"$attribute_definitions" \
    --key-schema file://"$key_schema" \
    --provisioned-throughput "$provisioned_throughput")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-table operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

#############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
#############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
```

```
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte CreateTableem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon DynamoDB table.
/*!
  \sa createTable()
  \param tableName: Name for the DynamoDB table.
  \param primaryKey: Primary key for the DynamoDB table.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::createTable(const Aws::String &tableName,
                                   const Aws::String &primaryKey,
```

```
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Creating table " << tableName <<
              " with a simple primary key: \"" << primaryKey << "\"." <<
 std::endl;

    Aws::DynamoDB::Model::CreateTableRequest request;

    Aws::DynamoDB::Model::AttributeDefinition hashKey;
    hashKey.SetAttributeName(primaryKey);
    hashKey.SetAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
    request.AddAttributeDefinitions(hashKey);

    Aws::DynamoDB::Model::KeySchemaElement keySchemaElement;
    keySchemaElement.WithAttributeName(primaryKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::HASH);
    request.AddKeySchema(keySchemaElement);

    Aws::DynamoDB::Model::ProvisionedThroughput throughput;
    throughput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
    request.SetProvisionedThroughput(throughput);
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::CreateTableOutcome &outcome =
 dynamoClient.CreateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Table \""
                  << outcome.GetResult().GetTableDescription().GetTableName() <<
                  " created!" << std::endl;
    }
    else {
        std::cerr << "Failed to create table: " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar uma tabela com tags

O exemplo de `create-table` a seguir usa os atributos especificados e o esquema de chaves para criar uma tabela chamada `MusicCollection`. Essa tabela usa um throughput provisionado e é criptografada em repouso usando a CMK de propriedade padrão da AWS. O comando também aplica uma tag à tabela, com uma chave `Owner` e valor de `blueTeam`.

```
aws dynamodb create-table \
    --table-name MusicCollection \
    --attribute-definitions AttributeName=Artist,AttributeType=S
 AttributeName=SongTitle,AttributeType=S \
    --key-schema AttributeName=Artist,KeyType=HASH
 AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5 \
    --tags Key=Owner,Value=blueTeam
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "TableName": "MusicCollection",
        "TableStatus": "CREATING",
```

```
        "KeySchema": [
            {
                "KeyType": "HASH",
                "AttributeName": "Artist"
            },
            {
                "KeyType": "RANGE",
                "AttributeName": "SongTitle"
            }
        ],
        "ItemCount": 0,
        "CreationDateTime": "2020-05-26T16:04:41.627000-07:00",
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
MusicCollection",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111"
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como criar uma tabela no modo sob demanda

O exemplo a seguir cria uma tabela chamada `MusicCollection` usando o modo sob demanda, em vez do modo de throughput provisionado. Esse método é útil para tabelas com workloads imprevisíveis.

```
aws dynamodb create-table \
    --table-name MusicCollection \
    --attribute-definitions AttributeName=Artist,AttributeType=S
 AttributeName=SongTitle,AttributeType=S \
    --key-schema AttributeName=Artist,KeyType=HASH
 AttributeName=SongTitle,KeyType=RANGE \
    --billing-mode PAY_PER_REQUEST
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
```

```
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "TableName": "MusicCollection",
        "KeySchema": [
            {
                "AttributeName": "Artist",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "SongTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-05-27T11:44:10.807000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 0,
            "WriteCapacityUnits": 0
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
MusicCollection",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "BillingModeSummary": {
            "BillingMode": "PAY_PER_REQUEST"
        }
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 3: como criar uma tabela e criptografá-la com uma CMK gerenciada pelo cliente

O exemplo a seguir cria uma tabela chamada `MusicCollection` e a criptografa usando uma CMK gerenciada pelo cliente.

```
aws dynamodb create-table \
    --table-name MusicCollection \
    --attribute-definitions AttributeName=Artist,AttributeType=S
 AttributeName=SongTitle,AttributeType=S \
    --key-schema AttributeName=Artist,KeyType=HASH
 AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5 \
    --sse-specification Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-
abcd-1234-a123-ab1234a1b234
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "TableName": "MusicCollection",
        "KeySchema": [
            {
                "AttributeName": "Artist",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "SongTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-05-27T11:12:16.431000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 5,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
```

```
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
MusicCollection",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "SSEDescription": {
            "Status": "ENABLED",
            "SSEType": "KMS",
            "KMSMasterKeyArn": "arn:aws:kms:us-west-2:123456789012:key/abcd1234-
abcd-1234-a123-ab1234a1b234"
        }
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 4: como criar uma tabela com um índice secundário local

O exemplo a seguir usa os atributos especificados e o esquema de chaves para criar uma tabela chamada `MusicCollection` com um índice secundário local chamado `AlbumTitleIndex`.

```
aws dynamodb create-table \
    --table-name MusicCollection \
    --attribute-definitions AttributeName=Artist,AttributeType=S
 AttributeName=SongTitle,AttributeType=S AttributeName=AlbumTitle,AttributeType=S
 \
    --key-schema AttributeName=Artist,KeyType=HASH
 AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --local-secondary-indexes \
        "[
            {
                \"IndexName\": \"AlbumTitleIndex\",
                \"KeySchema\": [
                    {\"AttributeName\": \"Artist\",\"KeyType\":\"HASH\"},
                    {\"AttributeName\": \"AlbumTitle\",\"KeyType\":\"RANGE\"}
                ],
                \"Projection\": {
                    \"ProjectionType\": \"INCLUDE\",
                    \"NonKeyAttributes\": [\"Genre\", \"Year\"]
                }
            }
```

```
        ]"
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "AlbumTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "TableName": "MusicCollection",
        "KeySchema": [
            {
                "AttributeName": "Artist",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "SongTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-05-26T15:59:49.473000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
MusicCollection",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
```

```
        "LocalSecondaryIndexes": [
            {
                "IndexName": "AlbumTitleIndex",
                "KeySchema": [
                    {
                        "AttributeName": "Artist",
                        "KeyType": "HASH"
                    },
                    {
                        "AttributeName": "AlbumTitle",
                        "KeyType": "RANGE"
                    }
                ],
                "Projection": {
                    "ProjectionType": "INCLUDE",
                    "NonKeyAttributes": [
                        "Genre",
                        "Year"
                    ]
                },
                "IndexSizeBytes": 0,
                "ItemCount": 0,
                "IndexArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
MusicCollection/index/AlbumTitleIndex"
            }
        ]
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 5: como criar uma tabela com um índice secundário global

O exemplo a seguir cria uma tabela chamada `GameScores` com um índice secundário global chamado `GameTitleIndex`. A tabela-base tem uma chave de partição `UserId` e uma chave de classificação `GameTitle`, permitindo que você encontre a melhor pontuação de um usuário individual para um jogo específico de forma eficiente, enquanto o GSI tem uma chave de partição `GameTitle` e uma chave de classificação `TopScore`, permitindo que você encontre rapidamente a pontuação mais alta geral para um jogo específico.

```
aws dynamodb create-table \
```

```
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S AttributeName=TopScore,AttributeType=N \
    --key-schema AttributeName=UserId,KeyType=HASH \
                 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --global-secondary-indexes \
        "[
            {
                \"IndexName\": \"GameTitleIndex\",
                \"KeySchema\": [
                    {\"AttributeName\":\"GameTitle\",\"KeyType\":\"HASH\"},
                    {\"AttributeName\":\"TopScore\",\"KeyType\":\"RANGE\"}
                ],
                \"Projection\": {
                    \"ProjectionType\":\"INCLUDE\",
                    \"NonKeyAttributes\":[\"UserId\"]
                },
                \"ProvisionedThroughput\": {
                    \"ReadCapacityUnits\": 10,
                    \"WriteCapacityUnits\": 5
                }
            }
        ]"
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "TopScore",
                "AttributeType": "N"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
```

```
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "GameTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-05-26T17:28:15.602000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "GlobalSecondaryIndexes": [
            {
                "IndexName": "GameTitleIndex",
                "KeySchema": [
                    {
                        "AttributeName": "GameTitle",
                        "KeyType": "HASH"
                    },
                    {
                        "AttributeName": "TopScore",
                        "KeyType": "RANGE"
                    }
                ],
                "Projection": {
                    "ProjectionType": "INCLUDE",
                    "NonKeyAttributes": [
                        "UserId"
                    ]
                },
                "IndexStatus": "CREATING",
                "ProvisionedThroughput": {
                    "NumberOfDecreasesToday": 0,
```

```
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 5
                },
                "IndexSizeBytes": 0,
                "ItemCount": 0,
                "IndexArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
GameScores/index/GameTitleIndex"
            }
        ]
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 6: como criar uma tabela com vários índices secundários globais ao mesmo tempo

O exemplo a seguir cria uma tabela chamada `GameScores` com dos índices secundários globais. Os esquemas do GSI são passados por meio de um arquivo, e não pela linha de comando.

```
aws dynamodb create-table \
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S AttributeName=TopScore,AttributeType=N
 AttributeName=Date,AttributeType=S \
    --key-schema AttributeName=UserId,KeyType=HASH
 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --global-secondary-indexes file://gsi.json
```

Conteúdo de `gsi.json`:

```
[
    {
        "IndexName": "GameTitleIndex",
        "KeySchema": [
            {
                "AttributeName": "GameTitle",
                "KeyType": "HASH"
            },
            {
```

```
                "AttributeName": "TopScore",
                "KeyType": "RANGE"
            }
        ],
        "Projection": {
            "ProjectionType": "ALL"
        },
        "ProvisionedThroughput": {
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        }
    },
    {
        "IndexName": "GameDateIndex",
        "KeySchema": [
            {
                "AttributeName": "GameTitle",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "Date",
                "KeyType": "RANGE"
            }
        ],
        "Projection": {
            "ProjectionType": "ALL"
        },
        "ProvisionedThroughput": {
            "ReadCapacityUnits": 5,
            "WriteCapacityUnits": 5
        }
    }
]
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Date",
                "AttributeType": "S"
            },
```

```
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "TopScore",
                "AttributeType": "N"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "GameTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-08-04T16:40:55.524000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "GlobalSecondaryIndexes": [
            {
                "IndexName": "GameTitleIndex",
                "KeySchema": [
                    {
                        "AttributeName": "GameTitle",
                        "KeyType": "HASH"
                    },
                    {
```

```
                        "AttributeName": "TopScore",
                        "KeyType": "RANGE"
                    }
                ],
                "Projection": {
                    "ProjectionType": "ALL"
                },
                "IndexStatus": "CREATING",
                "ProvisionedThroughput": {
                    "NumberOfDecreasesToday": 0,
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 5
                },
                "IndexSizeBytes": 0,
                "ItemCount": 0,
                "IndexArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
GameScores/index/GameTitleIndex"
            },
            {
                "IndexName": "GameDateIndex",
                "KeySchema": [
                    {
                        "AttributeName": "GameTitle",
                        "KeyType": "HASH"
                    },
                    {
                        "AttributeName": "Date",
                        "KeyType": "RANGE"
                    }
                ],
                "Projection": {
                    "ProjectionType": "ALL"
                },
                "IndexStatus": "CREATING",
                "ProvisionedThroughput": {
                    "NumberOfDecreasesToday": 0,
                    "ReadCapacityUnits": 5,
                    "WriteCapacityUnits": 5
                },
                "IndexSizeBytes": 0,
                "ItemCount": 0,
                "IndexArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
GameScores/index/GameDateIndex"
            }
```

```
        ]
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 7: como criar uma tabela com o Streams habilitado

O exemplo a seguir cria uma tabela chamada `GameScores` com o DynamoDB Streams habilitado. Imagens novas e antigas de cada item serão gravadas no fluxo.

```
aws dynamodb create-table \
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S \
    --key-schema AttributeName=UserId,KeyType=HASH
 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --stream-specification StreamEnabled=TRUE,StreamViewType=NEW_AND_OLD_IMAGES
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
```

```
                "AttributeName": "GameTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2020-05-27T10:49:34.056000-07:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "StreamSpecification": {
            "StreamEnabled": true,
            "StreamViewType": "NEW_AND_OLD_IMAGES"
        },
        "LatestStreamLabel": "2020-05-27T17:49:34.056",
        "LatestStreamArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
GameScores/stream/2020-05-27T17:49:34.056"
    }
}
```

Para obter mais informações, consulte Operações básicas nas tabelas no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 8: como criar uma tabela com o fluxo somente de chaves habilitado

O exemplo a seguir cria uma tabela chamada `GameScores` com o DynamoDB Streams habilitado. Somente os atributos-chave dos itens modificados são gravados no fluxo.

```
aws dynamodb create-table \
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S \
    --key-schema AttributeName=UserId,KeyType=HASH
 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --stream-specification StreamEnabled=TRUE,StreamViewType=KEYS_ONLY
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "GameTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2023-05-25T18:45:34.140000+00:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "StreamSpecification": {
            "StreamEnabled": true,
            "StreamViewType": "KEYS_ONLY"
        },
        "LatestStreamLabel": "2023-05-25T18:45:34.140",
        "LatestStreamArn": "arn:aws:dynamodb:us-west-2:123456789012:table/
GameScores/stream/2023-05-25T18:45:34.140",
        "DeletionProtectionEnabled": false
    }
```

```
}
```

Para obter mais informações, consulte Captura de dados de alterações com o Amazon DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 9: como criar uma tabela com a classe Standard-Infrequent Access

O exemplo a seguir cria uma tabela chamada `GameScores` e atribui a classe de tabela Standard-Infrequent Access (DynamoDB Standard-IA). Essa classe de tabela é otimizada para que o armazenamento seja o custo dominante.

```
aws dynamodb create-table \
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S \
    --key-schema AttributeName=UserId,KeyType=HASH
 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --table-class STANDARD_INFREQUENT_ACCESS
```

Saída:

```
{
    "TableDescription": {
        "AttributeDefinitions": [
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "GameTitle",
```

```
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2023-05-25T18:33:07.581000+00:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "TableClassSummary": {
            "TableClass": "STANDARD_INFREQUENT_ACCESS"
        },
        "DeletionProtectionEnabled": false
    }
}
```

Para obter mais informações, consulte Classes de tabela no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 10: como criar uma tabela com a proteção contra exclusão habilitada

O exemplo a seguir cria uma tabela chamada `GameScores` e habilita a proteção contra exclusão.

```
aws dynamodb create-table \
    --table-name GameScores \
    --attribute-definitions AttributeName=UserId,AttributeType=S
 AttributeName=GameTitle,AttributeType=S \
    --key-schema AttributeName=UserId,KeyType=HASH
 AttributeName=GameTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --deletion-protection-enabled
```

Saída:

```
{
    "TableDescription": {
```

```
        "AttributeDefinitions": [
            {
                "AttributeName": "GameTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "UserId",
                "AttributeType": "S"
            }
        ],
        "TableName": "GameScores",
        "KeySchema": [
            {
                "AttributeName": "UserId",
                "KeyType": "HASH"
            },
            {
                "AttributeName": "GameTitle",
                "KeyType": "RANGE"
            }
        ],
        "TableStatus": "CREATING",
        "CreationDateTime": "2023-05-25T23:02:17.093000+00:00",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "ReadCapacityUnits": 10,
            "WriteCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableArn": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
        "TableId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
        "DeletionProtectionEnabled": true
    }
}
```

Para obter mais informações, consulte Usar a proteção contra exclusão no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte CreateTableem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// CreateMovieTable creates a DynamoDB table with a composite primary key defined
 as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
 var tableDesc *types.TableDescription
 table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
 &dynamodb.CreateTableInput{
  AttributeDefinitions: []types.AttributeDefinition{{
   AttributeName: aws.String("year"),
   AttributeType: types.ScalarAttributeTypeN,
  }, {
   AttributeName: aws.String("title"),
   AttributeType: types.ScalarAttributeTypeS,
  }},
  KeySchema: []types.KeySchemaElement{{
   AttributeName: aws.String("year"),
   KeyType:       types.KeyTypeHash,
  }, {
```

```
    AttributeName: aws.String("title"),
    KeyType:       types.KeyTypeRange,
   }},
   TableName: aws.String(basics.TableName),
   ProvisionedThroughput: &types.ProvisionedThroughput{
    ReadCapacityUnits:  aws.Int64(10),
    WriteCapacityUnits: aws.Int64(10),
   },
  })
  if err != nil {
   log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
  } else {
   waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
   err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
    TableName: aws.String(basics.TableName)}, 5*time.Minute)
   if err != nil {
    log.Printf("Wait for table exists failed. Here's why: %v\n", err)
   }
   tableDesc = table.TableDescription
  }
  return tableDesc, err
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeDefinition;
import software.amazon.awssdk.services.dynamodb.model.CreateTableRequest;
```

```
import software.amazon.awssdk.services.dynamodb.model.CreateTableResponse;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableRequest;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableResponse;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.KeySchemaElement;
import software.amazon.awssdk.services.dynamodb.model.KeyType;
import software.amazon.awssdk.services.dynamodb.model.ProvisionedThroughput;
import software.amazon.awssdk.services.dynamodb.model.ScalarAttributeType;
import software.amazon.awssdk.services.dynamodb.waiters.DynamoDbWaiter;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key>

                Where:
                    tableName - The Amazon DynamoDB table to create (for example,
 Music3).
                    key - The key for the Amazon DynamoDB table (for example,
 Artist).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        System.out.println("Creating an Amazon DynamoDB table " + tableName + "
 with a simple primary key: " + key);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
```

```
                .region(region)
                .build();

        String result = createTable(ddb, tableName, key);
        System.out.println("New table is " + result);
        ddb.close();
    }

    public static String createTable(DynamoDbClient ddb, String tableName, String
key) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        CreateTableRequest request = CreateTableRequest.builder()
                .attributeDefinitions(AttributeDefinition.builder()
                        .attributeName(key)
                        .attributeType(ScalarAttributeType.S)
                        .build())
                .keySchema(KeySchemaElement.builder()
                        .attributeName(key)
                        .keyType(KeyType.HASH)
                        .build())
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .tableName(tableName)
                .build();

        String newTable;
        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            newTable = response.tableDescription().tableName();
            return newTable;

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
```

```
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { CreateTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new CreateTableCommand({
    TableName: "EspressoDrinks",
    // For more information about data types,
    // see https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
HowItWorks.NamingRulesDataTypes.html#HowItWorks.DataTypes and
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
    AttributeDefinitions: [
      {
        AttributeName: "DrinkName",
        AttributeType: "S",
      },
    ],
    KeySchema: [
      {
        AttributeName: "DrinkName",
        KeyType: "HASH",
```

```
      },
    ],
    ProvisionedThroughput: {
      ReadCapacityUnits: 1,
      WriteCapacityUnits: 1,
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  AttributeDefinitions: [
    {
      AttributeName: "CUSTOMER_ID",
      AttributeType: "N",
    },
    {
```

```
      AttributeName: "CUSTOMER_NAME",
      AttributeType: "S",
    },
  ],
  KeySchema: [
    {
      AttributeName: "CUSTOMER_ID",
      KeyType: "HASH",
    },
    {
      AttributeName: "CUSTOMER_NAME",
      KeyType: "RANGE",
    },
  ],
  ProvisionedThroughput: {
    ReadCapacityUnits: 1,
    WriteCapacityUnits: 1,
  },
  TableName: "CUSTOMER_LIST",
  StreamSpecification: {
    StreamEnabled: false,
  },
};

// Call DynamoDB to create the table
ddb.createTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Table Created", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewTable(tableNameVal: String, key: String): String? {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef)
        keySchema = listOf(keySchemaVal)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        var tableArn: String
        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        tableArn = response.tableDescription!!.tableArn.toString()
        println("Table $tableArn is ready")
```

```
        return tableArn
    }
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela.

```
        $tableName = "ddb_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

    public function createTable(string $tableName, array $attributes)
    {
        $keySchema = [];
        $attributeDefinitions = [];
        foreach ($attributes as $attribute) {
            if (is_a($attribute, DynamoDBAttribute::class)) {
                $keySchema[] = ['AttributeName' => $attribute->AttributeName,
 'KeyType' => $attribute->KeyType];
                $attributeDefinitions[] =
                    ['AttributeName' => $attribute->AttributeName,
 'AttributeType' => $attribute->AttributeType];
            }
        }
```

```
        $this->dynamoDbClient->createTable([
            'TableName' => $tableName,
            'KeySchema' => $keySchema,
            'AttributeDefinitions' => $attributeDefinitions,
            'ProvisionedThroughput' => ['ReadCapacityUnits' => 10,
 'WriteCapacityUnits' => 10],
        ]);
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela para armazenar dados de filmes.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.
```

```
        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {"AttributeName": "year", "KeyType": "HASH"},  # Partition
key
                    {"AttributeName": "title", "KeyType": "RANGE"},  # Sort key
                ],
                AttributeDefinitions=[
                    {"AttributeName": "year", "AttributeType": "N"},
                    {"AttributeName": "title", "AttributeType": "S"},
                ],
                ProvisionedThroughput={
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 10,
                },
            )
            self.table.wait_until_exists()
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.table
```

- Para obter detalhes da API, consulte a CreateTableReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Creates an Amazon DynamoDB table that can be used to store movie data.
  # The table uses the release year of the movie as the partition key and the
  # title as the sort key.
  #
  # @param table_name [String] The name of the table to create.
  # @return [Aws::DynamoDB::Table] The newly created table.
  def create_table(table_name)
    @table = @dynamo_resource.create_table(
      table_name: table_name,
      key_schema: [
        {attribute_name: "year", key_type: "HASH"},  # Partition key
        {attribute_name: "title", key_type: "RANGE"}  # Sort key
      ],
      attribute_definitions: [
        {attribute_name: "year", attribute_type: "N"},
        {attribute_name: "title", attribute_type: "S"}
      ],
```

```
      provisioned_throughput: {read_capacity_units: 10, write_capacity_units:
 10})
    @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
    @table
  rescue Aws::DynamoDB::Errors::ServiceError => e
    @logger.error("Failed create table #{table_name}:\n#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_table(
    client: &Client,
    table: &str,
    key: &str,
) -> Result<CreateTableOutput, Error> {
    let a_name: String = key.into();
    let table_name: String = table.into();

    let ad = AttributeDefinition::builder()
        .attribute_name(&a_name)
        .attribute_type(ScalarAttributeType::S)
        .build()
        .map_err(Error::BuildError)?;

    let ks = KeySchemaElement::builder()
        .attribute_name(&a_name)
        .key_type(KeyType::Hash)
        .build()
        .map_err(Error::BuildError)?;
```

```
    let pt = ProvisionedThroughput::builder()
        .read_capacity_units(10)
        .write_capacity_units(5)
        .build()
        .map_err(Error::BuildError)?;

    let create_table_response = client
        .create_table()
        .table_name(table_name)
        .key_schema(ks)
        .attribute_definitions(ad)
        .provisioned_throughput(pt)
        .send()
        .await;

    match create_table_response {
        Ok(out) => {
            println!("Added table {} with key {}", table, key);
            Ok(out)
        }
        Err(e) => {
            eprintln!("Got an error creating table:");
            eprintln!("{}", e);
            Err(Error::unhandled(e))
        }
    }
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        DATA(lt_keyschema) = VALUE /aws1/cl_dynkeyschemaelement=>tt_keyschema(
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'year'
                                              iv_keytype = 'HASH' ) )
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'title'
                                              iv_keytype = 'RANGE' ) ) ).
        DATA(lt_attributedefinitions) = VALUE /aws1/
cl_dynattributedefn=>tt_attributedefinitions(
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'year'
                                           iv_attributetype = 'N' ) )
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'title'
                                           iv_attributetype = 'S' ) ) ).

        " Adjust read/write capacities as desired.
        DATA(lo_dynprovthroughput)  = NEW /aws1/cl_dynprovthroughput(
          iv_readcapacityunits = 5
          iv_writecapacityunits = 5 ).
        oo_result = lo_dyn->createtable(
          it_keyschema = lt_keyschema
          iv_tablename = iv_table_name
          it_attributedefinitions = lt_attributedefinitions
          io_provisionedthroughput = lo_dynprovthroughput ).
        " Table creation can take some time. Wait till table exists before
 returning.
        lo_dyn->get_waiter( )->tableexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table' && iv_table_name && 'created.' TYPE 'I'.
      " This exception can happen if the table already exists.
      CATCH /aws1/cx_dynresourceinuseex INTO DATA(lo_resourceinuseex).
        DATA(lv_error) = |"{ lo_resourceinuseex->av_err_code }" -
{ lo_resourceinuseex->av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    ///
    /// Create a movie table in the Amazon DynamoDB data store.
    ///
    private func createTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = CreateTableInput(
            attributeDefinitions: [
                DynamoDBClientTypes.AttributeDefinition(attributeName: "year",
attributeType: .n),
                DynamoDBClientTypes.AttributeDefinition(attributeName: "title",
attributeType: .s),
            ],
            keySchema: [
                DynamoDBClientTypes.KeySchemaElement(attributeName: "year",
keyType: .hash),
                DynamoDBClientTypes.KeySchemaElement(attributeName: "title",
keyType: .range)
            ],
            provisionedThroughput: DynamoDBClientTypes.ProvisionedThroughput(
                readCapacityUnits: 10,
                writeCapacityUnits: 10
            ),
```

```
            tableName: self.tableName
        )
        let output = try await client.createTable(input: input)
        if output.tableDescription == nil {
            throw MoviesError.TableNotFound
        }
    }
```

- Para obter detalhes da API, consulte CreateTablea referência da API AWS SDK for Swift.

Excluir uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX
- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient
client, string tableName)
        {
            var request = new DeleteTableRequest
            {
                TableName = tableName,
            };

            var response = await client.DeleteTableAsync(request);
```

```
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Table {response.TableDescription.TableName}
 successfully deleted.");
                return true;
            }
            else
            {
                Console.WriteLine("Could not delete table.");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_delete_table
#
# This function deletes a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_delete_table() {
  local table_name response
  local option OPTARG # Required to use getopts command in a function.
```

```
# bashsupport disable=BP5008
function usage() {
  echo "function dynamodb_delete_table"
  echo "Deletes an Amazon DynamoDB table."
  echo " -n table_name  -- The name of the table to delete."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho ""

response=$(aws dynamodb delete-table \
  --table-name "$table_name")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports delete-table operation failed.$response"
```

```
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

#############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
```

```
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteTableem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon DynamoDB table.
/*!
  \sa deleteTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteTable(const Aws::String &tableName,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir uma tabela

O exemplo de `delete-table` a seguir exclui a tabela `MusicCollection`.

```
aws dynamodb delete-table \
    --table-name MusicCollection
```

Saída:

```
{
```

```
    "TableDescription": {
        "TableStatus": "DELETING",
        "TableSizeBytes": 0,
        "ItemCount": 0,
        "TableName": "MusicCollection",
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 5
        }
    }
}
```

Para obter mais informações, consulte Excluir uma tabela no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte DeleteTableem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
```

```
 _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
 &dynamodb.DeleteTableInput{
  TableName: aws.String(basics.TableName)})
 if err != nil {
  log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DeleteTableRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DeleteTable {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table to delete (for example,
 Music3).

                **Warning** This program will delete the table that you specify!
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        System.out.format("Deleting the Amazon DynamoDB table %s...\n",
 tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        deleteDynamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName)
 {
        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new DeleteTableCommand({
    TableName: "DecafCoffees",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to delete the specified table
ddb.deleteTable(params, function (err, data) {
  if (err && err.code === "ResourceNotFoundException") {
    console.log("Error: Table not found");
  } else if (err && err.code === "ResourceInUseException") {
    console.log("Error: Table in use");
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDynamoDBTable(tableNameVal: String) {
```

```
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function deleteTable(string $TableName)
    {
        $this->customWaiter(function () use ($TableName) {
            return $this->dynamoDbClient->deleteTable([
                'TableName' => $TableName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def delete_table(self):
        """
        Deletes the table.
        """
        try:
            self.table.delete()
            self.table = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Deletes the table.
  def delete_table
    @table.delete
    @table = nil
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't delete table. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_table(client: &Client, table: &str) ->
 Result<DeleteTableOutput, Error> {
    let resp = client.delete_table().table_name(table).send().await;

    match resp {
        Ok(out) => {
            println!("Deleted table");
            Ok(out)
        }
        Err(e) => Err(Error::Unhandled(e.into())),
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_dyn->deletetable( iv_tablename = iv_table_name ).
        " Wait till the table is actually deleted.
        lo_dyn->get_waiter( )->tablenotexists(
```

```
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'Table ' && iv_table_name && ' deleted.' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table ' && iv_table_name && ' does not exist' TYPE 'E'.
      CATCH /aws1/cx_dynresourceinuseex.
        MESSAGE 'The table cannot be deleted since it is in use' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    ///
    /// Deletes the table from Amazon DynamoDB.
    ///
    func deleteTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DeleteTableInput(
            tableName: self.tableName
        )
```

```
        _ = try await client.deleteTable(input: input)
    }
```

- Para obter detalhes da API, consulte DeleteTablea referência da API AWS SDK for Swift.

Excluir um item de uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um item em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Deletes a single item from a DynamoDB table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table from which the item
        /// will be deleted.</param>
        /// <param name="movieToDelete">A movie object containing the title and
        /// year of the movie to delete.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// delete operation.</returns>
        public static async Task<bool> DeleteItemAsync(
            AmazonDynamoDBClient client,
            string tableName,
            Movie movieToDelete)
        {
```

```
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = movieToDelete.Title },
                ["year"] = new AttributeValue { N =
 movieToDelete.Year.ToString() },
            };

            var request = new DeleteItemRequest
            {
                TableName = tableName,
                Key = key,
            };

            var response = await client.DeleteItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_delete_item
#
# This function deletes an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to delete.
#
#  Returns:
```

```
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_delete_item() {
  local table_name keys response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_delete_item"
    echo "Delete an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to delete."
    echo ""
  }
  while getopts "n:k:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
```

```
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    keys:   $keys"
  iecho ""

  response=$(aws dynamodb delete-item \
    --table-name "$table_name" \
    --key file://"$keys")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-item operation failed.$response"
    return 1
  fi

  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
```

```
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an item from an Amazon DynamoDB table.
/*!
  \sa deleteItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::deleteItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteItemRequest request;

    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteItemOutcome &outcome =
 dynamoClient.DeleteItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item \"" << partitionValue << "\" deleted!" << std::endl;
    }
    else {
        std::cerr << "Failed to delete item: " << outcome.GetError().GetMessage()
                  << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como excluir um item

O exemplo de `delete-item` a seguir exclui um item da tabela `MusicCollection` e solicita detalhes sobre o item excluído e a capacidade usada pela solicitação.

```
aws dynamodb delete-item \
    --table-name MusicCollection \
    --key file://key.json \
    --return-values ALL_OLD \
    --return-consumed-capacity TOTAL \
    --return-item-collection-metrics SIZE
```

Conteúdo de `key.json`:

```
{
    "Artist": {"S": "No One You Know"},
    "SongTitle": {"S": "Scared of My Shadow"}
}
```

Saída:

```
{
    "Attributes": {
        "AlbumTitle": {
            "S": "Blue Sky Blues"
        },
        "Artist": {
            "S": "No One You Know"
        },
```

```
        "SongTitle": {
            "S": "Scared of My Shadow"
        }
    },
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 2.0
    },
    "ItemCollectionMetrics": {
        "ItemCollectionKey": {
            "Artist": {
                "S": "No One You Know"
            }
        },
        "SizeEstimateRangeGB": [
            0.0,
            1.0
        ]
    }
}
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como excluir um item de forma condicional

O exemplo a seguir exclui um item da tabela `ProductCatalog` somente se a `ProductCategory` for `Sporting Goods` ou `Gardening Supplies` e o preço estiver entre 500 e 600. Ele retorna detalhes sobre o item que foi excluído.

```
aws dynamodb delete-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"456"}}' \
    --condition-expression "(ProductCategory IN (:cat1, :cat2)) and (#P
 between :lo and :hi)" \
    --expression-attribute-names file://names.json \
    --expression-attribute-values file://values.json \
    --return-values ALL_OLD
```

Conteúdo de `names.json`:

```
{
```

```
    "#P": "Price"
}
```

Conteúdo de `values.json`:

```
{
    ":cat1": {"S": "Sporting Goods"},
    ":cat2": {"S": "Gardening Supplies"},
    ":lo": {"N": "500"},
    ":hi": {"N": "600"}
}
```

Saída:

```
{
    "Attributes": {
        "Id": {
            "N": "456"
        },
        "Price": {
            "N": "550"
        },
        "ProductCategory": {
            "S": "Sporting Goods"
        }
    }
}
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte DeleteItemem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
 _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
 &dynamodb.DeleteItemInput{
  TableName: aws.String(basics.TableName), Key: movie.GetKey(),
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
```

```
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DeleteItemRequest;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyval>

                Where:
                    tableName - The Amazon DynamoDB table to delete the item from
 (for example, Music3).
                    key - The key used in the Amazon DynamoDB table (for example,
 Artist).\s
                    keyval - The key value that represents the item to delete
 (for example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        System.out.format("Deleting item \"%s\" from %s\n", keyVal, tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        deleteDynamoDBItem(ddb, tableName, key, keyVal);
        ddb.close();
    }

    public static void deleteDynamoDBItem(DynamoDbClient ddb, String tableName,
 String key, String keyVal) {
        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());
```

```
        DeleteItemRequest deleteReq = DeleteItemRequest.builder()
                .tableName(tableName)
                .key(keyToGet)
                .build();

        try {
            ddb.deleteItem(deleteReq);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte DeleteCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, DeleteCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new DeleteCommand({
    TableName: "Sodas",
    Key: {
      Flavor: "Cola",
```

```
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Exclua um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "VALUE" },
  },
};

// Call DynamoDB to delete the item from the table
ddb.deleteItem(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Exclua um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  Key: {
    HASH_KEY: VALUE,
  },
  TableName: "TABLE",
};

docClient.delete(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDynamoDBItem(tableNameVal: String, keyName: String, keyVal:
 String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = DeleteItemRequest {
        tableName = tableNameVal
        key = keyToGet
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteItem(request)
        println("Item with key matching $keyVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $key = [
```

```
            'Item' => [
                'title' => [
                    'S' => $movieName,
                ],
                'year' => [
                    'N' => $movieYear,
                ],
            ]
        ];

        $service->deleteItemByKey($tableName, $key);
        echo "But, bad news, this was a trap. That movie has now been deleted
 because of your rating...harsh.\n";

    public function deleteItemByKey(string $tableName, array $key)
    {
        $this->dynamoDbClient->deleteItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
```

```
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def delete_movie(self, title, year):
        """
        Deletes a movie from the table.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        """
        try:
            self.table.delete_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s",
                title,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

É possível especificar uma condição para que um item seja excluído somente quando ele atender a determinados critérios.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def delete_underrated_movie(self, title, year, rating):
        """
        Deletes a movie only if it is rated below a specified value. By using a
        condition expression in a delete operation, you can specify that an item
 is
        deleted only when it meets certain criteria.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
```

```
        :param rating: The rating threshold to check before deleting the movie.
        """
        try:
            self.table.delete_item(
                Key={"year": year, "title": title},
                ConditionExpression="info.rating <= :val",
                ExpressionAttributeValues={":val": Decimal(str(rating))},
            )
        except ClientError as err:
            if err.response["Error"]["Code"] ==
 "ConditionalCheckFailedException":
                logger.warning(
                    "Didn't delete %s because its rating is greater than %s.",
                    title,
                    rating,
                )
            else:
                logger.error(
                    "Couldn't delete movie %s. Here's why: %s: %s",
                    title,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
```

- Para obter detalhes da API, consulte a DeleteItemReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
```

```
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Deletes a movie from the table.
  #
  # @param title [String] The title of the movie to delete.
  # @param year [Integer] The release year of the movie to delete.
  def delete_item(title, year)
    @table.delete_item(key: {"year" => year, "title" => title})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't delete movie #{title}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_item(
    client: &Client,
    table: &str,
    key: &str,
    value: &str,
) -> Result<DeleteItemOutput, Error> {
    match client
        .delete_item()
```

```
        .table_name(table)
        .key(key, AttributeValue::S(value.into()))
        .send()
        .await
    {
        Ok(out) => {
            println!("Deleted item from table");
            Ok(out)
        }
        Err(e) => Err(Error::unhandled(e)),
    }
}
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA(lo_resp) = lo_dyn->deleteitem(
          iv_tablename                = iv_table_name
          it_key                      = it_key_input ).
        MESSAGE 'Deleted one item.' TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
 TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Delete a movie, given its title and release year.
///
/// - Parameters:
///   - title: The movie's title.
///   - year: The movie's release year.
///
func delete(title: String, year: Int) async throws {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = DeleteItemInput(
        key: [
            "year": .n(String(year)),
            "title": .s(title)
        ],
        tableName: self.tableName
    )
    _ = try await client.deleteItem(input: input)
}
```

- Para obter detalhes da API, consulte DeleteItema referência da API AWS SDK for Swift.

Obter um lote de itens do DynamoDB usando um AWS SDK

Os exemplos de códigos a seguir mostram como obter um lote de itens do DynamoDB.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;

namespace LowLevelBatchGet
{
    public class LowLevelBatchGet
    {
        private static readonly string _table1Name = "Forum";
        private static readonly string _table2Name = "Thread";

        public static async void
 RetrieveMultipleItemsBatchGet(AmazonDynamoDBClient client)
        {
            var request = new BatchGetItemRequest
            {
                RequestItems = new Dictionary<string, KeysAndAttributes>()
            {
                { _table1Name,
                  new KeysAndAttributes
                  {
                      Keys = new List<Dictionary<string, AttributeValue> >()
                      {
                          new Dictionary<string, AttributeValue>()
                          {
```

```
                                { "Name", new AttributeValue {
                                  S = "Amazon DynamoDB"
                              } }
                                },
                                new Dictionary<string, AttributeValue>()
                                {
                                { "Name", new AttributeValue {
                                  S = "Amazon S3"
                              } }
                                }
                            }
                        }},
                    {
                        _table2Name,
                        new KeysAndAttributes
                        {
                            Keys = new List<Dictionary<string, AttributeValue> >()
                            {
                                new Dictionary<string, AttributeValue>()
                                {
                                    { "ForumName", new AttributeValue {
                                          S = "Amazon DynamoDB"
                                      } },
                                    { "Subject", new AttributeValue {
                                          S = "DynamoDB Thread 1"
                                      } }
                                },
                                new Dictionary<string, AttributeValue>()
                                {
                                    { "ForumName", new AttributeValue {
                                          S = "Amazon DynamoDB"
                                      } },
                                    { "Subject", new AttributeValue {
                                          S = "DynamoDB Thread 2"
                                      } }
                                },
                                new Dictionary<string, AttributeValue>()
                                {
                                    { "ForumName", new AttributeValue {
                                          S = "Amazon S3"
                                      } },
                                    { "Subject", new AttributeValue {
                                          S = "S3 Thread 1"
                                      } }
```

```
                            }
                        }
                    }
                }
            }
            };

            BatchGetItemResponse response;
            do
            {
                Console.WriteLine("Making request");
                response = await client.BatchGetItemAsync(request);

                // Check the response.
                var responses = response.Responses; // Attribute list in the
response.

                foreach (var tableResponse in responses)
                {
                    var tableResults = tableResponse.Value;
                    Console.WriteLine("Items retrieved from table {0}",
tableResponse.Key);
                    foreach (var item1 in tableResults)
                    {
                        PrintItem(item1);
                    }
                }

                // Any unprocessed keys? could happen if you exceed
ProvisionedThroughput or some other error.
                Dictionary<string, KeysAndAttributes> unprocessedKeys =
response.UnprocessedKeys;
                foreach (var unprocessedTableKeys in unprocessedKeys)
                {
                    // Print table name.
                    Console.WriteLine(unprocessedTableKeys.Key);
                    // Print unprocessed primary keys.
                    foreach (var key in unprocessedTableKeys.Value.Keys)
                    {
                        PrintItem(key);
                    }
                }

                request.RequestItems = unprocessedKeys;
```

```
            } while (response.UnprocessedKeys.Count > 0);
        }

        private static void PrintItem(Dictionary<string, AttributeValue>
 attributeList)
        {
            foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
            {
                string attributeName = kvp.Key;
                AttributeValue value = kvp.Value;

                Console.WriteLine(
                    attributeName + " " +
                    (value.S == null ? "" : "S=[" + value.S + "]") +
                    (value.N == null ? "" : "N=[" + value.N + "]") +
                    (value.SS == null ? "" : "SS=[" + string.Join(",",
 value.SS.ToArray()) + "]") +
                    (value.NS == null ? "" : "NS=[" + string.Join(",",
 value.NS.ToArray()) + "]")
                    );
            }

 Console.WriteLine("************************************************");
        }

        static void Main()
        {
            var client = new AmazonDynamoDBClient();

            RetrieveMultipleItemsBatchGet(client);
        }
    }
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_batch_get_item
#
# This function gets a batch of items from a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the keys of the items to get.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_batch_get_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_get_item"
    echo "Get a batch of items from a DynamoDB table."
    echo " -i item  -- Path to json file containing the keys of the items to
 get."
    echo ""
  }

  while getopts "i:h" option; do
    case "${option}" in
      i) item="${OPTARG}" ;;
```

```
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  response=$(aws dynamodb batch-get-item \
    --request-items file://"$item")
  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-get-item operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
```

```
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte BatchGetItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Batch get items from different Amazon DynamoDB tables.
/*!
  \sa batchGetItem()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::batchGetItem(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchGetItemRequest request;

    // Table1: Forum.
    Aws::String table1Name = "Forum";
    Aws::DynamoDB::Model::KeysAndAttributes table1KeysAndAttributes;

    // Table1: Projection expression.
    table1KeysAndAttributes.SetProjectionExpression("#n, Category, Messages,
 #v");

    // Table1: Expression attribute names.
    Aws::Http::HeaderValueCollection headerValueCollection;
    headerValueCollection.emplace("#n", "Name");
    headerValueCollection.emplace("#v", "Views");
    table1KeysAndAttributes.SetExpressionAttributeNames(headerValueCollection);

    // Table1: Set key name, type, and value to search.
    std::vector<Aws::String> nameValues = {"Amazon DynamoDB", "Amazon S3"};
    for (const Aws::String &name: nameValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetS(name);
```

```
        keys.emplace("Name", key);
        table1KeysAndAttributes.AddKeys(keys);
    }

    Aws::Map<Aws::String, Aws::DynamoDB::Model::KeysAndAttributes> requestItems;
    requestItems.emplace(table1Name, table1KeysAndAttributes);

    // Table2: ProductCatalog.
    Aws::String table2Name = "ProductCatalog";
    Aws::DynamoDB::Model::KeysAndAttributes table2KeysAndAttributes;
    table2KeysAndAttributes.SetProjectionExpression("Title, Price, Color");

    // Table2: Set key name, type, and value to search.
    std::vector<Aws::String> idValues = {"102", "103", "201"};
    for (const Aws::String &id: idValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetN(id);
        keys.emplace("Id", key);
        table2KeysAndAttributes.AddKeys(keys);
    }

    requestItems.emplace(table2Name, table2KeysAndAttributes);

    bool result = true;
    do {  // Use a do loop to handle pagination.
        request.SetRequestItems(requestItems);
        const Aws::DynamoDB::Model::BatchGetItemOutcome &outcome =
dynamoClient.BatchGetItem(
                request);

        if (outcome.IsSuccess()) {
            for (const auto &responsesMapEntry:
outcome.GetResult().GetResponses()) {
                Aws::String tableName = responsesMapEntry.first;
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &tableResults = responsesMapEntry.second;
                std::cout << "Retrieved " << tableResults.size()
                          << " responses for table '" << tableName << "'.\n"
                          << std::endl;
                if (tableName == "Forum") {

                    std::cout << "Name | Category | Message | Views" <<
std::endl;
```

```
                    for (const Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Name").GetS() << " | ";
                        std::cout << item.at("Category").GetS() << " | ";
                        std::cout << (item.count("Message") == 0 ? "" : item.at(
                                "Messages").GetN()) << " | ";
                        std::cout << (item.count("Views") == 0 ? "" : item.at(
                                "Views").GetN()) << std::endl;
                    }
                }
                else {
                    std::cout << "Title | Price | Color" << std::endl;
                    for (const Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Title").GetS() << " | ";
                        std::cout << (item.count("Price") == 0 ? "" : item.at(
                                "Price").GetN());
                        if (item.count("Color")) {
                            std::cout << " | ";
                            for (const
 std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> &listItem: item.at(
                                    "Color").GetL())
                                std::cout << listItem->GetS() << " ";
                        }
                        std::cout << std::endl;
                    }
                }
                std::cout << std::endl;
            }

            // If necessary, repeat request for remaining items.
            requestItems = outcome.GetResult().GetUnprocessedKeys();
        }
        else {
            std::cerr << "Batch get item failed: " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;
        }
    } while (!requestItems.empty());

    return result;
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como recuperar vários itens de uma tabela

O exemplo de `batch-get-items` a seguir lê vários itens da tabela `MusicCollection` usando um lote de três solicitações `GetItem` e solicita o número de unidades de capacidade de leitura consumidas pela operação. O comando retorna somente o atributo `AlbumTitle`.

```
aws dynamodb batch-get-item \
    --request-items file://request-items.json \
    --return-consumed-capacity TOTAL
```

Conteúdo de `request-items.json`:

```
{
    "MusicCollection": {
        "Keys": [
            {
                "Artist": {"S": "No One You Know"},
                "SongTitle": {"S": "Call Me Today"}
            },
            {
                "Artist": {"S": "Acme Band"},
                "SongTitle": {"S": "Happy Day"}
            },
            {
                "Artist": {"S": "No One You Know"},
                "SongTitle": {"S": "Scared of My Shadow"}
            }
        ],
        "ProjectionExpression":"AlbumTitle"
    }
}
```

Saída:

```
{
    "Responses": {
        "MusicCollection": [
            {
                "AlbumTitle": {
                    "S": "Somewhat Famous"
                }
            },
            {
                "AlbumTitle": {
                    "S": "Blue Sky Blues"
                }
            },
            {
                "AlbumTitle": {
                    "S": "Louder Than Ever"
                }
            }
        ]
    },
    "UnprocessedKeys": {},
    "ConsumedCapacity": [
        {
            "TableName": "MusicCollection",
            "CapacityUnits": 1.5
        }
    ]
}
```

Para obter mais informações, consulte Operações em lote no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte BatchGetItemem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

mostra como obter itens em lote usando o cliente de serviço.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemRequest;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemResponse;
import software.amazon.awssdk.services.dynamodb.model.KeysAndAttributes;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class BatchReadItems {
    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """;

        String tableName = "Music";
```

```
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        getBatchItems(dynamoDbClient, tableName);
    }

    public static void getBatchItems(DynamoDbClient dynamoDbClient, String
 tableName) {
        // Define the primary key values for the items you want to retrieve.
        Map<String, AttributeValue> key1 = new HashMap<>();
        key1.put("Artist", AttributeValue.builder().s("Artist1").build());

        Map<String, AttributeValue> key2 = new HashMap<>();
        key2.put("Artist", AttributeValue.builder().s("Artist2").build());

        // Construct the batchGetItem request.
        Map<String, KeysAndAttributes> requestItems = new HashMap<>();
        requestItems.put(tableName, KeysAndAttributes.builder()
            .keys(List.of(key1, key2))
            .projectionExpression("Artist, SongTitle")
            .build());

        BatchGetItemRequest batchGetItemRequest = BatchGetItemRequest.builder()
            .requestItems(requestItems)
            .build();

        // Make the batchGetItem request.
        BatchGetItemResponse batchGetItemResponse =
 dynamoDbClient.batchGetItem(batchGetItemRequest);

        // Extract and print the retrieved items.
        Map<String, List<Map<String, AttributeValue>>> responses =
 batchGetItemResponse.responses();
        if (responses.containsKey(tableName)) {
            List<Map<String, AttributeValue>> musicItems =
 responses.get(tableName);
            for (Map<String, AttributeValue> item : musicItems) {
                System.out.println("Artist: " + item.get("Artist").s() +
                    ", SongTitle: " + item.get("SongTitle").s());
            }
        } else {
            System.out.println("No items retrieved.");
```

```
        }
    }
}
```

mostra como obter itens em lote usando o cliente de serviço e um paginador.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemRequest;
import software.amazon.awssdk.services.dynamodb.model.KeysAndAttributes;
import java.util.Collections;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

public class BatchGetItemsPaginator {

    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """;

        String tableName = "Music";
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        getBatchItemsPaginator(dynamoDbClient, tableName) ;
    }

    public static void getBatchItemsPaginator(DynamoDbClient dynamoDbClient,
 String tableName) {
        // Define the primary key values for the items you want to retrieve.
        Map<String, AttributeValue> key1 = new HashMap<>();
        key1.put("Artist", AttributeValue.builder().s("Artist1").build());
```

```
        Map<String, AttributeValue> key2 = new HashMap<>();
        key2.put("Artist", AttributeValue.builder().s("Artist2").build());

        // Construct the batchGetItem request.
        Map<String, KeysAndAttributes> requestItems = new HashMap<>();
        requestItems.put(tableName, KeysAndAttributes.builder()
            .keys(List.of(key1, key2))
            .projectionExpression("Artist, SongTitle")
            .build());

        BatchGetItemRequest batchGetItemRequest = BatchGetItemRequest.builder()
            .requestItems(requestItems)
            .build();

        // Use batchGetItemPaginator for paginated requests.
        dynamoDbClient.batchGetItemPaginator(batchGetItemRequest).stream()
            .flatMap(response -> response.responses().getOrDefault(tableName,
 Collections.emptyList()).stream())
            .forEach(item -> {
                System.out.println("Artist: " + item.get("Artist").s() +
                    ", SongTitle: " + item.get("SongTitle").s());
            });
    }
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchGet.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { BatchGetCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchGetCommand({
    // Each key in this object is the name of a table. This example refers
    // to a Books table.
    RequestItems: {
      Books: {
        // Each entry in Keys is an object that specifies a primary key.
        Keys: [
          {
            Title: "How to AWS",
          },
          {
            Title: "DynamoDB for DBAs",
          },
        ],
        // Only return the "Title" and "PageCount" attributes.
        ProjectionExpression: "Title, PageCount",
      },
    },
  });

  const response = await docClient.send(command);
  console.log(response.Responses["Books"]);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: {
      Keys: [
        { KEY_NAME: { N: "KEY_VALUE_1" } },
        { KEY_NAME: { N: "KEY_VALUE_2" } },
        { KEY_NAME: { N: "KEY_VALUE_3" } },
      ],
      ProjectionExpression: "KEY_NAME, ATTRIBUTE",
    },
  },
};

ddb.batchGetItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    data.Responses.TABLE_NAME.forEach(function (element, index, array) {
      console.log(element);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import decimal
import json
import logging
import os
import pprint
import time
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
dynamodb = boto3.resource("dynamodb")

MAX_GET_SIZE = 100  # Amazon DynamoDB rejects a get batch larger than 100 items.


def do_batch_get(batch_keys):
    """
    Gets a batch of items from Amazon DynamoDB. Batches can contain keys from
    more than one table.

    When Amazon DynamoDB cannot process all items in a batch, a set of
 unprocessed
    keys is returned. This function uses an exponential backoff algorithm to
 retry
    getting the unprocessed keys until all are retrieved or the specified
    number of tries is reached.
```

```
    :param batch_keys: The set of keys to retrieve. A batch can contain at most
100
                       keys. Otherwise, Amazon DynamoDB returns an error.
    :return: The dictionary of retrieved items grouped under their respective
             table names.
    """
    tries = 0
    max_tries = 5
    sleepy_time = 1  # Start with 1 second of sleep, then exponentially increase.
    retrieved = {key: [] for key in batch_keys}
    while tries < max_tries:
        response = dynamodb.batch_get_item(RequestItems=batch_keys)
        # Collect any retrieved items and retry unprocessed keys.
        for key in response.get("Responses", []):
            retrieved[key] += response["Responses"][key]
        unprocessed = response["UnprocessedKeys"]
        if len(unprocessed) > 0:
            batch_keys = unprocessed
            unprocessed_count = sum(
                [len(batch_key["Keys"]) for batch_key in batch_keys.values()]
            )
            logger.info(
                "%s unprocessed keys returned. Sleep, then retry.",
unprocessed_count
            )
            tries += 1
            if tries < max_tries:
                logger.info("Sleeping for %s seconds.", sleepy_time)
                time.sleep(sleepy_time)
                sleepy_time = min(sleepy_time * 2, 32)
        else:
            break

    return retrieved
```

- Para obter detalhes da API, consulte a BatchGetItemReferência da API AWSSDK for Python (Boto3).

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Gets an array of `Movie` objects describing all the movies in the
/// specified list. Any movies that aren't found in the list have no
/// corresponding entry in the resulting array.
///
/// - Parameters
///     - keys: An array of tuples, each of which specifies the title and
///       release year of a movie to fetch from the table.
///
/// - Returns:
///     - An array of `Movie` objects describing each match found in the
///     table.
///
/// - Throws:
///     - `MovieError.ClientUninitialized` if the DynamoDB client has not
///     been initialized.
///     - DynamoDB errors are thrown without change.
func batchGet(keys: [(title: String, year: Int)]) async throws -> [Movie] {
    guard let client = self.ddbClient else {
        throw MovieError.ClientUninitialized
    }

    var movieList: [Movie] = []
    var keyItems: [[Swift.String:DynamoDBClientTypes.AttributeValue]] = []

    // Convert the list of keys into the form used by DynamoDB.
```

```
        for key in keys {
            let item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
                "title": .s(key.title),
                "year": .n(String(key.year))
            ]
            keyItems.append(item)
        }

        // Create the input record for `batchGetItem()`. The list of requested
        // items is in the `requestItems` property. This array contains one
        // entry for each table from which items are to be fetched. In this
        // example, there's only one table containing the movie data.
        //
        // If we wanted this program to also support searching for matches
        // in a table of book data, we could add a second `requestItem`
        // mapping the name of the book table to the list of items we want to
        // find in it.
        let input = BatchGetItemInput(
            requestItems: [
                self.tableName: .init(
                    consistentRead: true,
                    keys: keyItems
                )
            ]
        )

        // Fetch the matching movies from the table.

        let output = try await client.batchGetItem(input: input)

        // Get the set of responses. If there aren't any, return the empty
        // movie list.

        guard let responses = output.responses else {
            return movieList
        }

        // Get the list of matching items for the table with the name
        // `tableName`.

        guard let responseList = responses[self.tableName] else {
            return movieList
        }
```

```
        // Create `Movie` items for each of the matching movies in the table
        // and add them to the `MovieList` array.

        for response in responseList {
            movieList.append(try Movie(withItem: response))
        }

        return movieList
    }
```

- Para obter detalhes da API, consulte BatchGetItema referência da API AWS SDK for Swift.

Obter um item de uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como obter um item em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX
- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Gets information about an existing movie from the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
```

```
        /// <param name="newMovie">A Movie object containing information about
        /// the movie to retrieve.</param>
        /// <param name="tableName">The name of the table containing the movie.</
param>
        /// <returns>A Dictionary object containing information about the item
        /// retrieved.</returns>
        public static async Task<Dictionary<string, AttributeValue>>
 GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new GetItemRequest
            {
                Key = key,
                TableName = tableName,
            };

            var response = await client.GetItemAsync(request);
            return response.Item;
        }
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###########################################################################
# function dynamodb_get_item
#
```

```
# This function gets an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to get.
#       [-q query]  -- Optional JMESPath query expression.
#
#  Returns:
#       The item as text output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_get_item() {
  local table_name keys query response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_get_item"
    echo "Get an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to get."
    echo " [-q query]  -- Optional JMESPath query expression."
    echo ""
  }
  query=""
  while getopts "n:k:q:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      q) query="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
```

```
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
    return 1
  fi

  if [[ -n "$query" ]]; then
    response=$(aws dynamodb get-item \
      --table-name "$table_name" \
      --key file://"$keys" \
      --output text \
      --query "$query")
  else
    response=$(
      aws dynamodb get-item \
        --table-name "$table_name" \
        --key file://"$keys" \
        --output text
    )
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports get-item operation failed.$response"
    return 1
  fi

  if [[ -n "$query" ]]; then
    echo "$response" | sed "/^\t/s/\t//1" # Remove initial tab that the JMSEPath
query inserts on some strings.
  else
```

```
    echo "$response"
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
```

```
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte GetItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Get an item from an Amazon DynamoDB table.
/*!
  \sa getItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::getItem(const Aws::String &tableName,
                               const Aws::String &partitionKey,
                               const Aws::String &partitionValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::GetItemRequest request;
```

```
    // Set up the request.
    request.SetTableName(tableName);
    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));

    // Retrieve the item's fields and values.
    const Aws::DynamoDB::Model::GetItemOutcome &outcome =
 dynamoClient.GetItem(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved fields/values.
        const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> &item =
 outcome.GetResult().GetItem();
        if (!item.empty()) {
            // Output each retrieved field and its value.
            for (const auto &i: item)
                std::cout << "Values: " << i.first << ": " << i.second.GetS()
                          << std::endl;
        }
        else {
            std::cout << "No item found with the key " << partitionKey <<
 std::endl;
        }
    }
    else {
        std::cerr << "Failed to get item: " << outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como ler um item em uma tabela

O exemplo de `get-item` a seguir recupera um item da tabela `MusicCollection`. A tabela tem uma chave hash-and-range primária (`ArtisteSongTitle`), portanto, você deve

especificar esses dois atributos. O comando também solicita informações sobre a capacidade de leitura consumida pela operação.

```
aws dynamodb get-item \
    --table-name MusicCollection \
    --key file://key.json \
    --return-consumed-capacity TOTAL
```

Conteúdo de `key.json`:

```
{
    "Artist": {"S": "Acme Band"},
    "SongTitle": {"S": "Happy Day"}
}
```

Saída:

```
{
    "Item": {
        "AlbumTitle": {
            "S": "Songs About Life"
        },
        "SongTitle": {
            "S": "Happy Day"
        },
        "Artist": {
            "S": "Acme Band"
        }
    },
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 0.5
    }
}
```

Para obter mais informações, consulte Ler um item no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como ler um item usando uma leitura consistente

O exemplo a seguir recupera um item da tabela `MusicCollection` usando leituras altamente consistentes.

```
aws dynamodb get-item \
    --table-name MusicCollection \
    --key file://key.json \
    --consistent-read \
    --return-consumed-capacity TOTAL
```

Conteúdo de `key.json`:

```
{
    "Artist": {"S": "Acme Band"},
    "SongTitle": {"S": "Happy Day"}
}
```

Saída:

```
{
    "Item": {
        "AlbumTitle": {
            "S": "Songs About Life"
        },
        "SongTitle": {
            "S": "Happy Day"
        },
        "Artist": {
            "S": "Acme Band"
        }
    },
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 1.0
    }
}
```

Para obter mais informações, consulte Ler um item no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 3: como recuperar atributos específicos de um item

O exemplo a seguir usa uma expressão de projeção para recuperar apenas três atributos do item desejado.

```
aws dynamodb get-item \
```

```
    --table-name ProductCatalog \
    --key '{"Id": {"N": "102"}}' \
    --projection-expression "#T, #C, #P" \
    --expression-attribute-names file://names.json
```

Conteúdo de `names.json`:

```
{
    "#T": "Title",
    "#C": "ProductCategory",
    "#P": "Price"
}
```

Saída:

```
{
    "Item": {
        "Price": {
            "N": "20"
        },
        "Title": {
            "S": "Book 102 Title"
        },
        "ProductCategory": {
            "S": "Book"
        }
    }
}
```

Para obter mais informações, consulte Ler um item no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte GetItemem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// GetMovie gets movie data from the DynamoDB table by using the primary
 composite key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
 movie := Movie{Title: title, Year: year}
 response, err := basics.DynamoDbClient.GetItem(context.TODO(),
 &dynamodb.GetItemInput{
  Key: movie.GetKey(), TableName: aws.String(basics.TableName),
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Item, &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}
```

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtém um item de uma tabela usando DynamoDbClient o.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.GetItemRequest;
import java.util.HashMap;
import java.util.Map;
import java.util.Set;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To get an item from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client, see the EnhancedGetItem example.
 */
public class GetItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyVal>

                Where:
```

```
                    tableName - The Amazon DynamoDB table from which an item is
retrieved (for example, Music3).\s
                    key - The key used in the Amazon DynamoDB table (for example,
Artist).\s
                    keyval - The key value that represents the item to get (for
example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        System.out.format("Retrieving item \"%s\" from \"%s\"\n", keyVal,
tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        getDynamoDBItem(ddb, tableName, key, keyVal);
        ddb.close();
    }

    public static void getDynamoDBItem(DynamoDbClient ddb, String tableName,
String key, String keyVal) {
        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());

        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName(tableName)
                .build();

        try {
            // If there is no matching item, GetItem does not return any data.
            Map<String, AttributeValue> returnedItem =
ddb.getItem(request).item();
            if (returnedItem.isEmpty())
```

```
                System.out.format("No item found with the key %s!\n", key);
            else {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");
                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
 returnedItem.get(key1).toString());
                }
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte GetCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, GetCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new GetCommand({
    TableName: "AngryAnimals",
```

```
    Key: {
      CommonName: "Shoebill",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Obtenha um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "001" },
  },
  ProjectionExpression: "ATTRIBUTE_NAME",
};

// Call DynamoDB to read the item from the table
ddb.getItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
```

```
  } else {
    console.log("Success", data.Item);
  }
});
```

Obtenha um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "EPISODES_TABLE",
  Key: { KEY_NAME: VALUE },
};

docClient.get(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificItem(tableNameVal: String, keyName: String, keyVal:
 String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}
```

- Para obter detalhes da API, consulte a GetItemreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $movie = $service->getItemByKey($tableName, $key);
        echo "\nThe movie {$movie['Item']['title']['S']} was released in
 {$movie['Item']['year']['N']}.\n";

    public function getItemByKey(string $tableName, array $key)
    {
        return $this->dynamoDbClient->getItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
```

```
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Item"]
```

- Para obter detalhes da API, consulte a GetItemReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Gets movie data from the table for a specific movie.
  #
  # @param title [String] The title of the movie.
  # @param year [Integer] The release year of the movie.
  # @return [Hash] The data about the requested movie.
  def get_item(title, year)
    @table.get_item(key: {"year" => year, "title" => title})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't get movie #{title} (#{year}) from table #{@table.name}:\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    oo_item = lo_dyn->getitem(
      iv_tablename                = iv_table_name
      it_key                      = it_key ).
    DATA(lt_attr) = oo_item->get_item( ).
    DATA(lo_title) = lt_attr[ key = 'title' ]-value.
    DATA(lo_year) = lt_attr[ key = 'year' ]-value.
    DATA(lo_rating) = lt_attr[ key = 'rating' ]-value.
    MESSAGE 'Movie name is: ' && lo_title->get_s( )
      && 'Movie year is: ' && lo_year->get_n( )
      && 'Moving rating is: ' && lo_rating->get_n( ) TYPE 'I'.
  CATCH /aws1/cx_dynresourcenotfoundex.
    MESSAGE 'The table or index does not exist' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a GetItemreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Return a `Movie` record describing the specified movie from the Amazon
/// DynamoDB table.
///
/// - Parameters:
///   - title: The movie's title (`String`).
///   - year: The movie's release year (`Int`).
///
/// - Throws: `MoviesError.ItemNotFound` if the movie isn't in the table.
///
/// - Returns: A `Movie` record with the movie's details.
func get(title: String, year: Int) async throws -> Movie {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = GetItemInput(
        key: [
            "year": .n(String(year)),
            "title": .s(title)
        ],
        tableName: self.tableName
    )
    let output = try await client.getItem(input: input)
    guard let item = output.item else {
        throw MoviesError.ItemNotFound
    }

    let movie = try Movie(withItem: item)
    return movie
}
```

- Para obter detalhes da API, consulte GetItema referência da API AWS SDK for Swift.

Obter informações sobre uma tabela do DynamoDB

Os exemplos de código a seguir mostram como obter informações de uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
private static async Task GetTableInformation()
{
    Console.WriteLine("\n*** Retrieving table information ***");

    var response = await Client.DescribeTableAsync(new DescribeTableRequest
    {
        TableName = ExampleTableName
    });

    var table = response.Table;
    Console.WriteLine($"Name: {table.TableName}");
    Console.WriteLine($"# of items: {table.ItemCount}");
    Console.WriteLine($"Provision Throughput (reads/sec): " +
                      $"{table.ProvisionedThroughput.ReadCapacityUnits}");
    Console.WriteLine($"Provision Throughput (writes/sec): " +
                      $"{table.ProvisionedThroughput.WriteCapacityUnits}");
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_describe_table
#
# This function returns the status of a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#
#  Response:
#       - TableStatus:
#     And:
#       0 - Table is active.
#       1 - If it fails.
###############################################################################
function dynamodb_describe_table {
  local table_name
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_describe_table"
    echo "Describe the status of a DynamoDB table."
    echo "  -n table_name  -- The name of the table."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
```

```
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  local table_status
    table_status=$(
      aws dynamodb describe-table \
        --table-name "$table_name" \
        --output text \
        --query 'Table.TableStatus'
    )

   local error_code=${?}

    if [[ $error_code -ne 0 ]]; then
      aws_cli_error_log "$error_code"
      errecho "ERROR: AWS reports describe-table operation failed.$table_status"
      return 1
    fi

  echo "$table_status"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi
```

```
  return 0
}
```

- Para obter detalhes da API, consulte DescribeTableem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Describe an Amazon DynamoDB table.
/*!
  \sa describeTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::describeTable(const Aws::String &tableName,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DescribeTableOutcome &outcome =
 dynamoClient.DescribeTable(
            request);

    if (outcome.IsSuccess()) {
        const Aws::DynamoDB::Model::TableDescription &td =
 outcome.GetResult().GetTable();
        std::cout << "Table name  : " << td.GetTableName() << std::endl;
        std::cout << "Table ARN   : " << td.GetTableArn() << std::endl;
        std::cout << "Status      : "
```

```
                  <<
 Aws::DynamoDB::Model::TableStatusMapper::GetNameForTableStatus(
                         td.GetTableStatus()) << std::endl;
       std::cout << "Item count  : " << td.GetItemCount() << std::endl;
       std::cout << "Size (bytes): " << td.GetTableSizeBytes() << std::endl;

       const Aws::DynamoDB::Model::ProvisionedThroughputDescription &ptd =
 td.GetProvisionedThroughput();
       std::cout << "Throughput" << std::endl;
       std::cout << "  Read Capacity : " << ptd.GetReadCapacityUnits() <<
 std::endl;
       std::cout << "  Write Capacity: " << ptd.GetWriteCapacityUnits() <<
 std::endl;

       const Aws::Vector<Aws::DynamoDB::Model::AttributeDefinition> &ad =
 td.GetAttributeDefinitions();
       std::cout << "Attributes" << std::endl;
       for (const auto &a: ad)
           std::cout << "  " << a.GetAttributeName() << " (" <<

 Aws::DynamoDB::Model::ScalarAttributeTypeMapper::GetNameForScalarAttributeType(
                            a.GetAttributeType()) <<
                     ")" << std::endl;
   }
   else {
       std::cerr << "Failed to describe table: " <<
 outcome.GetError().GetMessage();
   }

   return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como descrever uma tabela

O exemplo a seguir de `describe-table` descreve a tabela `MusicCollection`.

```
aws dynamodb describe-table \
    --table-name MusicCollection
```

Saída:

```
{
    "Table": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 5
        },
        "TableSizeBytes": 0,
        "TableName": "MusicCollection",
        "TableStatus": "ACTIVE",
        "KeySchema": [
            {
                "KeyType": "HASH",
                "AttributeName": "Artist"
            },
            {
                "KeyType": "RANGE",
                "AttributeName": "SongTitle"
            }
        ],
        "ItemCount": 0,
        "CreationDateTime": 1421866952.062
    }
}
```

Para obter mais informações, consulte Descrever uma tabela no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte DescribeTableem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
 exists := true
 _, err := basics.DynamoDbClient.DescribeTable(
  context.TODO(), &dynamodb.DescribeTableInput{TableName:
 aws.String(basics.TableName)},
 )
 if err != nil {
  var notFoundEx *types.ResourceNotFoundException
  if errors.As(err, &notFoundEx) {
   log.Printf("Table %v does not exist.\n", basics.TableName)
   err = nil
  } else {
   log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
 basics.TableName, err)
  }
  exists = false
 }
```

```
 return exists, err
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeDefinition;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableRequest;
import
 software.amazon.awssdk.services.dynamodb.model.ProvisionedThroughputDescription;
import software.amazon.awssdk.services.dynamodb.model.TableDescription;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName>
```

```
                Where:
                    tableName - The Amazon DynamoDB table to get information
about (for example, Music3).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        System.out.format("Getting description for %s\n\n", tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        describeDymamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void describeDymamoDBTable(DynamoDbClient ddb, String
tableName) {
        DescribeTableRequest request = DescribeTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            TableDescription tableInfo = ddb.describeTable(request).table();
            if (tableInfo != null) {
                System.out.format("Table name  : %s\n", tableInfo.tableName());
                System.out.format("Table ARN   : %s\n", tableInfo.tableArn());
                System.out.format("Status      : %s\n", tableInfo.tableStatus());
                System.out.format("Item count  : %d\n", tableInfo.itemCount());
                System.out.format("Size (bytes): %d\n",
tableInfo.tableSizeBytes());

                ProvisionedThroughputDescription throughputInfo =
tableInfo.provisionedThroughput();
                System.out.println("Throughput");
                System.out.format("  Read Capacity : %d\n",
throughputInfo.readCapacityUnits());
```

```
                System.out.format("  Write Capacity: %d\n",
 throughputInfo.writeCapacityUnits());

                List<AttributeDefinition> attributes =
 tableInfo.attributeDefinitions();
                System.out.println("Attributes");
                for (AttributeDefinition a : attributes) {
                    System.out.format("  %s (%s)\n", a.attributeName(),
 a.attributeType());
                }
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("\nDone!");
    }
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { DescribeTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new DescribeTableCommand({
    TableName: "Pastries",
```

```
  });

  const response = await client.send(command);
  console.log(`TABLE NAME: ${response.Table.TableName}`);
  console.log(`TABLE ITEM COUNT: ${response.Table.ItemCount}`);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to retrieve the selected table descriptions
ddb.describeTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Table.KeySchema);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
```

```
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                exists = False
            else:
                logger.error(
                    "Couldn't check for existence of %s. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            self.table = table
        return exists
```

- Para obter detalhes da API, consulte a DescribeTableReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
```

```
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Determines whether a table exists. As a side effect, stores the table in
  # a member variable.
  #
  # @param table_name [String] The name of the table to check.
  # @return [Boolean] True when the table exists; otherwise, False.
  def exists?(table_name)
    @dynamo_resource.client.describe_table(table_name: table_name)
    @logger.debug("Table #{table_name} exists")
  rescue Aws::DynamoDB::Errors::ResourceNotFoundException
    @logger.debug("Table #{table_name} doesn't exist")
    false
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't check for existence of #{table_name}:\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_dyn->describetable( iv_tablename = iv_table_name ).
        DATA(lv_tablename) = oo_result->get_table( )->ask_tablename( ).
        DATA(lv_tablearn) = oo_result->get_table( )->ask_tablearn( ).
        DATA(lv_tablestatus) = oo_result->get_table( )->ask_tablestatus( ).
```

```
        DATA(lv_itemcount) = oo_result->get_table( )->ask_itemcount( ).
        MESSAGE 'The table name is ' && lv_tablename
            && '. The table ARN is ' && lv_tablearn
            && '. The tablestatus is ' && lv_tablestatus
            && '. Item count is ' && lv_itemcount TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table ' && lv_tablename && ' does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTablereferência da API AWS SDK for SAP ABAP.

Listar tabelas do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como listar tabelas do DynamoDB.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    private static async Task ListMyTables()
    {
        Console.WriteLine("\n*** Listing tables ***");

        string lastTableNameEvaluated = null;
        do
        {
            var response = await Client.ListTablesAsync(new ListTablesRequest
            {
                Limit = 2,
                ExclusiveStartTableName = lastTableNameEvaluated
            });

            foreach (var name in response.TableNames)
```

```
            {
                Console.WriteLine(name);
            }

            lastTableNameEvaluated = response.LastEvaluatedTableName;
        } while (lastTableNameEvaluated != null);
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_list_tables
#
# This function lists all the tables in a DynamoDB.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
#############################################################################
function dynamodb_list_tables() {
  response=$(aws dynamodb list-tables \
    --output text \
    --query "TableNames")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi
```

```
  echo "$response" | tr -s "[:space:]" "\n"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
```

```
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte ListTablesem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the Amazon DynamoDB tables for the current AWS account.
/*!
  \sa listTables()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::listTables(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
    listTablesRequest.SetLimit(50);
    do {
        const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamoClient.ListTables(
                listTablesRequest);
```

```
        if (!outcome.IsSuccess()) {
            std::cout << "Error: " << outcome.GetError().GetMessage() <<
 std::endl;
            return false;
        }

        for (const auto &tableName: outcome.GetResult().GetTableNames())
            std::cout << tableName << std::endl;
        listTablesRequest.SetExclusiveStartTableName(
                outcome.GetResult().GetLastEvaluatedTableName());

    } while (!listTablesRequest.GetExclusiveStartTableName().empty());

    return true;
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como listar tabelas

O exemplo de `list-tables` a seguir lista todas as tabelas associadas à conta e região atuais da AWS.

```
aws dynamodb list-tables
```

Saída:

```
{
    "TableNames": [
        "Forum",
        "ProductCatalog",
        "Reply",
        "Thread"
    ]
}
```

Para obter mais informações, consulte Listar nomes de tabela no Guia do desenvolvedor Amazon DynamoDB.

Exemplo 2: como limitar o tamanho da página

O exemplo a seguir retorna uma lista de todas as tabelas existentes, mas recupera apenas um item em cada chamada. Pode ser necessário realizar várias chamadas para obter a lista completa. Limitar o tamanho da página é útil ao executar os comandos da lista em um grande número de recursos, o que pode resultar em um erro de “tempo limite” ao usar o tamanho de página padrão de 1.000.

```
aws dynamodb list-tables \
    --page-size 1
```

Saída:

```
{
    "TableNames": [
        "Forum",
        "ProductCatalog",
        "Reply",
        "Thread"
    ]
}
```

Para obter mais informações, consulte Listar nomes de tabela no Guia do desenvolvedor Amazon DynamoDB.

Exemplo 3: como limitar o número de itens retornados

O exemplo a seguir limita o número de itens retornados para dois. A resposta inclui um valor `NextToken` a ser usado para recuperar a próxima página de resultados.

```
aws dynamodb list-tables \
    --max-items 2
```

Saída:

```
{
    "TableNames": [
        "Forum",
```

```
        "ProductCatalog"
    ],
    "NextToken":
 "abCDeFGhiJKlmnOPqrSTuvwxYZ1aBCdEFghijK7LM51nOpqRSTuv3WxY3ZabC5dEFGhI2Jk3LmnoPQ6RST9"
}
```

Para obter mais informações, consulte Listar nomes de tabela no Guia do desenvolvedor Amazon DynamoDB.

Exemplo 4: como recuperar a próxima página de resultados

O comando a seguir usa o valor `NextToken` de uma chamada anterior feita ao comando `list-tables` para recuperar outra página de resultados. Como a resposta nesse caso não inclui um valor para `NextToken`, sabemos que chegamos ao final dos resultados.

```
aws dynamodb list-tables \
    --starting-token
 abCDeFGhiJKlmnOPqrSTuvwxYZ1aBCdEFghijK7LM51nOpqRSTuv3WxY3ZabC5dEFGhI2Jk3LmnoPQ6RST9
```

Saída:

```
{
    "TableNames": [
        "Reply",
        "Thread"
    ]
}
```

Para obter mais informações, consulte Listar nomes de tabela no Guia do desenvolvedor Amazon DynamoDB.

- Para obter detalhes da API, consulte ListTablesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
 var tableNames []string
 var output *dynamodb.ListTablesOutput
 var err error
 tablePaginator := dynamodb.NewListTablesPaginator(basics.DynamoDbClient,
 &dynamodb.ListTablesInput{})
 for tablePaginator.HasMorePages() {
  output, err = tablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't list tables. Here's why: %v\n", err)
   break
  } else {
   tableNames = append(tableNames, output.TableNames...)
  }
 }
 return tableNames, err
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ListTablesRequest;
import software.amazon.awssdk.services.dynamodb.model.ListTablesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListTables {
    public static void main(String[] args) {
        System.out.println("Listing your Amazon DynamoDB tables:\n");
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
        listAllTables(ddb);
        ddb.close();
    }

    public static void listAllTables(DynamoDbClient ddb) {
        boolean moreTables = true;
        String lastName = null;

        while (moreTables) {
```

```
            try {
                ListTablesResponse response = null;
                if (lastName == null) {
                    ListTablesRequest request =
 ListTablesRequest.builder().build();
                    response = ddb.listTables(request);
                } else {
                    ListTablesRequest request = ListTablesRequest.builder()
                            .exclusiveStartTableName(lastName).build();
                    response = ddb.listTables(request);
                }

                List<String> tableNames = response.tableNames();
                if (tableNames.size() > 0) {
                    for (String curName : tableNames) {
                        System.out.format("* %s\n", curName);
                    }
                } else {
                    System.out.println("No tables found!");
                    System.exit(0);
                }

                lastName = response.lastEvaluatedTableName();
                if (lastName == null) {
                    moreTables = false;
                }

            } catch (DynamoDbException e) {
                System.err.println(e.getMessage());
                System.exit(1);
            }
        }
        System.out.println("\nDone!");
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { ListTablesCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new ListTablesCommand({});

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

// Call DynamoDB to retrieve the list of tables
ddb.listTables({ Limit: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err.code);
  } else {
    console.log("Table names are ", data.TableNames);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllTables() {
    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.listTables(ListTablesRequest {})
        response.tableNames?.forEach { tableName ->
            println("Table name is $tableName")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function listTables($exclusiveStartTableName = "", $limit = 100)
    {
        $this->dynamoDbClient->listTables([
            'ExclusiveStartTableName' => $exclusiveStartTableName,
            'Limit' => $limit,
        ]);
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
```

```
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def list_tables(self):
        """
        Lists the Amazon DynamoDB tables for the current account.

        :return: The list of tables.
        """
        try:
            tables = []
            for table in self.dyn_resource.tables.all():
                print(table.name)
                tables.append(table)
        except ClientError as err:
            logger.error(
                "Couldn't list tables. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tables
```

- Para obter detalhes da API, consulte a ListTablesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determine se uma tabela existe.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Determines whether a table exists. As a side effect, stores the table in
  # a member variable.
  #
  # @param table_name [String] The name of the table to check.
  # @return [Boolean] True when the table exists; otherwise, False.
  def exists?(table_name)
    @dynamo_resource.client.describe_table(table_name: table_name)
    @logger.debug("Table #{table_name} exists")
  rescue Aws::DynamoDB::Errors::ResourceNotFoundException
    @logger.debug("Table #{table_name} doesn't exist")
    false
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't check for existence of #{table_name}:\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
pub async fn list_tables(client: &Client) -> Result<Vec<String>, Error> {
    let paginator = client.list_tables().into_paginator().items().send();
    let table_names = paginator.collect::<Result<Vec<_>, _>>().await?;

    println!("Tables:");

    for name in &table_names {
        println!("  {}", name);
    }

    println!("Found {} tables", table_names.len());
    Ok(table_names)
}
```

Determine se a tabela existe.

```
pub async fn table_exists(client: &Client, table: &str) -> Result<bool, Error> {
    debug!("Checking for table: {table}");
    let table_list = client.list_tables().send().await;

    match table_list {
        Ok(list) => Ok(list.table_names().contains(&table.into())),
        Err(e) => Err(e.into()),
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_dyn->listtables( ).
        " You can loop over the oo_result to get table properties like this.
        LOOP AT oo_result->get_tablenames( ) INTO DATA(lo_table_name).
          DATA(lv_tablename) = lo_table_name->get_value( ).
        ENDLOOP.
        DATA(lv_tablecount) = lines( oo_result->get_tablenames( ) ).
        MESSAGE 'Found ' && lv_tablecount && ' tables' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Get a list of the DynamoDB tables available in the specified Region.
///
/// - Returns: An array of strings listing all of the tables available
///   in the Region specified when the session was created.
public func getTableList() async throws -> [String] {
    var tableList: [String] = []
    var lastEvaluated: String? = nil

    // Iterate over the list of tables, 25 at a time, until we have the
    // names of every table. Add each group to the `tableList` array.
    // Iteration is complete when `output.lastEvaluatedTableName` is `nil`.

    repeat {
        let input = ListTablesInput(
            exclusiveStartTableName: lastEvaluated,
            limit: 25
        )
        let output = try await self.session.listTables(input: input)
        guard let tableNames = output.tableNames else {
            return tableList
        }
        tableList.append(contentsOf: tableNames)
        lastEvaluated = output.lastEvaluatedTableName
    } while lastEvaluated != nil

    return tableList
}
```

- Para obter detalhes da API, consulte ListTablesa referência da API AWS SDK for Swift.

Colocar um item em uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como colocar um item em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX
- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Adds a new item to the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing informtation for
        /// the movie to add to the table.</param>
        /// <param name="tableName">The name of the table where the item will be
 added.</param>
        /// <returns>A Boolean value that indicates the results of adding the
 item.</returns>
        public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
 Movie newMovie, string tableName)
        {
            var item = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new PutItemRequest
            {
                TableName = tableName,
                Item = item,
```

```
            };

            var response = await client.PutItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_put_item
#
# This function puts an item into a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -i item  -- Path to json file containing the item values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_put_item() {
  local table_name item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_put_item"
```

```
  echo "Put an item into a DynamoDB table."
  echo " -n table_name  -- The name of the table."
  echo " -i item  -- Path to json file containing the item values."
  echo ""
}

while getopts "n:i:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    i) item="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$item" ]]; then
  errecho "ERROR: You must provide an item with the -i parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    item:   $item"
iecho ""
iecho ""

response=$(aws dynamodb put-item \
  --table-name "$table_name" \
  --item file://"$item")
```

```
  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports put-item operation failed.$response"
    return 1
  fi

  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

################################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
```

```
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte PutItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Put an item in an Amazon DynamoDB table.
/*!
  \sa putItem()
  \param tableName: The table name.
  \param artistKey: The artist key. This is the partition key for the table.
  \param artistValue: The artist value.
  \param albumTitleKey: The album title key.
  \param albumTitleValue: The album title value.
  \param awardsKey: The awards key.
  \param awardsValue: The awards value.
  \param songTitleKey: The song title key.
  \param songTitleValue: The song title value.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::putItem(const Aws::String &tableName,
                               const Aws::String &artistKey,
                               const Aws::String &artistValue,
                               const Aws::String &albumTitleKey,
                               const Aws::String &albumTitleValue,
                               const Aws::String &awardsKey,
                               const Aws::String &awardsValue,
                               const Aws::String &songTitleKey,
                               const Aws::String &songTitleValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::PutItemRequest putItemRequest;
    putItemRequest.SetTableName(tableName);
```

```
    putItemRequest.AddItem(artistKey,
 Aws::DynamoDB::Model::AttributeValue().SetS(
            artistValue)); // This is the hash key.
    putItemRequest.AddItem(albumTitleKey,
 Aws::DynamoDB::Model::AttributeValue().SetS(
            albumTitleValue));
    putItemRequest.AddItem(awardsKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(awardsValue));
    putItemRequest.AddItem(songTitleKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(songTitleValue));

    const Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
            putItemRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully added Item!" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como adicionar um item a uma tabela

O `put-item` exemplo a seguir adiciona um novo item à MusicCollectiontabela.

```
aws dynamodb put-item \
    --table-name MusicCollection \
    --item file://item.json \
    --return-consumed-capacity TOTAL \
    --return-item-collection-metrics SIZE
```

Conteúdo de `item.json`:

```
{
    "Artist": {"S": "No One You Know"},
    "SongTitle": {"S": "Call Me Today"},
    "AlbumTitle": {"S": "Greatest Hits"}
}
```

Saída:

```
{
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 1.0
    },
    "ItemCollectionMetrics": {
        "ItemCollectionKey": {
            "Artist": {
                "S": "No One You Know"
            }
        },
        "SizeEstimateRangeGB": [
            0.0,
            1.0
        ]
    }
}
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como substituir condicionalmente um item em uma tabela

O exemplo de `put-item` a seguir substitui um item existente na tabela `MusicCollection` somente se o item existente tiver um atributo `AlbumTitle` com o valor `Greatest Hits`. O comando retorna o valor anterior do item.

```
aws dynamodb put-item \
    --table-name MusicCollection \
    --item file://item.json \
    --condition-expression "#A = :A" \
    --expression-attribute-names file://names.json \
```

```
    --expression-attribute-values file://values.json \
    --return-values ALL_OLD
```

Conteúdo de `item.json`:

```
{
    "Artist": {"S": "No One You Know"},
    "SongTitle": {"S": "Call Me Today"},
    "AlbumTitle": {"S": "Somewhat Famous"}
}
```

Conteúdo de `names.json`:

```
{
    "#A": "AlbumTitle"
}
```

Conteúdo de `values.json`:

```
{
    ":A": {"S": "Greatest Hits"}
}
```

Saída:

```
{
    "Attributes": {
        "AlbumTitle": {
            "S": "Greatest Hits"
        },
        "Artist": {
            "S": "No One You Know"
        },
        "SongTitle": {
            "S": "Call Me Today"
        }
    }
}
```

Se a chave já existir, você verá a seguinte saída:

```
A client error (ConditionalCheckFailedException) occurred when calling the
 PutItem operation: The conditional request failed.
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte PutItemem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovie adds a movie the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
 item, err := attributevalue.MarshalMap(movie)
 if err != nil {
  panic(err)
 }
 _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
  TableName: aws.String(basics.TableName), Item: item,
 })
 if err != nil {
  log.Printf("Couldn't add item to table. Here's why: %v\n", err)
```

```
 }
 return err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Coloca um item em uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.PutItemRequest;
import software.amazon.awssdk.services.dynamodb.model.PutItemResponse;
import software.amazon.awssdk.services.dynamodb.model.ResourceNotFoundException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To place items into an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client. See the EnhancedPutItem example.
 */
public class PutItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyVal> <albumtitle> <albumtitleval>
 <awards> <awardsval> <Songtitle> <songtitleval>

                Where:
```

```
                    tableName - The Amazon DynamoDB table in which an item is
placed (for example, Music3).
                    key - The key used in the Amazon DynamoDB table (for example,
Artist).
                    keyval - The key value that represents the item to get (for
example, Famous Band).
                    albumTitle - The Album title (for example, AlbumTitle).
                    AlbumTitleValue - The name of the album (for example, Songs
About Life ).
                    Awards - The awards column (for example, Awards).
                    AwardVal - The value of the awards (for example, 10).
                    SongTitle - The song title (for example, SongTitle).
                    SongTitleVal - The value of the song title (for example,
Happy Day).
                **Warning** This program will  place an item that you specify
into a table!
                """;

       if (args.length != 9) {
           System.out.println(usage);
           System.exit(1);
       }

       String tableName = args[0];
       String key = args[1];
       String keyVal = args[2];
       String albumTitle = args[3];
       String albumTitleValue = args[4];
       String awards = args[5];
       String awardVal = args[6];
       String songTitle = args[7];
       String songTitleVal = args[8];

       Region region = Region.US_EAST_1;
       DynamoDbClient ddb = DynamoDbClient.builder()
               .region(region)
               .build();

       putItemInTable(ddb, tableName, key, keyVal, albumTitle, albumTitleValue,
awards, awardVal, songTitle,
               songTitleVal);
       System.out.println("Done!");
       ddb.close();
   }
```

```
    public static void putItemInTable(DynamoDbClient ddb,
            String tableName,
            String key,
            String keyVal,
            String albumTitle,
            String albumTitleValue,
            String awards,
            String awardVal,
            String songTitle,
            String songTitleVal) {

        HashMap<String, AttributeValue> itemValues = new HashMap<>();
        itemValues.put(key, AttributeValue.builder().s(keyVal).build());
        itemValues.put(songTitle,
 AttributeValue.builder().s(songTitleVal).build());
        itemValues.put(albumTitle,
 AttributeValue.builder().s(albumTitleValue).build());
        itemValues.put(awards, AttributeValue.builder().s(awardVal).build());

        PutItemRequest request = PutItemRequest.builder()
                .tableName(tableName)
                .item(itemValues)
                .build();

        try {
            PutItemResponse response = ddb.putItem(request);
            System.out.println(tableName + " was successfully updated. The
 request id is "
                    + response.responseMetadata().requestId());

        } catch (ResourceNotFoundException e) {
            System.err.format("Error: The Amazon DynamoDB table \"%s\" can't be
 found.\n", tableName);
            System.err.println("Be sure that it exists and that you've typed its
 name correctly!");
            System.exit(1);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte PutCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { PutCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new PutCommand({
    TableName: "HappyAnimals",
    Item: {
      CommonName: "Shiba Inu",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Coloque um item em uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "CUSTOMER_LIST",
  Item: {
    CUSTOMER_ID: { N: "001" },
    CUSTOMER_NAME: { S: "Richard Roe" },
  },
};

// Call DynamoDB to add the item to the table
ddb.putItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Coloque um item em uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Item: {
    HASHKEY: VALUE,
    ATTRIBUTE_1: "STRING_VALUE",
    ATTRIBUTE_2: VALUE_2,
  },
};

docClient.put(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putItemInTable(
    tableNameVal: String,
    key: String,
    keyVal: String,
    albumTitle: String,
```

```
    albumTitleValue: String,
    awards: String,
    awardVal: String,
    songTitle: String,
    songTitleVal: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()

    // Add all content to the table.
    itemValues[key] = AttributeValue.S(keyVal)
    itemValues[songTitle] = AttributeValue.S(songTitleVal)
    itemValues[albumTitle] = AttributeValue.S(albumTitleValue)
    itemValues[awards] = AttributeValue.S(awardVal)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println(" A new item was placed into $tableNameVal.")
    }
}
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
```

```
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }

        $service->putItem([
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
            'TableName' => $tableName,
        ]);

    public function putItem(array $array)
    {
        $this->dynamoDbClient->putItem($array);
    }
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
```

```
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    "year": year,
                    "title": title,
                    "info": {"plot": plot, "rating": Decimal(str(rating))},
                }
            )
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a PutItemReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Adds a movie to the table.
  #
  # @param movie [Hash] The title, year, plot, and rating of the movie.
  def add_item(movie)
    @table.put_item(
      item: {
        "year" => movie[:year],
        "title" => movie[:title],
        "info" => {"plot" => movie[:plot], "rating" => movie[:rating]}})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't add movie #{title} to table #{@table.name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn add_item(client: &Client, item: Item, table: &String) ->
 Result<ItemOut, Error> {
    let user_av = AttributeValue::S(item.username);
    let type_av = AttributeValue::S(item.p_type);
    let age_av = AttributeValue::S(item.age);
    let first_av = AttributeValue::S(item.first);
    let last_av = AttributeValue::S(item.last);

    let request = client
        .put_item()
        .table_name(table)
        .item("username", user_av)
        .item("account_type", type_av)
        .item("age", age_av)
        .item("first_name", first_av)
        .item("last_name", last_av);

    println!("Executing request [{request:?}] to add item...");

    let resp = request.send().await?;

    let attributes = resp.attributes().unwrap();

    let username = attributes.get("username").cloned();
    let first_name = attributes.get("first_name").cloned();
    let last_name = attributes.get("last_name").cloned();
    let age = attributes.get("age").cloned();
    let p_type = attributes.get("p_type").cloned();

    println!(
        "Added user {:?}, {:?} {:?}, age {:?} as {:?} user",
        username, first_name, last_name, age, p_type
```

```
    );

    Ok(ItemOut {
        p_type,
        age,
        username,
        first_name,
        last_name,
    })
}
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA(lo_resp) = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = it_item ).
        MESSAGE '1 row inserted into DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
 TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Add a movie specified as a `Movie` structure to the Amazon DynamoDB
/// table.
///
/// - Parameter movie: The `Movie` to add to the table.
///
func add(movie: Movie) async throws {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    // Get a DynamoDB item containing the movie data.
    let item = try await movie.getAsItem()

    // Send the `PutItem` request to Amazon DynamoDB.

    let input = PutItemInput(
        item: item,
        tableName: self.tableName
    )
    _ = try await client.putItem(input: input)
}

///
/// Return an array mapping attribute names to Amazon DynamoDB attribute
/// values, representing the contents of the `Movie` record as a DynamoDB
```

```
    /// item.
    ///
    /// - Returns: The movie item as an array of type
    ///   `[Swift.String:DynamoDBClientTypes.AttributeValue]`.
    ///
    func getAsItem() async throws ->
 [Swift.String:DynamoDBClientTypes.AttributeValue]  {
        // Build the item record, starting with the year and title, which are
        // always present.

        var item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
            "year": .n(String(self.year)),
            "title": .s(self.title)
        ]

        // Add the `info` field with the rating and/or plot if they're
        // available.

        var details: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]
        if (self.info.rating != nil || self.info.plot != nil) {
            if self.info.rating != nil {
                details["rating"] = .n(String(self.info.rating!))
            }
            if self.info.plot != nil {
                details["plot"] = .s(self.info.plot!)
            }
        }
        item["info"] = .m(details)

        return item
    }
```

- Para obter detalhes da API, consulte PutItema referência da API AWS SDK for Swift.

Consultar uma tabela no DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como consultar uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX

- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        /// <summary>
        /// Queries the table for movies released in a particular year and
        /// then displays the information for the movies returned.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table to query.</param>
        /// <param name="year">The release year for which we want to
        /// view movies.</param>
        /// <returns>The number of movies that match the query.</returns>
        public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient
client, string tableName, int year)
        {
            var movieTable = Table.LoadTable(client, tableName);
            var filter = new QueryFilter("year", QueryOperator.Equal, year);

            Console.WriteLine("\nFind movies released in: {year}:");

            var config = new QueryOperationConfig()
            {
                Limit = 10, // 10 items per page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "title",
                  "year",
                },
                ConsistentRead = true,
                Filter = filter,
            };
```

```
            // Value used to track how many movies match the
            // supplied criteria.
            var moviesFound = 0;

            Search search = movieTable.Query(config);
            do
            {
                var movieList = await search.GetNextSetAsync();
                moviesFound += movieList.Count;

                foreach (var movie in movieList)
                {
                    DisplayDocument(movie);
                }
            }
            while (!search.IsDone);

            return moviesFound;
        }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for .NET.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_query
#
# This function queries a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
```

```
#       -k key_condition_expression -- The key condition expression.
#       -a attribute_names -- Path to JSON file containing the attribute names.
#       -v attribute_values -- Path to JSON file containing the attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###########################################################################
function dynamodb_query() {
  local table_name key_condition_expression attribute_names attribute_values
 projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_query"
    echo "Query a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k key_condition_expression -- The key condition expression."
    echo " -a attribute_names -- Path to JSON file containing the attribute
 names."
    echo " -v attribute_values -- Path to JSON file containing the attribute
 values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:k:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) key_condition_expression="${OPTARG}" ;;
      a) attribute_names="${OPTARG}" ;;
      v) attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
```

```
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$key_condition_expression" ]]; then
    errecho "ERROR: You must provide a key condition expression with the -k
 parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_names" ]]; then
    errecho "ERROR: You must provide a attribute names with the -a parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_values" ]]; then
    errecho "ERROR: You must provide a attribute values with the -v parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values")
  else
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
```

```
      --expression-attribute-values file://"$attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports query operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

#############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
```

```
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte Query na Referência de comandos da AWS CLI.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
//! Perform a query on an Amazon DynamoDB Table and retrieve items.
/*!
  \sa queryItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
```

```
  \param projectionExpression: The projections expression, which is ignored if
 empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 * The partition key attribute is searched with the specified value. By default,
 all fields and values
 * contained in the item are returned. If an optional projection expression is
 * specified on the command line, only the specified fields and values are
 * returned.
 */

bool AwsDoc::DynamoDB::queryItems(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &projectionExpression,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::QueryRequest request;

    request.SetTableName(tableName);

    if (!projectionExpression.empty()) {
        request.SetProjectionExpression(projectionExpression);
    }

    // Set query key condition expression.
    request.SetKeyConditionExpression(partitionKey + "= :valueToMatch");

    // Set Expression AttributeValues.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> attributeValues;
    attributeValues.emplace(":valueToMatch", partitionValue);

    request.SetExpressionAttributeValues(attributeValues);

    bool result = true;

    // "exclusiveStartKey" is used for pagination.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 exclusiveStartKey;
    do {
```

```
        if (!exclusiveStartKey.empty()) {
            request.SetExclusiveStartKey(exclusiveStartKey);
            exclusiveStartKey.clear();
        }
        // Perform Query operation.
        const Aws::DynamoDB::Model::QueryOutcome &outcome =
 dynamoClient.Query(request);
        if (outcome.IsSuccess()) {
            // Reference the retrieved items.
            const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
            if (!items.empty()) {
                std::cout << "Number of items retrieved from Query: " <<
 items.size()
                          << std::endl;
                // Iterate each item and print.
                for (const auto &item: items) {
                    std::cout
                            <<
 "*****************************************************"
                            << std::endl;
                    // Output each retrieved field and its value.
                    for (const auto &i: item)
                        std::cout << i.first << ": " << i.second.GetS() <<
 std::endl;
                }
            }
            else {
                std::cout << "No item found in table: " << tableName <<
 std::endl;
            }

            exclusiveStartKey = outcome.GetResult().GetLastEvaluatedKey();
        }
        else {
            std::cerr << "Failed to Query items: " <<
 outcome.GetError().GetMessage();
            result = false;
            break;
        }
    } while (!exclusiveStartKey.empty());

    return result;
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Exemplo 1: como consultar uma tabela

O exemplo da `query` a seguir consulta itens da tabela `MusicCollection`. A tabela tem uma chave hash-and-range primária (`ArtisteSongTitle`), mas essa consulta especifica apenas o valor da chave de hash. Ela retorna nomes de músicas do artista “No One You Know”.

```
aws dynamodb query \
    --table-name MusicCollection \
    --projection-expression "SongTitle" \
    --key-condition-expression "Artist = :v1" \
    --expression-attribute-values file://expression-attributes.json \
    --return-consumed-capacity TOTAL
```

Conteúdo de `expression-attributes.json`:

```
{
    ":v1": {"S": "No One You Know"}
}
```

Saída:

```
{
    "Items": [
        {
            "SongTitle": {
                "S": "Call Me Today"
            },
            "SongTitle": {
                "S": "Scared of My Shadow"
            }
        }
    ],
    "Count": 2,
```

```
    "ScannedCount": 2,
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 0.5
    }
}
```

Para obter mais informações, consulte Operações de consulta no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como consultar uma tabela usando leituras altamente consistentes e percorrer o índice em ordem decrescente

O exemplo a seguir executa a mesma consulta do primeiro exemplo, mas retorna os resultados na ordem inversa e usa leituras altamente consistentes.

```
aws dynamodb query \
    --table-name MusicCollection \
    --projection-expression "SongTitle" \
    --key-condition-expression "Artist = :v1" \
    --expression-attribute-values file://expression-attributes.json \
    --consistent-read \
    --no-scan-index-forward \
    --return-consumed-capacity TOTAL
```

Conteúdo de `expression-attributes.json`:

```
{
    ":v1": {"S": "No One You Know"}
}
```

Saída:

```
{
    "Items": [
        {
            "SongTitle": {
                "S": "Scared of My Shadow"
            }
        },
        {
            "SongTitle": {
```

```
                "S": "Call Me Today"
            }
        }
    ],
    "Count": 2,
    "ScannedCount": 2,
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 1.0
    }
}
```

Para obter mais informações, consulte Operações de consulta no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 3: como filtrar resultados específicos

O exemplo a seguir consulta o `MusicCollection`, mas exclui os resultados com valores específicos no atributo `AlbumTitle`. Observe que isso não afeta `ScannedCount` ou `ConsumedCapacity` já que o filtro é aplicado após a leitura dos itens.

```
aws dynamodb query \
    --table-name MusicCollection \
    --key-condition-expression "#n1 = :v1" \
    --filter-expression "NOT (#n2 IN (:v2, :v3))" \
    --expression-attribute-names file://names.json \
    --expression-attribute-values file://values.json \
    --return-consumed-capacity TOTAL
```

Conteúdo de `values.json`:

```
{
    ":v1": {"S": "No One You Know"},
    ":v2": {"S": "Blue Sky Blues"},
    ":v3": {"S": "Greatest Hits"}
}
```

Conteúdo de `names.json`:

```
{
    "#n1": "Artist",
```

```
    "#n2": "AlbumTitle"
}
```

Saída:

```
{
    "Items": [
        {
            "AlbumTitle": {
                "S": "Somewhat Famous"
            },
            "Artist": {
                "S": "No One You Know"
            },
            "SongTitle": {
                "S": "Call Me Today"
            }
        }
    ],
    "Count": 1,
    "ScannedCount": 2,
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 0.5
    }
}
```

Para obter mais informações, consulte Operações de consulta no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 4: como recuperar somente uma contagem de itens

O exemplo a seguir recupera uma contagem de itens que correspondem à consulta, mas não recupera os itens em si.

```
aws dynamodb query \
    --table-name MusicCollection \
    --select COUNT \
    --key-condition-expression "Artist = :v1" \
    --expression-attribute-values file://expression-attributes.json
```

Conteúdo de `expression-attributes.json`:

```
{
    ":v1": {"S": "No One You Know"}
}
```

Saída:

```
{
    "Count": 2,
    "ScannedCount": 2,
    "ConsumedCapacity": null
}
```

Para obter mais informações, consulte Operações de consulta no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 5: como consultar um índice

O exemplo a seguir consulta o índice secundário local `AlbumTitleIndex`. A consulta retorna todos os atributos da tabela base projetados no índice secundário local. Ao consultar um índice secundário local ou global, você deve fornecer o nome da tabela base usando o parâmetro `table-name`.

```
aws dynamodb query \
    --table-name MusicCollection \
    --index-name AlbumTitleIndex \
    --key-condition-expression "Artist = :v1" \
    --expression-attribute-values file://expression-attributes.json \
    --select ALL_PROJECTED_ATTRIBUTES \
    --return-consumed-capacity INDEXES
```

Conteúdo de `expression-attributes.json`:

```
{
    ":v1": {"S": "No One You Know"}
}
```

Saída:

```
{
```

```
    "Items": [
        {
            "AlbumTitle": {
                "S": "Blue Sky Blues"
            },
            "Artist": {
                "S": "No One You Know"
            },
            "SongTitle": {
                "S": "Scared of My Shadow"
            }
        },
        {
            "AlbumTitle": {
                "S": "Somewhat Famous"
            },
            "Artist": {
                "S": "No One You Know"
            },
            "SongTitle": {
                "S": "Call Me Today"
            }
        }
    ],
    "Count": 2,
    "ScannedCount": 2,
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 0.5,
        "Table": {
            "CapacityUnits": 0.0
        },
        "LocalSecondaryIndexes": {
            "AlbumTitleIndex": {
                "CapacityUnits": 0.5
            }
        }
    }
}
```

Para obter mais informações, consulte Operações de consulta no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte Query na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// Query gets all movies in the DynamoDB table that were released in the
 specified year.
// The function uses the `expression` package to build the key condition
 expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
 var err error
 var response *dynamodb.QueryOutput
 var movies []Movie
 keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
 expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
 if err != nil {
  log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
 } else {
  queryPaginator := dynamodb.NewQueryPaginator(basics.DynamoDbClient,
 &dynamodb.QueryInput{
   TableName:                aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   KeyConditionExpression:    expr.KeyCondition(),
```

```
  })
  for queryPaginator.HasMorePages() {
   response, err = queryPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
 releaseYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
```

```
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Consulta uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.QueryRequest;
import software.amazon.awssdk.services.dynamodb.model.QueryResponse;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To query items from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client. See the EnhancedQueryRecords example.
 */
public class Query {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <partitionKeyName> <partitionKeyVal>

                Where:
                    tableName - The Amazon DynamoDB table to put the item in (for
 example, Music3).
                    partitionKeyName - The partition key name of the Amazon
 DynamoDB table (for example, Artist).
                    partitionKeyVal - The value of the partition key that should
 match (for example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String partitionKeyName = args[1];
        String partitionKeyVal = args[2];

        // For more information about an alias, see:
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Expressions.ExpressionAttributeNames.html
        String partitionAlias = "#a";

        System.out.format("Querying %s", tableName);
        System.out.println("");
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
```

```
        int count = queryTable(ddb, tableName, partitionKeyName, partitionKeyVal,
 partitionAlias);
        System.out.println("There were " + count + "  record(s) returned");
        ddb.close();
    }

    public static int queryTable(DynamoDbClient ddb, String tableName, String
 partitionKeyName, String partitionKeyVal,
            String partitionAlias) {
        // Set up an alias for the partition key name in case it's a reserved
 word.
        HashMap<String, String> attrNameAlias = new HashMap<String, String>();
        attrNameAlias.put(partitionAlias, partitionKeyName);

        // Set up mapping of the partition name with the value.
        HashMap<String, AttributeValue> attrValues = new HashMap<>();
        attrValues.put(":" + partitionKeyName, AttributeValue.builder()
                .s(partitionKeyVal)
                .build());

        QueryRequest queryReq = QueryRequest.builder()
                .tableName(tableName)
                .keyConditionExpression(partitionAlias + " = :" +
 partitionKeyName)
                .expressionAttributeNames(attrNameAlias)
                .expressionAttributeValues(attrValues)
                .build();

        try {
            QueryResponse response = ddb.query(queryReq);
            return response.count();

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return -1;
    }
}
```

Consulta uma tabela usando o `DynamoDbClient` e um índice secundário.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.QueryRequest;
import software.amazon.awssdk.services.dynamodb.model.QueryResponse;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * Create the Movies table by running the Scenario example and loading the Movie
 * data from the JSON file. Next create a secondary
 * index for the Movies table that uses only the year column. Name the index
 * **year-index**. For more information, see:
 *
 * https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GSI.html
 */
public class QueryItemsUsingIndex {
    public static void main(String[] args) {
        String tableName = "Movies";
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        queryIndex(ddb, tableName);
        ddb.close();
    }

    public static void queryIndex(DynamoDbClient ddb, String tableName) {
        try {
            Map<String, String> expressionAttributesNames = new HashMap<>();
            expressionAttributesNames.put("#year", "year");
            Map<String, AttributeValue> expressionAttributeValues = new
 HashMap<>();
```

```
            expressionAttributeValues.put(":yearValue",
 AttributeValue.builder().n("2013").build());

            QueryRequest request = QueryRequest.builder()
                    .tableName(tableName)
                    .indexName("year-index")
                    .keyConditionExpression("#year = :yearValue")
                    .expressionAttributeNames(expressionAttributesNames)
                    .expressionAttributeValues(expressionAttributeValues)
                    .build();

            System.out.println("=== Movie Titles ===");
            QueryResponse response = ddb.query(request);
            response.items()
                    .forEach(movie ->
 System.out.println(movie.get("title").s()));

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte QueryCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { QueryCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new QueryCommand({
    TableName: "CoffeeCrop",
    KeyConditionExpression:
      "OriginCountry = :originCountry AND RoastDate > :roastDate",
    ExpressionAttributeValues: {
      ":originCountry": "Ethiopia",
      ":roastDate": "2023-05-01",
    },
    ConsistentRead: true,
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  ExpressionAttributeValues: {
    ":s": 2,
    ":e": 9,
    ":topic": "PHRASE",
  },
  KeyConditionExpression: "Season = :s and Episode > :e",
  FilterExpression: "contains (Subtitle, :topic)",
  TableName: "EPISODES_TABLE",
};

docClient.query(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Items);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
suspend fun queryDynTable(
    tableNameVal: String,
```

```
    partitionKeyName: String,
    partitionKeyVal: String,
    partitionAlias: String
): Int {
    val attrNameAlias = mutableMapOf<String, String>()
    attrNameAlias[partitionAlias] = partitionKeyName

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.S(partitionKeyVal)

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
```

```
            ],
        ];
        $result = $service->query($tableName, $birthKey);

    public function query(string $tableName, $key)
    {
        $expressionAttributeValues = [];
        $expressionAttributeNames = [];
        $keyConditionExpression = "";
        $index = 1;
        foreach ($key as $name => $value) {
            $keyConditionExpression .= "#" . array_key_first($value) . " = :v
$index,";
            $expressionAttributeNames["#" . array_key_first($value)] =
 array_key_first($value);
            $hold = array_pop($value);
            $expressionAttributeValues[":v$index"] = [
                array_key_first($hold) => array_pop($hold),
            ];
        }
        $keyConditionExpression = substr($keyConditionExpression, 0, -1);
        $query = [
            'ExpressionAttributeValues' => $expressionAttributeValues,
            'ExpressionAttributeNames' => $expressionAttributeNames,
            'KeyConditionExpression' => $keyConditionExpression,
            'TableName' => $tableName,
        ];
        return $this->dynamoDbClient->query($query);
    }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Consulte itens usando uma expressão de condição de chave.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def query_movies(self, year):
        """
        Queries for movies that were released in the specified year.

        :param year: The year to query.
        :return: The list of movies that were released in the specified year.
        """
        try:
            response =
 self.table.query(KeyConditionExpression=Key("year").eq(year))
        except ClientError as err:
            logger.error(
                "Couldn't query for movies released in %s. Here's why: %s: %s",
                year,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Items"]
```

Consulte itens e projete-os para retornar um subconjunto de dados.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table
```

```
    def query_and_project_movies(self, year, title_bounds):
        """
        Query for movies that were released in a specified year and that have
titles
        that start within a range of letters. A projection expression is used
        to return a subset of data for each movie.

        :param year: The release year to query.
        :param title_bounds: The range of starting letters to query.
        :return: The list of movies.
        """
        try:
            response = self.table.query(
                ProjectionExpression="#yr, title, info.genres, info.actors[0]",
                ExpressionAttributeNames={"#yr": "year"},
                KeyConditionExpression=(
                    Key("year").eq(year)
                    & Key("title").between(
                        title_bounds["first"], title_bounds["second"]
                    )
                ),
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ValidationException":
                logger.warning(
                    "There's a validation error. Here's the message: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            else:
                logger.error(
                    "Couldn't query for movies. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return response["Items"]
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Queries for movies that were released in the specified year.
  #
  # @param year [Integer] The year to query.
  # @return [Array] The list of movies that were released in the specified year.
  def query_items(year)
    response = @table.query(
      key_condition_expression: "#yr = :year",
      expression_attribute_names: {"#yr" => "year"},
      expression_attribute_values: {":year" => year})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't query for movies released in #{year}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    response.items
  end
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Encontre os filmes feitos no ano especificado.

```
pub async fn movies_in_year(
    client: &Client,
    table_name: &str,
    year: u16,
) -> Result<Vec<Movie>, MovieError> {
    let results = client
        .query()
        .table_name(table_name)
        .key_condition_expression("#yr = :yyyy")
        .expression_attribute_names("#yr", "year")
        .expression_attribute_values(":yyyy",
 AttributeValue::N(year.to_string()))
        .send()
        .await?;

    if let Some(items) = results.items {
        let movies = items.iter().map(|v| v.into()).collect();
        Ok(movies)
    } else {
        Ok(vec![])
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        " Query movies for a given year .
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
            ( NEW /aws1/cl_dynattributevalue( iv_n = |{ iv_year }| ) ) ).
        DATA(lt_key_conditions) = VALUE /aws1/cl_dyncondition=>tt_keyconditions(
          ( VALUE /aws1/cl_dyncondition=>ts_keyconditions_maprow(
          key = 'year'
          value = NEW /aws1/cl_dyncondition(
          it_attributevaluelist = lt_attributelist
          iv_comparisonoperator = |EQ|
          ) ) ) ).
        oo_result = lo_dyn->query(
          iv_tablename = iv_table_name
          it_keyconditions = lt_key_conditions ).
        DATA(lt_items) = oo_result->get_items( ).
        "You can loop over the results to get item attributes.
        LOOP AT lt_items INTO DATA(lt_item).
          DATA(lo_title) = lt_item[ key = 'title' ]-value.
          DATA(lo_year) = lt_item[ key = 'year' ]-value.
        ENDLOOP.
        DATA(lv_count) = oo_result->get_count( ).
        MESSAGE 'Item count is: ' && lv_count TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Query na Referência da API do AWS SDK para SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Get all the movies released in the specified year.
///
/// - Parameter year: The release year of the movies to return.
///
/// - Returns: An array of `Movie` objects describing each matching movie.
///
func getMovies(fromYear year: Int) async throws -> [Movie] {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = QueryInput(
        expressionAttributeNames: [
            "#y": "year"
        ],
        expressionAttributeValues: [
            ":y": .n(String(year))
        ],
        keyConditionExpression: "#y = :y",
        tableName: self.tableName
    )
    let output = try await client.query(input: input)

    guard let items = output.items else {
        throw MoviesError.ItemNotFound
```

```
        }

        // Convert the found movies into `Movie` objects and return an array
        // of them.

        var movieList: [Movie] = []
        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }
        return movieList
    }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Swift.

Executar uma instrução PartiQL em uma tabela do DynamoDB usando um AWSSDK

Os exemplos de código a seguir mostram como executar uma instrução PartiQL em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Consultar uma tabela usando o PartiQL

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
        /// <summary>
```

```
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
 movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
 'year': ?}}";

            var response = await Client.ExecuteStatementAsync(new
 ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use uma instrução SELECT para obter um item.

```
        /// <summary>
        /// Uses a PartiQL SELECT statement to retrieve a single movie from the
        /// movie database.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
 GetSingleMovie(string tableName, string movieTitle)
        {
```

```
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }
```

Use uma instrução SELECT para obter uma lista de itens.

```
        /// <summary>
        /// Retrieve multiple movies by year using a SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="year">The year the movies were released.</param>
        /// <returns></returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetMovies(string tableName, int year)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { N = year.ToString() },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });
```

```
            return response.Items;
        }
```

Use uma instrução UPDATE para atualizar um item.

```
        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
 producer, string movieTitle, int year)
        {
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
 = ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
 ExecuteStatementRequest
            {
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use uma instrução DELETE para excluir um único filme.

```
        /// <summary>
        /// Deletes a single movie from the table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
   Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

   // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
   Aws::String title;
   float rating;
   int year;
   Aws::String plot;
   {
       title = askQuestion(
               "Enter the title of a movie you want to add to the table: ");
       year = askQuestionForInt("What year was it released? ");
       rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate
it? ",
                                         1, 10);
       plot = askQuestion("Summarize the plot for me: ");

       Aws::DynamoDB::Model::ExecuteStatementRequest request;
       std::stringstream sqlStream;
       sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                 << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                 << INFO_KEY << "': ?}";

       request.SetStatement(sqlStream.str());

       // Create the parameter attributes.
       Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
       attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
       attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

       Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

       std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
               ALLOCATION_TAG.c_str());
       ratingAttribute->SetN(rating);
       infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

       std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
               ALLOCATION_TAG.c_str());
       plotAttribute->SetS(plot);
       infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
```

```
        attributes.push_back(infoMapAttribute);
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

Use uma instrução SELECT para obter um item.

```
    //  3. Get the data for the movie using a "Select" statement.
(ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
```

```
            // Print the retrieved movie information.
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were
retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }
```

Use uma instrução UPDATE para atualizar um item.

```
    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
```

```
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
        }
    }
```

Use uma instrução DELETE para excluir um item.

```
    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
func (runner PartiQLRunner) AddMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
 }
 return err
}
```

Use uma instrução SELECT para obter um item.

```
// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB
 table by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
```

```
 var movie Movie
 params, err := attributevalue.MarshalList([]interface{}{title, year})
 if err != nil {
  panic(err)
 }
 response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Items[0], &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}
```

Use uma instrução SELECT para obter uma lista de itens e projetar os resultados.

```
// GetAllMovies runs a PartiQL SELECT statement to get all movies from the
 DynamoDB table.
// pageSize is not typically required and is used to show how to paginate the
 results.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies(pageSize int32)
 ([]map[string]interface{}, error) {
 var output []map[string]interface{}
 var response *dynamodb.ExecuteStatementOutput
 var err error
 var nextToken *string
 for moreData := true; moreData; {
  response, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
   Statement: aws.String(
```

```
    fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
   Limit:     aws.Int32(pageSize),
   NextToken: nextToken,
  })
  if err != nil {
   log.Printf("Couldn't get movies. Here's why: %v\n", err)
   moreData = false
  } else {
   var pageOutput []map[string]interface{}
   err = attributevalue.UnmarshalListOfMaps(response.Items, &pageOutput)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
    log.Printf("Got a page of length %v.\n", len(response.Items))
    output = append(output, pageOutput...)
   }
   nextToken = response.NextToken
   moreData = nextToken != nil
  }
 }
 return output, err
}
```

Use uma instrução UPDATE para atualizar um item.

```
// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie
 that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
 params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
```

```
 })
 if err != nil {
  log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
 }
 return err
}
```

Use uma instrução DELETE para excluir um item.

```
// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the
 DynamoDB table.
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
```

```
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: `INSERT INTO Flowers value {'Name':?}`,
    Parameters: ["Rose"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Obtenha um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: "SELECT * FROM CloudTypes WHERE IsStorm=?",
    Parameters: [false],
    ConsistentRead: true,
  });
```

```
  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Atualize um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: "UPDATE EyeColors SET IsRecessive=? where Color=?",
    Parameters: [true, "blue"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Exclua um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
```

```
  const command = new ExecuteStatementCommand({
    Statement: "DELETE FROM PaintColors where Name=?",
    Parameters: ["Purple"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function insertItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ]);
    }

    public function getItemByPartiQL(string $tableName, array $key): Result
    {
        list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);

        return $this->dynamoDbClient->executeStatement([
            'Parameters' => $parameters,
            'Statement' => $statement,
        ]);
```

```
    }

    public function updateItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }

    public function deleteItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PartiQLWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
```

```
        self.dyn_resource = dyn_resource


    def run_partiql(self, statement, params):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because
the
        resource transforms input and output from plain old Python objects
(POPOs) to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statement: The PartiQL statement.
        :param params: The list of PartiQL parameters. These are applied to the
                       statement in the order they are listed.
        :return: The items returned from the statement, if any.
        """
        try:
            output = self.dyn_resource.meta.client.execute_statement(
                Statement=statement, Parameters=params
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute PartiQL '%s' because the table does not
exist.",
                    statement,
                )
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s",
                    statement,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

- Para obter detalhes da API, consulte a ExecuteStatementReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Selecione um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Gets a single record from a table using PartiQL.
  # Note: To perform more fine-grained selects,
  # use the Client.query instance method instead.
  #
  # @param title [String] The title of the movie to search.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def select_item_by_title(title)
    request = {
      statement: "SELECT * FROM \"#{@table.name}\" WHERE title=?",
      parameters: [title]
    }
    @dynamodb.client.execute_statement(request)
  end
```

Atualize um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Updates a single record from a table using PartiQL.
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @param rating [Float] The new rating to assign the title.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def update_rating_by_title(title, year, rating)
    request = {
      statement: "UPDATE \"#{@table.name}\" SET info.rating=? WHERE title=? and
 year=?",
      parameters: [{ "N": rating }, title, year]
    }
    @dynamodb.client.execute_statement(request)
  end
```

Adicione um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Adds a single record to a table using PartiQL.
```

```
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @param plot [String] The plot of the movie.
  # @param rating [Float] The new rating to assign the title.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def insert_item(title, year, plot, rating)
    request = {
      statement: "INSERT INTO \"#{@table.name}\" VALUE {'title': ?, 'year': ?,
 'info': ?}",
      parameters: [title, year, {'plot': plot, 'rating': rating}]
    }
    @dynamodb.client.execute_statement(request)
  end
```

Exclua um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Deletes a single record from a table using PartiQL.
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def delete_item_by_title(title, year)
    request = {
      statement: "DELETE FROM \"#{@table.name}\" WHERE title=? and year=?",
      parameters: [title, year]
    }
    @dynamodb.client.execute_statement(request)
  end
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Ruby da API.

Executar lotes de instruções PartiQL em uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Consultar uma tabela usando lotes de instruções PartiQL

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table into which the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
```

```
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE
{{'title': ?, 'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset +=
25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
                                Parameters = new List<AttributeValue>
                                {
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
                            });
                        }

                        var response = await
Client.BatchExecuteStatementAsync(new BatchExecuteStatementRequest
                        {
                            Statements = statements,
                        });

                        // Wait between batches for movies to be successfully
added.
                        System.Threading.Thread.Sleep(3000);

                        success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;
```

```
                    // Clear the list of statements for the next batch.
                    statements.Clear();
                }
            }
            catch (AmazonDynamoDBException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        return success;
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the DynamoDB table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A generic list of movie objects.</returns>
    public static List<Movie> ImportMovies(string movieFileName)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();
        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

        if (allMovies is not null)
        {
            // Return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }
        else
        {
            return null!;
        }
    }
```

Use lotes de instruções SELECT para obter itens.

```
        /// <summary>
        /// Gets movies from the movie table by
        /// using an Amazon DynamoDB PartiQL SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year1">The year of the first movie.</param>
        /// <param name="year2">The year of the second movie.</param>
        /// <returns>True if successful.</returns>
        public static async Task<bool> GetBatch(
            string tableName,
            string title1,
            string title2,
            int year1,
            int year2)
        {
            var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year
= ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };
```

```
            var response = await Client.BatchExecuteStatementAsync(new
 BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            if (response.Responses.Count > 0)
            {
                response.Responses.ForEach(r =>
                {
                    Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
                });
                return true;
            }
            else
            {
                Console.WriteLine($"Couldn't find either {title1} or {title2}.");
                return false;
            }

        }
```

Use lotes de instruções UPDATE para atualizar itens.

```
        /// <summary>
        /// Updates information for multiple movies.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// movies to be updated.</param>
        /// <param name="producer1">The producer name for the first movie
        /// to update.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year that the first movie was released.</
param>
        /// <param name="producer2">The producer name for the second
        /// movie to update.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year that the second movie was released.</
param>
        /// <returns>A Boolean value that indicates the success of the update.</
returns>
        public static async Task<bool> UpdateBatch(
```

```
            string tableName,
            string producer1,
            string title1,
            int year1,
            string producer2,
            string title2,
            int year2)
        {

            string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer1 },
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer2 },
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use lotes de instruções DELETE para excluir itens.

```
        /// <summary>
        /// Deletes multiple movies using a PartiQL BatchExecuteAsync
        /// statement.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// moves that will be deleted.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year the first movie was released.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year the second movie was released.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeleteBatch(
            string tableName,
            string title1,
            int year1,
            string title2,
            int year2)
        {

            string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND
 year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
```

```
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
```

```
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);

        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/
n) "));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

 attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));

            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute
 = Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
```

```
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

Use lotes de instruções SELECT para obter itens.

```
    // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
```

```
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Use lotes de instruções UPDATE para atualizar itens.

```
    // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)
```

```
    for (size_t i = 0; i < titles.size(); ++i) {
        ratings[i] = askQuestionForFloatRange(
                Aws::String("\nLet's update your the movie, \"") + titles[i] +
                ".\nYou rated it  " + std::to_string(ratings[i])
                + ", what new rating would you give it? ", 1, 10);
    }

    std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);
        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
```

```
            return false;
        }
    }
```

Use lotes de instruções DELETE para excluir itens.

```
    // 6. Delete multiple movies using "Delete" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies
 to the
// DynamoDB table.
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year, movie.Info})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(fmt.Sprintf(
    "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n",
 err)
```

```
 }
 return err
}
```

Use lotes de instruções SELECT para obter itens.

```
// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies
 from
// the DynamoDB table by title and year.
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }

 output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 var outMovies []Movie
 if err != nil {
  log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
 } else {
  for _, response := range output.Responses {
   var movie Movie
   err = attributevalue.UnmarshalMap(response.Item, &movie)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
    outMovies = append(outMovies, movie)
```

```
    }
   }
  }
 return outMovies, err
}
```

Use lotes de instruções UPDATE para atualizar itens.

```
// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the
 rating of
// multiple movies that already exist in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64)
 error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{ratings[index],
 movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
 }
 return err
}
```

Use lotes de instruções DELETE para excluir itens.

```
// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
 movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
 }
 return err
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
```

```
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const breakfastFoods = ["Eggs", "Bacon", "Sausage"];
  const command = new BatchExecuteStatementCommand({
    Statements: breakfastFoods.map((food) => ({
      Statement: `INSERT INTO BreakfastFoods value {'Name':?}`,
      Parameters: [food],
    })),
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Obtenha um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchExecuteStatementCommand({
    Statements: [
      {
        Statement: "SELECT * FROM PepperMeasurements WHERE Unit=?",
        Parameters: ["Teaspoons"],
```

```
        ConsistentRead: true,
      },
      {
        Statement: "SELECT * FROM PepperMeasurements WHERE Unit=?",
        Parameters: ["Grams"],
        ConsistentRead: true,
      },
    ],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Atualize um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const eggUpdates = [
    ["duck", "fried"],
    ["chicken", "omelette"],
  ];
  const command = new BatchExecuteStatementCommand({
    Statements: eggUpdates.map((change) => ({
      Statement: "UPDATE Eggs SET Style=? where Variety=?",
      Parameters: [change[1], change[0]],
    })),
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
```

```
};
```

Exclua um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchExecuteStatementCommand({
    Statements: [
      {
        Statement: "DELETE FROM Flavors where Name=?",
        Parameters: ["Grape"],
      },
      {
        Statement: "DELETE FROM Flavors where Name=?",
        Parameters: ["Strawberry"],
      },
    ],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function getItemByPartiQLBatch(string $tableName, array $keys): Result
    {
        $statements = [];
        foreach ($keys as $key) {
            list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);
            $statements[] = [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ];
        }

        return $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => $statements,
        ]);
    }

    public function insertItemByPartiQLBatch(string $statement, array
 $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function updateItemByPartiQLBatch(string $statement, array
 $parameters)
```

```
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function deleteItemByPartiQLBatch(string $statement, array
 $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
```

```
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statements, param_list):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because
the
        resource transforms input and output from plain old Python objects
(POPOs) to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statements: The batch of PartiQL statements.
        :param param_list: The batch of PartiQL parameters that are associated
with
                           each statement. This list must be in the same order as
the
                           statements.
        :return: The responses returned from running the statements, if any.
        """
        try:
            output = self.dyn_resource.meta.client.batch_execute_statement(
                Statements=[
                    {"Statement": statement, "Parameters": params}
                    for statement, params in zip(statements, param_list)
                ]
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute batch of PartiQL statements because the
table "
                    "does not exist."
                )
            else:
                logger.error(
```

```
                    "Couldn't execute batch of PartiQL statements. Here's why:
%s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

- Para obter detalhes da API, consulte a BatchExecuteStatementReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Leia um lote de itens usando o PartiQL.

```
class DynamoDBPartiQLBatch

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Selects a batch of items from a table using PartiQL
  #
  # @param batch_titles [Array] Collection of movie titles
  # @return [Aws::DynamoDB::Types::BatchExecuteStatementOutput]
```

```
  def batch_execute_select(batch_titles)
    request_items = batch_titles.map do |title, year|
      {
        statement: "SELECT * FROM \"#{@table.name}\" WHERE title=? and year=?",
        parameters: [title, year]
      }
    end
    @dynamodb.client.batch_execute_statement({statements: request_items})
  end
```

Exclua um lote de itens usando o PartiQL.

```
class DynamoDBPartiQLBatch

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Deletes a batch of items from a table using PartiQL
  #
  # @param batch_titles [Array] Collection of movie titles
  # @return [Aws::DynamoDB::Types::BatchExecuteStatementOutput]
  def batch_execute_write(batch_titles)
    request_items = batch_titles.map do |title, year|
      {
        statement: "DELETE FROM \"#{@table.name}\" WHERE title=? and year=?",
        parameters: [title, year]
      }
    end
    @dynamodb.client.batch_execute_statement({statements: request_items})
  end
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Ruby da API.

Verificar uma tabela no DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como verificar uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Acelerar leituras com o DAX
- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        public static async Task<int> ScanTableAsync(
            AmazonDynamoDBClient client,
            string tableName,
            int startYear,
            int endYear)
        {
            var request = new ScanRequest
            {
                TableName = tableName,
                ExpressionAttributeNames = new Dictionary<string, string>
                {
                  { "#yr", "year" },
                },
                ExpressionAttributeValues = new Dictionary<string,
AttributeValue>
                {
                    { ":y_a", new AttributeValue { N = startYear.ToString() } },
                    { ":y_z", new AttributeValue { N = endYear.ToString() } },
                },
                FilterExpression = "#yr between :y_a and :y_z",
```

```
                ProjectionExpression = "#yr, title, info.actors[0],
info.directors, info.running_time_secs",
                Limit = 10 // Set a limit to demonstrate using the
LastEvaluatedKey.
            };

            // Keep track of how many movies were found.
            int foundCount = 0;

            var response = new ScanResponse();
            do
            {
                response = await client.ScanAsync(request);
                foundCount += response.Items.Count;
                response.Items.ForEach(i => DisplayItem(i));
                request.ExclusiveStartKey = response.LastEvaluatedKey;
            }
            while (response.LastEvaluatedKey.Count > 0);
            return foundCount;
        }
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for .NET.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###########################################################################
# function dynamodb_scan
#
# This function scans a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
```

```
#       -f filter_expression  -- The filter expression.
#       -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names.
#       -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_scan() {
  local table_name filter_expression expression_attribute_names
 expression_attribute_values projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_scan"
    echo "Scan a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -f filter_expression  -- The filter expression."
    echo " -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names."
    echo " -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:f:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      f) filter_expression="${OPTARG}" ;;
      a) expression_attribute_names="${OPTARG}" ;;
      v) expression_attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
```

```
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$filter_expression" ]]; then
    errecho "ERROR: You must provide a filter expression with the -f parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_names" ]]; then
    errecho "ERROR: You must provide expression attribute names with the -a
parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_values" ]]; then
    errecho "ERROR: You must provide expression attribute values with the -v
parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values")
  else
    response=$(aws dynamodb scan \
```

```
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports scan operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
```

```
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte Scan na Referência de comandos da AWS CLI.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
//! Scan an Amazon DynamoDB table.
/*!
  \sa scanTable()
```

```
  \param tableName: Name for the DynamoDB table.
  \param projectionExpression: An optional projection expression, ignored if
 empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::scanTable(const Aws::String &tableName,
                                 const Aws::String &projectionExpression,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::ScanRequest request;
    request.SetTableName(tableName);

    if (!projectionExpression.empty())
        request.SetProjectionExpression(projectionExpression);

    // Perform scan on table.
    const Aws::DynamoDB::Model::ScanOutcome &outcome =
 dynamoClient.Scan(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved items.
        const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
        if (!items.empty()) {
            std::cout << "Number of items retrieved from scan: " << items.size()
                      << std::endl;
            // Iterate each item and print.
            for (const Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &itemMap: items) {
                std::cout <<
 "*****************************************************"
                          << std::endl;
                // Output each retrieved field and its value.
                for (const auto &itemEntry: itemMap)
                    std::cout << itemEntry.first << ": " <<
 itemEntry.second.GetS()
                              << std::endl;
            }
        }

        else {
            std::cout << "No item found in table: " << tableName << std::endl;
```

```
        }
    }
    else {
        std::cerr << "Failed to Scan items: " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como verificar uma tabela

O exemplo de `scan` faz uma varredura da tabela `MusicCollection` e restringe os resultados a músicas do artista “No One You Know”. Em cada item, somente o nome do álbum e da música são retornados.

```
aws dynamodb scan \
    --table-name MusicCollection \
    --filter-expression "Artist = :a" \
    --projection-expression "#ST, #AT" \
    --expression-attribute-names file://expression-attribute-names.json \
    --expression-attribute-values file://expression-attribute-values.json
```

Conteúdo de `expression-attribute-names.json`:

```
{
    "#ST": "SongTitle",
    "#AT":"AlbumTitle"
}
```

Conteúdo de `expression-attribute-values.json`:

```
{
    ":a": {"S": "No One You Know"}
```

```
}
```

Saída:

```
{
    "Count": 2,
    "Items": [
        {
            "SongTitle": {
                "S": "Call Me Today"
            },
            "AlbumTitle": {
                "S": "Somewhat Famous"
            }
        },
        {
            "SongTitle": {
                "S": "Scared of My Shadow"
            },
            "AlbumTitle": {
                "S": "Blue Sky Blues"
            }
        }
    ],
    "ScannedCount": 3,
    "ConsumedCapacity": null
}
```

Para obter mais informações, consulte Trabalhar com verificações no DynamoDB no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte Scan na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// Scan gets all movies in the DynamoDB table that were released in a range of
 years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
 var movies []Movie
 var err error
 var response *dynamodb.ScanOutput
 filtEx := expression.Name("year").Between(expression.Value(startYear),
 expression.Value(endYear))
 projEx := expression.NamesList(
  expression.Name("year"), expression.Name("title"),
 expression.Name("info.rating"))
 expr, err :=
 expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
 if err != nil {
  log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
 } else {
  scanPaginator := dynamodb.NewScanPaginator(basics.DynamoDbClient,
 &dynamodb.ScanInput{
   TableName:                aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   FilterExpression:         expr.Filter(),
   ProjectionExpression:     expr.Projection(),
  })
  for scanPaginator.HasMorePages() {
   response, err = scanPaginator.NextPage(context.TODO())
   if err != nil {
```

```
    log.Printf("Couldn't scan for movies released between %v and %v. Here's why:
 %v\n",
     startYear, endYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
```

```
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Escaneia uma tabela do Amazon DynamoDB DynamoDbClientusando.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ScanRequest;
import software.amazon.awssdk.services.dynamodb.model.ScanResponse;
import java.util.Map;
import java.util.Set;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 *
 * To scan items from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client, See the EnhancedScanRecords example.
 */

public class DynamoDBScanItems {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table to get information from
 (for example, Music3).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        scanItems(ddb, tableName);
        ddb.close();
    }

    public static void scanItems(DynamoDbClient ddb, String tableName) {
        try {
            ScanRequest scanRequest = ScanRequest.builder()
                    .tableName(tableName)
                    .build();

            ScanResponse response = ddb.scan(scanRequest);
            for (Map<String, AttributeValue> item : response.items()) {
                Set<String> keys = item.keySet();
                for (String key : keys) {
```

```
                    System.out.println("The key name is " + key + "\n");
                    System.out.println("The value is " + item.get(key).s());
                }
            }

        } catch (DynamoDbException e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte ScanCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, ScanCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ScanCommand({
    ProjectionExpression: "#Name, Color, AvgLifeSpan",
    ExpressionAttributeNames: { "#Name": "Name" },
    TableName: "Birds",
  });
```

```
  const response = await docClient.send(command);
  for (const bird of response.Items) {
    console.log(`${bird.Name} - (${bird.Color}, ${bird.AvgLifeSpan})`);
  }
  return response;
};
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js.
var AWS = require("aws-sdk");
// Set the AWS Region.
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object.
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

const params = {
  // Specify which items in the results are returned.
  FilterExpression: "Subtitle = :topic AND Season = :s AND Episode = :e",
  // Define the expression attribute value, which are substitutes for the values
 you want to compare.
  ExpressionAttributeValues: {
    ":topic": { S: "SubTitle2" },
    ":s": { N: 1 },
    ":e": { N: 2 },
  },
  // Set the projection expression, which are the attributes that you want.
  ProjectionExpression: "Season, Episode, Title, Subtitle",
  TableName: "EPISODES_TABLE",
};

ddb.scan(params, function (err, data) {
```

```
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
    data.Items.forEach(function (element, index, array) {
      console.log(
        "printing",
        element.Title.S + " (" + element.Subtitle.S + ")"
      );
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
suspend fun scanItems(tableNameVal: String) {
    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
```

```
            }
        }
    }
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        $yearsKey = [
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

    public function scan(string $tableName, array $key, string $filters)
    {
        $query = [
            'ExpressionAttributeNames' => ['#year' => 'year'],
            'ExpressionAttributeValues' => [
                ":min" => ['N' => '1990'],
```

```
                ":max" => ['N' => '1999'],
            ],
            'FilterExpression' => "#year between :min and :max",
            'TableName' => $tableName,
        ];
        return $this->dynamoDbClient->scan($query);
    }
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def scan_movies(self, year_range):
        """
        Scans for movies that were released in a range of years.
        Uses a projection expression to return a subset of data for each movie.

        :param year_range: The range of years to retrieve.
        :return: The list of movies released in the specified years.
        """
```

```
        movies = []
        scan_kwargs = {
            "FilterExpression": Key("year").between(
                year_range["first"], year_range["second"]
            ),
            "ProjectionExpression": "#yr, title, info.rating",
            "ExpressionAttributeNames": {"#yr": "year"},
        }
        try:
            done = False
            start_key = None
            while not done:
                if start_key:
                    scan_kwargs["ExclusiveStartKey"] = start_key
                response = self.table.scan(**scan_kwargs)
                movies.extend(response.get("Items", []))
                start_key = response.get("LastEvaluatedKey", None)
                done = start_key is None
        except ClientError as err:
            logger.error(
                "Couldn't scan for movies. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

        return movies
```

- Para ver os detalhes da API, consulte Scan na Referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Scans for movies that were released in a range of years.
  # Uses a projection expression to return a subset of data for each movie.
  #
  # @param year_range [Hash] The range of years to retrieve.
  # @return [Array] The list of movies released in the specified years.
  def scan_items(year_range)
    movies = []
    scan_hash = {
      filter_expression: "#yr between :start_yr and :end_yr",
      projection_expression: "#yr, title, info.rating",
      expression_attribute_names: {"#yr" => "year"},
      expression_attribute_values: {
        ":start_yr" => year_range[:start], ":end_yr" => year_range[:end]}
    }
    done = false
    start_key = nil
    until done
      scan_hash[:exclusive_start_key] = start_key unless start_key.nil?
      response = @table.scan(scan_hash)
      movies.concat(response.items) unless response.items.empty?
      start_key = response.last_evaluated_key
      done = start_key.nil?
    end
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't scan for movies. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    movies
  end
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
pub async fn list_items(client: &Client, table: &str, page_size: Option<i32>) ->
 Result<(), Error> {
    let page_size = page_size.unwrap_or(10);
    let items: Result<Vec<_>, _> = client
        .scan()
        .table_name(table)
        .limit(page_size)
        .into_paginator()
        .items()
        .send()
        .collect()
        .await;

    println!("Items in table (up to {page_size}):");
    for item in items? {
        println!("   {:?}", item);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        " Scan movies for rating greater than or equal to the rating specified
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
            ( NEW /aws1/cl_dynattributevalue( iv_n = |{ iv_rating }| ) ) ).
        DATA(lt_filter_conditions) = VALUE /aws1/
cl_dyncondition=>tt_filterconditionmap(
          ( VALUE /aws1/cl_dyncondition=>ts_filterconditionmap_maprow(
          key = 'rating'
          value = NEW /aws1/cl_dyncondition(
          it_attributevaluelist = lt_attributelist
          iv_comparisonoperator = |GE|
          ) ) ) ).
        oo_scan_result = lo_dyn->scan( iv_tablename = iv_table_name
          it_scanfilter = lt_filter_conditions ).
        DATA(lt_items) = oo_scan_result->get_items( ).
        LOOP AT lt_items INTO DATA(lo_item).
          " You can loop over to get individual attributes.
          DATA(lo_title) = lo_item[ key = 'title' ]-value.
          DATA(lo_year) = lo_item[ key = 'year' ]-value.
        ENDLOOP.
        DATA(lv_count) = oo_scan_result->get_count( ).
        MESSAGE 'Found ' && lv_count && ' items' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Scan na Referência da API do AWS SDK para SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Return an array of `Movie` objects released in the specified range of
    /// years.
    ///
    /// - Parameters:
    ///   - firstYear: The first year of movies to return.
    ///   - lastYear: The last year of movies to return.
    ///   - startKey: A starting point to resume processing; always use `nil`.
    ///
    /// - Returns: An array of `Movie` objects describing the matching movies.
    ///
    /// > Note: The `startKey` parameter is used by this function when
    ///   recursively calling itself, and should always be `nil` when calling
    ///   directly.
    ///
    func getMovies(firstYear: Int, lastYear: Int,
                   startKey: [Swift.String:DynamoDBClientTypes.AttributeValue]? =
nil)
                   async throws -> [Movie] {
        var movieList: [Movie] = []

        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = ScanInput(
```

```
            consistentRead: true,
            exclusiveStartKey: startKey,
            expressionAttributeNames: [
                "#y": "year"            // `year` is a reserved word, so use `#y`
instead.
            ],
            expressionAttributeValues: [
                ":y1": .n(String(firstYear)),
                ":y2": .n(String(lastYear))
            ],
            filterExpression: "#y BETWEEN :y1 AND :y2",
            tableName: self.tableName
        )

        let output = try await client.scan(input: input)

        guard let items = output.items else {
            return movieList
        }

        // Build an array of `Movie` objects for the returned items.

        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }

        // Call this function recursively to continue collecting matching
        // movies, if necessary.

        if output.lastEvaluatedKey != nil {
            let movies = try await self.getMovies(firstYear: firstYear, lastYear:
lastYear,
                        startKey: output.lastEvaluatedKey)
            movieList += movies
        }
        return movieList
    }
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Swift.

Atualizar um item em uma tabela do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar um item em uma tabela do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Updates an existing item in the movies table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information for
        /// the movie to update.</param>
        /// <param name="newInfo">A MovieInfo object that contains the
        /// information that will be changed.</param>
        /// <param name="tableName">The name of the table that contains the
 movie.</param>
        /// <returns>A Boolean value that indicates the success of the
 operation.</returns>
        public static async Task<bool> UpdateItemAsync(
            AmazonDynamoDBClient client,
            Movie newMovie,
            MovieInfo newInfo,
            string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
```

```
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };
            var updates = new Dictionary<string, AttributeValueUpdate>
            {
                ["info.plot"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { S = newInfo.Plot },
                },

                ["info.rating"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { N = newInfo.Rank.ToString() },
                },
            };

            var request = new UpdateItemRequest
            {
                AttributeUpdates = updates,
                Key = key,
                TableName = tableName,
            };

            var response = await client.UpdateItemAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
##############################################################################
# function dynamodb_update_item
#
# This function updates an item in a DynamoDB table.
#
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to update.
#       -e update expression  -- An expression that defines one or more
 attributes to be updated.
#       -v values  -- Path to json file containing the update values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_update_item() {
  local table_name keys update_expression values response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_update_item"
    echo "Update an item in a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to update."
    echo " -e update expression  -- An expression that defines one or more
 attributes to be updated."
    echo " -v values  -- Path to json file containing the update values."
    echo ""
  }

  while getopts "n:k:e:v:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      e) update_expression="${OPTARG}" ;;
      v) values="${OPTARG}" ;;
```

```
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi
if [[ -z "$update_expression" ]]; then
  errecho "ERROR: You must provide an update expression with the -e parameter."
  usage
  return 1
fi

if [[ -z "$values" ]]; then
  errecho "ERROR: You must provide a values json file path the -v parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    keys:   $keys"
iecho "    update_expression:   $update_expression"
iecho "    values:   $values"

response=$(aws dynamodb update-item \
  --table-name "$table_name" \
```

```
    --key file://"$keys" \
    --update-expression "$update_expression" \
    --expression-attribute-values file://"$values")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports update-item operation failed.$response"
    return 1
  fi

  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

################################################################################
# function aws_cli_error_log()
#
```

```
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte UpdateItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Update an Amazon DynamoDB table item.
/*!
  \sa updateItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param attributeKey: The key for the attribute to be updated.
  \param attributeValue: The value for the attribute to be updated.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 *  The example code only sets/updates an attribute value. It processes
 *  the attribute value as a string, even if the value could be interpreted
 *  as a number. Also, the example code does not remove an existing attribute
 *  from the key value.
 */

bool AwsDoc::DynamoDB::updateItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &attributeKey,
                                  const Aws::String &attributeValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // *** Define UpdateItem request arguments.
    // Define TableName argument.
    Aws::DynamoDB::Model::UpdateItemRequest request;
    request.SetTableName(tableName);
```

```
    // Define KeyName argument.
    Aws::DynamoDB::Model::AttributeValue attribValue;
    attribValue.SetS(partitionValue);
    request.AddKey(partitionKey, attribValue);

    // Construct the SET update expression argument.
    Aws::String update_expression("SET #a = :valueA");
    request.SetUpdateExpression(update_expression);

    // Construct attribute name argument.
    Aws::Map<Aws::String, Aws::String> expressionAttributeNames;
    expressionAttributeNames["#a"] = attributeKey;
    request.SetExpressionAttributeNames(expressionAttributeNames);

    // Construct attribute value argument.
    Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
    attributeUpdatedValue.SetS(attributeValue);
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 expressionAttributeValues;
    expressionAttributeValues[":valueA"] = attributeUpdatedValue;
    request.SetExpressionAttributeValues(expressionAttributeValues);

    // Update the item.
    const Aws::DynamoDB::Model::UpdateItemOutcome &outcome =
 dynamoClient.UpdateItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item was updated" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como atualizar um item em uma tabela

O exemplo da `update-item` a seguir atualiza um item da tabela `MusicCollection`. Ele adiciona um novo atributo (`Year`) e modifica o atributo `AlbumTitle`. Todos os atributos no item, conforme aparecem após a atualização, são retornados na resposta.

```
aws dynamodb update-item \
    --table-name MusicCollection \
    --key file://key.json \
    --update-expression "SET #Y = :y, #AT = :t" \
    --expression-attribute-names file://expression-attribute-names.json \
    --expression-attribute-values file://expression-attribute-values.json  \
    --return-values ALL_NEW \
    --return-consumed-capacity TOTAL \
    --return-item-collection-metrics SIZE
```

Conteúdo de `key.json`:

```
{
    "Artist": {"S": "Acme Band"},
    "SongTitle": {"S": "Happy Day"}
}
```

Conteúdo de `expression-attribute-names.json`:

```
{
    "#Y":"Year", "#AT":"AlbumTitle"
}
```

Conteúdo de `expression-attribute-values.json`:

```
{
    ":y":{"N": "2015"},
    ":t":{"S": "Louder Than Ever"}
}
```

Saída:

```
{
    "Attributes": {
        "AlbumTitle": {
            "S": "Louder Than Ever"
        },
        "Awards": {
            "N": "10"
        },
        "Artist": {
            "S": "Acme Band"
        },
        "Year": {
            "N": "2015"
        },
        "SongTitle": {
            "S": "Happy Day"
        }
    },
    "ConsumedCapacity": {
        "TableName": "MusicCollection",
        "CapacityUnits": 3.0
    },
    "ItemCollectionMetrics": {
        "ItemCollectionKey": {
            "Artist": {
                "S": "Acme Band"
            }
        },
        "SizeEstimateRangeGB": [
            0.0,
            1.0
        ]
    }
}
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

Exemplo 2: como atualizar um item de forma condicional

O exemplo a seguir atualiza um item na tabela `MusicCollection`, mas somente se o item existente ainda não tiver um atributo `Year`.

```
aws dynamodb update-item \
    --table-name MusicCollection \
    --key file://key.json \
    --update-expression "SET #Y = :y, #AT = :t" \
    --expression-attribute-names file://expression-attribute-names.json \
    --expression-attribute-values file://expression-attribute-values.json  \
    --condition-expression "attribute_not_exists(#Y)"
```

Conteúdo de `key.json`:

```
{
    "Artist": {"S": "Acme Band"},
    "SongTitle": {"S": "Happy Day"}
}
```

Conteúdo de `expression-attribute-names.json`:

```
{
    "#Y":"Year",
    "#AT":"AlbumTitle"
}
```

Conteúdo de `expression-attribute-values.json`:

```
{
    ":y":{"N": "2015"},
    ":t":{"S": "Louder Than Ever"}
}
```

Se o item já tiver um atributo `Year`, o DynamoDB retornará saída a seguir.

```
An error occurred (ConditionalCheckFailedException) when calling the UpdateItem
 operation: The conditional request failed
```

Para obter mais informações, consulte Gravar um item no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte UpdateItemem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the
 update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
 (map[string]map[string]interface{}, error) {
 var err error
 var response *dynamodb.UpdateItemOutput
 var attributeMap map[string]map[string]interface{}
 update := expression.Set(expression.Name("info.rating"),
 expression.Value(movie.Info["rating"]))
 update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
 expr, err := expression.NewBuilder().WithUpdate(update).Build()
 if err != nil {
  log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
 } else {
  response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
 &dynamodb.UpdateItemInput{
   TableName:                 aws.String(basics.TableName),
   Key:                       movie.GetKey(),
```

```
    ExpressionAttributeNames:  expr.Names(),
    ExpressionAttributeValues: expr.Values(),
    UpdateExpression:          expr.Update(),
    ReturnValues:              types.ReturnValueUpdatedNew,
   })
   if err != nil {
    log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
   } else {
    err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
    if err != nil {
     log.Printf("Couldn't unmarshall update response. Here's why: %v\n", err)
    }
   }
  }
  return attributeMap, err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}
```

```
// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualiza um item em uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.AttributeAction;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.AttributeValueUpdate;
import software.amazon.awssdk.services.dynamodb.model.UpdateItemRequest;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To update an Amazon DynamoDB table using the AWS SDK for Java V2, its better
```

```
 * practice to use the
 * Enhanced Client, See the EnhancedModifyItem example.
 */
public class UpdateItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyVal> <name> <updateVal>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music3).
                    key - The name of the key in the table (for example, Artist).
                    keyVal - The value of the key (for example, Famous Band).
                    name - The name of the column where the value is updated (for
 example, Awards).
                    updateVal - The value used to update an item (for example,
 14).
                 Example:
                    UpdateItem Music3 Artist Famous Band Awards 14
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        String name = args[3];
        String updateVal = args[4];

        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
        updateTableItem(ddb, tableName, key, keyVal, name, updateVal);
        ddb.close();
    }

    public static void updateTableItem(DynamoDbClient ddb,
            String tableName,
            String key,
```

```
            String keyVal,
            String name,
            String updateVal) {

        HashMap<String, AttributeValue> itemKey = new HashMap<>();
        itemKey.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());

        HashMap<String, AttributeValueUpdate> updatedValues = new HashMap<>();
        updatedValues.put(name, AttributeValueUpdate.builder()
                .value(AttributeValue.builder().s(updateVal).build())
                .action(AttributeAction.PUT)
                .build());

        UpdateItemRequest request = UpdateItemRequest.builder()
                .tableName(tableName)
                .key(itemKey)
                .attributeUpdates(updatedValues)
                .build();

        try {
            ddb.updateItem(request);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("The Amazon DynamoDB table was updated!");
    }
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte UpdateCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, UpdateCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new UpdateCommand({
    TableName: "Dogs",
    Key: {
      Breed: "Labrador",
    },
    UpdateExpression: "set Color = :color",
    ExpressionAttributeValues: {
      ":color": "black",
    },
    ReturnValues: "ALL_NEW",
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateTableItem(
    tableNameVal: String,
    keyName: String,
    keyVal: String,
    name: String,
    updateVal: String
) {
    val itemKey = mutableMapOf<String, AttributeValue>()
    itemKey[keyName] = AttributeValue.S(keyVal)

    val updatedValues = mutableMapOf<String, AttributeValueUpdate>()
    updatedValues[name] = AttributeValueUpdate {
        value = AttributeValue.S(updateVal)
        action = AttributeAction.Put
    }

    val request = UpdateItemRequest {
        tableName = tableNameVal
        key = itemKey
        attributeUpdates = updatedValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.updateItem(request)
        println("Item in $tableNameVal was updated")
    }
}
```

- Para obter detalhes da API, consulte a UpdateItemreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "What rating would you like to give {$movie['Item']['title']['S']}?
\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $service->updateItemAttributeByKey($tableName, $key, 'rating', 'N',
 $rating);

    public function updateItemAttributeByKey(
        string $tableName,
        array $key,
        string $attributeName,
        string $attributeType,
        string $newValue
    ) {
        $this->dynamoDbClient->updateItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
            'UpdateExpression' => "set #NV=:NV",
            'ExpressionAttributeNames' => [
                '#NV' => $attributeName,
            ],
            'ExpressionAttributeValues' => [
                ':NV' => [
                    $attributeType => $newValue
                ]
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Atualize um item usando uma expressão de atualização.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to the give the movie.
        :param plot: The updated plot summary to give the movie.
        :return: The fields that were updated, with their new values.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
```

```
                ExpressionAttributeValues={":r": Decimal(str(rating)), ":p":
 plot},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]
```

Atualize um item usando uma expressão de atualização que inclui uma operação aritmética.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def update_rating(self, title, year, rating_change):
        """
        Updates the quality rating of a movie in the table by using an arithmetic
        operation in the update expression. By specifying an arithmetic
 operation,
        you can adjust a value in a single request, rather than first getting its
        value and then setting its new value.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating_change: The amount to add to the current rating for the
 movie.
        :return: The updated rating.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating = info.rating + :val",
```

```
                ExpressionAttributeValues={":val": Decimal(str(rating_change))},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]
```

Atualize um item somente quando ele atender a determinadas condições.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def remove_actors(self, title, year, actor_threshold):
        """
        Removes an actor from a movie, but only when the number of actors is
 greater
        than a specified threshold. If the movie does not list more than the
 threshold,
        no actors are removed.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param actor_threshold: The threshold of actors to check.
        :return: The movie data after the update.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="remove info.actors[0]",
                ConditionExpression="size(info.actors) > :num",
                ExpressionAttributeValues={":num": actor_threshold},
```

```
                ReturnValues="ALL_NEW",
            )
        except ClientError as err:
            if err.response["Error"]["Code"] ==
 "ConditionalCheckFailedException":
                logger.warning(
                    "Didn't update %s because it has fewer than %s actors.",
                    title,
                    actor_threshold + 1,
                )
            else:
                logger.error(
                    "Couldn't update movie %s. Here's why: %s: %s",
                    title,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return response["Attributes"]
```

- Para obter detalhes da API, consulte a UpdateItemReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
```

```
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Updates rating and plot data for a movie in the table.
  #
  # @param movie [Hash] The title, year, plot, rating of the movie.
  def update_item(movie)

    response = @table.update_item(
      key: {"year" => movie[:year], "title" => movie[:title]},
      update_expression: "set info.rating=:r",
      expression_attribute_values: { ":r" => movie[:rating] },
      return_values: "UPDATED_NEW")
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't update movie #{movie[:title]} (#{movie[:year]}) in table
#{@table.name}\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    response.attributes
  end
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_output = lo_dyn->updateitem(
          iv_tablename        = iv_table_name
          it_key              = it_item_key
          it_attributeupdates = it_attribute_updates ).
```

```
        MESSAGE '1 item updated in DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateItemreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Update the specified movie with new `rating` and `plot` information.
    ///
    /// - Parameters:
    ///   - title: The title of the movie to update.
    ///   - year: The release year of the movie to update.
    ///   - rating: The new rating for the movie.
    ///   - plot: The new plot summary string for the movie.
    ///
    /// - Returns: An array of mappings of attribute names to their new
    ///   listing each item actually changed. Items that didn't need to change
```

```
    ///   aren't included in this list. `nil` if no changes were made.
    ///
    func update(title: String, year: Int, rating: Double? = nil, plot: String? =
nil) async throws
                -> [Swift.String:DynamoDBClientTypes.AttributeValue]? {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Build the update expression and the list of expression attribute
        // values. Include only the information that's changed.

        var expressionParts: [String] = []
        var attrValues: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]

        if rating != nil {
            expressionParts.append("info.rating=:r")
            attrValues[":r"] = .n(String(rating!))
        }
        if plot != nil {
            expressionParts.append("info.plot=:p")
            attrValues[":p"] = .s(plot!)
        }
        let expression: String = "set \(expressionParts.joined(separator: ", "))"

        let input = UpdateItemInput(
            // Create substitution tokens for the attribute values, to ensure
            // no conflicts in expression syntax.
            expressionAttributeValues: attrValues,
            // The key identifying the movie to update consists of the release
            // year and title.
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            returnValues: .updatedNew,
            tableName: self.tableName,
            updateExpression: expression
        )
        let output = try await client.updateItem(input: input)

        guard let attributes: [Swift.String:DynamoDBClientTypes.AttributeValue] =
output.attributes else {
            throw MoviesError.InvalidAttributes
```

```
        }
        return attributes
    }
```

- Para obter detalhes da API, consulte UpdateItema referência da API AWS SDK for Swift.

Gravar um lote de itens do DynamoDB usando um AWS SDK

Os exemplos de códigos a seguir mostram como gravar um lote de itens do DynamoDB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de tabelas, itens e consultas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Grava um lote de itens na tabela de filmes.

```
        /// <summary>
        /// Loads the contents of a JSON file into a list of movies to be
        /// added to the DynamoDB table.
        /// </summary>
        /// <param name="movieFileName">The full path to the JSON file.</param>
        /// <returns>A generic list of movie objects.</returns>
        public static List<Movie> ImportMovies(string movieFileName)
        {
            if (!File.Exists(movieFileName))
            {
                return null;
            }
```

```
            using var sr = new StreamReader(movieFileName);
            string json = sr.ReadToEnd();
            var allMovies = JsonSerializer.Deserialize<List<Movie>>(
                json,
                new JsonSerializerOptions
                {
                    PropertyNameCaseInsensitive = true
                });

            // Now return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }

        /// <summary>
        /// Writes 250 items to the movie table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="movieFileName">A string containing the full path to
        /// the JSON file containing movie data.</param>
        /// <returns>A long integer value representing the number of movies
        /// imported from the JSON file.</returns>
        public static async Task<long> BatchWriteItemsAsync(
            AmazonDynamoDBClient client,
            string movieFileName)
        {
            var movies = ImportMovies(movieFileName);
            if (movies is null)
            {
                Console.WriteLine("Couldn't find the JSON file with movie
data.");
                return 0;
            }

            var context = new DynamoDBContext(client);

            var movieBatch = context.CreateBatchWrite<Movie>();
            movieBatch.AddPutItems(movies);

            Console.WriteLine("Adding imported movies to the table.");
            await movieBatch.ExecuteAsync();

            return movies.Count;
        }
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_batch_write_item
#
# This function writes a batch of items into a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the items to write.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
################################################################################
function dynamodb_batch_write_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_write_item"
    echo "Write a batch of items into a DynamoDB table."
    echo " -i item  -- Path to json file containing the items to write."
    echo ""
  }
```

```
  while getopts "i:h" option; do
    case "${option}" in
      i) item="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    item:   $item"
  iecho ""

  response=$(aws dynamodb batch-write-item \
    --request-items file://"$item")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
```

```
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte BatchWriteItemem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Batch write items from a JSON file.
/*!
  \sa batchWriteItem()
  \param jsonFilePath: JSON file path.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

/*
 * The input for this routine is a JSON file that you can download from the
 following URL:
```

```
 * https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
SampleData.html.
 *
 * The JSON data uses the BatchWriteItem API request syntax. The JSON strings are
 * converted to AttributeValue objects. These AttributeValue objects will then
 generate
 * JSON strings when constructing the BatchWriteItem request, essentially
 outputting
 * their input.
 *
 * This is perhaps an artificial example, but it demonstrates the APIs.
 */

bool AwsDoc::DynamoDB::batchWriteItem(const Aws::String &jsonFilePath,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    std::ifstream fileStream(jsonFilePath);

    if (!fileStream) {
        std::cerr << "Error: could not open file '" << jsonFilePath << "'."
                  << std::endl;
    }

    std::stringstream stringStream;
    stringStream << fileStream.rdbuf();
    Aws::Utils::Json::JsonValue jsonValue(stringStream);

    Aws::DynamoDB::Model::BatchWriteItemRequest batchWriteItemRequest;
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> level1Map =
 jsonValue.View().GetAllObjects();
    for (const auto &level1Entry: level1Map) {
        const Aws::Utils::Json::JsonView &entriesView = level1Entry.second;
        const Aws::String &tableName = level1Entry.first;
        // The JSON entries at this level are as follows:
        //  key - table name
        //  value - list of request objects
        if (!entriesView.IsListType()) {
            std::cerr << "Error: JSON file entry '"
                      << tableName << "' is not a list." << std::endl;
            continue;
        }

        Aws::Utils::Array<Aws::Utils::Json::JsonView> entries =
 entriesView.AsArray();
```

```
        Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;
        if (AwsDoc::DynamoDB::addWriteRequests(tableName, entries,
                                               writeRequests)) {
            batchWriteItemRequest.AddRequestItems(tableName, writeRequests);
        }
    }

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchWriteItemOutcome outcome =
 dynamoClient.BatchWriteItem(
            batchWriteItemRequest);

    if (outcome.IsSuccess()) {
        std::cout << "DynamoDB::BatchWriteItem was successful." << std::endl;
    }
    else {
        std::cerr << "Error with DynamoDB::BatchWriteItem. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return true;
}

//! Convert requests in JSON format to a vector of WriteRequest objects.
/*!
  \sa addWriteRequests()
  \param tableName: Name of the table for the write operations.
  \param requestsJson: Request data in JSON format.
  \param writeRequests: Vector to receive the WriteRequest objects.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::addWriteRequests(const Aws::String &tableName,
                                        const
 Aws::Utils::Array<Aws::Utils::Json::JsonView> &requestsJson,

 Aws::Vector<Aws::DynamoDB::Model::WriteRequest> &writeRequests) {
    for (size_t i = 0; i < requestsJson.GetLength(); ++i) {
        const Aws::Utils::Json::JsonView &requestsEntry = requestsJson[i];
        if (!requestsEntry.IsObject()) {
            std::cerr << "Error: incorrect requestsEntry type "
                      << requestsEntry.WriteReadable() << std::endl;
```

```
            return false;
        }

        Aws::Map<Aws::String, Aws::Utils::Json::JsonView> requestsMap =
 requestsEntry.GetAllObjects();

        for (const auto &request: requestsMap) {
            const Aws::String &requestType = request.first;
            const Aws::Utils::Json::JsonView &requestJsonView = request.second;

            if (requestType == "PutRequest") {
                if (!requestJsonView.ValueExists("Item")) {
                    std::cerr << "Error: item key missing for requests "
                              << requestJsonView.WriteReadable() << std::endl;
                    return false;
                }
                Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 attributes;
                if (!getAttributeObjectsMap(requestJsonView.GetObject("Item"),
                                            attributes)) {
                    std::cerr << "Error getting attributes "
                              << requestJsonView.WriteReadable() << std::endl;
                    return false;
                }

                Aws::DynamoDB::Model::PutRequest putRequest;
                putRequest.SetItem(attributes);
                writeRequests.push_back(
                        Aws::DynamoDB::Model::WriteRequest().WithPutRequest(
                                putRequest));
            }
            else {
                std::cerr << "Error: unimplemented request type '" << requestType
                          << "'." << std::endl;
            }
        }
    }

    return true;
}

//! Generate a map of AttributeValue objects from JSON records.
/*!
  \sa getAttributeObjectsMap()
```

```
  \param jsonView: JSONView of attribute records.
  \param writeRequests: Map to receive the AttributeValue objects.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::getAttributeObjectsMap(const Aws::Utils::Json::JsonView
 &jsonView,
                                          Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &attributes) {
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> objectsMap =
 jsonView.GetAllObjects();
    for (const auto &entry: objectsMap) {
        const Aws::String &attributeKey = entry.first;
        const Aws::Utils::Json::JsonView &attributeJsonView = entry.second;

        if (!attributeJsonView.IsObject()) {
            std::cerr << "Error: attribute not an object "
                      << attributeJsonView.WriteReadable() << std::endl;
            return false;
        }

        attributes.emplace(attributeKey,

 Aws::DynamoDB::Model::AttributeValue(attributeJsonView));
    }

    return true;
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como adicionar vários itens a uma tabela

O exemplo de `batch-write-item` a seguir adiciona três novos itens à tabela `MusicCollection` usando um lote de três solicitações `PutItem`. Ele também solicita

informações sobre o número de unidades de capacidade de gravação consumidas pela operação e quaisquer coleções de itens modificadas pela operação.

```
aws dynamodb batch-write-item \
    --request-items file://request-items.json \
    --return-consumed-capacity INDEXES \
    --return-item-collection-metrics SIZE
```

Conteúdo de `request-items.json`:

```
{
    "MusicCollection": [
        {
            "PutRequest": {
                "Item": {
                    "Artist": {"S": "No One You Know"},
                    "SongTitle": {"S": "Call Me Today"},
                    "AlbumTitle": {"S": "Somewhat Famous"}
                }
            }
        },
        {
            "PutRequest": {
                "Item": {
                    "Artist": {"S": "Acme Band"},
                    "SongTitle": {"S": "Happy Day"},
                    "AlbumTitle": {"S": "Songs About Life"}
                }
            }
        },
        {
            "PutRequest": {
                "Item": {
                    "Artist": {"S": "No One You Know"},
                    "SongTitle": {"S": "Scared of My Shadow"},
                    "AlbumTitle": {"S": "Blue Sky Blues"}
                }
            }
        }
    ]
}
```

Saída:

```
{
    "UnprocessedItems": {},
    "ItemCollectionMetrics": {
        "MusicCollection": [
            {
                "ItemCollectionKey": {
                    "Artist": {
                        "S": "No One You Know"
                    }
                },
                "SizeEstimateRangeGB": [
                    0.0,
                    1.0
                ]
            },
            {
                "ItemCollectionKey": {
                    "Artist": {
                        "S": "Acme Band"
                    }
                },
                "SizeEstimateRangeGB": [
                    0.0,
                    1.0
                ]
            }
        ]
    },
    "ConsumedCapacity": [
        {
            "TableName": "MusicCollection",
            "CapacityUnits": 6.0,
            "Table": {
                "CapacityUnits": 3.0
            },
            "LocalSecondaryIndexes": {
                "AlbumTitleIndex": {
                    "CapacityUnits": 3.0
                }
            }
        }
    ]
}
```

Para obter mais informações, consulte Operações em lote no Guia do desenvolvedor do Amazon DynamoDB.

- Para obter detalhes da API, consulte BatchWriteItemem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int,
 error) {
 var err error
 var item map[string]types.AttributeValue
 written := 0
 batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
 start := 0
 end := start + batchSize
 for start < maxMovies && start < len(movies) {
  var writeReqs []types.WriteRequest
  if end > len(movies) {
```

```
    end = len(movies)
   }
   for _, movie := range movies[start:end] {
    item, err = attributevalue.MarshalMap(movie)
    if err != nil {
     log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
 movie.Title, err)
    } else {
     writeReqs = append(
      writeReqs,
      types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
     )
    }
   }
   _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
 &dynamodb.BatchWriteItemInput{
    RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
   if err != nil {
    log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
 basics.TableName, err)
   } else {
    written += len(writeReqs)
   }
   start = end
   end += batchSize
  }

  return written, err
}



// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
```

```
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Insere muitos itens em uma tabela usando o cliente de serviço.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchWriteItemRequest;
import software.amazon.awssdk.services.dynamodb.model.BatchWriteItemResponse;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
```

```
import software.amazon.awssdk.services.dynamodb.model.PutRequest;
import software.amazon.awssdk.services.dynamodb.model.WriteRequest;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class BatchWriteItems {
    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """;

        String tableName = "Music";
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        addBatchItems(dynamoDbClient, tableName);
    }

    public static void addBatchItems(DynamoDbClient dynamoDbClient, String
 tableName) {
        // Specify the updates you want to perform.
        List<WriteRequest> writeRequests = new ArrayList<>();

        // Set item 1.
        Map<String, AttributeValue> item1Attributes = new HashMap<>();
```

```
        item1Attributes.put("Artist",
 AttributeValue.builder().s("Artist1").build());
        item1Attributes.put("Rating", AttributeValue.builder().s("5").build());
        item1Attributes.put("Comments", AttributeValue.builder().s("Great
 song!").build());
        item1Attributes.put("SongTitle",
 AttributeValue.builder().s("SongTitle1").build());

 writeRequests.add(WriteRequest.builder().putRequest(PutRequest.builder().item(item1Attri

        // Set item 2.
        Map<String, AttributeValue> item2Attributes = new HashMap<>();
        item2Attributes.put("Artist",
 AttributeValue.builder().s("Artist2").build());
        item2Attributes.put("Rating", AttributeValue.builder().s("4").build());
        item2Attributes.put("Comments", AttributeValue.builder().s("Nice
 melody.").build());
        item2Attributes.put("SongTitle",
 AttributeValue.builder().s("SongTitle2").build());

 writeRequests.add(WriteRequest.builder().putRequest(PutRequest.builder().item(item2Attri

        try {
            // Create the BatchWriteItemRequest.
            BatchWriteItemRequest batchWriteItemRequest =
 BatchWriteItemRequest.builder()
                .requestItems(Map.of(tableName, writeRequests))
                .build();

            // Execute the BatchWriteItem operation.
            BatchWriteItemResponse batchWriteItemResponse =
 dynamoDbClient.batchWriteItem(batchWriteItemRequest);

            // Process the response.
            System.out.println("Batch write successful: " +
 batchWriteItemResponse);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Insira vários itens em uma tabela usando o cliente aprimorado.

```
import com.example.dynamodb.Customer;
import com.example.dynamodb.Music;
import software.amazon.awssdk.enhanced.dynamodb.DynamoDbEnhancedClient;
import software.amazon.awssdk.enhanced.dynamodb.DynamoDbTable;
import software.amazon.awssdk.enhanced.dynamodb.Key;
import software.amazon.awssdk.enhanced.dynamodb.TableSchema;
import
 software.amazon.awssdk.enhanced.dynamodb.model.BatchWriteItemEnhancedRequest;
import software.amazon.awssdk.enhanced.dynamodb.model.WriteBatch;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import java.time.Instant;
import java.time.LocalDate;
import java.time.LocalDateTime;
import java.time.ZoneOffset;

/*
 * Before running this code example, create an Amazon DynamoDB table named
 Customer with these columns:
 *   - id - the id of the record that is the key
 *   - custName - the customer name
 *   - email - the email value
 *   - registrationDate - an instant value when the item was added to the table
 *
 * Also, ensure that you have set up your development environment, including your
 credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class EnhancedBatchWriteItems {
        public static void main(String[] args) {
                Region region = Region.US_EAST_1;
                DynamoDbClient ddb = DynamoDbClient.builder()
                                .region(region)
                                .build();
```

```
                DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
                                .dynamoDbClient(ddb)
                                .build();
                putBatchRecords(enhancedClient);
                ddb.close();
        }

        public static void putBatchRecords(DynamoDbEnhancedClient enhancedClient)
{
                try {
                        DynamoDbTable<Customer> customerMappedTable =
enhancedClient.table("Customer",
                                        TableSchema.fromBean(Customer.class));
                        DynamoDbTable<Music> musicMappedTable =
enhancedClient.table("Music",
                                        TableSchema.fromBean(Music.class));
                        LocalDate localDate = LocalDate.parse("2020-04-07");
                        LocalDateTime localDateTime = localDate.atStartOfDay();
                        Instant instant =
localDateTime.toInstant(ZoneOffset.UTC);

                        Customer record2 = new Customer();
                        record2.setCustName("Fred Pink");
                        record2.setId("id110");
                        record2.setEmail("fredp@noserver.com");
                        record2.setRegistrationDate(instant);

                        Customer record3 = new Customer();
                        record3.setCustName("Susan Pink");
                        record3.setId("id120");
                        record3.setEmail("spink@noserver.com");
                        record3.setRegistrationDate(instant);

                        Customer record4 = new Customer();
                        record4.setCustName("Jerry orange");
                        record4.setId("id101");
                        record4.setEmail("jorange@noserver.com");
                        record4.setRegistrationDate(instant);

                        BatchWriteItemEnhancedRequest
batchWriteItemEnhancedRequest = BatchWriteItemEnhancedRequest
                                        .builder()
                                        .writeBatches(
```

```
 WriteBatch.builder(Customer.class) // add items to the Customer

         // table

 .mappedTableResource(customerMappedTable)

 .addPutItem(builder -> builder.item(record2))

 .addPutItem(builder -> builder.item(record3))

 .addPutItem(builder -> builder.item(record4))
                                                                    .build(),

 WriteBatch.builder(Music.class) // delete an item from the Music

       // table

 .mappedTableResource(musicMappedTable)

 .addDeleteItem(builder -> builder.key(

       Key.builder().partitionValue(

                        "Famous Band")

                        .build()))
                                                                    .build())
                                        .build();

                        // Add three items to the Customer table and delete one
 item from the Music
                        // table.

 enhancedClient.batchWriteItem(batchWriteItemEnhancedRequest);
                        System.out.println("done");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchWrite.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import {
  BatchWriteCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";
import { readFileSync } from "fs";

// These modules are local to our GitHub repository. We recommend cloning
// the project from GitHub if you want to run this example.
// For more information, see https://github.com/awsdocs/aws-doc-sdk-examples.
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { chunkArray } from "@aws-sdk-examples/libs/utils/util-array.js";

const dirname = dirnameFromMetaUrl(import.meta.url);

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const file = readFileSync(
    `${dirname}../../../../../resources/sample_files/movies.json`,
  );
```

```
  const movies = JSON.parse(file.toString());

  // chunkArray is a local convenience function. It takes an array and returns
  // a generator function. The generator function yields every N items.
  const movieChunks = chunkArray(movies, 25);

  // For every chunk of 25 movies, make one BatchWrite request.
  for (const chunk of movieChunks) {
    const putRequests = chunk.map((movie) => ({
      PutRequest: {
        Item: movie,
      },
    }));

    const command = new BatchWriteCommand({
      RequestItems: {
        // An existing table is required. A composite key of 'title' and 'year'
 is recommended
        // to account for duplicate titles.
        ["BatchWriteMoviesTable"]: putRequests,
      },
    });

    await docClient.send(command);
  }
};
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: [
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
          },
        },
      },
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
          },
        },
      },
    ],
  },
};

ddb.batchWriteItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function writeBatch(string $TableName, array $Batch, int $depth = 2)
    {
        if (--$depth <= 0) {
            throw new Exception("Max depth exceeded. Please try with fewer batch
 items or increase depth.");
        }

        $marshal = new Marshaler();
        $total = 0;
        foreach (array_chunk($Batch, 25) as $Items) {
            foreach ($Items as $Item) {
                $BatchWrite['RequestItems'][$TableName][] = ['PutRequest' =>
 ['Item' => $marshal->marshalItem($Item)]];
            }
            try {
                echo "Batching another " . count($Items) . " for a total of " .
 ($total += count($Items)) . " items!\n";
                $response = $this->dynamoDbClient->batchWriteItem($BatchWrite);
                $BatchWrite = [];
            } catch (Exception $e) {
                echo "uh oh...";
                echo $e->getMessage();
                die();
            }
            if ($total >= 250) {
                echo "250 movies is probably enough. Right? We can stop there.
\n";
                break;
            }
        }
    }
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def write_batch(self, movies):
        """
        Fills an Amazon DynamoDB table with the specified data, using the Boto3
        Table.batch_writer() function to put the items in the table.
        Inside the context manager, Table.batch_writer builds a list of
        requests. On exiting the context manager, Table.batch_writer starts
 sending
        batches of write requests to Amazon DynamoDB and automatically
        handles chunking, buffering, and retrying.

        :param movies: The data to put in the table. Each item must contain at
 least
                       the keys required by the schema that was specified when
 the
                       table was created.
```

```
        """
        try:
            with self.table.batch_writer() as writer:
                for movie in movies:
                    writer.put_item(Item=movie)
        except ClientError as err:
            logger.error(
                "Couldn't load data into table %s. Here's why: %s: %s",
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a BatchWriteItemReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Fills an Amazon DynamoDB table with the specified data. Items are sent in
  # batches of 25 until all items are written.
```

```
 #
 # @param movies [Enumerable] The data to put in the table. Each item must
contain at least
 #                            the keys required by the schema that was specified
when the
 #                            table was created.
 def write_batch(movies)
   index = 0
   slice_size = 25
   while index < movies.length
     movie_items = []
     movies[index, slice_size].each do |movie|
       movie_items.append({put_request: { item: movie }})
     end
     @dynamo_resource.client.batch_write_item({request_items: { @table.name =>
movie_items }})
     index += slice_size
   end
 rescue Aws::DynamoDB::Errors::ServiceError => e
   puts(
     "Couldn't load data into table #{@table.name}. Here's why:")
   puts("\t#{e.code}: #{e.message}")
   raise
 end
```

- Para obter detalhes da API, consulte BatchWriteItem a Referência AWS SDK for Ruby da API.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Populate the movie database from the specified JSON file.
    ///
    /// - Parameter jsonPath: Path to a JSON file containing movie data.
    ///
    func populate(jsonPath: String) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Create a Swift `URL` and use it to load the file into a `Data`
        // object. Then decode the JSON into an array of `Movie` objects.

        let fileUrl = URL(fileURLWithPath: jsonPath)
        let jsonData = try Data(contentsOf: fileUrl)

        var movieList = try JSONDecoder().decode([Movie].self, from: jsonData)

        // Truncate the list to the first 200 entries or so for this example.

        if movieList.count > 200 {
            movieList = Array(movieList[...199])
        }

        // Before sending records to the database, break the movie list into
        // 25-entry chunks, which is the maximum size of a batch item request.

        let count = movieList.count
        let chunks = stride(from: 0, to: count, by: 25).map {
            Array(movieList[$0 ..< Swift.min($0 + 25, count)])
        }

        // For each chunk, create a list of write request records and populate
        // them with `PutRequest` requests, each specifying one movie from the
        // chunk. Once the chunk's items are all in the `PutRequest` list,
        // send them to Amazon DynamoDB using the
        // `DynamoDBClient.batchWriteItem()` function.
```

```
        for chunk in chunks {
            var requestList: [DynamoDBClientTypes.WriteRequest] = []

            for movie in chunk {
                let item = try await movie.getAsItem()
                let request = DynamoDBClientTypes.WriteRequest(
                    putRequest: .init(
                        item: item
                    )
                )
                requestList.append(request)
            }

            let input = BatchWriteItemInput(requestItems: [tableName:
requestList])
            _ = try await client.batchWriteItem(input: input)
        }
    }
```

- Para obter detalhes da API, consulte BatchWriteItema referência da API AWS SDK for Swift.

Cenários do DynamoDB usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon DynamoDB com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Acelerar as leituras do DynamoDB com o DAX usando um AWS SDK
- Conceitos básicos de tabelas, itens e consultas do DynamoDB usando um AWS SDK
- Consultar uma tabela do DynamoDB usando lotes de instruções PartiQL e um AWS SDK
- Consultar uma tabela do DynamoDB usando o PartiQL e um AWS SDK
- Usar um modelo de documento para o DynamoDB usando um AWS SDK
- Usar um modelo de persistência de objetos de alto nível para o DynamoDB usando um AWS SDK

Acelerar as leituras do DynamoDB com o DAX usando um AWS SDK

O código de exemplo a seguir mostra como:

- Criar e gravar dados em uma tabela com os clientes DAX e SDK.
- Obter, consultar e verificar a tabela com ambos os clientes e comparar a respectiva performance.

Para obter mais informações, consulte Desenvolver com o cliente do DynamoDB Accelerator.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela com o cliente do DAX ou Boto3.

```
import boto3


def create_dax_table(dyn_resource=None):
    """
    Creates a DynamoDB table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The newly created table.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table_name = "TryDaxTable"
    params = {
        "TableName": table_name,
        "KeySchema": [
            {"AttributeName": "partition_key", "KeyType": "HASH"},
            {"AttributeName": "sort_key", "KeyType": "RANGE"},
        ],
```

```
        "AttributeDefinitions": [
            {"AttributeName": "partition_key", "AttributeType": "N"},
            {"AttributeName": "sort_key", "AttributeType": "N"},
        ],
        "ProvisionedThroughput": {"ReadCapacityUnits": 10, "WriteCapacityUnits":
 10},
    }
    table = dyn_resource.create_table(**params)
    print(f"Creating {table_name}...")
    table.wait_until_exists()
    return table


if __name__ == "__main__":
    dax_table = create_dax_table()
    print(f"Created table.")
```

Grave dados de teste na tabela.

```
import boto3


def write_data_to_dax_table(key_count, item_size, dyn_resource=None):
    """
    Writes test data to the demonstration table.

    :param key_count: The number of partition and sort keys to use to populate
 the
                      table. The total number of items is key_count * key_count.
    :param item_size: The size of non-key data for each test item.
    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    some_data = "X" * item_size

    for partition_key in range(1, key_count + 1):
        for sort_key in range(1, key_count + 1):
            table.put_item(
                Item={
```

```
                    "partition_key": partition_key,
                    "sort_key": sort_key,
                    "some_data": some_data,
                }
            )
            print(f"Put item ({partition_key}, {sort_key}) succeeded.")


if __name__ == "__main__":
    write_key_count = 10
    write_item_size = 1000
    print(
        f"Writing {write_key_count*write_key_count} items to the table. "
        f"Each item is {write_item_size} characters."
    )
    write_data_to_dax_table(write_key_count, write_item_size)
```

Obtenha itens para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import sys
import time
import amazondax
import boto3


def get_item_test(key_count, iterations, dyn_resource=None):
    """
    Gets items from the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param key_count: The number of items to get from the table in each
 iteration.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")
```

```
    table = dyn_resource.Table("TryDaxTable")
    start = time.perf_counter()
    for _ in range(iterations):
        for partition_key in range(1, key_count + 1):
            for sort_key in range(1, key_count + 1):
                table.get_item(
                    Key={"partition_key": partition_key, "sort_key": sort_key}
                )
                print(".", end="")
                sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()

    test_key_count = 10
    test_iterations = 50
    if args.endpoint_url:
        print(
            f"Getting each item from the table {test_iterations} times, "
            f"using the DAX client."
        )
        # Use a with statement so the DAX client closes the cluster after
 completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url)
 as dax:
            test_start, test_end = get_item_test(
                test_key_count, test_iterations, dyn_resource=dax
            )
    else:
        print(
            f"Getting each item from the table {test_iterations} times, "
            f"using the Boto3 client."
```

```
        )
        test_start, test_end = get_item_test(test_key_count, test_iterations)
    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
        f"{(test_end - test_start)/ test_iterations}."
    )
```

Consulte a tabela para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import time
import sys
import amazondax
import boto3
from boto3.dynamodb.conditions import Key


def query_test(partition_key, sort_keys, iterations, dyn_resource=None):
    """
    Queries the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param partition_key: The partition key value to use in the query. The query
                          returns items that have partition keys equal to this
 value.
    :param sort_keys: The range of sort key values for the query. The query
 returns
                      items that have sort key values between these two values.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    key_condition_expression = Key("partition_key").eq(partition_key) & Key(
        "sort_key"
    ).between(*sort_keys)
```

```
    start = time.perf_counter()
    for _ in range(iterations):
        table.query(KeyConditionExpression=key_condition_expression)
        print(".", end="")
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()

    test_partition_key = 5
    test_sort_keys = (2, 9)
    test_iterations = 100
    if args.endpoint_url:
        print(f"Querying the table {test_iterations} times, using the DAX
 client.")
        # Use a with statement so the DAX client closes the cluster after
 completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url)
 as dax:
            test_start, test_end = query_test(
                test_partition_key, test_sort_keys, test_iterations,
 dyn_resource=dax
            )
    else:
        print(f"Querying the table {test_iterations} times, using the Boto3
 client.")
        test_start, test_end = query_test(
            test_partition_key, test_sort_keys, test_iterations
        )

    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
```

```
        f"{(test_end - test_start)/test_iterations}."
    )
```

Verifique a tabela para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import time
import sys
import amazondax
import boto3


def scan_test(iterations, dyn_resource=None):
    """
    Scans the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    start = time.perf_counter()
    for _ in range(iterations):
        table.scan()
        print(".", end="")
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
```

```
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()

    test_iterations = 100
    if args.endpoint_url:
        print(f"Scanning the table {test_iterations} times, using the DAX
 client.")
        # Use a with statement so the DAX client closes the cluster after
 completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url)
 as dax:
            test_start, test_end = scan_test(test_iterations, dyn_resource=dax)
    else:
        print(f"Scanning the table {test_iterations} times, using the Boto3
 client.")
        test_start, test_end = scan_test(test_iterations)
    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
        f"{(test_end - test_start)/test_iterations}."
    )
```

Exclua a tabela.

```
import boto3


def delete_dax_table(dyn_resource=None):
    """
    Deletes the demonstration table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    table.delete()

    print(f"Deleting {table.name}...")
```

```
    table.wait_until_not_exists()


if __name__ == "__main__":
    delete_dax_table()
    print("Table deleted!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTable
  - DeleteTable
  - GetItem
  - PutItem
  - Query
  - Scan

Conceitos básicos de tabelas, itens e consultas do DynamoDB usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// This example application performs the following basic Amazon DynamoDB
// functions:
//
//     CreateTableAsync
//     PutItemAsync
//     UpdateItemAsync
//     BatchWriteItemAsync
//     GetItemAsync
//     DeleteItemAsync
//     Query
//     Scan
//     DeleteItemAsync
//
using Amazon.DynamoDBv2;
using DynamoDB_Actions;

public class DynamoDB_Basics
{
    // Separator for the console display.
    private static readonly string SepBar = new string('-', 80);

    public static async Task Main()
    {
        var client = new AmazonDynamoDBClient();

        var tableName = "movie_table";

        // Relative path to moviedata.json in the local repository.
        var movieFileName = @"..\..\..\..\..\..\..\..\resources\sample_files
\movies.json";

        DisplayInstructions();

        // Create a new table and wait for it to be active.
        Console.WriteLine($"Creating the new table: {tableName}");

        var success = await DynamoDbMethods.CreateMovieTableAsync(client,
 tableName);

        if (success)
        {
            Console.WriteLine($"\nTable: {tableName} successfully created.");
        }
```

```
        else
        {
            Console.WriteLine($"\nCould not create {tableName}.");
        }

        WaitForEnter();

        // Add a single new movie to the table.
        var newMovie = new Movie
        {
            Year = 2021,
            Title = "Spider-Man: No Way Home",
        };

        success = await DynamoDbMethods.PutItemAsync(client, newMovie,
tableName);
        if (success)
        {
            Console.WriteLine($"Added {newMovie.Title} to the table.");
        }
        else
        {
            Console.WriteLine("Could not add movie to table.");
        }

        WaitForEnter();

        // Update the new movie by adding a plot and rank.
        var newInfo = new MovieInfo
        {
            Plot = "With Spider-Man's identity now revealed, Peter asks" +
                   "Doctor Strange for help. When a spell goes wrong, dangerous"
+
                   "foes from other worlds start to appear, forcing Peter to" +
                   "discover what it truly means to be Spider-Man.",
            Rank = 9,
        };

        success = await DynamoDbMethods.UpdateItemAsync(client, newMovie,
newInfo, tableName);
        if (success)
        {
            Console.WriteLine($"Successfully updated the movie:
{newMovie.Title}");
```

```
        }
        else
        {
            Console.WriteLine("Could not update the movie.");
        }

        WaitForEnter();

        // Add a batch of movies to the DynamoDB table from a list of
        // movies in a JSON file.
        var itemCount = await DynamoDbMethods.BatchWriteItemsAsync(client,
movieFileName);
        Console.WriteLine($"Added {itemCount} movies to the table.");

        WaitForEnter();

        // Get a movie by key. (partition + sort)
        var lookupMovie = new Movie
        {
            Title = "Jurassic Park",
            Year = 1993,
        };

        Console.WriteLine("Looking for the movie \"Jurassic Park\".");
        var item = await DynamoDbMethods.GetItemAsync(client, lookupMovie,
tableName);
        if (item.Count > 0)
        {
            DynamoDbMethods.DisplayItem(item);
        }
        else
        {
            Console.WriteLine($"Couldn't find {lookupMovie.Title}");
        }

        WaitForEnter();

        // Delete a movie.
        var movieToDelete = new Movie
        {
            Title = "The Town",
            Year = 2010,
        };
```

```
        success = await DynamoDbMethods.DeleteItemAsync(client, tableName,
movieToDelete);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {movieToDelete.Title}.");
        }
        else
        {
            Console.WriteLine($"Could not delete {movieToDelete.Title}.");
        }

        WaitForEnter();

        // Use Query to find all the movies released in 2010.
        int findYear = 2010;
        Console.WriteLine($"Movies released in {findYear}");
        var queryCount = await DynamoDbMethods.QueryMoviesAsync(client,
tableName, findYear);
        Console.WriteLine($"Found {queryCount} movies released in {findYear}");

        WaitForEnter();

        // Use Scan to get a list of movies from 2001 to 2011.
        int startYear = 2001;
        int endYear = 2011;
        var scanCount = await DynamoDbMethods.ScanTableAsync(client, tableName,
startYear, endYear);
        Console.WriteLine($"Found {scanCount} movies released between {startYear}
and {endYear}");

        WaitForEnter();

        // Delete the table.
        success = await DynamoDbMethods.DeleteTableAsync(client, tableName);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {tableName}");
        }
        else
        {
            Console.WriteLine($"Could not delete {tableName}");
        }
```

```
        Console.WriteLine("The DynamoDB Basics example application is done.");

        WaitForEnter();
    }

    /// <summary>
    /// Displays the description of the application on the console.
    /// </summary>
    private static void DisplayInstructions()
    {
        Console.Clear();
        Console.WriteLine();
        Console.Write(new string(' ', 28));
        Console.WriteLine("DynamoDB Basics Example");
        Console.WriteLine(SepBar);
        Console.WriteLine("This demo application shows the basics of using
DynamoDB with the AWS SDK.");
        Console.WriteLine(SepBar);
        Console.WriteLine("The application does the following:");
        Console.WriteLine("\t1. Creates a table with partition: year and
sort:title.");
        Console.WriteLine("\t2. Adds a single movie to the table.");
        Console.WriteLine("\t3. Adds movies to the table from moviedata.json.");
        Console.WriteLine("\t4. Updates the rating and plot of the movie that was
just added.");
        Console.WriteLine("\t5. Gets a movie using its key (partition + sort).");
        Console.WriteLine("\t6. Deletes a movie.");
        Console.WriteLine("\t7. Uses QueryAsync to return all movies released in
a given year.");
        Console.WriteLine("\t8. Uses ScanAsync to return all movies released
within a range of years.");
        Console.WriteLine("\t9. Finally, it deletes the table that was just
created.");
        WaitForEnter();
    }

    /// <summary>
    /// Simple method to wait for the Enter key to be pressed.
    /// </summary>
    private static void WaitForEnter()
    {
        Console.WriteLine("\nPress <Enter> to continue.");
        Console.WriteLine(SepBar);
```

```
        _ = Console.ReadLine();
    }
}
```

Cria uma tabela para conter dados de filmes.

```
        /// <summary>
        /// Creates a new Amazon DynamoDB table and then waits for the new
        /// table to become active.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="tableName">The name of the table to create.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
 client, string tableName)
        {
            var response = await client.CreateTableAsync(new CreateTableRequest
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                {
                    new AttributeDefinition
                    {
                        AttributeName = "title",
                        AttributeType = ScalarAttributeType.S,
                    },
                    new AttributeDefinition
                    {
                        AttributeName = "year",
                        AttributeType = ScalarAttributeType.N,
                    },
                },
                KeySchema = new List<KeySchemaElement>()
                {
                    new KeySchemaElement
                    {
                        AttributeName = "year",
                        KeyType = KeyType.HASH,
```

```
                    },
                    new KeySchemaElement
                    {
                        AttributeName = "title",
                        KeyType = KeyType.RANGE,
                    },
                },
                ProvisionedThroughput = new ProvisionedThroughput
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5,
                },
            });

            // Wait until the table is ACTIVE and then report success.
            Console.Write("Waiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = response.TableDescription.TableName,
            };

            TableStatus status;

            int sleepDuration = 2000;

            do
            {
                System.Threading.Thread.Sleep(sleepDuration);

                var describeTableResponse = await
client.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
```

Adiciona um único filme à tabela.

```
        /// <summary>
        /// Adds a new item to the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing informtation for
        /// the movie to add to the table.</param>
        /// <param name="tableName">The name of the table where the item will be
 added.</param>
        /// <returns>A Boolean value that indicates the results of adding the
 item.</returns>
        public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
 Movie newMovie, string tableName)
        {
            var item = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new PutItemRequest
            {
                TableName = tableName,
                Item = item,
            };

            var response = await client.PutItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Atualiza um item único em uma tabela.

```
        /// <summary>
        /// Updates an existing item in the movies table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
```

```
        /// <param name="newMovie">A Movie object containing information for
        /// the movie to update.</param>
        /// <param name="newInfo">A MovieInfo object that contains the
        /// information that will be changed.</param>
        /// <param name="tableName">The name of the table that contains the
movie.</param>
        /// <returns>A Boolean value that indicates the success of the
operation.</returns>
        public static async Task<bool> UpdateItemAsync(
            AmazonDynamoDBClient client,
            Movie newMovie,
            MovieInfo newInfo,
            string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };
            var updates = new Dictionary<string, AttributeValueUpdate>
            {
                ["info.plot"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { S = newInfo.Plot },
                },

                ["info.rating"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { N = newInfo.Rank.ToString() },
                },
            };

            var request = new UpdateItemRequest
            {
                AttributeUpdates = updates,
                Key = key,
                TableName = tableName,
            };

            var response = await client.UpdateItemAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
```

```
        }
```

Recupera um único item de uma tabela de filmes.

```
        /// <summary>
        /// Gets information about an existing movie from the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information about
        /// the movie to retrieve.</param>
        /// <param name="tableName">The name of the table containing the movie.</
param>
        /// <returns>A Dictionary object containing information about the item
        /// retrieved.</returns>
        public static async Task<Dictionary<string, AttributeValue>>
 GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new GetItemRequest
            {
                Key = key,
                TableName = tableName,
            };

            var response = await client.GetItemAsync(request);
            return response.Item;
        }
```

Grava um lote de itens na tabela de filmes.

```
        /// <summary>
```

```
        /// Loads the contents of a JSON file into a list of movies to be
        /// added to the DynamoDB table.
        /// </summary>
        /// <param name="movieFileName">The full path to the JSON file.</param>
        /// <returns>A generic list of movie objects.</returns>
        public static List<Movie> ImportMovies(string movieFileName)
        {
            if (!File.Exists(movieFileName))
            {
                return null;
            }

            using var sr = new StreamReader(movieFileName);
            string json = sr.ReadToEnd();
            var allMovies = JsonSerializer.Deserialize<List<Movie>>(
                json,
                new JsonSerializerOptions
                {
                    PropertyNameCaseInsensitive = true
                });

            // Now return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }

        /// <summary>
        /// Writes 250 items to the movie table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="movieFileName">A string containing the full path to
        /// the JSON file containing movie data.</param>
        /// <returns>A long integer value representing the number of movies
        /// imported from the JSON file.</returns>
        public static async Task<long> BatchWriteItemsAsync(
            AmazonDynamoDBClient client,
            string movieFileName)
        {
            var movies = ImportMovies(movieFileName);
            if (movies is null)
            {
                Console.WriteLine("Couldn't find the JSON file with movie
data.");
                return 0;
            }
```

```
            var context = new DynamoDBContext(client);

            var movieBatch = context.CreateBatchWrite<Movie>();
            movieBatch.AddPutItems(movies);

            Console.WriteLine("Adding imported movies to the table.");
            await movieBatch.ExecuteAsync();

            return movies.Count;
        }
```

Exclui um único item da tabela.

```
        /// <summary>
        /// Deletes a single item from a DynamoDB table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table from which the item
        /// will be deleted.</param>
        /// <param name="movieToDelete">A movie object containing the title and
        /// year of the movie to delete.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// delete operation.</returns>
        public static async Task<bool> DeleteItemAsync(
            AmazonDynamoDBClient client,
            string tableName,
            Movie movieToDelete)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = movieToDelete.Title },
                ["year"] = new AttributeValue { N =
movieToDelete.Year.ToString() },
            };

            var request = new DeleteItemRequest
            {
                TableName = tableName,
                Key = key,
```

```
            };

            var response = await client.DeleteItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Consulta a tabela de filmes lançados em determinado ano.

```
        /// <summary>
        /// Queries the table for movies released in a particular year and
        /// then displays the information for the movies returned.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table to query.</param>
        /// <param name="year">The release year for which we want to
        /// view movies.</param>
        /// <returns>The number of movies that match the query.</returns>
        public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient
 client, string tableName, int year)
        {
            var movieTable = Table.LoadTable(client, tableName);
            var filter = new QueryFilter("year", QueryOperator.Equal, year);

            Console.WriteLine("\nFind movies released in: {year}:");

            var config = new QueryOperationConfig()
            {
                Limit = 10, // 10 items per page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "title",
                  "year",
                },
                ConsistentRead = true,
                Filter = filter,
            };

            // Value used to track how many movies match the
            // supplied criteria.
```

```
            var moviesFound = 0;

            Search search = movieTable.Query(config);
            do
            {
                var movieList = await search.GetNextSetAsync();
                moviesFound += movieList.Count;

                foreach (var movie in movieList)
                {
                    DisplayDocument(movie);
                }
            }
            while (!search.IsDone);

            return moviesFound;
        }
```

Busca na tabela os filmes lançados em um intervalo de anos.

```
        public static async Task<int> ScanTableAsync(
            AmazonDynamoDBClient client,
            string tableName,
            int startYear,
            int endYear)
        {
            var request = new ScanRequest
            {
                TableName = tableName,
                ExpressionAttributeNames = new Dictionary<string, string>
                {
                  { "#yr", "year" },
                },
                ExpressionAttributeValues = new Dictionary<string,
 AttributeValue>
                {
                    { ":y_a", new AttributeValue { N = startYear.ToString() } },
                    { ":y_z", new AttributeValue { N = endYear.ToString() } },
                },
                FilterExpression = "#yr between :y_a and :y_z",
```

```
                ProjectionExpression = "#yr, title, info.actors[0],
info.directors, info.running_time_secs",
                Limit = 10 // Set a limit to demonstrate using the
LastEvaluatedKey.
            };

            // Keep track of how many movies were found.
            int foundCount = 0;

            var response = new ScanResponse();
            do
            {
                response = await client.ScanAsync(request);
                foundCount += response.Items.Count;
                response.Items.ForEach(i => DisplayItem(i));
                request.ExclusiveStartKey = response.LastEvaluatedKey;
            }
            while (response.LastEvaluatedKey.Count > 0);
            return foundCount;
        }
```

Exclui a tabela de filmes.

```
        public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient
client, string tableName)
        {
            var request = new DeleteTableRequest
            {
                TableName = tableName,
            };

            var response = await client.DeleteTableAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Table {response.TableDescription.TableName}
successfully deleted.");
                return true;
            }
            else
            {
                Console.WriteLine("Could not delete table.");
```

```
                return false;
            }
        }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O cenário de conceitos básicos do DynamoDB.

```
###############################################################################
# function dynamodb_getting_started_movies
#
# Scenario to create an Amazon DynamoDB table and perform a series of operations
 on the table.
#
```

```
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
###############################################################################
function dynamodb_getting_started_movies() {

  source ./dynamodb_operations.sh

  key_schema_json_file="dynamodb_key_schema.json"
  attribute_definitions_json_file="dynamodb_attr_def.json"
  item_json_file="movie_item.json"
  key_json_file="movie_key.json"
  batch_json_file="batch.json"
  attribute_names_json_file="attribute_names.json"
  attributes_values_json_file="attribute_values.json"

  echo_repeat "*" 88
  echo
  echo "Welcome to the Amazon DynamoDB getting started demo."
  echo
  echo_repeat "*" 88
  echo

  local table_name
  echo -n "Enter a name for a new DynamoDB table: "
  get_input
  table_name=$get_input_result

  local provisioned_throughput="ReadCapacityUnits=5,WriteCapacityUnits=5"

  echo '[
  {"AttributeName": "year", "KeyType": "HASH"},
   {"AttributeName": "title", "KeyType": "RANGE"}
  ]' >"$key_schema_json_file"

  echo '[
  {"AttributeName": "year", "AttributeType": "N"},
   {"AttributeName": "title", "AttributeType": "S"}
  ]' >"$attribute_definitions_json_file"

  if dynamodb_create_table -n "$table_name" -a "$attribute_definitions_json_file"
 \
    -k "$key_schema_json_file" -p "$provisioned_throughput" 1>/dev/null; then
    echo "Created a DynamoDB table named $table_name"
```

```
  else
    errecho "The table failed to create. This demo will exit."
    clean_up
    return 1
  fi

  echo "Waiting for the table to become active...."

  if dynamodb_wait_table_active -n "$table_name"; then
    echo "The table is now active."
  else
    errecho "The table failed to become active. This demo will exit."
    cleanup "$table_name"
    return 1
  fi

  echo
  echo_repeat "*" 88
  echo

  echo -n "Enter the title of a movie you want to add to the table: "
  get_input
  local added_title
  added_title=$get_input_result

  local added_year
  get_int_input "What year was it released? "
  added_year=$get_input_result

  local rating
  get_float_input "On a scale of 1 - 10, how do you rate it? " "1" "10"
  rating=$get_input_result

  local plot
  echo -n "Summarize the plot for me: "
  get_input
  plot=$get_input_result

  echo '{
    "year": {"N" :"'"$added_year"'"},
    "title": {"S" :  "'"$added_title"'"},
    "info": {"M" : {"plot": {"S" : "'"$plot"'"}, "rating":
{"N" :"'"$rating"'"} } }
  }' >"$item_json_file"
```

```
 if dynamodb_put_item -n "$table_name" -i "$item_json_file"; then
   echo "The movie '$added_title' was successfully added to the table
'$table_name'."
 else
   errecho "Put item failed. This demo will exit."
   clean_up "$table_name"
   return 1
 fi

 echo
 echo_repeat "*" 88
 echo

 echo "Let's update your movie '$added_title'."
 get_float_input "You rated it $rating, what new rating would you give it? " "1"
"10"
 rating=$get_input_result

 echo -n "You summarized the plot as '$plot'."
 echo "What would you say now? "
 get_input
 plot=$get_input_result

 echo '{
   "year": {"N" :"'"$added_year"'"},
   "title": {"S" :  "'"$added_title"'"}
   }' >"$key_json_file"

 echo '{
   ":r": {"N" :"'"$rating"'"},
   ":p": {"S" : "'"$plot"'"}
  }' >"$item_json_file"

 local update_expression="SET info.rating = :r, info.plot = :p"

 if dynamodb_update_item -n "$table_name" -k "$key_json_file" -e
"$update_expression" -v "$item_json_file"; then
   echo "Updated '$added_title' with new attributes."
 else
   errecho "Update item failed. This demo will exit."
   clean_up "$table_name"
   return 1
 fi
```

```
  echo
  echo_repeat "*" 88
  echo

  echo "We will now use batch write to upload 150 movie entries into the table."

  local batch_json
  for batch_json in movie_files/movies_*.json; do
    echo "{ \"$table_name\" : $(<"$batch_json") }" >"$batch_json_file"
    if dynamodb_batch_write_item -i "$batch_json_file" 1>/dev/null; then
      echo "Entries in $batch_json added to table."
    else
      errecho "Batch write failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi
  done

  local title="The Lord of the Rings: The Fellowship of the Ring"
  local year="2001"

  if get_yes_no_input "Let's move on...do you want to get info about '$title'?
 (y/n) "; then
    echo '{
  "year": {"N" :"'"$year"'"},
  "title": {"S" :  "'"$title"'"}
  }' >"$key_json_file"
    local info
    info=$(dynamodb_get_item -n "$table_name" -k "$key_json_file")

    # shellcheck disable=SC2181
    if [[ ${?} -ne 0 ]]; then
      errecho "Get item failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi

    echo "Here is what I found:"
    echo "$info"
  fi

  local ask_for_year=true
  while [[ "$ask_for_year" == true ]]; do
```

```
    echo "Let's get a list of movies released in a given year."
    get_int_input "Enter a year between 1972 and 2018: " "1972" "2018"
    year=$get_input_result
    echo '{
    "#n": "year"
    }' >"$attribute_names_json_file"

    echo '{
    ":v": {"N" :"'"$year"'"}
    }' >"$attributes_values_json_file"

    response=$(dynamodb_query -n "$table_name" -k "#n=:v" -a
"$attribute_names_json_file" -v "$attributes_values_json_file")

    # shellcheck disable=SC2181
    if [[ ${?} -ne 0 ]]; then
      errecho "Query table failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi

    echo "Here is what I found:"
    echo "$response"

    if ! get_yes_no_input "Try another year? (y/n) "; then
      ask_for_year=false
    fi
  done

  echo "Now let's scan for movies released in a range of years. Enter a year: "
  get_int_input "Enter a year between 1972 and 2018: " "1972" "2018"
  local start=$get_input_result

  get_int_input "Enter another year: " "1972" "2018"
  local end=$get_input_result

  echo '{
    "#n": "year"
    }' >"$attribute_names_json_file"

  echo '{
    ":v1": {"N" : "'"$start"'"},
    ":v2": {"N" : "'"$end"'"}
    }' >"$attributes_values_json_file"
```

```
 response=$(dynamodb_scan -n "$table_name" -f "#n BETWEEN :v1 AND :v2" -a
"$attribute_names_json_file" -v "$attributes_values_json_file")

 # shellcheck disable=SC2181
 if [[ ${?} -ne 0 ]]; then
   errecho "Scan table failed. This demo will exit."
   clean_up "$table_name"
   return 1
 fi

 echo "Here is what I found:"
 echo "$response"

 echo
 echo_repeat "*" 88
 echo

 echo "Let's remove your movie '$added_title' from the table."

 if get_yes_no_input "Do you want to remove '$added_title'? (y/n) "; then
   echo '{
 "year": {"N" :"'"$added_year"'"},
 "title": {"S" :  "'"$added_title"'"}
 }' >"$key_json_file"

   if ! dynamodb_delete_item -n "$table_name" -k "$key_json_file"; then
     errecho "Delete item failed. This demo will exit."
     clean_up "$table_name"
     return 1
   fi
 fi

 if get_yes_no_input "Do you want to delete the table '$table_name'? (y/n) ";
then
   if ! clean_up "$table_name"; then
     return 1
   fi
 else
   if ! clean_up; then
     return 1
   fi
 fi
```

```
  return 0
}
```

As funções do DynamoDB usadas nesse cenário.

```
##############################################################################
# function dynamodb_create_table
#
# This function creates an Amazon DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to create.
#       -a attribute_definitions -- JSON file path of a list of attributes and
 their types.
#       -k key_schema -- JSON file path of a list of attributes and their key
 types.
#       -p provisioned_throughput -- Provisioned throughput settings for the
 table.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_create_table() {
  local table_name attribute_definitions key_schema provisioned_throughput
 response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_create_table"
    echo "Creates an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to create."
    echo " -a attribute_definitions -- JSON file path of a list of attributes and
 their types."
    echo " -k key_schema -- JSON file path of a list of attributes and their key
 types."
    echo " -p provisioned_throughput -- Provisioned throughput settings for the
 table."
    echo ""
```

```
}

# Retrieve the calling parameters.
while getopts "n:a:k:p:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    a) attribute_definitions="${OPTARG}" ;;
    k) key_schema="${OPTARG}" ;;
    p) provisioned_throughput="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$attribute_definitions" ]]; then
  errecho "ERROR: You must provide an attribute definitions json file path the
-a parameter."
  usage
  return 1
fi

if [[ -z "$key_schema" ]]; then
  errecho "ERROR: You must provide a key schema json file path the -k
parameter."
  usage
  return 1
fi

if [[ -z "$provisioned_throughput" ]]; then
```

```
    errecho "ERROR: You must provide a provisioned throughput json file path the
 -p parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    attribute_definitions:   $attribute_definitions"
  iecho "    key_schema:   $key_schema"
  iecho "    provisioned_throughput:   $provisioned_throughput"
  iecho ""

  response=$(aws dynamodb create-table \
    --table-name "$table_name" \
    --attribute-definitions file://"$attribute_definitions" \
    --key-schema file://"$key_schema" \
    --provisioned-throughput "$provisioned_throughput")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-table operation failed.$response"
    return 1
  fi

  return 0
}

###############################################################################
# function dynamodb_describe_table
#
# This function returns the status of a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#
#  Response:
#       - TableStatus:
#     And:
#       0 - Table is active.
#       1 - If it fails.
###############################################################################
```

```
function dynamodb_describe_table {
  local table_name
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_describe_table"
    echo "Describe the status of a DynamoDB table."
    echo "  -n table_name  -- The name of the table."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  local table_status
    table_status=$(
      aws dynamodb describe-table \
        --table-name "$table_name" \
        --output text \
        --query 'Table.TableStatus'
    )
```

```
   local error_code=${?}

    if [[ $error_code -ne 0 ]]; then
      aws_cli_error_log "$error_code"
      errecho "ERROR: AWS reports describe-table operation failed.$table_status"
      return 1
    fi

  echo "$table_status"

  return 0
}

###############################################################################
# function dynamodb_put_item
#
# This function puts an item into a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -i item  -- Path to json file containing the item values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_put_item() {
  local table_name item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_put_item"
    echo "Put an item into a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -i item  -- Path to json file containing the item values."
    echo ""
  }

  while getopts "n:i:h" option; do
    case "${option}" in
```

```
    n) table_name="${OPTARG}" ;;
    i) item="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$item" ]]; then
  errecho "ERROR: You must provide an item with the -i parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    item:   $item"
iecho ""
iecho ""

response=$(aws dynamodb put-item \
  --table-name "$table_name" \
  --item file://"$item")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports put-item operation failed.$response"
  return 1
fi
```

```
  return 0

}

##############################################################################
# function dynamodb_update_item
#
# This function updates an item in a DynamoDB table.
#
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to update.
#       -e update expression  -- An expression that defines one or more
 attributes to be updated.
#       -v values  -- Path to json file containing the update values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_update_item() {
  local table_name keys update_expression values response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_update_item"
    echo "Update an item in a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to update."
    echo " -e update expression  -- An expression that defines one or more
 attributes to be updated."
    echo " -v values  -- Path to json file containing the update values."
    echo ""
  }

  while getopts "n:k:e:v:h" option; do
    case "${option}" in
```

```
    n) table_name="${OPTARG}" ;;
    k) keys="${OPTARG}" ;;
    e) update_expression="${OPTARG}" ;;
    v) values="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi
if [[ -z "$update_expression" ]]; then
  errecho "ERROR: You must provide an update expression with the -e parameter."
  usage
  return 1
fi

if [[ -z "$values" ]]; then
  errecho "ERROR: You must provide a values json file path the -v parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    keys:   $keys"
iecho "    update_expression:   $update_expression"
```

```
  iecho "    values:   $values"

  response=$(aws dynamodb update-item \
    --table-name "$table_name" \
    --key file://"$keys" \
    --update-expression "$update_expression" \
    --expression-attribute-values file://"$values")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports update-item operation failed.$response"
    return 1
  fi

  return 0

}

###############################################################################
# function dynamodb_batch_write_item
#
# This function writes a batch of items into a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the items to write.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_batch_write_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_write_item"
    echo "Write a batch of items into a DynamoDB table."
    echo " -i item  -- Path to json file containing the items to write."
    echo ""
```

```
  }
  while getopts "i:h" option; do
    case "${option}" in
      i) item="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    item:   $item"
  iecho ""

  response=$(aws dynamodb batch-write-item \
    --request-items file://"$item")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi

  return 0
}

###############################################################################
# function dynamodb_get_item
```

```
#
# This function gets an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to get.
#       [-q query]  -- Optional JMESPath query expression.
#
#  Returns:
#       The item as text output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_get_item() {
  local table_name keys query response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_get_item"
    echo "Get an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to get."
    echo " [-q query]  -- Optional JMESPath query expression."
    echo ""
  }
  query=""
  while getopts "n:k:q:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      q) query="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
```

```
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
    return 1
  fi

  if [[ -n "$query" ]]; then
    response=$(aws dynamodb get-item \
      --table-name "$table_name" \
      --key file://"$keys" \
      --output text \
      --query "$query")
  else
    response=$(
      aws dynamodb get-item \
        --table-name "$table_name" \
        --key file://"$keys" \
        --output text
    )
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports get-item operation failed.$response"
    return 1
  fi

  if [[ -n "$query" ]]; then
    echo "$response" | sed "/^\t/s/\t//1" # Remove initial tab that the JMSEPath
query inserts on some strings.
```

```
  else
    echo "$response"
  fi

  return 0
}

###########################################################################
# function dynamodb_query
#
# This function queries a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k key_condition_expression -- The key condition expression.
#       -a attribute_names -- Path to JSON file containing the attribute names.
#       -v attribute_values -- Path to JSON file containing the attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###########################################################################
function dynamodb_query() {
  local table_name key_condition_expression attribute_names attribute_values
 projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_query"
    echo "Query a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k key_condition_expression -- The key condition expression."
    echo " -a attribute_names -- Path to JSON file containing the attribute
 names."
    echo " -v attribute_values -- Path to JSON file containing the attribute
 values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
```

```
  }

  while getopts "n:k:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) key_condition_expression="${OPTARG}" ;;
      a) attribute_names="${OPTARG}" ;;
      v) attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$key_condition_expression" ]]; then
    errecho "ERROR: You must provide a key condition expression with the -k
 parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_names" ]]; then
    errecho "ERROR: You must provide a attribute names with the -a parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_values" ]]; then
    errecho "ERROR: You must provide a attribute values with the -v parameter."
    usage
```

```
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values")
  else
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports query operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function dynamodb_scan
#
# This function scans a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -f filter_expression  -- The filter expression.
#       -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names.
#       -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values.
#       [-p projection_expression]  -- Optional projection expression.
```

```
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_scan() {
  local table_name filter_expression expression_attribute_names
 expression_attribute_values projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_scan"
    echo "Scan a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -f filter_expression  -- The filter expression."
    echo " -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names."
    echo " -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:f:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      f) filter_expression="${OPTARG}" ;;
      a) expression_attribute_names="${OPTARG}" ;;
      v) expression_attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
```

```
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$filter_expression" ]]; then
    errecho "ERROR: You must provide a filter expression with the -f parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_names" ]]; then
    errecho "ERROR: You must provide expression attribute names with the -a
parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_values" ]]; then
    errecho "ERROR: You must provide expression attribute values with the -v
parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values")
  else
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values" \
      --projection-expression "$projection_expression")
  fi
```

```
  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports scan operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function dynamodb_delete_item
#
# This function deletes an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item
 to delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_delete_item() {
  local table_name keys response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_delete_item"
    echo "Delete an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the
 item to delete."
    echo ""
  }
  while getopts "n:k:h" option; do
```

```
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    k) keys="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    keys:   $keys"
iecho ""

response=$(aws dynamodb delete-item \
  --table-name "$table_name" \
  --key file://"$keys")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports delete-item operation failed.$response"
  return 1
fi
```

```
  return 0

}

###############################################################################
# function dynamodb_delete_table
#
# This function deletes a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_delete_table() {
  local table_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function dynamodb_delete_table"
    echo "Deletes an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to delete."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
```

```
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho ""

  response=$(aws dynamodb delete-table \
    --table-name "$table_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-table operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas nesse cenário.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
```

```
#
# This function outputs everything sent to it to STDERR (standard error output).
#############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

#############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-
help-return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
#############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    {
        Aws::Client::ClientConfiguration clientConfig;
        //  1. Create a table with partition: year (N) and sort: title (S).
(CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::dynamodbGettingStartedScenario(clientConfig);

            // 9. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }
    }
```

```
//! Scenario to modify and query a DynamoDB table.
/*!
  \sa dynamodbGettingStartedScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::dynamodbGettingStartedScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;
    std::cout << "Welcome to the Amazon DynamoDB getting started demo." <<
 std::endl;
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // 2. Add a new movie.
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate
 it? ",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::PutItemRequest putItemRequest;
        putItemRequest.SetTableName(MOVIE_TABLE_NAME);

        putItemRequest.AddItem(YEAR_KEY,

 Aws::DynamoDB::Model::AttributeValue().SetN(year));
        putItemRequest.AddItem(TITLE_KEY,

 Aws::DynamoDB::Model::AttributeValue().SetS(title));

        // Create attribute for the info map.
        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;
```

```
        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);

        putItemRequest.AddItem(INFO_KEY, infoMapAttribute);

        Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
                putItemRequest);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add an item: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    // 3. Update the rating and plot of the movie by using an update expression.
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);
        plot = askQuestion(Aws::String("You summarized the plot as '") + plot +
                           "'.\nWhat would you say now? ");

        Aws::DynamoDB::Model::UpdateItemRequest request;
        request.SetTableName(MOVIE_TABLE_NAME);
        request.AddKey(TITLE_KEY,
Aws::DynamoDB::Model::AttributeValue().SetS(title));
        request.AddKey(YEAR_KEY,
Aws::DynamoDB::Model::AttributeValue().SetN(year));
        std::stringstream expressionStream;
```

```
        expressionStream << "set " << INFO_KEY << "." << RATING_KEY << " =:r, "
                         << INFO_KEY << "." << PLOT_KEY << " =:p";
        request.SetUpdateExpression(expressionStream.str());
        request.SetExpressionAttributeValues({
                                                    {":r",
Aws::DynamoDB::Model::AttributeValue().SetN(
                                                            rating)},
                                                    {":p",
Aws::DynamoDB::Model::AttributeValue().SetS(
                                                            plot)}
                                            });

        request.SetReturnValues(Aws::DynamoDB::Model::ReturnValue::UPDATED_NEW);

        const Aws::DynamoDB::Model::UpdateItemOutcome &result =
dynamoClient.UpdateItem(
                request);
        if (!result.IsSuccess()) {
            std::cerr << "Error updating movie " + result.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

    // 4. Put 250 movies in the table from moviedata.json.
    {
        std::cout << "Adding movies from a json file to the database." <<
std::endl;
        const size_t MAX_SIZE_FOR_BATCH_WRITE = 25;
        const size_t MOVIES_TO_WRITE = 10 * MAX_SIZE_FOR_BATCH_WRITE;
        Aws::String jsonString = getMovieJSON();
        if (!jsonString.empty()) {
            Aws::Utils::Json::JsonValue json(jsonString);
            Aws::Utils::Array<Aws::Utils::Json::JsonView> movieJsons =
json.View().AsArray();
            Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;

            // To add movies with a cross-section of years, use an appropriate
increment
            // value for iterating through the database.
            size_t increment = movieJsons.GetLength() / MOVIES_TO_WRITE;
            for (size_t i = 0; i < movieJsons.GetLength(); i += increment) {
```

```
                writeRequests.push_back(Aws::DynamoDB::Model::WriteRequest());
                Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
putItems = movieJsonViewToAttributeMap(
                        movieJsons[i]);
                Aws::DynamoDB::Model::PutRequest putRequest;
                putRequest.SetItem(putItems);
                writeRequests.back().SetPutRequest(putRequest);
                if (writeRequests.size() == MAX_SIZE_FOR_BATCH_WRITE) {
                    Aws::DynamoDB::Model::BatchWriteItemRequest request;
                    request.AddRequestItems(MOVIE_TABLE_NAME, writeRequests);
                    const Aws::DynamoDB::Model::BatchWriteItemOutcome &outcome =
dynamoClient.BatchWriteItem(
                            request);
                    if (!outcome.IsSuccess()) {
                        std::cerr << "Unable to batch write movie data: "
                                  << outcome.GetError().GetMessage()
                                  << std::endl;
                        writeRequests.clear();
                        break;
                    }
                    else {
                        std::cout << "Added batch of " << writeRequests.size()
                                  << " movies to the database."
                                  << std::endl;
                    }
                    writeRequests.clear();
                }
            }
        }
    }

    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    // 5. Get a movie by Key (partition + sort).
    {
        Aws::String titleToGet("King Kong");
        Aws::String answer = askQuestion(Aws::String(
                "Let's move on...Would you like to get info about '" + titleToGet
+
                "'? (y/n) "));
        if (answer == "y") {
            Aws::DynamoDB::Model::GetItemRequest request;
            request.SetTableName(MOVIE_TABLE_NAME);
```

```
            request.AddKey(TITLE_KEY,

Aws::DynamoDB::Model::AttributeValue().SetS(titleToGet));
            request.AddKey(YEAR_KEY,
Aws::DynamoDB::Model::AttributeValue().SetN(1933));

            const Aws::DynamoDB::Model::GetItemOutcome &result =
dynamoClient.GetItem(
                    request);
            if (!result.IsSuccess()) {
                std::cerr << "Error " << result.GetError().GetMessage();
            }
            else {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = result.GetResult().GetItem();
                if (!item.empty()) {
                    std::cout << "\nHere's what I found:" << std::endl;
                    printMovieInfo(item);
                }
                else {
                    std::cout << "\nThe movie was not found in the database."
                              << std::endl;
                }
            }
        }
    }

    // 6. Use Query with a key condition expression to return all movies
    //    released in a given year.
    Aws::String doAgain = "n";
    do {
        Aws::DynamoDB::Model::QueryRequest req;

        req.SetTableName(MOVIE_TABLE_NAME);

        // "year" is a DynamoDB reserved keyword and must be replaced with an
        // expression attribute name.
        req.SetKeyConditionExpression("#dynobase_year = :valueToMatch");
        req.SetExpressionAttributeNames({{"#dynobase_year", YEAR_KEY}});

        int yearToMatch = askQuestionForIntRange(
                "\nLet's get a list of movies released in"
                " a given year. Enter a year between 1972 and 2018 ",
                1972, 2018);
```

```
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
        attributeValues.emplace(":valueToMatch",
                                Aws::DynamoDB::Model::AttributeValue().SetN(
                                        yearToMatch));
        req.SetExpressionAttributeValues(attributeValues);

        const Aws::DynamoDB::Model::QueryOutcome &result =
dynamoClient.Query(req);
        if (result.IsSuccess()) {
            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
            if (!items.empty()) {
                std::cout << "\nThere were " << items.size()
                          << " movies in the database from "
                          << yearToMatch << "." << std::endl;
                for (const auto &item: items) {
                    printMovieInfo(item);
                }
                doAgain = "n";
            }
            else {
                std::cout << "\nNo movies from " << yearToMatch
                          << " were found in the database"
                          << std::endl;
                doAgain = askQuestion(Aws::String("Try another year? (y/n) "));
            }
        }
        else {
            std::cerr << "Failed to Query items: " <<
result.GetError().GetMessage()
                      << std::endl;
        }

    } while (doAgain == "y");

    //  7. Use Scan to return movies released within a range of years.
    //     Show how to paginate data using ExclusiveStartKey. (Scan +
FilterExpression)
    {
        int startYear = askQuestionForIntRange("\nNow let's scan a range of years
"
                                               "for movies in the database. Enter
a start year: ",
```

```
                                                1972, 2018);
        int endYear = askQuestionForIntRange("\nEnter an end year: ",
                                             startYear, 2018);
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
exclusiveStartKey;
        do {
            Aws::DynamoDB::Model::ScanRequest scanRequest;
            scanRequest.SetTableName(MOVIE_TABLE_NAME);
            scanRequest.SetFilterExpression(
                    "#dynobase_year >= :startYear AND #dynobase_year
<= :endYear");
            scanRequest.SetExpressionAttributeNames({{"#dynobase_year",
YEAR_KEY}});

            Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
            attributeValues.emplace(":startYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            startYear));
            attributeValues.emplace(":endYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            endYear));
            scanRequest.SetExpressionAttributeValues(attributeValues);

            if (!exclusiveStartKey.empty()) {
                scanRequest.SetExclusiveStartKey(exclusiveStartKey);
            }

            const Aws::DynamoDB::Model::ScanOutcome &result = dynamoClient.Scan(
                    scanRequest);
            if (result.IsSuccess()) {
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
                if (!items.empty()) {
                    std::stringstream stringStream;
                    stringStream << "\nFound " << items.size() << " movies in one
scan."
                                 << " How many would you like to see? ";
                    size_t count = askQuestionForInt(stringStream.str());
                    for (size_t i = 0; i < count && i < items.size(); ++i) {
                        printMovieInfo(items[i]);
                    }
                }
                else {
```

```
                    std::cout << "\nNo movies in the database between " <<
startYear <<
                              " and " << endYear << "." << std::endl;
                }

                exclusiveStartKey = result.GetResult().GetLastEvaluatedKey();
                if (!exclusiveStartKey.empty()) {
                    std::cout << "Not all movies were retrieved. Scanning for
more."
                              << std::endl;
                }
                else {
                    std::cout << "All movies were retrieved with this scan."
                              << std::endl;
                }
            }
            else {
                std::cerr << "Failed to Scan movies: "
                          << result.GetError().GetMessage() << std::endl;
            }
        } while (!exclusiveStartKey.empty());
    }

    // 8. Delete a movie. (DeleteItem)
    {
        std::stringstream stringStream;
        stringStream << "\nWould you like to delete the movie " << title
                     << " from the database? (y/n) ";
        Aws::String answer = askQuestion(stringStream.str());
        if (answer == "y") {
            Aws::DynamoDB::Model::DeleteItemRequest request;
            request.AddKey(YEAR_KEY,
Aws::DynamoDB::Model::AttributeValue().SetN(year));
            request.AddKey(TITLE_KEY,
                           Aws::DynamoDB::Model::AttributeValue().SetS(title));
            request.SetTableName(MOVIE_TABLE_NAME);

            const Aws::DynamoDB::Model::DeleteItemOutcome &result =
dynamoClient.DeleteItem(
                    request);
            if (result.IsSuccess()) {
                std::cout << "\nRemoved \"" << title << "\" from the database."
                          << std::endl;
            }
```

```
            else {
                std::cerr << "Failed to delete the movie: "
                          << result.GetError().GetMessage()
                          << std::endl;
            }
        }
    }

    return true;
}

//! Routine to convert a JsonView object to an attribute map.
/*!
  \sa movieJsonViewToAttributeMap()
  \param jsonView: Json view object.
  \return map: Map that can be used in a DynamoDB request.
 */
Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
AwsDoc::DynamoDB::movieJsonViewToAttributeMap(
        const Aws::Utils::Json::JsonView &jsonView) {
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> result;

    if (jsonView.KeyExists(YEAR_KEY)) {
        result[YEAR_KEY].SetN(jsonView.GetInteger(YEAR_KEY));
    }
    if (jsonView.KeyExists(TITLE_KEY)) {
        result[TITLE_KEY].SetS(jsonView.GetString(TITLE_KEY));
    }
    if (jsonView.KeyExists(INFO_KEY)) {
        Aws::Map<Aws::String, const
 std::shared_ptr<Aws::DynamoDB::Model::AttributeValue>> infoMap;
        Aws::Utils::Json::JsonView infoView = jsonView.GetObject(INFO_KEY);
        if (infoView.KeyExists(RATING_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue
 = std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetN(infoView.GetDouble(RATING_KEY));
            infoMap.emplace(std::make_pair(RATING_KEY, attributeValue));
        }
        if (infoView.KeyExists(PLOT_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue
 = std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetS(infoView.GetString(PLOT_KEY));
            infoMap.emplace(std::make_pair(PLOT_KEY, attributeValue));
        }
```

```
        result[INFO_KEY].SetM(infoMap);
    }

    return result;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);
```

```
        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." <<
 std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
 dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
```

```
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
```

```
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo para criar a tabela e executar ações nela.

```
// RunMovieScenario is an interactive example that shows you how to use the AWS
 SDK for Go
// to create and use an Amazon DynamoDB table that stores data about movies.
//
//   1. Create a table that can hold movie data.
//   2. Put, get, and update a single movie in the table.
//   3. Write movie data to the table from a sample JSON file.
//   4. Query for movies that were released in a given year.
//   5. Scan for movies that were released in a range of years.
//   6. Delete a movie from the table.
//   7. Delete the table.
//
// This example creates a DynamoDB service client from the specified sdkConfig so
 that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
//
// The specified movie sampler is used to get sample data from a URL that is
 loaded
// into the named table.
func RunMovieScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner, tableName string,
 movieSampler actions.IMovieSampler) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
```

```
}()

log.Println(strings.Repeat("-", 88))
log.Println("Welcome to the Amazon DynamoDB getting started demo.")
log.Println(strings.Repeat("-", 88))

tableBasics := actions.TableBasics{TableName: tableName,
 DynamoDbClient: dynamodb.NewFromConfig(sdkConfig)}

exists, err := tableBasics.TableExists()
if err != nil {
 panic(err)
}
if !exists {
 log.Printf("Creating table %v...\n", tableName)
 _, err = tableBasics.CreateMovieTable()
 if err != nil {
  panic(err)
 } else {
  log.Printf("Created table %v.\n", tableName)
 }
} else {
 log.Printf("Table %v already exists.\n", tableName)
}

var customMovie actions.Movie
customMovie.Title = questioner.Ask("Enter a movie title to add to the table:",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
customMovie.Year = questioner.AskInt("What year was it released?",
 []demotools.IAnswerValidator{demotools.NotEmpty{}, demotools.InIntRange{
  Lower: 1900, Upper: 2030}})
customMovie.Info = map[string]interface{}{}
customMovie.Info["rating"] = questioner.AskFloat64(
 "Enter a rating between 1 and 10:", []demotools.IAnswerValidator{
  demotools.NotEmpty{}, demotools.InFloatRange{Lower: 1, Upper: 10}})
customMovie.Info["plot"] = questioner.Ask("What's the plot? ",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
err = tableBasics.AddMovie(customMovie)
if err == nil {
 log.Printf("Added %v to the movie table.\n", customMovie.Title)
}
log.Println(strings.Repeat("-", 88))
```

```
log.Printf("Let's update your movie. You previously rated it %v.\n",
customMovie.Info["rating"])
customMovie.Info["rating"] = questioner.AskFloat64(
 "What new rating would you give it?", []demotools.IAnswerValidator{
  demotools.NotEmpty{}, demotools.InFloatRange{Lower: 1, Upper: 10}})
log.Printf("You summarized the plot as '%v'.\n", customMovie.Info["plot"])
customMovie.Info["plot"] = questioner.Ask("What would you say now?",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
attributes, err := tableBasics.UpdateMovie(customMovie)
if err == nil {
 log.Printf("Updated %v with new values.\n", customMovie.Title)
 for _, attVal := range attributes {
  for valKey, val := range attVal {
   log.Printf("\t%v: %v\n", valKey, val)
  }
 }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Getting movie data from %v and adding 250 movies to the table...\n",
 movieSampler.GetURL())
movies := movieSampler.GetSampleMovies()
written, err := tableBasics.AddMovieBatch(movies, 250)
if err != nil {
 panic(err)
} else {
 log.Printf("Added %v movies to the table.\n", written)
}

show := 10
if show > written {
 show = written
}
log.Printf("The first %v movies in the table are:", show)
for index, movie := range movies[:show] {
 log.Printf("\t%v. %v\n", index+1, movie.Title)
}
movieIndex := questioner.AskInt(
 "Enter the number of a movie to get info about it: ",
[]demotools.IAnswerValidator{
  demotools.InIntRange{Lower: 1, Upper: show}},
)
movie, err := tableBasics.GetMovie(movies[movieIndex-1].Title,
movies[movieIndex-1].Year)
```

```
if err == nil {
 log.Println(movie)
}
log.Println(strings.Repeat("-", 88))

log.Println("Let's get a list of movies released in a given year.")
releaseYear := questioner.AskInt("Enter a year between 1972 and 2018: ",
 []demotools.IAnswerValidator{demotools.InIntRange{Lower: 1972, Upper: 2018}},
)
releases, err := tableBasics.Query(releaseYear)
if err == nil {
 if len(releases) == 0 {
  log.Printf("I couldn't find any movies released in %v!\n", releaseYear)
 } else {
  for _, movie = range releases {
   log.Println(movie)
  }
 }
}
log.Println(strings.Repeat("-", 88))

log.Println("Now let's scan for movies released in a range of years.")
startYear := questioner.AskInt("Enter a year: ", []demotools.IAnswerValidator{
 demotools.InIntRange{Lower: 1972, Upper: 2018}})
endYear := questioner.AskInt("Enter another year: ",
[]demotools.IAnswerValidator{
 demotools.InIntRange{Lower: 1972, Upper: 2018}})
releases, err = tableBasics.Scan(startYear, endYear)
if err == nil {
 if len(releases) == 0 {
  log.Printf("I couldn't find any movies released between %v and %v!\n",
startYear, endYear)
 } else {
  log.Printf("Found %v movies. In this list, the plot is <nil> because "+
   "we used a projection expression when scanning for items to return only "+
   "the title, year, and rating.\n", len(releases))
  for _, movie = range releases {
   log.Println(movie)
  }
 }
}
log.Println(strings.Repeat("-", 88))

var tables []string
```

```
 if questioner.AskBool("Do you want to list all of your tables? (y/n) ", "y") {
  tables, err = tableBasics.ListTables()
  if err == nil {
   log.Printf("Found %v tables:", len(tables))
   for _, table := range tables {
    log.Printf("\t%v", table)
   }
  }
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Let's remove your movie '%v'.\n", customMovie.Title)
 if questioner.AskBool("Do you want to delete it from the table? (y/n) ", "y") {
  err = tableBasics.DeleteMovie(customMovie)
 }
 if err == nil {
  log.Printf("Deleted %v.\n", customMovie.Title)
 }

 if questioner.AskBool("Delete the table, too? (y/n)", "y") {
  err = tableBasics.DeleteTable()
 } else {
  log.Println("Don't forget to delete the table when you're done or you might " +
   "incur charges on your account.")
 }
 if err == nil {
  log.Printf("Deleted table %v.\n", tableBasics.TableName)
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
```

```
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

Crie uma estrutura e métodos que chamem ações do DynamoDB.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified
 table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}
```

```
// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
 exists := true
 _, err := basics.DynamoDbClient.DescribeTable(
  context.TODO(), &dynamodb.DescribeTableInput{TableName:
 aws.String(basics.TableName)},
 )
 if err != nil {
  var notFoundEx *types.ResourceNotFoundException
  if errors.As(err, &notFoundEx) {
   log.Printf("Table %v does not exist.\n", basics.TableName)
   err = nil
  } else {
   log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
 basics.TableName, err)
  }
  exists = false
 }
 return exists, err
}



// CreateMovieTable creates a DynamoDB table with a composite primary key defined
 as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
 var tableDesc *types.TableDescription
 table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
 &dynamodb.CreateTableInput{
  AttributeDefinitions: []types.AttributeDefinition{{
   AttributeName: aws.String("year"),
   AttributeType: types.ScalarAttributeTypeN,
  }, {
   AttributeName: aws.String("title"),
   AttributeType: types.ScalarAttributeTypeS,
  }},
  KeySchema: []types.KeySchemaElement{{
   AttributeName: aws.String("year"),
   KeyType:       types.KeyTypeHash,
  }, {
```

```
    AttributeName: aws.String("title"),
    KeyType:       types.KeyTypeRange,
   }},
   TableName: aws.String(basics.TableName),
   ProvisionedThroughput: &types.ProvisionedThroughput{
    ReadCapacityUnits:  aws.Int64(10),
    WriteCapacityUnits: aws.Int64(10),
   },
  })
  if err != nil {
   log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
  } else {
   waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
   err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
    TableName: aws.String(basics.TableName)}, 5*time.Minute)
   if err != nil {
    log.Printf("Wait for table exists failed. Here's why: %v\n", err)
   }
   tableDesc = table.TableDescription
  }
  return tableDesc, err
}



// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
 var tableNames []string
 var output *dynamodb.ListTablesOutput
 var err error
 tablePaginator := dynamodb.NewListTablesPaginator(basics.DynamoDbClient,
 &dynamodb.ListTablesInput{})
 for tablePaginator.HasMorePages() {
  output, err = tablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't list tables. Here's why: %v\n", err)
   break
  } else {
   tableNames = append(tableNames, output.TableNames...)
  }
 }
 return tableNames, err
}
```

```
// AddMovie adds a movie the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
 item, err := attributevalue.MarshalMap(movie)
 if err != nil {
  panic(err)
 }
 _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
  TableName: aws.String(basics.TableName), Item: item,
 })
 if err != nil {
  log.Printf("Couldn't add item to table. Here's why: %v\n", err)
 }
 return err
}



// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the
 update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
 (map[string]map[string]interface{}, error) {
 var err error
 var response *dynamodb.UpdateItemOutput
 var attributeMap map[string]map[string]interface{}
 update := expression.Set(expression.Name("info.rating"),
 expression.Value(movie.Info["rating"]))
 update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
 expr, err := expression.NewBuilder().WithUpdate(update).Build()
 if err != nil {
  log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
 } else {
  response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
 &dynamodb.UpdateItemInput{
   TableName:                aws.String(basics.TableName),
   Key:                      movie.GetKey(),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   UpdateExpression:         expr.Update(),
   ReturnValues:             types.ReturnValueUpdatedNew,
  })
```

```
  if err != nil {
   log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
  } else {
   err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
   if err != nil {
    log.Printf("Couldn't unmarshall update response. Here's why: %v\n", err)
   }
  }
 }
 return attributeMap, err
}



// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int,
 error) {
 var err error
 var item map[string]types.AttributeValue
 written := 0
 batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
 start := 0
 end := start + batchSize
 for start < maxMovies && start < len(movies) {
  var writeReqs []types.WriteRequest
  if end > len(movies) {
   end = len(movies)
  }
  for _, movie := range movies[start:end] {
   item, err = attributevalue.MarshalMap(movie)
   if err != nil {
    log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
 movie.Title, err)
   } else {
    writeReqs = append(
     writeReqs,
     types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
    )
   }
  }
  _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
 &dynamodb.BatchWriteItemInput{
```

```
    RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
   if err != nil {
    log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
  basics.TableName, err)
   } else {
    written += len(writeReqs)
   }
   start = end
   end += batchSize
  }

  return written, err
}



// GetMovie gets movie data from the DynamoDB table by using the primary
 composite key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
 movie := Movie{Title: title, Year: year}
 response, err := basics.DynamoDbClient.GetItem(context.TODO(),
 &dynamodb.GetItemInput{
  Key: movie.GetKey(), TableName: aws.String(basics.TableName),
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Item, &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}



// Query gets all movies in the DynamoDB table that were released in the
 specified year.
// The function uses the `expression` package to build the key condition
 expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
```

```
 var err error
 var response *dynamodb.QueryOutput
 var movies []Movie
 keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
 expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
 if err != nil {
  log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
 } else {
  queryPaginator := dynamodb.NewQueryPaginator(basics.DynamoDbClient,
 &dynamodb.QueryInput{
   TableName:                aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   KeyConditionExpression:    expr.KeyCondition(),
  })
  for queryPaginator.HasMorePages() {
   response, err = queryPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
 releaseYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}



// Scan gets all movies in the DynamoDB table that were released in a range of
 years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
```

```
 var movies []Movie
 var err error
 var response *dynamodb.ScanOutput
 filtEx := expression.Name("year").Between(expression.Value(startYear),
 expression.Value(endYear))
 projEx := expression.NamesList(
  expression.Name("year"), expression.Name("title"),
 expression.Name("info.rating"))
 expr, err :=
 expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
 if err != nil {
  log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
 } else {
  scanPaginator := dynamodb.NewScanPaginator(basics.DynamoDbClient,
 &dynamodb.ScanInput{
   TableName:                 aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   FilterExpression:          expr.Filter(),
   ProjectionExpression:      expr.Projection(),
  })
  for scanPaginator.HasMorePages() {
   response, err = scanPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't scan for movies released between %v and %v. Here's why:
 %v\n",
     startYear, endYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}
```

```
// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
 _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
 &dynamodb.DeleteItemInput{
  TableName: aws.String(basics.TableName), Key: movie.GetKey(),
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}



// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
 _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
 &dynamodb.DeleteTableInput{
  TableName: aws.String(basics.TableName)})
 if err != nil {
  log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query

- Scan
- UpdateItem

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela do DynamoDB.

```
// Create a table with a Sort key.
public static void createTable(DynamoDbClient ddb, String tableName) {
    DynamoDbWaiter dbWaiter = ddb.waiter();
    ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

    // Define attributes.
    attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("year")
            .attributeType("N")
            .build());

    attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("title")
            .attributeType("S")
            .build());

    ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
    KeySchemaElement key = KeySchemaElement.builder()
            .attributeName("year")
            .keyType(KeyType.HASH)
            .build();

    KeySchemaElement key2 = KeySchemaElement.builder()
            .attributeName("title")
            .keyType(KeyType.RANGE)
            .build();
```

```
        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(ddb)
                .build();
```

```
        DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        while (iter.hasNext()) {
            // Only add 200 Movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            Movies movies = new Movies();
            movies.setYear(year);
            movies.setTitle(title);
            movies.setInfo(info);

            // Put the data into the Amazon DynamoDB Movie table.
            mappedTable.putItem(movies);
            t++;
        }
    }
```

Obtenha um item de uma tabela.

```
    public static void getItem(DynamoDbClient ddb) {

        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put("year", AttributeValue.builder()
                .n("1933")
                .build());

        keyToGet.put("title", AttributeValue.builder()
                .s("King Kong")
                .build());
```

```
        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName("Movies")
                .build();

        try {
            Map<String, AttributeValue> returnedItem =
 ddb.getItem(request).item();

            if (returnedItem != null) {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");

                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
 returnedItem.get(key1).toString());
                }
            } else {
                System.out.format("No item found with the key %s!\n", "year");
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

Exemplo completo.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java example performs these tasks:
 *
 * 1. Creates the Amazon DynamoDB Movie table with partition and sort key.
```

```
 * 2. Puts data into the Amazon DynamoDB table from a JSON document using the
 * Enhanced client.
 * 3. Gets data from the Movie table.
 * 4. Adds a new item.
 * 5. Updates an item.
 * 6. Uses a Scan to query items using the Enhanced client.
 * 7. Queries all items where the year is 2013 using the Enhanced Client.
 * 8. Deletes the table.
 */

public class Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <fileName>

                Where:
                    fileName - The path to the moviedata.json file that you can
 download from the Amazon DynamoDB Developer Guide.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = "Movies";
        String fileName = args[0];
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon DynamoDB example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
```

```
                "1. Creating an Amazon DynamoDB table named Movies with a key
named year and a sort key named title.");
        createTable(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Loading data into the Amazon DynamoDB table.");
        loadData(ddb, tableName, fileName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Getting data from the Movie table.");
        getItem(ddb);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Putting a record into the Amazon DynamoDB
table.");
        putRecord(ddb);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Updating a record.");
        updateTableItem(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Scanning the Amazon DynamoDB table.");
        scanMovies(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Querying the Movies released in 2013.");
        queryTable(ddb);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
        System.out.println(DASHES);

        ddb.close();
    }
```

```
    // Create a table with a Sort key.
    public static void createTable(DynamoDbClient ddb, String tableName) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("year")
                .attributeType("N")
                .build());

        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("title")
                .attributeType("S")
                .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
                .attributeName("year")
                .keyType(KeyType.HASH)
                .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
                .attributeName("title")
                .keyType(KeyType.RANGE)
                .build();

        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
```

```
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Query the table.
    public static void queryTable(DynamoDbClient ddb) {
        try {
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
                    .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            QueryConditional queryConditional = QueryConditional
                    .keyEqualTo(Key.builder()
                            .partitionValue(2013)
                            .build());

            // Get items in the table and write out the ID value.
            Iterator<Movies> results =
custTable.query(queryConditional).items().iterator();
            String result = "";

            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The title of the movie is " +
rec.getTitle());
                System.out.println("The movie information  is " + rec.getInfo());
            }

        } catch (DynamoDbException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Scan the table.
    public static void scanMovies(DynamoDbClient ddb, String tableName) {
        System.out.println("******* Scanning all movies.\n");
        try {
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
                    .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            Iterator<Movies> results = custTable.scan().items().iterator();
            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The movie title is " + rec.getTitle());
                System.out.println("The movie year is " + rec.getYear());
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(ddb)
                .build();

        DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
```

```
        while (iter.hasNext()) {
            // Only add 200 Movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            Movies movies = new Movies();
            movies.setYear(year);
            movies.setTitle(title);
            movies.setInfo(info);

            // Put the data into the Amazon DynamoDB Movie table.
            mappedTable.putItem(movies);
            t++;
        }
    }

    // Update the record to include show only directors.
    public static void updateTableItem(DynamoDbClient ddb, String tableName) {
        HashMap<String, AttributeValue> itemKey = new HashMap<>();
        itemKey.put("year", AttributeValue.builder().n("1933").build());
        itemKey.put("title", AttributeValue.builder().s("King Kong").build());

        HashMap<String, AttributeValueUpdate> updatedValues = new HashMap<>();
        updatedValues.put("info", AttributeValueUpdate.builder()
                .value(AttributeValue.builder().s("{\"directors\":[\"Merian C.
Cooper\",\"Ernest B. Schoedsack\"]")
                        .build())
                .action(AttributeAction.PUT)
                .build());

        UpdateItemRequest request = UpdateItemRequest.builder()
                .tableName(tableName)
                .key(itemKey)
                .attributeUpdates(updatedValues)
                .build();

        try {
            ddb.updateItem(request);
        } catch (ResourceNotFoundException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }

        System.out.println("Item was updated!");
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName)
{
        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }

    public static void putRecord(DynamoDbClient ddb) {
        try {
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
                    .build();

            DynamoDbTable<Movies> table = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));

            // Populate the Table.
            Movies record = new Movies();
            record.setYear(2020);
            record.setTitle("My Movie2");
            record.setInfo("no info");
            table.putItem(record);

        } catch (DynamoDbException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("Added a new movie to the table.");
    }

    public static void getItem(DynamoDbClient ddb) {

        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put("year", AttributeValue.builder()
                .n("1933")
                .build());

        keyToGet.put("title", AttributeValue.builder()
                .s("King Kong")
                .build());

        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName("Movies")
                .build();

        try {
            Map<String, AttributeValue> returnedItem =
 ddb.getItem(request).item();

            if (returnedItem != null) {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");

                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
 returnedItem.get(key1).toString());
                }
            } else {
                System.out.format("No item found with the key %s!\n", "year");
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { readFileSync } from "fs";
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";

/**
 * This module is a convenience library. It abstracts Amazon DynamoDB's data type
 * descriptors (such as S, N, B, and BOOL) by marshalling JavaScript objects into
```

```
 * AttributeValue shapes.
 */
import {
  BatchWriteCommand,
  DeleteCommand,
  DynamoDBDocumentClient,
  GetCommand,
  PutCommand,
  UpdateCommand,
  paginateQuery,
  paginateScan,
} from "@aws-sdk/lib-dynamodb";

// These modules are local to our GitHub repository. We recommend cloning
// the project from GitHub if you want to run this example.
// For more information, see https://github.com/awsdocs/aws-doc-sdk-examples.
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { chunkArray } from "@aws-sdk-examples/libs/utils/util-array.js";

const dirname = dirnameFromMetaUrl(import.meta.url);
const tableName = getUniqueName("Movies");
const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);

export const main = async () => {
  /**
   * Create a table.
   */

  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
    // Set the billing mode to PAY_PER_REQUEST to
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
    AttributeDefinitions: [
      {
        AttributeName: "year",
        // 'N' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
```

```
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "N",
      },
      { AttributeName: "title", AttributeType: "S" },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [
      // The way your data is accessed determines how you structure your keys.
      // The movies table will be queried for movies by year. It makes sense
      // to make year our partition (HASH) key.
      { AttributeName: "year", KeyType: "HASH" },
      { AttributeName: "title", KeyType: "RANGE" },
    ],
  });

  log("Creating a table.");
  const createTableResponse = await client.send(createTableCommand);
  log(`Table created: ${JSON.stringify(createTableResponse.TableDescription)}`);

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Add a movie to the table.
   */

  log("Adding a single movie to the table.");
  // PutCommand is the first example usage of 'lib-dynamodb'.
  const putCommand = new PutCommand({
    TableName: tableName,
    Item: {
      // In 'client-dynamodb', the AttributeValue would be required (`year: { N:
 1981 }`)
      // 'lib-dynamodb' simplifies the usage ( `year: 1981` )
      year: 1981,
```

```
      // The preceding KeySchema defines 'title' as our sort (RANGE) key, so
 'title'
      // is required.
      title: "The Evil Dead",
      // Every other attribute is optional.
      info: {
        genres: ["Horror"],
      },
    },
  });
  await docClient.send(putCommand);
  log("The movie was added.");

  /**
   * Get a movie from the table.
   */

  log("Getting a single movie from the table.");
  const getCommand = new GetCommand({
    TableName: tableName,
    // Requires the complete primary key. For the movies table, the primary key
    // is only the id (partition key).
    Key: {
      year: 1981,
      title: "The Evil Dead",
    },
    // Set this to make sure that recent writes are reflected.
    // For more information, see https://docs.aws.amazon.com/amazondynamodb/
latest/developerguide/HowItWorks.ReadConsistency.html.
    ConsistentRead: true,
  });
  const getResponse = await docClient.send(getCommand);
  log(`Got the movie: ${JSON.stringify(getResponse.Item)}`);

  /**
   * Update a movie in the table.
   */

  log("Updating a single movie in the table.");
  const updateCommand = new UpdateCommand({
    TableName: tableName,
    Key: { year: 1981, title: "The Evil Dead" },
    // This update expression appends "Comedy" to the list of genres.
    // For more information on update expressions, see
```

```
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Expressions.UpdateExpressions.html
    UpdateExpression: "set #i.#g = list_append(#i.#g, :vals)",
    ExpressionAttributeNames: { "#i": "info", "#g": "genres" },
    ExpressionAttributeValues: {
      ":vals": ["Comedy"],
    },
    ReturnValues: "ALL_NEW",
  });
  const updateResponse = await docClient.send(updateCommand);
  log(`Movie updated: ${JSON.stringify(updateResponse.Attributes)}`);

  /**
   * Delete a movie from the table.
   */

  log("Deleting a single movie from the table.");
  const deleteCommand = new DeleteCommand({
    TableName: tableName,
    Key: { year: 1981, title: "The Evil Dead" },
  });
  await client.send(deleteCommand);
  log("Movie deleted.");

  /**
   * Upload a batch of movies.
   */

  log("Adding movies from local JSON file.");
  const file = readFileSync(
    `${dirname}../../../../resources/sample_files/movies.json`,
  );
  const movies = JSON.parse(file.toString());
  // chunkArray is a local convenience function. It takes an array and returns
  // a generator function. The generator function yields every N items.
  const movieChunks = chunkArray(movies, 25);
  // For every chunk of 25 movies, make one BatchWrite request.
  for (const chunk of movieChunks) {
    const putRequests = chunk.map((movie) => ({
      PutRequest: {
        Item: movie,
      },
    }));
```

```
    const command = new BatchWriteCommand({
      RequestItems: {
        [tableName]: putRequests,
      },
    });

    await docClient.send(command);
  }
  log("Movies added.");

  /**
   * Query for movies by year.
   */

  log("Querying for all movies from 1981.");
  const paginatedQuery = paginateQuery(
    { client: docClient },
    {
      TableName: tableName,
      //For more information about query expressions, see
      // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Query.html#Query.KeyConditionExpressions
      KeyConditionExpression: "#y = :y",
      // 'year' is a reserved word in DynamoDB. Indicate that it's an attribute
      // name by using an expression attribute name.
      ExpressionAttributeNames: { "#y": "year" },
      ExpressionAttributeValues: { ":y": 1981 },
      ConsistentRead: true,
    },
  );
  /**
   * @type { Record<string, any>[] };
   */
  const movies1981 = [];
  for await (const page of paginatedQuery) {
    movies1981.push(...page.Items);
  }
  log(`Movies: ${movies1981.map((m) => m.title).join(", ")}`);

  /**
   * Scan the table for movies between 1980 and 1990.
   */

  log(`Scan for movies released between 1980 and 1990`);
```

```
  // A 'Scan' operation always reads every item in the table. If your design
 requires
  // the use of 'Scan', consider indexing your table or changing your design.
  // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/bp-query-
scan.html
  const paginatedScan = paginateScan(
    { client: docClient },
    {
      TableName: tableName,
      // Scan uses a filter expression instead of a key condition expression.
 Scan will
      // read the entire table and then apply the filter.
      FilterExpression: "#y between :y1 and :y2",
      ExpressionAttributeNames: { "#y": "year" },
      ExpressionAttributeValues: { ":y1": 1980, ":y2": 1990 },
      ConsistentRead: true,
    },
  );
  /**
   * @type { Record<string, any>[] };
   */
  const movies1980to1990 = [];
  for await (const page of paginatedScan) {
    movies1980to1990.push(...page.Items);
  }
  log(
    `Movies: ${movies1980to1990
      .map((m) => `${m.title} (${m.year})`)
      .join(", ")}`,
  );

  /**
   * Delete the table.
   */

  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
  log(`Deleting table ${tableName}.`);
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela do DynamoDB.

```
suspend fun createScenarioTable(tableNameVal: String, key: String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
```

```
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
 ${response.tableDescription?.tableArn}")
    }
}
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
```

```
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
        putMovie(tableName, year, title, info)
        t++
    }
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()
    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}
```

Obtenha um item de uma tabela.

```
suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
```

```
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}
```

Exemplo completo.

```
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
          <fileName>

        Where:
           fileName - The path to the moviedata.json you can download from the
 Amazon DynamoDB Developer Guide.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(1)
    }

    // Get the moviedata.json from the Amazon DynamoDB Developer Guide.
    val tableName = "Movies"
    val fileName = args[0]
    val partitionAlias = "#a"

    println("Creating an Amazon DynamoDB table named Movies with a key named id
 and a sort key named title.")
```

```
    createScenarioTable(tableName, "year")
    loadData(tableName, fileName)
    getMovie(tableName, "year", "1933")
    scanMovies(tableName)
    val count = queryMovieTable(tableName, "year", partitionAlias)
    println("There are $count Movies released in 2013.")
    deletIssuesTable(tableName)
}

suspend fun createScenarioTable(tableNameVal: String, key: String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
```

```
        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
 ${response.tableDescription?.tableArn}")
    }
}

// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
        putMovie(tableName, year, title, info)
        t++
    }
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()
    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)
```

```
    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}

suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}

suspend fun deletIssuesTable(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}

suspend fun queryMovieTable(
    tableNameVal: String,
```

```
    partitionKeyName: String,
    partitionAlias: String
): Int {
    val attrNameAlias = mutableMapOf<String, String>()
    attrNameAlias[partitionAlias] = "year"

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.N("2013")

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
    }
}

suspend fun scanMovies(tableNameVal: String) {
    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - BatchWriteItem

- CreateTable
- DeleteItem
- DeleteTable
- DescribeTable
- GetItem
- PutItem
- Query
- Scan
- UpdateItem

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace DynamoDb\Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;
use DynamoDb\DynamoDBService;

use function AwsUtilities\loadMovieData;
use function AwsUtilities\testable_readline;

class GettingStartedWithDynamoDB
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB getting started demo using PHP!
\n");
```

```
        echo("-------------------------------------\n");

        $uuid = uniqid();
        $service = new DynamoDBService();

        $tableName = "ddb_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
$tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }

        $service->putItem([
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
            'TableName' => $tableName,
        ]);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
```

```
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $key = [
            'Item' => [
                'title' => [
                    'S' => $movieName,
                ],
                'year' => [
                    'N' => $movieYear,
                ],
            ]
        ];
        $attributes = ["rating" =>
            [
                'AttributeName' => 'rating',
                'AttributeType' => 'N',
                'Value' => $rating,
            ],
            'plot' => [
                'AttributeName' => 'plot',
                'AttributeType' => 'S',
                'Value' => $plot,
            ]
        ];
        $service->updateItemAttributesByKey($tableName, $key, $attributes);
        echo "Movie added and updated.";

        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);


        $movie = $service->getItemByKey($tableName, $key);
        echo "\nThe movie {$movie['Item']['title']['S']} was released in
 {$movie['Item']['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Item']['title']['S']}?
\n";
        $rating = 0;
```

```
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
|| $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $service->updateItemAttributeByKey($tableName, $key, 'rating', 'N',
$rating);

        $movie = $service->getItemByKey($tableName, $key);
        echo "Ok, you have rated {$movie['Item']['title']['S']} as a
{$movie['Item']['rating']['N']}\n";

        $service->deleteItemByKey($tableName, $key);
        echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something
lighter, in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were
born:\n";
        $oops = "Oops! There were no movies released in that year (that we know
of).\n";
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
        echo ($display) ?: $oops;

        $yearsKey = [
            'Key' => [
                'year' => [
```

```
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que encapsule uma tabela do DynamoDB.

```
from decimal import Decimal
from io import BytesIO
import json
import logging
import os
from pprint import pprint
import requests
from zipfile import ZipFile
import boto3
from boto3.dynamodb.conditions import Key
from botocore.exceptions import ClientError
from question import Question

logger = logging.getLogger(__name__)

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
```

```
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                exists = False
            else:
                logger.error(
                    "Couldn't check for existence of %s. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            self.table = table
        return exists


    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.

        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {"AttributeName": "year", "KeyType": "HASH"},  # Partition
key
                    {"AttributeName": "title", "KeyType": "RANGE"},  # Sort key
                ],
                AttributeDefinitions=[
                    {"AttributeName": "year", "AttributeType": "N"},
```

```
                    {"AttributeName": "title", "AttributeType": "S"},
                ],
                ProvisionedThroughput={
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 10,
                },
            )
            self.table.wait_until_exists()
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.table


    def list_tables(self):
        """
        Lists the Amazon DynamoDB tables for the current account.

        :return: The list of tables.
        """
        try:
            tables = []
            for table in self.dyn_resource.tables.all():
                print(table.name)
                tables.append(table)
        except ClientError as err:
            logger.error(
                "Couldn't list tables. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tables


    def write_batch(self, movies):
        """
```

```
        Fills an Amazon DynamoDB table with the specified data, using the Boto3
        Table.batch_writer() function to put the items in the table.
        Inside the context manager, Table.batch_writer builds a list of
        requests. On exiting the context manager, Table.batch_writer starts
sending
        batches of write requests to Amazon DynamoDB and automatically
        handles chunking, buffering, and retrying.

        :param movies: The data to put in the table. Each item must contain at
least
                       the keys required by the schema that was specified when
the
                       table was created.
        """
        try:
            with self.table.batch_writer() as writer:
                for movie in movies:
                    writer.put_item(Item=movie)
        except ClientError as err:
            logger.error(
                "Couldn't load data into table %s. Here's why: %s: %s",
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    "year": year,
                    "title": title,
                    "info": {"plot": plot, "rating": Decimal(str(rating))},
                }
```

```
            )
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Item"]


    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to the give the movie.
        :param plot: The updated plot summary to give the movie.
        :return: The fields that were updated, with their new values.
```

```
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
                ExpressionAttributeValues={":r": Decimal(str(rating)), ":p":
plot},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]


    def query_movies(self, year):
        """
        Queries for movies that were released in the specified year.

        :param year: The year to query.
        :return: The list of movies that were released in the specified year.
        """
        try:
            response =
self.table.query(KeyConditionExpression=Key("year").eq(year))
        except ClientError as err:
            logger.error(
                "Couldn't query for movies released in %s. Here's why: %s: %s",
                year,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Items"]
```

```
    def scan_movies(self, year_range):
        """
        Scans for movies that were released in a range of years.
        Uses a projection expression to return a subset of data for each movie.

        :param year_range: The range of years to retrieve.
        :return: The list of movies released in the specified years.
        """
        movies = []
        scan_kwargs = {
            "FilterExpression": Key("year").between(
                year_range["first"], year_range["second"]
            ),
            "ProjectionExpression": "#yr, title, info.rating",
            "ExpressionAttributeNames": {"#yr": "year"},
        }
        try:
            done = False
            start_key = None
            while not done:
                if start_key:
                    scan_kwargs["ExclusiveStartKey"] = start_key
                response = self.table.scan(**scan_kwargs)
                movies.extend(response.get("Items", []))
                start_key = response.get("LastEvaluatedKey", None)
                done = start_key is None
        except ClientError as err:
            logger.error(
                "Couldn't scan for movies. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

        return movies


    def delete_movie(self, title, year):
        """
        Deletes a movie from the table.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        """
```

```
        try:
            self.table.delete_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s",
                title,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_table(self):
        """
        Deletes the table.
        """
        try:
            self.table.delete()
            self.table = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
def get_sample_movie_data(movie_file_name):
    """
    Gets sample movie data, either from a local file or by first downloading it
 from
    the Amazon DynamoDB developer guide.

    :param movie_file_name: The local file name where the movie data is stored in
 JSON format.
    :return: The movie data as a dict.
    """
```

```
    if not os.path.isfile(movie_file_name):
        print(f"Downloading {movie_file_name}...")
        movie_content = requests.get(
            "https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
samples/moviedata.zip"
        )
        movie_zip = ZipFile(BytesIO(movie_content.content))
        movie_zip.extractall()

    try:
        with open(movie_file_name) as movie_file:
            movie_data = json.load(movie_file, parse_float=Decimal)
    except FileNotFoundError:
        print(
            f"File {movie_file_name} not found. You must first download the file
 to "
            "run this demo. See the README for instructions."
        )
        raise
    else:
        # The sample file lists over 4000 movies, return only the first 250.
        return movie_data[:250]
```

Execute um cenário interativo para criar a tabela e executar ações nela.

```
def run_scenario(table_name, movie_file_name, dyn_resource):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB getting started demo.")
    print("-" * 88)

    movies = Movies(dyn_resource)
    movies_exists = movies.exists(table_name)
    if not movies_exists:
        print(f"\nCreating table {table_name}...")
        movies.create_table(table_name)
        print(f"\nCreated table {movies.table.name}.")

    my_movie = Question.ask_questions(
```

```
        [
            Question(
                "title", "Enter the title of a movie you want to add to the
table: "
            ),
            Question("year", "What year was it released? ", Question.is_int),
            Question(
                "rating",
                "On a scale of 1 - 10, how do you rate it? ",
                Question.is_float,
                Question.in_range(1, 10),
            ),
            Question("plot", "Summarize the plot for me: "),
        ]
    )
    movies.add_movie(**my_movie)
    print(f"\nAdded '{my_movie['title']}' to '{movies.table.name}'.")
    print("-" * 88)

    movie_update = Question.ask_questions(
        [
            Question(
                "rating",
                f"\nLet's update your movie.\nYou rated it {my_movie['rating']},
what new "
                f"rating would you give it? ",
                Question.is_float,
                Question.in_range(1, 10),
            ),
            Question(
                "plot",
                f"You summarized the plot as '{my_movie['plot']}'.\nWhat would
you say now? ",
            ),
        ]
    )
    my_movie.update(movie_update)
    updated = movies.update_movie(**my_movie)
    print(f"\nUpdated '{my_movie['title']}' with new attributes:")
    pprint(updated)
    print("-" * 88)

    if not movies_exists:
        movie_data = get_sample_movie_data(movie_file_name)
```

```
        print(f"\nReading data from '{movie_file_name}' into your table.")
        movies.write_batch(movie_data)
        print(f"\nWrote {len(movie_data)} movies into {movies.table.name}.")
    print("-" * 88)

    title = "The Lord of the Rings: The Fellowship of the Ring"
    if Question.ask_question(
        f"Let's move on...do you want to get info about '{title}'? (y/n) ",
        Question.is_yesno,
    ):
        movie = movies.get_movie(title, 2001)
        print("\nHere's what I found:")
        pprint(movie)
    print("-" * 88)

    ask_for_year = True
    while ask_for_year:
        release_year = Question.ask_question(
            f"\nLet's get a list of movies released in a given year. Enter a year
between "
            f"1972 and 2018: ",
            Question.is_int,
            Question.in_range(1972, 2018),
        )
        releases = movies.query_movies(release_year)
        if releases:
            print(f"There were {len(releases)} movies released in
{release_year}:")
            for release in releases:
                print(f"\t{release['title']}")
            ask_for_year = False
        else:
            print(f"I don't know about any movies released in {release_year}!")
            ask_for_year = Question.ask_question(
                "Try another year? (y/n) ", Question.is_yesno
            )
    print("-" * 88)

    years = Question.ask_questions(
        [
            Question(
                "first",
                f"\nNow let's scan for movies released in a range of years. Enter
a year: ",
```

```
                Question.is_int,
                Question.in_range(1972, 2018),
            ),
            Question(
                "second",
                "Now enter another year: ",
                Question.is_int,
                Question.in_range(1972, 2018),
            ),
        ]
    )
    releases = movies.scan_movies(years)
    if releases:
        count = Question.ask_question(
            f"\nFound {len(releases)} movies. How many do you want to see? ",
            Question.is_int,
            Question.in_range(1, len(releases)),
        )
        print(f"\nHere are your {count} movies:\n")
        pprint(releases[:count])
    else:
        print(
            f"I don't know about any movies released between {years['first']} "
            f"and {years['second']}."
        )
    print("-" * 88)

    if Question.ask_question(
        f"\nLet's remove your movie from the table. Do you want to remove "
        f"'{my_movie['title']}'? (y/n)",
        Question.is_yesno,
    ):
        movies.delete_movie(my_movie["title"], my_movie["year"])
        print(f"\nRemoved '{my_movie['title']}' from the table.")
    print("-" * 88)

    if Question.ask_question(f"\nDelete the table? (y/n) ", Question.is_yesno):
        movies.delete_table()
        print(f"Deleted {table_name}.")
    else:
        print(
            "Don't forget to delete the table when you're done or you might incur
"
            "charges on your account."
```

```
        )

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        run_scenario(
            "doc-example-table-movies", "moviedata.json",
 boto3.resource("dynamodb")
        )
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

Esse cenário usa a classe auxiliar a seguir para fazer perguntas em um prompt de comando.

```
class Question:
    """
    A helper class to ask questions at a command prompt and validate and convert
    the answers.
    """

    def __init__(self, key, question, *validators):
        """
        :param key: The key that is used for storing the answer in a dict, when
                    multiple questions are asked in a set.
        :param question: The question to ask.
        :param validators: The answer is passed through the list of validators
 until
                           one fails or they all pass. Validators may also
 convert the
                           answer to another form, such as from a str to an int.
        """
        self.key = key
        self.question = question
        self.validators = Question.non_empty, *validators

    @staticmethod
    def ask_questions(questions):
        """
        Asks a set of questions and stores the answers in a dict.
```

```
        :param questions: The list of questions to ask.
        :return: A dict of answers.
        """
        answers = {}
        for question in questions:
            answers[question.key] = Question.ask_question(
                question.question, *question.validators
            )
        return answers

    @staticmethod
    def ask_question(question, *validators):
        """
        Asks a single question and validates it against a list of validators.
        When an answer fails validation, the complaint is printed and the
question
        is asked again.

        :param question: The question to ask.
        :param validators: The list of validators that the answer must pass.
        :return: The answer, converted to its final form by the validators.
        """
        answer = None
        while answer is None:
            answer = input(question)
            for validator in validators:
                answer, complaint = validator(answer)
                if answer is None:
                    print(complaint)
                    break
        return answer

    @staticmethod
    def non_empty(answer):
        """
        Validates that the answer is not empty.
        :return: The non-empty answer, or None.
        """
        return answer if answer != "" else None, "I need an answer. Please?"

    @staticmethod
    def is_yesno(answer):
        """
```

```
        Validates a yes/no answer.
        :return: True when the answer is 'y'; otherwise, False.
        """
        return answer.lower() == "y", ""

    @staticmethod
    def is_int(answer):
        """
        Validates that the answer can be converted to an int.
        :return: The int answer; otherwise, None.
        """
        try:
            int_answer = int(answer)
        except ValueError:
            int_answer = None
        return int_answer, f"{answer} must be a valid integer."

    @staticmethod
    def is_letter(answer):
        """
        Validates that the answer is a letter.
        :return The letter answer, converted to uppercase; otherwise, None.
        """
        return (
            answer.upper() if answer.isalpha() else None,
            f"{answer} must be a single letter.",
        )

    @staticmethod
    def is_float(answer):
        """
        Validate that the answer can be converted to a float.
        :return The float answer; otherwise, None.
        """
        try:
            float_answer = float(answer)
        except ValueError:
            float_answer = None
        return float_answer, f"{answer} must be a valid float."

    @staticmethod
    def in_range(lower, upper):
        """
```

```
        Validate that the answer is within a range. The answer must be of a type
that can
        be compared to the lower and upper bounds.
        :return: The answer, if it is within the range; otherwise, None.
        """

        def _validate(answer):
            return (
                answer if lower <= answer <= upper else None,
                f"{answer} must be between {lower} and {upper}.",
            )

        return _validate
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que encapsule uma tabela do DynamoDB.

```
# Creates an Amazon DynamoDB table that can be used to store movie data.
# The table uses the release year of the movie as the partition key and the
# title as the sort key.
#
# @param table_name [String] The name of the table to create.
# @return [Aws::DynamoDB::Table] The newly created table.
def create_table(table_name)
  @table = @dynamo_resource.create_table(
    table_name: table_name,
    key_schema: [
      {attribute_name: "year", key_type: "HASH"},  # Partition key
      {attribute_name: "title", key_type: "RANGE"}  # Sort key
    ],
    attribute_definitions: [
      {attribute_name: "year", attribute_type: "N"},
      {attribute_name: "title", attribute_type: "S"}
    ],
    provisioned_throughput: {read_capacity_units: 10, write_capacity_units:
10})
  @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
  @table
rescue Aws::DynamoDB::Errors::ServiceError => e
  @logger.error("Failed create table #{table_name}:\n#{e.code}: #{e.message}")
  raise
end
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
  # Gets sample movie data, either from a local file or by first downloading it
 from
  # the Amazon DynamoDB Developer Guide.
  #
  # @param movie_file_name [String] The local file name where the movie data is
 stored in JSON format.
  # @return [Hash] The movie data as a Hash.
  def fetch_movie_data(movie_file_name)
    if !File.file?(movie_file_name)
      @logger.debug("Downloading #{movie_file_name}...")
      movie_content = URI.open(
        "https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
samples/moviedata.zip"
      )
      movie_json = ""
      Zip::File.open_buffer(movie_content) do |zip|
        zip.each do |entry|
          movie_json = entry.get_input_stream.read
        end
      end
    else
      movie_json = File.read(movie_file_name)
    end
    movie_data = JSON.parse(movie_json)
    # The sample file lists over 4000 movies. This returns only the first 250.
    movie_data.slice(0, 250)
  rescue StandardError => e
    puts("Failure downloading movie data:\n#{e}")
    raise
  end
```

Execute um cenário interativo para criar a tabela e executar ações nela.

```
  table_name = "doc-example-table-movies-#{rand(10**4)}"
  scaffold = Scaffold.new(table_name)
  dynamodb_wrapper = DynamoDBBasics.new(table_name)

  new_step(1, "Create a new DynamoDB table if none already exists.")
  unless scaffold.exists?(table_name)
    puts("\nNo such table: #{table_name}. Creating it...")
    scaffold.create_table(table_name)
    print "Done!\n".green
```

```
 end

 new_step(2, "Add a new record to the DynamoDB table.")
 my_movie = {}
 my_movie[:title] = CLI::UI::Prompt.ask("Enter the title of a movie to add to
the table. E.g. The Matrix")
 my_movie[:year] = CLI::UI::Prompt.ask("What year was it released? E.g.
1989").to_i
 my_movie[:rating] = CLI::UI::Prompt.ask("On a scale of 1 - 10, how do you rate
it? E.g. 7").to_i
 my_movie[:plot] = CLI::UI::Prompt.ask("Enter a brief summary of the plot. E.g.
A man awakens to a new reality.")
 dynamodb_wrapper.add_item(my_movie)
 puts("\nNew record added:")
 puts JSON.pretty_generate(my_movie).green
 print "Done!\n".green

 new_step(3, "Update a record in the DynamoDB table.")
 my_movie[:rating] = CLI::UI::Prompt.ask("Let's update the movie you added with
a new rating, e.g. 3:").to_i
 response = dynamodb_wrapper.update_item(my_movie)
 puts("Updated '#{my_movie[:title]}' with new attributes:")
 puts JSON.pretty_generate(response).green
 print "Done!\n".green

 new_step(4, "Get a record from the DynamoDB table.")
 puts("Searching for #{my_movie[:title]} (#{my_movie[:year]})...")
 response = dynamodb_wrapper.get_item(my_movie[:title], my_movie[:year])
 puts JSON.pretty_generate(response).green
 print "Done!\n".green

 new_step(5, "Write a batch of items into the DynamoDB table.")
 download_file = "moviedata.json"
 puts("Downloading movie database to #{download_file}...")
 movie_data = scaffold.fetch_movie_data(download_file)
 puts("Writing movie data from #{download_file} into your table...")
 scaffold.write_batch(movie_data)
 puts("Records added: #{movie_data.length}.")
 print "Done!\n".green

 new_step(5, "Query for a batch of items by key.")
 loop do
   release_year = CLI::UI::Prompt.ask("Enter a year between 1972 and 2018, e.g.
1999:").to_i
```

```
    results = dynamodb_wrapper.query_items(release_year)
    if results.any?
      puts("There were #{results.length} movies released in #{release_year}:")
      results.each do |movie|
        print "\t #{movie["title"]}".green
      end
      break
    else
      continue = CLI::UI::Prompt.ask("Found no movies released in
 #{release_year}! Try another year? (y/n)")
      break if !continue.eql?("y")
    end
  end
  print "\nDone!\n".green

  new_step(6, "Scan for a batch of items using a filter expression.")
  years = {}
  years[:start] = CLI::UI::Prompt.ask("Enter a starting year between 1972 and
 2018:")
  years[:end] = CLI::UI::Prompt.ask("Enter an ending year between 1972 and
 2018:")
  releases = dynamodb_wrapper.scan_items(years)
  if !releases.empty?
    puts("Found #{releases.length} movies.")
    count = Question.ask(
      "How many do you want to see? ", method(:is_int), in_range(1,
 releases.length))
    puts("Here are your #{count} movies:")
    releases.take(count).each do |release|
      puts("\t#{release["title"]}")
    end
  else
    puts("I don't know about any movies released between #{years[:start]} "\
         "and #{years[:end]}.")
  end
  print "\nDone!\n".green

  new_step(7, "Delete an item from the DynamoDB table.")
  answer = CLI::UI::Prompt.ask("Do you want to remove '#{my_movie[:title]}'? (y/
n) ")
  if answer.eql?("y")
    dynamodb_wrapper.delete_item(my_movie[:title], my_movie[:year])
    puts("Removed '#{my_movie[:title]}' from the table.")
    print "\nDone!\n".green
```

```
  end

  new_step(8, "Delete the DynamoDB table.")
  answer = CLI::UI::Prompt.ask("Delete the table? (y/n)")
  if answer.eql?("y")
    scaffold.delete_table
    puts("Deleted #{table_name}.")
  else
    puts("Don't forget to delete the table when you're done!")
  end
  print "\nThanks for watching!\n".green
rescue Aws::Errors::ServiceError
  puts("Something went wrong with the demo.")
rescue Errno::ENOENT
  true
end
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    " Create an Amazon Dynamo DB table.

    TRY.
        DATA(lo_session) = /aws1/cl_rt_session_aws=>create( cv_pfl ).
        DATA(lo_dyn) = /aws1/cl_dyn_factory=>create( lo_session ).
        DATA(lt_keyschema) = VALUE /aws1/cl_dynkeyschemaelement=>tt_keyschema(
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'year'
                                              iv_keytype = 'HASH' ) )
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'title'
                                              iv_keytype = 'RANGE' ) ) ).
        DATA(lt_attributedefinitions) = VALUE /aws1/
cl_dynattributedefn=>tt_attributedefinitions(
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'year'
                                           iv_attributetype = 'N' ) )
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'title'
                                           iv_attributetype = 'S' ) ) ).

        " Adjust read/write capacities as desired.
        DATA(lo_dynprovthroughput)  = NEW /aws1/cl_dynprovthroughput(
          iv_readcapacityunits = 5
          iv_writecapacityunits = 5 ).
        DATA(oo_result) = lo_dyn->createtable(
          it_keyschema = lt_keyschema
          iv_tablename = iv_table_name
          it_attributedefinitions = lt_attributedefinitions
          io_provisionedthroughput = lo_dynprovthroughput ).
        " Table creation can take some time. Wait till table exists before
 returning.
        lo_dyn->get_waiter( )->tableexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table' && iv_table_name && 'created.' TYPE 'I'.
```

```
      " It throws exception if the table already exists.
      CATCH /aws1/cx_dynresourceinuseex INTO DATA(lo_resourceinuseex).
        DATA(lv_error) = |"{ lo_resourceinuseex->av_err_code }" -
 { lo_resourceinuseex->av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.

    " Describe table
    TRY.
        DATA(lo_table) = lo_dyn->describetable( iv_tablename = iv_table_name ).
        DATA(lv_tablename) = lo_table->get_table( )->ask_tablename( ).
        MESSAGE 'The table name is ' && lv_tablename TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table does not exist' TYPE 'E'.
    ENDTRY.

    " Put items into the table.
    TRY.
        DATA(lo_resp_putitem) = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Jaws' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1975' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '7.5' }| ) ) )
          ) ).
        lo_resp_putitem = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s = 'Star
 Wars' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1978' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
```

```
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '8.1' }| ) ) )
          ) ).
        lo_resp_putitem = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Speed' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1994' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '7.9' }| ) ) )
          ) ).
        " TYPE REF TO ZCL_AWS1_dyn_PUT_ITEM_OUTPUT
        MESSAGE '3 rows inserted into DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
 TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.

    " Get item from table.
    TRY.
        DATA(lo_resp_getitem) = lo_dyn->getitem(
          iv_tablename                = iv_table_name
          it_key                      = VALUE /aws1/cl_dynattributevalue=>tt_key(
           ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
             key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Jaws' ) ) )
           ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
             key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n =
 '1975' ) ) )
          ) ).
        DATA(lt_attr) = lo_resp_getitem->get_item( ).
        DATA(lo_title) = lt_attr[ key = 'title' ]-value.
        DATA(lo_year) = lt_attr[ key = 'year' ]-value.
        DATA(lo_rating) = lt_attr[ key = 'year' ]-value.
```

```
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Query item from table.
    TRY.
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
              ( NEW /aws1/cl_dynattributevalue( iv_n = '1975' ) ) ).
        DATA(lt_keyconditions) = VALUE /aws1/cl_dyncondition=>tt_keyconditions(
          ( VALUE /aws1/cl_dyncondition=>ts_keyconditions_maprow(
          key = 'year'
          value = NEW /aws1/cl_dyncondition(
            it_attributevaluelist = lt_attributelist
            iv_comparisonoperator = |EQ|
          ) ) ) ).
        DATA(lo_query_result) = lo_dyn->query(
          iv_tablename = iv_table_name
          it_keyconditions = lt_keyconditions ).
        DATA(lt_items) = lo_query_result->get_items( ).
        READ TABLE lo_query_result->get_items( ) INTO DATA(lt_item) INDEX 1.
        lo_title = lt_item[ key = 'title' ]-value.
        lo_year = lt_item[ key = 'year' ]-value.
        lo_rating = lt_item[ key = 'rating' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Scan items from table.
    TRY.
        DATA(lo_scan_result) = lo_dyn->scan( iv_tablename = iv_table_name ).
        lt_items = lo_scan_result->get_items( ).
        " Read the first item and display the attributes.
        READ TABLE lo_query_result->get_items( ) INTO lt_item INDEX 1.
        lo_title = lt_item[ key = 'title' ]-value.
        lo_year = lt_item[ key = 'year' ]-value.
        lo_rating = lt_item[ key = 'rating' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
```

```
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Update items from table.
    TRY.
        DATA(lt_attributeupdates) = VALUE /aws1/
cl_dynattrvalueupdate=>tt_attributeupdates(
          ( VALUE /aws1/cl_dynattrvalueupdate=>ts_attributeupdates_maprow(
          key = 'rating' value = NEW /aws1/cl_dynattrvalueupdate(
            io_value  = NEW /aws1/cl_dynattributevalue( iv_n = '7.6' )
            iv_action = |PUT| ) ) ) ).
        DATA(lt_key) = VALUE /aws1/cl_dynattributevalue=>tt_key(
          ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
            key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n =
 '1975' ) ) )
          ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
            key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 '1980' ) ) ) ).
        DATA(lo_resp) = lo_dyn->updateitem(
          iv_tablename        = iv_table_name
          it_key              = lt_key
          it_attributeupdates = lt_attributeupdates ).
        MESSAGE '1 item updated in DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
 TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.

    " Delete table.
    TRY.
        lo_dyn->deletetable( iv_tablename = iv_table_name ).
        lo_dyn->get_waiter( )->tablenotexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table deleted.' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
```

```
      CATCH /aws1/cx_dynresourceinuseex.
        MESSAGE 'The table cannot be deleted as it is in use' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma classe Swift que gerencia chamadas do DynamoDB para o SDK para Swift.

```
import Foundation
import AWSDynamoDB

/// An enumeration of error codes representing issues that can arise when using
/// the `MovieTable` class.
enum MoviesError: Error {
    /// The specified table wasn't found or couldn't be created.
    case TableNotFound
    /// The specified item wasn't found or couldn't be created.
    case ItemNotFound
    /// The Amazon DynamoDB client is not properly initialized.
    case UninitializedClient
    /// The table status reported by Amazon DynamoDB is not recognized.
    case StatusUnknown
    /// One or more specified attribute values are invalid or missing.
    case InvalidAttributes
}


/// A class representing an Amazon DynamoDB table containing movie
/// information.
public class MovieTable {
    var ddbClient: DynamoDBClient? = nil
    let tableName: String

    /// Create an object representing a movie table in an Amazon DynamoDB
    /// database.
    ///
    /// - Parameters:
    ///   - region: The Amazon Region to create the database in.
    ///   - tableName: The name to assign to the table. If not specified, a
    ///     random table name is generated automatically.
    ///
    /// > Note: The table is not necessarily available when this function
    /// returns. Use `tableExists()` to check for its availability, or
    /// `awaitTableActive()` to wait until the table's status is reported as
    /// ready to use by Amazon DynamoDB.
    ///
    init(region: String = "us-east-2", tableName: String) async throws {
        ddbClient = try DynamoDBClient(region: region)
        self.tableName = tableName

        try await self.createTable()
```

```
    }

    ///
    /// Create a movie table in the Amazon DynamoDB data store.
    ///
    private func createTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = CreateTableInput(
            attributeDefinitions: [
                DynamoDBClientTypes.AttributeDefinition(attributeName: "year",
attributeType: .n),
                DynamoDBClientTypes.AttributeDefinition(attributeName: "title",
attributeType: .s),
            ],
            keySchema: [
                DynamoDBClientTypes.KeySchemaElement(attributeName: "year",
keyType: .hash),
                DynamoDBClientTypes.KeySchemaElement(attributeName: "title",
keyType: .range)
            ],
            provisionedThroughput: DynamoDBClientTypes.ProvisionedThroughput(
                readCapacityUnits: 10,
                writeCapacityUnits: 10
            ),
            tableName: self.tableName
        )
        let output = try await client.createTable(input: input)
        if output.tableDescription == nil {
            throw MoviesError.TableNotFound
        }
    }

    /// Check to see if the table exists online yet.
    ///
    /// - Returns: `true` if the table exists, or `false` if not.
    ///
    func tableExists() async throws -> Bool {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }
```

```
        let input = DescribeTableInput(
            tableName: tableName
        )
        let output = try await client.describeTable(input: input)
        guard let description = output.table else {
            throw MoviesError.TableNotFound
        }

        return (description.tableName == self.tableName)
    }

    ///
    /// Waits for the table to exist and for its status to be active.
    ///
    func awaitTableActive() async throws {
        while (try await tableExists() == false) {
            Thread.sleep(forTimeInterval: 0.25)
        }

        while (try await getTableStatus() != .active) {
            Thread.sleep(forTimeInterval: 0.25)
        }
    }

    ///
    /// Deletes the table from Amazon DynamoDB.
    ///
    func deleteTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DeleteTableInput(
            tableName: self.tableName
        )
        _ = try await client.deleteTable(input: input)
    }

    /// Get the table's status.
    ///
    /// - Returns: The table status, as defined by the
    ///   `DynamoDBClientTypes.TableStatus` enum.
    ///
    func getTableStatus() async throws -> DynamoDBClientTypes.TableStatus {
```

```
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DescribeTableInput(
            tableName: self.tableName
        )
        let output = try await client.describeTable(input: input)
        guard let description = output.table else {
            throw MoviesError.TableNotFound
        }
        guard let status = description.tableStatus else {
            throw MoviesError.StatusUnknown
        }
        return status
    }

    /// Populate the movie database from the specified JSON file.
    ///
    /// - Parameter jsonPath: Path to a JSON file containing movie data.
    ///
    func populate(jsonPath: String) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Create a Swift `URL` and use it to load the file into a `Data`
        // object. Then decode the JSON into an array of `Movie` objects.

        let fileUrl = URL(fileURLWithPath: jsonPath)
        let jsonData = try Data(contentsOf: fileUrl)

        var movieList = try JSONDecoder().decode([Movie].self, from: jsonData)

        // Truncate the list to the first 200 entries or so for this example.

        if movieList.count > 200 {
            movieList = Array(movieList[...199])
        }

        // Before sending records to the database, break the movie list into
        // 25-entry chunks, which is the maximum size of a batch item request.

        let count = movieList.count
```

```
        let chunks = stride(from: 0, to: count, by: 25).map {
            Array(movieList[$0 ..< Swift.min($0 + 25, count)])
        }

        // For each chunk, create a list of write request records and populate
        // them with `PutRequest` requests, each specifying one movie from the
        // chunk. Once the chunk's items are all in the `PutRequest` list,
        // send them to Amazon DynamoDB using the
        // `DynamoDBClient.batchWriteItem()` function.

        for chunk in chunks {
            var requestList: [DynamoDBClientTypes.WriteRequest] = []

            for movie in chunk {
                let item = try await movie.getAsItem()
                let request = DynamoDBClientTypes.WriteRequest(
                    putRequest: .init(
                        item: item
                    )
                )
                requestList.append(request)
            }

            let input = BatchWriteItemInput(requestItems: [tableName:
requestList])
            _ = try await client.batchWriteItem(input: input)
        }
    }

    /// Add a movie specified as a `Movie` structure to the Amazon DynamoDB
    /// table.
    ///
    /// - Parameter movie: The `Movie` to add to the table.
    ///
    func add(movie: Movie) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Get a DynamoDB item containing the movie data.
        let item = try await movie.getAsItem()

        // Send the `PutItem` request to Amazon DynamoDB.
```

```
        let input = PutItemInput(
            item: item,
            tableName: self.tableName
        )
        _ = try await client.putItem(input: input)
    }

    /// Given a movie's details, add a movie to the Amazon DynamoDB table.
    ///
    /// - Parameters:
    ///   - title: The movie's title as a `String`.
    ///   - year: The release year of the movie (`Int`).
    ///   - rating: The movie's rating if available (`Double`; default is
    ///     `nil`).
    ///   - plot: A summary of the movie's plot (`String`; default is `nil`,
    ///     indicating no plot summary is available).
    ///
    func add(title: String, year: Int, rating: Double? = nil,
             plot: String? = nil) async throws {
        let movie = Movie(title: title, year: year, rating: rating, plot: plot)
        try await self.add(movie: movie)
    }

    /// Return a `Movie` record describing the specified movie from the Amazon
    /// DynamoDB table.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The movie's release year (`Int`).
    ///
    /// - Throws: `MoviesError.ItemNotFound` if the movie isn't in the table.
    ///
    /// - Returns: A `Movie` record with the movie's details.
    func get(title: String, year: Int) async throws -> Movie {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = GetItemInput(
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            tableName: self.tableName
```

```
        )
        let output = try await client.getItem(input: input)
        guard let item = output.item else {
            throw MoviesError.ItemNotFound
        }

        let movie = try Movie(withItem: item)
        return movie
    }

    /// Get all the movies released in the specified year.
    ///
    /// - Parameter year: The release year of the movies to return.
    ///
    /// - Returns: An array of `Movie` objects describing each matching movie.
    ///
    func getMovies(fromYear year: Int) async throws -> [Movie] {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = QueryInput(
            expressionAttributeNames: [
                "#y": "year"
            ],
            expressionAttributeValues: [
                ":y": .n(String(year))
            ],
            keyConditionExpression: "#y = :y",
            tableName: self.tableName
        )
        let output = try await client.query(input: input)

        guard let items = output.items else {
            throw MoviesError.ItemNotFound
        }

        // Convert the found movies into `Movie` objects and return an array
        // of them.

        var movieList: [Movie] = []
        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
```

```
        }
        return movieList
    }

    /// Return an array of `Movie` objects released in the specified range of
    /// years.
    ///
    /// - Parameters:
    ///   - firstYear: The first year of movies to return.
    ///   - lastYear: The last year of movies to return.
    ///   - startKey: A starting point to resume processing; always use `nil`.
    ///
    /// - Returns: An array of `Movie` objects describing the matching movies.
    ///
    /// > Note: The `startKey` parameter is used by this function when
    ///   recursively calling itself, and should always be `nil` when calling
    ///   directly.
    ///
    func getMovies(firstYear: Int, lastYear: Int,
                   startKey: [Swift.String:DynamoDBClientTypes.AttributeValue]? =
nil)
                   async throws -> [Movie] {
        var movieList: [Movie] = []

        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = ScanInput(
            consistentRead: true,
            exclusiveStartKey: startKey,
            expressionAttributeNames: [
                "#y": "year"            // `year` is a reserved word, so use `#y`
instead.
            ],
            expressionAttributeValues: [
                ":y1": .n(String(firstYear)),
                ":y2": .n(String(lastYear))
            ],
            filterExpression: "#y BETWEEN :y1 AND :y2",
            tableName: self.tableName
        )

        let output = try await client.scan(input: input)
```

```
        guard let items = output.items else {
            return movieList
        }

        // Build an array of `Movie` objects for the returned items.

        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }

        // Call this function recursively to continue collecting matching
        // movies, if necessary.

        if output.lastEvaluatedKey != nil {
            let movies = try await self.getMovies(firstYear: firstYear, lastYear:
lastYear,
                        startKey: output.lastEvaluatedKey)
            movieList += movies
        }
        return movieList
    }

    /// Update the specified movie with new `rating` and `plot` information.
    ///
    /// - Parameters:
    ///   - title: The title of the movie to update.
    ///   - year: The release year of the movie to update.
    ///   - rating: The new rating for the movie.
    ///   - plot: The new plot summary string for the movie.
    ///
    /// - Returns: An array of mappings of attribute names to their new
    ///   listing each item actually changed. Items that didn't need to change
    ///   aren't included in this list. `nil` if no changes were made.
    ///
    func update(title: String, year: Int, rating: Double? = nil, plot: String? =
nil) async throws
                -> [Swift.String:DynamoDBClientTypes.AttributeValue]? {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Build the update expression and the list of expression attribute
```

```
        // values. Include only the information that's changed.

        var expressionParts: [String] = []
        var attrValues: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]

        if rating != nil {
            expressionParts.append("info.rating=:r")
            attrValues[":r"] = .n(String(rating!))
        }
        if plot != nil {
            expressionParts.append("info.plot=:p")
            attrValues[":p"] = .s(plot!)
        }
        let expression: String = "set \(expressionParts.joined(separator: ", "))"

        let input = UpdateItemInput(
            // Create substitution tokens for the attribute values, to ensure
            // no conflicts in expression syntax.
            expressionAttributeValues: attrValues,
            // The key identifying the movie to update consists of the release
            // year and title.
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            returnValues: .updatedNew,
            tableName: self.tableName,
            updateExpression: expression
        )
        let output = try await client.updateItem(input: input)

        guard let attributes: [Swift.String:DynamoDBClientTypes.AttributeValue] =
output.attributes else {
            throw MoviesError.InvalidAttributes
        }
        return attributes
    }

    /// Delete a movie, given its title and release year.
    ///
    /// - Parameters:
    ///   - title: The movie's title.
    ///   - year: The movie's release year.
    ///
```

```
    func delete(title: String, year: Int) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DeleteItemInput(
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            tableName: self.tableName
        )
        _ = try await client.deleteItem(input: input)
    }
}
```

As estruturas usadas pela MovieTable classe para representar filmes.

```
import Foundation
import AWSDynamoDB

/// The optional details about a movie.
public struct Details: Codable {
    /// The movie's rating, if available.
    var rating: Double?
    /// The movie's plot, if available.
    var plot: String?
}

/// A structure describing a movie. The `year` and `title` properties are
/// required and are used as the key for Amazon DynamoDB operations. The
/// `info` sub-structure's two properties, `rating` and `plot`, are optional.
public struct Movie: Codable {
    /// The year in which the movie was released.
    var year: Int
    /// The movie's title.
    var title: String
    /// A `Details` object providing the optional movie rating and plot
    /// information.
    var info: Details

    /// Create a `Movie` object representing a movie, given the movie's
```

```
    /// details.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The year in which the movie was released (`Int`).
    ///   - rating: The movie's rating (optional `Double`).
    ///   - plot: The movie's plot (optional `String`)
    init(title: String, year: Int, rating: Double? = nil, plot: String? = nil) {
        self.title = title
        self.year = year

        self.info = Details(rating: rating, plot: plot)
    }

    /// Create a `Movie` object representing a movie, given the movie's
    /// details.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The year in which the movie was released (`Int`).
    ///   - info: The optional rating and plot information for the movie in a
    ///     `Details` object.
    init(title: String, year: Int, info: Details?){
        self.title = title
        self.year = year

        if info != nil {
            self.info = info!
        } else {
            self.info = Details(rating: nil, plot: nil)
        }
    }

    ///
    /// Return a new `MovieTable` object, given an array mapping string to Amazon
    /// DynamoDB attribute values.
    ///
    /// - Parameter item: The item information provided to the form used by
    ///   DynamoDB. This is an array of strings mapped to
    ///   `DynamoDBClientTypes.AttributeValue` values.
    init(withItem item: [Swift.String:DynamoDBClientTypes.AttributeValue]) throws
  {
        // Read the attributes.
```

```
        guard let titleAttr = item["title"],
              let yearAttr = item["year"] else {
            throw MoviesError.ItemNotFound
        }
        let infoAttr = item["info"] ?? nil

        // Extract the values of the title and year attributes.

        if case .s(let titleVal) = titleAttr {
            self.title = titleVal
        } else {
            throw MoviesError.InvalidAttributes
        }

        if case .n(let yearVal) = yearAttr {
            self.year = Int(yearVal)!
        } else {
            throw MoviesError.InvalidAttributes
        }

        // Extract the rating and/or plot from the `info` attribute, if
        // they're present.

        var rating: Double? = nil
        var plot: String? = nil

        if infoAttr != nil, case .m(let infoVal) = infoAttr {
            let ratingAttr = infoVal["rating"] ?? nil
            let plotAttr = infoVal["plot"] ?? nil

            if ratingAttr != nil, case .n(let ratingVal) = ratingAttr {
                rating = Double(ratingVal) ?? nil
            }
            if plotAttr != nil, case .s(let plotVal) = plotAttr {
                plot = plotVal
            }
        }

        self.info = Details(rating: rating, plot: plot)
    }

    ///
    /// Return an array mapping attribute names to Amazon DynamoDB attribute
    /// values, representing the contents of the `Movie` record as a DynamoDB
```

```
    /// item.
    ///
    /// - Returns: The movie item as an array of type
    ///   `[Swift.String:DynamoDBClientTypes.AttributeValue]`.
    ///
    func getAsItem() async throws ->
 [Swift.String:DynamoDBClientTypes.AttributeValue]  {
        // Build the item record, starting with the year and title, which are
        // always present.

        var item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
            "year": .n(String(self.year)),
            "title": .s(self.title)
        ]

        // Add the `info` field with the rating and/or plot if they're
        // available.

        var details: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]
        if (self.info.rating != nil || self.info.plot != nil) {
            if self.info.rating != nil {
                details["rating"] = .n(String(self.info.rating!))
            }
            if self.info.plot != nil {
                details["plot"] = .s(self.info.plot!)
            }
        }
        item["info"] = .m(details)

        return item
    }
 }
```

Um programa que usa a MovieTable classe para acessar um banco de dados do DynamoDB.

```
import Foundation
import ArgumentParser
import AWSDynamoDB
import ClientRuntime

@testable import MovieList
```

```
struct ExampleCommand: ParsableCommand {
    @Argument(help: "The path of the sample movie data JSON file.")
    var jsonPath: String = "../../../../resources/sample_files/movies.json"

    @Option(help: "The AWS Region to run AWS API calls in.")
    var awsRegion = "us-east-2"

    @Option(
        help: ArgumentHelp("The level of logging for the Swift SDK to perform."),
        completion: .list([
            "critical",
            "debug",
            "error",
            "info",
            "notice",
            "trace",
            "warning"
        ])
    )
    var logLevel: String = "error"

    /// Configuration details for the command.
    static var configuration = CommandConfiguration(
        commandName: "basics",
        abstract: "A basic scenario demonstrating the usage of Amazon DynamoDB.",
        discussion: """
        An example showing how to use Amazon DynamoDB to perform a series of
        common database activities on a simple movie database.
        """
    )

    /// Called by ``main()`` to asynchronously run the AWS example.
    func runAsync() async throws {
        print("Welcome to the AWS SDK for Swift basic scenario for Amazon
 DynamoDB!")
        SDKLoggingSystem.initialize(logLevel: .error)

        //===========================================================================
        // 1. Create the table. The Amazon DynamoDB table is represented by
        //    the `MovieTable` class.
        //===========================================================================

        let tableName = "ddb-movies-sample-\(Int.random(in: 1...Int.max))"
```

```
        //let tableName = String.uniqueName(withPrefix: "ddb-movies-sample",
maxDigits: 8)

        print("Creating table \"\(tableName)\"...")

        let movieDatabase = try await MovieTable(region: awsRegion,
                            tableName: tableName)

        print("\nWaiting for table to be ready to use...")
        try await movieDatabase.awaitTableActive()

        //=====================================================================
        // 2. Add a movie to the table.
        //=====================================================================

        print("\nAdding a movie...")
        try await movieDatabase.add(title: "Avatar: The Way of Water", year:
2022)
        try await movieDatabase.add(title: "Not a Real Movie", year: 2023)

        //=====================================================================
        // 3. Update the plot and rating of the movie using an update
        //    expression.
        //=====================================================================

        print("\nAdding details to the added movie...")
        _ = try await movieDatabase.update(title: "Avatar: The Way of Water",
year: 2022,
                    rating: 9.2, plot: "It's a sequel.")

        //=====================================================================
        // 4. Populate the table from the JSON file.
        //=====================================================================

        print("\nPopulating the movie database from JSON...")
        try await movieDatabase.populate(jsonPath: jsonPath)

        //=====================================================================
        // 5. Get a specific movie by key. In this example, the key is a
        //    combination of `title` and `year`.
        //=====================================================================

        print("\nLooking for a movie in the table...")
```

```
        let gotMovie = try await movieDatabase.get(title: "This Is the End",
year: 2013)

        print("Found the movie \"\(gotMovie.title)\", released in
\(gotMovie.year).")
        print("Rating: \(gotMovie.info.rating ?? 0.0).")
        print("Plot summary: \(gotMovie.info.plot ?? "None.")")

        //=====================================================================
        // 6. Delete a movie.
        //=====================================================================

        print("\nDeleting the added movie...")
        try await movieDatabase.delete(title: "Avatar: The Way of Water", year:
2022)

        //=====================================================================
        // 7. Use a query with a key condition expression to return all movies
        //    released in a given year.
        //=====================================================================

        print("\nGetting movies released in 1994...")
        let movieList = try await movieDatabase.getMovies(fromYear: 1994)
        for movie in movieList {
            print("    \(movie.title)")
        }

        //=====================================================================
        // 8. Use `scan()` to return movies released in a range of years.
        //=====================================================================

        print("\nGetting movies released between 1993 and 1997...")
        let scannedMovies = try await movieDatabase.getMovies(firstYear: 1993,
lastYear: 1997)
        for movie in scannedMovies {
            print("    \(movie.title) (\(movie.year))")
        }

        //=====================================================================
        // 9. Delete the table.
        //=====================================================================

        print("\nDeleting the table...")
        try await movieDatabase.deleteTable()
```

```
    }
}

@main
struct Main {
    static func main() async {
        let args = Array(CommandLine.arguments.dropFirst())

        do {
            let command = try ExampleCommand.parse(args)
            try await command.runAsync()
        } catch {
            ExampleCommand.exit(withError: error)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela do DynamoDB usando lotes de instruções PartiQL e um AWS SDK

Os exemplos de código a seguir mostram como:

- Obter um lote de itens executando várias instruções SELECT.

- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Before you run this example, download 'movies.json' from
// https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
GettingStarted.Js.02.html,
// and put it in the same folder as the example.

// Separator for the console display.
var SepBar = new string('-', 80);
const string tableName = "movie_table";
const string movieFileName = "moviedata.json";

DisplayInstructions();

// Create the table and wait for it to be active.
Console.WriteLine($"Creating the movie table: {tableName}");

var success = await DynamoDBMethods.CreateMovieTableAsync(tableName);
if (success)
{
    Console.WriteLine($"Successfully created table: {tableName}.");
}

WaitForEnter();

// Add movie information to the table from moviedata.json. See the
// instructions at the top of this file to download the JSON file.
Console.WriteLine($"Inserting movies into the new table. Please wait...");
```

```
success = await PartiQLBatchMethods.InsertMovies(tableName, movieFileName);
if (success)
{
    Console.WriteLine("Movies successfully added to the table.");
}
else
{
    Console.WriteLine("Movies could not be added to the table.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var title1 = "Star Wars";
var year1 = 1977;
var title2 = "Wizard of Oz";
var year2 = 1939;

Console.WriteLine($"Updating two movies with producer information: {title1} and
 {title2}.");
success = await PartiQLBatchMethods.GetBatch(tableName, title1, title2, year1,
 year2);
if (success)
{
    Console.WriteLine($"Successfully retrieved {title1} and {title2}.");
}
else
{
    Console.WriteLine("Select statement failed.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var producer1 = "LucasFilm";
var producer2 = "MGM";

Console.WriteLine($"Updating two movies with producer information: {title1} and
 {title2}.");
success = await PartiQLBatchMethods.UpdateBatch(tableName, producer1, title1,
 year1, producer2, title2, year2);
if (success)
{
    Console.WriteLine($"Successfully updated {title1} and {title2}.");
```

```
}
else
{
    Console.WriteLine("Update failed.");
}

WaitForEnter();

// Delete multiple movies by using the BatchExecute statement.
Console.WriteLine($"Now we will delete {title1} and {title2} from the table.");
success = await PartiQLBatchMethods.DeleteBatch(tableName, title1, year1, title2,
 year2);

if (success)
{
    Console.WriteLine($"Deleted {title1} and {title2}");
}
else
{
    Console.WriteLine($"could not delete {title1} or {title2}");
}

WaitForEnter();

// DNow that the PartiQL Batch scenario is complete, delete the movie table.
success = await DynamoDBMethods.DeleteTableAsync(tableName);

if (success)
{
    Console.WriteLine($"Successfully deleted {tableName}");
}
else
{
    Console.WriteLine($"Could not delete {tableName}");
}

/// <summary>
/// Displays the description of the application on the console.
/// </summary>
void DisplayInstructions()
{
    Console.Clear();
    Console.WriteLine();
    Console.Write(new string(' ', 24));
```

```
    Console.WriteLine("DynamoDB PartiQL Basics Example");
    Console.WriteLine(SepBar);
    Console.WriteLine("This demo application shows the basics of using Amazon
 DynamoDB with the AWS SDK for");
    Console.WriteLine(".NET version 3.7 and .NET 6.");
    Console.WriteLine(SepBar);
    Console.WriteLine("Creates a table by using the CreateTable method.");
    Console.WriteLine("Gets multiple movies by using a PartiQL SELECT
 statement.");
    Console.WriteLine("Updates multiple movies by using the ExecuteBatch
 method.");
    Console.WriteLine("Deletes multiple movies by using a PartiQL DELETE
 statement.");
    Console.WriteLine("Cleans up the resources created for the demo by deleting
 the table.");
    Console.WriteLine(SepBar);

    WaitForEnter();
}

/// <summary>
/// Simple method to wait for the <Enter> key to be pressed.
/// </summary>
void WaitForEnter()
{
    Console.WriteLine("\nPress <Enter> to continue.");
    Console.Write(SepBar);
    _ = Console.ReadLine();
}


        /// <summary>
        /// Gets movies from the movie table by
        /// using an Amazon DynamoDB PartiQL SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year1">The year of the first movie.</param>
        /// <param name="year2">The year of the second movie.</param>
        /// <returns>True if successful.</returns>
        public static async Task<bool> GetBatch(
            string tableName,
            string title1,
```

```
            string title2,
            int year1,
            int year2)
        {
            var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year
= ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            if (response.Responses.Count > 0)
            {
                response.Responses.ForEach(r =>
                {
                    Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
                });
                return true;
            }
            else
```

```
            {
                Console.WriteLine($"Couldn't find either {title1} or {title2}.");
                return false;
            }

        }

        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table into which the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE
{{'title': ?, 'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset +=
25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
```

```
                                Parameters = new List<AttributeValue>
                                {
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
                            });
                        }

                        var response = await
Client.BatchExecuteStatementAsync(new BatchExecuteStatementRequest
                        {
                            Statements = statements,
                        });

                        // Wait between batches for movies to be successfully
added.
                        System.Threading.Thread.Sleep(3000);

                        success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                        // Clear the list of statements for the next batch.
                        statements.Clear();
                    }
                }
                catch (AmazonDynamoDBException ex)
                {
                    Console.WriteLine(ex.Message);
                }
            }

            return success;
        }

        /// <summary>
        /// Loads the contents of a JSON file into a list of movies to be
        /// added to the DynamoDB table.
        /// </summary>
        /// <param name="movieFileName">The full path to the JSON file.</param>
        /// <returns>A generic list of movie objects.</returns>
        public static List<Movie> ImportMovies(string movieFileName)
        {
            if (!File.Exists(movieFileName))
```

```
            {
                return null!;
            }

            using var sr = new StreamReader(movieFileName);
            string json = sr.ReadToEnd();
            var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

            if (allMovies is not null)
            {
                // Return the first 250 entries.
                return allMovies.GetRange(0, 250);
            }
            else
            {
                return null!;
            }
        }

        /// <summary>
        /// Updates information for multiple movies.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// movies to be updated.</param>
        /// <param name="producer1">The producer name for the first movie
        /// to update.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year that the first movie was released.</
param>
        /// <param name="producer2">The producer name for the second
        /// movie to update.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year that the second movie was released.</
param>
        /// <returns>A Boolean value that indicates the success of the update.</
returns>
        public static async Task<bool> UpdateBatch(
            string tableName,
            string producer1,
            string title1,
            int year1,
            string producer2,
            string title2,
            int year2)
```

```
        {

            string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer1 },
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer2 },
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }

        /// <summary>
        /// Deletes multiple movies using a PartiQL BatchExecuteAsync
        /// statement.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// moves that will be deleted.</param>
```

```
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year the first movie was released.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year the second movie was released.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeleteBatch(
            string tableName,
            string title1,
            int year1,
            string title2,
            int year2)
        {

            string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND
 year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
 BatchExecuteStatementRequest
            {
                Statements = statements,
            });
```

```
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlBatchExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using PartiQL batch statements.
/*!
  \sa partiqlBatchExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::partiqlBatchExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
```

```
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);

        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/
n) "));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

 attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
```

```
            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute
= Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "Retrieving the movie data with a batch \"SELECT\" statement."
              << std::endl;

    // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
```

```
                << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

```
   // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)

   for (size_t i = 0; i < titles.size(); ++i) {
       ratings[i] = askQuestionForFloatRange(
               Aws::String("\nLet's update your the movie, \"") + titles[i] +
               ".\nYou rated it  " + std::to_string(ratings[i])
               + ", what new rating would you give it? ", 1, 10);
   }

   std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;

   {
       Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
               titles.size());

       std::stringstream sqlStream;
       sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                 << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                 << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


       std::string sql(sqlStream.str());

       for (size_t i = 0; i < statements.size(); ++i) {
           statements[i].SetStatement(sql);

           Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
           attributes.push_back(
                   Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
           attributes.push_back(
                   Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
           statements[i].SetParameters(attributes);
       }

       Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

       request.SetStatements(statements);
       Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
               request);
```

```
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Retrieving the updated movie data with a batch \"SELECT\"
statement."
              << std::endl;

    // 5. Get the updated data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();
```

```
            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movies information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Deleting the movie data with a batch \"DELETE\" statement."
              << std::endl;

    // 6. Delete multiple movies using "Delete" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;
```

```
        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
 dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
```

```
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." <<
std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
```

```
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
```

```
                                        const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute lotes de consultas do PartiQL.

```
// RunPartiQLBatchScenario shows you how to use the AWS SDK for Go
// to run batches of PartiQL statements to query a table that stores data about
 movies.
//
//   - Use batches of PartiQL statements to add, get, update, and delete data for
//     individual movies.
//
// This example creates an Amazon DynamoDB service client from the specified
 sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLBatchScenario(sdkConfig aws.Config, tableName string) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon DynamoDB PartiQL batch demo.")
 log.Println(strings.Repeat("-", 88))

 tableBasics := actions.TableBasics{
  DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
  TableName:      tableName,
 }
 runner := actions.PartiQLRunner{
  DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
  TableName:      tableName,
```

```
}

exists, err := tableBasics.TableExists()
if err != nil {
 panic(err)
}
if !exists {
 log.Printf("Creating table %v...\n", tableName)
 _, err = tableBasics.CreateMovieTable()
 if err != nil {
  panic(err)
 } else {
  log.Printf("Created table %v.\n", tableName)
 }
} else {
 log.Printf("Table %v already exists.\n", tableName)
}
log.Println(strings.Repeat("-", 88))

currentYear, _, _ := time.Now().Date()
customMovies := []actions.Movie{{
 Title: "House PartiQL",
 Year:  currentYear - 5,
 Info: map[string]interface{}{
  "plot":   "Wacky high jinks result from querying a mysterious database.",
  "rating": 8.5}}, {
 Title: "House PartiQL 2",
 Year:  currentYear - 3,
 Info: map[string]interface{}{
  "plot":   "Moderate high jinks result from querying another mysterious
database.",
  "rating": 6.5}}, {
 Title: "House PartiQL 3",
 Year:  currentYear - 1,
 Info: map[string]interface{}{
  "plot":   "Tepid high jinks result from querying yet another mysterious
database.",
  "rating": 2.5},
},
}

log.Printf("Inserting a batch of movies into table '%v'.\n", tableName)
err = runner.AddMovieBatch(customMovies)
if err == nil {
```

```
 log.Printf("Added %v movies to the table.\n", len(customMovies))
}
log.Println(strings.Repeat("-", 88))

log.Println("Getting data for a batch of movies.")
movies, err := runner.GetMovieBatch(customMovies)
if err == nil {
 for _, movie := range movies {
  log.Println(movie)
 }
}
log.Println(strings.Repeat("-", 88))

newRatings := []float64{7.7, 4.4, 1.1}
log.Println("Updating a batch of movies with new ratings.")
err = runner.UpdateMovieBatch(customMovies, newRatings)
if err == nil {
 log.Printf("Updated %v movies with new ratings.\n", len(customMovies))
}
log.Println(strings.Repeat("-", 88))

log.Println("Getting projected data from the table to verify our update.")
log.Println("Using a page size of 2 to demonstrate paging.")
projections, err := runner.GetAllMovies(2)
if err == nil {
 log.Println("All movies:")
 for _, projection := range projections {
  log.Println(projection)
 }
}
log.Println(strings.Repeat("-", 88))

log.Println("Deleting a batch of movies.")
err = runner.DeleteMovieBatch(customMovies)
if err == nil {
 log.Printf("Deleted %v movies.\n", len(customMovies))
}

err = tableBasics.DeleteTable()
if err == nil {
 log.Printf("Deleted table %v.\n", tableBasics.TableName)
}

log.Println(strings.Repeat("-", 88))
```

```
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

Crie uma estrutura e métodos que executem instruções partiQL.

```
// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
// PartiQL examples. It contains a DynamoDB service client that is used to act on
 the
// specified table.
type PartiQLRunner struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies
 to the
// DynamoDB table.
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year, movie.Info})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(fmt.Sprintf(
    "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n",
 err)
 }
 return err
}
```

```
// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies
 from
// the DynamoDB table by title and year.
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }

 output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 var outMovies []Movie
 if err != nil {
  log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
 } else {
  for _, response := range output.Responses {
   var movie Movie
   err = attributevalue.UnmarshalMap(response.Item, &movie)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
    outMovies = append(outMovies, movie)
   }
  }
 }
 return outMovies, err
}
```

```
// GetAllMovies runs a PartiQL SELECT statement to get all movies from the
 DynamoDB table.
// pageSize is not typically required and is used to show how to paginate the
 results.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies(pageSize int32)
 ([]map[string]interface{}, error) {
 var output []map[string]interface{}
 var response *dynamodb.ExecuteStatementOutput
 var err error
 var nextToken *string
 for moreData := true; moreData; {
  response, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
   Statement: aws.String(
    fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
   Limit:     aws.Int32(pageSize),
   NextToken: nextToken,
  })
  if err != nil {
   log.Printf("Couldn't get movies. Here's why: %v\n", err)
   moreData = false
  } else {
   var pageOutput []map[string]interface{}
   err = attributevalue.UnmarshalListOfMaps(response.Items, &pageOutput)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
    log.Printf("Got a page of length %v.\n", len(response.Items))
    output = append(output, pageOutput...)
   }
   nextToken = response.NextToken
   moreData = nextToken != nil
  }
 }
 return output, err
}



// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the
 rating of
// multiple movies that already exist in the DynamoDB table.
```

```
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64)
 error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{ratings[index],
 movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
 }
 return err
}



// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
 movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
 runner.TableName)),
```

```
    Parameters: params,
   }
  }

  _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
  &dynamodb.BatchExecuteStatementInput{
   Statements: statementRequests,
  })
  if err != nil {
   log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
  }
  return err
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ScenarioPartiQLBatch {
        public static void main(String[] args) throws IOException {
                String tableName = "MoviesPartiQBatch";
                Region region = Region.US_EAST_1;
                DynamoDbClient ddb = DynamoDbClient.builder()
                                .region(region)
                                .build();

                System.out.println("******* Creating an Amazon DynamoDB table
 named " + tableName
                                + " with a key named year and a sort key named
 title.");
```

```
                createTable(ddb, tableName);

                System.out.println("******* Adding multiple records into the " +
tableName
                                + " table using a batch command.");
                putRecordBatch(ddb);

                System.out.println("******* Updating multiple records using a
batch command.");
                updateTableItemBatch(ddb);

                System.out.println("******* Deleting multiple records using a
batch command.");
                deleteItemBatch(ddb);

                System.out.println("******* Deleting the Amazon DynamoDB
table.");
                deleteDynamoDBTable(ddb, tableName);
                ddb.close();
        }

        public static void createTable(DynamoDbClient ddb, String tableName) {
                DynamoDbWaiter dbWaiter = ddb.waiter();
                ArrayList<AttributeDefinition> attributeDefinitions = new
ArrayList<>();

                // Define attributes.
                attributeDefinitions.add(AttributeDefinition.builder()
                                .attributeName("year")
                                .attributeType("N")
                                .build());

                attributeDefinitions.add(AttributeDefinition.builder()
                                .attributeName("title")
                                .attributeType("S")
                                .build());

                ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
                KeySchemaElement key = KeySchemaElement.builder()
                                .attributeName("year")
                                .keyType(KeyType.HASH)
                                .build();

                KeySchemaElement key2 = KeySchemaElement.builder()
```

```
                                .attributeName("title")
                                .keyType(KeyType.RANGE) // Sort
                                .build();

                // Add KeySchemaElement objects to the list.
                tableKey.add(key);
                tableKey.add(key2);

                CreateTableRequest request = CreateTableRequest.builder()
                                .keySchema(tableKey)

.provisionedThroughput(ProvisionedThroughput.builder()
                                                .readCapacityUnits(new Long(10))
                                                .writeCapacityUnits(new Long(10))
                                                .build())
                                .attributeDefinitions(attributeDefinitions)
                                .tableName(tableName)
                                .build();

                try {
                        CreateTableResponse response = ddb.createTable(request);
                        DescribeTableRequest tableRequest =
DescribeTableRequest.builder()
                                        .tableName(tableName)
                                        .build();

                        // Wait until the Amazon DynamoDB table is created.
                        WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter
                                        .waitUntilTableExists(tableRequest);

waiterResponse.matched().response().ifPresent(System.out::println);
                        String newTable =
response.tableDescription().tableName();
                        System.out.println("The " + newTable + " was successfully
created.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void putRecordBatch(DynamoDbClient ddb) {
```

```
                String sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE
{'year':?, 'title' : ?, 'info' : ?}";
                try {
                        // Create three movies to add to the Amazon DynamoDB
table.
                        // Set data for Movie 1.
                        List<AttributeValue> parameters = new ArrayList<>();

                        AttributeValue att1 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue att2 = AttributeValue.builder()
                                        .s("My Movie 1")
                                        .build();

                        AttributeValue att3 = AttributeValue.builder()
                                        .s("No Information")
                                        .build();

                        parameters.add(att1);
                        parameters.add(att2);
                        parameters.add(att3);

                        BatchStatementRequest statementRequestMovie1 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parameters)
                                        .build();

                        // Set data for Movie 2.
                        List<AttributeValue> parametersMovie2 = new
ArrayList<>();
                        AttributeValue attMovie2 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue attMovie2A = AttributeValue.builder()
                                        .s("My Movie 2")
                                        .build();

                        AttributeValue attMovie2B = AttributeValue.builder()
                                        .s("No Information")
                                        .build();
```

```
                        parametersMovie2.add(attMovie2);
                        parametersMovie2.add(attMovie2A);
                        parametersMovie2.add(attMovie2B);

                        BatchStatementRequest statementRequestMovie2 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parametersMovie2)
                                        .build();

                        // Set data for Movie 3.
                        List<AttributeValue> parametersMovie3 = new
ArrayList<>();
                        AttributeValue attMovie3 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue attMovie3A = AttributeValue.builder()
                                        .s("My Movie 3")
                                        .build();

                        AttributeValue attMovie3B = AttributeValue.builder()
                                        .s("No Information")
                                        .build();

                        parametersMovie3.add(attMovie3);
                        parametersMovie3.add(attMovie3A);
                        parametersMovie3.add(attMovie3B);

                        BatchStatementRequest statementRequestMovie3 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parametersMovie3)
                                        .build();

                        // Add all three movies to the list.
                        List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                        myBatchStatementList.add(statementRequestMovie1);
                        myBatchStatementList.add(statementRequestMovie2);
                        myBatchStatementList.add(statementRequestMovie3);
```

```
                        BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                        .statements(myBatchStatementList)
                                        .build();

                        BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
                        System.out.println("ExecuteStatement successful: " +
response.toString());
                        System.out.println("Added new movies using a batch
command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void updateTableItemBatch(DynamoDbClient ddb) {
                String sqlStatement = "UPDATE MoviesPartiQBatch SET info =
'directors\":[\"Merian C. Cooper\",\"Ernest B. Schoedsack' where year=? and
title=?";
                List<AttributeValue> parametersRec1 = new ArrayList<>();

                // Update three records.
                AttributeValue att1 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue att2 = AttributeValue.builder()
                                .s("My Movie 1")
                                .build();

                parametersRec1.add(att1);
                parametersRec1.add(att2);

                BatchStatementRequest statementRequestRec1 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec1)
                                .build();

                // Update record 2.
                List<AttributeValue> parametersRec2 = new ArrayList<>();
```

```
                AttributeValue attRec2 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec2a = AttributeValue.builder()
                                .s("My Movie 2")
                                .build();

                parametersRec2.add(attRec2);
                parametersRec2.add(attRec2a);
                BatchStatementRequest statementRequestRec2 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec2)
                                .build();

                // Update record 3.
                List<AttributeValue> parametersRec3 = new ArrayList<>();
                AttributeValue attRec3 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec3a = AttributeValue.builder()
                                .s("My Movie 3")
                                .build();

                parametersRec3.add(attRec3);
                parametersRec3.add(attRec3a);
                BatchStatementRequest statementRequestRec3 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec3)
                                .build();

                // Add all three movies to the list.
                List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                myBatchStatementList.add(statementRequestRec1);
                myBatchStatementList.add(statementRequestRec2);
                myBatchStatementList.add(statementRequestRec3);

                BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                .statements(myBatchStatementList)
```

```
                                .build();

                try {
                        BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
                        System.out.println("ExecuteStatement successful: " +
response.toString());
                        System.out.println("Updated three movies using a batch
command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
                System.out.println("Item was updated!");
        }

        public static void deleteItemBatch(DynamoDbClient ddb) {
                String sqlStatement = "DELETE FROM MoviesPartiQBatch WHERE year
= ? and title=?";
                List<AttributeValue> parametersRec1 = new ArrayList<>();

                // Specify three records to delete.
                AttributeValue att1 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue att2 = AttributeValue.builder()
                                .s("My Movie 1")
                                .build();

                parametersRec1.add(att1);
                parametersRec1.add(att2);

                BatchStatementRequest statementRequestRec1 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec1)
                                .build();

                // Specify record 2.
                List<AttributeValue> parametersRec2 = new ArrayList<>();
                AttributeValue attRec2 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
```

```
                                .build();

                AttributeValue attRec2a = AttributeValue.builder()
                                .s("My Movie 2")
                                .build();

                parametersRec2.add(attRec2);
                parametersRec2.add(attRec2a);
                BatchStatementRequest statementRequestRec2 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec2)
                                .build();

                // Specify record 3.
                List<AttributeValue> parametersRec3 = new ArrayList<>();
                AttributeValue attRec3 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec3a = AttributeValue.builder()
                                .s("My Movie 3")
                                .build();

                parametersRec3.add(attRec3);
                parametersRec3.add(attRec3a);

                BatchStatementRequest statementRequestRec3 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec3)
                                .build();

                // Add all three movies to the list.
                List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                myBatchStatementList.add(statementRequestRec1);
                myBatchStatementList.add(statementRequestRec2);
                myBatchStatementList.add(statementRequestRec3);

                BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                .statements(myBatchStatementList)
                                .build();
```

```
                try {
                        ddb.batchExecuteStatement(batchRequest);
                        System.out.println("Deleted three movies using a batch
 command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void deleteDynamoDBTable(DynamoDbClient ddb, String
 tableName) {
                DeleteTableRequest request = DeleteTableRequest.builder()
                                .tableName(tableName)
                                .build();

                try {
                        ddb.deleteTable(request);

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
                System.out.println(tableName + " was successfully deleted!");
        }

        private static ExecuteStatementResponse
 executeStatementRequest(DynamoDbClient ddb, String statement,
                        List<AttributeValue> parameters) {
                ExecuteStatementRequest request =
 ExecuteStatementRequest.builder()
                                .statement(statement)
                                .parameters(parameters)
                                .build();

                return ddb.executeStatement(request);
        }
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute instruções PartiQL em lote.

```
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);
const tableName = "Cities";

export const main = async () => {
  /**
   * Create a table.
   */

  log("Creating a table.");
  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
```

```
    // Set the billing mode to PAY_PER_REQUEST to
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
    AttributeDefinitions: [
      {
        AttributeName: "name",
        // 'S' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "S",
      },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [{ AttributeName: "name", KeyType: "HASH" }],
  });
  await client.send(createTableCommand);
  log(`Table created: ${tableName}.`);

  /**
   * Wait until the table is active.
   */

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Insert items.
   */

  log("Inserting cities into the table.");
  const addItemsStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.insert.html
    Statements: [
      {
```

```
        Statement: `INSERT INTO ${tableName} value {'name':?, 'population':?}`,
        Parameters: ["Alachua", 10712],
      },
      {
        Statement: `INSERT INTO ${tableName} value {'name':?, 'population':?}`,
        Parameters: ["High Springs", 6415],
      },
    ],
  });
  await docClient.send(addItemsStatementCommand);
  log(`Cities inserted.`);

  /**
   * Select items.
   */

  log("Selecting cities from the table.");
  const selectItemsStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.select.html
    Statements: [
      {
        Statement: `SELECT * FROM ${tableName} WHERE name=?`,
        Parameters: ["Alachua"],
      },
      {
        Statement: `SELECT * FROM ${tableName} WHERE name=?`,
        Parameters: ["High Springs"],
      },
    ],
  });
  const selectItemResponse = await docClient.send(selectItemsStatementCommand);
  log(
    `Got cities: ${selectItemResponse.Responses.map(
      (r) => `${r.Item.name} (${r.Item.population})`,
    ).join(", ")}`,
  );

  /**
   * Update items.
   */

  log("Modifying the populations.");
  const updateItemStatementCommand = new BatchExecuteStatementCommand({
```

```
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.update.html
    Statements: [
      {
        Statement: `UPDATE ${tableName} SET population=? WHERE name=?`,
        Parameters: [10, "Alachua"],
      },
      {
        Statement: `UPDATE ${tableName} SET population=? WHERE name=?`,
        Parameters: [5, "High Springs"],
      },
    ],
  });
  await docClient.send(updateItemStatementCommand);
  log(`Updated cities.`);

  /**
   * Delete the items.
   */

  log("Deleting the cities.");
  const deleteItemStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.delete.html
    Statements: [
      {
        Statement: `DELETE FROM ${tableName} WHERE name=?`,
        Parameters: ["Alachua"],
      },
      {
        Statement: `DELETE FROM ${tableName} WHERE name=?`,
        Parameters: ["High Springs"],
      },
    ],
  });
  await docClient.send(deleteItemStatementCommand);
  log("Cities deleted.");

  /**
   * Delete the table.
   */

  log("Deleting the table.");
  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
```

```
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main() {
    val ddb = DynamoDbClient { region = "us-east-1" }
    val tableName = "MoviesPartiQBatch"
    println("Creating an Amazon DynamoDB table named $tableName with a key named
 id and a sort key named title.")
    createTablePartiQLBatch(ddb, tableName, "year")
    putRecordBatch(ddb)
    updateTableItemBatchBatch(ddb)
    deleteItemsBatch(ddb)
    deleteTablePartiQLBatch(tableName)
}

suspend fun createTablePartiQLBatch(ddb: DynamoDbClient, tableNameVal: String,
 key: String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }
```

```
    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    val response = ddb.createTable(request)
    ddb.waitUntilTableExists { // suspend call
        tableName = tableNameVal
    }
    println("The table was successfully created
 ${response.tableDescription?.tableArn}")
}

suspend fun putRecordBatch(ddb: DynamoDbClient) {
    val sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE {'year':?,
 'title' : ?, 'info' : ?}"

    // Create three movies to add to the Amazon DynamoDB table.
    val parametersMovie1 = mutableListOf<AttributeValue>()
    parametersMovie1.add(AttributeValue.N("2022"))
    parametersMovie1.add(AttributeValue.S("My Movie 1"))
    parametersMovie1.add(AttributeValue.S("No Information"))

    val statementRequestMovie1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie1
```

```
    }

    // Set data for Movie 2.
    val parametersMovie2 = mutableListOf<AttributeValue>()
    parametersMovie2.add(AttributeValue.N("2022"))
    parametersMovie2.add(AttributeValue.S("My Movie 2"))
    parametersMovie2.add(AttributeValue.S("No Information"))

    val statementRequestMovie2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie2
    }

    // Set data for Movie 3.
    val parametersMovie3 = mutableListOf<AttributeValue>()
    parametersMovie3.add(AttributeValue.N("2022"))
    parametersMovie3.add(AttributeValue.S("My Movie 3"))
    parametersMovie3.add(AttributeValue.S("No Information"))

    val statementRequestMovie3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestMovie1)
    myBatchStatementList.add(statementRequestMovie2)
    myBatchStatementList.add(statementRequestMovie3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
    }
    val response = ddb.batchExecuteStatement(batchRequest)
    println("ExecuteStatement successful: " + response.toString())
    println("Added new movies using a batch command.")
}

suspend fun updateTableItemBatchBatch(ddb: DynamoDbClient) {
    val sqlStatement =
        "UPDATE MoviesPartiQBatch SET info = 'directors\":[\"Merian C. Cooper\",
\"Ernest B. Schoedsack' where year=? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
    parametersRec1.add(AttributeValue.N("2022"))
```

```
    parametersRec1.add(AttributeValue.S("My Movie 1"))
    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Update record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Update record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestRec1)
    myBatchStatementList.add(statementRequestRec2)
    myBatchStatementList.add(statementRequestRec3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
    }

    val response = ddb.batchExecuteStatement(batchRequest)
    println("ExecuteStatement successful: $response")
    println("Updated three movies using a batch command.")
    println("Items were updated!")
}

suspend fun deleteItemsBatch(ddb: DynamoDbClient) {
    // Specify three records to delete.
    val sqlStatement = "DELETE FROM MoviesPartiQBatch WHERE year = ? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
```

```
    parametersRec1.add(AttributeValue.N("2022"))
    parametersRec1.add(AttributeValue.S("My Movie 1"))

    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Specify record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Specify record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestRec1)
    myBatchStatementList.add(statementRequestRec2)
    myBatchStatementList.add(statementRequestRec3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
    }

    ddb.batchExecuteStatement(batchRequest)
    println("Deleted three movies using a batch command.")
}

suspend fun deleteTablePartiQLBatch(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }
```

```
    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a BatchExecuteStatementreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;

use function AwsUtilities\loadMovieData;
use function AwsUtilities\testable_readline;

class GettingStartedWithPartiQLBatch
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo
 using PHP!\n");
        echo("--------------------------------------\n");

        $uuid = uniqid();
```

```
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
 $tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
        $service->insertItemByPartiQLBatch($statement, $parameters);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
```

```
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
        ];

        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQLBatch($statement, $parameters);
        echo "Movie added and updated.\n";

        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);

        $movie = $service->getItemByPartiQLBatch($tableName, [$key]);
        echo "\nThe movie {$movie['Responses'][0]['Item']['title']['S']}
        was released in {$movie['Responses'][0]['Item']['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Responses'][0]['Item']
['title']['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQLBatch($statement, $parameters);

        $movie = $service->getItemByPartiQLBatch($tableName, [$key]);
        echo "Okay, you have rated {$movie['Responses'][0]['Item']['title']
['S']}
        as a {$movie['Responses'][0]['Item']['rating']['N']}\n";

        $service->deleteItemByPartiQLBatch($statement, $parameters);
```

```
        echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something
lighter, in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were
born:\n";
        $oops = "Oops! There were no movies released in that year (that we know
of).\n";
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
        echo ($display) ?: $oops;

        $yearsKey = [
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
```

```
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
    }
}

    public function insertItemByPartiQLBatch(string $statement, array
 $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function getItemByPartiQLBatch(string $tableName, array $keys): Result
    {
        $statements = [];
        foreach ($keys as $key) {
            list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);
            $statements[] = [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ];
        }

        return $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => $statements,
        ]);
    }

    public function updateItemByPartiQLBatch(string $statement, array
 $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
```

```
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function deleteItemByPartiQLBatch(string $statement, array
 $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que possa executar lotes de instruções PartiQL.

```
from datetime import datetime
from decimal import Decimal
import logging
from pprint import pprint

import boto3
```

```
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statements, param_list):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because
 the
        resource transforms input and output from plain old Python objects
 (POPOs) to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statements: The batch of PartiQL statements.
        :param param_list: The batch of PartiQL parameters that are associated
 with
                           each statement. This list must be in the same order as
 the
                           statements.
        :return: The responses returned from running the statements, if any.
        """
        try:
            output = self.dyn_resource.meta.client.batch_execute_statement(
                Statements=[
                    {"Statement": statement, "Parameters": params}
                    for statement, params in zip(statements, param_list)
                ]
            )
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute batch of PartiQL statements because the
 table "
                    "does not exist."
                )
            else:
                logger.error(
                    "Couldn't execute batch of PartiQL statements. Here's why:
 %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

Execute um cenário que crie uma tabela e execute consultas do PartiQL em lotes.

```
def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB PartiQL batch statement demo.")
    print("-" * 88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print("-" * 88)

    movie_data = [
        {
            "title": f"House PartiQL",
            "year": datetime.now().year - 5,
            "info": {
                "plot": "Wacky high jinks result from querying a mysterious
 database.",
                "rating": Decimal("8.5"),
            },
```

```
        },
        {
            "title": f"House PartiQL 2",
            "year": datetime.now().year - 3,
            "info": {
                "plot": "Moderate high jinks result from querying another
mysterious database.",
                "rating": Decimal("6.5"),
            },
        },
        {
            "title": f"House PartiQL 3",
            "year": datetime.now().year - 1,
            "info": {
                "plot": "Tepid high jinks result from querying yet another
mysterious database.",
                "rating": Decimal("2.5"),
            },
        },
    ]

    print(f"Inserting a batch of movies into table '{table_name}.")
    statements = [
        f'INSERT INTO "{table_name}" ' f"VALUE {{'title': ?, 'year': ?,
'info': ?}}"
    ] * len(movie_data)
    params = [list(movie.values()) for movie in movie_data]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)

    print(f"Getting data for a batch of movies.")
    statements = [f'SELECT * FROM "{table_name}" WHERE title=? AND year=?'] *
len(
        movie_data
    )
    params = [[movie["title"], movie["year"]] for movie in movie_data]
    output = wrapper.run_partiql(statements, params)
    for item in output["Responses"]:
        print(f"\n{item['Item']['title']}, {item['Item']['year']}")
        pprint(item["Item"])
    print("-" * 88)

    ratings = [Decimal("7.7"), Decimal("5.5"), Decimal("1.3")]
```

```
    print(f"Updating a batch of movies with new ratings.")
    statements = [
        f'UPDATE "{table_name}" SET info.rating=? ' f"WHERE title=? AND year=?"
    ] * len(movie_data)
    params = [
        [rating, movie["title"], movie["year"]]
        for rating, movie in zip(ratings, movie_data)
    ]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)

    print(f"Getting projected data from the table to verify our update.")
    output = wrapper.dyn_resource.meta.client.execute_statement(
        Statement=f'SELECT title, info.rating FROM "{table_name}"'
    )
    pprint(output["Items"])
    print("-" * 88)

    print(f"Deleting a batch of movies from the table.")
    statements = [f'DELETE FROM "{table_name}" WHERE title=? AND year=?'] * len(
        movie_data
    )
    params = [[movie["title"], movie["year"]] for movie in movie_data]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)

    print(f"Deleting table '{table_name}'...")
    scaffold.delete_table()
    print("-" * 88)

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        dyn_res = boto3.resource("dynamodb")
        scaffold = Scaffold(dyn_res)
        movies = PartiQLBatchWrapper(dyn_res)
        run_scenario(scaffold, movies, "doc-example-table-partiql-movies")
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

- Para obter detalhes da API, consulte a BatchExecuteStatementReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL em lotes.

```
table_name = "doc-example-table-movies-partiql-#{rand(10**4)}"
scaffold = Scaffold.new(table_name)
sdk = DynamoDBPartiQLBatch.new(table_name)

new_step(1, "Create a new DynamoDB table if none already exists.")
unless scaffold.exists?(table_name)
  puts("\nNo such table: #{table_name}. Creating it...")
  scaffold.create_table(table_name)
  print "Done!\n".green
end

new_step(2, "Populate DynamoDB table with movie data.")
download_file = "moviedata.json"
puts("Downloading movie database to #{download_file}...")
movie_data = scaffold.fetch_movie_data(download_file)
puts("Writing movie data from #{download_file} into your table...")
scaffold.write_batch(movie_data)
puts("Records added: #{movie_data.length}.")
print "Done!\n".green

new_step(3, "Select a batch of items from the movies table.")
puts "Let's select some popular movies for side-by-side comparison."
response = sdk.batch_execute_select([["Mean Girls", 2004], ["Goodfellas",
1977], ["The Prancing of the Lambs", 2005]])
puts("Items selected: #{response['responses'].length}\n")
```

```
  print "\nDone!\n".green

  new_step(4, "Delete a batch of items from the movies table.")
  sdk.batch_execute_write([["Mean Girls", 2004], ["Goodfellas", 1977], ["The
 Prancing of the Lambs", 2005]])
  print "\nDone!\n".green

  new_step(5, "Delete the table.")
  if scaffold.exists?(table_name)
    scaffold.delete_table
  end
end
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Ruby da API.

Consultar uma tabela do DynamoDB usando o PartiQL e um AWS SDK

Os exemplos de código a seguir mostram como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace PartiQL_Basics_Scenario
{
    public class PartiQLMethods
```

```
    {
        private static readonly AmazonDynamoDBClient Client = new
AmazonDynamoDBClient();


        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table where the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE
{{'title': ?, 'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset +=
25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
                                Parameters = new List<AttributeValue>
                                {
```

```
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
                            });
                        }

                        var response = await
Client.BatchExecuteStatementAsync(new BatchExecuteStatementRequest
                        {
                            Statements = statements,
                        });

                        // Wait between batches for movies to be successfully
added.
                        System.Threading.Thread.Sleep(3000);

                        success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                        // Clear the list of statements for the next batch.
                        statements.Clear();
                    }
                }
                catch (AmazonDynamoDBException ex)
                {
                    Console.WriteLine(ex.Message);
                }
            }

            return success;
        }

        /// <summary>
        /// Loads the contents of a JSON file into a list of movies to be
        /// added to the DynamoDB table.
        /// </summary>
        /// <param name="movieFileName">The full path to the JSON file.</param>
        /// <returns>A generic list of movie objects.</returns>
        public static List<Movie> ImportMovies(string movieFileName)
        {
            if (!File.Exists(movieFileName))
            {
                return null!;
```

```
            }

            using var sr = new StreamReader(movieFileName);
            string json = sr.ReadToEnd();
            var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

            if (allMovies is not null)
            {
                // Return the first 250 entries.
                return allMovies.GetRange(0, 250);
            }
            else
            {
                return null!;
            }
        }



        /// <summary>
        /// Uses a PartiQL SELECT statement to retrieve a single movie from the
        /// movie database.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
```

```
        }



        /// <summary>
        /// Retrieve multiple movies by year using a SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="year">The year the movies were released.</param>
        /// <returns></returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetMovies(string tableName, int year)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { N = year.ToString() },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }


        /// <summary>
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";
```

```
            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
        {
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });
```

```
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Deletes a single movie from the table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }


        /// <summary>
        /// Displays the list of movies returned from a database query.
        /// </summary>
        /// <param name="items">The list of movie information to display.</param>
        private static void DisplayMovies(List<Dictionary<string,
AttributeValue>> items)
        {
            if (items.Count > 0)
            {
                Console.WriteLine($"Found {items.Count} movies.");
```

```
                items.ForEach(item =>
 Console.WriteLine($"{item["year"].N}\t{item["title"].S}"));
            }
            else
            {
                Console.WriteLine($"Didn't find a movie that matched the supplied
 criteria.");
            }
        }


    }
}



        /// <summary>
        /// Uses a PartiQL SELECT statement to retrieve a single movie from the
        /// movie database.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
 GetSingleMovie(string tableName, string movieTitle)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
 ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }
```

```
        /// <summary>
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
 movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
 'year': ?}}";

            var response = await Client.ExecuteStatementAsync(new
 ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
 producer, string movieTitle, int year)
        {
```

```
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Deletes a single movie from the table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });
```

```
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using single PartiQL
 statements.
/*!
  \sa partiqlExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::partiqlExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
```

```
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate
it? ",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        request.SetStatement(sqlStream.str());

        // Create the parameter attributes.
        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
        attributes.push_back(infoMapAttribute);
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
```

```
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    //  3. Get the data for the movie using a "Select" statement.
(ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            // Print the retrieved movie information.
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();
```

```
            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were
retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }

    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
```

```
        }
    }

    std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

    //  5. Get the updated data for the movie using a "Select" statement.
(ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were
retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
```

```
    }

    std::cout << "Deleting the movie" << std::endl;

    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
 dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Movie successfully deleted." << std::endl;
    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;
```

```
    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." <<
std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
```

```
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
```

```
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
```

```
        count++;
    }
    return false;
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
// RunPartiQLSingleScenario shows you how to use the AWS SDK for Go
// to use PartiQL to query a table that stores data about movies.
//
// * Use PartiQL statements to add, get, update, and delete data for individual
 movies.
//
// This example creates an Amazon DynamoDB service client from the specified
 sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLSingleScenario(sdkConfig aws.Config, tableName string) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon DynamoDB PartiQL single action demo.")
```

```
log.Println(strings.Repeat("-", 88))

tableBasics := actions.TableBasics{
 DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
 TableName:      tableName,
}
runner := actions.PartiQLRunner{
 DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
 TableName:      tableName,
}

exists, err := tableBasics.TableExists()
if err != nil {
 panic(err)
}
if !exists {
 log.Printf("Creating table %v...\n", tableName)
 _, err = tableBasics.CreateMovieTable()
 if err != nil {
  panic(err)
 } else {
  log.Printf("Created table %v.\n", tableName)
 }
} else {
 log.Printf("Table %v already exists.\n", tableName)
}
log.Println(strings.Repeat("-", 88))

currentYear, _, _ := time.Now().Date()
customMovie := actions.Movie{
 Title: "24 Hour PartiQL People",
 Year:  currentYear,
 Info: map[string]interface{}{
  "plot":   "A group of data developers discover a new query language they can't
stop using.",
  "rating": 9.9,
 },
}

log.Printf("Inserting movie '%v' released in %v.", customMovie.Title,
customMovie.Year)
err = runner.AddMovie(customMovie)
if err == nil {
 log.Printf("Added %v to the movie table.\n", customMovie.Title)
```

```
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Getting data for movie '%v' released in %v.", customMovie.Title,
 customMovie.Year)
 movie, err := runner.GetMovie(customMovie.Title, customMovie.Year)
 if err == nil {
  log.Println(movie)
 }
 log.Println(strings.Repeat("-", 88))

 newRating := 6.6
 log.Printf("Updating movie '%v' with a rating of %v.", customMovie.Title,
 newRating)
 err = runner.UpdateMovie(customMovie, newRating)
 if err == nil {
  log.Printf("Updated %v with a new rating.\n", customMovie.Title)
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Getting data again to verify the update.")
 movie, err = runner.GetMovie(customMovie.Title, customMovie.Year)
 if err == nil {
  log.Println(movie)
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Deleting movie '%v'.\n", customMovie.Title)
 err = runner.DeleteMovie(customMovie)
 if err == nil {
  log.Printf("Deleted %v.\n", customMovie.Title)
 }

 err = tableBasics.DeleteTable()
 if err == nil {
  log.Printf("Deleted table %v.\n", tableBasics.TableName)
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite
 primary key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

Crie uma estrutura e métodos que executem instruções partiQL.

```
// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
```

```
// PartiQL examples. It contains a DynamoDB service client that is used to act on
 the
// specified table.
type PartiQLRunner struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
func (runner PartiQLRunner) AddMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
 }
 return err
}



// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB
 table by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
 var movie Movie
 params, err := attributevalue.MarshalList([]interface{}{title, year})
 if err != nil {
  panic(err)
 }
 response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
```

```
    fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
     runner.TableName)),
   Parameters: params,
  })
  if err != nil {
   log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
  } else {
   err = attributevalue.UnmarshalMap(response.Items[0], &movie)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   }
  }
  return movie, err
}



// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie
 that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
 params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
 }
 return err
}



// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the
 DynamoDB table.
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
```

```
 params, err := attributevalue.MarshalList([]interface{}{movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ScenarioPartiQ {
    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <fileName>
```

```
                Where:
                    fileName - The path to the moviedata.json file that you can
download from the Amazon DynamoDB Developer Guide.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String fileName = args[0];
        String tableName = "MoviesPartiQ";
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        System.out.println(
                "******* Creating an Amazon DynamoDB table named MoviesPartiQ
with a key named year and a sort key named title.");
        createTable(ddb, tableName);

        System.out.println("******* Loading data into the MoviesPartiQ table.");
        loadData(ddb, fileName);

        System.out.println("******* Getting data from the MoviesPartiQ table.");
        getItem(ddb);

        System.out.println("******* Putting a record into the MoviesPartiQ
table.");
        putRecord(ddb);

        System.out.println("******* Updating a record.");
        updateTableItem(ddb);

        System.out.println("******* Querying the movies released in 2013.");
        queryTable(ddb);

        System.out.println("******* Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void createTable(DynamoDbClient ddb, String tableName) {
```

```
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("year")
                .attributeType("N")
                .build());

        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("title")
                .attributeType("S")
                .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
                .attributeName("year")
                .keyType(KeyType.HASH)
                .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
                .attributeName("title")
                .keyType(KeyType.RANGE) // Sort
                .build();

        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(new Long(10))
                        .writeCapacityUnits(new Long(10))
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();
```

```
            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String fileName) throws
IOException {

        String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?,
'title' : ?, 'info' : ?}";
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        List<AttributeValue> parameters = new ArrayList<>();
        while (iter.hasNext()) {

            // Add 200 movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf(year))
                    .build();

            AttributeValue att2 = AttributeValue.builder()
                    .s(title)
```

```
                    .build();

            AttributeValue att3 = AttributeValue.builder()
                    .s(info)
                    .build();

            parameters.add(att1);
            parameters.add(att2);
            parameters.add(att3);

            // Insert the movie into the Amazon DynamoDB table.
            executeStatementRequest(ddb, sqlStatement, parameters);
            System.out.println("Added Movie " + title);

            parameters.remove(att1);
            parameters.remove(att2);
            parameters.remove(att3);
            t++;
        }
    }

    public static void getItem(DynamoDbClient ddb) {

        String sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and
title=?";
        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
                .n("2012")
                .build();

        AttributeValue att2 = AttributeValue.builder()
                .s("The Perks of Being a Wallflower")
                .build();

        parameters.add(att1);
        parameters.add(att2);

        try {
            ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
            System.out.println("ExecuteStatement successful: " +
response.toString());

        } catch (DynamoDbException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void putRecord(DynamoDbClient ddb) {

        String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?,
 'title' : ?, 'info' : ?}";
        try {
            List<AttributeValue> parameters = new ArrayList<>();

            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf("2020"))
                    .build();

            AttributeValue att2 = AttributeValue.builder()
                    .s("My Movie")
                    .build();

            AttributeValue att3 = AttributeValue.builder()
                    .s("No Information")
                    .build();

            parameters.add(att1);
            parameters.add(att2);
            parameters.add(att3);

            executeStatementRequest(ddb, sqlStatement, parameters);
            System.out.println("Added new movie.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateTableItem(DynamoDbClient ddb) {

        String sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\":
[\"Merian C. Cooper\",\"Ernest B. Schoedsack' where year=? and title=?";
        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
                .n(String.valueOf("2013"))
```

```
                .build();

        AttributeValue att2 = AttributeValue.builder()
                .s("The East")
                .build();

        parameters.add(att1);
        parameters.add(att2);

        try {
            executeStatementRequest(ddb, sqlStatement, parameters);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("Item was updated!");
    }

    // Query the table where the year is 2013.
    public static void queryTable(DynamoDbClient ddb) {
        String sqlStatement = "SELECT * FROM MoviesPartiQ where year = ? ORDER BY
year";
        try {

            List<AttributeValue> parameters = new ArrayList<>();
            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf("2013"))
                    .build();
            parameters.add(att1);

            // Get items in the table and write out the ID value.
            ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
            System.out.println("ExecuteStatement successful: " +
response.toString());

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName)
 {

        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }

    private static ExecuteStatementResponse
 executeStatementRequest(DynamoDbClient ddb, String statement,
            List<AttributeValue> parameters) {
        ExecuteStatementRequest request = ExecuteStatementRequest.builder()
                .statement(statement)
                .parameters(parameters)
                .build();

        return ddb.executeStatement(request);
    }

    private static void processResults(ExecuteStatementResponse
 executeStatementResult) {
        System.out.println("ExecuteStatement successful: " +
 executeStatementResult.toString());
    }
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute instruções PartiQL individuais.

```
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  DynamoDBDocumentClient,
  ExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);
const tableName = "SingleOriginCoffees";

export const main = async () => {
  /**
   * Create a table.
   */

  log("Creating a table.");
  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
    // Set the billing mode to PAY_PER_REQUEST to
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
```

```
    AttributeDefinitions: [
      {
        AttributeName: "varietal",
        // 'S' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "S",
      },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [{ AttributeName: "varietal", KeyType: "HASH" }],
  });
  await client.send(createTableCommand);
  log(`Table created: ${tableName}.`);

  /**
   * Wait until the table is active.
   */

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Insert an item.
   */

  log("Inserting a coffee into the table.");
  const addItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.insert.html
    Statement: `INSERT INTO ${tableName} value {'varietal':?, 'profile':?}`,
    Parameters: ["arabica", ["chocolate", "floral"]],
  });
  await client.send(addItemStatementCommand);
  log(`Coffee inserted.`);
```

```
  /**
   * Select an item.
   */

  log("Selecting the coffee from the table.");
  const selectItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.select.html
    Statement: `SELECT * FROM ${tableName} WHERE varietal=?`,
    Parameters: ["arabica"],
  });
  const selectItemResponse = await docClient.send(selectItemStatementCommand);
  log(`Got coffee: ${JSON.stringify(selectItemResponse.Items[0])}`);

  /**
   * Update the item.
   */

  log("Add a flavor profile to the coffee.");
  const updateItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.update.html
    Statement: `UPDATE ${tableName} SET profile=list_append(profile, ?) WHERE
 varietal=?`,
    Parameters: [["fruity"], "arabica"],
  });
  await client.send(updateItemStatementCommand);
  log(`Updated coffee`);

  /**
   * Delete the item.
   */

  log("Deleting the coffee.");
  const deleteItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.delete.html
    Statement: `DELETE FROM ${tableName} WHERE varietal=?`,
    Parameters: ["arabica"],
  });
  await docClient.send(deleteItemStatementCommand);
  log("Coffee deleted.");

  /**
```

```
   * Delete the table.
   */

  log("Deleting the table.");
  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
          <fileName>

        Where:
           fileName - The path to the moviedata.json you can download from the
 Amazon DynamoDB Developer Guide.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(1)
    }

    val ddb = DynamoDbClient { region = "us-east-1" }
    val tableName = "MoviesPartiQ"
```

```
    // Get the moviedata.json from the Amazon DynamoDB Developer Guide.
    val fileName = args[0]
    println("Creating an Amazon DynamoDB table named MoviesPartiQ with a key
 named id and a sort key named title.")
    createTablePartiQL(ddb, tableName, "year")
    loadDataPartiQL(ddb, fileName)

    println("******* Getting data from the MoviesPartiQ table.")
    getMoviePartiQL(ddb)

    println("******* Putting a record into the MoviesPartiQ table.")
    putRecordPartiQL(ddb)

    println("******* Updating a record.")
    updateTableItemPartiQL(ddb)

    println("******* Querying the movies released in 2013.")
    queryTablePartiQL(ddb)

    println("******* Deleting the MoviesPartiQ table.")
    deleteTablePartiQL(tableName)
}

suspend fun createTablePartiQL(ddb: DynamoDbClient, tableNameVal: String, key:
 String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }
```

```
    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    val response = ddb.createTable(request)
    ddb.waitUntilTableExists { // suspend call
        tableName = tableNameVal
    }
    println("The table was successfully created
 ${response.tableDescription?.tableArn}")
}

suspend fun loadDataPartiQL(ddb: DynamoDbClient, fileName: String) {
    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?,
 'info' : ?}"
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode
    var t = 0

    while (iter.hasNext()) {
        if (t == 200) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()

        val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
        parameters.add(AttributeValue.N(year.toString()))
        parameters.add(AttributeValue.S(title))
        parameters.add(AttributeValue.S(info))
```

```
        executeStatementPartiQL(ddb, sqlStatement, parameters)
        println("Added Movie $title")
        parameters.clear()
        t++
    }
}

suspend fun getMoviePartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and title=?"
    val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
    parameters.add(AttributeValue.N("2012"))
    parameters.add(AttributeValue.S("The Perks of Being a Wallflower"))
    val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("ExecuteStatement successful: $response")
}

suspend fun putRecordPartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?,
 'info' : ?}"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2020"))
    parameters.add(AttributeValue.S("My Movie"))
    parameters.add(AttributeValue.S("No Info"))
    executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("Added new movie.")
}

suspend fun updateTableItemPartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\":[\"Merian C.
 Cooper\",\"Ernest B. Schoedsack\' where year=? and title=?"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2013"))
    parameters.add(AttributeValue.S("The East"))
    executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("Item was updated!")
}

// Query the table where the year is 2013.
suspend fun queryTablePartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "SELECT * FROM MoviesPartiQ where year = ?"

    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2013"))
```

```
    val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("ExecuteStatement successful: $response")
}

suspend fun deleteTablePartiQL(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}

suspend fun executeStatementPartiQL(
    ddb: DynamoDbClient,
    statementVal: String,
    parametersVal: List<AttributeValue>
): ExecuteStatementResponse {
    val request = ExecuteStatementRequest {
        statement = statementVal
        parameters = parametersVal
    }

    return ddb.executeStatement(request)
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;

use function AwsUtilities\testable_readline;
use function AwsUtilities\loadMovieData;

class GettingStartedWithPartiQL
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo
 using PHP!\n");
        echo("--------------------------------------\n");

        $uuid = uniqid();
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
 $tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
```

```
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
        $service->insertItemByPartiQL($statement, $parameters);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
        ];

        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQL($statement, $parameters);
        echo "Movie added and updated.\n";



        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);

        $movie = $service->getItemByPartiQL($tableName, $key);
```

```
        echo "\nThe movie {$movie['Items'][0]['title']['S']} was released in
 {$movie['Items'][0]['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Items'][0]['title']
['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1
 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQL($statement, $parameters);

        $movie = $service->getItemByPartiQL($tableName, $key);
        echo "Okay, you have rated {$movie['Items'][0]['title']['S']} as a
 {$movie['Items'][0]['rating']['N']}\n";

        $service->deleteItemByPartiQL($statement, $parameters);
        echo "But, bad news, this was a trap. That movie has now been deleted
 because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something
 lighter, in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were
 born:\n";
        $oops = "Oops! There were no movies released in that year (that we know
 of).\n";
```

```
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
        echo ($display) ?: $oops;

        $yearsKey = [
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
    }
}

    public function insertItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ]);
    }

    public function getItemByPartiQL(string $tableName, array $key): Result
    {
        list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);

        return $this->dynamoDbClient->executeStatement([
```

```
            'Parameters' => $parameters,
            'Statement' => $statement,
        ]);
    }

    public function updateItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }

    public function deleteItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que possa executar instruções PartiQL.

```
from datetime import datetime
from decimal import Decimal
import logging
from pprint import pprint
```

```
import boto3
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statement, params):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because
 the
        resource transforms input and output from plain old Python objects
 (POPOs) to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statement: The PartiQL statement.
        :param params: The list of PartiQL parameters. These are applied to the
                       statement in the order they are listed.
        :return: The items returned from the statement, if any.
        """
        try:
            output = self.dyn_resource.meta.client.execute_statement(
                Statement=statement, Parameters=params
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute PartiQL '%s' because the table does not
 exist.",
                    statement,
```

```
                )
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s",
                    statement,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB PartiQL single statement demo.")
    print("-" * 88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print("-" * 88)

    title = "24 Hour PartiQL People"
    year = datetime.now().year
    plot = "A group of data developers discover a new query language they can't
 stop using."
    rating = Decimal("9.9")

    print(f"Inserting movie '{title}' released in {year}.")
    wrapper.run_partiql(
        f"INSERT INTO \"{table_name}\" VALUE {{'title': ?, 'year': ?,
 'info': ?}}",
        [title, year, {"plot": plot, "rating": rating}],
    )
    print("Success!")
    print("-" * 88)
```

```
    print(f"Getting data for movie '{title}' released in {year}.")
    output = wrapper.run_partiql(
        f'SELECT * FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    for item in output["Items"]:
        print(f"\n{item['title']}, {item['year']}")
        pprint(output["Items"])
    print("-" * 88)

    rating = Decimal("2.4")
    print(f"Updating movie '{title}' with a rating of {float(rating)}.")
    wrapper.run_partiql(
        f'UPDATE "{table_name}" SET info.rating=? WHERE title=? AND year=?',
        [rating, title, year],
    )
    print("Success!")
    print("-" * 88)

    print(f"Getting data again to verify our update.")
    output = wrapper.run_partiql(
        f'SELECT * FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    for item in output["Items"]:
        print(f"\n{item['title']}, {item['year']}")
        pprint(output["Items"])
    print("-" * 88)

    print(f"Deleting movie '{title}' released in {year}.")
    wrapper.run_partiql(
        f'DELETE FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    print("Success!")
    print("-" * 88)

    print(f"Deleting table '{table_name}'...")
    scaffold.delete_table()
    print("-" * 88)

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
```

```
        dyn_res = boto3.resource("dynamodb")
        scaffold = Scaffold(dyn_res)
        movies = PartiQLWrapper(dyn_res)
        run_scenario(scaffold, movies, "doc-example-table-partiql-movies")
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

- Para obter detalhes da API, consulte a ExecuteStatementReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
table_name = "doc-example-table-movies-partiql-#{rand(10**8)}"
scaffold = Scaffold.new(table_name)
sdk = DynamoDBPartiQLSingle.new(table_name)

new_step(1, "Create a new DynamoDB table if none already exists.")
unless scaffold.exists?(table_name)
  puts("\nNo such table: #{table_name}. Creating it...")
  scaffold.create_table(table_name)
  print "Done!\n".green
end

new_step(2, "Populate DynamoDB table with movie data.")
download_file = "moviedata.json"
puts("Downloading movie database to #{download_file}...")
movie_data = scaffold.fetch_movie_data(download_file)
puts("Writing movie data from #{download_file} into your table...")
scaffold.write_batch(movie_data)
puts("Records added: #{movie_data.length}.")
print "Done!\n".green
```

```
  new_step(3, "Select a single item from the movies table.")
  response = sdk.select_item_by_title("Star Wars")
  puts("Items selected for title 'Star Wars': #{response.items.length}\n")
  print "#{response.items.first}".yellow
  print "\n\nDone!\n".green

  new_step(4, "Update a single item from the movies table.")
  puts "Let's correct the rating on The Big Lebowski to 10.0."
  sdk.update_rating_by_title("The Big Lebowski", 1998, 10.0)
  print "\nDone!\n".green

  new_step(5, "Delete a single item from the movies table.")
  puts "Let's delete The Silence of the Lambs because it's just too scary."
  sdk.delete_item_by_title("The Silence of the Lambs", 1991)
  print "\nDone!\n".green

  new_step(6, "Insert a new item into the movies table.")
  puts "Let's create a less-scary movie called The Prancing of the Lambs."
  sdk.insert_item("The Prancing of the Lambs", 2005, "A movie about happy
 livestock.", 5.0)
  print "\nDone!\n".green

  new_step(7, "Delete the table.")
  if scaffold.exists?(table_name)
    scaffold.delete_table
  end
end
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_table(
    client: &Client,
    table: &str,
    key: &str,
) -> Result<(), SdkError<CreateTableError>> {
    let ad = AttributeDefinition::builder()
        .attribute_name(key)
        .attribute_type(ScalarAttributeType::S)
        .build()
        .expect("creating AttributeDefinition");

    let ks = KeySchemaElement::builder()
        .attribute_name(key)
        .key_type(KeyType::Hash)
        .build()
        .expect("creating KeySchemaElement");

    let pt = ProvisionedThroughput::builder()
        .read_capacity_units(10)
        .write_capacity_units(5)
        .build()
        .expect("creating ProvisionedThroughput");

    match client
        .create_table()
        .table_name(table)
        .key_schema(ks)
        .attribute_definitions(ad)
        .provisioned_throughput(pt)
        .send()
        .await
    {
        Ok(_) => Ok(()),
        Err(e) => Err(e),
    }
}

async fn add_item(client: &Client, item: Item) -> Result<(),
 SdkError<ExecuteStatementError>> {
    match client
        .execute_statement()
        .statement(format!(
            r#"INSERT INTO "{}" VALUE {{
```

```
                "{}": ?,
                "acount_type": ?,
                "age": ?,
                "first_name": ?,
                "last_name": ?
        }} "#,
            item.table, item.key
        ))
        .set_parameters(Some(vec![
            AttributeValue::S(item.utype),
            AttributeValue::S(item.age),
            AttributeValue::S(item.first_name),
            AttributeValue::S(item.last_name),
        ]))
        .send()
        .await
    {
        Ok(_) => Ok(()),
        Err(e) => Err(e),
    }
}

async fn query_item(client: &Client, item: Item) -> bool {
    match client
        .execute_statement()
        .statement(format!(
            r#"SELECT * FROM "{}" WHERE "{}" = ?"#,
            item.table, item.key
        ))
        .set_parameters(Some(vec![AttributeValue::S(item.value)]))
        .send()
        .await
    {
        Ok(resp) => {
            if !resp.items().is_empty() {
                println!("Found a matching entry in the table:");
                println!("{:?}", resp.items.unwrap_or_default().pop());
                true
            } else {
                println!("Did not find a match.");
                false
            }
        }
        Err(e) => {
```

```
            println!("Got an error querying table:");
            println!("{}", e);
            process::exit(1);
        }
    }
}

async fn remove_item(client: &Client, table: &str, key: &str, value: String) ->
 Result<(), Error> {
    client
        .execute_statement()
        .statement(format!(r#"DELETE FROM "{table}" WHERE "{key}" = ?"#))
        .set_parameters(Some(vec![AttributeValue::S(value)]))
        .send()
        .await?;

    println!("Deleted item.");

    Ok(())
}

async fn remove_table(client: &Client, table: &str) -> Result<(), Error> {
    client.delete_table().table_name(table).send().await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWS SDK for Rust.

Usar um modelo de documento para o DynamoDB usando um AWS SDK

O exemplo de código a seguir mostra como realizar operações de criação, leitura, atualização e exclusão (CRUD) e operações em lote usando um modelo de documento para o DynamoDB e um AWS SDK.

Para obter mais informações, consulte o modelo de documento.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Execute operações CRUD usando um modelo de documento.

```
/// <summary>
/// Performs CRUD operations on an Amazon DynamoDB table.
/// </summary>
public class MidlevelItemCRUD
{
    public static async Task Main()
    {
        var tableName = "ProductCatalog";
        var sampleBookId = 555;

        var client = new AmazonDynamoDBClient();
        var productCatalog = LoadTable(client, tableName);

        await CreateBookItem(productCatalog, sampleBookId);
        RetrieveBook(productCatalog, sampleBookId);

        // Couple of sample updates.
        UpdateMultipleAttributes(productCatalog, sampleBookId);
        UpdateBookPriceConditionally(productCatalog, sampleBookId);

        // Delete.
        await DeleteBook(productCatalog, sampleBookId);
    }

    /// <summary>
    /// Loads the contents of a DynamoDB table.
    /// </summary>
    /// <param name="client">An initialized DynamoDB client object.</param>
    /// <param name="tableName">The name of the table to load.</param>
    /// <returns>A DynamoDB table object.</returns>
```

```
        public static Table LoadTable(IAmazonDynamoDB client, string tableName)
        {
            Table productCatalog = Table.LoadTable(client, tableName);
            return productCatalog;
        }

        /// <summary>
        /// Creates an example book item and adds it to the DynamoDB table
        /// ProductCatalog.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async Task CreateBookItem(Table productCatalog, int
sampleBookId)
        {
            Console.WriteLine("\n*** Executing CreateBookItem() ***");
            var book = new Document
            {
                ["Id"] = sampleBookId,
                ["Title"] = "Book " + sampleBookId,
                ["Price"] = 19.99,
                ["ISBN"] = "111-1111111111",
                ["Authors"] = new List<string> { "Author 1", "Author 2", "Author
3" },
                ["PageCount"] = 500,
                ["Dimensions"] = "8.5x11x.5",
                ["InPublication"] = new DynamoDBBool(true),
                ["InStock"] = new DynamoDBBool(false),
                ["QuantityOnHand"] = 0,
            };

            // Adds the book to the ProductCatalog table.
            await productCatalog.PutItemAsync(book);
        }

        /// <summary>
        /// Retrieves an item, a book, from the DynamoDB ProductCatalog table.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async void RetrieveBook(
          Table productCatalog,
```

```
          int sampleBookId)
       {
           Console.WriteLine("\n*** Executing RetrieveBook() ***");

           // Optional configuration.
           var config = new GetItemOperationConfig
           {
               AttributesToGet = new List<string> { "Id", "ISBN", "Title",
"Authors", "Price" },
               ConsistentRead = true,
           };

           Document document = await productCatalog.GetItemAsync(sampleBookId,
config);
           Console.WriteLine("RetrieveBook: Printing book retrieved...");
           PrintDocument(document);
       }

       /// <summary>
       /// Updates multiple attributes for a book and writes the changes to the
       /// DynamoDB table ProductCatalog.
       /// </summary>
       /// <param name="productCatalog">A DynamoDB table object.</param>
       /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
       public static async void UpdateMultipleAttributes(
         Table productCatalog,
         int sampleBookId)
       {
           Console.WriteLine("\nUpdating multiple attributes....");
           int partitionKey = sampleBookId;

           var book = new Document
           {
               ["Id"] = partitionKey,

               // List of attribute updates.
               // The following replaces the existing authors list.
               ["Authors"] = new List<string> { "Author x", "Author y" },
               ["newAttribute"] = "New Value",
               ["ISBN"] = null, // Remove it.
           };

           // Optional parameters.
```

```
            var config = new UpdateItemOperationConfig
            {
                // Gets updated item in response.
                ReturnValues = ReturnValues.AllNewAttributes,
            };

            Document updatedBook = await productCatalog.UpdateItemAsync(book,
config);
            Console.WriteLine("UpdateMultipleAttributes: Printing item after
updates ...");
            PrintDocument(updatedBook);
        }

        /// <summary>
        /// Updates a book item if it meets the specified criteria.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async void UpdateBookPriceConditionally(
          Table productCatalog,
          int sampleBookId)
        {
            Console.WriteLine("\n*** Executing UpdateBookPriceConditionally()
***");

            int partitionKey = sampleBookId;

            var book = new Document
            {
                ["Id"] = partitionKey,
                ["Price"] = 29.99,
            };

            // For conditional price update, creating a condition expression.
            var expr = new Expression
            {
                ExpressionStatement = "Price = :val",
            };
            expr.ExpressionAttributeValues[":val"] = 19.00;

            // Optional parameters.
            var config = new UpdateItemOperationConfig
            {
```

```
                ConditionalExpression = expr,
                ReturnValues = ReturnValues.AllNewAttributes,
            };

            Document updatedBook = await productCatalog.UpdateItemAsync(book,
config);
            Console.WriteLine("UpdateBookPriceConditionally: Printing item whose
price was conditionally updated");
            PrintDocument(updatedBook);
        }

        /// <summary>
        /// Deletes the book with the supplied Id value from the DynamoDB table
        /// ProductCatalog.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async Task DeleteBook(
          Table productCatalog,
          int sampleBookId)
        {
            Console.WriteLine("\n*** Executing DeleteBook() ***");

            // Optional configuration.
            var config = new DeleteItemOperationConfig
            {
                // Returns the deleted item.
                ReturnValues = ReturnValues.AllOldAttributes,
            };
            Document document = await
productCatalog.DeleteItemAsync(sampleBookId, config);
            Console.WriteLine("DeleteBook: Printing deleted just deleted...");

            PrintDocument(document);
        }

        /// <summary>
        /// Prints the information for the supplied DynamoDB document.
        /// </summary>
        /// <param name="updatedDocument">A DynamoDB document object.</param>
        public static void PrintDocument(Document updatedDocument)
        {
            if (updatedDocument is null)
```

```
            {
                return;
            }

            foreach (var attribute in updatedDocument.GetAttributeNames())
            {
                string stringValue = null;
                var value = updatedDocument[attribute];

                if (value is null)
                {
                    continue;
                }

                if (value is Primitive)
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                  select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}", attribute,
stringValue);
            }
        }
    }
```

Execute operações de gravação em lote usando um modelo de documento.

```
    /// <summary>
    /// Shows how to use mid-level Amazon DynamoDB API calls to perform batch
    /// operations.
    /// </summary>
    public class MidLevelBatchWriteItem
    {
```

```
        public static async Task Main()
        {
            IAmazonDynamoDB client = new AmazonDynamoDBClient();

            await SingleTableBatchWrite(client);
            await MultiTableBatchWrite(client);
        }

        /// <summary>
        /// Perform a batch operation on a single DynamoDB table.
        /// </summary>
        /// <param name="client">An initialized DynamoDB object.</param>
        public static async Task SingleTableBatchWrite(IAmazonDynamoDB client)
        {
            Table productCatalog = Table.LoadTable(client, "ProductCatalog");
            var batchWrite = productCatalog.CreateBatchWrite();

            var book1 = new Document
            {
                ["Id"] = 902,
                ["Title"] = "My book1 in batch write using .NET helper classes",
                ["ISBN"] = "902-11-11-1111",
                ["Price"] = 10,
                ["ProductCategory"] = "Book",
                ["Authors"] = new List<string> { "Author 1", "Author 2", "Author
3" },
                ["Dimensions"] = "8.5x11x.5",
                ["InStock"] = new DynamoDBBool(true),
                ["QuantityOnHand"] = new DynamoDBNull(), // Quantity is unknown
at this time.
            };

            batchWrite.AddDocumentToPut(book1);

            // Specify delete item using overload that takes PK.
            batchWrite.AddKeyToDelete(12345);
            Console.WriteLine("Performing batch write in
SingleTableBatchWrite()");
            await batchWrite.ExecuteAsync();
        }

        /// <summary>
        /// Perform a batch operation involving multiple DynamoDB tables.
        /// </summary>
```

```
        /// <param name="client">An initialized DynamoDB client object.</param>
        public static async Task MultiTableBatchWrite(IAmazonDynamoDB client)
        {
            // Specify item to add in the Forum table.
            Table forum = Table.LoadTable(client, "Forum");
            var forumBatchWrite = forum.CreateBatchWrite();

            var forum1 = new Document
            {
                ["Name"] = "Test BatchWrite Forum",
                ["Threads"] = 0,
            };
            forumBatchWrite.AddDocumentToPut(forum1);

            // Specify item to add in the Thread table.
            Table thread = Table.LoadTable(client, "Thread");
            var threadBatchWrite = thread.CreateBatchWrite();

            var thread1 = new Document
            {
                ["ForumName"] = "S3 forum",
                ["Subject"] = "My sample question",
                ["Message"] = "Message text",
                ["KeywordTags"] = new List<string> { "S3", "Bucket" },
            };
            threadBatchWrite.AddDocumentToPut(thread1);

            // Specify item to delete from the Thread table.
            threadBatchWrite.AddKeyToDelete("someForumName", "someSubject");

            // Create multi-table batch.
            var superBatch = new MultiTableDocumentBatchWrite();
            superBatch.AddBatch(forumBatchWrite);
            superBatch.AddBatch(threadBatchWrite);
            Console.WriteLine("Performing batch write in
MultiTableBatchWrite()");

            // Execute the batch.
            await superBatch.ExecuteAsync();
        }
    }
```

Verifique uma tabela usando um modelo de documento.

```
   /// <summary>
   /// Shows how to use mid-level Amazon DynamoDB API calls to scan a DynamoDB
   /// table for values.
   /// </summary>
   public class MidLevelScanOnly
   {
       public static async Task Main()
       {
           IAmazonDynamoDB client = new AmazonDynamoDBClient();

           Table productCatalogTable = Table.LoadTable(client,
"ProductCatalog");

           await FindProductsWithNegativePrice(productCatalogTable);
           await FindProductsWithNegativePriceWithConfig(productCatalogTable);
       }

       /// <summary>
       /// Retrieves any products that have a negative price in a DynamoDB
table.
       /// </summary>
       /// <param name="productCatalogTable">A DynamoDB table object.</param>
       public static async Task FindProductsWithNegativePrice(
         Table productCatalogTable)
       {
           // Assume there is a price error. So we scan to find items priced <
0.
           var scanFilter = new ScanFilter();
           scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

           Search search = productCatalogTable.Scan(scanFilter);

           do
           {
               var documentList = await search.GetNextSetAsync();
               Console.WriteLine("\nFindProductsWithNegativePrice:
printing ............");

               foreach (var document in documentList)
               {
                   PrintDocument(document);
```

```
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Finds any items in the ProductCatalog table using a DynamoDB
        /// configuration object.
        /// </summary>
        /// <param name="productCatalogTable">A DynamoDB table object.</param>
        public static async Task FindProductsWithNegativePriceWithConfig(
          Table productCatalogTable)
        {
            // Assume there is a price error. So we scan to find items priced <
0.
            var scanFilter = new ScanFilter();
            scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

            var config = new ScanOperationConfig()
            {
                Filter = scanFilter,
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string> { "Title", "Id" },
            };

            Search search = productCatalogTable.Scan(config);

            do
            {
                var documentList = await search.GetNextSetAsync();
                Console.WriteLine("\nFindProductsWithNegativePriceWithConfig:
printing ............");

                foreach (var document in documentList)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Displays the details of the passed DynamoDB document object on the
        /// console.
```

```
        /// </summary>
        /// <param name="document">A DynamoDB document object.</param>
        public static void PrintDocument(Document document)
        {
            Console.WriteLine();
            foreach (var attribute in document.GetAttributeNames())
            {
                string stringValue = null;
                var value = document[attribute];
                if (value is Primitive)
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                    select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}");
            }
        }
    }
```

Consulte e verifique uma tabela usando um modelo de documento.

```
    /// <summary>
    /// Shows how to perform mid-level query procedures on an Amazon DynamoDB
    /// table.
    /// </summary>
    public class MidLevelQueryAndScan
    {
        public static async Task Main()
        {
            IAmazonDynamoDB client = new AmazonDynamoDBClient();

            // Query examples.
            Table replyTable = Table.LoadTable(client, "Reply");
```

```
            string forumName = "Amazon DynamoDB";
            string threadSubject = "DynamoDB Thread 2";

            await FindRepliesInLast15Days(replyTable);
            await FindRepliesInLast15DaysWithConfig(replyTable, forumName,
 threadSubject);
            await FindRepliesPostedWithinTimePeriod(replyTable, forumName,
 threadSubject);

            // Get Example.
            Table productCatalogTable = Table.LoadTable(client,
 "ProductCatalog");
            int productId = 101;

            await GetProduct(productCatalogTable, productId);
        }

        /// <summary>
        /// Retrieves information about a product from the DynamoDB table
        /// ProductCatalog based on the product ID and displays the information
        /// on the console.
        /// </summary>
        /// <param name="tableName">The name of the table from which to retrieve
        /// product information.</param>
        /// <param name="productId">The ID of the product to retrieve.</param>
        public static async Task GetProduct(Table tableName, int productId)
        {
            Console.WriteLine("*** Executing GetProduct() ***");
            Document productDocument = await tableName.GetItemAsync(productId);
            if (productDocument != null)
            {
                PrintDocument(productDocument);
            }
            else
            {
                Console.WriteLine("Error: product " + productId + " does not
 exist");
            }
        }

        /// <summary>
        /// Retrieves replies from the passed DynamoDB table object.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
```

```
        public static async Task FindRepliesInLast15Days(
          Table table)
        {
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
            var filter = new QueryFilter("Id", QueryOperator.Equal, "Id");
            filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);

            // Use Query overloads that take the minimum required query
parameters.
            Search search = table.Query(filter);

            do
            {
                var documentSet = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesInLast15Days:
printing ............");

                foreach (var document in documentSet)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Retrieve replies made during a specific time period.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadSubject">The subject of the thread, which we are
        /// searching for replies.</param>
        public static async Task FindRepliesPostedWithinTimePeriod(
          Table table,
          string forumName,
          string threadSubject)
        {
            DateTime startDate = DateTime.UtcNow.Subtract(new TimeSpan(21, 0, 0,
0));
            DateTime endDate = DateTime.UtcNow.Subtract(new TimeSpan(1, 0, 0,
0));
```

```
            var filter = new QueryFilter("Id", QueryOperator.Equal, forumName +
"#" + threadSubject);
            filter.AddCondition("ReplyDateTime", QueryOperator.Between,
startDate, endDate);

            var config = new QueryOperationConfig()
            {
                Limit = 2, // 2 items/page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
        {
          "Message",
          "ReplyDateTime",
          "PostedBy",
        },
                ConsistentRead = true,
                Filter = filter,
            };

            Search search = table.Query(config);

            do
            {
                var documentList = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesPostedWithinTimePeriod: printing
replies posted within dates: {0} and {1} ............", startDate, endDate);

                foreach (var document in documentList)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Perform a query for replies made in the last 15 days using a DynamoDB
        /// QueryOperationConfig object.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadName">The bane of the thread that we are searching
        /// for replies.</param>
```

```
        public static async Task FindRepliesInLast15DaysWithConfig(
          Table table,
          string forumName,
          string threadName)
        {
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
            var filter = new QueryFilter("Id", QueryOperator.Equal, forumName +
"#" + threadName);
            filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);

            var config = new QueryOperationConfig()
            {
                Filter = filter,

                // Optional parameters.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "Message",
                  "ReplyDateTime",
                  "PostedBy",
                },
                ConsistentRead = true,
            };

            Search search = table.Query(config);

            do
            {
                var documentSet = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesInLast15DaysWithConfig:
printing ............");

                foreach (var document in documentSet)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Displays the contents of the passed DynamoDB document on the console.
```

```
        /// </summary>
        /// <param name="document">A DynamoDB document to display.</param>
        public static void PrintDocument(Document document)
        {
            Console.WriteLine();
            foreach (var attribute in document.GetAttributeNames())
            {
                string stringValue = null;
                var value = document[attribute];

                if (value is Primitive)
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                        select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}");
            }
        }
    }
```

Usar um modelo de persistência de objetos de alto nível para o DynamoDB usando um AWS SDK

O exemplo de código a seguir mostra como realizar operações de criação, leitura, atualização e exclusão (CRUD) e operações em lote usando um modelo de persistência de objetos para o DynamoDB e um AWS SDK.

Para obter mais informações, consulte Modelo de persistência de objetos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Realize operações CRUD usando um modelo de persistência de objetos de alto nível.

```
/// <summary>
/// Shows how to perform high-level CRUD operations on an Amazon DynamoDB
/// table.
/// </summary>
public class HighLevelItemCrud
{
    public static async Task Main()
    {
        var client = new AmazonDynamoDBClient();
        DynamoDBContext context = new DynamoDBContext(client);
        await PerformCRUDOperations(context);
    }

    public static async Task PerformCRUDOperations(IDynamoDBContext context)
    {
        int bookId = 1001; // Some unique value.
        Book myBook = new Book
        {
            Id = bookId,
            Title = "object persistence-AWS SDK for.NET SDK-Book 1001",
            Isbn = "111-1111111001",
            BookAuthors = new List<string> { "Author 1", "Author 2" },
        };

        // Save the book to the ProductCatalog table.
        await context.SaveAsync(myBook);

        // Retrieve the book from the ProductCatalog table.
        Book bookRetrieved = await context.LoadAsync<Book>(bookId);
```

```
            // Update some properties.
            bookRetrieved.Isbn = "222-2222221001";

            // Update existing authors list with the following values.
            bookRetrieved.BookAuthors = new List<string> { " Author 1", "Author
x" };
            await context.SaveAsync(bookRetrieved);

            // Retrieve the updated book. This time, add the optional
            // ConsistentRead parameter using DynamoDBContextConfig object.
            await context.LoadAsync<Book>(bookId, new DynamoDBContextConfig
            {
                ConsistentRead = true,
            });

            // Delete the book.
            await context.DeleteAsync<Book>(bookId);

            // Try to retrieve deleted book. It should return null.
            Book deletedBook = await context.LoadAsync<Book>(bookId, new
DynamoDBContextConfig
            {
                ConsistentRead = true,
            });

            if (deletedBook == null)
            {
                Console.WriteLine("Book is deleted");
            }
        }
    }
```

Realize operações de gravação em lote usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Performs high-level batch write operations to an Amazon DynamoDB table.
    /// This example was written using the AWS SDK for .NET version 3.7 and .NET
    /// Core 5.0.
    /// </summary>
```

```
    public class HighLevelBatchWriteItem
    {
        public static async Task SingleTableBatchWrite(IDynamoDBContext context)
        {
            Book book1 = new Book
            {
                Id = 902,
                InPublication = true,
                Isbn = "902-11-11-1111",
                PageCount = "100",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book3 in batch write",
            };

            Book book2 = new Book
            {
                Id = 903,
                InPublication = true,
                Isbn = "903-11-11-1111",
                PageCount = "200",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book4 in batch write",
            };

            var bookBatch = context.CreateBatchWrite<Book>();
            bookBatch.AddPutItems(new List<Book> { book1, book2 });

            Console.WriteLine("Adding two books to ProductCatalog table.");
            await bookBatch.ExecuteAsync();
        }

        public static async Task MultiTableBatchWrite(IDynamoDBContext context)
        {
            // New Forum item.
            Forum newForum = new Forum
            {
                Name = "Test BatchWrite Forum",
                Threads = 0,
            };
            var forumBatch = context.CreateBatchWrite<Forum>();
            forumBatch.AddPutItem(newForum);
```

```
            // New Thread item.
            Thread newThread = new Thread
            {
                ForumName = "S3 forum",
                Subject = "My sample question",
                KeywordTags = new List<string> { "S3", "Bucket" },
                Message = "Message text",
            };

            DynamoDBOperationConfig config = new DynamoDBOperationConfig();
            config.SkipVersionCheck = true;
            var threadBatch = context.CreateBatchWrite<Thread>(config);
            threadBatch.AddPutItem(newThread);
            threadBatch.AddDeleteKey("some partition key value", "some sort key
value");

            var superBatch = new MultiTableBatchWrite(forumBatch, threadBatch);

            Console.WriteLine("Performing batch write in
MultiTableBatchWrite().");
            await superBatch.ExecuteAsync();
        }

        public static async Task Main()
        {
            AmazonDynamoDBClient client = new AmazonDynamoDBClient();
            DynamoDBContext context = new DynamoDBContext(client);

            await SingleTableBatchWrite(context);
            await MultiTableBatchWrite(context);
        }
    }
```

Mapeie dados arbitrários em uma tabela usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Shows how to map arbitrary data to an Amazon DynamoDB table.
    /// </summary>
    public class HighLevelMappingArbitraryData
```

```
    {
        /// <summary>
        /// Creates a book, adds it to the DynamoDB ProductCatalog table,
retrieves
        /// the new book from the table, updates the dimensions and writes the
        /// changed item back to the table.
        /// </summary>
        /// <param name="context">The DynamoDB context object used to write and
        /// read data from the table.</param>
        public static async Task AddRetrieveUpdateBook(IDynamoDBContext context)
        {
            // Create a book.
            DimensionType myBookDimensions = new DimensionType()
            {
                Length = 8M,
                Height = 11M,
                Thickness = 0.5M,
            };

            Book myBook = new Book
            {
                Id = 501,
                Title = "AWS SDK for .NET Object Persistence Model Handling
Arbitrary Data",
                Isbn = "999-9999999999",
                BookAuthors = new List<string> { "Author 1", "Author 2" },
                Dimensions = myBookDimensions,
            };

            // Add the book to the DynamoDB table ProductCatalog.
            await context.SaveAsync(myBook);

            // Retrieve the book.
            Book bookRetrieved = await context.LoadAsync<Book>(501);

            // Update the book dimensions property.
            bookRetrieved.Dimensions.Height += 1;
            bookRetrieved.Dimensions.Length += 1;
            bookRetrieved.Dimensions.Thickness += 0.2M;

            // Write the changed item to the table.
            await context.SaveAsync(bookRetrieved);
        }
```

```
        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();
            DynamoDBContext context = new DynamoDBContext(client);
            await AddRetrieveUpdateBook(context);
        }
    }
```

Consulte e verifique uma tabela usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Shows how to perform high-level query and scan operations to Amazon
    /// DynamoDB tables.
    /// </summary>
    public class HighLevelQueryAndScan
    {
        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();

            DynamoDBContext context = new DynamoDBContext(client);

            // Get an item.
            await GetBook(context, 101);

            // Sample forum and thread to test queries.
            string forumName = "Amazon DynamoDB";
            string threadSubject = "DynamoDB Thread 1";

            // Sample queries.
            await FindRepliesInLast15Days(context, forumName, threadSubject);
            await FindRepliesPostedWithinTimePeriod(context, forumName,
 threadSubject);

            // Scan table.
            await FindProductsPricedLessThanZero(context);
        }

        public static async Task GetBook(IDynamoDBContext context, int productId)
        {
```

```
            Book bookItem = await context.LoadAsync<Book>(productId);

            Console.WriteLine("\nGetBook: Printing result.....");
            Console.WriteLine($"Title: {bookItem.Title} \n ISBN:{bookItem.Isbn}
\n No. of pages: {bookItem.PageCount}");
        }

        /// <summary>
        /// Queries a DynamoDB table to find replies posted within the last 15
days.
        /// </summary>
        /// <param name="context">The DynamoDB context used to perform the
query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadSubject">The thread object containing the query
parameters.</param>
        public static async Task FindRepliesInLast15Days(
          IDynamoDBContext context,
          string forumName,
          string threadSubject)
        {
            string replyId = $"{forumName} #{threadSubject}";
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);

            List<object> times = new List<object>();
            times.Add(twoWeeksAgoDate);

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc = new ScanCondition("PostedBy", ScanOperator.GreaterThan,
times.ToArray());
            scs.Add(sc);

            var cfg = new DynamoDBOperationConfig
            {
                QueryFilter = scs,
            };

            AsyncSearch<Reply> response = context.QueryAsync<Reply>(replyId,
cfg);
            IEnumerable<Reply> latestReplies = await
response.GetRemainingAsync();

            Console.WriteLine("\nReplies in last 15 days:");
```

```
            foreach (Reply r in latestReplies)
            {

Console.WriteLine($"{r.Id}\t{r.PostedBy}\t{r.Message}\t{r.ReplyDateTime}");
            }
        }

        /// <summary>
        /// Queries for replies posted within a specific time period.
        /// </summary>
        /// <param name="context">The DynamoDB context used to perform the
query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadSubject">Information about the subject that we're
        /// interested in.</param>
        public static async Task FindRepliesPostedWithinTimePeriod(
          IDynamoDBContext context,
          string forumName,
          string threadSubject)
        {
            string forumId = forumName + "#" + threadSubject;
            Console.WriteLine("\nReplies posted within time period:");

            DateTime startDate = DateTime.UtcNow - TimeSpan.FromDays(30);
            DateTime endDate = DateTime.UtcNow - TimeSpan.FromDays(1);

            List<object> times = new List<object>();
            times.Add(startDate);
            times.Add(endDate);

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc = new ScanCondition("LastPostedBy", ScanOperator.Between,
times.ToArray());
            scs.Add(sc);

            var cfg = new DynamoDBOperationConfig
            {
                QueryFilter = scs,
            };

            AsyncSearch<Reply> response = context.QueryAsync<Reply>(forumId,
cfg);
```

```
            IEnumerable<Reply> repliesInAPeriod = await
response.GetRemainingAsync();

            foreach (Reply r in repliesInAPeriod)
            {

Console.WriteLine("{r.Id}\t{r.PostedBy}\t{r.Message}\t{r.ReplyDateTime}");
            }
        }

        /// <summary>
        /// Queries the DynamoDB ProductCatalog table for products costing less
        /// than zero.
        /// </summary>
        /// <param name="context">The DynamoDB context object used to perform the
        /// query.</param>
        public static async Task FindProductsPricedLessThanZero(IDynamoDBContext
context)
        {
            int price = 0;

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc1 = new ScanCondition("Price", ScanOperator.LessThan, price);
            var sc2 = new ScanCondition("ProductCategory", ScanOperator.Equal,
"Book");
            scs.Add(sc1);
            scs.Add(sc2);

            AsyncSearch<Book> response = context.ScanAsync<Book>(scs);

            IEnumerable<Book> itemsWithWrongPrice = await
response.GetRemainingAsync();

            Console.WriteLine("\nFindProductsPricedLessThanZero: Printing
result.....");

            foreach (Book r in itemsWithWrongPrice)
            {
                Console.WriteLine($"{r.Id}\t{r.Title}\t{r.Price}\t{r.Isbn}");
            }
        }
    }
```

Exemplos do DynamoDB entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon DynamoDB com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação para enviar dados para uma tabela do DynamoDB
- Criar uma API REST do API Gateway para monitorar dados da COVID-19
- Criar uma aplicação de mensageiro com o Step Functions
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Criar uma aplicação de chat websocket com o API Gateway
- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Chamar uma função do Lambda em um navegador
- Salvar o EXIF e outras informações de imagem usando um AWS SDK
- Usar o API Gateway para invocar uma função do Lambda
- Usar Step Functions para invocar funções do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma aplicação para enviar dados para uma tabela do DynamoDB

Os exemplos de código a seguir mostram como criar uma aplicação que envia dados para uma tabela do Amazon DynamoDB e notifica você quando um usuário atualiza a tabela.

Java

SDK para Java 2.x

Mostra como criar uma aplicação Web dinâmica que envia dados usando a API Java do Amazon DynamoDB e envia uma mensagem de texto usando a API Java do Amazon Simple Notification Service.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Este exemplo mostra como criar uma aplicação que permite que os usuários enviem dados para uma tabela do Amazon DynamoDB e enviem uma mensagem de texto ao administrador usando o Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como criar uma aplicação Android nativa que envia dados usando a API Kotlin do Amazon DynamoDB e envia uma mensagem de texto usando a API Kotlin do Amazon SNS.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Criar uma API REST do API Gateway para monitorar dados da COVID-19

O exemplo de código a seguir mostra como criar uma API REST que simula um sistema para monitorar casos diários de COVID-19 nos Estados Unidos, usando dados fictícios.

Python

SDK para Python (Boto3)

Mostra como usar o AWS Chalice com o AWS SDK for Python (Boto3) para criar uma API REST sem servidor que usa o Amazon API Gateway, o AWS Lambda e o Amazon DynamoDB. O exemplo de código a seguir simula um sistema que monitora casos diários de COVID-19 nos Estados Unidos, usando dados fictícios. Aprenda como:

- Usar o AWS Chalice para definir rotas nas funções do Lambda que são chamadas para lidar com solicitações REST provenientes do API Gateway.
- Usar as funções do Lambda para recuperar e armazenar dados em uma tabela do DynamoDB para atender a solicitações REST.
- Definir recursos de função de segurança e estrutura de tabela em um modelo do AWS CloudFormation.
- Use AWS Chalice e CloudFormation para empacotar e implantar todos os recursos necessários.
- Use CloudFormation para limpar todos os recursos criados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- AWS CloudFormation

- DynamoDB
- Lambda

Criar uma aplicação de mensageiro com o Step Functions

O exemplo de código a seguir mostra como criar uma aplicação de mensageiro do AWS Step Functions que recupera registros de mensagens de uma tabela de banco de dados.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o AWS Step Functions para criar uma aplicação de mensageiro que recupere registros de mensagens de uma tabela do Amazon DynamoDB e os envia com o Amazon Simple Queue Service (Amazon SQS). A máquina de estado se integra a uma função do AWS Lambda para verificar o banco de dados em busca de mensagens não enviadas.

- Crie uma máquina de estado que recupere e atualize registros de mensagens de uma tabela do Amazon DynamoDB.
- Atualize a definição de máquina de estado para enviar mensagens ao Amazon Simple Queue Service (Amazon SQS).
- Inicie e interrompa execuções da máquina de estado.
- Conecte-se ao Lambda, ao DynamoDB e ao Amazon SQS por meio de uma máquina de estado usando integrações de serviço.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB

- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação Web para monitorar dados do DynamoDB

O exemplo de código a seguir mostra como criar uma aplicação Web que monitora itens de trabalho em uma tabela do Amazon DynamoDB e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Java

SDK para Java 2.x

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para construir um serviço REST que monitora itens de trabalho no Amazon DynamoDB e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa a estrutura web Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST de Flask que se integre com Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em uma tabela do DynamoDB.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo no Repositório de exemplos de AWS código em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Criar uma aplicação de chat websocket com o API Gateway

O exemplo de código a seguir mostra como criar uma aplicação de chat que é atendido por uma API de Websocket criada no Amazon API Gateway.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon API Gateway V2 para criar uma API de Websocket que se integra ao AWS Lambda e ao Amazon DynamoDB.

- Crie uma API de Websocket atendida pelo API Gateway.
- Defina um manipulador do Lambda que armazena conexões no DynamoDB e publica mensagens para outros participantes do chat.
- Conecte-se à aplicação de chat websocket e envie mensagens com o pacote Websockets.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar equipamentos de proteção individual (EPI) em imagens.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda que detecta imagens com equipamento de proteção individual.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar equipamentos de proteção individual (EPI) em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação salva os resultados em uma tabela do Amazon DynamoDB e envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Atualizar uma tabela do DynamoDB com resultados.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

Chamar uma função do Lambda em um navegador

O exemplo de código a seguir mostra como chamar uma função do AWS Lambda em um navegador.

JavaScript

SDK para JavaScript (v2)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

SDK para JavaScript (v3)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário. Essa aplicação usa o AWS SDK for JavaScript v3.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

Salvar o EXIF e outras informações de imagem usando um AWS SDK

O código de exemplo a seguir mostra como:

- Obter informações de EXIF de um arquivo JPG, JPEG ou PNG.
- Faça upload do arquivo de imagem para um bucket do Amazon S3.
- Use o Amazon Rekognition para identificar os três principais atributos (rótulos) no arquivo.
- Adicione as informações de EXIF e rótulo a uma tabela do Amazon DynamoDB na região.

Rust

SDK for Rust

Obtenha informações de EXIF de um arquivo JPG, JPEG ou PNG, faça upload do arquivo de imagem para um bucket do Amazon S3, use o Amazon Rekognition para identificar os três principais atributos (rótulos no Amazon Rekognition) no arquivo e adicione as informações de EXIF e de rótulo a uma tabela do Amazon DynamoDB na região.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3

Usar o API Gateway para invocar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma função do AWS Lambda invocada pelo Amazon API Gateway que envia mensagens de texto de aniversário.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar uma AWS Lambda função usando a API de tempo de JavaScript execução do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Usar Step Functions para invocar funções do Lambda

Os exemplos de código a seguir mostram como criar um máquina de estado do AWS Step Functions que invoca a funções do AWS Lambda em sequência.

Java

SDK para Java 2.x

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for Java 2.x. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

JavaScript

SDK para JavaScript (v3)

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for JavaScript. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

O Lambda é um serviço computacional que permite executar código sem provisionar ou gerenciar servidores. O Step Functions é um serviço de orquestração sem servidor que

permite combinar funções do Lambda e outros serviços da AWS para criar aplicações essenciais aos negócios.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Usar eventos programados para chamar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma AWS Lambda função invocada por um evento EventBridge agendado pela Amazon.

Java

SDK para Java 2.x

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função do Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- EventBridge
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função Lambda usando a API de tempo de execução do JavaScript Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

Exemplos de código para o Amazon EBS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Block Store (Amazon EBS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Amazon EBS – Mais informações sobre o Amazon EBS.
- Referência da API do Amazon EBS – Detalhes sobre todas as ações disponíveis do Amazon EBS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon EBS usando SDKs da AWS
  - Crie um snapshot do Amazon EBS usando um SDK da AWS
  - Sele e conclua o snapshot do Amazon EBS usando um SDK da AWS
  - Grave um bloco de dados em um snapshot do Amazon EBS usando um SDK da AWS

Ações para o Amazon EBS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Block Store (Amazon EBS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um snapshot do Amazon EBS usando um SDK da AWS
- Sele e conclua o snapshot do Amazon EBS usando um SDK da AWS
- Grave um bloco de dados em um snapshot do Amazon EBS usando um SDK da AWS

Crie um snapshot do Amazon EBS usando um SDK da AWS

O exemplo de código a seguir mostra como criar um snapshot do Amazon EBS.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn start(client: &Client, description: &str) -> Result<String, Error> {
    let snapshot = client
        .start_snapshot()
        .description(description)
        .encrypted(false)
        .volume_size(1)
        .send()
        .await?;

    Ok(snapshot.snapshot_id.unwrap())
}
```

- Para obter detalhes da API, consulte a StartSnapshotreferência da API AWS SDK for Rust.

Sele e conclua o snapshot do Amazon EBS usando um SDK da AWS

O exemplo de código a seguir mostra como selar e completar um snapshot do Amazon EBS.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn finish(client: &Client, id: &str) -> Result<(), Error> {
```

```
    client
        .complete_snapshot()
        .changed_blocks_count(2)
        .snapshot_id(id)
        .send()
        .await?;

    println!("Snapshot ID {}", id);
    println!("The state is 'completed' when all of the modified blocks have been
 transferred to Amazon S3.");
    println!("Use the get-snapshot-state code example to get the state of the
 snapshot.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CompleteSnapshotreferência da API AWS SDK for Rust.

Grave um bloco de dados em um snapshot do Amazon EBS usando um SDK da AWS

O exemplo de código a seguir mostra como gravar um bloco de dados em um snapshot do Amazon EBS.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_block(
    client: &Client,
    id: &str,
    idx: usize,
    block: Vec<u8>,
    checksum: &str,
```

```
) -> Result<(), Error> {
    client
        .put_snapshot_block()
        .snapshot_id(id)
        .block_index(idx as i32)
        .block_data(ByteStream::from(block))
        .checksum(checksum)
        .checksum_algorithm(ChecksumAlgorithm::ChecksumAlgorithmSha256)
        .data_length(EBS_BLOCK_SIZE as i32)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutSnapshotBlockreferência da API AWS SDK for Rust.

Exemplos de código para o Amazon EC2 usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Elastic Compute Cloud (Amazon EC2) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Amazon EC2 – Mais informações sobre o Amazon EC2.
- Referência da API do Amazon EC2 – Detalhes sobre todas as ações disponíveis do Amazon EC2.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace EC2Actions;

public class HelloEc2
{
    /// <summary>
    /// HelloEc2 lists the existing security groups for the default users.
    /// </summary>
    /// <param name="args">Command line arguments</param>
    /// <returns>A Task object.</returns>
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Elastic Compute Cloud (Amazon
 EC2).
        using var host =
 Microsoft.Extensions.Hosting.Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonEC2>()
                .AddTransient<EC2Wrapper>()
            )
            .Build();

        // Now the client is available for injection.
        var ec2Client = host.Services.GetRequiredService<IAmazonEC2>();

        var request = new DescribeSecurityGroupsRequest
        {
```

```
            MaxResults = 10,
        };


        // Retrieve information about up to 10 Amazon EC2 security groups.
        var response = await ec2Client.DescribeSecurityGroupsAsync(request);

        // Now print the security groups returned by the call to
        // DescribeSecurityGroupsAsync.
        Console.WriteLine("Security Groups:");
        response.SecurityGroups.ForEach(group =>
        {
            Console.WriteLine($"Security group: {group.GroupName} ID:
 {group.GroupId}");
        });
    }
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS ec2)

# Set this project's name.
project("hello_ec2")
```

```
# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_ec2.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo fonte hello_ec2.cpp.

```
#include <aws/core/Aws.h>
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeInstancesRequest.h>
```

```
#include <iomanip>
#include <iostream>

/*
 *  A "Hello EC2" starter application which initializes an Amazon Elastic Compute
 Cloud (Amazon EC2) client and describes
 *  the Amazon EC2 instances.
 *
 *  main function
 *
 *  Usage: 'hello_ec2'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::EC2::EC2Client ec2Client(clientConfig);
        Aws::EC2::Model::DescribeInstancesRequest request;
        bool header = false;
        bool done = false;
        while (!done) {
            auto outcome = ec2Client.DescribeInstances(request);
            if (outcome.IsSuccess()) {
                if (!header) {
                    std::cout << std::left <<
                              std::setw(48) << "Name" <<
                              std::setw(20) << "ID" <<
                              std::setw(25) << "Ami" <<
                              std::setw(15) << "Type" <<
                              std::setw(15) << "State" <<
                              std::setw(15) << "Monitoring" << std::endl;
                    header = true;
                }

                const std::vector<Aws::EC2::Model::Reservation> &reservations =
```

```
                        outcome.GetResult().GetReservations();

                for (const auto &reservation: reservations) {
                    const std::vector<Aws::EC2::Model::Instance> &instances =
                            reservation.GetInstances();
                    for (const auto &instance: instances) {
                        Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                        instance.GetState().GetName());

                        Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                        instance.GetInstanceType());

                        Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                        instance.GetMonitoring().GetState());
                        Aws::String name = "Unknown";

                        const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                        auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                     [](const
Aws::EC2::Model::Tag &tag) {
                                                         return tag.GetKey() ==
"Name";
                                                     });
                        if (nameIter != tags.cend()) {
                            name = nameIter->GetValue();
                        }
                        std::cout <<
                                  std::setw(48) << name <<
                                  std::setw(20) << instance.GetInstanceId() <<
                                  std::setw(25) << instance.GetImageId() <<
                                  std::setw(15) << typeString <<
                                  std::setw(15) << instanceStateString <<
                                  std::setw(15) << monitorString << std::endl;
                    }
                }

                if (!outcome.GetResult().GetNextToken().empty()) {
```

```
                    request.SetNextToken(outcome.GetResult().GetNextToken());
                } else {
                    done = true;
                }
            } else {
                std::cerr << "Failed to describe EC2 instances:" <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DescribeSecurityGroupsRequest;
import software.amazon.awssdk.services.ec2.model.DescribeSecurityGroupsResponse;
import software.amazon.awssdk.services.ec2.model.SecurityGroup;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeSecurityGroups {
    public static void main(String[] args) {
        final String usage = "To run this example, supply a group id\n" +
                "Ex: DescribeSecurityGroups <groupId>\n";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        describeEC2SecurityGroups(ec2, groupId);
        ec2.close();
    }

    public static void describeEC2SecurityGroups(Ec2Client ec2, String groupId) {
        try {
            DescribeSecurityGroupsRequest request =
 DescribeSecurityGroupsRequest.builder()
                    .groupIds(groupId)
                    .build();

            DescribeSecurityGroupsResponse response =
 ec2.describeSecurityGroups(request);
            for (SecurityGroup group : response.securityGroups()) {
                System.out.printf(
                        "Found Security Group with id %s, " +
                                "vpc id %s " +
                                "and description %s",
                        group.groupId(),
                        group.vpcId(),
                        group.description());
```

```
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSecurityGroupsCommand } from "@aws-sdk/client-ec2";

import { client } from "./libs/client.js";

// Call DescribeSecurityGroups and display the result.
export const main = async () => {
  try {
    const { SecurityGroups } = await client.send(
      new DescribeSecurityGroupsCommand({}),
    );

    const securityGroupList = SecurityGroups.slice(0, 9)
      .map((sg) => ` • ${sg.GroupId}: ${sg.GroupName}`)
      .join("\n");

    console.log(
      "Hello, Amazon EC2! Let's list up to 10 of your security groups:",
    );
```

```
    console.log(securityGroupList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2SecurityGroups(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->

        val response = ec2.describeSecurityGroups(request)
        response.securityGroups?.forEach { group ->
            println("Found Security Group with id ${group.groupId}, vpc id
 ${group.vpcId} and description ${group.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_ec2(ec2_resource):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Elastic Compute Cloud
    (Amazon EC2) resource and list the security groups in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param ec2_resource: A Boto3 EC2 ServiceResource object. This object is a
 high-level
                         resource that wraps the low-level EC2 service API.
    """
    print("Hello, Amazon EC2! Let's list up to 10 of your security groups:")
    for sg in ec2_resource.security_groups.limit(10):
        print(f"\t{sg.id}: {sg.group_name}")


if __name__ == "__main__":
    hello_ec2(boto3.resource("ec2"))
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações para o Amazon EC2 usando AWS SDKs
  - Adicionar tags a recursos do Amazon EC2 usando um AWS SDK
  - Alocar um endereço IP elástico ao Amazon EC2 usando um AWS SDK

- Associar um endereço IP elástico a uma instância do Amazon EC2 usando um AWS SDK
- Criar uma Amazon Virtual Private Cloud (Amazon VPC)
- Crie um modelo de execução do Amazon EC2 usando um SDK AWS
- Criar uma tabela de rotas na Amazon Virtual Private Cloud (Amazon VPC) e associá-la a uma sub-rede
- Criar um grupo de segurança do Amazon EC2 usando um AWS SDK
- Criar um par de chaves de segurança do Amazon EC2 usando um AWS SDK
- Criar e marcar uma sub-rede na Amazon Virtual Private Cloud (Amazon VPC)
- Criar e executar uma instância de banco de dados do Amazon EC2 usando um AWS SDK
- Exclua um modelo de execução do Amazon EC2 usando um SDK AWS
- Excluir um grupo de segurança do Amazon EC2 usando um AWS SDK
- Excluir um par de chaves de segurança do Amazon EC2 usando um AWS SDK
- Excluir o snapshot do Amazon EBS usando um AWS SDK
- Descrever as zonas de disponibilidade da sua conta usando um AWS SDK
- Descreve as regiões da sua conta usando um AWS SDK
- Descreve o status das instâncias do Amazon EC2 usando um AWS SDK
- Descrever instâncias do Amazon EC2 usando um AWS SDK
- Descrever um ou mais snapshots do Amazon EBS usando um AWS SDK
- Desabilitar o monitoramento detalhado de uma instância do Amazon EC2 usando um AWS SDK
- Desassociar um endereço IP elástico de uma instância do Amazon EC2 usando um AWS SDK
- Habilita o monitoramento de uma instância do Amazon EC2 em execução usando um AWS SDK
- Obter dados sobre imagens de máquina da Amazon usando um AWS SDK
- Obter dados sobre um grupo de segurança do Amazon EC2 usando um AWS SDK
- Obter dados sobre os tipos de instâncias do Amazon EC2 usando um AWS SDK
- Obtenha dados sobre o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS
- Obter detalhes sobre endereços IP elásticos usando um AWS SDK
- Obtenha a VPC padrão usando um SDK AWS
- Obtenha sub-redes padrão para uma VPC usando um SDK AWS
- Listar pares de chaves de segurança do Amazon EC2 usando um AWS SDK
- Reinicializar uma instância do Amazon EC2 usando um AWS SDK

- Liberar um endereço IP elástico usando um AWS SDK
- Subtitua o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS
- Definir regras de entrada para um grupo de segurança do Amazon EC2 usando um AWS SDK
- Iniciar uma instância do Amazon EC2 usando um AWS SDK
- Interromper uma instância do Amazon EC2 usando um AWS SDK
- Encerrar uma instância do Amazon EC2 usando um AWS SDK
- Cenários do Amazon EC2 com AWS SDKs
  - Criar e gerenciar um serviço resiliente usando um AWS SDK
  - Começar a usar instâncias do Amazon EC2 com um AWS SDK

Ações para o Amazon EC2 usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Elastic Compute Cloud (Amazon EC2) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon EC2 com AWS SDKs.

Exemplos

- Adicionar tags a recursos do Amazon EC2 usando um AWS SDK
- Alocar um endereço IP elástico ao Amazon EC2 usando um AWS SDK
- Associar um endereço IP elástico a uma instância do Amazon EC2 usando um AWS SDK
- Criar uma Amazon Virtual Private Cloud (Amazon VPC)
- Crie um modelo de execução do Amazon EC2 usando um SDK AWS
- Criar uma tabela de rotas na Amazon Virtual Private Cloud (Amazon VPC) e associá-la a uma sub-rede
- Criar um grupo de segurança do Amazon EC2 usando um AWS SDK
- Criar um par de chaves de segurança do Amazon EC2 usando um AWS SDK
- Criar e marcar uma sub-rede na Amazon Virtual Private Cloud (Amazon VPC)
- Criar e executar uma instância de banco de dados do Amazon EC2 usando um AWS SDK
- Exclua um modelo de execução do Amazon EC2 usando um SDK AWS
- Excluir um grupo de segurança do Amazon EC2 usando um AWS SDK

- Excluir um par de chaves de segurança do Amazon EC2 usando um AWS SDK
- Excluir o snapshot do Amazon EBS usando um AWS SDK
- Descrever as zonas de disponibilidade da sua conta usando um AWS SDK
- Descreve as regiões da sua conta usando um AWS SDK
- Descreve o status das instâncias do Amazon EC2 usando um AWS SDK
- Descrever instâncias do Amazon EC2 usando um AWS SDK
- Descrever um ou mais snapshots do Amazon EBS usando um AWS SDK
- Desabilitar o monitoramento detalhado de uma instância do Amazon EC2 usando um AWS SDK
- Desassociar um endereço IP elástico de uma instância do Amazon EC2 usando um AWS SDK
- Habilita o monitoramento de uma instância do Amazon EC2 em execução usando um AWS SDK
- Obter dados sobre imagens de máquina da Amazon usando um AWS SDK
- Obter dados sobre um grupo de segurança do Amazon EC2 usando um AWS SDK
- Obter dados sobre os tipos de instâncias do Amazon EC2 usando um AWS SDK
- Obtenha dados sobre o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS
- Obter detalhes sobre endereços IP elásticos usando um AWS SDK
- Obtenha a VPC padrão usando um SDK AWS
- Obtenha sub-redes padrão para uma VPC usando um SDK AWS
- Listar pares de chaves de segurança do Amazon EC2 usando um AWS SDK
- Reinicializar uma instância do Amazon EC2 usando um AWS SDK
- Liberar um endereço IP elástico usando um AWS SDK
- Subtitua o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS
- Definir regras de entrada para um grupo de segurança do Amazon EC2 usando um AWS SDK
- Iniciar uma instância do Amazon EC2 usando um AWS SDK
- Interromper uma instância do Amazon EC2 usando um AWS SDK
- Encerrar uma instância do Amazon EC2 usando um AWS SDK

Adicionar tags a recursos do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar tags aos recursos do Amazon EC2.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::Tag nameTag;
nameTag.SetKey("Name");
nameTag.SetValue(instanceName);

Aws::EC2::Model::CreateTagsRequest createRequest;
createRequest.AddResources(instanceID);
createRequest.AddTags(nameTag);

Aws::EC2::Model::CreateTagsOutcome createOutcome = ec2Client.CreateTags(
        createRequest);
if (!createOutcome.IsSuccess()) {
    std::cerr << "Failed to tag ec2 instance " << instanceID <<
              " with name " << instanceName << ":" <<
              createOutcome.GetError().GetMessage() << std::endl;
    return false;
}
```

- Para obter detalhes da API, consulte CreateTagsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para adicionar uma tag a um recurso

O exemplo `create-tags` a seguir adiciona a tag `Stack=production` à imagem especificada ou substitui uma tag existente para a AMI na qual a chave de tag é `Stack`.

```
aws ec2 create-tags \
    --resources ami-1234567890abcdef0 --tags Key=Stack,Value=production
```

Para adicionar tags a vários recursos

O exemplo `create-tags` a seguir adiciona (ou substitui) duas tags para uma AMI e uma instância. Uma das tags tem uma chave (`webserver`), mas nenhum valor (o valor é definido como uma string vazia). A outra tag tem uma chave (`stack`) e um valor (`Production`).

```
aws ec2 create-tags \
    --resources ami-1a2b3c4d i-1234567890abcdef0 \
    --tags Key=webserver,Value=   Key=stack,Value=Production
```

Para adicionar tags contendo caracteres especiais

O exemplo `create-tags` a seguir adiciona a tag `[Group]=test` para uma instância. Os colchetes ([e]) são caracteres especiais e devem ser recuados. Os exemplos a seguir também usam o caractere de continuação de linha apropriado para cada ambiente.

Se você estiver usando o Windows, coloque o elemento com caracteres especiais entre aspas duplas (“) e preceda cada caractere de aspas duplas com uma barra invertida (\) da seguinte maneira:

```
aws ec2 create-tags ^
    --resources i-1234567890abcdef0 ^
    --tags Key=\"[Group]\",Value=test
```

Se você estiver usando o Windows PowerShell, elemente o valor que tem caracteres especiais com aspas duplas (“), preceda cada caractere de aspas duplas com uma barra invertida (\) e, em seguida, coloque toda a estrutura de chave e valor entre aspas simples (') da seguinte forma:

```
aws ec2 create-tags `
    --resources i-1234567890abcdef0 `
    --tags 'Key=\"[Group]\",Value=test'
```

Se você estiver usando Linux ou OS X, coloque o elemento com caracteres especiais entre aspas duplas (“) e coloque toda a estrutura de chave e valor entre aspas simples (‘) da seguinte maneira:

```
aws ec2 create-tags \
    --resources i-1234567890abcdef0 \
    --tags 'Key="[Group]",Value=test'
```

- Para obter detalhes da API, consulte CreateTagsem Referência de AWS CLI Comandos.

Alocar um endereço IP elástico ao Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como alocar um endereço IP elástico ao Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Allocate an Elastic IP address.
    /// </summary>
    /// <returns>The allocation Id of the allocated address.</returns>
    public async Task<string> AllocateAddress()
    {
        var request = new AllocateAddressRequest();

        var response = await _amazonEC2.AllocateAddressAsync(request);
        return response.AllocationId;
    }
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::AllocateAddressRequest request;
request.SetDomain(Aws::EC2::Model::DomainType::vpc);

const Aws::EC2::Model::AllocateAddressOutcome outcome =
        ec2Client.AllocateAddress(request);
if (!outcome.IsSuccess()) {
    std::cerr << "Failed to allocate Elastic IP address:" <<
              outcome.GetError().GetMessage() << std::endl;
    return false;
}

allocationId = outcome.GetResult().GetAllocationId();
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: alocar um endereço IP elástico do conjunto de endereços da Amazon

O exemplo `allocate-address` a seguir aloca um endereço IP elástico. O Amazon EC2 seleciona o endereço do conjunto de endereços da Amazon.

```
aws ec2 allocate-address
```

Saída:

```
{
    "PublicIp": "70.224.234.241",
    "AllocationId": "eipalloc-01435ba59eEXAMPLE",
    "PublicIpv4Pool": "amazon",
    "NetworkBorderGroup": "us-west-2",
    "Domain": "vpc"
}
```

Para obter mais informações, consulte Endereços IP elásticos no Guia do usuário do Amazon EC2.

Exemplo 2: alocar um endereço IP elástico e associá-lo a um grupo de borda de rede

O exemplo `allocate-address` a seguir aloca um endereço IP elástico e o associa ao grupo de borda de rede especificado.

```
aws ec2 allocate-address \
    --network-border-group us-west-2-lax-1
```

Saída:

```
{
    "PublicIp": "70.224.234.241",
    "AllocationId": "eipalloc-e03dd489ceEXAMPLE",
    "PublicIpv4Pool": "amazon",
    "NetworkBorderGroup": "us-west-2-lax-1",
    "Domain": "vpc"
}
```

Para obter mais informações, consulte Endereços IP elásticos no Guia do usuário do Amazon EC2.

Exemplo 3: alocar um endereço IP elástico de um conjunto de endereços de sua propriedade

O exemplo `allocate-address` a seguir aloca um endereço IP elástico de um conjunto de endereços que você trouxe para a conta da Amazon Web Services. O Amazon EC2 seleciona o endereço do conjunto de endereços.

```
aws ec2 allocate-address \
    --public-ipv4-pool ipv4pool-ec2-1234567890abcdef0
```

Saída:

```
{
    "AllocationId": "eipalloc-02463d08ceEXAMPLE",
    "NetworkBorderGroup": "us-west-2",
    "CustomerOwnedIp": "18.218.95.81",
    "CustomerOwnedIpv4Pool": "ipv4pool-ec2-1234567890abcdef0",
    "Domain": "vpc"
    "NetworkBorderGroup": "us-west-2",
}
```

Para obter mais informações, consulte Endereços IP elásticos no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte AllocateAddressem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.AllocateAddressRequest;
import software.amazon.awssdk.services.ec2.model.DomainType;
import software.amazon.awssdk.services.ec2.model.AllocateAddressResponse;
import software.amazon.awssdk.services.ec2.model.AssociateAddressRequest;
import software.amazon.awssdk.services.ec2.model.AssociateAddressResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AllocateAddress {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <instanceId>

                Where:
                    instanceId - An instance id value that you can obtain from
 the AWS Console.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String instanceId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        System.out.println(getAllocateAddress(ec2, instanceId));
        ec2.close();
    }

    public static String getAllocateAddress(Ec2Client ec2, String instanceId) {
        try {
            AllocateAddressRequest allocateRequest =
 AllocateAddressRequest.builder()
                    .domain(DomainType.VPC)
                    .build();

            AllocateAddressResponse allocateResponse =
 ec2.allocateAddress(allocateRequest);
            String allocationId = allocateResponse.allocationId();
            AssociateAddressRequest associateRequest =
 AssociateAddressRequest.builder()
```

```
                    .instanceId(instanceId)
                    .allocationId(allocationId)
                    .build();

            AssociateAddressResponse associateResponse =
 ec2.associateAddress(associateRequest);
            return associateResponse.associationId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AllocateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new AllocateAddressCommand({});

  try {
    const { AllocationId, PublicIp } = await client.send(command);
    console.log("A new IP address has been allocated to your account:");
    console.log(`ID: ${AllocationId} Public IP: ${PublicIp}`);
```

```
    console.log(
      "You can view your IP addresses in the AWS Management Console for Amazon
 EC2. Look under Network & Security > Elastic IPs",
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAllocateAddress(instanceIdVal: String?): String? {
    val allocateRequest = AllocateAddressRequest {
        domain = DomainType.Vpc
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val allocateResponse = ec2.allocateAddress(allocateRequest)
        val allocationIdVal = allocateResponse.allocationId

        val request = AssociateAddressRequest {
            instanceId = instanceIdVal
            allocationId = allocationIdVal
        }

        val associateResponse = ec2.associateAddress(request)
        return associateResponse.associationId
    }
}
```

- Para obter detalhes da API, consulte a AllocateAddressreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def allocate(self):
        """
        Allocates an Elastic IP address that can be associated with an Amazon EC2
```

```
        instance. By using an Elastic IP address, you can keep the public IP
address
        constant even when you restart the associated instance.

        :return: The newly created Elastic IP object. By default, the address is
not
                 associated with any instance.
        """
        try:
            response =
self.ec2_resource.meta.client.allocate_address(Domain="vpc")
            self.elastic_ip =
self.ec2_resource.VpcAddress(response["AllocationId"])
        except ClientError as err:
            logger.error(
                "Couldn't allocate Elastic IP. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.elastic_ip
```

- Para obter detalhes da API, consulte a AllocateAddressReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates an Elastic IP address in Amazon Virtual Private Cloud (Amazon VPC).
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
```

```
# @return [String] The allocation ID corresponding to the Elastic IP address.
# @example
#   puts allocate_elastic_ip_address(Aws::EC2::Client.new(region: 'us-west-2'))
def allocate_elastic_ip_address(ec2_client)
  response = ec2_client.allocate_address(domain: "vpc")
  return response.allocation_id
rescue StandardError => e
  puts "Error allocating Elastic IP address: #{e.message}"
  return "Error"
end
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->allocateaddress( iv_domain = 'vpc' ).   " oo_result
 is returned for testing purposes. "
        MESSAGE 'Allocated an Elastic IP address.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a AllocateAddressreferência da API AWS SDK for SAP ABAP.

Associar um endereço IP elástico a uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como associar um endereço IP elástico a uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Associate an Elastic IP address to an EC2 instance.
    /// </summary>
    /// <param name="allocationId">The allocation Id of an Elastic IP address.</
param>
    /// <param name="instanceId">The instance Id of the EC2 instance to
    /// associate the address with.</param>
    /// <returns>The association Id that represents
    /// the association of the Elastic IP address with an instance.</returns>
    public async Task<string> AssociateAddress(string allocationId, string
 instanceId)
    {
        var request = new AssociateAddressRequest
        {
            AllocationId = allocationId,
            InstanceId = instanceId
        };

        var response = await _amazonEC2.AssociateAddressAsync(request);
        return response.AssociationId;
```

```
    }
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::AssociateAddressRequest associate_request;
associate_request.SetInstanceId(instanceId);
associate_request.SetAllocationId(allocationId);

const Aws::EC2::Model::AssociateAddressOutcome associate_outcome =
        ec2Client.AssociateAddress(associate_request);
if (!associate_outcome.IsSuccess()) {
    std::cerr << "Failed to associate Elastic IP address " << allocationId
              << " with instance " << instanceId << ":" <<
              associate_outcome.GetError().GetMessage() << std::endl;
    return false;
}

std::cout << "Successfully associated Elastic IP address " << allocationId
          << " with instance " << instanceId << std::endl;
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para associar endereços IP elásticos no EC2-Classic

Este exemplo associa um endereço IP elástico a uma instância no EC2-Classic. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 associate-address --instance-id i-07ffe74c7330ebf53 --public-ip
 198.51.100.0
```

Para associar um endereço IP elástico no EC2-VPC

Este exemplo associa um endereço IP elástico a uma instância em uma VPC.

Comando:

```
aws ec2 associate-address --instance-id i-0b263919b6498b123 --allocation-id
 eipalloc-64d5890a
```

Saída:

```
{
    "AssociationId": "eipassoc-2bebb745"
}
```

Este exemplo associa um endereço IP elástico a uma interface de rede.

Comando:

```
aws ec2 associate-address --allocation-id eipalloc-64d5890a --network-interface-
id eni-1a2b3c4d
```

Este exemplo associa um IP elástico a um endereço IP privado associado a uma interface de rede.

Comando:

```
aws ec2 associate-address --allocation-id eipalloc-64d5890a --network-interface-
id eni-1a2b3c4d --private-ip-address 10.0.0.85
```

- Para obter detalhes da API, consulte AssociateAddressem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String associateAddress(Ec2Client ec2, String instanceId,
String allocationId) {
       try {
           AssociateAddressRequest associateRequest =
AssociateAddressRequest.builder()
                   .instanceId(instanceId)
                   .allocationId(allocationId)
                   .build();

           AssociateAddressResponse associateResponse =
ec2.associateAddress(associateRequest);
           return associateResponse.associationId();

       } catch (Ec2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AssociateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  // You need to allocate an Elastic IP address before associating it with an
 instance.
  // You can do that with the AllocateAddressCommand.
  const allocationId = "ALLOCATION_ID";
  // You need to create an EC2 instance before an IP address can be associated
 with it.
  // You can do that with the RunInstancesCommand.
  const instanceId = "INSTANCE_ID";
  const command = new AssociateAddressCommand({
    AllocationId: allocationId,
    InstanceId: instanceId,
  });

  try {
    const { AssociationId } = await client.send(command);
    console.log(
      `Address with allocation ID ${allocationId} is now associated with instance
 ${instanceId}.`,
      `The association ID is ${AssociationId}.`,
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun associateAddressSc(instanceIdVal: String?, allocationIdVal: String?):
 String? {
    val associateRequest = AssociateAddressRequest {
        instanceId = instanceIdVal
        allocationId = allocationIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val associateResponse = ec2.associateAddress(associateRequest)
        return associateResponse.associationId
    }
}
```

- Para obter detalhes da API, consulte a AssociateAddressreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def associate(self, instance):
        """
        Associates an Elastic IP address with an instance. When this association
 is
        created, the Elastic IP's public IP address is immediately used as the
 public
        IP address of the associated instance.

        :param instance: A Boto3 Instance object. This is a high-level object
 that wraps
                         Amazon EC2 instance actions.
        :return: A response that contains the ID of the association.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to associate.")
            return

        try:
            response = self.elastic_ip.associate(InstanceId=instance.id)
        except ClientError as err:
```

```
            logger.error(
                "Couldn't associate Elastic IP %s with instance %s. Here's why:
 %s: %s",
                self.elastic_ip.allocation_id,
                instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        return response
```

- Para obter detalhes da API, consulte a AssociateAddressReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Associates an Elastic IP address with an Amazon Elastic Compute Cloud
# (Amazon EC2) instance.
#
# Prerequisites:
#
# - The allocation ID corresponding to the Elastic IP address.
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param allocation_id [String] The ID of the allocation corresponding to
#   the Elastic IP address.
# @param instance_id [String] The ID of the instance.
# @return [String] The assocation ID corresponding to the association of the
#   Elastic IP address to the instance.
# @example
```

```
#   puts allocate_elastic_ip_address(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'eipalloc-04452e528a66279EX',
#     'i-033c48ef067af3dEX')
def associate_elastic_ip_address_with_instance(
  ec2_client,
  allocation_id,
  instance_id
)
  response = ec2_client.associate_address(
    allocation_id: allocation_id,
    instance_id: instance_id,
  )
  return response.association_id
rescue StandardError => e
  puts "Error associating Elastic IP address with instance: #{e.message}"
  return "Error"
end
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->associateaddress(                        " oo_result
 is returned for testing purposes. "
            iv_allocationid = iv_allocation_id
            iv_instanceid = iv_instance_id
        ).
        MESSAGE 'Associated an Elastic IP address with an EC2 instance.' TYPE
 'I'.
```

```
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a AssociateAddressreferência da API AWS SDK for SAP ABAP.

Criar uma Amazon Virtual Private Cloud (Amazon VPC)

Os exemplos de código a seguir mostram como criar uma Amazon Virtual Private Cloud (Amazon VPC).

CLI

AWS CLI

Exemplo 1: criar uma VPC

O exemplo `create-vpc` a seguir cria uma VPC com o bloco CIDR IPv4 especificado e uma tag de nome.

```
aws ec2 create-vpc \
    --cidr-block 10.0.0.0/16 \
    --tag-specification ResourceType=vpc,Tags=[{Key=Name,Value=MyVpc}]
```

Saída:

```
{
    "Vpc": {
        "CidrBlock": "10.0.0.0/16",
        "DhcpOptionsId": "dopt-5EXAMPLE",
        "State": "pending",
        "VpcId": "vpc-0a60eb65b4EXAMPLE",
        "OwnerId": "123456789012",
        "InstanceTenancy": "default",
        "Ipv6CidrBlockAssociationSet": [],
        "CidrBlockAssociationSet": [
            {
                "AssociationId": "vpc-cidr-assoc-07501b79ecEXAMPLE",
```

```
                "CidrBlock": "10.0.0.0/16",
                "CidrBlockState": {
                    "State": "associated"
                }
            }
        ],
        "IsDefault": false,
        "Tags": [
            {
                "Key": "Name",
                "Value": MyVpc"
            }
        ]
    }
}
```

Exemplo 2: para criar uma VPC com locação dedicada

O exemplo `create-vpc` a seguir cria uma VPC com o bloco CIDR IPv4 especificado e locação dedicada.

```
aws ec2 create-vpc \
    --cidr-block 10.0.0.0/16 \
    --instance-tenancy dedicated
```

Saída:

```
{
    "Vpc": {
        "CidrBlock": "10.0.0.0/16",
        "DhcpOptionsId": "dopt-19edf471",
        "State": "pending",
        "VpcId": "vpc-0a53287fa4EXAMPLE",
        "OwnerId": "111122223333",
        "InstanceTenancy": "dedicated",
        "Ipv6CidrBlockAssociationSet": [],
        "CidrBlockAssociationSet": [
            {
                "AssociationId": "vpc-cidr-assoc-00b24cc1c2EXAMPLE",
                "CidrBlock": "10.0.0.0/16",
                "CidrBlockState": {
                    "State": "associated"
                }
```

```
            }
        ],
        "IsDefault": false
    }
}
```

Exemplo 3: criar uma VPC com um bloco CIDR IPv6

O exemplo `create-vpc` a seguir cria uma VPC com um bloco CIDR IPv6 fornecido pela Amazon.

```
aws ec2 create-vpc \
    --cidr-block 10.0.0.0/16 \
    --amazon-provided-ipv6-cidr-block
```

Saída:

```
{
    "Vpc": {
        "CidrBlock": "10.0.0.0/16",
        "DhcpOptionsId": "dopt-dEXAMPLE",
        "State": "pending",
        "VpcId": "vpc-0fc5e3406bEXAMPLE",
        "OwnerId": "123456789012",
        "InstanceTenancy": "default",
        "Ipv6CidrBlockAssociationSet": [
            {
                "AssociationId": "vpc-cidr-assoc-068432c60bEXAMPLE",
                "Ipv6CidrBlock": "",
                "Ipv6CidrBlockState": {
                    "State": "associating"
                },
                "Ipv6Pool": "Amazon",
                "NetworkBorderGroup": "us-west-2"
            }
        ],
        "CidrBlockAssociationSet": [
            {
                "AssociationId": "vpc-cidr-assoc-0669f8f9f5EXAMPLE",
                "CidrBlock": "10.0.0.0/16",
                "CidrBlockState": {
                    "State": "associated"
                }
```

```
            }
        ],
        "IsDefault": false
    }
}
```

Exemplo 4: criar uma VPC com um CIDR de um grupo do IPAM

O exemplo `create-vpc` a seguir cria uma VPC com um CIDR de um conjunto do gerenciador de endereços IP (IPAM) da Amazon VPC.

Linux e macOS:

```
aws ec2 create-vpc \
    --ipv4-ipam-pool-id ipam-pool-0533048da7d823723 \
    --tag-specifications
 ResourceType=vpc,Tags='[{Key=Environment,Value="Preprod"},
{Key=Owner,Value="Build Team"}]'
```

Windows:

```
aws ec2 create-vpc ^
    --ipv4-ipam-pool-id ipam-pool-0533048da7d823723 ^
    --tag-specifications
 ResourceType=vpc,Tags=[{Key=Environment,Value="Preprod"},{Key=Owner,Value="Build
 Team"}]
```

Saída:

```
{
     "Vpc": {
         "CidrBlock": "10.0.1.0/24",
         "DhcpOptionsId": "dopt-2afccf50",
         "State": "pending",
         "VpcId": "vpc-010e1791024eb0af9",
         "OwnerId": "123456789012",
         "InstanceTenancy": "default",
         "Ipv6CidrBlockAssociationSet": [],
         "CidrBlockAssociationSet": [
             {
                 "AssociationId": "vpc-cidr-assoc-0a77de1d803226d4b",
                 "CidrBlock": "10.0.1.0/24",
                 "CidrBlockState": {
```

```
                    "State": "associated"
                }
            }
        ],
        "IsDefault": false,
        "Tags": [
            {
                "Key": "Environment",
                "Value": "Preprod"
            },
            {
                "Key": "Owner",
                "Value": "Build Team"
            }
        ]
    }
}
```

Para obter mais informações, consulte Criar uma VPC que usa um CIDR de um conjunto do IPAM no Guia do usuário do IPAM da Amazon VPC.

- Para obter detalhes da API, consulte CreateVpcem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Creates a virtual private cloud (VPC) in
# Amazon Virtual Private Cloud (Amazon VPC) and then tags
# the VPC.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
```

```
# @param cidr_block [String] The IPv4 CIDR block for the subnet.
# @param tag_key [String] The key portion of the tag for the VPC.
# @param tag_value [String] The value portion of the tag for the VPC.
# @return [Boolean] true if the VPC was created and tagged;
#   otherwise, false.
# @example
#   exit 1 unless vpc_created_and_tagged?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     '10.0.0.0/24',
#     'my-key',
#     'my-value'
#   )
def vpc_created_and_tagged?(
  ec2_resource,
  cidr_block,
  tag_key,
  tag_value
)
  vpc = ec2_resource.create_vpc(cidr_block: cidr_block)

  # Create a public DNS by enabling DNS support and DNS hostnames.
  vpc.modify_attribute(enable_dns_support: { value: true })
  vpc.modify_attribute(enable_dns_hostnames: { value: true })

  vpc.create_tags(tags: [{ key: tag_key, value: tag_value }])

  puts "Created VPC with ID '#{vpc.id}' and tagged with key " \
    "'#{tag_key}' and value '#{tag_value}'."
  return true
rescue StandardError => e
  puts "#{e.message}"
  return false
end

# Example usage:
def run_me
  cidr_block = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-create-vpc.rb " \
      "CIDR_BLOCK TAG_KEY TAG_VALUE REGION"
```

```
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-create-vpc.rb " \
      "10.0.0.0/24 my-key my-value us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    cidr_block = "10.0.0.0/24"
    tag_key = "my-key"
    tag_value = "my-value"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    cidr_block = ARGV[0]
    tag_key = ARGV[1]
    tag_value = ARGV[2]
    region = ARGV[3]
  end

  ec2_resource = Aws::EC2::Resource.new(region: region)

  if vpc_created_and_tagged?(
    ec2_resource,
    cidr_block,
    tag_key,
    tag_value
  )
    puts "VPC created and tagged."
  else
    puts "VPC not created or not tagged."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateVpca Referência AWS SDK for Ruby da API.

Crie um modelo de execução do Amazon EC2 usando um SDK AWS

Os exemplos de código a seguir mostram como criar um modelo de inicialização de sub-rede do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling.
   /// The launch template specifies a Bash script in its user data field that
runs after
   /// the instance is started. This script installs the Python packages and
starts a Python
   /// web server on the instance.
   /// </summary>
   /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
   /// <param name="instancePolicyPath">The path to a permissions policy to
create and attach to the profile.</param>
   /// <returns>The template object.</returns>
   public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
   {
       await CreateKeyPair(_keyPairName);
       await CreateInstanceProfileWithName(_instancePolicyName,
_instanceRoleName, _instanceProfileName, instancePolicyPath);

       var startServerText = await File.ReadAllTextAsync(startupScriptPath);
       var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

       var amiLatest = await _amazonSsm.GetParameterAsync(
           new GetParameterRequest() { Name = _amiParam });
```

```
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new

 LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }
```

- Para obter detalhes da API, consulte CreateLaunchTemplatea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: criar um modelo de lançamento

O exemplo `create-launch-template` a seguir cria um modelo de execução que especifica a sub-rede na qual executar a instância, atribui um endereço IP público e um endereço IPv6 à instância e cria uma tag para a instância.

```
aws ec2 create-launch-template \
    --launch-template-name TemplateForWebServer \
    --version-description WebVersion1 \
```

```
    --launch-template-data '{"NetworkInterfaces":
[{"AssociatePublicIpAddress":true,"DeviceIndex":0,"Ipv6AddressCount":1,"SubnetId":"subnet
[{"ResourceType":"instance","Tags":[{"Key":"purpose","Value":"webserver"}]}]}'
```

Saída:

```
{
    "LaunchTemplate": {
        "LatestVersionNumber": 1,
        "LaunchTemplateId": "lt-01238c059e3466abc",
        "LaunchTemplateName": "TemplateForWebServer",
        "DefaultVersionNumber": 1,
        "CreatedBy": "arn:aws:iam::123456789012:user/Bob",
        "CreateTime": "2019-01-27T09:13:24.000Z"
    }
}
```

Para obter mais informações, consulte Execução de uma instância em um modelo de execução no Guia do usuário do Amazon Elastic Compute Cloud. Para obter informações sobre como citar parâmetros formatados em JSON, consulte Uso de aspas com strings no Guia do usuário da AWS Command Line Interface.

Exemplo 2: para criar um modelo de execução para o Amazon EC2 Auto Scaling

O exemplo `create-launch-template` a seguir cria um modelo de execução com várias tags e um mapeamento de dispositivos de blocos para especificar um volume adicional do EBS quando uma instância é executada. Especifique um valor para `Groups` que corresponda aos grupos de segurança da VPC na qual o seu grupo do Auto Scaling executará as instâncias. Especifique a VPC e as sub-redes como propriedades do grupo do Auto Scaling.

```
aws ec2 create-launch-template \
    --launch-template-name TemplateForAutoScaling \
    --version-description AutoScalingVersion1 \
    --launch-template-data '{"NetworkInterfaces":
[{"DeviceIndex":0,"AssociatePublicIpAddress":true,"Groups":
["sg-7c227019,sg-903004f8"],"DeleteOnTermination":true}],"ImageId":"ami-
b42209de","InstanceType":"m4.large","TagSpecifications":
[{"ResourceType":"instance","Tags":[{"Key":"environment","Value":"production"},
{"Key":"purpose","Value":"webserver"}]},{"ResourceType":"volume","Tags":
[{"Key":"environment","Value":"production"},{"Key":"cost-
```

```
center","Value":"cc123"}]}],"BlockDeviceMappings":[{"DeviceName":"/dev/
sda1","Ebs":{"VolumeSize":100}}]}' --region us-east-1
```

Saída:

```
{
    "LaunchTemplate": {
        "LatestVersionNumber": 1,
        "LaunchTemplateId": "lt-0123c79c33a54e0abc",
        "LaunchTemplateName": "TemplateForAutoScaling",
        "DefaultVersionNumber": 1,
        "CreatedBy": "arn:aws:iam::123456789012:user/Bob",
        "CreateTime": "2019-04-30T18:16:06.000Z"
    }
}
```

Para obter mais informações, consulte Como criar um modelo de execução para um grupo do Auto Scaling no Guia do usuário do Amazon EC2 Auto Scaling. Para obter informações sobre como citar parâmetros formatados em JSON, consulte Uso de aspas com strings no Guia do usuário da AWS Command Line Interface.

Exemplo 3: criar um modelo de execução que especifique a criptografia dos volumes do EBS

O exemplo `create-launch-template` a seguir cria um modelo de execução que inclui volumes criptografados do EBS criados de um snapshot não criptografado. Ele também coloca tags nos volumes durante a criação. Se a criptografia por padrão estiver desabilitada, você deve especificar a opção `"Encrypted"` conforme mostrado no exemplo a seguir. Se você usar a opção `"KmsKeyId"` para especificar uma CMK gerenciada pelo cliente, também deverá especificar a opção `"Encrypted"` mesmo que a criptografia por padrão esteja habilitada.

```
aws ec2 create-launch-template \
  --launch-template-name TemplateForEncryption \
  --launch-template-data file://config.json
```

Conteúdo de `config.json`:

```
{
    "BlockDeviceMappings":[
        {
            "DeviceName":"/dev/sda1",
```

```
            "Ebs":{
                "VolumeType":"gp2",
                "DeleteOnTermination":true,
                "SnapshotId":"snap-066877671789bd71b",
                "Encrypted":true,
                "KmsKeyId":"arn:aws:kms:us-east-1:012345678910:key/abcd1234-
a123-456a-a12b-a123b4cd56ef"
            }
        }
    ],
    "ImageId":"ami-00068cd7555f543d5",
    "InstanceType":"c5.large",
    "TagSpecifications":[
        {
            "ResourceType":"volume",
            "Tags":[
                {
                    "Key":"encrypted",
                    "Value":"yes"
                }
            ]
        }
    ]
}
```

Saída:

```
{
    "LaunchTemplate": {
        "LatestVersionNumber": 1,
        "LaunchTemplateId": "lt-0d5bd51bcf8530abc",
        "LaunchTemplateName": "TemplateForEncryption",
        "DefaultVersionNumber": 1,
        "CreatedBy": "arn:aws:iam::123456789012:user/Bob",
        "CreateTime": "2020-01-07T19:08:36.000Z"
    }
}
```

Para obter mais informações, consulte Restoring an Amazon EBS Volume from a Snapshot and Encryption by Default no Guia do usuário do Amazon Elastic Compute Cloud.

- Para obter detalhes da API, consulte CreateLaunchTemplateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const ssmClient = new SSMClient({});
const { Parameter } = await ssmClient.send(
  new GetParameterCommand({
    Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
  }),
);
const ec2Client = new EC2Client({});
await ec2Client.send(
  new CreateLaunchTemplateCommand({
    LaunchTemplateName: NAMES.launchTemplateName,
    LaunchTemplateData: {
      InstanceType: "t3.micro",
      ImageId: Parameter.Value,
      IamInstanceProfile: { Name: NAMES.instanceProfileName },
      UserData: readFileSync(
        join(RESOURCES_PATH, "server_startup_script.sh"),
      ).toString("base64"),
      KeyName: NAMES.keyPairName,
    },
  }),
```

- Para obter detalhes da API, consulte CreateLaunchTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo cria um modelo de execução que inclui um perfil de instância que concede permissões específicas à instância e um script Bash de dados do usuário que é executado na instância após sua inicialização.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
```

```
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling. The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts
a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a
permissions policy
                                     to create and attach to the instance
profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
```

```
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template
{self.launch_template_name}: {err}."
                )
        return template
```

- Para obter detalhes da API, consulte a CreateLaunchTemplateReferência da API AWSSDK for Python (Boto3).

Criar uma tabela de rotas na Amazon Virtual Private Cloud (Amazon VPC) e associá-la a uma sub-rede

Os exemplos de código a seguir mostram como criar uma tabela de rotas e associá-la à sub-rede do Amazon EC2.

CLI

AWS CLI

Para criar uma tabela de rotas

Este exemplo cria uma tabela de rotas para a VPC especificada.

Comando:

```
aws ec2 create-route-table --vpc-id vpc-a01106c2
```

Saída:

```
{
    "RouteTable": {
        "Associations": [],
        "RouteTableId": "rtb-22574640",
        "VpcId": "vpc-a01106c2",
        "PropagatingVgws": [],
        "Tags": [],
        "Routes": [
            {
                "GatewayId": "local",
                "DestinationCidrBlock": "10.0.0.0/16",
                "State": "active"
            }
        ]
    }
}
```

- Para obter detalhes da API, consulte CreateRouteTableem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - A VPC in Amazon VPC.
# - A subnet in that VPC.
# - A gateway attached to that subnet.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
# @param vpc_id [String] The ID of the VPC for the route table.
# @param subnet_id [String] The ID of the subnet for the route table.
# @param gateway_id [String] The ID of the gateway for the route.
# @param destination_cidr_block [String] The destination CIDR block
#   for the route.
# @param tag_key [String] The key portion of the tag for the route table.
# @param tag_value [String] The value portion of the tag for the route table.
# @return [Boolean] true if the route table was created and associated;
#   otherwise, false.
# @example
#   exit 1 unless route_table_created_and_associated?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     'vpc-0b6f769731EXAMPLE',
#     'subnet-03d9303b57EXAMPLE',
#     'igw-06ca90c011EXAMPLE',
#     '0.0.0.0/0',
#     'my-key',
#     'my-value'
#   )
def route_table_created_and_associated?(
  ec2_resource,
  vpc_id,
```

```
  subnet_id,
  gateway_id,
  destination_cidr_block,
  tag_key,
  tag_value
)
  route_table = ec2_resource.create_route_table(vpc_id: vpc_id)
  puts "Created route table with ID '#{route_table.id}'."
  route_table.create_tags(
    tags: [
      {
        key: tag_key,
        value: tag_value
      }
    ]
  )
  puts "Added tags to route table."
  route_table.create_route(
    destination_cidr_block: destination_cidr_block,
    gateway_id: gateway_id
  )
  puts "Created route with destination CIDR block " \
    "'#{destination_cidr_block}' and associated with gateway " \
    "with ID '#{gateway_id}'."
  route_table.associate_with_subnet(subnet_id: subnet_id)
  puts "Associated route table with subnet with ID '#{subnet_id}'."
  return true
rescue StandardError => e
  puts "Error creating or associating route table: #{e.message}"
  puts "If the route table was created but not associated, you should " \
    "clean up by deleting the route table."
  return false
end

# Example usage:
def run_me
  vpc_id = ""
  subnet_id = ""
  gateway_id = ""
  destination_cidr_block = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
```

```
if ARGV[0] == "--help" || ARGV[0] == "-h"
  puts "Usage: ruby ec2-ruby-example-create-route-table.rb " \
    "VPC_ID SUBNET_ID GATEWAY_ID DESTINATION_CIDR_BLOCK " \
    "TAG_KEY TAG_VALUE REGION"
# Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  puts "Example: ruby ec2-ruby-example-create-route-table.rb " \
    "vpc-0b6f769731EXAMPLE subnet-03d9303b57EXAMPLE igw-06ca90c011EXAMPLE " \
    "'0.0.0.0/0' my-key my-value us-west-2"
  exit 1
# If no values are specified at the command prompt, use these default values.
elsif ARGV.count.zero?
  vpc_id = "vpc-0b6f769731EXAMPLE"
  subnet_id = "subnet-03d9303b57EXAMPLE"
  gateway_id = "igw-06ca90c011EXAMPLE"
  destination_cidr_block = "0.0.0.0/0"
  tag_key = "my-key"
  tag_value = "my-value"
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  region = "us-west-2"
# Otherwise, use the values as specified at the command prompt.
else
  vpc_id = ARGV[0]
  subnet_id = ARGV[1]
  gateway_id = ARGV[2]
  destination_cidr_block = ARGV[3]
  tag_key = ARGV[4]
  tag_value = ARGV[5]
  region = ARGV[6]
end

ec2_resource = Aws::EC2::Resource.new(region: region)

if route_table_created_and_associated?(
  ec2_resource,
  vpc_id,
  subnet_id,
  gateway_id,
  destination_cidr_block,
  tag_key,
  tag_value
)
  puts "Route table created and associated."
else
  puts "Route table not created or not associated."
```

```
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateRouteTablea Referência AWS SDK for Ruby da API.

Criar um grupo de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como criar um grupo de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name for the new security group.</param>
    /// <param name="groupDescription">A description of the new security group.</
param>
    /// <returns>The group Id of the new security group.</returns>
    public async Task<string> CreateSecurityGroup(string groupName, string
 groupDescription)
    {
        var response = await _amazonEC2.CreateSecurityGroupAsync(
```

```
            new CreateSecurityGroupRequest(groupName, groupDescription));

        return response.GroupId;
    }
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::CreateSecurityGroupRequest request;

    request.SetGroupName(groupName);
    request.SetDescription(description);
    request.SetVpcId(vpcID);

    const Aws::EC2::Model::CreateSecurityGroupOutcome outcome =
            ec2Client.CreateSecurityGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create security group:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    std::cout << "Successfully created security group named " << groupName <<
              std::endl;
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar um grupo de segurança do EC2-Classic

Este exemplo cria um grupo de segurança chamado `MySecurityGroup`.

Comando:

```
aws ec2 create-security-group --group-name MySecurityGroup --description "My
 security group"
```

Saída:

```
{
    "GroupId": "sg-903004f8"
}
```

Para criar um grupo de segurança do EC2-VPC

Este exemplo cria um grupo de segurança chamado `MySecurityGroup` para a VPC especificada.

Comando:

```
aws ec2 create-security-group --group-name MySecurityGroup --description "My
 security group" --vpc-id vpc-1a2b3c4d
```

Saída:

```
{
    "GroupId": "sg-903004f8"
}
```

Para obter mais informações, consulte Using Security Groups no Guia do usuário da AWS Command Line Interface.

- Para obter detalhes da API, consulte CreateSecurityGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.CreateSecurityGroupRequest;
import
 software.amazon.awssdk.services.ec2.model.AuthorizeSecurityGroupIngressRequest;
import
 software.amazon.awssdk.services.ec2.model.AuthorizeSecurityGroupIngressResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import software.amazon.awssdk.services.ec2.model.IpPermission;
import software.amazon.awssdk.services.ec2.model.CreateSecurityGroupResponse;
import software.amazon.awssdk.services.ec2.model.IpRange;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateSecurityGroup {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                   <groupName> <groupDesc> <vpcId>\s
```

```
                                Where:
                                   groupName - A group name (for example,
TestKeyPair).\s
                                   groupDesc - A group description  (for example,
TestKeyPair).\s
                                   vpcId - A VPC ID that you can obtain from the
AWS Management Console (for example, vpc-xxxxxf2f).\s

                                """;

               if (args.length != 3) {
                       System.out.println(usage);
                       System.exit(1);
               }

               String groupName = args[0];
               String groupDesc = args[1];
               String vpcId = args[2];

               Region region = Region.US_EAST_1;
               Ec2Client ec2 = Ec2Client.builder()
                               .region(region)
                               .build();

               String id = createEC2SecurityGroup(ec2, groupName, groupDesc,
vpcId);
               System.out.printf("Successfully created Security Group with this
ID %s", id);
               ec2.close();
       }

       public static String createEC2SecurityGroup(Ec2Client ec2, String
groupName, String groupDesc, String vpcId) {
               try {
                       CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                                       .groupName(groupName)
                                       .description(groupDesc)
                                       .vpcId(vpcId)
                                       .build();

                       CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);
```

```
                        IpRange ipRange = IpRange.builder()
                                        .cidrIp("0.0.0.0/0").build();

                        IpPermission ipPerm = IpPermission.builder()
                                        .ipProtocol("tcp")
                                        .toPort(80)
                                        .fromPort(80)
                                        .ipRanges(ipRange)
                                        .build();

                        IpPermission ipPerm2 = IpPermission.builder()
                                        .ipProtocol("tcp")
                                        .toPort(22)
                                        .fromPort(22)
                                        .ipRanges(ipRange)
                                        .build();

                        AuthorizeSecurityGroupIngressRequest authRequest =
 AuthorizeSecurityGroupIngressRequest
                                        .builder()
                                        .groupName(groupName)
                                        .ipPermissions(ipPerm, ipPerm2)
                                        .build();

                        AuthorizeSecurityGroupIngressResponse authResponse = ec2

 .authorizeSecurityGroupIngress(authRequest);
                        System.out.printf("Successfully added ingress policy to
 Security Group %s", groupName);
                        return resp.groupId();

                } catch (Ec2Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
                return "";
        }
}
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateSecurityGroupCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new CreateSecurityGroupCommand({
    // Up to 255 characters in length. Cannot start with sg-.
    GroupName: "SECURITY_GROUP_NAME",
    // Up to 255 characters in length.
    Description: "DESCRIPTION",
  });

  try {
    const { GroupId } = await client.send(command);
    console.log(GroupId);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2SecurityGroup(groupNameVal: String?, groupDescVal: String?,
 vpcIdVal: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "0.0.0.0/0"
        }

        val ipPerm = IpPermission {
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
        }
```

```
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group
 $groupNameVal")
        return resp.groupId
    }
}
```

- Para obter detalhes da API, consulte a CreateSecurityGroupreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
```

```
        return cls(ec2_resource)


    def create(self, group_name, group_description):
        """
        Creates a security group in the default virtual private cloud (VPC) of
the
        current account.

        :param group_name: The name of the security group to create.
        :param group_description: The description of the security group to
create.
        :return: A Boto3 SecurityGroup object that represents the newly created
security group.
        """
        try:
            self.security_group = self.ec2_resource.create_security_group(
                GroupName=group_name, Description=group_description
            )
        except ClientError as err:
            logger.error(
                "Couldn't create security group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.security_group
```

- Para obter detalhes da API, consulte a CreateSecurityGroupReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example does the following:
# 1. Creates an Amazon Elastic Compute Cloud (Amazon EC2) security group.
# 2. Adds inbound rules to the security group.
# 3. Displays information about available security groups.
# 4. Deletes the security group.

require "aws-sdk-ec2"

# Creates an Amazon Elastic Compute Cloud (Amazon EC2) security group.
#
# Prerequisites:
#
# - A VPC in Amazon Virtual Private Cloud (Amazon VPC).
#
# @param ec2_client [Aws::EC2::Client] An initialized
#   Amazon EC2 client.
# @param group_name [String] A name for the security group.
# @param description [String] A description for the security group.
# @param vpc_id [String] The ID of the VPC for the security group.
# @return [String] The ID of security group that was created.
# @example
#   puts create_security_group(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-security-group',
#     'This is my security group.',
#     'vpc-6713dfEX'
#   )
def create_security_group(
  ec2_client,
  group_name,
  description,
```

```
  vpc_id
)
  security_group = ec2_client.create_security_group(
    group_name: group_name,
    description: description,
    vpc_id: vpc_id
  )
  puts "Created security group '#{group_name}' with ID " \
    "'#{security_group.group_id}' in VPC with ID '#{vpc_id}'."
  return security_group.group_id
rescue StandardError => e
  puts "Error creating security group: #{e.message}"
  return "Error"
end

# Adds an inbound rule to an Amazon Elastic Compute Cloud (Amazon EC2)
# security group.
#
# Prerequisites:
#
# - The security group.
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @param security_group_id [String] The ID of the security group.
# @param ip_protocol [String] The network protocol for the inbound rule.
# @param from_port [String] The originating port for the inbound rule.
# @param to_port [String] The destination port for the inbound rule.
# @param cidr_ip_range [String] The CIDR IP range for the inbound rule.
# @return
# @example
#   exit 1 unless security_group_ingress_authorized?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'sg-030a858e078f1b9EX',
#     'tcp',
#     '80',
#     '80',
#     '0.0.0.0/0'
#   )
def security_group_ingress_authorized?(
  ec2_client,
  security_group_id,
  ip_protocol,
  from_port,
  to_port,
```

```
  cidr_ip_range
)
  ec2_client.authorize_security_group_ingress(
    group_id: security_group_id,
    ip_permissions: [
      {
        ip_protocol: ip_protocol,
        from_port: from_port,
        to_port: to_port,
        ip_ranges: [
          {
            cidr_ip: cidr_ip_range
          }
        ]
      }
    ]
  )
  puts "Added inbound rule to security group '#{security_group_id}' for protocol
 " \
    "'#{ip_protocol}' from port '#{from_port}' to port '#{to_port}' " \
    "with CIDR IP range '#{cidr_ip_range}'."
  return true
rescue StandardError => e
  puts "Error adding inbound rule to security group: #{e.message}"
  return false
end

# Displays information about a security group's IP permissions set in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# Prerequisites:
#
# - A security group with inbound rules, outbound rules, or both.
#
# @param p [Aws::EC2::Types::IpPermission] The IP permissions set.
# @example
#   ec2_client = Aws::EC2::Client.new(region: 'us-west-2')
#   response = ec2_client.describe_security_groups
#   unless sg.ip_permissions.empty?
#     describe_security_group_permissions(
#       response.security_groups[0].ip_permissions[0]
#     )
#   end
def describe_security_group_permissions(perm)
```

```
  print "  Protocol: #{perm.ip_protocol == '-1' ? 'All' : perm.ip_protocol}"

  unless perm.from_port.nil?
    if perm.from_port == "-1" || perm.from_port == -1
      print ", From: All"
    else
      print ", From: #{perm.from_port}"
    end
  end

  unless perm.to_port.nil?
    if perm.to_port == "-1" || perm.to_port == -1
      print ", To: All"
    else
      print ", To: #{perm.to_port}"
    end
  end

  if perm.key?(:ipv_6_ranges) && perm.ipv_6_ranges.count.positive?
    print ", CIDR IPv6: #{perm.ipv_6_ranges[0].cidr_ipv_6}"
  end

  if perm.key?(:ip_ranges) && perm.ip_ranges.count.positive?
    print ", CIDR IPv4: #{perm.ip_ranges[0].cidr_ip}"
  end

  print "\n"
end

# Displays information about available security groups in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @example
#   describe_security_groups(Aws::EC2::Client.new(region: 'us-west-2'))
def describe_security_groups(ec2_client)
  response = ec2_client.describe_security_groups

  if response.security_groups.count.positive?
    response.security_groups.each do |sg|
      puts "-" * (sg.group_name.length + 13)
      puts "Name:        #{sg.group_name}"
      puts "Description: #{sg.description}"
      puts "Group ID:    #{sg.group_id}"
```

```
      puts "Owner ID:    #{sg.owner_id}"
      puts "VPC ID:      #{sg.vpc_id}"

      if sg.tags.count.positive?
        puts "Tags:"
        sg.tags.each do |tag|
          puts "  Key: #{tag.key}, Value: #{tag.value}"
        end
      end

      unless sg.ip_permissions.empty?
        puts "Inbound rules:" if sg.ip_permissions.count.positive?
        sg.ip_permissions.each do |p|
          describe_security_group_permissions(p)
        end
      end

      unless sg.ip_permissions_egress.empty?
        puts "Outbound rules:" if sg.ip_permissions.count.positive?
        sg.ip_permissions_egress.each do |p|
          describe_security_group_permissions(p)
        end
      end
    end
  else
    puts "No security groups found."
  end
rescue StandardError => e
  puts "Error getting information about security groups: #{e.message}"
end

# Deletes an Amazon Elastic Compute Cloud (Amazon EC2)
# security group.
#
# Prerequisites:
#
# - The security group.
#
# @param ec2_client [Aws::EC2::Client] An initialized
#   Amazon EC2 client.
# @param security_group_id [String] The ID of the security group to delete.
# @return [Boolean] true if the security group was deleted; otherwise, false.
# @example
#   exit 1 unless security_group_deleted?(
```

```
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'sg-030a858e078f1b9EX'
#   )
def security_group_deleted?(ec2_client, security_group_id)
  ec2_client.delete_security_group(group_id: security_group_id)
  puts "Deleted security group '#{security_group_id}'."
  return true
rescue StandardError => e
  puts "Error deleting security group: #{e.message}"
  return false
end

# Example usage:
def run_me
  group_name = ""
  description = ""
  vpc_id = ""
  ip_protocol_http = ""
  from_port_http = ""
  to_port_http = ""
  cidr_ip_range_http = ""
  ip_protocol_ssh = ""
  from_port_ssh = ""
  to_port_ssh = ""
  cidr_ip_range_ssh = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-security-group.rb " \
      "GROUP_NAME DESCRIPTION VPC_ID IP_PROTOCOL_1 FROM_PORT_1 TO_PORT_1 " \
      "CIDR_IP_RANGE_1 IP_PROTOCOL_2 FROM_PORT_2 TO_PORT_2 " \
      "CIDR_IP_RANGE_2 REGION"
    puts "Example: ruby ec2-ruby-example-security-group.rb " \
      "my-security-group 'This is my security group.' vpc-6713dfEX " \
      "tcp 80 80 '0.0.0.0/0' tcp 22 22 '0.0.0.0/0' us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    group_name = "my-security-group"
    description = "This is my security group."
    vpc_id = "vpc-6713dfEX"
    ip_protocol_http = "tcp"
    from_port_http = "80"
    to_port_http = "80"
```

```
    cidr_ip_range_http = "0.0.0.0/0"
    ip_protocol_ssh = "tcp"
    from_port_ssh = "22"
    to_port_ssh = "22"
    cidr_ip_range_ssh = "0.0.0.0/0"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    group_name = ARGV[0]
    description = ARGV[1]
    vpc_id = ARGV[2]
    ip_protocol_http = ARGV[3]
    from_port_http = ARGV[4]
    to_port_http = ARGV[5]
    cidr_ip_range_http = ARGV[6]
    ip_protocol_ssh = ARGV[7]
    from_port_ssh = ARGV[8]
    to_port_ssh = ARGV[9]
    cidr_ip_range_ssh = ARGV[10]
    region = ARGV[11]
  end

  security_group_id = ""
  security_group_exists = false
  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to create security group..."
  security_group_id = create_security_group(
    ec2_client,
    group_name,
    description,
    vpc_id
  )
  if security_group_id == "Error"
    puts "Could not create security group. Skipping this step."
  else
    security_group_exists = true
  end

  if security_group_exists
    puts "Attempting to add inbound rules to security group..."
    unless security_group_ingress_authorized?(
      ec2_client,
```

```
      security_group_id,
      ip_protocol_http,
      from_port_http,
      to_port_http,
      cidr_ip_range_http
    )
      puts "Could not add inbound HTTP rule to security group. " \
        "Skipping this step."
    end

    unless security_group_ingress_authorized?(
      ec2_client,
      security_group_id,
      ip_protocol_ssh,
      from_port_ssh,
      to_port_ssh,
      cidr_ip_range_ssh
    )
      puts "Could not add inbound SSH rule to security group. " \
        "Skipping this step."
    end
  end

  puts "\nInformation about available security groups:"
  describe_security_groups(ec2_client)

  if security_group_exists
    puts "\nAttempting to delete security group..."
    unless security_group_deleted?(ec2_client, security_group_id)
      puts "Could not delete security group. You must delete it yourself."
    end
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->createsecuritygroup(                " oo_result is
 returned for testing purposes. "
          iv_description = 'Security group example'
          iv_groupname = iv_security_group_name
          iv_vpcid = iv_vpc_id
        ).
        MESSAGE 'Security group created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateSecurityGroupreferência da API AWS SDK for SAP ABAP.

Criar um par de chaves de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como criar um par de chaves de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create an Amazon EC2 key pair.
/// </summary>
/// <param name="keyPairName">The name for the new key pair.</param>
/// <returns>The Amazon EC2 key pair created.</returns>
public async Task<KeyPair?> CreateKeyPair(string keyPairName)
{
    var request = new CreateKeyPairRequest
    {
        KeyName = keyPairName,
    };

    var response = await _amazonEC2.CreateKeyPairAsync(request);

    if (response.HttpStatusCode == HttpStatusCode.OK)
    {
        var kp = response.KeyPair;
        return kp;
    }
    else
    {
        Console.WriteLine("Could not create key pair.");
        return null;
    }
}

/// <summary>
/// Save KeyPair information to a temporary file.
/// </summary>
/// <param name="keyPair">The name of the key pair.</param>
/// <returns>The full path to the temporary file.</returns>
public string SaveKeyPair(KeyPair keyPair)
```

```
    {
        var tempPath = Path.GetTempPath();
        var tempFileName = $"{tempPath}\\{Path.GetRandomFileName()}";
        var pemFileName = Path.ChangeExtension(tempFileName, "pem");

        // Save the key pair to a file in a temporary folder.
        using var stream = new FileStream(pemFileName, FileMode.Create);
        using var writer = new StreamWriter(stream);
        writer.WriteLine(keyPair.KeyMaterial);

        return pemFileName;
    }
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::CreateKeyPairRequest request;
    request.SetKeyName(keyPairName);

    Aws::EC2::Model::CreateKeyPairOutcome outcome =
ec2Client.CreateKeyPair(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create key pair:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created key pair named " <<
                  keyPairName << std::endl;
    }
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar um par de chaves

Este exemplo cria um par de chaves denominado `MyKeyPair`.

Comando:

```
aws ec2 create-key-pair --key-name MyKeyPair
```

A saída é uma versão ASCII da chave privada e da impressão digital da chave. Você precisa salvar a chave em um arquivo.

Para obter mais informações, consulte Using Key Pairs no Guia do usuário da AWS Command Line Interface.

- Para obter detalhes da API, consulte CreateKeyPairem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.CreateKeyPairRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateKeyPair {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <keyName>\s

                Where:
                   keyName - A key pair name (for example, TestKeyPair).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyName = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        createEC2KeyPair(ec2, keyName);
        ec2.close();
    }

    public static void createEC2KeyPair(Ec2Client ec2, String keyName) {
        try {
            CreateKeyPairRequest request = CreateKeyPairRequest.builder()
                    .keyName(keyName)
                    .build();

            ec2.createKeyPair(request);
            System.out.printf("Successfully created key pair named %s", keyName);

        } catch (Ec2Exception e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateKeyPairCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a key pair in Amazon EC2.
    const { KeyMaterial, KeyName } = await client.send(
      // A unique name for the key pair. Up to 255 ASCII characters.
      new CreateKeyPairCommand({ KeyName: "KEY_PAIR_NAME" }),
    );
    // This logs your private key. Be sure to save it.
    console.log(KeyName);
    console.log(KeyMaterial);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2KeyPair(keyNameVal: String) {
    val request = CreateKeyPairRequest {
        keyName = keyNameVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.createKeyPair(request)
        println("The key ID is ${response.keyPairId}")
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyPairreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
```

```
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair
actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is
stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def create(self, key_name):
        """
        Creates a key pair that can be used to securely connect to an EC2
instance.
        The returned key pair contains private key information that cannot be
retrieved
        again. The private key data is stored as a .pem file.

        :param key_name: The name of the key pair to create.
        :return: A Boto3 KeyPair object that represents the newly created key
pair.
        """
        try:
            self.key_pair = self.ec2_resource.create_key_pair(KeyName=key_name)
            self.key_file_path = os.path.join(
                self.key_file_dir.name, f"{self.key_pair.name}.pem"
            )
            with open(self.key_file_path, "w") as key_file:
```

```
                key_file.write(self.key_pair.key_material)
        except ClientError as err:
            logger.error(
                "Couldn't create key %s. Here's why: %s: %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.key_pair
```

- Para obter detalhes da API, consulte a CreateKeyPairReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example does the following:
# 1. Creates a key pair in Amazon Elastic Compute Cloud (Amazon EC2).
# 2. Displays information about available key pairs.
# 3. Deletes the key pair.

require "aws-sdk-ec2"

# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param key_pair_name [String] The name for the key pair and private
#   key file.
# @return [Boolean] true if the key pair and private key file were
#   created; otherwise, false.
# @example
```

```
#   exit 1 unless key_pair_created?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-key-pair'
#   )
def key_pair_created?(ec2_client, key_pair_name)
  key_pair = ec2_client.create_key_pair(key_name: key_pair_name)
  puts "Created key pair '#{key_pair.key_name}' with fingerprint " \
    "'#{key_pair.key_fingerprint}' and ID '#{key_pair.key_pair_id}'."
  filename = File.join(Dir.home, key_pair_name + ".pem")
  File.open(filename, "w") { |file| file.write(key_pair.key_material) }
  puts "Private key file saved locally as '#{filename}'."
  return true
rescue Aws::EC2::Errors::InvalidKeyPairDuplicate
  puts "Error creating key pair: a key pair named '#{key_pair_name}' " \
    "already exists."
  return false
rescue StandardError => e
  puts "Error creating key pair or saving private key file: #{e.message}"
  return false
end

# Displays information about available key pairs in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   describe_key_pairs(Aws::EC2::Client.new(region: 'us-west-2'))
def describe_key_pairs(ec2_client)
  result = ec2_client.describe_key_pairs
  if result.key_pairs.count.zero?
    puts "No key pairs found."
  else
    puts "Key pair names:"
    result.key_pairs.each do |key_pair|
      puts key_pair.key_name
    end
  end
rescue StandardError => e
  puts "Error getting information about key pairs: #{e.message}"
end

# Deletes a key pair in Amazon Elastic Compute Cloud (Amazon EC2).
#
# Prerequisites:
```

```
#
# - The key pair to delete.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param key_pair_name [String] The name of the key pair to delete.
# @return [Boolean] true if the key pair was deleted; otherwise, false.
# @example
#   exit 1 unless key_pair_deleted?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-key-pair'
#   )
def key_pair_deleted?(ec2_client, key_pair_name)
  ec2_client.delete_key_pair(key_name: key_pair_name)
  return true
rescue StandardError => e
  puts "Error deleting key pair: #{e.message}"
  return false
end

# Example usage:
def run_me
  key_pair_name = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-key-pairs.rb KEY_PAIR_NAME REGION"
    puts "Example: ruby ec2-ruby-example-key-pairs.rb my-key-pair us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    key_pair_name = "my-key-pair"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    key_pair_name = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Displaying existing key pair names before creating this key pair..."
  describe_key_pairs(ec2_client)
```

```
  puts "-" * 10
  puts "Creating key pair..."
  unless key_pair_created?(ec2_client, key_pair_name)
    puts "Stopping program."
    exit 1
  end

  puts "-" * 10
  puts "Displaying existing key pair names after creating this key pair..."
  describe_key_pairs(ec2_client)

  puts "-" * 10
  puts "Deleting key pair..."
  unless key_pair_deleted?(ec2_client, key_pair_name)
    puts "Stopping program. You must delete the key pair yourself."
    exit 1
  end
  puts "Key pair deleted."

  puts "-" * 10
  puts "Now that the key pair is deleted, " \
    "also deleting the related private key pair file..."
  filename = File.join(Dir.home, key_pair_name + ".pem")
  File.delete(filename)
  if File.exist?(filename)
    puts "Could not delete file at '#{filename}'. You must delete it yourself."
  else
    puts "File deleted."
  end

  puts "-" * 10
  puts "Displaying existing key pair names after deleting this key pair..."
  describe_key_pairs(ec2_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->createkeypair( iv_keyname = iv_key_name ).
                 " oo_result is returned for testing purposes. "
        MESSAGE 'Amazon EC2 key pair created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateKeyPairreferência da API AWS SDK for SAP ABAP.

Criar e marcar uma sub-rede na Amazon Virtual Private Cloud (Amazon VPC)

Os exemplos de código a seguir mostram como criar uma sub-rede do Amazon EC2.

CLI

AWS CLI

Exemplo 1: criar uma sub-rede somente com um bloco CIDR IPv4

O exemplo `create-subnet` a seguir cria uma sub-rede na VPC especificada com o bloco CIDR IPv4 especificado.

```
aws ec2 create-subnet \
    --vpc-id vpc-081ec835f3EXAMPLE \
    --cidr-block 10.0.0.0/24 \
```

```
    --tag-specifications ResourceType=subnet,Tags=[{Key=Name,Value=my-ipv4-only-
subnet}]
```

Saída:

```
{
    "Subnet": {
        "AvailabilityZone": "us-west-2a",
        "AvailabilityZoneId": "usw2-az2",
        "AvailableIpAddressCount": 251,
        "CidrBlock": "10.0.0.0/24",
        "DefaultForAz": false,
        "MapPublicIpOnLaunch": false,
        "State": "available",
        "SubnetId": "subnet-0e99b93155EXAMPLE",
        "VpcId": "vpc-081ec835f3EXAMPLE",
        "OwnerId": "123456789012",
        "AssignIpv6AddressOnCreation": false,
        "Ipv6CidrBlockAssociationSet": [],
        "Tags": [
            {
                "Key": "Name",
                "Value": "my-ipv4-only-subnet"
            }
        ],
        "SubnetArn": "arn:aws:ec2:us-west-2:123456789012:subnet/
subnet-0e99b93155EXAMPLE"
    }
}
```

Exemplo 2: para criar uma sub-rede com blocos CIDR IPv4 e IPv6

O exemplo `create-subnet` a seguir cria uma sub-rede na VPC especificada com os blocos CIDR IPv4 e IPv6 especificados.

```
aws ec2 create-subnet \
    --vpc-id vpc-081ec835f3EXAMPLE \
    --cidr-block 10.0.0.0/24 \
    --ipv6-cidr-block 2600:1f16:cfe:3660::/64 \
    --tag-specifications ResourceType=subnet,Tags=[{Key=Name,Value=my-ipv4-ipv6-
subnet}]
```

Saída:

```
{
    "Subnet": {
        "AvailabilityZone": "us-west-2a",
        "AvailabilityZoneId": "usw2-az2",
        "AvailableIpAddressCount": 251,
        "CidrBlock": "10.0.0.0/24",
        "DefaultForAz": false,
        "MapPublicIpOnLaunch": false,
        "State": "available",
        "SubnetId": "subnet-0736441d38EXAMPLE",
        "VpcId": "vpc-081ec835f3EXAMPLE",
        "OwnerId": "123456789012",
        "AssignIpv6AddressOnCreation": false,
        "Ipv6CidrBlockAssociationSet": [
            {
                "AssociationId": "subnet-cidr-assoc-06c5f904499fcc623",
                "Ipv6CidrBlock": "2600:1f13:cfe:3660::/64",
                "Ipv6CidrBlockState": {
                    "State": "associating"
                }
            }
        ],
        "Tags": [
            {
                "Key": "Name",
                "Value": "my-ipv4-ipv6-subnet"
            }
        ],
        "SubnetArn": "arn:aws:ec2:us-west-2:123456789012:subnet/
subnet-0736441d38EXAMPLE"
    }
}
```

Exemplo 3: criar uma sub-rede somente com um bloco CIDR IPv6

O exemplo `create-subnet` a seguir cria uma sub-rede na VPC especificada com o bloco CIDR IPv6 especificado.

```
aws ec2 create-subnet \
    --vpc-id vpc-081ec835f3EXAMPLE \
    --ipv6-native \
```

```
    --ipv6-cidr-block 2600:1f16:115:200::/64 \
    --tag-specifications ResourceType=subnet,Tags=[{Key=Name,Value=my-ipv6-only-
subnet}]
```

Saída:

```
{
    "Subnet": {
        "AvailabilityZone": "us-west-2a",
        "AvailabilityZoneId": "usw2-az2",
        "AvailableIpAddressCount": 0,
        "DefaultForAz": false,
        "MapPublicIpOnLaunch": false,
        "State": "available",
        "SubnetId": "subnet-03f720e7deEXAMPLE",
        "VpcId": "vpc-081ec835f3EXAMPLE",
        "OwnerId": "123456789012",
        "AssignIpv6AddressOnCreation": true,
        "Ipv6CidrBlockAssociationSet": [
            {
                "AssociationId": "subnet-cidr-assoc-01ef639edde556709",
                "Ipv6CidrBlock": "2600:1f13:cfe:3660::/64",
                "Ipv6CidrBlockState": {
                    "State": "associating"
                }
            }
        ],
        "Tags": [
            {
                "Key": "Name",
                "Value": "my-ipv6-only-subnet"
            }
        ],
        "SubnetArn": "arn:aws:ec2:us-west-2:123456789012:subnet/
subnet-03f720e7deEXAMPLE"
    }
}
```

Para obter mais informações, consulte VPCs e sub-redes no Manual do usuário da Amazon VPC.

- Para obter detalhes da API, consulte CreateSubnetem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Creates a subnet within a virtual private cloud (VPC) in
# Amazon Virtual Private Cloud (Amazon VPC) and then tags
# the subnet.
#
# Prerequisites:
#
# - A VPC in Amazon VPC.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
# @param vpc_id [String] The ID of the VPC for the subnet.
# @param cidr_block [String] The IPv4 CIDR block for the subnet.
# @param availability_zone [String] The ID of the Availability Zone
#   for the subnet.
# @param tag_key [String] The key portion of the tag for the subnet.
# @param tag_vlue [String] The value portion of the tag for the subnet.
# @return [Boolean] true if the subnet was created and tagged;
#   otherwise, false.
# @example
#   exit 1 unless subnet_created_and_tagged?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     'vpc-6713dfEX',
#     '10.0.0.0/24',
#     'us-west-2a',
#     'my-key',
#     'my-value'
#   )
def subnet_created_and_tagged?(
  ec2_resource,
```

```
  vpc_id,
  cidr_block,
  availability_zone,
  tag_key,
  tag_value
)
  subnet = ec2_resource.create_subnet(
    vpc_id: vpc_id,
    cidr_block: cidr_block,
    availability_zone: availability_zone
  )
  subnet.create_tags(
    tags: [
      {
        key: tag_key,
        value: tag_value
      }
    ]
  )
  puts "Subnet created with ID '#{subnet.id}' in VPC with ID '#{vpc_id}' " \
    "and CIDR block '#{cidr_block}' in availability zone " \
    "'#{availability_zone}' and tagged with key '#{tag_key}' and " \
    "value '#{tag_value}'."
  return true
rescue StandardError => e
  puts "Error creating or tagging subnet: #{e.message}"
  return false
end

# Example usage:
def run_me
  vpc_id = ""
  cidr_block = ""
  availability_zone = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-create-subnet.rb " \
      "VPC_ID CIDR_BLOCK AVAILABILITY_ZONE TAG_KEY TAG_VALUE REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-create-subnet.rb " \
      "vpc-6713dfEX 10.0.0.0/24 us-west-2a my-key my-value us-west-2"
```

```
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    vpc_id = "vpc-6713dfEX"
    cidr_block = "10.0.0.0/24"
    availability_zone = "us-west-2a"
    tag_key = "my-key"
    tag_value = "my-value"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    vpc_id = ARGV[0]
    cidr_block = ARGV[1]
    availability_zone = ARGV[2]
    tag_key = ARGV[3]
    tag_value = ARGV[4]
    region = ARGV[5]
  end

  ec2_resource = Aws::EC2::Resource.new(region: region)

  if subnet_created_and_tagged?(
    ec2_resource,
    vpc_id,
    cidr_block,
    availability_zone,
    tag_key,
    tag_value
  )
    puts "Subnet created and tagged."
  else
    puts "Subnet not created or not tagged."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateSubneta Referência AWS SDK for Ruby da API.

Criar e executar uma instância de banco de dados do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como criar e executar uma instância de banco de dados do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create and run an EC2 instance.
   /// </summary>
   /// <param name="ImageId">The image Id of the image used as a basis for the
   /// EC2 instance.</param>
   /// <param name="instanceType">The instance type of the EC2 instance to
create.</param>
   /// <param name="keyName">The name of the key pair to associate with the
   /// instance.</param>
   /// <param name="groupId">The Id of the Amazon EC2 security group that will
be
   /// allowed to interact with the new EC2 instance.</param>
   /// <returns>The instance Id of the new EC2 instance.</returns>
   public async Task<string> RunInstances(string imageId, string instanceType,
string keyName, string groupId)
   {
       var request = new RunInstancesRequest
       {
           ImageId = imageId,
           InstanceType = instanceType,
```

```
            KeyName = keyName,
            MinCount = 1,
            MaxCount = 1,
            SecurityGroupIds = new List<string> { groupId }
        };
        var response = await _amazonEC2.RunInstancesAsync(request);
        return response.Reservation.Instances[0].InstanceId;
    }
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RunInstancesRequest runRequest;
    runRequest.SetImageId(amiId);
    runRequest.SetInstanceType(Aws::EC2::Model::InstanceType::t1_micro);
    runRequest.SetMinCount(1);
    runRequest.SetMaxCount(1);

    Aws::EC2::Model::RunInstancesOutcome runOutcome = ec2Client.RunInstances(
            runRequest);
    if (!runOutcome.IsSuccess()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    const Aws::Vector<Aws::EC2::Model::Instance> &instances =
runOutcome.GetResult().GetInstances();
```

```
    if (instances.empty()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    instanceID = instances[0].GetInstanceId();
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: executar uma instância em uma sub-rede padrão

O exemplo `run-instances` a seguir executa uma única instância do tipo `t2.micro` na sub-rede padrão da região atual e a associa à sub-rede padrão da VPC padrão da região. O par de chaves é opcional se você não planeja se conectar à instância usando SSH (Linux) ou RDP (Windows).

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --key-name MyKeyPair
```

Saída:

```
{
    "Instances": [
        {
            "AmiLaunchIndex": 0,
            "ImageId": "ami-0abcdef1234567890",
            "InstanceId": "i-1231231230abcdef0",
            "InstanceType": "t2.micro",
            "KeyName": "MyKeyPair",
            "LaunchTime": "2018-05-10T08:05:20.000Z",
            "Monitoring": {
                "State": "disabled"
            },
```

```
            "Placement": {
                "AvailabilityZone": "us-east-2a",
                "GroupName": "",
                "Tenancy": "default"
            },
            "PrivateDnsName": "ip-10-0-0-157.us-east-2.compute.internal",
            "PrivateIpAddress": "10.0.0.157",
            "ProductCodes": [],
            "PublicDnsName": "",
            "State": {
                "Code": 0,
                "Name": "pending"
            },
            "StateTransitionReason": "",
            "SubnetId": "subnet-04a636d18e83cfacb",
            "VpcId": "vpc-1234567890abcdef0",
            "Architecture": "x86_64",
            "BlockDeviceMappings": [],
            "ClientToken": "",
            "EbsOptimized": false,
            "Hypervisor": "xen",
            "NetworkInterfaces": [
                {
                    "Attachment": {
                        "AttachTime": "2018-05-10T08:05:20.000Z",
                        "AttachmentId": "eni-attach-0e325c07e928a0405",
                        "DeleteOnTermination": true,
                        "DeviceIndex": 0,
                        "Status": "attaching"
                    },
                    "Description": "",
                    "Groups": [
                        {
                            "GroupName": "MySecurityGroup",
                            "GroupId": "sg-0598c7d356eba48d7"
                        }
                    ],
                    "Ipv6Addresses": [],
                    "MacAddress": "0a:ab:58:e0:67:e2",
                    "NetworkInterfaceId": "eni-0c0a29997760baee7",
                    "OwnerId": "123456789012",
                    "PrivateDnsName": "ip-10-0-0-157.us-east-2.compute.internal",
                    "PrivateIpAddress": "10.0.0.157",
                    "PrivateIpAddresses": [
```

```
                        {
                            "Primary": true,
                            "PrivateDnsName": "ip-10-0-0-157.us-
east-2.compute.internal",
                            "PrivateIpAddress": "10.0.0.157"
                        }
                    ],
                    "SourceDestCheck": true,
                    "Status": "in-use",
                    "SubnetId": "subnet-04a636d18e83cfacb",
                    "VpcId": "vpc-1234567890abcdef0",
                    "InterfaceType": "interface"
                }
            ],
            "RootDeviceName": "/dev/xvda",
            "RootDeviceType": "ebs",
            "SecurityGroups": [
                {
                    "GroupName": "MySecurityGroup",
                    "GroupId": "sg-0598c7d356eba48d7"
                }
            ],
            "SourceDestCheck": true,
            "StateReason": {
                "Code": "pending",
                "Message": "pending"
            },
            "Tags": [],
            "VirtualizationType": "hvm",
            "CpuOptions": {
                "CoreCount": 1,
                "ThreadsPerCore": 1
            },
            "CapacityReservationSpecification": {
                "CapacityReservationPreference": "open"
            },
            "MetadataOptions": {
                "State": "pending",
                "HttpTokens": "optional",
                "HttpPutResponseHopLimit": 1,
                "HttpEndpoint": "enabled"
            }
        }
    ],
```

```
    "OwnerId": "123456789012",
    "ReservationId": "r-02a3f596d91211712"
}
```

Exemplo 2: para executar uma instância em uma sub-rede não padrão e adicionar um endereço IP público

O exemplo `run-instances` a seguir solicita um endereço IP público para uma instância que você está executando em uma sub-rede não padrão. A instância está associada ao grupo de segurança especificado.

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --subnet-id subnet-08fc749671b2d077c \
    --security-group-ids sg-0b0384b66d7d692f9 \
    --associate-public-ip-address \
    --key-name MyKeyPair
```

Para obter um exemplo da saída de `run-instances`, consulte o Exemplo 1.

Exemplo 3: executar uma instância com volumes adicionais

O exemplo `run-instances` a seguir usa um mapeamento de dispositivos de blocos, especificado em mapping.json, para anexar volumes adicionais na execução. Um mapeamento de dispositivos de blocos pode especificar volumes do EBS, volumes de armazenamento de instância ou tanto volumes do EBS quanto volumes de armazenamento de instância.

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --subnet-id subnet-08fc749671b2d077c \
    --security-group-ids sg-0b0384b66d7d692f9 \
    --key-name MyKeyPair \
    --block-device-mappings file://mapping.json
```

Conteúdo de `mapping.json`. Este exemplo adiciona `/dev/sdh` como um volume vazio do EBS com um tamanho de 100 GiB.

```
[
```

```
    {
        "DeviceName": "/dev/sdh",
        "Ebs": {
            "VolumeSize": 100
        }
    }
]
```

Conteúdo de `mapping.json`. Este exemplo adiciona `ephemeral1` como um volume de armazenamento de instância.

```
[
    {
        "DeviceName": "/dev/sdc",
        "VirtualName": "ephemeral1"
    }
]
```

Para obter um exemplo da saída de `run-instances`, consulte o Exemplo 1.

Para obter mais informações sobre mapeamentos de dispositivos de blocos, consulte Mapeamento de dispositivos de blocos no Guia do usuário do Amazon EC2.

Exemplo 4: executar uma instância e adicionar tags na criação

O exemplo `run-instances` a seguir adiciona uma tag com uma chave de `webserver` e um valor de `production` à instância. O comando também aplica uma tag com uma chave de `cost-center` e um valor de `cc123` a qualquer volume do EBS criado (neste caso, o volume do dispositivo raiz).

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --count 1 \
    --subnet-id subnet-08fc749671b2d077c \
    --key-name MyKeyPair \
    --security-group-ids sg-0b0384b66d7d692f9 \
    --tag-specifications
 'ResourceType=instance,Tags=[{Key=webserver,Value=production}]'
 'ResourceType=volume,Tags=[{Key=cost-center,Value=cc123}]'
```

Para obter um exemplo da saída de `run-instances`, consulte o Exemplo 1.

Exemplo 5: executar uma instância com dados do usuário

O exemplo `run-instances` a seguir passa dados do usuário em um arquivo chamado `my_script.txt` que contém um script de configuração para a sua instância. O script é executado na inicialização.

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --count 1 \
    --subnet-id subnet-08fc749671b2d077c \
    --key-name MyKeyPair \
    --security-group-ids sg-0b0384b66d7d692f9 \
    --user-data file://my_script.txt
```

Para obter um exemplo da saída de `run-instances`, consulte o Exemplo 1.

Para obter mais informações sobre dados do usuário da instância, consulte Trabalho com dados do usuário da instância no Guia do usuário do Amazon EC2.

Exemplo 6: executar uma instância de desempenho expansível

O exemplo `run-instances` a seguir executa uma instância t2.micro com a opção de crédito `unlimited`. Ao executar uma instância T2, se você não especificar a `--credit-specification`, o padrão é a opção de crédito `standard`. Ao executar uma instância T3, o padrão é a opção de crédito `unlimited`.

```
aws ec2 run-instances \
    --image-id ami-0abcdef1234567890 \
    --instance-type t2.micro \
    --count 1 \
    --subnet-id subnet-08fc749671b2d077c \
    --key-name MyKeyPair \
    --security-group-ids sg-0b0384b66d7d692f9 \
    --credit-specification CpuCredits=unlimited
```

Para obter um exemplo da saída de `run-instances`, consulte o Exemplo 1.

Para obter mais informações sobre instâncias de desempenho expansível, consulte Instâncias de desempenho expansível no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte RunInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.InstanceType;
import software.amazon.awssdk.services.ec2.model.RunInstancesRequest;
import software.amazon.awssdk.services.ec2.model.RunInstancesResponse;
import software.amazon.awssdk.services.ec2.model.Tag;
import software.amazon.awssdk.services.ec2.model.CreateTagsRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This code example requires an AMI value. You can learn more about this value
 * by reading this documentation topic:
 *
 * https://docs.aws.amazon.com/AWSEC2/latest/WindowsGuide/AMIs.html
 */
public class CreateInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <name> <amiId>

                Where:
```

```
                    name - An instance name value that you can obtain from the AWS
Console (for example, ami-xxxxxx5c8b987b1a0).\s
                    amiId - An Amazon Machine Image (AMI) value that you can
obtain from the AWS Console (for example, i-xxxxxx2734106d0ab).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String name = args[0];
        String amiId = args[1];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        String instanceId = createEC2Instance(ec2, name, amiId);
        System.out.println("The Amazon EC2 Instance ID is " + instanceId);
        ec2.close();
    }

    public static String createEC2Instance(Ec2Client ec2, String name, String
amiId) {
        RunInstancesRequest runRequest = RunInstancesRequest.builder()
                .imageId(amiId)
                .instanceType(InstanceType.T1_MICRO)
                .maxCount(1)
                .minCount(1)
                .build();

        RunInstancesResponse response = ec2.runInstances(runRequest);
        String instanceId = response.instances().get(0).instanceId();
        Tag tag = Tag.builder()
                .key("Name")
                .value(name)
                .build();

        CreateTagsRequest tagRequest = CreateTagsRequest.builder()
                .resources(instanceId)
                .tags(tag)
                .build();
```

```
        try {
            ec2.createTags(tagRequest);
            System.out.printf("Successfully started EC2 Instance %s based on AMI
 %s", instanceId, amiId);
            return instanceId;

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
}
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { RunInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Create a new EC2 instance.
export const main = async () => {
  const command = new RunInstancesCommand({
    // Your key pair name.
    KeyName: "KEY_PAIR_NAME",
    // Your security group.
    SecurityGroupIds: ["SECURITY_GROUP_ID"],
    // An x86_64 compatible image.
```

```
    ImageId: "ami-0001a0d1a04bfcc30",
    // An x86_64 compatible free-tier instance type.
    InstanceType: "t1.micro",
    // Ensure only 1 instance launches.
    MinCount: 1,
    MaxCount: 1,
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2Instance(name: String, amiId: String): String? {
    val request = RunInstancesRequest {
        imageId = amiId
        instanceType = InstanceType.T1Micro
        maxCount = 1
        minCount = 1
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.runInstances(request)
        val instanceId = response.instances?.get(0)?.instanceId
```

```
        val tag = Tag {
            key = "Name"
            value = name
        }

        val requestTags = CreateTagsRequest {
            resources = listOf(instanceId.toString())
            tags = listOf(tag)
        }
        ec2.createTags(requestTags)
        println("Successfully started EC2 Instance $instanceId based on AMI
 $amiId")
        return instanceId
    }
}
```

- Para obter detalhes da API, consulte a RunInstancesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
 that
                           wraps instance actions.
```

```
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, image, instance_type, key_pair, security_groups=None):
        """
        Creates a new EC2 instance. The instance starts immediately after
        it is created.

        The instance is created in the default VPC of the current account.

        :param image: A Boto3 Image object that represents an Amazon Machine
Image (AMI)
                      that defines attributes of the instance that is created.
The AMI
                      defines things like the kind of operating system and the
type of
                      storage used by the instance.
        :param instance_type: The type of instance to create, such as 't2.micro'.
                              The instance type defines things like the number of
CPUs and
                              the amount of memory.
        :param key_pair: A Boto3 KeyPair or KeyPairInfo object that represents
the key
                         pair that is used to secure connections to the instance.
        :param security_groups: A list of Boto3 SecurityGroup objects that
represents the
                                security groups that are used to grant access to
the
                                instance. When no security groups are specified,
the
                                default security group of the VPC is used.
        :return: A Boto3 Instance object that represents the newly created
instance.
        """
        try:
            instance_params = {
                "ImageId": image.id,
```

```
                "InstanceType": instance_type,
                "KeyName": key_pair.name,
            }
            if security_groups is not None:
                instance_params["SecurityGroupIds"] = [sg.id for sg in
security_groups]
            self.instance = self.ec2_resource.create_instances(
                **instance_params, MinCount=1, MaxCount=1
            )[0]
            self.instance.wait_until_running()
        except ClientError as err:
            logging.error(
                "Couldn't create instance with image %s, instance type %s, and
key %s. "
                "Here's why: %s: %s",
                image.id,
                instance_type,
                key_pair.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.instance
```

- Para obter detalhes da API, consulte a RunInstancesReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    " Create tags for resource created during instance launch. "
    DATA lt_tagspecifications TYPE /aws1/
cl_ec2tagspecification=>tt_tagspecificationlist.
    DATA ls_tagspecifications LIKE LINE OF lt_tagspecifications.
    ls_tagspecifications =  NEW /aws1/cl_ec2tagspecification(
      iv_resourcetype = 'instance'
      it_tags = VALUE /aws1/cl_ec2tag=>tt_taglist(
        ( NEW /aws1/cl_ec2tag( iv_key = 'Name' iv_value = iv_tag_value ) )
      )
    ).
    APPEND ls_tagspecifications TO lt_tagspecifications.

    TRY.
        " Create/launch Amazon Elastic Compute Cloud (Amazon EC2) instance. "
        oo_result = lo_ec2->runinstances(                           " oo_result
 is returned for testing purposes. "
          iv_imageid = iv_ami_id
          iv_instancetype = 't2.micro'
          iv_maxcount = 1
          iv_mincount = 1
          it_tagspecifications = lt_tagspecifications
          iv_subnetid = iv_subnet_id
        ).
        MESSAGE 'EC2 instance created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a RunInstancesreferência da API AWS SDK for SAP ABAP.

Exclua um modelo de execução do Amazon EC2 usando um SDK AWS

Os exemplos de código a seguir mostram como excluir um modelo de inicialização de sub-rede do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete a launch template by name.
/// </summary>
/// <param name="templateName">The name of the template to delete.</param>
/// <returns>Async task.</returns>
public async Task DeleteTemplateByName(string templateName)
{
    try
    {
        await _amazonEc2.DeleteLaunchTemplateAsync(
            new DeleteLaunchTemplateRequest()
            {
                LaunchTemplateName = templateName
            });
    }
    catch (AmazonClientException)
    {
        Console.WriteLine($"Unable to delete template {templateName}.");
    }
}
```

- Para obter detalhes da API, consulte DeleteLaunchTemplatea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para excluir um modelo de execução

Este exemplo exclui o modelo de execução especificado.

Comando:

```
aws ec2 delete-launch-template --launch-template-id lt-0abcd290751193123
```

Saída:

```
{
  "LaunchTemplate": {
      "LatestVersionNumber": 2,
      "LaunchTemplateId": "lt-0abcd290751193123",
      "LaunchTemplateName": "TestTemplate",
      "DefaultVersionNumber": 2,
      "CreatedBy": "arn:aws:iam::123456789012:root",
      "CreateTime": "2017-11-23T16:46:25.000Z"
  }
}
```

- Para obter detalhes da API, consulte DeleteLaunchTemplateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
```

```
        }),
      );
```

- Para obter detalhes da API, consulte DeleteLaunchTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
```

```
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
```

```
                    f"Couldn't delete launch template
{self.launch_template_name}: {err}."
                )
```

- Para obter detalhes da API, consulte a DeleteLaunchTemplateReferência da API AWSSDK for Python (Boto3).

Excluir um grupo de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um grupo de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteSecurityGroup(string groupId)
    {
        var response = await _amazonEC2.DeleteSecurityGroupAsync(new
DeleteSecurityGroupRequest { GroupId = groupId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DeleteSecurityGroupRequest request;

request.SetGroupId(securityGroupID);
auto outcome = ec2Client.DeleteSecurityGroup(request);

if (!outcome.IsSuccess()) {
    std::cerr << "Failed to delete security group " << securityGroupID <<
              ":" << outcome.GetError().GetMessage() << std::endl;
}
else {
    std::cout << "Successfully deleted security group " << securityGroupID <<
              std::endl;
}
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for C++ da API.

CLI

AWS CLI

[EC2-Classic] Para excluir um grupo de segurança

Este exemplo exclui o grupo de segurança chamado `MySecurityGroup`. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 delete-security-group --group-name MySecurityGroup
```

[EC2-VPC] Para excluir um grupo de segurança

Este exemplo exclui o grupo de segurança com o ID `sg-903004f8`. Não é possível fazer referência a um grupo de segurança do EC2-VPC por nome. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 delete-security-group --group-id sg-903004f8
```

Para obter mais informações, consulte Using Security Groups no Guia do usuário da AWS Command Line Interface.

- Para obter detalhes da API, consulte DeleteSecurityGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DeleteSecurityGroupRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteSecurityGroup {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <groupId>\s

                Where:
                   groupId - A security group id that you can obtain from the AWS
 Console (for example, sg-xxxxxx1c0b65785c3).""";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        deleteEC2SecGroup(ec2, groupId);
        ec2.close();
    }

    public static void deleteEC2SecGroup(Ec2Client ec2, String groupId) {
        try {
            DeleteSecurityGroupRequest request =
 DeleteSecurityGroupRequest.builder()
                    .groupId(groupId)
                    .build();

            ec2.deleteSecurityGroup(request);
            System.out.printf("Successfully deleted Security Group with id %s",
 groupId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSecurityGroupCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DeleteSecurityGroupCommand({
    GroupId: "GROUP_ID",
  });

  try {
    await client.send(command);
    console.log("Security group deleted successfully.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteEC2SecGroup(groupIdVal: String) {
    val request = DeleteSecurityGroupRequest {
        groupId = groupIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteSecurityGroup(request)
        println("Successfully deleted Security Group with id $groupIdVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""
```

```
    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def delete(self):
        """
        Deletes the security group.
        """
        if self.security_group is None:
            logger.info("No security group to delete.")
            return

        group_id = self.security_group.id
        try:
            self.security_group.delete()
        except ClientError as err:
            logger.error(
                "Couldn't delete security group %s. Here's why: %s: %s",
                group_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->deletesecuritygroup( iv_groupid = iv_security_group_id ).
        MESSAGE 'Security group deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupreferência da API AWS SDK for SAP ABAP.

Excluir um par de chaves de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um par de chaves de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyPair(string keyPairName)
    {
        try
        {
            await _amazonEC2.DeleteKeyPairAsync(new
DeleteKeyPairRequest(keyPairName)).ConfigureAwait(false);
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Couldn't delete the key pair because:
{ex.Message}");
            return false;
        }
    }

    /// <summary>
    /// Delete the temporary file where the key pair information was saved.
    /// </summary>
    /// <param name="tempFileName">The path to the temporary file.</param>
    public void DeleteTempFile(string tempFileName)
    {
        if (File.Exists(tempFileName))
        {
            File.Delete(tempFileName);
        }
    }
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   Aws::EC2::EC2Client ec2Client(clientConfiguration);
   Aws::EC2::Model::DeleteKeyPairRequest request;

   request.SetKeyName(keyPairName);
   const Aws::EC2::Model::DeleteKeyPairOutcome outcome =
ec2Client.DeleteKeyPair(
           request);

   if (!outcome.IsSuccess()) {
       std::cerr << "Failed to delete key pair " << keyPairName <<
                 ":" << outcome.GetError().GetMessage() << std::endl;
   }
   else {
       std::cout << "Successfully deleted key pair named " << keyPairName <<
                 std::endl;
   }
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para excluir um par de chaves

Este exemplo exclui o par de chaves chamado `MyKeyPair`. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 delete-key-pair --key-name MyKeyPair
```

Para obter mais informações, consulte Using Key Pairs no Guia do usuário da AWS Command Line Interface.

- Para obter detalhes da API, consulte DeleteKeyPairem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DeleteKeyPairRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteKeyPair {

    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                   <keyPair>\s

                Where:
                   keyPair - A key pair name (for example, TestKeyPair).""";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyPair = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        deleteKeys(ec2, keyPair);
        ec2.close();
    }

    public static void deleteKeys(Ec2Client ec2, String keyPair) {
        try {
            DeleteKeyPairRequest request = DeleteKeyPairRequest.builder()
                    .keyName(keyPair)
                    .build();

            ec2.deleteKeyPair(request);
            System.out.printf("Successfully deleted key pair named %s", keyPair);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteKeyPairCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DeleteKeyPairCommand({
    KeyName: "KEY_PAIR_NAME",
  });

  try {
    await client.send(command);
    console.log("Successfully deleted key pair.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteKeyPair a Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKeys(keyPair: String?) {
    val request = DeleteKeyPairRequest {
        keyName = keyPair
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteKeyPair(request)
        println("Successfully deleted key pair named $keyPair")
    }
}
```

- Para obter detalhes da API, consulte a DeleteKeyPairreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair
 actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is
 stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
```

```
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def delete(self):
        """
        Deletes a key pair.
        """
        if self.key_pair is None:
            logger.info("No key pair to delete.")
            return

        key_name = self.key_pair.name
        try:
            self.key_pair.delete()
            self.key_pair = None
        except ClientError as err:
            logger.error(
                "Couldn't delete key %s. Here's why: %s : %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteKeyPairReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->deletekeypair( iv_keyname = iv_key_name ).
        MESSAGE 'Amazon EC2 key pair deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteKeyPairreferência da API AWS SDK for SAP ABAP.

Excluir o snapshot do Amazon EBS usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um snapshot do Amazon EBS.

CLI

AWS CLI

Para excluir um snapshot

Este exemplo de comando exclui um snapshot com o ID de snapshot de `snap-1234567890abcdef0`. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 delete-snapshot --snapshot-id snap-1234567890abcdef0
```

- Para obter detalhes da API, consulte DeleteSnapshotem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn delete_snapshot(client: &Client, id: &str) -> Result<(), Error> {
    client.delete_snapshot().snapshot_id(id).send().await?;

    println!("Deleted");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteSnapshotreferência da API AWS SDK for Rust.

Descrever as zonas de disponibilidade da sua conta usando um AWS SDK

Os exemplos de código a seguir mostram como descrever as zonas de disponibilidade do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2
 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }
```

- Para obter detalhes da API, consulte DescribeAvailabilityZonesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::DescribeAvailabilityZonesRequest describe_request;
```

```
   auto describe_outcome =
ec2Client.DescribeAvailabilityZones(describe_request);

   if (describe_outcome.IsSuccess()) {
       std::cout << std::left <<
                 std::setw(32) << "ZoneName" <<
                 std::setw(20) << "State" <<
                 std::setw(32) << "Region" << std::endl;

       const auto &zones =
               describe_outcome.GetResult().GetAvailabilityZones();

       for (const auto &zone: zones) {
           Aws::String stateString =

Aws::EC2::Model::AvailabilityZoneStateMapper::GetNameForAvailabilityZoneState(
                           zone.GetState());
           std::cout << std::left <<
                     std::setw(32) << zone.GetZoneName() <<
                     std::setw(20) << stateString <<
                     std::setw(32) << zone.GetRegionName() << std::endl;
       }
   }
   else {
       std::cerr << "Failed to describe availability zones:" <<
                 describe_outcome.GetError().GetMessage() << std::endl;
       result = false;
   }
```

- Para obter detalhes da API, consulte DescribeAvailabilityZonesa Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Para descrever suas zonas de disponibilidade

O exemplo `describe-availability-zones` a seguir exibe detalhes das zonas de disponibilidade disponíveis para você. A resposta inclui zonas de disponibilidade somente

para a região atual. Neste exemplo, ela usa a região padrão dos perfis do `us-west-2` (Oregon).

```
aws ec2 describe-availability-zones
```

Saída:

```
{
    "AvailabilityZones": [
        {
            "State": "available",
            "OptInStatus": "opt-in-not-required",
            "Messages": [],
            "RegionName": "us-west-2",
            "ZoneName": "us-west-2a",
            "ZoneId": "usw2-az1",
            "GroupName": "us-west-2",
            "NetworkBorderGroup": "us-west-2"
        },
        {
            "State": "available",
            "OptInStatus": "opt-in-not-required",
            "Messages": [],
            "RegionName": "us-west-2",
            "ZoneName": "us-west-2b",
            "ZoneId": "usw2-az2",
            "GroupName": "us-west-2",
            "NetworkBorderGroup": "us-west-2"
        },
        {
            "State": "available",
            "OptInStatus": "opt-in-not-required",
            "Messages": [],
            "RegionName": "us-west-2",
            "ZoneName": "us-west-2c",
            "ZoneId": "usw2-az3",
            "GroupName": "us-west-2",
            "NetworkBorderGroup": "us-west-2"
        },
        {
            "State": "available",
            "OptInStatus": "opt-in-not-required",
            "Messages": [],
```

```
            "RegionName": "us-west-2",
            "ZoneName": "us-west-2d",
            "ZoneId": "usw2-az4",
            "GroupName": "us-west-2",
            "NetworkBorderGroup": "us-west-2"
        },
        {
            "State": "available",
            "OptInStatus": "opted-in",
            "Messages": [],
            "RegionName": "us-west-2",
            "ZoneName": "us-west-2-lax-1a",
            "ZoneId": "usw2-lax1-az1",
            "GroupName": "us-west-2-lax-1",
            "NetworkBorderGroup": "us-west-2-lax-1"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAvailabilityZonesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
```

```
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
```

```
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones
```

- Para obter detalhes da API, consulte a DescribeAvailabilityZonesReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeavailabilityzones( ) .
 " oo_result is returned for testing purposes. "
        DATA(lt_zones) = oo_result->get_availabilityzones( ).
        MESSAGE 'Retrieved information about Availability Zones.' TYPE 'I'.

      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAvailabilityZonesreferência da API AWS SDK for SAP ABAP.

Descreve as regiões da sua conta usando um AWS SDK

Os exemplos de código a seguir mostram como descrever as regiões do Amazon EC2.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::DescribeRegionsRequest request;
auto outcome = ec2Client.DescribeRegions(request);
bool result = true;
if (outcome.IsSuccess()) {
    std::cout << std::left <<
              std::setw(32) << "RegionName" <<
              std::setw(64) << "Endpoint" << std::endl;

    const auto &regions = outcome.GetResult().GetRegions();
    for (const auto &region: regions) {
        std::cout << std::left <<
                  std::setw(32) << region.GetRegionName() <<
                  std::setw(64) << region.GetEndpoint() << std::endl;
    }
}
else {
    std::cerr << "Failed to describe regions:" <<
              outcome.GetError().GetMessage() << std::endl;
    result = false;
}
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: descrever todas as suas regiões habilitadas

O exemplo `describe-regions` a seguir descreve todas as regiões habilitadas para a sua conta.

```
aws ec2 describe-regions
```

Saída:

```
{
    "Regions": [
        {
            "Endpoint": "ec2.eu-north-1.amazonaws.com",
            "RegionName": "eu-north-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-south-1.amazonaws.com",
            "RegionName": "ap-south-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-3.amazonaws.com",
            "RegionName": "eu-west-3",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-2.amazonaws.com",
            "RegionName": "eu-west-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-1.amazonaws.com",
            "RegionName": "eu-west-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-northeast-3.amazonaws.com",
            "RegionName": "ap-northeast-3",
```

```
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-northeast-2.amazonaws.com",
            "RegionName": "ap-northeast-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-northeast-1.amazonaws.com",
            "RegionName": "ap-northeast-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.sa-east-1.amazonaws.com",
            "RegionName": "sa-east-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ca-central-1.amazonaws.com",
            "RegionName": "ca-central-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-southeast-1.amazonaws.com",
            "RegionName": "ap-southeast-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-southeast-2.amazonaws.com",
            "RegionName": "ap-southeast-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-central-1.amazonaws.com",
            "RegionName": "eu-central-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-east-1.amazonaws.com",
            "RegionName": "us-east-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-east-2.amazonaws.com",
```

```
            "RegionName": "us-east-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-west-1.amazonaws.com",
            "RegionName": "us-west-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-west-2.amazonaws.com",
            "RegionName": "us-west-2",
            "OptInStatus": "opt-in-not-required"
        }
    ]
}
```

Para obter mais informações, consulte Regiões e zonas no Guia do usuário do Amazon EC2.

Exemplo 2: para descrever as regiões habilitadas com um endpoint cujo nome contém uma string específica

O exemplo `describe-regions` a seguir descreve todas as regiões que você habilitou e que têm a string “us” no endpoint.

```
aws ec2 describe-regions \
    --filters "Name=endpoint,Values=*us*"
```

Saída:

```
{
    "Regions": [
        {
            "Endpoint": "ec2.us-east-1.amazonaws.com",
            "RegionName": "us-east-1"
        },
        {
            "Endpoint": "ec2.us-east-2.amazonaws.com",
            "RegionName": "us-east-2"
        },
        {
            "Endpoint": "ec2.us-west-1.amazonaws.com",
            "RegionName": "us-west-1"
        },
```

```
        {
            "Endpoint": "ec2.us-west-2.amazonaws.com",
            "RegionName": "us-west-2"
        }
    ]
}
```

Para obter mais informações, consulte Regiões e zonas no Guia do usuário do Amazon EC2.

Exemplo 3: descrever todas as regiões

O exemplo `describe-regions` a seguir descreve todas as regiões disponíveis, incluindo as que estão desabilitadas.

```
aws ec2 describe-regions \
    --all-regions
```

Saída:

```
{
    "Regions": [
        {
            "Endpoint": "ec2.eu-north-1.amazonaws.com",
            "RegionName": "eu-north-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-south-1.amazonaws.com",
            "RegionName": "ap-south-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-3.amazonaws.com",
            "RegionName": "eu-west-3",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-2.amazonaws.com",
            "RegionName": "eu-west-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-west-1.amazonaws.com",
```

```
            "RegionName": "eu-west-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-northeast-3.amazonaws.com",
            "RegionName": "ap-northeast-3",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.me-south-1.amazonaws.com",
            "RegionName": "me-south-1",
            "OptInStatus": "not-opted-in"
        },
        {
            "Endpoint": "ec2.ap-northeast-2.amazonaws.com",
            "RegionName": "ap-northeast-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-northeast-1.amazonaws.com",
            "RegionName": "ap-northeast-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.sa-east-1.amazonaws.com",
            "RegionName": "sa-east-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ca-central-1.amazonaws.com",
            "RegionName": "ca-central-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.ap-east-1.amazonaws.com",
            "RegionName": "ap-east-1",
            "OptInStatus": "not-opted-in"
        },
        {
            "Endpoint": "ec2.ap-southeast-1.amazonaws.com",
            "RegionName": "ap-southeast-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
```

```
            "Endpoint": "ec2.ap-southeast-2.amazonaws.com",
            "RegionName": "ap-southeast-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.eu-central-1.amazonaws.com",
            "RegionName": "eu-central-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-east-1.amazonaws.com",
            "RegionName": "us-east-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-east-2.amazonaws.com",
            "RegionName": "us-east-2",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-west-1.amazonaws.com",
            "RegionName": "us-west-1",
            "OptInStatus": "opt-in-not-required"
        },
        {
            "Endpoint": "ec2.us-west-2.amazonaws.com",
            "RegionName": "us-west-2",
            "OptInStatus": "opt-in-not-required"
        }
    ]
}
```

Para obter mais informações, consulte Regiões e zonas no Guia do usuário do Amazon EC2.

Exemplo 4: listar somente os nomes das regiões

O exemplo `describe-regions` a seguir usa o parâmetro `--query` para filtrar a saída e retornar somente os nomes das regiões como texto.

```
aws ec2 describe-regions \
    --all-regions \
    --query "Regions[].{Name:RegionName}" \
    --output text
```

Saída:

```
eu-north-1
ap-south-1
eu-west-3
eu-west-2
eu-west-1
ap-northeast-3
ap-northeast-2
me-south-1
ap-northeast-1
sa-east-1
ca-central-1
ap-east-1
ap-southeast-1
ap-southeast-2
eu-central-1
us-east-1
us-east-2
us-west-1
us-west-2
```

Para obter mais informações, consulte Regiões e zonas no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeRegionsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeRegionsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";
```

```
export const main = async () => {
  const command = new DescribeRegionsCommand({
    // By default this command will not show regions that require you to opt-in.
    // When AllRegions true even the regions that require opt-in will be
 returned.
    AllRegions: true,
    // You can omit the Filters property if you want to get all regions.
    Filters: [
      {
        Name: "region-name",
        // You can specify multiple values for a filter.
        // You can also use '*' as a wildcard. This will return all
        // of the regions that start with `us-east-`.
        Values: ["ap-southeast-4"],
      },
    ],
  });

  try {
    const { Regions } = await client.send(command);
    const regionsList = Regions.map((reg) => ` • ${reg.RegionName}`);
    console.log("Found regions:");
    console.log(regionsList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   list_regions_endpoints(Aws::EC2::Client.new(region: 'us-west-2'))
def list_regions_endpoints(ec2_client)
  result = ec2_client.describe_regions
  # Enable pretty printing.
  max_region_string_length = 16
  max_endpoint_string_length = 33
  # Print header.
  print "Region"
  print " " * (max_region_string_length - "Region".length)
  print "  Endpoint\n"
  print "-" * max_region_string_length
  print "  "
  print "-" * max_endpoint_string_length
  print "\n"
  # Print Regions and their endpoints.
  result.regions.each do |region|
    print region.region_name
    print " " * (max_region_string_length - region.region_name.length)
    print "  "
    print region.endpoint
    print "\n"
  end
end

# Displays a list of Amazon Elastic Compute Cloud (Amazon EC2)
# Availability Zones available to you depending on the AWS Region
# of the Amazon EC2 client.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   list_availability_zones(Aws::EC2::Client.new(region: 'us-west-2'))
def list_availability_zones(ec2_client)
  result = ec2_client.describe_availability_zones
  # Enable pretty printing.
  max_region_string_length = 16
  max_zone_string_length = 18
  max_state_string_length = 9
  # Print header.
```

```
  print "Region"
  print " " * (max_region_string_length - "Region".length)
  print "  Zone"
  print " " * (max_zone_string_length - "Zone".length)
  print "  State\n"
  print "-" * max_region_string_length
  print "  "
  print "-" * max_zone_string_length
  print "  "
  print "-" * max_state_string_length
  print "\n"
  # Print Regions, Availability Zones, and their states.
  result.availability_zones.each do |zone|
    print zone.region_name
    print " " * (max_region_string_length - zone.region_name.length)
    print "  "
    print zone.zone_name
    print " " * (max_zone_string_length - zone.zone_name.length)
    print "  "
    print zone.state
    # Print any messages for this Availability Zone.
    if zone.messages.count.positive?
      print "\n"
      puts "  Messages for this zone:"
      zone.messages.each do |message|
        print "    #{message.message}\n"
      end
    end
    print "\n"
  end
end

# Example usage:
def run_me
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-regions-availability-zones.rb REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-regions-availability-zones.rb us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
```

```
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    region = ARGV[0]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "AWS Regions for Amazon EC2 that are available to you:"
  list_regions_endpoints(ec2_client)
  puts "\n\nAmazon EC2 Availability Zones that are available to you for AWS
 Region '#{region}':"
  list_availability_zones(ec2_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_regions(client: &Client) -> Result<(), Error> {
    let rsp = client.describe_regions().send().await?;

    println!("Regions:");
    for region in rsp.regions() {
        println!("  {}", region.region_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeRegionsreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeregions( ) .                        "
 oo_result is returned for testing purposes. "
        DATA(lt_regions) = oo_result->get_regions( ).
        MESSAGE 'Retrieved information about Regions.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeRegionsreferência da API AWS SDK for SAP ABAP.

Descreve o status das instâncias do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como descrever o status de instâncias do Amazon EC2.

CLI

AWS CLI

Para descrever o status de uma instância

O exemplo `describe-instance-status` a seguir descreve o status atual da instância especificada.

```
aws ec2 describe-instance-status \
    --instance-ids i-1234567890abcdef0
```

Saída:

```
{
    "InstanceStatuses": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "InstanceState": {
                "Code": 16,
                "Name": "running"
            },
            "AvailabilityZone": "us-east-1d",
            "SystemStatus": {
                "Status": "ok",
                "Details": [
                    {
                        "Status": "passed",
                        "Name": "reachability"
                    }
                ]
            },
            "InstanceStatus": {
                "Status": "ok",
                "Details": [
                    {
                        "Status": "passed",
                        "Name": "reachability"
                    }
                ]
            }
        }
    ]
}
```

Para obter mais informações, consulte Monitorar o status das instâncias no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeInstanceStatusem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_all_events(client: &Client) -> Result<(), Error> {
    let resp = client.describe_regions().send().await.unwrap();

    for region in resp.regions.unwrap_or_default() {
        let reg: &'static str =
 Box::leak(Box::from(region.region_name().unwrap()));
        let region_provider =
 RegionProviderChain::default_provider().or_else(reg);
        let config = aws_config::from_env().region(region_provider).load().await;
        let new_client = Client::new(&config);

        let resp = new_client.describe_instance_status().send().await;

        println!("Instances in region {}:", reg);
        println!();

        for status in resp.unwrap().instance_statuses() {
            println!(
                "  Events scheduled for instance ID: {}",
                status.instance_id().unwrap_or_default()
            );
            for event in status.events() {
                println!("    Event ID:     {}",
 event.instance_event_id().unwrap());
                println!("    Description:  {}", event.description().unwrap());
                println!("    Event code:   {}", event.code().unwrap().as_ref());
                println!();
            }
```

```
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeInstanceStatusreferência da API AWS SDK for Rust.

Descrever instâncias do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como descrever instâncias do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e gerenciar um serviço resiliente
- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about existing EC2 images.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task DescribeInstances()
    {
        // List all EC2 instances.
        await GetInstanceDescriptions();

        string tagName = "IncludeInList";
```

```
        string tagValue = "Yes";
        await GetInstanceDescriptionsFiltered(tagName, tagValue);
    }

    /// <summary>
    /// Get information for all existing Amazon EC2 instances.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptions()
    {
        Console.WriteLine("Showing all instances:");
        var paginator = _amazonEC2.Paginators.DescribeInstances(new
 DescribeInstancesRequest());

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId}");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Get information about EC2 instances filtered by a tag name and value.
    /// </summary>
    /// <param name="tagName">The name of the tag to filter on.</param>
    /// <param name="tagValue">The value of the tag to look for.</param>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptionsFiltered(string tagName, string
 tagValue)
    {
        // This tag filters the results of the instance list.
        var filters = new List<Filter>
        {
            new Filter
            {
                Name = $"tag:{tagName}",
                Values = new List<string>
                {
```

```
                    tagValue,
                },
            },
        };
        var request = new DescribeInstancesRequest
        {
            Filters = filters,
        };

        Console.WriteLine("\nShowing instances with tag: \"IncludeInList\" set to
\"Yes\".");
        var paginator = _amazonEC2.Paginators.DescribeInstances(request);

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId} ");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
```

```
    Aws::EC2::Model::DescribeInstancesRequest request;
    bool header = false;
    bool done = false;
    while (!done) {
        auto outcome = ec2Client.DescribeInstances(request);
        if (outcome.IsSuccess()) {
            if (!header) {
                std::cout << std::left <<
                          std::setw(48) << "Name" <<
                          std::setw(20) << "ID" <<
                          std::setw(25) << "Ami" <<
                          std::setw(15) << "Type" <<
                          std::setw(15) << "State" <<
                          std::setw(15) << "Monitoring" << std::endl;
                header = true;
            }

            const std::vector<Aws::EC2::Model::Reservation> &reservations =
                    outcome.GetResult().GetReservations();

            for (const auto &reservation: reservations) {
                const std::vector<Aws::EC2::Model::Instance> &instances =
                        reservation.GetInstances();
                for (const auto &instance: instances) {
                    Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                    instance.GetState().GetName());

                    Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                    instance.GetInstanceType());

                    Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                    instance.GetMonitoring().GetState());
                    Aws::String name = "Unknown";

                    const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                    auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
```

```
                                                    [](const Aws::EC2::Model::Tag
&tag) {
                                                            return tag.GetKey() ==
"Name";
                                                    });
                    if (nameIter != tags.cend()) {
                        name = nameIter->GetValue();
                    }
                    std::cout <<
                              std::setw(48) << name <<
                              std::setw(20) << instance.GetInstanceId() <<
                              std::setw(25) << instance.GetImageId() <<
                              std::setw(15) << typeString <<
                              std::setw(15) << instanceStateString <<
                              std::setw(15) << monitorString << std::endl;
                }
            }

            if (!outcome.GetResult().GetNextToken().empty()) {
                request.SetNextToken(outcome.GetResult().GetNextToken());
            }
            else {
                done = true;
            }
        }
        else {
            std::cerr << "Failed to describe EC2 instances:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: descrever uma instância

O exemplo `describe-instances` a seguir descreve a instância especificada.

```
aws ec2 describe-instances \
    --instance-ids i-1234567890abcdef0
```

Saída:

```
{
    "Reservations": [
        {
            "Groups": [],
            "Instances": [
                {
                    "AmiLaunchIndex": 0,
                    "ImageId": "ami-0abcdef1234567890",
                    "InstanceId": "i-1234567890abcdef0",
                    "InstanceType": "t3.nano",
                    "KeyName": "my-key-pair",
                    "LaunchTime": "2022-11-15T10:48:59+00:00",
                    "Monitoring": {
                        "State": "disabled"
                    },
                    "Placement": {
                        "AvailabilityZone": "us-east-2a",
                        "GroupName": "",
                        "Tenancy": "default"
                    },
                    "PrivateDnsName": "ip-10-0-0-157.us-east-2.compute.internal",
                    "PrivateIpAddress": "10-0-0-157",
                    "ProductCodes": [],
                    "PublicDnsName": "ec2-34-253-223-13.us-
east-2.compute.amazonaws.com",
                    "PublicIpAddress": "34.253.223.13",
                    "State": {
                        "Code": 16,
                        "Name": "running"
                    },
                    "StateTransitionReason": "",
                    "SubnetId": "subnet-04a636d18e83cfacb",
                    "VpcId": "vpc-1234567890abcdef0",
                    "Architecture": "x86_64",
                    "BlockDeviceMappings": [
                        {
                            "DeviceName": "/dev/xvda",
                            "Ebs": {
```

```
                                "AttachTime": "2022-11-15T10:49:00+00:00",
                                "DeleteOnTermination": true,
                                "Status": "attached",
                                "VolumeId": "vol-02e6ccdca7de29cf2"
                            }
                        }
                    ],
                    "ClientToken": "1234abcd-1234-abcd-1234-d46a8903e9bc",
                    "EbsOptimized": true,
                    "EnaSupport": true,
                    "Hypervisor": "xen",
                    "IamInstanceProfile": {
                        "Arn": "arn:aws:iam::111111111111:instance-profile/
AmazonSSMRoleForInstancesQuickSetup",
                        "Id": "11111111111111111111"
                    },
                    "NetworkInterfaces": [
                        {
                            "Association": {
                                "IpOwnerId": "amazon",
                                "PublicDnsName": "ec2-34-253-223-13.us-
east-2.compute.amazonaws.com",
                                "PublicIp": "34.253.223.13"
                            },
                            "Attachment": {
                                "AttachTime": "2022-11-15T10:48:59+00:00",
                                "AttachmentId": "eni-attach-1234567890abcdefg",
                                "DeleteOnTermination": true,
                                "DeviceIndex": 0,
                                "Status": "attached",
                                "NetworkCardIndex": 0
                            },
                            "Description": "",
                            "Groups": [
                                {
                                    "GroupName": "launch-wizard-146",
                                    "GroupId": "sg-1234567890abcdefg"
                                }
                            ],
                            "Ipv6Addresses": [],
                            "MacAddress": "00:11:22:33:44:55",
                            "NetworkInterfaceId": "eni-1234567890abcdefg",
                            "OwnerId": "104024344472",
```

```
                            "PrivateDnsName": "ip-10-0-0-157.us-
east-2.compute.internal",
                            "PrivateIpAddress": "10-0-0-157",
                            "PrivateIpAddresses": [
                                {
                                    "Association": {
                                        "IpOwnerId": "amazon",
                                        "PublicDnsName": "ec2-34-253-223-13.us-
east-2.compute.amazonaws.com",
                                        "PublicIp": "34.253.223.13"
                                    },
                                    "Primary": true,
                                    "PrivateDnsName": "ip-10-0-0-157.us-
east-2.compute.internal",
                                    "PrivateIpAddress": "10-0-0-157"
                                }
                            ],
                            "SourceDestCheck": true,
                            "Status": "in-use",
                            "SubnetId": "subnet-1234567890abcdefg",
                            "VpcId": "vpc-1234567890abcdefg",
                            "InterfaceType": "interface"
                        }
                    ],
                    "RootDeviceName": "/dev/xvda",
                    "RootDeviceType": "ebs",
                    "SecurityGroups": [
                        {
                            "GroupName": "launch-wizard-146",
                            "GroupId": "sg-1234567890abcdefg"
                        }
                    ],
                    "SourceDestCheck": true,
                    "Tags": [
                        {
                            "Key": "Name",
                            "Value": "my-instance"
                        }
                    ],
                    "VirtualizationType": "hvm",
                    "CpuOptions": {
                        "CoreCount": 1,
                        "ThreadsPerCore": 2
                    },
```

```
                    "CapacityReservationSpecification": {
                        "CapacityReservationPreference": "open"
                    },
                    "HibernationOptions": {
                        "Configured": false
                    },
                    "MetadataOptions": {
                        "State": "applied",
                        "HttpTokens": "optional",
                        "HttpPutResponseHopLimit": 1,
                        "HttpEndpoint": "enabled",
                        "HttpProtocolIpv6": "disabled",
                        "InstanceMetadataTags": "enabled"
                    },
                    "EnclaveOptions": {
                        "Enabled": false
                    },
                    "PlatformDetails": "Linux/UNIX",
                    "UsageOperation": "RunInstances",
                    "UsageOperationUpdateTime": "2022-11-15T10:48:59+00:00",
                    "PrivateDnsNameOptions": {
                        "HostnameType": "ip-name",
                        "EnableResourceNameDnsARecord": true,
                        "EnableResourceNameDnsAAAARecord": false
                    },
                    "MaintenanceOptions": {
                        "AutoRecovery": "default"
                    }
                }
            ],
            "OwnerId": "111111111111",
            "ReservationId": "r-1234567890abcdefg"
        }
    ]
}
```

Exemplo 2: para filtrar instâncias com o tipo especificado

O exemplo `describe-instances` a seguir usa filtros para definir o escopo dos resultados para instâncias do tipo especificado.

```
aws ec2 describe-instances \
    --filters Name=instance-type,Values=m5.large
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Para obter mais informações, consulte Listar e filtrar usando a CLI no Guia do usuário do Amazon EC2.

Exemplo 3: filtrar instâncias com o tipo e a zona de disponibilidade especificados

O exemplo `describe-instances` a seguir usa vários filtros para definir o escopo dos resultados para instâncias com o tipo especificado que também estão na zona de disponibilidade especificada.

```
aws ec2 describe-instances \
    --filters Name=instance-type,Values=t2.micro,t3.micro Name=availability-
zone,Values=us-east-2c
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Exemplo 4: filtrar instâncias com o tipo e a zona de disponibilidade especificados usando um arquivo JSON

O exemplo `describe-instances` a seguir usa um arquivo de entrada JSON para realizar a mesma filtragem do exemplo anterior. Quando os filtros ficam mais complicados, pode ser mais fácil especificá-los em um arquivo JSON.

```
aws ec2 describe-instances \
    --filters file://filters.json
```

Conteúdo de `filters.json`:

```
[
    {
        "Name": "instance-type",
        "Values": ["t2.micro", "t3.micro"]
    },
    {
        "Name": "availability-zone",
        "Values": ["us-east-2c"]
    }
]
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Exemplo 5: filtrar instâncias com a tag Proprietário especificada

O exemplo `describe-instances` a seguir usa filtros de tag para definir o escopo dos resultados para instâncias que têm uma tag com a chave de tag especificada (Proprietário), independentemente do valor da tag.

```
aws ec2 describe-instances \
    --filters "Name=tag-key,Values=Owner"
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Exemplo 6: filtrar instâncias com o valor especificado my-team da tag

O exemplo `describe-instances` a seguir usa filtros de tag para definir o escopo dos resultados para instâncias que têm uma tag com o valor especificado da tag (my-team), independentemente da chave da tag.

```
aws ec2 describe-instances \
    --filters "Name=tag-value,Values=my-team"
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Exemplo 7: filtrar instâncias com a tag Proprietário e o valor my-team especificados

O exemplo `describe-instances` a seguir usa filtros de tag para definir o escopo dos resultados para instâncias que têm a tag especificada (Owner=my-team).

```
aws ec2 describe-instances \
    --filters "Name=tag:Owner,Values=my-team"
```

Para obter um exemplo da saída, consulte o Exemplo 1.

Exemplo 8: exibir somente IDs de instância e sub-rede de todas as instâncias

Os exemplos `describe-instances` a seguir usam o parâmetro `--query` para exibir somente os IDs de instância e sub-rede de todas as instâncias, no formato JSON.

Linux e macOS:

```
aws ec2 describe-instances \
    --query 'Reservations[*].Instances[*].{Instance:InstanceId,Subnet:SubnetId}'
 \
```

```
    --output json
```

Windows:

```
aws ec2 describe-instances ^
    --query "Reservations[*].Instances[*].{Instance:InstanceId,Subnet:SubnetId}"
 ^
    --output json
```

Saída:

```
[
    {
        "Instance": "i-057750d42936e468a",
        "Subnet": "subnet-069beee9b12030077"
    },
    {
        "Instance": "i-001efd250faaa6ffa",
        "Subnet": "subnet-0b715c6b7db68927a"
    },
    {
        "Instance": "i-027552a73f021f3bd",
        "Subnet": "subnet-0250c25a1f4e15235"
    }
    ...
]
```

Exemplo 9: filtrar instâncias do tipo especificado e exibir somente os IDs de instância

O exemplo `describe-instances` a seguir usa filtros para definir o escopo dos resultados para instâncias do tipo especificado e o parâmetro `--query` para exibir somente os IDs da instância.

```
aws ec2 describe-instances \
    --filters "Name=instance-type,Values=t2.micro" \
    --query "Reservations[*].Instances[*].[InstanceId]" \
    --output text
```

Saída:

```
i-031c0dc19de2fb70c
i-00d8bff789a736b75
```

```
i-0b715c6b7db68927a
i-0626d4edd54f1286d
i-00b8ae04f9f99908e
i-0fc71c25d2374130c
```

Exemplo 10: filtrar instâncias do tipo especificado e exibir somente os IDs de instância, a zona de disponibilidade e o valor especificado da tag

Os exemplos `describe-instances` a seguir exibem o ID da instância, a zona de disponibilidade e o valor da tag `Name` para instâncias que têm uma tag com o nome `tag-key`, em formato de tabela.

Linux e macOS:

```
aws ec2 describe-instances \
    --filters Name=tag-key,Values=Name \
    --query 'Reservations[*].Instances[*].
{Instance:InstanceId,AZ:Placement.AvailabilityZone,Name:Tags[?Key==`Name`]|
[0].Value}' \
    --output table
```

Windows:

```
aws ec2 describe-instances ^
    --filters Name=tag-key,Values=Name ^
    --query "Reservations[*].Instances[*].
{Instance:InstanceId,AZ:Placement.AvailabilityZone,Name:Tags[?Key=='Name']|
[0].Value}" ^
    --output table
```

Saída:

```
-------------------------------------------------------------
|                     DescribeInstances                     |
+--------------+-----------------------+--------------------+
|      AZ      |       Instance        |        Name        |
+--------------+-----------------------+--------------------+
|  us-east-2b  |  i-057750d42936e468a  |  my-prod-server    |
|  us-east-2a  |  i-001efd250faaa6ffa  |  test-server-1     |
|  us-east-2a  |  i-027552a73f021f3bd  |  test-server-2     |
+--------------+-----------------------+--------------------+
```

Exemplo 11: descrever instâncias em um grupo com posicionamento em partições

O exemplo `describe-instances` a seguir descreve a instância especificada. A saída inclui as informações de posicionamento da instância, o que contém o nome do grupo de posicionamento e o número da partição da instância.

```
aws ec2 describe-instances \
    --instance-ids i-0123a456700123456 \
    --query "Reservations[*].Instances[*].Placement"
```

Saída:

```
[
    [
        {
            "AvailabilityZone": "us-east-1c",
            "GroupName": "HDFS-Group-A",
            "PartitionNumber": 3,
            "Tenancy": "default"
        }

    ]
]
```

Para obter mais informações, consulte Descrever instâncias em um grupo de posicionamento no Guia do usuário do Amazon EC2.

Exemplo 12: filtrar instâncias com o grupo de posicionamento e o número de partição especificados

O exemplo `describe-instances` a seguir filtra os resultados somente para as instâncias com o grupo de posicionamento e o número de partição especificados.

```
aws ec2 describe-instances \
    --filters "Name=placement-group-name,Values=HDFS-Group-A" "Name=placement-
partition-number,Values=7"
```

A seguir, são mostradas somente as informações relevantes da saída.

```
"Instances": [
    {
```

```
        "InstanceId": "i-0123a456700123456",
        "InstanceType": "r4.large",
        "Placement": {
            "AvailabilityZone": "us-east-1c",
            "GroupName": "HDFS-Group-A",
            "PartitionNumber": 7,
            "Tenancy": "default"
        }
    },
    {
        "InstanceId": "i-9876a543210987654",
        "InstanceType": "r4.large",
        "Placement": {
            "AvailabilityZone": "us-east-1c",
            "GroupName": "HDFS-Group-A",
            "PartitionNumber": 7,
            "Tenancy": "default"
        }
    ],
```

Para obter mais informações, consulte Descrever instâncias em um grupo de posicionamento no Guia do usuário do Amazon EC2.

Exemplo 13: filtrar instâncias configuradas para permitir o acesso às tags dos metadados da instância

O exemplo `describe-instances` a seguir filtra os resultados somente para as instâncias que estão configuradas para permitir o acesso às tags de instância nos metadados da instância.

```
aws ec2 describe-instances \
    --filters "Name=metadata-options.instance-metadata-tags,Values=enabled" \
    --query "Reservations[*].Instances[*].InstanceId" \
    --output text
```

A saída esperada é mostrada a seguir.

```
i-1234567890abcdefg
i-abcdefg1234567890
i-11111111aaaaaaaaa
i-aaaaaaaa111111111
```

Para obter mais informações, consulte Work with instance tags in instance metadata no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String describeEC2Instances(Ec2Client ec2, String
newInstanceId) {
       try {
           String pubAddress = "";
           boolean isRunning = false;
           DescribeInstancesRequest request = DescribeInstancesRequest.builder()
                   .instanceIds(newInstanceId)
                   .build();

           while (!isRunning) {
               DescribeInstancesResponse response =
ec2.describeInstances(request);
               String state =
response.reservations().get(0).instances().get(0).state().name().name();
               if (state.compareTo("RUNNING") == 0) {
                   System.out.println("Image id is " +
response.reservations().get(0).instances().get(0).imageId());
                   System.out.println(
                           "Instance type is " +
response.reservations().get(0).instances().get(0).instanceType());
                   System.out.println(
                           "Instance state is " +
response.reservations().get(0).instances().get(0).state().name());
                   pubAddress =
response.reservations().get(0).instances().get(0).publicIpAddress();
                   System.out.println("Instance address is " + pubAddress);
```

```
                    isRunning = true;
                }
            }
            return pubAddress;
        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List all of your EC2 instances running with x86_64 architecture that were
// launched this month.
export const main = async () => {
  const d = new Date();
  const year = d.getFullYear();
  const month = `0${d.getMonth() + 1}`.slice(-2);
  const launchTimePattern = `${year}-${month}-*`;
  const command = new DescribeInstancesCommand({
    Filters: [
      { Name: "architecture", Values: ["x86_64"] },
      { Name: "instance-state-name", Values: ["running"] },
      {
```

```
        Name: "launch-time",
        Values: [launchTimePattern],
      },
    ],
  });

  try {
    const { Reservations } = await client.send(command);
    const instanceList = Reservations.reduce((prev, current) => {
      return prev.concat(current.Instances);
    }, []);

    console.log(instanceList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2Instances() {
    val request = DescribeInstancesRequest {
        maxResults = 6
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstances(request)
        response.reservations?.forEach { reservation ->
            reservation.instances?.forEach { instance ->
```

```
                println("Instance Id is ${instance.instanceId}")
                println("Image id is ${instance.imageId}")
                println("Instance type is ${instance.instanceType}")
                println("Instance state name is ${instance.state?.name}")
                println("monitoring information is
 ${instance.monitoring?.state}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
 that
                            wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance
```

```
    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def display(self, indent=1):
        """
        Displays information about an instance.

        :param indent: The visual indent to apply to the output.
        """
        if self.instance is None:
            logger.info("No instance to display.")
            return

        try:
            self.instance.load()
            ind = "\t" * indent
            print(f"{ind}ID: {self.instance.id}")
            print(f"{ind}Image ID: {self.instance.image_id}")
            print(f"{ind}Instance type: {self.instance.instance_type}")
            print(f"{ind}Key name: {self.instance.key_name}")
            print(f"{ind}VPC ID: {self.instance.vpc_id}")
            print(f"{ind}Public IP: {self.instance.public_ip_address}")
            print(f"{ind}State: {self.instance.state['Name']}")
        except ClientError as err:
            logger.error(
                "Couldn't display your instance. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DescribeInstancesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# @param ec2_resource [Aws::EC2::Resource] An initialized EC2 resource object.
# @example
#   list_instance_ids_states(Aws::EC2::Resource.new(region: 'us-west-2'))
def list_instance_ids_states(ec2_resource)
  response = ec2_resource.instances
  if response.count.zero?
    puts "No instances found."
  else
    puts "Instances -- ID, state:"
    response.each do |instance|
      puts "#{instance.id}, #{instance.state.name}"
    end
  end
rescue StandardError => e
  puts "Error getting information about instances: #{e.message}"
end

# Example usage:
def run_me
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-get-all-instance-info.rb REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-get-all-instance-info.rb us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
```

```
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    region = ARGV[0]
  end
  ec2_resource = Aws::EC2::Resource.new(region: region)
  list_instance_ids_states(ec2_resource)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_state(client: &Client, ids: Option<Vec<String>>) -> Result<(),
 Error> {
    let resp = client
        .describe_instances()
        .set_instance_ids(ids)
        .send()
        .await?;

    for reservation in resp.reservations() {
        for instance in reservation.instances() {
            println!("Instance ID: {}", instance.instance_id().unwrap());
            println!(
                "State:       {:?}",
                instance.state().unwrap().name().unwrap()
            );
            println!();
```

```
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeinstances( ) .                        "
oo_result is returned for testing purposes. "

        " Retrieving details of EC2 instances. "
        DATA: lv_istance_id    TYPE /aws1/ec2string,
              lv_status        TYPE /aws1/ec2instancestatename,
              lv_instance_type TYPE /aws1/ec2instancetype,
              lv_image_id      TYPE /aws1/ec2string.
        LOOP AT oo_result->get_reservations( ) INTO DATA(lo_reservation).
          LOOP AT lo_reservation->get_instances( ) INTO DATA(lo_instance).
            lv_istance_id = lo_instance->get_instanceid( ).
            lv_status =  lo_instance->get_state( )->get_name( ).
            lv_instance_type = lo_instance->get_instancetype( ).
            lv_image_id = lo_instance->get_imageid( ).
          ENDLOOP.
        ENDLOOP.
        MESSAGE 'Retrieved information about EC2 instances.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
```

```
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWS SDK for SAP ABAP.

Descrever um ou mais snapshots do Amazon EBS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever snapshots do Amazon EBS.

CLI

AWS CLI

Exemplo 1: descrever um snapshot

O exemplo `describe-snapshots` a seguir descreve o snapshot especificado.

```
aws ec2 describe-snapshots \
    --snapshot-ids snap-1234567890abcdef0
```

Saída:

```
{
    "Snapshots": [
        {
            "Description": "This is my snapshot",
            "Encrypted": false,
            "VolumeId": "vol-049df61146c4d7901",
            "State": "completed",
            "VolumeSize": 8,
            "StartTime": "2019-02-28T21:28:32.000Z",
            "Progress": "100%",
            "OwnerId": "012345678910",
            "SnapshotId": "snap-01234567890abcdef",
            "Tags": [
                {
                    "Key": "Stack",
                    "Value": "test"
                }
            ]
```

```
        }
    ]
}
```

Para obter mais informações, consulte Snapshots do Amazon EBS no Guia do usuário do Amazon EC2.

Exemplo 2: descrever snapshots com base em filtros

O exemplo `describe-snapshots` a seguir usa filtros para definir o escopo dos resultados para snapshots pertencentes à sua conta da AWS que estão no estado `pending`. O exemplo usa o parâmetro `--query` para exibir somente os IDs do snapshot e a hora em que o snapshot foi iniciado.

```
aws ec2 describe-snapshots \
    --owner-ids self \
    --filters Name=status,Values=pending \
    --query "Snapshots[*].{ID:SnapshotId,Time:StartTime}"
```

Saída:

```
[
    {
        "ID": "snap-1234567890abcdef0",
        "Time": "2019-08-04T12:48:18.000Z"
    },
    {
        "ID": "snap-066877671789bd71b",
        "Time": "2019-08-04T02:45:16.000Z
    },
    ...
]
```

O exemplo `describe-snapshots` a seguir usa filtros para definir o escopo dos resultados para snapshots criados no volume especificado. O exemplo usa o parâmetro `--query` para exibir somente os IDs do snapshot.

```
aws ec2 describe-snapshots \
    --filters Name=volume-id,Values=049df61146c4d7901 \
    --query "Snapshots[*].[SnapshotId]" \
    --output text
```

Saída:

```
snap-1234567890abcdef0
snap-08637175a712c3fb9
...
```

Para obter mais exemplos do uso de filtros, consulte Listar e filtrar seus recursos no Guia do usuário do Amazon EC2.

Exemplo 3: descrever snapshots com base em tags

O exemplo `describe-snapshots` a seguir usa filtros de tag para definir o escopo dos resultados para snapshots que tenham a tag `Stack=Prod`.

```
aws ec2 describe-snapshots \
    --filters Name=tag:Stack,Values=prod
```

Para obter um exemplo da saída de `describe-snapshots`, consulte o Exemplo 1.

Para obter mais exemplos do uso de filtros de tags, consulte Trabalhando com tags no Guia do usuário do Amazon EC2.

Exemplo 4: descrever snapshots com base na idade

O exemplo `describe-snapshots` a seguir usa expressões JMESPath para descrever todos os snapshots criados pela sua conta da AWS antes da data especificada. Ele exibe somente os IDs do snapshot.

```
aws ec2 describe-snapshots \
    --owner-ids 012345678910 \
    --query "Snapshots[?(StartTime<='2020-03-31')].[SnapshotId]"
```

Para obter mais exemplos do uso de filtros, consulte Listar e filtrar seus recursos no Guia do usuário do Amazon EC2.

Exemplo 5: visualizar somente snapshots arquivados

O exemplo `describe-snapshots` a seguir lista apenas os snapshots armazenados no nível de arquivamento.

```
aws ec2 describe-snapshots \
```

```
    --filters "Name=storage-tier,Values=archive"
```

Saída:

```
{
    "Snapshots": [
        {
            "Description": "Snap A",
            "Encrypted": false,
            "VolumeId": "vol-01234567890aaaaaa",
            "State": "completed",
            "VolumeSize": 8,
            "StartTime": "2021-09-07T21:00:00.000Z",
            "Progress": "100%",
            "OwnerId": "123456789012",
            "SnapshotId": "snap-01234567890aaaaaa",
            "StorageTier": "archive",
            "Tags": []
        },
    ]
}
```

Para obter mais informações, consulte View archived snapshots no Guia do usuário do Amazon Elastic Compute Cloud.

- Para obter detalhes da API, consulte DescribeSnapshotsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Mostra o estado de um snapshot.

```
async fn show_state(client: &Client, id: &str) -> Result<(), Error> {
```

```
    let resp = client
        .describe_snapshots()
        .filters(Filter::builder().name("snapshot-id").values(id).build())
        .send()
        .await?;

    println!(
        "State: {}",
        resp.snapshots().first().unwrap().state().unwrap().as_ref()
    );

    Ok(())
}
```

```
async fn show_snapshots(client: &Client) -> Result<(), Error> {
    // "self" represents your account ID.
    // You can list the snapshots for any account by replacing
    // "self" with that account ID.
    let resp = client.describe_snapshots().owner_ids("self").send().await?;
    let snapshots = resp.snapshots();
    let length = snapshots.len();

    for snapshot in snapshots {
        println!(
            "ID:          {}",
            snapshot.snapshot_id().unwrap_or_default()
        );
        println!(
            "Description: {}",
            snapshot.description().unwrap_or_default()
        );
        println!("State:       {}", snapshot.state().unwrap().as_ref());
        println!();
    }

    println!();
    println!("Found {} snapshot(s)", length);
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeSnapshotsreferência da API AWS SDK for Rust.

Desabilitar o monitoramento detalhado de uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como desabilitar o monitoramento detalhado em uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::UnmonitorInstancesRequest unrequest;
    unrequest.AddInstanceIds(instanceId);
    unrequest.SetDryRun(true);

    auto undryRunOutcome = ec2Client.UnmonitorInstances(unrequest);
    if (undryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to disable monitoring on instance. A dry run
should trigger an error."
                <<
                std::endl;
        return false;
    }
    else if (undryRunOutcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
```

```
        std::cout << "Failed dry run to disable monitoring on instance " <<
                  instanceId << ": " << undryRunOutcome.GetError().GetMessage()
 <<
                  std::endl;
        return false;
    }

    unrequest.SetDryRun(false);
    auto unmonitorInstancesOutcome = ec2Client.UnmonitorInstances(unrequest);
    if (!unmonitorInstancesOutcome.IsSuccess()) {
        std::cout << "Failed to disable monitoring on instance " << instanceId
                  << ": " << unmonitorInstancesOutcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully disable monitoring on instance " <<
                  instanceId << std::endl;
    }
```

- Para obter detalhes da API, consulte UnmonitorInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para desabilitar o monitoramento detalhado de uma instância

Este exemplo de comando desabilita o monitoramento detalhado da instância especificada.

Comando:

```
aws ec2 unmonitor-instances --instance-ids i-1234567890abcdef0
```

Saída:

```
{
  "InstanceMonitorings": [
      {
          "InstanceId": "i-1234567890abcdef0",
          "Monitoring": {
              "State": "disabling"
```

```
            }
        }
    ]
}
```

- Para obter detalhes da API, consulte UnmonitorInstancesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UnmonitorInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new UnmonitorInstancesCommand({
    InstanceIds: ["i-09a3dfe7ae00e853f"],
  });

  try {
    const { InstanceMonitorings } = await client.send(command);
    const instanceMonitoringsList = InstanceMonitorings.map(
      (im) =>
        ` • Detailed monitoring state for ${im.InstanceId} is
 ${im.Monitoring.State}.`,
    );
    console.log("Monitoring status:");
    console.log(instanceMonitoringsList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte UnmonitorInstancesa Referência AWS SDK for JavaScript da API.

Desassociar um endereço IP elástico de uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como desassociar um endereço IP elástico de uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Disassociate an Elastic IP address from an EC2 instance.
/// </summary>
/// <param name="associationId">The association Id.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> DisassociateIp(string associationId)
{
    var response = await _amazonEC2.DisassociateAddressAsync(
        new DisassociateAddressRequest { AssociationId = associationId });
    return response.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para desassociar um endereço IP elástico no EC2-Classic

Este exemplo desassocia um endereço IP elástico de uma instância no EC2-Classic. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 disassociate-address --public-ip 198.51.100.0
```

Para desassociar um endereço IP elástico no EC2-VPC

Este exemplo desassocia um endereço IP elástico de uma instância em uma VPC. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 disassociate-address --association-id eipassoc-2bebb745
```

- Para obter detalhes da API, consulte DisassociateAddressem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void disassociateAddress(Ec2Client ec2, String associationId) {
        try {
            DisassociateAddressRequest addressRequest =
DisassociateAddressRequest.builder()
                    .associationId(associationId)
                    .build();
```

```
            ec2.disassociateAddress(addressRequest);
            System.out.println("You successfully disassociated the address!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DisassociateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Disassociate an Elastic IP address from an instance.
export const main = async () => {
  const command = new DisassociateAddressCommand({
    // You can also use PublicIp, but that is for EC2 classic which is being
 retired.
    AssociationId: "ASSOCIATION_ID",
  });

  try {
    await client.send(command);
    console.log("Successfully disassociated address");
  } catch (err) {
    console.error(err);
```

```
  }
};
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disassociateAddressSc(associationIdVal: String?) {
    val addressRequest = DisassociateAddressRequest {
        associationId = associationIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.disassociateAddress(addressRequest)
        println("You successfully disassociated the address!")
    }
}
```

- Para obter detalhes da API, consulte a DisassociateAddressreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def disassociate(self):
        """
        Removes an association between an Elastic IP address and an instance.
 When the
        association is removed, the instance is assigned a new public IP address.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to disassociate.")
            return

        try:
            self.elastic_ip.association.delete()
        except ClientError as err:
            logger.error(
                "Couldn't disassociate Elastic IP %s from its instance. Here's
 why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
```

- Para obter detalhes da API, consulte a DisassociateAddressReferência da API AWSSDK for Python (Boto3).

Habilita o monitoramento de uma instância do Amazon EC2 em execução usando um AWS SDK

Os exemplos de código a seguir mostram como habilitar o monitoramento em uma instância do Amazon EC2 em execução.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::MonitorInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.MonitorInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to enable monitoring on instance. A dry run
should trigger an error."
                <<
                std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType()
             != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cerr << "Failed dry run to enable monitoring on instance " <<
```

```
                    instanceId << ": " << dry_run_outcome.GetError().GetMessage()
 <<
                    std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto monitorInstancesOutcome = ec2Client.MonitorInstances(request);
    if (!monitorInstancesOutcome.IsSuccess()) {
        std::cerr << "Failed to enable monitoring on instance " <<
                    instanceId << ": " <<
                    monitorInstancesOutcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully enabled monitoring on instance " <<
                    instanceId << std::endl;
    }
```

- Para obter detalhes da API, consulte MonitorInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para habilitar o monitoramento detalhado de uma instância

Este exemplo de comando habilita o monitoramento detalhado da instância especificada.

Comando:

```
aws ec2 monitor-instances --instance-ids i-1234567890abcdef0
```

Saída:

```
{
  "InstanceMonitorings": [
      {
          "InstanceId": "i-1234567890abcdef0",
          "Monitoring": {
              "State": "pending"
```

```
            }
        }
    ]
}
```

- Para obter detalhes da API, consulte MonitorInstancesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { MonitorInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Turn on detailed monitoring for the selected instance.
// By default, metrics are sent to Amazon CloudWatch every 5 minutes.
// For a cost you can enable detailed monitoring which sends metrics every
 minute.
export const main = async () => {
  const command = new MonitorInstancesCommand({
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { InstanceMonitorings } = await client.send(command);
    const instancesBeingMonitored = InstanceMonitorings.map(
      (im) =>
        ` • Detailed monitoring state for ${im.InstanceId} is
 ${im.Monitoring.State}.`,
    );
    console.log("Monitoring status:");
    console.log(instancesBeingMonitored.join("\n"));
  } catch (err) {
```

```
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte MonitorInstancesa Referência AWS SDK for JavaScript da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn enable_monitoring(client: &Client, id: &str) -> Result<(), Error> {
    client.monitor_instances().instance_ids(id).send().await?;

    println!("Enabled monitoring");

    Ok(())
}
```

- Para obter detalhes da API, consulte a MonitorInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to
 monitor the instance without actually making the request. "
        lo_ec2->monitorinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to monitor this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to enable detailed monitoring completed.' TYPE 'I'.
          " DryRun is set to false to enable detailed monitoring. "
          lo_ec2->monitorinstances(
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Detailed monitoring enabled.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to monitor this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to enable detailed monitoring failed. User does not
 have the permissions to monitor the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a MonitorInstancesreferência da API AWS SDK for SAP ABAP.

Obter dados sobre imagens de máquina da Amazon usando um AWS SDK

Os exemplos de código a seguir mostram como obter dados sobre imagens de máquina da Amazon (AMIs).

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

CLI

AWS CLI

Exemplo 1: descrever uma AMI

O exemplo `describe-images` a seguir descreve a AMI especificada na região especificada.

```
aws ec2 describe-images \
    --region us-east-1 \
    --image-ids ami-1234567890EXAMPLE
```

Saída:

```
{
    "Images": [
        {
            "VirtualizationType": "hvm",
            "Description": "Provided by Red Hat, Inc.",
            "PlatformDetails": "Red Hat Enterprise Linux",
            "EnaSupport": true,
            "Hypervisor": "xen",
            "State": "available",
            "SriovNetSupport": "simple",
            "ImageId": "ami-1234567890EXAMPLE",
            "UsageOperation": "RunInstances:0010",
            "BlockDeviceMappings": [
                {
                    "DeviceName": "/dev/sda1",
                    "Ebs": {
                        "SnapshotId": "snap-111222333444aaabb",
                        "DeleteOnTermination": true,
```

```
                        "VolumeType": "gp2",
                        "VolumeSize": 10,
                        "Encrypted": false
                    }
                }
            ],
            "Architecture": "x86_64",
            "ImageLocation": "123456789012/RHEL-8.0.0_HVM-20190618-x86_64-1-
Hourly2-GP2",
            "RootDeviceType": "ebs",
            "OwnerId": "123456789012",
            "RootDeviceName": "/dev/sda1",
            "CreationDate": "2019-05-10T13:17:12.000Z",
            "Public": true,
            "ImageType": "machine",
            "Name": "RHEL-8.0.0_HVM-20190618-x86_64-1-Hourly2-GP2"
        }
    ]
}
```

Para obter mais informações, consulte Imagens de máquina da Amazon (AMIs) no Guia do usuário do Amazon EC2.

Exemplo 2: descrever AMIs com base em filtros

O exemplo `describe-images` a seguir descreve as AMIs do Windows fornecidas pela Amazon com o Amazon EBS.

```
aws ec2 describe-images \
    --owners amazon \
    --filters "Name=platform,Values=windows" "Name=root-device-type,Values=ebs"
```

Para obter um exemplo da saída de `describe-images`, consulte o Exemplo 1.

Para obter mais exemplos do uso de filtros, consulte Listar e filtrar seus recursos no Guia do usuário do Amazon EC2.

Exemplo 3: descrever AMIs com base em tags

O exemplo `describe-images` a seguir descreve todas as AMIs que têm a tag `Type=Custom`. O exemplo usa o parâmetro `--query` para exibir somente os IDs da AMI.

```
aws ec2 describe-images \
```

```
    --filters "Name=tag:Type,Values=Custom" \
    --query 'Images[*].[ImageId]' \
    --output text
```

Saída:

```
ami-1234567890EXAMPLE
ami-0abcdef1234567890
```

Para obter mais exemplos do uso de filtros de tags, consulte Trabalhando com tags no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeImagesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { paginateDescribeImages } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List at least the first i386 image available for EC2 instances.
export const main = async () => {
  // The paginate function is a wrapper around the base command.
  const paginator = paginateDescribeImages(
    // Without limiting the page size, this call can take a long time. pageSize
 is just sugar for
    // the MaxResults property in the base command.
    { client, pageSize: 25 },
    {
      // There are almost 70,000 images available. Be specific with your
 filtering
      // to increase efficiency.
```

```
      // See https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/
client-ec2/interfaces/describeimagescommandinput.html#filters
      Filters: [{ Name: "architecture", Values: ["x86_64"] }],
    },
  );

  try {
    const arm64Images = [];
    for await (const page of paginator) {
      if (page.Images.length) {
        arm64Images.push(...page.Images);
        // Once we have at least 1 result, we can stop.
        if (arm64Images.length >= 1) {
          break;
        }
      }
    }
    console.log(arm64Images);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeImagesa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""
```

```
    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def get_images(self, image_ids):
        """
        Gets information about Amazon Machine Images (AMIs) from a list of AMI
IDs.

        :param image_ids: The list of AMIs to look up.
        :return: A list of Boto3 Image objects that represent the requested AMIs.
        """
        try:
            images = list(self.ec2_resource.images.filter(ImageIds=image_ids))
        except ClientError as err:
            logger.error(
                "Couldn't get images. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return images
```

- Para obter detalhes da API, consulte a DescribeImagesReferência da API AWSSDK for Python (Boto3).

Obter dados sobre um grupo de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como obter dados sobre um grupo de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Retrieve information for an Amazon EC2 security group.
/// </summary>
/// <param name="groupId">The Id of the Amazon EC2 security group.</param>
/// <returns>A list of security group information.</returns>
public async Task<List<SecurityGroup>> DescribeSecurityGroups(string groupId)
{
    var request = new DescribeSecurityGroupsRequest();
    var groupIds = new List<string> { groupId };
    request.GroupIds = groupIds;

    var response = await _amazonEC2.DescribeSecurityGroupsAsync(request);
    return response.SecurityGroups;
}

/// <summary>
/// Display the information returned by the call to
/// DescribeSecurityGroupsAsync.
/// </summary>
/// <param name="securityGroup">A list of security group information.</param>
public void DisplaySecurityGroupInfoAsync(SecurityGroup securityGroup)
```

```
    {
        Console.WriteLine($"{securityGroup.GroupName}");
        Console.WriteLine("Ingress permissions:");
        securityGroup.IpPermissions.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIp} "); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
        Console.WriteLine("Egress permissions:");
        securityGroup.IpPermissionsEgress.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIp} "); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
    }
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DescribeSecurityGroupsRequest request;

if (!groupID.empty()) {
    request.AddGroupIds(groupID);
}

Aws::String nextToken;
do {
    if (!nextToken.empty()) {
        request.SetNextToken(nextToken);
    }

    auto outcome = ec2Client.DescribeSecurityGroups(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "Name" <<
                  std::setw(30) << "GroupId" <<
                  std::setw(30) << "VpcId" <<
                  std::setw(64) << "Description" << std::endl;

        const std::vector<Aws::EC2::Model::SecurityGroup> &securityGroups =
                outcome.GetResult().GetSecurityGroups();

        for (const auto &securityGroup: securityGroups) {
            std::cout << std::left <<
                      std::setw(32) << securityGroup.GetGroupName() <<
                      std::setw(30) << securityGroup.GetGroupId() <<
```

```
                            std::setw(30) << securityGroup.GetVpcId() <<
                            std::setw(64) << securityGroup.GetDescription() <<
                            std::endl;
            }
        }
        else {
            std::cerr << "Failed to describe security groups:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: descrever um grupo de segurança

O exemplo `describe-security-groups` a seguir descreve o grupo de segurança especificado.

```
aws ec2 describe-security-groups \
    --group-ids sg-903004f8
```

Saída:

```
{
    "SecurityGroups": [
        {
            "IpPermissionsEgress": [
                {
                    "IpProtocol": "-1",
                    "IpRanges": [
                        {
                            "CidrIp": "0.0.0.0/0"
                        }
```

```
                    ],
                    "UserIdGroupPairs": [],
                    "PrefixListIds": []
                }
            ],
            "Description": "My security group",
            "Tags": [
                {
                    "Value": "SG1",
                    "Key": "Name"
                }
            ],
            "IpPermissions": [
                {
                    "IpProtocol": "-1",
                    "IpRanges": [],
                    "UserIdGroupPairs": [
                        {
                            "UserId": "123456789012",
                            "GroupId": "sg-903004f8"
                        }
                    ],
                    "PrefixListIds": []
                },
                {
                    "PrefixListIds": [],
                    "FromPort": 22,
                    "IpRanges": [
                        {
                            "Description": "Access from NY office",
                            "CidrIp": "203.0.113.0/24"
                        }
                    ],
                    "ToPort": 22,
                    "IpProtocol": "tcp",
                    "UserIdGroupPairs": []
                    }
            ],
            "GroupName": "MySecurityGroup",
            "VpcId": "vpc-1a2b3c4d",
            "OwnerId": "123456789012",
            "GroupId": "sg-903004f8",
        }
    ]
```

```
}
```

Exemplo 2: descrever grupos de segurança com regras específicas

O exemplo `describe-security-groups``example uses filters to scope the results to security groups that have a rule that allows SSH traffic (port 22) and a rule that allows traffic from all addresses (``0.0.0.0/0` a seguir usa filtros para definir o escopo dos resultados para grupos de segurança que contêm uma regra que permite tráfego SSH (porta 22) e uma regra que permite tráfego de todos os endereços (0.0.0.0/0). O exemplo usa o parâmetro `--query` para exibir somente os nomes dos grupos de segurança. Os grupos de segurança devem corresponder a todos os filtros para serem retornados nos resultados; no entanto, uma única regra não precisa corresponder a todos os filtros. Por exemplo, a saída retorna um grupo de segurança com uma regra que permite o tráfego SSH de um endereço IP específico e outra regra que permite o tráfego HTTP de todos os endereços.

```
aws ec2 describe-security-groups \
    --filters Name=ip-permission.from-port,Values=22 Name=ip-permission.to-
port,Values=22 Name=ip-permission.cidr,Values='0.0.0.0/0' \
    --query "SecurityGroups[*].[GroupName]" \
    --output text
```

Saída:

```
default
my-security-group
web-servers
launch-wizard-1
```

Exemplo 3: descrever grupos de segurança com base em tags

O exemplo a seguir `describe-security-groups` usa filtros para definir o escopo dos resultados para grupos de segurança que incluem `test` no nome do grupo de segurança e contêm a tag `Test=To-delete`. O exemplo usa o parâmetro `--query` para exibir somente os nomes e os IDs dos grupos de segurança.

```
aws ec2 describe-security-groups \
    --filters Name=group-name,Values=*test* Name=tag:Test,Values=To-delete \
    --query "SecurityGroups[*].{Name:GroupName,ID:GroupId}"
```

Saída:

```
[
    {
        "Name": "testfornewinstance",
        "ID": "sg-33bb22aa"
    },
    {
        "Name": "newgrouptest",
        "ID": "sg-1a2b3c4d"
    }
]
```

Para obter mais exemplos do uso de filtros de tags, consulte Trabalhando com tags no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeSecurityGroupsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeSecurityGroups(Ec2Client ec2, String groupId) {
        try {
            DescribeSecurityGroupsRequest request =
DescribeSecurityGroupsRequest.builder()
                    .groupIds(groupId)
                    .build();

            DescribeSecurityGroupsResponse response =
ec2.describeSecurityGroups(request);
            for (SecurityGroup group : response.securityGroups()) {
                System.out
```

```
                        .println("Found Security Group with Id " +
 group.groupId() + " and group VPC " + group.vpcId());
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSecurityGroupsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Log the details of a specific security group.
export const main = async () => {
  const command = new DescribeSecurityGroupsCommand({
    GroupIds: ["SECURITY_GROUP_ID"],
  });

  try {
    const { SecurityGroups } = await client.send(command);
    console.log(JSON.stringify(SecurityGroups, null, 2));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2SecurityGroups(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->

        val response = ec2.describeSecurityGroups(request)
        response.securityGroups?.forEach { group ->
            println("Found Security Group with id ${group.groupId}, vpc id
 ${group.vpcId} and description ${group.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def describe(self):
        """
        Displays information about the security group.
        """
        if self.security_group is None:
            logger.info("No security group to describe.")
            return

        try:
```

```
            print(f"Security group: {self.security_group.group_name}")
            print(f"\tID: {self.security_group.id}")
            print(f"\tVPC: {self.security_group.vpc_id}")
            if self.security_group.ip_permissions:
                print(f"Inbound permissions:")
                pp(self.security_group.ip_permissions)
        except ClientError as err:
            logger.error(
                "Couldn't get data for security group %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA lt_group_ids TYPE /aws1/
cl_ec2groupidstrlist_w=>tt_groupidstringlist.
        APPEND NEW /aws1/cl_ec2groupidstrlist_w( iv_value = iv_group_id ) TO
 lt_group_ids.
        oo_result = lo_ec2->describesecuritygroups( it_groupids = lt_group_ids ).
         " oo_result is returned for testing purposes. "
        DATA(lt_security_groups) = oo_result->get_securitygroups( ).
        MESSAGE 'Retrieved information about security groups.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
```

```
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWS SDK for SAP ABAP.

Obter dados sobre os tipos de instâncias do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como obter dados sobre tipos de instâncias do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Describe the instance types available.
   /// </summary>
   /// <returns>A list of instance type information.</returns>
   public async Task<List<InstanceTypeInfo>>
DescribeInstanceTypes(ArchitectureValues architecture)
   {
       var request = new DescribeInstanceTypesRequest();

       var filters = new List<Filter>
```

```
            { new Filter("processor-info.supported-architecture", new
 List<string> { architecture.ToString() }) };
        filters.Add(new Filter("instance-type", new() { "*.micro", "*.small" }));

        request.Filters = filters;
        var instanceTypes = new List<InstanceTypeInfo>();

        var paginator = _amazonEC2.Paginators.DescribeInstanceTypes(request);
        await foreach (var instanceType in paginator.InstanceTypes)
        {
            instanceTypes.Add(instanceType);
        }
        return instanceTypes;
    }
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: descrever um tipo de instância

O exemplo `describe-instance-types` a seguir exibe os detalhes do tipo da instância especificado.

```
aws ec2 describe-instance-types \
    --instance-types t2.micro
```

Saída:

```
{
    "InstanceTypes": [
        {
            "InstanceType": "t2.micro",
            "CurrentGeneration": true,
            "FreeTierEligible": true,
            "SupportedUsageClasses": [
                "on-demand",
                "spot"
```

```
            ],
            "SupportedRootDeviceTypes": [
                "ebs"
            ],
            "BareMetal": false,
            "Hypervisor": "xen",
            "ProcessorInfo": {
                "SupportedArchitectures": [
                    "i386",
                    "x86_64"
                ],
                "SustainedClockSpeedInGhz": 2.5
            },
            "VCpuInfo": {
                "DefaultVCpus": 1,
                "DefaultCores": 1,
                "DefaultThreadsPerCore": 1,
                "ValidCores": [
                    1
                ],
                "ValidThreadsPerCore": [
                    1
                ]
            },
            "MemoryInfo": {
                "SizeInMiB": 1024
            },
            "InstanceStorageSupported": false,
            "EbsInfo": {
                "EbsOptimizedSupport": "unsupported",
                "EncryptionSupport": "supported"
            },
            "NetworkInfo": {
                "NetworkPerformance": "Low to Moderate",
                "MaximumNetworkInterfaces": 2,
                "Ipv4AddressesPerInterface": 2,
                "Ipv6AddressesPerInterface": 2,
                "Ipv6Supported": true,
                "EnaSupport": "unsupported"
            },
            "PlacementGroupInfo": {
                "SupportedStrategies": [
                    "partition",
                    "spread"
```

```
                ]
            },
            "HibernationSupported": false,
            "BurstablePerformanceSupported": true,
            "DedicatedHostsSupported": false,
            "AutoRecoverySupported": true
        }
    ]
}
```

Exemplo 2: filtrar os tipos de instância disponíveis

Você pode especificar um filtro para definir o escopo dos resultados para os tipos de instância que tenham uma característica específica. O exemplo `describe-instance-types` a seguir lista os tipos de instância compatíveis com hibernação.

```
aws ec2 describe-instance-types --filters Name=hibernation-supported,Values=true
 --query InstanceTypes[].InstanceType
```

Saída:

```
[
    "m5.8xlarge",
    "r3.large",
    "c3.8xlarge",
    "r5.large",
    "m4.4xlarge",
    "c4.large",
    "m5.xlarge",
    "m4.xlarge",
    "c3.large",
    "c4.8xlarge",
    "c4.4xlarge",
    "c5.xlarge",
    "c5.12xlarge",
    "r5.4xlarge",
    "c5.4xlarge"
]
```

- Para obter detalhes da API, consulte DescribeInstanceTypesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Get a list of instance types.
    public static String getInstanceTypes(Ec2Client ec2) {
        String instanceType = "";
        try {
            List<Filter> filters = new ArrayList<>();
            Filter filter = Filter.builder()
                    .name("processor-info.supported-architecture")
                    .values("arm64")
                    .build();

            filters.add(filter);
            DescribeInstanceTypesRequest typesRequest =
DescribeInstanceTypesRequest.builder()
                    .filters(filters)
                    .maxResults(10)
                    .build();

            DescribeInstanceTypesResponse response =
ec2.describeInstanceTypes(typesRequest);
            List<InstanceTypeInfo> instanceTypes = response.instanceTypes();
            for (InstanceTypeInfo type : instanceTypes) {
                System.out.println("The memory information of this type is " +
type.memoryInfo().sizeInMiB());
                System.out.println("Network information is " +
type.networkInfo().toString());
                instanceType = type.instanceType().toString();
            }

            return instanceType;

        } catch (SsmException e) {
            System.err.println(e.getMessage());
```

```
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateDescribeInstanceTypes,
  DescribeInstanceTypesCommand,
} from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List at least the first arm64 EC2 instance type available.
export const main = async () => {
  // The paginate function is a wrapper around the underlying command.
  const paginator = paginateDescribeInstanceTypes(
    // Without limiting the page size, this call can take a long time. pageSize
 is just sugar for
    // the MaxResults property in the underlying command.
    { client, pageSize: 25 },
    {
      Filters: [
        { Name: "processor-info.supported-architecture", Values: ["x86_64"] },
        { Name: "free-tier-eligible", Values: ["true"] },
      ],
    }
  );
```

```
  try {
    const instanceTypes = [];

    for await (const page of paginator) {
      if (page.InstanceTypes.length) {
        instanceTypes.push(...page.InstanceTypes);

        // When we have at least 1 result, we can stop.
        if (instanceTypes.length >= 1) {
          break;
        }
      }
    }
    console.log(instanceTypes);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get a list of instance types.
suspend fun getInstanceTypesSc(): String {
    var instanceType = ""
    val filterObs = ArrayList<Filter>()
    val filter = Filter {
        name = "processor-info.supported-architecture"
        values = listOf("arm64")
```

```
    }

    filterObs.add(filter)
    val typesRequest = DescribeInstanceTypesRequest {
        filters = filterObs
        maxResults = 10
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstanceTypes(typesRequest)
        response.instanceTypes?.forEach { type ->
            println("The memory information of this type is
 ${type.memoryInfo?.sizeInMib}")
            println("Maximum number of network cards is
 ${type.networkInfo?.maximumNetworkCards}")
            instanceType = type.instanceType.toString()
        }
        return instanceType
    }
}
```

- Para obter detalhes da API, consulte a DescribeInstanceTypesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
```

```
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
that
                           wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def get_instance_types(self, architecture):
        """
        Gets instance types that support the specified architecture and are
designated
        as either 'micro' or 'small'. When an instance is created, the instance
type
        you specify must support the architecture of the AMI you use.

        :param architecture: The kind of architecture the instance types must
support,
                             such as 'x86_64'.
        :return: A list of instance types that support the specified architecture
                 and are either 'micro' or 'small'.
        """
        try:
            inst_types = []
            it_paginator = self.ec2_resource.meta.client.get_paginator(
                "describe_instance_types"
            )
            for page in it_paginator.paginate(
                Filters=[
                    {
                        "Name": "processor-info.supported-architecture",
                        "Values": [architecture],
                    },
                    {"Name": "instance-type", "Values": ["*.micro", "*.small"]},
                ]
```

```
            ):
                inst_types += page["InstanceTypes"]
        except ClientError as err:
            logger.error(
                "Couldn't get instance types. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_types
```

- Para obter detalhes da API, consulte a DescribeInstanceTypesReferência da API AWSSDK for Python (Boto3).

Obtenha dados sobre o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS

Os exemplos de código a seguir mostram como obter dados sobre o perfil de instância associado a uma instância Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
 instanceId)
    {
        var response = await
 _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }
```

- Para obter detalhes da API, consulte DescribeIamInstanceProfileAssociationsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para descrever as associações do perfil de instância do IAM

Este exemplo descreve todas as suas associações de perfil de instância do IAM.

Comando:

```
aws ec2 describe-iam-instance-profile-associations
```

Saída:

```
{
  "IamInstanceProfileAssociations": [
      {
          "InstanceId": "i-09eb09efa73ec1dee",
```

```
            "State": "associated",
            "AssociationId": "iip-assoc-0db249b1f25fa24b8",
            "IamInstanceProfile": {
                "Id": "AIPAJVQN4F5WVLGCJDRGM",
                "Arn": "arn:aws:iam::123456789012:instance-profile/admin-role"
            }
        },
        {
            "InstanceId": "i-0402909a2f4dffd14",
            "State": "associating",
            "AssociationId": "iip-assoc-0d1ec06278d29f44a",
            "IamInstanceProfile": {
                "Id": "AGJAJVQN4F5WVLGCJABCM",
                "Arn": "arn:aws:iam::123456789012:instance-profile/user1-role"
            }
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeIamInstanceProfileAssociationsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const ec2Client = new EC2Client({});
const { IamInstanceProfileAssociations } = await ec2Client.send(
  new DescribeIamInstanceProfileAssociationsCommand({
    Filters: [
      { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
    ],
  }),
);
```

- Para obter detalhes da API, consulte DescribeIamInstanceProfileAssociationsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
```

```
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response =
self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]
```

- Para obter detalhes da API, consulte a DescribeIamInstanceProfileAssociationsReferência da API AWSSDK for Python (Boto3).

Obter detalhes sobre endereços IP elásticos usando um AWS SDK

Os exemplos de código a seguir mostram como obter detalhes sobre endereços IP elásticos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DescribeAddressesRequest request;
auto outcome = ec2Client.DescribeAddresses(request);
if (outcome.IsSuccess()) {
    std::cout << std::left << std::setw(20) << "InstanceId" <<
              std::setw(15) << "Public IP" << std::setw(10) << "Domain" <<
              std::setw(30) << "Allocation ID" << std::setw(25) <<
              "NIC ID" << std::endl;

    const auto &addresses = outcome.GetResult().GetAddresses();
    for (const auto &address: addresses) {
        Aws::String domainString =
                Aws::EC2::Model::DomainTypeMapper::GetNameForDomainType(
                        address.GetDomain());

        std::cout << std::left << std::setw(20) <<
                  address.GetInstanceId() << std::setw(15) <<
                  address.GetPublicIp() << std::setw(10) << domainString <<
                  std::setw(30) << address.GetAllocationId() << std::setw(25)
                  << address.GetNetworkInterfaceId() << std::endl;
    }
}
else {
    std::cerr << "Failed to describe Elastic IP addresses:" <<
              outcome.GetError().GetMessage() << std::endl;
}
```

- Para obter detalhes da API, consulte DescribeAddressesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: recuperar detalhes de todos os seus endereços IP elásticos

O exemplo `describe addresses` a seguir mostra os detalhes dos seus endereços IP elásticos.

```
aws ec2 describe-addresses
```

Saída:

```
{
    "Addresses": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "PublicIp": "198.51.100.0",
            "PublicIpv4Pool": "amazon",
            "Domain": "standard"
        },
        {
            "Domain": "vpc",
            "PublicIpv4Pool": "amazon",
            "InstanceId": "i-1234567890abcdef0",
            "NetworkInterfaceId": "eni-12345678",
            "AssociationId": "eipassoc-12345678",
            "NetworkInterfaceOwnerId": "123456789012",
            "PublicIp": "203.0.113.0",
            "AllocationId": "eipalloc-12345678",
            "PrivateIpAddress": "10.0.1.241"
        }
    ]
}
```

Exemplo 2: recuperar detalhes dos seus endereços IP elásticos para EC2-VPC

O exemplo `describe-addresses` a seguir mostra os detalhes dos seus endereços IP elásticos para usar com instâncias em uma VPC.

```
aws ec2 describe-addresses \
    --filters "Name=domain,Values=vpc"
```

Saída:

```
{
    "Addresses": [
        {
            "Domain": "vpc",
            "PublicIpv4Pool": "amazon",
            "InstanceId": "i-1234567890abcdef0",
            "NetworkInterfaceId": "eni-12345678",
            "AssociationId": "eipassoc-12345678",
            "NetworkInterfaceOwnerId": "123456789012",
            "PublicIp": "203.0.113.0",
            "AllocationId": "eipalloc-12345678",
            "PrivateIpAddress": "10.0.1.241"
        }
    ]
}
```

Exemplo 3: recuperar detalhes sobre um endereço IP elástico especificado pelo ID de alocação

O exemplo `describe-addresses` a seguir exibe os detalhes do endereço IP elástico com o ID de alocação especificado, que está associado a uma instância no EC2-VPC.

```
aws ec2 describe-addresses \
    --allocation-ids eipalloc-282d9641
```

Saída:

```
{
    "Addresses": [
        {
            "Domain": "vpc",
            "PublicIpv4Pool": "amazon",
            "InstanceId": "i-1234567890abcdef0",
            "NetworkInterfaceId": "eni-1a2b3c4d",
            "AssociationId": "eipassoc-123abc12",
            "NetworkInterfaceOwnerId": "1234567891012",
            "PublicIp": "203.0.113.25",
```

```
            "AllocationId": "eipalloc-282d9641",
            "PrivateIpAddress": "10.251.50.12"
        }
    ]
}
```

Exemplo 4: recuperar detalhes sobre um endereço IP elástico especificado pelo endereço IP privado de VPC

O exemplo `describe-addresses` a seguir mostra os detalhes do endereço IP elástico associado a um determinado endereço IP privado no EC2-VPC.

```
aws ec2 describe-addresses \
    --filters "Name=private-ip-address,Values=10.251.50.12"
```

Exemplo 5: recuperar detalhes sobre endereços IP elásticos no EC2-Classic

O exemplo `describe-addresses` a seguir mostra os detalhes dos seus endereços IP elásticos para usar no EC2-Classic.

```
aws ec2 describe-addresses \
    --filters "Name=domain,Values=standard"
```

Saída:

```
{
    "Addresses": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "PublicIp": "203.0.110.25",
            "PublicIpv4Pool": "amazon",
            "Domain": "standard"
        }
    ]
}
```

Exemplo 6: recuperar detalhes sobre um endereço IP elástico especificado pelo endereço IP público

O exemplo `describe-addresses` a seguir mostra os detalhes do endereço IP elástico com o valor`203.0.110.25`, que está associado a uma instância no EC2-Classic.

```
aws ec2 describe-addresses \
    --public-ips 203.0.110.25
```

Saída:

```
{
    "Addresses": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "PublicIp": "203.0.110.25",
            "PublicIpv4Pool": "amazon",
            "Domain": "standard"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAddressesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeAddressesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DescribeAddressesCommand({
    // You can omit this property to show all addresses.
    AllocationIds: ["ALLOCATION_ID"],
  });

  try {
```

```
    const { Addresses } = await client.send(command);
    const addressList = Addresses.map((address) => ` • ${address.PublicIp}`);
    console.log("Elastic IP addresses:");
    console.log(addressList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeAddressesa Referência AWS SDK for JavaScript da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeaddresses( ) .                       "
 oo_result is returned for testing purposes. "
        DATA(lt_addresses) = oo_result->get_addresses( ).
        MESSAGE 'Retrieved information about Elastic IP addresses.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAddressesreferência da API AWS SDK for SAP ABAP.

Obtenha a VPC padrão usando um SDK AWS

Os exemplos de código a seguir mostram como obter a VPC padrão da conta atual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get the default VPC for the account.
/// </summary>
/// <returns>The default VPC object.</returns>
public async Task<Vpc> GetDefaultVpc()
{
    var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
        new DescribeVpcsRequest()
        {
            Filters = new List<Amazon.EC2.Model.Filter>()
            {
                new ("is-default", new List<string>() { "true" })
            }
        });
    return vpcResponse.Vpcs[0];
}
```

- Para obter detalhes da API, consulte DescribeVpcsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: descrever todas as suas VPCs

O exemplo `describe-vpcs` a seguir recupera detalhes das suas VPCs.

```
aws ec2 describe-vpcs
```

Saída:

```
{
    "Vpcs": [
        {
            "CidrBlock": "30.1.0.0/16",
            "DhcpOptionsId": "dopt-19edf471",
            "State": "available",
            "VpcId": "vpc-0e9801d129EXAMPLE",
            "OwnerId": "111122223333",
            "InstanceTenancy": "default",
            "CidrBlockAssociationSet": [
                {
                    "AssociationId": "vpc-cidr-assoc-062c64cfafEXAMPLE",
                    "CidrBlock": "30.1.0.0/16",
                    "CidrBlockState": {
                        "State": "associated"
                    }
                }
            ],
            "IsDefault": false,
            "Tags": [
                {
                    "Key": "Name",
                    "Value": "Not Shared"
                }
            ]
        },
        {
            "CidrBlock": "10.0.0.0/16",
            "DhcpOptionsId": "dopt-19edf471",
            "State": "available",
            "VpcId": "vpc-06e4ab6c6cEXAMPLE",
```

```
            "OwnerId": "222222222222",
            "InstanceTenancy": "default",
            "CidrBlockAssociationSet": [
                {
                    "AssociationId": "vpc-cidr-assoc-00b17b4eddEXAMPLE",
                    "CidrBlock": "10.0.0.0/16",
                    "CidrBlockState": {
                        "State": "associated"
                    }
                }
            ],
            "IsDefault": false,
            "Tags": [
                {
                    "Key": "Name",
                    "Value": "Shared VPC"
                }
            ]
        }
    ]
}
```

Exemplo 2: descrever uma VPC especificada

O exemplo de `describe-vpcs` a seguir recupera detalhes da VPC especificada.

```
aws ec2 describe-vpcs \
    --vpc-ids vpc-06e4ab6c6cEXAMPLE
```

Saída:

```
{
    "Vpcs": [
        {
            "CidrBlock": "10.0.0.0/16",
            "DhcpOptionsId": "dopt-19edf471",
            "State": "available",
            "VpcId": "vpc-06e4ab6c6cEXAMPLE",
            "OwnerId": "111122223333",
            "InstanceTenancy": "default",
            "CidrBlockAssociationSet": [
                {
                    "AssociationId": "vpc-cidr-assoc-00b17b4eddEXAMPLE",
```

```
                    "CidrBlock": "10.0.0.0/16",
                    "CidrBlockState": {
                        "State": "associated"
                    }
                }
            ],
            "IsDefault": false,
            "Tags": [
                {
                    "Key": "Name",
                    "Value": "Shared VPC"
                }
            ]
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeVpcsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new EC2Client({});
const { Vpcs } = await client.send(
  new DescribeVpcsCommand({
    Filters: [{ Name: "is-default", Values: ["true"] }],
  }),
);
```

- Para obter detalhes da API, consulte DescribeVpcsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
```

```
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]
```

- Para obter detalhes da API, consulte a DescribeVpcsReferência da API AWSSDK for Python (Boto3).

Obtenha sub-redes padrão para uma VPC usando um SDK AWS

Os exemplos de código a seguir mostram como obter as sub-redes padrão de uma VPC.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Get all the subnets for a Vpc in a set of availability zones.
   /// </summary>
   /// <param name="vpcId">The Id of the Vpc.</param>
   /// <param name="availabilityZones">The list of availability zones.</param>
   /// <returns>The collection of subnet objects.</returns>
   public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
   {
       var subnets = new List<Subnet>();
       var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
           new DescribeSubnetsRequest()
           {
               Filters = new List<Amazon.EC2.Model.Filter>()
               {
                   new ("vpc-id", new List<string>() { vpcId}),
                   new ("availability-zone", availabilityZones),
                   new ("default-for-az", new List<string>() { "true" })
               }
           });

       // Get the entire list using the paginator.
       await foreach (var subnet in subnetPaginator.Subnets)
       {
           subnets.Add(subnet);
       }

       return subnets;
   }
```

- Para obter detalhes da API, consulte DescribeSubnetsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: descrever todas as suas sub-redes

O exemplo `describe-subnets` a seguir mostra os detalhes das suas sub-redes.

```
aws ec2 describe-subnets
```

Saída:

```
{
    "Subnets": [
        {
            "AvailabilityZone": "us-east-1d",
            "AvailabilityZoneId": "use1-az2",
            "AvailableIpAddressCount": 4089,
            "CidrBlock": "172.31.80.0/20",
            "DefaultForAz": true,
            "MapPublicIpOnLaunch": false,
            "MapCustomerOwnedIpOnLaunch": true,
            "State": "available",
            "SubnetId": "subnet-0bb1c79de3EXAMPLE",
            "VpcId": "vpc-0ee975135dEXAMPLE",
            "OwnerId": "111122223333",
            "AssignIpv6AddressOnCreation": false,
            "Ipv6CidrBlockAssociationSet": [],
            "CustomerOwnedIpv4Pool:": 'pool-2EXAMPLE',
            "SubnetArn": "arn:aws:ec2:us-east-2:111122223333:subnet/
subnet-0bb1c79de3EXAMPLE",
            "EnableDns64": false,
            "Ipv6Native": false,
            "PrivateDnsNameOptionsOnLaunch": {
                "HostnameType": "ip-name",
                "EnableResourceNameDnsARecord": false,
                "EnableResourceNameDnsAAAARecord": false
            }
        },
```

```
        {
            "AvailabilityZone": "us-east-1d",
            "AvailabilityZoneId": "use1-az2",
            "AvailableIpAddressCount": 4089,
            "CidrBlock": "172.31.80.0/20",
            "DefaultForAz": true,
            "MapPublicIpOnLaunch": true,
            "MapCustomerOwnedIpOnLaunch": false,
            "State": "available",
            "SubnetId": "subnet-8EXAMPLE",
            "VpcId": "vpc-3EXAMPLE",
            "OwnerId": "1111222233333",
            "AssignIpv6AddressOnCreation": false,
            "Ipv6CidrBlockAssociationSet": [],
            "Tags": [
                {
                    "Key": "Name",
                    "Value": "MySubnet"
                }
            ],
            "SubnetArn": "arn:aws:ec2:us-east-1:111122223333:subnet/
subnet-8EXAMPLE",
            "EnableDns64": false,
            "Ipv6Native": false,
            "PrivateDnsNameOptionsOnLaunch": {
                "HostnameType": "ip-name",
                "EnableResourceNameDnsARecord": false,
                "EnableResourceNameDnsAAAARecord": false
            }
        }
    ]
}
```

Para obter mais informações, consulte Working with VPCs and Subnets no Guia do usuário da VPC da AWS.

Exemplo 2: descrever as sub-redes de uma VPC específica

O exemplo de `describe-subnets` a seguir usa um filtro para recuperar detalhes das sub-redes da VPC especificada.

```
aws ec2 describe-subnets \
    --filters "Name=vpc-id,Values=vpc-3EXAMPLE"
```

Saída:

```
{
    "Subnets": [
        {
            "AvailabilityZone": "us-east-1d",
            "AvailabilityZoneId": "use1-az2",
            "AvailableIpAddressCount": 4089,
            "CidrBlock": "172.31.80.0/20",
            "DefaultForAz": true,
            "MapPublicIpOnLaunch": true,
            "MapCustomerOwnedIpOnLaunch": false,
            "State": "available",
            "SubnetId": "subnet-8EXAMPLE",
            "VpcId": "vpc-3EXAMPLE",
            "OwnerId": "1111222233333",
            "AssignIpv6AddressOnCreation": false,
            "Ipv6CidrBlockAssociationSet": [],
            "Tags": [
                {
                    "Key": "Name",
                    "Value": "MySubnet"
                }
            ],
            "SubnetArn": "arn:aws:ec2:us-east-1:111122223333:subnet/
subnet-8EXAMPLE",
            "EnableDns64": false,
            "Ipv6Native": false,
            "PrivateDnsNameOptionsOnLaunch": {
                "HostnameType": "ip-name",
                "EnableResourceNameDnsARecord": false,
                "EnableResourceNameDnsAAAARecord": false
            }
        }
    ]
}
```

Para obter mais informações, consulte Working with VPCs and Subnets no Guia do usuário da VPC da AWS.

Exemplo 3: descrever as sub-redes com uma tag específica

O exemplo `describe-subnets` a seguir usa um filtro para recuperar os detalhes dessas sub-redes com a tag `CostCenter=123` e o parâmetro `--query` para exibir os IDs de sub-redes com essa tag.

```
aws ec2 describe-subnets \
    --filters "Name=tag:CostCenter,Values=123" \
    --query "Subnets[*].SubnetId" \
    --output text
```

Saída:

```
subnet-0987a87c8b37348ef
subnet-02a95061c45f372ee
subnet-03f720e7de2788d73
```

Para obter mais informações, consulte Working with VPCs and Subnets no Guia do usuário da Amazon VPC.

- Para obter detalhes da API, consulte DescribeSubnetsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
```

```
    );
```

- Para obter detalhes da API, consulte DescribeSubnetsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
```

```
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
  Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

- Para obter detalhes da API, consulte a DescribeSubnetsReferência da API AWSSDK for Python (Boto3).

Listar pares de chaves de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como listar pares de chaves de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get information about an Amazon EC2 key pair.
/// </summary>
/// <param name="keyPairName">The name of the key pair.</param>
/// <returns>A list of key pair information.</returns>
public async Task<List<KeyPairInfo>> DescribeKeyPairs(string keyPairName)
{
    var request = new DescribeKeyPairsRequest();
    if (!string.IsNullOrEmpty(keyPairName))
    {
        request = new DescribeKeyPairsRequest
        {
            KeyNames = new List<string> { keyPairName }
        };
    }
```

```
        var response = await _amazonEC2.DescribeKeyPairsAsync(request);
        return response.KeyPairs.ToList();
    }
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DescribeKeyPairsRequest request;

auto outcome = ec2Client.DescribeKeyPairs(request);
if (outcome.IsSuccess()) {
    std::cout << std::left <<
              std::setw(32) << "Name" <<
              std::setw(64) << "Fingerprint" << std::endl;

    const std::vector<Aws::EC2::Model::KeyPairInfo> &key_pairs =
            outcome.GetResult().GetKeyPairs();
    for (const auto &key_pair: key_pairs) {
        std::cout << std::left <<
                  std::setw(32) << key_pair.GetKeyName() <<
                  std::setw(64) << key_pair.GetKeyFingerprint() << std::endl;
    }
}
else {
    std::cerr << "Failed to describe key pairs:" <<
              outcome.GetError().GetMessage() << std::endl;
}
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exibir um par de chaves

O exemplo `describe-key-pairs` a seguir mostra as informações do par de chaves especificado.

```
aws ec2 describe-key-pairs \
    --key-names my-key-pair
```

Saída:

```
{
    "KeyPairs": [
        {
            "KeyPairId": "key-0b94643da6EXAMPLE",
            "KeyFingerprint":
 "1f:51:ae:28:bf:89:e9:d8:1f:25:5d:37:2d:7d:b8:ca:9f:f5:f1:6f",
            "KeyName": "my-key-pair",
            "KeyType": "rsa",
            "Tags": [],
            "CreateTime": "2022-05-27T21:51:16.000Z"
        }
    ]
}
```

Para obter mais informações, consulte Descrever chaves públicas no Guia do usuário do Amazon EC2.

- Para obter detalhes da API, consulte DescribeKeyPairsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DescribeKeyPairsResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeKeyPairs {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        describeEC2Keys(ec2);
        ec2.close();
    }

    public static void describeEC2Keys(Ec2Client ec2) {
        try {
            DescribeKeyPairsResponse response = ec2.describeKeyPairs();
            response.keyPairs().forEach(keyPair -> System.out.printf(
                    "Found key pair with name %s " +
                            "and fingerprint %s",
                    keyPair.keyName(),
```

```
                    keyPair.keyFingerprint()));

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeKeyPairsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DescribeKeyPairsCommand({});

  try {
    const { KeyPairs } = await client.send(command);
    const keyPairList = KeyPairs.map(
      (kp) => ` • ${kp.KeyPairId}: ${kp.KeyName}`,
    ).join("\n");
    console.log("The following key pairs were found in your account:");
    console.log(keyPairList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2Keys() {
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeKeyPairs(DescribeKeyPairsRequest {})
        response.keyPairs?.forEach { keyPair ->
            println("Found key pair with name ${keyPair.keyName} and fingerprint
 ${ keyPair.keyFingerprint}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeKeyPairsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair
 actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is
 stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def list(self, limit):
        """
        Displays a list of key pairs for the current account.

        :param limit: The maximum number of key pairs to list.
        """
        try:
            for kp in self.ec2_resource.key_pairs.limit(limit):
                print(f"Found {kp.key_type} key {kp.name} with fingerprint:")
                print(f"\t{kp.key_fingerprint}")
        except ClientError as err:
            logger.error(
                "Couldn't list key pairs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
```

- Para obter detalhes da API, consulte a DescribeKeyPairsReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describekeypairs( ) .                       "
 oo_result is returned for testing purposes. "
        DATA(lt_key_pairs) = oo_result->get_keypairs( ).
        MESSAGE 'Retrieved information about key pairs.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeKeyPairsreferência da API AWS SDK for SAP ABAP.

Reinicializar uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como reinicializar uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Reboot EC2 instances.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the instances that will be
rebooted.</param>
    /// <returns>Async task.</returns>
    public async Task RebootInstances(string ec2InstanceId)
    {
        var request = new RebootInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.RebootInstancesAsync(request);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine("Instances successfully rebooted.");
        }
        else
        {
            Console.WriteLine("Could not reboot one or more instances.");
        }
    }
```

Substitua o perfil de uma instância, reinicialize e reinicie um servidor Web.

```
    /// <summary>
    /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
```

```
   /// used to restart the Python web server.
   /// </summary>
   /// <param name="instanceId">The Id of the instance to update.</param>
   /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
   /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
   /// <returns>Async task.</returns>
   public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
   {
       await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
               new ReplaceIamInstanceProfileAssociationRequest()
               {
                   AssociationId = associationId,
                   IamInstanceProfile = new IamInstanceProfileSpecification()
                   {
                       Name = credsProfileName
                   }
               });
       // Allow time before resetting.
       Thread.Sleep(25000);
       var instanceReady = false;
       var retries = 5;
       while (retries-- > 0 && !instanceReady)
       {
           await _amazonEc2.RebootInstancesAsync(
               new RebootInstancesRequest(new List<string>() { instanceId }));
           Thread.Sleep(10000);

           var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
               new DescribeInstanceInformationRequest());
           // Get the entire list using the paginator.
           await foreach (var instance in
instancesPaginator.InstanceInformationList)
           {
               instanceReady = instance.InstanceId == instanceId;
               if (instanceReady)
               {
                   break;
               }
           }
       }
```

```
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RebootInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.RebootInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to reboot on instance. A dry run should
trigger an error."
                <<
```

```
                std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType()
             != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to reboot instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto outcome = ec2Client.RebootInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to reboot instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully rebooted instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para reinicializar uma instância do Amazon EC2

Este exemplo reinicia a instância especificada. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 reboot-instances --instance-ids i-1234567890abcdef5
```

Para obter mais informações, consulte Reinicializar a instância no Guia do usuário do Amazon Elastic Compute Cloud.

- Para obter detalhes da API, consulte RebootInstancesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { RebootInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new RebootInstancesCommand({
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    await client.send(command);
    console.log("Instance rebooted successfully.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"
```

```
    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                                the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                            instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
```

```
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
 instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
 {profile_association_id}: {err}"
            )
```

- Para obter detalhes da API, consulte a RebootInstancesReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn reboot_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.reboot_instances().instance_ids(id).send().await?;

    println!("Rebooted instance.");
    Ok(())
}
```

- Para obter detalhes da API, consulte a RebootInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to
 reboot the instance without actually making the request. "
        lo_ec2->rebootinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to reboot this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to reboot instance completed.' TYPE 'I'.
          " DryRun is set to false to make a reboot request. "
          lo_ec2->rebootinstances(
             it_instanceids = lt_instance_ids
             iv_dryrun = abap_false
           ).
          MESSAGE 'Instance rebooted.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to reboot this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to reboot instance failed. User does not have
 permissions to reboot the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
```

```
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a RebootInstancesreferência da API AWS SDK for SAP ABAP.

Liberar um endereço IP elástico usando um AWS SDK

Os exemplos de código a seguir mostram como liberar um endereço IP elástico.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Release an Elastic IP address.
    /// </summary>
    /// <param name="allocationId">The allocation Id of the Elastic IP address.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> ReleaseAddress(string allocationId)
    {
        var request = new ReleaseAddressRequest
        {
            AllocationId = allocationId
        };
```

```
        var response = await _amazonEC2.ReleaseAddressAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2(clientConfiguration);

Aws::EC2::Model::ReleaseAddressRequest request;
request.SetAllocationId(allocationID);

auto outcome = ec2.ReleaseAddress(request);
if (!outcome.IsSuccess()) {
    std::cerr << "Failed to release Elastic IP address " <<
              allocationID << ":" << outcome.GetError().GetMessage() <<
              std::endl;
}
else {
    std::cout << "Successfully released Elastic IP address " <<
              allocationID << std::endl;
}
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para liberar um endereço IP elástico do EC2-Classic

Este exemplo libera um endereço IP elástico para usar com instâncias no EC2-Classic. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 release-address --public-ip 198.51.100.0
```

Para liberar um endereço IP elástico para o EC2-VPC

Este exemplo libera um endereço IP elástico para usar com instâncias em uma VPC. Se o comando for bem-sucedido, nenhuma saída será retornada.

Comando:

```
aws ec2 release-address --allocation-id eipalloc-64d5890a
```

- Para obter detalhes da API, consulte ReleaseAddressem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import software.amazon.awssdk.services.ec2.model.ReleaseAddressRequest;

/**
```

```
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ReleaseAddress {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <allocId>

                Where:
                   allocId - An allocation ID value that you can obtain from the
 AWS Console.\s

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String allocId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        releaseEC2Address(ec2, allocId);
        ec2.close();
    }

    public static void releaseEC2Address(Ec2Client ec2, String allocId) {
        try {
            ReleaseAddressRequest request = ReleaseAddressRequest.builder()
                    .allocationId(allocId)
                    .build();

            ec2.releaseAddress(request);
```

```
            System.out.printf("Successfully released elastic IP address %s",
 allocId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ReleaseAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new ReleaseAddressCommand({
    // You can also use PublicIp, but that is for EC2 classic which is being
 retired.
    AllocationId: "ALLOCATION_ID",
  });

  try {
    await client.send(command);
    console.log("Successfully released address.");
  } catch (err) {
    console.error(err);
  }
```

```
};
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun releaseEC2AddressSc(allocId: String?) {
    val request = ReleaseAddressRequest {
        allocationId = allocId
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.releaseAddress(request)
        println("Successfully released Elastic IP address $allocId")
    }
}
```

- Para obter detalhes da API, consulte a ReleaseAddressreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def release(self):
        """
        Releases an Elastic IP address. After the Elastic IP address is released,
        it can no longer be used.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to release.")
            return

        try:
            self.elastic_ip.release()
        except ClientError as err:
            logger.error(
                "Couldn't release Elastic IP address %s. Here's why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ReleaseAddressReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Releases an Elastic IP address from an
# Amazon Elastic Compute Cloud (Amazon EC2) instance.
#
# Prerequisites:
#
# - An Amazon EC2 instance with an associated Elastic IP address.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param allocation_id [String] The ID of the allocation corresponding to
#   the Elastic IP address.
# @return [Boolean] true if the Elastic IP address was released;
#   otherwise, false.
# @example
#   exit 1 unless elastic_ip_address_released?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'eipalloc-04452e528a66279EX'
#   )
def elastic_ip_address_released?(ec2_client, allocation_id)
  ec2_client.release_address(allocation_id: allocation_id)
  return true
rescue StandardError => e
  puts("Error releasing Elastic IP address: #{e.message}")
  return false
end
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->releaseaddress( iv_allocationid = iv_allocation_id ).
        MESSAGE 'Elastic IP address released.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ReleaseAddressreferência da API AWS SDK for SAP ABAP.

Subtitua o perfil de instância associado a uma instância Amazon EC2 usando um SDK AWS

Os exemplos de código a seguir mostram como substituir o perfil de instância associado com uma instância Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
   /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
   /// used to restart the Python web server.
   /// </summary>
   /// <param name="instanceId">The Id of the instance to update.</param>
   /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
   /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
   /// <returns>Async task.</returns>
   public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
   {
       await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
               new ReplaceIamInstanceProfileAssociationRequest()
               {
                   AssociationId = associationId,
                   IamInstanceProfile = new IamInstanceProfileSpecification()
                   {
                       Name = credsProfileName
                   }
               });
       // Allow time before resetting.
       Thread.Sleep(25000);
       var instanceReady = false;
       var retries = 5;
       while (retries-- > 0 && !instanceReady)
       {
           await _amazonEc2.RebootInstancesAsync(
```

```
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }
```

- Para obter detalhes da API, consulte ReplaceIamInstanceProfileAssociationa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para substituir um perfil de instância do IAM de uma instância

Este exemplo substitui o perfil de instância do IAM representado pela associação `iip-assoc-060bae234aac2e7fa` pelo perfil de instância do IAM chamado `AdminRole`.

```
aws ec2 replace-iam-instance-profile-association \
    --iam-instance-profile Name=AdminRole \
    --association-id iip-assoc-060bae234aac2e7fa
```

Saída:

```
{
    "IamInstanceProfileAssociation": {
        "InstanceId": "i-087711ddaf98f9489",
        "State": "associating",
        "AssociationId": "iip-assoc-0b215292fab192820",
        "IamInstanceProfile": {
            "Id": "AIPAJLNLDX3AMYZNWYYAY",
            "Arn": "arn:aws:iam::123456789012:instance-profile/AdminRole"
        }
    }
}
```

- Para obter detalhes da API, consulte ReplaceIamInstanceProfileAssociationem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
```

```
        ),
      );
```

- Para obter detalhes da API, consulte ReplaceIamInstanceProfileAssociationa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo substitui o perfil de instância de uma instância em execução, reinicia a instância e envia um comando para a instância após ela iniciar.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
```

```
                            created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
```

```
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )
```

- Para obter detalhes da API, consulte a ReplaceIamInstanceProfileAssociationReferência da API AWSSDK for Python (Boto3).

Definir regras de entrada para um grupo de segurança do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como definir regras de entrada para um grupo de segurança do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Authorize the local computer ingress to EC2 instances associated
    /// with the virtual private cloud (VPC) security group.
    /// </summary>
    /// <param name="groupName">The name of the security group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AuthorizeSecurityGroupIngress(string groupName)
    {
        // Get the IP address for the local computer.
        var ipAddress = await GetIpAddress();
        Console.WriteLine($"Your IP address is: {ipAddress}");
        var ipRanges = new List<IpRange> { new IpRange { CidrIp =
$"{ipAddress}/32" } };
        var permission = new IpPermission
        {
            Ipv4Ranges = ipRanges,
            IpProtocol = "tcp",
            FromPort = 22,
            ToPort = 22
        };
```

```
        var permissions = new List<IpPermission> { permission };
        var response = await _amazonEC2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest(groupName, permissions));
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Authorize the local computer for ingress to
    /// the Amazon EC2 SecurityGroup.
    /// </summary>
    /// <returns>The IPv4 address of the computer running the scenario.</returns>
    private static async Task<string> GetIpAddress()
    {
        var httpClient = new HttpClient();
        var ipString = await httpClient.GetStringAsync("https://
checkip.amazonaws.com");

        // The IP address is returned with a new line
        // character on the end. Trim off the whitespace and
        // return the value to the caller.
        return ipString.Trim();
    }
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::IpRange ip_range;
    ip_range.SetCidrIp("0.0.0.0/0");
```

```
    Aws::EC2::Model::IpPermission permission1;
    permission1.SetIpProtocol("tcp");
    permission1.SetToPort(80);
    permission1.SetFromPort(80);
    permission1.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission1);

    Aws::EC2::Model::IpPermission permission2;
    permission2.SetIpProtocol("tcp");
    permission2.SetToPort(22);
    permission2.SetFromPort(22);
    permission2.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission2);

    const Aws::EC2::Model::AuthorizeSecurityGroupIngressOutcome authorizeOutcome
=
            ec2Client.AuthorizeSecurityGroupIngress(authorizeRequest);

    if (!authorizeOutcome.IsSuccess()) {
        std::cerr << "Failed to set ingress policy for security group " <<
                  groupName << ":" << authorizeOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    std::cout << "Successfully added ingress policy to security group " <<
              groupName << std::endl;
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: adicionar uma regra que permita tráfego SSH de entrada

O exemplo `authorize-security-group-ingress` a seguir adiciona uma regra que permite o tráfego de entrada na porta TCP 22 (SSH).

```
aws ec2 authorize-security-group-ingress \
    --group-id sg-1234567890abcdef0 \
    --protocol tcp \
    --port 22 \
    --cidr 203.0.113.0/24
```

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-01afa97ef3e1bedfc",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": 22,
            "ToPort": 22,
            "CidrIpv4": "203.0.113.0/24"
        }
    ]
}
```

Exemplo 2: adicionar uma regra que permita tráfego HTTP de entrada de outro grupo de segurança

O exemplo `authorize-security-group-ingress` a seguir adiciona uma regra que permite o acesso de entrada na porta TCP 80 do grupo de segurança de origem `sg-1a2b3c4d`. O grupo de origem deve estar na mesma VPC ou em uma VPC de par (requer uma conexão de emparelhamento da VPC). O tráfego de entrada é permitido com base nos endereços IP privados das instâncias associadas ao grupo de segurança de origem (e não ao endereço IP público ou ao endereço IP elástico).

```
aws ec2 authorize-security-group-ingress \
    --group-id sg-1234567890abcdef0 \
    --protocol tcp \
    --port 80 \
    --source-group sg-1a2b3c4d
```

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-01f4be99110f638a7",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": 80,
            "ToPort": 80,
            "ReferencedGroupInfo": {
                "GroupId": "sg-1a2b3c4d",
                "UserId": "123456789012"
            }
        }
    ]
}
```

Exemplo 3: adicionar várias regras na mesma chamada

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar duas regras de entrada, uma que habilita o acesso de entrada na porta TCP 3389 (RDP) e a outra que habilita o ping e ICMP.

aws ec2 authorize-security-group-ingress --group-id sg-1234567890abcdef0 --ip-permissions IpProtocol =tcp, =3389, FromPort =3389, = "[{=172.31.0.0/16}]" =icmp, =-1, =-1, = "[{=172.31.0.0/16}ToPort]" IpRanges CidrIp IpProtocol FromPort ToPort IpRanges CidrIp

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-00e06e5d3690f29f3",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": 3389,
            "ToPort": 3389,
```

```
            "CidrIpv4": "172.31.0.0/16"
        },
        {
            "SecurityGroupRuleId": "sgr-0a133dd4493944b87",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": -1,
            "ToPort": -1,
            "CidrIpv4": "172.31.0.0/16"
        }
    ]
}
```

Exemplo 4: adicionar uma regra para o tráfego ICMP

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar uma regra de entrada que permite a mensagem do ICMP `Destination Unreachable: Fragmentation Needed and Don't Fragment was Set` (Tipo 3, Código 4) de qualquer lugar.

aws ec2 authorize-security-group-ingress --group-id sg-1234567890abcdef0 --ip-permissions =icmp, =3, =4, = "[{=0.0.0.0/0}]" IpProtocol FromPort ToPort IpRanges CidrIp

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-0de3811019069b787",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "icmp",
            "FromPort": 3,
            "ToPort": 4,
            "CidrIpv4": "0.0.0.0/0"
        }
    ]
}
```

Exemplo 5: adicionar uma regra para o tráfego IPv6

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar uma regra de entrada que permite o acesso SSH (porta 22) do intervalo IPv6 `2001:db8:1234:1a00::/64`.

aws ec2 authorize-security-group-ingress --group-id sg-1234567890abcdef0 --ip-permissions =tcp, =22, =22, Ipv6Ranges= "[{6=2001:db 8:1234:1 a00: :/64 IpProtocol}]" FromPort ToPort CidrIpv

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-0455bc68b60805563",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": 22,
            "ToPort": 22,
            "CidrIpv6": "2001:db8:1234:1a00::/64"
        }
    ]
}
```

Exemplo 6: adicionar uma regra para o tráfego ICMPv6

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar uma regra de entrada que permite o tráfego ICMPv6 de qualquer lugar.

aws ec2 authorize-security-group-ingress --group-id sg-1234567890abcdef0 --ip-permissions =icmpv6, Ipv6Ranges= "[{6=: :/0}]" IpProtocol CidrIpv

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
```

```
        {
            "SecurityGroupRuleId": "sgr-04b612d9363ab6327",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "icmpv6",
            "FromPort": -1,
            "ToPort": -1,
            "CidrIpv6": "::/0"
        }
    ]
}
```

Exemplo 7: adicionar uma regra com uma descrição

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar uma regra de entrada que permite o tráfego RDP do intervalo de endereços IPv4 especificado. A regra inclui uma descrição para ajudar a identificá-lo posteriormente.

aws ec2 authorize-security-group-ingress --group-id sg-1234567890abcdef0 --ip-permissions IpProtocol =tcp, =3389, =3389, = "[{=203.0.113.0/24, description='Acesso RDP do escritório de NY'}]" FromPort ToPort IpRanges CidrIp

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-0397bbcc01e974db3",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "tcp",
            "FromPort": 3389,
            "ToPort": 3389,
            "CidrIpv4": "203.0.113.0/24",
            "Description": "RDP access from NY office"
        }
    ]
}
```

Exemplo 8: adicionar uma regra de entrada que use uma lista de prefixos

O exemplo `authorize-security-group-ingress` a seguir usa o parâmetro `ip-permissions` para adicionar uma regra de entrada que permite todo o tráfego para os intervalos CIDR na lista de prefixos especificada.

aws ec2 authorize-security-group-ingress --group-id sg-04a351bfe432d4e71 --ip-permissions =all, = "[{=pl-002dc3ec097de1514}]" IpProtocol PrefixListIds PrefixListId

Saída:

```
{
    "Return": true,
    "SecurityGroupRules": [
        {
            "SecurityGroupRuleId": "sgr-09c74b32f677c6c7c",
            "GroupId": "sg-1234567890abcdef0",
            "GroupOwnerId": "123456789012",
            "IsEgress": false,
            "IpProtocol": "-1",
            "FromPort": -1,
            "ToPort": -1,
            "PrefixListId": "pl-0721453c7ac4ec009"
        }
    ]
}
```

Para obter mais informações, consulte Grupos de segurança no Manual do usuário da Amazon VPC.

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createSecurityGroup(Ec2Client ec2, String groupName,
String groupDesc, String vpcId,
           String myIpAddress) {
       try {
           CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                   .groupName(groupName)
                   .description(groupDesc)
                   .vpcId(vpcId)
                   .build();

           CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);
           IpRange ipRange = IpRange.builder()
                   .cidrIp(myIpAddress + "/0")
                   .build();

           IpPermission ipPerm = IpPermission.builder()
                   .ipProtocol("tcp")
                   .toPort(80)
                   .fromPort(80)
                   .ipRanges(ipRange)
                   .build();

           IpPermission ipPerm2 = IpPermission.builder()
                   .ipProtocol("tcp")
                   .toPort(22)
                   .fromPort(22)
                   .ipRanges(ipRange)
                   .build();

           AuthorizeSecurityGroupIngressRequest authRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                   .groupName(groupName)
                   .ipPermissions(ipPerm, ipPerm2)
                   .build();

           ec2.authorizeSecurityGroupIngress(authRequest);
           System.out.println("Successfully added ingress policy to security
group " + groupName);
           return resp.groupId();

       } catch (Ec2Exception e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AuthorizeSecurityGroupIngressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Grant permissions for a single IP address to ssh into instances
// within the provided security group.
export const main = async () => {
  const command = new AuthorizeSecurityGroupIngressCommand({
    // Replace with a security group ID from the AWS console or
    // the DescribeSecurityGroupsCommand.
    GroupId: "SECURITY_GROUP_ID",
    IpPermissions: [
      {
        IpProtocol: "tcp",
        FromPort: 22,
        ToPort: 22,
        // Replace 0.0.0.0 with the IP address to authorize.
        // For more information on this notation, see
        // https://en.wikipedia.org/wiki/Classless_Inter-
Domain_Routing#CIDR_notation
        IpRanges: [{ CidrIp: "0.0.0.0/32" }],
```

```
      },
    ],
  });

  try {
    const { SecurityGroupRules } = await client.send(command);
    console.log(JSON.stringify(SecurityGroupRules, null, 2));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2SecurityGroupSc(groupNameVal: String?, groupDescVal:
 String?, vpcIdVal: String?, myIpAddress: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "$myIpAddress/0"
        }

        val ipPerm = IpPermission {
```

```
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
        }
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group
 $groupNameVal")
        return resp.groupId
    }
}
```

- Para obter detalhes da API, consulte a AuthorizeSecurityGroupIngressreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""
```

```
    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def authorize_ingress(self, ssh_ingress_ip):
        """
        Adds a rule to the security group to allow access to SSH.

        :param ssh_ingress_ip: The IP address that is granted inbound access to
connect
                               to port 22 over TCP, used for SSH.
        :return: The response to the authorization request. The 'Return' field of
the
                 response indicates whether the request succeeded or failed.
        """
        if self.security_group is None:
            logger.info("No security group to update.")
            return

        try:
            ip_permissions = [
                {
                    # SSH ingress open to only the specified IP address.
                    "IpProtocol": "tcp",
                    "FromPort": 22,
                    "ToPort": 22,
                    "IpRanges": [{"CidrIp": f"{ssh_ingress_ip}/32"}],
                }
```

```
            ]
            response = self.security_group.authorize_ingress(
                IpPermissions=ip_permissions
            )
        except ClientError as err:
            logger.error(
                "Couldn't authorize inbound rules for %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a AuthorizeSecurityGroupIngressReferência da API AWSSDK for Python (Boto3).

Iniciar uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como iniciar uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Start an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the Amazon EC2 instance
    /// to start.</param>
    /// <returns>Async task.</returns>
    public async Task StartInstances(string ec2InstanceId)
    {
        var request = new StartInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StartInstancesAsync(request);

        if (response.StartingInstances.Count > 0)
        {
            var instances = response.StartingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully started the EC2 instance with
instance ID: {i.InstanceId}.");
            });
        }
    }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
```

```
    Aws::EC2::Model::StartInstancesRequest start_request;
    start_request.AddInstanceIds(instanceId);
    start_request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.StartInstances(start_request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to start instance. A dry run should trigger an
error."
                << std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to start instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    start_request.SetDryRun(false);
    auto start_instancesOutcome = ec2Client.StartInstances(start_request);

    if (!start_instancesOutcome.IsSuccess()) {
        std::cout << "Failed to start instance " << instanceId << ": " <<
                  start_instancesOutcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully started instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para iniciar uma instância do Amazon EC2

Este exemplo inicia a instância especificada com o Amazon EBS.

Comando:

```
aws ec2 start-instances --instance-ids i-1234567890abcdef0
```

Saída:

```
{
    "StartingInstances": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "CurrentState": {
                "Code": 0,
                "Name": "pending"
            },
            "PreviousState": {
                "Code": 80,
                "Name": "stopped"
            }
        }
    ]
}
```

Para obter mais informações, consulte Interromper e iniciar sua instância no Guia do usuário do Amazon Elastic Compute Cloud.

- Para obter detalhes da API, consulte StartInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void startInstance(Ec2Client ec2, String instanceId) {
        Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                .overrideConfiguration(b -> b.maxAttempts(100))
                .client(ec2)
                .build();
```

```
        StartInstancesRequest request = StartInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to run.
 This will take a few minutes.");
        ec2.startInstances(request);
        DescribeInstancesRequest instanceRequest =
 DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
 ec2Waiter.waitUntilInstanceRunning(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully started instance " + instanceId);
    }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { StartInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new StartInstancesCommand({
    // Use DescribeInstancesCommand to find InstanceIds
    InstanceIds: ["INSTANCE_ID"],
  });
```

```
  try {
    const { StartingInstances } = await client.send(command);
    const instanceIdList = StartingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Starting instances:");
    console.log(instanceIdList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startInstanceSc(instanceId: String) {
    val request = StartInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.startInstances(request)
        println("Waiting until instance $instanceId starts. This will take a few
 minutes.")
        ec2.waitUntilInstanceRunning { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully started instance $instanceId")
    }
```

```
}
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
 that
                            wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def start(self):
        """
        Starts an instance and waits for it to be in a running state.
```

```
        :return: The response to the start request.
        """
        if self.instance is None:
            logger.info("No instance to start.")
            return

        try:
            response = self.instance.start()
            self.instance.wait_until_running()
        except ClientError as err:
            logger.error(
                "Couldn't start instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartInstancesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Attempts to start an Amazon Elastic Compute Cloud (Amazon EC2) instance.
#
# Prerequisites:
```

```
#
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was started; otherwise, false.
# @example
#   exit 1 unless instance_started?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_started?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive?
    state = response.instance_statuses[0].instance_state.name
    case state
    when "pending"
      puts "Error starting instance: the instance is pending. Try again later."
      return false
    when "running"
      puts "The instance is already running."
      return true
    when "terminated"
      puts "Error starting instance: " \
        "the instance is terminated, so you cannot start it."
      return false
    end
  end

  ec2_client.start_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_running, instance_ids: [instance_id])
  puts "Instance started."
  return true
rescue StandardError => e
  puts "Error starting instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
```

```
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "INSTANCE_ID REGION "
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to start instance '#{instance_id}' " \
    "(this might take a few minutes)..."
  unless instance_started?(ec2_client, instance_id)
    puts "Could not start instance."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn start_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.start_instances().instance_ids(id).send().await?;

    println!("Started instance.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to
 start the instance without actually making the request. "
        lo_ec2->startinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to start this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to start instance completed.' TYPE 'I'.
          " DryRun is set to false to start instance. "
```

```
          oo_result = lo_ec2->startinstances(           " oo_result is returned
 for testing purposes. "
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Successfully started the EC2 instance.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to start this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to start instance failed. User does not have
 permissions to start the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWS SDK for SAP ABAP.

Interromper uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como interromper uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Stop an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance to
    /// stop.</param>
    /// <returns>Async task.</returns>
    public async Task StopInstances(string ec2InstanceId)
    {
        // In addition to the list of instance Ids, the
        // request can also include the following properties:
        //     Force      When true, forces the instances to
        //                stop but you must check the integrity
        //                of the file system. Not recommended on
        //                Windows instances.
        //     Hibernate  When true, hibernates the instance if the
        //                instance was enabled for hibernation when
        //                it was launched.
        var request = new StopInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StopInstancesAsync(request);

        if (response.StoppingInstances.Count > 0)
        {
            var instances = response.StoppingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully stopped the EC2 Instance " +
                                  $"with InstanceID: {i.InstanceId}.");
            });
        }
    }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::StopInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.StopInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to stop instance. A dry run should trigger an
error."
                << std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to stop instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto outcome = ec2Client.StopInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to stop instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully stopped instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: interromper uma instância do Amazon EC2

O exemplo `stop-instances` a seguir interrompe a instância especificada com o Amazon EBS.

```
aws ec2 stop-instances \
    --instance-ids i-1234567890abcdef0
```

Saída:

```
{
    "StoppingInstances": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "CurrentState": {
                "Code": 64,
                "Name": "stopping"
            },
            "PreviousState": {
                "Code": 16,
                "Name": "running"
            }
        }
    ]
}
```

Para obter mais informações, consulte Interromper e iniciar sua instância no Guia do usuário do Amazon Elastic Compute Cloud.

Exemplo 2: hibernar uma instância do Amazon EC2

O exemplo `stop-instances` a seguir hiberna uma instância com o Amazon EBS se ela estiver habilitada para isso e atender aos pré-requisitos de hibernação. Depois de colocar a instância em hibernação, ela é interrompida.

```
aws ec2 stop-instances \
```

```
    --instance-ids i-1234567890abcdef0 \
    --hibernate
```

Saída:

```
{
    "StoppingInstances": [
        {
            "CurrentState": {
                "Code": 64,
                "Name": "stopping"
            },
            "InstanceId": "i-1234567890abcdef0",
            "PreviousState": {
                "Code": 16,
                "Name": "running"
            }
        }
    ]
}
```

Para obter mais informações, consulte Colocar em hibernação uma instância sob demanda do Linux no Guia do usuário do Amazon Elastic Cloud Compute.

- Para obter detalhes da API, consulte StopInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void stopInstance(Ec2Client ec2, String instanceId) {
        Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                .overrideConfiguration(b -> b.maxAttempts(100))
                .client(ec2)
                .build();
```

```
        StopInstancesRequest request = StopInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to stop.
 This will take a few minutes.");
        ec2.stopInstances(request);
        DescribeInstancesRequest instanceRequest =
 DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
 ec2Waiter.waitUntilInstanceStopped(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully stopped instance " + instanceId);
    }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { StopInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new StopInstancesCommand({
    // Use DescribeInstancesCommand to find InstanceIds
    InstanceIds: ["INSTANCE_ID"],
  });
```

```
  try {
    const { StoppingInstances } = await client.send(command);
    const instanceIdList = StoppingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Stopping instances:");
    console.log(instanceIdList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun stopInstanceSc(instanceId: String) {
    val request = StopInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.stopInstances(request)
        println("Waiting until instance $instanceId stops. This will take a few
 minutes.")
        ec2.waitUntilInstanceStopped { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully stopped instance $instanceId")
    }
```

```
}
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
 that
                          wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def stop(self):
        """
        Stops an instance and waits for it to be in a stopped state.
```

```
        :return: The response to the stop request.
        """
        if self.instance is None:
            logger.info("No instance to stop.")
            return

        try:
            response = self.instance.stop()
            self.instance.wait_until_stopped()
        except ClientError as err:
            logger.error(
                "Couldn't stop instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StopInstancesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - The Amazon EC2 instance.
```

```
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was stopped; otherwise, false.
# @example
#   exit 1 unless instance_stopped?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_stopped?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive?
    state = response.instance_statuses[0].instance_state.name
    case state
    when "stopping"
      puts "The instance is already stopping."
      return true
    when "stopped"
      puts "The instance is already stopped."
      return true
    when "terminated"
      puts "Error stopping instance: " \
        "the instance is terminated, so you cannot stop it."
      return false
    end
  end

  ec2_client.stop_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_stopped, instance_ids: [instance_id])
  puts "Instance stopped."
  return true
rescue StandardError => e
  puts "Error stopping instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-stop-instance-i-123abc.rb " \
```

```
      "INSTANCE_ID REGION "
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to stop instance '#{instance_id}' " \
    "(this might take a few minutes)..."
  unless instance_stopped?(ec2_client, instance_id)
    puts "Could not stop instance."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn stop_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.stop_instances().instance_ids(id).send().await?;

    println!("Stopped instance.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to stop
 the instance without actually making the request. "
        lo_ec2->stopinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to stop this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to stop instance completed.' TYPE 'I'.
          " DryRun is set to false to stop instance. "
```

```
          oo_result = lo_ec2->stopinstances(           " oo_result is returned
 for testing purposes. "
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Successfully stopped the EC2 instance.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to stop this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to stop instance failed. User does not have
 permissions to stop the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWS SDK for SAP ABAP.

Encerrar uma instância do Amazon EC2 usando um AWS SDK

Os exemplos de código a seguir mostram como encerrar uma instância do Amazon EC2.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Terminate an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance
    /// to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task<List<InstanceStateChange>> TerminateInstances(string
ec2InstanceId)
    {
        var request = new TerminateInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId }
        };

        var response = await _amazonEC2.TerminateInstancesAsync(request);
        return response.TerminatingInstances;
    }
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::TerminateInstancesRequest request;
    request.SetInstanceIds({instanceID});

    Aws::EC2::Model::TerminateInstancesOutcome outcome =
            ec2Client.TerminateInstances(request);
    if (outcome.IsSuccess()) {
        std::cout << "Ec2 instance '" << instanceID <<
```

```
                    "' was terminated." << std::endl;
    }
    else {
        std::cerr << "Failed to terminate ec2 instance " << instanceID <<
                    ", " <<
                    outcome.GetError().GetMessage() << std::endl;
        return false;
    }
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para encerrar uma instância do Amazon EC2

Este exemplo encerra a instância especificada.

Comando:

```
aws ec2 terminate-instances --instance-ids i-1234567890abcdef0
```

Saída:

```
{
    "TerminatingInstances": [
        {
            "InstanceId": "i-1234567890abcdef0",
            "CurrentState": {
                "Code": 32,
                "Name": "shutting-down"
            },
            "PreviousState": {
                "Code": 16,
                "Name": "running"
            }
        }
    ]
}
```

Para obter mais informações, consulte Using Amazon EC2 Instances no Guia do usuário da AWS Command Line Interface.

- Para obter detalhes da API, consulte TerminateInstancesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.TerminateInstancesRequest;
import software.amazon.awssdk.services.ec2.model.TerminateInstancesResponse;
import software.amazon.awssdk.services.ec2.model.InstanceStateChange;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class TerminateInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <instanceId>

                Where:
```

```
                    instanceId - An instance id value that you can obtain from the
 AWS Console.\s
                """";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String instanceId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        terminateEC2(ec2, instanceId);
        ec2.close();
    }

    public static void terminateEC2(Ec2Client ec2, String instanceID) {
        try {
            TerminateInstancesRequest ti = TerminateInstancesRequest.builder()
                    .instanceIds(instanceID)
                    .build();

            TerminateInstancesResponse response = ec2.terminateInstances(ti);
            List<InstanceStateChange> list = response.terminatingInstances();
            for (InstanceStateChange sc : list) {
                System.out.println("The ID of the terminated instance is " +
 sc.instanceId());
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { TerminateInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new TerminateInstancesCommand({
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { TerminatingInstances } = await client.send(command);
    const instanceList = TerminatingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Terminating instances:");
    console.log(instanceList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun terminateEC2(instanceID: String) {
    val request = TerminateInstancesRequest {
        instanceIds = listOf(instanceID)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.terminateInstances(request)
        response.terminatingInstances?.forEach { instance ->
            println("The ID of the terminated instance is
 ${instance.instanceId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a TerminateInstancesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
```

```
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
that
                            wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def terminate(self):
        """
        Terminates an instance and waits for it to be in a terminated state.
        """
        if self.instance is None:
            logger.info("No instance to terminate.")
            return

        instance_id = self.instance.id
        try:
            self.instance.terminate()
            self.instance.wait_until_terminated()
            self.instance = None
        except ClientError as err:
            logging.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a TerminateInstancesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was terminated; otherwise, false.
# @example
#   exit 1 unless instance_terminated?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_terminated?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive? &&
    response.instance_statuses[0].instance_state.name == "terminated"

    puts "The instance is already terminated."
    return true
  end

  ec2_client.terminate_instances(instance_ids: [instance_id])
```

```
  ec2_client.wait_until(:instance_terminated, instance_ids: [instance_id])
  puts "Instance terminated."
  return true
rescue StandardError => e
  puts "Error terminating instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-terminate-instance-i-123abc.rb " \
      "INSTANCE_ID REGION "
   # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-terminate-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to terminate instance '#{instance_id}' " \
    "(this might take a few minutes)..."
  unless instance_terminated?(ec2_client, instance_id)
    puts "Could not terminate instance."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for Ruby da API.

Cenários do Amazon EC2 com AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Elastic Compute Cloud (Amazon EC2) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar e gerenciar um serviço resiliente usando um AWS SDK
- Começar a usar instâncias do Amazon EC2 com um AWS SDK

Criar e gerenciar um serviço resiliente usando um AWS SDK

Os exemplos de código a seguir mostram como criar um serviço da Web com carga balanceada que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
    static async Task Main(string[] args)
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
```

```
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
```

```
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper =
host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several
AWS resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server.");
```

```
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs
'server_startup_script.sh' when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the
`server.py` script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and
Systems Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
```

```
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3,
_autoScalerWrapper.GroupName, zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or
continue with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the
demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
_autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
```

```
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGro
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.Lo
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port,
 ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for
 your default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management
 Console.\n");
```

```
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
inbound traffic from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port,
ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
ipString);
                }
            }
            loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite
of these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as\n" +
```

```
                            "healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service
fails, the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
"static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
_smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
```

```
            $"Replacing the profile for instance {badInstanceId} with a profile
that contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo,
a deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not
for Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the
Auto Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load
balancer can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two
for the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");
```

```
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by
an auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler
start a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a
successful recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the
load balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance
typically takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
checks mean all instances report as unhealthy.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
```

```
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBal
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGr
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupNa
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you
might incur unexpected charges."
            );
        }
```

```
        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
```

```
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with
 a specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
 granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to
 the role.</param>
    /// <returns>The Arn of the profile.</returns>
```

```
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
                                         "\"Effect\": \"Allow\"," +
                                         "\"Principal\": {" +
                                         "\"Service\": [" +
                                             "\"ec2.amazonaws.com\"" +
                                         "]" +
                                         "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                                    "}]" +
                                "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
```

```
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }
```

```
        string profileArn = "";
        try
        {
            var profileCreateResponse = await
 _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
```

```
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling.
    /// The launch template specifies a Bash script in its user data field that
runs after
    /// the instance is started. This script installs the Python packages and
starts a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to
create and attach to the profile.</param>
    /// <returns>The template object.</returns>
```

```
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName,
_instanceRoleName, _instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new

LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2
Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
```

```
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new
 Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with
 size {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
 exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
```

```
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
 List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }
```

```
    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the
role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
```

```
            var attachedPolicies = await
_amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
```

```
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await
_amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
```

```
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
```

```
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await
_amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for
{instanceId}. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
```

```
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string
groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
```

```
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the
calling computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP
address while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
```

```
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be
open to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0),
or to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
```

```
    /// Add an ingress rule to the specified security group that allows access on
 the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName,
 string targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
```

```
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
```

```
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
```

```
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened
 times and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</
param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer
 exists.</param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
```

```
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
        var loadBalancerReady = false;
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
```

```
                    await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
```

```
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
```

```
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await
_amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn =
targetArn });
                Console.WriteLine($"Deleted load balancing target group
{groupName}.");
```

```
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books,
 movies, and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
```

```
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
```

```
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
```

```
    {
        var recommendationsText = await
 File.ReadAllTextAsync(recommendationsPath);
        var records =

 JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
```

```
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement
 _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-
architecture-table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";

    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
```

```
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers

- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
```

```
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-
prof-bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws IOException,
 InterruptedException {
        Scanner in = new Scanner(System.in);
        Database database = new Database();
        AutoScaler autoScaler = new AutoScaler();
        LoadBalancer loadBalancer = new LoadBalancer();

        System.out.println(DASHES);
        System.out.println("Welcome to the demonstration of How to Build and
 Manage a Resilient Service!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("A - SETUP THE RESOURCES");
        System.out.println("Press Enter when you're ready to start deploying
 resources.");
        in.nextLine();
        deploy(loadBalancer);
        System.out.println(DASHES);
        System.out.println(DASHES);
        System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
        System.out.println("Press Enter when you're ready.");
        in.nextLine();
        demo(loadBalancer);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("C - DELETE THE RESOURCES");
        System.out.println("""
```

```
                This concludes the demo of how to build and manage a resilient
service.
                To keep things tidy and to avoid unwanted charges on your
account, we can clean up all AWS resources
                that were created for this demo.
                """);

        System.out.println("\n Do you want to delete the resources (y/n)? ");
        String userInput = in.nextLine().trim().toLowerCase(); // Capture user
input

        if (userInput.equals("y")) {
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }
```

```
   private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
       Scanner in = new Scanner(System.in);
       System.out.println(
               """
                       For this demo, we'll use the AWS SDK for Java (v2) to
create several AWS resources
                       to set up a load-balanced web service endpoint and
explore some ways to make it resilient
                       against various kinds of failures.

                       Some of the resources create by this demo are:
                       \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                       \t* An EC2 launch template that defines EC2 instances
that each contain a Python web server.
                       \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                       \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                       """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
```

```
                run a web server, such as Apache, with least-privileged
credentials.

                The template also defines an IAM policy that each instance uses
to assume a role that grants
                permissions to access the DynamoDB recommendation table and
Systems Manager parameters
                that control the flow of the demo.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the
demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("""
                Creating an Elastic Load Balancing target group and load
balancer. The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets,
targetGroupArn, lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul =
loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(),
StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
```

```
                            For this example to work, the default security group
for your default VPC must
                            allow access from this computer. You can either add
it automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security
group are configured correctly and that");
            System.out.println("you can successfully make a GET request to the
load balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }
```

```
   // A method that controls the demo part of the Java program.
   public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
       ParameterHelper paramHelper = new ParameterHelper();
       System.out.println("Read the ssm_only_policy.json file");
       String ssmOnlyPolicy = readFileAsString(ssmJSON);

       System.out.println("Resetting parameters to starting values for demo.");
       paramHelper.reset();

       System.out.println(
               """
                       This part of the demonstration shows how to toggle
different parts of the system
                       to create situations where the web service fails, and
shows how using a resilient
                       architecture can keep the web service running in spite
of these failures.

                       At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                      """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                       The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                       The table name is contained in a Systems Manager
parameter named self.param_helper.table.
                       To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.
                      """);
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       System.out.println(
               """
                       \nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as
                       healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.
                      """);
       demoChoices(loadBalancer);
```

```
        System.out.println(
                """
                        Instead of failing when the recommendation service fails,
the web service can return a static response.
                        While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                        """);
        paramHelper.put(paramHelper.failureResponse, "static");

        System.out.println("""
                Now, sending a GET request to the load balancer endpoint returns
a static response.
                The service still reports as healthy because health checks are
still shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance
id value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId =
autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " +
profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
```

```
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on
for recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto
Scaling instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the
load balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);
```

```
        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an
auto scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start
a new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load
balancing rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance
is running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);
```

```
        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode =
response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
```

```
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load
balancer targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
target.target().id(),
                                    target.target().port(),
target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the
health check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value
between 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
```

```
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
```

```
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance
is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile
is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure
'newInstanceProfileName' is a valid IAM Instance Profile
                                                // name.
                .build();
```

```
        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();

        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with
profile %s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
```

```
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress)
{
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
```

```
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);

            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request =
DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }
```

```
            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network,
you
     * must instead specify a prefix list ID. You can also temporarily open the
port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
```

```
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();

            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse =
getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup :
securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " +
secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " +
ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
```

```
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to
be open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);
```

```
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.

software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();

        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
```

```
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability
Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
```

```
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response =
getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
```

```
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
 InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to
 the policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM
 role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
```

```
                DeletePolicyRequest deletePolicyRequest =
DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance
profile " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
```

```
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String
 targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
 DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
 getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
 DescribeTargetHealthRequest.builder()

 .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
 getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
```

```
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()

.loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
```

```
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load
balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws
IOException, InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how
instance
     * health is checked.
```

```
    */
   public String createTargetGroup(String protocol, int port, String vpcId,
String targetGroupName) {
       CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
               .healthCheckPath("/healthcheck")
               .healthCheckTimeoutSeconds(5)
               .port(port)
               .vpcId(vpcId)
               .name(targetGroupName)
               .protocol(protocol)
               .build();

       CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
       String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
       String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
       System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
       return targetGroupArn;
   }

   /*
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String
targetGroupARN, String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();
```

```
            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                    + targetGroupARN);
```

```
            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
```

```
            System.err.println("Error checking table existence: " +
e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended,
such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException
{
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
```

```
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");

            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws
IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable =
enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
```

```
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-
response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
```

```
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances

- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
```

```
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
```

```
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
```

```
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
```

```
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item']
[] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
```

```
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
```

```
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
```

```
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
```

```
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
```

```
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
```

```
    }),
    new ScenarioOutput("gotVpc", (state) =>
      MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
    ),
    new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
    new ScenarioAction("getSubnets", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
      const client = new EC2Client({});
      const { Subnets } = await client.send(
        new DescribeSubnetsCommand({
          Filters: [
            { Name: "vpc-id", Values: [state.defaultVpc] },
            { Name: "availability-zone", Values: state.availabilityZoneNames },
            { Name: "default-for-az", Values: ["true"] },
          ],
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
      state.subnets = Subnets.map((subnet) => subnet.SubnetId);
    }),
    new ScenarioOutput(
      "gotSubnets",
      /**
       * @param {{ subnets: string[] }} state
       */
      (state) =>
        MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
    ),
    new ScenarioOutput(
      "creatingLoadBalancerTargetGroup",
      MESSAGES.creatingLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      ),
    ),
    new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
      const client = new ElasticLoadBalancingV2Client({});
      const { TargetGroups } = await client.send(
        new CreateTargetGroupCommand({
          Name: NAMES.loadBalancerTargetGroupName,
          Protocol: "HTTP",
          Port: 80,
          HealthCheckPath: "/healthcheck",
```

```
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
```

```
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
```

```
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup}} state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
```

```
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
```

```
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
```

```
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
```

```
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
```

```
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
```

```
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
```

```
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-
scaling').Instance }} state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
```

```
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation}} state
     */
    (state) =>
```

```
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
```

```
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
```

```
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
```

```
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";
```

```
/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
```

```
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
```

```
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
```

```
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
```

```
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
```

```
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
```

```
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
```

```
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
```

```
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
```

```
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
```

```
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
```

```
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
```

```
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones

- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22
```

```
    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server."
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
'{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.\n"
```

```
            f"This script starts a Python web server defined in the `server.py`
script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged
credentials.\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
            f"Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or
continue with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load
balancer provides a\n"
```

```
            "single endpoint where clients connect and dispatches requests to
 instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port
 is open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for
 your default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.
\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
```

```
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging
 from your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
                "Couldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                "manually verifying that your VPC and security group are
 configured correctly and that\n"
                "you can successfully make a GET request to the load balancer
 endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
 following choices:\n"
```

```
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health
check to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts
of the system\n"
```

```
            "to create situations where the web service fails, and shows how
using a resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations
by querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't
check for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with
a somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns
a static response.\n"
            f"The service still reports as healthy because health checks are
still shallow.\n"
        )
        self.demo_choices()
```

```
        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a
profile that contains\n"
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto
Scaling instance health.\n"
```

```
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect
when one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
            "\nBecause the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
starting, sending a GET\n"
            "request to the web service continues to get a successful
recommendation response because\n"
            "the load balancer routes requests to the healthy instances. After
the replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
running and healthy.\n"
        )
        self.demo_choices()
```

```
        print(
            "\nIf the recommendation service fails now, deep health checks mean
all instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient
service.\n"
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n"
            "that were created for this demo."
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ",
q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you
might incur unexpected charges."
            )
```

```
def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM
 policies and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
```

```
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
```

```
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are
created by this class.
        """
        as_client = boto3.client("autoscaling")
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
```

```
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is
assumed by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as
AmazonSSMManagedInstanceCore to grant
                                     use of Systems Manager to send commands to
the instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to
role\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response =
self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
```

```
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
```

```
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the
role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
```

```
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.

        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
```

```
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.",
self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling. The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts
a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a
permissions policy
                                     to create and attach to the instance
profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
```

```
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template
{self.launch_template_name}: {err}."
                )
        return template


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
```

```
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template
{self.launch_template_name}: {err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones


    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
```

```
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
```

```
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group
{self.group_name}: {err}"
            )
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance
is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
```

```
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group
%s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
```

```
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] ==
 "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling
 group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")
```

```
    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress
from this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
```

```
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to
either this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
```

```
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port}
from {ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by
 this class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
```

```
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group
specifies how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened
times and
        lower thresholds. In production, you might want to decrease the
sensitivity of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
```

```
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to
do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )
```

```
    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener
to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
```

```
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
        success = False
        retries = 3
        while not success and retries > 0:
            try:
```

```
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint,
retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets:
{err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books,
 movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended,
 such as
        Book or Movie, and a range key named 'ItemId' that, combined with the
 MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
```

```
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5,
"WriteCapacityUnits": 5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name,
data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}:
{err}"
            )
```

```
    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.",
 self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters
 to drive
    the demonstration of resilient architecture, such as failure of a dependency
 or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
```

```
        """
        self.ssm_client = ssm_client
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when
a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups

- CreateAutoScalingGroup
- CreateInstanceProfile
- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Começar a usar instâncias do Amazon EC2 com um AWS SDK

Os exemplos de código a seguir mostram como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.

- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.
- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário em um prompt de comando.

```
/// <summary>
/// Show Amazon Elastic Compute Cloud (Amazon EC2) Basics actions.
/// </summary>
public class EC2Basics
{
    /// <summary>
    /// Perform the actions defined for the Amazon EC2 Basics scenario.
    /// </summary>
    /// <param name="args">Command line arguments.</param>
    /// <returns>A Task object.</returns>
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EC2 and Amazon Simple Systems
        // Management Service.
        using var host =
 Microsoft.Extensions.Hosting.Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonEC2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddTransient<EC2Wrapper>()
                    .AddTransient<SsmWrapper>()
            )
            .Build();

        // Now the client is available for injection.
```

```
        var ec2Client = host.Services.GetRequiredService<IAmazonEC2>();
        var ec2Methods = new EC2Wrapper(ec2Client);

        var ssmClient =
host.Services.GetRequiredService<IAmazonSimpleSystemsManagement>();
        var ssmMethods = new SsmWrapper(ssmClient);
        var uiMethods = new UiMethods();

        var uniqueName = Guid.NewGuid().ToString();
        var keyPairName = "mvp-example-key-pair" + uniqueName;
        var groupName = "ec2-scenario-group" + uniqueName;
        var groupDescription = "A security group created for the EC2 Basics
scenario.";

        // Start the scenario.
        uiMethods.DisplayOverview();
        uiMethods.PressEnter();

        // Create the key pair.
        uiMethods.DisplayTitle("Create RSA key pair");
        Console.Write("Let's create an RSA key pair that you can be use to ");
        Console.WriteLine("securely connect to your EC2 instance.");
        var keyPair = await ec2Methods.CreateKeyPair(keyPairName);

        // Save key pair information to a temporary file.
        var tempFileName = ec2Methods.SaveKeyPair(keyPair);

        Console.WriteLine($"Created the key pair: {keyPair.KeyName} and saved it
to: {tempFileName}");
        string? answer;
        do
        {
            Console.Write("Would you like to list your existing key pairs? ");
            answer = Console.ReadLine();
        } while (answer!.ToLower() != "y" && answer.ToLower() != "n");

        if (answer == "y")
        {
            // List existing key pairs.
            uiMethods.DisplayTitle("Existing key pairs");

            // Passing an empty string to the DescribeKeyPairs method will return
            // a list of all existing key pairs.
            var keyPairs = await ec2Methods.DescribeKeyPairs("");
```

```
            keyPairs.ForEach(kp =>
            {
                Console.WriteLine($"{kp.KeyName} created at: {kp.CreateTime}
 Fingerprint: {kp.KeyFingerprint}");
            });
        }
        uiMethods.PressEnter();

        // Create the security group.
        Console.WriteLine("Let's create a security group to manage access to your
 instance.");
        var secGroupId = await ec2Methods.CreateSecurityGroup(groupName,
 groupDescription);
        Console.WriteLine("Let's add rules to allow all HTTP and HTTPS inbound
 traffic and to allow SSH only from your current IP address.");

        uiMethods.DisplayTitle("Security group information");
        var secGroups = await ec2Methods.DescribeSecurityGroups(secGroupId);

        Console.WriteLine($"Created security group {groupName} in your default
 VPC.");
        secGroups.ForEach(group =>
        {
            ec2Methods.DisplaySecurityGroupInfoAsync(group);
        });
        uiMethods.PressEnter();

        Console.WriteLine("Now we'll authorize the security group we just created
 so that it can");
        Console.WriteLine("access the EC2 instances you create.");
        var success = await ec2Methods.AuthorizeSecurityGroupIngress(groupName);

        secGroups = await ec2Methods.DescribeSecurityGroups(secGroupId);
        Console.WriteLine($"Now let's look at the permissions again.");
        secGroups.ForEach(group =>
        {
            ec2Methods.DisplaySecurityGroupInfoAsync(group);
        });
        uiMethods.PressEnter();

        // Get list of available Amazon Linux 2 Amazon Machine Images (AMIs).
        var parameters = await ssmMethods.GetParametersByPath("/aws/service/ami-
amazon-linux-latest");
```

```
        List<string> imageIds = parameters.Select(param => param.Value).ToList();

        var images = await ec2Methods.DescribeImages(imageIds);

        var i = 1;
        images.ForEach(image =>
        {
            Console.WriteLine($"\t{i++}\t{image.Description}");
        });

        int choice;
        bool validNumber = false;

        do
        {
            Console.Write("Please select an image: ");
            var selImage = Console.ReadLine();
            validNumber = int.TryParse(selImage, out choice);
        } while (!validNumber);

        var selectedImage = images[choice - 1];

        // Display available instance types.
        uiMethods.DisplayTitle("Instance Types");
        var instanceTypes = await
ec2Methods.DescribeInstanceTypes(selectedImage.Architecture);

        i = 1;
        instanceTypes.ForEach(instanceType =>
        {
            Console.WriteLine($"\t{i++}\t{instanceType.InstanceType}");
        });

        do
        {
            Console.Write("Please select an instance type: ");
            var selImage = Console.ReadLine();
            validNumber = int.TryParse(selImage, out choice);
        } while (!validNumber);

        var selectedInstanceType = instanceTypes[choice - 1].InstanceType;

        // Create an EC2 instance.
        uiMethods.DisplayTitle("Creating an EC2 Instance");
```

```
        var instanceId = await ec2Methods.RunInstances(selectedImage.ImageId,
 selectedInstanceType, keyPairName, secGroupId);
        Console.Write("Waiting for the instance to start.");
        var isRunning = false;
        do
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        uiMethods.PressEnter();

        var instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nYou can use SSH to connect to your instance. For
 example:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        uiMethods.PressEnter();

        Console.WriteLine("Now we'll stop the instance and then start it again to
 see what's changed.");

        await ec2Methods.StopInstances(instanceId);
        var hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");

        Console.WriteLine("Now let's start it up again.");
        await ec2Methods.StartInstances(instanceId);
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
```

```
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        Console.WriteLine("\nLet's see what changed.");

        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nNotice the change in the SSH information:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        uiMethods.PressEnter();

        Console.WriteLine("Now we will stop the instance again. Then we will
 create and associate an");
        Console.WriteLine("Elastic IP address to use with our instance.");

        await ec2Methods.StopInstances(instanceId);
        hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("Allocate Elastic IP address");
        Console.WriteLine("You can allocate an Elastic IP address and associate
 it with your instance\nto keep a consistent IP address even when your instance
 restarts.");
        var allocationId = await ec2Methods.AllocateAddress();
        Console.WriteLine("Now we will associate the Elastic IP address with our
 instance.");
        var associationId = await ec2Methods.AssociateAddress(allocationId,
 instanceId);

        // Start the instance again.
        Console.WriteLine("Now let's start the instance again.");
        await ec2Methods.StartInstances(instanceId);
```

```
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        Console.WriteLine("\nLet's see what changed.");

        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("Instance information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nHere is the SSH information:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        Console.WriteLine("Let's stop and start the instance again.");
        uiMethods.PressEnter();

        await ec2Methods.StopInstances(instanceId);

        hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");

        Console.WriteLine("Now let's start it up again.");
        await ec2Methods.StartInstances(instanceId);
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);
```

```
        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);
        Console.WriteLine("Note that the IP address did not change this time.");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("Clean up resources");

        Console.WriteLine("Now let's clean up the resources we created.");

        // Terminate the instance.
        Console.WriteLine("Terminating the instance we created.");
        var stateChange = await ec2Methods.TerminateInstances(instanceId);

        // Wait for the instance state to be terminated.
        var hasTerminated = false;
        do
        {
            hasTerminated = await ec2Methods.WaitForInstanceState(instanceId,
InstanceStateName.Terminated);
        } while (!hasTerminated);

        Console.WriteLine($"\nThe instance {instanceId} has been terminated.");
        Console.WriteLine("Now we can disassociate the Elastic IP address and
release it.");

        // Disassociate the Elastic IP address.
        var disassociated = ec2Methods.DisassociateIp(associationId);

        // Delete the Elastic IP address.
        var released = ec2Methods.ReleaseAddress(allocationId);

        // Delete the security group.
        Console.WriteLine($"Deleting the Security Group: {groupName}.");
        success = await ec2Methods.DeleteSecurityGroup(secGroupId);
        if (success)
        {
            Console.WriteLine($"Successfully deleted {groupName}.");
        }

        // Delete the RSA key pair.
        Console.WriteLine($"Deleting the key pair: {keyPairName}");
        await ec2Methods.DeleteKeyPair(keyPairName);
```

```
        Console.WriteLine("Deleting the temporary file with the key
 information.");
        ec2Methods.DeleteTempFile(tempFileName);
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("EC2 Basics Scenario completed.");
        uiMethods.PressEnter();
    }
}
```

Defina uma classe que envolva as ações do EC2.

```
/// <summary>
/// Methods of this class perform Amazon Elastic Compute Cloud (Amazon EC2).
/// </summary>
public class EC2Wrapper
{
    private readonly IAmazonEC2 _amazonEC2;

    public EC2Wrapper(IAmazonEC2 amazonService)
    {
        _amazonEC2 = amazonService;
    }

    /// <summary>
    /// Allocate an Elastic IP address.
    /// </summary>
    /// <returns>The allocation Id of the allocated address.</returns>
    public async Task<string> AllocateAddress()
    {
        var request = new AllocateAddressRequest();

        var response = await _amazonEC2.AllocateAddressAsync(request);
        return response.AllocationId;
    }

    /// <summary>
    /// Associate an Elastic IP address to an EC2 instance.
    /// </summary>
    /// <param name="allocationId">The allocation Id of an Elastic IP address.</
param>
    /// <param name="instanceId">The instance Id of the EC2 instance to
```

```
    /// associate the address with.</param>
    /// <returns>The association Id that represents
    /// the association of the Elastic IP address with an instance.</returns>
    public async Task<string> AssociateAddress(string allocationId, string
instanceId)
    {
        var request = new AssociateAddressRequest
        {
            AllocationId = allocationId,
            InstanceId = instanceId
        };

        var response = await _amazonEC2.AssociateAddressAsync(request);
        return response.AssociationId;
    }

    /// <summary>
    /// Authorize the local computer ingress to EC2 instances associated
    /// with the virtual private cloud (VPC) security group.
    /// </summary>
    /// <param name="groupName">The name of the security group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AuthorizeSecurityGroupIngress(string groupName)
    {
        // Get the IP address for the local computer.
        var ipAddress = await GetIpAddress();
        Console.WriteLine($"Your IP address is: {ipAddress}");
        var ipRanges = new List<IpRange> { new IpRange { CidrIp =
$"{ipAddress}/32" } };
        var permission = new IpPermission
        {
            Ipv4Ranges = ipRanges,
            IpProtocol = "tcp",
            FromPort = 22,
            ToPort = 22
        };
        var permissions = new List<IpPermission> { permission };
        var response = await _amazonEC2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest(groupName, permissions));
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Authorize the local computer for ingress to
```

```
    /// the Amazon EC2 SecurityGroup.
    /// </summary>
    /// <returns>The IPv4 address of the computer running the scenario.</returns>
    private static async Task<string> GetIpAddress()
    {
        var httpClient = new HttpClient();
        var ipString = await httpClient.GetStringAsync("https://
checkip.amazonaws.com");

        // The IP address is returned with a new line
        // character on the end. Trim off the whitespace and
        // return the value to the caller.
        return ipString.Trim();
    }

    /// <summary>
    /// Create an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name for the new key pair.</param>
    /// <returns>The Amazon EC2 key pair created.</returns>
    public async Task<KeyPair?> CreateKeyPair(string keyPairName)
    {
        var request = new CreateKeyPairRequest
        {
            KeyName = keyPairName,
        };

        var response = await _amazonEC2.CreateKeyPairAsync(request);

        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            var kp = response.KeyPair;
            return kp;
        }
        else
        {
            Console.WriteLine("Could not create key pair.");
            return null;
        }
    }

    /// <summary>
    /// Save KeyPair information to a temporary file.
    /// </summary>
```

```
    /// <param name="keyPair">The name of the key pair.</param>
    /// <returns>The full path to the temporary file.</returns>
    public string SaveKeyPair(KeyPair keyPair)
    {
        var tempPath = Path.GetTempPath();
        var tempFileName = $"{tempPath}\\{Path.GetRandomFileName()}";
        var pemFileName = Path.ChangeExtension(tempFileName, "pem");

        // Save the key pair to a file in a temporary folder.
        using var stream = new FileStream(pemFileName, FileMode.Create);
        using var writer = new StreamWriter(stream);
        writer.WriteLine(keyPair.KeyMaterial);

        return pemFileName;
    }

    /// <summary>
    /// Create an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name for the new security group.</param>
    /// <param name="groupDescription">A description of the new security group.</
param>
    /// <returns>The group Id of the new security group.</returns>
    public async Task<string> CreateSecurityGroup(string groupName, string
 groupDescription)
    {
        var response = await _amazonEC2.CreateSecurityGroupAsync(
            new CreateSecurityGroupRequest(groupName, groupDescription));

        return response.GroupId;
    }


    /// <summary>
    /// Create a new Amazon EC2 VPC.
    /// </summary>
    /// <param name="cidrBlock">The CIDR block for the new security group.</
param>
    /// <returns>The VPC Id of the new VPC.</returns>
    public async Task<string?> CreateVPC(string cidrBlock)
    {

        try
        {
```

```
            var response = await _amazonEC2.CreateVpcAsync(new CreateVpcRequest
            {
                CidrBlock = cidrBlock,
            });

            Vpc vpc = response.Vpc;
            Console.WriteLine($"Created VPC with ID: {vpc.VpcId}.");
            return vpc.VpcId;
        }
        catch (AmazonEC2Exception ex)
        {
            Console.WriteLine($"Couldn't create VPC because: {ex.Message}");
            return null;
        }
    }

    /// <summary>
    /// Delete an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyPair(string keyPairName)
    {
        try
        {
            await _amazonEC2.DeleteKeyPairAsync(new
DeleteKeyPairRequest(keyPairName)).ConfigureAwait(false);
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Couldn't delete the key pair because:
{ex.Message}");
            return false;
        }
    }

    /// <summary>
    /// Delete the temporary file where the key pair information was saved.
    /// </summary>
    /// <param name="tempFileName">The path to the temporary file.</param>
    public void DeleteTempFile(string tempFileName)
    {
        if (File.Exists(tempFileName))
```

```
        {
            File.Delete(tempFileName);
        }
    }

    /// <summary>
    /// Delete an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteSecurityGroup(string groupId)
    {
        var response = await _amazonEC2.DeleteSecurityGroupAsync(new
 DeleteSecurityGroupRequest { GroupId = groupId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete an Amazon EC2 VPC.
    /// </summary>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteVpc(string vpcId)
    {
        var request = new DeleteVpcRequest
        {
            VpcId = vpcId,
        };

        var response = await _amazonEC2.DeleteVpcAsync(request);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Get information about existing Amazon EC2 images.
    /// </summary>
    /// <returns>A list of image information.</returns>
    public async Task<List<Image>> DescribeImages(List<string>? imageIds)
    {
        var request = new DescribeImagesRequest();
        if (imageIds is not null)
        {
            // If the imageIds list is not null, add the list
            // to the request object.
```

```
            request.ImageIds = imageIds;
        }

        var response = await _amazonEC2.DescribeImagesAsync(request);
        return response.Images;
    }

    /// <summary>
    /// Display the information returned by DescribeImages.
    /// </summary>
    /// <param name="images">The list of image information to display.</param>
    public void DisplayImageInfo(List<Image> images)
    {
        images.ForEach(image =>
        {
            Console.WriteLine($"{image.Name} Created on: {image.CreationDate}");
        });

    }

    /// <summary>
    /// Get information about an Amazon EC2 instance.
    /// </summary>
    /// <param name="instanceId">The instance Id of the EC2 instance.</param>
    /// <returns>An EC2 instance.</returns>
    public async Task<Instance> DescribeInstance(string instanceId)
    {
        var response = await _amazonEC2.DescribeInstancesAsync(
            new DescribeInstancesRequest { InstanceIds = new List<string>
{ instanceId } });
        return response.Reservations[0].Instances[0];
    }

    /// <summary>
    /// Display EC2 instance information.
    /// </summary>
    /// <param name="instance">The instance Id of the EC2 instance.</param>
    public void DisplayInstanceInformation(Instance instance)
    {
        Console.WriteLine($"ID: {instance.InstanceId}");
        Console.WriteLine($"Image ID: {instance.ImageId}");
        Console.WriteLine($"{instance.InstanceType}");
        Console.WriteLine($"Key Name: {instance.KeyName}");
        Console.WriteLine($"VPC ID: {instance.VpcId}");
```

```
        Console.WriteLine($"Public IP: {instance.PublicIpAddress}");
        Console.WriteLine($"State: {instance.State.Name}");
    }

    /// <summary>
    /// Get information about existing EC2 images.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task DescribeInstances()
    {
        // List all EC2 instances.
        await GetInstanceDescriptions();

        string tagName = "IncludeInList";
        string tagValue = "Yes";
        await GetInstanceDescriptionsFiltered(tagName, tagValue);
    }

    /// <summary>
    /// Get information for all existing Amazon EC2 instances.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptions()
    {
        Console.WriteLine("Showing all instances:");
        var paginator = _amazonEC2.Paginators.DescribeInstances(new
DescribeInstancesRequest());

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId}");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Get information about EC2 instances filtered by a tag name and value.
    /// </summary>
```

```
    /// <param name="tagName">The name of the tag to filter on.</param>
    /// <param name="tagValue">The value of the tag to look for.</param>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptionsFiltered(string tagName, string
tagValue)
    {
        // This tag filters the results of the instance list.
        var filters = new List<Filter>
        {
            new Filter
            {
                Name = $"tag:{tagName}",
                Values = new List<string>
                {
                    tagValue,
                },
            },
        };
        var request = new DescribeInstancesRequest
        {
            Filters = filters,
        };

        Console.WriteLine("\nShowing instances with tag: \"IncludeInList\" set to
\"Yes\".");
        var paginator = _amazonEC2.Paginators.DescribeInstances(request);

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId} ");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Describe the instance types available.
    /// </summary>
    /// <returns>A list of instance type information.</returns>
```

```
    public async Task<List<InstanceTypeInfo>>
 DescribeInstanceTypes(ArchitectureValues architecture)
    {
        var request = new DescribeInstanceTypesRequest();

        var filters = new List<Filter>
            { new Filter("processor-info.supported-architecture", new
 List<string> { architecture.ToString() }) };
        filters.Add(new Filter("instance-type", new() { "*.micro", "*.small" }));

        request.Filters = filters;
        var instanceTypes = new List<InstanceTypeInfo>();

        var paginator = _amazonEC2.Paginators.DescribeInstanceTypes(request);
        await foreach (var instanceType in paginator.InstanceTypes)
        {
            instanceTypes.Add(instanceType);
        }
        return instanceTypes;
    }

    /// <summary>
    /// Display the instance type information returned by
 DescribeInstanceTypesAsync.
    /// </summary>
    /// <param name="instanceTypes">The list of instance type information.</
param>
    public void DisplayInstanceTypeInfo(List<InstanceTypeInfo> instanceTypes)
    {
        instanceTypes.ForEach(type =>
        {
            Console.WriteLine($"{type.InstanceType}\t{type.MemoryInfo}");
        });
    }

    /// <summary>
    /// Get information about an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair.</param>
    /// <returns>A list of key pair information.</returns>
    public async Task<List<KeyPairInfo>> DescribeKeyPairs(string keyPairName)
    {
        var request = new DescribeKeyPairsRequest();
        if (!string.IsNullOrEmpty(keyPairName))
```

```
        {
            request = new DescribeKeyPairsRequest
            {
                KeyNames = new List<string> { keyPairName }
            };
        }
        var response = await _amazonEC2.DescribeKeyPairsAsync(request);
        return response.KeyPairs.ToList();
    }


    /// <summary>
    /// Retrieve information for an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupId">The Id of the Amazon EC2 security group.</param>
    /// <returns>A list of security group information.</returns>
    public async Task<List<SecurityGroup>> DescribeSecurityGroups(string groupId)
    {
        var request = new DescribeSecurityGroupsRequest();
        var groupIds = new List<string> { groupId };
        request.GroupIds = groupIds;

        var response = await _amazonEC2.DescribeSecurityGroupsAsync(request);
        return response.SecurityGroups;
    }

    /// <summary>
    /// Display the information returned by the call to
    /// DescribeSecurityGroupsAsync.
    /// </summary>
    /// <param name="securityGroup">A list of security group information.</param>
    public void DisplaySecurityGroupInfoAsync(SecurityGroup securityGroup)
    {
        Console.WriteLine($"{securityGroup.GroupName}");
        Console.WriteLine("Ingress permissions:");
        securityGroup.IpPermissions.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIp} "); });
```

```
            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
        Console.WriteLine("Egress permissions:");
        securityGroup.IpPermissionsEgress.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIp} "); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
    }


    /// <summary>
    /// Disassociate an Elastic IP address from an EC2 instance.
    /// </summary>
    /// <param name="associationId">The association Id.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DisassociateIp(string associationId)
    {
        var response = await _amazonEC2.DisassociateAddressAsync(
            new DisassociateAddressRequest { AssociationId = associationId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
```

```
    /// Retrieve a list of available Amazon Linux images.
    /// </summary>
    /// <returns>A list of image information.</returns>
    public async Task<List<Image>> GetEC2AmiList()
    {
        var filter = new Filter { Name = "architecture", Values = new
 List<string> { "x86_64" } };
        var filters = new List<Filter> { filter };
        var response = await _amazonEC2.DescribeImagesAsync(new
 DescribeImagesRequest { Filters = filters });
        return response.Images;
    }

    /// <summary>
    /// Reboot EC2 instances.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the instances that will be
 rebooted.</param>
    /// <returns>Async task.</returns>
    public async Task RebootInstances(string ec2InstanceId)
    {
        var request = new RebootInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.RebootInstancesAsync(request);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine("Instances successfully rebooted.");
        }
        else
        {
            Console.WriteLine("Could not reboot one or more instances.");
        }
    }

    /// <summary>
    /// Release an Elastic IP address.
    /// </summary>
    /// <param name="allocationId">The allocation Id of the Elastic IP address.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> ReleaseAddress(string allocationId)
```

```
    {
        var request = new ReleaseAddressRequest
        {
            AllocationId = allocationId
        };

        var response = await _amazonEC2.ReleaseAddressAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Create and run an EC2 instance.
    /// </summary>
    /// <param name="ImageId">The image Id of the image used as a basis for the
    /// EC2 instance.</param>
    /// <param name="instanceType">The instance type of the EC2 instance to
create.</param>
    /// <param name="keyName">The name of the key pair to associate with the
    /// instance.</param>
    /// <param name="groupId">The Id of the Amazon EC2 security group that will
be
    /// allowed to interact with the new EC2 instance.</param>
    /// <returns>The instance Id of the new EC2 instance.</returns>
    public async Task<string> RunInstances(string imageId, string instanceType,
string keyName, string groupId)
    {
        var request = new RunInstancesRequest
        {
            ImageId = imageId,
            InstanceType = instanceType,
            KeyName = keyName,
            MinCount = 1,
            MaxCount = 1,
            SecurityGroupIds = new List<string> { groupId }
        };
        var response = await _amazonEC2.RunInstancesAsync(request);
        return response.Reservation.Instances[0].InstanceId;
    }


    /// <summary>
    /// Start an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the Amazon EC2 instance
```

```
    /// to start.</param>
    /// <returns>Async task.</returns>
    public async Task StartInstances(string ec2InstanceId)
    {
        var request = new StartInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StartInstancesAsync(request);

        if (response.StartingInstances.Count > 0)
        {
            var instances = response.StartingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully started the EC2 instance with
instance ID: {i.InstanceId}.");
            });
        }
    }

    /// <summary>
    /// Stop an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance to
    /// stop.</param>
    /// <returns>Async task.</returns>
    public async Task StopInstances(string ec2InstanceId)
    {
        // In addition to the list of instance Ids, the
        // request can also include the following properties:
        //     Force      When true, forces the instances to
        //                stop but you must check the integrity
        //                of the file system. Not recommended on
        //                Windows instances.
        //     Hibernate  When true, hibernates the instance if the
        //                instance was enabled for hibernation when
        //                it was launched.
        var request = new StopInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };
```

```
        var response = await _amazonEC2.StopInstancesAsync(request);

        if (response.StoppingInstances.Count > 0)
        {
            var instances = response.StoppingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully stopped the EC2 Instance " +
                                  $"with InstanceID: {i.InstanceId}.");
            });
        }
    }

    /// <summary>
    /// Terminate an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance
    /// to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task<List<InstanceStateChange>> TerminateInstances(string
ec2InstanceId)
    {
        var request = new TerminateInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId }
        };

        var response = await _amazonEC2.TerminateInstancesAsync(request);
        return response.TerminatingInstances;
    }

    /// <summary>
    /// Wait until an EC2 instance is in a specified state.
    /// </summary>
    /// <param name="instanceId">The instance Id.</param>
    /// <param name="stateName">The state to wait for.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitForInstanceState(string instanceId,
InstanceStateName stateName)
    {
        var request = new DescribeInstancesRequest
        {
            InstanceIds = new List<string> { instanceId }
        };
```

```
        // Wait until the instance is running.
        var hasState = false;
        do
        {
            // Wait 5 seconds.
            Thread.Sleep(5000);

            // Check for the desired state.
            var response = await _amazonEC2.DescribeInstancesAsync(request);
            var instance = response.Reservations[0].Instances[0];
            hasState = instance.State.Name == stateName;
            Console.Write(". ");
        } while (!hasState);

        return hasState;
    }

}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress

- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java example performs the following tasks:
 *
 * 1. Creates an RSA key pair and saves the private key data as a .pem file.
 * 2. Lists key pairs.
 * 3. Creates a security group for the default VPC.
 * 4. Displays security group information.
 * 5. Gets a list of Amazon Linux 2 AMIs and selects one.
 * 6. Gets more information about the image.
 * 7. Gets a list of instance types that are compatible with the selected AMI’s
 * architecture.
 * 8. Creates an instance with the key pair, security group, AMI, and an
 * instance type.
 * 9. Displays information about the instance.
 * 10. Stops the instance and waits for it to stop.
 * 11. Starts the instance and waits for it to start.
```

```
 * 12. Allocates an Elastic IP address and associates it with the instance.
 * 13. Displays SSH connection info for the instance.
 * 14. Disassociates and deletes the Elastic IP address.
 * 15. Terminates the instance and waits for it to terminate.
 * 16. Deletes the security group.
 * 17. Deletes the key pair.
 */
public class EC2Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException {

        final String usage = """

                Usage:
                   <keyName> <fileName> <groupName> <groupDesc> <vpcId>

                Where:
                   keyName -  A key pair name (for example, TestKeyPair).\s
                   fileName -  A file name where the key information is written
 to.\s
                   groupName - The name of the security group.\s
                   groupDesc - The description of the security group.\s
                   vpcId - A VPC Id value. You can get this value from the AWS
 Management Console.\s
                   myIpAddress - The IP address of your development machine.\s

                """;

        if (args.length != 6) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyName = args[0];
        String fileName = args[1];
        String groupName = args[2];
        String groupDesc = args[3];
        String vpcId = args[4];
        String myIpAddress = args[5];

        Region region = Region.US_WEST_2;
        Ec2Client ec2 = Ec2Client.builder()
```

```
                .region(region)
                .build();

        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon EC2 example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an RSA key pair and save the private key
 material as a .pem file.");
        createKeyPair(ec2, keyName, fileName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. List key pairs.");
        describeKeys(ec2);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Create a security group.");
        String groupId = createSecurityGroup(ec2, groupName, groupDesc, vpcId,
 myIpAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Display security group info for the newly created
 security group.");
        describeSecurityGroups(ec2, groupId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get a list of Amazon Linux 2 AMIs and selects one
 with amzn2 in the name.");
        String instanceId = getParaValues(ssmClient);
        System.out.println("The instance Id is " + instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Get more information about an amzn2 image.");
        String amiValue = describeImage(ec2, instanceId);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of instance types.");
        String instanceType = getInstanceTypes(ec2);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Create an instance.");
        String newInstanceId = runInstance(ec2, instanceType, keyName, groupName,
 amiValue);
        System.out.println("The instance Id is " + newInstanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Display information about the running instance.
 ");
        String ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Stop the instance and use a waiter.");
        stopInstance(ec2, newInstanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Start the instance and use a waiter.");
        startInstance(ec2, newInstanceId);
        ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Allocate an Elastic IP address and associate it
 with the instance.");
        String allocationId = allocateAddress(ec2);
        System.out.println("The allocation Id value is " + allocationId);
        String associationId = associateAddress(ec2, newInstanceId,
 allocationId);
        System.out.println("The associate Id value is " + associationId);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("13. Describe the instance again.");
        ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Disassociate and release the Elastic IP
address.");
        disassociateAddress(ec2, associationId);
        releaseEC2Address(ec2, allocationId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Terminate the instance and use a waiter.");
        terminateEC2(ec2, newInstanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete the security group.");
        deleteEC2SecGroup(ec2, groupId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Delete the key.");
        deleteKeys(ec2, keyName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("You successfully completed the Amazon EC2
scenario.");
        System.out.println(DASHES);
        ec2.close();
    }

    public static void deleteEC2SecGroup(Ec2Client ec2, String groupId) {
        try {
            DeleteSecurityGroupRequest request =
DeleteSecurityGroupRequest.builder()
                    .groupId(groupId)
                    .build();
```

```
            ec2.deleteSecurityGroup(request);
            System.out.println("Successfully deleted security group with Id " +
groupId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void terminateEC2(Ec2Client ec2, String instanceId) {
        try {
            Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                    .overrideConfiguration(b -> b.maxAttempts(100))
                    .client(ec2)
                    .build();

            TerminateInstancesRequest ti = TerminateInstancesRequest.builder()
                    .instanceIds(instanceId)
                    .build();

            System.out.println("Use an Ec2Waiter to wait for the instance to
terminate. This will take a few minutes.");
            ec2.terminateInstances(ti);
            DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                    .instanceIds(instanceId)
                    .build();

            WaiterResponse<DescribeInstancesResponse> waiterResponse = ec2Waiter
                    .waitUntilInstanceTerminated(instanceRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Successfully started instance " + instanceId);
            System.out.println(instanceId + " is terminated!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteKeys(Ec2Client ec2, String keyPair) {
        try {
            DeleteKeyPairRequest request = DeleteKeyPairRequest.builder()
```

```
                    .keyName(keyPair)
                    .build();

            ec2.deleteKeyPair(request);
            System.out.println("Successfully deleted key pair named " + keyPair);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void releaseEC2Address(Ec2Client ec2, String allocId) {
        try {
            ReleaseAddressRequest request = ReleaseAddressRequest.builder()
                    .allocationId(allocId)
                    .build();

            ec2.releaseAddress(request);
            System.out.println("Successfully released Elastic IP address " +
allocId);
        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void disassociateAddress(Ec2Client ec2, String associationId) {
        try {
            DisassociateAddressRequest addressRequest =
DisassociateAddressRequest.builder()
                    .associationId(associationId)
                    .build();

            ec2.disassociateAddress(addressRequest);
            System.out.println("You successfully disassociated the address!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static String associateAddress(Ec2Client ec2, String instanceId,
String allocationId) {
       try {
           AssociateAddressRequest associateRequest =
AssociateAddressRequest.builder()
                   .instanceId(instanceId)
                   .allocationId(allocationId)
                   .build();

           AssociateAddressResponse associateResponse =
ec2.associateAddress(associateRequest);
           return associateResponse.associationId();

       } catch (Ec2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }

   public static String allocateAddress(Ec2Client ec2) {
       try {
           AllocateAddressRequest allocateRequest =
AllocateAddressRequest.builder()
                   .domain(DomainType.VPC)
                   .build();

           AllocateAddressResponse allocateResponse =
ec2.allocateAddress(allocateRequest);
           return allocateResponse.allocationId();

       } catch (Ec2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }

   public static void startInstance(Ec2Client ec2, String instanceId) {
       Ec2Waiter ec2Waiter = Ec2Waiter.builder()
               .overrideConfiguration(b -> b.maxAttempts(100))
               .client(ec2)
               .build();
```

```
        StartInstancesRequest request = StartInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to run.
This will take a few minutes.");
        ec2.startInstances(request);
        DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceRunning(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully started instance " + instanceId);
    }

    public static void stopInstance(Ec2Client ec2, String instanceId) {
        Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                .overrideConfiguration(b -> b.maxAttempts(100))
                .client(ec2)
                .build();
        StopInstancesRequest request = StopInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to stop.
This will take a few minutes.");
        ec2.stopInstances(request);
        DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceStopped(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully stopped instance " + instanceId);
    }

    public static String describeEC2Instances(Ec2Client ec2, String
newInstanceId) {
        try {
```

```
            String pubAddress = "";
            boolean isRunning = false;
            DescribeInstancesRequest request = DescribeInstancesRequest.builder()
                    .instanceIds(newInstanceId)
                    .build();

            while (!isRunning) {
                DescribeInstancesResponse response =
ec2.describeInstances(request);
                String state =
response.reservations().get(0).instances().get(0).state().name().name();
                if (state.compareTo("RUNNING") == 0) {
                    System.out.println("Image id is " +
response.reservations().get(0).instances().get(0).imageId());
                    System.out.println(
                            "Instance type is " +
response.reservations().get(0).instances().get(0).instanceType());
                    System.out.println(
                            "Instance state is " +
response.reservations().get(0).instances().get(0).state().name());
                    pubAddress =
response.reservations().get(0).instances().get(0).publicIpAddress();
                    System.out.println("Instance address is " + pubAddress);
                    isRunning = true;
                }
            }
            return pubAddress;
        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static String runInstance(Ec2Client ec2, String instanceType, String
keyName, String groupName,
            String amiId) {
        try {
            RunInstancesRequest runRequest = RunInstancesRequest.builder()
                    .instanceType(instanceType)
                    .keyName(keyName)
                    .securityGroups(groupName)
                    .maxCount(1)
                    .minCount(1)
```

```
                    .imageId(amiId)
                    .build();

            RunInstancesResponse response = ec2.runInstances(runRequest);
            String instanceId = response.instances().get(0).instanceId();
            System.out.println("Successfully started EC2 instance " + instanceId
+ " based on AMI " + amiId);
            return instanceId;

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Get a list of instance types.
    public static String getInstanceTypes(Ec2Client ec2) {
        String instanceType = "";
        try {
            List<Filter> filters = new ArrayList<>();
            Filter filter = Filter.builder()
                    .name("processor-info.supported-architecture")
                    .values("arm64")
                    .build();

            filters.add(filter);
            DescribeInstanceTypesRequest typesRequest =
DescribeInstanceTypesRequest.builder()
                    .filters(filters)
                    .maxResults(10)
                    .build();

            DescribeInstanceTypesResponse response =
ec2.describeInstanceTypes(typesRequest);
            List<InstanceTypeInfo> instanceTypes = response.instanceTypes();
            for (InstanceTypeInfo type : instanceTypes) {
                System.out.println("The memory information of this type is " +
type.memoryInfo().sizeInMiB());
                System.out.println("Network information is " +
type.networkInfo().toString());
                instanceType = type.instanceType().toString();
            }
```

```
            return instanceType;

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Display the Description field that corresponds to the instance Id value.
    public static String describeImage(Ec2Client ec2, String instanceId) {
        try {
            DescribeImagesRequest imagesRequest = DescribeImagesRequest.builder()
                    .imageIds(instanceId)
                    .build();

            DescribeImagesResponse response = ec2.describeImages(imagesRequest);
            System.out.println("The description of the first image is " +
response.images().get(0).description());
            System.out.println("The name of the first image is " +
response.images().get(0).name());

            // Return the image Id value.
            return response.images().get(0).imageId();

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Get the Id value of an instance with amzn2 in the name.
    public static String getParaValues(SsmClient ssmClient) {
        try {
            GetParametersByPathRequest parameterRequest =
GetParametersByPathRequest.builder()
                    .path("/aws/service/ami-amazon-linux-latest")
                    .build();

            GetParametersByPathIterable responses =
ssmClient.getParametersByPathPaginator(parameterRequest);
```

```
            for
(software.amazon.awssdk.services.ssm.model.GetParametersByPathResponse
response : responses) {
                System.out.println("Test " + response.nextToken());
                List<Parameter> parameterList = response.parameters();
                for (Parameter para : parameterList) {
                    System.out.println("The name of the para is: " +
para.name());
                    System.out.println("The type of the para is: " +
para.type());
                    if (filterName(para.name())) {
                        return para.value();
                    }
                }
            }

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Return true if the name has amzn2 in it. For example:
    // /aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-arm64-gp2
    private static boolean filterName(String name) {
        String[] parts = name.split("/");
        String myValue = parts[4];
        return myValue.contains("amzn2");
    }

    public static void describeSecurityGroups(Ec2Client ec2, String groupId) {
        try {
            DescribeSecurityGroupsRequest request =
DescribeSecurityGroupsRequest.builder()
                    .groupIds(groupId)
                    .build();

            DescribeSecurityGroupsResponse response =
ec2.describeSecurityGroups(request);
            for (SecurityGroup group : response.securityGroups()) {
                System.out
                        .println("Found Security Group with Id " +
group.groupId() + " and group VPC " + group.vpcId());
```

```
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createSecurityGroup(Ec2Client ec2, String groupName,
String groupDesc, String vpcId,
            String myIpAddress) {
        try {
            CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                    .groupName(groupName)
                    .description(groupDesc)
                    .vpcId(vpcId)
                    .build();

            CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);
            IpRange ipRange = IpRange.builder()
                    .cidrIp(myIpAddress + "/0")
                    .build();

            IpPermission ipPerm = IpPermission.builder()
                    .ipProtocol("tcp")
                    .toPort(80)
                    .fromPort(80)
                    .ipRanges(ipRange)
                    .build();

            IpPermission ipPerm2 = IpPermission.builder()
                    .ipProtocol("tcp")
                    .toPort(22)
                    .fromPort(22)
                    .ipRanges(ipRange)
                    .build();

            AuthorizeSecurityGroupIngressRequest authRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                    .groupName(groupName)
                    .ipPermissions(ipPerm, ipPerm2)
                    .build();
```

```
            ec2.authorizeSecurityGroupIngress(authRequest);
            System.out.println("Successfully added ingress policy to security
group " + groupName);
            return resp.groupId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void describeKeys(Ec2Client ec2) {
        try {
            DescribeKeyPairsResponse response = ec2.describeKeyPairs();
            response.keyPairs().forEach(keyPair -> System.out.printf(
                    "Found key pair with name %s " +
                            "and fingerprint %s",
                    keyPair.keyName(),
                    keyPair.keyFingerprint()));

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createKeyPair(Ec2Client ec2, String keyName, String
fileName) {
        try {
            CreateKeyPairRequest request = CreateKeyPairRequest.builder()
                    .keyName(keyName)
                    .build();

            CreateKeyPairResponse response = ec2.createKeyPair(request);
            String content = response.keyMaterial();
            BufferedWriter writer = new BufferedWriter(new FileWriter(fileName));
            writer.write(content);
            writer.close();
            System.out.println("Successfully created key pair named " + keyName);

        } catch (Ec2Exception | IOException e) {
            System.err.println(e.getMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress
  - RunInstances
  - StartInstances
  - StopInstances
  - TerminateInstances
  - UnmonitorInstances

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
import { mkdtempSync, writeFileSync, rmSync } from "fs";
import { tmpdir } from "os";
import { join } from "path";
import { get } from "http";

import {
  AllocateAddressCommand,
  AssociateAddressCommand,
  AuthorizeSecurityGroupIngressCommand,
  CreateKeyPairCommand,
  CreateSecurityGroupCommand,
  DeleteKeyPairCommand,
  DeleteSecurityGroupCommand,
  DescribeInstancesCommand,
  DescribeKeyPairsCommand,
  DescribeSecurityGroupsCommand,
  DisassociateAddressCommand,
  EC2Client,
  paginateDescribeImages,
  paginateDescribeInstanceTypes,
  ReleaseAddressCommand,
  RunInstancesCommand,
  StartInstancesCommand,
  StopInstancesCommand,
  TerminateInstancesCommand,
  waitUntilInstanceStatusOk,
  waitUntilInstanceStopped,
  waitUntilInstanceTerminated,
} from "@aws-sdk/client-ec2";
import { paginateGetParametersByPath, SSMClient } from "@aws-sdk/client-ssm";
```

```
import { wrapText } from "@aws-sdk-examples/libs/utils/util-string.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";

const ec2Client = new EC2Client();
const ssmClient = new SSMClient();

const prompter = new Prompter();
const confirmMessage = "Continue?";
const tmpDirectory = mkdtempSync(join(tmpdir(), "ec2-scenario-tmp"));

const createKeyPair = async (keyPairName) => {
  // Create a key pair in Amazon EC2.
  const { KeyMaterial, KeyPairId } = await ec2Client.send(
    // A unique name for the key pair. Up to 255 ASCII characters.
    new CreateKeyPairCommand({ KeyName: keyPairName }),
  );

  // Save the private key in a temporary location.
  writeFileSync(`${tmpDirectory}/${keyPairName}.pem`, KeyMaterial, {
    mode: 0o400,
  });

  return KeyPairId;
};

const describeKeyPair = async (keyPairName) => {
  const command = new DescribeKeyPairsCommand({
    KeyNames: [keyPairName],
  });
  const { KeyPairs } = await ec2Client.send(command);
  return KeyPairs[0];
};

const createSecurityGroup = async (securityGroupName) => {
  const command = new CreateSecurityGroupCommand({
    GroupName: securityGroupName,
    Description: "A security group for the Amazon EC2 example.",
  });
  const { GroupId } = await ec2Client.send(command);
  return GroupId;
};

const allocateIpAddress = async () => {
  const command = new AllocateAddressCommand({});
```

```
  const { PublicIp, AllocationId } = await ec2Client.send(command);
  return { PublicIp, AllocationId };
};

const getLocalIpAddress = () => {
  return new Promise((res, rej) => {
    get("http://checkip.amazonaws.com", (response) => {
      let data = "";
      response.on("data", (chunk) => (data += chunk));
      response.on("end", () => res(data.trim()));
    }).on("error", (err) => {
      rej(err);
    });
  });
};

const authorizeSecurityGroupIngress = async (securityGroupId) => {
  const ipAddress = await getLocalIpAddress();
  const command = new AuthorizeSecurityGroupIngressCommand({
    GroupId: securityGroupId,
    IpPermissions: [
      {
        IpProtocol: "tcp",
        FromPort: 22,
        ToPort: 22,
        IpRanges: [{ CidrIp: `${ipAddress}/32` }],
      },
    ],
  });

  await ec2Client.send(command);
  return ipAddress;
};

const describeSecurityGroup = async (securityGroupName) => {
  const command = new DescribeSecurityGroupsCommand({
    GroupNames: [securityGroupName],
  });
  const { SecurityGroups } = await ec2Client.send(command);

  return SecurityGroups[0];
};

const getAmznLinux2AMIs = async () => {
```

```
  const AMIs = [];
  for await (const page of paginateGetParametersByPath(
    {
      client: ssmClient,
    },
    { Path: "/aws/service/ami-amazon-linux-latest" },
  )) {
    page.Parameters.forEach((param) => {
      if (param.Name.includes("amzn2")) {
        AMIs.push(param.Value);
      }
    });
  }

  const imageDetails = [];

  for await (const page of paginateDescribeImages(
    { client: ec2Client },
    { ImageIds: AMIs },
  )) {
    imageDetails.push(...(page.Images || []));
  }

  const choices = imageDetails.map((image, index) => ({
    name: `${image.ImageId} - ${image.Description}`,
    value: index,
  }));

  /**
   * @type {number}
   */
  const selectedIndex = await prompter.select({
    message: "Select an image.",
    choices,
  });

  return imageDetails[selectedIndex];
};

/**
 * @param {import('@aws-sdk/client-ec2').Image} imageDetails
 */
const getCompatibleInstanceTypes = async (imageDetails) => {
  const paginator = paginateDescribeInstanceTypes(
```

```
    { client: ec2Client, pageSize: 25 },
    {
      Filters: [
        {
          Name: "processor-info.supported-architecture",
          Values: [imageDetails.Architecture],
        },
        { Name: "instance-type", Values: ["*.micro", "*.small"] },
      ],
    },
  );

  const instanceTypes = [];

  for await (const page of paginator) {
    if (page.InstanceTypes.length) {
      instanceTypes.push(...(page.InstanceTypes || []));
    }
  }

  const choices = instanceTypes.map((type, index) => ({
    name: `${type.InstanceType} - Memory:${type.MemoryInfo.SizeInMiB}`,
    value: index,
  }));

  /**
   * @type {number}
   */
  const selectedIndex = await prompter.select({
    message: "Select an instance type.",
    choices,
  });
  return instanceTypes[selectedIndex];
};

const runInstance = async ({
  keyPairName,
  securityGroupId,
  imageId,
  instanceType,
}) => {
  const command = new RunInstancesCommand({
    KeyName: keyPairName,
    SecurityGroupIds: [securityGroupId],
```

```
    ImageId: imageId,
    InstanceType: instanceType,
    MinCount: 1,
    MaxCount: 1,
  });

  const { Instances } = await ec2Client.send(command);
  await waitUntilInstanceStatusOk(
    { client: ec2Client },
    { InstanceIds: [Instances[0].InstanceId] },
  );
  return Instances[0].InstanceId;
};

const describeInstance = async (instanceId) => {
  const command = new DescribeInstancesCommand({
    InstanceIds: [instanceId],
  });

  const { Reservations } = await ec2Client.send(command);
  return Reservations[0].Instances[0];
};

const displaySSHConnectionInfo = ({ publicIp, keyPairName }) => {
  return `ssh -i ${tmpDirectory}/${keyPairName}.pem ec2-user@${publicIp}`;
};

const stopInstance = async (instanceId) => {
  const command = new StopInstancesCommand({ InstanceIds: [instanceId] });
  await ec2Client.send(command);
  await waitUntilInstanceStopped(
    { client: ec2Client },
    { InstanceIds: [instanceId] },
  );
};

const startInstance = async (instanceId) => {
  const startCommand = new StartInstancesCommand({ InstanceIds: [instanceId] });
  await ec2Client.send(startCommand);
  await waitUntilInstanceStatusOk(
    { client: ec2Client },
    { InstanceIds: [instanceId] },
  );
  return await describeInstance(instanceId);
```

```
};

const associateAddress = async ({ allocationId, instanceId }) => {
  const command = new AssociateAddressCommand({
    AllocationId: allocationId,
    InstanceId: instanceId,
  });

  const { AssociationId } = await ec2Client.send(command);
  return AssociationId;
};

const disassociateAddress = async (associationId) => {
  const command = new DisassociateAddressCommand({
    AssociationId: associationId,
  });
  try {
    await ec2Client.send(command);
  } catch (err) {
    console.warn(
      `Failed to disassociated address with association id: ${associationId}`,
      err,
    );
  }
};

const releaseAddress = async (allocationId) => {
  const command = new ReleaseAddressCommand({
    AllocationId: allocationId,
  });

  try {
    await ec2Client.send(command);
    console.log(`# Address with allocation ID ${allocationId} released.\n`);
  } catch (err) {
    console.log(
      `Failed to release address with allocation id: ${allocationId}.`,
      err,
    );
  }
};

const restartInstance = async (instanceId) => {
  console.log("Stopping instance.");
```

```
  await stopInstance(instanceId);
  console.log("Instance stopped.");
  console.log("Starting instance.");
  const { PublicIpAddress } = await startInstance(instanceId);
  return PublicIpAddress;
};

const terminateInstance = async (instanceId) => {
  const command = new TerminateInstancesCommand({
    InstanceIds: [instanceId],
  });

  try {
    await ec2Client.send(command);
    await waitUntilInstanceTerminated(
      { client: ec2Client },
      { InstanceIds: [instanceId] },
    );
    console.log(`# Instance with ID ${instanceId} terminated.\n`);
  } catch (err) {
    console.warn(`Failed to terminate instance ${instanceId}.`, err);
  }
};

const deleteSecurityGroup = async (securityGroupId) => {
  const command = new DeleteSecurityGroupCommand({
    GroupId: securityGroupId,
  });

  try {
    await ec2Client.send(command);
    console.log(`# Security group ${securityGroupId} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete security group ${securityGroupId}.`, err);
  }
};

const deleteKeyPair = async (keyPairName) => {
  const command = new DeleteKeyPairCommand({
    KeyName: keyPairName,
  });

  try {
    await ec2Client.send(command);
```

```
    console.log(`# Key pair ${keyPairName} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete key pair ${keyPairName}.`, err);
  }
};

const deleteTemporaryDirectory = () => {
  try {
    rmSync(tmpDirectory, { recursive: true });
    console.log(`# Temporary directory ${tmpDirectory} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete temporary directory ${tmpDirectory}.`, err);
  }
};

export const main = async () => {
  const keyPairName = "ec2-scenario-key-pair";
  const securityGroupName = "ec2-scenario-security-group";

  let securityGroupId, ipAllocationId, publicIp, instanceId, associationId;

  console.log(wrapText("Welcome to the Amazon EC2 basic usage scenario."));

  try {
    // Prerequisites
    console.log(
      "Before you launch an instance, you'll need a few things:",
      "\n - A Key Pair",
      "\n - A Security Group",
      "\n - An IP Address",
      "\n - An AMI",
      "\n - A compatible instance type",
      "\n\n I'll go ahead and take care of the first three, but I'll need your
 help for the rest.",
    );

    await prompter.confirm({ message: confirmMessage });

    await createKeyPair(keyPairName);
    securityGroupId = await createSecurityGroup(securityGroupName);
    const { PublicIp, AllocationId } = await allocateIpAddress();
    ipAllocationId = AllocationId;
    publicIp = PublicIp;
    const ipAddress = await authorizeSecurityGroupIngress(securityGroupId);
```

```
    const { KeyName } = await describeKeyPair(keyPairName);
    const { GroupName } = await describeSecurityGroup(securityGroupName);
    console.log(`# created the key pair ${KeyName}.\n`);
    console.log(
      `# created the security group ${GroupName}`,
      `and allowed SSH access from ${ipAddress} (your IP).\n`,
    );
    console.log(`# allocated ${publicIp} to be used for your EC2 instance.\n`);

    await prompter.confirm({ message: confirmMessage });

    // Creating the instance
    console.log(wrapText("Create the instance."));
    console.log(
      "You get to choose which image you want. Select an amazon-linux-2 image
from the following:",
    );
    const imageDetails = await getAmznLinux2AMIs();
    const instanceTypeDetails = await getCompatibleInstanceTypes(imageDetails);
    console.log("Creating your instance. This can take a few seconds.");
    instanceId = await runInstance({
      keyPairName,
      securityGroupId,
      imageId: imageDetails.ImageId,
      instanceType: instanceTypeDetails.InstanceType,
    });
    const instanceDetails = await describeInstance(instanceId);
    console.log(`# instance ${instanceId}.\n`);
    console.log(instanceDetails);
    console.log(
      `\nYou should now be able to SSH into your instance from another
terminal:`,
      `\n${displaySSHConnectionInfo({
        publicIp: instanceDetails.PublicIpAddress,
        keyPairName,
      })}`,
    );

    await prompter.confirm({ message: confirmMessage });

    // Understanding the IP address.
    console.log(wrapText("Understanding the IP address."));
    console.log(
```

```
      "When you stop and start an instance, the IP address will change. I'll
restart your",
      "instance for you. Notice how the IP address changes.",
    );
    const ipAddressAfterRestart = await restartInstance(instanceId);
    console.log(
      `\n Instance started. The IP address changed from
${instanceDetails.PublicIpAddress} to ${ipAddressAfterRestart}`,
      `\n${displaySSHConnectionInfo({
        publicIp: ipAddressAfterRestart,
        keyPairName,
      })}`,
    );
    await prompter.confirm({ message: confirmMessage });
    console.log(
      `If you want to the IP address to be static, you can associate an
allocated`,
      `IP address to your instance. I allocated ${publicIp} for you earlier, and
now I'll associate it to your instance.`,
    );
    associationId = await associateAddress({
      allocationId: ipAllocationId,
      instanceId,
    });
    console.log(
      "Done. Now you should be able to SSH using the new IP.\n",
      `${displaySSHConnectionInfo({ publicIp, keyPairName })}`,
    );
    await prompter.confirm({ message: confirmMessage });
    console.log(
      "I'll restart the server again so you can see the IP address remains the
same.",
    );
    const ipAddressAfterAssociated = await restartInstance(instanceId);
    console.log(
      `Done. Here's your SSH info. Notice the IP address hasn't changed.`,
      `\n${displaySSHConnectionInfo({
        publicIp: ipAddressAfterAssociated,
        keyPairName,
      })}`,
    );
    await prompter.confirm({ message: confirmMessage });
  } catch (err) {
    console.error(err);
```

```
  } finally {
    // Clean up.
    console.log(wrapText("Clean up."));
    console.log("Now I'll clean up all of the stuff I created.");
    await prompter.confirm({ message: confirmMessage });
    console.log("Cleaning up. Some of these steps can take a bit of time.");
    await disassociateAddress(associationId);
    await terminateInstance(instanceId);
    await releaseAddress(ipAllocationId);
    await deleteSecurityGroup(securityGroupId);
    deleteTemporaryDirectory();
    await deleteKeyPair(keyPairName);
    console.log(
      "Done cleaning up. Thanks for staying until the end!",
      "If you have any feedback please use the feedback button in the docs",
      "or create an issue on GitHub.",
    );
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress

- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This Kotlin example performs the following tasks:

 1. Creates an RSA key pair and saves the private key data as a .pem file.
 2. Lists key pairs.
 3. Creates a security group for the default VPC.
 4. Displays security group information.
 5. Gets a list of Amazon Linux 2 AMIs and selects one.
 6. Gets more information about the image.
 7. Gets a list of instance types that are compatible with the selected AMI’s
 architecture.
 8. Creates an instance with the key pair, security group, AMI, and an instance
 type.
 9. Displays information about the instance.
 10. Stops the instance and waits for it to stop.
 11. Starts the instance and waits for it to start.
 12. Allocates an Elastic IP address and associates it with the instance.
 13. Displays SSH connection info for the instance.
```

```
 14. Disassociates and deletes the Elastic IP address.
 15. Terminates the instance.
 16. Deletes the security group.
 17. Deletes the key pair.
 */

val DASHES = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <keyName> <fileName> <groupName> <groupDesc> <vpcId> <myIpAddress>

        Where:
            keyName - A key pair name (for example, TestKeyPair).
            fileName - A file name where the key information is written to.
            groupName - The name of the security group.
            groupDesc - The description of the security group.
            vpcId - A VPC ID. You can get this value from the AWS Management
 Console.
            myIpAddress - The IP address of your development machine.

"""

    if (args.size != 6) {
        println(usage)
        exitProcess(0)
    }

    val keyName = args[0]
    val fileName = args[1]
    val groupName = args[2]
    val groupDesc = args[3]
    val vpcId = args[4]
    val myIpAddress = args[5]
    var newInstanceId: String? = ""

    println(DASHES)
    println("Welcome to the Amazon EC2 example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create an RSA key pair and save the private key material as
 a .pem file.")
    createKeyPairSc(keyName, fileName)
```

```
    println(DASHES)

    println(DASHES)
    println("2. List key pairs.")
    describeEC2KeysSc()
    println(DASHES)

    println(DASHES)
    println("3. Create a security group.")
    val groupId = createEC2SecurityGroupSc(groupName, groupDesc, vpcId,
myIpAddress)
    println(DASHES)

    println(DASHES)
    println("4. Display security group info for the newly created security
group.")
    describeSecurityGroupsSc(groupId.toString())
    println(DASHES)

    println(DASHES)
    println("5. Get a list of Amazon Linux 2 AMIs and select one with amzn2 in
the name.")
    val instanceId = getParaValuesSc()
    if (instanceId == "") {
        println("The instance Id value isn't valid.")
        exitProcess(0)
    }
    println("The instance Id is $instanceId.")
    println(DASHES)

    println(DASHES)
    println("6. Get more information about an amzn2 image and return the AMI
value.")
    val amiValue = instanceId?.let { describeImageSc(it) }
    if (instanceId == "") {
        println("The instance Id value is invalid.")
        exitProcess(0)
    }
    println("The AMI value is $amiValue.")
    println(DASHES)

    println(DASHES)
    println("7. Get a list of instance types.")
    val instanceType = getInstanceTypesSc()
```

```
    println(DASHES)

    println(DASHES)
    println("8. Create an instance.")
    if (amiValue != null) {
        newInstanceId = runInstanceSc(instanceType, keyName, groupName, amiValue)
        println("The instance Id is $newInstanceId")
    }
    println(DASHES)

    println(DASHES)
    println("9. Display information about the running instance. ")
    var ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("10.  Stop the instance.")
    if (newInstanceId != null) {
        stopInstanceSc(newInstanceId)
    }
    println(DASHES)

    println(DASHES)
    println("11.  Start the instance.")
    if (newInstanceId != null) {
        startInstanceSc(newInstanceId)
    }
    ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("12. Allocate an Elastic IP address and associate it with the
 instance.")
    val allocationId = allocateAddressSc()
    println("The allocation Id value is $allocationId")
    val associationId = associateAddressSc(newInstanceId, allocationId)
    println("The associate Id value is $associationId")
    println(DASHES)

    println(DASHES)
```

```
    println("13. Describe the instance again.")
    ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("14. Disassociate and release the Elastic IP address.")
    disassociateAddressSc(associationId)
    releaseEC2AddressSc(allocationId)
    println(DASHES)

    println(DASHES)
    println("15. Terminate the instance and use a waiter.")
    if (newInstanceId != null) {
        terminateEC2Sc(newInstanceId)
    }
    println(DASHES)

    println(DASHES)
    println("16. Delete the security group.")
    if (groupId != null) {
        deleteEC2SecGroupSc(groupId)
    }
    println(DASHES)

    println(DASHES)
    println("17. Delete the key pair.")
    deleteKeysSc(keyName)
    println(DASHES)

    println(DASHES)
    println("You successfully completed the Amazon EC2 scenario.")
    println(DASHES)
}

suspend fun deleteKeysSc(keyPair: String) {
    val request = DeleteKeyPairRequest {
        keyName = keyPair
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteKeyPair(request)
        println("Successfully deleted key pair named $keyPair")
    }
```

```
}

suspend fun deleteEC2SecGroupSc(groupIdVal: String) {
    val request = DeleteSecurityGroupRequest {
        groupId = groupIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteSecurityGroup(request)
        println("Successfully deleted security group with Id $groupIdVal")
    }
}

suspend fun terminateEC2Sc(instanceIdVal: String) {
    val ti = TerminateInstancesRequest {
        instanceIds = listOf(instanceIdVal)
    }
    println("Wait for the instance to terminate. This will take a few minutes.")
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.terminateInstances(ti)
        ec2.waitUntilInstanceTerminated { // suspend call
            instanceIds = listOf(instanceIdVal)
        }
        println("$instanceIdVal is terminated!")
    }
}

suspend fun releaseEC2AddressSc(allocId: String?) {
    val request = ReleaseAddressRequest {
        allocationId = allocId
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.releaseAddress(request)
        println("Successfully released Elastic IP address $allocId")
    }
}

suspend fun disassociateAddressSc(associationIdVal: String?) {
    val addressRequest = DisassociateAddressRequest {
        associationId = associationIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.disassociateAddress(addressRequest)
        println("You successfully disassociated the address!")
```

```
    }
}

suspend fun associateAddressSc(instanceIdVal: String?, allocationIdVal: String?):
 String? {
    val associateRequest = AssociateAddressRequest {
        instanceId = instanceIdVal
        allocationId = allocationIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val associateResponse = ec2.associateAddress(associateRequest)
        return associateResponse.associationId
    }
}

suspend fun allocateAddressSc(): String? {
    val allocateRequest = AllocateAddressRequest {
        domain = DomainType.Vpc
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val allocateResponse = ec2.allocateAddress(allocateRequest)
        return allocateResponse.allocationId
    }
}

suspend fun startInstanceSc(instanceId: String) {
    val request = StartInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.startInstances(request)
        println("Waiting until instance $instanceId starts. This will take a few
 minutes.")
        ec2.waitUntilInstanceRunning { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully started instance $instanceId")
    }
}

suspend fun stopInstanceSc(instanceId: String) {
    val request = StopInstancesRequest {
```

```
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.stopInstances(request)
        println("Waiting until instance $instanceId stops. This will take a few
 minutes.")
        ec2.waitUntilInstanceStopped { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully stopped instance $instanceId")
    }
}

suspend fun describeEC2InstancesSc(newInstanceId: String?): String {
    var pubAddress = ""
    var isRunning = false
    val request = DescribeInstancesRequest {
        instanceIds = listOf(newInstanceId.toString())
    }

    while (!isRunning) {
        Ec2Client { region = "us-west-2" }.use { ec2 ->
            val response = ec2.describeInstances(request)
            val state =
 response.reservations?.get(0)?.instances?.get(0)?.state?.name?. value
            if (state != null) {
                if (state.compareTo("running") == 0) {
                    println("Image id is
 ${response.reservations!!.get(0).instances?.get(0)?.imageId}")
                    println("Instance type is
 ${response.reservations!!.get(0).instances?.get(0)?.instanceType}")
                    println("Instance state is
 ${response.reservations!!.get(0).instances?.get(0)?.state}")
                    pubAddress =
 response.reservations!!.get(0).instances?.get(0)?.publicIpAddress.toString()
                    println("Instance address is $pubAddress")
                    isRunning = true
                }
            }
        }
    }
    return pubAddress
}
```

```
suspend fun runInstanceSc(instanceTypeVal: String, keyNameVal: String,
 groupNameVal: String, amiIdVal: String): String {
    val runRequest = RunInstancesRequest {
        instanceType = InstanceType.fromValue(instanceTypeVal)
        keyName = keyNameVal
        securityGroups = listOf(groupNameVal)
        maxCount = 1
        minCount = 1
        imageId = amiIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.runInstances(runRequest)
        val instanceId = response.instances?.get(0)?.instanceId
        println("Successfully started EC2 Instance $instanceId based on AMI
 $amiIdVal")
        return instanceId.toString()
    }
}

// Get a list of instance types.
suspend fun getInstanceTypesSc(): String {
    var instanceType = ""
    val filterObs = ArrayList<Filter>()
    val filter = Filter {
        name = "processor-info.supported-architecture"
        values = listOf("arm64")
    }

    filterObs.add(filter)
    val typesRequest = DescribeInstanceTypesRequest {
        filters = filterObs
        maxResults = 10
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstanceTypes(typesRequest)
        response.instanceTypes?.forEach { type ->
            println("The memory information of this type is
 ${type.memoryInfo?.sizeInMib}")
            println("Maximum number of network cards is
 ${type.networkInfo?.maximumNetworkCards}")
            instanceType = type.instanceType.toString()
        }
```

```
        return instanceType
    }
}

// Display the Description field that corresponds to the instance Id value.
suspend fun describeImageSc(instanceId: String): String? {
    val imagesRequest = DescribeImagesRequest {
        imageIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeImages(imagesRequest)
        println("The description of the first image is
 ${response.images?.get(0)?.description}")
        println("The name of the first image is
 ${response.images?.get(0)?.name}")

        // Return the image Id value.
        return response.images?.get(0)?.imageId
    }
}

// Get the Id value of an instance with amzn2 in the name.
suspend fun getParaValuesSc(): String? {
    val parameterRequest = GetParametersByPathRequest {
        path = "/aws/service/ami-amazon-linux-latest"
    }

    SsmClient { region = "us-west-2" }.use { ssmClient ->
        val response = ssmClient.getParametersByPath(parameterRequest)
        response.parameters?.forEach { para ->
            println("The name of the para is: ${para.name}")
            println("The type of the para is: ${para.type}")
            println("")
            if (para.name?.let { filterName(it) } == true) {
                return para.value
            }
        }
    }
    return ""
}

fun filterName(name: String): Boolean {
    val parts = name.split("/").toTypedArray()
```

```
    val myValue = parts[4]
    return myValue.contains("amzn2")
}

suspend fun describeSecurityGroupsSc(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeSecurityGroups(request)
        for (group in response.securityGroups!!) {
            println("Found Security Group with id " + group.groupId.toString() +
 " and group VPC " + group.vpcId)
        }
    }
}

suspend fun createEC2SecurityGroupSc(groupNameVal: String?, groupDescVal:
 String?, vpcIdVal: String?, myIpAddress: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "$myIpAddress/0"
        }

        val ipPerm = IpPermission {
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
```

```
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
        }
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group
 $groupNameVal")
        return resp.groupId
    }
}

suspend fun describeEC2KeysSc() {
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeKeyPairs(DescribeKeyPairsRequest {})
        response.keyPairs?.forEach { keyPair ->
            println("Found key pair with name ${keyPair.keyName} and fingerprint
 ${ keyPair.keyFingerprint}")
        }
    }
}

suspend fun createKeyPairSc(keyNameVal: String, fileNameVal: String) {
    val request = CreateKeyPairRequest {
        keyName = keyNameVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.createKeyPair(request)
        val content = response.keyMaterial
        if (content != null) {
            File(fileNameVal).writeText(content)
        }
        println("Successfully created key pair named $keyNameVal")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AllocateAddress

- AssociateAddress
- AuthorizeSecurityGroupIngress
- CreateKeyPair
- CreateSecurityGroup
- DeleteKeyPair
- DeleteSecurityGroup
- DescribeImages
- DescribeInstanceTypes
- DescribeInstances
- DescribeKeyPairs
- DescribeSecurityGroups
- DisassociateAddress
- ReleaseAddress
- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class Ec2InstanceScenario:
    """Runs an interactive scenario that shows how to get started using EC2
 instances."""
```

```
    def __init__(self, inst_wrapper, key_wrapper, sg_wrapper, eip_wrapper,
ssm_client):
        """
        :param inst_wrapper: An object that wraps instance actions.
        :param key_wrapper: An object that wraps key pair actions.
        :param sg_wrapper: An object that wraps security group actions.
        :param eip_wrapper: An object that wraps Elastic IP actions.
        :param ssm_client: A Boto3 AWS Systems Manager client.
        """
        self.inst_wrapper = inst_wrapper
        self.key_wrapper = key_wrapper
        self.sg_wrapper = sg_wrapper
        self.eip_wrapper = eip_wrapper
        self.ssm_client = ssm_client

    @demo_func
    def create_and_list_key_pairs(self):
        """
        1. Creates an RSA key pair and saves its private key data as a .pem file
in secure
           temporary storage. The private key data is deleted after the example
completes.
        2. Lists the first five key pairs for the current account.
        """
        print(
            "Let's create an RSA key pair that you can be use to securely connect
to "
            "your EC2 instance."
        )
        key_name = q.ask("Enter a unique name for your key: ", q.non_empty)
        self.key_wrapper.create(key_name)
        print(
            f"Created a key pair {self.key_wrapper.key_pair.key_name} and saved
the "
            f"private key to {self.key_wrapper.key_file_path}.\n"
        )
        if q.ask("Do you want to list some of your key pairs? (y/n) ",
q.is_yesno):
            self.key_wrapper.list(5)

    @demo_func
    def create_security_group(self):
        """
```

```
        1. Creates a security group for the default VPC.
        2. Adds an inbound rule to allow SSH. The SSH rule allows only
           inbound traffic from the current computer’s public IPv4 address.
        3. Displays information about the security group.

        This function uses 'http://checkip.amazonaws.com' to get the current
public IP
        address of the computer that is running the example. This method works in
most
        cases. However, depending on how your computer connects to the internet,
you
        might have to manually add your public IP address to the security group
by using
        the AWS Management Console.
        """
        print("Let's create a security group to manage access to your instance.")
        sg_name = q.ask("Enter a unique name for your security group: ",
q.non_empty)
        security_group = self.sg_wrapper.create(
            sg_name, "Security group for example: get started with instances."
        )
        print(
            f"Created security group {security_group.group_name} in your default
"
            f"VPC {security_group.vpc_id}.\n"
        )

        ip_response = urllib.request.urlopen("http://checkip.amazonaws.com")
        current_ip_address = ip_response.read().decode("utf-8").strip()
        print("Let's add a rule to allow SSH only from your current IP address.")
        print(f"Your public IP address is {current_ip_address}.")
        q.ask("Press Enter to add this rule to your security group.")
        response = self.sg_wrapper.authorize_ingress(current_ip_address)
        if response["Return"]:
            print("Security group rules updated.")
        else:
            print("Couldn't update security group rules.")
        self.sg_wrapper.describe()

    @demo_func
    def create_instance(self):
        """
        1. Gets a list of Amazon Linux 2 AMIs from AWS Systems Manager.
Specifying the
```

```
            '/aws/service/ami-amazon-linux-latest' path returns only the latest
 AMIs.
        2. Gets and displays information about the available AMIs and lets you
 select one.
        3. Gets a list of instance types that are compatible with the selected
 AMI and
            lets you select one.
        4. Creates an instance with the previously created key pair and security
 group,
            and the selected AMI and instance type.
        5. Waits for the instance to be running and then displays its
 information.
        """
        ami_paginator = self.ssm_client.get_paginator("get_parameters_by_path")
        ami_options = []
        for page in ami_paginator.paginate(Path="/aws/service/ami-amazon-linux-
latest"):
            ami_options += page["Parameters"]
        amzn2_images = self.inst_wrapper.get_images(
            [opt["Value"] for opt in ami_options if "amzn2" in opt["Name"]]
        )
        print(
            "Let's create an instance from an Amazon Linux 2 AMI. Here are some
 options:"
        )
        image_choice = q.choose(
            "Which one do you want to use? ", [opt.description for opt in
 amzn2_images]
        )
        print("Great choice!\n")

        print(
            f"Here are some instance types that support the "
            f"{amzn2_images[image_choice].architecture} architecture of the
 image:"
        )
        inst_types = self.inst_wrapper.get_instance_types(
            amzn2_images[image_choice].architecture
        )
        inst_type_choice = q.choose(
            "Which one do you want to use? ", [it["InstanceType"] for it in
 inst_types]
        )
        print("Another great choice.\n")
```

```
        print("Creating your instance and waiting for it to start...")
        self.inst_wrapper.create(
            amzn2_images[image_choice],
            inst_types[inst_type_choice]["InstanceType"],
            self.key_wrapper.key_pair,
            [self.sg_wrapper.security_group],
        )
        print(f"Your instance is ready:\n")
        self.inst_wrapper.display()

        print("You can use SSH to connect to your instance.")
        print(
            "If the connection attempt times out, you might have to manually
update "
            "the SSH ingress rule for your IP address in the AWS Management
Console."
        )
        self._display_ssh_info()

    def _display_ssh_info(self):
        """
        Displays an SSH connection string that can be used to connect to a
running
        instance.
        """
        print("To connect, open another command prompt and run the following
command:")
        if self.eip_wrapper.elastic_ip is None:
            print(
                f"\tssh -i {self.key_wrapper.key_file_path} "
                f"ec2-user@{self.inst_wrapper.instance.public_ip_address}"
            )
        else:
            print(
                f"\tssh -i {self.key_wrapper.key_file_path} "
                f"ec2-user@{self.eip_wrapper.elastic_ip.public_ip}"
            )
        q.ask("Press Enter when you're ready to continue the demo.")

    @demo_func
    def associate_elastic_ip(self):
        """
        1. Allocates an Elastic IP address and associates it with the instance.
```

```
        2. Displays an SSH connection string that uses the Elastic IP address.
        """
        print(
            "You can allocate an Elastic IP address and associate it with your
instance\n"
            "to keep a consistent IP address even when your instance restarts."
        )
        elastic_ip = self.eip_wrapper.allocate()
        print(f"Allocated static Elastic IP address: {elastic_ip.public_ip}.")
        self.eip_wrapper.associate(self.inst_wrapper.instance)
        print(f"Associated your Elastic IP with your instance.")
        print(
            "You can now use SSH to connect to your instance by using the Elastic
IP."
        )
        self._display_ssh_info()

    @demo_func
    def stop_and_start_instance(self):
        """
        1. Stops the instance and waits for it to stop.
        2. Starts the instance and waits for it to start.
        3. Displays information about the instance.
        4. Displays an SSH connection string. When an Elastic IP address is
associated
           with the instance, the IP address stays consistent when the instance
stops
           and starts.
        """
        print("Let's stop and start your instance to see what changes.")
        print("Stopping your instance and waiting until it's stopped...")
        self.inst_wrapper.stop()
        print("Your instance is stopped. Restarting...")
        self.inst_wrapper.start()
        print("Your instance is running.")
        self.inst_wrapper.display()
        if self.eip_wrapper.elastic_ip is None:
            print(
                "Every time your instance is restarted, its public IP address
changes."
            )
        else:
            print(
```

```
                "Because you have associated an Elastic IP with your instance,
you can \n"
                "connect by using a consistent IP address after the instance
restarts."
            )
        self._display_ssh_info()

    @demo_func
    def cleanup(self):
        """
        1. Disassociate and delete the previously created Elastic IP.
        2. Terminate the previously created instance.
        3. Delete the previously created security group.
        4. Delete the previously created key pair.
        """
        print("Let's clean everything up. This example created these resources:")
        print(f"\tElastic IP: {self.eip_wrapper.elastic_ip.allocation_id}")
        print(f"\tInstance: {self.inst_wrapper.instance.id}")
        print(f"\tSecurity group: {self.sg_wrapper.security_group.id}")
        print(f"\tKey pair: {self.key_wrapper.key_pair.name}")
        if q.ask("Ready to delete these resources? (y/n) ", q.is_yesno):
            self.eip_wrapper.disassociate()
            print("Disassociated the Elastic IP from the instance.")
            self.eip_wrapper.release()
            print("Released the Elastic IP.")
            print("Terminating the instance and waiting for it to terminate...")
            self.inst_wrapper.terminate()
            print("Instance terminated.")
            self.sg_wrapper.delete()
            print("Deleted security group.")
            self.key_wrapper.delete()
            print("Deleted key pair.")

    def run_scenario(self):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s:
%(message)s")

        print("-" * 88)
        print(
            "Welcome to the Amazon Elastic Compute Cloud (Amazon EC2) get started
with instances demo."
        )
        print("-" * 88)
```

```
        self.create_and_list_key_pairs()
        self.create_security_group()
        self.create_instance()
        self.stop_and_start_instance()
        self.associate_elastic_ip()
        self.stop_and_start_instance()
        self.cleanup()

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = Ec2InstanceScenario(
            InstanceWrapper.from_resource(),
            KeyPairWrapper.from_resource(),
            SecurityGroupWrapper.from_resource(),
            ElasticIpWrapper.from_resource(),
            boto3.client("ssm"),
        )
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina uma classe que envolva as ações de pares de chaves.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair
 actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is
 stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
```

```
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def create(self, key_name):
        """
        Creates a key pair that can be used to securely connect to an EC2
instance.
        The returned key pair contains private key information that cannot be
retrieved
        again. The private key data is stored as a .pem file.

        :param key_name: The name of the key pair to create.
        :return: A Boto3 KeyPair object that represents the newly created key
pair.
        """
        try:
            self.key_pair = self.ec2_resource.create_key_pair(KeyName=key_name)
            self.key_file_path = os.path.join(
                self.key_file_dir.name, f"{self.key_pair.name}.pem"
            )
            with open(self.key_file_path, "w") as key_file:
                key_file.write(self.key_pair.key_material)
        except ClientError as err:
            logger.error(
                "Couldn't create key %s. Here's why: %s: %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.key_pair


    def list(self, limit):
```

```
        """
        Displays a list of key pairs for the current account.

        :param limit: The maximum number of key pairs to list.
        """
        try:
            for kp in self.ec2_resource.key_pairs.limit(limit):
                print(f"Found {kp.key_type} key {kp.name} with fingerprint:")
                print(f"\t{kp.key_fingerprint}")
        except ClientError as err:
            logger.error(
                "Couldn't list key pairs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self):
        """
        Deletes a key pair.
        """
        if self.key_pair is None:
            logger.info("No key pair to delete.")
            return

        key_name = self.key_pair.name
        try:
            self.key_pair.delete()
            self.key_pair = None
        except ClientError as err:
            logger.error(
                "Couldn't delete key %s. Here's why: %s : %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que envolva as ações de grupos de segurança.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, group_name, group_description):
        """
        Creates a security group in the default virtual private cloud (VPC) of
 the
        current account.

        :param group_name: The name of the security group to create.
        :param group_description: The description of the security group to
 create.
        :return: A Boto3 SecurityGroup object that represents the newly created
 security group.
        """
        try:
            self.security_group = self.ec2_resource.create_security_group(
                GroupName=group_name, Description=group_description
            )
        except ClientError as err:
            logger.error(
                "Couldn't create security group %s. Here's why: %s: %s",
```

```
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.security_group


    def authorize_ingress(self, ssh_ingress_ip):
        """
        Adds a rule to the security group to allow access to SSH.

        :param ssh_ingress_ip: The IP address that is granted inbound access to
connect
                               to port 22 over TCP, used for SSH.
        :return: The response to the authorization request. The 'Return' field of
the
                 response indicates whether the request succeeded or failed.
        """
        if self.security_group is None:
            logger.info("No security group to update.")
            return

        try:
            ip_permissions = [
                {
                    # SSH ingress open to only the specified IP address.
                    "IpProtocol": "tcp",
                    "FromPort": 22,
                    "ToPort": 22,
                    "IpRanges": [{"CidrIp": f"{ssh_ingress_ip}/32"}],
                }
            ]
            response = self.security_group.authorize_ingress(
                IpPermissions=ip_permissions
            )
        except ClientError as err:
            logger.error(
                "Couldn't authorize inbound rules for %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
        else:
            return response


    def describe(self):
        """
        Displays information about the security group.
        """
        if self.security_group is None:
            logger.info("No security group to describe.")
            return

        try:
            print(f"Security group: {self.security_group.group_name}")
            print(f"\tID: {self.security_group.id}")
            print(f"\tVPC: {self.security_group.vpc_id}")
            if self.security_group.ip_permissions:
                print(f"Inbound permissions:")
                pp(self.security_group.ip_permissions)
        except ClientError as err:
            logger.error(
                "Couldn't get data for security group %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self):
        """
        Deletes the security group.
        """
        if self.security_group is None:
            logger.info("No security group to delete.")
            return

        group_id = self.security_group.id
        try:
            self.security_group.delete()
        except ClientError as err:
            logger.error(
                "Couldn't delete security group %s. Here's why: %s: %s",
```

```
                group_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que envolva as ações de instâncias.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance
 actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object
 that
                            wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, image, instance_type, key_pair, security_groups=None):
        """
        Creates a new EC2 instance. The instance starts immediately after
        it is created.

        The instance is created in the default VPC of the current account.
```

```
        :param image: A Boto3 Image object that represents an Amazon Machine
Image (AMI)
                      that defines attributes of the instance that is created.
The AMI
                      defines things like the kind of operating system and the
type of
                      storage used by the instance.
        :param instance_type: The type of instance to create, such as 't2.micro'.
                              The instance type defines things like the number of
CPUs and
                              the amount of memory.
        :param key_pair: A Boto3 KeyPair or KeyPairInfo object that represents
the key
                         pair that is used to secure connections to the instance.
        :param security_groups: A list of Boto3 SecurityGroup objects that
represents the
                                security groups that are used to grant access to
the
                                instance. When no security groups are specified,
the
                                default security group of the VPC is used.
        :return: A Boto3 Instance object that represents the newly created
instance.
        """
        try:
            instance_params = {
                "ImageId": image.id,
                "InstanceType": instance_type,
                "KeyName": key_pair.name,
            }
            if security_groups is not None:
                instance_params["SecurityGroupIds"] = [sg.id for sg in
security_groups]
            self.instance = self.ec2_resource.create_instances(
                **instance_params, MinCount=1, MaxCount=1
            )[0]
            self.instance.wait_until_running()
        except ClientError as err:
            logging.error(
                "Couldn't create instance with image %s, instance type %s, and
key %s. "
                "Here's why: %s: %s",
                image.id,
                instance_type,
```

```
                key_pair.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.instance


    def display(self, indent=1):
        """
        Displays information about an instance.

        :param indent: The visual indent to apply to the output.
        """
        if self.instance is None:
            logger.info("No instance to display.")
            return

        try:
            self.instance.load()
            ind = "\t" * indent
            print(f"{ind}ID: {self.instance.id}")
            print(f"{ind}Image ID: {self.instance.image_id}")
            print(f"{ind}Instance type: {self.instance.instance_type}")
            print(f"{ind}Key name: {self.instance.key_name}")
            print(f"{ind}VPC ID: {self.instance.vpc_id}")
            print(f"{ind}Public IP: {self.instance.public_ip_address}")
            print(f"{ind}State: {self.instance.state['Name']}")
        except ClientError as err:
            logger.error(
                "Couldn't display your instance. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def terminate(self):
        """
        Terminates an instance and waits for it to be in a terminated state.
        """
        if self.instance is None:
            logger.info("No instance to terminate.")
```

```
            return

        instance_id = self.instance.id
        try:
            self.instance.terminate()
            self.instance.wait_until_terminated()
            self.instance = None
        except ClientError as err:
            logging.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def start(self):
        """
        Starts an instance and waits for it to be in a running state.

        :return: The response to the start request.
        """
        if self.instance is None:
            logger.info("No instance to start.")
            return

        try:
            response = self.instance.start()
            self.instance.wait_until_running()
        except ClientError as err:
            logger.error(
                "Couldn't start instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def stop(self):
        """
```

```
        Stops an instance and waits for it to be in a stopped state.

        :return: The response to the stop request.
        """
        if self.instance is None:
            logger.info("No instance to stop.")
            return

        try:
            response = self.instance.stop()
            self.instance.wait_until_stopped()
        except ClientError as err:
            logger.error(
                "Couldn't stop instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def get_images(self, image_ids):
        """
        Gets information about Amazon Machine Images (AMIs) from a list of AMI
IDs.

        :param image_ids: The list of AMIs to look up.
        :return: A list of Boto3 Image objects that represent the requested AMIs.
        """
        try:
            images = list(self.ec2_resource.images.filter(ImageIds=image_ids))
        except ClientError as err:
            logger.error(
                "Couldn't get images. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return images
```

```
    def get_instance_types(self, architecture):
        """
        Gets instance types that support the specified architecture and are
designated
        as either 'micro' or 'small'. When an instance is created, the instance
type
        you specify must support the architecture of the AMI you use.

        :param architecture: The kind of architecture the instance types must
support,
                             such as 'x86_64'.
        :return: A list of instance types that support the specified architecture
                 and are either 'micro' or 'small'.
        """
        try:
            inst_types = []
            it_paginator = self.ec2_resource.meta.client.get_paginator(
                "describe_instance_types"
            )
            for page in it_paginator.paginate(
                Filters=[
                    {
                        "Name": "processor-info.supported-architecture",
                        "Values": [architecture],
                    },
                    {"Name": "instance-type", "Values": ["*.micro", "*.small"]},
                ]
            ):
                inst_types += page["InstanceTypes"]
        except ClientError as err:
            logger.error(
                "Couldn't get instance types. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_types
```

Defina uma classe que envolva as ações de IP elástico.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level
 resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def allocate(self):
        """
        Allocates an Elastic IP address that can be associated with an Amazon EC2
        instance. By using an Elastic IP address, you can keep the public IP
 address
        constant even when you restart the associated instance.

        :return: The newly created Elastic IP object. By default, the address is
 not
                 associated with any instance.
        """
        try:
            response =
 self.ec2_resource.meta.client.allocate_address(Domain="vpc")
            self.elastic_ip =
 self.ec2_resource.VpcAddress(response["AllocationId"])
        except ClientError as err:
            logger.error(
                "Couldn't allocate Elastic IP. Here's why: %s: %s",
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.elastic_ip


    def associate(self, instance):
        """
        Associates an Elastic IP address with an instance. When this association
is
        created, the Elastic IP's public IP address is immediately used as the
public
        IP address of the associated instance.

        :param instance: A Boto3 Instance object. This is a high-level object
that wraps
                         Amazon EC2 instance actions.
        :return: A response that contains the ID of the association.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to associate.")
            return

        try:
            response = self.elastic_ip.associate(InstanceId=instance.id)
        except ClientError as err:
            logger.error(
                "Couldn't associate Elastic IP %s with instance %s. Here's why:
%s: %s",
                self.elastic_ip.allocation_id,
                instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        return response


    def disassociate(self):
        """
        Removes an association between an Elastic IP address and an instance.
When the
```

```
        association is removed, the instance is assigned a new public IP address.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to disassociate.")
            return

        try:
            self.elastic_ip.association.delete()
        except ClientError as err:
            logger.error(
                "Couldn't disassociate Elastic IP %s from its instance. Here's
why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def release(self):
        """
        Releases an Elastic IP address. After the Elastic IP address is released,
        it can no longer be used.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to release.")
            return

        try:
            self.elastic_ip.release()
        except ClientError as err:
            logger.error(
                "Couldn't release Elastic IP address %s. Here's why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress
  - RunInstances
  - StartInstances
  - StopInstances
  - TerminateInstances
  - UnmonitorInstances

Exemplos de código para o Amazon ECR usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Container Registry (Amazon ECR) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Amazon ECR – Mais informações sobre o Amazon ECR.

- Referência da API do Amazon ECR – Detalhes sobre todas as ações disponíveis do Amazon ECR.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon ECR usando SDKs da AWS
  - Liste os IDs de imagem para um repositório Amazon ECR usando um SDK da AWS
  - Liste seus repositórios do Amazon ECR usando um SDK da AWS

Ações para o Amazon ECR usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Container Registry (Amazon ECR) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Liste os IDs de imagem para um repositório Amazon ECR usando um SDK da AWS
- Liste seus repositórios do Amazon ECR usando um SDK da AWS

Liste os IDs de imagem para um repositório Amazon ECR usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os IDs de imagem de um repositório.

CLI

AWS CLI

Como listar as imagens em um repositório

O exemplo de `list-images` a seguir exibe uma lista das imagens presentes no repositório `cluster-autoscaler`.

```
aws ecr list-images \
    --repository-name cluster-autoscaler
```

Saída:

```
{
    "imageIds": [
        {
            "imageDigest":
 "sha256:99c6fb4377e9a420a1eb3b410a951c9f464eff3b7dbc76c65e434e39b94b6570",
            "imageTag": "v1.13.8"
        },
        {
            "imageDigest":
 "sha256:99c6fb4377e9a420a1eb3b410a951c9f464eff3b7dbc76c65e434e39b94b6570",
            "imageTag": "v1.13.7"
        },
        {
            "imageDigest":
 "sha256:4a1c6567c38904384ebc64e35b7eeddd8451110c299e3368d2210066487d97e5",
            "imageTag": "v1.13.6"
        }
    ]
}
```

- Para obter detalhes da API, consulte ListImagesem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_images(
    client: &aws_sdk_ecr::Client,
    repository: &str,
) -> Result<(), aws_sdk_ecr::Error> {
    let rsp = client
        .list_images()
        .repository_name(repository)
        .send()
        .await?;
```

```
    let images = rsp.image_ids();

    println!("found {} images", images.len());

    for image in images {
        println!(
            "image: {}:{}",
            image.image_tag().unwrap(),
            image.image_digest().unwrap()
        );
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListImagesreferência da API AWS SDK for Rust.

Liste seus repositórios do Amazon ECR usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os repositórios.

CLI

AWS CLI

Como descrever os repositórios em um registro

Este exemplo descreve os repositórios no registro padrão de uma conta.

Comando:

```
aws ecr describe-repositories
```

Saída:

```
{
    "repositories": [
        {
            "registryId": "012345678910",
```

```
            "repositoryName": "ubuntu",
            "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/
ubuntu"
        },
        {
            "registryId": "012345678910",
            "repositoryName": "test",
            "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/test"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeRepositoriesem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_repos(client: &aws_sdk_ecr::Client) -> Result<(),
 aws_sdk_ecr::Error> {
    let rsp = client.describe_repositories().send().await?;

    let repos = rsp.repositories();

    println!("Found {} repositories:", repos.len());

    for repo in repos {
        println!("  ARN:  {}", repo.repository_arn().unwrap());
        println!("  Name: {}", repo.repository_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeRepositoriesreferência da API AWS SDK for Rust.

Exemplos de código para o Amazon ECS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Container Service (Amazon ECS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Amazon ECS – Mais informações sobre o Amazon ECS.
- Referência da API do Amazon ECS – Detalhes sobre todas as ações disponíveis do Amazon ECS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Amazon ECS

O exemplo de código a seguir mostra como começar a usar o Amazon ECS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.ECS;
using Amazon.ECS.Model;
using Microsoft.Extensions.Hosting;

namespace ECSActions;

public class HelloECS
{
    static async System.Threading.Tasks.Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon ECS domain registration service.
        // Use your AWS profile name, or leave it blank to use the default
 profile.
        using var host = Host.CreateDefaultBuilder(args).Build();

        // Now the client is available for injection.
        var amazonECSClient = new AmazonECSClient();

        // You can use await and any of the async methods to get a response.
        var response = await amazonECSClient.ListClustersAsync(new
 ListClustersRequest { });

        Console.WriteLine($"Hello Amazon ECS! Following are some cluster ARNS
 available in the your aws account");
        Console.WriteLine();
        foreach (var arn in response.ClusterArns.Take(5))
        {
            Console.WriteLine($"\tARN: {arn}");
            Console.WriteLine($"Cluster Name: {arn.Split("/").Last()}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for .NET da API.

Exemplos de código

- Ações para o Amazon ECS usando SDKs da AWS
  - Crie um cluster do Amazon ECS usando um SDK da AWS

- Crie um serviço do Amazon ECS usando um SDK da AWS
- Exclua um cluster do Amazon ECS usando um SDK da AWS
- Exclua um serviço do Amazon ECS usando um SDK da AWS
- Descreva seus clusters do Amazon ECS usando um SDK da AWS
- Descreva suas tarefas do Amazon ECS usando um SDK da AWS
- Liste seus clusters do Amazon ECS usando um SDK da AWS
- Liste seus serviços do Amazon ECS em um cluster usando um SDK da AWS
- Liste suas tarefas do Amazon ECS em um cluster usando um SDK da AWS
- Atualize um serviço do Amazon ECS usando um SDK da AWS
- Cenários para o Amazon ECS usando SDKs da AWS
  - Obtenha informações de ARN para clusters, serviços e tarefas do Amazon ECS usando um SDK da AWS

Ações para o Amazon ECS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Container Service (Amazon ECS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon ECS usando SDKs da AWS.

Exemplos

- Crie um cluster do Amazon ECS usando um SDK da AWS
- Crie um serviço do Amazon ECS usando um SDK da AWS
- Exclua um cluster do Amazon ECS usando um SDK da AWS
- Exclua um serviço do Amazon ECS usando um SDK da AWS
- Descreva seus clusters do Amazon ECS usando um SDK da AWS
- Descreva suas tarefas do Amazon ECS usando um SDK da AWS
- Liste seus clusters do Amazon ECS usando um SDK da AWS
- Liste seus serviços do Amazon ECS em um cluster usando um SDK da AWS
- Liste suas tarefas do Amazon ECS em um cluster usando um SDK da AWS
- Atualize um serviço do Amazon ECS usando um SDK da AWS

Crie um cluster do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um cluster do Amazon ECS.

CLI

AWS CLI

Exemplo 1: como criar um cluster

O exemplo de `create-cluster` a seguir cria um cluster.

```
aws ecs create-cluster \
    --cluster-name MyCluster
```

Saída:

```
{
    "cluster": {
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "clusterName": "MyCluster",
        "status": "ACTIVE",
        "registeredContainerInstancesCount": 0,
        "pendingTasksCount": 0,
        "runningTasksCount": 0,
        "activeServicesCount": 0,
        "statistics": [],
        "tags": []
    }
}
```

Para obter mais informações, consulte Creating a Cluster no Guia do desenvolvedor do Amazon ECS.

Exemplo 2: como criar um cluster usando provedores de capacidade

O exemplo de `create-cluster` a seguir cria um cluster e associa dois provedores de capacidade existentes a ele. O comando `create-capacity-provider` é usado para criar um provedor de capacidade. Embora recomendado, não é necessário especificar uma estratégia de provedor de capacidade. Neste exemplo, criamos um cluster chamado `MyCluster` e associamos os provedores de capacidade `MyCapacityProvider1` e

`MyCapacityProvider2` a ele. Uma estratégia de provedor de capacidade padrão é especificada e distribui a tarefa igualmente em ambos os provedores de capacidade.

aws ecs create-cluster --cluster-name MyCluster --capacity-providers MyCapacityProvider 1 2 -- CapacityProvider= 1, peso=1 CapacityProvider= 2, peso=1 MyCapacityProvider default-capacity-provider-strategy MyCapacityProvider MyCapacityProvider

Saída:

```
{
    "cluster": {
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "clusterName": "MyCluster",
        "status": "PROVISIONING",
        "registeredContainerInstancesCount": 0,
        "pendingTasksCount": 0,
        "runningTasksCount": 0,
        "activeServicesCount": 0,
        "statistics": [],
        "settings": [
            {
                "name": "containerInsights",
                "value": "enabled"
            }
        ],
        "capacityProviders": [
            "MyCapacityProvider1",
            "MyCapacityProvider2"
        ],
        "defaultCapacityProviderStrategy": [
            {
                "capacityProvider": "MyCapacityProvider1",
                "weight": 1,
                "base": 0
            },
            {
                "capacityProvider": "MyCapacityProvider2",
                "weight": 1,
                "base": 0
            }
        ],
        "attachments": [
           {
```

```
                "id": "0fb0c8f4-6edd-4de1-9b09-17e470ee1918",
                "type": "asp",
                "status": "PRECREATED",
                "details": [
                    {
                        "name": "capacityProviderName",
                        "value": "MyCapacityProvider1"
                    },
                    {
                        "name": "scalingPlanName",
                        "value": "ECSManagedAutoScalingPlan-a1b2c3d4-5678-90ab-
cdef-EXAMPLE11111"
                    }
                ]
            },
            {
                "id": "ae592060-2382-4663-9476-b015c685593c",
                "type": "asp",
                "status": "PRECREATED",
                "details": [
                    {
                        "name": "capacityProviderName",
                        "value": "MyCapacityProvider2"
                    },
                    {
                        "name": "scalingPlanName",
                        "value": "ECSManagedAutoScalingPlan-a1b2c3d4-5678-90ab-
cdef-EXAMPLE22222"
                    }
                ]
            }
        ],
        "attachmentsStatus": "UPDATE_IN_PROGRESS"
    }
}
```

Para obter mais informações, consulte provedores de capacidade de clusters no Guia do desenvolvedor do Amazon ECS.

Exemplo 3: como criar um cluster com várias tags

O exemplo `create-cluster` a seguir cria um cluster com várias tags. Para obter mais informações sobre como adicionar tags com sintaxe simplificada, consulte Usar sintaxe simplificada com a AWS Command Line Interface no Guia do usuário da AWS CLI.

```
aws ecs create-cluster \
    --cluster-name MyCluster \
    --tags key=key1,value=value1 key=key2,value=value2 key=key3,value=value3
```

Saída:

```
{
    "cluster": {
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "clusterName": "MyCluster",
        "status": "ACTIVE",
        "registeredContainerInstancesCount": 0,
        "pendingTasksCount": 0,
        "runningTasksCount": 0,
        "activeServicesCount": 0,
        "statistics": [],
        "tags": [
            {
                "key": "key1",
                "value": "value1"
            },
            {
                "key": "key2",
                "value": "value2"
            },
            {
                "key": "key3",
                "value": "value3"
            }
        ]
    }
}
```

Para obter mais informações, consulte Creating a Cluster no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte CreateClusterem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.ExecuteCommandConfiguration;
import software.amazon.awssdk.services.ecs.model.ExecuteCommandLogging;
import software.amazon.awssdk.services.ecs.model.ClusterConfiguration;
import software.amazon.awssdk.services.ecs.model.CreateClusterResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.CreateClusterRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateCluster {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <clusterName>\s

                Where:
                   clusterName - The name of the ECS cluster to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String clusterName = args[0];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        String clusterArn = createGivenCluster(ecsClient, clusterName);
        System.out.println("The cluster ARN is " + clusterArn);
        ecsClient.close();
    }

    public static String createGivenCluster(EcsClient ecsClient, String
 clusterName) {
        try {
            ExecuteCommandConfiguration commandConfiguration =
 ExecuteCommandConfiguration.builder()
                    .logging(ExecuteCommandLogging.DEFAULT)
                    .build();

            ClusterConfiguration clusterConfiguration =
 ClusterConfiguration.builder()
                    .executeCommandConfiguration(commandConfiguration)
                    .build();

            CreateClusterRequest clusterRequest = CreateClusterRequest.builder()
                    .clusterName(clusterName)
                    .configuration(clusterConfiguration)
                    .build();

            CreateClusterResponse response =
 ecsClient.createCluster(clusterRequest);
            return response.cluster().clusterArn();

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateClustera Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_cluster(client: &aws_sdk_ecs::Client, name: &str) -> Result<(),
 aws_sdk_ecs::Error> {
    let cluster = client.create_cluster().cluster_name(name).send().await?;
    println!("cluster created: {:?}", cluster);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWS SDK for Rust.

Crie um serviço do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um serviço do Amazon ECS.

CLI

AWS CLI

Exemplo 1: como criar um serviço com uma tarefa do Fargate

O exemplo de `create-service` a seguir demonstra como criar um serviço usando uma tarefa do Fargate.

```
aws ecs create-service \
    --cluster MyCluster \
    --service-name MyService \
```

```
    --task-definition sample-fargate:1 \
    --desired-count 2 \
    --launch-type FARGATE \
    --platform-version LATEST \
    --network-configuration
 "awsvpcConfiguration={subnets=[subnet-12344321],securityGroups=[sg-12344321],assignPubli
 \
    --tags key=key1,value=value1 key=key2,value=value2 key=key3,value=value3
```

Saída:

```
{
    "service": {
        "serviceArn": "arn:aws:ecs:us-west-2:123456789012:service/MyCluster/
MyService",
        "serviceName": "MyService",
          "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "loadBalancers": [],
        "serviceRegistries": [],
        "status": "ACTIVE",
        "desiredCount": 2,
        "runningCount": 0,
        "pendingCount": 0,
        "launchType": "FARGATE",
        "platformVersion": "LATEST",
        "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-definition/
sample-fargate:1",
        "deploymentConfiguration": {
            "maximumPercent": 200,
            "minimumHealthyPercent": 100
        },
        "deployments": [
            {
                "id": "ecs-svc/1234567890123456789",
                "status": "PRIMARY",
                "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-
definition/sample-fargate:1",
                "desiredCount": 2,
                "pendingCount": 0,
                "runningCount": 0,
                "createdAt": 1557119253.821,
                "updatedAt": 1557119253.821,
                "launchType": "FARGATE",
```

```
                "platformVersion": "1.3.0",
                "networkConfiguration": {
                    "awsvpcConfiguration": {
                        "subnets": [
                            "subnet-12344321"
                        ],
                        "securityGroups": [
                            "sg-12344321"
                        ],
                        "assignPublicIp": "ENABLED"
                    }
                }
            }
        ],
        "roleArn": "arn:aws:iam::123456789012:role/aws-service-role/
ecs.amazonaws.com/AWSServiceRoleForECS",
        "events": [],
        "createdAt": 1557119253.821,
        "placementConstraints": [],
        "placementStrategy": [],
        "networkConfiguration": {
            "awsvpcConfiguration": {
                "subnets": [
                    "subnet-12344321"
                ],
                "securityGroups": [
                    "sg-12344321"
                ],
                "assignPublicIp": "ENABLED"
            }
        },
        "schedulingStrategy": "REPLICA",
        "tags": [
            {
                "key": "key1",
                "value": "value1"
            },
            {
                "key": "key2",
                "value": "value2"
            },
            {
                "key": "key3",
                "value": "value3"
```

```
            }
        ],
        "enableECSManagedTags": false,
        "propagateTags": "NONE"
    }
}
```

Exemplo 2: como criar um serviço usando o tipo de inicialização do EC2

O exemplo de `create-service` a seguir mostra como criar um serviço chamado `ecs-simple-service` com uma tarefa que usa o tipo de inicialização do EC2. O serviço usa a definição de tarefa `sleep360` e mantem uma instanciação da tarefa.

```
aws ecs create-service \
    --cluster MyCluster \
    --service-name ecs-simple-service \
    --task-definition sleep360:2 \
    --desired-count 1
```

Saída:

```
{
    "service": {
        "serviceArn": "arn:aws:ecs:us-west-2:123456789012:service/MyCluster/ecs-
simple-service",
        "serviceName": "ecs-simple-service",
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "loadBalancers": [],
        "serviceRegistries": [],
        "status": "ACTIVE",
        "desiredCount": 1,
        "runningCount": 0,
        "pendingCount": 0,
        "launchType": "EC2",
        "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-definition/
sleep360:2",
        "deploymentConfiguration": {
            "maximumPercent": 200,
            "minimumHealthyPercent": 100
        },
        "deployments": [
            {
                "id": "ecs-svc/1234567890123456789",
```

```
                "status": "PRIMARY",
                "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-
definition/sleep360:2",
                "desiredCount": 1,
                "pendingCount": 0,
                "runningCount": 0,
                "createdAt": 1557206498.798,
                "updatedAt": 1557206498.798,
                "launchType": "EC2"
            }
        ],
        "events": [],
        "createdAt": 1557206498.798,
        "placementConstraints": [],
        "placementStrategy": [],
        "schedulingStrategy": "REPLICA",
        "enableECSManagedTags": false,
        "propagateTags": "NONE"
    }
}
```

Exemplo 3: como criar um serviço que usa um controlador de implantação externo

O exemplo de `create-service` a seguir cria um serviço que usa um controlador de implantação externo.

```
aws ecs create-service \
    --cluster MyCluster \
    --service-name MyService \
    --deployment-controller type=EXTERNAL \
    --desired-count 1
```

Saída:

```
{
    "service": {
        "serviceArn": "arn:aws:ecs:us-west-2:123456789012:service/MyCluster/
MyService",
        "serviceName": "MyService",
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "loadBalancers": [],
        "serviceRegistries": [],
        "status": "ACTIVE",
```

```
        "desiredCount": 1,
        "runningCount": 0,
        "pendingCount": 0,
        "launchType": "EC2",
        "deploymentConfiguration": {
            "maximumPercent": 200,
            "minimumHealthyPercent": 100
        },
        "taskSets": [],
        "deployments": [],
        "roleArn": "arn:aws:iam::123456789012:role/aws-service-role/
ecs.amazonaws.com/AWSServiceRoleForECS",
        "events": [],
        "createdAt": 1557128207.101,
        "placementConstraints": [],
        "placementStrategy": [],
        "schedulingStrategy": "REPLICA",
        "deploymentController": {
            "type": "EXTERNAL"
        },
        "enableECSManagedTags": false,
        "propagateTags": "NONE"
    }
}
```

Exemplo 4: como criar um serviço por trás de um balanceador de carga

O exemplo de `create-service` a seguir mostra como criar um serviço que fique por trás de um balanceador de carga. É necessário ter um balanceador de carga configurado na mesma região da instância de contêiner. Este exemplo usa a opção `--cli-input-json` e um arquivo de entrada JSON `ecs-simple-service-elb.json` com o seguinte conteúdo:

```
{
    "serviceName": "ecs-simple-service-elb",
    "taskDefinition": "ecs-demo",
    "loadBalancers": [
        {
            "loadBalancerName": "EC2Contai-EcsElast-123456789012",
            "containerName": "simple-demo",
            "containerPort": 80
        }
    ],
    "desiredCount": 10,
```

```
    "role": "ecsServiceRole"
}
```

Comando:

```
aws ecs create-service \
    --cluster MyCluster \
    --service-name ecs-simple-service-elb \
    --cli-input-json file://ecs-simple-service-elb.json
```

Saída:

```
{
    "service": {
        "status": "ACTIVE",
        "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-definition/
ecs-demo:1",
        "pendingCount": 0,
        "loadBalancers": [
            {
                "containerName": "ecs-demo",
                "containerPort": 80,
                "loadBalancerName": "EC2Contai-EcsElast-123456789012"
            }
        ],
        "roleArn": "arn:aws:iam::123456789012:role/ecsServiceRole",
        "desiredCount": 10,
        "serviceName": "ecs-simple-service-elb",
        "clusterArn": "arn:aws:ecs:<us-west-2:123456789012:cluster/MyCluster",
        "serviceArn": "arn:aws:ecs:us-west-2:123456789012:service/ecs-simple-
service-elb",
        "deployments": [
            {
                "status": "PRIMARY",
                "pendingCount": 0,
                "createdAt": 1428100239.123,
                "desiredCount": 10,
                "taskDefinition": "arn:aws:ecs:us-west-2:123456789012:task-
definition/ecs-demo:1",
                "updatedAt": 1428100239.123,
                "id": "ecs-svc/1234567890123456789",
                "runningCount": 0
            }
```

```
        ],
        "events": [],
        "runningCount": 0
    }
}
```

Para obter mais informações, consulte Creating a Service no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte CreateServiceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.AwsVpcConfiguration;
import software.amazon.awssdk.services.ecs.model.NetworkConfiguration;
import software.amazon.awssdk.services.ecs.model.CreateServiceRequest;
import software.amazon.awssdk.services.ecs.model.LaunchType;
import software.amazon.awssdk.services.ecs.model.CreateServiceResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateService {
        public static void main(String[] args) {
                final String usage = """
```

```
                                Usage:
                                  <clusterName> <serviceName> <securityGroups>
<subnets> <taskDefinition>

                                Where:
                                  clusterName - The name of the ECS cluster.
                                  serviceName - The name of the ECS service to
create.
                                  securityGroups - The name of the security
group.
                                  subnets - The name of the subnet.
                                  taskDefinition - The name of the task
definition.
                                """;

               if (args.length != 5) {
                       System.out.println(usage);
                       System.exit(1);
               }

               String clusterName = args[0];
               String serviceName = args[1];
               String securityGroups = args[2];
               String subnets = args[3];
               String taskDefinition = args[4];
               Region region = Region.US_EAST_1;
               EcsClient ecsClient = EcsClient.builder()
                               .region(region)
                               .build();

               String serviceArn = createNewService(ecsClient, clusterName,
serviceName, securityGroups, subnets,
                               taskDefinition);
               System.out.println("The ARN of the service is " + serviceArn);
               ecsClient.close();
       }

       public static String createNewService(EcsClient ecsClient,
                       String clusterName,
                       String serviceName,
                       String securityGroups,
                       String subnets,
                       String taskDefinition) {
```

```
                try {
                        AwsVpcConfiguration vpcConfiguration =
 AwsVpcConfiguration.builder()
                                        .securityGroups(securityGroups)
                                        .subnets(subnets)
                                        .build();

                        NetworkConfiguration configuration =
 NetworkConfiguration.builder()
                                        .awsvpcConfiguration(vpcConfiguration)
                                        .build();

                        CreateServiceRequest serviceRequest =
 CreateServiceRequest.builder()
                                        .cluster(clusterName)
                                        .networkConfiguration(configuration)
                                        .desiredCount(1)
                                        .launchType(LaunchType.FARGATE)
                                        .serviceName(serviceName)
                                        .taskDefinition(taskDefinition)
                                        .build();

                        CreateServiceResponse response =
 ecsClient.createService(serviceRequest);
                        return response.service().serviceArn();

                } catch (EcsException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
                return "";
        }
}
```

- Para obter detalhes da API, consulte CreateServicea Referência AWS SDK for Java 2.x da API.

Exclua um cluster do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um cluster do Amazon ECS.

CLI

AWS CLI

Como excluir um cluster vazio

O exemplo de `delete-cluster` a seguir exclui o cluster vazio especificado.

```
aws ecs delete-cluster --cluster MyCluster
```

Saída:

```
{
    "cluster": {
        "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/MyCluster",
        "status": "INACTIVE",
        "clusterName": "MyCluster",
        "registeredContainerInstancesCount": 0,
        "pendingTasksCount": 0,
        "runningTasksCount": 0,
        "activeServicesCount": 0
        "statistics": [],
        "tags": []
    }
}
```

Para obter mais informações, consulte Deleting a Cluster no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte DeleteClusterem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_cluster(
    client: &aws_sdk_ecs::Client,
    name: &str,
) -> Result<(), aws_sdk_ecs::Error> {
    let cluster_deleted = client.delete_cluster().cluster(name).send().await?;
    println!("cluster deleted: {:?}", cluster_deleted);

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWS SDK for Rust.

Exclua um serviço do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um serviço do Amazon ECS.

CLI

AWS CLI

Como excluir um serviço

O exemplo de `ecs delete-service` a seguir exclui o serviço especificado de um cluster. Inclua o parâmetro `--force` para excluir um serviço mesmo que ele não tenha sido reduzido a zero tarefas.

```
aws ecs delete-service --cluster MyCluster --service MyService1 --force
```

Para obter mais informações, consulte Deleting a Service no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte DeleteServiceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DeleteServiceRequest;
import software.amazon.awssdk.services.ecs.model.EcsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DeleteService {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterName> <serviceArn>\s

                Where:
                  clusterName - The name of the ECS cluster.
                  serviceArn - The ARN of the ECS service.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String clusterName = args[0];
        String serviceArn = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        deleteSpecificService(ecsClient, clusterName, serviceArn);
        ecsClient.close();
    }

    public static void deleteSpecificService(EcsClient ecsClient, String
 clusterName, String serviceArn) {
        try {
            DeleteServiceRequest serviceRequest = DeleteServiceRequest.builder()
                    .cluster(clusterName)
                    .service(serviceArn)
                    .build();

            ecsClient.deleteService(serviceRequest);
            System.out.println("The Service was successfully deleted");

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteServicea Referência AWS SDK for Java 2.x da API.

Descreva seus clusters do Amazon ECS usando um SDK da AWS

O exemplo de código a seguir mostra como descrever clusters do Amazon ECS.

CLI

AWS CLI

Exemplo 1: como descrever um cluster

O exemplo de `describe-clusters` a seguir recupera detalhes do cluster especificado.

```
aws ecs describe-clusters \
    --cluster default
```

Saída:

```
{
    "clusters": [
        {
            "status": "ACTIVE",
            "clusterName": "default",
            "registeredContainerInstancesCount": 0,
            "pendingTasksCount": 0,
            "runningTasksCount": 0,
            "activeServicesCount": 1,
            "clusterArn": "arn:aws:ecs:us-west-2:123456789012:cluster/default"
        }
    ],
    "failures": []
}
```

Para obter mais informações, consulte Clusters do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

Exemplo 2: como descrever um cluster com a opção de anexo

O exemplo de `describe-clusters` a seguir especifica a opção de ANEXOS. Ele recupera detalhes sobre o cluster especificado e uma lista dos recursos anexados ao cluster no formato de anexos. Ao usar um provedor de capacidade com um cluster, os recursos, sejam AutoScaling planos ou políticas de escalabilidade, serão representados como ASP ou as_policy ATTACHMENTS.

```
aws ecs describe-clusters \
    --include ATTACHMENTS \
    --clusters sampleCluster
```

Saída:

```
{
```

```
    "clusters": [
        {
            "clusterArn": "arn:aws:ecs:af-south-1:123456789222:cluster/
sampleCluster",
            "clusterName": "sampleCluster",
            "status": "ACTIVE",
            "registeredContainerInstancesCount": 0,
            "runningTasksCount": 0,
            "pendingTasksCount": 0,
            "activeServicesCount": 0,
            "statistics": [],
            "tags": [],
            "settings": [],
            "capacityProviders": [
                "sampleCapacityProvider"
            ],
            "defaultCapacityProviderStrategy": [],
            "attachments": [
                {
                    "id": "a1b2c3d4-5678-901b-cdef-EXAMPLE22222",
                    "type": "as_policy",
                    "status": "CREATED",
                    "details": [
                        {
                            "name": "capacityProviderName",
                            "value": "sampleCapacityProvider"
                        },
                        {
                            "name": "scalingPolicyName",
                            "value": "ECSManagedAutoScalingPolicy-3048e262-
fe39-4eaf-826d-6f975d303188"
                        }
                    ]
                }
            ],
            "attachmentsStatus": "UPDATE_COMPLETE"
        }
    ],
    "failures": []
}
```

Para obter mais informações, consulte Clusters do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte DescribeClustersem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DescribeClustersRequest;
import software.amazon.awssdk.services.ecs.model.DescribeClustersResponse;
import software.amazon.awssdk.services.ecs.model.Cluster;
import software.amazon.awssdk.services.ecs.model.EcsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeClusters {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterArn> \s

                Where:
                  clusterArn - The ARN of the ECS cluster to describe.
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterArn = args[0];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        descCluster(ecsClient, clusterArn);
    }

    public static void descCluster(EcsClient ecsClient, String clusterArn) {
        try {
            DescribeClustersRequest clustersRequest =
 DescribeClustersRequest.builder()
                    .clusters(clusterArn)
                    .build();

            DescribeClustersResponse response =
 ecsClient.describeClusters(clustersRequest);
            List<Cluster> clusters = response.clusters();
            for (Cluster cluster : clusters) {
                System.out.println("The cluster name is " +
 cluster.clusterName());
            }

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_clusters(client: &aws_sdk_ecs::Client) -> Result<(),
 aws_sdk_ecs::Error> {
    let resp = client.list_clusters().send().await?;

    let cluster_arns = resp.cluster_arns();
    println!("Found {} clusters:", cluster_arns.len());

    let clusters = client
        .describe_clusters()
        .set_clusters(Some(cluster_arns.into()))
        .send()
        .await?;

    for cluster in clusters.clusters() {
        println!("  ARN:  {}", cluster.cluster_arn().unwrap());
        println!("  Name: {}", cluster.cluster_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeClustersreferência da API AWS SDK for Rust.

Descreva suas tarefas do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever tarefas do Amazon ECS.

CLI

AWS CLI

Exemplo 1: como descrever uma única tarefa

O exemplo de `describe-tasks` a seguir recupera os detalhes de uma tarefa em um cluster. É possível especificar a tarefa usando o ID ou o ARN completo da tarefa. Este exemplo usa o ARN completo da tarefa.

```
aws ecs describe-tasks \
    --cluster MyCluster \
    --tasks arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/4d590253bb114126b7afa7b58EXAMPLE
```

Saída:

```
{
    "tasks": [
        {
            "attachments": [],
            "attributes": [
                {
                    "name": "ecs.cpu-architecture",
                    "value": "x86_64"
                }
            ],
            "availabilityZone": "us-east-1b",
            "clusterArn": "arn:aws:ecs:us-east-1:123456789012:cluster/MyCluster",
            "connectivity": "CONNECTED",
            "connectivityAt": "2021-08-11T12:21:26.681000-04:00",
            "containerInstanceArn": "arn:aws:ecs:us-
east-1:123456789012:container-instance/test/025c7e2c5e054a6790a29fc1fEXAMPLE",
            "containers": [
                {
                    "containerArn": "arn:aws:ecs:us-
east-1:123456789012:container/MyCluster/4d590253bb114126b7afa7b58eea9221/
a992d1cc-ea46-474a-b6e8-24688EXAMPLE",
                    "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/4d590253bb114126b7afa7b58EXAMPLE",
                    "name": "simple-app",
                    "image": "httpd:2.4",
```

```
                    "runtimeId":
 "91251eed27db90006ad67b1a08187290869f216557717dd5c39b37c94EXAMPLE",
                    "lastStatus": "RUNNING",
                    "networkBindings": [
                        {
                            "bindIP": "0.0.0.0",
                            "containerPort": 80,
                            "hostPort": 80,
                            "protocol": "tcp"
                        }
                    ],
                    "networkInterfaces": [],
                    "healthStatus": "UNKNOWN",
                    "cpu": "10",
                    "memory": "300"
                }
            ],
            "cpu": "10",
            "createdAt": "2021-08-11T12:21:26.681000-04:00",
            "desiredStatus": "RUNNING",
            "enableExecuteCommand": false,
            "group": "service:testupdate",
            "healthStatus": "UNKNOWN",
            "lastStatus": "RUNNING",
            "launchType": "EC2",
            "memory": "300",
            "overrides": {
                "containerOverrides": [
                    {
                        "name": "simple-app"
                    }
                ],
                "inferenceAcceleratorOverrides": []
            },
            "pullStartedAt": "2021-08-11T12:21:28.234000-04:00",
            "pullStoppedAt": "2021-08-11T12:21:33.793000-04:00",
            "startedAt": "2021-08-11T12:21:34.945000-04:00",
            "startedBy": "ecs-svc/968695068243EXAMPLE",
            "tags": [],
            "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/4d590253bb114126b7afa7b58eea9221",
            "taskDefinitionArn": "arn:aws:ecs:us-east-1:123456789012:task-
definition/console-sample-app-static2:1",
            "version": 2
```

```
        }
    ],
    "failures": []
}
```

Para obter mais informações, consulte Definições de tarefa do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

Exemplo 2: como descrever várias tarefas

O exemplo de `describe-tasks` a seguir recupera os detalhes de várias tarefas de um cluster. É possível especificar a tarefa usando o ID ou o ARN completo da tarefa. Este exemplo usa os IDs completos das tarefas.

```
aws ecs describe-tasks \
    --cluster MyCluster \
    --tasks "74de0355a10a4f979ac495c14EXAMPLE" "d789e94343414c25b9f6bd59eEXAMPLE"
```

Saída:

```
{
    "tasks": [
        {
            "attachments": [
                {
                    "id": "d9e7735a-16aa-4128-bc7a-b2d51EXAMPLE",
                    "type": "ElasticNetworkInterface",
                    "status": "ATTACHED",
                    "details": [
                        {
                            "name": "subnetId",
                            "value": "subnet-0d0eab1bb3EXAMPLE"
                        },
                        {
                            "name": "networkInterfaceId",
                            "value": "eni-0fa40520aeEXAMPLE"
                        },
                        {
                            "name": "macAddress",
                            "value": "0e:89:76:28:07:b3"
                        },
                        {
                            "name": "privateDnsName",
```

```
                            "value": "ip-10-0-1-184.ec2.internal"
                        },
                        {
                            "name": "privateIPv4Address",
                            "value": "10.0.1.184"
                        }
                    ]
                }
            ],
            "attributes": [
                {
                    "name": "ecs.cpu-architecture",
                    "value": "x86_64"
                }
            ],
            "availabilityZone": "us-east-1b",
            "clusterArn": "arn:aws:ecs:us-east-1:123456789012:cluster/MyCluster",
            "connectivity": "CONNECTED",
            "connectivityAt": "2021-12-20T12:13:37.875000-05:00",
            "containers": [
                {
                    "containerArn": "arn:aws:ecs:us-
east-1:123456789012:container/MyCluster/74de0355a10a4f979ac495c14EXAMPLE/
aad3ba00-83b3-4dac-84d4-11f8cEXAMPLE",
                    "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/74de0355a10a4f979ac495c14EXAMPLE",
                    "name": "web",
                    "image": "nginx",
                    "runtimeId": "74de0355a10a4f979ac495c14EXAMPLE-265927825",
                    "lastStatus": "RUNNING",
                    "networkBindings": [],
                    "networkInterfaces": [
                        {
                            "attachmentId": "d9e7735a-16aa-4128-bc7a-
b2d51EXAMPLE",
                            "privateIpv4Address": "10.0.1.184"
                        }
                    ],
                    "healthStatus": "UNKNOWN",
                    "cpu": "99",
                    "memory": "100"
                }
            ],
            "cpu": "256",
```

```
            "createdAt": "2021-12-20T12:13:20.226000-05:00",
            "desiredStatus": "RUNNING",
            "enableExecuteCommand": false,
            "group": "service:tdsevicetag",
            "healthStatus": "UNKNOWN",
            "lastStatus": "RUNNING",
            "launchType": "FARGATE",
            "memory": "512",
            "overrides": {
                "containerOverrides": [
                    {
                        "name": "web"
                    }
                ],
                "inferenceAcceleratorOverrides": []
            },
            "platformVersion": "1.4.0",
            "platformFamily": "Linux",
            "pullStartedAt": "2021-12-20T12:13:42.665000-05:00",
            "pullStoppedAt": "2021-12-20T12:13:46.543000-05:00",
            "startedAt": "2021-12-20T12:13:48.086000-05:00",
            "startedBy": "ecs-svc/988401040018EXAMPLE",
            "tags": [],
            "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/74de0355a10a4f979ac495c14EXAMPLE",
            "taskDefinitionArn": "arn:aws:ecs:us-east-1:123456789012:task-
definition/webserver:2",
            "version": 3,
            "ephemeralStorage": {
            "sizeInGiB": 20
            }
        },
        {
            "attachments": [
                {
                    "id": "214eb5a9-45cd-4bf8-87bc-57fefEXAMPLE",
                    "type": "ElasticNetworkInterface",
                    "status": "ATTACHED",
                    "details": [
                        {
                            "name": "subnetId",
                            "value": "subnet-0d0eab1bb3EXAMPLE"
                        },
                        {
```

```
                            "name": "networkInterfaceId",
                            "value": "eni-064c7766daEXAMPLE"
                        },
                        {
                            "name": "macAddress",
                            "value": "0e:76:83:01:17:a9"
                        },
                        {
                            "name": "privateDnsName",
                            "value": "ip-10-0-1-41.ec2.internal"
                        },
                        {
                            "name": "privateIPv4Address",
                            "value": "10.0.1.41"
                        }
                    ]
                }
            ],
            "attributes": [
                {
                    "name": "ecs.cpu-architecture",
                    "value": "x86_64"
                }
            ],
            "availabilityZone": "us-east-1b",
            "clusterArn": "arn:aws:ecs:us-east-1:123456789012:cluster/MyCluster",
            "connectivity": "CONNECTED",
            "connectivityAt": "2021-12-20T12:13:35.243000-05:00",
            "containers": [
                {
                    "containerArn": "arn:aws:ecs:us-
east-1:123456789012:container/MyCluster/
d789e94343414c25b9f6bd59eEXAMPLE/9afef792-609b-43a5-bb6a-3efdbEXAMPLE",
                    "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/
MyCluster/d789e94343414c25b9f6bd59eEXAMPLE",
                    "name": "web",
                    "image": "nginx",
                    "runtimeId": "d789e94343414c25b9f6bd59eEXAMPLE-265927825",
                    "lastStatus": "RUNNING",
                    "networkBindings": [],
                    "networkInterfaces": [
                        {
                            "attachmentId":
 "214eb5a9-45cd-4bf8-87bc-57fefEXAMPLE",
```

```
                            "privateIpv4Address": "10.0.1.41"
                        }
                    ],
                    "healthStatus": "UNKNOWN",
                    "cpu": "99",
                    "memory": "100"
                }
            ],
            "cpu": "256",
            "createdAt": "2021-12-20T12:13:20.226000-05:00",
            "desiredStatus": "RUNNING",
            "enableExecuteCommand": false,
            "group": "service:tdsevicetag",
            "healthStatus": "UNKNOWN",
            "lastStatus": "RUNNING",
            "launchType": "FARGATE",
            "memory": "512",
            "overrides": {
                "containerOverrides": [
                    {
                        "name": "web"
                    }
                ],
                "inferenceAcceleratorOverrides": []
            },
            "platformVersion": "1.4.0",
            "platformFamily": "Linux",
            "pullStartedAt": "2021-12-20T12:13:44.611000-05:00",
            "pullStoppedAt": "2021-12-20T12:13:48.251000-05:00",
            "startedAt": "2021-12-20T12:13:49.326000-05:00",
            "startedBy": "ecs-svc/988401040018EXAMPLE",
            "tags": [],
            "taskArn": "arn:aws:ecs:us-east-1:123456789012:task/MyCluster/
d789e94343414c25b9f6bd59eEXAMPLE",
            "taskDefinitionArn": "arn:aws:ecs:us-east-1:123456789012:task-
definition/webserver:2",
            "version": 3,
            "ephemeralStorage": {
                "sizeInGiB": 20
            }
        }
    ],
    "failures": []
```

```
}
```

Para obter mais informações, consulte Definições de tarefa do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte DescribeTasksem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DescribeTasksRequest;
import software.amazon.awssdk.services.ecs.model.DescribeTasksResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.Task;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListTaskDefinitions {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterArn> <taskId>\s

                Where:
```

```
                  clusterArn - The ARN of an ECS cluster.
                  taskId - The task Id value.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterArn = args[0];
        String taskId = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        getAllTasks(ecsClient, clusterArn, taskId);
        ecsClient.close();
    }

    public static void getAllTasks(EcsClient ecsClient, String clusterArn, String
 taskId) {
        try {
            DescribeTasksRequest tasksRequest = DescribeTasksRequest.builder()
                    .cluster(clusterArn)
                    .tasks(taskId)
                    .build();

            DescribeTasksResponse response =
 ecsClient.describeTasks(tasksRequest);
            List<Task> tasks = response.tasks();
            for (Task task : tasks) {
                System.out.println("The task ARN is " +
 task.taskDefinitionArn());
            }

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeTasksa Referência AWS SDK for Java 2.x da API.

Liste seus clusters do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como listar clusters do Amazon ECS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obter informações de ARN para clusters, serviços e tarefas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List cluster ARNs available.
    /// </summary>
    /// <returns>The ARN list of clusters.</returns>
    public async Task<List<string>> GetClusterARNSAsync()
    {

        Console.WriteLine("Getting a list of all the clusters in your AWS
account...");
        List<string> clusterArnList = new List<string>();
        // Get a list of all the clusters in your AWS account
        try
        {

            var listClustersResponse = _ecsClient.Paginators.ListClusters(new
ListClustersRequest
            {
            });
```

```
            var clusterArns = listClustersResponse.ClusterArns;

            // Print the ARNs of the clusters
            await foreach (var clusterArn in clusterArns)
            {
                clusterArnList.Add(clusterArn);
            }

            if (clusterArnList.Count == 0)
            {
                _logger.LogWarning("No clusters found in your AWS account.");
            }
            return clusterArnList;
        }
        catch (Exception e)
        {
            _logger.LogError($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
            throw new Exception($"An error occurred while getting a list of all
the clusters in your AWS account. {e.InnerException}");
        }
    }
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os clusters disponíveis

O exemplo de `list-clusters` a seguir lista todos os clusters disponíveis.

```
aws ecs list-clusters
```

Saída:

```
{
    "clusterArns": [
        "arn:aws:ecs:us-west-2:123456789012:cluster/MyECSCluster1",
```

```
        "arn:aws:ecs:us-west-2:123456789012:cluster/AnotherECSCluster"
    ]
}
```

Para obter mais informações, consulte Clusters do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte ListClustersem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.ListClustersResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class ListClusters {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();
```

```
        listAllClusters(ecsClient);
        ecsClient.close();
    }

    public static void listAllClusters(EcsClient ecsClient) {
        try {
            ListClustersResponse response = ecsClient.listClusters();
            List<String> clusters = response.clusterArns();
            for (String cluster : clusters) {
                System.out.println("The cluster arn is " + cluster);
            }

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for Java 2.x da API.

Liste seus serviços do Amazon ECS em um cluster usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os serviços do Amazon ECS em um cluster.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obter informações de ARN para clusters, serviços e tarefas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List service ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
    /// <returns>The ARN list of services in given cluster.</returns>
    public async Task<List<string>> GetServiceARNSAsync(string clusterARN)
    {
        List<string> serviceArns = new List<string>();

        var request = new ListServicesRequest
        {
            Cluster = clusterARN
        };
        // Call the ListServices API operation and get the list of service ARNs
        var serviceList = _ecsClient.Paginators.ListServices(request);

        await foreach (var serviceARN in serviceList.ServiceArns)
        {
            if (serviceARN is null)
                continue;

            serviceArns.Add(serviceARN);
        }

        if (serviceArns.Count == 0)
        {
            _logger.LogWarning($"No services found in cluster {clusterARN} .");
        }

        return serviceArns;
    }
```

- Para obter detalhes da API, consulte ListServicesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os serviços em um cluster

O exemplo de `list-services` a seguir mostra como listar os serviços em execução em um cluster.

```
aws ecs list-services --cluster MyCluster
```

Saída:

```
 {
     "serviceArns": [
         "arn:aws:ecs:us-west-2:123456789012:service/MyCluster/MyService"
     ]
}
```

Para obter mais informações, consulte Serviços no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte ListServicesem Referência de AWS CLI Comandos.

Liste suas tarefas do Amazon ECS em um cluster usando um SDK da AWS

Os exemplos de código a seguir mostram como listar as tarefas do Amazon ECS em um cluster.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obter informações de ARN para clusters, serviços e tarefas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List task ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
```

```
    /// <returns>The ARN list of tasks in given cluster.</returns>
    public async Task<List<string>> GetTaskARNsAsync(string clusterARN)
    {
        // Set up the request to describe the tasks in the service
        var listTasksRequest = new ListTasksRequest
        {
            Cluster = clusterARN
        };
        List<string> taskArns = new List<string>();

        // Call the ListTasks API operation and get the list of task ARNs
        var tasks = _ecsClient.Paginators.ListTasks(listTasksRequest);

        await foreach (var task in tasks.TaskArns)
        {
            if (task is null)
                continue;


            taskArns.Add(task);
        }

        if (taskArns.Count == 0)
        {
            _logger.LogWarning("No tasks found in cluster: " + clusterARN);
        }

        return taskArns;
    }
```

- Para obter detalhes da API, consulte ListTasksa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como listar as tarefas em um cluster

O exemplo de `list-tasks` a seguir lista todas as tarefas de um cluster.

```
aws ecs list-tasks --cluster default
```

Saída:

```
{
    "taskArns": [
        "arn:aws:ecs:us-west-2:123456789012:task/a1b2c3d4-5678-90ab-
cdef-11111EXAMPLE",
        "arn:aws:ecs:us-west-2:123456789012:task/a1b2c3d4-5678-90ab-
cdef-22222EXAMPLE"
    ]
}
```

Exemplo 2: como listar as tarefas de uma instância de contêiner específica

O exemplo de `list-tasks` a seguir lista as tarefas de uma instância de contêiner, usando o UUID da instância de contêiner como filtro.

```
aws ecs list-tasks --cluster default --container-instance a1b2c3d4-5678-90ab-
cdef-33333EXAMPLE
```

Saída:

```
{
    "taskArns": [
        "arn:aws:ecs:us-west-2:123456789012:task/a1b2c3d4-5678-90ab-
cdef-44444EXAMPLE"
    ]
}
```

Para obter mais informações, consulte Definições de tarefa do Amazon ECS no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte ListTasksem Referência de AWS CLI Comandos.

Atualize um serviço do Amazon ECS usando um SDK da AWS

Os exemplos de código a seguir mostram como atualizar um serviço do Amazon ECS.

CLI

AWS CLI

Exemplo 1: como alterar a definição de tarefa usada em um serviço

O exemplo de `update-service` a seguir atualiza o serviço `my-http-service` para usar a definição de tarefa `amazon-ecs-sample`.

```
aws ecs update-service --service my-http-service --task-definition amazon-ecs-
sample
```

Exemplo 2: Para alterar o número de tarefas em um serviço

O exemplo de `update-service` a seguir atualiza a contagem de tarefas desejada do serviço `my-http-service` para 3.

```
aws ecs update-service --service my-http-service --desired-count 3
```

Para obter mais informações, consulte Updating a Service no Guia do desenvolvedor do Amazon ECS.

- Para obter detalhes da API, consulte UpdateServiceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.UpdateServiceRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 */

public class UpdateService {

    public static void main(String[] args) {

        final String usage = """

                Usage:
                   <clusterName> <serviceArn>\s

                Where:
                  clusterName - The cluster name.
                  serviceArn - The service ARN value.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterName = args[0];
        String serviceArn = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        updateSpecificService(ecsClient, clusterName, serviceArn);
        ecsClient.close();
    }

    public static void updateSpecificService(EcsClient ecsClient, String
 clusterName, String serviceArn) {
        try {
            UpdateServiceRequest serviceRequest = UpdateServiceRequest.builder()
                    .cluster(clusterName)
                    .service(serviceArn)
                    .desiredCount(0)
                    .build();

            ecsClient.updateService(serviceRequest);
            System.out.println("The service was modified");
```

```
        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateServicea Referência AWS SDK for Java 2.x da API.

Cenários para o Amazon ECS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Container Service (Amazon ECS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Obtenha informações de ARN para clusters, serviços e tarefas do Amazon ECS usando um SDK da AWS

Obtenha informações de ARN para clusters, serviços e tarefas do Amazon ECS usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Obtenha uma lista de todos os clusters.
- Obtenha serviços para um cluster.
- Obtenha tarefas para um cluster.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
using Amazon.ECS;
using ECSActions;
using Microsoft.Extensions.Hosting;
using Microsoft.Extensions.Logging;
using Microsoft.Extensions.Logging.Console;
using Microsoft.Extensions.Logging.Debug;

namespace ECSScenario;

public class ECSScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.


    This .NET example performs the following tasks:
        1. List ECS Cluster ARNs.
        2. List services in every cluster
        3. List Task ARNs in every cluster.
    */

    private static ILogger logger = null!;
    private static ECSWrapper _ecsWrapper = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
```

```
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
       .Build();

       ILoggerFactory loggerFactory = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       });

       logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
           .CreateLogger<ECSScenario>();

       var loggerECSWarpper = LoggerFactory.Create(builder =>
{ builder.AddConsole(); })
         .CreateLogger<ECSWrapper>();

       var amazonECSClient = new AmazonECSClient();

       _ecsWrapper = new ECSWrapper(amazonECSClient, loggerECSWarpper);

       Console.WriteLine(new string('-', 80));
       Console.WriteLine("Welcome to the Amazon ECS example scenario.");
       Console.WriteLine(new string('-', 80));

       try
       {
           await ListClusterARNs();
           await ListServiceARNs();
           await ListTaskARNs();

       }
       catch (Exception ex)
       {
           logger.LogError(ex, "There was a problem executing the scenario.");
       }
   }

   /// <summary>
   /// List ECS Cluster ARNs
   /// </summary>
   private static async Task ListClusterARNs()
   {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. List Cluster ARNs from ECS.");
        var arns = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var arn in arns)
        {
            Console.WriteLine($"Cluster arn: {arn}");
            Console.WriteLine($"Cluster name: {arn.Split("/").Last()}");
        }

        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// List services in every cluster
    /// </summary>
    private static async Task ListServiceARNs()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"2. List Service ARNs in every cluster.");
        var clusterARNs = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var clusterARN in clusterARNs)
        {
            Console.WriteLine($"Getting services for cluster name:
{clusterARN.Split("/").Last()}");
            Console.WriteLine(new string('.', 5));


            var serviceARNs = await _ecsWrapper.GetServiceARNSAsync(clusterARN);

            foreach (var serviceARN in serviceARNs)
            {
                Console.WriteLine($"Service arn: {serviceARN}");
                Console.WriteLine($"Service name:
{serviceARN.Split("/").Last()}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }
```

```
    /// <summary>
    /// List tasks in every cluster
    /// </summary>
    private static async Task ListTaskARNs()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. List Task ARNs in every cluster.");
        var clusterARNs = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var clusterARN in clusterARNs)
        {
            Console.WriteLine($"Getting tasks for cluster name:
 {clusterARN.Split("/").Last()}");
            Console.WriteLine(new string('.', 5));

            var taskARNs = await _ecsWrapper.GetTaskARNsAsync(clusterARN);

            foreach (var taskARN in taskARNs)
            {
                Console.WriteLine($"Task arn: {taskARN}");
            }
        }
        Console.WriteLine(new string('-', 80));
    }
}
```

Métodos de encapsulamento que são chamados pelo cenário para gerenciar as ações do Amazon ECS.

```
using Amazon.ECS;
using Amazon.ECS.Model;
using Microsoft.Extensions.Logging;

namespace ECSActions;

public class ECSWrapper
{
    private readonly AmazonECSClient _ecsClient;
    private readonly ILogger<ECSWrapper> _logger;

    /// <summary>
    /// Constructor for the ECS wrapper.
```

```
    /// </summary>
    /// <param name="ecsClient">The injected ECS client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public ECSWrapper(AmazonECSClient ecsClient, ILogger<ECSWrapper> logger)

    {
        _logger = logger;
        _ecsClient = ecsClient;
    }

    /// <summary>
    /// List cluster ARNs available.
    /// </summary>
    /// <returns>The ARN list of clusters.</returns>
    public async Task<List<string>> GetClusterARNSAsync()
    {

        Console.WriteLine("Getting a list of all the clusters in your AWS
 account...");
        List<string> clusterArnList = new List<string>();
        // Get a list of all the clusters in your AWS account
        try
        {

            var listClustersResponse = _ecsClient.Paginators.ListClusters(new
 ListClustersRequest
            {
            });

            var clusterArns = listClustersResponse.ClusterArns;

            // Print the ARNs of the clusters
            await foreach (var clusterArn in clusterArns)
            {
                clusterArnList.Add(clusterArn);
            }

            if (clusterArnList.Count == 0)
            {
                _logger.LogWarning("No clusters found in your AWS account.");
            }
            return clusterArnList;
        }
        catch (Exception e)
```

```
        {
            _logger.LogError($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
            throw new Exception($"An error occurred while getting a list of all
the clusters in your AWS account. {e.InnerException}");
        }
    }

    /// <summary>
    /// List service ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
    /// <returns>The ARN list of services in given cluster.</returns>
    public async Task<List<string>> GetServiceARNSAsync(string clusterARN)
    {
        List<string> serviceArns = new List<string>();

        var request = new ListServicesRequest
        {
            Cluster = clusterARN
        };
        // Call the ListServices API operation and get the list of service ARNs
        var serviceList = _ecsClient.Paginators.ListServices(request);

        await foreach (var serviceARN in serviceList.ServiceArns)
        {
            if (serviceARN is null)
                continue;

            serviceArns.Add(serviceARN);
        }

        if (serviceArns.Count == 0)
        {
            _logger.LogWarning($"No services found in cluster {clusterARN} .");
        }

        return serviceArns;
    }

    /// <summary>
    /// List task ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
```

```
    /// <returns>The ARN list of tasks in given cluster.</returns>
    public async Task<List<string>> GetTaskARNsAsync(string clusterARN)
    {
        // Set up the request to describe the tasks in the service
        var listTasksRequest = new ListTasksRequest
        {
            Cluster = clusterARN
        };
        List<string> taskArns = new List<string>();

        // Call the ListTasks API operation and get the list of task ARNs
        var tasks = _ecsClient.Paginators.ListTasks(listTasksRequest);

        await foreach (var task in tasks.TaskArns)
        {
            if (task is null)
                continue;


            taskArns.Add(task);
        }

        if (taskArns.Count == 0)
        {
            _logger.LogWarning("No tasks found in cluster: " + clusterARN);
        }

        return taskArns;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - ListClusters
  - ListServices
  - ListTasks

Exemplos de código para o Amazon EKS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Kubernetes Service (Amazon EKS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Amazon EKS – Mais informações sobre o Amazon EKS.
- Referência da API do Amazon EKS – Detalhes sobre todas as ações disponíveis do Amazon EKS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon EKS usando SDKs da AWS
  - Crie um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS
  - Exclua um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS

Ações para o Amazon EKS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Elastic Kubernetes Service (Amazon EKS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS
- Exclua um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS

Crie um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS

Os exemplos de código a seguir mostram como criar ambiente de gerenciamento de cluster do Amazon EKS.

CLI

AWS CLI

Como criar um cluster

Este comando de exemplo cria o cluster `prod` na sua região padrão.

Comando:

```
aws eks create-cluster --name prod \
--role-arn arn:aws:iam::012345678910:role/eks-service-role-
AWSServiceRoleForAmazonEKS-J7ONKE3BQ4PI \
--resources-vpc-config subnetIds=subnet-6782e71e,subnet-
e7e761ac,securityGroupIds=sg-6979fe18
```

Saída:

```
{
    "cluster": {
        "name": "prod",
        "arn": "arn:aws:eks:us-west-2:012345678910:cluster/prod",
        "createdAt": 1527808069.147,
        "version": "1.10",
        "roleArn": "arn:aws:iam::012345678910:role/eks-service-role-
AWSServiceRoleForAmazonEKS-J7ONKE3BQ4PI",
        "resourcesVpcConfig": {
            "subnetIds": [
                "subnet-6782e71e",
                "subnet-e7e761ac"
            ],
            "securityGroupIds": [
                "sg-6979fe18"
            ],
            "vpcId": "vpc-950809ec"
        },
```

```
        "status": "CREATING",
        "certificateAuthority": {}
    }
}
```

Como criar um cluster com acesso ao endpoint privado e registro em log habilitado

Este comando de exemplo cria o cluster `example` na região padrão com acesso ao endpoint público desabilitado e acesso ao endpoint privado e todos os tipos de registro em log habilitados.

Comando:

```
aws eks create-cluster --name example --kubernetes-version 1.12 \
--role-arn arn:aws:iam::012345678910:role/example-cluster-
ServiceRole-1XWBQWYSFRE2Q \
--resources-vpc-config
 subnetIds=subnet-0a188dccd2f9a632f,subnet-09290d93da4278664,subnet-0f21dd86e0e91134a,sub
 \
--logging '{"clusterLogging":[{"types":
["api","audit","authenticator","controllerManager","scheduler"],"enabled":true}]}'
```

Saída:

```
{
    "cluster": {
        "name": "example",
        "arn": "arn:aws:eks:us-west-2:012345678910:cluster/example",
        "createdAt": 1565804921.901,
        "version": "1.12",
        "roleArn": "arn:aws:iam::012345678910:role/example-cluster-
ServiceRole-1XWBQWYSFRE2Q",
        "resourcesVpcConfig": {
            "subnetIds": [
                "subnet-0a188dccd2f9a632f",
                "subnet-09290d93da4278664",
                "subnet-0f21dd86e0e91134a",
                "subnet-0173dead68481a583",
                "subnet-051f70a57ed6fcab6",
                "subnet-01322339c5c7de9b4"
            ],
            "securityGroupIds": [
```

```
                "sg-0c5b580845a031c10"
            ],
            "vpcId": "vpc-0f622c01f68d4afec",
            "endpointPublicAccess": false,
            "endpointPrivateAccess": true
        },
        "logging": {
            "clusterLogging": [
                {
                    "types": [
                        "api",
                        "audit",
                        "authenticator",
                        "controllerManager",
                        "scheduler"
                    ],
                    "enabled": true
                }
            ]
        },
        "status": "CREATING",
        "certificateAuthority": {},
        "platformVersion": "eks.3"
    }
}
```

- Para obter detalhes da API, consulte CreateClusterem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_cluster(
    client: &aws_sdk_eks::Client,
    name: &str,
    arn: &str,
```

```
    subnet_ids: Vec<String>,
) -> Result<(), aws_sdk_eks::Error> {
    let cluster = client
        .create_cluster()
        .name(name)
        .role_arn(arn)
        .resources_vpc_config(
            VpcConfigRequest::builder()
                .set_subnet_ids(Some(subnet_ids))
                .build(),
        )
        .send()
        .await?;
    println!("cluster created: {:?}", cluster);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWS SDK for Rust.

Exclua um ambiente de gerenciamento de cluster do Amazon EKS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um cluster do Amazon EKS.

CLI

AWS CLI

Para excluir um cluster

Este comando de exemplo exclui o cluster `devel` na sua região padrão.

Comando:

```
aws eks delete-cluster --name devel
```

- Para obter detalhes da API, consulte DeleteClusterem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_cluster(
    client: &aws_sdk_eks::Client,
    name: &str,
) -> Result<(), aws_sdk_eks::Error> {
    let cluster_deleted = client.delete_cluster().name(name).send().await?;
    println!("cluster deleted: {:?}", cluster_deleted);

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWS SDK for Rust.

Exemplos de código para o Elastic Beanstalk usando SDKs AWS

Os exemplos de código a seguir mostram como usar AWS Elastic Beanstalk com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Elastic Beanstalk — Mais informações sobre o Elastic Beanstalk.
- Referência da API do Elastic Beanstalk — Detalhes sobre todas as ações disponíveis do Elastic Beanstalk.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.

- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Elastic Beanstalk usando SDKs AWS
  - Descrever um aplicativo do Elastic Beanstalk usando um SDK AWS
  - Listar pilhas do Elastic Beanstalk usando um SDK AWS
  - Atualizar um aplicativo do Elastic Beanstalk usando um SDK AWS

Ações para o Elastic Beanstalk usando SDKs AWS

Os exemplos de código a seguir mostram como usar o AWS Elastic Beanstalk com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Descrever um aplicativo do Elastic Beanstalk usando um SDK AWS
- Listar pilhas do Elastic Beanstalk usando um SDK AWS
- Atualizar um aplicativo do Elastic Beanstalk usando um SDK AWS

Descrever um aplicativo do Elastic Beanstalk usando um SDK AWS

O exemplo de código a seguir mostra como descrever um AWS Elastic Beanstalk aplicativo.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Class to manage Elastic Beanstalk applications
class ElasticBeanstalkManager
  def initialize(eb_client, logger: Logger.new($stdout))
```

```
    @eb_client = eb_client
    @logger = logger
  end

  # Lists applications and their environments
  def list_applications
    @eb_client.describe_applications.applications.each do |application|
      log_application_details(application)
      list_environments(application.application_name)
    end
  rescue Aws::ElasticBeanstalk::Errors::ServiceError => e
    @logger.error("Elastic Beanstalk Service Error: #{e.message}")
  end

  private

  # Logs application details
  def log_application_details(application)
    @logger.info("Name:        #{application.application_name}")
    @logger.info("Description: #{application.description}")
  end

  # Lists and logs details of environments for a given application
  def list_environments(application_name)
    @eb_client.describe_environments(application_name:
 application_name).environments.each do |env|
      @logger.info("  Environment:  #{env.environment_name}")
      @logger.info("    URL:        #{env.cname}")
      @logger.info("    Health:     #{env.health}")
    end
  rescue Aws::ElasticBeanstalk::Errors::ServiceError => e
    @logger.error("Error listing environments for application
 #{application_name}: #{e.message}")
  end
end
```

- Para obter detalhes da API, consulte DescribeApplicationsa Referência AWS SDK for Ruby da API.

Listar pilhas do Elastic Beanstalk usando um SDK AWS

O exemplo de código a seguir mostra como listar AWS Elastic Beanstalk pilhas.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Manages listing of AWS Elastic Beanstalk solution stacks
# @param [Aws::ElasticBeanstalk::Client] eb_client
# @param [String] filter - Returns subset of results based on match
# @param [Logger] logger
class StackLister
  # Initialize with AWS Elastic Beanstalk client
  def initialize(eb_client, filter, logger: Logger.new($stdout))
    @eb_client = eb_client
    @filter = filter.downcase
    @logger = logger
  end

  # Lists and logs Elastic Beanstalk solution stacks
  def list_stacks
    stacks = @eb_client.list_available_solution_stacks.solution_stacks
    orig_length = stacks.length
    filtered_length = 0

    stacks.each do |stack|
      if @filter.empty? || stack.downcase.include?(@filter)
        @logger.info(stack)
        filtered_length += 1
      end
    end

    log_summary(filtered_length, orig_length)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Error listing solution stacks: #{e.message}")
  end

  private
```

```
  # Logs summary of listed stacks
  def log_summary(filtered_length, orig_length)
    if @filter.empty?
      @logger.info("Showed #{orig_length} stack(s)")
    else
      @logger.info("Showed #{filtered_length} stack(s) of #{orig_length}")
    end
  end
end
```

- Para obter detalhes da API, consulte ListAvailableSolutionStacksa Referência AWS SDK for Ruby da API.

Atualizar um aplicativo do Elastic Beanstalk usando um SDK AWS

Os exemplos de código a seguir mostram como atualizar um AWS Elastic Beanstalk aplicativo.

CLI

AWS CLI

Para alterar a descrição de um aplicativo

O comando a seguir atualiza a descrição de um aplicativo chamado`my-app`:

```
aws elasticbeanstalk update-application --application-name my-app --description
 "my Elastic Beanstalk application"
```

Saída:

```
{
    "Application": {
        "ApplicationName": "my-app",
        "Description": "my Elastic Beanstalk application",
        "Versions": [
            "2fba-stage-150819_234450",
            "bf07-stage-150820_214945",
            "93f8",
            "fd7c-stage-150820_000431",
            "22a0-stage-150819_185942"
        ],
```

```
        "DateCreated": "2015-08-13T19:15:50.449Z",
        "ConfigurationTemplates": [],
        "DateUpdated": "2015-08-20T22:34:56.195Z"
    }
}
```

- Para obter detalhes da API, consulte UpdateApplicationem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Manages deployment of Rails applications to AWS Elastic Beanstalk
class RailsAppDeployer
  def initialize(eb_client, s3_client, app_name, logger: Logger.new($stdout))
    @eb_client = eb_client
    @s3_client = s3_client
    @app_name = app_name
    @logger = logger
  end

  # Deploys the latest application version to Elastic Beanstalk
  def deploy
    create_storage_location
    zip_file_name = create_zip_file
    upload_zip_to_s3(zip_file_name)
    create_and_deploy_new_application_version(zip_file_name)
  end

  private

  # Creates a new S3 storage location for the application
  def create_storage_location
    resp = @eb_client.create_storage_location
```

```
    @logger.info("Created storage location in bucket #{resp.s3_bucket}")
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to create storage location: #{e.message}")
  end

  # Creates a ZIP file of the application using git
  def create_zip_file
    zip_file_basename = SecureRandom.urlsafe_base64
    zip_file_name = "#{zip_file_basename}.zip"
    `git archive --format=zip -o #{zip_file_name} HEAD`
    zip_file_name
  end

  # Uploads the ZIP file to the S3 bucket
  def upload_zip_to_s3(zip_file_name)
    zip_contents = File.read(zip_file_name)
    key = "#{@app_name}/#{zip_file_name}"
    @s3_client.put_object(body: zip_contents, bucket: fetch_bucket_name, key:
key)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to upload ZIP file to S3: #{e.message}")
  end

  # Fetches the S3 bucket name from Elastic Beanstalk application versions
  def fetch_bucket_name
    app_versions = @eb_client.describe_application_versions(application_name:
@app_name)
    av = app_versions.application_versions.first
    av.source_bundle.s3_bucket
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to fetch bucket name: #{e.message}")
    raise
  end

  # Creates a new application version and deploys it
  def create_and_deploy_new_application_version(zip_file_name)
    version_label = File.basename(zip_file_name, ".zip")
    @eb_client.create_application_version(
      process: false,
      application_name: @app_name,
      version_label: version_label,
      source_bundle: {
        s3_bucket: fetch_bucket_name,
        s3_key: "#{@app_name}/#{zip_file_name}"
```

```
      },
      description: "Updated #{Time.now.strftime('%d/%m/%Y')}"
    )
    update_environment(version_label)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to create or deploy application version: #{e.message}")
  end

  # Updates the environment to the new application version
  def update_environment(version_label)
    env_name = fetch_environment_name
    @eb_client.update_environment(
      environment_name: env_name,
      version_label: version_label
    )
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to update environment: #{e.message}")
  end

  # Fetches the environment name of the application
  def fetch_environment_name
    envs = @eb_client.describe_environments(application_name: @app_name)
    envs.environments.first.environment_name
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to fetch environment name: #{e.message}")
    raise
  end
end
```

- Para obter detalhes da API, consulte UpdateApplicationa Referência AWS SDK for Ruby da API.

Exemplos de código para o Elastic Load Balancing usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Elastic Load Balancing (ELB) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do Elastic Load Balancing – Mais informações sobre o Elastic Load Balancing
- Referência da API do Elastic Load Balancing – Detalhes sobre todas as ações disponíveis do Elastic Load Balancing.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Elastic Load Balancing

Os exemplos de código a seguir mostram como começar a usar o Elastic Load Balancing.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class HelloLoadBalancer {

        public static void main(String[] args) {
                ElasticLoadBalancingV2Client loadBalancingV2Client =
 ElasticLoadBalancingV2Client.builder()
                                .region(Region.US_EAST_1)
```

```
                                .build();

                DescribeLoadBalancersResponse loadBalancersResponse =
 loadBalancingV2Client
                                .describeLoadBalancers(r -> r.pageSize(10));
                List<LoadBalancer> loadBalancerList =
 loadBalancersResponse.loadBalancers();
                for (LoadBalancer lb : loadBalancerList)
                        System.out.println("Load Balancer DNS name = " +
 lb.dnsName());
        }
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  ElasticLoadBalancingV2Client,
  DescribeLoadBalancersCommand,
} from "@aws-sdk/client-elastic-load-balancing-v2";

export async function main() {
  const client = new ElasticLoadBalancingV2Client({});
  const { LoadBalancers } = await client.send(
    new DescribeLoadBalancersCommand({}),
  );
  const loadBalancersList = LoadBalancers.map(
```

```
    (lb) => `• ${lb.LoadBalancerName}: ${lb.DNSName}`,
  ).join("\n");
  console.log(
    "Hello, Elastic Load Balancing! Let's list some of your load balancers:\n",
    loadBalancersList,
  );
}

// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  main();
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_elbv2(elbv2_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Elastic Load Balancing V2
 client and list
    up to ten of the load balancers for your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param elbv2_client: A Boto3 Elastic Load Balancing V2 client object.
    """
```

```
    print("Hello, Elastic Load Balancing! Let's list some of your load
 balancers:")
    load_balancers = elbv2_client.describe_load_balancers(PageSize=10).get(
        "LoadBalancers", []
    )
    if load_balancers:
        for lb in load_balancers:
            print(f"\t{lb['LoadBalancerName']}: {lb['DNSName']}")
    else:
        print("Your account doesn't have any load balancers.")


if __name__ == "__main__":
    hello_elbv2(boto3.client("elbv2"))
```

- Para obter detalhes da API, consulte a DescribeLoadBalancersReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações para o Elastic Load Balancing usando SDKs da AWS
  - Crie um receptor para um balanceador de carga ELB usando um SDK da AWS
  - Crie um grupo de destino do ELB usando um SDK da AWS
  - Crie um Application Load Balancer do ELB usando um SDK da AWS
  - Exclua um balanceador de carga ELB usando um SDK da AWS
  - Exclua um grupo de destino do ELB usando um SDK da AWS
  - Descrever os grupos de destino especificados ou todos os grupos de destino
  - Obtenha o endpoint de um balanceador de carga ELB usando um SDK da AWS
  - Obtenha a integridade de um grupo de destino do ELB usando um SDK da AWS
- Cenários para o Elastic Load Balancing usando SDKs da AWS
  - Criar e gerenciar um serviço resiliente usando um AWS SDK

Ações para o Elastic Load Balancing usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Elastic Load Balancing (ELB) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Elastic Load Balancing usando SDKs da AWS.

Exemplos

- Crie um receptor para um balanceador de carga ELB usando um SDK da AWS
- Crie um grupo de destino do ELB usando um SDK da AWS
- Crie um Application Load Balancer do ELB usando um SDK da AWS
- Exclua um balanceador de carga ELB usando um SDK da AWS
- Exclua um grupo de destino do ELB usando um SDK da AWS
- Descrever os grupos de destino especificados ou todos os grupos de destino
- Obtenha o endpoint de um balanceador de carga ELB usando um SDK da AWS
- Obtenha a integridade de um grupo de destino do ELB usando um SDK da AWS

Crie um receptor para um balanceador de carga ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um receptor que transmite solicitações de um balanceador de carga do ELB para um grupo de destino.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
```

```
   /// and forwards requests to the specified target group.
   /// </summary>
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
           {
               var describeResponse =
                   await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                       new DescribeLoadBalancersRequest()
                       {
                           Names = new List<string>() { name }
                       });

               var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

               loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
           }
           catch (LoadBalancerNotFoundException)
           {
               loadBalancerReady = false;
           }
           Thread.Sleep(10000);
       }
```

```
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar um receptor HTTP

O exemplo de `create-listener` a seguir cria um receptor HTTP para o Application Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado.

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188 \
    --protocol HTTP \
    --port 80 \
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Para obter mais informações, consulte Tutorial: criar um Application Load Balancer usando a AWS CLI no Guia do usuário dos Application Load Balancers.

Exemplo 2: como criar um receptor HTTPS

O exemplo de `create-listener` a seguir cria um receptor HTTPS para o Application Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado. É necessário especificar um certificado SSL para um receptor HTTPS. Você pode criar e gerenciar certificados usando AWS Certificate Manager (ACM). Como alternativa, você pode criar um certificado usando ferramentas SSL/TLS, obter a assinatura de uma autoridade de certificação (CA) e fazer upload do certificado no AWS Identity and Access Management (IAM).

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188 \
    --protocol HTTPS \
    --port 443 \
    --certificates CertificateArn=arn:aws:acm:us-
west-2:123456789012:certificate/3dcb0a41-bd72-4774-9ad9-756919c40557 \
    --ssl-policy ELBSecurityPolicy-2016-08 \
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Para obter mais informações, consulte Adicionar um receptor HTTPS no Guia do usuário de Application Load Balancers.

Exemplo 3: como criar um receptor TCP

O exemplo de `create-listener` a seguir cria um receptor TCP para o Network Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado.

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/net/my-network-load-balancer/5d1b75f4f1cee11e \
    --protocol TCP \
    --port 80 \
```

```
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-tcp-targets/b6bba954d1361c78
```

Para obter mais informações, consulte Tutorial: criar um Network Load Balancer usando a AWS CLI no Guia do usuário dos Network Load Balancers.

Exemplo 4: como criar um receptor TLS

O exemplo de `create-listener` a seguir cria um receptor TLS para o Network Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado. É necessário especificar um certificado SSL para um listener TLS.

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188 \
    --protocol TLS \
    --port 443 \
    --certificates CertificateArn=arn:aws:acm:us-
west-2:123456789012:certificate/3dcb0a41-bd72-4774-9ad9-756919c40557 \
    --ssl-policy ELBSecurityPolicy-2016-08 \
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Para obter mais informações, consulte Listeners TLS para o Network Load Balancer no Guia do usuário dos Network Load Balancers.

Exemplo 5: como criar um receptor UDP

O exemplo de `create-listener` a seguir cria um receptor UDP para o Network Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado.

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/net/my-network-load-balancer/5d1b75f4f1cee11e \
    --protocol UDP \
    --port 53 \
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-tcp-targets/b6bba954d1361c78
```

Para obter mais informações, consulte Tutorial: criar um Network Load Balancer usando a AWS CLI no Guia do usuário dos Network Load Balancers.

Exemplo 6: como criar um receptor para o gateway e encaminhamento especificados

O exemplo de `create-listener` a seguir cria um receptor para o Gateway Load Balancer especificado. Esse receptor encaminha as solicitações para o grupo de destino especificado.

```
aws elbv2 create-listener \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
east-1:850631746142:loadbalancer/gwy/my-gateway-load-balancer/e0f9b3d5c7f7d3d6 \
    --default-actions
 Type=forward,TargetGroupArn=arn:aws:elasticloadbalancing:us-
east-1:850631746142:targetgroup/my-glb-targets/007ca469fae3bb1615
```

Saída:

```
{
    "Listeners": [
        {
            "ListenerArn": "arn:aws:elasticloadbalancing:us-
east-1:850631746142:listener/gwy/my-agw-lb-example2/e0f9b3d5c7f7d3d6/
afc127db15f925de",
            "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
east-1:850631746142:loadbalancer/gwy/my-agw-lb-example2/e0f9b3d5c7f7d3d6",
            "DefaultActions": [
                {
                    "Type": "forward",
                    "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
east-1:850631746142:targetgroup/test-tg-agw-2/007ca469fae3bb1615",
                    "ForwardConfig": {
                        "TargetGroups": [
                            {
                                "TargetGroupArn":
 "arn:aws:elasticloadbalancing:us-east-1:850631746142:targetgroup/test-tg-
agw-2/007ca469fae3bb1615"
                            }
                        ]
                    }
                }
            ]
        }
    ]
```

```
}
```

Para mais informações, consulte Saiba como começar a usar Gateway Load Balancers com a AWS CLI no Guia do usuário para Gateway Load Balancers.

- Para obter detalhes da API, consulte CreateListenerem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /*
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String
targetGroupARN, String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();

           // Create and wait for the load balancer to become available.
           CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
           String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();
```

```
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
```

```
            e.printStackTrace();
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const { Listeners } = await client.send(
  new CreateListenerCommand({
    LoadBalancerArn: state.loadBalancerArn,
    Protocol: state.targetGroupProtocol,
    Port: state.targetGroupPort,
    DefaultActions: [
      { Type: "forward", TargetGroupArn: state.targetGroupArn },
    ],
  }),
);
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
 subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener
 to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
```

```
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer
```

- Para obter detalhes da API, consulte a CreateListenerReferência da API AWSSDK for Python (Boto3).

Crie um grupo de destino do ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um grupo de destino ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened
 times and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</
param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer
 exists.</param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
```

```
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar um grupo de destino para rotear o tráfego para instâncias registradas por ID de instância

O exemplo de `create-target-group` a seguir cria um grupo de destino para um Application Load Balancer no qual você registra destinos por ID de instância (o tipo do destino é `instance`). Esse grupo de destino usa o protocolo HTTP, a porta 80 e as configurações padrão de verificação de integridade de um grupo de destino HTTP.

```
aws elbv2 create-target-group \
    --name my-targets \
    --protocol HTTP \
    --port 80 \
    --target-type instance \
    --vpc-id vpc-3ac0fb5f
```

Saída:

```
{
    "TargetGroups": [
        {
            "TargetGroupName": "my-targets",
```

```
            "Protocol": "HTTP",
            "Port": 80,
            "VpcId": "vpc-3ac0fb5f",
            "TargetType": "instance",
            "HealthCheckEnabled": true,
            "UnhealthyThresholdCount": 2,
            "HealthyThresholdCount": 5,
            "HealthCheckPath": "/",
            "Matcher": {
                "HttpCode": "200"
            },
            "HealthCheckProtocol": "HTTP",
            "HealthCheckPort": "traffic-port",
            "HealthCheckIntervalSeconds": 30,
            "HealthCheckTimeoutSeconds": 5,
            "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067"
        }
    ]
}
```

Para obter mais informações, consulte Criar um grupo de destino no Guia do usuário dos Application Load Balancers.

Exemplo 2: como criar um grupo de destino para rotear o tráfego para um endereço IP

O exemplo de `create-target-group` a seguir cria um grupo de destino para um Network Load Balancer no qual você registra destinos por endereço IP (o tipo do destino é `ip`). Esse grupo de destino usa o protocolo TCP, a porta 80 e as configurações padrão de verificação de integridade de um grupo de destino TCP.

```
aws elbv2 create-target-group \
    --name my-ip-targets \
    --protocol TCP \
    --port 80 \
    --target-type ip \
    --vpc-id vpc-3ac0fb5f
```

Saída:

```
{
    "TargetGroups": [
```

```
        {
            "TargetGroupName": "my-ip-targets",
            "Protocol": "TCP",
            "Port": 80,
            "VpcId": "vpc-3ac0fb5f",
            "TargetType": "ip",
            "HealthCheckEnabled": true,
            "UnhealthyThresholdCount": 3,
            "HealthyThresholdCount": 3,
            "HealthCheckProtocol": "TCP",
            "HealthCheckPort": "traffic-port",
            "HealthCheckIntervalSeconds": 30,
            "HealthCheckTimeoutSeconds": 10,
            "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-ip-targets/b6bba954d1361c78"
        }
    ]
}
```

Para obter mais informações, consulte Criar um grupo de destino para o Network Load Balancer no Guia do usuário dos Network Load Balancers.

Exemplo 3: como criar um grupo de destino para rotear o tráfego para uma função do Lambda

O exemplo de `create-target-group` a seguir cria um grupo de destino para um Application Load Balancer, no qual o destino é uma função do Lambda (o tipo do destino é `lambda`). Por padrão, as verificações de integridade estão desabilitadas para esse grupo de destino.

```
aws elbv2 create-target-group \
    --name my-lambda-target \
    --target-type lambda
```

Saída:

```
{
    "TargetGroups": [
        {
            "TargetGroupName": "my-lambda-target",
            "TargetType": "lambda",
            "HealthCheckEnabled": false,
            "UnhealthyThresholdCount": 2,
```

```
            "HealthyThresholdCount": 5,
            "HealthCheckPath": "/",
            "Matcher": {
                "HttpCode": "200"
            },
            "HealthCheckIntervalSeconds": 35,
            "HealthCheckTimeoutSeconds": 30,
            "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-lambda-target/a3003e085dbb8ddc"
        }
    ]
}
```

Para obter mais informações, consulte Lambda functions as targets no Guia do usuário de Application Load Balancers.

Exemplo 4: como criar um grupo de destino para rotear o tráfego para um Gateway Load Balancer

O exemplo de `create-target-group` a seguir cria um grupo destino para um Gateway Load Balancer, no qual o destino é uma instância e o protocolo do grupo de destino é GENEVE.

```
aws elbv2 create-target-group \
    --name my-glb-targetgroup \
    --protocol GENEVE \
    --port 6081 \
    --target-type instance \
    --vpc-id vpc-838475fe
```

Saída:

```
{
    "TargetGroups": [
        {
            "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-glb-targetgroup/00c3d57eacd6f40b6f",
            "TargetGroupName": "my-glb-targetgroup",
            "Protocol": "GENEVE",
            "Port": 6081,
            "VpcId": "vpc-838475fe",
            "HealthCheckProtocol": "TCP",
```

```
            "HealthCheckPort": "80",
            "HealthCheckEnabled": true,
            "HealthCheckIntervalSeconds": 10,
            "HealthCheckTimeoutSeconds": 5,
            "HealthyThresholdCount": 5,
            "UnhealthyThresholdCount": 2,
            "TargetType": "instance"
        }
    ]
}
```

Para obter mais informações, consulte Criar um grupo de destino para seu Gateway Load Balancer no Guia do usuário dos Gateway Load Balancers.

- Para obter detalhes da API, consulte CreateTargetGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /*
    * Creates an Elastic Load Balancing target group. The target group specifies
    * how
    * the load balancer forward requests to instances in the group and how
instance
    * health is checked.
    */
   public String createTargetGroup(String protocol, int port, String vpcId,
String targetGroupName) {
       CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
               .healthCheckPath("/healthcheck")
               .healthCheckTimeoutSeconds(5)
               .port(port)
```

```
                .vpcId(vpcId)
                .name(targetGroupName)
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
```

```
        VpcId: state.defaultVpc,
      }),
    );
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group
 specifies how
        the load balancer forward requests to instances in the group and how
 instance
        health is checked.
```

```
        To speed up this demo, the health check is configured with shortened
times and
        lower thresholds. In production, you might want to decrease the
sensitivity of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group
```

- Para obter detalhes da API, consulte a CreateTargetGroupReferência da API AWSSDK for Python (Boto3).

Crie um Application Load Balancer do ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um Application Load Balancer do ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
   /// and forwards requests to the specified target group.
   /// </summary>
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
```

```
            {
                var describeResponse =
                    await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar um balanceador de carga voltado para a internet

O exemplo de `create-load-balancer` a seguir cria um Application Load Balancer voltado para a internet e habilita as zonas de disponibilidade para as sub-redes especificadas.

```
aws elbv2 create-load-balancer \
    --name my-load-balancer \
    --subnets subnet-b7d581c0 subnet-8360a9e7
```

Saída:

```
{
    "LoadBalancers": [
        {
            "Type": "application",
            "Scheme": "internet-facing",
            "IpAddressType": "ipv4",
            "VpcId": "vpc-3ac0fb5f",
            "AvailabilityZones": [
                {
                    "ZoneName": "us-west-2a",
                    "SubnetId": "subnet-8360a9e7"
                },
                {
                    "ZoneName": "us-west-2b",
                    "SubnetId": "subnet-b7d581c0"
                }
            ],
            "CreatedTime": "2017-08-25T21:26:12.920Z",
            "CanonicalHostedZoneId": "Z2P70J7EXAMPLE",
            "DNSName": "my-load-balancer-424835706.us-west-2.elb.amazonaws.com",
            "SecurityGroups": [
                "sg-5943793c"
            ],
            "LoadBalancerName": "my-load-balancer",
            "State": {
                "Code": "provisioning"
            },
```

```
            "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188"
        }
    ]
}
```

Para obter mais informações, consulte Tutorial: criar um Application Load Balancer usando a AWS CLI no Guia do usuário dos Application Load Balancers.

Exemplo 2: como criar um balanceador de carga interno

O exemplo de `create-load-balancer` a seguir cria um Application Load Balancer interno e habilita as zonas de disponibilidade para as sub-redes especificadas.

```
aws elbv2 create-load-balancer \
    --name my-internal-load-balancer \
    --scheme internal \
    --subnets subnet-b7d581c0 subnet-8360a9e7
```

Saída:

```
{
    "LoadBalancers": [
        {
            "Type": "application",
            "Scheme": "internal",
            "IpAddressType": "ipv4",
            "VpcId": "vpc-3ac0fb5f",
            "AvailabilityZones": [
                {
                    "ZoneName": "us-west-2a",
                    "SubnetId": "subnet-8360a9e7"
                },
                {
                    "ZoneName": "us-west-2b",
                    "SubnetId": "subnet-b7d581c0"
                }
            ],
            "CreatedTime": "2016-03-25T21:29:48.850Z",
            "CanonicalHostedZoneId": "Z2P70J7EXAMPLE",
            "DNSName": "internal-my-internal-load-balancer-1529930873.us-
west-2.elb.amazonaws.com",
            "SecurityGroups": [
```

```
                "sg-5943793c"
            ],
            "LoadBalancerName": "my-internal-load-balancer",
            "State": {
                "Code": "provisioning"
            },
            "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-internal-load-balancer/5b49b8d4303115c2"
        }
    ]
}
```

Para obter mais informações, consulte Tutorial: criar um Application Load Balancer usando a AWS CLI no Guia do usuário dos Application Load Balancers.

Exemplo 3: como criar um Network Load Balancer

O exemplo de `create-load-balancer` a seguir cria um Network Load Balancer voltado para a internet e habilita a zona de disponibilidade para as sub-redes especificadas. Ele usa o mapeamento de sub-redes para associar o endereço IP do Elastic específico à interface de rede usada pelos nós do balanceador de carga da zona de disponibilidade.

```
aws elbv2 create-load-balancer \
    --name my-network-load-balancer \
    --type network \
    --subnet-mappings SubnetId=subnet-b7d581c0,AllocationId=eipalloc-64d5890a
```

Saída:

```
{
    "LoadBalancers": [
        {
            "Type": "network",
            "Scheme": "internet-facing",
            "IpAddressType": "ipv4",
            "VpcId": "vpc-3ac0fb5f",
            "AvailabilityZones": [
                {
                    "LoadBalancerAddresses": [
                        {
                            "IpAddress": "35.161.207.171",
                            "AllocationId": "eipalloc-64d5890a"
```

```
                        }
                    ],
                    "ZoneName": "us-west-2b",
                    "SubnetId": "subnet-5264e837"
                }
            ],
            "CreatedTime": "2017-10-15T22:41:25.657Z",
            "CanonicalHostedZoneId": "Z2P70J7EXAMPLE",
            "DNSName": "my-network-load-balancer-5d1b75f4f1cee11e.elb.us-
west-2.amazonaws.com",
            "LoadBalancerName": "my-network-load-balancer",
            "State": {
                "Code": "provisioning"
            },
            "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/net/my-network-load-balancer/5d1b75f4f1cee11e"
        }
    ]
}
```

Para obter mais informações, consulte Tutorial: criar um Network Load Balancer usando a AWS CLI no Guia do usuário dos Network Load Balancers.

Exemplo 4: como criar um Gateway Load Balancer

O exemplo de `create-load-balancer` a seguir cria um Gateway Load Balancer e habilita as zonas de disponibilidade para as sub-redes especificadas.

```
aws elbv2 create-load-balancer \
    --name my-gateway-load-balancer \
    --type gateway \
    --subnets subnet-dc83f691 subnet-a62583f9
```

Saída:

```
{
    "LoadBalancers": [
        {
            "Type": "gateway",
            "VpcId": "vpc-838475fe",
            "AvailabilityZones": [
                {
                    "ZoneName": "us-east-1b",
```

```
                    "SubnetId": "subnet-a62583f9"
                },
            {
                    "ZoneName": "us-east-1a",
                    "SubnetId": "subnet-dc83f691"
                }
            ],
            "CreatedTime": "2021-07-14T19:33:43.324000+00:00",
            "LoadBalancerName": "my-gateway-load-balancer",
            "State": {
                "Code": "provisioning"
            },
            "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
east-1:850631746142:loadbalancer/gwy/my-gateway-load-balancer/dfbb5a7d32cdee79"
        }
    ]
}
```

Para mais informações, consulte Saiba como começar a usar Gateway Load Balancers com a AWS CLI no Guia do usuário para Gateway Load Balancers.

- Para obter detalhes da API, consulte CreateLoadBalancerem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
    public String createLoadBalancer(List<Subnet> subnetIds, String
 targetGroupARN, String lbName, int port,
            String protocol) {
```

```
        try {
            List<String> subnetIdStrings = subnetIds.stream()
                    .map(Subnet::subnetId)
                    .collect(Collectors.toList());

            CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                    .subnets(subnetIdStrings)
                    .name(lbName)
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
CreateListenerRequest.builder()
```

```
.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                   .defaultActions(action)
                   .port(port)
                   .protocol(protocol)
                   .defaultActions(action)
                   .build();

           getLoadBalancerClient().createListener(listenerRequest);
           System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                   + targetGroupARN);

           // Return the load balancer DNS name.
           return lbDNSName;

       } catch (ElasticLoadBalancingV2Exception e) {
           e.printStackTrace();
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   const client = new ElasticLoadBalancingV2Client({});
   const { LoadBalancers } = await client.send(
     new CreateLoadBalancerCommand({
       Name: NAMES.loadBalancerName,
       Subnets: state.subnets,
```

```
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_load_balancer(self, subnet_ids, target_group):
        """
```

```
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener
to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
```

```
            self._endpoint = load_balancer["DNSName"]
            return load_balancer
```

- Para obter detalhes da API, consulte a CreateLoadBalancerReferência da API AWSSDK for Python (Boto3).

Exclua um balanceador de carga ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um balanceador de carga do ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
```

```
                        Names = new List<string>() { name }
                    });
            var lbArn =
 describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um balanceador de carga

O exemplo `delete-load-balancer` a seguir exclui o balanceador de carga especificado.

```
aws elbv2 delete-load-balancer \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
```

- Para obter detalhes da API, consulte DeleteLoadBalancerem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Deletes a load balancer.
   public void deleteLoadBalancer(String lbName) {
       try {
           // Use a waiter to delete the Load Balancer.
           DescribeLoadBalancersResponse res = getLoadBalancerClient()
                   .describeLoadBalancers(describe -> describe.names(lbName));
           ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
           DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()

.loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                   .build();

           getLoadBalancerClient().deleteLoadBalancer(
                   builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
           WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                   .waitUntilLoadBalancersDeleted(request);
           waiterResponse.matched().response().ifPresent(System.out::println);

       } catch (ElasticLoadBalancingV2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
       }
       System.out.println(lbName + " was deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
await client.send(
  new DeleteLoadBalancerCommand({
    LoadBalancerArn: loadBalancer.LoadBalancerArn,
  }),
);
await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
  const lb = await findLoadBalancer(NAMES.loadBalancerName);
  if (lb) {
    throw new Error("Load balancer still exists.");
  }
});
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""
```

```
    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )
```

- Para obter detalhes da API, consulte a DeleteLoadBalancerReferência da API AWSSDK for Python (Boto3).

Exclua um grupo de destino do ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um grupo de destino do ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await
_amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
```

```
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn =
 targetArn });
                Console.WriteLine($"Deleted load balancing target group
 {groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um grupo de destino

O exemplo de `delete-target-group` a seguir exclui o grupo de destino especificado.

```
aws elbv2 delete-target-group \
    --target-group-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

- Para obter detalhes da API, consulte DeleteTargetGroupem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const client = new ElasticLoadBalancingV2Client({});
```

```
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
```

```
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to
do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )
```

- Para obter detalhes da API, consulte a DeleteTargetGroupReferência da API AWSSDK for Python (Boto3).

Descrever os grupos de destino especificados ou todos os grupos de destino

Os exemplos de código a seguir mostram como descrever grupos de destino específicos.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

CLI

AWS CLI

Exemplo 1: como descrever um grupo de destino

O exemplo de `describe-target-groups` a seguir exibe os detalhes do grupo de destino especificado.

```
aws elbv2 describe-target-groups \
    --target-group-arns arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Saída:

```
{
    "TargetGroups": [
        {
            "TargetGroupName": "my-targets",
            "Protocol": "HTTP",
            "Port": 80,
            "VpcId": "vpc-3ac0fb5f",
            "TargetType": "instance",
            "HealthCheckEnabled": true,
            "UnhealthyThresholdCount": 2,
            "HealthyThresholdCount": 5,
```

```
            "HealthCheckPath": "/",
            "Matcher": {
                "HttpCode": "200"
            },
            "HealthCheckProtocol": "HTTP",
            "HealthCheckPort": "traffic-port",
            "HealthCheckIntervalSeconds": 30,
            "HealthCheckTimeoutSeconds": 5,
            "TargetGroupArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067",
            "LoadBalancerArns": [
                "arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188"
            ]
        }
    ]
}
```

Exemplo 2: como descrever todos os grupos de destino de um balanceador de carga

O exemplo de `describe-target-groups` a seguir exibe os detalhes de todos os grupos de destino do balanceador de carga especificado.

```
aws elbv2 describe-target-groups \
    --load-balancer-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
```

Exemplo 3: como descrever todos os grupos de destino

O exemplo de `describe-target-groups` a seguir exibe detalhes de todos os grupos de destino.

```
aws elbv2 describe-target-groups
```

- Para obter detalhes da API, consulte DescribeTargetGroupsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const { TargetGroups } = await client.send(
  new DescribeTargetGroupsCommand({
    Names: [NAMES.loadBalancerTargetGroupName],
  }),
);
```

- Para obter detalhes da API, consulte DescribeTargetGroupsa Referência AWS SDK for JavaScript da API.

Obtenha o endpoint de um balanceador de carga ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como obter um endpoint de um balanceador de carga do ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como descrever um balanceador de carga

Este exemplo descreve o balanceador de carga especificado.

Comando:

```
aws elbv2 describe-load-balancers --load-balancer-arns
 arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-
balancer/50dc6c495c0c9188
```

Saída:

```
{
  "LoadBalancers": [
      {
          "Type": "application",
          "Scheme": "internet-facing",
          "IpAddressType": "ipv4",
          "VpcId": "vpc-3ac0fb5f",
          "AvailabilityZones": [
              {
                  "ZoneName": "us-west-2a",
                  "SubnetId": "subnet-8360a9e7"
              },
              {
                  "ZoneName": "us-west-2b",
                  "SubnetId": "subnet-b7d581c0"
              }
          ],
          "CreatedTime": "2016-03-25T21:26:12.920Z",
          "CanonicalHostedZoneId": "Z2P70J7EXAMPLE",
          "DNSName": "my-load-balancer-424835706.us-west-2.elb.amazonaws.com",
          "SecurityGroups": [
              "sg-5943793c"
          ],
          "LoadBalancerName": "my-load-balancer",
          "State": {
              "Code": "active"
          },
          "LoadBalancerArn": "arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188"
      }
  ]
}
```

Como descrever todos os balanceadores de carga

Este exemplo descreve todos os balanceadores de carga.

Comando:

```
aws elbv2 describe-load-balancers
```

- Para obter detalhes da API, consulte DescribeLoadBalancersem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  ElasticLoadBalancingV2Client,
  DescribeLoadBalancersCommand,
} from "@aws-sdk/client-elastic-load-balancing-v2";

export async function main() {
  const client = new ElasticLoadBalancingV2Client({});
  const { LoadBalancers } = await client.send(
    new DescribeLoadBalancersCommand({}),
  );
  const loadBalancersList = LoadBalancers.map(
    (lb) => `• ${lb.LoadBalancerName}: ${lb.DNSName}`,
  ).join("\n");
  console.log(
    "Hello, Elastic Load Balancing! Let's list some of your load balancers:\n",
    loadBalancersList,
  );
}

// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  main();
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
 {self.load_balancer_name}: {err}"
```

```
                )
        return self._endpoint
```

- Para obter detalhes da API, consulte a DescribeLoadBalancersReferência da API AWSSDK for Python (Boto3).

Obtenha a integridade de um grupo de destino do ELB usando um SDK da AWS

Os exemplos de código a seguir mostram como obter a integridade de instâncias em um grupo de destino do ELB.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
```

```
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }
```

- Para obter detalhes da API, consulte DescribeTargetHealtha Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como descrever a integridade dos destinos de um grupo de destino

O exemplo de `describe-target-health` a seguir exibe os detalhes de integridade dos destinos do grupo de destino especificado. Os destinos estão íntegros.

```
aws elbv2 describe-target-health \
    --target-group-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Saída:

```
{
```

```
    "TargetHealthDescriptions": [
        {
            "HealthCheckPort": "80",
            "Target": {
                "Id": "i-ceddcd4d",
                "Port": 80
            },
            "TargetHealth": {
                "State": "healthy"
            }
        },
        {
            "HealthCheckPort": "80",
            "Target": {
                "Id": "i-0f76fade",
                "Port": 80
            },
            "TargetHealth": {
                "State": "healthy"
            }
        }
    ]
}
```

Exemplo 2: como descrever a integridade de um destino

O exemplo de `describe-target-health` a seguir exibe os detalhes de integridade do destino especificado. Este destino é íntegro.

```
aws elbv2 describe-target-health \
    --targets Id=i-0f76fade,Port=80 \
    --target-group-arn arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
```

Saída:

```
{
    "TargetHealthDescriptions": [
        {
            "HealthCheckPort": "80",
            "Target": {
                "Id": "i-0f76fade",
                "Port": 80
```

```
            },
            "TargetHealth": {
                "State": "healthy"
            }
        }
    ]
}
```

O exemplo de saída a seguir é de um destino cujo grupo de destino não está especificado em uma ação de um receptor. Esse destino não pode receber tráfego do balanceador de carga.

```
{
    "TargetHealthDescriptions": [
    {
        "HealthCheckPort": "80",
        "Target": {
            "Id": "i-0f76fade",
            "Port": 80
        },
            "TargetHealth": {
                "State": "unused",
                "Reason": "Target.NotInUse",
                "Description": "Target group is not configured to receive traffic
 from the load balancer"
            }
        }
    ]
}
```

O exemplo de saída a seguir é de um destino cujo grupo de destino foi especificado em uma ação de um receptor. O destino ainda está sendo registrado.

```
{
    "TargetHealthDescriptions": [
        {
            "HealthCheckPort": "80",
            "Target": {
                "Id": "i-0f76fade",
                "Port": 80
            },
            "TargetHealth": {
                "State": "initial",
```

```
                "Reason": "Elb.RegistrationInProgress",
                "Description": "Target registration is in progress"
            }
        }
    ]
}
```

O exemplo de saída a seguir é de um destino não íntegro.

```
{
    "TargetHealthDescriptions": [
        {
            "HealthCheckPort": "80",
            "Target": {
                "Id": "i-0f76fade",
                "Port": 80
            },
            "TargetHealth": {
                "State": "unhealthy",
                "Reason": "Target.Timeout",
                "Description": "Connection to target timed out"
            }
        }
    ]
}
```

O exemplo de saída a seguir é de um destino que é uma função do Lambda e com verificações de integridade desabilitadas.

```
{
    "TargetHealthDescriptions": [
        {
            "Target": {
                "Id": "arn:aws:lambda:us-west-2:123456789012:function:my-
function",
                "AvailabilityZone": "all",
            },
            "TargetHealth": {
                "State": "unavailable",
                "Reason": "Target.HealthCheckDisabled",
                "Description": "Health checks are not enabled for this target"
            }
        }
```

```
    ]
}
```

- Para obter detalhes da API, consulte DescribeTargetHealthem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Checks the health of the instances in the target group.
   public List<TargetHealthDescription> checkTargetHealth(String
targetGroupName) {
       DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
               .names(targetGroupName)
               .build();

       DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

       DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()

.targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
               .build();

       DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
       return healthResponse.targetHealthDescriptions();
   }
```

- Para obter detalhes da API, consulte DescribeTargetHeltha Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const { TargetHealthDescriptions } = await client.send(
  new DescribeTargetHealthCommand({
    TargetGroupArn: TargetGroups[0].TargetGroupArn,
  }),
);
```

- Para obter detalhes da API, consulte DescribeTargetHealtha Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
```

```
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets:
{err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

- Para obter detalhes da API, consulte a DescribeTargetHealthReferência da API AWSSDK for Python (Boto3).

Cenários para o Elastic Load Balancing usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Elastic Load Balancing (ELB) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar e gerenciar um serviço resiliente usando um AWS SDK

Criar e gerenciar um serviço resiliente usando um AWS SDK

Os exemplos de código a seguir mostram como criar um serviço da Web com carga balanceada que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
static async Task Main(string[] args)
{
    _configuration = new ConfigurationBuilder()
        .SetBasePath(Directory.GetCurrentDirectory())
        .AddJsonFile("settings.json") // Load settings from .json file.
```

```
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
```

```
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper =
host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }
```

```
    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several
AWS resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server.");
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
```

```
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs
'server_startup_script.sh' when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the
`server.py` script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and
Systems Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3,
_autoScalerWrapper.GroupName, zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
```

```
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or
continue with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the
demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
_autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
        var targetGroup = await
_elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGro
protocol, port, defaultVpc.VpcId);

        await
_elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.Lo
subnetIds, targetGroup);
        await
_autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
_elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper
        var loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
```

```
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port,
 ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for
 your default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management
 Console.\n");

                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound traffic from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port,
 ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound SSH traffic for debugging from your computer's IP address?"))
                {
```

```
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
ipString);
                }
            }
            loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite
of these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service
fails, the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
"static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a static response.");
```

```
        Console.WriteLine("The service still reports as healthy because health
checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
_smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile
that contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();
```

```
        Console.WriteLine("\nLet's implement a deep health check. For this demo,
a deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not
for Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the
Auto Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load
balancer can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two
for the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by
an auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler
start a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a
successful recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the
load balancing rotation.");
```

```
        Console.WriteLine("Note that terminating and replacing an instance
typically takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
checks mean all instances report as unhealthy.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n" +
            "that were created for this demo."
        );
```

```
        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBal
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGr
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupNa
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you
might incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
```

```
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
```

```
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with
 a specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
 granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to
 the role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
                                         "\"Effect\": \"Allow\"," +
                                         "\"Principal\": {" +
                                         "\"Service\": [" +
                                             "\"ec2.amazonaws.com\"" +
                                         "]" +
```

```
                                        "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                                    "}]" +
                                "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
```

```
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await
_amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
```

```
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
```

```
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
 Scaling.
    /// The launch template specifies a Bash script in its user data field that
 runs after
    /// the instance is started. This script installs the Python packages and
 starts a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
 run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to
 create and attach to the profile.</param>
    /// <returns>The template object.</returns>
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
 startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName,
 _instanceRoleName, _instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
```

```
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new

 LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2
 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
```

```
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new
Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with
size {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
```

```
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
 List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
```

```
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the
role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await
_amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
```

```
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
 name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
 _amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
 instanceId)
    {
        var response = await
 _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
```

```
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);
```

```
            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await
_amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
```

```
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for
{instanceId}. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running.
Waiting...");
                Thread.Sleep(10000);
```

```
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string
groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
```

```
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the
 calling computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
 instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP
 address while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
 ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
```

```
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be
open to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0),
or to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
```

```
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName,
 string targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
```

```
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }
```

```
        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
```

```
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened
 times and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</
param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer
 exists.</param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
```

```
   /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
   /// and forwards requests to the specified target group.
   /// </summary>
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
           {
               var describeResponse =
                   await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                       new DescribeLoadBalancersRequest()
                       {
                           Names = new List<string>() { name }
                       });

               var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

               loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
           }
           catch (LoadBalancerNotFoundException)
           {
               loadBalancerReady = false;
           }
```

```
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
```

```
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
  describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }
```

```
    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await
 _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn =
 targetArn });
                Console.WriteLine($"Deleted load balancing target group
 {groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books,
 movies, and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
```

```
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
```

```
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await
 File.ReadAllTextAsync(recommendationsPath);
        var records =

 JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }
```

```
    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement
 _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-
architecture-table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";
```

```
    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-
prof-bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;
```

```
   public static final String DASHES = new String(new char[80]).replace("\0",
"-");

   public static void main(String[] args) throws IOException,
InterruptedException {
       Scanner in = new Scanner(System.in);
       Database database = new Database();
       AutoScaler autoScaler = new AutoScaler();
       LoadBalancer loadBalancer = new LoadBalancer();

       System.out.println(DASHES);
       System.out.println("Welcome to the demonstration of How to Build and
Manage a Resilient Service!");
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("A - SETUP THE RESOURCES");
       System.out.println("Press Enter when you're ready to start deploying
resources.");
       in.nextLine();
       deploy(loadBalancer);
       System.out.println(DASHES);
       System.out.println(DASHES);
       System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       demo(loadBalancer);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("C - DELETE THE RESOURCES");
       System.out.println("""
               This concludes the demo of how to build and manage a resilient
service.
               To keep things tidy and to avoid unwanted charges on your
account, we can clean up all AWS resources
               that were created for this demo.
               """);

       System.out.println("\n Do you want to delete the resources (y/n)? ");
       String userInput = in.nextLine().trim().toLowerCase(); // Capture user
input

       if (userInput.equals("y")) {
```

```
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }

    private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
        Scanner in = new Scanner(System.in);
        System.out.println(
                """
                        For this demo, we'll use the AWS SDK for Java (v2) to
create several AWS resources
                        to set up a load-balanced web service endpoint and
explore some ways to make it resilient
                        against various kinds of failures.

                        Some of the resources create by this demo are:
```

```
                        \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                        \t* An EC2 launch template that defines EC2 instances
that each contain a Python web server.
                        \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                        \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                        """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
               run a web server, such as Apache, with least-privileged
credentials.

               The template also defines an IAM policy that each instance uses
to assume a role that grants
               permissions to access the DynamoDB recommendation table and
Systems Manager parameters
               that control the flow of the demo.
               """);

       LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
       templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the
demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load
balancer. The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
```

```
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets,
targetGroupArn, lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul =
loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(),
StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group
for your default VPC must
                            allow access from this computer. You can either add
it automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
```

```
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security
group are configured correctly and that");
            System.out.println("you can successfully make a GET request to the
load balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
```

```
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and
shows how using a resilient
                        architecture can keep the web service running in spite
of these failures.

                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager
parameter named self.param_helper.table.
                        To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.
                       """);
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       System.out.println(
               """
                        \nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                       Instead of failing when the recommendation service fails,
the web service can return a static response.
                       While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                       """);
       paramHelper.put(paramHelper.failureResponse, "static");

       System.out.println("""
               Now, sending a GET request to the load balancer endpoint returns
a static response.
```

```
                The service still reports as healthy because health checks are
still shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance
id value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId =
autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " +
profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);
```

```
        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on
for recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto
Scaling instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the
load balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an
auto scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start
a new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
```

```
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load
balancing rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance
is running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);

        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
```

```
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode =
response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load
balancer targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
```

```
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
 target.target().id(),
                                    target.target().port(),
 target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the
 health check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value
 between 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;
```

```
    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance
is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
```

```
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile
is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure
'newInstanceProfileName' is a valid IAM Instance Profile
                                              // name.
                .build();

        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();

        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
```

```
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with
 profile %s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
 waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
 getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
 informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
```

```
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
               .build();

       getSSMClient().sendCommand(sendCommandRequest);
       System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
   }

   public void openInboundPort(String secGroupId, String port, String ipAddress)
{
       AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
               .groupName(secGroupId)
               .cidrIp(ipAddress)
               .fromPort(Integer.parseInt(port))
               .build();

       getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
       System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
   }

   /**
    * Detaches a role from an instance profile, detaches policies from the role,
    * and deletes all the resources.
    */
   public void deleteInstanceProfile(String roleName, String profileName) {
       try {
           software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                   .builder()
                   .instanceProfileName(profileName)
                   .build();

           GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
           String name = response.instanceProfile().instanceProfileName();
           System.out.println(name);

           RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                   .instanceProfileName(profileName)
```

```
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request =
DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
```

```
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network,
you
     * must instead specify a prefix list ID. You can also temporarily open the
port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();
```

```
            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse =
getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup :
securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " +
secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " +
ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to
be open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                        } else {
                            break;
```

```
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
```

```
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
               .builder()
               .build();

       DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
       List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
               .collect(Collectors.toList());

       String availabilityZones = String.join(",", availabilityZoneNames);
       LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
               .launchTemplateName(templateName)
               .version("$Default")
               .build();

       String[] zones = availabilityZones.split(",");
       CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
               .launchTemplate(specification)
               .availabilityZones(zones)
               .maxSize(groupSize)
               .minSize(groupSize)
               .autoScalingGroupName(autoScalingGroupName)
               .build();

       try {
           getAutoScalingClient().createAutoScalingGroup(groupRequest);

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
       return zones;
   }
```

```
    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability
Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response =
getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
```

```
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
InstanceProfile) {
```

```
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to
 the policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM
 role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
 DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }
```

```
        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
 ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
 iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
 listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
 RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance
 profile " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
 DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
```

```
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String
targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()

.targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
```

```
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()

.loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load
balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws
IOException, InterruptedException {
        boolean success = false;
        int retries = 3;
```

```
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how
instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId,
String targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
```

```
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }

    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
    public String createLoadBalancer(List<Subnet> subnetIds, String
targetGroupARN, String lbName, int port,
            String protocol) {
        try {
            List<String> subnetIdStrings = subnetIds.stream()
                    .map(Subnet::subnetId)
                    .collect(Collectors.toList());

            CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                    .subnets(subnetIdStrings)
                    .name(lbName)
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
```

```
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
 become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
 loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
 CreateListenerRequest.builder()

 .loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " +
 e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended,
 such
```

```
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException
{
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
```

```
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");

            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws
IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable =
enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);
```

```
            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-
response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
```

```
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
```

```
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
```

```
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
```

```
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item']
[] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
```

```
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
```

```
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
```

```
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
```

```
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
```

```
        LaunchTemplate: {
          LaunchTemplateName: NAMES.launchTemplateName,
          Version: "$Default",
        },
        MinSize: 3,
        MaxSize: 3,
      }),
    ),
  );
}),
new ScenarioOutput(
  "createdAutoScalingGroup",
  /**
   * @param {{ availabilityZoneNames: string[] }} state
   */
  (state) =>
    MESSAGES.createdAutoScalingGroup
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
      .replace(
        "${AVAILABILITY_ZONE_NAMES}",
        state.availabilityZoneNames.join(", "),
      ),
),
new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
  type: "confirm",
}),
new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
new ScenarioAction("getVpc", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
  const client = new EC2Client({});
  const { Vpcs } = await client.send(
    new DescribeVpcsCommand({
      Filters: [{ Name: "is-default", Values: ["true"] }],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
  state.defaultVpc = Vpcs[0].VpcId;
}),
new ScenarioOutput("gotVpc", (state) =>
  MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
),
new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
new ScenarioAction("getSubnets", async (state) => {
```

```
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
```

```
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
```

```
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
```

```
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup}} state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
```

```
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
```

```
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
```

```
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
```

```
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
```

```
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
```

```
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
```

```
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
```

```
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-
scaling').Instance }} state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
```

```
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation}} state
     */
    (state) =>
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
```

```
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
```

```
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
```

```
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
```

```
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";
```

```
import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
```

```
    new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
    new ScenarioAction(
      "abort",
      (state) => state.destroy === false && process.exit(),
    ),
    new ScenarioAction("deleteTable", async (c) => {
      try {
        const client = new DynamoDBClient({});
        await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
      } catch (e) {
        c.deleteTableError = e;
      }
    }),
    new ScenarioOutput("deleteTableResult", (state) => {
      if (state.deleteTableError) {
        console.error(state.deleteTableError);
        return MESSAGES.deleteTableError.replace(
          "${TABLE_NAME}",
          NAMES.tableName,
        );
      } else {
        return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
      }
    }),
    new ScenarioAction("deleteKeyPair", async (state) => {
      try {
        const client = new EC2Client({});
        await client.send(
          new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
        );
        unlinkSync(`${NAMES.keyPairName}.pem`);
      } catch (e) {
        state.deleteKeyPairError = e;
      }
    }),
    new ScenarioOutput("deleteKeyPairResult", (state) => {
      if (state.deleteKeyPairError) {
        console.error(state.deleteKeyPairError);
        return MESSAGES.deleteKeyPairError.replace(
          "${KEY_PAIR_NAME}",
          NAMES.keyPairName,
        );
      } else {
        return MESSAGES.deletedKeyPair.replace(
```

```
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
```

```
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
```

```
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
```

```
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
```

```
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
```

```
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
```

```
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
```

```
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
```

```
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
```

```
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
      return policy;
    }
  }
}
```

```
/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
        }),
      ),
    );
  }
```

```
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers

- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"
```

```
        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server."
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
'{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
```

```
            f"For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged
credentials.\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
            f"Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or
continue with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load
balancer provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
```

```
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port
 is open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for
 your default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.
\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
```

```
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging
 from your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
                "Couldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                "manually verifying that your VPC and security group are
 configured correctly and that\n"
                "you can successfully make a GET request to the load balancer
 endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
 following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
```

```
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health
check to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts
of the system\n"
            "to create situations where the web service fails, and shows how
using a resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)
```

```
        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations
by querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't
check for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with
a somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns
a static response.\n"
            f"The service still reports as healthy because health checks are
still shallow.\n"
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
```

```
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a
profile that contains\n"
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto
Scaling instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.\n"
        )
        print(
```

```
            "By implementing deep health checks, the load balancer can detect
when one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
            "\nBecause the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
starting, sending a GET\n"
            "request to the web service continues to get a successful
recommendation response because\n"
            "the load balancer routes requests to the healthy instances. After
the replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
running and healthy.\n"
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean
all instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
```

```
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient
 service.\n"
            "To keep things tidy and to avoid unwanted charges on your account,
 we can clean up all AWS resources\n"
            "that were created for this demo."
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ",
 q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you
 might incur unexpected charges."
            )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
```

```
        help="The action to take for the demo. When 'all' is specified, resources
are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM
policies and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
Service!"
    )
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer,
param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
"destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)
```

```
if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
```

```
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are
created by this class.
        """
        as_client = boto3.client("autoscaling")
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is
assumed by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.
```

```
        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as
AmazonSSMManagedInstanceCore to grant
                                     use of Systems Manager to send commands to
the instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
```

```
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
```

```
                    "Instance profile %s already exists, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to
role\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response =
self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.
```

```
        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
instance_id)
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the
role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )
```

```
    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.

        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.",
self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
```

```
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling. The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts
a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a
permissions policy
                                     to create and attach to the instance
profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
```

```
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template
{self.launch_template_name}: {err}."
                )
        return template


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
```

```
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template
{self.launch_template_name}: {err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones


    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
```

```
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group
{self.group_name}: {err}"
            )
```

```
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance
is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group
%s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] ==
"ScalingActivityInProgress"
                ):
```

```
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling
 group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
```

```
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress
from this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
```

```
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to
either this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
```

```
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port}
from {ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""
```

```
    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by
this class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint
```

```
    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group
specifies how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened
times and
        lower thresholds. In production, you might want to decrease the
sensitivity of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
```

```
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to
do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
```

```
        :param target_group: An existing target group that is added as a listener
to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
```

```
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
```

```
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint,
 retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets:
 {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books,
 movies,
    and songs.
    """
```

```
    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended,
such as
        Book or Movie, and a range key named 'ItemId' that, combined with the
MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5,
"WriteCapacityUnits": 5},
            )
            log.info("Creating table %s...", self.table_name)
```

```
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name,
data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}:
{err}"
            )

    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
```

```
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.",
 self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters
 to drive
    the demonstration of resilient architecture, such as failure of a dependency
 or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)
```

```
    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when
a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup

- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Exemplos de código para MediaStore usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Elemental MediaStore com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- MediaStore Guia do usuário — Mais informações sobre MediaStore.
- MediaStore Referência da API — Detalhes sobre todas as MediaStore ações disponíveis.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para MediaStore usar AWS SDKs
  - Criar um contêiner do AWS Elemental MediaStore usando um SDK da AWS
  - Excluir um contêiner do AWS Elemental MediaStore usando um SDK da AWS
  - Excluir um objeto do AWS Elemental MediaStore usando um SDK da AWS
  - Descrever um contêiner do AWS Elemental MediaStore usando um SDK da AWS
  - Obter um objeto do AWS Elemental MediaStore usando um SDK da AWS
  - Listar contêineres do AWS Elemental MediaStore usando um SDK da AWS
  - Colocar um objeto do AWS Elemental MediaStore em um contêiner usando um SDK da AWS

Ações para MediaStore usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Elemental MediaStore com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Criar um contêiner do AWS Elemental MediaStore usando um SDK da AWS
- Excluir um contêiner do AWS Elemental MediaStore usando um SDK da AWS
- Excluir um objeto do AWS Elemental MediaStore usando um SDK da AWS
- Descrever um contêiner do AWS Elemental MediaStore usando um SDK da AWS
- Obter um objeto do AWS Elemental MediaStore usando um SDK da AWS
- Listar contêineres do AWS Elemental MediaStore usando um SDK da AWS
- Colocar um objeto do AWS Elemental MediaStore em um contêiner usando um SDK da AWS

Criar um contêiner do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como criar um contêiner do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.model.CreateContainerRequest;
import software.amazon.awssdk.services.mediastore.model.CreateContainerResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateContainer {
    public static long sleepTime = 10;

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        createMediaContainer(mediaStoreClient, containerName);
        mediaStoreClient.close();
    }

    public static void createMediaContainer(MediaStoreClient mediaStoreClient,
 String containerName) {
        try {
            CreateContainerRequest containerRequest =
 CreateContainerRequest.builder()
                    .containerName(containerName)
                    .build();

            CreateContainerResponse containerResponse =
 mediaStoreClient.createContainer(containerRequest);
            String status = containerResponse.container().status().toString();
            while (!status.equalsIgnoreCase("Active")) {
                status = DescribeContainer.checkContainer(mediaStoreClient,
 containerName);
                System.out.println("Status - " + status);
                Thread.sleep(sleepTime * 1000);
            }

            System.out.println("The container ARN value is " +
 containerResponse.container().arn());
            System.out.println("Finished ");

        } catch (MediaStoreException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateContainera Referência AWS SDK for Java 2.x da API.

Excluir um contêiner do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um contêiner do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.model.CreateContainerRequest;
import software.amazon.awssdk.services.mediastore.model.CreateContainerResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateContainer {
    public static long sleepTime = 10;

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to create.
                """;

        if (args.length != 1) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        createMediaContainer(mediaStoreClient, containerName);
        mediaStoreClient.close();
    }

    public static void createMediaContainer(MediaStoreClient mediaStoreClient,
 String containerName) {
        try {
            CreateContainerRequest containerRequest =
 CreateContainerRequest.builder()
                    .containerName(containerName)
                    .build();

            CreateContainerResponse containerResponse =
 mediaStoreClient.createContainer(containerRequest);
            String status = containerResponse.container().status().toString();
            while (!status.equalsIgnoreCase("Active")) {
                status = DescribeContainer.checkContainer(mediaStoreClient,
 containerName);
                System.out.println("Status - " + status);
                Thread.sleep(sleepTime * 1000);
            }

            System.out.println("The container ARN value is " +
 containerResponse.container().arn());
            System.out.println("Finished ");

        } catch (MediaStoreException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteContainera Referência AWS SDK for Java 2.x da API.

Excluir um objeto do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um objeto do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import
 software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.services.mediastoredata.model.DeleteObjectRequest;
import
 software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteObject {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """
```

```
                Usage:    <completePath> <containerName>

                Where:
                   completePath - The path (including the container) of the item
to delete.
                   containerName - The name of the container.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String completePath = args[0];
        String containerName = args[1];
        Region region = Region.US_EAST_1;
        URI uri = new URI(getEndpoint(containerName));

        MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
                .endpointOverride(uri)
                .region(region)
                .build();

        deleteMediaObject(mediaStoreData, completePath);
        mediaStoreData.close();
    }

    public static void deleteMediaObject(MediaStoreDataClient mediaStoreData,
String completePath) {
        try {
            DeleteObjectRequest deleteObjectRequest =
DeleteObjectRequest.builder()
                    .path(completePath)
                    .build();

            mediaStoreData.deleteObject(deleteObjectRequest);

        } catch (MediaStoreDataException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    private static String getEndpoint(String containerName) {
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        DescribeContainerRequest containerRequest =
 DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
 mediaStoreClient.describeContainer(containerRequest);
        mediaStoreClient.close();
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for Java 2.x da API.

Descrever um contêiner do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um contêiner do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import
 software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
```

```
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeContainer {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to describe.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        System.out.println("Status is " + checkContainer(mediaStoreClient,
 containerName));
        mediaStoreClient.close();
    }

    public static String checkContainer(MediaStoreClient mediaStoreClient, String
 containerName) {
        try {
            DescribeContainerRequest describeContainerRequest =
 DescribeContainerRequest.builder()
                    .containerName(containerName)
```

```
                    .build();

            DescribeContainerResponse containerResponse =
 mediaStoreClient.describeContainer(describeContainerRequest);
            System.out.println("The container name is " +
 containerResponse.container().name());
            System.out.println("The container ARN is " +
 containerResponse.container().arn());
            return containerResponse.container().status().toString();

        } catch (MediaStoreException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte DescribeContainera Referência AWS SDK for Java 2.x da API.

Obter um objeto do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como obter um objeto do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.ResponseInputStream;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
```

```
import
 software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.services.mediastoredata.model.GetObjectRequest;
import software.amazon.awssdk.services.mediastoredata.model.GetObjectResponse;
import
 software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetObject {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """

                Usage:    <completePath> <containerName> <savePath>

                Where:
                   completePath - The path of the object in the container (for
 example, Videos5/sampleVideo.mp4).
                   containerName - The name of the container.
                   savePath - The path on the local drive where the file is
 saved, including the file name (for example, C:/AWS/myvid.mp4).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String completePath = args[0];
        String containerName = args[1];
```

```
        String savePath = args[2];

        Region region = Region.US_EAST_1;
        URI uri = new URI(getEndpoint(containerName));
        MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
                .endpointOverride(uri)
                .region(region)
                .build();

        getMediaObject(mediaStoreData, completePath, savePath);
        mediaStoreData.close();
    }

    public static void getMediaObject(MediaStoreDataClient mediaStoreData, String
 completePath, String savePath) {

        try {
            GetObjectRequest objectRequest = GetObjectRequest.builder()
                    .path(completePath)
                    .build();

            // Write out the data to a file.
            ResponseInputStream<GetObjectResponse> data =
 mediaStoreData.getObject(objectRequest);
            byte[] buffer = new byte[data.available()];
            data.read(buffer);

            File targetFile = new File(savePath);
            OutputStream outStream = new FileOutputStream(targetFile);
            outStream.write(buffer);
            System.out.println("The data was written to " + savePath);

        } catch (MediaStoreDataException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    private static String getEndpoint(String containerName) {
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();
```

```
        DescribeContainerRequest containerRequest =
 DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
 mediaStoreClient.describeContainer(containerRequest);
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Java 2.x da API.

Listar contêineres do AWS Elemental MediaStore usando um SDK da AWS

O exemplo de código a seguir mostra como listar contêineres do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.Container;
import software.amazon.awssdk.services.mediastore.model.ListContainersResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListContainers {

    public static void main(String[] args) {

        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        listAllContainers(mediaStoreClient);
        mediaStoreClient.close();
    }

    public static void listAllContainers(MediaStoreClient mediaStoreClient) {
        try {
            ListContainersResponse containersResponse =
 mediaStoreClient.listContainers();
            List<Container> containers = containersResponse.containers();
            for (Container container : containers) {
                System.out.println("Container name is " + container.name());
            }

        } catch (MediaStoreException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListContainersa Referência AWS SDK for Java 2.x da API.

Colocar um objeto do AWS Elemental MediaStore em um contêiner usando um SDK da AWS

O exemplo de código a seguir mostra como colocar um objeto em um contêiner do AWS Elemental MediaStore.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.mediastoredata.model.PutObjectRequest;
import
 software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import software.amazon.awssdk.services.mediastoredata.model.PutObjectResponse;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import
 software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import java.io.File;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutObject {
    public static void main(String[] args) throws URISyntaxException {
        final String USAGE = """

                To run this example, supply the name of a container, a file
 location to use, and path in the container\s

                Ex: <containerName> <filePath> <completePath>
```

```
                """;

        if (args.length < 3) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String containerName = args[0];
        String filePath = args[1];
        String completePath = args[2];

        Region region = Region.US_EAST_1;
        URI uri = new URI(getEndpoint(containerName));
        MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
                .endpointOverride(uri)
                .region(region)
                .build();

        putMediaObject(mediaStoreData, filePath, completePath);
        mediaStoreData.close();
    }

    public static void putMediaObject(MediaStoreDataClient mediaStoreData, String
filePath, String completePath) {
        try {
            File myFile = new File(filePath);
            RequestBody requestBody = RequestBody.fromFile(myFile);

            PutObjectRequest objectRequest = PutObjectRequest.builder()
                    .path(completePath)
                    .contentType("video/mp4")
                    .build();

            PutObjectResponse response = mediaStoreData.putObject(objectRequest,
requestBody);
            System.out.println("The saved object is " +
response.storageClass().toString());

        } catch (MediaStoreDataException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static String getEndpoint(String containerName) {

        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        DescribeContainerRequest containerRequest =
 DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
 mediaStoreClient.describeContainer(containerRequest);
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Java 2.x da API.

Exemplos de código para o Amazon EMR usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EMR com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia de gerenciamento do Amazon EMR – Mais informações sobre o Amazon EMR.
- Referência da API do Amazon EMR – Detalhes sobre todas as ações disponíveis do Amazon EMR.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.

- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon EMR usando SDKs da AWS
  - Adicione etapas a um fluxo de trabalho do Amazon EMR usando um SDK da AWS
  - Descreva um cluster do Amazon EMR usando um SDK da AWS
  - Descreva uma etapa em um cluster do Amazon EMR usando um SDK da AWS
  - Liste etapas para um cluster do Amazon EMR usando um SDK da AWS
  - Execute um fluxo de trabalho do Amazon EMR usando um SDK da AWS
  - Encerre fluxos de trabalho do Amazon EMR usando um SDK da AWS
- Cenários do Amazon EMR com SDKs da AWS
  - Criar um cluster do Amazon EMR de curta duração e executar uma etapa usando um AWS SDK
  - Execute um script shell para instalar bibliotecas em instâncias do Amazon EMR usando um SDK da AWS

Ações para o Amazon EMR usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EMR com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon EMR com SDKs da AWS.

Exemplos

- Adicione etapas a um fluxo de trabalho do Amazon EMR usando um SDK da AWS
- Descreva um cluster do Amazon EMR usando um SDK da AWS
- Descreva uma etapa em um cluster do Amazon EMR usando um SDK da AWS
- Liste etapas para um cluster do Amazon EMR usando um SDK da AWS
- Execute um fluxo de trabalho do Amazon EMR usando um SDK da AWS
- Encerre fluxos de trabalho do Amazon EMR usando um SDK da AWS

Adicione etapas a um fluxo de trabalho do Amazon EMR usando um SDK da AWS

O exemplo de código a seguir mostra como adicionar etapas a fluxo de trabalho do Amazon EMR.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicionar uma etapa do Spark, que é executada pelo cluster assim que é adicionada.

```
def add_step(cluster_id, name, script_uri, script_args, emr_client):
    """
    Adds a job step to the specified cluster. This example adds a Spark
    step, which is run by the cluster as soon as it is added.

    :param cluster_id: The ID of the cluster.
    :param name: The name of the step.
    :param script_uri: The URI where the Python script is stored.
    :param script_args: Arguments to pass to the Python script.
    :param emr_client: The Boto3 EMR client object.
    :return: The ID of the newly added step.
    """
    try:
        response = emr_client.add_job_flow_steps(
            JobFlowId=cluster_id,
            Steps=[
                {
                    "Name": name,
                    "ActionOnFailure": "CONTINUE",
                    "HadoopJarStep": {
                        "Jar": "command-runner.jar",
                        "Args": [
                            "spark-submit",
                            "--deploy-mode",
                            "cluster",
                            script_uri,
```

```
                            *script_args,
                        ],
                    },
                }
            ],
        )
        step_id = response["StepIds"][0]
        logger.info("Started step with ID %s", step_id)
    except ClientError:
        logger.exception("Couldn't start step %s with URI %s.", name, script_uri)
        raise
    else:
        return step_id
```

Executar um comando do Amazon EMR File System (EMRFS) como uma etapa de trabalho em um cluster. Isso pode ser usado para automatizar comandos do EMRFS em um cluster em vez de executar comandos manualmente por meio de uma conexão SSH.

```
import boto3
from botocore.exceptions import ClientError


def add_emrfs_step(command, bucket_url, cluster_id, emr_client):
    """
    Add an EMRFS command as a job flow step to an existing cluster.

    :param command: The EMRFS command to run.
    :param bucket_url: The URL of a bucket that contains tracking metadata.
    :param cluster_id: The ID of the cluster to update.
    :param emr_client: The Boto3 Amazon EMR client object.
    :return: The ID of the added job flow step. Status can be tracked by calling
             the emr_client.describe_step() function.
    """
    job_flow_step = {
        "Name": "Example EMRFS Command Step",
        "ActionOnFailure": "CONTINUE",
        "HadoopJarStep": {
            "Jar": "command-runner.jar",
            "Args": ["/usr/bin/emrfs", command, bucket_url],
        },
```

```
    }

    try:
        response = emr_client.add_job_flow_steps(
            JobFlowId=cluster_id, Steps=[job_flow_step]
        )
        step_id = response["StepIds"][0]
        print(f"Added step {step_id} to cluster {cluster_id}.")
    except ClientError:
        print(f"Couldn't add a step to cluster {cluster_id}.")
        raise
    else:
        return step_id


def usage_demo():
    emr_client = boto3.client("emr")
    # Assumes the first waiting cluster has EMRFS enabled and has created
 metadata
    # with the default name of 'EmrFSMetadata'.
    cluster = emr_client.list_clusters(ClusterStates=["WAITING"])["Clusters"][0]
    add_emrfs_step(
        "sync", "s3://elasticmapreduce/samples/cloudfront", cluster["Id"],
 emr_client
    )


if __name__ == "__main__":
    usage_demo()
```

- Para obter detalhes da API, consulte a AddJobFlowStepsReferência da API AWSSDK for Python (Boto3).

Descreva um cluster do Amazon EMR usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um cluster do Amazon EMR.

CLI

AWS CLI

Comando:

```
aws emr describe-cluster --cluster-id j-XXXXXXXX
```

Saída:

```
For release-label based uniform instance groups cluster:

        {
            "Cluster": {
                "Status": {
                    "Timeline": {
                        "ReadyDateTime": 1436475075.199,
                        "CreationDateTime": 1436474656.563,
                    },
                    "State": "WAITING",
                    "StateChangeReason": {
                        "Message": "Waiting for steps to run"
                    }
                },
                "Ec2InstanceAttributes": {
                    "ServiceAccessSecurityGroup": "sg-xxxxxxxx",
                    "EmrManagedMasterSecurityGroup": "sg-xxxxxxxx",
                    "IamInstanceProfile": "EMR_EC2_DefaultRole",
                    "Ec2KeyName": "myKey",
                    "Ec2AvailabilityZone": "us-east-1c",
                    "EmrManagedSlaveSecurityGroup": "sg-yyyyyyyyy"
                },
                "Name": "My Cluster",
                "ServiceRole": "EMR_DefaultRole",
                "Tags": [],
                "TerminationProtected": true,
                "ReleaseLabel": "emr-4.0.0",
                "NormalizedInstanceHours": 96,
                "InstanceGroups": [
                    {
                        "RequestedInstanceCount": 2,
                        "Status": {
                            "Timeline": {
                                "ReadyDateTime": 1436475074.245,
                                "CreationDateTime": 1436474656.564,
                                "EndDateTime": 1436638158.387
                            },
                            "State": "RUNNING",
                            "StateChangeReason": {
```

```
                                "Message": "",
                            }
                        },
                        "Name": "CORE",
                        "InstanceGroupType": "CORE",
                        "Id": "ig-YYYYYYY",
                        "Configurations": [],
                        "InstanceType": "m3.large",
                        "Market": "ON_DEMAND",
                        "RunningInstanceCount": 2
                    },
                    {
                        "RequestedInstanceCount": 1,
                        "Status": {
                            "Timeline": {
                                "ReadyDateTime": 1436475074.245,
                                "CreationDateTime": 1436474656.564,
                                "EndDateTime": 1436638158.387
                            },
                            "State": "RUNNING",
                            "StateChangeReason": {
                                "Message": "",
                            }
                        },
                        "Name": "MASTER",
                        "InstanceGroupType": "MASTER",
                        "Id": "ig-XXXXXXXXX",
                        "Configurations": [],
                        "InstanceType": "m3.large",
                        "Market": "ON_DEMAND",
                        "RunningInstanceCount": 1
                    }
                ],
                "Applications": [
                    {
                        "Name": "Hadoop"
                    }
                ],
                "VisibleToAllUsers": true,
                "BootstrapActions": [],
                "MasterPublicDnsName":
 "ec2-54-147-144-78.compute-1.amazonaws.com",
                "AutoTerminate": false,
                "Id": "j-XXXXXXXX",
```

```
                "Configurations": [
                    {
                        "Properties": {
                            "fs.s3.consistent.retryPeriodSeconds": "20",
                            "fs.s3.enableServerSideEncryption": "true",
                            "fs.s3.consistent": "false",
                            "fs.s3.consistent.retryCount": "2"
                        },
                        "Classification": "emrfs-site"
                    }
                ]
            }
        }


For release-label based instance fleet cluster:
{
    "Cluster": {
        "Status": {
            "Timeline": {
                "ReadyDateTime": 1487897289.705,
                "CreationDateTime": 1487896933.942
            },
            "State": "WAITING",
            "StateChangeReason": {
                "Message": "Waiting for steps to run"
            }
        },
        "Ec2InstanceAttributes": {
            "EmrManagedMasterSecurityGroup": "sg-xxxxx",
            "RequestedEc2AvailabilityZones": [],
            "RequestedEc2SubnetIds": [],
            "IamInstanceProfile": "EMR_EC2_DefaultRole",
            "Ec2AvailabilityZone": "us-east-1a",
            "EmrManagedSlaveSecurityGroup": "sg-xxxxx"
        },
        "Name": "My Cluster",
        "ServiceRole": "EMR_DefaultRole",
        "Tags": [],
        "TerminationProtected": false,
        "ReleaseLabel": "emr-5.2.0",
        "NormalizedInstanceHours": 472,
        "InstanceCollectionType": "INSTANCE_FLEET",
        "InstanceFleets": [
```

```
            {
                "Status": {
                    "Timeline": {
                        "ReadyDateTime": 1487897212.74,
                        "CreationDateTime": 1487896933.948
                    },
                    "State": "RUNNING",
                    "StateChangeReason": {
                        "Message": ""
                    }
                },
                "ProvisionedSpotCapacity": 1,
                "Name": "MASTER",
                "InstanceFleetType": "MASTER",
                "LaunchSpecifications": {
                    "SpotSpecification": {
                        "TimeoutDurationMinutes": 60,
                        "TimeoutAction": "TERMINATE_CLUSTER"
                    }
                },
                "TargetSpotCapacity": 1,
                "ProvisionedOnDemandCapacity": 0,
                "InstanceTypeSpecifications": [
                    {
                        "BidPrice": "0.5",
                        "InstanceType": "m3.xlarge",
                        "WeightedCapacity": 1
                    }
                ],
                "Id": "if-xxxxxxx",
                "TargetOnDemandCapacity": 0
            }
        ],
        "Applications": [
            {
                "Version": "2.7.3",
                "Name": "Hadoop"
            }
        ],
        "ScaleDownBehavior": "TERMINATE_AT_INSTANCE_HOUR",
        "VisibleToAllUsers": true,
        "BootstrapActions": [],
        "MasterPublicDnsName": "ec2-xxx-xx-xxx-xx.compute-1.amazonaws.com",
        "AutoTerminate": false,
```

```
        "Id": "j-xxxxx",
        "Configurations": []
    }
}

For ami based uniform instance group cluster:

    {
        "Cluster": {
            "Status": {
                "Timeline": {
                    "ReadyDateTime": 1399400564.432,
                    "CreationDateTime": 1399400268.62
                },
                "State": "WAITING",
                "StateChangeReason": {
                    "Message": "Waiting for steps to run"
                }
            },
            "Ec2InstanceAttributes": {
                "IamInstanceProfile": "EMR_EC2_DefaultRole",
                "Ec2AvailabilityZone": "us-east-1c"
            },
            "Name": "My Cluster",
            "Tags": [],
            "TerminationProtected": true,
            "RunningAmiVersion": "2.5.4",
            "InstanceGroups": [
                {
                    "RequestedInstanceCount": 1,
                    "Status": {
                        "Timeline": {
                            "ReadyDateTime": 1399400558.848,
                            "CreationDateTime": 1399400268.621
                        },
                        "State": "RUNNING",
                        "StateChangeReason": {
                            "Message": ""
                        }
                    },
                    "Name": "Master instance group",
                    "InstanceGroupType": "MASTER",
                    "InstanceType": "m1.small",
                    "Id": "ig-ABCD",
```

```
                    "Market": "ON_DEMAND",
                    "RunningInstanceCount": 1
                },
                {
                    "RequestedInstanceCount": 2,
                    "Status": {
                        "Timeline": {
                            "ReadyDateTime": 1399400564.439,
                            "CreationDateTime": 1399400268.621
                        },
                        "State": "RUNNING",
                        "StateChangeReason": {
                            "Message": ""
                        }
                    },
                    "Name": "Core instance group",
                    "InstanceGroupType": "CORE",
                    "InstanceType": "m1.small",
                    "Id": "ig-DEF",
                    "Market": "ON_DEMAND",
                    "RunningInstanceCount": 2
                }
            ],
            "Applications": [
                {
                    "Version": "1.0.3",
                    "Name": "hadoop"
                }
            ],
            "BootstrapActions": [],
            "VisibleToAllUsers": false,
            "RequestedAmiVersion": "2.4.2",
            "LogUri": "s3://myLogUri/",
            "AutoTerminate": false,
            "Id": "j-XXXXXXXX"
        }
    }
```

- Para obter detalhes da API, consulte DescribeClusterem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_cluster(cluster_id, emr_client):
    """
    Gets detailed information about a cluster.

    :param cluster_id: The ID of the cluster to describe.
    :param emr_client: The Boto3 EMR client object.
    :return: The retrieved cluster information.
    """
    try:
        response = emr_client.describe_cluster(ClusterId=cluster_id)
        cluster = response["Cluster"]
        logger.info("Got data for cluster %s.", cluster["Name"])
    except ClientError:
        logger.exception("Couldn't get data for cluster %s.", cluster_id)
        raise
    else:
        return cluster
```

- Para obter detalhes da API, consulte a DescribeClusterReferência da API AWSSDK for Python (Boto3).

Descreva uma etapa em um cluster do Amazon EMR usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma etapa em um cluster do Amazon EMR.

CLI

AWS CLI

O seguinte comando descreve uma etapa com o ID de etapa `s-3LZC0QUT43AM` em um cluster com o ID de cluster `j-3SD91U2E1L2QX`:

```
aws emr describe-step --cluster-id j-3SD91U2E1L2QX --step-id s-3LZC0QUT43AM
```

Saída:

```
{
    "Step": {
        "Status": {
            "Timeline": {
                "EndDateTime": 1433200470.481,
                "CreationDateTime": 1433199926.597,
                "StartDateTime": 1433200404.959
            },
            "State": "COMPLETED",
            "StateChangeReason": {}
        },
        "Config": {
            "Args": [
                "s3://us-west-2.elasticmapreduce/libs/hive/hive-script",
                "--base-path",
                "s3://us-west-2.elasticmapreduce/libs/hive/",
                "--install-hive",
                "--hive-versions",
                "0.13.1"
            ],
            "Jar": "s3://us-west-2.elasticmapreduce/libs/script-runner/script-
runner.jar",
            "Properties": {}
        },
        "Id": "s-3LZC0QUT43AM",
        "ActionOnFailure": "TERMINATE_CLUSTER",
        "Name": "Setup hive"
    }
}
```

- Para obter detalhes da API, consulte DescribeStepem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_step(cluster_id, step_id, emr_client):
    """
    Gets detailed information about the specified step, including the current
 state of
    the step.

    :param cluster_id: The ID of the cluster.
    :param step_id: The ID of the step.
    :param emr_client: The Boto3 EMR client object.
    :return: The retrieved information about the specified step.
    """
    try:
        response = emr_client.describe_step(ClusterId=cluster_id, StepId=step_id)
        step = response["Step"]
        logger.info("Got data for step %s.", step_id)
    except ClientError:
        logger.exception("Couldn't get data for step %s.", step_id)
        raise
    else:
        return step
```

- Para obter detalhes da API, consulte a DescribeStepReferência da API AWSSDK for Python (Boto3).

Liste etapas para um cluster do Amazon EMR usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever etapas de um cluster do Amazon EMR.

CLI

AWS CLI

O seguinte comando lista todas as etapas em um cluster com o ID de cluster `j-3SD91U2E1L2QX`:

```
aws emr list-steps --cluster-id j-3SD91U2E1L2QX
```

- Para obter detalhes da API, consulte ListStepsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_steps(cluster_id, emr_client):
    """
    Gets a list of steps for the specified cluster. In this example, all steps
 are
    returned, including completed and failed steps.

    :param cluster_id: The ID of the cluster.
    :param emr_client: The Boto3 EMR client object.
    :return: The list of steps for the specified cluster.
    """
    try:
        response = emr_client.list_steps(ClusterId=cluster_id)
        steps = response["Steps"]
        logger.info("Got %s steps for cluster %s.", len(steps), cluster_id)
    except ClientError:
        logger.exception("Couldn't get steps for cluster %s.", cluster_id)
        raise
    else:
        return steps
```

- Para obter detalhes da API, consulte a ListStepsReferência da API AWSSDK for Python (Boto3).

Execute um fluxo de trabalho do Amazon EMR usando um SDK da AWS

O exemplo de código a seguir mostra como executar um fluxo de trabalho do Amazon EMR.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def run_job_flow(
    name,
    log_uri,
    keep_alive,
    applications,
    job_flow_role,
    service_role,
    security_groups,
    steps,
    emr_client,
):
    """
    Runs a job flow with the specified steps. A job flow creates a cluster of
    instances and adds steps to be run on the cluster. Steps added to the cluster
    are run as soon as the cluster is ready.

    This example uses the 'emr-5.30.1' release. A list of recent releases can be
    found here:
        https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-release-
components.html.
```

```
    :param name: The name of the cluster.
    :param log_uri: The URI where logs are stored. This can be an Amazon S3
bucket URL,
                    such as 's3://my-log-bucket'.
    :param keep_alive: When True, the cluster is put into a Waiting state after
all
                       steps are run. When False, the cluster terminates itself
when
                       the step queue is empty.
    :param applications: The applications to install on each instance in the
cluster,
                         such as Hive or Spark.
    :param job_flow_role: The IAM role assumed by the cluster.
    :param service_role: The IAM role assumed by the service.
    :param security_groups: The security groups to assign to the cluster
instances.
                            Amazon EMR adds all needed rules to these groups, so
                            they can be empty if you require only the default
rules.
    :param steps: The job flow steps to add to the cluster. These are run in
order
                  when the cluster is ready.
    :param emr_client: The Boto3 EMR client object.
    :return: The ID of the newly created cluster.
    """
    try:
        response = emr_client.run_job_flow(
            Name=name,
            LogUri=log_uri,
            ReleaseLabel="emr-5.30.1",
            Instances={
                "MasterInstanceType": "m5.xlarge",
                "SlaveInstanceType": "m5.xlarge",
                "InstanceCount": 3,
                "KeepJobFlowAliveWhenNoSteps": keep_alive,
                "EmrManagedMasterSecurityGroup": security_groups["manager"].id,
                "EmrManagedSlaveSecurityGroup": security_groups["worker"].id,
            },
            Steps=[
                {
                    "Name": step["name"],
                    "ActionOnFailure": "CONTINUE",
                    "HadoopJarStep": {
                        "Jar": "command-runner.jar",
```

```
                        "Args": [
                            "spark-submit",
                            "--deploy-mode",
                            "cluster",
                            step["script_uri"],
                            *step["script_args"],
                        ],
                    },
                }
                for step in steps
            ],
            Applications=[{"Name": app} for app in applications],
            JobFlowRole=job_flow_role.name,
            ServiceRole=service_role.name,
            EbsRootVolumeSize=10,
            VisibleToAllUsers=True,
        )
        cluster_id = response["JobFlowId"]
        logger.info("Created cluster %s.", cluster_id)
    except ClientError:
        logger.exception("Couldn't create cluster.")
        raise
    else:
        return cluster_id
```

- Para obter detalhes da API, consulte a RunJobFlowReferência da API AWSSDK for Python (Boto3).

Encerre fluxos de trabalho do Amazon EMR usando um SDK da AWS

O exemplo de código a seguir mostra como encerrar fluxos de trabalho do Amazon EMR.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def terminate_cluster(cluster_id, emr_client):
    """
    Terminates a cluster. This terminates all instances in the cluster and cannot
    be undone. Any data not saved elsewhere, such as in an Amazon S3 bucket, is
 lost.

    :param cluster_id: The ID of the cluster to terminate.
    :param emr_client: The Boto3 EMR client object.
    """
    try:
        emr_client.terminate_job_flows(JobFlowIds=[cluster_id])
        logger.info("Terminated cluster %s.", cluster_id)
    except ClientError:
        logger.exception("Couldn't terminate cluster %s.", cluster_id)
        raise
```

- Para obter detalhes da API, consulte a TerminateJobFlowsReferência da API AWSSDK for Python (Boto3).

Cenários do Amazon EMR com SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon EMR com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar um cluster do Amazon EMR de curta duração e executar uma etapa usando um AWS SDK
- Execute um script shell para instalar bibliotecas em instâncias do Amazon EMR usando um SDK da AWS

Criar um cluster do Amazon EMR de curta duração e executar uma etapa usando um AWS SDK

O exemplo de código a seguir mostra como criar um cluster do Amazon EMR de curta duração que executa uma etapa e termina automaticamente após a conclusão dessa etapa.

Python

SDK para Python (Boto3)

Crie um cluster do Amazon EMR de curta duração que estime o valor de pi usando o Apache Spark para paralelizar um grande número de cálculos. O trabalho grava a saída em logs do Amazon EMR e em um bucket do Amazon Simple Storage Service (Amazon S3). O cluster é encerrado automaticamente após a conclusão do trabalho.

- Crie um bucket do Amazon S3 e carregue um script de trabalho.
- Crie perfis do AWS Identity and Access Management (IAM).
- Crie grupos de segurança do Amazon Elastic Compute Cloud (Amazon EC2).
- Criar um cluster de curta duração e executar uma única etapa do trabalho.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon EMR

Execute um script shell para instalar bibliotecas em instâncias do Amazon EMR usando um SDK da AWS

O exemplo de código a seguir mostra como usar o AWS Systems Manager para executar um script shell em instâncias do Amazon EMR que instalam bibliotecas adicionais. Dessa forma, é possível automatizar o gerenciamento de instâncias em vez de executar comandos manualmente por meio de uma conexão SSH.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import argparse
import time
import boto3


def install_libraries_on_core_nodes(cluster_id, script_path, emr_client,
 ssm_client):
    """
    Copies and runs a shell script on the core nodes in the cluster.

    :param cluster_id: The ID of the cluster.
    :param script_path: The path to the script, typically an Amazon S3 object
 URL.
    :param emr_client: The Boto3 Amazon EMR client.
    :param ssm_client: The Boto3 AWS Systems Manager client.
    """
    core_nodes = emr_client.list_instances(
        ClusterId=cluster_id, InstanceGroupTypes=["CORE"]
    )["Instances"]
    core_instance_ids = [node["Ec2InstanceId"] for node in core_nodes]
    print(f"Found core instances: {core_instance_ids}.")

    commands = [
        # Copy the shell script from Amazon S3 to each node instance.
        f"aws s3 cp {script_path} /home/hadoop",
        # Run the shell script to install libraries on each node instance.
        "bash /home/hadoop/install_libraries.sh",
    ]
    for command in commands:
        print(f"Sending '{command}' to core instances...")
        command_id = ssm_client.send_command(
            InstanceIds=core_instance_ids,
```

```
            DocumentName="AWS-RunShellScript",
            Parameters={"commands": [command]},
            TimeoutSeconds=3600,
        )["Command"]["CommandId"]
        while True:
            # Verify the previous step succeeded before running the next step.
            cmd_result = ssm_client.list_commands(CommandId=command_id)
["Commands"][0]
            if cmd_result["StatusDetails"] == "Success":
                print(f"Command succeeded.")
                break
            elif cmd_result["StatusDetails"] in ["Pending", "InProgress"]:
                print(f"Command status is {cmd_result['StatusDetails']},
 waiting...")
                time.sleep(10)
            else:
                print(f"Command status is {cmd_result['StatusDetails']},
 quitting.")
                raise RuntimeError(
                    f"Command {command} failed to run. "
                    f"Details: {cmd_result['StatusDetails']}"
                )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument("cluster_id", help="The ID of the cluster.")
    parser.add_argument("script_path", help="The path to the script in Amazon
 S3.")
    args = parser.parse_args()

    emr_client = boto3.client("emr")
    ssm_client = boto3.client("ssm")

    install_libraries_on_core_nodes(
        args.cluster_id, args.script_path, emr_client, ssm_client
    )


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a ListInstancesReferência da API AWSSDK for Python (Boto3).

Exemplos de código para OpenSearch serviço usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon OpenSearch Service com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- OpenSearch Guia do usuário do serviço — Mais informações sobre o OpenSearch serviço.
- OpenSearch Referência da API de serviço — detalhes sobre todas as ações OpenSearch de serviço disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o OpenSearch serviço usando AWS SDKs
  - Crie um domínio OpenSearch de serviço usando um AWS SDK
  - Excluir um domínio de OpenSearch serviço usando um AWS SDK
  - Listar domínios de OpenSearch serviço usando um SDK AWS
  - Modificar uma configuração de cluster do domínio OpenSearch de serviço especificado usando um AWS SDK

Ações para o OpenSearch serviço usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon OpenSearch Service com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um domínio OpenSearch de serviço usando um AWS SDK
- Excluir um domínio de OpenSearch serviço usando um AWS SDK
- Listar domínios de OpenSearch serviço usando um SDK AWS
- Modificar uma configuração de cluster do domínio OpenSearch de serviço especificado usando um AWS SDK

Crie um domínio OpenSearch de serviço usando um AWS SDK

Os exemplos de código a seguir mostram como criar um domínio OpenSearch de serviço.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.ClusterConfig;
import software.amazon.awssdk.services.opensearch.model.EBSOptions;
import software.amazon.awssdk.services.opensearch.model.VolumeType;
import
 software.amazon.awssdk.services.opensearch.model.NodeToNodeEncryptionOptions;
import software.amazon.awssdk.services.opensearch.model.CreateDomainRequest;
import software.amazon.awssdk.services.opensearch.model.CreateDomainResponse;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class CreateDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
                    domainName - The name of the domain to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        createNewDomain(searchClient, domainName);
        System.out.println("Done");
    }

    public static void createNewDomain(OpenSearchClient searchClient, String
 domainName) {
        try {
            ClusterConfig clusterConfig = ClusterConfig.builder()
                    .dedicatedMasterEnabled(true)
                    .dedicatedMasterCount(3)
                    .dedicatedMasterType("t2.small.search")
                    .instanceType("t2.small.search")
                    .instanceCount(5)
                    .build();

            EBSOptions ebsOptions = EBSOptions.builder()
                    .ebsEnabled(true)
                    .volumeSize(10)
                    .volumeType(VolumeType.GP2)
                    .build();
```

```
            NodeToNodeEncryptionOptions encryptionOptions =
 NodeToNodeEncryptionOptions.builder()
                    .enabled(true)
                    .build();

            CreateDomainRequest domainRequest = CreateDomainRequest.builder()
                    .domainName(domainName)
                    .engineVersion("OpenSearch_1.0")
                    .clusterConfig(clusterConfig)
                    .ebsOptions(ebsOptions)
                    .nodeToNodeEncryptionOptions(encryptionOptions)
                    .build();

            System.out.println("Sending domain creation request...");
            CreateDomainResponse createResponse =
 searchClient.createDomain(domainRequest);
            System.out.println("Domain status is " +
 createResponse.domainStatus().toString());
            System.out.println("Domain Id is " +
 createResponse.domainStatus().domainId());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateDomaina Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewDomain(domainNameVal: String?) {

    val clusterConfigOb = ClusterConfig {
        dedicatedMasterEnabled = true
        dedicatedMasterCount = 3
        dedicatedMasterType =
 OpenSearchPartitionInstanceType.fromValue("t2.small.search")
        instanceType =
 OpenSearchPartitionInstanceType.fromValue("t2.small.search")
        instanceCount = 5
    }

    val ebsOptionsOb = EbsOptions {
        ebsEnabled = true
        volumeSize = 10
        volumeType = VolumeType.Gp2
    }

    val encryptionOptionsOb = NodeToNodeEncryptionOptions {
        enabled = true
    }

    val request = CreateDomainRequest {
        domainName = domainNameVal
        engineVersion = "OpenSearch_1.0"
        clusterConfig = clusterConfigOb
        ebsOptions = ebsOptionsOb
        nodeToNodeEncryptionOptions = encryptionOptionsOb
    }

    println("Sending domain creation request...")
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val createResponse = searchClient.createDomain(request)
        println("Domain status is ${createResponse.domainStatus}")
        println("Domain Id is ${createResponse.domainStatus?.domainId}")
    }
}
```

- Para obter detalhes da API, consulte a CreateDomainreferência da API AWSSDK for Kotlin.

Excluir um domínio de OpenSearch serviço usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um domínio OpenSearch de serviço.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;
import software.amazon.awssdk.services.opensearch.model.DeleteDomainRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
                    domainName - The name of the domain to delete.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        deleteSpecificDomain(searchClient, domainName);
        System.out.println("Done");
    }

    public static void deleteSpecificDomain(OpenSearchClient searchClient, String
 domainName) {
        try {
            DeleteDomainRequest domainRequest = DeleteDomainRequest.builder()
                    .domainName(domainName)
                    .build();

            searchClient.deleteDomain(domainRequest);
            System.out.println(domainName + " was successfully deleted.");

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteDomaina Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSpecificDomain(domainNameVal: String) {

    val request = DeleteDomainRequest {
        domainName = domainNameVal
    }
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        searchClient.deleteDomain(request)
        println("$domainNameVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteDomainreferência da API AWSSDK for Kotlin.

Listar domínios de OpenSearch serviço usando um SDK AWS

Os exemplos de código a seguir mostram como listar domínios OpenSearch de serviço.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.DomainInfo;
import software.amazon.awssdk.services.opensearch.model.ListDomainNamesRequest;
import software.amazon.awssdk.services.opensearch.model.ListDomainNamesResponse;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;

import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListDomainNames {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();
        listAllDomains(searchClient);
        System.out.println("Done");
    }

    public static void listAllDomains(OpenSearchClient searchClient) {
        try {
            ListDomainNamesRequest namesRequest =
 ListDomainNamesRequest.builder()
                    .engineType("OpenSearch")
                    .build();

            ListDomainNamesResponse response =
 searchClient.listDomainNames(namesRequest);
            List<DomainInfo> domainInfoList = response.domainNames();
            for (DomainInfo domain : domainInfoList)
                System.out.println("Domain name is " + domain.domainName());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListDomainNamesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllDomains() {

    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val response: ListDomainNamesResponse =
 searchClient.listDomainNames(ListDomainNamesRequest {})
        response.domainNames?.forEach { domain ->
            println("Domain name is " + domain.domainName)
        }
    }
}
```

- Para obter detalhes da API, consulte a ListDomainNamesreferência da API AWSSDK for Kotlin.

Modificar uma configuração de cluster do domínio OpenSearch de serviço especificado usando um AWS SDK

Os exemplos de código a seguir mostram como modificar a configuração de um cluster de um domínio de OpenSearch serviço.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.ClusterConfig;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;
import
 software.amazon.awssdk.services.opensearch.model.UpdateDomainConfigRequest;
import
 software.amazon.awssdk.services.opensearch.model.UpdateDomainConfigResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
                    domainName - The name of the domain to update.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        updateSpecificDomain(searchClient, domainName);
        System.out.println("Done");
```

```
    }

    public static void updateSpecificDomain(OpenSearchClient searchClient, String
 domainName) {
        try {
            ClusterConfig clusterConfig = ClusterConfig.builder()
                    .instanceCount(3)
                    .build();

            UpdateDomainConfigRequest updateDomainConfigRequest =
 UpdateDomainConfigRequest.builder()
                    .domainName(domainName)
                    .clusterConfig(clusterConfig)
                    .build();

            System.out.println("Sending domain update request...");
            UpdateDomainConfigResponse updateResponse =
 searchClient.updateDomainConfig(updateDomainConfigRequest);
            System.out.println("Domain update response from Amazon OpenSearch
 Service:");
            System.out.println(updateResponse.toString());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateDomainConfiga Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateSpecificDomain(domainNameVal: String?) {

    val clusterConfigOb = ClusterConfig {
        instanceCount = 3
    }

    val request = UpdateDomainConfigRequest {
        domainName = domainNameVal
        clusterConfig = clusterConfigOb
    }

    println("Sending domain update request...")
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val updateResponse = searchClient.updateDomainConfig(request)
        println("Domain update response from Amazon OpenSearch Service:")
        println(updateResponse.toString())
    }
}
```

- Para obter detalhes da API, consulte a UpdateDomainConfigreferência da API AWSSDK for Kotlin.

Exemplos de código para EventBridge usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon EventBridge com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- EventBridge Guia do usuário — Mais informações sobre EventBridge.
- EventBridge Referência da API — Detalhes sobre todas as EventBridge ações disponíveis.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá EventBridge

O exemplo de código a seguir mostra como começar a usar o EventBridge.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.EventBridge;
using Amazon.EventBridge.Model;

namespace EventBridgeActions;

public static class HelloEventBridge
{
    static async Task Main(string[] args)
    {
        var eventBridgeClient = new AmazonEventBridgeClient();

        Console.WriteLine($"Hello Amazon EventBridge! Following are some of your
 EventBuses:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five event buses.
        var response = await eventBridgeClient.ListEventBusesAsync(
            new ListEventBusesRequest()
```

```
            {
                Limit = 5
            });

        foreach (var eventBus in response.EventBuses)
        {
            Console.WriteLine($"\tEventBus: {eventBus.Name}");
            Console.WriteLine($"\tArn: {eventBus.Arn}");
            Console.WriteLine($"\tPolicy: {eventBus.Policy}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListEventBusesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 */
public class HelloEventBridge {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
```

```
        EventBridgeClient eventBrClient = EventBridgeClient.builder()
                .region(region)
                .build();

        listBuses(eventBrClient);
        eventBrClient.close();
    }

    public static void listBuses(EventBridgeClient eventBrClient) {
        try {
            ListEventBusesRequest busesRequest = ListEventBusesRequest.builder()
                    .limit(10)
                    .build();

            ListEventBusesResponse response =
 eventBrClient.listEventBuses(busesRequest);
            List<EventBus> buses = response.eventBuses();
            for (EventBus bus : buses) {
                System.out.println("The name of the event bus is: " +
 bus.name());
                System.out.println("The ARN of the event bus is: " + bus.arn());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListEventBusesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.eventbridge.EventBridgeClient
import aws.sdk.kotlin.services.eventbridge.model.ListEventBusesRequest
import aws.sdk.kotlin.services.eventbridge.model.ListEventBusesResponse

suspend fun main() {
    listBusesHello()
}

suspend fun listBusesHello() {
    val request = ListEventBusesRequest {
        limit = 10
    }

    EventBridgeClient { region = "us-west-2" }.use { eventBrClient ->
        val response: ListEventBusesResponse =
 eventBrClient.listEventBuses(request)
        response.eventBuses?.forEach { bus ->
            println("The name of the event bus is ${bus.name}")
            println("The ARN of the event bus is ${bus.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListEventBusesreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações para EventBridge usar AWS SDKs
  - Adicionar um destino usando um AWS SDK

- Crie uma EventBridge regra usando um AWS SDK
- Excluir uma EventBridge regra usando um AWS SDK
- Descrever uma EventBridge regra usando um AWS SDK
- Desabilitar uma EventBridge regra usando um AWS SDK
- Ativar uma EventBridge regra usando um AWS SDK
- EventBridge Listar nomes de regras para um destino usando um AWS SDK
- Listar EventBridge regras usando um AWS SDK
- Listar EventBridge destinos para uma regra usando um AWS SDK
- Remover EventBridge alvos de uma regra usando um AWS SDK
- Envie EventBridge eventos usando um AWS SDK

- Cenários para EventBridge usar AWS SDKs
  - Crie e acione uma regra na Amazon EventBridge usando um AWS SDK
  - Comece a usar EventBridge regras e metas usando um AWS SDK
- Exemplos de vários serviços para EventBridge usar SDKs AWS
  - Usar eventos programados para chamar uma função do Lambda

Ações para EventBridge usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon EventBridge com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para EventBridge usar AWS SDKs.

Exemplos

- Adicionar um destino usando um AWS SDK
- Crie uma EventBridge regra usando um AWS SDK
- Excluir uma EventBridge regra usando um AWS SDK
- Descrever uma EventBridge regra usando um AWS SDK
- Desabilitar uma EventBridge regra usando um AWS SDK
- Ativar uma EventBridge regra usando um AWS SDK
- EventBridge Listar nomes de regras para um destino usando um AWS SDK

- Listar EventBridge regras usando um AWS SDK
- Listar EventBridge destinos para uma regra usando um AWS SDK
- Remover EventBridge alvos de uma regra usando um AWS SDK
- Envie EventBridge eventos usando um AWS SDK

Adicionar um destino usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar um alvo a um EventBridge evento da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione um tópico do Amazon SNS como um destino para uma regra.

```
    /// <summary>
    /// Add an Amazon SNS target topic to a rule.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <param name="targetArn">The ARN of the Amazon SNS target.</param>
    /// <param name="eventBusArn">The optional event bus name, uses default if
empty.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> AddSnsTargetToRule(string ruleName, string
targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();
```

```
        // Create the list of targets and add a new target.
        var targets = new List<Target>
        {
            new Target()
            {
                Arn = targetArn,
                Id = targetID
            }
        };

        // Add the targets to the rule.
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });

        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }

        return targetID;
    }
```

Adicione um transformador de entrada a um destino para uma regra.

```
    /// <summary>
    /// Update an Amazon S3 object created rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the
default event bus.</param>
```

```
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateS3UploadRuleTargetWithTransform(string
ruleName, string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
                InputTransformer = new InputTransformer()
                {
                    InputPathsMap = new Dictionary<string, string>()
                    {
                        {"bucket", "$.detail.bucket.name"},
                        {"time", "$.time"}
                    },
                    InputTemplate = "\"Notification: an object was uploaded to
bucket <bucket> at <time>.\""
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }
        return targetID;
    }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutTargetsRequest.h>
#include <aws/events/model/PutTargetsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Adicionar o destino.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::Target target;
        target.SetArn(lambda_arn);
        target.SetId(target_id);

        Aws::CloudWatchEvents::Model::PutTargetsRequest request;
        request.SetRule(rule_name);
        request.AddTargets(target);

        auto putTargetsOutcome = cwe.PutTargets(request);
        if (!putTargetsOutcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events target for rule "
                << rule_name << ": " <<
                putTargetsOutcome.GetError().GetMessage() << std::endl;
        }
```

```
        else
        {
            std::cout <<
                "Successfully created CloudWatch events target for rule "
                << rule_name << std::endl;
        }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para adicionar alvos às regras de CloudWatch eventos

Este exemplo adiciona uma função do Lambda como o destino de uma regra:

```
aws events put-targets --rule DailyLambdaFunction --targets
 "Id"="1","Arn"="arn:aws:lambda:us-east-1:123456789012:function:MyFunctionName"
```

Este exemplo define um stream do Amazon Kinesis como o destino, de forma que os eventos capturados por essa regra sejam retransmitidos para o stream:

```
aws events put-targets --rule EC2InstanceStateChanges --targets
 "Id"="1","Arn"="arn:aws:kinesis:us-east-1:123456789012:stream/
MyStream","RoleArn"="arn:aws:iam::123456789012:role/MyRoleForThisRule"
```

Este exemplo define dois streams do Amazon Kinesis como destinos de uma regra:

```
aws events put-targets --rule DailyLambdaFunction --targets
 "Id"="Target1","Arn"="arn:aws:kinesis:us-east-1:379642911888:stream/
MyStream1","RoleArn"="arn:aws:iam::379642911888:role/ MyRoleToAccessLambda"
  "Id"="Target2"," Arn"="arn:aws:kinesis:us-east-1:379642911888:stream/
MyStream2","RoleArn"="arn:aws:iam::379642911888:role/MyRoleToAccessLambda"
```

- Para obter detalhes da API, consulte PutTargetsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione um tópico do Amazon SNS como um destino para uma regra.

```
   // Add a rule which triggers an SNS target when a file is uploaded to an S3
   // bucket.
   public static void addSnsEventRule(EventBridgeClient eventBrClient, String
ruleName, String topicArn,
           String topicName, String eventRuleName, String bucketName) {
       String targetID = java.util.UUID.randomUUID().toString();
       Target myTarget = Target.builder()
               .id(targetID)
               .arn(topicArn)
               .build();

       List<Target> targets = new ArrayList<>();
       targets.add(myTarget);
       PutTargetsRequest request = PutTargetsRequest.builder()
               .eventBusName(null)
               .targets(targets)
               .rule(ruleName)
               .build();

       eventBrClient.putTargets(request);
       System.out.println("Added event rule " + eventRuleName + " with Amazon
SNS target " + topicName + " for bucket "
               + bucketName + ".");
   }
```

Adicione um transformador de entrada a um destino para uma regra.

```
   public static void updateCustomRuleTargetWithTransform(EventBridgeClient
eventBrClient, String topicArn,
```

```
            String ruleName) {
        String targetId = java.util.UUID.randomUUID().toString();
        InputTransformer inputTransformer = InputTransformer.builder()
                .inputTemplate("\"Notification: sample event was received.\"")
                .build();

        Target target = Target.builder()
                .id(targetId)
                .arn(topicArn)
                .inputTransformer(inputTransformer)
                .build();

        try {
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);
        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
```

```
  EventBridgeClient,
  PutTargetsCommand,
} from "@aws-sdk/client-eventbridge";

export const putTarget = async (
  existingRuleName = "some-rule",
  targetArn = "arn:aws:lambda:us-east-1:000000000000:function:test-func",
  uniqueId = Date.now().toString(),
) => {
  const client = new EventBridgeClient({});
  const response = await client.send(
    new PutTargetsCommand({
      Rule: existingRuleName,
      Targets: [
        {
          Arn: targetArn,
          Id: uniqueId,
        },
      ],
    }),
  );

  console.log("PutTargets response:");
  console.log(response);
  // PutTargets response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'f5b23b9a-2c17-45c1-ad5c-f926c3692e3d',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   FailedEntries: [],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myEventBridgeTarget",
    },
  ],
};

ebevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Add a rule that triggers an SNS target when a file is uploaded to an S3
 bucket.
suspend fun addSnsEventRule(ruleName: String?, topicArn: String?, topicName:
 String, eventRuleName: String, bucketName: String) {
    val targetID = UUID.randomUUID().toString()
    val myTarget = Target {
        id = targetID
        arn = topicArn
    }

    val targetsOb = mutableListOf<Target>()
    targetsOb.add(myTarget)

    val request = PutTargetsRequest {
        eventBusName = null
        targets = targetsOb
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(request)
        println("Added event rule $eventRuleName with Amazon SNS target
 $topicName for bucket $bucketName.")
    }
}
```

Adicionar um transformador de entrada a um destino para uma regra.

```
suspend fun updateCustomRuleTargetWithTransform(topicArn: String?, ruleName:
 String?) {
    val targetId = UUID.randomUUID().toString()
```

```
    val inputTransformerOb = InputTransformer {
        inputTemplate = "\"Notification: sample event was received.\""
    }

    val target = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransformerOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
        targets = listOf(target)
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}
```

- Para obter detalhes da API, consulte a PutTargetsreferência da API AWSSDK for Kotlin.

Crie uma EventBridge regra usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma EventBridge regra da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e acionar uma regra
- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
    /// <summary>
    /// Create a new event rule that triggers when an Amazon S3 object is created
 in a bucket.
    /// </summary>
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="ruleName">The name to give the rule.</param>
    /// <param name="bucketName">The name of the bucket to trigger the event.</
param>
    /// <returns>The ARN of the new rule.</returns>
    public async Task<string> PutS3UploadRule(string roleArn, string ruleName,
 string bucketName)
    {
        string eventPattern = "{" +
                                "\"source\": [\"aws.s3\"]," +
                                    "\"detail-type\": [\"Object Created\"]," +
                                    "\"detail\": {" +
                                        "\"bucket\": {" +
                                            "\"name\": [\"" + bucketName + "\"]"
 +
                                        "}" +
                                    "}" +
                                "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Example S3 upload rule for EventBridge",
                RoleArn = roleArn,
```

```
                EventPattern = eventPattern
            });

        return response.RuleArn;
    }
```

Crie uma regra que use um padrão personalizado.

```
    /// <summary>
    /// Update a rule to use a custom defined event pattern.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <returns>The ARN of the updated rule.</returns>
    public async Task<string> UpdateCustomEventPattern(string ruleName)
    {
        string customEventsPattern = "{" +
                                     "\"source\": [\"ExampleSource\"]," +
                                     "\"detail-type\": [\"ExampleType\"]" +
                                     "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Custom test rule",
                EventPattern = customEventsPattern
            });

        return response.RuleArn;
    }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutRuleRequest.h>
#include <aws/events/model/PutRuleResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Crie a regra.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;
        Aws::CloudWatchEvents::Model::PutRuleRequest request;
        request.SetName(rule_name);
        request.SetRoleArn(role_arn);
        request.SetScheduleExpression("rate(5 minutes)");
        request.SetState(Aws::CloudWatchEvents::Model::RuleState::ENABLED);

        auto outcome = cwe.PutRule(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events rule " <<
                rule_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch events rule " <<
                rule_name << " with resulting Arn " <<
                outcome.GetResult().GetRuleArn() << std::endl;
        }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar regras de CloudWatch eventos

Este exemplo cria uma regra que é acionada diariamente às 9h (UTC). Ao utilizar put-targets para adicionar uma função do Lambda como destino dessa regra, é possível executar a função do Lambda todos os dias no horário especificado:

```
aws events put-rule --name "DailyLambdaFunction" --schedule-expression "cron(0 9
 * * ? *)"
```

O exemplo a seguir cria uma regra que é acionada quando qualquer instância do EC2 na região muda de estado.

```
aws events put-rule --name "EC2InstanceStateChanges" --event-pattern "{\"source
\":[\"aws.ec2\"],\"detail-type\":[\"EC2 Instance State-change Notification\"]}"
 --role-arn "arn:aws:iam::123456789012:role/MyRoleForThisRule"
```

O exemplo a seguir cria uma regra que é acionada quando qualquer instância do EC2 na região é interrompida ou encerrada:

```
aws events put-rule --name "EC2InstanceStateChangeStopOrTerminate" --event-
pattern "{\"source\":[\"aws.ec2\"],\"detail-type\":[\"EC2 Instance State-change
 Notification\"],\"detail\":{\"state\":[\"stopped\",\"terminated\"]}}" --role-arn
 "arn:aws:iam::123456789012:role/MyRoleForThisRule"
```

- Para obter detalhes da API, consulte PutRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma regra agendada

```
   public static void createEBRule(EventBridgeClient eventBrClient, String
ruleName, String cronExpression) {
       try {
           PutRuleRequest ruleRequest = PutRuleRequest.builder()
                   .name(ruleName)
                   .eventBusName("default")
                   .scheduleExpression(cronExpression)
                   .state("ENABLED")
                   .description("A test rule that runs on a schedule created by
the Java API")
                   .build();

           PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
           System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

       } catch (EventBridgeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

Criar uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
   // Create a new event rule that triggers when an Amazon S3 object is created
in
   // a bucket.
```

```
    public static void addEventRule(EventBridgeClient eventBrClient, String
roleArn, String bucketName,
            String eventRuleName) {
        String pattern = "{\n" +
                "  \"source\": [\"aws.s3\"],\n" +
                "  \"detail-type\": [\"Object Created\"],\n" +
                "  \"detail\": {\n" +
                "    \"bucket\": {\n" +
                "      \"name\": [\"" + bucketName + "\"]\n" +
                "    }\n" +
                "  }\n" +
                "}";

        try {
            PutRuleRequest ruleRequest = PutRuleRequest.builder()
                    .description("Created by using the AWS SDK for Java v2")
                    .name(eventRuleName)
                    .eventPattern(pattern)
                    .roleArn(roleArn)
                    .build();

            PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
            System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EventBridgeClient, PutRuleCommand } from "@aws-sdk/client-eventbridge";

export const putRule = async (
  ruleName = "some-rule",
  source = "some-source",
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutRuleCommand({
      Name: ruleName,
      EventPattern: JSON.stringify({ source: [source] }),
      State: "ENABLED",
      EventBusName: "default",
    }),
  );

  console.log("PutRule response:");
  console.log(response);
  // PutRule response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'd7292ced-1544-421b-842f-596326bc7072',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   RuleArn: 'arn:aws:events:us-east-1:xxxxxxxxxxxx:rule/
EventBridgeTestRule-1696280037720'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

ebevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.RuleArn);
  }
});
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma regra agendada

```
suspend fun createScRule(ruleName: String?, cronExpression: String?) {
    val ruleRequest = PutRuleRequest {
        name = ruleName
        eventBusName = "default"
        scheduleExpression = cronExpression
        state = RuleState.Enabled
        description = "A test rule that runs on a schedule created by the Kotlin
 API"
    }

    EventBridgeClient { region = "us-west-2" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}
```

Criar uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
// Create a new event rule that triggers when an Amazon S3 object is created in a
 bucket.
suspend fun addEventRule(roleArnVal: String?, bucketName: String, eventRuleName:
 String?) {
    val pattern = """{
        "source": ["aws.s3"],
        "detail-type": ["Object Created"],
        "detail": {
        "bucket": {
            "name": ["$bucketName"]
```

```
            }
        }
    }"""

    val ruleRequest = PutRuleRequest {
        description = "Created by using the AWS SDK for Kotlin"
        name = eventRuleName
        eventPattern = pattern
        roleArn = roleArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}
```

- Para obter detalhes da API, consulte a PutRulereferência da API AWSSDK for Kotlin.

Excluir uma EventBridge regra usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma EventBridge regra da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma regra pelo nome.

```
    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteRuleByName(string ruleName)
    {
        var response = await _amazonEventBridge.DeleteRuleAsync(
            new DeleteRuleRequest()
            {
                Name = ruleName
            });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRulea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para excluir uma regra de CloudWatch eventos

Este exemplo exclui a regra chamada InstanceStateChanges EC2:

```
aws events delete-rule --name "EC2InstanceStateChanges"
```

- Para obter detalhes da API, consulte DeleteRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteRuleByName(EventBridgeClient eventBrClient, String
 ruleName) {
        DeleteRuleRequest ruleRequest = DeleteRuleRequest.builder()
                .name(ruleName)
                .build();

        eventBrClient.deleteRule(ruleRequest);
        System.out.println("Successfully deleted the rule");
    }
```

- Para obter detalhes da API, consulte DeleteRulea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteRuleByName(ruleName: String?) {
    val ruleRequest = DeleteRuleRequest {
        name = ruleName
    }
    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.deleteRule(ruleRequest)
        println("Successfully deleted the rule")
    }
}
```

- Para obter detalhes da API, consulte a DeleteRulereferência da API AWSSDK for Kotlin.

Descrever uma EventBridge regra usando um AWS SDK

Os exemplos de código a seguir mostram como descrever uma EventBridge regra da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o estado de uma regra usando a descrição da regra.

```
    /// <summary>
    /// Get the state for a rule by the rule name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="eventBusName">The optional name of the event bus. If empty,
uses the default event bus.</param>
    /// <returns>The state of the rule.</returns>
    public async Task<RuleState> GetRuleStateByRuleName(string ruleName, string?
eventBusName = null)
    {
        var ruleResponse = await _amazonEventBridge.DescribeRuleAsync(
            new DescribeRuleRequest()
            {
                Name = ruleName,
                EventBusName = eventBusName
            });
        return ruleResponse.State;
    }
```

- Para obter detalhes da API, consulte DescribeRulea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para exibir informações sobre uma regra de CloudWatch Eventos

Este exemplo exibe informações sobre a regra chamada DailyLambdaFunction:

```
aws events describe-rule --name "DailyLambdaFunction"
```

- Para obter detalhes da API, consulte DescribeRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkRule(EventBridgeClient eventBrClient, String
eventRuleName) {
       try {
           DescribeRuleRequest ruleRequest = DescribeRuleRequest.builder()
                   .name(eventRuleName)
                   .build();

           DescribeRuleResponse response =
eventBrClient.describeRule(ruleRequest);
           System.out.println("The state of the rule is " +
response.stateAsString());

       } catch (EventBridgeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeRulea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkRule(eventRuleName: String?) {
    val ruleRequest = DescribeRuleRequest {
        name = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.describeRule(ruleRequest)
        println("The state of the rule is $response")
    }
}
```

- Para obter detalhes da API, consulte a DescribeRulereferência da API AWSSDK for Kotlin.

Desabilitar uma EventBridge regra usando um AWS SDK

Os exemplos de código a seguir mostram como desativar uma EventBridge regra da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desabilite uma regra pelo nome da regra.

```
/// <summary>
/// Disable a particular rule on an event bus.
/// </summary
/// <param name="ruleName">The name of the rule.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DisableRuleByName(string ruleName)
{
    var ruleResponse = await _amazonEventBridge.DisableRuleAsync(
        new DisableRuleRequest()
        {
            Name = ruleName
        });
    return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DisableRulea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para desativar uma regra de CloudWatch eventos

Este exemplo desativa a regra chamada DailyLambdaFunction. A regra não é excluída:

```
aws events disable-rule --name "DailyLambdaFunction"
```

- Para obter detalhes da API, consulte DisableRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desabilitar uma regra usando o nome da regra.

```
   public static void changeRuleState(EventBridgeClient eventBrClient, String
eventRuleName, Boolean isEnabled) {
       try {
           if (!isEnabled) {
               System.out.println("Disabling the rule: " + eventRuleName);
               DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                       .name(eventRuleName)
                       .build();

               eventBrClient.disableRule(ruleRequest);
           } else {
               System.out.println("Enabling the rule: " + eventRuleName);
               EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                       .name(eventRuleName)
                       .build();
               eventBrClient.enableRule(ruleRequest);
           }

       } catch (EventBridgeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DisableRulea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}
```

- Para obter detalhes da API, consulte a DisableRulereferência da API AWSSDK for Kotlin.

Ativar uma EventBridge regra usando um AWS SDK

Os exemplos de código a seguir mostram como habilitar uma EventBridge regra da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilite uma regra pelo nome da regra.

```
/// <summary>
/// Enable a particular rule on an event bus.
/// </summary>
/// <param name="ruleName">The name of the rule.</param>
/// <returns>True if successful.</returns>
public async Task<bool> EnableRuleByName(string ruleName)
{
    var ruleResponse = await _amazonEventBridge.EnableRuleAsync(
        new EnableRuleRequest()
        {
            Name = ruleName
        });
    return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte EnableRulea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para habilitar uma regra de CloudWatch Eventos

Este exemplo ativa a regra chamada DailyLambdaFunction, que havia sido desativada anteriormente:

```
aws events enable-rule --name "DailyLambdaFunction"
```

- Para obter detalhes da API, consulte EnableRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilitar uma regra usando o nome da regra.

```
   public static void changeRuleState(EventBridgeClient eventBrClient, String
eventRuleName, Boolean isEnabled) {
       try {
           if (!isEnabled) {
               System.out.println("Disabling the rule: " + eventRuleName);
               DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                       .name(eventRuleName)
                       .build();

               eventBrClient.disableRule(ruleRequest);
           } else {
               System.out.println("Enabling the rule: " + eventRuleName);
               EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                       .name(eventRuleName)
                       .build();
               eventBrClient.enableRule(ruleRequest);
           }

       } catch (EventBridgeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte EnableRulea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}
```

- Para obter detalhes da API, consulte a EnableRulereferência da API AWSSDK for Kotlin.

EventBridge Listar nomes de regras para um destino usando um AWS SDK

Os exemplos de código a seguir mostram como listar nomes de EventBridge regras da Amazon para um alvo.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos os nomes das regras usando o destino.

```
    /// <summary>
    /// List names of all rules matching a target.
    /// </summary>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <returns>The list of rule names.</returns>
    public async Task<List<string>> ListAllRuleNamesByTarget(string targetArn)
    {
        var results = new List<string>();
        var request = new ListRuleNamesByTargetRequest()
        {
            TargetArn = targetArn
        };
        ListRuleNamesByTargetResponse response;
        do
        {
            response = await
_amazonEventBridge.ListRuleNamesByTargetAsync(request);
            results.AddRange(response.RuleNames);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }
```

- Para obter detalhes da API, consulte ListRuleNamesByTargeta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como exibir todas as regras que têm um destino especificado

Este exemplo exibe todas as regras que têm a função Lambda chamada "MyFunctionName" como destino:

```
aws events list-rule-names-by-target --target-arn "arn:aws:lambda:us-
east-1:123456789012:function:MyFunctionName"
```

- Para obter detalhes da API, consulte ListRuleNamesByTargetem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos os nomes das regras usando a destino.

```
   public static void listTargetRules(EventBridgeClient eventBrClient, String
topicArn) {
       ListRuleNamesByTargetRequest ruleNamesByTargetRequest =
ListRuleNamesByTargetRequest.builder()
               .targetArn(topicArn)
               .build();

       ListRuleNamesByTargetResponse response =
eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest);
       List<String> rules = response.ruleNames();
```

```
        for (String rule : rules) {
            System.out.println("The rule name is " + rule);
        }
    }
```

- Para obter detalhes da API, consulte ListRuleNamesByTargeta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTargetRules(topicArnVal: String?) {
    val ruleNamesByTargetRequest = ListRuleNamesByTargetRequest {
        targetArn = topicArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response =
 eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest)
        response.ruleNames?.forEach { rule ->
            println("The rule name is $rule")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListRuleNamesByTargetreferência da API AWSSDK for Kotlin.

Listar EventBridge regras usando um AWS SDK

Os exemplos de código a seguir mostram como listar EventBridge as regras da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todas as regras para um barramento de eventos.

```
   /// <summary>
   /// List the rules on an event bus.
   /// </summary>
   /// <param name="eventBusArn">The optional ARN of the event bus. If empty,
uses the default event bus.</param>
   /// <returns>The list of rules.</returns>
   public async Task<List<Rule>> ListAllRulesForEventBus(string? eventBusArn =
null)
   {
       var results = new List<Rule>();
       var request = new ListRulesRequest()
       {
           EventBusName = eventBusArn
       };
       // Get all of the pages of rules.
       ListRulesResponse response;
       do
       {
           response = await _amazonEventBridge.ListRulesAsync(request);
           results.AddRange(response.Rules);
           request.NextToken = response.NextToken;

       } while (response.NextToken is not null);

       return results;
```

```
    }
```

- Para obter detalhes da API, consulte ListRulesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para exibir uma lista de todas as regras de CloudWatch eventos

Este exemplo exibe todas as regras de CloudWatch eventos na região:

```
aws events list-rules
```

Para exibir uma lista de regras de CloudWatch eventos começando com uma determinada string.

Este exemplo exibe todas as regras de CloudWatch eventos na região que têm um nome começando com “Diário”:

```
aws events list-rules --name-prefix "Daily"
```

- Para obter detalhes da API, consulte ListRulesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilitar uma regra usando o nome da regra.

```
    public static void listRules(EventBridgeClient eventBrClient) {
        try {
```

```
            ListRulesRequest rulesRequest = ListRulesRequest.builder()
                    .eventBusName("default")
                    .limit(10)
                    .build();

            ListRulesResponse response = eventBrClient.listRules(rulesRequest);
            List<Rule> rules = response.rules();
            for (Rule rule : rules) {
                System.out.println("The rule name is : " + rule.name());
                System.out.println("The rule description is : " +
 rule.description());
                System.out.println("The rule state is : " +
 rule.stateAsString());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListRulesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listRules() {
    val rulesRequest = ListRulesRequest {
        eventBusName = "default"
        limit = 10
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRules(rulesRequest)
```

```
        response.rules?.forEach { rule ->
            println("The rule name is ${rule.name}")
            println("The rule ARN is ${rule.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListRulesreferência da API AWSSDK for Kotlin.

Listar EventBridge destinos para uma regra usando um AWS SDK

Os exemplos de código a seguir mostram como listar EventBridge alvos da Amazon para uma regra.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste todos os destinos para uma regra usando o nome da regra.

```
    /// <summary>
    /// List all of the targets matching a rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>The list of targets.</returns>
    public async Task<List<Target>> ListAllTargetsOnRule(string ruleName)
    {
        var results = new List<Target>();
        var request = new ListTargetsByRuleRequest()
```

```
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse response;
        do
        {
            response = await _amazonEventBridge.ListTargetsByRuleAsync(request);
            results.AddRange(response.Targets);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }
```

- Para obter detalhes da API, consulte ListTargetsByRulea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para exibir todos os alvos de uma regra de CloudWatch Eventos

Este exemplo exibe todos os alvos da regra chamada DailyLambdaFunction:

```
aws events list-targets-by-rule --rule  "DailyLambdaFunction"
```

- Para obter detalhes da API, consulte ListTargetsByRuleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos as destinos de uma regra usando o nome da regra.

```
    public static void listTargets(EventBridgeClient eventBrClient, String
 ruleName) {
        ListTargetsByRuleRequest ruleRequest = ListTargetsByRuleRequest.builder()
                .rule(ruleName)
                .build();

        ListTargetsByRuleResponse res =
 eventBrClient.listTargetsByRule(ruleRequest);
        List<Target> targetsList = res.targets();
        for (Target target: targetsList) {
            System.out.println("Target ARN: "+target.arn());
        }
    }
```

- Para obter detalhes da API, consulte ListTargetsByRulea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTargets(ruleName: String?) {
    val ruleRequest = ListTargetsByRuleRequest {
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(ruleRequest)
        response.targets?.forEach { target ->
            println("Target ARN: ${target.arn}")
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte a ListTargetsByRulereferência da API AWSSDK for Kotlin.

Remover EventBridge alvos de uma regra usando um AWS SDK

Os exemplos de código a seguir mostram como remover EventBridge alvos da Amazon de uma regra.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remova todos os destinos de uma regra usando o nome da regra.

```
    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> RemoveAllTargetsFromRule(string ruleName)
    {
        var targetIds = new List<string>();
        var request = new ListTargetsByRuleRequest()
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse targetsResponse;
        do
        {
            targetsResponse = await
_amazonEventBridge.ListTargetsByRuleAsync(request);
            targetIds.AddRange(targetsResponse.Targets.Select(t => t.Id));
```

```
            request.NextToken = targetsResponse.NextToken;

        } while (targetsResponse.NextToken is not null);

        var removeResponse = await _amazonEventBridge.RemoveTargetsAsync(
            new RemoveTargetsRequest()
            {
                Rule = ruleName,
                Ids = targetIds
            });

        if (removeResponse.FailedEntryCount > 0)
        {
            removeResponse.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to remove target {e.TargetId}: {e.ErrorMessage},
 code {e.ErrorCode}");
            });
        }

        return removeResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte RemoveTargetsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como remover um destino de um evento

Este exemplo remove o stream do Amazon Kinesis chamado MyStream 1 de ser um alvo da regra. DailyLambdaFunction Quando DailyLambdaFunction foi criado, esse fluxo foi definido como um destino com um ID de Target1:

```
aws events remove-targets --rule "DailyLambdaFunction" --ids "Target1"
```

- Para obter detalhes da API, consulte RemoveTargetsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover todos as destinos de uma regra usando o nome da regra.

```
   public static void deleteTargetsFromRule(EventBridgeClient eventBrClient,
String eventRuleName) {
       // First, get all targets that will be deleted.
       ListTargetsByRuleRequest request = ListTargetsByRuleRequest.builder()
               .rule(eventRuleName)
               .build();

       ListTargetsByRuleResponse response =
eventBrClient.listTargetsByRule(request);
       List<Target> allTargets = response.targets();

       // Get all targets and delete them.
       for (Target myTarget : allTargets) {
           RemoveTargetsRequest removeTargetsRequest =
RemoveTargetsRequest.builder()
                   .rule(eventRuleName)
                   .ids(myTarget.id())
                   .build();

           eventBrClient.removeTargets(removeTargetsRequest);
           System.out.println("Successfully removed the target");
       }
   }
```

- Para obter detalhes da API, consulte RemoveTargetsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteTargetsFromRule(eventRuleName: String?) {
    // First, get all targets that will be deleted.
    val request = ListTargetsByRuleRequest {
        rule = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(request)
        val allTargets = response.targets

        // Get all targets and delete them.
        if (allTargets != null) {
            for (myTarget in allTargets) {
                val removeTargetsRequest = RemoveTargetsRequest {
                    rule = eventRuleName
                    ids = listOf(myTarget.id.toString())
                }
                eventBrClient.removeTargets(removeTargetsRequest)
                println("Successfully removed the target")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a RemoveTargetsreferência da API AWSSDK for Kotlin.

Envie EventBridge eventos usando um AWS SDK

Os exemplos de código a seguir mostram como enviar EventBridge eventos da Amazon.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e acionar uma regra
- Conceitos básicos de regras e destinos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie um evento que corresponda a um padrão personalizado para uma regra.

```
    /// <summary>
    /// Add an event to the event bus that includes an email, message, and time.
    /// </summary>
    /// <param name="email">The email to use in the event detail of the custom
event.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutCustomEmailEvent(string email)
    {
        var eventDetail = new
        {
            UserEmail = email,
            Message = "This event was generated by example code.",
            UtcTime = DateTime.UtcNow.ToString("g")
        };
        var response = await _amazonEventBridge.PutEventsAsync(
            new PutEventsRequest()
            {
                Entries = new List<PutEventsRequestEntry>()
                {
                    new PutEventsRequestEntry()
                    {
                        Source = "ExampleSource",
                        Detail = JsonSerializer.Serialize(eventDetail),
```

```
                        DetailType = "ExampleType"
                    }
                }
            });

        return response.FailedEntryCount == 0;
    }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutEventsRequest.h>
#include <aws/events/model/PutEventsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Enviar evento.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::PutEventsRequestEntry event_entry;
        event_entry.SetDetail(MakeDetails(event_key, event_value));
        event_entry.SetDetailType("sampleSubmitted");
        event_entry.AddResources(resource_arn);
        event_entry.SetSource("aws-sdk-cpp-cloudwatch-example");
```

```
        Aws::CloudWatchEvents::Model::PutEventsRequest request;
        request.AddEntries(event_entry);

        auto outcome = cwe.PutEvents(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to post CloudWatch event: " <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully posted CloudWatch event" << std::endl;
        }
```

- Para obter detalhes da API, consulte PutEvents a Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para enviar um evento personalizado para CloudWatch Eventos

Este exemplo envia um evento personalizado para CloudWatch Eventos. O evento está contido no arquivo putevents.json:

```
aws events put-events --entries file://putevents.json
```

Veja a seguir o conteúdo do arquivo putevent.json:

```
[
  {
    "Source": "com.mycompany.myapp",
    "Detail": "{ \"key1\": \"value1\", \"key2\": \"value2\" }",
    "Resources": [
      "resource1",
      "resource2"
    ],
    "DetailType": "myDetailType"
  },
  {
    "Source": "com.mycompany.myapp",
```

```
    "Detail": "{ \"key1\": \"value3\", \"key2\": \"value4\" }",
    "Resources": [
      "resource1",
      "resource2"
    ],
    "DetailType": "myDetailType"
   }
]
```

- Para obter detalhes da API, consulte PutEventsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void triggerCustomRule(EventBridgeClient eventBrClient, String
email) {
       String json = "{" +
               "\"UserEmail\": \"" + email + "\"," +
               "\"Message\": \"This event was generated by example code.\"," +
               "\"UtcTime\": \"Now.\"" +
               "}";

       PutEventsRequestEntry entry = PutEventsRequestEntry.builder()
               .source("ExampleSource")
               .detail(json)
               .detailType("ExampleType")
               .build();

       PutEventsRequest eventsRequest = PutEventsRequest.builder()
               .entries(entry)
               .build();

       eventBrClient.putEvents(eventsRequest);
   }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
  EventBridgeClient,
  PutEventsCommand,
} from "@aws-sdk/client-eventbridge";

export const putEvents = async (
  source = "eventbridge.integration.test",
  detailType = "greeting",
  resources = [],
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutEventsCommand({
      Entries: [
        {
          Detail: JSON.stringify({ greeting: "Hello there." }),
          DetailType: detailType,
          Resources: resources,
          Source: source,
        },
      ],
    }),
  );

  console.log("PutEvents response:");
```

```
  console.log(response);
  // PutEvents response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '3d0df73d-dcea-4a23-ae0d-f5556a3ac109',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Entries: [ { EventId: '51620841-5af4-6402-d9bc-b77734991eb5' } ],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
```

```
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
    },
  ],
};

ebevents.putEvents(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun triggerCustomRule(email: String) {
    val json = "{" +
        "\"UserEmail\": \"" + email + "\"," +
        "\"Message\": \"This event was generated by example code.\"" +
        "\"UtcTime\": \"Now.\"" +
        "}"

    val entry = PutEventsRequestEntry {
        source = "ExampleSource"
        detail = json
        detailType = "ExampleType"
    }
```

```
    val eventsRequest = PutEventsRequest {
        this.entries = listOf(entry)
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putEvents(eventsRequest)
    }
}
```

- Para obter detalhes da API, consulte a PutEventsreferência da API AWSSDK for Kotlin.

Cenários para EventBridge usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon EventBridge com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie e acione uma regra na Amazon EventBridge usando um AWS SDK
- Comece a usar EventBridge regras e metas usando um AWS SDK

Crie e acione uma regra na Amazon EventBridge usando um AWS SDK

O exemplo de código a seguir mostra como criar e acionar uma regra na Amazon EventBridge.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chamar as funções na ordem correta.

```
require "aws-sdk-sns"
require "aws-sdk-iam"
require "aws-sdk-cloudwatchevents"
require "aws-sdk-ec2"
require "aws-sdk-cloudwatch"
require "aws-sdk-cloudwatchlogs"
require "securerandom"
```

Verifica se o tópico do Amazon Simple Notification Service (Amazon SNS) existe dentre aqueles fornecidos para essa função.

```
# Checks whether the specified Amazon SNS
# topic exists among those provided to this function.
# This is a helper function that is called by the topic_exists? function.
#
# @param topics [Array] An array of Aws::SNS::Types::Topic objects.
# @param topic_arn [String] The ARN of the topic to find.
# @return [Boolean] true if the topic ARN was found; otherwise, false.
# @example
#   sns_client = Aws::SNS::Client.new(region: 'us-east-1')
#   response = sns_client.list_topics
#   if topic_found?(
#     response.topics,
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
#   )
#     puts 'Topic found.'
#   end

def topic_found?(topics, topic_arn)
  topics.each do |topic|
    return true if topic.topic_arn == topic_arn
  end
  return false
end
```

Verifica se o tópico especificado existe dentre aqueles disponíveis para o chamador no Amazon SNS.

```
# Checks whether the specified topic exists among those available to the
# caller in Amazon SNS.
```

```
#
# @param sns_client [Aws::SNS::Client] An initialized Amazon SNS client.
# @param topic_arn [String] The ARN of the topic to find.
# @return [Boolean] true if the topic ARN was found; otherwise, false.
# @example
#   exit 1 unless topic_exists?(
#     Aws::SNS::Client.new(region: 'us-east-1'),
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
#   )
def topic_exists?(sns_client, topic_arn)
  puts "Searching for topic with ARN '#{topic_arn}'..."
  response = sns_client.list_topics
  if response.topics.count.positive?
    if topic_found?(response.topics, topic_arn)
      puts "Topic found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.topics.count.positive?
        if topic_found?(response.topics, topic_arn)
          puts "Topic found."
          return true
        end
      end
    end
  end
  puts "Topic not found."
  return false
rescue StandardError => e
  puts "Topic not found: #{e.message}"
  return false
end
```

Crie um tópico no Amazon SNS e, em seguida, assine um endereço de e-mail para receber notificações sobre esse tópico.

```
# Creates a topic in Amazon SNS
# and then subscribes an email address to receive notifications to that topic.
#
# @param sns_client [Aws::SNS::Client] An initialized Amazon SNS client.
# @param topic_name [String] The name of the topic to create.
```

```
# @param email_address [String] The email address of the recipient to notify.
# @return [String] The ARN of the topic that was created.
# @example
#   puts create_topic(
#     Aws::SNS::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-topic',
#     'mary@example.com'
#   )
def create_topic(sns_client, topic_name, email_address)
  puts "Creating the topic named '#{topic_name}'..."
  topic_response = sns_client.create_topic(name: topic_name)
  puts "Topic created with ARN '#{topic_response.topic_arn}'."
  subscription_response = sns_client.subscribe(
    topic_arn: topic_response.topic_arn,
    protocol: "email",
    endpoint: email_address,
    return_subscription_arn: true
  )
  puts "Subscription created with ARN " \
    "'#{subscription_response.subscription_arn}'. Have the owner of the " \
    "email address '#{email_address}' check their inbox in a few minutes " \
    "and confirm the subscription to start receiving notification emails."
  return topic_response.topic_arn
rescue StandardError => e
  puts "Error creating or subscribing to topic: #{e.message}"
  return "Error"
end
```

Verifique se a função AWS Identity and Access Management (IAM) especificada existe dentre aquelas fornecidas para essa função.

```
# Checks whether the specified AWS Identity and Access Management (IAM)
# role exists among those provided to this function.
# This is a helper function that is called by the role_exists? function.
#
# @param roles [Array] An array of Aws::IAM::Role objects.
# @param role_arn [String] The ARN of the role to find.
# @return [Boolean] true if the role ARN was found; otherwise, false.
# @example
#   iam_client = Aws::IAM::Client.new(region: 'us-east-1')
#   response = iam_client.list_roles
#   if role_found?(
```

```
#     response.roles,
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change'
#   )
#     puts 'Role found.'
#   end
def role_found?(roles, role_arn)
  roles.each do |role|
    return true if role.arn == role_arn
  end
  return false
end
```

Verifique se a função especificada existe dentre aquelas disponíveis para o chamador no IAM.

```
# Checks whether the specified role exists among those available to the
# caller in AWS Identity and Access Management (IAM).
#
# @param iam_client [Aws::IAM::Client] An initialized IAM client.
# @param role_arn [String] The ARN of the role to find.
# @return [Boolean] true if the role ARN was found; otherwise, false.
# @example
#   exit 1 unless role_exists?(
#     Aws::IAM::Client.new(region: 'us-east-1'),
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change'
#   )
def role_exists?(iam_client, role_arn)
  puts "Searching for role with ARN '#{role_arn}'..."
  response = iam_client.list_roles
  if response.roles.count.positive?
    if role_found?(response.roles, role_arn)
      puts "Role found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.roles.count.positive?
        if role_found?(response.roles, role_arn)
          puts "Role found."
          return true
        end
      end
    end
```

```
  end
  puts "Role not found."
  return false
rescue StandardError => e
  puts "Role not found: #{e.message}"
  return false
end
```

Criar uma função no IAM.

```
# Creates a role in AWS Identity and Access Management (IAM).
# This role is used by a rule in Amazon EventBridge to allow
# that rule to operate within the caller's account.
# This role is designed to be used specifically by this code example.
#
# @param iam_client [Aws::IAM::Client] An initialized IAM client.
# @param role_name [String] The name of the role to create.
# @return [String] The ARN of the role that was created.
# @example
#   puts create_role(
#     Aws::IAM::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change'
#   )
def create_role(iam_client, role_name)
  puts "Creating the role named '#{role_name}'..."
  response = iam_client.create_role(
    assume_role_policy_document: {
      'Version': "2012-10-17",
      'Statement': [
        {
          'Sid': "",
          'Effect': "Allow",
          'Principal': {
            'Service': "events.amazonaws.com"
          },
          'Action': "sts:AssumeRole"
        }
      ]
    }.to_json,
    path: "/",
    role_name: role_name
  )
```

```
  puts "Role created with ARN '#{response.role.arn}'."
  puts "Adding access policy to role..."
  iam_client.put_role_policy(
    policy_document: {
      'Version': "2012-10-17",
      'Statement': [
        {
          'Sid': "CloudWatchEventsFullAccess",
          'Effect': "Allow",
          'Resource': "*",
          'Action': "events:*"
        },
        {
          'Sid': "IAMPassRoleForCloudWatchEvents",
          'Effect': "Allow",
          'Resource': "arn:aws:iam::*:role/AWS_Events_Invoke_Targets",
          'Action': "iam:PassRole"
        }
      ]
    }.to_json,
    policy_name: "CloudWatchEventsPolicy",
    role_name: role_name
  )
  puts "Access policy added to role."
  return response.role.arn
rescue StandardError => e
  puts "Error creating role or adding policy to it: #{e.message}"
  puts "If the role was created, you must add the access policy " \
    "to the role yourself, or delete the role yourself and try again."
  return "Error"
end
```

Verifica se a EventBridge regra especificada existe entre as fornecidas para essa função.

```
# Checks whether the specified Amazon EventBridge rule exists among
# those provided to this function.
# This is a helper function that is called by the rule_exists? function.
#
# @param rules [Array] An array of Aws::CloudWatchEvents::Types::Rule objects.
# @param rule_arn [String] The name of the rule to find.
# @return [Boolean] true if the name of the rule was found; otherwise, false.
# @example
```

```
#   cloudwatchevents_client = Aws::CloudWatch::Client.new(region: 'us-east-1')
#   response = cloudwatchevents_client.list_rules
#   if rule_found?(response.rules, 'aws-doc-sdk-examples-ec2-state-change')
#     puts 'Rule found.'
#   end
def rule_found?(rules, rule_name)
  rules.each do |rule|
    return true if rule.name == rule_name
  end
  return false
end
```

Verifica se a regra especificada existe entre as disponíveis para o chamador. EventBridge

```
# Checks whether the specified rule exists among those available to the
# caller in Amazon EventBridge.
#
# @param cloudwatchevents_client [Aws::CloudWatchEvents::Client]
#   An initialized Amazon EventBridge client.
# @param rule_name [String] The name of the rule to find.
# @return [Boolean] true if the rule name was found; otherwise, false.
# @example
#   exit 1 unless rule_exists?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1')
#     'aws-doc-sdk-examples-ec2-state-change'
#   )
def rule_exists?(cloudwatchevents_client, rule_name)
  puts "Searching for rule with name '#{rule_name}'..."
  response = cloudwatchevents_client.list_rules
  if response.rules.count.positive?
    if rule_found?(response.rules, rule_name)
      puts "Rule found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.rules.count.positive?
        if rule_found?(response.rules, rule_name)
          puts "Rule found."
          return true
        end
      end
```

```
    end
  end
  puts "Rule not found."
  return false
rescue StandardError => e
  puts "Rule not found: #{e.message}"
  return false
end
```

Crie uma regra em EventBridge.

```
# Creates a rule in Amazon EventBridge.
# This rule is triggered whenever an available instance in
# Amazon EC2 changes to the specified state.
# This rule is designed to be used specifically by this code example.
#
# Prerequisites:
#
# - A role in AWS Identity and Access Management (IAM) that is designed
#   to be used specifically by this code example.
# - A topic in Amazon SNS.
#
# @param cloudwatchevents_client [Aws::CloudWatchEvents::Client]
#   An initialized Amazon EventBridge client.
# @param rule_name [String] The name of the rule to create.
# @param rule_description [String] Some description for this rule.
# @param instance_state [String] The state that available instances in
#   Amazon EC2 must change to, to
#   trigger this rule.
# @param role_arn [String] The Amazon Resource Name (ARN) of the IAM role.
# @param target_id [String] Some identifying string for the rule's target.
# @param topic_arn [String] The ARN of the Amazon SNS topic.
# @return [Boolean] true if the rule was created; otherwise, false.
# @example
#   exit 1 unless rule_created?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change',
#     'Triggers when any available EC2 instance starts.',
#     'running',
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change',
#     'sns-topic',
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
```

```
#   )
def rule_created?(
  cloudwatchevents_client,
  rule_name,
  rule_description,
  instance_state,
  role_arn,
  target_id,
  topic_arn
)
  puts "Creating rule with name '#{rule_name}'..."
  put_rule_response = cloudwatchevents_client.put_rule(
    name: rule_name,
    description: rule_description,
    event_pattern: {
      'source': [
        "aws.ec2"
      ],
      'detail-type': [
        "EC2 Instance State-change Notification"
      ],
      'detail': {
        'state': [
          instance_state
        ]
      }
    }.to_json,
    state: "ENABLED",
    role_arn: role_arn
  )
  puts "Rule created with ARN '#{put_rule_response.rule_arn}'."

  put_targets_response = cloudwatchevents_client.put_targets(
    rule: rule_name,
    targets: [
      {
        id: target_id,
        arn: topic_arn
      }
    ]
  )
  if put_targets_response.key?(:failed_entry_count) &&
      put_targets_response.failed_entry_count > 0
    puts "Error(s) adding target to rule:"
```

```
    put_targets_response.failed_entries.each do |failure|
      puts failure.error_message
    end
    return false
  else
    return true
  end
rescue StandardError => e
  puts "Error creating rule or adding target to rule: #{e.message}"
  puts "If the rule was created, you must add the target " \
    "to the rule yourself, or delete the rule yourself and try again."
  return false
end
```

Verifique se o grupo de registros especificado existe entre aqueles disponíveis para o chamador no Amazon CloudWatch Logs.

```
# Checks to see whether the specified log group exists among those available
# to the caller in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group to find.
# @return [Boolean] true if the log group name was found; otherwise, false.
# @example
#   exit 1 unless log_group_exists?(
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def log_group_exists?(cloudwatchlogs_client, log_group_name)
  puts "Searching for log group with name '#{log_group_name}'..."
  response = cloudwatchlogs_client.describe_log_groups(
    log_group_name_prefix: log_group_name
  )
  if response.log_groups.count.positive?
    response.log_groups.each do |log_group|
      if log_group.log_group_name == log_group_name
        puts "Log group found."
        return true
      end
    end
  end
```

```
  puts "Log group not found."
  return false
rescue StandardError => e
  puts "Log group not found: #{e.message}"
  return false
end
```

Crie um grupo de CloudWatch registros em Registros.

```
# Creates a log group in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group to create.
# @return [Boolean] true if the log group name was created; otherwise, false.
# @example
#   exit 1 unless log_group_created?(
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def log_group_created?(cloudwatchlogs_client, log_group_name)
  puts "Attempting to create log group with the name '#{log_group_name}'..."
  cloudwatchlogs_client.create_log_group(log_group_name: log_group_name)
  puts "Log group created."
  return true
rescue StandardError => e
  puts "Error creating log group: #{e.message}"
  return false
end
```

Grave um evento em um stream de CloudWatch registros em Logs.

```
# Writes an event to a log stream in Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - A log group in Amazon CloudWatch Logs.
# - A log stream within the log group.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
```

```
# @param log_group_name [String] The name of the log group.
# @param log_stream_name [String] The name of the log stream within
#   the log group.
# @param message [String] The message to write to the log stream.
# @param sequence_token [String] If available, the sequence token from the
#   message that was written immediately before this message. This sequence
#   token is returned by Amazon CloudWatch Logs whenever you programmatically
#   write a message to the log stream.
# @return [String] The sequence token that is returned by
#   Amazon CloudWatch Logs after successfully writing the message to the
#   log stream.
# @example
#   puts log_event(
#     Aws::EC2::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#     '2020/11/19/53f985be-199f-408e-9a45-fc242df41fEX',
#     "Instance 'i-033c48ef067af3dEX' restarted.",
#     '49542672486831074009579604567656788214806863282469607 3EX'
#   )
def log_event(
  cloudwatchlogs_client,
  log_group_name,
  log_stream_name,
  message,
  sequence_token
)
  puts "Attempting to log '#{message}' to log stream '#{log_stream_name}'..."
  event = {
    log_group_name: log_group_name,
    log_stream_name: log_stream_name,
    log_events: [
      {
        timestamp: (Time.now.utc.to_f.round(3) * 1_000).to_i,
        message: message
      }
    ]
  }
  unless sequence_token.empty?
    event[:sequence_token] = sequence_token
  end

  response = cloudwatchlogs_client.put_log_events(event)
  puts "Message logged."
  return response.next_sequence_token
```

```
rescue StandardError => e
  puts "Message not logged: #{e.message}"
end
```

Reinicie uma instância do Amazon Elastic Compute Cloud (Amazon EC2) e adicione informações sobre a atividade relacionada a um stream de log no Logs. CloudWatch

```
# Restarts an Amazon EC2 instance
# and adds information about the related activity to a log stream
# in Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - The Amazon EC2 instance to restart.
# - The log group in Amazon CloudWatch Logs to add related activity
#   information to.
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client]
#   An initialized Amazon CloudWatch Logs client.
# @param instance_id [String] The ID of the instance.
# @param log_group_name [String] The name of the log group.
# @return [Boolean] true if the instance was restarted and the information
#   was written to the log stream; otherwise, false.
# @example
#   exit 1 unless instance_restarted?(
#     Aws::EC2::Client.new(region: 'us-east-1'),
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'i-033c48ef067af3dEX',
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def instance_restarted?(
  ec2_client,
  cloudwatchlogs_client,
  instance_id,
  log_group_name
)
  log_stream_name = "#{Time.now.year}/#{Time.now.month}/#{Time.now.day}/" \
    "#{SecureRandom.uuid}"
  cloudwatchlogs_client.create_log_stream(
    log_group_name: log_group_name,
```

```
    log_stream_name: log_stream_name
  )
  sequence_token = ""

  puts "Attempting to stop the instance with the ID '#{instance_id}'. " \
    "This might take a few minutes..."
  ec2_client.stop_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_stopped, instance_ids: [instance_id])
  puts "Instance stopped."
  sequence_token = log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Instance '#{instance_id}' stopped.",
    sequence_token
  )

  puts "Attempting to restart the instance. This might take a few minutes..."
  ec2_client.start_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_running, instance_ids: [instance_id])
  puts "Instance restarted."
  sequence_token = log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Instance '#{instance_id}' restarted.",
    sequence_token
  )

  return true
rescue StandardError => e
  puts "Error creating log stream or stopping or restarting the instance: " \
    "#{e.message}"
  log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Error stopping or starting instance '#{instance_id}': #{e.message}",
    sequence_token
  )
  return false
end
```

Exibir informações sobre a atividade de uma regra em EventBridge.

```
# Displays information about activity for a rule in Amazon EventBridge.
#
# Prerequisites:
#
# - A rule in Amazon EventBridge.
#
# @param cloudwatch_client [Amazon::CloudWatch::Client] An initialized
#   Amazon CloudWatch client.
# @param rule_name [String] The name of the rule.
# @param start_time [Time] The timestamp that determines the first datapoint
#   to return. Can also be expressed as DateTime, Date, Integer, or String.
# @param end_time [Time] The timestamp that determines the last datapoint
#   to return. Can also be expressed as DateTime, Date, Integer, or String.
# @param period [Integer] The interval, in seconds, to check for activity.
# @example
#   display_rule_activity(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change',
#     Time.now - 600, # Start checking from 10 minutes ago.
#     Time.now, # Check up until now.
#     60 # Check every minute during those 10 minutes.
#   )
def display_rule_activity(
  cloudwatch_client,
  rule_name,
  start_time,
  end_time,
  period
)
  puts "Attempting to display rule activity..."
  response = cloudwatch_client.get_metric_statistics(
    namespace: "AWS/Events",
    metric_name: "Invocations",
    dimensions: [
      {
        name: "RuleName",
        value: rule_name
      }
    ],
    start_time: start_time,
    end_time: end_time,
    period: period,
```

```
    statistics: ["Sum"],
    unit: "Count"
  )

  if response.key?(:datapoints) && response.datapoints.count.positive?
    puts "The event rule '#{rule_name}' was triggered:"
    response.datapoints.each do |datapoint|
      puts "  #{datapoint.sum} time(s) at #{datapoint.timestamp}"
    end
  else
    puts "The event rule '#{rule_name}' was not triggered during the " \
      "specified time period."
  end
rescue StandardError => e
  puts "Error getting information about event rule activity: #{e.message}"
end
```

Exibir informações de registro de todos os fluxos de registros em um grupo de CloudWatch registros de registros.

```
# Displays log information for all of the log streams in a log group in
# Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - A log group in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Amazon::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group.
# @example
#   display_log_data(
#     Amazon::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def display_log_data(cloudwatchlogs_client, log_group_name)
  puts "Attempting to display log stream data for the log group " \
    "named '#{log_group_name}'..."
  describe_log_streams_response = cloudwatchlogs_client.describe_log_streams(
    log_group_name: log_group_name,
    order_by: "LastEventTime",
    descending: true
```

```
  )
  if describe_log_streams_response.key?(:log_streams) &&
      describe_log_streams_response.log_streams.count.positive?
    describe_log_streams_response.log_streams.each do |log_stream|
      get_log_events_response = cloudwatchlogs_client.get_log_events(
        log_group_name: log_group_name,
        log_stream_name: log_stream.log_stream_name
      )
      puts "\nLog messages for '#{log_stream.log_stream_name}':"
      puts "-" * (log_stream.log_stream_name.length + 20)
      if get_log_events_response.key?(:events) &&
          get_log_events_response.events.count.positive?
        get_log_events_response.events.each do |event|
          puts event.message
        end
      else
        puts "No log messages for this log stream."
      end
    end
  end
rescue StandardError => e
  puts "Error getting information about the log streams or their messages: " \
    "#{e.message}"
end
```

Exibir um lembrete para o chamador limpar manualmente todos os recursos AWS associados dos quais ele não precisa mais.

```
# Displays a reminder to the caller to manually clean up any associated
# AWS resources that they no longer need.
#
# @param topic_name [String] The name of the Amazon SNS topic.
# @param role_name [String] The name of the IAM role.
# @param rule_name [String] The name of the Amazon EventBridge rule.
# @param log_group_name [String] The name of the Amazon CloudWatch Logs log
 group.
# @param instance_id [String] The ID of the Amazon EC2 instance.
# @example
#   manual_cleanup_notice(
#     'aws-doc-sdk-examples-topic',
#     'aws-doc-sdk-examples-cloudwatch-events-rule-role',
```

```
#     'aws-doc-sdk-examples-ec2-state-change',
#     'aws-doc-sdk-examples-cloudwatch-log',
#     'i-033c48ef067af3dEX'
#   )
def manual_cleanup_notice(
  topic_name, role_name, rule_name, log_group_name, instance_id
)
  puts "-" * 10
  puts "Some of the following AWS resources might still exist in your account."
  puts "If you no longer want to use this code example, then to clean up"
  puts "your AWS account and avoid unexpected costs, you might want to"
  puts "manually delete any of the following resources if they exist:"
  puts "- The Amazon SNS topic named '#{topic_name}'."
  puts "- The IAM role named '#{role_name}'."
  puts "- The Amazon EventBridge rule named '#{rule_name}'."
  puts "- The Amazon CloudWatch Logs log group named '#{log_group_name}'."
  puts "- The Amazon EC2 instance with the ID '#{instance_id}'."
end

# Example usage:
def run_me
  # Properties for the Amazon SNS topic.
  topic_name = "aws-doc-sdk-examples-topic"
  email_address = "mary@example.com"
  # Properties for the IAM role.
  role_name = "aws-doc-sdk-examples-cloudwatch-events-rule-role"
  # Properties for the Amazon EventBridge rule.
  rule_name = "aws-doc-sdk-examples-ec2-state-change"
  rule_description = "Triggers when any available EC2 instance starts."
  instance_state = "running"
  target_id = "sns-topic"
  # Properties for the Amazon EC2 instance.
  instance_id = "i-033c48ef067af3dEX"
  # Properties for displaying the event rule's activity.
  start_time = Time.now - 600 # Go back over the past 10 minutes
                              # (10 minutes * 60 seconds = 600 seconds).
  end_time = Time.now
  period = 60 # Look back every 60 seconds over the past 10 minutes.
  # Properties for the Amazon CloudWatch Logs log group.
  log_group_name = "aws-doc-sdk-examples-cloudwatch-log"
  # AWS service clients for this code example.
  region = "us-east-1"
  sts_client = Aws::STS::Client.new(region: region)
  sns_client = Aws::SNS::Client.new(region: region)
```

```
iam_client = Aws::IAM::Client.new(region: region)
cloudwatchevents_client = Aws::CloudWatchEvents::Client.new(region: region)
ec2_client = Aws::EC2::Client.new(region: region)
cloudwatch_client = Aws::CloudWatch::Client.new(region: region)
cloudwatchlogs_client = Aws::CloudWatchLogs::Client.new(region: region)

# Get the caller's account ID for use in forming
# Amazon Resource Names (ARNs) that this code relies on later.
account_id = sts_client.get_caller_identity.account

# If the Amazon SNS topic doesn't exist, create it.
topic_arn = "arn:aws:sns:#{region}:#{account_id}:#{topic_name}"
unless topic_exists?(sns_client, topic_arn)
  topic_arn = create_topic(sns_client, topic_name, email_address)
  if topic_arn == "Error"
    puts "Could not create the Amazon SNS topic correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
    exit 1
  end
end

# If the IAM role doesn't exist, create it.
role_arn = "arn:aws:iam::#{account_id}:role/#{role_name}"
unless role_exists?(iam_client, role_arn)
  role_arn = create_role(iam_client, role_name)
  if role_arn == "Error"
    puts "Could not create the IAM role correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# If the Amazon EventBridge rule doesn't exist, create it.
unless rule_exists?(cloudwatchevents_client, rule_name)
  unless rule_created?(
    cloudwatchevents_client,
    rule_name,
    rule_description,
    instance_state,
    role_arn,
    target_id,
```

```
    topic_arn
  )
    puts "Could not create the Amazon EventBridge rule correctly. " \
      "Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# If the Amazon CloudWatch Logs log group doesn't exist, create it.
unless log_group_exists?(cloudwatchlogs_client, log_group_name)
  unless log_group_created?(cloudwatchlogs_client, log_group_name)
    puts "Could not create the Amazon CloudWatch Logs log group " \
    "correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# Restart the Amazon EC2 instance, which triggers the rule.
unless instance_restarted?(
  ec2_client,
  cloudwatchlogs_client,
  instance_id,
  log_group_name
)
  puts "Could not restart the instance to trigger the rule. " \
    "Continuing anyway to show information about the rule and logs..."
end

# Display how many times the rule was triggered over the past 10 minutes.
display_rule_activity(
  cloudwatch_client,
  rule_name,
  start_time,
  end_time,
  period
)

# Display related log data in Amazon CloudWatch Logs.
display_log_data(cloudwatchlogs_client, log_group_name)
```

```
  # Reminder the caller to clean up any AWS resources that are used
  # by this code example and are no longer needed.
  manual_cleanup_notice(
    topic_name, role_name, rule_name, log_group_name, instance_id
  )
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - PutEvents
  - PutRule

Comece a usar EventBridge regras e metas usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Criar uma regra e adicionar um destino a ela.
- Habilitar e desabilitar regras.
- Listar e atualizar regras e destinos.
- Enviar os eventos e limpar os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public class EventBridgeScenario
{
    /*
```

```
   Before running this .NET code example, set up your development environment,
including your credentials.

   This .NET example performs the following tasks with Amazon EventBridge:
   - Create a rule.
   - Add a target to a rule.
   - Enable and disable rules.
   - List rules and targets.
   - Update rules and targets.
   - Send events.
   - Delete the rule.
   */

   private static ILogger logger = null!;
   private static EventBridgeWrapper _eventBridgeWrapper = null!;
   private static IConfiguration _configuration = null!;

   private static IAmazonIdentityManagementService? _iamClient = null!;
   private static IAmazonSimpleNotificationService? _snsClient = null!;
   private static IAmazonS3 _s3Client = null!;

   static async Task Main(string[] args)
   {
       // Set up dependency injection for Amazon EventBridge.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
           .ConfigureServices((_, services) =>
           services.AddAWSService<IAmazonEventBridge>()
           .AddAWSService<IAmazonIdentityManagementService>()
           .AddAWSService<IAmazonS3>()
           .AddAWSService<IAmazonSimpleNotificationService>()
           .AddTransient<EventBridgeWrapper>()
           )
           .Build();

       _configuration = new ConfigurationBuilder()
           .SetBasePath(Directory.GetCurrentDirectory())
           .AddJsonFile("settings.json") // Load settings from .json file.
           .AddJsonFile("settings.local.json",
```

```
                true) // Optionally, load local settings.
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<EventBridgeScenario>();

        ServicesSetup(host);

        string topicArn = "";
        string roleArn = "";

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon EventBridge example scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            roleArn = await CreateRole();

            await CreateBucketWithEventBridgeEvents();

            await AddEventRule(roleArn);

            await ListEventRules();

            topicArn = await CreateSnsTopic();

            var email = await SubscribeToSnsTopic(topicArn);

            await AddSnsTarget(topicArn);

            await ListTargets();

            await ListRulesForTarget(topicArn);

            await UploadS3File(_s3Client);

            await ChangeRuleState(false);

            await GetRuleState();

            await UpdateSnsEventRule(topicArn);

            await ChangeRuleState(true);
```

```
            await UploadS3File(_s3Client);

            await UpdateToCustomRule(topicArn);

            await TriggerCustomRule(email);

            await CleanupResources(topicArn);
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
            await CleanupResources(topicArn);
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("The Amazon EventBridge example scenario is
complete.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _eventBridgeWrapper =
host.Services.GetRequiredService<EventBridgeWrapper>();
        _snsClient =
host.Services.GetRequiredService<IAmazonSimpleNotificationService>();
        _s3Client = host.Services.GetRequiredService<IAmazonS3>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
    }

    /// <summary>
    /// Create a role to be used by EventBridge.
    /// </summary>
    /// <returns>The role Amazon Resource Name (ARN).</returns>
    public static async Task<string> CreateRole()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Creating a role to use with EventBridge and attaching
managed policy AmazonEventBridgeFullAccess.");
```

```
        Console.WriteLine(new string('-', 80));

        var roleName = _configuration["roleName"];

        var assumeRolePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                "\"Effect\": \"Allow\"," +
                                "\"Principal\": {" +
                                $"\"Service\": \"events.amazonaws.com\"" +
                                "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                                "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
                RoleName = roleName
            });

        await _iamClient.AttachRolePolicyAsync(
            new AttachRolePolicyRequest()
            {
                PolicyArn = "arn:aws:iam::aws:policy/
AmazonEventBridgeFullAccess",
                RoleName = roleName
            });
        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        return roleResult.Role.Arn;
    }

    /// <summary>
    /// Create an Amazon Simple Storage Service (Amazon S3) bucket with
 EventBridge events enabled.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateBucketWithEventBridgeEvents()
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine("Creating an S3 bucket with EventBridge events
enabled.");

        var testBucketName = _configuration["testBucketName"];

        var bucketExists = await
Amazon.S3.Util.AmazonS3Util.DoesS3BucketExistV2Async(_s3Client,
            testBucketName);

        if (!bucketExists)
        {
            await _s3Client.PutBucketAsync(new PutBucketRequest()
            {
                BucketName = testBucketName,
                UseClientRegion = true
            });
        }

        await _s3Client.PutBucketNotificationAsync(new
PutBucketNotificationRequest()
        {
            BucketName = testBucketName,
            EventBridgeConfiguration = new EventBridgeConfiguration()
        });

        Console.WriteLine($"\tAdded bucket {testBucketName} with EventBridge
events enabled.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create and upload a file to an S3 bucket to trigger an event.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task UploadS3File(IAmazonS3 s3Client)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Uploading a file to the test bucket. This will trigger
a subscription email.");

        var testBucketName = _configuration["testBucketName"];

        var fileName = $"example_upload_{DateTime.UtcNow.Ticks}.txt";
```

```
        // Create the file if it does not already exist.
        if (!File.Exists(fileName))
        {
            await using StreamWriter sw = File.CreateText(fileName);
            await sw.WriteLineAsync(
                "This is a sample file for testing uploads.");
        }

        await s3Client.PutObjectAsync(new PutObjectRequest()
        {
            FilePath = fileName,
            BucketName = testBucketName
        });

        Console.WriteLine($"\tPress Enter to continue.");
        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create an Amazon Simple Notification Service (Amazon SNS) topic to use as
an EventBridge target.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> CreateSnsTopic()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "Creating an Amazon Simple Notification Service (Amazon SNS) topic
for email subscriptions.");

        var topicName = _configuration["topicName"];

        string topicPolicy = "{" +
                             "\"Version\": \"2012-10-17\"," +
                             "\"Statement\": [{" +
                             "\"Sid\": \"EventBridgePublishTopic\"," +
                             "\"Effect\": \"Allow\"," +
                             "\"Principal\": {" +
                             $"\"Service\": \"events.amazonaws.com\"" +
                             "}," +
                             "\"Resource\": \"*\"," +
```

```
                            "\"Action\": \"sns:Publish\"" +
                            "}]" +
                            "}";

        var topicAttributes = new Dictionary<string, string>()
        {
            { "Policy", topicPolicy }
        };

        var topicResponse = await _snsClient!.CreateTopicAsync(new
CreateTopicRequest()
        {
            Name = topicName,
            Attributes = topicAttributes

        });

        Console.WriteLine($"\tAdded topic {topicName} for email subscriptions.");

        Console.WriteLine(new string('-', 80));

        return topicResponse.TopicArn;
    }

    /// <summary>
    /// Subscribe a user email to an SNS topic.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
    /// <returns>The user's email.</returns>
    private static async Task<string> SubscribeToSnsTopic(string topicArn)
    {
        Console.WriteLine(new string('-', 80));


        string email = "";
        while (string.IsNullOrEmpty(email))
        {
            Console.WriteLine("Enter your email to subscribe to the Amazon SNS
topic:");
            email = Console.ReadLine()!;
        }

        var subscriptions = new List<string>();
```

```
        var paginatedSubscriptions =
_snsClient!.Paginators.ListSubscriptionsByTopic(
            new ListSubscriptionsByTopicRequest()
            {
                TopicArn = topicArn
            });

        // Get the entire list using the paginator.
        await foreach (var subscription in paginatedSubscriptions.Subscriptions)
        {
            subscriptions.Add(subscription.Endpoint);
        }

        if (subscriptions.Contains(email))
        {
            Console.WriteLine($"\tYour email is already subscribed.");
            Console.WriteLine(new string('-', 80));
            return email;
        }

        await _snsClient.SubscribeAsync(new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "email",
            Endpoint = email
        });

        Console.WriteLine($"Use the link in the email you received to confirm
your subscription, then press Enter to continue.");

        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
        return email;
    }

    /// <summary>
    /// Add a rule which triggers when a file is uploaded to an S3 bucket.
    /// </summary>
    /// <param name="roleArn">The ARN of the role used by EventBridge.</param>
    /// <returns>Async task.</returns>
    private static async Task AddEventRule(string roleArn)
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine("Creating an EventBridge event that sends an email when
an Amazon S3 object is created.");

        var eventRuleName = _configuration["eventRuleName"];
        var testBucketName = _configuration["testBucketName"];

        await _eventBridgeWrapper.PutS3UploadRule(roleArn, eventRuleName,
testBucketName);
        Console.WriteLine($"\tAdded event rule {eventRuleName} for bucket
{testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add an SNS target to the rule.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
    /// <returns>Async task.</returns>
    private static async Task AddSnsTarget(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Adding a target to the rule to that sends an email
when the rule is triggered.");

        var eventRuleName = _configuration["eventRuleName"];
        var testBucketName = _configuration["testBucketName"];
        var topicName = _configuration["topicName"];
        await _eventBridgeWrapper.AddSnsTargetToRule(eventRuleName, topicArn);
        Console.WriteLine($"\tAdded event rule {eventRuleName} with Amazon SNS
target {topicName} for bucket {testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List the event rules on the default event bus.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListEventRules()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Current event rules:");
```

```
        var rules = await _eventBridgeWrapper.ListAllRulesForEventBus();
        rules.ForEach(r => Console.WriteLine($"\tRule: {r.Name} Description:
{r.Description} State: {r.State}"));

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Update the event target to use a transform.
    /// </summary>
    /// <param name="topicArn">The SNS topic ARN target to update.</param>
    /// <returns>Async task.</returns>
    private static async Task UpdateSnsEventRule(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Let's update the event target with a transform.");

        var eventRuleName = _configuration["eventRuleName"];
        var testBucketName = _configuration["testBucketName"];

        await
_eventBridgeWrapper.UpdateS3UploadRuleTargetWithTransform(eventRuleName,
topicArn);
        Console.WriteLine($"\tUpdated event rule {eventRuleName} with Amazon SNS
target {topicArn} for bucket {testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Update the rule to use a custom event pattern.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task UpdateToCustomRule(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Updating the event pattern to be triggered by a custom
event instead.");

        var eventRuleName = _configuration["eventRuleName"];

        await _eventBridgeWrapper.UpdateCustomEventPattern(eventRuleName);
```

```
        Console.WriteLine($"\tUpdated event rule {eventRuleName} to custom
pattern.");
        await
_eventBridgeWrapper.UpdateCustomRuleTargetWithTransform(eventRuleName,
            topicArn);

        Console.WriteLine($"\tUpdated event target {topicArn}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Send rule events for a custom rule using the user's email address.
    /// </summary>
    /// <param name="email">The email address to include.</param>
    /// <returns>Async task.</returns>
    private static async Task TriggerCustomRule(string email)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Sending an event to trigger the rule. This will
trigger a subscription email.");

        await _eventBridgeWrapper.PutCustomEmailEvent(email);

        Console.WriteLine($"\tEvents have been sent. Press Enter to continue.");
        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List all of the targets for a rule.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListTargets()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("List all of the targets for a particular rule.");

        var eventRuleName = _configuration["eventRuleName"];
        var targets = await
_eventBridgeWrapper.ListAllTargetsOnRule(eventRuleName);
        targets.ForEach(t => Console.WriteLine($"\tTarget: {t.Arn} Id: {t.Id}
Input: {t.Input}"));
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List all of the rules for a particular target.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
    /// <returns>Async task.</returns>
    private static async Task ListRulesForTarget(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("List all of the rules for a particular target.");

        var rules = await _eventBridgeWrapper.ListAllRuleNamesByTarget(topicArn);
        rules.ForEach(r => Console.WriteLine($"\tRule: {r}"));

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Enable or disable a particular rule.
    /// </summary>
    /// <param name="isEnabled">True to enable the rule, otherwise false.</param>
    /// <returns>Async task.</returns>
    private static async Task ChangeRuleState(bool isEnabled)
    {
        Console.WriteLine(new string('-', 80));
        var eventRuleName = _configuration["eventRuleName"];

        if (!isEnabled)
        {
            Console.WriteLine($"Disabling the rule: {eventRuleName}");
            await _eventBridgeWrapper.DisableRuleByName(eventRuleName);
        }
        else
        {
            Console.WriteLine($"Enabling the rule: {eventRuleName}");
            await _eventBridgeWrapper.EnableRuleByName(eventRuleName);
        }

        Console.WriteLine(new string('-', 80));
    }
```

```
    /// <summary>
    /// Get the current state of the rule.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetRuleState()
    {
        Console.WriteLine(new string('-', 80));
        var eventRuleName = _configuration["eventRuleName"];

        var state = await
_eventBridgeWrapper.GetRuleStateByRuleName(eventRuleName);
        Console.WriteLine($"Rule {eventRuleName} is in current state {state}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic to clean up.</param>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        var eventRuleName = _configuration["eventRuleName"];
        if (GetYesNoResponse($"\tDelete all targets and event rule
{eventRuleName}? (y/n)"))
        {
            Console.WriteLine($"\tRemoving all targets from the event rule.");
            await _eventBridgeWrapper.RemoveAllTargetsFromRule(eventRuleName);

            Console.WriteLine($"\tDeleting event rule.");
            await _eventBridgeWrapper.DeleteRuleByName(eventRuleName);
        }

        var topicName = _configuration["topicName"];
        if (GetYesNoResponse($"\tDelete Amazon SNS subscription topic
{topicName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting topic.");
            await _snsClient!.DeleteTopicAsync(new DeleteTopicRequest()
            {
```

```
                TopicArn = topicArn
            });
        }

        var bucketName = _configuration["testBucketName"];
        if (GetYesNoResponse($"\tDelete Amazon S3 bucket {bucketName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting bucket.");
            // Delete all objects in the bucket.
            var deleteList = await _s3Client.ListObjectsV2Async(new
 ListObjectsV2Request()
            {
                BucketName = bucketName
            });
            await _s3Client.DeleteObjectsAsync(new DeleteObjectsRequest()
            {
                BucketName = bucketName,
                Objects = deleteList.S3Objects
                    .Select(o => new KeyVersion { Key = o.Key }).ToList()
            });
            // Now delete the bucket.
            await _s3Client.DeleteBucketAsync(new DeleteBucketRequest()
            {
                BucketName = bucketName
            });
        }

        var roleName = _configuration["roleName"];
        if (GetYesNoResponse($"\tDelete role {roleName}? (y/n)"))
        {
            Console.WriteLine($"\tDetaching policy and deleting role.");

            await _iamClient!.DetachRolePolicyAsync(new DetachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = "arn:aws:iam::aws:policy/
AmazonEventBridgeFullAccess",
            });

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = roleName
            });
        }
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

Crie uma classe que envolva as EventBridge operações.

```
/// <summary>
/// Wrapper for Amazon EventBridge operations.
/// </summary>
public class EventBridgeWrapper
{
    private readonly IAmazonEventBridge _amazonEventBridge;
    private readonly ILogger<EventBridgeWrapper> _logger;

    /// <summary>
    /// Constructor for the EventBridge wrapper.
    /// </summary>
    /// <param name="amazonEventBridge">The injected EventBridge client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public EventBridgeWrapper(IAmazonEventBridge amazonEventBridge,
 ILogger<EventBridgeWrapper> logger)

    {
        _amazonEventBridge = amazonEventBridge;
```

```
        _logger = logger;
    }

    /// <summary>
    /// Get the state for a rule by the rule name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="eventBusName">The optional name of the event bus. If empty,
uses the default event bus.</param>
    /// <returns>The state of the rule.</returns>
    public async Task<RuleState> GetRuleStateByRuleName(string ruleName, string?
eventBusName = null)
    {
        var ruleResponse = await _amazonEventBridge.DescribeRuleAsync(
            new DescribeRuleRequest()
            {
                Name = ruleName,
                EventBusName = eventBusName
            });
        return ruleResponse.State;
    }

    /// <summary>
    /// Enable a particular rule on an event bus.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableRuleByName(string ruleName)
    {
        var ruleResponse = await _amazonEventBridge.EnableRuleAsync(
            new EnableRuleRequest()
            {
                Name = ruleName
            });
        return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Disable a particular rule on an event bus.
    /// </summary
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DisableRuleByName(string ruleName)
    {
```

```
        var ruleResponse = await _amazonEventBridge.DisableRuleAsync(
            new DisableRuleRequest()
            {
                Name = ruleName
            });
        return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// List the rules on an event bus.
    /// </summary>
    /// <param name="eventBusArn">The optional ARN of the event bus. If empty,
 uses the default event bus.</param>
    /// <returns>The list of rules.</returns>
    public async Task<List<Rule>> ListAllRulesForEventBus(string? eventBusArn =
 null)
    {
        var results = new List<Rule>();
        var request = new ListRulesRequest()
        {
            EventBusName = eventBusArn
        };
        // Get all of the pages of rules.
        ListRulesResponse response;
        do
        {
            response = await _amazonEventBridge.ListRulesAsync(request);
            results.AddRange(response.Rules);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// List all of the targets matching a rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>The list of targets.</returns>
    public async Task<List<Target>> ListAllTargetsOnRule(string ruleName)
    {
        var results = new List<Target>();
        var request = new ListTargetsByRuleRequest()
```

```
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse response;
        do
        {
            response = await _amazonEventBridge.ListTargetsByRuleAsync(request);
            results.AddRange(response.Targets);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// List names of all rules matching a target.
    /// </summary>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <returns>The list of rule names.</returns>
    public async Task<List<string>> ListAllRuleNamesByTarget(string targetArn)
    {
        var results = new List<string>();
        var request = new ListRuleNamesByTargetRequest()
        {
            TargetArn = targetArn
        };
        ListRuleNamesByTargetResponse response;
        do
        {
            response = await
_amazonEventBridge.ListRuleNamesByTargetAsync(request);
            results.AddRange(response.RuleNames);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// Create a new event rule that triggers when an Amazon S3 object is created
in a bucket.
    /// </summary>
```

```
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="ruleName">The name to give the rule.</param>
    /// <param name="bucketName">The name of the bucket to trigger the event.</
param>
    /// <returns>The ARN of the new rule.</returns>
    public async Task<string> PutS3UploadRule(string roleArn, string ruleName,
 string bucketName)
    {
        string eventPattern = "{" +
                                "\"source\": [\"aws.s3\"]," +
                                    "\"detail-type\": [\"Object Created\"]," +
                                    "\"detail\": {" +
                                        "\"bucket\": {" +
                                            "\"name\": [\"" + bucketName + "\"]"
 +
                                        "}" +
                                    "}" +
                                "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Example S3 upload rule for EventBridge",
                RoleArn = roleArn,
                EventPattern = eventPattern
            });

        return response.RuleArn;
    }

    /// <summary>
    /// Update an Amazon S3 object created rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the
 default event bus.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateS3UploadRuleTargetWithTransform(string
 ruleName, string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();
```

```
        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
                InputTransformer = new InputTransformer()
                {
                    InputPathsMap = new Dictionary<string, string>()
                    {
                        {"bucket", "$.detail.bucket.name"},
                        {"time", "$.time"}
                    },
                    InputTemplate = "\"Notification: an object was uploaded to
bucket <bucket> at <time>.\""
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }
        return targetID;
    }

    /// <summary>
    /// Update a custom rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the
default event bus.</param>
```

```
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateCustomRuleTargetWithTransform(string
 ruleName, string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
                InputTransformer = new InputTransformer()
                {
                    InputTemplate = "\"Notification: sample event was received.
\""
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
 {e.ErrorCode}");
            });
        }
        return targetID;
    }

    /// <summary>
    /// Add an event to the event bus that includes an email, message, and time.
    /// </summary>
    /// <param name="email">The email to use in the event detail of the custom
 event.</param>
    /// <returns>True if successful.</returns>
```

```
    public async Task<bool> PutCustomEmailEvent(string email)
    {
        var eventDetail = new
        {
            UserEmail = email,
            Message = "This event was generated by example code.",
            UtcTime = DateTime.UtcNow.ToString("g")
        };
        var response = await _amazonEventBridge.PutEventsAsync(
            new PutEventsRequest()
            {
                Entries = new List<PutEventsRequestEntry>()
                {
                    new PutEventsRequestEntry()
                    {
                        Source = "ExampleSource",
                        Detail = JsonSerializer.Serialize(eventDetail),
                        DetailType = "ExampleType"
                    }
                }
            });

        return response.FailedEntryCount == 0;
    }

    /// <summary>
    /// Update a rule to use a custom defined event pattern.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <returns>The ARN of the updated rule.</returns>
    public async Task<string> UpdateCustomEventPattern(string ruleName)
    {
        string customEventsPattern = "{" +
                                     "\"source\": [\"ExampleSource\"]," +
                                     "\"detail-type\": [\"ExampleType\"]" +
                                     "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Custom test rule",
                EventPattern = customEventsPattern
            });
```

```
        return response.RuleArn;
    }

    /// <summary>
    /// Add an Amazon SNS target topic to a rule.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <param name="targetArn">The ARN of the Amazon SNS target.</param>
    /// <param name="eventBusArn">The optional event bus name, uses default if
empty.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> AddSnsTargetToRule(string ruleName, string
targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        // Create the list of targets and add a new target.
        var targets = new List<Target>
        {
            new Target()
            {
                Arn = targetArn,
                Id = targetID
            }
        };

        // Add the targets to the rule.
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });

        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
```

```
        }

        return targetID;
    }

    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> RemoveAllTargetsFromRule(string ruleName)
    {
        var targetIds = new List<string>();
        var request = new ListTargetsByRuleRequest()
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse targetsResponse;
        do
        {
            targetsResponse = await
_amazonEventBridge.ListTargetsByRuleAsync(request);
            targetIds.AddRange(targetsResponse.Targets.Select(t => t.Id));
            request.NextToken = targetsResponse.NextToken;

        } while (targetsResponse.NextToken is not null);

        var removeResponse = await _amazonEventBridge.RemoveTargetsAsync(
            new RemoveTargetsRequest()
            {
                Rule = ruleName,
                Ids = targetIds
            });

        if (removeResponse.FailedEntryCount > 0)
        {
            removeResponse.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to remove target {e.TargetId}: {e.ErrorMessage},
code {e.ErrorCode}");
            });
        }
```

```
        return removeResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteRuleByName(string ruleName)
    {
        var response = await _amazonEventBridge.DeleteRuleAsync(
            new DeleteRuleRequest()
            {
                Name = ruleName
            });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java code example performs the following tasks:
 *
 * This Java V2 example performs the following tasks with Amazon EventBridge:
 *
 * 1. Creates an AWS Identity and Access Management (IAM) role to use with
 * Amazon EventBridge.
 * 2. Amazon Simple Storage Service (Amazon S3) bucket with EventBridge events
 * enabled.
 * 3. Creates a rule that triggers when an object is uploaded to Amazon S3.
 * 4. Lists rules on the event bus.
 * 5. Creates a new Amazon Simple Notification Service (Amazon SNS) topic and
 * lets the user subscribe to it.
 * 6. Adds a target to the rule that sends an email to the specified topic.
 * 7. Creates an EventBridge event that sends an email when an Amazon S3 object
 * is created.
 * 8. Lists Targets.
 * 9. Lists the rules for the same target.
 * 10. Triggers the rule by uploading a file to the Amazon S3 bucket.
 * 11. Disables a specific rule.
 * 12. Checks and print the state of the rule.
 * 13. Adds a transform to the rule to change the text of the email.
 * 14. Enables a specific rule.
 * 15. Triggers the updated rule by uploading a file to the Amazon S3 bucket.
```

```
 * 16. Updates the rule to be a custom rule pattern.
 * 17. Sending an event to trigger the rule.
 * 18. Cleans up resources.
 *
 */
public class EventbridgeMVP {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException,
 IOException {
        final String usage = """

                Usage:
                    <roleName> <bucketName> <topicName> <eventRuleName>

                Where:
                    roleName - The name of the role to create.
                    bucketName - The Amazon Simple Storage Service (Amazon S3)
 bucket name to create.
                    topicName - The name of the Amazon Simple Notification
 Service (Amazon SNS) topic to create.
                    eventRuleName - The Amazon EventBridge rule name to create.
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String polJSON = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": \"events.amazonaws.com\"" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        Scanner sc = new Scanner(System.in);
        String roleName = args[0];
        String bucketName = args[1];
```

```
        String topicName = args[2];
        String eventRuleName = args[3];

        Region region = Region.US_EAST_1;
        EventBridgeClient eventBrClient = EventBridgeClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        Region regionGl = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(regionGl)
                .build();

        SnsClient snsClient = SnsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon EventBridge example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out
                .println("1. Create an AWS Identity and Access Management (IAM)
role to use with Amazon EventBridge.");
        String roleArn = createIAMRole(iam, roleName, polJSON);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create an S3 bucket with EventBridge events
enabled.");
        if (checkBucket(s3Client, bucketName)) {
            System.out.println("Bucket " + bucketName + " already exists. Ending
this scenario.");
            System.exit(1);
        }

        createBucket(s3Client, bucketName);
        Thread.sleep(3000);
```

```
        setBucketNotification(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Create a rule that triggers when an object is
uploaded to Amazon S3.");
        Thread.sleep(10000);
        addEventRule(eventBrClient, roleArn, bucketName, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. List rules on the event bus.");
        listRules(eventBrClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create a new SNS topic for testing and let the
user subscribe to the topic.");
        String topicArn = createSnsTopic(snsClient, topicName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Add a target to the rule that sends an email to
the specified topic.");
        System.out.println("Enter your email to subscribe to the Amazon SNS
topic:");
        String email = sc.nextLine();
        subEmail(snsClient, topicArn, email);
        System.out.println(
                "Use the link in the email you received to confirm your
subscription. Then, press Enter to continue.");
        sc.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Create an EventBridge event that sends an email
when an Amazon S3 object is created.");
        addSnsEventRule(eventBrClient, eventRuleName, topicArn, topicName,
eventRuleName, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 8. List Targets.");
        listTargets(eventBrClient, eventRuleName);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 9. List the rules for the same target.");
        listTargetRules(eventBrClient, topicArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 10. Trigger the rule by uploading a file to the S3
bucket.");
        System.out.println("Press Enter to continue.");
        sc.nextLine();
        uploadTextFiletoS3(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Disable a specific rule.");
        changeRuleState(eventBrClient, eventRuleName, false);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Check and print the state of the rule.");
        checkRule(eventBrClient, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Add a transform to the rule to change the text of
the email.");
        updateSnsEventRule(eventBrClient, topicArn, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Enable a specific rule.");
        changeRuleState(eventBrClient, eventRuleName, true);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 15. Trigger the updated rule by uploading a file to
the S3 bucket.");
        System.out.println("Press Enter to continue.");
        sc.nextLine();
        uploadTextFiletoS3(s3Client, bucketName);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println(" 16. Update the rule to be a custom rule pattern.");
        updateToCustomRule(eventBrClient, eventRuleName);
        System.out.println("Updated event rule " + eventRuleName + " to use a
custom pattern.");
        updateCustomRuleTargetWithTransform(eventBrClient, topicArn,
eventRuleName);
        System.out.println("Updated event target " + topicArn + ".");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Sending an event to trigger the rule. This will
trigger a subscription email.");
        triggerCustomRule(eventBrClient, email);
        System.out.println("Events have been sent. Press Enter to continue.");
        sc.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Clean up resources.");
        System.out.println("Do you want to clean up resources (y/n)");
        String ans = sc.nextLine();
        if (ans.compareTo("y") == 0) {
            cleanupResources(eventBrClient, snsClient, s3Client, iam, topicArn,
eventRuleName, bucketName, roleName);
        } else {
            System.out.println("The resources will not be cleaned up. ");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Amazon EventBridge example scenario has
successfully completed.");
        System.out.println(DASHES);
    }

    public static void cleanupResources(EventBridgeClient eventBrClient,
SnsClient snsClient, S3Client s3Client,
            IamClient iam, String topicArn, String eventRuleName, String
bucketName, String roleName) {
        System.out.println("Removing all targets from the event rule.");
        deleteTargetsFromRule(eventBrClient, eventRuleName);
        deleteRuleByName(eventBrClient, eventRuleName);
        deleteSNSTopic(snsClient, topicArn);
```

```
        deleteS3Bucket(s3Client, bucketName);
        deleteRole(iam, roleName);
    }

    public static void deleteRole(IamClient iam, String roleName) {
        String policyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess";
        DetachRolePolicyRequest policyRequest = DetachRolePolicyRequest.builder()
                .policyArn(policyArn)
                .roleName(roleName)
                .build();

        iam.detachRolePolicy(policyRequest);
        System.out.println("Successfully detached policy " + policyArn + " from
role " + roleName);

        // Delete the role.
        DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                .roleName(roleName)
                .build();

        iam.deleteRole(roleRequest);
        System.out.println("*** Successfully deleted " + roleName);
    }

    public static void deleteS3Bucket(S3Client s3Client, String bucketName) {
        // Remove all the objects from the S3 bucket.
        ListObjectsRequest listObjects = ListObjectsRequest.builder()
                .bucket(bucketName)
                .build();

        ListObjectsResponse res = s3Client.listObjects(listObjects);
        List<S3Object> objects = res.contents();
        ArrayList<ObjectIdentifier> toDelete = new ArrayList<>();

        for (S3Object myValue : objects) {
            toDelete.add(ObjectIdentifier.builder()
                    .key(myValue.key())
                    .build());
        }

        DeleteObjectsRequest dor = DeleteObjectsRequest.builder()
                .bucket(bucketName)
                .delete(Delete.builder()
                        .objects(toDelete).build())
```

```
                .build();

        s3Client.deleteObjects(dor);

        // Delete the S3 bucket.
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucketName)
                .build();

        s3Client.deleteBucket(deleteBucketRequest);
        System.out.println("You have deleted the bucket and the objects");
    }

    // Delete the SNS topic.
    public static void deleteSNSTopic(SnsClient snsClient, String topicArn) {
        try {
            DeleteTopicRequest request = DeleteTopicRequest.builder()
                    .topicArn(topicArn)
                    .build();

            DeleteTopicResponse result = snsClient.deleteTopic(request);
            System.out.println("\n\nStatus was " +
result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteRuleByName(EventBridgeClient eventBrClient, String
ruleName) {
        DeleteRuleRequest ruleRequest = DeleteRuleRequest.builder()
                .name(ruleName)
                .build();

        eventBrClient.deleteRule(ruleRequest);
        System.out.println("Successfully deleted the rule");
    }

    public static void deleteTargetsFromRule(EventBridgeClient eventBrClient,
String eventRuleName) {
        // First, get all targets that will be deleted.
        ListTargetsByRuleRequest request = ListTargetsByRuleRequest.builder()
```

```
                .rule(eventRuleName)
                .build();

        ListTargetsByRuleResponse response =
eventBrClient.listTargetsByRule(request);
        List<Target> allTargets = response.targets();

        // Get all targets and delete them.
        for (Target myTarget : allTargets) {
            RemoveTargetsRequest removeTargetsRequest =
RemoveTargetsRequest.builder()
                    .rule(eventRuleName)
                    .ids(myTarget.id())
                    .build();

            eventBrClient.removeTargets(removeTargetsRequest);
            System.out.println("Successfully removed the target");
        }
    }

    public static void triggerCustomRule(EventBridgeClient eventBrClient, String
email) {
        String json = "{" +
                "\"UserEmail\": \"" + email + "\"," +
                "\"Message\": \"This event was generated by example code.\"," +
                "\"UtcTime\": \"Now.\"" +
                "}";

        PutEventsRequestEntry entry = PutEventsRequestEntry.builder()
                .source("ExampleSource")
                .detail(json)
                .detailType("ExampleType")
                .build();

        PutEventsRequest eventsRequest = PutEventsRequest.builder()
                .entries(entry)
                .build();

        eventBrClient.putEvents(eventsRequest);
    }

    public static void updateCustomRuleTargetWithTransform(EventBridgeClient
eventBrClient, String topicArn,
            String ruleName) {
```

```
        String targetId = java.util.UUID.randomUUID().toString();
        InputTransformer inputTransformer = InputTransformer.builder()
                .inputTemplate("\"Notification: sample event was received.\"")
                .build();

        Target target = Target.builder()
                .id(targetId)
                .arn(topicArn)
                .inputTransformer(inputTransformer)
                .build();

        try {
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);
        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void updateToCustomRule(EventBridgeClient eventBrClient, String
 ruleName) {
        String customEventsPattern = "{" +
                "\"source\": [\"ExampleSource\"]," +
                "\"detail-type\": [\"ExampleType\"]" +
                "}";

        PutRuleRequest request = PutRuleRequest.builder()
                .name(ruleName)
                .description("Custom test rule")
                .eventPattern(customEventsPattern)
                .build();

        eventBrClient.putRule(request);
    }

    // Update an Amazon S3 object created rule with a transform on the target.
    public static void updateSnsEventRule(EventBridgeClient eventBrClient, String
 topicArn, String ruleName) {
```

```
        String targetId = java.util.UUID.randomUUID().toString();
        Map<String, String> myMap = new HashMap<>();
        myMap.put("bucket", "$.detail.bucket.name");
        myMap.put("time", "$.time");

        InputTransformer inputTransformer = InputTransformer.builder()
                .inputTemplate("\"Notification: an object was uploaded to bucket
<bucket> at <time>.\"")
                .inputPathsMap(myMap)
                .build();

        Target target = Target.builder()
                .id(targetId)
                .arn(topicArn)
                .inputTransformer(inputTransformer)
                .build();

        try {
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkRule(EventBridgeClient eventBrClient, String
eventRuleName) {
        try {
            DescribeRuleRequest ruleRequest = DescribeRuleRequest.builder()
                    .name(eventRuleName)
                    .build();

            DescribeRuleResponse response =
eventBrClient.describeRule(ruleRequest);
            System.out.println("The state of the rule is " +
response.stateAsString());
```

```
        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void changeRuleState(EventBridgeClient eventBrClient, String
 eventRuleName, Boolean isEnabled) {
        try {
            if (!isEnabled) {
                System.out.println("Disabling the rule: " + eventRuleName);
                DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();

                eventBrClient.disableRule(ruleRequest);
            } else {
                System.out.println("Enabling the rule: " + eventRuleName);
                EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();
                eventBrClient.enableRule(ruleRequest);
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Create and upload a file to an S3 bucket to trigger an event.
    public static void uploadTextFiletoS3(S3Client s3Client, String bucketName)
 throws IOException {
        // Create a unique file name.
        String fileSuffix = new SimpleDateFormat("yyyyMMddHHmmss").format(new
 Date());
        String fileName = "TextFile" + fileSuffix + ".txt";

        File myFile = new File(fileName);
        FileWriter fw = new FileWriter(myFile.getAbsoluteFile());
        BufferedWriter bw = new BufferedWriter(fw);
        bw.write("This is a sample file for testing uploads.");
        bw.close();
```

```
        try {
            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(fileName)
                    .build();

            s3Client.putObject(putOb, RequestBody.fromFile(myFile));

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listTargetRules(EventBridgeClient eventBrClient, String
 topicArn) {
        ListRuleNamesByTargetRequest ruleNamesByTargetRequest =
 ListRuleNamesByTargetRequest.builder()
                .targetArn(topicArn)
                .build();

        ListRuleNamesByTargetResponse response =
 eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest);
        List<String> rules = response.ruleNames();
        for (String rule : rules) {
            System.out.println("The rule name is " + rule);
        }
    }

    public static void listTargets(EventBridgeClient eventBrClient, String
 ruleName) {
        ListTargetsByRuleRequest ruleRequest = ListTargetsByRuleRequest.builder()
                .rule(ruleName)
                .build();

        ListTargetsByRuleResponse res =
 eventBrClient.listTargetsByRule(ruleRequest);
        List<Target> targetsList = res.targets();
        for (Target target: targetsList) {
            System.out.println("Target ARN: "+target.arn());
        }
    }

    // Add a rule which triggers an SNS target when a file is uploaded to an S3
```

```
    // bucket.
    public static void addSnsEventRule(EventBridgeClient eventBrClient, String
ruleName, String topicArn,
            String topicName, String eventRuleName, String bucketName) {
        String targetID = java.util.UUID.randomUUID().toString();
        Target myTarget = Target.builder()
                .id(targetID)
                .arn(topicArn)
                .build();

        List<Target> targets = new ArrayList<>();
        targets.add(myTarget);
        PutTargetsRequest request = PutTargetsRequest.builder()
                .eventBusName(null)
                .targets(targets)
                .rule(ruleName)
                .build();

        eventBrClient.putTargets(request);
        System.out.println("Added event rule " + eventRuleName + " with Amazon
SNS target " + topicName + " for bucket "
                + bucketName + ".");
    }

    public static void subEmail(SnsClient snsClient, String topicArn, String
email) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("email")
                    .endpoint(email)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN: " + result.subscriptionArn() +
"\n\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static void listRules(EventBridgeClient eventBrClient) {
        try {
            ListRulesRequest rulesRequest = ListRulesRequest.builder()
                    .eventBusName("default")
                    .limit(10)
                    .build();

            ListRulesResponse response = eventBrClient.listRules(rulesRequest);
            List<Rule> rules = response.rules();
            for (Rule rule : rules) {
                System.out.println("The rule name is : " + rule.name());
                System.out.println("The rule description is : " +
rule.description());
                System.out.println("The rule state is : " +
rule.stateAsString());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createSnsTopic(SnsClient snsClient, String topicName) {
        String topicPolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Sid\": \"EventBridgePublishTopic\"," +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": \"events.amazonaws.com\"" +
                "}," +
                "\"Resource\": \"*\"," +
                "\"Action\": \"sns:Publish\"" +
                "}]" +
                "}";

        Map<String, String> topicAttributes = new HashMap<>();
        topicAttributes.put("Policy", topicPolicy);
        CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                .name(topicName)
                .attributes(topicAttributes)
                .build();
```

```
        CreateTopicResponse response = snsClient.createTopic(topicRequest);
        System.out.println("Added topic " + topicName + " for email
subscriptions.");
        return response.topicArn();
    }

    // Create a new event rule that triggers when an Amazon S3 object is created
in
    // a bucket.
    public static void addEventRule(EventBridgeClient eventBrClient, String
roleArn, String bucketName,
            String eventRuleName) {
        String pattern = "{\n" +
                "  \"source\": [\"aws.s3\"],\n" +
                "  \"detail-type\": [\"Object Created\"],\n" +
                "  \"detail\": {\n" +
                "    \"bucket\": {\n" +
                "      \"name\": [\"" + bucketName + "\"]\n" +
                "    }\n" +
                "  }\n" +
                "}";

        try {
            PutRuleRequest ruleRequest = PutRuleRequest.builder()
                    .description("Created by using the AWS SDK for Java v2")
                    .name(eventRuleName)
                    .eventPattern(pattern)
                    .roleArn(roleArn)
                    .build();

            PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
            System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Determine if the S3 bucket exists.
    public static Boolean checkBucket(S3Client s3Client, String bucketName) {
        try {
```

```
            HeadBucketRequest headBucketRequest = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.headBucket(headBucketRequest);
            return true;
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        return false;
    }

    // Set the S3 bucket notification configuration.
    public static void setBucketNotification(S3Client s3Client, String
bucketName) {
        try {
            EventBridgeConfiguration eventBridgeConfiguration =
EventBridgeConfiguration.builder()
                    .build();

            NotificationConfiguration configuration =
NotificationConfiguration.builder()
                    .eventBridgeConfiguration(eventBridgeConfiguration)
                    .build();

            PutBucketNotificationConfigurationRequest configurationRequest =
PutBucketNotificationConfigurationRequest
                    .builder()
                    .bucket(bucketName)
                    .notificationConfiguration(configuration)
                    .skipDestinationValidation(true)
                    .build();

            s3Client.putBucketNotificationConfiguration(configurationRequest);
            System.out.println("Added bucket " + bucketName + " with EventBridge
events enabled.");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createBucket(S3Client s3Client, String bucketName) {
```

```
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
 s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createIAMRole(IamClient iam, String rolename, String
 polJSON) {
        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(polJSON)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            AttachRolePolicyRequest rolePolicyRequest =
 AttachRolePolicyRequest.builder()
                    .roleName(rolename)
                    .policyArn("arn:aws:iam::aws:policy/
AmazonEventBridgeFullAccess")
                    .build();

            iam.attachRolePolicy(rolePolicyRequest);
            return response.role().arn();

        } catch (IamException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/*
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
```

```
 This Kotlin example performs the following tasks with Amazon EventBridge:

 1. Creates an AWS Identity and Access Management (IAM) role to use with Amazon
 EventBridge.
 2. Creates an Amazon Simple Storage Service (Amazon S3) bucket with EventBridge
 events enabled.
 3. Creates a rule that triggers when an object is uploaded to Amazon S3.
 4. Lists rules on the event bus.
 5. Creates a new Amazon Simple Notification Service (Amazon SNS) topic and lets
 the user subscribe to it.
 6. Adds a target to the rule that sends an email to the specified topic.
 7. Creates an EventBridge event that sends an email when an Amazon S3 object is
 created.
 8. Lists targets.
 9. Lists the rules for the same target.
 10. Triggers the rule by uploading a file to the S3 bucket.
 11. Disables a specific rule.
 12. Checks and prints the state of the rule.
 13. Adds a transform to the rule to change the text of the email.
 14. Enables a specific rule.
 15. Triggers the updated rule by uploading a file to the S3 bucket.
 16. Updates the rule to a custom rule pattern.
 17. Sends an event to trigger the rule.
 18. Cleans up resources.
*/
val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <roleName> <bucketName> <topicName> <eventRuleName>

    Where:
        roleName - The name of the role to create.
        bucketName - The Amazon Simple Storage Service (Amazon S3) bucket name to
 create.
        topicName - The name of the Amazon Simple Notification Service (Amazon
 SNS) topic to create.
        eventRuleName - The Amazon EventBridge rule name to create.
    """
    val polJSON = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
```

```
        "\"Principal\": {" +
        "\"Service\": \"events.amazonaws.com\"" +
        "}," +
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
        "}"

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val sc = Scanner(System.`in`)
    val roleName = args[0]
    val bucketName = args[1]
    val topicName = args[2]
    val eventRuleName = args[3]

    println(DASHES)
    println("Welcome to the Amazon EventBridge example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create an AWS Identity and Access Management (IAM) role to use
 with Amazon EventBridge.")
    val roleArn = createIAMRole(roleName, polJSON)
    println(DASHES)

    println(DASHES)
    println("2. Create an S3 bucket with EventBridge events enabled.")
    if (checkBucket(bucketName)) {
        println("$bucketName already exists. Ending this scenario.")
        exitProcess(1)
    }

    createBucket(bucketName)
    delay(3000)
    setBucketNotification(bucketName)
    println(DASHES)

    println(DASHES)
    println("3. Create a rule that triggers when an object is uploaded to Amazon
 S3.")
    delay(10000)
```

```
    addEventRule(roleArn, bucketName, eventRuleName)
    println(DASHES)

    println(DASHES)
    println("4. List rules on the event bus.")
    listRules()
    println(DASHES)

    println(DASHES)
    println("5. Create a new SNS topic for testing and let the user subscribe to
the topic.")
    val topicArn = createSnsTopic(topicName)
    println(DASHES)

    println(DASHES)
    println("6. Add a target to the rule that sends an email to the specified
topic.")
    println("Enter your email to subscribe to the Amazon SNS topic:")
    val email = sc.nextLine()
    subEmail(topicArn, email)
    println("Use the link in the email you received to confirm your subscription.
Then press Enter to continue.")
    sc.nextLine()
    println(DASHES)

    println(DASHES)
    println("7. Create an EventBridge event that sends an email when an Amazon S3
object is created.")
    addSnsEventRule(eventRuleName, topicArn, topicName, eventRuleName,
bucketName)
    println(DASHES)

    println(DASHES)
    println("8. List targets.")
    listTargets(eventRuleName)
    println(DASHES)

    println(DASHES)
    println(" 9. List the rules for the same target.")
    listTargetRules(topicArn)
    println(DASHES)

    println(DASHES)
    println("10. Trigger the rule by uploading a file to the S3 bucket.")
```

```
    println("Press Enter to continue.")
    sc.nextLine()
    uploadTextFiletoS3(bucketName)
    println(DASHES)

    println(DASHES)
    println("11. Disable a specific rule.")
    changeRuleState(eventRuleName, false)
    println(DASHES)

    println(DASHES)
    println("12. Check and print the state of the rule.")
    checkRule(eventRuleName)
    println(DASHES)

    println(DASHES)
    println("13. Add a transform to the rule to change the text of the email.")
    updateSnsEventRule(topicArn, eventRuleName)
    println(DASHES)

    println(DASHES)
    println("14. Enable a specific rule.")
    changeRuleState(eventRuleName, true)
    println(DASHES)

    println(DASHES)
    println("15. Trigger the updated rule by uploading a file to the S3 bucket.")
    println("Press Enter to continue.")
    sc.nextLine()
    uploadTextFiletoS3(bucketName)
    println(DASHES)

    println(DASHES)
    println("16. Update the rule to a custom rule pattern.")
    updateToCustomRule(eventRuleName)
    println("Updated event rule $eventRuleName to use a custom pattern.")
    updateCustomRuleTargetWithTransform(topicArn, eventRuleName)
    println("Updated event target $topicArn.")
    println(DASHES)

    println(DASHES)
    println("17. Send an event to trigger the rule. This will trigger a
 subscription email.")
    triggerCustomRule(email)
```

```
    println("Events have been sent. Press Enter to continue.")
    sc.nextLine()
    println(DASHES)

    println(DASHES)
    println("18. Clean up resources.")
    println("Do you want to clean up resources (y/n)")
    val ans = sc.nextLine()
    if (ans.compareTo("y") == 0) {
        cleanupResources(topicArn, eventRuleName, bucketName, roleName)
    } else {
        println("The resources will not be cleaned up. ")
    }
    println(DASHES)

    println(DASHES)
    println("The Amazon EventBridge example scenario has successfully
 completed.")
    println(DASHES)
}

suspend fun cleanupResources(topicArn: String?, eventRuleName: String?,
 bucketName: String?, roleName: String?) {
    println("Removing all targets from the event rule.")
    deleteTargetsFromRule(eventRuleName)
    deleteRuleByName(eventRuleName)
    deleteSNSTopic(topicArn)
    deleteS3Bucket(bucketName)
    deleteRole(roleName)
}

suspend fun deleteRole(roleNameVal: String?) {
    val policyArnVal = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess"
    val policyRequest = DetachRolePolicyRequest {
        policyArn = policyArnVal
        roleName = roleNameVal
    }
    IamClient { region = "us-east-1" }.use { iam ->
        iam.detachRolePolicy(policyRequest)
        println("Successfully detached policy $policyArnVal from role
 $roleNameVal")

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
```

```
            roleName = roleNameVal
        }

        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}

suspend fun deleteS3Bucket(bucketName: String?) {
    // Remove all the objects from the S3 bucket.
    val listObjects = ListObjectsRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        val res = s3Client.listObjects(listObjects)
        val myObjects = res.contents
        val toDelete = mutableListOf<ObjectIdentifier>()

        if (myObjects != null) {
            for (myValue in myObjects) {
                toDelete.add(
                    ObjectIdentifier {
                        key = myValue.key
                    }
                )
            }
        }

        val delOb = Delete {
            objects = toDelete
        }

        val dor = DeleteObjectsRequest {
            bucket = bucketName
            delete = delOb
        }
        s3Client.deleteObjects(dor)

        // Delete the S3 bucket.
        val deleteBucketRequest = DeleteBucketRequest {
            bucket = bucketName
        }
        s3Client.deleteBucket(deleteBucketRequest)
        println("You have deleted the bucket and the objects")
```

```
    }
}

// Delete the SNS topic.
suspend fun deleteSNSTopic(topicArnVal: String?) {
    val request = DeleteTopicRequest {
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.deleteTopic(request)
        println(" $topicArnVal was deleted.")
    }
}

suspend fun deleteRuleByName(ruleName: String?) {
    val ruleRequest = DeleteRuleRequest {
        name = ruleName
    }
    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.deleteRule(ruleRequest)
        println("Successfully deleted the rule")
    }
}

suspend fun deleteTargetsFromRule(eventRuleName: String?) {
    // First, get all targets that will be deleted.
    val request = ListTargetsByRuleRequest {
        rule = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(request)
        val allTargets = response.targets

        // Get all targets and delete them.
        if (allTargets != null) {
            for (myTarget in allTargets) {
                val removeTargetsRequest = RemoveTargetsRequest {
                    rule = eventRuleName
                    ids = listOf(myTarget.id.toString())
                }
                eventBrClient.removeTargets(removeTargetsRequest)
                println("Successfully removed the target")
```

```
            }
        }
    }
}

suspend fun triggerCustomRule(email: String) {
    val json = "{" +
        "\"UserEmail\": \"" + email + "\"," +
        "\"Message\": \"This event was generated by example code.\"" +
        "\"UtcTime\": \"Now.\"" +
        "}"

    val entry = PutEventsRequestEntry {
        source = "ExampleSource"
        detail = json
        detailType = "ExampleType"
    }

    val eventsRequest = PutEventsRequest {
        this.entries = listOf(entry)
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putEvents(eventsRequest)
    }
}

suspend fun updateCustomRuleTargetWithTransform(topicArn: String?, ruleName:
 String?) {
    val targetId = UUID.randomUUID().toString()

    val inputTransformerOb = InputTransformer {
        inputTemplate = "\"Notification: sample event was received.\""
    }

    val target = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransformerOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
        targets = listOf(target)
```

```
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}

suspend fun updateToCustomRule(ruleName: String?) {
    val customEventsPattern = "{" +
        "\"source\": [\"ExampleSource\"]," +
        "\"detail-type\": [\"ExampleType\"]" +
        "}"
    val request = PutRuleRequest {
        name = ruleName
        description = "Custom test rule"
        eventPattern = customEventsPattern
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putRule(request)
    }
}

// Update an Amazon S3 object created rule with a transform on the target.
suspend fun updateSnsEventRule(topicArn: String?, ruleName: String?) {
    val targetId = UUID.randomUUID().toString()
    val myMap = mutableMapOf<String, String>()
    myMap["bucket"] = "$.detail.bucket.name"
    myMap["time"] = "$.time"

    val inputTransOb = InputTransformer {
        inputTemplate = "\"Notification: an object was uploaded to bucket
 <bucket> at <time>.\""
        inputPathsMap = myMap
    }
    val targetOb = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
```

```
        targets = listOf(targetOb)
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}

suspend fun checkRule(eventRuleName: String?) {
    val ruleRequest = DescribeRuleRequest {
        name = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.describeRule(ruleRequest)
        println("The state of the rule is $response")
    }
}

suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}

// Create and upload a file to an S3 bucket to trigger an event.
@Throws(IOException::class)
suspend fun uploadTextFiletoS3(bucketName: String?) {
    val fileSuffix = SimpleDateFormat("yyyyMMddHHmmss").format(Date())
```

```
    val fileName = "TextFile$fileSuffix.txt"
    val myFile = File(fileName)
    val fw = FileWriter(myFile.absoluteFile)
    val bw = BufferedWriter(fw)
    bw.write("This is a sample file for testing uploads.")
    bw.close()

    val putOb = PutObjectRequest {
        bucket = bucketName
        key = fileName
        body = myFile.asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.putObject(putOb)
    }
}

suspend fun listTargetRules(topicArnVal: String?) {
    val ruleNamesByTargetRequest = ListRuleNamesByTargetRequest {
        targetArn = topicArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response =
 eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest)
        response.ruleNames?.forEach { rule ->
            println("The rule name is $rule")
        }
    }
}

suspend fun listTargets(ruleName: String?) {
    val ruleRequest = ListTargetsByRuleRequest {
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(ruleRequest)
        response.targets?.forEach { target ->
            println("Target ARN: ${target.arn}")
        }
    }
}
```

```
// Add a rule that triggers an SNS target when a file is uploaded to an S3
 bucket.
suspend fun addSnsEventRule(ruleName: String?, topicArn: String?, topicName:
 String, eventRuleName: String, bucketName: String) {
    val targetID = UUID.randomUUID().toString()
    val myTarget = Target {
        id = targetID
        arn = topicArn
    }

    val targetsOb = mutableListOf<Target>()
    targetsOb.add(myTarget)

    val request = PutTargetsRequest {
        eventBusName = null
        targets = targetsOb
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(request)
        println("Added event rule $eventRuleName with Amazon SNS target
 $topicName for bucket $bucketName.")
    }
}

suspend fun subEmail(topicArnVal: String?, email: String?) {
    val request = SubscribeRequest {
        protocol = "email"
        endpoint = email
        returnSubscriptionArn = true
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.subscribe(request)
        println(" Subscription ARN: ${result.subscriptionArn}")
    }
}

suspend fun createSnsTopic(topicName: String): String? {
    val topicPolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
```

```
        "\"Statement\": [{" +
        "\"Sid\": \"EventBridgePublishTopic\"," +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": \"events.amazonaws.com\"" +
        "}," +
        "\"Resource\": \"*\"," +
        "\"Action\": \"sns:Publish\"" +
        "}]" +
        "}"

    val topicAttributes = mutableMapOf<String, String>()
    topicAttributes["Policy"] = topicPolicy

    val topicRequest = CreateTopicRequest {
        name = topicName
        attributes = topicAttributes
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.createTopic(topicRequest)
        println("Added topic $topicName for email subscriptions.")
        return response.topicArn
    }
}

suspend fun listRules() {
    val rulesRequest = ListRulesRequest {
        eventBusName = "default"
        limit = 10
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRules(rulesRequest)
        response.rules?.forEach { rule ->
            println("The rule name is ${rule.name}")
            println("The rule ARN is ${rule.arn}")
        }
    }
}

// Create a new event rule that triggers when an Amazon S3 object is created in a
 bucket.
```

```
suspend fun addEventRule(roleArnVal: String?, bucketName: String, eventRuleName:
 String?) {
    val pattern = """{
        "source": ["aws.s3"],
        "detail-type": ["Object Created"],
        "detail": {
        "bucket": {
            "name": ["$bucketName"]
            }
        }
    }"""

    val ruleRequest = PutRuleRequest {
        description = "Created by using the AWS SDK for Kotlin"
        name = eventRuleName
        eventPattern = pattern
        roleArn = roleArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}

// Set the Amazon S3 bucket notification configuration.
suspend fun setBucketNotification(bucketName: String) {
    val eventBridgeConfig = EventBridgeConfiguration {
    }

    val configuration = NotificationConfiguration {
        eventBridgeConfiguration = eventBridgeConfig
    }

    val configurationRequest = PutBucketNotificationConfigurationRequest {
        bucket = bucketName
        notificationConfiguration = configuration
        skipDestinationValidation = true
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.putBucketNotificationConfiguration(configurationRequest)
        println("Added bucket $bucketName with EventBridge events enabled.")
    }
```

```
}

// Create an S3 bucket using a waiter.
suspend fun createBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        s3.waitUntilBucketExists {
            bucket = bucketName
        }
        println("$bucketName is ready")
    }
}

suspend fun checkBucket(bucketName: String?): Boolean {
    try {
        // Determine if the S3 bucket exists.
        val headBucketRequest = HeadBucketRequest {
            bucket = bucketName
        }

        S3Client { region = "us-east-1" }.use { s3Client ->
            s3Client.headBucket(headBucketRequest)
            return true
        }
    } catch (e: S3Exception) {
        System.err.println(e.message)
    }
    return false
}

suspend fun createIAMRole(rolenameVal: String?, polJSON: String?): String? {
    val request = CreateRoleRequest {
        roleName = rolenameVal
        assumeRolePolicyDocument = polJSON
        description = "Created using the AWS SDK for Kotlin"
    }

    val rolePolicyRequest = AttachRolePolicyRequest {
        roleName = rolenameVal
        policyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess"
```

```
    }

    IamClient { region = "us-east-1" }.use { iam ->
        val response = iam.createRole(request)
        iam.attachRolePolicy(rolePolicyRequest)
        return response.role?.arn
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Exemplos de vários serviços para EventBridge usar SDKs AWS

Os exemplos de código a seguir mostram como usar a Amazon EventBridge com AWS SDKs. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Usar eventos programados para chamar uma função do Lambda

Usar eventos programados para chamar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma AWS Lambda função invocada por um evento EventBridge agendado pela Amazon.

Java

SDK para Java 2.x

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função do Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função Lambda usando a API de tempo de execução do JavaScript Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

Python

SDK para Python (Boto3)

Este exemplo mostra como registrar uma AWS Lambda função como alvo de um EventBridge evento programado da Amazon. O manipulador do Lambda grava uma mensagem amigável e os dados completos do evento no Amazon CloudWatch Logs para recuperação posterior.

- Implanta uma função do Lambda
- Cria um evento EventBridge agendado e torna a função Lambda o alvo.
- Concede permissão para permitir a EventBridge invocação da função Lambda.
- Imprime os dados mais recentes do CloudWatch Logs para mostrar o resultado das invocações programadas.
- Limpa todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- CloudWatch Registros
- EventBridge
- Lambda

Exemplos de código para o Forecast usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Forecast com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Forecast – Mais informações sobre o Forecast.
- Referência da API do Forecast – Detalhes sobre todas as ações disponíveis do Forecast.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Forecast usando SDKs da AWS
  - Crie um conjunto de dados para o Amazon Forecast usando um SDK da AWS
  - Crie uma previsão para o Amazon Forecast usando um SDK da AWS
  - Exclua um conjunto de dados para o Amazon Forecast usando um SDK da AWS
  - Exclua uma previsão para o Amazon Forecast usando um SDK da AWS
  - Descreva uma previsão para o Amazon Forecast usando um SDK da AWS
  - Liste grupos de conjuntos de dados do Amazon Forecast usando um SDK da AWS
  - Liste previsões do Amazon Forecast usando um SDK da AWS

Ações para o Forecast usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Forecast com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um conjunto de dados para o Amazon Forecast usando um SDK da AWS

- Crie uma previsão para o Amazon Forecast usando um SDK da AWS
- Exclua um conjunto de dados para o Amazon Forecast usando um SDK da AWS
- Exclua uma previsão para o Amazon Forecast usando um SDK da AWS
- Descreva uma previsão para o Amazon Forecast usando um SDK da AWS
- Liste grupos de conjuntos de dados do Amazon Forecast usando um SDK da AWS
- Liste previsões do Amazon Forecast usando um SDK da AWS

Crie um conjunto de dados para o Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como criar um conjunto de dados do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.CreateDatasetRequest;
import software.amazon.awssdk.services.forecast.model.Schema;
import software.amazon.awssdk.services.forecast.model.SchemaAttribute;
import software.amazon.awssdk.services.forecast.model.CreateDatasetResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 */
public class CreateDataSet {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <name>\s

                Where:
                    name - The name of the data set.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String name = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        String myDataSetARN = createForecastDataSet(forecast, name);
        System.out.println("The ARN of the new data set is " + myDataSetARN);
        forecast.close();
    }

    public static String createForecastDataSet(ForecastClient forecast, String
 name) {
        try {
            Schema schema = Schema.builder()
                    .attributes(getSchema())
                    .build();

            CreateDatasetRequest datasetRequest = CreateDatasetRequest.builder()
                    .datasetName(name)
                    .domain("CUSTOM")
                    .datasetType("RELATED_TIME_SERIES")
                    .dataFrequency("D")
                    .schema(schema)
                    .build();
```

```
            CreateDatasetResponse response =
 forecast.createDataset(datasetRequest);
            return response.datasetArn();

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }

    // Create a SchemaAttribute list required to create a data set.
    private static List<SchemaAttribute> getSchema() {

        List<SchemaAttribute> schemaList = new ArrayList<>();
        SchemaAttribute att1 = SchemaAttribute.builder()
                .attributeName("item_id")
                .attributeType("string")
                .build();

        SchemaAttribute att2 = SchemaAttribute.builder()
                .attributeName("timestamp")
                .attributeType("timestamp")
                .build();

        SchemaAttribute att3 = SchemaAttribute.builder()
                .attributeName("target_value")
                .attributeType("float")
                .build();

        // Push the SchemaAttribute objects to the List.
        schemaList.add(att1);
        schemaList.add(att2);
        schemaList.add(att3);
        return schemaList;
    }
}
```

- Para obter detalhes da API, consulte CreateDataseta Referência AWS SDK for Java 2.x da API.

Crie uma previsão para o Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como criar uma previsão do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.CreateForecastRequest;
import software.amazon.awssdk.services.forecast.model.CreateForecastResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateForecast {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <name> <predictorArn>\s

                Where:
                    name - The name of the forecast.\s
                    predictorArn - The arn of the predictor to use.\s

                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String name = args[0];
        String predictorArn = args[1];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        String forecastArn = createNewForecast(forecast, name, predictorArn);
        System.out.println("The ARN of the new forecast is " + forecastArn);
        forecast.close();
    }

    public static String createNewForecast(ForecastClient forecast, String name,
 String predictorArn) {
        try {
            CreateForecastRequest forecastRequest =
 CreateForecastRequest.builder()
                    .forecastName(name)
                    .predictorArn(predictorArn)
                    .build();

            CreateForecastResponse response =
 forecast.createForecast(forecastRequest);
            return response.forecastArn();

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateForecasta Referência AWS SDK for Java 2.x da API.

Exclua um conjunto de dados para o Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um conjunto de dados do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DeleteDatasetRequest;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteDataset {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <datasetARN>\s

                Where:
                    datasetARN - The ARN of the data set to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String datasetARN = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        deleteForecastDataSet(forecast, datasetARN);
        forecast.close();
    }

    public static void deleteForecastDataSet(ForecastClient forecast, String
 myDataSetARN) {
        try {
            DeleteDatasetRequest deleteRequest = DeleteDatasetRequest.builder()
                    .datasetArn(myDataSetARN)
                    .build();

            forecast.deleteDataset(deleteRequest);
            System.out.println("The Data Set was deleted");

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteDataseta Referência AWS SDK for Java 2.x da API.

Exclua uma previsão para o Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma previsão do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DeleteDatasetRequest;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteDataset {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <datasetARN>\s

                Where:
                    datasetARN - The ARN of the data set to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String datasetARN = args[0];
```

```
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        deleteForecastDataSet(forecast, datasetARN);
        forecast.close();
    }

    public static void deleteForecastDataSet(ForecastClient forecast, String
 myDataSetARN) {
        try {
            DeleteDatasetRequest deleteRequest = DeleteDatasetRequest.builder()
                    .datasetArn(myDataSetARN)
                    .build();

            forecast.deleteDataset(deleteRequest);
            System.out.println("The Data Set was deleted");

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteForecasta Referência AWS SDK for Java 2.x da API.

Descreva uma previsão para o Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como descrever uma previsão do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DescribeForecastRequest;
import software.amazon.awssdk.services.forecast.model.DescribeForecastResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeForecast {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <forecastarn>\s

                Where:
                    forecastarn - The arn of the forecast (for example,
 "arn:aws:forecast:us-west-2:xxxxx322:forecast/my_forecast)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String forecastarn = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        describe(forecast, forecastarn);
        forecast.close();
    }

    public static void describe(ForecastClient forecast, String forecastarn) {
        try {
            DescribeForecastRequest request = DescribeForecastRequest.builder()
                    .forecastArn(forecastarn)
                    .build();

            DescribeForecastResponse response =
 forecast.describeForecast(request);
            System.out.println("The name of the forecast is " +
 response.forecastName());

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeForecasta Referência AWS SDK for Java 2.x da API.

Liste grupos de conjuntos de dados do Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como listar grupos de conjuntos de dados do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DatasetGroupSummary;
import software.amazon.awssdk.services.forecast.model.ListDatasetGroupsRequest;
import software.amazon.awssdk.services.forecast.model.ListDatasetGroupsResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListDataSetGroups {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        listDataGroups(forecast);
        forecast.close();
    }

    public static void listDataGroups(ForecastClient forecast) {
        try {
            ListDatasetGroupsRequest group = ListDatasetGroupsRequest.builder()
                    .maxResults(10)
```

```
                    .build();

            ListDatasetGroupsResponse response =
 forecast.listDatasetGroups(group);
            List<DatasetGroupSummary> groups = response.datasetGroups();
            for (DatasetGroupSummary myGroup : groups) {
                System.out.println("The Data Set name is " +
 myGroup.datasetGroupName());
            }

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListDatasetGroupsa Referência AWS SDK for Java 2.x da API.

Liste previsões do Amazon Forecast usando um SDK da AWS

O exemplo de código a seguir mostra como listar previsões do Forecast.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.ListForecastsResponse;
import software.amazon.awssdk.services.forecast.model.ListForecastsRequest;
import software.amazon.awssdk.services.forecast.model.ForecastSummary;
import software.amazon.awssdk.services.forecast.model.ForecastException;
```

```
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListForecasts {

    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        listAllForeCasts(forecast);
        forecast.close();
    }

    public static void listAllForeCasts(ForecastClient forecast) {
        try {
            ListForecastsRequest request = ListForecastsRequest.builder()
                    .maxResults(10)
                    .build();

            ListForecastsResponse response = forecast.listForecasts(request);
            List<ForecastSummary> forecasts = response.forecasts();
            for (ForecastSummary forecastSummary : forecasts) {
                System.out.println("The name of the forecast is " +
 forecastSummary.forecastName());
            }

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListForecastsa Referência AWS SDK for Java 2.x da API.

Exemplos de código para o AWS Glue usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Glue com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do AWS Glue – Mais informações sobre o AWS Glue.
- Referência da API do AWS Glue – Detalhes sobre todas as ações disponíveis do AWS Glue.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace GlueActions;

public class HelloGlue
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Glue.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonGlue>()
                .AddTransient<GlueWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<HelloGlue>();
        var glueClient = host.Services.GetRequiredService<IAmazonGlue>();

        var request = new ListJobsRequest();

        var jobNames = new List<string>();

        do
        {
            var response = await glueClient.ListJobsAsync(request);
            jobNames.AddRange(response.JobNames);
            request.NextToken = response.NextToken;
        }
        while (request.NextToken is not null);

        Console.Clear();
        Console.WriteLine("Hello, Glue. Let's list your existing Glue Jobs:");
        if (jobNames.Count == 0)
        {
            Console.WriteLine("You don't have any AWS Glue jobs.");
```

```
        }
        else
        {
            jobNames.ForEach(Console.WriteLine);
        }
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS glue)

# Set this project's name.
project("hello_glue")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
```

```
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you
 may need to uncomment this
                                       # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_glue.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_glue.cpp.

```
#include <aws/core/Aws.h>
#include <aws/glue/GlueClient.h>
#include <aws/glue/model/ListJobsRequest.h>
#include <iostream>

/*
 *  A "Hello Glue" starter application which initializes an AWS Glue client and
 lists the
 *  AWS Glue job definitions.
 *
 *  main function
 *
 *  Usage: 'hello_glue'
```

```
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Glue::GlueClient glueClient(clientConfig);

        std::vector<Aws::String> jobs;

        Aws::String nextToken;  // Used for pagination.
        do {
            Aws::Glue::Model::ListJobsRequest listJobsRequest;
            if (!nextToken.empty()) {
                listJobsRequest.SetNextToken(nextToken);
            }

            Aws::Glue::Model::ListJobsOutcome listRunsOutcome =
 glueClient.ListJobs(
                    listJobsRequest);

            if (listRunsOutcome.IsSuccess()) {
                const std::vector<Aws::String> &jobNames =
 listRunsOutcome.GetResult().GetJobNames();
                jobs.insert(jobs.end(), jobNames.begin(), jobNames.end());

                nextToken = listRunsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error listing jobs. "
                          << listRunsOutcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!nextToken.empty());
```

```
        std::cout << "Your account has " << jobs.size() << " jobs."
                  << std::endl;
        for (size_t i = 0; i < jobs.size(); ++i) {
            std::cout << "   " << i + 1 << ". " << jobs[i] << std::endl;
        }
    }
    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.glue;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.ListJobsRequest;
import software.amazon.awssdk.services.glue.model.ListJobsResponse;
import java.util.List;

public class HelloGlue {
    public static void main(String[] args) {
        GlueClient glueClient = GlueClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listJobs(glueClient);
    }

    public static void listJobs(GlueClient glueClient) {
        ListJobsRequest request = ListJobsRequest.builder()
```

```
                .maxResults(10)
                .build();
        ListJobsResponse response = glueClient.listJobs(request);
        List<String> jobList = response.jobNames();
        jobList.forEach(job -> {
            System.out.println("Job Name: " + job);
        });
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListJobsCommand, GlueClient } from "@aws-sdk/client-glue";

const client = new GlueClient({});

export const main = async () => {
  const command = new ListJobsCommand({});

  const { JobNames } = await client.send(command);
  const formattedJobNames = JobNames.join("\n");
  console.log("Job names: ");
  console.log(formattedJobNames);
  return JobNames;
};
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for JavaScript da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let mut list_jobs = glue.list_jobs().into_paginator().send();
        while let Some(list_jobs_output) = list_jobs.next().await {
            match list_jobs_output {
                Ok(list_jobs) => {
                    let names = list_jobs.job_names();
                    info!(?names, "Found these jobs")
                }
                Err(err) => return Err(GlueMvpError::from_glue_sdk(err)),
            }
        }
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWS SDK for Rust.

Exemplos de código

- Ações para o AWS Glue usando AWS SDKs
  - Criar um crawler do AWS Glue usando um AWS SDK
  - Criar uma definição de trabalho do AWS Glue usando um AWS SDK
  - Excluir um crawler do AWS Glue usando um AWS SDK
  - Excluir um banco de dados do AWS Glue Data Catalog usando um AWS SDK
  - Excluir uma definição de trabalho do AWS Glue usando um AWS SDK
  - Excluir uma tabela do AWS Glue Data Catalog usando um AWS SDK
  - Obter um crawler do AWS Glue usando um AWS SDK
  - Obter um banco de dados do AWS Glue Data Catalog usando um AWS SDK
  - Obter uma execução de trabalho do AWS Glue usando um AWS SDK
  - Obter uma lista de bancos de dados do AWS Glue Data Catalog usando um AWS SDK

- Obter um trabalho do AWS Glue Data Catalog usando um AWS SDK
- Obter execuções de um trabalho do AWS Glue usando um AWS SDK
- Obter tabelas de um banco de dados do AWS Glue Data Catalog um AWS SDK
- Listar definições de trabalhos do AWS Glue usando um AWS SDK
- Iniciar um crawler do AWS Glue usando um AWS SDK
- Iniciar uma execução de trabalho do AWS Glue usando um AWS SDK
- Cenários para o AWS Glue usando AWS SDKs
  - Começar a executar crawlers e trabalhos do AWS Glue usando um AWS SDK

Ações para o AWS Glue usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Glue com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o AWS Glue usando AWS SDKs.

Exemplos

- Criar um crawler do AWS Glue usando um AWS SDK
- Criar uma definição de trabalho do AWS Glue usando um AWS SDK
- Excluir um crawler do AWS Glue usando um AWS SDK
- Excluir um banco de dados do AWS Glue Data Catalog usando um AWS SDK
- Excluir uma definição de trabalho do AWS Glue usando um AWS SDK
- Excluir uma tabela do AWS Glue Data Catalog usando um AWS SDK
- Obter um crawler do AWS Glue usando um AWS SDK
- Obter um banco de dados do AWS Glue Data Catalog usando um AWS SDK
- Obter uma execução de trabalho do AWS Glue usando um AWS SDK
- Obter uma lista de bancos de dados do AWS Glue Data Catalog usando um AWS SDK
- Obter um trabalho do AWS Glue Data Catalog usando um AWS SDK
- Obter execuções de um trabalho do AWS Glue usando um AWS SDK
- Obter tabelas de um banco de dados do AWS Glue Data Catalog um AWS SDK
- Listar definições de trabalhos do AWS Glue usando um AWS SDK

- Iniciar um crawler do AWS Glue usando um AWS SDK
- Iniciar uma execução de trabalho do AWS Glue usando um AWS SDK

Criar um crawler do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como criar um crawler do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name for the crawler.</param>
    /// <param name="crawlerDescription">A description of the crawler.</param>
    /// <param name="role">The AWS Identity and Access Management (IAM) role to
    /// be assumed by the crawler.</param>
    /// <param name="schedule">The schedule on which the crawler will be
executed.</param>
    /// <param name="s3Path">The path to the Amazon Simple Storage Service
(Amazon S3)
    /// bucket where the Python script has been stored.</param>
    /// <param name="dbName">The name to use for the database that will be
    /// created by the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateCrawlerAsync(
        string crawlerName,
        string crawlerDescription,
```

```
        string role,
        string schedule,
        string s3Path,
        string dbName)
    {
        var s3Target = new S3Target
        {
            Path = s3Path,
        };

        var targetList = new List<S3Target>
        {
            s3Target,
        };

        var targets = new CrawlerTargets
        {
            S3Targets = targetList,
        };

        var crawlerRequest = new CreateCrawlerRequest
        {
            DatabaseName = dbName,
            Name = crawlerName,
            Description = crawlerDescription,
            Targets = targets,
            Role = role,
            Schedule = schedule,
        };

        var response = await _amazonGlue.CreateCrawlerAsync(crawlerRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::S3Target s3Target;
       s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
       Aws::Glue::Model::CrawlerTargets crawlerTargets;
       crawlerTargets.AddS3Targets(s3Target);

       Aws::Glue::Model::CreateCrawlerRequest request;
       request.SetTargets(crawlerTargets);
       request.SetName(CRAWLER_NAME);
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);
       request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
       request.SetRole(roleArn);

       Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

       if (outcome.IsSuccess()) {
           std::cout << "Successfully created the crawler." << std::endl;
       }
       else {
           std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName,
clientConfig);
           return false;
```

```
        }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.CreateCrawlerRequest;
import software.amazon.awssdk.services.glue.model.CrawlerTargets;
import software.amazon.awssdk.services.glue.model.GlueException;
import software.amazon.awssdk.services.glue.model.S3Target;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <IAM> <s3Path> <cron> <dbName> <crawlerName>

                Where:
```

```
                    IAM - The ARN of the IAM role that has AWS Glue and S3
permissions.\s
                    s3Path - The Amazon Simple Storage Service (Amazon S3) target
that contains data (for example, CSV data).
                    cron - A cron expression used to specify the schedule  (i.e.,
cron(15 12 * * ? *).
                    dbName - The database name.\s
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String iam = args[0];
        String s3Path = args[1];
        String cron = args[2];
        String dbName = args[3];
        String crawlerName = args[4];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        createGlueCrawler(glueClient, iam, s3Path, cron, dbName, crawlerName);
        glueClient.close();
    }

    public static void createGlueCrawler(GlueClient glueClient,
            String iam,
            String s3Path,
            String cron,
            String dbName,
            String crawlerName) {

        try {
            S3Target s3Target = S3Target.builder()
                    .path(s3Path)
                    .build();

            // Add the S3Target to a list.
            List<S3Target> targetList = new ArrayList<>();
            targetList.add(s3Target);
```

```
            CrawlerTargets targets = CrawlerTargets.builder()
                    .s3Targets(targetList)
                    .build();

            CreateCrawlerRequest crawlerRequest = CreateCrawlerRequest.builder()
                    .databaseName(dbName)
                    .name(crawlerName)
                    .description("Created by the AWS Glue Java API")
                    .targets(targets)
                    .role(iam)
                    .schedule(cron)
                    .build();

            glueClient.createCrawler(crawlerRequest);
            System.out.println(crawlerName + " was successfully created");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createCrawler = (name, role, dbName, tablePrefix, s3TargetPath) => {
  const client = new GlueClient({});
```

```
  const command = new CreateCrawlerCommand({
    Name: name,
    Role: role,
    DatabaseName: dbName,
    TablePrefix: tablePrefix,
    Targets: {
      S3Targets: [{ Path: s3TargetPath }],
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createGlueCrawler(
    iam: String?,
    s3Path: String?,
    cron: String?,
    dbName: String?,
    crawlerName: String
) {
    val s3Target = S3Target {
        path = s3Path
    }

    // Add the S3Target to a list.
    val targetList = mutableListOf<S3Target>()
    targetList.add(s3Target)
```

```
    val targetOb = CrawlerTargets {
        s3Targets = targetList
    }

    val request = CreateCrawlerRequest {
        databaseName = dbName
        name = crawlerName
        description = "Created by the AWS Glue Kotlin API"
        targets = targetOb
        role = iam
        schedule = cron
    }

    GlueClient { region = "us-west-2" }.use { glueClient ->
        glueClient.createCrawler(request)
        println("$crawlerName was successfully created")
    }
}
```

- Para obter detalhes da API, consulte a CreateCrawlerreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $crawlerName = "example-crawler-test-" . $uniqid;

        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $path = 's3://crawler-public-us-east-1/flight/2016/csv';
        $glueService->createCrawler($crawlerName, $role['Role']['Arn'],
 $databaseName, $path);
```

```
    public function createCrawler($crawlerName, $role, $databaseName, $path):
 Result
    {
        return $this->customWaiter(function () use ($crawlerName, $role,
 $databaseName, $path) {
            return $this->glueClient->createCrawler([
                'Name' => $crawlerName,
                'Role' => $role,
                'DatabaseName' => $databaseName,
                'Targets' => [
                    'S3Targets' =>
                        [[
                            'Path' => $path,
                        ]]
                ],
            ]);
        });
    }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client
```

```
    def create_crawler(self, name, role_arn, db_name, db_prefix, s3_target):
        """
        Creates a crawler that can crawl the specified target and populate a
        database in your AWS Glue Data Catalog with metadata that describes the
data
        in the target.

        :param name: The name of the crawler.
        :param role_arn: The Amazon Resource Name (ARN) of an AWS Identity and
Access
                         Management (IAM) role that grants permission to let AWS
Glue
                         access the resources it needs.
        :param db_name: The name to give the database that is created by the
crawler.
        :param db_prefix: The prefix to give any database tables that are created
by
                          the crawler.
        :param s3_target: The URL to an S3 bucket that contains data that is
                          the target of the crawler.
        """
        try:
            self.glue_client.create_crawler(
                Name=name,
                Role=role_arn,
                DatabaseName=db_name,
                TablePrefix=db_prefix,
                Targets={"S3Targets": [{"Path": s3_target}]},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create crawler. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateCrawlerReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Creates a new crawler with the specified configuration.
  #
  # @param name [String] The name of the crawler.
  # @param role_arn [String] The ARN of the IAM role to be used by the crawler.
  # @param db_name [String] The name of the database where the crawler stores its
 metadata.
  # @param db_prefix [String] The prefix to be added to the names of tables that
 the crawler creates.
  # @param s3_target [String] The S3 path that the crawler will crawl.
  # @return [void]
  def create_crawler(name, role_arn, db_name, db_prefix, s3_target)
    @glue_client.create_crawler(
      name: name,
      role: role_arn,
      database_name: db_name,
      targets: {
        s3_targets: [
          {
            path: s3_target
```

```
          }
        ]
      }
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create crawler: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let create_crawler = glue
            .create_crawler()
            .name(self.crawler())
            .database_name(self.database())
            .role(self.iam_role.expose_secret())
            .targets(
                CrawlerTargets::builder()
                    .s3_targets(S3Target::builder().path(CRAWLER_TARGET).build())
                    .build(),
            )
            .send()
            .await;

        match create_crawler {
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::AlreadyExistsException(_) => {
```

```
                        info!("Using existing crawler");
                        Ok(())
                    }
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
            Ok(_) => Ok(()),
        }?;
```

- Para obter detalhes da API, consulte a CreateCrawlerreferência da API AWS SDK for Rust.

Criar uma definição de trabalho do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma definição de trabalho do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="roleName">The name of the IAM role to be assumed by
    /// the job.</param>
    /// <param name="description">A description of the job.</param>
    /// <param name="scriptUrl">The URL to the script.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
```

```
    public async Task<bool> CreateJobAsync(string dbName, string tableName,
string bucketUrl, string jobName, string roleName, string description, string
scriptUrl)
    {
        var command = new JobCommand
        {
            PythonVersion = "3",
            Name = "glueetl",
            ScriptLocation = scriptUrl,
        };

        var arguments = new Dictionary<string, string>
        {
            { "--input_database", dbName },
            { "--input_table", tableName },
            { "--output_bucket_url", bucketUrl }
        };

        var request = new CreateJobRequest
        {
            Command = command,
            DefaultArguments = arguments,
            Description = description,
            GlueVersion = "3.0",
            Name = jobName,
            NumberOfWorkers = 10,
            Role = roleName,
            WorkerType = "G.1X"
        };

        var response = await _amazonGlue.CreateJobAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar um trabalho para transformar dados

O exemplo de `create-job` a seguir cria um trabalho de streaming que executa um script armazenado no S3.

```
aws glue create-job \
    --name my-testing-job \
    --role AWSGlueServiceRoleDefault \
    --command '{ \
        "Name": "gluestreaming", \
        "ScriptLocation": "s3://DOC-EXAMPLE-BUCKET/folder/" \
    }' \
    --region us-east-1 \
    --output json \
    --default-arguments '{ \
        "--job-language":"scala", \
        "--class":"GlueApp" \
    }' \
    --profile my-profile \
    --endpoint https://glue.us-east-1.amazonaws.com
```

Conteúdo de `test_script.scala`:

```
import com.amazonaws.services.glue.ChoiceOption
import com.amazonaws.services.glue.GlueContext
import com.amazonaws.services.glue.MappingSpec
import com.amazonaws.services.glue.ResolveSpec
import com.amazonaws.services.glue.errors.CallSite
import com.amazonaws.services.glue.util.GlueArgParser
import com.amazonaws.services.glue.util.Job
import com.amazonaws.services.glue.util.JsonOptions
import org.apache.spark.SparkContext
import scala.collection.JavaConverters._
```

```
object GlueApp {
    def main(sysArgs: Array[String]) {
        val spark: SparkContext = new SparkContext()
        val glueContext: GlueContext = new GlueContext(spark)
        // @params: [JOB_NAME]
        val args = GlueArgParser.getResolvedOptions(sysArgs,
 Seq("JOB_NAME").toArray)
        Job.init(args("JOB_NAME"), glueContext, args.asJava)
        // @type: DataSource
        // @args: [database = "tempdb", table_name = "s3-source",
 transformation_ctx = "datasource0"]
        // @return: datasource0
        // @inputs: []
        val datasource0 = glueContext.getCatalogSource(database = "tempdb",
 tableName = "s3-source", redshiftTmpDir = "", transformationContext =
 "datasource0").getDynamicFrame()
        // @type: ApplyMapping
        // @args: [mapping = [("sensorid", "int", "sensorid", "int"),
 ("currenttemperature", "int", "currenttemperature", "int"), ("status", "string",
 "status", "string")], transformation_ctx = "applymapping1"]
        // @return: applymapping1
        // @inputs: [frame = datasource0]
        val applymapping1 = datasource0.applyMapping(mappings = Seq(("sensorid",
 "int", "sensorid", "int"), ("currenttemperature", "int", "currenttemperature",
 "int"), ("status", "string", "status", "string")), caseSensitive = false,
 transformationContext = "applymapping1")
        // @type: SelectFields
        // @args: [paths = ["sensorid", "currenttemperature", "status"],
 transformation_ctx = "selectfields2"]
        // @return: selectfields2
        // @inputs: [frame = applymapping1]
        val selectfields2 = applymapping1.selectFields(paths = Seq("sensorid",
 "currenttemperature", "status"), transformationContext = "selectfields2")
        // @type: ResolveChoice
        // @args: [choice = "MATCH_CATALOG", database = "tempdb", table_name =
 "my-s3-sink", transformation_ctx = "resolvechoice3"]
        // @return: resolvechoice3
        // @inputs: [frame = selectfields2]
        val resolvechoice3 = selectfields2.resolveChoice(choiceOption =
 Some(ChoiceOption("MATCH_CATALOG")), database = Some("tempdb"), tableName =
 Some("my-s3-sink"), transformationContext = "resolvechoice3")
        // @type: DataSink
        // @args: [database = "tempdb", table_name = "my-s3-sink",
 transformation_ctx = "datasink4"]
```

```
        // @return: datasink4
        // @inputs: [frame = resolvechoice3]
        val datasink4 = glueContext.getCatalogSink(database = "tempdb",
 tableName = "my-s3-sink", redshiftTmpDir = "", transformationContext =
 "datasink4").writeDynamicFrame(resolvechoice3)
        Job.commit()
    }
}
```

Saída:

```
{
    "Name": "my-testing-job"
}
```

Para obter mais informações, consulte Criação de trabalhos no AWS Glue no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte CreateJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createJob = (name, role, scriptBucketName, scriptKey) => {
  const client = new GlueClient({});

  const command = new CreateJobCommand({
    Name: name,
    Role: role,
    Command: {
      Name: "glueetl",
      PythonVersion: "3",
      ScriptLocation: `s3://${scriptBucketName}/${scriptKey}`,
    },
```

```
    GlueVersion: "3.0",
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $jobName = 'test-job-' . $uniqid;

        $scriptLocation = "s3://$bucketName/run_job.py";
        $job = $glueService->createJob($jobName, $role['Role']['Arn'],
 $scriptLocation);

    public function createJob($jobName, $role, $scriptLocation, $pythonVersion =
 '3', $glueVersion = '3.0'): Result
    {
        return $this->glueClient->createJob([
            'Name' => $jobName,
            'Role' => $role,
            'Command' => [
                'Name' => 'glueetl',
                'ScriptLocation' => $scriptLocation,
                'PythonVersion' => $pythonVersion,
            ],
            'GlueVersion' => $glueVersion,
        ]);
```

```
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def create_job(self, name, description, role_arn, script_location):
        """
        Creates a job definition for an extract, transform, and load (ETL) job
 that can
        be run by AWS Glue.

        :param name: The name of the job definition.
        :param description: The description of the job definition.
        :param role_arn: The ARN of an IAM role that grants AWS Glue the
 permissions
                         it requires to run the job.
        :param script_location: The Amazon S3 URL of a Python ETL script that is
 run as
                                part of the job. The script defines how the data
 is
                                transformed.
        """
```

```
        try:
            self.glue_client.create_job(
                Name=name,
                Description=description,
                Role=role_arn,
                Command={
                    "Name": "glueetl",
                    "ScriptLocation": script_location,
                    "PythonVersion": "3",
                },
                GlueVersion="3.0",
            )
        except ClientError as err:
            logger.error(
                "Couldn't create job %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateJobReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
```

```
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Creates a new job with the specified configuration.
  #
  # @param name [String] The name of the job.
  # @param description [String] The description of the job.
  # @param role_arn [String] The ARN of the IAM role to be used by the job.
  # @param script_location [String] The location of the ETL script for the job.
  # @return [void]
  def create_job(name, description, role_arn, script_location)
    @glue_client.create_job(
      name: name,
      description: description,
      role: role_arn,
      command: {
        name: "glueetl",
        script_location: script_location,
        python_version: "3"
      },
      glue_version: "3.0"
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create job #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let create_job = glue
            .create_job()
            .name(self.job())
            .role(self.iam_role.expose_secret())
            .command(
                JobCommand::builder()
                    .name("glueetl")
                    .python_version("3")
                    .script_location(format!("s3://{}/job.py", self.bucket()))
                    .build(),
            )
            .glue_version("3.0")
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job_name = create_job.name().ok_or_else(|| {
            GlueMvpError::Unknown("Did not get job name after creating
job".into())
        })?;
```

- Para obter detalhes da API, consulte a CreateJobreferência da API AWS SDK for Rust.

Excluir um crawler do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um crawler do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteCrawlerAsync(string crawlerName)
    {
        var response = await _amazonGlue.DeleteCrawlerAsync(new
DeleteCrawlerRequest { Name = crawlerName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
```

```
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteCrawlerRequest request;
        request.SetName(crawler);

        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
 client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteCrawler = (crawlerName) => {
  const client = new GlueClient({});

  const command = new DeleteCrawlerCommand({
    Name: crawlerName,
  });

  return client.send(command);
```

```
};
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the crawler.\n";
        $glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);

    public function deleteCrawler($crawlerName)
    {
        return $this->glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_crawler(self, name):
        """
        Deletes a crawler.

        :param name: The name of the crawler to delete.
        """
        try:
            self.glue_client.delete_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteCrawlerReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Deletes a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to delete.
  # @return [void]
  def delete_crawler(name)
    @glue_client.delete_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_crawler()
            .name(self.crawler())
            .send()
```

```
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteCrawlerreferência da API AWS SDK for Rust.

Excluir um banco de dados do AWS Glue Data Catalog usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um banco de dados do AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete the AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteDatabaseAsync(string dbName)
    {
        var response = await _amazonGlue.DeleteDatabaseAsync(new
DeleteDatabaseRequest { Name = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteDatabaseRequest request;
        request.SetName(database);

        Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the database." << std::endl;
        }
        else {
            std::cerr << "Error deleting database. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteDatabase = (databaseName) => {
  const client = new GlueClient({});

  const command = new DeleteDatabaseCommand({
    Name: databaseName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the databases.\n";
        $glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);

    public function deleteDatabase($databaseName)
```

```
    {
        return $this->glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_database(self, name):
        """
        Deletes a metadata database from your Data Catalog.

        :param name: The name of the database to delete.
        """
        try:
            self.glue_client.delete_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete database %s. Here's why: %s: %s",
```

```
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteDatabaseReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Removes a specified database from a Data Catalog.
  #
  # @param database_name [String] The name of the database to delete.
  # @return [void]
  def delete_database(database_name)
    @glue_client.delete_database(name: database_name)
  rescue Aws::Glue::Errors::ServiceError => e
```

```
  @logger.error("Glue could not delete database: \n#{e.message}")
end
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteDatabasereferência da API AWS SDK for Rust.

Excluir uma definição de trabalho do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteJobAsync(string jobName)
    {
        var response = await _amazonGlue.DeleteJobAsync(new DeleteJobRequest
{ JobName = jobName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";
```

```
    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteJobRequest request;
        request.SetJobName(job);

        Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the job." << std::endl;
        }
        else {
            std::cerr << "Error deleting the job. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para excluir um trabalho

O exemplo de `delete-job` a seguir exclui um trabalho que não é mais necessário.

```
aws glue delete-job \
    --job-name my-testing-job
```

Saída:

```
{
    "JobName": "my-testing-job"
}
```

Para obter mais informações, consulte Trabalhar com trabalhos no console do AWS Glue no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte DeleteJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteJob = (jobName) => {
  const client = new GlueClient({});

  const command = new DeleteJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the job.\n";
        $glueClient->deleteJob([
            'JobName' => $job['Name'],
        ]);

    public function deleteJob($jobName)
```

```
    {
        return $this->glueClient->deleteJob([
            'JobName' => $jobName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_job(self, job_name):
        """
        Deletes a job definition. This also deletes data about all runs that are
        associated with this job definition.

        :param job_name: The name of the job definition to delete.
        """
        try:
            self.glue_client.delete_job(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete job %s. Here's why: %s: %s",
                job_name,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteJobReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Deletes a job with the specified name.
  #
  # @param job_name [String] The name of the job to delete.
  # @return [void]
  def delete_job(job_name)
    @glue_client.delete_job(job_name: job_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
```

```
end
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_job()
            .job_name(self.job())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteJobreferência da API AWS SDK for Rust.

Excluir uma tabela do AWS Glue Data Catalog usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma tabela do AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a table from an AWS Glue database.
    /// </summary>
    /// <param name="tableName">The table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTableAsync(string dbName, string tableName)
    {
        var response = await _amazonGlue.DeleteTableAsync(new DeleteTableRequest
 { Name = tableName, DatabaseName = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteTable = (databaseName, tableName) => {
  const client = new GlueClient({});

  const command = new DeleteTableCommand({
```

```
    DatabaseName: databaseName,
    Name: tableName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the tables.\n";
        foreach ($tables['TableList'] as $table) {
            $glueService->deleteTable($table['Name'], $databaseName);
        }

    public function deleteTable($tableName, $databaseName)
    {
        return $this->glueClient->deleteTable([
            'DatabaseName' => $databaseName,
            'Name' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_table(self, db_name, table_name):
        """
        Deletes a table from a metadata database.

        :param db_name: The name of the database that contains the table.
        :param table_name: The name of the table to delete.
        """
        try:
            self.glue_client.delete_table(DatabaseName=db_name, Name=table_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Deletes a table with the specified name.
  #
  # @param database_name [String] The name of the catalog database in which the
 table resides.
  # @param table_name [String] The name of the table to be deleted.
  # @return [void]
  def delete_table(database_name, table_name)
    @glue_client.delete_table(database_name: database_name, name: table_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        for t in &self.tables {
            glue.delete_table()
                .name(t.name())
                .database_name(self.database())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
        }
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for Rust.

Obter um crawler do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como obter um crawler do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Crawler object describing the crawler.</returns>
    public async Task<Crawler?> GetCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new GetCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.GetCrawlerAsync(crawlerRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            var databaseName = response.Crawler.DatabaseName;
            Console.WriteLine($"{crawlerName} has the database {databaseName}");
            return response.Crawler;
        }

        Console.WriteLine($"No information regarding {crawlerName} could be
found.");
        return null;
    }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
```

```
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

        if (outcome.IsSuccess()) {
            Aws::Glue::Model::CrawlerState crawlerState =
 outcome.GetResult().GetCrawler().GetState();
            std::cout << "Retrieved crawler with state " <<

 Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                              crawlerState)
                      << "." << std::endl;
        }
        else {
            std::cerr << "Error retrieving a crawler.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetCrawlerRequest;
import software.amazon.awssdk.services.glue.model.GetCrawlerResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <crawlerName>

                Where:
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String crawlerName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getSpecificCrawler(glueClient, crawlerName);
        glueClient.close();
    }
```

```
    public static void getSpecificCrawler(GlueClient glueClient, String
 crawlerName) {
        try {
            GetCrawlerRequest crawlerRequest = GetCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            GetCrawlerResponse response = glueClient.getCrawler(crawlerRequest);
            Instant createDate = response.crawler().creationTime();

            // Convert the Instant to readable date
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the Crawler is " +
 createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getCrawler = (name) => {
  const client = new GlueClient({});

  const command = new GetCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificCrawler(crawlerName: String?) {

    val request = GetCrawlerRequest {
        name = crawlerName
    }
    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getCrawler(request)
        val role = response.crawler?.role
        println("The role associated with this crawler is $role")
    }
}
```

- Para obter detalhes da API, consulte a GetCrawlerreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Waiting for crawler";
        do {
            $crawler = $glueService->getCrawler($crawlerName);
            echo ".";
            sleep(10);
        } while ($crawler['Crawler']['State'] != "READY");
        echo "\n";

    public function getCrawler($crawlerName)
    {
        return $this->customWaiter(function () use ($crawlerName) {
            return $this->glueClient->getCrawler([
                'Name' => $crawlerName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_crawler(self, name):
        """
        Gets information about a crawler.

        :param name: The name of the crawler to look up.
        :return: Data about the crawler.
        """
        crawler = None
        try:
            response = self.glue_client.get_crawler(Name=name)
            crawler = response["Crawler"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityNotFoundException":
                logger.info("Crawler %s doesn't exist.", name)
            else:
                logger.error(
                    "Couldn't get crawler %s. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return crawler
```

- Para obter detalhes da API, consulte a GetCrawlerReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific crawler.
  #
  # @param name [String] The name of the crawler to retrieve information about.
  # @return [Aws::Glue::Types::Crawler, nil] The crawler object if found, or nil
 if not found.
  def get_crawler(name)
    @glue_client.get_crawler(name: name)
  rescue Aws::Glue::Errors::EntityNotFoundException
    @logger.info("Crawler #{name} doesn't exist.")
    false
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            let tmp_crawler = glue
                .get_crawler()
                .name(self.crawler())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a GetCrawlerreferência da API AWS SDK for Rust.

Obter um banco de dados do AWS Glue Data Catalog usando um AWS SDK

Os exemplos de código a seguir mostram como obter um banco de dados do AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Database object containing information about the database.</
returns>
    public async Task<Database> GetDatabaseAsync(string dbName)
    {
        var databasesRequest = new GetDatabaseRequest
        {
            Name = dbName,
        };

        var response = await _amazonGlue.GetDatabaseAsync(databasesRequest);
        return response.Database;
    }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetDatabaseRequest request;
        request.SetName(CRAWLER_DATABASE_NAME);
```

```
        Aws::Glue::Model::GetDatabaseOutcome outcome =
client.GetDatabase(request);

        if (outcome.IsSuccess()) {
            const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

            std::cout << "Successfully retrieve the database\n" <<
                      database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
        }
        else {
            std::cerr << "Error getting the database.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetDatabaseRequest;
import software.amazon.awssdk.services.glue.model.GetDatabaseResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetDatabase {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <databaseName>

                Where:
                    databaseName - The name of the database.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String databaseName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getSpecificDatabase(glueClient, databaseName);
        glueClient.close();
    }

    public static void getSpecificDatabase(GlueClient glueClient, String
 databaseName) {
        try {
            GetDatabaseRequest databasesRequest = GetDatabaseRequest.builder()
                    .name(databaseName)
                    .build();
```

```
            GetDatabaseResponse response =
 glueClient.getDatabase(databasesRequest);
            Instant createDate = response.database().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the database is " +
 createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getDatabase = (name) => {
  const client = new GlueClient({});

  const command = new GetDatabaseCommand({
    Name: name,
  });
```

```
  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificDatabase(databaseName: String?) {

    val request = GetDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getDatabase(request)
        val dbDesc = response.database?.description
        println("The database description is $dbDesc")
    }
}
```

- Para obter detalhes da API, consulte a GetDatabasereferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $databaseName = "doc-example-database-$uniqid";

        $database = $glueService->getDatabase($databaseName);
        echo "Found a database named " . $database['Database']['Name'] . "\n";

    public function getDatabase(string $databaseName): Result
    {
        return $this->customWaiter(function () use ($databaseName) {
            return $this->glueClient->getDatabase([
                'Name' => $databaseName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""
```

```
    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_database(self, name):
        """
        Gets information about a database in your Data Catalog.

        :param name: The name of the database to look up.
        :return: Information about the database.
        """
        try:
            response = self.glue_client.get_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't get database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Database"]
```

- Para obter detalhes da API, consulte a GetDatabaseReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific database.
  #
  # @param name [String] The name of the database to retrieve information about.
  # @return [Aws::Glue::Types::Database, nil] The database object if found, or
 nil if not found.
  def get_database(name)
    response = @glue_client.get_database(name: name)
    response.database
rescue Aws::Glue::Errors::GlueException => e
  @logger.error("Glue could not get database #{name}: \n#{e.message}")
  raise
  end
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let database = glue
            .get_database()
```

```
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?
            .to_owned();
        let database = database
            .database()
            .ok_or_else(|| GlueMvpError::Unknown("Could not find
database".into()))?;
```

- Para obter detalhes da API, consulte a GetDatabasereferência da API AWS SDK for Rust.

Obter uma execução de trabalho do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como obter uma execução de trabalho do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about a specific AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="jobRunId">The Id of the job run.</param>
    /// <returns>A JobRun object with information about the job run.</returns>
    public async Task<JobRun> GetJobRunAsync(string jobName, string jobRunId)
    {
```

```
        var response = await _amazonGlue.GetJobRunAsync(new GetJobRunRequest
{ JobName = jobName, RunId = jobRunId });
        return response.JobRun;
    }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetJobRunRequest jobRunRequest;
        jobRunRequest.SetJobName(jobName);
        jobRunRequest.SetRunId(jobRunID);

        Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                jobRunRequest);

        if (jobRunOutcome.IsSuccess()) {
            std::cout << "Displaying the job run JSON description." << std::endl;
            std::cout
                    <<
jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                    << std::endl;
        }
        else {
            std::cerr << "Error get a job run. "
```

```
                        << jobRunOutcome.GetError().GetMessage()
                        << std::endl;
        }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para obter informações sobre uma execução de trabalho

O exemplo `get-job-run` a seguir recupera informações sobre uma execução de trabalho.

```
aws glue get-job-run \
    --job-name "Combine legistators data" \
    --run-id jr_012e176506505074d94d761755e5c62538ee1aad6f17d39f527e9140cf0c9a5e
```

Saída:

```
{
    "JobRun": {
        "Id":
 "jr_012e176506505074d94d761755e5c62538ee1aad6f17d39f527e9140cf0c9a5e",
        "Attempt": 0,
        "JobName": "Combine legistators data",
        "StartedOn": 1602873931.255,
        "LastModifiedOn": 1602874075.985,
        "CompletedOn": 1602874075.985,
        "JobRunState": "SUCCEEDED",
        "Arguments": {
            "--enable-continuous-cloudwatch-log": "true",
            "--enable-metrics": "",
            "--enable-spark-ui": "true",
            "--job-bookmark-option": "job-bookmark-enable",
            "--spark-event-logs-path": "s3://aws-glue-assets-111122223333-us-
east-1/sparkHistoryLogs/"
        },
        "PredecessorRuns": [],
        "AllocatedCapacity": 10,
        "ExecutionTime": 117,
```

```
        "Timeout": 2880,
        "MaxCapacity": 10.0,
        "WorkerType": "G.1X",
        "NumberOfWorkers": 10,
        "LogGroupName": "/aws-glue/jobs",
        "GlueVersion": "2.0"
    }
}
```

Para obter mais informações, consulte Execuções de trabalhos no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte GetJobRunem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJobRun = (jobName, jobRunId) => {
  const client = new GlueClient({});
  const command = new GetJobRunCommand({
    JobName: jobName,
    RunId: jobRunId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobName = 'test-job-' . $uniqid;

        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl)['JobRunId'];

        echo "waiting for job";
        do {
            $jobRun = $glueService->getJobRun($jobName, $runId);
            echo ".";
            sleep(10);
        } while (!array_intersect([$jobRun['JobRun']['JobRunState']],
['SUCCEEDED', 'STOPPED', 'FAILED', 'TIMEOUT']));
        echo "\n";

    public function getJobRun($jobName, $runId, $predecessorsIncluded = false):
Result
    {
        return $this->glueClient->getJobRun([
            'JobName' => $jobName,
            'RunId' => $runId,
            'PredecessorsIncluded' => $predecessorsIncluded,
        ]);
    }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_job_run(self, name, run_id):
        """
        Gets information about a single job run.

        :param name: The name of the job definition for the run.
        :param run_id: The ID of the run.
        :return: Information about the run.
        """
        try:
            response = self.glue_client.get_job_run(JobName=name, RunId=run_id)
        except ClientError as err:
            logger.error(
                "Couldn't get job run %s/%s. Here's why: %s: %s",
                name,
                run_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRun"]
```

- Para obter detalhes da API, consulte a GetJobRunReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves data for a specific job run.
  #
  # @param job_name [String] The name of the job run to retrieve data for.
  # @return [Glue::Types::GetJobRunResponse]
  def get_job_run(job_name, run_id)
    @glue_client.get_job_run(job_name: job_name, run_id: run_id)
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let get_job_run = || async {
            Ok::<JobRun, GlueMvpError>(
                glue.get_job_run()
                    .job_name(self.job())
                    .run_id(job_run_id.to_string())
                    .send()
                    .await
                    .map_err(GlueMvpError::from_glue_sdk)?
                    .job_run()
                    .ok_or_else(|| GlueMvpError::Unknown("Failed to get
job_run".into()))?
                    .to_owned(),
            )
        };

        let mut job_run = get_job_run().await?;
        let mut state =
job_run.job_run_state().unwrap_or(&unknown_state).to_owned();

        while matches!(
            state,
            JobRunState::Starting | JobRunState::Stopping | JobRunState::Running
        ) {
            info!(?state, "Waiting for job to finish");
            tokio::time::sleep(self.wait_delay).await;

            job_run = get_job_run().await?;
            state = job_run.job_run_state().unwrap_or(&unknown_state).to_owned();
        }
```

- Para obter detalhes da API, consulte a GetJobRunreferência da API AWS SDK for Rust.

Obter uma lista de bancos de dados do AWS Glue Data Catalog usando um AWS SDK

Os exemplos de código a seguir mostram como obter uma lista de bancos de dados do AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

CLI

AWS CLI

Para listar as definições de alguns ou de todos os bancos de dados no Catálogo de Dados do AWS Glue

O exemplo de `get-databases` a seguir retorna informações sobre os bancos de dados no Catálogo de Dados.

```
aws glue get-databases
```

Saída:

```
{
    "DatabaseList": [
        {
            "Name": "default",
            "Description": "Default Hive database",
            "LocationUri": "file:/spark-warehouse",
            "CreateTime": 1602084052.0,
            "CreateTableDefaultPermissions": [
                {
                    "Principal": {
                        "DataLakePrincipalIdentifier": "IAM_ALLOWED_PRINCIPALS"
                    },
                    "Permissions": [
                        "ALL"
                    ]
                }
            ],
```

```
            "CatalogId": "111122223333"
        },
        {
            "Name": "flights-db",
            "CreateTime": 1587072847.0,
            "CreateTableDefaultPermissions": [
                {
                    "Principal": {
                        "DataLakePrincipalIdentifier": "IAM_ALLOWED_PRINCIPALS"
                    },
                    "Permissions": [
                        "ALL"
                    ]
                }
            ],
            "CatalogId": "111122223333"
        },
        {
            "Name": "legislators",
            "CreateTime": 1601415625.0,
            "CreateTableDefaultPermissions": [
                {
                    "Principal": {
                        "DataLakePrincipalIdentifier": "IAM_ALLOWED_PRINCIPALS"
                    },
                    "Permissions": [
                        "ALL"
                    ]
                }
            ],
            "CatalogId": "111122223333"
        },
        {
            "Name": "tempdb",
            "CreateTime": 1601498566.0,
            "CreateTableDefaultPermissions": [
                {
                    "Principal": {
                        "DataLakePrincipalIdentifier": "IAM_ALLOWED_PRINCIPALS"
                    },
                    "Permissions": [
                        "ALL"
                    ]
                }
```

```
            ],
            "CatalogId": "111122223333"
        }
    ]
}
```

Para obter mais informações, consulte Definir um banco de dados no seu Catálogo de Dados no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte GetDatabasesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getDatabases = () => {
  const client = new GlueClient({});

  const command = new GetDatabasesCommand({});

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetDatabasesa Referência AWS SDK for JavaScript da API.

Obter um trabalho do AWS Glue Data Catalog usando um AWS SDK

Os exemplos de código a seguir mostram como obter um trabalho do AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

CLI

AWS CLI

Para recuperar informações sobre um trabalho

O exemplo de `get-job` a seguir recupera informações sobre um trabalho.

```
aws glue get-job \
    --job-name my-testing-job
```

Saída:

```
{
    "Job": {
        "Name": "my-testing-job",
        "Role": "Glue_DefaultRole",
        "CreatedOn": 1602805698.167,
        "LastModifiedOn": 1602805698.167,
        "ExecutionProperty": {
            "MaxConcurrentRuns": 1
        },
        "Command": {
            "Name": "gluestreaming",
            "ScriptLocation": "s3://janetst-bucket-01/Scripts/test_script.scala",
            "PythonVersion": "2"
        },
        "DefaultArguments": {
            "--class": "GlueApp",
            "--job-language": "scala"
        },
        "MaxRetries": 0,
        "AllocatedCapacity": 10,
        "MaxCapacity": 10.0,
        "GlueVersion": "1.0"
    }
}
```

Para obter mais informações, consulte Trabalhos no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte GetJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJob = (jobName) => {
  const client = new GlueClient({});

  const command = new GetJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for JavaScript da API.

Obter execuções de um trabalho do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como obter execuções de um trabalho do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about all AWS Glue runs of a specific job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A list of JobRun objects.</returns>
    public async Task<List<JobRun>> GetJobRunsAsync(string jobName)
    {
        var jobRuns = new List<JobRun>();

        var request = new GetJobRunsRequest
        {
            JobName = jobName,
        };

        // No need to loop to get all the log groups--the SDK does it for us
behind the scenes
        var paginatorForJobRuns =
            _amazonGlue.Paginators.GetJobRuns(request);

        await foreach (var response in paginatorForJobRuns.Responses)
        {
            response.JobRuns.ForEach(jobRun =>
            {
                jobRuns.Add(jobRun);
            });
        }

        return jobRuns;
    }
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);

        Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                getJobRunsRequest);

        if (jobRunsOutcome.IsSuccess()) {
            std::vector<Aws::Glue::Model::JobRun> jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
            std::cout << "There are " << jobRuns.size() << " runs in the job '"
                      <<
                      jobName << "'." << std::endl;

            for (size_t i = 0; i < jobRuns.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobRuns[i].GetJobName()
                          << std::endl;
            }

            int runIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobRuns.size()) +
                    " to see details for a run: ",
                    1, static_cast<int>(jobRuns.size()));
```

```
            jobRunID = jobRuns[runIndex - 1].GetId();
        }
        else {
            std::cerr << "Error getting job runs. "
                      << jobRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para obter informações sobre todas as execuções de um trabalho

O exemplo `get-job-runs` a seguir recupera informações sobre execuções de trabalho para um trabalho.

```
aws glue get-job-runs \
    --job-name "my-testing-job"
```

Saída:

```
{
    "JobRuns": [
        {
            "Id":
 "jr_012e176506505074d94d761755e5c62538ee1aad6f17d39f527e9140cf0c9a5e",
            "Attempt": 0,
            "JobName": "my-testing-job",
            "StartedOn": 1602873931.255,
            "LastModifiedOn": 1602874075.985,
            "CompletedOn": 1602874075.985,
            "JobRunState": "SUCCEEDED",
            "Arguments": {
                "--enable-continuous-cloudwatch-log": "true",
                "--enable-metrics": "",
                "--enable-spark-ui": "true",
                "--job-bookmark-option": "job-bookmark-enable",
```

```
                "--spark-event-logs-path": "s3://aws-glue-assets-111122223333-us-
east-1/sparkHistoryLogs/"
            },
            "PredecessorRuns": [],
            "AllocatedCapacity": 10,
            "ExecutionTime": 117,
            "Timeout": 2880,
            "MaxCapacity": 10.0,
            "WorkerType": "G.1X",
            "NumberOfWorkers": 10,
            "LogGroupName": "/aws-glue/jobs",
            "GlueVersion": "2.0"
        },
        {
            "Id":
 "jr_03cc19ddab11c4e244d3f735567de74ff93b0b3ef468a713ffe73e53d1aec08f_attempt_2",
            "Attempt": 2,
            "PreviousRunId":
 "jr_03cc19ddab11c4e244d3f735567de74ff93b0b3ef468a713ffe73e53d1aec08f_attempt_1",
            "JobName": "my-testing-job",
            "StartedOn": 1602811168.496,
            "LastModifiedOn": 1602811282.39,
            "CompletedOn": 1602811282.39,
            "JobRunState": "FAILED",
            "ErrorMessage": "An error occurred while calling
 o122.pyWriteDynamicFrame.
                Access Denied (Service: Amazon S3; Status Code: 403; Error Code:
 AccessDenied;
                Request ID: 021AAB703DB20A2D;
                S3 Extended Request ID: teZk24Y09TkXzBvMPG502L5VJBhe9DJuWA9/
TXtuGOqfByajkfL/Tlqt5JBGdEGpigAqzdMDM/U=)",
            "PredecessorRuns": [],
            "AllocatedCapacity": 10,
            "ExecutionTime": 110,
            "Timeout": 2880,
            "MaxCapacity": 10.0,
            "WorkerType": "G.1X",
            "NumberOfWorkers": 10,
            "LogGroupName": "/aws-glue/jobs",
            "GlueVersion": "2.0"
        },
        {
            "Id":
 "jr_03cc19ddab11c4e244d3f735567de74ff93b0b3ef468a713ffe73e53d1aec08f_attempt_1",
```

```
            "Attempt": 1,
            "PreviousRunId":
 "jr_03cc19ddab11c4e244d3f735567de74ff93b0b3ef468a713ffe73e53d1aec08f",
            "JobName": "my-testing-job",
            "StartedOn": 1602811020.518,
            "LastModifiedOn": 1602811138.364,
            "CompletedOn": 1602811138.364,
            "JobRunState": "FAILED",
            "ErrorMessage": "An error occurred while calling
 o122.pyWriteDynamicFrame.
                 Access Denied (Service: Amazon S3; Status Code: 403; Error Code:
 AccessDenied;
                 Request ID: 2671D37856AE7ABB;
                 S3 Extended Request ID: RLJCJw20brV
+PpC6GpORahyF2fp9flB5SSb2bTGPnUSPVizLXRl1PN3QZldb+v1o9qRVktNYbW8=)",
            "PredecessorRuns": [],
            "AllocatedCapacity": 10,
            "ExecutionTime": 113,
            "Timeout": 2880,
            "MaxCapacity": 10.0,
            "WorkerType": "G.1X",
            "NumberOfWorkers": 10,
            "LogGroupName": "/aws-glue/jobs",
            "GlueVersion": "2.0"
        }
    ]
}
```

Para obter mais informações, consulte Execuções de trabalhos no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte GetJobRunsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJobRuns = (jobName) => {
  const client = new GlueClient({});
  const command = new GetJobRunsCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobName = 'test-job-' . $uniqid;

        $jobRuns = $glueService->getJobRuns($jobName);

    public function getJobRuns($jobName, $maxResults = 0, $nextToken = ''):
 Result
    {
        $arguments = ['JobName' => $jobName];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        return $this->glueClient->getJobRuns($arguments);
    }
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_job_runs(self, job_name):
        """
        Gets information about runs that have been performed for a specific job
        definition.

        :param job_name: The name of the job definition to look up.
        :return: The list of job runs.
        """
        try:
            response = self.glue_client.get_job_runs(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't get job runs for %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRuns"]
```

- Para obter detalhes da API, consulte a GetJobRunsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of job runs for the specified job.
  #
  # @param job_name [String] The name of the job to retrieve job runs for.
  # @return [Array<Aws::Glue::Types::JobRun>]
  def get_job_runs(job_name)
    response = @glue_client.get_job_runs(job_name: job_name)
    response.job_runs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for Ruby da API.

Obter tabelas de um banco de dados do AWS Glue Data Catalog um AWS SDK

Os exemplos de código a seguir mostram como obter tabelas de um banco de dados no AWS Glue Data Catalog.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of tables for an AWS Glue database.
/// </summary>
/// <param name="dbName">The name of the database.</param>
/// <returns>A list of Table objects.</returns>
public async Task<List<Table>> GetTablesAsync(string dbName)
{
    var request = new GetTablesRequest { DatabaseName = dbName };
    var tables = new List<Table>();

    // Get a paginator for listing the tables.
    var tablePaginator = _amazonGlue.Paginators.GetTables(request);

    await foreach (var response in tablePaginator.Responses)
    {
        tables.AddRange(response.TableList);
    }

    return tables;
```

```
    }
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::GetTablesRequest request;
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);

       Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

       if (outcome.IsSuccess()) {
           const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
           std::cout << "The database contains " << tables.size()
                     << (tables.size() == 1 ?
                         " table." : "tables.") << std::endl;
           std::cout << "Here is a list of the tables in the database.";
           for (size_t index = 0; index < tables.size(); ++index) {
               std::cout << "    " << index + 1 << ":  " <<
tables[index].GetName()
                         << std::endl;
           }

           if (!tables.empty()) {
```

```
                int tableIndex = askQuestionForIntRange(
                        "Enter an index to display the database detail ",
                        1, static_cast<int>(tables.size()));
                std::cout << tables[tableIndex -
 1].Jsonize().View().WriteReadable()
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error getting the tables. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para listar as definições de algumas ou de todas as tabelas no banco de dados especificado

O exemplo de `get-tables` a seguir retorna informações sobre as tabelas no banco de dados especificado.

```
aws glue get-tables --database-name 'tempdb'
```

Saída:

```
{
    "TableList": [
        {
            "Name": "my-s3-sink",
            "DatabaseName": "tempdb",
            "CreateTime": 1602730539.0,
            "UpdateTime": 1602730539.0,
            "Retention": 0,
            "StorageDescriptor": {
```

```
                "Columns": [
                    {
                        "Name": "sensorid",
                        "Type": "int"
                    },
                    {
                        "Name": "currenttemperature",
                        "Type": "int"
                    },
                    {
                        "Name": "status",
                        "Type": "string"
                    }
                ],
                "Location": "s3://janetst-bucket-01/test-s3-output/",
                "Compressed": false,
                "NumberOfBuckets": 0,
                "SerdeInfo": {
                    "SerializationLibrary": "org.openx.data.jsonserde.JsonSerDe"
                },
                "SortColumns": [],
                "StoredAsSubDirectories": false
            },
            "Parameters": {
                "classification": "json"
            },
            "CreatedBy": "arn:aws:iam::007436865787:user/JRSTERN",
            "IsRegisteredWithLakeFormation": false,
            "CatalogId": "007436865787"
        },
        {
            "Name": "s3-source",
            "DatabaseName": "tempdb",
            "CreateTime": 1602730658.0,
            "UpdateTime": 1602730658.0,
            "Retention": 0,
            "StorageDescriptor": {
                "Columns": [
                    {
                        "Name": "sensorid",
                        "Type": "int"
                    },
                    {
                        "Name": "currenttemperature",
```

```
                        "Type": "int"
                    },
                    {
                        "Name": "status",
                        "Type": "string"
                    }
                ],
                "Location": "s3://janetst-bucket-01/",
                "Compressed": false,
                "NumberOfBuckets": 0,
                "SortColumns": [],
                "StoredAsSubDirectories": false
            },
            "Parameters": {
                "classification": "json"
            },
            "CreatedBy": "arn:aws:iam::007436865787:user/JRSTERN",
            "IsRegisteredWithLakeFormation": false,
            "CatalogId": "007436865787"
        },
        {
            "Name": "test-kinesis-input",
            "DatabaseName": "tempdb",
            "CreateTime": 1601507001.0,
            "UpdateTime": 1601507001.0,
            "Retention": 0,
            "StorageDescriptor": {
                "Columns": [
                    {
                        "Name": "sensorid",
                        "Type": "int"
                    },
                    {
                        "Name": "currenttemperature",
                        "Type": "int"
                    },
                    {
                        "Name": "status",
                        "Type": "string"
                    }
                ],
                "Location": "my-testing-stream",
                "Compressed": false,
                "NumberOfBuckets": 0,
```

```
                "SerdeInfo": {
                    "SerializationLibrary": "org.openx.data.jsonserde.JsonSerDe"
                },
                "SortColumns": [],
                "Parameters": {
                    "kinesisUrl": "https://kinesis.us-east-1.amazonaws.com",
                    "streamName": "my-testing-stream",
                    "typeOfData": "kinesis"
                },
                "StoredAsSubDirectories": false
            },
            "Parameters": {
                "classification": "json"
            },
            "CreatedBy": "arn:aws:iam::007436865787:user/JRSTERN",
            "IsRegisteredWithLakeFormation": false,
            "CatalogId": "007436865787"
        }
    ]
}
```

Para obter mais informações, consulte Definição de tabelas no catálogo de dados do AWS Glue no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte GetTablesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetTableRequest;
import software.amazon.awssdk.services.glue.model.GetTableResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
```

```
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbName> <tableName>

                Where:
                    dbName - The database name.\s
                    tableName - The name of the table.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbName = args[0];
        String tableName = args[1];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getGlueTable(glueClient, dbName, tableName);
        glueClient.close();
    }

    public static void getGlueTable(GlueClient glueClient, String dbName, String
 tableName) {
```

```
        try {
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .databaseName(dbName)
                    .name(tableName)
                    .build();

            GetTableResponse tableResponse = glueClient.getTable(tableRequest);
            Instant createDate = tableResponse.table().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the table is " + createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getTables = (databaseName) => {
  const client = new GlueClient({});

  const command = new GetTablesCommand({
```

```
    DatabaseName: databaseName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $databaseName = "doc-example-database-$uniqid";

        $tables = $glueService->getTables($databaseName);

    public function getTables($databaseName): Result
    {
        return $this->glueClient->getTables([
            'DatabaseName' => $databaseName,
        ]);
    }
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_tables(self, db_name):
        """
        Gets a list of tables in a Data Catalog database.

        :param db_name: The name of the database to query.
        :return: The list of tables in the database.
        """
        try:
            response = self.glue_client.get_tables(DatabaseName=db_name)
        except ClientError as err:
            logger.error(
                "Couldn't get tables %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["TableList"]
```

- Para obter detalhes da API, consulte a GetTablesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of tables in the specified database.
  #
  # @param db_name [String] The name of the database to retrieve tables from.
  # @return [Array<Aws::Glue::Types::Table>]
  def get_tables(db_name)
    response = @glue_client.get_tables(database_name: db_name)
    response.table_list
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get tables #{db_name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let tables = glue
            .get_tables()
            .database_name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let tables = tables.table_list();
```

- Para obter detalhes da API, consulte a GetTablesreferência da API AWS SDK for Rust.

Listar definições de trabalhos do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como listas definições de trabalho do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List AWS Glue jobs using a paginator.
    /// </summary>
    /// <returns>A list of AWS Glue job names.</returns>
    public async Task<List<string>> ListJobsAsync()
    {
        var jobNames = new List<string>();

        var listJobsPaginator = _amazonGlue.Paginators.ListJobs(new
ListJobsRequest { MaxResults = 10 });
        await foreach (var response in listJobsPaginator.Responses)
        {
            jobNames.AddRange(response.JobNames);
        }

        return jobNames;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::ListJobsRequest listJobsRequest;
        Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
```

```
                listJobsRequest);

        if (listRunsOutcome.IsSuccess()) {
            const std::vector<Aws::String> &jobNames =
 listRunsOutcome.GetResult().GetJobNames();
            std::cout << "Your account has " << jobNames.size() << " jobs."
                      << std::endl;
            for (size_t i = 0; i < jobNames.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobNames[i] << std::endl;
            }
            int jobIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobNames.size()) +
                    " to see the list of runs for a job: ",
                    1, static_cast<int>(jobNames.size()));

            jobName = jobNames[jobIndex - 1];
        }
        else {
            std::cerr << "Error listing jobs. "
                      << listRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listJobs = () => {
  const client = new GlueClient({});

  const command = new ListJobsCommand({});
```

```
  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobs = $glueService->listJobs();
        echo "Current jobs:\n";
        foreach ($jobs['JobNames'] as $jobsName) {
            echo "{$jobsName}\n";
        }

    public function listJobs($maxResults = null, $nextToken = null, $tags = []):
Result
    {
        $arguments = [];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        if (!empty($tags)) {
            $arguments['Tags'] = $tags;
        }
        return $this->glueClient->listJobs($arguments);
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def list_jobs(self):
        """
        Lists the names of job definitions in your account.

        :return: The list of job definition names.
        """
        try:
            response = self.glue_client.list_jobs()
        except ClientError as err:
            logger.error(
                "Couldn't list jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobNames"]
```

- Para obter detalhes da API, consulte a ListJobsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of jobs in AWS Glue.
  #
  # @return [Aws::Glue::Types::ListJobsResponse]
  def list_jobs
    @glue_client.list_jobs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not list jobs: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let mut list_jobs = glue.list_jobs().into_paginator().send();
        while let Some(list_jobs_output) = list_jobs.next().await {
            match list_jobs_output {
                Ok(list_jobs) => {
                    let names = list_jobs.job_names();
                    info!(?names, "Found these jobs")
                }
                Err(err) => return Err(GlueMvpError::from_glue_sdk(err)),
            }
        }
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWS SDK for Rust.

Iniciar um crawler do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como iniciar um crawler do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Start an AWS Glue crawler.
/// </summary>
/// <param name="crawlerName">The name of the crawler.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> StartCrawlerAsync(string crawlerName)
{
    var crawlerRequest = new StartCrawlerRequest
    {
        Name = crawlerName,
    };

    var response = await _amazonGlue.StartCrawlerAsync(crawlerRequest);

    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::StartCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


        if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
                                    outcome.GetError().GetErrorType())) {
            if (!outcome.IsSuccess()) {
                std::cout << "Crawler was already started." << std::endl;
            }
            else {
                std::cout << "Successfully started crawler." << std::endl;
            }

            std::cout << "This may take a while to run." << std::endl;

            Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
            int iterations = 0;
            while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
                ++iterations;
                if ((iterations % 10) == 0) { // Log status every 10 seconds.
                    std::cout << "Crawler status " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                        crawlerState)
                                << ". After " << iterations
                                << " seconds elapsed."
                                << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);
```

```
                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                              << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }

            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para iniciar um crawler

O exemplo de `start-crawler` a seguir inicia um crawler.

```
aws glue start-crawler --name my-crawler
```

Saída:

```
None
```

Para obter mais informações, consulte Definição de crawlers no Guia do desenvolvedor do AWS Glue.

- Para obter detalhes da API, consulte StartCrawlerem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GlueException;
import software.amazon.awssdk.services.glue.model.StartCrawlerRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class StartCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
```

```
                    <crawlerName>

                Where:
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String crawlerName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        startSpecificCrawler(glueClient, crawlerName);
        glueClient.close();
    }

    public static void startSpecificCrawler(GlueClient glueClient, String
 crawlerName) {
        try {
            StartCrawlerRequest crawlerRequest = StartCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.startCrawler(crawlerRequest);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const startCrawler = (name) => {
  const client = new GlueClient({});

  const command = new StartCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startSpecificCrawler(crawlerName: String?) {

    val request = StartCrawlerRequest {
        name = crawlerName
    }
```

```
    GlueClient { region = "us-west-2" }.use { glueClient ->
        glueClient.startCrawler(request)
        println("$crawlerName was successfully started.")
    }
}
```

- Para obter detalhes da API, consulte a StartCrawlerreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $crawlerName = "example-crawler-test-" . $uniqid;

        $databaseName = "doc-example-database-$uniqid";

        $glueService->startCrawler($crawlerName);

    public function startCrawler($crawlerName): Result
    {
        return $this->glueClient->startCrawler([
            'Name' => $crawlerName,
        ]);
    }
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def start_crawler(self, name):
        """
        Starts a crawler. The crawler crawls its configured target and creates
        metadata that describes the data it finds in the target data source.

        :param name: The name of the crawler to start.
        """
        try:
            self.glue_client.start_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't start crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a StartCrawlerReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Starts a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to start.
  # @return [void]
  def start_crawler(name)
    @glue_client.start_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not start crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let start_crawler =
glue.start_crawler().name(self.crawler()).send().await;

        match start_crawler {
            Ok(_) => Ok(()),
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::CrawlerRunningException(_) => Ok(()),
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
        }?;
```

- Para obter detalhes da API, consulte a StartCrawlerreferência da API AWS SDK for Rust.

Iniciar uma execução de trabalho do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como iniciar uma execução de trabalho do AWS Glue.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a executar crawlers e trabalhos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Start an AWS Glue job run.
/// </summary>
/// <param name="jobName">The name of the job.</param>
/// <returns>A string representing the job run Id.</returns>
public async Task<string> StartJobRunAsync(
    string jobName,
    string inputDatabase,
    string inputTable,
    string bucketName)
{
    var request = new StartJobRunRequest
    {
        JobName = jobName,
        Arguments = new Dictionary<string, string>
        {
            {"--input_database", inputDatabase},
            {"--input_table", inputTable},
            {"--output_bucket_url", $"s3://{bucketName}/"}
        }
    };

    var response = await _amazonGlue.StartJobRunAsync(request);
    return response.JobRunId;
}
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName +
"/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome =
client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;

            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
```

```
                jobRunRequest.SetRunId(jobRunId);

                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome =
client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();

                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED)
||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT))
{
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME,
JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10
seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                            jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
                    }
                }
                else {
                    std::cerr << "Error retrieving job run state. "
```

```
                                << jobRunOutcome.GetError().GetMessage()
                                << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                     bucketName, clientConfig);
                        return false;
                    }
                }
            }
            else {
                std::cerr << "Error starting a job. " <<
 outcome.GetError().GetMessage()
                          << std::endl;
                deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
 bucketName,
                             clientConfig);
                return false;
            }
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para iniciar a execução de um trabalho

O exemplo de `start-job-run` a seguir inicia um trabalho.

```
aws glue start-job-run \
    --job-name my-job
```

Saída:

```
{
    "JobRunId":
 "jr_22208b1f44eb5376a60569d4b21dd20fcb8621e1a366b4e7b2494af764b82ded"
}
```

Para obter mais informações, consulte Criação de trabalhos no Guia do desenvolvedor do AWSGlue.

- Para obter detalhes da API, consulte StartJobRunem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const startJobRun = (jobName, dbName, tableName, bucketName) => {
  const client = new GlueClient({});

  const command = new StartJobRunCommand({
    JobName: jobName,
    Arguments: {
      "--input_database": dbName,
      "--input_table": tableName,
      "--output_bucket_url": `s3://${bucketName}/`,
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobName = 'test-job-' . $uniqid;
```

```
        $databaseName = "doc-example-database-$uniqid";

        $tables = $glueService->getTables($databaseName);

        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
 $outputBucketUrl)['JobRunId'];

    public function startJobRun($jobName, $databaseName, $tables,
 $outputBucketUrl): Result
    {
        return $this->glueClient->startJobRun([
            'JobName' => $jobName,
            'Arguments' => [
                'input_database' => $databaseName,
                'input_table' => $tables['TableList'][0]['Name'],
                'output_bucket_url' => $outputBucketUrl,
                '--input_database' => $databaseName,
                '--input_table' => $tables['TableList'][0]['Name'],
                '--output_bucket_url' => $outputBucketUrl,
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
```

```
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def start_job_run(self, name, input_database, input_table,
output_bucket_name):
        """
        Starts a job run. A job run extracts data from the source, transforms it,
        and loads it to the output bucket.

        :param name: The name of the job definition.
        :param input_database: The name of the metadata database that contains
tables
                               that describe the source data. This is typically
created
                               by a crawler.
        :param input_table: The name of the table in the metadata database that
                            describes the source data.
        :param output_bucket_name: The S3 bucket where the output is written.
        :return: The ID of the job run.
        """
        try:
            # The custom Arguments that are passed to this function are used by
the
            # Python ETL script to determine the location of input and output
data.
            response = self.glue_client.start_job_run(
                JobName=name,
                Arguments={
                    "--input_database": input_database,
                    "--input_table": input_table,
                    "--output_bucket_url": f"s3://{output_bucket_name}/",
                },
            )
        except ClientError as err:
            logger.error(
                "Couldn't start job run %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return response["JobRunId"]
```

- Para obter detalhes da API, consulte a StartJobRunReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Starts a job run for the specified job.
  #
  # @param name [String] The name of the job to start the run for.
  # @param input_database [String] The name of the input database for the job.
  # @param input_table [String] The name of the input table for the job.
  # @param output_bucket_name [String] The name of the output S3 bucket for the
 job.
  # @return [String] The ID of the started job run.
  def start_job_run(name, input_database, input_table, output_bucket_name)
    response = @glue_client.start_job_run(
```

```
      job_name: name,
      arguments: {
        '--input_database': input_database,
        '--input_table': input_table,
        '--output_bucket_url': "s3://#{output_bucket_name}/"
      }
    )
    response.job_run_id
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not start job run #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let job_run_output = glue
            .start_job_run()
            .job_name(self.job())
            .arguments("--input_database", self.database())
            .arguments(
                "--input_table",
                self.tables
                    .get(0)
                    .ok_or_else(|| GlueMvpError::Unknown("Missing crawler
table".into()))?
                    .name(),
            )
            .arguments("--output_bucket_url", self.bucket())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

```
        let job = job_run_output
            .job_run_id()
            .ok_or_else(|| GlueMvpError::Unknown("Missing run id from just
started job".into()))?
            .to_string();
```

- Para obter detalhes da API, consulte a StartJobRunreferência da API AWS SDK for Rust.

Cenários para o AWS Glue usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Glue com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Começar a executar crawlers e trabalhos do AWS Glue usando um AWS SDK

Começar a executar crawlers e trabalhos do AWS Glue usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que abranja as funções do AWS Glue usadas no cenário.

```
using System.Net;

namespace GlueActions;

public class GlueWrapper
{
    private readonly IAmazonGlue _amazonGlue;

    /// <summary>
    /// Constructor for the AWS Glue actions wrapper.
    /// </summary>
    /// <param name="amazonGlue"></param>
    public GlueWrapper(IAmazonGlue amazonGlue)
    {
        _amazonGlue = amazonGlue;
    }

    /// <summary>
    /// Create an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name for the crawler.</param>
    /// <param name="crawlerDescription">A description of the crawler.</param>
    /// <param name="role">The AWS Identity and Access Management (IAM) role to
    /// be assumed by the crawler.</param>
    /// <param name="schedule">The schedule on which the crawler will be
 executed.</param>
    /// <param name="s3Path">The path to the Amazon Simple Storage Service
 (Amazon S3)
    /// bucket where the Python script has been stored.</param>
    /// <param name="dbName">The name to use for the database that will be
```

```
    /// created by the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateCrawlerAsync(
        string crawlerName,
        string crawlerDescription,
        string role,
        string schedule,
        string s3Path,
        string dbName)
    {
        var s3Target = new S3Target
        {
            Path = s3Path,
        };

        var targetList = new List<S3Target>
        {
            s3Target,
        };

        var targets = new CrawlerTargets
        {
            S3Targets = targetList,
        };

        var crawlerRequest = new CreateCrawlerRequest
        {
            DatabaseName = dbName,
            Name = crawlerName,
            Description = crawlerDescription,
            Targets = targets,
            Role = role,
            Schedule = schedule,
        };

        var response = await _amazonGlue.CreateCrawlerAsync(crawlerRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Create an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
```

```
    /// <param name="roleName">The name of the IAM role to be assumed by
    /// the job.</param>
    /// <param name="description">A description of the job.</param>
    /// <param name="scriptUrl">The URL to the script.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateJobAsync(string dbName, string tableName,
 string bucketUrl, string jobName, string roleName, string description, string
 scriptUrl)
    {
        var command = new JobCommand
        {
            PythonVersion = "3",
            Name = "glueetl",
            ScriptLocation = scriptUrl,
        };

        var arguments = new Dictionary<string, string>
        {
            { "--input_database", dbName },
            { "--input_table", tableName },
            { "--output_bucket_url", bucketUrl }
        };

        var request = new CreateJobRequest
        {
            Command = command,
            DefaultArguments = arguments,
            Description = description,
            GlueVersion = "3.0",
            Name = jobName,
            NumberOfWorkers = 10,
            Role = roleName,
            WorkerType = "G.1X"
        };

        var response = await _amazonGlue.CreateJobAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteCrawlerAsync(string crawlerName)
    {
        var response = await _amazonGlue.DeleteCrawlerAsync(new
DeleteCrawlerRequest { Name = crawlerName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete the AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteDatabaseAsync(string dbName)
    {
        var response = await _amazonGlue.DeleteDatabaseAsync(new
DeleteDatabaseRequest { Name = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteJobAsync(string jobName)
    {
        var response = await _amazonGlue.DeleteJobAsync(new DeleteJobRequest
{ JobName = jobName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete a table from an AWS Glue database.
    /// </summary>
    /// <param name="tableName">The table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTableAsync(string dbName, string tableName)
    {
        var response = await _amazonGlue.DeleteTableAsync(new DeleteTableRequest
{ Name = tableName, DatabaseName = dbName });
```

```
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Get information about an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Crawler object describing the crawler.</returns>
    public async Task<Crawler?> GetCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new GetCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.GetCrawlerAsync(crawlerRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            var databaseName = response.Crawler.DatabaseName;
            Console.WriteLine($"{crawlerName} has the database {databaseName}");
            return response.Crawler;
        }

        Console.WriteLine($"No information regarding {crawlerName} could be
found.");
        return null;
    }


    /// <summary>
    /// Get information about the state of an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A value describing the state of the crawler.</returns>
    public async Task<CrawlerState> GetCrawlerStateAsync(string crawlerName)
    {
        var response = await _amazonGlue.GetCrawlerAsync(
            new GetCrawlerRequest { Name = crawlerName });
        return response.Crawler.State;
    }


    /// <summary>
```

```
    /// Get information about an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Database object containing information about the database.</
returns>
    public async Task<Database> GetDatabaseAsync(string dbName)
    {
        var databasesRequest = new GetDatabaseRequest
        {
            Name = dbName,
        };

        var response = await _amazonGlue.GetDatabaseAsync(databasesRequest);
        return response.Database;
    }


    /// <summary>
    /// Get information about a specific AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="jobRunId">The Id of the job run.</param>
    /// <returns>A JobRun object with information about the job run.</returns>
    public async Task<JobRun> GetJobRunAsync(string jobName, string jobRunId)
    {
        var response = await _amazonGlue.GetJobRunAsync(new GetJobRunRequest
 { JobName = jobName, RunId = jobRunId });
        return response.JobRun;
    }


    /// <summary>
    /// Get information about all AWS Glue runs of a specific job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A list of JobRun objects.</returns>
    public async Task<List<JobRun>> GetJobRunsAsync(string jobName)
    {
        var jobRuns = new List<JobRun>();

        var request = new GetJobRunsRequest
        {
            JobName = jobName,
        };
```

```
        // No need to loop to get all the log groups--the SDK does it for us
behind the scenes
        var paginatorForJobRuns =
            _amazonGlue.Paginators.GetJobRuns(request);

        await foreach (var response in paginatorForJobRuns.Responses)
        {
            response.JobRuns.ForEach(jobRun =>
            {
                jobRuns.Add(jobRun);
            });
        }

        return jobRuns;
    }


    /// <summary>
    /// Get a list of tables for an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A list of Table objects.</returns>
    public async Task<List<Table>> GetTablesAsync(string dbName)
    {
        var request = new GetTablesRequest { DatabaseName = dbName };
        var tables = new List<Table>();

        // Get a paginator for listing the tables.
        var tablePaginator = _amazonGlue.Paginators.GetTables(request);

        await foreach (var response in tablePaginator.Responses)
        {
            tables.AddRange(response.TableList);
        }

        return tables;
    }


    /// <summary>
    /// List AWS Glue jobs using a paginator.
    /// </summary>
    /// <returns>A list of AWS Glue job names.</returns>
```

```
    public async Task<List<string>> ListJobsAsync()
    {
        var jobNames = new List<string>();

        var listJobsPaginator = _amazonGlue.Paginators.ListJobs(new
ListJobsRequest { MaxResults = 10 });
        await foreach (var response in listJobsPaginator.Responses)
        {
            jobNames.AddRange(response.JobNames);
        }

        return jobNames;
    }


    /// <summary>
    /// Start an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> StartCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new StartCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.StartCrawlerAsync(crawlerRequest);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Start an AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A string representing the job run Id.</returns>
    public async Task<string> StartJobRunAsync(
        string jobName,
        string inputDatabase,
        string inputTable,
        string bucketName)
    {
```

```
        var request = new StartJobRunRequest
        {
            JobName = jobName,
            Arguments = new Dictionary<string, string>
            {
                {"--input_database", inputDatabase},
                {"--input_table", inputTable},
                {"--output_bucket_url", $"s3://{bucketName}/"}
            }
        };

        var response = await _amazonGlue.StartJobRunAsync(request);
        return response.JobRunId;
    }

}
```

Crie uma classe que execute o cenário.

```
global using Amazon.Glue;
global using GlueActions;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;



using Amazon.Glue.Model;
using Amazon.S3;
using Amazon.S3.Model;

namespace GlueBasics;

public class GlueBasics
{
    private static ILogger logger = null!;
    private static IConfiguration _configuration = null!;
```

```
    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Glue.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonGlue>()
            .AddTransient<GlueWrapper>()
            .AddTransient<UiWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
        .CreateLogger<GlueBasics>();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        // These values are stored in settings.json
        // Once you have run the CDK script to deploy the resources,
        // edit the file to set "BucketName", "RoleName", and "ScriptURL"
        // to the appropriate values. Also set "CrawlerName" to the name
        // you want to give the crawler when it is created.
        string bucketName = _configuration["BucketName"]!;
        string bucketUrl = _configuration["BucketUrl"]!;
        string crawlerName = _configuration["CrawlerName"]!;
        string roleName = _configuration["RoleName"]!;
        string sourceData = _configuration["SourceData"]!;
        string dbName = _configuration["DbName"]!;
        string cron = _configuration["Cron"]!;
        string scriptUrl = _configuration["ScriptURL"]!;
        string jobName = _configuration["JobName"]!;

        var wrapper = host.Services.GetRequiredService<GlueWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UiWrapper>();
```

```
        uiWrapper.DisplayOverview();
        uiWrapper.PressEnter();

        // Create the crawler and wait for it to be ready.
        uiWrapper.DisplayTitle("Create AWS Glue crawler");
        Console.WriteLine("Let's begin by creating the AWS Glue crawler.");

        var crawlerDescription = "Crawler created for the AWS Glue Basics
scenario.";
        var crawlerCreated = await wrapper.CreateCrawlerAsync(crawlerName,
crawlerDescription, roleName, cron, sourceData, dbName);
        if (crawlerCreated)
        {
            Console.WriteLine($"The crawler: {crawlerName} has been created. Now
let's wait until it's ready.");
            CrawlerState crawlerState;
            do
            {
                crawlerState = await wrapper.GetCrawlerStateAsync(crawlerName);
            }
            while (crawlerState != "READY");
            Console.WriteLine($"The crawler {crawlerName} is now ready for
use.");
        }
        else
        {
            Console.WriteLine($"Couldn't create crawler {crawlerName}.");
            return; // Exit the application.
        }

        uiWrapper.DisplayTitle("Start AWS Glue crawler");
        Console.WriteLine("Now let's wait until the crawler has successfully
started.");
        var crawlerStarted = await wrapper.StartCrawlerAsync(crawlerName);
        if (crawlerStarted)
        {
            CrawlerState crawlerState;
            do
            {
                crawlerState = await wrapper.GetCrawlerStateAsync(crawlerName);
            }
            while (crawlerState != "READY");
```

```
            Console.WriteLine($"The crawler {crawlerName} is now ready for
use.");
        }
        else
        {
            Console.WriteLine($"Couldn't start the crawler {crawlerName}.");
            return; // Exit the application.
        }

        uiWrapper.PressEnter();

        Console.WriteLine($"\nLet's take a look at the database: {dbName}");
        var database = await wrapper.GetDatabaseAsync(dbName);

        if (database != null)
        {
            uiWrapper.DisplayTitle($"{database.Name} Details");
            Console.WriteLine($"{database.Name} created on
{database.CreateTime}");
            Console.WriteLine(database.Description);
        }

        uiWrapper.PressEnter();

        var tables = await wrapper.GetTablesAsync(dbName);
        if (tables.Count > 0)
        {
            tables.ForEach(table =>
            {
                Console.WriteLine($"{table.Name}\tCreated:
{table.CreateTime}\tUpdated: {table.UpdateTime}");
            });
        }

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Create AWS Glue job");
        Console.WriteLine("Creating a new AWS Glue job.");
        var description = "An AWS Glue job created using the AWS SDK for .NET";
        await wrapper.CreateJobAsync(dbName, tables[0].Name, bucketUrl, jobName,
roleName, description, scriptUrl);

        uiWrapper.PressEnter();
```

```
        uiWrapper.DisplayTitle("Starting AWS Glue job");
        Console.WriteLine("Starting the new AWS Glue job...");
        var jobRunId = await wrapper.StartJobRunAsync(jobName, dbName,
tables[0].Name, bucketName);
        var jobRunComplete = false;
        var jobRun = new JobRun();
        do
        {
            jobRun = await wrapper.GetJobRunAsync(jobName, jobRunId);
            if (jobRun.JobRunState == "SUCCEEDED" || jobRun.JobRunState ==
"STOPPED" ||
                jobRun.JobRunState == "FAILED" || jobRun.JobRunState ==
"TIMEOUT")
            {
                jobRunComplete = true;
            }
        } while (!jobRunComplete);

        uiWrapper.DisplayTitle($"Data in {bucketName}");

        // Get the list of data stored in the S3 bucket.
        var s3Client = new AmazonS3Client();

        var response = await s3Client.ListObjectsAsync(new ListObjectsRequest
{ BucketName = bucketName });
        response.S3Objects.ForEach(s3Object =>
        {
            Console.WriteLine(s3Object.Key);
        });

        uiWrapper.DisplayTitle("AWS Glue jobs");
        var jobNames = await wrapper.ListJobsAsync();
        jobNames.ForEach(jobName =>
        {
            Console.WriteLine(jobName);
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Get AWS Glue job run information");
        Console.WriteLine("Getting information about the AWS Glue job.");
        var jobRuns = await wrapper.GetJobRunsAsync(jobName);

        jobRuns.ForEach(jobRun =>
```

```
        {

 Console.WriteLine($"{jobRun.JobName}\t{jobRun.JobRunState}\t{jobRun.CompletedOn}");
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Deleting resources");
        Console.WriteLine("Deleting the AWS Glue job used by the example.");
        await wrapper.DeleteJobAsync(jobName);

        Console.WriteLine("Deleting the tables from the database.");
        tables.ForEach(async table =>
        {
            await wrapper.DeleteTableAsync(dbName, table.Name);
        });

        Console.WriteLine("Deleting the database.");
        await wrapper.DeleteDatabaseAsync(dbName);

        Console.WriteLine("Deleting the AWS Glue crawler.");
        await wrapper.DeleteCrawlerAsync(crawlerName);

        Console.WriteLine("The AWS Glue scenario has completed.");
        uiWrapper.PressEnter();
    }
}


namespace GlueBasics;

public class UiWrapper
{
    public readonly string SepBar = new string('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the scenario.
    /// </summary>
    public void DisplayOverview()
    {
        Console.Clear();
        DisplayTitle("Amazon Glue: get started with crawlers and jobs");

        Console.WriteLine("This example application does the following:");
```

```
        Console.WriteLine("\t 1. Create a crawler, pass it the IAM role and the
URL to the public S3 bucket that contains the source data");
        Console.WriteLine("\t 2. Start the crawler.");
        Console.WriteLine("\t 3. Get the database created by the crawler and the
tables in the database.");
        Console.WriteLine("\t 4. Create a job.");
        Console.WriteLine("\t 5. Start a job run.");
        Console.WriteLine("\t 6. Wait for the job run to complete.");
        Console.WriteLine("\t 7. Show the data stored in the bucket.");
        Console.WriteLine("\t 8. List jobs for the account.");
        Console.WriteLine("\t 9. Get job run details for the job that was run.");
        Console.WriteLine("\t10. Delete the demo job.");
        Console.WriteLine("\t11. Delete the database and tables created for the
demo.");
        Console.WriteLine("\t12. Delete the crawler.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPlease press <Enter> to continue. ");
        _ = Console.ReadLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to center on the screen.</param>
    /// <returns>The string padded to make it center on the screen.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
```

```
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Scenario which demonstrates using AWS Glue to add a crawler and run a job.
/*!
 \\sa runGettingStartedWithGlueScenario()
 \param bucketName: An S3 bucket created in the setup.
 \param roleName: An AWS Identity and Access Management (IAM) role created in the
 setup.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */

bool AwsDoc::Glue::runGettingStartedWithGlueScenario(const Aws::String
 &bucketName,
                                                      const Aws::String &roleName,
                                                      const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::Glue::GlueClient client(clientConfig);

    Aws::String roleArn;
    if (!getRoleArn(roleName, roleArn, clientConfig)) {
        std::cerr << "Error getting role ARN for role." << std::endl;
        return false;
    }

    // 1. Upload the job script to the S3 bucket.
    {
        std::cout << "Uploading the job script '"
                  << AwsDoc::Glue::PYTHON_SCRIPT
                  << "'." << std::endl;

        if (!AwsDoc::Glue::uploadFile(bucketName,
                                      AwsDoc::Glue::PYTHON_SCRIPT_PATH,
                                      AwsDoc::Glue::PYTHON_SCRIPT,
```

```
                                        clientConfig)) {
            std::cerr << "Error uploading the job file." << std::endl;
            return false;
        }
    }

    // 2. Create a crawler.
    {
        Aws::Glue::Model::S3Target s3Target;
        s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
        Aws::Glue::Model::CrawlerTargets crawlerTargets;
        crawlerTargets.AddS3Targets(s3Target);

        Aws::Glue::Model::CreateCrawlerRequest request;
        request.SetTargets(crawlerTargets);
        request.SetName(CRAWLER_NAME);
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);
        request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
        request.SetRole(roleArn);

        Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the crawler." << std::endl;
        }
        else {
            std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName,
clientConfig);
            return false;
        }
    }

    // 3. Get a crawler.
    {
        Aws::Glue::Model::GetCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

        if (outcome.IsSuccess()) {
```

```
            Aws::Glue::Model::CrawlerState crawlerState =
outcome.GetResult().GetCrawler().GetState();
            std::cout << "Retrieved crawler with state " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                              crawlerState)
                      << "." << std::endl;
        }
        else {
            std::cerr << "Error retrieving a crawler.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 4. Start a crawler.
    {
        Aws::Glue::Model::StartCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


        if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
                                    outcome.GetError().GetErrorType())) {
            if (!outcome.IsSuccess()) {
                std::cout << "Crawler was already started." << std::endl;
            }
            else {
                std::cout << "Successfully started crawler." << std::endl;
            }

            std::cout << "This may take a while to run." << std::endl;

            Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
            int iterations = 0;
            while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
                ++iterations;
                if ((iterations % 10) == 0) { // Log status every 10 seconds.
```

```
                    std::cout << "Crawler status " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                    crawlerState)
                            << ". After " << iterations
                            << " seconds elapsed."
                            << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);

                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                            << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }

            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }
```

```
   // 5. Get a database.
   {
       Aws::Glue::Model::GetDatabaseRequest request;
       request.SetName(CRAWLER_DATABASE_NAME);

       Aws::Glue::Model::GetDatabaseOutcome outcome =
client.GetDatabase(request);

       if (outcome.IsSuccess()) {
           const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

           std::cout << "Successfully retrieve the database\n" <<
                     database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
       }
       else {
           std::cerr << "Error getting the database.  "
                     << outcome.GetError().GetMessage() << std::endl;
           deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                        clientConfig);
           return false;
       }
   }

   // 6. Get tables.
   Aws::String tableName;
   {
       Aws::Glue::Model::GetTablesRequest request;
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);

       Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

       if (outcome.IsSuccess()) {
           const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
           std::cout << "The database contains " << tables.size()
                     << (tables.size() == 1 ?
                         " table." : "tables.") << std::endl;
           std::cout << "Here is a list of the tables in the database.";
           for (size_t index = 0; index < tables.size(); ++index) {
               std::cout << "    " << index + 1 << ":  " <<
tables[index].GetName()
                         << std::endl;
```

```
            }

            if (!tables.empty()) {
                int tableIndex = askQuestionForIntRange(
                        "Enter an index to display the database detail ",
                        1, static_cast<int>(tables.size()));
                std::cout << tables[tableIndex -
1].Jsonize().View().WriteReadable()
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error getting the tables. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 7. Create a job.
    {
        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
```

```
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 8. Start a job run.
    {
        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName +
"/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome =
client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;

            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
                jobRunRequest.SetRunId(jobRunId);

                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome =
client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();
```

```
                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED)
||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT))
{
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME,
JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10
seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                           jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
                    }
                }
                else {
                    std::cerr << "Error retrieving job run state. "
                              << jobRunOutcome.GetError().GetMessage()
                              << std::endl;
                    deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                 bucketName, clientConfig);
                    return false;
                }
            }
        }
        else {
            std::cerr << "Error starting a job. " <<
outcome.GetError().GetMessage()
```

```
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
bucketName,
                         clientConfig);
            return false;
        }
    }

    // 9. List the output data stored in the S3 bucket.
    {
        Aws::S3::S3Client s3Client;
        Aws::S3::Model::ListObjectsRequest request;
        request.SetBucket(bucketName);
        request.SetPrefix(OUTPUT_FILE_PREFIX);

        Aws::S3::Model::ListObjectsOutcome outcome =
s3Client.ListObjects(request);

        if (outcome.IsSuccess()) {
            const std::vector<Aws::S3::Model::Object> &objects =
outcome.GetResult().GetContents();
            std::cout << "Data from your job is in " << objects.size() <<
                      " files in the S3 bucket, " << bucketName << "." <<
std::endl;

            for (size_t i = 0; i < objects.size(); ++i) {
                std::cout << "    " << i + 1 << ". " << objects[i].GetKey()
                          << std::endl;
            }

            int objectIndex = askQuestionForIntRange(
                    std::string(
                            "Enter the number of a block to download it and see
the first ") +
                    std::to_string(LINES_OF_RUN_FILE_TO_DISPLAY) +
                    " lines of JSON output in the block: ", 1,
                    static_cast<int>(objects.size()));

            Aws::String objectKey = objects[objectIndex - 1].GetKey();

            std::stringstream stringStream;
            if (getObjectFromBucket(bucketName, objectKey, stringStream,
                                    clientConfig)) {
```

```
                for (int i = 0; i < LINES_OF_RUN_FILE_TO_DISPLAY && stringStream;
++i) {
                    std::string line;
                    std::getline(stringStream, line);
                    std::cout << "    " << line << std::endl;
                }
            }
            else {
                deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
bucketName,
                             clientConfig);
                return false;
            }
        }
        else {
            std::cerr << "Error listing objects. " <<
outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    // 10. List all the jobs.
    Aws::String jobName;
    {
        Aws::Glue::Model::ListJobsRequest listJobsRequest;
        Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
                listJobsRequest);

        if (listRunsOutcome.IsSuccess()) {
            const std::vector<Aws::String> &jobNames =
listRunsOutcome.GetResult().GetJobNames();
            std::cout << "Your account has " << jobNames.size() << " jobs."
                      << std::endl;
            for (size_t i = 0; i < jobNames.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobNames[i] << std::endl;
            }
            int jobIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobNames.size()) +
                    " to see the list of runs for a job: ",
                    1, static_cast<int>(jobNames.size()));

            jobName = jobNames[jobIndex - 1];
        }
```

```
        else {
            std::cerr << "Error listing jobs. "
                      << listRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    // 11. Get the job runs for a job.
    Aws::String jobRunID;
    if (!jobName.empty()) {
        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);

        Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                getJobRunsRequest);

        if (jobRunsOutcome.IsSuccess()) {
            std::vector<Aws::Glue::Model::JobRun> jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
            std::cout << "There are " << jobRuns.size() << " runs in the job '"
                      <<
                      jobName << "'." << std::endl;

            for (size_t i = 0; i < jobRuns.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobRuns[i].GetJobName()
                          << std::endl;
            }

            int runIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobRuns.size()) +
                    " to see details for a run: ",
                    1, static_cast<int>(jobRuns.size()));
            jobRunID = jobRuns[runIndex - 1].GetId();
        }
        else {
            std::cerr << "Error getting job runs. "
                      << jobRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    // 12. Get a single job run.
    if (!jobRunID.empty()) {
```

```
        Aws::Glue::Model::GetJobRunRequest jobRunRequest;
        jobRunRequest.SetJobName(jobName);
        jobRunRequest.SetRunId(jobRunID);

        Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                jobRunRequest);

        if (jobRunOutcome.IsSuccess()) {
            std::cout << "Displaying the job run JSON description." << std::endl;
            std::cout
                    <<
 jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                    << std::endl;
        }
        else {
            std::cerr << "Error get a job run. "
                      << jobRunOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    return deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
 bucketName,
                        clientConfig);
}

//! Cleanup routine to delete created assets.
/*!
 \\sa deleteAssets()
 \param crawler: Name of an AWS Glue crawler.
 \param database: The name of an AWS Glue database.
 \param job: The name of an AWS Glue job.
 \param bucketName: The name of an S3 bucket.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAssets(const Aws::String &crawler, const Aws::String
 &database,
                                const Aws::String &job, const Aws::String
 &bucketName,
                                const Aws::Client::ClientConfiguration
 &clientConfig) {
    const Aws::Glue::GlueClient client(clientConfig);
    bool result = true;
```

```
    // 13. Delete a job.
    if (!job.empty()) {
        Aws::Glue::Model::DeleteJobRequest request;
        request.SetJobName(job);

        Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the job." << std::endl;
        }
        else {
            std::cerr << "Error deleting the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    // 14. Delete a database.
    if (!database.empty()) {
        Aws::Glue::Model::DeleteDatabaseRequest request;
        request.SetName(database);

        Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the database." << std::endl;
        }
        else {
            std::cerr << "Error deleting database. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    // 15. Delete a crawler.
    if (!crawler.empty()) {
        Aws::Glue::Model::DeleteCrawlerRequest request;
        request.SetName(crawler);
```

```
        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
 client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
    }

    // 16. Delete the job script and run data from the S3 bucket.
    result &= AwsDoc::Glue::deleteAllObjectsInS3Bucket(bucketName,
                                                       clientConfig);
    return result;
}

//! Routine which uploads a file to an S3 bucket.
/*!
 \\sa uploadFile()
 \param bucketName: An S3 bucket created in the setup.
 \param filePath: The path of the file to upload.
 \param fileName The name for the uploaded file.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool
AwsDoc::Glue::uploadFile(const Aws::String &bucketName,
                         const Aws::String &filePath,
                         const Aws::String &fileName,
                         const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          filePath.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);
```

```
    if (!*inputData) {
        std::cerr << "Error unable to read file " << filePath << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3_client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Added object '" << filePath << "' to bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which deletes all objects in an S3 bucket.
/*!
 \\sa deleteAllObjectsInS3Bucket()
 \param bucketName: The S3 bucket name.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAllObjectsInS3Bucket(const Aws::String &bucketName,
                                              const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::ListObjectsRequest listObjectsRequest;
    listObjectsRequest.SetBucket(bucketName);


    Aws::S3::Model::ListObjectsOutcome listObjectsOutcome = client.ListObjects(
            listObjectsRequest);

    bool result = false;
    if (listObjectsOutcome.IsSuccess()) {
```

```
        const std::vector<Aws::S3::Model::Object> &objects =
 listObjectsOutcome.GetResult().GetContents();
        if (!objects.empty()) {
            Aws::S3::Model::DeleteObjectsRequest deleteObjectsRequest;
            deleteObjectsRequest.SetBucket(bucketName);

            std::vector<Aws::S3::Model::ObjectIdentifier> objectIdentifiers;
            for (const Aws::S3::Model::Object &object: objects) {
                objectIdentifiers.push_back(

 Aws::S3::Model::ObjectIdentifier().WithKey(object.GetKey()));
            }
            Aws::S3::Model::Delete objectsDelete;
            objectsDelete.SetObjects(objectIdentifiers);
            objectsDelete.SetQuiet(true);
            deleteObjectsRequest.SetDelete(objectsDelete);

            Aws::S3::Model::DeleteObjectsOutcome deleteObjectsOutcome =
                    client.DeleteObjects(deleteObjectsRequest);

            if (!deleteObjectsOutcome.IsSuccess()) {
                std::cerr << "Error deleting objects. " <<
                          deleteObjectsOutcome.GetError().GetMessage() <<
 std::endl;
            }
            else {
                std::cout << "Successfully deleted the objects." << std::endl;
                result = true;
            }
        }
        else {
            std::cout << "No objects to delete in '" << bucketName << "'." <<
 std::endl;
        }
    }
    else {
        std::cerr << "Error listing objects. "
                  << listObjectsOutcome.GetError().GetMessage() << std::endl;
    }

    return result;
}

//! Routine which retrieves an object from an S3 bucket.
```

```
/*!
 \\sa getObjectFromBucket()
 \param bucketName: The S3 bucket name.
 \param objectKey: The object's name.
 \param objectStream: A stream to receive the retrieved data.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::getObjectFromBucket(const Aws::String &bucketName,
                                       const Aws::String &objectKey,
                                       std::ostream &objectStream,
                                       const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome = client.GetObject(request);


    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved '" << objectKey << "'." <<
 std::endl;
        auto &body = outcome.GetResult().GetBody();
        objectStream << body.rdbuf();
    }
    else {
        std::cerr << "Error retrieving object. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateCrawler
  - CreateJob

- DeleteCrawler
- DeleteDatabase
- DeleteJob
- DeleteTable
- GetCrawler
- GetDatabase
- GetDatabases
- GetJob
- GetJobRun
- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 *
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * To set up the resources, see this documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/glue/latest/ug/tutorial-add-crawler.html
 *
 * This example performs the following tasks:
 *
 * 1. Create a database.
 * 2. Create a crawler.
 * 3. Get a crawler.
 * 4. Start a crawler.
 * 5. Get a database.
 * 6. Get tables.
 * 7. Create a job.
 * 8. Start a job run.
 * 9. List all jobs.
 * 10. Get job runs.
 * 11. Delete a job.
 * 12. Delete a database.
 * 13. Delete a crawler.
 */

public class GlueScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <iam> <s3Path> <cron> <dbName> <crawlerName> <jobName>\s

                Where:
                    iam - The ARN of the IAM role that has AWS Glue and S3
 permissions.\s
                    s3Path - The Amazon Simple Storage Service (Amazon S3) target
 that contains data (for example, CSV data).
                    cron - A cron expression used to specify the schedule  (i.e.,
 cron(15 12 * * ? *).
                    dbName - The database name.\s
                    crawlerName - The name of the crawler.\s
                    jobName - The name you assign to this job definition.
                    scriptLocation - The Amazon S3 path to a script that runs a
 job.
                    locationUri - The location of the database
```

```
                    bucketNameSc - The Amazon S3 bucket name used when creating a
job
                    """;

        if (args.length != 9) {
            System.out.println(usage);
            System.exit(1);
        }

        String iam = args[0];
        String s3Path = args[1];
        String cron = args[2];
        String dbName = args[3];
        String crawlerName = args[4];
        String jobName = args[5];
        String scriptLocation = args[6];
        String locationUri = args[7];
        String bucketNameSc = args[8];

        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();
        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Glue scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create a database.");
        createDatabase(glueClient, dbName, locationUri);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a crawler.");
        createGlueCrawler(glueClient, iam, s3Path, cron, dbName, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get a crawler.");
        getSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Start a crawler.");
```

```
        startSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get a database.");
        getSpecificDatabase(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Wait 5 min for the tables to become available");
        TimeUnit.MINUTES.sleep(5);
        System.out.println("6. Get tables.");
        String myTableName = getGlueTables(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Create a job.");
        createJob(glueClient, jobName, iam, scriptLocation);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Start a Job run.");
        startJob(glueClient, jobName, dbName, myTableName, bucketNameSc);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. List all jobs.");
        getAllJobs(glueClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get job runs.");
        getJobRuns(glueClient, jobName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Delete a job.");
        deleteJob(glueClient, jobName);
        System.out.println("*** Wait 5 MIN for the " + crawlerName + " to stop");
        TimeUnit.MINUTES.sleep(5);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Delete a database.");
```

```
        deleteDatabase(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Delete a crawler.");
        deleteSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Successfully completed the AWS Glue Scenario");
        System.out.println(DASHES);
    }

    public static void createDatabase(GlueClient glueClient, String dbName,
 String locationUri) {
        try {
            DatabaseInput input = DatabaseInput.builder()
                    .description("Built with the AWS SDK for Java V2")
                    .name(dbName)
                    .locationUri(locationUri)
                    .build();

            CreateDatabaseRequest request = CreateDatabaseRequest.builder()
                    .databaseInput(input)
                    .build();

            glueClient.createDatabase(request);
            System.out.println(dbName + " was successfully created");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createGlueCrawler(GlueClient glueClient,
            String iam,
            String s3Path,
            String cron,
            String dbName,
            String crawlerName) {

        try {
            S3Target s3Target = S3Target.builder()
```

```
                .path(s3Path)
                .build();

        List<S3Target> targetList = new ArrayList<>();
        targetList.add(s3Target);
        CrawlerTargets targets = CrawlerTargets.builder()
                .s3Targets(targetList)
                .build();

        CreateCrawlerRequest crawlerRequest = CreateCrawlerRequest.builder()
                .databaseName(dbName)
                .name(crawlerName)
                .description("Created by the AWS Glue Java API")
                .targets(targets)
                .role(iam)
                .schedule(cron)
                .build();

        glueClient.createCrawler(crawlerRequest);
        System.out.println(crawlerName + " was successfully created");

    } catch (GlueException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}

public static void getSpecificCrawler(GlueClient glueClient, String
crawlerName) {
    try {
        GetCrawlerRequest crawlerRequest = GetCrawlerRequest.builder()
                .name(crawlerName)
                .build();

        boolean ready = false;
        while (!ready) {
            GetCrawlerResponse response =
glueClient.getCrawler(crawlerRequest);
            String status = response.crawler().stateAsString();
            if (status.compareTo("READY") == 0) {
                ready = true;
            }
            Thread.sleep(3000);
        }
```

```
            System.out.println("The crawler is now ready");

        } catch (GlueException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void startSpecificCrawler(GlueClient glueClient, String
crawlerName) {
        try {
            StartCrawlerRequest crawlerRequest = StartCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.startCrawler(crawlerRequest);
            System.out.println(crawlerName + " was successfully started!");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getSpecificDatabase(GlueClient glueClient, String
databaseName) {
        try {
            GetDatabaseRequest databasesRequest = GetDatabaseRequest.builder()
                    .name(databaseName)
                    .build();

            GetDatabaseResponse response =
glueClient.getDatabase(databasesRequest);
            Instant createDate = response.database().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
```

```
            System.out.println("The create date of the database is " +
 createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String getGlueTables(GlueClient glueClient, String dbName) {
        String myTableName = "";
        try {
            GetTablesRequest tableRequest = GetTablesRequest.builder()
                    .databaseName(dbName)
                    .build();

            GetTablesResponse response = glueClient.getTables(tableRequest);
            List<Table> tables = response.tableList();
            if (tables.isEmpty()) {
                System.out.println("No tables were returned");
            } else {
                for (Table table : tables) {
                    myTableName = table.name();
                    System.out.println("Table name is: " + myTableName);
                }
            }

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return myTableName;
    }

    public static void startJob(GlueClient glueClient, String jobName, String
 inputDatabase, String inputTable,
            String outBucket) {
        try {
            Map<String, String> myMap = new HashMap<>();
            myMap.put("--input_database", inputDatabase);
            myMap.put("--input_table", inputTable);
            myMap.put("--output_bucket_url", outBucket);

            StartJobRunRequest runRequest = StartJobRunRequest.builder()
```

```
                    .workerType(WorkerType.G_1_X)
                    .numberOfWorkers(10)
                    .arguments(myMap)
                    .jobName(jobName)
                    .build();

            StartJobRunResponse response = glueClient.startJobRun(runRequest);
            System.out.println("The request Id of the job is " +
response.responseMetadata().requestId());

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createJob(GlueClient glueClient, String jobName, String
iam, String scriptLocation) {
        try {
            JobCommand command = JobCommand.builder()
                    .pythonVersion("3")
                    .name("glueetl")
                    .scriptLocation(scriptLocation)
                    .build();

            CreateJobRequest jobRequest = CreateJobRequest.builder()
                    .description("A Job created by using the AWS SDK for Java
V2")
                    .glueVersion("2.0")
                    .workerType(WorkerType.G_1_X)
                    .numberOfWorkers(10)
                    .name(jobName)
                    .role(iam)
                    .command(command)
                    .build();

            glueClient.createJob(jobRequest);
            System.out.println(jobName + " was successfully created.");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static void getAllJobs(GlueClient glueClient) {
        try {
            GetJobsRequest jobsRequest = GetJobsRequest.builder()
                    .maxResults(10)
                    .build();

            GetJobsResponse jobsResponse = glueClient.getJobs(jobsRequest);
            List<Job> jobs = jobsResponse.jobs();
            for (Job job : jobs) {
                System.out.println("Job name is : " + job.name());
                System.out.println("The job worker type is : " +
job.workerType().name());
            }

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getJobRuns(GlueClient glueClient, String jobName) {
        try {
            GetJobRunsRequest runsRequest = GetJobRunsRequest.builder()
                    .jobName(jobName)
                    .maxResults(20)
                    .build();

            boolean jobDone = false;
            while (!jobDone) {
                GetJobRunsResponse response = glueClient.getJobRuns(runsRequest);
                List<JobRun> jobRuns = response.jobRuns();
                for (JobRun jobRun : jobRuns) {
                    String jobState = jobRun.jobRunState().name();
                    if (jobState.compareTo("SUCCEEDED") == 0) {
                        System.out.println(jobName + " has succeeded");
                        jobDone = true;

                    } else if (jobState.compareTo("STOPPED") == 0) {
                        System.out.println("Job run has stopped");
                        jobDone = true;

                    } else if (jobState.compareTo("FAILED") == 0) {
                        System.out.println("Job run has failed");
```

```
                        jobDone = true;

                    } else if (jobState.compareTo("TIMEOUT") == 0) {
                        System.out.println("Job run has timed out");
                        jobDone = true;

                    } else {
                        System.out.println("*** Job run state is " +
jobRun.jobRunState().name());
                        System.out.println("Job run Id is " + jobRun.id());
                        System.out.println("The Glue version is " +
jobRun.glueVersion());
                    }
                    TimeUnit.SECONDS.sleep(5);
                }
            }

        } catch (GlueException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void deleteJob(GlueClient glueClient, String jobName) {
        try {
            DeleteJobRequest jobRequest = DeleteJobRequest.builder()
                    .jobName(jobName)
                    .build();

            glueClient.deleteJob(jobRequest);
            System.out.println(jobName + " was successfully deleted");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteDatabase(GlueClient glueClient, String databaseName)
{
        try {
            DeleteDatabaseRequest request = DeleteDatabaseRequest.builder()
                    .name(databaseName)
                    .build();
```

```
            glueClient.deleteDatabase(request);
            System.out.println(databaseName + " was successfully deleted");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteSpecificCrawler(GlueClient glueClient, String
 crawlerName) {
        try {
            DeleteCrawlerRequest deleteCrawlerRequest =
 DeleteCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.deleteCrawler(deleteCrawlerRequest);
            System.out.println(crawlerName + " was deleted");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase

- GetDatabases
- GetJob
- GetJobRun
- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e execute um crawler que examine um bucket público do Amazon Simple Storage Service (Amazon S3) e gere um banco de dados de metadados que descreva os dados no formato CSV que encontrar.

```
const createCrawler = (name, role, dbName, tablePrefix, s3TargetPath) => {
  const client = new GlueClient({});

  const command = new CreateCrawlerCommand({
    Name: name,
    Role: role,
    DatabaseName: dbName,
    TablePrefix: tablePrefix,
    Targets: {
      S3Targets: [{ Path: s3TargetPath }],
    },
  });

  return client.send(command);
};
```

```
const getCrawler = (name) => {
  const client = new GlueClient({});

  const command = new GetCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};

const startCrawler = (name) => {
  const client = new GlueClient({});

  const command = new StartCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};

const crawlerExists = async ({ getCrawler }, crawlerName) => {
  try {
    await getCrawler(crawlerName);
    return true;
  } catch {
    return false;
  }
};

const makeCreateCrawlerStep = (actions) => async (context) => {
  if (await crawlerExists(actions, process.env.CRAWLER_NAME)) {
    log("Crawler already exists. Skipping creation.");
  } else {
    await actions.createCrawler(
      process.env.CRAWLER_NAME,
      process.env.ROLE_NAME,
      process.env.DATABASE_NAME,
      process.env.TABLE_PREFIX,
      process.env.S3_TARGET_PATH
    );

    log("Crawler created successfully.", { type: "success" });
  }
```

```
  return { ...context };
};

/**
 * @param {(name: string) => Promise<import('@aws-sdk/client-
glue').GetCrawlerCommandOutput>} getCrawler
 * @param {string} crawlerName
 */
const waitForCrawler = async (getCrawler, crawlerName) => {
  const waitTimeInSeconds = 30;
  const { Crawler } = await getCrawler(crawlerName);

  if (!Crawler) {
    throw new Error(`Crawler with name ${crawlerName} not found.`);
  }

  if (Crawler.State === "READY") {
    return;
  }

  log(`Crawler is ${Crawler.State}. Waiting ${waitTimeInSeconds} seconds...`);
  await wait(waitTimeInSeconds);
  return waitForCrawler(getCrawler, crawlerName);
};

const makeStartCrawlerStep =
  ({ startCrawler, getCrawler }) =>
  async (context) => {
    log("Starting crawler.");
    await startCrawler(process.env.CRAWLER_NAME);
    log("Crawler started.", { type: "success" });

    log("Waiting for crawler to finish running. This can take a while.");
    await waitForCrawler(getCrawler, process.env.CRAWLER_NAME);
    log("Crawler ready.", { type: "success" });

    return { ...context };
  };
```

Liste informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.

```
const getDatabase = (name) => {
  const client = new GlueClient({});

  const command = new GetDatabaseCommand({
    Name: name,
  });

  return client.send(command);
};

const getTables = (databaseName) => {
  const client = new GlueClient({});

  const command = new GetTablesCommand({
    DatabaseName: databaseName,
  });

  return client.send(command);
};

const makeGetDatabaseStep =
  ({ getDatabase }) =>
  async (context) => {
    const {
      Database: { Name },
    } = await getDatabase(process.env.DATABASE_NAME);
    log(`Database: ${Name}`);
    return { ...context };
  };

const makeGetTablesStep =
  ({ getTables }) =>
  async (context) => {
    const { TableList } = await getTables(process.env.DATABASE_NAME);
    log("Tables:");
    log(TableList.map((table) => `  • ${table.Name}\n`));
    return { ...context };
  };
```

Crie e execute um trabalho que extraia dados em CSV do bucket do Amazon S3 de origem, transforme-os removendo e renomeando campos, e carregue a saída formatada em JSON em outro bucket do Amazon S3.

```
const createJob = (name, role, scriptBucketName, scriptKey) => {
  const client = new GlueClient({});

  const command = new CreateJobCommand({
    Name: name,
    Role: role,
    Command: {
      Name: "glueetl",
      PythonVersion: "3",
      ScriptLocation: `s3://${scriptBucketName}/${scriptKey}`,
    },
    GlueVersion: "3.0",
  });

  return client.send(command);
};

const startJobRun = (jobName, dbName, tableName, bucketName) => {
  const client = new GlueClient({});

  const command = new StartJobRunCommand({
    JobName: jobName,
    Arguments: {
      "--input_database": dbName,
      "--input_table": tableName,
      "--output_bucket_url": `s3://${bucketName}/`,
    },
  });

  return client.send(command);
};

const makeCreateJobStep =
  ({ createJob }) =>
  async (context) => {
    log("Creating Job.");
    await createJob(
      process.env.JOB_NAME,
      process.env.ROLE_NAME,
      process.env.BUCKET_NAME,
      process.env.PYTHON_SCRIPT_KEY,
    );
    log("Job created.", { type: "success" });
```

```
    return { ...context };
  };

/**
 * @param {(name: string, runId: string) => Promise<import('@aws-sdk/client-
glue').GetJobRunCommandOutput> }  getJobRun
 * @param {string} jobName
 * @param {string} jobRunId
 */
const waitForJobRun = async (getJobRun, jobName, jobRunId) => {
  const waitTimeInSeconds = 30;
  const { JobRun } = await getJobRun(jobName, jobRunId);

  if (!JobRun) {
    throw new Error(`Job run with id ${jobRunId} not found.`);
  }

  switch (JobRun.JobRunState) {
    case "FAILED":
    case "TIMEOUT":
    case "STOPPED":
      throw new Error(
        `Job ${JobRun.JobRunState}. Error: ${JobRun.ErrorMessage}`,
      );
    case "RUNNING":
      break;
    case "SUCCEEDED":
      return;
    default:
      throw new Error(`Unknown job run state: ${JobRun.JobRunState}`);
  }

  log(
    `Job ${JobRun.JobRunState}. Waiting ${waitTimeInSeconds} more seconds...`,
  );
  await wait(waitTimeInSeconds);
  return waitForJobRun(getJobRun, jobName, jobRunId);
};

/**
 * @param {{ prompter: { prompt: () => Promise<{ shouldOpen: boolean }>} }}
 context
 */
```

```
const promptToOpen = async (context) => {
  const { shouldOpen } = await context.prompter.prompt({
    name: "shouldOpen",
    type: "confirm",
    message: "Open the output bucket in your browser?",
  });

  if (shouldOpen) {
    return open(
      `https://s3.console.aws.amazon.com/s3/buckets/${process.env.BUCKET_NAME} to
 view the output.`,
    );
  }
};

const makeStartJobRunStep =
  ({ startJobRun, getJobRun }) =>
  async (context) => {
    log("Starting job.");
    const { JobRunId } = await startJobRun(
      process.env.JOB_NAME,
      process.env.DATABASE_NAME,
      process.env.TABLE_NAME,
      process.env.BUCKET_NAME,
    );
    log("Job started.", { type: "success" });

    log("Waiting for job to finish running. This can take a while.");
    await waitForJobRun(getJobRun, process.env.JOB_NAME, JobRunId);
    log("Job run succeeded.", { type: "success" });

    await promptToOpen(context);

    return { ...context };
  };
```

Liste informações sobre execuções de tarefas e visualize alguns dos dados transformados.

```
const getJobRuns = (jobName) => {
  const client = new GlueClient({});
  const command = new GetJobRunsCommand({
    JobName: jobName,
```

```
  });

  return client.send(command);
};

const getJobRun = (jobName, jobRunId) => {
  const client = new GlueClient({});
  const command = new GetJobRunCommand({
    JobName: jobName,
    RunId: jobRunId,
  });

  return client.send(command);
};

const logJobRunDetails = async (getJobRun, jobName, jobRunId) => {
  const { JobRun } = await getJobRun(jobName, jobRunId);
  log(JobRun, { type: "object" });
};

const makePickJobRunStep =
  ({ getJobRuns, getJobRun }) =>
  async (context) => {
    if (context.selectedJobName) {
      const { JobRuns } = await getJobRuns(context.selectedJobName);

      const { jobRunId } = await context.prompter.prompt({
        name: "jobRunId",
        type: "list",
        message: "Select a job run to see details.",
        choices: JobRuns.map((run) => run.Id),
      });

      logJobRunDetails(getJobRun, context.selectedJobName, jobRunId);
    }

    return { ...context };
  };
```

Exclua todos os recursos criados pela demonstração.

```
const deleteJob = (jobName) => {
```

```
  const client = new GlueClient({});

  const command = new DeleteJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};

const deleteTable = (databaseName, tableName) => {
  const client = new GlueClient({});

  const command = new DeleteTableCommand({
    DatabaseName: databaseName,
    Name: tableName,
  });

  return client.send(command);
};

const deleteDatabase = (databaseName) => {
  const client = new GlueClient({});

  const command = new DeleteDatabaseCommand({
    Name: databaseName,
  });

  return client.send(command);
};

const deleteCrawler = (crawlerName) => {
  const client = new GlueClient({});

  const command = new DeleteCrawlerCommand({
    Name: crawlerName,
  });

  return client.send(command);
};

const handleDeleteJobs = async (deleteJobFn, jobNames, context) => {
  const { selectedJobNames } = await context.prompter.prompt({
    name: "selectedJobNames",
    type: "checkbox",
```

```
    message: "Let's clean up jobs. Select jobs to delete.",
    choices: jobNames,
  });

  if (selectedJobNames.length === 0) {
    log("No jobs selected.");
  } else {
    log("Deleting jobs.");
    await Promise.all(
      selectedJobNames.map((n) => deleteJobFn(n).catch(console.error))
    );
    log("Jobs deleted.", { type: "success" });
  }
};

const makeCleanUpJobsStep =
  ({ listJobs, deleteJob }) =>
  async (context) => {
    const { JobNames } = await listJobs();
    if (JobNames.length > 0) {
      await handleDeleteJobs(deleteJob, JobNames, context);
    }

    return { ...context };
  };

const deleteTables = (deleteTable, databaseName, tableNames) =>
  Promise.all(
    tableNames.map((tableName) =>
      deleteTable(databaseName, tableName).catch(console.error)
    )
  );

const makeCleanUpTablesStep =
  ({ getTables, deleteTable }) =>
  async (context) => {
    const { TableList } = await getTables(process.env.DATABASE_NAME).catch(
      () => ({ TableList: null })
    );

    if (TableList && TableList.length > 0) {
      const { tableNames } = await context.prompter.prompt({
        name: "tableNames",
        type: "checkbox",
```

```
        message: "Let's clean up tables. Select tables to delete.",
        choices: TableList.map((t) => t.Name),
      });

      if (tableNames.length === 0) {
        log("No tables selected.");
      } else {
        log("Deleting tables.");
        await deleteTables(deleteTable, process.env.DATABASE_NAME, tableNames);
        log("Tables deleted.", { type: "success" });
      }
    }

    return { ...context };
  };

const deleteDatabases = (deleteDatabase, databaseNames) =>
  Promise.all(
    databaseNames.map((dbName) => deleteDatabase(dbName).catch(console.error))
  );

const makeCleanUpDatabasesStep =
  ({ getDatabases, deleteDatabase }) =>
  async (context) => {
    const { DatabaseList } = await getDatabases();

    if (DatabaseList.length > 0) {
      const { dbNames } = await context.prompter.prompt({
        name: "dbNames",
        type: "checkbox",
        message: "Let's clean up databases. Select databases to delete.",
        choices: DatabaseList.map((db) => db.Name),
      });

      if (dbNames.length === 0) {
        log("No databases selected.");
      } else {
        log("Deleting databases.");
        await deleteDatabases(deleteDatabase, dbNames);
        log("Databases deleted.", { type: "success" });
      }
    }

    return { ...context };
```

```
  };

const cleanUpCrawlerStep = async (context) => {
  log(`Deleting crawler.`);

  try {
    await deleteCrawler(process.env.CRAWLER_NAME);
    log("Crawler deleted.", { type: "success" });
  } catch (err) {
    if (err.name === "EntityNotFoundException") {
      log(`Crawler is already deleted.`);
    } else {
      throw err;
    }
  }

  return { ...context };
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler

- StartJobRun

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
            <iam> <s3Path> <cron> <dbName> <crawlerName> <jobName>
 <scriptLocation> <locationUri>

        Where:
            iam - The Amazon Resource Name (ARN) of the AWS Identity and Access
 Management (IAM) role that has AWS Glue and Amazon Simple Storage Service
 (Amazon S3) permissions.
            s3Path - The Amazon Simple Storage Service (Amazon S3) target that
 contains data (for example, CSV data).
            cron - A cron expression used to specify the schedule (for example,
 cron(15 12 * * ? *).
            dbName - The database name.
            crawlerName - The name of the crawler.
            jobName - The name you assign to this job definition.
            scriptLocation - Specifies the Amazon S3 path to a script that runs a
 job.
            locationUri - Specifies the location of the database
        """

    if (args.size != 8) {
        println(usage)
        exitProcess(1)
    }

    val iam = args[0]
```

```
    val s3Path = args[1]
    val cron = args[2]
    val dbName = args[3]
    val crawlerName = args[4]
    val jobName = args[5]
    val scriptLocation = args[6]
    val locationUri = args[7]

    println("About to start the AWS Glue Scenario")
    createDatabase(dbName, locationUri)
    createCrawler(iam, s3Path, cron, dbName, crawlerName)
    getCrawler(crawlerName)
    startCrawler(crawlerName)
    getDatabase(dbName)
    getGlueTables(dbName)
    createJob(jobName, iam, scriptLocation)
    startJob(jobName)
    getJobs()
    getJobRuns(jobName)
    deleteJob(jobName)
    println("*** Wait for 5 MIN so the $crawlerName is ready to be deleted")
    TimeUnit.MINUTES.sleep(5)
    deleteMyDatabase(dbName)
    deleteCrawler(crawlerName)
}

suspend fun createDatabase(dbName: String?, locationUriVal: String?) {

    val input = DatabaseInput {
        description = "Built with the AWS SDK for Kotlin"
        name = dbName
        locationUri = locationUriVal
    }

    val request = CreateDatabaseRequest {
        databaseInput = input
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createDatabase(request)
        println("The database was successfully created")
    }
}
```

```
suspend fun createCrawler(iam: String?, s3Path: String?, cron: String?, dbName:
 String?, crawlerName: String) {

    val s3Target = S3Target {
        path = s3Path
    }

    val targetList = ArrayList<S3Target>()
    targetList.add(s3Target)

    val targetOb = CrawlerTargets {
        s3Targets = targetList
    }

    val crawlerRequest = CreateCrawlerRequest {
        databaseName = dbName
        name = crawlerName
        description = "Created by the AWS Glue Java API"
        targets = targetOb
        role = iam
        schedule = cron
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createCrawler(crawlerRequest)
        println("$crawlerName was successfully created")
    }
}

suspend fun getCrawler(crawlerName: String?) {

    val request = GetCrawlerRequest {
        name = crawlerName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getCrawler(request)
        val role = response.crawler?.role
        println("The role associated with this crawler is $role")
    }
}

suspend fun startCrawler(crawlerName: String) {
```

```
    val crawlerRequest = StartCrawlerRequest {
        name = crawlerName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.startCrawler(crawlerRequest)
        println("$crawlerName was successfully started.")
    }
}

suspend fun getDatabase(databaseName: String?) {

    val request = GetDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getDatabase(request)
        val dbDesc = response.database?.description
        println("The database description is $dbDesc")
    }
}

suspend fun getGlueTables(dbName: String?) {

    val tableRequest = GetTablesRequest {
        databaseName = dbName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getTables(tableRequest)
        response.tableList?.forEach { tableName ->
            println("Table name is ${tableName.name}")
        }
    }
}

suspend fun startJob(jobNameVal: String?) {

    val runRequest = StartJobRunRequest {
        workerType = WorkerType.G1X
        numberOfWorkers = 10
        jobName = jobNameVal
    }
```

```
    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.startJobRun(runRequest)
        println("The job run Id is ${response.jobRunId}")
    }
}

suspend fun createJob(jobName: String, iam: String?, scriptLocationVal: String?)
 {

    val commandOb = JobCommand {
        pythonVersion = "3"
        name = "MyJob1"
        scriptLocation = scriptLocationVal
    }

    val jobRequest = CreateJobRequest {
        description = "A Job created by using the AWS SDK for Java V2"
        glueVersion = "2.0"
        workerType = WorkerType.G1X
        numberOfWorkers = 10
        name = jobName
        role = iam
        command = commandOb
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createJob(jobRequest)
        println("$jobName was successfully created.")
    }
}

suspend fun getJobs() {

    val request = GetJobsRequest {
        maxResults = 10
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getJobs(request)
        response.jobs?.forEach { job ->
            println("Job name is ${job.name}")
        }
    }
```

```
}

suspend fun getJobRuns(jobNameVal: String?) {

    val request = GetJobRunsRequest {
        jobName = jobNameVal
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getJobRuns(request)
        response.jobRuns?.forEach { job ->
            println("Job name is ${job.jobName}")
        }
    }
}

suspend fun deleteJob(jobNameVal: String) {

    val jobRequest = DeleteJobRequest {
        jobName = jobNameVal
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteJob(jobRequest)
        println("$jobNameVal was successfully deleted")
    }
}

suspend fun deleteMyDatabase(databaseName: String) {

    val request = DeleteDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteDatabase(request)
        println("$databaseName was successfully deleted")
    }
}

suspend fun deleteCrawler(crawlerName: String) {

    val request = DeleteCrawlerRequest {
        name = crawlerName
```

```
    }
    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteCrawler(request)
        println("$crawlerName was deleted")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Glue;

use Aws\Glue\GlueClient;
use Aws\S3\S3Client;
use AwsUtilities\AWSServiceClass;
use GuzzleHttp\Psr7\Stream;
use Iam\IAMService;

class GettingStartedWithGlue
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the AWS Glue getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();

        $glueClient = new GlueClient($clientArgs);
        $glueService = new GlueService($glueClient);
        $iamService = new IAMService();
        $crawlerName = "example-crawler-test-" . $uniqid;

        AWSServiceClass::$waitTime = 5;
        AWSServiceClass::$maxWaitAttempts = 20;
```

```
        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $databaseName = "doc-example-database-$uniqid";
        $path = 's3://crawler-public-us-east-1/flight/2016/csv';
        $glueService->createCrawler($crawlerName, $role['Role']['Arn'],
$databaseName, $path);
        $glueService->startCrawler($crawlerName);

        echo "Waiting for crawler";
        do {
            $crawler = $glueService->getCrawler($crawlerName);
            echo ".";
            sleep(10);
        } while ($crawler['Crawler']['State'] != "READY");
        echo "\n";

        $database = $glueService->getDatabase($databaseName);
        echo "Found a database named " . $database['Database']['Name'] . "\n";

        //Upload job script
        $s3client = new S3Client($clientArgs);
        $bucketName = "test-glue-bucket-" . $uniqid;
        $s3client->createBucket([
            'Bucket' => $bucketName,
            'CreateBucketConfiguration' => ['LocationConstraint' => 'us-west-2'],
        ]);

        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => 'run_job.py',
            'SourceFile' => __DIR__ . '/flight_etl_job_script.py'
        ]);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => 'setup_scenario_getting_started.yaml',
            'SourceFile' => __DIR__ . '/setup_scenario_getting_started.yaml'
        ]);

        $tables = $glueService->getTables($databaseName);

        $jobName = 'test-job-' . $uniqid;
        $scriptLocation = "s3://$bucketName/run_job.py";
        $job = $glueService->createJob($jobName, $role['Role']['Arn'],
$scriptLocation);
```

```
        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl)['JobRunId'];

        echo "waiting for job";
        do {
            $jobRun = $glueService->getJobRun($jobName, $runId);
            echo ".";
            sleep(10);
        } while (!array_intersect([$jobRun['JobRun']['JobRunState']],
['SUCCEEDED', 'STOPPED', 'FAILED', 'TIMEOUT']));
        echo "\n";

        $jobRuns = $glueService->getJobRuns($jobName);

        $objects = $s3client->listObjects([
            'Bucket' => $bucketName,
        ])['Contents'];

        foreach ($objects as $object) {
            echo $object['Key'] . "\n";
        }

        echo "Downloading " . $objects[1]['Key'] . "\n";
        /** @var Stream $downloadObject */
        $downloadObject = $s3client->getObject([
            'Bucket' => $bucketName,
            'Key' => $objects[1]['Key'],
        ])['Body']->getContents();
        echo "Here is the first 1000 characters in the object.";
        echo substr($downloadObject, 0, 1000);

        $jobs = $glueService->listJobs();
        echo "Current jobs:\n";
        foreach ($jobs['JobNames'] as $jobsName) {
            echo "{$jobsName}\n";
        }

        echo "Delete the job.\n";
        $glueClient->deleteJob([
            'JobName' => $job['Name'],
        ]);
```

```
        echo "Delete the tables.\n";
        foreach ($tables['TableList'] as $table) {
            $glueService->deleteTable($table['Name'], $databaseName);
        }

        echo "Delete the databases.\n";
        $glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);

        echo "Delete the crawler.\n";
        $glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);

        $deleteObjects = $s3client->listObjectsV2([
            'Bucket' => $bucketName,
        ]);
        echo "Delete all objects in the bucket.\n";
        $deleteObjects = $s3client->deleteObjects([
            'Bucket' => $bucketName,
            'Delete' => [
                'Objects' => $deleteObjects['Contents'],
            ]
        ]);
        echo "Delete the bucket.\n";
        $s3client->deleteBucket(['Bucket' => $bucketName]);

        echo "This job was brought to you by the number $uniqid\n";
    }
}

namespace Glue;

use Aws\Glue\GlueClient;
use Aws\Result;

use function PHPUnit\Framework\isEmpty;

class GlueService extends \AwsUtilities\AWSServiceClass
{
    protected GlueClient $glueClient;

    public function __construct($glueClient)
```

```
    {
        $this->glueClient = $glueClient;
    }

    public function getCrawler($crawlerName)
    {
        return $this->customWaiter(function () use ($crawlerName) {
            return $this->glueClient->getCrawler([
                'Name' => $crawlerName,
            ]);
        });
    }

    public function createCrawler($crawlerName, $role, $databaseName, $path):
 Result
    {
        return $this->customWaiter(function () use ($crawlerName, $role,
 $databaseName, $path) {
            return $this->glueClient->createCrawler([
                'Name' => $crawlerName,
                'Role' => $role,
                'DatabaseName' => $databaseName,
                'Targets' => [
                    'S3Targets' =>
                        [[
                            'Path' => $path,
                        ]]
                ],
            ]);
        });
    }

    public function startCrawler($crawlerName): Result
    {
        return $this->glueClient->startCrawler([
            'Name' => $crawlerName,
        ]);
    }

    public function getDatabase(string $databaseName): Result
    {
        return $this->customWaiter(function () use ($databaseName) {
            return $this->glueClient->getDatabase([
                'Name' => $databaseName,
```

```
            ]);
        });
    }

    public function getTables($databaseName): Result
    {
        return $this->glueClient->getTables([
            'DatabaseName' => $databaseName,
        ]);
    }

    public function createJob($jobName, $role, $scriptLocation, $pythonVersion =
'3', $glueVersion = '3.0'): Result
    {
        return $this->glueClient->createJob([
            'Name' => $jobName,
            'Role' => $role,
            'Command' => [
                'Name' => 'glueetl',
                'ScriptLocation' => $scriptLocation,
                'PythonVersion' => $pythonVersion,
            ],
            'GlueVersion' => $glueVersion,
        ]);
    }

    public function startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl): Result
    {
        return $this->glueClient->startJobRun([
            'JobName' => $jobName,
            'Arguments' => [
                'input_database' => $databaseName,
                'input_table' => $tables['TableList'][0]['Name'],
                'output_bucket_url' => $outputBucketUrl,
                '--input_database' => $databaseName,
                '--input_table' => $tables['TableList'][0]['Name'],
                '--output_bucket_url' => $outputBucketUrl,
            ],
        ]);
    }

    public function listJobs($maxResults = null, $nextToken = null, $tags = []):
Result
```

```
    {
        $arguments = [];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        if (!empty($tags)) {
            $arguments['Tags'] = $tags;
        }
        return $this->glueClient->listJobs($arguments);
    }

    public function getJobRuns($jobName, $maxResults = 0, $nextToken = ''):
 Result
    {
        $arguments = ['JobName' => $jobName];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        return $this->glueClient->getJobRuns($arguments);
    }

    public function getJobRun($jobName, $runId, $predecessorsIncluded = false):
 Result
    {
        return $this->glueClient->getJobRun([
            'JobName' => $jobName,
            'RunId' => $runId,
            'PredecessorsIncluded' => $predecessorsIncluded,
        ]);
    }

    public function deleteJob($jobName)
    {
        return $this->glueClient->deleteJob([
            'JobName' => $jobName,
        ]);
    }
```

```
    public function deleteTable($tableName, $databaseName)
    {
        return $this->glueClient->deleteTable([
            'DatabaseName' => $databaseName,
            'Name' => $tableName,
        ]);
    }

    public function deleteDatabase($databaseName)
    {
        return $this->glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);
    }

    public function deleteCrawler($crawlerName)
    {
        return $this->glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns

- GetTables
- ListJobs
- StartCrawler
- StartJobRun

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do AWS Glue usadas no cenário.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_crawler(self, name):
        """
        Gets information about a crawler.

        :param name: The name of the crawler to look up.
        :return: Data about the crawler.
        """
        crawler = None
        try:
            response = self.glue_client.get_crawler(Name=name)
            crawler = response["Crawler"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityNotFoundException":
```

```
                logger.info("Crawler %s doesn't exist.", name)
            else:
                logger.error(
                    "Couldn't get crawler %s. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return crawler


    def create_crawler(self, name, role_arn, db_name, db_prefix, s3_target):
        """
        Creates a crawler that can crawl the specified target and populate a
        database in your AWS Glue Data Catalog with metadata that describes the
data
        in the target.

        :param name: The name of the crawler.
        :param role_arn: The Amazon Resource Name (ARN) of an AWS Identity and
Access
                         Management (IAM) role that grants permission to let AWS
Glue
                         access the resources it needs.
        :param db_name: The name to give the database that is created by the
crawler.
        :param db_prefix: The prefix to give any database tables that are created
by
                          the crawler.
        :param s3_target: The URL to an S3 bucket that contains data that is
                          the target of the crawler.
        """
        try:
            self.glue_client.create_crawler(
                Name=name,
                Role=role_arn,
                DatabaseName=db_name,
                TablePrefix=db_prefix,
                Targets={"S3Targets": [{"Path": s3_target}]},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create crawler. Here's why: %s: %s",
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def start_crawler(self, name):
        """
        Starts a crawler. The crawler crawls its configured target and creates
        metadata that describes the data it finds in the target data source.

        :param name: The name of the crawler to start.
        """
        try:
            self.glue_client.start_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't start crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_database(self, name):
        """
        Gets information about a database in your Data Catalog.

        :param name: The name of the database to look up.
        :return: Information about the database.
        """
        try:
            response = self.glue_client.get_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't get database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Database"]
```

```
    def get_tables(self, db_name):
        """
        Gets a list of tables in a Data Catalog database.

        :param db_name: The name of the database to query.
        :return: The list of tables in the database.
        """
        try:
            response = self.glue_client.get_tables(DatabaseName=db_name)
        except ClientError as err:
            logger.error(
                "Couldn't get tables %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["TableList"]


    def create_job(self, name, description, role_arn, script_location):
        """
        Creates a job definition for an extract, transform, and load (ETL) job
that can
        be run by AWS Glue.

        :param name: The name of the job definition.
        :param description: The description of the job definition.
        :param role_arn: The ARN of an IAM role that grants AWS Glue the
permissions
                         it requires to run the job.
        :param script_location: The Amazon S3 URL of a Python ETL script that is
run as
                                part of the job. The script defines how the data
is
                                transformed.
        """
        try:
            self.glue_client.create_job(
                Name=name,
                Description=description,
```

```
                Role=role_arn,
                Command={
                    "Name": "glueetl",
                    "ScriptLocation": script_location,
                    "PythonVersion": "3",
                },
                GlueVersion="3.0",
            )
        except ClientError as err:
            logger.error(
                "Couldn't create job %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def start_job_run(self, name, input_database, input_table,
output_bucket_name):
        """
        Starts a job run. A job run extracts data from the source, transforms it,
        and loads it to the output bucket.

        :param name: The name of the job definition.
        :param input_database: The name of the metadata database that contains
tables
                               that describe the source data. This is typically
created
                               by a crawler.
        :param input_table: The name of the table in the metadata database that
                            describes the source data.
        :param output_bucket_name: The S3 bucket where the output is written.
        :return: The ID of the job run.
        """
        try:
            # The custom Arguments that are passed to this function are used by
the
            # Python ETL script to determine the location of input and output
data.
            response = self.glue_client.start_job_run(
                JobName=name,
                Arguments={
                    "--input_database": input_database,
```

```
                    "--input_table": input_table,
                    "--output_bucket_url": f"s3://{output_bucket_name}/",
                },
            )
        except ClientError as err:
            logger.error(
                "Couldn't start job run %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRunId"]


    def list_jobs(self):
        """
        Lists the names of job definitions in your account.

        :return: The list of job definition names.
        """
        try:
            response = self.glue_client.list_jobs()
        except ClientError as err:
            logger.error(
                "Couldn't list jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobNames"]


    def get_job_runs(self, job_name):
        """
        Gets information about runs that have been performed for a specific job
        definition.

        :param job_name: The name of the job definition to look up.
        :return: The list of job runs.
        """
        try:
```

```
            response = self.glue_client.get_job_runs(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't get job runs for %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRuns"]


    def get_job_run(self, name, run_id):
        """
        Gets information about a single job run.

        :param name: The name of the job definition for the run.
        :param run_id: The ID of the run.
        :return: Information about the run.
        """
        try:
            response = self.glue_client.get_job_run(JobName=name, RunId=run_id)
        except ClientError as err:
            logger.error(
                "Couldn't get job run %s/%s. Here's why: %s: %s",
                name,
                run_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRun"]


    def delete_job(self, job_name):
        """
        Deletes a job definition. This also deletes data about all runs that are
        associated with this job definition.

        :param job_name: The name of the job definition to delete.
        """
        try:
```

```
            self.glue_client.delete_job(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete job %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_table(self, db_name, table_name):
        """
        Deletes a table from a metadata database.

        :param db_name: The name of the database that contains the table.
        :param table_name: The name of the table to delete.
        """
        try:
            self.glue_client.delete_table(DatabaseName=db_name, Name=table_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_database(self, name):
        """
        Deletes a metadata database from your Data Catalog.

        :param name: The name of the database to delete.
        """
        try:
            self.glue_client.delete_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise


    def delete_crawler(self, name):
        """
        Deletes a crawler.

        :param name: The name of the crawler to delete.
        """
        try:
            self.glue_client.delete_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma classe que execute o cenário.

```
class GlueCrawlerJobScenario:
    """
    Encapsulates a scenario that shows how to create an AWS Glue crawler and job
 and use
    them to transform data from CSV to JSON format.
    """

    def __init__(self, glue_client, glue_service_role, glue_bucket):
        """
        :param glue_client: A Boto3 AWS Glue client.
        :param glue_service_role: An AWS Identity and Access Management (IAM)
 role
                                  that AWS Glue can assume to gain access to the
                                  resources it requires.
        :param glue_bucket: An S3 bucket that can hold a job script and output
 data
```

```
                                from AWS Glue job runs.
        """
        self.glue_client = glue_client
        self.glue_service_role = glue_service_role
        self.glue_bucket = glue_bucket

    @staticmethod
    def wait(seconds, tick=12):
        """
        Waits for a specified number of seconds, while also displaying an
animated
        spinner.

        :param seconds: The number of seconds to wait.
        :param tick: The number of frames per second used to animate the spinner.
        """
        progress = "|/-\\"
        waited = 0
        while waited < seconds:
            for frame in range(tick):
                sys.stdout.write(f"\r{progress[frame % len(progress)]}")
                sys.stdout.flush()
                time.sleep(1 / tick)
            waited += 1

    def upload_job_script(self, job_script):
        """
        Uploads a Python ETL script to an S3 bucket. The script is used by the
AWS Glue
        job to transform data.

        :param job_script: The relative path to the job script.
        """
        try:
            self.glue_bucket.upload_file(Filename=job_script, Key=job_script)
            print(f"Uploaded job script '{job_script}' to the example bucket.")
        except S3UploadFailedError as err:
            logger.error("Couldn't upload job script. Here's why: %s", err)
            raise

    def run(self, crawler_name, db_name, db_prefix, data_source, job_script,
job_name):
        """
```

```
        Runs the scenario. This is an interactive experience that runs at a
command
        prompt and asks you for input throughout.

        :param crawler_name: The name of the crawler used in the scenario. If the
                             crawler does not exist, it is created.
        :param db_name: The name to give the metadata database created by the
crawler.
        :param db_prefix: The prefix to give tables added to the database by the
                          crawler.
        :param data_source: The location of the data source that is targeted by
the
                            crawler and extracted during job runs.
        :param job_script: The job script that is used to transform data during
job
                           runs.
        :param job_name: The name to give the job definition that is created
during the
                         scenario.
        """
        wrapper = GlueWrapper(self.glue_client)
        print(f"Checking for crawler {crawler_name}.")
        crawler = wrapper.get_crawler(crawler_name)
        if crawler is None:
            print(f"Creating crawler {crawler_name}.")
            wrapper.create_crawler(
                crawler_name,
                self.glue_service_role.arn,
                db_name,
                db_prefix,
                data_source,
            )
            print(f"Created crawler {crawler_name}.")
            crawler = wrapper.get_crawler(crawler_name)
        pprint(crawler)
        print("-" * 88)

        print(
            f"When you run the crawler, it crawls data stored in {data_source}
and "
            f"creates a metadata database in the AWS Glue Data Catalog that
describes "
            f"the data in the data source."
        )
```

```
        print("In this example, the source data is in CSV format.")
        ready = False
        while not ready:
            ready = Question.ask_question(
                "Ready to start the crawler? (y/n) ", Question.is_yesno
            )
        wrapper.start_crawler(crawler_name)
        print("Let's wait for the crawler to run. This typically takes a few
minutes.")
        crawler_state = None
        while crawler_state != "READY":
            self.wait(10)
            crawler = wrapper.get_crawler(crawler_name)
            crawler_state = crawler["State"]
            print(f"Crawler is {crawler['State']}.")
        print("-" * 88)

        database = wrapper.get_database(db_name)
        print(f"The crawler created database {db_name}:")
        pprint(database)
        print(f"The database contains these tables:")
        tables = wrapper.get_tables(db_name)
        for index, table in enumerate(tables):
            print(f"\t{index + 1}. {table['Name']}")
        table_index = Question.ask_question(
            f"Enter the number of a table to see more detail: ",
            Question.is_int,
            Question.in_range(1, len(tables)),
        )
        pprint(tables[table_index - 1])
        print("-" * 88)

        print(f"Creating job definition {job_name}.")
        wrapper.create_job(
            job_name,
            "Getting started example job.",
            self.glue_service_role.arn,
            f"s3://{self.glue_bucket.name}/{job_script}",
        )
        print("Created job definition.")
        print(
            f"When you run the job, it extracts data from {data_source},
transforms it "
            f"by using the {job_script} script, and loads the output into "
```

```
            f"S3 bucket {self.glue_bucket.name}."
        )
        print(
            "In this example, the data is transformed from CSV to JSON, and only
a few "
            "fields are included in the output."
        )
        job_run_status = None
        if Question.ask_question(f"Ready to run? (y/n) ", Question.is_yesno):
            job_run_id = wrapper.start_job_run(
                job_name, db_name, tables[0]["Name"], self.glue_bucket.name
            )
            print(f"Job {job_name} started. Let's wait for it to run.")
            while job_run_status not in ["SUCCEEDED", "STOPPED", "FAILED",
"TIMEOUT"]:
                self.wait(10)
                job_run = wrapper.get_job_run(job_name, job_run_id)
                job_run_status = job_run["JobRunState"]
                print(f"Job {job_name}/{job_run_id} is {job_run_status}.")
        print("-" * 88)

        if job_run_status == "SUCCEEDED":
            print(
                f"Data from your job run is stored in your S3 bucket
'{self.glue_bucket.name}':"
            )
            try:
                keys = [
                    obj.key for obj in
self.glue_bucket.objects.filter(Prefix="run-")
                ]
                for index, key in enumerate(keys):
                    print(f"\t{index + 1}: {key}")
                lines = 4
                key_index = Question.ask_question(
                    f"Enter the number of a block to download it and see the
first {lines} "
                    f"lines of JSON output in the block: ",
                    Question.is_int,
                    Question.in_range(1, len(keys)),
                )
                job_data = io.BytesIO()
                self.glue_bucket.download_fileobj(keys[key_index - 1], job_data)
                job_data.seek(0)
```

```
                for _ in range(lines):
                    print(job_data.readline().decode("utf-8"))
            except ClientError as err:
                logger.error(
                    "Couldn't get job run data. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
            print("-" * 88)

        job_names = wrapper.list_jobs()
        if job_names:
            print(f"Your account has {len(job_names)} jobs defined:")
            for index, job_name in enumerate(job_names):
                print(f"\t{index + 1}. {job_name}")
            job_index = Question.ask_question(
                f"Enter a number between 1 and {len(job_names)} to see the list
of runs for "
                f"a job: ",
                Question.is_int,
                Question.in_range(1, len(job_names)),
            )
            job_runs = wrapper.get_job_runs(job_names[job_index - 1])
            if job_runs:
                print(f"Found {len(job_runs)} runs for job {job_names[job_index -
1]}:")
                for index, job_run in enumerate(job_runs):
                    print(
                        f"\t{index + 1}. {job_run['JobRunState']} on "
                        f"{job_run['CompletedOn']:%Y-%m-%d %H:%M:%S}"
                    )
                run_index = Question.ask_question(
                    f"Enter a number between 1 and {len(job_runs)} to see details
for a run: ",
                    Question.is_int,
                    Question.in_range(1, len(job_runs)),
                )
                pprint(job_runs[run_index - 1])
            else:
                print(f"No runs found for job {job_names[job_index - 1]}")
        else:
            print("Your account doesn't have any jobs defined.")
        print("-" * 88)
```

```
        print(
            f"Let's clean up. During this example we created job definition
 '{job_name}'."
        )
        if Question.ask_question(
            "Do you want to delete the definition and all runs? (y/n) ",
            Question.is_yesno,
        ):
            wrapper.delete_job(job_name)
            print(f"Job definition '{job_name}' deleted.")
        tables = wrapper.get_tables(db_name)
        print(f"We also created database '{db_name}' that contains these
 tables:")
        for table in tables:
            print(f"\t{table['Name']}")
        if Question.ask_question(
            "Do you want to delete the tables and the database? (y/n) ",
            Question.is_yesno,
        ):
            for table in tables:
                wrapper.delete_table(db_name, table["Name"])
                print(f"Deleted table {table['Name']}.")
            wrapper.delete_database(db_name)
            print(f"Deleted database {db_name}.")
        print(f"We also created crawler '{crawler_name}'.")
        if Question.ask_question(
            "Do you want to delete the crawler? (y/n) ", Question.is_yesno
        ):
            wrapper.delete_crawler(crawler_name)
            print(f"Deleted crawler {crawler_name}.")
        print("-" * 88)


def parse_args(args):
    """
    Parse command line arguments.

    :param args: The command line arguments.
    :return: The parsed arguments.
    """
    parser = argparse.ArgumentParser(
        description="Runs the AWS Glue getting started with crawlers and jobs
 scenario. "
```

```
        "Before you run this scenario, set up scaffold resources by running "
        "'python scaffold.py deploy'."
    )
    parser.add_argument(
        "role_name",
        help="The name of an IAM role that AWS Glue can assume. This role must
 grant access "
        "to Amazon S3 and to the permissions granted by the AWSGlueServiceRole "
        "managed policy.",
    )
    parser.add_argument(
        "bucket_name",
        help="The name of an S3 bucket that AWS Glue can access to get the job
 script and "
        "put job results.",
    )
    parser.add_argument(
        "--job_script",
        default="flight_etl_job_script.py",
        help="The name of the job script file that is used in the scenario.",
    )
    return parser.parse_args(args)


def main():
    args = parse_args(sys.argv[1:])
    try:
        print("-" * 88)
        print(
            "Welcome to the AWS Glue getting started with crawlers and jobs
 scenario."
        )
        print("-" * 88)
        scenario = GlueCrawlerJobScenario(
            boto3.client("glue"),
            boto3.resource("iam").Role(args.role_name),
            boto3.resource("s3").Bucket(args.bucket_name),
        )
        scenario.upload_job_script(args.job_script)
        scenario.run(
            "doc-example-crawler",
            "doc-example-database",
            "doc-example-",
            "s3://crawler-public-us-east-1/flight/2016/csv",
```

```
            args.job_script,
            "doc-example-job",
        )
        print("-" * 88)
        print(
            "To destroy scaffold resources, including the IAM role and S3 bucket
 "
            "used in this scenario, run 'python scaffold.py destroy'."
        )
        print("\nThanks for watching!")
        print("-" * 88)
    except Exception:
        logging.exception("Something went wrong with the example.")
```

Crie um script de ETL usado pelo AWS Glue para extrair, transformar e carregar dados durante execuções de trabalhos.

```
import sys
from awsglue.transforms import *
from awsglue.utils import getResolvedOptions
from pyspark.context import SparkContext
from awsglue.context import GlueContext
from awsglue.job import Job

"""
These custom arguments must be passed as Arguments to the StartJobRun request.
    --input_database    The name of a metadata database that is contained in
 your
                        AWS Glue Data Catalog and that contains tables that
 describe
                        the data to be processed.
    --input_table       The name of a table in the database that describes the
 data to
                        be processed.
    --output_bucket_url An S3 bucket that receives the transformed output data.
"""
args = getResolvedOptions(
    sys.argv, ["JOB_NAME", "input_database", "input_table", "output_bucket_url"]
)
sc = SparkContext()
```

```
glueContext = GlueContext(sc)
spark = glueContext.spark_session
job = Job(glueContext)
job.init(args["JOB_NAME"], args)

# Script generated for node S3 Flight Data.
S3FlightData_node1 = glueContext.create_dynamic_frame.from_catalog(
    database=args["input_database"],
    table_name=args["input_table"],
    transformation_ctx="S3FlightData_node1",
)

# This mapping performs two main functions:
# 1. It simplifies the output by removing most of the fields from the data.
# 2. It renames some fields. For example, `fl_date` is renamed to `flight_date`.
ApplyMapping_node2 = ApplyMapping.apply(
    frame=S3FlightData_node1,
    mappings=[
        ("year", "long", "year", "long"),
        ("month", "long", "month", "tinyint"),
        ("day_of_month", "long", "day", "tinyint"),
        ("fl_date", "string", "flight_date", "string"),
        ("carrier", "string", "carrier", "string"),
        ("fl_num", "long", "flight_num", "long"),
        ("origin_city_name", "string", "origin_city_name", "string"),
        ("origin_state_abr", "string", "origin_state_abr", "string"),
        ("dest_city_name", "string", "dest_city_name", "string"),
        ("dest_state_abr", "string", "dest_state_abr", "string"),
        ("dep_time", "long", "departure_time", "long"),
        ("wheels_off", "long", "wheels_off", "long"),
        ("wheels_on", "long", "wheels_on", "long"),
        ("arr_time", "long", "arrival_time", "long"),
        ("mon", "string", "mon", "string"),
    ],
    transformation_ctx="ApplyMapping_node2",
)

# Script generated for node Revised Flight Data.
RevisedFlightData_node3 = glueContext.write_dynamic_frame.from_options(
    frame=ApplyMapping_node2,
    connection_type="s3",
    format="json",
    connection_options={"path": args["output_bucket_url"], "partitionKeys": []},
    transformation_ctx="RevisedFlightData_node3",
```

```
)

job.commit()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do AWS Glue usadas no cenário.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing
 a simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods
 for interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific crawler.
  #
  # @param name [String] The name of the crawler to retrieve information about.
  # @return [Aws::Glue::Types::Crawler, nil] The crawler object if found, or nil
 if not found.
  def get_crawler(name)
    @glue_client.get_crawler(name: name)
  rescue Aws::Glue::Errors::EntityNotFoundException
    @logger.info("Crawler #{name} doesn't exist.")
    false
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get crawler #{name}: \n#{e.message}")
    raise
  end

  # Creates a new crawler with the specified configuration.
  #
  # @param name [String] The name of the crawler.
  # @param role_arn [String] The ARN of the IAM role to be used by the crawler.
  # @param db_name [String] The name of the database where the crawler stores its
 metadata.
  # @param db_prefix [String] The prefix to be added to the names of tables that
 the crawler creates.
  # @param s3_target [String] The S3 path that the crawler will crawl.
  # @return [void]
  def create_crawler(name, role_arn, db_name, db_prefix, s3_target)
    @glue_client.create_crawler(
      name: name,
      role: role_arn,
      database_name: db_name,
```

```
      targets: {
        s3_targets: [
          {
            path: s3_target
          }
        ]
      }
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create crawler: \n#{e.message}")
    raise
  end

  # Starts a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to start.
  # @return [void]
  def start_crawler(name)
    @glue_client.start_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not start crawler #{name}: \n#{e.message}")
    raise
  end

  # Deletes a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to delete.
  # @return [void]
  def delete_crawler(name)
    @glue_client.delete_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete crawler #{name}: \n#{e.message}")
    raise
  end

  # Retrieves information about a specific database.
  #
  # @param name [String] The name of the database to retrieve information about.
  # @return [Aws::Glue::Types::Database, nil] The database object if found, or
 nil if not found.
  def get_database(name)
    response = @glue_client.get_database(name: name)
    response.database
rescue Aws::Glue::Errors::GlueException => e
```

```
  @logger.error("Glue could not get database #{name}: \n#{e.message}")
  raise
  end

  # Retrieves a list of tables in the specified database.
  #
  # @param db_name [String] The name of the database to retrieve tables from.
  # @return [Array<Aws::Glue::Types::Table>]
  def get_tables(db_name)
    response = @glue_client.get_tables(database_name: db_name)
    response.table_list
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get tables #{db_name}: \n#{e.message}")
    raise
  end

  # Creates a new job with the specified configuration.
  #
  # @param name [String] The name of the job.
  # @param description [String] The description of the job.
  # @param role_arn [String] The ARN of the IAM role to be used by the job.
  # @param script_location [String] The location of the ETL script for the job.
  # @return [void]
  def create_job(name, description, role_arn, script_location)
    @glue_client.create_job(
      name: name,
      description: description,
      role: role_arn,
      command: {
        name: "glueetl",
        script_location: script_location,
        python_version: "3"
      },
      glue_version: "3.0"
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create job #{name}: \n#{e.message}")
    raise
  end

  # Starts a job run for the specified job.
  #
  # @param name [String] The name of the job to start the run for.
  # @param input_database [String] The name of the input database for the job.
```

```
  # @param input_table [String] The name of the input table for the job.
  # @param output_bucket_name [String] The name of the output S3 bucket for the
 job.
  # @return [String] The ID of the started job run.
  def start_job_run(name, input_database, input_table, output_bucket_name)
    response = @glue_client.start_job_run(
      job_name: name,
      arguments: {
        '--input_database': input_database,
        '--input_table': input_table,
        '--output_bucket_url': "s3://#{output_bucket_name}/"
      }
    )
    response.job_run_id
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not start job run #{name}: \n#{e.message}")
    raise
  end

  # Retrieves a list of jobs in AWS Glue.
  #
  # @return [Aws::Glue::Types::ListJobsResponse]
  def list_jobs
    @glue_client.list_jobs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not list jobs: \n#{e.message}")
    raise
  end

  # Retrieves a list of job runs for the specified job.
  #
  # @param job_name [String] The name of the job to retrieve job runs for.
  # @return [Array<Aws::Glue::Types::JobRun>]
  def get_job_runs(job_name)
    response = @glue_client.get_job_runs(job_name: job_name)
    response.job_runs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end

  # Retrieves data for a specific job run.
  #
  # @param job_name [String] The name of the job run to retrieve data for.
  # @return [Glue::Types::GetJobRunResponse]
```

```
  def get_job_run(job_name, run_id)
    @glue_client.get_job_run(job_name: job_name, run_id: run_id)
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end

  # Deletes a job with the specified name.
  #
  # @param job_name [String] The name of the job to delete.
  # @return [void]
  def delete_job(job_name)
    @glue_client.delete_job(job_name: job_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end

  # Deletes a table with the specified name.
  #
  # @param database_name [String] The name of the catalog database in which the
 table resides.
  # @param table_name [String] The name of the table to be deleted.
  # @return [void]
  def delete_table(database_name, table_name)
    @glue_client.delete_table(database_name: database_name, name: table_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end

  # Removes a specified database from a Data Catalog.
  #
  # @param database_name [String] The name of the database to delete.
  # @return [void]
  def delete_database(database_name)
    @glue_client.delete_database(name: database_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete database: \n#{e.message}")
  end

  # Uploads a job script file to an S3 bucket.
  #
  # @param file_path [String] The local path of the job script file.
  # @param bucket_resource [Aws::S3::Bucket] The S3 bucket resource to upload the
 file to.
  # @return [void]
```

```
  def upload_job_script(file_path, bucket_resource)
    File.open(file_path) do |file|
      bucket_resource.client.put_object({
       body: file,
       bucket: bucket_resource.name,
       key: file_path
     })
    end
  rescue Aws::S3::Errors::S3UploadFailedError => e
    @logger.error("S3 could not upload job script: \n#{e.message}")
    raise
  end

end
```

Crie uma classe que execute o cenário.

```
class GlueCrawlerJobScenario
  def initialize(glue_client, glue_service_role, glue_bucket, logger)
    @glue_client = glue_client
    @glue_service_role = glue_service_role
    @glue_bucket = glue_bucket
    @logger = logger
  end

  def run(crawler_name, db_name, db_prefix, data_source, job_script, job_name)
    wrapper = GlueWrapper.new(@glue_client, @logger)

    new_step(1, "Create a crawler")
    puts "Checking for crawler #{crawler_name}."
    crawler = wrapper.get_crawler(crawler_name)
    if crawler == false
      puts "Creating crawler #{crawler_name}."
      wrapper.create_crawler(crawler_name, @glue_service_role.arn, db_name,
 db_prefix, data_source)
      puts "Successfully created #{crawler_name}:"
      crawler = wrapper.get_crawler(crawler_name)
      puts JSON.pretty_generate(crawler).yellow
    end
    print "\nDone!\n".green

    new_step(2, "Run a crawler to output a database.")
```

```
    puts "Location of input data analyzed by crawler: #{data_source}"
    puts "Outputs: a Data Catalog database in CSV format containing metadata on
input."
    wrapper.start_crawler(crawler_name)
    puts "Starting crawler... (this typically takes a few minutes)"
    crawler_state = nil
    while crawler_state != "READY"
      custom_wait(15)
      crawler = wrapper.get_crawler(crawler_name)
      crawler_state = crawler[0]["state"]
      print "Status check: #{crawler_state}.".yellow
    end
    print "\nDone!\n".green

    new_step(3, "Query the database.")
    database = wrapper.get_database(db_name)
    puts "The crawler created database #{db_name}:"
    print "#{database}".yellow
    puts "\nThe database contains these tables:"
    tables = wrapper.get_tables(db_name)
    tables.each_with_index do |table, index|
      print "\t#{index + 1}. #{table['name']}".yellow
    end
    print "\nDone!\n".green

    new_step(4, "Create a job definition that runs an ETL script.")
    puts "Uploading Python ETL script to S3..."
    wrapper.upload_job_script(job_script, @glue_bucket)
    puts "Creating job definition #{job_name}:\n"
    response = wrapper.create_job(job_name, "Getting started example job.",
@glue_service_role.arn, "s3://#{@glue_bucket.name}/#{job_script}")
    puts JSON.pretty_generate(response).yellow
    print "\nDone!\n".green

    new_step(5, "Start a new job")
    job_run_status = nil
    job_run_id = wrapper.start_job_run(
      job_name,
      db_name,
      tables[0]["name"],
      @glue_bucket.name
    )
    puts "Job #{job_name} started. Let's wait for it to run."
    until ["SUCCEEDED", "STOPPED", "FAILED", "TIMEOUT"].include?(job_run_status)
```

```
      custom_wait(10)
      job_run = wrapper.get_job_runs(job_name)
      job_run_status = job_run[0]["job_run_state"]
      print "Status check: #{job_name}/#{job_run_id} - #{job_run_status}.".yellow
    end
    print "\nDone!\n".green

    new_step(6, "View results from a successful job run.")
    if job_run_status == "SUCCEEDED"
      puts "Data from your job run is stored in your S3 bucket
'#{@glue_bucket.name}'. Files include:"
      begin

        # Print the key name of each object in the bucket.
        @glue_bucket.objects.each do |object_summary|
          if object_summary.key.include?("run-")
            print "#{object_summary.key}".yellow
          end
        end

        # Print the first 256 bytes of a run file
        desired_sample_objects = 1
        @glue_bucket.objects.each do |object_summary|
          if object_summary.key.include?("run-")
            if desired_sample_objects > 0
              sample_object = @glue_bucket.object(object_summary.key)
              sample = sample_object.get(range: "bytes=0-255").body.read
              puts "\nSample run file contents:"
              print "#{sample}".yellow
              desired_sample_objects -= 1
            end
          end
        end
      rescue Aws::S3::Errors::ServiceError => e
        logger.error(
          "Couldn't get job run data. Here's why: %s: %s",
          e.response.error.code, e.response.error.message
        )
        raise
      end
    end
    print "\nDone!\n".green

    new_step(7, "Delete job definition and crawler.")
```

```
    wrapper.delete_job(job_name)
    puts "Job deleted: #{job_name}."
    wrapper.delete_crawler(crawler_name)
    puts "Crawler deleted: #{crawler_name}."
    wrapper.delete_table(db_name, tables[0]["name"])
    puts "Table deleted: #{tables[0]["name"]} in #{db_name}."
    wrapper.delete_database(db_name)
    puts "Database deleted: #{db_name}."
    print "\nDone!\n".green
  end
end

def main

  banner("../../helpers/banner.txt")
  puts
 "##################################################################################
  puts "#
                            #".yellow
  puts "#                                          EXAMPLE CODE DEMO:
                            #".yellow
  puts "#                                              AWS Glue
                            #".yellow
  puts "#
                            #".yellow
  puts
 "##################################################################################
  puts ""
  puts "You have launched a demo of AWS Glue using the AWS for Ruby v3 SDK. Over
 the next 60 seconds, it will"
  puts "do the following:"
  puts "    1. Create a crawler."
  puts "    2. Run a crawler to output a database."
  puts "    3. Query the database."
  puts "    4. Create a job definition that runs an ETL script."
  puts "    5. Start a new job."
  puts "    6. View results from a successful job run."
  puts "    7. Delete job definition and crawler."
  puts ""

  confirm_begin
  billing
  security
  puts "\e[H\e[2J"
```

```
  # Set input file names
  job_script_filepath = "job_script.py"
  resource_names = YAML.load_file("resource_names.yaml")

  # Instantiate existing IAM role.
  iam = Aws::IAM::Resource.new(region: "us-east-1")
  iam_role_name = resource_names["glue_service_role"]
  iam_role = iam.role(iam_role_name)

  # Instantiate existing S3 bucket.
  s3 = Aws::S3::Resource.new(region: "us-east-1")
  s3_bucket_name = resource_names["glue_bucket"]
  s3_bucket = s3.bucket(s3_bucket_name)

  scenario = GlueCrawlerJobScenario.new(
    Aws::Glue::Client.new(region: "us-east-1"),
    iam_role,
    s3_bucket,
    @logger
  )

  random_int = rand(10 ** 4)
  scenario.run(
    "doc-example-crawler-#{random_int}",
    "doc-example-database-#{random_int}",
    "doc-example-#{random_int}-",
    "s3://crawler-public-us-east-1/flight/2016/csv",
    job_script_filepath,
    "doc-example-job-#{random_int}"
  )

  puts "-" * 88
  puts "You have reached the end of this tour of AWS Glue."
  puts "To destroy CDK-created resources, run:\n       cdk destroy"
  puts "-" * 88

end
```

Crie um script de ETL usado pelo AWS Glue para extrair, transformar e carregar dados durante execuções de trabalhos.

```
import sys
from awsglue.transforms import *
from awsglue.utils import getResolvedOptions
from pyspark.context import SparkContext
from awsglue.context import GlueContext
from awsglue.job import Job

"""
These custom arguments must be passed as Arguments to the StartJobRun request.
    --input_database    The name of a metadata database that is contained in
 your
                        AWS Glue Data Catalog and that contains tables that
 describe
                        the data to be processed.
    --input_table       The name of a table in the database that describes the
 data to
                        be processed.
    --output_bucket_url An S3 bucket that receives the transformed output data.
"""
args = getResolvedOptions(
    sys.argv, ["JOB_NAME", "input_database", "input_table", "output_bucket_url"]
)
sc = SparkContext()
glueContext = GlueContext(sc)
spark = glueContext.spark_session
job = Job(glueContext)
job.init(args["JOB_NAME"], args)

# Script generated for node S3 Flight Data.
S3FlightData_node1 = glueContext.create_dynamic_frame.from_catalog(
    database=args["input_database"],
    table_name=args["input_table"],
    transformation_ctx="S3FlightData_node1",
)

# This mapping performs two main functions:
# 1. It simplifies the output by removing most of the fields from the data.
# 2. It renames some fields. For example, `fl_date` is renamed to `flight_date`.
ApplyMapping_node2 = ApplyMapping.apply(
    frame=S3FlightData_node1,
    mappings=[
        ("year", "long", "year", "long"),
        ("month", "long", "month", "tinyint"),
```

```
        ("day_of_month", "long", "day", "tinyint"),
        ("fl_date", "string", "flight_date", "string"),
        ("carrier", "string", "carrier", "string"),
        ("fl_num", "long", "flight_num", "long"),
        ("origin_city_name", "string", "origin_city_name", "string"),
        ("origin_state_abr", "string", "origin_state_abr", "string"),
        ("dest_city_name", "string", "dest_city_name", "string"),
        ("dest_state_abr", "string", "dest_state_abr", "string"),
        ("dep_time", "long", "departure_time", "long"),
        ("wheels_off", "long", "wheels_off", "long"),
        ("wheels_on", "long", "wheels_on", "long"),
        ("arr_time", "long", "arrival_time", "long"),
        ("mon", "string", "mon", "string"),
    ],
    transformation_ctx="ApplyMapping_node2",
)

# Script generated for node Revised Flight Data.
RevisedFlightData_node3 = glueContext.write_dynamic_frame.from_options(
    frame=ApplyMapping_node2,
    connection_type="s3",
    format="json",
    connection_options={"path": args["output_bucket_url"], "partitionKeys": []},
    transformation_ctx="RevisedFlightData_node3",
)

job.commit()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase

- GetDatabases
- GetJob
- GetJobRun
- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e execute um crawler que examine um bucket público do Amazon Simple Storage Service (Amazon S3) e gere um banco de dados de metadados que descreva os dados no formato CSV que encontrar.

```
        let create_crawler = glue
            .create_crawler()
            .name(self.crawler())
            .database_name(self.database())
            .role(self.iam_role.expose_secret())
            .targets(
                CrawlerTargets::builder()
                    .s3_targets(S3Target::builder().path(CRAWLER_TARGET).build())
                    .build(),
            )
            .send()
            .await;

        match create_crawler {
            Err(err) => {
```

```
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::AlreadyExistsException(_) => {
                        info!("Using existing crawler");
                        Ok(())
                    }
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
            Ok(_) => Ok(()),
        }?;

        let start_crawler =
glue.start_crawler().name(self.crawler()).send().await;

        match start_crawler {
            Ok(_) => Ok(()),
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::CrawlerRunningException(_) => Ok(()),
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
        }?;
```

Liste informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.

```
        let database = glue
            .get_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?
            .to_owned();
        let database = database
            .database()
            .ok_or_else(|| GlueMvpError::Unknown("Could not find
database".into()))?;

        let tables = glue
            .get_tables()
```

```
            .database_name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let tables = tables.table_list();
```

Crie e execute um trabalho que extraia dados em CSV do bucket do Amazon S3 de origem, transforme-os removendo e renomeando campos, e carregue a saída formatada em JSON em outro bucket do Amazon S3.

```
        let create_job = glue
            .create_job()
            .name(self.job())
            .role(self.iam_role.expose_secret())
            .command(
                JobCommand::builder()
                    .name("glueetl")
                    .python_version("3")
                    .script_location(format!("s3://{}/job.py", self.bucket()))
                    .build(),
            )
            .glue_version("3.0")
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job_name = create_job.name().ok_or_else(|| {
            GlueMvpError::Unknown("Did not get job name after creating
job".into())
        })?;

        let job_run_output = glue
            .start_job_run()
            .job_name(self.job())
            .arguments("--input_database", self.database())
            .arguments(
                "--input_table",
                self.tables
                    .get(0)
                    .ok_or_else(|| GlueMvpError::Unknown("Missing crawler
table".into()))?
```

```
                    .name(),
            )
            .arguments("--output_bucket_url", self.bucket())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job = job_run_output
            .job_run_id()
            .ok_or_else(|| GlueMvpError::Unknown("Missing run id from just
started job".into()))?
            .to_string();
```

Exclua todos os recursos criados pela demonstração.

```
        glue.delete_job()
            .job_name(self.job())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        for t in &self.tables {
            glue.delete_table()
                .name(t.name())
                .database_name(self.database())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
        }

        glue.delete_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        glue.delete_crawler()
            .name(self.crawler())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

Exemplos de código para HealthImaging usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS HealthImaging com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- HealthImaging Guia do desenvolvedor — Mais informações sobre HealthImaging.

- HealthImaging Referência da API — Detalhes sobre todas as HealthImaging ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá HealthImaging

O exemplo de código a seguir mostra como começar a usar o HealthImaging.

C++

SDK for C++

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS medical-imaging)

# Set this project's name.
project("hello_health-imaging")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
```

```
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
    # and set the proper subdirectory to the executable location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS "" ${CMAKE_CURRENT_BINARY_DIR}
 ${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_health_imaging.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_health_imaging.cpp.

```
#include <aws/core/Aws.h>
#include <aws/medical-imaging/MedicalImagingClient.h>
#include <aws/medical-imaging/model/ListDatastoresRequest.h>

#include <iostream>

/*
 *  A "Hello HealthImaging" starter application which initializes an AWS
 HealthImaging (HealthImaging) client
 *  and lists the HealthImaging data stores in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_health-imaging'
 *
 */
#include <aws/core/auth/AWSCredentialsProviderChain.h>
#include <aws/core/platform/Environment.h>

int main(int argc, char **argv) {
```

```
    (void) argc;
    (void) argv;
    Aws::SDKOptions options;
    //   Optional: change the log level for debugging.
    //   options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Debug;

    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::MedicalImaging::MedicalImagingClient
medicalImagingClient(clientConfig);
        Aws::MedicalImaging::Model::ListDatastoresRequest listDatastoresRequest;

        Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
allDataStoreSummaries;
        Aws::String nextToken; // Used for paginated results.
        do {
            if (!nextToken.empty()) {
                listDatastoresRequest.SetNextToken(nextToken);
            }
            Aws::MedicalImaging::Model::ListDatastoresOutcome
listDatastoresOutcome =
                    medicalImagingClient.ListDatastores(listDatastoresRequest);
            if (listDatastoresOutcome.IsSuccess()) {
                const Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
&dataStoreSummaries =

listDatastoresOutcome.GetResult().GetDatastoreSummaries();
                allDataStoreSummaries.insert(allDataStoreSummaries.cend(),
                                             dataStoreSummaries.cbegin(),
                                             dataStoreSummaries.cend());
                nextToken = listDatastoresOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "ListDatastores error: "
                          << listDatastoresOutcome.GetError().GetMessage() <<
std::endl;
                break;
            }
        } while (!nextToken.empty());
```

```
        std::cout << allDataStoreSummaries.size() << " HealthImaging data "
                  << ((allDataStoreSummaries.size() == 1) ?
                      "store was retrieved." : "stores were retrieved.") <<
 std::endl;

        for (auto const &dataStoreSummary: allDataStoreSummaries) {
            std::cout << "  Datastore: " << dataStoreSummary.GetDatastoreName()
                      << std::endl;
            std::cout << "  Datastore ID: " << dataStoreSummary.GetDatastoreId()
                      << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import {
  ListDatastoresCommand,
  MedicalImagingClient,
} from "@aws-sdk/client-medical-imaging";

// When no region or credentials are provided, the SDK will use the
// region and credentials from the local AWS config.
const client = new MedicalImagingClient({});

export const helloMedicalImaging = async () => {
  const command = new ListDatastoresCommand({});
```

```
  const { datastoreSummaries } = await client.send(command);
  console.log("Datastores: ");
  console.log(datastoreSummaries.map((item) => item.datastoreName).join("\n"));
  return datastoreSummaries;
};
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos de código

- Ações para HealthImaging usar AWS SDKs
  - Adicionar uma tag a um HealthImaging recurso usando um AWS SDK
  - Copiar um conjunto de HealthImaging imagens usando um AWS SDK
  - Crie um armazenamento HealthImaging de dados usando um AWS SDK
  - Excluir um armazenamento HealthImaging de dados usando um AWS SDK
  - Excluir um conjunto de HealthImaging imagens usando um AWS SDK
  - Obtenha uma moldura de HealthImaging imagem usando um AWS SDK
  - Obtenha propriedades do armazenamento de HealthImaging dados usando um AWS SDK
  - Obtenha as propriedades do conjunto de HealthImaging imagens usando um AWS SDK
  - Obtenha propriedades do trabalho de importação usando um SDK da AWS
  - Obtenha metadados para um conjunto de HealthImaging imagens usando um SDK AWS
  - Importe dados em massa para um armazenamento HealthImaging de dados usando um AWS SDK
  - Listar armazenamentos de HealthImaging dados usando um AWS SDK
  - Listar versões do conjunto de HealthImaging imagens usando um AWS SDK
  - Listar trabalhos de importação para um armazenamento HealthImaging de dados usando um AWS SDK
  - Listar tags para um HealthImaging recurso usando um AWS SDK

- Remover uma tag de um HealthImaging recurso usando um AWS SDK
- Pesquise conjuntos de HealthImaging imagens usando um AWS SDK
- Atualize os metadados do conjunto de HealthImaging imagens usando um SDK AWS
- Cenários para HealthImaging usar AWS SDKs
  - Comece a usar conjuntos de HealthImaging imagens e molduras de imagem usando um AWS SDK
  - Marcar um armazenamento HealthImaging de dados usando um SDK AWS
  - Marcar um conjunto de HealthImaging imagens usando um SDK AWS

Ações para HealthImaging usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS HealthImaging com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para HealthImaging usar AWS SDKs.

Exemplos

- Adicionar uma tag a um HealthImaging recurso usando um AWS SDK
- Copiar um conjunto de HealthImaging imagens usando um AWS SDK
- Crie um armazenamento HealthImaging de dados usando um AWS SDK
- Excluir um armazenamento HealthImaging de dados usando um AWS SDK
- Excluir um conjunto de HealthImaging imagens usando um AWS SDK
- Obtenha uma moldura de HealthImaging imagem usando um AWS SDK
- Obtenha propriedades do armazenamento de HealthImaging dados usando um AWS SDK
- Obtenha as propriedades do conjunto de HealthImaging imagens usando um AWS SDK
- Obtenha propriedades do trabalho de importação usando um SDK da AWS
- Obtenha metadados para um conjunto de HealthImaging imagens usando um SDK AWS
- Importe dados em massa para um armazenamento HealthImaging de dados usando um AWS SDK
- Listar armazenamentos de HealthImaging dados usando um AWS SDK
- Listar versões do conjunto de HealthImaging imagens usando um AWS SDK
- Listar trabalhos de importação para um armazenamento HealthImaging de dados usando um AWS SDK

- Listar tags para um HealthImaging recurso usando um AWS SDK
- Remover uma tag de um HealthImaging recurso usando um AWS SDK
- Pesquise conjuntos de HealthImaging imagens usando um AWS SDK
- Atualize os metadados do conjunto de HealthImaging imagens usando um SDK AWS

Adicionar uma tag a um HealthImaging recurso usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar uma tag a um HealthImaging recurso.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Marcar um datastore
- Marcar um conjunto de imagens

CLI

AWS CLI

Exemplo 1: para marcar um armazenamento de dados

Os exemplos de código `tag-resource` a seguir marcam um armazenamento de dados.

```
aws medical-imaging tag-resource \
  --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012" \
  --tags '{"Deployment":"Development"}'
```

Este comando não produz saída.

Exemplo 2: para marcar um conjunto de imagens

Os exemplos de código `tag-resource` a seguir marcam um conjunto de imagens.

```
aws medical-imaging tag-resource \
    --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/18f88ac7870584f58d56256646b4d92b" \
```

```
    --tags '{"Deployment":"Development"}'
```

Este comando não produz saída.

Para obter mais informações, consulte Como marcar recursos AWS HealthImaging no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte TagResourceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static void tagMedicalImagingResource(MedicalImagingClient
medicalImagingClient,
           String resourceArn,
           Map<String, String> tags) {
       try {
           TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .tags(tags)
                   .build();

           medicalImagingClient.tagResource(tagResourceRequest);

           System.out.println("Tags have been added to the resource.");
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte TagResourcea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tags = {}
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte TagResourceea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
tags=tags)
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a TagResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copiar um conjunto de HealthImaging imagens usando um AWS SDK

Os exemplos de código a seguir mostram como copiar um conjunto de HealthImaging imagens.

CLI

AWS CLI

Exemplo 1: para copiar um conjunto de imagens sem um destino.

O exemplo de código `copy-image-set` a seguir faz uma cópia duplicada de uma imagem sem um destino.

```
aws medical-imaging copy-image-set \
    --datastore-id 12345678901234567890123456789012 \
    --source-image-set-id ea92b0d8838c72a3f25d00d13616f87e \
    --copy-image-set-information '{"sourceImageSet": {"latestVersionId": "1" } }'
```

Saída:

```
{
    "destinationImageSetProperties": {
        "latestVersionId": "1",
        "imageSetWorkflowStatus": "COPYING",
        "updatedAt": 1680042357.432,
        "imageSetId": "b9a06fef182a5f992842f77f8e0868e5",
        "imageSetState": "LOCKED",
        "createdAt": 1680042357.432
    },
    "sourceImageSetProperties": {
        "latestVersionId": "5",
        "imageSetWorkflowStatus": "COPYING_WITH_READ_ONLY_ACCESS",
        "updatedAt": 1680042357.432,
        "imageSetState": "LOCKED",
        "createdAt": 1680027126.436
    },
    "datastoreId": "12345678901234567890123456789012"
}
```

Exemplo 2: para copiar um conjunto de imagens com um destino.

O exemplo de código `copy-image-set` a seguir faz uma cópia duplicada de um conjunto de imagens com um destino.

```
aws medical-imaging copy-image-set \
    --datastore-id 12345678901234567890123456789012 \
    --source-image-set-id ea92b0d8838c72a3f25d00d13616f87e \
    --copy-image-set-information '{"sourceImageSet": {"latestVersionId": "5" },
 "destinationImageSet": { "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
 "latestVersionId": "1"} }'
```

Saída:

```
{
    "destinationImageSetProperties": {
        "latestVersionId": "2",
        "imageSetWorkflowStatus": "COPYING",
        "updatedAt": 1680042505.135,
        "imageSetId": "b9a06fef182a5f992842f77f8e0868e5",
        "imageSetState": "LOCKED",
        "createdAt": 1680042357.432
    },
    "sourceImageSetProperties": {
        "latestVersionId": "5",
        "imageSetWorkflowStatus": "COPYING_WITH_READ_ONLY_ACCESS",
        "updatedAt": 1680042505.135,
        "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
        "imageSetState": "LOCKED",
        "createdAt": 1680027126.436
    },
    "datastoreId": "12345678901234567890123456789012"
}
```

Para obter mais informações, consulte Copiar um conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte CopyImageSetem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
    public static String copyMedicalImageSet(MedicalImagingClient
 medicalImagingClient,
            String datastoreId,
            String imageSetId,
```

```
            String latestVersionId,
            String destinationImageSetId,
            String destinationVersionId) {

        try {
            CopySourceImageSetInformation copySourceImageSetInformation =
CopySourceImageSetInformation.builder()
                    .latestVersionId(latestVersionId)
                    .build();

            CopyImageSetInformation.Builder copyImageSetBuilder =
CopyImageSetInformation.builder()
                    .sourceImageSet(copySourceImageSetInformation);

            if (destinationImageSetId != null) {
                copyImageSetBuilder =
copyImageSetBuilder.destinationImageSet(CopyDestinationImageSet.builder()
                        .imageSetId(destinationImageSetId)
                        .latestVersionId(destinationVersionId)
                        .build());
            }

            CopyImageSetRequest copyImageSetRequest =
CopyImageSetRequest.builder()
                    .datastoreId(datastoreId)
                    .sourceImageSetId(imageSetId)
                    .copyImageSetInformation(copyImageSetBuilder.build())
                    .build();

            CopyImageSetResponse response =
medicalImagingClient.copyImageSet(copyImageSetRequest);

            return response.destinationImageSetProperties().imageSetId();
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
```

- Para obter detalhes da API, consulte CopyImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

Função de utilitário para copiar um conjunto de imagens.

```
import { CopyImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imageSetId - The source image set ID.
 * @param {string} sourceVersionId - The source version ID.
 * @param {string} destinationImageSetId - The optional ID of the destination
 image set.
 * @param {string} destinationVersionId - The optional version ID of the
 destination image set.
 */
export const copyImageSet = async (
  datastoreId = "xxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxx",
  sourceVersionId = "1",
  destinationImageSetId = "",
  destinationVersionId = ""
) => {
  const params = {
    datastoreId: datastoreId,
    sourceImageSetId: imageSetId,
    copyImageSetInformation: {
      sourceImageSet: { latestVersionId: sourceVersionId },
    },
  };
  if (destinationImageSetId !== "" && destinationVersionId !== "") {
```

```
    params.copyImageSetInformation.destinationImageSet = {
      imageSetId: destinationImageSetId,
      latestVersionId: destinationVersionId,
    };
  }

  const response = await medicalImagingClient.send(
    new CopyImageSetCommand(params)
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'd9b219ce-cc48-4a44-a5b2-c5c3068f1ee8',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //      },
  //       datastoreId: 'xxxxxxxxxxxxxx',
  //       destinationImageSetProperties: {
  //             createdAt: 2023-09-27T19:46:21.824Z,
  //             imageSetArn: 'arn:aws:medical-imaging:us-
east-1:xxxxxxxxxxx:datastore/xxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxxxx',
  //             imageSetId: 'xxxxxxxxxxxxxxx',
  //             imageSetState: 'LOCKED',
  //             imageSetWorkflowStatus: 'COPYING',
  //             latestVersionId: '1',
  //             updatedAt: 2023-09-27T19:46:21.824Z
  //       },
  //       sourceImageSetProperties: {
  //             createdAt: 2023-09-22T14:49:26.427Z,
  //             imageSetArn: 'arn:aws:medical-imaging:us-
east-1:xxxxxxxxxxx:datastore/xxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxx',
  //             imageSetId: 'xxxxxxxxxxxxxxx',
  //             imageSetState: 'LOCKED',
  //             imageSetWorkflowStatus: 'COPYING_WITH_READ_ONLY_ACCESS',
  //             latestVersionId: '4',
  //             updatedAt: 2023-09-27T19:46:21.824Z
  //      }
  // }
  return response;
};
```

Copie um conjunto de imagens sem um destino.

```
try {
  await copyImageSet(
    "12345678901234567890123456789012",
    "12345678901234567890123456789012",
    "1"
  );
} catch (err) {
  console.error(err);
}
```

Copie um conjunto de imagens com um destino.

```
try {
  await copyImageSet(
    "12345678901234567890123456789012",
    "12345678901234567890123456789012",
    "4",
    "12345678901234567890123456789012",
    "1"
  );
} catch (err) {
  console.error(err);
}
```

- Para obter detalhes da API, consulte CopyImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

Função de utilitário para copiar um conjunto de imagens.

```
    def copy_image_set(
        self,
        datastore_id,
        image_set_id,
        version_id,
        destination_image_set_id=None,
        destination_version_id=None,
    ):
        """
        Copy an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The ID of the image set version.
        :param destination_image_set_id: The ID of the optional destination image
set.
        :param destination_version_id: The ID of the optional destination image
set version.
        :return: The copied image set ID.
        """
        try:
            copy_image_set_information = {
                "sourceImageSet": {"latestVersionId": version_id}
            }
            if destination_image_set_id and destination_version_id:
                copy_image_set_information["destinationImageSet"] = {
                    "imageSetId": destination_image_set_id,
                    "latestVersionId": destination_version_id,
                }
            copy_results = self.health_imaging_client.copy_image_set(
                datastoreId=datastore_id,
                sourceImageSetId=image_set_id,
                copyImageSetInformation=copy_image_set_information,
            )
        except ClientError as err:
            logger.error(
                "Couldn't copy image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return copy_results["destinationImageSetProperties"]["imageSetId"]
```

Copie um conjunto de imagens sem um destino.

```
            copy_image_set_information = {
                "sourceImageSet": {"latestVersionId": version_id}
            }

            copy_results = self.health_imaging_client.copy_image_set(
                datastoreId=datastore_id,
                sourceImageSetId=image_set_id,
                copyImageSetInformation=copy_image_set_information,
            )
```

Copie um conjunto de imagens com um destino.

```
            copy_image_set_information = {
                "sourceImageSet": {"latestVersionId": version_id}
            }

            if destination_image_set_id and destination_version_id:
                copy_image_set_information["destinationImageSet"] = {
                    "imageSetId": destination_image_set_id,
                    "latestVersionId": destination_version_id,
                }

            copy_results = self.health_imaging_client.copy_image_set(
                datastoreId=datastore_id,
                sourceImageSetId=image_set_id,
                copyImageSetInformation=copy_image_set_information,
            )
```

- Para obter detalhes da API, consulte a CopyImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um armazenamento HealthImaging de dados usando um AWS SDK

Os exemplos de código a seguir mostram como criar um armazenamento HealthImaging de dados.

Bash

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_create_datastore
#
# This function creates an AWS HealthImaging data store for importing DICOM P10
 files.
#
# Parameters:
#       -n data_store_name - The name of the data store.
#
# Returns:
#       The datastore ID.
#    And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function imaging_create_datastore() {
  local datastore_name response
  local option OPTARG # Required to use getopts command in a function.
```

```
# bashsupport disable=BP5008
function usage() {
  echo "function imaging_create_datastore"
  echo "Creates an AWS HealthImaging data store for importing DICOM P10 files."
  echo "  -n data_store_name - The name of the data store."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:h" option; do
  case "${option}" in
    n) datastore_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$datastore_name" ]]; then
  errecho "ERROR: You must provide a data store name with the -n parameter."
  usage
  return 1
fi

response=$(aws medical-imaging create-datastore \
  --datastore-name "$datastore_name" \
  --output text \
  --query 'datastoreId')

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports medical-imaging create-datastore operation
failed.$response"
  return 1
fi
```

```
  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para criar um armazenamento de dados

O exemplo de código `create-datastore` a seguir cria um armazenamento de dados com o nome de `my-datastore`.

```
aws medical-imaging create-datastore \
    --datastore-name "my-datastore"
```

Saída:

```
{
    "datastoreId": "12345678901234567890123456789012",
    "datastoreStatus": "CREATING"
}
```

Para obter mais informações, consulte Criação de um armazenamento de dados no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte CreateDatastoreem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static String createMedicalImageDatastore(MedicalImagingClient
medicalImagingClient,
           String datastoreName) {
       try {
           CreateDatastoreRequest datastoreRequest =
CreateDatastoreRequest.builder()
                   .datastoreName(datastoreName)
                   .build();
           CreateDatastoreResponse response =
medicalImagingClient.createDatastore(datastoreRequest);
           return response.datastoreId();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return "";
   }
```

- Para obter detalhes da API, consulte CreateDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { CreateDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreName - The name of the data store to create.
```

```
 */
export const createDatastore = async (datastoreName = "DATASTORE_NAME") => {
  const response = await medicalImagingClient.send(
    new CreateDatastoreCommand({ datastoreName: datastoreName })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: 'a71cd65f-2382-49bf-b682-f9209d8d399b',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //    },
  //    datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //    datastoreStatus: 'CREATING'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte CreateDatastorea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def create_datastore(self, name):
        """
        Create a data store.

        :param name: The name of the data store to create.
        :return: The data store ID.
        """
```

```
        try:
            data_store =
 self.health_imaging_client.create_datastore(datastoreName=name)
        except ClientError as err:
            logger.error(
                "Couldn't create data store %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return data_store["datastoreId"]
```

- Para obter detalhes da API, consulte a CreateDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um armazenamento HealthImaging de dados usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um armazenamento HealthImaging de dados.

Bash

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}
```

```
##############################################################################
# function imaging_delete_datastore
#
# This function deletes an AWS HealthImaging data store.
#
# Parameters:
#       -i datastore_id - The ID of the data store.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function imaging_delete_datastore() {
  local datastore_id response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_delete_datastore"
    echo "Deletes an AWS HealthImaging data store."
    echo "  -i datastore_id - The ID of the data store."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "i:h" option; do
    case "${option}" in
      i) datastore_id="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$datastore_id" ]]; then
    errecho "ERROR: You must provide a data store ID with the -i parameter."
    usage
```

```
    return 1
  fi

  response=$(aws medical-imaging delete-datastore \
    --datastore-id "$datastore_id")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports medical-imaging delete-datastore operation
 failed.$response"
    return 1
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para excluir um armazenamento de dados

O exemplo de código `delete-datastore` a seguir exclui um armazenamento de dados.

```
aws medical-imaging delete-datastore \
    --datastore-id "12345678901234567890123456789012"
```

Saída:

```
{
```

```
    "datastoreId": "12345678901234567890123456789012",
    "datastoreStatus": "DELETING"
}
```

Para obter mais informações, consulte Excluindo um armazenamento de dados no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte DeleteDatastoreem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static void deleteMedicalImagingDatastore(MedicalImagingClient
medicalImagingClient,
           String datastoreID) {
       try {
           DeleteDatastoreRequest datastoreRequest =
DeleteDatastoreRequest.builder()
                   .datastoreId(datastoreID)
                   .build();
           medicalImagingClient.deleteDatastore(datastoreRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { DeleteDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store to delete.
 */
export const deleteDatastore = async (datastoreId = "DATASTORE_ID") => {
  const response = await medicalImagingClient.send(
    new DeleteDatastoreCommand({ datastoreId })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //           httpStatusCode: 200,
  //           requestId: 'f5beb409-678d-48c9-9173-9a001ee1ebb1',
  //           extendedRequestId: undefined,
  //           cfId: undefined,
  //           attempts: 1,
  //           totalRetryDelay: 0
  //        },
  //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //     datastoreStatus: 'DELETING'
  // }

  return response;
};
```

- Para obter detalhes da API, consulte DeleteDatastorea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def delete_datastore(self, datastore_id):
        """
        Delete a data store.

        :param datastore_id: The ID of the data store.
        """
        try:
            self.health_imaging_client.delete_datastore(datastoreId=datastore_id)
        except ClientError as err:
            logger.error(
                "Couldn't delete data store %s. Here's why: %s: %s",
                datastore_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um conjunto de HealthImaging imagens usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um conjunto de HealthImaging imagens.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

```
//! Routine which deletes an AWS HealthImaging image set.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::deleteImageSet(
        const Aws::String &dataStoreID, const Aws::String &imageSetID,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::DeleteImageSetRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    Aws::MedicalImaging::Model::DeleteImageSetOutcome outcome =
 client.DeleteImageSet(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted image set " << imageSetID
                  << " from data store " << dataStoreID << std::endl;
    }
    else {
        std::cerr << "Error deleting image set " << imageSetID << " from data
 store "
                  << dataStoreID << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para excluir um conjunto de imagens

O exemplo de código `delete-image-set` a seguir exclui um conjunto de imagens.

```
aws medical-imaging delete-image-set \
    --datastore-id 12345678901234567890123456789012 \
    --image-set-id ea92b0d8838c72a3f25d00d13616f87e
```

Saída:

```
{
    "imageSetWorkflowStatus": "DELETING",
    "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
    "imageSetState": "LOCKED",
    "datastoreId": "12345678901234567890123456789012"
}
```

Para obter mais informações, consulte Excluir um conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte DeleteImageSetem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
    public static void deleteMedicalImageSet(MedicalImagingClient
 medicalImagingClient,
            String datastoreId,
            String imagesetId) {
```

```
        try {
            DeleteImageSetRequest deleteImageSetRequest =
 DeleteImageSetRequest.builder()
                    .datastoreId(datastoreId)
                    .imageSetId(imagesetId)
                    .build();

            medicalImagingClient.deleteImageSet(deleteImageSetRequest);

            System.out.println("The image set was deleted.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { DeleteImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The data store ID.
 * @param {string} imageSetId - The image set ID.
 */
export const deleteImageSet = async (
  datastoreId = "xxxxxxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxxxxxx"
) => {
  const response = await medicalImagingClient.send(
```

```
    new DeleteImageSetCommand({
      datastoreId: datastoreId,
      imageSetId: imageSetId,
    })
  );
  console.log(response);
  // {
  //    '$metadata': {
  //        httpStatusCode: 200,
  //        requestId: '6267bbd2-eaa5-4a50-8ee8-8fddf535cf73',
  //        extendedRequestId: undefined,
  //        cfId: undefined,
  //        attempts: 1,
  //        totalRetryDelay: 0
  //     },
  //     datastoreId: 'xxxxxxxxxxxxxxx',
  //     imageSetId: 'xxxxxxxxxxxxxx',
  //     imageSetState: 'LOCKED',
  //     imageSetWorkflowStatus: 'DELETING'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def delete_image_set(self, datastore_id, image_set_id):
        """
        Delete an image set.

        :param datastore_id: The ID of the data store.
```

```
        :param image_set_id: The ID of the image set.
        :return: The delete results.
        """
        try:
            delete_results = self.health_imaging_client.delete_image_set(
                imageSetId=image_set_id, datastoreId=datastore_id
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return delete_results
```

- Para obter detalhes da API, consulte a DeleteImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha uma moldura de HealthImaging imagem usando um AWS SDK

O exemplo de código a seguir mostra como obter um quadro de imagem.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

```
//! Routine which downloads an AWS HealthImaging image frame.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param frameID: The image frame ID.
  \param jphFile: File to store the downloaded frame.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageFrame(const Aws::String &dataStoreID,
                                            const Aws::String &imageSetID,
                                            const Aws::String &frameID,
                                            const Aws::String &jphFile,
                                            const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);

    Aws::MedicalImaging::Model::GetImageFrameRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);

    Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
    imageFrameInformation.SetImageFrameId(frameID);
    request.SetImageFrameInformation(imageFrameInformation);

    Aws::MedicalImaging::Model::GetImageFrameOutcome outcome =
 client.GetImageFrame(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved image frame." << std::endl;
        auto &buffer = outcome.GetResult().GetImageFrameBlob();

        std::ofstream outfile(jphFile, std::ios::binary);
        outfile << buffer.rdbuf();
    }
    else {
        std::cout << "Error retrieving image frame." <<
 outcome.GetError().GetMessage()
                  << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para obter dados de pixels do conjunto de imagens

O exemplo de código `get-image-frame` a seguir obtém um quadro de imagem.

```
aws medical-imaging get-image-frame \
    --datastore-id "12345678901234567890123456789012" \
    --image-set-id "98765412345612345678907890789012" \
    --image-frame-information imageFrameId=3abf5d5d7ae72f80a0ec81b2c0de3ef4 \
    imageframe.jph
```

Observação: esse exemplo de código não inclui a saída porque a GetImageFrame ação retorna um fluxo de dados de pixels para o arquivo imageframe.jph. Para obter informações sobre decodificação e visualização de quadros de imagem, consulte as bibliotecas de decodificação HTJ2K.

Para obter mais informações, consulte Obter dados de pixels do conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte GetImageFrameem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
        public static void getMedicalImageSetFrame(MedicalImagingClient
medicalImagingClient,
                        String destinationPath,
                        String datastoreId,
                        String imagesetId,
                        String imageFrameId) {

                try {
                        GetImageFrameRequest getImageSetMetadataRequest =
GetImageFrameRequest.builder()
                                        .datastoreId(datastoreId)
                                        .imageSetId(imagesetId)

.imageFrameInformation(ImageFrameInformation.builder()

.imageFrameId(imageFrameId)
                                                        .build())
                                        .build();

medicalImagingClient.getImageFrame(getImageSetMetadataRequest,

FileSystems.getDefault().getPath(destinationPath));

                        System.out.println("Image frame downloaded to " +
destinationPath);
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { GetImageFrameCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} imageFrameFileName - The name of the file for the HTJ2K-
encoded image frame.
 * @param {string} datastoreID - The data store's ID.
 * @param {string} imageSetID - The image set's ID.
 * @param {string} imageFrameID - The image frame's ID.
 */
export const getImageFrame = async (
  imageFrameFileName = "image.jph",
  datastoreID = "DATASTORE_ID",
  imageSetID = "IMAGE_SET_ID",
  imageFrameID = "IMAGE_FRAME_ID"
) => {
  const response = await medicalImagingClient.send(
    new GetImageFrameCommand({
      datastoreId: datastoreID,
      imageSetId: imageSetID,
      imageFrameInformation: { imageFrameId: imageFrameID },
    })
  );
  const buffer = await response.imageFrameBlob.transformToByteArray();
  writeFileSync(imageFrameFileName, buffer);

  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'e4ab42a5-25a3-4377-873f-374ecf4380e1',
  //         extendedRequestId: undefined,
```

```
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     contentType: 'application/octet-stream',
  //     imageFrameBlob: <ref *1> IncomingMessage {}
  // }
  return response;
};
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def get_pixel_data(
        self, file_path_to_write, datastore_id, image_set_id, image_frame_id
    ):
        """
        Get an image frame's pixel data.

        :param file_path_to_write: The path to write the image frame's HTJ2K
 encoded pixel data.
        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param image_frame_id: The ID of the image frame.
        """
        try:
            image_frame = self.health_imaging_client.get_image_frame(
                datastoreId=datastore_id,
                imageSetId=image_set_id,
                imageFrameInformation={"imageFrameId": image_frame_id},
            )
```

```
            with open(file_path_to_write, "wb") as f:
                for chunk in image_frame["imageFrameBlob"].iter_chunks():
                    if chunk:
                        f.write(chunk)
        except ClientError as err:
            logger.error(
                "Couldn't get image frame. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a GetImageFrameReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha propriedades do armazenamento de HealthImaging dados usando um AWS SDK

Os exemplos de código a seguir mostram como obter propriedades do armazenamento de HealthImaging dados.

Bash

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}
```

```
##############################################################################
# function imaging_get_datastore
#
# Get a data store's properties.
#
# Parameters:
#       -i data_store_id - The ID of the data store.
#
# Returns:
#       [datastore_name, datastore_id, datastore_status, datastore_arn,
 created_at, updated_at]
#    And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function imaging_get_datastore() {
  local datastore_id option OPTARG # Required to use getopts command in a
 function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_get_datastore"
    echo "Gets a data store's properties."
    echo "  -i datastore_id - The ID of the data store."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "i:h" option; do
    case "${option}" in
      i) datastore_id="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1
```

```
  if [[ -z "$datastore_id" ]]; then
    errecho "ERROR: You must provide a data store ID with the -i parameter."
    usage
    return 1
  fi

  local response

  response=$(
    aws medical-imaging get-datastore \
      --datastore-id "$datastore_id" \
      --output text \
      --query "[ datastoreProperties.datastoreName,
 datastoreProperties.datastoreId, datastoreProperties.datastoreStatus,
 datastoreProperties.datastoreArn,  datastoreProperties.createdAt,
 datastoreProperties.updatedAt]"
  )
  error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-datastores operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte GetDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para obter as propriedades de um armazenamento de dados

O exemplo de código `get-datastore` a seguir obtém as propriedades de um armazenamento de dados.

```
aws medical-imaging get-datastore \
    --datastore-id 12345678901234567890123456789012
```

Saída:

```
{
    "datastoreProperties": {
        "datastoreId": "12345678901234567890123456789012",
        "datastoreName": "TestDatastore123",
        "datastoreStatus": "ACTIVE",
        "datastoreArn": "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012",
        "createdAt": "2022-11-15T23:33:09.643000+00:00",
        "updatedAt": "2022-11-15T23:33:09.643000+00:00"
    }
}
```

Para obter mais informações, consulte Obter propriedades do armazenamento de dados no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte GetDatastoreem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
    public static DatastoreProperties
 getMedicalImageDatastore(MedicalImagingClient medicalImagingClient,
            String datastoreID) {
        try {
            GetDatastoreRequest datastoreRequest = GetDatastoreRequest.builder()
                    .datastoreId(datastoreID)
```

```
                    .build();
            GetDatastoreResponse response =
 medicalImagingClient.getDatastore(datastoreRequest);
            return response.datastoreProperties();
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }
```

- Para obter detalhes da API, consulte GetDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { GetDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreID - The ID of the data store.
 */
export const getDatastore = async (datastoreID = "DATASTORE_ID") => {
  const response = await medicalImagingClient.send(
    new GetDatastoreCommand({ datastoreId: datastoreID })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: '55ea7d2e-222c-4a6a-871e-4f591f40cadb',
  //       extendedRequestId: undefined,
```

```
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //    },
  //   datastoreProperties: {
  //        createdAt: 2023-08-04T18:50:36.239Z,
  //         datastoreArn: 'arn:aws:medical-imaging:us-
east-1:xxxxxxxxx:datastore/xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //         datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //         datastoreName: 'my_datastore',
  //         datastoreStatus: 'ACTIVE',
  //         updatedAt: 2023-08-04T18:50:36.239Z
  //   }
  // }
  return response["datastoreProperties"];
};
```

- Para obter detalhes da API, consulte GetDatastorea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def get_datastore_properties(self, datastore_id):
        """
        Get the properties of a data store.

        :param datastore_id: The ID of the data store.
        :return: The data store properties.
        """
        try:
            data_store = self.health_imaging_client.get_datastore(
                datastoreId=datastore_id
            )
```

```
        except ClientError as err:
            logger.error(
                "Couldn't get data store %s. Here's why: %s: %s",
                id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return data_store["datastoreProperties"]
```

- Para obter detalhes da API, consulte a GetDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha as propriedades do conjunto de HealthImaging imagens usando um AWS SDK

Os exemplos de código a seguir mostram como obter as propriedades do conjunto de HealthImaging imagens.

CLI

AWS CLI

Para obter as propriedades do conjunto de imagens

O exemplo de código `get-image-set` a seguir obtém as propriedades de um conjunto de imagens.

```
aws medical-imaging get-image-set \
    --datastore-id 12345678901234567890123456789012 \
    --image-set-id 18f88ac7870584f58d56256646b4d92b \
    --version-id 1
```

Saída:

```
{
    "versionId": "1",
    "imageSetWorkflowStatus": "COPIED",
    "updatedAt": 1680027253.471,
    "imageSetId": "18f88ac7870584f58d56256646b4d92b",
    "imageSetState": "ACTIVE",
    "createdAt": 1679592510.753,
    "datastoreId": "12345678901234567890123456789012"
}
```

Para obter mais informações, consulte Como obter propriedades do conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte GetImageSetem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static GetImageSetResponse getMedicalImageSet(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String imagesetId,
           String versionId) {
       try {
           GetImageSetRequest.Builder getImageSetRequestBuilder =
GetImageSetRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId);

           if (versionId != null) {
               getImageSetRequestBuilder =
getImageSetRequestBuilder.versionId(versionId);
           }

           return
medicalImagingClient.getImageSet(getImageSetRequestBuilder.build());
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
        return null;
    }
```

- Para obter detalhes da API, consulte GetImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { GetImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imageSetId - The ID of the image set.
 * @param {string} imageSetVersion - The optional version of the image set.
 *
 */
export const getImageSet = async (
  datastoreId = "xxxxxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxxxxx",
  imageSetVersion = ""
) => {
  let params = { datastoreId: datastoreId, imageSetId: imageSetId };
  if (imageSetVersion !== "") {
    params.imageSetVersion = imageSetVersion;
  }
  const response = await medicalImagingClient.send(
    new GetImageSetCommand(params)
  );
  console.log(response);
  // {
  //     '$metadata': {
```

```
  //     httpStatusCode: 200,
  //         requestId: '0615c161-410d-4d06-9d8c-6e1241bb0a5a',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     createdAt: 2023-09-22T14:49:26.427Z,
  //     datastoreId: 'xxxxxxxxxxxxxx',
  //     imageSetArn: 'arn:aws:medical-imaging:us-east-1:xxxxxxxxxx:datastore/
xxxxxxxxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxxxxx',
  //     imageSetId: 'xxxxxxxxxxxxxx',
  //     imageSetState: 'ACTIVE',
  //     imageSetWorkflowStatus: 'CREATED',
  //     updatedAt: 2023-09-22T14:49:26.427Z,
  //     versionId: '1'
  // }

  return response;
};
```

- Para obter detalhes da API, consulte GetImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def get_image_set(self, datastore_id, image_set_id, version_id=None):
        """
        Get the properties of an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
```

```
        :param version_id: The optional version of the image set.
        :return: The image set properties.
        """
        try:
            if version_id:
                image_set = self.health_imaging_client.get_image_set(
                    imageSetId=image_set_id,
                    datastoreId=datastore_id,
                    versionId=version_id,
                )
            else:
                image_set = self.health_imaging_client.get_image_set(
                    imageSetId=image_set_id, datastoreId=datastore_id
                )
        except ClientError as err:
            logger.error(
                "Couldn't get image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return image_set
```

- Para obter detalhes da API, consulte a GetImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha propriedades do trabalho de importação usando um SDK da AWS

Os exemplos de código a seguir mostram como obter as propriedades do trabalho de importação.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

```
//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
                                           const Aws::String &importJobID,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome;
}
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para obter as propriedades de um trabalho de importação dicom

O exemplo de código `get-dicom-import-job` a seguir obtém as propriedades de um trabalho de importação dicom.

```
aws medical-imaging get-dicom-import-job \
    --datastore-id "12345678901234567890123456789012" \
    --job-id "09876543210987654321098765432109"
```

Saída:

```
{
    "jobProperties": {
        "jobId": "09876543210987654321098765432109",
        "jobName": "my-job",
        "jobStatus": "COMPLETED",
        "datastoreId": "12345678901234567890123456789012",
        "dataAccessRoleArn": "arn:aws:iam::123456789012:role/
ImportJobDataAccessRole",
        "endedAt": "2022-08-12T11:29:42.285000+00:00",
        "submittedAt": "2022-08-12T11:28:11.152000+00:00",
        "inputS3Uri": "s3://medical-imaging-dicom-input/dicom_input/",
        "outputS3Uri": "s3://medical-imaging-output/
job_output/12345678901234567890123456789012-
DicomImport-09876543210987654321098765432109/"
    }
}
```

Para obter mais informações, consulte Obter propriedades do trabalho de importação no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência de AWS CLIComandos.

Java

SDK para Java 2.x

```
   public static DICOMImportJobProperties getDicomImportJob(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String jobId) {

       try {
           GetDicomImportJobRequest getDicomImportJobRequest =
GetDicomImportJobRequest.builder()
                   .datastoreId(datastoreId)
                   .jobId(jobId)
                   .build();
           GetDicomImportJobResponse response =
medicalImagingClient.getDICOMImportJob(getDicomImportJobRequest);
           return response.jobProperties();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { GetDICOMImportJobCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";
```

```
/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} jobId - The ID of the import job.
 */
export const getDICOMImportJob = async (
  datastoreId = "xxxxxxxxxxxxxxxxxxxx",
  jobId = "xxxxxxxxxxxxxxxxxxxx"
) => {
  const response = await medicalImagingClient.send(
    new GetDICOMImportJobCommand({ datastoreId: datastoreId, jobId: jobId })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: 'a2637936-78ea-44e7-98b8-7a87d95dfaee',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     jobProperties: {
  //         dataAccessRoleArn: 'arn:aws:iam::xxxxxxxxxxxx:role/dicom_import',
  //             datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxx',
  //             endedAt: 2023-09-19T17:29:21.753Z,
  //             inputS3Uri: 's3://healthimaging-source/CTStudy/',
  //             jobId: ''xxxxxxxxxxxxxxxxxxxxxxxx'',
  //             jobName: 'job_1',
  //             jobStatus: 'COMPLETED',
  //             outputS3Uri: 's3://health-imaging-dest/
ouput_ct/'xxxxxxxxxxxxxxxxxxxxxxxx'-DicomImport-'xxxxxxxxxxxxxxxxxxxxxxxx'/',
  //             submittedAt: 2023-09-19T17:27:25.143Z
  //     }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
def get_dicom_import_job(self, datastore_id, job_id):
    """
    Get the properties of a DICOM import job.

    :param datastore_id: The ID of the data store.
    :param job_id: The ID of the job.
    :return: The job properties.
    """
    try:
        job = self.health_imaging_client.get_dicom_import_job(
            jobId=job_id, datastoreId=datastore_id
        )
    except ClientError as err:
        logger.error(
            "Couldn't get DICOM import job. Here's why: %s: %s",
            err.response["Error"]["Code"],
            err.response["Error"]["Message"],
        )
        raise
    else:
        return job["jobProperties"]
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha metadados para um conjunto de HealthImaging imagens usando um SDK AWS

Os exemplos de código a seguir mostram como obter metadados para um conjunto de HealthImaging imagens.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

Função de utilitário para obter metadados do conjunto de imagens.

```
//! Routine which gets a HealthImaging image set's metadata.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped
 json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String
 &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
```

```
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Obtenha metadados do conjunto de imagens sem versão.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 "", outputFilePath, clientConfig))
        {
            std::cout << "Successfully retrieved image set metadata." <<
 std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

Obtenha metadados do conjunto de imagens com versão.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 versionID, outputFilePath, clientConfig))
        {
            std::cout << "Successfully retrieved image set metadata." <<
 std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Exemplo 1: para obter os metadados de um conjunto de imagens sem versão

O exemplo de código `get-image-set-metadata` a seguir obtém metadados para um conjunto de imagens sem especificar uma versão.

Observação: `outfile` é um parâmetro obrigatório

```
aws medical-imaging get-image-set-metadata \
    --datastore-id 12345678901234567890123456789012 \
    --image-set-id ea92b0d8838c72a3f25d00d13616f87e \
    studymetadata.json.gz
```

Os metadados retornados são compactados com o gzip e armazenados no arquivo studymetadata.json.gz. Para visualizar o conteúdo do objeto JSON retornado, você deve primeiro descompactá-lo.

Saída:

```
{
    "contentType": "application/json",
    "contentEncoding": "gzip"
}
```

Exemplo 2: para obter os metadados de um conjunto de imagens com versão

O exemplo de código `get-image-set-metadata` a seguir obtém metadados para um conjunto de imagens com uma versão especificada.

Observação: `outfile` é um parâmetro obrigatório

```
aws medical-imaging get-image-set-metadata \
    --datastore-id 12345678901234567890123456789012 \
```

```
    --image-set-id ea92b0d8838c72a3f25d00d13616f87e \
    --version-id 1 \
    studymetadata.json.gz
```

Os metadados retornados são compactados com o gzip e armazenados no arquivo studymetadata.json.gz. Para visualizar o conteúdo do objeto JSON retornado, você deve primeiro descompactá-lo.

Saída:

```
{
    "contentType": "application/json",
    "contentEncoding": "gzip"
}
```

Para obter mais informações, consulte Como obter metadados do conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte GetImageSetMetadataem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static void getMedicalImageSetMetadata(MedicalImagingClient
medicalImagingClient,
           String destinationPath,
           String datastoreId,
           String imagesetId,
           String versionId) {

       try {
           GetImageSetMetadataRequest.Builder getImageSetMetadataRequestBuilder
= GetImageSetMetadataRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId);

           if (versionId != null) {
               getImageSetMetadataRequestBuilder =
getImageSetMetadataRequestBuilder.versionId(versionId);
           }
```

```
medicalImagingClient.getImageSetMetadata(getImageSetMetadataRequestBuilder.build(),
                    FileSystems.getDefault().getPath(destinationPath));

            System.out.println("Metadata downloaded to " + destinationPath);
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

Função de utilitário para obter metadados do conjunto de imagens.

```
import { GetImageSetMetadataCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";
import { writeFileSync } from "fs";

/**
 * @param {string} metadataFileName - The name of the file for the gzipped
 metadata.
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imagesetId - The ID of the image set.
 * @param {string} versionID - The optional version ID of the image set.
 */
export const getImageSetMetadata = async (
  metadataFileName = "metadata.json.gzip",
  datastoreId = "xxxxxxxxxxxxxx",
```

```
  imagesetId = "xxxxxxxxxxxxxx",
  versionID = ""
) => {
  const params = { datastoreId: datastoreId, imageSetId: imagesetId };

  if (versionID) {
    params.versionID = versionID;
  }

  const response = await medicalImagingClient.send(
    new GetImageSetMetadataCommand(params)
  );
  const buffer = await response.imageSetMetadataBlob.transformToByteArray();
  writeFileSync(metadataFileName, buffer);

  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '5219b274-30ff-4986-8cab-48753de3a599',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     contentType: 'application/json',
  //     contentEncoding: 'gzip',
  //     imageSetMetadataBlob: <ref *1> IncomingMessage {}
  // }

  return response;
};
```

Obtenha metadados do conjunto de imagens sem versão.

```
  try {
    await getImageSetMetadata(
      "metadata.json.gzip",
      "12345678901234567890123456789012",
      "12345678901234567890123456789012"
    );
```

```
} catch (err) {
  console.log("Error", err);
}
```

Obtenha metadados do conjunto de imagens com versão.

```
try {
  await getImageSetMetadata(
    "metadata2.json.gzip",
    "12345678901234567890123456789012",
    "12345678901234567890123456789012",
    "1"
  );
} catch (err) {
  console.log("Error", err);
}
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

Função de utilitário para obter metadados do conjunto de imagens.

```
def get_image_set_metadata(
    self, metadata_file, datastore_id, image_set_id, version_id=None
):
    """
    Get the metadata of an image set.

    :param metadata_file: The file to store the JSON gzipped metadata.
```

```
        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The version of the image set.
        """
        try:
            if version_id:
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id,
                    datastoreId=datastore_id,
                    versionId=version_id,
                )
            else:

                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id, datastoreId=datastore_id
                )
            print(image_set_metadata)
            with open(metadata_file, "wb") as f:
                for chunk in
image_set_metadata["imageSetMetadataBlob"].iter_chunks():
                    if chunk:
                        f.write(chunk)

        except ClientError as err:
            logger.error(
                "Couldn't get image metadata. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Obtenha metadados do conjunto de imagens sem versão.

```
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id, datastoreId=datastore_id
                )
```

Obtenha metadados do conjunto de imagens com versão.

```
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id,
                    datastoreId=datastore_id,
                    versionId=version_id,
                )
```

- Para obter detalhes da API, consulte a GetImageSetMetadataReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe dados em massa para um armazenamento HealthImaging de dados usando um AWS SDK

Os exemplos de código a seguir mostram como importar dados em massa para um armazenamento HealthImaging de dados.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

```
//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
```

```
  \param inputDirectory: The directory in the S3 bucket containing the DICOM
 files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory +
 "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for C++ Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para iniciar um trabalho de importação dicom

O exemplo de código `start-dicom-import-job` a seguir inicia um trabalho de importação dicom.

```
aws medical-imaging start-dicom-import-job \
    --job-name "my-job" \
    --datastore-id "12345678901234567890123456789012" \
    --input-s3-uri "s3://medical-imaging-dicom-input/dicom_input/" \
    --output-s3-uri "s3://medical-imaging-output/job_output/" \
    --data-access-role-arn "arn:aws:iam::123456789012:role/
ImportJobDataAccessRole"
```

Saída:

```
{
    "datastoreId": "12345678901234567890123456789012",
    "jobId": "09876543210987654321098765432109",
    "jobStatus": "SUBMITTED",
    "submittedAt": "2022-08-12T11:28:11.152000+00:00"
}
```

Para obter mais informações, consulte Iniciando um trabalho de importação no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS CLI Referência de Comandos.

Java

SDK para Java 2.x

```
   public static String startDicomImportJob(MedicalImagingClient
medicalImagingClient,
           String jobName,
           String datastoreId,
           String dataAccessRoleArn,
           String inputS3Uri,
           String outputS3Uri) {

       try {
           StartDicomImportJobRequest startDicomImportJobRequest =
StartDicomImportJobRequest.builder()
                   .jobName(jobName)
                   .datastoreId(datastoreId)
                   .dataAccessRoleArn(dataAccessRoleArn)
                   .inputS3Uri(inputS3Uri)
                   .outputS3Uri(outputS3Uri)
                   .build();
           StartDicomImportJobResponse response =
medicalImagingClient.startDICOMImportJob(startDicomImportJobRequest);
           return response.jobId();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return "";
   }
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for Java 2.x Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { StartDICOMImportJobCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} jobName - The name of the import job.
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} dataAccessRoleArn - The Amazon Resource Name (ARN) of the role
 that grants permission.
 * @param {string} inputS3Uri - The URI of the S3 bucket containing the input
 files.
 * @param {string} outputS3Uri - The URI of the S3 bucket where the output files
 are stored.
 */
export const startDicomImportJob = async (
  jobName = "test-1",
  datastoreId = "12345678901234567890123456789012",
  dataAccessRoleArn = "arn:aws:iam::xxxxxxxxxxxx:role/ImportJobDataAccessRole",
  inputS3Uri = "s3://medical-imaging-dicom-input/dicom_input/",
  outputS3Uri = "s3://medical-imaging-output/job_output/"
) => {
  const response = await medicalImagingClient.send(
    new StartDICOMImportJobCommand({
      jobName: jobName,
      datastoreId: datastoreId,
      dataAccessRoleArn: dataAccessRoleArn,
      inputS3Uri: inputS3Uri,
      outputS3Uri: outputS3Uri,
    })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '6e81d191-d46b-4e48-a08a-cdcc7e11eb79',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
```

```
  //     jobId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //     jobStatus: 'SUBMITTED',
  //     submittedAt: 2023-09-22T14:48:45.767Z
  // }
  return response;
};
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for JavaScript Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def start_dicom_import_job(
        self, job_name, datastore_id, role_arn, input_s3_uri, output_s3_uri
    ):
        """
        Start a DICOM import job.

        :param job_name: The name of the job.
        :param datastore_id: The ID of the data store.
        :param role_arn: The Amazon Resource Name (ARN) of the role to use for
the job.
        :param input_s3_uri: The S3 bucket input prefix path containing the DICOM
files.
        :param output_s3_uri: The S3 bucket output prefix path for the result.
        :return: The job ID.
        """
        try:
            job = self.health_imaging_client.start_dicom_import_job(
                jobName=job_name,
                datastoreId=datastore_id,
                dataAccessRoleArn=role_arn,
                inputS3Uri=input_s3_uri,
```

```
                outputS3Uri=output_s3_uri,
            )
        except ClientError as err:
            logger.error(
                "Couldn't start DICOM import job. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return job["jobId"]
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar armazenamentos de HealthImaging dados usando um AWS SDK

Os exemplos de código a seguir mostram como listar armazenamentos HealthImaging de dados.

Bash

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_list_datastores
```

```
#
# List the HealthImaging data stores in the account.
#
# Returns:
#       [[datastore_name, datastore_id, datastore_status]]
#    And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function imaging_list_datastores() {
  local option OPTARG # Required to use getopts command in a function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_list_datastores"
    echo "Lists the AWS HealthImaging data stores in the account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "h" option; do
    case "${option}" in
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  local response
  response=$(aws medical-imaging list-datastores \
    --output text \
    --query "datastoreSummaries[*][datastoreName, datastoreId, datastoreStatus]")
  error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-datastores operation failed.$response"
```

```
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListDatastoresem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Para listar armazenamentos de dados

O exemplo de código `list-datastores` a seguir lista os armazenamentos de dados disponíveis.

```
aws medical-imaging list-datastores
```

Saída:

```
{
    "datastoreSummaries": [
        {
            "datastoreId": "12345678901234567890123456789012",
            "datastoreName": "TestDatastore123",
            "datastoreStatus": "ACTIVE",
            "datastoreArn": "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012",
            "createdAt": "2022-11-15T23:33:09.643000+00:00",
            "updatedAt": "2022-11-15T23:33:09.643000+00:00"
        }
    ]
```

```
}
```

Para obter mais informações, consulte Listar armazenamentos de dados no Guia do AWS HealthImaging Desenvolvedor.

- Para obter detalhes da API, consulte ListDatastoresem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static List<DatastoreSummary>
listMedicalImagingDatastores(MedicalImagingClient medicalImagingClient) {
       try {
           ListDatastoresRequest datastoreRequest =
ListDatastoresRequest.builder()
                   .build();
           ListDatastoresIterable responses =
medicalImagingClient.listDatastoresPaginator(datastoreRequest);
           List<DatastoreSummary> datastoreSummaries = new ArrayList<>();

           responses.stream().forEach(response ->
datastoreSummaries.addAll(response.datastoreSummaries()));

           return datastoreSummaries;
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { paginateListDatastores } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

export const listDatastores = async () => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };

  const commandParams = {};
  const paginator = paginateListDatastores(paginatorConfig, commandParams);

  /**
   * @type {import("@aws-sdk/client-medical-imaging").DatastoreSummary[]}
   */
  const datastoreSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    datastoreSummaries.push(...page["datastoreSummaries"]);
    console.log(page);
  }
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: '6aa99231-d9c2-4716-a46e-edb830116fa3',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //   },
  //   datastoreSummaries: [
  //     {
  //       createdAt: 2023-08-04T18:49:54.429Z,
  //       datastoreArn: 'arn:aws:medical-imaging:us-east-1:xxxxxxxxx:datastore/
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //       datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //       datastoreName: 'my_datastore',
  //       datastoreStatus: 'ACTIVE',
  //       updatedAt: 2023-08-04T18:49:54.429Z
```

```
  //     }
  //     ...
  //   ]
  // }

  return datastoreSummaries;
};
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def list_datastores(self):
        """
        List the data stores.

        :return: The list of data stores.
        """
        try:
            paginator =
self.health_imaging_client.get_paginator("list_datastores")
            page_iterator = paginator.paginate()
            datastore_summaries = []
            for page in page_iterator:
                datastore_summaries.extend(page["datastoreSummaries"])
        except ClientError as err:
            logger.error(
                "Couldn't list data stores. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return datastore_summaries
```

- Para obter detalhes da API, consulte a ListDatastoresReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar versões do conjunto de HealthImaging imagens usando um AWS SDK

Os exemplos de código a seguir mostram como listar as versões do conjunto de HealthImaging imagens.

CLI

AWS CLI

Para listar as versões de um conjunto de imagens

O exemplo de código `list-image-set-versions` a seguir lista o histórico de versões de um conjunto de imagens.

```
aws medical-imaging list-image-set-versions \
    --datastore-id 12345678901234567890123456789012 \
    --image-set-id ea92b0d8838c72a3f25d00d13616f87e
```

Saída:

```
{
    "imageSetPropertiesList": [
        {
            "ImageSetWorkflowStatus": "UPDATED",
            "versionId": "4",
            "updatedAt": 1680029436.304,
            "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
            "imageSetState": "ACTIVE",
```

```
            "createdAt": 1680027126.436
        },
        {
            "ImageSetWorkflowStatus": "UPDATED",
            "versionId": "3",
            "updatedAt": 1680029163.325,
            "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
            "imageSetState": "ACTIVE",
            "createdAt": 1680027126.436
        },
        {
            "ImageSetWorkflowStatus": "COPY_FAILED",
            "versionId": "2",
            "updatedAt": 1680027455.944,
            "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
            "imageSetState": "ACTIVE",
            "message": "INVALID_REQUEST:  Series of SourceImageSet and
 DestinationImageSet don't match.",
            "createdAt": 1680027126.436
        },
        {
            "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
            "imageSetState": "ACTIVE",
            "versionId": "1",
            "ImageSetWorkflowStatus": "COPIED",
            "createdAt": 1680027126.436
        }
    ]
}
```

Para obter mais informações, consulte Listar as versões do conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte ListImageSetVersionsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
    public static List<ImageSetProperties>
 listMedicalImageSetVersions(MedicalImagingClient medicalImagingClient,
            String datastoreId,
```

```
            String imagesetId) {
        try {
            ListImageSetVersionsRequest getImageSetRequest =
ListImageSetVersionsRequest.builder()
                    .datastoreId(datastoreId)
                    .imageSetId(imagesetId)
                    .build();

            ListImageSetVersionsIterable responses = medicalImagingClient
                    .listImageSetVersionsPaginator(getImageSetRequest);
            List<ImageSetProperties> imageSetProperties = new ArrayList<>();
            responses.stream().forEach(response ->
imageSetProperties.addAll(response.imageSetPropertiesList()));

            return imageSetProperties;
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }
```

- Para obter detalhes da API, consulte ListImageSetVersionsa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { paginateListImageSetVersions } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
```

```
 * @param {string} imageSetId - The ID of the image set.
 */
export const listImageSetVersions = async (
  datastoreId = "xxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxx"
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };

  const commandParams = { datastoreId, imageSetId };
  const paginator = paginateListImageSetVersions(
    paginatorConfig,
    commandParams
  );

  let imageSetPropertiesList = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    imageSetPropertiesList.push(...page["imageSetPropertiesList"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '74590b37-a002-4827-83f2-3c590279c742',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     imageSetPropertiesList: [
  //         {
  //             ImageSetWorkflowStatus: 'CREATED',
  //             createdAt: 2023-09-22T14:49:26.427Z,
  //             imageSetId: 'xxxxxxxxxxxxxxxxxxxxxx',
  //             imageSetState: 'ACTIVE',
  //             versionId: '1'
  //         }]
  // }
  return imageSetPropertiesList;
};
```

- Para obter detalhes da API, consulte ListImageSetVersionsa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def list_image_set_versions(self, datastore_id, image_set_id):
        """
        List the image set versions.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :return: The list of image set versions.
        """
        try:
            paginator = self.health_imaging_client.get_paginator(
                "list_image_set_versions"
            )
            page_iterator = paginator.paginate(
                imageSetId=image_set_id, datastoreId=datastore_id
            )
            image_set_properties_list = []
            for page in page_iterator:
                image_set_properties_list.extend(page["imageSetPropertiesList"])
        except ClientError as err:
            logger.error(
                "Couldn't list image set versions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return image_set_properties_list
```

- Para obter detalhes da API, consulte a ListImageSetVersionsReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar trabalhos de importação para um armazenamento HealthImaging de dados usando um AWS SDK

Os exemplos de código a seguir mostram como listar trabalhos de importação para um armazenamento HealthImaging de dados.

CLI

AWS CLI

Para listar trabalhos de importação dicom

O exemplo de código `list-dicom-import-jobs` a seguir lista os trabalhos de importação dicom.

```
aws medical-imaging list-dicom-import-jobs \
    --datastore-id "12345678901234567890123456789012"
```

Saída:

```
{
    "jobSummaries": [
        {
            "jobId": "09876543210987654321098765432109",
            "jobName": "my-job",
            "jobStatus": "COMPLETED",
            "datastoreId": "12345678901234567890123456789012",
            "dataAccessRoleArn": "arn:aws:iam::123456789012:role/
ImportJobDataAccessRole",
```

```
            "endedAt": "2022-08-12T11:21:56.504000+00:00",
            "submittedAt": "2022-08-12T11:20:21.734000+00:00"
        }
    ]
}
```

Para obter mais informações, consulte Listar trabalhos de importação no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência de AWS CLIComandos.

Java

SDK para Java 2.x

```
   public static List<DICOMImportJobSummary>
listDicomImportJobs(MedicalImagingClient medicalImagingClient,
           String datastoreId) {

       try {
           ListDicomImportJobsRequest listDicomImportJobsRequest =
ListDicomImportJobsRequest.builder()
                   .datastoreId(datastoreId)
                   .build();
           ListDicomImportJobsResponse response =
medicalImagingClient.listDICOMImportJobs(listDicomImportJobsRequest);
           return response.jobSummaries();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return new ArrayList<>();
   }
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { paginateListDICOMImportJobs } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 */
export const listDICOMImportJobs = async (
  datastoreId = "xxxxxxxxxxxxxxxxxx"
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };

  const commandParams = { datastoreId: datastoreId };
  const paginator = paginateListDICOMImportJobs(paginatorConfig, commandParams);

  let jobSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    jobSummaries.push(...page["jobSummaries"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '3c20c66e-0797-446a-a1d8-91b742fd15a0',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
```

```
  // },
  //     jobSummaries: [
  //         {
  //             dataAccessRoleArn: 'arn:aws:iam::xxxxxxxxxxxx:role/
dicom_import',
  //             datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxx',
  //             endedAt: 2023-09-22T14:49:51.351Z,
  //             jobId: 'xxxxxxxxxxxxxxxxxxxxxxxx',
  //             jobName: 'test-1',
  //             jobStatus: 'COMPLETED',
  //             submittedAt: 2023-09-22T14:48:45.767Z
  // }
  // ]}

  return jobSummaries;
};
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def list_dicom_import_jobs(self, datastore_id):
        """
        List the DICOM import jobs.

        :param datastore_id: The ID of the data store.
        :return: The list of jobs.
        """
        try:
            paginator = self.health_imaging_client.get_paginator(
                "list_dicom_import_jobs"
            )
```

```
            page_iterator = paginator.paginate(datastoreId=datastore_id)
            job_summaries = []
            for page in page_iterator:
                job_summaries.extend(page["jobSummaries"])
        except ClientError as err:
            logger.error(
                "Couldn't list DICOM import jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return job_summaries
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar tags para um HealthImaging recurso usando um AWS SDK

Os exemplos de código a seguir mostram como listar tags para um HealthImaging recurso.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Marcar um datastore
- Marcar um conjunto de imagens

CLI

AWS CLI

Exemplo 1: para listar as tags de recurso de um armazenamento de dados

O exemplo de código `list-tags-for-resource` a seguir lista as tags de um armazenamento de dados.

```
aws medical-imaging list-tags-for-resource \
    --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"
```

Saída:

```
{
    "tags":{
        "Deployment":"Development"
    }
}
```

Exemplo 2: para listar tags de recurso de um conjunto de imagens

O exemplo de código `list-tags-for-resource` a seguir lista as tags de um conjunto de imagens.

```
aws medical-imaging list-tags-for-resource \
    --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/18f88ac7870584f58d56256646b4d92b"
```

Saída:

```
{
    "tags":{
        "Deployment":"Development"
    }
}
```

Para obter mais informações, consulte Como marcar recursos AWS HealthImaging no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte ListTagsForResourceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
   public static ListTagsForResourceResponse
listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
           String resourceArn) {
       try {
           ListTagsForResourceRequest listTagsForResourceRequest =
ListTagsForResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .build();

           return
medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte ListTagsForResourceа Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
```

```
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/
ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte ListTagsForResourcea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def list_tags_for_resource(self, resource_arn):
        """
```

```
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

- Para obter detalhes da API, consulte a ListTagsForResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover uma tag de um HealthImaging recurso usando um AWS SDK

Os exemplos de código a seguir mostram como remover uma tag de um HealthImaging recurso.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Marcar um datastore
- Marcar um conjunto de imagens

CLI

AWS CLI

Exemplo 1: para desmarcar um armazenamento de dados

O exemplo de código `untag-resource` a seguir desmarca um armazenamento de dados.

```
aws medical-imaging untag-resource \
    --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012" \
    --tag-keys '["Deployment"]'
```

Este comando não produz saída.

Exemplo 2: para desmarcar um conjunto de imagens

O exemplo de código `untag-resource` a seguir desmarca um conjunto de imagens.

```
aws medical-imaging untag-resource \
    --resource-arn "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/18f88ac7870584f58d56256646b4d92b" \
    --tag-keys '["Deployment"]'
```

Este comando não produz saída.

Para obter mais informações, consulte Como marcar recursos AWS HealthImaging no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte UntagResourceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
    public static void untagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Collection<String> tagKeys) {
        try {
```

```
            UntagResourceRequest untagResourceRequest =
 UntagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tagKeys(tagKeys)
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte UntagResourcea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tagKeys = []
) => {
```

```
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte UntagResourcea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
```

```
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a UntagResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Pesquise conjuntos de HealthImaging imagens usando um AWS SDK

Os exemplos de código a seguir mostram como pesquisar conjuntos de HealthImaging imagens.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar conjuntos de imagens e quadros de imagem

C++

SDK for C++

A função de utilitário para pesquisar conjuntos de imagens.

```
//! Routine which searches for image sets based on defined input attributes.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param searchCriteria: A search criteria instance.
  \param imageSetResults: Vector to receive the image set IDs.
  \param clientConfig: Aws client configuration.
```

```
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::searchImageSets(
        const Aws::String &dataStoreID,
        const Aws::MedicalImaging::Model::SearchCriteria &searchCriteria,
        Aws::Vector<Aws::String> &imageSetResults,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::SearchImageSetsRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetSearchCriteria(searchCriteria);

    Aws::String nextToken; // Used for paginated results.
    bool result = true;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::MedicalImaging::Model::SearchImageSetsOutcome outcome =
 client.SearchImageSets(
                request);
        if (outcome.IsSuccess()) {
            for (auto &imageSetMetadataSummary:
 outcome.GetResult().GetImageSetsMetadataSummaries()) {

 imageSetResults.push_back(imageSetMetadataSummary.GetImageSetId());
            }

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error: " << outcome.GetError().GetMessage() <<
 std::endl;
            result = false;
        }
    } while (!nextToken.empty());

    return result;
}
```

Caso de uso nº 1: operador EQUAL.

```
        Aws::Vector<Aws::String> imageIDsForPatientID;
        Aws::MedicalImaging::Model::SearchCriteria searchCriteriaEqualsPatientID;
        Aws::Vector<Aws::MedicalImaging::Model::SearchFilter>
 patientIDSearchFilters = {

 Aws::MedicalImaging::Model::SearchFilter().WithOperator(Aws::MedicalImaging::Model::Oper

 .WithValues({Aws::MedicalImaging::Model::SearchByAttributeValue().WithDICOMPatientId(pat
        };
        searchCriteriaEqualsPatientID.SetFilters(patientIDSearchFilters);
        bool result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
 searchCriteriaEqualsPatientID, imageIDsForPatientID,
                                                                  clientConfig);
        if (result) {
            std::cout << imageIDsForPatientID.size() << " image sets found for
 the patient with ID '"
            <<  patientID << "'." << std::endl;
            for (auto &imageSetResult : imageIDsForPatientID) {
                std::cout << "  Image set with ID '" << imageSetResult <<
 std::endl;
            }
        }
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
         Aws::MedicalImaging::Model::SearchByAttributeValue useCase2StartDate;

 useCase2StartDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAnd
        .WithDICOMStudyDate("19990101")
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchByAttributeValue useCase2EndDate;

 useCase2EndDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAndTi

 .WithDICOMStudyDate(Aws::Utils::DateTime(std::chrono::system_clock::now()).ToLocalTimeSt
%m%d"))
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchFilter useCase2SearchFilter;
        useCase2SearchFilter.SetValues({useCase2StartDate, useCase2EndDate});
```

```
useCase2SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

       Aws::MedicalImaging::Model::SearchCriteria useCase2SearchCriteria;
       useCase2SearchCriteria.SetFilters({useCase2SearchFilter});

       Aws::Vector<Aws::String> usesCase2Results;
       result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
useCase2SearchCriteria, usesCase2Results,
                                                                 clientConfig);
       if (result) {
           std::cout << usesCase2Results.size() << " image sets found for
between 1999/01/01 and present."
                     <<  std::endl;
           for (auto &imageSetResult : usesCase2Results) {
               std::cout << "  Image set with ID '" << imageSetResult <<
std::endl;
           }
       }
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
       Aws::MedicalImaging::Model::SearchByAttributeValue useCase3StartDate;

useCase3StartDate.SetCreatedAt(Aws::Utils::DateTime("20231130T000000000Z",Aws::Utils::Da

       Aws::MedicalImaging::Model::SearchByAttributeValue useCase3EndDate;

useCase3EndDate.SetCreatedAt(Aws::Utils::DateTime(std::chrono::system_clock::now()));

       Aws::MedicalImaging::Model::SearchFilter useCase3SearchFilter;
       useCase3SearchFilter.SetValues({useCase3StartDate, useCase3EndDate});

useCase3SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

       Aws::MedicalImaging::Model::SearchCriteria useCase3SearchCriteria;
       useCase3SearchCriteria.SetFilters({useCase3SearchFilter});

       Aws::Vector<Aws::String> usesCase3Results;
       result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
useCase3SearchCriteria, usesCase3Results,
```

```
                                                                clientConfig);
        if (result) {
            std::cout << usesCase3Results.size() << " image sets found for
created between 2023/11/30 and present."
                      <<  std::endl;
            for (auto &imageSetResult : usesCase3Results) {
                std::cout << "  Image set with ID '" << imageSetResult <<
std::endl;
            }
        }
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

CLI

AWS CLI

Exemplo 1: para pesquisar conjuntos de imagens com um operador EQUAL

O exemplo de código `search-image-sets` a seguir usa o operador EQUAL para pesquisar conjuntos de imagens com base em um valor específico.

```
aws medical-imaging search-image-sets \
    --datastore-id 12345678901234567890123456789012 \
    --search-criteria file://search-criteria.json
```

Conteúdo de `search-criteria.json`

```
{
    "filters": [{
        "values": [{"DICOMPatientId" : "SUBJECT08701"}],
        "operator": "EQUAL"
    }]
```

```
}
```

Saída:

```
{
    "imageSetsMetadataSummaries": [{
        "imageSetId": "09876543210987654321098765432109",
        "createdAt": "2022-12-06T21:40:59.429000+00:00",
        "version": 1,
        "DICOMTags": {
            "DICOMStudyId": "2011201407",
            "DICOMStudyDate": "19991122",
             "DICOMPatientSex": "F",
             "DICOMStudyInstanceUID": "1.2.840.99999999.84710745.943275268089",
             "DICOMPatientBirthDate": "19201120",
             "DICOMStudyDescription": "UNKNOWN",
             "DICOMPatientId": "SUBJECT08701",
             "DICOMPatientName": "Melissa844 Huel628",
             "DICOMNumberOfStudyRelatedInstances": 1,
             "DICOMStudyTime": "140728",
             "DICOMNumberOfStudyRelatedSeries": 1
            },
        "updatedAt": "2022-12-06T21:40:59.429000+00:00"
    }]
}
```

Exemplo 2: Para pesquisar conjuntos de imagens com um operador BETWEEN usando DICOM StudyDate e DICOM StudyTime

O exemplo de código `search-image-sets` a seguir pesquisa conjuntos de imagens com estudos DICOM gerados entre 1º de janeiro de 1990 (00h) e 1º de janeiro de 2023 (00h).

Nota: O DICOM StudyTime é opcional. Se não estiver presente, 00h (início do dia) é o valor da hora para as datas fornecidas para filtragem.

```
aws medical-imaging search-image-sets \
    --datastore-id 12345678901234567890123456789012 \
    --search-criteria file://search-criteria.json
```

Conteúdo de `search-criteria.json`

```
{
```

```
    "filters": [{
        "values": [{
            "DICOMStudyDateAndTime": {
                "DICOMStudyDate": "19900101",
                "DICOMStudyTime": "000000"
            }
        },
        {
            "DICOMStudyDateAndTime": {
                "DICOMStudyDate": "20230101",
                "DICOMStudyTime": "000000"
            }
        }],
        "operator": "BETWEEN"
    }]
}
```

Saída:

```
{
    "imageSetsMetadataSummaries": [{
        "imageSetId": "09876543210987654321098765432109",
        "createdAt": "2022-12-06T21:40:59.429000+00:00",
        "version": 1,
        "DICOMTags": {
            "DICOMStudyId": "2011201407",
            "DICOMStudyDate": "19991122",
            "DICOMPatientSex": "F",
            "DICOMStudyInstanceUID": "1.2.840.99999999.84710745.943275268089",
            "DICOMPatientBirthDate": "19201120",
            "DICOMStudyDescription": "UNKNOWN",
            "DICOMPatientId": "SUBJECT08701",
            "DICOMPatientName": "Melissa844 Huel628",
            "DICOMNumberOfStudyRelatedInstances": 1,
            "DICOMStudyTime": "140728",
            "DICOMNumberOfStudyRelatedSeries": 1
        },
        "updatedAt": "2022-12-06T21:40:59.429000+00:00"
    }]
}
```

Exemplo 3: para pesquisar conjuntos de imagens com um operador BETWEEN usando createdAt (os estudos de tempo persistiam anteriormente)

O exemplo de `search-image-sets` código a seguir pesquisa conjuntos de imagens com estudos DICOM persistentes HealthImaging entre os intervalos de tempo no fuso horário UTC.

Observação: forneça createdAt no formato do exemplo ("1985-04-12T23:20:50.52Z").

```
aws medical-imaging search-image-sets \
    --datastore-id 12345678901234567890123456789012 \
    --search-criteria  file://search-criteria.json
```

Conteúdo de `search-criteria.json`

```
{
    "filters": [{
        "values": [{
            "createdAt": "1985-04-12T23:20:50.52Z"
        },
        {
            "createdAt": "2022-04-12T23:20:50.52Z"
        }],
        "operator": "BETWEEN"
    }]
}
```

Saída:

```
{
    "imageSetsMetadataSummaries": [{
        "imageSetId": "09876543210987654321098765432109",
        "createdAt": "2022-12-06T21:40:59.429000+00:00",
        "version": 1,
        "DICOMTags": {
            "DICOMStudyId": "2011201407",
            "DICOMStudyDate": "19991122",
            "DICOMPatientSex": "F",
            "DICOMStudyInstanceUID": "1.2.840.99999999.84710745.943275268089",
            "DICOMPatientBirthDate": "19201120",
            "DICOMStudyDescription": "UNKNOWN",
            "DICOMPatientId": "SUBJECT08701",
            "DICOMPatientName": "Melissa844 Huel628",
            "DICOMNumberOfStudyRelatedInstances": 1,
            "DICOMStudyTime": "140728",
            "DICOMNumberOfStudyRelatedSeries": 1
```

```
        },
        "lastUpdatedAt": "2022-12-06T21:40:59.429000+00:00"
    }]
}
```

Para obter mais informações, consulte Pesquisar conjuntos de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte SearchImageSetsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

A função de utilitário para pesquisar conjuntos de imagens.

```
        public static List<ImageSetsMetadataSummary>
searchMedicalImagingImageSets(
                        MedicalImagingClient medicalImagingClient,
                        String datastoreId, List<SearchFilter> searchFilters) {
                try {
                        SearchImageSetsRequest datastoreRequest =
SearchImageSetsRequest.builder()
                                        .datastoreId(datastoreId)

.searchCriteria(SearchCriteria.builder().filters(searchFilters).build())
                                        .build();
                        SearchImageSetsIterable responses = medicalImagingClient

.searchImageSetsPaginator(datastoreRequest);
                        List<ImageSetsMetadataSummary> imageSetsMetadataSummaries
= new ArrayList<>();

                        responses.stream().forEach(response ->
imageSetsMetadataSummaries

.addAll(response.imageSetsMetadataSummaries()));

                        return imageSetsMetadataSummaries;
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
```

```
                }

                return null;
        }
```

Caso de uso nº 1: operador EQUAL.

```
                List<SearchFilter> searchFilters =
Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.EQUAL)
                                .values(SearchByAttributeValue.builder()
                                                .dicomPatientId(patientId)
                                                .build())
                                .build());

                List<ImageSetsMetadataSummary> imageSetsMetadataSummaries =
searchMedicalImagingImageSets(
                                medicalImagingClient,
                                datastoreId, searchFilters);
                if (imageSetsMetadataSummaries != null) {
                        System.out.println("The image sets for patient " +
patientId + " are:\n"
                                        + imageSetsMetadataSummaries);
                        System.out.println();
                }
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
                DateTimeFormatter formatter =
DateTimeFormatter.ofPattern("yyyyMMdd");
                searchFilters = Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.BETWEEN)
                                .values(SearchByAttributeValue.builder()

.dicomStudyDateAndTime(DICOMStudyDateAndTime.builder()

.dicomStudyDate("19990101")

.dicomStudyTime("000000.000")
                                                                .build())
                                                .build(),
```

```
                                                        SearchByAttributeValue.builder()

.dicomStudyDateAndTime(DICOMStudyDateAndTime.builder()

.dicomStudyDate((LocalDate.now()

              .format(formatter)))

.dicomStudyTime("000000.000")

.build())
                                                                    .build())
                                .build());

               imageSetsMetadataSummaries =
searchMedicalImagingImageSets(medicalImagingClient,
                                datastoreId, searchFilters);
               if (imageSetsMetadataSummaries != null) {
                       System.out.println(
                                       "The image sets searched with BETWEEN
operator using DICOMStudyDate and DICOMStudyTime are:\n"
                                                          +

imageSetsMetadataSummaries);
                       System.out.println();
               }
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
               searchFilters = Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.BETWEEN)
                                .values(SearchByAttributeValue.builder()

.createdAt(Instant.parse("1985-04-12T23:20:50.52Z"))
                                                        .build(),
                                                        SearchByAttributeValue.builder()

.createdAt(Instant.now())
                                                                    .build())
                                .build());
```

```
                imageSetsMetadataSummaries =
 searchMedicalImagingImageSets(medicalImagingClient,
                                datastoreId, searchFilters);
                if (imageSetsMetadataSummaries != null) {
                        System.out.println("The image sets searched with BETWEEN
 operator using createdAt are:\n "
                                        + imageSetsMetadataSummaries);
                        System.out.println();
                }
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

A função de utilitário para pesquisar conjuntos de imagens.

```
import { paginateSearchImageSets } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The data store's ID.
 * @param { import('@aws-sdk/client-medical-imaging').SearchFilter[] } filters -
 The search criteria filters.
 */
export const searchImageSets = async (
  datastoreId = "xxxxxxxx",
  filters = []
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };
```

```
  const commandParams = {
    datastoreId: datastoreId,
    searchCriteria: {
      filters,
    },
  };

  const paginator = paginateSearchImageSets(paginatorConfig, commandParams);

  const imageSetsMetadataSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    imageSetsMetadataSummaries.push(...page["imageSetsMetadataSummaries"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'f009ea9c-84ca-4749-b5b6-7164f00a5ada',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     imageSetsMetadataSummaries: [
  //         {
  //             DICOMTags: [Object],
  //             createdAt: "2023-09-19T16:59:40.551Z",
  //             imageSetId: '7f75e1b5c0f40eac2b24cf712f485f50',
  //             updatedAt: "2023-09-19T16:59:40.551Z",
  //             version: 1
  //         }]
  // }

  return imageSetsMetadataSummaries;
};
```

Caso de uso nº 1: operador EQUAL.

```
  const datastoreId = "12345678901234567890123456789012";
```

```
try {
  const filters = [
    {
      values: [{ DICOMPatientId: "9227465" }],
      operator: "EQUAL",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
}
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
const datastoreId = "12345678901234567890123456789012";

try {
  const filters = [
    {
      values: [
        {
          DICOMStudyDateAndTime: {
            DICOMStudyDate: "19900101",
            DICOMStudyTime: "000000",
          },
        },
        {
          DICOMStudyDateAndTime: {
            DICOMStudyDate: "20230901",
            DICOMStudyTime: "000000",
          },
        },
      ],
      operator: "BETWEEN",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
```

```
}
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
const datastoreId = "12345678901234567890123456789012";

try {
  const filters = [
    {
      values: [
        { createdAt: new Date("1985-04-12T23:20:50.52Z") },
        { createdAt: new Date("2023-09-12T23:20:50.52Z") },
      ],
      operator: "BETWEEN",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
}
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

A função de utilitário para pesquisar conjuntos de imagens.

```
    def search_image_sets(self, datastore_id, search_filter):
        """
```

```
        Search for image sets.

        :param datastore_id: The ID of the data store.
        :param search_filter: The search filter.
            For example: {"filters" : [{ "operator": "EQUAL", "values":
[{"DICOMPatientId": "3524578"}]}]}.
        :return: The list of image sets.
        """
        try:
            paginator =
self.health_imaging_client.get_paginator("search_image_sets")
            page_iterator = paginator.paginate(
                datastoreId=datastore_id, searchCriteria=search_filter
            )
            metadata_summaries = []
            for page in page_iterator:
                metadata_summaries.extend(page["imageSetsMetadataSummaries"])
        except ClientError as err:
            logger.error(
                "Couldn't search image sets. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return metadata_summaries
```

Caso de uso nº 1: operador EQUAL.

```
        filter = {
            "filters": [
                {"operator": "EQUAL", "values": [{"DICOMPatientId": "3524578"}]}
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
        filter = {
```

```
            "filters": [
                {
                    "operator": "BETWEEN",
                    "values": [
                        {
                            "DICOMStudyDateAndTime": {
                                "DICOMStudyDate": "19900101",
                                "DICOMStudyTime": "000000",
                            }
                        },
                        {
                            "DICOMStudyDateAndTime": {
                                "DICOMStudyDate": "20230101",
                                "DICOMStudyTime": "000000",
                            }
                        },
                    ],
                }
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
        filter = {
            "filters": [
                {
                    "values": [
                        {
                            "createdAt": datetime.datetime(
                                2021, 8, 4, 14, 49, 54, 429000
                            )
                        },
                        {
                            "createdAt": datetime.datetime.now()
                            + datetime.timedelta(days=1)
                        },
                    ],
                    "operator": "BETWEEN",
                }
```

```
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

- Para obter detalhes da API, consulte a SearchImageSetsReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize os metadados do conjunto de HealthImaging imagens usando um SDK AWS

Os exemplos de código a seguir mostram como atualizar os metadados do conjunto de HealthImaging imagens.

CLI

AWS CLI

Para atualizar metadados de um conjunto de imagens

O exemplo de código `update-image-set-metadata` a seguir atualiza os metadados de um conjunto de imagens.

```
aws medical-imaging update-image-set-metadata \
    --datastore-id 12345678901234567890123456789012 \
    --image-set-id ea92b0d8838c72a3f25d00d13616f87e \
    --latest-version-id 1 \
    --update-image-set-metadata-updates file://metadata-updates.json
```

Conteúdo de `metadata-updates.json`

```
{
    "DICOMUpdates": {
        "updatableAttributes":
 "eyJTY2hlbWFWZXJzaW9uIjoxLjEsIlBhdGllbnQiOnsiRElDT00iOnsiUGF0aWVudE5hbWUiOiJNWF5NWCJ9fX0
    }
```

```
}
```

Observação: `updatableAttributes` é uma string JSON codificada em Base64. Está é a string JSON não codificada.

{" SchemaVersion ":1.1, "Paciente": {"DICOM": {" PatientName ":"MX^MX"}}}

Saída:

```
{
    "latestVersionId": "5",
    "imageSetWorkflowStatus": "UPDATING",
    "updatedAt": 1680042257.908,
    "imageSetId": "ea92b0d8838c72a3f25d00d13616f87e",
    "imageSetState": "LOCKED",
    "createdAt": 1680027126.436,
    "datastoreId": "12345678901234567890123456789012"
}
```

Para obter mais informações, consulte Atualização dos metadados do conjunto de imagens no Guia do AWS HealthImaging desenvolvedor.

- Para obter detalhes da API, consulte UpdateImageSetMetadataem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

```
        public static void updateMedicalImageSetMetadata(MedicalImagingClient
 medicalImagingClient,
                        String datastoreId,
                        String imagesetId,
                        String versionId,
                        MetadataUpdates metadataUpdates) {
                try {
                        UpdateImageSetMetadataRequest
 updateImageSetMetadataRequest = UpdateImageSetMetadataRequest
                                        .builder()
                                        .datastoreId(datastoreId)
                                        .imageSetId(imagesetId)
                                        .latestVersionId(versionId)
```

```
 .updateImageSetMetadataUpdates(metadataUpdates)
                                        .build();


 medicalImagingClient.updateImageSetMetadata(updateImageSetMetadataRequest);

                        System.out.println("The image set metadata was updated");
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
```

- Para obter detalhes da API, consulte UpdateImageSetMetadataa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

```
import {UpdateImageSetMetadataCommand} from "@aws-sdk/client-medical-imaging";
import {medicalImagingClient} from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the HealthImaging data store.
 * @param {string} imageSetId - The ID of the HealthImaging image set.
 * @param {string} latestVersionId - The ID of the HealthImaging image set
 version.
 * @param {{}} updateMetadata - The metadata to update.
 */
export const updateImageSetMetadata = async (datastoreId = "xxxxxxxxxx",
                                             imageSetId = "xxxxxxxxxx",
                                             latestVersionId = "1",
                                             updateMetadata = '{}') => {
```

```
    const response = await medicalImagingClient.send(
        new UpdateImageSetMetadataCommand({
            datastoreId: datastoreId,
            imageSetId: imageSetId,
            latestVersionId: latestVersionId,
            updateImageSetMetadataUpdates: updateMetadata
        })
    );
    console.log(response);
    // {
    //     '$metadata': {
    //     httpStatusCode: 200,
    //         requestId: '7966e869-e311-4bff-92ec-56a61d3003ea',
    //         extendedRequestId: undefined,
    //         cfId: undefined,
    //         attempts: 1,
    //         totalRetryDelay: 0
    // },
    //     createdAt: 2023-09-22T14:49:26.427Z,
    //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
    //     imageSetId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
    //     imageSetState: 'LOCKED',
    //     imageSetWorkflowStatus: 'UPDATING',
    //     latestVersionId: '4',
    //     updatedAt: 2023-09-27T19:41:43.494Z
    // }
    return response;
};
```

Codifique os metadados.

```
    const updatableAttributes =
JSON.stringify({
  "SchemaVersion": 1.1,
  "Patient": {
    "DICOM": {
      "PatientName": "Garcia^Gloria"
    }
  }
})

    const updateMetadata = {
```

```
        "DICOMUpdates": {
            "updatableAttributes":
                new TextEncoder().encode(updatableAttributes)
        }
    };

    await updateImageSetMetadata("12345678901234567890123456789012",
 "12345678901234567890123456789012",
        "1", updateMetadata);
```

- Para obter detalhes da API, consulte UpdateImageSetMetadataa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

```
    def update_image_set_metadata(
        self, datastore_id, image_set_id, version_id, metadata
    ):
        """
        Update the metadata of an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The ID of the image set version.
        :param metadata: The image set metadata as a dictionary.
            For example {"DICOMUpdates": {"updatableAttributes":
            "{\"SchemaVersion\":1.1,\"Patient\":{\"DICOM\":{\"PatientName\":
\"Garcia^Gloria\"}}}"}}
        :return: The updated image set metadata.
        """
        try:
            updated_metadata =
 self.health_imaging_client.update_image_set_metadata(
```

```
                imageSetId=image_set_id,
                datastoreId=datastore_id,
                latestVersionId=version_id,
                updateImageSetMetadataUpdates=metadata,
            )
        except ClientError as err:
            logger.error(
                "Couldn't update image set metadata. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return updated_metadata
```

- Para obter detalhes da API, consulte a UpdateImageSetMetadataReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cenários para HealthImaging usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS HealthImaging com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar conjuntos de HealthImaging imagens e molduras de imagem usando um AWS SDK
- Marcar um armazenamento HealthImaging de dados usando um SDK AWS
- Marcar um conjunto de HealthImaging imagens usando um SDK AWS

Comece a usar conjuntos de HealthImaging imagens e molduras de imagem usando um AWS SDK

O exemplo de código a seguir mostra como importar arquivos DICOM e baixar molduras de imagem em HealthImaging.

A implementação é estruturada como um aplicativo de linha de comando de fluxo de trabalho.

- Configurar recursos para uma importação DICOM.
- Importe arquivos DICOM para um armazenamento de dados.
- Recupere os IDs do conjunto de imagens para o trabalho de importação.
- Recupere os IDs do quadro de imagem para o conjunto de imagens.
- Baixe, decodifique e verifique os quadros de imagem.
- Limpe os recursos.

C++

SDK for C++

Crie uma AWS CloudFormation pilha com os recursos necessários.

```
    Aws::String inputBucketName;
    Aws::String outputBucketName;
    Aws::String dataStoreId;
    Aws::String roleArn;
    Aws::String stackName;

    if (askYesNoQuestion(
            "Would you like to let this workflow create the resources for you?
(y/n) ")) {
        stackName = askQuestion(
                "Enter a name for the AWS CloudFormation stack to create. ");
        Aws::String dataStoreName = askQuestion(
                "Enter a name for the HealthImaging datastore to create. ");

        Aws::Map<Aws::String, Aws::String> outputs = createCloudFormationStack(
                stackName,
                dataStoreName,
                clientConfiguration);
```

```
        if (!retrieveOutputs(outputs, dataStoreId, inputBucketName,
outputBucketName,
                             roleArn)) {
            return false;
        }

        std::cout << "The following resources have been created." << std::endl;
        std::cout << "A HealthImaging datastore with ID: " << dataStoreId << "."
                  << std::endl;
        std::cout << "An Amazon S3 input bucket named: " << inputBucketName <<
"."
                  << std::endl;
        std::cout << "An Amazon S3 output bucket named: " << outputBucketName <<
"."
                  << std::endl;
        std::cout << "An IAM role with the ARN: " << roleArn << "." << std::endl;
        askQuestion("Enter return to continue.", alwaysTrueTest);
    }
    else {
        std::cout << "You have chosen to use preexisting resources:" <<
std::endl;
        dataStoreId = askQuestion(
                "Enter the data store ID of the HealthImaging datastore you wish
to use: ");
        inputBucketName = askQuestion(
                "Enter the name of the S3 input bucket you wish to use: ");
        outputBucketName = askQuestion(
                "Enter the name of the S3 output bucket you wish to use: ");
        roleArn = askQuestion(
                "Enter the ARN for the IAM role with the proper permissions to
import a DICOM series: ");
    }
```

Copie arquivos DICOM para o bucket de importação do Amazon S3.

```
    std::cout
            << "This workflow uses DICOM files from the National Cancer Institute
Imaging Data\n"
            << "Commons (IDC) Collections." << std::endl;
    std::cout << "Here is the link to their website." << std::endl;
    std::cout << "https://registry.opendata.aws/nci-imaging-data-commons/" <<
std::endl;
```

```
   std::cout << "We will use DICOM files stored in an S3 bucket managed by the
IDC."
             << std::endl;
   std::cout
           << "First one of the DICOM folders in the IDC collection must be
copied to your\n"
              "input S3 bucket."
           << std::endl;
   std::cout << "You have the choice of one of the following "
             << IDC_ImageChoices.size() << " folders to copy." << std::endl;

   int index = 1;
   for (auto &idcChoice: IDC_ImageChoices) {
       std::cout << index << " - " << idcChoice.mDescription << std::endl;
       index++;
   }
   int choice = askQuestionForIntRange("Choose DICOM files to import: ", 1, 4);

   Aws::String fromDirectory = IDC_ImageChoices[choice - 1].mDirectory;
   Aws::String inputDirectory = "input";

   std::cout << "The files in the directory '" << fromDirectory << "' in the
bucket '"
             << IDC_S3_BucketName << "' will be copied " << std::endl;
   std::cout << "to the folder '" << inputDirectory << "/" << fromDirectory
             << "' in the bucket '" << inputBucketName << "'." << std::endl;
   askQuestion("Enter return to start the copy.", alwaysTrueTest);

   if (!AwsDoc::Medical_Imaging::copySeriesBetweenBuckets(
           IDC_S3_BucketName,
           fromDirectory,
           inputBucketName,
           inputDirectory, clientConfiguration)) {
       std::cerr << "This workflow will exit because of an error." << std::endl;
       cleanup(stackName, dataStoreId, clientConfiguration);
       return false;
   }
```

Importe os arquivos DICOM para o armazenamento de dados do Amazon S3.

```
bool AwsDoc::Medical_Imaging::startDicomImport(const Aws::String &dataStoreID,
```

```
                                                const Aws::String
 &inputBucketName,
                                                const Aws::String &inputDirectory,
                                                const Aws::String
 &outputBucketName,
                                                const Aws::String
 &outputDirectory,
                                                const Aws::String &roleArn,
                                                Aws::String &importJobId,
                                                const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    bool result = false;
    if (startDICOMImportJob(dataStoreID, inputBucketName, inputDirectory,
                            outputBucketName, outputDirectory, roleArn,
 importJobId,
                            clientConfiguration)) {
        std::cout << "DICOM import job started with job ID " << importJobId <<
 "."
                  << std::endl;
        result = waitImportJobCompleted(dataStoreID, importJobId,
 clientConfiguration);
        if (result) {
            std::cout << "DICOM import job completed." << std::endl;

        }
    }

    return result;
}

//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
  \param inputDirectory: The directory in the S3 bucket containing the DICOM
 files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
```

```
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory +
 "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}


//! Routine which waits for a DICOM import job to complete.
/*!
 * @param dataStoreID: The HealthImaging data store ID.
 * @param importJobId: The import job ID.
 * @param clientConfiguration : Aws client configuration.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::waitImportJobCompleted(const Aws::String
 &datastoreID,
```

```
                                                        const Aws::String
 &importJobId,
                                                        const
 Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MedicalImaging::Model::JobStatus jobStatus =
 Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS;
    while (jobStatus == Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS) {
        std::this_thread::sleep_for(std::chrono::seconds(1));

        Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
 getDicomImportJobOutcome = getDICOMImportJob(
                datastoreID, importJobId,
                clientConfiguration);

        if (getDicomImportJobOutcome.IsSuccess()) {
            jobStatus =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetJobStatus();

            std::cout << "DICOM import job status: " <<

 Aws::MedicalImaging::Model::JobStatusMapper::GetNameForJobStatus(
                              jobStatus) << std::endl;
        }
        else {
            std::cerr << "Failed to get import job status because "
                      << getDicomImportJobOutcome.GetError().GetMessage() <<
 std::endl;
            return false;
        }
    }

    return jobStatus == Aws::MedicalImaging::Model::JobStatus::COMPLETED;
}

//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
```

```
                                                const Aws::String &importJobID,
                                                const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome;
}
```

Obtenha conjuntos de imagens criados pelo trabalho de importação DICOM.

```
bool
AwsDoc::Medical_Imaging::getImageSetsForDicomImportJob(const Aws::String
 &datastoreID,
                                                        const Aws::String
 &importJobId,
                                                        Aws::Vector<Aws::String>
 &imageSets,
                                                        const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome getDicomImportJobOutcome
 = getDICOMImportJob(
            datastoreID, importJobId, clientConfiguration);
    bool result = false;
    if (getDicomImportJobOutcome.IsSuccess()) {
        auto outputURI =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetOutputS3Uri();
        Aws::Http::URI uri(outputURI);
        const Aws::String &bucket = uri.GetAuthority();
        Aws::String key = uri.GetPath();

        Aws::S3::S3Client s3Client(clientConfiguration);
        Aws::S3::Model::GetObjectRequest objectRequest;
```

```
        objectRequest.SetBucket(bucket);
        objectRequest.SetKey(key + "/" + IMPORT_JOB_MANIFEST_FILE_NAME);

        auto getObjectOutcome = s3Client.GetObject(objectRequest);
        if (getObjectOutcome.IsSuccess()) {
            auto &data = getObjectOutcome.GetResult().GetBody();

            std::stringstream stringStream;
            stringStream << data.rdbuf();

            try {
                // Use JMESPath to extract the image set IDs.
                // https://jmespath.org/specification.html
                std::string jmesPathExpression =
"jobSummary.imageSetsSummary[].imageSetId";
                jsoncons::json doc = jsoncons::json::parse(stringStream.str());

                jsoncons::json imageSetsJson = jsoncons::jmespath::search(doc,

jmesPathExpression);\
                for (auto &imageSet: imageSetsJson.array_range()) {
                    imageSets.push_back(imageSet.as_string());
                }

                result = true;
            }
            catch (const std::exception &e) {
                std::cerr << e.what() << '\n';
            }

        }
        else {
            std::cerr << "Failed to get object because "
                      << getObjectOutcome.GetError().GetMessage() << std::endl;
        }

    }
    else {
        std::cerr << "Failed to get import job status because "
                  << getDicomImportJobOutcome.GetError().GetMessage() <<
std::endl;
    }

    return result;
```

```
}
```

Obtenha informações sobre os quadros de imagem de conjuntos de imagens.

```
bool AwsDoc::Medical_Imaging::getImageFramesForImageSet(const Aws::String
 &dataStoreID,
                                                         const Aws::String
 &imageSetID,
                                                         const Aws::String
 &outDirectory,

 Aws::Vector<ImageFrameInfo> &imageFrames,
                                                         const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::String fileName = outDirectory + "/" + imageSetID +
 "_metadata.json.gzip";
    bool result = false;
    if (getImageSetMetadata(dataStoreID, imageSetID, "", // Empty string for
 version ID.
                            fileName, clientConfiguration)) {
        try {
            std::string metadataGZip;
            {
                std::ifstream inFileStream(fileName.c_str(), std::ios::binary);
                if (!inFileStream) {
                    throw std::runtime_error("Failed to open file " + fileName);
                }

                std::stringstream stringStream;
                stringStream << inFileStream.rdbuf();
                metadataGZip = stringStream.str();
            }
            std::string metadataJson = gzip::decompress(metadataGZip.data(),
                                                         metadataGZip.size());
            // Use JMESPath to extract the image set IDs.
            // https://jmespath.org/specification.html
            jsoncons::json doc = jsoncons::json::parse(metadataJson);
            std::string jmesPathExpression = "Study.Series.*.Instances[].*[]";
            jsoncons::json instances = jsoncons::jmespath::search(doc,

 jmesPathExpression);
            for (auto &instance: instances.array_range()) {
```

```
                jmesPathExpression = "DICOM.RescaleSlope";
                std::string rescaleSlope = jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();
                jmesPathExpression = "DICOM.RescaleIntercept";
                std::string rescaleIntercept =
jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();

                jmesPathExpression = "ImageFrames[][]";
                jsoncons::json imageFramesJson =
jsoncons::jmespath::search(instance,

jmesPathExpression);

                for (auto &imageFrame: imageFramesJson.array_range()) {
                    ImageFrameInfo imageFrameIDs;
                    imageFrameIDs.mImageSetId = imageSetID;
                    imageFrameIDs.mImageFrameId = imageFrame.find(
                            "ID")->value().as_string();
                    imageFrameIDs.mRescaleIntercept = rescaleIntercept;
                    imageFrameIDs.mRescaleSlope = rescaleSlope;
                    imageFrameIDs.MinPixelValue = imageFrame.find(
                            "MinPixelValue")->value().as_string();
                    imageFrameIDs.MaxPixelValue = imageFrame.find(
                            "MaxPixelValue")->value().as_string();

                    jmesPathExpression =
"max_by(PixelDataChecksumFromBaseToFullResolution, &Width).Checksum";
                    jsoncons::json checksumJson =
jsoncons::jmespath::search(imageFrame,

jmesPathExpression);
                    imageFrameIDs.mFullResolutionChecksum =
checksumJson.as_integer<uint32_t>();

                    imageFrames.emplace_back(imageFrameIDs);
                }
            }

            result = true;
        }
        catch (const std::exception &e) {
```

```
            std::cerr << "getImageFramesForImageSet failed because " << e.what()
                      << std::endl;
        }
    }

    return result;
}

//! Routine which gets a HealthImaging image set's metadata.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped
 json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String
 &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

Baixe, decodifique e verifique os quadros de imagem.

```
bool AwsDoc::Medical_Imaging::downloadDecodeAndCheckImageFrames(
        const Aws::String &dataStoreID,
        const Aws::Vector<ImageFrameInfo> &imageFrames,
        const Aws::String &outDirectory,
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::Client::ClientConfiguration clientConfiguration1(clientConfiguration);
    clientConfiguration1.executor =
 Aws::MakeShared<Aws::Utils::Threading::PooledThreadExecutor>(
            "executor", 25);
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(
            clientConfiguration1);

    Aws::Utils::Threading::Semaphore semaphore(0, 1);
    std::atomic<size_t> count(imageFrames.size());

    bool result = true;
    for (auto &imageFrame: imageFrames) {
        Aws::MedicalImaging::Model::GetImageFrameRequest getImageFrameRequest;
        getImageFrameRequest.SetDatastoreId(dataStoreID);
        getImageFrameRequest.SetImageSetId(imageFrame.mImageSetId);

        Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
        imageFrameInformation.SetImageFrameId(imageFrame.mImageFrameId);
        getImageFrameRequest.SetImageFrameInformation(imageFrameInformation);

        auto getImageFrameAsyncLambda = [&semaphore, &result, &count, imageFrame,
 outDirectory](
                const Aws::MedicalImaging::MedicalImagingClient *client,
                const Aws::MedicalImaging::Model::GetImageFrameRequest &request,
                Aws::MedicalImaging::Model::GetImageFrameOutcome outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext>
 &context) {

                if (!handleGetImageFrameResult(outcome, outDirectory,
 imageFrame)) {
```

```
                    std::cerr << "Failed to download and convert image frame: "
                              << imageFrame.mImageFrameId << " from image set: "
                              << imageFrame.mImageSetId << std::endl;
                    result = false;
                }

                count--;
                if (count <= 0) {

                    semaphore.ReleaseAll();
                }
        }; // End of 'getImageFrameAsyncLambda' lambda.

        medicalImagingClient.GetImageFrameAsync(getImageFrameRequest,
                                                getImageFrameAsyncLambda);
    }

    if (count > 0) {
        semaphore.WaitOne();
    }

    if (result) {
        std::cout << imageFrames.size() << " image files were downloaded."
                  << std::endl;
    }

    return result;
}

bool AwsDoc::Medical_Imaging::decodeJPHFileAndValidateWithChecksum(
        const Aws::String &jphFile,
        uint32_t crc32Checksum) {
    opj_image_t *outputImage = jphImageToOpjBitmap(jphFile);
    if (!outputImage) {
        return false;
    }

    bool result = true;
    if (!verifyChecksumForImage(outputImage, crc32Checksum)) {
        std::cerr << "The checksum for the image does not match the expected
 value."
                  << std::endl;
        std::cerr << "File :" << jphFile << std::endl;
        result = false;
```

```
    }

    opj_image_destroy(outputImage);

    return result;
}

opj_image *
AwsDoc::Medical_Imaging::jphImageToOpjBitmap(const Aws::String &jphFile) {
    opj_stream_t *inFileStream = nullptr;
    opj_codec_t *decompressorCodec = nullptr;
    opj_image_t *outputImage = nullptr;
    try {
        std::shared_ptr<opj_dparameters> decodeParameters =
 std::make_shared<opj_dparameters>();
        memset(decodeParameters.get(), 0, sizeof(opj_dparameters));

        opj_set_default_decoder_parameters(decodeParameters.get());

        decodeParameters->decod_format = 1; // JP2 image format.
        decodeParameters->cod_format = 2; // BMP image format.

        std::strncpy(decodeParameters->infile, jphFile.c_str(),
                     OPJ_PATH_LEN);

        inFileStream = opj_stream_create_default_file_stream(
                decodeParameters->infile, true);
        if (!inFileStream) {
            throw std::runtime_error(
                    "Unable to create input file stream for file '" + jphFile +
 "'.");
        }

        decompressorCodec = opj_create_decompress(OPJ_CODEC_JP2);
        if (!decompressorCodec) {
            throw std::runtime_error("Failed to create decompression codec.");
        }

        int decodeMessageLevel = 1;
        if (!setupCodecLogging(decompressorCodec, &decodeMessageLevel)) {
            std::cerr << "Failed to setup codec logging." << std::endl;
        }

        if (!opj_setup_decoder(decompressorCodec, decodeParameters.get())) {
```

```
            throw std::runtime_error("Failed to setup decompression codec.");
        }
        if (!opj_codec_set_threads(decompressorCodec, 4)) {
            throw std::runtime_error("Failed to set decompression codec
 threads.");
        }

        if (!opj_read_header(inFileStream, decompressorCodec, &outputImage)) {
            throw std::runtime_error("Failed to read header.");
        }

        if (!opj_decode(decompressorCodec, inFileStream,
                        outputImage)) {
            throw std::runtime_error("Failed to decode.");
        }

        if (DEBUGGING) {
            std::cout << "image width : " << outputImage->x1 - outputImage->x0
                      << std::endl;
            std::cout << "image height : " << outputImage->y1 - outputImage->y0
                      << std::endl;
            std::cout << "number of channels: " << outputImage->numcomps
                      << std::endl;
            std::cout << "colorspace : " << outputImage->color_space <<
 std::endl;
        }

    } catch (const std::exception &e) {
        std::cerr << e.what() << std::endl;
        if (outputImage) {
            opj_image_destroy(outputImage);
            outputImage = nullptr;
        }
    }
    if (inFileStream) {
        opj_stream_destroy(inFileStream);
    }
    if (decompressorCodec) {
        opj_destroy_codec(decompressorCodec);
    }

    return outputImage;
}
```

```
//! Template function which converts a planar image bitmap to an interleaved
 image bitmap and
//! then verifies the checksum of the bitmap.
/*!
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
template<class myType>
bool verifyChecksumForImageForType(opj_image_t *image, uint32_t crc32Checksum) {
    uint32_t width = image->x1 - image->x0;
    uint32_t height = image->y1 - image->y0;
    uint32_t numOfChannels = image->numcomps;

    // Buffer for interleaved bitmap.
    std::vector<myType> buffer(width * height * numOfChannels);

    // Convert planar bitmap to interleaved bitmap.
    for (uint32_t channel = 0; channel < numOfChannels; channel++) {
        for (uint32_t row = 0; row < height; row++) {
            uint32_t fromRowStart = row / image->comps[channel].dy * width /
                                    image->comps[channel].dx;
            uint32_t toIndex = (row * width) * numOfChannels + channel;

            for (uint32_t col = 0; col < width; col++) {
                uint32_t fromIndex = fromRowStart + col / image-
>comps[channel].dx;

                buffer[toIndex] = static_cast<myType>(image-
>comps[channel].data[fromIndex]);

                toIndex += numOfChannels;
            }
        }
    }

    // Verify checksum.
    boost::crc_32_type crc32;
    crc32.process_bytes(reinterpret_cast<char *>(buffer.data()),
                        buffer.size() * sizeof(myType));

    bool result = crc32.checksum() == crc32Checksum;
    if (!result) {
        std::cerr << "verifyChecksumForImage, checksum mismatch, expected - "
```

```
                  << crc32Checksum << ", actual - " << crc32.checksum()
                  << std::endl;
    }

    return result;
}

//! Routine which verifies the checksum of an OpenJPEG image struct.
/*!
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::verifyChecksumForImage(opj_image_t *image,
                                                     uint32_t crc32Checksum) {
    uint32_t channels = image->numcomps;
    bool result = false;
    if (0 < channels) {
        // Assume the precision is the same for all channels.
        uint32_t precision = image->comps[0].prec;
        bool signedData = image->comps[0].sgnd;
        uint32_t bytes = (precision + 7) / 8;

        if (signedData) {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<int8_t>(image,

 crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<int16_t>(image,

 crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<int32_t>(image,

 crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
 signed bytes - "
```

```
                            << bytes << std::endl;
                    break;
            }
        }
        else {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<uint8_t>(image,

 crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<uint16_t>(image,

 crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<uint32_t>(image,

 crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
 unsigned bytes - "
                            << bytes << std::endl;
                    break;
            }
        }

        if (!result) {
            std::cerr << "verifyChecksumForImage, error bytes " << bytes
                      << " signed "
                      << signedData << std::endl;
        }
    }
    else {
        std::cerr << "'verifyChecksumForImage', no channels in the image."
                  << std::endl;
    }
    return result;
}
```

Limpe os recursos.

```
bool AwsDoc::Medical_Imaging::cleanup(const Aws::String &stackName,
                                      const Aws::String &dataStoreId,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    bool result = true;

    if (!stackName.empty() && askYesNoQuestion(
            "Would you like to delete the stack " + stackName + "? (y/n)")) {
        std::cout << "Deleting the image sets in the stack." << std::endl;
        result &= emptyDatastore(dataStoreId, clientConfiguration);
        printAsterisksLine();
        std::cout << "Deleting the stack." << std::endl;
        result &= deleteStack(stackName, clientConfiguration);
    }
    return result;
}

bool AwsDoc::Medical_Imaging::emptyDatastore(const Aws::String &datastoreID,
                                             const
 Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MedicalImaging::Model::SearchCriteria emptyCriteria;
    Aws::Vector<Aws::String> imageSetIDs;
    bool result = false;
    if (searchImageSets(datastoreID, emptyCriteria, imageSetIDs,
                        clientConfiguration)) {
        result = true;
        for (auto &imageSetID: imageSetIDs) {
            result &= deleteImageSet(datastoreID, imageSetID,
 clientConfiguration);
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - DeleteImageSet

- Obtenha o DICOM ImportJob
- GetImageFrame
- GetImageSetMetadata
- SearchImageSets
- Inicie o DICOM ImportJob

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Marcar um armazenamento HealthImaging de dados usando um SDK AWS

Os exemplos de código a seguir mostram como marcar um armazenamento HealthImaging de dados.

Java

SDK para Java 2.x

Para marcar um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                TagResource.tagMedicalImagingResource(medicalImagingClient,
 datastoreArn,
                                ImmutableMap.of("Deployment", "Development"));
```

A função utilitária para marcar um recurso.

```
    public static void tagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Map<String, String> tags) {
        try {
            TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                    .resourceArn(resourceArn)
```

```
                    .tags(tags)
                    .build();

            medicalImagingClient.tagResource(tagResourceRequest);

            System.out.println("Tags have been added to the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Para listar tags para um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                ListTagsForResourceResponse result =
 ListTagsForResource.listMedicalImagingResourceTags(
                                medicalImagingClient,
                                datastoreArn);
                if (result != null) {
                        System.out.println("Tags for resource: " +
 result.tags());
                }
```

A função utilitária para listar as tags de um recurso.

```
    public static ListTagsForResourceResponse
 listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
            String resourceArn) {
        try {
            ListTagsForResourceRequest listTagsForResourceRequest =
 ListTagsForResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .build();

            return
 medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }

        return null;
    }
```

Para desmarcar um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                UntagResource.untagMedicalImagingResource(medicalImagingClient,
 datastoreArn,
                                Collections.singletonList("Deployment"));
```

A função de utilitário para desmarcar um recurso.

```
    public static void untagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Collection<String> tagKeys) {
        try {
            UntagResourceRequest untagResourceRequest =
 UntagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tagKeys(tagKeys)
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.

- ListTagsForResource
- TagResource
- UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

Para marcar um armazenamento de dados

```
  try {
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const tags = {
      Deployment: "Development",
    };
    await tagResource(datastoreArn, tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para marcar um recurso.

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
```

```
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tags = {}
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

Para listar tags para um armazenamento de dados

```
  try {
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const { tags } = await listTagsForResource(datastoreArn);
    console.log(tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para listar as tags de um recurso.

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
```

```
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/
ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
  // }

  return response;
};
```

Para desmarcar um armazenamento de dados

```
  try {
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const keys = ["Deployment"];
    await untagResource(datastoreArn, keys);
  } catch (e) {
    console.log(e);
  }
```

A função de utilitário para desmarcar um recurso.

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
```

```
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tagKeys = []
) => {
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

Para marcar um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.tag_resource(data_store_arn, {"Deployment":
 "Development"})
```

A função utilitária para marcar um recurso.

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
 tags=tags)
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Para listar tags para um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.list_tags_for_resource(data_store_arn)
```

A função utilitária para listar as tags de um recurso.

```
    def list_tags_for_resource(self, resource_arn):
        """
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

Para desmarcar um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.untag_resource(data_store_arn, ["Deployment"])
```

A função de utilitário para desmarcar um recurso.

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
```

```
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Marcar um conjunto de HealthImaging imagens usando um SDK AWS

Os exemplos de código a seguir mostram como marcar um conjunto de HealthImaging imagens.

Java

SDK para Java 2.x

Para marcar um conjunto de imagens

```
                final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
```

```
                TagResource.tagMedicalImagingResource(medicalImagingClient,
 imageSetArn,
                                ImmutableMap.of("Deployment", "Development"));
```

A função utilitária para marcar um recurso.

```
   public static void tagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
           String resourceArn,
           Map<String, String> tags) {
       try {
           TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .tags(tags)
                   .build();

           medicalImagingClient.tagResource(tagResourceRequest);

           System.out.println("Tags have been added to the resource.");
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

Para listar tags para um conjunto de imagens

```
                final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";

                ListTagsForResourceResponse result =
 ListTagsForResource.listMedicalImagingResourceTags(
                                medicalImagingClient,
                                imageSetArn);
                if (result != null) {
                        System.out.println("Tags for resource: " +
 result.tags());
                }
```

A função utilitária para listar as tags de um recurso.

```
    public static ListTagsForResourceResponse
 listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
            String resourceArn) {
        try {
            ListTagsForResourceRequest listTagsForResourceRequest =
 ListTagsForResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .build();

            return
 medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }
```

Para desmarcar um conjunto de imagens

```
                final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";

                UntagResource.untagMedicalImagingResource(medicalImagingClient,
 imageSetArn,
                                Collections.singletonList("Deployment"));
```

A função de utilitário para desmarcar um recurso.

```
    public static void untagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Collection<String> tagKeys) {
        try {
            UntagResourceRequest untagResourceRequest =
 UntagResourceRequest.builder()
```

```
                    .resourceArn(resourceArn)
                    .tagKeys(tagKeys)
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

JavaScript

SDK para JavaScript (v3)

Para marcar um conjunto de imagens

```
  try {
    const imagesetArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const tags = {
      Deployment: "Development",
    };
    await tagResource(imagesetArn, tags);
```

```
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para marcar um recurso.

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tags = {}
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

Para listar tags para um conjunto de imagens

```
  try {
```

```
    const imagesetArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const { tags } = await listTagsForResource(imagesetArn);
    console.log(tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para listar as tags de um recurso.

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/
ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
  // }

  return response;
};
```

Para desmarcar um conjunto de imagens

```
  try {
    const imagesetArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const keys = ["Deployment"];
    await untagResource(imagesetArn, keys);
  } catch (e) {
    console.log(e);
  }
```

A função de utilitário para desmarcar um recurso.

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data
 store or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/
imageset/xxx",
  tagKeys = []
) => {
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }
```

```
  return response;
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Python

SDK para Python (Boto3)

Para marcar um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
    )

    medical_imaging_wrapper.tag_resource(image_set_arn, {"Deployment":
 "Development"})
```

A função utilitária para marcar um recurso.

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
```

```
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
 tags=tags)
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Para listar tags para um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
    )

    medical_imaging_wrapper.list_tags_for_resource(image_set_arn)
```

A função utilitária para listar as tags de um recurso.

```
    def list_tags_for_resource(self, resource_arn):
        """
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

Para desmarcar um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
    )

    medical_imaging_wrapper.untag_resource(image_set_arn, ["Deployment"])
```

A função de utilitário para desmarcar um recurso.

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos de código para o IAM usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Identity and Access Management (IAM) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do IAM – Mais informações sobre o IAM.
- Referência da API do IAM – Detalhes sobre todas as ações disponíveis do IAM.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace IAMActions;

public class HelloIAM
{
    static async Task Main(string[] args)
    {
        // Getting started with AWS Identity and Access Management (IAM). List
        // the policies for the account.
        var iamClient = new AmazonIdentityManagementServiceClient();

        var listPoliciesPaginator = iamClient.Paginators.ListPolicies(new
 ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        Console.WriteLine("Here are the policies defined for your account:\n");
        policies.ForEach(policy =>
        {
            Console.WriteLine($"Created:
 {policy.CreateDate}\t{policy.PolicyName}\t{policy.Description}");
        });
    }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS iam)

# Set this project's name.
project("hello_iam")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.
```

```
    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you
 may need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_iam.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem iam.cpp.

```
#include <aws/core/Aws.h>
#include <aws/iam/IAMClient.h>
#include <aws/iam/model/ListPoliciesRequest.h>
#include <iostream>
#include <iomanip>

/*
 *  A "Hello IAM" starter application which initializes an AWS Identity and
 Access Management (IAM) client
 *  and lists the IAM policies.
 *
 *  main function
 *
 *  Usage: 'hello_iam'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        const Aws::String DATE_FORMAT("%Y-%m-%d");
        Aws::Client::ClientConfiguration clientConfig;
```

```
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::IAM::IAMClient iamClient(clientConfig);
        Aws::IAM::Model::ListPoliciesRequest request;

        bool done = false;
        bool header = false;
        while (!done) {
            auto outcome = iamClient.ListPolicies(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Failed to list iam policies: " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }

            if (!header) {
                std::cout << std::left << std::setw(55) << "Name" <<
                          std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                          std::setw(64) << "Description" << std::setw(12) <<
                          "CreateDate" << std::endl;
                header = true;
            }

            const auto &policies = outcome.GetResult().GetPolicies();
            for (const auto &policy: policies) {
                std::cout << std::left << std::setw(55) <<
                          policy.GetPolicyName() << std::setw(30) <<
                          policy.GetPolicyId() << std::setw(80) <<
policy.GetArn() <<
                          std::setw(64) << policy.GetDescription() <<
std::setw(12) <<
                          policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str())
<<
                          std::endl;
            }

            if (outcome.GetResult().GetIsTruncated()) {
                request.SetMarker(outcome.GetResult().GetMarker());
            } else {
                done = true;
            }
        }
```

```
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/iam"
)

// main uses the AWS SDK for Go (v2) to create an AWS Identity and Access
 Management (IAM)
// client and list up to 10 policies in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
```

```
  fmt.Println(err)
  return
 }
 iamClient := iam.NewFromConfig(sdkConfig)
 const maxPols = 10
 fmt.Printf("Let's list up to %v policies for your account.\n", maxPols)
 result, err := iamClient.ListPolicies(context.TODO(), &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPols),
 })
 if err != nil {
  fmt.Printf("Couldn't list policies for your account. Here's why: %v\n", err)
  return
 }
 if len(result.Policies) == 0 {
  fmt.Println("You don't have any policies!")
 } else {
  for _, policy := range result.Policies {
   fmt.Printf("\t%v\n", *policy.PolicyName)
  }
 }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.ListPoliciesResponse;
import software.amazon.awssdk.services.iam.model.Policy;
import java.util.List;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloIAM {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listPolicies(iam);
    }

    public static void listPolicies(IamClient iam) {
        ListPoliciesResponse response = iam.listPolicies();
        List<Policy> polList = response.policies();
        polList.forEach(policy -> {
            System.out.println("Policy Name: " + policy.policyName());
        });
    }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { IAMClient, paginateListPolicies } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listLocalPolicies = async () => {
  /**
   * In v3, the clients expose paginateOperationName APIs that are written using
 async generators so that you can use async iterators in a for await..of loop.
   * https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/index.html#paginators
   */
  const paginator = paginateListPolicies(
    { client, pageSize: 10 },
    // List only customer managed policies.
    { Scope: "Local" },
  );

  console.log("IAM policies defined in your account:");
  let policyCount = 0;
  for await (const page of paginator) {
    if (page.Policies) {
      page.Policies.forEach((p) => {
        console.log(`${p.PolicyName}`);
        policyCount++;
      });
    }
  }
  console.log(`Found ${policyCount} policies.`);
};
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for JavaScript da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

De src/bin/hello.rs.

```
use aws_sdk_iam::error::SdkError;
use aws_sdk_iam::operation::list_policies::ListPoliciesError;
use clap::Parser;

const PATH_PREFIX_HELP: &str = "The path prefix for filtering the results.";

#[derive(Debug, clap::Parser)]
#[command(about)]
struct HelloScenarioArgs {
    #[arg(long, default_value="/", help=PATH_PREFIX_HELP)]
    pub path_prefix: String,
}

#[tokio::main]
async fn main() -> Result<(), SdkError<ListPoliciesError>> {
    let sdk_config = aws_config::load_from_env().await;
    let client = aws_sdk_iam::Client::new(&sdk_config);

    let args = HelloScenarioArgs::parse();

    iam_service::list_policies(client, args.path_prefix).await?;

    Ok(())
}
```

De src/ iam-service-lib .rs.

```
pub async fn list_policies(
    client: iamClient,
    path_prefix: String,
) -> Result<Vec<String>, SdkError<ListPoliciesError>> {
    let list_policies = client
        .list_policies()
        .path_prefix(path_prefix)
        .scope(PolicyScopeType::Local)
        .into_paginator()
        .items()
        .send()
        .try_collect()
```

```
        .await?;

    let policy_names = list_policies
        .into_iter()
        .map(|p| {
            let name = p
                .policy_name
                .unwrap_or_else(|| "Missing Policy Name".to_string());
            println!("{}", name);
            name
        })
        .collect();

    Ok(policy_names)
}
```

- Para obter detalhes da API, consulte a ListPoliciesreferência da API AWS SDK for Rust.

Exemplos de código

- Ações do IAM usando AWS SDKs
  - Adicionar um usuário do IAM a um grupo usando um AWS SDK
  - Anexar uma política do IAM a um perfil usando um SDK da AWS
  - Anexar uma política do IAM a um usuário usando um AWS SDK
  - Anexar uma política em linha a um perfil do IAM usando um AWS SDK
  - Criar um provedor SAML do IAM usando um AWS SDK
  - Criar um grupo do IAM usando um AWS SDK
  - Criar uma política do IAM usando um AWS SDK
  - Criar uma versão de política do IAM usando um AWS SDK
  - Criar um perfil do IAM usando um AWS SDK
  - Criar uma função vinculada ao serviço do IAM usando um AWS SDK
  - Criar um usuário do IAM usando um AWS SDK
  - Criar uma chave de acesso do IAM usando um AWS SDK
  - Criar um alias para uma conta do IAM usando um AWS SDK
  - Criar uma política do IAM em linha para um grupo usando um AWS SDK
  - Criar uma política em linha do IAM para um usuário usando um AWS SDK

- Criar um perfil de instância do IAM usando um SDK da AWS
- Excluir um provedor SAML do IAM usando um AWS SDK
- Excluir um grupo do IAM usando um AWS SDK
- Excluir uma política de grupo do IAM usando um AWS SDK
- Excluir uma política do IAM usando um AWS SDK
- Excluir um perfil do IAM usando um AWS SDK
- Excluir uma política de perfil do IAM usando um AWS SDK
- Excluir um certificado de servidor do IAM usando um AWS SDK
- Excluir um perfil vinculado ao serviço do IAM usando um AWS SDK
- Excluir um usuário do IAM usando um AWS SDK
- Excluir uma chave de acesso do IAM usando um AWS SDK
- Excluir uma conta do IAM usando um AWS SDK
- Excluir uma política do IAM em linha de um usuário usando um AWSSDK
- Criar um perfil de instância do IAM usando um AWS SDK
- Desanexar uma política do IAM de um perfil usando um SDK da AWS
- Desanexar uma política do IAM de um usuário usando um AWS SDK
- Gerar um relatório de credenciais do IAM usando um AWS SDK
- Obter um relatório de credenciais do IAM usando um AWS SDK
- Obter um relatório detalhado de autorização do IAM para a conta usando um AWS SDK
- Obter uma política do IAM usando um AWS SDK
- Obter uma versão de política do IAM usando um AWS SDK
- Obter um perfil do IAM usando um AWS SDK
- Obter um certificado de servidor do IAM usando um AWS SDK
- Obter o status de exclusão do perfil vinculado ao serviço do IAM usando um AWS SDK
- Obter um resumo da utilização da conta do IAM usando um AWS SDK
- Obter um usuário do IAM usando um AWS SDK
- Obter dados sobre a última utilização de uma chave de acesso do IAM usando um AWS SDK
- Obter a política de senha da conta do IAM usando um AWS SDK
- Listar provedores SAML para o IAM usando um AWS SDK

- Listar as chaves de acesso do IAM de um usuário usando um AWS SDK

- Listar aliases da conta do IAM usando um AWS SDK
- Listar grupos do IAM usando um AWS SDK
- Listar políticas em linha para um perfil do IAM usando um AWS SDK
- Listar políticas do IAM em linha para um usuário com um AWS SDK
- Listar políticas do IAM usando um AWS SDK
- Listar políticas anexadas a um perfil do IAM usando um AWS SDK
- Listar perfis do IAM usando um AWS SDK
- Listar certificados de servidor do IAM usando um AWS SDK
- Listar usuários do IAM usando um AWS SDK
- Remover um usuário do IAM de um grupo usando um AWS SDK
- Atualizar um certificado de servidor do IAM usando um AWS SDK
- Atualizar um usuário do IAM usando um AWS SDK
- Atualizar uma chave de acesso do IAM usando um AWS SDK
- Fazer upload de um certificado de servidor do IAM usando um AWS SDK

- Cenários para o IAM usando AWS SDKs
  - Criar e gerenciar um serviço resiliente usando um AWS SDK
  - Criar um grupo do IAM e adicionar um usuário ao grupo usando um AWS SDK
  - Criar um usuário do IAM e assumir uma função com o AWS STS usando um AWS SDK
  - Criar usuários do IAM somente leitura e leitura/gravação usando um AWS SDK
  - Gerenciar chaves de acesso do IAM usando um AWS SDK
  - Gerenciar políticas do IAM usando um AWS SDK
  - Gerenciar perfis do IAM usando um AWS SDK
  - Gerenciar a conta do IAM usando um AWS SDK
  - Reverter uma versão de política do IAM usando um AWS SDK
  - Trabalhar com a API IAM Policy Builder usando um AWS SDK

Ações do IAM usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Identity and Access Management (IAM) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o IAM usando AWS SDKs.

Exemplos

- Adicionar um usuário do IAM a um grupo usando um AWS SDK
- Anexar uma política do IAM a um perfil usando um SDK da AWS
- Anexar uma política do IAM a um usuário usando um AWS SDK
- Anexar uma política em linha a um perfil do IAM usando um AWS SDK
- Criar um provedor SAML do IAM usando um AWS SDK
- Criar um grupo do IAM usando um AWS SDK
- Criar uma política do IAM usando um AWS SDK
- Criar uma versão de política do IAM usando um AWS SDK
- Criar um perfil do IAM usando um AWS SDK
- Criar uma função vinculada ao serviço do IAM usando um AWS SDK
- Criar um usuário do IAM usando um AWS SDK
- Criar uma chave de acesso do IAM usando um AWS SDK
- Criar um alias para uma conta do IAM usando um AWS SDK
- Criar uma política do IAM em linha para um grupo usando um AWS SDK
- Criar uma política em linha do IAM para um usuário usando um AWS SDK
- Criar um perfil de instância do IAM usando um SDK da AWS
- Excluir um provedor SAML do IAM usando um AWS SDK
- Excluir um grupo do IAM usando um AWS SDK
- Excluir uma política de grupo do IAM usando um AWS SDK
- Excluir uma política do IAM usando um AWS SDK
- Excluir um perfil do IAM usando um AWS SDK
- Excluir uma política de perfil do IAM usando um AWS SDK
- Excluir um certificado de servidor do IAM usando um AWS SDK
- Excluir um perfil vinculado ao serviço do IAM usando um AWS SDK
- Excluir um usuário do IAM usando um AWS SDK
- Excluir uma chave de acesso do IAM usando um AWS SDK

- Excluir uma conta do IAM usando um AWS SDK
- Excluir uma política do IAM em linha de um usuário usando um AWSSDK
- Criar um perfil de instância do IAM usando um AWS SDK
- Desanexar uma política do IAM de um perfil usando um SDK da AWS
- Desanexar uma política do IAM de um usuário usando um AWS SDK
- Gerar um relatório de credenciais do IAM usando um AWS SDK
- Obter um relatório de credenciais do IAM usando um AWS SDK
- Obter um relatório detalhado de autorização do IAM para a conta usando um AWS SDK
- Obter uma política do IAM usando um AWS SDK
- Obter uma versão de política do IAM usando um AWS SDK
- Obter um perfil do IAM usando um AWS SDK
- Obter um certificado de servidor do IAM usando um AWS SDK
- Obter o status de exclusão do perfil vinculado ao serviço do IAM usando um AWS SDK
- Obter um resumo da utilização da conta do IAM usando um AWS SDK
- Obter um usuário do IAM usando um AWS SDK
- Obter dados sobre a última utilização de uma chave de acesso do IAM usando um AWS SDK
- Obter a política de senha da conta do IAM usando um AWS SDK
- Listar provedores SAML para o IAM usando um AWS SDK
- Listar as chaves de acesso do IAM de um usuário usando um AWS SDK
- Listar aliases da conta do IAM usando um AWS SDK
- Listar grupos do IAM usando um AWS SDK
- Listar políticas em linha para um perfil do IAM usando um AWS SDK
- Listar políticas do IAM em linha para um usuário com um AWS SDK
- Listar políticas do IAM usando um AWS SDK
- Listar políticas anexadas a um perfil do IAM usando um AWS SDK
- Listar perfis do IAM usando um AWS SDK
- Listar certificados de servidor do IAM usando um AWS SDK
- Listar usuários do IAM usando um AWS SDK
- Remover um usuário do IAM de um grupo usando um AWS SDK
- Atualizar um certificado de servidor do IAM usando um AWS SDK

- Atualizar um usuário do IAM usando um AWS SDK
- Atualizar uma chave de acesso do IAM usando um AWS SDK
- Fazer upload de um certificado de servidor do IAM usando um AWS SDK

Adicionar um usuário do IAM a um grupo usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como adicionar um usuário a um grupo do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add an existing IAM user to an existing IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string
groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
AddUserToGroupRequest
        {
            GroupName = groupName,
            UserName = userName,
        });
```

```
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte AddUserToGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como adicionar um usuário a um grupo do IAM

O comando `add-user-to-group`, apresentado a seguir, adiciona um usuário do IAM denominado `Bob` ao grupo do IAM denominado `Admins`.

```
aws iam add-user-to-group \
    --user-name Bob \
    --group-name Admins
```

Este comando não produz saída.

Para obter mais informações, consulte Adicionar e remover usuários de um grupo de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte AddUserToGroupem Referência de AWS CLI Comandos.

Anexar uma política do IAM a um perfil usando um SDK da AWS

Os exemplos de código a seguir mostram como anexar uma política do IAM a uma função.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Gerenciar funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _IAMService.AttachRolePolicyAsync(new
 AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_attach_role_policy
#
# This function attaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_attach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_attach_role_policy"
    echo "Attaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
```

```
  echo "  -p policy_ARN -- The IAM policy document ARN."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) role_name="${OPTARG}" ;;
    p) policy_arn="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$role_name" ]]; then
  errecho "ERROR: You must provide a role name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_arn" ]]; then
  errecho "ERROR: You must provide a policy ARN with the -p parameter."
  usage
  return 1
fi

response=$(aws iam attach-role-policy \
  --role-name "$role_name" \
  --policy-arn "$policy_arn")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports attach-role-policy operation failed.\n$response"
  return 1
```

```
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte AttachRolePolicyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::attachRolePolicy(const Aws::String &roleName,
                                   const Aws::String &policyArn,
                                   const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::ListAttachedRolePoliciesRequest list_request;
    list_request.SetRoleName(roleName);

    bool done = false;
    while (!done) {
        auto list_outcome = iam.ListAttachedRolePolicies(list_request);
        if (!list_outcome.IsSuccess()) {
            std::cerr << "Failed to list attached policies of role " <<
                      roleName << ": " << list_outcome.GetError().GetMessage() <<
                      std::endl;
            return false;
        }

        const auto &policies = list_outcome.GetResult().GetAttachedPolicies();
```

```
        if (std::any_of(policies.cbegin(), policies.cend(),
                        [=](const Aws::IAM::Model::AttachedPolicy &policy) {
                                return policy.GetPolicyArn() == policyArn;
                        })) {
            std::cout << "Policy " << policyArn <<
                      " is already attached to role " << roleName << std::endl;
            return true;
        }

        done = !list_outcome.GetResult().GetIsTruncated();
        list_request.SetMarker(list_outcome.GetResult().GetMarker());
    }

    Aws::IAM::Model::AttachRolePolicyRequest request;
    request.SetRoleName(roleName);
    request.SetPolicyArn(policyArn);

    Aws::IAM::Model::AttachRolePolicyOutcome outcome =
 iam.AttachRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to attach policy " << policyArn << " to role " <<
                  roleName << ": " << outcome.GetError().GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Successfully attached policy " << policyArn << " to role "
 <<
                  roleName << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como anexar uma política gerenciada a um perfil do IAM

O comando `attach-role-policy`, apresentado a seguir, anexa a política gerenciada pela AWS denominada `ReadOnlyAccess` ao perfil do IAM denominado `ReadOnlyRole`.

```
aws iam attach-role-policy \
    --policy-arn arn:aws:iam::aws:policy/ReadOnlyAccess \
    --role-name ReadOnlyRole
```

Este comando não produz saída.

Para obter mais informações, consulte Políticas gerenciadas e em linha no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte AttachRolePolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// AttachRolePolicy attaches a policy to a role.
func (wrapper RoleWrapper) AttachRolePolicy(policyArn string, roleName string)
 error {
 _, err := wrapper.IamClient.AttachRolePolicy(context.TODO(),
 &iam.AttachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
```

```
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't attach policy %v to role %v. Here's why: %v\n", policyArn,
 roleName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.AttachRolePolicyRequest;
import software.amazon.awssdk.services.iam.model.AttachedPolicy;
import software.amazon.awssdk.services.iam.model.ListAttachedRolePoliciesRequest;
import
 software.amazon.awssdk.services.iam.model.ListAttachedRolePoliciesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AttachRolePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleName> <policyArn>\s

                Where:
                    roleName - A role name that you can obtain from the AWS
 Management Console.\s
                    policyArn - A policy ARN that you can obtain from the AWS
 Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleName = args[0];
        String policyArn = args[1];

        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        attachIAMRolePolicy(iam, roleName, policyArn);
        iam.close();
    }

    public static void attachIAMRolePolicy(IamClient iam, String roleName, String
 policyArn) {
        try {
            ListAttachedRolePoliciesRequest request =
 ListAttachedRolePoliciesRequest.builder()
                    .roleName(roleName)
                    .build();

            ListAttachedRolePoliciesResponse response =
 iam.listAttachedRolePolicies(request);
```

```
            List<AttachedPolicy> attachedPolicies = response.attachedPolicies();

            // Ensure that the policy is not attached to this role
            String polArn = "";
            for (AttachedPolicy policy : attachedPolicies) {
                polArn = policy.policyArn();
                if (polArn.compareTo(policyArn) == 0) {
                    System.out.println(roleName + " policy is already attached to
 this role.");
                    return;
                }
            }

            AttachRolePolicyRequest attachRequest =
 AttachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.attachRolePolicy(attachRequest);

            System.out.println("Successfully attached policy " + policyArn +
                    " to role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Anexe a política.

```
import { AttachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const attachRolePolicy = (policyArn, roleName) => {
  const command = new AttachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        console.log(
          "AmazonDynamoDBFullAccess is already attached to this role."
        );
        process.exit();
      }
    });
    var params = {
      PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
      RoleName: process.argv[2],
    };
    iam.attachRolePolicy(params, function (err, data) {
      if (err) {
        console.log("Unable to attach policy to role", err);
      } else {
        console.log("Role attached successfully");
```

```
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun attachIAMRolePolicy(roleNameVal: String, policyArnVal: String) {

    val request = ListAttachedRolePoliciesRequest {
        roleName = roleNameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAttachedRolePolicies(request)
        val attachedPolicies = response.attachedPolicies

        // Ensure that the policy is not attached to this role.
        val checkStatus: Int
        if (attachedPolicies != null) {
            checkStatus = checkList(attachedPolicies, policyArnVal)
            if (checkStatus == -1)
                return
        }

        val policyRequest = AttachRolePolicyRequest {
            roleName = roleNameVal
```

```
            policyArn = policyArnVal
        }
        iamClient.attachRolePolicy(policyRequest)
        println("Successfully attached policy $policyArnVal to role
 $roleNameVal")
    }
}

fun checkList(attachedPolicies: List<AttachedPolicy>, policyArnVal: String): Int
 {

    for (policy in attachedPolicies) {
        val polArn = policy.policyArn.toString()

        if (polArn.compareTo(policyArnVal) == 0) {
            println("The policy is already attached to this role.")
            return -1
        }
    }
    return 0
}
```

- Para obter detalhes da API, consulte a AttachRolePolicyreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
```

```
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
echo "Created role: {$assumeRoleRole['RoleName']}\n";

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";

$service->attachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);

    public function attachRolePolicy($roleName, $policyArn)
    {
        return $this->customWaiter(function () use ($roleName, $policyArn) {
            $this->iamClient->attachRolePolicy([
                'PolicyArn' => $policyArn,
                'RoleName' => $roleName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Anexar uma política a uma função usando o objeto Policy do Boto3.

```
def attach_to_role(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Policy(policy_arn).attach_role(RoleName=role_name)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise
```

Anexar uma política a uma função usando o objeto Role do Boto3.

```
def attach_policy(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
```

```
        iam.Role(role_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise
```

- Para obter detalhes da API, consulte a AttachRolePolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
```

```
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end
```

```
  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn attach_role_policy(
    client: &iamClient,
    role: &Role,
    policy: &Policy,
) -> Result<AttachRolePolicyOutput, SdkError<AttachRolePolicyError>> {
    client
        .attach_role_policy()
        .role_name(role.role_name())
        .policy_arn(policy.arn().unwrap_or_default())
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a AttachRolePolicyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func attachRolePolicy(role: String, policyArn: String) async throws {
    let input = AttachRolePolicyInput(
        policyArn: policyArn,
        roleName: role
    )
    do {
        _ = try await client.attachRolePolicy(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte AttachRolePolicya referência da API AWS SDK for Swift.

Anexar uma política do IAM a um usuário usando um AWS SDK

Os exemplos de código a seguir mostram como anexar uma política do IAM a um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar usuários somente leitura e leitura/gravação usando

CLI

AWS CLI

Como anexar uma política gerenciada a um usuário do IAM

O comando `attach-user-policy`, apresentado a seguir, anexa a política gerenciada pela AWS denominada `AdministratorAccess` ao usuário do IAM denominado `Alice`.

```
aws iam attach-user-policy \
    --policy-arn arn:aws:iam::aws:policy/AdministratorAccess \
    --user-name Alice
```

Este comando não produz saída.

Para obter mais informações, consulte Políticas gerenciadas e em linha no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte AttachUserPolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def attach_policy(user_name, policy_arn):
    """
    Attaches a policy to a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to user %s.", policy_arn, user_name)
```

```
    except ClientError:
        logger.exception("Couldn't attach policy %s to user %s.", policy_arn,
user_name)
        raise
```

- Para obter detalhes da API, consulte a AttachUserPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Attaches a policy to a user
#
# @param user_name [String] The name of the user
# @param policy_arn [String] The Amazon Resource Name (ARN) of the policy
# @return [Boolean] true if successful, false otherwise
def attach_policy_to_user(user_name, policy_arn)
  @iam_client.attach_user_policy(
    user_name: user_name,
    policy_arn: policy_arn
  )
  true
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error attaching policy to user: #{e.message}")
  false
end
```

- Para obter detalhes da API, consulte AttachUserPolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn attach_user_policy(
    client: &iamClient,
    user_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .attach_user_policy()
        .user_name(user_name)
        .policy_arn(policy_arn)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a AttachUserPolicyreferência da API AWS SDK for Rust.

Anexar uma política em linha a um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como anexar uma política em linha a um perfil do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the inline policy document embedded in a role.
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string
 roleName, string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::putRolePolicy(
        const Aws::String &roleName,
        const Aws::String &policyName,
        const Aws::String &policyDocument,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iamClient(clientConfig);
    Aws::IAM::Model::PutRolePolicyRequest request;

    request.SetRoleName(roleName);
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(policyDocument);

    Aws::IAM::Model::PutRolePolicyOutcome outcome =
 iamClient.PutRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error putting policy on role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully put the role policy." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como anexar uma política de permissões a um perfil do IAM

O comando `put-role-policy`, apresentado a seguir, adiciona uma política de permissões ao perfil denominada `Test-Role`.

```
aws iam put-role-policy \
    --role-name Test-Role \
    --policy-name ExamplePolicy \
    --policy-document file://AdminPolicy.json
```

Este comando não produz saída.

A política é definida como um documento JSON no AdminPolicyarquivo.json. (O nome e a extensão do arquivo não têm significado.)

Para anexar uma política de confiança a um perfil, use o comando `update-assume-role-policy`.

Para obter mais informações, consulte Modificar um perfil no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte PutRolePolicyem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { PutRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const examplePolicyDocument = JSON.stringify({
  Version: "2012-10-17",
  Statement: [
    {
```

```
      Sid: "VisualEditor0",
      Effect: "Allow",
      Action: [
        "s3:ListBucketMultipartUploads",
        "s3:ListBucketVersions",
        "s3:ListBucket",
        "s3:ListMultipartUploadParts",
      ],
      Resource: "arn:aws:s3:::some-test-bucket",
    },
    {
      Sid: "VisualEditor1",
      Effect: "Allow",
      Action: [
        "s3:ListStorageLensConfigurations",
        "s3:ListAccessPointsForObjectLambda",
        "s3:ListAllMyBuckets",
        "s3:ListAccessPoints",
        "s3:ListJobs",
        "s3:ListMultiRegionAccessPoints",
      ],
      Resource: "*",
    },
  ],
});

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 * @param {string} policyName
 * @param {string} policyDocument
 */
export const putRolePolicy = async (roleName, policyName, policyDocument) => {
  const command = new PutRolePolicyCommand({
    RoleName: roleName,
    PolicyName: policyName,
    PolicyDocument: policyDocument,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
```

```
};
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for JavaScript da API.

Criar um provedor SAML do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como criar um provedor SAML do AWS Identity and Access Management (IAM).

CLI

AWS CLI

Como criar um provedor SAML

Este exemplo cria um novo provedor SAML no IAM denominado `MySAMLProvider`. Ele é descrito pelo documento de metadados do SAML, que encontra-se no arquivo `SAMLMetaData.xml`.

```
aws iam create-saml-provider \
    --saml-metadata-document file://SAMLMetaData.xml \
    --name MySAMLProvider
```

Saída:

```
{
    "SAMLProviderArn": "arn:aws:iam::123456789012:saml-provider/MySAMLProvider"
}
```

Para obter mais informações, consulte Criação de provedores de identidade SAML do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateSAMLProvider na Referência de comandos da AWS CLI.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateSAMLProviderCommand, IAMClient } from "@aws-sdk/client-iam";
import { readFileSync } from "fs";
import * as path from "path";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";

const client = new IAMClient({});

/**
 * This sample document was generated using Auth0.
 * For more information on generating this document,
 see https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_providers_create_saml.html#samlstep1.
 */
const sampleMetadataDocument = readFileSync(
  path.join(
    dirnameFromMetaUrl(import.meta.url),
    "../../../../resources/sample_files/sample_saml_metadata.xml",
  ),
);

/**
 *
 * @param {*} providerName
 * @returns
 */
export const createSAMLProvider = async (providerName) => {
  const command = new CreateSAMLProviderCommand({
    Name: providerName,
    SAMLMetadataDocument: sampleMetadataDocument.toString(),
  });

  const response = await client.send(command);
```

```
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte CreateSAMLProvider na Referência da API do AWS SDK for JavaScript.

Criar um grupo do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar um grupo do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
 { GroupName = groupName });
        return response.Group;
    }
```

- Para obter detalhes da API, consulte CreateGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para criar um grupo do IAM

O comando `create-group`, apresentado a seguir, cria um grupo do IAM denominado `Admins`.

```
aws iam create-group \
    --group-name Admins
```

Saída:

```
{
    "Group": {
        "Path": "/",
        "CreateDate": "2015-03-09T20:30:24.940Z",
        "GroupId": "AIDGPMS9RO4H3FEXAMPLE",
        "Arn": "arn:aws:iam::123456789012:group/Admins",
        "GroupName": "Admins"
    }
}
```

Para obter mais informações, consulte Criação de grupos de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateGroupem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateGroupCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} groupName
 */
export const createGroup = async (groupName) => {
  const command = new CreateGroupCommand({ GroupName: groupName });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte CreateGroupa Referência AWS SDK for JavaScript da API.

Criar uma política do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando
- Políticas gerenciadas
- Trabalhar com a API IAM Policy Builder

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</
param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
 policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new
 CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });

        return response.Policy;
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_policy
#
# This function creates an IAM policy.
#
# Parameters:
#       -n policy_name -- The name of the IAM policy.
#       -p policy_json -- The policy document.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_policy() {
  local policy_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_policy"
    echo "Creates an AWS Identity and Access Management (IAM) policy."
    echo "  -n policy_name   The name of the IAM policy."
    echo "  -p policy_json -- The policy document."
```

```
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) policy_name="${OPTARG}" ;;
    p) policy_document="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$policy_name" ]]; then
  errecho "ERROR: You must provide a policy name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_document" ]]; then
  errecho "ERROR: You must provide a policy document with the -p parameter."
  usage
  return 1
fi

response=$(aws iam create-policy \
  --policy-name "$policy_name" \
  --policy-document "$policy_document" \
  --output text \
  --query Policy.Arn)

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports create-policy operation failed.\n$response"
```

```
    return 1
  fi

  echo "$response"
}
```

- Para obter detalhes da API, consulte CreatePolicyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createPolicy(const Aws::String &policyName,
                                      const Aws::String &rsrcArn,
                                      const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreatePolicyRequest request;
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(BuildSamplePolicyDocument(rsrcArn));

    Aws::IAM::Model::CreatePolicyOutcome outcome = iam.CreatePolicy(request);
    Aws::String result;
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating policy " << policyName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        result = outcome.GetResult().GetPolicy().GetArn();
        std::cout << "Successfully created policy " << policyName <<
                  std::endl;
    }

    return result;
```

```
}

Aws::String AwsDoc::IAM::BuildSamplePolicyDocument(const Aws::String &rsrc_arn) {
    std::stringstream stringStream;
    stringStream << "{"
                 << "  \"Version\": \"2012-10-17\","
                 << "  \"Statement\": ["
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": \"logs:CreateLogGroup\","
                 << "        \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    },"
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": ["
                 << "            \"dynamodb:DeleteItem\","
                 << "            \"dynamodb:GetItem\","
                 << "            \"dynamodb:PutItem\","
                 << "            \"dynamodb:Scan\","
                 << "            \"dynamodb:UpdateItem\""
                 << "       ],"
                 << "       \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    }"
                 << "   ]"
                 << "}";

    return stringStream.str();
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar uma política gerenciada pelo cliente

O comando apresentado a seguir cria uma política gerenciada pelo cliente denominada `my-policy`.

```
aws iam create-policy \
    --policy-name my-policy \
    --policy-document file://policy
```

O arquivo `policy` é um documento JSON na pasta atual que concede acesso somente leitura à pasta `shared` em um bucket do Amazon S3 denominado `my-bucket`.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "s3:Get*",
                "s3:List*"
            ],
            "Resource": [
                "arn:aws:s3:::my-bucket/shared/*"
            ]
        }
    ]
}
```

Saída:

```
{
    "Policy": {
        "PolicyName": "my-policy",
        "CreateDate": "2015-06-01T19:31:18.620Z",
        "AttachmentCount": 0,
        "IsAttachable": true,
        "PolicyId": "ZXR6A36LTYANPAI7NJ5UV",
        "DefaultVersionId": "v1",
        "Path": "/",
        "Arn": "arn:aws:iam::0123456789012:policy/my-policy",
        "UpdateDate": "2015-06-01T19:31:18.620Z"
    }
}
```

Para obter mais informações sobre como usar arquivos como entrada para parâmetros de string, consulte Especificar valores de parâmetro para a AWS CLI no Guia do usuário da AWS CLI.

Exemplo 2: como criar uma política gerenciada pelo cliente com uma descrição

O seguinte comando cria uma política gerenciada pelo cliente denominada `my-policy` com uma descrição imutável:

```
aws iam create-policy \
    --policy-name my-policy \
    --policy-document file://policy.json \
    --description "This policy grants access to all Put, Get, and List actions
 for my-bucket"
```

O arquivo `policy.json` é um documento JSON na pasta atual que concede acesso a todas as ações Put, List e Get para um bucket do Amazon S3 denominado `my-bucket`.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                 "s3:ListBucket*",
                 "s3:PutBucket*",
                 "s3:GetBucket*"
             ],
             "Resource": [
                 "arn:aws:s3:::my-bucket"
             ]
         }
     ]
 }
```

Saída:

```
{
    "Policy": {
        "PolicyName": "my-policy",
        "PolicyId": "ANPAWGSUGIDPEXAMPLE",
```

```
        "Arn": "arn:aws:iam::123456789012:policy/my-policy",
        "Path": "/",
        "DefaultVersionId": "v1",
        "AttachmentCount": 0,
        "PermissionsBoundaryUsageCount": 0,
        "IsAttachable": true,
        "CreateDate": "2023-05-24T22:38:47+00:00",
        "UpdateDate": "2023-05-24T22:38:47+00:00"
    }
}
```

Para obter mais informações sobre as políticas baseadas em identidade, consulte Políticas baseadas em identidade e em recurso no Guia do usuário do AWS IAM.

Exemplo 3: como criar uma política gerenciada pelo cliente com etiquetas

O comando apresentado a seguir cria uma política gerenciada pelo cliente, denominada `my-policy`, com etiquetas. Este exemplo usa o sinalizador de parâmetro `--tags` com as seguintes etiquetas formatadas em JSON: `'{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location", "Value": "Seattle"}'`. Como alternativa, o sinalizador `--tags` pode ser usado com etiquetas no formato abreviado: `'Key=Department,Value=Accounting Key=Location,Value=Seattle'`.

```
aws iam create-policy \
    --policy-name my-policy \
    --policy-document file://policy.json \
    --tags '{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location",
 "Value": "Seattle"}'
```

O arquivo `policy.json` é um documento JSON na pasta atual que concede acesso a todas as ações Put, List e Get para um bucket do Amazon S3 denominado `my-bucket`.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                 "s3:ListBucket*",
                 "s3:PutBucket*",
                 "s3:GetBucket*"
```

```
            ],
            "Resource": [
                "arn:aws:s3:::my-bucket"
            ]
        }
    ]
}
```

Saída:

```
{
    "Policy": {
        "PolicyName": "my-policy",
        "PolicyId": "ANPAWGSUGIDPEXAMPLE",
        "Arn": "arn:aws:iam::12345678012:policy/my-policy",
        "Path": "/",
        "DefaultVersionId": "v1",
        "AttachmentCount": 0,
        "PermissionsBoundaryUsageCount": 0,
        "IsAttachable": true,
        "CreateDate": "2023-05-24T23:16:39+00:00",
        "UpdateDate": "2023-05-24T23:16:39+00:00",
        "Tags": [
            {
                "Key": "Department",
                "Value": "Accounting"
            },
                "Key": "Location",
                "Value": "Seattle"
            {

        ]
    }
}
```

Para obter mais informações sobre as políticas de marcação, consulte Marcar políticas gerenciadas pelo cliente no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreatePolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// CreatePolicy creates a policy that grants a list of actions to the specified
 resource.
// PolicyDocument shows how to work with a policy document as a data structure
 and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper PolicyWrapper) CreatePolicy(policyName string, actions []string,
  resourceArn string) (*types.Policy, error) {
 var policy *types.Policy
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(resourceArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n",
 resourceArn, err)
  return nil, err
```

```
 }
 result, err := wrapper.IamClient.CreatePolicy(context.TODO(),
 &iam.CreatePolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
 })
 if err != nil {
  log.Printf("Couldn't create policy %v. Here's why: %v\n", policyName, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.services.iam.model.CreatePolicyRequest;
import software.amazon.awssdk.services.iam.model.CreatePolicyResponse;
import software.amazon.awssdk.services.iam.model.GetPolicyRequest;
import software.amazon.awssdk.services.iam.model.GetPolicyResponse;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.waiters.IamWaiter;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreatePolicy {

    public static final String PolicyDocument = "{" +
            "  \"Version\": \"2012-10-17\"," +
            "  \"Statement\": [" +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Action\": [" +
            "            \"dynamodb:DeleteItem\"," +
            "            \"dynamodb:GetItem\"," +
            "            \"dynamodb:PutItem\"," +
            "            \"dynamodb:Scan\"," +
            "            \"dynamodb:UpdateItem\"" +
            "        ]," +
            "        \"Resource\": \"*\"" +
            "    }" +
            "   ]" +
            "}";

    public static void main(String[] args) {

        final String usage = """
                Usage:
                    CreatePolicy <policyName>\s

                Where:
                    policyName - A unique policy name.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String policyName = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();
```

```
        String result = createIAMPolicy(iam, policyName);
        System.out.println("Successfully created a policy with this ARN value: "
 + result);
        iam.close();
    }

    public static String createIAMPolicy(IamClient iam, String policyName) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();

            CreatePolicyRequest request = CreatePolicyRequest.builder()
                    .policyName(policyName)
                    .policyDocument(PolicyDocument)
                    .build();

            CreatePolicyResponse response = iam.createPolicy(request);

            // Wait until the policy is created.
            GetPolicyRequest polRequest = GetPolicyRequest.builder()
                    .policyArn(response.policy().arn())
                    .build();

            WaiterResponse<GetPolicyResponse> waitUntilPolicyExists =
 iamWaiter.waitUntilPolicyExists(polRequest);

 waitUntilPolicyExists.matched().response().ifPresent(System.out::println);
            return response.policy().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a política do

```
import { CreatePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyName
 */
export const createPolicy = (policyName) => {
  const command = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: "*",
          Resource: "*",
        },
      ],
    }),
    PolicyName: policyName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var myManagedPolicy = {
  Version: "2012-10-17",
  Statement: [
    {
      Effect: "Allow",
      Action: "logs:CreateLogGroup",
      Resource: "RESOURCE_ARN",
    },
    {
      Effect: "Allow",
      Action: [
        "dynamodb:DeleteItem",
        "dynamodb:GetItem",
        "dynamodb:PutItem",
        "dynamodb:Scan",
        "dynamodb:UpdateItem",
      ],
      Resource: "RESOURCE_ARN",
    },
  ],
};

var params = {
  PolicyDocument: JSON.stringify(myManagedPolicy),
```

```
  PolicyName: "myDynamoDBPolicy",
};

iam.createPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMPolicy(policyNameVal: String?): String {

    val policyDocumentVal = "{" +
        "  \"Version\": \"2012-10-17\"," +
        "  \"Statement\": [" +
        "    {" +
        "        \"Effect\": \"Allow\"," +
        "        \"Action\": [" +
        "            \"dynamodb:DeleteItem\"," +
        "            \"dynamodb:GetItem\"," +
        "            \"dynamodb:PutItem\"," +
        "            \"dynamodb:Scan\"," +
        "            \"dynamodb:UpdateItem\"" +
        "        ]," +
```

```
        "       \"Resource\": \"*\"" +
        "    }" +
        "   ]" +
        "}"

    val request = CreatePolicyRequest {
        policyName = policyNameVal
        policyDocument = policyDocumentVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createPolicy(request)
        return response.policy?.arn.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreatePolicyreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";
```

```
    public function createPolicy(string $policyName, string $policyDocument)
    {
        $result = $this->customWaiter(function () use ($policyName,
 $policyDocument) {
            return $this->iamClient->createPolicy([
                'PolicyName' => $policyName,
                'PolicyDocument' => $policyDocument,
            ]);
        });
        return $result['Policy'];
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy(name, description, actions, resource_arn):
    """
    Creates a policy that contains a single statement.

    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this
 policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all
 objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
```

```
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a CreatePolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
```

```
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
```

```
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_policy(
    client: &iamClient,
    policy_name: &str,
    policy_document: &str,
) -> Result<Policy, iamError> {
    let policy = client
        .create_policy()
        .policy_name(policy_name)
        .policy_document(policy_document)
        .send()
        .await?;
    Ok(policy.policy.unwrap())
}
```

- Para obter detalhes da API, consulte a CreatePolicyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func createPolicy(name: String, policyDocument: String) async throws -
> IAMClientTypes.Policy {
        let input = CreatePolicyInput(
            policyDocument: policyDocument,
            policyName: name
        )
        do {
            let output = try await iamClient.createPolicy(input: input)
            guard let policy = output.policy else {
                throw ServiceHandlerError.noSuchPolicy
            }
            return policy
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte CreatePolicya referência da API AWS SDK for Swift.

Criar uma versão de política do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como criar uma versão da política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Políticas gerenciadas

CLI

AWS CLI

Como criar uma nova versão de uma política gerenciada

Este exemplo cria uma nova versão `v2` da política do IAM cujo ARN é `arn:aws:iam::123456789012:policy/MyPolicy` e a torna a versão padrão.

```
aws iam create-policy-version \
    --policy-arn arn:aws:iam::123456789012:policy/MyPolicy \
    --policy-document file://NewPolicyVersion.json \
    --set-as-default
```

Saída:

```
{
    "PolicyVersion": {
        "CreateDate": "2015-06-16T18:56:03.721Z",
        "VersionId": "v2",
        "IsDefaultVersion": true
    }
}
```

Para obter mais informações, consulte Versionamento de políticas do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreatePolicyVersionem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy_version(policy_arn, actions, resource_arn, set_as_default):
```

```
    """
    Creates a policy version. Policies can have up to five versions. The default
    version is the one that is used for all resources that reference the policy.

    :param policy_arn: The ARN of the policy.
    :param actions: The actions to allow in the policy version.
    :param resource_arn: The ARN of the resource this policy version applies to.
    :param set_as_default: When True, this policy version is set as the default
                           version for the policy. Otherwise, the default
                           is not changed.
    :return: The newly created policy version.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
resource_arn}],
    }
    try:
        policy = iam.Policy(policy_arn)
        policy_version = policy.create_version(
            PolicyDocument=json.dumps(policy_doc), SetAsDefault=set_as_default
        )
        logger.info(
            "Created policy version %s for policy %s.",
            policy_version.version_id,
            policy_version.arn,
        )
    except ClientError:
        logger.exception("Couldn't create a policy version for %s.", policy_arn)
        raise
    else:
        return policy_version
```

- Para obter detalhes da API, consulte a CreatePolicyVersionReferência da API AWSSDK for Python (Boto3).

Criar um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar um perfil do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Gerenciar funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
    public async Task<string> CreateRoleAsync(string roleName, string
rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_role
#
# This function creates an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_json -- The assume role policy document.
#
# Returns:
#       The ARN of the role.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_role() {
  local role_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) role."
```

```
  echo "  -n role_name   The name of the IAM role."
  echo "  -p policy_json -- The assume role policy document."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) role_name="${OPTARG}" ;;
    p) policy_document="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$role_name" ]]; then
  errecho "ERROR: You must provide a role name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_document" ]]; then
  errecho "ERROR: You must provide a policy document with the -p parameter."
  usage
  return 1
fi

response=$(aws iam create-role \
  --role-name "$role_name" \
  --assume-role-policy-document "$policy_document" \
  --output text \
  --query Role.Arn)

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
```

```
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-role operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateRoleem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::createIamRole(
        const Aws::String &roleName,
        const Aws::String &policy,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::CreateRoleRequest request;

    request.SetRoleName(roleName);
    request.SetAssumeRolePolicyDocument(policy);

    Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const Aws::IAM::Model::Role iamRole = outcome.GetResult().GetRole();
        std::cout << "Created role " << iamRole.GetRoleName() << "\n";
        std::cout << "ID: " << iamRole.GetRoleId() << "\n";
```

```
        std::cout << "ARN: " << iamRole.GetArn() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar um perfil do IAM

O comando `create-role`, apresentado a seguir, cria um perfil, denominado `Test-Role`, e anexa uma política de confiança a ele.

```
aws iam create-role \
    --role-name Test-Role \
    --assume-role-policy-document file://Test-Role-Trust-Policy.json
```

Saída:

```
{
    "Role": {
        "AssumeRolePolicyDocument": "<URL-encoded-JSON>",
        "RoleId": "AKIAIOSFODNN7EXAMPLE",
        "CreateDate": "2013-06-07T20:43:32.821Z",
        "RoleName": "Test-Role",
        "Path": "/",
        "Arn": "arn:aws:iam::123456789012:role/Test-Role"
    }
}
```

A política de confiança é definida como um documento JSON no arquivo Test-Role-Trust-Policy.json. (O nome e a extensão do arquivo não têm significado.) A política de confiança deve especificar uma entidade principal.

Para anexar uma política de permissões a um perfil, use o comando `put-role-policy`.

Para obter mais informações, consulte Criação de perfis do IAM no Guia do usuário do AWS IAM.

Exemplo 2: como criar um perfil do IAM com a duração máxima da sessão especificada

O comando `create-role`, apresentado a seguir, cria um perfil denominado `Test-Role` e define a duração máxima da sessão como 7.200 segundos (duas horas).

```
aws iam create-role \
    --role-name Test-Role \
    --assume-role-policy-document file://Test-Role-Trust-Policy.json \
    --max-session-duration 7200
```

Saída:

```
{
    "Role": {
        "Path": "/",
        "RoleName": "Test-Role",
        "RoleId": "AKIAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::12345678012:role/Test-Role",
        "CreateDate": "2023-05-24T23:50:25+00:00",
        "AssumeRolePolicyDocument": {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Sid": "Statement1",
                    "Effect": "Allow",
                    "Principal": {
                        "AWS": "arn:aws:iam::12345678012:root"
                    },
                    "Action": "sts:AssumeRole"
                }
            ]
        }
    }
}
```

Para obter mais informações, consulte Modificar a duração máxima da sessão de um perfil (API da AWS) no Guia do usuário do AWS IAM.

Exemplo 3: como criar um perfil do IAM com etiquetas

O comando apresentado a seguir cria um perfil do IAM `Test-Role` com etiquetas. Este exemplo usa o sinalizador de parâmetro `--tags` com as seguintes etiquetas formatadas em JSON: `'{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location", "Value": "Seattle"}'`. Como alternativa, o sinalizador `--tags` pode ser usado com etiquetas no formato abreviado: `'Key=Department,Value=Accounting Key=Location,Value=Seattle'`.

```
aws iam create-role \
    --role-name Test-Role \
    --assume-role-policy-document file://Test-Role-Trust-Policy.json \
    --tags '{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location",
 "Value": "Seattle"}'
```

Saída:

```
{
    "Role": {
        "Path": "/",
        "RoleName": "Test-Role",
        "RoleId": "AKIAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::123456789012:role/Test-Role",
        "CreateDate": "2023-05-25T23:29:41+00:00",
        "AssumeRolePolicyDocument": {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Sid": "Statement1",
                    "Effect": "Allow",
                    "Principal": {
                        "AWS": "arn:aws:iam::123456789012:root"
                    },
                    "Action": "sts:AssumeRole"
                }
            ]
        },
        "Tags": [
            {
                "Key": "Department",
                "Value": "Accounting"
            },
            {
                "Key": "Location",
```

```
                "Value": "Seattle"
            }
        ]
    }
}
```

Para obter mais informações, consulte Marcar perfis do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateRoleem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// CreateRole creates a role that trusts a specified user. The trusted user can
 assume
// the role to acquire its permissions.
// PolicyDocument shows how to work with a policy document as a data structure
 and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper RoleWrapper) CreateRole(roleName string, trustedUserArn string)
 (*types.Role, error) {
 var role *types.Role
 trustPolicy := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
```

```
    Effect: "Allow",
    Principal: map[string]string{"AWS": trustedUserArn},
    Action: []string{"sts:AssumeRole"},
   }},
  }
  policyBytes, err := json.Marshal(trustPolicy)
  if err != nil {
   log.Printf("Couldn't create trust policy for %v. Here's why: %v\n",
  trustedUserArn, err)
   return nil, err
  }
  result, err := wrapper.IamClient.CreateRole(context.TODO(),
  &iam.CreateRoleInput{
   AssumeRolePolicyDocument: aws.String(string(policyBytes)),
   RoleName:                 aws.String(roleName),
  })
  if err != nil {
   log.Printf("Couldn't create role %v. Here's why: %v\n", roleName, err)
  } else {
   role = result.Role
  }
  return role, err
 }
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import org.json.simple.JSONObject;
import org.json.simple.parser.JSONParser;
import software.amazon.awssdk.services.iam.model.CreateRoleRequest;
import software.amazon.awssdk.services.iam.model.CreateRoleResponse;
```

```
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import java.io.FileReader;

/*
*   This example requires a trust policy document. For more information, see:
*   https://aws.amazon.com/blogs/security/how-to-use-trust-policies-with-iam-
roles/
*
*
*  In addition, set up your development environment, including your credentials.
*
*  For information, see this documentation topic:
*
*  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class CreateRole {
    public static void main(String[] args) throws Exception {
        final String usage = """
                Usage:
                    <rolename> <fileLocation>\s

                Where:
                    rolename - The name of the role to create.\s
                    fileLocation - The location of the JSON document that
 represents the trust policy.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String rolename = args[0];
        String fileLocation = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String result = createIAMRole(iam, rolename, fileLocation);
```

```
        System.out.println("Successfully created user: " + result);
        iam.close();
    }

    public static String createIAMRole(IamClient iam, String rolename, String
 fileLocation) throws Exception {
        try {
            JSONObject jsonObject = (JSONObject)
 readJsonSimpleDemo(fileLocation);
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(jsonObject.toJSONString())
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            System.out.println("The ARN of the role is " +
 response.role().arn());

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static Object readJsonSimpleDemo(String filename) throws Exception {
        FileReader reader = new FileReader(filename);
        JSONParser jsonParser = new JSONParser();
        return jsonParser.parse(reader);
    }
}
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a função.

```
import { CreateRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const createRole = (roleName) => {
  const command = new CreateRoleCommand({
    AssumeRolePolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Principal: {
            Service: "lambda.amazonaws.com",
          },
          Action: "sts:AssumeRole",
        },
      ],
    }),
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
echo "Created role: {$assumeRoleRole['RoleName']}\n";

    /**
     * @param string $roleName
     * @param string $rolePolicyDocument
     * @return array
     * @throws AwsException
     */
    public function createRole(string $roleName, string $rolePolicyDocument)
    {
        $result = $this->customWaiter(function () use ($roleName,
 $rolePolicyDocument) {
            return $this->iamClient->createRole([
                'AssumeRolePolicyDocument' => $rolePolicyDocument,
                'RoleName' => $roleName,
```

```
            ]);
        });
        return $result['Role'];
    }
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_role(role_name, allowed_services):
    """
    Creates a role that lets a list of specified services assume the role.

    :param role_name: The name of the role.
    :param allowed_services: The services that can assume the role.
    :return: The newly created role.
    """
    trust_policy = {
        "Version": "2012-10-17",
        "Statement": [
            {
                "Effect": "Allow",
                "Principal": {"Service": service},
                "Action": "sts:AssumeRole",
            }
            for service in allowed_services
        ],
    }

    try:
        role = iam.create_role(
            RoleName=role_name, AssumeRolePolicyDocument=json.dumps(trust_policy)
```

```
        )
        logger.info("Created role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create role %s.", role_name)
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a CreateRoleReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Creates a role and attaches policies to it.
 #
 # @param role_name [String] The name of the role.
 # @param assume_role_policy_document [Hash] The trust relationship policy
document.
 # @param policy_arns [Array<String>] The ARNs of the policies to attach.
 # @return [String, nil] The ARN of the new role if successful, or nil if an
error occurred.
 def create_role(role_name, assume_role_policy_document, policy_arns)
   response = @iam_client.create_role(
     role_name: role_name,
     assume_role_policy_document: assume_role_policy_document.to_json
   )
   role_arn = response.role.arn

   policy_arns.each do |policy_arn|
     @iam_client.attach_role_policy(
```

```
        role_name: role_name,
        policy_arn: policy_arn
      )
    end

    role_arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating role: #{e.message}")
    nil
  end
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_role(
    client: &iamClient,
    role_name: &str,
    role_policy_document: &str,
) -> Result<Role, iamError> {
    let response: CreateRoleOutput = loop {
        if let Ok(response) = client
            .create_role()
            .role_name(role_name)
            .assume_role_policy_document(role_policy_document)
            .send()
            .await
        {
            break response;
        }
    };

    Ok(response.role.unwrap())
```

```
}
```

- Para obter detalhes da API, consulte a CreateRolereferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createRole(name: String, policyDocument: String) async throws ->
String {
       let input = CreateRoleInput(
           assumeRolePolicyDocument: policyDocument,
           roleName: name
       )
       do {
           let output = try await client.createRole(input: input)
           guard let role = output.role else {
               throw ServiceHandlerError.noSuchRole
           }
           guard let id = role.roleId else {
               throw ServiceHandlerError.noSuchRole
           }
           return id
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreateRolea referência da API AWS SDK for Swift.

Criar uma função vinculada ao serviço do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma função vinculada ao serviço do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName,
 string description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
    }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar um perfil vinculado ao serviço

O exemplo que usa `create-service-linked-role`, apresentado a seguir, cria um perfil vinculado ao serviço para o serviço da AWS especificado e anexa a descrição especificada.

```
aws iam create-service-linked-role \
    --aws-service-name lex.amazonaws.com \
    --description "My service-linked role to support Lex"
```

Saída:

```
{
    "Role": {
        "Path": "/aws-service-role/lex.amazonaws.com/",
        "RoleName": "AWSServiceRoleForLexBots",
        "RoleId": "AROA1234567890EXAMPLE",
        "Arn": "arn:aws:iam::1234567890:role/aws-service-role/lex.amazonaws.com/
AWSServiceRoleForLexBots",
        "CreateDate": "2019-04-17T20:34:14+00:00",
        "AssumeRolePolicyDocument": {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Action": [
                        "sts:AssumeRole"
                    ],
                    "Effect": "Allow",
                    "Principal": {
                        "Service": [
                            "lex.amazonaws.com"
                        ]
                    }
                }
            ]
        }
```

```
    }
}
```

Para obter mais informações, consulte Usar perfis vinculados ao serviço no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateServiceLinkedRoleem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// CreateServiceLinkedRole creates a service-linked role that is owned by the
 specified service.
func (wrapper RoleWrapper) CreateServiceLinkedRole(serviceName string,
 description string) (*types.Role, error) {
 var role *types.Role
 result, err := wrapper.IamClient.CreateServiceLinkedRole(context.TODO(),
 &iam.CreateServiceLinkedRoleInput{
  AWSServiceName: aws.String(serviceName),
  Description:    aws.String(description),
 })
 if err != nil {
  log.Printf("Couldn't create service-linked role %v. Here's why: %v\n",
 serviceName, err)
```

```
 } else {
  role = result.Role
 }
 return role, err
}
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma função vinculada ao serviço.

```
import { CreateServiceLinkedRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} serviceName
 */
export const createServiceLinkedRole = async (serviceName) => {
  const command = new CreateServiceLinkedRoleCommand({
    // For a list of AWS services that support service-linked roles,
    // see https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_aws-
services-that-work-with-iam.html.
    //
    // For a list of AWS service endpoints, see https://docs.aws.amazon.com/
general/latest/gr/aws-service-information.html.
    AWSServiceName: serviceName,
  });
```

```
  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function createServiceLinkedRole($awsServiceName, $customSuffix = "",
 $description = "")
    {
        $createServiceLinkedRoleArguments = ['AWSServiceName' =>
 $awsServiceName];
        if ($customSuffix) {
            $createServiceLinkedRoleArguments['CustomSuffix'] = $customSuffix;
        }
        if ($description) {
            $createServiceLinkedRoleArguments['Description'] = $description;
        }
        return $this->iamClient-
>createServiceLinkedRole($createServiceLinkedRoleArguments);
    }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_service_linked_role(service_name, description):
    """
    Creates a service-linked role.

    :param service_name: The name of the service that owns the role.
    :param description: A description to give the role.
    :return: The newly created role.
    """
    try:
        response = iam.meta.client.create_service_linked_role(
            AWSServiceName=service_name, Description=description
        )
        role = iam.Role(response["Role"]["RoleName"])
        logger.info("Created service-linked role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create service-linked role for %s.",
 service_name)
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a CreateServiceLinkedRoleReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Creates a service-linked role
 #
 # @param service_name [String] The service name to create the role for.
 # @param description [String] The description of the service-linked role.
 # @param suffix [String] Suffix for customizing role name.
 # @return [String] The name of the created role
 def create_service_linked_role(service_name, description, suffix)
   response = @iam_client.create_service_linked_role(
     aws_service_name: service_name, description: description, custom_suffix:
suffix,)
   role_name = response.role.role_name
   @logger.info("Created service-linked role #{role_name}.")
   role_name
 rescue Aws::Errors::ServiceError => e
   @logger.error("Couldn't create service-linked role for #{service_name}.
Here's why:")
   @logger.error("\t#{e.code}: #{e.message}")
   raise
 end
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_service_linked_role(
    client: &iamClient,
    aws_service_name: String,
    custom_suffix: Option<String>,
    description: Option<String>,
) -> Result<CreateServiceLinkedRoleOutput,
 SdkError<CreateServiceLinkedRoleError>> {
    let response = client
        .create_service_linked_role()
        .aws_service_name(aws_service_name)
        .set_custom_suffix(custom_suffix)
        .set_description(description)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a CreateServiceLinkedRolereferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createServiceLinkedRole(service: String, suffix: String? = nil,
description: String?)
                    async throws -> IAMClientTypes.Role {
       let input = CreateServiceLinkedRoleInput(
           awsServiceName: service,
           customSuffix: suffix,
           description: description
       )
       do {
           let output = try await client.createServiceLinkedRole(input: input)
           guard let role = output.role else {
               throw ServiceHandlerError.noSuchRole
           }
           return role
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea referência da API AWS SDK for Swift.

Criar um usuário do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM user.
    /// </summary>
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
{ UserName = userName });
        return response.User;
    }
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_user
#
# This function creates the specified IAM user, unless
# it already exists.
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       The ARN of the user.
```

```
#     And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_create_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user"
    echo "Creates an WS Identity and Access Management (IAM) user. You must
 supply a username:"
    echo "  -u user_name    The name of the user. It must be unique within the
 account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""
```

```
  # If the user already exists, we don't want to try to create it.
  if (iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name already exists in the account."
    return 1
  fi

  response=$(aws iam create-user --user-name "$user_name" \
    --output text \
    --query 'User.Arn')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-user operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateUserem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreateUserRequest create_request;
    create_request.SetUserName(userName);
```

```
    auto create_outcome = iam.CreateUser(create_request);
    if (!create_outcome.IsSuccess()) {
        std::cerr << "Error creating IAM user " << userName << ":" <<
                  create_outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created IAM user " << userName << std::endl;
    }

    return create_outcome.IsSuccess();
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar um usuário do IAM

O comando `create-user`, apresentado a seguir, cria um usuário do IAM denominado Bob na conta atual.

```
aws iam create-user \
    --user-name Bob
```

Saída:

```
{
    "User": {
        "UserName": "Bob",
        "Path": "/",
        "CreateDate": "2023-06-08T03:20:41.270Z",
        "UserId": "AIDAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::123456789012:user/Bob"
    }
}
```

Para obter mais informações, consulte Criar um usuário do IAM na sua conta da AWS no Guia do usuário do AWS IAM.

Exemplo 2: como criar um usuário do IAM em um caminho especificado

O comando `create-user`, apresentado a seguir, cria um usuário do IAM denominado Bob no caminho especificado.

```
aws iam create-user \
    --user-name Bob \
    --path /division_abc/subdivision_xyz/
```

Saída:

```
{
    "User": {
        "Path": "/division_abc/subdivision_xyz/",
        "UserName": "Bob",
        "UserId": "AIDAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::12345678012:user/division_abc/subdivision_xyz/Bob",
        "CreateDate": "2023-05-24T18:20:17+00:00"
    }
}
```

Para obter mais informações, consulte Identificadores do IAM no Guia do usuário do AWS IAM.

Exemplo 3: como criar um usuário do IAM com etiquetas

O comando `create-user`, apresentado a seguir, cria um usuário do IAM denominado Bob com etiquetas. Este exemplo usa o sinalizador de parâmetro `--tags` com as seguintes etiquetas formatadas em JSON: `'{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location", "Value": "Seattle"}'`. Como alternativa, o sinalizador `--tags` pode ser usado com etiquetas no formato abreviado: `'Key=Department,Value=Accounting Key=Location,Value=Seattle'`.

```
aws iam create-user \
    --user-name Bob \
    --tags '{"Key": "Department", "Value": "Accounting"}' '{"Key": "Location",
 "Value": "Seattle"}'
```

Saída:

```
{
    "User": {
        "Path": "/",
```

```
        "UserName": "Bob",
        "UserId": "AIDAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::12345678012:user/Bob",
        "CreateDate": "2023-05-25T17:14:21+00:00",
        "Tags": [
            {
                "Key": "Department",
                "Value": "Accounting"
            },
            {
                "Key": "Location",
                "Value": "Seattle"
            }
        ]
    }
}
```

Para obter mais informações, consulte Marcar usuários do IAM no Guia do usuário do AWS IAM.

Exemplo 4: como criar um usuário do IAM com um limite de permissões definido

O `create-user` comando a seguir cria um usuário do IAM chamado Bob com o limite de permissões do FullAccess AmazonS3.

```
aws iam create-user \
    --user-name Bob \
    --permissions-boundary arn:aws:iam::aws:policy/AmazonS3FullAccess
```

Saída:

```
{
    "User": {
        "Path": "/",
        "UserName": "Bob",
        "UserId": "AIDAIOSFODNN7EXAMPLE",
        "Arn": "arn:aws:iam::12345678012:user/Bob",
        "CreateDate": "2023-05-24T17:50:53+00:00",
        "PermissionsBoundary": {
        "PermissionsBoundaryType": "Policy",
        "PermissionsBoundaryArn": "arn:aws:iam::aws:policy/AmazonS3FullAccess"
        }
```

```
    }
}
```

Para obter mais informações, consulte Limites de permissões para entidades do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateUserem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateUser creates a new user with the specified name.
func (wrapper UserWrapper) CreateUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.CreateUser(context.TODO(),
 &iam.CreateUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create user %v. Here's why: %v\n", userName, err)
 } else {
  user = result.User
 }
 return user, err
}
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.services.iam.model.CreateUserRequest;
import software.amazon.awssdk.services.iam.model.CreateUserResponse;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.waiters.IamWaiter;
import software.amazon.awssdk.services.iam.model.GetUserRequest;
import software.amazon.awssdk.services.iam.model.GetUserResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <username>\s

                Where:
                    username - The name of the user to create.\s
```

```
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String username = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String result = createIAMUser(iam, username);
        System.out.println("Successfully created user: " + result);
        iam.close();
    }

    public static String createIAMUser(IamClient iam, String username) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();

            CreateUserRequest request = CreateUserRequest.builder()
                    .userName(username)
                    .build();

            CreateUserResponse response = iam.createUser(request);

            // Wait until the user is created.
            GetUserRequest userRequest = GetUserRequest.builder()
                    .userName(response.user().userName())
                    .build();

            WaiterResponse<GetUserResponse> waitUntilUserExists =
iamWaiter.waitUntilUserExists(userRequest);

waitUntilUserExists.matched().response().ifPresent(System.out::println);
            return response.user().userName();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o usuário.

```
import { CreateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} name
 */
export const createUser = (name) => {
  const command = new CreateUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    iam.createUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Success", data);
      }
    });
  } else {
    console.log(
      "User " + process.argv[2] + " already exists",
      data.User.UserId
    );
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMUser(usernameVal: String?): String? {

    val request = CreateUserRequest {
        userName = usernameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createUser(request)
        return response.user?.userName
    }
}
```

- Para obter detalhes da API, consulte a CreateUserreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
```

```
$service = new IAMService();

$user = $service->createUser("iam_demo_user_$uuid");
echo "Created user with the arn: {$user['Arn']}\n";


    /**
     * @param string $name
     * @return array
     * @throws AwsException
     */
    public function createUser(string $name): array
    {
        $result = $this->iamClient->createUser([
            'UserName' => $name,
        ]);

        return $result['User'];
    }
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_user(user_name):
    """
    Creates a user. By default, a user has no permissions or access keys.

    :param user_name: The name of the user.
    :return: The newly created user.
    """
    try:
        user = iam.create_user(UserName=user_name)
```

```
        logger.info("Created user %s.", user.name)
    except ClientError:
        logger.exception("Couldn't create user %s.", user_name)
        raise
    else:
        return user
```

- Para obter detalhes da API, consulte a CreateUserReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Creates a user and their login profile
 #
 # @param user_name [String] The name of the user
 # @param initial_password [String] The initial password for the user
 # @return [String, nil] The ID of the user if created, or nil if an error
occurred
 def create_user(user_name, initial_password)
   response = @iam_client.create_user(user_name: user_name)
   @iam_client.wait_until(:user_exists, user_name: user_name)
   @iam_client.create_login_profile(
     user_name: user_name,
     password: initial_password,
     password_reset_required: true
   )
   @logger.info("User '#{user_name}' created successfully.")
   response.user.user_id
 rescue Aws::IAM::Errors::EntityAlreadyExists
   @logger.error("Error creating user '#{user_name}': user already exists.")
```

```
    nil
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating user '#{user_name}': #{e.message}")
    nil
  end
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_user(client: &iamClient, user_name: &str) -> Result<User,
 iamError> {
    let response = client.create_user().user_name(user_name).send().await?;

    Ok(response.user.unwrap())
}
```

- Para obter detalhes da API, consulte a CreateUserreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func createUser(name: String) async throws -> String {
    let input = CreateUserInput(
        userName: name
    )
    do {
        let output = try await client.createUser(input: input)
        guard let user = output.user else {
            throw ServiceHandlerError.noSuchUser
        }
        guard let id = user.userId else {
            throw ServiceHandlerError.noSuchUser
        }
        return id
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte CreateUsera referência da API AWS SDK for Swift.

Criar uma chave de acesso do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma chave de acesso do Amazon IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando
- Gerenciar chaves de acesso

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
    /// key.</param>
    /// <returns>The AccessKey.</returns>
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
        var response = await _IAMService.CreateAccessKeyAsync(new
CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;

    }
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_user_access_key
#
# This function creates an IAM access key for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#       [-f file_name] -- The optional file name for the access key output.
#
# Returns:
#       [access_key_id access_key_secret]
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_user_access_key() {
  local user_name file_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) key pair."
```

```
  echo "  -u user_name   The name of the IAM user."
  echo "  [-f file_name]   Optional file name for the access key output."
  echo ""
}

# Retrieve the calling parameters.
while getopts "u:f:h" option; do
  case "${option}" in
    u) user_name="${OPTARG}" ;;
    f) file_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$user_name" ]]; then
  errecho "ERROR: You must provide a username with the -u parameter."
  usage
  return 1
fi

response=$(aws iam create-access-key \
  --user-name "$user_name" \
  --output text)

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports create-access-key operation failed.$response"
  return 1
fi

if [[ -n "$file_name" ]]; then
  echo "$response" >"$file_name"
fi
```

```
  local key_id key_secret
  # shellcheck disable=SC2086
  key_id=$(echo $response | cut -f 2 -d ' ')
  # shellcheck disable=SC2086
  key_secret=$(echo $response | cut -f 4 -d ' ')

  echo "$key_id $key_secret"

  return 0
}
```

- Para obter detalhes da API, consulte CreateAccessKeyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createAccessKey(const Aws::String &userName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreateAccessKeyRequest request;
    request.SetUserName(userName);

    Aws::String result;
    Aws::IAM::Model::CreateAccessKeyOutcome outcome =
 iam.CreateAccessKey(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating access key for IAM user " << userName
                  << ":" << outcome.GetError().GetMessage() << std::endl;
    }
```

```
    else {
        const auto &accessKey = outcome.GetResult().GetAccessKey();
        std::cout << "Successfully created access key for IAM user " <<
                  userName << std::endl << "  aws_access_key_id = " <<
                  accessKey.GetAccessKeyId() << std::endl <<
                  " aws_secret_access_key = " << accessKey.GetSecretAccessKey()
 <<
                  std::endl;
        result = accessKey.GetAccessKeyId();
    }

    return result;
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como criar uma chave de acesso para um usuário do IAM

O comando `create-access-key`, apresentado a seguir, cria uma chave de acesso (ID da chave de acesso e chave de acesso secreta) para o usuário do IAM denominado Bob.

```
aws iam create-access-key \
    --user-name Bob
```

Saída:

```
{
    "AccessKey": {
        "UserName": "Bob",
        "Status": "Active",
        "CreateDate": "2015-03-09T18:39:23.411Z",
        "SecretAccessKey": "wJalrXUtnFEMI/K7MDENG/bPxRfiCYzEXAMPLEKEY",
        "AccessKeyId": "AKIAIOSFODNN7EXAMPLE"
    }
}
```

Armazene a chave de acesso secreta em um local seguro. Se ela for perdida, não será possível recuperá-la e você deverá criar uma nova chave de acesso.

Para obter mais informações, consulte Gerenciamento de chaves de acesso de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateAccessKeyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateAccessKeyPair creates an access key for a user. The returned access key
 contains
// the ID and secret credentials needed to use the key.
func (wrapper UserWrapper) CreateAccessKeyPair(userName string)
 (*types.AccessKey, error) {
 var key *types.AccessKey
 result, err := wrapper.IamClient.CreateAccessKey(context.TODO(),
 &iam.CreateAccessKeyInput{
  UserName: aws.String(userName)})
 if err != nil {
  log.Printf("Couldn't create access key pair for user %v. Here's why: %v\n",
 userName, err)
 } else {
  key = result.AccessKey
```

```
 }
 return key, err
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.CreateAccessKeyRequest;
import software.amazon.awssdk.services.iam.model.CreateAccessKeyResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateAccessKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <user>\s
```

```
                Where:
                   user - An AWS IAM user that you can obtain from the AWS
 Management Console.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String user = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String keyId = createIAMAccessKey(iam, user);
        System.out.println("The Key Id is " + keyId);
        iam.close();
    }

    public static String createIAMAccessKey(IamClient iam, String user) {
        try {
            CreateAccessKeyRequest request = CreateAccessKeyRequest.builder()
                    .userName(user)
                    .build();

            CreateAccessKeyResponse response = iam.createAccessKey(request);
            return response.accessKey().accessKeyId();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a chave de acesso.

```
import { CreateAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 */
export const createAccessKey = (userName) => {
  const command = new CreateAccessKeyCommand({ UserName: userName });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
```

```
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccessKey({ UserName: "IAM_USER_NAME" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.AccessKey);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMAccessKey(user: String?): String {

    val request = CreateAccessKeyRequest {
        userName = user
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createAccessKey(request)
        return response.accessKey?.accessKeyId.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateAccessKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.

    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair
```

- Para obter detalhes da API, consulte a CreateAccessKeyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
  end

  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
```

```
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
#{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create
more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end

  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end

  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
```

```
    false
  end
end
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_access_key(client: &iamClient, user_name: &str) ->
 Result<AccessKey, iamError> {
    let mut tries: i32 = 0;
    let max_tries: i32 = 10;

    let response: Result<CreateAccessKeyOutput, SdkError<CreateAccessKeyError>> =
 loop {
        match client.create_access_key().user_name(user_name).send().await {
            Ok(inner_response) => {
                break Ok(inner_response);
            }
            Err(e) => {
                tries += 1;
                if tries > max_tries {
                    break Err(e);
                }
                sleep(Duration::from_secs(2)).await;
            }
        }
    };

    Ok(response.unwrap().access_key.unwrap())
}
```

- Para obter detalhes da API, consulte a CreateAccessKeyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createAccessKey(userName: String) async throws ->
IAMClientTypes.AccessKey {
       let input = CreateAccessKeyInput(
           userName: userName
       )
       do {
           let output = try await iamClient.createAccessKey(input: input)
           guard let accessKey = output.accessKey else {
               throw ServiceHandlerError.keyError
           }
           return accessKey
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreateAccessKeya referência da API AWS SDK for Swift.

Criar um alias para uma conta do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como criar um alias para uma conta do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::createAccountAlias(const Aws::String &aliasName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::CreateAccountAliasRequest request;
    request.SetAccountAlias(aliasName);

    Aws::IAM::Model::CreateAccountAliasOutcome outcome = iam.CreateAccountAlias(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating account alias " << aliasName << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created account alias " << aliasName <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como criar um alias da conta

O comando `create-account-alias`, apresentado a seguir, cria o alias `examplecorp` para sua conta da AWS.

```
aws iam create-account-alias \
    --account-alias examplecorp
```

Este comando não produz saída.

Para obter mais informações, consulte O ID da sua conta da AWS e seu alias no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateAccountAliasem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.CreateAccountAliasRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateAccountAlias {
    public static void main(String[] args) {
        final String usage = """
                Usage:
                    <alias>\s

                Where:
                    alias - The account alias to create (for example,
 myawsaccount).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alias = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        createIAMAccountAlias(iam, alias);
        iam.close();
        System.out.println("Done");
    }

    public static void createIAMAccountAlias(IamClient iam, String alias) {
        try {
            CreateAccountAliasRequest request =
 CreateAccountAliasRequest.builder()
                    .accountAlias(alias)
                    .build();

            iam.createAccountAlias(request);
            System.out.println("Successfully created account alias: " + alias);

        } catch (IamException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o alias da conta.

```
import { CreateAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} alias - A unique name for the account alias.
 * @returns
 */
export const createAccountAlias = (alias) => {
  const command = new CreateAccountAliasCommand({
    AccountAlias: alias,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMAccountAlias(alias: String) {

    val request = CreateAccountAliasRequest {
        accountAlias = alias
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.createAccountAlias(request)
        println("Successfully created account alias named $alias")
    }
}
```

- Para obter detalhes da API, consulte a CreateAccountAliasreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_alias(alias):
    """
    Creates an alias for the current account. The alias can be used in place of
 the
```

```
    account ID in the sign-in URL. An account can have only one alias. When a new
    alias is created, it replaces any existing alias.

    :param alias: The alias to assign to the account.
    """

    try:
        iam.create_account_alias(AccountAlias=alias)
        logger.info("Created an alias '%s' for your account.", alias)
    except ClientError:
        logger.exception("Couldn't create alias '%s' for your account.", alias)
        raise
```

- Para obter detalhes da API, consulte a CreateAccountAliasReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists available AWS account aliases.
```

```
  def list_aliases
    response = @iam_client.list_account_aliases

    if response.account_aliases.count.positive?
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for Ruby da API.

Criar uma política do IAM em linha para um grupo usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como criar uma política do IAM em linha para um grupo.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM
policy.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string
policyName, string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutGroupPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como adicionar uma política a um grupo

O comando `put-group-policy`, apresentado a seguir, adiciona uma política ao grupo do IAM denominado `Admins`.

```
aws iam put-group-policy \
    --group-name Admins \
    --policy-document file://AdminPolicy.json \
    --policy-name AdminRoot
```

Este comando não produz saída.

A política é definida como um documento JSON no AdminPolicyarquivo.json. (O nome e a extensão do arquivo não têm significado.)

Para obter mais informações, consulte Gerenciamento de políticas do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte PutGroupPolicyem Referência de AWS CLI Comandos.

Criar uma política em linha do IAM para um usuário usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma política do IAM em linha para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um usuário e assumir uma função

CLI

AWS CLI

Como anexar uma política a um usuário do IAM

O comando `put-user-policy`, apresentado a seguir, anexa uma política ao usuário do IAM denominado `Bob`.

```
aws iam put-user-policy \
    --user-name Bob \
    --policy-name ExamplePolicy \
    --policy-document file://AdminPolicy.json
```

Este comando não produz saída.

A política é definida como um documento JSON no AdminPolicyarquivo.json. (O nome e a extensão do arquivo não têm significado.)

Para obter mais informações, consulte Adicionar e remover permissões de identidade do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte PutUserPolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
```

```
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateUserPolicy adds an inline policy to a user. This example creates a
 policy that
// grants a list of actions on a specified role.
// PolicyDocument shows how to work with a policy document as a data structure
 and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper UserWrapper) CreateUserPolicy(userName string, policyName string,
 actions []string,
  roleArn string) error {
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(roleArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n", roleArn,
 err)
  return err
 }
 _, err = wrapper.IamClient.PutUserPolicy(context.TODO(),
 &iam.PutUserPolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
  UserName:       aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create policy for user %v. Here's why: %v\n", userName,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte PutUserPolicya Referência AWS SDK for Go da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates an inline policy for a specified user.
# @param username [String] The name of the IAM user.
# @param policy_name [String] The name of the policy to create.
# @param policy_document [String] The JSON policy document.
# @return [Boolean]
def create_user_policy(username, policy_name, policy_document)
  @iam_client.put_user_policy({
    user_name: username,
    policy_name: policy_name,
    policy_document: policy_document
  })
  @logger.info("Policy #{policy_name} created for user #{username}.")
  true
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Couldn't create policy #{policy_name} for user #{username}.
Here's why:")
  @logger.error("\t#{e.code}: #{e.message}")
  false
end
```

- Para obter detalhes da API, consulte PutUserPolicya Referência AWS SDK for Ruby da API.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   func putUserPolicy(policyDocument: String, policyName: String, user:
IAMClientTypes.User) async throws {
       let input = PutUserPolicyInput(
           policyDocument: policyDocument,
           policyName: policyName,
           userName: user.userName
       )
       do {
           _ = try await iamClient.putUserPolicy(input: input)
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte PutUserPolicya referência da API AWS SDK for Swift.

Criar um perfil de instância do IAM usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um perfil de instância do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create a policy, role, and profile that is associated with instances with
a specified name.
   /// An instance's associated profile defines a role that is assumed by the
   /// instance.The role has attached policies that specify the AWS permissions
granted to
   /// clients that run on the instance.
   /// </summary>
   /// <param name="policyName">Name to use for the policy.</param>
   /// <param name="roleName">Name to use for the role.</param>
   /// <param name="profileName">Name to use for the profile.</param>
   /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
   /// <param name="awsManagedPolicies">AWS Managed policies to be attached to
the role.</param>
   /// <returns>The Arn of the profile.</returns>
   public async Task<string> CreateInstanceProfileWithName(
       string policyName,
       string roleName,
       string profileName,
       string ssmOnlyPolicyFile,
       List<string>? awsManagedPolicies = null)
   {

       var assumeRoleDoc = "{" +
                                   "\"Version\": \"2012-10-17\"," +
                                   "\"Statement\": [{" +
                                        "\"Effect\": \"Allow\"," +
                                        "\"Principal\": {" +
                                        "\"Service\": [" +
                                            "\"ec2.amazonaws.com\"" +
```

```
                                    "]" +
                                    "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                            "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
```

```
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await
_amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
```

```
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }
```

- Para obter detalhes da API, consulte CreateInstanceProfilea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar um perfil de instância

O comando `create-instance-profile`, apresentado a seguir, cria um perfil de instância denominado `Webserver`.

```
aws iam create-instance-profile \
    --instance-profile-name Webserver
```

Saída:

```
{
    "InstanceProfile": {
        "InstanceProfileId": "AIPAJMBYC7DLSPEXAMPLE",
        "Roles": [],
        "CreateDate": "2015-03-09T20:33:19.626Z",
```

```
        "InstanceProfileName": "Webserver",
        "Path": "/",
        "Arn": "arn:aws:iam::123456789012:instance-profile/Webserver"
    }
}
```

Para adicionar um perfil a um perfil de instância, use o comando `add-role-to-instance-profile`.

Para obter mais informações, consulte Uso de um perfil do IAM para conceder permissões a aplicações em execução em instâncias do Amazon EC2 no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte CreateInstanceProfileem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const { InstanceProfile } = await iamClient.send(
  new CreateInstanceProfileCommand({
    InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
  }),
);
await waitUntilInstanceProfileExists(
  { client: iamClient },
  { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
);
```

- Para obter detalhes da API, consulte CreateInstanceProfilea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo cria uma política, um perfil e um perfil de instância e vincula uns aos outros.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
```

```
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is
assumed by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as
AmazonSSMManagedInstanceCore to grant
                                     use of Systems Manager to send commands to
the instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
```

```
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to
role\n"
                    f"{role_name}: {err}"
                )
        return profile_arn
```

- Para obter detalhes da API, consulte a CreateInstanceProfileReferência da API AWSSDK for Python (Boto3).

Excluir um provedor SAML do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como excluir um provedor SAML do AWS Identity and Access Management (IAM).

CLI

AWS CLI

Como excluir um provedor SAML

Este exemplo exclui o provedor SAML 2.0 do IAM cujo ARN é `arn:aws:iam::123456789012:saml-provider/SAMLADFSProvider`.

```
aws iam delete-saml-provider \
--saml-provider-arn arn:aws:iam::123456789012:saml-provider/SAMLADFSProvider
```

Este comando não produz saída.

Para obter mais informações, consulte Criação de provedores de identidade SAML do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteSAMLProvider na Referência de comandos da AWS CLI.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSAMLProviderCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
```

```
 *
 * @param {string} providerArn
 * @returns
 */
export const deleteSAMLProvider = async (providerArn) => {
  const command = new DeleteSAMLProviderCommand({
    SAMLProviderArn: providerArn,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteSAMLProvider na Referência da API do AWS SDK for JavaScript.

Excluir um grupo do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um grupo do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM group.
    /// </summary>
```

```
    /// <param name="groupName">The name of the IAM group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
 { GroupName = groupName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um grupo do IAM

O comando `delete-group`, apresentado a seguir, exclui um grupo do IAM denominado `MyTestGroup`.

```
aws iam delete-group \
    --group-name MyTestGroup
```

Este comando não produz saída.

Para obter mais informações, consulte Exclusão de um grupo de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteGroupem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteGroupCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} groupName
 */
export const deleteGroup = async (groupName) => {
  const command = new DeleteGroupCommand({
    GroupName: groupName,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteGroupa Referência AWS SDK for JavaScript da API.

Excluir uma política de grupo do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como excluir uma política de grupo do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
 policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteGroupPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir uma política de um grupo do IAM

O comando `delete-group-policy`, apresentado a seguir, exclui a política denominada `ExamplePolicy` do grupo denominado `Admins`.

```
aws iam delete-group-policy \
    --group-name Admins \
    --policy-name ExamplePolicy
```

Este comando não produz saída.

Para visualizar as políticas anexadas a um grupo, use o comando `list-group-policies`.

Para obter mais informações, consulte Gerenciamento de políticas do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteGroupPolicyem Referência de AWS CLI Comandos.

Excluir uma política do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando
- Políticas gerenciadas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new
DeletePolicyRequest { PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_policy
#
# This function deletes an IAM policy.
#
# Parameters:
#       -n policy_arn -- The name of the IAM policy arn.
```

```
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_delete_policy() {
  local policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_policy"
    echo "Deletes an WS Identity and Access Management (IAM) policy"
    echo "  -n policy_arn -- The name of the IAM policy arn."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy arn with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Policy arn:  $policy_arn"
  iecho ""
```

```
  response=$(aws iam delete-policy \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-policy operation failed.\n$response"
    return 1
  fi

  iecho "delete-policy response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeletePolicyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deletePolicy(const Aws::String &policyArn,
                               const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeletePolicyRequest request;
    request.SetPolicyArn(policyArn);

    auto outcome = iam.DeletePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting policy with arn " << policyArn << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

```
    else {
        std::cout << "Successfully deleted policy with arn " << policyArn
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir uma política do IAM

Este exemplo exclui a política cujo ARN é `arn:aws:iam::123456789012:policy/MySamplePolicy`.

```
aws iam delete-policy \
    --policy-arn arn:aws:iam::123456789012:policy/MySamplePolicy
```

Este comando não produz saída.

Para obter mais informações, consulte Políticas e permissões no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeletePolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// DeletePolicy deletes a policy.
func (wrapper PolicyWrapper) DeletePolicy(policyArn string) error {
 _, err := wrapper.IamClient.DeletePolicy(context.TODO(), &iam.DeletePolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't delete policy %v. Here's why: %v\n", policyArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DeletePolicyRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeletePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <policyARN>\s

                Where:
                    policyARN - A policy ARN value to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String policyARN = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMPolicy(iam, policyARN);
        iam.close();
    }

    public static void deleteIAMPolicy(IamClient iam, String policyARN) {
        try {
            DeletePolicyRequest request = DeletePolicyRequest.builder()
                    .policyArn(policyARN)
                    .build();

            iam.deletePolicy(request);
            System.out.println("Successfully deleted the policy");

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a política.

```
import { DeletePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 */
export const deletePolicy = (policyArn) => {
  const command = new DeletePolicyCommand({ PolicyArn: policyArn });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMPolicy(policyARNVal: String?) {

    val request = DeletePolicyRequest {
        policyArn = policyARNVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deletePolicy(request)
        println("Successfully deleted $policyARNVal")
    }
}
```

- Para obter detalhes da API, consulte a DeletePolicyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
```

```
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
        raise
```

- Para obter detalhes da API, consulte a DeletePolicyReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_policy(client: &iamClient, policy: Policy) -> Result<(),
 iamError> {
    client
        .delete_policy()
        .policy_arn(policy.arn.unwrap())
        .send()
        .await?;
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeletePolicyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deletePolicy(policy: IAMClientTypes.Policy) async throws {
    let input = DeletePolicyInput(
        policyArn: policy.arn
    )
    do {
        _ = try await iamClient.deletePolicy(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeletePolicya referência da API AWS SDK for Swift.

Excluir um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um perfil do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um usuário e assumir uma função
- Gerenciar funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
{ RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
```

```
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_role
#
# This function deletes an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_role() {
  local role_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_role"
    echo "Deletes an WS Identity and Access Management (IAM) role"
    echo "  -n role_name -- The name of the IAM role."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
```

```
      n) role_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  echo "role_name:$role_name"
  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Role name:  $role_name"
  iecho ""

  response=$(aws iam delete-role \
    --role-name "$role_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-role operation failed.\n$response"
    return 1
  fi

  iecho "delete-role response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteRoleem Referência de AWS CLI Comandos.

CLI

AWS CLI

Como excluir um perfil do IAM

O comando `delete-role`, apresentado a seguir, remove o perfil denominado `Test-Role`.

```
aws iam delete-role \
    --role-name Test-Role
```

Este comando não produz saída.

Antes de poder excluir um perfil, você deve removê-lo de qualquer perfil de instância (`remove-role-from-instance-profile`), desanexar quaisquer políticas gerenciadas (`detach-role-policy`) e excluir quaisquer políticas em linha anexadas a ele (`delete-role-policy`).

Para obter mais informações, consulte Criação de perfis do IAM e Usar perfis de instância no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteRoleem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}
```

```
// DeleteRole deletes a role. All attached policies must be detached before a
// role can be deleted.
func (wrapper RoleWrapper) DeleteRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't delete role %v. Here's why: %v\n", roleName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a função.

```
import { DeleteRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const deleteRole = (roleName) => {
  const command = new DeleteRoleCommand({ RoleName: roleName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_role(role_name):
    """
    Deletes a role.

    :param role_name: The name of the role to delete.
    """
    try:
        iam.Role(role_name).delete()
        logger.info("Deleted role %s.", role_name)
    except ClientError:
        logger.exception("Couldn't delete role %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteRoleReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Deletes a role and its attached policies.
  #
  # @param role_name [String] The name of the role to delete.
  def delete_role(role_name)
    begin
      # Detach and delete attached policies
      @iam_client.list_attached_role_policies(role_name: role_name).each do |
response|
        response.attached_policies.each do |policy|
          @iam_client.detach_role_policy({
                                          role_name: role_name,
                                          policy_arn: policy.policy_arn
                                        })
          # Check if the policy is a customer managed policy (not AWS managed)
          unless policy.policy_arn.include?("aws:policy/")
            @iam_client.delete_policy({ policy_arn: policy.policy_arn })
            @logger.info("Deleted customer managed policy
 #{policy.policy_name}.")
          end
        end
      end

      # Delete the role
      @iam_client.delete_role({ role_name: role_name })
      @logger.info("Deleted role #{role_name}.")
    rescue Aws::IAM::Errors::ServiceError => e
      @logger.error("Couldn't detach policies and delete role #{role_name}.
 Here's why:")
      @logger.error("\t#{e.code}: #{e.message}")
      raise
    end
  end
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_role(client: &iamClient, role: &Role) -> Result<(), iamError>
 {
    let role = role.clone();
    while client
        .delete_role()
        .role_name(role.role_name())
        .send()
        .await
        .is_err()
    {
        sleep(Duration::from_secs(2)).await;
    }
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteRolereferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteRole(role: IAMClientTypes.Role) async throws {
    let input = DeleteRoleInput(
        roleName: role.roleName
    )
    do {
        _ = try await iamClient.deleteRole(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeleteRolea referência da API AWS SDK for Swift.

Excluir uma política de perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma política de perfil do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="policyName">The name of the IAM role policy to delete.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
 policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
 DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRolePolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como remover uma política de um perfil do IAM

O comando `delete-role-policy`, apresentado a seguir, remove a política denominada `ExamplePolicy` do perfil denominado `Test-Role`.

```
aws iam delete-role-policy \
    --role-name Test-Role \
    --policy-name ExamplePolicy
```

Este comando não produz saída.

Para obter mais informações, consulte Modificar um perfil no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteRolePolicyem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 * @param {string} policyName
 */
export const deleteRolePolicy = (roleName, policyName) => {
  const command = new DeleteRolePolicyCommand({
    RoleName: roleName,
    PolicyName: policyName,
  });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteRolePolicya Referência AWS SDK for JavaScript da API.

Excluir um certificado de servidor do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um certificado de servidor do IAM.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteServerCertificate(const Aws::String &certificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeleteServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);

    const auto outcome = iam.DeleteServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error deleting server certificate " << certificateName
 <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
```

```
        std::cout << "Successfully deleted server certificate " <<
 certificateName
                  << std::endl;
    }

    return result;
}
```

- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir um certificado de servidor da sua conta da AWS

O comando `delete-server-certificate`, apresentado a seguir, remove o certificado de servidor especificado da sua conta da AWS.

```
aws iam delete-server-certificate \
    --server-certificate-name myUpdatedServerCertificate
```

Este comando não produz saída.

Para listar os certificados de servidor disponíveis em sua conta da AWS, use o comando `list-server-certificates`.

Para obter mais informações, consulte Gerenciar certificados de servidor no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteServerCertificateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um certificado de servidor.

```
import { DeleteServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
 */
export const deleteServerCertificate = (certName) => {
  const command = new DeleteServerCertificateCommand({
    ServerCertificateName: certName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
```

```
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates

    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
#{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
      new_server_certificate_name: new_name
    )
```

```
    @logger.info("Server certificate name updated from '#{current_name}' to
 '#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for Ruby da API.

Excluir um perfil vinculado ao serviço do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um perfil vinculado ao serviço do IAM.

CLI

AWS CLI

Como excluir um perfil vinculado ao serviço

O exemplo para `delete-service-linked-role`, apresentado a seguir, exclui o perfil vinculado ao serviço especificado que não é mais necessário. A exclusão acontece de forma assíncrona. É possível verificar o status da exclusão e confirmar quando ela for concluída ao usar o comando `get-service-linked-role-deletion-status`.

```
aws iam delete-service-linked-role \
    --role-name AWSServiceRoleForLexBots
```

Saída:

```
{
    "DeletionTaskId": "task/aws-service-role/lex.amazonaws.com/
AWSServiceRoleForLexBots/1a2b3c4d-1234-abcd-7890-abcdeEXAMPLE"
}
```

Para obter mais informações, consulte Usar perfis vinculados ao serviço no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteServiceLinkedRoleem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// DeleteServiceLinkedRole deletes a service-linked role.
func (wrapper RoleWrapper) DeleteServiceLinkedRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteServiceLinkedRole(context.TODO(),
 &iam.DeleteServiceLinkedRoleInput{
  RoleName: aws.String(roleName)},
 )
 if err != nil {
  log.Printf("Couldn't delete service-linked role %v. Here's why: %v\n",
 roleName, err)
 }
```

```
 return err
}
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteServiceLinkedRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const deleteServiceLinkedRole = (roleName) => {
  const command = new DeleteServiceLinkedRoleCommand({ RoleName: roleName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes a service-linked role.
#
# @param role_name [String] The name of the role to delete.
def delete_service_linked_role(role_name)
  response = @iam_client.delete_service_linked_role(role_name: role_name)
  task_id = response.deletion_task_id
  check_deletion_status(role_name, task_id)
rescue Aws::Errors::ServiceError => e
  handle_deletion_error(e, role_name)
end

private

# Checks the deletion status of a service-linked role
#
# @param role_name [String] The name of the role being deleted
# @param task_id [String] The task ID for the deletion process
def check_deletion_status(role_name, task_id)
  loop do
    response = @iam_client.get_service_linked_role_deletion_status(
      deletion_task_id: task_id)
    status = response.status
    @logger.info("Deletion of #{role_name} #{status}.")
    break if %w[SUCCEEDED FAILED].include?(status)
    sleep(3)
  end
end

# Handles deletion error
#
# @param e [Aws::Errors::ServiceError] The error encountered during deletion
# @param role_name [String] The name of the role attempted to delete
```

```
  def handle_deletion_error(e, role_name)
    unless e.code == "NoSuchEntity"
      @logger.error("Couldn't delete #{role_name}. Here's why:")
      @logger.error("\t#{e.code}: #{e.message}")
      raise
    end
  end
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_service_linked_role(
    client: &iamClient,
    role_name: &str,
) -> Result<(), iamError> {
    client
        .delete_service_linked_role()
        .role_name(role_name)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteServiceLinkedRolereferência da API AWS SDK for Rust.

Excluir um usuário do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM user.
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
{ UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
```

```
    }
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_user
#
# This function deletes the specified IAM user.
#
```

```
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_delete_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_user"
    echo "Deletes an WS Identity and Access Management (IAM) user. You must
 supply a username:"
    echo "  -u user_name    The name of the user."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
```

```
  iecho "    User name:   $user_name"
  iecho ""

  # If the user does not exist, we don't want to try to delete it.
  if (! iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name does not exist in the account."
    return 1
  fi

  response=$(aws iam delete-user \
    --user-name "$user_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-user operation failed.$response"
    return 1
  fi

  iecho "delete-user response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteUserem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteUserRequest request;
```

```
    request.SetUserName(userName);
    auto outcome = iam.DeleteUser(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting IAM user " << userName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;;
    }
    else {
        std::cout << "Successfully deleted IAM user " << userName << std::endl;
    }

    return outcome.IsSuccess();
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir um usuário do IAM

O comando `delete-user`, apresentado a seguir, remove o usuário do IAM denominado Bob da conta atual.

```
aws iam delete-user \
    --user-name Bob
```

Este comando não produz saída.

Para obter mais informações, consulte Exclusão de um usuário do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteUserem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// DeleteUser deletes a user.
func (wrapper UserWrapper) DeleteUser(userName string) error {
 _, err := wrapper.IamClient.DeleteUser(context.TODO(), &iam.DeleteUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete user %v. Here's why: %v\n", userName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.DeleteUserRequest;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <userName>\s

                Where:
                    userName - The name of the user to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userName = args[0];
        Region region = Region.AWS_GLOBAL;
```

```
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMUser(iam, userName);
        System.out.println("Done");
        iam.close();
    }

    public static void deleteIAMUser(IamClient iam, String userName) {
        try {
            DeleteUserRequest request = DeleteUserRequest.builder()
                    .userName(userName)
                    .build();

            iam.deleteUser(request);
            System.out.println("Successfully deleted IAM user " + userName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o usuário.

```
import { DeleteUserCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 *
 * @param {string} name
 */
export const deleteUser = (name) => {
  const command = new DeleteUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    console.log("User " + process.argv[2] + " does not exist.");
  } else {
```

```
    iam.deleteUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Success", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMUser(userNameVal: String) {

    val request = DeleteUserRequest {
        userName = userNameVal
    }

    // To delete a user, ensure that the user's access keys are deleted first.
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteUser(request)
        println("Successfully deleted user $userNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteUserreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_user(user_name):
    """
    Deletes a user. Before a user can be deleted, all associated resources,
    such as access keys and policies, must be deleted or detached.

    :param user_name: The name of the user.
    """
    try:
        iam.User(user_name).delete()
        logger.info("Deleted user %s.", user_name)
    except ClientError:
        logger.exception("Couldn't delete user %s.", user_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteUserReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Deletes a user and their associated resources
 #
 # @param user_name [String] The name of the user to delete
 def delete_user(user_name)
   user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
   user.each do |key|
     @iam_client.delete_access_key({ access_key_id: key.access_key_id,
user_name: user_name })
     @logger.info("Deleted access key #{key.access_key_id} for user
'#{user_name}'.")
   end

   @iam_client.delete_user(user_name: user_name)
   @logger.info("Deleted user '#{user_name}'.")
 rescue Aws::IAM::Errors::ServiceError => e
   @logger.error("Error deleting user '#{user_name}': #{e.message}")
 end
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_user(client: &iamClient, user: &User) -> Result<(),
 SdkError<DeleteUserError>> {
    let user = user.clone();
    let mut tries: i32 = 0;
    let max_tries: i32 = 10;

    let response: Result<(), SdkError<DeleteUserError>> = loop {
        match client
            .delete_user()
            .user_name(user.user_name())
            .send()
            .await
        {
            Ok(_) => {
                break Ok(());
            }
            Err(e) => {
                tries += 1;
                if tries > max_tries {
                    break Err(e);
                }
                sleep(Duration::from_secs(2)).await;
            }
        }
    };

    response
}
```

- Para obter detalhes da API, consulte a DeleteUserreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteUser(user: IAMClientTypes.User) async throws {
    let input = DeleteUserInput(
        userName: user.userName
    )
    do {
        _ = try await iamClient.deleteUser(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeleteUsera referência da API AWS SDK for Swift.

Excluir uma chave de acesso do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um grupo e adicionar um usuário
- Criar um usuário e assumir uma função
- Criar usuários somente leitura e leitura/gravação usando
- Gerenciar chaves de acesso

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Delete an IAM user's access key.
   /// </summary>
   /// <param name="accessKeyId">The Id for the IAM access key.</param>
   /// <param name="userName">The username of the user that owns the IAM
   /// access key.</param>
   /// <returns>A Boolean value indicating the success of the action.</returns>
   public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
userName)
   {
       var response = await _IAMService.DeleteAccessKeyAsync(new
DeleteAccessKeyRequest
       {
           AccessKeyId = accessKeyId,
           UserName = userName,
       });

       return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
   }
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_access_key
#
# This function deletes an IAM access key for the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user.
#       -k access_key -- The access key to delete.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_access_key() {
  local user_name access_key response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_access_key"
    echo "Deletes an WS Identity and Access Management (IAM) access key for the
 specified IAM user"
    echo "  -u user_name    The name of the user."
```

```
  echo "  -k access_key   The access key to delete."
  echo ""
}

# Retrieve the calling parameters.
while getopts "u:k:h" option; do
  case "${option}" in
    u) user_name="${OPTARG}" ;;
    k) access_key="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$user_name" ]]; then
  errecho "ERROR: You must provide a username with the -u parameter."
  usage
  return 1
fi

if [[ -z "$access_key" ]]; then
  errecho "ERROR: You must provide an access key with the -k parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    Username:   $user_name"
iecho "    Access key:   $access_key"
iecho ""

response=$(aws iam delete-access-key \
  --user-name "$user_name" \
  --access-key-id "$access_key")

local error_code=${?}
```

```
  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-access-key operation failed.\n$response"
    return 1
  fi

  iecho "delete-access-key response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteAccessKeyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);

    auto outcome = iam.DeleteAccessKey(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting access key " << accessKeyID << " from user "
```

```
                    << userName << ": " << outcome.GetError().GetMessage() <<
                    std::endl;
    }
    else {
        std::cout << "Successfully deleted access key " << accessKeyID
                    << " for IAM user " << userName << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir uma chave de acesso para um usuário do IAM

O comando `delete-access-key`, apresentado a seguir, exclui a chave de acesso especificada (ID da chave de acesso e chave de acesso secreta) para o usuário do IAM denominado Bob.

```
aws iam delete-access-key \
    --access-key-id AKIDPMS9RO4H3FEXAMPLE \
    --user-name Bob
```

Este comando não produz saída.

Para listar as chaves de acesso definidas para um usuário do IAM, use o comando `list-access-keys`.

Para obter mais informações, consulte Gerenciamento de chaves de acesso de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteAccessKeyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// DeleteAccessKey deletes an access key from a user.
func (wrapper UserWrapper) DeleteAccessKey(userName string, keyId string) error {
 _, err := wrapper.IamClient.DeleteAccessKey(context.TODO(),
 &iam.DeleteAccessKeyInput{
  AccessKeyId: aws.String(keyId),
  UserName:    aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete access key %v. Here's why: %v\n", keyId, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.DeleteAccessKeyRequest;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteAccessKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <username> <accessKey>\s

                Where:
                    username - The name of the user.\s
                    accessKey - The access key ID for the secret access key you
 want to delete.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String username = args[0];
        String accessKey = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();
        deleteKey(iam, username, accessKey);
        iam.close();
    }

    public static void deleteKey(IamClient iam, String username, String
 accessKey) {
        try {
            DeleteAccessKeyRequest request = DeleteAccessKeyRequest.builder()
                    .accessKeyId(accessKey)
                    .userName(username)
                    .build();

            iam.deleteAccessKey(request);
            System.out.println("Successfully deleted access key " + accessKey +
                    " from user " + username);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a chave de acesso.

```
import { DeleteAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
export const deleteAccessKey = (userName, accessKeyId) => {
  const command = new DeleteAccessKeyCommand({
    AccessKeyId: accessKeyId,
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });
```

```
var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  UserName: "USER_NAME",
};

iam.deleteAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKey(userNameVal: String, accessKey: String) {

    val request = DeleteAccessKeyRequest {
        accessKeyId = accessKey
        userName = userNameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteAccessKey(request)
        println("Successfully deleted access key $accessKey from $userNameVal")
    }
```

```
}
```

- Para obter detalhes da API, consulte a DeleteAccessKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteAccessKeyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
  end

  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
```

```
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
#{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create
more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end

  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end

  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
```

```
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_access_key(
    client: &iamClient,
    user: &User,
    key: &AccessKey,
) -> Result<(), iamError> {
    loop {
        match client
            .delete_access_key()
            .user_name(user.user_name())
            .access_key_id(key.access_key_id())
            .send()
            .await
        {
            Ok(_) => {
                break;
            }
            Err(e) => {
                println!("Can't delete the access key: {:?}", e);
                sleep(Duration::from_secs(2)).await;
            }
        }
    }
    Ok(())
```

```
}
```

- Para obter detalhes da API, consulte a DeleteAccessKeyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func deleteAccessKey(user: IAMClientTypes.User? = nil,
                                key: IAMClientTypes.AccessKey) async throws {
        let userName: String?

        if user != nil {
            userName = user!.userName
        } else {
            userName = nil
        }

        let input = DeleteAccessKeyInput(
            accessKeyId: key.accessKeyId,
            userName: userName
        )
        do {
            _ = try await iamClient.deleteAccessKey(input: input)
        } catch {
            throw error
```

```
        }
    }
```

- Para obter detalhes da API, consulte DeleteAccessKeya referência da API AWS SDK for Swift.

Excluir uma conta do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma conta do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccountAlias(const Aws::String &accountAlias,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccountAliasRequest request;
    request.SetAccountAlias(accountAlias);

    const auto outcome = iam.DeleteAccountAlias(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting account alias " << accountAlias << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
```

```
        std::cout << "Successfully deleted account alias " << accountAlias <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir um alias da conta

O comando `delete-account-alias`, apresentado a seguir, remove o alias `mycompany` para a conta atual.

```
aws iam delete-account-alias \
    --account-alias mycompany
```

Este comando não produz saída.

Para obter mais informações, consulte O ID da sua conta da AWS e seu alias no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteAccountAliasem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DeleteAccountAliasRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteAccountAlias {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <alias>\s

                Where:
                    alias - The account alias to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alias = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMAccountAlias(iam, alias);
        iam.close();
    }

    public static void deleteIAMAccountAlias(IamClient iam, String alias) {
        try {
```

```
            DeleteAccountAliasRequest request =
 DeleteAccountAliasRequest.builder()
                    .accountAlias(alias)
                    .build();

            iam.deleteAccountAlias(request);
            System.out.println("Successfully deleted account alias " + alias);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o alias da conta.

```
import { DeleteAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} alias
 */
export const deleteAccountAlias = (alias) => {
```

```
  const command = new DeleteAccountAliasCommand({ AccountAlias: alias });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMAccountAlias(alias: String) {

    val request = DeleteAccountAliasRequest {
        accountAlias = alias
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteAccountAlias(request)
        println("Successfully deleted account alias $alias")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAccountAliasreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_alias(alias):
    """
    Removes the alias from the current account.
```

```
    :param alias: The alias to remove.
    """
    try:
        iam.meta.client.delete_account_alias(AccountAlias=alias)
        logger.info("Removed alias '%s' from your account.", alias)
    except ClientError:
        logger.exception("Couldn't remove alias '%s' from your account.", alias)
        raise
```

- Para obter detalhes da API, consulte a DeleteAccountAliasReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists available AWS account aliases.
  def list_aliases
    response = @iam_client.list_account_aliases

    if response.account_aliases.count.positive?
```

```
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for Ruby da API.

Excluir uma política do IAM em linha de um usuário usando um AWSSDK

Os exemplos de código a seguir mostram como excluir uma política em linha do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um usuário e assumir uma função

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como remover uma política de um usuário do IAM

O comando `delete-user-policy`, apresentado a seguir, remove a política especificada do usuário do IAM denominado `Bob`.

```
aws iam delete-user-policy \
    --user-name Bob \
    --policy-name ExamplePolicy
```

Este comando não produz saída.

Para obter uma lista de políticas para um usuário do IAM, use o comando `list-user-policies`.

Para obter mais informações, consulte Criar um usuário do IAM na sua conta da AWS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteUserPolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
```

```
 IamClient *iam.Client
}



// DeleteUserPolicy deletes an inline policy from a user.
func (wrapper UserWrapper) DeleteUserPolicy(userName string, policyName string)
 error {
 _, err := wrapper.IamClient.DeleteUserPolicy(context.TODO(),
 &iam.DeleteUserPolicyInput{
  PolicyName: aws.String(policyName),
  UserName:   aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete policy from user %v. Here's why: %v\n", userName,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for Go da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Deletes a user and their associated resources
  #
  # @param user_name [String] The name of the user to delete
  def delete_user(user_name)
    user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
    user.each do |key|
```

```
      @iam_client.delete_access_key({ access_key_id: key.access_key_id,
 user_name: user_name })
      @logger.info("Deleted access key #{key.access_key_id} for user
 '#{user_name}'.")
    end

    @iam_client.delete_user(user_name: user_name)
    @logger.info("Deleted user '#{user_name}'.")
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting user '#{user_name}': #{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_user_policy(
    client: &iamClient,
    user: &User,
    policy_name: &str,
) -> Result<(), SdkError<DeleteUserPolicyError>> {
    client
        .delete_user_policy()
        .user_name(user.user_name())
        .policy_name(policy_name)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteUserPolicyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   func deleteUserPolicy(user: IAMClientTypes.User, policyName: String) async
throws {
       let input = DeleteUserPolicyInput(
           policyName: policyName,
           userName: user.userName
       )
       do {
           _ = try await iamClient.deleteUserPolicy(input: input)
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte DeleteUserPolicya referência da API AWS SDK for Swift.

Criar um perfil de instância do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um perfil de instância do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar e gerenciar um serviço resiliente

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the
role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await
_amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
```

```
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }
```

- Para obter detalhes da API, consulte DeleteInstanceProfile a Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um perfil de instância

O comando `delete-instance-profile`, apresentado a seguir, exclui o perfil de instância denominado `ExampleInstanceProfile`.

```
aws iam delete-instance-profile \
    --instance-profile-name ExampleInstanceProfile
```

Este comando não produz saída.

Para obter mais informações, consulte Usar perfis de instância no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DeleteInstanceProfileem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new IAMClient({});
await client.send(
  new DeleteInstanceProfileCommand({
    InstanceProfileName: NAMES.instanceProfileName,
  }),
);
```

- Para obter detalhes da API, consulte DeleteInstanceProfilea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo remove o perfil do perfil de instância, separa todas as políticas anexadas ao perfil e exclui todos os recursos.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
```

```
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the
role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )
```

- Para obter detalhes da API, consulte a DeleteInstanceProfileReferência da API AWSSDK for Python (Boto3).

Desanexar uma política do IAM de um perfil usando um SDK da AWS

Os exemplos de código a seguir mostram como desanexar uma política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar um usuário e assumir uma função
- Gerenciar funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Detach an IAM policy from an IAM role.
   /// </summary>
   /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM
policy.</param>
   /// <param name="roleName">The name of the IAM role.</param>
   /// <returns>A Boolean value indicating the success of the action.</returns>
   public async Task<bool> DetachRolePolicyAsync(string policyArn, string
roleName)
   {
       var response = await _IAMService.DetachRolePolicyAsync(new
DetachRolePolicyRequest
       {
           PolicyArn = policyArn,
           RoleName = roleName,
```

```
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_detach_role_policy
#
# This function detaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
```

```
###############################################################################
function iam_detach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_detach_role_policy"
    echo "Detaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi
```

```
  response=$(aws iam detach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports detach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte DetachRolePolicyem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DetachRolePolicyRequest detachRequest;
    detachRequest.SetRoleName(roleName);
    detachRequest.SetPolicyArn(policyArn);

    auto detachOutcome = iam.DetachRolePolicy(detachRequest);
    if (!detachOutcome.IsSuccess()) {
        std::cerr << "Failed to detach policy " << policyArn << " from role "
```

```
                    << roleName << ": " << detachOutcome.GetError().GetMessage() <<
                    std::endl;
    }
    else {
        std::cout << "Successfully detached policy " << policyArn << " from role
 "
                    << roleName << std::endl;
    }

    return detachOutcome.IsSuccess();
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como desanexar uma política de um perfil

Este exemplo remove a política gerenciada com o ARN `arn:aws:iam::123456789012:policy/FederatedTesterAccessPolicy` do perfil denominado `FedTesterRole`.

```
aws iam detach-role-policy \
    --role-name FedTesterRole \
    --policy-arn arn:aws:iam::123456789012:policy/FederatedTesterAccessPolicy
```

Este comando não produz saída.

Para obter mais informações, consulte Modificar um perfil no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DetachRolePolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// DetachRolePolicy detaches a policy from a role.
func (wrapper RoleWrapper) DetachRolePolicy(roleName string, policyArn string)
 error {
 _, err := wrapper.IamClient.DetachRolePolicy(context.TODO(),
 &iam.DetachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't detach policy from role %v. Here's why: %v\n", roleName,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DetachRolePolicyRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetachRolePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleName> <policyArn>\s

                Where:
                    roleName - A role name that you can obtain from the AWS
 Management Console.\s
                    policyArn - A policy ARN that you can obtain from the AWS
 Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String roleName = args[0];
        String policyArn = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();
        detachPolicy(iam, roleName, policyArn);
        System.out.println("Done");
        iam.close();
    }

    public static void detachPolicy(IamClient iam, String roleName, String
 policyArn) {
        try {
            DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.detachRolePolicy(request);
            System.out.println("Successfully detached policy " + policyArn +
                    " from role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desanexe a política.

```
import { DetachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const detachRolePolicy = (policyArn, roleName) => {
  const command = new DetachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        var params = {
          PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
          RoleName: process.argv[2],
        };
        iam.detachRolePolicy(params, function (err, data) {
          if (err) {
            console.log("Unable to detach policy from role", err);
          } else {
            console.log("Policy detached from role successfully");
            process.exit();
          }
        });
      }
    });
  }
```

```
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detachPolicy(roleNameVal: String, policyArnVal: String) {

    val request = DetachRolePolicyRequest {
        roleName = roleNameVal
        policyArn = policyArnVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.detachRolePolicy(request)
        println("Successfully detached policy $policyArnVal from role
 $roleNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DetachRolePolicyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desanexar uma política de uma função usando o objeto Policy do Boto3.

```
def detach_from_role(role_name, policy_arn):
    """
    Detaches a policy from a role.

    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Policy(policy_arn).detach_role(RoleName=role_name)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise
```

Desanexar uma política de uma função usando o objeto Role do Boto3.

```
def detach_policy(role_name, policy_arn):
    """
    Detaches a policy from a role.

    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
```

```
    try:
        iam.Role(role_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise
```

- Para obter detalhes da API, consulte a DetachRolePolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
```

```
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
```

```
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn detach_role_policy(
    client: &iamClient,
    role_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .detach_role_policy()
        .role_name(role_name)
        .policy_arn(policy_arn)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DetachRolePolicyreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func detachRolePolicy(policy: IAMClientTypes.Policy, role:
IAMClientTypes.Role) async throws {
       let input = DetachRolePolicyInput(
           policyArn: policy.arn,
           roleName: role.roleName
       )

       do {
           _ = try await iamClient.detachRolePolicy(input: input)
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte DetachRolePolicya referência da API AWS SDK for Swift.

Desanexar uma política do IAM de um usuário usando um AWS SDK

Os exemplos de código a seguir mostram como desanexar uma política do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar usuários somente leitura e leitura/gravação usando

CLI

AWS CLI

Como desanexar uma política de um usuário

Este exemplo remove a política gerenciada com o ARN `arn:aws:iam::123456789012:policy/TesterPolicy` do usuário `Bob`.

```
aws iam detach-user-policy \
    --user-name Bob \
    --policy-arn arn:aws:iam::123456789012:policy/TesterPolicy
```

Este comando não produz saída.

Para obter mais informações, consulte Alteração de permissões de um usuário do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte DetachUserPolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def detach_policy(user_name, policy_arn):
    """
    Detaches a policy from a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from user %s.", policy_arn, user_name)
    except ClientError:
```

```
        logger.exception(
            "Couldn't detach policy %s from user %s.", policy_arn, user_name
        )
        raise
```

- Para obter detalhes da API, consulte a DetachUserPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Detaches a policy from a user
 #
 # @param user_name [String] The name of the user
 # @param policy_arn [String] The ARN of the policy to detach
 # @return [Boolean] true if the policy was successfully detached, false
otherwise
 def detach_user_policy(user_name, policy_arn)
   @iam_client.detach_user_policy(
     user_name: user_name,
     policy_arn: policy_arn
   )
   @logger.info("Policy '#{policy_arn}' detached from user '#{user_name}'
successfully.")
   true
 rescue Aws::IAM::Errors::NoSuchEntity
   @logger.error("Error detaching policy: Policy or user does not exist.")
   false
 rescue Aws::IAM::Errors::ServiceError => e
   @logger.error("Error detaching policy from user '#{user_name}':
#{e.message}")
```

```
    false
  end
```

- Para obter detalhes da API, consulte DetachUserPolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn detach_user_policy(
    client: &iamClient,
    user_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .detach_user_policy()
        .user_name(user_name)
        .policy_arn(policy_arn)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DetachUserPolicyreferência da API AWS SDK for Rust.

Gerar um relatório de credenciais do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como gerar um relatório de credenciais do IAM para a conta atual. Depois que o relatório for gerado, obtenha-o usando a GetCredentialReport ação.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

CLI

AWS CLI

Como gerar um relatório de credenciais

O exemplo apresentado a seguir tenta gerar um relatório de credenciais para a conta da AWS.

```
aws iam generate-credential-report
```

Saída:

```
{
    "State":  "STARTED",
    "Description": "No report exists. Starting a new report generation task"
}
```

Para obter mais informações, consulte Obter relatórios de credenciais da sua conta da AWS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GenerateCredentialReportem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def generate_credential_report():
    """
    Starts generation of a credentials report about the current account. After
    calling this function to generate the report, call get_credential_report
    to get the latest report. A new report can be generated a minimum of four
 hours
    after the last one was generated.
    """
    try:
        response = iam.meta.client.generate_credential_report()
        logger.info(
            "Generating credentials report for your account. " "Current state is
 %s.",
            response["State"],
        )
    except ClientError:
        logger.exception("Couldn't generate a credentials report for your
 account.")
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a GenerateCredentialReportReferência da API AWSSDK for Python (Boto3).

Obter um relatório de credenciais do IAM usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter o relatório de credenciais gerado mais recentemente do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

CLI

AWS CLI

Como obter um relatório de credenciais

Este exemplo abre o relatório retornado e o envia ao pipeline como uma matriz de linhas de texto.

```
aws iam get-credential-report
```

Saída:

```
{
    "GeneratedTime":  "2015-06-17T19:11:50Z",
    "ReportFormat": "text/csv"
}
```

Para obter mais informações, consulte Obter relatórios de credenciais da sua conta da AWS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetCredentialReportem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_credential_report():
    """
    Gets the most recently generated credentials report about the current
 account.

    :return: The credentials report.
    """
    try:
        response = iam.meta.client.get_credential_report()
        logger.debug(response["Content"])
    except ClientError:
        logger.exception("Couldn't get credentials report.")
        raise
    else:
        return response["Content"]
```

- Para obter detalhes da API, consulte a GetCredentialReportReferência da API AWSSDK for Python (Boto3).

Obter um relatório detalhado de autorização do IAM para a conta usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter um relatório detalhado de autorização do IAM para sua conta.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

CLI

AWS CLI

Como listar usuários, grupos, perfis e políticas do IAM de contas da AWS

O comando `get-account-authorization-details`, apresentado a seguir, retorna informações sobre todos os usuários, grupos, perfis e políticas do IAM na conta da AWS.

```
aws iam get-account-authorization-details
```

Saída:

```
{
    "RoleDetailList": [
        {
            "AssumeRolePolicyDocument": {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Sid": "",
                        "Effect": "Allow",
                        "Principal": {
                            "Service": "ec2.amazonaws.com"
                        },
                        "Action": "sts:AssumeRole"
                    }
                ]
            },
            "RoleId": "AROA1234567890EXAMPLE",
            "CreateDate": "2014-07-30T17:09:20Z",
            "InstanceProfileList": [
                {
                    "InstanceProfileId": "AIPA1234567890EXAMPLE",
                    "Roles": [
                        {
                            "AssumeRolePolicyDocument": {
                                "Version": "2012-10-17",
                                "Statement": [
                                    {
```

```
                                        "Sid": "",
                                        "Effect": "Allow",
                                        "Principal": {
                                            "Service": "ec2.amazonaws.com"
                                        },
                                        "Action": "sts:AssumeRole"
                                    }
                                ]
                            },
                            "RoleId": "AROA1234567890EXAMPLE",
                            "CreateDate": "2014-07-30T17:09:20Z",
                            "RoleName": "EC2role",
                            "Path": "/",
                            "Arn": "arn:aws:iam::123456789012:role/EC2role"
                        }
                    ],
                    "CreateDate": "2014-07-30T17:09:20Z",
                    "InstanceProfileName": "EC2role",
                    "Path": "/",
                    "Arn": "arn:aws:iam::123456789012:instance-profile/EC2role"
                }
            ],
            "RoleName": "EC2role",
            "Path": "/",
            "AttachedManagedPolicies": [
                {
                    "PolicyName": "AmazonS3FullAccess",
                    "PolicyArn": "arn:aws:iam::aws:policy/AmazonS3FullAccess"
                },
                {
                    "PolicyName": "AmazonDynamoDBFullAccess",
                    "PolicyArn": "arn:aws:iam::aws:policy/
AmazonDynamoDBFullAccess"
                }
            ],
            "RoleLastUsed": {
                "Region": "us-west-2",
                "LastUsedDate": "2019-11-13T17:30:00Z"
            },
            "RolePolicyList": [],
            "Arn": "arn:aws:iam::123456789012:role/EC2role"
        }
    ],
    "GroupDetailList": [
```

```
        {
            "GroupId": "AIDA1234567890EXAMPLE",
            "AttachedManagedPolicies": {
                "PolicyName": "AdministratorAccess",
                "PolicyArn": "arn:aws:iam::aws:policy/AdministratorAccess"
            },
            "GroupName": "Admins",
            "Path": "/",
            "Arn": "arn:aws:iam::123456789012:group/Admins",
            "CreateDate": "2013-10-14T18:32:24Z",
            "GroupPolicyList": []
        },
        {
            "GroupId": "AIDA1234567890EXAMPLE",
            "AttachedManagedPolicies": {
                "PolicyName": "PowerUserAccess",
                "PolicyArn": "arn:aws:iam::aws:policy/PowerUserAccess"
            },
            "GroupName": "Dev",
            "Path": "/",
            "Arn": "arn:aws:iam::123456789012:group/Dev",
            "CreateDate": "2013-10-14T18:33:55Z",
            "GroupPolicyList": []
        },
        {
            "GroupId": "AIDA1234567890EXAMPLE",
            "AttachedManagedPolicies": [],
            "GroupName": "Finance",
            "Path": "/",
            "Arn": "arn:aws:iam::123456789012:group/Finance",
            "CreateDate": "2013-10-14T18:57:48Z",
            "GroupPolicyList": [
                {
                    "PolicyName": "policygen-201310141157",
                    "PolicyDocument": {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Action": "aws-portal:*",
                                "Sid": "Stmt1381777017000",
                                "Resource": "*",
                                "Effect": "Allow"
                            }
                        ]
```

```
                    }
                }
            ]
        }
    ],
    "UserDetailList": [
        {
            "UserName": "Alice",
            "GroupList": [
                "Admins"
            ],
            "CreateDate": "2013-10-14T18:32:24Z",
            "UserId": "AIDA1234567890EXAMPLE",
            "UserPolicyList": [],
            "Path": "/",
            "AttachedManagedPolicies": [],
            "Arn": "arn:aws:iam::123456789012:user/Alice"
        },
        {
            "UserName": "Bob",
            "GroupList": [
                "Admins"
            ],
            "CreateDate": "2013-10-14T18:32:25Z",
            "UserId": "AIDA1234567890EXAMPLE",
            "UserPolicyList": [
                {
                    "PolicyName": "DenyBillingAndIAMPolicy",
                    "PolicyDocument": {
                        "Version": "2012-10-17",
                        "Statement": {
                            "Effect": "Deny",
                            "Action": [
                                "aws-portal:*",
                                "iam:*"
                            ],
                            "Resource": "*"
                        }
                    }
                }
            ],
            "Path": "/",
            "AttachedManagedPolicies": [],
            "Arn": "arn:aws:iam::123456789012:user/Bob"
```

```
        },
        {
            "UserName": "Charlie",
            "GroupList": [
                "Dev"
            ],
            "CreateDate": "2013-10-14T18:33:56Z",
            "UserId": "AIDA1234567890EXAMPLE",
            "UserPolicyList": [],
            "Path": "/",
            "AttachedManagedPolicies": [],
            "Arn": "arn:aws:iam::123456789012:user/Charlie"
        }
    ],
    "Policies": [
        {
            "PolicyName": "create-update-delete-set-managed-policies",
            "CreateDate": "2015-02-06T19:58:34Z",
            "AttachmentCount": 1,
            "IsAttachable": true,
            "PolicyId": "ANPA1234567890EXAMPLE",
            "DefaultVersionId": "v1",
            "PolicyVersionList": [
                {
                    "CreateDate": "2015-02-06T19:58:34Z",
                    "VersionId": "v1",
                    "Document": {
                        "Version": "2012-10-17",
                        "Statement": {
                            "Effect": "Allow",
                            "Action": [
                                "iam:CreatePolicy",
                                "iam:CreatePolicyVersion",
                                "iam:DeletePolicy",
                                "iam:DeletePolicyVersion",
                                "iam:GetPolicy",
                                "iam:GetPolicyVersion",
                                "iam:ListPolicies",
                                "iam:ListPolicyVersions",
                                "iam:SetDefaultPolicyVersion"
                            ],
                            "Resource": "*"
                        }
                    },
```

```
                    "IsDefaultVersion": true
                }
            ],
            "Path": "/",
            "Arn": "arn:aws:iam::123456789012:policy/create-update-delete-set-
managed-policies",
            "UpdateDate": "2015-02-06T19:58:34Z"
        },
        {
            "PolicyName": "S3-read-only-specific-bucket",
            "CreateDate": "2015-01-21T21:39:41Z",
            "AttachmentCount": 1,
            "IsAttachable": true,
            "PolicyId": "ANPA1234567890EXAMPLE",
            "DefaultVersionId": "v1",
            "PolicyVersionList": [
                {
                    "CreateDate": "2015-01-21T21:39:41Z",
                    "VersionId": "v1",
                    "Document": {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
                                "Action": [
                                    "s3:Get*",
                                    "s3:List*"
                                ],
                                "Resource": [
                                    "arn:aws:s3:::example-bucket",
                                    "arn:aws:s3:::example-bucket/*"
                                ]
                            }
                        ]
                    },
                    "IsDefaultVersion": true
                }
            ],
            "Path": "/",
            "Arn": "arn:aws:iam::123456789012:policy/S3-read-only-specific-
bucket",
            "UpdateDate": "2015-01-21T23:39:41Z"
        },
        {
```

```
            "PolicyName": "AmazonEC2FullAccess",
            "CreateDate": "2015-02-06T18:40:15Z",
            "AttachmentCount": 1,
            "IsAttachable": true,
            "PolicyId": "ANPA1234567890EXAMPLE",
            "DefaultVersionId": "v1",
            "PolicyVersionList": [
                {
                    "CreateDate": "2014-10-30T20:59:46Z",
                    "VersionId": "v1",
                    "Document": {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Action": "ec2:*",
                                "Effect": "Allow",
                                "Resource": "*"
                            },
                            {
                                "Effect": "Allow",
                                "Action": "elasticloadbalancing:*",
                                "Resource": "*"
                            },
                            {
                                "Effect": "Allow",
                                "Action": "cloudwatch:*",
                                "Resource": "*"
                            },
                            {
                                "Effect": "Allow",
                                "Action": "autoscaling:*",
                                "Resource": "*"
                            }
                        ]
                    },
                    "IsDefaultVersion": true
                }
            ],
            "Path": "/",
            "Arn": "arn:aws:iam::aws:policy/AmazonEC2FullAccess",
            "UpdateDate": "2015-02-06T18:40:15Z"
        }
    ],
```

```
    "Marker": "EXAMPLEkakv9BCuUNFDtxWSyfzetYwEx2ADc8dnzfvERF5S6YMvXKx41t6gCl/
eeaCX3Jo94/bKqezEAg8TEVS99EKFLxm3jtbpl25FDWEXAMPLE",
    "IsTruncated": true
}
```

Para obter mais informações, consulte Diretrizes de auditoria de segurança da AWS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetAccountAuthorizationDetailsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_authorization_details(response_filter):
    """
    Gets an authorization detail report for the current account.

    :param response_filter: A list of resource types to include in the report,
 such
                            as users or roles. When not specified, all resources
                            are included.
    :return: The authorization detail report.
    """
    try:
        account_details = iam.meta.client.get_account_authorization_details(
            Filter=response_filter
        )
        logger.debug(account_details)
    except ClientError:
        logger.exception("Couldn't get details for your account.")
        raise
    else:
        return account_details
```

- Para obter detalhes da API, consulte a GetAccountAuthorizationDetailsReferência da API AWSSDK for Python (Boto3).

Obter uma política do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter a política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Trabalhar com a API IAM Policy Builder

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM policy.
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</
param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
 { PolicyArn = policyArn });
        return response.Policy;
    }
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::getPolicy(const Aws::String &policyArn,
                            const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetPolicyRequest request;
    request.SetPolicyArn(policyArn);

    auto outcome = iam.GetPolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error getting policy " << policyArn << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const auto &policy = outcome.GetResult().GetPolicy();
        std::cout << "Name: " << policy.GetPolicyName() << std::endl <<
                  "ID: " << policy.GetPolicyId() << std::endl << "Arn: " <<
                  policy.GetArn() << std::endl << "Description: " <<
                  policy.GetDescription() << std::endl << "CreateDate: " <<

 policy.GetCreateDate().ToGmtString(Aws::Utils::DateFormat::ISO_8601)
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como recuperar informações sobre a política gerenciada especificada

Este exemplo retorna detalhes sobre a política gerenciada cujo ARN é `arn:aws:iam::123456789012:policy/MySamplePolicy`.

```
aws iam get-policy \
    --policy-arn arn:aws:iam::123456789012:policy/MySamplePolicy
```

Saída:

```
{
    "Policy": {
        "PolicyName": "MySamplePolicy",
        "CreateDate": "2015-06-17T19:23;32Z",
        "AttachmentCount": 0,
        "IsAttachable": true,
        "PolicyId": "Z27SI6FQMGNQ2EXAMPLE1",
        "DefaultVersionId": "v1",
        "Path": "/",
        "Arn": "arn:aws:iam::123456789012:policy/MySamplePolicy",
        "UpdateDate": "2015-06-17T19:23:32Z"
    }
}
```

Para obter mais informações, consulte Políticas e permissões no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetPolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// GetPolicy gets data about a policy.
func (wrapper PolicyWrapper) GetPolicy(policyArn string) (*types.Policy, error) {
 var policy *types.Policy
 result, err := wrapper.IamClient.GetPolicy(context.TODO(), &iam.GetPolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't get policy %v. Here's why: %v\n", policyArn, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política.

```
import { GetPolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 */
export const getPolicy = (policyArn) => {
  const command = new GetPolicyCommand({
    PolicyArn: policyArn,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  PolicyArn: "arn:aws:iam::aws:policy/AWSLambdaExecute",
};

iam.getPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Policy.Description);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getIAMPolicy(policyArnVal: String?) {

    val request = GetPolicyRequest {
        policyArn = policyArnVal
```

```
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.getPolicy(request)
        println("Successfully retrieved policy ${response.policy?.policyName}")
    }
}
```

- Para obter detalhes da API, consulte a GetPolicyreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function getPolicy($policyArn)
    {
        return $this->customWaiter(function () use ($policyArn) {
            return $this->iamClient->getPolicy(['PolicyArn' => $policyArn]);
        });
    }
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement
```

- Para obter detalhes da API, consulte a GetPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Fetches an IAM policy by its ARN
# @param policy_arn [String] the ARN of the IAM policy to retrieve
# @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
def get_policy(policy_arn)
  response = @iam_client.get_policy(policy_arn: policy_arn)
  policy = response.policy
  @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
  policy
rescue Aws::IAM::Errors::NoSuchEntity
  @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
  raise
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
  raise
end
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for Ruby da API.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func getPolicy(arn: String) async throws -> IAMClientTypes.Policy {
    let input = GetPolicyInput(
        policyArn: arn
    )
    do {
        let output = try await client.getPolicy(input: input)
        guard let policy = output.policy else {
            throw ServiceHandlerError.noSuchPolicy
        }
        return policy
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte GetPolicya referência da API AWS SDK for Swift.

Obter uma versão de política do IAM usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter uma versão da política do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Políticas gerenciadas
- Trabalhar com a API IAM Policy Builder

CLI

AWS CLI

Como recuperar informações sobre a versão especificada da política gerenciada especificada

Este exemplo retorna o documento da política para a versão v2 da política cujo ARN é `arn:aws:iam::123456789012:policy/MyManagedPolicy`.

```
aws iam get-policy-version \
    --policy-arn arn:aws:iam::123456789012:policy/MyPolicy \
    --version-id v2
```

Saída:

```
{
    "PolicyVersion": {
        "Document": {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Action": "iam:*",
                    "Resource": "*"
                }
            ]
        },
        "VersionId": "v2",
        "IsDefaultVersion": true,
        "CreateDate": "2023-04-11T00:22:54+00:00"
    }
}
```

Para obter mais informações, consulte Políticas e permissões no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetPolicyVersionem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement
```

- Para obter detalhes da API, consulte a GetPolicyVersionReferência da API AWSSDK for Python (Boto3).

Obter um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter um perfil do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });

        return response.Role;
    }
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como obter informações sobre um perfil do IAM

O comando `get-role`, apresentado a seguir, obtém informações sobre o perfil denominado `Test-Role`.

```
aws iam get-role \
    --role-name Test-Role
```

Saída:

```
{
    "Role": {
        "Description": "Test Role",
        "AssumeRolePolicyDocument":"<URL-encoded-JSON>",
        "MaxSessionDuration": 3600,
        "RoleId": "AROA1234567890EXAMPLE",
        "CreateDate": "2019-11-13T16:45:56Z",
        "RoleName": "Test-Role",
```

```
        "Path": "/",
        "RoleLastUsed": {
            "Region": "us-east-1",
            "LastUsedDate": "2019-11-13T17:14:00Z"
        },
        "Arn": "arn:aws:iam::123456789012:role/Test-Role"
    }
}
```

O comando exibe a política de confiança anexada ao perfil. Para listar as políticas de permissões anexadas a um perfil, use o comando `list-role-policies`.

Para obter mais informações, consulte Criação de perfis do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetRoleem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// GetRole gets data about a role.
func (wrapper RoleWrapper) GetRole(roleName string) (*types.Role, error) {
 var role *types.Role
 result, err := wrapper.IamClient.GetRole(context.TODO(),
  &iam.GetRoleInput{RoleName: aws.String(roleName)})
```

```
 if err != nil {
  log.Printf("Couldn't get role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a função.

```
import { GetRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const getRole = (roleName) => {
  const command = new GetRoleCommand({
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function getRole($roleName)
    {
        return $this->customWaiter(function () use ($roleName) {
            return $this->iamClient->getRole(['RoleName' => $roleName]);
        });
    }
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_role(role_name):
    """
    Gets a role by name.

    :param role_name: The name of the role to retrieve.
    :return: The specified role.
    """
```

```
    try:
        role = iam.Role(role_name)
        role.load()  # calls GetRole to load attributes
        logger.info("Got role with arn %s.", role.arn)
    except ClientError:
        logger.exception("Couldn't get role named %s.", role_name)
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a GetRoleReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Gets data about a role.
#
# @param name [String] The name of the role to look up.
# @return [Aws::IAM::Role] The retrieved role.
def get_role(name)
  role = @iam_client.get_role({
                                role_name: name,
                              }).role
  puts("Got data for role '#{role.role_name}'. Its ARN is '#{role.arn}'.")
rescue Aws::Errors::ServiceError => e
  puts("Couldn't get data for role '#{name}' Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
else
  role
```

```
  end
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn get_role(
    client: &iamClient,
    role_name: String,
) -> Result<GetRoleOutput, SdkError<GetRoleError>> {
    let response = client.get_role().role_name(role_name).send().await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a GetRolereferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func getRole(name: String) async throws -> IAMClientTypes.Role {
    let input = GetRoleInput(
        roleName: name
    )
    do {
        let output = try await client.getRole(input: input)
        guard let role = output.role else {
            throw ServiceHandlerError.noSuchRole
        }
        return role
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte GetRolea referência da API AWS SDK for Swift.

Obter um certificado de servidor do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter um certificado de servidor do IAM.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::getServerCertificate(const Aws::String &certificateName,
```

```
                                        const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);

    auto outcome = iam.GetServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error getting server certificate " << certificateName
 <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
        const auto &certificate = outcome.GetResult().GetServerCertificate();
        std::cout << "Name: " <<

 certificate.GetServerCertificateMetadata().GetServerCertificateName()
                 << std::endl << "Body: " << certificate.GetCertificateBody() <<
                 std::endl << "Chain: " << certificate.GetCertificateChain() <<
                 std::endl;
    }

    return result;
}
```

- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter detalhes sobre um certificado de servidor em sua conta da AWS

O comando `get-server-certificate`, apresentado a seguir, recupera todos os detalhes sobre o certificado de servidor especificado em sua conta da AWS.

```
aws iam get-server-certificate \
    --server-certificate-name myUpdatedServerCertificate
```

Saída:

```
{
    "ServerCertificate": {
        "ServerCertificateMetadata": {
            "Path": "/",
            "ServerCertificateName": "myUpdatedServerCertificate",
            "ServerCertificateId": "ASCAEXAMPLE123EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:server-certificate/
myUpdatedServerCertificate",
            "UploadDate": "2019-04-22T21:13:44+00:00",
            "Expiration": "2019-10-15T22:23:16+00:00"
        },
        "CertificateBody": "-----BEGIN CERTIFICATE-----
            MIICiTCCAfICCQD6m7oRw0uXOjANBgkqhkiG9w0BAQUFADCBiDELMAkGA1UEBhMC
            VVMxCzAJBgNVBAgTAldBMRAwDgYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6
            b24xFDASBgNVBAsTC0lBTSBDb25zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAd
            BgkqhkiG9w0BCQEWEG5vb25lQGFtYXpvbi5jb20wHhcNMTEwNDI1MjA0NTIxWhcN
            MTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgTAldBMRAwDgYD
            VQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAsTC0lBTSBDb25z
            b2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQEWEG5vb25lQGFt
            YXpvbi5jb20wgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAMaK0dn+a4GmWIWJ
            21uUSfwfEvySWtC2XADZ4nB+BLYgVIk60CpiwsZ3G93vUEIO3IyNoH/f0wYK8m9T
            rDHudUZg3qX4waLG5M43q7Wgc/MbQITxOUSQv7c7ugFFDzQGBzZswY6786m86gpE
            Ibb3OhjZnzcvQAaRHhdlQWIMm2nrAgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCu4
            nUhVVxYUntneD9+h8Mg9q6q+auNKyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0Fkb
            FFBjvSfpJIlJ00zbhNYS5f6GuoEDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjSTb
            NYiytVbZPQUQ5Yaxu2jXnimvrszlaEXAMPLE=-----END CERTIFICATE-----",
        "CertificateChain": "-----BEGIN CERTIFICATE-----\nMIICiTCCAfICCQD6md
            7oRw0uXOjANBgkqhkiG9w0BAqQUFADCBiDELMAkGA1UEBhMCVVMxCzAJBgNVBAgT
            AldBMRAwDgYDVQQHEwdTZWF0drGxlMQ8wDQYDVQQKEwZBbWF6b24xFDASBgNVBAs
            TC0lBTSBDb25zb2xlMRIwEAYDVsQQDEwlUZXN0Q2lsYWMxHzAdBgkqhkiG9w0BCQ
            jb20wHhcNMTEwNDI1MjA0NTIxWhtcNMTIwNDI0MjA0NTIxWjCBiDELMAkGA1UEBh
            MCVVMxCzAJBgNVBAgTAldBMRAwDgsYDVQQHEwdTZWF0dGxlMQ8wDQYDVQQKEwZBb
            WF6b24xFDASBgNVBAsTC0lBTSBDb2d5zb2xlMRIwEAYDVQQDEwlUZXN0Q2lsYWMx
            HzAdBgkqhkiG9w0BCQEWEG5vb25lQGfFtYXpvbi5jb20wgZ8wDQYJKoZIhvcNAQE
            BBQADgY0AMIGJAoGBAMaK0dn+a4GmWIgWJ21uUSfwfEvySWtC2XADZ4nB+BLYgVI
```

```
            k60CpiwsZ3G93vUEIO3IyNoH/f0wYK8mh9TrDHudUZg3qX4waLG5M43q7Wgc/MbQ
            ITxOUSQv7c7ugFFDzQGBzZswY6786m86gjpEIbb3OhjZnzcvQAaRHhdlQWIMm2nr
            AgMBAAEwDQYJKoZIhvcNAQEFBQADgYEAtCku4nUhVVxYUntneD9+h8Mg9q6q+auN
            KyExzyLwaxlAoo7TJHidbtS4J5iNmZgXL0FlkbFFBjvSfpJIlJ00zbhNYS5f6Guo
            EDmFJl0ZxBHjJnyp378OD8uTs7fLvjx79LjS;TbNYiytVbZPQUQ5Yaxu2jXnimvw
            3rrszlaEWEG5vb25lQGFtsYXpvbiEXAMPLE=\n-----END CERTIFICATE-----"
    }
}
```

Para listar os certificados de servidor disponíveis em sua conta da AWS, use o comando `list-server-certificates`.

Para obter mais informações, consulte Gerenciar certificados de servidor no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetServerCertificateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um certificado do servidor.

```
import { GetServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
 * @returns
 */
export const getServerCertificate = async (certName) => {
  const command = new GetServerCertificateCommand({
```

```
    ServerCertificateName: certName,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

Obter o status de exclusão do perfil vinculado ao serviço do IAM usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter o status de exclusão de um perfil vinculado ao serviço do AWS Identity and Access Management (IAM).

CLI

AWS CLI

Como verificar o status de uma solicitação para excluir um perfil vinculado ao serviço

O exemplo de `get-service-linked-role-deletion-status`, apresentado a seguir, exibe o status de uma solicitação anterior para excluir um perfil vinculado ao serviço. A operação de exclusão ocorre de forma assíncrona. Ao fazer a solicitação, você obtém um valor `DeletionTaskId` fornecido como parâmetro para esse comando.

```
aws iam get-service-linked-role-deletion-status \
    --deletion-task-id task/aws-service-role/lex.amazonaws.com/
AWSServiceRoleForLexBots/1a2b3c4d-1234-abcd-7890-abcdeEXAMPLE
```

Saída:

```
{
"Status": "SUCCEEDED"
}
```

Para obter mais informações, consulte Usar perfis vinculados ao serviço no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetServiceLinkedRoleDeletionStatusem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  GetServiceLinkedRoleDeletionStatusCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} deletionTaskId
 */
export const getServiceLinkedRoleDeletionStatus = (deletionTaskId) => {
  const command = new GetServiceLinkedRoleDeletionStatusCommand({
    DeletionTaskId: deletionTaskId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetServiceLinkedRoleDeletionStatusa Referência AWS SDK for JavaScript da API.

Obter um resumo da utilização da conta do IAM usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter um resumo do uso da conta do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

CLI

AWS CLI

Como obter informações sobre o uso da entidade do IAM e das cotas do IAM na conta atual

O comando `get-account-summary`, apresentado a seguir, retorna informações sobre o uso atual da entidade do IAM e das cotas atuais da entidade do IAM na conta.

```
aws iam get-account-summary
```

Saída:

```
{
    "SummaryMap": {
        "UsersQuota": 5000,
        "GroupsQuota": 100,
        "InstanceProfiles": 6,
        "SigningCertificatesPerUserQuota": 2,
        "AccountAccessKeysPresent": 0,
        "RolesQuota": 250,
        "RolePolicySizeQuota": 10240,
        "AccountSigningCertificatesPresent": 0,
        "Users": 27,
        "ServerCertificatesQuota": 20,
        "ServerCertificates": 0,
        "AssumeRolePolicySizeQuota": 2048,
        "Groups": 7,
        "MFADevicesInUse": 1,
        "Roles": 3,
        "AccountMFAEnabled": 1,
        "MFADevices": 3,
        "GroupsPerUserQuota": 10,
        "GroupPolicySizeQuota": 5120,
        "InstanceProfilesQuota": 100,
        "AccessKeysPerUserQuota": 2,
        "Providers": 0,
        "UserPolicySizeQuota": 2048
    }
}
```

Para obter mais informações sobre as limitações de entidade, consulte IAM e cotas do AWS STS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetAccountSummaryem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_summary():
    """
    Gets a summary of account usage.

    :return: The summary of account usage.
    """
    try:
        summary = iam.AccountSummary()
        logger.debug(summary.summary_map)
    except ClientError:
        logger.exception("Couldn't get a summary for your account.")
        raise
    else:
        return summary.summary_map
```

- Para obter detalhes da API, consulte a GetAccountSummaryReferência da API AWSSDK for Python (Boto3).

Obter um usuário do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
    {
        var response = await _IAMService.GetUserAsync(new GetUserRequest
{ UserName = userName });
        return response.User;
    }
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_user_exists
#
# This function checks to see if the specified AWS Identity and Access Management
 (IAM) user already exists.
#
# Parameters:
#       $1 - The name of the IAM user to check.
#
# Returns:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
###############################################################################
function iam_user_exists() {
  local user_name
  user_name=$1

  # Check whether the IAM user already exists.
  # We suppress all output - we're interested only in the return code.

  local errors
  errors=$(aws iam get-user \
    --user-name "$user_name" 2>&1 >/dev/null)
```

```
  local error_code=${?}

  if [[ $error_code -eq 0 ]]; then
    return 0 # 0 in Bash script means true.
  else
    if [[ $errors != *"error"*"(NoSuchEntity)"* ]]; then
      aws_cli_error_log $error_code
      errecho "Error calling iam get-user $errors"
    fi

    return 1 # 1 in Bash script means false.
  fi
}
```

- Para obter detalhes da API, consulte GetUserem Referência de AWS CLI Comandos.

CLI

AWS CLI

Como obter informações sobre um usuário do IAM

O comando `get-user`, apresentado a seguir, obtém informações sobre o usuário do IAM denominado `Paulo`.

```
aws iam get-user \
    --user-name Paulo
```

Saída:

```
{
    "User": {
        "UserName": "Paulo",
        "Path": "/",
        "CreateDate": "2019-09-21T23:03:13Z",
        "UserId": "AIDA123456789EXAMPLE",
        "Arn": "arn:aws:iam::123456789012:user/Paulo"
    }
}
```

Para obter mais informações, consulte Gerenciar usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetUserem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// GetUser gets data about a user.
func (wrapper UserWrapper) GetUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.GetUser(context.TODO(), &iam.GetUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NoSuchEntityException:
    log.Printf("User %v does not exist.\n", userName)
    err = nil
   default:
    log.Printf("Couldn't get user %v. Here's why: %v\n", userName, err)
   }
  }
 } else {
```

```
  user = result.User
 }
 return user, err
}
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for Go da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Retrieves a user's details
 #
 # @param user_name [String] The name of the user to retrieve
 # @return [Aws::IAM::Types::User, nil] The user object if found, or nil if an
error occurred
 def get_user(user_name)
   response = @iam_client.get_user(user_name: user_name)
   response.user
 rescue Aws::IAM::Errors::NoSuchEntity
   @logger.error("User '#{user_name}' not found.")
   nil
 rescue Aws::IAM::Errors::ServiceError => e
   @logger.error("Error retrieving user '#{user_name}': #{e.message}")
   nil
 end
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for Ruby da API.

Obter dados sobre a última utilização de uma chave de acesso do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter dados sobre a última utilização de uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves de acesso

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::accessKeyLastUsed(const Aws::String &secretKeyID,
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetAccessKeyLastUsedRequest request;

    request.SetAccessKeyId(secretKeyID);

    Aws::IAM::Model::GetAccessKeyLastUsedOutcome outcome =
 iam.GetAccessKeyLastUsed(
            request);
```

```
    if (!outcome.IsSuccess()) {
        std::cerr << "Error querying last used time for access key " <<
                  secretKeyID << ":" << outcome.GetError().GetMessage() <<
 std::endl;
    }
    else {
        Aws::String lastUsedTimeString =
                outcome.GetResult()
                        .GetAccessKeyLastUsed()
                        .GetLastUsedDate()
                        .ToGmtString(Aws::Utils::DateFormat::ISO_8601);
        std::cout << "Access key " << secretKeyID << " last used at time " <<
                  lastUsedTimeString << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetAccessKeyLastUsedda Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como recuperar informações sobre quando a chave de acesso especificada foi usada pela última vez

O exemplo apresentado a seguir recupera informações sobre quando a chave de acesso `ABCDEXAMPLE` foi usada pela última vez.

```
aws iam get-access-key-last-used \
    --access-key-id ABCDEXAMPLE
```

Saída:

```
{
    "UserName":  "Bob",
    "AccessKeyLastUsed": {
```

```
        "Region": "us-east-1",
        "ServiceName": "iam",
        "LastUsedDate": "2015-06-16T22:45:00Z"
    }
}
```

Para obter mais informações, consulte Gerenciamento de chaves de acesso de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetAccessKeyLastUsedem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a chave de acesso.

```
import { GetAccessKeyLastUsedCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} accessKeyId
 */
export const getAccessKeyLastUsed = async (accessKeyId) => {
  const command = new GetAccessKeyLastUsedCommand({
    AccessKeyId: accessKeyId,
  });

  const response = await client.send(command);

  if (response.AccessKeyLastUsed?.LastUsedDate) {
    console.log(`
    ${accessKeyId} was last used by ${response.UserName} via
```

```
    the ${response.AccessKeyLastUsed.ServiceName} service on
    ${response.AccessKeyLastUsed.LastUsedDate.toISOString()}
    `);
  }

  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUsedda Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getAccessKeyLastUsed(
  { AccessKeyId: "ACCESS_KEY_ID" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data.AccessKeyLastUsed);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUsedda Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_last_use(key_id):
    """
    Gets information about when and how a key was last used.

    :param key_id: The ID of the key to look up.
    :return: Information about the key's last use.
    """
    try:
        response = iam.meta.client.get_access_key_last_used(AccessKeyId=key_id)
        last_used_date = response["AccessKeyLastUsed"].get("LastUsedDate", None)
        last_service = response["AccessKeyLastUsed"].get("ServiceName", None)
        logger.info(
            "Key %s was last used by %s on %s to access %s.",
            key_id,
            response["UserName"],
            last_used_date,
            last_service,
        )
    except ClientError:
        logger.exception("Couldn't get last use of key %s.", key_id)
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a GetAccessKeyLastUsedReferência da API AWSSDK for Python (Boto3).

Obter a política de senha da conta do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como obter a política de senha da conta do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
GetAccountPasswordPolicyRequest());
        return response.PasswordPolicy;
    }
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como visualizar a política de senha da conta atual

O comando `get-account-password-policy`, apresentado a seguir, exibe detalhes sobre a política de senha para a conta atual.

```
aws iam get-account-password-policy
```

Saída:

```
{
    "PasswordPolicy": {
        "AllowUsersToChangePassword": false,
        "RequireLowercaseCharacters": false,
        "RequireUppercaseCharacters": false,
        "MinimumPasswordLength": 8,
        "RequireNumbers": true,
        "RequireSymbols": true
    }
}
```

Se nenhuma política de senha estiver definida para a conta, o comando retornará um erro `NoSuchEntity`.

Para obter mais informações, consulte Definição de uma política de senhas de contas para usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetAccountPasswordPolicyem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
```

```
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
}



// GetAccountPasswordPolicy gets the account password policy for the current
 account.
// If no policy has been set, a NoSuchEntityException is error is returned.
func (wrapper AccountWrapper) GetAccountPasswordPolicy() (*types.PasswordPolicy,
 error) {
 var pwPolicy *types.PasswordPolicy
 result, err := wrapper.IamClient.GetAccountPasswordPolicy(context.TODO(),
  &iam.GetAccountPasswordPolicyInput{})
 if err != nil {
  log.Printf("Couldn't get account password policy. Here's why: %v\n", err)
 } else {
  pwPolicy = result.PasswordPolicy
 }
 return pwPolicy, err
}
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de senha da conta.

```
import {
```

```
  GetAccountPasswordPolicyCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const getAccountPasswordPolicy = async () => {
  const command = new GetAccountPasswordPolicyCommand({});

  const response = await client.send(command);
  console.log(response.PasswordPolicy);
  return response;
};
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function getAccountPasswordPolicy()
    {
        return $this->iamClient->getAccountPasswordPolicy();
    }
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def print_password_policy():
    """
    Prints the password policy for the account.
    """
    try:
        pw_policy = iam.AccountPasswordPolicy()
        print("Current account password policy:")
        print(
            f"\tallow_users_to_change_password:
 {pw_policy.allow_users_to_change_password}"
        )
        print(f"\texpire_passwords: {pw_policy.expire_passwords}")
        print(f"\thard_expiry: {pw_policy.hard_expiry}")
        print(f"\tmax_password_age: {pw_policy.max_password_age}")
        print(f"\tminimum_password_length: {pw_policy.minimum_password_length}")
        print(f"\tpassword_reuse_prevention:
 {pw_policy.password_reuse_prevention}")
        print(
            f"\trequire_lowercase_characters:
 {pw_policy.require_lowercase_characters}"
        )
        print(f"\trequire_numbers: {pw_policy.require_numbers}")
        print(f"\trequire_symbols: {pw_policy.require_symbols}")
        print(
            f"\trequire_uppercase_characters:
 {pw_policy.require_uppercase_characters}"
        )
        printed = True
    except ClientError as error:
        if error.response["Error"]["Code"] == "NoSuchEntity":
            print("The account does not have a password policy set.")
        else:
```

```
            logger.exception("Couldn't get account password policy.")
            raise
    else:
        return printed
```

- Para obter detalhes da API, consulte a GetAccountPasswordPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Class to manage IAM account password policies
class PasswordPolicyManager
  attr_accessor :iam_client, :logger

  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "IAMPolicyManager"
  end

  # Retrieves and logs the account password policy
  def print_account_password_policy
    begin
      response = @iam_client.get_account_password_policy
      @logger.info("The account password policy is:
 #{response.password_policy.to_h}")
    rescue Aws::IAM::Errors::NoSuchEntity
      @logger.info("The account does not have a password policy.")
    rescue Aws::Errors::ServiceError => e
```

```
      @logger.error("Couldn't print the account password policy. Error: #{e.code}
 - #{e.message}")
      raise
    end
  end
end
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn get_account_password_policy(
    client: &iamClient,
) -> Result<GetAccountPasswordPolicyOutput,
 SdkError<GetAccountPasswordPolicyError>> {
    let response = client.get_account_password_policy().send().await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a GetAccountPasswordPolicyreferência da API AWS SDK for Rust.

Listar provedores SAML para o IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar provedores SAML para o IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for .NET.

CLI

AWS CLI

Como listar os provedores SAML na conta da AWS

Este exemplo recupera a lista de provedores SAML 2.0 criados na conta da AWS atual.

```
aws iam list-saml-providers
```

Saída:

```
{
    "SAMLProviderList": [
```

```
        {
            "Arn": "arn:aws:iam::123456789012:saml-provider/SAML-ADFS",
            "ValidUntil": "2015-06-05T22:45:14Z",
            "CreateDate": "2015-06-05T22:45:14Z"
        }
    ]
}
```

Para obter mais informações, consulte Criação de provedores de identidade SAML do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListSAMLProviders na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
}



// ListSAMLProviders gets the SAML providers for the account.
func (wrapper AccountWrapper) ListSAMLProviders() ([]types.SAMLProviderListEntry,
 error) {
 var providers []types.SAMLProviderListEntry
 result, err := wrapper.IamClient.ListSAMLProviders(context.TODO(),
 &iam.ListSAMLProvidersInput{})
```

```
 if err != nil {
  log.Printf("Couldn't list SAML providers. Here's why: %v\n", err)
 } else {
  providers = result.SAMLProviderList
 }
 return providers, err
}
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Go.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os provedores SAML.

```
import { ListSAMLProvidersCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listSamlProviders = async () => {
  const command = new ListSAMLProvidersCommand({});

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for JavaScript.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listSAMLProviders()
    {
        return $this->iamClient->listSAMLProviders();
    }
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
def list_saml_providers(count):
    """
    Lists the SAML providers for the account.

    :param count: The maximum number of providers to list.
    """
    try:
        found = 0
```

```
        for provider in iam.saml_providers.limit(count):
            logger.info("Got SAML provider %s.", provider.arn)
            found += 1
        if found == 0:
            logger.info("Your account has no SAML providers.")
    except ClientError:
        logger.exception("Couldn't list SAML providers.")
        raise
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
class SamlProviderLister
  # Initializes the SamlProviderLister with IAM client and a logger.
  # @param iam_client [Aws::IAM::Client] The IAM client object.
  # @param logger [Logger] The logger object for logging output.
  def initialize(iam_client, logger = Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists up to a specified number of SAML providers for the account.
  # @param count [Integer] The maximum number of providers to list.
  # @return [Aws::IAM::Client::Response]
  def list_saml_providers(count)
    response = @iam_client.list_saml_providers
    response.saml_provider_list.take(count).each do |provider|
      @logger.info("\t#{provider.arn}")
```

```
    end
    response
  rescue Aws::Errors::ServiceError => e
    @logger.error("Couldn't list SAML providers. Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
    raise
  end
end
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
pub async fn list_saml_providers(
    client: &Client,
) -> Result<ListSamlProvidersOutput, SdkError<ListSAMLProvidersError>> {
    let response = client.list_saml_providers().send().await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte ListSAMLProvider na referência da API do AWS SDK for Rust.

Listar as chaves de acesso do IAM de um usuário usando um AWS SDK

Os exemplos de código a seguir mostram como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves de acesso

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_list_access_keys
#
# This function lists the access keys for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#
# Returns:
```

```
#       access_key_ids
#     And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_list_access_keys() {

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_list_access_keys"
    echo "Lists the AWS Identity and Access Management (IAM) access key IDs for
 the specified user."
    echo "  -u user_name   The name of the IAM user."
    echo ""
  }

  local user_name response
  local option OPTARG # Required to use getopts command in a function.
  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  response=$(aws iam list-access-keys \
    --user-name "$user_name" \
    --output text \
```

```
    --query 'AccessKeyMetadata[].AccessKeyId')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-access-keys operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListAccessKeysem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listAccessKeys(const Aws::String &userName,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccessKeysRequest request;
    request.SetUserName(userName);

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccessKeys(request);
        if (!outcome.IsSuccess()) {
```

```
            std::cerr << "Failed to list access keys for user " << userName
                      << ": " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(32) << "UserName" <<
                      std::setw(30) << "KeyID" << std::setw(20) << "Status" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &keys = outcome.GetResult().GetAccessKeyMetadata();
        const Aws::String DATE_FORMAT = "%Y-%m-%d";

        for (const auto &key: keys) {
            Aws::String statusString =
                    Aws::IAM::Model::StatusTypeMapper::GetNameForStatusType(
                            key.GetStatus());
            std::cout << std::left << std::setw(32) << key.GetUserName() <<
                      std::setw(30) << key.GetAccessKeyId() << std::setw(20) <<
                      statusString << std::setw(20) <<
                      key.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
 std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar os IDs da chave de acesso para um usuário do IAM

O comando `list-access-keys`, apresentado a seguir, lista os IDs das chaves de acesso para o usuário do IAM denominado Bob.

```
aws iam list-access-keys \
    --user-name Bob
```

Saída:

```
{
    "AccessKeyMetadata": [
        {
            "UserName": "Bob",
            "Status": "Active",
            "CreateDate": "2013-06-04T18:17:34Z",
            "AccessKeyId": "AKIAIOSFODNN7EXAMPLE"
        },
        {
            "UserName": "Bob",
            "Status": "Inactive",
            "CreateDate": "2013-06-06T20:42:26Z",
            "AccessKeyId": "AKIAI44QH8DHBEXAMPLE"
        }
    ]
}
```

Não é possível listar as chaves de acesso secretas para os usuários do IAM. Se as chaves de acesso secretas forem perdidas, você deverá criar novas chaves de acesso usando o comando `create-access-keys`.

Para obter mais informações, consulte Gerenciamento de chaves de acesso de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListAccessKeysem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListAccessKeys lists the access keys for the specified user.
func (wrapper UserWrapper) ListAccessKeys(userName string)
 ([]types.AccessKeyMetadata, error) {
 var keys []types.AccessKeyMetadata
 result, err := wrapper.IamClient.ListAccessKeys(context.TODO(),
 &iam.ListAccessKeysInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list access keys for user %v. Here's why: %v\n", userName,
 err)
 } else {
  keys = result.AccessKeyMetadata
 }
 return keys, err
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.AccessKeyMetadata;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListAccessKeysRequest;
import software.amazon.awssdk.services.iam.model.ListAccessKeysResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListAccessKeys {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <userName>\s

                Where:
                    userName - The name of the user for which access keys are
 retrieved.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String userName = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listKeys(iam, userName);
        System.out.println("Done");
        iam.close();
    }

    public static void listKeys(IamClient iam, String userName) {
        try {
            boolean done = false;
            String newMarker = null;

            while (!done) {
                ListAccessKeysResponse response;

                if (newMarker == null) {
                    ListAccessKeysRequest request =
ListAccessKeysRequest.builder()
                            .userName(userName)
                            .build();

                    response = iam.listAccessKeys(request);

                } else {
                    ListAccessKeysRequest request =
ListAccessKeysRequest.builder()
                            .userName(userName)
                            .marker(newMarker)
                            .build();

                    response = iam.listAccessKeys(request);
                }

                for (AccessKeyMetadata metadata : response.accessKeyMetadata()) {
                    System.out.format("Retrieved access key %s",
metadata.accessKeyId());
                }

                if (!response.isTruncated()) {
```

```
                    done = true;
                } else {
                    newMarker = response.marker();
                }
            }

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as chaves de acesso.

```
import { ListAccessKeysCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 *
 * @param {string} userName
 */
```

```
export async function* listAccessKeys(userName) {
  const command = new ListAccessKeysCommand({
    MaxItems: 5,
    UserName: userName,
  });

  /**
   * @type {import("@aws-sdk/client-iam").ListAccessKeysCommandOutput |
 undefined}
   */
  let response = await client.send(command);

  while (response?.AccessKeyMetadata?.length) {
    for (const key of response.AccessKeyMetadata) {
      yield key;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccessKeysCommand({
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 5,
  UserName: "IAM_USER_NAME",
};

iam.listAccessKeys(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listKeys(userNameVal: String?) {

    val request = ListAccessKeysRequest {
```

```
        userName = userNameVal
    }
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAccessKeys(request)
        response.accessKeyMetadata?.forEach { md ->
            println("Retrieved access key ${md.accessKeyId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAccessKeysreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_keys(user_name):
    """
    Lists the keys owned by the specified user.

    :param user_name: The name of the user.
    :return: The list of keys owned by the user.
    """
    try:
        keys = list(iam.User(user_name).access_keys.all())
        logger.info("Got %s access keys for %s.", len(keys), user_name)
    except ClientError:
        logger.exception("Couldn't get access keys for %s.", user_name)
        raise
    else:
        return keys
```

- Para obter detalhes da API, consulte a ListAccessKeysReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
  end
```

```
  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
#{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create
more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end

  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end

  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
```

```
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Ruby da API.

Listar aliases da conta do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar aliases de conta do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar sua conta

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool
AwsDoc::IAM::listAccountAliases(const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccountAliasesRequest request;

    bool done = false;
```

```
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccountAliases(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list account aliases: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        const auto &aliases = outcome.GetResult().GetAccountAliases();
        if (!header) {
            if (aliases.size() == 0) {
                std::cout << "Account has no aliases" << std::endl;
                break;
            }
            std::cout << std::left << std::setw(32) << "Alias" << std::endl;
            header = true;
        }

        for (const auto &alias: aliases) {
            std::cout << std::left << std::setw(32) << alias << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar os aliases da conta

O comando `list-account-aliases`, apresentado a seguir, lista os aliases para a conta atual.

```
aws iam list-account-aliases
```

Saída:

```
{
    "AccountAliases": [
    "mycompany"
    ]
}
```

Para obter mais informações, consulte O ID da sua conta da AWS e seu alias no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListAccountAliasesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListAccountAliasesResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListAccountAliases {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listAliases(iam);
        System.out.println("Done");
        iam.close();
    }

    public static void listAliases(IamClient iam) {
        try {
            ListAccountAliasesResponse response = iam.listAccountAliases();
            for (String alias : response.accountAliases()) {
                System.out.printf("Retrieved account alias %s", alias);
            }

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os aliases de conta.

```
import { ListAccountAliasesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 */
export async function* listAccountAliases() {
  const command = new ListAccountAliasesCommand({ MaxItems: 5 });

  let response = await client.send(command);

  while (response.AccountAliases?.length) {
    for (const alias of response.AccountAliases) {
      yield alias;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccountAliasesCommand({
          Marker: response.Marker,
          MaxItems: 5,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listAccountAliases({ MaxItems: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAliases() {

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAccountAliases(ListAccountAliasesRequest {})
        response.accountAliases?.forEach { alias ->
            println("Retrieved account alias $alias")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAccountAliasesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_aliases():
    """
    Gets the list of aliases for the current account. An account has at most one
 alias.

    :return: The list of aliases for the account.
    """
    try:
        response = iam.meta.client.list_account_aliases()
        aliases = response["AccountAliases"]
        if len(aliases) > 0:
            logger.info("Got aliases for your account: %s.", ",".join(aliases))
        else:
            logger.info("Got no aliases for your account.")
    except ClientError:
        logger.exception("Couldn't list aliases for your account.")
        raise
```

```
    else:
        return response["AccountAliases"]
```

- Para obter detalhes da API, consulte a ListAccountAliasesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists available AWS account aliases.
  def list_aliases
    response = @iam_client.list_account_aliases

    if response.account_aliases.count.positive?
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
```

```
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for Ruby da API.

Listar grupos do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar grupos do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }

        return groups;
    }
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os grupos do IAM para a conta atual

O comando `list-groups`, apresentado a seguir, lista os grupos do IAM na conta atual.

```
aws iam list-groups
```

Saída:

```
{
    "Groups": [
        {
            "Path": "/",
            "CreateDate": "2013-06-04T20:27:27.972Z",
            "GroupId": "AIDACKCEVSQ6C2EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:group/Admins",
            "GroupName": "Admins"
        },
        {
            "Path": "/",
            "CreateDate": "2013-04-16T20:30:42Z",
            "GroupId": "AIDGPMS9RO4H3FEXAMPLE",
            "Arn": "arn:aws:iam::123456789012:group/S3-Admins",
            "GroupName": "S3-Admins"
        }
    ]
}
```

Para obter mais informações, consulte Gerenciar grupos de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListGroupsem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// GroupWrapper encapsulates AWS Identity and Access Management (IAM) group
 actions
// used in the examples.
// It contains an IAM service client that is used to perform group actions.
type GroupWrapper struct {
```

```
 IamClient *iam.Client
}



// ListGroups lists up to maxGroups number of groups.
func (wrapper GroupWrapper) ListGroups(maxGroups int32) ([]types.Group, error) {
 var groups []types.Group
 result, err := wrapper.IamClient.ListGroups(context.TODO(),
 &iam.ListGroupsInput{
  MaxItems: aws.Int32(maxGroups),
 })
 if err != nil {
  log.Printf("Couldn't list groups. Here's why: %v\n", err)
 } else {
  groups = result.Groups
 }
 return groups, err
}
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os grupos.

```
import { ListGroupsCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
```

```
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 */
export async function* listGroups() {
  const command = new ListGroupsCommand({
    MaxItems: 10,
  });

  let response = await client.send(command);

  while (response.Groups?.length) {
    for (const group of response.Groups) {
      yield group;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListGroupsCommand({
          Marker: response.Marker,
          MaxItems: 10,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listGroups($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listGroupsArguments = [];
        if ($pathPrefix) {
            $listGroupsArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listGroupsArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listGroupsArguments["MaxItems"] = $maxItems;
        }

        return $this->iamClient->listGroups($listGroupsArguments);
    }
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_groups(count):
    """
    Lists the specified number of groups for the account.

    :param count: The number of groups to list.
    """
    try:
        for group in iam.groups.limit(count):
            logger.info("Group: %s", group.name)
```

```
    except ClientError:
        logger.exception("Couldn't list groups for the account.")
        raise
```

- Para obter detalhes da API, consulte a ListGroupsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# A class to manage IAM operations via the AWS SDK client
class IamGroupManager
  # Initializes the IamGroupManager class
  # @param iam_client [Aws::IAM::Client] An instance of the IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists up to a specified number of groups for the account.
  # @param count [Integer] The maximum number of groups to list.
  # @return [Aws::IAM::Client::Response]
  def list_groups(count)
    response = @iam_client.list_groups(max_items: count)
    response.groups.each do |group|
      @logger.info("\t#{group.group_name}")
    end
    response
  rescue Aws::Errors::ServiceError => e
    @logger.error("Couldn't list groups for the account. Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
```

```
    raise
  end
end
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_groups(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListGroupsOutput, SdkError<ListGroupsError>> {
    let response = client
        .list_groups()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListGroupsreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listGroups() async throws -> [String] {
    var groupList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListGroupsInput(marker: marker)
        let output = try await client.listGroups(input: input)

        guard let groups = output.groups else {
            return groupList
        }

        for group in groups {
            if let name = group.groupName {
                groupList.append(name)
            }
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return groupList
}
```

- Para obter detalhes da API, consulte ListGroupsa referência da API AWS SDK for Swift.

Listar políticas em linha para um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar políticas em linha para um perfil do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</
param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
        var listRolePoliciesPaginator =
 _IAMService.Paginators.ListRolePolicies(new ListRolePoliciesRequest { RoleName =
 roleName });
        var policyNames = new List<string>();

        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar as políticas anexadas a um perfil do IAM

O comando `list-role-policies`, apresentado a seguir, lista os nomes das políticas de permissões para o perfil do IAM especificado.

```
aws iam list-role-policies \
    --role-name Test-Role
```

Saída:

```
{
    "PolicyNames": [
        "ExamplePolicy"
    ]
}
```

Para visualizar a política de confiança anexada a um perfil, use o comando `get-role`. Para visualizar os detalhes de uma política de permissões, use o comando `get-role-policy`.

Para obter mais informações, consulte Criação de perfis do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListRolePoliciesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRolePolicies lists the inline policies for a role.
func (wrapper RoleWrapper) ListRolePolicies(roleName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListRolePolicies(context.TODO(),
 &iam.ListRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for role %v. Here's why: %v\n", roleName,
 err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as políticas.

```
import { ListRolePoliciesCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 *
 * @param {string} roleName
 */
export async function* listRolePolicies(roleName) {
  const command = new ListRolePoliciesCommand({
    RoleName: roleName,
    MaxItems: 10,
  });

  let response = await client.send(command);

  while (response.PolicyNames?.length) {
    for (const policyName of response.PolicyNames) {
      yield policyName;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListRolePoliciesCommand({
          RoleName: roleName,
          MaxItems: 10,
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listRolePolicies($roleName, $marker = "", $maxItems = 0)
    {
        $listRolePoliciesArguments = ['RoleName' => $roleName];
        if ($marker) {
            $listRolePoliciesArguments['Marker'] = $marker;
        }
        if ($maxItems) {
            $listRolePoliciesArguments['MaxItems'] = $maxItems;
        }
        return $this->customWaiter(function () use ($listRolePoliciesArguments) {
            return $this->iamClient-
>listRolePolicies($listRolePoliciesArguments);
        });
    }
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(role_name):
    """
    Lists inline policies for a role.

    :param role_name: The name of the role to query.
    """
    try:
        role = iam.Role(role_name)
        for policy in role.policies.all():
            logger.info("Got inline policy %s.", policy.name)
    except ClientError:
        logger.exception("Couldn't list inline policies for %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a ListRolePoliciesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists policy ARNs attached to a role
#
# @param role_name [String] The name of the role
# @return [Array<String>] List of policy ARNs
def list_attached_policy_arns(role_name)
  response = @iam_client.list_attached_role_policies(role_name: role_name)
  response.attached_policies.map(&:policy_arn)
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error listing policies attached to role: #{e.message}")
  []
end
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_role_policies(
    client: &iamClient,
    role_name: &str,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListRolePoliciesOutput, SdkError<ListRolePoliciesError>> {
    let response = client
        .list_role_policies()
        .role_name(role_name)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListRolePoliciesreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listRolePolicies(role: String) async throws -> [String] {
    var policyList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListRolePoliciesInput(
            marker: marker,
            roleName: role
        )
        let output = try await client.listRolePolicies(input: input)

        guard let policies = output.policyNames else {
            return policyList
        }

        for policy in policies {
            policyList.append(policy)
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return policyList
}
```

- Para obter detalhes da API, consulte ListRolePoliciesa referência da API AWS SDK for Swift.

Listar políticas do IAM em linha para um usuário com um AWS SDK

Os exemplos de código apresentados a seguir demonstram como listar políticas do IAM em linha para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

CLI

AWS CLI

Como listar as políticas para um usuário do IAM

O comando `list-user-policies`, apresentado a seguir, lista as políticas anexadas ao usuário do IAM denominado `Bob`.

```
aws iam list-user-policies \
    --user-name Bob
```

Saída:

```
{
    "PolicyNames": [
        "ExamplePolicy",
        "TestPolicy"
    ]
}
```

Para obter mais informações, consulte Criar um usuário do IAM na sua conta da AWS no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListUserPoliciesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUserPolicies lists the inline policies for the specified user.
func (wrapper UserWrapper) ListUserPolicies(userName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListUserPolicies(context.TODO(),
 &iam.ListUserPoliciesInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for user %v. Here's why: %v\n", userName,
 err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListUserPoliciesa Referência AWS SDK for Go da API.

Listar políticas do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar políticas do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Políticas gerenciadas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        return policies;
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listPolicies(const Aws::Client::ClientConfiguration
 &clientConfig) {
    const Aws::String DATE_FORMAT("%Y-%m-%d");
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListPoliciesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListPolicies(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam policies: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(64) << "Description" << std::setw(12) <<
                      "CreateDate" << std::endl;
            header = true;
        }

        const auto &policies = outcome.GetResult().GetPolicies();
        for (const auto &policy: policies) {
            std::cout << std::left << std::setw(55) <<
                      policy.GetPolicyName() << std::setw(30) <<
                      policy.GetPolicyId() << std::setw(80) << policy.GetArn() <<
                      std::setw(64) << policy.GetDescription() << std::setw(12)
 <<
                      policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
```

```
                        std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar as políticas gerenciadas disponíveis para sua conta da AWS

Este exemplo retorna uma compilação das duas primeiras políticas gerenciadas disponíveis na conta da AWS atual.

```
aws iam list-policies \
    --max-items 3
```

Saída:

```
{
    "Policies": [
        {
            "PolicyName": "AWSCloudTrailAccessPolicy",
            "PolicyId": "ANPAXQE2B5PJ7YEXAMPLE",
            "Arn": "arn:aws:iam::123456789012:policy/AWSCloudTrailAccessPolicy",
            "Path": "/",
            "DefaultVersionId": "v1",
            "AttachmentCount": 0,
            "PermissionsBoundaryUsageCount": 0,
            "IsAttachable": true,
```

```
            "CreateDate": "2019-09-04T17:43:42+00:00",
            "UpdateDate": "2019-09-04T17:43:42+00:00"
        },
        {
            "PolicyName": "AdministratorAccess",
            "PolicyId": "ANPAIWMBCKSKIEE64ZLYK",
            "Arn": "arn:aws:iam::aws:policy/AdministratorAccess",
            "Path": "/",
            "DefaultVersionId": "v1",
            "AttachmentCount": 6,
            "PermissionsBoundaryUsageCount": 0,
            "IsAttachable": true,
            "CreateDate": "2015-02-06T18:39:46+00:00",
            "UpdateDate": "2015-02-06T18:39:46+00:00"
        },
        {
            "PolicyName": "PowerUserAccess",
            "PolicyId": "ANPAJYRXTHIB4FOVS3ZXS",
            "Arn": "arn:aws:iam::aws:policy/PowerUserAccess",
            "Path": "/",
            "DefaultVersionId": "v5",
            "AttachmentCount": 1,
            "PermissionsBoundaryUsageCount": 0,
            "IsAttachable": true,
            "CreateDate": "2015-02-06T18:39:47+00:00",
            "UpdateDate": "2023-07-06T22:04:00+00:00"
        }
    ],
    "NextToken": "EXAMPLErZXIiOiBudWxsLCAiYm90b190cnVuY2F0ZV9hbW91bnQiOiA4fQ=="
}
```

Para obter mais informações, consulte Políticas e permissões no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListPoliciesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// ListPolicies gets up to maxPolicies policies.
func (wrapper PolicyWrapper) ListPolicies(maxPolicies int32) ([]types.Policy,
 error) {
 var policies []types.Policy
 result, err := wrapper.IamClient.ListPolicies(context.TODO(),
 &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPolicies),
 })
 if err != nil {
  log.Printf("Couldn't list policies. Here's why: %v\n", err)
 } else {
  policies = result.Policies
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as políticas.

```
import { ListPoliciesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 *
 */
export async function* listPolicies() {
  const command = new ListPoliciesCommand({
    MaxItems: 10,
    OnlyAttached: false,
    // List only the customer managed policies in your Amazon Web Services
 account.
    Scope: "Local",
  });

  let response = await client.send(command);

  while (response.Policies?.length) {
    for (const policy of response.Policies) {
      yield policy;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListPoliciesCommand({
          Marker: response.Marker,
```

```
          MaxItems: 10,
          OnlyAttached: false,
          Scope: "Local",
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listPolicies($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listPoliciesArguments = [];
        if ($pathPrefix) {
            $listPoliciesArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listPoliciesArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listPoliciesArguments["MaxItems"] = $maxItems;
        }
```

```
        return $this->iamClient->listPolicies($listPoliciesArguments);
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(scope):
    """
    Lists the policies in the current account.

    :param scope: Limits the kinds of policies that are returned. For example,
                  'Local' specifies that only locally managed policies are
 returned.
    :return: The list of policies.
    """
    try:
        policies = list(iam.policies.filter(Scope=scope))
        logger.info("Got %s policies in scope '%s'.", len(policies), scope)
    except ClientError:
        logger.exception("Couldn't get policies for scope '%s'.", scope)
        raise
    else:
        return policies
```

- Para obter detalhes da API, consulte a ListPoliciesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
```

```
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
```

```
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_policies(
    client: iamClient,
    path_prefix: String,
) -> Result<Vec<String>, SdkError<ListPoliciesError>> {
    let list_policies = client
        .list_policies()
        .path_prefix(path_prefix)
        .scope(PolicyScopeType::Local)
        .into_paginator()
        .items()
        .send()
        .try_collect()
        .await?;
```

```
    let policy_names = list_policies
        .into_iter()
        .map(|p| {
            let name = p
                .policy_name
                .unwrap_or_else(|| "Missing Policy Name".to_string());
            println!("{}", name);
            name
        })
        .collect();

    Ok(policy_names)
}
```

- Para obter detalhes da API, consulte a ListPoliciesreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func listPolicies() async throws -> [MyPolicyRecord] {
        var policyList: [MyPolicyRecord] = []
        var marker: String? = nil
        var isTruncated: Bool

        repeat {
            let input = ListPoliciesInput(marker: marker)
```

```
            let output = try await client.listPolicies(input: input)

            guard let policies = output.policies else {
                return policyList
            }

            for policy in policies {
                guard   let name = policy.policyName,
                        let id = policy.policyId,
                        let arn = policy.arn else {
                    throw ServiceHandlerError.noSuchPolicy
                }
                policyList.append(MyPolicyRecord(name: name, id: id, arn: arn))
            }
            marker = output.marker
            isTruncated = output.isTruncated
        } while isTruncated == true
        return policyList
    }
```

- Para obter detalhes da API, consulte ListPoliciesa referência da API AWS SDK for Swift.

Listar políticas anexadas a um perfil do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar políticas do IAM a um perfil do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
```

```
    public async Task<List<AttachedPolicyType>>
 ListAttachedRolePoliciesAsync(string roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
 _IAMService.Paginators.ListAttachedRolePolicies(new
 ListAttachedRolePoliciesRequest { RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar todas as políticas gerenciadas anexadas ao perfil especificado

Este comando retorna os nomes e os ARNs das políticas gerenciadas anexadas ao perfil do IAM denominado `SecurityAuditRole` na conta da AWS.

```
aws iam list-attached-role-policies \
    --role-name SecurityAuditRole
```

Saída:

```
{
    "AttachedPolicies": [
        {
            "PolicyName": "SecurityAudit",
            "PolicyArn": "arn:aws:iam::aws:policy/SecurityAudit"
        }
    ],
```

```
    "IsTruncated": false
}
```

Para obter mais informações, consulte Políticas e permissões no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListAttachedRolePoliciesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListAttachedRolePolicies lists the policies that are attached to the specified
 role.
func (wrapper RoleWrapper) ListAttachedRolePolicies(roleName string)
 ([]types.AttachedPolicy, error) {
 var policies []types.AttachedPolicy
 result, err := wrapper.IamClient.ListAttachedRolePolicies(context.TODO(),
 &iam.ListAttachedRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list attached policies for role %v. Here's why: %v\n",
 roleName, err)
 } else {
```

```
  policies = result.AttachedPolicies
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Lista as políticas que estão anexadas a uma função.

```
import {
  ListAttachedRolePoliciesCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 * @param {string} roleName
 */
export async function* listAttachedRolePolicies(roleName) {
  const command = new ListAttachedRolePoliciesCommand({
    RoleName: roleName,
  });

  let response = await client.send(command);
```

```
  while (response.AttachedPolicies?.length) {
    for (const policy of response.AttachedPolicies) {
      yield policy;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAttachedRolePoliciesCommand({
          RoleName: roleName,
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listAttachedRolePolicies($roleName, $pathPrefix = "", $marker
 = "", $maxItems = 0)
    {
        $listAttachRolePoliciesArguments = ['RoleName' => $roleName];
        if ($pathPrefix) {
```

```
            $listAttachRolePoliciesArguments['PathPrefix'] = $pathPrefix;
        }
        if ($marker) {
            $listAttachRolePoliciesArguments['Marker'] = $marker;
        }
        if ($maxItems) {
            $listAttachRolePoliciesArguments['MaxItems'] = $maxItems;
        }
        return $this->iamClient-
>listAttachedRolePolicies($listAttachRolePoliciesArguments);
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_attached_policies(role_name):
    """
    Lists policies attached to a role.

    :param role_name: The name of the role to query.
    """
    try:
        role = iam.Role(role_name)
        for policy in role.attached_policies.all():
            logger.info("Got policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't list attached policies for %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a ListAttachedRolePoliciesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
```

```
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not
exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
```

```
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_attached_role_policies(
    client: &iamClient,
    role_name: String,
    path_prefix: Option<String>,
    marker: Option<String>,
```

```
    max_items: Option<i32>,
) -> Result<ListAttachedRolePoliciesOutput,
 SdkError<ListAttachedRolePoliciesError>> {
    let response = client
        .list_attached_role_policies()
        .role_name(role_name)
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListAttachedRolePoliciesreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Returns a list of AWS Identity and Access Management (IAM) policies
    /// that are attached to the role.
    ///
    /// - Parameter role: The IAM role to return the policy list for.
```

```
    ///
    /// - Returns: An array of `IAMClientTypes.AttachedPolicy` objects
    ///   describing each managed policy that's attached to the role.
    public func listAttachedRolePolicies(role: String) async throws ->
[IAMClientTypes.AttachedPolicy] {
        var policyList: [IAMClientTypes.AttachedPolicy] = []
        var marker: String? = nil
        var isTruncated: Bool

        repeat {
            let input = ListAttachedRolePoliciesInput(
                marker: marker,
                roleName: role
            )
            let output = try await client.listAttachedRolePolicies(input: input)

            guard let attachedPolicies = output.attachedPolicies else {
                return policyList
            }

            for attachedPolicy in attachedPolicies {
                policyList.append(attachedPolicy)
            }
            marker = output.marker
            isTruncated = output.isTruncated
        } while isTruncated == true
        return policyList
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa referência da API AWS SDK for Swift.

Listar perfis do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar perfis do IAM.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();

        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os perfis do IAM para a conta atual

O comando `list-roles`, apresentado a seguir, lista os perfis do IAM para a conta atual.

```
aws iam list-roles
```

Saída:

```
{
    "Roles": [
        {
            "Path": "/",
            "RoleName": "ExampleRole",
            "RoleId": "AROAJ52OTH4H7LEXAMPLE",
            "Arn": "arn:aws:iam::123456789012:role/ExampleRole",
            "CreateDate": "2017-09-12T19:23:36+00:00",
            "AssumeRolePolicyDocument": {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Sid": "",
                        "Effect": "Allow",
                        "Principal": {
                            "Service": "ec2.amazonaws.com"
                        },
                        "Action": "sts:AssumeRole"
                    }
                ]
            },
            "MaxSessionDuration": 3600
        },
        {
            "Path": "/example_path/",
            "RoleName": "ExampleRoleWithPath",
            "RoleId": "AROAI4QRP7UFT7EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:role/example_path/
ExampleRoleWithPath",
            "CreateDate": "2023-09-21T20:29:38+00:00",
            "AssumeRolePolicyDocument": {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Sid": "",
                        "Effect": "Allow",
                        "Principal": {
                            "Service": "ec2.amazonaws.com"
                        },
                        "Action": "sts:AssumeRole"
                    }
                ]
```

```
            },
            "MaxSessionDuration": 3600
        }
    ]
}
```

Para obter mais informações, consulte Criação de perfis do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListRolesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRoles gets up to maxRoles roles.
func (wrapper RoleWrapper) ListRoles(maxRoles int32) ([]types.Role, error) {
 var roles []types.Role
 result, err := wrapper.IamClient.ListRoles(context.TODO(),
  &iam.ListRolesInput{MaxItems: aws.Int32(maxRoles)},
 )
 if err != nil {
  log.Printf("Couldn't list roles. Here's why: %v\n", err)
 } else {
  roles = result.Roles
 }
```

```
 return roles, err
}
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os perfis.

```
import { ListRolesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 *
 */
export async function* listRoles() {
  const command = new ListRolesCommand({
    MaxItems: 10,
  });

  /**
   * @type {import("@aws-sdk/client-iam").ListRolesCommandOutput | undefined}
   */
  let response = await client.send(command);

  while (response?.Roles?.length) {
    for (const role of response.Roles) {
```

```
      yield role;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListRolesCommand({
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    /**
     * @param string $pathPrefix
     * @param string $marker
     * @param int $maxItems
     * @return Result
     * $roles = $service->listRoles();
     */
    public function listRoles($pathPrefix = "", $marker = "", $maxItems = 0)
    {
```

```
        $listRolesArguments = [];
        if ($pathPrefix) {
            $listRolesArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listRolesArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listRolesArguments["MaxItems"] = $maxItems;
        }
        return $this->iamClient->listRoles($listRolesArguments);
    }
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_roles(count):
    """
    Lists the specified number of roles for the account.

    :param count: The number of roles to list.
    """
    try:
        roles = list(iam.roles.limit(count=count))
        for role in roles:
            logger.info("Role: %s", role.name)
    except ClientError:
        logger.exception("Couldn't list roles for the account.")
        raise
    else:
        return roles
```

- Para obter detalhes da API, consulte a ListRolesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists IAM roles up to a specified count.
# @param count [Integer] the maximum number of roles to list.
# @return [Array<String>] the names of the roles.
def list_roles(count)
  role_names = []
  roles_counted = 0

  @iam_client.list_roles.each_page do |page|
    page.roles.each do |role|
      break if roles_counted >= count
      @logger.info("\t#{roles_counted + 1}: #{role.role_name}")
      role_names << role.role_name
      roles_counted += 1
    end
    break if roles_counted >= count
  end

  role_names
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Couldn't list roles for the account. Here's why:")
  @logger.error("\t#{e.code}: #{e.message}")
  raise
end
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_roles(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListRolesOutput, SdkError<ListRolesError>> {
    let response = client
        .list_roles()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListRolesreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listRoles() async throws -> [String] {
    var roleList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListRolesInput(marker: marker)
        let output = try await client.listRoles(input: input)

        guard let roles = output.roles else {
            return roleList
        }

        for role in roles {
            if let name = role.roleName {
                roleList.append(name)
            }
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return roleList
}
```

- Para obter detalhes da API, consulte ListRolesa referência da API AWS SDK for Swift.

Listar certificados de servidor do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar os certificados de servidor do IAM.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listServerCertificates(
        const Aws::Client::ClientConfiguration &clientConfig) {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";

    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListServerCertificatesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListServerCertificates(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list server certificates: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(14) << "UploadDate" << std::setw(14) <<
                      "ExpirationDate" << std::endl;
            header = true;
        }

        const auto &certificates =
                outcome.GetResult().GetServerCertificateMetadataList();

        for (const auto &certificate: certificates) {
            std::cout << std::left << std::setw(55) <<
                      certificate.GetServerCertificateName() << std::setw(30) <<
                      certificate.GetServerCertificateId() << std::setw(80) <<
```

```
                        certificate.GetArn() << std::setw(14) <<

 certificate.GetUploadDate().ToGmtString(DATE_FORMAT.c_str()) <<
                        std::setw(14) <<

 certificate.GetExpiration().ToGmtString(DATE_FORMAT.c_str()) <<
                        std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar os certificados de servidor em sua conta da AWS

O comando `list-server-certificates`, apresentado a seguir, lista todos os certificados de servidor armazenados e disponíveis para uso em sua conta da AWS.

```
aws iam list-server-certificates
```

Saída:

```
{
    "ServerCertificateMetadataList": [
        {
            "Path": "/",
            "ServerCertificateName": "myUpdatedServerCertificate",
```

```
            "ServerCertificateId": "ASCAEXAMPLE123EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:server-certificate/
myUpdatedServerCertificate",
            "UploadDate": "2019-04-22T21:13:44+00:00",
            "Expiration": "2019-10-15T22:23:16+00:00"
        },
        {
            "Path": "/cloudfront/",
            "ServerCertificateName": "MyTestCert",
            "ServerCertificateId": "ASCAEXAMPLE456EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:server-certificate/Org1/Org2/
MyTestCert",
            "UploadDate": "2015-04-21T18:14:16+00:00",
            "Expiration": "2018-01-14T17:52:36+00:00"
        }
    ]
}
```

Para obter mais informações, consulte Gerenciar certificados de servidor no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListServerCertificatesem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os certificados.

```
import { ListServerCertificatesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
```

```
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to
 simplify this.
 *
 */
export async function* listServerCertificates() {
  const command = new ListServerCertificatesCommand({});
  let response = await client.send(command);

  while (response.ServerCertificateMetadataList?.length) {
    for await (const cert of response.ServerCertificateMetadataList) {
      yield cert;
    }

    if (response.IsTruncated) {
      response = await client.send(new ListServerCertificatesCommand({}));
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
```

```
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listServerCertificates({}, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
```

```
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates

    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
#{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
      new_server_certificate_name: new_name
    )
    @logger.info("Server certificate name updated from '#{current_name}' to
'#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
```

```
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for Ruby da API.

Listar usuários do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar usuários somente leitura e leitura/gravação usando

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM users.
    /// </summary>
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
 ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}
```

```
##############################################################################
# function iam_list_users
#
# List the IAM users in the account.
#
# Returns:
#       The list of users names
#    And:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
##############################################################################
function iam_list_users() {
  local option OPTARG # Required to use getopts command in a function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_list_users"
    echo "Lists the AWS Identity and Access Management (IAM) user in the
 account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "h" option; do
    case "${option}" in
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  local response

  response=$(aws iam list-users \
    --output text \
    --query "Users[].UserName")
  error_code=${?}
```

```
  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-users operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListUsersem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listUsers(const Aws::Client::ClientConfiguration &clientConfig)
 {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListUsersRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListUsers(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam users:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
```

```
            std::cout << std::left << std::setw(32) << "Name" <<
                      std::setw(30) << "ID" << std::setw(64) << "Arn" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &users = outcome.GetResult().GetUsers();
        for (const auto &user: users) {
            std::cout << std::left << std::setw(32) << user.GetUserName() <<
                      std::setw(30) << user.GetUserId() << std::setw(64) <<
                      user.GetArn() << std::setw(20) <<
                      user.GetCreateDate().ToGmtString(DATE_FORMAT.c_str())
                      << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar os usuários do IAM

O comando `list-users`, apresentado a seguir, lista os usuários do IAM na conta atual.

```
aws iam list-users
```

Saída:

```
{
    "Users": [
```

```
        {
            "UserName": "Adele",
            "Path": "/",
            "CreateDate": "2013-03-07T05:14:48Z",
            "UserId": "AKIAI44QH8DHBEXAMPLE",
            "Arn": "arn:aws:iam::123456789012:user/Adele"
        },
        {
            "UserName": "Bob",
            "Path": "/",
            "CreateDate": "2012-09-21T23:03:13Z",
            "UserId": "AKIAIOSFODNN7EXAMPLE",
            "Arn": "arn:aws:iam::123456789012:user/Bob"
        }
    ]
}
```

Para obter mais informações, consulte Listagem de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte ListUsersem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUsers gets up to maxUsers number of users.
```

```
func (wrapper UserWrapper) ListUsers(maxUsers int32) ([]types.User, error) {
 var users []types.User
 result, err := wrapper.IamClient.ListUsers(context.TODO(), &iam.ListUsersInput{
  MaxItems: aws.Int32(maxUsers),
 })
 if err != nil {
  log.Printf("Couldn't list users. Here's why: %v\n", err)
 } else {
  users = result.Users
 }
 return users, err
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.AttachedPermissionsBoundary;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListUsersRequest;
import software.amazon.awssdk.services.iam.model.ListUsersResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.User;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListUsers {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listAllUsers(iam);
        System.out.println("Done");
        iam.close();
    }

    public static void listAllUsers(IamClient iam) {
        try {
            boolean done = false;
            String newMarker = null;
            while (!done) {
                ListUsersResponse response;
                if (newMarker == null) {
                    ListUsersRequest request =
 ListUsersRequest.builder().build();
                    response = iam.listUsers(request);
                } else {
                    ListUsersRequest request = ListUsersRequest.builder()
                            .marker(newMarker)
                            .build();

                    response = iam.listUsers(request);
                }

                for (User user : response.users()) {
                    System.out.format("\n Retrieved user %s", user.userName());
                    AttachedPermissionsBoundary permissionsBoundary =
 user.permissionsBoundary();
                    if (permissionsBoundary != null)
                        System.out.format("\n Permissions boundary details %s",

 permissionsBoundary.permissionsBoundaryTypeAsString());
                }

                if (!response.isTruncated()) {
```

```
                    done = true;
                } else {
                    newMarker = response.marker();
                }
            }

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os usuários.

```
import { ListUsersCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listUsers = async () => {
  const command = new ListUsersCommand({ MaxItems: 10 });

  const response = await client.send(command);
  response.Users?.forEach(({ UserName, CreateDate }) => {
    console.log(`${UserName} created on: ${CreateDate}`);
  });
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 10,
};

iam.listUsers(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var users = data.Users || [];
    users.forEach(function (user) {
      console.log("User " + user.UserName + " created", user.CreateDate);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllUsers() {

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listUsers(ListUsersRequest { })
        response.users?.forEach { user ->
            println("Retrieved user ${user.userName}")
            val permissionsBoundary = user.permissionsBoundary
            if (permissionsBoundary != null)
                println("Permissions boundary details
 ${permissionsBoundary.permissionsBoundaryType}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listUsers($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listUsersArguments = [];
        if ($pathPrefix) {
            $listUsersArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listUsersArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listUsersArguments["MaxItems"] = $maxItems;
        }

        return $this->iamClient->listUsers($listUsersArguments);
    }
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_users():
    """
    Lists the users in the current account.

    :return: The list of users.
    """
    try:
        users = list(iam.users.all())
        logger.info("Got %s users.", len(users))
```

```
    except ClientError:
        logger.exception("Couldn't get users.")
        raise
    else:
        return users
```

- Para obter detalhes da API, consulte a ListUsersReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists all users in the AWS account
#
# @return [Array<Aws::IAM::Types::User>] An array of user objects
def list_users
  users = []
  @iam_client.list_users.each_page do |page|
    page.users.each do |user|
      users << user
    end
  end
  users
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error listing users: #{e.message}")
  []
end
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_users(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListUsersOutput, SdkError<ListUsersError>> {
    let response = client
        .list_users()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listUsers() async throws -> [MyUserRecord] {
    var userList: [MyUserRecord] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListUsersInput(marker: marker)
        let output = try await client.listUsers(input: input)

        guard let users = output.users else {
            return userList
        }

        for user in users {
            if let id = user.userId, let name = user.userName {
                userList.append(MyUserRecord(id: id, name: name))
            }
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return userList
}
```

- Para obter detalhes da API, consulte ListUsersa referência da API AWS SDK for Swift.

Remover um usuário do IAM de um grupo usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como remover um usuário de um grupo do IAM.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar um grupo e adicionar um usuário

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
    /// <param name="groupName">The name of the IAM group to remove the user
from.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
_IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte RemoveUserFromGroupa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como remover um usuário de um grupo do IAM

O comando `remove-user-from-group`, apresentado a seguir, remove o usuário denominado `Bob` do grupo do IAM denominado `Admins`.

```
aws iam remove-user-from-group \
    --user-name Bob \
    --group-name Admins
```

Este comando não produz saída.

Para obter mais informações, consulte Adicionar e remover usuários de um grupo de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte RemoveUserFromGroupem Referência de AWS CLI Comandos.

Atualizar um certificado de servidor do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar um certificado de servidor do IAM.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateServerCertificate(const Aws::String
 &currentCertificateName,
                                          const Aws::String &newCertificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
```

```
    Aws::IAM::Model::UpdateServerCertificateRequest request;
    request.SetServerCertificateName(currentCertificateName);
    request.SetNewServerCertificateName(newCertificateName);

    auto outcome = iam.UpdateServerCertificate(request);
    bool result = true;
    if (outcome.IsSuccess()) {
        std::cout << "Server certificate " << currentCertificateName
                  << " successfully renamed as " << newCertificateName
                  << std::endl;
    }
    else {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error changing name of server certificate " <<
                      currentCertificateName << " to " << newCertificateName <<
 ":" <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << currentCertificateName
                      << "' not found." << std::endl;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte UpdateServerCertificate a Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como alterar o caminho ou o nome de um certificado de servidor em sua conta da AWS

O comando `update-server-certificate`, apresentado a seguir, altera o nome do certificado de `myServerCertificate` para `myUpdatedServerCertificate`. Também altera o caminho para que `/cloudfront/` possa ser acessado pelo CloudFront serviço da

Amazon. Este comando não produz saída. É possível visualizar os resultados da atualização ao executar o comando `list-server-certificates`.

```
aws-iam update-server-certificate \
    --server-certificate-name myServerCertificate \
    --new-server-certificate-name myUpdatedServerCertificate \
    --new-path /cloudfront/
```

Este comando não produz saída.

Para obter mais informações, consulte Gerenciar certificados de servidor no IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte UpdateServerCertificateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize um certificado do servidor.

```
import { UpdateServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentName
 * @param {string} newName
 */
export const updateServerCertificate = (currentName, newName) => {
  const command = new UpdateServerCertificateCommand({
    ServerCertificateName: currentName,
    NewServerCertificateName: newName,
  });
```

```
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  ServerCertificateName: "CERTIFICATE_NAME",
  NewServerCertificateName: "NEW_CERTIFICATE_NAME",
};

iam.updateServerCertificate(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates
```

```
    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
 #{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
      new_server_certificate_name: new_name
    )
    @logger.info("Server certificate name updated from '#{current_name}' to
 '#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for Ruby da API.

Atualizar um usuário do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criar usuários somente leitura e leitura/gravação usando

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateUser(const Aws::String &currentUserName,
                             const Aws::String &newUserName,
                             const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::UpdateUserRequest request;
    request.SetUserName(currentUserName);
    request.SetNewUserName(newUserName);

    auto outcome = iam.UpdateUser(request);
    if (outcome.IsSuccess()) {
        std::cout << "IAM user " << currentUserName <<
                  " successfully updated with new user name " << newUserName <<
```

```
                    std::endl;
    }
    else {
        std::cerr << "Error updating user name for IAM user " << currentUserName
 <<
                    ":" << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como alterar o nome de um usuário do IAM

O comando `update-user`, apresentado a seguir, altera o nome do usuário do IAM de `Bob` para `Robert`.

```
aws iam update-user \
    --user-name Bob \
    --new-user-name Robert
```

Este comando não produz saída.

Para obter mais informações, consulte Renomeação de um grupo de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte UpdateUserem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.UpdateUserRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <curName> <newName>\s

                Where:
                    curName - The current user name.\s
                    newName - An updated user name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String curName = args[0];
```

```
        String newName = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        updateIAMUser(iam, curName, newName);
        System.out.println("Done");
        iam.close();
    }

    public static void updateIAMUser(IamClient iam, String curName, String
 newName) {
        try {
            UpdateUserRequest request = UpdateUserRequest.builder()
                    .userName(curName)
                    .newUserName(newName)
                    .build();

            iam.updateUser(request);
            System.out.printf("Successfully updated user to username %s",
 newName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize o usuário.

```
import { UpdateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentUserName
 * @param {string} newUserName
 */
export const updateUser = (currentUserName, newUserName) => {
  const command = new UpdateUserCommand({
    UserName: currentUserName,
    NewUserName: newUserName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
  NewUserName: process.argv[3],
};

iam.updateUser(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateIAMUser(curName: String?, newName: String?) {

    val request = UpdateUserRequest {
        userName = curName
        newUserName = newName
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.updateUser(request)
        println("Successfully updated user to $newName")
    }
}
```

- Para obter detalhes da API, consulte a UpdateUserreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_user(user_name, new_user_name):
    """
    Updates a user's name.
```

```
    :param user_name: The current name of the user to update.
    :param new_user_name: The new name to assign to the user.
    :return: The updated user.
    """
    try:
        user = iam.User(user_name)
        user.update(NewUserName=new_user_name)
        logger.info("Renamed %s to %s.", user_name, new_user_name)
    except ClientError:
        logger.exception("Couldn't update name for user %s.", user_name)
        raise
    return user
```

- Para obter detalhes da API, consulte a UpdateUserReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Updates an IAM user's name
  #
  # @param current_name [String] The current name of the user
  # @param new_name [String] The new name of the user
  def update_user_name(current_name, new_name)
    @iam_client.update_user(user_name: current_name, new_user_name: new_name)
    true
  rescue StandardError => e
    @logger.error("Error updating user name from '#{current_name}' to
'#{new_name}': #{e.message}")
    false
  end
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for Ruby da API.

Atualizar uma chave de acesso do IAM usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves de acesso

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  Aws::IAM::Model::StatusType status,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::UpdateAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);
```

```
    request.SetStatus(status);

    auto outcome = iam.UpdateAccessKey(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated status of access key "
                  << accessKeyID << " for user " << userName << std::endl;
    }
    else {
        std::cerr << "Error updated status of access key " << accessKeyID <<
                  " for user " << userName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como ativar ou desativar uma chave de acesso para um usuário do IAM

O comando `update-access-key`, apresentado a seguir, desativa a chave de acesso especificada (ID da chave de acesso e chave de acesso secreta) para o usuário do IAM denominado Bob.

```
aws iam update-access-key \
    --access-key-id AKIAIOSFODNN7EXAMPLE \
    --status Inactive \
    --user-name Bob
```

Este comando não produz saída.

A desativação da chave significa que ela não pode ser usada para acesso programático à AWS. No entanto, a chave continua disponível e pode ser ativada novamente.

Para obter mais informações, consulte Gerenciamento de chaves de acesso de usuários do IAM no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte UpdateAccessKeyem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.StatusType;
import software.amazon.awssdk.services.iam.model.UpdateAccessKeyRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateAccessKey {

    private static StatusType statusType;

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <username> <accessId> <status>\s

                Where:
                    username - The name of the user whose key you want to update.
\s
```

```
                    accessId - The access key ID of the secret access key you
want to update.\s
                    status - The status you want to assign to the secret access
key.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String username = args[0];
        String accessId = args[1];
        String status = args[2];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        updateKey(iam, username, accessId, status);
        System.out.println("Done");
        iam.close();
    }

    public static void updateKey(IamClient iam, String username, String accessId,
String status) {
        try {
            if (status.toLowerCase().equalsIgnoreCase("active")) {
                statusType = StatusType.ACTIVE;
            } else if (status.toLowerCase().equalsIgnoreCase("inactive")) {
                statusType = StatusType.INACTIVE;
            } else {
                statusType = StatusType.UNKNOWN_TO_SDK_VERSION;
            }

            UpdateAccessKeyRequest request = UpdateAccessKeyRequest.builder()
                    .accessKeyId(accessId)
                    .userName(username)
                    .status(statusType)
                    .build();

            iam.updateAccessKey(request);
            System.out.printf("Successfully updated the status of access key %s
to" +
```

```
                    "status %s for user %s", accessId, status, username);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize a chave de acesso.

```
import {
  UpdateAccessKeyCommand,
  IAMClient,
  StatusType,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
export const updateAccessKey = (userName, accessKeyId) => {
  const command = new UpdateAccessKeyCommand({
    AccessKeyId: accessKeyId,
    Status: StatusType.Inactive,
```

```
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  Status: "Active",
  UserName: "USER_NAME",
};

iam.updateAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_key(user_name, key_id, activate):
    """
    Updates the status of a key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to update.
    :param activate: When True, the key is activated. Otherwise, the key is
 deactivated.
    """

    try:
        key = iam.User(user_name).AccessKey(key_id)
        if activate:
            key.activate()
        else:
            key.deactivate()
        logger.info("%s key %s.", "Activated" if activate else "Deactivated",
 key_id)
    except ClientError:
        logger.exception(
            "Couldn't %s key %s.", "Activate" if activate else "Deactivate",
 key_id
        )
        raise
```

- Para obter detalhes da API, consulte a UpdateAccessKeyReferência da API AWSSDK for Python (Boto3).

Fazer upload de um certificado de servidor do IAM usando um AWS SDK

Os exemplos de código apresentados a seguir demonstram como fazer upload de um certificado de servidor do AWS Identity and Access Management (IAM).

CLI

AWS CLI

Como fazer upload de um certificado de servidor para sua conta da AWS

O upload-server-certificatecomando a seguir carrega um certificado de servidor em sua AWS conta. Neste exemplo, o certificado está no arquivo `public_key_cert_file.pem`, a chave privada associada está no arquivo `my_private_key.pem` e a cadeia de certificados fornecida pela autoridade de certificação (CA) está no arquivo `my_certificate_chain_file.pem`. Quando o upload do arquivo for concluído, ele estará disponível com o nome myServerCertificate. Os parâmetros que começam com `file://` informam ao comando para ler o conteúdo do arquivo e usá-lo como valor do parâmetro em vez do próprio nome do arquivo.

```
aws iam upload-server-certificate \
    --server-certificate-name myServerCertificate \
    --certificate-body file://public_key_cert_file.pem \
    --private-key file://my_private_key.pem \
    --certificate-chain file://my_certificate_chain_file.pem
```

Saída:

```
{
    "ServerCertificateMetadata": {
        "Path": "/",
        "ServerCertificateName": "myServerCertificate",
        "ServerCertificateId": "ASCAEXAMPLE123EXAMPLE",
        "Arn": "arn:aws:iam::1234567989012:server-certificate/
myServerCertificate",
```

```
        "UploadDate": "2019-04-22T21:13:44+00:00",
        "Expiration": "2019-10-15T22:23:16+00:00"
    }
}
```

Para obter mais informações, consulte Creating, Uploading, and Deleting Server Certificates no guia Using IAM.

- Para obter detalhes da API, consulte UploadServerCertificateem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UploadServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";
import { readFileSync } from "fs";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import * as path from "path";

const client = new IAMClient({});

const certMessage = `Generate a certificate and key with the following command,
 or the equivalent for your system.

openssl req -x509 -newkey rsa:4096 -sha256 -days 3650 -nodes \
-keyout example.key -out example.crt -subj "/CN=example.com" \
-addext "subjectAltName=DNS:example.com,DNS:www.example.net,IP:10.0.0.1"
`;

const getCertAndKey = () => {
  try {
    const cert = readFileSync(
      path.join(dirnameFromMetaUrl(import.meta.url), "./example.crt")
    );
```

```
    const key = readFileSync(
      path.join(dirnameFromMetaUrl(import.meta.url), "./example.key")
    );
    return { cert, key };
  } catch (err) {
    if (err.code === "ENOENT") {
      throw new Error(
        `Certificate and/or private key not found. ${certMessage}`
      );
    }

    throw err;
  }
};

/**
 *
 * @param {string} certificateName
 */
export const uploadServerCertificate = (certificateName) => {
  const { cert, key } = getCertAndKey();
  const command = new UploadServerCertificateCommand({
    ServerCertificateName: certificateName,
    CertificateBody: cert.toString(),
    PrivateKey: key.toString(),
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte UploadServerCertificatea Referência AWS SDK for JavaScript da API.

Cenários para o IAM usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Identity and Access Management (IAM) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar e gerenciar um serviço resiliente usando um AWS SDK
- Criar um grupo do IAM e adicionar um usuário ao grupo usando um AWS SDK
- Criar um usuário do IAM e assumir uma função com o AWS STS usando um AWS SDK
- Criar usuários do IAM somente leitura e leitura/gravação usando um AWS SDK
- Gerenciar chaves de acesso do IAM usando um AWS SDK
- Gerenciar políticas do IAM usando um AWS SDK
- Gerenciar perfis do IAM usando um AWS SDK
- Gerenciar a conta do IAM usando um AWS SDK
- Reverter uma versão de política do IAM usando um AWS SDK
- Trabalhar com a API IAM Policy Builder usando um AWS SDK

Criar e gerenciar um serviço resiliente usando um AWS SDK

Os exemplos de código a seguir mostram como criar um serviço da Web com carga balanceada que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
    static async Task Main(string[] args)
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
```

```
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
```

```
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper =
host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several
AWS resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server.");
```

```
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs
'server_startup_script.sh' when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the
`server.py` script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and
Systems Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
```

```
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3,
_autoScalerWrapper.GroupName, zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or
continue with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the
demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
_autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
```

```
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGro
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.Lo
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port,
 ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for
 your default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management
 Console.\n");
```

```
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
inbound traffic from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port,
ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
ipString);
                }
            }
            loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite
of these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as\n" +
```

```
                            "healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service
fails, the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
"static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
_smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
```

```
            $"Replacing the profile for instance {badInstanceId} with a profile
that contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo,
a deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not
for Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the
Auto Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load
balancer can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two
for the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");
```

```
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by
an auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler
start a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a
successful recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the
load balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance
typically takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
checks mean all instances report as unhealthy.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
"this-is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
```

```
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBal
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGr
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupNa
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you
might incur unexpected charges."
            );
        }
```

```
        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
```

```
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with
 a specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
 granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to
 the role.</param>
    /// <returns>The Arn of the profile.</returns>
```

```
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
                                         "\"Effect\": \"Allow\"," +
                                         "\"Principal\": {" +
                                         "\"Service\": [" +
                                             "\"ec2.amazonaws.com\"" +
                                         "]" +
                                         "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                                    "}]" +
                                "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
```

```
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }
```

```
        string profileArn = "";
        try
        {
            var profileCreateResponse = await
 _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
```

```
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling.
    /// The launch template specifies a Bash script in its user data field that
runs after
    /// the instance is started. This script installs the Python packages and
starts a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to
create and attach to the profile.</param>
    /// <returns>The template object.</returns>
```

```
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName,
_instanceRoleName, _instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new

LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2
Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
```

```
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new
 Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with
 size {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
 exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
```

```
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
 List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }
```

```
    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the
role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
```

```
            var attachedPolicies = await
_amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
```

```
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await
_amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile
is replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate
with the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association
for the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
```

```
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
```

```
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await
_amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for
{instanceId}. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
```

```
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string
groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
```

```
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the
calling computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP
address while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
```

```
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be
open to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0),
or to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
```

```
    /// Add an ingress rule to the specified security group that allows access on
 the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName,
 string targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
```

```
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
```

```
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
```

```
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened
 times and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</
param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer
 exists.</param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
```

```
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
        var loadBalancerReady = false;
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
```

```
                    await
_amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
```

```
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
```

```
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await
_amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn =
targetArn });
                Console.WriteLine($"Deleted load balancing target group
{groupName}.");
```

```
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books,
 movies, and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
```

```
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
```

```
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
```

```
    {
        var recommendationsText = await
 File.ReadAllTextAsync(recommendationsPath);
        var records =

 JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
```

```
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement
 _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-
architecture-table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";

    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
```

```
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers

- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
```

```
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-
prof-bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws IOException,
 InterruptedException {
        Scanner in = new Scanner(System.in);
        Database database = new Database();
        AutoScaler autoScaler = new AutoScaler();
        LoadBalancer loadBalancer = new LoadBalancer();

        System.out.println(DASHES);
        System.out.println("Welcome to the demonstration of How to Build and
 Manage a Resilient Service!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("A - SETUP THE RESOURCES");
        System.out.println("Press Enter when you're ready to start deploying
 resources.");
        in.nextLine();
        deploy(loadBalancer);
        System.out.println(DASHES);
        System.out.println(DASHES);
        System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
        System.out.println("Press Enter when you're ready.");
        in.nextLine();
        demo(loadBalancer);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("C - DELETE THE RESOURCES");
        System.out.println("""
```

```
                This concludes the demo of how to build and manage a resilient
service.
                To keep things tidy and to avoid unwanted charges on your
account, we can clean up all AWS resources
                that were created for this demo.
                """);

        System.out.println("\n Do you want to delete the resources (y/n)? ");
        String userInput = in.nextLine().trim().toLowerCase(); // Capture user
input

        if (userInput.equals("y")) {
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }
```

```
   private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
       Scanner in = new Scanner(System.in);
       System.out.println(
               """
                       For this demo, we'll use the AWS SDK for Java (v2) to
create several AWS resources
                       to set up a load-balanced web service endpoint and
explore some ways to make it resilient
                       against various kinds of failures.

                       Some of the resources create by this demo are:
                       \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                       \t* An EC2 launch template that defines EC2 instances
that each contain a Python web server.
                       \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                       \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                       """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to
'/' and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
```

```
                run a web server, such as Apache, with least-privileged
credentials.

                The template also defines an IAM policy that each instance uses
to assume a role that grants
                permissions to access the DynamoDB recommendation table and
Systems Manager parameters
                that control the flow of the demo.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the
demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("""
                Creating an Elastic Load Balancing target group and load
balancer. The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets,
targetGroupArn, lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul =
loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(),
StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
```

```
                            For this example to work, the default security group
for your default VPC must
                            allow access from this computer. You can either add
it automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security
group are configured correctly and that");
            System.out.println("you can successfully make a GET request to the
load balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }
```

```
   // A method that controls the demo part of the Java program.
   public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
       ParameterHelper paramHelper = new ParameterHelper();
       System.out.println("Read the ssm_only_policy.json file");
       String ssmOnlyPolicy = readFileAsString(ssmJSON);

       System.out.println("Resetting parameters to starting values for demo.");
       paramHelper.reset();

       System.out.println(
               """
                       This part of the demonstration shows how to toggle
different parts of the system
                       to create situations where the web service fails, and
shows how using a resilient
                       architecture can keep the web service running in spite
of these failures.

                       At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                      """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                       The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                       The table name is contained in a Systems Manager
parameter named self.param_helper.table.
                       To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.
                      """);
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       System.out.println(
               """
                       \nNow, sending a GET request to the load balancer
endpoint returns a failure code. But, the service reports as
                       healthy to the load balancer because shallow health
checks don't check for failure of the recommendation service.
                      """);
       demoChoices(loadBalancer);
```

```
        System.out.println(
                """
                        Instead of failing when the recommendation service fails,
the web service can return a static response.
                        While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                        """);
        paramHelper.put(paramHelper.failureResponse, "static");

        System.out.println("""
                Now, sending a GET request to the load balancer endpoint returns
a static response.
                The service still reports as healthy because health checks are
still shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance
id value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId =
autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " +
profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
```

```
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on
for recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto
Scaling instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the
load balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);
```

```
        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an
auto scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start
a new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load
balancing rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance
is running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);
```

```
        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode =
response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
```

```
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load
balancer targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
target.target().id(),
                                    target.target().port(),
target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the
health check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value
between 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
```

```
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
```

```
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance
is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile
is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure
'newInstanceProfileName' is a valid IAM Instance Profile
                                                // name.
                .build();
```

```
        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();

        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with
profile %s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
```

```
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress)
{
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
```

```
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);

            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request =
DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }
```

```
            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network,
you
     * must instead specify a prefix list ID. You can also temporarily open the
port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
```

```
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();

            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse =
getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup :
securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " +
secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " +
ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
```

```
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to
be open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);
```

```
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.

software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();

        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
```

```
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability
Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
```

```
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response =
getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
```

```
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
 InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to
 the policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM
 role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
```

```
                DeletePolicyRequest deletePolicyRequest =
DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance
profile " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
```

```
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String
 targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
 DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
 getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
 DescribeTargetHealthRequest.builder()

 .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
 getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
```

```
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()

.loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
```

```
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load
balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws
IOException, InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how
instance
     * health is checked.
```

```
    */
   public String createTargetGroup(String protocol, int port, String vpcId,
String targetGroupName) {
       CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
               .healthCheckPath("/healthcheck")
               .healthCheckTimeoutSeconds(5)
               .port(port)
               .vpcId(vpcId)
               .name(targetGroupName)
               .protocol(protocol)
               .build();

       CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
       String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
       String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
       System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
       return targetGroupArn;
   }

   /*
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String
targetGroupARN, String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();
```

```
            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to
become available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest =
CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                    + targetGroupARN);
```

```
            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
```

```
            System.err.println("Error checking table existence: " +
e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended,
such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException
{
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
```

```
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");

            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws
IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable =
enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
```

```
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-
response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
```

```
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances

- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
```

```
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
```

```
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
```

```
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
```

```
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item']
[] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
```

```
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
```

```
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
```

```
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
```

```
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
```

```
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
```

```
    }),
    new ScenarioOutput("gotVpc", (state) =>
      MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
    ),
    new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
    new ScenarioAction("getSubnets", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
      const client = new EC2Client({});
      const { Subnets } = await client.send(
        new DescribeSubnetsCommand({
          Filters: [
            { Name: "vpc-id", Values: [state.defaultVpc] },
            { Name: "availability-zone", Values: state.availabilityZoneNames },
            { Name: "default-for-az", Values: ["true"] },
          ],
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
      state.subnets = Subnets.map((subnet) => subnet.SubnetId);
    }),
    new ScenarioOutput(
      "gotSubnets",
      /**
       * @param {{ subnets: string[] }} state
       */
      (state) =>
        MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
    ),
    new ScenarioOutput(
      "creatingLoadBalancerTargetGroup",
      MESSAGES.creatingLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      ),
    ),
    new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
      const client = new ElasticLoadBalancingV2Client({});
      const { TargetGroups } = await client.send(
        new CreateTargetGroupCommand({
          Name: NAMES.loadBalancerTargetGroupName,
          Protocol: "HTTP",
          Port: 80,
          HealthCheckPath: "/healthcheck",
```

```
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
```

```
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
```

```
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup}} state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
```

```
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
```

```
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
```

```
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
```

```
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
```

```
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
```

```
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
```

```
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-
scaling').Instance }} state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
```

```
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation}} state
     */
    (state) =>
```

```
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
```

```
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
```

```
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
```

```
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";
```

```
/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
```

```
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
```

```
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
```

```
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
```

```
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
```

```
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
```

```
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
```

```
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
```

```
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
```

```
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
```

```
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
```

```
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
```

```
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones

- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22
```

```
    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways
to make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide
book, movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each
contain a Python web server."
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across
several Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the
Auto Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
'{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when
an instance starts.\n"
```

```
            f"This script starts a Python web server defined in the `server.py`
script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged
credentials.\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
            f"Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or
continue with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load
balancer provides a\n"
```

```
            "single endpoint where clients connect and dispatches requests to
 instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port
 is open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for
 your default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.
\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
```

```
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging
 from your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
                "Couldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                "manually verifying that your VPC and security group are
 configured correctly and that\n"
                "you can successfully make a GET request to the load balancer
 endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
 following choices:\n"
```

```
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health
check to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts
of the system\n"
```

```
            "to create situations where the web service fails, and shows how
using a resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations
by querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't
check for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with
a somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns
a static response.\n"
            f"The service still reports as healthy because health checks are
still shallow.\n"
        )
        self.demo_choices()
```

```
        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in
the target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a
profile that contains\n"
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns
either a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto
Scaling instance health.\n"
```

```
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect
when one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint
always returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
            "\nBecause the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
starting, sending a GET\n"
            "request to the web service continues to get a successful
recommendation response because\n"
            "the load balancer routes requests to the healthy instances. After
the replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
running and healthy.\n"
        )
        self.demo_choices()
```

```
        print(
            "\nIf the recommendation service fails now, deep health checks mean
all instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient
service.\n"
            "To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources\n"
            "that were created for this demo."
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ",
q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you
might incur unexpected charges."
            )
```

```
def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM
 policies and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer,
 param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
```

```
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are
 created by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI
 that is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
```

```
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are
created by this class.
        """
        as_client = boto3.client("autoscaling")
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
```

```
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is
assumed by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as
AmazonSSMManagedInstanceCore to grant
                                     use of Systems Manager to send commands to
the instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to
role\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response =
self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
```

```
        Replaces the profile associated with a running instance. After the
profile is
        replaced, the instance is rebooted to ensure that it uses the new
profile. When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to
associate with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be
ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
```

```
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.",
instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the
role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
```

```
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.

        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
```

```
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.",
self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto
Scaling. The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts
a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a
permissions policy
                                     to create and attach to the instance
profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
```

```
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template
{self.launch_template_name}: {err}."
                )
        return template


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
```

```
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template
{self.launch_template_name}: {err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones


    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
```

```
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
```

```
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group
{self.group_name}: {err}"
            )
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance
is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
```

```
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group
%s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
```

```
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] ==
 "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling
 group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")
```

```
    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress
from this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
```

```
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to
either this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
```

```
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port}
from {ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with
 the load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by
 this class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
```

```
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group
specifies how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened
times and
        lower thresholds. In production, you might want to decrease the
sensitivity of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
```

```
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to
do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )
```

```
    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener
to the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to
target group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
```

```
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
        success = False
        retries = 3
        while not success and retries > 0:
            try:
```

```
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint,
retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets:
{err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books,
 movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended,
 such as
        Book or Movie, and a range key named 'ItemId' that, combined with the
 MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
```

```
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5,
"WriteCapacityUnits": 5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name,
data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}:
{err}"
            )
```

```
    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.",
 self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters
 to drive
    the demonstration of resilient architecture, such as failure of a dependency
 or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
```

```
        """
        self.ssm_client = ssm_client
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when
a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups

- CreateAutoScalingGroup
- CreateInstanceProfile
- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Criar um grupo do IAM e adicionar um usuário ao grupo usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie um grupo e conceda permissões de acesso completo ao Amazon S3 a ele.
- Crie um novo usuário sem permissões para acessar o Amazon S3.

- Adicione o usuário ao grupo e mostre que agora ele tem permissões para o Amazon S3. Em seguida, limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using Amazon.IdentityManagement;
global using Amazon.S3;
global using Amazon.SecurityToken;
global using IAMActions;
global using IamScenariosCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;


namespace IAMActions;

public class IAMWrapper
{
    private readonly IAmazonIdentityManagementService _IAMService;

    /// <summary>
    /// Constructor for the IAMWrapper class.
    /// </summary>
    /// <param name="IAMService">An IAM client object.</param>
    public IAMWrapper(IAmazonIdentityManagementService IAMService)
    {
        _IAMService = IAMService;
    }

    /// <summary>
```

```
    /// Add an existing IAM user to an existing IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string
 groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
 AddUserToGroupRequest
        {
            GroupName = groupName,
            UserName = userName,
        });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _IAMService.AttachRolePolicyAsync(new
 AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
```

```
    /// key.</param>
    /// <returns>The AccessKey.</returns>
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
        var response = await _IAMService.CreateAccessKeyAsync(new
 CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;

    }


    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
 { GroupName = groupName });
        return response.Group;
    }


    /// <summary>
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</
param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
 policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new
 CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });
```

```
        return response.Policy;
    }


    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
    public async Task<string> CreateRoleAsync(string roleName, string
 rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }


    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName,
 string description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
```

```
    }


    /// <summary>
    /// Create an IAM user.
    /// </summary>
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
{ UserName = userName });
        return response.User;
    }


    /// <summary>
    /// Delete an IAM user's access key.
    /// </summary>
    /// <param name="accessKeyId">The Id for the IAM access key.</param>
    /// <param name="userName">The username of the user that owns the IAM
    /// access key.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
userName)
    {
        var response = await _IAMService.DeleteAccessKeyAsync(new
DeleteAccessKeyRequest
        {
            AccessKeyId = accessKeyId,
            UserName = userName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
```

```
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
{ GroupName = groupName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new
DeletePolicyRequest { PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role.
    /// </summary>
```

```
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
 { RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="policyName">The name of the IAM role policy to delete.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
 policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
 DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM user.
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
 { UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Detach an IAM policy from an IAM role.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM
policy.</param>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DetachRolePolicyAsync(string policyArn, string
roleName)
    {
        var response = await _IAMService.DetachRolePolicyAsync(new
DetachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
```

```
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
 GetAccountPasswordPolicyRequest());
        return response.PasswordPolicy;
    }


    /// <summary>
    /// Get information about an IAM policy.
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</
param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
 { PolicyArn = policyArn });
        return response.Policy;
    }


    /// <summary>
    /// Get information about an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });

        return response.Role;
    }


    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
```

```
    {
        var response = await _IAMService.GetUserAsync(new GetUserRequest
{ UserName = userName });
        return response.User;
    }


    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
    public async Task<List<AttachedPolicyType>>
ListAttachedRolePoliciesAsync(string roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
_IAMService.Paginators.ListAttachedRolePolicies(new
ListAttachedRolePoliciesRequest { RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }


    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }
```

```
        return groups;
    }


    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
 ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        return policies;
    }


    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</
param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
        var listRolePoliciesPaginator =
 _IAMService.Paginators.ListRolePolicies(new ListRolePoliciesRequest { RoleName =
 roleName });
        var policyNames = new List<string>();

        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }
```

```
    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();

        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }


    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }


    /// <summary>
    /// List IAM users.
    /// </summary>
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
```

```
            users.AddRange(response.Users);
        }

        return users;
    }


    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
    /// <param name="groupName">The name of the IAM group to remove the user
from.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
_IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM
policy.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string
policyName, string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
```

```
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Update the inline policy document embedded in a role.
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string
 roleName, string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM user.
    /// </summary>
    /// <param name="userName">The name of the IAM user.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM
 policy.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutUserPolicyAsync(string userName, string
 policyName, string policyDocument)
    {
        var request = new PutUserPolicyRequest
```

```
        {
            UserName = userName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutUserPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Wait for a new access key to be ready to use.
    /// </summary>
    /// <param name="accessKeyId">The Id of the access key.</param>
    /// <returns>A boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitUntilAccessKeyIsReady(string accessKeyId)
    {
        var keyReady = false;

        do
        {
            try
            {
                var response = await _IAMService.GetAccessKeyLastUsedAsync(
                    new GetAccessKeyLastUsedRequest { AccessKeyId =
 accessKeyId });
                if (response.UserName is not null)
                {
                    keyReady = true;
                }
            }
            catch (NoSuchEntityException)
            {
                keyReady = false;
            }
        } while (!keyReady);

        return keyReady;
    }
}


using Microsoft.Extensions.Configuration;
```

```
namespace IAMGroups;

public class IAMGroups
{
    private static ILogger logger = null!;

    // Represents JSON code for AWS full access policy for Amazon Simple
    // Storage Service (Amazon S3).
    private const string S3FullAccessPolicyDocument = "{" +
        " \"Statement\" : [{" +
            " \"Action\" : [\"s3:*\"]," +
            " \"Effect\" : \"Allow\"," +
            " \"Resource\" : \"*\"" +
        "}]" +
    "}";


    static async Task Main(string[] args)
    {
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<IAMWrapper>()
            .AddTransient<UIWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<IAMGroups>();

        IConfiguration configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();
```

```
        var groupUserName = configuration["GroupUserName"];
        var groupName = configuration["GroupName"];
        var groupPolicyName = configuration["GroupPolicyName"];
        var groupBucketName = configuration["GroupBucketName"];

        var wrapper = host.Services.GetRequiredService<IAMWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        uiWrapper.DisplayGroupsOverview();
        uiWrapper.PressEnter();

        // Create an IAM group.
        uiWrapper.DisplayTitle("Create IAM group");
        Console.WriteLine("Let's begin by creating a new IAM group.");
        var group = await wrapper.CreateGroupAsync(groupName);

        // Add an inline IAM policy to the group.
        uiWrapper.DisplayTitle("Add policy to group");
        Console.WriteLine("Add an inline policy to the group that allows members
 to have full access to");
        Console.WriteLine("Amazon Simple Storage Service (Amazon S3) buckets.");

        await wrapper.PutGroupPolicyAsync(group.GroupName, groupPolicyName,
 S3FullAccessPolicyDocument);

        uiWrapper.PressEnter();

        // Now create a new user.
        uiWrapper.DisplayTitle("Create an IAM user");
        Console.WriteLine("Now let's create a new IAM user.");
        var groupUser = await wrapper.CreateUserAsync(groupUserName);

        // Add the new user to the group.
        uiWrapper.DisplayTitle("Add the user to the group");
        Console.WriteLine("Adding the user to the group, which will give the user
 the same permissions as the group.");
        await wrapper.AddUserToGroupAsync(groupUser.UserName, group.GroupName);

        Console.WriteLine($"User, {groupUser.UserName}, has been added to the
 group, {group.GroupName}.");
        uiWrapper.PressEnter();

        Console.WriteLine("Now that we have created a user, and added the user to
 the group, let's create an IAM access key.");
```

```
        // Create access and secret keys for the user.
        var accessKey = await wrapper.CreateAccessKeyAsync(groupUserName);
        Console.WriteLine("Key created.");
        uiWrapper.WaitABit(15, "Waiting for the access key to be ready for
use.");

        uiWrapper.DisplayTitle("List buckets");
        Console.WriteLine("To prove that the user has access to Amazon S3, list
the S3 buckets for the account.");

        var s3Client = new AmazonS3Client(accessKey.AccessKeyId,
accessKey.SecretAccessKey);
        var stsClient = new
AmazonSecurityTokenServiceClient(accessKey.AccessKeyId,
accessKey.SecretAccessKey);

        var s3Wrapper = new S3Wrapper(s3Client, stsClient);

        var buckets = await s3Wrapper.ListMyBucketsAsync();

        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName}\tcreated on:
{bucket.CreationDate}");
            });
        }

        // Show that the user also has write access to Amazon S3 by creating
        // a new bucket.
        uiWrapper.DisplayTitle("Create a bucket");
        Console.WriteLine("Since group members have full access to Amazon S3,
let's create a bucket.");
        var success = await s3Wrapper.PutBucketAsync(groupBucketName);

        if (success)
        {
            Console.WriteLine($"Successfully created the bucket:
{groupBucketName}.");
        }

        uiWrapper.PressEnter();
```

```
        Console.WriteLine("Let's list the user's S3 buckets again to show the new
bucket.");

        buckets = await s3Wrapper.ListMyBucketsAsync();

        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName}\tcreated on:
{bucket.CreationDate}");
            });
        }

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("First delete the bucket we created.");
        await s3Wrapper.DeleteBucketAsync(groupBucketName);

        Console.WriteLine($"Now remove the user, {groupUserName}, from the group,
{groupName}.");
        await wrapper.RemoveUserFromGroupAsync(groupUserName, groupName);

        Console.WriteLine("Delete the user's access key.");
        await wrapper.DeleteAccessKeyAsync(accessKey.AccessKeyId, groupUserName);

        // Now we can safely delete the user.
        Console.WriteLine("Now we can delete the user.");
        await wrapper.DeleteUserAsync(groupUserName);

        uiWrapper.PressEnter();

        Console.WriteLine("Now we will delete the IAM policy attached to the
group.");
        await wrapper.DeleteGroupPolicyAsync(groupName, groupPolicyName);

        Console.WriteLine("Now we delete the IAM group.");
        await wrapper.DeleteGroupAsync(groupName);

        uiWrapper.PressEnter();

        Console.WriteLine("The IAM groups demo has completed.");
```

```
        uiWrapper.PressEnter();
    }
}


namespace IamScenariosCommon;

using System.Net;

/// <summary>
/// A class to perform Amazon Simple Storage Service (Amazon S3) actions for
/// the IAM Basics scenario.
/// </summary>
public class S3Wrapper
{
    private IAmazonS3 _s3Service;
    private IAmazonSecurityTokenService _stsService;

    /// <summary>
    /// Constructor for the S3Wrapper class.
    /// </summary>
    /// <param name="s3Service">An Amazon S3 client object.</param>
    /// <param name="stsService">An AWS Security Token Service (AWS STS)
    /// client object.</param>
    public S3Wrapper(IAmazonS3 s3Service, IAmazonSecurityTokenService stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }

    /// <summary>
    /// Assumes an AWS Identity and Access Management (IAM) role that allows
    /// Amazon S3 access for the current session.
    /// </summary>
    /// <param name="roleSession">A string representing the current session.</
param>
    /// <param name="roleToAssume">The name of the IAM role to assume.</param>
    /// <returns>Credentials for the newly assumed IAM role.</returns>
    public async Task<Credentials> AssumeS3RoleAsync(string roleSession, string
 roleToAssume)
    {
        // Create the request to use with the AssumeRoleAsync call.
        var request = new AssumeRoleRequest()
```

```
        {
            RoleSessionName = roleSession,
            RoleArn = roleToAssume,
        };

        var response = await _stsService.AssumeRoleAsync(request);

        return response.Credentials;
    }


    /// <summary>
    /// Delete an S3 bucket.
    /// </summary>
    /// <param name="bucketName">Name of the S3 bucket to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteBucketAsync(string bucketName)
    {
        var result = await _s3Service.DeleteBucketAsync(new DeleteBucketRequest
 { BucketName = bucketName });
        return result.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// List the buckets that are owned by the user's account.
    /// </summary>
    /// <returns>Async Task.</returns>
    public async Task<List<S3Bucket>?> ListMyBucketsAsync()
    {
        try
        {
            // Get the list of buckets accessible by the new user.
            var response = await _s3Service.ListBucketsAsync();

            return response.Buckets;
        }
        catch (AmazonS3Exception ex)
        {
            // Something else went wrong. Display the error message.
            Console.WriteLine($"Error: {ex.Message}");
            return null;
        }
    }
```

```
    /// <summary>
    /// Create a new S3 bucket.
    /// </summary>
    /// <param name="bucketName">The name for the new bucket.</param>
    /// <returns>A Boolean value indicating whether the action completed
    /// successfully.</returns>
    public async Task<bool> PutBucketAsync(string bucketName)
    {
        var response = await _s3Service.PutBucketAsync(new PutBucketRequest
 { BucketName = bucketName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Update the client objects with new client objects. This is available
    /// because the scenario uses the methods of this class without and then
    /// with the proper permissions to list S3 buckets.
    /// </summary>
    /// <param name="s3Service">The Amazon S3 client object.</param>
    /// <param name="stsService">The AWS STS client object.</param>
    public void UpdateClients(IAmazonS3 s3Service, IAmazonSecurityTokenService
 stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }
}


namespace IamScenariosCommon;

public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the IAM Groups scenario.
    /// </summary>
    public void DisplayGroupsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to the IAM Groups Demo");
        Console.WriteLine("This example application does the following:");
```

```
        Console.WriteLine("\t1. Creates an Amazon Identity and Access Management
(IAM) group.");
        Console.WriteLine("\t2. Adds an IAM policy to the IAM group giving it
full access to Amazon S3.");
        Console.WriteLine("\t3. Creates a new IAM user.");
        Console.WriteLine("\t4. Creates an IAM access key for the user.");
        Console.WriteLine("\t5. Adds the user to the IAM group.");
        Console.WriteLine("\t6. Lists the buckets on the account.");
        Console.WriteLine("\t7. Proves that the user has full Amazon S3 access by
creating a bucket.");
        Console.WriteLine("\t8. List the buckets again to show the new bucket.");
        Console.WriteLine("\t9. Cleans up all the resources created.");
    }

    /// <summary>
    /// Show information about the IAM Basics scenario.
    /// </summary>
    public void DisplayBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to IAM Basics");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates a user with no permissions.");
        Console.WriteLine("\t2. Creates a role and policy that grant
s3:ListAllMyBuckets permission.");
        Console.WriteLine("\t3. Grants the user permission to assume the role.");
        Console.WriteLine("\t4. Creates an S3 client object as the user and tries
to list buckets (this will fail).");
        Console.WriteLine("\t5. Gets temporary credentials by assuming the
role.");
        Console.WriteLine("\t6. Creates a new S3 client object with the temporary
credentials and lists the buckets (this will succeed).");
        Console.WriteLine("\t7. Deletes all the resources.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
```

```
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AddUserToGroup
  - AttachRolePolicy
  - CreateAccessKey
  - CreateGroup
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeleteGroup
  - DeleteGroupPolicy
  - DeleteUser
  - PutGroupPolicy
  - RemoveUserFromGroup

Criar um usuário do IAM e assumir uma função com o AWS STS usando um AWS SDK

Os exemplos de código a seguir mostram como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.

- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using Amazon.IdentityManagement;
global using Amazon.S3;
global using Amazon.SecurityToken;
global using IAMActions;
global using IamScenariosCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;


namespace IAMActions;

public class IAMWrapper
{
    private readonly IAmazonIdentityManagementService _IAMService;

    /// <summary>
    /// Constructor for the IAMWrapper class.
    /// </summary>
    /// <param name="IAMService">An IAM client object.</param>
    public IAMWrapper(IAmazonIdentityManagementService IAMService)
    {
        _IAMService = IAMService;
    }

    /// <summary>
    /// Add an existing IAM user to an existing IAM group.
    /// </summary>
```

```
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string
 groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
 AddUserToGroupRequest
        {
            GroupName = groupName,
            UserName = userName,
        });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _IAMService.AttachRolePolicyAsync(new
 AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
    /// key.</param>
    /// <returns>The AccessKey.</returns>
```

```
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
        var response = await _IAMService.CreateAccessKeyAsync(new
 CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;

    }


    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
 { GroupName = groupName });
        return response.Group;
    }


    /// <summary>
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</
param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
 policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new
 CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });

        return response.Policy;
```

```
    }


    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
    public async Task<string> CreateRoleAsync(string roleName, string
 rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }


    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName,
 string description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
    }
```

```
    /// <summary>
    /// Create an IAM user.
    /// </summary>
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
{ UserName = userName });
        return response.User;
    }


    /// <summary>
    /// Delete an IAM user's access key.
    /// </summary>
    /// <param name="accessKeyId">The Id for the IAM access key.</param>
    /// <param name="userName">The username of the user that owns the IAM
    /// access key.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
userName)
    {
        var response = await _IAMService.DeleteAccessKeyAsync(new
DeleteAccessKeyRequest
        {
            AccessKeyId = accessKeyId,
            UserName = userName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
{ GroupName = groupName });
```

```
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new
DeletePolicyRequest { PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
```

```
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
 { RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="policyName">The name of the IAM role policy to delete.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
 policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
 DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM user.
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
 { UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
```

```
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Detach an IAM policy from an IAM role.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM
policy.</param>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DetachRolePolicyAsync(string policyArn, string
roleName)
    {
        var response = await _IAMService.DetachRolePolicyAsync(new
DetachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
GetAccountPasswordPolicyRequest());
```

```
        return response.PasswordPolicy;
    }


    /// <summary>
    /// Get information about an IAM policy.
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</
param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
 { PolicyArn = policyArn });
        return response.Policy;
    }


    /// <summary>
    /// Get information about an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });

        return response.Role;
    }


    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
    {
```

```
        var response = await _IAMService.GetUserAsync(new GetUserRequest
{ UserName = userName });
        return response.User;
    }


    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
    public async Task<List<AttachedPolicyType>>
ListAttachedRolePoliciesAsync(string roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
_IAMService.Paginators.ListAttachedRolePolicies(new
ListAttachedRolePoliciesRequest { RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }


    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }

        return groups;
```

```
    }


    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
 ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        return policies;
    }


    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</
param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
        var listRolePoliciesPaginator =
 _IAMService.Paginators.ListRolePolicies(new ListRolePoliciesRequest { RoleName =
 roleName });
        var policyNames = new List<string>();

        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }
```

```
    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();

        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }


    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }


    /// <summary>
    /// List IAM users.
    /// </summary>
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
            users.AddRange(response.Users);
```

```
        }

        return users;
    }


    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
    /// <param name="groupName">The name of the IAM group to remove the user
from.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
_IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM
policy.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string
policyName, string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
            PolicyName = policyName,
```

```
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Update the inline policy document embedded in a role.
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string
 roleName, string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM user.
    /// </summary>
    /// <param name="userName">The name of the IAM user.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM
 policy.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutUserPolicyAsync(string userName, string
 policyName, string policyDocument)
    {
        var request = new PutUserPolicyRequest
        {
```

```
            UserName = userName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutUserPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Wait for a new access key to be ready to use.
    /// </summary>
    /// <param name="accessKeyId">The Id of the access key.</param>
    /// <returns>A boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitUntilAccessKeyIsReady(string accessKeyId)
    {
        var keyReady = false;

        do
        {
            try
            {
                var response = await _IAMService.GetAccessKeyLastUsedAsync(
                    new GetAccessKeyLastUsedRequest { AccessKeyId =
 accessKeyId });
                if (response.UserName is not null)
                {
                    keyReady = true;
                }
            }
            catch (NoSuchEntityException)
            {
                keyReady = false;
            }
        } while (!keyReady);

        return keyReady;
    }
}



using Microsoft.Extensions.Configuration;
```

```
namespace IAMBasics;

public class IAMBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<IAMWrapper>()
            .AddTransient<UIWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<IAMBasics>();


        IConfiguration configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        // Values needed for user, role, and policies.
        string userName = configuration["UserName"]!;
        string s3PolicyName = configuration["S3PolicyName"]!;
        string roleName = configuration["RoleName"]!;


        var iamWrapper = host.Services.GetRequiredService<IAMWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        uiWrapper.DisplayBasicsOverview();
```

```
        uiWrapper.PressEnter();

        // First create a user. By default, the new user has
        // no permissions.
        uiWrapper.DisplayTitle("Create User");
        Console.WriteLine($"Creating a new user with user name: {userName}.");
        var user = await iamWrapper.CreateUserAsync(userName);
        var userArn = user.Arn;

        Console.WriteLine($"Successfully created user: {userName} with ARN:
{userArn}.");
        uiWrapper.WaitABit(15, "Now let's wait for the user to be ready for
use.");

        // Define a role policy document that allows the new user
        // to assume the role.
        string assumeRolePolicyDocument = "{" +
          "\"Version\": \"2012-10-17\"," +
          "\"Statement\": [{" +
              "\"Effect\": \"Allow\"," +
              "\"Principal\": {" +
              $" \"AWS\": \"{userArn}\"" +
              "}," +
              "\"Action\": \"sts:AssumeRole\"" +
          "}]" +
        "}";

        // Permissions to list all buckets.
        string policyDocument = "{" +
            "\"Version\": \"2012-10-17\"," +
            " \"Statement\" : [{" +
                " \"Action\" : [\"s3:ListAllMyBuckets\"]," +
                " \"Effect\" : \"Allow\"," +
                " \"Resource\" : \"*\"" +
            "}]" +
        "}";

        // Create an AccessKey for the user.
        uiWrapper.DisplayTitle("Create access key");
        Console.WriteLine("Now let's create an access key for the new user.");
        var accessKey = await iamWrapper.CreateAccessKeyAsync(userName);

        var accessKeyId = accessKey.AccessKeyId;
        var secretAccessKey = accessKey.SecretAccessKey;
```

```
        Console.WriteLine($"We have created the access key with Access key id:
{accessKeyId}.");

        Console.WriteLine("Now let's wait until the IAM access key is ready to
use.");
        var keyReady = await iamWrapper.WaitUntilAccessKeyIsReady(accessKeyId);

        // Now try listing the Amazon Simple Storage Service (Amazon S3)
        // buckets. This should fail at this point because the user doesn't
        // have permissions to perform this task.
        uiWrapper.DisplayTitle("Try to display Amazon S3 buckets");
        Console.WriteLine("Now let's try to display a list of the user's Amazon
S3 buckets.");
        var s3Client1 = new AmazonS3Client(accessKeyId, secretAccessKey);
        var stsClient1 = new AmazonSecurityTokenServiceClient(accessKeyId,
secretAccessKey);

        var s3Wrapper = new S3Wrapper(s3Client1, stsClient1);
        var buckets = await s3Wrapper.ListMyBucketsAsync();

        Console.WriteLine(buckets is null
            ? "As expected, the call to list the buckets has returned a null
list."
            : "Something went wrong. This shouldn't have worked.");

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Create IAM role");
        Console.WriteLine($"Creating the role: {roleName}");

        // Creating an IAM role to allow listing the S3 buckets. A role name
        // is not case sensitive and must be unique to the account for which it
        // is created.
        var roleArn = await iamWrapper.CreateRoleAsync(roleName,
assumeRolePolicyDocument);

        uiWrapper.PressEnter();

        // Create a policy with permissions to list S3 buckets.
        uiWrapper.DisplayTitle("Create IAM policy");
        Console.WriteLine($"Creating the policy: {s3PolicyName}");
        Console.WriteLine("with permissions to list the Amazon S3 buckets for the
account.");
```

```
        var policy = await iamWrapper.CreatePolicyAsync(s3PolicyName,
policyDocument);

        // Wait 15 seconds for the IAM policy to be available.
        uiWrapper.WaitABit(15, "Waiting for the policy to be available.");

        // Attach the policy to the role you created earlier.
        uiWrapper.DisplayTitle("Attach new IAM policy");
        Console.WriteLine("Now let's attach the policy to the role.");
        await iamWrapper.AttachRolePolicyAsync(policy.Arn, roleName);

        // Wait 15 seconds for the role to be updated.
        Console.WriteLine();
        uiWrapper.WaitABit(15, "Waiting for the policy to be attached.");

        // Use the AWS Security Token Service (AWS STS) to have the user
        // assume the role we created.
        var stsClient2 = new AmazonSecurityTokenServiceClient(accessKeyId,
secretAccessKey);

        // Wait for the new credentials to become valid.
        uiWrapper.WaitABit(10, "Waiting for the credentials to be valid.");

        var assumedRoleCredentials = await
s3Wrapper.AssumeS3RoleAsync("temporary-session", roleArn);

        // Try again to list the buckets using the client created with
        // the new user's credentials. This time, it should work.
        var s3Client2 = new AmazonS3Client(assumedRoleCredentials);

        s3Wrapper.UpdateClients(s3Client2, stsClient2);

        buckets = await s3Wrapper.ListMyBucketsAsync();

        uiWrapper.DisplayTitle("List Amazon S3 buckets");
        Console.WriteLine("This time we should have buckets to list.");
        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName} created:
{bucket.CreationDate}");
            });
        }
```

```
        uiWrapper.PressEnter();

        // Now clean up all the resources used in the example.
        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("Thank you for watching. The IAM Basics demo is
 complete.");
        Console.WriteLine("Please wait while we clean up the resources we
 created.");

        await iamWrapper.DetachRolePolicyAsync(policy.Arn, roleName);

        await iamWrapper.DeletePolicyAsync(policy.Arn);

        await iamWrapper.DeleteRoleAsync(roleName);

        await iamWrapper.DeleteAccessKeyAsync(accessKeyId, userName);

        await iamWrapper.DeleteUserAsync(userName);

        uiWrapper.PressEnter();

        Console.WriteLine("All done cleaning up our resources. Thank you for your
 patience.");
    }
}


namespace IamScenariosCommon;

using System.Net;

/// <summary>
/// A class to perform Amazon Simple Storage Service (Amazon S3) actions for
/// the IAM Basics scenario.
/// </summary>
public class S3Wrapper
{
    private IAmazonS3 _s3Service;
    private IAmazonSecurityTokenService _stsService;

    /// <summary>
    /// Constructor for the S3Wrapper class.
    /// </summary>
```

```
    /// <param name="s3Service">An Amazon S3 client object.</param>
    /// <param name="stsService">An AWS Security Token Service (AWS STS)
    /// client object.</param>
    public S3Wrapper(IAmazonS3 s3Service, IAmazonSecurityTokenService stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }

    /// <summary>
    /// Assumes an AWS Identity and Access Management (IAM) role that allows
    /// Amazon S3 access for the current session.
    /// </summary>
    /// <param name="roleSession">A string representing the current session.</
param>
    /// <param name="roleToAssume">The name of the IAM role to assume.</param>
    /// <returns>Credentials for the newly assumed IAM role.</returns>
    public async Task<Credentials> AssumeS3RoleAsync(string roleSession, string
 roleToAssume)
    {
        // Create the request to use with the AssumeRoleAsync call.
        var request = new AssumeRoleRequest()
        {
            RoleSessionName = roleSession,
            RoleArn = roleToAssume,
        };

        var response = await _stsService.AssumeRoleAsync(request);

        return response.Credentials;
    }


    /// <summary>
    /// Delete an S3 bucket.
    /// </summary>
    /// <param name="bucketName">Name of the S3 bucket to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteBucketAsync(string bucketName)
    {
        var result = await _s3Service.DeleteBucketAsync(new DeleteBucketRequest
 { BucketName = bucketName });
        return result.HttpStatusCode == HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// List the buckets that are owned by the user's account.
    /// </summary>
    /// <returns>Async Task.</returns>
    public async Task<List<S3Bucket>?> ListMyBucketsAsync()
    {
        try
        {
            // Get the list of buckets accessible by the new user.
            var response = await _s3Service.ListBucketsAsync();

            return response.Buckets;
        }
        catch (AmazonS3Exception ex)
        {
            // Something else went wrong. Display the error message.
            Console.WriteLine($"Error: {ex.Message}");
            return null;
        }
    }

    /// <summary>
    /// Create a new S3 bucket.
    /// </summary>
    /// <param name="bucketName">The name for the new bucket.</param>
    /// <returns>A Boolean value indicating whether the action completed
    /// successfully.</returns>
    public async Task<bool> PutBucketAsync(string bucketName)
    {
        var response = await _s3Service.PutBucketAsync(new PutBucketRequest
{ BucketName = bucketName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Update the client objects with new client objects. This is available
    /// because the scenario uses the methods of this class without and then
    /// with the proper permissions to list S3 buckets.
    /// </summary>
    /// <param name="s3Service">The Amazon S3 client object.</param>
    /// <param name="stsService">The AWS STS client object.</param>
    public void UpdateClients(IAmazonS3 s3Service, IAmazonSecurityTokenService
stsService)
```

```
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }
}


namespace IamScenariosCommon;

public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the IAM Groups scenario.
    /// </summary>
    public void DisplayGroupsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to the IAM Groups Demo");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates an Amazon Identity and Access Management
 (IAM) group.");
        Console.WriteLine("\t2. Adds an IAM policy to the IAM group giving it
 full access to Amazon S3.");
        Console.WriteLine("\t3. Creates a new IAM user.");
        Console.WriteLine("\t4. Creates an IAM access key for the user.");
        Console.WriteLine("\t5. Adds the user to the IAM group.");
        Console.WriteLine("\t6. Lists the buckets on the account.");
        Console.WriteLine("\t7. Proves that the user has full Amazon S3 access by
 creating a bucket.");
        Console.WriteLine("\t8. List the buckets again to show the new bucket.");
        Console.WriteLine("\t9. Cleans up all the resources created.");
    }

    /// <summary>
    /// Show information about the IAM Basics scenario.
    /// </summary>
    public void DisplayBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to IAM Basics");
```

```
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates a user with no permissions.");
        Console.WriteLine("\t2. Creates a role and policy that grant
s3:ListAllMyBuckets permission.");
        Console.WriteLine("\t3. Grants the user permission to assume the role.");
        Console.WriteLine("\t4. Creates an S3 client object as the user and tries
to list buckets (this will fail).");
        Console.WriteLine("\t5. Gets temporary credentials by assuming the
role.");
        Console.WriteLine("\t6. Creates a new S3 client object with the temporary
credentials and lists the buckets (this will succeed).");
        Console.WriteLine("\t7. Deletes all the resources.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
```

```
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy

- PutUserPolicy

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iam_create_user_assume_role
#
# Scenario to create an IAM user, create an IAM role, and apply the role to the
 user.
#
#     "IAM access" permissions are needed to run this code.
#     "STS assume role" permissions are needed to run this code. (Note: It might
 be necessary to
#           create a custom policy).
#
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
###############################################################################
function iam_create_user_assume_role() {
  {
    if [ "$IAM_OPERATIONS_SOURCED" != "True" ]; then

      source ./iam_operations.sh
    fi
  }

  echo_repeat "*" 88
  echo "Welcome to the IAM create user and assume role demo."
  echo
  echo "This demo will create an IAM user, create an IAM role, and apply the role
 to the user."
  echo_repeat "*" 88
```

```
  echo

  echo -n "Enter a name for a new IAM user: "
  get_input
  user_name=$get_input_result

  local user_arn
  user_arn=$(iam_create_user -u "$user_name")

  # shellcheck disable=SC2181
  if [[ ${?} == 0 ]]; then
    echo "Created demo IAM user named $user_name"
  else
    errecho "$user_arn"
    errecho "The user failed to create. This demo will exit."
    return 1
  fi

  local access_key_response
  access_key_response=$(iam_create_user_access_key -u "$user_name")
  # shellcheck disable=SC2181
  if [[ ${?} != 0 ]]; then
    errecho "The access key failed to create. This demo will exit."
    clean_up "$user_name"
    return 1
  fi

  IFS=$'\t ' read -r -a access_key_values <<<"$access_key_response"
  local key_name=${access_key_values[0]}
  local key_secret=${access_key_values[1]}

  echo "Created access key named $key_name"

  echo "Wait 10 seconds for the user to be ready."
  sleep 10
  echo_repeat "*" 88
  echo

  local iam_role_name
  iam_role_name=$(generate_random_name "test-role")
  echo "Creating a role named $iam_role_name with user $user_name as the
principal."

  local assume_role_policy_document="{
```

```
    \"Version\": \"2012-10-17\",
    \"Statement\": [{
        \"Effect\": \"Allow\",
        \"Principal\": {\"AWS\": \"$user_arn\"},
        \"Action\": \"sts:AssumeRole\"
        }]
    }"

  local role_arn
  role_arn=$(iam_create_role -n "$iam_role_name" -p
"$assume_role_policy_document")

  # shellcheck disable=SC2181
  if [ ${?} == 0 ]; then
    echo "Created IAM role named $iam_role_name"
  else
    errecho "The role failed to create. This demo will exit."
    clean_up "$user_name" "$key_name"
    return 1
  fi

  local policy_name
  policy_name=$(generate_random_name "test-policy")
  local policy_document="{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]}"

  local policy_arn
  policy_arn=$(iam_create_policy -n "$policy_name" -p "$policy_document")
  # shellcheck disable=SC2181
  if [[ ${?} == 0 ]]; then
    echo "Created  IAM policy named $policy_name"
  else
    errecho "The policy failed to create."
    clean_up "$user_name" "$key_name" "$iam_role_name"
    return 1
  fi

  if (iam_attach_role_policy -n "$iam_role_name" -p "$policy_arn"); then
    echo "Attached policy $policy_arn to role $iam_role_name"
  else
```

```
    errecho "The policy failed to attach."
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn"
    return 1
  fi

  local assume_role_policy_document="{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"$role_arn\"}]}"

  local assume_role_policy_name
  assume_role_policy_name=$(generate_random_name "test-assume-role-")

  # shellcheck disable=SC2181
  local assume_role_policy_arn
  assume_role_policy_arn=$(iam_create_policy -n "$assume_role_policy_name" -p
"$assume_role_policy_document")
  # shellcheck disable=SC2181
  if [ ${?} == 0 ]; then
    echo "Created  IAM policy named $assume_role_policy_name for sts assume role"
  else
    errecho "The policy failed to create."
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn"
"$policy_arn"
    return 1
  fi

  echo "Wait 10 seconds to give AWS time to propagate these new resources and
connections."
  sleep 10
  echo_repeat "*" 88
  echo

  echo "Try to list buckets without the new user assuming the role."
  echo_repeat "*" 88
  echo

  # Set the environment variables for the created user.
  # bashsupport disable=BP2001
  export AWS_ACCESS_KEY_ID=$key_name
  # bashsupport disable=BP2001
  export AWS_SECRET_ACCESS_KEY=$key_secret
```

```
 local buckets
 buckets=$(s3_list_buckets)

 # shellcheck disable=SC2181
 if [ ${?} == 0 ]; then
   local bucket_count
   bucket_count=$(echo "$buckets" | wc -w | xargs)
   echo "There are $bucket_count buckets in the account. This should not have
happened."
 else
   errecho "Because the role with permissions has not been assumed, listing
buckets failed."
 fi

 echo
 echo_repeat "*" 88
 echo "Now assume the role $iam_role_name and list the buckets."
 echo_repeat "*" 88
 echo

 local credentials

 credentials=$(sts_assume_role -r "$role_arn" -n "AssumeRoleDemoSession")
 # shellcheck disable=SC2181
 if [ ${?} == 0 ]; then
   echo "Assumed role $iam_role_name"
 else
   errecho "Failed to assume role."
   export AWS_ACCESS_KEY_ID=""
   export AWS_SECRET_ACCESS_KEY=""
   clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn"
"$policy_arn" "$assume_role_policy_arn"
   return 1
 fi

 IFS=$'\t ' read -r -a credentials <<<"$credentials"

 export AWS_ACCESS_KEY_ID=${credentials[0]}
 export AWS_SECRET_ACCESS_KEY=${credentials[1]}
 # bashsupport disable=BP2001
 export AWS_SESSION_TOKEN=${credentials[2]}

 buckets=$(s3_list_buckets)
```

```
  # shellcheck disable=SC2181
  if [ ${?} == 0 ]; then
    local bucket_count
    bucket_count=$(echo "$buckets" | wc -w | xargs)
    echo "There are $bucket_count buckets in the account. Listing buckets
 succeeded because of "
    echo "the assumed role."
  else
    errecho "Failed to list buckets. This should not happen."
    export AWS_ACCESS_KEY_ID=""
    export AWS_SECRET_ACCESS_KEY=""
    export AWS_SESSION_TOKEN=""
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn"
 "$policy_arn" "$assume_role_policy_arn"
    return 1
  fi

  local result=0
  export AWS_ACCESS_KEY_ID=""
  export AWS_SECRET_ACCESS_KEY=""

  echo
  echo_repeat "*" 88
  echo "The created resources will now be deleted."
  echo_repeat "*" 88
  echo

  clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn" "$policy_arn"
 "$assume_role_policy_arn"

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    result=1
  fi

  return $result
}
```

As funções do IAM usadas nesse cenário.

```
##############################################################################
```

```
# function iam_user_exists
#
# This function checks to see if the specified AWS Identity and Access Management
 (IAM) user already exists.
#
# Parameters:
#       $1 - The name of the IAM user to check.
#
# Returns:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
###############################################################################
function iam_user_exists() {
  local user_name
  user_name=$1

  # Check whether the IAM user already exists.
  # We suppress all output - we're interested only in the return code.

  local errors
  errors=$(aws iam get-user \
    --user-name "$user_name" 2>&1 >/dev/null)

  local error_code=${?}

  if [[ $error_code -eq 0 ]]; then
    return 0 # 0 in Bash script means true.
  else
    if [[ $errors != *"error"*"(NoSuchEntity)"* ]]; then
      aws_cli_error_log $error_code
      errecho "Error calling iam get-user $errors"
    fi

    return 1 # 1 in Bash script means false.
  fi
}

###############################################################################
# function iam_create_user
#
# This function creates the specified IAM user, unless
# it already exists.
#
# Parameters:
```

```
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       The ARN of the user.
#     And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_create_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user"
    echo "Creates an WS Identity and Access Management (IAM) user. You must
 supply a username:"
    echo "  -u user_name    The name of the user. It must be unique within the
 account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi
```

```
  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""

  # If the user already exists, we don't want to try to create it.
  if (iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name already exists in the account."
    return 1
  fi

  response=$(aws iam create-user --user-name "$user_name" \
    --output text \
    --query 'User.Arn')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-user operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_create_user_access_key
#
# This function creates an IAM access key for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#       [-f file_name] -- The optional file name for the access key output.
#
# Returns:
#       [access_key_id access_key_secret]
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_user_access_key() {
```

```
  local user_name file_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) key pair."
    echo "  -u user_name   The name of the IAM user."
    echo "  [-f file_name]   Optional file name for the access key output."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:f:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      f) file_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  response=$(aws iam create-access-key \
    --user-name "$user_name" \
    --output text)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
```

```
    errecho "ERROR: AWS reports create-access-key operation failed.$response"
    return 1
  fi

  if [[ -n "$file_name" ]]; then
    echo "$response" >"$file_name"
  fi

  local key_id key_secret
  # shellcheck disable=SC2086
  key_id=$(echo $response | cut -f 2 -d ' ')
  # shellcheck disable=SC2086
  key_secret=$(echo $response | cut -f 4 -d ' ')

  echo "$key_id $key_secret"

  return 0
}

###############################################################################
# function iam_create_role
#
# This function creates an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_json -- The assume role policy document.
#
# Returns:
#       The ARN of the role.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_role() {
  local role_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_json -- The assume role policy document."
```

```
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) role_name="${OPTARG}" ;;
    p) policy_document="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$role_name" ]]; then
  errecho "ERROR: You must provide a role name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_document" ]]; then
  errecho "ERROR: You must provide a policy document with the -p parameter."
  usage
  return 1
fi

response=$(aws iam create-role \
  --role-name "$role_name" \
  --assume-role-policy-document "$policy_document" \
  --output text \
  --query Role.Arn)

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports create-role operation failed.\n$response"
```

```
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_create_policy
#
# This function creates an IAM policy.
#
# Parameters:
#       -n policy_name -- The name of the IAM policy.
#       -p policy_json -- The policy document.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_policy() {
  local policy_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_policy"
    echo "Creates an AWS Identity and Access Management (IAM) policy."
    echo "  -n policy_name   The name of the IAM policy."
    echo "  -p policy_json -- The policy document."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) policy_name="${OPTARG}" ;;
      p) policy_document="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
```

```
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$policy_name" ]]; then
    errecho "ERROR: You must provide a policy name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_document" ]]; then
    errecho "ERROR: You must provide a policy document with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam create-policy \
    --policy-name "$policy_name" \
    --policy-document "$policy_document" \
    --output text \
    --query Policy.Arn)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"
}

###############################################################################
# function iam_attach_role_policy
#
# This function attaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
```

```
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_attach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_attach_role_policy"
    echo "Attaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi
```

```
  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam attach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports attach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_detach_role_policy
#
# This function detaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_detach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_detach_role_policy"
```

```
    echo "Detaches an AWS Identity and Access Management (IAM) policy to an IAM
role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam detach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
```

```
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports detach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_delete_policy
#
# This function deletes an IAM policy.
#
# Parameters:
#       -n policy_arn -- The name of the IAM policy arn.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_policy() {
  local policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_policy"
    echo "Deletes an WS Identity and Access Management (IAM) policy"
    echo "  -n policy_arn -- The name of the IAM policy arn."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
```

```
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy arn with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Policy arn:  $policy_arn"
  iecho ""

  response=$(aws iam delete-policy \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-policy operation failed.\n$response"
    return 1
  fi

  iecho "delete-policy response:$response"
  iecho

  return 0
}

###############################################################################
# function iam_delete_role
#
# This function deletes an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#
# Returns:
#       0 - If successful.
```

```
#       1 - If it fails.
###############################################################################
function iam_delete_role() {
  local role_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_role"
    echo "Deletes an WS Identity and Access Management (IAM) role"
    echo "  -n role_name -- The name of the IAM role."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  echo "role_name:$role_name"
  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Role name:  $role_name"
  iecho ""

  response=$(aws iam delete-role \
    --role-name "$role_name")
```

```
  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-role operation failed.\n$response"
    return 1
  fi

  iecho "delete-role response:$response"
  iecho

  return 0
}

###############################################################################
# function iam_delete_access_key
#
# This function deletes an IAM access key for the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user.
#       -k access_key -- The access key to delete.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_access_key() {
  local user_name access_key response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_access_key"
    echo "Deletes an WS Identity and Access Management (IAM) access key for the
 specified IAM user"
    echo "  -u user_name    The name of the user."
    echo "  -k access_key   The access key to delete."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:k:h" option; do
```

```
  case "${option}" in
    u) user_name="${OPTARG}" ;;
    k) access_key="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$user_name" ]]; then
  errecho "ERROR: You must provide a username with the -u parameter."
  usage
  return 1
fi

if [[ -z "$access_key" ]]; then
  errecho "ERROR: You must provide an access key with the -k parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    Username:   $user_name"
iecho "    Access key:   $access_key"
iecho ""

response=$(aws iam delete-access-key \
  --user-name "$user_name" \
  --access-key-id "$access_key")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports delete-access-key operation failed.\n$response"
  return 1
fi
```

```
  iecho "delete-access-key response:$response"
  iecho

  return 0
}

###############################################################################
# function iam_delete_user
#
# This function deletes the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_user"
    echo "Deletes an WS Identity and Access Management (IAM) user. You must
 supply a username:"
    echo "  -u user_name    The name of the user."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
```

```
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""

  # If the user does not exist, we don't want to try to delete it.
  if (! iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name does not exist in the account."
    return 1
  fi

  response=$(aws iam delete-user \
    --user-name "$user_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-user operation failed.$response"
    return 1
  fi

  iecho "delete-user response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - AttachRolePolicy

- CreateAccessKey
- CreatePolicy
- CreateRole
- CreateUser
- DeleteAccessKey
- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace AwsDoc {
    namespace IAM {

        //! Cleanup by deleting created entities.
        /*!
          \sa DeleteCreatedEntities
          \param client: IAM client.
          \param role: IAM role.
          \param user: IAM user.
          \param policy: IAM policy.
        */
        static bool DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                          const Aws::IAM::Model::Role &role,
                                          const Aws::IAM::Model::User &user,
                                          const Aws::IAM::Model::Policy &policy);
```

```
    }

    static const int LIST_BUCKETS_WAIT_SEC = 20;

    static const char ALLOCATION_TAG[] = "example_code";
}

//! Scenario to create an IAM user, create an IAM role, and apply the role to the
 user.
// "IAM access" permissions are needed to run this code.
// "STS assume role" permissions are needed to run this code. (Note: It might be
 necessary to
//    create a custom policy).
/*!
  \sa iamCreateUserAssumeRoleScenario
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
*/
bool AwsDoc::IAM::iamCreateUserAssumeRoleScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::User user;
    Aws::IAM::Model::Role role;
    Aws::IAM::Model::Policy policy;

    // 1. Create a user.
    {
        Aws::IAM::Model::CreateUserRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String userName = "iam-demo-user-" +
                                Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetUserName(userName);

        Aws::IAM::Model::CreateUserOutcome outcome = client.CreateUser(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Error creating IAM user " << userName << ":" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            std::cout << "Successfully created IAM user " << userName <<
 std::endl;
        }
```

```
        user = outcome.GetResult().GetUser();
    }

    // 2. Create a role.
    {
        // Get the IAM user for the current client in order to access its ARN.
        Aws::String iamUserArn;
        {
            Aws::IAM::Model::GetUserRequest request;
            Aws::IAM::Model::GetUserOutcome outcome = client.GetUser(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error getting Iam user. " <<
                          outcome.GetError().GetMessage() << std::endl;

                DeleteCreatedEntities(client, role, user, policy);
                return false;
            }
            else {
                std::cout << "Successfully retrieved Iam user "
                          << outcome.GetResult().GetUser().GetUserName()
                          << std::endl;
            }

            iamUserArn = outcome.GetResult().GetUser().GetArn();
        }

        Aws::IAM::Model::CreateRoleRequest request;

        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String roleName = "iam-demo-role-" +
                               Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetRoleName(roleName);

        // Build policy document for role.
        Aws::Utils::Document jsonStatement;
        jsonStatement.WithString("Effect", "Allow");

        Aws::Utils::Document jsonPrincipal;
        jsonPrincipal.WithString("AWS", iamUserArn);
        jsonStatement.WithObject("Principal", jsonPrincipal);
        jsonStatement.WithString("Action", "sts:AssumeRole");
        jsonStatement.WithObject("Condition", Aws::Utils::Document());
```

```
        Aws::Utils::Document policyDocument;
        policyDocument.WithString("Version", "2012-10-17");

        Aws::Utils::Array<Aws::Utils::Document> statements(1);
        statements[0] = jsonStatement;
        policyDocument.WithArray("Statement", statements);

        std::cout << "Setting policy for role\n   "
                  << policyDocument.View().WriteCompact() << std::endl;

        // Set role policy document as JSON string.

  request.SetAssumeRolePolicyDocument(policyDocument.View().WriteCompact());

        Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating role. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
        }
        else {
            std::cout << "Successfully created a role with name " << roleName
                      << std::endl;
        }

        role = outcome.GetResult().GetRole();
    }

    // 3. Create an IAM policy.
    {
        Aws::IAM::Model::CreatePolicyRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String policyName = "iam-demo-policy-" +
                                 Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetPolicyName(policyName);

        // Build IAM policy document.
        Aws::Utils::Document jsonStatement;
        jsonStatement.WithString("Effect", "Allow");
        jsonStatement.WithString("Action", "s3:ListAllMyBuckets");
        jsonStatement.WithString("Resource", "arn:aws:s3:::*");
```

```
        Aws::Utils::Document policyDocument;
        policyDocument.WithString("Version", "2012-10-17");

        Aws::Utils::Array<Aws::Utils::Document> statements(1);
        statements[0] = jsonStatement;
        policyDocument.WithArray("Statement", statements);

        std::cout << "Creating a policy.\n   " <<
policyDocument.View().WriteCompact()
                  << std::endl;

        // Set IAM policy document as JSON string.
        request.SetPolicyDocument(policyDocument.View().WriteCompact());

        Aws::IAM::Model::CreatePolicyOutcome outcome =
client.CreatePolicy(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
        }
        else {
            std::cout << "Successfully created a policy with name, " <<
policyName <<
                      "." << std::endl;
        }

        policy = outcome.GetResult().GetPolicy();
    }

    // 4. Assume the new role using the AWS Security Token Service (STS).
    Aws::STS::Model::Credentials credentials;
    {
        Aws::STS::STSClient stsClient(clientConfig);

        Aws::STS::Model::AssumeRoleRequest request;
        request.SetRoleArn(role.GetArn());
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String roleSessionName = "iam-demo-role-session-" +

Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetRoleSessionName(roleSessionName);
```

```
        Aws::STS::Model::AssumeRoleOutcome assumeRoleOutcome;

        // Repeatedly call AssumeRole, because there is often a delay
        // before the role is available to be assumed.
        // Repeat at most 20 times when access is denied.
        int count = 0;
        while (true) {
            assumeRoleOutcome = stsClient.AssumeRole(request);
            if (!assumeRoleOutcome.IsSuccess()) {
                if (count > 20 ||
                    assumeRoleOutcome.GetError().GetErrorType() !=
                    Aws::STS::STSErrors::ACCESS_DENIED) {
                    std::cerr << "Error assuming role after 20 tries. " <<
                              assumeRoleOutcome.GetError().GetMessage() <<
std::endl;

                    DeleteCreatedEntities(client, role, user, policy);
                    return false;
                }
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                std::cout << "Successfully assumed the role after " << count
                          << " seconds." << std::endl;
                break;
            }
            count++;
        }

        credentials = assumeRoleOutcome.GetResult().GetCredentials();
    }


    // 5. List objects in the bucket (This should fail).
    {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
s3Client.ListBuckets();
```

```
        if (!listBucketsOutcome.IsSuccess()) {
            if (listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets. " <<
                          listBucketsOutcome.GetError().GetMessage() <<
std::endl;
            }
            else {
                std::cout
                        << "Access to list buckets denied because privileges have
not been applied."
                        << std::endl;
            }
        }
        else {
            std::cerr
                    << "Successfully retrieved bucket lists when this should not
happen."
                    << std::endl;
        }
    }

    // 6. Attach the policy to the role.
    {
        Aws::IAM::Model::AttachRolePolicyRequest request;
        request.SetRoleName(role.GetRoleName());
        request.WithPolicyArn(policy.GetArn());

        Aws::IAM::Model::AttachRolePolicyOutcome outcome =
client.AttachRolePolicy(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
        }
        else {
            std::cout << "Successfully attached the policy with name, "
                      << policy.GetPolicyName() <<
                      ", to the role, " << role.GetRoleName() << "." <<
std::endl;
        }
```

```
    }

    int count = 0;
    // 7. List objects in the bucket (this should succeed).
    // Repeatedly call ListBuckets, because there is often a delay
    // before the policy with ListBucket permissions has been applied to the
 role.
    // Repeat at most LIST_BUCKETS_WAIT_SEC times when access is denied.
    while (true) {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
 s3Client.ListBuckets();
        if (!listBucketsOutcome.IsSuccess()) {
            if ((count > LIST_BUCKETS_WAIT_SEC) ||
                listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets after " <<
 LIST_BUCKETS_WAIT_SEC << " seconds. " <<
                          listBucketsOutcome.GetError().GetMessage() <<
 std::endl;
                DeleteCreatedEntities(client, role, user, policy);
                return false;
            }

            std::this_thread::sleep_for(std::chrono::seconds(1));
        }
        else {

            std::cout << "Successfully retrieved bucket lists after " << count
                      << " seconds." << std::endl;
            break;
        }
        count++;
    }

    // 8. Delete all the created resources.
    return DeleteCreatedEntities(client, role, user, policy);
}
```

```
bool AwsDoc::IAM::DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                        const Aws::IAM::Model::Role &role,
                                        const Aws::IAM::Model::User &user,
                                        const Aws::IAM::Model::Policy &policy) {
    bool result = true;
    if (policy.ArnHasBeenSet()) {
        // Detach the policy from the role.
        {
            Aws::IAM::Model::DetachRolePolicyRequest request;
            request.SetPolicyArn(policy.GetArn());
            request.SetRoleName(role.GetRoleName());

            Aws::IAM::Model::DetachRolePolicyOutcome outcome =
 client.DetachRolePolicy(
                    request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error Detaching policy from roles. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully detached the policy with arn "
                          << policy.GetArn()
                          << " from role " << role.GetRoleName() << "." <<
 std::endl;
            }
        }

        // Delete the policy.
        {
            Aws::IAM::Model::DeletePolicyRequest request;
            request.WithPolicyArn(policy.GetArn());

            Aws::IAM::Model::DeletePolicyOutcome outcome =
 client.DeletePolicy(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error deleting policy. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully deleted the policy with arn "
                          << policy.GetArn() << std::endl;
            }
```

```
        }

    }

    if (role.RoleIdHasBeenSet()) {
        // Delete the role.
        Aws::IAM::Model::DeleteRoleRequest request;
        request.SetRoleName(role.GetRoleName());

        Aws::IAM::Model::DeleteRoleOutcome outcome = client.DeleteRole(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting role. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the role with name "
                      << role.GetRoleName() << std::endl;
        }
    }

    if (user.ArnHasBeenSet()) {
        // Delete the user.
        Aws::IAM::Model::DeleteUserRequest request;
        request.WithUserName(user.GetUserName());

        Aws::IAM::Model::DeleteUserOutcome outcome = client.DeleteUser(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting user. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the user with name "
                      << user.GetUserName() << std::endl;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// AssumeRoleScenario shows you how to use the AWS Identity and Access Management
 (IAM)
// service to perform the following actions:
//
// 1. Create a user who has no permissions.
// 2. Create a role that grants permission to list Amazon Simple Storage Service
//    (Amazon S3) buckets for the account.
// 3. Add a policy to let the user assume the role.
```

```
// 4. Try and fail to list buckets without permissions.
// 5. Assume the role and list S3 buckets using temporary credentials.
// 6. Delete the policy, role, and user.
type AssumeRoleScenario struct {
 sdkConfig aws.Config
 accountWrapper actions.AccountWrapper
 policyWrapper actions.PolicyWrapper
 roleWrapper actions.RoleWrapper
 userWrapper actions.UserWrapper
 questioner demotools.IQuestioner
 helper IScenarioHelper
 isTestRun bool
}

// NewAssumeRoleScenario constructs an AssumeRoleScenario instance from a
 configuration.
// It uses the specified config to get an IAM client and create wrappers for the
 actions
// used in the scenario.
func NewAssumeRoleScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner,
  helper IScenarioHelper) AssumeRoleScenario {
 iamClient := iam.NewFromConfig(sdkConfig)
 return AssumeRoleScenario{
  sdkConfig:   sdkConfig,
  accountWrapper: actions.AccountWrapper{IamClient: iamClient},
  policyWrapper:  actions.PolicyWrapper{IamClient: iamClient},
  roleWrapper:    actions.RoleWrapper{IamClient: iamClient},
  userWrapper:    actions.UserWrapper{IamClient: iamClient},
  questioner:     questioner,
  helper:         helper,
 }
}

// addTestOptions appends the API options specified in the original configuration
 to
// another configuration. This is used to attach the middleware stubber to
 clients
// that are constructed during the scenario, which is needed for unit testing.
func (scenario AssumeRoleScenario) addTestOptions(scenarioConfig *aws.Config) {
 if scenario.isTestRun {
  scenarioConfig.APIOptions = append(scenarioConfig.APIOptions,
 scenario.sdkConfig.APIOptions...)
 }
```

```
}

// Run runs the interactive scenario.
func (scenario AssumeRoleScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo.\n")
   log.Println(r)
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the AWS Identity and Access Management (IAM) assume role
 demo.")
 log.Println(strings.Repeat("-", 88))

 user := scenario.CreateUser()
 accessKey := scenario.CreateAccessKey(user)
 role := scenario.CreateRoleAndPolicies(user)
 noPermsConfig := scenario.ListBucketsWithoutPermissions(accessKey)
 scenario.ListBucketsWithAssumedRole(noPermsConfig, role)
 scenario.Cleanup(user, role)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateUser creates a new IAM user. This user has no permissions.
func (scenario AssumeRoleScenario) CreateUser() *types.User {
 log.Println("Let's create an example user with no permissions.")
 userName := scenario.questioner.Ask("Enter a name for the example user:",
 demotools.NotEmpty{})
 user, err := scenario.userWrapper.GetUser(userName)
 if err != nil {
  panic(err)
 }
 if user == nil {
  user, err = scenario.userWrapper.CreateUser(userName)
  if err != nil {
   panic(err)
  }
  log.Printf("Created user %v.\n", *user.UserName)
 } else {
```

```
  log.Printf("User %v already exists.\n", *user.UserName)
 }
 log.Println(strings.Repeat("-", 88))
 return user
}

// CreateAccessKey creates an access key for the user.
func (scenario AssumeRoleScenario) CreateAccessKey(user *types.User)
 *types.AccessKey {
 accessKey, err := scenario.userWrapper.CreateAccessKeyPair(*user.UserName)
 if err != nil {
  panic(err)
 }
 log.Printf("Created access key %v for your user.", *accessKey.AccessKeyId)
 log.Println("Waiting a few seconds for your user to be ready...")
 scenario.helper.Pause(10)
 log.Println(strings.Repeat("-", 88))
 return accessKey
}

// CreateRoleAndPolicies creates a policy that grants permission to list S3
 buckets for
// the current account and attaches the policy to a newly created role. It also
 adds an
// inline policy to the specified user that grants the user permission to assume
 the role.
func (scenario AssumeRoleScenario) CreateRoleAndPolicies(user *types.User)
 *types.Role {
 log.Println("Let's create a role and policy that grant permission to list S3
 buckets.")
 scenario.questioner.Ask("Press Enter when you're ready.")
 listBucketsRole, err :=
 scenario.roleWrapper.CreateRole(scenario.helper.GetName(), *user.Arn)
 if err != nil {panic(err)}
 log.Printf("Created role %v.\n", *listBucketsRole.RoleName)
 listBucketsPolicy, err := scenario.policyWrapper.CreatePolicy(
  scenario.helper.GetName(), []string{"s3:ListAllMyBuckets"}, "arn:aws:s3:::*")
 if err != nil {panic(err)}
 log.Printf("Created policy %v.\n", *listBucketsPolicy.PolicyName)
 err = scenario.roleWrapper.AttachRolePolicy(*listBucketsPolicy.Arn,
 *listBucketsRole.RoleName)
 if err != nil {panic(err)}
 log.Printf("Attached policy %v to role %v.\n", *listBucketsPolicy.PolicyName,
  *listBucketsRole.RoleName)
```

```
 err = scenario.userWrapper.CreateUserPolicy(*user.UserName,
 scenario.helper.GetName(),
  []string{"sts:AssumeRole"}, *listBucketsRole.Arn)
 if err != nil {panic(err)}
 log.Printf("Created an inline policy for user %v that lets the user assume the
 role.\n",
  *user.UserName)
 log.Println("Let's give AWS a few seconds to propagate these new resources and
 connections...")
 scenario.helper.Pause(10)
 log.Println(strings.Repeat("-", 88))
 return listBucketsRole
}

// ListBucketsWithoutPermissions creates an Amazon S3 client from the user's
 access key
// credentials and tries to list buckets for the account. Because the user does
 not have
// permission to perform this action, the action fails.
func (scenario AssumeRoleScenario) ListBucketsWithoutPermissions(accessKey
 *types.AccessKey) *aws.Config {
  log.Println("Let's try to list buckets without permissions. This should return
 an AccessDenied error.")
  scenario.questioner.Ask("Press Enter when you're ready.")
  noPermsConfig, err := config.LoadDefaultConfig(context.TODO(),
  config.WithCredentialsProvider(credentials.NewStaticCredentialsProvider(
   *accessKey.AccessKeyId, *accessKey.SecretAccessKey, ""),
 ))
  if err != nil {panic(err)}

  // Add test options if this is a test run. This is needed only for testing
 purposes.
 scenario.addTestOptions(&noPermsConfig)

  s3Client := s3.NewFromConfig(noPermsConfig)
  _, err = s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
  if err != nil {
   // The SDK for Go does not model the AccessDenied error, so check ErrorCode
 directly.
  var ae smithy.APIError
  if errors.As(err, &ae) {
   switch ae.ErrorCode() {
   case "AccessDenied":
```

```
    log.Println("Got AccessDenied error, which is the expected result because\n"
 +
     "the ListBuckets call was made without permissions.")
   default:
    log.Println("Expected AccessDenied, got something else.")
    panic(err)
   }
  }
  } else {
   log.Println("Expected AccessDenied error when calling ListBuckets without
 permissions,\n" +
    "but the call succeeded. Continuing the example anyway...")
 }
 log.Println(strings.Repeat("-", 88))
  return &noPermsConfig
}

// ListBucketsWithAssumedRole performs the following actions:
//
// 1. Creates an AWS Security Token Service (AWS STS) client from the config
 created from
//   the user's access key credentials.
// 2. Gets temporary credentials by assuming the role that grants permission to
 list the
//    buckets.
// 3. Creates an Amazon S3 client from the temporary credentials.
// 4. Lists buckets for the account. Because the temporary credentials are
 generated by
//    assuming the role that grants permission, the action succeeds.
func (scenario AssumeRoleScenario) ListBucketsWithAssumedRole(noPermsConfig
 *aws.Config, role *types.Role) {
 log.Println("Let's assume the role that grants permission to list buckets and
 try again.")
 scenario.questioner.Ask("Press Enter when you're ready.")
 stsClient := sts.NewFromConfig(*noPermsConfig)
 tempCredentials, err := stsClient.AssumeRole(context.TODO(),
 &sts.AssumeRoleInput{
  RoleArn:           role.Arn,
  RoleSessionName:   aws.String("AssumeRoleExampleSession"),
  DurationSeconds:   aws.Int32(900),
 })
 if err != nil {
  log.Printf("Couldn't assume role %v.\n", *role.RoleName)
  panic(err)
```

```
 }
 log.Printf("Assumed role %v, got temporary credentials.\n", *role.RoleName)
 assumeRoleConfig, err := config.LoadDefaultConfig(context.TODO(),
  config.WithCredentialsProvider(credentials.NewStaticCredentialsProvider(
   *tempCredentials.Credentials.AccessKeyId,
   *tempCredentials.Credentials.SecretAccessKey,
   *tempCredentials.Credentials.SessionToken),
  ),
 )
 if err != nil {panic(err)}

 // Add test options if this is a test run. This is needed only for testing
 purposes.
 scenario.addTestOptions(&assumeRoleConfig)

 s3Client := s3.NewFromConfig(assumeRoleConfig)
 result, err := s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 if err != nil {
  log.Println("Couldn't list buckets with assumed role credentials.")
  panic(err)
 }
 log.Println("Successfully called ListBuckets with assumed role credentials, \n"
 +
  "here are some of them:")
 for i := 0; i < len(result.Buckets) && i < 5; i++ {
  log.Printf("\t%v\n", *result.Buckets[i].Name)
 }
 log.Println(strings.Repeat("-", 88))
}

// Cleanup deletes all resources created for the scenario.
func (scenario AssumeRoleScenario) Cleanup(user *types.User, role *types.Role) {
 if scenario.questioner.AskBool(
  "Do you want to delete the resources created for this example? (y/n)", "y",
 ) {
   policies, err := scenario.roleWrapper.ListAttachedRolePolicies(*role.RoleName)
   if err != nil {panic(err)}
   for _, policy := range policies {
    err = scenario.roleWrapper.DetachRolePolicy(*role.RoleName,
 *policy.PolicyArn)
    if err != nil {panic(err)}
    err = scenario.policyWrapper.DeletePolicy(*policy.PolicyArn)
    if err != nil {panic(err)}
    log.Printf("Detached policy %v from role %v and deleted the policy.\n",
```

```
      *policy.PolicyName, *role.RoleName)
    }
    err = scenario.roleWrapper.DeleteRole(*role.RoleName)
    if err != nil {panic(err)}
    log.Printf("Deleted role %v.\n", *role.RoleName)

    userPols, err := scenario.userWrapper.ListUserPolicies(*user.UserName)
    if err != nil {panic(err)}
    for _, userPol := range userPols {
     err = scenario.userWrapper.DeleteUserPolicy(*user.UserName, userPol)
     if err != nil {panic(err)}
     log.Printf("Deleted policy %v from user %v.\n", userPol, *user.UserName)
    }
    keys, err := scenario.userWrapper.ListAccessKeys(*user.UserName)
    if err != nil {panic(err)}
    for _, key := range keys {
     err = scenario.userWrapper.DeleteAccessKey(*user.UserName, *key.AccessKeyId)
     if err != nil {panic(err)}
     log.Printf("Deleted access key %v from user %v.\n", *key.AccessKeyId,
 *user.UserName)
    }
    err = scenario.userWrapper.DeleteUser(*user.UserName)
    if err != nil {panic(err)}
    log.Printf("Deleted user %v.\n", *user.UserName)
    log.Println(strings.Repeat("-", 88))
  }

}
```

Defina um struct que encapsule as ações de conta.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
}
```

```
// GetAccountPasswordPolicy gets the account password policy for the current
 account.
// If no policy has been set, a NoSuchEntityException is error is returned.
func (wrapper AccountWrapper) GetAccountPasswordPolicy() (*types.PasswordPolicy,
 error) {
 var pwPolicy *types.PasswordPolicy
 result, err := wrapper.IamClient.GetAccountPasswordPolicy(context.TODO(),
  &iam.GetAccountPasswordPolicyInput{})
 if err != nil {
  log.Printf("Couldn't get account password policy. Here's why: %v\n", err)
 } else {
  pwPolicy = result.PasswordPolicy
 }
 return pwPolicy, err
}



// ListSAMLProviders gets the SAML providers for the account.
func (wrapper AccountWrapper) ListSAMLProviders() ([]types.SAMLProviderListEntry,
 error) {
 var providers []types.SAMLProviderListEntry
 result, err := wrapper.IamClient.ListSAMLProviders(context.TODO(),
 &iam.ListSAMLProvidersInput{})
 if err != nil {
  log.Printf("Couldn't list SAML providers. Here's why: %v\n", err)
 } else {
  providers = result.SAMLProviderList
 }
 return providers, err
}
```

Defina um struct que encapsule as ações de política.

```
// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version string
 Statement []PolicyStatement
```

```
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect string
 Action []string
 Principal map[string]string `json:",omitempty"`
 Resource *string `json:",omitempty"`
}



// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// ListPolicies gets up to maxPolicies policies.
func (wrapper PolicyWrapper) ListPolicies(maxPolicies int32) ([]types.Policy,
 error) {
 var policies []types.Policy
 result, err := wrapper.IamClient.ListPolicies(context.TODO(),
 &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPolicies),
 })
 if err != nil {
  log.Printf("Couldn't list policies. Here's why: %v\n", err)
 } else {
  policies = result.Policies
 }
 return policies, err
}



// CreatePolicy creates a policy that grants a list of actions to the specified
 resource.
// PolicyDocument shows how to work with a policy document as a data structure
 and
```

```
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper PolicyWrapper) CreatePolicy(policyName string, actions []string,
  resourceArn string) (*types.Policy, error) {
 var policy *types.Policy
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(resourceArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n",
 resourceArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreatePolicy(context.TODO(),
 &iam.CreatePolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
 })
 if err != nil {
  log.Printf("Couldn't create policy %v. Here's why: %v\n", policyName, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}



// GetPolicy gets data about a policy.
func (wrapper PolicyWrapper) GetPolicy(policyArn string) (*types.Policy, error) {
 var policy *types.Policy
 result, err := wrapper.IamClient.GetPolicy(context.TODO(), &iam.GetPolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't get policy %v. Here's why: %v\n", policyArn, err)
 } else {
  policy = result.Policy
 }
```

```
 return policy, err
}



// DeletePolicy deletes a policy.
func (wrapper PolicyWrapper) DeletePolicy(policyArn string) error {
 _, err := wrapper.IamClient.DeletePolicy(context.TODO(), &iam.DeletePolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't delete policy %v. Here's why: %v\n", policyArn, err)
 }
 return err
}
```

Defina um struct que encapsule as ações de perfil.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRoles gets up to maxRoles roles.
func (wrapper RoleWrapper) ListRoles(maxRoles int32) ([]types.Role, error) {
 var roles []types.Role
 result, err := wrapper.IamClient.ListRoles(context.TODO(),
  &iam.ListRolesInput{MaxItems: aws.Int32(maxRoles)},
 )
 if err != nil {
  log.Printf("Couldn't list roles. Here's why: %v\n", err)
 } else {
  roles = result.Roles
 }
 return roles, err
}
```

```
// CreateRole creates a role that trusts a specified user. The trusted user can
 assume
// the role to acquire its permissions.
// PolicyDocument shows how to work with a policy document as a data structure
 and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper RoleWrapper) CreateRole(roleName string, trustedUserArn string)
 (*types.Role, error) {
 var role *types.Role
 trustPolicy := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Principal: map[string]string{"AWS": trustedUserArn},
   Action: []string{"sts:AssumeRole"},
  }},
 }
 policyBytes, err := json.Marshal(trustPolicy)
 if err != nil {
  log.Printf("Couldn't create trust policy for %v. Here's why: %v\n",
 trustedUserArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreateRole(context.TODO(),
 &iam.CreateRoleInput{
  AssumeRolePolicyDocument: aws.String(string(policyBytes)),
  RoleName:                 aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't create role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// GetRole gets data about a role.
func (wrapper RoleWrapper) GetRole(roleName string) (*types.Role, error) {
 var role *types.Role
```

```
 result, err := wrapper.IamClient.GetRole(context.TODO(),
  &iam.GetRoleInput{RoleName: aws.String(roleName)})
 if err != nil {
  log.Printf("Couldn't get role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// CreateServiceLinkedRole creates a service-linked role that is owned by the
 specified service.
func (wrapper RoleWrapper) CreateServiceLinkedRole(serviceName string,
 description string) (*types.Role, error) {
 var role *types.Role
 result, err := wrapper.IamClient.CreateServiceLinkedRole(context.TODO(),
 &iam.CreateServiceLinkedRoleInput{
  AWSServiceName: aws.String(serviceName),
  Description:    aws.String(description),
 })
 if err != nil {
  log.Printf("Couldn't create service-linked role %v. Here's why: %v\n",
 serviceName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// DeleteServiceLinkedRole deletes a service-linked role.
func (wrapper RoleWrapper) DeleteServiceLinkedRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteServiceLinkedRole(context.TODO(),
 &iam.DeleteServiceLinkedRoleInput{
  RoleName: aws.String(roleName)},
 )
 if err != nil {
  log.Printf("Couldn't delete service-linked role %v. Here's why: %v\n",
 roleName, err)
 }
 return err
```

```
}



// AttachRolePolicy attaches a policy to a role.
func (wrapper RoleWrapper) AttachRolePolicy(policyArn string, roleName string)
 error {
 _, err := wrapper.IamClient.AttachRolePolicy(context.TODO(),
 &iam.AttachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't attach policy %v to role %v. Here's why: %v\n", policyArn,
 roleName, err)
 }
 return err
}



// ListAttachedRolePolicies lists the policies that are attached to the specified
 role.
func (wrapper RoleWrapper) ListAttachedRolePolicies(roleName string)
 ([]types.AttachedPolicy, error) {
 var policies []types.AttachedPolicy
 result, err := wrapper.IamClient.ListAttachedRolePolicies(context.TODO(),
 &iam.ListAttachedRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list attached policies for role %v. Here's why: %v\n",
 roleName, err)
 } else {
  policies = result.AttachedPolicies
 }
 return policies, err
}



// DetachRolePolicy detaches a policy from a role.
func (wrapper RoleWrapper) DetachRolePolicy(roleName string, policyArn string)
 error {
```

```
 _, err := wrapper.IamClient.DetachRolePolicy(context.TODO(),
 &iam.DetachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't detach policy from role %v. Here's why: %v\n", roleName,
 err)
 }
 return err
}



// ListRolePolicies lists the inline policies for a role.
func (wrapper RoleWrapper) ListRolePolicies(roleName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListRolePolicies(context.TODO(),
 &iam.ListRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for role %v. Here's why: %v\n", roleName,
 err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}



// DeleteRole deletes a role. All attached policies must be detached before a
// role can be deleted.
func (wrapper RoleWrapper) DeleteRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't delete role %v. Here's why: %v\n", roleName, err)
 }
 return err
}
```

Defina um struct que encapsule as ações de usuário.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUsers gets up to maxUsers number of users.
func (wrapper UserWrapper) ListUsers(maxUsers int32) ([]types.User, error) {
 var users []types.User
 result, err := wrapper.IamClient.ListUsers(context.TODO(), &iam.ListUsersInput{
  MaxItems: aws.Int32(maxUsers),
 })
 if err != nil {
  log.Printf("Couldn't list users. Here's why: %v\n", err)
 } else {
  users = result.Users
 }
 return users, err
}



// GetUser gets data about a user.
func (wrapper UserWrapper) GetUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.GetUser(context.TODO(), &iam.GetUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NoSuchEntityException:
    log.Printf("User %v does not exist.\n", userName)
    err = nil
```

```
    default:
     log.Printf("Couldn't get user %v. Here's why: %v\n", userName, err)
    }
   }
  } else {
   user = result.User
  }
  return user, err
}



// CreateUser creates a new user with the specified name.
func (wrapper UserWrapper) CreateUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.CreateUser(context.TODO(),
 &iam.CreateUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create user %v. Here's why: %v\n", userName, err)
 } else {
  user = result.User
 }
 return user, err
}



// CreateUserPolicy adds an inline policy to a user. This example creates a
 policy that
// grants a list of actions on a specified role.
// PolicyDocument shows how to work with a policy document as a data structure
 and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper UserWrapper) CreateUserPolicy(userName string, policyName string,
 actions []string,
  roleArn string) error {
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(roleArn),
```

```
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n", roleArn,
 err)
  return err
 }
 _, err = wrapper.IamClient.PutUserPolicy(context.TODO(),
 &iam.PutUserPolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
  UserName:       aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create policy for user %v. Here's why: %v\n", userName,
 err)
 }
 return err
}



// ListUserPolicies lists the inline policies for the specified user.
func (wrapper UserWrapper) ListUserPolicies(userName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListUserPolicies(context.TODO(),
 &iam.ListUserPoliciesInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for user %v. Here's why: %v\n", userName,
 err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}



// DeleteUserPolicy deletes an inline policy from a user.
func (wrapper UserWrapper) DeleteUserPolicy(userName string, policyName string)
 error {
```

```
 _, err := wrapper.IamClient.DeleteUserPolicy(context.TODO(),
 &iam.DeleteUserPolicyInput{
  PolicyName: aws.String(policyName),
  UserName:   aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete policy from user %v. Here's why: %v\n", userName,
 err)
 }
 return err
}



// DeleteUser deletes a user.
func (wrapper UserWrapper) DeleteUser(userName string) error {
 _, err := wrapper.IamClient.DeleteUser(context.TODO(), &iam.DeleteUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete user %v. Here's why: %v\n", userName, err)
 }
 return err
}



// CreateAccessKeyPair creates an access key for a user. The returned access key
 contains
// the ID and secret credentials needed to use the key.
func (wrapper UserWrapper) CreateAccessKeyPair(userName string)
 (*types.AccessKey, error) {
 var key *types.AccessKey
 result, err := wrapper.IamClient.CreateAccessKey(context.TODO(),
 &iam.CreateAccessKeyInput{
  UserName: aws.String(userName)})
 if err != nil {
  log.Printf("Couldn't create access key pair for user %v. Here's why: %v\n",
 userName, err)
 } else {
  key = result.AccessKey
 }
 return key, err
}
```

```
// DeleteAccessKey deletes an access key from a user.
func (wrapper UserWrapper) DeleteAccessKey(userName string, keyId string) error {
 _, err := wrapper.IamClient.DeleteAccessKey(context.TODO(),
 &iam.DeleteAccessKeyInput{
  AccessKeyId: aws.String(keyId),
  UserName:    aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete access key %v. Here's why: %v\n", keyId, err)
 }
 return err
}



// ListAccessKeys lists the access keys for the specified user.
func (wrapper UserWrapper) ListAccessKeys(userName string)
 ([]types.AccessKeyMetadata, error) {
 var keys []types.AccessKeyMetadata
 result, err := wrapper.IamClient.ListAccessKeys(context.TODO(),
 &iam.ListAccessKeysInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list access keys for user %v. Here's why: %v\n", userName,
 err)
 } else {
  keys = result.AccessKeyMetadata
 }
 return keys, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy

- CreateRole
- CreateUser
- DeleteAccessKey
- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
/*
  To run this Java V2 code example, set up your development environment,
 including your credentials.

  For information, see this documentation topic:

  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html

  This example performs these operations:

  1. Creates a user that has no permissions.
  2. Creates a role and policy that grants Amazon S3 permissions.
  3. Creates a role.
  4. Grants the user permissions.
```

```
  5. Gets temporary credentials by assuming the role.  Creates an Amazon S3
 Service client object with the temporary credentials.
  6. Deletes the resources.
 */

public class IAMScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");
    public static final String PolicyDocument = "{" +
            "  \"Version\": \"2012-10-17\"," +
            "  \"Statement\": [" +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Action\": [" +
            "            \"s3:*\"" +
            "       ]," +
            "       \"Resource\": \"*\"" +
            "    }" +
            "   ]" +
            "}";

    public static String userArn;

    public static void main(String[] args) throws Exception {

        final String usage = """

                Usage:
                    <username> <policyName> <roleName> <roleSessionName>
 <bucketName>\s

                Where:
                    username - The name of the IAM user to create.\s
                    policyName - The name of the policy to create.\s
                    roleName - The name of the role to create.\s
                    roleSessionName - The name of the session required for the
 assumeRole operation.\s
                    bucketName - The name of the Amazon S3 bucket from which
 objects are read.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String userName = args[0];
        String policyName = args[1];
        String roleName = args[2];
        String roleSessionName = args[3];
        String bucketName = args[4];

        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS IAM example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 1. Create the IAM user.");
        User createUser = createIAMUser(iam, userName);

        System.out.println(DASHES);
        userArn = createUser.arn();

        AccessKey myKey = createIAMAccessKey(iam, userName);
        String accessKey = myKey.accessKeyId();
        String secretKey = myKey.secretAccessKey();
        String assumeRolePolicyDocument = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                " \"AWS\": \"" + userArn + "\"" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        System.out.println(assumeRolePolicyDocument);
        System.out.println(userName + " was successfully created.");
        System.out.println(DASHES);
        System.out.println("2. Creates a policy.");
        String polArn = createIAMPolicy(iam, policyName);
```

```
        System.out.println("The policy " + polArn + " was successfully
created.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Creates a role.");
        TimeUnit.SECONDS.sleep(30);
        String roleArn = createIAMRole(iam, roleName, assumeRolePolicyDocument);
        System.out.println(roleArn + " was successfully created.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Grants the user permissions.");
        attachIAMRolePolicy(iam, roleName, polArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Wait for 30 secs so the resource is available");
        TimeUnit.SECONDS.sleep(30);
        System.out.println("5. Gets temporary credentials by assuming the
role.");
        System.out.println("Perform an Amazon S3 Service operation using the
temporary credentials.");
        assumeRole(roleArn, roleSessionName, bucketName, accessKey, secretKey);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6 Getting ready to delete the AWS resources");
        deleteKey(iam, userName, accessKey);
        deleteRole(iam, roleName, polArn);
        deleteIAMUser(iam, userName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("This IAM Scenario has successfully completed");
        System.out.println(DASHES);
    }

    public static AccessKey createIAMAccessKey(IamClient iam, String user) {
        try {
            CreateAccessKeyRequest request = CreateAccessKeyRequest.builder()
                    .userName(user)
                    .build();
```

```
            CreateAccessKeyResponse response = iam.createAccessKey(request);
            return response.accessKey();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static User createIAMUser(IamClient iam, String username) {
        try {
            // Create an IamWaiter object
            IamWaiter iamWaiter = iam.waiter();
            CreateUserRequest request = CreateUserRequest.builder()
                    .userName(username)
                    .build();

            // Wait until the user is created.
            CreateUserResponse response = iam.createUser(request);
            GetUserRequest userRequest = GetUserRequest.builder()
                    .userName(response.user().userName())
                    .build();

            WaiterResponse<GetUserResponse> waitUntilUserExists =
iamWaiter.waitUntilUserExists(userRequest);

waitUntilUserExists.matched().response().ifPresent(System.out::println);
            return response.user();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static String createIAMRole(IamClient iam, String rolename, String
json) {

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(json)
```

```
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            System.out.println("The ARN of the role is " +
response.role().arn());
            return response.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createIAMPolicy(IamClient iam, String policyName) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();
            CreatePolicyRequest request = CreatePolicyRequest.builder()
                    .policyName(policyName)
                    .policyDocument(PolicyDocument).build();

            CreatePolicyResponse response = iam.createPolicy(request);
            GetPolicyRequest polRequest = GetPolicyRequest.builder()
                    .policyArn(response.policy().arn())
                    .build();

            WaiterResponse<GetPolicyResponse> waitUntilPolicyExists =
iamWaiter.waitUntilPolicyExists(polRequest);

waitUntilPolicyExists.matched().response().ifPresent(System.out::println);
            return response.policy().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void attachIAMRolePolicy(IamClient iam, String roleName, String
policyArn) {
        try {
```

```
            ListAttachedRolePoliciesRequest request =
ListAttachedRolePoliciesRequest.builder()
                    .roleName(roleName)
                    .build();

            ListAttachedRolePoliciesResponse response =
iam.listAttachedRolePolicies(request);
            List<AttachedPolicy> attachedPolicies = response.attachedPolicies();
            String polArn;
            for (AttachedPolicy policy : attachedPolicies) {
                polArn = policy.policyArn();
                if (polArn.compareTo(policyArn) == 0) {
                    System.out.println(roleName + " policy is already attached to
this role.");
                    return;
                }
            }

            AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.attachRolePolicy(attachRequest);
            System.out.println("Successfully attached policy " + policyArn + " to
role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Invoke an Amazon S3 operation using the Assumed Role.
    public static void assumeRole(String roleArn, String roleSessionName, String
bucketName, String keyVal,
            String keySecret) {

        // Use the creds of the new IAM user that was created in this code
example.
        AwsBasicCredentials credentials = AwsBasicCredentials.create(keyVal,
keySecret);
        StsClient stsClient = StsClient.builder()
```

```
                .region(Region.US_EAST_1)

.credentialsProvider(StaticCredentialsProvider.create(credentials))
                .build();

        try {
            AssumeRoleRequest roleRequest = AssumeRoleRequest.builder()
                    .roleArn(roleArn)
                    .roleSessionName(roleSessionName)
                    .build();

            AssumeRoleResponse roleResponse = stsClient.assumeRole(roleRequest);
            Credentials myCreds = roleResponse.credentials();
            String key = myCreds.accessKeyId();
            String secKey = myCreds.secretAccessKey();
            String secToken = myCreds.sessionToken();

            // List all objects in an Amazon S3 bucket using the temp creds
retrieved by
            // invoking assumeRole.
            Region region = Region.US_EAST_1;
            S3Client s3 = S3Client.builder()
                    .credentialsProvider(

StaticCredentialsProvider.create(AwsSessionCredentials.create(key, secKey,
secToken)))
                    .region(region)
                    .build();

            System.out.println("Created a S3Client using temp credentials.");
            System.out.println("Listing objects in " + bucketName);
            ListObjectsRequest listObjects = ListObjectsRequest.builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.println("The name of the key is " + myValue.key());
                System.out.println("The owner is " + myValue.owner());
            }

        } catch (StsException e) {
            System.err.println(e.getMessage());
```

```
            System.exit(1);
        }
    }

    public static void deleteRole(IamClient iam, String roleName, String polArn)
{

        try {
            // First the policy needs to be detached.
            DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
                    .policyArn(polArn)
                    .roleName(roleName)
                    .build();

            iam.detachRolePolicy(rolePolicyRequest);

            // Delete the policy.
            DeletePolicyRequest request = DeletePolicyRequest.builder()
                    .policyArn(polArn)
                    .build();

            iam.deletePolicy(request);
            System.out.println("*** Successfully deleted " + polArn);

            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteKey(IamClient iam, String username, String
accessKey) {
        try {
            DeleteAccessKeyRequest request = DeleteAccessKeyRequest.builder()
                    .accessKeyId(accessKey)
```

```
                    .userName(username)
                    .build();

            iam.deleteAccessKey(request);
            System.out.println("Successfully deleted access key " + accessKey +
                    " from user " + username);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteIAMUser(IamClient iam, String userName) {
        try {
            DeleteUserRequest request = DeleteUserRequest.builder()
                    .userName(userName)
                    .build();

            iam.deleteUser(request);
            System.out.println("*** Successfully deleted " + userName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole

- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
import {
  CreateUserCommand,
  CreateAccessKeyCommand,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  DeleteAccessKeyCommand,
  DeleteUserCommand,
  DeleteRoleCommand,
  DeletePolicyCommand,
  DetachRolePolicyCommand,
  IAMClient,
} from "@aws-sdk/client-iam";
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";
import { AssumeRoleCommand, STSClient } from "@aws-sdk/client-sts";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

// Set the parameters.
const iamClient = new IAMClient({});
const userName = "test_name";
const policyName = "test_policy";
```

```
const roleName = "test_role";

export const main = async () => {
  // Create a user. The user has no permissions by default.
  const { User } = await iamClient.send(
    new CreateUserCommand({ UserName: userName }),
  );

  if (!User) {
    throw new Error("User not created");
  }

  // Create an access key. This key is used to authenticate the new user to
  // Amazon Simple Storage Service (Amazon S3) and AWS Security Token Service
 (AWS STS).
  // It's not best practice to use access keys. For more information, see
 https://aws.amazon.com/iam/resources/best-practices/.
  const createAccessKeyResponse = await iamClient.send(
    new CreateAccessKeyCommand({ UserName: userName }),
  );

  if (
    !createAccessKeyResponse.AccessKey?.AccessKeyId ||
    !createAccessKeyResponse.AccessKey?.SecretAccessKey
  ) {
    throw new Error("Access key not created");
  }

  const {
    AccessKey: { AccessKeyId, SecretAccessKey },
  } = createAccessKeyResponse;

  let s3Client = new S3Client({
    credentials: {
      accessKeyId: AccessKeyId,
      secretAccessKey: SecretAccessKey,
    },
  });

  // Retry the list buckets operation until it succeeds. InvalidAccessKeyId is
  // thrown while the user and access keys are still stabilizing.
  await retry({ intervalInMs: 1000, maxRetries: 300 }, async () => {
    try {
      return await listBuckets(s3Client);
```

```
    } catch (err) {
      if (err instanceof Error && err.name === "InvalidAccessKeyId") {
        throw err;
      }
    }
  });

  // Retry the create role operation until it succeeds. A MalformedPolicyDocument
 error
  // is thrown while the user and access keys are still stabilizing.
  const { Role } = await retry(
    {
      intervalInMs: 2000,
      maxRetries: 60,
    },
    () =>
      iamClient.send(
        new CreateRoleCommand({
          AssumeRolePolicyDocument: JSON.stringify({
            Version: "2012-10-17",
            Statement: [
              {
                Effect: "Allow",
                Principal: {
                  // Allow the previously created user to assume this role.
                  AWS: User.Arn,
                },
                Action: "sts:AssumeRole",
              },
            ],
          }),
          RoleName: roleName,
        }),
      ),
  );

  if (!Role) {
    throw new Error("Role not created");
  }

  // Create a policy that allows the user to list S3 buckets.
  const { Policy: listBucketPolicy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyDocument: JSON.stringify({
```

```
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Action: ["s3:ListAllMyBuckets"],
            Resource: "*",
          },
        ],
      }),
      PolicyName: policyName,
    }),
  );

  if (!listBucketPolicy) {
    throw new Error("Policy not created");
  }

  // Attach the policy granting the 's3:ListAllMyBuckets' action to the role.
  await iamClient.send(
    new AttachRolePolicyCommand({
      PolicyArn: listBucketPolicy.Arn,
      RoleName: Role.RoleName,
    }),
  );

  // Assume the role.
  const stsClient = new STSClient({
    credentials: {
      accessKeyId: AccessKeyId,
      secretAccessKey: SecretAccessKey,
    },
  });

  // Retry the assume role operation until it succeeds.
  const { Credentials } = await retry(
    { intervalInMs: 2000, maxRetries: 60 },
    () =>
      stsClient.send(
        new AssumeRoleCommand({
          RoleArn: Role.Arn,
          RoleSessionName: `iamBasicScenarioSession-${Math.floor(
            Math.random() * 1000000,
          )}`,
          DurationSeconds: 900,
```

```
      }),
    ),
);

if (!Credentials?.AccessKeyId || !Credentials?.SecretAccessKey) {
  throw new Error("Credentials not created");
}

s3Client = new S3Client({
  credentials: {
    accessKeyId: Credentials.AccessKeyId,
    secretAccessKey: Credentials.SecretAccessKey,
    sessionToken: Credentials.SessionToken,
  },
});

// List the S3 buckets again.
// Retry the list buckets operation until it succeeds. AccessDenied might
// be thrown while the role policy is still stabilizing.
await retry({ intervalInMs: 2000, maxRetries: 60 }, () =>
  listBuckets(s3Client),
);

// Clean up.
await iamClient.send(
  new DetachRolePolicyCommand({
    PolicyArn: listBucketPolicy.Arn,
    RoleName: Role.RoleName,
  }),
);

await iamClient.send(
  new DeletePolicyCommand({
    PolicyArn: listBucketPolicy.Arn,
  }),
);

await iamClient.send(
  new DeleteRoleCommand({
    RoleName: Role.RoleName,
  }),
);

await iamClient.send(
```

```
    new DeleteAccessKeyCommand({
      UserName: userName,
      AccessKeyId,
    }),
  );

  await iamClient.send(
    new DeleteUserCommand({
      UserName: userName,
    }),
  );
};

/**
 *
 * @param {S3Client} s3Client
 */
const listBuckets = async (s3Client) => {
  const { Buckets } = await s3Client.send(new ListBucketsCommand({}));

  if (!Buckets) {
    throw new Error("Buckets not listed");
  }

  console.log(Buckets.map((bucket) => bucket.Name).join("\n"));
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole

- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
suspend fun main(args: Array<String>) {

    val usage = """
    Usage:
        <username> <policyName> <roleName> <roleSessionName> <fileLocation>
 <bucketName>

    Where:
        username - The name of the IAM user to create.
        policyName - The name of the policy to create.
        roleName - The name of the role to create.
        roleSessionName - The name of the session required for the assumeRole
 operation.
        fileLocation - The file location to the JSON required to create the role
 (see Readme).
        bucketName - The name of the Amazon S3 bucket from which objects are
 read.
    """

    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }
```

```
    val userName = args[0]
    val policyName = args[1]
    val roleName = args[2]
    val roleSessionName = args[3]
    val fileLocation = args[4]
    val bucketName = args[5]

    createUser(userName)
    println("$userName was successfully created.")

    val polArn = createPolicy(policyName)
    println("The policy $polArn was successfully created.")

    val roleArn = createRole(roleName, fileLocation)
    println("$roleArn was successfully created.")
    attachRolePolicy(roleName, polArn)

    println("*** Wait for 1 MIN so the resource is available.")
    delay(60000)
    assumeGivenRole(roleArn, roleSessionName, bucketName)

    println("*** Getting ready to delete the AWS resources.")
    deleteRole(roleName, polArn)
    deleteUser(userName)
    println("This IAM Scenario has successfully completed.")
}

suspend fun createUser(usernameVal: String?): String? {

    val request = CreateUserRequest {
        userName = usernameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createUser(request)
        return response.user?.userName
    }
}

suspend fun createPolicy(policyNameVal: String?): String {

    val policyDocumentValue: String = "{" +
        "  \"Version\": \"2012-10-17\"," +
```

```
        "  \"Statement\": [" +
        "    {" +
        "        \"Effect\": \"Allow\"," +
        "        \"Action\": [" +
        "            \"s3:*\"" +
        "       ]," +
        "       \"Resource\": \"*\"" +
        "    }" +
        "   ]" +
        "}"

    val request = CreatePolicyRequest {
        policyName = policyNameVal
        policyDocument = policyDocumentValue
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createPolicy(request)
        return response.policy?.arn.toString()
    }
}

suspend fun createRole(rolenameVal: String?, fileLocation: String?): String? {

    val jsonObject = fileLocation?.let { readJsonSimpleDemo(it) } as JSONObject

    val request = CreateRoleRequest {
        roleName = rolenameVal
        assumeRolePolicyDocument = jsonObject.toJSONString()
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createRole(request)
        return response.role?.arn
    }
}

suspend fun attachRolePolicy(roleNameVal: String, policyArnVal: String) {

    val request = ListAttachedRolePoliciesRequest {
        roleName = roleNameVal
    }
```

```
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAttachedRolePolicies(request)
        val attachedPolicies = response.attachedPolicies

        // Ensure that the policy is not attached to this role.
        val checkStatus: Int
        if (attachedPolicies != null) {
            checkStatus = checkMyList(attachedPolicies, policyArnVal)
            if (checkStatus == -1)
                return
        }

        val policyRequest = AttachRolePolicyRequest {
            roleName = roleNameVal
            policyArn = policyArnVal
        }
        iamClient.attachRolePolicy(policyRequest)
        println("Successfully attached policy $policyArnVal to role
 $roleNameVal")
    }
}

fun checkMyList(attachedPolicies: List<AttachedPolicy>, policyArnVal: String):
 Int {

    for (policy in attachedPolicies) {
        val polArn = policy.policyArn.toString()

        if (polArn.compareTo(policyArnVal) == 0) {
            println("The policy is already attached to this role.")
            return -1
        }
    }
    return 0
}

suspend fun assumeGivenRole(roleArnVal: String?, roleSessionNameVal: String?,
 bucketName: String) {

    val stsClient = StsClient {
        region = "us-east-1"
    }

    val roleRequest = AssumeRoleRequest {
```

```
        roleArn = roleArnVal
        roleSessionName = roleSessionNameVal
    }

    val roleResponse = stsClient.assumeRole(roleRequest)
    val myCreds = roleResponse.credentials
    val key = myCreds?.accessKeyId
    val secKey = myCreds?.secretAccessKey
    val secToken = myCreds?.sessionToken

    val staticCredentials = StaticCredentialsProvider {
        accessKeyId = key
        secretAccessKey = secKey
        sessionToken = secToken
    }

    // List all objects in an Amazon S3 bucket using the temp creds.
    val s3 = S3Client {
        credentialsProvider = staticCredentials
        region = "us-east-1"
    }

    println("Created a S3Client using temp credentials.")
    println("Listing objects in $bucketName")

    val listObjects = ListObjectsRequest {
        bucket = bucketName
    }

    val response = s3.listObjects(listObjects)
    response.contents?.forEach { myObject ->
        println("The name of the key is ${myObject.key}")
        println("The owner is ${myObject.owner}")
    }
}

suspend fun deleteRole(roleNameVal: String, polArn: String) {

    val iam = IamClient { region = "AWS_GLOBAL" }

    // First the policy needs to be detached.
    val rolePolicyRequest = DetachRolePolicyRequest {
        policyArn = polArn
        roleName = roleNameVal
```

```
    }

    iam.detachRolePolicy(rolePolicyRequest)

    // Delete the policy.
    val request = DeletePolicyRequest {
        policyArn = polArn
    }

    iam.deletePolicy(request)
    println("*** Successfully deleted $polArn")

    // Delete the role.
    val roleRequest = DeleteRoleRequest {
        roleName = roleNameVal
    }

    iam.deleteRole(roleRequest)
    println("*** Successfully deleted $roleNameVal")
}

suspend fun deleteUser(userNameVal: String) {
    val iam = IamClient { region = "AWS_GLOBAL" }
    val request = DeleteUserRequest {
        userName = userNameVal
    }

    iam.deleteUser(request)
    println("*** Successfully deleted $userNameVal")
}

@Throws(java.lang.Exception::class)
fun readJsonSimpleDemo(filename: String): Any? {
    val reader = FileReader(filename)
    val jsonParser = JSONParser()
    return jsonParser.parse(reader)
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AttachRolePolicy

- CreateAccessKey
- CreatePolicy
- CreateRole
- CreateUser
- DeleteAccessKey
- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Iam\Basics;

require 'vendor/autoload.php';

use Aws\Credentials\Credentials;
use Aws\S3\Exception\S3Exception;
use Aws\S3\S3Client;
use Aws\Sts\StsClient;
use Iam\IAMService;

echo("\n");
echo("--------------------------------------\n");
print("Welcome to the IAM getting started demo using PHP!\n");
echo("--------------------------------------\n");
```

```
$uuid = uniqid();
$service = new IAMService();

$user = $service->createUser("iam_demo_user_$uuid");
echo "Created user with the arn: {$user['Arn']}\n";

$key = $service->createAccessKey($user['UserName']);
$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
echo "Created role: {$assumeRoleRole['RoleName']}\n";

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";

$service->attachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);

$inlinePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"{$assumeRoleRole['Arn']}\"}]
}";
$inlinePolicy = $service->createUserPolicy("iam_demo_inline_policy_$uuid",
 $inlinePolicyDocument, $user['UserName']);
//First, fail to list the buckets with the user
$credentials = new Credentials($key['AccessKeyId'], $key['SecretAccessKey']);
```

```
$s3Client = new S3Client(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $credentials]);
try {
    $s3Client->listBuckets([
    ]);
    echo "this should not run";
} catch (S3Exception $exception) {
    echo "successfully failed!\n";
}

$stsClient = new StsClient(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $credentials]);
sleep(10);
$assumedRole = $stsClient->assumeRole([
    'RoleArn' => $assumeRoleRole['Arn'],
    'RoleSessionName' => "DemoAssumeRoleSession_$uuid",
]);
$assumedCredentials = [
    'key' => $assumedRole['Credentials']['AccessKeyId'],
    'secret' => $assumedRole['Credentials']['SecretAccessKey'],
    'token' => $assumedRole['Credentials']['SessionToken'],
];
$s3Client = new S3Client(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $assumedCredentials]);
try {
    $s3Client->listBuckets([]);
    echo "this should now run!\n";
} catch (S3Exception $exception) {
    echo "this should now not fail\n";
}

$service->detachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);
$deletePolicy = $service->deletePolicy($listAllBucketsPolicy['Arn']);
echo "Delete policy: {$listAllBucketsPolicy['PolicyName']}\n";
$deletedRole = $service->deleteRole($assumeRoleRole['Arn']);
echo "Deleted role: {$assumeRoleRole['RoleName']}\n";
$deletedKey = $service->deleteAccessKey($key['AccessKeyId'], $user['UserName']);
$deletedUser = $service->deleteUser($user['UserName']);
echo "Delete user: {$user['UserName']}\n";
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
import json
import sys
import time
from uuid import uuid4

import boto3
from botocore.exceptions import ClientError
```

```
def progress_bar(seconds):
    """Shows a simple progress bar in the command window."""
    for _ in range(seconds):
        time.sleep(1)
        print(".", end="")
        sys.stdout.flush()
    print()


def setup(iam_resource):
    """
    Creates a new user with no permissions.
    Creates an access key pair for the user.
    Creates a role with a policy that lets the user assume the role.
    Creates a policy that allows listing Amazon S3 buckets.
    Attaches the policy to the role.
    Creates an inline policy for the user that lets the user assume the role.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM)
 resource
                         that has permissions to create users, roles, and
 policies
                         in the account.
    :return: The newly created user, user key, and role.
    """
    try:
        user = iam_resource.create_user(UserName=f"demo-user-{uuid4()}")
        print(f"Created user {user.name}.")
    except ClientError as error:
        print(
            f"Couldn't create a user for the demo. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        user_key = user.create_access_key_pair()
        print(f"Created access key pair for user.")
    except ClientError as error:
        print(
            f"Couldn't create access keys for user {user.name}. Here's why: "
            f"{error.response['Error']['Message']}"
```

```
        )
        raise

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    try:
        role = iam_resource.create_role(
            RoleName=f"demo-role-{uuid4()}",
            AssumeRolePolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Principal": {"AWS": user.arn},
                            "Action": "sts:AssumeRole",
                        }
                    ],
                }
            ),
        )
        print(f"Created role {role.name}.")
    except ClientError as error:
        print(
            f"Couldn't create a role for the demo. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        policy = iam_resource.create_policy(
            PolicyName=f"demo-policy-{uuid4()}",
            PolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Action": "s3:ListAllMyBuckets",
                            "Resource": "arn:aws:s3:::*",
                        }
                    ],
                }
```

```
            ),
        )
        role.attach_policy(PolicyArn=policy.arn)
        print(f"Created policy {policy.policy_name} and attached it to the
role.")
    except ClientError as error:
        print(
            f"Couldn't create a policy and attach it to role {role.name}. Here's
why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        user.create_policy(
            PolicyName=f"demo-user-policy-{uuid4()}",
            PolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Action": "sts:AssumeRole",
                            "Resource": role.arn,
                        }
                    ],
                }
            ),
        )
        print(
            f"Created an inline policy for {user.name} that lets the user assume
"
            f"the role."
        )
    except ClientError as error:
        print(
            f"Couldn't create an inline policy for user {user.name}. Here's why:
"
            f"{error.response['Error']['Message']}"
        )
        raise

    print("Give AWS time to propagate these new resources and connections.",
end="")
```

```
    progress_bar(10)

    return user, user_key, role


def show_access_denied_without_role(user_key):
    """
    Shows that listing buckets without first assuming the role is not allowed.

    :param user_key: The key of the user created during setup. This user does not
                     have permission to list buckets in the account.
    """
    print(f"Try to list buckets without first assuming the role.")
    s3_denied_resource = boto3.resource(
        "s3", aws_access_key_id=user_key.id,
 aws_secret_access_key=user_key.secret
    )
    try:
        for bucket in s3_denied_resource.buckets.all():
            print(bucket.name)
        raise RuntimeError("Expected to get AccessDenied error when listing
 buckets!")
    except ClientError as error:
        if error.response["Error"]["Code"] == "AccessDenied":
            print("Attempt to list buckets with no permissions: AccessDenied.")
        else:
            raise


def list_buckets_from_assumed_role(user_key, assume_role_arn, session_name):
    """
    Assumes a role that grants permission to list the Amazon S3 buckets in the
 account.
    Uses the temporary credentials from the role to list the buckets that are
 owned
    by the assumed role's account.

    :param user_key: The access key of a user that has permission to assume the
 role.
    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    """
    sts_client = boto3.client(
```

```
        "sts", aws_access_key_id=user_key.id,
 aws_secret_access_key=user_key.secret
    )
    try:
        response = sts_client.assume_role(
            RoleArn=assume_role_arn, RoleSessionName=session_name
        )
        temp_credentials = response["Credentials"]
        print(f"Assumed role {assume_role_arn} and got temporary credentials.")
    except ClientError as error:
        print(
            f"Couldn't assume role {assume_role_arn}. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    # Create an S3 resource that can access the account with the temporary
 credentials.
    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )
    print(f"Listing buckets for the assumed role's account:")
    try:
        for bucket in s3_resource.buckets.all():
            print(bucket.name)
    except ClientError as error:
        print(
            f"Couldn't list buckets for the account. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise




def teardown(user, role):
    """
    Removes all resources created during setup.

    :param user: The demo user.
    :param role: The demo role.
```

```
    """
    try:
        for attached in role.attached_policies.all():
            policy_name = attached.policy_name
            role.detach_policy(PolicyArn=attached.arn)
            attached.delete()
            print(f"Detached and deleted {policy_name}.")
        role.delete()
        print(f"Deleted {role.name}.")
    except ClientError as error:
        print(
            "Couldn't detach policy, delete policy, or delete role. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        for user_pol in user.policies.all():
            user_pol.delete()
            print("Deleted inline user policy.")
        for key in user.access_keys.all():
            key.delete()
            print("Deleted user's access key.")
        user.delete()
        print(f"Deleted {user.name}.")
    except ClientError as error:
        print(
            "Couldn't delete user policy or delete user. Here's why: "
            f"{error.response['Error']['Message']}"
        )


def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(f"Welcome to the IAM create user and assume role demo.")
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    user = None
    role = None
    try:
        user, user_key, role = setup(iam_resource)
        print(f"Created {user.name} and {role.name}.")
        show_access_denied_without_role(user_key)
```

```
        list_buckets_from_assumed_role(user_key, role.arn,
 "AssumeRoleDemoSession")
    except Exception:
        print("Something went wrong!")
    finally:
        if user is not None and role is not None:
            teardown(user, role)
        print("Thanks for watching!")


if __name__ == "__main__":
    usage_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
# Wraps the scenario actions.
class ScenarioCreateUserAssumeRole
  attr_reader :iam_client

  # @param [Aws::IAM::Client] iam_client: The AWS IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Waits for the specified number of seconds.
  #
  # @param duration [Integer] The number of seconds to wait.
  def wait(duration)
    puts("Give AWS time to propagate resources...")
    sleep(duration)
  end

  # Creates a user.
  #
  # @param user_name [String] The name to give the user.
  # @return [Aws::IAM::User] The newly created user.
  def create_user(user_name)
    user = @iam_client.create_user(user_name: user_name).user
    @logger.info("Created demo user named #{user.user_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Tried and failed to create demo user.")
    @logger.info("\t#{e.code}: #{e.message}")
```

```
    @logger.info("\nCan't continue the demo without a user!")
    raise
  else
    user
  end

  # Creates an access key for a user.
  #
  # @param user [Aws::IAM::User] The user that owns the key.
  # @return [Aws::IAM::AccessKeyPair] The newly created access key.
  def create_access_key_pair(user)
    user_key = @iam_client.create_access_key(user_name:
user.user_name).access_key
    @logger.info("Created accesskey pair for user #{user.user_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't create access keys for user #{user.user_name}.")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  else
    user_key
  end

  # Creates a role that can be assumed by a user.
  #
  # @param role_name [String] The name to give the role.
  # @param user [Aws::IAM::User] The user who is granted permission to assume the
role.
  # @return [Aws::IAM::Role] The newly created role.
  def create_role(role_name, user)
    trust_policy = {
      Version: "2012-10-17",
      Statement: [{
                    Effect: "Allow",
                    Principal: {'AWS': user.arn},
                    Action: "sts:AssumeRole"
                  }]
    }.to_json
    role = @iam_client.create_role(
      role_name: role_name,
      assume_role_policy_document: trust_policy
    ).role
    @logger.info("Created role #{role.role_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't create a role for the demo. Here's why: ")
```

```
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  else
    role
  end

  # Creates a policy that grants permission to list S3 buckets in the account,
and
  # then attaches the policy to a role.
  #
  # @param policy_name [String] The name to give the policy.
  # @param role [Aws::IAM::Role] The role that the policy is attached to.
  # @return [Aws::IAM::Policy] The newly created policy.
  def create_and_attach_role_policy(policy_name, role)
    policy_document = {
      Version: "2012-10-17",
      Statement: [{
                    Effect: "Allow",
                    Action: "s3:ListAllMyBuckets",
                    Resource: "arn:aws:s3:::*"
                  }]
    }.to_json
    policy = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document
    ).policy
    @iam_client.attach_role_policy(
      role_name: role.role_name,
      policy_arn: policy.arn
    )
    @logger.info("Created policy #{policy.policy_name} and attached it to role
#{role.role_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't create a policy and attach it to role
#{role.role_name}. Here's why: ")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  end

  # Creates an inline policy for a user that lets the user assume a role.
  #
  # @param policy_name [String] The name to give the policy.
  # @param user [Aws::IAM::User] The user that owns the policy.
  # @param role [Aws::IAM::Role] The role that can be assumed.
```

```
 # @return [Aws::IAM::UserPolicy] The newly created policy.
 def create_user_policy(policy_name, user, role)
   policy_document = {
     Version: "2012-10-17",
     Statement: [{
                   Effect: "Allow",
                   Action: "sts:AssumeRole",
                   Resource: role.arn
                 }]
   }.to_json
   @iam_client.put_user_policy(
     user_name: user.user_name,
     policy_name: policy_name,
     policy_document: policy_document
   )
   puts("Created an inline policy for #{user.user_name} that lets the user
assume role #{role.role_name}.")
 rescue Aws::Errors::ServiceError => e
   @logger.info("Couldn't create an inline policy for user #{user.user_name}.
Here's why: ")
   @logger.info("\t#{e.code}: #{e.message}")
   raise
 end

 # Creates an Amazon S3 resource with specified credentials. This is separated
into a
 # factory function so that it can be mocked for unit testing.
 #
 # @param credentials [Aws::Credentials] The credentials used by the Amazon S3
resource.
 def create_s3_resource(credentials)
   Aws::S3::Resource.new(client: Aws::S3::Client.new(credentials: credentials))
 end

 # Lists the S3 buckets for the account, using the specified Amazon S3 resource.
 # Because the resource uses credentials with limited access, it may not be able
to
 # list the S3 buckets.
 #
 # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
 def list_buckets(s3_resource)
   count = 10
   s3_resource.buckets.each do |bucket|
     @logger.info "\t#{bucket.name}"
```

```
      count -= 1
      break if count.zero?
    end
  rescue Aws::Errors::ServiceError => e
    if e.code == "AccessDenied"
      puts("Attempt to list buckets with no permissions: AccessDenied.")
    else
      @logger.info("Couldn't list buckets for the account. Here's why: ")
      @logger.info("\t#{e.code}: #{e.message}")
      raise
    end
  end

  # Creates an AWS Security Token Service (AWS STS) client with specified
credentials.
  # This is separated into a factory function so that it can be mocked for unit
testing.
  #
  # @param key_id [String] The ID of the access key used by the STS client.
  # @param key_secret [String] The secret part of the access key used by the STS
client.
  def create_sts_client(key_id, key_secret)
    Aws::STS::Client.new(access_key_id: key_id, secret_access_key: key_secret)
  end

  # Gets temporary credentials that can be used to assume a role.
  #
  # @param role_arn [String] The ARN of the role that is assumed when these
credentials
  #                          are used.
  # @param sts_client [AWS::STS::Client] An AWS STS client.
  # @return [Aws::AssumeRoleCredentials] The credentials that can be used to
assume the role.
  def assume_role(role_arn, sts_client)
    credentials = Aws::AssumeRoleCredentials.new(
      client: sts_client,
      role_arn: role_arn,
      role_session_name: "create-use-assume-role-scenario"
    )
    @logger.info("Assumed role '#{role_arn}', got temporary credentials.")
    credentials
  end

  # Deletes a role. If the role has policies attached, they are detached and
```

```
  # deleted before the role is deleted.
  #
  # @param role_name [String] The name of the role to delete.
  def delete_role(role_name)
    @iam_client.list_attached_role_policies(role_name:
 role_name).attached_policies.each do |policy|
      @iam_client.detach_role_policy(role_name: role_name, policy_arn:
 policy.policy_arn)
      @iam_client.delete_policy(policy_arn: policy.policy_arn)
      @logger.info("Detached and deleted policy #{policy.policy_name}.")
    end
    @iam_client.delete_role({ role_name: role_name })
    @logger.info("Role deleted: #{role_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't detach policies and delete role #{role.name}. Here's
 why:")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  end

  # Deletes a user. If the user has inline policies or access keys, they are
 deleted
  # before the user is deleted.
  #
  # @param user [Aws::IAM::User] The user to delete.
  def delete_user(user_name)
    user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
    user.each do |key|
      @iam_client.delete_access_key({ access_key_id: key.access_key_id,
 user_name: user_name })
      @logger.info("Deleted access key #{key.access_key_id} for user
 '#{user_name}'.")
    end

    @iam_client.delete_user(user_name: user_name)
    @logger.info("Deleted user '#{user_name}'.")
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting user '#{user_name}': #{e.message}")
  end
end

# Runs the IAM create a user and assume a role scenario.
def run_scenario(scenario)
  puts("-" * 88)
```

```
  puts("Welcome to the IAM create a user and assume a role demo!")
  puts("-" * 88)
  user = scenario.create_user("doc-example-user-#{Random.uuid}")
  user_key = scenario.create_access_key_pair(user)
  scenario.wait(10)
  role = scenario.create_role("doc-example-role-#{Random.uuid}", user)
  scenario.create_and_attach_role_policy("doc-example-role-policy-
#{Random.uuid}", role)
  scenario.create_user_policy("doc-example-user-policy-#{Random.uuid}", user,
 role)
  scenario.wait(10)
  puts("Try to list buckets with credentials for a user who has no permissions.")
  puts("Expect AccessDenied from this call.")
  scenario.list_buckets(
    scenario.create_s3_resource(Aws::Credentials.new(user_key.access_key_id,
 user_key.secret_access_key)))
  puts("Now, assume the role that grants permission.")
  temp_credentials = scenario.assume_role(
    role.arn, scenario.create_sts_client(user_key.access_key_id,
 user_key.secret_access_key))
  puts("Here are your buckets:")
  scenario.list_buckets(scenario.create_s3_resource(temp_credentials))
  puts("Deleting role '#{role.role_name}' and attached policies.")
  scenario.delete_role(role.role_name)
  puts("Deleting user '#{user.user_name}', policies, and keys.")
  scenario.delete_user(user.user_name)
  puts("Thanks for watching!")
  puts("-" * 88)
rescue Aws::Errors::ServiceError => e
  puts("Something went wrong with the demo.")
  puts("\t#{e.code}: #{e.message}")
end

run_scenario(ScenarioCreateUserAssumeRole.new(Aws::IAM::Client.new)) if
 $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy

- CreateRole
- CreateUser
- DeleteAccessKey
- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
use aws_config::meta::region::RegionProviderChain;
use aws_sdk_iam::Error as iamError;
use aws_sdk_iam::{config::Credentials as iamCredentials, config::Region, Client
 as iamClient};
use aws_sdk_s3::Client as s3Client;
use aws_sdk_sts::Client as stsClient;
use tokio::time::{sleep, Duration};
use uuid::Uuid;

#[tokio::main]
async fn main() -> Result<(), iamError> {
    let (client, uuid, list_all_buckets_policy_document, inline_policy_document)
 =
        initialize_variables().await;

    if let Err(e) = run_iam_operations(
        client,
```

```
        uuid,
        list_all_buckets_policy_document,
        inline_policy_document,
    )
    .await
    {
        println!("{:?}", e);
    };

    Ok(())
}

async fn initialize_variables() -> (iamClient, String, String, String) {
    let region_provider = RegionProviderChain::first_try(Region::new("us-
west-2"));

    let shared_config =
 aws_config::from_env().region(region_provider).load().await;
    let client = iamClient::new(&shared_config);
    let uuid = Uuid::new_v4().to_string();

    let list_all_buckets_policy_document = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
    }"
    .to_string();
    let inline_policy_document = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"{}\"}]
    }"
    .to_string();

    (
        client,
        uuid,
        list_all_buckets_policy_document,
        inline_policy_document,
    )
```

```
}

async fn run_iam_operations(
    client: iamClient,
    uuid: String,
    list_all_buckets_policy_document: String,
    inline_policy_document: String,
) -> Result<(), iamError> {
    let user = iam_service::create_user(&client, &format!("{}{}",
 "iam_demo_user_", uuid)).await?;
    println!("Created the user with the name: {}", user.user_name());
    let key = iam_service::create_access_key(&client, user.user_name()).await?;

    let assume_role_policy_document = "{
        \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }"
    .to_string()
    .replace("{}", user.arn());

    let assume_role_role = iam_service::create_role(
        &client,
        &format!("{}{}", "iam_demo_role_", uuid),
        &assume_role_policy_document,
    )
    .await?;
    println!("Created the role with the ARN: {}", assume_role_role.arn());

    let list_all_buckets_policy = iam_service::create_policy(
        &client,
        &format!("{}{}", "iam_demo_policy_", uuid),
        &list_all_buckets_policy_document,
    )
    .await?;
    println!(
        "Created policy: {}",
        list_all_buckets_policy.policy_name.as_ref().unwrap()
    );

    let attach_role_policy_result =
```

```
        iam_service::attach_role_policy(&client, &assume_role_role,
&list_all_buckets_policy)
            .await?;
    println!(
        "Attached the policy to the role: {:?}",
        attach_role_policy_result
    );

    let inline_policy_name = format!("{}{}", "iam_demo_inline_policy_", uuid);
    let inline_policy_document = inline_policy_document.replace("{}",
assume_role_role.arn());
    iam_service::create_user_policy(&client, &user, &inline_policy_name,
&inline_policy_document)
        .await?;
    println!("Created inline policy.");

    //First, fail to list the buckets with the user.
    let creds = iamCredentials::from_keys(key.access_key_id(),
key.secret_access_key(), None);
    let fail_config = aws_config::from_env()
        .credentials_provider(creds.clone())
        .load()
        .await;
    println!("Fail config: {:?}", fail_config);
    let fail_client: s3Client = s3Client::new(&fail_config);
    match fail_client.list_buckets().send().await {
        Ok(e) => {
            println!("This should not run. {:?}", e);
        }
        Err(e) => {
            println!("Successfully failed with error: {:?}", e)
        }
    }

    let sts_config = aws_config::from_env()
        .credentials_provider(creds.clone())
        .load()
        .await;
    let sts_client: stsClient = stsClient::new(&sts_config);
    sleep(Duration::from_secs(10)).await;
    let assumed_role = sts_client
        .assume_role()
        .role_arn(assume_role_role.arn())
```

```
        .role_session_name(&format!("{}{}", "iam_demo_assumerole_session_",
uuid))
        .send()
        .await;
    println!("Assumed role: {:?}", assumed_role);
    sleep(Duration::from_secs(10)).await;

    let assumed_credentials = iamCredentials::from_keys(
        assumed_role
            .as_ref()
            .unwrap()
            .credentials
            .as_ref()
            .unwrap()
            .access_key_id(),
        assumed_role
            .as_ref()
            .unwrap()
            .credentials
            .as_ref()
            .unwrap()
            .secret_access_key(),
        Some(
            assumed_role
                .as_ref()
                .unwrap()
                .credentials
                .as_ref()
                .unwrap()
                .session_token
                .clone(),
        ),
    );

    let succeed_config = aws_config::from_env()
        .credentials_provider(assumed_credentials)
        .load()
        .await;
    println!("succeed config: {:?}", succeed_config);
    let succeed_client: s3Client = s3Client::new(&succeed_config);
    sleep(Duration::from_secs(10)).await;
    match succeed_client.list_buckets().send().await {
        Ok(_) => {
            println!("This should now run successfully.")
```

```
        }
        Err(e) => {
            println!("This should not run. {:?}", e);
            panic!()
        }
    }

    //Clean up.
    iam_service::detach_role_policy(
        &client,
        assume_role_role.role_name(),
        list_all_buckets_policy.arn().unwrap_or_default(),
    )
    .await?;
    iam_service::delete_policy(&client, list_all_buckets_policy).await?;
    iam_service::delete_role(&client, &assume_role_role).await?;
    println!("Deleted role {}", assume_role_role.role_name());
    iam_service::delete_access_key(&client, &user, &key).await?;
    println!("Deleted key for {}", key.user_name());
    iam_service::delete_user_policy(&client, &user, &inline_policy_name).await?;
    println!("Deleted inline user policy: {}", inline_policy_name);
    iam_service::delete_user(&client, &user).await?;
    println!("Deleted user {}", user.user_name());

    Ok(())
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser

- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Criar usuários do IAM somente leitura e leitura/gravação usando um AWS SDK

Os exemplos de código a seguir mostram como criar usuários e anexar políticas a eles.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar dois usuários IAM.
- Anexe uma política para um usuário obter e colocar objetos em um bucket do Amazon S3.
- Anexar uma política para o segundo usuário para obter objetos do bucket.
- Obter outras permissões para o bucket com base nas credenciais do usuário.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
import logging
import time

import boto3
from botocore.exceptions import ClientError
```

```
import access_key_wrapper
import policy_wrapper

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_user(user_name):
    """
    Creates a user. By default, a user has no permissions or access keys.

    :param user_name: The name of the user.
    :return: The newly created user.
    """
    try:
        user = iam.create_user(UserName=user_name)
        logger.info("Created user %s.", user.name)
    except ClientError:
        logger.exception("Couldn't create user %s.", user_name)
        raise
    else:
        return user



def update_user(user_name, new_user_name):
    """
    Updates a user's name.

    :param user_name: The current name of the user to update.
    :param new_user_name: The new name to assign to the user.
    :return: The updated user.
    """
    try:
        user = iam.User(user_name)
        user.update(NewUserName=new_user_name)
        logger.info("Renamed %s to %s.", user_name, new_user_name)
    except ClientError:
        logger.exception("Couldn't update name for user %s.", user_name)
        raise
    return user



def list_users():
```

```
    """
    Lists the users in the current account.

    :return: The list of users.
    """
    try:
        users = list(iam.users.all())
        logger.info("Got %s users.", len(users))
    except ClientError:
        logger.exception("Couldn't get users.")
        raise
    else:
        return users



def delete_user(user_name):
    """
    Deletes a user. Before a user can be deleted, all associated resources,
    such as access keys and policies, must be deleted or detached.

    :param user_name: The name of the user.
    """
    try:
        iam.User(user_name).delete()
        logger.info("Deleted user %s.", user_name)
    except ClientError:
        logger.exception("Couldn't delete user %s.", user_name)
        raise



def attach_policy(user_name, policy_arn):
    """
    Attaches a policy to a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to user %s.", policy_arn, user_name)
    except ClientError:
```

```
        logger.exception("Couldn't attach policy %s to user %s.", policy_arn,
 user_name)
        raise



def detach_policy(user_name, policy_arn):
    """
    Detaches a policy from a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from user %s.", policy_arn, user_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from user %s.", policy_arn, user_name
        )
        raise
```

Crie a funções que envolvam ações de política do IAM.

```
import json
import logging
import operator
import pprint
import time

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_policy(name, description, actions, resource_arn):
    """
    Creates a policy that contains a single statement.
```

```
    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this
 policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all
 objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy



def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
        raise
```

Crie funções que envolvam ações de chave de acesso do IAM.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)

iam = boto3.resource("iam")

def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.

    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair



def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
```

```
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

Use as funções de wrapper para criar usuários com políticas diferentes e use as credenciais deles para acessar um bucket do Amazon S3.

```
def usage_demo():
    """
    Shows how to manage users, keys, and policies.
    This demonstration creates two users: one user who can put and get objects in
 an
    Amazon S3 bucket, and another user who can only get objects from the bucket.
    The demo then shows how the users can perform only the actions they are
 permitted
    to perform.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management user demo.")
    print("-" * 88)
    print(
        "Users can have policies and roles attached to grant them specific "
        "permissions."
    )
    s3 = boto3.resource("s3")
    bucket = s3.create_bucket(
        Bucket=f"demo-iam-bucket-{time.time_ns()}",
        CreateBucketConfiguration={
            "LocationConstraint": s3.meta.client.meta.region_name
        },
    )
    print(f"Created an Amazon S3 bucket named {bucket.name}.")
    user_read_writer = create_user("demo-iam-read-writer")
```

```
    user_reader = create_user("demo-iam-reader")
    print(f"Created two IAM users: {user_read_writer.name} and
{user_reader.name}")
    update_user(user_read_writer.name, "demo-iam-creator")
    update_user(user_reader.name, "demo-iam-getter")
    users = list_users()
    user_read_writer = next(
        user for user in users if user.user_id == user_read_writer.user_id
    )
    user_reader = next(user for user in users if user.user_id ==
user_reader.user_id)
    print(
        f"Changed the names of the users to {user_read_writer.name} "
        f"and {user_reader.name}."
    )

    read_write_policy = policy_wrapper.create_policy(
        "demo-iam-read-write-policy",
        "Grants rights to create and get an object in the demo bucket.",
        ["s3:PutObject", "s3:GetObject"],
        f"arn:aws:s3:::{bucket.name}/*",
    )
    print(
        f"Created policy {read_write_policy.policy_name} with ARN:
{read_write_policy.arn}"
    )
    print(read_write_policy.description)
    read_policy = policy_wrapper.create_policy(
        "demo-iam-read-policy",
        "Grants rights to get an object from the demo bucket.",
        "s3:GetObject",
        f"arn:aws:s3:::{bucket.name}/*",
    )
    print(f"Created policy {read_policy.policy_name} with ARN:
{read_policy.arn}")
    print(read_policy.description)
    attach_policy(user_read_writer.name, read_write_policy.arn)
    print(f"Attached {read_write_policy.policy_name} to
{user_read_writer.name}.")
    attach_policy(user_reader.name, read_policy.arn)
    print(f"Attached {read_policy.policy_name} to {user_reader.name}.")

    user_read_writer_key = access_key_wrapper.create_key(user_read_writer.name)
    print(f"Created access key pair for {user_read_writer.name}.")
```

```
    user_reader_key = access_key_wrapper.create_key(user_reader.name)
    print(f"Created access key pair for {user_reader.name}.")

    s3_read_writer_resource = boto3.resource(
        "s3",
        aws_access_key_id=user_read_writer_key.id,
        aws_secret_access_key=user_read_writer_key.secret,
    )
    demo_object_key = f"object-{time.time_ns()}"
    demo_object = None
    while demo_object is None:
        try:
            demo_object = s3_read_writer_resource.Bucket(bucket.name).put_object(
                Key=demo_object_key, Body=b"AWS IAM demo object content!"
            )
        except ClientError as error:
            if error.response["Error"]["Code"] == "InvalidAccessKeyId":
                print("Access key not yet available. Waiting...")
                time.sleep(1)
            else:
                raise
    print(
        f"Put {demo_object_key} into {bucket.name} using "
        f"{user_read_writer.name}'s credentials."
    )

    read_writer_object = s3_read_writer_resource.Bucket(bucket.name).Object(
        demo_object_key
    )
    read_writer_content = read_writer_object.get()["Body"].read()
    print(f"Got object {read_writer_object.key} using read-writer user's
credentials.")
    print(f"Object content: {read_writer_content}")

    s3_reader_resource = boto3.resource(
        "s3",
        aws_access_key_id=user_reader_key.id,
        aws_secret_access_key=user_reader_key.secret,
    )
    demo_content = None
    while demo_content is None:
        try:
            demo_object =
s3_reader_resource.Bucket(bucket.name).Object(demo_object_key)
```

```
            demo_content = demo_object.get()["Body"].read()
            print(f"Got object {demo_object.key} using reader user's
credentials.")
            print(f"Object content: {demo_content}")
        except ClientError as error:
            if error.response["Error"]["Code"] == "InvalidAccessKeyId":
                print("Access key not yet available. Waiting...")
                time.sleep(1)
            else:
                raise

    try:
        demo_object.delete()
    except ClientError as error:
        if error.response["Error"]["Code"] == "AccessDenied":
            print("-" * 88)
            print(
                "Tried to delete the object using the reader user's credentials.
"
                "Got expected AccessDenied error because the reader is not "
                "allowed to delete objects."
            )
            print("-" * 88)

    access_key_wrapper.delete_key(user_reader.name, user_reader_key.id)
    detach_policy(user_reader.name, read_policy.arn)
    policy_wrapper.delete_policy(read_policy.arn)
    delete_user(user_reader.name)
    print(f"Deleted keys, detached and deleted policy, and deleted
{user_reader.name}.")

    access_key_wrapper.delete_key(user_read_writer.name, user_read_writer_key.id)
    detach_policy(user_read_writer.name, read_write_policy.arn)
    policy_wrapper.delete_policy(read_write_policy.arn)
    delete_user(user_read_writer.name)
    print(
        f"Deleted keys, detached and deleted policy, and deleted
{user_read_writer.name}."
    )

    bucket.objects.delete()
    bucket.delete()
    print(f"Emptied and deleted {bucket.name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachUserPolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteUser
  - DetachUserPolicy
  - ListUsers
  - UpdateUser

Gerenciar chaves de acesso do IAM usando um AWS SDK

O exemplo de código a seguir mostra como gerenciar chaves de acesso.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar e listar chaves de acesso.
- Descobrir quando e como a chave de acesso foi usada pela última vez.
- Atualizar e excluir chaves de acesso.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a funções que envolvam ações de chave de acesso do IAM.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)

iam = boto3.resource("iam")

def list_keys(user_name):
    """
    Lists the keys owned by the specified user.

    :param user_name: The name of the user.
    :return: The list of keys owned by the user.
    """
    try:
        keys = list(iam.User(user_name).access_keys.all())
        logger.info("Got %s access keys for %s.", len(keys), user_name)
    except ClientError:
        logger.exception("Couldn't get access keys for %s.", user_name)
        raise
    else:
        return keys



def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.
```

```
    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair



def get_last_use(key_id):
    """
    Gets information about when and how a key was last used.

    :param key_id: The ID of the key to look up.
    :return: Information about the key's last use.
    """
    try:
        response = iam.meta.client.get_access_key_last_used(AccessKeyId=key_id)
        last_used_date = response["AccessKeyLastUsed"].get("LastUsedDate", None)
        last_service = response["AccessKeyLastUsed"].get("ServiceName", None)
        logger.info(
            "Key %s was last used by %s on %s to access %s.",
            key_id,
            response["UserName"],
            last_used_date,
            last_service,
        )
    except ClientError:
        logger.exception("Couldn't get last use of key %s.", key_id)
        raise
    else:
        return response
```

```
def update_key(user_name, key_id, activate):
    """
    Updates the status of a key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to update.
    :param activate: When True, the key is activated. Otherwise, the key is
 deactivated.
    """

    try:
        key = iam.User(user_name).AccessKey(key_id)
        if activate:
            key.activate()
        else:
            key.deactivate()
        logger.info("%s key %s.", "Activated" if activate else "Deactivated",
 key_id)
    except ClientError:
        logger.exception(
            "Couldn't %s key %s.", "Activate" if activate else "Deactivate",
 key_id
        )
        raise



def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

Use a funções de wrapper para executar ações de chave de acesso para o usuário atual.

```
def usage_demo():
    """Shows how to create and manage access keys."""

    def print_keys():
        """Gets and prints the current keys for a user."""
        current_keys = list_keys(current_user_name)
        print("The current user's keys are now:")
        print(*[f"{key.id}: {key.status}" for key in current_keys], sep="\n")

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management access key demo.")
    print("-" * 88)
    current_user_name = iam.CurrentUser().user_name
    print(
        f"This demo creates an access key for the current user "
        f"({current_user_name}), manipulates the key in a few ways, and then "
        f"deletes it."
    )
    all_keys = list_keys(current_user_name)
    if len(all_keys) == 2:
        print(
            "The current user already has the maximum of 2 access keys. To run "
            "this demo, either delete one of the access keys or use a user "
            "that has only 1 access key."
        )
    else:
        new_key = create_key(current_user_name)
        print(f"Created a new key with id {new_key.id} and secret
 {new_key.secret}.")
        print_keys()
        existing_key = next(key for key in all_keys if key != new_key)
        last_use = get_last_use(existing_key.id)["AccessKeyLastUsed"]
        print(
            f"Key {all_keys[0].id} was last used to access
 {last_use['ServiceName']} "
            f"on {last_use['LastUsedDate']}"
        )
        update_key(current_user_name, new_key.id, False)
```

```
        print(f"Key {new_key.id} is now deactivated.")
        print_keys()
        delete_key(current_user_name, new_key.id)
        print_keys()
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAccessKey
  - DeleteAccessKey
  - GetAccessKeyLastUsed
  - ListAccessKeys
  - UpdateAccessKey

Gerenciar políticas do IAM usando um AWS SDK

O código de exemplo a seguir mostra como:

- Criar e listar políticas.
- Criar e obter versões de políticas.
- Reverter uma política para uma versão anterior.
- Excluir políticas.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a funções que envolvam ações de política do IAM.

```
import json
import logging
import operator
import pprint
import time

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_policy(name, description, actions, resource_arn):
    """
    Creates a policy that contains a single statement.

    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this
 policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all
 objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
```

```
    else:
        return policy



def list_policies(scope):
    """
    Lists the policies in the current account.

    :param scope: Limits the kinds of policies that are returned. For example,
                  'Local' specifies that only locally managed policies are
 returned.
    :return: The list of policies.
    """
    try:
        policies = list(iam.policies.filter(Scope=scope))
        logger.info("Got %s policies in scope '%s'.", len(policies), scope)
    except ClientError:
        logger.exception("Couldn't get policies for scope '%s'.", scope)
        raise
    else:
        return policies



def create_policy_version(policy_arn, actions, resource_arn, set_as_default):
    """
    Creates a policy version. Policies can have up to five versions. The default
    version is the one that is used for all resources that reference the policy.

    :param policy_arn: The ARN of the policy.
    :param actions: The actions to allow in the policy version.
    :param resource_arn: The ARN of the resource this policy version applies to.
    :param set_as_default: When True, this policy version is set as the default
                           version for the policy. Otherwise, the default
                           is not changed.
    :return: The newly created policy version.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
```

```
        policy = iam.Policy(policy_arn)
        policy_version = policy.create_version(
            PolicyDocument=json.dumps(policy_doc), SetAsDefault=set_as_default
        )
        logger.info(
            "Created policy version %s for policy %s.",
            policy_version.version_id,
            policy_version.arn,
        )
    except ClientError:
        logger.exception("Couldn't create a policy version for %s.", policy_arn)
        raise
    else:
        return policy_version



def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement



def rollback_policy_version(policy_arn):
    """
    Rolls back to the previous default policy, if it exists.
```

```
    1. Gets the list of policy versions in order by date.
    2. Finds the default.
    3. Makes the previous policy the default.
    4. Deletes the old default version.

    :param policy_arn: The ARN of the policy to roll back.
    :return: The default version of the policy after the rollback.
    """
    try:
        policy_versions = sorted(
            iam.Policy(policy_arn).versions.all(),
            key=operator.attrgetter("create_date"),
        )
        logger.info("Got %s versions for %s.", len(policy_versions), policy_arn)
    except ClientError:
        logger.exception("Couldn't get versions for %s.", policy_arn)
        raise

    default_version = None
    rollback_version = None
    try:
        while default_version is None:
            ver = policy_versions.pop()
            if ver.is_default_version:
                default_version = ver
        rollback_version = policy_versions.pop()
        rollback_version.set_as_default()
        logger.info("Set %s as the default version.",
rollback_version.version_id)
        default_version.delete()
        logger.info("Deleted original default version %s.",
default_version.version_id)
    except IndexError:
        if default_version is None:
            logger.warning("No default version found for %s.", policy_arn)
        elif rollback_version is None:
            logger.warning(
                "Default version %s found for %s, but no previous version exists,
so "
                "nothing to roll back to.",
                default_version.version_id,
                policy_arn,
            )
    except ClientError:
```

```
        logger.exception("Couldn't roll back version for %s.", policy_arn)
        raise
    else:
        return rollback_version



def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
        raise
```

Use a funções de wrapper para criar políticas, atualizar versões e obter informações sobre elas.

```
def usage_demo():
    """Shows how to use the policy functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management policy demo.")
    print("-" * 88)
    print(
        "Policies let you define sets of permissions that can be attached to "
        "other IAM resources, like users and roles."
    )
    bucket_arn = f"arn:aws:s3:::made-up-bucket-name"
    policy = create_policy(
        "demo-iam-policy",
        "Policy for IAM demonstration.",
        ["s3:ListObjects"],
        bucket_arn,
    )
```

```
    print(f"Created policy {policy.policy_name}.")
    policies = list_policies("Local")
    print(f"Your account has {len(policies)} managed policies:")
    print(*[pol.policy_name for pol in policies], sep=", ")
    time.sleep(1)
    policy_version = create_policy_version(
        policy.arn, ["s3:PutObject"], bucket_arn, True
    )
    print(
        f"Added policy version {policy_version.version_id} to policy "
        f"{policy.policy_name}."
    )
    default_statement = get_default_policy_statement(policy.arn)
    print(f"The default policy statement for {policy.policy_name} is:")
    pprint.pprint(default_statement)
    rollback_version = rollback_policy_version(policy.arn)
    print(
        f"Rolled back to version {rollback_version.version_id} for "
        f"{policy.policy_name}."
    )
    default_statement = get_default_policy_statement(policy.arn)
    print(f"The default policy statement for {policy.policy_name} is now:")
    pprint.pprint(default_statement)
    delete_policy(policy.arn)
    print(f"Deleted policy {policy.policy_name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreatePolicy
  - CreatePolicyVersion
  - DeletePolicy
  - DeletePolicyVersion
  - GetPolicyVersion
  - ListPolicies
  - ListPolicyVersions
  - SetDefaultPolicyVersion

Gerenciar perfis do IAM usando um AWS SDK

O código de exemplo a seguir mostra como:

- Criar um perfil do IAM.
- Anexar e separar políticas para um perfil.
- Excluir um perfil.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar perfis que envolvam ações de perfil do IAM.

```
import json
import logging
import pprint

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_role(role_name, allowed_services):
    """
    Creates a role that lets a list of specified services assume the role.

    :param role_name: The name of the role.
    :param allowed_services: The services that can assume the role.
    :return: The newly created role.
    """
    trust_policy = {
        "Version": "2012-10-17",
        "Statement": [
```

```
            {
                "Effect": "Allow",
                "Principal": {"Service": service},
                "Action": "sts:AssumeRole",
            }
            for service in allowed_services
        ],
    }

    try:
        role = iam.create_role(
            RoleName=role_name, AssumeRolePolicyDocument=json.dumps(trust_policy)
        )
        logger.info("Created role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create role %s.", role_name)
        raise
    else:
        return role



def attach_policy(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise



def detach_policy(role_name, policy_arn):
    """
    Detaches a policy from a role.
```

```
    :param role_name: The name of the role. **Note** this is the name, not the
 ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise



def delete_role(role_name):
    """
    Deletes a role.

    :param role_name: The name of the role to delete.
    """
    try:
        iam.Role(role_name).delete()
        logger.info("Deleted role %s.", role_name)
    except ClientError:
        logger.exception("Couldn't delete role %s.", role_name)
        raise
```

Use a funções de wrapper para criar uma função, depois, anexe e desanexe uma política.

```
def usage_demo():
    """Shows how to use the role functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management role demo.")
    print("-" * 88)
    print(
        "Roles let you define sets of permissions and can be assumed by "
        "other entities, like users and services."
    )
```

```
    print("The first 10 roles currently in your account are:")
    roles = list_roles(10)
    print(f"The inline policies for role {roles[0].name} are:")
    list_policies(roles[0].name)
    role = create_role(
        "demo-iam-role", ["lambda.amazonaws.com",
"batchoperations.s3.amazonaws.com"]
    )
    print(f"Created role {role.name}, with trust policy:")
    pprint.pprint(role.assume_role_policy_document)
    policy_arn = "arn:aws:iam::aws:policy/AmazonS3ReadOnlyAccess"
    attach_policy(role.name, policy_arn)
    print(f"Attached policy {policy_arn} to {role.name}.")
    print(f"Policies attached to role {role.name} are:")
    list_attached_policies(role.name)
    detach_policy(role.name, policy_arn)
    print(f"Detached policy {policy_arn} from {role.name}.")
    delete_role(role.name)
    print(f"Deleted {role.name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachRolePolicy
  - CreateRole
  - DeleteRole
  - DetachRolePolicy

Gerenciar a conta do IAM usando um AWS SDK

O código de exemplo a seguir mostra como:

- Obtenha e atualize o alias da conta.
- Gere um relatório de usuários e credenciais.
- Obter um resumo da utilização da conta.

- Obtenha detalhes de todos os usuários, grupos, perfis e políticas em sua conta, incluindo as relações uns com os outros.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações de conta do IAM.

```
import logging
import pprint
import sys
import time
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def list_aliases():
    """
    Gets the list of aliases for the current account. An account has at most one
 alias.

    :return: The list of aliases for the account.
    """
    try:
        response = iam.meta.client.list_account_aliases()
        aliases = response["AccountAliases"]
        if len(aliases) > 0:
            logger.info("Got aliases for your account: %s.", ",".join(aliases))
        else:
            logger.info("Got no aliases for your account.")
    except ClientError:
        logger.exception("Couldn't list aliases for your account.")
        raise
```

```
    else:
        return response["AccountAliases"]



def create_alias(alias):
    """
    Creates an alias for the current account. The alias can be used in place of
 the
    account ID in the sign-in URL. An account can have only one alias. When a new
    alias is created, it replaces any existing alias.

    :param alias: The alias to assign to the account.
    """

    try:
        iam.create_account_alias(AccountAlias=alias)
        logger.info("Created an alias '%s' for your account.", alias)
    except ClientError:
        logger.exception("Couldn't create alias '%s' for your account.", alias)
        raise



def delete_alias(alias):
    """
    Removes the alias from the current account.

    :param alias: The alias to remove.
    """
    try:
        iam.meta.client.delete_account_alias(AccountAlias=alias)
        logger.info("Removed alias '%s' from your account.", alias)
    except ClientError:
        logger.exception("Couldn't remove alias '%s' from your account.", alias)
        raise



def generate_credential_report():
    """
    Starts generation of a credentials report about the current account. After
    calling this function to generate the report, call get_credential_report
```

```
    to get the latest report. A new report can be generated a minimum of four
 hours
    after the last one was generated.
    """
    try:
        response = iam.meta.client.generate_credential_report()
        logger.info(
            "Generating credentials report for your account. " "Current state is
 %s.",
            response["State"],
        )
    except ClientError:
        logger.exception("Couldn't generate a credentials report for your
 account.")
        raise
    else:
        return response



def get_credential_report():
    """
    Gets the most recently generated credentials report about the current
 account.

    :return: The credentials report.
    """
    try:
        response = iam.meta.client.get_credential_report()
        logger.debug(response["Content"])
    except ClientError:
        logger.exception("Couldn't get credentials report.")
        raise
    else:
        return response["Content"]



def get_summary():
    """
    Gets a summary of account usage.

    :return: The summary of account usage.
    """
```

```
    try:
        summary = iam.AccountSummary()
        logger.debug(summary.summary_map)
    except ClientError:
        logger.exception("Couldn't get a summary for your account.")
        raise
    else:
        return summary.summary_map



def get_authorization_details(response_filter):
    """
    Gets an authorization detail report for the current account.

    :param response_filter: A list of resource types to include in the report,
 such
                            as users or roles. When not specified, all resources
                            are included.
    :return: The authorization detail report.
    """
    try:
        account_details = iam.meta.client.get_account_authorization_details(
            Filter=response_filter
        )
        logger.debug(account_details)
    except ClientError:
        logger.exception("Couldn't get details for your account.")
        raise
    else:
        return account_details
```

Chame funções de wrapper para alterar o alias da conta e obter relatórios sobre a conta.

```
def usage_demo():
    """Shows how to use the account functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management account demo.")
    print("-" * 88)
```

```
    print(
        "Setting an account alias lets you use the alias in your sign-in URL "
        "instead of your account number."
    )
    old_aliases = list_aliases()
    if len(old_aliases) > 0:
        print(f"Your account currently uses '{old_aliases[0]}' as its alias.")
    else:
        print("Your account currently has no alias.")
    for index in range(1, 3):
        new_alias = f"alias-{index}-{time.time_ns()}"
        print(f"Setting your account alias to {new_alias}")
        create_alias(new_alias)
    current_aliases = list_aliases()
    print(f"Your account alias is now {current_aliases}.")
    delete_alias(current_aliases[0])
    print(f"Your account now has no alias.")
    if len(old_aliases) > 0:
        print(f"Restoring your original alias back to {old_aliases[0]}...")
        create_alias(old_aliases[0])

    print("-" * 88)
    print("You can get various reports about your account.")
    print("Let's generate a credentials report...")
    report_state = None
    while report_state != "COMPLETE":
        cred_report_response = generate_credential_report()
        old_report_state = report_state
        report_state = cred_report_response["State"]
        if report_state != old_report_state:
            print(report_state, sep="")
        else:
            print(".", sep="")
        sys.stdout.flush()
        time.sleep(1)
    print()
    cred_report = get_credential_report()
    col_count = 3
    print(f"Got credentials report. Showing only the first {col_count} columns.")
    cred_lines = [
        line.split(",")[:col_count] for line in
cred_report.decode("utf-8").split("\n")
    ]
    col_width = max([len(item) for line in cred_lines for item in line]) + 2
```

```
    for line in cred_report.decode("utf-8").split("\n"):
        print(
            "".join(element.ljust(col_width) for element in line.split(",")
[:col_count])
        )

    print("-" * 88)
    print("Let's get an account summary.")
    summary = get_summary()
    print("Here's your summary:")
    pprint.pprint(summary)

    print("-" * 88)
    print("Let's get authorization details!")
    details = get_authorization_details([])
    see_details = input("These are pretty long, do you want to see them (y/n)? ")
    if see_details.lower() == "y":
        pprint.pprint(details)

    print("-" * 88)
    pw_policy_created = None
    see_pw_policy = input("Want to see the password policy for the account (y/n)?
 ")
    if see_pw_policy.lower() == "y":
        while True:
            if print_password_policy():
                break
            else:
                answer = input(
                    "Do you want to create a default password policy (y/n)? "
                )
                if answer.lower() == "y":
                    pw_policy_created = iam.create_account_password_policy()
                else:
                    break
    if pw_policy_created is not None:
        answer = input("Do you want to delete the password policy (y/n)? ")
        if answer.lower() == "y":
            pw_policy_created.delete()
            print("Password policy deleted.")

    print("The SAML providers for your account are:")
    list_saml_providers(10)
```

```
    print("-" * 88)
    print("Thanks for watching.")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAccountAlias
  - DeleteAccountAlias
  - GenerateCredentialReport
  - GetAccountAuthorizationDetails
  - GetAccountSummary
  - GetCredentialReport
  - ListAccountAliases

Reverter uma versão de política do IAM usando um AWS SDK

O código de exemplo a seguir mostra como:

- Obter a lista de versões da política em ordem por data.
- Encontrar a versão da política padrão.
- Tornar a versão da política anterior a padrão.
- Excluir a versão padrão antiga.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def rollback_policy_version(policy_arn):
```

```
    """
    Rolls back to the previous default policy, if it exists.

    1. Gets the list of policy versions in order by date.
    2. Finds the default.
    3. Makes the previous policy the default.
    4. Deletes the old default version.

    :param policy_arn: The ARN of the policy to roll back.
    :return: The default version of the policy after the rollback.
    """
    try:
        policy_versions = sorted(
            iam.Policy(policy_arn).versions.all(),
            key=operator.attrgetter("create_date"),
        )
        logger.info("Got %s versions for %s.", len(policy_versions), policy_arn)
    except ClientError:
        logger.exception("Couldn't get versions for %s.", policy_arn)
        raise

    default_version = None
    rollback_version = None
    try:
        while default_version is None:
            ver = policy_versions.pop()
            if ver.is_default_version:
                default_version = ver
        rollback_version = policy_versions.pop()
        rollback_version.set_as_default()
        logger.info("Set %s as the default version.",
rollback_version.version_id)
        default_version.delete()
        logger.info("Deleted original default version %s.",
default_version.version_id)
    except IndexError:
        if default_version is None:
            logger.warning("No default version found for %s.", policy_arn)
        elif rollback_version is None:
            logger.warning(
                "Default version %s found for %s, but no previous version exists,
so "
                "nothing to roll back to.",
                default_version.version_id,
```

```
                policy_arn,
            )
    except ClientError:
        logger.exception("Couldn't roll back version for %s.", policy_arn)
        raise
    else:
        return rollback_version
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeletePolicyVersion
  - ListPolicyVersions
  - SetDefaultPolicyVersion

Trabalhar com a API IAM Policy Builder usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie políticas do IAM usando a API orientada por objetos.
- Use a API IAM Policy Builder com o serviço do IAM.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos usam as importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
```

```
import software.amazon.awssdk.policybuilder.iam.IamConditionOperator;
import software.amazon.awssdk.policybuilder.iam.IamEffect;
import software.amazon.awssdk.policybuilder.iam.IamPolicy;
import software.amazon.awssdk.policybuilder.iam.IamPolicyWriter;
import software.amazon.awssdk.policybuilder.iam.IamPrincipal;
import software.amazon.awssdk.policybuilder.iam.IamPrincipalType;
import software.amazon.awssdk.policybuilder.iam.IamResource;
import software.amazon.awssdk.policybuilder.iam.IamStatement;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.GetPolicyResponse;
import software.amazon.awssdk.services.iam.model.GetPolicyVersionResponse;
import software.amazon.awssdk.services.sts.StsClient;

import java.net.URLDecoder;
import java.nio.charset.StandardCharsets;
import java.util.Arrays;
import java.util.List;
```

Crie uma política com base no tempo.

```
        public String timeBasedPolicyExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:GetItem")
                                                .addResource(IamResource.ALL)
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.DATE_GREATER_THAN)

 .key("aws:CurrentTime")

 .value("2020-04-01T00:00:00Z"))
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.DATE_LESS_THAN)

 .key("aws:CurrentTime")

 .value("2020-06-30T23:59:59Z")))
                                .build();
```

```
                // Use an IamPolicyWriter to write out the JSON string to a more
 readable
                // format.
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true)
                                .build());
        }
```

Crie uma política com várias condições.

```
        public String multipleConditionsExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:GetItem")

 .addAction("dynamodb:BatchGetItem")
                                                .addAction("dynamodb:Query")
                                                .addAction("dynamodb:PutItem")
                                                .addAction("dynamodb:UpdateItem")
                                                .addAction("dynamodb:DeleteItem")

 .addAction("dynamodb:BatchWriteItem")

 .addResource("arn:aws:dynamodb:*:*:table/table-name")

 .addConditions(IamConditionOperator.STRING_EQUALS

 .addPrefix("ForAllValues:"),

 "dynamodb:Attributes",
                                                                        List.of("column-
name1", "column-name2", "column-name3"))
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.STRING_EQUALS

 .addSuffix("IfExists"))

 .key("dynamodb:Select")
```

```
.value("SPECIFIC_ATTRIBUTES")))
                                .build();

                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Use entidades principais em uma política.

```
        public String specifyPrincipalsExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.DENY)
                                                .addAction("s3:*")
                                                .addPrincipal(IamPrincipal.ALL)

.addResource("arn:aws:s3:::BUCKETNAME/*")

.addResource("arn:aws:s3:::BUCKETNAME")
                                                .addCondition(b1 -> b1

.operator(IamConditionOperator.ARN_NOT_EQUALS)

.key("aws:PrincipalArn")

.value("arn:aws:iam::444455556666:user/user-name")))
                                .build();
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Permitir o acesso entre contas ao .

```
        public String allowCrossAccountAccessExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)

.addPrincipal(IamPrincipalType.AWS, "111122223333")
                                                .addAction("s3:PutObject")
```

```
                                                .addResource("arn:aws:s3:::DOC-
EXAMPLE-BUCKET/*")
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.STRING_EQUALS)
                                                                .key("s3:x-amz-
acl")
                                                                .value("bucket-
owner-full-control")))
                                .build();
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Crie e carregue uma `IamPolicy`.

```
        public String createAndUploadPolicyExample(IamClient iam, String
 accountID, String policyName) {
                // Build the policy.
                IamPolicy policy = IamPolicy.builder() // 'version' defaults to
 "2012-10-17".
                                .addStatement(IamStatement.builder()
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:PutItem")

 .addResource("arn:aws:dynamodb:us-east-1:" + accountID
                                                                + ":table/
exampleTableName")
                                                .build())
                                .build();
                // Upload the policy.
                iam.createPolicy(r ->
 r.policyName(policyName).policyDocument(policy.toJson()));
                return
 policy.toJson(IamPolicyWriter.builder().prettyPrint(true).build());
        }
```

Baixe e trabalhe com uma `IamPolicy`.

```
        public String createNewBasedOnExistingPolicyExample(IamClient iam, String
 accountID, String policyName,
```

```
                        String newPolicyName) {

                String policyArn = "arn:aws:iam::" + accountID + ":policy/" +
policyName;
                GetPolicyResponse getPolicyResponse = iam.getPolicy(r ->
r.policyArn(policyArn));

                String policyVersion =
getPolicyResponse.policy().defaultVersionId();
                GetPolicyVersionResponse getPolicyVersionResponse = iam
                                .getPolicyVersion(r ->
r.policyArn(policyArn).versionId(policyVersion));

                // Create an IamPolicy instance from the JSON string returned
from IAM.
                String decodedPolicy =
URLDecoder.decode(getPolicyVersionResponse.policyVersion().document(),
                                StandardCharsets.UTF_8);
                IamPolicy policy = IamPolicy.fromJson(decodedPolicy);

                /*
                 * All IamPolicy components are immutable, so use the copy method
that creates a
                 * new instance that
                 * can be altered in the same method call.
                 *
                 * Add the ability to get an item from DynamoDB as an additional
action.
                 */
                IamStatement newStatement = policy.statements().get(0).copy(s ->
s.addAction("dynamodb:GetItem"));

                // Create a new statement that replaces the original statement.
                IamPolicy newPolicy = policy.copy(p ->
p.statements(Arrays.asList(newStatement)));

                // Upload the new policy. IAM now has both policies.
                iam.createPolicy(r -> r.policyName(newPolicyName)
                                .policyDocument(newPolicy.toJson()));

                return
newPolicy.toJson(IamPolicyWriter.builder().prettyPrint(true).build());
        }
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Java 2.x.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreatePolicy
  - GetPolicy
  - GetPolicyVersion

Exemplos de código para o AWS IoT usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS IoT com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do AWS IoT – Mais informações sobre o AWS IoT.
- Referência da API do AWS IoT – Detalhes sobre todas as ações disponíveis do AWS IoT.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, AWS IoT

O exemplo de código a seguir mostra como começar a usar o AWS IoT.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iot.IotClient;
import software.amazon.awssdk.services.iot.model.ListThingsRequest;
import software.amazon.awssdk.services.iot.model.ListThingsResponse;
import software.amazon.awssdk.services.iot.model.ThingAttribute;
import java.util.List;

public class HelloIoT {
    public static void main(String[] args) {
        System.out.println("Hello AWS IoT. Here is a listing of your AWS IoT
 Things:");
        IotClient iotClient = IotClient.builder()
            .region(Region.US_EAST_1)
            .build();

        listAllThings(iotClient);
    }

    public static void listAllThings( IotClient iotClient) {
        ListThingsRequest thingsRequest = ListThingsRequest.builder()
            .maxResults(10)
            .build();

        ListThingsResponse response = iotClient.listThings(thingsRequest) ;
        List<ThingAttribute> thingList = response.things();
        for (ThingAttribute attribute : thingList) {
            System.out.println("Thing name: "+attribute.thingName());
            System.out.println("Thing ARN: "+attribute.thingArn());
        }
    }
}
```

- Para obter detalhes da API, consulte ListThings na Referência AWS SDK for Java 2.x da API.

Exemplos de código

- Ações para o AWS IoT usando AWS SDKs
  - Anexe um certificado a qualquer AWS IoT coisa usando um AWS SDK
  - Crie um AWS IoT certificado usando um AWS SDK
  - Crie uma AWS IoT regra usando um AWS SDK
  - Crie AWS IoT coisas usando um AWS SDK
  - Excluir um AWS IoT certificado usando um AWS SDK
  - Exclua qualquer AWS IoT coisa usando um AWS SDK
  - Descreva AWS IoT qualquer coisa usando um AWS SDK
  - Separe um certificado de qualquer AWS IoT coisa usando um SDK AWS
  - Obtenha informações sobre um endpoint usando um SDK da AWS
  - Liste seus AWS IoT certificados usando um AWS SDK
  - Liste suas coisas da AWS IoT usando um SDK da AWS
  - Consulte o índice AWS IoT de pesquisa usando um AWS SDK
  - Atualize qualquer AWS IoT coisa usando um AWS SDK
- Cenários para o AWS IoT usando AWS SDKs
  - Trabalhando com AWS IoT dispositivos, coisas e sombras usando o SDK AWS IoT

Ações para o AWS IoT usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS IoT com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o AWS IoT usando AWS SDKs.

Exemplos

- Anexe um certificado a qualquer AWS IoT coisa usando um AWS SDK
- Crie um AWS IoT certificado usando um AWS SDK
- Crie uma AWS IoT regra usando um AWS SDK

- Crie AWS IoT coisas usando um AWS SDK
- Excluir um AWS IoT certificado usando um AWS SDK
- Exclua qualquer AWS IoT coisa usando um AWS SDK
- Descreva AWS IoT qualquer coisa usando um AWS SDK
- Separe um certificado de qualquer AWS IoT coisa usando um SDK AWS
- Obtenha informações sobre um endpoint usando um SDK da AWS
- Liste seus AWS IoT certificados usando um AWS SDK
- Liste suas coisas da AWS IoT usando um SDK da AWS
- Consulte o índice AWS IoT de pesquisa usando um AWS SDK
- Atualize qualquer AWS IoT coisa usando um AWS SDK

Anexe um certificado a qualquer AWS IoT coisa usando um AWS SDK

Os exemplos de código a seguir mostram como anexar um AWS IoT certificado.

CLI

AWS CLI

Para anexar um certificado à sua coisa

O `attach-thing-principal` exemplo a seguir anexa um certificado à MyTemperatureSensor coisa. O certificado é identificado por um ARN. Você pode encontrar o ARN de um certificado no console de IoTAWS.

```
aws iot attach-thing-principal \
    --thing-name MyTemperatureSensor \
    --principal arn:aws:iot:us-
west-2:123456789012:cert/2e1eb273792174ec2b9bf4e9b37e6c6c692345499506002a35159767055278e8
```

Este comando não produz saída.

Para acessar mais informações, consulte Como gerenciar objetos com o registro no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte AttachThingPrincipalem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void attachCertificateToThing(IotClient iotClient, String
thingName, String certificateArn) {
       // Attach the certificate to the thing.
       AttachThingPrincipalRequest principalRequest =
AttachThingPrincipalRequest.builder()
           .thingName(thingName)
           .principal(certificateArn)
           .build();

       AttachThingPrincipalResponse attachResponse =
iotClient.attachThingPrincipal(principalRequest);

       // Verify the attachment was successful.
       if (attachResponse.sdkHttpResponse().isSuccessful()) {
           System.out.println("Certificate attached to Thing successfully.");

           // Print additional information about the Thing.
           describeThing(iotClient, thingName);
       } else {
           System.err.println("Failed to attach certificate to Thing. HTTP
Status Code: " +
               attachResponse.sdkHttpResponse().statusCode());
       }
   }
```

- Para obter detalhes da API, consulte AttachThingPrincipala Referência AWS SDK for Java 2.x da API.

Crie um AWS IoT certificado usando um AWS SDK

O exemplo de código a seguir mostra como criar um AWS IoT certificado.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createCertificate(IotClient iotClient) {
        try {
            CreateKeysAndCertificateResponse response =
iotClient.createKeysAndCertificate();
            String certificatePem = response.certificatePem();
            String certificateArn = response.certificateArn();

            // Print the details.
            System.out.println("\nCertificate:");
            System.out.println(certificatePem);
            System.out.println("\nCertificate ARN:");
            System.out.println(certificateArn);
            return certificateArn;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
```

- Para obter detalhes da API, consulte CreateKeysAndCertificatea Referência AWS SDK for Java 2.x da API.

Crie uma AWS IoT regra usando um AWS SDK

O exemplo de código a seguir mostra como criar uma AWS IoT regra.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createIoTRule(IotClient iotClient, String roleARN, String
ruleName, String action) {
       try {
           String sql = "SELECT * FROM '" + TOPIC + "'";
           SnsAction action1 = SnsAction.builder()
               .targetArn(action)
               .roleArn(roleARN)
               .build();

           // Create the action.
           Action myAction = Action.builder()
               .sns(action1)
               .build();

           // Create the topic rule payload.
           TopicRulePayload topicRulePayload = TopicRulePayload.builder()
               .sql(sql)
               .actions(myAction)
               .build();

           // Create the topic rule request.
           CreateTopicRuleRequest topicRuleRequest =
CreateTopicRuleRequest.builder()
               .ruleName(ruleName)
               .topicRulePayload(topicRulePayload)
               .build();

           // Create the rule.
```

```
            iotClient.createTopicRule(topicRuleRequest);
            System.out.println("IoT Rule created successfully.");

        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateTopicRulea Referência AWS SDK for Java 2.x da API.

Crie AWS IoT coisas usando um AWS SDK

Os exemplos de código a seguir mostram como criar AWS IoT algo.

CLI

AWS CLI

Exemplo 1: Para criar um registro de coisa no registro

O `create-thing` exemplo a seguir cria uma entrada para um dispositivo no registro de coisas da AWS IoT.

```
aws iot create-thing \
    --thing-name SampleIoTThing
```

Saída:

```
{
    "thingName": "SampleIoTThing",
    "thingArn": "arn:aws:iot:us-west-2: 123456789012:thing/SampleIoTThing",
    "thingId": " EXAMPLE1-90ab-cdef-fedc-ba987EXAMPLE "
}
```

Exemplo 2: Para definir uma coisa que está associada a um tipo de coisa

O `create-thing` exemplo a seguir cria uma coisa que tem o tipo de coisa especificado e seus atributos.

```
aws iot create-thing \
    --thing-name "MyLightBulb" \
    --thing-type-name "LightBulb" \
    --attribute-payload "{"attributes": {"wattage":"75", "model":"123"}}"
```

Saída:

```
{
    "thingName": "MyLightBulb",
    "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/MyLightBulb",
    "thingId": "40da2e73-c6af-406e-b415-15acae538797"
}
```

Para obter mais informações, consulte Como gerenciar coisas com o registro e os tipos de coisas no Guia AWSpara desenvolvedores de IoT.

- Para obter detalhes da API, consulte CreateThingem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void createIoTThing(IotClient iotClient, String thingName) {
        try {
            CreateThingRequest createThingRequest = CreateThingRequest.builder()
                .thingName(thingName)
                .build();

            CreateThingResponse createThingResponse =
 iotClient.createThing(createThingRequest);
            System.out.println(thingName +" was successfully created. The ARN
 value is " + createThingResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateThinga Referência AWS SDK for Java 2.x da API.

Excluir um AWS IoT certificado usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um AWS IoT certificado.

CLI

AWS CLI

Para excluir um certificado de dispositivo

O `delete-certificate` exemplo a seguir exclui o certificado do dispositivo com a ID especificada.

```
aws iot delete-certificate \
    --certificate-id
 c0c57bbc8baaf4631a9a0345c957657f5e710473e3ddbee1428d216d54d53ac9
```

Este comando não produz saída.

Para obter mais informações, consulte a DeleteCertificateReferência da API de AWS IoT.

- Para obter detalhes da API, consulte DeleteCertificateem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteCertificate(IotClient iotClient, String
certificateArn ) {
       DeleteCertificateRequest certificateProviderRequest =
DeleteCertificateRequest.builder()
           .certificateId(extractCertificateId(certificateArn))
           .build();

       iotClient.deleteCertificate(certificateProviderRequest);
       System.out.println(certificateArn +" was successfully deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteCertificatea Referência AWS SDK for Java 2.x da API.

Exclua qualquer AWS IoT coisa usando um AWS SDK

Os exemplos de código a seguir mostram como excluir qualquer AWS IoT coisa.

CLI

AWS CLI

Para exibir informações detalhadas sobre uma coisa

O `delete-thing` exemplo a seguir exclui algo do registro de AWS IoT da sua conta. AWS

era delete-thing --thing-name” FourthBulb

Este comando não produz saída.

Para acessar mais informações, consulte Como gerenciar objetos com o registro no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte DeleteThingem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void deleteIoTThing(IotClient iotClient, String thingName) {
    try {
        DeleteThingRequest deleteThingRequest = DeleteThingRequest.builder()
            .thingName(thingName)
            .build();

        iotClient.deleteThing(deleteThingRequest);
        System.out.println("Deleted Thing " + thingName);

    } catch (IotException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}
```

- Para obter detalhes da API, consulte DeleteThinga Referência AWS SDK for Java 2.x da API.

Descreva AWS IoT qualquer coisa usando um AWS SDK

Os exemplos de código a seguir mostram como descrever qualquer AWS IoT coisa.

CLI

AWS CLI

Para exibir informações detalhadas sobre uma coisa

O `describe-thing` exemplo a seguir exibe informações sobre uma coisa (dispositivo) definida no registro de AWS IoT da sua AWS conta.

como descrever a coisa --nome da coisa" MyLightBulb

Saída:

```
{
    "defaultClientId": "MyLightBulb",
    "thingName": "MyLightBulb",
    "thingId": "40da2e73-c6af-406e-b415-15acae538797",
    "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/MyLightBulb",
    "thingTypeName": "LightBulb",
    "attributes": {
        "model": "123",
        "wattage": "75"
    },
    "version": 1
}
```

Para acessar mais informações, consulte Como gerenciar objetos com o registro no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte DescribeThingem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    private static void describeThing(IotClient iotClient, String thingName) {
        try {
            DescribeThingRequest thingRequest = DescribeThingRequest.builder()
                .thingName(thingName)
                .build() ;

            // Print Thing details.
            DescribeThingResponse describeResponse =
iotClient.describeThing(thingRequest);
```

```
            System.out.println("Thing Details:");
            System.out.println("Thing Name: " + describeResponse.thingName());
            System.out.println("Thing ARN: " + describeResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeThinga Referência AWS SDK for Java 2.x da API.

Separe um certificado de qualquer AWS IoT coisa usando um SDK AWS

Os exemplos de código a seguir mostram como desanexar um AWS IoT certificado.

CLI

AWS CLI

Para separar um certificado/diretor de uma coisa

O `detach-thing-principal` exemplo a seguir remove um certificado que representa um principal da coisa especificada.

```
aws iot detach-thing-principal \
    --thing-name "MyLightBulb" \
    --principal "arn:aws:iot:us-
west-2:123456789012:cert/604c48437a57b7d5fc5d137c5be75011c6ee67c9a6943683a1acb4b1626bac36
```

Este comando não produz saída.

Para acessar mais informações, consulte Como gerenciar objetos com o registro no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte DetachThingPrincipalem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void detachThingPrincipal(IotClient iotClient, String
thingName, String certificateArn){
       try {
           DetachThingPrincipalRequest thingPrincipalRequest =
DetachThingPrincipalRequest.builder()
               .principal(certificateArn)
               .thingName(thingName)
               .build();

           iotClient.detachThingPrincipal(thingPrincipalRequest);
           System.out.println(certificateArn +" was successfully removed from "
+thingName);

       } catch (IotException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DetachThingPrincipala Referência AWS SDK for Java 2.x da API.

Obtenha informações sobre um endpoint usando um SDK da AWS

O exemplo de código a seguir mostra como obter informações do endpoint de AWS IoT.

CLI

AWS CLI

Exemplo 1: como obter o endpoint atual da AWS

O exemplo de `describe-endpoint` a seguir recupera o endpoint padrão da AWS ao qual todos os comandos são aplicados.

```
aws iot describe-endpoint
```

Saída:

```
{
    "endpointAddress": "abc123defghijk.iot.us-west-2.amazonaws.com"
}
```

Para obter mais informações, consulte o DescribeEndpointGuia do desenvolvedor de AWS IoT.

Exemplo 2: como obter o endpoint do ATS

O exemplo de `describe-endpoint` a seguir recupera o endpoint do Amazon Trust Services (ATS).

```
aws iot describe-endpoint \
    --endpoint-type iot:Data-ATS
```

Saída:

```
{
    "endpointAddress": "abc123defghijk-ats.iot.us-west-2.amazonaws.com"
}
```

Para obter mais informações, consulte X.509 Certificates and AWS IoT no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte DescribeEndpointem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String describeEndpoint(IotClient iotClient) {
        try {
            DescribeEndpointResponse endpointResponse =
 iotClient.describeEndpoint(DescribeEndpointRequest.builder().build());

            // Get the endpoint URL.
            String endpointUrl = endpointResponse.endpointAddress();
            String exString = getValue(endpointUrl);
            String fullEndpoint = "https://"+exString+"-ats.iot.us-
east-1.amazonaws.com";

            System.out.println("Full Endpoint URL: "+fullEndpoint);
            return fullEndpoint;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "" ;
    }
```

- Para obter detalhes da API, consulte DescribeEndpointa Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_address(client: &Client, endpoint_type: &str) -> Result<(), Error>
 {
    let resp = client
        .describe_endpoint()
        .endpoint_type(endpoint_type)
        .send()
        .await?;

    println!("Endpoint address: {}", resp.endpoint_address.unwrap());

    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeEndpointreferência da API AWS SDK for Rust.

Liste seus AWS IoT certificados usando um AWS SDK

Os exemplos de código a seguir mostram como listar seus AWS IoT certificados.

CLI

AWS CLI

Exemplo 1: Para listar os certificados registrados em sua AWS conta

O `list-certificates` exemplo a seguir lista todos os certificados registrados em sua conta. Se você tiver mais do que o limite de paginação padrão de 25, poderá usar o valor

de `nextMarker` resposta desse comando e fornecê-lo ao próximo comando para obter o próximo lote de resultados. Repita até `nextMarker` retornar sem um valor.

```
aws iot list-certificates
```

Saída:

```
{
    "certificates": [
        {
            "certificateArn": "arn:aws:iot:us-
west-2:123456789012:cert/604c48437a57b7d5fc5d137c5be75011c6ee67c9a6943683a1acb4b1626bac36
            "certificateId":
 "604c48437a57b7d5fc5d137c5be75011c6ee67c9a6943683a1acb4b1626bac36",
            "status": "ACTIVE",
            "creationDate": 1556810537.617
        },
        {
            "certificateArn": "arn:aws:iot:us-
west-2:123456789012:cert/262a1ac8a7d8aa72f6e96e365480f7313aa9db74b8339ec65d34dc3074e1c31e
            "certificateId":
 "262a1ac8a7d8aa72f6e96e365480f7313aa9db74b8339ec65d34dc3074e1c31e",
            "status": "ACTIVE",
            "creationDate": 1546447050.885
        },
        {
            "certificateArn": "arn:aws:iot:us-west-2:123456789012:cert/
b193ab7162c0fadca83246d24fa090300a1236fe58137e121b011804d8ac1d6b",
            "certificateId":
 "b193ab7162c0fadca83246d24fa090300a1236fe58137e121b011804d8ac1d6b",
            "status": "ACTIVE",
            "creationDate": 1546292258.322
        },
        {
            "certificateArn": "arn:aws:iot:us-
west-2:123456789012:cert/7aebeea3845d14a44ec80b06b8b78a89f3f8a706974b8b34d18f5adf0741db42
            "certificateId":
 "7aebeea3845d14a44ec80b06b8b78a89f3f8a706974b8b34d18f5adf0741db42",
            "status": "ACTIVE",
            "creationDate": 1541457693.453
        },
        {
```

```
            "certificateArn": "arn:aws:iot:us-
west-2:123456789012:cert/54458aa39ebb3eb39c91ffbbdcc3a6ca1c7c094d1644b889f735a6fc2cd9a7e3
            "certificateId":
 "54458aa39ebb3eb39c91ffbbdcc3a6ca1c7c094d1644b889f735a6fc2cd9a7e3",
            "status": "ACTIVE",
            "creationDate": 1541113568.611
        },
        {
            "certificateArn": "arn:aws:iot:us-
west-2:123456789012:cert/4f0ba725787aa94d67d2fca420eca022242532e8b3c58e7465c7778b443fd65e
            "certificateId":
 "4f0ba725787aa94d67d2fca420eca022242532e8b3c58e7465c7778b443fd65e",
            "status": "ACTIVE",
            "creationDate": 1541022751.983
        }
    ]
}
```

- Para obter detalhes da API, consulte ListCertificatesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listCertificates(IotClient iotClient) {
        ListCertificatesResponse response = iotClient.listCertificates();
        List<Certificate> certList = response.certificates();
        for (Certificate cert : certList) {
            System.out.println("Cert id: " + cert.certificateId());
            System.out.println("Cert Arn: " + cert.certificateArn());
        }
    }
```

- Para obter detalhes da API, consulte ListCertificatesa Referência AWS SDK for Java 2.x da API.

Liste suas coisas da AWS IoT usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os itens da AWS IoT.

CLI

AWS CLI

Exemplo 1: como listar todas os itens do registro

O exemplo de `list-things` a seguir lista os itens (dispositivos) que estão definidos no registro do AWS IoT da conta da AWS.

```
aws iot list-things
```

Saída:

```
{
    "things": [
        {
            "thingName": "ThirdBulb",
            "thingTypeName": "LightBulb",
            "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/ThirdBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "version": 2
        },
        {
            "thingName": "MyOtherLightBulb",
            "thingTypeName": "LightBulb",
            "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/
MyOtherLightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
```

```
            "version": 3
        },
        {
            "thingName": "MyLightBulb",
            "thingTypeName": "LightBulb",
            "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/MyLightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "version": 1
        },
        {
        "thingName": "SampleIoTThing",
        "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/SampleIoTThing",
        "attributes": {},
        "version": 1
        }
    ]
}
```

Exemplo 2: como listar os itens definidos que possuem um atributo específico

O exemplo de `list-things` a seguir exibe uma lista dos itens que têm um atributo chamado `wattage`.

```
aws iot list-things \
    --attribute-name wattage
```

Saída:

```
{
    "things": [
        {
            "thingName": "MyLightBulb",
            "thingTypeName": "LightBulb",
            "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/MyLightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "version": 1
```

```
        },
        {
            "thingName": "MyOtherLightBulb",
            "thingTypeName": "LightBulb",
            "thingArn": "arn:aws:iot:us-west-2:123456789012:thing/
MyOtherLightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "version": 3
        }
    ]
}
```

Para acessar mais informações, consulte Como gerenciar objetos com o registro no Guia do desenvolvedor do AWS IoT.

- Para obter detalhes da API, consulte ListThingsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_things(client: &Client) -> Result<(), Error> {
    let resp = client.list_things().send().await?;

    println!("Things:");

    for thing in resp.things.unwrap() {
        println!(
            "  Name:  {}",
            thing.thing_name.as_deref().unwrap_or_default()
        );
        println!(
            "  Type:  {}",
```

```
            thing.thing_type_name.as_deref().unwrap_or_default()
        );
        println!(
            "  ARN:   {}",
            thing.thing_arn.as_deref().unwrap_or_default()
        );
        println!();
    }

    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListThingsreferência da API AWS SDK for Rust.

Consulte o índice AWS IoT de pesquisa usando um AWS SDK

Os exemplos de código a seguir mostram como consultar o índice AWS IoT de pesquisa.

CLI

AWS CLI

Para consultar o índice da coisa

O `search-index` exemplo a seguir consulta o `AWS_Things` índice em busca de itens que têm um tipo de`LightBulb`.

```
aws iot search-index \
    --index-name "AWS_Things" \
    --query-string "thingTypeName:LightBulb"
```

Saída:

```
{
    "things": [
        {
            "thingName": "MyLightBulb",
            "thingId": "40da2e73-c6af-406e-b415-15acae538797",
```

```
            "thingTypeName": "LightBulb",
            "thingGroupNames": [
                "LightBulbs",
                "DeadBulbs"
            ],
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "connectivity": {
                "connected": false
            }
        },
        {
            "thingName": "ThirdBulb",
            "thingId": "615c8455-33d5-40e8-95fd-3ee8b24490af",
            "thingTypeName": "LightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "connectivity": {
                "connected": false
            }
        },
        {
            "thingName": "MyOtherLightBulb",
            "thingId": "6dae0d3f-40c1-476a-80c4-1ed24ba6aa11",
            "thingTypeName": "LightBulb",
            "attributes": {
                "model": "123",
                "wattage": "75"
            },
            "connectivity": {
                "connected": false
            }
        }
    ]
}
```

Para obter mais informações, consulte Managing Thing Indexing no Guia do desenvolvedor de AWSIoT.

- Para obter detalhes da API, consulte SearchIndexem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void searchThings(IotClient iotClient, String queryString){
        SearchIndexRequest searchIndexRequest = SearchIndexRequest.builder()
            .queryString(queryString)
            .build();

        try {
            // Perform the search and get the result.
            SearchIndexResponse searchIndexResponse =
iotClient.searchIndex(searchIndexRequest);

            // Process the result.
            if (searchIndexResponse.things().isEmpty()) {
                System.out.println("No things found.");
            } else {
                searchIndexResponse.things().forEach(thing ->
System.out.println("Thing id found using search is " + thing.thingId()));
            }
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte SearchIndexa Referência AWS SDK for Java 2.x da API.

Atualize qualquer AWS IoT coisa usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar qualquer AWS IoT coisa.

CLI

AWS CLI

Para associar uma coisa a um tipo de coisa

O `update-thing` exemplo a seguir associa uma coisa no registro de AWS IoT a um tipo de coisa. Ao fazer a associação, você fornece valores para os atributos definidos pelo tipo de coisa.

```
aws iot update-thing \
    --thing-name "MyOtherLightBulb" \
    --thing-type-name "LightBulb" \
    --attribute-payload "{"attributes": {"wattage":"75", "model":"123"}}"
```

Esse comando não produz saída. Use o `describe-thing` comando para ver o resultado.

Para obter mais informações, consulte Tipos de coisas no Guia AWSpara desenvolvedores de IoT.

- Para obter detalhes da API, consulte UpdateThingna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void updateThing(IotClient iotClient, String thingName) {
        // Specify the new attribute values.
        String newLocation = "Office";
        String newFirmwareVersion = "v2.0";

        Map<String, String> attMap = new HashMap<>();
        attMap.put("location", newLocation);
        attMap.put("firmwareVersion", newFirmwareVersion);
```

```
        AttributePayload attributePayload = AttributePayload.builder()
            .attributes(attMap)
            .build();

        UpdateThingRequest updateThingRequest = UpdateThingRequest.builder()
            .thingName(thingName)
            .attributePayload(attributePayload)
            .build();

        try {
            // Update the IoT Thing attributes.
            iotClient.updateThing(updateThingRequest);
            System.out.println("Thing attributes updated successfully.");

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte UpdateThinga Referência AWS SDK for Java 2.x da API.

Cenários para o AWS IoT usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS IoT com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Trabalhando com AWS IoT dispositivos, coisas e sombras usando o SDK AWS IoT

Trabalhando com AWS IoT dispositivos, coisas e sombras usando o SDK AWS IoT

O exemplo de código a seguir mostra como trabalhar com casos de uso de gerenciamento de AWS IoT dispositivos usando o AWS IoT SDK.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iot.IotClient;
import software.amazon.awssdk.services.iot.model.Action;
import software.amazon.awssdk.services.iot.model.AttachThingPrincipalRequest;
import software.amazon.awssdk.services.iot.model.AttachThingPrincipalResponse;
import software.amazon.awssdk.services.iot.model.AttributePayload;
import software.amazon.awssdk.services.iot.model.Certificate;
import
 software.amazon.awssdk.services.iot.model.CreateKeysAndCertificateResponse;
import software.amazon.awssdk.services.iot.model.CreateThingRequest;
import software.amazon.awssdk.services.iot.model.CreateTopicRuleRequest;
import software.amazon.awssdk.services.iot.model.DeleteCertificateRequest;
import software.amazon.awssdk.services.iot.model.CreateThingResponse;
import software.amazon.awssdk.services.iot.model.DeleteThingRequest;
import software.amazon.awssdk.services.iot.model.DescribeEndpointRequest;
import software.amazon.awssdk.services.iot.model.DescribeEndpointResponse;
import software.amazon.awssdk.services.iot.model.DescribeThingRequest;
import software.amazon.awssdk.services.iot.model.DescribeThingResponse;
import software.amazon.awssdk.services.iot.model.DetachThingPrincipalRequest;
import software.amazon.awssdk.services.iot.model.IotException;
import software.amazon.awssdk.services.iot.model.ListCertificatesResponse;
import software.amazon.awssdk.services.iot.model.ListTopicRulesRequest;
import software.amazon.awssdk.services.iot.model.ListTopicRulesResponse;
import software.amazon.awssdk.services.iot.model.SearchIndexRequest;
import software.amazon.awssdk.services.iot.model.SearchIndexResponse;
import software.amazon.awssdk.services.iot.model.SnsAction;
import software.amazon.awssdk.services.iot.model.TopicRuleListItem;
import software.amazon.awssdk.services.iot.model.TopicRulePayload;
import software.amazon.awssdk.services.iot.model.UpdateThingRequest;
import software.amazon.awssdk.services.iotdataplane.IotDataPlaneClient;
import software.amazon.awssdk.services.iotdataplane.model.GetThingShadowRequest;
```

```
import software.amazon.awssdk.services.iotdataplane.model.GetThingShadowResponse;
import
 software.amazon.awssdk.services.iotdataplane.model.UpdateThingShadowRequest;
import java.net.URI;
import java.nio.charset.StandardCharsets;
import java.util.HashMap;
import java.util.List;
import java.util.Map;
import java.util.Scanner;
import java.util.regex.Matcher;
import java.util.regex.Pattern;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java example performs these tasks:
 *
 * 1. Creates an AWS IoT Thing.
 * 2. Generate and attach a device certificate.
 * 3. Update an AWS IoT Thing with Attributes.
 * 4. Get an AWS IoT Endpoint.
 * 5. List your certificates.
 * 6. Updates the shadow for the specified thing..
 * 7. Write out the state information, in JSON format
 * 8. Creates a rule
 * 9. List rules
 * 10. Search things
 * 11. Detach amd delete the certificate.
 * 12. Delete Thing.
 */
public class IotScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");
    private static final String TOPIC = "your-iot-topic";
    public static void main(String[] args) {
        final String usage =
            """
                Usage:
```

```
                    <roleARN> <snsAction>

                Where:
                    roleARN - The ARN of an IAM role that has permission to work
with AWS IOT.
                    snsAction  - An ARN of an SNS topic.
                """;

      if (args.length != 2) {
          System.out.println(usage);
          System.exit(1);
      }

       String thingName;
       String ruleName;
       String roleARN = args[0];
       String snsAction = args[1];
       Scanner scanner = new Scanner(System.in);
       IotClient iotClient = IotClient.builder()
           .region(Region.US_EAST_1)
           .build();

       System.out.println(DASHES);
       System.out.println("Welcome to the AWS IoT example workflow.");
       System.out.println("""
           This example program demonstrates various interactions with the AWS
Internet of Things (IoT) Core service. The program guides you through a series
of steps,
           including creating an IoT Thing, generating a device certificate,
updating the Thing with attributes, and so on.
           It utilizes the AWS SDK for Java V2 and incorporates functionality
for creating and managing IoT Things, certificates, rules,
           shadows, and performing searches. The program aims to showcase AWS
IoT capabilities and provides a comprehensive example for
           developers working with AWS IoT in a Java environment.

           """);
       System.out.print("Press Enter to continue...");
       scanner.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("1. Create an AWS IoT Thing.");
       System.out.println("""
```

```
            An AWS IoT Thing represents a virtual entity in the AWS IoT service
that can be associated with a physical device.
            """);
        // Prompt the user for input.
        System.out.print("Enter Thing name: ");
        thingName = scanner.nextLine();
        createIoTThing(iotClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Generate a device certificate.");
        System.out.println("""
            A device certificate performs a role in securing the communication
between devices (Things) and the AWS IoT platform.
            """);

        System.out.print("Do you want to create a certificate for " +thingName
+"? (y/n)");
        String certAns = scanner.nextLine();
        String certificateArn="" ;
        if (certAns != null && certAns.trim().equalsIgnoreCase("y")) {
            certificateArn = createCertificate(iotClient);
            System.out.println("Attach the certificate to the AWS IoT Thing.");
            attachCertificateToThing(iotClient, thingName, certificateArn);
        } else {
            System.out.println("A device certificate was not created.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Update an AWS IoT Thing with Attributes.");
        System.out.println("""
             IoT Thing attributes, represented as key-value pairs, offer a
pivotal advantage in facilitating efficient data
             management and retrieval within the AWS IoT ecosystem.
            """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        updateThing(iotClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Return a unique endpoint specific to the Amazon
Web Services account.");
```

```
        System.out.println("""
            An IoT Endpoint refers to a specific URL or Uniform Resource Locator
that serves as the entry point for communication between IoT devices and the AWS
IoT service.
           """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        String endpointUrl = describeEndpoint(iotClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. List your AWS IoT certificates");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        if (certificateArn.length() > 0) {
            listCertificates(iotClient);
        } else {
            System.out.println("You did not create a certificates. Skipping this
step.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Create an IoT shadow that refers to a digital
representation or virtual twin of a physical IoT device");
        System.out.println("""
            A Thing Shadow refers to a feature that enables you to create a
virtual representation, or "shadow,"
            of a physical device or thing. The Thing Shadow allows you to
synchronize and control the state of a device between
            the cloud and the device itself. and the AWS IoT service. For
example, you can write and retrieve JSON data from a Thing Shadow.
           """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        IotDataPlaneClient iotPlaneClient = IotDataPlaneClient.builder()
            .region(Region.US_EAST_1)
            .endpointOverride(URI.create(endpointUrl))
            .build();

        updateShadowThing(iotPlaneClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("7. Write out the state information, in JSON
format.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        getPayload(iotPlaneClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Creates a rule");
        System.out.println("""
        Creates a rule that is an administrator-level action.
        Any user who has permission to create rules will be able to access data
processed by the rule.
        """);
        System.out.print("Enter Rule name: ");
        ruleName = scanner.nextLine();
        createIoTRule(iotClient, roleARN, ruleName, snsAction);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. List your rules.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        listIoTRules(iotClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Search things using the Thing name.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        String queryString = "thingName:"+thingName ;
        searchThings(iotClient, queryString);
        System.out.println(DASHES);

        System.out.println(DASHES);
        if (certificateArn.length() > 0) {
            System.out.print("Do you want to detach and delete the certificate
for " +thingName +"? (y/n)");
            String delAns = scanner.nextLine();
            if (delAns != null && delAns.trim().equalsIgnoreCase("y")) {
                System.out.println("11. You selected to detach amd delete the
certificate.");
                System.out.print("Press Enter to continue...");
                scanner.nextLine();
```

```
                detachThingPrincipal(iotClient, thingName, certificateArn);
                deleteCertificate(iotClient, certificateArn);
            } else {
                System.out.println("11. You selected not to delete the
certificate.");
            }
        } else {
            System.out.println("11. You did not create a certificate so there is
nothing to delete.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Delete the AWS IoT Thing.");
        System.out.print("Do you want to delete the IoT Thing? (y/n)");
        String delAns = scanner.nextLine();
        if (delAns != null && delAns.trim().equalsIgnoreCase("y")) {
            deleteIoTThing(iotClient, thingName);
        } else {
            System.out.println("The IoT Thing was not deleted.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS IoT workflow has successfully completed.");
        System.out.println(DASHES);
    }

    public static void listCertificates(IotClient iotClient) {
        ListCertificatesResponse response = iotClient.listCertificates();
        List<Certificate> certList = response.certificates();
        for (Certificate cert : certList) {
            System.out.println("Cert id: " + cert.certificateId());
            System.out.println("Cert Arn: " + cert.certificateArn());
        }
    }

    public static void listIoTRules(IotClient iotClient) {
        try {
            ListTopicRulesRequest listTopicRulesRequest =
ListTopicRulesRequest.builder().build();
            ListTopicRulesResponse listTopicRulesResponse =
iotClient.listTopicRules(listTopicRulesRequest);
            System.out.println("List of IoT Rules:");
```

```
            List<TopicRuleListItem> ruleList = listTopicRulesResponse.rules();
            for (TopicRuleListItem rule : ruleList) {
                System.out.println("Rule Name: " + rule.ruleName());
                System.out.println("Rule ARN: " + rule.ruleArn());
                System.out.println("--------------");
            }

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createIoTRule(IotClient iotClient, String roleARN, String
 ruleName, String action) {
        try {
            String sql = "SELECT * FROM '" + TOPIC + "'";
            SnsAction action1 = SnsAction.builder()
                .targetArn(action)
                .roleArn(roleARN)
                .build();

            // Create the action.
            Action myAction = Action.builder()
                .sns(action1)
                .build();

            // Create the topic rule payload.
            TopicRulePayload topicRulePayload = TopicRulePayload.builder()
                .sql(sql)
                .actions(myAction)
                .build();

            // Create the topic rule request.
            CreateTopicRuleRequest topicRuleRequest =
 CreateTopicRuleRequest.builder()
                .ruleName(ruleName)
                .topicRulePayload(topicRulePayload)
                .build();

            // Create the rule.
            iotClient.createTopicRule(topicRuleRequest);
            System.out.println("IoT Rule created successfully.");
```

```
        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getPayload(IotDataPlaneClient iotPlaneClient, String
thingName) {
        try {
            GetThingShadowRequest getThingShadowRequest =
GetThingShadowRequest.builder()
                .thingName(thingName)
                .build();

            GetThingShadowResponse getThingShadowResponse =
iotPlaneClient.getThingShadow(getThingShadowRequest);

            // Extracting payload from response.
            SdkBytes payload = getThingShadowResponse.payload();
            String payloadString = payload.asUtf8String();
            System.out.println("Received Shadow Data: " + payloadString);

        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateShadowThing(IotDataPlaneClient iotPlaneClient,
String thingName) {
        try {
            // Create Thing Shadow State Document.
            String stateDocument = "{\"state\":{\"reported\":{\"temperature\":25,
\"humidity\":50}}}";
            SdkBytes data= SdkBytes.fromString(stateDocument,
StandardCharsets.UTF_8 );
            UpdateThingShadowRequest updateThingShadowRequest =
UpdateThingShadowRequest.builder()
                .thingName(thingName)
                .payload(data)
                .build();

            // Update Thing Shadow.
            iotPlaneClient.updateThingShadow(updateThingShadowRequest);
```

```
            System.out.println("Thing Shadow updated successfully.");

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void updateThing(IotClient iotClient, String thingName) {
        // Specify the new attribute values.
        String newLocation = "Office";
        String newFirmwareVersion = "v2.0";

        Map<String, String> attMap = new HashMap<>();
        attMap.put("location", newLocation);
        attMap.put("firmwareVersion", newFirmwareVersion);

        AttributePayload attributePayload = AttributePayload.builder()
            .attributes(attMap)
            .build();

        UpdateThingRequest updateThingRequest = UpdateThingRequest.builder()
            .thingName(thingName)
            .attributePayload(attributePayload)
            .build();

        try {
            // Update the IoT Thing attributes.
            iotClient.updateThing(updateThingRequest);
            System.out.println("Thing attributes updated successfully.");

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String describeEndpoint(IotClient iotClient) {
        try {
            DescribeEndpointResponse endpointResponse =
iotClient.describeEndpoint(DescribeEndpointRequest.builder().build());

            // Get the endpoint URL.
            String endpointUrl = endpointResponse.endpointAddress();
```

```
            String exString = getValue(endpointUrl);
            String fullEndpoint = "https://"+exString+"-ats.iot.us-
east-1.amazonaws.com";

            System.out.println("Full Endpoint URL: "+fullEndpoint);
            return fullEndpoint;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "" ;
    }

    public static void detachThingPrincipal(IotClient iotClient, String
 thingName, String certificateArn){
        try {
            DetachThingPrincipalRequest thingPrincipalRequest =
 DetachThingPrincipalRequest.builder()
                .principal(certificateArn)
                .thingName(thingName)
                .build();

            iotClient.detachThingPrincipal(thingPrincipalRequest);
            System.out.println(certificateArn +" was successfully removed from "
 +thingName);

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteCertificate(IotClient iotClient, String
 certificateArn ) {
        DeleteCertificateRequest certificateProviderRequest =
 DeleteCertificateRequest.builder()
            .certificateId(extractCertificateId(certificateArn))
            .build();

        iotClient.deleteCertificate(certificateProviderRequest);
        System.out.println(certificateArn +" was successfully deleted.");
    }
```

```
    // Get the cert Id  from the Cert ARN value.
    private static String extractCertificateId(String certificateArn) {
        // Example ARN: arn:aws:iot:region:account-id:cert/certificate-id.
        String[] arnParts = certificateArn.split(":");
        String certificateIdPart = arnParts[arnParts.length - 1];
        return certificateIdPart.substring(certificateIdPart.lastIndexOf("/") +
 1);
    }

    public static String createCertificate(IotClient iotClient) {
        try {
            CreateKeysAndCertificateResponse response =
 iotClient.createKeysAndCertificate();
            String certificatePem = response.certificatePem();
            String certificateArn = response.certificateArn();

            // Print the details.
            System.out.println("\nCertificate:");
            System.out.println(certificatePem);
            System.out.println("\nCertificate ARN:");
            System.out.println(certificateArn);
            return certificateArn;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }

    public static void attachCertificateToThing(IotClient iotClient, String
 thingName, String certificateArn) {
        // Attach the certificate to the thing.
        AttachThingPrincipalRequest principalRequest =
 AttachThingPrincipalRequest.builder()
            .thingName(thingName)
            .principal(certificateArn)
            .build();

        AttachThingPrincipalResponse attachResponse =
 iotClient.attachThingPrincipal(principalRequest);

        // Verify the attachment was successful.
```

```
        if (attachResponse.sdkHttpResponse().isSuccessful()) {
            System.out.println("Certificate attached to Thing successfully.");

            // Print additional information about the Thing.
            describeThing(iotClient, thingName);
        } else {
            System.err.println("Failed to attach certificate to Thing. HTTP
Status Code: " +
                attachResponse.sdkHttpResponse().statusCode());
        }
    }

    private static void describeThing(IotClient iotClient, String thingName) {
        try {
            DescribeThingRequest thingRequest = DescribeThingRequest.builder()
                .thingName(thingName)
                .build() ;

            // Print Thing details.
            DescribeThingResponse describeResponse =
iotClient.describeThing(thingRequest);
            System.out.println("Thing Details:");
            System.out.println("Thing Name: " + describeResponse.thingName());
            System.out.println("Thing ARN: " + describeResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteIoTThing(IotClient iotClient, String thingName) {
        try {
            DeleteThingRequest deleteThingRequest = DeleteThingRequest.builder()
                .thingName(thingName)
                .build();

            iotClient.deleteThing(deleteThingRequest);
            System.out.println("Deleted Thing " + thingName);

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void createIoTThing(IotClient iotClient, String thingName) {
        try {
            CreateThingRequest createThingRequest = CreateThingRequest.builder()
                .thingName(thingName)
                .build();

            CreateThingResponse createThingResponse =
 iotClient.createThing(createThingRequest);
            System.out.println(thingName +" was successfully created. The ARN
 value is " + createThingResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    private static String getValue(String input) {
        // Define a regular expression pattern for extracting the subdomain.
        Pattern pattern = Pattern.compile("^(.*?)\\.iot\\.us-east-1\\.amazonaws\
\.com");

        // Match the pattern against the input string.
        Matcher matcher = pattern.matcher(input);

        // Check if a match is found.
        if (matcher.find()) {
            // Extract the subdomain from the first capturing group.
            String subdomain = matcher.group(1);
            System.out.println("Extracted subdomain: " + subdomain);
            return subdomain ;
        } else {
            System.out.println("No match found");
        }
        return "" ;
    }

    public static void searchThings(IotClient iotClient, String queryString){
        SearchIndexRequest searchIndexRequest = SearchIndexRequest.builder()
            .queryString(queryString)
            .build();
```

```
        try {
            // Perform the search and get the result.
            SearchIndexResponse searchIndexResponse =
 iotClient.searchIndex(searchIndexRequest);

            // Process the result.
            if (searchIndexResponse.things().isEmpty()) {
                System.out.println("No things found.");
            } else {
                searchIndexResponse.things().forEach(thing ->
 System.out.println("Thing id found using search is " + thing.thingId()));
            }
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Exemplos de código para o AWS IoT data usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS IoT data com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do AWS IoT data – Mais informações sobre o AWS IoT data.
- Referência da API do AWS IoT data – Detalhes sobre todas as ações disponíveis do AWS IoT data.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o AWS IoT data usando AWS SDKs
  - Obtenha a sombra da coisa especificada usando um AWS SDK
  - Atualize a sombra da coisa especificada usando um AWS SDK

Ações para o AWS IoT data usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS IoT data com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Obtenha a sombra da coisa especificada usando um AWS SDK
- Atualize a sombra da coisa especificada usando um AWS SDK

Obtenha a sombra da coisa especificada usando um AWS SDK

Os exemplos de código a seguir mostram como obter a sombra de qualquer AWS IoT coisa.

CLI

AWS CLI

Para obter uma coisa, documente de sombra

O `get-thing-shadow` exemplo a seguir obtém o documento sombra da coisa para a coisa de IoT especificada.

```
aws iot-data get-thing-shadow \
    --thing-name MyRPi \
    output.txt
```

O comando não produz nenhuma saída na tela, mas o seguinte mostra o conteúdo de`output.txt`:

```
{
  "state":{
    "reported":{
```

```
    "moisture":"low"
    }
  },
  "metadata":{
    "reported":{
      "moisture":{
        "timestamp":1560269319
      }
    }
  },
  "version":1,"timestamp":1560269405
}
```

Para obter mais informações, consulte Fluxo de dados do Device Shadow Service no AWSIoT Developers Guide.

- Para obter detalhes da API, consulte GetThingShadowna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getPayload(IotDataPlaneClient iotPlaneClient, String
thingName) {
       try {
           GetThingShadowRequest getThingShadowRequest =
GetThingShadowRequest.builder()
               .thingName(thingName)
               .build();

           GetThingShadowResponse getThingShadowResponse =
iotPlaneClient.getThingShadow(getThingShadowRequest);

           // Extracting payload from response.
```

```
            SdkBytes payload = getThingShadowResponse.payload();
            String payloadString = payload.asUtf8String();
            System.out.println("Received Shadow Data: " + payloadString);

        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetThingShadowa Referência AWS SDK for Java 2.x da API.

Atualize a sombra da coisa especificada usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar a sombra de qualquer AWS IoT coisa.

CLI

AWS CLI

Para atualizar uma coisa, sombra

O `update-thing-shadow` exemplo a seguir modifica o estado atual da sombra do dispositivo para a coisa especificada e a salva no arquivo`output.txt`.

```
aws iot-data update-thing-shadow \
    --thing-name MyRPi \
    --payload "{"state":{"reported":{"moisture":"okay"}}}" \
    "output.txt"
```

O comando não produz nenhuma saída na tela, mas o seguinte mostra o conteúdo de`output.txt`:

```
{
    "state": {
        "reported": {
            "moisture": "okay"
        }
    },
```

```
    "metadata": {
        "reported": {
            "moisture": {
                "timestamp": 1560270036
            }
        }
    },
    "version": 2,
    "timestamp": 1560270036
}
```

Para obter mais informações, consulte Fluxo de dados do Device Shadow Service no AWSIoT Developers Guide.

- Para obter detalhes da API, consulte UpdateThingShadowna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void updateShadowThing(IotDataPlaneClient iotPlaneClient,
String thingName) {
       try {
           // Create Thing Shadow State Document.
           String stateDocument = "{\"state\":{\"reported\":{\"temperature\":25,
\"humidity\":50}}}";
           SdkBytes data= SdkBytes.fromString(stateDocument,
StandardCharsets.UTF_8 );
           UpdateThingShadowRequest updateThingShadowRequest =
UpdateThingShadowRequest.builder()
               .thingName(thingName)
               .payload(data)
               .build();

           // Update Thing Shadow.
```

```
            iotPlaneClient.updateThingShadow(updateThingShadowRequest);
            System.out.println("Thing Shadow updated successfully.");

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte UpdateThingShadowa Referência AWS SDK for Java 2.x da API.

Exemplos de código para o Amazon Keyspaces usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Keyspaces (para Apache Cassandra) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Amazon Keyspaces – Mais informações sobre o Amazon Keyspaces.
- Referência da API do Amazon Keyspaces – Detalhes sobre todas as ações disponíveis do Amazon Keyspaces.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon Keyspaces

Os exemplos de código a seguir mostram como começar a usar o Amazon Keyspaces.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace KeyspacesActions;

public class HelloKeyspaces
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Keyspaces (for Apache
 Cassandra).
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonKeyspaces>()
                .AddTransient<KeyspacesWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<HelloKeyspaces>();

        var keyspacesClient =
 host.Services.GetRequiredService<IAmazonKeyspaces>();
        var keyspacesWrapper = new KeyspacesWrapper(keyspacesClient);
```

```
        Console.WriteLine("Hello, Amazon Keyspaces! Let's list your keyspaces:");
        await keyspacesWrapper.ListKeyspaces();
    }
}
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.keyspaces.KeyspacesClient;
import software.amazon.awssdk.services.keyspaces.model.KeyspaceSummary;
import software.amazon.awssdk.services.keyspaces.model.KeyspacesException;
import software.amazon.awssdk.services.keyspaces.model.ListKeyspacesRequest;
import software.amazon.awssdk.services.keyspaces.model.ListKeyspacesResponse;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloKeyspaces {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
```

```
        KeyspacesClient keyClient = KeyspacesClient.builder()
                .region(region)
                .build();

        listKeyspaces(keyClient);
    }

    public static void listKeyspaces(KeyspacesClient keyClient) {
        try {
            ListKeyspacesRequest keyspacesRequest =
 ListKeyspacesRequest.builder()
                    .maxResults(10)
                    .build();

            ListKeyspacesResponse response =
 keyClient.listKeyspaces(keyspacesRequest);
            List<KeyspaceSummary> keyspaces = response.keyspaces();
            for (KeyspaceSummary keyspace : keyspaces) {
                System.out.println("The name of the keyspace is " +
 keyspace.keyspaceName());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
 including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
*/

suspend fun main() {
    listKeyspaces()
}

suspend fun listKeyspaces() {
    val keyspacesRequest = ListKeyspacesRequest {
        maxResults = 10
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.listKeyspaces(keyspacesRequest)
        response.keyspaces?.forEach { keyspace ->
            println("The name of the keyspace is ${keyspace.keyspaceName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListKeyspacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3
```

```
def hello_keyspaces(keyspaces_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Keyspaces (for Apache
 Cassandra)
    client and list the keyspaces in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param keyspaces_client: A Boto3 Amazon Keyspaces Client object. This object
 wraps
                             the low-level Amazon Keyspaces service API.
    """
    print("Hello, Amazon Keyspaces! Let's list some of your keyspaces:\n")
    for ks in keyspaces_client.list_keyspaces(maxResults=5).get("keyspaces", []):
        print(ks["keyspaceName"])
        print(f"\t{ks['resourceArn']}")


if __name__ == "__main__":
    hello_keyspaces(boto3.client("keyspaces"))
```

- Para obter detalhes da API, consulte a ListKeyspacesReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações do Amazon Keyspaces usando SDKs AWS
  - Crie um espaço de chaves do Amazon Keyspaces usando um SDK AWS
  - Crie uma tabela do Amazon Keyspaces usando um SDK AWS
  - Exclua um espaço de chaves do Amazon Keyspaces usando um SDK AWS
  - Exclua uma tabela do Amazon Keyspaces usando um SDK da AWS
  - Obtenha dados sobre um keyspace do Amazon Keyspaces usando um SDK da AWS
  - Obtenha dados sobre uma tabela do Amazon Keyspaces usando um SDK da AWS
  - Listar os espaços de chaves do Amazon Keyspaces usando um SDK AWS
  - Listar tabelas do Amazon Keyspaces em um keyspace usando um SDK da AWS
  - Restaure uma tabela do Amazon Keyspaces para um ponto no tempo usando um SDK AWS
  - Atualize uma tabela do Amazon Keyspaces usando um SDK da AWS

- Cenários do Amazon Keyspaces com SDKs AWS
  - Comece a usar tabelas e espaços de chaves do Amazon Keyspaces usando um SDK AWS

Ações do Amazon Keyspaces usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Keyspaces (para Apache Cassandra) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon Keyspaces com SDKs AWS.

Exemplos

- Crie um espaço de chaves do Amazon Keyspaces usando um SDK AWS
- Crie uma tabela do Amazon Keyspaces usando um SDK AWS
- Exclua um espaço de chaves do Amazon Keyspaces usando um SDK AWS
- Exclua uma tabela do Amazon Keyspaces usando um SDK da AWS
- Obtenha dados sobre um keyspace do Amazon Keyspaces usando um SDK da AWS
- Obtenha dados sobre uma tabela do Amazon Keyspaces usando um SDK da AWS
- Listar os espaços de chaves do Amazon Keyspaces usando um SDK AWS
- Listar tabelas do Amazon Keyspaces em um keyspace usando um SDK da AWS
- Restaure uma tabela do Amazon Keyspaces para um ponto no tempo usando um SDK AWS
- Atualize uma tabela do Amazon Keyspaces usando um SDK da AWS

Crie um espaço de chaves do Amazon Keyspaces usando um SDK AWS

Os exemplos de código a seguir mostram como criar um espaço de chave do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create a new keyspace.
/// </summary>
/// <param name="keyspaceName">The name for the new keyspace.</param>
/// <returns>The Amazon Resource Name (ARN) of the new keyspace.</returns>
public async Task<string> CreateKeyspace(string keyspaceName)
{
    var response =
        await _amazonKeyspaces.CreateKeyspaceAsync(
            new CreateKeyspaceRequest { KeyspaceName = keyspaceName });
    return response.ResourceArn;
}
```

- Para obter detalhes da API, consulte CreateKeyspacea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createKeySpace(KeyspacesClient keyClient, String
keyspaceName) {
```

```
        try {
            CreateKeyspaceRequest keyspaceRequest =
 CreateKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            CreateKeyspaceResponse response =
 keyClient.createKeyspace(keyspaceRequest);
            System.out.println("The ARN of the KeySpace is " +
 response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateKeyspacea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createKeySpace(keyspaceNameVal: String) {
    val keyspaceRequest = CreateKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createKeyspace(keyspaceRequest)
        println("The ARN of the KeySpace is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyspacereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def create_keyspace(self, name):
        """
        Creates a keyspace.

        :param name: The name to give the keyspace.
        :return: The Amazon Resource Name (ARN) of the new keyspace.
        """
```

```
        try:
            response = self.keyspaces_client.create_keyspace(keyspaceName=name)
            self.ks_name = name
            self.ks_arn = response["resourceArn"]
        except ClientError as err:
            logger.error(
                "Couldn't create %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.ks_arn
```

- Para obter detalhes da API, consulte a CreateKeyspaceReferência da API AWSSDK for Python (Boto3).

Crie uma tabela do Amazon Keyspaces usando um SDK AWS

O exemplo de código a seguir mostra como criar uma tabela do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Create a new Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace where the table will be
created.</param>
    /// <param name="schema">The schema for the new table.</param>
    /// <param name="tableName">The name of the new table.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new table.</returns>
    public async Task<string> CreateTable(string keyspaceName, SchemaDefinition
schema, string tableName)
    {
        var request = new CreateTableRequest
        {
            KeyspaceName = keyspaceName,
            SchemaDefinition = schema,
            TableName = tableName,
            PointInTimeRecovery = new PointInTimeRecovery { Status =
PointInTimeRecoveryStatus.ENABLED }
        };

        var response = await _amazonKeyspaces.CreateTableAsync(request);
        return response.ResourceArn;
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void createTable(KeyspacesClient keyClient, String keySpace,
String tableName) {
        try {
            // Set the columns.
            ColumnDefinition defTitle = ColumnDefinition.builder()
```

```
                .name("title")
                .type("text")
                .build();

        ColumnDefinition defYear = ColumnDefinition.builder()
                .name("year")
                .type("int")
                .build();

        ColumnDefinition defReleaseDate = ColumnDefinition.builder()
                .name("release_date")
                .type("timestamp")
                .build();

        ColumnDefinition defPlot = ColumnDefinition.builder()
                .name("plot")
                .type("text")
                .build();

        List<ColumnDefinition> colList = new ArrayList<>();
        colList.add(defTitle);
        colList.add(defYear);
        colList.add(defReleaseDate);
        colList.add(defPlot);

        // Set the keys.
        PartitionKey yearKey = PartitionKey.builder()
                .name("year")
                .build();

        PartitionKey titleKey = PartitionKey.builder()
                .name("title")
                .build();

        List<PartitionKey> keyList = new ArrayList<>();
        keyList.add(yearKey);
        keyList.add(titleKey);

        SchemaDefinition schemaDefinition = SchemaDefinition.builder()
                .partitionKeys(keyList)
                .allColumns(colList)
                .build();

        PointInTimeRecovery timeRecovery = PointInTimeRecovery.builder()
```

```
                    .status(PointInTimeRecoveryStatus.ENABLED)
                    .build();

            CreateTableRequest tableRequest = CreateTableRequest.builder()
                    .keyspaceName(keySpace)
                    .tableName(tableName)
                    .schemaDefinition(schemaDefinition)
                    .pointInTimeRecovery(timeRecovery)
                    .build();

            CreateTableResponse response = keyClient.createTable(tableRequest);
            System.out.println("The table ARN is " + response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createTable(keySpaceVal: String?, tableNameVal: String?) {
    // Set the columns.
    val defTitle = ColumnDefinition {
        name = "title"
        type = "text"
    }

    val defYear = ColumnDefinition {
```

```
        name = "year"
        type = "int"
    }

    val defReleaseDate = ColumnDefinition {
        name = "release_date"
        type = "timestamp"
    }

    val defPlot = ColumnDefinition {
        name = "plot"
        type = "text"
    }

    val colList = ArrayList<ColumnDefinition>()
    colList.add(defTitle)
    colList.add(defYear)
    colList.add(defReleaseDate)
    colList.add(defPlot)

    // Set the keys.
    val yearKey = PartitionKey {
        name = "year"
    }

    val titleKey = PartitionKey {
        name = "title"
    }

    val keyList = ArrayList<PartitionKey>()
    keyList.add(yearKey)
    keyList.add(titleKey)

    val schemaDefinitionOb = SchemaDefinition {
        partitionKeys = keyList
        allColumns = colList
    }

    val timeRecovery = PointInTimeRecovery {
        status = PointInTimeRecoveryStatus.Enabled
    }

    val tableRequest = CreateTableRequest {
        keyspaceName = keySpaceVal
```

```
        tableName = tableNameVal
        schemaDefinition = schemaDefinitionOb
        pointInTimeRecovery = timeRecovery
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createTable(tableRequest)
        println("The table ARN is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)
```

```
    def create_table(self, table_name):
        """
        Creates a table in the  keyspace.
        The table is created with a schema for storing movie data
        and has point-in-time recovery enabled.

        :param table_name: The name to give the table.
        :return: The ARN of the new table.
        """
        try:
            response = self.keyspaces_client.create_table(
                keyspaceName=self.ks_name,
                tableName=table_name,
                schemaDefinition={
                    "allColumns": [
                        {"name": "title", "type": "text"},
                        {"name": "year", "type": "int"},
                        {"name": "release_date", "type": "timestamp"},
                        {"name": "plot", "type": "text"},
                    ],
                    "partitionKeys": [{"name": "year"}, {"name": "title"}],
                },
                pointInTimeRecovery={"status": "ENABLED"},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["resourceArn"]
```

- Para obter detalhes da API, consulte a CreateTableReferência da API AWSSDK for Python (Boto3).

Exclua um espaço de chaves do Amazon Keyspaces usando um SDK AWS

O exemplo de código a seguir mostra como excluir um espaço de chaves do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete an existing keyspace.
/// </summary>
/// <param name="keyspaceName"></param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> DeleteKeyspace(string keyspaceName)
{
    var response = await _amazonKeyspaces.DeleteKeyspaceAsync(
        new DeleteKeyspaceRequest { KeyspaceName = keyspaceName });
    return response.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteKeyspacea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteKeyspace(KeyspacesClient keyClient, String
keyspaceName) {
       try {
           DeleteKeyspaceRequest deleteKeyspaceRequest =
DeleteKeyspaceRequest.builder()
                   .keyspaceName(keyspaceName)
                   .build();

           keyClient.deleteKeyspace(deleteKeyspaceRequest);

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteKeyspacea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKeyspace(keyspaceNameVal: String?) {
    val deleteKeyspaceRequest = DeleteKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteKeyspace(deleteKeyspaceRequest)
    }
}
```

- Para obter detalhes da API, consulte a DeleteKeyspacereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)
```

```
    def delete_keyspace(self):
        """
        Deletes the keyspace.
        """
        try:
            self.keyspaces_client.delete_keyspace(keyspaceName=self.ks_name)
            self.ks_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteKeyspaceReferência da API AWSSDK for Python (Boto3).

Exclua uma tabela do Amazon Keyspaces usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma tabela do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTable(string keyspaceName, string tableName)
    {
        var response = await _amazonKeyspaces.DeleteTableAsync(
            new DeleteTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteTable(KeyspacesClient keyClient, String
keyspaceName, String tableName) {
        try {
            DeleteTableRequest tableRequest = DeleteTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            keyClient.deleteTable(tableRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteTable(keyspaceNameVal: String?, tableNameVal: String?) {
    val tableRequest = DeleteTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteTable(tableRequest)
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def delete_table(self):
        """
        Deletes the table from the keyspace.
        """
        try:
            self.keyspaces_client.delete_table(
                keyspaceName=self.ks_name, tableName=self.table_name
            )
            self.table_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Obtenha dados sobre um keyspace do Amazon Keyspaces usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados sobre um keyspace do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get data about a keyspace.
/// </summary>
/// <param name="keyspaceName">The name of the keyspace.</param>
/// <returns>The Amazon Resource Name (ARN) of the keyspace.</returns>
public async Task<string> GetKeyspace(string keyspaceName)
{
    var response = await _amazonKeyspaces.GetKeyspaceAsync(
        new GetKeyspaceRequest { KeyspaceName = keyspaceName });
    return response.ResourceArn;
}
```

- Para obter detalhes da API, consulte GetKeyspacea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkKeyspaceExistence(KeyspacesClient keyClient, String
keyspaceName) {
       try {
           GetKeyspaceRequest keyspaceRequest = GetKeyspaceRequest.builder()
                   .keyspaceName(keyspaceName)
                   .build();

           GetKeyspaceResponse response =
keyClient.getKeyspace(keyspaceRequest);
           String name = response.keyspaceName();
           System.out.println("The " + name + " KeySpace is ready");

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetKeyspacea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkKeyspaceExistence(keyspaceNameVal: String?) {
    val keyspaceRequest = GetKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response: GetKeyspaceResponse =
 keyClient.getKeyspace(keyspaceRequest)
        val name = response.keyspaceName
        println("The $name KeySpace is ready")
    }
}
```

- Para obter detalhes da API, consulte a GetKeyspacereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
```

```
        return cls(keyspaces_client)


    def exists_keyspace(self, name):
        """
        Checks whether a keyspace exists.

        :param name: The name of the keyspace to look up.
        :return: True when the keyspace exists. Otherwise, False.
        """
        try:
            response = self.keyspaces_client.get_keyspace(keyspaceName=name)
            self.ks_name = response["keyspaceName"]
            self.ks_arn = response["resourceArn"]
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Keyspace %s does not exist.", name)
                exists = False
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return exists
```

- Para obter detalhes da API, consulte a GetKeyspaceReferência da API AWSSDK for Python (Boto3).

Obtenha dados sobre uma tabela do Amazon Keyspaces usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados sobre uma tabela do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the Amazon Keyspaces table.</param>
    /// <returns>The response containing data about the table.</returns>
    public async Task<GetTableResponse> GetTable(string keyspaceName, string
tableName)
    {
        var response = await _amazonKeyspaces.GetTableAsync(
            new GetTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response;
    }
```

- Para obter detalhes da API, consulte GetTablea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkTable(KeyspacesClient keyClient, String keyspaceName,
String tableName)
           throws InterruptedException {
       try {
           boolean tableStatus = false;
           String status;
           GetTableResponse response = null;
           GetTableRequest tableRequest = GetTableRequest.builder()
                   .keyspaceName(keyspaceName)
                   .tableName(tableName)
                   .build();

           while (!tableStatus) {
               response = keyClient.getTable(tableRequest);
               status = response.statusAsString();
               System.out.println(". The table status is " + status);

               if (status.compareTo("ACTIVE") == 0) {
                   tableStatus = true;
               }
               Thread.sleep(500);
           }

           List<ColumnDefinition> cols =
response.schemaDefinition().allColumns();
           for (ColumnDefinition def : cols) {
               System.out.println("The column name is " + def.name());
               System.out.println("The column type is " + def.type());
           }

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetTablea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println(". The table status is $status")
            if (status.compareTo("ACTIVE") == 0) {
                tableStatus = true
            }
            delay(500)
        }
        val cols: List<ColumnDefinition>? =
 response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a GetTablereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def get_table(self, table_name):
        """
        Gets data about a table in the keyspace.

        :param table_name: The name of the table to look up.
        :return: Data about the table.
        """
        try:
            response = self.keyspaces_client.get_table(
                keyspaceName=self.ks_name, tableName=table_name
            )
            self.table_name = table_name
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Table %s does not exist.", table_name)
                self.table_name = None
                response = None
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response
```

- Para obter detalhes da API, consulte a GetTableReferência da API AWSSDK for Python (Boto3).

Listar os espaços de chaves do Amazon Keyspaces usando um SDK AWS

O exemplo de código a seguir mostra como listar espaços de chaves do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Lists all keyspaces for the account.
```

```
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task ListKeyspaces()
    {
        var paginator = _amazonKeyspaces.Paginators.ListKeyspaces(new
ListKeyspacesRequest());

        Console.WriteLine("{0, -30}\t{1}", "Keyspace name", "Keyspace ARN");
        Console.WriteLine(new string('-', Console.WindowWidth));
        await foreach (var keyspace in paginator.Keyspaces)
        {

Console.WriteLine($"{keyspace.KeyspaceName,-30}\t{keyspace.ResourceArn}");
        }
    }
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listKeyspacesPaginator(KeyspacesClient keyClient) {
        try {
            ListKeyspacesRequest keyspacesRequest =
ListKeyspacesRequest.builder()
                    .maxResults(10)
                    .build();

            ListKeyspacesIterable listRes =
keyClient.listKeyspacesPaginator(keyspacesRequest);
            listRes.stream()
```

```
                    .flatMap(r -> r.keyspaces().stream())
                    .forEach(content -> System.out.println(" Name: " +
 content.keyspaceName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listKeyspacesPaginator() {
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listKeyspacesPaginated(ListKeyspacesRequest {})
            .transform { it.keyspaces?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name: ${obj.keyspaceName}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListKeyspacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def list_keyspaces(self, limit):
        """
        Lists the keyspaces in your account.

        :param limit: The maximum number of keyspaces to list.
        """
        try:
            ks_paginator = self.keyspaces_client.get_paginator("list_keyspaces")
            for page in ks_paginator.paginate(PaginationConfig={"MaxItems":
 limit}):
                for ks in page["keyspaces"]:
                    print(ks["keyspaceName"])
                    print(f"\t{ks['resourceArn']}")
```

```
        except ClientError as err:
            logger.error(
                "Couldn't list keyspaces. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListKeyspacesReferência da API AWSSDK for Python (Boto3).

Listar tabelas do Amazon Keyspaces em um keyspace usando um SDK da AWS

Os exemplos de código a seguir mostram como listar tabelas do Amazon Keyspaces em um keyspace.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Lists the Amazon Keyspaces tables in a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>A list of TableSummary objects.</returns>
    public async Task<List<TableSummary>> ListTables(string keyspaceName)
    {
```

```
        var response = await _amazonKeyspaces.ListTablesAsync(new
ListTablesRequest { KeyspaceName = keyspaceName });
        response.Tables.ForEach(table =>
        {

Console.WriteLine($"{table.KeyspaceName}\t{table.TableName}\t{table.ResourceArn}");
        });

        return response.Tables;
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listTables(KeyspacesClient keyClient, String keyspaceName)
{
        try {
            ListTablesRequest tablesRequest = ListTablesRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            ListTablesIterable listRes =
keyClient.listTablesPaginator(tablesRequest);
            listRes.stream()
                    .flatMap(r -> r.tables().stream())
                    .forEach(content -> System.out.println(" ARN: " +
content.resourceArn() +
                            " Table name: " + content.tableName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTables(keyspaceNameVal: String?) {
    val tablesRequest = ListTablesRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listTablesPaginated(tablesRequest)
            .transform { it.tables?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(
                    " ARN: " + obj.resourceArn.toString() +
                        " Table name: " + obj.tableName
                )
            }
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def list_tables(self):
        """
        Lists the tables in the keyspace.
        """
        try:
            table_paginator = self.keyspaces_client.get_paginator("list_tables")
            for page in table_paginator.paginate(keyspaceName=self.ks_name):
                for table in page["tables"]:
                    print(table["tableName"])
                    print(f"\t{table['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list tables in keyspace %s. Here's why: %s: %s",
```

```
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListTablesReferência da API AWSSDK for Python (Boto3).

Restaure uma tabela do Amazon Keyspaces para um ponto no tempo usando um SDK AWS

Os exemplos de código a seguir mostram como restaurar uma tabela do Amazon Keyspaces para um momento específico.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Restores the specified table to the specified point in time.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to restore.</param>
    /// <param name="timestamp">The time to which the table will be restored.</
param>
```

```
    /// <returns>The Amazon Resource Name (ARN) of the restored table.</returns>
    public async Task<string> RestoreTable(string keyspaceName, string tableName,
string restoredTableName, DateTime timestamp)
    {
        var request = new RestoreTableRequest
        {
            RestoreTimestamp = timestamp,
            SourceKeyspaceName = keyspaceName,
            SourceTableName = tableName,
            TargetKeyspaceName = keyspaceName,
            TargetTableName = restoredTableName
        };

        var response = await _amazonKeyspaces.RestoreTableAsync(request);
        return response.RestoredTableARN;
    }
```

- Para obter detalhes da API, consulte RestoreTablea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void restoreTable(KeyspacesClient keyClient, String
keyspaceName, ZonedDateTime utc) {
        try {
            Instant myTime = utc.toInstant();
            RestoreTableRequest restoreTableRequest =
RestoreTableRequest.builder()
                    .restoreTimestamp(myTime)
                    .sourceTableName("Movie")
                    .targetKeyspaceName(keyspaceName)
                    .targetTableName("MovieRestore")
                    .sourceKeyspaceName(keyspaceName)
```

```
                    .build();

            RestoreTableResponse response =
 keyClient.restoreTable(restoreTableRequest);
            System.out.println("The ARN of the restored table is " +
 response.restoredTableARN());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte RestoreTablea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun restoreTable(keyspaceName: String?, utc: ZonedDateTime) {
    // Create an aws.smithy.kotlin.runtime.time.Instant value.
    val timeStamp = aws.smithy.kotlin.runtime.time.Instant(utc.toInstant())
    val restoreTableRequest = RestoreTableRequest {
        restoreTimestamp = timeStamp
        sourceTableName = "MovieKotlin"
        targetKeyspaceName = keyspaceName
        targetTableName = "MovieRestore"
        sourceKeyspaceName = keyspaceName
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.restoreTable(restoreTableRequest)
        println("The ARN of the restored table is ${response.restoredTableArn}")
```

```
    }
}
```

- Para obter detalhes da API, consulte a RestoreTablereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def restore_table(self, restore_timestamp):
        """
        Restores the table to a previous point in time. The table is restored
        to a new table in the same keyspace.

        :param restore_timestamp: The point in time to restore the table. This
 time
```

```
                                must be in UTC format.
        :return: The name of the restored table.
        """
        try:
            restored_table_name = f"{self.table_name}_restored"
            self.keyspaces_client.restore_table(
                sourceKeyspaceName=self.ks_name,
                sourceTableName=self.table_name,
                targetKeyspaceName=self.ks_name,
                targetTableName=restored_table_name,
                restoreTimestamp=restore_timestamp,
            )
        except ClientError as err:
            logger.error(
                "Couldn't restore table %s. Here's why: %s: %s",
                restore_timestamp,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return restored_table_name
```

- Para obter detalhes da API, consulte a RestoreTableReferência da API AWSSDK for Python (Boto3).

Atualize uma tabela do Amazon Keyspaces usando um SDK da AWS

Os exemplos de código a seguir mostram como atualizar um item em uma tabela do Amazon Keyspaces.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar espaços de chaves e tabelas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Updates the movie table to add a boolean column named watched.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to change.</param>
    /// <returns>The Amazon Resource Name (ARN) of the updated table.</returns>
    public async Task<string> UpdateTable(string keyspaceName, string tableName)
    {
        var newColumn = new ColumnDefinition { Name = "watched", Type =
"boolean" };
        var request = new UpdateTableRequest
        {
            KeyspaceName = keyspaceName,
            TableName = tableName,
            AddColumns = new List<ColumnDefinition> { newColumn }
        };
        var response = await _amazonKeyspaces.UpdateTableAsync(request);
        return response.ResourceArn;
    }
```

- Para obter detalhes da API, consulte UpdateTablea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void updateTable(KeyspacesClient keyClient, String keySpace,
String tableName) {
       try {
           ColumnDefinition def = ColumnDefinition.builder()
                   .name("watched")
                   .type("boolean")
                   .build();

           UpdateTableRequest tableRequest = UpdateTableRequest.builder()
                   .keyspaceName(keySpace)
                   .tableName(tableName)
                   .addColumns(def)
                   .build();

           keyClient.updateTable(tableRequest);

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte UpdateTablea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateTable(keySpace: String?, tableNameVal: String?) {
    val def = ColumnDefinition {
        name = "watched"
        type = "boolean"
    }

    val tableRequest = UpdateTableRequest {
        keyspaceName = keySpace
        tableName = tableNameVal
        addColumns = listOf(def)
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.updateTable(tableRequest)
    }
}
```

- Para obter detalhes da API, consulte a UpdateTablereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def update_table(self):
        """
        Updates the schema of the table.

        This example updates a table of movie data by adding a new column
        that tracks whether the movie has been watched.
        """
        try:
            self.keyspaces_client.update_table(
                keyspaceName=self.ks_name,
                tableName=self.table_name,
                addColumns=[{"name": "watched", "type": "boolean"}],
            )
        except ClientError as err:
            logger.error(
                "Couldn't update table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a UpdateTableReferência da API AWSSDK for Python (Boto3).

Cenários do Amazon Keyspaces com SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Keyspaces (para Apache Cassandra) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar tabelas e espaços de chaves do Amazon Keyspaces usando um SDK AWS

Comece a usar tabelas e espaços de chaves do Amazon Keyspaces usando um SDK AWS

Os exemplos de código a seguir mostram como:

- Crie um espaço de chaves e uma tabela. O esquema da tabela contém dados do filme e tem a point-in-time recuperação ativada.
- Conectar-se ao espaço de chaves usando uma conexão TLS segura com autenticação SigV4.
- Consulte a tabela. Adicionar recuperar e atualizar dados do filme.
- Atualizar tabela. Adicionar uma coluna para rastrear os filmes assistidos.
- Restaurar a tabela ao estado anterior e limpar os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using System.Security.Cryptography.X509Certificates;
global using Amazon.Keyspaces;
global using Amazon.Keyspaces.Model;
global using KeyspacesActions;
global using KeyspacesScenario;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;
global using Newtonsoft.Json;


namespace KeyspacesBasics;

/// <summary>
/// Amazon Keyspaces (for Apache Cassandra) scenario. Shows some of the basic
/// actions performed with Amazon Keyspaces.
/// </summary>
public class KeyspacesBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonKeyspaces>()
            .AddTransient<KeyspacesWrapper>()
            .AddTransient<CassandraWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<KeyspacesBasics>();
```

```
        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var keyspacesWrapper =
host.Services.GetRequiredService<KeyspacesWrapper>();
        var uiMethods = new UiMethods();

        var keyspaceName = configuration["KeyspaceName"];
        var tableName = configuration["TableName"];

        bool success; // Used to track the results of some operations.

        uiMethods.DisplayOverview();
        uiMethods.PressEnter();

        // Create the keyspace.
        var keyspaceArn = await keyspacesWrapper.CreateKeyspace(keyspaceName);

        // Wait for the keyspace to be available. GetKeyspace results in a
        // resource not found error until it is ready for use.
        try
        {
            var getKeyspaceArn = "";
            Console.Write($"Created {keyspaceName}. Waiting for it to become
available. ");
            do
            {
                getKeyspaceArn = await
keyspacesWrapper.GetKeyspace(keyspaceName);
                Console.Write(". ");
            } while (getKeyspaceArn != keyspaceArn);
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine("Waiting for keyspace to be created.");
        }

        Console.WriteLine($"\nThe keyspace {keyspaceName} is ready for use.");
```

```
        uiMethods.PressEnter();

        // Create the table.
        // First define the schema.
        var allColumns = new List<ColumnDefinition>
        {
            new ColumnDefinition { Name = "title", Type = "text" },
            new ColumnDefinition { Name = "year", Type = "int" },
            new ColumnDefinition { Name = "release_date", Type = "timestamp" },
            new ColumnDefinition { Name = "plot", Type = "text" },
        };

        var partitionKeys = new List<PartitionKey>
        {
            new PartitionKey { Name = "year", },
            new PartitionKey { Name = "title" },
        };

        var tableSchema = new SchemaDefinition
        {
            AllColumns = allColumns,
            PartitionKeys = partitionKeys,
        };

        var tableArn = await keyspacesWrapper.CreateTable(keyspaceName,
tableSchema, tableName);

        // Wait for the table to be active.
        try
        {
            var resp = new GetTableResponse();
            Console.Write("Waiting for the new table to be active. ");
            do
            {
                try
                {
                    resp = await keyspacesWrapper.GetTable(keyspaceName,
tableName);
                    Console.Write(".");
                }
                catch (ResourceNotFoundException)
                {
                    Console.Write(".");
                }
```

```
            } while (resp.Status != TableStatus.ACTIVE);

            // Display the table's schema.
            Console.WriteLine($"\nTable {tableName} has been created in
{keyspaceName}");
            Console.WriteLine("Let's take a look at the schema.");
            uiMethods.DisplayTitle("All columns");
            resp.SchemaDefinition.AllColumns.ForEach(column =>
            {
                Console.WriteLine($"{column.Name,-40}\t{column.Type,-20}");
            });

            uiMethods.DisplayTitle("Cluster keys");
            resp.SchemaDefinition.ClusteringKeys.ForEach(clusterKey =>
            {

Console.WriteLine($"{clusterKey.Name,-40}\t{clusterKey.OrderBy,-20}");
            });

            uiMethods.DisplayTitle("Partition keys");
            resp.SchemaDefinition.PartitionKeys.ForEach(partitionKey =>
            {
                Console.WriteLine($"{partitionKey.Name}");
            });

            uiMethods.PressEnter();
        }
        catch (ResourceNotFoundException ex)
        {
            Console.WriteLine($"Error: {ex.Message}");
        }

        // Access Apache Cassandra using the Cassandra drive for C#.
        var cassandraWrapper =
host.Services.GetRequiredService<CassandraWrapper>();
        var movieFilePath = configuration["MovieFile"];

        Console.WriteLine("Let's add some movies to the table we created.");
        var inserted = await cassandraWrapper.InsertIntoMovieTable(keyspaceName,
tableName, movieFilePath);

        uiMethods.PressEnter();

        Console.WriteLine("Added the following movies to the table:");
```

```
        var rows = await cassandraWrapper.GetMovies(keyspaceName, tableName);
        uiMethods.DisplayTitle("All Movies");

        foreach (var row in rows)
        {
            var title = row.GetValue<string>("title");
            var year = row.GetValue<int>("year");
            var plot = row.GetValue<string>("plot");
            var release_date = row.GetValue<DateTime>("release_date");
            Console.WriteLine($"{release_date}\t{title}\t{year}\n{plot}");
            Console.WriteLine(uiMethods.SepBar);
        }

        // Update the table schema
        uiMethods.DisplayTitle("Update table schema");
        Console.WriteLine("Now we will update the table to add a boolean field
 called watched.");

        // First save the current time as a UTC Date so the original
        // table can be restored later.
        var timeChanged = DateTime.UtcNow;

        // Now update the schema.
        var resourceArn = await keyspacesWrapper.UpdateTable(keyspaceName,
 tableName);
        uiMethods.PressEnter();

        Console.WriteLine("Now let's mark some of the movies as watched.");

        // Pick some files to mark as watched.
        var movieToWatch = rows[2].GetValue<string>("title");
        var watchedMovieYear = rows[2].GetValue<int>("year");
        var changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
 tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[6].GetValue<string>("title");
        watchedMovieYear = rows[6].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
 tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[9].GetValue<string>("title");
        watchedMovieYear = rows[9].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
 tableName, movieToWatch, watchedMovieYear);
```

```
        movieToWatch = rows[10].GetValue<string>("title");
        watchedMovieYear = rows[10].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[13].GetValue<string>("title");
        watchedMovieYear = rows[13].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        uiMethods.DisplayTitle("Watched movies");
        Console.WriteLine("These movies have been marked as watched:");
        rows = await cassandraWrapper.GetWatchedMovies(keyspaceName, tableName);
        foreach (var row in rows)
        {
            var title = row.GetValue<string>("title");
            var year = row.GetValue<int>("year");
            Console.WriteLine($"{title,-40}\t{year,8}");
        }
        uiMethods.PressEnter();

        Console.WriteLine("We can restore the table to its previous state but
that can take up to 20 minutes to complete.");
        string answer;
        do
        {
            Console.WriteLine("Do you want to restore the table? (y/n)");
            answer = Console.ReadLine();
        } while (answer.ToLower() != "y" && answer.ToLower() != "n");

        if (answer == "y")
        {
            var restoredTableName = $"{tableName}_restored";
            var restoredTableArn = await keyspacesWrapper.RestoreTable(
                keyspaceName,
                tableName,
                restoredTableName,
                timeChanged);
            // Loop and call GetTable until the table is gone. Once it has been
            // deleted completely, GetTable will raise a
ResourceNotFoundException.
            bool wasRestored = false;
```

```
            try
            {
                do
                {
                    var resp = await keyspacesWrapper.GetTable(keyspaceName,
restoredTableName);
                    wasRestored = (resp.Status == TableStatus.ACTIVE);
                } while (!wasRestored);
            }
            catch (ResourceNotFoundException)
            {
                // If the restored table raised an error, it isn't
                // ready yet.
                Console.Write(".");
            }
        }

        uiMethods.DisplayTitle("Clean up resources.");

        // Delete the table.
        success = await keyspacesWrapper.DeleteTable(keyspaceName, tableName);

        Console.WriteLine($"Table {tableName} successfully deleted from
{keyspaceName}.");
        Console.WriteLine("Waiting for the table to be removed completely. ");

        // Loop and call GetTable until the table is gone. Once it has been
        // deleted completely, GetTable will raise a ResourceNotFoundException.
        bool wasDeleted = false;

        try
        {
            do
            {
                var resp = await keyspacesWrapper.GetTable(keyspaceName,
tableName);
            } while (!wasDeleted);
        }
        catch (ResourceNotFoundException ex)
        {
            wasDeleted = true;
            Console.WriteLine($"{ex.Message} indicates that the table has been
deleted.");
        }
```

```
        // Delete the keyspace.
        success = await keyspacesWrapper.DeleteKeyspace(keyspaceName);
        Console.WriteLine("The keyspace has been deleted and the demo is now
 complete.");
    }
}
```

```
namespace KeyspacesActions;

/// <summary>
/// Performs Amazon Keyspaces (for Apache Cassandra) actions.
/// </summary>
public class KeyspacesWrapper
{
    private readonly IAmazonKeyspaces _amazonKeyspaces;

    /// <summary>
    /// Constructor for the KeyspaceWrapper.
    /// </summary>
    /// <param name="amazonKeyspaces">An Amazon Keyspaces client object.</param>
    public KeyspacesWrapper(IAmazonKeyspaces amazonKeyspaces)
    {
        _amazonKeyspaces = amazonKeyspaces;
    }

    /// <summary>
    /// Create a new keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name for the new keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new keyspace.</returns>
    public async Task<string> CreateKeyspace(string keyspaceName)
    {
        var response =
            await _amazonKeyspaces.CreateKeyspaceAsync(
                new CreateKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.ResourceArn;
    }


    /// <summary>
```

```
    /// Create a new Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace where the table will be
created.</param>
    /// <param name="schema">The schema for the new table.</param>
    /// <param name="tableName">The name of the new table.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new table.</returns>
    public async Task<string> CreateTable(string keyspaceName, SchemaDefinition
schema, string tableName)
    {
        var request = new CreateTableRequest
        {
            KeyspaceName = keyspaceName,
            SchemaDefinition = schema,
            TableName = tableName,
            PointInTimeRecovery = new PointInTimeRecovery { Status =
PointInTimeRecoveryStatus.ENABLED }
        };

        var response = await _amazonKeyspaces.CreateTableAsync(request);
        return response.ResourceArn;
    }


    /// <summary>
    /// Delete an existing keyspace.
    /// </summary>
    /// <param name="keyspaceName"></param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.DeleteKeyspaceAsync(
            new DeleteKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTable(string keyspaceName, string tableName)
```

```
    {
        var response = await _amazonKeyspaces.DeleteTableAsync(
            new DeleteTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Get data about a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the keyspace.</returns>
    public async Task<string> GetKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.GetKeyspaceAsync(
            new GetKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.ResourceArn;
    }


    /// <summary>
    /// Get information about an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the Amazon Keyspaces table.</param>
    /// <returns>The response containing data about the table.</returns>
    public async Task<GetTableResponse> GetTable(string keyspaceName, string
tableName)
    {
        var response = await _amazonKeyspaces.GetTableAsync(
            new GetTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response;
    }


    /// <summary>
    /// Lists all keyspaces for the account.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task ListKeyspaces()
    {
```

```
        var paginator = _amazonKeyspaces.Paginators.ListKeyspaces(new
 ListKeyspacesRequest());

        Console.WriteLine("{0, -30}\t{1}", "Keyspace name", "Keyspace ARN");
        Console.WriteLine(new string('-', Console.WindowWidth));
        await foreach (var keyspace in paginator.Keyspaces)
        {

 Console.WriteLine($"{keyspace.KeyspaceName,-30}\t{keyspace.ResourceArn}");
        }
    }


    /// <summary>
    /// Lists the Amazon Keyspaces tables in a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>A list of TableSummary objects.</returns>
    public async Task<List<TableSummary>> ListTables(string keyspaceName)
    {
        var response = await _amazonKeyspaces.ListTablesAsync(new
 ListTablesRequest { KeyspaceName = keyspaceName });
        response.Tables.ForEach(table =>
        {

 Console.WriteLine($"{table.KeyspaceName}\t{table.TableName}\t{table.ResourceArn}");
        });

        return response.Tables;
    }


    /// <summary>
    /// Restores the specified table to the specified point in time.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to restore.</param>
    /// <param name="timestamp">The time to which the table will be restored.</
param>
    /// <returns>The Amazon Resource Name (ARN) of the restored table.</returns>
    public async Task<string> RestoreTable(string keyspaceName, string tableName,
 string restoredTableName, DateTime timestamp)
    {
        var request = new RestoreTableRequest
```

```
        {
            RestoreTimestamp = timestamp,
            SourceKeyspaceName = keyspaceName,
            SourceTableName = tableName,
            TargetKeyspaceName = keyspaceName,
            TargetTableName = restoredTableName
        };

        var response = await _amazonKeyspaces.RestoreTableAsync(request);
        return response.RestoredTableARN;
    }


    /// <summary>
    /// Updates the movie table to add a boolean column named watched.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to change.</param>
    /// <returns>The Amazon Resource Name (ARN) of the updated table.</returns>
    public async Task<string> UpdateTable(string keyspaceName, string tableName)
    {
        var newColumn = new ColumnDefinition { Name = "watched", Type =
 "boolean" };
        var request = new UpdateTableRequest
        {
            KeyspaceName = keyspaceName,
            TableName = tableName,
            AddColumns = new List<ColumnDefinition> { newColumn }
        };
        var response = await _amazonKeyspaces.UpdateTableAsync(request);
        return response.ResourceArn;
    }

}
```

```
using System.Net;
using Cassandra;

namespace KeyspacesScenario;

/// <summary>
```

```
/// Class to perform CRUD methods on an Amazon Keyspaces (for Apache Cassandra)
 database.
///
/// NOTE: This sample uses a plain text authenticator for example purposes only.
/// Recommended best practice is to use a SigV4 authentication plugin, if
 available.
/// </summary>
public class CassandraWrapper
{
    private readonly IConfiguration _configuration;
    private readonly string _localPathToFile;
    private const string _certLocation = "https://certs.secureserver.net/
repository/sf-class2-root.crt";
    private const string _certFileName = "sf-class2-root.crt";
    private readonly X509Certificate2Collection _certCollection;
    private X509Certificate2 _amazoncert;
    private Cluster _cluster;

    // User name and password for the service.
    private string _userName = null!;
    private string _pwd = null!;

    public CassandraWrapper()
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        _localPathToFile = Path.GetTempPath();

        // Get the Starfield digital certificate and save it locally.
        var client = new WebClient();
        client.DownloadFile(_certLocation, $"{_localPathToFile}/
{_certFileName}");

        //var httpClient = new HttpClient();
        //var httpResult = httpClient.Get(fileUrl);
        //using var resultStream = await httpResult.Content.ReadAsStreamAsync();
        //using var fileStream = File.Create(pathToSave);
        //resultStream.CopyTo(fileStream);
```

```
        _certCollection = new X509Certificate2Collection();
        _amazoncert = new X509Certificate2($"{_localPathToFile}/
{_certFileName}");

        // Get the user name and password stored in the configuration file.
        _userName = _configuration["UserName"]!;
        _pwd = _configuration["Password"]!;

        // For a list of Service Endpoints for Amazon Keyspaces, see:
        // https://docs.aws.amazon.com/keyspaces/latest/devguide/
programmatic.endpoints.html
        var awsEndpoint = _configuration["ServiceEndpoint"];

        _cluster = Cluster.Builder()
            .AddContactPoints(awsEndpoint)
            .WithPort(9142)
            .WithAuthProvider(new PlainTextAuthProvider(_userName, _pwd))
            .WithSSL(new SSLOptions().SetCertificateCollection(_certCollection))
            .WithQueryOptions(
                new QueryOptions()
                    .SetConsistencyLevel(ConsistencyLevel.LocalQuorum)
                    .SetSerialConsistencyLevel(ConsistencyLevel.LocalSerial))
            .Build();
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the Apache Cassandra table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A list of movie objects.</returns>
    public List<Movie> ImportMoviesFromJson(string movieFileName, int numToImport
 = 0)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();

        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);
```

```
        // If numToImport = 0, return all movies in the collection.
        if (numToImport == 0)
        {
            // Now return the entire list of movies.
            return allMovies;
        }
        else
        {
            // Now return the first numToImport entries.
            return allMovies.GetRange(0, numToImport);
        }
    }

    /// <summary>
    /// Insert movies into the movie table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="movieTableName">The Amazon Keyspaces table.</param>
    /// <param name="movieFilePath">The path to the resource file containing
    /// movie data to insert into the table.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> InsertIntoMovieTable(string keyspaceName, string
 movieTableName, string movieFilePath, int numToImport = 20)
    {
        // Get some movie data from the movies.json file
        var movies = ImportMoviesFromJson(movieFilePath, numToImport);

        var session = _cluster.Connect(keyspaceName);

        string insertCql;

        RowSet rs;

        // Now we insert the numToImport movies into the table.
        foreach (var movie in movies)
        {
            // Escape single quote characters in the plot.
            insertCql = $"INSERT INTO {keyspaceName}.{movieTableName}
 (title, year, release_date, plot) values($${movie.Title}$$, {movie.Year},
 '{movie.Info.Release_Date.ToString("yyyy-MM-dd")}', $${movie.Info.Plot}$$)";
            rs = await session.ExecuteAsync(new SimpleStatement(insertCql));
        }

        return true;
```

```
    }

    /// <summary>
    /// Gets all of the movies in the movies table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <returns>A list of row objects containing movie data.</returns>
    public async Task<List<Row>> GetMovies(string keyspaceName, string tableName)
    {
        var session = _cluster.Connect();
        RowSet rs;
        try
        {
            rs = await session.ExecuteAsync(new SimpleStatement($"SELECT * FROM
{keyspaceName}.{tableName}"));

            // Extract the row data from the returned RowSet.
            var rows = rs.GetRows().ToList();
            return rows;
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            return null!;
        }
    }

    /// <summary>
    /// Mark a movie in the movie table as watched.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <param name="title">The title of the movie to mark as watched.</param>
    /// <param name="year">The year the movie was released.</param>
    /// <returns>A set of rows containing the changed data.</returns>
    public async Task<List<Row>> MarkMovieAsWatched(string keyspaceName, string
tableName, string title, int year)
    {
        var session = _cluster.Connect();
        string updateCql = $"UPDATE {keyspaceName}.{tableName} SET watched=true
WHERE title = $${title}$$ AND year = {year};";
        var rs = await session.ExecuteAsync(new SimpleStatement(updateCql));
        var rows = rs.GetRows().ToList();
```

```
        return rows;
    }

    /// <summary>
    /// Retrieve the movies in the movies table where watched is true.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <returns>A list of row objects containing information about movies
    /// where watched is true.</returns>
    public async Task<List<Row>> GetWatchedMovies(string keyspaceName, string
 tableName)
    {
        var session = _cluster.Connect();
        RowSet rs;
        try
        {
            rs = await session.ExecuteAsync(new SimpleStatement($"SELECT
 title, year, plot FROM {keyspaceName}.{tableName} WHERE watched = true ALLOW
 FILTERING"));

            // Extract the row data from the returned RowSet.
            var rows = rs.GetRows().ToList();
            return rows;
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            return null!;
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable

- GetKeyspace
- GetTable
- ListKeyspaces
- ListTables
- RestoreTable
- UpdateTable

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * Before running this Java code example, you must create a
 * Java keystore (JKS) file and place it in your project's resources folder.
 *
 * This file is a secure file format used to hold certificate information for
 * Java applications. This is required to make a connection to Amazon Keyspaces.
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/keyspaces/latest/devguide/using_java_driver.html
 *
 * This Java example performs the following tasks:
 *
 * 1. Create a keyspace.
 * 2. Check for keyspace existence.
```

```
 * 3. List keyspaces using a paginator.
 * 4. Create a table with a simple movie data schema and enable point-in-time
 * recovery.
 * 5. Check for the table to be in an Active state.
 * 6. List all tables in the keyspace.
 * 7. Use a Cassandra driver to insert some records into the Movie table.
 * 8. Get all records from the Movie table.
 * 9. Get a specific Movie.
 * 10. Get a UTC timestamp for the current time.
 * 11. Update the table schema to add a ‘watched’ Boolean column.
 * 12. Update an item as watched.
 * 13. Query for items with watched = True.
 * 14. Restore the table back to the previous state using the timestamp.
 * 15. Check for completion of the restore action.
 * 16. Delete the table.
 * 17. Confirm that both tables are deleted.
 * 18. Delete the keyspace.
 */

public class ScenarioKeyspaces {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    /*
     * Usage:
     * fileName - The name of the JSON file that contains movie data. (Get this
 file
     * from the GitHub repo at resources/sample_file.)
     * keyspaceName - The name of the keyspace to create.
     */
    public static void main(String[] args) throws InterruptedException,
 IOException {
        String fileName = "<Replace with the JSON file that contains movie
 data>";
        String configFilePath = "C:\\AWS\\application.conf";
        String keyspaceName = "<Replace with the name of the keyspace to
 create>";
        String titleUpdate = "The Family";
        int yearUpdate = 2013;
        String tableName = "Movie";
        String tableNameRestore = "MovieRestore";
        Region region = Region.US_EAST_1;
        KeyspacesClient keyClient = KeyspacesClient.builder()
                .region(region)
```

```
                .build();

        DriverConfigLoader loader = DriverConfigLoader.fromFile(new
File(configFilePath));
        CqlSession session = CqlSession.builder()
                .withConfigLoader(loader)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Keyspaces example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create a keyspace.");
        createKeySpace(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        Thread.sleep(5000);
        System.out.println("2. Check for keyspace existence.");
        checkKeyspaceExistence(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. List keyspaces using a paginator.");
        listKeyspacesPaginator(keyClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Create a table with a simple movie data schema and
enable point-in-time recovery.");
        createTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Check for the table to be in an Active state.");
        Thread.sleep(6000);
        checkTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. List all tables in the keyspace.");
        listTables(keyClient, keyspaceName);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("7. Use a Cassandra driver to insert some records into
the Movie table.");
        Thread.sleep(6000);
        loadData(session, fileName, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Get all records from the Movie table.");
        getMovieData(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get a specific Movie.");
        getSpecificMovie(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a UTC timestamp for the current time.");
        ZonedDateTime utc = ZonedDateTime.now(ZoneOffset.UTC);
        System.out.println("DATETIME = " + Date.from(utc.toInstant()));
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Update the table schema to add a watched Boolean
column.");
        updateTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Update an item as watched.");
        Thread.sleep(10000); // Wait 10 secs for the update.
        updateRecord(session, keyspaceName, titleUpdate, yearUpdate);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Query for items with watched = True.");
        getWatchedData(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Restore the table back to the previous state
using the timestamp.");
```

```
        System.out.println("Note that the restore operation can take up to 20
minutes.");
        restoreTable(keyClient, keyspaceName, utc);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Check for completion of the restore action.");
        Thread.sleep(5000);
        checkRestoredTable(keyClient, keyspaceName, "MovieRestore");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete both tables.");
        deleteTable(keyClient, keyspaceName, tableName);
        deleteTable(keyClient, keyspaceName, tableNameRestore);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Confirm that both tables are deleted.");
        checkTableDelete(keyClient, keyspaceName, tableName);
        checkTableDelete(keyClient, keyspaceName, tableNameRestore);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Delete the keyspace.");
        deleteKeyspace(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The scenario has completed successfully.");
        System.out.println(DASHES);
    }

    public static void deleteKeyspace(KeyspacesClient keyClient, String
keyspaceName) {
        try {
            DeleteKeyspaceRequest deleteKeyspaceRequest =
DeleteKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            keyClient.deleteKeyspace(deleteKeyspaceRequest);

        } catch (KeyspacesException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkTableDelete(KeyspacesClient keyClient, String
keyspaceName, String tableName)
            throws InterruptedException {
        try {
            String status;
            GetTableResponse response;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            // Keep looping until table cannot be found and a
ResourceNotFoundException is
            // thrown.
            while (true) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println(". The table status is " + status);
                Thread.sleep(500);
            }

        } catch (ResourceNotFoundException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println("The table is deleted");
    }

    public static void deleteTable(KeyspacesClient keyClient, String
keyspaceName, String tableName) {
        try {
            DeleteTableRequest tableRequest = DeleteTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            keyClient.deleteTable(tableRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }

    public static void checkRestoredTable(KeyspacesClient keyClient, String
keyspaceName, String tableName)
            throws InterruptedException {
        try {
            boolean tableStatus = false;
            String status;
            GetTableResponse response = null;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            while (!tableStatus) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println("The table status is " + status);

                if (status.compareTo("ACTIVE") == 0) {
                    tableStatus = true;
                }
                Thread.sleep(500);
            }

            List<ColumnDefinition> cols =
response.schemaDefinition().allColumns();
            for (ColumnDefinition def : cols) {
                System.out.println("The column name is " + def.name());
                System.out.println("The column type is " + def.type());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void restoreTable(KeyspacesClient keyClient, String
keyspaceName, ZonedDateTime utc) {
        try {
            Instant myTime = utc.toInstant();
```

```
            RestoreTableRequest restoreTableRequest =
RestoreTableRequest.builder()
                    .restoreTimestamp(myTime)
                    .sourceTableName("Movie")
                    .targetKeyspaceName(keyspaceName)
                    .targetTableName("MovieRestore")
                    .sourceKeyspaceName(keyspaceName)
                    .build();

            RestoreTableResponse response =
keyClient.restoreTable(restoreTableRequest);
            System.out.println("The ARN of the restored table is " +
response.restoredTableARN());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getWatchedData(CqlSession session, String keyspaceName) {
        ResultSet resultSet = session
                .execute("SELECT * FROM \"" + keyspaceName + "\".\"Movie\" WHERE
watched = true ALLOW FILTERING;");
        resultSet.forEach(item -> {
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }

    public static void updateRecord(CqlSession session, String keySpace, String
titleUpdate, int yearUpdate) {
        String sqlStatement = "UPDATE \"" + keySpace
                + "\".\"Movie\" SET watched=true WHERE title = :k0 AND year
= :k1;";
        BatchStatementBuilder builder =
BatchStatement.builder(DefaultBatchType.UNLOGGED);
        builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM);
        PreparedStatement preparedStatement = session.prepare(sqlStatement);
        builder.addStatement(preparedStatement.boundStatementBuilder()
                .setString("k0", titleUpdate)
                .setInt("k1", yearUpdate)
                .build());
```

```
        BatchStatement batchStatement = builder.build();
        session.execute(batchStatement);
    }

    public static void updateTable(KeyspacesClient keyClient, String keySpace,
 String tableName) {
        try {
            ColumnDefinition def = ColumnDefinition.builder()
                    .name("watched")
                    .type("boolean")
                    .build();

            UpdateTableRequest tableRequest = UpdateTableRequest.builder()
                    .keyspaceName(keySpace)
                    .tableName(tableName)
                    .addColumns(def)
                    .build();

            keyClient.updateTable(tableRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getSpecificMovie(CqlSession session, String keyspaceName)
 {
        ResultSet resultSet = session.execute(
                "SELECT * FROM \"" + keyspaceName + "\".\"Movie\" WHERE title =
 'The Family' ALLOW FILTERING ;");
        resultSet.forEach(item -> {
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }

    // Get records from the Movie table.
    public static void getMovieData(CqlSession session, String keyspaceName) {
        ResultSet resultSet = session.execute("SELECT * FROM \"" + keyspaceName +
 "\".\"Movie\";");
        resultSet.forEach(item -> {
```

```
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }

    // Load data into the table.
    public static void loadData(CqlSession session, String fileName, String
keySpace) throws IOException {
        String sqlStatement = "INSERT INTO \"" + keySpace + "\".\"Movie\" (title,
year, plot) values (:k0, :k1, :k2)";
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        while (iter.hasNext()) {

            // Add 20 movies to the table.
            if (t == 20)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String plot = currentNode.path("info").path("plot").toString();

            // Insert the data into the Amazon Keyspaces table.
            BatchStatementBuilder builder =
BatchStatement.builder(DefaultBatchType.UNLOGGED);
            builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM);
            PreparedStatement preparedStatement = session.prepare(sqlStatement);
            builder.addStatement(preparedStatement.boundStatementBuilder()
                    .setString("k0", title)
                    .setInt("k1", year)
                    .setString("k2", plot)
                    .build());

            BatchStatement batchStatement = builder.build();
            session.execute(batchStatement);
            t++;
        }
```

```
        System.out.println("You have added " + t + " records successfully!");
    }

    public static void listTables(KeyspacesClient keyClient, String keyspaceName)
{
        try {
            ListTablesRequest tablesRequest = ListTablesRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            ListTablesIterable listRes =
keyClient.listTablesPaginator(tablesRequest);
            listRes.stream()
                    .flatMap(r -> r.tables().stream())
                    .forEach(content -> System.out.println(" ARN: " +
content.resourceArn() +
                            " Table name: " + content.tableName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkTable(KeyspacesClient keyClient, String keyspaceName,
String tableName)
            throws InterruptedException {
        try {
            boolean tableStatus = false;
            String status;
            GetTableResponse response = null;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            while (!tableStatus) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println(". The table status is " + status);

                if (status.compareTo("ACTIVE") == 0) {
                    tableStatus = true;
                }
```

```
                Thread.sleep(500);
            }

            List<ColumnDefinition> cols =
 response.schemaDefinition().allColumns();
            for (ColumnDefinition def : cols) {
                System.out.println("The column name is " + def.name());
                System.out.println("The column type is " + def.type());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createTable(KeyspacesClient keyClient, String keySpace,
 String tableName) {
        try {
            // Set the columns.
            ColumnDefinition defTitle = ColumnDefinition.builder()
                    .name("title")
                    .type("text")
                    .build();

            ColumnDefinition defYear = ColumnDefinition.builder()
                    .name("year")
                    .type("int")
                    .build();

            ColumnDefinition defReleaseDate = ColumnDefinition.builder()
                    .name("release_date")
                    .type("timestamp")
                    .build();

            ColumnDefinition defPlot = ColumnDefinition.builder()
                    .name("plot")
                    .type("text")
                    .build();

            List<ColumnDefinition> colList = new ArrayList<>();
            colList.add(defTitle);
            colList.add(defYear);
            colList.add(defReleaseDate);
```

```
            colList.add(defPlot);

            // Set the keys.
            PartitionKey yearKey = PartitionKey.builder()
                    .name("year")
                    .build();

            PartitionKey titleKey = PartitionKey.builder()
                    .name("title")
                    .build();

            List<PartitionKey> keyList = new ArrayList<>();
            keyList.add(yearKey);
            keyList.add(titleKey);

            SchemaDefinition schemaDefinition = SchemaDefinition.builder()
                    .partitionKeys(keyList)
                    .allColumns(colList)
                    .build();

            PointInTimeRecovery timeRecovery = PointInTimeRecovery.builder()
                    .status(PointInTimeRecoveryStatus.ENABLED)
                    .build();

            CreateTableRequest tableRequest = CreateTableRequest.builder()
                    .keyspaceName(keySpace)
                    .tableName(tableName)
                    .schemaDefinition(schemaDefinition)
                    .pointInTimeRecovery(timeRecovery)
                    .build();

            CreateTableResponse response = keyClient.createTable(tableRequest);
            System.out.println("The table ARN is " + response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listKeyspacesPaginator(KeyspacesClient keyClient) {
        try {
            ListKeyspacesRequest keyspacesRequest =
ListKeyspacesRequest.builder()
```

```
                    .maxResults(10)
                    .build();

            ListKeyspacesIterable listRes =
keyClient.listKeyspacesPaginator(keyspacesRequest);
            listRes.stream()
                    .flatMap(r -> r.keyspaces().stream())
                    .forEach(content -> System.out.println(" Name: " +
content.keyspaceName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkKeyspaceExistence(KeyspacesClient keyClient, String
keyspaceName) {
        try {
            GetKeyspaceRequest keyspaceRequest = GetKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            GetKeyspaceResponse response =
keyClient.getKeyspace(keyspaceRequest);
            String name = response.keyspaceName();
            System.out.println("The " + name + " KeySpace is ready");

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createKeySpace(KeyspacesClient keyClient, String
keyspaceName) {
        try {
            CreateKeyspaceRequest keyspaceRequest =
CreateKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            CreateKeyspaceResponse response =
keyClient.createKeyspace(keyspaceRequest);
```

```
            System.out.println("The ARN of the KeySpace is " +
 response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable
  - UpdateTable

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.
```

```
 For more information, see the following documentation topic:

 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This example uses a secure file format to hold certificate information for
 Kotlin applications. This is required to make a connection to Amazon Keyspaces.
 For more information, see the following documentation topic:

 https://docs.aws.amazon.com/keyspaces/latest/devguide/using_java_driver.html

 This Kotlin example performs the following tasks:

 1. Create a keyspace.
 2. Check for keyspace existence.
 3. List keyspaces using a paginator.
 4. Create a table with a simple movie data schema and enable point-in-time
 recovery.
 5. Check for the table to be in an Active state.
 6. List all tables in the keyspace.
 7. Use a Cassandra driver to insert some records into the Movie table.
 8. Get all records from the Movie table.
 9. Get a specific Movie.
 10. Get a UTC timestamp for the current time.
 11. Update the table schema to add a 'watched' Boolean column.
 12. Update an item as watched.
 13. Query for items with watched = True.
 14. Restore the table back to the previous state using the timestamp.
 15. Check for completion of the restore action.
 16. Delete the table.
 17. Confirm that both tables are deleted.
 18. Delete the keyspace.
 */

/*
   Usage:
     fileName - The name of the JSON file that contains movie data. (Get this
 file from the GitHub repo at resources/sample_file.)
     keyspaceName - The name of the keyspace to create.
  */
val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main() {
    val fileName = "<Replace with the JSON file that contains movie data>"
    val keyspaceName = "<Replace with the name of the keyspace to create>"
```

```
    val titleUpdate = "The Family"
    val yearUpdate = 2013
    val tableName = "MovieKotlin"
    val tableNameRestore = "MovieRestore"

    val loader = DriverConfigLoader.fromClasspath("application.conf")
    val session = CqlSession.builder()
        .withConfigLoader(loader)
        .build()

    println(DASHES)
    println("Welcome to the Amazon Keyspaces example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create a keyspace.")
    createKeySpace(keyspaceName)
    println(DASHES)

    println(DASHES)
    delay(5000)
    println("2. Check for keyspace existence.")
    checkKeyspaceExistence(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("3. List keyspaces using a paginator.")
    listKeyspacesPaginator()
    println(DASHES)

    println(DASHES)
    println("4. Create a table with a simple movie data schema and enable point-
in-time recovery.")
    createTable(keyspaceName, tableName)
    println(DASHES)

    println(DASHES)
    println("5. Check for the table to be in an Active state.")
    delay(6000)
    checkTable(keyspaceName, tableName)
    println(DASHES)

    println(DASHES)
    println("6. List all tables in the keyspace.")
```

```
    listTables(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("7. Use a Cassandra driver to insert some records into the Movie
 table.")
    delay(6000)
    loadData(session, fileName, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("8. Get all records from the Movie table.")
    getMovieData(session, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("9. Get a specific Movie.")
    getSpecificMovie(session, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("10. Get a UTC timestamp for the current time.")
    val utc = ZonedDateTime.now(ZoneOffset.UTC)
    println("DATETIME = ${Date.from(utc.toInstant())}")
    println(DASHES)

    println(DASHES)
    println("11. Update the table schema to add a watched Boolean column.")
    updateTable(keyspaceName, tableName)
    println(DASHES)

    println(DASHES)
    println("12. Update an item as watched.")
    delay(10000) // Wait 10 seconds for the update.
    updateRecord(session, keyspaceName, titleUpdate, yearUpdate)
    println(DASHES)

    println(DASHES)
    println("13. Query for items with watched = True.")
    getWatchedData(session, keyspaceName)
    println(DASHES)

    println(DASHES)
```

```
    println("14. Restore the table back to the previous state using the
 timestamp.")
    println("Note that the restore operation can take up to 20 minutes.")
    restoreTable(keyspaceName, utc)
    println(DASHES)

    println(DASHES)
    println("15. Check for completion of the restore action.")
    delay(5000)
    checkRestoredTable(keyspaceName, "MovieRestore")
    println(DASHES)

    println(DASHES)
    println("16. Delete both tables.")
    deleteTable(keyspaceName, tableName)
    deleteTable(keyspaceName, tableNameRestore)
    println(DASHES)

    println(DASHES)
    println("17. Confirm that both tables are deleted.")
    checkTableDelete(keyspaceName, tableName)
    checkTableDelete(keyspaceName, tableNameRestore)
    println(DASHES)

    println(DASHES)
    println("18. Delete the keyspace.")
    deleteKeyspace(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("The scenario has completed successfully.")
    println(DASHES)
}

suspend fun deleteKeyspace(keyspaceNameVal: String?) {
    val deleteKeyspaceRequest = DeleteKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteKeyspace(deleteKeyspaceRequest)
    }
}
```

```
suspend fun checkTableDelete(keyspaceNameVal: String?, tableNameVal: String?) {
    var status: String
    var response: GetTableResponse
    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    try {
        KeyspacesClient { region = "us-east-1" }.use { keyClient ->
            // Keep looping until the table cannot be found and a
 ResourceNotFoundException is thrown.
            while (true) {
                response = keyClient.getTable(tableRequest)
                status = response.status.toString()
                println(". The table status is $status")
                delay(500)
            }
        }
    } catch (e: ResourceNotFoundException) {
        println(e.message)
    }
    println("The table is deleted")
}

suspend fun deleteTable(keyspaceNameVal: String?, tableNameVal: String?) {
    val tableRequest = DeleteTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteTable(tableRequest)
    }
}

suspend fun checkRestoredTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
```

```
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println("The table status is $status")

            if (status.compareTo("ACTIVE") == 0) {
                tableStatus = true
            }
            delay(500)
        }

        val cols = response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}

suspend fun restoreTable(keyspaceName: String?, utc: ZonedDateTime) {
    // Create an aws.smithy.kotlin.runtime.time.Instant value.
    val timeStamp = aws.smithy.kotlin.runtime.time.Instant(utc.toInstant())
    val restoreTableRequest = RestoreTableRequest {
        restoreTimestamp = timeStamp
        sourceTableName = "MovieKotlin"
        targetKeyspaceName = keyspaceName
        targetTableName = "MovieRestore"
        sourceKeyspaceName = keyspaceName
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.restoreTable(restoreTableRequest)
        println("The ARN of the restored table is ${response.restoredTableArn}")
    }
}

fun getWatchedData(session: CqlSession, keyspaceName: String) {
    val resultSet = session.execute("SELECT * FROM \"$keyspaceName\".
\"MovieKotlin\" WHERE watched = true ALLOW FILTERING;")
```

```
    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

fun updateRecord(session: CqlSession, keySpace: String, titleUpdate: String?,
 yearUpdate: Int) {
    val sqlStatement =
        "UPDATE \"$keySpace\".\"MovieKotlin\" SET watched=true WHERE title = :k0
 AND year = :k1;"
    val builder = BatchStatement.builder(DefaultBatchType.UNLOGGED)
    builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM)
    val preparedStatement = session.prepare(sqlStatement)
    builder.addStatement(
        preparedStatement.boundStatementBuilder()
            .setString("k0", titleUpdate)
            .setInt("k1", yearUpdate)
            .build()
    )
    val batchStatement = builder.build()
    session.execute(batchStatement)
}

suspend fun updateTable(keySpace: String?, tableNameVal: String?) {
    val def = ColumnDefinition {
        name = "watched"
        type = "boolean"
    }

    val tableRequest = UpdateTableRequest {
        keyspaceName = keySpace
        tableName = tableNameVal
        addColumns = listOf(def)
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.updateTable(tableRequest)
    }
}

fun getSpecificMovie(session: CqlSession, keyspaceName: String) {
    val resultSet =
```

```
        session.execute("SELECT * FROM \"$keyspaceName\".\"MovieKotlin\" WHERE
 title = 'The Family' ALLOW FILTERING ;")

    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

// Get records from the Movie table.
fun getMovieData(session: CqlSession, keyspaceName: String) {
    val resultSet = session.execute("SELECT * FROM \"$keyspaceName\".
\"MovieKotlin\";")
    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

// Load data into the table.
fun loadData(session: CqlSession, fileName: String, keySpace: String) {
    val sqlStatement =
        "INSERT INTO \"$keySpace\".\"MovieKotlin\" (title, year, plot) values
 (:k0, :k1, :k2)"
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()

        // Insert the data into the Amazon Keyspaces table.
        val builder = BatchStatement.builder(DefaultBatchType.UNLOGGED)
```

```
        builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM)
        val preparedStatement: PreparedStatement = session.prepare(sqlStatement)
        builder.addStatement(
            preparedStatement.boundStatementBuilder()
                .setString("k0", title)
                .setInt("k1", year)
                .setString("k2", info)
                .build()
        )

        val batchStatement = builder.build()
        session.execute(batchStatement)
        t++
    }
}

suspend fun listTables(keyspaceNameVal: String?) {
    val tablesRequest = ListTablesRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listTablesPaginated(tablesRequest)
            .transform { it.tables?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(
                    " ARN: " + obj.resourceArn.toString() +
                        " Table name: " + obj.tableName
                )
            }
    }
}

suspend fun checkTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
```

```
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println(". The table status is $status")
            if (status.compareTo("ACTIVE") == 0) {
                tableStatus = true
            }
            delay(500)
        }
        val cols: List<ColumnDefinition>? =
 response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}

suspend fun createTable(keySpaceVal: String?, tableNameVal: String?) {
    // Set the columns.
    val defTitle = ColumnDefinition {
        name = "title"
        type = "text"
    }

    val defYear = ColumnDefinition {
        name = "year"
        type = "int"
    }

    val defReleaseDate = ColumnDefinition {
        name = "release_date"
        type = "timestamp"
    }

    val defPlot = ColumnDefinition {
        name = "plot"
        type = "text"
    }

    val colList = ArrayList<ColumnDefinition>()
    colList.add(defTitle)
    colList.add(defYear)
```

```
    colList.add(defReleaseDate)
    colList.add(defPlot)

    // Set the keys.
    val yearKey = PartitionKey {
        name = "year"
    }

    val titleKey = PartitionKey {
        name = "title"
    }

    val keyList = ArrayList<PartitionKey>()
    keyList.add(yearKey)
    keyList.add(titleKey)

    val schemaDefinitionOb = SchemaDefinition {
        partitionKeys = keyList
        allColumns = colList
    }

    val timeRecovery = PointInTimeRecovery {
        status = PointInTimeRecoveryStatus.Enabled
    }

    val tableRequest = CreateTableRequest {
        keyspaceName = keySpaceVal
        tableName = tableNameVal
        schemaDefinition = schemaDefinitionOb
        pointInTimeRecovery = timeRecovery
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createTable(tableRequest)
        println("The table ARN is ${response.resourceArn}")
    }
}

suspend fun listKeyspacesPaginator() {
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listKeyspacesPaginated(ListKeyspacesRequest {})
            .transform { it.keyspaces?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name: ${obj.keyspaceName}")
```

```
            }
    }
}

suspend fun checkKeyspaceExistence(keyspaceNameVal: String?) {
    val keyspaceRequest = GetKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response: GetKeyspaceResponse =
 keyClient.getKeyspace(keyspaceRequest)
        val name = response.keyspaceName
        println("The $name KeySpace is ready")
    }
}

suspend fun createKeySpace(keyspaceNameVal: String) {
    val keyspaceRequest = CreateKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createKeyspace(keyspaceRequest)
        println("The ARN of the KeySpace is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable

- UpdateTable

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class KeyspaceScenario:
    """Runs an interactive scenario that shows how to get started using Amazon
 Keyspaces."""

    def __init__(self, ks_wrapper):
        """
        :param ks_wrapper: An object that wraps Amazon Keyspace actions.
        """
        self.ks_wrapper = ks_wrapper

    @demo_func
    def create_keyspace(self):
        """
        1. Creates a keyspace.
        2. Lists up to 10 keyspaces in your account.
        """
        print("Let's create a keyspace.")
        ks_name = q.ask(
            "Enter a name for your new keyspace.\nThe name can contain only
 letters, "
            "numbers and underscores: ",
            q.non_empty,
        )
        if self.ks_wrapper.exists_keyspace(ks_name):
            print(f"A keyspace named {ks_name} exists.")
        else:
            ks_arn = self.ks_wrapper.create_keyspace(ks_name)
            ks_exists = False
```

```
            while not ks_exists:
                wait(3)
                ks_exists = self.ks_wrapper.exists_keyspace(ks_name)
            print(f"Created a new keyspace.\n\t{ks_arn}.")
        print("The first 10 keyspaces in your account are:\n")
        self.ks_wrapper.list_keyspaces(10)

    @demo_func
    def create_table(self):
        """
        1. Creates a table in the keyspace. The table is configured with a schema
to hold
           movie data and has point-in-time recovery enabled.
        2. Waits for the table to be in an active state.
        3. Displays schema information for the table.
        4. Lists tables in the keyspace.
        """
        print("Let's create a table for movies in your keyspace.")
        table_name = q.ask("Enter a name for your table: ", q.non_empty)
        table = self.ks_wrapper.get_table(table_name)
        if table is not None:
            print(
                f"A table named {table_name} already exists in keyspace "
                f"{self.ks_wrapper.ks_name}."
            )
        else:
            table_arn = self.ks_wrapper.create_table(table_name)
            print(f"Created table {table_name}:\n\t{table_arn}")
            table = {"status": None}
            print("Waiting for your table to be ready...")
            while table["status"] != "ACTIVE":
                wait(5)
                table = self.ks_wrapper.get_table(table_name)
        print(f"Your table is {table['status']}. Its schema is:")
        pp(table["schemaDefinition"])
        print("\nThe tables in your keyspace are:\n")
        self.ks_wrapper.list_tables()

    @demo_func
    def ensure_tls_cert(self):
        """
        Ensures you have a TLS certificate available to use to secure the
connection
```

```
        to the keyspace. This function downloads a default certificate or lets
you
        specify your own.
        """
        print("To connect to your keyspace, you must have a TLS certificate.")
        print("Checking for TLS certificate...")
        cert_path = os.path.join(
            os.path.dirname(__file__), QueryManager.DEFAULT_CERT_FILE
        )
        if not os.path.exists(cert_path):
            cert_choice = q.ask(
                f"Press enter to download a certificate from
{QueryManager.CERT_URL} "
                f"or enter the full path to the certificate you want to use: "
            )
            if cert_choice:
                cert_path = cert_choice
            else:
                cert = requests.get(QueryManager.CERT_URL).text
                with open(cert_path, "w") as cert_file:
                    cert_file.write(cert)
        else:
            q.ask(f"Certificate {cert_path} found. Press Enter to continue.")
        print(
            f"Certificate {cert_path} will be used to secure the connection to
your keyspace."
        )
        return cert_path

    @demo_func
    def query_table(self, qm, movie_file):
        """
        1. Adds movies to the table from a sample movie data file.
        2. Gets a list of movies from the table and lets you select one.
        3. Displays more information about the selected movie.
        """
        qm.add_movies(self.ks_wrapper.table_name, movie_file)
        movies = qm.get_movies(self.ks_wrapper.table_name)
        print(f"Added {len(movies)} movies to the table:")
        sel = q.choose("Pick one to learn more about it: ", [m.title for m in
movies])
        movie_choice = qm.get_movie(
            self.ks_wrapper.table_name, movies[sel].title, movies[sel].year
        )
```

```
        print(movie_choice.title)
        print(f"\tReleased: {movie_choice.release_date}")
        print(f"\tPlot: {movie_choice.plot}")

    @demo_func
    def update_and_restore_table(self, qm):
        """
        1. Updates the table by adding a column to track watched movies.
        2. Marks some of the movies as watched.
        3. Gets the list of watched movies from the table.
        4. Restores to a movies_restored table at a previous point in time.
        5. Gets the list of movies from the restored table.
        """
        print("Let's add a column to record which movies you've watched.")
        pre_update_timestamp = datetime.utcnow()
        print(
            f"Recorded the current UTC time of {pre_update_timestamp} so we can
restore the table later."
        )
        self.ks_wrapper.update_table()
        print("Waiting for your table to update...")
        table = {"status": "UPDATING"}
        while table["status"] != "ACTIVE":
            wait(5)
            table = self.ks_wrapper.get_table(self.ks_wrapper.table_name)
        print("Column 'watched' added to table.")
        q.ask(
            "Let's mark some of the movies as watched. Press Enter when you're
ready.\n"
        )
        movies = qm.get_movies(self.ks_wrapper.table_name)
        for movie in movies[:10]:
            qm.watched_movie(self.ks_wrapper.table_name, movie.title, movie.year)
            print(f"Marked {movie.title} as watched.")
        movies = qm.get_movies(self.ks_wrapper.table_name, watched=True)
        print("-" * 88)
        print("The watched movies in our table are:\n")
        for movie in movies:
            print(movie.title)
        print("-" * 88)
        if q.ask(
            "Do you want to restore the table to the way it was before all of
these\n"
            "updates? Keep in mind, this can take up to 20 minutes. (y/n) ",
```

```
            q.is_yesno,
        ):
            starting_table_name = self.ks_wrapper.table_name
            table_name_restored =
self.ks_wrapper.restore_table(pre_update_timestamp)
            table = {"status": "RESTORING"}
            while table["status"] != "ACTIVE":
                wait(10)
                table = self.ks_wrapper.get_table(table_name_restored)
            print(
                f"Restored {starting_table_name} to {table_name_restored} "
                f"at a point in time of {pre_update_timestamp}."
            )
            movies = qm.get_movies(table_name_restored)
            print("Now the movies in our table are:")
            for movie in movies:
                print(movie.title)

    def cleanup(self, cert_path):
        """
        1. Deletes the table and waits for it to be removed.
        2. Deletes the keyspace.

        :param cert_path: The path of the TLS certificate used in the demo. If
the
                          certificate was downloaded during the demo, it is
removed.
        """
        if q.ask(
            f"Do you want to delete your {self.ks_wrapper.table_name} table and "
            f"{self.ks_wrapper.ks_name} keyspace? (y/n) ",
            q.is_yesno,
        ):
            table_name = self.ks_wrapper.table_name
            self.ks_wrapper.delete_table()
            table = self.ks_wrapper.get_table(table_name)
            print("Waiting for the table to be deleted.")
            while table is not None:
                wait(5)
                table = self.ks_wrapper.get_table(table_name)
            print("Table deleted.")
            self.ks_wrapper.delete_keyspace()
            print(
```

```
                "Keyspace deleted. If you chose to restore your table during the
 "
                "demo, the original table is also deleted."
            )
            if cert_path == os.path.join(
                os.path.dirname(__file__), QueryManager.DEFAULT_CERT_FILE
            ) and os.path.exists(cert_path):
                os.remove(cert_path)
                print("Removed certificate that was downloaded for this demo.")

    def run_scenario(self):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s:
 %(message)s")

        print("-" * 88)
        print("Welcome to the Amazon Keyspaces (for Apache Cassandra) demo.")
        print("-" * 88)

        self.create_keyspace()
        self.create_table()
        cert_file_path = self.ensure_tls_cert()
        # Use a context manager to ensure the connection to the keyspace is
 closed.
        with QueryManager(
            cert_file_path, boto3.DEFAULT_SESSION, self.ks_wrapper.ks_name
        ) as qm:
            self.query_table(qm, "../../../resources/sample_files/movies.json")
            self.update_and_restore_table(qm)
        self.cleanup(cert_file_path)

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = KeyspaceScenario(KeyspaceWrapper.from_client())
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina uma classe que envolva as ações de tabelas e de espaço de chaves.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def create_keyspace(self, name):
        """
        Creates a keyspace.

        :param name: The name to give the keyspace.
        :return: The Amazon Resource Name (ARN) of the new keyspace.
        """
        try:
            response = self.keyspaces_client.create_keyspace(keyspaceName=name)
            self.ks_name = name
            self.ks_arn = response["resourceArn"]
        except ClientError as err:
            logger.error(
                "Couldn't create %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.ks_arn


    def exists_keyspace(self, name):
```

```
        """
        Checks whether a keyspace exists.

        :param name: The name of the keyspace to look up.
        :return: True when the keyspace exists. Otherwise, False.
        """
        try:
            response = self.keyspaces_client.get_keyspace(keyspaceName=name)
            self.ks_name = response["keyspaceName"]
            self.ks_arn = response["resourceArn"]
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Keyspace %s does not exist.", name)
                exists = False
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return exists


    def list_keyspaces(self, limit):
        """
        Lists the keyspaces in your account.

        :param limit: The maximum number of keyspaces to list.
        """
        try:
            ks_paginator = self.keyspaces_client.get_paginator("list_keyspaces")
            for page in ks_paginator.paginate(PaginationConfig={"MaxItems":
limit}):
                for ks in page["keyspaces"]:
                    print(ks["keyspaceName"])
                    print(f"\t{ks['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list keyspaces. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise


    def create_table(self, table_name):
        """
        Creates a table in the  keyspace.
        The table is created with a schema for storing movie data
        and has point-in-time recovery enabled.

        :param table_name: The name to give the table.
        :return: The ARN of the new table.
        """
        try:
            response = self.keyspaces_client.create_table(
                keyspaceName=self.ks_name,
                tableName=table_name,
                schemaDefinition={
                    "allColumns": [
                        {"name": "title", "type": "text"},
                        {"name": "year", "type": "int"},
                        {"name": "release_date", "type": "timestamp"},
                        {"name": "plot", "type": "text"},
                    ],
                    "partitionKeys": [{"name": "year"}, {"name": "title"}],
                },
                pointInTimeRecovery={"status": "ENABLED"},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["resourceArn"]


    def get_table(self, table_name):
        """
        Gets data about a table in the keyspace.
```

```
        :param table_name: The name of the table to look up.
        :return: Data about the table.
        """
        try:
            response = self.keyspaces_client.get_table(
                keyspaceName=self.ks_name, tableName=table_name
            )
            self.table_name = table_name
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Table %s does not exist.", table_name)
                self.table_name = None
                response = None
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response


    def list_tables(self):
        """
        Lists the tables in the keyspace.
        """
        try:
            table_paginator = self.keyspaces_client.get_paginator("list_tables")
            for page in table_paginator.paginate(keyspaceName=self.ks_name):
                for table in page["tables"]:
                    print(table["tableName"])
                    print(f"\t{table['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list tables in keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
    def update_table(self):
        """
        Updates the schema of the table.

        This example updates a table of movie data by adding a new column
        that tracks whether the movie has been watched.
        """
        try:
            self.keyspaces_client.update_table(
                keyspaceName=self.ks_name,
                tableName=self.table_name,
                addColumns=[{"name": "watched", "type": "boolean"}],
            )
        except ClientError as err:
            logger.error(
                "Couldn't update table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def restore_table(self, restore_timestamp):
        """
        Restores the table to a previous point in time. The table is restored
        to a new table in the same keyspace.

        :param restore_timestamp: The point in time to restore the table. This
time
                                  must be in UTC format.
        :return: The name of the restored table.
        """
        try:
            restored_table_name = f"{self.table_name}_restored"
            self.keyspaces_client.restore_table(
                sourceKeyspaceName=self.ks_name,
                sourceTableName=self.table_name,
                targetKeyspaceName=self.ks_name,
                targetTableName=restored_table_name,
                restoreTimestamp=restore_timestamp,
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't restore table %s. Here's why: %s: %s",
                restore_timestamp,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return restored_table_name


    def delete_table(self):
        """
        Deletes the table from the keyspace.
        """
        try:
            self.keyspaces_client.delete_table(
                keyspaceName=self.ks_name, tableName=self.table_name
            )
            self.table_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_keyspace(self):
        """
        Deletes the keyspace.
        """
        try:
            self.keyspaces_client.delete_keyspace(keyspaceName=self.ks_name)
            self.ks_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que crie uma conexão TLS com um espaço de chaves, autentique com SigV4 e envie consultas CQL para uma tabela no espaço de chaves.

```
class QueryManager:
    """
    Manages queries to an Amazon Keyspaces (for Apache Cassandra) keyspace.
    Queries are secured by TLS and authenticated by using the Signature V4
 (SigV4)
    AWS signing protocol. This is more secure than sending username and password
    with a plain-text authentication provider.

    This example downloads a default certificate to secure TLS, or lets you
 specify
    your own.

    This example uses a table of movie data to demonstrate basic queries.
    """

    DEFAULT_CERT_FILE = "sf-class2-root.crt"
    CERT_URL = f"https://certs.secureserver.net/repository/sf-class2-root.crt"

    def __init__(self, cert_file_path, boto_session, keyspace_name):
        """
        :param cert_file_path: The path and file name of the certificate used for
 TLS.
        :param boto_session: A Boto3 session. This is used to acquire your AWS
 credentials.
        :param keyspace_name: The name of the keyspace to connect.
        """
        self.cert_file_path = cert_file_path
        self.boto_session = boto_session
        self.ks_name = keyspace_name
        self.cluster = None
        self.session = None

    def __enter__(self):
        """
        Creates a session connection to the keyspace that is secured by TLS and
```

```
        authenticated by SigV4.
        """
        ssl_context = SSLContext(PROTOCOL_TLSv1_2)
        ssl_context.load_verify_locations(self.cert_file_path)
        ssl_context.verify_mode = CERT_REQUIRED
        auth_provider = SigV4AuthProvider(self.boto_session)
        contact_point = f"cassandra.
{self.boto_session.region_name}.amazonaws.com"
        exec_profile = ExecutionProfile(
            consistency_level=ConsistencyLevel.LOCAL_QUORUM,
            load_balancing_policy=DCAwareRoundRobinPolicy(),
        )
        self.cluster = Cluster(
            [contact_point],
            ssl_context=ssl_context,
            auth_provider=auth_provider,
            port=9142,
            execution_profiles={EXEC_PROFILE_DEFAULT: exec_profile},
            protocol_version=4,
        )
        self.cluster.__enter__()
        self.session = self.cluster.connect(self.ks_name)
        return self

    def __exit__(self, *args):
        """
        Exits the cluster. This shuts down all existing session connections.
        """
        self.cluster.__exit__(*args)

    def add_movies(self, table_name, movie_file_path):
        """
        Gets movies from a JSON file and adds them to a table in the keyspace.

        :param table_name: The name of the table.
        :param movie_file_path: The path and file name of a JSON file that
 contains movie data.
        """
        with open(movie_file_path, "r") as movie_file:
            movies = json.loads(movie_file.read())
        stmt = self.session.prepare(
            f"INSERT INTO {table_name} (year, title, release_date, plot) VALUES
 (?, ?, ?, ?);"
        )
```

```
        for movie in movies[:20]:
            self.session.execute(
                stmt,
                parameters=[
                    movie["year"],
                    movie["title"],
                    date.fromisoformat(movie["info"]
["release_date"].partition("T")[0]),
                    movie["info"]["plot"],
                ],
            )

    def get_movies(self, table_name, watched=None):
        """
        Gets the title and year of the full list of movies from the table.

        :param table_name: The name of the movie table.
        :param watched: When specified, the returned list of movies is filtered
 to
                        either movies that have been watched or movies that have
 not
                        been watched. Otherwise, all movies are returned.
        :return: A list of movies in the table.
        """
        if watched is None:
            stmt = SimpleStatement(f"SELECT title, year from {table_name}")
            params = None
        else:
            stmt = SimpleStatement(
                f"SELECT title, year from {table_name} WHERE watched = %s ALLOW
 FILTERING"
            )
            params = [watched]
        return self.session.execute(stmt, parameters=params).all()

    def get_movie(self, table_name, title, year):
        """
        Gets a single movie from the table, by title and year.

        :param table_name: The name of the movie table.
        :param title: The title of the movie.
        :param year: The year of the movie's release.
        :return: The requested movie.
        """
```

```
        return self.session.execute(
            SimpleStatement(
                f"SELECT * from {table_name} WHERE title = %s AND year = %s"
            ),
            parameters=[title, year],
        ).one()

    def watched_movie(self, table_name, title, year):
        """
        Updates a movie as having been watched.

        :param table_name: The name of the movie table.
        :param title: The title of the movie.
        :param year: The year of the movie's release.
        """
        self.session.execute(
            SimpleStatement(
                f"UPDATE {table_name} SET watched=true WHERE title = %s AND year
= %s"
            ),
            parameters=[title, year],
        )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable
  - UpdateTable

Exemplos de código para o IAM usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Kinesis com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Kinesis – Mais informações sobre o Kinesis.
- Referência da API do Kinesis – Detalhes sobre todas as ações disponíveis do Kinesis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Kinesis usando SDKs da AWS
  - Adicione tags a um fluxo do Kinesis usando um SDK da AWS
  - Crie um fluxo do Kinesis usando um SDK da AWS
  - Exclua um fluxo do Kinesis usando um SDK da AWS
  - Cancele o registro de um consumidor de um fluxo do Kinesis usando um SDK da AWS
  - Descreva um fluxo do Kinesis usando um SDK da AWS
  - Obtenha dados em lotes de um fluxo do Kinesis usando um SDK da AWS
  - Liste fluxos do Kinesis usando um SDK da AWS
  - Liste as tags associadas a um fluxo do Kinesis usando um SDK da AWS
  - Liste os consumidores de um fluxo do Kinesis usando um SDK da AWS
  - Insira dados em um fluxo do Kinesis usando um SDK da AWS
  - Registre um consumidor em um fluxo do Kinesis usando um SDK da AWS

- Cenários para o Kinesis usando SDKs da AWS
  - Comece a usar as operações básicas de fluxo de dados do Kinesis usando um SDK da AWS
- Exemplos de tecnologia sem servidor para o Lambda usando SDKs da AWS
  - Invocar uma função do Lambda em um trigger do Kinesis
  - Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

Ações para o Kinesis usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Kinesis com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Kinesis usando SDKs da AWS.

Exemplos

- Adicione tags a um fluxo do Kinesis usando um SDK da AWS
- Crie um fluxo do Kinesis usando um SDK da AWS
- Exclua um fluxo do Kinesis usando um SDK da AWS
- Cancele o registro de um consumidor de um fluxo do Kinesis usando um SDK da AWS
- Descreva um fluxo do Kinesis usando um SDK da AWS
- Obtenha dados em lotes de um fluxo do Kinesis usando um SDK da AWS
- Liste fluxos do Kinesis usando um SDK da AWS
- Liste as tags associadas a um fluxo do Kinesis usando um SDK da AWS
- Liste os consumidores de um fluxo do Kinesis usando um SDK da AWS
- Insira dados em um fluxo do Kinesis usando um SDK da AWS
- Registre um consumidor em um fluxo do Kinesis usando um SDK da AWS

Adicione tags a um fluxo do Kinesis usando um SDK da AWS

O exemplo de código a seguir mostra como adicionar tags a um fluxo do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// This example shows how to apply key/value pairs to an Amazon Kinesis
/// stream.
/// </summary>
public class TagStream
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();

        string streamName = "AmazonKinesisStream";
        var tags = new Dictionary<string, string>
        {
            { "Project", "Sample Kinesis Project" },
            { "Application", "Sample Kinesis App" },
        };

        var success = await ApplyTagsToStreamAsync(client, streamName, tags);

        if (success)
        {
            Console.WriteLine($"Taggs successfully added to {streamName}.");
        }
        else
        {
            Console.WriteLine("Tags were not added to the stream.");
```

```
            }
        }

        /// <summary>
        /// Applies the set of tags to the named Kinesis stream.
        /// </summary>
        /// <param name="client">The initialized Kinesis client.</param>
        /// <param name="streamName">The name of the Kinesis stream to which
        /// the tags will be attached.</param>
        /// <param name="tags">A sictionary containing key/value pairs which
        /// will be used to create the Kinesis tags.</param>
        /// <returns>A Boolean value which represents the success or failure
        /// of AddTagsToStreamAsync.</returns>
        public static async Task<bool> ApplyTagsToStreamAsync(
            IAmazonKinesis client,
            string streamName,
            Dictionary<string, string> tags)
        {
            var request = new AddTagsToStreamRequest
            {
                StreamName = streamName,
                Tags = tags,
            };

            var response = await client.AddTagsToStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte AddTagsToStreama Referência AWS SDK for .NET da API.

Crie um fluxo do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um stream do Kinesis.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar de fluxos de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// This example shows how to create a new Amazon Kinesis stream.
/// </summary>
public class CreateStream
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();

        string streamName = "AmazonKinesisStream";
        int shardCount = 1;

        var success = await CreateNewStreamAsync(client, streamName,
shardCount);
        if (success)
        {
            Console.WriteLine($"The stream, {streamName} successfully
created.");
        }
    }

    /// <summary>
    /// Creates a new Kinesis stream.
    /// </summary>
    /// <param name="client">An initialized Kinesis client.</param>
```

```
        /// <param name="streamName">The name for the new stream.</param>
        /// <param name="shardCount">The number of shards the new stream will
        /// use. The throughput of the stream is a function of the number of
        /// shards; more shards are required for greater provisioned
        /// throughput.</param>
        /// <returns>A Boolean value indicating whether the stream was created.</
returns>
        public static async Task<bool> CreateNewStreamAsync(IAmazonKinesis
 client, string streamName, int shardCount)
        {
            var request = new CreateStreamRequest
            {
                StreamName = streamName,
                ShardCount = shardCount,
            };

            var response = await client.CreateStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte CreateStreama Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar um fluxo de dados

O exemplo de `create-stream` a seguir cria um fluxo de dados chamado samplestream com três fragmentos.

```
aws kinesis create-stream \
    --stream-name samplestream \
    --shard-count 3
```

Este comando não produz saída.

Para obter mais informações, consulte Creating a stream no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte CreateStreamna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.CreateStreamRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateDataStream {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream (for example,
 StockTradeStream).
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();
        createStream(kinesisClient, streamName);
        System.out.println("Done");
        kinesisClient.close();
    }

    public static void createStream(KinesisClient kinesisClient, String
 streamName) {
        try {
            CreateStreamRequest streamReq = CreateStreamRequest.builder()
                    .streamName(streamName)
                    .shardCount(1)
                    .build();

            kinesisClient.createStream(streamReq);

        } catch (KinesisException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateStreama Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def create(self, name, wait_until_exists=True):
        """
        Creates a stream.

        :param name: The name of the stream.
        :param wait_until_exists: When True, waits until the service reports that
                                  the stream exists, then queries for its
 metadata.
        """
        try:
            self.kinesis_client.create_stream(StreamName=name, ShardCount=1)
            self.name = name
            logger.info("Created stream %s.", name)
            if wait_until_exists:
                logger.info("Waiting until exists.")
                self.stream_exists_waiter.wait(StreamName=name)
                self.describe(name)
        except ClientError:
            logger.exception("Couldn't create stream %s.", name)
```

```
            raise
```

- Para obter detalhes da API, consulte a CreateStreamReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_stream(client: &Client, stream: &str) -> Result<(), Error> {
    client
        .create_stream()
        .stream_name(stream)
        .shard_count(4)
        .send()
        .await?;

    println!("Created stream");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateStreamreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       lo_kns->createstream(
           iv_streamname = iv_stream_name
           iv_shardcount = iv_shard_count
       ).
       MESSAGE 'Stream created.' TYPE 'I'.
     CATCH /aws1/cx_knsinvalidargumentex.
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
     CATCH /aws1/cx_knslimitexceededex .
       MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
     CATCH /aws1/cx_knsresourceinuseex .
       MESSAGE 'The request processing has failed because the resource is in
use.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a CreateStreamreferência da API AWS SDK for SAP ABAP.

Exclua um fluxo do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um fluxo do Kinesis.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar de fluxos de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// Shows how to delete an Amazon Kinesis stream.
/// </summary>
public class DeleteStream
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();
        string streamName = "AmazonKinesisStream";

        var success = await DeleteStreamAsync(client, streamName);

        if (success)
        {
            Console.WriteLine($"Stream, {streamName} successfully deleted.");
        }
        else
        {
            Console.WriteLine("Stream not deleted.");
        }
    }

    /// <summary>
    /// Deletes a Kinesis stream.
    /// </summary>
    /// <param name="client">An initialized Kinesis client object.</param>
    /// <param name="streamName">The name of the string to delete.</param>
```

```
        /// <returns>A Boolean value representing the success of the operation.</
returns>
        public static async Task<bool> DeleteStreamAsync(IAmazonKinesis client,
 string streamName)
        {
            // If EnforceConsumerDeletion is true, any consumers
            // of this stream will also be deleted. If it is set
            // to false and this stream has any consumers, the
            // call will fail with a ResourceInUseException.
            var request = new DeleteStreamRequest
            {
                StreamName = streamName,
                EnforceConsumerDeletion = true,
            };

            var response = await client.DeleteStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeleteStreama Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um fluxo de dados

O exemplo de `delete-stream` a seguir exclui o fluxo de dados especificado.

```
aws kinesis delete-stream \
    --stream-name samplestream
```

Este comando não produz saída.

Para obter mais informações, consulte Excluir um stream no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte DeleteStreamna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.DeleteStreamRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteDataStream {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream (for example,
 StockTradeStream)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        deleteStream(kinesisClient, streamName);
        kinesisClient.close();
        System.out.println("Done");
    }

    public static void deleteStream(KinesisClient kinesisClient, String
 streamName) {
        try {
            DeleteStreamRequest delStream = DeleteStreamRequest.builder()
                    .streamName(streamName)
                    .build();

            kinesisClient.deleteStream(delStream);

        } catch (KinesisException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteStreama Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def delete(self):
        """
        Deletes a stream.
        """
        try:
            self.kinesis_client.delete_stream(StreamName=self.name)
            self._clear()
            logger.info("Deleted stream %s.", self.name)
        except ClientError:
            logger.exception("Couldn't delete stream %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteStreamReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_stream(client: &Client, stream: &str) -> Result<(), Error> {
```

```
    client.delete_stream().stream_name(stream).send().await?;

    println!("Deleted stream.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteStreamreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       lo_kns->deletestream(
           iv_streamname = iv_stream_name
       ).
       MESSAGE 'Stream deleted.' TYPE 'I'.
     CATCH /aws1/cx_knslimitexceededex .
       MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
     CATCH /aws1/cx_knsresourceinuseex .
       MESSAGE 'The request processing has failed because the resource is in
use.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteStreamreferência da API AWS SDK for SAP ABAP.

Cancele o registro de um consumidor de um fluxo do Kinesis usando um SDK da AWS

O exemplo de código a seguir mostra como cancelar o registro de um consumidor em um fluxo do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// Shows how to deregister a consumer from an Amazon Kinesis stream.
    /// </summary>
    public class DeregisterConsumer
    {
        public static async Task Main(string[] args)
        {
            IAmazonKinesis client = new AmazonKinesisClient();

            string streamARN = "arn:aws:kinesis:us-west-2:000000000000:stream/
AmazonKinesisStream";
            string consumerName = "CONSUMER_NAME";
            string consumerARN = "arn:aws:kinesis:us-west-2:000000000000:stream/
AmazonKinesisStream/consumer/CONSUMER_NAME:000000000000";

            var success = await DeregisterConsumerAsync(client, streamARN,
 consumerARN, consumerName);

            if (success)
            {
                Console.WriteLine($"{consumerName} successfully deregistered.");
            }
```

```
            else
            {
                Console.WriteLine($"{consumerName} was not successfully
 deregistered.");
            }
        }

        /// <summary>
        /// Deregisters a consumer from a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamARN">The ARN of a Kinesis stream.</param>
        /// <param name="consumerARN">The ARN of the consumer.</param>
        /// <param name="consumerName">The name of the consumer.</param>
        /// <returns>A Boolean value representing the success of the operation.</
returns>
        public static async Task<bool> DeregisterConsumerAsync(
            IAmazonKinesis client,
            string streamARN,
            string consumerARN,
            string consumerName)
        {
            var request = new DeregisterStreamConsumerRequest
            {
                StreamARN = streamARN,
                ConsumerARN = consumerARN,
                ConsumerName = consumerName,
            };

            var response = await client.DeregisterStreamConsumerAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeregisterStreamConsumera Referência AWS SDK for .NET da API.

Descreva um fluxo do Kinesis usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um stream do Kinesis.

CLI

AWS CLI

Como descrever um fluxo de dados

O exemplo de `describe-stream` a seguir retorna detalhes sobre o fluxo de dados especificado.

```
aws kinesis describe-stream \
    --stream-name samplestream
```

Saída:

```
{
    "StreamDescription": {
        "Shards": [
            {
                "ShardId": "shardId-000000000000",
                "HashKeyRange": {
                    "StartingHashKey": "0",
                    "EndingHashKey": "113427455640312821154458202477256070484"
                },
                "SequenceNumberRange": {
                    "StartingSequenceNumber":
 "49600871682957036442365024926191073437251060580128653314"
                }
            },
            {
                "ShardId": "shardId-000000000001",
                "HashKeyRange": {
                    "StartingHashKey": "113427455640312821154458202477256070485",
                    "EndingHashKey": "226854911280625642308916404954512140969"
                },
                "SequenceNumberRange": {
                    "StartingSequenceNumber":
 "49600871682979337187563555549332609155523708941634633746"
                }
            },
            {
                "ShardId": "shardId-000000000002",
                "HashKeyRange": {
                    "StartingHashKey": "226854911280625642308916404954512140970",
```

```
                    "EndingHashKey": "340282366920938463463374607431768211455"
                },
                "SequenceNumberRange": {
                    "StartingSequenceNumber":
 "49600871683001637932762086172474144873796357303140614178"
                }
            }
        ],
        "StreamARN": "arn:aws:kinesis:us-west-2:123456789012:stream/
samplestream",
        "StreamName": "samplestream",
        "StreamStatus": "ACTIVE",
        "RetentionPeriodHours": 24,
        "EnhancedMonitoring": [
            {
                "ShardLevelMetrics": []
            }
        ],
        "EncryptionType": "NONE",
        "KeyId": null,
        "StreamCreationTimestamp": 1572297168.0
    }
}
```

Para obter mais informações, consulte Criar e gerenciar streamings no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte DescribeStreamna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
```

```
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def describe(self, name):
        """
        Gets metadata about a stream.

        :param name: The name of the stream.
        :return: Metadata about the stream.
        """
        try:
            response = self.kinesis_client.describe_stream(StreamName=name)
            self.name = name
            self.details = response["StreamDescription"]
            logger.info("Got stream %s.", name)
        except ClientError:
            logger.exception("Couldn't get %s.", name)
            raise
        else:
            return self.details
```

- Para obter detalhes da API, consulte a DescribeStreamReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_stream(client: &Client, stream: &str) -> Result<(), Error> {
    let resp = client.describe_stream().stream_name(stream).send().await?;

    let desc = resp.stream_description.unwrap();

    println!("Stream description:");
    println!("  Name:              {}:", desc.stream_name());
    println!("  Status:            {:?}", desc.stream_status());
    println!("  Open shards:       {:?}", desc.shards.len());
    println!("  Retention (hours): {}", desc.retention_period_hours());
    println!("  Encryption:        {:?}", desc.encryption_type.unwrap());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeStreamreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        oo_result = lo_kns->describestream(
            iv_streamname = iv_stream_name
        ).
        DATA(lt_stream_description) = oo_result->get_streamdescription( ).
        MESSAGE 'Streams retrieved.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceed
 exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeStreamreferência da API AWS SDK for SAP ABAP.

Obtenha dados em lotes de um fluxo do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados em lotes de um fluxo do Kinesis.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar de fluxos de dados

CLI

AWS CLI

Como obter registros de um fragmento

O exemplo de `get-records` a seguir obtém registros de dados do fragmento de um fluxo de dados do Kinesis usando o iterador de fragmento especificado.

```
aws kinesis get-records \
    --shard-iterator AAAAAAAAAAF7/0mWD7IuHj1yGv/
TKuNgx2ukD5xipCY4cy4gU96orWwZwcSXh3K9tAmGYeOZyLZrvzzeOFVf9iN99hUPw/w/
b0YWYeehfNvnf1DYt5XpDJghLKr3DzgznkTmMymDP3R+3wRKeuEw6/kdxY2yKJH0veaiekaVc4N2VwK/
GvaGP2Hh9Fg7N++q0Adg6fIDQPt4p8RpavDbk+A4sL9SWGE1
```

Saída:

```
{
    "Records": [],
    "MillisBehindLatest": 80742000
}
```

Para obter mais informações, consulte Developing Consumers Using the Kinesis Data Streams API with the AWS SDK for Java no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - GetRecords
  - GetShardIterator

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamResponse;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamRequest;
import software.amazon.awssdk.services.kinesis.model.Shard;
import software.amazon.awssdk.services.kinesis.model.GetShardIteratorRequest;
import software.amazon.awssdk.services.kinesis.model.GetShardIteratorResponse;
import software.amazon.awssdk.services.kinesis.model.Record;
import software.amazon.awssdk.services.kinesis.model.GetRecordsRequest;
import software.amazon.awssdk.services.kinesis.model.GetRecordsResponse;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetRecords {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream to read from (for
 example, StockTradeStream).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        getStockTrades(kinesisClient, streamName);
        kinesisClient.close();
    }

    public static void getStockTrades(KinesisClient kinesisClient, String
 streamName) {
        String shardIterator;
        String lastShardId = null;
        DescribeStreamRequest describeStreamRequest =
 DescribeStreamRequest.builder()
                .streamName(streamName)
                .build();

        List<Shard> shards = new ArrayList<>();
```

```
        DescribeStreamResponse streamRes;
        do {
            streamRes = kinesisClient.describeStream(describeStreamRequest);
            shards.addAll(streamRes.streamDescription().shards());

            if (shards.size() > 0) {
                lastShardId = shards.get(shards.size() - 1).shardId();
            }
        } while (streamRes.streamDescription().hasMoreShards());

        GetShardIteratorRequest itReq = GetShardIteratorRequest.builder()
                .streamName(streamName)
                .shardIteratorType("TRIM_HORIZON")
                .shardId(lastShardId)
                .build();

        GetShardIteratorResponse shardIteratorResult =
 kinesisClient.getShardIterator(itReq);
        shardIterator = shardIteratorResult.shardIterator();

        // Continuously read data records from shard.
        List<Record> records;

        // Create new GetRecordsRequest with existing shardIterator.
        // Set maximum records to return to 1000.
        GetRecordsRequest recordsRequest = GetRecordsRequest.builder()
                .shardIterator(shardIterator)
                .limit(1000)
                .build();

        GetRecordsResponse result = kinesisClient.getRecords(recordsRequest);

        // Put result into record list. Result may be empty.
        records = result.records();

        // Print records
        for (Record record : records) {
            SdkBytes byteBuffer = record.data();
            System.out.printf("Seq No: %s - %s%n", record.sequenceNumber(), new
 String(byteBuffer.asByteArray()));
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetRecords
  - GetShardIterator

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def get_records(self, max_records):
        """
        Gets records from the stream. This function is a generator that first
 gets
        a shard iterator for the stream, then uses the shard iterator to get
 records
        in batches from the stream. Each batch of records is yielded back to the
        caller until the specified maximum number of records has been retrieved.

        :param max_records: The maximum number of records to retrieve.
```

```
        :return: Yields the current batch of retrieved records.
        """
        try:
            response = self.kinesis_client.get_shard_iterator(
                StreamName=self.name,
                ShardId=self.details["Shards"][0]["ShardId"],
                ShardIteratorType="LATEST",
            )
            shard_iter = response["ShardIterator"]
            record_count = 0
            while record_count < max_records:
                response = self.kinesis_client.get_records(
                    ShardIterator=shard_iter, Limit=10
                )
                shard_iter = response["NextShardIterator"]
                records = response["Records"]
                logger.info("Got %s records.", len(records))
                record_count += len(records)
                yield records
        except ClientError:
            logger.exception("Couldn't get records from stream %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - GetRecords
  - GetShardIterator

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_kns->getrecords(             " oo_result is returned for
testing purposes. "
           iv_sharditerator = iv_shard_iterator
       ).
       DATA(lt_records) = oo_result->get_records( ).
       MESSAGE 'Record retrieved.' TYPE 'I'.
     CATCH /aws1/cx_knsexpirediteratorex .
       MESSAGE 'Iterator expired.' TYPE 'E'.
     CATCH /aws1/cx_knsinvalidargumentex .
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
     CATCH /aws1/cx_knskmsaccessdeniedex .
       MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
     CATCH /aws1/cx_knskmsdisabledex .
       MESSAGE 'KMS key used is disabled.' TYPE 'E'.
     CATCH /aws1/cx_knskmsinvalidstateex .
       MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
     CATCH /aws1/cx_knskmsnotfoundex .
       MESSAGE 'KMS key used is not found.' TYPE 'E'.
     CATCH /aws1/cx_knskmsoptinrequired .
       MESSAGE 'KMS key option is required.' TYPE 'E'.
     CATCH /aws1/cx_knskmsthrottlingex .
       MESSAGE 'The rate of requests to AWS KMS is exceeding the request
quotas.' TYPE 'E'.
     CATCH /aws1/cx_knsprovthruputexcdex .
       MESSAGE 'The request rate for the stream is too high, or the requested
data is too large for the available throughput.' TYPE 'E'.
     CATCH /aws1/cx_knsresourcenotfoundex .
       MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - GetRecords
  - GetShardIterator

Liste fluxos do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como listar as informações sobre um ou mais fluxos do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// Retrieves and displays a list of existing Amazon Kinesis streams.
/// </summary>
public class ListStreams
{
    public static async Task Main(string[] args)
    {
        IAmazonKinesis client = new AmazonKinesisClient();
        var response = await client.ListStreamsAsync(new
ListStreamsRequest());

        List<string> streamNames = response.StreamNames;

        if (streamNames.Count > 0)
        {
            streamNames
                .ForEach(s => Console.WriteLine($"Stream name: {s}"));
        }
        else
        {
            Console.WriteLine("No streams were found.");
```

```
            }
        }
    }
```

- Para obter detalhes da API, consulte ListStreamsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar fluxos de dados

O exemplo de `list-streams` a seguir lista todos os fluxos de dados ativos na conta e região atuais.

```
aws kinesis list-streams
```

Saída:

```
{
    "StreamNames": [
        "samplestream",
        "samplestream1"
    ]
}
```

Para obter mais informações, consulte Listar streams no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte ListStreamsna Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_streams(client: &Client) -> Result<(), Error> {
    let resp = client.list_streams().send().await?;

    println!("Stream names:");

    let streams = resp.stream_names;
    for stream in &streams {
        println!("  {}", stream);
    }

    println!("Found {} stream(s)", streams.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListStreamsreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        oo_result = lo_kns->liststreams(        " oo_result is returned for
testing purposes. "
            "Set Limit to specify that a maximum of streams should be returned."
            iv_limit = iv_limit
        ).
        DATA(lt_streams) = oo_result->get_streamnames( ).
        MESSAGE 'Streams listed.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListStreamsreferência da API AWS SDK for SAP ABAP.

Liste as tags associadas a um fluxo do Kinesis usando um SDK da AWS

O exemplo de código a seguir mostra como listar as tags associadas a um fluxo do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// Shows how to list the tags that have been attached to an Amazon Kinesis
/// stream.
/// </summary>
public class ListTags
```

```
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();
            string streamName = "AmazonKinesisStream";

            await ListTagsAsync(client, streamName);
        }

        /// <summary>
        /// List the tags attached to a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamName">The name of the Kinesis stream for which you
        /// wish to display tags.</param>
        public static async Task ListTagsAsync(IAmazonKinesis client, string
streamName)
        {
            var request = new ListTagsForStreamRequest
            {
                StreamName = streamName,
                Limit = 10,
            };

            var response = await client.ListTagsForStreamAsync(request);
            DisplayTags(response.Tags);

            while (response.HasMoreTags)
            {
                request.ExclusiveStartTagKey = response.Tags[response.Tags.Count
- 1].Key;
                response = await client.ListTagsForStreamAsync(request);
            }
        }

        /// <summary>
        /// Displays the items in a list of Kinesis tags.
        /// </summary>
        /// <param name="tags">A list of the Tag objects to be displayed.</param>
        public static void DisplayTags(List<Tag> tags)
        {
            tags
                .ForEach(t => Console.WriteLine($"Key: {t.Key} Value:
{t.Value}"));
```

```
        }
    }
```

- Para obter detalhes da API, consulte ListTagsForStreama Referência AWS SDK for .NET da API.

Liste os consumidores de um fluxo do Kinesis usando um SDK da AWS

O exemplo de código a seguir mostra como listar os consumidores de um fluxo do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// List the consumers of an Amazon Kinesis stream.
    /// </summary>
    public class ListConsumers
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();

            string streamARN = "arn:aws:kinesis:us-east-2:000000000000:stream/
AmazonKinesisStream";
            int maxResults = 10;
```

```
            var consumers = await ListConsumersAsync(client, streamARN,
 maxResults);

            if (consumers.Count > 0)
            {
                consumers
                    .ForEach(c => Console.WriteLine($"Name: {c.ConsumerName} ARN:
 {c.ConsumerARN}"));
            }
            else
            {
                Console.WriteLine("No consumers found.");
            }
        }

        /// <summary>
        /// Retrieve a list of the consumers for a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamARN">The ARN of the stream for which we want to
        /// retrieve a list of clients.</param>
        /// <param name="maxResults">The maximum number of results to return.</
param>
        /// <returns>A list of Consumer objects.</returns>
        public static async Task<List<Consumer>>
 ListConsumersAsync(IAmazonKinesis client, string streamARN, int maxResults)
        {
            var request = new ListStreamConsumersRequest
            {
                StreamARN = streamARN,
                MaxResults = maxResults,
            };

            var response = await client.ListStreamConsumersAsync(request);

            return response.Consumers;
        }
    }
```

- Para obter detalhes da API, consulte ListStreamConsumersa Referência AWS SDK for .NET da API.

Insira dados em um fluxo do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como inserir dados em um fluxo do Kinesis.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Comece a usar de fluxos de dados

CLI

AWS CLI

Como gravar um registro em um fluxo de dados

O exemplo de `put-record` a seguir grava um único registro de dados no fluxo de dados especificado usando a chave de partição especificada.

```
aws kinesis put-record \
    --stream-name samplestream \
    --data sampledatarecord \
    --partition-key samplepartitionkey
```

Saída:

```
{
    "ShardId": "shardId-000000000009",
    "SequenceNumber": "49600902273357540915989931256901506243878407835297513618",
    "EncryptionType": "KMS"
}
```

Para obter mais informações, consulte Desenvolver produtores usando a API do Amazon Kinesis Data Streams com o AWS SDK for Java no Guia do desenvolvedor do Amazon Kinesis Data Streams.

- Para obter detalhes da API, consulte PutRecordna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.PutRecordRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamRequest;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class StockTradesWriter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream to which records
 are written (for example, StockTradeStream)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        // Ensure that the Kinesis Stream is valid.
        validateStream(kinesisClient, streamName);
        setStockData(kinesisClient, streamName);
        kinesisClient.close();
    }

    public static void setStockData(KinesisClient kinesisClient, String
streamName) {
        try {
            // Repeatedly send stock trades with a 100 milliseconds wait in
between.
            StockTradeGenerator stockTradeGenerator = new StockTradeGenerator();

            // Put in 50 Records for this example.
            int index = 50;
            for (int x = 0; x < index; x++) {
                StockTrade trade = stockTradeGenerator.getRandomTrade();
                sendStockTrade(trade, kinesisClient, streamName);
                Thread.sleep(100);
            }

        } catch (KinesisException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }

    private static void sendStockTrade(StockTrade trade, KinesisClient
kinesisClient,
            String streamName) {
        byte[] bytes = trade.toJsonAsBytes();

        // The bytes could be null if there is an issue with the JSON
serialization by
        // the Jackson JSON library.
```

```
        if (bytes == null) {
            System.out.println("Could not get JSON bytes for stock trade");
            return;
        }

        System.out.println("Putting trade: " + trade);
        PutRecordRequest request = PutRecordRequest.builder()
                .partitionKey(trade.getTickerSymbol()) // We use the ticker
 symbol as the partition key, explained in
                                                        // the Supplemental
 Information section below.
                .streamName(streamName)
                .data(SdkBytes.fromByteArray(bytes))
                .build();

        try {
            kinesisClient.putRecord(request);
        } catch (KinesisException e) {
            System.err.println(e.getMessage());
        }
    }

    private static void validateStream(KinesisClient kinesisClient, String
 streamName) {
        try {
            DescribeStreamRequest describeStreamRequest =
 DescribeStreamRequest.builder()
                    .streamName(streamName)
                    .build();

            DescribeStreamResponse describeStreamResponse =
 kinesisClient.describeStream(describeStreamRequest);

            if (!
describeStreamResponse.streamDescription().streamStatus().toString().equals("ACTIVE"))
 {
                System.err.println("Stream " + streamName + " is not active.
 Please wait a few moments and try again.");
                System.exit(1);
            }

        } catch (KinesisException e) {
            System.err.println("Error found while describing the stream " +
 streamName);
```

```
            System.err.println(e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutRecorda Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def put_record(self, data, partition_key):
        """
        Puts data into the stream. The data is formatted as JSON before it is
 passed
        to the stream.

        :param data: The data to put in the stream.
        :param partition_key: The partition key to use for the data.
        :return: Metadata about the record, including its shard ID and sequence
 number.
```

```
        """
        try:
            response = self.kinesis_client.put_record(
                StreamName=self.name, Data=json.dumps(data),
 PartitionKey=partition_key
            )
            logger.info("Put record in stream %s.", self.name)
        except ClientError:
            logger.exception("Couldn't put record in stream %s.", self.name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a PutRecordReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_record(client: &Client, stream: &str, key: &str, data: &str) ->
 Result<(), Error> {
    let blob = Blob::new(data);

    client
        .put_record()
        .data(blob)
        .partition_key(key)
        .stream_name(stream)
        .send()
        .await?;

    println!("Put data into stream.");
```

```
    Ok(())
}
```

- Para obter detalhes da API, consulte a PutRecordreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_kns->putrecord(            " oo_result is returned for
testing purposes. "
           iv_streamname = iv_stream_name
           iv_data       = iv_data
           iv_partitionkey = iv_partition_key
       ).
       MESSAGE 'Record created.' TYPE 'I'.
     CATCH /aws1/cx_knsinvalidargumentex .
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
     CATCH /aws1/cx_knskmsaccessdeniedex .
       MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
     CATCH /aws1/cx_knskmsdisabledex .
       MESSAGE 'KMS key used is disabled.' TYPE 'E'.
     CATCH /aws1/cx_knskmsinvalidstateex .
       MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
     CATCH /aws1/cx_knskmsnotfoundex .
       MESSAGE 'KMS key used is not found.' TYPE 'E'.
     CATCH /aws1/cx_knskmsoptinrequired .
       MESSAGE 'KMS key option is required.' TYPE 'E'.
     CATCH /aws1/cx_knskmsthrottlingex .
       MESSAGE 'The rate of requests to AWS KMS is exceeding the request
quotas.' TYPE 'E'.
     CATCH /aws1/cx_knsprovthruputexcdex .
```

```
        MESSAGE 'The request rate for the stream is too high, or the requested
 data is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutRecordreferência da API AWS SDK for SAP ABAP.

Registre um consumidor em um fluxo do Kinesis usando um SDK da AWS

Os exemplos de código a seguir mostram como registrar um consumidor em um fluxo do Kinesis.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// This example shows how to register a consumer to an Amazon Kinesis
    /// stream.
    /// </summary>
    public class RegisterConsumer
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();
            string consumerName = "NEW_CONSUMER_NAME";
            string streamARN = "arn:aws:kinesis:us-east-2:000000000000:stream/
AmazonKinesisStream";
```

```
            var consumer = await RegisterConsumerAsync(client, consumerName,
 streamARN);

            if (consumer is not null)
            {
                Console.WriteLine($"{consumer.ConsumerName}");
            }
        }

        /// <summary>
        /// Registers the consumer to a Kinesis stream.
        /// </summary>
        /// <param name="client">The initialized Kinesis client object.</param>
        /// <param name="consumerName">A string representing the consumer.</
param>
        /// <param name="streamARN">The ARN of the stream.</param>
        /// <returns>A Consumer object that contains information about the
 consumer.</returns>
        public static async Task<Consumer> RegisterConsumerAsync(IAmazonKinesis
 client, string consumerName, string streamARN)
        {
            var request = new RegisterStreamConsumerRequest
            {
                ConsumerName = consumerName,
                StreamARN = streamARN,
            };

            var response = await client.RegisterStreamConsumerAsync(request);
            return response.Consumer;
        }
    }
```

- Para obter detalhes da API, consulte RegisterStreamConsumera Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_kns->registerstreamconsumer(       " oo_result is returned
for testing purposes. "
           iv_streamarn = iv_stream_arn
           iv_consumername = iv_consumer_name
       ).
       MESSAGE 'Stream consumer registered.' TYPE 'I'.
     CATCH /aws1/cx_knsinvalidargumentex .
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
     CATCH /aws1/cx_sgmresourcelimitexcd.
       MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
     CATCH /aws1/cx_sgmresourceinuse.
       MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
     CATCH /aws1/cx_sgmresourcenotfound.
       MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a RegisterStreamConsumerreferência da API AWS SDK for SAP ABAP.

Cenários para o Kinesis usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Kinesis com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar as operações básicas de fluxo de dados do Kinesis usando um SDK da AWS

Comece a usar as operações básicas de fluxo de dados do Kinesis usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Crie um stream e coloque um registro nele.
- Crie um iterador de fragmentos.
- Leia o registro e, em seguida, limpe os recursos.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_stream_describe_result TYPE REF TO /aws1/cl_knsdescrstreamoutput.
    DATA lo_stream_description TYPE REF TO /aws1/cl_knsstreamdescription.
    DATA lo_sharditerator TYPE REF TO /aws1/cl_knsgetsharditerator01.
    DATA lo_record_result TYPE REF TO /aws1/cl_knsputrecordoutput.

    "Create stream."
    TRY.
        lo_kns->createstream(
            iv_streamname = iv_stream_name
            iv_shardcount = iv_shard_count
        ).
        MESSAGE 'Stream created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex.
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceeded
exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourceinuseex .
```

```
        MESSAGE 'The request processing has failed because the resource is in
 use.' TYPE 'E'.
    ENDTRY.

    "Wait for stream to becomes active."
    lo_stream_describe_result = lo_kns->describestream( iv_streamname =
 iv_stream_name ).
    lo_stream_description = lo_stream_describe_result->get_streamdescription( ).
    WHILE lo_stream_description->get_streamstatus( ) <> 'ACTIVE'.
      IF sy-index = 30.
        EXIT.               "maximum 5 minutes"
      ENDIF.
      WAIT UP TO 10 SECONDS.
      lo_stream_describe_result = lo_kns->describestream( iv_streamname =
 iv_stream_name ).
      lo_stream_description =  lo_stream_describe_result-
>get_streamdescription( ).
    ENDWHILE.

    "Create record."
    TRY.
        lo_record_result = lo_kns->putrecord(
            iv_streamname = iv_stream_name
            iv_data       = iv_data
            iv_partitionkey = iv_partition_key
        ).
        MESSAGE 'Record created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
 'E'.
      CATCH /aws1/cx_knskmsdisabledex .
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request
 quotas.' TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
```

```
        MESSAGE 'The request rate for the stream is too high, or the requested
data is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Create a shard iterator in order to read the record."
    TRY.
        lo_sharditerator = lo_kns->getsharditerator(
          iv_shardid = lo_record_result->get_shardid( )
          iv_sharditeratortype = iv_sharditeratortype
          iv_streamname = iv_stream_name
      ).
        MESSAGE 'Shard iterator created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex.
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested
data is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Read the record."
    TRY.
        oo_result = lo_kns->getrecords(                    " oo_result is
returned for testing purposes. "
            iv_sharditerator   = lo_sharditerator->get_sharditerator( )
        ).
        MESSAGE 'Shard iterator created.' TYPE 'I'.
      CATCH /aws1/cx_knsexpirediteratorex .
        MESSAGE 'Iterator expired.' TYPE 'E'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
      CATCH /aws1/cx_knskmsdisabledex .
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
```

```
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request
quotas.' TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested
data is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Delete stream."
    TRY.
        lo_kns->deletestream(
            iv_streamname = iv_stream_name
        ).
        MESSAGE 'Stream deleted.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceeded
exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourceinuseex .
        MESSAGE 'The request processing has failed because the resource is in
use.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateStream
  - DeleteStream
  - GetRecords
  - GetShardIterator
  - PutRecord

Exemplos de tecnologia sem servidor para o Lambda usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Kinesis com SDKs da AWS.

Exemplos

- Invocar uma função do Lambda em um trigger do Kinesis
- Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

Invocar uma função do Lambda em um trigger do Kinesis

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando .NET.

```
using System.Text;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace KinesisIntegrationSampleCode;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task FunctionHandler(KinesisEvent evnt, ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
```

```
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return;
        }

        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                throw;
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent) error {
 if len(kinesisEvent.Records) == 0 {
  log.Printf("empty Kinesis event received")
  return nil
 }

 for _, record := range kinesisEvent.Records {
  log.Printf("processed Kinesis event with EventId: %v", record.EventID)
  recordDataBytes := record.Kinesis.Data
  recordDataText := string(recordDataBytes)
  log.Printf("record data: %v", recordDataText)
  // TODO: Do interesting work based on the new data
 }
 log.Printf("successfully processed %v records", len(kinesisEvent.Records))
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;

public class Handler implements RequestHandler<KinesisEvent, Void> {
    @Override
    public Void handleRequest(final KinesisEvent event, final Context context) {
        LambdaLogger logger = context.getLogger();
        if (event.getRecords().isEmpty()) {
            logger.log("Empty Kinesis Event received");
            return null;
        }
        for (KinesisEvent.KinesisEventRecord record : event.getRecords()) {
            try {
                logger.log("Processed Event with EventId: "+record.getEventID());
                String data = new String(record.getKinesis().getData().array());
                logger.log("Data:"+ data);
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex) {
                logger.log("An error occurred:"+ex.getMessage());
                throw ex;
            }
        }
```

```
        logger.log("Successfully processed:"+event.getRecords().size()+"
 records");
        return null;
    }

}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do Kinesis com o uso do Lambda. JavaScript

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      throw err;
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Consumindo um evento do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      throw err;
    }
    logger.info(`Successfully processed ${event.Records.length} records.`);
  }
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Kinesis\KinesisHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler extends KinesisHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handleKinesis(KinesisEvent $event, Context $context): void
    {
        $this->logger->info("Processing records");
        $records = $event->getRecords();
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
```

```
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                throw $e;
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Python.

```
import base64
def lambda_handler(event, context):

    for record in event['Records']:
        try:
            print(f"Processed Kinesis Event - EventID: {record['eventID']}")
            record_data = base64.b64decode(record['kinesis']
['data']).decode('utf-8')
            print(f"Record Data: {record_data}")
            # TODO: Do interesting work based on the new data
        except Exception as e:
            print(f"An error occurred {e}")
            raise e
    print(f"Successfully processed {len(event['Records'])} records.")
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::event::kinesis::KinesisEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) -> Result<(), Error>
 {
    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(());
    }

    event.payload.records.iter().for_each(|record| {
        tracing::info!("EventId:
 {}",record.event_id.as_deref().unwrap_or_default());

        let record_data = std::str::from_utf8(&record.kinesis.data);

        match record_data {
            Ok(data) => {
                // log the record data
                tracing::info!("Data: {}", data);
            }
            Err(e) => {
                tracing::error!("Error: {}", e);
            }
        }
    });

    tracing::info!(
```

```
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

Os exemplos de código a seguir mostram como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando o .NET.

```
using System.Text;
using System.Text.Json.Serialization;
```

```
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace KinesisIntegration;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task<StreamsEventResponse> FunctionHandler(KinesisEvent evnt,
 ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return new StreamsEventResponse();
        }

        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                /* Since we are working with streams, we can return the failed
 item immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                return new StreamsEventResponse
                {
```

```
                    BatchItemFailures = new
 List<StreamsEventResponse.BatchItemFailure>
                    {
                        new StreamsEventResponse.BatchItemFailure
 { ItemIdentifier = record.Kinesis.SequenceNumber }
                    }
                };
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
        return new StreamsEventResponse();
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}

public class StreamsEventResponse
{
    [JsonPropertyName("batchItemFailures")]
    public IList<BatchItemFailure> BatchItemFailures { get; set; }
    public class BatchItemFailure
    {
        [JsonPropertyName("itemIdentifier")]
        public string ItemIdentifier { get; set; }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, record := range kinesisEvent.Records {
  curRecordSequenceNumber := ""

  // Process your record
  if /* Your record processing condition here */ {
   curRecordSequenceNumber = record.Kinesis.SequenceNumber
  }

  // Add a condition to check if the record processing failed
  if curRecordSequenceNumber != "" {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": curRecordSequenceNumber})
  }
 }

 kinesisBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
```

```
 return kinesisBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;
import com.amazonaws.services.lambda.runtime.events.StreamsEventResponse;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.List;

public class ProcessKinesisRecords implements RequestHandler<KinesisEvent,
 StreamsEventResponse> {

    @Override
    public StreamsEventResponse handleRequest(KinesisEvent input, Context
 context) {

        List<StreamsEventResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<>();
        String curRecordSequenceNumber = "";

        for (KinesisEvent.KinesisEventRecord kinesisEventRecord :
 input.getRecords()) {
```

```
            try {
                //Process your record
                KinesisEvent.Record kinesisRecord =
 kinesisEventRecord.getKinesis();
                curRecordSequenceNumber = kinesisRecord.getSequenceNumber();

            } catch (Exception e) {
                /* Since we are working with streams, we can return the failed
 item immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                batchItemFailures.add(new
 StreamsEventResponse.BatchItemFailure(curRecordSequenceNumber));
                return new StreamsEventResponse(batchItemFailures);
            }
        }

       return new StreamsEventResponse(batchItemFailures);
    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
```

```
      console.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
            Lambda will immediately begin to retry processing from this failed
 item onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Relatando falhas de itens em lote do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
  KinesisStreamBatchResponse,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<KinesisStreamBatchResponse> => {
  for (const record of event.Records) {
```

```
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
           Lambda will immediately begin to retry processing from this failed
 item onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  logger.info(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando PHP.

```
<?php
```

```
# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $kinesisEvent = new KinesisEvent($event);
        $this->logger->info("Processing records");
        $records = $kinesisEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getSequenceNumber();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");

        // change format for the response
```

```
        $failures = array_map(
            fn(string $sequenceNumber) => ['itemIdentifier' => $sequenceNumber],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Python.

```
def handler(event, context):
    records = event.get("Records")
    curRecordSequenceNumber = ""

    for record in records:
        try:
            # Process your record
            curRecordSequenceNumber = record["kinesis"]["sequenceNumber"]
        except Exception as e:
            # Return failed record's sequence number
            return {"batchItemFailures":[{"itemIdentifier":
 curRecordSequenceNumber}]}

    return {"batchItemFailures":[]}
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relate falhas de itens em lote do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::kinesis::KinesisEvent,
    kinesis::KinesisEventRecord,
    streams::{KinesisBatchItemFailure, KinesisEventResponse},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) ->
 Result<KinesisEventResponse, Error> {
    let mut response = KinesisEventResponse {
        batch_item_failures: vec![],
    };

    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(response);
    }

    for record in &event.payload.records {
        tracing::info!(
            "EventId: {}",
            record.event_id.as_deref().unwrap_or_default()
        );

        let record_processing_result = process_record(record);

        if record_processing_result.is_err() {
            response.batch_item_failures.push(KinesisBatchItemFailure {
```

```
                item_identifier: record.kinesis.sequence_number.clone(),
            });
            /* Since we are working with streams, we can return the failed item
 immediately.
            Lambda will immediately begin to retry processing from this failed
 item onwards. */
            return Ok(response);
        }
    }

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(response)
}

fn process_record(record: &KinesisEventRecord) -> Result<(), Error> {
    let record_data = std::str::from_utf8(record.kinesis.data.as_slice());

    if let Some(err) = record_data.err() {
        tracing::error!("Error: {}", err);
        return Err(Error::from(err));
    }

    let record_data = record_data.unwrap_or_default();

    // do something interesting with the data
    tracing::info!("Data: {}", record_data);

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();
```

```
    run(service_fn(function_handler)).await
}
```

Exemplos de código para Firehose usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Data Firehose com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Firehose — Mais informações sobre o Firehose.
- Referência da API Firehose — Detalhes sobre todas as ações disponíveis do Firehose.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para Firehose usando SDKs AWS
  - Grave vários registros do Firehose usando um SDK AWS

Ações para Firehose usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Data Firehose com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos

- Grave vários registros do Firehose usando um SDK AWS

Grave vários registros do Firehose usando um SDK AWS

Os exemplos de código a seguir mostram como gravar vários registros de dados em um stream de entrega do Firehose em uma única chamada, o que pode atingir uma taxa de transferência maior por produtor do que ao gravar registros únicos.

CLI

AWS CLI

Como gravar vários registros em um fluxo

O exemplo de `put-record-batch` a seguir grava três registro em um fluxo. Os dados são codificados no formato Base64.

```
aws firehose put-record-batch \
    --delivery-stream-name my-stream \
    --records file://records.json
```

Conteúdo de `myfile.json`:

```
[
    {"Data": "Rmlyc3QgdGhpbmc="},
    {"Data": "U2Vjb25kIHRoaW5n"},
    {"Data": "VGhpcmQgdGhpbmc="}
]
```

Saída:

```
{
    "FailedPutCount": 0,
    "Encrypted": false,
    "RequestResponses": [
        {
            "RecordId": "9D2OJ6t2EqCTZTXwGzeSv/EVHxRoRCw89xd+o3+sXg8DhYOaWKPSmZy/
CGlRVEys1u1xbeKh6VofEYKkoeiDrcjrxhQp9iF7sUW7pujiMEQ5LzlrzCkGosxQn
+3boDnURDEaD42V7GiixpOyLJkYZcae1i7HzlCEoy9LJhMr8EjDSi4Om/9Vc2uhwwuAtGE0XKpxJ2WD7ZRWtAnYlK
        },
        {
            "RecordId": "jFirejqxCLlK5xjH/UNmlMVcjktEN76I7916X9PaZ
+PVaOSXDfU1WGOqEZhxq2js7xcZ552eoeDxsuTU1MSq9nZTbVfb6cQTIXnm/
```

```
GsuF37Uhg67GKmR5z90l6XKJ+/
+pDloFv7Hh9a3oUS6wYm3DcNRLTHHAimANp1PhkQvWpvLRfzbuCUkBphR2QVzhP9OiHLbzGwy8/
DfH8sqWEUYASNJKS8GXP5s"
        },
        {
            "RecordId":
 "oy0amQ40o5Y2YV4vxzufdcMOOw6n3EPr3tpPJGoYVNKH4APPVqNcbUgefo1stEFRg4hTLrf2k6eliHu/9+YJ5R3
DTBt3qBlmTj7Xq8SKVbO1S7YvMTpWkMKA86f8JfmT8BMKoMb4XZS/sOkQLe+qh0sYKXWl"
        }
    ]
}
```

Para obter mais informações, consulte Sending Data to an Amazon Kinesis Data Firehose Delivery Stream no Guia do desenvolvedor do Amazon Kinesis Data Firehose.

- Para obter detalhes da API, consulte PutRecordBatchna Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn put_record_batch(
    client: &Client,
    stream: &str,
    data: Vec<Record>,
) -> Result<PutRecordBatchOutput, SdkError<PutRecordBatchError>> {
    client
        .put_record_batch()
        .delivery_stream_name(stream)
        .set_records(Some(data))
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a PutRecordBatchreferência da API AWS SDK for Rust.

Exemplos de código para o AWS KMS usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Key Management Service (AWS KMS) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do AWS KMS – Mais informações sobre o AWS KMS.
- Referência da API do AWS KMS – Detalhes sobre todas as ações disponíveis do AWS KMS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o AWS KMS usando AWS SDKs
  - Crie uma concessão para uma AWS KMS key usando um SDK da AWS
  - Criar uma AWS KMS key usando um SDK da AWS
  - Gere uma string de bytes aleatória usando um SDK da AWS
  - Criar um alias para uma AWS KMS key usando um SDK da AWS
  - Decriptografe texto cifrado com uma AWS KMS key usando um SDK da AWS
  - Exclua um alias do AWS KMS usando um SDK da AWS
  - Descrever casos do AWS KMS key usando um SDK da AWS
  - Desabilite uma AWS KMS key usando um SDK da AWS
  - Habilite uma AWS KMS key usando um SDK da AWS

- Criptografe texto usando uma AWS KMS key usando um SDK da AWS
- Gere uma chave de dados em texto simples para criptografia do lado do cliente usando um SDK da AWS
- Gere uma chave de dados criptografada usando um AWS da SDK
- Obtenha uma política para uma AWS KMS key usando um SDK da AWS
- Liste os aliases definidos para uma AWS KMS key usando um SDK da AWS
- Liste as concessões para uma AWS KMS key usando um SDK da AWS
- Liste AWS KMS keys usando um SDK da AWS
- Liste políticas para uma AWS KMS key usando um SDK da AWS
- Recriptografe texto cifrado de uma AWS KMS key para outra usando um SDK da AWS
- Retire uma concessão para uma AWS KMS key usando um SDK da AWS
- Revogue uma concessão para uma AWS KMS key usando um SDK da AWS
- Agende a exclusão de uma AWS KMS key usando um SDK da AWS
- Defina a política para AWS KMS key usando um SDK da AWS
- Atualize a AWS KMS key referida por um alias usando um SDK da AWS

- Cenários para o AWS KMS usando AWS SDKs
  - Criptografe e descriptografe texto com AWS KMS keys usando um SDK da AWS
  - Gerencie AWS KMS keys usando um SDK da AWS

Ações para o AWS KMS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Key Management Service (AWS KMS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o AWS KMS usando AWS SDKs.

Exemplos

- Crie uma concessão para uma AWS KMS key usando um SDK da AWS
- Criar uma AWS KMS key usando um SDK da AWS
- Gere uma string de bytes aleatória usando um SDK da AWS
- Criar um alias para uma AWS KMS key usando um SDK da AWS
- Decriptografe texto cifrado com uma AWS KMS key usando um SDK da AWS

- Exclua um alias do AWS KMS usando um SDK da AWS
- Descrever casos do AWS KMS key usando um SDK da AWS
- Desabilite uma AWS KMS key usando um SDK da AWS
- Habilite uma AWS KMS key usando um SDK da AWS
- Criptografe texto usando uma AWS KMS key usando um SDK da AWS
- Gere uma chave de dados em texto simples para criptografia do lado do cliente usando um SDK da AWS
- Gere uma chave de dados criptografada usando um AWS da SDK
- Obtenha uma política para uma AWS KMS key usando um SDK da AWS
- Liste os aliases definidos para uma AWS KMS key usando um SDK da AWS
- Liste as concessões para uma AWS KMS key usando um SDK da AWS
- Liste AWS KMS keys usando um SDK da AWS
- Liste políticas para uma AWS KMS key usando um SDK da AWS
- Recriptografe texto cifrado de uma AWS KMS key para outra usando um SDK da AWS
- Retire uma concessão para uma AWS KMS key usando um SDK da AWS
- Revogue uma concessão para uma AWS KMS key usando um SDK da AWS
- Agende a exclusão de uma AWS KMS key usando um SDK da AWS
- Defina a política para AWS KMS key usando um SDK da AWS
- Atualize a AWS KMS key referida por um alias usando um SDK da AWS

Crie uma concessão para uma AWS KMS key usando um SDK da AWS

O exemplo de código a seguir mostra como criar uma concessão para uma chave KMS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static async Task Main()
        {
            var client = new AmazonKeyManagementServiceClient();

            // The identity that is given permission to perform the operations
            // specified in the grant.
            var grantee = "arn:aws:iam::111122223333:role/ExampleRole";

            // The identifier of the AWS KMS key to which the grant applies. You
            // can use the key ID or the Amazon Resource Name (ARN) of the KMS
key.
            var keyId = "7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";

            var request = new CreateGrantRequest
            {
                GranteePrincipal = grantee,
                KeyId = keyId,

                // A list of operations that the grant allows.
                Operations = new List<string>
                {
                    "Encrypt",
                    "Decrypt",
                },
            };

            var response = await client.CreateGrantAsync(request);

            string grantId = response.GrantId; // The unique identifier of the
grant.
            string grantToken = response.GrantToken; // The grant token.

            Console.WriteLine($"Id: {grantId}, Token: {grantToken}");
        }
    }
```

- Para obter detalhes da API, consulte CreateGrant a Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar uma concessão

O exemplo de `create-grant` a seguir cria uma concessão que permite que o usuário `exampleUser` use o comando `decrypt` na chave do KMS `1234abcd-12ab-34cd-56ef-1234567890ab` de exemplo. A entidade principal descontinuada é o perfil `adminRole`. A concessão usa a restrição de concessão `EncryptionContextSubset` para conceder essa permissão apenas quando o contexto de criptografia na solicitação `decrypt` incluir o par de chave/valor `"Department": "IT"`.

```
aws kms create-grant \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --grantee-principal arn:aws:iam::123456789012:user/exampleUser \
    --operations Decrypt \
    --constraints EncryptionContextSubset={Department=IT} \
    --retiring-principal arn:aws:iam::123456789012:role/adminRole
```

Saída:

```
{
    "GrantId":
 "1a2b3c4d2f5e69f440bae30eaec9570bb1fb7358824f9ddfa1aa5a0dab1a59b2",
    "GrantToken": "<grant token here>"
}
```

Use o `list-grants` comando para visualizar informações detalhadas sobre a concessão.

Para obter mais informações, consulte Grants in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte CreateGrantna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateGrantRequest;
import software.amazon.awssdk.services.kms.model.CreateGrantResponse;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateGrant {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId> <granteePrincipal> <operation>\s

                Where:
                    keyId - The unique identifier for the customer master key
 (CMK) that the grant applies to.\s
                    granteePrincipal - The principal that is given permission to
 perform the operations that the grant permits.\s
                    operation - An operation (for example, Encrypt).\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String keyId = args[0];
        String granteePrincipal = args[1];
        String operation = args[2];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        String grantId = createGrant(kmsClient, keyId, granteePrincipal,
 operation);
        System.out.printf("Successfully created a grant with ID %s%n", grantId);
        kmsClient.close();
    }

    public static String createGrant(KmsClient kmsClient, String keyId, String
 granteePrincipal, String operation) {
        try {
            CreateGrantRequest grantRequest = CreateGrantRequest.builder()
                    .keyId(keyId)
                    .granteePrincipal(granteePrincipal)
                    .operationsWithStrings(operation)
                    .build();

            CreateGrantResponse response = kmsClient.createGrant(grantRequest);
            return response.grantId();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateGrant a Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewGrant(keyIdVal: String?, granteePrincipalVal: String?,
 operation: String): String? {

    val operationOb = GrantOperation.fromValue(operation)
    val grantOperationList = ArrayList<GrantOperation>()
    grantOperationList.add(operationOb)

    val request = CreateGrantRequest {
        keyId = keyIdVal
        granteePrincipal = granteePrincipalVal
        operations = grantOperationList
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.createGrant(request)
        return response.grantId
    }
}
```

- Para obter detalhes da API, consulte a CreateGrantreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def create_grant(self, key_id):
        """
        Creates a grant for a key that lets a principal generate a symmetric data
        encryption key.

        :param key_id: The ARN or ID of the key.
        :return: The grant that is created.
        """
        principal = input(
            f"Enter the ARN of a principal, such as an IAM role, to grant that
 role "
            f"GenerateDataKey permissions on key {key_id}: "
        )
        if principal != "":
            try:
                grant = self.kms_client.create_grant(
                    KeyId=key_id,
                    GranteePrincipal=principal,
                    Operations=["GenerateDataKey"],
                )
            except ClientError as err:
                logger.error(
                    "Couldn't create a grant on key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Grant created on key {key_id}.")
                return grant
        else:
            print("Skipping grant creation.")
```

- Para obter detalhes da API, consulte a CreateGrantReferência da API AWSSDK for Python (Boto3).

Criar uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma AWS KMS key.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Shows how to create a new AWS Key Management Service (AWS KMS)
/// key.
/// </summary>
public class CreateKey
{
    public static async Task Main()
    {
        // Note that if you need to create a Key in an AWS Region
        // other than the Region defined for the default user, you need to
        // pass the Region to the client constructor.
        var client = new AmazonKeyManagementServiceClient();

        // The call to CreateKeyAsync will create a symmetrical AWS KMS
        // key. For more information about symmetrical and asymmetrical
        // keys, see:
        //
```

```
            // https://docs.aws.amazon.com/kms/latest/developerguide/symm-asymm-
choose.html
            var response = await client.CreateKeyAsync(new CreateKeyRequest());

            // The KeyMetadata object contains information about the new AWS KMS
 key.
            KeyMetadata keyMetadata = response.KeyMetadata;

            if (keyMetadata is not null)
            {
                Console.WriteLine($"KMS Key: {keyMetadata.KeyId} was successfully
 created.");
            }
            else
            {
                Console.WriteLine("Could not create KMS Key.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar uma chave do KMS gerenciada pelo cliente no AWS KMS

O exemplo de `create-key` a seguir cria uma chave do KMS de criptografia simétrica.

Não é necessário especificar parâmetros para criar a chave básica do KMS (uma chave de criptografia simétrica). Os valores padrão desses parâmetros criam uma chave de criptografia simétrica.

Como esse comando não especifica uma política de chave, a chave do KMS adota a política de chave padrão para chaves do KMS criadas programaticamente. Use o comando `get-key-policy` para visualizar a política de chave. Use o comando `put-key-policy` para alterar a política de chave.

```
aws kms create-key
```

O comando `create-key` retorna os metadados da chave, incluindo o ID da chave e o ARN da nova chave do KMS. Use esses valores para identificar a chave do KMS em outras operações do AWS KMS. A saída não inclui as tags. Use `list-resource-tags command` para visualizar as tags de uma chave do KMS.

Saída:

```
{
    "KeyMetadata": {
        "AWSAccountId": "111122223333",
        "Arn": "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "CreationDate": "2017-07-05T14:04:55-07:00",
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "Description": "",
        "Enabled": true,
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "SYMMETRIC_DEFAULT",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": false,
        "Origin": "AWS_KMS"
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ]
    }
}
```

Observação: o comando `create-key` não permite especificar um alias. Use o comando `create-alias` para especificar um alias para a nova chave do KMS.

Para obter mais informações, consulte Creating keys no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 2: como criar uma chave RSA assimétrica do KMS para criptografia e decodificação

O exemplo de `create-key` a seguir cria uma chave do KMS que contém um par de chaves RSA assimétrico para criptografia e descriptografia.

```
aws kms create-key \
   --key-spec RSA_4096 \
```

```
    --key-usage ENCRYPT_DECRYPT
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "AWSAccountId": "111122223333",
        "CreationDate": "2021-04-05T14:04:55-07:00",
        "CustomerMasterKeySpec": "RSA_4096",
        "Description": "",
        "Enabled": true,
        "EncryptionAlgorithms": [
            "RSAES_OAEP_SHA_1",
            "RSAES_OAEP_SHA_256"
        ],
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "RSA_4096",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": false,
        "Origin": "AWS_KMS"
    }
}
```

Para obter mais informações, consulte Asymmetric keys in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 3: como criar uma chave do KMS de curva elíptica assimétrica para assinatura e verificação

Como criar uma chave do KMS assimétrica que contém um par de chaves com curva elíptica (ECC) assimétrica para assinatura e verificação. O parâmetro `--key-usage` é obrigatório, embora `SIGN_VERIFY` seja o único valor válido para chaves ECC do KMS.

```
aws kms create-key \
    --key-spec ECC_NIST_P521 \
    --key-usage SIGN_VERIFY
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "AWSAccountId": "111122223333",
        "CreationDate": "2019-12-02T07:48:55-07:00",
        "CustomerMasterKeySpec": "ECC_NIST_P521",
        "Description": "",
        "Enabled": true,
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "ECC_NIST_P521",
        "KeyState": "Enabled",
        "KeyUsage": "SIGN_VERIFY",
        "MultiRegion": false,
        "Origin": "AWS_KMS",
        "SigningAlgorithms": [
            "ECDSA_SHA_512"
        ]
    }
}
```

Para obter mais informações, consulte Asymmetric keys in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 4: como criar uma chave do KMS com HMAC

O exemplo de `create-key` a seguir cria uma chave do KMS com HMAC de 384 bits. O valor `GENERATE_VERIFY_MAC` é obrigatório para o parâmetro `--key-usage`, mesmo que seja o único valor válido para chaves do KMS com HMAC.

```
aws kms create-key \
    --key-spec HMAC_384 \
    --key-usage GENERATE_VERIFY_MAC
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "AWSAccountId": "111122223333",
```

```
        "CreationDate": "2022-04-05T14:04:55-07:00",
        "CustomerMasterKeySpec": "HMAC_384",
        "Description": "",
        "Enabled": true,
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "HMAC_384",
        "KeyState": "Enabled",
        "KeyUsage": "GENERATE_VERIFY_MAC",
        "MacAlgorithms": [
            "HMAC_SHA_384"
        ],
        "MultiRegion": false,
        "Origin": "AWS_KMS"
    }
}
```

Para obter mais informações, consulte HMAC keys in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 4: como criar uma chave do KMS primária multirregional

O exemplo de `create-key` a seguir cria uma chave primária de criptografia simétrica multirregional. Como os valores padrão de todos os parâmetros criam uma chave de criptografia simétrica, somente o parâmetro `--multi-region` é necessário para a chave do KMS. Na AWS CLI, especifique o nome do parâmetro para indicar que o parâmetro booleano é verdadeiro.

```
aws kms create-key \
    --multi-region
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-west-2:111122223333:key/
mrk-1234abcd12ab34cd56ef12345678990ab",
        "AWSAccountId": "111122223333",
        "CreationDate": "2021-09-02T016:15:21-09:00",
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "Description": "",
        "Enabled": true,
```

```
        "EncryptionAlgorithms": [
          "SYMMETRIC_DEFAULT"
        ],
        "KeyId": "mrk-1234abcd12ab34cd56ef12345678990ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "SYMMETRIC_DEFAULT",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": true,
        "MultiRegionConfiguration": {
            "MultiRegionKeyType": "PRIMARY",
            "PrimaryKey": {
                "Arn": "arn:aws:kms:us-west-2:111122223333:key/
mrk-1234abcd12ab34cd56ef12345678990ab",
                "Region": "us-west-2"
            },
            "ReplicaKeys": []
        },
        "Origin": "AWS_KMS"
    }
}
```

Para obter mais informações, consulte Asymmetric keys in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 5: como criar uma chave do KMS para material de chave importada

O exemplo de `create-key` a seguir cria uma chave do KMS sem material de chave. Quando a operação for concluída, você poderá importar seu próprio material de chave na chave do KMS. Defina o parâmetro `--origin` como `EXTERNAL` para criar a chave do KMS.

```
aws kms create-key \
    --origin EXTERNAL
```

Saída:

```
{
     "KeyMetadata": {
         "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
         "AWSAccountId": "111122223333",
         "CreationDate": "2019-12-02T07:48:55-07:00",
         "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
```

```
        "Description": "",
        "Enabled": false,
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ],
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "SYMMETRIC_DEFAULT",
        "KeyState": "PendingImport",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": false,
        "Origin": "EXTERNAL"
    }
}
```

Para obter mais informações, consulte Importing key material in AWS KMS keys no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 6: como criar uma chave do KMS em um repositório de chaves do AWS CloudHSM

O exemplo de `create-key` a seguir cria uma chave do KMS no repositório de chaves do AWS CloudHSM especificado. A operação cria a chave do KMS e seus metadados no AWS KMS e cria o material da chave no cluster do AWS CloudHSM associado ao repositório de chaves personalizadas. Os parâmetros `--custom-key-store-id` e `--origin` são obrigatórios.

```
aws kms create-key \
    --origin AWS_CLOUDHSM \
    --custom-key-store-id cks-1234567890abcdef0
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "AWSAccountId": "111122223333",
        "CloudHsmClusterId": "cluster-1a23b4cdefg",
        "CreationDate": "2019-12-02T07:48:55-07:00",
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "CustomKeyStoreId": "cks-1234567890abcdef0",
        "Description": "",
```

```
        "Enabled": true,
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ],
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "SYMMETRIC_DEFAULT",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": false,
        "Origin": "AWS_CLOUDHSM"
    }
}
```

Para obter mais informações, consulte AWS CloudHSM key stores no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 7: como criar uma chave do KMS em um repositório de chaves externo

O exemplo de `create-key` a seguir cria uma chave do KMS no repositório de chaves externo especificado. Os parâmetros `--custom-key-store-id`, `--origin` e `--xks-key-id` são obrigatórios neste comando.

O parâmetro `--xks-key-id` especifica o ID de uma chave de criptografia simétrica existente no gerenciador de chaves externo. Essa chave serve como o material de chave externo para a chave do KMS. O valor do parâmetro `--origin` deve ser `EXTERNAL_KEY_STORE`. O parâmetro `custom-key-store-id` deve identificar um repositório de chaves externo conectado ao proxy do repositório de chaves externo.

```
aws kms create-key \
    --origin EXTERNAL_KEY_STORE \
    --custom-key-store-id cks-9876543210fedcba9 \
    --xks-key-id bb8562717f809024
```

Saída:

```
{
    "KeyMetadata": {
        "Arn": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "AWSAccountId": "111122223333",
        "CreationDate": "2022-12-02T07:48:55-07:00",
```

```
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "CustomKeyStoreId": "cks-9876543210fedcba9",
        "Description": "",
        "Enabled": true,
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ],
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeySpec": "SYMMETRIC_DEFAULT",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "MultiRegion": false,
        "Origin": "EXTERNAL_KEY_STORE",
        "XksKeyConfiguration": {
            "Id": "bb8562717f809024"
        }
    }
}
```

Para obter mais informações, consulte External key stores no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte CreateKeyna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateKeyRequest;
import software.amazon.awssdk.services.kms.model.CustomerMasterKeySpec;
import software.amazon.awssdk.services.kms.model.CreateKeyResponse;
import software.amazon.awssdk.services.kms.model.KmsException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateCustomerKey {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        String keyDesc = "Created by the AWS KMS API";
        System.out.println("The key id is " + createKey(kmsClient, keyDesc));
        kmsClient.close();
    }

    public static String createKey(KmsClient kmsClient, String keyDesc) {
        try {
            CreateKeyRequest keyRequest = CreateKeyRequest.builder()
                    .description(keyDesc)

 .customerMasterKeySpec(CustomerMasterKeySpec.SYMMETRIC_DEFAULT)
                    .keyUsage("ENCRYPT_DECRYPT")
                    .build();

            CreateKeyResponse result = kmsClient.createKey(keyRequest);
            System.out.printf("Created a customer key with id \"%s\"%n",
 result.keyMetadata().arn());
            return result.keyMetadata().keyId();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createKey(keyDesc: String?): String? {

    val request = CreateKeyRequest {
        description = keyDesc
        customerMasterKeySpec = CustomerMasterKeySpec.SymmetricDefault
        keyUsage = KeyUsageType.fromValue("ENCRYPT_DECRYPT")
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val result = kmsClient.createKey(request)
        println("Created a customer key with id " + result.keyMetadata?.arn)
        return result.keyMetadata?.keyId
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def create_key(self):
        """
        Creates a key (or multiple keys) with a user-provided description.
        """
        answer = "y"
        while answer.lower() == "y":
            key_desc = input("\nLet's create a key. Describe it for me: ")
            if not key_desc:
                key_desc = "Key management demo key"
            try:
                key = self.kms_client.create_key(Description=key_desc)
["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't create your key. Here's why: %s",
                    err.response["Error"]["Message"],
                )
                raise
            else:
                print("Key created:")
                pprint(key)
                self.created_keys.append(key)
                answer = input("Create another (y/n)? ")
```

- Para obter detalhes da API, consulte a CreateKeyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms" # v2: require 'aws-sdk'

# Create a AWS KMS key.
# As long we are only encrypting small amounts of data (4 KiB or less) directly,
# a KMS key is fine for our purposes.
# For larger amounts of data,
# use the KMS key to encrypt a data encryption key (DEK).

client = Aws::KMS::Client.new

resp = client.create_key({
                           tags: [
                             {
                               tag_key: "CreatedBy",
                               tag_value: "ExampleUser"
                             }
                           ]
                         })

puts resp.key_metadata.key_id
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client) -> Result<(), Error> {
    let resp = client.create_key().send().await?;

    let id = resp.key_metadata.as_ref().unwrap().key_id();

    println!("Key: {}", id);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateKeyreferência da API AWS SDK for Rust.

Gere uma string de bytes aleatória usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma string de bytes aleatória que é criptograficamente segura usando o AWS KMS.

CLI

AWS CLI

Exemplo 1: como gerar uma string de bytes aleatória de 256 bits (Linux ou macOS)

O exemplo de `generate-random` a seguir gera uma string de bytes aleatórios de 256 bits (32 bytes) codificada em base64. O exemplo decodifica a string de bytes e a salva no arquivo aleatório.

Ao executar esse comando, use o parâmetro `number-of-bytes` para especificar o tamanho do valor aleatório em bytes.

Você não especifica uma chave do KMS ao executar esse comando. A sequência de bytes aleatória não está relacionada a nenhuma chave do KMS.

Por padrão, o AWS KMS gera o número aleatório. No entanto, se você especificar um armazenamento de chaves personalizadas< https://docs.aws.amazon.com/kms/latest/developerguide/ custom-key-store-overview .html>, a sequência de bytes aleatória será gerada no cluster do CloudHSM AWS associado ao armazenamento de chaves personalizadas.

Este exemplo usa os seguintes parâmetros e valores:

Ele usa o parâmetro obrigatório `--number-of-bytes` com o valor de `32` para solicitar uma string de 32 bytes (256 bits). Ele usa o parâmetro `--output` com o valor de `text` para direcionar a AWS CLI a retornar a saída como texto em vez de um JSON. Ele usa `--query parameter` para extrair o valor da propriedade `Plaintext` da resposta. Ele canaliza (|) a saída do comando para o utilitário `base64`, que decodifica a saída extraída. Ele usa o operador de redirecionamento (>) para salvar a string de bytes decodificada no arquivo `ExampleRandom`. Ele usa o operador de redirecionamento (>) para salvar o texto cifrado binário em um arquivo.

```
aws kms generate-random \
    --number-of-bytes 32 \
    --output text \
    --query Plaintext | base64 --decode > ExampleRandom
```

Este comando não produz saída.

Para obter mais informações, consulte GenerateRandoma Referência da API do AWS Key Management Service.

Exemplo 2: como gerar um número aleatório de 256 bits (prompt de comando do Windows)

O exemplo a seguir usa o comando `generate-random` para gerar uma string aleatória de 256 bits (32 bytes) codificada em base64. O exemplo decodifica a string de bytes e a salva no arquivo aleatório. Esse exemplo é igual ao exemplo anterior, mas usa o utilitário `certutil` no Windows para decodificar em base64 a string de bytes aleatória antes de salvá-la em um arquivo.

Primeiro, gere uma string de bytes aleatória codificada em base64 e salve-a em um arquivo temporário (`ExampleRandom.base64`).

```
aws kms generate-random \
    --number-of-bytes 32 \
    --output text \
    --query Plaintext > ExampleRandom.base64
```

Como a saída do comando `generate-random` é salva em um arquivo, esse exemplo não produz nenhuma saída.

Use o comando `certutil -decode` para decodificar a string de bytes codificada em base64 no arquivo `ExampleRandom.base64`. Em seguida, ele salva a string de bytes decodificada no arquivo `ExampleRandom`.

```
certutil -decode ExampleRandom.base64 ExampleRandom
```

Saída:

```
Input Length = 18
Output Length = 12
CertUtil: -decode command completed successfully.
```

Para obter mais informações, consulte GenerateRandoma Referência da API do AWS Key Management Service.

- Para obter detalhes da API, consulte GenerateRandomna Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_string(client: &Client, length: i32) -> Result<(), Error> {
    let resp = client
        .generate_random()
        .number_of_bytes(length)
```

```
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.plaintext.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    println!();
    println!("Data key:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateRandomreferência da API AWS SDK for Rust.

Criar um alias para uma AWS KMS key usando um SDK da AWS

O exemplo de código a seguir mostra como criar um alias para uma chave do KMS Key.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.KeyManagementService;
    using Amazon.KeyManagementService.Model;

    /// <summary>
    /// Creates an alias for an AWS Key Management Service (AWS KMS) key.
```

```
/// </summary>
public class CreateAlias
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();

        // The alias name must start with alias/ and can be
        // up to 256 alphanumeric characters long.
        var aliasName = "alias/ExampleAlias";

        // The value supplied as the TargetKeyId can be either
        // the key ID or key Amazon Resource Name (ARN) of the
        // AWS KMS key.
        var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

        var request = new CreateAliasRequest
        {
            AliasName = aliasName,
            TargetKeyId = keyId,
        };

        var response = await client.CreateAliasAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"Alias, {aliasName}, successfully created.");
        }
        else
        {
            Console.WriteLine($"Could not create alias.");
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAliasa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar um alias para uma chave do KMS

O comando `create-alias` a seguir cria um alias com o nome `example-alias` para a chave do KMS identificada pelo ID de chave `1234abcd-12ab-34cd-56ef-1234567890ab`.

Os nomes de alias devem começar com `alias/`. Não use nomes de alias que comecem com `alias/aws`. Eles são reservados para uso pela AWS.

```
aws kms create-alias \
    --alias-name alias/example-alias \
    --target-key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Esse comando não retorna resultados. Use o `list-aliases` comando para visualizar o novo alias.

Para obter mais informações, consulte Using aliases no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte CreateAliasna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateAliasRequest;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateAlias {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <targetKeyId> <aliasName>\s

                Where:
                    targetKeyId - The key ID or the Amazon Resource Name (ARN) of
 the customer master key (CMK).\s
                    aliasName - An alias name (for example, alias/myAlias).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String targetKeyId = args[0];
        String aliasName = args[1];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        createCustomAlias(kmsClient, targetKeyId, aliasName);
        kmsClient.close();
    }

    public static void createCustomAlias(KmsClient kmsClient, String targetKeyId,
 String aliasName) {
        try {
            CreateAliasRequest aliasRequest = CreateAliasRequest.builder()
                    .aliasName(aliasName)
                    .targetKeyId(targetKeyId)
                    .build();
```

```
            kmsClient.createAlias(aliasRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAliasa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createCustomAlias(targetKeyIdVal: String?, aliasNameVal: String?) {

    val request = CreateAliasRequest {
        aliasName = aliasNameVal
        targetKeyId = targetKeyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.createAlias(request)
        println("$aliasNameVal was successfully created")
    }
}
```

- Para obter detalhes da API, consulte a CreateAliasreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def create_alias(self, key_id):
        """
        Creates an alias for the specified key.

        :param key_id: The ARN or ID of a key to give an alias.
        :return: The alias given to the key.
        """
        alias = ""
        while alias == "":
            alias = input(f"What alias would you like to give to key {key_id}? ")
        try:
            self.kms_client.create_alias(AliasName=alias, TargetKeyId=key_id)
        except ClientError as err:
            logger.error(
                "Couldn't create alias %s. Here's why: %s",
                alias,
                err.response["Error"]["Message"],
            )
        else:
            print(f"Created alias {alias} for key {key_id}.")
            return alias
```

- Para obter detalhes da API, consulte a CreateAliasReferência da API AWSSDK for Python (Boto3).

Decriptografe texto cifrado com uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como descriptografar texto cifrado que foi criptografado com uma chave KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criptografar e descriptografar texto

CLI

AWS CLI

Exemplo 1: como descriptografar uma mensagem criptografada com uma chave simétrica do KMS (Linux e macOS)

O exemplo de comando `decrypt` a seguir demonstra a forma recomendada de descriptografar dados com a AWS CLI. Esta versão mostra como descriptografar dados com uma chave simétrica do KMS.

Forneça o texto cifrado em um arquivo. No valor do parâmetro `--ciphertext-blob`, use o prefixo `fileb://`, que instrui a CLI a ler os dados de um arquivo binário. Se o arquivo não estiver no diretório atual, digite o caminho completo para o arquivo. Para obter mais informações sobre a leitura dos valores dos parâmetros da AWS CLI de um arquivo, consulte Carregando parâmetros da AWS CLI de um arquivo < https://docs.aws.amazon.com/cli/latest/userguide/ cli-usage-parameters-file .html> no Guia do usuário da interface de linha de AWS comando e práticas recomendadas para parâmetros de arquivos locais< https://aws.amazon.com/blogs/developer/ best-practices-for-local -file-parameters/> no blog da ferramenta de linha de comando .Especifique a chave KMS para descriptografar o texto cifrado.O parâmetro não é necessário ao AWS descriptografar com um KMS simétrico `--key-id` chave. AWS KMS pode obter o ID de chave da chave do KMS usada para criptografar os dados dos metadados no texto cifrado. Porém, sempre é uma prática recomendada especificar a chave do KMS que você está usando. Esta prática garante que você use a chave do KMS desejada e impede que você descriptografe um texto cifrado acidentalmente usando uma chave do KMS em que você não confia. Solicite a saída de texto simples como um valor de texto. O parâmetro `--query` instrui a CLI obter somente o valor do campo `Plaintext` da saída. O parâmetro `--output` retorna a saída como texto. Decodifique o texto simples em Base64 e salve-o em um arquivo. O seguinte exemplo

canaliza (|) o valor do parâmetro `Plaintext` para o utilitário Base64, que o decodifica. Em seguida, ele redireciona (>) a saída decodificada para o arquivo `ExamplePlaintext`.

Antes de executar esse comando, substitua o ID de chave de exemplo por um ID de chave válido da sua conta da AWS.

```
aws kms decrypt \
    --ciphertext-blob fileb://ExampleEncryptedFile \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --output text \
    --query Plaintext | base64 \
    --decode > ExamplePlaintextFile
```

Este comando não produz saída. A saída do comando `decrypt` é decodificada em base64 e salva em um arquivo.

Para obter mais informações, consulte Decrypt na Referência da API do AWS Key Management Service.

Exemplo 2: como descriptografar uma mensagem criptografada com uma chave simétrica do KMS (prompt de comando do Windows)

O exemplo a seguir é igual ao anterior, mas ele usa o utilitário `certutil` para decodificar em Base64 os dados em texto simples. Esse procedimento requer dois comandos, conforme mostrado nos exemplos a seguir.

Antes de executar esse comando, substitua o ID de chave de exemplo por um ID de chave válido da sua conta da AWS.

```
aws kms decrypt ^
    --ciphertext-blob fileb://ExampleEncryptedFile ^
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab ^
    --output text ^
    --query Plaintext > ExamplePlaintextFile.base64
```

Execute o comando `certutil`.

```
certutil -decode ExamplePlaintextFile.base64 ExamplePlaintextFile
```

Saída:

```
Input Length = 18
Output Length = 12
CertUtil: -decode command completed successfully.
```

Para obter mais informações, consulte Decrypt na Referência da API do AWS Key Management Service.

Exemplo 3: como descriptografar uma mensagem criptografada com uma chave assimétrica do KMS (Linux e macOS)

O exemplo de comando `decrypt` a seguir mostra como descriptografar dados criptografados sob uma chave RSA assimétrica do KMS.

Ao usar uma chave assimétrica do KMS, o parâmetro `encryption-algorithm`, que especifica o algoritmo usado para criptografar o texto simples, é necessário.

Antes de executar esse comando, substitua o ID de chave de exemplo por um ID de chave válido da sua conta da AWS.

```
aws kms decrypt \
    --ciphertext-blob fileb://ExampleEncryptedFile \
    --key-id 0987dcba-09fe-87dc-65ba-ab0987654321 \
    --encryption-algorithm RSAES_OAEP_SHA_256 \
    --output text \
    --query Plaintext | base64 \
    --decode > ExamplePlaintextFile
```

Este comando não produz saída. A saída do comando `decrypt` é decodificada em base64 e salva em um arquivo.

Para obter mais informações, consulte Asymmetric keys in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte Decrypt na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void decryptData(KmsClient kmsClient, SdkBytes encryptedData,
String keyId) {
       try {
           DecryptRequest decryptRequest = DecryptRequest.builder()
                   .ciphertextBlob(encryptedData)
                   .keyId(keyId)
                   .build();

           DecryptResponse decryptResponse = kmsClient.decrypt(decryptRequest);
           decryptResponse.plaintext();

       } catch (KmsException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte Decrypt na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun encryptData(keyIdValue: String): ByteArray? {

    val text = "This is the text to encrypt by using the AWS KMS Service"
    val myBytes: ByteArray = text.toByteArray()

    val encryptRequest = EncryptRequest {
        keyId = keyIdValue
        plaintext = myBytes
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.encrypt(encryptRequest)
        val algorithm: String = response.encryptionAlgorithm.toString()
        println("The encryption algorithm is $algorithm")

        // Return the encrypted data.
        return response.ciphertextBlob
    }
}

suspend fun decryptData(encryptedDataVal: ByteArray?, keyIdVal: String?, path:
 String) {

    val decryptRequest = DecryptRequest {
        ciphertextBlob = encryptedDataVal
        keyId = keyIdVal
    }
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val decryptResponse = kmsClient.decrypt(decryptRequest)
        val myVal = decryptResponse.plaintext

        // Write the decrypted data to a file.
        if (myVal != null) {
            File(path).writeBytes(myVal)
        }
    }
}
```

- Para obter detalhes da API, consulte Decrypt na Referência da API do SDK da AWS para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def decrypt(self, key_id, cipher_text):
        """
        Decrypts text previously encrypted with a key.

        :param key_id: The ARN or ID of the key used to decrypt the data.
        :param cipher_text: The encrypted text to decrypt.
        """
        answer = input("Ready to decrypt your ciphertext (y/n)? ")
        if answer.lower() == "y":
            try:
                text = self.kms_client.decrypt(
                    KeyId=key_id, CiphertextBlob=cipher_text
                )["Plaintext"]
            except ClientError as err:
                logger.error(
                    "Couldn't decrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Your plaintext is {text.decode()}")
        else:
            print("Skipping decryption demo.")
```

- Para obter detalhes da API, consulte Decrypt na Referência da API do SDK da AWS para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms" # v2: require 'aws-sdk'

# Decrypted blob

blob =
 "01020200785d68faeec386af1057904926253051eb2919d3c16078badf65b808b26dd057c101747cadf3593
blob_packed = [blob].pack("H*")

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.decrypt({
                        ciphertext_blob: blob_packed
                      })

puts "Raw text: "
puts resp.plaintext
```

- Para obter detalhes da API, consulte Decrypt na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn decrypt_key(client: &Client, key: &str, filename: &str) -> Result<(),
 Error> {
    // Open input text file and get contents as a string
    // input is a base-64 encoded string, so decode it:
    let data = fs::read_to_string(filename)
        .map(|input| {
            base64::decode(input).expect("Input file does not contain valid base
 64 characters.")
        })
        .map(Blob::new);

    let resp = client
        .decrypt()
        .key_id(key)
        .ciphertext_blob(data.unwrap())
        .send()
        .await?;

    let inner = resp.plaintext.unwrap();
    let bytes = inner.as_ref();

    let s = String::from_utf8(bytes.to_vec()).expect("Could not convert to
 UTF-8");

    println!();
    println!("Decoded string:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte Decrypt na Referência da API do SDK da AWS para Rust.

Exclua um alias do AWS KMS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um alias do AWS KMS.

CLI

AWS CLI

Como excluir um alias do AWS KMS

O exemplo de `delete-alias` a seguir exclui o alias `alias/example-alias`. O nome de alias deve começar com alias/.

```
aws kms delete-alias \
    --alias-name alias/example-alias
```

Este comando não produz saída. Use o `list-aliases` comando para localizar o alias.

Para obter mais informações, consulte Deleting an alias no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte DeleteAliasna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def delete_alias(self):
        """
        Deletes an alias.
        """
        alias = input(f"Enter an alias that you'd like to delete: ")
        if alias != "":
```

```
            try:
                self.kms_client.delete_alias(AliasName=alias)
            except ClientError as err:
                logger.error(
                    "Couldn't delete alias %s. Here's why: %s",
                    alias,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Deleted alias {alias}.")
        else:
            print("Skipping alias deletion.")
```

- Para obter detalhes da API, consulte a DeleteAliasReferência da API AWSSDK for Python (Boto3).

Descrever casos do AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma chave do KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
```

```
    using Amazon.KeyManagementService;
    using Amazon.KeyManagementService.Model;

    /// <summary>
    /// Retrieve information about an AWS Key Management Service (AWS KMS) key.
    /// You can supply either the key Id or the key Amazon Resource Name (ARN)
    /// to the DescribeKeyRequest KeyId property.
    /// </summary>
    public class DescribeKey
    {
        public static async Task Main()
        {
            var keyId = "7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";
            var request = new DescribeKeyRequest
            {
                KeyId = keyId,
            };

            var client = new AmazonKeyManagementServiceClient();

            var response = await client.DescribeKeyAsync(request);
            var metadata = response.KeyMetadata;

            Console.WriteLine($"{metadata.KeyId} created on:
{metadata.CreationDate}");
            Console.WriteLine($"State: {metadata.KeyState}");
            Console.WriteLine($"{metadata.Description}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeKeya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como localizar informações detalhadas sobre uma chave do KMS

O exemplo de `describe-key` a seguir obtém informações detalhadas sobre a chave gerenciada da AWS para o Amazon S3 na conta e região do exemplo. Você pode usar esse comando para encontrar detalhes sobre chaves gerenciadas pela AWS e pelo cliente.

Use o parâmetro `key-id` para especificar a chave do KMS. Este exemplo usa um valor de nome de alias, mas você pode usar um ID de chave, o ARN da chave, o nome do alias ou o ARN do alias neste comando.

```
aws kms describe-key \
    --key-id alias/aws/s3
```

Saída:

```
{
    "KeyMetadata": {
        "AWSAccountId": "846764612917",
        "KeyId": "b8a9477d-836c-491f-857e-07937918959b",
        "Arn": "arn:aws:kms:us-west-2:846764612917:key/
b8a9477d-836c-491f-857e-07937918959b",
        "CreationDate": 2017-06-30T21:44:32.140000+00:00,
        "Enabled": true,
        "Description": "Default KMS key that protects my S3 objects when no other
 key is defined",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "KeyState": "Enabled",
        "Origin": "AWS_KMS",
        "KeyManager": "AWS",
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ]
    }
}
```

Para obter mais informações, consulte Viewing keys no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 2: como obter detalhes sobre uma chave RSA assimétrica do KMS

O exemplo de `describe-key` a seguir obtém informações detalhadas sobre uma chave RSA assimétrica do KMS usada para assinatura e verificação.

```
aws kms describe-key \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Saída:

```
{
    "KeyMetadata": {
        "AWSAccountId": "111122223333",
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "Arn": "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "CreationDate": "2019-12-02T19:47:14.861000+00:00",
        "CustomerMasterKeySpec": "RSA_2048",
        "Enabled": false,
        "Description": "",
        "KeyState": "Disabled",
        "Origin": "AWS_KMS",
        "MultiRegion": false,
        "KeyManager": "CUSTOMER",
        "KeySpec": "RSA_2048",
        "KeyUsage": "SIGN_VERIFY",
        "SigningAlgorithms": [
            "RSASSA_PKCS1_V1_5_SHA_256",
            "RSASSA_PKCS1_V1_5_SHA_384",
            "RSASSA_PKCS1_V1_5_SHA_512",
            "RSASSA_PSS_SHA_256",
            "RSASSA_PSS_SHA_384",
            "RSASSA_PSS_SHA_512"
        ]
    }
}
```

Exemplo 3: como obter detalhes sobre uma chave de réplica multirregional

O exemplo de `describe-key` a seguir os obtém metadados de uma chave de réplica multirregional. Essa chave multirregional é uma chave de criptografia simétrica. A saída de um comando `describe-key` para qualquer chave multirregional retorna informações sobre a chave primária e todas as suas réplicas.

```
aws kms describe-key \
    --key-id arn:aws:kms:ap-northeast-1:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab
```

Saída:

```
{
    "KeyMetadata": {
```

```
        "MultiRegion": true,
        "AWSAccountId": "111122223333",
        "Arn": "arn:aws:kms:ap-northeast-1:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab",
        "CreationDate": "2021-06-28T21:09:16.114000+00:00",
        "Description": "",
        "Enabled": true,
        "KeyId": "mrk-1234abcd12ab34cd56ef1234567890ab",
        "KeyManager": "CUSTOMER",
        "KeyState": "Enabled",
        "KeyUsage": "ENCRYPT_DECRYPT",
        "Origin": "AWS_KMS",
        "CustomerMasterKeySpec": "SYMMETRIC_DEFAULT",
        "EncryptionAlgorithms": [
            "SYMMETRIC_DEFAULT"
        ],
        "MultiRegionConfiguration": {
            "MultiRegionKeyType": "PRIMARY",
            "PrimaryKey": {
                "Arn": "arn:aws:kms:us-west-2:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab",
                "Region": "us-west-2"
            },
            "ReplicaKeys": [
                {
                    "Arn": "arn:aws:kms:eu-west-1:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab",
                    "Region": "eu-west-1"
                },
                {
                    "Arn": "arn:aws:kms:ap-northeast-1:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab",
                    "Region": "ap-northeast-1"
                },
                {
                    "Arn": "arn:aws:kms:sa-east-1:111122223333:key/
mrk-1234abcd12ab34cd56ef1234567890ab",
                    "Region": "sa-east-1"
                }
            ]
        }
    }
}
```

Exemplo 4: como obter detalhes sobre uma chave do KMS com HMAC

O exemplo de `describe-key` a seguir obtém informações detalhadas sobre uma chave do KMS com HMAC.

```
aws kms describe-key \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Saída:

```
{
    "KeyMetadata": {
        "AWSAccountId": "123456789012",
        "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
        "Arn": "arn:aws:kms:us-
west-2:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "CreationDate": "2022-04-03T22:23:10.194000+00:00",
        "Enabled": true,
        "Description": "Test key",
        "KeyUsage": "GENERATE_VERIFY_MAC",
        "KeyState": "Enabled",
        "Origin": "AWS_KMS",
        "KeyManager": "CUSTOMER",
        "CustomerMasterKeySpec": "HMAC_256",
        "MacAlgorithms": [
            "HMAC_SHA_256"
        ],
        "MultiRegion": false
    }
}
```

- Para obter detalhes da API, consulte DescribeKeyna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.DescribeKeyRequest;
import software.amazon.awssdk.services.kms.model.DescribeKeyResponse;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId -  A key id value to describe (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        describeSpecifcKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void describeSpecifcKey(KmsClient kmsClient, String keyId) {
```

```
        try {
            DescribeKeyRequest keyRequest = DescribeKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            DescribeKeyResponse response = kmsClient.describeKey(keyRequest);
            System.out.println("The key description is " +
 response.keyMetadata().description());
            System.out.println("The key ARN is " + response.keyMetadata().arn());

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeKeya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeSpecifcKey(keyIdVal: String?) {

    val request = DescribeKeyRequest {
        keyId = keyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.describeKey(request)
        println("The key description is ${response.keyMetadata?.description}")
        println("The key ARN is ${response.keyMetadata?.arn}")
```

```
    }
}
```

- Para obter detalhes da API, consulte a DescribeKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def describe_key(self):
        """
        Describes a key.
        """
        key_id = input("Enter a key ID or ARN here to get information about the
 key: ")
        if key_id:
            try:
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't get key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Got key {key_id}:")
                pprint(key)
        return key_id
```

- Para obter detalhes da API, consulte a DescribeKeyReferência da API AWSSDK for Python (Boto3).

Desabilite uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como desabilitar uma chave KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Disable an AWS Key Management Service (AWS KMS) key and then retrieve
/// the key's status to show that it has been disabled.
/// </summary>
public class DisableKey
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();

        // The identifier of the AWS KMS key to disable. You can use the
```

```
            // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
            var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

            var request = new DisableKeyRequest
            {
                KeyId = keyId,
            };

            var response = await client.DisableKeyAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                // Retrieve information about the key to show that it has now
                // been disabled.
                var describeResponse = await client.DescribeKeyAsync(new
 DescribeKeyRequest
                {
                    KeyId = keyId,
                });
                Console.WriteLine($"{describeResponse.KeyMetadata.KeyId} - state:
 {describeResponse.KeyMetadata.KeyState}");
            }
        }
    }
```

- Para obter detalhes da API, consulte DisableKeya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como desativar uma chave do KMS temporariamente

O exemplo a seguir usa o comando `disable-key` para desabilitar uma chave do KMS gerenciada pelo cliente. Use o `enable-key` comando para reabilitar a chave do KMS.

```
aws kms disable-key \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Este comando não produz saída.

Para obter mais informações, consulte Enabling and Disabling Keys no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte DisableKeyna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.DisableKeyRequest;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DisableCustomerKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to disable (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        disableKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void disableKey(KmsClient kmsClient, String keyId) {
        try {
            DisableKeyRequest keyRequest = DisableKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            kmsClient.disableKey(keyRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DisableKeya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableKey(keyIdVal: String?) {

    val request = DisableKeyRequest {
        keyId = keyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.disableKey(request)
        println("$keyIdVal was successfully disabled")
    }
}
```

- Para obter detalhes da API, consulte a DisableKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state
 change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
```

```
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")

            try:
                self.kms_client.enable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't enable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")
```

- Para obter detalhes da API, consulte a DisableKeyReferência da API AWSSDK for Python (Boto3).

Habilite uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como habilitar uma chave do KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Enable an AWS Key Management Service (AWS KMS) key.
/// </summary>
public class EnableKey
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();

        // The identifier of the AWS KMS key to enable. You can use the
        // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
        var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

        var request = new EnableKeyRequest
        {
            KeyId = keyId,
        };

        var response = await client.EnableKeyAsync(request);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            // Retrieve information about the key to show that it has now
            // been enabled.
            var describeResponse = await client.DescribeKeyAsync(new
DescribeKeyRequest
            {
                KeyId = keyId,
```

```
                });
                Console.WriteLine($"{describeResponse.KeyMetadata.KeyId} - state:
{describeResponse.KeyMetadata.KeyState}");
            }
        }
    }
```

- Para obter detalhes da API, consulte EnableKeya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como habilitar uma chave do KMS

O exemplo de `enable-key` a seguir habilita uma chave gerenciada pelo cliente. Você pode usar um comando como esse para habilitar uma chave do KMS que foi temporariamente desabilitada usando o comando `disable-key`. Você também pode usá-lo para habilitar uma chave do KMS que está desabilitada porque foi programada para exclusão, mas a exclusão foi cancelada.

Use o parâmetro `key-id` para especificar a chave do KMS. Este exemplo usa um valor de ID de chave, mas você pode usar um ID de chave ou o valor do ARN da chave neste comando.

Antes de executar esse comando, substitua o ID da chave de exemplo por um ID válido.

```
aws kms enable-key \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Este comando não produz saída. Use o `describe-key` comando para verificar se a chave KMS está habilitada. Consulte os valores dos campos `KeyState` e `Enabled` na saída `describe-key`.

Para obter mais informações, consulte Enabling and Disabling Keys no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte EnableKeyna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.EnableKeyRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class EnableCustomerKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to enable (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
```

```
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        enableKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void enableKey(KmsClient kmsClient, String keyId) {
        try {
            EnableKeyRequest enableKeyRequest = EnableKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            kmsClient.enableKey(enableKeyRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte EnableKeya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableKey(keyIdVal: String?) {

    val request = EnableKeyRequest {
        keyId = keyIdVal
    }
```

```
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.enableKey(request)
        println("$keyIdVal was successfully enabled.")
    }
}
```

- Para obter detalhes da API, consulte a EnableKeyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state
 change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
```

```
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")

            try:
                self.kms_client.enable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't enable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")
```

- Para obter detalhes da API, consulte a EnableKeyReferência da API AWSSDK for Python (Boto3).

Criptografe texto usando uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como criptografar texto usando uma chave do KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criptografar e descriptografar texto

CLI

AWS CLI

Exemplo 1: como criptografar o conteúdo de um arquivo no Linux ou no macOS

O comando `encrypt` a seguir demonstra a forma recomendada de criptografar dados com a AWS CLI.

```
aws kms encrypt \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --plaintext fileb://ExamplePlaintextFile \
    --output text \
```

```
    --query CiphertextBlob | base64 \
    --decode > ExampleEncryptedFile
```

O comando realiza diversas ações:

Usa o parâmetro `--plaintext` para indicar os dados a serem criptografados. Esse valor de parâmetro deve ser codificado em base64. O valor do parâmetro `plaintext` deve ser codificado em base64, ou você deve usar o prefixo `fileb://`, que informa a AWS CLI para que leia os dados binários do arquivo. Se o arquivo não estiver no diretório atual, digite o caminho completo do arquivo. Por exemplo: `fileb:///var/tmp/ExamplePlaintextFile` ou `fileb://C:\Temp\ExamplePlaintextFile`. Para obter informações sobre como ler o valores de parâmetros da AWS CLI de um arquivo, consulte Loading Parameters from a File no Guia do usuário da AWS Command Line Interface e Best Practices for Local File Parameters no AWS Command Line Tool Blog. Usa os parâmetros `--output` e `--query` para controlar a saída do comando. Esses parâmetros extraem os dados criptografados, chamados de texto cifrado, da saída do comando. Para obter mais informações sobre como controlar a saída, consulte Controlling Command Output no Guia do usuário da AWS Command Line Interface. Usa o utilitário `base64` para decodificar a saída extraída em dados binários. O texto cifrado retornado por um comando `encrypt` bem sucedido é um texto codificado em base64. Você deve codificar o texto antes de usar a AWS CLI para descriptografá-lo. Salva o texto cifrado binário em um arquivo. A parte final do comando (`> ExampleEncryptedFile`) salva o texto cifrado binário em um arquivo para facilitar a descriptografia. Consulte os exemplos de descriptografia para ver um comando de exemplo que usa a AWS CLI para descriptografar dados.

Exemplo 2: como usar a AWS CLI para criptografar dados no Windows

Esse exemplo é igual ao exemplo anterior, mas usa a ferramenta `certutil` em vez do `base64`. Esse procedimento requer dois comandos, conforme mostrado no exemplo a seguir.

```
aws kms encrypt \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --plaintext fileb://ExamplePlaintextFile \
    --output text \
    --query CiphertextBlob > C:\Temp\ExampleEncryptedFile.base64

certutil -decode C:\Temp\ExampleEncryptedFile.base64 C:\Temp\ExampleEncryptedFile
```

Exemplo 3: criptografia com uma chave do KMS assimétrica

O comando `encrypt` a seguir mostra como criptografar texto simples com uma chave assimétrica do KMS. O parâmetro `--encryption-algorithm` é obrigatório. Como em todos os comandos da `encrypt` CLI, o parâmetro `plaintext` deve ser codificado em base64 ou você deve usar o prefixo `fileb://`, que informa a AWS CLI para ler os dados binários do arquivo.

```
aws kms encrypt \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --encryption-algorithm RSAES_OAEP_SHA_256 \
    --plaintext fileb://ExamplePlaintextFile \
    --output text \
    --query CiphertextBlob | base64 \
    --decode > ExampleEncryptedFile
```

Este comando não produz saída.

- Para obter detalhes da API, consulte Encrypt na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.EncryptRequest;
import software.amazon.awssdk.services.kms.model.EncryptResponse;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.DecryptRequest;
import software.amazon.awssdk.services.kms.model.DecryptResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class EncryptDataKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to use to encrypt/decrypt the data
 (for example, xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        SdkBytes encryData = encryptData(kmsClient, keyId);
        decryptData(kmsClient, encryData, keyId);
        System.out.println("Done");
        kmsClient.close();
    }

    public static SdkBytes encryptData(KmsClient kmsClient, String keyId) {
        try {
            SdkBytes myBytes = SdkBytes.fromByteArray(new byte[] { 1, 2, 3, 4, 5,
 6, 7, 8, 9, 0 });
            EncryptRequest encryptRequest = EncryptRequest.builder()
                    .keyId(keyId)
                    .plaintext(myBytes)
                    .build();
```

```
            EncryptResponse response = kmsClient.encrypt(encryptRequest);
            String algorithm = response.encryptionAlgorithm().toString();
            System.out.println("The encryption algorithm is " + algorithm);

            // Get the encrypted data.
            SdkBytes encryptedData = response.ciphertextBlob();
            return encryptedData;

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return null;
    }

    public static void decryptData(KmsClient kmsClient, SdkBytes encryptedData,
 String keyId) {
        try {
            DecryptRequest decryptRequest = DecryptRequest.builder()
                    .ciphertextBlob(encryptedData)
                    .keyId(keyId)
                    .build();

            DecryptResponse decryptResponse = kmsClient.decrypt(decryptRequest);
            decryptResponse.plaintext();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Encrypt na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun encryptData(keyIdValue: String): ByteArray? {

    val text = "This is the text to encrypt by using the AWS KMS Service"
    val myBytes: ByteArray = text.toByteArray()

    val encryptRequest = EncryptRequest {
        keyId = keyIdValue
        plaintext = myBytes
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.encrypt(encryptRequest)
        val algorithm: String = response.encryptionAlgorithm.toString()
        println("The encryption algorithm is $algorithm")

        // Return the encrypted data.
        return response.ciphertextBlob
    }
}

suspend fun decryptData(encryptedDataVal: ByteArray?, keyIdVal: String?, path:
 String) {

    val decryptRequest = DecryptRequest {
        ciphertextBlob = encryptedDataVal
        keyId = keyIdVal
    }
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val decryptResponse = kmsClient.decrypt(decryptRequest)
        val myVal = decryptResponse.plaintext

        // Write the decrypted data to a file.
```

```
        if (myVal != null) {
            File(path).writeBytes(myVal)
        }
    }
}
```

- Para obter detalhes da API, consulte Encrypt na Referência da API do SDK da AWS para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def encrypt(self, key_id):
        """
        Encrypts text by using the specified key.

        :param key_id: The ARN or ID of the key to use for encryption.
        :return: The encrypted version of the text.
        """
        text = input("Enter some text to encrypt: ")
        try:
            cipher_text = self.kms_client.encrypt(
                KeyId=key_id, Plaintext=text.encode()
            )["CiphertextBlob"]
        except ClientError as err:
            logger.error(
                "Couldn't encrypt text. Here's why: %s",
                err.response["Error"]["Message"],
```

```
            )
        else:
            print(f"Your ciphertext is: {cipher_text}")
            return cipher_text
```

- Para obter detalhes da API, consulte Encrypt na Referência da API do SDK da AWS para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms"  # v2: require 'aws-sdk'

# ARN of the AWS KMS key.
#
# Replace the fictitious key ARN with a valid key ID

keyId = "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab"

text = "1234567890"

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.encrypt({
  key_id: keyId,
  plaintext: text,
})

# Display a readable version of the resulting encrypted blob.
puts "Blob:"
puts resp.ciphertext_blob.unpack("H*")
```

- Para obter detalhes da API, consulte Encrypt na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn encrypt_string(
    verbose: bool,
    client: &Client,
    text: &str,
    key: &str,
    out_file: &str,
) -> Result<(), Error> {
    let blob = Blob::new(text.as_bytes());

    let resp = client.encrypt().key_id(key).plaintext(blob).send().await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    let mut ofile = File::create(out_file).expect("unable to create file");
    ofile.write_all(s.as_bytes()).expect("unable to write");

    if verbose {
        println!("Wrote the following to {:?}", out_file);
        println!("{}", s);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte Encrypt na Referência da API do SDK da AWS para Rust.

Gere uma chave de dados em texto simples para criptografia do lado do cliente usando um SDK da AWS

Os exemplos de código a seguir mostram como gerar uma chave de dados simétrica exclusiva para criptografia do lado do cliente a partir de uma AWS KMS key. A chave contém versões em texto simples e em texto cifrado.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

CLI

AWS CLI

Exemplo 1: como gerar uma chave de dados simétrica de 256 bits

O exemplo `generate-data-key` a seguir solicita uma chave de dados simétrica de 256 bits para uso externo à AWS. O comando retorna uma chave de dados em texto simples para uso e exclusão imediatos e uma cópia da chave de dados criptografada na chave do KMS especificada. A chave de dados criptografada pode ser armazenada com segurança junto com os dados criptografados.

Use o parâmetro `key-spec` com um valor de `AES_256` para solicitar uma chave de dados de 256 bits. Use o parâmetro `key-spec` com um valor de `AES_128` para solicitar uma chave de dados de 128 bits. Para todos os outros comprimentos de chave de dados, use o parâmetro `number-of-bytes`.

A chave do KMS especificada deve ser uma chave de criptografia simétrica do KMS, ou seja, uma chave do KMS com um valor de especificação de chave de SYMMETRIC_DEFAULT.

```
aws kms generate-data-key \
```

```
    --key-id alias/ExampleAlias \
    --key-spec AES_256
```

Saída:

```
{
    "Plaintext": "VdzKNHGzUAzJeRBVY+uUmofUGGiDzyB3+i9fVkh3piw=",
    "KeyId": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
    "CiphertextBlob":
 "AQEDAHjRYf5WytIc0C857tFSnBaPn2F8DgfmThbJlGfR8P3WlwAAAH4wfAYJKoZIhvcNAQcGoG8wbQIBADBoBgk
+YdhV8MrkBQPeac0ReRVNDt9qleAt+SHgIRF8P0H+7U="
}
```

A `Plaintext` (chave de dados em texto simples) e a `CiphertextBlob` (chave de dados criptografada) são retornadas no formato codificado em base64.

Para obter mais informações, consulte Data keys (https://docs.aws.amazon.com/kms/latest/developerguide/concepts.html#data-keys) no Guia do desenvolvedor do AWS Key Management Service.

Exemplo 2: como gerar uma chave de dados simétrica de 512 bits

O exemplo de `generate-data-key` a seguir solicita uma chave de dados simétrica de 512 bits para criptografia e descriptografia. O comando retorna uma chave de dados em texto simples para uso e exclusão imediatos e uma cópia da chave de dados criptografada na chave do KMS especificada. A chave de dados criptografada pode ser armazenada com segurança junto com os dados criptografados.

Use o parâmetro `number-of-bytes` para solicitar um comprimento de chave diferente de 128 ou 256 bits. Para solicitar uma chave de dados de 512 bits, o exemplo a seguir usa o parâmetro `number-of-bytes` com um valor de 64 (bytes).

A chave do KMS especificada deve ser uma chave de criptografia simétrica do KMS, ou seja, uma chave do KMS com um valor de especificação de chave de SYMMETRIC_DEFAULT.

OBSERVAÇÃO: os valores na saída deste exemplo são truncados para exibição.

```
aws kms generate-data-key \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
```

```
    --number-of-bytes 64
```

Saída:

```
{
    "CiphertextBlob": "AQIBAHi6LtupRpdKl2aJTzkK6FbhOtQkMlQJJH3PdtHvS/y+hAEnX/
QQNmMwDfg2korNMEc8AAACaDCCAmQGCSqGSIb3DQEHBqCCAlUwggJRAgEAMIICSgYJKoZ...",
    "Plaintext": "ty8Lr0Bk6OF07M2BWt6qbFdNB
+G00ZLtf5MSEb4al3R2UKWGOp06njAwy2n72VRm2m7z/
Pm9Wpbvttz6a4lSo9hgPvKhZ5y6RTm4OovEXiVfBveyX3DQxDzRSwbKDPk/...",
    "KeyId": "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab"
}
```

`Plaintext` (chave de dados em texto simples) e `CiphertextBlob` (chave de dados criptografada) são retornadas no formato codificado em base64.

Para obter mais informações, consulte Data keys (https://docs.aws.amazon.com/kms/latest/developerguide/concepts.html#data-keys) no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte GenerateDataKeyna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []
```

```
    def generate_data_key(self, key_id):
        """
        Generates a symmetric data key that can be used for client-side
 encryption.
        """
        answer = input(
            f"Do you want to generate a symmetric data key from key {key_id} (y/
n)? "
        )
        if answer.lower() == "y":
            try:
                data_key = self.kms_client.generate_data_key(
                    KeyId=key_id, KeySpec="AES_256"
                )
            except ClientError as err:
                logger.error(
                    "Couldn't generate a data key for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(data_key)
```

- Para obter detalhes da API, consulte a GenerateDataKeyReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client, key: &str) -> Result<(), Error> {
    let resp = client
        .generate_data_key()
```

```
        .key_id(key)
        .key_spec(DataKeySpec::Aes256)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    println!();
    println!("Data key:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateDataKeyreferência da API AWS SDK for Rust.

Gere uma chave de dados criptografada usando um AWS da SDK

Os exemplos de código a seguir mostram como gerar uma chave de dados criptografada de um AWS KMS key. A chave contém somente uma versão em texto cifrado.

CLI

AWS CLI

Como gerar uma chave de dados simétrica de 256 bits sem uma chave de texto simples

O exemplo de `generate-data-key-without-plaintext` a seguir solicita uma cópia criptografada de uma chave de dados simétrica de 256 bits para uso externo à AWS. Você pode chamar o AWS KMS para descriptografar a chave de dados quando quiser usá-la.

Use o parâmetro `key-spec` com um valor de `AES_256` para solicitar uma chave de dados de 256 bits. Use o parâmetro `key-spec` com um valor de `AES_128` para solicitar uma chave de dados de 128 bits. Para todos os outros comprimentos de chave de dados, use o parâmetro `number-of-bytes`.

A chave do KMS especificada deve ser uma chave de criptografia simétrica do KMS, ou seja, uma chave do KMS com um valor de especificação de chave de SYMMETRIC_DEFAULT.

```
aws kms generate-data-key-without-plaintext \
    --key-id "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab" \
    --key-spec AES_256
```

Saída:

```
{
    "CiphertextBlob":
 "AQEDAHjRYf5WytIc0C857tFSnBaPn2F8DgfmThbJlGfR8P3WlwAAAH4wfAYJKoZIhvcNAQcGoG8wbQIBADBoBgk
    "KeyId": "arn:aws:kms:us-
east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab"
}
```

A `CiphertextBlob` (chave de dados criptografada) é retornada em um formato codificado em base64.

Para obter mais informações, consulte Data keys no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte GenerateDataKeyWithoutPlaintextna Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client, key: &str) -> Result<(), Error> {
    let resp = client
        .generate_data_key_without_plaintext()
        .key_id(key)
```

```
        .key_spec(DataKeySpec::Aes256)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    println!();
    println!("Data key:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateDataKeyWithoutPlaintextreferência da API AWS SDK for Rust.

Obtenha uma política para uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como obter uma política pelo nome para uma chave do KMS.

CLI

AWS CLI

Como copiar uma política de chave de uma chave do KMS para outra chave do KMS

O exemplo de `get-key-policy` a seguir obtém a política de chave de uma chave do KMS e a salva em um arquivo de texto. Em seguida, ele substitui a política de uma chave diferente do KMS usando o arquivo de texto como a entrada da política.

Como o parâmetro `--policy` de `put-key-policy` requer uma string, você deve usar a opção `--output text` para retornar a saída como uma string de texto em vez de JSON.

```
aws kms get-key-policy \
    --policy-name default \
```

```
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --query Policy \
    --output text > policy.txt

aws kms put-key-policy \
    --policy-name default \
    --key-id 0987dcba-09fe-87dc-65ba-ab0987654321 \
    --policy file://policy.txt
```

Este comando não produz saída.

Para obter mais informações, consulte PutKeyPolicya Referência da API AWS KMS.

- Para obter detalhes da API, consulte GetKeyPolicyna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def get_policy(self, key_id):
        """
        Gets the policy of a key.

        :param key_id: The ARN or ID of the key to query.
        :return: The key policy as a dict.
        """
        if key_id != "":
            try:
                response = self.kms_client.get_key_policy(
                    KeyId=key_id, PolicyName="default"
                )
```

```
                policy = json.loads(response["Policy"])
            except ClientError as err:
                logger.error(
                    "Couldn't get policy for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(policy)
                return policy
        else:
            print("Skipping get policy demo.")
```

- Para obter detalhes da API, consulte a GetKeyPolicyReferência da API AWSSDK for Python (Boto3).

Liste os aliases definidos para uma AWS KMS key usando um SDK da AWS

O exemplo de código a seguir mostra como listar aliases para uma chave do KMS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.Threading.Tasks;
   using Amazon.KeyManagementService;
   using Amazon.KeyManagementService.Model;

   /// <summary>
   /// List the AWS Key Management Service (AWS KMS) aliases that have been
defined for
   /// the keys in the same AWS Region as the default user. If you want to list
```

```
    /// the aliases in a different Region, pass the Region to the client
    /// constructor.
    /// </summary>
    public class ListAliases
    {
        public static async Task Main()
        {
            var client = new AmazonKeyManagementServiceClient();
            var request = new ListAliasesRequest();
            var response = new ListAliasesResponse();

            do
            {
                response = await client.ListAliasesAsync(request);

                response.Aliases.ForEach(alias =>
                {
                    Console.WriteLine($"Created: {alias.CreationDate} Last
 Update: {alias.LastUpdatedDate} Name: {alias.AliasName}");
                });

                request.Marker = response.NextMarker;
            }
            while (response.Truncated);
        }
    }
```

- Para obter detalhes da API, consulte ListAliasesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como listar todos os aliases em uma conta e região da AWS

O exemplo a seguir usa o comando `list-aliases` para listar todos os aliases na região padrão da conta da AWS. A saída inclui aliases associados às chaves do KMS gerenciadas pela AWS e pelo cliente.

```
aws kms list-aliases
```

Saída:

```
{
    "Aliases": [
        {
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/testKey",
            "AliasName": "alias/testKey",
            "TargetKeyId": "1234abcd-12ab-34cd-56ef-1234567890ab"
        },
        {
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/FinanceDept",
            "AliasName": "alias/FinanceDept",
            "TargetKeyId": "0987dcba-09fe-87dc-65ba-ab0987654321"
        },
        {
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/aws/dynamodb",
            "AliasName": "alias/aws/dynamodb",
            "TargetKeyId": "1a2b3c4d-5e6f-1a2b-3c4d-5e6f1a2b3c4d"
        },
        {
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/aws/ebs",
            "AliasName": "alias/aws/ebs",
            "TargetKeyId": "0987ab65-43cd-21ef-09ab-87654321cdef"
        },
        ...
    ]
}
```

Exemplo 2: como listar todos os aliases de uma chave específica do KMS

O exemplo a seguir usa o comando `list-aliases` e seu parâmetro `key-id` para listar todos os aliases associados a uma determinada chave do KMS.

Cada alias é associado a apenas um chave do KMS, mas uma chave do KMS pode ter vários aliases. Esse comando é muito útil porque o console do AWS KMS lista somente um alias para cada chave do KMS. Você deve usar o comando `list-aliases` para localizar todos os aliases de uma chave do KMS.

Este exemplo usa o ID de chave da chave do KMS no parâmetro `--key-id`, mas você pode usar um ID de chave, o ARN da chave, o nome do alias ou o ARN do alias neste comando.

```
aws kms list-aliases --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Saída:

```
{
    "Aliases": [
        {
            "TargetKeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/oregon-test-
key",
            "AliasName": "alias/oregon-test-key"
        },
        {
            "TargetKeyId": "1234abcd-12ab-34cd-56ef-1234567890ab",
            "AliasArn": "arn:aws:kms:us-west-2:111122223333:alias/project121-
test",
            "AliasName": "alias/project121-test"
        }
    ]
}
```

Para obter mais informações, consulte Working with aliases no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte ListAliasesna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.AliasListEntry;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.ListAliasesRequest;
import software.amazon.awssdk.services.kms.model.ListAliasesResponse;
import java.util.List;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListAliases {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        listAllAliases(kmsClient);
        kmsClient.close();
    }

    public static void listAllAliases(KmsClient kmsClient) {
        try {
            ListAliasesRequest aliasesRequest = ListAliasesRequest.builder()
                    .limit(15)
                    .build();

            ListAliasesResponse aliasesResponse =
 kmsClient.listAliases(aliasesRequest);
            List<AliasListEntry> aliases = aliasesResponse.aliases();
            for (AliasListEntry alias : aliases) {
                System.out.println("The alias name is: " + alias.aliasName());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAliasesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllAliases() {

    val request = ListAliasesRequest {
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listAliases(request)
        response.aliases?.forEach { alias ->
            println("The alias name is ${alias.aliasName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAliasesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
```

```
        self.created_key = None


    def list_aliases(self):
        """
        Lists aliases for the current account.
        """
        answer = input("\nLet's list your key aliases. Ready (y/n)? ")
        if answer.lower() == "y":
            try:
                page_size = 10

                alias_paginator = self.kms_client.get_paginator("list_aliases")
                for alias_page in alias_paginator.paginate(
                    PaginationConfig={"PageSize": 10}
                ):
                    print(f"Here are {page_size} aliases:")
                    pprint(alias_page["Aliases"])
                    if alias_page["Truncated"]:
                        answer = input(
                            f"Do you want to see the next {page_size} aliases (y/
n)? "
                        )
                        if answer.lower() != "y":
                            break
                    else:
                        print("That's all your aliases!")
            except ClientError as err:
                logging.error(
                    "Couldn't list your aliases. Here's why: %s",
                    err.response["Error"]["Message"],
                )
```

- Para obter detalhes da API, consulte a ListAliasesReferência da API AWSSDK for Python (Boto3).

Liste as concessões para uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como listar concessões para uma chave do KMS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.Threading.Tasks;
   using Amazon.KeyManagementService;
   using Amazon.KeyManagementService.Model;

   /// <summary>
   /// List the AWS Key Management Service (AWS KMS) grants that are associated
with
   /// a specific key.
   /// </summary>
   public class ListGrants
   {
       public static async Task Main()
       {
           // The identifier of the AWS KMS key to disable. You can use the
           // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
           var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";
           var client = new AmazonKeyManagementServiceClient();
           var request = new ListGrantsRequest
           {
               KeyId = keyId,
           };

           var response = new ListGrantsResponse();

           do
           {
               response = await client.ListGrantsAsync(request);

               response.Grants.ForEach(grant =>
               {
                   Console.WriteLine($"{grant.GrantId}");
```

```
                });

                request.Marker = response.NextMarker;
            }
            while (response.Truncated);
        }
    }
```

- Para obter detalhes da API, consulte ListGrantsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como visualizar as concessões de uma chave do AWS KMS

O exemplo de `list-grants` a seguir exibe todas as concessões da chave especificada do KMS gerenciada pela AWS para o Amazon DynamoDB na conta. Essa concessão permite que o DynamoDB use a chave do KMS em seu nome para criptografar uma tabela do DynamoDB antes de gravá-la no disco. Você pode usar um comando como esse para visualizar as concessões nas chaves do KMS gerenciadas pela AWS e nas chaves do KMS gerenciadas pelo cliente na conta e na região da AWS.

Este comando usa o parâmetro `key-id` com um ID de chave para identificar a chave do KMS. Você pode usar um ID de chave ou o ARN da chave para identificar a chave do KMS. Para obter o ID da chave ou o ARN da chave de uma chave do KMS gerenciada pela AWS, use o comando `list-keys` ou o `list-aliases`.

```
aws kms list-grants \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

O resultado mostra que a concessão fornece ao Amazon DynamoDB permissão para usar a chave do KMS para operações criptográficas e permite que ele visualize detalhes sobre a chave do KMS (`DescribeKey`) e descontinue concessões (`RetireGrant`). A restrição `EncryptionContextSubset` limita a permissão às solicitações que incluem os pares de contexto de criptografia especificados. Como resultado, as permissões na concessão são efetivas somente na conta especificada e na tabela do DynamoDB.

```
{
    "Grants": [
        {
            "Constraints": {
                "EncryptionContextSubset": {
                    "aws:dynamodb:subscriberId": "123456789012",
                    "aws:dynamodb:tableName": "Services"
                }
            },
            "IssuingAccount": "arn:aws:iam::123456789012:root",
            "Name": "8276b9a6-6cf0-46f1-b2f0-7993a7f8c89a",
            "Operations": [
                "Decrypt",
                "Encrypt",
                "GenerateDataKey",
                "ReEncryptFrom",
                "ReEncryptTo",
                "RetireGrant",
                "DescribeKey"
            ],
            "GrantId":
 "1667b97d27cf748cf05b487217dd4179526c949d14fb3903858e25193253fe59",
            "KeyId": "arn:aws:kms:us-
west-2:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab",
            "RetiringPrincipal": "dynamodb.us-west-2.amazonaws.com",
            "GranteePrincipal": "dynamodb.us-west-2.amazonaws.com",
            "CreationDate": "2021-05-13T18:32:45.144000+00:00"
        }
    ]
}
```

Para obter mais informações, consulte Grants in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte ListGrantsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.GrantListEntry;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.ListGrantsRequest;
import software.amazon.awssdk.services.kms.model.ListGrantsResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListGrants {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - a key id value to use (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        displayGrantIds(kmsClient, keyId);
        kmsClient.close();
    }

    public static void displayGrantIds(KmsClient kmsClient, String keyId) {
        try {
            ListGrantsRequest grantsRequest = ListGrantsRequest.builder()
                    .keyId(keyId)
                    .limit(15)
                    .build();

            ListGrantsResponse response = kmsClient.listGrants(grantsRequest);
            List<GrantListEntry> grants = response.grants();
            for (GrantListEntry grant : grants) {
                System.out.println("The grant Id is : " + grant.grantId());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListGrantsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun displayGrantIds(keyIdVal: String?) {

    val request = ListGrantsRequest {
        keyId = keyIdVal
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listGrants(request)
        response.grants?.forEach { grant ->
            println("The grant Id is ${grant.grantId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListGrantsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
```

```
        self.kms_client = kms_client


    def list_grants(self, key_id):
        """
        Lists grants for a key.

        :param key_id: The ARN or ID of the key to query.
        :return: The grants for the key.
        """
        answer = input(f"Ready to list grants on key {key_id} (y/n)? ")
        if answer.lower() == "y":
            try:
                grants = self.kms_client.list_grants(KeyId=key_id)["Grants"]
            except ClientError as err:
                logger.error(
                    "Couldn't list grants for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Grants for key {key_id}:")
                pprint(grants)
                return grants
```

- Para obter detalhes da API, consulte a ListGrantsReferência da API AWSSDK for Python (Boto3).

Liste AWS KMS keys usando um SDK da AWS

O exemplo de código a seguir mostra como listar chaves do KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// List the AWS Key Managements Service (AWS KMS) keys for the AWS Region
/// of the default user. To list keys in another AWS Region, supply the
Region
/// as a parameter to the client constructor.
/// </summary>
public class ListKeys
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();
        var request = new ListKeysRequest();
        var response = new ListKeysResponse();

        do
        {
            response = await client.ListKeysAsync(request);

            response.Keys.ForEach(key =>
            {
                Console.WriteLine($"ID: {key.KeyId}, {key.KeyArn}");
            });

            // Set the Marker property when response.Truncated is true
            // in order to get the next keys.
            request.Marker = response.NextMarker;
        }
```

```
            while (response.Truncated);
        }
    }
```

- Para obter detalhes da API, consulte ListKeysa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como obter chaves do KMS em uma conta e região

O exemplo `list-keys` a seguir obtém as chaves do KMS em uma conta e região. Esse comando retorna chaves gerenciadas pela AWS e pelo cliente.

```
aws kms list-keys
```

Saída:

```
{
    "Keys": [
        {
            "KeyArn": "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab",
            "KeyId": "1234abcd-12ab-34cd-56ef-1234567890ab"
        },
        {
            "KeyArn": "arn:aws:kms:us-
west-2:111122223333:key/0987dcba-09fe-87dc-65ba-ab0987654321",
            "KeyId": "0987dcba-09fe-87dc-65ba-ab0987654321"
        },
        {
            "KeyArn": "arn:aws:kms:us-
east-2:111122223333:key/1a2b3c4d-5e6f-1a2b-3c4d-5e6f1a2b3c4d",
            "KeyId": "1a2b3c4d-5e6f-1a2b-3c4d-5e6f1a2b3c4d"
        }
    ]
}
```

Para obter mais informações, consulte Viewing Keys no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte ListKeysem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.KeyListEntry;
import software.amazon.awssdk.services.kms.model.ListKeysRequest;
import software.amazon.awssdk.services.kms.model.ListKeysResponse;
import software.amazon.awssdk.services.kms.model.KmsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListKeys {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        listAllKeys(kmsClient);
        kmsClient.close();
    }
```

```
    public static void listAllKeys(KmsClient kmsClient) {
        try {
            ListKeysRequest listKeysRequest = ListKeysRequest.builder()
                    .limit(15)
                    .build();

            ListKeysResponse keysResponse = kmsClient.listKeys(listKeysRequest);
            List<KeyListEntry> keyListEntries = keysResponse.keys();
            for (KeyListEntry key : keyListEntries) {
                System.out.println("The key ARN is: " + key.keyArn());
                System.out.println("The key Id is: " + key.keyId());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListKeysa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllKeys() {

    val request = ListKeysRequest {
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listKeys(request)
```

```
        response.keys?.forEach { key ->
            println("The key ARN is ${key.keyArn}")
            println("The key Id is ${key.keyId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListKeysreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def list_keys(self):
        """
        Lists the keys for the current account by using a paginator.
        """
        try:
            page_size = 10
            print("\nLet's list your keys.")
            key_paginator = self.kms_client.get_paginator("list_keys")
            for key_page in key_paginator.paginate(PaginationConfig={"PageSize":
 10}):
                print(f"Here are {len(key_page['Keys'])} keys:")
                pprint(key_page["Keys"])
                if key_page["Truncated"]:
                    answer = input(
                        f"Do you want to see the next {page_size} keys (y/n)? "
                    )
```

```
                    if answer.lower() != "y":
                        break
                else:
                    print("That's all your keys!")
        except ClientError as err:
            logging.error(
                "Couldn't list your keys. Here's why: %s",
                err.response["Error"]["Message"],
            )
```

- Para obter detalhes da API, consulte a ListKeysReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_keys(client: &Client) -> Result<(), Error> {
    let resp = client.list_keys().send().await?;

    let keys = resp.keys.unwrap_or_default();

    let len = keys.len();

    for key in keys {
        println!("Key ARN: {}", key.key_arn.as_deref().unwrap_or_default());
    }

    println!();
    println!("Found {} keys", len);

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListKeysreferência da API AWS SDK for Rust.

Liste políticas para uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como listar as políticas de uma chave do KMS.

CLI

AWS CLI

Como obter os nomes das políticas de chave de uma chave do KMS

O exemplo de `list-key-policies` a seguir obtém os nomes das políticas de chave de uma chave gerenciada pelo cliente na conta e região de exemplo. Você pode usar esse comando para encontrar os nomes das políticas de chave de chaves gerenciadas pela AWS e pelo cliente.

Como o único nome de política de chave válido é `default`, esse comando não é muito útil.

Use o parâmetro `key-id` para especificar a chave do KMS. Este exemplo usa um valor de ID de chave, mas você pode usar um ID de chave ou o ARN da chave neste comando.

```
aws kms list-key-policies \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Saída:

```
{
    "PolicyNames": [
    "default"
    ]
}
```

Para obter mais informações sobre as políticas de chave do AWS KMS, consulte Using Key Policies in AWS KMS no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte ListKeyPoliciesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def list_policies(self, key_id):
        """
        Lists the names of the policies for a key.

        :param key_id: The ARN or ID of the key to query.
        """
        try:
            policy_names = self.kms_client.list_key_policies(KeyId=key_id)[
                "PolicyNames"
            ]
        except ClientError as err:
            logging.error(
                "Couldn't list your policies. Here's why: %s",
                err.response["Error"]["Message"],
            )
        else:
            print(f"The policies for key {key_id} are:")
            pprint(policy_names)
```

- Para obter detalhes da API, consulte a ListKeyPoliciesReferência da API AWSSDK for Python (Boto3).

Recriptografe texto cifrado de uma AWS KMS key para outra usando um SDK da AWS

Os exemplos de código a seguir mostram como recriptografar texto cifrado de uma chave do KMS para outra.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Criptografar e descriptografar texto

CLI

AWS CLI

Exemplo 1: como criptografar novamente uma mensagem criptografada com uma chave simétrica diferente do KMS (Linux e macOS).

O exemplo de comando `re-encrypt` a seguir demonstra a forma recomendada de recriptografar dados com a AWS CLI.

Forneça o texto cifrado em um arquivo. No valor do parâmetro `--ciphertext-blob`, use o prefixo `fileb://`, que instrui a CLI a ler os dados de um arquivo binário. Se o arquivo não estiver no diretório atual, digite o caminho completo para o arquivo. Para obter mais informações sobre a leitura dos valores dos parâmetros da AWS CLI de um arquivo, consulte Carregando parâmetros da AWS CLI de um arquivo < https://docs.aws.amazon.com/cli/latest/userguide/ cli-usage-parameters-file .html> no Guia do usuário da interface de linha de AWS comando e práticas recomendadas para parâmetros de arquivos locais< https://aws.amazon.com/blogs/developer/ best-practices-for-local -file-parameters/> no blog da ferramenta de linha de AWS comando .Especifique a chave KMS de origem, que descriptografa o texto cifrado.O parâmetro não é necessário ao descriptografar com `--source-key-id` chaves KMS de criptografia simétrica. AWS KMS pode recuperar a chave do KMS que foi usada para criptografar os dados dos metadados no blob de texto cifrado. Porém, sempre é uma prática recomendada especificar a chave do KMS que você está usando. Essa prática garante que você use a chave do KMS desejada e impede que você descriptografe um texto cifrado acidentalmente usando uma chave do KMS em que você não confia. Especifique a chave do KMS de destino, que criptografa os dados novamente. O parâmetro `--destination-key-id` é sempre obrigatório. Este exemplo usa um ARN de chave, mas você pode usar qualquer identificador de chave válido. Solicite a saída de texto simples como um valor de texto. O parâmetro `--query` informa à CLI para obter somente

o valor do campo `Plaintext` da saída. O parâmetro `--output` retorna a saída como texto. Decodifique o texto simples em Base64 e salve-o em um arquivo. O seguinte exemplo canaliza (|) o valor do parâmetro `Plaintext` para o utilitário Base64, que o decodifica. Em seguida, ele redireciona (**>**) a saída decodificada para o arquivo `ExamplePlaintext`.

Antes de executar esse comando, substitua os IDs de chave de exemplo por identificadores de chave válidos de sua conta da AWS.

```
aws kms re-encrypt \
    --ciphertext-blob fileb://ExampleEncryptedFile \
    --source-key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --destination-key-id 0987dcba-09fe-87dc-65ba-ab0987654321 \
    --query CiphertextBlob \
    --output text | base64 --decode > ExampleReEncryptedFile
```

Este comando não produz saída. A saída do comando `re-encrypt` é decodificada em base64 e salva em um arquivo.

Para obter mais informações, consulte ReEncrypt **<** https://docs.aws.amazon.com/kms/latest/APIReference/API_ ReEncrypt .html na Referência da API do AWS Key Management Service.

Exemplo 2: como criptografar novamente uma mensagem criptografada com uma chave simétrica diferente do KMS (prompt de comando do Windows).

O exemplo de comando `re-encrypt` a seguir é o mesmo que o anterior, mas ele usa o utilitário `certutil` para decodificar em Base64 os dados em texto simples. Esse procedimento requer dois comandos, conforme mostrado nos exemplos a seguir.

Antes de executar esse comando, substitua o ID de chave de exemplo por um ID de chave válido da sua conta da AWS.

```
aws kms re-encrypt ^
    --ciphertext-blob fileb://ExampleEncryptedFile ^
    --source-key-id 1234abcd-12ab-34cd-56ef-1234567890ab ^
    --destination-key-id 0987dcba-09fe-87dc-65ba-ab0987654321 ^
    --query CiphertextBlob ^
    --output text > ExampleReEncryptedFile.base64
```

Em seguida, use o utilitário `certutil`.

```
certutil -decode ExamplePlaintextFile.base64 ExamplePlaintextFile
```

Saída:

```
Input Length = 18
Output Length = 12
CertUtil: -decode command completed successfully.
```

Para obter mais informações, consulte ReEncrypt < https://docs.aws.amazon.com/kms/latest/APIReference/API_ ReEncrypt .html na Referência da API do AWS Key Management Service.

- Para obter detalhes da API, consulte ReEncryptem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def re_encrypt(self, source_key_id, cipher_text):
        """
        Takes ciphertext previously encrypted with one key and reencrypt it by
 using
        another key.

        :param source_key_id: The ARN or ID of the original key used to encrypt
 the
                              ciphertext.
        :param cipher_text: The encrypted ciphertext.
        :return: The ciphertext encrypted by the second key.
        """
        destination_key_id = input(
            f"Your ciphertext is currently encrypted with key {source_key_id}. "
            f"Enter another key ID or ARN to reencrypt it: "
        )
```

```
        if destination_key_id != "":
            try:
                cipher_text = self.kms_client.re_encrypt(
                    SourceKeyId=source_key_id,
                    DestinationKeyId=destination_key_id,
                    CiphertextBlob=cipher_text,
                )["CiphertextBlob"]
            except ClientError as err:
                logger.error(
                    "Couldn't reencrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Reencrypted your ciphertext as: {cipher_text}")
                return cipher_text
        else:
            print("Skipping reencryption demo.")
```

- Para obter detalhes da API, consulte a ReEncryptReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms"  # v2: require 'aws-sdk'

# Human-readable version of the ciphertext of the data to reencrypt.

blob =
 "01020200785d68faeec386af1057904926253051eb2919d3c16078badf65b808b26dd057c101747cadf3593
```

```
sourceCiphertextBlob = [blob].pack("H*")

# Replace the fictitious key ARN with a valid key ID

destinationKeyId = "arn:aws:kms:us-
west-2:111122223333:key/0987dcba-09fe-87dc-65ba-ab0987654321"

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.re_encrypt({
  ciphertext_blob: sourceCiphertextBlob,
  destination_key_id: destinationKeyId
})

# Display a readable version of the resulting re-encrypted blob.
puts "Blob:"
puts resp.ciphertext_blob.unpack("H*")
```

- Para obter detalhes da API, consulte ReEncrypta Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn reencrypt_string(
    verbose: bool,
    client: &Client,
    input_file: &str,
    output_file: &str,
    first_key: &str,
    new_key: &str,
) -> Result<(), Error> {
    // Get blob from input file
    // Open input text file and get contents as a string
    // input is a base-64 encoded string, so decode it:
```

```
    let data = fs::read_to_string(input_file)
        .map(|input_file| base64::decode(input_file).expect("invalid base 64"))
        .map(Blob::new);

    let resp = client
        .re_encrypt()
        .ciphertext_blob(data.unwrap())
        .source_key_id(first_key)
        .destination_key_id(new_key)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);
    let o = &output_file;

    let mut ofile = File::create(o).expect("unable to create file");
    ofile.write_all(s.as_bytes()).expect("unable to write");

    if verbose {
        println!("Wrote the following to {}:", output_file);
        println!("{}", s);
    } else {
        println!("Wrote base64-encoded output to {}", output_file);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ReEncryptreferência da API AWS SDK for Rust.

Retire uma concessão para uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como descontinuar uma concessão de uma chave do KMS.

CLI

AWS CLI

Como descontinuar uma concessão em uma chave mestra do cliente

O exemplo de `retire-grant` a seguir exclui a concessão de uma chave do KMS.

O comando de exemplo a seguir especifica os parâmetros `grant-id` e `key-id`. O valor do parâmetro `key-id` deve ser o ARN de chave da chave do KMS.

```
aws kms retire-grant \
    --grant-id 1234a2345b8a4e350500d432bccf8ecd6506710e1391880c4f7f7140160c9af3 \
    --key-id arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab
```

Este comando não produz saída. Use o comando `list-grants` para confirmar a descontinuação da concessão.

Para obter mais informações, consulte Retiring and revoking grants no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte RetireGrantem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def retire_grant(self, grant):
        """
        Retires a grant so that it can no longer be used.
```

```
        :param grant: The grant to retire.
        """
        try:
            self.kms_client.retire_grant(GrantToken=grant["GrantToken"])
        except ClientError as err:
            logger.error(
                "Couldn't retire grant %s. Here's why: %s",
                grant["GrantId"],
                err.response["Error"]["Message"],
            )
        else:
            print(f"Grant {grant['GrantId']} retired.")
```

- Para obter detalhes da API, consulte a RetireGrantReferência da API AWSSDK for Python (Boto3).

Revogue uma concessão para uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como revogar uma concessão de uma chave do KMS.

CLI

AWS CLI

Como revogar uma concessão em uma chave mestra do cliente

O exemplo de `revoke-grant` a seguir exclui a concessão de uma chave do KMS. O comando de exemplo a seguir especifica os parâmetros `grant-id` e `key-id`. O valor do parâmetro `key-id` pode ser o ID ou o ARN de chave da chave do KMS.

```
aws kms revoke-grant \
    --grant-id 1234a2345b8a4e350500d432bccf8ecd6506710e1391880c4f7f7140160c9af3 \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Este comando não produz saída. Use o comando `list-grants` para confirmar que a concessão foi revogada.

Para obter mais informações, consulte Retiring and revoking grants no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte RevokeGrantem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def revoke_grant(self, key_id, grant):
        """
        Revokes a grant so that it can no longer be used.

        :param key_id: The ARN or ID of the key associated with the grant.
        :param grant: The grant to revoke.
        """
        try:
            self.kms_client.revoke_grant(KeyId=key_id, GrantId=grant["GrantId"])
        except ClientError as err:
            logger.error(
                "Couldn't revoke grant %s. Here's why: %s",
                grant["GrantId"],
                err.response["Error"]["Message"],
            )
        else:
            print(f"Grant {grant['GrantId']} revoked.")
```

- Para obter detalhes da API, consulte a RevokeGrantReferência da API AWSSDK for Python (Boto3).

Agende a exclusão de uma AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como programar a exclusão de uma chave do KMS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar chaves do

CLI

AWS CLI

Como programar a exclusão de uma chave do KMS gerenciada pelo cliente.

O exemplo de `schedule-key-deletion` a seguir programa a chave do KMS gerenciada pelo cliente especificada pala ser excluída em 15 dias.

O parâmetro `--key-id` identifica a chave do KMS. Este exemplo usa o valor do ARN da chave, mas você pode usar o ID da chave ou o ARN da chave do KMS. O parâmetro `--pending-window-in-days` especifica a duração do período de espera (7 a 30 dias). Por padrão, o período de espera é de 30 dias. Este exemplo especifica o valor de 15, que informa à AWS para excluir a chave do KMS permanentemente 15 dias após a conclusão do comando.

```
aws kms schedule-key-deletion \
    --key-id arn:aws:kms:us-
west-2:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab \
    --pending-window-in-days 15
```

A resposta inclui o ARN da chave, o estado da chave, o período de espera (`PendingWindowInDays`) e a data de exclusão no horário Unix. Use o console do AWS KMS para visualizar a data de exclusão no horário local. As chaves do KMS no estado `PendingDeletion` não podem ser usadas em operações criptográficas.

```
{
    "KeyId": "arn:aws:kms:us-
west-2:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab",
    "DeletionDate": "2022-06-18T23:43:51.272000+00:00",
    "KeyState": "PendingDeletion",
```

```
    "PendingWindowInDays": 15
}
```

Para obter mais informações, consulte Deleting keys no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte ScheduleKeyDeletionem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def delete_keys(self, keys):
        """
        Deletes a list of keys.

        :param keys: The list of keys to delete.
        """
        answer = input("Do you want to delete these keys (y/n)? ")
        if answer.lower() == "y":
            window = 7
            for key in keys:
                try:
                    self.kms_client.schedule_key_deletion(
                        KeyId=key["KeyId"], PendingWindowInDays=window
                    )
                except ClientError as err:
                    logging.error(
                        "Couldn't delete key %s. Here's why: %s",
```

```
                        key["KeyId"],
                        err.response["Error"]["Message"],
                    )
                else:
                    print(
                        f"Key {key['KeyId']} scheduled for deletion in {window}
days."
                    )
```

- Para obter detalhes da API, consulte a ScheduleKeyDeletionReferência da API AWSSDK for Python (Boto3).

Defina a política para AWS KMS key usando um SDK da AWS

Os exemplos de código a seguir mostram como definir uma política para uma chave do KMS.

CLI

AWS CLI

Como alterar a política de chaves de uma chave do KMS

O exemplo de `put-key-policy` a seguir altera a política de chave de uma chave gerenciada pelo cliente.

Para começar, crie uma política de chave e salve-a em um arquivo JSON local. Neste exemplo, o arquivo é `key_policy.json`. Você também pode especificar a política de chave como o valor da string do parâmetro `policy`.

A primeira instrução nesta política de chave fornece à conta da AWS permissão para usar as políticas do IAM para controlar o acesso à chave do KMS. A segunda instrução fornece permissão de usuário ao `test-user` para executar os comandos `describe-key` e `list-keys` na chave do KMS.

Conteúdo de `key_policy.json`:

```
{
    "Version" : "2012-10-17",
    "Id" : "key-default-1",
```

```
    "Statement" : [
        {
            "Sid" : "Enable IAM User Permissions",
            "Effect" : "Allow",
            "Principal" : {
                "AWS" : "arn:aws:iam::111122223333:root"
            },
            "Action" : "kms:*",
            "Resource" : "*"
        },
        {
            "Sid" : "Allow Use of Key",
            "Effect" : "Allow",
            "Principal" : {
                "AWS" : "arn:aws:iam::111122223333:user/test-user"
            },
            "Action" : [
                "kms:DescribeKey",
                "kms:ListKeys"
            ],
            "Resource" : "*"
        }
    ]
}
```

Este exemplo usa o ID de chave para identificar a chave do KMS, mas também é possível usar o ARN da chave. O comando usa o parâmetro `policy` para especificar a política de chave. Para indicar que a política está em um arquivo, ela usa o prefixo `file://` necessário. Esse prefixo é necessário para identificar arquivos em todos os sistemas operacionais compatíveis. Por fim, o comando usa o parâmetro `policy-name` com um valor `default`. Esse parâmetro é necessário, embora `default` seja o único valor válido.

```
aws kms put-key-policy \
    --policy-name default \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --policy file://key_policy.json
```

Esse comando não produz nenhuma saída. Use o comando `get-key-policy` para verificar se o comando está em vigor. O comando de exemplo a seguir recupera a política de chave da mesma chave do KMS. O parâmetro `output` com o valor `text` retorna um formato de texto fácil de ler.

```
aws kms get-key-policy \
    --policy-name default \
    --key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
    --output text
```

Saída:

```
{
    "Version" : "2012-10-17",
    "Id" : "key-default-1",
    "Statement" : [
        {
            "Sid" : "Enable IAM User Permissions",
            "Effect" : "Allow",
            "Principal" : {
                "AWS" : "arn:aws:iam::111122223333:root"
            },
            "Action" : "kms:*",
            "Resource" : "*"
            },
            {
            "Sid" : "Allow Use of Key",
            "Effect" : "Allow",
            "Principal" : {
                "AWS" : "arn:aws:iam::111122223333:user/test-user"
            },
            "Action" : [ "kms:Describe", "kms:List" ],
            "Resource" : "*"
        }
    ]
}
```

Para obter mais informações, consulte Changing a Key Policy no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte PutKeyPolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def set_policy(self, key_id, policy):
        """
        Sets the policy of a key. Setting a policy entirely overwrites the
 existing
        policy, so care is taken to add a statement to the existing list of
 statements
        rather than simply writing a new policy.

        :param key_id: The ARN or ID of the key to set the policy to.
        :param policy: The existing policy of the key.
        """
        principal = input(
            "Enter the ARN of an IAM role to set as the principal on the policy:
 "
        )
        if key_id != "" and principal != "":
            # The updated policy replaces the existing policy. Add a new
 statement to
            # the list along with the original policy statements.
            policy["Statement"].append(
                {
                    "Sid": "Allow access for ExampleRole",
                    "Effect": "Allow",
                    "Principal": {"AWS": principal},
                    "Action": [
                        "kms:Encrypt",
                        "kms:GenerateDataKey*",
```

```
                        "kms:Decrypt",
                        "kms:DescribeKey",
                        "kms:ReEncrypt*",
                    ],
                    "Resource": "*",
                }
            )
            try:
                self.kms_client.put_key_policy(
                    KeyId=key_id, PolicyName="default", Policy=json.dumps(policy)
                )
            except ClientError as err:
                logger.error(
                    "Couldn't set policy for key %s. Here's why %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Set policy for key {key_id}.")
        else:
            print("Skipping set policy demo.")
```

- Para obter detalhes da API, consulte a PutKeyPolicyReferência da API AWSSDK for Python (Boto3).

Atualize a AWS KMS key referida por um alias usando um SDK da AWS

Os exemplos de código a seguir mostram como atualizar a chave do KMS referida por um alias.

CLI

AWS CLI

Como associar um alias a uma chave do KMS diferente

O exemplo de `update-alias` a seguir associa o alias `alias/test-key` a uma chave do KMS diferente.

O parâmetro `--alias-name` especifica o alias. O valor do nome do alias deve começar com `alias/`. O parâmetro `--target-key-id` especifica a chave do KMS que deve ser associada ao alias. Não é necessário especificar a chave do KMS atual para o alias.

```
aws kms update-alias \
    --alias-name alias/test-key \
    --target-key-id 1234abcd-12ab-34cd-56ef-1234567890ab
```

Este comando não produz saída. Use o `list-aliases` comando para localizar o alias.

Para obter mais informações, consulte Updating aliases no Guia do desenvolvedor do AWS Key Management Service.

- Para obter detalhes da API, consulte UpdateAliasem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def update_alias(self, alias, current_key_id):
        """
        Updates an alias by assigning it to another key.

        :param alias: The alias to reassign.
        :param current_key_id: The ARN or ID of the key currently associated with
 the alias.
        """
        new_key_id = input(
            f"Alias {alias} is currently associated with {current_key_id}. "
```

```
            f"Enter another key ID or ARN that you want to associate with
{alias}: "
        )
        if new_key_id != "":
            try:
                self.kms_client.update_alias(AliasName=alias,
TargetKeyId=new_key_id)
            except ClientError as err:
                logger.error(
                    "Couldn't associate alias %s with key %s. Here's why: %s",
                    alias,
                    new_key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Alias {alias} is now associated with key {new_key_id}.")
        else:
            print("Skipping alias update.")
```

- Para obter detalhes da API, consulte a UpdateAliasReferência da API AWSSDK for Python (Boto3).

Cenários para o AWS KMS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Key Management Service (AWS KMS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criptografe e descriptografe texto com AWS KMS keys usando um SDK da AWS
- Gerencie AWS KMS keys usando um SDK da AWS

Criptografe e descriptografe texto com AWS KMS keys usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Criptografr texto sem formatação usando uma chave KMS.
- Decriptografar o texto cifrado usando uma chave KMS.
- Recriptografar texto cifrado usando uma segunda chave KMS.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def encrypt(self, key_id):
        """
        Encrypts text by using the specified key.

        :param key_id: The ARN or ID of the key to use for encryption.
        :return: The encrypted version of the text.
        """
        text = input("Enter some text to encrypt: ")
        try:
            cipher_text = self.kms_client.encrypt(
                KeyId=key_id, Plaintext=text.encode()
            )["CiphertextBlob"]
        except ClientError as err:
            logger.error(
                "Couldn't encrypt text. Here's why: %s",
```

```
                err.response["Error"]["Message"],
            )
        else:
            print(f"Your ciphertext is: {cipher_text}")
            return cipher_text


    def decrypt(self, key_id, cipher_text):
        """
        Decrypts text previously encrypted with a key.

        :param key_id: The ARN or ID of the key used to decrypt the data.
        :param cipher_text: The encrypted text to decrypt.
        """
        answer = input("Ready to decrypt your ciphertext (y/n)? ")
        if answer.lower() == "y":
            try:
                text = self.kms_client.decrypt(
                    KeyId=key_id, CiphertextBlob=cipher_text
                )["Plaintext"]
            except ClientError as err:
                logger.error(
                    "Couldn't decrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Your plaintext is {text.decode()}")
        else:
            print("Skipping decryption demo.")


    def re_encrypt(self, source_key_id, cipher_text):
        """
        Takes ciphertext previously encrypted with one key and reencrypt it by
using
        another key.

        :param source_key_id: The ARN or ID of the original key used to encrypt
the
                              ciphertext.
        :param cipher_text: The encrypted ciphertext.
        :return: The ciphertext encrypted by the second key.
        """
        destination_key_id = input(
```

```
            f"Your ciphertext is currently encrypted with key {source_key_id}. "
            f"Enter another key ID or ARN to reencrypt it: "
        )
        if destination_key_id != "":
            try:
                cipher_text = self.kms_client.re_encrypt(
                    SourceKeyId=source_key_id,
                    DestinationKeyId=destination_key_id,
                    CiphertextBlob=cipher_text,
                )["CiphertextBlob"]
            except ClientError as err:
                logger.error(
                    "Couldn't reencrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Reencrypted your ciphertext as: {cipher_text}")
                return cipher_text
        else:
            print("Skipping reencryption demo.")




def key_encryption(kms_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the AWS Key Management Service (AWS KMS) key encryption
 demo.")
    print("-" * 88)

    key_id = input("Enter a key ID or ARN to start the demo: ")
    if key_id == "":
        print("A key is required to run this demo.")
        return

    key_encrypt = KeyEncrypt(kms_client)
    cipher_text = key_encrypt.encrypt(key_id)
    print("-" * 88)
    if cipher_text is not None:
        key_encrypt.decrypt(key_id, cipher_text)
        print("-" * 88)
        key_encrypt.re_encrypt(key_id, cipher_text)
```

```
    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        key_encryption(boto3.client("kms"))
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - Decrypt
  - Encrypt
  - ReEncrypt

Gerencie AWS KMS keys usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Crie uma chave do KMS.
- Listar chaves KMS para uma conta e obter detalhes sobre elas.
- Habilitar e desabilitar chaves do KMS.
- Gerar uma chave de dados simétrica que possa ser usada para criptografia do lado do cliente.
- Excluir chaves do KMS.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def create_key(self):
        """
        Creates a key (or multiple keys) with a user-provided description.
        """
        answer = "y"
        while answer.lower() == "y":
            key_desc = input("\nLet's create a key. Describe it for me: ")
            if not key_desc:
                key_desc = "Key management demo key"
            try:
                key = self.kms_client.create_key(Description=key_desc)
["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't create your key. Here's why: %s",
                    err.response["Error"]["Message"],
                )
                raise
            else:
                print("Key created:")
                pprint(key)
                self.created_keys.append(key)
                answer = input("Create another (y/n)? ")


    def list_keys(self):
        """
        Lists the keys for the current account by using a paginator.
        """
```

```
        try:
            page_size = 10
            print("\nLet's list your keys.")
            key_paginator = self.kms_client.get_paginator("list_keys")
            for key_page in key_paginator.paginate(PaginationConfig={"PageSize":
10}):
                print(f"Here are {len(key_page['Keys'])} keys:")
                pprint(key_page["Keys"])
                if key_page["Truncated"]:
                    answer = input(
                        f"Do you want to see the next {page_size} keys (y/n)? "
                    )
                    if answer.lower() != "y":
                        break
                else:
                    print("That's all your keys!")
        except ClientError as err:
            logging.error(
                "Couldn't list your keys. Here's why: %s",
                err.response["Error"]["Message"],
            )


    def describe_key(self):
        """
        Describes a key.
        """
        key_id = input("Enter a key ID or ARN here to get information about the
key: ")
        if key_id:
            try:
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't get key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Got key {key_id}:")
                pprint(key)
        return key_id
```

```
    def generate_data_key(self, key_id):
        """
        Generates a symmetric data key that can be used for client-side
 encryption.
        """
        answer = input(
            f"Do you want to generate a symmetric data key from key {key_id} (y/
n)? "
        )
        if answer.lower() == "y":
            try:
                data_key = self.kms_client.generate_data_key(
                    KeyId=key_id, KeySpec="AES_256"
                )
            except ClientError as err:
                logger.error(
                    "Couldn't generate a data key for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(data_key)


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state
 change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")

            try:
```

```
                self.kms_client.enable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't enable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")


    def delete_keys(self, keys):
        """
        Deletes a list of keys.

        :param keys: The list of keys to delete.
        """
        answer = input("Do you want to delete these keys (y/n)? ")
        if answer.lower() == "y":
            window = 7
            for key in keys:
                try:
                    self.kms_client.schedule_key_deletion(
                        KeyId=key["KeyId"], PendingWindowInDays=window
                    )
                except ClientError as err:
                    logging.error(
                        "Couldn't delete key %s. Here's why: %s",
                        key["KeyId"],
                        err.response["Error"]["Message"],
                    )
                else:
                    print(
                        f"Key {key['KeyId']} scheduled for deletion in {window}
 days."
                    )




def key_management(kms_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
```

```
    print("-" * 88)
    print("Welcome to the AWS Key Management Service (AWS KMS) key management
 demo.")
    print("-" * 88)

    key_manager = KeyManager(kms_client)
    key_manager.create_key()
    print("-" * 88)
    key_manager.list_keys()
    print("-" * 88)
    key_id = key_manager.describe_key()
    if key_id:
        key_manager.enable_disable_key(key_id)
        print("-" * 88)
        key_manager.generate_data_key(key_id)
    print("-" * 88)
    print("For this demo, we created these keys:")
    for key in key_manager.created_keys:
        print(f"\tKeyId: {key['KeyId']}")
        print(f"\tDescription: {key['Description']}")
        print("-" * 66)
    key_manager.delete_keys(key_manager.created_keys)
    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        key_management(boto3.client("kms"))
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateKey
  - DescribeKey
  - DisableKey
  - EnableKey
  - GenerateDataKey
  - ListKeys

- ScheduleKeyDeletion

Exemplos de código do Lambda usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Lambda com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Lambda – Mais informações sobre o Lambda.
- Referência da API do Lambda – Detalhes sobre todas as ações disponíveis do Lambda.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace LambdaActions;

using Amazon.Lambda;

public class HelloLambda
{
    static async Task Main(string[] args)
    {
        var lambdaClient = new AmazonLambdaClient();

        Console.WriteLine("Hello AWS Lambda");
        Console.WriteLine("Let's get started with AWS Lambda by listing your
 existing Lambda functions:");

        var response = await lambdaClient.ListFunctionsAsync();
        response.Functions.ForEach(function =>
        {

 Console.WriteLine($"{function.FunctionName}\t{function.Description}");
        });
    }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)
```

```
# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS lambda)

# Set this project's name.
project("hello_lambda")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you
 may need to uncomment this
                                       # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_lambda.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_lambda.cpp.

```
#include <aws/core/Aws.h>
#include <aws/lambda/LambdaClient.h>
#include <aws/lambda/model/ListFunctionsRequest.h>
#include <iostream>

/*
 *  A "Hello Lambda" starter application which initializes an AWS Lambda (Lambda)
 client and lists the Lambda functions.
 *
 *  main function
 *
 *  Usage: 'hello_lambda'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Lambda::LambdaClient lambdaClient(clientConfig);
        std::vector<Aws::String> functions;
        Aws::String marker; // Used for pagination.

        do {
            Aws::Lambda::Model::ListFunctionsRequest request;
            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::Lambda::Model::ListFunctionsOutcome outcome =
 lambdaClient.ListFunctions(
                    request);

            if (outcome.IsSuccess()) {
```

```
                const Aws::Lambda::Model::ListFunctionsResult
 &listFunctionsResult = outcome.GetResult();
                std::cout << listFunctionsResult.GetFunctions().size()
                          << " lambda functions were retrieved." << std::endl;

                for (const Aws::Lambda::Model::FunctionConfiguration
 &functionConfiguration: listFunctionsResult.GetFunctions()) {
                    functions.push_back(functionConfiguration.GetFunctionName());
                    std::cout << functions.size() << "  "
                              << functionConfiguration.GetDescription() <<
 std::endl;
                    std::cout << "   "
                              <<
 Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                      functionConfiguration.GetRuntime()) << ": "
                              << functionConfiguration.GetHandler()
                              << std::endl;
                }
                marker = listFunctionsResult.GetNextMarker();
            } else {
                std::cerr << "Error with Lambda::ListFunctions. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!marker.empty());
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/lambda"
)

// main uses the AWS SDK for Go (v2) to create an AWS Lambda client and list up
 to 10
// functions in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 lambdaClient := lambda.NewFromConfig(sdkConfig)

 maxItems := 10
 fmt.Printf("Let's list up to %v functions for your account.\n", maxItems)
 result, err := lambdaClient.ListFunctions(context.TODO(),
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
```

```
 })
 if err != nil {
  fmt.Printf("Couldn't list functions for your account. Here's why: %v\n", err)
  return
 }
 if len(result.Functions) == 0 {
  fmt.Println("You don't have any functions!")
 } else {
  for _, function := range result.Functions {
   fmt.Printf("\t%v\n", *function.FunctionName)
  }
 }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.lambda;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.services.lambda.model.LambdaException;
import software.amazon.awssdk.services.lambda.model.ListFunctionsResponse;
import software.amazon.awssdk.services.lambda.model.FunctionConfiguration;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListLambdaFunctions {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        listFunctions(awsLambda);
        awsLambda.close();
    }

    public static void listFunctions(LambdaClient awsLambda) {
        try {
            ListFunctionsResponse functionResult = awsLambda.listFunctions();
            List<FunctionConfiguration> list = functionResult.functions();
            for (FunctionConfiguration config : list) {
                System.out.println("The function name is " +
 config.functionName());
            }

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { LambdaClient, paginateListFunctions } from "@aws-sdk/client-lambda";

const client = new LambdaClient({});

export const helloLambda = async () => {
  const paginator = paginateListFunctions({ client }, {});
  const functions = [];

  for await (const page of paginator) {
    const funcNames = page.Functions.map((f) => f.FunctionName);
    functions.push(...funcNames);
  }

  console.log("Functions:");
  console.log(functions.join("\n"));
  return functions;
};
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for JavaScript da API.

Exemplos de código

- Ações do Lambda usando AWS SDKs
  - Criar uma função do Lambda usando um AWS SDK
  - Excluir uma função do Lambda usando um AWS SDK
  - Obter uma função do Lambda usando um AWS SDK
  - Invocar uma função do Lambda usando um AWS SDK
  - Listar funções do Lambda usando um AWS SDK

- Excluir um código de função do Lambda usando um AWS SDK
- Atualizar uma configuração de função do Lambda usando um AWS SDK
- Cenários do Lambda usando AWS SDKs
  - Começar a criar e invocar funções do Lambda usando um AWS SDK
- Exemplos de tecnologia sem servidor para o Lambda usando SDKs da AWS
  - Conectando-se a um banco de dados do Amazon RDS em uma função Lambda
  - Invocar uma função do Lambda em um trigger do Kinesis
  - Invocar uma função do Lambda em um acionador do Amazon S3
  - Invocar uma função do Lambda em um acionador do Amazon SNS
  - Invocar uma função do Lambda em um trigger do Amazon SQS
  - Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis
  - Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS
- Exemplos do Lambda entre serviços usando AWS SDKs
  - Criar uma API REST do API Gateway para monitorar dados da COVID-19
  - Criar uma API REST de biblioteca de empréstimos
  - Criar uma aplicação de mensageiro com o Step Functions
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Criar uma aplicação de chat websocket com o API Gateway
  - Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
  - Chamar uma função do Lambda em um navegador
  - Usar o API Gateway para invocar uma função do Lambda
  - Usar Step Functions para invocar funções do Lambda
  - Usar eventos programados para chamar uma função do Lambda

Ações do Lambda usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Lambda com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Lambda usando AWS SDKs.

Exemplos

- Criar uma função do Lambda usando um AWS SDK
- Excluir uma função do Lambda usando um AWS SDK
- Obter uma função do Lambda usando um AWS SDK
- Invocar uma função do Lambda usando um AWS SDK
- Listar funções do Lambda usando um AWS SDK
- Excluir um código de função do Lambda usando um AWS SDK
- Atualizar uma configuração de função do Lambda usando um AWS SDK

Criar uma função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Creates a new Lambda function.
/// </summary>
/// <param name="functionName">The name of the function.</param>
/// <param name="s3Bucket">The Amazon Simple Storage Service (Amazon S3)
/// bucket where the zip file containing the code is located.</param>
/// <param name="s3Key">The Amazon S3 key of the zip file.</param>
/// <param name="role">The Amazon Resource Name (ARN) of a role with the
```

```
    /// appropriate Lambda permissions.</param>
    /// <param name="handler">The name of the handler function.</param>
    /// <returns>The Amazon Resource Name (ARN) of the newly created
    /// Lambda function.</returns>
    public async Task<string> CreateLambdaFunctionAsync(
        string functionName,
        string s3Bucket,
        string s3Key,
        string role,
        string handler)
    {
        // Defines the location for the function code.
        // S3Bucket - The S3 bucket where the file containing
        //            the source code is stored.
        // S3Key    - The name of the file containing the code.
        var functionCode = new FunctionCode
        {
            S3Bucket = s3Bucket,
            S3Key = s3Key,
        };

        var createFunctionRequest = new CreateFunctionRequest
        {
            FunctionName = functionName,
            Description = "Created by the Lambda .NET API",
            Code = functionCode,
            Handler = handler,
            Runtime = Runtime.Dotnet6,
            Role = role,
        };

        var reponse = await
_lambdaService.CreateFunctionAsync(createFunctionRequest);
        return reponse.FunctionArn;
    }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same
 architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_8);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
```

```
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
 buffer.str().c_str(),
                                                buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome =
 client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " <<
 seconds
                      << " seconds elapsed." << std::endl;
            break;
        }

        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for C++ da API.

CLI

AWS CLI

Criar uma função do Lambda

O exemplo `create-function` a seguir cria uma função do Lambda denominada `my-function`.

```
aws lambda create-function \
    --function-name my-function \
    --runtime nodejs14.x \
    --zip-file fileb://my-function.zip \
    --handler my-function.handler \
    --role arn:aws:iam::123456789012:role/service-role/MyTestFunction-role-
tges6bf4
```

Conteúdo de `my-function.zip`: esse arquivo é um pacote de implantação que contém o código de função e todas as dependências.

Saída:

```
{
    "TracingConfig": {
        "Mode": "PassThrough"
    },
    "CodeSha256": "PFn4S+er27qk+UuZSTKEQfNKG/XNn7QJs90mJgq6oH8=",
    "FunctionName": "my-function",
    "CodeSize": 308,
    "RevisionId": "873282ed-4cd3-4dc8-a069-d0c647e470c6",
    "MemorySize": 128,
    "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-function",
    "Version": "$LATEST",
    "Role": "arn:aws:iam::123456789012:role/service-role/MyTestFunction-role-
zgur6bf4",
    "Timeout": 3,
    "LastModified": "2019-08-14T22:26:11.234+0000",
    "Handler": "my-function.handler",
```

```
    "Runtime": "nodejs14.x",
    "Description": ""
}
```

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte CreateFunctionem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// CreateFunction creates a new Lambda function from code contained in the
 zipPackage
// buffer. The specified handlerName must match the name of the file and function
// contained in the uploaded code. The role specified by iamRoleArn is assumed by
// Lambda and grants specific permissions.
// When the function already exists, types.StateActive is returned.
// When the function is created, a lambda.FunctionActiveV2Waiter is used to wait
 until the
// function is active.
func (wrapper FunctionWrapper) CreateFunction(functionName string, handlerName
 string,
 iamRoleArn *string, zipPackage *bytes.Buffer) types.State {
```

```
 var state types.State
 _, err := wrapper.LambdaClient.CreateFunction(context.TODO(),
 &lambda.CreateFunctionInput{
  Code:         &types.FunctionCode{ZipFile: zipPackage.Bytes()},
  FunctionName: aws.String(functionName),
  Role:         iamRoleArn,
  Handler:      aws.String(handlerName),
  Publish:      true,
  Runtime:      types.RuntimePython38,
 })
 if err != nil {
  var resConflict *types.ResourceConflictException
  if errors.As(err, &resConflict) {
   log.Printf("Function %v already exists.\n", functionName)
   state = types.StateActive
  } else {
   log.Panicf("Couldn't create function %v. Here's why: %v\n", functionName, err)
  }
 } else {
  waiter := lambda.NewFunctionActiveV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(),
 &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.services.lambda.model.CreateFunctionRequest;
import software.amazon.awssdk.services.lambda.model.FunctionCode;
import software.amazon.awssdk.services.lambda.model.CreateFunctionResponse;
import software.amazon.awssdk.services.lambda.model.GetFunctionRequest;
import software.amazon.awssdk.services.lambda.model.GetFunctionResponse;
import software.amazon.awssdk.services.lambda.model.LambdaException;
import software.amazon.awssdk.services.lambda.model.Runtime;
import software.amazon.awssdk.services.lambda.waiters.LambdaWaiter;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;

/**
 * This code example requires a ZIP or JAR that represents the code of the
 * Lambda function.
 * If you do not have a ZIP or JAR, please refer to the following document:
 *
 * https://github.com/aws-doc-sdk-examples/tree/master/javav2/usecases/
creating_workflows_stepfunctions
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class CreateFunction {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <functionName> <filePath> <role> <handler>\s

                Where:
                    functionName - The name of the Lambda function.\s
                    filePath - The path to the ZIP or JAR where the code is
 located.\s
                    role - The role ARN that has Lambda permissions.\s
                    handler - The fully qualified method name (for example,
 example.Handler::handleRequest). \s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        String filePath = args[1];
        String role = args[2];
        String handler = args[3];
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        createLambdaFunction(awsLambda, functionName, filePath, role, handler);
        awsLambda.close();
    }

    public static void createLambdaFunction(LambdaClient awsLambda,
            String functionName,
            String filePath,
            String role,
            String handler) {

        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
```

```
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);

            FunctionCode code = FunctionCode.builder()
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest =
 CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("Created by the Lambda Java API")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA8)
                    .role(role)
                    .build();

            // Create a Lambda function using a waiter.
            CreateFunctionResponse functionResponse =
 awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
 waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("The function ARN is " +
 functionResponse.functionArn());

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createFunction = async (funcName, roleArn) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${funcName}.zip`);

  const command = new CreateFunctionCommand({
    Code: { ZipFile: code },
    FunctionName: funcName,
    Role: roleArn,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewFunction(
    myFunctionName: String,
    s3BucketName: String,
    myS3Key: String,
    myHandler: String,
    myRole: String
): String? {

    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }

    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java8
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val functionResponse = awsLambda.createFunction(request)
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        return functionResponse.functionArn
    }
}
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function createFunction($functionName, $role, $bucketName, $handler)
    {
        //This assumes the Lambda function is in an S3 bucket.
        return $this->customWaiter(function () use ($functionName, $role,
$bucketName, $handler) {
            return $this->lambdaClient->createFunction([
                'Code' => [
                    'S3Bucket' => $bucketName,
                    'S3Key' => $functionName,
                ],
                'FunctionName' => $functionName,
                'Role' => $role['Arn'],
                'Runtime' => 'python3.9',
                'Handler' => "$handler.lambda_handler",
            ]);
        });
    }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def create_function(
        self, function_name, handler_name, iam_role, deployment_package
    ):
        """
        Deploys a Lambda function.

        :param function_name: The name of the Lambda function.
        :param handler_name: The fully qualified name of the handler function.
 This
                              must include the file name and the function name.
        :param iam_role: The IAM role to use for the function.
        :param deployment_package: The deployment package that contains the
 function
                                      code in .zip format.
        :return: The Amazon Resource Name (ARN) of the newly created function.
        """
        try:
            response = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="AWS Lambda doc example",
                Runtime="python3.8",
                Role=iam_role.arn,
                Handler=handler_name,
                Code={"ZipFile": deployment_package},
                Publish=True,
            )
            function_arn = response["FunctionArn"]
            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)
            logger.info(
                "Created function '%s' with ARN: '%s'.",
                function_name,
                response["FunctionArn"],
            )
        except ClientError:
            logger.error("Couldn't create function %s.", function_name)
            raise
```

```
        else:
            return function_arn
```

- Para obter detalhes da API, consulte a CreateFunctionReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Deploys a Lambda function.
  #
  # @param function_name: The name of the Lambda function.
  # @param handler_name: The fully qualified name of the handler function. This
  #                      must include the file name and the function name.
  # @param role_arn: The IAM role to use for the function.
  # @param deployment_package: The deployment package that contains the function
  #                            code in .zip format.
  # @return: The Amazon Resource Name (ARN) of the newly created function.
  def create_function(function_name, handler_name, role_arn, deployment_package)
    response = @lambda_client.create_function({
                                                role: role_arn.to_s,
                                                function_name: function_name,
                                                handler: handler_name,
```

```
                                                    runtime: "ruby2.7",
                                                    code: {
                                                      zip_file: deployment_package
                                                    },
                                                    environment: {
                                                      variables: {
                                                        "LOG_LEVEL" => "info"
                                                      }
                                                    }
                                                  })
   @lambda_client.wait_until(:function_active_v2, { function_name:
function_name}) do |w|
     w.max_attempts = 5
     w.delay = 5
   end
   response
 rescue Aws::Lambda::Errors::ServiceException => e
   @logger.error("There was an error creating #{function_name}:\n #{e.message}")
 rescue Aws::Waiters::Errors::WaiterFailed => e
   @logger.error("Failed waiting for #{function_name} to activate:\n
#{e.message}")
 end
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /**
    * Create a function, uploading from a zip file.
    */
```

```
    pub async fn create_function(&self, zip_file: PathBuf) -> Result<String,
anyhow::Error> {
        let code = self.prepare_function(zip_file, None).await?;

        let key = code.s3_key().unwrap().to_string();

        self.create_role().await;

        let role = self
            .iam_client
            .create_role()
            .role_name(self.role_name.clone())
            .assume_role_policy_document(ROLE_POLICY_DOCUMENT)
            .send()
            .await?;

        info!("Created iam role, waiting 15s for it to become active");
        tokio::time::sleep(Duration::from_secs(15)).await;

        info!("Creating lambda function {}", self.lambda_name);
        let _ = self
            .lambda_client
            .create_function()
            .function_name(self.lambda_name.clone())
            .code(code)
            .role(role.role().map(|r| r.arn()).unwrap_or_default())
            .runtime(aws_sdk_lambda::types::Runtime::Providedal2)
            .handler("_unused")
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        self.lambda_client
            .publish_version()
            .function_name(self.lambda_name.clone())
            .send()
            .await?;

        Ok(key)
    }

    /**
```

```
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --
output-format Zip`.
     */
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));

        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
            .s3_key(key)
            .build())
    }
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       lo_lmd->createfunction(
           iv_functionname = iv_function_name
           iv_runtime = `python3.9`
           iv_role = iv_role_arn
           iv_handler = iv_handler
           io_code = io_zip_file
           iv_description = 'AWS Lambda code example'
       ).
       MESSAGE 'Lambda function created.' TYPE 'I'.
     CATCH /aws1/cx_lmdcodesigningcfgno00.
       MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
     CATCH /aws1/cx_lmdcodestorageexcdex.
       MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
     CATCH /aws1/cx_lmdcodeverification00.
       MESSAGE 'Code signature failed one or more validation checks for
signature mismatch or expiration.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvalidcodesigex.
       MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvparamvalueex.
       MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
     CATCH /aws1/cx_lmdresourceconflictex.
       MESSAGE 'Resource already exists or another operation is in progress.'
TYPE 'E'.
     CATCH /aws1/cx_lmdresourcenotfoundex.
       MESSAGE 'The requested resource does not exist.' TYPE 'E'.
     CATCH /aws1/cx_lmdserviceexception.
       MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
     CATCH /aws1/cx_lmdtoomanyrequestsex.
       MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWS SDK for SAP ABAP.

Excluir uma função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an AWS Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// delete.</param>
    /// <returns>A Boolean value that indicates the success of the action.</
returns>
    public async Task<bool> DeleteFunctionAsync(string functionName)
    {
        var request = new DeleteFunctionRequest
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.DeleteFunctionAsync(request);

        // A return value of NoContent means that the request was processed.
        // In this case, the function was deleted, and the return value
        // is intentionally blank.
        return response.HttpStatusCode == System.Net.HttpStatusCode.NoContent;
    }
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    Aws::Lambda::Model::DeleteFunctionRequest request;
    request.SetFunctionName(LAMBDA_NAME);

    Aws::Lambda::Model::DeleteFunctionOutcome outcome = client.DeleteFunction(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "The lambda function was successfully deleted." <<
std::endl;
    }
    else {
        std::cerr << "Error with Lambda::DeleteFunction. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: excluir uma função do Lambda pelo nome da função

O exemplo de `delete-function` a seguir exclui a função do Lambda denominada `my-function` ao especificar o nome da função.

```
aws lambda delete-function \
    --function-name my-function
```

Este comando não produz saída.

Exemplo 2: excluir uma função do Lambda pelo ARN da função

O exemplo `delete-function` a seguir exclui a função do Lambda denominada `my-function` ao especificar o ARN da função.

```
aws lambda delete-function \
    --function-name arn:aws:lambda:us-west-2:123456789012:function:my-function
```

Este comando não produz saída.

Exemplo 3: excluir uma função do Lambda pelo ARN parcial da função

O exemplo `delete-function` a seguir exclui a função do Lambda denominada `my-function` ao especificar o ARN parcial da função.

```
aws lambda delete-function \
    --function-name 123456789012:function:my-function
```

Este comando não produz saída.

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte DeleteFunctionem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// DeleteFunction deletes the Lambda function specified by functionName.
func (wrapper FunctionWrapper) DeleteFunction(functionName string) {
 _, err := wrapper.LambdaClient.DeleteFunction(context.TODO(),
 &lambda.DeleteFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't delete function %v. Here's why: %v\n", functionName, err)
 }
}
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.model.DeleteFunctionRequest;
import software.amazon.awssdk.services.lambda.model.LambdaException;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteFunction {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName>\s

                Where:
                    functionName - The name of the Lambda function.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        Region region = Region.US_EAST_1;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        deleteLambdaFunction(awsLambda, functionName);
        awsLambda.close();
    }

    public static void deleteLambdaFunction(LambdaClient awsLambda, String
 functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            awsLambda.deleteFunction(request);
            System.out.println("The " + functionName + " function was deleted");

        } catch (LambdaException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * @param {string} funcName
 */
const deleteFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new DeleteFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun delLambdaFunction(myFunctionName: String) {

    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function deleteFunction($functionName)
    {
        return $this->lambdaClient->deleteFunction([
            'FunctionName' => $functionName,
        ]);
```

```
    }
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def delete_function(self, function_name):
        """
        Deletes a Lambda function.

        :param function_name: The name of the function to delete.
        """
        try:
            self.lambda_client.delete_function(FunctionName=function_name)
        except ClientError:
            logger.exception("Couldn't delete function %s.", function_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteFunctionReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Deletes a Lambda function.
  # @param function_name: The name of the function to delete.
  def delete_function(function_name)
    print "Deleting function: #{function_name}..."
    @lambda_client.delete_function(
      function_name: function_name
    )
    print "Done!".green
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error deleting #{function_name}:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /** Delete a function and its role, and if possible or necessary, its
associated code object and bucket. */
   pub async fn delete_function(
       &self,
       location: Option<String>,
   ) -> (
       Result<DeleteFunctionOutput, anyhow::Error>,
       Result<DeleteRoleOutput, anyhow::Error>,
       Option<Result<DeleteObjectOutput, anyhow::Error>>,
   ) {
       info!("Deleting lambda function {}", self.lambda_name);
       let delete_function = self
           .lambda_client
           .delete_function()
           .function_name(self.lambda_name.clone())
           .send()
           .await
           .map_err(anyhow::Error::from);

       info!("Deleting iam role {}", self.role_name);
       let delete_role = self
           .iam_client
           .delete_role()
           .role_name(self.role_name.clone())
           .send()
           .await
           .map_err(anyhow::Error::from);

       let delete_object: Option<Result<DeleteObjectOutput, anyhow::Error>> =
           if let Some(location) = location {
               info!("Deleting object {location}");
               Some(
```

```
                    self.s3_client
                        .delete_object()
                        .bucket(self.bucket.clone())
                        .key(location)
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
            } else {
                info!(?location, "Skipping delete object");
                None
            };

        (delete_function, delete_role, delete_object)
    }
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_lmd->deletefunction( iv_functionname = iv_function_name ).
        MESSAGE 'Lambda function deleted.' TYPE 'I'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.'
TYPE 'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
```

```
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWS SDK for SAP ABAP.

Obter uma função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como obter uma função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Gets information about a Lambda function.
   /// </summary>
   /// <param name="functionName">The name of the Lambda function for
   /// which to retrieve information.</param>
   /// <returns>Async Task.</returns>
   public async Task<FunctionConfiguration> GetFunctionAsync(string
functionName)
   {
       var functionRequest = new GetFunctionRequest
       {
           FunctionName = functionName,
       };
```

```
        var response = await _lambdaService.GetFunctionAsync(functionRequest);
        return response.Configuration;
    }
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Lambda::LambdaClient client(clientConfig);

       Aws::Lambda::Model::GetFunctionRequest request;
       request.SetFunctionName(functionName);

       Aws::Lambda::Model::GetFunctionOutcome outcome =
client.GetFunction(request);

       if (outcome.IsSuccess()) {
           std::cout << "Function retrieve.\n" <<

outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                     << std::endl;
       }
       else {
           std::cerr << "Error with Lambda::GetFunction. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
```

```
        }
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for C++ da API.

CLI

AWS CLI

Recuperar informações sobre uma função

O exemplo `get-function` a seguir mostra informações sobre a função `my-function`.

```
aws lambda get-function \
    --function-name  my-function
```

Saída:

```
{
    "Concurrency": {
        "ReservedConcurrentExecutions": 100
    },
    "Code": {
        "RepositoryType": "S3",
        "Location": "https://awslambda-us-west-2-tasks.s3.us-
west-2.amazonaws.com/snapshots/123456789012/my-function..."
    },
    "Configuration": {
        "TracingConfig": {
            "Mode": "PassThrough"
        },
        "Version": "$LATEST",
        "CodeSha256": "5tT2qgzYUHoqwR616pZ2dpkn/0J1FrzJmlKidWaaCgk=",
        "FunctionName": "my-function",
        "VpcConfig": {
            "SubnetIds": [],
            "VpcId": "",
            "SecurityGroupIds": []
        },
        "MemorySize": 128,
        "RevisionId": "28f0fb31-5c5c-43d3-8955-03e76c5c1075",
        "CodeSize": 304,
```

```
        "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-
function",
        "Handler": "index.handler",
        "Role": "arn:aws:iam::123456789012:role/service-role/helloWorldPython-
role-uy3l9qyq",
        "Timeout": 3,
        "LastModified": "2019-09-24T18:20:35.054+0000",
        "Runtime": "nodejs10.x",
        "Description": ""
    }
}
```

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte GetFunctionem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// GetFunction gets data about the Lambda function specified by functionName.
func (wrapper FunctionWrapper) GetFunction(functionName string) types.State {
 var state types.State
 funcOutput, err := wrapper.LambdaClient.GetFunction(context.TODO(),
 &lambda.GetFunctionInput{
  FunctionName: aws.String(functionName),
```

```
 })
 if err != nil {
  log.Panicf("Couldn't get function %v. Here's why: %v\n", functionName, err)
 } else {
  state = funcOutput.Configuration.State
 }
 return state
}
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new GetFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function getFunction($functionName)
    {
        return $this->lambdaClient->getFunction([
            'FunctionName' => $functionName,
        ]);
    }
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def get_function(self, function_name):
        """
        Gets data about a Lambda function.
```

```
        :param function_name: The name of the function.
        :return: The function data.
        """
        response = None
        try:
            response =
 self.lambda_client.get_function(FunctionName=function_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Function %s does not exist.", function_name)
            else:
                logger.error(
                    "Couldn't get function %s. Here's why: %s: %s",
                    function_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response
```

- Para obter detalhes da API, consulte a GetFunctionReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
```

```
    @logger.level = Logger::WARN
  end

  # Gets data about a Lambda function.
  #
  # @param function_name: The name of the function.
  # @return response: The function data, or nil if no such function exists.
  def get_function(function_name)
    @lambda_client.get_function(
      {
        function_name: function_name
      }
    )
  rescue Aws::Lambda::Errors::ResourceNotFoundException => e
    @logger.debug("Could not find function: #{function_name}:\n #{e.message}")
    nil
  end
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Get the Lambda function with this Manager's name. */
    pub async fn get_function(&self) -> Result<GetFunctionOutput, anyhow::Error>
{
        info!("Getting lambda function");
        self.lambda_client
            .get_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
```

- Para obter detalhes da API, consulte a GetFunctionreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result =  lo_lmd->getfunction( iv_functionname = iv_function_name ).
    " oo_result is returned for testing purposes. "
       MESSAGE 'Lambda function information retrieved.' TYPE 'I'.
     CATCH /aws1/cx_lmdinvparamvalueex.
       MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
     CATCH /aws1/cx_lmdserviceexception.
       MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
     CATCH /aws1/cx_lmdtoomanyrequestsex.
       MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a GetFunctionreferência da API AWS SDK for SAP ABAP.

Invocar uma função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como invocar uma função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Invoke a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// invoke.</param
    /// <param name="parameters">The parameter values that will be passed to the
function.</param>
    /// <returns>A System Threading Task.</returns>
    public async Task<string> InvokeFunctionAsync(
        string functionName,
        string parameters)
    {
        var payload = parameters;
        var request = new InvokeRequest
        {
            FunctionName = functionName,
            Payload = payload,
        };

        var response = await _lambdaService.InvokeAsync(request);
        MemoryStream stream = response.Payload;
        string returnValue =
System.Text.Encoding.UTF8.GetString(stream.ToArray());
        return returnValue;
    }
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Lambda::LambdaClient client(clientConfig);

       Aws::Lambda::Model::InvokeRequest request;
       request.SetFunctionName(LAMBDA_NAME);
       request.SetLogType(logType);
       std::shared_ptr<Aws::IOStream> payload =
Aws::MakeShared<Aws::StringStream>(
               "FunctionTest");
       *payload << jsonPayload.View().WriteReadable();
       request.SetBody(payload);
       request.SetContentType("application/json");
       Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

       if (outcome.IsSuccess()) {
           invokeResult = std::move(outcome.GetResult());
           result = true;
           break;
       }

       else {
           std::cerr << "Error with Lambda::InvokeRequest. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           break;
       }
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for C++.

CLI

AWS CLI

Exemplo 1: invocar uma função do Lambda de forma síncrona

O exemplo de `invoke` a seguir invoca a função `my-function` de forma síncrona. A opção `cli-binary-format` será necessária se você estiver usando a AWS CLI versão 2. Para obter mais informações, consulte Opções de linha de comando globais compatíveis da AWS CLI no Guia do usuário da AWS Command Line Interface.

```
aws lambda invoke \
    --function-name my-function \
    --cli-binary-format raw-in-base64-out \
    --payload '{ "name": "Bob" }' \
    response.json
```

Saída:

```
{
    "ExecutedVersion": "$LATEST",
    "StatusCode": 200
}
```

Para obter mais informações, consulte Invocação síncrona no Guia do desenvolvedor do AWS Lambda.

Exemplo 2: invocar uma função do Lambda de forma assíncrona

O exemplo `invoke` a seguir invoca a função `my-function` de forma assíncrona. A opção `cli-binary-format` será necessária se você estiver usando a AWS CLI versão 2. Para obter mais informações, consulte Opções de linha de comando globais compatíveis da AWS CLI no Guia do usuário da AWS Command Line Interface.

```
aws lambda invoke \
    --function-name my-function \
    --invocation-type Event \
    --cli-binary-format raw-in-base64-out \
    --payload '{ "name": "Bob" }' \
```

```
    response.json
```

Saída:

```
{
    "StatusCode": 202
}
```

Para obter mais informações, consulte Invocação assíncrona no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte Invocar na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// Invoke invokes the Lambda function specified by functionName, passing the
 parameters
// as a JSON payload. When getLog is true, types.LogTypeTail is specified, which
 tells
// Lambda to include the last few log lines in the returned result.
func (wrapper FunctionWrapper) Invoke(functionName string, parameters any, getLog
 bool) *lambda.InvokeOutput {
 logType := types.LogTypeNone
 if getLog {
```

```
  logType = types.LogTypeTail
 }
 payload, err := json.Marshal(parameters)
 if err != nil {
  log.Panicf("Couldn't marshal parameters to JSON. Here's why %v\n", err)
 }
 invokeOutput, err := wrapper.LambdaClient.Invoke(context.TODO(),
 &lambda.InvokeInput{
  FunctionName: aws.String(functionName),
  LogType:      logType,
  Payload:      payload,
 })
 if err != nil {
  log.Panicf("Couldn't invoke function %v. Here's why: %v\n", functionName, err)
 }
 return invokeOutput
}
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import org.json.JSONObject;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.model.InvokeRequest;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.services.lambda.model.InvokeResponse;
import software.amazon.awssdk.services.lambda.model.LambdaException;

public class LambdaInvoke {
```

```
    /*
     * Function names appear as
     * arn:aws:lambda:us-west-2:335556666777:function:HelloFunction
     * you can retrieve the value by looking at the function in the AWS Console
     *
     * Also, set up your development environment, including your credentials.
     *
     * For information, see this documentation topic:
     *
     * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.
     * html
     */

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName>\s

                Where:
                    functionName - The name of the Lambda function\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        invokeFunction(awsLambda, functionName);
        awsLambda.close();
    }

    public static void invokeFunction(LambdaClient awsLambda, String
 functionName) {

        InvokeResponse res = null;
```

```
        try {
            // Need a SdkBytes instance for the payload.
            JSONObject jsonObj = new JSONObject();
            jsonObj.put("inputValue", "2000");
            String json = jsonObj.toString();
            SdkBytes payload = SdkBytes.fromUtf8String(json);

            // Setup an InvokeRequest.
            InvokeRequest request = InvokeRequest.builder()
                    .functionName(functionName)
                    .payload(payload)
                    .build();

            res = awsLambda.invoke(request);
            String value = res.payload().asUtf8String();
            System.out.println(value);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const invoke = async (funcName, payload) => {
  const client = new LambdaClient({});
  const command = new InvokeCommand({
```

```
    FunctionName: funcName,
    Payload: JSON.stringify(payload),
    LogType: LogType.Tail,
  });

  const { Payload, LogResult } = await client.send(command);
  const result = Buffer.from(Payload).toString();
  const logs = Buffer.from(LogResult, "base64").toString();
  return { logs, result };
};
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun invokeFunction(functionNameVal: String) {

    val json = """{"inputValue":"1000"}"""
    val byteArray = json.trimIndent().encodeToByteArray()
    val request = InvokeRequest {
        functionName = functionNameVal
        logType = LogType.Tail
        payload = byteArray
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val res = awsLambda.invoke(request)
        println("${res.payload?.toString(Charsets.UTF_8)}")
        println("The log result is ${res.logResult}")
    }
}
```

- Para obter detalhes da API, consulte Invoke na Referência da APIs do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function invoke($functionName, $params, $logType = 'None')
    {
        return $this->lambdaClient->invoke([
            'FunctionName' => $functionName,
            'Payload' => json_encode($params),
            'LogType' => $logType,
        ]);
    }
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
```

```
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def invoke_function(self, function_name, function_params, get_log=False):
        """
        Invokes a Lambda function.

        :param function_name: The name of the function to invoke.
        :param function_params: The parameters of the function as a dict. This
dict
                                is serialized to JSON before it is sent to
Lambda.
        :param get_log: When true, the last 4 KB of the execution log are
included in
                        the response.
        :return: The response from the function invocation.
        """
        try:
            response = self.lambda_client.invoke(
                FunctionName=function_name,
                Payload=json.dumps(function_params),
                LogType="Tail" if get_log else "None",
            )
            logger.info("Invoked function %s.", function_name)
        except ClientError:
            logger.exception("Couldn't invoke function %s.", function_name)
            raise
        return response
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Invokes a Lambda function.
  # @param function_name [String] The name of the function to invoke.
  # @param payload [nil] Payload containing runtime parameters.
  # @return [Object] The response from the function invocation.
  def invoke_function(function_name, payload = nil)
    params = { function_name: function_name}
    params[:payload] = payload unless payload.nil?
    @lambda_client.invoke(params)
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n
 #{e.message}")
  end
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Invoke the lambda function using calculator InvokeArgs. */
    pub async fn invoke(&self, args: InvokeArgs) -> Result<InvokeOutput,
 anyhow::Error> {
        info!(?args, "Invoking {}", self.lambda_name);
        let payload = serde_json::to_string(&args)?;
        debug!(?payload, "Sending payload");
        self.lambda_client
            .invoke()
            .function_name(self.lambda_name.clone())
            .payload(Blob::new(payload))
            .send()
            .await
            .map_err(anyhow::Error::from)
    }

fn log_invoke_output(invoke: &InvokeOutput, message: &str) {
    if let Some(payload) = invoke.payload().cloned() {
        let payload = String::from_utf8(payload.into_inner());
        info!(?payload, message);
    } else {
        info!("Could not extract payload")
    }
    if let Some(logs) = invoke.log_result() {
        debug!(?logs, "Invoked function logs")
    } else {
        debug!("Invoked function had no logs")
    }
}
```

- Para obter detalhes da API, consulte Invoke na Referência da API do AWS SDK para Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       DATA(lv_json) = /aws1/cl_rt_util=>string_to_xstring(
         `{`  &&
           `"action": "increment",`  &&
           `"number": 10` &&
         `}`
       ).
       oo_result =  lo_lmd->invoke(                  " oo_result is returned for
testing purposes. "
               iv_functionname = iv_function_name
               iv_payload = lv_json
            ).
       MESSAGE 'Lambda function invoked.' TYPE 'I'.
     CATCH /aws1/cx_lmdinvparamvalueex.
       MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvrequestcontex.
       MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvalidzipfileex.
       MESSAGE 'The deployment package could not be unzipped.' TYPE 'E'.
     CATCH /aws1/cx_lmdrequesttoolargeex.
       MESSAGE 'Invoke request body JSON input limit was exceeded by the request
payload.' TYPE 'E'.
     CATCH /aws1/cx_lmdresourceconflictex.
       MESSAGE 'Resource already exists or another operation is in progress.'
TYPE 'E'.
     CATCH /aws1/cx_lmdresourcenotfoundex.
       MESSAGE 'The requested resource does not exist.' TYPE 'E'.
     CATCH /aws1/cx_lmdserviceexception.
       MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
     CATCH /aws1/cx_lmdtoomanyrequestsex.
       MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
```

```
      CATCH /aws1/cx_lmdunsuppedmediatyp00.
        MESSAGE 'Invoke request body does not have JSON as its content type.'
TYPE 'E'.
   ENDTRY.
```

- Para obter os detalhes da API, consulte Invoke na Referência da API do AWS SDK para SAP ABAP.

Listar funções do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como listar funções do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of Lambda functions.
    /// </summary>
    /// <returns>A list of FunctionConfiguration objects.</returns>
    public async Task<List<FunctionConfiguration>> ListFunctionsAsync()
    {
        var functionList = new List<FunctionConfiguration>();

        var functionPaginator =
            _lambdaService.Paginators.ListFunctions(new ListFunctionsRequest());
        await foreach (var function in functionPaginator.Functions)
        {
```

```
            functionList.Add(function);
        }

        return functionList;
    }
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    std::vector<Aws::String> functions;
    Aws::String marker;

    do {
        Aws::Lambda::Model::ListFunctionsRequest request;
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
```

```
            std::cout << result.GetFunctions().size()
                      << " lambda functions were retrieved." << std::endl;

            for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
                functions.push_back(functionConfiguration.GetFunctionName());
                std::cout << functions.size() << "  "
                          << functionConfiguration.GetDescription() << std::endl;
                std::cout << "   "
                          <<
Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                  functionConfiguration.GetRuntime()) << ": "
                          << functionConfiguration.GetHandler()
                          << std::endl;
            }
            marker = result.GetNextMarker();
        }
        else {
            std::cerr << "Error with Lambda::ListFunctions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Recuperar uma lista de funções do Lambda

O exemplo de `list-functions` a seguir exibe uma lista de todas as funções do usuário atual.

```
aws lambda list-functions
```

Saída:

```
{
    "Functions": [
```

```
        {
            "TracingConfig": {
                "Mode": "PassThrough"
            },
            "Version": "$LATEST",
            "CodeSha256": "dBG9m8SGdmlEjw/JYXlhhvCrAv5TxvXsbL/RMr0fT/I=",
            "FunctionName": "helloworld",
            "MemorySize": 128,
            "RevisionId": "1718e831-badf-4253-9518-d0644210af7b",
            "CodeSize": 294,
            "FunctionArn": "arn:aws:lambda:us-
west-2:123456789012:function:helloworld",
            "Handler": "helloworld.handler",
            "Role": "arn:aws:iam::123456789012:role/service-role/MyTestFunction-
role-zgur6bf4",
            "Timeout": 3,
            "LastModified": "2019-09-23T18:32:33.857+0000",
            "Runtime": "nodejs10.x",
            "Description": ""
        },
        {
            "TracingConfig": {
                "Mode": "PassThrough"
            },
            "Version": "$LATEST",
            "CodeSha256": "sU0cJ2/hOZevwV/lTxCuQqK3gDZP3i8gUoqUUVRmY6E=",
            "FunctionName": "my-function",
            "VpcConfig": {
                "SubnetIds": [],
                "VpcId": "",
                "SecurityGroupIds": []
            },
            "MemorySize": 256,
            "RevisionId": "93017fc9-59cb-41dc-901b-4845ce4bf668",
            "CodeSize": 266,
            "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-
function",
            "Handler": "index.handler",
            "Role": "arn:aws:iam::123456789012:role/service-role/
helloWorldPython-role-uy3l9qyq",
            "Timeout": 3,
            "LastModified": "2019-10-01T16:47:28.490+0000",
            "Runtime": "nodejs10.x",
            "Description": ""
```

```
        },
        {
            "Layers": [
                {
                    "CodeSize": 41784542,
                    "Arn": "arn:aws:lambda:us-
west-2:420165488524:layer:AWSLambda-Python37-SciPy1x:2"
                },
                {
                    "CodeSize": 4121,
                    "Arn": "arn:aws:lambda:us-
west-2:123456789012:layer:pythonLayer:1"
                }
            ],
            "TracingConfig": {
                "Mode": "PassThrough"
            },
            "Version": "$LATEST",
            "CodeSha256": "ZQukCqxtkqFgyF2cU41Avj99TKQ/hNihPtDtRcc08mI=",
            "FunctionName": "my-python-function",
            "VpcConfig": {
                "SubnetIds": [],
                "VpcId": "",
                "SecurityGroupIds": []
            },
            "MemorySize": 128,
            "RevisionId": "80b4eabc-acf7-4ea8-919a-e874c213707d",
            "CodeSize": 299,
            "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-
python-function",
            "Handler": "lambda_function.lambda_handler",
            "Role": "arn:aws:iam::123456789012:role/service-role/my-python-
function-role-z5g7dr6n",
            "Timeout": 3,
            "LastModified": "2019-10-01T19:40:41.643+0000",
            "Runtime": "python3.7",
            "Description": ""
        }
    ]
}
```

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte ListFunctionsem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// ListFunctions lists up to maxItems functions for the account. This function
 uses a
// lambda.ListFunctionsPaginator to paginate the results.
func (wrapper FunctionWrapper) ListFunctions(maxItems int)
 []types.FunctionConfiguration {
 var functions []types.FunctionConfiguration
 paginator := lambda.NewListFunctionsPaginator(wrapper.LambdaClient,
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
 })
 for paginator.HasMorePages() && len(functions) < maxItems {
  pageOutput, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Panicf("Couldn't list functions for your account. Here's why: %v\n", err)
  }
  functions = append(functions, pageOutput.Functions...)
 }
 return functions
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listFunctions = () => {
  const client = new LambdaClient({});
  const command = new ListFunctionsCommand({});

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function listFunctions($maxItems = 50, $marker = null)
    {
        if (is_null($marker)) {
            return $this->lambdaClient->listFunctions([
```

```
                'MaxItems' => $maxItems,
            ]);
        }

        return $this->lambdaClient->listFunctions([
            'Marker' => $marker,
            'MaxItems' => $maxItems,
        ]);
    }
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def list_functions(self):
        """
        Lists the Lambda functions for the current account.
        """
        try:
            func_paginator = self.lambda_client.get_paginator("list_functions")
            for func_page in func_paginator.paginate():
                for func in func_page["Functions"]:
                    print(func["FunctionName"])
                    desc = func.get("Description")
                    if desc:
                        print(f"\t{desc}")
                    print(f"\t{func['Runtime']}: {func['Handler']}")
```

```
        except ClientError as err:
            logger.error(
                "Couldn't list functions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListFunctionsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Lists the Lambda functions for the current account.
  def list_functions
    functions = []
    @lambda_client.list_functions.each do |response|
      response["functions"].each do |function|
        functions.append(function["function_name"])
      end
    end
    functions
```

```
 rescue Aws::Lambda::Errors::ServiceException => e
   @logger.error("There was an error executing #{function_name}:\n
#{e.message}")
 end
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /** List all Lambda functions in the current Region. */
   pub async fn list_functions(&self) -> Result<ListFunctionsOutput,
anyhow::Error> {
       info!("Listing lambda functions");
       self.lambda_client
           .list_functions()
           .send()
           .await
           .map_err(anyhow::Error::from)
   }
```

- Para obter detalhes da API, consulte a ListFunctionsreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result =  lo_lmd->listfunctions( ).       " oo_result is returned for
testing purposes. "
       DATA(lt_functions) = oo_result->get_functions( ).
       MESSAGE 'Retrieved list of Lambda functions.' TYPE 'I'.
     CATCH /aws1/cx_lmdinvparamvalueex.
       MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
     CATCH /aws1/cx_lmdserviceexception.
       MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
     CATCH /aws1/cx_lmdtoomanyrequestsex.
       MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListFunctionsreferência da API AWS SDK for SAP ABAP.

Excluir um código de função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar um código de função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update an existing Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to update.</
param>
    /// <param name="bucketName">The bucket where the zip file containing
    /// the Lambda function code is stored.</param>
    /// <param name="key">The key name of the source code file.</param>
    /// <returns>Async Task.</returns>
    public async Task UpdateFunctionCodeAsync(
        string functionName,
        string bucketName,
        string key)
    {
        var functionCodeRequest = new UpdateFunctionCodeRequest
        {
            FunctionName = functionName,
            Publish = true,
            S3Bucket = bucketName,
            S3Key = key,
        };

        var response = await
 _lambdaService.UpdateFunctionCodeAsync(functionCodeRequest);
        Console.WriteLine($"The Function was last modified at
 {response.LastModified}.");
    }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
        request.SetPublish(true);
```

```
        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
 client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." <<
 std::endl;
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Atualizar o código de uma função do Lambda

O exemplo de `update-function-code` a seguir substitui o código da versão não publicada ($LATEST) da função `my-function` pelo conteúdo do arquivo zip especificado.

```
aws lambda update-function-code \
    --function-name  my-function \
    --zip-file fileb://my-function.zip
```

Saída:

```
{
    "FunctionName": "my-function",
    "LastModified": "2019-09-26T20:28:40.438+0000",
    "RevisionId": "e52502d4-9320-4688-9cd6-152a6ab7490d",
    "MemorySize": 256,
    "Version": "$LATEST",
    "Role": "arn:aws:iam::123456789012:role/service-role/my-function-role-
uy3l9qyq",
```

```
    "Timeout": 3,
    "Runtime": "nodejs10.x",
    "TracingConfig": {
        "Mode": "PassThrough"
    },
    "CodeSha256": "5tT2qgzYUHaqwR716pZ2dpkn/0J1FrzJmlKidWoaCgk=",
    "Description": "",
    "VpcConfig": {
        "SubnetIds": [],
        "VpcId": "",
        "SecurityGroupIds": []
    },
    "CodeSize": 304,
    "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-function",
    "Handler": "index.handler"
}
```

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte UpdateFunctionCodeem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}
```

```
// UpdateFunctionCode updates the code for the Lambda function specified by
 functionName.
// The existing code for the Lambda function is entirely replaced by the code in
 the
// zipPackage buffer. After the update action is called, a
 lambda.FunctionUpdatedV2Waiter
// is used to wait until the update is successful.
func (wrapper FunctionWrapper) UpdateFunctionCode(functionName string, zipPackage
 *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.UpdateFunctionCode(context.TODO(),
 &lambda.UpdateFunctionCodeInput{
  FunctionName: aws.String(functionName), ZipFile: zipPackage.Bytes(),
 })
 if err != nil {
  log.Panicf("Couldn't update code for function %v. Here's why: %v\n",
 functionName, err)
 } else {
  waiter := lambda.NewFunctionUpdatedV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(),
 &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const updateFunctionCode = async (funcName, newFunc) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${newFunc}.zip`);
  const command = new UpdateFunctionCodeCommand({
    ZipFile: code,
    FunctionName: funcName,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function updateFunctionCode($functionName, $s3Bucket, $s3Key)
```

```
    {
        return $this->lambdaClient->updateFunctionCode([
            'FunctionName' => $functionName,
            'S3Bucket' => $s3Bucket,
            'S3Key' => $s3Key,
        ]);
    }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def update_function_code(self, function_name, deployment_package):
        """
        Updates the code for a Lambda function by submitting a .zip archive that
 contains
        the code for the function.

        :param function_name: The name of the function to update.
        :param deployment_package: The function code to update, packaged as bytes
 in
                                   .zip format.
        :return: Data about the update, including the status.
        """
        try:
```

```
            response = self.lambda_client.update_function_code(
                FunctionName=function_name, ZipFile=deployment_package
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a UpdateFunctionCodeReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Updates the code for a Lambda function by submitting a .zip archive that
 contains
  # the code for the function.
```

```
 # @param function_name: The name of the function to update.
 # @param deployment_package: The function code to update, packaged as bytes in
 #                            .zip format.
 # @return: Data about the update, including the status.
 def update_function_code(function_name, deployment_package)
   @lambda_client.update_function_code(
     function_name: function_name,
     zip_file: deployment_package
   )
   @lambda_client.wait_until(:function_updated_v2, { function_name:
function_name}) do |w|
     w.max_attempts = 5
     w.delay = 5
   end
 rescue Aws::Lambda::Errors::ServiceException => e
   @logger.error("There was an error updating function code for:
#{function_name}:\n #{e.message}")
   nil
 rescue Aws::Waiters::Errors::WaiterFailed => e
   @logger.error("Failed waiting for #{function_name} to update:\n
#{e.message}")
 end
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /** Given a Path to a zip file, update the function's code and wait for the
update to finish. */
   pub async fn update_function_code(
```

```
        &self,
        zip_file: PathBuf,
        key: String,
    ) -> Result<UpdateFunctionCodeOutput, anyhow::Error> {
        let function_code = self.prepare_function(zip_file, Some(key)).await?;

        info!("Updating code for {}", self.lambda_name);
        let update = self
            .lambda_client
            .update_function_code()
            .function_name(self.lambda_name.clone())
            .s3_bucket(self.bucket.clone())
            .s3_key(function_code.s3_key().unwrap().to_string())
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(update)
    }

    /**
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --
output-format Zip`.
     */
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));

        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
```

```
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
            .s3_key(key)
            .build())
    }
```

- Para obter detalhes da API, consulte a UpdateFunctionCodereferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_lmd->updatefunctioncode(     " oo_result is returned for
testing purposes. "
              iv_functionname = iv_function_name
              iv_zipfile = io_zip_file
          ).

        MESSAGE 'Lambda function code updated.' TYPE 'I'.
      CATCH /aws1/cx_lmdcodesigningcfgno00.
        MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdcodestorageexcdex.
        MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
      CATCH /aws1/cx_lmdcodeverification00.
        MESSAGE 'Code signature failed one or more validation checks for
signature mismatch or expiration.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvalidcodesigex.
        MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvparamvalueex.
```

```
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.'
TYPE 'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateFunctionCodereferência da API AWS SDK for SAP ABAP.

Atualizar uma configuração de função do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar uma configuração de função do Lambda.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de funções

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the code of a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the function to update.</param>
```

```
    /// <param name="functionHandler">The code that performs the function's
actions.</param>
    /// <param name="environmentVariables">A dictionary of environment
variables.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateFunctionConfigurationAsync(
        string functionName,
        string functionHandler,
        Dictionary<string, string> environmentVariables)
    {
        var request = new UpdateFunctionConfigurationRequest
        {
            Handler = functionHandler,
            FunctionName = functionName,
            Environment = new Amazon.Lambda.Model.Environment { Variables =
environmentVariables },
        };

        var response = await
_lambdaService.UpdateFunctionConfigurationAsync(request);

        Console.WriteLine(response.LastModified);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);

        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
        }

        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Modificar a configuração de uma função

O exemplo de `update-function-configuration` a seguir modifica o tamanho da memória para 256 MB para a versão não publicada ($LATEST) da função `my-function`.

```
aws lambda update-function-configuration \
    --function-name  my-function \
    --memory-size 256
```

Saída:

```
{
    "FunctionName": "my-function",
    "LastModified": "2019-09-26T20:28:40.438+0000",
    "RevisionId": "e52502d4-9320-4688-9cd6-152a6ab7490d",
    "MemorySize": 256,
    "Version": "$LATEST",
    "Role": "arn:aws:iam::123456789012:role/service-role/my-function-role-
uy3l9qyq",
    "Timeout": 3,
    "Runtime": "nodejs10.x",
    "TracingConfig": {
        "Mode": "PassThrough"
    },
    "CodeSha256": "5tT2qgzYUHaqwR716pZ2dpkn/0J1FrzJmlKidWoaCgk=",
    "Description": "",
    "VpcConfig": {
        "SubnetIds": [],
        "VpcId": "",
        "SecurityGroupIds": []
    },
    "CodeSize": 304,
    "FunctionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-function",
    "Handler": "index.handler"
}
```

Para obter mais informações, consulte Configurar opções da função do AWS Lambda no Guia do desenvolvedor do AWS Lambda.

- Para obter detalhes da API, consulte UpdateFunctionConfigurationem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// UpdateFunctionConfiguration updates a map of environment variables configured
 for
// the Lambda function specified by functionName.
func (wrapper FunctionWrapper) UpdateFunctionConfiguration(functionName string,
 envVars map[string]string) {
 _, err := wrapper.LambdaClient.UpdateFunctionConfiguration(context.TODO(),
 &lambda.UpdateFunctionConfigurationInput{
  FunctionName: aws.String(functionName),
  Environment:  &types.Environment{Variables: envVars},
 })
 if err != nil {
  log.Panicf("Couldn't update configuration for %v. Here's why: %v",
 functionName, err)
 }
}
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const updateFunctionConfiguration = (funcName) => {
  const client = new LambdaClient({});
  const config = readFileSync(`${dirname}../functions/config.json`).toString();
  const command = new UpdateFunctionConfigurationCommand({
    ...JSON.parse(config),
    FunctionName: funcName,
  });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte UpdateFunctionConfiguration a Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function updateFunctionConfiguration($functionName, $handler,
 $environment = '')
    {
        return $this->lambdaClient->updateFunctionConfiguration([
            'FunctionName' => $functionName,
            'Handler' => "$handler.lambda_handler",
```

```
            'Environment' => $environment,
        ]);
    }
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def update_function_configuration(self, function_name, env_vars):
        """
        Updates the environment variables for a Lambda function.

        :param function_name: The name of the function to update.
        :param env_vars: A dict of environment variables to update.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_configuration(
                FunctionName=function_name, Environment={"Variables": env_vars}
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function configuration %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Updates the environment variables for a Lambda function.
  # @param function_name: The name of the function to update.
  # @param log_level: The log level of the function.
  # @return: Data about the update, including the status.
  def update_function_configuration(function_name, log_level)
    @lambda_client.update_function_configuration({
                                                   function_name: function_name,
                                                   environment: {
                                                     variables: {
                                                       "LOG_LEVEL" => log_level
                                                     }
```

```
                                                    }
                                                  })
   @lambda_client.wait_until(:function_updated_v2, { function_name:
function_name}) do |w|
     w.max_attempts = 5
     w.delay = 5
   end
 rescue Aws::Lambda::Errors::ServiceException => e
   @logger.error("There was an error updating configurations for
#{function_name}:\n #{e.message}")
 rescue Aws::Waiters::Errors::WaiterFailed => e
   @logger.error("Failed waiting for #{function_name} to activate:\n
#{e.message}")
 end
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Update the environment for a function. */
    pub async fn update_function_configuration(
        &self,
        environment: Environment,
    ) -> Result<UpdateFunctionConfigurationOutput, anyhow::Error> {
        info!(
            ?environment,
            "Updating environment for {}", self.lambda_name
        );
        let updated = self
            .lambda_client
            .update_function_configuration()
```

```
            .function_name(self.lambda_name.clone())
            .environment(environment)
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(updated)
    }
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_lmd->updatefunctionconfiguration(     " oo_result is
returned for testing purposes. "
             iv_functionname = iv_function_name
             iv_runtime = iv_runtime
             iv_description  = 'Updated Lambda function'
             iv_memorysize  = iv_memory_size
         ).

       MESSAGE 'Lambda function configuration/settings updated.' TYPE 'I'.
     CATCH /aws1/cx_lmdcodesigningcfgno00.
       MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
     CATCH /aws1/cx_lmdcodeverification00.
       MESSAGE 'Code signature failed one or more validation checks for
signature mismatch or expiration.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvalidcodesigex.
```

```
        MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.'
TYPE 'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationreferência da API AWS SDK for SAP ABAP.

Cenários do Lambda usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Lambda com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Começar a criar e invocar funções do Lambda usando um AWS SDK

Começar a criar e invocar funções do Lambda usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie métodos que executem ações do Lambda.

```
namespace LambdaActions;

using Amazon.Lambda;
using Amazon.Lambda.Model;

/// <summary>
/// A class that implements AWS Lambda methods.
/// </summary>
public class LambdaWrapper
{
    private readonly IAmazonLambda _lambdaService;

    /// <summary>
    /// Constructor for the LambdaWrapper class.
    /// </summary>
    /// <param name="lambdaService">An initialized Lambda service client.</param>
    public LambdaWrapper(IAmazonLambda lambdaService)
    {
        _lambdaService = lambdaService;
    }

    /// <summary>
    /// Creates a new Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the function.</param>
    /// <param name="s3Bucket">The Amazon Simple Storage Service (Amazon S3)
    /// bucket where the zip file containing the code is located.</param>
    /// <param name="s3Key">The Amazon S3 key of the zip file.</param>
    /// <param name="role">The Amazon Resource Name (ARN) of a role with the
```

```
    /// appropriate Lambda permissions.</param>
    /// <param name="handler">The name of the handler function.</param>
    /// <returns>The Amazon Resource Name (ARN) of the newly created
    /// Lambda function.</returns>
    public async Task<string> CreateLambdaFunctionAsync(
        string functionName,
        string s3Bucket,
        string s3Key,
        string role,
        string handler)
    {
        // Defines the location for the function code.
        // S3Bucket - The S3 bucket where the file containing
        //            the source code is stored.
        // S3Key    - The name of the file containing the code.
        var functionCode = new FunctionCode
        {
            S3Bucket = s3Bucket,
            S3Key = s3Key,
        };

        var createFunctionRequest = new CreateFunctionRequest
        {
            FunctionName = functionName,
            Description = "Created by the Lambda .NET API",
            Code = functionCode,
            Handler = handler,
            Runtime = Runtime.Dotnet6,
            Role = role,
        };

        var reponse = await
 _lambdaService.CreateFunctionAsync(createFunctionRequest);
        return reponse.FunctionArn;
    }


    /// <summary>
    /// Delete an AWS Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// delete.</param>
    /// <returns>A Boolean value that indicates the success of the action.</
returns>
```

```
    public async Task<bool> DeleteFunctionAsync(string functionName)
    {
        var request = new DeleteFunctionRequest
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.DeleteFunctionAsync(request);

        // A return value of NoContent means that the request was processed.
        // In this case, the function was deleted, and the return value
        // is intentionally blank.
        return response.HttpStatusCode == System.Net.HttpStatusCode.NoContent;
    }


    /// <summary>
    /// Gets information about a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function for
    /// which to retrieve information.</param>
    /// <returns>Async Task.</returns>
    public async Task<FunctionConfiguration> GetFunctionAsync(string
functionName)
    {
        var functionRequest = new GetFunctionRequest
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.GetFunctionAsync(functionRequest);
        return response.Configuration;
    }


    /// <summary>
    /// Invoke a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// invoke.</param
    /// <param name="parameters">The parameter values that will be passed to the
function.</param>
    /// <returns>A System Threading Task.</returns>
    public async Task<string> InvokeFunctionAsync(
```

```
        string functionName,
        string parameters)
    {
        var payload = parameters;
        var request = new InvokeRequest
        {
            FunctionName = functionName,
            Payload = payload,
        };

        var response = await _lambdaService.InvokeAsync(request);
        MemoryStream stream = response.Payload;
        string returnValue =
 System.Text.Encoding.UTF8.GetString(stream.ToArray());
        return returnValue;
    }


    /// <summary>
    /// Get a list of Lambda functions.
    /// </summary>
    /// <returns>A list of FunctionConfiguration objects.</returns>
    public async Task<List<FunctionConfiguration>> ListFunctionsAsync()
    {
        var functionList = new List<FunctionConfiguration>();

        var functionPaginator =
            _lambdaService.Paginators.ListFunctions(new ListFunctionsRequest());
        await foreach (var function in functionPaginator.Functions)
        {
            functionList.Add(function);
        }

        return functionList;
    }


    /// <summary>
    /// Update an existing Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to update.</
param>
    /// <param name="bucketName">The bucket where the zip file containing
    /// the Lambda function code is stored.</param>
```

```
    /// <param name="key">The key name of the source code file.</param>
    /// <returns>Async Task.</returns>
    public async Task UpdateFunctionCodeAsync(
        string functionName,
        string bucketName,
        string key)
    {
        var functionCodeRequest = new UpdateFunctionCodeRequest
        {
            FunctionName = functionName,
            Publish = true,
            S3Bucket = bucketName,
            S3Key = key,
        };

        var response = await
_lambdaService.UpdateFunctionCodeAsync(functionCodeRequest);
        Console.WriteLine($"The Function was last modified at
{response.LastModified}.");
    }


    /// <summary>
    /// Update the code of a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the function to update.</param>
    /// <param name="functionHandler">The code that performs the function's
actions.</param>
    /// <param name="environmentVariables">A dictionary of environment
variables.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateFunctionConfigurationAsync(
        string functionName,
        string functionHandler,
        Dictionary<string, string> environmentVariables)
    {
        var request = new UpdateFunctionConfigurationRequest
        {
            Handler = functionHandler,
            FunctionName = functionName,
            Environment = new Amazon.Lambda.Model.Environment { Variables =
environmentVariables },
        };
```

```
        var response = await
 _lambdaService.UpdateFunctionConfigurationAsync(request);

        Console.WriteLine(response.LastModified);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


}
```

Crie uma função que execute o cenário.

```
global using System.Threading.Tasks;
global using Amazon.IdentityManagement;
global using Amazon.Lambda;
global using LambdaActions;
global using LambdaScenarioCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;


using Amazon.Lambda.Model;
using Microsoft.Extensions.Configuration;

namespace LambdaBasics;

public class LambdaBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
```

```
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonLambda>()
            .AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<LambdaWrapper>()
            .AddTransient<LambdaRoleWrapper>()
            .AddTransient<UIWrapper>()
        )
        .Build();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
            true) // Optionally load local settings.
        .Build();


        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<LambdaBasics>();

        var lambdaWrapper = host.Services.GetRequiredService<LambdaWrapper>();
        var lambdaRoleWrapper =
host.Services.GetRequiredService<LambdaRoleWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        string functionName = configuration["FunctionName"]!;
        string roleName = configuration["RoleName"]!;
        string policyDocument = "{" +
            " \"Version\": \"2012-10-17\"," +
            " \"Statement\": [ " +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Principal\": {" +
            "            \"Service\": \"lambda.amazonaws.com\" " +
            "    }," +
            "        \"Action\": \"sts:AssumeRole\" " +
            "    }" +
            "]" +
        "}";
```

```
        var incrementHandler = configuration["IncrementHandler"];
        var calculatorHandler = configuration["CalculatorHandler"];
        var bucketName = configuration["BucketName"];
        var incrementKey = configuration["IncrementKey"];
        var calculatorKey = configuration["CalculatorKey"];
        var policyArn = configuration["PolicyArn"];

        uiWrapper.DisplayLambdaBasicsOverview();

        // Create the policy to use with the AWS Lambda functions and then attach
the
        // policy to a new role.
        var roleArn = await lambdaRoleWrapper.CreateLambdaRoleAsync(roleName,
policyDocument);

        Console.WriteLine("Waiting for role to become active.");
        uiWrapper.WaitABit(15, "Wait until the role is active before trying to
use it.");

        // Attach the appropriate AWS Identity and Access Management (IAM) role
policy to the new role.
        var success = await
lambdaRoleWrapper.AttachLambdaRolePolicyAsync(policyArn, roleName);
        uiWrapper.WaitABit(10, "Allow time for the IAM policy to be attached to
the role.");

        // Create the Lambda function using a zip file stored in an Amazon Simple
Storage Service
        // (Amazon S3) bucket.
        uiWrapper.DisplayTitle("Create Lambda Function");
        Console.WriteLine($"Creating the AWS Lambda function: {functionName}.");
        var lambdaArn = await lambdaWrapper.CreateLambdaFunctionAsync(
            functionName,
            bucketName,
            incrementKey,
            roleArn,
            incrementHandler);

        Console.WriteLine("Waiting for the new function to be available.");
        Console.WriteLine($"The AWS Lambda ARN is {lambdaArn}");

        // Get the Lambda function.
        Console.WriteLine($"Getting the {functionName} AWS Lambda function.");
        FunctionConfiguration config;
```

```
        do
        {
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.State != State.Active);

        Console.WriteLine($"\nThe function, {functionName} has been created.");
        Console.WriteLine($"The runtime of this Lambda function is
{config.Runtime}.");

        uiWrapper.PressEnter();

        // List the Lambda functions.
        uiWrapper.DisplayTitle("Listing all Lambda functions.");
        var functions = await lambdaWrapper.ListFunctionsAsync();
        DisplayFunctionList(functions);

        uiWrapper.DisplayTitle("Invoke increment function");
        Console.WriteLine("Now that it has been created, invoke the Lambda
increment function.");
        string? value;
        do
        {
            Console.Write("Enter a value to increment: ");
            value = Console.ReadLine();
        }
        while (string.IsNullOrEmpty(value));

        string functionParameters = "{" +
            "\"action\": \"increment\", " +
            "\"x\": \"" + value + "\"" +
        "}";
        var answer = await lambdaWrapper.InvokeFunctionAsync(functionName,
functionParameters);
        Console.WriteLine($"{value} + 1 = {answer}.");

        uiWrapper.DisplayTitle("Update function");
        Console.WriteLine("Now update the Lambda function code.");
        await lambdaWrapper.UpdateFunctionCodeAsync(functionName, bucketName,
calculatorKey);

        do
        {
```

```
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.LastUpdateStatus == LastUpdateStatus.InProgress);

        await lambdaWrapper.UpdateFunctionConfigurationAsync(
            functionName,
            calculatorHandler,
            new Dictionary<string, string> { { "LOG_LEVEL", "DEBUG" } });

        do
        {
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.LastUpdateStatus == LastUpdateStatus.InProgress);

        uiWrapper.DisplayTitle("Call updated function");
        Console.WriteLine("Now call the updated function...");

        bool done = false;

        do
        {
            string? opSelected;

            Console.WriteLine("Select the operation to perform:");
            Console.WriteLine("\t1. add");
            Console.WriteLine("\t2. subtract");
            Console.WriteLine("\t3. multiply");
            Console.WriteLine("\t4. divide");
            Console.WriteLine("\tOr enter \"q\" to quit.");
            Console.WriteLine("Enter the number (1, 2, 3, 4, or q) of the
operation you want to perform: ");
            do
            {
                Console.Write("Your choice? ");
                opSelected = Console.ReadLine();
            }
            while (opSelected == string.Empty);

            var operation = (opSelected) switch
            {
                "1" => "add",
```

```
                "2" => "subtract",
                "3" => "multiply",
                "4" => "divide",
                "q" => "quit",
                _ => "add",
            };

            if (operation == "quit")
            {
                done = true;
            }
            else
            {
                // Get two numbers and an action from the user.
                value = string.Empty;
                do
                {
                    Console.Write("Enter the first value: ");
                    value = Console.ReadLine();
                }
                while (value == string.Empty);

                string? value2;
                do
                {
                    Console.Write("Enter a second value: ");
                    value2 = Console.ReadLine();
                }
                while (value2 == string.Empty);

                functionParameters = "{" +
                    "\"action\": \"" + operation + "\", " +
                    "\"x\": \"" + value + "\"," +
                    "\"y\": \"" + value2 + "\"" +
                "}";

                answer = await lambdaWrapper.InvokeFunctionAsync(functionName,
functionParameters);
                Console.WriteLine($"The answer when we {operation} the two
numbers is: {answer}.");
            }

            uiWrapper.PressEnter();
        } while (!done);
```

```
        // Delete the function created earlier.

        uiWrapper.DisplayTitle("Clean up resources");
        // Detach the IAM policy from the IAM role.
        Console.WriteLine("First detach the IAM policy from the role.");
        success = await lambdaRoleWrapper.DetachLambdaRolePolicyAsync(policyArn,
roleName);
        uiWrapper.WaitABit(15, "Let's wait for the policy to be fully detached
from the role.");

        Console.WriteLine("Delete the AWS Lambda function.");
        success = await lambdaWrapper.DeleteFunctionAsync(functionName);
        if (success)
        {
            Console.WriteLine($"The {functionName} function was deleted.");
        }
        else
        {
            Console.WriteLine($"Could not remove the function {functionName}");
        }

        // Now delete the IAM role created for use with the functions
        // created by the application.
        Console.WriteLine("Now we can delete the role that we created.");
        success = await lambdaRoleWrapper.DeleteLambdaRoleAsync(roleName);
        if (success)
        {
            Console.WriteLine("The role has been successfully removed.");
        }
        else
        {
            Console.WriteLine("Couldn't delete the role.");
        }

        Console.WriteLine("The Lambda Scenario is now complete.");
        uiWrapper.PressEnter();

        // Displays a formatted list of existing functions returned by the
        // LambdaMethods.ListFunctions.
        void DisplayFunctionList(List<FunctionConfiguration> functions)
        {
            functions.ForEach(functionConfig =>
            {
```

```
 Console.WriteLine($"{functionConfig.FunctionName}\t{functionConfig.Description}");
            });
        }
    }
}


namespace LambdaActions;

using Amazon.IdentityManagement;
using Amazon.IdentityManagement.Model;

public class LambdaRoleWrapper
{
    private readonly IAmazonIdentityManagementService _lambdaRoleService;

    public LambdaRoleWrapper(IAmazonIdentityManagementService lambdaRoleService)
    {
        _lambdaRoleService = lambdaRoleService;
    }

    /// <summary>
    /// Attach an AWS Identity and Access Management (IAM) role policy to the
    /// IAM role to be assumed by the AWS Lambda functions created for the
 scenario.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM
 policy.</param>
    /// <param name="roleName">The name of the IAM role to attach the IAM policy
 to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachLambdaRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _lambdaRoleService.AttachRolePolicyAsync(new
 AttachRolePolicyRequest { PolicyArn = policyArn, RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to create.</param>
```

```
    /// <param name="policyDocument">The policy document for the new IAM role.</
param>
    /// <returns>A string representing the ARN for newly created role.</returns>
    public async Task<string> CreateLambdaRoleAsync(string roleName, string
 policyDocument)
    {
        var request = new CreateRoleRequest
        {
            AssumeRolePolicyDocument = policyDocument,
            RoleName = roleName,
        };

        var response = await _lambdaRoleService.CreateRoleAsync(request);
        return response.Role.Arn;
    }

    /// <summary>
    /// Deletes an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>A Boolean value indicating the success of the operation.</
returns>
    public async Task<bool> DeleteLambdaRoleAsync(string roleName)
    {
        var request = new DeleteRoleRequest
        {
            RoleName = roleName,
        };

        var response = await _lambdaRoleService.DeleteRoleAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    public async Task<bool> DetachLambdaRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _lambdaRoleService.DetachRolePolicyAsync(new
 DetachRolePolicyRequest { PolicyArn = policyArn, RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
}


namespace LambdaScenarioCommon;
```

```
public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the AWS Lambda Basics scenario.
    /// </summary>
    public void DisplayLambdaBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to AWS Lambda Basics");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates an AWS Identity and Access Management
 (IAM) role that will be assumed by the functions we create.");
        Console.WriteLine("\t2. Attaches an IAM role policy that has Lambda
 permissions.");
        Console.WriteLine("\t3. Creates a Lambda function that increments the
 value passed to it.");
        Console.WriteLine("\t4. Calls the increment function and passes a
 value.");
        Console.WriteLine("\t5. Updates the code so that the function is a simple
 calculator.");
        Console.WriteLine("\t6. Calls the calculator function with the values
 entered.");
        Console.WriteLine("\t7. Deletes the Lambda function.");
        Console.WriteLine("\t7. Detaches the IAM role policy.");
        Console.WriteLine("\t8. Deletes the IAM role.");
        PressEnter();
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
```

```
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

Defina um manipulador do Lambda que aumente um número.

```
using Amazon.Lambda.Core;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace LambdaIncrement;

public class Function
{

    /// <summary>
    /// A simple function increments the integer parameter.
    /// </summary>
    /// <param name="input">A JSON string containing an action, which must be
    /// "increment" and a string representing the value to increment.</param>
    /// <param name="context">The context object passed by Lambda containing
    /// information about invocation, function, and execution environment.</
param>
    /// <returns>A string representing the incremented value of the parameter.</
returns>
    public int FunctionHandler(Dictionary<string, string> input, ILambdaContext
 context)
    {
        if (input["action"] == "increment")
        {
            int inputValue = Convert.ToInt32(input["x"]);
            return inputValue + 1;
        }
        else
        {
            return 0;
        }
    }
}
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
using Amazon.Lambda.Core;
```

```
// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace LambdaCalculator;

public class Function
{

    /// <summary>
    /// A simple function that takes two number in string format and performs
    /// the requested arithmetic function.
    /// </summary>
    /// <param name="input">JSON data containing an action, and x and y values.
    /// Valid actions include: add, subtract, multiply, and divide.</param>
    /// <param name="context">The context object passed by Lambda containing
    /// information about invocation, function, and execution environment.</
param>
    /// <returns>A string representing the results of the calculation.</returns>
    public int FunctionHandler(Dictionary<string, string> input, ILambdaContext
 context)
    {
        var action = input["action"];
        int x = Convert.ToInt32(input["x"]);
        int y = Convert.ToInt32(input["y"]);
        int result;
        switch (action)
        {
            case "add":
                result = x + y;
                break;
            case "subtract":
                result = x - y;
                break;
            case "multiply":
                result = x * y;
                break;
            case "divide":
                if (y == 0)
                {
                    Console.Error.WriteLine("Divide by zero error.");
                    result = 0;
                }
```

```
                else
                    result = x / y;
                break;
            default:
                Console.Error.WriteLine($"{action} is not a valid operation.");
                result = 0;
                break;
        }
        return result;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Get started with functions scenario.
/*!
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
```

```
 */
bool AwsDoc::Lambda::getStartedWithFunctionsScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::Lambda::LambdaClient client(clientConfig);

    // 1. Create an AWS Identity and Access Management (IAM) role for Lambda
 function.
    Aws::String roleArn;
    if (!getIamRoleArn(roleArn, clientConfig)) {
        return false;
    }

    // 2. Create a Lambda function.
    int seconds = 0;
    do {
        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same
 architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_8);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
```

```
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
 buffer.str().c_str(),
                                                buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome =
 client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " <<
 seconds
                      << " seconds elapsed." << std::endl;
            break;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::INVALID_PARAMETER_VALUE &&
                 outcome.GetError().GetMessage().find("role") >= 0) {
            if ((seconds % 5) == 0) { // Log status every 10 seconds.
                std::cout
                        << "Waiting for the IAM role to become available as a
 CreateFunction parameter. "
                        << seconds
                        << " seconds elapsed." << std::endl;

                std::cout << outcome.GetError().GetMessage() << std::endl;
            }
        }
```

```
        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (60 > seconds);

    std::cout << "The current Lambda function increments 1 by an input." <<
std::endl;

    // 3.  Invoke the Lambda function.
    {
        int increment = askQuestionForInt("Enter an increment integer: ");

        Aws::Lambda::Model::InvokeResult invokeResult;
        Aws::Utils::Json::JsonValue jsonPayload;
        jsonPayload.WithString("action", "increment");
        jsonPayload.WithInteger("number", increment);
        if (invokeLambdaFunction(jsonPayload, Aws::Lambda::Model::LogType::Tail,
                                 invokeResult, client)) {
            Aws::Utils::Json::JsonValue jsonValue(invokeResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                {
                    std::cout << INCREMENT_RESULT_PREFIX
                              << iter->second.AsInteger() << std::endl;
                }
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
Aws::Utils::HashingUtils::Base64Decode(
                        invokeResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() <<
std::endl;
            }
        }
```

```
    }

    std::cout
            << "The Lambda function will now be updated with new code. Press
 return to continue, ";
    Aws::String answer;
    std::getline(std::cin, answer);

    // 4.  Update the Lambda function code.
    {
        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
        request.SetPublish(true);

        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
 client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." <<
 std::endl;
        }
```

```
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "This function uses an environment variable to control the logging
level."
            << std::endl;
    std::cout
            << "UpdateFunctionConfiguration will be used to set the LOG_LEVEL to
DEBUG."
            << std::endl;
    seconds = 0;

    // 5.  Update the Lambda function configuration.
    do {
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);

        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
        }

            // RESOURCE_IN_USE: function code update not completed.
        else if (outcome.GetError().GetErrorType() !=
                 Aws::Lambda::LambdaErrors::RESOURCE_IN_USE) {
            if ((seconds % 10) == 0) { // Log status every 10 seconds.
                std::cout << "Lambda function update in progress . After " <<
seconds
                          << " seconds elapsed." << std::endl;
```

```
            }
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }

    } while (0 < seconds);

    if (0 > seconds) {
        std::cerr << "Function failed to become active." << std::endl;
    }
    else {
        std::cout << "Updated function active after " << seconds << " seconds."
                  << std::endl;
    }

    std::cout
            << "\nThe new code applies an arithmetic operator to two variables, x
 an y."
            << std::endl;
    std::vector<Aws::String> operators = {"plus", "minus", "times", "divided-
by"};
    for (size_t i = 0; i < operators.size(); ++i) {
        std::cout << "   " << i + 1 << " " << operators[i] << std::endl;
    }

    // 6.  Invoke the updated Lambda function.
    do {
        int operatorIndex = askQuestionForIntRange("Select an operator index 1 -
 4 ", 1,
                                                   4);
        int x = askQuestionForInt("Enter an integer for the x value ");
        int y = askQuestionForInt("Enter an integer for the y value ");

        Aws::Utils::Json::JsonValue calculateJsonPayload;
        calculateJsonPayload.WithString("action", operators[operatorIndex - 1]);
        calculateJsonPayload.WithInteger("x", x);
        calculateJsonPayload.WithInteger("y", y);
        Aws::Lambda::Model::InvokeResult calculatedResult;
        if (invokeLambdaFunction(calculateJsonPayload,
                                 Aws::Lambda::Model::LogType::Tail,
                                 calculatedResult, client)) {
```

```
            Aws::Utils::Json::JsonValue jsonValue(calculatedResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                std::cout << ARITHMETIC_RESUlT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsInteger() <<
std::endl;
            }
            else if (iter != values.end() && iter->second.IsFloatingPointType())
{
                std::cout << ARITHMETIC_RESUlT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsDouble() << std::endl;
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
Aws::Utils::HashingUtils::Base64Decode(
                        calculatedResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() <<
std::endl;
            }
        }

        answer = askQuestion("Would you like to try another operation? (y/n) ");
    } while (answer == "y");

    std::cout
            << "A list of the lambda functions will be retrieved. Press return to
continue, ";
    std::getline(std::cin, answer);

    // 7.  List the Lambda functions.

    std::vector<Aws::String> functions;
    Aws::String marker;

    do {
        Aws::Lambda::Model::ListFunctionsRequest request;
        if (!marker.empty()) {
            request.SetMarker(marker);
```

```
        }

        Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
            std::cout << result.GetFunctions().size()
                      << " lambda functions were retrieved." << std::endl;

            for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
                functions.push_back(functionConfiguration.GetFunctionName());
                std::cout << functions.size() << "  "
                          << functionConfiguration.GetDescription() << std::endl;
                std::cout << "   "
                          <<
Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                  functionConfiguration.GetRuntime()) << ": "
                          << functionConfiguration.GetHandler()
                          << std::endl;
            }
            marker = result.GetNextMarker();
        }
        else {
            std::cerr << "Error with Lambda::ListFunctions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());

    // 8.  Get a Lambda function.
    if (!functions.empty()) {
        std::stringstream question;
        question << "Choose a function to retrieve between 1 and " <<
functions.size()
                 << " ";
        int functionIndex = askQuestionForIntRange(question.str(), 1,

static_cast<int>(functions.size()));

        Aws::String functionName = functions[functionIndex - 1];
```

```
        Aws::Lambda::Model::GetFunctionRequest request;
        request.SetFunctionName(functionName);

        Aws::Lambda::Model::GetFunctionOutcome outcome =
 client.GetFunction(request);

        if (outcome.IsSuccess()) {
            std::cout << "Function retrieve.\n" <<

 outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                      << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::GetFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout << "The resources will be deleted. Press return to continue, ";
    std::getline(std::cin, answer);

    // 9.  Delete the Lambda function.
    bool result = deleteLambdaFunction(client);

    // 10. Delete the IAM role.
    return result && deleteIamRole(clientConfig);
}

//! Routine which invokes a Lambda function and returns the result.
/*!
 \param jsonPayload: Payload for invoke function.
 \param logType: Log type setting for invoke function.
 \param invokeResult: InvokeResult object to receive the result.
 \param client: Lambda client.
 \return bool: Successful completion.
 */
bool
AwsDoc::Lambda::invokeLambdaFunction(const Aws::Utils::Json::JsonValue
 &jsonPayload,
                                     Aws::Lambda::Model::LogType logType,
                                     Aws::Lambda::Model::InvokeResult
 &invokeResult,
                                     const Aws::Lambda::LambdaClient &client) {
```

```
   int seconds = 0;
   bool result = false;
   /*
    * In this example, the Invoke function can be called before recently created
resources are
    * available.  The Invoke function is called repeatedly until the resources
are
    * available.
    */
   do {
       Aws::Lambda::Model::InvokeRequest request;
       request.SetFunctionName(LAMBDA_NAME);
       request.SetLogType(logType);
       std::shared_ptr<Aws::IOStream> payload =
Aws::MakeShared<Aws::StringStream>(
               "FunctionTest");
       *payload << jsonPayload.View().WriteReadable();
       request.SetBody(payload);
       request.SetContentType("application/json");
       Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

       if (outcome.IsSuccess()) {
           invokeResult = std::move(outcome.GetResult());
           result = true;
           break;
       }

           // ACCESS_DENIED: because the role is not available yet.
           // RESOURCE_CONFLICT: because the Lambda function is being created or
updated.
       else if ((outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::ACCESS_DENIED) ||
                (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::RESOURCE_CONFLICT)) {
           if ((seconds % 5) == 0) { // Log status every 10 seconds.
               std::cout << "Waiting for the invoke api to be available, status
" <<
                         ((outcome.GetError().GetErrorType() ==
                           Aws::Lambda::LambdaErrors::ACCESS_DENIED ?
                           "ACCESS_DENIED" : "RESOURCE_CONFLICT")) << ". " <<
seconds
                         << " seconds elapsed." << std::endl;
           }
       }
```

```
        else {
            std::cerr << "Error with Lambda::InvokeRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            break;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (seconds < 60);

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um cenário interativo para mostrar como começar a usar funções do Lambda.

```
// GetStartedFunctionsScenario shows you how to use AWS Lambda to perform the
 following
```

```
// actions:
//
//  1. Create an AWS Identity and Access Management (IAM) role and Lambda
 function, then upload handler code.
//  2. Invoke the function with a single parameter and get results.
//  3. Update the function code and configure with an environment variable.
//  4. Invoke the function with new parameters and get results. Display the
 returned execution log.
//  5. List the functions for your account, then clean up resources.
type GetStartedFunctionsScenario struct {
 sdkConfig       aws.Config
 functionWrapper actions.FunctionWrapper
 questioner      demotools.IQuestioner
 helper          IScenarioHelper
 isTestRun       bool
}

// NewGetStartedFunctionsScenario constructs a GetStartedFunctionsScenario
 instance from a configuration.
// It uses the specified config to get a Lambda client and create wrappers for
 the actions
// used in the scenario.
func NewGetStartedFunctionsScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner,
 helper IScenarioHelper) GetStartedFunctionsScenario {
 lambdaClient := lambda.NewFromConfig(sdkConfig)
 return GetStartedFunctionsScenario{
  sdkConfig:       sdkConfig,
  functionWrapper: actions.FunctionWrapper{LambdaClient: lambdaClient},
  questioner:      questioner,
  helper:          helper,
 }
}

// Run runs the interactive scenario.
func (scenario GetStartedFunctionsScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo.\n")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the AWS Lambda get started with functions demo.")
```

```
 log.Println(strings.Repeat("-", 88))

 role := scenario.GetOrCreateRole()
 funcName := scenario.CreateFunction(role)
 scenario.InvokeIncrement(funcName)
 scenario.UpdateFunction(funcName)
 scenario.InvokeCalculator(funcName)
 scenario.ListFunctions()
 scenario.Cleanup(role, funcName)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// GetOrCreateRole checks whether the specified role exists and returns it if it
 does.
// Otherwise, a role is created that specifies Lambda as a trusted principal.
// The AWSLambdaBasicExecutionRole managed policy is attached to the role and the
 role
// is returned.
func (scenario GetStartedFunctionsScenario) GetOrCreateRole() *iamtypes.Role {
 var role *iamtypes.Role
 iamClient := iam.NewFromConfig(scenario.sdkConfig)
 log.Println("First, we need an IAM role that Lambda can assume.")
 roleName := scenario.questioner.Ask("Enter a name for the role:",
 demotools.NotEmpty{})
 getOutput, err := iamClient.GetRole(context.TODO(), &iam.GetRoleInput{
  RoleName: aws.String(roleName)})
 if err != nil {
  var noSuch *iamtypes.NoSuchEntityException
  if errors.As(err, &noSuch) {
   log.Printf("Role %v doesn't exist. Creating it....\n", roleName)
  } else {
   log.Panicf("Couldn't check whether role %v exists. Here's why: %v\n",
    roleName, err)
  }
 } else {
  role = getOutput.Role
  log.Printf("Found role %v.\n", *role.RoleName)
 }
 if role == nil {
  trustPolicy := PolicyDocument{
   Version: "2012-10-17",
```

```
    Statement: []PolicyStatement{{
     Effect:    "Allow",
     Principal: map[string]string{"Service": "lambda.amazonaws.com"},
     Action:    []string{"sts:AssumeRole"},
    }},
   }
   policyArn := "arn:aws:iam::aws:policy/service-role/AWSLambdaBasicExecutionRole"
   createOutput, err := iamClient.CreateRole(context.TODO(), &iam.CreateRoleInput{
    AssumeRolePolicyDocument: aws.String(trustPolicy.String()),
    RoleName:                 aws.String(roleName),
   })
   if err != nil {
    log.Panicf("Couldn't create role %v. Here's why: %v\n", roleName, err)
   }
   role = createOutput.Role
   _, err = iamClient.AttachRolePolicy(context.TODO(), &iam.AttachRolePolicyInput{
    PolicyArn: aws.String(policyArn),
    RoleName:  aws.String(roleName),
   })
   if err != nil {
    log.Panicf("Couldn't attach a policy to role %v. Here's why: %v\n", roleName,
  err)
   }
   log.Printf("Created role %v.\n", *role.RoleName)
   log.Println("Let's give AWS a few seconds to propagate resources...")
   scenario.helper.Pause(10)
  }
  log.Println(strings.Repeat("-", 88))
  return role
 }

 // CreateFunction creates a Lambda function and uploads a handler written in
  Python.
 // The code for the Python handler is packaged as a []byte in .zip format.
 func (scenario GetStartedFunctionsScenario) CreateFunction(role *iamtypes.Role)
  string {
  log.Println("Let's create a function that increments a number.\n" +
   "The function uses the 'lambda_handler_basic.py' script found in the \n" +
   "'handlers' directory of this project.")
  funcName := scenario.questioner.Ask("Enter a name for the Lambda function:",
  demotools.NotEmpty{})
  zipPackage := scenario.helper.CreateDeploymentPackage("lambda_handler_basic.py",
  fmt.Sprintf("%v.py", funcName))
  log.Printf("Creating function %v and waiting for it to be ready.", funcName)
```

```
 funcState := scenario.functionWrapper.CreateFunction(funcName,
 fmt.Sprintf("%v.lambda_handler", funcName),
  role.Arn, zipPackage)
 log.Printf("Your function is %v.", funcState)
 log.Println(strings.Repeat("-", 88))
 return funcName
}

// InvokeIncrement invokes a Lambda function that increments a number. The
 function
// parameters are contained in a Go struct that is used to serialize the
 parameters to
// a JSON payload that is passed to the function.
// The result payload is deserialized into a Go struct that contains an int
 value.
func (scenario GetStartedFunctionsScenario) InvokeIncrement(funcName string) {
 parameters := actions.IncrementParameters{Action: "increment"}
 log.Println("Let's invoke our function. This function increments a number.")
 parameters.Number = scenario.questioner.AskInt("Enter a number to increment:",
 demotools.NotEmpty{})
 log.Printf("Invoking %v with %v...\n", funcName, parameters.Number)
 invokeOutput := scenario.functionWrapper.Invoke(funcName, parameters, false)
 var payload actions.LambdaResultInt
 err := json.Unmarshal(invokeOutput.Payload, &payload)
 if err != nil {
  log.Panicf("Couldn't unmarshal payload from invoking %v. Here's why: %v\n",
   funcName, err)
 }
 log.Printf("Invoking %v with %v returned %v.\n", funcName, parameters.Number,
 payload)
 log.Println(strings.Repeat("-", 88))
}

// UpdateFunction updates the code for a Lambda function by uploading a simple
 arithmetic
// calculator written in Python. The code for the Python handler is packaged as a
// []byte in .zip format.
// After the code is updated, the configuration is also updated with a new log
// level that instructs the handler to log additional information.
func (scenario GetStartedFunctionsScenario) UpdateFunction(funcName string) {
 log.Println("Let's update the function to an arithmetic calculator.\n" +
  "The function uses the 'lambda_handler_calculator.py' script found in the \n" +
  "'handlers' directory of this project.")
 scenario.questioner.Ask("Press Enter when you're ready.")
```

```
 log.Println("Creating deployment package...")
 zipPackage :=
 scenario.helper.CreateDeploymentPackage("lambda_handler_calculator.py",
  fmt.Sprintf("%v.py", funcName))
 log.Println("...and updating the Lambda function and waiting for it to be
 ready.")
 funcState := scenario.functionWrapper.UpdateFunctionCode(funcName, zipPackage)
 log.Printf("Updated function %v. Its current state is %v.", funcName, funcState)
 log.Println("This function uses an environment variable to control logging
 level.")
 log.Println("Let's set it to DEBUG to get the most logging.")
 scenario.functionWrapper.UpdateFunctionConfiguration(funcName,
  map[string]string{"LOG_LEVEL": "DEBUG"})
 log.Println(strings.Repeat("-", 88))
}

// InvokeCalculator invokes the Lambda calculator function. The parameters are
 stored in a
// Go struct that is used to serialize the parameters to a JSON payload. That
 payload is then passed
// to the function.
// The result payload is deserialized to a Go struct that stores the result as
 either an
// int or float32, depending on the kind of operation that was specified.
func (scenario GetStartedFunctionsScenario) InvokeCalculator(funcName string) {
 wantInvoke := true
 choices := []string{"plus", "minus", "times", "divided-by"}
 for wantInvoke {
  choice := scenario.questioner.AskChoice("Select an arithmetic operation:\n",
 choices)
  x := scenario.questioner.AskInt("Enter a value for x:", demotools.NotEmpty{})
  y := scenario.questioner.AskInt("Enter a value for y:", demotools.NotEmpty{})
  log.Printf("Invoking %v %v %v...", x, choices[choice], y)
  calcParameters := actions.CalculatorParameters{
   Action: choices[choice],
   X:      x,
   Y:      y,
  }
  invokeOutput := scenario.functionWrapper.Invoke(funcName, calcParameters, true)
  var payload any
  if choice == 3 { // divide-by results in a float.
   payload = actions.LambdaResultFloat{}
  } else {
   payload = actions.LambdaResultInt{}
```

```
  }
  err := json.Unmarshal(invokeOutput.Payload, &payload)
  if err != nil {
   log.Panicf("Couldn't unmarshal payload from invoking %v. Here's why: %v\n",
    funcName, err)
  }
  log.Printf("Invoking %v with %v %v %v returned %v.\n", funcName,
   calcParameters.X, calcParameters.Action, calcParameters.Y, payload)
  scenario.questioner.Ask("Press Enter to see the logs from the call.")
  logRes, err := base64.StdEncoding.DecodeString(*invokeOutput.LogResult)
  if err != nil {
   log.Panicf("Couldn't decode log result. Here's why: %v\n", err)
  }
  log.Println(string(logRes))
  wantInvoke = scenario.questioner.AskBool("Do you want to calculate again? (y/
n)", "y")
 }
 log.Println(strings.Repeat("-", 88))
}

// ListFunctions lists up to the specified number of functions for your account.
func (scenario GetStartedFunctionsScenario) ListFunctions() {
 count := scenario.questioner.AskInt(
  "Let's list functions for your account. How many do you want to see?",
 demotools.NotEmpty{})
 functions := scenario.functionWrapper.ListFunctions(count)
 log.Printf("Found %v functions:", len(functions))
 for _, function := range functions {
  log.Printf("\t%v", *function.FunctionName)
 }
 log.Println(strings.Repeat("-", 88))
}

// Cleanup removes the IAM and Lambda resources created by the example.
func (scenario GetStartedFunctionsScenario) Cleanup(role *iamtypes.Role, funcName
 string) {
 if scenario.questioner.AskBool("Do you want to clean up resources created for
 this example? (y/n)",
  "y") {
  iamClient := iam.NewFromConfig(scenario.sdkConfig)
  policiesOutput, err := iamClient.ListAttachedRolePolicies(context.TODO(),
   &iam.ListAttachedRolePoliciesInput{RoleName: role.RoleName})
  if err != nil {
   log.Panicf("Couldn't get policies attached to role %v. Here's why: %v\n",
```

```
    *role.RoleName, err)
  }
  for _, policy := range policiesOutput.AttachedPolicies {
   _, err = iamClient.DetachRolePolicy(context.TODO(),
 &iam.DetachRolePolicyInput{
    PolicyArn: policy.PolicyArn, RoleName: role.RoleName,
   })
   if err != nil {
    log.Panicf("Couldn't detach policy %v from role %v. Here's why: %v\n",
     *policy.PolicyArn, *role.RoleName, err)
   }
  }
  _, err = iamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{RoleName:
 role.RoleName})
  if err != nil {
   log.Panicf("Couldn't delete role %v. Here's why: %v\n", *role.RoleName, err)
  }
  log.Printf("Deleted role %v.\n", *role.RoleName)

  scenario.functionWrapper.DeleteFunction(funcName)
  log.Printf("Deleted function %v.\n", funcName)
 } else {
  log.Println("Okay. Don't forget to delete the resources when you're done with
 them.")
 }
}
```

Crie uma estrutura que encapsule ações individuais do Lambda.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}


// GetFunction gets data about the Lambda function specified by functionName.
func (wrapper FunctionWrapper) GetFunction(functionName string) types.State {
 var state types.State
```

```
 funcOutput, err := wrapper.LambdaClient.GetFunction(context.TODO(),
 &lambda.GetFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't get function %v. Here's why: %v\n", functionName, err)
 } else {
  state = funcOutput.Configuration.State
 }
 return state
}



// CreateFunction creates a new Lambda function from code contained in the
 zipPackage
// buffer. The specified handlerName must match the name of the file and function
// contained in the uploaded code. The role specified by iamRoleArn is assumed by
// Lambda and grants specific permissions.
// When the function already exists, types.StateActive is returned.
// When the function is created, a lambda.FunctionActiveV2Waiter is used to wait
 until the
// function is active.
func (wrapper FunctionWrapper) CreateFunction(functionName string, handlerName
 string,
 iamRoleArn *string, zipPackage *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.CreateFunction(context.TODO(),
 &lambda.CreateFunctionInput{
  Code:         &types.FunctionCode{ZipFile: zipPackage.Bytes()},
  FunctionName: aws.String(functionName),
  Role:         iamRoleArn,
  Handler:      aws.String(handlerName),
  Publish:      true,
  Runtime:      types.RuntimePython38,
 })
 if err != nil {
  var resConflict *types.ResourceConflictException
  if errors.As(err, &resConflict) {
   log.Printf("Function %v already exists.\n", functionName)
   state = types.StateActive
  } else {
   log.Panicf("Couldn't create function %v. Here's why: %v\n", functionName, err)
  }
```

```
 } else {
  waiter := lambda.NewFunctionActiveV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(),
 &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}



// UpdateFunctionCode updates the code for the Lambda function specified by
 functionName.
// The existing code for the Lambda function is entirely replaced by the code in
 the
// zipPackage buffer. After the update action is called, a
 lambda.FunctionUpdatedV2Waiter
// is used to wait until the update is successful.
func (wrapper FunctionWrapper) UpdateFunctionCode(functionName string, zipPackage
 *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.UpdateFunctionCode(context.TODO(),
 &lambda.UpdateFunctionCodeInput{
  FunctionName: aws.String(functionName), ZipFile: zipPackage.Bytes(),
 })
 if err != nil {
  log.Panicf("Couldn't update code for function %v. Here's why: %v\n",
 functionName, err)
 } else {
  waiter := lambda.NewFunctionUpdatedV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(),
 &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
```

```
  }
 }
 return state
}



// UpdateFunctionConfiguration updates a map of environment variables configured
 for
// the Lambda function specified by functionName.
func (wrapper FunctionWrapper) UpdateFunctionConfiguration(functionName string,
 envVars map[string]string) {
 _, err := wrapper.LambdaClient.UpdateFunctionConfiguration(context.TODO(),
 &lambda.UpdateFunctionConfigurationInput{
  FunctionName: aws.String(functionName),
  Environment:  &types.Environment{Variables: envVars},
 })
 if err != nil {
  log.Panicf("Couldn't update configuration for %v. Here's why: %v",
 functionName, err)
 }
}



// ListFunctions lists up to maxItems functions for the account. This function
 uses a
// lambda.ListFunctionsPaginator to paginate the results.
func (wrapper FunctionWrapper) ListFunctions(maxItems int)
 []types.FunctionConfiguration {
 var functions []types.FunctionConfiguration
 paginator := lambda.NewListFunctionsPaginator(wrapper.LambdaClient,
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
 })
 for paginator.HasMorePages() && len(functions) < maxItems {
  pageOutput, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Panicf("Couldn't list functions for your account. Here's why: %v\n", err)
  }
  functions = append(functions, pageOutput.Functions...)
 }
 return functions
}
```

```
// DeleteFunction deletes the Lambda function specified by functionName.
func (wrapper FunctionWrapper) DeleteFunction(functionName string) {
 _, err := wrapper.LambdaClient.DeleteFunction(context.TODO(),
 &lambda.DeleteFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't delete function %v. Here's why: %v\n", functionName, err)
 }
}



// Invoke invokes the Lambda function specified by functionName, passing the
 parameters
// as a JSON payload. When getLog is true, types.LogTypeTail is specified, which
 tells
// Lambda to include the last few log lines in the returned result.
func (wrapper FunctionWrapper) Invoke(functionName string, parameters any, getLog
 bool) *lambda.InvokeOutput {
 logType := types.LogTypeNone
 if getLog {
  logType = types.LogTypeTail
 }
 payload, err := json.Marshal(parameters)
 if err != nil {
  log.Panicf("Couldn't marshal parameters to JSON. Here's why %v\n", err)
 }
 invokeOutput, err := wrapper.LambdaClient.Invoke(context.TODO(),
 &lambda.InvokeInput{
  FunctionName: aws.String(functionName),
  LogType:      logType,
  Payload:      payload,
 })
 if err != nil {
  log.Panicf("Couldn't invoke function %v. Here's why: %v\n", functionName, err)
 }
 return invokeOutput
}
```

```
// IncrementParameters is used to serialize parameters to the increment Lambda
 handler.
type IncrementParameters struct {
 Action string `json:"action"`
 Number int    `json:"number"`
}

// CalculatorParameters is used to serialize parameters to the calculator Lambda
 handler.
type CalculatorParameters struct {
 Action string `json:"action"`
 X      int    `json:"x"`
 Y      int    `json:"y"`
}

// LambdaResultInt is used to deserialize an int result from a Lambda handler.
type LambdaResultInt struct {
 Result int `json:"result"`
}

// LambdaResultFloat is used to deserialize a float32 result from a Lambda
 handler.
type LambdaResultFloat struct {
 Result float32 `json:"result"`
}
```

Crie uma estrutura que implemente funções para ajudar a executar o cenário.

```
// IScenarioHelper abstracts I/O and wait functions from a scenario so that they
// can be mocked for unit testing.
type IScenarioHelper interface {
 Pause(secs int)
 CreateDeploymentPackage(sourceFile string, destinationFile string) *bytes.Buffer
}

// ScenarioHelper lets the caller specify the path to Lambda handler functions.
type ScenarioHelper struct {
 HandlerPath string
}
```

```
// Pause waits for the specified number of seconds.
func (helper *ScenarioHelper) Pause(secs int) {
 time.Sleep(time.Duration(secs) * time.Second)
}

// CreateDeploymentPackage creates an AWS Lambda deployment package from a source
 file. The
// deployment package is stored in .zip format in a bytes.Buffer. The buffer can
 be
// used to pass a []byte to Lambda when creating the function.
// The specified destinationFile is the name to give the file when it's deployed
 to Lambda.
func (helper *ScenarioHelper) CreateDeploymentPackage(sourceFile string,
 destinationFile string) *bytes.Buffer {
 var err error
 buffer := &bytes.Buffer{}
 writer := zip.NewWriter(buffer)
 zFile, err := writer.Create(destinationFile)
 if err != nil {
  log.Panicf("Couldn't create destination archive %v. Here's why: %v\n",
 destinationFile, err)
 }
 sourceBody, err := os.ReadFile(fmt.Sprintf("%v/%v", helper.HandlerPath,
 sourceFile))
 if err != nil {
  log.Panicf("Couldn't read handler source file %v. Here's why: %v\n",
   sourceFile, err)
 } else {
  _, err = zFile.Write(sourceBody)
  if err != nil {
   log.Panicf("Couldn't write handler %v to zip archive. Here's why: %v\n",
    sourceFile, err)
  }
 }
 err = writer.Close()
 if err != nil {
  log.Panicf("Couldn't close zip writer. Here's why: %v\n", err)
 }
 return buffer
}
```

Defina um manipulador do Lambda que aumente um número.

```
import logging

logger = logging.getLogger()
logger.setLevel(logging.INFO)


def lambda_handler(event, context):
    """
    Accepts an action and a single number, performs the specified action on the
 number,
    and returns the result. The only allowable action is 'increment'.

    :param event: The event dict that contains the parameters sent when the
 function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the action.
    """
    result = None
    action = event.get("action")
    if action == "increment":
        result = event.get("number", 0) + 1
        logger.info("Calculated result of %s", result)
    else:
        logger.error("%s is not a valid action.", action)

    response = {"result": result}
    return response
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
import logging
import os


logger = logging.getLogger()
```

```
# Define a list of Python lambda functions that are called by this AWS Lambda
 function.
ACTIONS = {
    "plus": lambda x, y: x + y,
    "minus": lambda x, y: x - y,
    "times": lambda x, y: x * y,
    "divided-by": lambda x, y: x / y,
}


def lambda_handler(event, context):
    """
    Accepts an action and two numbers, performs the specified action on the
 numbers,
    and returns the result.

    :param event: The event dict that contains the parameters sent when the
 function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the specified action.
    """
    # Set the log level based on a variable configured in the Lambda environment.
    logger.setLevel(os.environ.get("LOG_LEVEL", logging.INFO))
    logger.debug("Event: %s", event)

    action = event.get("action")
    func = ACTIONS.get(action)
    x = event.get("x")
    y = event.get("y")
    result = None
    try:
        if func is not None and x is not None and y is not None:
            result = func(x, y)
            logger.info("%s %s %s is %s", x, action, y, result)
        else:
            logger.error("I can't calculate %s %s %s.", x, action, y)
    except ZeroDivisionError:
        logger.warning("I can't divide %s by 0!", x)

    response = {"result": result}
    return response
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/*
 *  Lambda function names appear as:
 *
 *  arn:aws:lambda:us-west-2:335556666777:function:HelloFunction
 *
 *  To find this value, look at the function in the AWS Management Console.
 *
 *  Before running this Java code example, set up your development environment,
 including your credentials.
 *
 *  For more information, see this documentation topic:
 *
 *  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 *  This example performs the following tasks:
```

```
 *
 * 1. Creates an AWS Lambda function.
 * 2. Gets a specific AWS Lambda function.
 * 3. Lists all Lambda functions.
 * 4. Invokes a Lambda function.
 * 5. Updates the Lambda function code and invokes it again.
 * 6. Updates a Lambda function's configuration value.
 * 7. Deletes a Lambda function.
 */

public class LambdaScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <functionName> <filePath> <role> <handler> <bucketName> <key>
\s

                Where:
                    functionName - The name of the Lambda function.\s
                    filePath - The path to the .zip or .jar where the code is
 located.\s
                    role - The AWS Identity and Access Management (IAM) service
 role that has Lambda permissions.\s
                    handler - The fully qualified method name (for example,
 example.Handler::handleRequest).\s
                    bucketName - The Amazon Simple Storage Service (Amazon S3)
 bucket name that contains the .zip or .jar used to update the Lambda function's
 code.\s
                    key - The Amazon S3 key name that represents the .zip or .jar
 (for example, LambdaHello-1.0-SNAPSHOT.jar).
                    """;

        if (args.length != 6) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        String filePath = args[1];
        String role = args[2];
```

```
        String handler = args[3];
        String bucketName = args[4];
        String key = args[5];

        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Lambda example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an AWS Lambda function.");
        String funArn = createLambdaFunction(awsLambda, functionName, filePath,
 role, handler);
        System.out.println("The AWS Lambda ARN is " + funArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Get the " + functionName + " AWS Lambda
 function.");
        getFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. List all AWS Lambda functions.");
        listFunctions(awsLambda);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Invoke the Lambda function.");
        System.out.println("*** Sleep for 1 min to get Lambda function ready.");
        Thread.sleep(60000);
        invokeFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Update the Lambda function code and invoke it
 again.");
        updateFunctionCode(awsLambda, functionName, bucketName, key);
        System.out.println("*** Sleep for 1 min to get Lambda function ready.");
        Thread.sleep(60000);
```

```
        invokeFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Update a Lambda function's configuration value.");
        updateFunctionConfiguration(awsLambda, functionName, handler);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the AWS Lambda function.");
        LambdaScenario.deleteLambdaFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS Lambda scenario completed successfully");
        System.out.println(DASHES);
        awsLambda.close();
    }

    public static String createLambdaFunction(LambdaClient awsLambda,
            String functionName,
            String filePath,
            String role,
            String handler) {

        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);

            FunctionCode code = FunctionCode.builder()
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest =
  CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("Created by the Lambda Java API")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA8)
                    .role(role)
                    .build();
```

```
            // Create a Lambda function using a waiter
            CreateFunctionResponse functionResponse =
awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            return functionResponse.functionArn();

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void getFunction(LambdaClient awsLambda, String functionName) {
        try {
            GetFunctionRequest functionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            GetFunctionResponse response =
awsLambda.getFunction(functionRequest);
            System.out.println("The runtime of this Lambda function is " +
response.configuration().runtime());

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listFunctions(LambdaClient awsLambda) {
        try {
            ListFunctionsResponse functionResult = awsLambda.listFunctions();
            List<FunctionConfiguration> list = functionResult.functions();
            for (FunctionConfiguration config : list) {
                System.out.println("The function name is " +
config.functionName());
            }
```

```
        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void invokeFunction(LambdaClient awsLambda, String
functionName) {

        InvokeResponse res;
        try {
            // Need a SdkBytes instance for the payload.
            JSONObject jsonObj = new JSONObject();
            jsonObj.put("inputValue", "2000");
            String json = jsonObj.toString();
            SdkBytes payload = SdkBytes.fromUtf8String(json);

            InvokeRequest request = InvokeRequest.builder()
                    .functionName(functionName)
                    .payload(payload)
                    .build();

            res = awsLambda.invoke(request);
            String value = res.payload().asUtf8String();
            System.out.println(value);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateFunctionCode(LambdaClient awsLambda, String
functionName, String bucketName, String key) {
        try {
            LambdaWaiter waiter = awsLambda.waiter();
            UpdateFunctionCodeRequest functionCodeRequest =
UpdateFunctionCodeRequest.builder()
                    .functionName(functionName)
                    .publish(true)
                    .s3Bucket(bucketName)
                    .s3Key(key)
                    .build();
```

```
            UpdateFunctionCodeResponse response =
awsLambda.updateFunctionCode(functionCodeRequest);
            GetFunctionConfigurationRequest getFunctionConfigRequest =
GetFunctionConfigurationRequest.builder()
                    .functionName(functionName)
                    .build();

            WaiterResponse<GetFunctionConfigurationResponse> waiterResponse =
waiter
                    .waitUntilFunctionUpdated(getFunctionConfigRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("The last modified value is " +
response.lastModified());

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateFunctionConfiguration(LambdaClient awsLambda, String
functionName, String handler) {
        try {
            UpdateFunctionConfigurationRequest configurationRequest =
UpdateFunctionConfigurationRequest.builder()
                    .functionName(functionName)
                    .handler(handler)
                    .runtime(Runtime.JAVA11)
                    .build();

            awsLambda.updateFunctionConfiguration(configurationRequest);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void deleteLambdaFunction(LambdaClient awsLambda, String
functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
```

```
            awsLambda.deleteFunction(request);
            System.out.println("The " + functionName + " function was deleted");

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um perfil do AWS Identity and Access Management (IAM) que concede permissão ao Lambda para gravar em logs.

```
    log(`Creating role (${NAME_ROLE_LAMBDA})...`);
    const response = await createRole(NAME_ROLE_LAMBDA);
```

```
import { AttachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const attachRolePolicy = (policyArn, roleName) => {
  const command = new AttachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

Crie uma função do Lambda e carregue o código de manipulador.

```
const createFunction = async (funcName, roleArn) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${funcName}.zip`);

  const command = new CreateFunctionCommand({
    Code: { ZipFile: code },
    FunctionName: funcName,
    Role: roleArn,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

Invoque essa função com um único parâmetro e receba resultados.

```
const invoke = async (funcName, payload) => {
  const client = new LambdaClient({});
```

```
  const command = new InvokeCommand({
    FunctionName: funcName,
    Payload: JSON.stringify(payload),
    LogType: LogType.Tail,
  });

  const { Payload, LogResult } = await client.send(command);
  const result = Buffer.from(Payload).toString();
  const logs = Buffer.from(LogResult, "base64").toString();
  return { logs, result };
};
```

Atualize o código de função e configure seu ambiente do Lambda usando uma variável de ambiente.

```
const updateFunctionCode = async (funcName, newFunc) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${newFunc}.zip`);
  const command = new UpdateFunctionCodeCommand({
    ZipFile: code,
    FunctionName: funcName,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};

const updateFunctionConfiguration = (funcName) => {
  const client = new LambdaClient({});
  const config = readFileSync(`${dirname}../functions/config.json`).toString();
  const command = new UpdateFunctionConfigurationCommand({
    ...JSON.parse(config),
    FunctionName: funcName,
  });
  return client.send(command);
};
```

Liste as funções para a sua conta.

```
const listFunctions = () => {
  const client = new LambdaClient({});
  const command = new ListFunctionsCommand({});

  return client.send(command);
};
```

Exclua o perfil do IAM e a função do Lambda.

```
import { DeleteRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const deleteRole = (roleName) => {
  const command = new DeleteRoleCommand({ RoleName: roleName });
  return client.send(command);
};

/**
 * @param {string} funcName
 */
const deleteFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new DeleteFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions

- UpdateFunctionCode
- UpdateFunctionConfiguration

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
            <functionName> <role> <handler> <bucketName> <updatedBucketName>
 <key>

        Where:
            functionName - The name of the AWS Lambda function.
            role - The AWS Identity and Access Management (IAM) service role that
 has AWS Lambda permissions.
            handler - The fully qualified method name (for example,
 example.Handler::handleRequest).
            bucketName - The Amazon Simple Storage Service (Amazon S3) bucket
 name that contains the ZIP or JAR used for the Lambda function's code.
            updatedBucketName - The Amazon S3 bucket name that contains the .zip
 or .jar used to update the Lambda function's code.
            key - The Amazon S3 key name that represents the .zip or .jar file
 (for example, LambdaHello-1.0-SNAPSHOT.jar).
            """

    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }

    val functionName = args[0]
    val role = args[1]
```

```
    val handler = args[2]
    val bucketName = args[3]
    val updatedBucketName = args[4]
    val key = args[5]

    println("Creating a Lambda function named $functionName.")
    val funArn = createScFunction(functionName, bucketName, key, handler, role)
    println("The AWS Lambda ARN is $funArn")

    // Get a specific Lambda function.
    println("Getting the $functionName AWS Lambda function.")
    getFunction(functionName)

    // List the Lambda functions.
    println("Listing all AWS Lambda functions.")
    listFunctionsSc()

    // Invoke the Lambda function.
    println("*** Invoke the Lambda function.")
    invokeFunctionSc(functionName)

    // Update the AWS Lambda function code.
    println("*** Update the Lambda function code.")
    updateFunctionCode(functionName, updatedBucketName, key)

    // println("*** Invoke the function again after updating the code.")
    invokeFunctionSc(functionName)

    // Update the AWS Lambda function configuration.
    println("Update the run time of the function.")
    UpdateFunctionConfiguration(functionName, handler)

    // Delete the AWS Lambda function.
    println("Delete the AWS Lambda function.")
    delFunction(functionName)
}

suspend fun createScFunction(
    myFunctionName: String,
    s3BucketName: String,
    myS3Key: String,
    myHandler: String,
    myRole: String
): String {
```

```
    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }

    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java8
    }

    // Create a Lambda function using a waiter
    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val functionResponse = awsLambda.createFunction(request)
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        return functionResponse.functionArn.toString()
    }
}

suspend fun getFunction(functionNameVal: String) {

    val functionRequest = GetFunctionRequest {
        functionName = functionNameVal
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.getFunction(functionRequest)
        println("The runtime of this Lambda function is
 ${response.configuration?.runtime}")
    }
}

suspend fun listFunctionsSc() {

    val request = ListFunctionsRequest {
        maxItems = 10
    }
```

```
    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.listFunctions(request)
        response.functions?.forEach { function ->
            println("The function name is ${function.functionName}")
        }
    }
}

suspend fun invokeFunctionSc(functionNameVal: String) {

    val json = """{"inputValue":"1000"}"""
    val byteArray = json.trimIndent().encodeToByteArray()
    val request = InvokeRequest {
        functionName = functionNameVal
        payload = byteArray
        logType = LogType.Tail
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val res = awsLambda.invoke(request)
        println("The function payload is
 ${res.payload?.toString(Charsets.UTF_8)}")
    }
}

suspend fun updateFunctionCode(functionNameVal: String?, bucketName: String?,
 key: String?) {

    val functionCodeRequest = UpdateFunctionCodeRequest {
        functionName = functionNameVal
        publish = true
        s3Bucket = bucketName
        s3Key = key
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.updateFunctionCode(functionCodeRequest)
        awsLambda.waitUntilFunctionUpdated {
            functionName = functionNameVal
        }
        println("The last modified value is " + response.lastModified)
    }
}
```

```
suspend fun UpdateFunctionConfiguration(functionNameVal: String?, handlerVal:
 String?) {

    val configurationRequest = UpdateFunctionConfigurationRequest {
        functionName = functionNameVal
        handler = handlerVal
        runtime = Runtime.Java11
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.updateFunctionConfiguration(configurationRequest)
    }
}

suspend fun delFunction(myFunctionName: String) {

    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Lambda;

use Aws\S3\S3Client;
use GuzzleHttp\Psr7\Stream;
use Iam\IAMService;

class GettingStartedWithLambda
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the AWS Lambda getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();

        $iamService = new IAMService();
        $s3client = new S3Client($clientArgs);
        $lambdaService = new LambdaService();

        echo "First, let's create a role to run our Lambda code.\n";
        $roleName = "test-lambda-role-$uniqid";
        $rolePolicyDocument = "{
            \"Version\": \"2012-10-17\",
            \"Statement\": [
                {
```

```
                    \"Effect\": \"Allow\",
                    \"Principal\": {
                        \"Service\": \"lambda.amazonaws.com\"
                    },
                    \"Action\": \"sts:AssumeRole\"
                }
            ]
        }";
        $role = $iamService->createRole($roleName, $rolePolicyDocument);
        echo "Created role {$role['RoleName']}.\n";

        $iamService->attachRolePolicy(
            $role['RoleName'],
            "arn:aws:iam::aws:policy/service-role/AWSLambdaBasicExecutionRole"
        );
        echo "Attached the AWSLambdaBasicExecutionRole to {$role['RoleName']}.
\n";

        echo "\nNow let's create an S3 bucket and upload our Lambda code there.
\n";
        $bucketName = "test-example-bucket-$uniqid";
        $s3client->createBucket([
            'Bucket' => $bucketName,
        ]);
        echo "Created bucket $bucketName.\n";

        $functionName = "doc_example_lambda_$uniqid";
        $codeBasic = __DIR__ . "/lambda_handler_basic.zip";
        $handler = "lambda_handler_basic";
        $file = file_get_contents($codeBasic);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => $functionName,
            'Body' => $file,
        ]);
        echo "Uploaded the Lambda code.\n";

        $createLambdaFunction = $lambdaService->createFunction($functionName,
 $role, $bucketName, $handler);
        // Wait until the function has finished being created.
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
        } while ($getLambdaFunction['Configuration']['State'] == "Pending");
```

```
        echo "Created Lambda function {$getLambdaFunction['Configuration']
['FunctionName']}.\n";

        sleep(1);

        echo "\nOk, let's invoke that Lambda code.\n";
        $basicParams = [
            'action' => 'increment',
            'number' => 3,
        ];
        /** @var Stream $invokeFunction */
        $invokeFunction = $lambdaService->invoke($functionName, $basicParams)
['Payload'];
        $result = json_decode($invokeFunction->getContents())->result;
        echo "After invoking the Lambda code with the input of
 {$basicParams['number']} we received $result.\n";

        echo "\nSince that's working, let's update the Lambda code.\n";
        $codeCalculator = "lambda_handler_calculator.zip";
        $handlerCalculator = "lambda_handler_calculator";
        echo "First, put the new code into the S3 bucket.\n";
        $file = file_get_contents($codeCalculator);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => $functionName,
            'Body' => $file,
        ]);
        echo "New code uploaded.\n";

        $lambdaService->updateFunctionCode($functionName, $bucketName,
 $functionName);
        // Wait for the Lambda code to finish updating.
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
        } while ($getLambdaFunction['Configuration']['LastUpdateStatus'] !==
 "Successful");
        echo "New Lambda code uploaded.\n";

        $environment = [
            'Variable' => ['Variables' => ['LOG_LEVEL' => 'DEBUG']],
        ];
        $lambdaService->updateFunctionConfiguration($functionName,
 $handlerCalculator, $environment);
```

```
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
        } while ($getLambdaFunction['Configuration']['LastUpdateStatus'] !==
 "Successful");
        echo "Lambda code updated with new handler and a LOG_LEVEL of DEBUG for
 more information.\n";

        echo "Invoke the new code with some new data.\n";
        $calculatorParams = [
            'action' => 'plus',
            'x' => 5,
            'y' => 4,
        ];
        $invokeFunction = $lambdaService->invoke($functionName,
 $calculatorParams, "Tail");
        $result = json_decode($invokeFunction['Payload']->getContents())->result;
        echo "Indeed, {$calculatorParams['x']} + {$calculatorParams['y']} does
 equal $result.\n";
        echo "Here's the extra debug info: ";
        echo base64_decode($invokeFunction['LogResult']) . "\n";

        echo "\nBut what happens if you try to divide by zero?\n";
        $divZeroParams = [
            'action' => 'divide',
            'x' => 5,
            'y' => 0,
        ];
        $invokeFunction = $lambdaService->invoke($functionName, $divZeroParams,
 "Tail");
        $result = json_decode($invokeFunction['Payload']->getContents())->result;
        echo "You get a |$result| result.\n";
        echo "And an error message: ";
        echo base64_decode($invokeFunction['LogResult']) . "\n";

        echo "\nHere's all the Lambda functions you have in this Region:\n";
        $listLambdaFunctions = $lambdaService->listFunctions(5);
        $allLambdaFunctions = $listLambdaFunctions['Functions'];
        $next = $listLambdaFunctions->get('NextMarker');
        while ($next != false) {
            $listLambdaFunctions = $lambdaService->listFunctions(5, $next);
            $next = $listLambdaFunctions->get('NextMarker');
            $allLambdaFunctions = array_merge($allLambdaFunctions,
 $listLambdaFunctions['Functions']);
```

```
        }
        foreach ($allLambdaFunctions as $function) {
            echo "{$function['FunctionName']}\n";
        }

        echo "\n\nAnd don't forget to clean up your data!\n";

        $lambdaService->deleteFunction($functionName);
        echo "Deleted Lambda function.\n";
        $iamService->deleteRole($role['RoleName']);
        echo "Deleted Role.\n";
        $deleteObjects = $s3client->listObjectsV2([
            'Bucket' => $bucketName,
        ]);
        $deleteObjects = $s3client->deleteObjects([
            'Bucket' => $bucketName,
            'Delete' => [
                'Objects' => $deleteObjects['Contents'],
            ]
        ]);
        echo "Deleted all objects from the S3 bucket.\n";
        $s3client->deleteBucket(['Bucket' => $bucketName]);
        echo "Deleted the bucket.\n";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina um manipulador do Lambda que aumente um número.

```
import logging

logger = logging.getLogger()
logger.setLevel(logging.INFO)


def lambda_handler(event, context):
    """
    Accepts an action and a single number, performs the specified action on the
 number,
    and returns the result. The only allowable action is 'increment'.

    :param event: The event dict that contains the parameters sent when the
 function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the action.
    """
    result = None
    action = event.get("action")
    if action == "increment":
        result = event.get("number", 0) + 1
        logger.info("Calculated result of %s", result)
    else:
        logger.error("%s is not a valid action.", action)

    response = {"result": result}
    return response
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
import logging
import os


logger = logging.getLogger()

# Define a list of Python lambda functions that are called by this AWS Lambda
 function.
ACTIONS = {
    "plus": lambda x, y: x + y,
    "minus": lambda x, y: x - y,
    "times": lambda x, y: x * y,
    "divided-by": lambda x, y: x / y,
}


def lambda_handler(event, context):
    """
    Accepts an action and two numbers, performs the specified action on the
 numbers,
    and returns the result.

    :param event: The event dict that contains the parameters sent when the
 function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the specified action.
    """
    # Set the log level based on a variable configured in the Lambda environment.
    logger.setLevel(os.environ.get("LOG_LEVEL", logging.INFO))
    logger.debug("Event: %s", event)

    action = event.get("action")
    func = ACTIONS.get(action)
    x = event.get("x")
    y = event.get("y")
    result = None
    try:
        if func is not None and x is not None and y is not None:
```

```
            result = func(x, y)
            logger.info("%s %s %s is %s", x, action, y, result)
        else:
            logger.error("I can't calculate %s %s %s.", x, action, y)
    except ZeroDivisionError:
        logger.warning("I can't divide %s by 0!", x)

    response = {"result": result}
    return response
```

Crie funções que envolvam ações do Lambda.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    @staticmethod
    def create_deployment_package(source_file, destination_file):
        """
        Creates a Lambda deployment package in .zip format in an in-memory
 buffer. This
        buffer can be passed directly to Lambda when creating the function.

        :param source_file: The name of the file that contains the Lambda handler
                            function.
        :param destination_file: The name to give the file when it's deployed to
 Lambda.
        :return: The deployment package.
        """
        buffer = io.BytesIO()
        with zipfile.ZipFile(buffer, "w") as zipped:
            zipped.write(source_file, destination_file)
        buffer.seek(0)
        return buffer.read()

    def get_iam_role(self, iam_role_name):
        """
        Get an AWS Identity and Access Management (IAM) role.
```

```
        :param iam_role_name: The name of the role to retrieve.
        :return: The IAM role.
        """
        role = None
        try:
            temp_role = self.iam_resource.Role(iam_role_name)
            temp_role.load()
            role = temp_role
            logger.info("Got IAM role %s", role.name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                logger.info("IAM role %s does not exist.", iam_role_name)
            else:
                logger.error(
                    "Couldn't get IAM role %s. Here's why: %s: %s",
                    iam_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return role

    def create_iam_role_for_lambda(self, iam_role_name):
        """
        Creates an IAM role that grants the Lambda function basic permissions. If
a
        role with the specified name already exists, it is used for the demo.

        :param iam_role_name: The name of the role to create.
        :return: The role and a value that indicates whether the role is newly
created.
        """
        role = self.get_iam_role(iam_role_name)
        if role is not None:
            return role, False

        lambda_assume_role_policy = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "lambda.amazonaws.com"},
                    "Action": "sts:AssumeRole",
```

```
                }
            ],
        }
        policy_arn = "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole"

        try:
            role = self.iam_resource.create_role(
                RoleName=iam_role_name,
                AssumeRolePolicyDocument=json.dumps(lambda_assume_role_policy),
            )
            logger.info("Created role %s.", role.name)
            role.attach_policy(PolicyArn=policy_arn)
            logger.info("Attached basic execution policy to role %s.", role.name)
        except ClientError as error:
            if error.response["Error"]["Code"] == "EntityAlreadyExists":
                role = self.iam_resource.Role(iam_role_name)
                logger.warning("The role %s already exists. Using it.",
 iam_role_name)
            else:
                logger.exception(
                    "Couldn't create role %s or attach policy %s.",
                    iam_role_name,
                    policy_arn,
                )
                raise

        return role, True

    def get_function(self, function_name):
        """
        Gets data about a Lambda function.

        :param function_name: The name of the function.
        :return: The function data.
        """
        response = None
        try:
            response =
 self.lambda_client.get_function(FunctionName=function_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Function %s does not exist.", function_name)
            else:
```

```
                logger.error(
                    "Couldn't get function %s. Here's why: %s: %s",
                    function_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response


    def create_function(
        self, function_name, handler_name, iam_role, deployment_package
    ):
        """
        Deploys a Lambda function.

        :param function_name: The name of the Lambda function.
        :param handler_name: The fully qualified name of the handler function.
This
                              must include the file name and the function name.
        :param iam_role: The IAM role to use for the function.
        :param deployment_package: The deployment package that contains the
function
                                     code in .zip format.
        :return: The Amazon Resource Name (ARN) of the newly created function.
        """
        try:
            response = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="AWS Lambda doc example",
                Runtime="python3.8",
                Role=iam_role.arn,
                Handler=handler_name,
                Code={"ZipFile": deployment_package},
                Publish=True,
            )
            function_arn = response["FunctionArn"]
            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)
            logger.info(
                "Created function '%s' with ARN: '%s'.",
                function_name,
                response["FunctionArn"],
            )
```

```
        except ClientError:
            logger.error("Couldn't create function %s.", function_name)
            raise
        else:
            return function_arn


    def delete_function(self, function_name):
        """
        Deletes a Lambda function.

        :param function_name: The name of the function to delete.
        """
        try:
            self.lambda_client.delete_function(FunctionName=function_name)
        except ClientError:
            logger.exception("Couldn't delete function %s.", function_name)
            raise


    def invoke_function(self, function_name, function_params, get_log=False):
        """
        Invokes a Lambda function.

        :param function_name: The name of the function to invoke.
        :param function_params: The parameters of the function as a dict. This
dict
                                is serialized to JSON before it is sent to
Lambda.
        :param get_log: When true, the last 4 KB of the execution log are
included in
                        the response.
        :return: The response from the function invocation.
        """
        try:
            response = self.lambda_client.invoke(
                FunctionName=function_name,
                Payload=json.dumps(function_params),
                LogType="Tail" if get_log else "None",
            )
            logger.info("Invoked function %s.", function_name)
        except ClientError:
            logger.exception("Couldn't invoke function %s.", function_name)
            raise
```

```
        return response


    def update_function_code(self, function_name, deployment_package):
        """
        Updates the code for a Lambda function by submitting a .zip archive that
contains
        the code for the function.

        :param function_name: The name of the function to update.
        :param deployment_package: The function code to update, packaged as bytes
in
                                   .zip format.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_code(
                FunctionName=function_name, ZipFile=deployment_package
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def update_function_configuration(self, function_name, env_vars):
        """
        Updates the environment variables for a Lambda function.

        :param function_name: The name of the function to update.
        :param env_vars: A dict of environment variables to update.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_configuration(
                FunctionName=function_name, Environment={"Variables": env_vars}
            )
        except ClientError as err:
```

```
            logger.error(
                "Couldn't update function configuration %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def list_functions(self):
        """
        Lists the Lambda functions for the current account.
        """
        try:
            func_paginator = self.lambda_client.get_paginator("list_functions")
            for func_page in func_paginator.paginate():
                for func in func_page["Functions"]:
                    print(func["FunctionName"])
                    desc = func.get("Description")
                    if desc:
                        print(f"\t{desc}")
                    print(f"\t{func['Runtime']}: {func['Handler']}")
        except ClientError as err:
            logger.error(
                "Couldn't list functions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma função que execute o cenário.

```
class UpdateFunctionWaiter(CustomWaiter):
    """A custom waiter that waits until a function is successfully updated."""

    def __init__(self, client):
        super().__init__(
```

```
            "UpdateSuccess",
            "GetFunction",
            "Configuration.LastUpdateStatus",
            {"Successful": WaitState.SUCCESS, "Failed": WaitState.FAILURE},
            client,
        )

    def wait(self, function_name):
        self._wait(FunctionName=function_name)


def run_scenario(lambda_client, iam_resource, basic_file, calculator_file,
 lambda_name):
    """
    Runs the scenario.

    :param lambda_client: A Boto3 Lambda client.
    :param iam_resource: A Boto3 IAM resource.
    :param basic_file: The name of the file that contains the basic Lambda
 handler.
    :param calculator_file: The name of the file that contains the calculator
 Lambda handler.
    :param lambda_name: The name to give resources created for the scenario, such
 as the
                        IAM role and the Lambda function.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the AWS Lambda getting started with functions demo.")
    print("-" * 88)

    wrapper = LambdaWrapper(lambda_client, iam_resource)

    print("Checking for IAM role for Lambda...")
    iam_role, should_wait = wrapper.create_iam_role_for_lambda(lambda_name)
    if should_wait:
        logger.info("Giving AWS time to create resources...")
        wait(10)

    print(f"Looking for function {lambda_name}...")
    function = wrapper.get_function(lambda_name)
    if function is None:
        print("Zipping the Python script into a deployment package...")
```

```
        deployment_package = wrapper.create_deployment_package(
            basic_file, f"{lambda_name}.py"
        )
        print(f"...and creating the {lambda_name} Lambda function.")
        wrapper.create_function(
            lambda_name, f"{lambda_name}.lambda_handler", iam_role,
deployment_package
        )
    else:
        print(f"Function {lambda_name} already exists.")
    print("-" * 88)

    print(f"Let's invoke {lambda_name}. This function increments a number.")
    action_params = {
        "action": "increment",
        "number": q.ask("Give me a number to increment: ", q.is_int),
    }
    print(f"Invoking {lambda_name}...")
    response = wrapper.invoke_function(lambda_name, action_params)
    print(
        f"Incrementing {action_params['number']} resulted in "
        f"{json.load(response['Payload'])}"
    )
    print("-" * 88)

    print(f"Let's update the function to an arithmetic calculator.")
    q.ask("Press Enter when you're ready.")
    print("Creating a new deployment package...")
    deployment_package = wrapper.create_deployment_package(
        calculator_file, f"{lambda_name}.py"
    )
    print(f"...and updating the {lambda_name} Lambda function.")
    update_waiter = UpdateFunctionWaiter(lambda_client)
    wrapper.update_function_code(lambda_name, deployment_package)
    update_waiter.wait(lambda_name)
    print(f"This function uses an environment variable to control logging
level.")
    print(f"Let's set it to DEBUG to get the most logging.")
    wrapper.update_function_configuration(
        lambda_name, {"LOG_LEVEL": logging.getLevelName(logging.DEBUG)}
    )

    actions = ["plus", "minus", "times", "divided-by"]
    want_invoke = True
```

```
    while want_invoke:
        print(f"Let's invoke {lambda_name}. You can invoke these actions:")
        for index, action in enumerate(actions):
            print(f"{index + 1}: {action}")
        action_params = {}
        action_index = q.ask(
            "Enter the number of the action you want to take: ",
            q.is_int,
            q.in_range(1, len(actions)),
        )
        action_params["action"] = actions[action_index - 1]
        print(f"You've chosen to invoke 'x {action_params['action']} y'.")
        action_params["x"] = q.ask("Enter a value for x: ", q.is_int)
        action_params["y"] = q.ask("Enter a value for y: ", q.is_int)
        print(f"Invoking {lambda_name}...")
        response = wrapper.invoke_function(lambda_name, action_params, True)
        print(
            f"Calculating {action_params['x']} {action_params['action']}
{action_params['y']} "
            f"resulted in {json.load(response['Payload'])}"
        )
        q.ask("Press Enter to see the logs from the call.")
        print(base64.b64decode(response["LogResult"]).decode())
        want_invoke = q.ask("That was fun. Shall we do it again? (y/n) ",
q.is_yesno)
    print("-" * 88)

    if q.ask(
        "Do you want to list all of the functions in your account? (y/n) ",
q.is_yesno
    ):
        wrapper.list_functions()
    print("-" * 88)

    if q.ask("Ready to delete the function and role? (y/n) ", q.is_yesno):
        for policy in iam_role.attached_policies.all():
            policy.detach_role(RoleName=iam_role.name)
        iam_role.delete()
        print(f"Deleted role {lambda_name}.")
        wrapper.delete_function(lambda_name)
        print(f"Deleted function {lambda_name}.")

    print("\nThanks for watching!")
    print("-" * 88)
```

```
if __name__ == "__main__":
    try:
        run_scenario(
            boto3.client("lambda"),
            boto3.resource("iam"),
            "lambda_handler_basic.py",
            "lambda_handler_calculator.py",
            "doc_example_lambda_calculator",
        )
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure as permissões de pré-requisitos do IAM para uma função do Lambda capaz de gravar logs.

```
  # Get an AWS Identity and Access Management (IAM) role.
  #
  # @param iam_role_name: The name of the role to retrieve.
  # @param action: Whether to create or destroy the IAM apparatus.
  # @return: The IAM role.
  def manage_iam(iam_role_name, action)
    role_policy = {
      'Version': "2012-10-17",
      'Statement': [
        {
          'Effect': "Allow",
          'Principal': {
            'Service': "lambda.amazonaws.com"
          },
          'Action': "sts:AssumeRole"
        }
      ]
    }
    case action
    when "create"
      role = $iam_client.create_role(
        role_name: iam_role_name,
        assume_role_policy_document: role_policy.to_json
      )
      $iam_client.attach_role_policy(
        {
          policy_arn: "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole",
          role_name: iam_role_name
        }
      )
      $iam_client.wait_until(:role_exists, { role_name: iam_role_name }) do |w|
        w.max_attempts = 5
        w.delay = 5
      end
      @logger.debug("Successfully created IAM role: #{role['role']['arn']}")
      @logger.debug("Enforcing a 10-second sleep to allow IAM role to activate
 fully.")
      sleep(10)
      return role, role_policy.to_json
    when "destroy"
      $iam_client.detach_role_policy(
        {
```

```
          policy_arn: "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole",
          role_name: iam_role_name
        }
      )
      $iam_client.delete_role(
        role_name: iam_role_name
      )
      @logger.debug("Detached policy & deleted IAM role: #{iam_role_name}")
    else
      raise "Incorrect action provided. Must provide 'create' or 'destroy'"
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error creating role or attaching policy:\n
 #{e.message}")
  end
```

Defina um manipulador do Lambda que incremente um número fornecido como um parâmetro de invocação.

```
require "logger"

# A function that increments a whole number by one (1) and logs the result.
# Requires a manually-provided runtime parameter, 'number', which must be Int
#
# @param event [Hash] Parameters sent when the function is invoked
# @param context [Hash] Methods and properties that provide information
# about the invocation, function, and execution environment.
# @return incremented_number [String] The incremented number.
def lambda_handler(event:, context:)
  logger = Logger.new($stdout)
  log_level = ENV["LOG_LEVEL"]
  logger.level = case log_level
                 when "debug"
                   Logger::DEBUG
                 when "info"
                   Logger::INFO
                 else
                   Logger::ERROR
                 end
  logger.debug("This is a debug log message.")
  logger.info("This is an info log message. Code executed successfully!")
```

```
  number = event["number"].to_i
  incremented_number = number + 1
  logger.info("You provided #{number.round} and it was incremented to
 #{incremented_number.round}")
  incremented_number.round.to_s
end
```

Compacte a função do Lambda em um pacote de implantação.

```
  # Creates a Lambda deployment package in .zip format.
  # This zip can be passed directly as a string to Lambda when creating the
 function.
  #
  # @param source_file: The name of the object, without suffix, for the Lambda
 file and zip.
  # @return: The deployment package.
  def create_deployment_package(source_file)
    Dir.chdir(File.dirname(__FILE__))
    if File.exist?("lambda_function.zip")
      File.delete("lambda_function.zip")
      @logger.debug("Deleting old zip: lambda_function.zip")
    end
    Zip::File.open("lambda_function.zip", create: true) {
      |zipfile|
      zipfile.add("lambda_function.rb", "#{source_file}.rb")
    }
    @logger.debug("Zipping #{source_file}.rb into: lambda_function.zip.")
    File.read("lambda_function.zip").to_s
  rescue StandardError => e
    @logger.error("There was an error creating deployment package:\n
 #{e.message}")
  end
```

Crie uma nova função do Lambda.

```
  # Deploys a Lambda function.
  #
  # @param function_name: The name of the Lambda function.
  # @param handler_name: The fully qualified name of the handler function. This
  #                      must include the file name and the function name.
  # @param role_arn: The IAM role to use for the function.
```

```
  # @param deployment_package: The deployment package that contains the function
  #                            code in .zip format.
  # @return: The Amazon Resource Name (ARN) of the newly created function.
  def create_function(function_name, handler_name, role_arn, deployment_package)
    response = @lambda_client.create_function({
                                                role: role_arn.to_s,
                                                function_name: function_name,
                                                handler: handler_name,
                                                runtime: "ruby2.7",
                                                code: {
                                                  zip_file: deployment_package
                                                },
                                                environment: {
                                                  variables: {
                                                    "LOG_LEVEL" => "info"
                                                  }
                                                }
                                              })
    @lambda_client.wait_until(:function_active_v2, { function_name:
 function_name}) do |w|
      w.max_attempts = 5
      w.delay = 5
    end
    response
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error creating #{function_name}:\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n
 #{e.message}")
  end
```

Invoque a função do Lambda com parâmetros de runtime opcionais.

```
  # Invokes a Lambda function.
  # @param function_name [String] The name of the function to invoke.
  # @param payload [nil] Payload containing runtime parameters.
  # @return [Object] The response from the function invocation.
  def invoke_function(function_name, payload = nil)
    params = { function_name: function_name}
    params[:payload] = payload unless payload.nil?
    @lambda_client.invoke(params)
  rescue Aws::Lambda::Errors::ServiceException => e
```

```
    @logger.error("There was an error executing #{function_name}:\n
#{e.message}")
  end
```

Atualize a configuração da função do Lambda para injetar uma nova variável de ambiente.

```
  # Updates the environment variables for a Lambda function.
  # @param function_name: The name of the function to update.
  # @param log_level: The log level of the function.
  # @return: Data about the update, including the status.
  def update_function_configuration(function_name, log_level)
    @lambda_client.update_function_configuration({
                                                    function_name: function_name,
                                                    environment: {
                                                      variables: {
                                                        "LOG_LEVEL" => log_level
                                                      }
                                                    }
                                                  })
    @lambda_client.wait_until(:function_updated_v2, { function_name:
function_name}) do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating configurations for
#{function_name}:\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n
#{e.message}")
  end
```

Atualize o código da função do Lambda com um pacote de implantação diferente que contenha um código diferente.

```
  # Updates the code for a Lambda function by submitting a .zip archive that
contains
  # the code for the function.

  # @param function_name: The name of the function to update.
  # @param deployment_package: The function code to update, packaged as bytes in
```

```
  #                             .zip format.
  # @return: Data about the update, including the status.
  def update_function_code(function_name, deployment_package)
    @lambda_client.update_function_code(
      function_name: function_name,
      zip_file: deployment_package
    )
    @lambda_client.wait_until(:function_updated_v2, { function_name:
function_name}) do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating function code for:
#{function_name}:\n #{e.message}")
    nil
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to update:\n
#{e.message}")
  end
```

Liste todas as funções do Lambda existentes usando o paginador integrado.

```
  # Lists the Lambda functions for the current account.
  def list_functions
    functions = []
    @lambda_client.list_functions.each do |response|
      response["functions"].each do |function|
        functions.append(function["function_name"])
      end
    end
    functions
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n
#{e.message}")
  end
```

Exclua uma função do Lambda específica.

```
  # Deletes a Lambda function.
  # @param function_name: The name of the function to delete.
```

```
  def delete_function(function_name)
    print "Deleting function: #{function_name}..."
    @lambda_client.delete_function(
      function_name: function_name
    )
    print "Done!".green
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error deleting #{function_name}:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O Cargo.toml com dependências usadas neste cenário.

```
[package]
name = "lambda-code-examples"
version = "0.1.0"
edition = "2021"
```

```
# See more keys and their definitions at https://doc.rust-lang.org/cargo/
reference/manifest.html

[dependencies]
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-sdk-ec2 = { version = "1.3.0" }
aws-sdk-iam = { version = "1.3.0" }
aws-sdk-lambda = { version = "1.3.0" }
aws-sdk-s3 = { version = "1.4.0" }
aws-smithy-types = { version = "1.0.1" }
aws-types = { version = "1.0.1" }
clap = { version = "~4.4", features = ["derive"] }
tokio = { version = "1.20.1", features = ["full"] }
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
tracing = "0.1.37"
serde_json = "1.0.94"
anyhow = "1.0.71"
uuid = { version = "1.3.3", features = ["v4"] }
lambda_runtime = "0.8.0"
serde = "1.0.164"
```

Uma coleção de utilitários que simplificam chamar o Lambda para este cenário. Este arquivo está como src/ations.rs no crate.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use anyhow::anyhow;
use aws_sdk_iam::operation::delete_role::DeleteRoleOutput;
use aws_sdk_lambda::{
    operation::{
        delete_function::DeleteFunctionOutput, get_function::GetFunctionOutput,
        invoke::InvokeOutput, list_functions::ListFunctionsOutput,
        update_function_code::UpdateFunctionCodeOutput,
        update_function_configuration::UpdateFunctionConfigurationOutput,
    },
    primitives::ByteStream,
    types::{Environment, FunctionCode, LastUpdateStatus, State},
};
use aws_sdk_s3::{
    operation::{delete_bucket::DeleteBucketOutput,
 delete_object::DeleteObjectOutput},
```

```
    types::CreateBucketConfiguration,
};
use aws_smithy_types::Blob;
use serde::{ser::SerializeMap, Serialize};
use std::{path::PathBuf, str::FromStr, time::Duration};
use tracing::{debug, info, warn};

/* Operation describes  */
#[derive(Clone, Copy, Debug, Serialize)]
pub enum Operation {
    #[serde(rename = "plus")]
    Plus,
    #[serde(rename = "minus")]
    Minus,
    #[serde(rename = "times")]
    Times,
    #[serde(rename = "divided-by")]
    DividedBy,
}

impl FromStr for Operation {
    type Err = anyhow::Error;

    fn from_str(s: &str) -> Result<Self, Self::Err> {
        match s {
            "plus" => Ok(Operation::Plus),
            "minus" => Ok(Operation::Minus),
            "times" => Ok(Operation::Times),
            "divided-by" => Ok(Operation::DividedBy),
            _ => Err(anyhow!("Unknown operation {s}")),
        }
    }
}

impl ToString for Operation {
    fn to_string(&self) -> String {
        match self {
            Operation::Plus => "plus".to_string(),
            Operation::Minus => "minus".to_string(),
            Operation::Times => "times".to_string(),
            Operation::DividedBy => "divided-by".to_string(),
        }
    }
}
```

```
/**
 * InvokeArgs will be serialized as JSON and sent to the AWS Lambda handler.
 */
#[derive(Debug)]
pub enum InvokeArgs {
    Increment(i32),
    Arithmetic(Operation, i32, i32),
}

impl Serialize for InvokeArgs {
    fn serialize<S>(&self, serializer: S) -> Result<S::Ok, S::Error>
    where
        S: serde::Serializer,
    {
        match self {
            InvokeArgs::Increment(i) => serializer.serialize_i32(*i),
            InvokeArgs::Arithmetic(o, i, j) => {
                let mut map: S::SerializeMap =
 serializer.serialize_map(Some(3))?;
                map.serialize_key(&"op".to_string())?;
                map.serialize_value(&o.to_string())?;
                map.serialize_key(&"i".to_string())?;
                map.serialize_value(&i)?;
                map.serialize_key(&"j".to_string())?;
                map.serialize_value(&j)?;
                map.end()
            }
        }
    }
}

/** A policy document allowing Lambda to execute this function on the account's
 behalf. */
const ROLE_POLICY_DOCUMENT: &str = r#"{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Principal": { "Service": "lambda.amazonaws.com" },
            "Action": "sts:AssumeRole"
        }
    ]
}"#;
```

```
/**
 * A LambdaManager gathers all the resources necessary to run the Lambda example
 scenario.
 * This includes instantiated aws_sdk clients and details of resource names.
 */
pub struct LambdaManager {
    iam_client: aws_sdk_iam::Client,
    lambda_client: aws_sdk_lambda::Client,
    s3_client: aws_sdk_s3::Client,
    lambda_name: String,
    role_name: String,
    bucket: String,
    own_bucket: bool,
}

// These unit type structs provide nominal typing on top of String parameters for
 LambdaManager::new
pub struct LambdaName(pub String);
pub struct RoleName(pub String);
pub struct Bucket(pub String);
pub struct OwnBucket(pub bool);

impl LambdaManager {
    pub fn new(
        iam_client: aws_sdk_iam::Client,
        lambda_client: aws_sdk_lambda::Client,
        s3_client: aws_sdk_s3::Client,
        lambda_name: LambdaName,
        role_name: RoleName,
        bucket: Bucket,
        own_bucket: OwnBucket,
    ) -> Self {
        Self {
            iam_client,
            lambda_client,
            s3_client,
            lambda_name: lambda_name.0,
            role_name: role_name.0,
            bucket: bucket.0,
            own_bucket: own_bucket.0,
        }
    }
```

```
   /**
    * Load the AWS configuration from the environment.
    * Look up lambda_name and bucket if none are given, or generate a random
name if not present in the environment.
    * If the bucket name is provided, the caller needs to have created the
bucket.
    * If the bucket name is generated, it will be created.
    */
   pub async fn load_from_env(lambda_name: Option<String>, bucket:
Option<String>) -> Self {
       let sdk_config = aws_config::load_from_env().await;
       let lambda_name = LambdaName(lambda_name.unwrap_or_else(|| {
           std::env::var("LAMBDA_NAME").unwrap_or_else(|_|
"rust_lambda_example".to_string())
       }));
       let role_name = RoleName(format!("{}_role", lambda_name.0));
       let (bucket, own_bucket) =
           match bucket {
               Some(bucket) => (Bucket(bucket), false),
               None => (
                   Bucket(std::env::var("LAMBDA_BUCKET").unwrap_or_else(|_| {
                       format!("rust-lambda-example-{}", uuid::Uuid::new_v4())
                   })),
                   true,
               ),
           };

       let s3_client = aws_sdk_s3::Client::new(&sdk_config);

       if own_bucket {
           info!("Creating bucket for demo: {}", bucket.0);
           s3_client
               .create_bucket()
               .bucket(bucket.0.clone())
               .create_bucket_configuration(
                   CreateBucketConfiguration::builder()

.location_constraint(aws_sdk_s3::types::BucketLocationConstraint::from(
                           sdk_config.region().unwrap().as_ref(),
                       ))
                       .build(),
               )
               .send()
               .await
```

```
                .unwrap();
        }

        Self::new(
            aws_sdk_iam::Client::new(&sdk_config),
            aws_sdk_lambda::Client::new(&sdk_config),
            s3_client,
            lambda_name,
            role_name,
            bucket,
            OwnBucket(own_bucket),
        )
    }

    // snippet-start:[lambda.rust.scenario.prepare_function]
    /**
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --
output-format Zip`.
     */
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));

        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
            .s3_key(key)
            .build())
```

```
    }
    // snippet-end:[lambda.rust.scenario.prepare_function]

    // snippet-start:[lambda.rust.scenario.create_function]
    /**
     * Create a function, uploading from a zip file.
     */
    pub async fn create_function(&self, zip_file: PathBuf) -> Result<String,
anyhow::Error> {
        let code = self.prepare_function(zip_file, None).await?;

        let key = code.s3_key().unwrap().to_string();

        self.create_role().await;

        let role = self
            .iam_client
            .create_role()
            .role_name(self.role_name.clone())
            .assume_role_policy_document(ROLE_POLICY_DOCUMENT)
            .send()
            .await?;

        info!("Created iam role, waiting 15s for it to become active");
        tokio::time::sleep(Duration::from_secs(15)).await;

        info!("Creating lambda function {}", self.lambda_name);
        let _ = self
            .lambda_client
            .create_function()
            .function_name(self.lambda_name.clone())
            .code(code)
            .role(role.role().map(|r| r.arn()).unwrap_or_default())
            .runtime(aws_sdk_lambda::types::Runtime::Providedal2)
            .handler("_unused")
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        self.lambda_client
            .publish_version()
            .function_name(self.lambda_name.clone())
```

```
            .send()
            .await?;

        Ok(key)
    }
    // snippet-end:[lambda.rust.scenario.create_function]

    /**
     * Create an IAM execution role for the managed Lambda function.
     */
    async fn create_role(&self) {
        info!("Creating execution role for function");
        if let Ok(_response) = self
            .iam_client
            .get_role()
            .role_name(self.role_name.clone())
            .send()
            .await
        {
            let delete_response = self
                .iam_client
                .delete_role()
                .role_name(self.role_name.clone())
                .send()
                .await;
            match delete_response {
                Ok(_) => debug!("Deleted role first"),
                Err(_) => {
                    warn!("Failed to delete role, will probably fail to create
the new role")
                }
            }
        }
    }

    /**
     * Poll `is_function_ready` with a 1-second delay. It returns when the
function is ready or when there's an error checking the function's state.
     */
    pub async fn wait_for_function_ready(&self) -> Result<(), anyhow::Error> {
        info!("Waiting for function");
        while !self.is_function_ready(None).await? {
            info!("Function is not ready, sleeping 1s");
            tokio::time::sleep(Duration::from_secs(1)).await;
```

```
        }
        Ok(())
    }

    /**
     * Check if a Lambda function is ready to be invoked.
     * A Lambda function is ready for this scenario when its state is active and
its LastUpdateStatus is Successful.
     * Additionally, if a sha256 is provided, the function must have that as its
current code hash.
     * Any missing properties or failed requests will be reported as an Err.
     */
    async fn is_function_ready(
        &self,
        expected_code_sha256: Option<&str>,
    ) -> Result<bool, anyhow::Error> {
        match self.get_function().await {
            Ok(func) => {
                if let Some(config) = func.configuration() {
                    if let Some(state) = config.state() {
                        info!(?state, "Checking if function is active");
                        if !matches!(state, State::Active) {
                            return Ok(false);
                        }
                    }
                    match config.last_update_status() {
                        Some(last_update_status) => {
                            info!(?last_update_status, "Checking if function is
ready");
                            match last_update_status {
                                LastUpdateStatus::Successful => {
                                    // continue
                                }
                                LastUpdateStatus::Failed |
LastUpdateStatus::InProgress => {
                                    return Ok(false);
                                }
                                unknown => {
                                    warn!(
                                        status_variant = unknown.as_str(),
                                        "LastUpdateStatus unknown"
                                    );
                                    return Err(anyhow!(
```

```
                                        "Unknown LastUpdateStatus, fn config is
{config:?}"
                                    ));
                                }
                            }
                        }
                        None => {
                            warn!("Missing last update status");
                            return Ok(false);
                        }
                    };
                    if expected_code_sha256.is_none() {
                        return Ok(true);
                    }
                    if let Some(code_sha256) = config.code_sha256() {
                        return Ok(code_sha256 ==
expected_code_sha256.unwrap_or_default());
                    }
                }
            }
            Err(e) => {
                warn!(?e, "Could not get function while waiting");
            }
        }
        Ok(false)
    }

    // snippet-start:[lambda.rust.scenario.get_function]
    /** Get the Lambda function with this Manager's name. */
    pub async fn get_function(&self) -> Result<GetFunctionOutput, anyhow::Error>
{
        info!("Getting lambda function");
        self.lambda_client
            .get_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.get_function]

    // snippet-start:[lambda.rust.scenario.list_functions]
    /** List all Lambda functions in the current Region. */
```

```
    pub async fn list_functions(&self) -> Result<ListFunctionsOutput,
anyhow::Error> {
        info!("Listing lambda functions");
        self.lambda_client
            .list_functions()
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.list_functions]

    // snippet-start:[lambda.rust.scenario.invoke]
    /** Invoke the lambda function using calculator InvokeArgs. */
    pub async fn invoke(&self, args: InvokeArgs) -> Result<InvokeOutput,
anyhow::Error> {
        info!(?args, "Invoking {}", self.lambda_name);
        let payload = serde_json::to_string(&args)?;
        debug!(?payload, "Sending payload");
        self.lambda_client
            .invoke()
            .function_name(self.lambda_name.clone())
            .payload(Blob::new(payload))
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.invoke]

    // snippet-start:[lambda.rust.scenario.update_function_code]
    /** Given a Path to a zip file, update the function's code and wait for the
update to finish. */
    pub async fn update_function_code(
        &self,
        zip_file: PathBuf,
        key: String,
    ) -> Result<UpdateFunctionCodeOutput, anyhow::Error> {
        let function_code = self.prepare_function(zip_file, Some(key)).await?;

        info!("Updating code for {}", self.lambda_name);
        let update = self
            .lambda_client
            .update_function_code()
            .function_name(self.lambda_name.clone())
            .s3_bucket(self.bucket.clone())
```

```
            .s3_key(function_code.s3_key().unwrap().to_string())
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(update)
    }
    // snippet-end:[lambda.rust.scenario.update_function_code]

    // snippet-start:[lambda.rust.scenario.update_function_configuration]
    /** Update the environment for a function. */
    pub async fn update_function_configuration(
        &self,
        environment: Environment,
    ) -> Result<UpdateFunctionConfigurationOutput, anyhow::Error> {
        info!(
            ?environment,
            "Updating environment for {}", self.lambda_name
        );
        let updated = self
            .lambda_client
            .update_function_configuration()
            .function_name(self.lambda_name.clone())
            .environment(environment)
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ref().await?;

        Ok(updated)
    }
    // snippet-end:[lambda.rust.scenario.update_function_configuration]

    // snippet-start:[lambda.rust.scenario.delete_function]
    /** Delete a function and its role, and if possible or necessary, its
associated code object and bucket. */
    pub async fn delete_function(
        &self,
        location: Option<String>,
    ) -> (
        Result<DeleteFunctionOutput, anyhow::Error>,
```

```
        Result<DeleteRoleOutput, anyhow::Error>,
        Option<Result<DeleteObjectOutput, anyhow::Error>>,
    ) {
        info!("Deleting lambda function {}", self.lambda_name);
        let delete_function = self
            .lambda_client
            .delete_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        info!("Deleting iam role {}", self.role_name);
        let delete_role = self
            .iam_client
            .delete_role()
            .role_name(self.role_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        let delete_object: Option<Result<DeleteObjectOutput, anyhow::Error>> =
            if let Some(location) = location {
                info!("Deleting object {location}");
                Some(
                    self.s3_client
                        .delete_object()
                        .bucket(self.bucket.clone())
                        .key(location)
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
            } else {
                info!(?location, "Skipping delete object");
                None
            };

        (delete_function, delete_role, delete_object)
    }
    // snippet-end:[lambda.rust.scenario.delete_function]

    pub async fn cleanup(
        &self,
```

```
        location: Option<String>,
    ) -> (
        (
            Result<DeleteFunctionOutput, anyhow::Error>,
            Result<DeleteRoleOutput, anyhow::Error>,
            Option<Result<DeleteObjectOutput, anyhow::Error>>,
        ),
        Option<Result<DeleteBucketOutput, anyhow::Error>>,
    ) {
        let delete_function = self.delete_function(location).await;

        let delete_bucket = if self.own_bucket {
            info!("Deleting bucket {}", self.bucket);
            if delete_function.2.is_none() ||
 delete_function.2.as_ref().unwrap().is_ok() {
                Some(
                    self.s3_client
                        .delete_bucket()
                        .bucket(self.bucket.clone())
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
            } else {
                None
            }
        } else {
            info!("No bucket to clean up");
            None
        };

        (delete_function, delete_bucket)
    }
}

/**
 * Testing occurs primarily as an integration test running the `scenario` bin
 successfully.
 * Each action relies deeply on the internal workings and state of Amazon Simple
 Storage Service (Amazon S3), Lambda, and IAM working together.
 * It is therefore infeasible to mock the clients to test the individual actions.
 */
#[cfg(test)]
mod test {
```

```
    use super::{InvokeArgs, Operation};
    use serde_json::json;

    /** Make sure that the JSON output of serializing InvokeArgs is what's
 expected by the calculator. */
    #[test]
    fn test_serialize() {
        assert_eq!(json!(InvokeArgs::Increment(5)), 5);
        assert_eq!(
            json!(InvokeArgs::Arithmetic(Operation::Plus, 5, 7)).to_string(),
            r#"{"i":5,"j":7,"op":"plus"}"#.to_string(),
        );
    }
}
```

Um binário para executar o cenário do início ao fim usando sinalizadores de linha de comando para controlar algum comportamento. Este arquivo está como src/bin/scenario.rs no crate.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

/*
## Service actions

Service actions wrap the SDK call, taking a client and any specific parameters
 necessary for the call.

* CreateFunction
* GetFunction
* ListFunctions
* Invoke
* UpdateFunctionCode
* UpdateFunctionConfiguration
* DeleteFunction

## Scenario
A scenario runs at a command prompt and prints output to the user on the result
 of each service action. A scenario can run in one of two ways: straight through,
 printing out progress as it goes, or as an interactive question/answer script.

## Getting started with functions
```

```
Use an SDK to manage AWS Lambda functions: create a function, invoke it, update
 its code, invoke it again, view its output and logs, and delete it.

This scenario uses two Lambda handlers:
_Note: Handlers don't use AWS SDK API calls._

The increment handler is straightforward:

1. It accepts a number, increments it, and returns the new value.
2. It performs simple logging of the result.

The arithmetic handler is more complex:
1. It accepts a set of actions ['plus', 'minus', 'times', 'divided-by'] and two
 numbers, and returns the result of the calculation.
2. It uses an environment variable to control log level (such as DEBUG, INFO,
 WARNING, ERROR).
It logs a few things at different levels, such as:
    * DEBUG: Full event data.
    * INFO: The calculation result.
    * WARN~ING~: When a divide by zero error occurs.
    * This will be the typical `RUST_LOG` variable.


The steps of the scenario are:

1. Create an AWS Identity and Access Management (IAM) role that meets the
 following requirements:
    * Has an assume_role policy that grants 'lambda.amazonaws.com' the
 'sts:AssumeRole' action.
    * Attaches the 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole' managed role.
    * _You must wait for ~10 seconds after the role is created before you can use
 it!_
2. Create a function (CreateFunction) for the increment handler by packaging it
 as a zip and doing one of the following:
    * Adding it with CreateFunction Code.ZipFile.
    * --or--
    * Uploading it to Amazon Simple Storage Service (Amazon S3) and adding it
 with CreateFunction Code.S3Bucket/S3Key.
    * _Note: Zipping the file does not have to be done in code._
    * If you have a waiter, use it to wait until the function is active.
 Otherwise, call GetFunction until State is Active.
3. Invoke the function with a number and print the result.
```

```
4. Update the function (UpdateFunctionCode) to the arithmetic handler by
 packaging it as a zip and doing one of the following:
    * Adding it with UpdateFunctionCode ZipFile.
    * --or--
    * Uploading it to Amazon S3 and adding it with UpdateFunctionCode S3Bucket/
S3Key.
5. Call GetFunction until Configuration.LastUpdateStatus is 'Successful' (or
 'Failed').
6. Update the environment variable by calling UpdateFunctionConfiguration and
 pass it a log level, such as:
    * Environment={'Variables': {'RUST_LOG': 'TRACE'}}
7. Invoke the function with an action from the list and a couple of values.
 Include LogType='Tail' to get logs in the result. Print the result of the
 calculation and the log.
8. [Optional] Invoke the function to provoke a divide-by-zero error and show the
 log result.
9. List all functions for the account, using pagination (ListFunctions).
10. Delete the function (DeleteFunction).
11. Delete the role.

Each step should use the function created in Service Actions to abstract calling
 the SDK.
 */

use aws_sdk_lambda::{operation::invoke::InvokeOutput, types::Environment};
use clap::Parser;
use std::{collections::HashMap, path::PathBuf};
use tracing::{debug, info, warn};
use tracing_subscriber::EnvFilter;

use lambda_code_examples::actions::{
    InvokeArgs::{Arithmetic, Increment},
    LambdaManager, Operation,
};

#[derive(Debug, Parser)]
pub struct Opt {
    /// The AWS Region.
    #[structopt(short, long)]
    pub region: Option<String>,

    // The bucket to use for the FunctionCode.
    #[structopt(short, long)]
    pub bucket: Option<String>,
```

```
    // The name of the Lambda function.
    #[structopt(short, long)]
    pub lambda_name: Option<String>,

    // The number to increment.
    #[structopt(short, long, default_value = "12")]
    pub inc: i32,

    // The left operand.
    #[structopt(long, default_value = "19")]
    pub num_a: i32,

    // The right operand.
    #[structopt(long, default_value = "23")]
    pub num_b: i32,

    // The arithmetic operation.
    #[structopt(short, long, default_value = "plus")]
    pub operation: Operation,

    #[structopt(long)]
    pub cleanup: Option<bool>,

    #[structopt(long)]
    pub no_cleanup: Option<bool>,
}

fn code_path(lambda: &str) -> PathBuf {
    PathBuf::from(format!("../target/lambda/{lambda}/bootstrap.zip"))
}

// snippet-start:[lambda.rust.scenario.log_invoke_output]
fn log_invoke_output(invoke: &InvokeOutput, message: &str) {
    if let Some(payload) = invoke.payload().cloned() {
        let payload = String::from_utf8(payload.into_inner());
        info!(?payload, message);
    } else {
        info!("Could not extract payload")
    }
    if let Some(logs) = invoke.log_result() {
        debug!(?logs, "Invoked function logs")
    } else {
        debug!("Invoked function had no logs")
```

```
    }
}
// snippet-end:[lambda.rust.scenario.log_invoke_output]

async fn main_block(
    opt: &Opt,
    manager: &LambdaManager,
    code_location: String,
) -> Result<(), anyhow::Error> {
    let invoke = manager.invoke(Increment(opt.inc)).await?;
    log_invoke_output(&invoke, "Invoked function configured as increment");

    let update_code = manager
        .update_function_code(code_path("arithmetic"), code_location.clone())
        .await?;

    let code_sha256 = update_code.code_sha256().unwrap_or("Unknown SHA");
    info!(?code_sha256, "Updated function code with arithmetic.zip");

    let arithmetic_args = Arithmetic(opt.operation, opt.num_a, opt.num_b);
    let invoke = manager.invoke(arithmetic_args).await?;
    log_invoke_output(&invoke, "Invoked function configured as arithmetic");

    let update = manager
        .update_function_configuration(
            Environment::builder()
                .set_variables(Some(HashMap::from([(
                    "RUST_LOG".to_string(),
                    "trace".to_string(),
                )])))
                .build(),
        )
        .await?;
    let updated_environment = update.environment();
    info!(?updated_environment, "Updated function configuration");

    let invoke = manager
        .invoke(Arithmetic(opt.operation, opt.num_a, opt.num_b))
        .await?;
    log_invoke_output(
        &invoke,
        "Invoked function configured as arithmetic with increased logging",
    );
```

```
    let invoke = manager
        .invoke(Arithmetic(Operation::DividedBy, opt.num_a, 0))
        .await?;
    log_invoke_output(
        &invoke,
        "Invoked function configured as arithmetic with divide by zero",
    );

    Ok::<(), anyhow::Error>(())
}

#[tokio::main]
async fn main() {
    tracing_subscriber::fmt()
        .without_time()
        .with_file(true)
        .with_line_number(true)
        .with_env_filter(EnvFilter::from_default_env())
        .init();

    let opt = Opt::parse();
    let manager = LambdaManager::load_from_env(opt.lambda_name.clone(),
 opt.bucket.clone()).await;

    let key = match manager.create_function(code_path("increment")).await {
        Ok(init) => {
            info!(?init, "Created function, initially with increment.zip");
            let run_block = main_block(&opt, &manager, init.clone()).await;
            info!(?run_block, "Finished running example, cleaning up");
            Some(init)
        }
        Err(err) => {
            warn!(?err, "Error happened when initializing function");
            None
        }
    };

    if Some(false) == opt.cleanup || Some(true) == opt.no_cleanup {
        info!("Skipping cleanup")
    } else {
        let delete = manager.cleanup(key).await;
        info!(?delete, "Deleted function & cleaned up resources");
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       "Create an AWS Identity and Access Management (IAM) role that grants AWS
Lambda permission to write to logs."
       DATA(lv_policy_document) = `{` &&
           `"Version":"2012-10-17",` &&
                 `"Statement": [` &&
                   `{` &&
                     `"Effect": "Allow",` &&
                     `"Action": [` &&
                       `"sts:AssumeRole"` &&
                     `],` &&
                     `"Principal": {` &&
                       `"Service": [` &&
                         `"lambda.amazonaws.com"` &&
                       `]` &&
```

```
                        `}` &&
                      `}` &&
                    `]` &&
                  `}`.
        TRY.
            DATA(lo_create_role_output) =  lo_iam->createrole(
                    iv_rolename = iv_role_name
                    iv_assumerolepolicydocument = lv_policy_document
                    iv_description = 'Grant lambda permission to write to logs'
                ).
            MESSAGE 'IAM role created.' TYPE 'I'.
            WAIT UP TO 10 SECONDS.            " Make sure that the IAM role is
 ready for use. "
          CATCH /aws1/cx_iamentityalrdyexex.
            MESSAGE 'IAM role already exists.' TYPE 'E'.
          CATCH /aws1/cx_iaminvalidinputex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iammalformedplydocex.
            MESSAGE 'Policy document in the request is malformed.' TYPE 'E'.
        ENDTRY.

        TRY.
            lo_iam->attachrolepolicy(
                iv_rolename  = iv_role_name
                iv_policyarn = 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole'
            ).
            MESSAGE 'Attached policy to the IAM role.' TYPE 'I'.
          CATCH /aws1/cx_iaminvalidinputex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamplynotattachableex.
            MESSAGE 'Service role policies can only be attached to the service-
linked role for their service.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
 modifiable.' TYPE 'E'.
        ENDTRY.

        " Create a Lambda function and upload handler code. "
        " Lambda function performs 'increment' action on a number. "
        TRY.
            lo_lmd->createfunction(
```

```
                iv_functionname = iv_function_name
                iv_runtime = `python3.9`
                iv_role = lo_create_role_output->get_role( )->get_arn( )
                iv_handler = iv_handler
                io_code = io_initial_zip_file
                iv_description = 'AWS Lambda code example'
            ).
          MESSAGE 'Lambda function created.' TYPE 'I'.
        CATCH /aws1/cx_lmdcodestorageexcdex.
          MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
        CATCH /aws1/cx_lmdinvparamvalueex.
          MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
        CATCH /aws1/cx_lmdresourcenotfoundex.
          MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      ENDTRY.

      " Verify the function is in Active state "
      WHILE lo_lmd->getfunction( iv_functionname = iv_function_name )-
>get_configuration( )->ask_state( ) <> 'Active'.
        IF sy-index = 10.
          EXIT.               " Maximum 10 seconds. "
        ENDIF.
        WAIT UP TO 1 SECONDS.
      ENDWHILE.

      "Invoke the function with a single parameter and get results."
      TRY.
          DATA(lv_json) = /aws1/cl_rt_util=>string_to_xstring(
            `{`  &&
              `"action": "increment",`  &&
              `"number": 10` &&
            `}`
          ).
          DATA(lo_initial_invoke_output) =  lo_lmd->invoke(
                     iv_functionname = iv_function_name
                     iv_payload = lv_json
                 ).
          ov_initial_invoke_payload = lo_initial_invoke_output->get_payload( ).
         " ov_initial_invoke_payload is returned for testing purposes. "
          DATA(lo_writer_json) = cl_sxml_string_writer=>create( type =
 if_sxml=>co_xt_json ).
          CALL TRANSFORMATION id SOURCE XML ov_initial_invoke_payload RESULT
 XML lo_writer_json.
```

```
            DATA(lv_result) = cl_abap_codepage=>convert_from( lo_writer_json-
>get_output( ) ).
            MESSAGE 'Lambda function invoked.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvrequestcontex.
            MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
          CATCH /aws1/cx_lmdunsuppedmediatyp00.
            MESSAGE 'Invoke request body does not have JSON as its content type.'
 TYPE 'E'.
        ENDTRY.

        " Update the function code and configure its Lambda environment with an
 environment variable. "
        " Lambda function is updated to perform 'decrement' action also. "
        TRY.
            lo_lmd->updatefunctioncode(
                  iv_functionname = iv_function_name
                  iv_zipfile = io_updated_zip_file
              ).
            WAIT UP TO 10 SECONDS.            " Make sure that the update is
 completed. "
            MESSAGE 'Lambda function code updated.' TYPE 'I'.
          CATCH /aws1/cx_lmdcodestorageexcdex.
            MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        TRY.
            DATA lt_variables TYPE /aws1/
cl_lmdenvironmentvaria00=>tt_environmentvariables.
            DATA ls_variable LIKE LINE OF lt_variables.
            ls_variable-key = 'LOG_LEVEL'.
            ls_variable-value = NEW /aws1/cl_lmdenvironmentvaria00( iv_value =
 'info' ).
            INSERT ls_variable INTO TABLE lt_variables.

            lo_lmd->updatefunctionconfiguration(
                  iv_functionname = iv_function_name
```

```
                  io_environment = NEW /aws1/cl_lmdenvironment( it_variables =
 lt_variables )
             ).
           WAIT UP TO 10 SECONDS.            " Make sure that the update is
 completed. "
           MESSAGE 'Lambda function configuration/settings updated.' TYPE 'I'.
         CATCH /aws1/cx_lmdinvparamvalueex.
           MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
         CATCH /aws1/cx_lmdresourceconflictex.
           MESSAGE 'Resource already exists or another operation is in
 progress.' TYPE 'E'.
         CATCH /aws1/cx_lmdresourcenotfoundex.
           MESSAGE 'The requested resource does not exist.' TYPE 'E'.
       ENDTRY.

       "Invoke the function with new parameters and get results. Display the
 execution log that's returned from the invocation."
       TRY.
           lv_json = /aws1/cl_rt_util=>string_to_xstring(
             `{`  &&
               `"action": "decrement",`  &&
               `"number": 10` &&
             `}`
           ).
           DATA(lo_updated_invoke_output) =  lo_lmd->invoke(
                     iv_functionname = iv_function_name
                     iv_payload = lv_json
                  ).
           ov_updated_invoke_payload = lo_updated_invoke_output->get_payload( ).
          " ov_updated_invoke_payload is returned for testing purposes. "
           lo_writer_json = cl_sxml_string_writer=>create( type =
 if_sxml=>co_xt_json ).
           CALL TRANSFORMATION id SOURCE XML ov_updated_invoke_payload RESULT
 XML lo_writer_json.
           lv_result = cl_abap_codepage=>convert_from( lo_writer_json-
>get_output( ) ).
           MESSAGE 'Lambda function invoked.' TYPE 'I'.
         CATCH /aws1/cx_lmdinvparamvalueex.
           MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
         CATCH /aws1/cx_lmdinvrequestcontex.
           MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
         CATCH /aws1/cx_lmdresourcenotfoundex.
           MESSAGE 'The requested resource does not exist.' TYPE 'E'.
         CATCH /aws1/cx_lmdunsuppedmediatyp00.
```

```
            MESSAGE 'Invoke request body does not have JSON as its content type.'
 TYPE 'E'.
        ENDTRY.

        " List the functions for your account. "
        TRY.
            DATA(lo_list_output) = lo_lmd->listfunctions( ).
            DATA(lt_functions) = lo_list_output->get_functions( ).
            MESSAGE 'Retrieved list of Lambda functions.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
        ENDTRY.

        " Delete the Lambda function. "
        TRY.
            lo_lmd->deletefunction( iv_functionname = iv_function_name ).
            MESSAGE 'Lambda function deleted.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        " Detach role policy. "
        TRY.
            lo_iam->detachrolepolicy(
                iv_rolename  = iv_role_name
                iv_policyarn = 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole'
            ).
            MESSAGE 'Detached policy from the IAM role.' TYPE 'I'.
          CATCH /aws1/cx_iaminvalidinputex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamplynotattachableex.
            MESSAGE 'Service role policies can only be attached to the service-
linked role for their service.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
 modifiable.' TYPE 'E'.
        ENDTRY.

        " Delete the IAM role. "
```

```
        TRY.
            lo_iam->deleterole( iv_rolename = iv_role_name ).
            MESSAGE 'IAM role deleted.' TYPE 'I'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
modifiable.' TYPE 'E'.
        ENDTRY.

      CATCH /aws1/cx_rt_service_generic INTO lo_exception.
        DATA(lv_error) = lo_exception->get_longtext( ).
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos de tecnologia sem servidor para o Lambda usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Lambda com SDKs da AWS.

Exemplos

- Conectando-se a um banco de dados do Amazon RDS em uma função Lambda
- Invocar uma função do Lambda em um trigger do Kinesis
- Invocar uma função do Lambda em um acionador do Amazon S3
- Invocar uma função do Lambda em um acionador do Amazon SNS

- Invocar uma função do Lambda em um trigger do Amazon SQS
- Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis
- Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

Conectando-se a um banco de dados do Amazon RDS em uma função Lambda

O exemplo de código a seguir mostra como implementar uma função Lambda que se conecta a um banco de dados do RDS. A função faz uma solicitação simples ao banco de dados e retorna o resultado.

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
/*
Node.js code here.
*/
// ES6+ example
import { Signer } from "@aws-sdk/rds-signer";
import mysql from 'mysql2/promise';

async function createAuthToken() {
  // Define connection authentication parameters
  const dbinfo = {

    hostname: process.env.ProxyHostName,
    port: process.env.Port,
    username: process.env.DBUserName,
    region: process.env.AWS_REGION,

  }

  // Create RDS Signer object
```

```
  const signer = new Signer(dbinfo);

  // Request authorization token from RDS, specifying the username
  const token = await signer.getAuthToken();
  return token;
}

async function dbOps() {

  // Obtain auth token
  const token = await createAuthToken();
  // Define connection configuration
  let connectionConfig = {
    host: process.env.ProxyHostName,
    user: process.env.DBUserName,
    password: token,
    database: process.env.DBName,
    ssl: 'Amazon RDS'
  }
  // Create the connection to the DB
  const conn = await mysql.createConnection(connectionConfig);
  // Obtain the result of the query
  const [res,] = await conn.execute('select ?+? as sum', [3, 2]);
  return res;

}

export const handler = async (event) => {
  // Execute database flow
  const result = await dbOps();
  // Return result
  return {
    statusCode: 200,
    body: JSON.stringify("The selected sum is: " + result[0].sum)
  }
};
```

Invocar uma função do Lambda em um trigger do Kinesis

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando .NET.

```
using System.Text;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace KinesisIntegrationSampleCode;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task FunctionHandler(KinesisEvent evnt, ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return;
        }
```

```
        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                throw;
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent) error {
 if len(kinesisEvent.Records) == 0 {
  log.Printf("empty Kinesis event received")
  return nil
 }

 for _, record := range kinesisEvent.Records {
  log.Printf("processed Kinesis event with EventId: %v", record.EventID)
  recordDataBytes := record.Kinesis.Data
  recordDataText := string(recordDataBytes)
  log.Printf("record data: %v", recordDataText)
  // TODO: Do interesting work based on the new data
 }
 log.Printf("successfully processed %v records", len(kinesisEvent.Records))
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;

public class Handler implements RequestHandler<KinesisEvent, Void> {
    @Override
    public Void handleRequest(final KinesisEvent event, final Context context) {
        LambdaLogger logger = context.getLogger();
        if (event.getRecords().isEmpty()) {
            logger.log("Empty Kinesis Event received");
            return null;
        }
        for (KinesisEvent.KinesisEventRecord record : event.getRecords()) {
            try {
                logger.log("Processed Event with EventId: "+record.getEventID());
                String data = new String(record.getKinesis().getData().array());
                logger.log("Data:"+ data);
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex) {
                logger.log("An error occurred:"+ex.getMessage());
                throw ex;
            }
        }
        logger.log("Successfully processed:"+event.getRecords().size()+"
 records");
        return null;
    }

}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do Kinesis com o uso do Lambda. JavaScript

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      throw err;
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Consumindo um evento do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
} from "aws-lambda";
```

```
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      throw err;
    }
    logger.info(`Successfully processed ${event.Records.length} records.`);
  }
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Kinesis\KinesisHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler extends KinesisHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handleKinesis(KinesisEvent $event, Context $context): void
    {
        $this->logger->info("Processing records");
        $records = $event->getRecords();
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
```

```
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                throw $e;
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Python.

```
import base64
def lambda_handler(event, context):

    for record in event['Records']:
        try:
            print(f"Processed Kinesis Event - EventID: {record['eventID']}")
            record_data = base64.b64decode(record['kinesis']
['data']).decode('utf-8')
            print(f"Record Data: {record_data}")
            # TODO: Do interesting work based on the new data
        except Exception as e:
            print(f"An error occurred {e}")
            raise e
    print(f"Successfully processed {len(event['Records'])} records.")
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::event::kinesis::KinesisEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) -> Result<(), Error>
 {
    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(());
    }

    event.payload.records.iter().for_each(|record| {
        tracing::info!("EventId:
 {}",record.event_id.as_deref().unwrap_or_default());

        let record_data = std::str::from_utf8(&record.kinesis.data);

        match record_data {
            Ok(data) => {
                // log the record data
                tracing::info!("Data: {}", data);
            }
            Err(e) => {
                tracing::error!("Error: {}", e);
            }
        }
    });

    tracing::info!(
```

```
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Invocar uma função do Lambda em um acionador do Amazon S3

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando .NET.

```
using System.Threading.Tasks;
```

```
using Amazon.Lambda.Core;
using Amazon.S3;
using System;
using Amazon.Lambda.S3Events;
using System.Web;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace S3Integration
{
    public class Function
    {
        private static AmazonS3Client _s3Client;
        public Function() : this(null)
        {
        }

        internal Function(AmazonS3Client s3Client)
        {
            _s3Client = s3Client ?? new AmazonS3Client();
        }

        public async Task<string> Handler(S3Event evt, ILambdaContext context)
        {
            try
            {
                if (evt.Records.Count <= 0)
                {
                    context.Logger.LogLine("Empty S3 Event received");
                    return string.Empty;
                }

                var bucket = evt.Records[0].S3.Bucket.Name;
                var key = HttpUtility.UrlDecode(evt.Records[0].S3.Object.Key);

                context.Logger.LogLine($"Request is for {bucket} and {key}");

                var objectResult = await _s3Client.GetObjectAsync(bucket, key);

                context.Logger.LogLine($"Returning {objectResult.Key}");
```

```
                return objectResult.Key;
            }
            catch (Exception e)
            {
                context.Logger.LogLine($"Error processing request -
 {e.Message}");

                return string.Empty;
            }
        }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

func handler(ctx context.Context, s3Event events.S3Event) error {
 sdkConfig, err := config.LoadDefaultConfig(ctx)
 if err != nil {
  log.Printf("failed to load default config: %s", err)
  return err
```

```
 }
 s3Client := s3.NewFromConfig(sdkConfig)

 for _, record := range s3Event.Records {
  bucket := record.S3.Bucket.Name
  key := record.S3.Object.URLDecodedKey
  headOutput, err := s3Client.HeadObject(ctx, &s3.HeadObjectInput{
   Bucket: &bucket,
   Key:    &key,
  })
  if err != nil {
   log.Printf("error getting head of object %s/%s: %s", bucket, key, err)
   return err
  }
  log.Printf("successfully retrieved %s/%s of type %s", bucket, key,
 *headOutput.ContentType)
 }

 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Java.

```
package example;

import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
```

```
import software.amazon.awssdk.services.s3.S3Client;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.S3Event;
import
 com.amazonaws.services.lambda.runtime.events.models.s3.S3EventNotification.S3EventNotifi

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Handler implements RequestHandler<S3Event, String> {
    private static final Logger logger = LoggerFactory.getLogger(Handler.class);
    @Override
    public String handleRequest(S3Event s3event, Context context) {
        try {
          S3EventNotificationRecord record = s3event.getRecords().get(0);
          String srcBucket = record.getS3().getBucket().getName();
          String srcKey = record.getS3().getObject().getUrlDecodedKey();

          S3Client s3Client = S3Client.builder().build();
          HeadObjectResponse headObject = getHeadObject(s3Client, srcBucket,
 srcKey);

          logger.info("Successfully retrieved " + srcBucket + "/" + srcKey + " of
 type " + headObject.contentType());

          return "Ok";
        } catch (Exception e) {
          throw new RuntimeException(e);
        }
    }

    private HeadObjectResponse getHeadObject(S3Client s3Client, String bucket,
 String key) {
        HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                .bucket(bucket)
                .key(key)
                .build();
        return s3Client.headObject(headObjectRequest);
    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do S3 com o uso do JavaScript Lambda.

```
const aws = require('aws-sdk');

const s3 = new aws.S3({ apiVersion: '2006-03-01' });

exports.handler = async (event, context) => {
    // Get the object from the event and show its content type
    const bucket = event.Records[0].s3.bucket.name;
    const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g,
 ' '));
    const params = {
        Bucket: bucket,
        Key: key,
    };
    try {
        const { ContentType } = await s3.headObject(params).promise();
        console.log('CONTENT TYPE:', ContentType);
        return ContentType;
    } catch (err) {
        console.log(err);
        const message = `Error getting object ${key} from bucket ${bucket}. Make
 sure they exist and your bucket is in the same region as this function.`;
        console.log(message);
        throw new Error(message);
    }
};
```

Consumindo um evento do S3 com o uso do TypeScript Lambda.

```
import { S3Event } from 'aws-lambda';
```

```
import { S3Client, HeadObjectCommand } from '@aws-sdk/client-s3';

const s3 = new S3Client({ region: process.env.AWS_REGION });

export const handler = async (event: S3Event): Promise<string | undefined> => {
  // Get the object from the event and show its content type
  const bucket = event.Records[0].s3.bucket.name;
  const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
  const params = {
    Bucket: bucket,
    Key: key,
  };
  try {
    const { ContentType } = await s3.send(new HeadObjectCommand(params));
    console.log('CONTENT TYPE:', ContentType);
    return ContentType;
  } catch (err) {
    console.log(err);
    const message = `Error getting object ${key} from bucket ${bucket}. Make sure
 they exist and your bucket is in the same region as this function.`;
    console.log(message);
    throw new Error(message);
  }
};
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Python.

```
import json
import urllib.parse
import boto3
```

```
print('Loading function')

s3 = boto3.client('s3')


def lambda_handler(event, context):
    #print("Received event: " + json.dumps(event, indent=2))

    # Get the object from the event and show its content type
    bucket = event['Records'][0]['s3']['bucket']['name']
    key = urllib.parse.unquote_plus(event['Records'][0]['s3']['object']['key'],
 encoding='utf-8')
    try:
        response = s3.get_object(Bucket=bucket, Key=key)
        print("CONTENT TYPE: " + response['ContentType'])
        return response['ContentType']
    except Exception as e:
        print(e)
        print('Error getting object {} from bucket {}. Make sure they exist and
 your bucket is in the same region as this function.'.format(key, bucket))
        raise e
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Rust.

```
use aws_lambda_events::event::s3::S3Event;
use aws_sdk_s3::{Client};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};


/// Main function
#[tokio::main]
```

```
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    // Initialize the AWS SDK for Rust
    let config = aws_config::load_from_env().await;
    let s3_client = Client::new(&config);

    let res = run(service_fn(|request: LambdaEvent<S3Event>| {
        function_handler(&s3_client, request)
    })).await;

    res
}

async fn function_handler(
    s3_client: &Client,
    evt: LambdaEvent<S3Event>
) -> Result<(), Error> {
    tracing::info!(records = ?evt.payload.records.len(), "Received request from
 SQS");

    if evt.payload.records.len() == 0 {
        tracing::info!("Empty S3 event received");
    }

    let bucket = evt.payload.records[0].s3.bucket.name.as_ref().expect("Bucket
 name to exist");
    let key = evt.payload.records[0].s3.object.key.as_ref().expect("Object key to
 exist");

    tracing::info!("Request is for {} and object {}", bucket, key);

    let s3_get_object_result = s3_client
        .get_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await;

    match s3_get_object_result {
```

```
        Ok(_) => tracing::info!("S3 Get Object success, the s3GetObjectResult
 contains a 'body' property of type ByteStream"),
        Err(_) => tracing::info!("Failure with S3 Get Object request")
    }

    Ok(())
}
```

Invocar uma função do Lambda em um acionador do Amazon SNS

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SNSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace SnsIntegration;

public class Function
{
    public async Task FunctionHandler(SNSEvent evnt, ILambdaContext context)
    {
```

```
        foreach (var record in evnt.Records)
        {
            await ProcessRecordAsync(record, context);
        }
        context.Logger.LogInformation("done");
    }

    private async Task ProcessRecordAsync(SNSEvent.SNSRecord record,
 ILambdaContext context)
    {
        try
        {
            context.Logger.LogInformation($"Processed record
 {record.Sns.Message}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Go.

```
package main
```

```
import (
 "context"
 "fmt"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, snsEvent events.SNSEvent) {
 for _, record := range snsEvent.Records {
  processMessage(record)
 }
 fmt.Println("done")
}

func processMessage(record events.SNSEventRecord) {
 message := record.SNS.Message
 fmt.Printf("Processed message: %s\n", message)
 // TODO: Process your record here
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
```

```
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SNSEvent;
import com.amazonaws.services.lambda.runtime.events.SNSEvent.SNSRecord;


import java.util.Iterator;
import java.util.List;

public class SNSEventHandler implements RequestHandler<SNSEvent, Boolean> {
    LambdaLogger logger;

    @Override
    public Boolean handleRequest(SNSEvent event, Context context) {
        logger = context.getLogger();
        List<SNSRecord> records = event.getRecords();
        if (!records.isEmpty()) {
            Iterator<SNSRecord> recordsIter = records.iterator();
            while (recordsIter.hasNext()) {
                processRecord(recordsIter.next());
            }
        }
        return Boolean.TRUE;
    }

    public void processRecord(SNSRecord record) {
        try {
            String message = record.getSNS().getMessage();
            logger.log("message: " + message);
        } catch (Exception e) {
            throw new RuntimeException(e);
        }
    }

}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do SNS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};

async function processMessageAsync(record) {
  try {
    const message = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento do SNS com o TypeScript Lambda usando.

```
import { SNSEvent, Context, SNSHandler, SNSEventRecord } from "aws-lambda";

export const functionHandler: SNSHandler = async (
  event: SNSEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
```

```
  console.info("done");
};

async function processMessageAsync(record: SNSEventRecord): Promise<any> {
  try {
    const message: string = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando PHP.

```
<?php

/*
Since native PHP support for AWS Lambda is not available, we are utilizing Bref's
 PHP functions runtime for AWS Lambda.
For more information on Bref's PHP runtime for Lambda, refer to: https://bref.sh/
docs/runtimes/function

Another approach would be to create a custom runtime.
A practical example can be found here: https://aws.amazon.com/blogs/apn/aws-
lambda-custom-runtime-for-php-a-practical-example/
*/

// Additional composer packages may be required when using Bref or any other PHP
 functions runtime.
```

```
// require __DIR__ . '/vendor/autoload.php';

return function ($event, $context) {
    foreach ($event["Records"] as $record) {
        processMessage($record);
    }
    echo "Done!" . PHP_EOL;
};

function processMessage($record)
{
    try {
        $message = $record['Sns']['Message'];
        echo "Processed Message: {$message}" . PHP_EOL;
    } catch (Exception $e) {
        echo "Error occured: {$e->getMessage()}" . PHP_EOL;
        throw $e;
    }
}
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for record in event['Records']:
        process_message(record)
    print("done")

def process_message(record):
    try:
        message = record['Sns']['Message']
        print(f"Processed message {message}")
```

```
        # TODO; Process your record here

    except Exception as e:
        print("An error occurred")
        raise e
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].map { |record| process_message(record) }
end

def process_message(record)
  message = record['Sns']['Message']
  puts("Processing message: #{message}")
rescue StandardError => e
  puts("Error processing message: #{e}")
  raise
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SNS com o Lambda usando Rust.

```
use aws_lambda_events::event::sns::SnsEvent;
use aws_lambda_events::sns::SnsRecord;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};
use tracing::info;

// Built with the following dependencies:
//  aws_lambda_events = { version = "0.10.0", default-features = false, features
 = ["sns"] }
//  lambda_runtime = "0.8.1"
//  tokio = { version = "1", features = ["macros"] }
//  tracing = { version = "0.1", features = ["log"] }
//  tracing-subscriber = { version = "0.3", default-features = false, features =
 ["fmt"] }

async fn function_handler(event: LambdaEvent<SnsEvent>) -> Result<(), Error> {
    for event in event.payload.records {
        process_record(&event)?;
    }

    Ok(())
}

fn process_record(record: &SnsRecord) -> Result<(), Error> {
    info!("Processing SNS Message: {}", record.sns.message);

    // Implement your record handling code here.

    Ok(())
}

#[tokio::main]
```

```
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace SqsIntegrationSampleCode
{
    public async Task FunctionHandler(SQSEvent evnt, ILambdaContext context)
    {
```

```
        foreach (var message in evnt.Records)
        {
            await ProcessMessageAsync(message, context);
        }

        context.Logger.LogInformation("done");
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        try
        {
            context.Logger.LogInformation($"Processed message {message.Body}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }

    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Go.

```
package integration_sqs_to_lambda

import (
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(event events.SQSEvent) error {
 for _, record := range event.Records {
  err := processMessage(record)
  if err != nil {
   return err
  }
 }
 fmt.Println("done")
 return nil
}

func processMessage(record events.SQSMessage) error {
 fmt.Printf("Processed message %s\n", record.Body)
 // TODO: Do interesting work based on the new message
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando JavaScript.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSEvent.SQSMessage;

public class Function implements RequestHandler<SQSEvent, Void> {
    @Override
    public Void handleRequest(SQSEvent sqsEvent, Context context) {
        for (SQSMessage msg : sqsEvent.getRecords()) {
            processMessage(msg, context);
        }
        context.getLogger().log("done");
        return null;
    }

    private void processMessage(SQSMessage msg, Context context) {
        try {
            context.getLogger().log("Processed message " + msg.getBody());

            // TODO: Do interesting work based on the new message

        } catch (Exception e) {
            context.getLogger().log("An error occurred");
            throw e;
        }

    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento SQS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message) {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento SQS com o TypeScript Lambda usando.

```
import { SQSEvent, Context, SQSHandler, SQSRecord } from "aws-lambda";

export const functionHandler: SQSHandler = async (
  event: SQSEvent,
  context: Context
): Promise<void> => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message: SQSRecord): Promise<any> {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for message in event['Records']:
        process_message(message)
    print("done")

def process_message(message):
    try:
        print(f"Processed message {message['body']}")
        # TODO: Do interesting work based on the new message
    except Exception as err:
        print("An error occurred")
        raise err
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].each do |message|
    process_message(message)
  end
  puts "done"
end

def process_message(message)
  begin
    puts "Processed message #{message['body']}"
    # TODO: Do interesting work based on the new message
  rescue StandardError => err
    puts "An error occurred"
    raise err
  end
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SQS com o Lambda usando Rust.

```
use aws_lambda_events::event::sqs::SqsEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<(), Error> {
    event.payload.records.iter().for_each(|record| {
        // process the record
        tracing::info!("Message body: {}",
 record.body.as_deref().unwrap_or_default())
    });

    Ok(())
}
```

```
#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

Os exemplos de código a seguir mostram como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando o .NET.

```
using System.Text;
using System.Text.Json.Serialization;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
```

```
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace KinesisIntegration;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task<StreamsEventResponse> FunctionHandler(KinesisEvent evnt,
 ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return new StreamsEventResponse();
        }

        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                /* Since we are working with streams, we can return the failed
 item immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                return new StreamsEventResponse
                {
                    BatchItemFailures = new
 List<StreamsEventResponse.BatchItemFailure>
                    {
                        new StreamsEventResponse.BatchItemFailure
 { ItemIdentifier = record.Kinesis.SequenceNumber }
                    }
```

```
                };
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
        return new StreamsEventResponse();
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}

public class StreamsEventResponse
{
    [JsonPropertyName("batchItemFailures")]
    public IList<BatchItemFailure> BatchItemFailures { get; set; }
    public class BatchItemFailure
    {
        [JsonPropertyName("itemIdentifier")]
        public string ItemIdentifier { get; set; }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando Go.

```
package main
```

```
import (
 "context"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, record := range kinesisEvent.Records {
  curRecordSequenceNumber := ""

  // Process your record
  if /* Your record processing condition here */ {
   curRecordSequenceNumber = record.Kinesis.SequenceNumber
  }

  // Add a condition to check if the record processing failed
  if curRecordSequenceNumber != "" {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": curRecordSequenceNumber})
  }
 }

 kinesisBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return kinesisBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;
import com.amazonaws.services.lambda.runtime.events.StreamsEventResponse;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.List;

public class ProcessKinesisRecords implements RequestHandler<KinesisEvent,
 StreamsEventResponse> {

    @Override
    public StreamsEventResponse handleRequest(KinesisEvent input, Context
 context) {

        List<StreamsEventResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<>();
        String curRecordSequenceNumber = "";

        for (KinesisEvent.KinesisEventRecord kinesisEventRecord :
 input.getRecords()) {
            try {
                //Process your record
                KinesisEvent.Record kinesisRecord =
 kinesisEventRecord.getKinesis();
                curRecordSequenceNumber = kinesisRecord.getSequenceNumber();

            } catch (Exception e) {
                /* Since we are working with streams, we can return the failed
 item immediately.
```

```
                    Lambda will immediately begin to retry processing from this
 failed item onwards. */
                batchItemFailures.add(new
 StreamsEventResponse.BatchItemFailure(curRecordSequenceNumber));
                return new StreamsEventResponse(batchItemFailures);
            }
        }

       return new StreamsEventResponse(batchItemFailures);
    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
            Lambda will immediately begin to retry processing from this failed
 item onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
```

```
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Relatando falhas de itens em lote do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
  KinesisStreamBatchResponse,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<KinesisStreamBatchResponse> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
```

```
            Lambda will immediately begin to retry processing from this failed
 item onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  logger.info(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';
```

```
class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $kinesisEvent = new KinesisEvent($event);
        $this->logger->info("Processing records");
        $records = $kinesisEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getSequenceNumber();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");

        // change format for the response
        $failures = array_map(
            fn(string $sequenceNumber) => ['itemIdentifier' => $sequenceNumber],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
```

```
}

$logger = new StderrLogger();
return new Handler($logger);
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Python.

```
def handler(event, context):
    records = event.get("Records")
    curRecordSequenceNumber = ""

    for record in records:
        try:
            # Process your record
            curRecordSequenceNumber = record["kinesis"]["sequenceNumber"]
        except Exception as e:
            # Return failed record's sequence number
            return {"batchItemFailures":[{"itemIdentifier":
 curRecordSequenceNumber}]}

    return {"batchItemFailures":[]}
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relate falhas de itens em lote do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::kinesis::KinesisEvent,
    kinesis::KinesisEventRecord,
    streams::{KinesisBatchItemFailure, KinesisEventResponse},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) ->
 Result<KinesisEventResponse, Error> {
    let mut response = KinesisEventResponse {
        batch_item_failures: vec![],
    };

    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(response);
    }

    for record in &event.payload.records {
        tracing::info!(
            "EventId: {}",
            record.event_id.as_deref().unwrap_or_default()
        );

        let record_processing_result = process_record(record);

        if record_processing_result.is_err() {
            response.batch_item_failures.push(KinesisBatchItemFailure {
                item_identifier: record.kinesis.sequence_number.clone(),
            });
```

```
            /* Since we are working with streams, we can return the failed item
 immediately.
            Lambda will immediately begin to retry processing from this failed
 item onwards. */
            return Ok(response);
        }
    }

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(response)
}

fn process_record(record: &KinesisEventRecord) -> Result<(), Error> {
    let record_data = std::str::from_utf8(record.kinesis.data.as_slice());

    if let Some(err) = record_data.err() {
        tracing::error!("Error: {}", err);
        return Err(Error::from(err));
    }

    let record_data = record_data.unwrap_or_default();

    // do something interesting with the data
    tracing::info!("Data: {}", record_data);

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
```

```
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

Os exemplos de código a seguir mostram como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando o .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri
namespace sqsSample;

public class Function
{
    public async Task<SQSBatchResponse> FunctionHandler(SQSEvent evnt,
 ILambdaContext context)
    {
        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 List<SQSBatchResponse.BatchItemFailure>();
        foreach(var message in evnt.Records)
        {
            try
            {
```

```
                //process your message
                await ProcessMessageAsync(message, context);
            }
            catch (System.Exception)
            {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.Add(new
 SQSBatchResponse.BatchItemFailure{ItemIdentifier=message.MessageId});
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        if (String.IsNullOrEmpty(message.Body))
        {
            throw new Exception("No Body in SQS Message.");
        }
        context.Logger.LogInformation($"Processed message {message.Body}");
        // TODO: Do interesting work based on the new message
        await Task.CompletedTask;
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando Go.

```
package main

import (
 "context"
```

```
 "encoding/json"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, sqsEvent events.SQSEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, message := range sqsEvent.Records {

  if /* Your message processing condition here */ {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": message.MessageId})
  }
 }

 sqsBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return sqsBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
```

```
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSBatchResponse;

import java.util.ArrayList;
import java.util.List;

public class ProcessSQSMessageBatch implements RequestHandler<SQSEvent,
 SQSBatchResponse> {
    @Override
    public SQSBatchResponse handleRequest(SQSEvent sqsEvent, Context context) {

        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<SQSBatchResponse.BatchItemFailure>();
        String messageId = "";
        for (SQSEvent.SQSMessage message : sqsEvent.getRecords()) {
            try {
                //process your message
                messageId = message.getMessageId();
            } catch (Exception e) {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.add(new
 SQSBatchResponse.BatchItemFailure(messageId));
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando PHP.

```
<?php
```

```
use Bref\Context\Context;
use Bref\Event\Sqs\SqsEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $sqsEvent = new SqsEvent($event);
        $this->logger->info("Processing SQS records");
        $records = $sqsEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                // Assuming the SQS message is in JSON format
                $message = json_decode($record->getBody(), true);
                $this->logger->info(json_encode($message));
                // TODO: Implement your custom processing logic here
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getMessageId();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords SQS records");

        // Format failures for the response
        $failures = array_map(
```

```
            fn(string $messageId) => ['itemIdentifier' => $messageId],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);

?>
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Python.

```
import json
def lambda_handler(event, context):
    if event:
        batch_item_failures = []
        sqs_batch_response = {}

        for record in event["Records"]:
            try:
                # process message
            except Exception as e:
                batch_item_failures.append({"itemIdentifier":
 record['messageId']})

        sqs_batch_response["batchItemFailures"] = batch_item_failures
```

```
        return sqs_batch_response
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Ruby.

```
require 'json'

def lambda_handler(event:, context:)
  if event
    batch_item_failures = []
    sqs_batch_response = {}

    event["Records"].each do |record|
      begin
        # process message
      rescue StandardError => e
        batch_item_failures << {"itemIdentifier" => record['messageId']}
      end
    end

    sqs_batch_response["batchItemFailures"] = batch_item_failures
    return sqs_batch_response
  end
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::sqs::{SqsBatchResponse, SqsEvent},
    sqs::{BatchItemFailure, SqsMessage},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn process_record(_: &SqsMessage) -> Result<(), Error> {
    Err(Error::from("Error processing message"))
}

async fn function_handler(event: LambdaEvent<SqsEvent>) ->
 Result<SqsBatchResponse, Error> {
    let mut batch_item_failures = Vec::new();
    for record in event.payload.records {
        match process_record(&record).await {
            Ok(_) => (),
            Err(_) => batch_item_failures.push(BatchItemFailure {
                item_identifier: record.message_id.unwrap(),
            }),
        }
    }

    Ok(SqsBatchResponse {
        batch_item_failures,
    })
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    run(service_fn(function_handler)).await
}
```

Exemplos do Lambda entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Lambda com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma API REST do API Gateway para monitorar dados da COVID-19
- Criar uma API REST de biblioteca de empréstimos
- Criar uma aplicação de mensageiro com o Step Functions
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação de chat websocket com o API Gateway
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
- Chamar uma função do Lambda em um navegador
- Usar o API Gateway para invocar uma função do Lambda
- Usar Step Functions para invocar funções do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma API REST do API Gateway para monitorar dados da COVID-19

O exemplo de código a seguir mostra como criar uma API REST que simula um sistema para monitorar casos diários de COVID-19 nos Estados Unidos, usando dados fictícios.

Python

SDK para Python (Boto3)

Mostra como usar o AWS Chalice com o AWS SDK for Python (Boto3) para criar uma API REST sem servidor que usa o Amazon API Gateway, o AWS Lambda e o Amazon DynamoDB. O exemplo de código a seguir simula um sistema que monitora casos diários de COVID-19 nos Estados Unidos, usando dados fictícios. Aprenda como:

- Usar o AWS Chalice para definir rotas nas funções do Lambda que são chamadas para lidar com solicitações REST provenientes do API Gateway.
- Usar as funções do Lambda para recuperar e armazenar dados em uma tabela do DynamoDB para atender a solicitações REST.
- Definir recursos de função de segurança e estrutura de tabela em um modelo do AWS CloudFormation.
- Use AWS Chalice e CloudFormation para empacotar e implantar todos os recursos necessários.
- Use CloudFormation para limpar todos os recursos criados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- AWS CloudFormation
- DynamoDB
- Lambda

Criar uma API REST de biblioteca de empréstimos

O exemplo de código abaixo mostra como criar uma biblioteca de empréstimos na qual os clientes possam pegar e devolver livros emprestados usando uma API REST com suporte por um banco de dados do Amazon Aurora.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com a API do Amazon Relational Database Service (Amazon RDS) e o AWS Chalice a fim de criar uma API REST com suporte por um banco de dados do Amazon Aurora. O serviço da Web é uma tecnologia sem servidor e representa uma biblioteca de empréstimos simples, na qual os clientes podem pegar e devolver livros emprestados. Aprenda como:

- Crie e gerencie um cluster de banco de dados Aurora com tecnologia sem servidor.
- Utilize o AWS Secrets Manager para gerenciar credenciais de bancos de dados.

- Implemente uma camada de armazenamento de dados que use o Amazon RDS para mover dados para dentro e fora do banco de dados.
- Use o AWS Chalice para implantar uma API REST com tecnologia sem servidor no Amazon API Gateway e no AWS Lambda.
- Use o pacote Requests para enviar solicitações ao serviço Web.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Aurora
- Lambda
- Secrets Manager

Criar uma aplicação de mensageiro com o Step Functions

O exemplo de código a seguir mostra como criar uma aplicação de mensageiro do AWS Step Functions que recupera registros de mensagens de uma tabela de banco de dados.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o AWS Step Functions para criar uma aplicação de mensageiro que recupere registros de mensagens de uma tabela do Amazon DynamoDB e os envia com o Amazon Simple Queue Service (Amazon SQS). A máquina de estado se integra a uma função do AWS Lambda para verificar o banco de dados em busca de mensagens não enviadas.

- Crie uma máquina de estado que recupere e atualize registros de mensagens de uma tabela do Amazon DynamoDB.
- Atualize a definição de máquina de estado para enviar mensagens ao Amazon Simple Queue Service (Amazon SQS).
- Inicie e interrompa execuções da máquina de estado.
- Conecte-se ao Lambda, ao DynamoDB e ao Amazon SQS por meio de uma máquina de estado usando integrações de serviço.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação de chat websocket com o API Gateway

O exemplo de código a seguir mostra como criar uma aplicação de chat que é atendido por uma API de Websocket criada no Amazon API Gateway.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon API Gateway V2 para criar uma API de Websocket que se integra ao AWS Lambda e ao Amazon DynamoDB.

- Crie uma API de Websocket atendida pelo API Gateway.
- Defina um manipulador do Lambda que armazena conexões no DynamoDB e publica mensagens para outros participantes do chat.
- Conecte-se à aplicação de chat websocket e envie mensagens com o pacote Websockets.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Os exemplos de código a seguir mostram como criar uma aplicação que analisa os cartões de comentários dos clientes, os traduz do idioma original, determina seus sentimentos e gera um arquivo de áudio do texto traduzido.

.NET

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly

- Amazon Textract
- Amazon Translate

Java

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";

/**
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );

  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);
```

```
  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";

/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
 */
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
    VoiceId: "Ruth",
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
```

```
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});

  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });

  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Ruby

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.

- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Chamar uma função do Lambda em um navegador

O exemplo de código a seguir mostra como chamar uma função do AWS Lambda em um navegador.

JavaScript

SDK para JavaScript (v2)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

SDK para JavaScript (v3)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário. Essa aplicação usa o AWS SDK for JavaScript v3.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

Usar o API Gateway para invocar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma função do AWS Lambda invocada pelo Amazon API Gateway que envia mensagens de texto de aniversário.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar uma AWS Lambda função usando a API de tempo de JavaScript execução do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Python

SDK para Python (Boto3)

Este exemplo mostra como criar e usar uma API REST do Amazon API Gateway cujo alvo é uma função do AWS Lambda. O manipulador do Lambda mostra como rotear com base em métodos HTTP; como obter dados da string de consulta, do cabeçalho e do corpo e como retornar uma resposta JSON.

- Implante uma função do Lambda.
- Crie uma API REST do API Gateway.
- Crie um recurso REST cujo alvo seja a função do Lambda.
- Conceda permissão para que o API Gateway possa invocar a função do Lambda.
- Use o pacote Requests para enviar solicitações à API REST.

- Limpe todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Lambda

Usar Step Functions para invocar funções do Lambda

Os exemplos de código a seguir mostram como criar um máquina de estado do AWS Step Functions que invoca a funções do AWS Lambda em sequência.

Java

SDK para Java 2.x

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for Java 2.x. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

JavaScript

SDK para JavaScript (v3)

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for JavaScript. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

O Lambda é um serviço computacional que permite executar código sem provisionar ou gerenciar servidores. O Step Functions é um serviço de orquestração sem servidor que permite combinar funções do Lambda e outros serviços da AWS para criar aplicações essenciais aos negócios.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Usar eventos programados para chamar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma AWS Lambda função invocada por um evento EventBridge agendado pela Amazon.

Java

SDK para Java 2.x

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função do Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- EventBridge
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função Lambda usando a API de tempo de execução do JavaScript Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

Python

SDK para Python (Boto3)

Este exemplo mostra como registrar uma AWS Lambda função como alvo de um EventBridge evento programado da Amazon. O manipulador do Lambda grava uma mensagem amigável e os dados completos do evento no Amazon CloudWatch Logs para recuperação posterior.

- Implanta uma função do Lambda

- Cria um evento EventBridge agendado e torna a função Lambda o alvo.
- Concede permissão para permitir a EventBridge invocação da função Lambda.
- Imprime os dados mais recentes do CloudWatch Logs para mostrar o resultado das invocações programadas.
- Limpa todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- CloudWatch Registros
- EventBridge
- Lambda

Exemplos de código para o Amazon Lex usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Lex com um Kit de desenvolvimento de software (SDK) da AWS.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Lex – Mais informações sobre o Amazon Lex.
- Referência da API do Amazon Lex – Detalhes sobre todas as ações disponíveis do Amazon Lex.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Exemplos do Amazon Lex entre serviços usando SDKs da AWS
  - Crie um chatbot do Amazon Lex para engajar os visitantes do seu site

Exemplos do Amazon Lex entre serviços usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Lex com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Crie um chatbot do Amazon Lex para engajar os visitantes do seu site

Crie um chatbot do Amazon Lex para engajar os visitantes do seu site

Os exemplos de código a seguir mostram como criar um chatbot para engajar os visitantes do seu site.

Java

SDK para Java 2.x

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, consulte o exemplo completo Construir um chatbot Amazon Lex no guia do desenvolvedor de AWS SDK for JavaScript.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

Exemplos de código para o Lookout for Vision usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Lookout for Vision com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do Lookout for Vision – Mais informações sobre o Lookout for Vision.
- Referência da API do Lookout for Vision – Detalhes sobre todas as ações disponíveis do Lookout for Vision.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Lookout for Vision

O exemplo de código a seguir mostra como começar a usar o Lookout for Vision.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"""
This example shows how to list your Amazon Lookout for Vision projects.
If you haven't previously created a project in the current AWS Region,
the response is an empty list, however it confirms that you can call the
Lookout for Vision API.
"""
from botocore.exceptions import ClientError
import boto3


class Hello:
    """Hello class for Amazon Lookout for Vision"""

    @staticmethod
    def list_projects(lookoutvision_client):
        """
        Lists information about the projects that are in your AWS account
        and in the current AWS Region.

        : param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            for project in response["Projects"]:
                print("Project: " + project["ProjectName"])
                print("ARN: " + project["ProjectArn"])
                print()
            print("Done!")
        except ClientError as err:
            print(f"Couldn't list projects. \n{err}")
            raise
```

```
def main():
    session = boto3.Session(profile_name="lookoutvision-access")
    lookoutvision_client = session.client("lookoutvision")

    Hello.list_projects(lookoutvision_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a ListProjectsReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações para o Lookout for Vision usando SDKs da AWS
  - Crie um conjunto de dados do Lookout for Vision usando um SDK da AWS
  - Crie um modelo do Lookout for Vision usando um SDK da AWS
  - Crie um projeto do Lookout for Vision usando um SDK da AWS
  - Exclua um conjunto de dados do Lookout for Vision usando um SDK da AWS
  - Exclua um modelo do Lookout for Vision usando um SDK da AWS
  - Exclua um projeto do Lookout for Vision usando um SDK da AWS
  - Descreva um conjunto de dados do Lookout for Vision usando um SDK da AWS
  - Descreva um modelo do Lookout for Vision usando um SDK da AWS
  - Detecte anomalias em uma imagem com um modelo treinado do Lookout for Vision usando um SDK da AWS
  - Liste modelos do Lookout for Vision usando um SDK da AWS
  - Liste projetos do Lookout for Vision usando um SDK da AWS
  - Inicie um modelo do Lookout for Vision usando um SDK da AWS
  - Interrompa um modelo do Lookout for Vision usando um SDK da AWS
- Cenários para o Lookout for Vision usando SDKs da AWS
  - Crie um arquivo de manifesto do Lookout for Vision usando um SDK da AWS

- Crie, treine e inicie um modelo do Lookout for Vision usando um SDK da AWS
- Exporte os conjuntos de dados de um projeto do Lookout for Vision usando um SDK da AWS
- Encontre um projeto do Lookout for Vision com uma tag específica usando um SDK da AWS
- Liste modelos do Lookout for Vision que estão hospedados no momento usando um SDK da AWS

Ações para o Lookout for Vision usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Lookout for Vision com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Lookout for Vision usando SDKs da AWS.

Exemplos

- Crie um conjunto de dados do Lookout for Vision usando um SDK da AWS
- Crie um modelo do Lookout for Vision usando um SDK da AWS
- Crie um projeto do Lookout for Vision usando um SDK da AWS
- Exclua um conjunto de dados do Lookout for Vision usando um SDK da AWS
- Exclua um modelo do Lookout for Vision usando um SDK da AWS
- Exclua um projeto do Lookout for Vision usando um SDK da AWS
- Descreva um conjunto de dados do Lookout for Vision usando um SDK da AWS
- Descreva um modelo do Lookout for Vision usando um SDK da AWS
- Detecte anomalias em uma imagem com um modelo treinado do Lookout for Vision usando um SDK da AWS
- Liste modelos do Lookout for Vision usando um SDK da AWS
- Liste projetos do Lookout for Vision usando um SDK da AWS
- Inicie um modelo do Lookout for Vision usando um SDK da AWS
- Interrompa um modelo do Lookout for Vision usando um SDK da AWS

Crie um conjunto de dados do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como criar um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Criar Conjunto Dados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def create_dataset(lookoutvision_client, project_name, manifest_file,
 dataset_type):
        """
        Creates a new Lookout for Vision dataset

        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        :param project_name: The name of the project in which you want to
                             create a dataset.
        :param bucket: The bucket that contains the manifest file.
        :param manifest_file: The path and name of the manifest file.
        :param dataset_type: The type of the dataset (train or test).
        """
        try:
            bucket, key = manifest_file.replace("s3://", "").split("/", 1)
            logger.info("Creating %s dataset type...", dataset_type)
            dataset = {
                "GroundTruthManifest": {"S3Object": {"Bucket": bucket, "Key":
 key}}
            }
            response = lookoutvision_client.create_dataset(
                ProjectName=project_name,
                DatasetType=dataset_type,
                DatasetSource=dataset,
            )
            logger.info("Dataset Status: %s", response["DatasetMetadata"]
["Status"])
            logger.info(
```

```
                "Dataset Status Message: %s",
                response["DatasetMetadata"]["StatusMessage"],
            )
            logger.info("Dataset Type: %s", response["DatasetMetadata"]
["DatasetType"])

            # Wait until either created or failed.
            finished = False
            status = ""
            dataset_description = {}
            while finished is False:
                dataset_description = lookoutvision_client.describe_dataset(
                    ProjectName=project_name, DatasetType=dataset_type
                )
                status = dataset_description["DatasetDescription"]["Status"]

                if status == "CREATE_IN_PROGRESS":
                    logger.info("Dataset creation in progress...")
                    time.sleep(2)
                elif status == "CREATE_COMPLETE":
                    logger.info("Dataset created.")
                    finished = True
                else:
                    logger.info(
                        "Dataset creation failed: %s",
                        dataset_description["DatasetDescription"]
["StatusMessage"],
                    )
                    finished = True

            if status != "CREATE_COMPLETE":
                message = dataset_description["DatasetDescription"]
["StatusMessage"]
                logger.exception("Couldn't create dataset: %s", message)
                raise Exception(f"Couldn't create dataset: {message}")

        except ClientError:
            logger.exception("Service error: Couldn't create dataset.")
            raise
```

- Para obter detalhes da API, consulte a CreateDatasetReferência da API AWSSDK for Python (Boto3).

Crie um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como criar um modelo do Lookout for Vision.

Para obter mais informações, consulte TreinandoModelo.

Python

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def create_model(
        lookoutvision_client,
        project_name,
        training_results,
        tag_key=None,
        tag_key_value=None,
    ):
        """
        Creates a version of a Lookout for Vision model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project in which you want to create
 a
                             model.
        :param training_results: The Amazon S3 location where training results
 are stored.
        :param tag_key: The key for a tag to add to the model.
        :param tag_key_value - A value associated with the tag_key.
        return: The model status and version.
        """
```

```
        try:
            logger.info("Training model...")
            output_bucket, output_folder = training_results.replace("s3://",
"").split(
                "/", 1
            )
            output_config = {
                "S3Location": {"Bucket": output_bucket, "Prefix": output_folder}
            }
            tags = []
            if tag_key is not None:
                tags = [{"Key": tag_key, "Value": tag_key_value}]

            response = lookoutvision_client.create_model(
                ProjectName=project_name, OutputConfig=output_config, Tags=tags
            )

            logger.info("ARN: %s", response["ModelMetadata"]["ModelArn"])
            logger.info("Version: %s", response["ModelMetadata"]["ModelVersion"])
            logger.info("Started training...")

            print("Training started. Training might take several hours to
complete.")

            # Wait until training completes.
            finished = False
            status = "UNKNOWN"
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name,
                    ModelVersion=response["ModelMetadata"]["ModelVersion"],
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "TRAINING":
                    logger.info("Model training in progress...")
                    time.sleep(600)
                    continue

                if status == "TRAINED":
                    logger.info("Model was successfully trained.")
                else:
                    logger.info(
                        "Model training failed: %s ",
```

```
                        model_description["ModelDescription"]["StatusMessage"],
                    )
                finished = True
        except ClientError:
            logger.exception("Couldn't train model.")
            raise
        else:
            return status, response["ModelMetadata"]["ModelVersion"]
```

- Para obter detalhes da API, consulte a CreateModelReferência da API AWSSDK for Python (Boto3).

Crie um projeto do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como criar um projeto do Lookout for Vision.

Para obter mais informações, consulte CriandoProjeto.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def create_project(lookoutvision_client, project_name):
        """
        Creates a new Lookout for Vision project.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param  project_name: The name for the new project.
        :return project_arn: The ARN of the new project.
        """
```

```
        try:
            logger.info("Creating project: %s", project_name)
            response =
 lookoutvision_client.create_project(ProjectName=project_name)
            project_arn = response["ProjectMetadata"]["ProjectArn"]
            logger.info("project ARN: %s", project_arn)
        except ClientError:
            logger.exception("Couldn't create project %s.", project_name)
            raise
        else:
            return project_arn
```

- Para obter detalhes da API, consulte a CreateProjectReferência da API AWSSDK for Python (Boto3).

Exclua um conjunto de dados do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Excluindo um conjunto de dados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def delete_dataset(lookoutvision_client, project_name, dataset_type):
        """
        Deletes a Lookout for Vision dataset

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
```

```
        :param project_name: The name of the project that contains the dataset
that
                             you want to delete.
        :param dataset_type: The type (train or test) of the dataset that you
                             want to delete.
        """
        try:
            logger.info(
                "Deleting the %s dataset for project %s.", dataset_type,
project_name
            )
            lookoutvision_client.delete_dataset(
                ProjectName=project_name, DatasetType=dataset_type
            )
            logger.info("Dataset deleted.")
        except ClientError:
            logger.exception("Service error: Couldn't delete dataset.")
            raise
```

- Para obter detalhes da API, consulte a DeleteDatasetReferência da API AWSSDK for Python (Boto3).

Exclua um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um modelo do Lookout for Vision.

Para obter mais informações, consulte Excluindo um modelo.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:
```

```
    @staticmethod
    def delete_model(lookoutvision_client, project_name, model_version):
        """
        Deletes a Lookout for Vision model. The model must first be stopped and
can't
        be in training.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the desired
model.
        :param model_version: The version of the model that you want to delete.
        """
        try:
            logger.info("Deleting model: %s", model_version)
            lookoutvision_client.delete_model(
                ProjectName=project_name, ModelVersion=model_version
            )

            model_exists = True
            while model_exists:
                response =
lookoutvision_client.list_models(ProjectName=project_name)

                model_exists = False
                for model in response["Models"]:
                    if model["ModelVersion"] == model_version:
                        model_exists = True

                if model_exists is False:
                    logger.info("Model deleted")
                else:
                    logger.info("Model is being deleted...")
                    time.sleep(2)

            logger.info("Deleted Model: %s", model_version)
        except ClientError:
            logger.exception("Couldn't delete model.")
            raise
```

- Para obter detalhes da API, consulte a DeleteModelReferência da API AWSSDK for Python (Boto3).

Exclua um projeto do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um projeto do Lookout for Vision.

Para obter mais informações, consulte Excluindo um projeto.

Python

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def delete_project(lookoutvision_client, project_name):
        """
        Deletes a Lookout for Vision Model

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that you want to delete.
        """
        try:
            logger.info("Deleting project: %s", project_name)
            response =
 lookoutvision_client.delete_project(ProjectName=project_name)
            logger.info("Deleted project ARN: %s ", response["ProjectArn"])
        except ClientError as err:
            logger.exception("Couldn't delete project %s.", project_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteProjectReferência da API AWSSDK for Python (Boto3).

Descreva um conjunto de dados do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Visualizar conjunto de dados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def describe_dataset(lookoutvision_client, project_name, dataset_type):
        """
        Gets information about a Lookout for Vision dataset.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the dataset
 that
                             you want to describe.
        :param dataset_type: The type (train or test) of the dataset that you
 want
                             to describe.
        """
        try:
            response = lookoutvision_client.describe_dataset(
                ProjectName=project_name, DatasetType=dataset_type
            )
            print(f"Name: {response['DatasetDescription']['ProjectName']}")
            print(f"Type: {response['DatasetDescription']['DatasetType']}")
            print(f"Status: {response['DatasetDescription']['Status']}")
            print(f"Message: {response['DatasetDescription']['StatusMessage']}")
```

```
            print(f"Images: {response['DatasetDescription']['ImageStats']
['Total']}")
            print(f"Labeled: {response['DatasetDescription']['ImageStats']
['Labeled']}")
            print(f"Normal: {response['DatasetDescription']['ImageStats']
['Normal']}")
            print(f"Anomaly: {response['DatasetDescription']['ImageStats']
['Anomaly']}")
        except ClientError:
            logger.exception("Service error: problem listing datasets.")
            raise
        print("Done.")
```

- Para obter detalhes da API, consulte a DescribeDatasetReferência da API AWSSDK for Python (Boto3).

Descreva um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um modelo do Lookout for Vision.

Para obter mais informações, consulte Visualizar modelos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def describe_model(lookoutvision_client, project_name, model_version):
        """
        Shows the performance metrics for a trained model.
```

```
        :param lookoutvision_client: A Boto3 Amazon Lookout for Vision client.
        :param project_name: The name of the project that contains the desired
 model.
        :param model_version: The version of the model.
        """
        response = lookoutvision_client.describe_model(
            ProjectName=project_name, ModelVersion=model_version
        )
        model_description = response["ModelDescription"]
        print(f"\tModel version: {model_description['ModelVersion']}")
        print(f"\tARN: {model_description['ModelArn']}")
        if "Description" in model_description:
            print(f"\tDescription: {model_description['Description']}")
        print(f"\tStatus: {model_description['Status']}")
        print(f"\tMessage: {model_description['StatusMessage']}")
        print(f"\tCreated: {str(model_description['CreationTimestamp'])}")

        if model_description["Status"] in ("TRAINED", "HOSTED"):
            training_start = model_description["CreationTimestamp"]
            training_end = model_description["EvaluationEndTimestamp"]
            duration = training_end - training_start
            print(f"\tTraining duration: {duration}")

            print("\n\tPerformance metrics\n\t-------------------")
            print(f"\tRecall: {model_description['Performance']['Recall']}")
            print(f"\tPrecision: {model_description['Performance']
['Precision']}")
            print(f"\tF1: {model_description['Performance']['F1Score']}")

            training_output_bucket = model_description["OutputConfig"]
["S3Location"][
                "Bucket"
            ]
            prefix = model_description["OutputConfig"]["S3Location"]["Prefix"]
            print(f"\tTraining output: s3://{training_output_bucket}/{prefix}")
```

- Para obter detalhes da API, consulte a DescribeModelReferência da API AWSSDK for Python (Boto3).

Detecte anomalias em uma imagem com um modelo treinado do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como detectar anomalias em uma imagem com um modelo treinado do Lookout for Vision.

Para obter mais informações, consulte Detectar anomalias em uma imagem.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Inference:
    """
    Shows how to detect anomalies in an image using a trained Lookout for Vision
 model.
    """

    @staticmethod
    def detect_anomalies(lookoutvision_client, project_name, model_version,
 photo):
        """
        Calls DetectAnomalies using the supplied project, model version, and
 image.
        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        :param project: The project that contains the model that you want to use.
        :param model_version: The version of the model that you want to use.
        :param photo: The photo that you want to analyze.
        :return: The DetectAnomalyResult object that contains the analysis
 results.
        """

        image_type = imghdr.what(photo)
        if image_type == "jpeg":
            content_type = "image/jpeg"
        elif image_type == "png":
```

```
            content_type = "image/png"
        else:
            logger.info("Image type not valid for %s", photo)
            raise ValueError(
                f"File format not valid. Supply a jpeg or png format file:
{photo}"
            )

        # Get images bytes for call to detect_anomalies.
        with open(photo, "rb") as image:
            response = lookoutvision_client.detect_anomalies(
                ProjectName=project_name,
                ContentType=content_type,
                Body=image.read(),
                ModelVersion=model_version,
            )

        return response["DetectAnomalyResult"]

    @staticmethod
    def download_from_s3(s3_resource, photo):
        """
        Downloads an image from an S3 bucket.

        :param s3_resource: A Boto3 Amazon S3 resource.
        :param photo: The Amazon S3 path of a photo to download.
        return: The local path to the downloaded file.
        """
        try:
            bucket, key = photo.replace("s3://", "").split("/", 1)
            local_file = os.path.basename(photo)
        except ValueError:
            logger.exception("Couldn't get S3 info for %s", photo)
            raise

        try:
            logger.info("Downloading %s", photo)
            s3_resource.Bucket(bucket).download_file(key, local_file)
        except ClientError:
            logger.exception("Couldn't download %s from S3.", photo)
            raise

        return local_file
```

```
    @staticmethod
    def reject_on_classification(image, prediction, confidence_limit):
        """
        Returns True if the anomaly confidence is greater than or equal to
        the supplied confidence limit.
        :param image: The name of the image file that was analyzed.
        :param prediction: The DetectAnomalyResult object returned from
DetectAnomalies.
        :param confidence_limit: The minimum acceptable confidence (float 0 - 1).
        :return: True if the error condition indicates an anomaly, otherwise
False.
        """

        reject = False

        logger.info("Checking classification for %s", image)

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
confidence_limit:
            reject = True
            reject_info = (
                f"Rejected: Anomaly confidence ({prediction['Confidence']:.2%})
is greater"
                f" than limit ({confidence_limit:.2%})"
            )
            logger.info("%s", reject_info)

        if not reject:
            logger.info("No anomalies found.")
        return reject

    @staticmethod
    def reject_on_anomaly_types(
        image, prediction, confidence_limit, anomaly_types_limit
    ):
        """
        Checks if the number of anomaly types is greater than the anomaly types
        limit and if the prediction confidence is greater than the confidence
limit.
        :param image: The name of the image file that was analyzed.
        :param prediction: The DetectAnomalyResult object returned from
DetectAnomalies.
        :param confidence: The minimum acceptable confidence (float 0 - 1).
```

```
        :param anomaly_types_limit: The maximum number of allowable anomaly types
(int).
        :return: True if the error condition indicates an anomaly, otherwise
False.
        """

        logger.info("Checking number of anomaly types for %s", image)

        reject = False

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
confidence_limit:
            anomaly_types = {
                anomaly["Name"]
                for anomaly in prediction["Anomalies"]
                if anomaly["Name"] != "background"
            }

            if len(anomaly_types) > anomaly_types_limit:
                reject = True
                reject_info = (
                    f"Rejected: Anomaly confidence
({prediction['Confidence']:.2%}) "
                    f"is greater than limit ({confidence_limit:.2%}) and "
                    f"the number of anomaly types ({len(anomaly_types)-1}) is "
                    f"greater than the limit ({anomaly_types_limit})"
                )

                logger.info("%s", reject_info)

        if not reject:
            logger.info("No anomalies found.")
        return reject

    @staticmethod
    def reject_on_coverage(
        image, prediction, confidence_limit, anomaly_label, coverage_limit
    ):
        """
        Checks if the coverage area of an anomaly is greater than the coverage
limit and if
        the prediction confidence is greater than the confidence limit.
        :param image: The name of the image file that was analyzed.
```

```
        :param prediction: The DetectAnomalyResult object returned from
 DetectAnomalies.
        :param confidence_limit: The minimum acceptable confidence (float 0-1).
        :anomaly_label: The anomaly label for the type of anomaly that you want
 to check.
        :coverage_limit: The maximum acceptable percentage coverage of an anomaly
 (float 0-1).
        :return: True if the error condition indicates an anomaly, otherwise
 False.
        """

        reject = False

        logger.info("Checking coverage for %s", image)

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
 confidence_limit:
            for anomaly in prediction["Anomalies"]:
                if anomaly["Name"] == anomaly_label and anomaly["PixelAnomaly"][
                    "TotalPercentageArea"
                ] > (coverage_limit):
                    reject = True
                    reject_info = (
                        f"Rejected: Anomaly confidence
 ({prediction['Confidence']:.2%}) "
                        f"is greater than limit ({confidence_limit:.2%}) and
 {anomaly['Name']} "
                        f"coverage ({anomaly['PixelAnomaly']
['TotalPercentageArea']:.2%}) "
                        f"is greater than limit ({coverage_limit:.2%})"
                    )

                    logger.info("%s", reject_info)

        if not reject:
            logger.info("No anomalies found.")

        return reject

    @staticmethod
    def analyze_image(lookoutvision_client, image, config):
        """
        Analyzes an image with an Amazon Lookout for Vision model. Also
        runs a series of checks to determine if the contents of an image
```

```
        should be rejected.
        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        param image: A local image that you want to analyze.
        param config: Configuration information for the model and reject
        limits.
        """

        project = config["project"]
        model_version = config["model_version"]
        confidence_limit = config["confidence_limit"]
        coverage_limit = config["coverage_limit"]
        anomaly_types_limit = config["anomaly_types_limit"]
        anomaly_label = config["anomaly_label"]

        # Get analysis results.
        print(f"Analyzing {image}.")

        prediction = Inference.detect_anomalies(
            lookoutvision_client, project, model_version, image
        )

        anomalies = []

        reject = Inference.reject_on_classification(image, prediction,
confidence_limit)

        if reject:
            anomalies.append("Classification: An anomaly was found.")

        reject = Inference.reject_on_coverage(
            image, prediction, confidence_limit, anomaly_label, coverage_limit
        )

        if reject:
            anomalies.append("Coverage: Anomaly coverage too high.")

        reject = Inference.reject_on_anomaly_types(
            image, prediction, confidence_limit, anomaly_types_limit
        )

        if reject:
            anomalies.append("Anomaly type count: Too many anomaly types found.")
            print()
```

```
        if len(anomalies) > 0:
            print(f"Anomalies found in {image}")
            for anomaly in anomalies:
                print(f"{anomaly}")
        else:
            print(f"No anomalies found in {image}")


def main():
    """
    Detects anomalies in an image file.
    """
    try:
        logging.basicConfig(level=logging.INFO, format="%(levelname)s:
 %(message)s")

        parser = argparse.ArgumentParser(
            description="Find anomalies with Amazon Lookout for Vision."
        )
        parser.add_argument(
            "image",
            help="The file that you want to analyze. Supply a local file path or
 a "
            "path to an S3 object.",
        )
        parser.add_argument(
            "config",
            help=(
                "The configuration JSON file to use. "
                "See https://github.com/awsdocs/aws-doc-sdk-examples/blob/main/"
                "python/example_code/lookoutvision/README.md"
            ),
        )

        args = parser.parse_args()

        session = boto3.Session(profile_name="lookoutvision-access")

        lookoutvision_client = session.client("lookoutvision")
        s3_resource = session.resource("s3")

        # Get configuration information.
        with open(args.config, encoding="utf-8") as config_file:
            config = json.load(config_file)
```

```
        # Download image if located in S3 bucket.
        if args.image.startswith("s3://"):
            image = Inference.download_from_s3(s3_resource, args.image)
        else:
            image = args.image

        Inference.analyze_image(lookoutvision_client, image, config)

        # Delete image, if downloaded from S3 bucket.
        if args.image.startswith("s3://"):
            os.remove(image)

    except ClientError as err:
        print(f"Service error: {err.response['Error']['Message']}")
    except FileNotFoundError as err:
        print(f"The supplied file couldn't be found: {err.filename}.")
    except ValueError as err:
        print(f"A value error occurred: {err}.")
    else:
        print("\nSuccessfully completed analysis.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a DetectAnomaliesReferência da API AWSSDK for Python (Boto3).

Liste modelos do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como listar os modelos do Lookout for Vision.

Para obter mais informações, consulte Visualizar modelos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def describe_models(lookoutvision_client, project_name):
        """
        Gets information about all models in a Lookout for Vision project.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that you want to use.
        """
        try:
            response = lookoutvision_client.list_models(ProjectName=project_name)
            print("Project: " + project_name)
            for model in response["Models"]:
                Models.describe_model(
                    lookoutvision_client, project_name, model["ModelVersion"]
                )
                print()
            print("Done...")
        except ClientError:
            logger.exception("Couldn't list models.")
            raise
```

- Para obter detalhes da API, consulte a ListModelsReferência da API AWSSDK for Python (Boto3).

Liste projetos do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como listar projetos do Lookout for Vision.

Para obter mais informações, consulte Visualizar projetos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def list_projects(lookoutvision_client):
        """
        Lists information about the projects that are in in your AWS account
        and in the current AWS Region.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            for project in response["Projects"]:
                print("Project: " + project["ProjectName"])
                print("\tARN: " + project["ProjectArn"])
                print("\tCreated: " + str(["CreationTimestamp"]))
                print("Datasets")
                project_description = lookoutvision_client.describe_project(
                    ProjectName=project["ProjectName"]
                )
                if not project_description["ProjectDescription"]["Datasets"]:
                    print("\tNo datasets")
                else:
                    for dataset in project_description["ProjectDescription"][
                        "Datasets"
                    ]:
                        print(f"\ttype: {dataset['DatasetType']}")
                        print(f"\tStatus: {dataset['StatusMessage']}")

                print("Models")
```

```
                response_models = lookoutvision_client.list_models(
                    ProjectName=project["ProjectName"]
                )
                if not response_models["Models"]:
                    print("\tNo models")
                else:
                    for model in response_models["Models"]:
                        Models.describe_model(
                            lookoutvision_client,
                            project["ProjectName"],
                            model["ModelVersion"],
                        )


print("--------------------------------------------------------------\n")
            print("Done!")
        except ClientError:
            logger.exception("Problem listing projects.")
            raise
```

- Para obter detalhes da API, consulte a ListProjectsReferência da API AWSSDK for Python (Boto3).

Inicie um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como iniciar um modelo do Lookout for Vision.

Para obter mais informações, consulte Iniciando modelo.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
    def start_model(
        lookoutvision_client, project_name, model_version, min_inference_units
    ):
        """
        Starts the hosting of a Lookout for Vision model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name:  The name of the project that contains the version
 of the
                              model that you want to start hosting.
        :param model_version: The version of the model that you want to start
 hosting.
        :param min_inference_units: The number of inference units to use for
 hosting.
        """
        try:
            logger.info(
                "Starting model version %s for project %s", model_version,
 project_name
            )
            lookoutvision_client.start_model(
                ProjectName=project_name,
                ModelVersion=model_version,
                MinInferenceUnits=min_inference_units,
            )
            print("Starting hosting...")

            status = ""
            finished = False

            # Wait until hosted or failed.
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name, ModelVersion=model_version
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "STARTING_HOSTING":
                    logger.info("Host starting in progress...")
                    time.sleep(10)
```

```
                    continue

                if status == "HOSTED":
                    logger.info("Model is hosted and ready for use.")
                    finished = True
                    continue

                logger.info("Model hosting failed and the model can't be used.")
                finished = True

            if status != "HOSTED":
                logger.error("Error hosting model: %s", status)
                raise Exception(f"Error hosting model: {status}")
        except ClientError:
            logger.exception("Couldn't host model.")
            raise
```

- Para obter detalhes da API, consulte a StartModelReferência da API AWSSDK for Python (Boto3).

Interrompa um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como interromper um modelo do Lookout for Vision.

Para obter mais informações, consulte Interrompendo modelo.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
```

```
    def stop_model(lookoutvision_client, project_name, model_version):
        """
        Stops a running Lookout for Vision Model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the version of
                             the model that you want to stop hosting.
        :param model_version:  The version of the model that you want to stop
hosting.
        """
        try:
            logger.info("Stopping model version %s for %s", model_version,
project_name)
            response = lookoutvision_client.stop_model(
                ProjectName=project_name, ModelVersion=model_version
            )
            logger.info("Stopping hosting...")

            status = response["Status"]
            finished = False

            # Wait until stopped or failed.
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name, ModelVersion=model_version
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "STOPPING_HOSTING":
                    logger.info("Host stopping in progress...")
                    time.sleep(10)
                    continue

                if status == "TRAINED":
                    logger.info("Model is no longer hosted.")
                    finished = True
                    continue

                logger.info("Failed to stop model: %s ", status)
                finished = True

            if status != "TRAINED":
                logger.error("Error stopping model: %s", status)
                raise Exception(f"Error stopping model: {status}")
```

```
        except ClientError:
            logger.exception("Couldn't stop hosting model.")
            raise
```

- Para obter detalhes da API, consulte a StopModelReferência da API AWSSDK for Python (Boto3).

Cenários para o Lookout for Vision usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Lookout for Vision com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie um arquivo de manifesto do Lookout for Vision usando um SDK da AWS
- Crie, treine e inicie um modelo do Lookout for Vision usando um SDK da AWS
- Exporte os conjuntos de dados de um projeto do Lookout for Vision usando um SDK da AWS
- Encontre um projeto do Lookout for Vision com uma tag específica usando um SDK da AWS
- Liste modelos do Lookout for Vision que estão hospedados no momento usando um SDK da AWS

Crie um arquivo de manifesto do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como criar um arquivo de manifesto do Lookout for Vision e carregá-lo para o Amazon S3.

Para obter mais informações, consulte Criando um arquivo de manifesto.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def create_manifest_file_s3(s3_resource, image_s3_path, manifest_s3_path):
        """
        Creates a manifest file and uploads to Amazon S3.

        :param s3_resource: A Boto3 Amazon S3 resource.
        :param image_s3_path: The Amazon S3 path to the images referenced by the
                              manifest file. The images must be in an Amazon S3
 bucket
                              with the following folder structure.
                                s3://doc-example-bucket/<train or test>/
                                    normal/
                                    anomaly/
                              Place normal images in the normal folder and
 anomalous
                              images in the anomaly folder.
        :param manifest_s3_path: The Amazon S3 location in which to store the
 created
                                 manifest file.
        """
        output_manifest_file = "temp.manifest"
        try:
            # Current date and time in manifest file format.
            dttm = datetime.now().strftime("%Y-%m-%dT%H:%M:%S.%f")

            # Get bucket and folder from image and manifest file paths.
            bucket, prefix = image_s3_path.replace("s3://", "").split("/", 1)
            if prefix[-1] != "/":
                prefix += "/"
            manifest_bucket, manifest_prefix = manifest_s3_path.replace(
```

```
                "s3://", ""
            ).split("/", 1)

            with open(output_manifest_file, "w") as mfile:
                logger.info("Creating manifest file")
                src_bucket = s3_resource.Bucket(bucket)

                # Create JSON lines for anomalous images.
                for obj in src_bucket.objects.filter(
                    Prefix=prefix + "anomaly/", Delimiter="/"
                ):
                    image_path = f"s3://{src_bucket.name}/{obj.key}"
                    manifest = Datasets.create_json_line(image_path, "anomaly",
dttm)
                    mfile.write(json.dumps(manifest) + "\n")

                # Create json lines for normal images.
                for obj in src_bucket.objects.filter(
                    Prefix=prefix + "normal/", Delimiter="/"
                ):
                    image_path = f"s3://{src_bucket.name}/{obj.key}"
                    manifest = Datasets.create_json_line(image_path, "normal",
dttm)
                    mfile.write(json.dumps(manifest) + "\n")

            logger.info("Uploading manifest file to %s", manifest_s3_path)
            s3_resource.Bucket(manifest_bucket).upload_file(
                output_manifest_file, manifest_prefix
            )
        except ClientError:
            logger.exception("Error uploading manifest.")
            raise
        except Exception:
            logger.exception("Error uploading manifest.")
            raise
        else:
            logger.info("Completed manifest file creation and upload.")
        finally:
            try:
                os.remove(output_manifest_file)
            except FileNotFoundError:
                pass

    @staticmethod
```

```
    def create_json_line(image, class_name, dttm):
        """
        Creates a single JSON line for an image.

        :param image: The S3 location for the image.
        :param class_name: The class of the image (normal or anomaly)
        :param dttm: The date and time that the JSON is created.
        """

        label = 0
        if class_name == "normal":
            label = 0
        elif class_name == "anomaly":
            label = 1
        else:
            logger.error("Unexpected label value: %s for %s", label, image)
            raise Exception(f"Unexpected label value: {label} for {image}")

        manifest = {
            "source-ref": image,
            "anomaly-label": label,
            "anomaly-label-metadata": {
                "confidence": 1,
                "job-name": "labeling-job/anomaly-label",
                "class-name": class_name,
                "human-annotated": "yes",
                "creation-date": dttm,
                "type": "groundtruth/image-classification",
            },
        }
        return manifest
```

Crie, treine e inicie um modelo do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como criar, treinar e iniciar um modelo do Lookout for Vision.

Python

SDK para Python (Boto3)

Criar e, opcionalmente, iniciar um modelo Amazon Lookout for Vision usando argumentos de linha de comando. O código de exemplo cria um novo projeto, treinando um conjunto de dados, teste opcional em conjunto de dados, e modelo. Depois que o treinamento do modelo for concluído, um script fornecido poderá ser usado para testar o modelo com uma imagem.

Este exemplo requer um conjunto de imagens para treinar o modelo. Você pode encontrar exemplos de imagens de placas de circuito GitHub que você pode usar para treinamento e teste. Para obter detalhes sobre como copiar essas imagens em um bucket do Amazon Simple Storage Service (Amazon S3), consulte Preparar imagens de exemplo.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Lookout for Vision

Exporte os conjuntos de dados de um projeto do Lookout for Vision usando um SDK da AWS

O exemplo de código a seguir mostra como exportar os conjuntos de dados de um projeto do Lookout for Vision.

Para obter mais informações, consulte Exportando conjuntos de dados de um projeto (SDK).

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"""
```

```
Purpose

Shows how to export the datasets (manifest files and images)
from an Amazon Lookout for Vision project to a new Amazon
S3 location.
"""

import argparse
import json
import logging

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def copy_file(s3_resource, source_file, destination_file):
    """
    Copies a file from a source Amazon S3 folder to a destination
    Amazon S3 folder.
    The destination can be in a different S3 bucket.
    :param s3: An Amazon S3 Boto3 resource.
    :param source_file: The Amazon S3 path to the source file.
    :param destination_file: The destination Amazon S3 path for
    the copy operation.
    """

    source_bucket, source_key = source_file.replace("s3://", "").split("/", 1)
    destination_bucket, destination_key = destination_file.replace("s3://",
 "").split(
        "/", 1
    )

    try:
        bucket = s3_resource.Bucket(destination_bucket)
        dest_object = bucket.Object(destination_key)
        dest_object.copy_from(CopySource={"Bucket": source_bucket, "Key":
 source_key})
        dest_object.wait_until_exists()
        logger.info("Copied %s to %s", source_file, destination_file)
    except ClientError as error:
        if error.response["Error"]["Code"] == "404":
            error_message = (
```

```
                f"Failed to copy {source_file} to "
                f"{destination_file}. : {error.response['Error']['Message']}"
            )
            logger.warning(error_message)
            error.response["Error"]["Message"] = error_message
        raise


def upload_manifest_file(s3_resource, manifest_file, destination):
    """
    Uploads a manifest file to a destination Amazon S3 folder.
    :param s3: An Amazon S3 Boto3 resource.
    :param manifest_file: The manifest file that you want to upload.
    :destination: The Amazon S3 folder location to upload the manifest
    file to.
    """

    destination_bucket, destination_key = destination.replace("s3://",
 "").split("/", 1)

    bucket = s3_resource.Bucket(destination_bucket)

    put_data = open(manifest_file, "rb")
    obj = bucket.Object(destination_key + manifest_file)

    try:
        obj.put(Body=put_data)
        obj.wait_until_exists()
        logger.info("Put manifest file '%s' to bucket '%s'.", obj.key,
 obj.bucket_name)
    except ClientError:
        logger.exception(
            "Couldn't put manifest file '%s' to bucket '%s'.", obj.key,
 obj.bucket_name
        )
        raise
    finally:
        if getattr(put_data, "close", None):
            put_data.close()


def get_dataset_types(lookoutvision_client, project):
    """
    Determines the types of the datasets (train or test) in an
```

```
    Amazon Lookout for Vision project.
    :param lookoutvision_client: A Lookout for Vision Boto3 client.
    :param project: The Lookout for Vision project that you want to check.
    :return: The dataset types in the project.
    """

    try:
        response = lookoutvision_client.describe_project(ProjectName=project)

        datasets = []

        for dataset in response["ProjectDescription"]["Datasets"]:
            if dataset["Status"] in ("CREATE_COMPLETE", "UPDATE_COMPLETE"):
                datasets.append(dataset["DatasetType"])
        return datasets

    except lookoutvision_client.exceptions.ResourceNotFoundException:
        logger.exception("Project %s not found.", project)
        raise


def process_json_line(s3_resource, entry, dataset_type, destination):
    """
    Creates a JSON line for a new manifest file, copies image and mask to
    destination.
    :param s3_resource: An Amazon S3 Boto3 resource.
    :param entry: A JSON line from the manifest file.
    :param dataset_type: The type (train or test) of the dataset that
    you want to create the manifest file for.
    :param destination: The destination Amazon S3 folder for the manifest
    file and dataset images.
    :return: A JSON line with details for the destination location.
    """
    entry_json = json.loads(entry)

    print(f"source: {entry_json['source-ref']}")

    # Use existing folder paths to ensure console added image names don't clash.
    bucket, key = entry_json["source-ref"].replace("s3://", "").split("/", 1)
    logger.info("Source location: %s/%s", bucket, key)

    destination_image_location = destination + dataset_type + "/images/" + key

    copy_file(s3_resource, entry_json["source-ref"], destination_image_location)
```

```
    # Update JSON for writing.
    entry_json["source-ref"] = destination_image_location

    if "anomaly-mask-ref" in entry_json:
        source_anomaly_ref = entry_json["anomaly-mask-ref"]
        mask_bucket, mask_key = source_anomaly_ref.replace("s3://",
 "").split("/", 1)

        destination_mask_location = destination + dataset_type + "/masks/" +
 mask_key
        entry_json["anomaly-mask-ref"] = destination_mask_location

        copy_file(s3_resource, source_anomaly_ref, entry_json["anomaly-mask-
ref"])

    return entry_json


def write_manifest_file(
    lookoutvision_client, s3_resource, project, dataset_type, destination
):
    """
    Creates a manifest file for a dataset. Copies the manifest file and
    dataset images (and masks, if present) to the specified Amazon S3
 destination.
    :param lookoutvision_client: A Lookout for Vision Boto3 client.
    :param project: The Lookout for Vision project that you want to use.
    :param dataset_type: The type (train or test) of the dataset that
    you want to create the manifest file for.
    :param destination: The destination Amazon S3 folder for the manifest file
    and dataset images.
    """

    try:
        # Create a reusable Paginator
        paginator = lookoutvision_client.get_paginator("list_dataset_entries")

        # Create a PageIterator from the Paginator
        page_iterator = paginator.paginate(
            ProjectName=project,
            DatasetType=dataset_type,
            PaginationConfig={"PageSize": 100},
        )
```

```
        output_manifest_file = dataset_type + ".manifest"

        # Create manifest file then upload to Amazon S3 with images.
        with open(output_manifest_file, "w", encoding="utf-8") as manifest_file:
            for page in page_iterator:
                for entry in page["DatasetEntries"]:
                    try:
                        entry_json = process_json_line(
                            s3_resource, entry, dataset_type, destination
                        )

                        manifest_file.write(json.dumps(entry_json) + "\n")

                    except ClientError as error:
                        if error.response["Error"]["Code"] == "404":
                            print(error.response["Error"]["Message"])
                            print(f"Excluded JSON line: {entry}")
                        else:
                            raise
        upload_manifest_file(
            s3_resource, output_manifest_file, destination + "datasets/"
        )

    except ClientError:
        logger.exception("Problem getting dataset_entries")
        raise


def export_datasets(lookoutvision_client, s3_resource, project, destination):
    """
    Exports the datasets from an Amazon Lookout for Vision project to a specified
    Amazon S3 destination.
    :param project: The Lookout for Vision project that you want to use.
    :param destination: The destination Amazon S3 folder for the exported
 datasets.
    """
    # Add trailing backslash, if missing.
    destination = destination if destination[-1] == "/" else destination + "/"

    print(f"Exporting project {project} datasets to {destination}.")

    # Get each dataset and export to destination.
```

```
    dataset_types = get_dataset_types(lookoutvision_client, project)
    for dataset in dataset_types:
        logger.info("Copying %s dataset to %s.", dataset, destination)

        write_manifest_file(
            lookoutvision_client, s3_resource, project, dataset, destination
        )

    print("Exported dataset locations")
    for dataset in dataset_types:
        print(f"   {dataset}: {destination}datasets/{dataset}.manifest")

    print("Done.")


def add_arguments(parser):
    """
    Adds command line arguments to the parser.
    :param parser: The command line parser.
    """

    parser.add_argument("project", help="The project that contains the dataset.")
    parser.add_argument("destination", help="The destination Amazon S3 folder.")


def main():
    """
    Exports the datasets from an Amazon Lookout for Vision project to a
    destination Amazon S3 location.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    parser = argparse.ArgumentParser(usage=argparse.SUPPRESS)
    add_arguments(parser)

    args = parser.parse_args()

    try:
        session = boto3.Session(profile_name="lookoutvision-access")
        lookoutvision_client = session.client("lookoutvision")
        s3_resource = session.resource("s3")

        export_datasets(
            lookoutvision_client, s3_resource, args.project, args.destination
        )
```

```
    except ClientError as err:
        logger.exception(err)
        print(f"Failed: {format(err)}")


if __name__ == "__main__":
    main()
```

Encontre um projeto do Lookout for Vision com uma tag específica usando um SDK da AWS

O exemplo de código a seguir mostra como encontrar um projeto do Lookout for Vision com uma tag específica.

Para obter mais informações, consulte Marcando modelos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import argparse
import boto3

from botocore.exceptions import ClientError


logger = logging.getLogger(__name__)


def find_tag(tags, key, value):
    """
    Finds a tag in the supplied list of tags.
```

```
    :param tags: A list of tags associated with a Lookout for Vision model.
    :param key: The tag to search for.
    :param value: The tag key value to search for.
    :return: True if the tag value exists, otherwise False.
    """

    found = False
    for tag in tags:
        if key == tag["Key"]:
            logger.info("\t\tMatch found for tag: %s value: %s.", key, value)
            found = True
            break
    return found


def find_tag_in_projects(lookoutvision_client, key, value):
    """
    Finds Lookout for Vision models tagged with the supplied key and value.

    :param lookoutvision_client: A Boto3 Lookout for Vision client.
    :param key: The tag key to find.
    :param value: The value of the tag that you want to find.
    return: A list of matching model versions (and model projects) that were
 found.
    """
    try:
        found_tags = []
        found = False
        projects = lookoutvision_client.list_projects()
        # Iterate through each project and models within a project.
        for project in projects["Projects"]:
            logger.info("Searching project: %s ...", project["ProjectName"])

            response_models = lookoutvision_client.list_models(
                ProjectName=project["ProjectName"]
            )
            for model in response_models["Models"]:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project["ProjectName"],
                    ModelVersion=model["ModelVersion"],
                )
                tags = lookoutvision_client.list_tags_for_resource(
                    ResourceArn=model_description["ModelDescription"]["ModelArn"]
```

```
                )

                logger.info(
                    "\tSearching model: %s for tag: %s value: %s.",
                    model_description["ModelDescription"]["ModelArn"],
                    key,
                    value,
                )
                if find_tag(tags["Tags"], key, value) is True:
                    found = True
                    logger.info(
                        "\t\tMATCH: Project: %s: model version %s",
                        project["ProjectName"],
                        model_description["ModelDescription"]["ModelVersion"],
                    )
                    found_tags.append(
                        {
                            "Project": project["ProjectName"],
                            "ModelVersion": model_description["ModelDescription"]
[
                                "ModelVersion"
                            ],
                        }
                    )
        if found is False:
            logger.info("No match for tag %s with value %s.", key, value)
    except ClientError:
        logger.exception("Problem finding tags.")
        raise
    else:
        return found_tags


def main():
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    parser = argparse.ArgumentParser(usage=argparse.SUPPRESS)
    parser.add_argument("tag", help="The tag that you want to find.")
    parser.add_argument("value", help="The tag value that you want to find.")
    args = parser.parse_args()
    key = args.tag
    value = args.value

    session = boto3.Session(profile_name="lookoutvision-access")
```

```
    lookoutvision_client = session.client("lookoutvision")

    print(f"Searching your models for tag: {key} with value: {value}.")
    tagged_models = find_tag_in_projects(lookoutvision_client, key, value)

    print("Matched models\n--------------")
    if len(tagged_models) > 0:
        for model in tagged_models:
            print(f"Project: {model['Project']}. model version:
{model['ModelVersion']}")
    else:
        print("No matches found.")


if __name__ == "__main__":
    main()
```

Liste modelos do Lookout for Vision que estão hospedados no momento usando um SDK da AWS

O exemplo de código a seguir mostra como listar modelos do Lookout for Vision que estão hospedados atualmente.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
    def list_hosted(lookoutvision_client):
        """
        Displays a list of models in your account that are currently hosted.
```

```
        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            hosted = 0
            print("Hosted models\n-------------")

            for project in response["Projects"]:
                response_models = lookoutvision_client.list_models(
                    ProjectName=project["ProjectName"]
                )

                for model in response_models["Models"]:
                    model_description = lookoutvision_client.describe_model(
                        ProjectName=project["ProjectName"],
                        ModelVersion=model["ModelVersion"],
                    )

                    if model_description["ModelDescription"]["Status"] ==
"HOSTED":
                        print(
                            f"Project: {project['ProjectName']} Model version: "
                            f"{model['ModelVersion']}"
                        )
                        hosted += 1
            print(f"{hosted} model(s) hosted")
        except ClientError:
            logger.exception("Problem listing hosted models.")
            raise
```

Exemplos de código para o Managed Service for Apache Flink usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Managed Service for Apache Flink com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do Desenvolvedor do Managed Service for Apache Flink – Mais informações sobre Managed Service for Apache Flink.
- Referência da API do Managed Service for Apache Flink – Detalhes sobre todas as ações do Managed Service for Apache Flink.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Managed Service for Apache Flink usando SDKs da AWS
  - Adicione um fluxo de entrada a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Adicione um fluxo de saída a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Crie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Exclua um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Descreva um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Descreva um snapshot do aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Descubra um formato de dados para um fluxo do Managed Service for Apache Flink usando um SDK da AWS
  - inicie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Interrompa um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
  - Atualize um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Gerador de dados para o Managed Service for Apache Flink usando SDKs da AWS
  - Gere um fluxo do Kinesis com um referenciador usando um SDK da AWS
  - Gere um fluxo do Kinesis com anomalias da pressão arterial usando um SDK da AWS

- Gere um fluxo do Kinesis com dados em colunas usando um SDK da AWS
- Gere um fluxo do Kinesis com anomalias da frequência cardíaca usando um SDK da AWS
- Gere um fluxo do Kinesis com hotspots usando um SDK da AWS
- Gere um fluxo do Kinesis com entradas de log usando um SDK da AWS
- Gere um fluxo do Kinesis com dados escalonados usando um SDK da AWS
- Gere um fluxo do Kinesis com dados do ticker de ações da bolsa usando um SDK da AWS
- Gere um fluxo do Kinesis com dois tipos de dados usando um SDK da AWS
- Gere um fluxo do Kinesis com dados de log da web usando um SDK da AWS

Ações para o Managed Service for Apache Flink usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Managed Service for Apache Flink com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Adicione um fluxo de entrada a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Adicione um fluxo de saída a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Crie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Exclua um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Descreva um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Descreva um snapshot do aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Descubra um formato de dados para um fluxo do Managed Service for Apache Flink usando um SDK da AWS
- inicie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Interrompa um aplicativo do Managed Service for Apache Flink usando um SDK da AWS
- Atualize um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

Adicione um fluxo de entrada a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como adicionar um fluxo de entrada a um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def add_input(self, input_prefix, stream_arn, input_schema):
        """
        Adds an input stream to the application. The input stream data is mapped
        to an in-application stream that can be processed by your code running in
        Kinesis Data Analytics.

        :param input_prefix: The prefix prepended to in-application input stream
 names.
        :param stream_arn: The ARN of the input stream.
        :param input_schema: A schema that maps the data in the input stream to
 the
```

```
                            runtime environment. This can be automatically
generated
                            by using `discover_input_schema` or you can create
it
                            yourself.
        :return: Metadata about the newly added input.
        """
        try:
            response = self.analytics_client.add_application_input(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                Input={
                    "NamePrefix": input_prefix,
                    "KinesisStreamsInput": {"ResourceARN": stream_arn},
                    "InputSchema": input_schema,
                },
            )
            self.version_id = response["ApplicationVersionId"]
            logger.info("Add input stream %s to application %s.", stream_arn,
self.name)
        except ClientError:
            logger.exception(
                "Couldn't add input stream %s to application %s.", stream_arn,
self.name
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a AddApplicationInputReferência da API AWSSDK for Python (Boto3).

Adicione um fluxo de saída a um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como adicionar um fluxo de saída a um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def add_output(self, in_app_stream_name, output_arn):
        """
        Adds an output stream to the application. Kinesis Data Analytics maps
 data
        from the specified in-application stream to the output stream.

        :param in_app_stream_name: The name of the in-application stream to map
                                   to the output stream.
        :param output_arn: The ARN of the output stream.
        :return: A list of metadata about the output resources currently assigned
                 to the application.
        """
        try:
            response = self.analytics_client.add_application_output(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                Output={
                    "Name": in_app_stream_name,
```

```
                    "KinesisStreamsOutput": {"ResourceARN": output_arn},
                    "DestinationSchema": {"RecordFormatType": "JSON"},
                },
            )
            outputs = response["OutputDescriptions"]
            self.version_id = response["ApplicationVersionId"]
            logging.info(
                "Added output %s to %s, which now has %s outputs.",
                output_arn,
                self.name,
                len(outputs),
            )
        except ClientError:
            logger.exception("Couldn't add output %s to %s.", output_arn,
 self.name)
            raise
        else:
            return outputs
```

- Para obter detalhes da API, consulte a AddApplicationOutputReferência da API AWSSDK for Python (Boto3).

Crie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como criar um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""
```

```
    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def create(self, app_name, role_arn, env="SQL-1_0"):
        """
        Creates a Kinesis Data Analytics application.

        :param app_name: The name of the application.
        :param role_arn: The ARN of a role that can be assumed by Kinesis Data
                         Analytics and grants needed permissions.
        :param env: The runtime environment of the application, such as SQL. Code
                    uploaded to the application runs in this environment.
        :return: Metadata about the newly created application.
        """
        try:
            response = self.analytics_client.create_application(
                ApplicationName=app_name,
                RuntimeEnvironment=env,
                ServiceExecutionRole=role_arn,
            )
            details = response["ApplicationDetail"]
            self._update_details(details)
            logger.info("Application %s created.", app_name)
        except ClientError:
            logger.exception("Couldn't create application %s.", app_name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a CreateApplicationReferência da API AWSSDK for Python (Boto3).

Exclua um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def delete(self):
        """
        Deletes an application.
        """
        try:
            self.analytics_client.delete_application(
                ApplicationName=self.name, CreateTimestamp=self.create_timestamp
            )
            logger.info("Deleted application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't delete application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteApplicationReferência da API AWSSDK for Python (Boto3).

Descreva um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def describe(self, name):
        """
        Gets metadata about an application.

        :param name: The name of the application to look up.
```

```
        :return: Metadata about the application.
        """
        try:
            response =
 self.analytics_client.describe_application(ApplicationName=name)
            details = response["ApplicationDetail"]
            self._update_details(details)
            logger.info("Got metadata for application %s.", name)
        except ClientError:
            logger.exception("Couldn't get metadata for application %s.", name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a DescribeApplicationReferência da API AWSSDK for Python (Boto3).

Descreva um snapshot do aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como descrever um snapshot do aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
```

```
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def describe_snapshot(self, application_name, snapshot_name):
        """
        Gets metadata about a previously saved application snapshot.

        :param application_name: The name of the application.
        :param snapshot_name: The name of the snapshot.
        :return: Metadata about the snapshot.
        """
        try:
            response = self.analytics_client.describe_application_snapshot(
                ApplicationName=application_name, SnapshotName=snapshot_name
            )
            snapshot = response["SnapshotDetails"]
            logger.info(
                "Got metadata for snapshot %s of application %s.",
                snapshot_name,
                application_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't get metadata for snapshot %s of application %s.",
                snapshot_name,
                application_name,
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte a DescribeApplicationSnapshotReferência da API AWSSDK for Python (Boto3).

Descubra um formato de dados para um fluxo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como descobrir um formato de dados para um fluxo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def discover_input_schema(self, stream_arn, role_arn):
        """
        Discovers a schema that maps data in a stream to a format that is usable
 by
        an application's runtime environment. The stream must be active and have
        enough data moving through it for the service to sample. The returned
 schema
        can be used when you add the stream as an input to the application or you
 can
        write your own schema.

        :param stream_arn: The ARN of the stream to map.
```

```
        :param role_arn: A role that lets Kinesis Data Analytics read from the
stream.
        :return: The discovered schema of the data in the input stream.
        """
        try:
            response = self.analytics_client.discover_input_schema(
                ResourceARN=stream_arn,
                ServiceExecutionRole=role_arn,
                InputStartingPositionConfiguration={"InputStartingPosition":
"NOW"},
            )
            schema = response["InputSchema"]
            logger.info("Discovered input schema for stream %s.", stream_arn)
        except ClientError:
            logger.exception(
                "Couldn't discover input schema for stream %s.", stream_arn
            )
            raise
        else:
            return schema
```

- Para obter detalhes da API, consulte a DiscoverInputSchemaReferência da API AWSSDK for Python (Boto3).

inicie um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como iniciar um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def start(self, input_id):
        """
        Starts an application. After the application is running, it reads from
 the
        specified input stream and runs the application code on the incoming
 data.

        :param input_id: The ID of the input to read.
        """
        try:
            self.analytics_client.start_application(
                ApplicationName=self.name,
                RunConfiguration={
                    "SqlRunConfigurations": [
                        {
                            "InputId": input_id,
                            "InputStartingPositionConfiguration": {
                                "InputStartingPosition": "NOW"
                            },
                        }
                    ]
                },
            )
            logger.info("Started application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't start application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a StartApplicationReferência da API AWSSDK for Python (Boto3).

Interrompa um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como interromper um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def stop(self):
        """
        Stops an application. This stops the application from processing data but
        does not delete any resources.
        """
        try:
            self.analytics_client.stop_application(ApplicationName=self.name)
            logger.info("Stopping application %s.", self.name)
```

```
        except ClientError:
            logger.exception("Couldn't stop application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a StopApplicationReferência da API AWSSDK for Python (Boto3).

Atualize um aplicativo do Managed Service for Apache Flink usando um SDK da AWS

O exemplo de código a seguir mostra como atualizar um aplicativo do Managed Service for Apache Flink.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo atualiza o código que é executado em uma aplicação existente.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None
```

```
    def update_code(self, code):
        """
        Updates the code that runs in the application. The code must run in the
        runtime environment of the application, such as SQL. Application code
        typically reads data from in-application streams and transforms it in
some way.

        :param code: The code to upload. This completely replaces any existing
code
                     in the application.
        :return: Metadata about the application.
        """
        try:
            response = self.analytics_client.update_application(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                ApplicationConfigurationUpdate={
                    "ApplicationCodeConfigurationUpdate": {
                        "CodeContentTypeUpdate": "PLAINTEXT",
                        "CodeContentUpdate": {"TextContentUpdate": code},
                    }
                },
            )
            details = response["ApplicationDetail"]
            self.version_id = details["ApplicationVersionId"]
            logger.info("Update code for application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't update code for application %s.",
self.name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a UpdateApplicationReferência da API AWSSDK for Python (Boto3).

Gerador de dados para o Managed Service for Apache Flink usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Managed Service for Apache Flink com SDKs da AWS.

Exemplos

- Gere um fluxo do Kinesis com um referenciador usando um SDK da AWS
- Gere um fluxo do Kinesis com anomalias da pressão arterial usando um SDK da AWS
- Gere um fluxo do Kinesis com dados em colunas usando um SDK da AWS
- Gere um fluxo do Kinesis com anomalias da frequência cardíaca usando um SDK da AWS
- Gere um fluxo do Kinesis com hotspots usando um SDK da AWS
- Gere um fluxo do Kinesis com entradas de log usando um SDK da AWS
- Gere um fluxo do Kinesis com dados escalonados usando um SDK da AWS
- Gere um fluxo do Kinesis com dados do ticker de ações da bolsa usando um SDK da AWS
- Gere um fluxo do Kinesis com dois tipos de dados usando um SDK da AWS
- Gere um fluxo do Kinesis com dados de log da web usando um SDK da AWS

Gere um fluxo do Kinesis com um referenciador usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com um referenciador.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3
```

```
STREAM_NAME = "ExampleInputStream"


def get_data():
    return {"REFERRER": "http://www.amazon.com"}


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com anomalias da pressão arterial usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com anomalias da pressão arterial.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
from enum import Enum
import json
import random
import boto3
```

```
STREAM_NAME = "ExampleInputStream"


class PressureType(Enum):
    low = "LOW"
    normal = "NORMAL"
    high = "HIGH"


def get_blood_pressure(pressure_type):
    pressure = {"BloodPressureLevel": pressure_type.value}
    if pressure_type == PressureType.low:
        pressure["Systolic"] = random.randint(50, 80)
        pressure["Diastolic"] = random.randint(30, 50)
    elif pressure_type == PressureType.normal:
        pressure["Systolic"] = random.randint(90, 120)
        pressure["Diastolic"] = random.randint(60, 80)
    elif pressure_type == PressureType.high:
        pressure["Systolic"] = random.randint(130, 200)
        pressure["Diastolic"] = random.randint(90, 150)
    else:
        raise TypeError
    return pressure


def generate(stream_name, kinesis_client):
    while True:
        rnd = random.random()
        pressure_type = (
            PressureType.low
            if rnd < 0.005
            else PressureType.high
            if rnd > 0.995
            else PressureType.normal
        )
        blood_pressure = get_blood_pressure(pressure_type)
        print(blood_pressure)
        kinesis_client.put_record(
            StreamName=stream_name,
            Data=json.dumps(blood_pressure),
            PartitionKey="partitionkey",
        )
```

```
if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com dados em colunas usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com dados em colunas.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {"Col_A": "a", "Col_B": "b", "Col_C": "c", "Col_E_Unstructured":
 "x,y,z"}


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )
```

```
if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com anomalias da frequência cardíaca usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com anomalias da frequência cardíaca.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
from enum import Enum
import json
import random
import boto3

STREAM_NAME = "ExampleInputStream"


class RateType(Enum):
    normal = "NORMAL"
    high = "HIGH"


def get_heart_rate(rate_type):
    if rate_type == RateType.normal:
        rate = random.randint(60, 100)
    elif rate_type == RateType.high:
        rate = random.randint(150, 200)
    else:
        raise TypeError
```

```
    return {"heartRate": rate, "rateType": rate_type.value}


def generate(stream_name, kinesis_client, output=True):
    while True:
        rnd = random.random()
        rate_type = RateType.high if rnd < 0.01 else RateType.normal
        heart_rate = get_heart_rate(rate_type)
        if output:
            print(heart_rate)
        kinesis_client.put_record(
            StreamName=stream_name,
            Data=json.dumps(heart_rate),
            PartitionKey="partitionkey",
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com hotspots usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com hotspots.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
from pprint import pprint
import random
import time
import boto3
```

```
STREAM_NAME = "ExampleInputStream"


def get_hotspot(field, spot_size):
    hotspot = {
        "left": field["left"] + random.random() * (field["width"] - spot_size),
        "width": spot_size,
        "top": field["top"] + random.random() * (field["height"] - spot_size),
        "height": spot_size,
    }
    return hotspot


def get_record(field, hotspot, hotspot_weight):
    rectangle = hotspot if random.random() < hotspot_weight else field
    point = {
        "x": rectangle["left"] + random.random() * rectangle["width"],
        "y": rectangle["top"] + random.random() * rectangle["height"],
        "is_hot": "Y" if rectangle is hotspot else "N",
    }
    return {"Data": json.dumps(point), "PartitionKey": "partition_key"}


def generate(
    stream_name, field, hotspot_size, hotspot_weight, batch_size, kinesis_client
):
    """
    Generates points used as input to a hotspot detection algorithm.
    With probability hotspot_weight (20%), a point is drawn from the hotspot;
    otherwise, it is drawn from the base field. The location of the hotspot
    changes for every 1000 points generated.
    """
    points_generated = 0
    hotspot = None
    while True:
        if points_generated % 1000 == 0:
            hotspot = get_hotspot(field, hotspot_size)
        records = [
            get_record(field, hotspot, hotspot_weight) for _ in range(batch_size)
        ]
        points_generated += len(records)
        pprint(records)
        kinesis_client.put_records(StreamName=stream_name, Records=records)
```

```
        time.sleep(0.1)


if __name__ == "__main__":
    generate(
        stream_name=STREAM_NAME,
        field={"left": 0, "width": 10, "top": 0, "height": 10},
        hotspot_size=1,
        hotspot_weight=0.2,
        batch_size=10,
        kinesis_client=boto3.client("kinesis"),
    )
```

Gere um fluxo do Kinesis com entradas de log usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com entradas de log.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {
        "LOGENTRY": "203.0.113.24 - - [25/Mar/2018:15:25:37 -0700] "
        '"GET /index.php HTTP/1.1" 200 125 "-" '
        '"Mozilla/5.0 [en] Gecko/20100101 Firefox/52.0"'
```

```
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com dados escalonados usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com dados escalonados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import datetime
import json
import random
import time
import boto3

STREAM_NAME = "ExampleInputStream"
```

```
def get_data():
    event_time = datetime.datetime.utcnow() - datetime.timedelta(seconds=10)
    return {
        "EVENT_TIME": event_time.isoformat(),
        "TICKER": random.choice(["AAPL", "AMZN", "MSFT", "INTC", "TBV"]),
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        # Send six records, ten seconds apart, with the same event time and
 ticker
        for _ in range(6):
            print(data)
            kinesis_client.put_record(
                StreamName=stream_name,
                Data=json.dumps(data),
                PartitionKey="partitionkey",
            )
            time.sleep(10)


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com dados do ticker de ações da bolsa usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com dados do ticker de ações da bolsa.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import datetime
import json
import random
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {
        "EVENT_TIME": datetime.datetime.now().isoformat(),
        "TICKER": random.choice(["AAPL", "AMZN", "MSFT", "INTC", "TBV"]),
        "PRICE": round(random.random() * 100, 2),
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com dois tipos de dados usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com dois tipos de dados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import random
import boto3

STREAM_NAME = "OrdersAndTradesStream"
PARTITION_KEY = "partition_key"


def get_order(order_id, ticker):
    return {
        "RecordType": "Order",
        "Oid": order_id,
        "Oticker": ticker,
        "Oprice": random.randint(500, 10000),
        "Otype": "Sell",
    }


def get_trade(order_id, trade_id, ticker):
    return {
        "RecordType": "Trade",
        "Tid": trade_id,
        "Toid": order_id,
        "Tticker": ticker,
        "Tprice": random.randint(0, 3000),
    }


def generate(stream_name, kinesis_client):
    order_id = 1
    while True:
```

```
        ticker = random.choice(["AAAA", "BBBB", "CCCC"])
        order = get_order(order_id, ticker)
        print(order)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(order),
 PartitionKey=PARTITION_KEY
        )
        for trade_id in range(1, random.randint(0, 6)):
            trade = get_trade(order_id, trade_id, ticker)
            print(trade)
            kinesis_client.put_record(
                StreamName=stream_name,
                Data=json.dumps(trade),
                PartitionKey=PARTITION_KEY,
            )
        order_id += 1


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gere um fluxo do Kinesis com dados de log da web usando um SDK da AWS

O exemplo de código a seguir mostra como gerar um fluxo do Kinesis com dados de logs da web.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"
```

```
def get_data():
    return {
        "log": "192.168.254.30 - John [24/May/2004:22:01:02 -0700] "
        '"GET /icons/apache_pb.gif HTTP/1.1" 304 0'
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Exemplos de código para MediaConvert usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Elemental MediaConvert com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- MediaConvert Guia do usuário — Mais informações sobre MediaConvert.
- MediaConvert Referência da API — Detalhes sobre todas as MediaConvert ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá MediaConvert

O exemplo de código a seguir mostra como começar a usar o AWS Elemental MediaConvert.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.MediaConvert;
using Amazon.MediaConvert.Model;

namespace MediaConvertActions;

public static class HelloMediaConvert
{
    static async Task Main(string[] args)
    {
        // Create the client using the default profile.
        var mediaConvertClient = new AmazonMediaConvertClient();

        Console.WriteLine($"Hello AWS Elemental MediaConvert! Your MediaConvert
 Endpoints are:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the MediaConvert endpoints.
        var response = await mediaConvertClient.DescribeEndpointsAsync(
            new DescribeEndpointsRequest()
            );

        foreach (var endPoint in response.Endpoints)
        {
            Console.WriteLine($"\tEndPoint: {endPoint.Url}");
            Console.WriteLine();
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte DescribeEndpointsa Referência AWS SDK for .NET da API.

Exemplos de código

- Ações para MediaConvert usar AWS SDKs
  - Crie um trabalho de MediaConvert transcodificação usando um SDK AWS
  - Consiga um trabalho de MediaConvert transcodificação usando um SDK AWS
  - Listar trabalhos de MediaConvert transcodificação usando um SDK AWS

Ações para MediaConvert usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Elemental MediaConvert com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um trabalho de MediaConvert transcodificação usando um SDK AWS
- Consiga um trabalho de MediaConvert transcodificação usando um SDK AWS
- Listar trabalhos de MediaConvert transcodificação usando um SDK AWS

Crie um trabalho de MediaConvert transcodificação usando um SDK AWS

O exemplo de código a seguir mostra como criar um trabalho de transcodificação AWS Elemental MediaConvert.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-
role-in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];

        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or
 set it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert
 endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
            DescribeEndpointsRequest describeRequest = new
 DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
 client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };
```

```
        AmazonMediaConvertClient mcClient = new
 AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Creating job for input file {fileInput}.");
        var jobId = await wrapper.CreateJob(mediaConvertRole!, fileInput!,
 fileOutput!);
        Console.WriteLine($"Created job with Job ID: {jobId}");
        Console.WriteLine(new string('-', 80));
```

Crie o trabalho usando o método wrapper e retorne o ID do trabalho.

```
    /// <summary>
    /// Create a job to convert a media file.
    /// </summary>
    /// <param name="mediaConvertRole">The Amazon Resource Name (ARN) of the
 media convert role, as specified here:
    /// https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-role-
in-mediaconvert-configured.html</param>
    /// <param name="fileInput">The Amazon Simple Storage Service (Amazon S3)
 location of the input media file.</param>
    /// <param name="fileOutput">The Amazon S3 location for the output media
 file.</param>
    /// <returns>The ID of the new job.</returns>
    public async Task<string> CreateJob(string mediaConvertRole, string
 fileInput,
        string fileOutput)
    {
        CreateJobRequest createJobRequest = new CreateJobRequest
        {
            Role = mediaConvertRole
        };

        createJobRequest.UserMetadata.Add("Customer", "Amazon");

        JobSettings jobSettings = new JobSettings
        {
            AdAvailOffset = 0,
```

```
            TimecodeConfig = new TimecodeConfig
            {
                Source = TimecodeSource.EMBEDDED
            }
        };
        createJobRequest.Settings = jobSettings;

        #region OutputGroup

        OutputGroup ofg = new OutputGroup
        {
            Name = "File Group",
            OutputGroupSettings = new OutputGroupSettings
            {
                Type = OutputGroupType.FILE_GROUP_SETTINGS,
                FileGroupSettings = new FileGroupSettings
                {
                    Destination = fileOutput
                }
            }
        };

        Output output = new Output
        {
            NameModifier = "_1"
        };

        #region VideoDescription

        VideoDescription vdes = new VideoDescription
        {
            ScalingBehavior = ScalingBehavior.DEFAULT,
            TimecodeInsertion = VideoTimecodeInsertion.DISABLED,
            AntiAlias = AntiAlias.ENABLED,
            Sharpness = 50,
            AfdSignaling = AfdSignaling.NONE,
            DropFrameTimecode = DropFrameTimecode.ENABLED,
            RespondToAfd = RespondToAfd.NONE,
            ColorMetadata = ColorMetadata.INSERT,
            CodecSettings = new VideoCodecSettings
            {
                Codec = VideoCodec.H_264
            }
        };
```

```
        output.VideoDescription = vdes;

        H264Settings h264 = new H264Settings
        {
            InterlaceMode = H264InterlaceMode.PROGRESSIVE,
            NumberReferenceFrames = 3,
            Syntax = H264Syntax.DEFAULT,
            Softness = 0,
            GopClosedCadence = 1,
            GopSize = 90,
            Slices = 1,
            GopBReference = H264GopBReference.DISABLED,
            SlowPal = H264SlowPal.DISABLED,
            SpatialAdaptiveQuantization =
H264SpatialAdaptiveQuantization.ENABLED,
            TemporalAdaptiveQuantization =
H264TemporalAdaptiveQuantization.ENABLED,
            FlickerAdaptiveQuantization =
H264FlickerAdaptiveQuantization.DISABLED,
            EntropyEncoding = H264EntropyEncoding.CABAC,
            Bitrate = 5000000,
            FramerateControl = H264FramerateControl.SPECIFIED,
            RateControlMode = H264RateControlMode.CBR,
            CodecProfile = H264CodecProfile.MAIN,
            Telecine = H264Telecine.NONE,
            MinIInterval = 0,
            AdaptiveQuantization = H264AdaptiveQuantization.HIGH,
            CodecLevel = H264CodecLevel.AUTO,
            FieldEncoding = H264FieldEncoding.PAFF,
            SceneChangeDetect = H264SceneChangeDetect.ENABLED,
            QualityTuningLevel = H264QualityTuningLevel.SINGLE_PASS,
            FramerateConversionAlgorithm =
                H264FramerateConversionAlgorithm.DUPLICATE_DROP,
            UnregisteredSeiTimecode = H264UnregisteredSeiTimecode.DISABLED,
            GopSizeUnits = H264GopSizeUnits.FRAMES,
            ParControl = H264ParControl.SPECIFIED,
            NumberBFramesBetweenReferenceFrames = 2,
            RepeatPps = H264RepeatPps.DISABLED,
            FramerateNumerator = 30,
            FramerateDenominator = 1,
            ParNumerator = 1,
            ParDenominator = 1
        };
        output.VideoDescription.CodecSettings.H264Settings = h264;
```

```
        #endregion VideoDescription

        #region AudioDescription

        AudioDescription ades = new AudioDescription
        {
            LanguageCodeControl = AudioLanguageCodeControl.FOLLOW_INPUT,
            // This name matches one specified in the following Inputs.
            AudioSourceName = "Audio Selector 1",
            CodecSettings = new AudioCodecSettings
            {
                Codec = AudioCodec.AAC
            }
        };

        AacSettings aac = new AacSettings
        {
            AudioDescriptionBroadcasterMix =
AacAudioDescriptionBroadcasterMix.NORMAL,
            RateControlMode = AacRateControlMode.CBR,
            CodecProfile = AacCodecProfile.LC,
            CodingMode = AacCodingMode.CODING_MODE_2_0,
            RawFormat = AacRawFormat.NONE,
            SampleRate = 48000,
            Specification = AacSpecification.MPEG4,
            Bitrate = 64000
        };
        ades.CodecSettings.AacSettings = aac;
        output.AudioDescriptions.Add(ades);

        #endregion AudioDescription

        #region Mp4 Container

        output.ContainerSettings = new ContainerSettings
        {
            Container = ContainerType.MP4
        };
        Mp4Settings mp4 = new Mp4Settings
        {
            CslgAtom = Mp4CslgAtom.INCLUDE,
            FreeSpaceBox = Mp4FreeSpaceBox.EXCLUDE,
            MoovPlacement = Mp4MoovPlacement.PROGRESSIVE_DOWNLOAD
```

```
        };
        output.ContainerSettings.Mp4Settings = mp4;

        #endregion Mp4 Container

        ofg.Outputs.Add(output);
        createJobRequest.Settings.OutputGroups.Add(ofg);

        #endregion OutputGroup

        #region Input

        Input input = new Input
        {
            FilterEnable = InputFilterEnable.AUTO,
            PsiControl = InputPsiControl.USE_PSI,
            FilterStrength = 0,
            DeblockFilter = InputDeblockFilter.DISABLED,
            DenoiseFilter = InputDenoiseFilter.DISABLED,
            TimecodeSource = InputTimecodeSource.EMBEDDED,
            FileInput = fileInput
        };

        AudioSelector audsel = new AudioSelector
        {
            Offset = 0,
            DefaultSelection = AudioDefaultSelection.NOT_DEFAULT,
            ProgramSelection = 1,
            SelectorType = AudioSelectorType.TRACK
        };
        audsel.Tracks.Add(1);
        input.AudioSelectors.Add("Audio Selector 1", audsel);

        input.VideoSelector = new VideoSelector
        {
            ColorSpace = ColorSpace.FOLLOW
        };

        createJobRequest.Settings.Inputs.Add(input);

        #endregion Input

        var jobId = "";
        try
```

```
        {
            CreateJobResponse createJobResponse =
                await _amazonMediaConvert.CreateJobAsync(createJobRequest);

            jobId = createJobResponse.Job.Id;
        }
        catch (BadRequestException bre)
        {
            // If the endpoint was bad.
            if (bre.Message.StartsWith("You must use the customer-"))
            {
                // The exception contains the correct endpoint; extract it.
                var mediaConvertEndpoint = bre.Message.Split('\'')[1];
                Console.WriteLine(
                    $"Request failed, please use endpoint
 {mediaConvertEndpoint}.");
            }
            else
                throw;
        }

        return jobId;
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an AWS Elemental MediaConvert job.
/*!
  \param mediaConvertRole: An Amazon Resource Name (ARN) for the AWS Identity and
                           Access Management (IAM) role for the job.
```

```
  \param fileInput: A URI to an input file that is stored in Amazon Simple
 Storage Service
                   (Amazon S3) or on an HTTP(S) server.
  \param fileOutput: A URI for an Amazon S3 output location and the output file
 name base.
  \param jobSettingsFile: An optional JSON settings file.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::MediaConvert::createJob(const Aws::String &mediaConvertRole,
                                     const Aws::String &fileInput,
                                     const Aws::String &fileOutput,
                                     const Aws::String &jobSettingsFile,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::MediaConvert::Model::CreateJobRequest createJobRequest;

    createJobRequest.SetRole(mediaConvertRole);
    Aws::Http::HeaderValueCollection hvc;
    hvc.emplace("Customer", "Amazon");
    createJobRequest.SetUserMetadata(hvc);

    if (!jobSettingsFile.empty()) // Use a JSON file for the job settings.
    {
        std::ifstream jobSettingsStream(jobSettingsFile, std::ios::ate);
        if (!jobSettingsStream) {
            std::cerr << "Unable to open the job template file." << std::endl;
            return false;
        }
        std::vector<char> buffer(jobSettingsStream.tellg());
        jobSettingsStream.seekg(0);
        jobSettingsStream.read(buffer.data(), buffer.size());
        std::string jobSettingsJSON(buffer.data(), buffer.size());
        size_t pos = jobSettingsJSON.find(INPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(INPUT_FILE_PLACEHOLDER),
 fileInput);
        }

        pos = jobSettingsJSON.find(OUTPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(OUTPUT_FILE_PLACEHOLDER),
 fileOutput);
```

```
        }
        Aws::Utils::Json::JsonValue jsonValue(jobSettingsJSON);
        Aws::MediaConvert::Model::JobSettings jobSettings(jsonValue);

        createJobRequest.SetSettings(jobSettings);
    }
    else { // Configure the job settings programmatically.
        Aws::MediaConvert::Model::JobSettings jobSettings;
        jobSettings.SetAdAvailOffset(0);
        Aws::MediaConvert::Model::TimecodeConfig timecodeConfig;

timecodeConfig.SetSource(Aws::MediaConvert::Model::TimecodeSource::EMBEDDED);
        jobSettings.SetTimecodeConfig(timecodeConfig);

        // Configure the output group.
        Aws::MediaConvert::Model::OutputGroup outputGroup;
        outputGroup.SetName("File Group");
        Aws::MediaConvert::Model::OutputGroupSettings outputGroupSettings;
        outputGroupSettings.SetType(
                Aws::MediaConvert::Model::OutputGroupType::FILE_GROUP_SETTINGS);
        Aws::MediaConvert::Model::FileGroupSettings fileGroupSettings;
        fileGroupSettings.SetDestination(fileOutput);
        outputGroupSettings.SetFileGroupSettings(fileGroupSettings);
        outputGroup.SetOutputGroupSettings(outputGroupSettings);

        Aws::MediaConvert::Model::Output output;
        output.SetNameModifier("_1");

        Aws::MediaConvert::Model::VideoDescription videoDescription;
        videoDescription.SetScalingBehavior(
                Aws::MediaConvert::Model::ScalingBehavior::DEFAULT);
        videoDescription.SetTimecodeInsertion(
                Aws::MediaConvert::Model::VideoTimecodeInsertion::DISABLED);

videoDescription.SetAntiAlias(Aws::MediaConvert::Model::AntiAlias::ENABLED);
        videoDescription.SetSharpness(50);

videoDescription.SetAfdSignaling(Aws::MediaConvert::Model::AfdSignaling::NONE);
        videoDescription.SetDropFrameTimecode(
                Aws::MediaConvert::Model::DropFrameTimecode::ENABLED);

videoDescription.SetRespondToAfd(Aws::MediaConvert::Model::RespondToAfd::NONE);
        videoDescription.SetColorMetadata(
                Aws::MediaConvert::Model::ColorMetadata::INSERT);
```

```
        Aws::MediaConvert::Model::VideoCodecSettings videoCodecSettings;
        videoCodecSettings.SetCodec(Aws::MediaConvert::Model::VideoCodec::H_264);
        Aws::MediaConvert::Model::H264Settings h264Settings;
        h264Settings.SetNumberReferenceFrames(3);
        h264Settings.SetSyntax(Aws::MediaConvert::Model::H264Syntax::DEFAULT);
        h264Settings.SetSoftness(0);
        h264Settings.SetGopClosedCadence(1);
        h264Settings.SetGopSize(90);
        h264Settings.SetSlices(1);
        h264Settings.SetGopBReference(
                Aws::MediaConvert::Model::H264GopBReference::DISABLED);
        h264Settings.SetSlowPal(Aws::MediaConvert::Model::H264SlowPal::DISABLED);
        h264Settings.SetSpatialAdaptiveQuantization(

Aws::MediaConvert::Model::H264SpatialAdaptiveQuantization::ENABLED);
        h264Settings.SetTemporalAdaptiveQuantization(

Aws::MediaConvert::Model::H264TemporalAdaptiveQuantization::ENABLED);
        h264Settings.SetFlickerAdaptiveQuantization(

Aws::MediaConvert::Model::H264FlickerAdaptiveQuantization::DISABLED);
        h264Settings.SetEntropyEncoding(
                Aws::MediaConvert::Model::H264EntropyEncoding::CABAC);
        h264Settings.SetBitrate(5000000);
        h264Settings.SetFramerateControl(
                Aws::MediaConvert::Model::H264FramerateControl::SPECIFIED);
        h264Settings.SetRateControlMode(
                Aws::MediaConvert::Model::H264RateControlMode::CBR);

h264Settings.SetCodecProfile(Aws::MediaConvert::Model::H264CodecProfile::MAIN);
        h264Settings.SetTelecine(Aws::MediaConvert::Model::H264Telecine::NONE);
        h264Settings.SetMinIInterval(0);
        h264Settings.SetAdaptiveQuantization(
                Aws::MediaConvert::Model::H264AdaptiveQuantization::HIGH);

h264Settings.SetCodecLevel(Aws::MediaConvert::Model::H264CodecLevel::AUTO);
        h264Settings.SetFieldEncoding(
                Aws::MediaConvert::Model::H264FieldEncoding::PAFF);
        h264Settings.SetSceneChangeDetect(
                Aws::MediaConvert::Model::H264SceneChangeDetect::ENABLED);
        h264Settings.SetQualityTuningLevel(
                Aws::MediaConvert::Model::H264QualityTuningLevel::SINGLE_PASS);
        h264Settings.SetFramerateConversionAlgorithm(
```

```
Aws::MediaConvert::Model::H264FramerateConversionAlgorithm::DUPLICATE_DROP);
       h264Settings.SetUnregisteredSeiTimecode(
               Aws::MediaConvert::Model::H264UnregisteredSeiTimecode::DISABLED);
       h264Settings.SetGopSizeUnits(
               Aws::MediaConvert::Model::H264GopSizeUnits::FRAMES);

h264Settings.SetParControl(Aws::MediaConvert::Model::H264ParControl::SPECIFIED);
       h264Settings.SetNumberBFramesBetweenReferenceFrames(2);

h264Settings.SetRepeatPps(Aws::MediaConvert::Model::H264RepeatPps::DISABLED);
       h264Settings.SetFramerateNumerator(30);
       h264Settings.SetFramerateDenominator(1);
       h264Settings.SetParNumerator(1);
       h264Settings.SetParDenominator(1);
       videoCodecSettings.SetH264Settings(h264Settings);
       videoDescription.SetCodecSettings(videoCodecSettings);
       output.SetVideoDescription(videoDescription);

       Aws::MediaConvert::Model::AudioDescription audioDescription;
       audioDescription.SetLanguageCodeControl(

Aws::MediaConvert::Model::AudioLanguageCodeControl::FOLLOW_INPUT);
       audioDescription.SetAudioSourceName(AUDIO_SOURCE_NAME);
       Aws::MediaConvert::Model::AudioCodecSettings audioCodecSettings;
       audioCodecSettings.SetCodec(Aws::MediaConvert::Model::AudioCodec::AAC);
       Aws::MediaConvert::Model::AacSettings aacSettings;
       aacSettings.SetAudioDescriptionBroadcasterMix(

Aws::MediaConvert::Model::AacAudioDescriptionBroadcasterMix::NORMAL);
       aacSettings.SetRateControlMode(
               Aws::MediaConvert::Model::AacRateControlMode::CBR);

aacSettings.SetCodecProfile(Aws::MediaConvert::Model::AacCodecProfile::LC);
       aacSettings.SetCodingMode(
               Aws::MediaConvert::Model::AacCodingMode::CODING_MODE_2_0);
       aacSettings.SetRawFormat(Aws::MediaConvert::Model::AacRawFormat::NONE);
       aacSettings.SetSampleRate(48000);

aacSettings.SetSpecification(Aws::MediaConvert::Model::AacSpecification::MPEG4);
       aacSettings.SetBitrate(64000);
       audioCodecSettings.SetAacSettings(aacSettings);
       audioDescription.SetCodecSettings(audioCodecSettings);
```

```
        Aws::Vector<Aws::MediaConvert::Model::AudioDescription>
audioDescriptions;
        audioDescriptions.emplace_back(audioDescription);
        output.SetAudioDescriptions(audioDescriptions);

        Aws::MediaConvert::Model::ContainerSettings mp4container;
        mp4container.SetContainer(Aws::MediaConvert::Model::ContainerType::MP4);
        Aws::MediaConvert::Model::Mp4Settings mp4Settings;
        mp4Settings.SetCslgAtom(Aws::MediaConvert::Model::Mp4CslgAtom::INCLUDE);

mp4Settings.SetFreeSpaceBox(Aws::MediaConvert::Model::Mp4FreeSpaceBox::EXCLUDE);
        mp4Settings.SetMoovPlacement(

Aws::MediaConvert::Model::Mp4MoovPlacement::PROGRESSIVE_DOWNLOAD);
        mp4container.SetMp4Settings(mp4Settings);
        output.SetContainerSettings(mp4container);

        outputGroup.AddOutputs(output);
        jobSettings.AddOutputGroups(outputGroup);

        // Configure inputs.
        Aws::MediaConvert::Model::Input input;
        input.SetFilterEnable(Aws::MediaConvert::Model::InputFilterEnable::AUTO);
        input.SetPsiControl(Aws::MediaConvert::Model::InputPsiControl::USE_PSI);
        input.SetFilterStrength(0);

input.SetDeblockFilter(Aws::MediaConvert::Model::InputDeblockFilter::DISABLED);

input.SetDenoiseFilter(Aws::MediaConvert::Model::InputDenoiseFilter::DISABLED);
        input.SetTimecodeSource(
                Aws::MediaConvert::Model::InputTimecodeSource::EMBEDDED);
        input.SetFileInput(fileInput);

        Aws::MediaConvert::Model::AudioSelector audioSelector;
        audioSelector.SetOffset(0);
        audioSelector.SetDefaultSelection(
                Aws::MediaConvert::Model::AudioDefaultSelection::NOT_DEFAULT);
        audioSelector.SetProgramSelection(1);
        audioSelector.SetSelectorType(
                Aws::MediaConvert::Model::AudioSelectorType::TRACK);
        audioSelector.AddTracks(1);
        input.AddAudioSelectors(AUDIO_SOURCE_NAME, audioSelector);

        Aws::MediaConvert::Model::VideoSelector videoSelector;
```

```
 videoSelector.SetColorSpace(Aws::MediaConvert::Model::ColorSpace::FOLLOW);
        input.SetVideoSelector(videoSelector);

        jobSettings.AddInputs(input);

        createJobRequest.SetSettings(jobSettings);
    }

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);
    Aws::MediaConvert::Model::CreateJobOutcome outcome = client.CreateJob(
            createJobRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Job successfully created with ID - "
                  << outcome.GetResult().GetJob().GetId() << std::endl;
    }
    else {
        std::cerr << "Error CreateJob - " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como criar um trabalho

O exemplo de `create-job` a seguir cria um trabalho de transcodificação com as configurações especificadas em um arquivo `job.json` presente no sistema que você usou para enviar o comando. Essa especificação de trabalho JSON pode especificar cada configuração individualmente, fazer referência a um modelo de trabalho ou a predefinições de saída.

```
aws mediaconvert create-job \
    --endpoint-url https://abcd1234.mediaconvert.region-name-1.amazonaws.com \
    --region region-name-1 \
```

```
    --cli-input-json file://~/job.json
```

Você pode usar o MediaConvert console AWS Elemental para gerar a especificação de trabalho JSON escolhendo suas configurações de trabalho e, em seguida, escolhendo Mostrar trabalho JSON na parte inferior da seção Trabalho.

Use `describe-endpoints` para obter o endpoint específico da sua conta ou envie o comando sem o endpoint. O serviço retorna um erro e o endpoint.

Se a solicitação for bem-sucedida, o serviço retornará a especificação do trabalho JSON enviado com a solicitação.

Para obter mais informações, consulte Trabalhando com MediaConvert tarefas AWS elementares no Guia do MediaConvert usuário do AWS Elemental.

- Para obter detalhes da API, consulte CreateJobem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.mediaconvert;

import java.net.URI;
import java.util.HashMap;
import java.util.Map;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.Output;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import software.amazon.awssdk.services.mediaconvert.model.OutputGroup;
```

```
import software.amazon.awssdk.services.mediaconvert.model.OutputGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.HlsGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.OutputGroupType;
import software.amazon.awssdk.services.mediaconvert.model.HlsDirectoryStructure;
import
 software.amazon.awssdk.services.mediaconvert.model.HlsManifestDurationFormat;
import software.amazon.awssdk.services.mediaconvert.model.HlsStreamInfResolution;
import software.amazon.awssdk.services.mediaconvert.model.HlsClientCache;
import
 software.amazon.awssdk.services.mediaconvert.model.HlsCaptionLanguageSetting;
import software.amazon.awssdk.services.mediaconvert.model.HlsManifestCompression;
import software.amazon.awssdk.services.mediaconvert.model.HlsCodecSpecification;
import software.amazon.awssdk.services.mediaconvert.model.HlsOutputSelection;
import software.amazon.awssdk.services.mediaconvert.model.HlsProgramDateTime;
import
 software.amazon.awssdk.services.mediaconvert.model.HlsTimedMetadataId3Frame;
import software.amazon.awssdk.services.mediaconvert.model.HlsSegmentControl;
import software.amazon.awssdk.services.mediaconvert.model.FileGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.ContainerSettings;
import software.amazon.awssdk.services.mediaconvert.model.VideoDescription;
import software.amazon.awssdk.services.mediaconvert.model.ContainerType;
import software.amazon.awssdk.services.mediaconvert.model.ScalingBehavior;
import software.amazon.awssdk.services.mediaconvert.model.VideoTimecodeInsertion;
import software.amazon.awssdk.services.mediaconvert.model.ColorMetadata;
import software.amazon.awssdk.services.mediaconvert.model.RespondToAfd;
import software.amazon.awssdk.services.mediaconvert.model.AfdSignaling;
import software.amazon.awssdk.services.mediaconvert.model.DropFrameTimecode;
import software.amazon.awssdk.services.mediaconvert.model.VideoCodecSettings;
import software.amazon.awssdk.services.mediaconvert.model.H264Settings;
import software.amazon.awssdk.services.mediaconvert.model.VideoCodec;
import software.amazon.awssdk.services.mediaconvert.model.CreateJobRequest;
import software.amazon.awssdk.services.mediaconvert.model.H264RateControlMode;
import software.amazon.awssdk.services.mediaconvert.model.H264QualityTuningLevel;
import software.amazon.awssdk.services.mediaconvert.model.H264SceneChangeDetect;
import
 software.amazon.awssdk.services.mediaconvert.model.AacAudioDescriptionBroadcasterMix;
import software.amazon.awssdk.services.mediaconvert.model.H264ParControl;
import software.amazon.awssdk.services.mediaconvert.model.AacRawFormat;
import software.amazon.awssdk.services.mediaconvert.model.H264QvbrSettings;
import
 software.amazon.awssdk.services.mediaconvert.model.H264FramerateConversionAlgorithm;
import software.amazon.awssdk.services.mediaconvert.model.H264CodecLevel;
import software.amazon.awssdk.services.mediaconvert.model.H264FramerateControl;
import software.amazon.awssdk.services.mediaconvert.model.AacCodingMode;
```

```
import software.amazon.awssdk.services.mediaconvert.model.H264Telecine;
import
 software.amazon.awssdk.services.mediaconvert.model.H264FlickerAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.H264GopSizeUnits;
import software.amazon.awssdk.services.mediaconvert.model.H264CodecProfile;
import software.amazon.awssdk.services.mediaconvert.model.H264GopBReference;
import software.amazon.awssdk.services.mediaconvert.model.AudioTypeControl;
import software.amazon.awssdk.services.mediaconvert.model.AntiAlias;
import software.amazon.awssdk.services.mediaconvert.model.H264SlowPal;
import
 software.amazon.awssdk.services.mediaconvert.model.H264SpatialAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.H264Syntax;
import software.amazon.awssdk.services.mediaconvert.model.M3u8Settings;
import software.amazon.awssdk.services.mediaconvert.model.InputDenoiseFilter;
import
 software.amazon.awssdk.services.mediaconvert.model.H264TemporalAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.CreateJobResponse;
import
 software.amazon.awssdk.services.mediaconvert.model.H264UnregisteredSeiTimecode;
import software.amazon.awssdk.services.mediaconvert.model.H264EntropyEncoding;
import software.amazon.awssdk.services.mediaconvert.model.InputPsiControl;
import software.amazon.awssdk.services.mediaconvert.model.ColorSpace;
import software.amazon.awssdk.services.mediaconvert.model.H264RepeatPps;
import software.amazon.awssdk.services.mediaconvert.model.H264FieldEncoding;
import software.amazon.awssdk.services.mediaconvert.model.M3u8NielsenId3;
import software.amazon.awssdk.services.mediaconvert.model.InputDeblockFilter;
import software.amazon.awssdk.services.mediaconvert.model.InputRotate;
import software.amazon.awssdk.services.mediaconvert.model.H264DynamicSubGop;
import software.amazon.awssdk.services.mediaconvert.model.TimedMetadata;
import software.amazon.awssdk.services.mediaconvert.model.JobSettings;
import software.amazon.awssdk.services.mediaconvert.model.AudioDefaultSelection;
import software.amazon.awssdk.services.mediaconvert.model.VideoSelector;
import software.amazon.awssdk.services.mediaconvert.model.AacSpecification;
import software.amazon.awssdk.services.mediaconvert.model.Input;
import software.amazon.awssdk.services.mediaconvert.model.OutputSettings;
import
 software.amazon.awssdk.services.mediaconvert.model.H264AdaptiveQuantization;
import
 software.amazon.awssdk.services.mediaconvert.model.AudioLanguageCodeControl;
import software.amazon.awssdk.services.mediaconvert.model.InputFilterEnable;
import software.amazon.awssdk.services.mediaconvert.model.AudioDescription;
import software.amazon.awssdk.services.mediaconvert.model.H264InterlaceMode;
import software.amazon.awssdk.services.mediaconvert.model.AudioCodecSettings;
import software.amazon.awssdk.services.mediaconvert.model.AacSettings;
```

```
import software.amazon.awssdk.services.mediaconvert.model.AudioCodec;
import software.amazon.awssdk.services.mediaconvert.model.AacRateControlMode;
import software.amazon.awssdk.services.mediaconvert.model.AacCodecProfile;
import software.amazon.awssdk.services.mediaconvert.model.HlsIFrameOnlyManifest;
import software.amazon.awssdk.services.mediaconvert.model.FrameCaptureSettings;
import software.amazon.awssdk.services.mediaconvert.model.AudioSelector;
import software.amazon.awssdk.services.mediaconvert.model.M3u8PcrControl;
import software.amazon.awssdk.services.mediaconvert.model.InputTimecodeSource;
import software.amazon.awssdk.services.mediaconvert.model.HlsSettings;
import software.amazon.awssdk.services.mediaconvert.model.M3u8Scte35Source;

/**
 * Create a MediaConvert job. Must supply MediaConvert access role Amazon
 * Resource Name (ARN), and a
 * valid video input file via Amazon S3 URL.
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 */
public class CreateJob {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                    <mcRoleARN> <fileInput>\s

                                Where:
                                    mcRoleARN - The MediaConvert Role ARN.\s
                                    fileInput -  The URL of an Amazon S3 bucket
 where the input file is located.\s
                                """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String mcRoleARN = args[0];
                String fileInput = args[1];
```

```
                Region region = Region.US_WEST_2;
                MediaConvertClient mc = MediaConvertClient.builder()
                                .region(region)
                                .build();

                String id = createMediaJob(mc, mcRoleARN, fileInput);
                System.out.println("MediaConvert job created. Job Id = " + id);
                mc.close();
        }

        public static String createMediaJob(MediaConvertClient mc, String
mcRoleARN, String fileInput) {

                String s3path = fileInput.substring(0, fileInput.lastIndexOf('/')
+ 1) + "javasdk/out/";
                String fileOutput = s3path + "index";
                String thumbsOutput = s3path + "thumbs/";
                String mp4Output = s3path + "mp4/";

                try {
                        DescribeEndpointsResponse res = mc

.describeEndpoints(DescribeEndpointsRequest.builder().maxResults(20).build());

                        if (res.endpoints().size() <= 0) {
                                System.out.println("Cannot find MediaConvert
service endpoint URL!");
                                System.exit(1);
                        }
                        String endpointURL = res.endpoints().get(0).url();
                        System.out.println("MediaConvert service URL: " +
endpointURL);
                        System.out.println("MediaConvert role arn: " +
mcRoleARN);
                        System.out.println("MediaConvert input file: " +
fileInput);
                        System.out.println("MediaConvert output path: " +
s3path);

                        MediaConvertClient emc = MediaConvertClient.builder()
                                        .region(Region.US_WEST_2)

.endpointOverride(URI.create(endpointURL))
                                        .build();
```

```
                        // output group Preset HLS low profile
                        Output hlsLow = createOutput("hls_low", "_low", "_$dt$",
 750000, 7, 1920, 1080, 640);
                        // output group Preset HLS media profile
                        Output hlsMedium = createOutput("hls_medium", "_medium",
 "_$dt$", 1200000, 7, 1920, 1080, 1280);
                        // output group Preset HLS high profole
                        Output hlsHigh = createOutput("hls_high", "_high", "_$dt
$", 3500000, 8, 1920, 1080, 1920);

                        OutputGroup appleHLS = OutputGroup.builder().name("Apple
 HLS").customName("Example")

 .outputGroupSettings(OutputGroupSettings.builder()

 .type(OutputGroupType.HLS_GROUP_SETTINGS)

 .hlsGroupSettings(HlsGroupSettings.builder()

 .directoryStructure(

       HlsDirectoryStructure.SINGLE_DIRECTORY)

 .manifestDurationFormat(

       HlsManifestDurationFormat.INTEGER)

 .streamInfResolution(

       HlsStreamInfResolution.INCLUDE)

 .clientCache(HlsClientCache.ENABLED)

 .captionLanguageSetting(

       HlsCaptionLanguageSetting.OMIT)

 .manifestCompression(

       HlsManifestCompression.NONE)

 .codecSpecification(
```

```
      HlsCodecSpecification.RFC_4281)

.outputSelection(

      HlsOutputSelection.MANIFESTS_AND_SEGMENTS)

.programDateTime(HlsProgramDateTime.EXCLUDE)

.programDateTimePeriod(600)

.timedMetadataId3Frame(

      HlsTimedMetadataId3Frame.PRIV)

.timedMetadataId3Period(10)

.destination(fileOutput)

.segmentControl(HlsSegmentControl.SEGMENTED_FILES)

.minFinalSegmentLength((double) 0)

.segmentLength(4).minSegmentLength(0).build())
                                                        .build())
                                        .outputs(hlsLow, hlsMedium,
hlsHigh).build();

                      OutputGroup fileMp4 = OutputGroup.builder().name("File
Group").customName("mp4")

.outputGroupSettings(OutputGroupSettings.builder()

.type(OutputGroupType.FILE_GROUP_SETTINGS)

.fileGroupSettings(FileGroupSettings.builder()

.destination(mp4Output).build())
                                                        .build())

.outputs(Output.builder().extension("mp4")

.containerSettings(ContainerSettings.builder()
```

```
.container(ContainerType.MP4).build())

.videoDescription(VideoDescription.builder().width(1280)

.height(720)

.scalingBehavior(ScalingBehavior.DEFAULT)

.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

      VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.respondToAfd(RespondToAfd.NONE)

.afdSignaling(AfdSignaling.NONE)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

      .codec(VideoCodec.H_264)

      .h264Settings(H264Settings

                        .builder()

                        .rateControlMode(

                                        H264RateControlMode.QVBR)

                        .parControl(H264ParControl.INITIALIZE_FROM_SOURCE)

                        .qualityTuningLevel(

                                        H264QualityTuningLevel.SINGLE_PASS)

                        .qvbrSettings(

                                        H264QvbrSettings.builder()
```

```
                                                        .qvbrQualityLevel(
                                                                        8)
                                                        .build())
                        .codecLevel(H264CodecLevel.AUTO)
                        .codecProfile(H264CodecProfile.MAIN)
                        .maxBitrate(2400000)
                        .framerateControl(
H264FramerateControl.INITIALIZE_FROM_SOURCE)
                        .gopSize(2.0)
                        .gopSizeUnits(H264GopSizeUnits.SECONDS)
                        .numberBFramesBetweenReferenceFrames(
                                        2)
                        .gopClosedCadence(
                                        1)
                        .gopBReference(H264GopBReference.DISABLED)
                        .slowPal(H264SlowPal.DISABLED)
                        .syntax(H264Syntax.DEFAULT)
                        .numberReferenceFrames(
                                        3)
                        .dynamicSubGop(H264DynamicSubGop.STATIC)
                        .fieldEncoding(H264FieldEncoding.PAFF)
```

```
                        .sceneChangeDetect(
                                        H264SceneChangeDetect.ENABLED)
                        .minIInterval(0)
                        .telecine(H264Telecine.NONE)
                        .framerateConversionAlgorithm(

H264FramerateConversionAlgorithm.DUPLICATE_DROP)
                        .entropyEncoding(
                                        H264EntropyEncoding.CABAC)
                        .slices(1)
                        .unregisteredSeiTimecode(
                                        H264UnregisteredSeiTimecode.DISABLED)
                        .repeatPps(H264RepeatPps.DISABLED)
                        .adaptiveQuantization(
                                        H264AdaptiveQuantization.HIGH)
                        .spatialAdaptiveQuantization(
                                        H264SpatialAdaptiveQuantization.ENABLED)
                        .temporalAdaptiveQuantization(
                                        H264TemporalAdaptiveQuantization.ENABLED)
                        .flickerAdaptiveQuantization(
                                        H264FlickerAdaptiveQuantization.DISABLED)
                        .softness(0)
```

```
                        .interlaceMode(H264InterlaceMode.PROGRESSIVE)

                        .build())

      .build())
                                                                                .build())

.audioDescriptions(AudioDescription.builder()

.audioTypeControl(AudioTypeControl.FOLLOW_INPUT)

.languageCodeControl(

      AudioLanguageCodeControl.FOLLOW_INPUT)

.codecSettings(AudioCodecSettings.builder()

      .codec(AudioCodec.AAC)

      .aacSettings(AacSettings

                        .builder()

                        .codecProfile(AacCodecProfile.LC)

                        .rateControlMode(

                                        AacRateControlMode.CBR)

                        .codingMode(AacCodingMode.CODING_MODE_2_0)

                        .sampleRate(44100)

                        .bitrate(160000)

                        .rawFormat(AacRawFormat.NONE)

                        .specification(AacSpecification.MPEG4)

                        .audioDescriptionBroadcasterMix(

                                        AacAudioDescriptionBroadcasterMix.NORMAL)
```

```
                        .build())

      .build())
                                                                                .build())
                                                                .build())
                                                .build();
                        OutputGroup thumbs = OutputGroup.builder().name("File
Group").customName("thumbs")

.outputGroupSettings(OutputGroupSettings.builder()

.type(OutputGroupType.FILE_GROUP_SETTINGS)

.fileGroupSettings(FileGroupSettings.builder()

.destination(thumbsOutput).build())
                                                                .build())

.outputs(Output.builder().extension("jpg")

.containerSettings(ContainerSettings.builder()

.container(ContainerType.RAW).build())

.videoDescription(VideoDescription.builder()

.scalingBehavior(ScalingBehavior.DEFAULT)

.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

      VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

      .codec(VideoCodec.FRAME_CAPTURE)

      .frameCaptureSettings(
```

```
                        FrameCaptureSettings

                                        .builder()

                                        .framerateNumerator(

                                                        1)

                                        .framerateDenominator(

                                                        1)

                                        .maxCaptures(10000000)

                                        .quality(80)

                                        .build())

       .build())
                                                                                .build())
                                                        .build())
                                         .build();

                        Map<String, AudioSelector> audioSelectors = new
HashMap<>();
                        audioSelectors.put("Audio Selector 1",

AudioSelector.builder().defaultSelection(AudioDefaultSelection.DEFAULT)
                                                        .offset(0).build());

                        JobSettings jobSettings =
JobSettings.builder().inputs(Input.builder()
                                         .audioSelectors(audioSelectors)
                                         .videoSelector(

VideoSelector.builder().colorSpace(ColorSpace.FOLLOW)

.rotate(InputRotate.DEGREE_0).build())

.filterEnable(InputFilterEnable.AUTO).filterStrength(0)

.deblockFilter(InputDeblockFilter.DISABLED)
```

```
.denoiseFilter(InputDenoiseFilter.DISABLED).psiControl(InputPsiControl.USE_PSI)

.timecodeSource(InputTimecodeSource.EMBEDDED).fileInput(fileInput).build())
                                        .outputGroups(appleHLS, thumbs,
fileMp4).build();

                        CreateJobRequest createJobRequest =
CreateJobRequest.builder().role(mcRoleARN)
                                        .settings(jobSettings)
                                        .build();

                        CreateJobResponse createJobResponse =
emc.createJob(createJobRequest);
                        return createJobResponse.job().id();

                } catch (MediaConvertException e) {
                        System.out.println(e.toString());
                        System.exit(0);
                }
                return "";
        }

        private final static Output createOutput(String customName,
                        String nameModifier,
                        String segmentModifier,
                        int qvbrMaxBitrate,
                        int qvbrQualityLevel,
                        int originWidth,
                        int originHeight,
                        int targetWidth) {

                int targetHeight = Math.round(originHeight * targetWidth /
originWidth)
                                - (Math.round(originHeight * targetWidth /
originWidth) % 4);
                Output output = null;
                try {
                        output =
Output.builder().nameModifier(nameModifier).outputSettings(OutputSettings.builder()

.hlsSettings(HlsSettings.builder().segmentModifier(segmentModifier)

.audioGroupId("program_audio")
```

```
.iFrameOnlyManifest(HlsIFrameOnlyManifest.EXCLUDE).build())
                                        .build())

.containerSettings(ContainerSettings.builder().container(ContainerType.M3_U8)

.m3u8Settings(M3u8Settings.builder().audioFramesPerPes(4)

.pcrControl(M3u8PcrControl.PCR_EVERY_PES_PACKET)

.pmtPid(480).privateMetadataPid(503)

.programNumber(1).patInterval(0).pmtInterval(0)

.scte35Source(M3u8Scte35Source.NONE)

.scte35Pid(500).nielsenId3(M3u8NielsenId3.NONE)

.timedMetadata(TimedMetadata.NONE)

.timedMetadataPid(502).videoPid(481)

.audioPids(482, 483, 484, 485, 486, 487, 488,

      489, 490, 491, 492)
                                                                                .build())
                                                                .build())
                                        .videoDescription(

VideoDescription.builder().width(targetWidth)

.height(targetHeight)

.scalingBehavior(ScalingBehavior.DEFAULT)

.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

      VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.respondToAfd(RespondToAfd.NONE)
```

```
.afdSignaling(AfdSignaling.NONE)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

      .codec(VideoCodec.H_264)

      .h264Settings(H264Settings

                      .builder()

                      .rateControlMode(

                                      H264RateControlMode.QVBR)

                      .parControl(H264ParControl.INITIALIZE_FROM_SOURCE)

                      .qualityTuningLevel(

                                      H264QualityTuningLevel.SINGLE_PASS)

                      .qvbrSettings(H264QvbrSettings

                                      .builder()

                                      .qvbrQualityLevel(

                                                      qvbrQualityLevel)

                                      .build())

                      .codecLevel(H264CodecLevel.AUTO)

                      .codecProfile((targetHeight > 720

                                      && targetWidth > 1280)

                                                      ? H264CodecProfile.HIGH

                                                      : H264CodecProfile.MAIN)

                      .maxBitrate(qvbrMaxBitrate)
```

```
                        .framerateControl(

H264FramerateControl.INITIALIZE_FROM_SOURCE)

                        .gopSize(2.0)

                        .gopSizeUnits(H264GopSizeUnits.SECONDS)

                        .numberBFramesBetweenReferenceFrames(

                                        2)

                        .gopClosedCadence(

                                        1)

                        .gopBReference(H264GopBReference.DISABLED)

                        .slowPal(H264SlowPal.DISABLED)

                        .syntax(H264Syntax.DEFAULT)

                        .numberReferenceFrames(

                                        3)

                        .dynamicSubGop(H264DynamicSubGop.STATIC)

                        .fieldEncoding(H264FieldEncoding.PAFF)

                        .sceneChangeDetect(

                                        H264SceneChangeDetect.ENABLED)

                        .minIInterval(0)

                        .telecine(H264Telecine.NONE)

                        .framerateConversionAlgorithm(

H264FramerateConversionAlgorithm.DUPLICATE_DROP)
```

```
                        .entropyEncoding(
                                        H264EntropyEncoding.CABAC)
                        .slices(1)
                        .unregisteredSeiTimecode(
                                        H264UnregisteredSeiTimecode.DISABLED)
                        .repeatPps(H264RepeatPps.DISABLED)
                        .adaptiveQuantization(
                                        H264AdaptiveQuantization.HIGH)
                        .spatialAdaptiveQuantization(
                                        H264SpatialAdaptiveQuantization.ENABLED)
                        .temporalAdaptiveQuantization(
                                        H264TemporalAdaptiveQuantization.ENABLED)
                        .flickerAdaptiveQuantization(
                                        H264FlickerAdaptiveQuantization.DISABLED)
                        .softness(0)
                        .interlaceMode(H264InterlaceMode.PROGRESSIVE)
                        .build())
      .build())
                                                                        .build())
.audioDescriptions(AudioDescription.builder()
.audioTypeControl(AudioTypeControl.FOLLOW_INPUT)
.languageCodeControl(AudioLanguageCodeControl.FOLLOW_INPUT)
```

```
 .codecSettings(AudioCodecSettings.builder()

 .codec(AudioCodec.AAC).aacSettings(AacSettings

       .builder()

       .codecProfile(AacCodecProfile.LC)

       .rateControlMode(

                      AacRateControlMode.CBR)

       .codingMode(AacCodingMode.CODING_MODE_2_0)

       .sampleRate(44100)

       .bitrate(96000)

       .rawFormat(AacRawFormat.NONE)

       .specification(AacSpecification.MPEG4)

       .audioDescriptionBroadcasterMix(

                      AacAudioDescriptionBroadcasterMix.NORMAL)

       .build())
                                                                    .build())
                                                        .build())
                                   .build();
               } catch (MediaConvertException e) {
                       e.printStackTrace();
                       System.exit(0);
               }
               return output;
        }
}
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createMediaJob(mcClient: MediaConvertClient, mcRoleARN: String,
 fileInputVal: String): String? {
    val s3path = fileInputVal.substring(0, fileInputVal.lastIndexOf('/') + 1) +
 "javasdk/out/"
    val fileOutput = s3path + "index"
    val thumbsOutput = s3path + "thumbs/"
    val mp4Output = s3path + "mp4/"

    try {
        val describeEndpoints = DescribeEndpointsRequest {
            maxResults = 20
        }

        val res = mcClient.describeEndpoints(describeEndpoints)
        if (res.endpoints?.size!! <= 0) {
            println("Cannot find MediaConvert service endpoint URL!")
            exitProcess(0)
        }
        val endpointURL = res.endpoints!!.get(0).url!!
        val mediaConvert = MediaConvertClient.fromEnvironment {
            region = "us-west-2"
            endpointProvider = MediaConvertEndpointProvider {
                Endpoint(endpointURL)
            }
        }

        // output group Preset HLS low profile
        val hlsLow = createOutput("_low", "_\$dt$", 750000, 7, 1920, 1080, 640)

        // output group Preset HLS medium profile
        val hlsMedium = createOutput("_medium", "_\$dt$", 1200000, 7, 1920, 1080,
 1280)
```

```
        // output group Preset HLS high profole
        val hlsHigh = createOutput("_high", "_\$dt$", 3500000, 8, 1920, 1080,
1920)

        val outputSettings = OutputGroupSettings {
            type = OutputGroupType.HlsGroupSettings
        }

        val OutputObsList: MutableList<Output> = mutableListOf()
        if (hlsLow != null) {
            OutputObsList.add(hlsLow)
        }
        if (hlsMedium != null) {
            OutputObsList.add(hlsMedium)
        }
        if (hlsHigh != null) {
            OutputObsList.add(hlsHigh)
        }

        // Create an OutputGroup object.
        val appleHLS = OutputGroup {
            name = "Apple HLS"
            customName = "Example"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.HlsGroupSettings
                this.hlsGroupSettings = HlsGroupSettings {
                    directoryStructure = HlsDirectoryStructure.SingleDirectory
                    manifestDurationFormat = HlsManifestDurationFormat.Integer
                    streamInfResolution = HlsStreamInfResolution.Include
                    clientCache = HlsClientCache.Enabled
                    captionLanguageSetting = HlsCaptionLanguageSetting.Omit
                    manifestCompression = HlsManifestCompression.None
                    codecSpecification = HlsCodecSpecification.Rfc4281
                    outputSelection = HlsOutputSelection.ManifestsAndSegments
                    programDateTime = HlsProgramDateTime.Exclude
                    programDateTimePeriod = 600
                    timedMetadataId3Frame = HlsTimedMetadataId3Frame.Priv
                    timedMetadataId3Period = 10
                    destination = fileOutput
                    segmentControl = HlsSegmentControl.SegmentedFiles
                    minFinalSegmentLength = 0.toDouble()
                    segmentLength = 4
                    minSegmentLength = 1
```

```
                }
            }
            outputs = OutputObsList
        }

        val theOutput = Output {
            extension = "mp4"
            containerSettings = ContainerSettings {
                container = ContainerType.fromValue("MP4")
            }

            videoDescription = VideoDescription {
                width = 1280
                height = 720
                scalingBehavior = ScalingBehavior.Default
                sharpness = 50
                antiAlias = AntiAlias.Enabled
                timecodeInsertion = VideoTimecodeInsertion.Disabled
                colorMetadata = ColorMetadata.Insert
                respondToAfd = RespondToAfd.None
                afdSignaling = AfdSignaling.None
                dropFrameTimecode = DropFrameTimecode.Enabled
                codecSettings = VideoCodecSettings {
                    codec = VideoCodec.H264
                    h264Settings = H264Settings {
                        rateControlMode = H264RateControlMode.Qvbr
                        parControl = H264ParControl.InitializeFromSource
                        qualityTuningLevel = H264QualityTuningLevel.SinglePass
                        qvbrSettings = H264QvbrSettings { qvbrQualityLevel = 8 }
                        codecLevel = H264CodecLevel.Auto
                        codecProfile = H264CodecProfile.Main
                        maxBitrate = 2400000
                        framerateControl =
H264FramerateControl.InitializeFromSource
                        gopSize = 2.0
                        gopSizeUnits = H264GopSizeUnits.Seconds
                        numberBFramesBetweenReferenceFrames = 2
                        gopClosedCadence = 1
                        gopBReference = H264GopBReference.Disabled
                        slowPal = H264SlowPal.Disabled
                        syntax = H264Syntax.Default
                        numberReferenceFrames = 3
                        dynamicSubGop = H264DynamicSubGop.Static
                        fieldEncoding = H264FieldEncoding.Paff
```

```
                        sceneChangeDetect = H264SceneChangeDetect.Enabled
                        minIInterval = 0
                        telecine = H264Telecine.None
                        framerateConversionAlgorithm =
H264FramerateConversionAlgorithm.DuplicateDrop
                        entropyEncoding = H264EntropyEncoding.Cabac
                        slices = 1
                        unregisteredSeiTimecode =
H264UnregisteredSeiTimecode.Disabled
                        repeatPps = H264RepeatPps.Disabled
                        adaptiveQuantization = H264AdaptiveQuantization.High
                        spatialAdaptiveQuantization =
H264SpatialAdaptiveQuantization.Enabled
                        temporalAdaptiveQuantization =
H264TemporalAdaptiveQuantization.Enabled
                        flickerAdaptiveQuantization =
H264FlickerAdaptiveQuantization.Disabled
                        softness = 0
                        interlaceMode = H264InterlaceMode.Progressive
                    }
                }
            }

            audioDescriptions = listOf(
                AudioDescription {
                    audioTypeControl = AudioTypeControl.FollowInput
                    languageCodeControl = AudioLanguageCodeControl.FollowInput
                    codecSettings = AudioCodecSettings {
                        codec = AudioCodec.Aac
                        aacSettings = AacSettings {
                            codecProfile = AacCodecProfile.Lc
                            rateControlMode = AacRateControlMode.Cbr
                            codingMode = AacCodingMode.CodingMode2_0
                            sampleRate = 44100
                            bitrate = 160000
                            rawFormat = AacRawFormat.None
                            specification = AacSpecification.Mpeg4
                            audioDescriptionBroadcasterMix =
AacAudioDescriptionBroadcasterMix.Normal
                        }
                    }
                }
            )
        }
```

```
        // Create an OutputGroup
        val fileMp4 = OutputGroup {
            name = "File Group"
            customName = "mp4"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.FileGroupSettings
                fileGroupSettings = FileGroupSettings {
                    destination = mp4Output
                }
            }
            outputs = listOf(theOutput)
        }

        val containerSettings1 = ContainerSettings {
            container = ContainerType.Raw
        }

        val thumbs = OutputGroup {
            name = "File Group"
            customName = "thumbs"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.FileGroupSettings
                fileGroupSettings = FileGroupSettings {
                    destination = thumbsOutput
                }
            }

            outputs = listOf(
                Output {
                    extension = "jpg"

                    this.containerSettings = containerSettings1
                    videoDescription = VideoDescription {
                        scalingBehavior = ScalingBehavior.Default
                        sharpness = 50
                        antiAlias = AntiAlias.Enabled
                        timecodeInsertion = VideoTimecodeInsertion.Disabled
                        colorMetadata = ColorMetadata.Insert
                        dropFrameTimecode = DropFrameTimecode.Enabled
                        codecSettings = VideoCodecSettings {
                            codec = VideoCodec.FrameCapture
                            frameCaptureSettings = FrameCaptureSettings {
                                framerateNumerator = 1
```

```
                            framerateDenominator = 1
                            maxCaptures = 10000000
                            quality = 80
                        }
                    }
                }
            }
        )
    }

    val audioSelectors1: MutableMap<String, AudioSelector> = HashMap()
    audioSelectors1["Audio Selector 1"] =
        AudioSelector {
            defaultSelection = AudioDefaultSelection.Default
            offset = 0
        }

    val jobSettings = JobSettings {
        inputs = listOf(
            Input {
                audioSelectors = audioSelectors1
                videoSelector = VideoSelector {
                    colorSpace = ColorSpace.Follow
                    rotate = InputRotate.Degree0
                }
                filterEnable = InputFilterEnable.Auto
                filterStrength = 0
                deblockFilter = InputDeblockFilter.Disabled
                denoiseFilter = InputDenoiseFilter.Disabled
                psiControl = InputPsiControl.UsePsi
                timecodeSource = InputTimecodeSource.Embedded
                fileInput = fileInputVal

                outputGroups = listOf(appleHLS, thumbs, fileMp4)
            }
        )
    }

    val createJobRequest = CreateJobRequest {
        role = mcRoleARN
        settings = jobSettings
    }

    val createJobResponse = mediaConvert.createJob(createJobRequest)
```

```
        return createJobResponse.job?.id
    } catch (ex: MediaConvertException) {
        println(ex.message)
        mcClient.close()
        exitProcess(0)
    }
}

fun createOutput(
    nameModifierVal: String,
    segmentModifierVal: String,
    qvbrMaxBitrate: Int,
    qvbrQualityLevelVal: Int,
    originWidth: Int,
    originHeight: Int,
    targetWidth: Int
): Output? {
    val targetHeight = (
        (originHeight * targetWidth / originWidth).toFloat().roundToInt() -
            (originHeight * targetWidth / originWidth).toFloat().roundToInt() % 4
        )

    var output: Output?
    try {
        val audio1 = AudioDescription {
            audioTypeControl = AudioTypeControl.FollowInput
            languageCodeControl = AudioLanguageCodeControl.FollowInput
            codecSettings = AudioCodecSettings {
                codec = AudioCodec.Aac
                aacSettings = AacSettings {
                    codecProfile = AacCodecProfile.Lc
                    rateControlMode = AacRateControlMode.Cbr
                    codingMode = AacCodingMode.CodingMode2_0
                    sampleRate = 44100
                    bitrate = 96000
                    rawFormat = AacRawFormat.None
                    specification = AacSpecification.Mpeg4
                    audioDescriptionBroadcasterMix =
 AacAudioDescriptionBroadcasterMix.Normal
                }
            }
        }

        output = Output {
```

```
            nameModifier = nameModifierVal
            outputSettings = OutputSettings {
                hlsSettings = HlsSettings {
                    segmentModifier = segmentModifierVal
                    audioGroupId = "program_audio"
                    iFrameOnlyManifest = HlsIFrameOnlyManifest.Exclude
                }
            }
            containerSettings = ContainerSettings {
                container = ContainerType.M3U8
                this.m3u8Settings = M3u8Settings {
                    audioFramesPerPes = 4
                    pcrControl = M3u8PcrControl.PcrEveryPesPacket
                    pmtPid = 480
                    privateMetadataPid = 503
                    programNumber = 1
                    patInterval = 0
                    pmtInterval = 0
                    scte35Source = M3u8Scte35Source.None
                    scte35Pid = 500
                    nielsenId3 = M3u8NielsenId3.None
                    timedMetadata = TimedMetadata.None
                    timedMetadataPid = 502
                    videoPid = 481
                    audioPids = listOf(482, 483, 484, 485, 486, 487, 488, 489,
490, 491, 492)
                }

                videoDescription = VideoDescription {
                    width = targetWidth
                    height = targetHeight
                    scalingBehavior = ScalingBehavior.Default
                    sharpness = 50
                    antiAlias = AntiAlias.Enabled
                    timecodeInsertion = VideoTimecodeInsertion.Disabled
                    colorMetadata = ColorMetadata.Insert
                    respondToAfd = RespondToAfd.None
                    afdSignaling = AfdSignaling.None
                    dropFrameTimecode = DropFrameTimecode.Enabled
                    codecSettings = VideoCodecSettings {
                        codec = VideoCodec.H264
                        h264Settings = H264Settings {
                            rateControlMode = H264RateControlMode.Qvbr
                            parControl = H264ParControl.InitializeFromSource
```

```
                            qualityTuningLevel =
H264QualityTuningLevel.SinglePass
                            qvbrSettings = H264QvbrSettings {
                                qvbrQualityLevel = qvbrQualityLevelVal
                            }
                            codecLevel = H264CodecLevel.Auto
                            codecProfile =
                                if (targetHeight > 720 && targetWidth > 1280)
H264CodecProfile.High else H264CodecProfile.Main
                            maxBitrate = qvbrMaxBitrate
                            framerateControl =
H264FramerateControl.InitializeFromSource
                            gopSize = 2.0
                            gopSizeUnits = H264GopSizeUnits.Seconds
                            numberBFramesBetweenReferenceFrames = 2
                            gopClosedCadence = 1
                            gopBReference = H264GopBReference.Disabled
                            slowPal = H264SlowPal.Disabled
                            syntax = H264Syntax.Default
                            numberReferenceFrames = 3
                            dynamicSubGop = H264DynamicSubGop.Static
                            fieldEncoding = H264FieldEncoding.Paff
                            sceneChangeDetect = H264SceneChangeDetect.Enabled
                            minIInterval = 0
                            telecine = H264Telecine.None
                            framerateConversionAlgorithm =
H264FramerateConversionAlgorithm.DuplicateDrop
                            entropyEncoding = H264EntropyEncoding.Cabac
                            slices = 1
                            unregisteredSeiTimecode =
H264UnregisteredSeiTimecode.Disabled
                            repeatPps = H264RepeatPps.Disabled
                            adaptiveQuantization = H264AdaptiveQuantization.High
                            spatialAdaptiveQuantization =
H264SpatialAdaptiveQuantization.Enabled
                            temporalAdaptiveQuantization =
H264TemporalAdaptiveQuantization.Enabled
                            flickerAdaptiveQuantization =
H264FlickerAdaptiveQuantization.Disabled
                            softness = 0
                            interlaceMode = H264InterlaceMode.Progressive
                        }
                    }
                    audioDescriptions = listOf(audio1)
```

```
                }
            }
        }
    } catch (ex: MediaConvertException) {
        println(ex.toString())
        exitProcess(0)
    }
    return output
}
```

- Para obter detalhes da API, consulte a CreateJobreferência da API AWSSDK for Kotlin.

Consiga um trabalho de MediaConvert transcodificação usando um SDK AWS

Os exemplos de código a seguir mostram como obter um trabalho de transcodificação do AWS Elemental MediaConvert.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-
role-in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];
```

```
        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or
set it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert
endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
            DescribeEndpointsRequest describeRequest = new
DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };

        AmazonMediaConvertClient mcClient = new
AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

Obtenha um trabalho pelo seu ID.

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Getting job information for Job ID {jobId}");
        var job = await wrapper.GetJobById(jobId);
        Console.WriteLine($"Job {job.Id} created on {job.CreatedAt:d} has status
{job.Status}.");
```

```
        Console.WriteLine(new string('-', 80));
```

```
    /// <summary>
    /// Get the job information for a job by its ID.
    /// </summary>
    /// <param name="jobId">The ID of the job.</param>
    /// <returns>The Job object.</returns>
    public async Task<Job> GetJobById(string jobId)
    {
        var jobResponse = await _amazonMediaConvert.GetJobAsync(
                new GetJobRequest
                {
                    Id = jobId
                });

        return jobResponse.Job;
    }
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the information for a specific completed transcoding job.
/*!
  \param jobID: A job ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::getJob(const Aws::String &jobID,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    Aws::MediaConvert::Model::GetJobRequest request;
    request.SetId(jobID);
    const Aws::MediaConvert::Model::GetJobOutcome outcome = client.GetJob(
            request);
    if (outcome.IsSuccess()) {
        std::cout <<
 outcome.GetResult().GetJob().Jsonize().View().WriteReadable()
                << std::endl;
    }
    else {
        std::cerr << "DescribeEndpoints error - " <<
 outcome.GetError().GetMessage()
                << std::endl;
    }


    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter detalhes de um trabalho específico

O exemplo a seguir solicita as informações do trabalho com o ID `1234567890987-1ab2c3` que, neste exemplo, resultou em erro.

```
aws mediaconvert get-job \
    --endpoint-url https://abcd1234.mediaconvert.region-name-1.amazonaws.com \
    --region region-name-1 \
    --id 1234567890987-1ab2c3
```

Use `describe-endpoints` para obter o endpoint específico da sua conta ou envie o comando sem o endpoint. O serviço retorna um erro e o endpoint.

Se a solicitação for bem-sucedida, o serviço retornará um arquivo JSON com as informações do trabalho, incluindo as configurações do trabalho, quaisquer erros retornados e outros dados do trabalho, da seguinte forma:

```
{
    "Job": {
        "Status": "ERROR",
        "Queue": "arn:aws:mediaconvert:region-name-1:012345678998:queues/Queue1",
        "Settings": {
            ...<truncated for brevity>...
        },
        "ErrorMessage": "Unable to open input file [s3://my-input-bucket/file-
name.mp4]: [Failed probe/open: [Failed to read data: AssumeRole failed]]",
        "ErrorCode": 1434,
        "Role": "arn:aws:iam::012345678998:role/MediaConvertServiceRole",
        "Arn": "arn:aws:mediaconvert:us-
west-1:012345678998:jobs/1234567890987-1ab2c3",
        "UserMetadata": {},
        "Timing": {
            "FinishTime": 1517442131,
            "SubmitTime": 1517442103,
            "StartTime": 1517442104
        },
        "Id": "1234567890987-1ab2c3",
        "CreatedAt": 1517442103
    }
}
```

Para obter mais informações, consulte Trabalhando com MediaConvert tarefas AWS elementares no Guia do MediaConvert usuário do AWS Elemental.

- Para obter detalhes da API, consulte GetJobem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
import software.amazon.awssdk.services.mediaconvert.model.GetJobRequest;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.GetJobResponse;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import java.net.URI;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetJob {

    public static void main(String[] args) {

        final String usage = "\n" +
                "  <jobId> \n\n" +
                "Where:\n" +
                "  jobId - The job id value.\n\n";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String jobId = args[0];
        Region region = Region.US_WEST_2;
        MediaConvertClient mc = MediaConvertClient.builder()
                .region(region)
                .build();

        getSpecificJob(mc, jobId);
        mc.close();
    }
```

```
    public static void getSpecificJob(MediaConvertClient mc, String jobId) {
        try {
            DescribeEndpointsResponse res =
 mc.describeEndpoints(DescribeEndpointsRequest.builder()
                    .maxResults(20)
                    .build());

            if (res.endpoints().size() <= 0) {
                System.out.println("Cannot find MediaConvert service endpoint
 URL!");
                System.exit(1);
            }
            String endpointURL = res.endpoints().get(0).url();
            MediaConvertClient emc = MediaConvertClient.builder()
                    .region(Region.US_WEST_2)
                    .endpointOverride(URI.create(endpointURL))
                    .build();

            GetJobRequest jobRequest = GetJobRequest.builder()
                    .id(jobId)
                    .build();

            GetJobResponse response = emc.getJob(jobRequest);
            System.out.println("The ARN of the job is " + response.job().arn());

        } catch (MediaConvertException e) {
            System.out.println(e.toString());
            System.exit(0);
        }
    }
}
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificJob(mcClient: MediaConvertClient, jobId: String?) {
    val describeEndpoints = DescribeEndpointsRequest {
        maxResults = 20
    }

    val res = mcClient.describeEndpoints(describeEndpoints)
    if (res.endpoints?.size!! <= 0) {
        println("Cannot find MediaConvert service endpoint URL!")
        exitProcess(0)
    }

    val endpointURL = res.endpoints!!.get(0).url!!
    val mediaConvert = MediaConvertClient.fromEnvironment {
        region = "us-west-2"
        endpointProvider = MediaConvertEndpointProvider {
            Endpoint(endpointURL)
        }
    }

    val jobRequest = GetJobRequest {
        id = jobId
    }

    val response: GetJobResponse = mediaConvert.getJob(jobRequest)
    println("The ARN of the job is ${response.job?.arn}.")
}
```

- Para obter detalhes da API, consulte a GetJobreferência da API AWSSDK for Kotlin.

Listar trabalhos de MediaConvert transcodificação usando um SDK AWS

Os exemplos de código a seguir mostram como listar trabalhos de transcodificação do AWS Elemental MediaConvert.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-
role-in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];

        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or
 set it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert
 endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
```

```
            DescribeEndpointsRequest describeRequest = new
DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };

        AmazonMediaConvertClient mcClient = new
AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

Liste os trabalhos com um status específico.

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Listing all complete jobs.");
        var completeJobs = await wrapper.ListAllJobsByStatus(JobStatus.COMPLETE);
        completeJobs.ForEach(j =>
        {
            Console.WriteLine($"Job {j.Id} created on {j.CreatedAt:d} has status
{j.Status}.");
        });
```

Liste os trabalhos usando um paginador.

```
    /// <summary>
    /// List all of the jobs with a particular status using a paginator.
    /// </summary>
    /// <param name="status">The status to use when listing jobs.</param>
    /// <returns>The list of jobs matching the status.</returns>
    public async Task<List<Job>> ListAllJobsByStatus(JobStatus? status = null)
```

```
    {
        var returnedJobs = new List<Job>();

        var paginatedJobs = _amazonMediaConvert.Paginators.ListJobs(
                new ListJobsRequest
                {
                    Status = status
                });

        // Get the entire list using the paginator.
        await foreach (var job in paginatedJobs.Jobs)
        {
            returnedJobs.Add(job);
        }

        return returnedJobs;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of created jobs.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::listJobs(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    bool result = true;
```

```
    Aws::String nextToken; // Used to handle paginated results.
    do {
        Aws::MediaConvert::Model::ListJobsRequest request;
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }
        const Aws::MediaConvert::Model::ListJobsOutcome outcome =
 client.ListJobs(
                request);
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::MediaConvert::Model::Job> &jobs =
                    outcome.GetResult().GetJobs();
            std::cout << jobs.size() << " jobs retrieved." << std::endl;
            for (const Aws::MediaConvert::Model::Job &job: jobs) {
                std::cout << "  " << job.Jsonize().View().WriteReadable() <<
 std::endl;
            }

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "DescribeEndpoints error - " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;

        }
    } while (!nextToken.empty());


    return result;
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter detalhes de todos os trabalhos de uma região

O exemplo a seguir solicita as informações de todos os trabalhos na região especificada.

```
aws mediaconvert list-jobs \
    --endpoint-url https://abcd1234.mediaconvert.region-name-1.amazonaws.com \
    --region region-name-1
```

Use `describe-endpoints` para obter o endpoint específico da sua conta ou envie o comando sem o endpoint. O serviço retorna um erro e o endpoint.

Para obter mais informações, consulte Trabalhando com MediaConvert tarefas AWS elementares no Guia do MediaConvert usuário do AWS Elemental.

- Para obter detalhes da API, consulte ListJobsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import software.amazon.awssdk.services.mediaconvert.model.ListJobsRequest;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
import
 software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.ListJobsResponse;
import software.amazon.awssdk.services.mediaconvert.model.Job;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import java.net.URI;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListJobs {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MediaConvertClient mc = MediaConvertClient.builder()
                .region(region)
                .build();

        listCompleteJobs(mc);
        mc.close();
    }

    public static void listCompleteJobs(MediaConvertClient mc) {
        try {
            DescribeEndpointsResponse res =
 mc.describeEndpoints(DescribeEndpointsRequest.builder()
                    .maxResults(20)
                    .build());

            if (res.endpoints().size() <= 0) {
                System.out.println("Cannot find MediaConvert service endpoint
 URL!");
                System.exit(1);
            }

            String endpointURL = res.endpoints().get(0).url();
            MediaConvertClient emc = MediaConvertClient.builder()
                    .region(Region.US_WEST_2)
                    .endpointOverride(URI.create(endpointURL))
                    .build();

            ListJobsRequest jobsRequest = ListJobsRequest.builder()
                    .maxResults(10)
                    .status("COMPLETE")
                    .build();

            ListJobsResponse jobsResponse = emc.listJobs(jobsRequest);
            List<Job> jobs = jobsResponse.jobs();
            for (Job job : jobs) {
                System.out.println("The JOB ARN is : " + job.arn());
```

```
            }

        } catch (MediaConvertException e) {
            System.out.println(e.toString());
            System.exit(0);
        }
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listCompleteJobs(mcClient: MediaConvertClient) {
    val describeEndpoints = DescribeEndpointsRequest {
        maxResults = 20
    }

    val res = mcClient.describeEndpoints(describeEndpoints)
    if (res.endpoints?.size!! <= 0) {
        println("Cannot find MediaConvert service endpoint URL!")
        exitProcess(0)
    }
    val endpointURL = res.endpoints!![0].url!!
    val mediaConvert = MediaConvertClient.fromEnvironment {
        region = "us-west-2"
        endpointProvider = MediaConvertEndpointProvider {
            Endpoint(endpointURL)
        }
    }

    val jobsRequest = ListJobsRequest {
        maxResults = 10
```

```
        status = JobStatus.fromValue("COMPLETE")
    }

    val jobsResponse = mediaConvert.listJobs(jobsRequest)
    val jobs = jobsResponse.jobs
    if (jobs != null) {
        for (job in jobs) {
            println("The JOB ARN is ${job.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWSSDK for Kotlin.

Exemplos de código para MediaLive usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Elemental MediaLive com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- MediaLive Guia do usuário — Mais informações sobre MediaLive.
- MediaLive Referência da API — Detalhes sobre todas as MediaLive ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para MediaLive usar AWS SDKs
  - Liste suas MediaLive entradas usando um SDK AWS

Ações para MediaLive usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Elemental MediaLive com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Liste suas MediaLive entradas usando um SDK AWS

Liste suas MediaLive entradas usando um SDK AWS

O exemplo de código a seguir mostra como listar suas MediaLive entradas.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste seus nomes MediaLive de entrada e ARNs na região.

```
async fn show_inputs(client: &Client) -> Result<(), Error> {
    let input_list = client.list_inputs().send().await?;

    for i in input_list.inputs() {
        let input_arn = i.arn().unwrap_or_default();
        let input_name = i.name().unwrap_or_default();

        println!("Input Name : {}", input_name);
        println!("Input ARN : {}", input_arn);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListInputsreferência da API AWS SDK for Rust.

Exemplos de código para MediaPackage usar AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Elemental MediaPackage com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- MediaPackage Guia do usuário — Mais informações sobre MediaPackage.
- MediaPackage Referência da API — Detalhes sobre todas as MediaPackage ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para MediaPackage usar AWS SDKs
  - Liste seus MediaPackage canais usando um AWS SDK
  - Liste seus endpoints de MediaPackage origem usando um SDK AWS

Ações para MediaPackage usar AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Elemental MediaPackage com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Liste seus MediaPackage canais usando um AWS SDK
- Liste seus endpoints de MediaPackage origem usando um SDK AWS

Liste seus MediaPackage canais usando um AWS SDK

Os exemplos de código a seguir mostram como listar seus MediaPackage canais.

CLI

AWS CLI

Como listar todos os canais

O comando `list-channels` a seguir lista todos os canais configurados na conta da AWS atual.

```
aws mediapackage list-channels
```

Saída:

```
{
    "Channels": [
        {
            "Arn": "arn:aws:mediapackage:us-
west-2:111222333:channels/584797f1740548c389a273585dd22a63",
            "HlsIngest": {
                "IngestEndpoints": [
                    {
                        "Id": "584797f1740548c389a273585dd22a63",
                        "Password": "webdavgeneratedpassword1",
                        "Url": "https://9be9c4405c474882.mediapackage.us-
west-2.amazonaws.com/in/
v2/584797f1740548c389a273585dd22a63/584797f1740548c389a273585dd22a63/channel",
                        "Username": "webdavgeneratedusername1"
                    },
                    {
                        "Id": "7d187c8616fd455f88aaa5a9fcf74442",
                        "Password": "webdavgeneratedpassword2",
                        "Url": "https://7bf454c57220328d.mediapackage.us-
west-2.amazonaws.com/in/
v2/584797f1740548c389a273585dd22a63/7d187c8616fd455f88aaa5a9fcf74442/channel",
                        "Username": "webdavgeneratedusername2"
                    }
                ]
            },
            "Id": "test",
            "Tags": {}
        }
    ]
}
```

Para obter mais informações, consulte Visualizando detalhes do canal no Guia do MediaPackage usuário do AWS Elemental.

- Para obter detalhes da API, consulte ListChannelsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar canais ARNs e as descrições.

```
async fn show_channels(client: &Client) -> Result<(), Error> {
    let list_channels = client.list_channels().send().await?;

    println!("Channels:");

    for c in list_channels.channels() {
        let description = c.description().unwrap_or_default();
        let arn = c.arn().unwrap_or_default();

        println!("  Description : {}", description);
        println!("  ARN :         {}", arn);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListChannelsreferência da API AWS SDK for Rust.

Liste seus endpoints de MediaPackage origem usando um SDK AWS

Os exemplos de código a seguir mostram como listar seus endpoints de MediaPackage origem.

CLI

AWS CLI

Como listar todos os endpoints de origem de um canal

O comando `list-origin-endpoints` a seguir lista todos endpoints de origem que estão configurados no canal `test`.

```
aws mediapackage list-origin-endpoints \
    --channel-id test
```

Saída:

```
{
    "OriginEndpoints": [
        {
            "Arn": "arn:aws:mediapackage:us-
west-2:111222333:origin_endpoints/247cff871f2845d3805129be22f2c0a2",
            "ChannelId": "test",
            "DashPackage": {
                "ManifestLayout": "FULL",
                "ManifestWindowSeconds": 60,
                "MinBufferTimeSeconds": 30,
                "MinUpdatePeriodSeconds": 15,
                "PeriodTriggers": [],
                "Profile": "NONE",
                "SegmentDurationSeconds": 2,
                "SegmentTemplateFormat": "NUMBER_WITH_TIMELINE",
                "StreamSelection": {
                    "MaxVideoBitsPerSecond": 2147483647,
                    "MinVideoBitsPerSecond": 0,
                    "StreamOrder": "ORIGINAL"
                },
                "SuggestedPresentationDelaySeconds": 25
            },
            "Id": "tester2",
            "ManifestName": "index",
            "StartoverWindowSeconds": 0,
            "Tags": {},
            "TimeDelaySeconds": 0,
            "Url": "https://8343f7014c0ea438.mediapackage.us-
west-2.amazonaws.com/out/v1/247cff871f2845d3805129be22f2c0a2/index.mpd",
```

```
            "Whitelist": []
        },
        {
            "Arn": "arn:aws:mediapackage:us-
west-2:111222333:origin_endpoints/869e237f851549e9bcf10e3bc2830839",
            "ChannelId": "test",
            "HlsPackage": {
                "AdMarkers": "NONE",
                "IncludeIframeOnlyStream": false,
                "PlaylistType": "EVENT",
                "PlaylistWindowSeconds": 60,
                "ProgramDateTimeIntervalSeconds": 0,
                "SegmentDurationSeconds": 6,
                "StreamSelection": {
                    "MaxVideoBitsPerSecond": 2147483647,
                    "MinVideoBitsPerSecond": 0,
                    "StreamOrder": "ORIGINAL"
                },
                "UseAudioRenditionGroup": false
            },
            "Id": "tester",
            "ManifestName": "index",
            "StartoverWindowSeconds": 0,
            "Tags": {},
            "TimeDelaySeconds": 0,
            "Url": "https://8343f7014c0ea438.mediapackage.us-
west-2.amazonaws.com/out/v1/869e237f851549e9bcf10e3bc2830839/index.m3u8",
            "Whitelist": []
        }
    ]
}
```

Para obter mais informações, consulte Visualização de todos os endpoints associados a um canal no Guia do MediaPackage usuário do AWS Elemental.

- Para obter detalhes da API, consulte ListOriginEndpointsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar as descrições de endpoint e URLs.

```
async fn show_endpoints(client: &Client) -> Result<(), Error> {
    let or_endpoints = client.list_origin_endpoints().send().await?;

    println!("Endpoints:");

    for e in or_endpoints.origin_endpoints() {
        let endpoint_url = e.url().unwrap_or_default();
        let endpoint_description = e.description().unwrap_or_default();
        println!("  Description: {}", endpoint_description);
        println!("  URL :        {}", endpoint_url);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListOriginEndpointsreferência da API AWS SDK for Rust.

Exemplos de código para o Migration Hub usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Migration Hub com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Migration Hub – Mais informações sobre o Migration Hub.
- Referência da API do Migration Hub – Detalhes sobre todas as ações disponíveis do Migration Hub.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Migration Hub usando SDKs da AWS
  - Exclua o fluxo de progresso usando o SDK do Migration Hub
  - Descreva o status de migração de um aplicativo usando o SDK do Migration Hub
  - Obtenha uma lista de atributos associados a uma migração usando o SDK do Migration Hub
  - Liste aplicativos usando o SDK do Migration Hub
  - Liste artefatos criados usando o SDK do Migration Hub
  - Liste tarefas de migração usando o SDK do Migration Hub
  - Registre uma tarefa de migração usando o SDK do Migration Hub

Ações para o Migration Hub usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Migration Hub com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Exclua o fluxo de progresso usando o SDK do Migration Hub
- Descreva o status de migração de um aplicativo usando o SDK do Migration Hub
- Obtenha uma lista de atributos associados a uma migração usando o SDK do Migration Hub
- Liste aplicativos usando o SDK do Migration Hub
- Liste artefatos criados usando o SDK do Migration Hub
- Liste tarefas de migração usando o SDK do Migration Hub
- Registre uma tarefa de migração usando o SDK do Migration Hub

Exclua o fluxo de progresso usando o SDK do Migration Hub

O exemplo de código a seguir mostra como excluir um stream de progresso.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DeleteProgressUpdateStreamRequest;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteProgressStream {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <progressStream>\s

                Where:
                    progressStream - the name of a progress stream to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String progressStream = args[0];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        deleteStream(migrationClient, progressStream);
        migrationClient.close();
    }

    public static void deleteStream(MigrationHubClient migrationClient, String
 streamName) {
        try {
            DeleteProgressUpdateStreamRequest deleteProgressUpdateStreamRequest =
 DeleteProgressUpdateStreamRequest
                    .builder()
                    .progressUpdateStreamName(streamName)
                    .build();


 migrationClient.deleteProgressUpdateStream(deleteProgressUpdateStreamRequest);
            System.out.println(streamName + " is deleted");

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteProgressUpdateStreama Referência AWS SDK for Java 2.x da API.

Descreva o status de migração de um aplicativo usando o SDK do Migration Hub

O exemplo de código a seguir mostra como descrever o status da migração.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeApplicationStateRequest;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeApplicationStateResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeAppState {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    DescribeAppState <appId>\s

                Where:
                    appId -  the application id value.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String appId = args[0];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        describeApplicationState(migrationClient, appId);
        migrationClient.close();
    }

    public static void describeApplicationState(MigrationHubClient
 migrationClient, String appId) {
        try {
            DescribeApplicationStateRequest applicationStateRequest =
 DescribeApplicationStateRequest.builder()
                    .applicationId(appId)
                    .build();

            DescribeApplicationStateResponse applicationStateResponse =
 migrationClient
                    .describeApplicationState(applicationStateRequest);
            System.out.println("The application status is " +
 applicationStateResponse.applicationStatusAsString());

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeApplicationStatea Referência AWS SDK for Java 2.x da API.

Obtenha uma lista de atributos associados a uma migração usando o SDK do Migration Hub

O exemplo de código a seguir mostra como obter uma lista de atributos associados a uma migração.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeMigrationTaskRequest;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeMigrationTaskResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeMigrationTask {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    DescribeMigrationTask <migrationTask> <progressStream>\s

                Where:
                    migrationTask - the name of a migration task.\s
                    progressStream - the name of a progress stream.\s
                """;

        if (args.length < 2) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String migrationTask = args[0];
        String progressStream = args[1];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        describeMigTask(migrationClient, migrationTask, progressStream);
        migrationClient.close();
    }

    public static void describeMigTask(MigrationHubClient migrationClient, String
 migrationTask,
            String progressStream) {
        try {
            DescribeMigrationTaskRequest migrationTaskRequestRequest =
 DescribeMigrationTaskRequest.builder()
                    .progressUpdateStream(progressStream)
                    .migrationTaskName(migrationTask)
                    .build();

            DescribeMigrationTaskResponse migrationTaskResponse = migrationClient
                    .describeMigrationTask(migrationTaskRequestRequest);
            System.out.println("The name is " +
 migrationTaskResponse.migrationTask().migrationTaskName());

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeMigrationTaska Referência AWS SDK for Java 2.x da API.

Liste aplicativos usando o SDK do Migration Hub

O exemplo de código a seguir mostra como listar aplicações.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import software.amazon.awssdk.services.migrationhub.model.ApplicationState;
import
 software.amazon.awssdk.services.migrationhub.model.ListApplicationStatesRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListApplicationStatesResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListApplications {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        listApps(migrationClient);
        migrationClient.close();
    }

    public static void listApps(MigrationHubClient migrationClient) {
        try {
```

```
            ListApplicationStatesRequest applicationStatesRequest =
 ListApplicationStatesRequest.builder()
                    .maxResults(10)
                    .build();

            ListApplicationStatesResponse response =
 migrationClient.listApplicationStates(applicationStatesRequest);
            List<ApplicationState> apps = response.applicationStateList();
            for (ApplicationState appState : apps) {
                System.out.println("App Id is " + appState.applicationId());
                System.out.println("The status is " +
 appState.applicationStatus().toString());
            }

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListApplicationsa Referência AWS SDK for Java 2.x da API.

Liste artefatos criados usando o SDK do Migration Hub

O código de exemplo a seguir mostra como listar artefatos criados.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
```

```
import software.amazon.awssdk.services.migrationhub.model.CreatedArtifact;
import
 software.amazon.awssdk.services.migrationhub.model.ListCreatedArtifactsRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListCreatedArtifactsResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
import java.util.List;

/**
 * To run this Java V2 code example, ensure that you have setup your development
 * environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListCreatedArtifacts {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        listArtifacts(migrationClient);
        migrationClient.close();
    }

    public static void listArtifacts(MigrationHubClient migrationClient) {
        try {
            ListCreatedArtifactsRequest listCreatedArtifactsRequest =
 ListCreatedArtifactsRequest.builder()
                    .maxResults(10)
                    .migrationTaskName("SampleApp5")
                    .progressUpdateStream("ProgressSteamB")
                    .build();

            ListCreatedArtifactsResponse response =
 migrationClient.listCreatedArtifacts(listCreatedArtifactsRequest);
            List<CreatedArtifact> apps = response.createdArtifactList();
            for (CreatedArtifact artifact : apps) {
                System.out.println("APp Id is " + artifact.description());
                System.out.println("The name is " + artifact.name());
            }
```

```
        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListCreatedArtifactsa Referência AWS SDK for Java 2.x da API.

Liste tarefas de migração usando o SDK do Migration Hub

O exemplo de código a seguir mostra como listar tarefas de migração.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.ListMigrationTasksRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListMigrationTasksResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationTaskSummary;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListMigrationTasks {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        listMigrTasks(migrationClient);
        migrationClient.close();
    }

    public static void listMigrTasks(MigrationHubClient migrationClient) {
        try {
            ListMigrationTasksRequest listMigrationTasksRequest =
 ListMigrationTasksRequest.builder()
                    .maxResults(10)
                    .build();

            ListMigrationTasksResponse response =
 migrationClient.listMigrationTasks(listMigrationTasksRequest);
            List<MigrationTaskSummary> migrationList =
 response.migrationTaskSummaryList();
            for (MigrationTaskSummary migration : migrationList) {
                System.out.println("Migration task name is " +
 migration.migrationTaskName());
                System.out.println("The Progress update stream is " +
 migration.progressUpdateStream());
            }

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMigrationTasksa Referência AWS SDK for Java 2.x da API.

Registre uma tarefa de migração usando o SDK do Migration Hub

O exemplo de código a seguir mostra como registrar uma tarefa de migração.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.CreateProgressUpdateStreamRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ImportMigrationTaskRequest;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ImportMigrationTask {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <migrationTask> <progressStream>\s

                Where:
                    migrationTask - the name of a migration task.\s
                    progressStream - the name of a progress stream.\s
                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String migrationTask = args[0];
        String progressStream = args[1];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        importMigrTask(migrationClient, migrationTask, progressStream);
        migrationClient.close();
    }

    public static void importMigrTask(MigrationHubClient migrationClient, String
 migrationTask, String progressStream) {
        try {
            CreateProgressUpdateStreamRequest progressUpdateStreamRequest =
 CreateProgressUpdateStreamRequest.builder()
                    .progressUpdateStreamName(progressStream)
                    .dryRun(false)
                    .build();


 migrationClient.createProgressUpdateStream(progressUpdateStreamRequest);
            ImportMigrationTaskRequest migrationTaskRequest =
 ImportMigrationTaskRequest.builder()
                    .migrationTaskName(migrationTask)
                    .progressUpdateStream(progressStream)
                    .dryRun(false)
                    .build();

            migrationClient.importMigrationTask(migrationTaskRequest);

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ImportMigrationTaska Referência AWS SDK for Java 2.x da API.

Exemplos de código para o Organizations usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Organizations com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Organizations – Mais informações sobre o Organizations.
- Referência da API do Organizations – Detalhes sobre todas as ações disponíveis do Organizations.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Organizations usando SDKs da AWS
  - Anexe uma política do Organizations a um destino usando um SDK da AWS
  - Crie uma política do Organizations usando um SDK da AWS
  - Crie uma conta do Organizations usando um SDK da AWS
  - Crie uma organização do Organizations usando um SDK da AWS
  - Crie uma unidade organizacional do Organizations usando um SDK da AWS
  - Exclua uma política do Organizations usando um SDK da AWS
  - Exclua uma organização do Organizations usando um SDK da AWS
  - Exclua uma unidade organizacional do Organizations usando um SDK da AWS

- Descreva uma política do Organizations usando um SDK da AWS
- Desvincule uma política do Organizations de um destino usando um SDK da AWS
- Liste contas de uma organização do Organizations usando um SDK da AWS
- Liste unidades organizacionais do Organizations usando um SDK da AWS
- Liste as políticas do Organizations usando um SDK da AWS

Ações para o Organizations usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Organizations com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Anexe uma política do Organizations a um destino usando um SDK da AWS
- Crie uma política do Organizations usando um SDK da AWS
- Crie uma conta do Organizations usando um SDK da AWS
- Crie uma organização do Organizations usando um SDK da AWS
- Crie uma unidade organizacional do Organizations usando um SDK da AWS
- Exclua uma política do Organizations usando um SDK da AWS
- Exclua uma organização do Organizations usando um SDK da AWS
- Exclua uma unidade organizacional do Organizations usando um SDK da AWS
- Descreva uma política do Organizations usando um SDK da AWS
- Desvincule uma política do Organizations de um destino usando um SDK da AWS
- Liste contas de uma organização do Organizations usando um SDK da AWS
- Liste unidades organizacionais do Organizations usando um SDK da AWS
- Liste as políticas do Organizations usando um SDK da AWS

Anexe uma política do Organizations a um destino usando um SDK da AWS

O exemplo de código a seguir mostra como anexar uma política de Organizações a um destino.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to attach an AWS Organizations policy to an organization,
/// an organizational unit, or an account.
/// </summary>
public class AttachPolicy
{
    /// <summary>
    /// Initializes the Organizations client object and then calls the
    /// AttachPolicyAsync method to attach the policy to the root
    /// organization.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();
        var policyId = "p-00000000";
        var targetId = "r-0000";

        var request = new AttachPolicyRequest
        {
            PolicyId = policyId,
            TargetId = targetId,
        };

        var response = await client.AttachPolicyAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
```

```
                Console.WriteLine($"Successfully attached Policy ID {policyId} to
 Target ID: {targetId}.");
            }
            else
            {
                Console.WriteLine("Was not successful in attaching the policy.");
            }
        }
    }
```

- Para obter detalhes da API, consulte AttachPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como anexar uma política a uma raiz, unidade operacional ou conta

Exemplo 1

O seguinte exemplo mostra com anexar uma política de controle de serviços (SCP) a uma unidade operacional (OU):

```
aws organizations attach-policy
                --policy-id p-examplepolicyid111
                --target-id ou-examplerootid111-exampleouid111
```

Exemplo 2

O seguinte exemplo mostra como anexar uma política de controle de serviços a uma conta:

```
aws organizations attach-policy
                --policy-id p-examplepolicyid111
                --target-id 333333333333
```

- Para obter detalhes da API, consulte AttachPolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def attach_policy(policy_id, target_id, orgs_client):
    """
    Attaches a policy to a target. The target is an organization root, account,
 or
    organizational unit.

    :param policy_id: The ID of the policy to attach.
    :param target_id: The ID of the resources to attach the policy to.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.attach_policy(PolicyId=policy_id, TargetId=target_id)
        logger.info("Attached policy %s to target %s.", policy_id, target_id)
    except ClientError:
        logger.exception(
            "Couldn't attach policy %s to target %s.", policy_id, target_id
        )
        raise
```

- Para obter detalhes da API, consulte a AttachPolicyReferência da API AWSSDK for Python (Boto3).

Crie uma política do Organizations usando um SDK da AWS

O exemplo de código a seguir mostra como criar uma política do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates a new AWS Organizations Policy.
/// </summary>
public class CreatePolicy
{
    /// <summary>
    /// Initializes the AWS Organizations client object, uses it to
    /// create a new Organizations Policy, and then displays information
    /// about the newly created Policy.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();
        var policyContent = "{" +
            "   \"Version\": \"2012-10-17\"," +
            " \"Statement\" : [{" +
                " \"Action\" : [\"s3:*\"]," +
                " \"Effect\" : \"Allow\"," +
                " \"Resource\" : \"*\"" +
            "}]" +
        "}";

        try
        {
            var response = await client.CreatePolicyAsync(new
CreatePolicyRequest
            {
```

```
                    Content = policyContent,
                    Description = "Enables admins of attached accounts to
 delegate all Amazon S3 permissions",
                    Name = "AllowAllS3Actions",
                    Type = "SERVICE_CONTROL_POLICY",
                });

                Policy policy = response.Policy;
                Console.WriteLine($"{policy.PolicySummary.Name} has the following
 content: {policy.Content}");
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar uma política com um arquivo de origem de texto na política JSON

O exemplo a seguir mostra como criar uma política de controle de serviço (SCP) chamada `AllowAllS3Actions`. O conteúdo da política provém de um arquivo chamado `policy.json` presente no computador local.

```
aws organizations create-policy --content file://policy.json --name
 AllowAllS3Actions, --type SERVICE_CONTROL_POLICY --description "Allows
 delegation of all S3 actions"
```

A saída inclui um objeto de política com detalhes sobre a nova política:

```
{
        "Policy": {
                "Content": "{\"Version\":\"2012-10-17\",\"Statement\":[{\"Effect
\":\"Allow\",\"Action\":[\"s3:*\"],\"Resource\":[\"*\"]}]}",
```

```
                "PolicySummary": {
                        "Arn": "arn:aws:organizations::o-exampleorgid:policy/
service_control_policy/p-examplepolicyid111",
                        "Description": "Allows delegation of all S3 actions",
                        "Name": "AllowAllS3Actions",
                        "Type":"SERVICE_CONTROL_POLICY"
                }
        }
}
```

Exemplo 2: como criar uma política tendo uma política JSON como parâmetro

O exemplo a seguir mostra como criar a mesma SCP, mas, desta vez, incorporando o conteúdo da política como uma string JSON no parâmetro. A string deve ser recuada com barras invertidas antes das aspas duplas para garantir que ela seja tratada como literal no parâmetro (que está entre aspas duplas):

```
aws organizations create-policy --content "{\"Version\":\"2012-10-17\",
\"Statement\":[{\"Effect\":\"Allow\",\"Action\":[\"s3:*\"],\"Resource\":[\"*
\"]}]}" --name AllowAllS3Actions --type SERVICE_CONTROL_POLICY --description
 "Allows delegation of all S3 actions"
```

Para obter mais informações sobre como criar e usar políticas em sua organização, consulte Gerenciamento de políticas organizacionais no Guia do usuário do AWS Organizations.

- Para obter detalhes da API, consulte CreatePolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy(name, description, content, policy_type, orgs_client):
    """
    Creates a policy.
```

```
    :param name: The name of the policy.
    :param description: The description of the policy.
    :param content: The policy content as a dict. This is converted to JSON
before
                    it is sent to AWS. The specific format depends on the policy
type.
    :param policy_type: The type of the policy.
    :param orgs_client: The Boto3 Organizations client.
    :return: The newly created policy.
    """
    try:
        response = orgs_client.create_policy(
            Name=name,
            Description=description,
            Content=json.dumps(content),
            Type=policy_type,
        )
        policy = response["Policy"]
        logger.info("Created policy %s.", name)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a CreatePolicyReferência da API AWSSDK for Python (Boto3).

Crie uma conta do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma conta do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates a new AWS Organizations account.
/// </summary>
public class CreateAccount
{
    /// <summary>
    /// Initializes an Organizations client object and uses it to create
    /// the new account with the name specified in accountName.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();
        var accountName = "ExampleAccount";
        var email = "someone@example.com";

        var request = new CreateAccountRequest
        {
            AccountName = accountName,
            Email = email,
        };

        var response = await client.CreateAccountAsync(request);
        var status = response.CreateAccountStatus;

        Console.WriteLine($"The staus of {status.AccountName} is
{status.State}.");
    }
```

```
    }
```

- Para obter detalhes da API, consulte CreateAccounta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar uma conta de membro que automaticamente faça parte da organização

O exemplo a seguir mostra como criar uma conta de membro em uma organização. A conta de membro é configurada com o nome Production Account e o endereço de e-mail susan@example.com. Organizations cria automaticamente uma função do IAM usando o nome padrão de OrganizationAccountAccessRole porque o parâmetro roleName não está especificado. Além disso, a configuração que permite que usuários ou funções do IAM com permissões suficientes acessem os dados de faturamento da conta é definida com o valor padrão de ALLOW porque o IamUserAccessToBilling parâmetro não foi especificado. O Organizations automaticamente envia um e-mail de “Boas-vindas à AWS” para Susan:

```
aws organizations create-account --email susan@example.com --account-name
 "Production Account"
```

A saída inclui um objeto de solicitação que mostra que o status agora é `IN_PROGRESS`:

```
{
        "CreateAccountStatus": {
                "State": "IN_PROGRESS",
                "Id": "car-examplecreateaccountrequestid111"
        }
}
```

Posteriormente, você pode consultar o status atual da solicitação fornecendo o valor de resposta Id ao describe-create-account-status comando como o valor do create-account-request-id parâmetro.

Para obter informações, consulte Creating an AWS Account in Your Organization no Guia do usuário do AWS Organizations.

- Para obter detalhes da API, consulte CreateAccountem Referência de AWS CLI Comandos.

Crie uma organização do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma organização do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates an organization in AWS Organizations.
/// </summary>
public class CreateOrganization
{
    /// <summary>
    /// Creates an Organizations client object and then uses it to create
    /// a new organization with the default user as the administrator, and
    /// then displays information about the new organization.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var response = await client.CreateOrganizationAsync(new
CreateOrganizationRequest
        {
            FeatureSet = "ALL",
        });

        Organization newOrg = response.Organization;
```

```
            Console.WriteLine($"Organization: {newOrg.Id} Main Accoount:
 {newOrg.MasterAccountId}");
        }
    }
```

- Para obter detalhes da API, consulte CreateOrganizationa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: como criar uma organização

Bill quer criar uma organização usando as credenciais da conta 111111111111. O exemplo a seguir mostra que a conta se torna a conta principal na nova organização. Como ele não especificou um conjunto de recursos, a nova organização usa como padrão todos os recursos habilitados e as políticas de controle de serviços são habilitadas na raiz.

```
aws organizations create-organization
```

A saída inclui um objeto de organização com detalhes sobre a nova organização:

```
{
        "Organization": {
                "AvailablePolicyTypes": [
                        {
                                "Status": "ENABLED",
                                "Type": "SERVICE_CONTROL_POLICY"
                        }
                ],
                "MasterAccountId": "111111111111",
                "MasterAccountArn": "arn:aws:organizations::111111111111:account/
o-exampleorgid/111111111111",
                "MasterAccountEmail": "bill@example.com",
                "FeatureSet": "ALL",
                "Id": "o-exampleorgid",
                "Arn": "arn:aws:organizations::111111111111:organization/o-
exampleorgid"
```

```
        }
}
```

Exemplo 2: como criar uma organização apenas com os recursos de faturamento consolidados

O seguinte exemplo cria uma organização compatível apenas com os recursos de faturamento consolidados:

```
aws organizations create-organization --feature-set CONSOLIDATED_BILLING
```

A saída inclui um objeto de organização com detalhes sobre a nova organização:

```
{
        "Organization": {
                "Arn": "arn:aws:organizations::111111111111:organization/o-
exampleorgid",
                "AvailablePolicyTypes": [],
                "Id": "o-exampleorgid",
                "MasterAccountArn": "arn:aws:organizations::111111111111:account/
o-exampleorgid/111111111111",
                "MasterAccountEmail": "bill@example.com",
                "MasterAccountId": "111111111111",
                "FeatureSet": "CONSOLIDATED_BILLING"
        }
}
```

Para obter informações, consulte Criar uma organização no Guia do usuário do AWS Organizations.

- Para obter detalhes da API, consulte CreateOrganizationem Referência de AWS CLI Comandos.

Crie uma unidade organizacional do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma unidade organizacional do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates a new organizational unit in AWS Organizations.
/// </summary>
public class CreateOrganizationalUnit
{
    /// <summary>
    /// Initializes an Organizations client object and then uses it to call
    /// the CreateOrganizationalUnit method. If the call succeeds, it
    /// displays information about the new organizational unit.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var orgUnitName = "ProductDevelopmentUnit";

        var request = new CreateOrganizationalUnitRequest
        {
            Name = orgUnitName,
            ParentId = "r-0000",
        };

        var response = await client.CreateOrganizationalUnitAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
```

```
                Console.WriteLine($"Successfully created organizational unit:
 {orgUnitName}.");
                Console.WriteLine($"Organizational unit {orgUnitName} Details");
                Console.WriteLine($"ARN: {response.OrganizationalUnit.Arn} Id:
 {response.OrganizationalUnit.Id}");
            }
            else
            {
                Console.WriteLine("Could not create new organizational unit.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateOrganizationalUnita Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar uma unidade organizacional em uma unidade organizacional raiz ou pai

O seguinte exemplo mostra como criar uma UO chamada AccountingOU:

```
aws organizations create-organizational-unit --parent-id r-examplerootid111 --
name AccountingOU
```

A saída inclui um objeto organizationalUnit que contém detalhes sobre a nova UO:

```
{
        "OrganizationalUnit": {
                "Id": "ou-examplerootid111-exampleouid111",
                "Arn": "arn:aws:organizations::111111111111:ou/o-exampleorgid/ou-
examplerootid111-exampleouid111",
                "Name": "AccountingOU"
        }
}
```

- Para obter detalhes da API, consulte CreateOrganizationalUnitem Referência de AWS CLI Comandos.

Exclua uma política do Organizations usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma política do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Deletes an existing AWS Organizations policy.
/// </summary>
public class DeletePolicy
{
    /// <summary>
    /// Initializes the Organizations client object and then uses it to
    /// delete the policy with the specified policyId.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var policyId = "p-00000000";

        var request = new DeletePolicyRequest
        {
            PolicyId = policyId,
        };

        var response = await client.DeletePolicyAsync(request);
```

```
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully deleted Policy: {policyId}.");
            }
            else
            {
                Console.WriteLine($"Could not delete Policy: {policyId}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir uma política

O exemplo a seguir mostra como excluir uma política de uma organização. O exemplo pressupõe que você já separou a política de todas as entidades:

```
aws organizations delete-policy --policy-id p-examplepolicyid111
```

- Para obter detalhes da API, consulte DeletePolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_policy(policy_id, orgs_client):
```

```
    """
    Deletes a policy.

    :param policy_id: The ID of the policy to delete.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.delete_policy(PolicyId=policy_id)
        logger.info("Deleted policy %s.", policy_id)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_id)
        raise
```

- Para obter detalhes da API, consulte a DeletePolicyReferência da API AWSSDK for Python (Boto3).

Exclua uma organização do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma organização do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to delete an existing organization using the AWS
/// Organizations Service.
```

```
    /// </summary>
    public class DeleteOrganization
    {
        /// <summary>
        /// Initializes the Organizations client and then calls
        /// DeleteOrganizationAsync to delete the organization.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            var response = await client.DeleteOrganizationAsync(new
 DeleteOrganizationRequest());

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine("Successfully deleted organization.");
            }
            else
            {
                Console.WriteLine("Could not delete organization.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteOrganizationa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir uma organização

O exemplo a seguir mostra como excluir uma organização. Você deve ser administrador da conta principal na organização para poder realizar essa operação. O exemplo pressupõe que você já removeu todas as contas de membro, UOs e políticas da organização:

```
aws organizations delete-organization
```

- Para obter detalhes da API, consulte DeleteOrganizationem Referência de AWS CLI Comandos.

Exclua uma unidade organizacional do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma unidade organizacional do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to delete an existing AWS Organizations organizational unit.
/// </summary>
public class DeleteOrganizationalUnit
{
    /// <summary>
    /// Initializes the Organizations client object and calls
    /// DeleteOrganizationalUnitAsync to delete the organizational unit
    /// with the selected ID.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var orgUnitId = "ou-0000-00000000";

        var request = new DeleteOrganizationalUnitRequest
```

```
            {
                OrganizationalUnitId = orgUnitId,
            };

            var response = await client.DeleteOrganizationalUnitAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully deleted the organizational unit
 with ID: {orgUnitId}.");
            }
            else
            {
                Console.WriteLine($"Could not delete the organizational unit with
 ID: {orgUnitId}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteOrganizationalUnita Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir uma UO

O exemplo a seguir mostra como excluir uma UO. O exemplo pressupõe que você já removeu todas as contas e outras UOs da UO:

```
aws organizations delete-organizational-unit --organizational-unit-id ou-
examplerootid111-exampleouid111
```

- Para obter detalhes da API, consulte DeleteOrganizationalUnitem Referência de AWS CLI Comandos.

Descreva uma política do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma política do Organizações.

CLI

AWS CLI

Como obter informações sobre uma política

O seguinte exemplo mostra como solicitar informações sobre uma política:

```
aws organizations describe-policy --policy-id p-examplepolicyid111
```

A saída inclui um objeto de política que contém detalhes sobre a política:

```
{
        "Policy": {
                "Content": "{\n  \"Version\": \"2012-10-17\",\n  \"Statement
\": [\n    {\n      \"Effect\": \"Allow\",\n      \"Action\": \"*\",\n
 \"Resource\": \"*\"\n    }\n  ]\n}",
                "PolicySummary": {
                        "Arn": "arn:aws:organizations::111111111111:policy/o-
exampleorgid/service_control_policy/p-examplepolicyid111",
                        "Type": "SERVICE_CONTROL_POLICY",
                        "Id": "p-examplepolicyid111",
                        "AwsManaged": false,
                        "Name": "AllowAllS3Actions",
                        "Description": "Enables admins to delegate S3
 permissions"
                }
        }
}
```

- Para obter detalhes da API, consulte DescribePolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_policy(policy_id, orgs_client):
    """
    Describes a policy.

    :param policy_id: The ID of the policy to describe.
    :param orgs_client: The Boto3 Organizations client.
    :return: The description of the policy.
    """
    try:
        response = orgs_client.describe_policy(PolicyId=policy_id)
        policy = response["Policy"]
        logger.info("Got policy %s.", policy_id)
    except ClientError:
        logger.exception("Couldn't get policy %s.", policy_id)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a DescribePolicyReferência da API AWSSDK for Python (Boto3).

Desvincule uma política do Organizations de um destino usando um SDK da AWS

O exemplo de código a seguir mostra como desanexar uma política do Organizações de um destino.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to detach a policy from an AWS Organizations organization,
/// organizational unit, or account.
/// </summary>
public class DetachPolicy
{
    /// <summary>
    /// Initializes the Organizations client object and uses it to call
    /// DetachPolicyAsync to detach the policy.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var policyId = "p-00000000";
        var targetId = "r-0000";

        var request = new DetachPolicyRequest
        {
            PolicyId = policyId,
            TargetId = targetId,
        };

        var response = await client.DetachPolicyAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
```

```
            {
                Console.WriteLine($"Successfully detached policy with Policy Id:
 {policyId}.");
            }
            else
            {
                Console.WriteLine("Could not detach the policy.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DetachPolicya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como separar uma política de uma raiz, UO ou conta

O seguinte exemplo mostra como separar uma política de uma UO:

```
aws organizations  detach-policy  --target-id ou-examplerootid111-exampleouid111
 --policy-id p-examplepolicyid111
```

- Para obter detalhes da API, consulte DetachPolicyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def detach_policy(policy_id, target_id, orgs_client):
    """
    Detaches a policy from a target.
```

```
    :param policy_id: The ID of the policy to detach.
    :param target_id: The ID of the resource where the policy is currently
attached.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.detach_policy(PolicyId=policy_id, TargetId=target_id)
        logger.info("Detached policy %s from target %s.", policy_id, target_id)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from target %s.", policy_id, target_id
        )
        raise
```

- Para obter detalhes da API, consulte a DetachPolicyReferência da API AWSSDK for Python (Boto3).

Liste contas de uma organização do Organizations usando um SDK da AWS

Os exemplos de código a seguir mostram como listar contas de uma organização do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
```

```
    /// Uses the AWS Organizations service to list the accounts associated
    /// with the default account.
    /// </summary>
    public class ListAccounts
    {
        /// <summary>
        /// Creates the Organizations client and then calls its
        /// ListAccountsAsync method.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            var request = new ListAccountsRequest
            {
                MaxResults = 5,
            };

            var response = new ListAccountsResponse();
            try
            {
                do
                {
                    response = await client.ListAccountsAsync(request);
                    response.Accounts.ForEach(a => DisplayAccounts(a));
                    if (response.NextToken is not null)
                    {
                        request.NextToken = response.NextToken;
                    }
                }
                while (response.NextToken is not null);
            }
            catch (AWSOrganizationsNotInUseException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Displays information about an Organizations account.
        /// </summary>
        /// <param name="account">An Organizations account for which to display
        /// information on the console.</param>
```

```
        private static void DisplayAccounts(Account account)
        {
            string accountInfo = $"{account.Id}
 {account.Name}\t{account.Status}";

            Console.WriteLine(accountInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListAccountsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como recuperar uma lista de todas as contas de uma organização

O seguinte exemplo mostra como solicitar uma lista das contas de uma organização:

```
aws organizations list-accounts
```

A saída inclui uma lista de objetos de resumo da conta.

```
{
        "Accounts": [
                {
                        "Arn": "arn:aws:organizations::111111111111:account/o-
exampleorgid/111111111111",
                        "JoinedMethod": "INVITED",
                        "JoinedTimestamp": 1481830215.45,
                        "Id": "111111111111",
                        "Name": "Master Account",
                        "Email": "bill@example.com",
                        "Status": "ACTIVE"
                },
                {
                        "Arn": "arn:aws:organizations::111111111111:account/o-
exampleorgid/222222222222",
                        "JoinedMethod": "INVITED",
                        "JoinedTimestamp": 1481835741.044,
                        "Id": "222222222222",
```

```
                        "Name": "Production Account",
                        "Email": "alice@example.com",
                        "Status": "ACTIVE"
                },
                {
                        "Arn": "arn:aws:organizations::111111111111:account/o-
exampleorgid/333333333333",
                        "JoinedMethod": "INVITED",
                        "JoinedTimestamp": 1481835795.536,
                        "Id": "333333333333",
                        "Name": "Development Account",
                        "Email": "juan@example.com",
                        "Status": "ACTIVE"
                },
                {
                        "Arn": "arn:aws:organizations::111111111111:account/o-
exampleorgid/444444444444",
                        "JoinedMethod": "INVITED",
                        "JoinedTimestamp": 1481835812.143,
                        "Id": "444444444444",
                        "Name": "Test Account",
                        "Email": "anika@example.com",
                        "Status": "ACTIVE"
                }
        ]
}
```

- Para obter detalhes da API, consulte ListAccountsem Referência de AWS CLI Comandos.

Liste unidades organizacionais do Organizations usando um SDK da AWS

O exemplo de código a seguir mostra como listar unidades organizacionais do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Lists the AWS Organizations organizational units that belong to an
/// organization.
/// </summary>
public class ListOrganizationalUnitsForParent
{
    /// <summary>
    /// Initializes the Organizations client object and then uses it to
    /// call the ListOrganizationalUnitsForParentAsync method to retrieve
    /// the list of organizational units.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var parentId = "r-0000";

        var request = new ListOrganizationalUnitsForParentRequest
        {
            ParentId = parentId,
            MaxResults = 5,
        };

        var response = new ListOrganizationalUnitsForParentResponse();
        try
        {
            do
            {
                response = await
client.ListOrganizationalUnitsForParentAsync(request);
                response.OrganizationalUnits.ForEach(u =>
DisplayOrganizationalUnit(u));
                if (response.NextToken is not null)
                {
                    request.NextToken = response.NextToken;
                }
            }
```

```
                while (response.NextToken is not null);
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Displays information about an Organizations organizational unit.
        /// </summary>
        /// <param name="unit">The OrganizationalUnit for which to display
        /// information.</param>
        public static void DisplayOrganizationalUnit(OrganizationalUnit unit)
        {
            string accountInfo = $"{unit.Id} {unit.Name}\t{unit.Arn}";

            Console.WriteLine(accountInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListOrganizationalUnitsForParenta Referência AWS SDK for .NET da API.

Liste as políticas do Organizations usando um SDK da AWS

O exemplo de código a seguir mostra como listar políticas do Organizations.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
```

```
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to list the AWS Organizations policies associated with an
/// organization.
/// </summary>
public class ListPolicies
{
    /// <summary>
    /// Initializes an Organizations client object, and then calls its
    /// ListPoliciesAsync method.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        // The value for the Filter parameter is required and must must be
        // one of the following:
        //     AISERVICES_OPT_OUT_POLICY
        //     BACKUP_POLICY
        //     SERVICE_CONTROL_POLICY
        //     TAG_POLICY
        var request = new ListPoliciesRequest
        {
            Filter = "SERVICE_CONTROL_POLICY",
            MaxResults = 5,
        };

        var response = new ListPoliciesResponse();
        try
        {
            do
            {
                response = await client.ListPoliciesAsync(request);
                response.Policies.ForEach(p => DisplayPolicies(p));
                if (response.NextToken is not null)
                {
                    request.NextToken = response.NextToken;
                }
            }
            while (response.NextToken is not null);
```

```
            }
            catch (AWSOrganizationsNotInUseException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Displays information about the Organizations policies associated
        /// with an organization.
        /// </summary>
        /// <param name="policy">An Organizations policy summary to display
        /// information on the console.</param>
        private static void DisplayPolicies(PolicySummary policy)
        {
            string policyInfo = $"{policy.Id}
 {policy.Name}\t{policy.Description}";

            Console.WriteLine(policyInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como recuperar uma lista de todas as políticas de um determinado tipo de uma organização

O seguinte exemplo mostra como obter uma lista de SCPs, conforme especificado pelo parâmetro do filtro:

```
aws organizations list-policies --filter SERVICE_CONTROL_POLICY
```

A saída inclui uma lista de políticas com informações resumidas:

```
{
        "Policies": [
                {
```

```
                        "Type": "SERVICE_CONTROL_POLICY",
                        "Name": "AllowAllS3Actions",
                        "AwsManaged": false,
                        "Id": "p-examplepolicyid111",
                        "Arn": "arn:aws:organizations::111111111111:policy/
service_control_policy/p-examplepolicyid111",
                        "Description": "Enables account admins to delegate
 permissions for any S3 actions to users and roles in their accounts."
                },
                {
                        "Type": "SERVICE_CONTROL_POLICY",
                        "Name": "AllowAllEC2Actions",
                        "AwsManaged": false,
                        "Id": "p-examplepolicyid222",
                        "Arn": "arn:aws:organizations::111111111111:policy/
service_control_policy/p-examplepolicyid222",
                        "Description": "Enables account admins to delegate
 permissions for any EC2 actions to users and roles in their accounts."
                },
                {
                        "AwsManaged": true,
                        "Description": "Allows access to every operation",
                        "Type": "SERVICE_CONTROL_POLICY",
                        "Id": "p-FullAWSAccess",
                        "Arn": "arn:aws:organizations::aws:policy/
service_control_policy/p-FullAWSAccess",
                        "Name": "FullAWSAccess"
                }
        ]
}
```

- Para obter detalhes da API, consulte ListPoliciesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(policy_filter, orgs_client):
    """
    Lists the policies for the account, limited to the specified filter.

    :param policy_filter: The kind of policies to return.
    :param orgs_client: The Boto3 Organizations client.
    :return: The list of policies found.
    """
    try:
        response = orgs_client.list_policies(Filter=policy_filter)
        policies = response["Policies"]
        logger.info("Found %s %s policies.", len(policies), policy_filter)
    except ClientError:
        logger.exception("Couldn't get %s policies.", policy_filter)
        raise
    else:
        return policies
```

- Para obter detalhes da API, consulte a ListPoliciesReferência da API AWSSDK for Python (Boto3).

Exemplos de código para o Amazon Personalize usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon Personalize – Mais informações sobre o Amazon Personalize.
- Referência da API do Amazon Personalize – Detalhes sobre todas as ações disponíveis do Amazon Personalize.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon Personalize usando SDKs da AWS
  - Crie um trabalho de inferência em lote com o Amazon Personalize usando um SDK da AWS
  - Crie um trabalho de segmento em lote com o Amazon Personalize usando um SDK da AWS
  - Crie uma campanha com o Amazon Personalize usando um SDK da AWS
  - Crie um conjunto de dados com o Amazon Personalize usando um SDK da AWS
  - Crie um trabalho de exportação de conjunto de dados com o Amazon Personalize usando um SDK da AWS
  - Crie um grupo de conjuntos de dados com o Amazon Personalize usando um SDK da AWS
  - Crie um trabalho de importação de conjunto de dados com o Amazon Personalize usando um SDK AWS
  - Crie um esquema de domínio com o Amazon Personalize usando um SDK da AWS
  - Crie um filtro com o Amazon Personalize usando um SDK da AWS
  - Crie um recomendador com o Amazon Personalize usando um SDK da AWS
  - Crie um esquema com o Amazon Personalize usando um SDK da AWS
  - Crie uma solução com o Amazon Personalize usando um SDK da AWS
  - Crie uma versão de solução com o Amazon Personalize usando um SDK da AWS
  - Crie um rastreador de eventos com o Amazon Personalize usando um SDK da AWS
  - Exclua uma campanha no Amazon Personalize usando um SDK da AWS
  - Exclua uma solução no Amazon Personalize usando um SDK da AWS
  - Exclua um rastreador de eventos com o Amazon Personalize usando um SDK da AWS
  - Descreva uma campanha no Amazon Personalize usando um SDK da AWS
  - Descreva uma fórmula no Amazon Personalize usando um SDK da AWS
  - Descreva uma solução no Amazon Personalize usando um SDK da AWS
  - Liste campanhas no Amazon Personalize usando um SDK da AWS

  - Liste grupos de conjuntos de dados no Amazon Personalize usando um SDK da AWS

- Liste fórmulas no Amazon Personalize usando um SDK da AWS
- Liste soluções no Amazon Personalize usando um SDK da AWS
- Atualize uma campanha no Amazon Personalize usando um SDK da AWS

Ações para o Amazon Personalize usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um trabalho de inferência em lote com o Amazon Personalize usando um SDK da AWS
- Crie um trabalho de segmento em lote com o Amazon Personalize usando um SDK da AWS
- Crie uma campanha com o Amazon Personalize usando um SDK da AWS
- Crie um conjunto de dados com o Amazon Personalize usando um SDK da AWS
- Crie um trabalho de exportação de conjunto de dados com o Amazon Personalize usando um SDK da AWS
- Crie um grupo de conjuntos de dados com o Amazon Personalize usando um SDK da AWS
- Crie um trabalho de importação de conjunto de dados com o Amazon Personalize usando um SDK AWS
- Crie um esquema de domínio com o Amazon Personalize usando um SDK da AWS
- Crie um filtro com o Amazon Personalize usando um SDK da AWS
- Crie um recomendador com o Amazon Personalize usando um SDK da AWS
- Crie um esquema com o Amazon Personalize usando um SDK da AWS
- Crie uma solução com o Amazon Personalize usando um SDK da AWS
- Crie uma versão de solução com o Amazon Personalize usando um SDK da AWS
- Crie um rastreador de eventos com o Amazon Personalize usando um SDK da AWS
- Exclua uma campanha no Amazon Personalize usando um SDK da AWS
- Exclua uma solução no Amazon Personalize usando um SDK da AWS
- Exclua um rastreador de eventos com o Amazon Personalize usando um SDK da AWS
- Descreva uma campanha no Amazon Personalize usando um SDK da AWS
- Descreva uma fórmula no Amazon Personalize usando um SDK da AWS
- Descreva uma solução no Amazon Personalize usando um SDK da AWS

- Liste campanhas no Amazon Personalize usando um SDK da AWS
- Liste grupos de conjuntos de dados no Amazon Personalize usando um SDK da AWS
- Liste fórmulas no Amazon Personalize usando um SDK da AWS
- Liste soluções no Amazon Personalize usando um SDK da AWS
- Atualize uma campanha no Amazon Personalize usando um SDK da AWS

Crie um trabalho de inferência em lote com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um trabalho de interface em lote do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static String createPersonalizeBatchInferenceJob(PersonalizeClient
personalizeClient,
                        String solutionVersionArn,
                        String jobName,
                        String s3InputDataSourcePath,
                        String s3DataDestinationPath,
                        String roleArn,
                        String explorationWeight,
                        String explorationItemAgeCutOff) {

                long waitInMilliseconds = 60 * 1000;
                String status;
                String batchInferenceJobArn;

                try {

                        // Set up data input and output parameters.
```

```
                        S3DataConfig inputSource = S3DataConfig.builder()
                                        .path(s3InputDataSourcePath)
                                        .build();

                        S3DataConfig outputDestination = S3DataConfig.builder()
                                        .path(s3DataDestinationPath)
                                        .build();

                        BatchInferenceJobInput jobInput =
BatchInferenceJobInput.builder()
                                        .s3DataSource(inputSource)
                                        .build();

                        BatchInferenceJobOutput jobOutputLocation =
BatchInferenceJobOutput.builder()
                                        .s3DataDestination(outputDestination)
                                        .build();

                        // Optional code to build the User-Personalization
specific item exploration
                        // config.
                        HashMap<String, String> explorationConfig = new
HashMap<>();

                        explorationConfig.put("explorationWeight",
explorationWeight);
                        explorationConfig.put("explorationItemAgeCutOff",
explorationItemAgeCutOff);

                        BatchInferenceJobConfig jobConfig =
BatchInferenceJobConfig.builder()
                                        .itemExplorationConfig(explorationConfig)
                                        .build();

                        // End optional User-Personalization recipe specific
code.

                        CreateBatchInferenceJobRequest
createBatchInferenceJobRequest = CreateBatchInferenceJobRequest
                                        .builder()
                                        .solutionVersionArn(solutionVersionArn)
                                        .jobInput(jobInput)
                                        .jobOutput(jobOutputLocation)
                                        .jobName(jobName)
```

```
                                        .roleArn(roleArn)
                                        .batchInferenceJobConfig(jobConfig) //
Optional
                                        .build();

                        batchInferenceJobArn =
personalizeClient.createBatchInferenceJob(createBatchInferenceJobRequest)
                                        .batchInferenceJobArn();

                        DescribeBatchInferenceJobRequest
describeBatchInferenceJobRequest = DescribeBatchInferenceJobRequest
                                        .builder()

.batchInferenceJobArn(batchInferenceJobArn)
                                        .build();

                        long maxTime = Instant.now().getEpochSecond() + 3 * 60 *
60;
                        while (Instant.now().getEpochSecond() < maxTime) {

                                BatchInferenceJob batchInferenceJob =
personalizeClient

.describeBatchInferenceJob(describeBatchInferenceJobRequest)
                                                .batchInferenceJob();

                                status = batchInferenceJob.status();
                                System.out.println("Batch inference job status: "
+ status);

                                if (status.equals("ACTIVE") ||
status.equals("CREATE FAILED")) {
                                        break;
                                }
                                try {
                                        Thread.sleep(waitInMilliseconds);
                                } catch (InterruptedException e) {
                                        System.out.println(e.getMessage());
                                }
                        }
                        return batchInferenceJobArn;

                } catch (PersonalizeException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
```

```
                }
                return "";
        }
```

- Para obter detalhes da API, consulte CreateBatchInferenceJoba Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateBatchInferenceJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the batch inference job's parameters.

export const createBatchInferenceJobParam = {
  jobName: 'JOB_NAME',
  jobInput: {         /* required */
    s3DataSource: {   /* required */
      path: 'INPUT_PATH', /* required */
      // kmsKeyArn: 'INPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  jobOutput: {         /* required */
    s3DataDestination: {   /* required */
      path: 'OUTPUT_PATH', /* required */
      // kmsKeyArn: 'OUTPUT_KMS_KEY_ARN' /* optional */'
    }
```

```
  },
  roleArn: 'ROLE_ARN', /* required */
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  numResults: 20 /* optional integer*/
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateBatchInferenceJobCommand(createBatchInferenceJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateBatchInferenceJoba Referência AWS SDK for JavaScript da API.

Crie um trabalho de segmento em lote com o Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como criar um trabalho de segmento em lotes do Amazon Personalize.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
```

```
import { CreateBatchSegmentJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the batch segment job's parameters.

export const createBatchSegmentJobParam = {
  jobName: 'NAME',
  jobInput: {         /* required */
    s3DataSource: {   /* required */
      path: 'INPUT_PATH', /* required */
      // kmsKeyArn: 'INPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  jobOutput: {         /* required */
    s3DataDestination: {   /* required */
      path: 'OUTPUT_PATH', /* required */
      // kmsKeyArn: 'OUTPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  roleArn: 'ROLE_ARN', /* required */
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  numResults: 20 /* optional */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateBatchSegmentJobCommand(createBatchSegmentJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateBatchSegmentJoba Referência AWS SDK for JavaScript da API.

Crie uma campanha com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma campanha do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalCompaign(PersonalizeClient
personalizeClient, String solutionVersionArn,
           String name) {

       try {
           CreateCampaignRequest createCampaignRequest =
CreateCampaignRequest.builder()
                   .minProvisionedTPS(1)
                   .solutionVersionArn(solutionVersionArn)
                   .name(name)
                   .build();

           CreateCampaignResponse campaignResponse =
personalizeClient.createCampaign(createCampaignRequest);
           System.out.println("The campaign ARN is " +
campaignResponse.campaignArn());
           return campaignResponse.campaignArn();

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "" ;
   }
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.

import { CreateCampaignCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the campaign's parameters.
export const createCampaignParam = {
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  name: 'NAME',  /* required */
  minProvisionedTPS: 1    /* optional integer */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateCampaignCommand(createCampaignParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for JavaScript da API.

Crie um conjunto de dados com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um conjunto de dados do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static String createDataset(PersonalizeClient personalizeClient,
        String datasetName,
        String datasetGroupArn,
        String datasetType,
        String schemaArn) {
    try {
        CreateDatasetRequest request = CreateDatasetRequest.builder()
                .name(datasetName)
                .datasetGroupArn(datasetGroupArn)
                .datasetType(datasetType)
                .schemaArn(schemaArn)
                .build();

        String datasetArn = personalizeClient.createDataset(request)
                .datasetArn();
        System.out.println("Dataset " + datasetName + " created.");
        return datasetArn;

    } catch (PersonalizeException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
    return "";
}
```

- Para obter detalhes da API, consulte CreateDataset a Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateDatasetCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the dataset's parameters.
export const createDatasetParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  datasetType: 'DATASET_TYPE', /* required */
  name: 'NAME', /* required */
  schemaArn: 'SCHEMA_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetCommand(createDatasetParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDataset a Referência AWS SDK for JavaScript da API.

Crie um trabalho de exportação de conjunto de dados com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um trabalho de exportação de conjunto de dados do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createDatasetExportJob(PersonalizeClient
personalizeClient,
           String jobName,
           String datasetArn,
           IngestionMode ingestionMode,
           String roleArn,
           String s3BucketPath,
           String kmsKeyArn) {

       long waitInMilliseconds = 30 * 1000; // 30 seconds
       String status = null;

       try {

           S3DataConfig exportS3DataConfig =
S3DataConfig.builder().path(s3BucketPath).kmsKeyArn(kmsKeyArn).build();
           DatasetExportJobOutput jobOutput =
DatasetExportJobOutput.builder().s3DataDestination(exportS3DataConfig)
                   .build();

           CreateDatasetExportJobRequest createRequest =
CreateDatasetExportJobRequest.builder()
                   .jobName(jobName)
                   .datasetArn(datasetArn)
                   .ingestionMode(ingestionMode)
                   .jobOutput(jobOutput)
```

```
                    .roleArn(roleArn)
                    .build();

            String datasetExportJobArn =
personalizeClient.createDatasetExportJob(createRequest).datasetExportJobArn();

            DescribeDatasetExportJobRequest describeDatasetExportJobRequest =
DescribeDatasetExportJobRequest.builder()
                    .datasetExportJobArn(datasetExportJobArn)
                    .build();

            long maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            while (Instant.now().getEpochSecond() < maxTime) {

                DatasetExportJob datasetExportJob = personalizeClient

.describeDatasetExportJob(describeDatasetExportJobRequest)
                        .datasetExportJob();

                status = datasetExportJob.status();
                System.out.println("Export job status: " + status);

                if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                    return status;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetExportJoba Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateDatasetExportJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the export job parameters.
export const datasetExportJobParam = {
  datasetArn: 'DATASET_ARN', /* required */
  jobOutput: {
    s3DataDestination: {
        path: 'S3_DESTINATION_PATH' /* required */
        //kmsKeyArn: 'ARN'  /* include if your bucket uses AWS KMS for encryption
    }
  },
  jobName: 'NAME',/* required */
  roleArn: 'ROLE_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetExportJobCommand(datasetExportJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetExportJoba Referência AWS SDK for JavaScript da API.

Crie um grupo de conjuntos de dados com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um grupo de conjuntos de dados do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createDatasetGroup(PersonalizeClient personalizeClient,
String datasetGroupName) {

       try {
           CreateDatasetGroupRequest createDatasetGroupRequest =
CreateDatasetGroupRequest.builder()
                   .name(datasetGroupName)
                   .build();
           return
personalizeClient.createDatasetGroup(createDatasetGroupRequest).datasetGroupArn();
       } catch (PersonalizeException e) {
           System.out.println(e.awsErrorDetails().errorMessage());
       }
       return "";
   }
```

Criar um grupo de conjunto de dados de domínio.

```
    public static String createDomainDatasetGroup(PersonalizeClient
 personalizeClient,
            String datasetGroupName,
            String domain) {

        try {
            CreateDatasetGroupRequest createDatasetGroupRequest =
 CreateDatasetGroupRequest.builder()
                    .name(datasetGroupName)
                    .domain(domain)
                    .build();
            return
 personalizeClient.createDatasetGroup(createDatasetGroupRequest).datasetGroupArn();
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetGroupa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.

import { CreateDatasetGroupCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});
```

```
// Set the dataset group parameters.
export const createDatasetGroupParam = {
  name: 'NAME' /* required */
}

export const run = async (createDatasetGroupParam) => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetGroupCommand(createDatasetGroupParam));
    console.log("Success", response);
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run(createDatasetGroupParam);
```

Criar um grupo de conjunto de dados de domínio.

```
// Get service clients module and commands using ES6 syntax.
import {  CreateDatasetGroupCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the domain dataset group parameters.
export const domainDatasetGroupParams = {
  name: 'NAME',  /* required */
  domain: 'DOMAIN'   /* required for a domain dsg, specify ECOMMERCE or
 VIDEO_ON_DEMAND */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetGroupCommand(domainDatasetGroupParams));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
```

```
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetGroupa Referência AWS SDK for JavaScript da API.

Crie um trabalho de importação de conjunto de dados com o Amazon Personalize usando um SDK AWS

Os exemplos de código a seguir mostram como criar um trabalho de importação de conjuntos dados do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalizeDatasetImportJob(PersonalizeClient
personalizeClient,
           String jobName,
           String datasetArn,
           String s3BucketPath,
           String roleArn) {

       long waitInMilliseconds = 60 * 1000;
       String status;
       String datasetImportJobArn;

       try {
           DataSource importDataSource = DataSource.builder()
                   .dataLocation(s3BucketPath)
                   .build();
```

```
            CreateDatasetImportJobRequest createDatasetImportJobRequest =
CreateDatasetImportJobRequest.builder()
                    .datasetArn(datasetArn)
                    .dataSource(importDataSource)
                    .jobName(jobName)
                    .roleArn(roleArn)
                    .build();

            datasetImportJobArn =
personalizeClient.createDatasetImportJob(createDatasetImportJobRequest)
                    .datasetImportJobArn();
            DescribeDatasetImportJobRequest describeDatasetImportJobRequest =
DescribeDatasetImportJobRequest.builder()
                    .datasetImportJobArn(datasetImportJobArn)
                    .build();

            long maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            while (Instant.now().getEpochSecond() < maxTime) {

                DatasetImportJob datasetImportJob = personalizeClient

.describeDatasetImportJob(describeDatasetImportJobRequest)
                        .datasetImportJob();

                status = datasetImportJob.status();
                System.out.println("Dataset import job status: " + status);

                if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return datasetImportJobArn;

        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetImportJoba Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import {CreateDatasetImportJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the dataset import job parameters.
export const datasetImportJobParam = {
  datasetArn: 'DATASET_ARN', /* required */
  dataSource: {  /* required */
    dataLocation: 'S3_PATH'
  },
  jobName: 'NAME',/* required */
  roleArn: 'ROLE_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetImportJobCommand(datasetImportJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
```

```
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetImportJoba Referência AWS SDK for JavaScript da API.

Crie um esquema de domínio com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um esquema de domínio do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createDomainSchema(PersonalizeClient personalizeClient,
String schemaName, String domain,
           String filePath) {

       String schema = null;
       try {
           schema = new String(Files.readAllBytes(Paths.get(filePath)));
       } catch (IOException e) {
           System.out.println(e.getMessage());
       }

       try {
           CreateSchemaRequest createSchemaRequest =
CreateSchemaRequest.builder()
                   .name(schemaName)
                   .domain(domain)
                   .schema(schema)
                   .build();
```

```
            String schemaArn =
 personalizeClient.createSchema(createSchemaRequest).schemaArn();

            System.out.println("Schema arn: " + schemaArn);

            return schemaArn;

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSchemaCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

import fs from 'fs';

let schemaFilePath = "SCHEMA_PATH";
let mySchema = "";
```

```
try {
  mySchema = fs.readFileSync(schemaFilePath).toString();
} catch (err) {
  mySchema = 'TEST' // for unit tests.
}

// Set the domain schema parameters.
export const createDomainSchemaParam = {
  name: 'NAME', /* required */
  schema: mySchema, /* required */
  domain: 'DOMAIN'   /* required for a domain dataset group, specify ECOMMERCE or
 VIDEO_ON_DEMAND */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSchemaCommand(createDomainSchemaParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for JavaScript da API.

Crie um filtro com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um filtro Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static String createFilter(PersonalizeClient personalizeClient,
        String filterName,
        String datasetGroupArn,
        String filterExpression) {
    try {
        CreateFilterRequest request = CreateFilterRequest.builder()
                .name(filterName)
                .datasetGroupArn(datasetGroupArn)
                .filterExpression(filterExpression)
                .build();

        return personalizeClient.createFilter(request).filterArn();
    } catch (PersonalizeException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
    return "";
}
```

- Para obter detalhes da API, consulte CreateFiltera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateFilterCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the filter's parameters.
export const createFilterParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  name: 'NAME', /* required */
  filterExpression: 'FILTER_EXPRESSION' /*required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateFilterCommand(createFilterParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateFiltera Referência AWS SDK for JavaScript da API.

Crie um recomendador com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um recomendador do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createRecommender(PersonalizeClient personalizeClient,
            String name,
            String datasetGroupArn,
            String recipeArn) {

        long maxTime = 0;
        long waitInMilliseconds = 30 * 1000; // 30 seconds
        String recommenderStatus = "";

        try {
            CreateRecommenderRequest createRecommenderRequest =
CreateRecommenderRequest.builder()
                    .datasetGroupArn(datasetGroupArn)
                    .name(name)
                    .recipeArn(recipeArn)
                    .build();

            CreateRecommenderResponse recommenderResponse = personalizeClient
                    .createRecommender(createRecommenderRequest);
            String recommenderArn = recommenderResponse.recommenderArn();
            System.out.println("The recommender ARN is " + recommenderArn);

            DescribeRecommenderRequest describeRecommenderRequest =
DescribeRecommenderRequest.builder()
                    .recommenderArn(recommenderArn)
                    .build();

            maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;
```

```
            while (Instant.now().getEpochSecond() < maxTime) {

                recommenderStatus =
personalizeClient.describeRecommender(describeRecommenderRequest).recommender()
                        .status();
                System.out.println("Recommender status: " + recommenderStatus);

                if (recommenderStatus.equals("ACTIVE") ||
recommenderStatus.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return recommenderArn;

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateRecommendera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateRecommenderCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the recommender's parameters.
export const createRecommenderParam = {
  name: 'NAME', /* required */
  recipeArn: 'RECIPE_ARN', /* required */
  datasetGroupArn: 'DATASET_GROUP_ARN'  /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateRecommenderCommand(createRecommenderParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateRecommendera Referência AWS SDK for JavaScript da API.

Crie um esquema com o Amazon Personalize usando um SDK da AWS

Os exemplos de códigos a seguir mostram como criar um esquema do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createSchema(PersonalizeClient personalizeClient, String
schemaName, String filePath) {

       String schema = null;
       try {
           schema = new String(Files.readAllBytes(Paths.get(filePath)));
       } catch (IOException e) {
           System.out.println(e.getMessage());
       }

       try {
           CreateSchemaRequest createSchemaRequest =
CreateSchemaRequest.builder()
                   .name(schemaName)
                   .schema(schema)
                   .build();

           String schemaArn =
personalizeClient.createSchema(createSchemaRequest).schemaArn();

           System.out.println("Schema arn: " + schemaArn);

           return schemaArn;

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSchemaCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

import fs from 'fs';

let schemaFilePath = "SCHEMA_PATH";
let mySchema = "";

try {
  mySchema = fs.readFileSync(schemaFilePath).toString();
} catch (err) {
  mySchema = 'TEST' // For unit tests.
}
// Set the schema parameters.
export const createSchemaParam = {
  name: 'NAME', /* required */
  schema: mySchema /* required */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSchemaCommand(createSchemaParam));
```

```
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for JavaScript da API.

Crie uma solução com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma solução do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalizeSolution(PersonalizeClient
personalizeClient,
           String datasetGroupArn,
           String solutionName,
           String recipeArn) {

       try {
           CreateSolutionRequest solutionRequest =
CreateSolutionRequest.builder()
                   .name(solutionName)
                   .datasetGroupArn(datasetGroupArn)
                   .recipeArn(recipeArn)
                   .build();
```

```
            CreateSolutionResponse solutionResponse =
 personalizeClient.createSolution(solutionRequest);
            return solutionResponse.solutionArn();

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateSolutiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSolutionCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the solution parameters.
export const createSolutionParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  recipeArn: 'RECIPE_ARN', /* required */
  name: 'NAME' /* required */
}

export const run = async () => {
  try {
```

```
    const response = await personalizeClient.send(new
 CreateSolutionCommand(createSolutionParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSolutiona Referência AWS SDK for JavaScript da API.

Crie uma versão de solução com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma solução do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createPersonalizeSolutionVersion(PersonalizeClient
 personalizeClient, String solutionArn) {
        long maxTime = 0;
        long waitInMilliseconds = 30 * 1000; // 30 seconds
        String solutionStatus = "";
        String solutionVersionStatus = "";
        String solutionVersionArn = "";

        try {
            DescribeSolutionRequest describeSolutionRequest =
 DescribeSolutionRequest.builder()
                    .solutionArn(solutionArn)
                    .build();
```

```
            maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            // Wait until solution is active.
            while (Instant.now().getEpochSecond() < maxTime) {

                solutionStatus =
personalizeClient.describeSolution(describeSolutionRequest).solution().status();
                System.out.println("Solution status: " + solutionStatus);

                if (solutionStatus.equals("ACTIVE") ||
solutionStatus.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }

            if (solutionStatus.equals("ACTIVE")) {

                CreateSolutionVersionRequest createSolutionVersionRequest =
CreateSolutionVersionRequest.builder()
                        .solutionArn(solutionArn)
                        .build();

                CreateSolutionVersionResponse createSolutionVersionResponse =
personalizeClient
                        .createSolutionVersion(createSolutionVersionRequest);
                solutionVersionArn =
createSolutionVersionResponse.solutionVersionArn();

                System.out.println("Solution version ARN: " +
solutionVersionArn);

                DescribeSolutionVersionRequest describeSolutionVersionRequest =
DescribeSolutionVersionRequest.builder()
                        .solutionVersionArn(solutionVersionArn)
                        .build();

                while (Instant.now().getEpochSecond() < maxTime) {
```

```
                    solutionVersionStatus =
personalizeClient.describeSolutionVersion(describeSolutionVersionRequest)
                            .solutionVersion().status();
                    System.out.println("Solution version status: " +
solutionVersionStatus);

                    if (solutionVersionStatus.equals("ACTIVE") ||
solutionVersionStatus.equals("CREATE FAILED")) {
                        break;
                    }
                    try {
                        Thread.sleep(waitInMilliseconds);
                    } catch (InterruptedException e) {
                        System.out.println(e.getMessage());
                    }
                }
                return solutionVersionArn;
            }
        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateSolutionVersiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSolutionVersionCommand } from
```

```
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the solution version parameters.
export const solutionVersionParam = {
  solutionArn: 'SOLUTION_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSolutionVersionCommand(solutionVersionParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSolutionVersiona Referência AWS SDK for JavaScript da API.

Crie um rastreador de eventos com o Amazon Personalize usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um rastreador de eventos do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createEventTracker(PersonalizeClient personalizeClient,
String eventTrackerName,
           String datasetGroupArn) {

       String eventTrackerId = "";
       String eventTrackerArn;
       long maxTime = 3 * 60 * 60; // 3 hours
       long waitInMilliseconds = 20 * 1000; // 20 seconds
       String status;

       try {

           CreateEventTrackerRequest createEventTrackerRequest =
CreateEventTrackerRequest.builder()
                   .name(eventTrackerName)
                   .datasetGroupArn(datasetGroupArn)
                   .build();

           CreateEventTrackerResponse createEventTrackerResponse =
personalizeClient
                   .createEventTracker(createEventTrackerRequest);

           eventTrackerArn = createEventTrackerResponse.eventTrackerArn();
           eventTrackerId = createEventTrackerResponse.trackingId();
           System.out.println("Event tracker ARN: " + eventTrackerArn);
           System.out.println("Event tracker ID: " + eventTrackerId);

           maxTime = Instant.now().getEpochSecond() + maxTime;

           DescribeEventTrackerRequest describeRequest =
DescribeEventTrackerRequest.builder()
                   .eventTrackerArn(eventTrackerArn)
                   .build();

           while (Instant.now().getEpochSecond() < maxTime) {

               status =
personalizeClient.describeEventTracker(describeRequest).eventTracker().status();
               System.out.println("EventTracker status: " + status);

               if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                   break;
               }
```

```
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return eventTrackerId;
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return eventTrackerId;
    }
```

- Para obter detalhes da API, consulte CreateEventTrackera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateEventTrackerCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the event tracker's parameters.
export const createEventTrackerParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  name: 'NAME', /* required */
}
```

```
export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateEventTrackerCommand(createEventTrackerParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateEventTrackera Referência AWS SDK for JavaScript da API.

Exclua uma campanha no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma campanha no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteSpecificCampaign(PersonalizeClient
 personalizeClient, String campaignArn) {

       try {
           DeleteCampaignRequest campaignRequest =
 DeleteCampaignRequest.builder()
                   .campaignArn(campaignArn)
                   .build();

           personalizeClient.deleteCampaign(campaignRequest);
```

```
        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteCampaigna Referência AWS SDK for Java 2.x da API.

Exclua uma solução no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma solução no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteGivenSolution(PersonalizeClient personalizeClient,
String solutionArn) {

        try {
            DeleteSolutionRequest solutionRequest =
DeleteSolutionRequest.builder()
                    .solutionArn(solutionArn)
                    .build();

            personalizeClient.deleteSolution(solutionRequest);
            System.out.println("Done");

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
```

- Para obter detalhes da API, consulte DeleteSolutiona Referência AWS SDK for Java 2.x da API.

Exclua um rastreador de eventos com o Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um rastreador de eventos no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteEventTracker(PersonalizeClient personalizeClient,
String eventTrackerArn) {
       try {
           DeleteEventTrackerRequest deleteEventTrackerRequest =
DeleteEventTrackerRequest.builder()
                   .eventTrackerArn(eventTrackerArn)
                   .build();

           int status =
personalizeClient.deleteEventTracker(deleteEventTrackerRequest).sdkHttpResponse().status

           System.out.println("Status code:" + status);

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteEventTrackera Referência AWS SDK for Java 2.x da API.

Descreva uma campanha no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como descrever uma campanha no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeSpecificCampaign(PersonalizeClient
personalizeClient, String campaignArn) {

       try {
           DescribeCampaignRequest campaignRequest =
DescribeCampaignRequest.builder()
                   .campaignArn(campaignArn)
                   .build();

           DescribeCampaignResponse campaignResponse =
personalizeClient.describeCampaign(campaignRequest);
           Campaign myCampaign = campaignResponse.campaign();
           System.out.println("The Campaign name is " + myCampaign.name());
           System.out.println("The Campaign status is " + myCampaign.status());

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeCampaigna Referência AWS SDK for Java 2.x da API.

Descreva uma fórmula no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como descrever uma fórmula no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeSpecificRecipe(PersonalizeClient
personalizeClient, String recipeArn) {

       try {
           DescribeRecipeRequest recipeRequest = DescribeRecipeRequest.builder()
                   .recipeArn(recipeArn)
                   .build();

           DescribeRecipeResponse recipeResponse =
personalizeClient.describeRecipe(recipeRequest);
           System.out.println("The recipe name is " +
recipeResponse.recipe().name());

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeRecipea Referência AWS SDK for Java 2.x da API.

Descreva uma solução no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como descrever uma solução no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeSpecificSolution(PersonalizeClient
personalizeClient, String solutionArn) {

       try {
           DescribeSolutionRequest solutionRequest =
DescribeSolutionRequest.builder()
                   .solutionArn(solutionArn)
                   .build();

           DescribeSolutionResponse response =
personalizeClient.describeSolution(solutionRequest);
           System.out.println("The Solution name is " +
response.solution().name());

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeSolutiona Referência AWS SDK for Java 2.x da API.

Liste campanhas no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como listar campanhas no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listAllCampaigns(PersonalizeClient personalizeClient,
String solutionArn) {

       try {
           ListCampaignsRequest campaignsRequest =
ListCampaignsRequest.builder()
                   .maxResults(10)
                   .solutionArn(solutionArn)
                   .build();

           ListCampaignsResponse response =
personalizeClient.listCampaigns(campaignsRequest);
           List<CampaignSummary> campaigns = response.campaigns();
           for (CampaignSummary campaign : campaigns) {
               System.out.println("Campaign name is : " + campaign.name());
               System.out.println("Campaign ARN is : " +
campaign.campaignArn());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListCampaignsa Referência AWS SDK for Java 2.x da API.

Liste grupos de conjuntos de dados no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como listar grupos de conjuntos de dados no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listDSGroups(PersonalizeClient personalizeClient) {

       try {
           ListDatasetGroupsRequest groupsRequest =
ListDatasetGroupsRequest.builder()
                   .maxResults(15)
                   .build();

           ListDatasetGroupsResponse groupsResponse =
personalizeClient.listDatasetGroups(groupsRequest);
           List<DatasetGroupSummary> groups = groupsResponse.datasetGroups();
           for (DatasetGroupSummary group : groups) {
               System.out.println("The DataSet name is : " + group.name());
               System.out.println("The DataSet ARN is : " +
group.datasetGroupArn());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListDatasetGroupsa Referência AWS SDK for Java 2.x da API.

Liste fórmulas no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como listar fórmulas no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listAllRecipes(PersonalizeClient personalizeClient) {

        try {
            ListRecipesRequest recipesRequest = ListRecipesRequest.builder()
                    .maxResults(15)
                    .build();

            ListRecipesResponse response =
personalizeClient.listRecipes(recipesRequest);
            List<RecipeSummary> recipes = response.recipes();
            for (RecipeSummary recipe : recipes) {
                System.out.println("The recipe ARN is: " + recipe.recipeArn());
                System.out.println("The recipe name is: " + recipe.name());
            }

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListRecipesa Referência AWS SDK for Java 2.x da API.

Liste soluções no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como listar soluções no Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listAllSolutions(PersonalizeClient personalizeClient,
String datasetGroupArn) {

       try {
           ListSolutionsRequest solutionsRequest =
ListSolutionsRequest.builder()
                   .maxResults(10)
                   .datasetGroupArn(datasetGroupArn)
                   .build();

           ListSolutionsResponse response =
personalizeClient.listSolutions(solutionsRequest);
           List<SolutionSummary> solutions = response.solutions();
           for (SolutionSummary solution : solutions) {
               System.out.println("The solution ARN is: " +
solution.solutionArn());
               System.out.println("The solution name is: " + solution.name());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListSolutionsa Referência AWS SDK for Java 2.x da API.

Atualize uma campanha no Amazon Personalize usando um SDK da AWS

O exemplo de código a seguir mostra como atualizar uma campanha do Amazon Personalize.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String updateCampaign(PersonalizeClient personalizeClient,
            String campaignArn,
            String solutionVersionArn,
            Integer minProvisionedTPS) {

        try {
            // build the updateCampaignRequest
            UpdateCampaignRequest updateCampaignRequest =
UpdateCampaignRequest.builder()
                    .campaignArn(campaignArn)
                    .solutionVersionArn(solutionVersionArn)
                    .minProvisionedTPS(minProvisionedTPS)
                    .build();

            // update the campaign
            personalizeClient.updateCampaign(updateCampaignRequest);

            DescribeCampaignRequest campaignRequest =
DescribeCampaignRequest.builder()
                    .campaignArn(campaignArn)
                    .build();

            DescribeCampaignResponse campaignResponse =
personalizeClient.describeCampaign(campaignRequest);
            Campaign updatedCampaign = campaignResponse.campaign();

            System.out.println("The Campaign status is " +
updatedCampaign.status());
```

```
            return updatedCampaign.status();

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte UpdateCampaigna Referência AWS SDK for Java 2.x da API.

Exemplos de códigos para o Amazon Personalize Events usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize Events com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon Personalize Events – Mais informações sobre o Amazon Personalize Events.
- Referência da API do Amazon Personalize Events – Detalhes sobre todas as ações disponíveis do Amazon Personalize Events.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para Amazon Personalize Events usando SDKs da AWS
  - Importe itens de forma incremental para o Amazon Personalize Events usando um SDK da AWS

- Importe dados de eventos de interação em tempo real para o Amazon Personalize Events usando um SDK AWS
- Importe usuários de forma incremental para eventos do Amazon Personalize Events usando um SDK da AWS

Ações para Amazon Personalize Events usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize Events com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Importe itens de forma incremental para o Amazon Personalize Events usando um SDK da AWS
- Importe dados de eventos de interação em tempo real para o Amazon Personalize Events usando um SDK AWS
- Importe usuários de forma incremental para eventos do Amazon Personalize Events usando um SDK da AWS

Importe itens de forma incremental para o Amazon Personalize Events usando um SDK da AWS

O exemplo de código a seguir mostra como importar itens de forma incremental para um conjunto de dados do Amazon Personalize Events.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { PutItemsCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
```

```
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region:
 "REGION"});

// Set the put items parameters. For string properties and values, use the \
 character to escape quotes.
var putItemsParam = {
  datasetArn: "DATASET_ARN" /* required */,
  items: [
    /* required */
    {
      itemId: "ITEM_ID" /*  required */,
      properties:
        '{"PROPERTY1_NAME": "PROPERTY1_VALUE", "PROPERTY2_NAME":
 "PROPERTY2_VALUE", "PROPERTY3_NAME": "PROPERTY3_VALUE"}' /* optional */,
    },
  ],
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutItemsCommand(putItemsParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutItemsa Referência AWS SDK for JavaScript da API.

Importe dados de eventos de interação em tempo real para o Amazon Personalize Events usando um SDK AWS

Os exemplos de código a seguir mostram como importar dados de eventos de interação em tempo real para o Amazon Personalize Events.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static int putItems(PersonalizeEventsClient
personalizeEventsClient,
                        String datasetArn,
                        String item1Id,
                        String item1PropertyName,
                        String item1PropertyValue,
                        String item2Id,
                        String item2PropertyName,
                        String item2PropertyValue) {

                int responseCode = 0;
                ArrayList<Item> items = new ArrayList<>();

                try {
                        Item item1 = Item.builder()
                                        .itemId(item1Id)
                                        .properties(String.format("{\"%1$s\":
\"%2$s\"}",
                                                        item1PropertyName,
item1PropertyValue))
                                        .build();

                        items.add(item1);

                        Item item2 = Item.builder()
                                        .itemId(item2Id)
                                        .properties(String.format("{\"%1$s\":
\"%2$s\"}",
                                                        item2PropertyName,
item2PropertyValue))
                                        .build();
```

```
                        items.add(item2);

                        PutItemsRequest putItemsRequest =
 PutItemsRequest.builder()
                                        .datasetArn(datasetArn)
                                        .items(items)
                                        .build();

                        responseCode =
 personalizeEventsClient.putItems(putItemsRequest).sdkHttpResponse().statusCode();
                        System.out.println("Response code: " + responseCode);
                        return responseCode;

                } catch (PersonalizeEventsException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
                }
                return responseCode;
        }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { PutEventsCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region:
 "REGION"});

// Convert your UNIX timestamp to a Date.
const sentAtDate = new Date(1613443801 * 1000); // 1613443801 is a testing value.
 Replace it with your sentAt timestamp in UNIX format.
```

```
// Set put events parameters.
var putEventsParam = {
  eventList: [
    /* required */
    {
      eventType: "EVENT_TYPE" /* required */,
      sentAt: sentAtDate /* required, must be a Date with js */,
      eventId: "EVENT_ID" /* optional */,
      itemId: "ITEM_ID" /* optional */,
    },
  ],
  sessionId: "SESSION_ID" /* required */,
  trackingId: "TRACKING_ID" /* required */,
  userId: "USER_ID" /* required */,
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutEventsCommand(putEventsParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

Importe usuários de forma incremental para eventos do Amazon Personalize Events usando um SDK da AWS

Os exemplos de código a seguir mostram como importar um usuário de forma incremental para eventos do Amazon Personalize Events.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static int putUsers(PersonalizeEventsClient
personalizeEventsClient,
                        String datasetArn,
                        String user1Id,
                        String user1PropertyName,
                        String user1PropertyValue,
                        String user2Id,
                        String user2PropertyName,
                        String user2PropertyValue) {

                int responseCode = 0;
                ArrayList<User> users = new ArrayList<>();

                try {
                        User user1 = User.builder()
                                        .userId(user1Id)
                                        .properties(String.format("{\"%1$s\":
\"%2$s\"}",
                                                        user1PropertyName,
user1PropertyValue))
                                        .build();

                        users.add(user1);

                        User user2 = User.builder()
                                        .userId(user2Id)
                                        .properties(String.format("{\"%1$s\":
\"%2$s\"}",
                                                        user2PropertyName,
user2PropertyValue))
                                        .build();
```

```
                        users.add(user2);

                        PutUsersRequest putUsersRequest =
 PutUsersRequest.builder()
                                        .datasetArn(datasetArn)
                                        .users(users)
                                        .build();

                        responseCode =
 personalizeEventsClient.putUsers(putUsersRequest).sdkHttpResponse().statusCode();
                        System.out.println("Response code: " + responseCode);
                        return responseCode;

                } catch (PersonalizeEventsException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
                }
                return responseCode;
        }
```

- Para obter detalhes da API, consulte PutUsersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { PutUsersCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region:
 "REGION"});

// Set the put users parameters. For string properties and values, use the \
 character to escape quotes.
var putUsersParam = {
```

```
  datasetArn: "DATASET_ARN",
  users: [
    {
      userId: "USER_ID",
      properties: '{"PROPERTY1_NAME": "PROPERTY1_VALUE"}',
    },
  ],
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutUsersCommand(putUsersParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutUsersa Referência AWS SDK for JavaScript da API.

Exemplos de código para o Amazon Personalize Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize Runtime com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon Personalize Runtime – Mais informações sobre o Amazon Personalize Runtime.

- Referência da API do Amazon Personalize – Detalhes sobre todas as ações disponíveis do Amazon Personalize Runtime.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon Personalize Runtime usando SDKs da AWS
  - Obtenha recomendações classificadas de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS
  - Obtenha recomendações de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS

Ações para o Amazon Personalize Runtime usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Personalize Runtime com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Obtenha recomendações classificadas de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS
- Obtenha recomendações de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS

Obtenha recomendações classificadas de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS

Os exemplos de código a seguir mostram como obter recomendações classificadas do Amazon Personalize Runtime.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static List<PredictedItem> getRankedRecs(PersonalizeRuntimeClient
personalizeRuntimeClient,
           String campaignArn,
           String userId,
           ArrayList<String> items) {

       try {
           GetPersonalizedRankingRequest rankingRecommendationsRequest =
GetPersonalizedRankingRequest.builder()
                   .campaignArn(campaignArn)
                   .userId(userId)
                   .inputList(items)
                   .build();

           GetPersonalizedRankingResponse recommendationsResponse =
personalizeRuntimeClient
                   .getPersonalizedRanking(rankingRecommendationsRequest);
           List<PredictedItem> rankedItems =
recommendationsResponse.personalizedRanking();
           int rank = 1;
           for (PredictedItem item : rankedItems) {
               System.out.println("Item ranked at position " + rank + "
details");
               System.out.println("Item Id is : " + item.itemId());
               System.out.println("Item score is : " + item.score());

System.out.println("--------------------------------------------");
               rank++;
           }
           return rankedItems;
       } catch (PersonalizeRuntimeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        return null;
    }
```

- Para obter detalhes da API, consulte GetPersonalizedRankinga Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { GetPersonalizedRankingCommand } from
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the ranking request parameters.
export const getPersonalizedRankingParam = {
  campaignArn: "CAMPAIGN_ARN", /* required */
  userId: 'USER_ID',      /* required */
  inputList: ["ITEM_ID_1", "ITEM_ID_2", "ITEM_ID_3", "ITEM_ID_4"]
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetPersonalizedRankingCommand(getPersonalizedRankingParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
```

```
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte GetPersonalizedRankinga Referência AWS SDK for JavaScript da API.

Obtenha recomendações de uma campanha criada em um grupo de conjuntos de dados personalizados com o Amazon Personalize Runtime usando um SDK da AWS

Os exemplos de código a seguir mostram como obter recomendações de runtime do Amazon Personalize Runtime.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter uma lista de itens recomendados.

```
   public static void getRecs(PersonalizeRuntimeClient personalizeRuntimeClient,
String campaignArn, String userId) {

       try {
           GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                   .campaignArn(campaignArn)
                   .numResults(20)
                   .userId(userId)
                   .build();

           GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
```

```
                    .getRecommendations(recommendationsRequest);
            List<PredictedItem> items = recommendationsResponse.itemList();
            for (PredictedItem item : items) {
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
            }

        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Obter uma lista de itens recomendados de um recomendador criado em um grupo de conjuntos de dados de domínio.

```
    public static void getRecs(PersonalizeRuntimeClient personalizeRuntimeClient,
String recommenderArn,
            String userId) {

        try {
            GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                    .recommenderArn(recommenderArn)
                    .numResults(20)
                    .userId(userId)
                    .build();

            GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
                    .getRecommendations(recommendationsRequest);
            List<PredictedItem> items = recommendationsResponse.itemList();

            for (PredictedItem item : items) {
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
            }
        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Usar um filtro ao solicitar recomendações.

```
   public static void getFilteredRecs(PersonalizeRuntimeClient
personalizeRuntimeClient,
           String campaignArn,
           String userId,
           String filterArn,
           String parameter1Name,
           String parameter1Value1,
           String parameter1Value2,
           String parameter2Name,
           String parameter2Value) {

       try {

           Map<String, String> filterValues = new HashMap<>();

           filterValues.put(parameter1Name, String.format("\"%1$s\",\"%2$s\"",
                   parameter1Value1, parameter1Value2));
           filterValues.put(parameter2Name, String.format("\"%1$s\"",
                   parameter2Value));

           GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                   .campaignArn(campaignArn)
                   .numResults(20)
                   .userId(userId)
                   .filterArn(filterArn)
                   .filterValues(filterValues)
                   .build();

           GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
                   .getRecommendations(recommendationsRequest);
           List<PredictedItem> items = recommendationsResponse.itemList();

           for (PredictedItem item : items) {
               System.out.println("Item Id is : " + item.itemId());
               System.out.println("Item score is : " + item.score());
           }
       } catch (PersonalizeRuntimeException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetRecommendationsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
  "@aws-sdk/client-personalize-runtime";

import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the recommendation request parameters.
export const getRecommendationsParam = {
  campaignArn: 'CAMPAIGN_ARN', /* required */
  userId: 'USER_ID',      /* required */
  numResults: 15    /* optional */
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
```

```
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Obter recomendações com um filtro (grupo de conjunto de dados personalizados).

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the recommendation request parameters.
export const getRecommendationsParam = {
  recommenderArn: 'RECOMMENDER_ARN', /* required */
  userId: 'USER_ID',       /* required */
  numResults: 15    /* optional */
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Obtenha as recomendações filtradas de um recomendador criado em um grupo de conjuntos de dados de domínio.

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
```

```
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here:
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set recommendation request parameters.
export const getRecommendationsParam = {
  campaignArn: 'CAMPAIGN_ARN', /* required */
  userId: 'USER_ID',      /* required */
  numResults: 15,    /* optional */
  filterArn: 'FILTER_ARN',   /* required to filter recommendations */
  filterValues: {
    "PROPERTY": "\"VALUE\""  /* Only required if your filter has a placeholder
 parameter */
  }
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte GetRecommendationsa Referência AWS SDK for JavaScript da API.

Exemplos de código para o Amazon Pinpoint usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Pinpoint com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon Pinpoint – Mais informações sobre o Amazon Pinpoint.
- Referência da API do Amazon Pinpoint – Detalhes sobre todas as ações disponíveis do Amazon Pinpoint.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Pinpoint usando AWS SDKs
  - Criar uma campanha do Amazon Pinpoint
  - Criar um segmento do Amazon Pinpoint
  - Crie uma aplicação do Amazon Pinpoint
  - Excluir um aplicativo do Amazon Pinpoint
  - Excluir um endpoint do Amazon Pinpoint
  - Exportar um endpoint do Amazon Pinpoint
  - Exibir informações sobre um endpoint existente do Amazon Pinpoint
  - Importar um segmento do Amazon Pinpoint
  - Liste os endpoints do Amazon Pinpoint que estão associados a um ID de usuário específico
  - Listar segmentos do Amazon Pinpoint em um aplicativo
  - Envie e-mails e mensagens de texto com o Amazon Pinpoint usando um AWS SDK
  - Envie mensagens de texto e e-mail modeladas com o Amazon Pinpoint usando um SDK AWS
  - Atualizar um endpoint do Amazon Pinpoint
  - Atualizar um canal do Amazon Pinpoint

Ações do Amazon Pinpoint usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Pinpoint com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Criar uma campanha do Amazon Pinpoint
- Criar um segmento do Amazon Pinpoint
- Crie uma aplicação do Amazon Pinpoint
- Excluir um aplicativo do Amazon Pinpoint
- Excluir um endpoint do Amazon Pinpoint
- Exportar um endpoint do Amazon Pinpoint
- Exibir informações sobre um endpoint existente do Amazon Pinpoint
- Importar um segmento do Amazon Pinpoint
- Liste os endpoints do Amazon Pinpoint que estão associados a um ID de usuário específico
- Listar segmentos do Amazon Pinpoint em um aplicativo
- Envie e-mails e mensagens de texto com o Amazon Pinpoint usando um AWS SDK
- Envie mensagens de texto e e-mail modeladas com o Amazon Pinpoint usando um SDK AWS
- Atualizar um endpoint do Amazon Pinpoint
- Atualizar um canal do Amazon Pinpoint

Criar uma campanha do Amazon Pinpoint

Os exemplos de código a seguir mostram como criar uma campanha.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma campanha.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CampaignResponse;
import software.amazon.awssdk.services.pinpoint.model.Message;
import software.amazon.awssdk.services.pinpoint.model.Schedule;
```

```
import software.amazon.awssdk.services.pinpoint.model.Action;
import software.amazon.awssdk.services.pinpoint.model.MessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.WriteCampaignRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateCampaignResponse;
import software.amazon.awssdk.services.pinpoint.model.CreateCampaignRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateCampaign {
    public static void main(String[] args) {

        final String usage = """

                Usage:   <appId> <segmentId>

                Where:
                  appId - The ID of the application to create the campaign in.
                  segmentId - The ID of the segment to create the campaign from.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String segmentId = args[1];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createPinCampaign(pinpoint, appId, segmentId);
        pinpoint.close();
    }
```

```
   public static void createPinCampaign(PinpointClient pinpoint, String appId,
String segmentId) {
       CampaignResponse result = createCampaign(pinpoint, appId, segmentId);
       System.out.println("Campaign " + result.name() + " created.");
       System.out.println(result.description());
   }

   public static CampaignResponse createCampaign(PinpointClient client, String
appID, String segmentID) {

       try {
           Schedule schedule = Schedule.builder()
                   .startTime("IMMEDIATE")
                   .build();

           Message defaultMessage = Message.builder()
                   .action(Action.OPEN_APP)
                   .body("My message body.")
                   .title("My message title.")
                   .build();

           MessageConfiguration messageConfiguration =
MessageConfiguration.builder()
                   .defaultMessage(defaultMessage)
                   .build();

           WriteCampaignRequest request = WriteCampaignRequest.builder()
                   .description("My description")
                   .schedule(schedule)
                   .name("MyCampaign")
                   .segmentId(segmentID)
                   .messageConfiguration(messageConfiguration)
                   .build();

           CreateCampaignResponse result =
client.createCampaign(CreateCampaignRequest.builder()
                   .applicationId(appID)
                   .writeCampaignRequest(request).build());

           System.out.println("Campaign ID: " + result.campaignResponse().id());
           return result.campaignResponse();

       } catch (PinpointException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }

        return null;
    }
}
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createPinCampaign(appId: String, segmentIdVal: String) {

    val scheduleOb = Schedule {
        startTime = "IMMEDIATE"
    }

    val defaultMessageOb = Message {
        action = Action.OpenApp
        body = "My message body"
        title = "My message title"
    }

    val messageConfigurationOb = MessageConfiguration {
        defaultMessage = defaultMessageOb
    }

    val writeCampaign = WriteCampaignRequest {
        description = "My description"
        schedule = scheduleOb
        name = "MyCampaign"
```

```
        segmentId = segmentIdVal
        messageConfiguration = messageConfigurationOb
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result: CreateCampaignResponse = pinpoint.createCampaign(
            CreateCampaignRequest {
                applicationId = appId
                writeCampaignRequest = writeCampaign
            }
        )
        println("Campaign ID is ${result.campaignResponse?.id}")
    }
}
```

- Para obter detalhes da API, consulte a CreateCampaignreferência da API AWSSDK for Kotlin.

Criar um segmento do Amazon Pinpoint

Os exemplos de código a seguir mostram como criar um segmento.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.AttributeDimension;
import software.amazon.awssdk.services.pinpoint.model.SegmentResponse;
import software.amazon.awssdk.services.pinpoint.model.AttributeType;
import software.amazon.awssdk.services.pinpoint.model.RecencyDimension;
import software.amazon.awssdk.services.pinpoint.model.SegmentBehaviors;
import software.amazon.awssdk.services.pinpoint.model.SegmentDemographics;
```

```
import software.amazon.awssdk.services.pinpoint.model.SegmentLocation;
import software.amazon.awssdk.services.pinpoint.model.SegmentDimensions;
import software.amazon.awssdk.services.pinpoint.model.WriteSegmentRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateSegmentRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateSegmentResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateSegment {
        public static void main(String[] args) {
                final String usage = """

                                Usage:   <appId>

                                Where:
                                  appId - The application ID to create a segment
 for.

                                """;

                if (args.length != 1) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String appId = args[0];
                PinpointClient pinpoint = PinpointClient.builder()
                                .region(Region.US_EAST_1)
                                .build();

                SegmentResponse result = createSegment(pinpoint, appId);
                System.out.println("Segment " + result.name() + " created.");
                System.out.println(result.segmentType());
                pinpoint.close();
```

```
        }

        public static SegmentResponse createSegment(PinpointClient client, String
appId) {
                try {
                        Map<String, AttributeDimension> segmentAttributes = new
HashMap<>();
                        segmentAttributes.put("Team",
AttributeDimension.builder()
                                        .attributeType(AttributeType.INCLUSIVE)
                                        .values("Lakers")
                                        .build());

                        RecencyDimension recencyDimension =
RecencyDimension.builder()
                                        .duration("DAY_30")
                                        .recencyType("ACTIVE")
                                        .build();

                        SegmentBehaviors segmentBehaviors =
SegmentBehaviors.builder()
                                        .recency(recencyDimension)
                                        .build();

                        SegmentDemographics segmentDemographics =
SegmentDemographics
                                        .builder()
                                        .build();

                        SegmentLocation segmentLocation = SegmentLocation
                                        .builder()
                                        .build();

                        SegmentDimensions dimensions = SegmentDimensions
                                        .builder()
                                        .attributes(segmentAttributes)
                                        .behavior(segmentBehaviors)
                                        .demographic(segmentDemographics)
                                        .location(segmentLocation)
                                        .build();

                        WriteSegmentRequest writeSegmentRequest =
WriteSegmentRequest.builder()
                                        .name("MySegment")
```

```
                                        .dimensions(dimensions)
                                        .build();

                        CreateSegmentRequest createSegmentRequest =
 CreateSegmentRequest.builder()
                                        .applicationId(appId)
                                        .writeSegmentRequest(writeSegmentRequest)
                                        .build();

                        CreateSegmentResponse createSegmentResult =
 client.createSegment(createSegmentRequest);
                        System.out.println("Segment ID: " +
 createSegmentResult.segmentResponse().id());
                        System.out.println("Done");
                        return createSegmentResult.segmentResponse();

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
                return null;
        }
}
```

- Para obter detalhes da API, consulte CreateSegmenta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createPinpointSegment(applicationIdVal: String?): String? {

    val segmentAttributes = mutableMapOf<String, AttributeDimension>()
```

```
    val myList = mutableListOf<String>()
    myList.add("Lakers")

    val atts = AttributeDimension {
        attributeType = AttributeType.Inclusive
        values = myList
    }

    segmentAttributes["Team"] = atts
    val recencyDimension = RecencyDimension {
        duration = Duration.fromValue("DAY_30")
        recencyType = RecencyType.fromValue("ACTIVE")
    }

    val segmentBehaviors = SegmentBehaviors {
        recency = recencyDimension
    }

    val segmentLocation = SegmentLocation {}
    val dimensionsOb = SegmentDimensions {
        attributes = segmentAttributes
        behavior = segmentBehaviors
        demographic = SegmentDemographics {}
        location = segmentLocation
    }

    val writeSegmentRequestOb = WriteSegmentRequest {
        name = "MySegment101"
        dimensions = dimensionsOb
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val createSegmentResult: CreateSegmentResponse = pinpoint.createSegment(
            CreateSegmentRequest {
                applicationId = applicationIdVal
                writeSegmentRequest = writeSegmentRequestOb
            }
        )
        println("Segment ID is ${createSegmentResult.segmentResponse?.id}")
        return createSegmentResult.segmentResponse?.id
    }
}
```

- Para obter detalhes da API, consulte a CreateSegmentreferência da API AWSSDK for Kotlin.

Crie uma aplicação do Amazon Pinpoint

Os exemplos de código a seguir mostram como criar um aplicativo.

CLI

AWS CLI

Exemplo 1: como criar uma aplicação

O exemplo `create-app` a seguir cria uma aplicação (projeto).

```
aws pinpoint create-app \
    --create-application-request Name=ExampleCorp
```

Saída:

```
{
    "ApplicationResponse": {
        "Arn": "arn:aws:mobiletargeting:us-
west-2:AIDACKCEVSQ6C2EXAMPLE:apps/810c7aab86d42fb2b56c8c966example",
        "Id": "810c7aab86d42fb2b56c8c966example",
        "Name": "ExampleCorp",
        "tags": {}
    }
}
```

Exemplo 2: Como criar uma aplicação marcada

O exemplo `create-app` a seguir cria uma aplicação (projeto) e associa uma tag (chave e valor) a ela.

```
aws pinpoint create-app \
    --create-application-request Name=ExampleCorp,tags={"Stack"="Test"}
```

Saída:

```
{
```

```
    "ApplicationResponse": {
        "Arn": "arn:aws:mobiletargeting:us-
west-2:AIDACKCEVSQ6C2EXAMPLE:apps/810c7aab86d42fb2b56c8c966example",
        "Id": "810c7aab86d42fb2b56c8c966example",
        "Name": "ExampleCorp",
        "tags": {
            "Stack": "Test"
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAppem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CreateAppRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateAppResponse;
import software.amazon.awssdk.services.pinpoint.model.CreateApplicationRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateApp {
    public static void main(String[] args) {
        final String usage = """
```

```
                 Usage:  <appName>

                 Where:
                  appName - The name of the application to create.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
        String appName = args[0];
        System.out.println("Creating an application with name: " + appName);

        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String appID = createApplication(pinpoint, appName);
        System.out.println("App ID is: " + appID);
        pinpoint.close();
    }

    public static String createApplication(PinpointClient pinpoint, String
appName) {
        try {
            CreateApplicationRequest appRequest =
CreateApplicationRequest.builder()
                    .name(appName)
                    .build();

            CreateAppRequest request = CreateAppRequest.builder()
                    .createApplicationRequest(appRequest)
                    .build();

            CreateAppResponse result = pinpoint.createApp(request);
            return result.applicationResponse().id();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
```

```
    }
}
```

- Para obter detalhes da API, consulte CreateApp a Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createApplication(applicationName: String?): String? {

    val createApplicationRequestOb = CreateApplicationRequest {
        name = applicationName
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.createApp(
            CreateAppRequest {
                createApplicationRequest = createApplicationRequestOb
            }
        )
        return result.applicationResponse?.id
    }
}
```

- Para obter detalhes da API, consulte a CreateAppreferência da API AWSSDK for Kotlin.

Excluir um aplicativo do Amazon Pinpoint

Os exemplos de código a seguir mostram como excluir um aplicativo.

CLI

AWS CLI

Como excluir uma aplicação

O exemplo `delete-app` a seguir exclui uma aplicação (projeto).

```
aws pinpoint delete-app \
    --application-id 810c7aab86d42fb2b56c8c966example
```

Saída:

```
{
    "ApplicationResponse": {
        "Arn": "arn:aws:mobiletargeting:us-
west-2:AIDACKCEVSQ6C2EXAMPLE:apps/810c7aab86d42fb2b56c8c966example",
        "Id": "810c7aab86d42fb2b56c8c966example",
        "Name": "ExampleCorp",
        "tags": {}
    }
}
```

- Para obter detalhes da API, consulte DeleteAppem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir uma aplicação.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DeleteAppRequest;
import software.amazon.awssdk.services.pinpoint.model.DeleteAppResponse;
```

```
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteApp {
    public static void main(String[] args) {
        final String usage = """

                Usage:  <appId>

                Where:
                 appId - The ID of the application to delete.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        System.out.println("Deleting an application with ID: " + appId);
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deletePinApp(pinpoint, appId);
        System.out.println("Done");
        pinpoint.close();
    }

    public static void deletePinApp(PinpointClient pinpoint, String appId) {
        try {
            DeleteAppRequest appRequest = DeleteAppRequest.builder()
                    .applicationId(appId)
                    .build();
```

```
            DeleteAppResponse result = pinpoint.deleteApp(appRequest);
            String appName = result.applicationResponse().name();
            System.out.println("Application " + appName + " has been deleted.");

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteApp a Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deletePinApp(appId: String?) {

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.deleteApp(
            DeleteAppRequest {
                applicationId = appId
            }
        )
        val appName = result.applicationResponse?.name
        println("Application $appName has been deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAppreferência da API AWSSDK for Kotlin.

Excluir um endpoint do Amazon Pinpoint

Os exemplos de código a seguir mostram como excluir um endpoint.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um endpoint

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DeleteEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.DeleteEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteEndpoint {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appName> <endpointId >

                Where:
                  appId - The id of the application to delete.
                  endpointId - The id of the endpoint to delete.
                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String endpointId = args[1];
        System.out.println("Deleting an endpoint with id: " + endpointId);
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deletePinEncpoint(pinpoint, appId, endpointId);
        pinpoint.close();
    }

    public static void deletePinEncpoint(PinpointClient pinpoint, String appId,
 String endpointId) {
        try {
            DeleteEndpointRequest appRequest = DeleteEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .build();

            DeleteEndpointResponse result = pinpoint.deleteEndpoint(appRequest);
            String id = result.endpointResponse().id();
            System.out.println("The deleted endpoint id  " + id);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeleteEndpointa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deletePinEncpoint(appIdVal: String?, endpointIdVal: String?) {

    val deleteEndpointRequest = DeleteEndpointRequest {
        applicationId = appIdVal
        endpointId = endpointIdVal
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.deleteEndpoint(deleteEndpointRequest)
        val id = result.endpointResponse?.id
        println("The deleted endpoint is  $id")
    }
}
```

- Para obter detalhes da API, consulte a DeleteEndpointreferência da API AWSSDK for Kotlin.

Exportar um endpoint do Amazon Pinpoint

Os exemplos a seguir mostram como exportar um endpoint.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exporte um endpoint.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.ExportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.CreateExportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateExportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.GetExportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.GetExportJobRequest;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Request;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Response;
import software.amazon.awssdk.services.s3.model.S3Object;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;
import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Date;
import java.util.List;
import java.util.concurrent.TimeUnit;
import java.util.stream.Collectors;

/**
 * To run this code example, you need to create an AWS Identity and Access
 * Management (IAM) role with the correct policy as described in this
 * documentation:
 * https://docs.aws.amazon.com/pinpoint/latest/developerguide/audience-data-
export.html
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class ExportEndpoints {
    public static void main(String[] args) {
        final String usage = """

                This program performs the following steps:

                1. Exports the endpoints to an Amazon S3 bucket.
                2. Downloads the exported endpoints files from Amazon S3.
                3. Parses the endpoints files to obtain the endpoint IDs and
 prints them.
                Usage: ExportEndpoints <applicationId> <s3BucketName>
 <iamExportRoleArn> <path>

                Where:
                  applicationId - The ID of the Amazon Pinpoint application that
 has the endpoint.
                  s3BucketName - The name of the Amazon S3 bucket to export the
 JSON file to.\s
                  iamExportRoleArn - The ARN of an IAM role that grants Amazon
 Pinpoint write permissions to the S3 bucket.  path - The path where the files
 downloaded from the Amazon S3 bucket are written (for example, C:/AWS/).
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String applicationId = args[0];
        String s3BucketName = args[1];
        String iamExportRoleArn = args[2];
        String path = args[3];
        System.out.println("Deleting an application with ID: " + applicationId);

        Region region = Region.US_EAST_1;
        PinpointClient pinpoint = PinpointClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();
```

```
        exportAllEndpoints(pinpoint, s3Client, applicationId, s3BucketName, path,
 iamExportRoleArn);
        pinpoint.close();
        s3Client.close();
    }

    public static void exportAllEndpoints(PinpointClient pinpoint,
            S3Client s3Client,
            String applicationId,
            String s3BucketName,
            String path,
            String iamExportRoleArn) {

        try {
            List<String> objectKeys = exportEndpointsToS3(pinpoint, s3Client,
 s3BucketName, iamExportRoleArn,
                    applicationId);
            List<String> endpointFileKeys = objectKeys.stream().filter(o ->
 o.endsWith(".gz"))
                    .collect(Collectors.toList());
            downloadFromS3(s3Client, path, s3BucketName, endpointFileKeys);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static List<String> exportEndpointsToS3(PinpointClient pinpoint,
 S3Client s3Client, String s3BucketName,
            String iamExportRoleArn, String applicationId) {

        SimpleDateFormat dateFormat = new SimpleDateFormat("yyyy-MM-dd-
HH_mm:ss.SSS_z");
        String endpointsKeyPrefix = "exports/" + applicationId + "_" +
 dateFormat.format(new Date());
        String s3UrlPrefix = "s3://" + s3BucketName + "/" + endpointsKeyPrefix +
 "/";
        List<String> objectKeys = new ArrayList<>();
        String key;

        try {
            // Defines the export job that Amazon Pinpoint runs.
            ExportJobRequest jobRequest = ExportJobRequest.builder()
```

```
                    .roleArn(iamExportRoleArn)
                    .s3UrlPrefix(s3UrlPrefix)
                    .build();

            CreateExportJobRequest exportJobRequest =
CreateExportJobRequest.builder()
                    .applicationId(applicationId)
                    .exportJobRequest(jobRequest)
                    .build();

            System.out.format("Exporting endpoints from Amazon Pinpoint
application %s to Amazon S3 " +
                    "bucket %s . . .\n", applicationId, s3BucketName);

            CreateExportJobResponse exportResult =
pinpoint.createExportJob(exportJobRequest);
            String jobId = exportResult.exportJobResponse().id();
            System.out.println(jobId);
            printExportJobStatus(pinpoint, applicationId, jobId);

            ListObjectsV2Request v2Request = ListObjectsV2Request.builder()
                    .bucket(s3BucketName)
                    .prefix(endpointsKeyPrefix)
                    .build();

            // Create a list of object keys.
            ListObjectsV2Response v2Response = s3Client.listObjectsV2(v2Request);
            List<S3Object> objects = v2Response.contents();
            for (S3Object object : objects) {
                key = object.key();
                objectKeys.add(key);
            }

            return objectKeys;

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static void printExportJobStatus(PinpointClient pinpointClient,
            String applicationId,
```

```
            String jobId) {

        GetExportJobResponse getExportJobResult;
        String status;

        try {
            // Checks the job status until the job completes or fails.
            GetExportJobRequest exportJobRequest = GetExportJobRequest.builder()
                    .jobId(jobId)
                    .applicationId(applicationId)
                    .build();

            do {
                getExportJobResult =
pinpointClient.getExportJob(exportJobRequest);
                status =
getExportJobResult.exportJobResponse().jobStatus().toString().toUpperCase();
                System.out.format("Export job %s . . .\n", status);
                TimeUnit.SECONDS.sleep(3);

            } while (!status.equals("COMPLETED") && !status.equals("FAILED"));

            if (status.equals("COMPLETED")) {
                System.out.println("Finished exporting endpoints.");
            } else {
                System.err.println("Failed to export endpoints.");
                System.exit(1);
            }

        } catch (PinpointException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Download files from an Amazon S3 bucket and write them to the path
location.
    public static void downloadFromS3(S3Client s3Client, String path, String
s3BucketName, List<String> objectKeys) {

        String newPath;
        try {
            for (String key : objectKeys) {
                GetObjectRequest objectRequest = GetObjectRequest.builder()
```

```
                        .bucket(s3BucketName)
                        .key(key)
                        .build();

                ResponseBytes<GetObjectResponse> objectBytes =
 s3Client.getObjectAsBytes(objectRequest);
                byte[] data = objectBytes.asByteArray();

                // Write the data to a local file.
                String fileSuffix = new
 SimpleDateFormat("yyyyMMddHHmmss").format(new Date());
                newPath = path + fileSuffix + ".gz";
                File myFile = new File(newPath);
                OutputStream os = new FileOutputStream(myFile);
                os.write(data);
            }
            System.out.println("Download finished.");

        } catch (S3Exception | NullPointerException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateExportJoba Referência AWS SDK for Java 2.x da API.

Exibir informações sobre um endpoint existente do Amazon Pinpoint

Os exemplos de código a seguir mostram como obter endpoints.

CLI

AWS CLI

Como recuperar informações sobre as configurações e os atributos de um endpoint específico de uma aplicação

O exemplo `get-endpoint` a seguir recupera informações sobre as configurações e os atributos de um endpoint específico de uma aplicação.

```
aws pinpoint get-endpoint \
    --application-id 611e3e3cdd47474c9c1399a505665b91 \
    --endpoint-id testendpoint \
    --region us-east-1
```

Saída:

```
{
    "EndpointResponse": {
        "Address": "+11234567890",
        "ApplicationId": "611e3e3cdd47474c9c1399a505665b91",
        "Attributes": {},
        "ChannelType": "SMS",
        "CohortId": "63",
        "CreationDate": "2019-01-28T23:55:11.534Z",
        "EffectiveDate": "2021-08-06T00:04:51.763Z",
        "EndpointStatus": "ACTIVE",
        "Id": "testendpoint",
        "Location": {
            "Country": "USA"
        },
        "Metrics": {
            "SmsDelivered": 1.0
        },
        "OptOut": "ALL",
        "RequestId": "a204b1f2-7e26-48a7-9c80-b49a2143489d",
        "User": {
            "UserAttributes": {
                "Age": [
                    "24"
                ]
            },
        "UserId": "testuser"
        }
    }
}
```

- Para obter detalhes da API, consulte GetEndpointem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import com.google.gson.FieldNamingPolicy;
import com.google.gson.Gson;
import com.google.gson.GsonBuilder;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class LookUpEndpoint {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId> <endpoint>

                Where:
                  appId - The ID of the application to delete.
                  endpoint - The ID of the endpoint.\s
                  """;

        if (args.length != 2) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String appId = args[0];
        String endpoint = args[1];
        System.out.println("Looking up an endpoint point with ID: " + endpoint);
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        lookupPinpointEndpoint(pinpoint, appId, endpoint);
        pinpoint.close();
    }

    public static void lookupPinpointEndpoint(PinpointClient pinpoint, String
 appId, String endpoint) {
        try {
            GetEndpointRequest appRequest = GetEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpoint)
                    .build();

            GetEndpointResponse result = pinpoint.getEndpoint(appRequest);
            EndpointResponse endResponse = result.endpointResponse();

            // Uses the Google Gson library to pretty print the endpoint JSON.
            Gson gson = new GsonBuilder()
                    .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                    .setPrettyPrinting()
                    .create();

            String endpointJson = gson.toJson(endResponse);
            System.out.println(endpointJson);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte GetEndpointa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun lookupPinpointEndpoint(appId: String?, endpoint: String?) {

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.getEndpoint(
            GetEndpointRequest {
                applicationId = appId
                endpointId = endpoint
            }
        )
        val endResponse = result.endpointResponse

        // Uses the Google Gson library to pretty print the endpoint JSON.
        val gson: com.google.gson.Gson = GsonBuilder()
            .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
            .setPrettyPrinting()
            .create()

        val endpointJson: String = gson.toJson(endResponse)
        println(endpointJson)
    }
}
```

- Para obter detalhes da API, consulte a GetEndpointreferência da API AWSSDK for Kotlin.

Importar um segmento do Amazon Pinpoint

O exemplo de código a seguir mostra como importar um segmento.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe um segmento.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CreateImportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.ImportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.ImportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.Format;
import software.amazon.awssdk.services.pinpoint.model.CreateImportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ImportSegment {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId> <bucket> <key> <roleArn>\s

                Where:
                  appId - The application ID to create a segment for.
```

```
                  bucket - The name of the Amazon S3 bucket that contains the
 segment definitons.
                  key - The key of the S3 object.
                  roleArn - ARN of the role that allows Amazon
 Pinpoint to access S3. You need to set trust management for this
 to work. See https://docs.aws.amazon.com/IAM/latest/UserGuide/
reference_policies_elements_principal.html
                  """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String bucket = args[1];
        String key = args[2];
        String roleArn = args[3];

        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        ImportJobResponse response = createImportSegment(pinpoint, appId, bucket,
 key, roleArn);
        System.out.println("Import job for " + bucket + " submitted.");
        System.out.println("See application " + response.applicationId() + " for
 import job status.");
        System.out.println("See application " + response.jobStatus() + " for
 import job status.");
        pinpoint.close();
    }

    public static ImportJobResponse createImportSegment(PinpointClient client,
            String appId,
            String bucket,
            String key,
            String roleArn) {

        try {
            ImportJobRequest importRequest = ImportJobRequest.builder()
                    .defineSegment(true)
                    .registerEndpoints(true)
                    .roleArn(roleArn)
```

```
                    .format(Format.JSON)
                    .s3Url("s3://" + bucket + "/" + key)
                    .build();

            CreateImportJobRequest jobRequest = CreateImportJobRequest.builder()
                    .importJobRequest(importRequest)
                    .applicationId(appId)
                    .build();

            CreateImportJobResponse jobResponse =
 client.createImportJob(jobRequest);
            return jobResponse.importJobResponse();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte CreateImportJoba Referência AWS SDK for Java 2.x da API.

Liste os endpoints do Amazon Pinpoint que estão associados a um ID de usuário específico

O exemplo de código a seguir mostra como listar endpoints.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetUserEndpointsRequest;
import software.amazon.awssdk.services.pinpoint.model.GetUserEndpointsResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListEndpointIds {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <applicationId> <userId>

                Where:
                   applicationId - The ID of the Amazon Pinpoint application that
 has the endpoint.
                   userId - The user id applicable to the endpoints""";

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String applicationId = args[0];
        String userId = args[1];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllEndpoints(pinpoint, applicationId, userId);
        pinpoint.close();
    }

    public static void listAllEndpoints(PinpointClient pinpoint,
            String applicationId,
```

```
            String userId) {

        try {
            GetUserEndpointsRequest endpointsRequest =
 GetUserEndpointsRequest.builder()
                    .userId(userId)
                    .applicationId(applicationId)
                    .build();

            GetUserEndpointsResponse response =
 pinpoint.getUserEndpoints(endpointsRequest);
            List<EndpointResponse> endpoints =
 response.endpointsResponse().item();

            // Display the results.
            for (EndpointResponse endpoint : endpoints) {
                System.out.println("The channel type is: " +
 endpoint.channelType());
                System.out.println("The address is  " + endpoint.address());
            }

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetUserEndpointsa Referência AWS SDK for Java 2.x da API.

Listar segmentos do Amazon Pinpoint em um aplicativo

Os exemplos de código a seguir mostram como listar segmentos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste segmentos.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.GetSegmentsRequest;
import software.amazon.awssdk.services.pinpoint.model.GetSegmentsResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.SegmentResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListSegments {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId>

                Where:
                  appId - The ID of the application that contains a segment.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String appId = args[0];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSegs(pinpoint, appId);
        pinpoint.close();
    }

    public static void listSegs(PinpointClient pinpoint, String appId) {
        try {
            GetSegmentsRequest request = GetSegmentsRequest.builder()
                    .applicationId(appId)
                    .build();

            GetSegmentsResponse response = pinpoint.getSegments(request);
            List<SegmentResponse> segments = response.segmentsResponse().item();
            for (SegmentResponse segment : segments) {
                System.out
                        .println("Segement " + segment.id() + " " +
 segment.name() + " " + segment.lastModifiedDate());
            }

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSegmentsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSegs(appId: String?) {

    PinpointClient { region = "us-west-2" }.use { pinpoint ->

        val response = pinpoint.getSegments(
            GetSegmentsRequest {
                applicationId = appId
            }
        )
        response.segmentsResponse?.item?.forEach { segment ->
            println("Segement id is ${segment.id}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetSegmentsreferência da API AWSSDK for Kotlin.

Envie e-mails e mensagens de texto com o Amazon Pinpoint usando um AWS SDK

Os exemplos de código a seguir mostram como enviar e-mails e mensagens de texto com o Amazon Pinpoint.

CLI

AWS CLI

Como enviar uma mensagem SMS usando o endpoint de uma aplicação

O exemplo `send-messages` a seguir envia uma mensagem direta a uma aplicação com um endpoint.

```
aws pinpoint send-messages \
    --application-id 611e3e3cdd47474c9c1399a505665b91 \
    --message-request file://myfile.json \
    --region us-west-2
```

Conteúdo de `myfile.json`:

```
{
    "MessageConfiguration": {
        "SMSMessage": {
            "Body": "hello, how are you?"
        }
    },
    "Endpoints": {
        "testendpoint": {}
    }
}
```

Saída:

```
{
    "MessageResponse": {
        "ApplicationId": "611e3e3cdd47474c9c1399a505665b91",
        "EndpointResult": {
            "testendpoint": {
                "Address": "+12345678900",
                "DeliveryStatus": "SUCCESSFUL",
                "MessageId": "itnuqhai5alf1n6ahv3udc05n7hhddr6gb3lq6g0",
                "StatusCode": 200,
                "StatusMessage": "MessageId:
 itnuqhai5alf1n6ahv3udc05n7hhddr6gb3lq6g0"
            }
        },
        "RequestId": "c7e23264-04b2-4a46-b800-d24923f74753"
    }
}
```

Para obter mais informações, consulte Canal de SMS do Amazon Pinpoint no Guia do usuário do Amazon Pinpoint.

- Para obter detalhes da API, consulte SendMessagesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.SimpleEmailPart;
import software.amazon.awssdk.services.pinpoint.model.SimpleEmail;
import software.amazon.awssdk.services.pinpoint.model.EmailMessage;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpointemail.PinpointEmailClient;
import software.amazon.awssdk.services.pinpointemail.model.Body;
import software.amazon.awssdk.services.pinpointemail.model.Content;
import software.amazon.awssdk.services.pinpointemail.model.Destination;
import software.amazon.awssdk.services.pinpointemail.model.EmailContent;
import software.amazon.awssdk.services.pinpointemail.model.Message;
import software.amazon.awssdk.services.pinpointemail.model.SendEmailRequest;

import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class SendEmailMessage {

        // The character encoding the you want to use for the subject line and
        // message body of the email.
        public static String charset = "UTF-8";

    // The body of the email for recipients whose email clients support HTML
 content.
    static final String body = """
        Amazon Pinpoint test (AWS SDK for Java 2.x)

        This email was sent through the Amazon Pinpoint Email API using the AWS
 SDK for Java 2.x

        """;

        public static void main(String[] args) {
                final String usage = """

                                Usage:    <subject> <appId> <senderAddress>
 <toAddress>

            Where:
               subject - The email subject to use.
               senderAddress - The from address. This address has to be verified
 in Amazon Pinpoint in the region you're using to send email\s
               toAddress - The to address. This address has to be verified in
 Amazon Pinpoint in the region you're using to send email\s
            """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String subject = args[0];
        String senderAddress = args[1];
        String toAddress = args[2];
        System.out.println("Sending a message");
        PinpointEmailClient pinpoint = PinpointEmailClient.builder()
            .region(Region.US_EAST_1)
            .build();

        sendEmail(pinpoint, subject, senderAddress, toAddress);
```

```
        System.out.println("Email was sent");
        pinpoint.close();
    }

    public static void sendEmail(PinpointEmailClient pinpointEmailClient, String
 subject, String senderAddress, String toAddress) {
        try {
            Content content = Content.builder()
                .data(body)
                .build();

            Body messageBody = Body.builder()
                .text(content)
                .build();

            Message message = Message.builder()
                .body(messageBody)
                .subject(Content.builder().data(subject).build())
                .build();

            Destination destination = Destination.builder()
                .toAddresses(toAddress)
                .build();

            EmailContent emailContent = EmailContent.builder()
                .simple(message)
                .build();

            SendEmailRequest sendEmailRequest = SendEmailRequest.builder()
                .fromEmailAddress(senderAddress)
                .destination(destination)
                .content(emailContent)
                .build();

            pinpointEmailClient.sendEmail(sendEmailRequest);
            System.out.println("Message Sent");

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Envie uma mensagem de e-mail com cópia para outros destinatários.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import  software.amazon.awssdk.services.pinpointemail.PinpointEmailClient;
import software.amazon.awssdk.services.pinpointemail.model.Body;
import software.amazon.awssdk.services.pinpointemail.model.Content;
import software.amazon.awssdk.services.pinpointemail.model.Destination;
import software.amazon.awssdk.services.pinpointemail.model.EmailContent;
import software.amazon.awssdk.services.pinpointemail.model.Message;
import software.amazon.awssdk.services.pinpointemail.model.SendEmailRequest;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendEmailMessageCC {

    // The body of the email.
    static final String body = """
        Amazon Pinpoint test (AWS SDK for Java 2.x)

        This email was sent through the Amazon Pinpoint Email API using the AWS
 SDK for Java 2.x

        """;
    public static void main(String[] args) {
        final String usage = """

            Usage:    <subject> <senderAddress> <toAddress> <ccAddress>

            Where:
               subject - The email subject to use.
               senderAddress - The from address. This address has to be verified
 in Amazon Pinpoint in the region you're using to send email\s
```

```
               toAddress - The to address. This address has to be verified in
Amazon Pinpoint in the region you're using to send email\s
               ccAddress - The CC address.
            """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String subject = args[0];
        String senderAddress = args[1];
        String toAddress = args[2];
        String ccAddress = args[3];

        System.out.println("Sending a message");
        PinpointEmailClient pinpoint = PinpointEmailClient.builder()
            .region(Region.US_EAST_1)
            .build();

        ArrayList<String> ccList = new ArrayList<>();
        ccList.add(ccAddress);
        sendEmail(pinpoint, subject, senderAddress, toAddress, ccList);
        pinpoint.close();
    }

    public static void sendEmail(PinpointEmailClient pinpointEmailClient, String
subject, String senderAddress, String toAddress, ArrayList<String> ccAddresses)
{
        try {
            Content content = Content.builder()
                .data(body)
                .build();

            Body messageBody = Body.builder()
                .text(content)
                .build();

            Message message = Message.builder()
                .body(messageBody)
                .subject(Content.builder().data(subject).build())
                .build();

            Destination destination = Destination.builder()
```

```
                .toAddresses(toAddress)
                .ccAddresses(ccAddresses)
                .build();

            EmailContent emailContent = EmailContent.builder()
                .simple(message)
                .build();

            SendEmailRequest sendEmailRequest = SendEmailRequest.builder()
                .fromEmailAddress(senderAddress)
                .destination(destination)
                .content(emailContent)
                .build();

            pinpointEmailClient.sendEmail(sendEmailRequest);
            System.out.println("Message Sent");

        } catch (PinpointException e) {
            // Handle exception
            e.printStackTrace();
        }
    }
}
```

Envie uma mensagem SMS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.SMSMessage;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesResponse;
import software.amazon.awssdk.services.pinpoint.model.MessageResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendMessage {

        // The type of SMS message that you want to send. If you plan to send
        // time-sensitive content, specify TRANSACTIONAL. If you plan to send
        // marketing-related content, specify PROMOTIONAL.
        public static String messageType = "TRANSACTIONAL";

        // The registered keyword associated with the originating short code.
        public static String registeredKeyword = "myKeyword";

        // The sender ID to use when sending the message. Support for sender ID
        // varies by country or region. For more information, see
        // https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html
        public static String senderId = "MySenderID";

        public static void main(String[] args) {
                final String usage = """

                                Usage:   <message> <appId> <originationNumber>
 <destinationNumber>\s

                                Where:
                                  message - The body of the message to send.
                                  appId - The Amazon Pinpoint project/application
 ID to use when you send this message.
                                  originationNumber - The phone number or
 short code that you specify has to be associated with your Amazon Pinpoint
 account. For best results, specify long codes in E.164 format (for example,
 +1-555-555-5654).
                                  destinationNumber - The recipient's phone
 number.  For best results, you should specify the phone number in E.164 format
 (for example, +1-555-555-5654).\s
                                  """;

                if (args.length != 4) {
                        System.out.println(usage);
```

```
                        System.exit(1);
                }

                String message = args[0];
                String appId = args[1];
                String originationNumber = args[2];
                String destinationNumber = args[3];
                System.out.println("Sending a message");
                PinpointClient pinpoint = PinpointClient.builder()
                                .region(Region.US_EAST_1)
                                .build();

                sendSMSMessage(pinpoint, message, appId, originationNumber,
destinationNumber);
                pinpoint.close();
        }

        public static void sendSMSMessage(PinpointClient pinpoint, String
message, String appId,
                        String originationNumber,
                        String destinationNumber) {
                try {
                        Map<String, AddressConfiguration> addressMap = new
HashMap<String, AddressConfiguration>();
                        AddressConfiguration addConfig =
AddressConfiguration.builder()
                                        .channelType(ChannelType.SMS)
                                        .build();

                        addressMap.put(destinationNumber, addConfig);
                        SMSMessage smsMessage = SMSMessage.builder()
                                        .body(message)
                                        .messageType(messageType)
                                        .originationNumber(originationNumber)
                                        .senderId(senderId)
                                        .keyword(registeredKeyword)
                                        .build();

                        // Create a DirectMessageConfiguration object.
                        DirectMessageConfiguration direct =
DirectMessageConfiguration.builder()
                                        .smsMessage(smsMessage)
                                        .build();
```

```
                        MessageRequest msgReq = MessageRequest.builder()
                                        .addresses(addressMap)
                                        .messageConfiguration(direct)
                                        .build();

                        // create a SendMessagesRequest object
                        SendMessagesRequest request =
 SendMessagesRequest.builder()
                                        .applicationId(appId)
                                        .messageRequest(msgReq)
                                        .build();

                        SendMessagesResponse response =
 pinpoint.sendMessages(request);
                        MessageResponse msg1 = response.messageResponse();
                        Map map1 = msg1.result();

                        // Write out the result of sendMessage.
                        map1.forEach((k, v) -> System.out.println((k + ":" +
 v)));

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

Envie mensagens SMS em massa.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.SMSMessage;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesResponse;
import software.amazon.awssdk.services.pinpoint.model.MessageResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
```

```
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendMessageBatch {

        // The type of SMS message that you want to send. If you plan to send
        // time-sensitive content, specify TRANSACTIONAL. If you plan to send
        // marketing-related content, specify PROMOTIONAL.
        public static String messageType = "TRANSACTIONAL";

        // The registered keyword associated with the originating short code.
        public static String registeredKeyword = "myKeyword";

        // The sender ID to use when sending the message. Support for sender ID
        // varies by country or region. For more information, see
        // https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html
        public static String senderId = "MySenderID";

        public static void main(String[] args) {
                final String usage = """

                                Usage:   <message> <appId> <originationNumber>
 <destinationNumber> <destinationNumber1>\s

                                Where:
                                  message - The body of the message to send.
                                  appId - The Amazon Pinpoint project/application
 ID to use when you send this message.
                                  originationNumber - The phone number or
 short code that you specify has to be associated with your Amazon Pinpoint
 account. For best results, specify long codes in E.164 format (for example,
 +1-555-555-5654).
                                  destinationNumber - The recipient's phone
 number.  For best results, you should specify the phone number in E.164 format
 (for example, +1-555-555-5654).
```

```
                                destinationNumber1 - The second recipient's
phone number.  For best results, you should specify the phone number in E.164
format (for example, +1-555-555-5654).\s
                                """;

               if (args.length != 5) {
                       System.out.println(usage);
                       System.exit(1);
               }

               String message = args[0];
               String appId = args[1];
               String originationNumber = args[2];
               String destinationNumber = args[3];
               String destinationNumber1 = args[4];
               System.out.println("Sending a message");
               PinpointClient pinpoint = PinpointClient.builder()
                               .region(Region.US_EAST_1)
                               .build();

               sendSMSMessage(pinpoint, message, appId, originationNumber,
destinationNumber, destinationNumber1);
               pinpoint.close();
       }

       public static void sendSMSMessage(PinpointClient pinpoint, String
message, String appId,
                       String originationNumber,
                       String destinationNumber, String destinationNumber1) {
               try {
                       Map<String, AddressConfiguration> addressMap = new
HashMap<String, AddressConfiguration>();
                       AddressConfiguration addConfig =
AddressConfiguration.builder()
                                       .channelType(ChannelType.SMS)
                                       .build();

                       // Add an entry to the Map object for each number to whom
you want to send a
                       // message.
                       addressMap.put(destinationNumber, addConfig);
                       addressMap.put(destinationNumber1, addConfig);
                       SMSMessage smsMessage = SMSMessage.builder()
                                       .body(message)
```

```
                                        .messageType(messageType)
                                        .originationNumber(originationNumber)
                                        .senderId(senderId)
                                        .keyword(registeredKeyword)
                                        .build();

                        // Create a DirectMessageConfiguration object.
                        DirectMessageConfiguration direct =
 DirectMessageConfiguration.builder()
                                        .smsMessage(smsMessage)
                                        .build();

                        MessageRequest msgReq = MessageRequest.builder()
                                        .addresses(addressMap)
                                        .messageConfiguration(direct)
                                        .build();

                        // Create a SendMessagesRequest object.
                        SendMessagesRequest request =
 SendMessagesRequest.builder()
                                        .applicationId(appId)
                                        .messageRequest(msgReq)
                                        .build();

                        SendMessagesResponse response =
 pinpoint.sendMessages(request);
                        MessageResponse msg1 = response.messageResponse();
                        Map map1 = msg1.result();

                        // Write out the result of sendMessage.
                        map1.forEach((k, v) -> System.out.println((k + ":" +
 v)));

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { PinpointClient } from "@aws-sdk/client-pinpoint";
// Set the AWS Region.
const REGION = "us-east-1";
//Set the MediaConvert Service Object
const pinClient = new PinpointClient({ region: REGION });
export { pinClient };
```

Envie uma mensagem de e-mail.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

// The FromAddress must be verified in SES.
const fromAddress = "FROM_ADDRESS";
const toAddress = "TO_ADDRESS";
const projectId = "PINPOINT_PROJECT_ID";

// The subject line of the email.
var subject = "Amazon Pinpoint Test (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https://aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
```

```
var body_html = `<html>
<head></head>
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint Email API</a>
 using the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding for the subject line and message body of the email.
var charset = "UTF-8";

const params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: fromAddress,
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};
```

```
const run = async () => {
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));

    const {
      MessageResponse: { Result },
    } = data;

    const recipientResult = Result[toAddress];

    if (recipientResult.StatusCode !== 200) {
      throw new Error(recipientResult.StatusMessage);
    } else {
      console.log(recipientResult.MessageId);
    }
  } catch (err) {
    console.log(err.message);
  }
};

run();
```

Envie uma mensagem SMS.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

("use strict");

/* The phone number or short code to send the message from. The phone number
 or short code that you specify has to be associated with your Amazon Pinpoint
account. For best results, specify long codes in E.164 format. */
const originationNumber = "SENDER_NUMBER"; //e.g., +1XXXXXXXXXX

// The recipient's phone number.  For best results, you should specify the phone
 number in E.164 format.
const destinationNumber = "RECEIVER_NUMBER"; //e.g., +1XXXXXXXXXX

// The content of the SMS message.
```

```
const message =
  "This message was sent through Amazon Pinpoint " +
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

/*The Amazon Pinpoint project/application ID to use when you send this message.
Make sure that the SMS channel is enabled for the project or application
that you choose.*/
const projectId = "PINPOINT_PROJECT_ID"; //e.g., XXXXXXXX66e4e9986478cXXXXXXXXX

/* The type of SMS message that you want to send. If you plan to send
time-sensitive content, specify TRANSACTIONAL. If you plan to send
marketing-related content, specify PROMOTIONAL.*/
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
var registeredKeyword = "myKeyword";

/* The sender ID to use when sending the message. Support for sender ID
// varies by country or region. For more information, see
https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html.*/

var senderId = "MySenderID";

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
```

```
};

const run = async () => {
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));
    return data; // For unit tests.
    console.log(
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  } catch (err) {
    console.log(err);
  }
};
run();
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
"use strict";

const AWS = require("aws-sdk");

// The AWS Region that you want to use to send the email. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
// https://docs.aws.amazon.com/pinpoint/latest/apireference/
const aws_region = "us-west-2";

// The "From" address. This address has to be verified in Amazon Pinpoint
// in the region that you use to send email.
const senderAddress = "sender@example.com";
```

```
// The address on the "To" line. If your Amazon Pinpoint account is in
// the sandbox, this address also has to be verified.
var toAddress = "recipient@example.com";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
const appId = "ce796be37f32f178af652b26eexample";

// The subject line of the email.
var subject = "Amazon Pinpoint (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https:\/\/aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
var body_html = `<html>
<head></head>
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint API</a> using
 the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding the you want to use for the subject line and
// message body of the email.
var charset = "UTF-8";

// Specify that you're using a shared credentials file.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });
```

```
//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: appId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: senderAddress,
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};

//Try to send the email.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
  } else {
    console.log(
      "Email sent! Message ID: ",
      data["MessageResponse"]["Result"][toAddress]["MessageId"]
    );
```

```
  }
});
```

Envie uma mensagem SMS.

```
"use strict";

var AWS = require("aws-sdk");

// The AWS Region that you want to use to send the message. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
// https://docs.aws.amazon.com/pinpoint/latest/apireference/.
var aws_region = "us-east-1";

// The phone number or short code to send the message from. The phone number
// or short code that you specify has to be associated with your Amazon Pinpoint
// account. For best results, specify long codes in E.164 format.
var originationNumber = "+12065550199";

// The recipient's phone number.  For best results, you should specify the
// phone number in E.164 format.
var destinationNumber = "+14255550142";

// The content of the SMS message.
var message =
  "This message was sent through Amazon Pinpoint " +
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
var applicationId = "ce796be37f32f178af652b26eexample";

// The type of SMS message that you want to send. If you plan to send
// time-sensitive content, specify TRANSACTIONAL. If you plan to send
// marketing-related content, specify PROMOTIONAL.
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
```

```
var registeredKeyword = "myKeyword";

// The sender ID to use when sending the message. Support for sender ID
// varies by country or region. For more information, see
// https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html
var senderId = "MySenderID";

// Specify that you're using a shared credentials file, and optionally specify
// the profile that you want to use.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: applicationId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
};

//Try to send the message.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
```

```
    console.log(err.message);
    // Otherwise, show the unique ID for the message.
  } else {
    console.log(
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  }
});
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

val body: String = """
        Amazon Pinpoint test (AWS SDK for Kotlin)

        This email was sent through the Amazon Pinpoint Email API using the AWS
 SDK for Kotlin.

""".trimIndent()
```

```
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <subject> <appId> <senderAddress> <toAddress>

    Where:
        subject - The email subject to use.
        senderAddress - The from address. This address has to be verified in
 Amazon Pinpoint in the region you're using to send email
        toAddress - The to address. This address has to be verified in Amazon
 Pinpoint in the region you're using to send email
    """

    if (args.size != 3) {
        println(usage)
        exitProcess(0)
    }

    val subject = args[0]
    val senderAddress = args[1]
    val toAddress = args[2]
    sendEmail(subject, senderAddress, toAddress)
}

suspend fun sendEmail(subjectVal: String?, senderAddress: String, toAddressVal:
 String) {
    var content = Content {
        data = body
    }

    val messageBody = Body {
        text = content
    }

    val subContent = Content {
        data = subjectVal
    }

    val message = Message {
        body = messageBody
        subject = subContent
    }

    val destinationOb = Destination {
```

```
        toAddresses = listOf(toAddressVal)
    }

    val emailContent = EmailContent {
        simple = message
    }

    val sendEmailRequest = SendEmailRequest {
        fromEmailAddress = senderAddress
        destination = destinationOb
        this.content = emailContent
    }

    PinpointEmailClient { region = "us-east-1" }.use { pinpointemail ->
        pinpointemail.sendEmail(sendEmailRequest)
        println("Message Sent")
    }
}
```

- Para obter detalhes da API, consulte a SendMessagesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
```

```
def send_email_message(
    pinpoint_client,
    app_id,
    sender,
    to_addresses,
    char_set,
    subject,
    html_message,
    text_message,
):
    """
    Sends an email message with HTML and plain text versions.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param app_id: The Amazon Pinpoint project ID to use when you send this
 message.
    :param sender: The "From" address. This address must be verified in
                   Amazon Pinpoint in the AWS Region you're using to send email.
    :param to_addresses: The addresses on the "To" line. If your Amazon Pinpoint
 account
                         is in the sandbox, these addresses must be verified.
    :param char_set: The character encoding to use for the subject line and
 message
                      body of the email.
    :param subject: The subject line of the email.
    :param html_message: The body of the email for recipients whose email clients
 can
                         display HTML content.
    :param text_message: The body of the email for recipients whose email clients
                         don't support HTML content.
    :return: A dict of to_addresses and their message IDs.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=app_id,
            MessageRequest={
                "Addresses": {
                    to_address: {"ChannelType": "EMAIL"} for to_address in
 to_addresses
                },
                "MessageConfiguration": {
                    "EmailMessage": {
                        "FromAddress": sender,
```

```
                        "SimpleEmail": {
                            "Subject": {"Charset": char_set, "Data": subject},
                            "HtmlPart": {"Charset": char_set, "Data":
 html_message},
                            "TextPart": {"Charset": char_set, "Data":
 text_message},
                        },
                    }
                },
            },
        )
    except ClientError:
        logger.exception("Couldn't send email.")
        raise
    else:
        return {
            to_address: message["MessageId"]
            for to_address, message in response["MessageResponse"]
["Result"].items()
        }


def main():
    app_id = "ce796be37f32f178af652b26eexample"
    sender = "sender@example.com"
    to_address = "recipient@example.com"
    char_set = "UTF-8"
    subject = "Amazon Pinpoint Test (SDK for Python (Boto3))"
    text_message = """Amazon Pinpoint Test (SDK for Python)
    -------------------------------------
    This email was sent with Amazon Pinpoint using the AWS SDK for Python
 (Boto3).
    For more information, see https://aws.amazon.com/sdk-for-python/
                """
    html_message = """<html>
    <head></head>
    <body>
      <h1>Amazon Pinpoint Test (SDK for Python (Boto3)</h1>
      <p>This email was sent with
        <a href='https://aws.amazon.com/pinpoint/'>Amazon Pinpoint</a> using the
        <a href='https://aws.amazon.com/sdk-for-python/'>
          AWS SDK for Python (Boto3)</a>.</p>
    </body>
    </html>
```

```
                """

    print("Sending email.")
    message_ids = send_email_message(
        boto3.client("pinpoint"),
        app_id,
        sender,
        [to_address],
        char_set,
        subject,
        html_message,
        text_message,
    )
    print(f"Message sent! Message IDs: {message_ids}")


if __name__ == "__main__":
    main()
```

Envie uma mensagem SMS.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_sms_message(
    pinpoint_client,
    app_id,
    origination_number,
    destination_number,
    message,
    message_type,
):
    """
    Sends an SMS message with Amazon Pinpoint.

    :param pinpoint_client: A Boto3 Pinpoint client.
```

```
    :param app_id: The Amazon Pinpoint project/application ID to use when you
 send
                   this message. The SMS channel must be enabled for the project
 or
                   application.
    :param destination_number: The recipient's phone number in E.164 format.
    :param origination_number: The phone number to send the message from. This
 phone
                               number must be associated with your Amazon
 Pinpoint
                               account and be in E.164 format.
    :param message: The content of the SMS message.
    :param message_type: The type of SMS message that you want to send. If you
 send
                         time-sensitive content, specify TRANSACTIONAL. If you
 send
                         marketing-related content, specify PROMOTIONAL.
    :return: The ID of the message.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=app_id,
            MessageRequest={
                "Addresses": {destination_number: {"ChannelType": "SMS"}},
                "MessageConfiguration": {
                    "SMSMessage": {
                        "Body": message,
                        "MessageType": message_type,
                        "OriginationNumber": origination_number,
                    }
                },
            },
        )
    except ClientError:
        logger.exception("Couldn't send message.")
        raise
    else:
        return response["MessageResponse"]["Result"][destination_number]
["MessageId"]


def main():
    app_id = "ce796be37f32f178af652b26eexample"
    origination_number = "+12065550199"
```

```
    destination_number = "+14255550142"
    message = (
        "This is a sample message sent from Amazon Pinpoint by using the AWS SDK
 for "
        "Python (Boto 3)."
    )
    message_type = "TRANSACTIONAL"

    print("Sending SMS message.")
    message_id = send_sms_message(
        boto3.client("pinpoint"),
        app_id,
        origination_number,
        destination_number,
        message,
        message_type,
    )
    print(f"Message sent! Message ID: {message_id}.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a SendMessagesReferência da API AWSSDK for Python (Boto3).

Envie mensagens de texto e e-mail modeladas com o Amazon Pinpoint usando um SDK AWS

O exemplo de código a seguir mostra como enviar e-mails e mensagens de texto modeladas com o Amazon Pinpoint.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail com um modelo de e-mail existente.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_templated_email_message(
    pinpoint_client, project_id, sender, to_addresses, template_name,
 template_version
):
    """
    Sends an email message with HTML and plain text versions.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param project_id: The Amazon Pinpoint project ID to use when you send this
 message.
    :param sender: The "From" address. This address must be verified in
                   Amazon Pinpoint in the AWS Region you're using to send email.
    :param to_addresses: The addresses on the "To" line. If your Amazon Pinpoint
                         account is in the sandbox, these addresses must be
 verified.
    :param template_name: The name of the email template to use when sending the
 message.
    :param template_version: The version number of the message template.

    :return: A dict of to_addresses and their message IDs.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=project_id,
            MessageRequest={
                "Addresses": {
                    to_address: {"ChannelType": "EMAIL"} for to_address in
 to_addresses
                },
                "MessageConfiguration": {"EmailMessage": {"FromAddress":
 sender}},
                "TemplateConfiguration": {
                    "EmailTemplate": {
                        "Name": template_name,
                        "Version": template_version,
```

```
                    }
                },
            },
        )
    except ClientError:
        logger.exception("Couldn't send email.")
        raise
    else:
        return {
            to_address: message["MessageId"]
            for to_address, message in response["MessageResponse"]
["Result"].items()
        }


def main():
    project_id = "296b04b342374fceb661bf494example"
    sender = "sender@example.com"
    to_addresses = ["recipient@example.com"]
    template_name = "My_Email_Template"
    template_version = "1"

    print("Sending email.")
    message_ids = send_templated_email_message(
        boto3.client("pinpoint"),
        project_id,
        sender,
        to_addresses,
        template_name,
        template_version,
    )
    print(f"Message sent! Message IDs: {message_ids}")


if __name__ == "__main__":
    main()
```

Envie uma mensagem de texto com um modelo de SMS existente.

```
import logging
import boto3
from botocore.exceptions import ClientError
```

```
logger = logging.getLogger(__name__)


def send_templated_sms_message(
    pinpoint_client,
    project_id,
    destination_number,
    message_type,
    origination_number,
    template_name,
    template_version,
):
    """
    Sends an SMS message to a specific phone number using a pre-defined template.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param project_id: An Amazon Pinpoint project (application) ID.
    :param destination_number: The phone number to send the message to.
    :param message_type: The type of SMS message (promotional or transactional).
    :param origination_number: The phone number that the message is sent from.
    :param template_name: The name of the SMS template to use when sending the
 message.
    :param template_version: The version number of the message template.

    :return The ID of the message.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=project_id,
            MessageRequest={
                "Addresses": {destination_number: {"ChannelType": "SMS"}},
                "MessageConfiguration": {
                    "SMSMessage": {
                        "MessageType": message_type,
                        "OriginationNumber": origination_number,
                    }
                },
                "TemplateConfiguration": {
                    "SMSTemplate": {"Name": template_name, "Version":
 template_version}
                },
            },
        )
```

```
    except ClientError:
        logger.exception("Couldn't send message.")
        raise
    else:
        return response["MessageResponse"]["Result"][destination_number]
["MessageId"]


def main():
    region = "us-east-1"
    origination_number = "+18555550001"
    destination_number = "+14255550142"
    project_id = "7353f53e6885409fa32d07cedexample"
    message_type = "TRANSACTIONAL"
    template_name = "My_SMS_Template"
    template_version = "1"
    message_id = send_templated_sms_message(
        boto3.client("pinpoint", region_name=region),
        project_id,
        destination_number,
        message_type,
        origination_number,
        template_name,
        template_version,
    )
    print(f"Message sent! Message ID: {message_id}.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a SendMessagesReferência da API AWSSDK for Python (Boto3).

Atualizar um endpoint do Amazon Pinpoint

O exemplo de código a seguir mostra como atualizar um endpoint.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.EndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.EndpointDemographic;
import software.amazon.awssdk.services.pinpoint.model.EndpointLocation;
import software.amazon.awssdk.services.pinpoint.model.EndpointUser;
import java.text.DateFormat;
import java.text.SimpleDateFormat;
import java.util.List;
import java.util.UUID;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.Map;
import java.util.Date;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateEndpoint {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:  <appId>

                Where:
                  appId - The ID of the application to create an endpoint for.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        EndpointResponse response = createEndpoint(pinpoint, appId);
        System.out.println("Got Endpoint: " + response.id());
        pinpoint.close();
    }

    public static EndpointResponse createEndpoint(PinpointClient client, String
appId) {
        String endpointId = UUID.randomUUID().toString();
        System.out.println("Endpoint ID: " + endpointId);

        try {
            EndpointRequest endpointRequest = createEndpointRequestData();
            UpdateEndpointRequest updateEndpointRequest =
UpdateEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .endpointRequest(endpointRequest)
                    .build();

            UpdateEndpointResponse updateEndpointResponse =
client.updateEndpoint(updateEndpointRequest);
            System.out.println("Update Endpoint Response: " +
updateEndpointResponse.messageBody());

            GetEndpointRequest getEndpointRequest = GetEndpointRequest.builder()
```

```
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .build();

            GetEndpointResponse getEndpointResponse =
client.getEndpoint(getEndpointRequest);
            System.out.println(getEndpointResponse.endpointResponse().address());

System.out.println(getEndpointResponse.endpointResponse().channelType());

System.out.println(getEndpointResponse.endpointResponse().applicationId());

System.out.println(getEndpointResponse.endpointResponse().endpointStatus());

System.out.println(getEndpointResponse.endpointResponse().requestId());
            System.out.println(getEndpointResponse.endpointResponse().user());

            return getEndpointResponse.endpointResponse();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static EndpointRequest createEndpointRequestData() {
        try {
            List<String> favoriteTeams = new ArrayList<>();
            favoriteTeams.add("Lakers");
            favoriteTeams.add("Warriors");
            HashMap<String, List<String>> customAttributes = new HashMap<>();
            customAttributes.put("team", favoriteTeams);

            EndpointDemographic demographic = EndpointDemographic.builder()
                    .appVersion("1.0")
                    .make("apple")
                    .model("iPhone")
                    .modelVersion("7")
                    .platform("ios")
                    .platformVersion("10.1.1")
                    .timezone("America/Los_Angeles")
                    .build();
```

```
            EndpointLocation location = EndpointLocation.builder()
                    .city("Los Angeles")
                    .country("US")
                    .latitude(34.0)
                    .longitude(-118.2)
                    .postalCode("90068")
                    .region("CA")
                    .build();

            Map<String, Double> metrics = new HashMap<>();
            metrics.put("health", 100.00);
            metrics.put("luck", 75.00);

            EndpointUser user = EndpointUser.builder()
                    .userId(UUID.randomUUID().toString())
                    .build();

            DateFormat df = new SimpleDateFormat("yyyy-MM-dd'T'HH:mm'Z'"); //
 Quoted "Z" to indicate UTC, no timezone
                                                                            //
 offset
            String nowAsISO = df.format(new Date());

            return EndpointRequest.builder()
                    .address(UUID.randomUUID().toString())
                    .attributes(customAttributes)
                    .channelType("APNS")
                    .demographic(demographic)
                    .effectiveDate(nowAsISO)
                    .location(location)
                    .metrics(metrics)
                    .optOut("NONE")
                    .requestId(UUID.randomUUID().toString())
                    .user(user)
                    .build();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte UpdateEndpointa Referência AWS SDK for Java 2.x da API.

Atualizar um canal do Amazon Pinpoint

Os exemplos de código a seguir mostram como atualizar canais.

CLI

AWS CLI

Como recuperar informações sobre o status e as configurações do canal de SMS de uma aplicação

O exemplo `get-sms-channel` a seguir recupera o status e as configurações do canal de sms de uma aplicação.

```
aws pinpoint get-sms-channel \
    --application-id 6e0b7591a90841d2b5d93fa11143e5a7 \
    --region us-east-1
```

Saída:

```
{
    "SMSChannelResponse": {
        "ApplicationId": "6e0b7591a90841d2b5d93fa11143e5a7",
        "CreationDate": "2019-10-08T18:39:18.511Z",
        "Enabled": true,
        "Id": "sms",
        "IsArchived": false,
        "LastModifiedDate": "2019-10-08T18:39:18.511Z",
        "Platform": "SMS",
        "PromotionalMessagesPerSecond": 20,
        "TransactionalMessagesPerSecond": 20,
        "Version": 1
    }
}
```

- Para obter detalhes da API, consulte GetSmsChannelem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.SMSChannelResponse;
import software.amazon.awssdk.services.pinpoint.model.GetSmsChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.SMSChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateSmsChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateSmsChannelResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateChannel {
    public static void main(String[] args) {
        final String usage = """

                Usage: CreateChannel <appId>

                Where:
                  appId - The name of the application whose channel is updated.

                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        SMSChannelResponse getResponse = getSMSChannel(pinpoint, appId);
        toggleSmsChannel(pinpoint, appId, getResponse);
        pinpoint.close();
    }

    private static SMSChannelResponse getSMSChannel(PinpointClient client, String
appId) {
        try {
            GetSmsChannelRequest request = GetSmsChannelRequest.builder()
                    .applicationId(appId)
                    .build();

            SMSChannelResponse response =
client.getSmsChannel(request).smsChannelResponse();
            System.out.println("Channel state is " + response.enabled());
            return response;

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static void toggleSmsChannel(PinpointClient client, String appId,
SMSChannelResponse getResponse) {
        boolean enabled = !getResponse.enabled();
        try {
            SMSChannelRequest request = SMSChannelRequest.builder()
                    .enabled(enabled)
                    .build();
```

```
            UpdateSmsChannelRequest updateRequest =
 UpdateSmsChannelRequest.builder()
                    .smsChannelRequest(request)
                    .applicationId(appId)
                    .build();

            UpdateSmsChannelResponse result =
 client.updateSmsChannel(updateRequest);
            System.out.println("Channel state: " +
 result.smsChannelResponse().enabled());

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSmsChannela Referência AWS SDK for Java 2.x da API.

Exemplos de código para a API de SMS e voz do Amazon Pinpoint usando AWS SDKs

Os exemplos de código a seguir mostram como usar a API de SMS e voz do Amazon Pinpoint com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor da API de SMS e voz do Amazon Pinpoint – Mais informações sobre a API de SMS e voz do Amazon Pinpoint.
- Referência da API de SMS e voz do Amazon Pinpoint – Detalhes sobre todas as ações disponíveis da API de SMS e voz do Amazon Pinpoint.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.

- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para a API de SMS e voz do Amazon Pinpoint usando AWS SDKs
  - Enviar uma mensagem de voz com a API de SMS e voz do Amazon Pinpoint usando um AWS SDK

Ações para a API de SMS e voz do Amazon Pinpoint usando AWS SDKs

Os exemplos de código a seguir mostram como usar a API de SMS e voz do Amazon Pinpoint com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos

- Enviar uma mensagem de voz com a API de SMS e voz do Amazon Pinpoint usando um AWS SDK

Enviar uma mensagem de voz com a API de SMS e voz do Amazon Pinpoint usando um AWS SDK

Os exemplos de código a seguir mostram como enviar uma mensagem de voz com a API de SMS e voz do Amazon Pinpoint.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.client.config.ClientOverrideConfiguration;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpointsmsvoice.PinpointSmsVoiceClient;
import software.amazon.awssdk.services.pinpointsmsvoice.model.SSMLMessageType;
```

```
import
 software.amazon.awssdk.services.pinpointsmsvoice.model.VoiceMessageContent;
import
 software.amazon.awssdk.services.pinpointsmsvoice.model.SendVoiceMessageRequest;
import
 software.amazon.awssdk.services.pinpointsmsvoice.model.PinpointSmsVoiceException;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendVoiceMessage {

        // The Amazon Polly voice that you want to use to send the message. For a
 list
        // of voices, see https://docs.aws.amazon.com/polly/latest/dg/
voicelist.html
        static final String voiceName = "Matthew";

        // The language to use when sending the message. For a list of supported
        // languages, see
        // https://docs.aws.amazon.com/polly/latest/dg/SupportedLanguage.html
        static final String languageCode = "en-US";

        // The content of the message. This example uses SSML to customize and
 control
        // certain aspects of the message, such as by adding pauses and changing
        // phonation. The message can't contain any line breaks.
        static final String ssmlMessage = "<speak>This is a test message sent
 from "
                        + "<emphasis>Amazon Pinpoint</emphasis> "
                        + "using the <break strength='weak'/>AWS "
                        + "SDK for Java. "
                        + "<amazon:effect phonation='soft'>Thank "
                        + "you for listening.</amazon:effect></speak>";
```

```
        public static void main(String[] args) {

                final String usage = """

                                Usage:   <originationNumber> <destinationNumber>
\s

                                Where:
                                  originationNumber - The phone number or
 short code that you specify has to be associated with your Amazon Pinpoint
 account. For best results, specify long codes in E.164 format (for example,
 +1-555-555-5654).
                                  destinationNumber - The recipient's phone
 number.  For best results, you should specify the phone number in E.164 format
 (for example, +1-555-555-5654).\s
                                  """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String originationNumber = args[0];
                String destinationNumber = args[1];
                System.out.println("Sending a voice message");

                // Set the content type to application/json.
                List<String> listVal = new ArrayList<>();
                listVal.add("application/json");
                Map<String, List<String>> values = new HashMap<>();
                values.put("Content-Type", listVal);

                ClientOverrideConfiguration config2 =
 ClientOverrideConfiguration.builder()
                                .headers(values)
                                .build();

                PinpointSmsVoiceClient client = PinpointSmsVoiceClient.builder()
                                .overrideConfiguration(config2)
                                .region(Region.US_EAST_1)
                                .build();

                sendVoiceMsg(client, originationNumber, destinationNumber);
```

```
                client.close();
        }

        public static void sendVoiceMsg(PinpointSmsVoiceClient client, String
 originationNumber,
                        String destinationNumber) {
                try {
                        SSMLMessageType ssmlMessageType =
 SSMLMessageType.builder()
                                        .languageCode(languageCode)
                                        .text(ssmlMessage)
                                        .voiceId(voiceName)
                                        .build();

                        VoiceMessageContent content =
 VoiceMessageContent.builder()
                                        .ssmlMessage(ssmlMessageType)
                                        .build();

                        SendVoiceMessageRequest voiceMessageRequest =
 SendVoiceMessageRequest.builder()

 .destinationPhoneNumber(destinationNumber)

 .originationPhoneNumber(originationNumber)
                                        .content(content)
                                        .build();

                        client.sendVoiceMessage(voiceMessageRequest);
                        System.out.println("The message was sent successfully.");

                } catch (PinpointSmsVoiceException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendVoiceMessagea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"use strict";

var AWS = require("aws-sdk");

// The AWS Region that you want to use to send the voice message. For a list of
// AWS Regions where the Amazon Pinpoint SMS and Voice API is available, see
// https://docs.aws.amazon.com/pinpoint-sms-voice/latest/APIReference/
var aws_region = "us-east-1";

// The phone number that the message is sent from. The phone number that you
// specify has to be associated with your Amazon Pinpoint account. For best
 results, you
// should specify the phone number in E.164 format.
var originationNumber = "+12065550110";

// The recipient's phone number. For best results, you should specify the phone
// number in E.164 format.
var destinationNumber = "+12065550142";

// The language to use when sending the message. For a list of supported
// languages, see https://docs.aws.amazon.com/polly/latest/dg/
SupportedLanguage.html
var languageCode = "en-US";

// The Amazon Polly voice that you want to use to send the message. For a list
// of voices, see https://docs.aws.amazon.com/polly/latest/dg/voicelist.html
var voiceId = "Matthew";

// The content of the message. This example uses SSML to customize and control
// certain aspects of the message, such as the volume or the speech rate.
// The message can't contain any line breaks.
```

```
var ssmlMessage =
  "<speak>" +
  "This is a test message sent from <emphasis>Amazon Pinpoint</emphasis> " +
  "using the <break strength='weak'/>AWS SDK for JavaScript in Node.js. " +
  "<amazon:effect phonation='soft'>Thank you for listening." +
  "</amazon:effect>" +
  "</speak>";

// The phone number that you want to appear on the recipient's device. The phone
// number that you specify has to be associated with your Amazon Pinpoint
 account.
var callerId = "+12065550199";

// The configuration set that you want to use to send the message.
var configurationSet = "ConfigSet";

// Specify that you're using a shared credentials file, and optionally specify
// the profile that you want to use.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpointsmsvoice = new AWS.PinpointSMSVoice();

var params = {
  CallerId: callerId,
  ConfigurationSetName: configurationSet,
  Content: {
    SSMLMessage: {
      LanguageCode: languageCode,
      Text: ssmlMessage,
      VoiceId: voiceId,
    },
  },
  DestinationPhoneNumber: destinationNumber,
  OriginationPhoneNumber: originationNumber,
};

//Try to send the message.
pinpointsmsvoice.sendVoiceMessage(params, function (err, data) {
  // If something goes wrong, print an error message.
```

```
  if (err) {
    console.log(err.message);
    // Otherwise, show the unique ID for the message.
  } else {
    console.log("Message sent! Message ID: " + data["MessageId"]);
  }
});
```

- Para obter detalhes da API, consulte SendVoiceMessagea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_voice_message(
    sms_voice_client,
    origination_number,
    caller_id,
    destination_number,
    language_code,
    voice_id,
    ssml_message,
):
    """
```

```
    Sends a voice message using speech synthesis provided by Amazon Polly.

    :param sms_voice_client: A Boto3 PinpointSMSVoice client.
    :param origination_number: The phone number that the message is sent from.
                               The phone number must be associated with your
Amazon
                               Pinpoint account and be in E.164 format.
    :param caller_id: The phone number that you want to appear on the recipient's
                      device. The phone number must be associated with your
Amazon
                      Pinpoint account and be in E.164 format.
    :param destination_number: The recipient's phone number. Specify the phone
                               number in E.164 format.
    :param language_code: The language to use when sending the message.
    :param voice_id: The Amazon Polly voice that you want to use to send the
message.
    :param ssml_message: The content of the message. This example uses SSML to
control
                         certain aspects of the message, such as the volume and
the
                         speech rate. The message must not contain line breaks.
    :return: The ID of the message.
    """
    try:
        response = sms_voice_client.send_voice_message(
            DestinationPhoneNumber=destination_number,
            OriginationPhoneNumber=origination_number,
            CallerId=caller_id,
            Content={
                "SSMLMessage": {
                    "LanguageCode": language_code,
                    "VoiceId": voice_id,
                    "Text": ssml_message,
                }
            },
        )
    except ClientError:
        logger.exception(
            "Couldn't send message from %s to %s.",
            origination_number,
            destination_number,
        )
        raise
    else:
```

```
        return response["MessageId"]


def main():
    origination_number = "+12065550110"
    caller_id = "+12065550199"
    destination_number = "+12065550142"
    language_code = "en-US"
    voice_id = "Matthew"
    ssml_message = (
        "<speak>"
        "This is a test message sent from <emphasis>Amazon Pinpoint</emphasis> "
        "using the <break strength='weak'/>AWS SDK for Python (Boto3). "
        "<amazon:effect phonation='soft'>Thank you for listening."
        "</amazon:effect>"
        "</speak>"
    )
    print(f"Sending voice message from {origination_number} to
 {destination_number}.")
    message_id = send_voice_message(
        boto3.client("pinpoint-sms-voice"),
        origination_number,
        caller_id,
        destination_number,
        language_code,
        voice_id,
        ssml_message,
    )
    print(f"Message sent!\nMessage ID: {message_id}")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a SendVoiceMessageReferência da API AWSSDK for Python (Boto3).

Exemplos de código do Amazon Polly usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Polly com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Polly – Mais informações sobre o Amazon Polly.
- Referência da API do Amazon Polly – Detalhes sobre todas as ações disponíveis do Amazon Polly.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon Polly usando SDKs da AWS
  - Exclua um léxico do Amazon Polly usando um SDK da AWS
  - Obtenha um léxico do Amazon Polly usando um SDK da AWS
  - Obtenha dados sobre uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS
  - Obtenha vozes do Amazon Polly para síntese usando um SDK da AWS
  - Listar léxicos de pronúncia do Amazon Polly usando um SDK da AWS
  - Inicie uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS
  - Armazene um léxico de pronúncia do Amazon Polly usando um SDK da AWS
  - Sintetize fala a partir de texto com o Amazon Polly usando um SDK da AWS.
- Cenários para o Amazon Polly com SDKs da AWS
  - Crie um aplicativo de sincronização labial com o Amazon Polly usando um SDK da AWS
- Exemplos do Amazon Polly entre serviços usando SDKs da AWS
  - Converter texto em fala e de volta em texto usando um AWS SDK
  - Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Ações para o Amazon Polly usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Polly com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon Polly com SDKs da AWS.

Exemplos

- Exclua um léxico do Amazon Polly usando um SDK da AWS
- Obtenha um léxico do Amazon Polly usando um SDK da AWS
- Obtenha dados sobre uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS
- Obtenha vozes do Amazon Polly para síntese usando um SDK da AWS
- Listar léxicos de pronúncia do Amazon Polly usando um SDK da AWS
- Inicie uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS
- Armazene um léxico de pronúncia do Amazon Polly usando um SDK da AWS
- Sintetize fala a partir de texto com o Amazon Polly usando um SDK da AWS.

Exclua um léxico do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um léxico do Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;
```

```
    /// <summary>
    /// Deletes an existing Amazon Polly lexicon using the AWS SDK for .NET.
    /// </summary>
    public class DeleteLexicon
    {
        public static async Task Main()
        {
            string lexiconName = "SampleLexicon";

            var client = new AmazonPollyClient();

            var success = await DeletePollyLexiconAsync(client, lexiconName);

            if (success)
            {
                Console.WriteLine($"Successfully deleted {lexiconName}.");
            }
            else
            {
                Console.WriteLine($"Could not delete {lexiconName}.");
            }
        }

        /// <summary>
        /// Deletes the named Amazon Polly lexicon.
        /// </summary>
        /// <param name="client">The initialized Amazon Polly client object.</
param>
        /// <param name="lexiconName">The name of the Amazon Polly lexicon to
        /// delete.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeletePollyLexiconAsync(
            AmazonPollyClient client,
            string lexiconName)
        {
            var deleteLexiconRequest = new DeleteLexiconRequest()
            {
                Name = lexiconName,
            };

            var response = await client.DeleteLexiconAsync(deleteLexiconRequest);
```

```
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeleteLexicona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir um léxico

O exemplo de `delete-lexicon` a seguir exclui o léxico especificado.

```
aws polly delete-lexicon \
    --name w3c
```

Este comando não produz saída.

Para obter mais informações, consulte Como usar a DeleteLexicon operação no Guia do desenvolvedor do Amazon Polly.

- Para obter detalhes da API, consulte DeleteLexiconem Referência de AWS CLI Comandos.

Obtenha um léxico do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como obter um léxico do Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
```

```
    using System.Threading.Tasks;
    using Amazon.Polly;
    using Amazon.Polly.Model;

    /// <summary>
    /// Retrieves information about a specific Amazon Polly lexicon.
    /// </summary>
    public class GetLexicon
    {
        public static async Task Main(string[] args)
        {
            string lexiconName = "SampleLexicon";

            var client = new AmazonPollyClient();

            await GetPollyLexiconAsync(client, lexiconName);
        }

        public static async Task GetPollyLexiconAsync(AmazonPollyClient client,
 string lexiconName)
        {
            var getLexiconRequest = new GetLexiconRequest()
            {
                Name = lexiconName,
            };

            try
            {
                var response = await client.GetLexiconAsync(getLexiconRequest);
                Console.WriteLine($"Lexicon:\n Name: {response.Lexicon.Name}");
                Console.WriteLine($"Content: {response.Lexicon.Content}");
            }
            catch (Exception ex)
            {
                Console.WriteLine("Error: " + ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte GetLexicona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como recuperar o conteúdo de um léxico

O exemplo de `get-lexicon` a seguir recupera o conteúdo do léxico de pronúncia especificado.

```
aws polly get-lexicon \
    --name w3c
```

Saída:

```
{
    "Lexicon": {
        "Content": "<?xml version=\"1.0\" encoding=\"UTF-8\"?>\n<lexicon version=
\"1.0\" \n      xmlns=    \"http://www.w3.org/2005/01/pronunciation-lexicon
\"\n      xmlns:xsi=\"http://www.w3.org/2001/XMLSchema-instance\" \n
 xsi:schemaLocation=\"http://www.w3.org/2005/01/pronunciation-lexicon \n
 http://www.w3.org/TR/2007/CR-pronunciation-    lexicon-20071212/pls.xsd\"\n
   alphabet=\"ipa\" \n      xml:lang=\"en-US\">\n  <lexeme>\n    <grapheme>W3C</
grapheme>\n        <alias>World Wide Web Consortium</alias>\n  </lexeme>\n</
lexicon>\n",
        "Name": "w3c"
    },
    "LexiconAttributes": {
        "Alphabet": "ipa",
        "LanguageCode": "en-US",
        "LastModified": 1603908910.99,
        "LexiconArn": "arn:aws:polly:us-west-2:880185128111:lexicon/w3c",
        "LexemesCount": 1,
        "Size": 492
    }
}
```

Para obter mais informações, consulte Como usar a GetLexicon operação no Amazon Polly Developer Guide.

- Para obter detalhes da API, consulte GetLexiconem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def get_lexicon(self, name):
        """
        Gets metadata and contents of an existing lexicon.

        :param name: The name of the lexicon to retrieve.
        :return: The retrieved lexicon.
        """
        try:
            response = self.polly_client.get_lexicon(Name=name)
            logger.info("Got lexicon %s.", name)
        except ClientError:
            logger.exception("Couldn't get lexicon %s.", name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetLexiconReferência da API AWSSDK for Python (Boto3).

Obtenha dados sobre uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados sobre uma tarefa de síntese de fala assíncrona existente do Amazon Polly.

CLI

AWS CLI

Como obter informações sobre uma tarefa de síntese de fala

O exemplo de `get-speech-synthesis-task` a seguir recupera informações sobre a tarefa de síntese de fala especificada.

```
aws polly get-speech-synthesis-task \
    --task-id 70b61c0f-57ce-4715-a247-cae8729dcce9
```

Saída:

```
{
    "SynthesisTask": {
        "TaskId": "70b61c0f-57ce-4715-a247-cae8729dcce9",
        "TaskStatus": "completed",
        "OutputUri": "https://s3.us-west-2.amazonaws.com/my-s3-
bucket/70b61c0f-57ce-4715-a247-cae8729dcce9.mp3",
        "CreationTime": 1603911042.689,
        "RequestCharacters": 1311,
        "OutputFormat": "mp3",
        "TextType": "text",
        "VoiceId": "Joanna"
    }
}
```

Para obter mais informações, consulte Criar arquivos de áudio longos no Guia do desenvolvedor do Amazon Polly.

- Para obter detalhes da API, consulte GetSpeechSynthesisTaskem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def get_speech_synthesis_task(self, task_id):
        """
        Gets metadata about an asynchronous speech synthesis task, such as its
 status.

        :param task_id: The ID of the task to retrieve.
        :return: Metadata about the task.
        """
        try:
            response =
 self.polly_client.get_speech_synthesis_task(TaskId=task_id)
            task = response["SynthesisTask"]
            logger.info("Got synthesis task. Status is %s.", task["TaskStatus"])
        except ClientError:
```

```
            logger.exception("Couldn't get synthesis task %s.", task_id)
            raise
        else:
            return task
```

- Para obter detalhes da API, consulte a GetSpeechSynthesisTaskReferência da API AWSSDK for Python (Boto3).

Obtenha vozes do Amazon Polly para síntese usando um SDK da AWS

Os exemplos de código a seguir mostram como obter vozes disponíveis para síntese do Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

public class DescribeVoices
{
    public static async Task Main()
    {
        var client = new AmazonPollyClient();

        var allVoicesRequest = new DescribeVoicesRequest();
        var enUsVoicesRequest = new DescribeVoicesRequest()
        {
            LanguageCode = "en-US",
        };
```

```
            try
            {
                string nextToken;
                do
                {
                    var allVoicesResponse = await
client.DescribeVoicesAsync(allVoicesRequest);
                    nextToken = allVoicesResponse.NextToken;
                    allVoicesRequest.NextToken = nextToken;

                    Console.WriteLine("\nAll voices: ");
                    allVoicesResponse.Voices.ForEach(voice =>
                    {
                        DisplayVoiceInfo(voice);
                    });
                }
                while (nextToken is not null);

                do
                {
                    var enUsVoicesResponse = await
client.DescribeVoicesAsync(enUsVoicesRequest);
                    nextToken = enUsVoicesResponse.NextToken;
                    enUsVoicesRequest.NextToken = nextToken;

                    Console.WriteLine("\nen-US voices: ");
                    enUsVoicesResponse.Voices.ForEach(voice =>
                    {
                        DisplayVoiceInfo(voice);
                    });
                }
                while (nextToken is not null);
            }
            catch (Exception ex)
            {
                Console.WriteLine("Exception caught: " + ex.Message);
            }
        }

        public static void DisplayVoiceInfo(Voice voice)
        {
            Console.WriteLine($" Name: {voice.Name}\tGender:
{voice.Gender}\tLanguageName: {voice.LanguageName}");
```

```
        }
    }
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.DescribeVoicesRequest;
import software.amazon.awssdk.services.polly.model.DescribeVoicesResponse;
import software.amazon.awssdk.services.polly.model.PollyException;
import software.amazon.awssdk.services.polly.model.Voice;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeVoicesSample {
    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();
```

```
        describeVoice(polly);
        polly.close();
    }

    public static void describeVoice(PollyClient polly) {
        try {
            DescribeVoicesRequest voicesRequest = DescribeVoicesRequest.builder()
                    .languageCode("en-US")
                    .build();

            DescribeVoicesResponse enUsVoicesResult =
 polly.describeVoices(voicesRequest);
            List<Voice> voices = enUsVoicesResult.voices();
            for (Voice myVoice : voices) {
                System.out.println("The ID of the voice is " + myVoice.id());
                System.out.println("The gender of the voice is " +
 myVoice.gender());
            }

        } catch (PollyException e) {
            System.err.println("Exception caught: " + e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
```

```
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def describe_voices(self):
        """
        Gets metadata about available voices.

        :return: The list of voice metadata.
        """
        try:
            response = self.polly_client.describe_voices()
            self.voice_metadata = response["Voices"]
            logger.info("Got metadata about %s voices.",
len(self.voice_metadata))
        except ClientError:
            logger.exception("Couldn't get voice metadata.")
            raise
        else:
            return self.voice_metadata
```

- Para obter detalhes da API, consulte a DescribeVoicesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/
config
  polly = Aws::Polly::Client.new

  # Get US English voices
  resp = polly.describe_voices(language_code: "en-US")

  resp.voices.each do |v|
    puts v.name
    puts "  " + v.gender
    puts
  end
rescue StandardError => ex
  puts "Could not get voices"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_voices(client: &Client) -> Result<(), Error> {
    let resp = client.describe_voices().send().await?;

    println!("Voices:");

    let voices = resp.voices();
    for voice in voices {
        println!("  Name:     {}", voice.name().unwrap_or("No name!"));
        println!(
            "  Language: {}",
            voice.language_name().unwrap_or("No language!")
        );

        println!();
    }

    println!("Found {} voices", voices.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeVoicesreferência da API AWS SDK for Rust.

Listar léxicos de pronúncia do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como listar léxicos de pronúncia do Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

/// <summary>
/// Lists the Amazon Polly lexicons that have been defined. By default,
/// lists the lexicons that are defined in the same AWS Region as the default
/// user. To view Amazon Polly lexicons that are defined in a different AWS
/// Region, supply it as a parameter to the Amazon Polly constructor.
/// </summary>
public class ListLexicons
{
    public static async Task Main()
    {
        var client = new AmazonPollyClient();
        var request = new ListLexiconsRequest();

        try
        {
            Console.WriteLine("All voices: ");

            do
            {
                var response = await client.ListLexiconsAsync(request);
                request.NextToken = response.NextToken;

                response.Lexicons.ForEach(lexicon =>
                {
                    var attributes = lexicon.Attributes;
                    Console.WriteLine($"Name: {lexicon.Name}");
                    Console.WriteLine($"\tAlphabet: {attributes.Alphabet}");
```

```
                        Console.WriteLine($"\tLanguageCode:
 {attributes.LanguageCode}");
                        Console.WriteLine($"\tLastModified:
 {attributes.LastModified}");
                        Console.WriteLine($"\tLexemesCount:
 {attributes.LexemesCount}");
                        Console.WriteLine($"\tLexiconArn:
 {attributes.LexiconArn}");
                        Console.WriteLine($"\tSize: {attributes.Size}");
                    });
                }
                while (request.NextToken is not null);
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os léxicos

O exemplo de `list-lexicons` a seguir lista os léxicos de pronúncia.

```
aws polly list-lexicons
```

Saída:

```
{
    "Lexicons": [
        {
            "Name": "w3c",
            "Attributes": {
                "Alphabet": "ipa",
```

```
                "LanguageCode": "en-US",
                "LastModified": 1603908910.99,
                "LexiconArn": "arn:aws:polly:us-east-2:123456789012:lexicon/w3c",
                "LexemesCount": 1,
                "Size": 492
            }
        }
    ]
}
```

Para obter mais informações, consulte Como usar a ListLexicons operação no Amazon Polly Developer Guide.

- Para obter detalhes da API, consulte ListLexiconsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.ListLexiconsResponse;
import software.amazon.awssdk.services.polly.model.ListLexiconsRequest;
import software.amazon.awssdk.services.polly.model.LexiconDescription;
import software.amazon.awssdk.services.polly.model.PollyException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class ListLexicons {
    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();

        listLexicons(polly);
        polly.close();
    }

    public static void listLexicons(PollyClient client) {
        try {
            ListLexiconsRequest listLexiconsRequest =
 ListLexiconsRequest.builder()
                    .build();

            ListLexiconsResponse listLexiconsResult =
 client.listLexicons(listLexiconsRequest);
            List<LexiconDescription> lexiconDescription =
 listLexiconsResult.lexicons();
            for (LexiconDescription lexDescription : lexiconDescription) {
                System.out.println("The name of the Lexicon is " +
 lexDescription.name());
            }

        } catch (PollyException e) {
            System.err.println("Exception caught: " + e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def list_lexicons(self):
        """
        Lists lexicons in the current account.

        :return: The list of lexicons.
        """
        try:
            response = self.polly_client.list_lexicons()
            lexicons = response["Lexicons"]
            logger.info("Got %s lexicons.", len(lexicons))
        except ClientError:
            logger.exception(
                "Couldn't get  %s.",
            )
            raise
        else:
            return lexicons
```

- Para obter detalhes da API, consulte a ListLexiconsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/
config
  polly = Aws::Polly::Client.new

  resp = polly.list_lexicons

  resp.lexicons.each do |l|
    puts l.name
    puts "  Alphabet:" + l.attributes.alphabet
    puts "  Language:" + l.attributes.language
    puts
  end
rescue StandardError => ex
  puts "Could not get lexicons"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_lexicons(client: &Client) -> Result<(), Error> {
    let resp = client.list_lexicons().send().await?;

    println!("Lexicons:");

    let lexicons = resp.lexicons();

    for lexicon in lexicons {
        println!("  Name:     {}", lexicon.name().unwrap_or_default());
        println!(
            "  Language: {:?}\n",
            lexicon
                .attributes()
                .as_ref()
                .map(|attrib| attrib
                    .language_code
                    .as_ref()
                    .expect("languages must have language codes"))
                .expect("languages must have attributes")
        );
    }

    println!();
    println!("Found {} lexicons.", lexicons.len());
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListLexiconsreferência da API AWS SDK for Rust.

Inicie uma tarefa de síntese de fala do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar uma tarefa de síntese de fala assíncrona do Amazon Polly.

CLI

AWS CLI

Como sintetizar texto

O exemplo de `start-speech-synthesis-task` a seguir sintetiza o texto em `text_file.txt` e armazena o arquivo MP3 resultante no bucket especificado.

```
aws polly start-speech-synthesis-task \
    --output-format mp3 \
    --output-s3-bucket-name my-s3-bucket \
    --text  file://text_file.txt \
    --voice-id Joanna
```

Saída:

```
{
    "SynthesisTask": {
        "TaskId": "70b61c0f-57ce-4715-a247-cae8729dcce9",
        "TaskStatus": "scheduled",
        "OutputUri": "https://s3.us-east-2.amazonaws.com/my-s3-
bucket/70b61c0f-57ce-4715-a247-cae8729dcce9.mp3",
        "CreationTime": 1603911042.689,
        "RequestCharacters": 1311,
        "OutputFormat": "mp3",
        "TextType": "text",
        "VoiceId": "Joanna"
    }
}
```

Para obter mais informações, consulte Criar arquivos de áudio longos no Guia do desenvolvedor do Amazon Polly.

- Para obter detalhes da API, consulte StartSpeechSynthesisTaskem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def do_synthesis_task(
        self,
        text,
        engine,
        voice,
        audio_format,
        s3_bucket,
        lang_code=None,
        include_visemes=False,
        wait_callback=None,
    ):
        """
        Start an asynchronous task to synthesize speech or speech marks, wait for
        the task to complete, retrieve the output from Amazon S3, and return the
        data.

        An asynchronous task is required when the text is too long for near-real
 time
```

```
        synthesis.

        :param text: The text to synthesize.
        :param engine: The kind of engine used. Can be standard or neural.
        :param voice: The ID of the voice to use.
        :param audio_format: The audio format to return for synthesized speech.
When
                             speech marks are synthesized, the output format is
JSON.
        :param s3_bucket: The name of an existing Amazon S3 bucket that you have
                          write access to. Synthesis output is written to this
bucket.
        :param lang_code: The language code of the voice to use. This has an
effect
                          only when a bilingual voice is selected.
        :param include_visemes: When True, a second request is made to Amazon
Polly
                                to synthesize a list of visemes, using the
specified
                                text and voice. A viseme represents the visual
position
                                of the face and mouth when saying part of a word.
        :param wait_callback: A callback function that is called periodically
during
                              task processing, to give the caller an opportunity
to
                              take action, such as to display status.
        :return: The audio stream that contains the synthesized speech and a list
                 of visemes that are associated with the speech audio.
        """
        try:
            kwargs = {
                "Engine": engine,
                "OutputFormat": audio_format,
                "OutputS3BucketName": s3_bucket,
                "Text": text,
                "VoiceId": voice,
            }
            if lang_code is not None:
                kwargs["LanguageCode"] = lang_code
            response = self.polly_client.start_speech_synthesis_task(**kwargs)
            speech_task = response["SynthesisTask"]
            logger.info("Started speech synthesis task %s.",
speech_task["TaskId"])
```

```
            viseme_task = None
            if include_visemes:
                kwargs["OutputFormat"] = "json"
                kwargs["SpeechMarkTypes"] = ["viseme"]
                response =
self.polly_client.start_speech_synthesis_task(**kwargs)
                viseme_task = response["SynthesisTask"]
                logger.info("Started viseme synthesis task %s.",
viseme_task["TaskId"])
        except ClientError:
            logger.exception("Couldn't start synthesis task.")
            raise
        else:
            bucket = self.s3_resource.Bucket(s3_bucket)
            audio_stream = self._wait_for_task(
                10, speech_task["TaskId"], "speech", wait_callback, bucket
            )

            visemes = None
            if include_visemes:
                viseme_data = self._wait_for_task(
                    10, viseme_task["TaskId"], "viseme", wait_callback, bucket
                )
                visemes = [
                    json.loads(v) for v in viseme_data.read().decode().split() if
v
                ]

            return audio_stream, visemes
```

- Para obter detalhes da API, consulte a StartSpeechSynthesisTaskReferência da API AWSSDK for Python (Boto3).

Armazene um léxico de pronúncia do Amazon Polly usando um SDK da AWS

Os exemplos de código a seguir mostram como armazenar um léxico de pronúncia do Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Polly;
    using Amazon.Polly.Model;

    /// <summary>
    /// Creates a new Amazon Polly lexicon using the AWS SDK for .NET.
    /// </summary>
    public class PutLexicon
    {
        public static async Task Main()
        {
            string lexiconContent = "<?xml version=\"1.0\" encoding=\"UTF-8\"?>"
 +
                "<lexicon version=\"1.0\" xmlns=\"http://www.w3.org/2005/01/
pronunciation-lexicon\" xmlns:xsi=\"http://www.w3.org/2001/XMLSchema-instance\" "
 +
                "xsi:schemaLocation=\"http://www.w3.org/2005/01/pronunciation-
lexicon http://www.w3.org/TR/2007/CR-pronunciation-lexicon-20071212/pls.xsd\" " +
                "alphabet=\"ipa\" xml:lang=\"en-US\">" +
                "<lexeme><grapheme>test1</grapheme><alias>test2</alias></lexeme>"
 +
                "</lexicon>";
            string lexiconName = "SampleLexicon";

            var client = new AmazonPollyClient();
            var putLexiconRequest = new PutLexiconRequest()
            {
                Name = lexiconName,
                Content = lexiconContent,
            };
```

```
            try
            {
                var response = await client.PutLexiconAsync(putLexiconRequest);
                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    Console.WriteLine($"Successfully created Lexicon:
 {lexiconName}.");
                }
                else
                {
                    Console.WriteLine($"Could not create Lexicon:
 {lexiconName}.");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine("Exception caught: " + ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte PutLexicona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como armazenar um léxico

O exemplo de `put-lexicon` a seguir armazena o léxico de pronúncia especificado. O arquivo `example.pls` especifica um léxico compatível com o PLS do W3C.

```
aws polly put-lexicon \
    --name w3c \
    --content file://example.pls
```

Conteúdo de `example.pls`

```
{
    <?xml version="1.0" encoding="UTF-8"?>
```

```
    <lexicon version="1.0"
        xmlns="http://www.w3.org/2005/01/pronunciation-lexicon"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.w3.org/2005/01/pronunciation-lexicon
            http://www.w3.org/TR/2007/CR-pronunciation-lexicon-20071212/pls.xsd"
        alphabet="ipa"
        xml:lang="en-US">
        <lexeme>
            <grapheme>W3C</grapheme>
            <alias>World Wide Web Consortium</alias>
        </lexeme>
    </lexicon>
}
```

Este comando não produz saída.

Para obter mais informações, consulte Como usar a PutLexicon operação no Amazon Polly Developer Guide.

- Para obter detalhes da API, consulte PutLexiconem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
```

```
        self.voice_metadata = None


    def create_lexicon(self, name, content):
        """
        Creates a lexicon with the specified content. A lexicon contains custom
        pronunciations.

        :param name: The name of the lexicon.
        :param content: The content of the lexicon.
        """
        try:
            self.polly_client.put_lexicon(Name=name, Content=content)
            logger.info("Created lexicon %s.", name)
        except ClientError:
            logger.exception("Couldn't create lexicon %s.")
            raise
```

- Para obter detalhes da API, consulte a PutLexiconReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_lexicon(client: &Client, name: &str, from: &str, to: &str) ->
 Result<(), Error> {
    let content = format!("<?xml version=\"1.0\" encoding=\"UTF-8\"?>
    <lexicon version=\"1.0\" xmlns=\"http://www.w3.org/2005/01/pronunciation-
lexicon\" xmlns:xsi=\"http://www.w3.org/2001/XMLSchema-instance\"
    xsi:schemaLocation=\"http://www.w3.org/2005/01/pronunciation-lexicon http://
www.w3.org/TR/2007/CR-pronunciation-lexicon-20071212/pls.xsd\"
    alphabet=\"ipa\" xml:lang=\"en-US\">
```

```
    <lexeme><grapheme>{}</grapheme><alias>{}</alias></lexeme>
    </lexicon>", from, to);

    client
        .put_lexicon()
        .name(name)
        .content(content)
        .send()
        .await?;

    println!("Added lexicon");

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutLexiconreferência da API AWS SDK for Rust.

Sintetize fala a partir de texto com o Amazon Polly usando um SDK da AWS.

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Polly;
    using Amazon.Polly.Model;

    public class SynthesizeSpeech
    {
        public static async Task Main()
        {
```

```
            string outputFileName = "speech.mp3";
            string text = "Twas brillig, and the slithy toves did gyre and gimbol
in the wabe";

            var client = new AmazonPollyClient();
            var response = await PollySynthesizeSpeech(client, text);

            WriteSpeechToStream(response.AudioStream, outputFileName);
        }

        /// <summary>
        /// Calls the Amazon Polly SynthesizeSpeechAsync method to convert text
        /// to speech.
        /// </summary>
        /// <param name="client">The Amazon Polly client object used to connect
        /// to the Amazon Polly service.</param>
        /// <param name="text">The text to convert to speech.</param>
        /// <returns>A SynthesizeSpeechResponse object that includes an
AudioStream
        /// object with the converted text.</returns>
        private static async Task<SynthesizeSpeechResponse>
PollySynthesizeSpeech(IAmazonPolly client, string text)
        {
            var synthesizeSpeechRequest = new SynthesizeSpeechRequest()
            {
                OutputFormat = OutputFormat.Mp3,
                VoiceId = VoiceId.Joanna,
                Text = text,
            };

            var synthesizeSpeechResponse =
                await client.SynthesizeSpeechAsync(synthesizeSpeechRequest);

            return synthesizeSpeechResponse;
        }

        /// <summary>
        /// Writes the AudioStream returned from the call to
        /// SynthesizeSpeechAsync to a file in MP3 format.
        /// </summary>
        /// <param name="audioStream">The AudioStream returned from the
        /// call to the SynthesizeSpeechAsync method.</param>
        /// <param name="outputFileName">The full path to the file in which to
        /// save the audio stream.</param>
```

```
        private static void WriteSpeechToStream(Stream audioStream, string
 outputFileName)
        {
            var outputStream = new FileStream(
                outputFileName,
                FileMode.Create,
                FileAccess.Write);
            byte[] buffer = new byte[2 * 1024];
            int readBytes;

            while ((readBytes = audioStream.Read(buffer, 0, 2 * 1024)) > 0)
            {
                outputStream.Write(buffer, 0, readBytes);
            }

            // Flushes the buffer to avoid losing the last second or so of
            // the synthesized text.
            outputStream.Flush();
            Console.WriteLine($"Saved {outputFileName} to disk.");
        }
    }
```

Sintetize fala a partir de texto usando marcas de fala com o Amazon Polly usando um SDK da AWS.

```
    using System;
    using System.Collections.Generic;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Polly;
    using Amazon.Polly.Model;

    public class SynthesizeSpeechMarks
    {
        public static async Task Main()
        {
            var client = new AmazonPollyClient();
            string outputFileName = "speechMarks.json";

            var synthesizeSpeechRequest = new SynthesizeSpeechRequest()
            {
```

```
                OutputFormat = OutputFormat.Json,
                SpeechMarkTypes = new List<string>
                {
                    SpeechMarkType.Viseme,
                    SpeechMarkType.Word,
                },
                VoiceId = VoiceId.Joanna,
                Text = "This is a sample text to be synthesized.",
            };

            try
            {
                using (var outputStream = new FileStream(outputFileName,
FileMode.Create, FileAccess.Write))
                {
                    var synthesizeSpeechResponse = await
client.SynthesizeSpeechAsync(synthesizeSpeechRequest);
                    var buffer = new byte[2 * 1024];
                    int readBytes;

                    var inputStream = synthesizeSpeechResponse.AudioStream;
                    while ((readBytes = inputStream.Read(buffer, 0, 2 * 1024)) >
0)
                    {
                        outputStream.Write(buffer, 0, readBytes);
                    }
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte SynthesizeSpeech a Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import javazoom.jl.decoder.JavaLayerException;
import software.amazon.awssdk.core.ResponseInputStream;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.DescribeVoicesRequest;
import software.amazon.awssdk.services.polly.model.Voice;
import software.amazon.awssdk.services.polly.model.DescribeVoicesResponse;
import software.amazon.awssdk.services.polly.model.OutputFormat;
import software.amazon.awssdk.services.polly.model.PollyException;
import software.amazon.awssdk.services.polly.model.SynthesizeSpeechRequest;
import software.amazon.awssdk.services.polly.model.SynthesizeSpeechResponse;
import java.io.IOException;
import java.io.InputStream;
import javazoom.jl.player.advanced.AdvancedPlayer;
import javazoom.jl.player.advanced.PlaybackEvent;
import javazoom.jl.player.advanced.PlaybackListener;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PollyDemo {
    private static final String SAMPLE = "Congratulations. You have successfully
 built this working demo " +
            " of Amazon Polly in Java Version 2. Have fun building voice enabled
 apps with Amazon Polly (that's me!), and always "
            +
```

```
            " look at the AWS website for tips and tricks on using Amazon Polly
and other great services from AWS";

    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();

        talkPolly(polly);
        polly.close();
    }

    public static void talkPolly(PollyClient polly) {
        try {
            DescribeVoicesRequest describeVoiceRequest =
DescribeVoicesRequest.builder()
                    .engine("standard")
                    .build();

            DescribeVoicesResponse describeVoicesResult =
polly.describeVoices(describeVoiceRequest);
            Voice voice = describeVoicesResult.voices().stream()
                    .filter(v -> v.name().equals("Joanna"))
                    .findFirst()
                    .orElseThrow(() -> new RuntimeException("Voice not found"));
            InputStream stream = synthesize(polly, SAMPLE, voice,
OutputFormat.MP3);
            AdvancedPlayer player = new AdvancedPlayer(stream,

javazoom.jl.player.FactoryRegistry.systemRegistry().createAudioDevice());
            player.setPlayBackListener(new PlaybackListener() {
                public void playbackStarted(PlaybackEvent evt) {
                    System.out.println("Playback started");
                    System.out.println(SAMPLE);
                }

                public void playbackFinished(PlaybackEvent evt) {
                    System.out.println("Playback finished");
                }
            });

            // play it!
            player.play();
```

```
        } catch (PollyException | JavaLayerException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static InputStream synthesize(PollyClient polly, String text, Voice
 voice, OutputFormat format)
            throws IOException {
        SynthesizeSpeechRequest synthReq = SynthesizeSpeechRequest.builder()
                .text(text)
                .voiceId(voice.id())
                .outputFormat(format)
                .build();

        ResponseInputStream<SynthesizeSpeechResponse> synthRes =
 polly.synthesizeSpeech(synthReq);
        return synthRes;
    }
}
```

- Para obter detalhes da API, consulte SynthesizeSpeecha Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
```

```
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def synthesize(
        self, text, engine, voice, audio_format, lang_code=None,
include_visemes=False
    ):
        """
        Synthesizes speech or speech marks from text, using the specified voice.

        :param text: The text to synthesize.
        :param engine: The kind of engine used. Can be standard or neural.
        :param voice: The ID of the voice to use.
        :param audio_format: The audio format to return for synthesized speech.
When
                             speech marks are synthesized, the output format is
JSON.
        :param lang_code: The language code of the voice to use. This has an
effect
                          only when a bilingual voice is selected.
        :param include_visemes: When True, a second request is made to Amazon
Polly
                                to synthesize a list of visemes, using the
specified
                                text and voice. A viseme represents the visual
position
                                of the face and mouth when saying part of a word.
        :return: The audio stream that contains the synthesized speech and a list
                 of visemes that are associated with the speech audio.
        """
        try:
            kwargs = {
                "Engine": engine,
                "OutputFormat": audio_format,
                "Text": text,
                "VoiceId": voice,
            }
            if lang_code is not None:
                kwargs["LanguageCode"] = lang_code
```

```
            response = self.polly_client.synthesize_speech(**kwargs)
            audio_stream = response["AudioStream"]
            logger.info("Got audio stream spoken by %s.", voice)
            visemes = None
            if include_visemes:
                kwargs["OutputFormat"] = "json"
                kwargs["SpeechMarkTypes"] = ["viseme"]
                response = self.polly_client.synthesize_speech(**kwargs)
                visemes = [
                    json.loads(v)
                    for v in response["AudioStream"].read().decode().split()
                    if v
                ]
                logger.info("Got %s visemes.", len(visemes))
        except ClientError:
            logger.exception("Couldn't get audio stream.")
            raise
        else:
            return audio_stream, visemes
```

- Para obter detalhes da API, consulte a SynthesizeSpeechReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Get the filename from the command line
  if ARGV.empty?
```

```
    puts "You must supply a filename"
    exit 1
  end

  filename = ARGV[0]

  # Open file and get the contents as a string
  if File.exist?(filename)
    contents = IO.read(filename)
  else
    puts "No such file: " + filename
    exit 1
  end

  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/
config
  polly = Aws::Polly::Client.new

  resp = polly.synthesize_speech({
    output_format: "mp3",
    text: contents,
    voice_id: "Joanna",
  })

  # Save output
  # Get just the file name
  #  abc/xyz.txt -> xyx.txt
  name = File.basename(filename)

  # Split up name so we get just the xyz part
  parts = name.split(".")
  first_part = parts[0]
  mp3_file = first_part + ".mp3"

  IO.copy_stream(resp.audio_stream, mp3_file)

  puts "Wrote MP3 content to: " + mp3_file
rescue StandardError => ex
  puts "Got error:"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte SynthesizeSpeecha Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn synthesize(client: &Client, filename: &str) -> Result<(), Error> {
    let content = fs::read_to_string(filename);

    let resp = client
        .synthesize_speech()
        .output_format(OutputFormat::Mp3)
        .text(content.unwrap())
        .voice_id(VoiceId::Joanna)
        .send()
        .await?;

    // Get MP3 data from response and save it
    let mut blob = resp
        .audio_stream
        .collect()
        .await
        .expect("failed to read data");

    let parts: Vec<&str> = filename.split('.').collect();
    let out_file = format!("{}{}", String::from(parts[0]), ".mp3");

    let mut file = tokio::fs::File::create(out_file)
        .await
        .expect("failed to create file");

    file.write_all_buf(&mut blob)
```

```
        .await
        .expect("failed to write to file");

    Ok(())
}
```

- Para obter detalhes da API, consulte a SynthesizeSpeechreferência da API AWS SDK for Rust.

Cenários para o Amazon Polly com SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Polly com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie um aplicativo de sincronização labial com o Amazon Polly usando um SDK da AWS

Crie um aplicativo de sincronização labial com o Amazon Polly usando um SDK da AWS

O exemplo de código a seguir mostra como criar uma aplicação de sincronização de lábios com o Amazon Polly.

Python

SDK para Python (Boto3)

Mostra como usar o Amazon Polly e o Tkinter para criar um aplicativo de sincronização labial que exibe um rosto animado falando junto com a fala sintetizada pelo Amazon Polly. A sincronização labial é realizada solicitando uma lista de fonemas do Amazon Polly que correspondam à fala sintetizada.

- Obter metadados de voz do Amazon Polly e exibir os mesmos em uma aplicação Tkinter.
- Obter áudio de fala sintetizado e marcas de fala de fonema correspondentes do Amazon Polly.

- Reproduzir o áudio com movimentos sincronizados da boca em um rosto animado.
- Enviar tarefas de síntese assíncrona para textos longos e recuperar a saída de um bucket do Amazon Simple Storage Service (Amazon S3).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly

Exemplos do Amazon Polly entre serviços usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Polly com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Converter texto em fala e de volta em texto usando um AWS SDK
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Converter texto em fala e de volta em texto usando um AWS SDK

O código de exemplo a seguir mostra como:

- Usar o Amazon Polly para sintetizar um arquivo de entrada de texto simples (UTF-8) para um arquivo de áudio.
- Faça upload do arquivo de áudio para um bucket do Amazon S3.
- Usar o Amazon Transcribe para converter o arquivo de áudio em texto.
- Exibir o texto.

Rust

SDK for Rust

Use o Amazon Polly para sintetizar um arquivo de texto simples (UTF-8) para um arquivo de áudio, fazer upload do arquivo de áudio para um bucket do Amazon S3, usar o Amazon Transcribe para converter esse arquivo de áudio em texto e exibir o texto.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly
- Amazon S3
- Amazon Transcribe

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Os exemplos de código a seguir mostram como criar uma aplicação que analisa os cartões de comentários dos clientes, os traduz do idioma original, determina seus sentimentos e gera um arquivo de áudio do texto traduzido.

.NET

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Java

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";

/**
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );
```

```
  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);

  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";

/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
 */
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
```

```
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
    VoiceId: "Ruth",
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
```

```
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});

  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });

  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Ruby

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Exemplos de código para o QLDB usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon QLDB (QLDB) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do QLDB – Mais informações sobre o QLDB.

- Referência da API do QLDB – Detalhes sobre todas as ações disponíveis do QLDB.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o QLDB usando SDKs da AWS
  - Crie um livro-razão do QLDB usando um SDK da AWS
  - Liste seus livros-razão do QLDB usando um SDK da AWS

Ações para o QLDB usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon QLDB (QLDB) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um livro-razão do QLDB usando um SDK da AWS
- Liste seus livros-razão do QLDB usando um SDK da AWS

Crie um livro-razão do QLDB usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um livro de registros do QLDB.

CLI

AWS CLI

Exemplo 1: como criar um livro contábil com propriedades padrão

O exemplo de `create-ledger` a seguir cria um livro contábil com o nome `myExampleLedger` e o modo de permissões `STANDARD`. Como os parâmetros opcionais para proteção contra exclusão e da chave do AWS KMS não foram especificados, eles assumem `true` e uma chave do KMS de propriedade da AWS, respectivamente, como padrão.

```
aws qldb create-ledger \
    --name myExampleLedger \
```

```
    --permissions-mode STANDARD
```

Saída:

```
{
    "State": "CREATING",
    "Arn": "arn:aws:qldb:us-west-2:123456789012:ledger/myExampleLedger",
    "DeletionProtection": true,
    "CreationDateTime": 1568839243.951,
    "Name": "myExampleLedger",
    "PermissionsMode": "STANDARD"
}
```

Exemplo 2: como criar um livro de registros com proteção contra exclusão desabilitada, uma chave de KMS gerenciada pelo cliente e tags especificadas

O exemplo de `create-ledger` a seguir cria um livro contábil com o nome `myExampleLedger2` e o modo de permissões `STANDARD`. O recurso de proteção conta exclusão é desabilitado, a chave do KMS gerenciada pelo cliente especificada é usada para criptografia em repouso e as tags especificadas são anexadas ao recurso.

```
aws qldb create-ledger \
    --name myExampleLedger2 \
    --permissions-mode STANDARD \
    --no-deletion-protection \
    --kms-key arn:aws:kms:us-west-2:123456789012:key/a1b2c3d4-5678-90ab-cdef-
EXAMPLE11111 \
    --tags IsTest=true,Domain=Test
```

Saída:

```
{
    "Arn": "arn:aws:qldb:us-west-2:123456789012:ledger/myExampleLedger2",
    "DeletionProtection": false,
    "CreationDateTime": 1568839543.557,
    "State": "CREATING",
    "Name": "myExampleLedger2",
    "PermissionsMode": "STANDARD",
    "KmsKeyArn": "arn:aws:kms:us-west-2:123456789012:key/a1b2c3d4-5678-90ab-cdef-
EXAMPLE11111"
}
```

Para obter mais informações, consulte Basic Operations for Amazon QLDB Ledgers no Guia do desenvolvedor do Amazon QLDB.

- Para obter detalhes da API, consulte CreateLedgerem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_ledger(client: &Client, ledger: &str) -> Result<(), Error> {
    let result = client
        .create_ledger()
        .name(ledger)
        .permissions_mode(PermissionsMode::AllowAll)
        .send()
        .await?;

    println!("ARN: {}", result.arn().unwrap());

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateLedgerreferência da API AWS SDK for Rust.

Liste seus livros-razão do QLDB usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os livros de registros do QLDB.

CLI

AWS CLI

Como listar os livros de registros disponíveis

O exemplo de `list-ledgers` a seguir lista todos os livros de registros associados à conta e região atuais da AWS.

```
aws qldb list-ledgers
```

Saída:

```
{
    "Ledgers": [
        {
            "State": "ACTIVE",
            "CreationDateTime": 1568839243.951,
            "Name": "myExampleLedger"
        },
        {
            "State": "ACTIVE",
            "CreationDateTime": 1568839543.557,
            "Name": "myExampleLedger2"
        }
    ]
}
```

Para obter mais informações, consulte Basic Operations for Amazon QLDB Ledgers no Guia do desenvolvedor do Amazon QLDB.

- Para obter detalhes da API, consulte ListLedgersem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_ledgers(client: &QLDBClient) -> Result<(), Error> {
    let mut pages = client.list_ledgers().into_paginator().page_size(2).send();
```

```
    while let Some(page) = pages.next().await {
        println!("* {:?}", page); //Prints an entire page of ledgers.
        for ledger in page.unwrap().ledgers() {
            println!("* {:?}", ledger); //Prints the LedgerSummary of a single
 ledger.
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListLedgersreferência da API AWS SDK for Rust.

Exemplos de código para o Amazon RDS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service (Amazon EKS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do Amazon RDS – Mais informações sobre o Amazon RDS.
- Referência da API do Amazon RDS — Detalhes sobre todas as ações disponíveis do Amazon RDS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon RDS

O exemplo de código a seguir mostra como começar a usar o Amazon RDS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.RDS;
using Amazon.RDS.Model;

namespace RDSActions;

public static class HelloRds
{
    static async Task Main(string[] args)
    {
        var rdsClient = new AmazonRDSClient();

        Console.WriteLine($"Hello Amazon RDS! Following are some of your DB
 instances:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first twenty DB instances.
        var response = await rdsClient.DescribeDBInstancesAsync(
            new DescribeDBInstancesRequest()
            {
                MaxRecords = 20 // Must be between 20 and 100.
            });

        foreach (var instance in response.DBInstances)
        {
            Console.WriteLine($"\tDB name: {instance.DBName}");
            Console.WriteLine($"\tArn: {instance.DBInstanceArn}");
```

```
            Console.WriteLine($"\tIdentifier: {instance.DBInstanceIdentifier}");
            Console.WriteLine();
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_rds")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
```

```
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_rds.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_rds.cpp.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBInstancesRequest.h>
#include <iostream>

/*
 *  A "Hello Rds" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client and
 *  describes the Amazon RDS instances.
 *
 *  main function
 *
 *  Usage: 'hello_rds'
 *
 */
```

```
int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::RDS::RDSClient rdsClient(clientConfig);
        Aws::String marker;
        std::vector<Aws::String> instanceDBIDs;

        do {
            Aws::RDS::Model::DescribeDBInstancesRequest request;

            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
                    rdsClient.DescribeDBInstances(request);

            if (outcome.IsSuccess()) {
                for (auto &instance: outcome.GetResult().GetDBInstances()) {
                    instanceDBIDs.push_back(instance.GetDBInstanceIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
                result = 1;
                std::cerr << "Error with RDS::DescribeDBInstances. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!marker.empty());

        std::cout << instanceDBIDs.size() << " RDS instances found." <<
 std::endl;
        for (auto &instanceDBID: instanceDBIDs) {
            std::cout << "   Instance: " << instanceDBID << std::endl;
```

```
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/rds"
)

// main uses the AWS SDK for Go V2 to create an Amazon Relational Database
 Service (Amazon RDS)
// client and list up to 20 DB instances in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
```

```
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 rdsClient := rds.NewFromConfig(sdkConfig)
 const maxInstances = 20
 fmt.Printf("Let's list up to %v DB instances.\n", maxInstances)
 output, err := rdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{MaxRecords: aws.Int32(maxInstances)})
 if err != nil {
  fmt.Printf("Couldn't list DB instances: %v\n", err)
  return
 }
 if len(output.DBInstances) == 0 {
  fmt.Println("No DB instances found.")
 } else {
  for _, instance := range output.DBInstances {
   fmt.Printf("DB instance %v has database %v.\n",
 *instance.DBInstanceIdentifier,
    *instance.DBName)
  }
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.RdsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeDBInstances {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeInstances(rdsClient);
        rdsClient.close();
    }

    public static void describeInstances(RdsClient rdsClient) {
        try {
            DescribeDbInstancesResponse response =
 rdsClient.describeDBInstances();
            List<DBInstance> instanceList = response.dbInstances();
            for (DBInstance instance : instanceList) {
                System.out.println("Instance ARN is: " +
 instance.dbInstanceArn());
                System.out.println("The Engine is " + instance.engine());
                System.out.println("Connection endpoint is" +
 instance.endpoint().address());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Exemplos de código

- Ações para o Amazon SNS usando AWS SDKs
  - Criar uma instância de banco de dados do Amazon RDS usando um AWS SDK
  - Criar um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
  - Criar um snapshot de uma instância de banco de dados do Amazon RDS usando um AWS SDK
  - Criar um token de autenticação para autenticação do IAM em um banco de dados do Amazon RDS usando um AWS SDK
  - Excluir uma instância de banco de dados do Amazon RDS usando um AWS SDK
  - Excluir um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever as instâncias de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever os grupos de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever as versões do mecanismo de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever as opções de instâncias de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
  - Descrever os snapshots de instâncias de banco de dados do Amazon RDS usando um AWS SDK
  - Modificar uma instância de banco de dados do Amazon RDS usando um AWS SDK
  - Reinicializar uma instância de banco de dados do Amazon RDS usando um AWS SDK
  - Recuperar atributos que pertencem a uma conta do Amazon RDS usando um AWS SDK
  - Atualizar os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
- Cenários do Amazon RDS usando AWS SDKs
  - Começar a usar instâncias de banco de dados do Amazon RDS usando um AWS SDK
- Exemplos sem servidor para Amazon RDS usando SDKs AWS

- Conectando-se a um banco de dados do Amazon RDS em uma função Lambda
- Exemplos do Amazon RDS entre serviços usando AWS SDKs
  - Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Ações para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service (Amazon RDS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon RDS usando AWS SDKs.

Exemplos

- Criar uma instância de banco de dados do Amazon RDS usando um AWS SDK
- Criar um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
- Criar um snapshot de uma instância de banco de dados do Amazon RDS usando um AWS SDK
- Criar um token de autenticação para autenticação do IAM em um banco de dados do Amazon RDS usando um AWS SDK
- Excluir uma instância de banco de dados do Amazon RDS usando um AWS SDK
- Excluir um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
- Descrever as instâncias de banco de dados do Amazon RDS usando um AWS SDK
- Descrever os grupos de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
- Descrever as versões do mecanismo de banco de dados do Amazon RDS usando um AWS SDK
- Descrever as opções de instâncias de banco de dados do Amazon RDS usando um AWS SDK
- Descrever os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK
- Descrever os snapshots de instâncias de banco de dados do Amazon RDS usando um AWS SDK
- Modificar uma instância de banco de dados do Amazon RDS usando um AWS SDK
- Reinicializar uma instância de banco de dados do Amazon RDS usando um AWS SDK
- Recuperar atributos que pertencem a uma conta do Amazon RDS usando um AWS SDK
- Atualizar os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Criar uma instância de banco de dados do Amazon RDS usando um AWS SDK

Os códigos de exemplo a seguir mostram como criar uma instância de banco de dados do Amazon RDS e aguardar até que se torne disponível.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   /// <summary>
   /// Create an RDS DB instance with a particular set of properties. Use the
action DescribeDBInstancesAsync
   /// to determine when the DB instance is ready to use.
   /// </summary>
   /// <param name="dbName">Name for the DB instance.</param>
   /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
   /// <param name="parameterGroupName">DB parameter group to associate with the
instance.</param>
   /// <param name="dbEngine">The engine for the DB instance.</param>
   /// <param name="dbEngineVersion">Version for the DB instance.</param>
   /// <param name="instanceClass">Class for the DB instance.</param>
   /// <param name="allocatedStorage">The amount of storage in gibibytes (GiB)
to allocate to the DB instance.</param>
   /// <param name="adminName">Admin user name.</param>
   /// <param name="adminPassword">Admin user password.</param>
   /// <returns>DB instance object.</returns>
   public async Task<DBInstance> CreateDBInstance(string dbName, string
dbInstanceIdentifier,
       string parameterGroupName, string dbEngine, string dbEngineVersion,
```

```
        string instanceClass, int allocatedStorage, string adminName, string
adminPassword)
    {
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBName = dbName,
                DBInstanceIdentifier = dbInstanceIdentifier,
                DBParameterGroupName = parameterGroupName,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass,
                AllocatedStorage = allocatedStorage,
                MasterUsername = adminName,
                MasterUserPassword = adminPassword
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);
```

```
        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBName(DB_NAME);
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetEngine(engineVersion.GetEngine());
        request.SetEngineVersion(engineVersion.GetEngineVersion());
        request.SetDBInstanceClass(dbInstanceClass);
        request.SetStorageType(DB_STORAGE_TYPE);
        request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como criar uma instância de banco de dados

O exemplo de `create-db-instance` a seguir usa as opções necessárias para iniciar uma nova instância de banco de dados.

```
aws rds create-db-instance \
    --db-instance-identifier test-mysql-instance \
    --db-instance-class db.t3.micro \
```

```
    --engine mysql \
    --master-username admin \
    --master-user-password secret99 \
    --allocated-storage 20
```

Saída:

```
{
    "DBInstance": {
        "DBInstanceIdentifier": "test-mysql-instance",
        "DBInstanceClass": "db.t3.micro",
        "Engine": "mysql",
        "DBInstanceStatus": "creating",
        "MasterUsername": "admin",
        "AllocatedStorage": 20,
        "PreferredBackupWindow": "12:55-13:25",
        "BackupRetentionPeriod": 1,
        "DBSecurityGroups": [],
        "VpcSecurityGroups": [
            {
                "VpcSecurityGroupId": "sg-12345abc",
                "Status": "active"
            }
        ],
        "DBParameterGroups": [
            {
                "DBParameterGroupName": "default.mysql5.7",
                "ParameterApplyStatus": "in-sync"
            }
        ],
        "DBSubnetGroup": {
            "DBSubnetGroupName": "default",
            "DBSubnetGroupDescription": "default",
            "VpcId": "vpc-2ff2ff2f",
            "SubnetGroupStatus": "Complete",
            "Subnets": [
                {
                    "SubnetIdentifier": "subnet-########",
                    "SubnetAvailabilityZone": {
                        "Name": "us-west-2c"
                    },
                    "SubnetStatus": "Active"
                },
```

```
                {
                    "SubnetIdentifier": "subnet-########",
                    "SubnetAvailabilityZone": {
                        "Name": "us-west-2d"
                    },
                    "SubnetStatus": "Active"
                },
                {
                    "SubnetIdentifier": "subnet-########",
                    "SubnetAvailabilityZone": {
                        "Name": "us-west-2a"
                    },
                    "SubnetStatus": "Active"
                },
                {
                    "SubnetIdentifier": "subnet-########",
                    "SubnetAvailabilityZone": {
                        "Name": "us-west-2b"
                    },
                    "SubnetStatus": "Active"
                }
            ]
        },
        "PreferredMaintenanceWindow": "sun:08:07-sun:08:37",
        "PendingModifiedValues": {
            "MasterUserPassword": "****"
        },
        "MultiAZ": false,
        "EngineVersion": "5.7.22",
        "AutoMinorVersionUpgrade": true,
        "ReadReplicaDBInstanceIdentifiers": [],
        "LicenseModel": "general-public-license",
        "OptionGroupMemberships": [
            {
                "OptionGroupName": "default:mysql-5-7",
                "Status": "in-sync"
            }
        ],
        "PubliclyAccessible": true,
        "StorageType": "gp2",
        "DbInstancePort": 0,
        "StorageEncrypted": false,
        "DbiResourceId": "db-5555EXAMPLE44444444EXAMPLE",
        "CACertificateIdentifier": "rds-ca-2019",
```

```
        "DomainMemberships": [],
        "CopyTagsToSnapshot": false,
        "MonitoringInterval": 0,
        "DBInstanceArn": "arn:aws:rds:us-west-2:123456789012:db:test-mysql-
instance",
        "IAMDatabaseAuthenticationEnabled": false,
        "PerformanceInsightsEnabled": false,
        "DeletionProtection": false,
        "AssociatedRoles": []
    }
}
```

Para obter mais informações, consulte Criar uma instância de banco de dados do Amazon RDS no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte CreateDBInstance na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateInstance creates a DB instance.
func (instances *DbInstances) CreateInstance(instanceName string, dbName string,
 dbEngine string, dbEngineVersion string, parameterGroupName string,
 dbInstanceClass string,
 storageType string, allocatedStorage int32, adminName string, adminPassword
 string) (
 *types.DBInstance, error) {
```

```
 output, err := instances.RdsClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBName:               aws.String(dbName),
  DBParameterGroupName: aws.String(parameterGroupName),
  Engine:               aws.String(dbEngine),
  EngineVersion:        aws.String(dbEngineVersion),
  DBInstanceClass:      aws.String(dbInstanceClass),
  StorageType:          aws.String(storageType),
  AllocatedStorage:     aws.Int32(allocatedStorage),
  MasterUsername:       aws.String(adminName),
  MasterUserPassword:   aws.String(adminPassword),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import com.google.gson.Gson;
import
 software.amazon.awssdk.auth.credentials.EnvironmentVariableCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
```

```
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;

import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For more details, see:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 *
 */

public class CreateDBInstance {
    public static long sleepTime = 20;

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <dbName> <secretName>

                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
```

```
                    dbName - The database name.\s
                    secretName - The name of the AWS Secrets Manager secret that
contains the database credentials."
               """;

       if (args.length != 3) {
           System.out.println(usage);
           System.exit(1);
       }

       String dbInstanceIdentifier = args[0];
       String dbName = args[1];
       String secretName = args[2];
       Gson gson = new Gson();
       User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
User.class);
       Region region = Region.US_WEST_2;
       RdsClient rdsClient = RdsClient.builder()
               .region(region)
               .build();

       createDatabaseInstance(rdsClient, dbInstanceIdentifier, dbName,
user.getUsername(), user.getPassword());
       waitForInstanceReady(rdsClient, dbInstanceIdentifier);
       rdsClient.close();
   }

   private static SecretsManagerClient getSecretClient() {
       Region region = Region.US_WEST_2;
       return SecretsManagerClient.builder()
               .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
               .build();
   }

   private static String getSecretValues(String secretName) {
       SecretsManagerClient secretClient = getSecretClient();
       GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
               .secretId(secretName)
               .build();

       GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
```

```
        return valueResponse.secretString();
    }

    public static void createDatabaseInstance(RdsClient rdsClient,
            String dbInstanceIdentifier,
            String dbName,
            String userName,
            String userPassword) {

        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .allocatedStorage(100)
                    .dbName(dbName)
                    .engine("mysql")
                    .dbInstanceClass("db.m4.large")
                    .engineVersion("8.0")
                    .storageType("standard")
                    .masterUsername(userName)
                    .masterUserPassword(userPassword)
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Waits until the database instance is available.
    public static void waitForInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
```

```
                    .build();

            // Loop until the cluster is ready.
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
 rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
                    if (instanceReadyStr.contains("available"))
                        instanceReady = true;
                    else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database instance is available!");

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDatabaseInstance(
    dbInstanceIdentifierVal: String?,
```

```
    dbNamedbVal: String?,
    masterUsernameVal: String?,
    masterUserPasswordVal: String?
) {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        allocatedStorage = 100
        dbName = dbNamedbVal
        engine = "mysql"
        dbInstanceClass = "db.m4.large"
        engineVersion = "8.0"
        storageType = "standard"
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
    }
}

// Waits until the database instance is available.
suspend fun waitForInstanceReady(dbInstanceIdentifierVal: String?) {
    val sleepTime: Long = 20
    var instanceReady = false
    var instanceReadyStr = ""
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            val instanceList = response.dbInstances
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus.toString()
                    if (instanceReadyStr.contains("available")) {
                        instanceReady = true
                    } else {
                        println("...$instanceReadyStr")
```

```
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
        println("Database instance is available!")
    }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;



$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

$dbIdentifier = '<<{{db-identifier}}>>';
$dbClass = 'db.t2.micro';
$storage = 5;
$engine = 'MySQL';
$username = 'MyUser';
$password = 'MyPassword';
```

```
try {
    $result = $rdsClient->createDBInstance([
        'DBInstanceIdentifier' => $dbIdentifier,
        'DBInstanceClass' => $dbClass,
        'AllocatedStorage' => $storage,
        'Engine' => $engine,
        'MasterUsername' => $username,
        'MasterUserPassword' => $password,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
```

```
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_db_instance(
        self,
        db_name,
        instance_id,
        parameter_group_name,
        db_engine,
        db_engine_version,
        instance_class,
        storage_type,
        allocated_storage,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB instance.

        :param db_name: The name of the database that is created in the DB
instance.
        :param instance_id: The ID to give the newly created DB instance.
        :param parameter_group_name: A parameter group to associate with the DB
instance.
        :param db_engine: The database engine of a database to create in the DB
instance.
        :param db_engine_version: The engine version for the created database.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :param storage_type: The storage type of the DB instance.
        :param allocated_storage: The amount of storage allocated on the DB
instance, in GiBs.
        :param admin_name: The name of the admin user for the created database.
        :param admin_password: The admin password for the created database.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBName=db_name,
```

```
                DBInstanceIdentifier=instance_id,
                DBParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                DBInstanceClass=instance_class,
                StorageType=storage_type,
                AllocatedStorage=allocated_storage,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Python (Boto3).

Criar um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como criar um grupo de parâmetros de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new DB parameter group. Use the action
DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="family">Family of the DB parameter group.</param>
    /// <param name="description">Description of the DB parameter group.</param>
    /// <returns>The new DB parameter group.</returns>
    public async Task<DBParameterGroup> CreateDBParameterGroup(
        string name, string family, string description)
    {
        var response = await _amazonRDS.CreateDBParameterGroupAsync(
            new CreateDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                DBParameterGroupFamily = family,
                Description = description
            });
        return response.DBParameterGroup;
    }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBParameterGroupRequest request;
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetDBParameterGroupFamily(dbParameterGroupFamily);
    request.SetDescription("Example parameter group.");

    Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
            client.CreateDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully created."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::CreateDBParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como criar um grupo de parâmetros de banco de dados

O exemplo de `create-db-parameter-group` a seguir cria um grupo de parâmetros de banco de dados.

```
aws rds create-db-parameter-group \
    --db-parameter-group-name mydbparametergroup \
    --db-parameter-group-family MySQL5.6 \
    --description "My new parameter group"
```

Saída:

```
{
    "DBParameterGroup": {
        "DBParameterGroupName": "mydbparametergroup",
        "DBParameterGroupFamily": "mysql5.6",
        "Description": "My new parameter group",
        "DBParameterGroupArn": "arn:aws:rds:us-
east-1:123456789012:pg:mydbparametergroup"
    }
}
```

Para obter mais informações, consulte Criar um grupo de parâmetros de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência de AWS CLIComandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateParameterGroup creates a DB parameter group that is based on the
 specified
// parameter group family.
func (instances *DbInstances) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBParameterGroup, error) {

 output, err := instances.RdsClient.CreateDBParameterGroup(context.TODO(),
  &rds.CreateDBParameterGroupInput{
   DBParameterGroupName:   aws.String(parameterGroupName),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
   Description:            aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBParameterGroup, err
 }
}
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void createDBParameterGroup(RdsClient rdsClient, String
 dbGroupName, String dbParameterGroupFamily) {
        try {
            CreateDbParameterGroupRequest groupRequest =
 CreateDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .description("Created by using the AWS SDK for Java")
                    .build();

            CreateDbParameterGroupResponse response =
 rdsClient.createDBParameterGroup(groupRequest);
            System.out.println("The group name is " +
 response.dbParameterGroup().dbParameterGroupName());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
```

```
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB parameter group that is based on the specified parameter
group
        family.

        :param parameter_group_name: The name of the newly created parameter
group.
        :param parameter_group_family: The family that is used as the basis of
the new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API CreateDB ParameterGroup no AWSSDK for Python (Boto3).

Criar um snapshot de uma instância de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como criar um snapshot de uma instância de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a snapshot of a DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBSnapshot> CreateDBSnapshot(string dbInstanceIdentifier,
string snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBSnapshotAsync(
            new CreateDBSnapshotRequest()
            {
```

```
                DBSnapshotIdentifier = snapshotIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        return response.DBSnapshot;
    }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
```

```
                        << outcome.GetError().GetMessage()
                        << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
                return false;
            }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como criar um snapshot de banco de dados

O exemplo de `create-db-snapshot` a seguir cria um snapshot de banco de dados.

```
aws rds create-db-snapshot \
    --db-instance-identifier database-mysql \
    --db-snapshot-identifier mydbsnapshot
```

Saída:

```
{
    "DBSnapshot": {
        "DBSnapshotIdentifier": "mydbsnapshot",
        "DBInstanceIdentifier": "database-mysql",
        "Engine": "mysql",
        "AllocatedStorage": 100,
        "Status": "creating",
        "Port": 3306,
        "AvailabilityZone": "us-east-1b",
        "VpcId": "vpc-6594f31c",
        "InstanceCreateTime": "2019-04-30T15:45:53.663Z",
        "MasterUsername": "admin",
        "EngineVersion": "5.6.40",
        "LicenseModel": "general-public-license",
        "SnapshotType": "manual",
        "Iops": 1000,
        "OptionGroupName": "default:mysql-5-6",
```

```
        "PercentProgress": 0,
        "StorageType": "io1",
        "Encrypted": true,
        "KmsKeyId": "arn:aws:kms:us-east-1:123456789012:key/
AKIAIOSFODNN7EXAMPLE",
        "DBSnapshotArn": "arn:aws:rds:us-
east-1:123456789012:snapshot:mydbsnapshot",
        "IAMDatabaseAuthenticationEnabled": false,
        "ProcessorFeatures": [],
        "DbiResourceId": "db-AKIAIOSFODNN7EXAMPLE"
    }
}
```

Para obter mais informações, consulte Criar um snapshot de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte CreateDBSnapshot na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateSnapshot creates a snapshot of a DB instance.
func (instances *DbInstances) CreateSnapshot(instanceName string, snapshotName
 string) (
 *types.DBSnapshot, error) {
 output, err := instances.RdsClient.CreateDBSnapshot(context.TODO(),
 &rds.CreateDBSnapshotInput{
```

```
  DBInstanceIdentifier: aws.String(instanceName),
  DBSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBSnapshot, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Create an Amazon RDS snapshot.
   public static void createSnapshot(RdsClient rdsClient, String
dbInstanceIdentifier, String dbSnapshotIdentifier) {
       try {
           CreateDbSnapshotRequest snapshotRequest =
CreateDbSnapshotRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .dbSnapshotIdentifier(dbSnapshotIdentifier)
                   .build();

           CreateDbSnapshotResponse response =
rdsClient.createDBSnapshot(snapshotRequest);
           System.out.println("The Snapshot id is " +
response.dbSnapshot().dbiResourceId());
```

```
        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Java 2.x.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;



$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

$dbIdentifier = '<<{{db-identifier}}>>';
$snapshotName = '<<{{backup_2018_12_25}}>>';

try {
    $result = $rdsClient->createDBSnapshot([
        'DBInstanceIdentifier' => $dbIdentifier,
        'DBSnapshotIdentifier' => $snapshotName,
    ]);
    var_dump($result);
} catch (AwsException $e) {
```

```
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_snapshot(self, snapshot_id, instance_id):
        """
        Creates a snapshot of a DB instance.
```

```
        :param snapshot_id: The ID to give the created snapshot.
        :param instance_id: The ID of the DB instance to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_snapshot(
                DBSnapshotIdentifier=snapshot_id,
DBInstanceIdentifier=instance_id
            )
            snapshot = response["DBSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# Create a snapshot for an Amazon Relational Database Service (Amazon RDS)
# DB instance.
#
```

```
# @param rds_resource [Aws::RDS::Resource] The resource containing SDK logic.
# @param db_instance_name [String] The name of the Amazon RDS DB instance.
# @return [Aws::RDS::DBSnapshot, nil] The snapshot created, or nil if error.
def create_snapshot(rds_resource, db_instance_name)
  id = "snapshot-#{rand(10**6)}"
  db_instance = rds_resource.db_instance(db_instance_name)
  db_instance.create_snapshot({
                              db_snapshot_identifier: id
                            })
rescue Aws::Errors::ServiceError => e
  puts "Couldn't create DB instance snapshot #{id}:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Ruby.

Criar um token de autenticação para autenticação do IAM em um banco de dados do Amazon RDS usando um AWS SDK

O exemplo de código a seguir mostra como criar um token de autenticação para autenticação do IAM.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use a RdsUtilitiesclasse para gerar um token de autenticação.

```
public class GenerateRDSAuthToken {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <masterUsername>
```

```
                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
                    masterUsername - The master user name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        String masterUsername = args[1];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        String token = getAuthToken(rdsClient, dbInstanceIdentifier,
masterUsername);
        System.out.println("The token response is " + token);
    }

    public static String getAuthToken(RdsClient rdsClient, String
dbInstanceIdentifier, String masterUsername) {

        RdsUtilities utilities = rdsClient.utilities();
        try {
            GenerateAuthenticationTokenRequest tokenRequest =
GenerateAuthenticationTokenRequest.builder()
                    .credentialsProvider(ProfileCredentialsProvider.create())
                    .username(masterUsername)
                    .port(3306)
                    .hostname(dbInstanceIdentifier)
                    .build();

            return utilities.generateAuthenticationToken(tokenRequest);

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }
```

```
}
```

- Para obter detalhes da API, consulte GenerateRds AuthToken na Referência AWS SDK for Java 2.x da API.

Excluir uma instância de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma instância de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
/// <summary>
/// Delete a particular DB instance.
/// </summary>
/// <param name="dbInstanceIdentifier">DB instance identifier.</param>
/// <returns>DB instance object.</returns>
public async Task<DBInstance> DeleteDBInstance(string dbInstanceIdentifier)
{
    var response = await _amazonRDS.DeleteDBInstanceAsync(
        new DeleteDBInstanceRequest()
        {
            DBInstanceIdentifier = dbInstanceIdentifier,
            SkipFinalSnapshot = true,
            DeleteAutomatedBackups = true
```

```
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
```

```
                            << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como excluir uma instância de banco de dados

O exemplo de `delete-db-instance` a seguir exclui a instância de banco de dados especificada depois de criar um snapshot de banco de dados final chamado `test-instance-final-snap`.

```
aws rds delete-db-instance \
    --db-instance-identifier test-instance \
    --final-db-snapshot-identifier test-instance-final-snap
```

Saída:

```
{
    "DBInstance": {
        "DBInstanceIdentifier": "test-instance",
        "DBInstanceStatus": "deleting",
        ...some output truncated...
    }
}
```

- Para obter detalhes da API, consulte DeleteDBInstance na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// DeleteInstance deletes a DB instance.
func (instances *DbInstances) DeleteInstance(instanceName string) error {
 _, err := instances.RdsClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier>\s

                Where:
                    dbInstanceIdentifier - The database instance identifier\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
```

```
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        rdsClient.close();
    }

    public static void deleteDatabaseInstance(RdsClient rdsClient, String
 dbInstanceIdentifier) {
        try {
            DeleteDbInstanceRequest deleteDbInstanceRequest =
 DeleteDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .deleteAutomatedBackups(true)
                    .skipFinalSnapshot(true)
                    .build();

            DeleteDbInstanceResponse response =
 rdsClient.deleteDBInstance(deleteDbInstanceRequest);
            System.out.print("The status of the database is " +
 response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDatabaseInstance(dbInstanceIdentifierVal: String?) {

    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;


//Create an RDSClient
$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-1'
]);

$dbIdentifier = '<<{{db-identifier}}>>';

try {
    $result = $rdsClient->deleteDBInstance([
        'DBInstanceIdentifier' => $dbIdentifier,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
```

```
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Python (Boto3).

Excluir um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a DB parameter group. The group cannot be a default DB parameter
group
    /// or be associated with any DB instances.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDBParameterGroup(string name)
    {
        var response = await _amazonRDS.DeleteDBParameterGroupAsync(
            new DeleteDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for .NET Referência da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::DeleteDBParameterGroupRequest request;
    request.SetDBParameterGroupName(parameterGroupName);

    Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
            client.DeleteDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully deleted."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        result = false;
    }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for C++ Referência da API.

CLI

AWS CLI

Como excluir um grupo de parâmetros de banco de dados

O exemplo de `commmand` a seguir exclui um grupo de parâmetros de banco de dados.

```
aws rds delete-db-parameter-group \
    --db-parameter-group-name mydbparametergroup
```

Este comando não produz saída.

Para obter mais informações, consulte Como trabalhar com grupos de parâmetros de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS CLI Referência de Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// DeleteParameterGroup deletes the named DB parameter group.
func (instances *DbInstances) DeleteParameterGroup(parameterGroupName string)
 error {
 _, err := instances.RdsClient.DeleteDBParameterGroup(context.TODO(),
  &rds.DeleteDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
```

```
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for Go Referência da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Delete the parameter group after database has been deleted.
   // An exception is thrown if you attempt to delete the para group while
database
   // exists.
   public static void deleteParaGroup(RdsClient rdsClient, String dbGroupName,
String dbARN)
           throws InterruptedException {
       try {
           boolean isDataDel = false;
           boolean didFind;
           String instanceARN;

           // Make sure that the database has been deleted.
           while (!isDataDel) {
               DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
               List<DBInstance> instanceList = response.dbInstances();
```

```
                int listSize = instanceList.size();
                didFind = false;
                int index = 1;
                for (DBInstance instance : instanceList) {
                    instanceARN = instance.dbInstanceArn();
                    if (instanceARN.compareTo(dbARN) == 0) {
                        System.out.println(dbARN + " still exists");
                        didFind = true;
                    }
                    if ((index == listSize) && (!didFind)) {
                        // Went through the entire list and did not find the
database ARN.
                        isDataDel = true;
                    }
                    Thread.sleep(sleepTime * 1000);
                    index++;
                }
            }

            // Delete the para group.
            DeleteDbParameterGroupRequest parameterGroupRequest =
DeleteDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .build();

            rdsClient.deleteDBParameterGroup(parameterGroupRequest);
            System.out.println(dbGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for Java 2.x Referência da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            self.rds_client.delete_db_parameter_group(
                DBParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
```

```
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte Referência da API DeleteDB ParameterGroup no AWSSDK for Python (Boto3).

Descrever as instâncias de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever instâncias de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Returns a list of DB instances.
   /// </summary>
   /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
   /// <returns>List of DB instances.</returns>
   public async Task<List<DBInstance>> DescribeDBInstances(string
dbInstanceIdentifier = null)
```

```
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
```

```
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como descrever uma instância de banco de dados

O exemplo de `describe-db-instances` a seguir recupera detalhes sobre a instância de banco de dados especificada.

```
aws rds describe-db-instances \
    --db-instance-identifier mydbinstancecf
```

Saída:

```
{
    "DBInstances": [
        {
            "DBInstanceIdentifier": "mydbinstancecf",
            "DBInstanceClass": "db.t3.small",
            "Engine": "mysql",
            "DBInstanceStatus": "available",
            "MasterUsername": "masterawsuser",
            "Endpoint": {
                "Address": "mydbinstancecf.abcexample.us-
east-1.rds.amazonaws.com",
                "Port": 3306,
                "HostedZoneId": "Z2R2ITUGPM61AM"
            },
            ...some output truncated...
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeDBInstances na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetInstance gets data about a DB instance.
func (instances *DbInstances) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.RdsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeDBInstances {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeInstances(rdsClient);
        rdsClient.close();
    }

    public static void describeInstances(RdsClient rdsClient) {
        try {
            DescribeDbInstancesResponse response =
 rdsClient.describeDBInstances();
            List<DBInstance> instanceList = response.dbInstances();
            for (DBInstance instance : instanceList) {
                System.out.println("Instance ARN is: " +
 instance.dbInstanceArn());
                System.out.println("The Engine is " + instance.engine());
                System.out.println("Connection endpoint is" +
 instance.endpoint().address());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeInstances() {

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbInstances(DescribeDbInstancesRequest
 {})
        response.dbInstances?.forEach { instance ->
            println("Instance Identifier is ${instance.dbInstanceIdentifier}")
            println("The Engine is ${instance.engine}")
            println("Connection endpoint is ${instance.endpoint?.address}")
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;


//Create an RDSClient
$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

try {
    $result = $rdsClient->describeDBInstances();
    foreach ($result['DBInstances'] as $instance) {
        print('<p>DB Identifier: ' . $instance['DBInstanceIdentifier']);
        print('<br />Endpoint: ' . $instance['Endpoint']["Address"]
            . ':' . $instance['Endpoint']["Port"]);
        print('<br />Current Status: ' . $instance["DBInstanceStatus"]);
        print('</p>');
    }
    print(" Raw Result ");
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
```

```
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) DB instances.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all DB instances, or nil if error.
def list_instances(rds_resource)
  db_instances = []
  rds_resource.db_instances.each do |i|
    db_instances.append({
                          "name": i.id,
                          "status": i.db_instance_status
                        })
  end
```

```
  db_instances
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list instances:\n#{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Ruby.

Descrever os grupos de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever um grupo de parâmetros de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get descriptions of DB parameter groups.
    /// </summary>
    /// <param name="name">Optional name of the DB parameter group to describe.</
param>
    /// <returns>The list of DB parameter group descriptions.</returns>
    public async Task<List<DBParameterGroup>> DescribeDBParameterGroups(string
 name = null)
    {
```

```
        var response = await _amazonRDS.DescribeDBParameterGroupsAsync(
            new DescribeDBParameterGroupsRequest()
            {
                DBParameterGroupName = name
            });
        return response.DBParameterGroups;
    }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
        }
```

```
        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como descrever um grupo de parâmetros de banco de dados

O exemplo de `describe-db-parameter-groups` a seguir recupera detalhes sobre os grupos de parâmetros de banco de dados.

```
aws rds describe-db-parameter-groups
```

Saída:

```
{
    "DBParameterGroups": [
        {
            "DBParameterGroupName": "default.aurora-mysql5.7",
            "DBParameterGroupFamily": "aurora-mysql5.7",
            "Description": "Default parameter group for aurora-mysql5.7",
            "DBParameterGroupArn": "arn:aws:rds:us-
east-1:123456789012:pg:default.aurora-mysql5.7"
        },
        {
            "DBParameterGroupName": "default.aurora-postgresql9.6",
            "DBParameterGroupFamily": "aurora-postgresql9.6",
            "Description": "Default parameter group for aurora-postgresql9.6",
            "DBParameterGroupArn": "arn:aws:rds:us-
east-1:123456789012:pg:default.aurora-postgresql9.6"
        },
        {
```

```
            "DBParameterGroupName": "default.aurora5.6",
            "DBParameterGroupFamily": "aurora5.6",
            "Description": "Default parameter group for aurora5.6",
            "DBParameterGroupArn": "arn:aws:rds:us-
east-1:123456789012:pg:default.aurora5.6"
        },
        {
            "DBParameterGroupName": "default.mariadb10.1",
            "DBParameterGroupFamily": "mariadb10.1",
            "Description": "Default parameter group for mariadb10.1",
            "DBParameterGroupArn": "arn:aws:rds:us-
east-1:123456789012:pg:default.mariadb10.1"
        },
        ...some output truncated...
    ]
}
```

Para obter mais informações, consulte Como trabalhar com grupos de parâmetros de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte DescribeDB ParameterGroups na Referência de AWS CLIComandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetParameterGroup gets a DB parameter group by name.
func (instances *DbInstances) GetParameterGroup(parameterGroupName string) (
```

```
 *types.DBParameterGroup, error) {
 output, err := instances.RdsClient.DescribeDBParameterGroups(
  context.TODO(), &rds.DescribeDBParameterGroupsInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBParameterGroups[0], err
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbParameterGroups(RdsClient rdsClient, String
dbGroupName) {
       try {
           DescribeDbParameterGroupsRequest groupsRequest =
DescribeDbParameterGroupsRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .maxRecords(20)
```

```
                    .build();

            DescribeDbParameterGroupsResponse response =
 rdsClient.describeDBParameterGroups(groupsRequest);
            List<DBParameterGroup> groups = response.dbParameterGroups();
            for (DBParameterGroup group : groups) {
                System.out.println("The group name is " +
 group.dbParameterGroupName());
                System.out.println("The group description is " +
 group.description());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client
```

```
    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The parameter group.
        """
        try:
            response = self.rds_client.describe_db_parameter_groups(
                DBParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups na Referência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) parameter groups.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all parameter groups, or nil if error.
def list_parameter_groups(rds_resource)
  parameter_groups = []
  rds_resource.db_parameter_groups.each do |p|
    parameter_groups.append({
                              "name": p.db_parameter_group_name,
                              "description": p.description
                            })
  end
  parameter_groups
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list parameter groups:\n #{e.message}"
end
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Ruby da API.

Descrever as versões do mecanismo de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="dbParameterGroupFamily">Optional parameter group family
name.</param>
    /// <returns>List of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>> DescribeDBEngineVersions(string
engine,
        string dbParameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = dbParameterGroupFamily
            });
        return response.DBEngineVersions;
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);
```

```
    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como descrever as versões do mecanismo de banco de dados do mecanismo de banco de dados do MySQL

O exemplo de `describe-db-engine-versions` a seguir exibe os detalhes de cada uma das versões do mecanismo de banco de dados para o mecanismo de banco de dados especificado.

```
aws rds describe-db-engine-versions \
    --engine mysql
```

Saída:

```
{
    "DBEngineVersions": [
        {
            "Engine": "mysql",
            "EngineVersion": "5.5.46",
            "DBParameterGroupFamily": "mysql5.5",
            "DBEngineDescription": "MySQL Community Edition",
            "DBEngineVersionDescription": "MySQL 5.5.46",
            "ValidUpgradeTarget": [
                {
```

```
                "Engine": "mysql",
                "EngineVersion": "5.5.53",
                "Description": "MySQL 5.5.53",
                "AutoUpgrade": false,
                "IsMajorVersionUpgrade": false
            },
            {
                "Engine": "mysql",
                "EngineVersion": "5.5.54",
                "Description": "MySQL 5.5.54",
                "AutoUpgrade": false,
                "IsMajorVersionUpgrade": false
            },
            {
                "Engine": "mysql",
                "EngineVersion": "5.5.57",
                "Description": "MySQL 5.5.57",
                "AutoUpgrade": false,
                "IsMajorVersionUpgrade": false
            },
            ...some output truncated...
        ]
    }
```

Para obter mais informações sobre o Amazon RDS, consulte O que é o Amazon Relational Database Service (Amazon RDS)? no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte DescribeDB EngineVersions na Referência de AWS CLIComandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
```

```
 RdsClient *rds.Client
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (instances *DbInstances) GetEngineVersions(engine string,
 parameterGroupFamily string) (
 []types.DBEngineVersion, error) {
 output, err := instances.RdsClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeDBEngines(RdsClient rdsClient) {
        try {
```

```
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .defaultOnly(true)
                    .engine("mysql")
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
engineOb.engine());
                System.out.println("The version number of the database engine " +
engineOb.engineVersion());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned
 list of
                                       engine versions to those that are
 compatible with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return versions
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na Referência da API AWSSDK for Python (Boto3).

Descrever as opções de instâncias de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever instâncias de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
```

```
    public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptions(string engine, string engineVersion)
    {
        // Use a paginator to get a list of DB instance options.
        var results = new List<OrderableDBInstanceOption>();
        var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
            new DescribeOrderableDBInstanceOptionsRequest()
            {
                Engine = engine,
                EngineVersion = engineVersion,
            });
        // Get the entire list using the paginator.
        await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
        {
            results.Add(instanceOptions);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for .NET API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);
```

```
//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption>
 &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option:
 options) {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
```

```
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available micro DB instance classes for your database
 engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for C++ API.

CLI

AWS CLI

Como descrever as opções de instância solicitável do banco de dados

O exemplo de `describe-orderable-db-instance-options` a seguir recupera detalhes sobre as opções que podem ser solicitadas em uma instância de banco de dados que executa o mecanismo de banco de dados do MySQL.

```
aws rds describe-orderable-db-instance-options \
    --engine mysql
```

Saída:

```
{
    "OrderableDBInstanceOptions": [
        {
            "MinStorageSize": 5,
            "ReadReplicaCapable": true,
            "MaxStorageSize": 6144,
            "AvailabilityZones": [
                {
                    "Name": "us-east-1a"
                },
                {
                    "Name": "us-east-1b"
                },
                {
                    "Name": "us-east-1c"
                },
                {
                    "Name": "us-east-1d"
                }
            ],
            "SupportsIops": false,
            "AvailableProcessorFeatures": [],
            "MultiAZCapable": true,
            "DBInstanceClass": "db.m1.large",
            "Vpc": true,
            "StorageType": "gp2",
            "LicenseModel": "general-public-license",
            "EngineVersion": "5.5.46",
            "SupportsStorageEncryption": false,
            "SupportsEnhancedMonitoring": true,
            "Engine": "mysql",
            "SupportsIAMDatabaseAuthentication": false,
            "SupportsPerformanceInsights": false
        }
    ]
    ...some output truncated...
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em AWS CLICommand Reference.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (instances *DbInstances) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instanceOptions []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(instances.RdsClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instance options: %v\n", err)
   break
  } else {
   instanceOptions = append(instanceOptions,
 output.OrderableDBInstanceOptions...)
  }
```

```
 }
 return instanceOptions, err
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Go API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
   public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
       try {
           DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .engine("mysql")
                   .build();

           DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
           List<DBEngineVersion> dbEngines = response.dbEngineVersions();
           for (DBEngineVersion dbEngine : dbEngines) {
               System.out.println("The engine version is " +
dbEngine.engineVersion());
               System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
           }

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Java 2.x API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.
```

```
        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by
the DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts
```

- Para obter detalhes da API, consulte DescribeOrderableReferência da API DB InstanceOptions in AWSSDK for Python (Boto3).

Descrever os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of DB parameters from a specific parameter group.
    /// </summary>
    /// <param name="dbParameterGroupName">Name of a specific DB parameter
group.</param>
    /// <param name="source">Optional source for selecting parameters.</param>
    /// <returns>List of parameter values.</returns>
    public async Task<List<Parameter>> DescribeDBParameters(string
dbParameterGroupName, string source = null)
    {
        var results = new List<Parameter>();
        var paginateParameters = _amazonRDS.Paginators.DescribeDBParameters(
            new DescribeDBParametersRequest()
            {
                DBParameterGroupName = dbParameterGroupName,
                Source = source
            });
        // Get the entire list using the paginator.
        await foreach (var parameters in paginateParameters.Parameters)
        {
            results.Add(parameters);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
                                  const Aws::String &namePrefix,
                                  const Aws::String &source,
                                  Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                  const Aws::RDS::RDSClient &client) {
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeDBParametersRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
```

```
        }

        Aws::RDS::Model::DescribeDBParametersOutcome outcome =
                client.DescribeDBParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Como descrever os parâmetros de um grupo de parâmetros de banco de dados

O exemplo de `describe-db-parameters` a seguir recupera detalhes sobre o grupo de parâmetros de banco de dados especificado.

```
aws rds describe-db-parameters \
    --db-parameter-group-name mydbpg
```

Saída:

```
{
    "Parameters": [
        {
            "ParameterName": "allow-suspicious-udfs",
            "Description": "Controls whether user-defined functions that have
 only an xxx symbol for the main function can be loaded",
            "Source": "engine-default",
            "ApplyType": "static",
            "DataType": "boolean",
            "AllowedValues": "0,1",
            "IsModifiable": false,
            "ApplyMethod": "pending-reboot"
        },
        {
            "ParameterName": "auto_generate_certs",
            "Description": "Controls whether the server autogenerates SSL key and
 certificate files in the data directory, if they do not already exist.",
            "Source": "engine-default",
            "ApplyType": "static",
            "DataType": "boolean",
            "AllowedValues": "0,1",
            "IsModifiable": false,
            "ApplyMethod": "pending-reboot"
        },
        ...some output truncated...
    ]
}
```

Para obter mais informações, consulte Como trabalhar com grupos de parâmetros de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte DescribeDBParameters na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetParameters gets the parameters that are contained in a DB parameter group.
func (instances *DbInstances) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator := rds.NewDescribeDBParametersPaginator(instances.RdsClient,
  &rds.DescribeDBParametersInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Source:               aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get parameters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Retrieve parameters in the group.
   public static void describeDbParameters(RdsClient rdsClient, String
dbGroupName, int flag) {
       try {
           DescribeDbParametersRequest dbParameterGroupsRequest;
           if (flag == 0) {
               dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                       .dbParameterGroupName(dbGroupName)
                       .build();
           } else {
               dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                       .dbParameterGroupName(dbGroupName)
                       .source("user")
                       .build();
           }

           DescribeDbParametersResponse response =
rdsClient.describeDBParameters(dbParameterGroupsRequest);
           List<Parameter> dbParameters = response.parameters();
           String paraName;
           for (Parameter para : dbParameters) {
               // Only print out information about either auto_increment_offset
or
               // auto_increment_increment.
               paraName = para.parameterName();
               if ((paraName.compareTo("auto_increment_offset") == 0)
```

```
                        || (paraName.compareTo("auto_increment_increment ") ==
 0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
 para.parameterValue());
                    System.out.println("*** The parameter data type is " +
 para.dataType());
                    System.out.println("*** The parameter description is " +
 para.description());
                    System.out.println("*** The parameter allowed values  is " +
 para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Java 2.x.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
```

```
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this
prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator = self.rds_client.get_paginator("describe_db_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) parameter groups.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all parameter groups, or nil if error.
def list_parameter_groups(rds_resource)
  parameter_groups = []
  rds_resource.db_parameter_groups.each do |p|
    parameter_groups.append({
                              "name": p.db_parameter_group_name,
                              "description": p.description
                            })
  end
  parameter_groups
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list parameter groups:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Ruby.

Descrever os snapshots de instâncias de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como descrever snapshots de instâncias de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Return a list of DB snapshots for a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBSnapshot>> DescribeDBSnapshots(string
dbInstanceIdentifier)
    {
        var results = new List<DBSnapshot>();
        var snapshotsPaginator = _amazonRDS.Paginators.DescribeDBSnapshots(
            new DescribeDBSnapshotsRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
```

```
        // Get the entire list using the paginator.
        await foreach (var snapshots in snapshotsPaginator.DBSnapshots)
        {
            results.Add(snapshots);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
```

```
                            << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
                return false;
            }
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Exemplo 1: como descrever um snapshot de banco de dados de uma instância de banco de dados

O exemplo de `describe-db-snapshots` a seguir recupera os detalhes de um snapshot de banco de dados para uma instância de banco de dados.

```
aws rds describe-db-snapshots \
    --db-snapshot-identifier mydbsnapshot
```

Saída:

```
{
    "DBSnapshots": [
        {
            "DBSnapshotIdentifier": "mydbsnapshot",
            "DBInstanceIdentifier": "mysqldb",
            "SnapshotCreateTime": "2018-02-08T22:28:08.598Z",
            "Engine": "mysql",
            "AllocatedStorage": 20,
            "Status": "available",
            "Port": 3306,
            "AvailabilityZone": "us-east-1f",
            "VpcId": "vpc-6594f31c",
            "InstanceCreateTime": "2018-02-08T22:24:55.973Z",
            "MasterUsername": "mysqladmin",
            "EngineVersion": "5.6.37",
            "LicenseModel": "general-public-license",
```

```
            "SnapshotType": "manual",
            "OptionGroupName": "default:mysql-5-6",
            "PercentProgress": 100,
            "StorageType": "gp2",
            "Encrypted": false,
            "DBSnapshotArn": "arn:aws:rds:us-
east-1:123456789012:snapshot:mydbsnapshot",
            "IAMDatabaseAuthenticationEnabled": false,
            "ProcessorFeatures": [],
            "DbiResourceId": "db-AKIAIOSFODNN7EXAMPLE"
        }
    ]
}
```

Para obter mais informações, consulte Criar um snapshot de banco de dados no Guia do usuário do Amazon RDS.

Exemplo 2: como encontrar o número de snapshots manuais criados

O exemplo de `describe-db-snapshots` a seguir usa o operador `length` na opção `--query` para retornar o número de snapshots manuais que foram criados em uma determinada região da AWS.

```
aws rds describe-db-snapshots \
    --snapshot-type manual \
    --query "length(*[].{DBSnapshots:SnapshotType})" \
    --region eu-central-1
```

Saída:

```
35
```

Para obter mais informações, consulte Criar um snapshot de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte DescribeDBSnapshots na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetSnapshot gets a DB instance snapshot.
func (instances *DbInstances) GetSnapshot(snapshotName string)
 (*types.DBSnapshot, error) {
 output, err := instances.RdsClient.DescribeDBSnapshots(context.TODO(),
  &rds.DescribeDBSnapshotsInput{
   DBSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBSnapshots[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for Go.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_snapshot(self, snapshot_id):
        """
        Gets a DB instance snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_snapshots(
                DBSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBSnapshots"][0]
        except ClientError as err:
            logger.error(
```

```
                "Couldn't get snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na referência da API do AWS SDK para Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds" # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) DB instance
# snapshots.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return instance_snapshots [Array, nil] All instance snapshots, or nil if
 error.
def list_instance_snapshots(rds_resource)
  instance_snapshots = []
  rds_resource.db_snapshots.each do |s|
    instance_snapshots.append({
                                "id": s.snapshot_id,
                                "status": s.status
                              })
  end
  instance_snapshots
```

```
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list instance snapshots:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for Ruby.

Modificar uma instância de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como modificar uma instância de banco de dados do Amazon RDS.

CLI

AWS CLI

Como modificar uma instância de banco de dados

O exemplo de `modify-db-instance` a seguir associa um grupo de opção e um grupo de parâmetros a uma instância de banco de dados do Microsoft SQL Server compatível. O parâmetro `--apply-immediately` faz com que os grupos de opção e parâmetro sejam associados imediatamente em vez de ter que esperar a próxima janela de manutenção.

```
aws rds modify-db-instance \
    --db-instance-identifier database-2 \
    --option-group-name test-se-2017 \
    --db-parameter-group-name test-sqlserver-se-2017 \
    --apply-immediately
```

Saída:

```
{
    "DBInstance": {
        "DBInstanceIdentifier": "database-2",
        "DBInstanceClass": "db.r4.large",
        "Engine": "sqlserver-se",
        "DBInstanceStatus": "available",
```

```
        ...output omitted...

        "DBParameterGroups": [
            {
                "DBParameterGroupName": "test-sqlserver-se-2017",
                "ParameterApplyStatus": "applying"
            }
        ],
        "AvailabilityZone": "us-west-2d",

        ...output omitted...

        "MultiAZ": true,
        "EngineVersion": "14.00.3281.6.v1",
        "AutoMinorVersionUpgrade": false,
        "ReadReplicaDBInstanceIdentifiers": [],
        "LicenseModel": "license-included",
        "OptionGroupMemberships": [
            {
                "OptionGroupName": "test-se-2017",
                "Status": "pending-apply"
            }
        ],
        "CharacterSetName": "SQL_Latin1_General_CP1_CI_AS",
        "SecondaryAvailabilityZone": "us-west-2c",
        "PubliclyAccessible": true,
        "StorageType": "gp2",

        ...output omitted...

        "DeletionProtection": false,
        "AssociatedRoles": [],
        "MaxAllocatedStorage": 1000
    }
}
```

Para obter mais informações, consulte Modificar uma instância de banco de dados do Amazon RDS no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte ModifyDBInstance na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.ModifyDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.ModifyDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ModifyDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <dbSnapshotIdentifier>\s
                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
                    masterUserPassword - The updated password that corresponds to
 the master user name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String dbInstanceIdentifier = args[0];
        String masterUserPassword = args[1];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        updateIntance(rdsClient, dbInstanceIdentifier, masterUserPassword);
        rdsClient.close();
    }

    public static void updateIntance(RdsClient rdsClient, String
 dbInstanceIdentifier, String masterUserPassword) {
        try {
            // For a demo - modify the DB instance by modifying the master
 password.
            ModifyDbInstanceRequest modifyDbInstanceRequest =
 ModifyDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .publiclyAccessible(true)
                    .masterUserPassword(masterUserPassword)
                    .build();

            ModifyDbInstanceResponse instanceResponse =
 rdsClient.modifyDBInstance(modifyDbInstanceRequest);
            System.out.print("The ARN of the modified database is: " +
 instanceResponse.dbInstance().dbInstanceArn());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte ModifyDBInstance na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateIntance(dbInstanceIdentifierVal: String?,
 masterUserPasswordVal: String?) {

    val request = ModifyDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        publiclyAccessible = true
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val instanceResponse = rdsClient.modifyDbInstance(request)
        println("The ARN of the modified database is
 ${instanceResponse.dbInstance?.dbInstanceArn}")
    }
}
```

- Para ter detalhes da API, consulte ModifyDBInstance na Referência da API do AWS SDK para Kotlin.

Reinicializar uma instância de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como reinicializar uma instância de banco de dados do Amazon RDS.

CLI

AWS CLI

Como reinicializar uma instância de banco de dados

O exemplo de `reboot-db-instance` a seguir inicia uma reinicialização da instância de banco de dados especificada.

```
aws rds reboot-db-instance \
    --db-instance-identifier test-mysql-instance
```

Saída:

```
{
    "DBInstance": {
        "DBInstanceIdentifier": "test-mysql-instance",
        "DBInstanceClass": "db.t3.micro",
        "Engine": "mysql",
        "DBInstanceStatus": "rebooting",
        "MasterUsername": "admin",
        "Endpoint": {
            "Address": "test-mysql-instance.############.us-
west-2.rds.amazonaws.com",
            "Port": 3306,
            "HostedZoneId": "Z1PVIF0EXAMPLE"
        },

    ... output omitted...

    }
}
```

Para obter mais informações, consulte Reinicializar uma instância de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte RebootDBInstance na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.RebootDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.RebootDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class RebootDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier>\s

                Where:
                    dbInstanceIdentifier - The database instance identifier\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        rebootInstance(rdsClient, dbInstanceIdentifier);
        rdsClient.close();
    }

    public static void rebootInstance(RdsClient rdsClient, String
 dbInstanceIdentifier) {
```

```
        try {
            RebootDbInstanceRequest rebootDbInstanceRequest =
 RebootDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            RebootDbInstanceResponse instanceResponse =
 rdsClient.rebootDBInstance(rebootDbInstanceRequest);
            System.out.print("The database " +
 instanceResponse.dbInstance().dbInstanceArn() + " was rebooted");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte RebootDBInstance na Referência da API do AWS SDK for Java 2.x.

Recuperar atributos que pertencem a uma conta do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como recuperar atributos que pertencem a uma conta do Amazon RDS.

CLI

AWS CLI

Como descrever os atributos da conta

O exemplo de `describe-account-attributes` a seguir recupera os atributos da conta da AWS atual.

```
aws rds describe-account-attributes
```

Saída:

```
{
    "AccountQuotas": [
        {
            "Max": 40,
            "Used": 4,
            "AccountQuotaName": "DBInstances"
        },
        {
            "Max": 40,
            "Used": 0,
            "AccountQuotaName": "ReservedDBInstances"
        },
        {
            "Max": 100000,
            "Used": 40,
            "AccountQuotaName": "AllocatedStorage"
        },
        {
            "Max": 25,
            "Used": 0,
            "AccountQuotaName": "DBSecurityGroups"
        },
        {
            "Max": 20,
            "Used": 0,
            "AccountQuotaName": "AuthorizationsPerDBSecurityGroup"
        },
        {
            "Max": 50,
            "Used": 1,
            "AccountQuotaName": "DBParameterGroups"
        },
        {
            "Max": 100,
            "Used": 3,
            "AccountQuotaName": "ManualSnapshots"
        },
        {
            "Max": 20,
            "Used": 0,
            "AccountQuotaName": "EventSubscriptions"
        },
        {
```

```
            "Max": 50,
            "Used": 1,
            "AccountQuotaName": "DBSubnetGroups"
        },
        {
            "Max": 20,
            "Used": 1,
            "AccountQuotaName": "OptionGroups"
        },
        {
            "Max": 20,
            "Used": 6,
            "AccountQuotaName": "SubnetsPerDBSubnetGroup"
        },
        {
            "Max": 5,
            "Used": 0,
            "AccountQuotaName": "ReadReplicasPerMaster"
        },
        {
            "Max": 40,
            "Used": 1,
            "AccountQuotaName": "DBClusters"
        },
        {
            "Max": 50,
            "Used": 0,
            "AccountQuotaName": "DBClusterParameterGroups"
        },
        {
            "Max": 5,
            "Used": 0,
            "AccountQuotaName": "DBClusterRoles"
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeAccountAttributesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.AccountQuota;
import software.amazon.awssdk.services.rds.model.RdsException;
import
 software.amazon.awssdk.services.rds.model.DescribeAccountAttributesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeAccountAttributes {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        getAccountAttributes(rdsClient);
        rdsClient.close();
    }

    public static void getAccountAttributes(RdsClient rdsClient) {
        try {
            DescribeAccountAttributesResponse response =
 rdsClient.describeAccountAttributes();
```

```
            List<AccountQuota> quotasList = response.accountQuotas();
            for (AccountQuota quotas : quotasList) {
                System.out.println("Name is: " + quotas.accountQuotaName());
                System.out.println("Max value is " + quotas.max());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeAccountAttributesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAccountAttributes() {

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeAccountAttributes(DescribeAccountAttributesRequest {})
        response.accountQuotas?.forEach { quotas ->
            val response = response.accountQuotas
            println("Name is: ${quotas.accountQuotaName}")
            println("Max value is ${quotas.max}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAccountAttributesreferência da API AWSSDK for Kotlin.

Atualizar os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar instâncias de banco de dados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update a DB parameter group. Use the action
 DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="parameters">List of parameters. Maximum of 20 per request.</
param>
    /// <returns>The updated DB parameter group name.</returns>
    public async Task<string> ModifyDBParameterGroup(
        string name, List<Parameter> parameters)
    {
        var response = await _amazonRDS.ModifyDBParameterGroupAsync(
            new ModifyDBParameterGroupRequest()
            {
```

```
                DBParameterGroupName = name,
                Parameters = parameters,
            });
        return response.DBParameterGroupName;
    }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::ModifyDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
                client.ModifyDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                      << outcome.GetError().GetMessage()
```

```
                        << std::endl;
        }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como modificar um grupo de parâmetros de banco de dados

O exemplo de `modify-db-parameter-group` a seguir altera o valor do parâmetro `clr enabled` em um grupo de parâmetros de banco de dados. O parâmetro `--apply-immediately` faz com que o grupo de parâmetros de banco de dados seja modificado imediatamente em vez de ter que esperar a próxima janela de manutenção.

```
aws rds modify-db-parameter-group \
    --db-parameter-group-name test-sqlserver-se-2017 \
    --parameters "ParameterName='clr
 enabled',ParameterValue=1,ApplyMethod=immediate"
```

Saída:

```
{
    "DBParameterGroupName": "test-sqlserver-se-2017"
}
```

Para obter mais informações, consulte Modificar parâmetros em um grupo de parâmetros de banco de dados no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência de AWS CLIComandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// UpdateParameters updates parameters in a named DB parameter group.
func (instances *DbInstances) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := instances.RdsClient.ModifyDBParameterGroup(context.TODO(),
  &rds.ModifyDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Parameters:           params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Modify auto_increment_offset and auto_increment_increment parameters.
    public static void modifyDBParas(RdsClient rdsClient, String dbGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
            paraList.add(parameter1);
            ModifyDbParameterGroupRequest groupRequest =
ModifyDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .parameters(paraList)
                    .build();

            ModifyDbParameterGroupResponse response =
rdsClient.modifyDBParameterGroup(groupRequest);
            System.out.println("The parameter group " +
response.dbParameterGroupName() + " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
 Parameters=update_parameters
            )
        except ClientError as err:
```

```
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API ModifyDB ParameterGroup no AWSSDK for Python (Boto3).

Cenários do Amazon RDS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service (Amazon RDS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Começar a usar instâncias de banco de dados do Amazon RDS usando um AWS SDK

Começar a usar instâncias de banco de dados do Amazon RDS usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Scenario for RDS DB instance example.
/// </summary>
public class RDSInstanceScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks:
    1.  Returns a list of the available DB engine families using the
 DescribeDBEngineVersionsAsync method.
    2.  Selects an engine family and creates a custom DB parameter group using
 the CreateDBParameterGroupAsync method.
    3.  Gets the parameter groups using the DescribeDBParameterGroupsAsync
 method.
    4.  Gets parameters in the group using the DescribeDBParameters method.
    5.  Parses and displays parameters in the group.
    6.  Modifies both the auto_increment_offset and auto_increment_increment
 parameters
        using the ModifyDBParameterGroupAsync method.
    7.  Gets and displays the updated parameters using the DescribeDBParameters
 method with a source of "user".
    8.  Gets a list of allowed engine versions using the
 DescribeDBEngineVersionsAsync method.
    9.  Displays and selects from a list of micro instance classes available for
 the selected engine and version.
    10. Creates an RDS DB instance that contains a MySql database and uses the
 parameter group
        using the CreateDBInstanceAsync method.
```

```
   11. Waits for DB instance to be ready using the DescribeDBInstancesAsync
method.
   12. Prints out the connection endpoint string for the new DB instance.
   13. Creates a snapshot of the DB instance using the CreateDBSnapshotAsync
method.
   14. Waits for DB snapshot to be ready using the DescribeDBSnapshots method.
   15. Deletes the DB instance using the DeleteDBInstanceAsync method.
   16. Waits for DB instance to be deleted using the DescribeDbInstances method.
   17. Deletes the parameter group using the DeleteDBParameterGroupAsync.
   */

   private static readonly string sepBar = new('-', 80);
   private static RDSWrapper rdsWrapper = null!;
   private static ILogger logger = null!;
   private static readonly string engine = "mysql";
   static async Task Main(string[] args)
   {
       // Set up dependency injection for the Amazon RDS service.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
           .ConfigureServices((_, services) =>
               services.AddAWSService<IAmazonRDS>()
                   .AddTransient<RDSWrapper>()
           )
           .Build();

       logger = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       }).CreateLogger<RDSInstanceScenario>();

       rdsWrapper = host.Services.GetRequiredService<RDSWrapper>();

       Console.WriteLine(sepBar);
       Console.WriteLine(
           "Welcome to the Amazon Relational Database Service (Amazon RDS) DB
instance scenario example.");
       Console.WriteLine(sepBar);
```

```
        try
        {
            var parameterGroupFamily = await ChooseParameterGroupFamily();

            var parameterGroup = await
CreateDbParameterGroup(parameterGroupFamily);

            var parameters = await
DescribeParametersInGroup(parameterGroup.DBParameterGroupName,
                new List<string> { "auto_increment_offset",
"auto_increment_increment" });

            await ModifyParameters(parameterGroup.DBParameterGroupName,
parameters);

            await
DescribeUserSourceParameters(parameterGroup.DBParameterGroupName);

            var engineVersionChoice = await
ChooseDbEngineVersion(parameterGroupFamily);

            var instanceChoice = await ChooseDbInstanceClass(engine,
engineVersionChoice.EngineVersion);

            var newInstanceIdentifier = "Example-Instance-" + DateTime.Now.Ticks;

            var newInstance = await CreateRdsNewInstance(parameterGroup, engine,
engineVersionChoice.EngineVersion,
                instanceChoice.DBInstanceClass, newInstanceIdentifier);
            if (newInstance != null)
            {
                DisplayConnectionString(newInstance);

                await CreateSnapshot(newInstance);

                await DeleteRdsInstance(newInstance);
            }

            await DeleteParameterGroup(parameterGroup);

            Console.WriteLine("Scenario complete.");
            Console.WriteLine(sepBar);
        }
        catch (Exception ex)
```

```
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// Choose the RDS DB parameter group family from a list of available
options.
    /// </summary>
    /// <returns>The selected parameter group family.</returns>
    public static async Task<string> ChooseParameterGroupFamily()
    {
        Console.WriteLine(sepBar);
        // 1. Get a list of available engines.
        var engines = await rdsWrapper.DescribeDBEngineVersions(engine);

        Console.WriteLine("1. The following is a list of available DB parameter
group families:");
        int i = 1;
        var parameterGroupFamilies = engines.GroupBy(e =>
e.DBParameterGroupFamily).ToList();
        foreach (var parameterGroupFamily in parameterGroupFamilies)
        {
            // List the available parameter group families.
            Console.WriteLine(
                $"\t{i}. Family: {parameterGroupFamily.Key}");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > parameterGroupFamilies.Count)
        {
            Console.WriteLine("Select an available DB parameter group family by
entering a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        var parameterGroupFamilyChoice = parameterGroupFamilies[choiceNumber -
1];
        Console.WriteLine(sepBar);
        return parameterGroupFamilyChoice.Key;
    }

    /// <summary>
```

```
    /// Create and get information on a DB parameter group.
    /// </summary>
    /// <param name="dbParameterGroupFamily">The DBParameterGroupFamily for the
new DB parameter group.</param>
    /// <returns>The new DBParameterGroup.</returns>
    public static async Task<DBParameterGroup> CreateDbParameterGroup(string
dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"2. Create new DB parameter group with family
{dbParameterGroupFamily}:");

        var parameterGroup = await rdsWrapper.CreateDBParameterGroup(
            "ExampleParameterGroup-" + DateTime.Now.Ticks,
            dbParameterGroupFamily, "New example parameter group");

        var groupInfo =
            await rdsWrapper.DescribeDBParameterGroups(parameterGroup
                .DBParameterGroupName);

        Console.WriteLine(
            $"3. New DB parameter group: \n\t{groupInfo[0].Description}, \n\tARN
{groupInfo[0].DBParameterGroupArn}");
        Console.WriteLine(sepBar);
        return parameterGroup;
    }

    /// <summary>
    /// Get and describe parameters from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameterNames">Optional specific names of parameters to
describe.</param>
    /// <returns>The list of requested parameters.</returns>
    public static async Task<List<Parameter>> DescribeParametersInGroup(string
parameterGroupName, List<string>? parameterNames = null)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("4. Get some parameters from the group.");
        Console.WriteLine(sepBar);

        var parameters =
            await rdsWrapper.DescribeDBParameters(parameterGroupName);
```

```
        var matchingParameters =
            parameters.Where(p => parameterNames == null ||
parameterNames.Contains(p.ParameterName)).ToList();

        Console.WriteLine("5. Parameter information:");
        matchingParameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);

        return matchingParameters;
    }

    /// <summary>
    /// Modify a parameter from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameters">The parameters to modify.</param>
    /// <returns>Async task.</returns>
    public static async Task ModifyParameters(string parameterGroupName,
List<Parameter> parameters)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("6. Modify some parameters in the group.");

        foreach (var p in parameters)
        {
            if (p.IsModifiable && p.DataType == "integer")
            {
                int newValue = 0;
                while (newValue == 0)
                {
                    Console.WriteLine(
                        $"Enter a new value for {p.ParameterName} from the
allowed values {p.AllowedValues} ");

                    var choice = Console.ReadLine();
                    Int32.TryParse(choice, out newValue);
                }
```

```
                p.ParameterValue = newValue.ToString();
            }
        }

        await rdsWrapper.ModifyDBParameterGroup(parameterGroupName, parameters);

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Describe the user source parameters in the group.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <returns>Async task.</returns>
    public static async Task DescribeUserSourceParameters(string
parameterGroupName)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("7. Describe user source parameters in the group.");

        var parameters =
            await rdsWrapper.DescribeDBParameters(parameterGroupName, "user");


        parameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);
    }


    /// <summary>
    /// Choose a DB engine version.
    /// </summary>
    /// <param name="dbParameterGroupFamily">DB parameter group family for engine
choice.</param>
    /// <returns>The selected engine version.</returns>
    public static async Task<DBEngineVersion> ChooseDbEngineVersion(string
dbParameterGroupFamily)
    {
```

```
        Console.WriteLine(sepBar);
        // Get a list of allowed engines.
        var allowedEngines =
            await rdsWrapper.DescribeDBEngineVersions(engine,
 dbParameterGroupFamily);

        Console.WriteLine($"Available DB engine versions for parameter group
 family {dbParameterGroupFamily}:");
        int i = 1;
        foreach (var version in allowedEngines)
        {
            Console.WriteLine(
                $"\t{i}. Engine: {version.Engine} Version
 {version.EngineVersion}.");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedEngines.Count)
        {
            Console.WriteLine("8. Select an available DB engine version by
 entering a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var engineChoice = allowedEngines[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return engineChoice;
    }

    /// <summary>
    /// Choose a DB instance class for a particular engine and engine version.
    /// </summary>
    /// <param name="engine">DB engine for DB instance choice.</param>
    /// <param name="engineVersion">DB engine version for DB instance choice.</
param>
    /// <returns>The selected orderable DB instance option.</returns>
    public static async Task<OrderableDBInstanceOption>
 ChooseDbInstanceClass(string engine, string engineVersion)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed DB instance classes.
        var allowedInstances =
```

```
            await rdsWrapper.DescribeOrderableDBInstanceOptions(engine,
 engineVersion);

        Console.WriteLine($"8. Available micro DB instance classes for engine
 {engine} and version {engineVersion}:");
        int i = 1;

        // Filter to micro instances for this example.
        allowedInstances = allowedInstances
            .Where(i => i.DBInstanceClass.Contains("micro")).ToList();

        foreach (var instance in allowedInstances)
        {
            Console.WriteLine(
                $"\t{i}. Instance class: {instance.DBInstanceClass} (storage type
 {instance.StorageType})");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedInstances.Count)
        {
            Console.WriteLine("9. Select an available DB instance class by
 entering a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var instanceChoice = allowedInstances[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return instanceChoice;
    }

    /// <summary>
    /// Create a new RDS DB instance.
    /// </summary>
    /// <param name="parameterGroup">Parameter group to use for the DB
 instance.</param>
    /// <param name="engineName">Engine to use for the DB instance.</param>
    /// <param name="engineVersion">Engine version to use for the DB instance.</
param>
    /// <param name="instanceClass">Instance class to use for the DB instance.</
param>
```

```
   /// <param name="instanceIdentifier">Instance identifier to use for the DB
instance.</param>
   /// <returns>The new DB instance.</returns>
   public static async Task<DBInstance?> CreateRdsNewInstance(DBParameterGroup
parameterGroup,
       string engineName, string engineVersion, string instanceClass, string
instanceIdentifier)
   {
       Console.WriteLine(sepBar);
       Console.WriteLine($"10. Create a new DB instance with identifier
{instanceIdentifier}.");
       bool isInstanceReady = false;
       DBInstance newInstance;
       var instances = await rdsWrapper.DescribeDBInstances();
       isInstanceReady = instances.FirstOrDefault(i =>
           i.DBInstanceIdentifier == instanceIdentifier)?.DBInstanceStatus ==
"available";

       if (isInstanceReady)
       {
           Console.WriteLine("Instance already created.");
           newInstance = instances.First(i => i.DBInstanceIdentifier ==
instanceIdentifier);
       }
       else
       {
           Console.WriteLine("Please enter an admin user name:");
           var username = Console.ReadLine();

           Console.WriteLine("Please enter an admin password:");
           var password = Console.ReadLine();

           newInstance = await rdsWrapper.CreateDBInstance(
               "ExampleInstance",
               instanceIdentifier,
               parameterGroup.DBParameterGroupName,
               engineName,
               engineVersion,
               instanceClass,
               20,
               username,
               password
           );
```

```
            // 11. Wait for the DB instance to be ready.

            Console.WriteLine("11. Waiting for DB instance to be ready...");
            while (!isInstanceReady)
            {
                instances = await
 rdsWrapper.DescribeDBInstances(instanceIdentifier);
                isInstanceReady = instances.FirstOrDefault()?.DBInstanceStatus ==
 "available";
                newInstance = instances.First();
                Thread.Sleep(30000);
            }
        }

        Console.WriteLine(sepBar);
        return newInstance;
    }

    /// <summary>
    /// Display a connection string for an RDS DB instance.
    /// </summary>
    /// <param name="instance">The DB instance to use to get a connection
 string.</param>
    public static void DisplayConnectionString(DBInstance instance)
    {
        Console.WriteLine(sepBar);
        // Display the connection string.
        Console.WriteLine("12. New DB instance connection string: ");
        Console.WriteLine(
            $"\n{engine} -h {instance.Endpoint.Address} -P
 {instance.Endpoint.Port} "
            + $"-u {instance.MasterUsername} -p [YOUR PASSWORD]\n");

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Create a snapshot from an RDS DB instance.
    /// </summary>
    /// <param name="instance">DB instance to use when creating a snapshot.</
param>
    /// <returns>The snapshot object.</returns>
    public static async Task<DBSnapshot> CreateSnapshot(DBInstance instance)
    {
```

```
        Console.WriteLine(sepBar);
        // Create a snapshot.
        Console.WriteLine($"13. Creating snapshot from DB instance
{instance.DBInstanceIdentifier}.");
        var snapshot = await
rdsWrapper.CreateDBSnapshot(instance.DBInstanceIdentifier, "ExampleSnapshot-" +
DateTime.Now.Ticks);

        // Wait for the snapshot to be available
        bool isSnapshotReady = false;

        Console.WriteLine($"14. Waiting for snapshot to be ready...");
        while (!isSnapshotReady)
        {
            var snapshots = await
rdsWrapper.DescribeDBSnapshots(instance.DBInstanceIdentifier);
            isSnapshotReady = snapshots.FirstOrDefault()?.Status == "available";
            snapshot = snapshots.First();
            Thread.Sleep(30000);
        }

        Console.WriteLine(
            $"Snapshot {snapshot.DBSnapshotIdentifier} status is
{snapshot.Status}.");
        Console.WriteLine(sepBar);
        return snapshot;
    }

    /// <summary>
    /// Delete an RDS DB instance.
    /// </summary>
    /// <param name="instance">The DB instance to delete.</param>
    /// <returns>Async task.</returns>
    public static async Task DeleteRdsInstance(DBInstance newInstance)
    {
        Console.WriteLine(sepBar);
        // Delete the DB instance.
        Console.WriteLine($"15. Delete the DB instance
{newInstance.DBInstanceIdentifier}.");
        await rdsWrapper.DeleteDBInstance(newInstance.DBInstanceIdentifier);

        // Wait for the DB instance to delete.
        Console.WriteLine($"16. Waiting for the DB instance to delete...");
        bool isInstanceDeleted = false;
```

```
        while (!isInstanceDeleted)
        {
            var instance = await rdsWrapper.DescribeDBInstances();
            isInstanceDeleted = instance.All(i => i.DBInstanceIdentifier !=
 newInstance.DBInstanceIdentifier);
            Thread.Sleep(30000);
        }

        Console.WriteLine("DB instance deleted.");
        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Delete a DB parameter group.
    /// </summary>
    /// <param name="parameterGroup">The parameter group to delete.</param>
    /// <returns>Async task.</returns>
    public static async Task DeleteParameterGroup(DBParameterGroup
 parameterGroup)
    {
        Console.WriteLine(sepBar);
        // Delete the parameter group.
        Console.WriteLine($"17. Delete the DB parameter group
 {parameterGroup.DBParameterGroupName}.");
        await
 rdsWrapper.DeleteDBParameterGroup(parameterGroup.DBParameterGroupName);

        Console.WriteLine(sepBar);
    }
```

Os métodos de wrapper usados pelo cenário para as ações de instância de banco de dados.

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with
 DB instance operations.
/// </summary>
public partial class RDSWrapper
{
    private readonly IAmazonRDS _amazonRDS;
    public RDSWrapper(IAmazonRDS amazonRDS)
```

```
    {
        _amazonRDS = amazonRDS;
    }


    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="dbParameterGroupFamily">Optional parameter group family
name.</param>
    /// <returns>List of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>> DescribeDBEngineVersions(string
engine,
        string dbParameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = dbParameterGroupFamily
            });
        return response.DBEngineVersions;
    }



    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
    public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptions(string engine, string engineVersion)
    {
        // Use a paginator to get a list of DB instance options.
        var results = new List<OrderableDBInstanceOption>();
        var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
            new DescribeOrderableDBInstanceOptionsRequest()
            {
                Engine = engine,
```

```
                EngineVersion = engineVersion,
            });
        // Get the entire list using the paginator.
        await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
        {
            results.Add(instanceOptions);
        }
        return results;
    }



    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstances(string
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }



    /// <summary>
    /// Create an RDS DB instance with a particular set of properties. Use the
action DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbName">Name for the DB instance.</param>
```

```
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="parameterGroupName">DB parameter group to associate with the
instance.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
    /// <param name="allocatedStorage">The amount of storage in gibibytes (GiB)
to allocate to the DB instance.</param>
    /// <param name="adminName">Admin user name.</param>
    /// <param name="adminPassword">Admin user password.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstance(string dbName, string
dbInstanceIdentifier,
        string parameterGroupName, string dbEngine, string dbEngineVersion,
        string instanceClass, int allocatedStorage, string adminName, string
adminPassword)
    {
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBName = dbName,
                DBInstanceIdentifier = dbInstanceIdentifier,
                DBParameterGroupName = parameterGroupName,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass,
                AllocatedStorage = allocatedStorage,
                MasterUsername = adminName,
                MasterUserPassword = adminPassword
            });

        return response.DBInstance;
    }



    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstance(string dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
```

```
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
```

Os métodos de wrapper usados pelo cenário para o grupos de parâmetros de banco de dados

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with
 parameter groups.
/// </summary>
public partial class RDSWrapper
{

    /// <summary>
    /// Get descriptions of DB parameter groups.
    /// </summary>
    /// <param name="name">Optional name of the DB parameter group to describe.</
param>
    /// <returns>The list of DB parameter group descriptions.</returns>
    public async Task<List<DBParameterGroup>> DescribeDBParameterGroups(string
 name = null)
    {
        var response = await _amazonRDS.DescribeDBParameterGroupsAsync(
            new DescribeDBParameterGroupsRequest()
            {
                DBParameterGroupName = name
            });
        return response.DBParameterGroups;
    }



    /// <summary>
```

```
    /// Create a new DB parameter group. Use the action
 DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="family">Family of the DB parameter group.</param>
    /// <param name="description">Description of the DB parameter group.</param>
    /// <returns>The new DB parameter group.</returns>
    public async Task<DBParameterGroup> CreateDBParameterGroup(
        string name, string family, string description)
    {
        var response = await _amazonRDS.CreateDBParameterGroupAsync(
            new CreateDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                DBParameterGroupFamily = family,
                Description = description
            });
        return response.DBParameterGroup;
    }



    /// <summary>
    /// Update a DB parameter group. Use the action
 DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="parameters">List of parameters. Maximum of 20 per request.</
param>
    /// <returns>The updated DB parameter group name.</returns>
    public async Task<string> ModifyDBParameterGroup(
        string name, List<Parameter> parameters)
    {
        var response = await _amazonRDS.ModifyDBParameterGroupAsync(
            new ModifyDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                Parameters = parameters,
            });
        return response.DBParameterGroupName;
    }
```

```
    /// <summary>
    /// Delete a DB parameter group. The group cannot be a default DB parameter
group
    /// or be associated with any DB instances.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDBParameterGroup(string name)
    {
        var response = await _amazonRDS.DeleteDBParameterGroupAsync(
            new DeleteDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }



    /// <summary>
    /// Get a list of DB parameters from a specific parameter group.
    /// </summary>
    /// <param name="dbParameterGroupName">Name of a specific DB parameter
group.</param>
    /// <param name="source">Optional source for selecting parameters.</param>
    /// <returns>List of parameter values.</returns>
    public async Task<List<Parameter>> DescribeDBParameters(string
dbParameterGroupName, string source = null)
    {
        var results = new List<Parameter>();
        var paginateParameters = _amazonRDS.Paginators.DescribeDBParameters(
            new DescribeDBParametersRequest()
            {
                DBParameterGroupName = dbParameterGroupName,
                Source = source
            });
        // Get the entire list using the paginator.
        await foreach (var parameters in paginateParameters.Parameters)
        {
            results.Add(parameters);
        }
        return results;
```

```
    }
```

Os métodos de wrapper usados pelo cenário para as ações de snapshot de banco de dados.

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with
 snapshots.
/// </summary>
public partial class RDSWrapper
{

    /// <summary>
    /// Create a snapshot of a DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBSnapshot> CreateDBSnapshot(string dbInstanceIdentifier,
 string snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBSnapshotAsync(
            new CreateDBSnapshotRequest()
            {
                DBSnapshotIdentifier = snapshotIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        return response.DBSnapshot;
    }



    /// <summary>
    /// Return a list of DB snapshots for a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBSnapshot>> DescribeDBSnapshots(string
 dbInstanceIdentifier)
    {
```

```
        var results = new List<DBSnapshot>();
        var snapshotsPaginator = _amazonRDS.Paginators.DescribeDBSnapshots(
            new DescribeDBSnapshotsRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        // Get the entire list using the paginator.
        await foreach (var snapshots in snapshotsPaginator.DBSnapshots)
        {
            results.Add(snapshots);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon RDS instance and demonstrates several
 operations
//! on that instance.
/*!
 \sa gettingStartedWithDBInstances()
 \param clientConfiguration: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::gettingStartedWithDBInstances(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);

    printAsterisksLine();
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon RDS)"
              << std::endl;
    std::cout << "get started with DB instances demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB parameter group named '" <<
              PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB parameter group already exists.
        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
```

```
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' does not exist." << std::endl;
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!parameterGroupFound) {
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available engine versions for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
        }

        std::cout << "Getting available database engine versions for " <<
 DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family <<
 std::endl;
            }
```

```
        }

        int choice = askQuestionForIntRange("Which family do you want to use? ",
1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB parameter group.
        Aws::RDS::Model::CreateDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example parameter group.");

        Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
                client.CreateDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your parameter group."
              << std::endl;

    Aws::String marker;
    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB parameter group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, AUTO_INCREMENT_PREFIX, NO_SOURCE,
                         autoIncrementParameters,
                         client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;
```

```
    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value in the range ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
                updateParameters.push_back(autoIncParameter);

            }
            else {
                std::cerr << "Error parsing " <<
autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the group.
        Aws::RDS::Model::ModifyDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
                client.ModifyDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully modified."
                      << std::endl;
        }
```

```
        else {
            std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a
source of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, NO_NAME_PREFIX, "user",
userParameters,
                         client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB instance." << std::endl;

    Aws::RDS::Model::DBInstance dbInstance;
    // 7.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
```

```
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters): 
");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of available engine versions.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily, 
engineVersions,
                                 client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "The available engines for your parameter group are:" << 
std::endl;

        int index = 1;
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion: 
engineVersions) {
            std::cout << "  " << index << ": " << 
engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ", 
1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion = 
engineVersions[choice -
                                                                                 1];

        Aws::String dbInstanceClass;
        // 9.  Get a list of micro instance classes.
        if (!chooseMicroDBInstanceClass(engineVersion.GetEngine(),
                                        engineVersion.GetEngineVersion(),
                                        dbInstanceClass,
                                        client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
```

```
                << "The DB instance is configured to use your custom parameter
group '"
                << PARAMETER_GROUP_NAME << "',\n"
                << "selected engine version " <<
engineVersion.GetEngineVersion()
                << ",\n"
                << "selected DB instance class '" << dbInstanceClass << "',"
                << " and " << DB_ALLOCATED_STORAGE << " GiB of " <<
DB_STORAGE_TYPE
                << " storage.\nThis typically takes several minutes." <<
std::endl;

       Aws::RDS::Model::CreateDBInstanceRequest request;
       request.SetDBName(DB_NAME);
       request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
       request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
       request.SetEngine(engineVersion.GetEngine());
       request.SetEngineVersion(engineVersion.GetEngineVersion());
       request.SetDBInstanceClass(dbInstanceClass);
       request.SetStorageType(DB_STORAGE_TYPE);
       request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
       request.SetMasterUsername(administratorName);
       request.SetMasterUserPassword(administratorPassword);

       Aws::RDS::Model::CreateDBInstanceOutcome outcome =
               client.CreateDBInstance(request);

       if (outcome.IsSuccess()) {
           std::cout << "The DB instance creation has started."
                     << std::endl;
       }
       else {
           std::cerr << "Error with RDS::CreateDBInstance. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           cleanUpResources(PARAMETER_GROUP_NAME, "", client);
           return false;
       }
   }

   std::cout << "Waiting for the DB instance to become available." << std::endl;

   int counter = 0;
   // 11. Wait for the DB instance to become available.
```

```
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");

    if (dbInstance.GetDBInstanceStatus() == "available") {
        std::cout << "The DB instance has been created." << std::endl;
    }

    printAsterisksLine();

    // 12. Display the connection string that can be used to connect a 'mysql'
shell to the database.
    displayConnection(dbInstance);

    printAsterisksLine();

    if (askYesNoQuestion(
            "Do you want to create a snapshot of your DB instance (y/n)? ")) {
        Aws::String snapshotID(DB_INSTANCE_IDENTIFIER + "-" +
                               Aws::String(Aws::Utils::UUID::RandomUUID()));
        {
```

```
            std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
            std::cout << "This typically takes a few minutes." << std::endl;

            // 13. Create a snapshot of the DB instance.
            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
        }

        std::cout << "Waiting for snapshot to become available." << std::endl;

        Aws::RDS::Model::DBSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            // 14. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
```

```
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
                return false;
            }

            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");

        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB instance and parameter group (y/n)? "))
 {
        result = cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
    }

    return result;
}


//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
```

```
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
                                  const Aws::String &namePrefix,
                                  const Aws::String &source,
                                  Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                  const Aws::RDS::RDSClient &client) {
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeDBParametersRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBParametersOutcome outcome =
                client.DescribeDBParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
```

```
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
```

```
                  << std::endl;
    }

    return outcome.IsSuccess();
}


//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

```
//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption>
 &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option:
 options) {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
            marker = outcome.GetResult().GetMarker();
```

```
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available micro DB instance classes for your database
 engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
*/
bool AwsDoc::RDS::cleanUpResources(const Aws::String &parameterGroupName,
                                   const Aws::String &dbInstanceIdentifier,
                                   const Aws::RDS::RDSClient &client) {
    bool result = true;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 15. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
```

```
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        std::cout
                << "Waiting for DB instance to delete before deleting the
parameter group."
                << std::endl;
        std::cout << "This may take a while." << std::endl;

        int counter = 0;
        Aws::RDS::Model::DBInstance dbInstance;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 800) {
                std::cerr << "Wait for instance to delete timed out ofter " <<
counter
                          << " seconds." << std::endl;
                return false;
            }

            dbInstance = Aws::RDS::Model::DBInstance();
            // 16. Wait for the DB instance to be deleted.
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }

            if (dbInstance.DBInstanceIdentifierHasBeenSet() && (counter % 20) ==
0) {
                std::cout << "Current DB instance status is '"
                          << dbInstance.GetDBInstanceStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
```

```
        } while (dbInstance.DBInstanceIdentifierHasBeenSet());
    }

    if (!parameterGroupName.empty()) {
        // 17. Delete the parameter group.
        Aws::RDS::Model::DeleteDBParameterGroupRequest request;
        request.SetDBParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
                client.DeleteDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots

- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ParameterGroup

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// GetStartedInstances is an interactive example that shows you how to use the
 AWS SDK for Go
// with Amazon Relation Database Service (Amazon RDS) to do the following:
//
//  1. Create a custom DB parameter group and set parameter values.
//  2. Create a DB instance that is configured to use the parameter group. The DB
 instance
//     also contains a database.
//  3. Take a snapshot of the DB instance.
//  4. Delete the DB instance and parameter group.
type GetStartedInstances struct {
 sdkConfig  aws.Config
 instances  actions.DbInstances
 questioner demotools.IQuestioner
 helper     IScenarioHelper
 isTestRun  bool
}

// NewGetStartedInstances constructs a GetStartedInstances instance from a
 configuration.
// It uses the specified config to get an Amazon RDS
// client and create wrappers for the actions used in the scenario.
func NewGetStartedInstances(sdkConfig aws.Config, questioner
 demotools.IQuestioner,
 helper IScenarioHelper) GetStartedInstances {
```

```
 rdsClient := rds.NewFromConfig(sdkConfig)
 return GetStartedInstances{
  sdkConfig:  sdkConfig,
  instances:  actions.DbInstances{RdsClient: rdsClient},
  questioner: questioner,
  helper:     helper,
 }
}

// Run runs the interactive scenario.
func (scenario GetStartedInstances) Run(dbEngine string, parameterGroupName
 string,
 instanceName string, dbName string) {
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon Relational Database Service (Amazon RDS) DB
 Instance demo.")
 log.Println(strings.Repeat("-", 88))

 parameterGroup := scenario.CreateParameterGroup(dbEngine, parameterGroupName)
 scenario.SetUserParameters(parameterGroupName)
 instance := scenario.CreateInstance(instanceName, dbEngine, dbName,
 parameterGroup)
 scenario.DisplayConnection(instance)
 scenario.CreateSnapshot(instance)
 scenario.Cleanup(instance, parameterGroup)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateParameterGroup shows how to get available engine versions for a
 specified
// database engine and create a DB parameter group that is compatible with a
// selected engine family.
func (scenario GetStartedInstances) CreateParameterGroup(dbEngine string,
 parameterGroupName string) *types.DBParameterGroup {
```

```
 log.Printf("Checking for an existing DB parameter group named %v.\n",
  parameterGroupName)
 parameterGroup, err := scenario.instances.GetParameterGroup(parameterGroupName)
 if err != nil {
  panic(err)
 }
 if parameterGroup == nil {
  log.Printf("Getting available database engine versions for %v.\n", dbEngine)
  engineVersions, err := scenario.instances.GetEngineVersions(dbEngine, "")
  if err != nil {
   panic(err)
  }

  familySet := map[string]struct{}{}
  for _, family := range engineVersions {
   familySet[*family.DBParameterGroupFamily] = struct{}{}
  }
  var families []string
  for family := range familySet {
   families = append(families, family)
  }
  sort.Strings(families)
  familyIndex := scenario.questioner.AskChoice("Which family do you want to use?
\n", families)
  log.Println("Creating a DB parameter group.")
  _, err = scenario.instances.CreateParameterGroup(
   parameterGroupName, families[familyIndex], "Example parameter group.")
  if err != nil {
   panic(err)
  }
  parameterGroup, err = scenario.instances.GetParameterGroup(parameterGroupName)
  if err != nil {
   panic(err)
  }
 }
 log.Printf("Parameter group %v:\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tName: %v\n", *parameterGroup.DBParameterGroupName)
 log.Printf("\tARN: %v\n", *parameterGroup.DBParameterGroupArn)
 log.Printf("\tFamily: %v\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tDescription: %v\n", *parameterGroup.Description)
 log.Println(strings.Repeat("-", 88))
 return parameterGroup
}
```

```
// SetUserParameters shows how to get the parameters contained in a custom
 parameter
// group and update some of the parameter values in the group.
func (scenario GetStartedInstances) SetUserParameters(parameterGroupName string)
 {
 log.Println("Let's set some parameter values in your parameter group.")
 dbParameters, err := scenario.instances.GetParameters(parameterGroupName, "")
 if err != nil {
  panic(err)
 }
 var updateParams []types.Parameter
 for _, dbParam := range dbParameters {
  if strings.HasPrefix(*dbParam.ParameterName, "auto_increment") &&
   dbParam.IsModifiable && *dbParam.DataType == "integer" {
   log.Printf("The %v parameter is described as:\n\t%v",
    *dbParam.ParameterName, *dbParam.Description)
   rangeSplit := strings.Split(*dbParam.AllowedValues, "-")
   lower, _ := strconv.Atoi(rangeSplit[0])
   upper, _ := strconv.Atoi(rangeSplit[1])
   newValue := scenario.questioner.AskInt(
    fmt.Sprintf("Enter a value between %v and %v:", lower, upper),
    demotools.InIntRange{Lower: lower, Upper: upper})
   dbParam.ParameterValue = aws.String(strconv.Itoa(newValue))
   updateParams = append(updateParams, dbParam)
  }
 }
 err = scenario.instances.UpdateParameters(parameterGroupName, updateParams)
 if err != nil {
  panic(err)
 }
 log.Println("To get a list of parameters that you set previously, specify a
 source of 'user'.")
 userParameters, err := scenario.instances.GetParameters(parameterGroupName,
 "user")
 if err != nil {
  panic(err)
 }
 log.Println("Here are the parameters you set:")
 for _, param := range userParameters {
  log.Printf("\t%v: %v\n", *param.ParameterName, *param.ParameterValue)
 }
 log.Println(strings.Repeat("-", 88))
}
```

```
// CreateInstance shows how to create a DB instance that contains a database of a
// specified type. The database is also configured to use a custom DB parameter
 group.
func (scenario GetStartedInstances) CreateInstance(instanceName string, dbEngine
 string,
 dbName string, parameterGroup *types.DBParameterGroup) *types.DBInstance {

 log.Println("Checking for an existing DB instance.")
 instance, err := scenario.instances.GetInstance(instanceName)
 if err != nil {
  panic(err)
 }
 if instance == nil {
  adminUsername := scenario.questioner.Ask(
   "Enter an administrator username for the database: ", demotools.NotEmpty{})
  adminPassword := scenario.questioner.AskPassword(
   "Enter a password for the administrator (at least 8 characters): ", 7)
  engineVersions, err := scenario.instances.GetEngineVersions(dbEngine,
   *parameterGroup.DBParameterGroupFamily)
  if err != nil {
   panic(err)
  }
  var engineChoices []string
  for _, engine := range engineVersions {
   engineChoices = append(engineChoices, *engine.EngineVersion)
  }
  engineIndex := scenario.questioner.AskChoice(
   "The available engines for your parameter group are:\n", engineChoices)
  engineSelection := engineVersions[engineIndex]
  instOpts, err :=
 scenario.instances.GetOrderableInstances(*engineSelection.Engine,
   *engineSelection.EngineVersion)
  if err != nil {
   panic(err)
  }
  optSet := map[string]struct{}{}
  for _, opt := range instOpts {
   if strings.Contains(*opt.DBInstanceClass, "micro") {
    optSet[*opt.DBInstanceClass] = struct{}{}
   }
  }
  var optChoices []string
  for opt := range optSet {
   optChoices = append(optChoices, opt)
```

```
  }
  sort.Strings(optChoices)
  optIndex := scenario.questioner.AskChoice(
   "The available micro DB instance classes for your database engine are:\n",
 optChoices)
  storageType := "standard"
  allocatedStorage := int32(5)
  log.Printf("Creating a DB instance named %v and database %v.\n"+
   "The DB instance is configured to use your custom parameter group %v,\n"+
   "selected engine %v,\n"+
   "selected DB instance class %v,"+
   "and %v GiB of %v storage.\n"+
   "This typically takes several minutes.",
   instanceName, dbName, *parameterGroup.DBParameterGroupName,
 *engineSelection.EngineVersion,
   optChoices[optIndex], allocatedStorage, storageType)
  instance, err = scenario.instances.CreateInstance(
   instanceName, dbName, *engineSelection.Engine, *engineSelection.EngineVersion,
   *parameterGroup.DBParameterGroupName, optChoices[optIndex], storageType,
   allocatedStorage, adminUsername, adminPassword)
  if err != nil {
   panic(err)
  }
  for *instance.DBInstanceStatus != "available" {
   scenario.helper.Pause(30)
   instance, err = scenario.instances.GetInstance(instanceName)
   if err != nil {
    panic(err)
   }
  }
  log.Println("Instance created and available.")
 }
 log.Println("Instance data:")
 log.Printf("\tDBInstanceIdentifier: %v\n", *instance.DBInstanceIdentifier)
 log.Printf("\tARN: %v\n", *instance.DBInstanceArn)
 log.Printf("\tStatus: %v\n", *instance.DBInstanceStatus)
 log.Printf("\tEngine: %v\n", *instance.Engine)
 log.Printf("\tEngine version: %v\n", *instance.EngineVersion)
 log.Println(strings.Repeat("-", 88))
 return instance
}

// DisplayConnection displays connection information about a DB instance and tips
// on how to connect to it.
```

```
func (scenario GetStartedInstances) DisplayConnection(instance *types.DBInstance)
 {
 log.Println(
  "You can now connect to your database by using your favorite MySQL client.\n" +
   "One way to connect is by using the 'mysql' shell on an Amazon EC2 instance\n"
 +
   "that is running in the same VPC as your DB instance. Pass the endpoint,\n" +
   "port, and administrator username to 'mysql'. Then, enter your password\n" +
   "when prompted:")
 log.Printf("\n\tmysql -h %v -P %v -u %v -p\n",
  *instance.Endpoint.Address, instance.Endpoint.Port, *instance.MasterUsername)
 log.Println("For more information, see the User Guide for RDS:\n" +
  "\thttps://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/
CHAP_GettingStarted.CreatingConnecting.MySQL.html#CHAP_GettingStarted.Connecting.MySQL")
 log.Println(strings.Repeat("-", 88))
}

// CreateSnapshot shows how to create a DB instance snapshot and wait until it's
 available.
func (scenario GetStartedInstances) CreateSnapshot(instance *types.DBInstance) {
 if scenario.questioner.AskBool(
  "Do you want to create a snapshot of your DB instance (y/n)? ", "y") {
  snapshotId := fmt.Sprintf("%v-%v", *instance.DBInstanceIdentifier,
 scenario.helper.UniqueId())
  log.Printf("Creating a snapshot named %v. This typically takes a few minutes.
\n", snapshotId)
  snapshot, err :=
 scenario.instances.CreateSnapshot(*instance.DBInstanceIdentifier, snapshotId)
  if err != nil {
   panic(err)
  }
  for *snapshot.Status != "available" {
   scenario.helper.Pause(30)
   snapshot, err = scenario.instances.GetSnapshot(snapshotId)
   if err != nil {
    panic(err)
   }
  }
  log.Println("Snapshot data:")
  log.Printf("\tDBSnapshotIdentifier: %v\n", *snapshot.DBSnapshotIdentifier)
  log.Printf("\tARN: %v\n", *snapshot.DBSnapshotArn)
  log.Printf("\tStatus: %v\n", *snapshot.Status)
  log.Printf("\tEngine: %v\n", *snapshot.Engine)
  log.Printf("\tEngine version: %v\n", *snapshot.EngineVersion)
```

```
  log.Printf("\tDBInstanceIdentifier: %v\n", *snapshot.DBInstanceIdentifier)
  log.Printf("\tSnapshotCreateTime: %v\n", *snapshot.SnapshotCreateTime)
  log.Println(strings.Repeat("-", 88))
 }
}

// Cleanup shows how to clean up a DB instance and DB parameter group.
// Before the DB parameter group can be deleted, all associated DB instances must
 first be deleted.
func (scenario GetStartedInstances) Cleanup(
 instance *types.DBInstance, parameterGroup *types.DBParameterGroup) {

 if scenario.questioner.AskBool(
  "\nDo you want to delete the database instance and parameter group (y/n)? ",
 "y") {
  log.Printf("Deleting database instance %v.\n", *instance.DBInstanceIdentifier)
  err := scenario.instances.DeleteInstance(*instance.DBInstanceIdentifier)
  if err != nil {
   panic(err)
  }
  log.Println(
   "Waiting for the DB instance to delete. This typically takes several
 minutes.")
  for instance != nil {
   scenario.helper.Pause(30)
   instance, err = scenario.instances.GetInstance(*instance.DBInstanceIdentifier)
   if err != nil {
    panic(err)
   }
  }
  log.Printf("Deleting parameter group %v.",
 *parameterGroup.DBParameterGroupName)
  err =
 scenario.instances.DeleteParameterGroup(*parameterGroup.DBParameterGroupName)
  if err != nil {
   panic(err)
  }
 }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Amazon RDS.

```
type DbInstances struct {
 RdsClient *rds.Client
}


// GetParameterGroup gets a DB parameter group by name.
func (instances *DbInstances) GetParameterGroup(parameterGroupName string) (
 *types.DBParameterGroup, error) {
 output, err := instances.RdsClient.DescribeDBParameterGroups(
  context.TODO(), &rds.DescribeDBParameterGroupsInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBParameterGroups[0], err
 }
}



// CreateParameterGroup creates a DB parameter group that is based on the
 specified
// parameter group family.
func (instances *DbInstances) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBParameterGroup, error) {

 output, err := instances.RdsClient.CreateDBParameterGroup(context.TODO(),
  &rds.CreateDBParameterGroupInput{
   DBParameterGroupName:   aws.String(parameterGroupName),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
   Description:            aws.String(description),
  })
 if err != nil {
```

```
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBParameterGroup, err
 }
}



// DeleteParameterGroup deletes the named DB parameter group.
func (instances *DbInstances) DeleteParameterGroup(parameterGroupName string)
 error {
 _, err := instances.RdsClient.DeleteDBParameterGroup(context.TODO(),
  &rds.DeleteDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// GetParameters gets the parameters that are contained in a DB parameter group.
func (instances *DbInstances) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator := rds.NewDescribeDBParametersPaginator(instances.RdsClient,
  &rds.DescribeDBParametersInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Source:               aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get parameters for %v: %v\n", parameterGroupName, err)
   break
```

```
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}



// UpdateParameters updates parameters in a named DB parameter group.
func (instances *DbInstances) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := instances.RdsClient.ModifyDBParameterGroup(context.TODO(),
  &rds.ModifyDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Parameters:           params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// CreateSnapshot creates a snapshot of a DB instance.
func (instances *DbInstances) CreateSnapshot(instanceName string, snapshotName
 string) (
 *types.DBSnapshot, error) {
 output, err := instances.RdsClient.CreateDBSnapshot(context.TODO(),
 &rds.CreateDBSnapshotInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBSnapshot, nil
 }
}
```

```
// GetSnapshot gets a DB instance snapshot.
func (instances *DbInstances) GetSnapshot(snapshotName string)
 (*types.DBSnapshot, error) {
 output, err := instances.RdsClient.DescribeDBSnapshots(context.TODO(),
  &rds.DescribeDBSnapshotsInput{
   DBSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBSnapshots[0], nil
 }
}



// CreateInstance creates a DB instance.
func (instances *DbInstances) CreateInstance(instanceName string, dbName string,
 dbEngine string, dbEngineVersion string, parameterGroupName string,
 dbInstanceClass string,
 storageType string, allocatedStorage int32, adminName string, adminPassword
 string) (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBName:               aws.String(dbName),
  DBParameterGroupName: aws.String(parameterGroupName),
  Engine:               aws.String(dbEngine),
  EngineVersion:        aws.String(dbEngineVersion),
  DBInstanceClass:      aws.String(dbInstanceClass),
  StorageType:          aws.String(storageType),
  AllocatedStorage:     aws.Int32(allocatedStorage),
  MasterUsername:       aws.String(adminName),
  MasterUserPassword:   aws.String(adminPassword),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
```

```
 }
}



// GetInstance gets data about a DB instance.
func (instances *DbInstances) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}



// DeleteInstance deletes a DB instance.
func (instances *DbInstances) DeleteInstance(instanceName string) error {
 _, err := instances.RdsClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}
```

```
// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (instances *DbInstances) GetEngineVersions(engine string,
 parameterGroupFamily string) (
 []types.DBEngineVersion, error) {
 output, err := instances.RdsClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (instances *DbInstances) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instanceOptions []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(instances.RdsClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instance options: %v\n", err)
   break
```

```
  } else {
   instanceOptions = append(instanceOptions,
 output.OrderableDBInstanceOptions...)
  }
 }
 return instanceOptions, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute várias operações.

```
import com.google.gson.Gson;
import
 software.amazon.awssdk.auth.credentials.EnvironmentVariableCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.CreateDbParameterGroupResponse;
import software.amazon.awssdk.services.rds.model.CreateDbSnapshotRequest;
import software.amazon.awssdk.services.rds.model.CreateDbSnapshotResponse;
import software.amazon.awssdk.services.rds.model.DBEngineVersion;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.DBParameterGroup;
import software.amazon.awssdk.services.rds.model.DBSnapshot;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbEngineVersionsRequest;
import
 software.amazon.awssdk.services.rds.model.DescribeDbEngineVersionsResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import
 software.amazon.awssdk.services.rds.model.DescribeDbParameterGroupsResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbParametersResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbSnapshotsRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbSnapshotsResponse;
import
 software.amazon.awssdk.services.rds.model.DescribeOrderableDbInstanceOptionsResponse;
import software.amazon.awssdk.services.rds.model.ModifyDbParameterGroupResponse;
import software.amazon.awssdk.services.rds.model.OrderableDBInstanceOption;
import software.amazon.awssdk.services.rds.model.Parameter;
import software.amazon.awssdk.services.rds.model.RdsException;
import software.amazon.awssdk.services.rds.model.CreateDbParameterGroupRequest;
import
 software.amazon.awssdk.services.rds.model.DescribeDbParameterGroupsRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbParametersRequest;
import software.amazon.awssdk.services.rds.model.ModifyDbParameterGroupRequest;
import
 software.amazon.awssdk.services.rds.model.DescribeOrderableDbInstanceOptionsRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbParameterGroupRequest;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
```

```
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For details, see:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 * This Java example performs these tasks:
 *
 * 1. Returns a list of the available DB engines.
 * 2. Selects an engine family and create a custom DB parameter group.
 * 3. Gets the parameter groups.
 * 4. Gets parameters in the group.
 * 5. Modifies the auto_increment_offset parameter.
 * 6. Gets and displays the updated parameters.
 * 7. Gets a list of allowed engine versions.
 * 8. Gets a list of micro instance classes available for the selected engine.
 * 9. Creates an RDS database instance that contains a MySql database and uses
 * the parameter group.
 * 10. Waits for the DB instance to be ready and prints out the connection
 * endpoint value.
 * 11. Creates a snapshot of the DB instance.
 * 12. Waits for an RDS DB snapshot to be ready.
 * 13. Deletes the RDS DB instance.
 * 14. Deletes the parameter group.
 */
public class RDSScenario {
    public static long sleepTime = 20;
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");
```

```
   public static void main(String[] args) throws InterruptedException {
       final String usage = """

               Usage:
                   <dbGroupName> <dbParameterGroupFamily> <dbInstanceIdentifier>
<dbName> <dbSnapshotIdentifier> <secretName>

               Where:
                   dbGroupName - The database group name.\s
                   dbParameterGroupFamily - The database parameter group name
(for example, mysql8.0).
                   dbInstanceIdentifier - The database instance identifier\s
                   dbName - The database name.\s
                   dbSnapshotIdentifier - The snapshot identifier.\s
                   secretName - The name of the AWS Secrets Manager secret that
contains the database credentials"
               """;

       if (args.length != 6) {
           System.out.println(usage);
           System.exit(1);
       }

       String dbGroupName = args[0];
       String dbParameterGroupFamily = args[1];
       String dbInstanceIdentifier = args[2];
       String dbName = args[3];
       String dbSnapshotIdentifier = args[4];
       String secretName = args[5];

       Gson gson = new Gson();
       User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
User.class);
       String masterUsername = user.getUsername();
       String masterUserPassword = user.getPassword();

       Region region = Region.US_WEST_2;
       RdsClient rdsClient = RdsClient.builder()
               .region(region)
               .build();
       System.out.println(DASHES);
       System.out.println("Welcome to the Amazon RDS example scenario.");
       System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("1. Return a list of the available DB engines");
        describeDBEngines(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a custom parameter group");
        createDBParameterGroup(rdsClient, dbGroupName, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get the parameter group");
        describeDbParameterGroups(rdsClient, dbGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get the parameters in the group");
        describeDbParameters(rdsClient, dbGroupName, 0);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Modify the auto_increment_offset parameter");
        modifyDBParas(rdsClient, dbGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Display the updated value");
        describeDbParameters(rdsClient, dbGroupName, -1);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of allowed engine versions");
        getAllowedEngines(rdsClient, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Get a list of micro instance classes available for
 the selected engine");
        getMicroInstances(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
```

```
                "9. Create an RDS database instance that contains a MySql
database and uses the parameter group");
        String dbARN = createDatabaseInstance(rdsClient, dbGroupName,
dbInstanceIdentifier, dbName, masterUsername,
                masterUserPassword);
        System.out.println("The ARN of the new database is " + dbARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Wait for DB instance to be ready");
        waitForInstanceReady(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Create a snapshot of the DB instance");
        createSnapshot(rdsClient, dbInstanceIdentifier, dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Wait for DB snapshot to be ready");
        waitForSnapshotReady(rdsClient, dbInstanceIdentifier,
dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Delete the DB instance");
        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Delete the parameter group");
        deleteParaGroup(rdsClient, dbGroupName, dbARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);

        rdsClient.close();
    }

    private static SecretsManagerClient getSecretClient() {
        Region region = Region.US_WEST_2;
        return SecretsManagerClient.builder()
```

```
                .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
                .build();
    }

    public static String getSecretValues(String secretName) {
        SecretsManagerClient secretClient = getSecretClient();
        GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                .secretId(secretName)
                .build();

        GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
        return valueResponse.secretString();
    }

    // Delete the parameter group after database has been deleted.
    // An exception is thrown if you attempt to delete the para group while
database
    // exists.
    public static void deleteParaGroup(RdsClient rdsClient, String dbGroupName,
String dbARN)
            throws InterruptedException {
        try {
            boolean isDataDel = false;
            boolean didFind;
            String instanceARN;

            // Make sure that the database has been deleted.
            while (!isDataDel) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
                List<DBInstance> instanceList = response.dbInstances();
                int listSize = instanceList.size();
                didFind = false;
                int index = 1;
                for (DBInstance instance : instanceList) {
                    instanceARN = instance.dbInstanceArn();
                    if (instanceARN.compareTo(dbARN) == 0) {
                        System.out.println(dbARN + " still exists");
                        didFind = true;
                    }
                    if ((index == listSize) && (!didFind)) {
```

```
                        // Went through the entire list and did not find the
database ARN.
                        isDataDel = true;
                    }
                    Thread.sleep(sleepTime * 1000);
                    index++;
                }
            }

            // Delete the para group.
            DeleteDbParameterGroupRequest parameterGroupRequest =
DeleteDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .build();

            rdsClient.deleteDBParameterGroup(parameterGroupRequest);
            System.out.println(dbGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Delete the DB instance.
    public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
        try {
            DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .deleteAutomatedBackups(true)
                    .skipFinalSnapshot(true)
                    .build();

            DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
            System.out.print("The status of the database is " +
response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
```

```
    }

    // Waits until the snapshot instance is available.
    public static void waitForSnapshotReady(RdsClient rdsClient, String
dbInstanceIdentifier,
            String dbSnapshotIdentifier) {
        try {
            boolean snapshotReady = false;
            String snapshotReadyStr;
            System.out.println("Waiting for the snapshot to become available.");

            DescribeDbSnapshotsRequest snapshotsRequest =
DescribeDbSnapshotsRequest.builder()
                    .dbSnapshotIdentifier(dbSnapshotIdentifier)
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            while (!snapshotReady) {
                DescribeDbSnapshotsResponse response =
rdsClient.describeDBSnapshots(snapshotsRequest);
                List<DBSnapshot> snapshotList = response.dbSnapshots();
                for (DBSnapshot snapshot : snapshotList) {
                    snapshotReadyStr = snapshot.status();
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }

            System.out.println("The Snapshot is available!");
        } catch (RdsException | InterruptedException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Create an Amazon RDS snapshot.
    public static void createSnapshot(RdsClient rdsClient, String
dbInstanceIdentifier, String dbSnapshotIdentifier) {
        try {
```

```
            CreateDbSnapshotRequest snapshotRequest =
CreateDbSnapshotRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .dbSnapshotIdentifier(dbSnapshotIdentifier)
                    .build();

            CreateDbSnapshotResponse response =
rdsClient.createDBSnapshot(snapshotRequest);
            System.out.println("The Snapshot id is " +
response.dbSnapshot().dbiResourceId());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Waits until the database instance is available.
    public static void waitForInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            String endpoint = "";
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint().address();
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
```

```
            }
            System.out.println("Database instance is available! The connection
endpoint is " + endpoint);

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Create a database instance and return the ARN of the database.
    public static String createDatabaseInstance(RdsClient rdsClient,
            String dbGroupName,
            String dbInstanceIdentifier,
            String dbName,
            String masterUsername,
            String masterUserPassword) {

        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .allocatedStorage(100)
                    .dbName(dbName)
                    .dbParameterGroupName(dbGroupName)
                    .engine("mysql")
                    .dbInstanceClass("db.m4.large")
                    .engineVersion("8.0")
                    .storageType("standard")
                    .masterUsername(masterUsername)
                    .masterUserPassword(masterUserPassword)
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
            return response.dbInstance().dbInstanceArn();

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
```

```
        return "";
    }

    // Get a list of micro instances.
    public static void getMicroInstances(RdsClient rdsClient) {
        try {
            DescribeOrderableDbInstanceOptionsRequest dbInstanceOptionsRequest =
DescribeOrderableDbInstanceOptionsRequest
                    .builder()
                    .engine("mysql")
                    .build();

            DescribeOrderableDbInstanceOptionsResponse response = rdsClient

.describeOrderableDBInstanceOptions(dbInstanceOptionsRequest);
            List<OrderableDBInstanceOption> orderableDBInstances =
response.orderableDBInstanceOptions();
            for (OrderableDBInstanceOption dbInstanceOption :
orderableDBInstances) {
                System.out.println("The engine version is " +
dbInstanceOption.engineVersion());
                System.out.println("The engine description is " +
dbInstanceOption.engine());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Get a list of allowed engine versions.
    public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
        try {
            DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .engine("mysql")
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
            List<DBEngineVersion> dbEngines = response.dbEngineVersions();
```

```
            for (DBEngineVersion dbEngine : dbEngines) {
                System.out.println("The engine version is " +
dbEngine.engineVersion());
                System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Modify auto_increment_offset and auto_increment_increment parameters.
    public static void modifyDBParas(RdsClient rdsClient, String dbGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
            paraList.add(parameter1);
            ModifyDbParameterGroupRequest groupRequest =
ModifyDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .parameters(paraList)
                    .build();

            ModifyDbParameterGroupResponse response =
rdsClient.modifyDBParameterGroup(groupRequest);
            System.out.println("The parameter group " +
response.dbParameterGroupName() + " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Retrieve parameters in the group.
    public static void describeDbParameters(RdsClient rdsClient, String
dbGroupName, int flag) {
```

```
        try {
            DescribeDbParametersRequest dbParameterGroupsRequest;
            if (flag == 0) {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbParametersResponse response =
rdsClient.describeDBParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset
or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") ==
0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

```
   public static void describeDbParameterGroups(RdsClient rdsClient, String
dbGroupName) {
       try {
           DescribeDbParameterGroupsRequest groupsRequest =
DescribeDbParameterGroupsRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .maxRecords(20)
                   .build();

           DescribeDbParameterGroupsResponse response =
rdsClient.describeDBParameterGroups(groupsRequest);
           List<DBParameterGroup> groups = response.dbParameterGroups();
           for (DBParameterGroup group : groups) {
               System.out.println("The group name is " +
group.dbParameterGroupName());
               System.out.println("The group description is " +
group.description());
           }

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }

   public static void createDBParameterGroup(RdsClient rdsClient, String
dbGroupName, String dbParameterGroupFamily) {
       try {
           CreateDbParameterGroupRequest groupRequest =
CreateDbParameterGroupRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .description("Created by using the AWS SDK for Java")
                   .build();

           CreateDbParameterGroupResponse response =
rdsClient.createDBParameterGroup(groupRequest);
           System.out.println("The group name is " +
response.dbParameterGroup().dbParameterGroupName());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
```

```
    }

    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
 DescribeDbEngineVersionsRequest.builder()
                    .defaultOnly(true)
                    .engine("mysql")
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
 rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
 the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
 engineOb.engine());
                System.out.println("The version number of the database engine " +
 engineOb.engineVersion());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup

- DB descrito EngineVersions
- DescribeDBInstances
- DB descrito ParameterGroups
- DescribeDBParameters
- DescribeDBSnapshots
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ParameterGroup

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this code example, set up your development environment, including
 your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

This example requires an AWS Secrets Manager secret that contains the database
 credentials. If you do not create a
secret, this example will not work. For more details, see:

https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html

This example performs the following tasks:

1. Returns a list of the available DB engines by invoking the
 DescribeDbEngineVersions method.
2. Selects an engine family and create a custom DB parameter group by invoking
 the createDBParameterGroup method.
```

```
3. Gets the parameter groups by invoking the DescribeDbParameterGroups method.
4. Gets parameters in the group by invoking the DescribeDbParameters method.
5. Modifies both the auto_increment_offset and auto_increment_increment
 parameters by invoking the modifyDbParameterGroup method.
6. Gets and displays the updated parameters.
7. Gets a list of allowed engine versions by invoking the
 describeDbEngineVersions method.
8. Gets a list of micro instance classes available for the selected engine.
9. Creates an Amazon Relational Database Service (Amazon RDS) database instance
 that contains a MySQL database and uses the parameter group.
10. Waits for DB instance to be ready and prints out the connection endpoint
 value.
11. Creates a snapshot of the DB instance.
12. Waits for the DB snapshot to be ready.
13. Deletes the DB instance.
14. Deletes the parameter group.
 */

var sleepTime: Long = 20
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <dbGroupName> <dbParameterGroupFamily> <dbInstanceIdentifier>
 <dbName> <dbSnapshotIdentifier><secretName>

        Where:
            dbGroupName - The database group name.
            dbParameterGroupFamily - The database parameter group name.
            dbInstanceIdentifier - The database instance identifier.
            dbName -  The database name.
            dbSnapshotIdentifier - The snapshot identifier.
            secretName - The name of the AWS Secrets Manager secret that contains
 the database credentials.
    """

    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }

    val dbGroupName = args[0]
    val dbParameterGroupFamily = args[1]
    val dbInstanceIdentifier = args[2]
    val dbName = args[3]
```

```
    val dbSnapshotIdentifier = args[4]
    val secretName = args[5]

    val gson = Gson()
    val user = gson.fromJson(getSecretValues(secretName).toString(),
User::class.java)
    val username = user.username
    val userPassword = user.password

    println("1. Return a list of the available DB engines")
    describeDBEngines()

    println("2. Create a custom parameter group")
    createDBParameterGroup(dbGroupName, dbParameterGroupFamily)

    println("3. Get the parameter groups")
    describeDbParameterGroups(dbGroupName)

    println("4. Get the parameters in the group")
    describeDbParameters(dbGroupName, 0)

    println("5. Modify the auto_increment_offset parameter")
    modifyDBParas(dbGroupName)

    println("6. Display the updated value")
    describeDbParameters(dbGroupName, -1)

    println("7. Get a list of allowed engine versions")
    getAllowedEngines(dbParameterGroupFamily)

    println("8. Get a list of micro instance classes available for the selected
engine")
    getMicroInstances()

    println("9. Create an RDS database instance that contains a MySql database
and uses the parameter group")
    val dbARN = createDatabaseInstance(dbGroupName, dbInstanceIdentifier, dbName,
username, userPassword)
    println("The ARN of the new database is $dbARN")

    println("10. Wait for DB instance to be ready")
    waitForDbInstanceReady(dbInstanceIdentifier)

    println("11. Create a snapshot of the DB instance")
```

```
    createDbSnapshot(dbInstanceIdentifier, dbSnapshotIdentifier)

    println("12. Wait for DB snapshot to be ready")
    waitForSnapshotReady(dbInstanceIdentifier, dbSnapshotIdentifier)

    println("13. Delete the DB instance")
    deleteDbInstance(dbInstanceIdentifier)

    println("14. Delete the parameter group")
    if (dbARN != null) {
        deleteParaGroup(dbGroupName, dbARN)
    }

    println("The Scenario has successfully completed.")
}

suspend fun deleteParaGroup(dbGroupName: String, dbARN: String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
            isDataDel = false // Reset this value.
            didFind = false // Reset this value.
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(dbARN) == 0) {
                        println("$dbARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database name.
                        isDataDel = true
                    }
                    index++
                }
```

```
            }
        }

        // Delete the para group.
        val parameterGroupRequest = DeleteDbParameterGroupRequest {
            dbParameterGroupName = dbGroupName
        }
        rdsClient.deleteDbParameterGroup(parameterGroupRequest)
        println("$dbGroupName was deleted.")
    }
}

suspend fun deleteDbInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}

// Waits until the snapshot instance is available.
suspend fun waitForSnapshotReady(dbInstanceIdentifierVal: String?,
 dbSnapshotIdentifierVal: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbSnapshotsRequest {
        dbSnapshotIdentifier = dbSnapshotIdentifierVal
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    while (!snapshotReady) {
        RdsClient { region = "us-west-2" }.use { rdsClient ->
            val response = rdsClient.describeDbSnapshots(snapshotsRequest)
            val snapshotList: List<DbSnapshot>? = response.dbSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
```

```
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
                    } else {
                        print(".")
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}

// Create an Amazon RDS snapshot.
suspend fun createDbSnapshot(dbInstanceIdentifierVal: String?,
 dbSnapshotIdentifierVal: String?) {
    val snapshotRequest = CreateDbSnapshotRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbSnapshotIdentifier = dbSnapshotIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbSnapshot(snapshotRequest)
        print("The Snapshot id is ${response.dbSnapshot?.dbiResourceId}")
    }
}

// Waits until the database instance is available.
suspend fun waitForDbInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }
    var endpoint = ""
    while (!instanceReady) {
        RdsClient { region = "us-west-2" }.use { rdsClient ->
            val response = rdsClient.describeDbInstances(instanceRequest)
            val instanceList = response.dbInstances
            if (instanceList != null) {
                for (instance in instanceList) {
```

```
                    instanceReadyStr = instance.dbInstanceStatus.toString()
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint?.address.toString()
                        instanceReady = true
                    } else {
                        print(".")
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
    }
    println("Database instance is available! The connection endpoint is
 $endpoint")
}

// Create a database instance and return the ARN of the database.
suspend fun createDatabaseInstance(dbGroupNameVal: String?,
 dbInstanceIdentifierVal: String?, dbNameVal: String?, masterUsernameVal:
 String?, masterUserPasswordVal: String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        allocatedStorage = 100
        dbName = dbNameVal
        dbParameterGroupName = dbGroupNameVal
        engine = "mysql"
        dbInstanceClass = "db.m4.large"
        engineVersion = "8.0"
        storageType = "standard"
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}

// Get a list of micro instances.
suspend fun getMicroInstances() {
    val dbInstanceOptionsRequest = DescribeOrderableDbInstanceOptionsRequest {
        engine = "mysql"
```

```
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeOrderableDbInstanceOptions(dbInstanceOptionsRequest)
        val orderableDBInstances = response.orderableDbInstanceOptions
        if (orderableDBInstances != null) {
            for (dbInstanceOption in orderableDBInstances) {
                println("The engine version is
 ${dbInstanceOption.engineVersion}")
                println("The engine description is ${dbInstanceOption.engine}")
            }
        }
    }
}

// Get a list of allowed engine versions.
suspend fun getAllowedEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "mysql"
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        val dbEngines: List<DbEngineVersion>? = response.dbEngineVersions
        if (dbEngines != null) {
            for (dbEngine in dbEngines) {
                println("The engine version is ${dbEngine.engineVersion}")
                println("The engine description is
 ${dbEngine.dbEngineDescription}")
            }
        }
    }
}

// Modify the auto_increment_offset parameter.
suspend fun modifyDBParas(dbGroupName: String) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.Immediate
        parameterValue = "5"
    }

    val paraList: ArrayList<Parameter> = ArrayList()
    paraList.add(parameter1)
```

```
    val groupRequest = ModifyDbParameterGroupRequest {
        dbParameterGroupName = dbGroupName
        parameters = paraList
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbParameterGroup(groupRequest)
        println("The parameter group ${response.dbParameterGroupName} was
 successfully modified")
    }
}

// Retrieve parameters in the group.
suspend fun describeDbParameters(dbGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbParametersRequest {
            dbParameterGroupName = dbGroupName
        }
    } else {
        DescribeDbParametersRequest {
            dbParameterGroupName = dbGroupName
            source = "user"
        }
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbParameters(dbParameterGroupsRequest)
        val dbParameters: List<Parameter>? = response.parameters
        var paraName: String
        if (dbParameters != null) {
            for (para in dbParameters) {
                // Only print out information about either auto_increment_offset
 or auto_increment_increment.
                paraName = para.parameterName.toString()
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    System.out.println("*** The parameter value is
 ${para.parameterValue}")
                    System.out.println("*** The parameter data type is
 ${para.dataType}")
                    System.out.println("*** The parameter description is
 ${para.description}")
```

```
                    System.out.println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
        }
    }
}

suspend fun describeDbParameterGroups(dbGroupName: String?) {
    val groupsRequest = DescribeDbParameterGroupsRequest {
        dbParameterGroupName = dbGroupName
        maxRecords = 20
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbParameterGroups(groupsRequest)
        val groups = response.dbParameterGroups
        if (groups != null) {
            for (group in groups) {
                println("The group name is ${group.dbParameterGroupName}")
                println("The group description is ${group.description}")
            }
        }
    }
}

// Create a parameter group.
suspend fun createDBParameterGroup(dbGroupName: String?,
 dbParameterGroupFamilyVal: String?) {
    val groupRequest = CreateDbParameterGroupRequest {
        dbParameterGroupName = dbGroupName
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbParameterGroup(groupRequest)
        println("The group name is
 ${response.dbParameterGroup?.dbParameterGroupName}")
    }
}

// Returns a list of the available DB engines.
suspend fun describeDBEngines() {
    val engineVersionsRequest = DescribeDbEngineVersionsRequest {
```

```
        defaultOnly = true
        engine = "mysql"
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(engineVersionsRequest)
        val engines: List<DbEngineVersion>? = response.dbEngineVersions

        // Get all DbEngineVersion objects.
        if (engines != null) {
            for (engineOb in engines) {
                println("The name of the DB parameter group family for the
 database engine is ${engineOb.dbParameterGroupFamily}.")
                println("The name of the database engine ${engineOb.engine}.")
                println("The version number of the database engine
 ${engineOb.engineVersion}")
            }
        }
    }
}

suspend fun getSecretValues(secretName: String?): String? {
    val valueRequest = GetSecretValueRequest {
        secretId = secretName
    }

    SecretsManagerClient { region = "us-west-2" }.use { secretsClient ->
        val valueResponse = secretsClient.getSecretValue(valueRequest)
        return valueResponse.secretString
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup

- DB descrito EngineVersions
- DescribeDBInstances
- DB descrito ParameterGroups
- DescribeDBParameters
- DescribeDBSnapshots
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ParameterGroup

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class RdsInstanceScenario:
    """Runs a scenario that shows how to get started using Amazon RDS DB
 instances."""

    def __init__(self, instance_wrapper):
        """
        :param instance_wrapper: An object that wraps Amazon RDS DB instance
 actions.
        """
        self.instance_wrapper = instance_wrapper

    def create_parameter_group(self, parameter_group_name, db_engine):
        """
        Shows how to get available engine versions for a specified database
 engine and
        create a DB parameter group that is compatible with a selected engine
 family.
```

```
        :param parameter_group_name: The name given to the newly created
parameter group.
        :param db_engine: The database engine to use as a basis.
        :return: The newly created parameter group.
        """
        print(
            f"Checking for an existing DB instance parameter group named
{parameter_group_name}."
        )
        parameter_group = self.instance_wrapper.get_parameter_group(
            parameter_group_name
        )
        if parameter_group is None:
            print(f"Getting available database engine versions for {db_engine}.")
            engine_versions =
self.instance_wrapper.get_engine_versions(db_engine)
            families = list({ver["DBParameterGroupFamily"] for ver in
engine_versions})
            family_index = q.choose("Which family do you want to use? ",
families)
            print(f"Creating a parameter group.")
            self.instance_wrapper.create_parameter_group(
                parameter_group_name, families[family_index], "Example parameter
group."
            )
            parameter_group = self.instance_wrapper.get_parameter_group(
                parameter_group_name
            )
        print(f"Parameter group {parameter_group['DBParameterGroupName']}:")
        pp(parameter_group)
        print("-" * 88)
        return parameter_group

    def update_parameters(self, parameter_group_name):
        """
        Shows how to get the parameters contained in a custom parameter group and
        update some of the parameter values in the group.

        :param parameter_group_name: The name of the parameter group to query and
modify.
        """
        print("Let's set some parameter values in your parameter group.")
        auto_inc_parameters = self.instance_wrapper.get_parameters(
            parameter_group_name, name_prefix="auto_increment"
```

```
        )
        update_params = []
        for auto_inc in auto_inc_parameters:
            if auto_inc["IsModifiable"] and auto_inc["DataType"] == "integer":
                print(f"The {auto_inc['ParameterName']} parameter is described
as:")
                print(f"\t{auto_inc['Description']}")
                param_range = auto_inc["AllowedValues"].split("-")
                auto_inc["ParameterValue"] = str(
                    q.ask(
                        f"Enter a value between {param_range[0]} and
{param_range[1]}: ",
                        q.is_int,
                        q.in_range(int(param_range[0]), int(param_range[1])),
                    )
                )
                update_params.append(auto_inc)
        self.instance_wrapper.update_parameters(parameter_group_name,
update_params)
        print(
            "You can get a list of parameters you've set by specifying a source
of 'user'."
        )
        user_parameters = self.instance_wrapper.get_parameters(
            parameter_group_name, source="user"
        )
        pp(user_parameters)
        print("-" * 88)

    def create_instance(self, instance_name, db_name, db_engine,
parameter_group):
        """
        Shows how to create a DB instance that contains a database of a specified
        type and is configured to use a custom DB parameter group.

        :param instance_name: The name given to the newly created DB instance.
        :param db_name: The name given to the created database.
        :param db_engine: The engine of the created database.
        :param parameter_group: The parameter group that is associated with the
DB instance.
        :return: The newly created DB instance.
        """
        print("Checking for an existing DB instance.")
        db_inst = self.instance_wrapper.get_db_instance(instance_name)
```

```
        if db_inst is None:
            print("Let's create a DB instance.")
            admin_username = q.ask(
                "Enter an administrator user name for the database: ",
q.non_empty
            )
            admin_password = q.ask(
                "Enter a password for the administrator (at least 8 characters):
",
                q.non_empty,
            )
            engine_versions = self.instance_wrapper.get_engine_versions(
                db_engine, parameter_group["DBParameterGroupFamily"]
            )
            engine_choices = [ver["EngineVersion"] for ver in engine_versions]
            print("The available engines for your parameter group are:")
            engine_index = q.choose("Which engine do you want to use? ",
engine_choices)
            engine_selection = engine_versions[engine_index]
            print(
                "The available micro DB instance classes for your database engine
are:"
            )
            inst_opts = self.instance_wrapper.get_orderable_instances(
                engine_selection["Engine"], engine_selection["EngineVersion"]
            )
            inst_choices = list(
                {
                    opt["DBInstanceClass"]
                    for opt in inst_opts
                    if "micro" in opt["DBInstanceClass"]
                }
            )
            inst_index = q.choose(
                "Which micro DB instance class do you want to use? ",
inst_choices
            )
            group_name = parameter_group["DBParameterGroupName"]
            storage_type = "standard"
            allocated_storage = 5
            print(
                f"Creating a DB instance named {instance_name} and database
{db_name}.\n"
```

```
                f"The DB instance is configured to use your custom parameter
 group {group_name},\n"
                f"selected engine {engine_selection['EngineVersion']},\n"
                f"selected DB instance class {inst_choices[inst_index]},"
                f"and {allocated_storage} GiB of {storage_type} storage.\n"
                f"This typically takes several minutes."
            )
            db_inst = self.instance_wrapper.create_db_instance(
                db_name,
                instance_name,
                group_name,
                engine_selection["Engine"],
                engine_selection["EngineVersion"],
                inst_choices[inst_index],
                storage_type,
                allocated_storage,
                admin_username,
                admin_password,
            )
            while db_inst.get("DBInstanceStatus") != "available":
                wait(10)
                db_inst = self.instance_wrapper.get_db_instance(instance_name)
        print("Instance data:")
        pp(db_inst)
        print("-" * 88)
        return db_inst

    @staticmethod
    def display_connection(db_inst):
        """
        Displays connection information about a DB instance and tips on how to
        connect to it.

        :param db_inst: The DB instance to display.
        """
        print(
            "You can now connect to your database using your favorite MySql
 client.\n"
            "One way to connect is by using the 'mysql' shell on an Amazon EC2
 instance\n"
            "that is running in the same VPC as your DB instance. Pass the
 endpoint,\n"
            "port, and administrator user name to 'mysql' and enter your password
\n"
```

```
            "when prompted:\n"
        )
        print(
            f"\n\tmysql -h {db_inst['Endpoint']['Address']} -P
 {db_inst['Endpoint']['Port']} "
            f"-u {db_inst['MasterUsername']} -p\n"
        )
        print(
            "For more information, see the User Guide for Amazon RDS:\n"
            "\thttps://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/
CHAP_GettingStarted.CreatingConnecting.MySQL.html#CHAP_GettingStarted.Connecting.MySQL"
        )
        print("-" * 88)

    def create_snapshot(self, instance_name):
        """
        Shows how to create a DB instance snapshot and wait until it's available.

        :param instance_name: The name of a DB instance to snapshot.
        """
        if q.ask(
            "Do you want to create a snapshot of your DB instance (y/n)? ",
 q.is_yesno
        ):
            snapshot_id = f"{instance_name}-{uuid.uuid4()}"
            print(
                f"Creating a snapshot named {snapshot_id}. This typically takes a
 few minutes."
            )
            snapshot = self.instance_wrapper.create_snapshot(snapshot_id,
 instance_name)
            while snapshot.get("Status") != "available":
                wait(10)
                snapshot = self.instance_wrapper.get_snapshot(snapshot_id)
            pp(snapshot)
            print("-" * 88)

    def cleanup(self, db_inst, parameter_group_name):
        """
        Shows how to clean up a DB instance and parameter group.
        Before the parameter group can be deleted, all associated DB instances
 must first
        be deleted.
```

```
        :param db_inst: The DB instance to delete.
        :param parameter_group_name: The DB parameter group to delete.
        """
        if q.ask(
            "\nDo you want to delete the DB instance and parameter group (y/n)?
",
            q.is_yesno,
        ):
            print(f"Deleting DB instance {db_inst['DBInstanceIdentifier']}.")

self.instance_wrapper.delete_db_instance(db_inst["DBInstanceIdentifier"])
            print(
                "Waiting for the DB instance to delete. This typically takes
several minutes."
            )
            while db_inst is not None:
                wait(10)
                db_inst = self.instance_wrapper.get_db_instance(
                    db_inst["DBInstanceIdentifier"]
                )
            print(f"Deleting parameter group {parameter_group_name}.")
            self.instance_wrapper.delete_parameter_group(parameter_group_name)

    def run_scenario(self, db_engine, parameter_group_name, instance_name,
db_name):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s:
%(message)s")

        print("-" * 88)
        print(
            "Welcome to the Amazon Relational Database Service (Amazon RDS)\n"
            "get started with DB instances demo."
        )
        print("-" * 88)

        parameter_group = self.create_parameter_group(parameter_group_name,
db_engine)
        self.update_parameters(parameter_group_name)
        db_inst = self.create_instance(
            instance_name, db_name, db_engine, parameter_group
        )
        self.display_connection(db_inst)
        self.create_snapshot(instance_name)
        self.cleanup(db_inst, parameter_group_name)
```

```
        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = RdsInstanceScenario(InstanceWrapper.from_client())
        scenario.run_scenario(
            "mysql",
            "doc-example-parameter-group",
            "doc-example-instance",
            "docexampledb",
        )
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Amazon RDS.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
```

```
        :return: The parameter group.
        """
        try:
            response = self.rds_client.describe_db_parameter_groups(
                DBParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB parameter group that is based on the specified parameter
group
        family.

        :param parameter_group_name: The name of the newly created parameter
group.
        :param parameter_group_family: The family that is used as the basis of
the new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
```

```
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            self.rds_client.delete_db_parameter_group(
                DBParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this
prefix.
```

```
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator = self.rds_client.get_paginator("describe_db_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
Parameters=update_parameters
            )
```

```
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def create_snapshot(self, snapshot_id, instance_id):
        """
        Creates a snapshot of a DB instance.

        :param snapshot_id: The ID to give the created snapshot.
        :param instance_id: The ID of the DB instance to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_snapshot(
                DBSnapshotIdentifier=snapshot_id,
DBInstanceIdentifier=instance_id
            )
            snapshot = response["DBSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def get_snapshot(self, snapshot_id):
        """
        Gets a DB instance snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
```

```
        """
        try:
            response = self.rds_client.describe_db_snapshots(
                DBSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned
list of
                                       engine versions to those that are
compatible with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise
        else:
            return versions


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by
the DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
```

```
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst


    def create_db_instance(
        self,
        db_name,
        instance_id,
        parameter_group_name,
        db_engine,
        db_engine_version,
        instance_class,
        storage_type,
        allocated_storage,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB instance.

        :param db_name: The name of the database that is created in the DB
instance.
        :param instance_id: The ID to give the newly created DB instance.
        :param parameter_group_name: A parameter group to associate with the DB
instance.
        :param db_engine: The database engine of a database to create in the DB
instance.
        :param db_engine_version: The engine version for the created database.
```

```
        :param instance_class: The DB instance class for the newly created DB
instance.
        :param storage_type: The storage type of the DB instance.
        :param allocated_storage: The amount of storage allocated on the DB
instance, in GiBs.
        :param admin_name: The name of the admin user for the created database.
        :param admin_password: The admin password for the created database.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBName=db_name,
                DBInstanceIdentifier=instance_id,
                DBParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                DBInstanceClass=instance_class,
                StorageType=storage_type,
                AllocatedStorage=allocated_storage,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
```

```
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

Exemplos sem servidor para Amazon RDS usando SDKs AWS

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service (Amazon RDS) com SDKs da AWS.

Exemplos

- Conectando-se a um banco de dados do Amazon RDS em uma função Lambda

Conectando-se a um banco de dados do Amazon RDS em uma função Lambda

O exemplo de código a seguir mostra como implementar uma função Lambda que se conecta a um banco de dados do RDS. A função faz uma solicitação simples ao banco de dados e retorna o resultado.

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
/*
Node.js code here.
*/
// ES6+ example
import { Signer } from "@aws-sdk/rds-signer";
import mysql from 'mysql2/promise';

async function createAuthToken() {
  // Define connection authentication parameters
  const dbinfo = {

    hostname: process.env.ProxyHostName,
    port: process.env.Port,
    username: process.env.DBUserName,
    region: process.env.AWS_REGION,
```

```
  }

  // Create RDS Signer object
  const signer = new Signer(dbinfo);

  // Request authorization token from RDS, specifying the username
  const token = await signer.getAuthToken();
  return token;
}

async function dbOps() {

  // Obtain auth token
  const token = await createAuthToken();
  // Define connection configuration
  let connectionConfig = {
    host: process.env.ProxyHostName,
    user: process.env.DBUserName,
    password: token,
    database: process.env.DBName,
    ssl: 'Amazon RDS'
  }
  // Create the connection to the DB
  const conn = await mysql.createConnection(connectionConfig);
  // Obtain the result of the query
  const [res,] = await conn.execute('select ?+? as sum', [3, 2]);
  return res;

}

export const handler = async (event) => {
  // Execute database flow
  const result = await dbOps();
  // Return result
  return {
    statusCode: 200,
    body: JSON.stringify("The selected sum is: " + result[0].sum)
  }
};
```

Exemplos do Amazon RDS entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service (Amazon RDS) com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia os itens de trabalho em um banco de dados do Amazon Aurora Sem Servidor e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar o AWS SDK for .NET para desenvolver uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end .NET RESTful.

- Integre uma aplicação Web do React com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Aurora.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS

- Serviços de dados do Amazon RDS
- Amazon SES

C++

SDK for C++

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Aurora Sem Servidor.

Para obter o código-fonte completo e instruções sobre como configurar uma API REST C++ que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Java

SDK para Java 2.x

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Para obter o código-fonte completo e instruções sobre como configurar e executar um exemplo que usa a API JDBC, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS

- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript (v3) para criar uma aplicação Web que rastreia itens de trabalho em um banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end Node.js Express.

- Integre uma aplicação Web React.js com Serviços da AWS.
- Liste, adicione e atualize itens em uma tabela do Aurora.
- Use o Amazon SES para enviar um relatório por e-mail dos itens de trabalho filtrados.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora

- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

PHP

SDK para PHP

Mostra como usar o AWS SDK for PHP para construir uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon RDS e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end construído com React.js para interagir com um back-end PHP RESTful.

- Integre uma aplicação Web React.js com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Amazon RDS.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar um serviço REST que rastreia itens de trabalho no banco de dados do Amazon Aurora Sem Servidor e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa o framework da Web do Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST do Flask que se integre a Serviços da AWS.

- Leia, grave e atualize itens de trabalho armazenados em um banco de dados do Aurora Sem Servidor.
- Crie um segredo do AWS Secrets Manager que contenha credenciais do banco de dados e use-o a fim de autenticar chamadas para o banco de dados.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Exemplos de código para o Amazon RDS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service Data Service com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, você pode ver as ações contextualizadas em seus devidos cenários e exemplos de serviços cruzados.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do Amazon RDS Data Service – Mais informações sobre o Amazon RDS Data Service.
- Referência da API do Amazon RDS Data Service – Detalhes sobre todas as ações disponíveis do Amazon RDS Data Service.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon SNS usando AWS SDKs
  - Executar uma instrução SQL usando um SDK da AWS
- Exemplos entre serviços para o Amazon RDS Data Service usando SDKs da AWS
  - Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Ações para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Executar uma instrução SQL usando um SDK da AWS

Executar uma instrução SQL usando um SDK da AWS

Os exemplos de código a seguir mostram como executar uma instrução SQL.

CLI

AWS CLI

Exemplo 1: como executar uma instrução SQL que faz parte de uma transação

O exemplo de `execute-statement` a seguir executa uma instrução SQL que é parte de uma transação.

```
aws rds-data execute-statement \
    --resource-arn "arn:aws:rds:us-west-2:123456789012:cluster:mydbcluster" \
    --database "mydb" \
    --secret-arn "arn:aws:secretsmanager:us-west-2:123456789012:secret:mysecret"
 \
    --sql "update mytable set quantity=5 where id=201" \
    --transaction-id "ABC1234567890xyz"
```

Saída:

```
{
    "numberOfRecordsUpdated": 1
```

```
}
```

Exemplo 2: como executar uma instrução SQL com parâmetros

O exemplo de `execute-statement` a seguir executa uma instrução SQL com parâmetros.

```
aws rds-data execute-statement \
    --resource-arn "arn:aws:rds:us-east-1:123456789012:cluster:mydbcluster" \
    --database "mydb" \
    --secret-arn "arn:aws:secretsmanager:us-east-1:123456789012:secret:mysecret"
 \
    --sql "insert into mytable values (:id, :val)" \
    --parameters "[{\"name\": \"id\", \"value\": {\"longValue\": 1}},{\"name\":
 \"val\", \"value\": {\"stringValue\": \"value1\"}}]"
```

Saída:

```
{
    "numberOfRecordsUpdated": 1
}
```

Para obter mais informações, consulte Using the Data API for Aurora Serverless no Guia do usuário do Amazon RDS.

- Para obter detalhes da API, consulte ExecuteStatementem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn query_cluster(
    client: &Client,
    cluster_arn: &str,
    query: &str,
```

```
    secret_arn: &str,
) -> Result<(), Error> {
    let st = client
        .execute_statement()
        .resource_arn(cluster_arn)
        .database("postgres") // Do not confuse this with db instance name
        .sql(query)
        .secret_arn(secret_arn);

    let result = st.send().await?;

    println!("{:?}", result);
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWS SDK for Rust.

Exemplos entre serviços para o Amazon RDS Data Service usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Relational Database Service com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia os itens de trabalho em um banco de dados do Amazon Aurora Sem Servidor e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar o AWS SDK for .NET para desenvolver uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end .NET RESTful.

- Integre uma aplicação Web do React com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Aurora.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

C++

SDK for C++

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Aurora Sem Servidor.

Para obter o código-fonte completo e instruções sobre como configurar uma API REST C++ que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS

- Serviços de dados do Amazon RDS
- Amazon SES

Java

SDK para Java 2.x

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Para obter o código-fonte completo e instruções sobre como configurar e executar um exemplo que usa a API JDBC, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript (v3) para criar uma aplicação Web que rastreia itens de trabalho em um banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end Node.js Express.

- Integre uma aplicação Web React.js com Serviços da AWS.
- Liste, adicione e atualize itens em uma tabela do Aurora.
- Use o Amazon SES para enviar um relatório por e-mail dos itens de trabalho filtrados.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

PHP

SDK para PHP

Mostra como usar o AWS SDK for PHP para construir uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon RDS e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end construído com React.js para interagir com um back-end PHP RESTful.

- Integre uma aplicação Web React.js com os serviços da AWS.

- Liste, adicione, atualize e exclua itens em uma tabela do Amazon RDS.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar um serviço REST que rastreia itens de trabalho no banco de dados do Amazon Aurora Sem Servidor e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa o framework da Web do Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST do Flask que se integre a Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em um banco de dados do Aurora Sem Servidor.
- Crie um segredo do AWS Secrets Manager que contenha credenciais do banco de dados e use-o a fim de autenticar chamadas para o banco de dados.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora

- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Exemplos de código para o Amazon Redshift usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Redshift com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, você pode ver as ações contextualizadas em seus devidos cenários e exemplos de serviços cruzados.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia de gerenciamento do Amazon Redshift – Mais informações sobre o Amazon Redshift.
- Referência da API do Amazon Redshift – Detalhes sobre todas as ações disponíveis do Amazon Redshift.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Redshift usando AWS SDKs
  - Crie um cluster do Amazon Redshift usando um SDK da AWS
  - Exclua um cluster do Amazon Redshift usando um SDK da AWS
  - Descreva um cluster do Amazon Redshift usando um SDK da AWS
  - Modifique um cluster do Amazon Redshift usando um SDK da AWS
- Exemplos entre serviços do Amazon RDS usando SDKs da AWS
  - Criar um rastreador de itens do Amazon Redshift

Ações do Amazon Redshift usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Redshift com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie um cluster do Amazon Redshift usando um SDK da AWS
- Exclua um cluster do Amazon Redshift usando um SDK da AWS
- Descreva um cluster do Amazon Redshift usando um SDK da AWS
- Modifique um cluster do Amazon Redshift usando um SDK da AWS

Crie um cluster do Amazon Redshift usando um SDK da AWS

O exemplo de código a seguir mostra como criar um cluster do Amazon Redshift.

CLI

AWS CLI

O ParametersThis exemplo Criar um cluster com mínimo cria um cluster com o conjunto mínimo de parâmetros. Por padrão, o formato da saída é JSON. Comando:

```
aws redshift create-cluster --node-type dw.hs1.xlarge --number-of-nodes 2 --
master-username adminuser --master-user-password TopSecret1 --cluster-identifier
 mycluster
```

Resultado:

```
{
   "Cluster": {
      "NodeType": "dw.hs1.xlarge",
      "ClusterVersion": "1.0",
      "PubliclyAccessible": "true",
      "MasterUsername": "adminuser",
      "ClusterParameterGroups": [
         {
            "ParameterApplyStatus": "in-sync",
            "ParameterGroupName": "default.redshift-1.0"
         } ],
```

```
        "ClusterSecurityGroups": [
           {
              "Status": "active",
              "ClusterSecurityGroupName": "default"
           } ],
        "AllowVersionUpgrade": true,
        "VpcSecurityGroups": \[],
        "PreferredMaintenanceWindow": "sat:03:30-sat:04:00",
        "AutomatedSnapshotRetentionPeriod": 1,
        "ClusterStatus": "creating",
        "ClusterIdentifier": "mycluster",
        "DBName": "dev",
        "NumberOfNodes": 2,
        "PendingModifiedValues": {
           "MasterUserPassword": "\****"
        }
    },
    "ResponseMetadata": {
        "RequestId": "7cf4bcfc-64dd-11e2-bea9-49e0ce183f07"
    }
}
```

- Para obter detalhes da API, consulte CreateClusterem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cluster.

```
    public static void createCluster(RedshiftClient redshiftClient, String
 clusterId, String masterUsername,
            String masterUserPassword) {
        try {
            CreateClusterRequest clusterRequest = CreateClusterRequest.builder()
                    .clusterIdentifier(clusterId)
```

```
                    .masterUsername(masterUsername) // set the user name here
                    .masterUserPassword(masterUserPassword) // set the user
 password here
                    .nodeType("dc2.large")
                    .publiclyAccessible(true)
                    .numberOfNodes(2)
                    .build();

            CreateClusterResponse clusterResponse =
 redshiftClient.createCluster(clusterRequest);
            System.out.println("Created cluster " +
 clusterResponse.cluster().clusterIdentifier());

        } catch (RedshiftException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateClustera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
```

```
export { redshiftClient };
```

Crie o cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { CreateClusterCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME", // Required
  NodeType: "NODE_TYPE", //Required
  MasterUsername: "MASTER_USER_NAME", // Required - must be lowercase
  MasterUserPassword: "MASTER_USER_PASSWORD", // Required - must contain at least
 one uppercase letter, and one number
  ClusterType: "CLUSTER_TYPE", // Required
  IAMRoleARN: "IAM_ROLE_ARN", // Optional - the ARN of an IAM role with
 permissions your cluster needs to access other AWS services on your behalf, such
 as Amazon S3.
  ClusterSubnetGroupName: "CLUSTER_SUBNET_GROUPNAME", //Optional - the name of a
 cluster subnet group to be associated with this cluster. Defaults to 'default'
 if not specified.
  DBName: "DATABASE_NAME", // Optional - defaults to 'dev' if not specified
  Port: "PORT_NUMBER", // Optional - defaults to '5439' if not specified
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new CreateClusterCommand(params));
    console.log(
      "Cluster " + data.Cluster.ClusterIdentifier + " successfully created",
    );
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateClustera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cluster.

```
suspend fun createCluster(clusterId: String?, masterUsernameVal: String?,
 masterUserPasswordVal: String?) {
    val clusterRequest = CreateClusterRequest {
        clusterIdentifier = clusterId
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
        nodeType = "ds2.xlarge"
        publiclyAccessible = true
        numberOfNodes = 2
    }

    RedshiftClient { region = "us-east-1" }.use { redshiftClient ->
        val clusterResponse = redshiftClient.createCluster(clusterRequest)
        println("Created cluster ${clusterResponse.cluster?.clusterIdentifier}")
    }
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWSSDK for Kotlin.

Exclua um cluster do Amazon Redshift usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um cluster do Amazon Redshift.

CLI

AWS CLI

O SnapshotThis exemplo Excluir um cluster sem cluster final exclui um cluster, forçando a exclusão de dados para que nenhum instantâneo final do cluster seja criado.Comando:

```
aws redshift delete-cluster --cluster-identifier mycluster --skip-final-cluster-
snapshot
```

Excluir um cluster, Permitindo um SnapshotThis exemplo de cluster final exclui um cluster, mas especifica um instantâneo final do cluster.Comando:

```
aws redshift delete-cluster --cluster-identifier mycluster --final-cluster-
snapshot-identifier myfinalsnapshot
```

- Para obter detalhes da API, consulte DeleteClusterem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o cluster.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.redshift.RedshiftClient;
import software.amazon.awssdk.services.redshift.model.DeleteClusterRequest;
import software.amazon.awssdk.services.redshift.model.DeleteClusterResponse;
import software.amazon.awssdk.services.redshift.model.RedshiftException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteCluster {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <clusterId>\s

                Where:
                    clusterId - The id of the cluster to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterId = args[0];
        Region region = Region.US_WEST_2;
        RedshiftClient redshiftClient = RedshiftClient.builder()
                .region(region)
                .build();

        deleteRedshiftCluster(redshiftClient, clusterId);
        redshiftClient.close();
    }

    public static void deleteRedshiftCluster(RedshiftClient redshiftClient,
 String clusterId) {
        try {
            DeleteClusterRequest deleteClusterRequest =
 DeleteClusterRequest.builder()
                    .clusterIdentifier(clusterId)
                    .skipFinalClusterSnapshot(true)
                    .build();

            DeleteClusterResponse response =
 redshiftClient.deleteCluster(deleteClusterRequest);
            System.out.println("The status is " +
 response.cluster().clusterStatus());

        } catch (RedshiftException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteCluster a Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Crie o cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { DeleteClusterCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME",
  SkipFinalClusterSnapshot: false,
  FinalClusterSnapshotIdentifier: "CLUSTER_SNAPSHOT_ID",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new DeleteClusterCommand(params));
```

```
    console.log("Success, cluster deleted. ", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte DeleteClustera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o cluster.

```
suspend fun deleteRedshiftCluster(clusterId: String?) {

    val request = DeleteClusterRequest {
        clusterIdentifier = clusterId
        skipFinalClusterSnapshot = true
    }

    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
        val response = redshiftClient.deleteCluster(request)
        println("The status is ${response.cluster?.clusterStatus}")
    }
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWSSDK for Kotlin.

Descreva um cluster do Amazon Redshift usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever clusters do Amazon Redshift.

CLI

AWS CLI

O ClustersThis exemplo Obter uma descrição de tudo retorna uma descrição de todos os clusters da conta. Por padrão, o formato da saída é JSON. Comando:

```
aws redshift describe-clusters
```

Resultado:

```
{
   "Clusters": [
   {
      "NodeType": "dw.hs1.xlarge",
      "Endpoint": {
         "Port": 5439,
         "Address": "mycluster.coqoarplqhsn.us-east-1.redshift.amazonaws.com"
      },
      "ClusterVersion": "1.0",
      "PubliclyAccessible": "true",
      "MasterUsername": "adminuser",
      "ClusterParameterGroups": [
         {
            "ParameterApplyStatus": "in-sync",
            "ParameterGroupName": "default.redshift-1.0"
         } ],
      "ClusterSecurityGroups": [
         {
            "Status": "active",
            "ClusterSecurityGroupName": "default"
         } ],
      "AllowVersionUpgrade": true,
      "VpcSecurityGroups": \[],
      "AvailabilityZone": "us-east-1a",
      "ClusterCreateTime": "2013-01-22T21:59:29.559Z",
      "PreferredMaintenanceWindow": "sat:03:30-sat:04:00",
      "AutomatedSnapshotRetentionPeriod": 1,
      "ClusterStatus": "available",
```

```
        "ClusterIdentifier": "mycluster",
        "DBName": "dev",
        "NumberOfNodes": 2,
        "PendingModifiedValues": {}
    } ],
    "ResponseMetadata": {
        "RequestId": "65b71cac-64df-11e2-8f5b-e90bd6c77476"
    }
}
```

Você pode obter as mesmas informações em formato de texto com a opção `--output text`. Comando:

opção `--output text`. Comando:

opção. Comando:

```
aws redshift describe-clusters --output text
```

Resultado:

```
dw.hs1.xlarge       1.0     true    adminuser       True    us-east-1a
 2013-01-22T21:59:29.559Z        sat:03:30-sat:04:00     1       available
 mycluster       dev     2
ENDPOINT    5439    mycluster.coqoarplqhsn.us-east-1.redshift.amazonaws.com
in-sync     default.redshift-1.0
active      default
PENDINGMODIFIEDVALUES
RESPONSEMETADATA    934281a8-64df-11e2-b07c-f7fbdd006c67
```

- Para obter detalhes da API, consulte DescribeClustersem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Descrever o cluster.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.redshift.RedshiftClient;
import software.amazon.awssdk.services.redshift.model.Cluster;
import software.amazon.awssdk.services.redshift.model.DescribeClustersResponse;
import software.amazon.awssdk.services.redshift.model.RedshiftException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeClusters {

    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        RedshiftClient redshiftClient = RedshiftClient.builder()
                .region(region)
                .build();

        describeRedshiftClusters(redshiftClient);
        redshiftClient.close();
    }

    public static void describeRedshiftClusters(RedshiftClient redshiftClient) {
        try {
```

```
            DescribeClustersResponse clusterResponse =
 redshiftClient.describeClusters();
            List<Cluster> clusterList = clusterResponse.clusters();
            for (Cluster cluster : clusterList) {
                System.out.println("Cluster database name is: " +
 cluster.dbName());
                System.out.println("Cluster status is: " +
 cluster.clusterStatus());
            }

        } catch (RedshiftException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Descreva seus clusters.

```
// Import required AWS SDK clients and commands for Node.js
import { DescribeClustersCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new DescribeClustersCommand(params));
    console.log("Success", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Descrever o cluster.

```
suspend fun describeRedshiftClusters() {

    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
```

```
        val clusterResponse =
 redshiftClient.describeClusters(DescribeClustersRequest {})
        val clusterList = clusterResponse.clusters

        if (clusterList != null) {
            for (cluster in clusterList) {
                println("Cluster database name is ${cluster.dbName}")
                println("Cluster status is ${cluster.clusterStatus}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeClustersreferência da API AWSSDK for Kotlin.

Modifique um cluster do Amazon Redshift usando um SDK da AWS

Os exemplos de código a seguir mostram como modificar um cluster do Amazon Redshift.

CLI

AWS CLI

Associar um grupo de segurança a um ClusterThis exemplo mostra como associar um grupo de segurança de cluster ao cluster especificado.Comando:

```
aws redshift modify-cluster --cluster-identifier mycluster --cluster-security-
groups mysecuritygroup
```

Modificar a janela de manutenção para a ClusterThis mostra como alterar a janela de manutenção semanal preferencial de um cluster para a janela mínima de quatro horas, começando aos domingos às 23h15 e terminando às segundas-feiras às 3h15.Comando:

```
aws redshift modify-cluster --cluster-identifier mycluster --preferred-
maintenance-window Sun:23:15-Mon:03:15
```

Alterar a senha mestra do ClusterThis exemplo mostra como alterar a senha mestra de um cluster.Comando:

```
aws redshift modify-cluster --cluster-identifier mycluster --master-user-password
 A1b2c3d4
```

- Para obter detalhes da API, consulte ModifyClusterem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Modifique um cluster.

```
   public static void modifyCluster(RedshiftClient redshiftClient, String
 clusterId) {

       try {
           ModifyClusterRequest modifyClusterRequest =
 ModifyClusterRequest.builder()
                   .clusterIdentifier(clusterId)
                   .preferredMaintenanceWindow("wed:07:30-wed:08:00")
                   .build();

           ModifyClusterResponse clusterResponse =
 redshiftClient.modifyCluster(modifyClusterRequest);
           System.out.println("The modified cluster was successfully modified
 and has "
                   + clusterResponse.cluster().preferredMaintenanceWindow() + "
 as the maintenance window");

       } catch (RedshiftException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ModifyClustera Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Modifique um cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { ModifyClusterCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

// Set the parameters
const params = {
  ClusterIdentifier: "CLUSTER_NAME",
  MasterUserPassword: "NEW_MASTER_USER_PASSWORD",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new ModifyClusterCommand(params));
    console.log("Success was modified.", data);
    return data; // For unit tests.
  } catch (err) {
```

```
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte ModifyClustera Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Modifique um cluster.

```
suspend fun modifyCluster(clusterId: String?) {
    val modifyClusterRequest = ModifyClusterRequest {
        clusterIdentifier = clusterId
        preferredMaintenanceWindow = "wed:07:30-wed:08:00"
    }

    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
        val clusterResponse = redshiftClient.modifyCluster(modifyClusterRequest)
        println("The modified cluster was successfully modified and has
 ${clusterResponse.cluster?.preferredMaintenanceWindow} as the maintenance
 window")
    }
}
```

- Para obter detalhes da API, consulte a ModifyClusterreferência da API AWSSDK for Kotlin.

Exemplos entre serviços do Amazon RDS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Redshift com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar um rastreador de itens do Amazon Redshift

Criar um rastreador de itens do Amazon Redshift

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho usando um banco de dados do Amazon Redshift.

Java

SDK para Java 2.x

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Exemplos de código para o Amazon Rekognition usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Rekognition com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Rekognition – Mais informações sobre o Amazon Rekognition.
- Referência da API do Amazon Rekognition – Detalhes sobre todas as ações disponíveis do Amazon Rekognition.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon Rekognition usando AWS SDK

- Compare faces em uma imagem com uma imagem de referência com o Amazon Rekognition usando um AWS SDK
- Criar uma coleção do Amazon Rekognition usando um AWS SDK.
- Exclua uma coleção do Amazon Rekognition usando um SDK da AWS.
- Exclua faces de uma coleção do Amazon Rekognition usando um SDK da AWS
- Descreva uma coleção do Amazon Rekognition usando um SDK da AWS.
- Detectar faces em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar rótulos em imagens com o Amazon Rekognition usando um AWSSDK
- Detecte rótulos de moderação em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Detecte textos em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Obtenha informações sobre celebridades com o Amazon Rekognition usando um SDK da AWS
- Indexe faces de uma coleção do Amazon Rekognition usando um AWS SDK.
- Liste uma coleção do Amazon Rekognition usando um SDK da AWS.
- Liste faces em uma coleção do Amazon Rekognition usando um SDK da AWS
- Reconheça celebridades em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Pesquise faces em uma coleção do Amazon Rekognition usando um SDK da AWS
- Pesquise rostos em uma coleção do Amazon Rekognition em comparação com uma imagem de referência usando um SDK da AWS

- Cenários do Amazon Rekognition usando os AWS SDKs
  - Crie uma coleção do Amazon Rekognition e encontre faces nela usando um AWS SDK
  - Detecte e exiba elementos em imagens com o Amazon Rekognition usando um SDK da AWS
  - Detecte informações em vídeos usando o Amazon Rekognition e o SDK da AWS
- Exemplos do Amazon Rekognition entre serviços usando AWS SDKs
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
  - Detectar faces em uma imagem usando um AWS SDK
  - Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
  - Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

  - Salvar o EXIF e outras informações de imagem usando um AWS SDK

Ações para o Amazon Rekognition usando AWS SDK

Os exemplos de código a seguir mostram como usar o Amazon Rekognition com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon Rekognition usando os AWS SDKs.

Exemplos

- Compare faces em uma imagem com uma imagem de referência com o Amazon Rekognition usando um AWS SDK
- Criar uma coleção do Amazon Rekognition usando um AWS SDK.
- Exclua uma coleção do Amazon Rekognition usando um SDK da AWS.
- Exclua faces de uma coleção do Amazon Rekognition usando um SDK da AWS
- Descreva uma coleção do Amazon Rekognition usando um SDK da AWS.
- Detectar faces em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar rótulos em imagens com o Amazon Rekognition usando um AWSSDK
- Detecte rótulos de moderação em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Detecte textos em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Obtenha informações sobre celebridades com o Amazon Rekognition usando um SDK da AWS
- Indexe faces de uma coleção do Amazon Rekognition usando um AWS SDK.
- Liste uma coleção do Amazon Rekognition usando um SDK da AWS.
- Liste faces em uma coleção do Amazon Rekognition usando um SDK da AWS
- Reconheça celebridades em uma imagem com o Amazon Rekognition usando um SDK da AWS
- Pesquise faces em uma coleção do Amazon Rekognition usando um SDK da AWS
- Pesquise rostos em uma coleção do Amazon Rekognition em comparação com uma imagem de referência usando um SDK da AWS

Compare faces em uma imagem com uma imagem de referência com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como comparar faces em uma imagem com uma imagem de referência com o Amazon Rekognition.

Para obter mais informações, consulte Comparar faces em imagens.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to compare faces in two images.
/// </summary>
public class CompareFaces
{
    public static async Task Main()
    {
        float similarityThreshold = 70F;
        string sourceImage = "source.jpg";
        string targetImage = "target.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        Amazon.Rekognition.Model.Image imageSource = new
Amazon.Rekognition.Model.Image();

        try
        {
```

```
                using FileStream fs = new FileStream(sourceImage, FileMode.Open,
FileAccess.Read);
                byte[] data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                imageSource.Bytes = new MemoryStream(data);
            }
            catch (Exception)
            {
                Console.WriteLine($"Failed to load source image: {sourceImage}");
                return;
            }

            Amazon.Rekognition.Model.Image imageTarget = new
Amazon.Rekognition.Model.Image();

            try
            {
                using FileStream fs = new FileStream(targetImage, FileMode.Open,
FileAccess.Read);
                byte[] data = new byte[fs.Length];
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                imageTarget.Bytes = new MemoryStream(data);
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Failed to load target image: {targetImage}");
                Console.WriteLine(ex.Message);
                return;
            }

            var compareFacesRequest = new CompareFacesRequest
            {
                SourceImage = imageSource,
                TargetImage = imageTarget,
                SimilarityThreshold = similarityThreshold,
            };

            // Call operation
            var compareFacesResponse = await
rekognitionClient.CompareFacesAsync(compareFacesRequest);

            // Display results
            compareFacesResponse.FaceMatches.ForEach(match =>
```

```
            {
                ComparedFace face = match.Face;
                BoundingBox position = face.BoundingBox;
                Console.WriteLine($"Face at {position.Left} {position.Top}
 matches with {match.Similarity}% confidence.");
            });

            Console.WriteLine($"Found {compareFacesResponse.UnmatchedFaces.Count}
 face(s) that did not match.");
        }
    }
```

- Para obter detalhes da API, consulte CompareFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como comparar faces em duas imagens

O comando `compare-faces` a seguir compara faces em duas imagens armazenadas em um bucket do Amazon S3.

```
aws rekognition compare-faces \
    --source-image '{"S3Object":
{"Bucket":"MyImageS3Bucket","Name":"source.jpg"}}' \
    --target-image '{"S3Object":
{"Bucket":"MyImageS3Bucket","Name":"target.jpg"}}'
```

Saída:

```
{
    "UnmatchedFaces": [],
    "FaceMatches": [
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.12368916720151901,
                    "Top": 0.16007372736930847,
```

```
                    "Left": 0.5901257991790771,
                    "Height": 0.25140416622161865
                },
                "Confidence": 100.0,
                "Pose": {
                    "Yaw": -3.7351467609405518,
                    "Roll": -0.10309021919965744,
                    "Pitch": 0.8637830018997192
                },
                "Quality": {
                    "Sharpness": 95.51618957519531,
                    "Brightness": 65.29893493652344
                },
                "Landmarks": [
                    {
                        "Y": 0.26721030473709106,
                        "X": 0.6204193830490112,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.26831310987472534,
                        "X": 0.6776827573776245,
                        "Type": "eyeRight"
                    },
                    {
                        "Y": 0.3514654338359833,
                        "X": 0.6241428852081299,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.35258132219314575,
                        "X": 0.6713621020317078,
                        "Type": "mouthRight"
                    },
                    {
                        "Y": 0.3140771687030792,
                        "X": 0.6428444981575012,
                        "Type": "nose"
                    }
                ]
            },
            "Similarity": 100.0
        }
    ],
```

```
    "SourceImageFace": {
        "BoundingBox": {
            "Width": 0.12368916720151901,
            "Top": 0.16007372736930847,
            "Left": 0.5901257991790771,
            "Height": 0.25140416622161865
        },
        "Confidence": 100.0
    }
}
```

Para obter mais informações, consulte Compare rostos em imagens no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte CompareFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.CompareFacesRequest;
import software.amazon.awssdk.services.rekognition.model.CompareFacesResponse;
import software.amazon.awssdk.services.rekognition.model.CompareFacesMatch;
import software.amazon.awssdk.services.rekognition.model.ComparedFace;
import software.amazon.awssdk.services.rekognition.model.BoundingBox;
import software.amazon.awssdk.core.SdkBytes;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CompareFaces {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <pathSource> <pathTarget>

                Where:
                   pathSource - The path to the source image (for example, C:\
\AWS\\pic1.png).\s
                    pathTarget - The path to the target image (for example, C:\
\AWS\\pic2.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        Float similarityThreshold = 70F;
        String sourceImage = args[0];
        String targetImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        compareTwoFaces(rekClient, similarityThreshold, sourceImage,
 targetImage);
        rekClient.close();
    }

    public static void compareTwoFaces(RekognitionClient rekClient, Float
 similarityThreshold, String sourceImage,
            String targetImage) {
        try {
```

```
            InputStream sourceStream = new FileInputStream(sourceImage);
            InputStream tarStream = new FileInputStream(targetImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            SdkBytes targetBytes = SdkBytes.fromInputStream(tarStream);

            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            Image tarImage = Image.builder()
                    .bytes(targetBytes)
                    .build();

            CompareFacesRequest facesRequest = CompareFacesRequest.builder()
                    .sourceImage(souImage)
                    .targetImage(tarImage)
                    .similarityThreshold(similarityThreshold)
                    .build();

            // Compare the two images.
            CompareFacesResponse compareFacesResult =
rekClient.compareFaces(facesRequest);
            List<CompareFacesMatch> faceDetails =
compareFacesResult.faceMatches();
            for (CompareFacesMatch match : faceDetails) {
                ComparedFace face = match.face();
                BoundingBox position = face.boundingBox();
                System.out.println("Face at " + position.left().toString()
                        + " " + position.top()
                        + " matches with " + face.confidence().toString()
                        + "% confidence.");

            }
            List<ComparedFace> uncompared = compareFacesResult.unmatchedFaces();
            System.out.println("There was " + uncompared.size() + " face(s) that
did not match");
            System.out.println("Source image rotation: " +
compareFacesResult.sourceImageOrientationCorrection());
            System.out.println("target image rotation: " +
compareFacesResult.targetImageOrientationCorrection());

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println("Failed to load source image " + sourceImage);
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CompareFacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun compareTwoFaces(similarityThresholdVal: Float, sourceImageVal:
 String, targetImageVal: String) {

    val sourceBytes = (File(sourceImageVal).readBytes())
    val targetBytes = (File(targetImageVal).readBytes())

    // Create an Image object for the source image.
    val souImage = Image {
        bytes = sourceBytes
    }

    val tarImage = Image {
        bytes = targetBytes
    }

    val facesRequest = CompareFacesRequest {
        sourceImage = souImage
        targetImage = tarImage
        similarityThreshold = similarityThresholdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
```

```
        val compareFacesResult = rekClient.compareFaces(facesRequest)
        val faceDetails = compareFacesResult.faceMatches

        if (faceDetails != null) {
            for (match: CompareFacesMatch in faceDetails) {
                val face = match.face
                val position = face?.boundingBox
                if (position != null)
                    println("Face at ${position.left} ${position.top} matches
 with ${face.confidence} % confidence.")
            }
        }

        val uncompared = compareFacesResult.unmatchedFaces
        if (uncompared != null)
            println("There was ${uncompared.size} face(s) that did not match")

        println("Source image rotation:
 ${compareFacesResult.sourceImageOrientationCorrection}")
        println("target image rotation:
 ${compareFacesResult.targetImageOrientationCorrection}")
    }
}
```

- Para obter detalhes da API, consulte a CompareFacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
```

```
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def compare_faces(self, target_image, similarity):
        """
        Compares faces in the image with the largest face in the target image.

        :param target_image: The target image to compare against.
        :param similarity: Faces in the image must have a similarity value
greater
                           than this value to be included in the results.
        :return: A tuple. The first element is the list of faces that match the
                 reference image. The second element is the list of faces that
have
                 a similarity value below the specified threshold.
        """
        try:
            response = self.rekognition_client.compare_faces(
                SourceImage=self.image,
                TargetImage=target_image.image,
                SimilarityThreshold=similarity,
            )
            matches = [
                RekognitionFace(match["Face"]) for match in
response["FaceMatches"]
            ]
            unmatches = [RekognitionFace(face) for face in
response["UnmatchedFaces"]]
            logger.info(
```

```
                "Found %s matched faces and %s unmatched faces.",
                len(matches),
                len(unmatches),
            )
        except ClientError:
            logger.exception(
                "Couldn't match faces from %s to %s.",
                self.image_name,
                target_image.image_name,
            )
            raise
        else:
            return matches, unmatches
```

- Para obter detalhes da API, consulte a CompareFacesReferência da API AWSSDK for Python (Boto3).

Criar uma coleção do Amazon Rekognition usando um AWS SDK.

Os exemplos de código a seguir mostram como criar uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Criar uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
```

```
    /// Uses Amazon Rekognition to create a collection to which you can add
    /// faces using the IndexFaces operation.
    /// </summary>
    public class CreateCollection
    {
        public static async Task Main()
        {
            var rekognitionClient = new AmazonRekognitionClient();

            string collectionId = "MyCollection";
            Console.WriteLine("Creating collection: " + collectionId);

            var createCollectionRequest = new CreateCollectionRequest
            {
                CollectionId = collectionId,
            };

            CreateCollectionResponse createCollectionResponse = await
 rekognitionClient.CreateCollectionAsync(createCollectionRequest);
            Console.WriteLine($"CollectionArn :
 {createCollectionResponse.CollectionArn}");
            Console.WriteLine($"Status code :
 {createCollectionResponse.StatusCode}");
        }
    }
```

- Para obter detalhes da API, consulte CreateCollectiona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar uma coleção

O comando `create-collection` a seguir cria uma coleção com o nome especificado.

```
aws rekognition create-collection \
    --collection-id "MyCollection"
```

Saída:

```
{
    "CollectionArn": "aws:rekognition:us-west-2:123456789012:collection/
MyCollection",
    "FaceModelVersion": "4.0",
    "StatusCode": 200
}
```

Para obter mais informações, consulte Criar uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte CreateCollectionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.CreateCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.CreateCollectionRequest;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class CreateCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionName>\s

                Where:
                   collectionName - The name of the collection.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Creating collection: " + collectionId);
        createMyCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void createMyCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            CreateCollectionRequest collectionRequest =
 CreateCollectionRequest.builder()
                    .collectionId(collectionId)
                    .build();

            CreateCollectionResponse collectionResponse =
 rekClient.createCollection(collectionRequest);
            System.out.println("CollectionArn: " +
 collectionResponse.collectionArn());
            System.out.println("Status code: " +
 collectionResponse.statusCode().toString());

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte CreateCollectiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createMyCollection(collectionIdVal: String) {

    val request = CreateCollectionRequest {
        collectionId = collectionIdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.createCollection(request)
        println("Collection ARN is ${response.collectionArn}")
        println("Status code is ${response.statusCode}")
    }
}
```

- Para obter detalhes da API, consulte a CreateCollectionreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollectionManager:
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition
 API.
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def create_collection(self, collection_id):
        """
        Creates an empty collection.

        :param collection_id: Text that identifies the collection.
        :return: The newly created collection.
        """
        try:
            response = self.rekognition_client.create_collection(
                CollectionId=collection_id
            )
            response["CollectionId"] = collection_id
            collection = RekognitionCollection(response, self.rekognition_client)
            logger.info("Created collection %s.", collection_id)
        except ClientError:
            logger.exception("Couldn't create collection %s.", collection_id)
```

```
            raise
        else:
            return collection
```

- Para obter detalhes da API, consulte a CreateCollectionReferência da API AWSSDK for Python (Boto3).

Exclua uma coleção do Amazon Rekognition usando um SDK da AWS.

Os exemplos de código a seguir mostram como excluir uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to delete an existing collection.
/// </summary>
public class DeleteCollection
{
    public static async Task Main()
    {
        var rekognitionClient = new AmazonRekognitionClient();

        string collectionId = "MyCollection";
        Console.WriteLine("Deleting collection: " + collectionId);
```

```
            var deleteCollectionRequest = new DeleteCollectionRequest()
            {
                CollectionId = collectionId,
            };

            var deleteCollectionResponse = await
 rekognitionClient.DeleteCollectionAsync(deleteCollectionRequest);
            Console.WriteLine($"{collectionId}:
 {deleteCollectionResponse.StatusCode}");
        }
    }
```

- Para obter detalhes da API, consulte DeleteCollectiona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir uma coleção

O comando `delete-collection` a seguir exclui a coleção especificada.

```
aws rekognition delete-collection \
    --collection-id MyCollection
```

Saída:

```
{
    "StatusCode": 200
}
```

Para obter mais informações, consulte Excluir uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DeleteCollectionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DeleteCollectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.DeleteCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId>\s

                Where:
                   collectionId - The id of the collection to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
```

```
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Deleting collection: " + collectionId);
        deleteMyCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void deleteMyCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            DeleteCollectionRequest deleteCollectionRequest =
 DeleteCollectionRequest.builder()
                    .collectionId(collectionId)
                    .build();

            DeleteCollectionResponse deleteCollectionResponse =
 rekClient.deleteCollection(deleteCollectionRequest);
            System.out.println(collectionId + ": " +
 deleteCollectionResponse.statusCode().toString());

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteCollectiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMyCollection(collectionIdVal: String) {

    val request = DeleteCollectionRequest {
        collectionId = collectionIdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.deleteCollection(request)
        println("The collectionId status is ${response.statusCode}")
    }
}
```

- Para obter detalhes da API, consulte a DeleteCollectionreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
```

```
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def delete_collection(self):
        """
        Deletes the collection.
        """
        try:

self.rekognition_client.delete_collection(CollectionId=self.collection_id)
            logger.info("Deleted collection %s.", self.collection_id)
            self.collection_id = None
        except ClientError:
```

```
            logger.exception("Couldn't delete collection %s.",
self.collection_id)
            raise
```

- Para obter detalhes da API, consulte a DeleteCollectionReferência da API AWSSDK for Python (Boto3).

Exclua faces de uma coleção do Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir faces de uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir faces de uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to delete one or more faces from
/// a Rekognition collection.
/// </summary>
public class DeleteFaces
{
    public static async Task Main()
    {
        string collectionId = "MyCollection";
```

```
            var faces = new List<string> { "xxxxxxxx-xxxx-xxxx-xxxx-
xxxxxxxxxxxx" };

            var rekognitionClient = new AmazonRekognitionClient();

            var deleteFacesRequest = new DeleteFacesRequest()
            {
                CollectionId = collectionId,
                FaceIds = faces,
            };

            DeleteFacesResponse deleteFacesResponse = await
 rekognitionClient.DeleteFacesAsync(deleteFacesRequest);
            deleteFacesResponse.DeletedFaces.ForEach(face =>
            {
                Console.WriteLine($"FaceID: {face}");
            });
        }
    }
```

- Para obter detalhes da API, consulte DeleteFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como excluir faces de uma coleção

O comando `delete-faces` a seguir exclui uma face especificada de uma coleção.

```
aws rekognition delete-faces \
    --collection-id MyCollection
    --face-ids '["0040279c-0178-436e-b70a-e61b074e96b0"]'
```

Saída:

```
{
    "DeletedFaces": [
        "0040279c-0178-436e-b70a-e61b074e96b0"
    ]
```

```
}
```

Para obter mais informações, consulte Excluir faces de uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DeleteFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DeleteFacesRequest;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteFacesFromCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId> <faceId>\s

                Where:
                   collectionId - The id of the collection from which faces are
 deleted.\s

                   faceId - The id of the face to delete.\s
```

```
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String faceId = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Deleting collection: " + collectionId);
        deleteFacesCollection(rekClient, collectionId, faceId);
        rekClient.close();
    }

    public static void deleteFacesCollection(RekognitionClient rekClient,
            String collectionId,
            String faceId) {

        try {
            DeleteFacesRequest deleteFacesRequest = DeleteFacesRequest.builder()
                    .collectionId(collectionId)
                    .faceIds(faceId)
                    .build();

            rekClient.deleteFaces(deleteFacesRequest);
            System.out.println("The face was deleted from the collection.");

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteFacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteFacesCollection(collectionIdVal: String?, faceIdVal: String) {

    val deleteFacesRequest = DeleteFacesRequest {
        collectionId = collectionIdVal
        faceIds = listOf(faceIdVal)
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        rekClient.deleteFaces(deleteFacesRequest)
        println("$faceIdVal was deleted from the collection")
    }
}
```

- Para obter detalhes da API, consulte a DeleteFacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
```

```
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def delete_faces(self, face_ids):
        """
        Deletes faces from the collection.

        :param face_ids: The list of IDs of faces to delete.
        :return: The list of IDs of faces that were deleted.
        """
        try:
            response = self.rekognition_client.delete_faces(
                CollectionId=self.collection_id, FaceIds=face_ids
            )
```

```
            deleted_ids = response["DeletedFaces"]
            logger.info(
                "Deleted %s faces from %s.", len(deleted_ids), self.collection_id
            )
        except ClientError:
            logger.exception("Couldn't delete faces from %s.",
self.collection_id)
            raise
        else:
            return deleted_ids
```

- Para obter detalhes da API, consulte a DeleteFacesReferência da API AWSSDK for Python (Boto3).

Descreva uma coleção do Amazon Rekognition usando um SDK da AWS.

Os exemplos de código a seguir mostram como descrever uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Descrever uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to describe the contents of a
/// collection.
```

```
    /// </summary>
    public class DescribeCollection
    {
        public static async Task Main()
        {
            var rekognitionClient = new AmazonRekognitionClient();

            string collectionId = "MyCollection";
            Console.WriteLine($"Describing collection: {collectionId}");

            var describeCollectionRequest = new DescribeCollectionRequest()
            {
                CollectionId = collectionId,
            };

            var describeCollectionResponse = await
 rekognitionClient.DescribeCollectionAsync(describeCollectionRequest);
            Console.WriteLine($"Collection ARN:
 {describeCollectionResponse.CollectionARN}");
            Console.WriteLine($"Face count:
 {describeCollectionResponse.FaceCount}");
            Console.WriteLine($"Face model version:
 {describeCollectionResponse.FaceModelVersion}");
            Console.WriteLine($"Created:
 {describeCollectionResponse.CreationTimestamp}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeCollectiona Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como descrever uma coleção

O exemplo de `describe-collection` a seguir exibe os detalhes da coleção especificada.

```
aws rekognition describe-collection \
```

```
    --collection-id MyCollection
```

Saída:

```
{
    "FaceCount": 200,
    "CreationTimestamp": 1569444828.274,
    "CollectionARN": "arn:aws:rekognition:us-west-2:123456789012:collection/
MyCollection",
    "FaceModelVersion": "4.0"
}
```

Para obter mais informações, consulte Descrever uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DescribeCollectionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.DescribeCollectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.DescribeCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionName>

                Where:
                   collectionName - The name of the Amazon Rekognition
 collection.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionName = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        describeColl(rekClient, collectionName);
        rekClient.close();
    }

    public static void describeColl(RekognitionClient rekClient, String
 collectionName) {
        try {
            DescribeCollectionRequest describeCollectionRequest =
 DescribeCollectionRequest.builder()
                    .collectionId(collectionName)
                    .build();

            DescribeCollectionResponse describeCollectionResponse = rekClient
                    .describeCollection(describeCollectionRequest);
            System.out.println("Collection Arn : " +
 describeCollectionResponse.collectionARN());
            System.out.println("Created : " +
 describeCollectionResponse.creationTimestamp().toString());
```

```
        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeCollectiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeColl(collectionName: String) {

    val request = DescribeCollectionRequest {
        collectionId = collectionName
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.describeCollection(request)
        println("The collection Arn is ${response.collectionArn}")
        println("The collection contains this many faces ${response.faceCount}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeCollectionreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
```

```
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def describe_collection(self):
        """
        Gets data about the collection from the Amazon Rekognition service.

        :return: The collection rendered as a dict.
        """
        try:
            response = self.rekognition_client.describe_collection(
                CollectionId=self.collection_id
            )
            # Work around capitalization of Arn vs. ARN
            response["CollectionArn"] = response.get("CollectionARN")
            (
                self.collection_arn,
                self.face_count,
                self.created,
            ) = self._unpack_collection(response)
            logger.info("Got data for collection %s.", self.collection_id)
        except ClientError:
            logger.exception("Couldn't get data for collection %s.",
self.collection_id)
            raise
        else:
            return self.to_dict()
```

- Para obter detalhes da API, consulte a DescribeCollectionReferência da API AWSSDK for Python (Boto3).

Detectar faces em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar rostos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar faces em uma imagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect faces within an image
/// stored in an Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class DetectFaces
{
    public static async Task Main()
    {
        string photo = "input.jpg";
        string bucket = "bucket";

        var rekognitionClient = new AmazonRekognitionClient();

        var detectFacesRequest = new DetectFacesRequest()
        {
            Image = new Image()
            {
                S3Object = new S3Object()
                {
                    Name = photo,
                    Bucket = bucket,
                },
            },

            // Attributes can be "ALL" or "DEFAULT".
```

```
                // "DEFAULT": BoundingBox, Confidence, Landmarks, Pose, and
 Quality.
                // "ALL": See https://docs.aws.amazon.com/sdkfornet/v3/apidocs/
items/Rekognition/TFaceDetail.html
                Attributes = new List<string>() { "ALL" },
            };

            try
            {
                DetectFacesResponse detectFacesResponse = await
 rekognitionClient.DetectFacesAsync(detectFacesRequest);
                bool hasAll = detectFacesRequest.Attributes.Contains("ALL");
                foreach (FaceDetail face in detectFacesResponse.FaceDetails)
                {
                    Console.WriteLine($"BoundingBox: top={face.BoundingBox.Left}
 left={face.BoundingBox.Top} width={face.BoundingBox.Width}
 height={face.BoundingBox.Height}");
                    Console.WriteLine($"Confidence: {face.Confidence}");
                    Console.WriteLine($"Landmarks: {face.Landmarks.Count}");
                    Console.WriteLine($"Pose: pitch={face.Pose.Pitch}
 roll={face.Pose.Roll} yaw={face.Pose.Yaw}");
                    Console.WriteLine($"Brightness:
 {face.Quality.Brightness}\tSharpness: {face.Quality.Sharpness}");

                    if (hasAll)
                    {
                        Console.WriteLine($"Estimated age is between
 {face.AgeRange.Low} and {face.AgeRange.High} years old.");
                    }
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

Exiba as informações da caixa delimitadora de todas as faces em uma imagem.

```
    using System;
```

```
    using System.Collections.Generic;
    using System.Drawing;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to display the details of the
    /// bounding boxes around the faces detected in an image.
    /// </summary>
    public class ImageOrientationBoundingBox
    {
        public static async Task Main()
        {
            string photo = @"D:\Development\AWS-Examples\Rekognition
\target.jpg"; // "photo.jpg";

            var rekognitionClient = new AmazonRekognitionClient();

            var image = new Amazon.Rekognition.Model.Image();
            try
            {
                using var fs = new FileStream(photo, FileMode.Open,
 FileAccess.Read);
                byte[] data = null;
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                image.Bytes = new MemoryStream(data);
            }
            catch (Exception)
            {
                Console.WriteLine("Failed to load file " + photo);
                return;
            }

            int height;
            int width;

            // Used to extract original photo width/height
            using (var imageBitmap = new Bitmap(photo))
            {
                height = imageBitmap.Height;
                width = imageBitmap.Width;
```

```
            }

            Console.WriteLine("Image Information:");
            Console.WriteLine(photo);
            Console.WriteLine("Image Height: " + height);
            Console.WriteLine("Image Width: " + width);

            try
            {
                var detectFacesRequest = new DetectFacesRequest()
                {
                    Image = image,
                    Attributes = new List<string>() { "ALL" },
                };

                DetectFacesResponse detectFacesResponse = await
rekognitionClient.DetectFacesAsync(detectFacesRequest);
                detectFacesResponse.FaceDetails.ForEach(face =>
                {
                    Console.WriteLine("Face:");
                    ShowBoundingBoxPositions(
                        height,
                        width,
                        face.BoundingBox,
                        detectFacesResponse.OrientationCorrection);

                    Console.WriteLine($"BoundingBox: top={face.BoundingBox.Left}
left={face.BoundingBox.Top} width={face.BoundingBox.Width}
height={face.BoundingBox.Height}");
                    Console.WriteLine($"The detected face is estimated to be
between {face.AgeRange.Low} and {face.AgeRange.High} years old.\n");
                });
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Display the bounding box information for an image.
        /// </summary>
        /// <param name="imageHeight">The height of the image.</param>
        /// <param name="imageWidth">The width of the image.</param>
```

```
        /// <param name="box">The bounding box for a face found within the
 image.</param>
        /// <param name="rotation">The rotation of the face's bounding box.</
param>
        public static void ShowBoundingBoxPositions(int imageHeight, int
 imageWidth, BoundingBox box, string rotation)
        {
            float left;
            float top;

            if (rotation == null)
            {
                Console.WriteLine("No estimated orientation. Check Exif data.");
                return;
            }

            // Calculate face position based on image orientation.
            switch (rotation)
            {
                case "ROTATE_0":
                    left = imageWidth * box.Left;
                    top = imageHeight * box.Top;
                    break;
                case "ROTATE_90":
                    left = imageHeight * (1 - (box.Top + box.Height));
                    top = imageWidth * box.Left;
                    break;
                case "ROTATE_180":
                    left = imageWidth - (imageWidth * (box.Left + box.Width));
                    top = imageHeight * (1 - (box.Top + box.Height));
                    break;
                case "ROTATE_270":
                    left = imageHeight * box.Top;
                    top = imageWidth * (1 - box.Left - box.Width);
                    break;
                default:
                    Console.WriteLine("No estimated orientation information.
 Check Exif data.");
                    return;
            }

            // Display face location information.
            Console.WriteLine($"Left: {left}");
            Console.WriteLine($"Top: {top}");
```

```
            Console.WriteLine($"Face Width: {imageWidth * box.Width}");
            Console.WriteLine($"Face Height: {imageHeight * box.Height}");
        }
    }
```

- Para obter detalhes da API, consulte DetectFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como detectar faces em uma imagem

O comando `detect-faces` a seguir detecta faces na imagem especificada armazenada em um bucket do Amazon S3.

```
aws rekognition detect-faces \
    --image '{"S3Object":{"Bucket":"MyImageS3Bucket","Name":"MyFriend.jpg"}}' \
    --attributes "ALL"
```

Saída:

```
{
    "FaceDetails": [
        {
            "Confidence": 100.0,
            "Eyeglasses": {
                "Confidence": 98.91107940673828,
                "Value": false
            },
            "Sunglasses": {
                "Confidence": 99.7966537475586,
                "Value": false
            },
            "Gender": {
                "Confidence": 99.56611633300781,
                "Value": "Male"
            },
            "Landmarks": [
                {
```

```
                "Y": 0.26721030473709106,
                "X": 0.6204193830490112,
                "Type": "eyeLeft"
            },
            {
                "Y": 0.26831310987472534,
                "X": 0.6776827573776245,
                "Type": "eyeRight"
            },
            {
                "Y": 0.3514654338359833,
                "X": 0.6241428852081299,
                "Type": "mouthLeft"
            },
            {
                "Y": 0.35258132219314575,
                "X": 0.6713621020317078,
                "Type": "mouthRight"
            },
            {
                "Y": 0.3140771687030792,
                "X": 0.6428444981575012,
                "Type": "nose"
            },
            {
                "Y": 0.24662546813488007,
                "X": 0.6001564860343933,
                "Type": "leftEyeBrowLeft"
            },
            {
                "Y": 0.24326619505882263,
                "X": 0.6303644776344299,
                "Type": "leftEyeBrowRight"
            },
            {
                "Y": 0.23818562924861908,
                "X": 0.6146903038024902,
                "Type": "leftEyeBrowUp"
            },
            {
                "Y": 0.24373626708984375,
                "X": 0.6640064716339111,
                "Type": "rightEyeBrowLeft"
            },
```

```
                {
                    "Y": 0.24877218902111053,
                    "X": 0.7025929093360901,
                    "Type": "rightEyeBrowRight"
                },
                {
                    "Y": 0.23938551545143127,
                    "X": 0.6823262572288513,
                    "Type": "rightEyeBrowUp"
                },
                {
                    "Y": 0.265746533870697,
                    "X": 0.6112898588180542,
                    "Type": "leftEyeLeft"
                },
                {
                    "Y": 0.2676128149032593,
                    "X": 0.6317071914672852,
                    "Type": "leftEyeRight"
                },
                {
                    "Y": 0.262735515832901,
                    "X": 0.6201658248901367,
                    "Type": "leftEyeUp"
                },
                {
                    "Y": 0.27025148272514343,
                    "X": 0.6206279993057251,
                    "Type": "leftEyeDown"
                },
                {
                    "Y": 0.268223375082016,
                    "X": 0.6658390760421753,
                    "Type": "rightEyeLeft"
                },
                {
                    "Y": 0.2672517001628876,
                    "X": 0.687832236289978,
                    "Type": "rightEyeRight"
                },
                {
                    "Y": 0.26383838057518005,
                    "X": 0.6769183874130249,
                    "Type": "rightEyeUp"
```

```
                },
                {
                    "Y": 0.27138751745224,
                    "X": 0.676596462726593,
                    "Type": "rightEyeDown"
                },
                {
                    "Y": 0.32283174991607666,
                    "X": 0.6350004076957703,
                    "Type": "noseLeft"
                },
                {
                    "Y": 0.3219289481639862,
                    "X": 0.6567046642303467,
                    "Type": "noseRight"
                },
                {
                    "Y": 0.3420318365097046,
                    "X": 0.6450609564781189,
                    "Type": "mouthUp"
                },
                {
                    "Y": 0.3664324879646301,
                    "X": 0.6455618143081665,
                    "Type": "mouthDown"
                },
                {
                    "Y": 0.26721030473709106,
                    "X": 0.6204193830490112,
                    "Type": "leftPupil"
                },
                {
                    "Y": 0.26831310987472534,
                    "X": 0.6776827573776245,
                    "Type": "rightPupil"
                },
                {
                    "Y": 0.26343393325805664,
                    "X": 0.5946047306060791,
                    "Type": "upperJawlineLeft"
                },
                {
                    "Y": 0.3543180525302887,
                    "X": 0.6044883728027344,
```

```
                "Type": "midJawlineLeft"
            },
            {
                "Y": 0.4084877669811249,
                "X": 0.6477024555206299,
                "Type": "chinBottom"
            },
            {
                "Y": 0.3562754988670349,
                "X": 0.707981526851654,
                "Type": "midJawlineRight"
            },
            {
                "Y": 0.26580461859703064,
                "X": 0.7234612107276917,
                "Type": "upperJawlineRight"
            }
        ],
        "Pose": {
            "Yaw": -3.7351467609405518,
            "Roll": -0.10309021919965744,
            "Pitch": 0.8637830018997192
        },
        "Emotions": [
            {
                "Confidence": 8.74203109741211,
                "Type": "SURPRISED"
            },
            {
                "Confidence": 2.501944065093994,
                "Type": "ANGRY"
            },
            {
                "Confidence": 0.7378743290901184,
                "Type": "DISGUSTED"
            },
            {
                "Confidence": 3.5296201705932617,
                "Type": "HAPPY"
            },
            {
                "Confidence": 1.7162904739379883,
                "Type": "SAD"
            },
```

```
                {
                    "Confidence": 9.518536567687988,
                    "Type": "CONFUSED"
                },
                {
                    "Confidence": 0.45474427938461304,
                    "Type": "FEAR"
                },
                {
                    "Confidence": 72.79895782470703,
                    "Type": "CALM"
                }
            ],
            "AgeRange": {
                "High": 48,
                "Low": 32
            },
            "EyesOpen": {
                "Confidence": 98.93987274169922,
                "Value": true
            },
            "BoundingBox": {
                "Width": 0.12368916720151901,
                "Top": 0.16007372736930847,
                "Left": 0.5901257991790771,
                "Height": 0.25140416622161865
            },
            "Smile": {
                "Confidence": 93.4493179321289,
                "Value": false
            },
            "MouthOpen": {
                "Confidence": 90.53053283691406,
                "Value": false
            },
            "Quality": {
                "Sharpness": 95.51618957519531,
                "Brightness": 65.29893493652344
            },
            "Mustache": {
                "Confidence": 89.85221099853516,
                "Value": false
            },
            "Beard": {
```

```
                "Confidence": 86.1991195678711,
                "Value": true
            }
        }
    ]
}
```

Para obter mais informações, consulte Detectar faces em uma imagem no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DetectFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.DetectFacesRequest;
import software.amazon.awssdk.services.rekognition.model.DetectFacesResponse;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.Attribute;
import software.amazon.awssdk.services.rekognition.model.FaceDetail;
import software.amazon.awssdk.services.rekognition.model.AgeRange;
import software.amazon.awssdk.core.SdkBytes;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectFaces {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectFacesinImage(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectFacesinImage(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectFacesRequest facesRequest = DetectFacesRequest.builder()
                    .attributes(Attribute.ALL)
                    .image(souImage)
```

```
                    .build();

            DetectFacesResponse facesResponse =
 rekClient.detectFaces(facesRequest);
            List<FaceDetail> faceDetails = facesResponse.faceDetails();
            for (FaceDetail face : faceDetails) {
                AgeRange ageRange = face.ageRange();
                System.out.println("The detected face is estimated to be between
 "
                        + ageRange.low().toString() + " and " +
 ageRange.high().toString()
                        + " years old.");

                System.out.println("There is a smile : " +
 face.smile().value().toString());
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectFacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectFacesinImage(sourceImage: String?) {

    val souImage = Image {
```

```
        bytes = (File(sourceImage).readBytes())
    }

    val request = DetectFacesRequest {
        attributes = listOf(Attribute.All)
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectFaces(request)
        response.faceDetails?.forEach { face ->
            val ageRange = face.ageRange
            println("The detected face is estimated to be between
 ${ageRange?.low} and ${ageRange?.high} years old.")
            println("There is a smile ${face.smile?.value}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectFacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.
```

```
        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_faces(self):
        """
        Detects faces in the image.

        :return: The list of faces found in the image.
        """
        try:
            response = self.rekognition_client.detect_faces(
                Image=self.image, Attributes=["ALL"]
            )
            faces = [RekognitionFace(face) for face in response["FaceDetails"]]
            logger.info("Detected %s faces.", len(faces))
        except ClientError:
            logger.exception("Couldn't detect faces in %s.", self.image_name)
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a DetectFacesReferência da API AWSSDK for Python (Boto3).

Detectar rótulos em imagens com o Amazon Rekognition usando um AWSSDK

Os exemplos de código a seguir mostram como detectar rótulos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar rótulos em uma imagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect labels within an image
/// stored in an Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class DetectLabels
{
    public static async Task Main()
    {
        string photo = "del_river_02092020_01.jpg"; // "input.jpg";
        string bucket = "igsmiths3photos"; // "bucket";

        var rekognitionClient = new AmazonRekognitionClient();

        var detectlabelsRequest = new DetectLabelsRequest
        {
            Image = new Image()
            {
                S3Object = new S3Object()
                {
                    Name = photo,
                    Bucket = bucket,
                },
            },
            MaxLabels = 10,
            MinConfidence = 75F,
        };
```

```
            try
            {
                DetectLabelsResponse detectLabelsResponse = await
rekognitionClient.DetectLabelsAsync(detectlabelsRequest);
                Console.WriteLine("Detected labels for " + photo);
                foreach (Label label in detectLabelsResponse.Labels)
                {
                    Console.WriteLine($"Name: {label.Name} Confidence:
{label.Confidence}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

Detecte rótulos em um arquivo de imagem armazenado em seu computador.

```
    using System;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to detect labels within an image
    /// stored locally.
    /// </summary>
    public class DetectLabelsLocalFile
    {
        public static async Task Main()
        {
            string photo = "input.jpg";

            var image = new Amazon.Rekognition.Model.Image();
            try
            {
                using var fs = new FileStream(photo, FileMode.Open,
FileAccess.Read);
```

```
                byte[] data = null;
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                image.Bytes = new MemoryStream(data);
            }
            catch (Exception)
            {
                Console.WriteLine("Failed to load file " + photo);
                return;
            }

            var rekognitionClient = new AmazonRekognitionClient();

            var detectlabelsRequest = new DetectLabelsRequest
            {
                Image = image,
                MaxLabels = 10,
                MinConfidence = 77F,
            };

            try
            {
                DetectLabelsResponse detectLabelsResponse = await
rekognitionClient.DetectLabelsAsync(detectlabelsRequest);
                Console.WriteLine($"Detected labels for {photo}");
                foreach (Label label in detectLabelsResponse.Labels)
                {
                    Console.WriteLine($"{label.Name}: {label.Confidence}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectLabelsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como detectar rótulos em uma imagem

O exemplo de `detect-labels` a seguir detecta cenas e objetos em uma imagem armazenada em um bucket do Amazon S3.

```
aws rekognition detect-labels \
    --image '{"S3Object":{"Bucket":"bucket","Name":"image"}}'
```

Saída:

```
{
    "Labels": [
        {
            "Instances": [],
            "Confidence": 99.15271759033203,
            "Parents": [
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Automobile"
        },
        {
            "Instances": [],
            "Confidence": 99.15271759033203,
            "Parents": [
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Vehicle"
        },
        {
            "Instances": [],
            "Confidence": 99.15271759033203,
            "Parents": [],
```

```
            "Name": "Transportation"
        },
        {
            "Instances": [
                {
                    "BoundingBox": {
                        "Width": 0.10616336017847061,
                        "Top": 0.5039216876029968,
                        "Left": 0.0037978808395564556,
                        "Height": 0.18528179824352264
                    },
                    "Confidence": 99.15271759033203
                },
                {
                    "BoundingBox": {
                        "Width": 0.2429988533258438,
                        "Top": 0.5251884460449219,
                        "Left": 0.7309805154800415,
                        "Height": 0.21577216684818268
                    },
                    "Confidence": 99.1286392211914
                },
                {
                    "BoundingBox": {
                        "Width": 0.14233611524105072,
                        "Top": 0.5333095788955688,
                        "Left": 0.6494812965393066,
                        "Height": 0.15528248250484467
                    },
                    "Confidence": 98.48368072509766
                },
                {
                    "BoundingBox": {
                        "Width": 0.11086395382881165,
                        "Top": 0.5354844927787781,
                        "Left": 0.10355594009160995,
                        "Height": 0.10271988064050674
                    },
                    "Confidence": 96.45606231689453
                },
                {
                    "BoundingBox": {
                        "Width": 0.06254628300666809,
                        "Top": 0.5573825240135193,
```

```
                        "Left": 0.46083059906959534,
                        "Height": 0.053911514580249786
                    },
                    "Confidence": 93.65448760986328
                },
                {
                    "BoundingBox": {
                        "Width": 0.10105438530445099,
                        "Top": 0.534368634223938,
                        "Left": 0.5743985772132874,
                        "Height": 0.12226245552301407
                    },
                    "Confidence": 93.06217193603516
                },
                {
                    "BoundingBox": {
                        "Width": 0.056389667093753815,
                        "Top": 0.5235804319381714,
                        "Left": 0.9427769780158997,
                        "Height": 0.17163699865341187
                    },
                    "Confidence": 92.6864013671875
                },
                {
                    "BoundingBox": {
                        "Width": 0.06003860384225845,
                        "Top": 0.5441341400146484,
                        "Left": 0.22409997880458832,
                        "Height": 0.06737709045410156
                    },
                    "Confidence": 90.4227066040039
                },
                {
                    "BoundingBox": {
                        "Width": 0.02848697081208229,
                        "Top": 0.5107086896896362,
                        "Left": 0,
                        "Height": 0.19150497019290924
                    },
                    "Confidence": 86.65286254882812
                },
                {
                    "BoundingBox": {
                        "Width": 0.04067881405353546,
```

```
                        "Top": 0.5566273927688599,
                        "Left": 0.316415935754776,
                        "Height": 0.03428703173995018
                    },
                    "Confidence": 85.36471557617188
                },
                {
                    "BoundingBox": {
                        "Width": 0.043411049991846085,
                        "Top": 0.5394920110702515,
                        "Left": 0.18293385207653046,
                        "Height": 0.0893595889210701
                    },
                    "Confidence": 82.21705627441406
                },
                {
                    "BoundingBox": {
                        "Width": 0.031183116137981415,
                        "Top": 0.5579366683959961,
                        "Left": 0.2853088080883026,
                        "Height": 0.03989990055561066
                    },
                    "Confidence": 81.0157470703125
                },
                {
                    "BoundingBox": {
                        "Width": 0.031113790348172188,
                        "Top": 0.5504819750785828,
                        "Left": 0.2580395042896271,
                        "Height": 0.056484755128622055
                    },
                    "Confidence": 56.13441467285156
                },
                {
                    "BoundingBox": {
                        "Width": 0.08586374670267105,
                        "Top": 0.5438792705535889,
                        "Left": 0.5128012895584106,
                        "Height": 0.08550430089235306
                    },
                    "Confidence": 52.37760925292969
                }
            ],
            "Confidence": 99.15271759033203,
```

```
            "Parents": [
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Car"
        },
        {
            "Instances": [],
            "Confidence": 98.9914321899414,
            "Parents": [],
            "Name": "Human"
        },
        {
            "Instances": [
                {
                    "BoundingBox": {
                        "Width": 0.19360728561878204,
                        "Top": 0.35072067379951477,
                        "Left": 0.43734854459762573,
                        "Height": 0.2742200493812561
                    },
                    "Confidence": 98.9914321899414
                },
                {
                    "BoundingBox": {
                        "Width": 0.03801717236638069,
                        "Top": 0.5010883808135986,
                        "Left": 0.9155802130699158,
                        "Height": 0.06597328186035156
                    },
                    "Confidence": 85.02790832519531
                }
            ],
            "Confidence": 98.9914321899414,
            "Parents": [],
            "Name": "Person"
        },
        {
            "Instances": [],
            "Confidence": 93.24951934814453,
```

```
            "Parents": [],
            "Name": "Machine"
        },
        {
            "Instances": [
                {
                    "BoundingBox": {
                        "Width": 0.03561960905790329,
                        "Top": 0.6468243598937988,
                        "Left": 0.7850857377052307,
                        "Height": 0.08878646790981293
                    },
                    "Confidence": 93.24951934814453
                },
                {
                    "BoundingBox": {
                        "Width": 0.02217046171426773,
                        "Top": 0.6149078607559204,
                        "Left": 0.04757237061858177,
                        "Height": 0.07136218994855881
                    },
                    "Confidence": 91.5025863647461
                },
                {
                    "BoundingBox": {
                        "Width": 0.016197510063648224,
                        "Top": 0.6274210214614868,
                        "Left": 0.6472989320755005,
                        "Height": 0.04955997318029404
                    },
                    "Confidence": 85.14686584472656
                },
                {
                    "BoundingBox": {
                        "Width": 0.020207518711686134,
                        "Top": 0.6348286867141724,
                        "Left": 0.7295016646385193,
                        "Height": 0.07059963047504425
                    },
                    "Confidence": 83.34547424316406
                },
                {
                    "BoundingBox": {
                        "Width": 0.020280985161662102,
```

```
                "Top": 0.6171894669532776,
                "Left": 0.08744934946298599,
                "Height": 0.05297485366463661
            },
            "Confidence": 79.9981460571289
        },
        {
            "BoundingBox": {
                "Width": 0.018318990245461464,
                "Top": 0.623889148235321,
                "Left": 0.6836880445480347,
                "Height": 0.06730121374130249
            },
            "Confidence": 78.87144470214844
        },
        {
            "BoundingBox": {
                "Width": 0.021310249343514442,
                "Top": 0.6167286038398743,
                "Left": 0.004064912907779217,
                "Height": 0.08317798376083374
            },
            "Confidence": 75.89361572265625
        },
        {
            "BoundingBox": {
                "Width": 0.03604431077837944,
                "Top": 0.7030032277107239,
                "Left": 0.9254803657531738,
                "Height": 0.04569442570209503
            },
            "Confidence": 64.402587890625
        },
        {
            "BoundingBox": {
                "Width": 0.009834849275648594,
                "Top": 0.5821820497512817,
                "Left": 0.28094568848609924,
                "Height": 0.01964157074689865
            },
            "Confidence": 62.79907989501953
        },
        {
            "BoundingBox": {
```

```
                        "Width": 0.01475677452981472,
                        "Top": 0.6137543320655823,
                        "Left": 0.5950819253921509,
                        "Height": 0.039063986390829086
                    },
                    "Confidence": 59.40483474731445
                }
            ],
            "Confidence": 93.24951934814453,
            "Parents": [
                {
                    "Name": "Machine"
                }
            ],
            "Name": "Wheel"
        },
        {
            "Instances": [],
            "Confidence": 92.61514282226562,
            "Parents": [],
            "Name": "Road"
        },
        {
            "Instances": [],
            "Confidence": 92.37877655029297,
            "Parents": [
                {
                    "Name": "Person"
                }
            ],
            "Name": "Sport"
        },
        {
            "Instances": [],
            "Confidence": 92.37877655029297,
            "Parents": [
                {
                    "Name": "Person"
                }
            ],
            "Name": "Sports"
        },
        {
            "Instances": [
```

```
                {
                    "BoundingBox": {
                        "Width": 0.12326609343290329,
                        "Top": 0.6332163214683533,
                        "Left": 0.44815489649772644,
                        "Height": 0.058117982000112534
                    },
                    "Confidence": 92.37877655029297
                }
            ],
            "Confidence": 92.37877655029297,
            "Parents": [
                {
                    "Name": "Person"
                },
                {
                    "Name": "Sport"
                }
            ],
            "Name": "Skateboard"
        },
        {
            "Instances": [],
            "Confidence": 90.62931060791016,
            "Parents": [
                {
                    "Name": "Person"
                }
            ],
            "Name": "Pedestrian"
        },
        {
            "Instances": [],
            "Confidence": 88.81334686279297,
            "Parents": [],
            "Name": "Asphalt"
        },
        {
            "Instances": [],
            "Confidence": 88.81334686279297,
            "Parents": [],
            "Name": "Tarmac"
        },
        {
```

```
            "Instances": [],
            "Confidence": 88.23201751708984,
            "Parents": [],
            "Name": "Path"
        },
        {
            "Instances": [],
            "Confidence": 80.26520538330078,
            "Parents": [],
            "Name": "Urban"
        },
        {
            "Instances": [],
            "Confidence": 80.26520538330078,
            "Parents": [
                {
                    "Name": "Building"
                },
                {
                    "Name": "Urban"
                }
            ],
            "Name": "Town"
        },
        {
            "Instances": [],
            "Confidence": 80.26520538330078,
            "Parents": [],
            "Name": "Building"
        },
        {
            "Instances": [],
            "Confidence": 80.26520538330078,
            "Parents": [
                {
                    "Name": "Building"
                },
                {
                    "Name": "Urban"
                }
            ],
            "Name": "City"
        },
        {
```

```
            "Instances": [],
            "Confidence": 78.37934875488281,
            "Parents": [
                {
                    "Name": "Car"
                },
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Parking Lot"
        },
        {
            "Instances": [],
            "Confidence": 78.37934875488281,
            "Parents": [
                {
                    "Name": "Car"
                },
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Parking"
        },
        {
            "Instances": [],
            "Confidence": 74.37590026855469,
            "Parents": [
                {
                    "Name": "Building"
                },
                {
                    "Name": "Urban"
                },
                {
                    "Name": "City"
                }
```

```
            ],
            "Name": "Downtown"
        },
        {
            "Instances": [],
            "Confidence": 69.84622955322266,
            "Parents": [
                {
                    "Name": "Road"
                }
            ],
            "Name": "Intersection"
        },
        {
            "Instances": [],
            "Confidence": 57.68518829345703,
            "Parents": [
                {
                    "Name": "Sports Car"
                },
                {
                    "Name": "Car"
                },
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
                }
            ],
            "Name": "Coupe"
        },
        {
            "Instances": [],
            "Confidence": 57.68518829345703,
            "Parents": [
                {
                    "Name": "Car"
                },
                {
                    "Name": "Vehicle"
                },
                {
                    "Name": "Transportation"
```

```
                }
            ],
            "Name": "Sports Car"
        },
        {
            "Instances": [],
            "Confidence": 56.59492111206055,
            "Parents": [
                {
                    "Name": "Path"
                }
            ],
            "Name": "Sidewalk"
        },
        {
            "Instances": [],
            "Confidence": 56.59492111206055,
            "Parents": [
                {
                    "Name": "Path"
                }
            ],
            "Name": "Pavement"
        },
        {
            "Instances": [],
            "Confidence": 55.58770751953125,
            "Parents": [
                {
                    "Name": "Building"
                },
                {
                    "Name": "Urban"
                }
            ],
            "Name": "Neighborhood"
        }
    ],
    "LabelModelVersion": "2.0"
}
```

Para obter mais informações, consulte Detectar rótulos em uma imagem no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DetectLabelsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.DetectLabelsRequest;
import software.amazon.awssdk.services.rekognition.model.DetectLabelsResponse;
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectLabels {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
```

```
                    sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectImageLabels(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectImageLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectLabelsRequest detectLabelsRequest =
 DetectLabelsRequest.builder()
                    .image(souImage)
                    .maxLabels(10)
                    .build();

            DetectLabelsResponse labelsResponse =
 rekClient.detectLabels(detectLabelsRequest);
            List<Label> labels = labelsResponse.labels();
            System.out.println("Detected labels for the given photo");
            for (Label label : labels) {
                System.out.println(label.name() + ": " +
 label.confidence().toString());
            }
```

```
        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectLabelsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectImageLabels(sourceImage: String) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }
    val request = DetectLabelsRequest {
        image = souImage
        maxLabels = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectLabels(request)
        response.labels?.forEach { label ->
            println("${label.name} : ${label.confidence}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectLabelsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_labels(self, max_labels):
        """
        Detects labels in the image. Labels are objects and people.

        :param max_labels: The maximum number of labels to return.
        :return: The list of labels detected in the image.
        """
        try:
            response = self.rekognition_client.detect_labels(
                Image=self.image, MaxLabels=max_labels
```

```
            )
            labels = [RekognitionLabel(label) for label in response["Labels"]]
            logger.info("Found %s labels in %s.", len(labels), self.image_name)
        except ClientError:
            logger.info("Couldn't detect labels in %s.", self.image_name)
            raise
        else:
            return labels
```

- Para obter detalhes da API, consulte a DetectLabelsReferência da API AWSSDK for Python (Boto3).

Detecte rótulos de moderação em uma imagem com o Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar rótulos de moderação em uma imagem com o Amazon Rekognition. Os rótulos de moderação identificam o conteúdo que pode ser inadequado para alguns públicos.

Para obter mais informações, consulte Detectar imagens inapropriadas.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect unsafe content in a
/// JPEG or PNG format image.
```

```
    /// </summary>
    public class DetectModerationLabels
    {
        public static async Task Main(string[] args)
        {
            string photo = "input.jpg";
            string bucket = "bucket";

            var rekognitionClient = new AmazonRekognitionClient();

            var detectModerationLabelsRequest = new
DetectModerationLabelsRequest()
            {
                Image = new Image()
                {
                    S3Object = new S3Object()
                    {
                        Name = photo,
                        Bucket = bucket,
                    },
                },
                MinConfidence = 60F,
            };

            try
            {
                var detectModerationLabelsResponse = await
rekognitionClient.DetectModerationLabelsAsync(detectModerationLabelsRequest);
                Console.WriteLine("Detected labels for " + photo);
                foreach (ModerationLabel label in
detectModerationLabelsResponse.ModerationLabels)
                {
                    Console.WriteLine($"Label: {label.Name}");
                    Console.WriteLine($"Confidence: {label.Confidence}");
                    Console.WriteLine($"Parent: {label.ParentName}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectModerationLabelsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como detectar conteúdo não seguro em uma imagem

O comando `detect-moderation-labels` a seguir detecta conteúdo não seguro na imagem especificada armazenada em um bucket do Amazon S3.

```
aws rekognition detect-moderation-labels \
    --image "S3Object={Bucket=MyImageS3Bucket,Name=gun.jpg}"
```

Saída:

```
{
    "ModerationModelVersion": "3.0",
    "ModerationLabels": [
        {
            "Confidence": 97.29618072509766,
            "ParentName": "Violence",
            "Name": "Weapon Violence"
        },
        {
            "Confidence": 97.29618072509766,
            "ParentName": "",
            "Name": "Violence"
        }
    ]
}
```

Para obter mais informações, consulte Detectando imagens inapropriadas no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte DetectModerationLabelsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import
 software.amazon.awssdk.services.rekognition.model.DetectModerationLabelsRequest;
import
 software.amazon.awssdk.services.rekognition.model.DetectModerationLabelsResponse;
import software.amazon.awssdk.services.rekognition.model.ModerationLabel;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectModerationLabels {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
```

```
                    sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectModLabels(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectModLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectModerationLabelsRequest moderationLabelsRequest =
 DetectModerationLabelsRequest.builder()
                    .image(souImage)
                    .minConfidence(60F)
                    .build();

            DetectModerationLabelsResponse moderationLabelsResponse = rekClient
                    .detectModerationLabels(moderationLabelsRequest);
            List<ModerationLabel> labels =
 moderationLabelsResponse.moderationLabels();
            System.out.println("Detected labels for image");
            for (ModerationLabel label : labels) {
                System.out.println("Label: " + label.name()
                        + "\n Confidence: " + label.confidence().toString() + "%"
                        + "\n Parent:" + label.parentName());
            }
```

```
        } catch (RekognitionException | FileNotFoundException e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectModerationLabelsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectModLabels(sourceImage: String) {

    val myImage = Image {
        this.bytes = (File(sourceImage).readBytes())
    }

    val request = DetectModerationLabelsRequest {
        image = myImage
        minConfidence = 60f
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectModerationLabels(request)
        response.moderationLabels?.forEach { label ->
            println("Label: ${label.name} - Confidence: ${label.confidence} %
 Parent: ${label.parentName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectModerationLabelsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_moderation_labels(self):
        """
        Detects moderation labels in the image. Moderation labels identify
 content
        that may be inappropriate for some audiences.
```

```
        :return: The list of moderation labels found in the image.
        """
        try:
            response = self.rekognition_client.detect_moderation_labels(
                Image=self.image
            )
            labels = [
                RekognitionModerationLabel(label)
                for label in response["ModerationLabels"]
            ]
            logger.info(
                "Found %s moderation labels in %s.", len(labels), self.image_name
            )
        except ClientError:
            logger.exception(
                "Couldn't detect moderation labels in %s.", self.image_name
            )
            raise
        else:
            return labels
```

- Para obter detalhes da API, consulte a DetectModerationLabelsReferência da API AWSSDK for Python (Boto3).

Detecte textos em uma imagem com o Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como detectar texto em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar texto em uma imagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect text in an image. The
/// example was created using the AWS SDK for .NET version 3.7 and .NET
/// Core 5.0.
/// </summary>
public class DetectText
{
    public static async Task Main()
    {
        string photo = "Dad_photographer.jpg"; // "input.jpg";
        string bucket = "igsmiths3photos"; // "bucket";

        var rekognitionClient = new AmazonRekognitionClient();

        var detectTextRequest = new DetectTextRequest()
        {
            Image = new Image()
            {
                S3Object = new S3Object()
                {
                    Name = photo,
                    Bucket = bucket,
                },
            },
        };

        try
        {
            DetectTextResponse detectTextResponse = await
rekognitionClient.DetectTextAsync(detectTextRequest);
            Console.WriteLine($"Detected lines and words for {photo}");
            detectTextResponse.TextDetections.ForEach(text =>
            {
                Console.WriteLine($"Detected: {text.DetectedText}");
                Console.WriteLine($"Confidence: {text.Confidence}");
                Console.WriteLine($"Id : {text.Id}");
                Console.WriteLine($"Parent Id: {text.ParentId}");
                Console.WriteLine($"Type: {text.Type}");
```

```
                });
            }
            catch (Exception e)
            {
                Console.WriteLine(e.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectTexta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como detectar texto em uma imagem

O comando `detect-text` a seguir detecta texto na imagem especificada.

```
aws rekognition detect-text \
    --image '{"S3Object":
{"Bucket":"MyImageS3Bucket","Name":"ExamplePicture.jpg"}}'
```

Saída:

```
{
    "TextDetections": [
        {
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.24624845385551453,
                    "Top": 0.28288066387176514,
                    "Left": 0.391388863325119,
                    "Height": 0.022687450051307678
                },
                "Polygon": [
                    {
                        "Y": 0.28288066387176514,
                        "X": 0.391388863325119
                    },
                    {
```

```
                        "Y": 0.2826388478279114,
                        "X": 0.6376373171806335
                    },
                    {
                        "Y": 0.30532628297805786,
                        "X": 0.637677013874054
                    },
                    {
                        "Y": 0.305568128824234,
                        "X": 0.39142853021621704
                    }
                ]
            },
            "Confidence": 94.35709381103516,
            "DetectedText": "ESTD 1882",
            "Type": "LINE",
            "Id": 0
        },
        {
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.33933889865875244,
                    "Top": 0.32603850960731506,
                    "Left": 0.34534579515457153,
                    "Height": 0.07126858830451965
                },
                "Polygon": [
                    {
                        "Y": 0.32603850960731506,
                        "X": 0.34534579515457153
                    },
                    {
                        "Y": 0.32633158564567566,
                        "X": 0.684684693813324
                    },
                    {
                        "Y": 0.3976001739501953,
                        "X": 0.684575080871582
                    },
                    {
                        "Y": 0.3973070979118347,
                        "X": 0.345236212015152
                    }
                ]
```

```
            },
            "Confidence": 99.95779418945312,
            "DetectedText": "BRAINS",
            "Type": "LINE",
            "Id": 1
        },
        {
            "Confidence": 97.22098541259766,
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.061079490929841995,
                    "Top": 0.2843210697174072,
                    "Left": 0.391391396522522,
                    "Height": 0.021029088646173477
                },
                "Polygon": [
                    {
                        "Y": 0.2843210697174072,
                        "X": 0.391391396522522
                    },
                    {
                        "Y": 0.2828207015991211,
                        "X": 0.4524524509906769
                    },
                    {
                        "Y": 0.3038259446620941,
                        "X": 0.4534534513950348
                    },
                    {
                        "Y": 0.30532634258270264,
                        "X": 0.3923923969268799
                    }
                ]
            },
            "DetectedText": "ESTD",
            "ParentId": 0,
            "Type": "WORD",
            "Id": 2
        },
        {
            "Confidence": 91.49320983886719,
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.07007007300853729,
```

```
                    "Top": 0.2828207015991211,
                    "Left": 0.5675675868988037,
                    "Height": 0.02250562608242035
                },
                "Polygon": [
                    {
                        "Y": 0.2828207015991211,
                        "X": 0.5675675868988037
                    },
                    {
                        "Y": 0.2828207015991211,
                        "X": 0.6376376152038574
                    },
                    {
                        "Y": 0.30532634258270264,
                        "X": 0.6376376152038574
                    },
                    {
                        "Y": 0.30532634258270264,
                        "X": 0.5675675868988037
                    }
                ]
            },
            "DetectedText": "1882",
            "ParentId": 0,
            "Type": "WORD",
            "Id": 3
        },
        {
            "Confidence": 99.95779418945312,
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.33933934569358826,
                    "Top": 0.32633158564567566,
                    "Left": 0.3453453481197357,
                    "Height": 0.07127484679222107
                },
                "Polygon": [
                    {
                        "Y": 0.32633158564567566,
                        "X": 0.3453453481197357
                    },
                    {
                        "Y": 0.32633158564567566,
```

```
                        "X": 0.684684693813324
                    },
                    {
                        "Y": 0.39759939908981323,
                        "X": 0.6836836934089661
                    },
                    {
                        "Y": 0.39684921503067017,
                        "X": 0.3453453481197357
                    }
                ]
            },
            "DetectedText": "BRAINS",
            "ParentId": 1,
            "Type": "WORD",
            "Id": 4
        }
    ]
}
```

- Para obter detalhes da API, consulte DetectTextem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DetectTextRequest;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.DetectTextResponse;
import software.amazon.awssdk.services.rekognition.model.TextDetection;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
```

```
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectText {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image that contains text (for
 example, C:\\AWS\\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectTextLabels(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectTextLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
```

```
                    .bytes(sourceBytes)
                    .build();

            DetectTextRequest textRequest = DetectTextRequest.builder()
                    .image(souImage)
                    .build();

            DetectTextResponse textResponse = rekClient.detectText(textRequest);
            List<TextDetection> textCollection = textResponse.textDetections();
            System.out.println("Detected lines and words");
            for (TextDetection text : textCollection) {
                System.out.println("Detected: " + text.detectedText());
                System.out.println("Confidence: " +
 text.confidence().toString());
                System.out.println("Id : " + text.id());
                System.out.println("Parent Id: " + text.parentId());
                System.out.println("Type: " + text.type());
                System.out.println();
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectTexta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectTextLabels(sourceImage: String?) {
```

```
    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = DetectTextRequest {
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectText(request)
        response.textDetections?.forEach { text ->
            println("Detected: ${text.detectedText}")
            println("Confidence: ${text.confidence}")
            println("Id: ${text.id}")
            println("Parent Id:  ${text.parentId}")
            println("Type: ${text.type}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectTextreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.
```

```
        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_text(self):
        """
        Detects text in the image.

        :return The list of text elements found in the image.
        """
        try:
            response = self.rekognition_client.detect_text(Image=self.image)
            texts = [RekognitionText(text) for text in
response["TextDetections"]]
            logger.info("Found %s texts in %s.", len(texts), self.image_name)
        except ClientError:
            logger.exception("Couldn't detect text in %s.", self.image_name)
            raise
        else:
            return texts
```

- Para obter detalhes da API, consulte a DetectTextReferência da API AWSSDK for Python (Boto3).

Obtenha informações sobre celebridades com o Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como obter informações sobre celebridades usando o Amazon Rekognition.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Shows how to use Amazon Rekognition to retrieve information about the
/// celebrity identified by the supplied celebrity Id.
/// </summary>
public class CelebrityInfo
{
    public static async Task Main()
    {
        string celebId = "nnnnnnnn";

        var rekognitionClient = new AmazonRekognitionClient();

        var celebrityInfoRequest = new GetCelebrityInfoRequest
        {
            Id = celebId,
        };

        Console.WriteLine($"Getting information for celebrity: {celebId}");

        var celebrityInfoResponse = await
rekognitionClient.GetCelebrityInfoAsync(celebrityInfoRequest);

        // Display celebrity information.
        Console.WriteLine($"celebrity name: {celebrityInfoResponse.Name}");
        Console.WriteLine("Further information (if available):");
        celebrityInfoResponse.Urls.ForEach(url =>
        {
```

```
                Console.WriteLine(url);
            });
        }
    }
```

- Para obter detalhes da API, consulte GetCelebrityInfoa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como obter informações sobre uma celebridade

O comando `get-celebrity-info` a seguir exibe informações sobre a celebridade especificada. O parâmetro `id` é proveniente de uma chamada anterior a `recognize-celebrities`.

```
aws rekognition get-celebrity-info --id nnnnnnn
```

Saída:

```
{
    "Name": "Celeb A",
    "Urls": [
        "www.imdb.com/name/aaaaaaaaa"
    ]
}
```

Para obter mais informações, consulte Obter informações sobre uma celebridade no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte GetCelebrityInfoem Referência de AWS CLI Comandos.

Indexe faces de uma coleção do Amazon Rekognition usando um AWS SDK.

Os exemplos de código a seguir mostram como indexar faces em uma imagem e adicioná-las a uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Adicionar faces a uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect faces in an image
/// that has been uploaded to an Amazon Simple Storage Service (Amazon S3)
/// bucket and then adds the information to a collection.
/// </summary>
public class AddFaces
{
    public static async Task Main()
    {
        string collectionId = "MyCollection2";
        string bucket = "doc-example-bucket";
        string photo = "input.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        var image = new Image
        {
            S3Object = new S3Object
            {
                Bucket = bucket,
                Name = photo,
            },
        };
```

```
            var indexFacesRequest = new IndexFacesRequest
            {
                Image = image,
                CollectionId = collectionId,
                ExternalImageId = photo,
                DetectionAttributes = new List<string>() { "ALL" },
            };

            IndexFacesResponse indexFacesResponse = await
 rekognitionClient.IndexFacesAsync(indexFacesRequest);

            Console.WriteLine($"{photo} added");
            foreach (FaceRecord faceRecord in indexFacesResponse.FaceRecords)
            {
                Console.WriteLine($"Face detected: Faceid is
 {faceRecord.Face.FaceId}");
            }
        }
    }
```

- Para obter detalhes da API, consulte IndexFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como adicionar faces a uma coleção

O comando `index-faces` a seguir adiciona as faces encontradas em uma imagem à coleção especificada.

```
aws rekognition index-faces \
    --image '{"S3Object":{"Bucket":"MyVideoS3Bucket","Name":"MyPicture.jpg"}}' \
    --collection-id MyCollection \
    --max-faces 1 \
    --quality-filter "AUTO" \
    --detection-attributes "ALL" \
    --external-image-id "MyPicture.jpg"
```

Saída:

```
{
    "FaceRecords": [
        {
            "FaceDetail": {
                "Confidence": 99.993408203125,
                "Eyeglasses": {
                    "Confidence": 99.11750030517578,
                    "Value": false
                },
                "Sunglasses": {
                    "Confidence": 99.98249053955078,
                    "Value": false
                },
                "Gender": {
                    "Confidence": 99.92769622802734,
                    "Value": "Male"
                },
                "Landmarks": [
                    {
                        "Y": 0.26750367879867554,
                        "X": 0.6202793717384338,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.26642778515815735,
                        "X": 0.6787431836128235,
                        "Type": "eyeRight"
                    },
                    {
                        "Y": 0.31361380219459534,
                        "X": 0.6421601176261902,
                        "Type": "nose"
                    },
                    {
                        "Y": 0.3495299220085144,
                        "X": 0.6216195225715637,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.35194727778434753,
                        "X": 0.669899046421051,
                        "Type": "mouthRight"
                    },
```

```
                    {
                        "Y": 0.26844894886016846,
                        "X": 0.6210268139839172,
                        "Type": "leftPupil"
                    },
                    {
                        "Y": 0.26707562804222107,
                        "X": 0.6817160844802856,
                        "Type": "rightPupil"
                    },
                    {
                        "Y": 0.24834522604942322,
                        "X": 0.6018546223640442,
                        "Type": "leftEyeBrowLeft"
                    },
                    {
                        "Y": 0.24397172033786774,
                        "X": 0.6172008514404297,
                        "Type": "leftEyeBrowUp"
                    },
                    {
                        "Y": 0.24677404761314392,
                        "X": 0.6339119076728821,
                        "Type": "leftEyeBrowRight"
                    },
                    {
                        "Y": 0.24582654237747192,
                        "X": 0.6619398593902588,
                        "Type": "rightEyeBrowLeft"
                    },
                    {
                        "Y": 0.23973053693771362,
                        "X": 0.6804757118225098,
                        "Type": "rightEyeBrowUp"
                    },
                    {
                        "Y": 0.24441994726657867,
                        "X": 0.6978968977928162,
                        "Type": "rightEyeBrowRight"
                    },
                    {
                        "Y": 0.2695908546447754,
                        "X": 0.6085202693939209,
                        "Type": "leftEyeLeft"
```

```
                    },
                    {
                        "Y": 0.26716896891593933,
                        "X": 0.6315826177597046,
                        "Type": "leftEyeRight"
                    },
                    {
                        "Y": 0.26289820671081543,
                        "X": 0.6202316880226135,
                        "Type": "leftEyeUp"
                    },
                    {
                        "Y": 0.27123287320137024,
                        "X": 0.6205548048019409,
                        "Type": "leftEyeDown"
                    },
                    {
                        "Y": 0.2668408751487732,
                        "X": 0.6663622260093689,
                        "Type": "rightEyeLeft"
                    },
                    {
                        "Y": 0.26741549372673035,
                        "X": 0.6910083889961243,
                        "Type": "rightEyeRight"
                    },
                    {
                        "Y": 0.2614026665687561,
                        "X": 0.6785826086997986,
                        "Type": "rightEyeUp"
                    },
                    {
                        "Y": 0.27075251936912537,
                        "X": 0.6789616942405701,
                        "Type": "rightEyeDown"
                    },
                    {
                        "Y": 0.3211299479007721,
                        "X": 0.6324167847633362,
                        "Type": "noseLeft"
                    },
                    {
                        "Y": 0.32276326417922974,
                        "X": 0.6558475494384766,
```

```
                "Type": "noseRight"
            },
            {
                "Y": 0.34385165572166443,
                "X": 0.6444970965385437,
                "Type": "mouthUp"
            },
            {
                "Y": 0.3671635091304779,
                "X": 0.6459195017814636,
                "Type": "mouthDown"
            }
        ],
        "Pose": {
            "Yaw": -9.54541015625,
            "Roll": -0.5709401965141296,
            "Pitch": 0.6045494675636292
        },
        "Emotions": [
            {
                "Confidence": 39.90074157714844,
                "Type": "HAPPY"
            },
            {
                "Confidence": 23.38753890991211,
                "Type": "CALM"
            },
            {
                "Confidence": 5.840933322906494,
                "Type": "CONFUSED"
            }
        ],
        "AgeRange": {
            "High": 63,
            "Low": 45
        },
        "EyesOpen": {
            "Confidence": 99.80887603759766,
            "Value": true
        },
        "BoundingBox": {
            "Width": 0.18562500178813934,
            "Top": 0.1618015021085739,
            "Left": 0.5575000047683716,
```

```
                    "Height": 0.24770642817020416
                },
                "Smile": {
                    "Confidence": 99.69740295410156,
                    "Value": false
                },
                "MouthOpen": {
                    "Confidence": 99.97393798828125,
                    "Value": false
                },
                "Quality": {
                    "Sharpness": 95.54405975341797,
                    "Brightness": 63.867706298828125
                },
                "Mustache": {
                    "Confidence": 97.05007934570312,
                    "Value": false
                },
                "Beard": {
                    "Confidence": 87.34505462646484,
                    "Value": false
                }
            },
            "Face": {
                "BoundingBox": {
                    "Width": 0.18562500178813934,
                    "Top": 0.1618015021085739,
                    "Left": 0.5575000047683716,
                    "Height": 0.24770642817020416
                },
                "FaceId": "ce7ed422-2132-4a11-ab14-06c5c410f29f",
                "ExternalImageId": "example-image.jpg",
                "Confidence": 99.993408203125,
                "ImageId": "8d67061e-90d2-598f-9fbd-29c8497039c0"
            }
        }
    ],
    "UnindexedFaces": [],
    "FaceModelVersion": "3.0",
    "OrientationCorrection": "ROTATE_0"
}
```

Para obter mais informações, consulte Adicionar faces a uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte IndexFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.IndexFacesResponse;
import software.amazon.awssdk.services.rekognition.model.IndexFacesRequest;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.QualityFilter;
import software.amazon.awssdk.services.rekognition.model.Attribute;
import software.amazon.awssdk.services.rekognition.model.FaceRecord;
import software.amazon.awssdk.services.rekognition.model.UnindexedFace;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Reason;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AddFacesToCollection {
```

```
    public static void main(String[] args) {

        final String usage = """

                Usage:     <collectionId> <sourceImage>

                Where:
                    collectionName - The name of the collection.
                    sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String sourceImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        addToCollection(rekClient, collectionId, sourceImage);
        rekClient.close();
    }

    public static void addToCollection(RekognitionClient rekClient, String
 collectionId, String sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            IndexFacesRequest facesRequest = IndexFacesRequest.builder()
                    .collectionId(collectionId)
                    .image(souImage)
                    .maxFaces(1)
                    .qualityFilter(QualityFilter.AUTO)
                    .detectionAttributes(Attribute.DEFAULT)
                    .build();
```

```
            IndexFacesResponse facesResponse =
 rekClient.indexFaces(facesRequest);
            System.out.println("Results for the image");
            System.out.println("\n Faces indexed:");
            List<FaceRecord> faceRecords = facesResponse.faceRecords();
            for (FaceRecord faceRecord : faceRecords) {
                System.out.println("  Face ID: " + faceRecord.face().faceId());
                System.out.println("  Location:" +
 faceRecord.faceDetail().boundingBox().toString());
            }

            List<UnindexedFace> unindexedFaces = facesResponse.unindexedFaces();
            System.out.println("Faces not indexed:");
            for (UnindexedFace unindexedFace : unindexedFaces) {
                System.out.println("  Location:" +
 unindexedFace.faceDetail().boundingBox().toString());
                System.out.println("  Reasons:");
                for (Reason reason : unindexedFace.reasons()) {
                    System.out.println("Reason:  " + reason);
                }
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte IndexFacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addToCollection(collectionIdVal: String?, sourceImage: String) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = IndexFacesRequest {
        collectionId = collectionIdVal
        image = souImage
        maxFaces = 1
        qualityFilter = QualityFilter.Auto
        detectionAttributes = listOf(Attribute.Default)
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val facesResponse = rekClient.indexFaces(request)

        // Display the results.
        println("Results for the image")
        println("\n Faces indexed:")
        facesResponse.faceRecords?.forEach { faceRecord ->
            println("Face ID: ${faceRecord.face?.faceId}")
            println("Location: ${faceRecord.faceDetail?.boundingBox}")
        }

        println("Faces not indexed:")
        facesResponse.unindexedFaces?.forEach { unindexedFace ->
            println("Location: ${unindexedFace.faceDetail?.boundingBox}")
            println("Reasons:")

            unindexedFace.reasons?.forEach { reason ->
                println("Reason:  $reason")
```

```
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a IndexFacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
```

```
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def index_faces(self, image, max_faces):
        """
        Finds faces in the specified image, indexes them, and stores them in the
        collection.

        :param image: The image to index.
        :param max_faces: The maximum number of faces to index.
        :return: A tuple. The first element is a list of indexed faces.
                 The second element is a list of faces that couldn't be indexed.
        """
        try:
            response = self.rekognition_client.index_faces(
                CollectionId=self.collection_id,
                Image=image.image,
                ExternalImageId=image.image_name,
                MaxFaces=max_faces,
                DetectionAttributes=["ALL"],
            )
            indexed_faces = [
                RekognitionFace({**face["Face"], **face["FaceDetail"]})
                for face in response["FaceRecords"]
            ]
            unindexed_faces = [
                RekognitionFace(face["FaceDetail"])
                for face in response["UnindexedFaces"]
            ]
            logger.info(
                "Indexed %s faces in %s. Could not index %s faces.",
                len(indexed_faces),
                image.image_name,
                len(unindexed_faces),
```

```
            )
        except ClientError:
            logger.exception("Couldn't index faces in image %s.",
image.image_name)
            raise
        else:
            return indexed_faces, unindexed_faces
```

- Para obter detalhes da API, consulte a IndexFacesReferência da API AWSSDK for Python (Boto3).

Liste uma coleção do Amazon Rekognition usando um SDK da AWS.

Os exemplos de código a seguir mostram como listar as coleções do Amazon Rekognition.

Para obter mais informações, consulte Listar coleções.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses Amazon Rekognition to list the collection IDs in the
/// current account.
/// </summary>
public class ListCollections
{
    public static async Task Main()
```

```
        {
            var rekognitionClient = new AmazonRekognitionClient();

            Console.WriteLine("Listing collections");
            int limit = 10;

            var listCollectionsRequest = new ListCollectionsRequest
            {
                MaxResults = limit,
            };

            var listCollectionsResponse = new ListCollectionsResponse();

            do
            {
                if (listCollectionsResponse is not null)
                {
                    listCollectionsRequest.NextToken =
listCollectionsResponse.NextToken;
                }

                listCollectionsResponse = await
rekognitionClient.ListCollectionsAsync(listCollectionsRequest);

                listCollectionsResponse.CollectionIds.ForEach(id =>
                {
                    Console.WriteLine(id);
                });
            }
            while (listCollectionsResponse.NextToken is not null);
        }
    }
```

- Para obter detalhes da API, consulte ListCollectionsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar as coleções disponíveis

O comando `list-collections` a seguir lista as coleções disponíveis na conta da AWS.

```
aws rekognition list-collections
```

Saída:

```
{
    "FaceModelVersions": [
        "2.0",
        "3.0",
        "3.0",
        "3.0",
        "4.0",
        "1.0",
        "3.0",
        "4.0",
        "4.0",
        "4.0"
    ],
    "CollectionIds": [
        "MyCollection1",
        "MyCollection2",
        "MyCollection3",
        "MyCollection4",
        "MyCollection5",
        "MyCollection6",
        "MyCollection7",
        "MyCollection8",
        "MyCollection9",
        "MyCollection10"
    ]
}
```

Para obter mais informações, consulte Listar coleções no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte ListCollectionsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.ListCollectionsRequest;
import software.amazon.awssdk.services.rekognition.model.ListCollectionsResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListCollections {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Listing collections");
        listAllCollections(rekClient);
        rekClient.close();
    }

    public static void listAllCollections(RekognitionClient rekClient) {
        try {
            ListCollectionsRequest listCollectionsRequest =
 ListCollectionsRequest.builder()
```

```
                    .maxResults(10)
                    .build();

            ListCollectionsResponse response =
 rekClient.listCollections(listCollectionsRequest);
            List<String> collectionIds = response.collectionIds();
            for (String resultId : collectionIds) {
                System.out.println(resultId);
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListCollectionsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllCollections() {

    val request = ListCollectionsRequest {
        maxResults = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.listCollections(request)
        response.collectionIds?.forEach { resultId ->
            println(resultId)
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte a ListCollectionsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollectionManager:
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition
 API.
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def list_collections(self, max_results):
        """
        Lists collections for the current account.

        :param max_results: The maximum number of collections to return.
        :return: The list of collections for the current account.
        """
        try:
```

```
            response =
self.rekognition_client.list_collections(MaxResults=max_results)
            collections = [
                RekognitionCollection({"CollectionId": col_id},
self.rekognition_client)
                for col_id in response["CollectionIds"]
            ]
        except ClientError:
            logger.exception("Couldn't list collections.")
            raise
        else:
            return collections
```

- Para obter detalhes da API, consulte a ListCollectionsReferência da API AWSSDK for Python (Boto3).

Liste faces em uma coleção do Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como listar faces em uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Listar faces em uma coleção.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
```

```
    /// Uses the Amazon Rekognition Service to retrieve the list of faces
    /// stored in a collection.
    /// </summary>
    public class ListFaces
    {
        public static async Task Main()
        {
            string collectionId = "MyCollection2";

            var rekognitionClient = new AmazonRekognitionClient();

            var listFacesResponse = new ListFacesResponse();
            Console.WriteLine($"Faces in collection {collectionId}");

            var listFacesRequest = new ListFacesRequest
            {
                CollectionId = collectionId,
                MaxResults = 1,
            };

            do
            {
                listFacesResponse = await
rekognitionClient.ListFacesAsync(listFacesRequest);
                listFacesResponse.Faces.ForEach(face =>
                {
                    Console.WriteLine(face.FaceId);
                });

                listFacesRequest.NextToken = listFacesResponse.NextToken;
            }
            while (!string.IsNullOrEmpty(listFacesResponse.NextToken));
        }
    }
```

- Para obter detalhes da API, consulte ListFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar faces de uma coleção

O comando `list-faces` a seguir lista as faces na coleção especificada.

```
aws rekognition list-faces \
    --collection-id MyCollection
```

Saída:

```
{
    "FaceModelVersion": "3.0",
    "Faces": [
        {
            "BoundingBox": {
                "Width": 0.5216310024261475,
                "Top": 0.3256250023841858,
                "Left": 0.13394300639629364,
                "Height": 0.3918749988079071
            },
            "FaceId": "0040279c-0178-436e-b70a-e61b074e96b0",
            "ExternalImageId": "image1.jpg",
            "Confidence": 100.0,
            "ImageId": "f976e487-3719-5e2d-be8b-ea2724c26991"
        },
        {
            "BoundingBox": {
                "Width": 0.5074880123138428,
                "Top": 0.3774999976158142,
                "Left": 0.18302799761295319,
                "Height": 0.3812499940395355
            },
            "FaceId": "086261e8-6deb-4bc0-ac73-ab22323cc38d",
            "ExternalImageId": "image2.jpg",
            "Confidence": 99.99930572509766,
            "ImageId": "ae1593b0-a8f6-5e24-a306-abf529e276fa"
        },
        {
            "BoundingBox": {
                "Width": 0.5574039816856384,
```

```
                "Top": 0.37187498807907104,
                "Left": 0.14559100568294525,
                "Height": 0.4181250035762787
            },
            "FaceId": "11c4bd3c-19c5-4eb8-aecc-24feb93a26e1",
            "ExternalImageId": "image3.jpg",
            "Confidence": 99.99960327148438,
            "ImageId": "80739b4d-883f-5b78-97cf-5124038e26b9"
        },
        {
            "BoundingBox": {
                "Width": 0.18562500178813934,
                "Top": 0.1618019938468933,
                "Left": 0.5575000047683716,
                "Height": 0.24770599603652954
            },
            "FaceId": "13692fe4-990a-4679-b14a-5ac23d135eab",
            "ExternalImageId": "image4.jpg",
            "Confidence": 99.99340057373047,
            "ImageId": "8df18239-9ad1-5acd-a46a-6581ff98f51b"
        },
        {
            "BoundingBox": {
                "Width": 0.5307819843292236,
                "Top": 0.2862499952316284,
                "Left": 0.1564060002565384,
                "Height": 0.3987500071525574
            },
            "FaceId": "2eb5f3fd-e2a9-4b1c-a89f-afa0a518fe06",
            "ExternalImageId": "image5.jpg",
            "Confidence": 99.99970245361328,
            "ImageId": "3c314792-197d-528d-bbb6-798ed012c150"
        },
        {
            "BoundingBox": {
                "Width": 0.5773710012435913,
                "Top": 0.34437501430511475,
                "Left": 0.12396000325679779,
                "Height": 0.4337500035762787
            },
            "FaceId": "57189455-42b0-4839-a86c-abda48b13174",
            "ExternalImageId": "image6.jpg",
            "Confidence": 100.0,
            "ImageId": "0aff2f37-e7a2-5dbc-a3a3-4ef6ec18eaa0"
```

```
        },
        {
            "BoundingBox": {
                "Width": 0.5349419713020325,
                "Top": 0.29124999046325684,
                "Left": 0.16389399766921997,
                "Height": 0.40187498927116394
            },
            "FaceId": "745f7509-b1fa-44e0-8b95-367b1359638a",
            "ExternalImageId": "image7.jpg",
            "Confidence": 99.99979400634766,
            "ImageId": "67a34327-48d1-5179-b042-01e52ccfeada"
        },
        {
            "BoundingBox": {
                "Width": 0.41499999165534973,
                "Top": 0.09187500178813934,
                "Left": 0.28083300590515137,
                "Height": 0.3112500011920929
            },
            "FaceId": "8d3cfc70-4ba8-4b36-9644-90fba29c2dac",
            "ExternalImageId": "image8.jpg",
            "Confidence": 99.99769592285156,
            "ImageId": "a294da46-2cb1-5cc4-9045-61d7ca567662"
        },
        {
            "BoundingBox": {
                "Width": 0.48166701197624207,
                "Top": 0.20999999344348907,
                "Left": 0.21250000596046448,
                "Height": 0.36125001311302185
            },
            "FaceId": "bd4ceb4d-9acc-4ab7-8ef8-1c2d2ba0a66a",
            "ExternalImageId": "image9.jpg",
            "Confidence": 99.99949645996094,
            "ImageId": "5e1a7588-e5a0-5ee3-bd00-c642518dfe3a"
        },
        {
            "BoundingBox": {
                "Width": 0.18562500178813934,
                "Top": 0.1618019938468933,
                "Left": 0.5575000047683716,
                "Height": 0.24770599603652954
            },
```

```
            "FaceId": "ce7ed422-2132-4a11-ab14-06c5c410f29f",
            "ExternalImageId": "image10.jpg",
            "Confidence": 99.99340057373047,
            "ImageId": "8d67061e-90d2-598f-9fbd-29c8497039c0"
        }
    ]
}
```

Para obter mais informações, consulte Listar faces em uma coleção no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte ListFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.Face;
import software.amazon.awssdk.services.rekognition.model.ListFacesRequest;
import software.amazon.awssdk.services.rekognition.model.ListFacesResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListFacesInCollection {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:    <collectionId>

                Where:
                   collectionId - The name of the collection.\s
                """;

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Faces in collection " + collectionId);
        listFacesCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void listFacesCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            ListFacesRequest facesRequest = ListFacesRequest.builder()
                    .collectionId(collectionId)
                    .maxResults(10)
                    .build();

            ListFacesResponse facesResponse = rekClient.listFaces(facesRequest);
            List<Face> faces = facesResponse.faces();
            for (Face face : faces) {
                System.out.println("Confidence level there is a face: " +
 face.confidence());
                System.out.println("The face Id value is " + face.faceId());
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte ListFacesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listFacesCollection(collectionIdVal: String?) {

    val request = ListFacesRequest {
        collectionId = collectionIdVal
        maxResults = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.listFaces(request)
        response.faces?.forEach { face ->
            println("Confidence level there is a face: ${face.confidence}")
            println("The face Id value is ${face.faceId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListFacesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
```

```
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def list_faces(self, max_results):
        """
        Lists the faces currently indexed in the collection.

        :param max_results: The maximum number of faces to return.
        :return: The list of faces in the collection.
        """
        try:
            response = self.rekognition_client.list_faces(
                CollectionId=self.collection_id, MaxResults=max_results
            )
            faces = [RekognitionFace(face) for face in response["Faces"]]
            logger.info(
                "Found %s faces in collection %s.", len(faces),
self.collection_id
            )
        except ClientError:
            logger.exception(
                "Couldn't list faces in collection %s.", self.collection_id
            )
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a ListFacesReferência da API AWSSDK for Python (Boto3).

Reconheça celebridades em uma imagem com o Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como reconhecer celebridades em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Reconhecer celebridades em uma imagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Shows how to use Amazon Rekognition to identify celebrities in a photo.
/// </summary>
public class CelebritiesInImage
{
    public static async Task Main(string[] args)
    {
        string photo = "moviestars.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        var recognizeCelebritiesRequest = new RecognizeCelebritiesRequest();

        var img = new Amazon.Rekognition.Model.Image();
        byte[] data = null;
        try
        {
            using var fs = new FileStream(photo, FileMode.Open,
FileAccess.Read);
            data = new byte[fs.Length];
            fs.Read(data, 0, (int)fs.Length);
        }
        catch (Exception)
        {
            Console.WriteLine($"Failed to load file {photo}");
            return;
```

```
            }

            img.Bytes = new MemoryStream(data);
            recognizeCelebritiesRequest.Image = img;

            Console.WriteLine($"Looking for celebrities in image {photo}\n");

            var recognizeCelebritiesResponse = await
rekognitionClient.RecognizeCelebritiesAsync(recognizeCelebritiesRequest);


Console.WriteLine($"{recognizeCelebritiesResponse.CelebrityFaces.Count}
celebrity(s) were recognized.\n");
            recognizeCelebritiesResponse.CelebrityFaces.ForEach(celeb =>
            {
                Console.WriteLine($"Celebrity recognized: {celeb.Name}");
                Console.WriteLine($"Celebrity ID: {celeb.Id}");
                BoundingBox boundingBox = celeb.Face.BoundingBox;
                Console.WriteLine($"position: {boundingBox.Left}
{boundingBox.Top}");
                Console.WriteLine("Further information (if available):");
                celeb.Urls.ForEach(url =>
                {
                    Console.WriteLine(url);
                });
            });


Console.WriteLine($"{recognizeCelebritiesResponse.UnrecognizedFaces.Count}
face(s) were unrecognized.");
        }
    }
```

- Para obter detalhes da API, consulte RecognizeCelebritiesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como reconhecer celebridades em uma imagem

O seguinte comando `recognize-celebrities` reconhece celebridades na imagem especificada armazenada em um bucket do Amazon S3:

```
aws rekognition recognize-celebrities \
    --image "S3Object={Bucket=MyImageS3Bucket,Name=moviestars.jpg}"
```

Saída:

```
{
    "UnrecognizedFaces": [
        {
            "BoundingBox": {
                "Width": 0.14416666328907013,
                "Top": 0.07777778059244156,
                "Left": 0.625,
                "Height": 0.2746031880378723
            },
            "Confidence": 99.9990234375,
            "Pose": {
                "Yaw": 10.80408763885498,
                "Roll": -12.761146545410156,
                "Pitch": 10.96889877319336
            },
            "Quality": {
                "Sharpness": 94.1185531616211,
                "Brightness": 79.18367004394531
            },
            "Landmarks": [
                {
                    "Y": 0.18220913410186768,
                    "X": 0.6702951788902283,
                    "Type": "eyeLeft"
                },
                {
                    "Y": 0.16337193548679352,
                    "X": 0.7188183665275574,
                    "Type": "eyeRight"
                },
                {
                    "Y": 0.20739148557186127,
                    "X": 0.7055801749229431,
                    "Type": "nose"
                },
```

```
                {
                    "Y": 0.2889308035373688,
                    "X": 0.687512218952179,
                    "Type": "mouthLeft"
                },
                {
                    "Y": 0.2706988751888275,
                    "X": 0.7250053286552429,
                    "Type": "mouthRight"
                }
            ]
        }
    ],
    "CelebrityFaces": [
        {
            "MatchConfidence": 100.0,
            "Face": {
                "BoundingBox": {
                    "Width": 0.14000000059604645,
                    "Top": 0.1190476194024086,
                    "Left": 0.82833331823349,
                    "Height": 0.2666666805744171
                },
                "Confidence": 99.99359130859375,
                "Pose": {
                    "Yaw": -10.509642601013184,
                    "Roll": -14.51749324798584,
                    "Pitch": 13.799399375915527
                },
                "Quality": {
                    "Sharpness": 78.74752044677734,
                    "Brightness": 42.201324462890625
                },
                "Landmarks": [
                    {
                        "Y": 0.2290833294391632,
                        "X": 0.8709492087364197,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.20639978349208832,
                        "X": 0.9153988361358643,
                        "Type": "eyeRight"
                    },
```

```
                    {
                        "Y": 0.25417643785476685,
                        "X": 0.8907724022865295,
                        "Type": "nose"
                    },
                    {
                        "Y": 0.32729196548461914,
                        "X": 0.8876466155052185,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.3115464746952057,
                        "X": 0.9238573312759399,
                        "Type": "mouthRight"
                    }
                ]
            },
            "Name": "Celeb A",
            "Urls": [
                "www.imdb.com/name/aaaaaaaaa"
            ],
            "Id": "1111111"
        },
        {
            "MatchConfidence": 97.0,
            "Face": {
                "BoundingBox": {
                    "Width": 0.13333334028720856,
                    "Top": 0.2492063492536544 8,
                    "Left": 0.4449999928474426,
                    "Height": 0.2539682686328888
                },
                "Confidence": 99.99979400634766,
                "Pose": {
                    "Yaw": 6.557040691375732,
                    "Roll": -7.316643714904785,
                    "Pitch": 9.272967338562012
                },
                "Quality": {
                    "Sharpness": 83.23492431640625,
                    "Brightness": 78.83267974853516
                },
                "Landmarks": [
                    {
```

```
                        "Y": 0.3625510632991791,
                        "X": 0.48898839950561523,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.35366007685661316,
                        "X": 0.5313721299171448,
                        "Type": "eyeRight"
                    },
                    {
                        "Y": 0.3894785940647125,
                        "X": 0.5173314809799194,
                        "Type": "nose"
                    },
                    {
                        "Y": 0.44889405369758606,
                        "X": 0.5020005702972412,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.4408611059188843,
                        "X": 0.5351271629333496,
                        "Type": "mouthRight"
                    }
                ]
            },
            "Name": "Celeb B",
            "Urls": [
                "www.imdb.com/name/bbbbbbbbb"
            ],
            "Id": "2222222"
        },
        {
            "MatchConfidence": 100.0,
            "Face": {
                "BoundingBox": {
                    "Width": 0.12416666746139526,
                    "Top": 0.2968254089355469,
                    "Left": 0.2150000035762787,
                    "Height": 0.23650793731212616
                },
                "Confidence": 99.99958801269531,
                "Pose": {
                    "Yaw": 7.801797866821289,
```

```
                    "Roll": -8.326810836791992,
                    "Pitch": 7.844768047332764
                },
                "Quality": {
                    "Sharpness": 86.93206024169922,
                    "Brightness": 79.81291198730469
                },
                "Landmarks": [
                    {
                        "Y": 0.4027804136276245,
                        "X": 0.2575301229953766,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.3934555947780609,
                        "X": 0.2956969439983368,
                        "Type": "eyeRight"
                    },
                    {
                        "Y": 0.4309830069541931,
                        "X": 0.2837020754814148,
                        "Type": "nose"
                    },
                    {
                        "Y": 0.48186683654785156,
                        "X": 0.26812544465065,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.47338807582855225,
                        "X": 0.29905644059181213,
                        "Type": "mouthRight"
                    }
                ]
            },
            "Name": "Celeb C",
            "Urls": [
                "www.imdb.com/name/ccccccccc"
            ],
            "Id": "3333333"
        },
        {
            "MatchConfidence": 97.0,
            "Face": {
```

```
                "BoundingBox": {
                    "Width": 0.11916666477918625,
                    "Top": 0.3698412775993347,
                    "Left": 0.008333333767950535,
                    "Height": 0.22698412835597992
                },
                "Confidence": 99.99999237060547,
                "Pose": {
                    "Yaw": 16.38478660583496,
                    "Roll": -1.0260354280471802,
                    "Pitch": 5.975185394287109
                },
                "Quality": {
                    "Sharpness": 83.23492431640625,
                    "Brightness": 61.408443450927734
                },
                "Landmarks": [
                    {
                        "Y": 0.4632347822189331,
                        "X": 0.049406956881284714,
                        "Type": "eyeLeft"
                    },
                    {
                        "Y": 0.46388113498687744,
                        "X": 0.08722897619009018,
                        "Type": "eyeRight"
                    },
                    {
                        "Y": 0.5020678639411926,
                        "X": 0.0758260041475296,
                        "Type": "nose"
                    },
                    {
                        "Y": 0.544157862663269,
                        "X": 0.054029736667871475,
                        "Type": "mouthLeft"
                    },
                    {
                        "Y": 0.5463630557060242,
                        "X": 0.08464983850717545,
                        "Type": "mouthRight"
                    }
                ]
            },
```

```
            "Name": "Celeb D",
            "Urls": [
                "www.imdb.com/name/ddddddddd"
            ],
            "Id": "4444444"
        }
    ]
}
```

Para obter mais informações, consulte Reconhecer celebridades em uma imagem no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte RecognizeCelebritiesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.core.SdkBytes;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;
import
 software.amazon.awssdk.services.rekognition.model.RecognizeCelebritiesRequest;
import
 software.amazon.awssdk.services.rekognition.model.RecognizeCelebritiesResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.Celebrity;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class RecognizeCelebrities {
    public static void main(String[] args) {
        final String usage = """
                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Locating celebrities in " + sourceImage);
        recognizeAllCelebrities(rekClient, sourceImage);
        rekClient.close();
    }

    public static void recognizeAllCelebrities(RekognitionClient rekClient,
 String sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            RecognizeCelebritiesRequest request =
 RecognizeCelebritiesRequest.builder()
```

```
                    .image(souImage)
                    .build();

            RecognizeCelebritiesResponse result =
 rekClient.recognizeCelebrities(request);
            List<Celebrity> celebs = result.celebrityFaces();
            System.out.println(celebs.size() + " celebrity(s) were recognized.
\n");
            for (Celebrity celebrity : celebs) {
                System.out.println("Celebrity recognized: " + celebrity.name());
                System.out.println("Celebrity ID: " + celebrity.id());

                System.out.println("Further information (if available):");
                for (String url : celebrity.urls()) {
                    System.out.println(url);
                }
                System.out.println();
            }
            System.out.println(result.unrecognizedFaces().size() + " face(s) were
 unrecognized.");

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte RecognizeCelebritiesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun recognizeAllCelebrities(sourceImage: String?) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = RecognizeCelebritiesRequest {
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.recognizeCelebrities(request)
        response.celebrityFaces?.forEach { celebrity ->
            println("Celebrity recognized: ${celebrity.name}")
            println("Celebrity ID:${celebrity.id}")
            println("Further information (if available):")
            celebrity.urls?.forEach { url ->
                println(url)
            }
        }
        println("${response.unrecognizedFaces?.size} face(s) were unrecognized.")
    }
}
```

- Para obter detalhes da API, consulte a RecognizeCelebritiesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
```

```
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def recognize_celebrities(self):
        """
        Detects celebrities in the image.

        :return: A tuple. The first element is the list of celebrities found in
                 the image. The second element is the list of faces that were
                 detected but did not match any known celebrities.
        """
        try:
            response =
self.rekognition_client.recognize_celebrities(Image=self.image)
            celebrities = [
                RekognitionCelebrity(celeb) for celeb in
response["CelebrityFaces"]
            ]
            other_faces = [
                RekognitionFace(face) for face in response["UnrecognizedFaces"]
            ]
            logger.info(
                "Found %s celebrities and %s other faces in %s.",
                len(celebrities),
                len(other_faces),
                self.image_name,
            )
        except ClientError:
            logger.exception("Couldn't detect celebrities in %s.",
self.image_name)
```

```
            raise
        else:
            return celebrities, other_faces
```

- Para obter detalhes da API, consulte a RecognizeCelebritiesReferência da API AWSSDK for Python (Boto3).

Pesquise faces em uma coleção do Amazon Rekognition usando um SDK da AWS

Os exemplos de código a seguir mostram como pesquisar rostos em uma coleção do Amazon Rekognition que correspondam a outro rosto da coleção.

Para obter mais informações, consulte Pesquisar uma face (face ID).

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to find faces in an image that
/// match the face Id provided in the method request.
/// </summary>
public class SearchFacesMatchingId
{
    public static async Task Main()
    {
        string collectionId = "MyCollection";
```

```
            string faceId = "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx";

            var rekognitionClient = new AmazonRekognitionClient();

            // Search collection for faces matching the face id.
            var searchFacesRequest = new SearchFacesRequest
            {
                CollectionId = collectionId,
                FaceId = faceId,
                FaceMatchThreshold = 70F,
                MaxFaces = 2,
            };

            SearchFacesResponse searchFacesResponse = await
 rekognitionClient.SearchFacesAsync(searchFacesRequest);

            Console.WriteLine("Face matching faceId " + faceId);

            Console.WriteLine("Matche(s): ");
            searchFacesResponse.FaceMatches.ForEach(face =>
            {
                Console.WriteLine($"FaceId: {face.Face.FaceId} Similarity:
 {face.Similarity}");
            });
        }
    }
```

- Para obter detalhes da API, consulte SearchFacesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como pesquisar faces em uma coleção que corresponda a um ID facial.

O comando `search-faces` a seguir pesquisa faces em uma coleção que correspondem ao ID facial especificado.

```
aws rekognition search-faces \
    --face-id 8d3cfc70-4ba8-4b36-9644-90fba29c2dac \
```

```
    --collection-id MyCollection
```

Saída:

```
{
    "SearchedFaceId": "8d3cfc70-4ba8-4b36-9644-90fba29c2dac",
    "FaceModelVersion": "3.0",
    "FaceMatches": [
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.48166701197624207,
                    "Top": 0.20999999344348907,
                    "Left": 0.21250000596046448,
                    "Height": 0.36125001311302185
                },
                "FaceId": "bd4ceb4d-9acc-4ab7-8ef8-1c2d2ba0a66a",
                "ExternalImageId": "image1.jpg",
                "Confidence": 99.99949645996094,
                "ImageId": "5e1a7588-e5a0-5ee3-bd00-c642518dfe3a"
            },
            "Similarity": 99.30997467041016
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.18562500178813934,
                    "Top": 0.1618019938468933,
                    "Left": 0.5575000047683716,
                    "Height": 0.24770599603652954
                },
                "FaceId": "ce7ed422-2132-4a11-ab14-06c5c410f29f",
                "ExternalImageId": "example-image.jpg",
                "Confidence": 99.99340057373047,
                "ImageId": "8d67061e-90d2-598f-9fbd-29c8497039c0"
            },
            "Similarity": 99.24862670898438
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.18562500178813934,
                    "Top": 0.1618019938468933,
```

```
                "Left": 0.5575000047683716,
                "Height": 0.24770599603652954
            },
            "FaceId": "13692fe4-990a-4679-b14a-5ac23d135eab",
            "ExternalImageId": "image3.jpg",
            "Confidence": 99.99340057373047,
            "ImageId": "8df18239-9ad1-5acd-a46a-6581ff98f51b"
        },
        "Similarity": 99.24862670898438
    },
    {
        "Face": {
            "BoundingBox": {
                "Width": 0.5349419713020325,
                "Top": 0.29124999046325684,
                "Left": 0.16389399766921997,
                "Height": 0.40187498927116394
            },
            "FaceId": "745f7509-b1fa-44e0-8b95-367b1359638a",
            "ExternalImageId": "image9.jpg",
            "Confidence": 99.99979400634766,
            "ImageId": "67a34327-48d1-5179-b042-01e52ccfeada"
        },
        "Similarity": 96.73158264160156
    },
    {
        "Face": {
            "BoundingBox": {
                "Width": 0.5307819843292236,
                "Top": 0.2862499952316284,
                "Left": 0.1564060002565384,
                "Height": 0.3987500071525574
            },
            "FaceId": "2eb5f3fd-e2a9-4b1c-a89f-afa0a518fe06",
            "ExternalImageId": "image10.jpg",
            "Confidence": 99.99970245361328,
            "ImageId": "3c314792-197d-528d-bbb6-798ed012c150"
        },
        "Similarity": 96.48291015625
    },
    {
        "Face": {
            "BoundingBox": {
                "Width": 0.5074880123138428,
```

```
                    "Top": 0.3774999976158142,
                    "Left": 0.18302799761295319,
                    "Height": 0.3812499940395355
                },
                "FaceId": "086261e8-6deb-4bc0-ac73-ab22323cc38d",
                "ExternalImageId": "image6.jpg",
                "Confidence": 99.99930572509766,
                "ImageId": "ae1593b0-a8f6-5e24-a306-abf529e276fa"
            },
            "Similarity": 96.43287658691406
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5574039816856384,
                    "Top": 0.37187498807907104,
                    "Left": 0.14559100568294525,
                    "Height": 0.4181250035762787
                },
                "FaceId": "11c4bd3c-19c5-4eb8-aecc-24feb93a26e1",
                "ExternalImageId": "image5.jpg",
                "Confidence": 99.99960327148438,
                "ImageId": "80739b4d-883f-5b78-97cf-5124038e26b9"
            },
            "Similarity": 95.25305938720703
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5773710012435913,
                    "Top": 0.34437501430511475,
                    "Left": 0.12396000325679779,
                    "Height": 0.4337500035762787
                },
                "FaceId": "57189455-42b0-4839-a86c-abda48b13174",
                "ExternalImageId": "image8.jpg",
                "Confidence": 100.0,
                "ImageId": "0aff2f37-e7a2-5dbc-a3a3-4ef6ec18eaa0"
            },
            "Similarity": 95.22837829589844
        }
    ]
}
```

Para obter mais informações, consulte Procurando uma face com um ID facial no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte SearchFacesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.SearchFacesByImageRequest;
import software.amazon.awssdk.services.rekognition.model.Image;
import
 software.amazon.awssdk.services.rekognition.model.SearchFacesByImageResponse;
import software.amazon.awssdk.services.rekognition.model.FaceMatch;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SearchFaceMatchingImageCollection {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:    <collectionId> <sourceImage>

                Where:
                   collectionId - The id of the collection. \s
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s

                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String sourceImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Searching for a face in a collections");
        searchFaceInCollection(rekClient, collectionId, sourceImage);
        rekClient.close();
    }

    public static void searchFaceInCollection(RekognitionClient rekClient, String
 collectionId, String sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(new
 File(sourceImage));
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            SearchFacesByImageRequest facesByImageRequest =
 SearchFacesByImageRequest.builder()
                    .image(souImage)
                    .maxFaces(10)
                    .faceMatchThreshold(70F)
                    .collectionId(collectionId)
```

```
                    .build();

            SearchFacesByImageResponse imageResponse =
 rekClient.searchFacesByImage(facesByImageRequest);
            System.out.println("Faces matching in the collection");
            List<FaceMatch> faceImageMatches = imageResponse.faceMatches();
            for (FaceMatch face : faceImageMatches) {
                System.out.println("The similarity level is  " +
 face.similarity());
                System.out.println();
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SearchFacesa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
```

```
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def search_faces(self, face_id, threshold, max_faces):
        """
        Searches for faces in the collection that match another face from the
        collection.

        :param face_id: The ID of the face in the collection to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: The list of matching faces found in the collection. This list
does
                 not contain the face specified by `face_id`.
        """
        try:
            response = self.rekognition_client.search_faces(
```

```
                CollectionId=self.collection_id,
                FaceId=face_id,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            faces = [RekognitionFace(face["Face"]) for face in
response["FaceMatches"]]
            logger.info(
                "Found %s faces in %s that match %s.",
                len(faces),
                self.collection_id,
                face_id,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                face_id,
            )
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a SearchFacesReferência da API AWSSDK for Python (Boto3).

Pesquise rostos em uma coleção do Amazon Rekognition em comparação com uma imagem de referência usando um SDK da AWS

Os exemplos de código a seguir mostram como pesquisar faces em uma coleção do Amazon Rekognition comparando com uma imagem de referência.

Para obter mais informações, consulte Pesquisar uma face (imagem).

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to search for images matching those
/// in a collection.
/// </summary>
public class SearchFacesMatchingImage
{
    public static async Task Main()
    {
        string collectionId = "MyCollection";
        string bucket = "bucket";
        string photo = "input.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        // Get an image object from S3 bucket.
        var image = new Image()
        {
            S3Object = new S3Object()
            {
                Bucket = bucket,
                Name = photo,
            },
        };

        var searchFacesByImageRequest = new SearchFacesByImageRequest()
        {
            CollectionId = collectionId,
```

```
                Image = image,
                FaceMatchThreshold = 70F,
                MaxFaces = 2,
            };

            SearchFacesByImageResponse searchFacesByImageResponse = await
 rekognitionClient.SearchFacesByImageAsync(searchFacesByImageRequest);

            Console.WriteLine("Faces matching largest face in image from " +
 photo);
            searchFacesByImageResponse.FaceMatches.ForEach(face =>
            {
                Console.WriteLine($"FaceId: {face.Face.FaceId}, Similarity:
 {face.Similarity}");
            });
        }
    }
```

- Para obter detalhes da API, consulte SearchFacesByImagea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como pesquisar faces em uma coleção que corresponda à maior face em uma imagem.

O seguinte comando `search-faces-by-image` pesquisa faces em uma coleção que corresponda à maior face na imagem especificada:

```
aws rekognition search-faces-by-image \
    --image '{"S3Object":
{"Bucket":"MyImageS3Bucket","Name":"ExamplePerson.jpg"}}' \
    --collection-id MyFaceImageCollection

{
    "SearchedFaceBoundingBox": {
        "Width": 0.18562500178813934,
        "Top": 0.1618015021085739,
        "Left": 0.5575000047683716,
        "Height": 0.24770642817020416
```

```
    },
    "SearchedFaceConfidence": 99.993408203125,
    "FaceMatches": [
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.18562500178813934,
                    "Top": 0.1618019938468933,
                    "Left": 0.5575000047683716,
                    "Height": 0.24770599603652954
                },
                "FaceId": "ce7ed422-2132-4a11-ab14-06c5c410f29f",
                "ExternalImageId": "example-image.jpg",
                "Confidence": 99.99340057373047,
                "ImageId": "8d67061e-90d2-598f-9fbd-29c8497039c0"
            },
            "Similarity": 99.97913360595703
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.18562500178813934,
                    "Top": 0.1618019938468933,
                    "Left": 0.5575000047683716,
                    "Height": 0.24770599603652954
                },
                "FaceId": "13692fe4-990a-4679-b14a-5ac23d135eab",
                "ExternalImageId": "image3.jpg",
                "Confidence": 99.99340057373047,
                "ImageId": "8df18239-9ad1-5acd-a46a-6581ff98f51b"
            },
            "Similarity": 99.97913360595703
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.41499999165534973,
                    "Top": 0.09187500178813934,
                    "Left": 0.28083300590515137,
                    "Height": 0.3112500011920929
                },
                "FaceId": "8d3cfc70-4ba8-4b36-9644-90fba29c2dac",
                "ExternalImageId": "image2.jpg",
                "Confidence": 99.99769592285156,
```

```
                "ImageId": "a294da46-2cb1-5cc4-9045-61d7ca567662"
            },
            "Similarity": 99.18069458007812
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.48166701197624207,
                    "Top": 0.20999999344348907,
                    "Left": 0.21250000596046448,
                    "Height": 0.36125001311302185
                },
                "FaceId": "bd4ceb4d-9acc-4ab7-8ef8-1c2d2ba0a66a",
                "ExternalImageId": "image1.jpg",
                "Confidence": 99.99949645996094,
                "ImageId": "5e1a7588-e5a0-5ee3-bd00-c642518dfe3a"
            },
            "Similarity": 98.66607666015625
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5349419713020325,
                    "Top": 0.29124999046325684,
                    "Left": 0.16389399766921997,
                    "Height": 0.40187498927116394
                },
                "FaceId": "745f7509-b1fa-44e0-8b95-367b1359638a",
                "ExternalImageId": "image9.jpg",
                "Confidence": 99.99979400634766,
                "ImageId": "67a34327-48d1-5179-b042-01e52ccfeada"
            },
            "Similarity": 98.24278259277344
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5307819843292236,
                    "Top": 0.2862499952316284,
                    "Left": 0.1564060002565384,
                    "Height": 0.3987500071525574
                },
                "FaceId": "2eb5f3fd-e2a9-4b1c-a89f-afa0a518fe06",
                "ExternalImageId": "image10.jpg",
```

```
                "Confidence": 99.99970245361328,
                "ImageId": "3c314792-197d-528d-bbb6-798ed012c150"
            },
            "Similarity": 98.10665893554688
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5074880123138428,
                    "Top": 0.3774999976158142,
                    "Left": 0.18302799761295319,
                    "Height": 0.3812499940395355
                },
                "FaceId": "086261e8-6deb-4bc0-ac73-ab22323cc38d",
                "ExternalImageId": "image6.jpg",
                "Confidence": 99.99930572509766,
                "ImageId": "ae1593b0-a8f6-5e24-a306-abf529e276fa"
            },
            "Similarity": 98.10526275634766
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5574039816856384,
                    "Top": 0.37187498807907104,
                    "Left": 0.14559100568294525,
                    "Height": 0.4181250035762787
                },
                "FaceId": "11c4bd3c-19c5-4eb8-aecc-24feb93a26e1",
                "ExternalImageId": "image5.jpg",
                "Confidence": 99.99960327148438,
                "ImageId": "80739b4d-883f-5b78-97cf-5124038e26b9"
            },
            "Similarity": 97.94659423828125
        },
        {
            "Face": {
                "BoundingBox": {
                    "Width": 0.5773710012435913,
                    "Top": 0.34437501430511475,
                    "Left": 0.12396000325679779,
                    "Height": 0.4337500035762787
                },
                "FaceId": "57189455-42b0-4839-a86c-abda48b13174",
```

```
                "ExternalImageId": "image8.jpg",
                "Confidence": 100.0,
                "ImageId": "0aff2f37-e7a2-5dbc-a3a3-4ef6ec18eaa0"
            },
            "Similarity": 97.93476867675781
        }
    ],
    "FaceModelVersion": "3.0"
}
```

Para obter mais informações, consulte Procurando um rosto com uma imagem no Guia do desenvolvedor do Amazon Rekognition.

- Para obter detalhes da API, consulte SearchFacesByImageem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.SearchFacesRequest;
import software.amazon.awssdk.services.rekognition.model.SearchFacesResponse;
import software.amazon.awssdk.services.rekognition.model.FaceMatch;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
```

```
 */
public class SearchFaceMatchingIdCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId> <sourceImage>

                Where:
                   collectionId - The id of the collection. \s
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String faceId = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Searching for a face in a collections");
        searchFacebyId(rekClient, collectionId, faceId);
        rekClient.close();
    }

    public static void searchFacebyId(RekognitionClient rekClient, String
 collectionId, String faceId) {
        try {
            SearchFacesRequest searchFacesRequest = SearchFacesRequest.builder()
                    .collectionId(collectionId)
                    .faceId(faceId)
                    .faceMatchThreshold(70F)
                    .maxFaces(2)
                    .build();

            SearchFacesResponse imageResponse =
 rekClient.searchFaces(searchFacesRequest);
            System.out.println("Faces matching in the collection");
            List<FaceMatch> faceImageMatches = imageResponse.faceMatches();
```

```
            for (FaceMatch face : faceImageMatches) {
                System.out.println("The similarity level is  " +
 face.similarity());
                System.out.println();
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SearchFacesByImagea Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
```

```
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def search_faces_by_image(self, image, threshold, max_faces):
        """
        Searches for faces in the collection that match the largest face in the
        reference image.

        :param image: The image that contains the reference face to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: A tuple. The first element is the face found in the reference
image.
                 The second element is the list of matching faces found in the
                 collection.
        """
        try:
            response = self.rekognition_client.search_faces_by_image(
                CollectionId=self.collection_id,
                Image=image.image,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
```

```
            image_face = RekognitionFace(
                {
                    "BoundingBox": response["SearchedFaceBoundingBox"],
                    "Confidence": response["SearchedFaceConfidence"],
                }
            )
            collection_faces = [
                RekognitionFace(face["Face"]) for face in response["FaceMatches"]
            ]
            logger.info(
                "Found %s faces in the collection that match the largest "
                "face in %s.",
                len(collection_faces),
                image.image_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                image.image_name,
            )
            raise
        else:
            return image_face, collection_faces
```

- Para obter detalhes da API, consulte a SearchFacesByImageReferência da API AWSSDK for Python (Boto3).

Cenários do Amazon Rekognition usando os AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Rekognition com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie uma coleção do Amazon Rekognition e encontre faces nela usando um AWS SDK

- Detecte e exiba elementos em imagens com o Amazon Rekognition usando um SDK da AWS
- Detecte informações em vídeos usando o Amazon Rekognition e o SDK da AWS

Crie uma coleção do Amazon Rekognition e encontre faces nela usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie uma coleção do Amazon Rekognition.
- Adicione imagens à coleção e detectar faces nela.
- Pesquise na coleção as faces que correspondem a uma imagem de referência.
- Excluir uma coleção.

Para obter mais informações, consulte Pesquisar faces em uma coleção.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar classes que agrupem as funções do Amazon Rekognition.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError
from rekognition_objects import RekognitionFace
from rekognition_image_detection import RekognitionImage

logger = logging.getLogger(__name__)


class RekognitionImage:
    """
```

```
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    @classmethod
    def from_file(cls, image_file_name, rekognition_client, image_name=None):
        """
        Creates a RekognitionImage object from a local file.

        :param image_file_name: The file name of the image. The file is opened
 and its
                                bytes are read.
        :param rekognition_client: A Boto3 Rekognition client.
        :param image_name: The name of the image. If this is not specified, the
                           file name is used as the image name.
        :return: The RekognitionImage object, initialized with image bytes from
 the
                 file.
        """
        with open(image_file_name, "rb") as img_file:
            image = {"Bytes": img_file.read()}
        name = image_file_name if image_name is None else image_name
        return cls(image, name, rekognition_client)


class RekognitionCollectionManager:
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition
 API.
```

```
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def create_collection(self, collection_id):
        """
        Creates an empty collection.

        :param collection_id: Text that identifies the collection.
        :return: The newly created collection.
        """
        try:
            response = self.rekognition_client.create_collection(
                CollectionId=collection_id
            )
            response["CollectionId"] = collection_id
            collection = RekognitionCollection(response, self.rekognition_client)
            logger.info("Created collection %s.", collection_id)
        except ClientError:
            logger.exception("Couldn't create collection %s.", collection_id)
            raise
        else:
            return collection


    def list_collections(self, max_results):
        """
        Lists collections for the current account.

        :param max_results: The maximum number of collections to return.
        :return: The list of collections for the current account.
        """
        try:
            response =
self.rekognition_client.list_collections(MaxResults=max_results)
            collections = [
```

```
                RekognitionCollection({"CollectionId": col_id},
 self.rekognition_client)
                for col_id in response["CollectionIds"]
            ]
        except ClientError:
            logger.exception("Couldn't list collections.")
            raise
        else:
            return collections



class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
```

```
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def to_dict(self):
        """
        Renders parts of the collection data to a dict.

        :return: The collection data as a dict.
        """
        rendering = {
            "collection_id": self.collection_id,
            "collection_arn": self.collection_arn,
            "face_count": self.face_count,
            "created": self.created,
        }
        return rendering


    def describe_collection(self):
        """
        Gets data about the collection from the Amazon Rekognition service.

        :return: The collection rendered as a dict.
        """
        try:
            response = self.rekognition_client.describe_collection(
                CollectionId=self.collection_id
            )
            # Work around capitalization of Arn vs. ARN
            response["CollectionArn"] = response.get("CollectionARN")
            (
                self.collection_arn,
                self.face_count,
                self.created,
            ) = self._unpack_collection(response)
            logger.info("Got data for collection %s.", self.collection_id)
        except ClientError:
            logger.exception("Couldn't get data for collection %s.",
self.collection_id)
            raise
        else:
            return self.to_dict()
```

```
    def delete_collection(self):
        """
        Deletes the collection.
        """
        try:

self.rekognition_client.delete_collection(CollectionId=self.collection_id)
            logger.info("Deleted collection %s.", self.collection_id)
            self.collection_id = None
        except ClientError:
            logger.exception("Couldn't delete collection %s.",
self.collection_id)
            raise


    def index_faces(self, image, max_faces):
        """
        Finds faces in the specified image, indexes them, and stores them in the
        collection.

        :param image: The image to index.
        :param max_faces: The maximum number of faces to index.
        :return: A tuple. The first element is a list of indexed faces.
                 The second element is a list of faces that couldn't be indexed.
        """
        try:
            response = self.rekognition_client.index_faces(
                CollectionId=self.collection_id,
                Image=image.image,
                ExternalImageId=image.image_name,
                MaxFaces=max_faces,
                DetectionAttributes=["ALL"],
            )
            indexed_faces = [
                RekognitionFace({**face["Face"], **face["FaceDetail"]})
                for face in response["FaceRecords"]
            ]
            unindexed_faces = [
                RekognitionFace(face["FaceDetail"])
                for face in response["UnindexedFaces"]
            ]
            logger.info(
```

```
                "Indexed %s faces in %s. Could not index %s faces.",
                len(indexed_faces),
                image.image_name,
                len(unindexed_faces),
            )
        except ClientError:
            logger.exception("Couldn't index faces in image %s.",
image.image_name)
            raise
        else:
            return indexed_faces, unindexed_faces


    def list_faces(self, max_results):
        """
        Lists the faces currently indexed in the collection.

        :param max_results: The maximum number of faces to return.
        :return: The list of faces in the collection.
        """
        try:
            response = self.rekognition_client.list_faces(
                CollectionId=self.collection_id, MaxResults=max_results
            )
            faces = [RekognitionFace(face) for face in response["Faces"]]
            logger.info(
                "Found %s faces in collection %s.", len(faces),
self.collection_id
            )
        except ClientError:
            logger.exception(
                "Couldn't list faces in collection %s.", self.collection_id
            )
            raise
        else:
            return faces


    def search_faces(self, face_id, threshold, max_faces):
        """
        Searches for faces in the collection that match another face from the
        collection.

        :param face_id: The ID of the face in the collection to search for.
```

```
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: The list of matching faces found in the collection. This list
does
                 not contain the face specified by `face_id`.
        """
        try:
            response = self.rekognition_client.search_faces(
                CollectionId=self.collection_id,
                FaceId=face_id,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            faces = [RekognitionFace(face["Face"]) for face in
response["FaceMatches"]]
            logger.info(
                "Found %s faces in %s that match %s.",
                len(faces),
                self.collection_id,
                face_id,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                face_id,
            )
            raise
        else:
            return faces


    def search_faces_by_image(self, image, threshold, max_faces):
        """
        Searches for faces in the collection that match the largest face in the
        reference image.

        :param image: The image that contains the reference face to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: A tuple. The first element is the face found in the reference
image.
```

```
                 The second element is the list of matching faces found in the
                 collection.
        """
        try:
            response = self.rekognition_client.search_faces_by_image(
                CollectionId=self.collection_id,
                Image=image.image,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            image_face = RekognitionFace(
                {
                    "BoundingBox": response["SearchedFaceBoundingBox"],
                    "Confidence": response["SearchedFaceConfidence"],
                }
            )
            collection_faces = [
                RekognitionFace(face["Face"]) for face in response["FaceMatches"]
            ]
            logger.info(
                "Found %s faces in the collection that match the largest "
                "face in %s.",
                len(collection_faces),
                image.image_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                image.image_name,
            )
            raise
        else:
            return image_face, collection_faces


class RekognitionFace:
    """Encapsulates an Amazon Rekognition face."""

    def __init__(self, face, timestamp=None):
        """
        Initializes the face object.

        :param face: Face data, in the format returned by Amazon Rekognition
```

```
                    functions.
        :param timestamp: The time when the face was detected, if the face was
                          detected in a video.
        """
        self.bounding_box = face.get("BoundingBox")
        self.confidence = face.get("Confidence")
        self.landmarks = face.get("Landmarks")
        self.pose = face.get("Pose")
        self.quality = face.get("Quality")
        age_range = face.get("AgeRange")
        if age_range is not None:
            self.age_range = (age_range.get("Low"), age_range.get("High"))
        else:
            self.age_range = None
        self.smile = face.get("Smile", {}).get("Value")
        self.eyeglasses = face.get("Eyeglasses", {}).get("Value")
        self.sunglasses = face.get("Sunglasses", {}).get("Value")
        self.gender = face.get("Gender", {}).get("Value", None)
        self.beard = face.get("Beard", {}).get("Value")
        self.mustache = face.get("Mustache", {}).get("Value")
        self.eyes_open = face.get("EyesOpen", {}).get("Value")
        self.mouth_open = face.get("MouthOpen", {}).get("Value")
        self.emotions = [
            emo.get("Type")
            for emo in face.get("Emotions", [])
            if emo.get("Confidence", 0) > 50
        ]
        self.face_id = face.get("FaceId")
        self.image_id = face.get("ImageId")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the face data to a dict.

        :return: A dict that contains the face data.
        """
        rendering = {}
        if self.bounding_box is not None:
            rendering["bounding_box"] = self.bounding_box
        if self.age_range is not None:
            rendering["age"] = f"{self.age_range[0]} - {self.age_range[1]}"
        if self.gender is not None:
            rendering["gender"] = self.gender
```

```
        if self.emotions:
            rendering["emotions"] = self.emotions
        if self.face_id is not None:
            rendering["face_id"] = self.face_id
        if self.image_id is not None:
            rendering["image_id"] = self.image_id
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        has = []
        if self.smile:
            has.append("smile")
        if self.eyeglasses:
            has.append("eyeglasses")
        if self.sunglasses:
            has.append("sunglasses")
        if self.beard:
            has.append("beard")
        if self.mustache:
            has.append("mustache")
        if self.eyes_open:
            has.append("open eyes")
        if self.mouth_open:
            has.append("open mouth")
        if has:
            rendering["has"] = has
        return rendering
```

Usar as classes wrapper para criar uma coleção de faces a partir de um conjunto de imagens e, em seguida, pesquise faces na coleção.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Rekognition face collection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    rekognition_client = boto3.client("rekognition")
    images = [
        RekognitionImage.from_file(
```

```
            ".media/pexels-agung-pandit-wiguna-1128316.jpg",
            rekognition_client,
            image_name="sitting",
        ),
        RekognitionImage.from_file(
            ".media/pexels-agung-pandit-wiguna-1128317.jpg",
            rekognition_client,
            image_name="hopping",
        ),
        RekognitionImage.from_file(
            ".media/pexels-agung-pandit-wiguna-1128318.jpg",
            rekognition_client,
            image_name="biking",
        ),
    ]

    collection_mgr = RekognitionCollectionManager(rekognition_client)
    collection = collection_mgr.create_collection("doc-example-collection-demo")
    print(f"Created collection {collection.collection_id}:")
    pprint(collection.describe_collection())

    print("Indexing faces from three images:")
    for image in images:
        collection.index_faces(image, 10)
    print("Listing faces in collection:")
    faces = collection.list_faces(10)
    for face in faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    print(
        f"Searching for faces in the collection that match the first face in the
"
        f"list (Face ID: {faces[0].face_id}."
    )
    found_faces = collection.search_faces(faces[0].face_id, 80, 10)
    print(f"Found {len(found_faces)} matching faces.")
    for face in found_faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    print(
        f"Searching for faces in the collection that match the largest face in "
        f"{images[0].image_name}."
```

```
    )
    image_face, match_faces = collection.search_faces_by_image(images[0], 80, 10)
    print(f"The largest face in {images[0].image_name} is:")
    pprint(image_face.to_dict())
    print(f"Found {len(match_faces)} matching faces.")
    for face in match_faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    collection.delete_collection()
    print("Thanks for watching!")
    print("-" * 88)
```

Detecte e exiba elementos em imagens com o Amazon Rekognition usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Detectar elementos em imagens usando o Amazon Rekognition.
- Exibir imagens e desenhar caixas delimitadoras ao redor dos elementos detectados.

Para obter mais informações, consulte Exibindo caixas delimitadoras.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar classes para agrupar as funções do Amazon Rekognition.

```
import logging
from pprint import pprint
```

```
import boto3
from botocore.exceptions import ClientError
import requests

from rekognition_objects import (
    RekognitionFace,
    RekognitionCelebrity,
    RekognitionLabel,
    RekognitionModerationLabel,
    RekognitionText,
    show_bounding_boxes,
    show_polygons,
)

logger = logging.getLogger(__name__)


class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    @classmethod
    def from_file(cls, image_file_name, rekognition_client, image_name=None):
        """
        Creates a RekognitionImage object from a local file.

        :param image_file_name: The file name of the image. The file is opened
 and its
```

```
                                bytes are read.
        :param rekognition_client: A Boto3 Rekognition client.
        :param image_name: The name of the image. If this is not specified, the
                           file name is used as the image name.
        :return: The RekognitionImage object, initialized with image bytes from
the
                 file.
        """
        with open(image_file_name, "rb") as img_file:
            image = {"Bytes": img_file.read()}
        name = image_file_name if image_name is None else image_name
        return cls(image, name, rekognition_client)


    @classmethod
    def from_bucket(cls, s3_object, rekognition_client):
        """
        Creates a RekognitionImage object from an Amazon S3 object.

        :param s3_object: An Amazon S3 object that identifies the image. The
image
                          is not retrieved until needed for a later call.
        :param rekognition_client: A Boto3 Rekognition client.
        :return: The RekognitionImage object, initialized with Amazon S3 object
data.
        """
        image = {"S3Object": {"Bucket": s3_object.bucket_name, "Name":
s3_object.key}}
        return cls(image, s3_object.key, rekognition_client)


    def detect_faces(self):
        """
        Detects faces in the image.

        :return: The list of faces found in the image.
        """
        try:
            response = self.rekognition_client.detect_faces(
                Image=self.image, Attributes=["ALL"]
            )
            faces = [RekognitionFace(face) for face in response["FaceDetails"]]
            logger.info("Detected %s faces.", len(faces))
        except ClientError:
```

```
            logger.exception("Couldn't detect faces in %s.", self.image_name)
            raise
        else:
            return faces


    def detect_labels(self, max_labels):
        """
        Detects labels in the image. Labels are objects and people.

        :param max_labels: The maximum number of labels to return.
        :return: The list of labels detected in the image.
        """
        try:
            response = self.rekognition_client.detect_labels(
                Image=self.image, MaxLabels=max_labels
            )
            labels = [RekognitionLabel(label) for label in response["Labels"]]
            logger.info("Found %s labels in %s.", len(labels), self.image_name)
        except ClientError:
            logger.info("Couldn't detect labels in %s.", self.image_name)
            raise
        else:
            return labels


    def recognize_celebrities(self):
        """
        Detects celebrities in the image.

        :return: A tuple. The first element is the list of celebrities found in
                 the image. The second element is the list of faces that were
                 detected but did not match any known celebrities.
        """
        try:
            response =
self.rekognition_client.recognize_celebrities(Image=self.image)
            celebrities = [
                RekognitionCelebrity(celeb) for celeb in
response["CelebrityFaces"]
            ]
            other_faces = [
                RekognitionFace(face) for face in response["UnrecognizedFaces"]
            ]
```

```
            logger.info(
                "Found %s celebrities and %s other faces in %s.",
                len(celebrities),
                len(other_faces),
                self.image_name,
            )
        except ClientError:
            logger.exception("Couldn't detect celebrities in %s.",
self.image_name)
            raise
        else:
            return celebrities, other_faces



    def compare_faces(self, target_image, similarity):
        """
        Compares faces in the image with the largest face in the target image.

        :param target_image: The target image to compare against.
        :param similarity: Faces in the image must have a similarity value
greater
                           than this value to be included in the results.
        :return: A tuple. The first element is the list of faces that match the
                 reference image. The second element is the list of faces that
have
                 a similarity value below the specified threshold.
        """
        try:
            response = self.rekognition_client.compare_faces(
                SourceImage=self.image,
                TargetImage=target_image.image,
                SimilarityThreshold=similarity,
            )
            matches = [
                RekognitionFace(match["Face"]) for match in
response["FaceMatches"]
            ]
            unmatches = [RekognitionFace(face) for face in
response["UnmatchedFaces"]]
            logger.info(
                "Found %s matched faces and %s unmatched faces.",
                len(matches),
                len(unmatches),
```

```
            )
        except ClientError:
            logger.exception(
                "Couldn't match faces from %s to %s.",
                self.image_name,
                target_image.image_name,
            )
            raise
        else:
            return matches, unmatches


    def detect_moderation_labels(self):
        """
        Detects moderation labels in the image. Moderation labels identify
content
        that may be inappropriate for some audiences.

        :return: The list of moderation labels found in the image.
        """
        try:
            response = self.rekognition_client.detect_moderation_labels(
                Image=self.image
            )
            labels = [
                RekognitionModerationLabel(label)
                for label in response["ModerationLabels"]
            ]
            logger.info(
                "Found %s moderation labels in %s.", len(labels), self.image_name
            )
        except ClientError:
            logger.exception(
                "Couldn't detect moderation labels in %s.", self.image_name
            )
            raise
        else:
            return labels


    def detect_text(self):
        """
        Detects text in the image.
```

```
        :return The list of text elements found in the image.
        """
        try:
            response = self.rekognition_client.detect_text(Image=self.image)
            texts = [RekognitionText(text) for text in
 response["TextDetections"]]
            logger.info("Found %s texts in %s.", len(texts), self.image_name)
        except ClientError:
            logger.exception("Couldn't detect text in %s.", self.image_name)
            raise
        else:
            return texts
```

Criar funções auxiliares para desenhar caixas delimitadoras e polígonos.

```
import io
import logging
from PIL import Image, ImageDraw

logger = logging.getLogger(__name__)


def show_bounding_boxes(image_bytes, box_sets, colors):
    """
    Draws bounding boxes on an image and shows it with the default image viewer.

    :param image_bytes: The image to draw, as bytes.
    :param box_sets: A list of lists of bounding boxes to draw on the image.
    :param colors: A list of colors to use to draw the bounding boxes.
    """
    image = Image.open(io.BytesIO(image_bytes))
    draw = ImageDraw.Draw(image)
    for boxes, color in zip(box_sets, colors):
        for box in boxes:
            left = image.width * box["Left"]
            top = image.height * box["Top"]
            right = (image.width * box["Width"]) + left
            bottom = (image.height * box["Height"]) + top
            draw.rectangle([left, top, right, bottom], outline=color, width=3)
    image.show()
```

```
def show_polygons(image_bytes, polygons, color):
    """
    Draws polygons on an image and shows it with the default image viewer.

    :param image_bytes: The image to draw, as bytes.
    :param polygons: The list of polygons to draw on the image.
    :param color: The color to use to draw the polygons.
    """
    image = Image.open(io.BytesIO(image_bytes))
    draw = ImageDraw.Draw(image)
    for polygon in polygons:
        draw.polygon(
            [
                (image.width * point["X"], image.height * point["Y"])
                for point in polygon
            ],
            outline=color,
        )
    image.show()
```

Criar classes para analisar objetos retornados pelo Amazon Rekognition.

```
class RekognitionFace:
    """Encapsulates an Amazon Rekognition face."""

    def __init__(self, face, timestamp=None):
        """
        Initializes the face object.

        :param face: Face data, in the format returned by Amazon Rekognition
                     functions.
        :param timestamp: The time when the face was detected, if the face was
                          detected in a video.
        """
        self.bounding_box = face.get("BoundingBox")
        self.confidence = face.get("Confidence")
        self.landmarks = face.get("Landmarks")
        self.pose = face.get("Pose")
```

```
        self.quality = face.get("Quality")
        age_range = face.get("AgeRange")
        if age_range is not None:
            self.age_range = (age_range.get("Low"), age_range.get("High"))
        else:
            self.age_range = None
        self.smile = face.get("Smile", {}).get("Value")
        self.eyeglasses = face.get("Eyeglasses", {}).get("Value")
        self.sunglasses = face.get("Sunglasses", {}).get("Value")
        self.gender = face.get("Gender", {}).get("Value", None)
        self.beard = face.get("Beard", {}).get("Value")
        self.mustache = face.get("Mustache", {}).get("Value")
        self.eyes_open = face.get("EyesOpen", {}).get("Value")
        self.mouth_open = face.get("MouthOpen", {}).get("Value")
        self.emotions = [
            emo.get("Type")
            for emo in face.get("Emotions", [])
            if emo.get("Confidence", 0) > 50
        ]
        self.face_id = face.get("FaceId")
        self.image_id = face.get("ImageId")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the face data to a dict.

        :return: A dict that contains the face data.
        """
        rendering = {}
        if self.bounding_box is not None:
            rendering["bounding_box"] = self.bounding_box
        if self.age_range is not None:
            rendering["age"] = f"{self.age_range[0]} - {self.age_range[1]}"
        if self.gender is not None:
            rendering["gender"] = self.gender
        if self.emotions:
            rendering["emotions"] = self.emotions
        if self.face_id is not None:
            rendering["face_id"] = self.face_id
        if self.image_id is not None:
            rendering["image_id"] = self.image_id
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
```

```
        has = []
        if self.smile:
            has.append("smile")
        if self.eyeglasses:
            has.append("eyeglasses")
        if self.sunglasses:
            has.append("sunglasses")
        if self.beard:
            has.append("beard")
        if self.mustache:
            has.append("mustache")
        if self.eyes_open:
            has.append("open eyes")
        if self.mouth_open:
            has.append("open mouth")
        if has:
            rendering["has"] = has
        return rendering



class RekognitionCelebrity:
    """Encapsulates an Amazon Rekognition celebrity."""

    def __init__(self, celebrity, timestamp=None):
        """
        Initializes the celebrity object.

        :param celebrity: Celebrity data, in the format returned by Amazon
 Rekognition
                          functions.
        :param timestamp: The time when the celebrity was detected, if the
 celebrity
                          was detected in a video.
        """
        self.info_urls = celebrity.get("Urls")
        self.name = celebrity.get("Name")
        self.id = celebrity.get("Id")
        self.face = RekognitionFace(celebrity.get("Face"))
        self.confidence = celebrity.get("MatchConfidence")
        self.bounding_box = celebrity.get("BoundingBox")
        self.timestamp = timestamp

    def to_dict(self):
```

```
        """
        Renders some of the celebrity data to a dict.

        :return: A dict that contains the celebrity data.
        """
        rendering = self.face.to_dict()
        if self.name is not None:
            rendering["name"] = self.name
        if self.info_urls:
            rendering["info URLs"] = self.info_urls
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionPerson:
    """Encapsulates an Amazon Rekognition person."""

    def __init__(self, person, timestamp=None):
        """
        Initializes the person object.

        :param person: Person data, in the format returned by Amazon Rekognition
                       functions.
        :param timestamp: The time when the person was detected, if the person
                          was detected in a video.
        """
        self.index = person.get("Index")
        self.bounding_box = person.get("BoundingBox")
        face = person.get("Face")
        self.face = RekognitionFace(face) if face is not None else None
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the person data to a dict.

        :return: A dict that contains the person data.
        """
        rendering = self.face.to_dict() if self.face is not None else {}
        if self.index is not None:
            rendering["index"] = self.index
        if self.bounding_box is not None:
```

```
            rendering["bounding_box"] = self.bounding_box
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionLabel:
    """Encapsulates an Amazon Rekognition label."""

    def __init__(self, label, timestamp=None):
        """
        Initializes the label object.

        :param label: Label data, in the format returned by Amazon Rekognition
                      functions.
        :param timestamp: The time when the label was detected, if the label
                          was detected in a video.
        """
        self.name = label.get("Name")
        self.confidence = label.get("Confidence")
        self.instances = label.get("Instances")
        self.parents = label.get("Parents")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the label data to a dict.

        :return: A dict that contains the label data.
        """
        rendering = {}
        if self.name is not None:
            rendering["name"] = self.name
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionModerationLabel:
    """Encapsulates an Amazon Rekognition moderation label."""

    def __init__(self, label, timestamp=None):
```

```
        """
        Initializes the moderation label object.

        :param label: Label data, in the format returned by Amazon Rekognition
                      functions.
        :param timestamp: The time when the moderation label was detected, if the
                          label was detected in a video.
        """
        self.name = label.get("Name")
        self.confidence = label.get("Confidence")
        self.parent_name = label.get("ParentName")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the moderation label data to a dict.

        :return: A dict that contains the moderation label data.
        """
        rendering = {}
        if self.name is not None:
            rendering["name"] = self.name
        if self.parent_name is not None:
            rendering["parent_name"] = self.parent_name
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionText:
    """Encapsulates an Amazon Rekognition text element."""

    def __init__(self, text_data):
        """
        Initializes the text object.

        :param text_data: Text data, in the format returned by Amazon Rekognition
                          functions.
        """
        self.text = text_data.get("DetectedText")
        self.kind = text_data.get("Type")
        self.id = text_data.get("Id")
        self.parent_id = text_data.get("ParentId")
```

```
        self.confidence = text_data.get("Confidence")
        self.geometry = text_data.get("Geometry")

    def to_dict(self):
        """
        Renders some of the text data to a dict.

        :return: A dict that contains the text data.
        """
        rendering = {}
        if self.text is not None:
            rendering["text"] = self.text
        if self.kind is not None:
            rendering["kind"] = self.kind
        if self.geometry is not None:
            rendering["polygon"] = self.geometry.get("Polygon")
        return rendering
```

Usar as classes wrapper para detectar elementos em imagens e exibir suas caixas delimitadoras. As imagens usadas neste exemplo podem ser encontradas GitHub junto com instruções e mais códigos.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Rekognition image detection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    rekognition_client = boto3.client("rekognition")
    street_scene_file_name = ".media/pexels-kaique-rocha-109919.jpg"
    celebrity_file_name = ".media/pexels-pixabay-53370.jpg"
    one_girl_url = "https://dhei5unw3vrsx.cloudfront.net/images/
source3_resized.jpg"
    three_girls_url = "https://dhei5unw3vrsx.cloudfront.net/images/
target3_resized.jpg"
    swimwear_object = boto3.resource("s3").Object(
        "console-sample-images-pdx", "yoga_swimwear.jpg"
    )
    book_file_name = ".media/pexels-christina-morillo-1181671.jpg"
```

```
    street_scene_image = RekognitionImage.from_file(
        street_scene_file_name, rekognition_client
    )
    print(f"Detecting faces in {street_scene_image.image_name}...")
    faces = street_scene_image.detect_faces()
    print(f"Found {len(faces)} faces, here are the first three.")
    for face in faces[:3]:
        pprint(face.to_dict())
    show_bounding_boxes(
        street_scene_image.image["Bytes"],
        [[face.bounding_box for face in faces]],
        ["aqua"],
    )
    input("Press Enter to continue.")

    print(f"Detecting labels in {street_scene_image.image_name}...")
    labels = street_scene_image.detect_labels(100)
    print(f"Found {len(labels)} labels.")
    for label in labels:
        pprint(label.to_dict())
    names = []
    box_sets = []
    colors = ["aqua", "red", "white", "blue", "yellow", "green"]
    for label in labels:
        if label.instances:
            names.append(label.name)
            box_sets.append([inst["BoundingBox"] for inst in label.instances])
    print(f"Showing bounding boxes for {names} in {colors[:len(names)]}.")
    show_bounding_boxes(
        street_scene_image.image["Bytes"], box_sets, colors[: len(names)]
    )
    input("Press Enter to continue.")

    celebrity_image = RekognitionImage.from_file(
        celebrity_file_name, rekognition_client
    )
    print(f"Detecting celebrities in {celebrity_image.image_name}...")
    celebs, others = celebrity_image.recognize_celebrities()
    print(f"Found {len(celebs)} celebrities.")
    for celeb in celebs:
        pprint(celeb.to_dict())
    show_bounding_boxes(
        celebrity_image.image["Bytes"],
        [[celeb.face.bounding_box for celeb in celebs]],
```

```
        ["aqua"],
    )
    input("Press Enter to continue.")

    girl_image_response = requests.get(one_girl_url)
    girl_image = RekognitionImage(
        {"Bytes": girl_image_response.content}, "one-girl", rekognition_client
    )
    group_image_response = requests.get(three_girls_url)
    group_image = RekognitionImage(
        {"Bytes": group_image_response.content}, "three-girls",
rekognition_client
    )
    print("Comparing reference face to group of faces...")
    matches, unmatches = girl_image.compare_faces(group_image, 80)
    print(f"Found {len(matches)} face matching the reference face.")
    show_bounding_boxes(
        group_image.image["Bytes"],
        [[match.bounding_box for match in matches]],
        ["aqua"],
    )
    input("Press Enter to continue.")

    swimwear_image = RekognitionImage.from_bucket(swimwear_object,
rekognition_client)
    print(f"Detecting suggestive content in {swimwear_object.key}...")
    labels = swimwear_image.detect_moderation_labels()
    print(f"Found {len(labels)} moderation labels.")
    for label in labels:
        pprint(label.to_dict())
    input("Press Enter to continue.")

    book_image = RekognitionImage.from_file(book_file_name, rekognition_client)
    print(f"Detecting text in {book_image.image_name}...")
    texts = book_image.detect_text()
    print(f"Found {len(texts)} text instances. Here are the first seven:")
    for text in texts[:7]:
        pprint(text.to_dict())
    show_polygons(
        book_image.image["Bytes"], [text.geometry["Polygon"] for text in texts],
"aqua"
    )

    print("Thanks for watching!")
```

```
    print("-" * 88)
```

Detecte informações em vídeos usando o Amazon Rekognition e o SDK da AWS

Os exemplos de código a seguir mostram como:

- Inicie trabalhos do Amazon Rekognition para detectar elementos como pessoas, objetos e texto em vídeos.
- Verificar o status do trabalho até que eles terminem.
- Criar uma lista de elementos detectados por cada trabalho.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter resultados de celebridades a partir de um vídeo localizado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartCelebrityRecognitionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.CelebrityRecognitionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.CelebrityRecognition;
```

```
import software.amazon.awssdk.services.rekognition.model.CelebrityDetail;
import
 software.amazon.awssdk.services.rekognition.model.StartCelebrityRecognitionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetCelebrityRecognitionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetCelebrityRecognitionResponse;
import java.util.List;

/**
 * To run this code example, ensure that you perform the Prerequisites as stated
 * in the Amazon Rekognition Guide:
 * https://docs.aws.amazon.com/rekognition/latest/dg/video-analyzing-with-
sqs.html
 *
 * Also, ensure that set up your development environment, including your
 * credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class VideoCelebrityDetection {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
 (IAM) role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startCelebrityDetection(rekClient, channel, bucket, video);
        getCelebrityDetectionResults(rekClient);
        System.out.println("This example is done!");
        rekClient.close();
    }

    public static void startCelebrityDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartCelebrityRecognitionRequest recognitionRequest =
StartCelebrityRecognitionRequest.builder()
                    .jobTag("Celebrities")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();
```

```
            StartCelebrityRecognitionResponse startCelebrityRecognitionResult =
rekClient
                    .startCelebrityRecognition(recognitionRequest);
            startJobId = startCelebrityRecognitionResult.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getCelebrityDetectionResults(RekognitionClient rekClient)
{

        try {
            String paginationToken = null;
            GetCelebrityRecognitionResponse recognitionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (recognitionResponse != null)
                    paginationToken = recognitionResponse.nextToken();

                GetCelebrityRecognitionRequest recognitionRequest =
GetCelebrityRecognitionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .sortBy(CelebrityRecognitionSortBy.TIMESTAMP)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds
                while (!finished) {
                    recognitionResponse =
rekClient.getCelebrityRecognition(recognitionRequest);
                    status = recognitionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
```

```
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is
 null.
                VideoMetadata videoMetaData =
 recognitionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
 videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<CelebrityRecognition> celebs =
 recognitionResponse.celebrities();
                for (CelebrityRecognition celeb : celebs) {
                    long seconds = celeb.timestamp() / 1000;
                    System.out.print("Sec: " + seconds + " ");
                    CelebrityDetail details = celeb.celebrity();
                    System.out.println("Name: " + details.name());
                    System.out.println("Id: " + details.id());
                    System.out.println();
                }

            } while (recognitionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar rótulos em um vídeo por meio de uma operação de detecção de rótulos.

```
import com.fasterxml.jackson.core.JsonProcessingException;
import com.fasterxml.jackson.databind.JsonMappingException;
import com.fasterxml.jackson.databind.JsonNode;
```

```
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetLabelDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.LabelDetectionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.LabelDetection;
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.Instance;
import software.amazon.awssdk.services.rekognition.model.Parent;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoDetect {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <queueUrl> <topicArn> <roleArn>
```

```
                Where:
                   bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                   video - The name of the video (for example, people.mp4).\s
                   queueUrl- The URL of a SQS queue.\s
                   topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
(IAM) role to use.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String queueUrl = args[2];
        String topicArn = args[3];
        String roleArn = args[4];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        SqsClient sqs = SqsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startLabels(rekClient, channel, bucket, video);
        getLabelJob(rekClient, sqs, queueUrl);
        System.out.println("This example is done!");
        sqs.close();
        rekClient.close();
    }

    public static void startLabels(RekognitionClient rekClient,
            NotificationChannel channel,
```

```
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartLabelDetectionRequest labelDetectionRequest =
StartLabelDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .minConfidence(50F)
                    .build();

            StartLabelDetectionResponse labelDetectionResponse =
rekClient.startLabelDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

            boolean ans = true;
            String status = "";
            int yy = 0;
            while (ans) {

                GetLabelDetectionRequest detectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .maxResults(10)
                        .build();

                GetLabelDetectionResponse result =
rekClient.getLabelDetection(detectionRequest);
                status = result.jobStatusAsString();

                if (status.compareTo("SUCCEEDED") == 0)
                    ans = false;
                else
                    System.out.println(yy + " status is: " + status);
```

```
                Thread.sleep(1000);
                yy++;
            }

            System.out.println(startJobId + " status is: " + status);

        } catch (RekognitionException | InterruptedException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getLabelJob(RekognitionClient rekClient, SqsClient sqs,
String queueUrl) {
        List<Message> messages;
        ReceiveMessageRequest messageRequest = ReceiveMessageRequest.builder()
                .queueUrl(queueUrl)
                .build();

        try {
            messages = sqs.receiveMessage(messageRequest).messages();

            if (!messages.isEmpty()) {
                for (Message message : messages) {
                    String notification = message.body();

                    // Get the status and job id from the notification
                    ObjectMapper mapper = new ObjectMapper();
                    JsonNode jsonMessageTree = mapper.readTree(notification);
                    JsonNode messageBodyText = jsonMessageTree.get("Message");
                    ObjectMapper operationResultMapper = new ObjectMapper();
                    JsonNode jsonResultTree =
operationResultMapper.readTree(messageBodyText.textValue());
                    JsonNode operationJobId = jsonResultTree.get("JobId");
                    JsonNode operationStatus = jsonResultTree.get("Status");
                    System.out.println("Job found in JSON is " + operationJobId);

                    DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                            .queueUrl(queueUrl)
                            .build();

                    String jobId = operationJobId.textValue();
                    if (startJobId.compareTo(jobId) == 0) {
```

```
                        System.out.println("Job id: " + operationJobId);
                        System.out.println("Status : " +
operationStatus.toString());

                        if (operationStatus.asText().equals("SUCCEEDED"))
                            getResultsLabels(rekClient);
                        else
                            System.out.println("Video analysis failed");

                        sqs.deleteMessage(deleteMessageRequest);
                    } else {
                        System.out.println("Job received was not job " +
startJobId);
                        sqs.deleteMessage(deleteMessageRequest);
                    }
                }
            }

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        } catch (JsonMappingException e) {
            e.printStackTrace();
        } catch (JsonProcessingException e) {
            e.printStackTrace();
        }
    }

    // Gets the job results by calling GetLabelDetection
    private static void getResultsLabels(RekognitionClient rekClient) {

        int maxResults = 10;
        String paginationToken = null;
        GetLabelDetectionResponse labelDetectionResult = null;

        try {
            do {
                if (labelDetectionResult != null)
                    paginationToken = labelDetectionResult.nextToken();

                GetLabelDetectionRequest labelDetectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .sortBy(LabelDetectionSortBy.TIMESTAMP)
```

```
                        .maxResults(maxResults)
                        .nextToken(paginationToken)
                        .build();

                labelDetectionResult =
rekClient.getLabelDetection(labelDetectionRequest);
                VideoMetadata videoMetaData =
labelDetectionResult.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());

                List<LabelDetection> detectedLabels =
labelDetectionResult.labels();
                for (LabelDetection detectedLabel : detectedLabels) {
                    long seconds = detectedLabel.timestamp();
                    Label label = detectedLabel.label();
                    System.out.println("Millisecond: " + seconds + " ");

                    System.out.println("   Label:" + label.name());
                    System.out.println("   Confidence:" +
detectedLabel.label().confidence().toString());

                    List<Instance> instances = label.instances();
                    System.out.println("   Instances of " + label.name());

                    if (instances.isEmpty()) {
                        System.out.println("        " + "None");
                    } else {
                        for (Instance instance : instances) {
                            System.out.println("        Confidence: " +
instance.confidence().toString());
                            System.out.println("        Bounding box: " +
instance.boundingBox().toString());
                        }
                    }
                    System.out.println("   Parent labels for " + label.name() +
":");
                    List<Parent> parents = label.parents();

                    if (parents.isEmpty()) {
                        System.out.println("        None");
```

```
                    } else {
                        for (Parent parent : parents) {
                            System.out.println("   " + parent.name());
                        }
                    }
                    System.out.println();
                }
            } while (labelDetectionResult != null &&
 labelDetectionResult.nextToken() != null);

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }
}
```

Detectar faces em um vídeo armazenado em um bucket do Amazon S3.

```
import com.fasterxml.jackson.core.JsonProcessingException;
import com.fasterxml.jackson.databind.JsonMappingException;
import com.fasterxml.jackson.databind.JsonNode;
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetLabelDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.LabelDetectionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.LabelDetection;
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.Instance;
```

```
import software.amazon.awssdk.services.rekognition.model.Parent;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoDetect {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <queueUrl> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of the video (for example, people.mp4).\s
                   queueUrl- The URL of a SQS queue.\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
 (IAM) role to use.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String queueUrl = args[2];
        String topicArn = args[3];
```

```
        String roleArn = args[4];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        SqsClient sqs = SqsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startLabels(rekClient, channel, bucket, video);
        getLabelJob(rekClient, sqs, queueUrl);
        System.out.println("This example is done!");
        sqs.close();
        rekClient.close();
    }

    public static void startLabels(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartLabelDetectionRequest labelDetectionRequest =
 StartLabelDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .minConfidence(50F)
                    .build();
```

```
            StartLabelDetectionResponse labelDetectionResponse =
rekClient.startLabelDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

            boolean ans = true;
            String status = "";
            int yy = 0;
            while (ans) {

                GetLabelDetectionRequest detectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .maxResults(10)
                        .build();

                GetLabelDetectionResponse result =
rekClient.getLabelDetection(detectionRequest);
                status = result.jobStatusAsString();

                if (status.compareTo("SUCCEEDED") == 0)
                    ans = false;
                else
                    System.out.println(yy + " status is: " + status);

                Thread.sleep(1000);
                yy++;
            }

            System.out.println(startJobId + " status is: " + status);

        } catch (RekognitionException | InterruptedException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getLabelJob(RekognitionClient rekClient, SqsClient sqs,
String queueUrl) {
        List<Message> messages;
        ReceiveMessageRequest messageRequest = ReceiveMessageRequest.builder()
                .queueUrl(queueUrl)
                .build();

        try {
```

```
            messages = sqs.receiveMessage(messageRequest).messages();

            if (!messages.isEmpty()) {
                for (Message message : messages) {
                    String notification = message.body();

                    // Get the status and job id from the notification
                    ObjectMapper mapper = new ObjectMapper();
                    JsonNode jsonMessageTree = mapper.readTree(notification);
                    JsonNode messageBodyText = jsonMessageTree.get("Message");
                    ObjectMapper operationResultMapper = new ObjectMapper();
                    JsonNode jsonResultTree =
operationResultMapper.readTree(messageBodyText.textValue());
                    JsonNode operationJobId = jsonResultTree.get("JobId");
                    JsonNode operationStatus = jsonResultTree.get("Status");
                    System.out.println("Job found in JSON is " + operationJobId);

                    DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                            .queueUrl(queueUrl)
                            .build();

                    String jobId = operationJobId.textValue();
                    if (startJobId.compareTo(jobId) == 0) {
                        System.out.println("Job id: " + operationJobId);
                        System.out.println("Status : " +
operationStatus.toString());

                        if (operationStatus.asText().equals("SUCCEEDED"))
                            getResultsLabels(rekClient);
                        else
                            System.out.println("Video analysis failed");

                        sqs.deleteMessage(deleteMessageRequest);
                    } else {
                        System.out.println("Job received was not job " +
startJobId);
                        sqs.deleteMessage(deleteMessageRequest);
                    }
                }
            }

        } catch (RekognitionException e) {
            e.getMessage();
```

```
            System.exit(1);
        } catch (JsonMappingException e) {
            e.printStackTrace();
        } catch (JsonProcessingException e) {
            e.printStackTrace();
        }
    }

    // Gets the job results by calling GetLabelDetection
    private static void getResultsLabels(RekognitionClient rekClient) {

        int maxResults = 10;
        String paginationToken = null;
        GetLabelDetectionResponse labelDetectionResult = null;

        try {
            do {
                if (labelDetectionResult != null)
                    paginationToken = labelDetectionResult.nextToken();

                GetLabelDetectionRequest labelDetectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .sortBy(LabelDetectionSortBy.TIMESTAMP)
                        .maxResults(maxResults)
                        .nextToken(paginationToken)
                        .build();

                labelDetectionResult =
rekClient.getLabelDetection(labelDetectionRequest);
                VideoMetadata videoMetaData =
labelDetectionResult.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());

                List<LabelDetection> detectedLabels =
labelDetectionResult.labels();
                for (LabelDetection detectedLabel : detectedLabels) {
                    long seconds = detectedLabel.timestamp();
                    Label label = detectedLabel.label();
                    System.out.println("Millisecond: " + seconds + " ");
```

```
                    System.out.println("   Label:" + label.name());
                    System.out.println("   Confidence:" +
 detectedLabel.label().confidence().toString());

                    List<Instance> instances = label.instances();
                    System.out.println("   Instances of " + label.name());

                    if (instances.isEmpty()) {
                        System.out.println("        " + "None");
                    } else {
                        for (Instance instance : instances) {
                            System.out.println("        Confidence: " +
 instance.confidence().toString());
                            System.out.println("        Bounding box: " +
 instance.boundingBox().toString());
                        }
                    }
                    System.out.println("   Parent labels for " + label.name() +
 ":");
                    List<Parent> parents = label.parents();

                    if (parents.isEmpty()) {
                        System.out.println("        None");
                    } else {
                        for (Parent parent : parents) {
                            System.out.println("   " + parent.name());
                        }
                    }
                    System.out.println();
                }
            } while (labelDetectionResult != null &&
 labelDetectionResult.nextToken() != null);

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }
}
```

Detectar conteúdo inapropriado ou ofensivo em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartContentModerationRequest;
import
 software.amazon.awssdk.services.rekognition.model.StartContentModerationResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetContentModerationResponse;
import
 software.amazon.awssdk.services.rekognition.model.GetContentModerationRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import
 software.amazon.awssdk.services.rekognition.model.ContentModerationDetection;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoDetectInappropriate {
    private static String startJobId = "";

    public static void main(String[] args) {

        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
```

```
                    video - The name of video (for example, people.mp4).\s
                    topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                    roleArn - The ARN of the AWS Identity and Access Management
(IAM) role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startModerationDetection(rekClient, channel, bucket, video);
        getModResults(rekClient);
        System.out.println("This example is done!");
        rekClient.close();
    }

    public static void startModerationDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {

        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
```

```
                    .s3Object(s3Obj)
                    .build();

            StartContentModerationRequest modDetectionRequest =
StartContentModerationRequest.builder()
                    .jobTag("Moderation")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();

            StartContentModerationResponse startModDetectionResult = rekClient
                    .startContentModeration(modDetectionRequest);
            startJobId = startModDetectionResult.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getModResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetContentModerationResponse modDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (modDetectionResponse != null)
                    paginationToken = modDetectionResponse.nextToken();

                GetContentModerationRequest modRequest =
GetContentModerationRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds.
                while (!finished) {
                    modDetectionResponse =
rekClient.getContentModeration(modRequest);
                    status = modDetectionResponse.jobStatusAsString();
```

```
                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is
 null.
                VideoMetadata videoMetaData =
 modDetectionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
 videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<ContentModerationDetection> mods =
 modDetectionResponse.moderationLabels();
                for (ContentModerationDetection mod : mods) {
                    long seconds = mod.timestamp() / 1000;
                    System.out.print("Mod label: " + seconds + " ");
                    System.out.println(mod.moderationLabel().toString());
                    System.out.println();
                }

            } while (modDetectionResponse != null &&
 modDetectionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar segmentos de sinal técnico e segmentos de detecção de tomada em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartShotDetectionFilter;
import
 software.amazon.awssdk.services.rekognition.model.StartTechnicalCueDetectionFilter;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionFilters;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetSegmentDetectionResponse;
import
 software.amazon.awssdk.services.rekognition.model.GetSegmentDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.SegmentDetection;
import software.amazon.awssdk.services.rekognition.model.TechnicalCueSegment;
import software.amazon.awssdk.services.rekognition.model.ShotSegment;
import software.amazon.awssdk.services.rekognition.model.SegmentType;
import software.amazon.awssdk.services.sqs.SqsClient;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoDetectSegment {
    private static String startJobId = "";
```

```
    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
(IAM) role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];

        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        SqsClient sqs = SqsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startSegmentDetection(rekClient, channel, bucket, video);
        getSegmentResults(rekClient);
        System.out.println("This example is done!");
        sqs.close();
        rekClient.close();
```

```
    }

    public static void startSegmentDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartShotDetectionFilter cueDetectionFilter =
StartShotDetectionFilter.builder()
                    .minSegmentConfidence(60F)
                    .build();

            StartTechnicalCueDetectionFilter technicalCueDetectionFilter =
StartTechnicalCueDetectionFilter.builder()
                    .minSegmentConfidence(60F)
                    .build();

            StartSegmentDetectionFilters filters =
StartSegmentDetectionFilters.builder()
                    .shotFilter(cueDetectionFilter)
                    .technicalCueFilter(technicalCueDetectionFilter)
                    .build();

            StartSegmentDetectionRequest segDetectionRequest =
StartSegmentDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .segmentTypes(SegmentType.TECHNICAL_CUE, SegmentType.SHOT)
                    .video(vidOb)
                    .filters(filters)
                    .build();

            StartSegmentDetectionResponse segDetectionResponse =
rekClient.startSegmentDetection(segDetectionRequest);
            startJobId = segDetectionResponse.jobId();
```

```
        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getSegmentResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetSegmentDetectionResponse segDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (segDetectionResponse != null)
                    paginationToken = segDetectionResponse.nextToken();

                GetSegmentDetectionRequest recognitionRequest =
GetSegmentDetectionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds.
                while (!finished) {
                    segDetectionResponse =
rekClient.getSegmentDetection(recognitionRequest);
                    status = segDetectionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }
                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is
null.
```

```
                List<VideoMetadata> videoMetaData =
segDetectionResponse.videoMetadata();
                for (VideoMetadata metaData : videoMetaData) {
                    System.out.println("Format: " + metaData.format());
                    System.out.println("Codec: " + metaData.codec());
                    System.out.println("Duration: " + metaData.durationMillis());
                    System.out.println("FrameRate: " + metaData.frameRate());
                    System.out.println("Job");
                }

                List<SegmentDetection> detectedSegments =
segDetectionResponse.segments();
                for (SegmentDetection detectedSegment : detectedSegments) {
                    String type = detectedSegment.type().toString();
                    if (type.contains(SegmentType.TECHNICAL_CUE.toString())) {
                        System.out.println("Technical Cue");
                        TechnicalCueSegment segmentCue =
detectedSegment.technicalCueSegment();
                        System.out.println("\tType: " + segmentCue.type());
                        System.out.println("\tConfidence: " +
segmentCue.confidence().toString());
                    }

                    if (type.contains(SegmentType.SHOT.toString())) {
                        System.out.println("Shot");
                        ShotSegment segmentShot = detectedSegment.shotSegment();
                        System.out.println("\tIndex " + segmentShot.index());
                        System.out.println("\tConfidence: " +
segmentShot.confidence().toString());
                    }

                    long seconds = detectedSegment.durationMillis();
                    System.out.println("\tDuration : " + seconds + "
milliseconds");
                    System.out.println("\tStart time code: " +
detectedSegment.startTimecodeSMPTE());
                    System.out.println("\tEnd time code: " +
detectedSegment.endTimecodeSMPTE());
                    System.out.println("\tDuration time code: " +
detectedSegment.durationSMPTE());
                    System.out.println();
                }
```

```
            } while (segDetectionResponse != null &&
 segDetectionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar texto em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartTextDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.StartTextDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetTextDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.GetTextDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.TextDetectionResult;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoDetectText {
    private static String startJobId = "";

    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
(IAM) role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];

        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startTextLabels(rekClient, channel, bucket, video);
        getTextResults(rekClient);
        System.out.println("This example is done!");
        rekClient.close();
    }

    public static void startTextLabels(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
```

```
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartTextDetectionRequest labelDetectionRequest =
StartTextDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();

            StartTextDetectionResponse labelDetectionResponse =
rekClient.startTextDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getTextResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetTextDetectionResponse textDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (textDetectionResponse != null)
                    paginationToken = textDetectionResponse.nextToken();

                GetTextDetectionRequest recognitionRequest =
GetTextDetectionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
```

```
                        .build();

                // Wait until the job succeeds.
                while (!finished) {
                    textDetectionResponse =
rekClient.getTextDetection(recognitionRequest);
                    status = textDetectionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is
null.
                VideoMetadata videoMetaData =
textDetectionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<TextDetectionResult> labels =
textDetectionResponse.textDetections();
                for (TextDetectionResult detectedText : labels) {
                    System.out.println("Confidence: " +
detectedText.textDetection().confidence().toString());
                    System.out.println("Id : " +
detectedText.textDetection().id());
                    System.out.println("Parent Id: " +
detectedText.textDetection().parentId());
                    System.out.println("Type: " +
detectedText.textDetection().type());
                    System.out.println("Text: " +
detectedText.textDetection().detectedText());
                    System.out.println();
```

```
                }

            } while (textDetectionResponse != null &&
 textDetectionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detecte pessoas em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import
 software.amazon.awssdk.services.rekognition.model.StartPersonTrackingRequest;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartPersonTrackingResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetPersonTrackingResponse;
import
 software.amazon.awssdk.services.rekognition.model.GetPersonTrackingRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.PersonDetection;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class VideoPersonDetection {
```

```
    private static String startJobId = "";

    public static void main(String[] args) {

        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management
(IAM) role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startPersonLabels(rekClient, channel, bucket, video);
        getPersonDetectionResults(rekClient);
        System.out.println("This example is done!");
        rekClient.close();
    }

    public static void startPersonLabels(RekognitionClient rekClient,
```

```
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartPersonTrackingRequest personTrackingRequest =
StartPersonTrackingRequest.builder()
                    .jobTag("DetectingLabels")
                    .video(vidOb)
                    .notificationChannel(channel)
                    .build();

            StartPersonTrackingResponse labelDetectionResponse =
rekClient.startPersonTracking(personTrackingRequest);
            startJobId = labelDetectionResponse.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getPersonDetectionResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetPersonTrackingResponse personTrackingResult = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (personTrackingResult != null)
                    paginationToken = personTrackingResult.nextToken();

                GetPersonTrackingRequest recognitionRequest =
GetPersonTrackingRequest.builder()
```

```
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds
                while (!finished) {

                    personTrackingResult =
rekClient.getPersonTracking(recognitionRequest);
                    status = personTrackingResult.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is
null.
                VideoMetadata videoMetaData =
personTrackingResult.videoMetadata();

                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " +
videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<PersonDetection> detectedPersons =
personTrackingResult.persons();
                for (PersonDetection detectedPerson : detectedPersons) {
                    long seconds = detectedPerson.timestamp() / 1000;
                    System.out.print("Sec: " + seconds + " ");
                    System.out.println("Person Identifier: " +
detectedPerson.person().index());
                    System.out.println();
                }
```

```
            } while (personTrackingResult != null &&
 personTrackingResult.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetCelebrityRecognition
  - GetContentModeration
  - GetLabelDetection
  - GetPersonTracking
  - GetSegmentDetection
  - GetTextDetection
  - StartCelebrityRecognition
  - StartContentModeration
  - StartLabelDetection
  - StartPersonTracking
  - StartSegmentDetection
  - StartTextDetection

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Detectar faces em um vídeo armazenado em um bucket do Amazon S3.

```
suspend fun startFaceDetection(channelVal: NotificationChannel?, bucketVal:
 String, videoVal: String) {

    val s3Obj = S3Object {
        bucket = bucketVal
        name = videoVal
    }
    val vidOb = Video {
        s3Object = s3Obj
    }

    val request = StartFaceDetectionRequest {
        jobTag = "Faces"
        faceAttributes = FaceAttributes.All
        notificationChannel = channelVal
        video = vidOb
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val startLabelDetectionResult = rekClient.startFaceDetection(request)
        startJobId = startLabelDetectionResult.jobId.toString()
    }
}

suspend fun getFaceResults() {

    var finished = false
    var status: String
    var yy = 0
    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        var response: GetFaceDetectionResponse? = null

        val recognitionRequest = GetFaceDetectionRequest {
            jobId = startJobId
            maxResults = 10
        }

        // Wait until the job succeeds.
        while (!finished) {
            response = rekClient.getFaceDetection(recognitionRequest)
            status = response.jobStatus.toString()
            if (status.compareTo("SUCCEEDED") == 0)
```

```
                finished = true
            else {
                println("$yy status is: $status")
                delay(1000)
            }
            yy++
        }

        // Proceed when the job is done - otherwise VideoMetadata is null.
        val videoMetaData = response?.videoMetadata
        println("Format: ${videoMetaData?.format}")
        println("Codec: ${videoMetaData?.codec}")
        println("Duration: ${videoMetaData?.durationMillis}")
        println("FrameRate: ${videoMetaData?.frameRate}")

        // Show face information.
        response?.faces?.forEach { face ->
            println("Age: ${face.face?.ageRange}")
            println("Face: ${face.face?.beard}")
            println("Eye glasses: ${face?.face?.eyeglasses}")
            println("Mustache: ${face.face?.mustache}")
            println("Smile: ${face.face?.smile}")
        }
    }
}
```

Detectar conteúdo inapropriado ou ofensivo em um vídeo armazenado em um bucket do Amazon S3.

```
suspend fun startModerationDetection(channel: NotificationChannel?, bucketVal:
 String?, videoVal: String?) {

    val s3Obj = S3Object {
        bucket = bucketVal
        name = videoVal
    }
    val vidOb = Video {
        s3Object = s3Obj
    }
    val request = StartContentModerationRequest {
        jobTag = "Moderation"
        notificationChannel = channel
```

```
        video = vidOb
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val startModDetectionResult = rekClient.startContentModeration(request)
        startJobId = startModDetectionResult.jobId.toString()
    }
}

suspend fun getModResults() {
    var finished = false
    var status: String
    var yy = 0
    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        var modDetectionResponse: GetContentModerationResponse? = null

        val modRequest = GetContentModerationRequest {
            jobId = startJobId
            maxResults = 10
        }

        // Wait until the job succeeds.
        while (!finished) {
            modDetectionResponse = rekClient.getContentModeration(modRequest)
            status = modDetectionResponse.jobStatus.toString()
            if (status.compareTo("SUCCEEDED") == 0)
                finished = true
            else {
                println("$yy status is: $status")
                delay(1000)
            }
            yy++
        }

        // Proceed when the job is done - otherwise VideoMetadata is null.
        val videoMetaData = modDetectionResponse?.videoMetadata
        println("Format: ${videoMetaData?.format}")
        println("Codec: ${videoMetaData?.codec}")
        println("Duration: ${videoMetaData?.durationMillis}")
        println("FrameRate: ${videoMetaData?.frameRate}")

        modDetectionResponse?.moderationLabels?.forEach { mod ->
            val seconds: Long = mod.timestamp / 1000
            print("Mod label: $seconds ")
```

```
            println(mod.moderationLabel)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - GetCelebrityRecognition
  - GetContentModeration
  - GetLabelDetection
  - GetPersonTracking
  - GetSegmentDetection
  - GetTextDetection
  - StartCelebrityRecognition
  - StartContentModeration
  - StartLabelDetection
  - StartPersonTracking
  - StartSegmentDetection
  - StartTextDetection

Exemplos do Amazon Rekognition entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Rekognition com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar faces em uma imagem usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Salvar o EXIF e outras informações de imagem usando um AWS SDK

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar equipamentos de proteção individual (EPI) em imagens.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda que detecta imagens com equipamento de proteção individual.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar equipamentos de proteção individual (EPI) em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação salva os resultados em uma tabela do Amazon DynamoDB e envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Atualizar uma tabela do DynamoDB com resultados.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar faces em uma imagem usando um AWS SDK

O código de exemplo a seguir mostra como:

- Salve uma imagem em um bucket do Amazon S3.
- Use o Amazon Rekognition para detectar detalhes faciais, como faixa etária, sexo e emoções (sorriso, etc.).
- Exibir esses detalhes.

Rust

SDK for Rust

Salve a imagem em um bucket do Amazon S3 com um prefixo uploads, use o Amazon Rekognition para detectar detalhes faciais, como faixa etária, sexo e emoções (sorriso, etc.), e exiba esses detalhes.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar objetos por categoria em imagens.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de objetos usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar uma aplicação Web que permite a você fazer o seguinte:

- Carregar fotos em um bucket do Amazon Simple Storage Service (Amazon S3).
- Usar o Amazon Rekognition para analisar e rotular as fotos.
- Usar o Amazon Simple Email Service (Amazon SES) para enviar relatórios de análise da imagem por e-mail.

Este exemplo contém dois componentes principais: uma página da Web criada com o React e um serviço REST escrito em Python que é criado com o Flask-RESTful. JavaScript

Você pode usar a página da Web do React para:

- Exibir uma lista de imagens que estão armazenadas no bucket do S3.
- Carregar imagens do computador para o bucket do S3.
- Exibir imagens e rótulos que identificam os itens detectados na imagem.
- Obter um relatório de todas as imagens no bucket do S3 e enviar um relatório por e-mail.

A página da Web chama o serviço REST. O serviço envia solicitações à AWS para realizar as seguintes ações:

- Obter e filtrar a lista de imagens no bucket do S3.
- Carregar fotos no bucket do S3.
- Usar o Amazon Rekognition para analisar fotos individuais e obter uma lista dos rótulos que identifiquem os itens detectados nas fotos.
- Analisar todas as fotos no bucket do S3 e usar o Amazon SES para enviar um relatório por e-mail.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar pessoas e objetos em um vídeo com o Amazon Rekognition.

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Python

SDK para Python (Boto3)

Use o Amazon Rekognition para detectar rostos, objetos e pessoas em vídeos iniciando trabalhos de detecção assíncrona. Este exemplo também configura o Amazon Rekognition

para notificar um tópico do Amazon Simple Notification Service (Amazon SNS) quando os trabalhos são concluídos e inscreve uma fila do Amazon Simple Queue Service (Amazon SQS) no tópico. Quando a fila recebe uma mensagem sobre um trabalho, o trabalho é recuperado e os resultados são apresentados.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon SNS
- Amazon SQS

Salvar o EXIF e outras informações de imagem usando um AWS SDK

O código de exemplo a seguir mostra como:

- Obter informações de EXIF de um arquivo JPG, JPEG ou PNG.
- Faça upload do arquivo de imagem para um bucket do Amazon S3.
- Use o Amazon Rekognition para identificar os três principais atributos (rótulos) no arquivo.
- Adicione as informações de EXIF e rótulo a uma tabela do Amazon DynamoDB na região.

Rust

SDK for Rust

Obtenha informações de EXIF de um arquivo JPG, JPEG ou PNG, faça upload do arquivo de imagem para um bucket do Amazon S3, use o Amazon Rekognition para identificar os três principais atributos (rótulos no Amazon Rekognition) no arquivo e adicione as informações de EXIF e de rótulo a uma tabela do Amazon DynamoDB na região.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon Rekognition
- Amazon S3

Exemplos de código para o Route 53 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Route 53 com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Route 53 – Mais informações sobre o Route 53.
- Referência da API do Route 53 – Detalhes sobre todas as ações disponíveis do Route 53.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Route 53 usando SDKs da AWS
  - Obter uma lista de zonas hospedadas públicas e privadas do Route 53 usando um SDK da AWS

Ações para o Route 53 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Route 53 com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Obter uma lista de zonas hospedadas públicas e privadas do Route 53 usando um SDK da AWS

Obter uma lista de zonas hospedadas públicas e privadas do Route 53 usando um SDK da AWS

O exemplo de código a seguir mostra como obter uma lista de zonas hospedadas públicas e privadas.

CLI

AWS CLI

Para listar as zonas hospedadas associadas à conta atual da AWS

O comando `list-hosted-zones` lista informações resumidas sobre as primeiras 100 zonas hospedadas associadas à conta atual da AWS:

```
aws route53 list-hosted-zones
```

Se você tiver mais de 100 zonas hospedadas ou se quiser listá-las em grupos de menos de 100 zonas, inclua o parâmetro `--max-items`. Por exemplo, para listar as zonas hospedadas, use o seguinte comando:

```
aws route53 list-hosted-zones --max-items 1
```

Para visualizar informações sobre a próxima zona hospedada, pegue o valor de `NextToken` da resposta ao comando anterior e inclua-o no parâmetro `--starting-token`, por exemplo:

```
aws route53 list-hosted-zones --max-items 1 --starting-token Z3M3LMPEXAMPLE
```

- Para obter detalhes da API, consulte ListHostedZonesem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_host_info(client: &aws_sdk_route53::Client) -> Result<(),
 aws_sdk_route53::Error> {
    let hosted_zone_count = client.get_hosted_zone_count().send().await?;

    println!(
        "Number of hosted zones in region : {}",
        hosted_zone_count.hosted_zone_count(),
    );

    let hosted_zones = client.list_hosted_zones().send().await?;

    println!("Zones:");

    for hz in hosted_zones.hosted_zones() {
        let zone_name = hz.name();
        let zone_id = hz.id();

        println!("  ID :   {}", zone_id);
        println!("  Name : {}", zone_name);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListHostedZonesreferência da API AWS SDK for Rust.

Exemplos de código para registro de domínios do Route 53 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar Amazon Route 53 domain registration com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do registro de domínio do Route 53 – Mais informações sobre o registro de domínio do Route 53.
- Referência da API do registro de domínio do Route 53 – Detalhes sobre todas as ações disponíveis do registro de domínio do Route 53.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Registro de domínios do Hello Route 53

O exemplo de código a seguir mostra como começar a usar o registro de domínios do Route 53.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static class HelloRoute53Domains
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon Route 53 domain registration service.
        // Use your AWS profile name, or leave it blank to use the default
 profile.
        using var host = Host.CreateDefaultBuilder(args)
```

```
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRoute53Domains>()
            ).Build();

        // Now the client is available for injection.
        var route53Client =
host.Services.GetRequiredService<IAmazonRoute53Domains>();

        // You can use await and any of the async methods to get a response.
        var response = await route53Client.ListPricesAsync(new ListPricesRequest
{ Tld = "com" });
        Console.WriteLine($"Hello Amazon Route 53 Domains! Following are prices
for .com domain operations:");
        var comPrices = response.Prices.FirstOrDefault();
        if (comPrices != null)
        {
            Console.WriteLine($"\tRegistration:
{comPrices.RegistrationPrice?.Price} {comPrices.RegistrationPrice?.Currency}");
            Console.WriteLine($"\tRenewal: {comPrices.RenewalPrice?.Price}
{comPrices.RenewalPrice?.Currency}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.route53domains.Route53DomainsClient;
import software.amazon.awssdk.services.route53.model.Route53Exception;
import software.amazon.awssdk.services.route53domains.model.DomainPrice;
import software.amazon.awssdk.services.route53domains.model.ListPricesRequest;
```

```
import software.amazon.awssdk.services.route53domains.model.ListPricesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java code examples performs the following operation:
 *
 * 1. Invokes ListPrices for at least one domain type, such as the “com” type
 * and displays the prices for Registration and Renewal.
 *
 */
public class HelloRoute53 {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) {
        final String usage = "\n" +
                "Usage:\n" +
                "    <hostedZoneId> \n\n" +
                "Where:\n" +
                "    hostedZoneId - The id value of an existing hosted zone. \n";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainType = args[0];
        Region region = Region.US_EAST_1;
        Route53DomainsClient route53DomainsClient =
 Route53DomainsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Invokes ListPrices for at least one domain type.");
        listPrices(route53DomainsClient, domainType);
```

```
        System.out.println(DASHES);
    }

    public static void listPrices(Route53DomainsClient route53DomainsClient,
 String domainType) {
        try {
            ListPricesRequest pricesRequest = ListPricesRequest.builder()
                    .maxItems(10)
                    .tld(domainType)
                    .build();

            ListPricesResponse response =
 route53DomainsClient.listPrices(pricesRequest);
            List<DomainPrice> prices = response.prices();
            for (DomainPrice pr : prices) {
                System.out.println("Name: " + pr.name());
                System.out.println(
                        "Registration: " + pr.registrationPrice().price() + " " +
 pr.registrationPrice().currency());
                System.out.println("Renewal: " + pr.renewalPrice().price() + " "
 + pr.renewalPrice().currency());
                System.out.println("Transfer: " + pr.transferPrice().price() + "
 " + pr.transferPrice().currency());
                System.out.println("Transfer: " + pr.transferPrice().price() + "
 " + pr.transferPrice().currency());
                System.out.println("Change Ownership: " +
 pr.changeOwnershipPrice().price() + " "
                        + pr.changeOwnershipPrice().currency());
                System.out.println(
                        "Restoration: " + pr.restorationPrice().price() + " " +
 pr.restorationPrice().currency());
                System.out.println(" ");
            }

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
           <domainType>

       Where:
           domainType - The domain type (for example, com).
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val domainType = args[0]
    println("Invokes ListPrices using a Paginated method.")
    listPricesPaginated(domainType)
}

suspend fun listPricesPaginated(domainType: String) {
    val pricesRequest = ListPricesRequest {
        maxItems = 10
        tld = domainType
    }
```

```
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListPricesreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações do registro de domínios do Route 53 usando SDKs da AWS
  - Verifique a disponibilidade de um domínio usando um SDK da AWS
  - Verifique a transferibilidade de um domínio usando um SDK da AWS
  - Obter detalhes de um domínio do registro de domínios do Route 53 usando um SDK da AWS
  - Obter detalhes de uma operação do registro de domínios do Route 53 usando um SDK da AWS
  - Obter sugestões de nomes de domínio do registro de domínios do Route 53 usando um SDK da AWS
  - Listar preços de domínios do registro de domínios do Route 53 usando um SDK da AWS
  - Listar os domínios registrados no registro de domínios do Route 53 usando um SDK da AWS
  - Listar as operações do registro de domínios do Route 53 usando um SDK da AWS
  - Registrar um domínio no registro de domínios do Route 53 usando um SDK da AWS
  - Visualizar os registros de cobrança do registro de domínios do Route 53 usando um SDK da AWS
- Cenários do registro de domínios do Route 53 usando SDKs da AWS
  - Começar a usar o registro de domínios do Route 53 com um SDK da AWS

Ações do registro de domínios do Route 53 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Route 53 domain registration com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do registro de domínios do Route 53 usando SDKs da AWS.

Exemplos

- Verifique a disponibilidade de um domínio usando um SDK da AWS
- Verifique a transferibilidade de um domínio usando um SDK da AWS
- Obter detalhes de um domínio do registro de domínios do Route 53 usando um SDK da AWS
- Obter detalhes de uma operação do registro de domínios do Route 53 usando um SDK da AWS
- Obter sugestões de nomes de domínio do registro de domínios do Route 53 usando um SDK da AWS
- Listar preços de domínios do registro de domínios do Route 53 usando um SDK da AWS
- Listar os domínios registrados no registro de domínios do Route 53 usando um SDK da AWS
- Listar as operações do registro de domínios do Route 53 usando um SDK da AWS
- Registrar um domínio no registro de domínios do Route 53 usando um SDK da AWS
- Visualizar os registros de cobrança do registro de domínios do Route 53 usando um SDK da AWS

Verifique a disponibilidade de um domínio usando um SDK da AWS

Os exemplos de código a seguir mostram como verificar a disponibilidade de um domínio.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Check the availability of a domain name.
/// </summary>
/// <param name="domain">The domain to check for availability.</param>
/// <returns>An availability result string.</returns>
public async Task<string> CheckDomainAvailability(string domain)
{
    var result = await _amazonRoute53Domains.CheckDomainAvailabilityAsync(
        new CheckDomainAvailabilityRequest
        {
            DomainName = domain
        }
    );
    return result.Availability.Value;
}
```

- Para obter detalhes da API, consulte CheckDomainAvailabilitya Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void checkDomainAvailability(Route53DomainsClient
 route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainAvailabilityRequest availabilityRequest =
 CheckDomainAvailabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainAvailabilityResponse response = route53DomainsClient
                    .checkDomainAvailability(availabilityRequest);
            System.out.println(domainSuggestion + " is " +
 response.availability().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CheckDomainAvailabilitya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkDomainAvailability(domainSuggestion: String) {
    val availabilityRequest = CheckDomainAvailabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainAvailability(availabilityRequest)
        println("$domainSuggestion is ${response.availability}")
```

```
    }
}
```

- Para obter detalhes da API, consulte a CheckDomainAvailabilityreferência da API AWSSDK for Kotlin.

Verifique a transferibilidade de um domínio usando um SDK da AWS

Os exemplos de código a seguir mostram como verificar a transferabilidade de um domínio.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Check the transferability of a domain name.
    /// </summary>
    /// <param name="domain">The domain to check for transferability.</param>
    /// <returns>A transferability result string.</returns>
    public async Task<string> CheckDomainTransferability(string domain)
    {
        var result = await _amazonRoute53Domains.CheckDomainTransferabilityAsync(
            new CheckDomainTransferabilityRequest
            {
                DomainName = domain
            }
        );
```

```
        return result.Transferability.Transferable.Value;
    }
```

- Para obter detalhes da API, consulte CheckDomainTransferabilitya Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkDomainTransferability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
       try {
           CheckDomainTransferabilityRequest transferabilityRequest =
CheckDomainTransferabilityRequest.builder()
                   .domainName(domainSuggestion)
                   .build();

           CheckDomainTransferabilityResponse response = route53DomainsClient
                   .checkDomainTransferability(transferabilityRequest);
           System.out.println("Transferability: " +
response.transferability().transferable().toString());

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte CheckDomainTransferabilitya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkDomainTransferability(domainSuggestion: String?) {
    val transferabilityRequest = CheckDomainTransferabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainTransferability(transferabilityRequest)
        println("Transferability: ${response.transferability?.transferable}")
    }
}
```

- Para obter detalhes da API, consulte a CheckDomainTransferabilityreferência da API AWSSDK for Kotlin.

Obter detalhes de um domínio do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como obter os detalhes de um domínio.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details for a domain.
    /// </summary>
    /// <returns>A string with detail information about the domain.</returns>
    public async Task<string> GetDomainDetail(string domainName)
    {
        try
        {
            var result = await _amazonRoute53Domains.GetDomainDetailAsync(
                new GetDomainDetailRequest()
                {
                    DomainName = domainName
                });
            var details = $"\tDomain {domainName}:\n" +
                          $"\tCreated on
{result.CreationDate.ToShortDateString()}.\n" +
                          $"\tAdmin contact is {result.AdminContact.Email}.\n" +
                          $"\tAuto-renew is {result.AutoRenew}.\n";

            return details;
        }
        catch (InvalidInputException)
        {
            return $"Domain {domainName} was not found in your account.";
        }
    }
```

- Para obter detalhes da API, consulte GetDomainDetaila Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getDomainDetails(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
       try {
           GetDomainDetailRequest detailRequest =
GetDomainDetailRequest.builder()
                   .domainName(domainSuggestion)
                   .build();

           GetDomainDetailResponse response =
route53DomainsClient.getDomainDetail(detailRequest);
           System.out.println("The contact first name is " +
response.registrantContact().firstName());
           System.out.println("The contact last name is " +
response.registrantContact().lastName());
           System.out.println("The contact org name is " +
response.registrantContact().organizationName());

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetDomainDetaila Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getDomainDetails(domainSuggestion: String?) {
    val detailRequest = GetDomainDetailRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainDetail(detailRequest)
        println("The contact first name is
 ${response.registrantContact?.firstName}")
        println("The contact last name is
 ${response.registrantContact?.lastName}")
        println("The contact org name is
 ${response.registrantContact?.organizationName}")
    }
}
```

- Para obter detalhes da API, consulte a GetDomainDetailreferência da API AWSSDK for Kotlin.

Obter detalhes de uma operação do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como obter os detalhes de uma operação.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details for a domain action operation.
    /// </summary>
    /// <param name="operationId">The operational Id.</param>
    /// <returns>A string describing the operational details.</returns>
    public async Task<string> GetOperationDetail(string? operationId)
    {
        if (operationId == null)
            return "Unable to get operational details because ID is null.";
        try
        {
            var operationDetails =
                await _amazonRoute53Domains.GetOperationDetailAsync(
                    new GetOperationDetailRequest
                    {
                        OperationId = operationId
                    }
                );

            var details = $"\tOperation {operationId}:\n" +
                          $"\tFor domain {operationDetails.DomainName} on
{operationDetails.SubmittedDate.ToShortDateString()}.\n" +
                          $"\tMessage is {operationDetails.Message}.\n" +
                          $"\tStatus is {operationDetails.Status}.\n";

            return details;
        }
        catch (AmazonRoute53DomainsException ex)
        {
            return $"Unable to get operation details. Here's why: {ex.Message}.";
        }
```

```
    }
```

- Para obter detalhes da API, consulte GetOperationDetail a Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getOperationalDetail(Route53DomainsClient
route53DomainsClient, String operationId) {
       try {
           GetOperationDetailRequest detailRequest =
GetOperationDetailRequest.builder()
                   .operationId(operationId)
                   .build();

           GetOperationDetailResponse response =
route53DomainsClient.getOperationDetail(detailRequest);
           System.out.println("Operation detail message is " +
response.message());

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetOperationDetail a Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getOperationalDetail(opId: String?) {
    val detailRequest = GetOperationDetailRequest {
        operationId = opId
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getOperationDetail(detailRequest)
        println("Operation detail message is ${response.message}")
    }
}
```

- Para obter detalhes da API, consulte a GetOperationDetailreferência da API AWSSDK for Kotlin.

Obter sugestões de nomes de domínio do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como obter sugestões de nomes de domínio.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of suggestions for a given domain.
    /// </summary>
    /// <param name="domain">The domain to check for suggestions.</param>
    /// <param name="onlyAvailable">If true, only returns available domains.</
param>
    /// <param name="suggestionCount">The number of suggestions to return.
 Defaults to the max of 50.</param>
    /// <returns>A collection of domain suggestions.</returns>
    public async Task<List<DomainSuggestion>> GetDomainSuggestions(string domain,
 bool onlyAvailable, int suggestionCount = 50)
    {
        var result = await _amazonRoute53Domains.GetDomainSuggestionsAsync(
            new GetDomainSuggestionsRequest
            {
                DomainName = domain,
                OnlyAvailable = onlyAvailable,
                SuggestionCount = suggestionCount
            }
        );
        return result.SuggestionsList;
    }
```

- Para obter detalhes da API, consulte GetDomainSuggestionsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listDomainSuggestions(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
       try {
           GetDomainSuggestionsRequest suggestionsRequest =
GetDomainSuggestionsRequest.builder()
                   .domainName(domainSuggestion)
                   .suggestionCount(5)
                   .onlyAvailable(true)
                   .build();

           GetDomainSuggestionsResponse response =
route53DomainsClient.getDomainSuggestions(suggestionsRequest);
           List<DomainSuggestion> suggestions = response.suggestionsList();
           for (DomainSuggestion suggestion : suggestions) {
               System.out.println("Suggestion Name: " +
suggestion.domainName());
               System.out.println("Availability: " + suggestion.availability());
               System.out.println(" ");
           }

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetDomainSuggestionsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDomainSuggestions(domainSuggestion: String?) {
    val suggestionsRequest = GetDomainSuggestionsRequest {
        domainName = domainSuggestion
        suggestionCount = 5
        onlyAvailable = true
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.getDomainSuggestions(suggestionsRequest)
        response.suggestionsList?.forEach { suggestion ->
            println("Suggestion Name: ${suggestion.domainName}")
            println("Availability: ${suggestion.availability}")
            println(" ")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetDomainSuggestionsreferência da API AWSSDK for Kotlin.

Listar preços de domínios do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como listar preços de domínios.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List prices for domain type operations.
    /// </summary>
    /// <param name="domainTypes">Domain types to include in the results.</param>
    /// <returns>The list of domain prices.</returns>
    public async Task<List<DomainPrice>> ListPrices(List<string> domainTypes)
    {
        var results = new List<DomainPrice>();
        var paginatePrices = _amazonRoute53Domains.Paginators.ListPrices(new
ListPricesRequest());
        // Get the entire list using the paginator.
        await foreach (var prices in paginatePrices.Prices)
        {
            results.Add(prices);
        }
        return results.Where(p => domainTypes.Contains(p.Name)).ToList();
    }
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listPrices(Route53DomainsClient route53DomainsClient,
String domainType) {
        try {
            ListPricesRequest pricesRequest = ListPricesRequest.builder()
                    .tld(domainType)
                    .build();

            ListPricesIterable listRes =
route53DomainsClient.listPricesPaginator(pricesRequest);
            listRes.stream()
                    .flatMap(r -> r.prices().stream())
                    .forEach(content -> System.out.println(" Name: " +
content.name() +
                            " Registration: " +
content.registrationPrice().price() + " "
                            + content.registrationPrice().currency() +
                            " Renewal: " + content.renewalPrice().price() + " " +
content.renewalPrice().currency()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllPrices(domainType: String?) {
    val pricesRequest = ListPricesRequest {
        tld = domainType
```

```
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListPricesreferência da API AWSSDK for Kotlin.

Listar os domínios registrados no registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os domínios registrados.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the domains for the account.
    /// </summary>
    /// <returns>A collection of domain summary records.</returns>
    public async Task<List<DomainSummary>> ListDomains()
    {
        var results = new List<DomainSummary>();
        var paginateDomains = _amazonRoute53Domains.Paginators.ListDomains(
            new ListDomainsRequest());

        // Get the entire list using the paginator.
        await foreach (var domain in paginateDomains.Domains)
        {
            results.Add(domain);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte ListDomainsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listDomains(Route53DomainsClient route53DomainsClient) {
        try {
            ListDomainsIterable listRes =
route53DomainsClient.listDomainsPaginator();
            listRes.stream()
                    .flatMap(r -> r.domains().stream())
                    .forEach(content -> System.out.println("The domain name is "
+ content.domainName()));
```

```
        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListDomainsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDomains() {
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listDomainsPaginated(ListDomainsRequest {})
            .transform { it.domains?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("The domain name is ${content.domainName}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListDomainsreferência da API AWSSDK for Kotlin.

Listar as operações do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como listar operações.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// List operations for the account that are submitted after a specified
date.
   /// </summary>
   /// <returns>A collection of operation summary records.</returns>
   public async Task<List<OperationSummary>> ListOperations(DateTime
submittedSince)
   {
       var results = new List<OperationSummary>();
       var paginateOperations = _amazonRoute53Domains.Paginators.ListOperations(
           new ListOperationsRequest()
           {
               SubmittedSince = submittedSince
           });

       // Get the entire list using the paginator.
       await foreach (var operations in paginateOperations.Operations)
       {
           results.Add(operations);
       }
       return results;
   }
```

- Para obter detalhes da API, consulte ListOperationsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listOperations(Route53DomainsClient route53DomainsClient)
{
       try {
           Date currentDate = new Date();
           LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
           ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
           localDateTime = localDateTime.minusYears(1);
           Instant myTime = localDateTime.toInstant(zoneOffset);

           ListOperationsRequest operationsRequest =
ListOperationsRequest.builder()
                   .submittedSince(myTime)
                   .build();

           ListOperationsIterable listRes =
route53DomainsClient.listOperationsPaginator(operationsRequest);
           listRes.stream()
                   .flatMap(r -> r.operations().stream())
                   .forEach(content -> System.out.println(" Operation Id: " +
content.operationId() +
                           " Status: " + content.statusAsString() +
                           " Date: " + content.submittedDate()));

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListOperationsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listOperations() {
    val currentDate = Date()
    var localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    localDateTime = localDateTime.minusYears(1)
    val myTime: java.time.Instant? = localDateTime.toInstant(zoneOffset)
    val time2: Instant? = myTime?.let { Instant(it) }
    val operationsRequest = ListOperationsRequest {
        submittedSince = time2
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listOperationsPaginated(operationsRequest)
            .transform { it.operations?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("Operation Id: ${content.operationId}")
                println("Status: ${content.status}")
                println("Date: ${content.submittedDate}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListOperationsreferência da API AWSSDK for Kotlin.

Registrar um domínio no registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como registrar um domínio.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate a domain registration request.
    /// </summary>
    /// <param name="contact">Contact details.</param>
    /// <param name="domainName">The domain name to register.</param>
    /// <param name="autoRenew">True if the domain should automatically renew.</
param>
    /// <param name="duration">The duration in years for the domain
 registration.</param>
    /// <returns>The operation Id.</returns>
    public async Task<string?> RegisterDomain(string domainName, bool autoRenew,
 int duration, ContactDetail contact)
    {
        // This example uses the same contact information for admin, registrant,
 and tech contacts.
        try
        {
            var result = await _amazonRoute53Domains.RegisterDomainAsync(
                new RegisterDomainRequest()
                {
                    AdminContact = contact,
                    RegistrantContact = contact,
```

```
                    TechContact = contact,
                    DomainName = domainName,
                    AutoRenew = autoRenew,
                    DurationInYears = duration,
                    PrivacyProtectAdminContact = false,
                    PrivacyProtectRegistrantContact = false,
                    PrivacyProtectTechContact = false
                }
            );
            return result.OperationId;
        }
        catch (InvalidInputException)
        {
            _logger.LogInformation($"Unable to request registration for domain
{domainName}");
            return null;
        }
    }
```

- Para obter detalhes da API, consulte RegisterDomaina Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String requestDomainRegistration(Route53DomainsClient
route53DomainsClient,
            String domainSuggestion,
            String phoneNumber,
            String email,
            String firstName,
            String lastName,
            String city) {
```

```
        try {
            ContactDetail contactDetail = ContactDetail.builder()
                    .contactType(ContactType.COMPANY)
                    .state("LA")
                    .countryCode(CountryCode.IN)
                    .email(email)
                    .firstName(firstName)
                    .lastName(lastName)
                    .city(city)
                    .phoneNumber(phoneNumber)
                    .organizationName("My Org")
                    .addressLine1("My Address")
                    .zipCode("123 123")
                    .build();

            RegisterDomainRequest domainRequest = RegisterDomainRequest.builder()
                    .adminContact(contactDetail)
                    .registrantContact(contactDetail)
                    .techContact(contactDetail)
                    .domainName(domainSuggestion)
                    .autoRenew(true)
                    .durationInYears(1)
                    .build();

            RegisterDomainResponse response =
route53DomainsClient.registerDomain(domainRequest);
            System.out.println("Registration requested. Operation Id: " +
response.operationId());
            return response.operationId();

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte RegisterDomaina Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun requestDomainRegistration(domainSuggestion: String?, phoneNumberVal:
 String?, emailVal: String?, firstNameVal: String?, lastNameVal: String?,
 cityVal: String?): String? {
    val contactDetail = ContactDetail {
        contactType = ContactType.Company
        state = "LA"
        countryCode = CountryCode.In
        email = emailVal
        firstName = firstNameVal
        lastName = lastNameVal
        city = cityVal
        phoneNumber = phoneNumberVal
        organizationName = "My Org"
        addressLine1 = "My Address"
        zipCode = "123 123"
    }

    val domainRequest = RegisterDomainRequest {
        adminContact = contactDetail
        registrantContact = contactDetail
        techContact = contactDetail
        domainName = domainSuggestion
        autoRenew = true
        durationInYears = 1
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.registerDomain(domainRequest)
        println("Registration requested. Operation Id: ${response.operationId}")
        return response.operationId
    }
}
```

- Para obter detalhes da API, consulte a RegisterDomainreferência da API AWSSDK for Kotlin.

Visualizar os registros de cobrança do registro de domínios do Route 53 usando um SDK da AWS

Os exemplos de código a seguir mostram como visualizar registros de cobrança.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de domínios

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// View billing records for the account between a start and end date.
    /// </summary>
    /// <param name="startDate">The start date for billing results.</param>
    /// <param name="endDate">The end date for billing results.</param>
    /// <returns>A collection of billing records.</returns>
    public async Task<List<BillingRecord>> ViewBilling(DateTime startDate,
DateTime endDate)
    {
        var results = new List<BillingRecord>();
        var paginateBilling = _amazonRoute53Domains.Paginators.ViewBilling(
            new ViewBillingRequest()
            {
                Start = startDate,
```

```
                End = endDate
            });

        // Get the entire list using the paginator.
        await foreach (var billingRecords in paginateBilling.BillingRecords)
        {
            results.Add(billingRecords);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte ViewBillinga Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listBillingRecords(Route53DomainsClient
route53DomainsClient) {
       try {
           Date currentDate = new Date();
           LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
           ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
           LocalDateTime localDateTime2 = localDateTime.minusYears(1);
           Instant myStartTime = localDateTime2.toInstant(zoneOffset);
           Instant myEndTime = localDateTime.toInstant(zoneOffset);

           ViewBillingRequest viewBillingRequest = ViewBillingRequest.builder()
                   .start(myStartTime)
                   .end(myEndTime)
                   .build();

           ViewBillingIterable listRes =
route53DomainsClient.viewBillingPaginator(viewBillingRequest);
```

```
            listRes.stream()
                    .flatMap(r -> r.billingRecords().stream())
                    .forEach(content -> System.out.println(" Bill Date:: " +
 content.billDate() +
                            " Operation: " + content.operationAsString() +
                            " Price: " + content.price()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ViewBillinga Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBillingRecords() {
    val currentDate = Date()
    val localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    val localDateTime2 = localDateTime.minusYears(1)
    val myStartTime = localDateTime2.toInstant(zoneOffset)
    val myEndTime = localDateTime.toInstant(zoneOffset)
    val timeStart: Instant? = myStartTime?.let { Instant(it) }
    val timeEnd: Instant? = myEndTime?.let { Instant(it) }

    val viewBillingRequest = ViewBillingRequest {
        start = timeStart
        end = timeEnd
    }
```

```
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.viewBillingPaginated(viewBillingRequest)
            .transform { it.billingRecords?.forEach { obj -> emit(obj) } }
            .collect { billing ->
                println("Bill Date: ${billing.billDate}")
                println("Operation: ${billing.operation}")
                println("Price: ${billing.price}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ViewBillingreferência da API AWSSDK for Kotlin.

Cenários do registro de domínios do Route 53 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Route 53 domain registration com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Começar a usar o registro de domínios do Route 53 com um SDK da AWS

Começar a usar o registro de domínios do Route 53 com um SDK da AWS

Os exemplos de código a seguir mostram como:

- Liste os domínios atuais e as operações do ano passado.
- Veja o faturamento do ano passado e os preços dos tipos de domínio.
- Receba sugestões de domínio.
- Verifique a disponibilidade e a transferibilidade de um domínio.
- Opcionalmente, solicite o registro de um domínio.
- Obtenha os detalhes de uma operação.
- Opcionalmente, obtenha os detalhes de um domínio.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public static class Route53DomainScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks:
        1. List current domains.
        2. List operations in the past year.
        3. View billing for the account in the past year.
        4. View prices for domain types.
        5. Get domain suggestions.
        6. Check domain availability.
        7. Check domain transferability.
        8. Optionally, request a domain registration.
        9. Get an operation detail.
       10. Optionally, get a domain detail.
   */

    private static Route53Wrapper _route53Wrapper = null!;
    private static IConfiguration _configuration = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
```

```
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
                    .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonRoute53Domains>()
                .AddTransient<Route53Wrapper>()
            )
            .Build();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();

        var logger = LoggerFactory.Create(builder =>
        {
            builder.AddConsole();
        }).CreateLogger(typeof(Route53DomainScenario));

        _route53Wrapper = host.Services.GetRequiredService<Route53Wrapper>();

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon Route 53 domains example
scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            await ListDomains();
            await ListOperations();
            await ListBillingRecords();
            await ListPrices();
            await ListDomainSuggestions();
            await CheckDomainAvailability();
            await CheckDomainTransferability();
            var operationId = await RequestDomainRegistration();
            await GetOperationalDetail(operationId);
            await GetDomainDetails();
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("The Amazon Route 53 domains example scenario is
complete.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List account registered domains.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDomains()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. List account domains.");
        var domains = await _route53Wrapper.ListDomains();
        for (int i = 0; i < domains.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {domains[i].DomainName}");
        }

        if (!domains.Any())
        {
            Console.WriteLine("\tNo domains found in this account.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List domain operations in the past year.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListOperations()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"2. List account domain operations in the past
year.");
        var operations = await _route53Wrapper.ListOperations(
            DateTime.Today.AddYears(-1));
        for (int i = 0; i < operations.Count; i++)
        {
            Console.WriteLine($"\tOperation Id: {operations[i].OperationId}");
            Console.WriteLine($"\tStatus: {operations[i].Status}");
```

```
            Console.WriteLine($"\tDate: {operations[i].SubmittedDate}");
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List billing in the past year.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListBillingRecords()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. View billing for the account in the past year.");
        var billingRecords = await _route53Wrapper.ViewBilling(
            DateTime.Today.AddYears(-1),
            DateTime.Today);
        for (int i = 0; i < billingRecords.Count; i++)
        {
            Console.WriteLine($"\tBill Date:
{billingRecords[i].BillDate.ToShortDateString()}");
            Console.WriteLine($"\tOperation: {billingRecords[i].Operation}");
            Console.WriteLine($"\tPrice: {billingRecords[i].Price}");
        }
        if (!billingRecords.Any())
        {
            Console.WriteLine("\tNo billing records found in this account for the
past year.");
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List prices for a few domain types.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListPrices()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. View prices for domain types.");
        var domainTypes = new List<string> { "net", "com", "org", "co" };

        var prices = await _route53Wrapper.ListPrices(domainTypes);
        foreach (var pr in prices)
        {
```

```
            Console.WriteLine($"\tName: {pr.Name}");
            Console.WriteLine($"\tRegistration: {pr.RegistrationPrice?.Price}
{pr.RegistrationPrice?.Currency}");
            Console.WriteLine($"\tRenewal: {pr.RenewalPrice?.Price}
{pr.RenewalPrice?.Currency}");
            Console.WriteLine($"\tTransfer: {pr.TransferPrice?.Price}
{pr.TransferPrice?.Currency}");
            Console.WriteLine($"\tChange Ownership:
{pr.ChangeOwnershipPrice?.Price} {pr.ChangeOwnershipPrice?.Currency}");
            Console.WriteLine($"\tRestoration: {pr.RestorationPrice?.Price}
{pr.RestorationPrice?.Currency}");
            Console.WriteLine();
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List domain suggestions for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDomainSuggestions()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"5. Get domain suggestions.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
            Console.WriteLine($"Enter a domain name to get available domain
suggestions.");
            domainName = Console.ReadLine();
        }

        var suggestions = await _route53Wrapper.GetDomainSuggestions(domainName,
true, 5);
        foreach (var suggestion in suggestions)
        {
            Console.WriteLine($"\tSuggestion Name: {suggestion.DomainName}");
            Console.WriteLine($"\tAvailability: {suggestion.Availability}");
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check availability for a domain name.
```

```
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckDomainAvailability()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. Check domain availability.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
            Console.WriteLine($"Enter a domain name to check domain
availability.");
            domainName = Console.ReadLine();
        }

        var availability = await
_route53Wrapper.CheckDomainAvailability(domainName);
        Console.WriteLine($"\tAvailability: {availability}");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check transferability for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckDomainTransferability()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Check domain transferability.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
            Console.WriteLine($"Enter a domain name to check domain
transferability.");
            domainName = Console.ReadLine();
        }

        var transferability = await
_route53Wrapper.CheckDomainTransferability(domainName);
        Console.WriteLine($"\tTransferability: {transferability}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
```

```
    /// Check transferability for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string?> RequestDomainRegistration()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. Optionally, request a domain registration.");

        Console.WriteLine($"\tNote: This example uses domain request settings in
 settings.json.");
        Console.WriteLine($"\tTo change the domain registration settings, set the
 values in that file.");
        Console.WriteLine($"\tRemember, registering an actual domain will incur
 an account billing cost.");
        Console.WriteLine($"\tWould you like to begin a domain registration? (y/
n)");
        var ynResponse = Console.ReadLine();
        if (ynResponse != null && ynResponse.Equals("y",
 StringComparison.InvariantCultureIgnoreCase))
        {
            string domainName = _configuration["DomainName"];
            ContactDetail contact = new ContactDetail();
            contact.CountryCode =
 CountryCode.FindValue(_configuration["Contact:CountryCode"]);
            contact.ContactType =
 ContactType.FindValue(_configuration["Contact:ContactType"]);

            _configuration.GetSection("Contact").Bind(contact);

            var operationId = await _route53Wrapper.RegisterDomain(
                domainName,
                Convert.ToBoolean(_configuration["AutoRenew"]),
                Convert.ToInt32(_configuration["DurationInYears"]),
                contact);
            if (operationId != null)
            {
                Console.WriteLine(
                    $"\tRegistration requested. Operation Id: {operationId}");
            }

            return operationId;
        }

        Console.WriteLine(new string('-', 80));
```

```
        return null;
    }

    /// <summary>
    /// Get details for an operation.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetOperationalDetail(string? operationId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Get an operation detail.");

        var operationDetails =
            await _route53Wrapper.GetOperationDetail(operationId);

        Console.WriteLine(operationDetails);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Optionally, get details for a registered domain.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string?> GetDomainDetails()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Get details on a domain.");

        Console.WriteLine($"\tNote: you must have a registered domain to get
details.");
        Console.WriteLine($"\tWould you like to get domain details? (y/n)");
        var ynResponse = Console.ReadLine();
        if (ynResponse != null && ynResponse.Equals("y",
StringComparison.InvariantCultureIgnoreCase))
        {
            string? domainName = null;
            while (domainName == null)
            {
                Console.WriteLine($"\tEnter a domain name to get details.");
                domainName = Console.ReadLine();
            }
```

```
            var domainDetails = await
 _route53Wrapper.GetDomainDetail(domainName);
            Console.WriteLine(domainDetails);
        }

        Console.WriteLine(new string('-', 80));
        return null;
    }
}
```

Os métodos de wrapper usados pelo cenário para as ações do registro de domínios do Route 53.

```
public class Route53Wrapper
{
    private readonly IAmazonRoute53Domains _amazonRoute53Domains;
    private readonly ILogger<Route53Wrapper> _logger;
    public Route53Wrapper(IAmazonRoute53Domains amazonRoute53Domains,
 ILogger<Route53Wrapper> logger)
    {
        _amazonRoute53Domains = amazonRoute53Domains;
        _logger = logger;
    }


    /// <summary>
    /// List prices for domain type operations.
    /// </summary>
    /// <param name="domainTypes">Domain types to include in the results.</param>
    /// <returns>The list of domain prices.</returns>
    public async Task<List<DomainPrice>> ListPrices(List<string> domainTypes)
    {
        var results = new List<DomainPrice>();
        var paginatePrices = _amazonRoute53Domains.Paginators.ListPrices(new
 ListPricesRequest());
        // Get the entire list using the paginator.
        await foreach (var prices in paginatePrices.Prices)
        {
            results.Add(prices);
        }
        return results.Where(p => domainTypes.Contains(p.Name)).ToList();
```

```
    }


    /// <summary>
    /// Check the availability of a domain name.
    /// </summary>
    /// <param name="domain">The domain to check for availability.</param>
    /// <returns>An availability result string.</returns>
    public async Task<string> CheckDomainAvailability(string domain)
    {
        var result = await _amazonRoute53Domains.CheckDomainAvailabilityAsync(
            new CheckDomainAvailabilityRequest
            {
                DomainName = domain
            }
        );
        return result.Availability.Value;
    }


    /// <summary>
    /// Check the transferability of a domain name.
    /// </summary>
    /// <param name="domain">The domain to check for transferability.</param>
    /// <returns>A transferability result string.</returns>
    public async Task<string> CheckDomainTransferability(string domain)
    {
        var result = await _amazonRoute53Domains.CheckDomainTransferabilityAsync(
            new CheckDomainTransferabilityRequest
            {
                DomainName = domain
            }
        );
        return result.Transferability.Transferable.Value;
    }


    /// <summary>
    /// Get a list of suggestions for a given domain.
    /// </summary>
    /// <param name="domain">The domain to check for suggestions.</param>
    /// <param name="onlyAvailable">If true, only returns available domains.</
param>
```

```
    /// <param name="suggestionCount">The number of suggestions to return.
Defaults to the max of 50.</param>
    /// <returns>A collection of domain suggestions.</returns>
    public async Task<List<DomainSuggestion>> GetDomainSuggestions(string domain,
bool onlyAvailable, int suggestionCount = 50)
    {
        var result = await _amazonRoute53Domains.GetDomainSuggestionsAsync(
            new GetDomainSuggestionsRequest
            {
                DomainName = domain,
                OnlyAvailable = onlyAvailable,
                SuggestionCount = suggestionCount
            }
        );
        return result.SuggestionsList;
    }


    /// <summary>
    /// Get details for a domain action operation.
    /// </summary>
    /// <param name="operationId">The operational Id.</param>
    /// <returns>A string describing the operational details.</returns>
    public async Task<string> GetOperationDetail(string? operationId)
    {
        if (operationId == null)
            return "Unable to get operational details because ID is null.";
        try
        {
            var operationDetails =
                await _amazonRoute53Domains.GetOperationDetailAsync(
                    new GetOperationDetailRequest
                    {
                        OperationId = operationId
                    }
                );

            var details = $"\tOperation {operationId}:\n" +
                          $"\tFor domain {operationDetails.DomainName} on
{operationDetails.SubmittedDate.ToShortDateString()}.\n" +
                          $"\tMessage is {operationDetails.Message}.\n" +
                          $"\tStatus is {operationDetails.Status}.\n";

            return details;
```

```
        }
        catch (AmazonRoute53DomainsException ex)
        {
            return $"Unable to get operation details. Here's why: {ex.Message}.";
        }
    }


    /// <summary>
    /// Initiate a domain registration request.
    /// </summary>
    /// <param name="contact">Contact details.</param>
    /// <param name="domainName">The domain name to register.</param>
    /// <param name="autoRenew">True if the domain should automatically renew.</
param>
    /// <param name="duration">The duration in years for the domain
 registration.</param>
    /// <returns>The operation Id.</returns>
    public async Task<string?> RegisterDomain(string domainName, bool autoRenew,
 int duration, ContactDetail contact)
    {
        // This example uses the same contact information for admin, registrant,
 and tech contacts.
        try
        {
            var result = await _amazonRoute53Domains.RegisterDomainAsync(
                new RegisterDomainRequest()
                {
                    AdminContact = contact,
                    RegistrantContact = contact,
                    TechContact = contact,
                    DomainName = domainName,
                    AutoRenew = autoRenew,
                    DurationInYears = duration,
                    PrivacyProtectAdminContact = false,
                    PrivacyProtectRegistrantContact = false,
                    PrivacyProtectTechContact = false
                }
            );
            return result.OperationId;
        }
        catch (InvalidInputException)
        {
```

```
            _logger.LogInformation($"Unable to request registration for domain
{domainName}");
            return null;
        }
    }


    /// <summary>
    /// View billing records for the account between a start and end date.
    /// </summary>
    /// <param name="startDate">The start date for billing results.</param>
    /// <param name="endDate">The end date for billing results.</param>
    /// <returns>A collection of billing records.</returns>
    public async Task<List<BillingRecord>> ViewBilling(DateTime startDate,
DateTime endDate)
    {
        var results = new List<BillingRecord>();
        var paginateBilling = _amazonRoute53Domains.Paginators.ViewBilling(
            new ViewBillingRequest()
            {
                Start = startDate,
                End = endDate
            });

        // Get the entire list using the paginator.
        await foreach (var billingRecords in paginateBilling.BillingRecords)
        {
            results.Add(billingRecords);
        }
        return results;
    }


    /// <summary>
    /// List the domains for the account.
    /// </summary>
    /// <returns>A collection of domain summary records.</returns>
    public async Task<List<DomainSummary>> ListDomains()
    {
        var results = new List<DomainSummary>();
        var paginateDomains = _amazonRoute53Domains.Paginators.ListDomains(
            new ListDomainsRequest());

        // Get the entire list using the paginator.
```

```
        await foreach (var domain in paginateDomains.Domains)
        {
            results.Add(domain);
        }
        return results;
    }


    /// <summary>
    /// List operations for the account that are submitted after a specified
date.
    /// </summary>
    /// <returns>A collection of operation summary records.</returns>
    public async Task<List<OperationSummary>> ListOperations(DateTime
submittedSince)
    {
        var results = new List<OperationSummary>();
        var paginateOperations = _amazonRoute53Domains.Paginators.ListOperations(
            new ListOperationsRequest()
            {
                SubmittedSince = submittedSince
            });

        // Get the entire list using the paginator.
        await foreach (var operations in paginateOperations.Operations)
        {
            results.Add(operations);
        }
        return results;
    }


    /// <summary>
    /// Get details for a domain.
    /// </summary>
    /// <returns>A string with detail information about the domain.</returns>
    public async Task<string> GetDomainDetail(string domainName)
    {
        try
        {
            var result = await _amazonRoute53Domains.GetDomainDetailAsync(
                new GetDomainDetailRequest()
                {
                    DomainName = domainName
```

```
                });
            var details = $"\tDomain {domainName}:\n" +
                          $"\tCreated on
 {result.CreationDate.ToShortDateString()}.\n" +
                          $"\tAdmin contact is {result.AdminContact.Email}.\n" +
                          $"\tAuto-renew is {result.AutoRenew}.\n";

            return details;
        }
        catch (InvalidInputException)
        {
            return $"Domain {domainName} was not found in your account.";
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This example uses pagination methods where applicable. For example, to list
 * domains, the
 * listDomainsPaginator method is used. For more information about pagination,
 * see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/
pagination.html
 *
 * This Java code example performs the following operations:
 *
 * 1. List current domains.
 * 2. List operations in the past year.
 * 3. View billing for the account in the past year.
 * 4. View prices for domain types.
 * 5. Get domain suggestions.
 * 6. Check domain availability.
 * 7. Check domain transferability.
 * 8. Request a domain registration.
 * 9. Get operation details.
 * 10. Optionally, get domain details.
 */

public class Route53Scenario {
```

```
   public static final String DASHES = new String(new char[80]).replace("\0",
"-");

   public static void main(String[] args) {
       final String usage = """

               Usage:
                   <domainType> <phoneNumber> <email> <domainSuggestion>
<firstName> <lastName> <city>

               Where:
                   domainType - The domain type (for example, com).\s
                   phoneNumber - The phone number to use (for example,
+91.9966564xxx)      email - The email address to use.      domainSuggestion -
The domain suggestion (for example, findmy.accountants).\s
                   firstName - The first name to use to register a domain.\s
                   lastName -  The last name to use to register a domain.\s
                   city - the city to use to register a domain.\s
                   """;

       if (args.length != 7) {
           System.out.println(usage);
           System.exit(1);
       }

       String domainType = args[0];
       String phoneNumber = args[1];
       String email = args[2];
       String domainSuggestion = args[3];
       String firstName = args[4];
       String lastName = args[5];
       String city = args[6];
       Region region = Region.US_EAST_1;
       Route53DomainsClient route53DomainsClient =
Route53DomainsClient.builder()
               .region(region)
               .build();

       System.out.println(DASHES);
       System.out.println("Welcome to the Amazon Route 53 domains example
scenario.");
       System.out.println(DASHES);

       System.out.println(DASHES);
```

```
        System.out.println("1. List current domains.");
        listDomains(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. List operations in the past year.");
        listOperations(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. View billing for the account in the past year.");
        listBillingRecords(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. View prices for domain types.");
        listPrices(route53DomainsClient, domainType);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get domain suggestions.");
        listDomainSuggestions(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Check domain availability.");
        checkDomainAvailability(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Check domain transferability.");
        checkDomainTransferability(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Request a domain registration.");
        String opId = requestDomainRegistration(route53DomainsClient,
domainSuggestion, phoneNumber, email, firstName,
                lastName, city);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get operation details.");
        getOperationalDetail(route53DomainsClient, opId);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get domain details.");
        System.out.println("Note: You must have a registered domain to get
details.");
        System.out.println("Otherwise, an exception is thrown that states ");
        System.out.println("Domain xxxxxxx not found in xxxxxxx account.");
        getDomainDetails(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);
    }

    public static void getDomainDetails(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            GetDomainDetailRequest detailRequest =
GetDomainDetailRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            GetDomainDetailResponse response =
route53DomainsClient.getDomainDetail(detailRequest);
            System.out.println("The contact first name is " +
response.registrantContact().firstName());
            System.out.println("The contact last name is " +
response.registrantContact().lastName());
            System.out.println("The contact org name is " +
response.registrantContact().organizationName());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getOperationalDetail(Route53DomainsClient
route53DomainsClient, String operationId) {
        try {
            GetOperationDetailRequest detailRequest =
GetOperationDetailRequest.builder()
                    .operationId(operationId)
                    .build();
```

```
            GetOperationDetailResponse response =
route53DomainsClient.getOperationDetail(detailRequest);
            System.out.println("Operation detail message is " +
response.message());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String requestDomainRegistration(Route53DomainsClient
route53DomainsClient,
            String domainSuggestion,
            String phoneNumber,
            String email,
            String firstName,
            String lastName,
            String city) {

        try {
            ContactDetail contactDetail = ContactDetail.builder()
                    .contactType(ContactType.COMPANY)
                    .state("LA")
                    .countryCode(CountryCode.IN)
                    .email(email)
                    .firstName(firstName)
                    .lastName(lastName)
                    .city(city)
                    .phoneNumber(phoneNumber)
                    .organizationName("My Org")
                    .addressLine1("My Address")
                    .zipCode("123 123")
                    .build();

            RegisterDomainRequest domainRequest = RegisterDomainRequest.builder()
                    .adminContact(contactDetail)
                    .registrantContact(contactDetail)
                    .techContact(contactDetail)
                    .domainName(domainSuggestion)
                    .autoRenew(true)
                    .durationInYears(1)
                    .build();
```

```
            RegisterDomainResponse response =
route53DomainsClient.registerDomain(domainRequest);
            System.out.println("Registration requested. Operation Id: " +
response.operationId());
            return response.operationId();

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void checkDomainTransferability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainTransferabilityRequest transferabilityRequest =
CheckDomainTransferabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainTransferabilityResponse response = route53DomainsClient
                    .checkDomainTransferability(transferabilityRequest);
            System.out.println("Transferability: " +
response.transferability().transferable().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void checkDomainAvailability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainAvailabilityRequest availabilityRequest =
CheckDomainAvailabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainAvailabilityResponse response = route53DomainsClient
                    .checkDomainAvailability(availabilityRequest);
            System.out.println(domainSuggestion + " is " +
response.availability().toString());
```

```
        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listDomainSuggestions(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            GetDomainSuggestionsRequest suggestionsRequest =
GetDomainSuggestionsRequest.builder()
                    .domainName(domainSuggestion)
                    .suggestionCount(5)
                    .onlyAvailable(true)
                    .build();

            GetDomainSuggestionsResponse response =
route53DomainsClient.getDomainSuggestions(suggestionsRequest);
            List<DomainSuggestion> suggestions = response.suggestionsList();
            for (DomainSuggestion suggestion : suggestions) {
                System.out.println("Suggestion Name: " +
suggestion.domainName());
                System.out.println("Availability: " + suggestion.availability());
                System.out.println(" ");
            }

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listPrices(Route53DomainsClient route53DomainsClient,
String domainType) {
        try {
            ListPricesRequest pricesRequest = ListPricesRequest.builder()
                    .tld(domainType)
                    .build();

            ListPricesIterable listRes =
route53DomainsClient.listPricesPaginator(pricesRequest);
            listRes.stream()
                    .flatMap(r -> r.prices().stream())
```

```
                    .forEach(content -> System.out.println(" Name: " +
content.name() +
                            " Registration: " +
content.registrationPrice().price() + " "
                            + content.registrationPrice().currency() +
                            " Renewal: " + content.renewalPrice().price() + " " +
content.renewalPrice().currency()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listBillingRecords(Route53DomainsClient
route53DomainsClient) {
        try {
            Date currentDate = new Date();
            LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
            ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
            LocalDateTime localDateTime2 = localDateTime.minusYears(1);
            Instant myStartTime = localDateTime2.toInstant(zoneOffset);
            Instant myEndTime = localDateTime.toInstant(zoneOffset);

            ViewBillingRequest viewBillingRequest = ViewBillingRequest.builder()
                    .start(myStartTime)
                    .end(myEndTime)
                    .build();

            ViewBillingIterable listRes =
route53DomainsClient.viewBillingPaginator(viewBillingRequest);
            listRes.stream()
                    .flatMap(r -> r.billingRecords().stream())
                    .forEach(content -> System.out.println(" Bill Date:: " +
content.billDate() +
                            " Operation: " + content.operationAsString() +
                            " Price: " + content.price()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
   public static void listOperations(Route53DomainsClient route53DomainsClient)
{
       try {
           Date currentDate = new Date();
           LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
           ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
           localDateTime = localDateTime.minusYears(1);
           Instant myTime = localDateTime.toInstant(zoneOffset);

           ListOperationsRequest operationsRequest =
ListOperationsRequest.builder()
                   .submittedSince(myTime)
                   .build();

           ListOperationsIterable listRes =
route53DomainsClient.listOperationsPaginator(operationsRequest);
           listRes.stream()
                   .flatMap(r -> r.operations().stream())
                   .forEach(content -> System.out.println(" Operation Id: " +
content.operationId() +
                           " Status: " + content.statusAsString() +
                           " Date: " + content.submittedDate()));

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }

   public static void listDomains(Route53DomainsClient route53DomainsClient) {
       try {
           ListDomainsIterable listRes =
route53DomainsClient.listDomainsPaginator();
           listRes.stream()
                   .flatMap(r -> r.domains().stream())
                   .forEach(content -> System.out.println("The domain name is "
+ content.domainName()));

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
```

```
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

This Kotlin code example performs the following operations:

1. List current domains.
```

```
2. List operations in the past year.
3. View billing for the account in the past year.
4. View prices for domain types.
5. Get domain suggestions.
6. Check domain availability.
7. Check domain transferability.
8. Request a domain registration.
9. Get operation details.
10. Optionally, get domain details.
 */

val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <domainType> <phoneNumber> <email> <domainSuggestion> <firstName>
 <lastName> <city>
        Where:
           domainType - The domain type (for example, com).
           phoneNumber - The phone number to use (for example, +1.2065550100)

           email - The email address to use.
           domainSuggestion - The domain suggestion (for example,
 findmy.example).
           firstName - The first name to use to register a domain.
           lastName -  The last name to use to register a domain.
           city - The city to use to register a domain.
    """

    if (args.size != 7) {
        println(usage)
        exitProcess(1)
    }

    val domainType = args[0]
    val phoneNumber = args[1]
    val email = args[2]
    val domainSuggestion = args[3]
    val firstName = args[4]
    val lastName = args[5]
    val city = args[6]

    println(DASHES)
    println("Welcome to the Amazon Route 53 domains example scenario.")
```

```
    println(DASHES)

    println(DASHES)
    println("1. List current domains.")
    listDomains()
    println(DASHES)

    println(DASHES)
    println("2. List operations in the past year.")
    listOperations()
    println(DASHES)

    println(DASHES)
    println("3. View billing for the account in the past year.")
    listBillingRecords()
    println(DASHES)

    println(DASHES)
    println("4. View prices for domain types.")
    listAllPrices(domainType)
    println(DASHES)

    println(DASHES)
    println("5. Get domain suggestions.")
    listDomainSuggestions(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("6. Check domain availability.")
    checkDomainAvailability(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("7. Check domain transferability.")
    checkDomainTransferability(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("8. Request a domain registration.")
    val opId = requestDomainRegistration(domainSuggestion, phoneNumber, email,
firstName, lastName, city)
    println(DASHES)

    println(DASHES)
```

```
    println("9. Get operation details.")
    getOperationalDetail(opId)
    println(DASHES)

    println(DASHES)
    println("10. Get domain details.")
    println("Note: You must have a registered domain to get details.")
    println("Otherwise an exception is thrown that states ")
    println("Domain xxxxxxx not found in xxxxxxx account.")
    getDomainDetails(domainSuggestion)
    println(DASHES)
}

suspend fun getDomainDetails(domainSuggestion: String?) {
    val detailRequest = GetDomainDetailRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainDetail(detailRequest)
        println("The contact first name is
 ${response.registrantContact?.firstName}")
        println("The contact last name is
 ${response.registrantContact?.lastName}")
        println("The contact org name is
 ${response.registrantContact?.organizationName}")
    }
}

suspend fun getOperationalDetail(opId: String?) {
    val detailRequest = GetOperationDetailRequest {
        operationId = opId
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getOperationDetail(detailRequest)
        println("Operation detail message is ${response.message}")
    }
}

suspend fun requestDomainRegistration(domainSuggestion: String?, phoneNumberVal:
 String?, emailVal: String?, firstNameVal: String?, lastNameVal: String?,
 cityVal: String?): String? {
    val contactDetail = ContactDetail {
        contactType = ContactType.Company
        state = "LA"
```

```
        countryCode = CountryCode.In
        email = emailVal
        firstName = firstNameVal
        lastName = lastNameVal
        city = cityVal
        phoneNumber = phoneNumberVal
        organizationName = "My Org"
        addressLine1 = "My Address"
        zipCode = "123 123"
    }

    val domainRequest = RegisterDomainRequest {
        adminContact = contactDetail
        registrantContact = contactDetail
        techContact = contactDetail
        domainName = domainSuggestion
        autoRenew = true
        durationInYears = 1
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.registerDomain(domainRequest)
        println("Registration requested. Operation Id: ${response.operationId}")
        return response.operationId
    }
}

suspend fun checkDomainTransferability(domainSuggestion: String?) {
    val transferabilityRequest = CheckDomainTransferabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainTransferability(transferabilityRequest)
        println("Transferability: ${response.transferability?.transferable}")
    }
}

suspend fun checkDomainAvailability(domainSuggestion: String) {
    val availabilityRequest = CheckDomainAvailabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
```

```
        val response =
 route53DomainsClient.checkDomainAvailability(availabilityRequest)
        println("$domainSuggestion is ${response.availability}")
    }
}

suspend fun listDomainSuggestions(domainSuggestion: String?) {
    val suggestionsRequest = GetDomainSuggestionsRequest {
        domainName = domainSuggestion
        suggestionCount = 5
        onlyAvailable = true
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.getDomainSuggestions(suggestionsRequest)
        response.suggestionsList?.forEach { suggestion ->
            println("Suggestion Name: ${suggestion.domainName}")
            println("Availability: ${suggestion.availability}")
            println(" ")
        }
    }
}

suspend fun listAllPrices(domainType: String?) {
    val pricesRequest = ListPricesRequest {
        tld = domainType
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}
```

```
suspend fun listBillingRecords() {
    val currentDate = Date()
    val localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    val localDateTime2 = localDateTime.minusYears(1)
    val myStartTime = localDateTime2.toInstant(zoneOffset)
    val myEndTime = localDateTime.toInstant(zoneOffset)
    val timeStart: Instant? = myStartTime?.let { Instant(it) }
    val timeEnd: Instant? = myEndTime?.let { Instant(it) }

    val viewBillingRequest = ViewBillingRequest {
        start = timeStart
        end = timeEnd
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.viewBillingPaginated(viewBillingRequest)
            .transform { it.billingRecords?.forEach { obj -> emit(obj) } }
            .collect { billing ->
                println("Bill Date: ${billing.billDate}")
                println("Operation: ${billing.operation}")
                println("Price: ${billing.price}")
            }
    }
}

suspend fun listOperations() {
    val currentDate = Date()
    var localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    localDateTime = localDateTime.minusYears(1)
    val myTime: java.time.Instant? = localDateTime.toInstant(zoneOffset)
    val time2: Instant? = myTime?.let { Instant(it) }
    val operationsRequest = ListOperationsRequest {
        submittedSince = time2
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listOperationsPaginated(operationsRequest)
            .transform { it.operations?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("Operation Id: ${content.operationId}")
```

```
                println("Status: ${content.status}")
                println("Date: ${content.submittedDate}")
            }
    }
}

suspend fun listDomains() {
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listDomainsPaginated(ListDomainsRequest {})
            .transform { it.domains?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("The domain name is ${content.domainName}")
            }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Exemplos de código do Amazon S3 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Storage Service (Amazon S3) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do Amazon S3 – Mais informações sobre o Amazon S3.
- Referência da API do Amazon S3 – Detalhes sobre todas as ações disponíveis do Amazon S3.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)
```

```
# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS s3)

# Set this project's name.
project("hello_s3")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you
 may need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_s3.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_s3.cpp.

```
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <iostream>
#include <aws/core/auth/AWSCredentialsProviderChain.h>
using namespace Aws;
using namespace Aws::Auth;

/*
 *  A "Hello S3" starter application which initializes an Amazon Simple Storage
 Service (Amazon S3) client
 *  and lists the Amazon S3 buckets in the selected region.
 *
 *  main function
 *
 *  Usage: 'hello_s3'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        // You don't normally have to test that you are authenticated. But the
 S3 service permits anonymous requests, thus the s3Client will return "success"
 and 0 buckets even if you are unauthenticated, which can be confusing to a new
 user.
        auto provider =
 Aws::MakeShared<DefaultAWSCredentialsProviderChain>("alloc-tag");
        auto creds = provider->GetAWSCredentials();
        if (creds.IsEmpty()) {
            std::cerr << "Failed authentication" << std::endl;
        }

        Aws::S3::S3Client s3Client(clientConfig);
        auto outcome = s3Client.ListBuckets();
```

```
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed with error: " << outcome.GetError() <<
 std::endl;
            result = 1;
        } else {
            std::cout << "Found " << outcome.GetResult().GetBuckets().size()
                      << " buckets\n";
            for (auto &bucket: outcome.GetResult().GetBuckets()) {
                std::cout << bucket.GetName() << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Storage Service
```

```
// (Amazon S3) client and list up to 10 buckets in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 s3Client := s3.NewFromConfig(sdkConfig)
 count := 10
 fmt.Printf("Let's list up to %v buckets for your account.\n", count)
 result, err := s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 if err != nil {
  fmt.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
  return
 }
 if len(result.Buckets) == 0 {
  fmt.Println("You don't have any buckets!")
 } else {
  if count > len(result.Buckets) {
   count = len(result.Buckets)
  }
  for _, bucket := range result.Buckets[:count] {
   fmt.Printf("\t%v\n", *bucket.Name)
  }
 }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.Bucket;
import software.amazon.awssdk.services.s3.model.ListBucketsResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloS3 {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBuckets(s3);
    }

    public static void listBuckets(S3Client s3) {
        try {
            ListBucketsResponse response = s3.listBuckets();
            List<Bucket> bucketList = response.buckets();
            bucketList.forEach(bucket -> {
                System.out.println("Bucket Name: " + bucket.name());
```

```
            });

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";

// When no region or credentials are provided, the SDK will use the
// region and credentials from the local AWS config.
const client = new S3Client({});

export const helloS3 = async () => {
  const command = new ListBucketsCommand({});

  const { Buckets } = await client.send(command);
  console.log("Buckets: ");
  console.log(Buckets.map((bucket) => bucket.Name).join("\n"));
  return Buckets;
};
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use Aws\S3\S3Client;

$client = new S3Client(['region' => 'us-west-2']);
$results = $client->listBuckets();
var_dump($results);
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_s3():
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Simple Storage Service
    (Amazon S3) resource and list the buckets in your account.
    This example uses the default settings specified in your shared credentials
    and config files.
    """
    s3_resource = boto3.resource("s3")
```

```
    print("Hello, Amazon S3! Let's list your buckets:")
    for bucket in s3_resource.buckets.all():
        print(f"\t{bucket.name}")


if __name__ == "__main__":
    hello_s3()
```

- Para obter detalhes da API, consulte a ListBucketsReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações do Amazon S3 usando SDKs da AWS
  - Adicionar regras de CORS a um bucket do Amazon S3 usando um SDK da AWS
  - Adicionar uma configuração de ciclo de vida a um bucket do Amazon S3 usando um AWS SDK
  - Adicionar uma política a um bucket do Amazon S3 usando um SDK da AWS
  - Cancelar multipart uploads usando um SDK da AWS
  - Concluir uma ação de multipart upload usando um AWS SDK
  - Copiar um objeto de um bucket do Amazon S3 para outro usando um AWS SDK
  - Crie um ponto de acesso multirregional Amazon S3 usando um SDK AWS
  - Criar um bucket do Amazon S3 usando um AWS SDK
  - Criar uma estrutura de carregamento fracionado usando um AWS SDK
  - Excluir regras de CORS de um bucket do Amazon S3 usando um AWS SDK
  - Excluir uma política de um bucket do Amazon S3 usando um AWS SDK
  - Excluir um bucket vazio do Amazon S3 usando um AWS SDK
  - Excluir um objeto do Amazon S3 usando um AWS SDK
  - Excluir vários objetos de um bucket do Amazon S3 usando um AWS SDK
  - Excluir a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK
  - Excluir a configuração de site de um bucket do Amazon S3 usando um AWS SDK
  - Determinar a existência e o tipo de conteúdo de um objeto em um bucket do Amazon S3 usando um AWS SDK
  - Determinar a existência de um bucket do Amazon S3 usando um AWS SDK

- Fazer download de todos os objetos de um bucket do Amazon Simple Storage Service (Amazon S3) em um diretório local
- Habilitar o registro em log em um bucket do Amazon S3 usando um AWS SDK
- Habilitar notificações para um bucket do Amazon S3 usando um AWS SDK
- Habilitar a aceleração de transferência para um bucket do Amazon S3 usando um AWS SDK
- Obter regras de CORS para um bucket do Amazon S3 usando um AWS SDK
- Obtenha um objeto Amazon S3 de um ponto de acesso multirregional usando um SDK AWS
- Obter um objeto de um bucket do Amazon S3 usando um AWS SDK
- Obter um objeto de um bucket do Amazon S3 usando um AWS SDK e especificando um cabeçalho If-Modified-Since
- Obter a ACL de um bucket do Amazon S3 usando um AWS SDK
- Obter a ACL de um bucket do Amazon S3 usando um AWS SDK
- Obter a região em que reside o bucket do Amazon S3 usando um AWS SDK
- Obter a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK
- Obter a política de um bucket do Amazon S3 usando um AWS SDK
- Obter a configuração de site de um bucket do Amazon S3 usando um AWS SDK
- Listar buckets do Amazon S3 usando um AWS SDK
- Listar carregamentos fracionados em andamento para um bucket do Amazon S3 usando um AWS SDK
- Listar a versão de objetos em um bucket do Amazon S3 usando um AWS SDK
- Listar objetos em um bucket do Amazon S3 usando um AWS SDK
- Restaurar uma cópia arquivada de um objeto em um bucket do Amazon S3 usando um AWS SDK
- Definir uma nova ACL para um bucket do Amazon S3 usando um AWS SDK
- Definir a ACL de um objeto do Amazon S3 usando um AWS SDK
- Definir a configuração de site de um bucket do Amazon S3 usando um AWS SDK
- Exemplos de abordagens para testes de unidade e integração com SDK da AWS
- Fazer upload de uma única parte de um carregamento fracionado usando um AWS SDK
- Carregar um objeto em um bucket do Amazon S3 usando um AWS SDK
- Fazer upload recursivo de um diretório local em um bucket do Amazon Simple Storage Service (Amazon S3)

- Cenários do Amazon S3 usando AWS SDKs
  - Criar um URL pré-assinado para o Amazon S3 usando um AWS SDK
  - Uma página da web que oferece uma lista de objetos do Amazon S3 usando um AWS SDK
  - Conceitos básicos de buckets e objetos do Amazon S3 usando um AWS SDK
  - Conceitos básicos de criptografia para objetos do Amazon S3 usando um AWS SDK
  - Conceitos básicos de etiquetas para objetos do Amazon S3 usando um AWS SDK
  - Gerenciar listas de controle de acesso (ACLs) para buckets do Amazon S3 usando um AWS SDK
  - Gerenciar objetos do Amazon S3 versionados em lotes com uma função do Lambda usando um AWS SDK
  - Analisar URIs do Amazon S3 usando um AWS SDK
  - Executar uma cópia multipart de um objeto do Amazon S3 usando um AWS SDK
  - Realizar um carregamento fracionado em um objeto do Amazon S3 usando um AWS SDK
  - Fazer upload ou download de arquivos grandes de e para o Amazon S3 usando um AWS SDK
  - Faça upload de um fluxo de tamanho desconhecido em um objeto do Amazon S3 usando um AWS SDK
  - Usar somas de verificação para trabalhar com um objeto do Amazon S3 usando um AWS SDK
  - Trabalhar com objetos versionados do Amazon S3 usando um AWS SDK
- Exemplos sem servidor para o Amazon S3 usando AWS SDKs
  - Invocar uma função do Lambda em um acionador do Amazon S3
- Exemplos do Amazon S3 entre serviços usando AWS SDKs
  - Criar uma aplicação Amazon Transcribe
  - Converter texto em fala e de volta em texto usando um AWS SDK
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Criar uma aplicação de exploração do Amazon Textract
  - Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
  - Detectar entidades em texto extraído de uma imagem usando um AWS SDK
  - Detectar faces em uma imagem usando um AWS SDK
  - Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

  - Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

- Salvar o EXIF e outras informações de imagem usando um AWS SDK

Ações do Amazon S3 usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Storage Service (Amazon S3) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do Amazon S3 usando AWS SDKs.

Exemplos

- Adicionar regras de CORS a um bucket do Amazon S3 usando um SDK da AWS
- Adicionar uma configuração de ciclo de vida a um bucket do Amazon S3 usando um AWS SDK
- Adicionar uma política a um bucket do Amazon S3 usando um SDK da AWS
- Cancelar multipart uploads usando um SDK da AWS
- Concluir uma ação de multipart upload usando um AWS SDK
- Copiar um objeto de um bucket do Amazon S3 para outro usando um AWS SDK
- Crie um ponto de acesso multirregional Amazon S3 usando um SDK AWS
- Criar um bucket do Amazon S3 usando um AWS SDK
- Criar uma estrutura de carregamento fracionado usando um AWS SDK
- Excluir regras de CORS de um bucket do Amazon S3 usando um AWS SDK
- Excluir uma política de um bucket do Amazon S3 usando um AWS SDK
- Excluir um bucket vazio do Amazon S3 usando um AWS SDK
- Excluir um objeto do Amazon S3 usando um AWS SDK
- Excluir vários objetos de um bucket do Amazon S3 usando um AWS SDK
- Excluir a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK
- Excluir a configuração de site de um bucket do Amazon S3 usando um AWS SDK
- Determinar a existência e o tipo de conteúdo de um objeto em um bucket do Amazon S3 usando um AWS SDK
- Determinar a existência de um bucket do Amazon S3 usando um AWS SDK
- Fazer download de todos os objetos de um bucket do Amazon Simple Storage Service (Amazon S3) em um diretório local
- Habilitar o registro em log em um bucket do Amazon S3 usando um AWS SDK

- Habilitar notificações para um bucket do Amazon S3 usando um AWS SDK
- Habilitar a aceleração de transferência para um bucket do Amazon S3 usando um AWS SDK
- Obter regras de CORS para um bucket do Amazon S3 usando um AWS SDK
- Obtenha um objeto Amazon S3 de um ponto de acesso multirregional usando um SDK AWS
- Obter um objeto de um bucket do Amazon S3 usando um AWS SDK
- Obter um objeto de um bucket do Amazon S3 usando um AWS SDK e especificando um cabeçalho If-Modified-Since
- Obter a ACL de um bucket do Amazon S3 usando um AWS SDK
- Obter a ACL de um bucket do Amazon S3 usando um AWS SDK
- Obter a região em que reside o bucket do Amazon S3 usando um AWS SDK
- Obter a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK
- Obter a política de um bucket do Amazon S3 usando um AWS SDK
- Obter a configuração de site de um bucket do Amazon S3 usando um AWS SDK
- Listar buckets do Amazon S3 usando um AWS SDK
- Listar carregamentos fracionados em andamento para um bucket do Amazon S3 usando um AWS SDK
- Listar a versão de objetos em um bucket do Amazon S3 usando um AWS SDK
- Listar objetos em um bucket do Amazon S3 usando um AWS SDK
- Restaurar uma cópia arquivada de um objeto em um bucket do Amazon S3 usando um AWS SDK
- Definir uma nova ACL para um bucket do Amazon S3 usando um AWS SDK
- Definir a ACL de um objeto do Amazon S3 usando um AWS SDK
- Definir a configuração de site de um bucket do Amazon S3 usando um AWS SDK
- Exemplos de abordagens para testes de unidade e integração com SDK da AWS
- Fazer upload de uma única parte de um carregamento fracionado usando um AWS SDK
- Carregar um objeto em um bucket do Amazon S3 usando um AWS SDK
- Fazer upload recursivo de um diretório local em um bucket do Amazon Simple Storage Service (Amazon S3)

Adicionar regras de CORS a um bucket do Amazon S3 usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Add CORS configuration to the Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to apply the CORS configuration to an Amazon S3 bucket.</param>
        /// <param name="configuration">The CORS configuration to apply.</param>
        private static async Task PutCORSConfigurationAsync(AmazonS3Client
client, CORSConfiguration configuration)
        {
            PutCORSConfigurationRequest request = new
PutCORSConfigurationRequest()
            {
                BucketName = BucketName,
                Configuration = configuration,
            };

            _ = await client.PutCORSConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte exemplo habilita solicitações `PUT`, `POST` e `DELETE` de www.example.com e solicitações `GET` de qualquer domínio:

```
aws s3api put-bucket-cors --bucket MyBucket --cors-configuration file://cors.json

cors.json:
{
  "CORSRules": [
    {
      "AllowedOrigins": ["http://www.example.com"],
      "AllowedHeaders": ["*"],
      "AllowedMethods": ["PUT", "POST", "DELETE"],
      "MaxAgeSeconds": 3000,
      "ExposeHeaders": ["x-amz-server-side-encryption"]
    },
    {
      "AllowedOrigins": ["*"],
      "AllowedHeaders": ["Authorization"],
      "AllowedMethods": ["GET"],
      "MaxAgeSeconds": 3000
    }
  ]
}
```

- Para obter detalhes da API, consulte PutBucketCorsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import java.util.ArrayList;
import java.util.List;
import software.amazon.awssdk.services.s3.model.GetBucketCorsRequest;
import software.amazon.awssdk.services.s3.model.GetBucketCorsResponse;
import software.amazon.awssdk.services.s3.model.DeleteBucketCorsRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
```

```
import software.amazon.awssdk.services.s3.model.CORSRule;
import software.amazon.awssdk.services.s3.model.CORSConfiguration;
import software.amazon.awssdk.services.s3.model.PutBucketCorsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class S3Cors {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <accountId>\s

                Where:
                    bucketName - The Amazon S3 bucket to upload an object into.
                    accountId - The id of the account that owns the Amazon S3
 bucket.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String accountId = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setCorsInformation(s3, bucketName, accountId);
        getBucketCorsInformation(s3, bucketName, accountId);
        deleteBucketCorsInformation(s3, bucketName, accountId);
        s3.close();
    }
```

```
   public static void deleteBucketCorsInformation(S3Client s3, String
bucketName, String accountId) {
       try {
           DeleteBucketCorsRequest bucketCorsRequest =
DeleteBucketCorsRequest.builder()
                   .bucket(bucketName)
                   .expectedBucketOwner(accountId)
                   .build();

           s3.deleteBucketCors(bucketCorsRequest);

       } catch (S3Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void getBucketCorsInformation(S3Client s3, String bucketName,
String accountId) {
       try {
           GetBucketCorsRequest bucketCorsRequest =
GetBucketCorsRequest.builder()
                   .bucket(bucketName)
                   .expectedBucketOwner(accountId)
                   .build();

           GetBucketCorsResponse corsResponse =
s3.getBucketCors(bucketCorsRequest);
           List<CORSRule> corsRules = corsResponse.corsRules();
           for (CORSRule rule : corsRules) {
               System.out.println("allowOrigins: " + rule.allowedOrigins());
               System.out.println("AllowedMethod: " + rule.allowedMethods());
           }

       } catch (S3Exception e) {

           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void setCorsInformation(S3Client s3, String bucketName, String
accountId) {
       List<String> allowMethods = new ArrayList<>();
```

```
        allowMethods.add("PUT");
        allowMethods.add("POST");
        allowMethods.add("DELETE");

        List<String> allowOrigins = new ArrayList<>();
        allowOrigins.add("http://example.com");
        try {
            // Define CORS rules.
            CORSRule corsRule = CORSRule.builder()
                    .allowedMethods(allowMethods)
                    .allowedOrigins(allowOrigins)
                    .build();

            List<CORSRule> corsRules = new ArrayList<>();
            corsRules.add(corsRule);
            CORSConfiguration configuration = CORSConfiguration.builder()
                    .corsRules(corsRules)
                    .build();

            PutBucketCorsRequest putBucketCorsRequest =
 PutBucketCorsRequest.builder()
                    .bucket(bucketName)
                    .corsConfiguration(configuration)
                    .expectedBucketOwner(accountId)
                    .build();

            s3.putBucketCors(putBucketCorsRequest);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione uma regra de CORS.

```
import { PutBucketCorsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// By default, Amazon S3 doesn't allow cross-origin requests. Use this command
// to explicitly allow cross-origin requests.
export const main = async () => {
  const command = new PutBucketCorsCommand({
    Bucket: "test-bucket",
    CORSConfiguration: {
      CORSRules: [
        {
          // Allow all headers to be sent to this bucket.
          AllowedHeaders: ["*"],
          // Allow only GET and PUT methods to be sent to this bucket.
          AllowedMethods: ["GET", "PUT"],
          // Allow only requests from the specified origin.
          AllowedOrigins: ["https://www.example.com"],
          // Allow the entity tag (ETag) header to be returned in the response.
 The ETag header
          // The entity tag represents a specific version of the object. The ETag
 reflects
          // changes only to the contents of an object, not its metadata.
          ExposeHeaders: ["ETag"],
          // How long the requesting browser should cache the preflight response.
 After
          // this time, the preflight request will have to be made again.
          MaxAgeSeconds: 3600,
        },
      ],
    },
```

```
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def put_cors(self, cors_rules):
        """
```

```
        Apply CORS rules to the bucket. CORS rules specify the HTTP actions that
 are
        allowed from other domains.

        :param cors_rules: The CORS rules to apply.
        """
        try:
            self.bucket.Cors().put(CORSConfiguration={"CORSRules": cors_rules})
            logger.info(
                "Put CORS rules %s for bucket '%s'.", cors_rules,
 self.bucket.name
            )
        except ClientError:
            logger.exception("Couldn't put CORS rules for bucket %s.",
 self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketCorsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with
 an existing bucket.
  def initialize(bucket_cors)
```

```
    @bucket_cors = bucket_cors
  end

  # Sets CORS rules on a bucket.
  #
  # @param allowed_methods [Array<String>] The types of HTTP requests to allow.
  # @param allowed_origins [Array<String>] The origins to allow.
  # @returns [Boolean] True if the CORS rules were set; otherwise, false.
  def set_cors(allowed_methods, allowed_origins)
    @bucket_cors.put(
      cors_configuration: {
        cors_rules: [
          {
            allowed_methods: allowed_methods,
            allowed_origins: allowed_origins,
            allowed_headers: %w[*],
            max_age_seconds: 3600
          }
        ]
      }
    )
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't set CORS rules for #{@bucket_cors.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for Ruby da API.

Adicionar uma configuração de ciclo de vida a um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como adicionar a configuração de ciclo de vida a um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Trabalhar com objetos versionados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Adds lifecycle configuration information to the S3 bucket named in
        /// the bucketName parameter.
        /// </summary>
        /// <param name="client">The S3 client used to call the
        /// PutLifecycleConfigurationAsync method.</param>
        /// <param name="bucketName">A string representing the S3 bucket to
        /// which configuration information will be added.</param>
        /// <param name="configuration">A LifecycleConfiguration object that
        /// will be applied to the S3 bucket.</param>
        public static async Task AddExampleLifecycleConfigAsync(IAmazonS3 client,
string bucketName, LifecycleConfiguration configuration)
        {
            var request = new PutLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
                Configuration = configuration,
            };
            var response = await client.PutLifecycleConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte PutBucketLifecycleConfigurationa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando aplica a configuração de ciclo de vida ao bucket `my-bucket`:

```
aws s3api put-bucket-lifecycle-configuration --bucket my-bucket --lifecycle-
configuration  file://lifecycle.json
```

O arquivo `lifecycle.json` é um documento JSON na pasta atual que especifica duas regras:

```
{
    "Rules": [
        {
            "ID": "Move rotated logs to Glacier",
            "Prefix": "rotated/",
            "Status": "Enabled",
            "Transitions": [
                {
                    "Date": "2015-11-10T00:00:00.000Z",
                    "StorageClass": "GLACIER"
                }
            ]
        },
        {
            "Status": "Enabled",
            "Prefix": "",
            "NoncurrentVersionTransitions": [
                {
                    "NoncurrentDays": 2,
                    "StorageClass": "GLACIER"
                }
            ],
            "ID": "Move old versions to Glacier"
        }
    ]
}
```

A primeira regra move arquivos com o prefixo `rotated` para o Glacier na data especificada. A segunda regra move versões antigas de objetos para o Glacier quando elas não estão mais

atualizadas. Para obter mais informações sobre formatos de data/hora aceitáveis, consulte Especificar valores de parâmetro Guia do usuário da AWS CLI.

- Para obter detalhes da API, consulte PutBucketLifecycleConfigurationem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.LifecycleRuleFilter;
import software.amazon.awssdk.services.s3.model.Transition;
import
 software.amazon.awssdk.services.s3.model.GetBucketLifecycleConfigurationRequest;
import
 software.amazon.awssdk.services.s3.model.GetBucketLifecycleConfigurationResponse;
import software.amazon.awssdk.services.s3.model.DeleteBucketLifecycleRequest;
import software.amazon.awssdk.services.s3.model.TransitionStorageClass;
import software.amazon.awssdk.services.s3.model.LifecycleRule;
import software.amazon.awssdk.services.s3.model.ExpirationStatus;
import software.amazon.awssdk.services.s3.model.BucketLifecycleConfiguration;
import
 software.amazon.awssdk.services.s3.model.PutBucketLifecycleConfigurationRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class LifecycleConfiguration {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                  <bucketName> <accountId>\s

                                Where:
                                  bucketName - The Amazon Simple Storage Service
 (Amazon S3) bucket to upload an object into.
                                  accountId - The id of the account that owns the
 Amazon S3 bucket.
                                """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String bucketName = args[0];
                String accountId = args[1];
                Region region = Region.US_EAST_1;
                S3Client s3 = S3Client.builder()
                                .region(region)
                                .build();

                setLifecycleConfig(s3, bucketName, accountId);
                getLifecycleConfig(s3, bucketName, accountId);
                deleteLifecycleConfig(s3, bucketName, accountId);
                System.out.println("You have successfully created, updated, and
 deleted a Lifecycle configuration");
                s3.close();
        }

        public static void setLifecycleConfig(S3Client s3, String bucketName,
 String accountId) {
                try {
                        // Create a rule to archive objects with the
 "glacierobjects/" prefix to Amazon
                        // S3 Glacier.
```

```
                        LifecycleRuleFilter ruleFilter =
LifecycleRuleFilter.builder()
                                        .prefix("glacierobjects/")
                                        .build();

                        Transition transition = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                        .days(0)
                                        .build();

                        LifecycleRule rule1 = LifecycleRule.builder()
                                        .id("Archive immediately rule")
                                        .filter(ruleFilter)
                                        .transitions(transition)
                                        .status(ExpirationStatus.ENABLED)
                                        .build();

                        // Create a second rule.
                        Transition transition2 = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                        .days(0)
                                        .build();

                        List<Transition> transitionList = new ArrayList<>();
                        transitionList.add(transition2);

                        LifecycleRuleFilter ruleFilter2 =
LifecycleRuleFilter.builder()
                                        .prefix("glacierobjects/")
                                        .build();

                        LifecycleRule rule2 = LifecycleRule.builder()
                                        .id("Archive and then delete rule")
                                        .filter(ruleFilter2)
                                        .transitions(transitionList)
                                        .status(ExpirationStatus.ENABLED)
                                        .build();

                        // Add the LifecycleRule objects to an ArrayList.
                        ArrayList<LifecycleRule> ruleList = new ArrayList<>();
                        ruleList.add(rule1);
                        ruleList.add(rule2);
```

```
                        BucketLifecycleConfiguration lifecycleConfiguration =
BucketLifecycleConfiguration.builder()
                                        .rules(ruleList)
                                        .build();

                        PutBucketLifecycleConfigurationRequest
putBucketLifecycleConfigurationRequest = PutBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)

.lifecycleConfiguration(lifecycleConfiguration)
                                        .expectedBucketOwner(accountId)
                                        .build();


s3.putBucketLifecycleConfiguration(putBucketLifecycleConfigurationRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }

        // Retrieve the configuration and add a new rule.
        public static void getLifecycleConfig(S3Client s3, String bucketName,
String accountId) {
                try {
                        GetBucketLifecycleConfigurationRequest
getBucketLifecycleConfigurationRequest = GetBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)
                                        .expectedBucketOwner(accountId)
                                        .build();

                        GetBucketLifecycleConfigurationResponse response = s3

.getBucketLifecycleConfiguration(getBucketLifecycleConfigurationRequest);
                        List<LifecycleRule> newList = new ArrayList<>();
                        List<LifecycleRule> rules = response.rules();
                        for (LifecycleRule rule : rules) {
                                newList.add(rule);
                        }
```

```
                        // Add a new rule with both a prefix predicate and a tag
predicate.
                        LifecycleRuleFilter ruleFilter =
LifecycleRuleFilter.builder()
                                        .prefix("YearlyDocuments/")
                                        .build();

                        Transition transition = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                        .days(3650)
                                        .build();

                        LifecycleRule rule1 = LifecycleRule.builder()
                                        .id("NewRule")
                                        .filter(ruleFilter)
                                        .transitions(transition)
                                        .status(ExpirationStatus.ENABLED)
                                        .build();

                        // Add the new rule to the list.
                        newList.add(rule1);
                        BucketLifecycleConfiguration lifecycleConfiguration =
BucketLifecycleConfiguration.builder()
                                        .rules(newList)
                                        .build();

                        PutBucketLifecycleConfigurationRequest
putBucketLifecycleConfigurationRequest = PutBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)

.lifecycleConfiguration(lifecycleConfiguration)
                                        .expectedBucketOwner(accountId)
                                        .build();


s3.putBucketLifecycleConfiguration(putBucketLifecycleConfigurationRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
```

```
        // Delete the configuration from the Amazon S3 bucket.
        public static void deleteLifecycleConfig(S3Client s3, String bucketName,
 String accountId) {
                try {
                        DeleteBucketLifecycleRequest deleteBucketLifecycleRequest
 = DeleteBucketLifecycleRequest
                                        .builder()
                                        .bucket(bucketName)
                                        .expectedBucketOwner(accountId)
                                        .build();

                        s3.deleteBucketLifecycle(deleteBucketLifecycleRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte PutBucketLifecycleConfigurationa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
```

```
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def put_lifecycle_configuration(self, lifecycle_rules):
        """
        Apply a lifecycle configuration to the bucket. The lifecycle
configuration can
        be used to archive or delete the objects in the bucket according to
specified
        parameters, such as a number of days.

        :param lifecycle_rules: The lifecycle rules to apply.
        """
        try:
            self.bucket.LifecycleConfiguration().put(
                LifecycleConfiguration={"Rules": lifecycle_rules}
            )
            logger.info(
                "Put lifecycle rules %s for bucket '%s'.",
                lifecycle_rules,
                self.bucket.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't put lifecycle rules for bucket '%s'.", self.bucket.name
            )
            raise
```

- Para obter detalhes da API, consulte a PutBucketLifecycleConfigurationReferência da API AWSSDK for Python (Boto3).

Adicionar uma política a um bucket do Amazon S3 usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar uma política a um bucket do S3.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutBucketPolicy(const Aws::String &bucketName,
                                 const Aws::String &policyBody,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    std::shared_ptr<Aws::StringStream> request_body =
            Aws::MakeShared<Aws::StringStream>("");
    *request_body << policyBody;

    Aws::S3::Model::PutBucketPolicyRequest request;
    request.SetBucket(bucketName);
    request.SetBody(request_body);

    Aws::S3::Model::PutBucketPolicyOutcome outcome =
            s3_client.PutBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketPolicy: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Set the following policy body for the bucket '" <<
                  bucketName << "':" << std::endl << std::endl;
        std::cout << policyBody << std::endl;
    }

    return outcome.IsSuccess();
}


//! Build a policy JSON string.
```

```
/*!
  \sa GetPolicyString()
  \param userArn Aws user Amazon Resource Name (ARN).
      For more information, see https://docs.aws.amazon.com/IAM/latest/UserGuide/
reference_identifiers.html#identifiers-arns.
  \param bucketName Name of a bucket.
*/

Aws::String GetPolicyString(const Aws::String &userArn,
                            const Aws::String &bucketName) {
    return
            "{\n"
            "   \"Version\":\"2012-10-17\",\n"
            "   \"Statement\":[\n"
            "       {\n"
            "           \"Sid\": \"1\",\n"
            "           \"Effect\": \"Allow\",\n"
            "           \"Principal\": {\n"
            "               \"AWS\": \""
            + userArn +
            "\"\n""           },\n"
            "           \"Action\": [ \"s3:GetObject\" ],\n"
            "           \"Resource\": [ \"arn:aws:s3:::"
            + bucketName +
            "/*\" ]\n"
            "       }\n"
            "   ]\n"
            "}";
}
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Este exemplo permite que todos os usuários recuperem qualquer objeto MyBucket, exceto aqueles no MySecretFolder. Ele também concede permissões `put` e `delete` ao usuário raiz da conta da AWS `1234-5678-9012`:

```
aws s3api put-bucket-policy --bucket MyBucket --policy file://policy.json

policy.json:
{
   "Statement": [
      {
         "Effect": "Allow",
         "Principal": "*",
         "Action": "s3:GetObject",
         "Resource": "arn:aws:s3:::MyBucket/*"
      },
      {
         "Effect": "Deny",
         "Principal": "*",
         "Action": "s3:GetObject",
         "Resource": "arn:aws:s3:::MyBucket/MySecretFolder/*"
      },
      {
         "Effect": "Allow",
         "Principal": {
            "AWS": "arn:aws:iam::123456789012:root"
         },
         "Action": [
            "s3:DeleteObject",
            "s3:PutObject"
         ],
         "Resource": "arn:aws:s3:::MyBucket/*"
      }
   ]
}
```

- Para obter detalhes da API, consulte PutBucketPolicyem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutBucketPolicyRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import java.io.IOException;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.List;
import com.fasterxml.jackson.core.JsonParser;
import com.fasterxml.jackson.databind.ObjectMapper;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SetBucketPolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <polFile>

                Where:
                    bucketName - The Amazon S3 bucket to set the policy on.
                    polFile - A JSON file containing the policy (see the Amazon
 S3 Readme for an example).\s
```

```
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String polFile = args[1];
        String policyText = getBucketPolicyFromFile(polFile);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setPolicy(s3, bucketName, policyText);
        s3.close();
    }

    public static void setPolicy(S3Client s3, String bucketName, String
 policyText) {
        System.out.println("Setting policy:");
        System.out.println("----");
        System.out.println(policyText);
        System.out.println("----");
        System.out.format("On Amazon S3 bucket: \"%s\"\n", bucketName);

        try {
            PutBucketPolicyRequest policyReq = PutBucketPolicyRequest.builder()
                    .bucket(bucketName)
                    .policy(policyText)
                    .build();

            s3.putBucketPolicy(policyReq);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        System.out.println("Done!");
    }

    // Loads a JSON-formatted policy from a file
```

```
    public static String getBucketPolicyFromFile(String policyFile) {

        StringBuilder fileText = new StringBuilder();
        try {
            List<String> lines = Files.readAllLines(Paths.get(policyFile),
 StandardCharsets.UTF_8);
            for (String line : lines) {
                fileText.append(line);
            }

        } catch (IOException e) {
            System.out.format("Problem reading file: \"%s\"", policyFile);
            System.out.println(e.getMessage());
        }

        try {
            final JsonParser parser = new
 ObjectMapper().getFactory().createParser(fileText.toString());
            while (parser.nextToken() != null) {
            }

        } catch (IOException jpe) {
            jpe.printStackTrace();
        }
        return fileText.toString();
    }
}
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione a política.

```
import { PutBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new PutBucketPolicyCommand({
    Policy: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Sid: "AllowGetObject",
          // Allow this particular user to call GetObject on any object in this
 bucket.
          Effect: "Allow",
          Principal: {
            AWS: "arn:aws:iam::ACCOUNT-ID:user/USERNAME",
          },
          Action: "s3:GetObject",
          Resource: "arn:aws:s3:::BUCKET-NAME/*",
        },
      ],
    }),
    // Apply the preceding policy to this bucket.
    Bucket: "BUCKET-NAME",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def put_policy(self, policy):
        """
        Apply a security policy to the bucket. Policies control users' ability
        to perform specific actions, such as listing the objects in the bucket.

        :param policy: The policy to apply to the bucket.
        """
        try:
            self.bucket.Policy().put(Policy=json.dumps(policy))
            logger.info("Put policy %s for bucket '%s'.", policy,
 self.bucket.name)
        except ClientError:
            logger.exception("Couldn't apply policy to bucket '%s'.",
 self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy

  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object
 configured with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  # Sets a policy on a bucket.
  #
  def set_policy(policy)
    @bucket_policy.put(policy: policy)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't set the policy for #{@bucket_policy.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for Ruby da API.

Cancelar multipart uploads usando um SDK da AWS

O exemplo de código a seguir mostra como cancelar multipart uploads.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Transfer;

/// <summary>
/// This example shows how to use the Amazon Simple Storage Service
/// (Amazon S3) to stop a multi-part upload process using the Amazon S3
/// TransferUtility.
/// </summary>
public class AbortMPU
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the S3 client object's constructor.
        // For example: RegionEndpoint.USWest2.
        IAmazonS3 client = new AmazonS3Client();

        await AbortMPUAsync(client, bucketName);
    }

    /// <summary>
    /// Cancels the multi-part copy process.
    /// </summary>
```

```
        /// <param name="client">The initialized client object used to create
        /// the TransferUtility object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the
        /// multi-part copy operation is in progress.</param>
        public static async Task AbortMPUAsync(IAmazonS3 client, string
bucketName)
        {
            try
            {
                var transferUtility = new TransferUtility(client);

                // Cancel all in-progress uploads initiated before the specified
date.
                await transferUtility.AbortMultipartUploadsAsync(
                    bucketName, DateTime.Now.AddDays(-7));
            }
            catch (AmazonS3Exception e)
            {
                Console.WriteLine($"Error: {e.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte AbortMultipartUploadsa Referência AWS SDK for .NET da API.

Concluir uma ação de multipart upload usando um AWS SDK

Os exemplos de código a seguir mostram como concluir uma ação de upload fracionado.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Executar uma cópia multipart
- Realizar um carregamento fracionado
- Usar somas de verificação

CLI

AWS CLI

O seguinte comando conclui um upload fracionado da chave `multipart/01` no bucket `my-bucket`:

```
aws s3api complete-multipart-upload --multipart-upload file://
mpustruct --bucket my-bucket --key 'multipart/01' --upload-id
 dfRtDYU0WWCCcH43C3WFbkRONycyCpTJJvxu2i5GYkZljF.Yxwh6XG7WfS2vC4to6HiV6Yjlx.cph0gtNBtJ8P3U
```

O ID de upload exigido por esse comando é a saída de `create-multipart-upload` e também pode ser recuperado com `list-multipart-uploads`.

A opção de upload fracionado no comando acima usa uma estrutura JSON que descreve quais partes do upload fracionado devem ser reagrupadas no arquivo completo. Neste exemplo, o prefixo `file://` é usado para carregar a estrutura JSON de um arquivo na pasta local chamada `mpustruct`.

mpustruct:

```
{
  "Parts": [
    {
      "ETag": "e868e0f4719e394144ef36531ee6824c",
      "PartNumber": 1
    },
    {
      "ETag": "6bb2b12753d66fe86da4998aa33fffb0",
      "PartNumber": 2
    },
    {
      "ETag": "d0a0112e841abec9c9ec83406f0159c8",
      "PartNumber": 3
    }
  ]
}
```

O valor de ETag de cada parte carregada é gerado sempre que você fizer o upload de uma parte usando o comando `upload-part`. Ele também pode ser recuperado ao chamar `list-parts` ou calculado fazendo a soma de verificação MD5 de cada parte.

Saída:

```
{
    "ETag": "\"3944a9f7a4faab7f78788ff6210f63f0-3\"",
    "Bucket": "my-bucket",
    "Location": "https://my-bucket.s3.amazonaws.com/multipart%2F01",
    "Key": "multipart/01"
}
```

- Para obter detalhes da API, consulte CompleteMultipartUploadem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    let _complete_multipart_upload_res = client
        .complete_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .multipart_upload(completed_multipart_upload)
        .upload_id(upload_id)
        .send()
        .await
        .unwrap();
```

- Para obter detalhes da API, consulte a CompleteMultipartUploadreferência da API AWS SDK for Rust.

Copiar um objeto de um bucket do Amazon S3 para outro usando um AWS SDK

Os exemplos de código a seguir mostram como copiar um objeto do S3 de um bucket para outro.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Conceitos básicos de buckets e objetos
- Conceitos básicos de criptografia

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

public class CopyObject
{
    public static async Task Main()
    {
        // Specify the AWS Region where your buckets are located if it is
        // different from the AWS Region of the default user.
        IAmazonS3 s3Client = new AmazonS3Client();

        // Remember to change these values to refer to your Amazon S3
objects.
        string sourceBucketName = "doc-example-bucket1";
        string destinationBucketName = "doc-example-bucket2";
        string sourceObjectKey = "testfile.txt";
        string destinationObjectKey = "testfilecopy.txt";

        Console.WriteLine($"Copying {sourceObjectKey} from {sourceBucketName}
to ");
        Console.WriteLine($"{destinationBucketName} as
{destinationObjectKey}");
```

```
            var response = await CopyingObjectAsync(
                s3Client,
                sourceObjectKey,
                destinationObjectKey,
                sourceBucketName,
                destinationBucketName);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine("\nCopy complete.");
            }
        }

        /// <summary>
        /// This method calls the AWS SDK for .NET to copy an
        /// object from one Amazon S3 bucket to another.
        /// </summary>
        /// <param name="client">The Amazon S3 client object.</param>
        /// <param name="sourceKey">The name of the object to be copied.</param>
        /// <param name="destinationKey">The name under which to save the copy.</
param>
        /// <param name="sourceBucketName">The name of the Amazon S3 bucket
        /// where the file is located now.</param>
        /// <param name="destinationBucketName">The name of the Amazon S3
        /// bucket where the copy should be saved.</param>
        /// <returns>Returns a CopyObjectResponse object with the results from
        /// the async call.</returns>
        public static async Task<CopyObjectResponse> CopyingObjectAsync(
            IAmazonS3 client,
            string sourceKey,
            string destinationKey,
            string sourceBucketName,
            string destinationBucketName)
        {
            var response = new CopyObjectResponse();
            try
            {
                var request = new CopyObjectRequest
                {
                    SourceBucket = sourceBucketName,
                    SourceKey = sourceKey,
                    DestinationBucket = destinationBucketName,
                    DestinationKey = destinationKey,
                };
```

```
                response = await client.CopyObjectAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error copying object: '{ex.Message}'");
            }

            return response;
        }
    }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function copy_item_in_bucket
#
# This function creates a copy of the specified file in the same bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file from and to.
#       $2 - The key of the source file to copy.
```

```
#       $3 - The key of the destination file.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_item_in_bucket() {
  local bucket_name=$1
  local source_key=$2
  local destination_key=$3
  local response

  response=$(aws s3api copy-object \
    --bucket "$bucket_name" \
    --copy-source "$bucket_name/$source_key" \
    --key "$destination_key")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api copy-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte CopyObjectem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::CopyObject(const Aws::String &objectKey, const Aws::String
 &fromBucket, const Aws::String &toBucket,
                            const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);
```

```
    Aws::S3::Model::CopyObjectRequest request;

    request.WithCopySource(fromBucket + "/" + objectKey)
            .WithKey(objectKey)
            .WithBucket(toBucket);

    Aws::S3::Model::CopyObjectOutcome outcome = client.CopyObject(request);
    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: CopyObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;

    }
    else {
        std::cout << "Successfully copied " << objectKey << " from " <<
 fromBucket <<
                  " to " << toBucket << "." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for C++ da API.

CLI

AWS CLI

O comando a seguir copia um objeto de `bucket-1` para `bucket-2`:

```
aws s3api copy-object --copy-source bucket-1/test.txt --key test.txt --bucket
 bucket-2
```

Saída:

```
{
    "CopyObjectResult": {
        "LastModified": "2015-11-10T01:07:25.000Z",
        "ETag": "\"589c8b79c230a6ecd5a7e1d040a9a030\""
    },
```

```
    "VersionId": "YdnYvTCVDqRRFA.NFJjy36p0hxifMlkA"
}
```

- Para obter detalhes da API, consulte CopyObjectem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// CopyToBucket copies an object in a bucket to another bucket.
func (basics BucketBasics) CopyToBucket(sourceBucket string, destinationBucket
 string, objectKey string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(destinationBucket),
  CopySource: aws.String(fmt.Sprintf("%v/%v", sourceBucket, objectKey)),
  Key:        aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v. Here's why: %v\n",
   sourceBucket, objectKey, destinationBucket, objectKey, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CopyObjectRequest;
import software.amazon.awssdk.services.s3.model.CopyObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class CopyObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <objectKey> <fromBucket> <toBucket>

                Where:
                    objectKey - The name of the object (for example, book.pdf).
```

```
                    fromBucket - The S3 bucket name that contains the object (for
example, bucket1).
                    toBucket - The S3 bucket to copy the object to (for example,
bucket2).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String objectKey = args[0];
        String fromBucket = args[1];
        String toBucket = args[2];
        System.out.format("Copying object %s from bucket %s to %s\n", objectKey,
fromBucket, toBucket);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        copyBucketObject(s3, fromBucket, objectKey, toBucket);
        s3.close();
    }

    public static String copyBucketObject(S3Client s3, String fromBucket, String
objectKey, String toBucket) {
        CopyObjectRequest copyReq = CopyObjectRequest.builder()
                .sourceBucket(fromBucket)
                .sourceKey(objectKey)
                .destinationBucket(toBucket)
                .destinationKey(objectKey)
                .build();

        try {
            CopyObjectResponse copyRes = s3.copyObject(copyReq);
            return copyRes.copyObjectResult().toString();

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

```
}
```

Use um S3 TransferManager para copiar um objeto de um bucket para outro. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.model.CopyObjectRequest;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedCopy;
import software.amazon.awssdk.transfer.s3.model.Copy;
import software.amazon.awssdk.transfer.s3.model.CopyRequest;

import java.util.UUID;

    public String copyObject(S3TransferManager transferManager, String
 bucketName,
            String key, String destinationBucket, String destinationKey) {
        CopyObjectRequest copyObjectRequest = CopyObjectRequest.builder()
                .sourceBucket(bucketName)
                .sourceKey(key)
                .destinationBucket(destinationBucket)
                .destinationKey(destinationKey)
                .build();

        CopyRequest copyRequest = CopyRequest.builder()
                .copyObjectRequest(copyObjectRequest)
                .build();

        Copy copy = transferManager.copy(copyRequest);

        CompletedCopy completedCopy = copy.completionFuture().join();
        return completedCopy.response().copyObjectResult().eTag();
    }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie o objeto.

```
import { S3Client, CopyObjectCommand } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new CopyObjectCommand({
    CopySource: "SOURCE_BUCKET/SOURCE_OBJECT_KEY",
    Bucket: "DESTINATION_BUCKET",
    Key: "NEW_OBJECT_KEY",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun copyBucketObject(
    fromBucket: String,
    objectKey: String,
    toBucket: String
) {
    var encodedUrl = ""
    try {
        encodedUrl = URLEncoder.encode("$fromBucket/$objectKey",
 StandardCharsets.UTF_8.toString())
    } catch (e: UnsupportedEncodingException) {
        println("URL could not be encoded: " + e.message)
    }

    val request = CopyObjectRequest {
        copySource = encodedUrl
        bucket = toBucket
        key = objectKey
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.copyObject(request)
    }
}
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cópia simples de um objeto.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $folder = "copied-folder";
            $this->s3client->copyObject([
                'Bucket' => $this->bucketName,
                'CopySource' => "$this->bucketName/$fileName",
                'Key' => "$folder/$fileName-copy",
            ]);
            echo "Copied $fileName to $folder/$fileName-copy.\n";
        } catch (Exception $exception) {
            echo "Failed to copy $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with object copying before continuing.");
        }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def copy(self, dest_object):
        """
        Copies the object to another bucket.

        :param dest_object: The destination object initialized with a bucket and
 key.
                            This is a Boto3 Object resource.
        """
        try:
            dest_object.copy_from(
                CopySource={"Bucket": self.object.bucket_name, "Key":
 self.object.key}
            )
            dest_object.wait_until_exists()
            logger.info(
                "Copied object from %s:%s to %s:%s.",
                self.object.bucket_name,
                self.object.key,
                dest_object.bucket_name,
                dest_object.key,
            )
        except ClientError:
            logger.exception(
                "Couldn't copy object from %s/%s to %s/%s.",
                self.object.bucket_name,
                self.object.key,
                dest_object.bucket_name,
                dest_object.key,
            )
            raise
```

- Para obter detalhes da API, consulte a CopyObjectReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie um objeto.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectCopyWrapper
  attr_reader :source_object

  # @param source_object [Aws::S3::Object] An existing Amazon S3 object. This is
 used as the source object for
  #                                          copy actions.
  def initialize(source_object)
    @source_object = source_object
  end

  # Copy the source object to the specified target bucket and rename it with the
 target key.
  #
  # @param target_bucket [Aws::S3::Bucket] An existing Amazon S3 bucket where the
 object is copied.
  # @param target_object_key [String] The key to give the copy of the object.
  # @return [Aws::S3::Object, nil] The copied object when successful; otherwise,
 nil.
  def copy_object(target_bucket, target_object_key)
    @source_object.copy_to(bucket: target_bucket.name, key: target_object_key)
    target_bucket.object(target_object_key)
```

```
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't copy #{@source_object.key} to #{target_object_key}. Here's
 why: #{e.message}"
  end
end

# Example usage:
def run_demo
  source_bucket_name = "doc-example-bucket1"
  source_key = "my-source-file.txt"
  target_bucket_name = "doc-example-bucket2"
  target_key = "my-target-file.txt"

  source_bucket = Aws::S3::Bucket.new(source_bucket_name)
  wrapper = ObjectCopyWrapper.new(source_bucket.object(source_key))
  target_bucket = Aws::S3::Bucket.new(target_bucket_name)
  target_object = wrapper.copy_object(target_bucket, target_key)
  return unless target_object

  puts "Copied #{source_key} from #{source_bucket_name} to
 #{target_object.bucket_name}:#{target_object.key}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Copie um objeto e adicione criptografia no lado do servidor ao objeto de destino.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectCopyEncryptWrapper
  attr_reader :source_object

  # @param source_object [Aws::S3::Object] An existing Amazon S3 object. This is
 used as the source object for
  #                                        copy actions.
  def initialize(source_object)
    @source_object = source_object
  end

  # Copy the source object to the specified target bucket, rename it with the
 target key, and encrypt it.
```

```
  #
  # @param target_bucket [Aws::S3::Bucket] An existing Amazon S3 bucket where the
 object is copied.
  # @param target_object_key [String] The key to give the copy of the object.
  # @return [Aws::S3::Object, nil] The copied object when successful; otherwise,
 nil.
  def copy_object(target_bucket, target_object_key, encryption)
    @source_object.copy_to(bucket: target_bucket.name, key: target_object_key,
 server_side_encryption: encryption)
    target_bucket.object(target_object_key)
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't copy #{@source_object.key} to #{target_object_key}. Here's
 why: #{e.message}"
  end
end

# Example usage:
def run_demo
  source_bucket_name = "doc-example-bucket1"
  source_key = "my-source-file.txt"
  target_bucket_name = "doc-example-bucket2"
  target_key = "my-target-file.txt"
  target_encryption = "AES256"

  source_bucket = Aws::S3::Bucket.new(source_bucket_name)
  wrapper = ObjectCopyEncryptWrapper.new(source_bucket.object(source_key))
  target_bucket = Aws::S3::Bucket.new(target_bucket_name)
  target_object = wrapper.copy_object(target_bucket, target_key,
 target_encryption)
  return unless target_object

  puts "Copied #{source_key} from #{source_bucket_name} to
 #{target_object.bucket_name}:#{target_object.key} and "\
       "encrypted the target with #{target_object.server_side_encryption}
 encryption."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn copy_object(
    client: &Client,
    bucket_name: &str,
    object_key: &str,
    target_key: &str,
) -> Result<CopyObjectOutput, SdkError<CopyObjectError>> {
    let mut source_bucket_and_object: String = "".to_owned();
    source_bucket_and_object.push_str(bucket_name);
    source_bucket_and_object.push('/');
    source_bucket_and_object.push_str(object_key);

    client
        .copy_object()
        .copy_source(source_bucket_and_object)
        .bucket(bucket_name)
        .key(target_key)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_s3->copyobject(
      iv_bucket = iv_dest_bucket
      iv_key = iv_dest_object
      iv_copysource = |{ iv_src_bucket }/{ iv_src_object }|
    ).
    MESSAGE 'Object copied to another bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
  CATCH /aws1/cx_s3_nosuchkey.
    MESSAGE 'Object key does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func copyFile(from sourceBucket: String, name: String, to destBucket:
 String) async throws {
        let srcUrl = ("\(sourceBucket)/
\(name)").addingPercentEncoding(withAllowedCharacters: .urlPathAllowed)

        let input = CopyObjectInput(
            bucket: destBucket,
            copySource: srcUrl,
            key: name
        )
        _ = try await client.copyObject(input: input)
    }
```

- Para obter detalhes da API, consulte CopyObjecta referência da API AWS SDK for Swift.

Crie um ponto de acesso multirregional Amazon S3 usando um SDK AWS

O exemplo de código a seguir mostra como criar um ponto de acesso multirregional Amazon S3.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure o cliente de controle S3 para enviar a solicitação para a região us-west-2.

```
        suspend fun createS3ControlClient(): S3ControlClient {
```

```
            // Configure your S3ControlClient to send requests to US West
(Oregon).
            val s3Control = S3ControlClient.fromEnvironment {
                region = "us-west-2"
            }
            return s3Control
        }
```

Crie o ponto de acesso multirregional.

```
    suspend fun createMrap(s3Control: S3ControlClient, accountIdParam: String,
bucketName1: String, bucketName2: String, mrapName: String): String {
        println("Creating MRAP ...")
        val createMrapResponse: CreateMultiRegionAccessPointResponse =
s3Control.createMultiRegionAccessPoint {
            accountId = accountIdParam
            clientToken = UUID.randomUUID().toString()
            details {
                name = mrapName

                regions = listOf(
                    Region {
                        bucket = bucketName1
                    },
                    Region {
                        bucket = bucketName2
                    }
                )
            }
        }
        val requestToken: String? = createMrapResponse.requestTokenArn

        // Use the request token to check for the status of the
CreateMultiRegionAccessPoint operation.
        if (requestToken != null) {
            waitForSucceededStatus(s3Control, requestToken, accountIdParam)
            println("MRAP created")
        }

        val getMrapResponse = s3Control.getMultiRegionAccessPoint(
            input = GetMultiRegionAccessPointRequest {
                accountId = accountIdParam
```

```
                name = mrapName
            }
        )
        val mrapAlias = getMrapResponse.accessPoint?.alias
        return "arn:aws:s3::$accountIdParam:accesspoint/$mrapAlias"
    }
```

Aguarde até que o ponto de acesso multirregional fique disponível.

```
        suspend fun waitForSucceededStatus(s3Control: S3ControlClient,
requestToken: String, accountIdParam: String, timeBetweenChecks: Duration =
1.minutes) {
            var describeResponse: DescribeMultiRegionAccessPointOperationResponse
            describeResponse = s3Control.describeMultiRegionAccessPointOperation(
                input = DescribeMultiRegionAccessPointOperationRequest {
                    accountId = accountIdParam
                    requestTokenArn = requestToken
                }
            )

            var status: String? = describeResponse.asyncOperation?.requestStatus
            while (status != "SUCCEEDED") {
                delay(timeBetweenChecks)
                describeResponse =
s3Control.describeMultiRegionAccessPointOperation(
                    input = DescribeMultiRegionAccessPointOperationRequest {
                        accountId = accountIdParam
                        requestTokenArn = requestToken
                    }
                )
                status = describeResponse.asyncOperation?.requestStatus
                println(status)
            }
        }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.
- Para obter detalhes da API, consulte a CreateMultiRegionAccessPointreferência da API AWSSDK for Kotlin.

Criar um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como criar um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Conceitos básicos de buckets e objetos
- Trabalhar com objetos versionados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to create a new Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket to create.</param>
        /// <returns>A boolean value representing the success or failure of
        /// the bucket creation process.</returns>
        public static async Task<bool> CreateBucketAsync(IAmazonS3 client, string
bucketName)
        {
            try
            {
                var request = new PutBucketRequest
                {
                    BucketName = bucketName,
                    UseClientRegion = true,
                };

                var response = await client.PutBucketAsync(request);
                return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
```

```
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error creating bucket: '{ex.Message}'");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}
```

```
##############################################################################
# function create-bucket
#
# This function creates the specified bucket in the specified AWS Region, unless
# it already exists.
#
# Parameters:
#       -b bucket_name  -- The name of the bucket to create.
#       -r region_code  -- The code for an AWS Region in which to
#                          create the bucket.
#
# Returns:
#       The URL of the bucket that was created.
#     And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function create_bucket() {
  local bucket_name region_code response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function create_bucket"
    echo "Creates an Amazon S3 bucket. You must supply a bucket name:"
    echo "  -b bucket_name    The name of the bucket. It must be globally
 unique."
    echo "  [-r region_code]    The code for an AWS Region in which the bucket is
 created."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "b:r:h" option; do
    case "${option}" in
      b) bucket_name="${OPTARG}" ;;
      r) region_code="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
```

```
        usage
        return 1
        ;;
    esac
  done

  if [[ -z "$bucket_name" ]]; then
    errecho "ERROR: You must provide a bucket name with the -b parameter."
    usage
    return 1
  fi

  local bucket_config_arg
  # A location constraint for "us-east-1" returns an error.
  if [[ -n "$region_code" ]] && [[ "$region_code" != "us-east-1" ]]; then
    bucket_config_arg="--create-bucket-configuration LocationConstraint=
$region_code"
  fi

  iecho "Parameters:\n"
  iecho "    Bucket name:   $bucket_name"
  iecho "    Region code:   $region_code"
  iecho ""

  # If the bucket already exists, we don't want to try to create it.
  if (bucket_exists "$bucket_name"); then
    errecho "ERROR: A bucket with that name already exists. Try again."
    return 1
  fi

  # shellcheck disable=SC2086
  response=$(aws s3api create-bucket \
    --bucket "$bucket_name" \
    $bucket_config_arg)

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports create-bucket operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte CreateBucketem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::CreateBucket(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CreateBucketRequest request;
    request.SetBucket(bucketName);

    //TODO(user): Change the bucket location constraint enum to your target
 Region.
    if (clientConfig.region != "us-east-1") {
        Aws::S3::Model::CreateBucketConfiguration createBucketConfig;
        createBucketConfig.SetLocationConstraint(

 Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                       clientConfig.region));
        request.SetCreateBucketConfiguration(createBucketConfig);
    }

    Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);
    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: CreateBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Created bucket " << bucketName <<
                  " in the specified AWS Region." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar um bucket

O seguinte exemplo de `create-bucket` cria um bucket chamado `my-bucket`:

```
aws s3api create-bucket \
    --bucket my-bucket \
    --region us-east-1
```

Saída:

```
{
    "Location": "/my-bucket"
}
```

Para obter mais informações, consulte Como criar um bucket no Guia do usuário do Amazon S3.

Exemplo 2: como criar um bucket com aplicação de políticas de proprietário

O exemplo de `create-bucket` a seguir cria um bucket chamado `my-bucket` que usa a configuração aplicada de proprietário de bucket para a propriedade de objetos do S3.

```
aws s3api create-bucket \
    --bucket my-bucket \
    --region us-east-1 \
    --object-ownership BucketOwnerEnforced
```

Saída:

```
{
    "Location": "/my-bucket"
}
```

Para obter mais informações, consulte Controlar a propriedade de objetos e desabilitar ACLs, no Guia do usuário do Amazon S3.

Exemplo 3: como criar um bucket fora da região ``us-east-1``

O exemplo de `create-bucket` a seguir cria um bucket chamado `my-bucket` na região `eu-west-1`. Regiões fora da `us-east-1` exigem que o `LocationConstraint` adequado seja especificado para poder criar o bucket na região desejada.

```
aws s3api create-bucket \
    --bucket my-bucket \
    --region eu-west-1 \
    --create-bucket-configuration LocationConstraint=eu-west-1
```

Saída:

```
{
    "Location": "http://my-bucket.s3.amazonaws.com/"
}
```

Para obter mais informações, consulte Como criar um bucket no Guia do usuário do Amazon S3.

- Para obter detalhes da API, consulte CreateBucketem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
```

```
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// CreateBucket creates a bucket with the specified name in the specified Region.
func (basics BucketBasics) CreateBucket(name string, region string) error {
 _, err := basics.S3Client.CreateBucket(context.TODO(), &s3.CreateBucketInput{
  Bucket: aws.String(name),
  CreateBucketConfiguration: &types.CreateBucketConfiguration{
   LocationConstraint: types.BucketLocationConstraint(region),
  },
 })
 if err != nil {
  log.Printf("Couldn't create bucket %v in Region %v. Here's why: %v\n",
   name, region, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CreateBucketRequest;
import software.amazon.awssdk.services.s3.model.HeadBucketRequest;
import software.amazon.awssdk.services.s3.model.HeadBucketResponse;
```

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class CreateBucket {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The name of the bucket to create. The bucket
 name must be unique, or an error occurs.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Creating a bucket named %s\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        createBucket(s3, bucketName);
        s3.close();
    }

    public static void createBucket(S3Client s3Client, String bucketName) {
        try {
```

```
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
 s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o bucket.

```
import { CreateBucketCommand, S3Client } from "@aws-sdk/client-s3";
```

```
const client = new S3Client({});

export const main = async () => {
  const command = new CreateBucketCommand({
    // The name of the bucket. Bucket names are unique and have several other
 constraints.
    // See https://docs.aws.amazon.com/AmazonS3/latest/userguide/
bucketnamingrules.html
    Bucket: "bucket-name",
  });

  try {
    const { Location } = await client.send(command);
    console.log(`Bucket created with location ${Location}`);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
```

```
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $this->s3client->createBucket([
                'Bucket' => $this->bucketName,
                'CreateBucketConfiguration' => ['LocationConstraint' => $region],
            ]);
            echo "Created bucket named: $this->bucketName \n";
        } catch (Exception $exception) {
            echo "Failed to create bucket $this->bucketName with error: " .
$exception->getMessage();
            exit("Please fix error with bucket creation before continuing.");
        }
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um bucket com as configurações padrão.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def create(self, region_override=None):
        """
        Create an Amazon S3 bucket in the default Region for the account or in
 the
        specified Region.

        :param region_override: The Region in which to create the bucket. If this
 is
                                not specified, the Region configured in your
 shared
                                credentials is used.
        """
        if region_override is not None:
            region = region_override
        else:
            region = self.bucket.meta.client.meta.region_name
        try:
```

```
            self.bucket.create(CreateBucketConfiguration={"LocationConstraint":
 region})

            self.bucket.wait_until_exists()
            logger.info("Created bucket '%s' in region=%s", self.bucket.name,
 region)
        except ClientError as error:
            logger.exception(
                "Couldn't create bucket named '%s' in region=%s.",
                self.bucket.name,
                region,
            )
            raise error
```

Crie um bucket versionado com uma configuração de ciclo de vida.

```
def create_versioned_bucket(bucket_name, prefix):
    """
    Creates an Amazon S3 bucket, enables it for versioning, and configures a
 lifecycle
    that expires noncurrent object versions after 7 days.

    Adding a lifecycle configuration to a versioned bucket is a best practice.
    It helps prevent objects in the bucket from accumulating a large number of
    noncurrent versions, which can slow down request performance.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket_name: The name of the bucket to create.
    :param prefix: Identifies which objects are automatically expired under the
                   configured lifecycle rules.
    :return: The newly created bucket.
    """
    try:
        bucket = s3.create_bucket(
            Bucket=bucket_name,
            CreateBucketConfiguration={
                "LocationConstraint": s3.meta.client.meta.region_name
            },
        )
```

```
        logger.info("Created bucket %s.", bucket.name)
    except ClientError as error:
        if error.response["Error"]["Code"] == "BucketAlreadyOwnedByYou":
            logger.warning("Bucket %s already exists! Using it.", bucket_name)
            bucket = s3.Bucket(bucket_name)
        else:
            logger.exception("Couldn't create bucket %s.", bucket_name)
            raise

    try:
        bucket.Versioning().enable()
        logger.info("Enabled versioning on bucket %s.", bucket.name)
    except ClientError:
        logger.exception("Couldn't enable versioning on bucket %s.", bucket.name)
        raise

    try:
        expiration = 7
        bucket.LifecycleConfiguration().put(
            LifecycleConfiguration={
                "Rules": [
                    {
                        "Status": "Enabled",
                        "Prefix": prefix,
                        "NoncurrentVersionExpiration": {"NoncurrentDays":
expiration},
                    }
                ]
            }
        )
        logger.info(
            "Configured lifecycle to expire noncurrent versions after %s days "
            "on bucket %s.",
            expiration,
            bucket.name,
        )
    except ClientError as error:
        logger.warning(
            "Couldn't configure lifecycle on bucket %s because %s. "
            "Continuing anyway.",
            bucket.name,
            error,
        )
```

```
    return bucket
```

- Para obter detalhes da API, consulte a CreateBucketReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket actions.
class BucketCreateWrapper
  attr_reader :bucket

  # @param bucket [Aws::S3::Bucket] An Amazon S3 bucket initialized with a name.
 This is a client-side object until
  #                                 create is called.
  def initialize(bucket)
    @bucket = bucket
  end

  # Creates an Amazon S3 bucket in the specified AWS Region.
  #
  # @param region [String] The Region where the bucket is created.
  # @return [Boolean] True when the bucket is created; otherwise, false.
  def create?(region)
    @bucket.create(create_bucket_configuration: { location_constraint: region })
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't create bucket. Here's why: #{e.message}"
    false
```

```
  end

  # Gets the Region where the bucket is located.
  #
  # @return [String] The location of the bucket.
  def location
    if @bucket.nil?
      "None. You must create a bucket before you can get its location!"
    else
      @bucket.client.get_bucket_location(bucket:
 @bucket.name).location_constraint
    end
  rescue Aws::Errors::ServiceError => e
    "Couldn't get the location of #{@bucket.name}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  region = "us-west-2"
  wrapper = BucketCreateWrapper.new(Aws::S3::Bucket.new("doc-example-bucket-
#{Random.uuid}"))
  return unless wrapper.create?(region)

  puts "Created bucket #{wrapper.bucket.name}."
  puts "Your bucket's region is: #{wrapper.location}"
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_bucket(
    client: &Client,
    bucket_name: &str,
    region: &str,
) -> Result<CreateBucketOutput, SdkError<CreateBucketError>> {
    let constraint = BucketLocationConstraint::from(region);
    let cfg = CreateBucketConfiguration::builder()
        .location_constraint(constraint)
        .build();
    client
        .create_bucket()
        .create_bucket_configuration(cfg)
        .bucket(bucket_name)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_s3->createbucket(
            iv_bucket = iv_bucket_name
        ).
        MESSAGE 'S3 bucket created.' TYPE 'I'.
      CATCH /aws1/cx_s3_bucketalrdyexists.
        MESSAGE 'Bucket name already exists.' TYPE 'E'.
      CATCH /aws1/cx_s3_bktalrdyownedbyyou.
        MESSAGE 'Bucket already exists and is owned by you.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func createBucket(name: String) async throws {
    let config = S3ClientTypes.CreateBucketConfiguration(
        locationConstraint: .usEast2
    )
    let input = CreateBucketInput(
        bucket: name,
        createBucketConfiguration: config
    )
    _ = try await client.createBucket(input: input)
}
```

- Para obter detalhes da API, consulte CreateBucketa referência da API AWS SDK for Swift.

Criar uma estrutura de carregamento fracionado usando um AWS SDK

Os exemplos de código a seguir mostram como criar a estrutura para construir uma ação de upload fracionado.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Executar uma cópia multipart
- Realizar um carregamento fracionado
- Usar somas de verificação

CLI

AWS CLI

O seguinte comando cria um upload fracionado no bucket `my-bucket` com a chave `multipart/01`:

```
aws s3api create-multipart-upload --bucket my-bucket --key 'multipart/01'
```

Saída:

```
{
    "Bucket": "my-bucket",
    "UploadId":
 "dfRtDYU0WWCCcH43C3WFbkRONycyCpTJJvxu2i5GYkZljF.Yxwh6XG7WfS2vC4to6HiV6Yjlx.cph0gtNBtJ8P3
    "Key": "multipart/01"
}
```

O arquivo concluído terá o nome `01` e estará em uma pasta chamada `multipart` no bucket `my-bucket`. Salve o ID de upload, a chave e o nome do bucket para usar com o comando `upload-part`.

- Para obter detalhes da API, consulte CreateMultipartUploadem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
let multipart_upload_res: CreateMultipartUploadOutput = client
    .create_multipart_upload()
    .bucket(&bucket_name)
    .key(&key)
    .send()
    .await
    .unwrap();
```

- Para obter detalhes da API, consulte a CreateMultipartUploadreferência da API AWS SDK for Rust.

Excluir regras de CORS de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir regras de CORS de um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Deletes a CORS configuration from an Amazon S3 bucket.
```

```
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to delete the CORS configuration from the bucket.</param>
        private static async Task DeleteCORSConfigurationAsync(AmazonS3Client
client)
        {
            DeleteCORSConfigurationRequest request = new
DeleteCORSConfigurationRequest()
            {
                BucketName = BucketName,
            };
            await client.DeleteCORSConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte DeleteBucketCorsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando exclui a configuração de compartilhamento de recursos de origem cruzada do bucket `my-bucket`:

```
aws s3api delete-bucket-cors --bucket my-bucket
```

- Para obter detalhes da API, consulte DeleteBucketCorsem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete_cors(self):
        """
        Delete the CORS rules from the bucket.

        :param bucket_name: The name of the bucket to update.
        """
        try:
            self.bucket.Cors().delete()
            logger.info("Deleted CORS from bucket '%s'.", self.bucket.name)
        except ClientError:
            logger.exception("Couldn't delete CORS from bucket '%s'.",
 self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketCorsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with
 an existing bucket.
  def initialize(bucket_cors)
    @bucket_cors = bucket_cors
  end

  # Deletes the CORS configuration of a bucket.
  #
  # @return [Boolean] True if the CORS rules were deleted; otherwise, false.
  def delete_cors
    @bucket_cors.delete
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't delete CORS rules for #{@bucket_cors.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte DeleteBucketCorsa Referência AWS SDK for Ruby da API.

Excluir uma política de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma política de um bucket do S3.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucketPolicy(const Aws::String &bucketName,
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketPolicyOutcome outcome =
 client.DeleteBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucketPolicy: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Policy was deleted from the bucket." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando exclui uma política de bucket do bucket `my-bucket`:

```
aws s3api delete-bucket-policy --bucket my-bucket
```

- Para obter detalhes da API, consulte DeleteBucketPolicyem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.DeleteBucketPolicyRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DeleteBucketPolicy {
    public static void main(String[] args) {

        final String usage = """
```

```
                Usage:
                    <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to delete the policy from
 (for example, bucket1).""";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Deleting policy from bucket: \"%s\"\n\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteS3BucketPolicy(s3, bucketName);
        s3.close();
    }

    // Delete the bucket policy.
    public static void deleteS3BucketPolicy(S3Client s3, String bucketName) {
        DeleteBucketPolicyRequest delReq = DeleteBucketPolicyRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            s3.deleteBucketPolicy(delReq);
            System.out.println("Done!");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a política de bucket.

```
import { DeleteBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// This will remove the policy from the bucket.
export const main = async () => {
  const command = new DeleteBucketPolicyCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteS3BucketPolicy(bucketName: String?) {
    val request = DeleteBucketPolicyRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucketPolicy(request)
        println("Done!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteBucketPolicyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
```

```
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                        that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete_policy(self):
        """
        Delete the security policy from the bucket.
        """
        try:
            self.bucket.Policy().delete()
            logger.info("Deleted policy for bucket '%s'.", self.bucket.name)
        except ClientError:
            logger.exception(
                "Couldn't delete policy for bucket '%s'.", self.bucket.name
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy
```

```
  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object
 configured with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  def delete_policy
    @bucket_policy.delete
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't delete the policy from #{@bucket_policy.bucket.name}. Here's
 why: #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for Ruby da API.

Excluir um bucket vazio do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um bucket vazio do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de buckets e objetos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to delete an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to
delete.</param>
        /// <returns>A boolean value that represents the success or failure of
        /// the delete operation.</returns>
        public static async Task<bool> DeleteBucketAsync(IAmazonS3 client, string
bucketName)
        {
            var request = new DeleteBucketRequest
            {
                BucketName = bucketName,
            };

            var response = await client.DeleteBucketAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
```

```
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function delete_bucket
#
# This function deletes the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api delete-bucket \
    --bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR: AWS reports s3api delete-bucket failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteBucketem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucket(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration
 &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "The bucket was deleted" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando exclui o bucket `my-bucket`:

```
aws s3api delete-bucket --bucket my-bucket --region us-east-1
```

- Para obter detalhes da API, consulte DeleteBucketem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DeleteBucket deletes a bucket. The bucket must be empty or an error is
 returned.
func (basics BucketBasics) DeleteBucket(bucketName string) error {
 _, err := basics.S3Client.DeleteBucket(context.TODO(), &s3.DeleteBucketInput{
  Bucket: aws.String(bucketName)})
 if err != nil {
  log.Printf("Couldn't delete bucket %v. Here's why: %v\n", bucketName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucket)
                .build();

        s3.deleteBucket(deleteBucketRequest);
        s3.close();
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o bucket.

```
import { DeleteBucketCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Delete a bucket.
export const main = async () => {
```

```
  const command = new DeleteBucketCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um bucket vazio.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $this->s3client->deleteBucket([
                'Bucket' => $this->bucketName,
            ]);
            echo "Deleted bucket $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $this->bucketName with error: " . $exception-
>getMessage();
            exit("Please fix error with bucket deletion before continuing.");
```

```
        }
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete(self):
        """
        Delete the bucket. The bucket must be empty or an error is raised.
        """
        try:
            self.bucket.delete()
            self.bucket.wait_until_not_exists()
            logger.info("Bucket %s successfully deleted.", self.bucket.name)
        except ClientError:
            logger.exception("Couldn't delete bucket %s.", self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes the objects in an Amazon S3 bucket and deletes the bucket.
#
# @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
def delete_bucket(bucket)
  puts("\nDo you want to delete all of the objects as well as the bucket (y/n)?
")
  answer = gets.chomp.downcase
  if answer == "y"
    bucket.objects.batch_delete!
    bucket.delete
    puts("Emptied and deleted bucket #{bucket.name}.\n")
  end
rescue Aws::Errors::ServiceError => e
  puts("Couldn't empty and delete bucket #{bucket.name}.")
  puts("\t#{e.code}: #{e.message}")
  raise
end
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_bucket(client: &Client, bucket_name: &str) -> Result<(),
 Error> {
    client.delete_bucket().bucket(bucket_name).send().await?;
    println!("Bucket deleted");
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteBucketreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.

        lo_s3->deletebucket(
            iv_bucket = iv_bucket_name
        ).
        MESSAGE 'Deleted S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteBucketreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteBucket(name: String) async throws {
    let input = DeleteBucketInput(
        bucket: name
    )
    _ = try await client.deleteBucket(input: input)
}
```

- Para obter detalhes da API, consulte DeleteBucketa referência da API AWS SDK for Swift.

Excluir um objeto do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um objeto do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Trabalhar com objetos versionados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto de um bucket do S3 sem versionamento.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to delete an object from a non-versioned Amazon
    /// Simple Storage Service (Amazon S3) bucket.
    /// </summary>
    public class DeleteObject
    {
        /// <summary>
        /// The Main method initializes the necessary variables and then calls
        /// the DeleteObjectNonVersionedBucketAsync method to delete the object
        /// named by the keyName parameter.
        /// </summary>
        public static async Task Main()
        {
            const string bucketName = "doc-example-bucket";
            const string keyName = "testfile.txt";

            // If the Amazon S3 bucket is located in an AWS Region other than the
            // Region of the default account, define the AWS Region for the
            // Amazon S3 bucket in your call to the AmazonS3Client constructor.
            // For example RegionEndpoint.USWest2.
            IAmazonS3 client = new AmazonS3Client();
            await DeleteObjectNonVersionedBucketAsync(client, bucketName,
keyName);
        }

        /// <summary>
```

```
        /// The DeleteObjectNonVersionedBucketAsync takes care of deleting the
        /// desired object from the named bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client used to delete
        /// an object from an Amazon S3 bucket.</param>
        /// <param name="bucketName">The name of the bucket from which the
        /// object will be deleted.</param>
        /// <param name="keyName">The name of the object to delete.</param>
        public static async Task DeleteObjectNonVersionedBucketAsync(IAmazonS3
 client, string bucketName, string keyName)
        {
            try
            {
                var deleteObjectRequest = new DeleteObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                };

                Console.WriteLine($"Deleting object: {keyName}");
                await client.DeleteObjectAsync(deleteObjectRequest);
                Console.WriteLine($"Object: {keyName} deleted from
 {bucketName}.");
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error encountered on server.
 Message:'{ex.Message}' when deleting an object.");
            }
        }
    }
```

Exclua um objeto de um bucket do S3 com versionamento.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example creates an object in an Amazon Simple Storage Service
```

```
    /// (Amazon S3) bucket and then deletes the object version that was
    /// created.
    /// </summary>
    public class DeleteObjectVersion
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "verstioned-object.txt";

            // If the AWS Region of the default user is different from the AWS
            // Region of the Amazon S3 bucket, pass the AWS Region of the
            // bucket region to the Amazon S3 client object's constructor.
            // Define it like this:
            //      RegionEndpoint bucketRegion = RegionEndpoint.USWest2;
            IAmazonS3 client = new AmazonS3Client();

            await CreateAndDeleteObjectVersionAsync(client, bucketName, keyName);
        }

        /// <summary>
        /// This method creates and then deletes a versioned object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
        /// create and delete the object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
        /// object will be created and deleted.</param>
        /// <param name="keyName">The key name of the object to create.</param>
        public static async Task CreateAndDeleteObjectVersionAsync(IAmazonS3
client, string bucketName, string keyName)
        {
            try
            {
                // Add a sample object.
                string versionID = await PutAnObject(client, bucketName,
keyName);

                // Delete the object by specifying an object key and a version
ID.
                DeleteObjectRequest request = new DeleteObjectRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                    VersionId = versionID,
```

```
                };

                Console.WriteLine("Deleting an object");
                await client.DeleteObjectAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }

        /// <summary>
        /// This method is used to create the temporary Amazon S3 object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 object which will be
 used
        /// to create the temporary Amazon S3 object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
 object
        /// will be created.</param>
        /// <param name="objectKey">The name of the Amazon S3 object co create.</
param>
        /// <returns>The Version ID of the created object.</returns>
        public static async Task<string> PutAnObject(IAmazonS3 client, string
 bucketName, string objectKey)
        {
            PutObjectRequest request = new PutObjectRequest()
            {
                BucketName = bucketName,
                Key = objectKey,
                ContentBody = "This is the content body!",
            };

            PutObjectResponse response = await client.PutObjectAsync(request);
            return response.VersionId;
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function delete_item_in_bucket
#
# This function deletes the specified file from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - The key (file name) in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function delete_item_in_bucket() {
  local bucket_name=$1
  local key=$2
  local response

  response=$(aws s3api delete-object \
    --bucket "$bucket_name" \
    --key "$key")

  # shellcheck disable=SC2181
```

```
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n
$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteObjectem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteObject(const Aws::String &objectKey,
                              const Aws::String &fromBucket,
                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectRequest request;

    request.WithKey(objectKey)
            .WithBucket(fromBucket);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: DeleteObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Successfully deleted the object." << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando exclui um objeto `test.txt` do bucket `my-bucket`:

```
aws s3api delete-object --bucket my-bucket --key test.txt
```

Se o versionamento de bucket estiver habilitado, a saída conterá o ID de versão do marcador excluído:

```
{
  "VersionId": "9_gKg5vG56F.TTEUdwkxGpJ3tNDlWlGq",
  "DeleteMarker": true
}
```

Para obter mais informações sobre como excluir objetos, consulte Excluir objetos no Guia do desenvolvedor do Amazon S3.

- Para obter detalhes da API, consulte DeleteObjectem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto.

```
import { DeleteObjectCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new DeleteObjectCommand({
    Bucket: "test-bucket",
    Key: "test-key.txt",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
```

```
                            that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def delete(self):
        """
        Deletes the object.
        """
        try:
            self.object.delete()
            self.object.wait_until_not_exists()
            logger.info(
                "Deleted object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't delete object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
```

Reverta um objeto para uma versão anterior excluindo versões posteriores do objeto.

```
def rollback_object(bucket, object_key, version_id):
    """
    Rolls back an object to an earlier version by deleting all versions that
    occurred after the specified rollback version.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that holds the object to roll back.
    :param object_key: The object to roll back.
    :param version_id: The version ID to roll back to.
    """
    # Versions must be sorted by last_modified date because delete markers are
```

```
    # at the end of the list even when they are interspersed in time.
    versions = sorted(
        bucket.object_versions.filter(Prefix=object_key),
        key=attrgetter("last_modified"),
        reverse=True,
    )

    logger.debug(
        "Got versions:\n%s",
        "\n".join(
            [
                f"\t{version.version_id}, last modified {version.last_modified}"
                for version in versions
            ]
        ),
    )

    if version_id in [ver.version_id for ver in versions]:
        print(f"Rolling back to version {version_id}")
        for version in versions:
            if version.version_id != version_id:
                version.delete()
                print(f"Deleted version {version.version_id}")
            else:
                break

        print(f"Active version is now {bucket.Object(object_key).version_id}")
    else:
        raise KeyError(
            f"{version_id} was not found in the list of versions for "
 f"{object_key}."
        )
```

Restaure um objeto excluído removendo o marcador de exclusão ativo do objeto.

```
def revive_object(bucket, object_key):
    """
    Revives a versioned object that was deleted by removing the object's active
    delete marker.
```

```
    A versioned object presents as deleted when its latest version is a delete
marker.
    By removing the delete marker, we make the previous version the latest
version
    and the object then presents as *not* deleted.

    Usage is shown in the usage_demo_single_object function at the end of this
module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to revive.
    """
    # Get the latest version for the object.
    response = s3.meta.client.list_object_versions(
        Bucket=bucket.name, Prefix=object_key, MaxKeys=1
    )

    if "DeleteMarkers" in response:
        latest_version = response["DeleteMarkers"][0]
        if latest_version["IsLatest"]:
            logger.info(
                "Object %s was indeed deleted on %s. Let's revive it.",
                object_key,
                latest_version["LastModified"],
            )
            obj = bucket.Object(object_key)
            obj.Version(latest_version["VersionId"]).delete()
            logger.info(
                "Revived %s, active version is now %s  with body '%s'",
                object_key,
                obj.version_id,
                obj.get()["Body"].read(),
            )
        else:
            logger.warning(
                "Delete marker is not the latest version for %s!", object_key
            )
    elif "Versions" in response:
        logger.warning("Got an active version for %s, nothing to do.",
object_key)
    else:
        logger.error("Couldn't get any version info for %s.", object_key)
```

Crie um manipulador do Lambda que remova um marcador de exclusão de um objeto do S3. Esse manipulador pode ser usado para limpar com eficiência marcadores de exclusão estranhos em um bucket versionado.

```
import logging
from urllib import parse
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
logger.setLevel("INFO")

s3 = boto3.client("s3")


def lambda_handler(event, context):
    """
    Removes a delete marker from the specified versioned object.

    :param event: The S3 batch event that contains the ID of the delete marker
                  to remove.
    :param context: Context about the event.
    :return: A result structure that Amazon S3 uses to interpret the result of
 the
             operation. When the result code is TemporaryFailure, S3 retries the
             operation.
    """
    # Parse job parameters from Amazon S3 batch operations
    invocation_id = event["invocationId"]
    invocation_schema_version = event["invocationSchemaVersion"]

    results = []
    result_code = None
    result_string = None

    task = event["tasks"][0]
    task_id = task["taskId"]

    try:
        obj_key = parse.unquote(task["s3Key"], encoding="utf-8")
        obj_version_id = task["s3VersionId"]
```

```
        bucket_name = task["s3BucketArn"].split(":")[-1]

        logger.info(
            "Got task: remove delete marker %s from object %s.", obj_version_id,
 obj_key
        )

        try:
            # If this call does not raise an error, the object version is not a
 delete
            # marker and should not be deleted.
            response = s3.head_object(
                Bucket=bucket_name, Key=obj_key, VersionId=obj_version_id
            )
            result_code = "PermanentFailure"
            result_string = (
                f"Object {obj_key}, ID {obj_version_id} is not " f"a delete
 marker."
            )

            logger.debug(response)
            logger.warning(result_string)
        except ClientError as error:
            delete_marker = error.response["ResponseMetadata"]
["HTTPHeaders"].get(
                "x-amz-delete-marker", "false"
            )
            if delete_marker == "true":
                logger.info(
                    "Object %s, version %s is a delete marker.", obj_key,
 obj_version_id
                )
                try:
                    s3.delete_object(
                        Bucket=bucket_name, Key=obj_key, VersionId=obj_version_id
                    )
                    result_code = "Succeeded"
                    result_string = (
                        f"Successfully removed delete marker "
                        f"{obj_version_id} from object {obj_key}."
                    )
                    logger.info(result_string)
                except ClientError as error:
```

```
                    # Mark request timeout as a temporary failure so it will be
retried.
                    if error.response["Error"]["Code"] == "RequestTimeout":
                        result_code = "TemporaryFailure"
                        result_string = (
                            f"Attempt to remove delete marker from  "
                            f"object {obj_key} timed out."
                        )
                        logger.info(result_string)
                    else:
                        raise
            else:
                raise ValueError(
                    f"The x-amz-delete-marker header is either not "
                    f"present or is not 'true'."
                )
    except Exception as error:
        # Mark all other exceptions as permanent failures.
        result_code = "PermanentFailure"
        result_string = str(error)
        logger.exception(error)
    finally:
        results.append(
            {
                "taskId": task_id,
                "resultCode": result_code,
                "resultString": result_string,
            }
        )
    return {
        "invocationSchemaVersion": invocation_schema_version,
        "treatMissingKeysAs": "PermanentFailure",
        "invocationId": invocation_id,
        "results": results,
    }
```

- Para obter detalhes da API, consulte a DeleteObjectReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_object(client: &Client, bucket: &str, key: &str) -> Result<(),
 Error> {
    client
        .delete_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await?;

    println!("Object deleted.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteObjectreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_s3->deleteobject(
            iv_bucket = iv_bucket_name
```

```
            iv_key = iv_object_key
        ).
        MESSAGE 'Object deleted from S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteObjectreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func deleteFile(bucket: String, key: String) async throws {
        let input = DeleteObjectInput(
            bucket: bucket,
            key: key
        )

        do {
            _ = try await client.deleteObject(input: input)
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjecta referência da API AWS SDK for Swift.

Excluir vários objetos de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir vários objetos de um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de buckets e objetos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua todos os objetos de um bucket do S3.

```
        /// <summary>
        /// Delete all of the objects stored in an existing Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket from which the
        /// contents will be deleted.</param>
        /// <returns>A boolean value that represents the success or failure of
        /// deleting all of the objects in the bucket.</returns>
        public static async Task<bool> DeleteBucketContentsAsync(IAmazonS3
client, string bucketName)
        {
            // Iterate over the contents of the bucket and delete all objects.
            var request = new ListObjectsV2Request
            {
                BucketName = bucketName,
            };
```

```
            try
            {
                ListObjectsV2Response response;

                do
                {
                    response = await client.ListObjectsV2Async(request);
                    response.S3Objects
                        .ForEach(async obj => await
client.DeleteObjectAsync(bucketName, obj.Key));

                    // If the response is truncated, set the request
ContinuationToken
                    // from the NextContinuationToken property of the response.
                    request.ContinuationToken = response.NextContinuationToken;
                }
                while (response.IsTruncated);

                return true;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error deleting objects: {ex.Message}");
                return false;
            }
        }
```

Exclua vários objetos de um bucket do S3 sem versionamento.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to delete multiple objects from an Amazon Simple
    /// Storage Service (Amazon S3) bucket.
    /// </summary>
    public class DeleteMultipleObjects
    {
```

```
        /// <summary>
        /// The Main method initializes the Amazon S3 client and the name of
        /// the bucket and then passes those values to MultiObjectDeleteAsync.
        /// </summary>
        public static async Task Main()
        {
            const string bucketName = "doc-example-bucket";

            // If the Amazon S3 bucket from which you wish to delete objects is
not
            // located in the same AWS Region as the default user, define the
            // AWS Region for the Amazon S3 bucket as a parameter to the client
            // constructor.
            IAmazonS3 s3Client = new AmazonS3Client();

            await MultiObjectDeleteAsync(s3Client, bucketName);
        }

        /// <summary>
        /// This method uses the passed Amazon S3 client to first create and then
        /// delete three files from the named bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// Amazon S3 methods.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where
objects
        /// will be created and then deleted.</param>
        public static async Task MultiObjectDeleteAsync(IAmazonS3 client, string
bucketName)
        {
            // Create three sample objects which we will then delete.
            var keysAndVersions = await PutObjectsAsync(client, 3, bucketName);

            // Now perform the multi-object delete, passing the key names and
            // version IDs. Since we are working with a non-versioned bucket,
            // the object keys collection includes null version IDs.
            DeleteObjectsRequest multiObjectDeleteRequest = new
DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keysAndVersions,
            };
```

```
            // You can add a specific object key to the delete request using the
            // AddKey method of the multiObjectDeleteRequest.
            try
            {
                DeleteObjectsResponse response = await
client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine("Successfully deleted all the {0} items",
response.DeletedObjects.Count);
            }
            catch (DeleteObjectsException e)
            {
                PrintDeletionErrorStatus(e);
            }
        }

        /// <summary>
        /// Prints the list of errors raised by the call to DeleteObjectsAsync.
        /// </summary>
        /// <param name="ex">A collection of exceptions returned by the call to
        /// DeleteObjectsAsync.</param>
        public static void PrintDeletionErrorStatus(DeleteObjectsException ex)
        {
            DeleteObjectsResponse errorResponse = ex.Response;
            Console.WriteLine("x {0}", errorResponse.DeletedObjects.Count);

            Console.WriteLine($"Successfully deleted
{errorResponse.DeletedObjects.Count}.");
            Console.WriteLine($"No. of objects failed to delete =
{errorResponse.DeleteErrors.Count}");

            Console.WriteLine("Printing error data...");
            foreach (DeleteError deleteError in errorResponse.DeleteErrors)
            {
                Console.WriteLine($"Object Key:
{deleteError.Key}\t{deleteError.Code}\t{deleteError.Message}");
            }
        }

        /// <summary>
        /// This method creates simple text file objects that can be used in
        /// the delete method.
        /// </summary>
        /// <param name="client">The Amazon S3 client used to call
PutObjectAsync.</param>
```

```
        /// <param name="number">The number of objects to create.</param>
        /// <param name="bucketName">The name of the bucket where the objects
        /// will be created.</param>
        /// <returns>A list of keys (object keys) and versions that the calling
        /// method will use to delete the newly created files.</returns>
        public static async Task<List<KeyVersion>> PutObjectsAsync(IAmazonS3
client, int number, string bucketName)
        {
            List<KeyVersion> keys = new List<KeyVersion>();
            for (int i = 0; i < number; i++)
            {
                string key = "ExampleObject-" + new System.Random().Next();
                PutObjectRequest request = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = key,
                    ContentBody = "This is the content body!",
                };

                PutObjectResponse response = await
client.PutObjectAsync(request);

                // For non-versioned bucket operations, we only need the
                // object key.
                KeyVersion keyVersion = new KeyVersion
                {
                    Key = key,
                };
                keys.Add(keyVersion);
            }

            return keys;
        }
    }
```

Exclua vários objetos de um bucket do S3 com versionamento.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
```

```
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to delete objects in a version-enabled Amazon
    /// Simple StorageService (Amazon S3) bucket.
    /// </summary>
    public class DeleteMultipleObjects
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";

            // If the AWS Region for your Amazon S3 bucket is different from
            // the AWS Region of the default user, define the AWS Region for
            // the Amazon S3 bucket and pass it to the client constructor
            // like this:
            // RegionEndpoint bucketRegion = RegionEndpoint.USWest2;
            IAmazonS3 s3Client;

            s3Client = new AmazonS3Client();
            await DeleteMultipleObjectsFromVersionedBucketAsync(s3Client,
bucketName);
        }

        /// <summary>
        /// This method removes multiple versions and objects from a
        /// version-enabled Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        public static async Task
DeleteMultipleObjectsFromVersionedBucketAsync(IAmazonS3 client, string
bucketName)
        {
            // Delete objects (specifying object version in the request).
            await DeleteObjectVersionsAsync(client, bucketName);

            // Delete objects (without specifying object version in the request).
            var deletedObjects = await DeleteObjectsAsync(client, bucketName);
```

```
            // Additional exercise - remove the delete markers Amazon S3 returned
from
            // the preceding response. This results in the objects reappearing
            // in the bucket (you can verify the appearance/disappearance of
            // objects in the console).
            await RemoveDeleteMarkersAsync(client, bucketName, deletedObjects);
        }

        /// <summary>
        /// Creates and then deletes non-versioned Amazon S3 objects and then
deletes
        /// them again. The method returns a list of the Amazon S3 objects
deleted.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// PubObjectsAsync and NonVersionedDeleteAsync.</param>
        /// <param name="bucketName">The name of the bucket where the objects
        /// will be created and then deleted.</param>
        /// <returns>A list of DeletedObjects.</returns>
        public static async Task<List<DeletedObject>>
DeleteObjectsAsync(IAmazonS3 client, string bucketName)
        {
            // Upload the sample objects.
            var keysAndVersions2 = await PutObjectsAsync(client, bucketName, 3);

            // Delete objects using only keys. Amazon S3 creates a delete marker
and
            // returns its version ID in the response.
            List<DeletedObject> deletedObjects = await
NonVersionedDeleteAsync(client, bucketName, keysAndVersions2);
            return deletedObjects;
        }

        /// <summary>
        /// This method creates several temporary objects and then deletes them.
        /// </summary>
        /// <param name="client">The S3 client.</param>
        /// <param name="bucketName">Name of the bucket.</param>
        /// <returns>Async task.</returns>
        public static async Task DeleteObjectVersionsAsync(IAmazonS3 client,
string bucketName)
        {
            // Upload the sample objects.
```

```
            var keysAndVersions1 = await PutObjectsAsync(client, bucketName, 3);

            // Delete the specific object versions.
            await VersionedDeleteAsync(client, bucketName, keysAndVersions1);
        }

        /// <summary>
        /// Displays the list of information about deleted files to the console.
        /// </summary>
        /// <param name="e">Error information from the delete process.</param>
        private static void DisplayDeletionErrors(DeleteObjectsException e)
        {
            var errorResponse = e.Response;
            Console.WriteLine($"No. of objects successfully deleted =
 {errorResponse.DeletedObjects.Count}");
            Console.WriteLine($"No. of objects failed to delete =
 {errorResponse.DeleteErrors.Count}");
            Console.WriteLine("Printing error data...");
            foreach (var deleteError in errorResponse.DeleteErrors)
            {
                Console.WriteLine($"Object Key:
 {deleteError.Key}\t{deleteError.Code}\t{deleteError.Message}");
            }
        }

        /// <summary>
        /// Delete multiple objects from a version-enabled bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="keys">A list of key names for the objects to delete.</
param>
        private static async Task VersionedDeleteAsync(IAmazonS3 client, string
 bucketName, List<KeyVersion> keys)
        {
            var multiObjectDeleteRequest = new DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keys, // This includes the object keys and specific
 version IDs.
```

```
            };

            try
            {
                Console.WriteLine("Executing VersionedDelete...");
                DeleteObjectsResponse response = await
 client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine($"Successfully deleted all the
 {response.DeletedObjects.Count} items");
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
            }
        }

        /// <summary>
        /// Deletes multiple objects from a non-versioned Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="keys">A list of key names for the objects to delete.</
param>
        /// <returns>A list of the deleted objects.</returns>
        private static async Task<List<DeletedObject>>
 NonVersionedDeleteAsync(IAmazonS3 client, string bucketName, List<KeyVersion>
 keys)
        {
            // Create a request that includes only the object key names.
            DeleteObjectsRequest multiObjectDeleteRequest = new
 DeleteObjectsRequest();
            multiObjectDeleteRequest.BucketName = bucketName;

            foreach (var key in keys)
            {
                multiObjectDeleteRequest.AddKey(key.Key);
            }

            // Execute DeleteObjectsAsync.
            // The DeleteObjectsAsync method adds a delete marker for each
```

```
            // object deleted. You can verify that the objects were removed
            // using the Amazon S3 console.
            DeleteObjectsResponse response;
            try
            {
                Console.WriteLine("Executing NonVersionedDelete...");
                response = await
client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine("Successfully deleted all the {0} items",
response.DeletedObjects.Count);
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
                throw; // Some deletions failed. Investigate before continuing.
            }

            // This response contains the DeletedObjects list which we use to
delete the delete markers.
            return response.DeletedObjects;
        }

        /// <summary>
        /// Deletes the markers left after deleting the temporary objects.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="deletedObjects">A list of the objects that were
deleted.</param>
        private static async Task RemoveDeleteMarkersAsync(IAmazonS3 client,
string bucketName, List<DeletedObject> deletedObjects)
        {
            var keyVersionList = new List<KeyVersion>();

            foreach (var deletedObject in deletedObjects)
            {
                KeyVersion keyVersion = new KeyVersion
                {
                    Key = deletedObject.Key,
                    VersionId = deletedObject.DeleteMarkerVersionId,
```

```
                };
                keyVersionList.Add(keyVersion);
            }

            // Create another request to delete the delete markers.
            var multiObjectDeleteRequest = new DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keyVersionList,
            };

            // Now, delete the delete marker to bring your objects back to the
 bucket.
            try
            {
                Console.WriteLine("Removing the delete markers .....");
                var deleteObjectResponse = await
 client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine($"Successfully deleted the
 {deleteObjectResponse.DeletedObjects.Count} delete markers");
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
            }
        }

        /// <summary>
        /// Create temporary Amazon S3 objects to show how object deletion wors
 in an
        /// Amazon S3 bucket with versioning enabled.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// PutObjectAsync to create temporary objects for the example.</param>
        /// <param name="bucketName">A string representing the name of the S3
        /// bucket where we will create the temporary objects.</param>
        /// <param name="number">The number of temporary objects to create.</
param>
        /// <returns>A list of the KeyVersion objects.</returns>
        private static async Task<List<KeyVersion>> PutObjectsAsync(IAmazonS3
 client, string bucketName, int number)
        {
            var keys = new List<KeyVersion>();
```

```
            for (var i = 0; i < number; i++)
            {
                string key = "ObjectToDelete-" + new System.Random().Next();
                PutObjectRequest request = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = key,
                    ContentBody = "This is the content body!",
                };

                var response = await client.PutObjectAsync(request);
                KeyVersion keyVersion = new KeyVersion
                {
                    Key = key,
                    VersionId = response.VersionId,
                };

                keys.Add(keyVersion);
            }

            return keys;
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
```

```
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function delete_items_in_bucket
#
# This function deletes the specified list of keys from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - A list of keys in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_items_in_bucket() {
  local bucket_name=$1
  local keys=$2
  local response

  # Create the JSON for the items to delete.
  local delete_items
  delete_items="{\"Objects\":["
  for key in $keys; do
    delete_items="$delete_items{\"Key\": \"$key\"},"
  done
  delete_items=${delete_items%?} # Remove the final comma.
  delete_items="$delete_items]}"

  response=$(aws s3api delete-objects \
    --bucket "$bucket_name" \
    --delete "$delete_items")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n
$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteObjectsem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteObjects(const std::vector<Aws::String> &objectKeys,
                               const Aws::String &fromBucket,
                               const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectsRequest request;

    Aws::S3::Model::Delete deleteObject;
    for (const Aws::String& objectKey : objectKeys)
    {

 deleteObject.AddObjects(Aws::S3::Model::ObjectIdentifier().WithKey(objectKey));
    }

    request.SetDelete(deleteObject);
    request.SetBucket(fromBucket);

    Aws::S3::Model::DeleteObjectsOutcome outcome =
            client.DeleteObjects(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error deleting objects. " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Successfully deleted the objects.";
```

```
        for (size_t i = 0; i < objectKeys.size(); ++i)
        {
            std::cout << objectKeys[i];
            if (i < objectKeys.size() - 1)
            {
                std::cout << ", ";
            }
        }

        std::cout << " from bucket " << fromBucket << "." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando exclui um objeto do bucket `my-bucket`:

```
aws s3api delete-objects --bucket my-bucket --delete file://delete.json
```

`delete.json` é um documento JSON no diretório atual que especifica o objeto a ser excluído:

```
{
  "Objects": [
    {
      "Key": "test1.txt"
    }
  ],
  "Quiet": false
}
```

Saída:

```
{
    "Deleted": [
```

```
        {
            "DeleteMarkerVersionId": "mYAT5Mc6F7aeUL8SS7FAAqUPO1koHwzU",
            "Key": "test1.txt",
            "DeleteMarker": true
        }
    ]
}
```

- Para obter detalhes da API, consulte DeleteObjectsem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DeleteObjects deletes a list of objects from a bucket.
func (basics BucketBasics) DeleteObjects(bucketName string, objectKeys []string)
 error {
 var objectIds []types.ObjectIdentifier
 for _, key := range objectKeys {
  objectIds = append(objectIds, types.ObjectIdentifier{Key: aws.String(key)})
 }
 output, err := basics.S3Client.DeleteObjects(context.TODO(),
 &s3.DeleteObjectsInput{
```

```
  Bucket: aws.String(bucketName),
  Delete: &types.Delete{Objects: objectIds},
 })
 if err != nil {
  log.Printf("Couldn't delete objects from bucket %v. Here's why: %v\n",
 bucketName, err)
 } else {
  log.Printf("Deleted %v objects.\n", len(output.Deleted))
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.services.s3.model.Delete;
import software.amazon.awssdk.services.s3.model.DeleteObjectsRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DeleteMultiObjects {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucketName>

                Where:
                   bucketName - the Amazon S3 bucket name.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void deleteBucketObjects(S3Client s3, String bucketName) {
        // Upload three sample objects to the specfied Amazon S3 bucket.
        ArrayList<ObjectIdentifier> keys = new ArrayList<>();
        PutObjectRequest putOb;
        ObjectIdentifier objectId;

        for (int i = 0; i < 3; i++) {
            String keyName = "delete object example " + i;
            objectId = ObjectIdentifier.builder()
                    .key(keyName)
                    .build();

            putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
```

```
                    .build();

            s3.putObject(putOb, RequestBody.fromString(keyName));
            keys.add(objectId);
        }

        System.out.println(keys.size() + " objects successfully created.");

        // Delete multiple objects in one request.
        Delete del = Delete.builder()
                .objects(keys)
                .build();

        try {
            DeleteObjectsRequest multiObjectDeleteRequest =
 DeleteObjectsRequest.builder()
                    .bucket(bucketName)
                    .delete(del)
                    .build();

            s3.deleteObjects(multiObjectDeleteRequest);
            System.out.println("Multiple objects are deleted!");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua vários objetos.

```
import { DeleteObjectsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new DeleteObjectsCommand({
    Bucket: "test-bucket",
    Delete: {
      Objects: [{ Key: "object1.txt" }, { Key: "object2.txt" }],
    },
  });

  try {
    const { Deleted } = await client.send(command);
    console.log(
      `Successfully deleted ${Deleted.length} objects from S3 bucket. Deleted
 objects:`,
    );
    console.log(Deleted.map((d) => ` • ${d.Key}`).join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteBucketObjects(bucketName: String, objectName: String) {
    val objectId = ObjectIdentifier {
        key = objectName
    }

    val delOb = Delete {
        objects = listOf(objectId)
    }

    val request = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteObjects(request)
        println("$objectName was deleted from $bucketName")
    }
}
```

- Para obter detalhes da API, consulte a DeleteObjectsreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um conjunto de objetos de uma lista de chaves.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $objects = [];
            foreach ($contents['Contents'] as $content) {
                $objects[] = [
                    'Key' => $content['Key'],
                ];
            }
            $this->s3client->deleteObjects([
                'Bucket' => $this->bucketName,
                'Delete' => [
                    'Objects' => $objects,
                ],
            ]);
            $check = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            if (count($check) <= 0) {
                throw new Exception("Bucket wasn't empty.");
            }
            echo "Deleted all objects and folders from $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $fileName from $this->bucketName with error:
" . $exception->getMessage();
            exit("Please fix error with object deletion before continuing.");
        }
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um conjunto de objetos de uma lista de chaves.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def delete_objects(bucket, object_keys):
        """
        Removes a list of objects from a bucket.
        This operation is done as a batch in a single request.

        :param bucket: The bucket that contains the objects. This is a Boto3
 Bucket
                       resource.
        :param object_keys: The list of keys that identify the objects to remove.
        :return: The response that contains data about which objects were deleted
                 and any that could not be deleted.
        """
        try:
            response = bucket.delete_objects(
                Delete={"Objects": [{"Key": key} for key in object_keys]}
            )
            if "Deleted" in response:
```

```
                logger.info(
                    "Deleted objects '%s' from bucket '%s'.",
                    [del_obj["Key"] for del_obj in response["Deleted"]],
                    bucket.name,
                )
            if "Errors" in response:
                logger.warning(
                    "Could not delete objects '%s' from bucket '%s'.",
                    [
                        f"{del_obj['Key']}: {del_obj['Code']}"
                        for del_obj in response["Errors"]
                    ],
                    bucket.name,
                )
        except ClientError:
            logger.exception("Couldn't delete any objects from bucket %s.",
 bucket.name)
            raise
        else:
            return response
```

Exclua todos os objetos em um bucket.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def empty_bucket(bucket):
        """
        Remove all objects from a bucket.
```

```
        :param bucket: The bucket to empty. This is a Boto3 Bucket resource.
        """
        try:
            bucket.objects.delete()
            logger.info("Emptied bucket '%s'.", bucket.name)
        except ClientError:
            logger.exception("Couldn't empty bucket '%s'.", bucket.name)
            raise
```

Exclua permanentemente um objeto versionado excluindo todas as suas versões.

```
def permanently_delete_object(bucket, object_key):
    """
    Permanently deletes a versioned object by deleting all of its versions.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to delete.
    """
    try:
        bucket.object_versions.filter(Prefix=object_key).delete()
        logger.info("Permanently deleted all versions of object %s.", object_key)
    except ClientError:
        logger.exception("Couldn't delete all versions of %s.", object_key)
        raise
```

- Para obter detalhes da API, consulte a DeleteObjectsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes the objects in an Amazon S3 bucket and deletes the bucket.
#
# @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
def delete_bucket(bucket)
  puts("\nDo you want to delete all of the objects as well as the bucket (y/n)?
")
  answer = gets.chomp.downcase
  if answer == "y"
    bucket.objects.batch_delete!
    bucket.delete
    puts("Emptied and deleted bucket #{bucket.name}.\n")
  end
rescue Aws::Errors::ServiceError => e
  puts("Couldn't empty and delete bucket #{bucket.name}.")
  puts("\t#{e.code}: #{e.message}")
  raise
end
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_objects(client: &Client, bucket_name: &str) ->
 Result<Vec<String>, Error> {
    let objects = client.list_objects_v2().bucket(bucket_name).send().await?;

    let mut delete_objects: Vec<ObjectIdentifier> = vec![];
    for obj in objects.contents() {
        let obj_id = ObjectIdentifier::builder()
            .set_key(Some(obj.key().unwrap().to_string()))
            .build()
            .map_err(Error::from)?;
        delete_objects.push(obj_id);
    }

    let return_keys = delete_objects.iter().map(|o| o.key.clone()).collect();

    if !delete_objects.is_empty() {
        client
            .delete_objects()
            .bucket(bucket_name)
            .delete(
                Delete::builder()
                    .set_objects(Some(delete_objects))
                    .build()
                    .map_err(Error::from)?,
            )
            .send()
            .await?;
    }

    let objects: ListObjectsV2Output =
 client.list_objects_v2().bucket(bucket_name).send().await?;

    eprintln!("{objects:?}");

    match objects.key_count {
        Some(0) => Ok(return_keys),
        _ => Err(Error::unhandled(
            "There were still objects left in the bucket.",
        )),
    }
}
```

- Para obter detalhes da API, consulte a DeleteObjectsreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteObjects(bucket: String, keys: [String]) async throws {
    let input = DeleteObjectsInput(
        bucket: bucket,
        delete: S3ClientTypes.Delete(
            objects: keys.map({ S3ClientTypes.ObjectIdentifier(key: $0) }),
            quiet: true
        )
    )

    do {
        let output = try await client.deleteObjects(input: input)

        // As of the last update to this example, any errors are returned
        // in the `output` object's `errors` property. If there are any
        // errors in this array, throw an exception. Once the error
        // handling is finalized in later updates to the AWS SDK for
        // Swift, this example will be updated to handle errors better.

        guard let errors = output.errors else {
            return  // No errors.
        }
        if errors.count != 0 {
            throw ServiceHandlerError.deleteObjectsError
```

```
            }
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjectsa referência da API AWS SDK for Swift.

Excluir a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como excluir a configuração de ciclo de vida de um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// This method removes the Lifecycle configuration from the named
        /// S3 bucket.
        /// </summary>
        /// <param name="client">The S3 client object used to call
        /// the RemoveLifecycleConfigAsync method.</param>
        /// <param name="bucketName">A string representing the name of the
        /// S3 bucket from which the configuration will be removed.</param>
        public static async Task RemoveLifecycleConfigAsync(IAmazonS3 client,
string bucketName)
        {
            var request = new DeleteLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
            };
```

```
            await client.DeleteLifecycleConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte DeleteBucketLifecyclea Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando exclui a configuração de ciclo de vida do bucket `my-bucket`:

```
aws s3api delete-bucket-lifecycle --bucket my-bucket
```

- Para obter detalhes da API, consulte DeleteBucketLifecycleem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name
```

```
    def delete_lifecycle_configuration(self):
        """
        Remove the lifecycle configuration from the specified bucket.
        """
        try:
            self.bucket.LifecycleConfiguration().delete()
            logger.info(
                "Deleted lifecycle configuration for bucket '%s'.",
self.bucket.name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete lifecycle configuration for bucket '%s'.",
                self.bucket.name,
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketLifecycleReferência da API AWSSDK for Python (Boto3).

Excluir a configuração de site de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como excluir a configuração de site de um bucket do S3.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucketWebsite(const Aws::String &bucketName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
```

```
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketWebsiteOutcome outcome =
            client.DeleteBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: DeleteBucketWebsite: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Website configuration was removed." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando exclui uma configuração de site do bucket `my-bucket`:

```
aws s3api delete-bucket-website --bucket my-bucket
```

- Para obter detalhes da API, consulte DeleteBucketWebsiteem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.DeleteBucketWebsiteRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class DeleteWebsiteConfiguration {
    public static void main(String[] args) {
        final String usage = """

                Usage:     <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to delete the website
 configuration from.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
```

```
        System.out.format("Deleting website configuration for Amazon S3 bucket:
 %s\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteBucketWebsiteConfig(s3, bucketName);
        System.out.println("Done!");
        s3.close();
    }

    public static void deleteBucketWebsiteConfig(S3Client s3, String bucketName)
 {
        DeleteBucketWebsiteRequest delReq = DeleteBucketWebsiteRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            s3.deleteBucketWebsite(delReq);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.out.println("Failed to delete website configuration!");
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a configuração de site do bucket.

```
import { DeleteBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Disable static website hosting on the bucket.
export const main = async () => {
  const command = new DeleteBucketWebsiteCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for JavaScript da API.

Determinar a existência e o tipo de conteúdo de um objeto em um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como determinar a existência e o tipo de conteúdo de um objeto em um bucket do S3.

CLI

AWS CLI

O seguinte comando recupera metadados de um objeto no bucket `my-bucket`:

```
aws s3api head-object --bucket my-bucket --key index.html
```

Saída:

```
{
    "AcceptRanges": "bytes",
    "ContentType": "text/html",
    "LastModified": "Thu, 16 Apr 2015 18:19:14 GMT",
    "ContentLength": 77,
    "VersionId": "null",
    "ETag": "\"30a6ec7e1a9ad79c203d05a589c8b400\"",
    "Metadata": {}
}
```

- Para obter detalhes da API, consulte HeadObjectem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determine o tipo de conteúdo de um objeto.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetObjectContentType {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <bucketName> <keyName>>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getContentType(s3, bucketName, keyName);
        s3.close();
    }

    public static void getContentType(S3Client s3, String bucketName, String
 keyName) {
        try {
            HeadObjectRequest objectRequest = HeadObjectRequest.builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            HeadObjectResponse objectHead = s3.headObject(objectRequest);
            String type = objectHead.contentType();
            System.out.println("The object content type is " + type);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha o status de restauração de um objeto.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

public class GetObjectRestoreStatus {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents the object.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        checkStatus(s3, bucketName, keyName);
        s3.close();
    }

    public static void checkStatus(S3Client s3, String bucketName, String
 keyName) {
        try {
            HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                    .bucket(bucketName)
```

```
                    .key(keyName)
                    .build();

            HeadObjectResponse response = s3.headObject(headObjectRequest);
            System.out.println("The Amazon S3 object restoration status is " +
 response.restore());

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte HeadObjecta Referência AWS SDK for Java 2.x da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectExistsWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Checks whether the object exists.
  #
```

```
  # @return [Boolean] True if the object exists; otherwise false.
  def exists?
    @object.exists?
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't check existence of object
 #{@object.bucket.name}:#{@object.key}. Here's why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"

  wrapper = ObjectExistsWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
  exists = wrapper.exists?

  puts "Object #{object_key} #{exists ? 'does' : 'does not'} exist."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte HeadObjecta Referência AWS SDK for Ruby da API.

Determinar a existência de um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como determinar a existência de um bucket do S3.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
```

```
# function bucket_exists
#
# This function checks to see if the specified bucket already exists.
#
# Parameters:
#       $1 - The name of the bucket to check.
#
# Returns:
#       0 - If the bucket already exists.
#       1 - If the bucket doesn't exist.
###############################################################################
function bucket_exists() {
  local bucket_name
  bucket_name=$1

  # Check whether the bucket already exists.
  # We suppress all output - we're interested only in the return code.

  if aws s3api head-bucket \
    --bucket "$bucket_name" \
    >/dev/null 2>&1; then
    return 0 # 0 in Bash script means true.
  else
    return 1 # 1 in Bash script means false.
  fi
}
```

- Para obter detalhes da API, consulte HeadBucketem Referência de AWS CLI Comandos.

CLI

AWS CLI

O seguinte comando verifica o acesso ao bucket `my-bucket`:

```
aws s3api head-bucket --bucket my-bucket
```

Se o bucket existir e você tiver acesso a ele, nenhuma saída será retornada. Caso contrário, uma mensagem de erro será exibida. Por exemplo: .

```
A client error (404) occurred when calling the HeadBucket operation: Not Found
```

- Para obter detalhes da API, consulte HeadBucketem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// BucketExists checks whether a bucket exists in the current account.
func (basics BucketBasics) BucketExists(bucketName string) (bool, error) {
 _, err := basics.S3Client.HeadBucket(context.TODO(), &s3.HeadBucketInput{
  Bucket: aws.String(bucketName),
 })
 exists := true
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NotFound:
    log.Printf("Bucket %v is available.\n", bucketName)
    exists = false
    err = nil
   default:
    log.Printf("Either you don't have access to bucket %v or another error
 occurred. "+
```

```
      "Here's what happened: %v\n", bucketName, err)
    }
   }
  } else {
   log.Printf("Bucket %v exists and you already own it.", bucketName)
  }

  return exists, err
}
```

- Para obter detalhes da API, consulte HeadBucketa Referência AWS SDK for Go da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def exists(self):
        """
        Determine whether the bucket exists and you have access to it.

        :return: True when the bucket exists; otherwise, False.
```

```
        """
        try:
            self.bucket.meta.client.head_bucket(Bucket=self.bucket.name)
            logger.info("Bucket %s exists.", self.bucket.name)
            exists = True
        except ClientError:
            logger.warning(
                "Bucket %s doesn't exist or you don't have access to it.",
                self.bucket.name,
            )
            exists = False
        return exists
```

- Para obter detalhes da API, consulte a HeadBucketReferência da API AWSSDK for Python (Boto3).

Fazer download de todos os objetos de um bucket do Amazon Simple Storage Service (Amazon S3) em um diretório local

O exemplo de código a seguir mostra como fazer download de todos os objetos de um bucket do Amazon Simple Storage Service (Amazon S3) em um diretório local.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use um S3 TransferManager para baixar todos os objetos do S3 no mesmo bucket do S3. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
```

```
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedDirectoryDownload;
import software.amazon.awssdk.transfer.s3.model.DirectoryDownload;
import software.amazon.awssdk.transfer.s3.model.DownloadDirectoryRequest;

import java.io.IOException;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.HashSet;
import java.util.Set;
import java.util.UUID;
import java.util.stream.Collectors;

    public Integer downloadObjectsToDirectory(S3TransferManager transferManager,
            String destinationPath, String bucketName) {
        DirectoryDownload directoryDownload =
 transferManager.downloadDirectory(DownloadDirectoryRequest.builder()
                .destination(Paths.get(destinationPath))
                .bucket(bucketName)
                .build());
        CompletedDirectoryDownload completedDirectoryDownload =
 directoryDownload.completionFuture().join();

        completedDirectoryDownload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
 fail.toString()));
        return completedDirectoryDownload.failedTransfers().size();
    }
```

- Para obter detalhes da API, consulte DownloadDirectorya Referência AWS SDK for Java 2.x da API.

Habilitar o registro em log em um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como habilitar o registro em log em um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;
using Microsoft.Extensions.Configuration;

/// <summary>
/// This example shows how to enable logging on an Amazon Simple Storage
/// Service (Amazon S3) bucket. You need to have two Amazon S3 buckets for
/// this example. The first is the bucket for which you wish to enable
/// logging, and the second is the location where you want to store the
/// logs.
/// </summary>
public class ServerAccessLogging
{
    private static IConfiguration _configuration = null!;

    public static async Task Main()
    {
        LoadConfig();

        string bucketName = _configuration["BucketName"];
        string logBucketName = _configuration["LogBucketName"];
        string logObjectKeyPrefix = _configuration["LogObjectKeyPrefix"];
        string accountId = _configuration["AccountId"];

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USWest2 or RegionEndpoint.USEast2.
        IAmazonS3 client = new AmazonS3Client();
```

```
            try
            {
                // Update bucket policy for target bucket to allow delivery of
logs to it.
                await SetBucketPolicyToAllowLogDelivery(
                    client,
                    bucketName,
                    logBucketName,
                    logObjectKeyPrefix,
                    accountId);

                // Enable logging on the source bucket.
                await EnableLoggingAsync(
                    client,
                    bucketName,
                    logBucketName,
                    logObjectKeyPrefix);
            }
            catch (AmazonS3Exception e)
            {
                Console.WriteLine($"Error: {e.Message}");
            }
        }

        /// <summary>
        /// This method grants appropriate permissions for logging to the
        /// Amazon S3 bucket where the logs will be stored.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client which will be
used
        /// to apply the bucket policy.</param>
        /// <param name="sourceBucketName">The name of the source bucket.</param>
        /// <param name="logBucketName">The name of the bucket where logging
        /// information will be stored.</param>
        /// <param name="logPrefix">The logging prefix where the logs should be
delivered.</param>
        /// <param name="accountId">The account id of the account where the
source bucket exists.</param>
        /// <returns>Async task.</returns>
        public static async Task SetBucketPolicyToAllowLogDelivery(
            IAmazonS3 client,
            string sourceBucketName,
            string logBucketName,
```

```
            string logPrefix,
            string accountId)
        {
            var resourceArn = @"""arn:aws:s3:::" + logBucketName + "/" +
logPrefix + @"*""";

            var newPolicy = @"{
                                ""Statement"":[{
                                ""Sid"": ""S3ServerAccessLogsPolicy"",
                                ""Effect"": ""Allow"",
                                ""Principal"": { ""Service"":
""logging.s3.amazonaws.com"" },
                                ""Action"": [""s3:PutObject""],
                                ""Resource"": [" + resourceArn + @"],
                                ""Condition"": {
                                ""ArnLike"": { ""aws:SourceArn"":
""arn:aws:s3:::" + sourceBucketName + @""" },
                                ""StringEquals"": { ""aws:SourceAccount"": """ +
accountId + @""" }
                                        }
                                    }]
                                }";
            Console.WriteLine($"The policy to apply to bucket {logBucketName} to
enable logging:");
            Console.WriteLine(newPolicy);

            PutBucketPolicyRequest putRequest = new PutBucketPolicyRequest
            {
                BucketName = logBucketName,
                Policy = newPolicy,
            };
            await client.PutBucketPolicyAsync(putRequest);
            Console.WriteLine("Policy applied.");
        }

        /// <summary>
        /// This method enables logging for an Amazon S3 bucket. Logs will be
stored
        /// in the bucket you selected for logging. Selected prefix
        /// will be prepended to each log object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client which will be
used
```

```
        /// to configure and apply logging to the selected Amazon S3 bucket.</
param>
        /// <param name="bucketName">The name of the Amazon S3 bucket for which
 you
        /// wish to enable logging.</param>
        /// <param name="logBucketName">The name of the Amazon S3 bucket where
 logging
        /// information will be stored.</param>
        /// <param name="logObjectKeyPrefix">The prefix to prepend to each
        /// object key.</param>
        /// <returns>Async task.</returns>
        public static async Task EnableLoggingAsync(
            IAmazonS3 client,
            string bucketName,
            string logBucketName,
            string logObjectKeyPrefix)
        {
            Console.WriteLine($"Enabling logging for bucket {bucketName}.");
            var loggingConfig = new S3BucketLoggingConfig
            {
                TargetBucketName = logBucketName,
                TargetPrefix = logObjectKeyPrefix,
            };

            var putBucketLoggingRequest = new PutBucketLoggingRequest
            {
                BucketName = bucketName,
                LoggingConfig = loggingConfig,
            };
            await client.PutBucketLoggingAsync(putBucketLoggingRequest);
            Console.WriteLine($"Logging enabled.");
        }

        /// <summary>
        /// Loads configuration from settings files.
        /// </summary>
        public static void LoadConfig()
        {
            _configuration = new ConfigurationBuilder()
                .SetBasePath(Directory.GetCurrentDirectory())
                .AddJsonFile("settings.json") // Load settings from .json file.
                .AddJsonFile("settings.local.json", true) // Optionally, load
 local settings.
                .Build();
```

```
        }
    }
```

- Para obter detalhes da API, consulte PutBucketLoggingga Referência AWS SDK for .NET da API.

Habilitar notificações para um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como habilitar notificações para um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to enable notifications for an Amazon Simple
    /// Storage Service (Amazon S3) bucket.
    /// </summary>
    public class EnableNotifications
    {
        public static async Task Main()
        {
            const string bucketName = "doc-example-bucket1";
            const string snsTopic = "arn:aws:sns:us-east-2:0123456789ab:bucket-
notify";
            const string sqsQueue = "arn:aws:sqs:us-
east-2:0123456789ab:Example_Queue";
```

```
            IAmazonS3 client = new AmazonS3Client(Amazon.RegionEndpoint.USEast2);
            await EnableNotificationAsync(client, bucketName, snsTopic,
sqsQueue);
        }

        /// <summary>
        /// This method makes the call to the PutBucketNotificationAsync method.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client used to call
        /// the PutBucketNotificationAsync method.</param>
        /// <param name="bucketName">The name of the bucket for which
        /// notifications will be turned on.</param>
        /// <param name="snsTopic">The ARN for the Amazon Simple Notification
        /// Service (Amazon SNS) topic associated with the S3 bucket.</param>
        /// <param name="sqsQueue">The ARN of the Amazon Simple Queue Service
        /// (Amazon SQS) queue to which notifications will be pushed.</param>
        public static async Task EnableNotificationAsync(
            IAmazonS3 client,
            string bucketName,
            string snsTopic,
            string sqsQueue)
        {
            try
            {
                // The bucket for which we are setting up notifications.
                var request = new PutBucketNotificationRequest()
                {
                    BucketName = bucketName,
                };

                // Defines the topic to use when sending a notification.
                var topicConfig = new TopicConfiguration()
                {
                    Events = new List<EventType> { EventType.ObjectCreatedCopy },
                    Topic = snsTopic,
                };
                request.TopicConfigurations = new List<TopicConfiguration>
                {
                    topicConfig,
                };
                request.QueueConfigurations = new List<QueueConfiguration>
                {
                    new QueueConfiguration()
```

```
                    {
                        Events = new List<EventType>
 { EventType.ObjectCreatedPut },
                        Queue = sqsQueue,
                    },
                };

                // Now apply the notification settings to the bucket.
                PutBucketNotificationResponse response = await
 client.PutBucketNotificationAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutBucketNotificationConfiguration a Referência AWS SDK for .NET da API.

CLI

AWS CLI

O exemplo aplica uma configuração de notificação ao bucket `my-bucket`:

```
aws s3api put-bucket-notification --bucket my-bucket --notification-configuration
 file://notification.json
```

O arquivo `notification.json` é um documento JSON na pasta atual que especifica um tópico do SNS e o tipo de evento a ser monitorado:

```
{
  "TopicConfiguration": {
    "Event": "s3:ObjectCreated:*",
    "Topic": "arn:aws:sns:us-west-2:123456789012:s3-notification-topic"
  }
}
```

O tópico do SNS deve ter uma política do IAM anexada que permita que o Amazon S3 publique nele:

```
{
 "Version": "2008-10-17",
 "Id": "example-ID",
 "Statement": [
  {
   "Sid": "example-statement-ID",
   "Effect": "Allow",
   "Principal": {
     "Service": "s3.amazonaws.com"
   },
   "Action": [
    "SNS:Publish"
   ],
   "Resource": "arn:aws:sns:us-west-2:123456789012:my-bucket",
   "Condition": {
      "ArnLike": {
      "aws:SourceArn": "arn:aws:s3:*:*:my-bucket"
    }
   }
  }
 ]
}
```

- Para obter detalhes da API, consulte PutBucketNotificationConfigurationem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
```

```
import software.amazon.awssdk.services.s3.model.Event;
import software.amazon.awssdk.services.s3.model.NotificationConfiguration;
import
 software.amazon.awssdk.services.s3.model.PutBucketNotificationConfigurationRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.TopicConfiguration;
import java.util.ArrayList;
import java.util.List;

public class SetBucketEventBridgeNotification {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The Amazon S3 bucket.\s
                    topicArn - The Simple Notification Service topic ARN.\s
                    id - An id value used for the topic configuration. This value
 is displayed in the AWS Management Console.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String topicArn = args[1];
        String id = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        setBucketNotification(s3Client, bucketName, topicArn, id);
        s3Client.close();
    }

    public static void setBucketNotification(S3Client s3Client, String
 bucketName, String topicArn, String id) {
        try {
            List<Event> events = new ArrayList<>();
```

```
            events.add(Event.S3_OBJECT_CREATED_PUT);

            TopicConfiguration config = TopicConfiguration.builder()
                    .topicArn(topicArn)
                    .events(events)
                    .id(id)
                    .build();

            List<TopicConfiguration> topics = new ArrayList<>();
            topics.add(config);

            NotificationConfiguration configuration =
 NotificationConfiguration.builder()
                    .topicConfigurations(topics)
                    .build();

            PutBucketNotificationConfigurationRequest configurationRequest =
 PutBucketNotificationConfigurationRequest
                    .builder()
                    .bucket(bucketName)
                    .notificationConfiguration(configuration)
                    .skipDestinationValidation(true)
                    .build();

            // Set the bucket notification configuration.
            s3Client.putBucketNotificationConfiguration(configurationRequest);
            System.out.println("Added bucket " + bucketName + " with EventBridge
 events enabled.");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketNotificationConfigurationa Referência AWS SDK for Java 2.x da API.

Habilitar a aceleração de transferência para um bucket do Amazon S3 usando um AWS SDK

O exemplo a seguir mostra como habilitar a aceleração de transferência para um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// Amazon Simple Storage Service (Amazon S3) Transfer Acceleration is a
/// bucket-level feature that enables you to perform faster data transfers
/// to Amazon S3. This example shows how to configure Transfer
/// Acceleration.
/// </summary>
public class TransferAcceleration
{
    /// <summary>
    /// The main method initializes the client object and sets the
    /// Amazon Simple Storage Service (Amazon S3) bucket name before
    /// calling EnableAccelerationAsync.
    /// </summary>
    public static async Task Main()
    {
        var s3Client = new AmazonS3Client();
        const string bucketName = "doc-example-bucket";

        await EnableAccelerationAsync(s3Client, bucketName);
    }

    /// <summary>
```

```
        /// This method sets the configuration to enable transfer acceleration
        /// for the bucket referred to in the bucketName parameter.
        /// </summary>
        /// <param name="client">An Amazon S3 client used to enable the
        /// acceleration on an Amazon S3 bucket.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket for which
the
        /// method will be enabling acceleration.</param>
        private static async Task EnableAccelerationAsync(AmazonS3Client client,
string bucketName)
        {
            try
            {
                var putRequest = new PutBucketAccelerateConfigurationRequest
                {
                    BucketName = bucketName,
                    AccelerateConfiguration = new AccelerateConfiguration
                    {
                        Status = BucketAccelerateStatus.Enabled,
                    },
                };
                await client.PutBucketAccelerateConfigurationAsync(putRequest);

                var getRequest = new GetBucketAccelerateConfigurationRequest
                {
                    BucketName = bucketName,
                };
                var response = await
client.GetBucketAccelerateConfigurationAsync(getRequest);

                Console.WriteLine($"Acceleration state = '{response.Status}' ");
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error occurred. Message:'{ex.Message}' when
setting transfer acceleration");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutBucketAccelerateConfigurationa Referência AWS SDK for .NET da API.

Obter regras de CORS para um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como obter regras de compartilhamento de recursos de origem cruzada (CORS) para um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Retrieve the CORS configuration applied to the Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to retrieve the CORS configuration.</param>
        /// <returns>The created CORS configuration object.</returns>
        private static async Task<CORSConfiguration>
RetrieveCORSConfigurationAsync(AmazonS3Client client)
        {
            GetCORSConfigurationRequest request = new
GetCORSConfigurationRequest()
            {
                BucketName = BucketName,
            };
            var response = await client.GetCORSConfigurationAsync(request);
            var configuration = response.Configuration;
            PrintCORSRules(configuration);
            return configuration;
        }
```

- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando recupera a configuração de compartilhamento de recursos de origem cruzada para o bucket `my-bucket`:

```
aws s3api get-bucket-cors --bucket my-bucket
```

Saída:

```
{
    "CORSRules": [
        {
            "AllowedHeaders": [
                "*"
            ],
            "ExposeHeaders": [
                "x-amz-server-side-encryption"
            ],
            "AllowedMethods": [
                "PUT",
                "POST",
                "DELETE"
            ],
            "MaxAgeSeconds": 3000,
            "AllowedOrigins": [
                "http://www.example.com"
            ]
        },
        {
            "AllowedHeaders": [
                "Authorization"
            ],
            "MaxAgeSeconds": 3000,
            "AllowedMethods": [
                "GET"
            ],
            "AllowedOrigins": [
```

```
                "*"
            ]
        }
    ]
}
```

- Para obter detalhes da API, consulte GetBucketCorsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de CORS para o bucket.

```
import { GetBucketCorsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketCorsCommand({
    Bucket: "test-bucket",
  });

  try {
    const { CORSRules } = await client.send(command);
    CORSRules.forEach((cr, i) => {
      console.log(
        `\nCORSRule ${i + 1}`,
        `\n${"-".repeat(10)}`,
        `\nAllowedHeaders: ${cr.AllowedHeaders.join(" ")}`,
        `\nAllowedMethods: ${cr.AllowedMethods.join(" ")}`,
        `\nAllowedOrigins: ${cr.AllowedOrigins.join(" ")}`,
        `\nExposeHeaders: ${cr.ExposeHeaders.join(" ")}`,
        `\nMaxAgeSeconds: ${cr.MaxAgeSeconds}`,
      );
    });
```

```
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_cors(self):
        """
        Get the CORS rules for the bucket.

        :return The CORS rules for the specified bucket.
        """
        try:
```

```
            cors = self.bucket.Cors()
            logger.info(
                "Got CORS rules %s for bucket '%s'.", cors.cors_rules,
 self.bucket.name
            )
        except ClientError:
            logger.exception(("Couldn't get CORS for bucket %s.",
 self.bucket.name))
            raise
        else:
            return cors
```

- Para obter detalhes da API, consulte a GetBucketCorsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with
 an existing bucket.
  def initialize(bucket_cors)
    @bucket_cors = bucket_cors
  end

  # Gets the CORS configuration of a bucket.
  #
```

```
  # @return [Aws::S3::Type::GetBucketCorsOutput, nil] The current CORS
 configuration for the bucket.
  def get_cors
    @bucket_cors.data
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get CORS configuration for #{@bucket_cors.bucket.name}. Here's
 why: #{e.message}"
    nil
  end

end
```

- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for Ruby da API.

Obtenha um objeto Amazon S3 de um ponto de acesso multirregional usando um SDK AWS

O exemplo de código a seguir mostra como obter um objeto de um ponto de acesso multirregional.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Conceitos básicos de buckets e objetos
- Conceitos básicos de criptografia

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure o cliente S3 para usar o algoritmo de assinatura assimétrica Sigv4 (SIGv4a).

```
        suspend fun createS3Client(): S3Client {
```

```
            // Configure your S3Client to use the Asymmetric Sigv4 (Sigv4a)
signing algorithm.
            val sigV4AScheme = SigV4AsymmetricAuthScheme(CrtAwsSigner)
            val s3 = S3Client.fromEnvironment {
                authSchemes = listOf(sigV4AScheme)
            }
            return s3
        }
```

Use o ARN do ponto de acesso multirregional em vez de um nome de bucket para recuperar o objeto.

```
    suspend fun getObjectFromMrap(s3: S3Client, mrapArn: String, keyName:
String): String? {
        val request = GetObjectRequest {
            bucket = mrapArn // Use the ARN instead of the bucket name for object
operations.
            key = keyName
        }

        var stringObj: String? = null
        s3.getObject(request) { resp ->
            stringObj = resp.body?.decodeToString()
            if (stringObj != null) {
                println("Successfully read $keyName from $mrapArn")
            }
        }
        return stringObj
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.
- Para obter detalhes da API, consulte a GetObjectreferência da API AWSSDK for Kotlin.

Obter um objeto de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como ler dados de um objeto em um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Conceitos básicos de buckets e objetos
- Conceitos básicos de criptografia

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to download an object from an Amazon S3 bucket to the
        /// local computer.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket where the object is
        /// currently stored.</param>
        /// <param name="objectName">The name of the object to download.</param>
        /// <param name="filePath">The path, including filename, where the
        /// downloaded object will be stored.</param>
        /// <returns>A boolean value indicating the success or failure of the
        /// download process.</returns>
        public static async Task<bool> DownloadObjectFromBucketAsync(
            IAmazonS3 client,
            string bucketName,
            string objectName,
            string filePath)
        {
            // Create a GetObject request
            var request = new GetObjectRequest
            {
                BucketName = bucketName,
                Key = objectName,
            };

            // Issue request and remember to dispose of the response
```

```
            using GetObjectResponse response = await
 client.GetObjectAsync(request);

            try
            {
                // Save object to local file
                await response.WriteResponseStreamToFileAsync($"{filePath}\
\{objectName}", true, CancellationToken.None);
                return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error saving {objectName}: {ex.Message}");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function download_object_from_bucket
```

```
#
# This function downloads an object in a bucket to a file.
#
# Parameters:
#       $1 - The name of the bucket to download the object from.
#       $2 - The path and file name to store the downloaded bucket.
#       $3 - The key (name) of the object in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function download_object_from_bucket() {
  local bucket_name=$1
  local destination_file_name=$2
  local object_name=$3
  local response

  response=$(aws s3api get-object \
    --bucket "$bucket_name" \
    --key "$object_name" \
    "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte GetObjectem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetObject(const Aws::String &objectKey,
                           const Aws::String &fromBucket,
                           const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(fromBucket);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome =
            client.GetObject(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Successfully retrieved '" << objectKey << "' from '"
                  << fromBucket << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte exemplo usa o comando `get-object` para fazer download de um objeto do Amazon S3:

```
aws s3api get-object --bucket text-content --key dir/my_images.tar.bz2
 my_images.tar.bz2
```

Observe que o parâmetro outfile é especificado sem um nome de opção, como “--outfile”. O nome do arquivo de saída deve ser o último parâmetro no comando.

O exemplo abaixo demonstra o uso de `--range` para fazer download de um intervalo de bytes específico de um objeto. Observe que os intervalos de bytes precisam ser prefixados com “bytes=”:

```
aws s3api get-object --bucket text-content --key dir/my_data --range
 bytes=8888-9999 my_data_range
```

Para obter mais informações sobre como recuperar objetos, consulte Obter um objeto no Guia do desenvolvedor do Amazon S3.

- Para obter detalhes da API, consulte GetObjectem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DownloadFile gets an object from a bucket and stores it in a local file.
func (basics BucketBasics) DownloadFile(bucketName string, objectKey string,
 fileName string) error {
 result, err := basics.S3Client.GetObject(context.TODO(), &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
```

```
 })
 if err != nil {
  log.Printf("Couldn't get object %v:%v. Here's why: %v\n", bucketName,
 objectKey, err)
  return err
 }
 defer result.Body.Close()
 file, err := os.Create(fileName)
 if err != nil {
  log.Printf("Couldn't create file %v. Here's why: %v\n", fileName, err)
  return err
 }
 defer file.Close()
 body, err := io.ReadAll(result.Body)
 if err != nil {
  log.Printf("Couldn't read object body from %v. Here's why: %v\n", objectKey,
 err)
 }
 _, err = file.Write(body)
 return err
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Leia dados como uma matriz de bytes usando um S3Client.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
```

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetObjectData {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <path>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
                    path - The path where the file is written to.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String path = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getObjectBytes(s3, bucketName, keyName, path);
```

```
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
 keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
 s3.getObjectAsBytes(objectRequest);
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Use um S3 TransferManager para baixar um objeto em um bucket do S3 para um arquivo local. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedFileDownload;
import software.amazon.awssdk.transfer.s3.model.DownloadFileRequest;
import software.amazon.awssdk.transfer.s3.model.FileDownload;
import software.amazon.awssdk.transfer.s3.progress.LoggingTransferListener;
```

```
import java.io.IOException;
import java.net.URL;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.UUID;

    public Long downloadFile(S3TransferManager transferManager, String
 bucketName,
            String key, String downloadedFileWithPath) {
        DownloadFileRequest downloadFileRequest = DownloadFileRequest.builder()
                .getObjectRequest(b -> b.bucket(bucketName).key(key))
                .addTransferListener(LoggingTransferListener.create())
                .destination(Paths.get(downloadedFileWithPath))
                .build();

        FileDownload downloadFile =
 transferManager.downloadFile(downloadFileRequest);

        CompletedFileDownload downloadResult =
 downloadFile.completionFuture().join();
        logger.info("Content length [{}]",
 downloadResult.response().contentLength());
        return downloadResult.response().contentLength();
    }
```

Leia etiquetas que pertencem a um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectTaggingRequest;
import software.amazon.awssdk.services.s3.model.GetObjectTaggingResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.Tag;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetObjectTags {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents the object.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listTags(s3, bucketName, keyName);
        s3.close();
    }

    public static void listTags(S3Client s3, String bucketName, String keyName) {
        try {
            GetObjectTaggingRequest getTaggingRequest = GetObjectTaggingRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            GetObjectTaggingResponse tags =
 s3.getObjectTagging(getTaggingRequest);
            List<Tag> tagSet = tags.tagSet();
            for (Tag tag : tagSet) {
```

```
                System.out.println(tag.key());
                System.out.println(tag.value());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha um URL para um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetUrlRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.net.URL;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetObjectUrl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.
                    keyName - A key name that represents the object.\s
                """;

        if (args.length != 2) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getURL(s3, bucketName, keyName);
        s3.close();
    }

    public static void getURL(S3Client s3, String bucketName, String keyName) {
        try {
            GetUrlRequest request = GetUrlRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            URL url = s3.utilities().getUrl(request);
            System.out.println("The URL for  " + keyName + " is " + url);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha um objeto usando o objeto de cliente S3Presigner usando um S3Client.

```
import java.io.IOException;
import java.io.InputStream;
import java.io.OutputStream;
import java.net.HttpURLConnection;
import java.time.Duration;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
```

```
import
 software.amazon.awssdk.services.s3.presigner.model.GetObjectPresignRequest;
import
 software.amazon.awssdk.services.s3.presigner.model.PresignedGetObjectRequest;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import software.amazon.awssdk.utils.IoUtils;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetObjectPresignedUrl {
    public static void main(String[] args) {
        final String USAGE = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents a text file.\s
                """;

        if (args.length != 2) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Presigner presigner = S3Presigner.builder()
                .region(region)
                .build();

        getPresignedUrl(presigner, bucketName, keyName);
        presigner.close();
    }
```

```
   public static void getPresignedUrl(S3Presigner presigner, String bucketName,
String keyName) {
       try {
           GetObjectRequest getObjectRequest = GetObjectRequest.builder()
                   .bucket(bucketName)
                   .key(keyName)
                   .build();

           GetObjectPresignRequest getObjectPresignRequest =
GetObjectPresignRequest.builder()
                   .signatureDuration(Duration.ofMinutes(60))
                   .getObjectRequest(getObjectRequest)
                   .build();

           PresignedGetObjectRequest presignedGetObjectRequest =
presigner.presignGetObject(getObjectPresignRequest);
           String theUrl = presignedGetObjectRequest.url().toString();
           System.out.println("Presigned URL: " + theUrl);
           HttpURLConnection connection = (HttpURLConnection)
presignedGetObjectRequest.url().openConnection();
           presignedGetObjectRequest.httpRequest().headers().forEach((header,
values) -> {
               values.forEach(value -> {
                   connection.addRequestProperty(header, value);
               });
           });

           // Send any request payload that the service needs (not needed when
           // isBrowserExecutable is true).
           if (presignedGetObjectRequest.signedPayload().isPresent()) {
               connection.setDoOutput(true);

               try (InputStream signedPayload =
presignedGetObjectRequest.signedPayload().get().asInputStream();
                       OutputStream httpOutputStream =
connection.getOutputStream()) {
                   IoUtils.copy(signedPayload, httpOutputStream);
               }
           }

           // Download the result of executing the request.
           try (InputStream content = connection.getInputStream()) {
               System.out.println("Service returned response: ");
               IoUtils.copy(content, System.out);
```

```
            }

        } catch (S3Exception | IOException e) {
            e.getStackTrace();
        }
    }
}
```

Obtenha um objeto usando um ResponseTransformer objeto e o S3Client.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.core.sync.ResponseTransformer;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetDataResponseTransformer {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <path>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
```

```
                    path - The path where the file is written to.\s
                """";

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String path = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getObjectBytes(s3, bucketName, keyName, path);
        s3.close();
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
s3.getObject(objectRequest, ResponseTransformer.toBytes());
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Baixe o objeto.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetObjectCommand({
    Bucket: "test-bucket",
    Key: "hello-s3.txt",
  });

  try {
    const response = await client.send(command);
    // The Body object also has 'transformToByteArray' and 'transformToWebStream'
 methods.
    const str = await response.Body.transformToString();
    console.log(str);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getObjectBytes(bucketName: String, keyName: String, path: String) {
    val request = GetObjectRequest {
        key = keyName
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.getObject(request) { resp ->
            val myFile = File(path)
            resp.body?.writeToFile(myFile)
            println("Successfully read $keyName from $bucketName")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um objeto.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $file = $this->s3client->getObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
            ]);
            $body = $file->get('Body');
            $body->rewind();
            echo "Downloaded the file and it begins with: {$body->read(26)}.\n";
        } catch (Exception $exception) {
            echo "Failed to download $fileName from $this->bucketName with error:
" . $exception->getMessage();
            exit("Please fix error with file downloading before continuing.");
        }
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def get(self):
        """
        Gets the object.

        :return: The object data in bytes.
        """
        try:
            body = self.object.get()["Body"].read()
            logger.info(
                "Got object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't get object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
        else:
            return body
```

- Para obter detalhes da API, consulte a GetObjectReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um objeto.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectGetWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Gets the object directly to a file.
  #
  # @param target_path [String] The path to the file where the object is
 downloaded.
  # @return [Aws::S3::Types::GetObjectOutput, nil] The retrieved object data if
 successful; otherwise nil.
  def get_object(target_path)
    @object.get(response_target: target_path)
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get object #{@object.key}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"
  target_path = "my-object-as-file.txt"

  wrapper = ObjectGetWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
```

```
  obj_data = wrapper.get_object(target_path)
  return unless obj_data

  puts "Object #{object_key} (#{obj_data.content_length} bytes} downloaded to
 #{target_path}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Obtenha um objeto e relate seu estado de criptografia no lado do servidor.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectGetEncryptionWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Gets the object into memory.
  #
  # @return [Aws::S3::Types::GetObjectOutput, nil] The retrieved object data if
 successful; otherwise nil.
  def get_object
    @object.get
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get object #{@object.key}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"

  wrapper = ObjectGetEncryptionWrapper.new(Aws::S3::Object.new(bucket_name,
 object_key))
  obj_data = wrapper.get_object
  return unless obj_data
```

```
  encryption = obj_data.server_side_encryption.nil? ? "no" :
 obj_data.server_side_encryption
  puts "Object #{object_key} uses #{encryption} encryption."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn get_object(client: Client, opt: Opt) -> Result<usize, anyhow::Error> {
    trace!("bucket:      {}", opt.bucket);
    trace!("object:      {}", opt.object);
    trace!("destination: {}", opt.destination.display());

    let mut file = File::create(opt.destination.clone())?;

    let mut object = client
        .get_object()
        .bucket(opt.bucket)
        .key(opt.object)
        .send()
        .await?;

    let mut byte_count = 0_usize;
    while let Some(bytes) = object.body.try_next().await? {
        let bytes_len = bytes.len();
        file.write_all(&bytes)?;
        trace!("Intermediate write of {bytes_len}");
        byte_count += bytes_len;
    }
```

```
    Ok(byte_count)
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_s3->getobject(           " oo_result is returned for
testing purposes. "
                  iv_bucket = iv_bucket_name
                  iv_key = iv_object_key
               ).
       DATA(lv_object_data) = oo_result->get_body( ).
       MESSAGE 'Object retrieved from S3 bucket.' TYPE 'I'.
     CATCH /aws1/cx_s3_nosuchbucket.
       MESSAGE 'Bucket does not exist.' TYPE 'E'.
     CATCH /aws1/cx_s3_nosuchkey.
       MESSAGE 'Object key does not exist.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Baixe um objeto de um bucket para um arquivo local.

```
   public func downloadFile(bucket: String, key: String, to: String) async
throws {
       let fileUrl = URL(fileURLWithPath: to).appendingPathComponent(key)

       let input = GetObjectInput(
           bucket: bucket,
           key: key
       )
       let output = try await client.getObject(input: input)

       // Get the data stream object. Return immediately if there isn't one.
       guard let body = output.body,
             let data = try await body.readData() else {
           return
       }
       try data.write(to: fileUrl)
   }
```

Leia um objeto em um objeto Swift Data.

```
   public func readFile(bucket: String, key: String) async throws -> Data {
```

```
        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the stream and return its contents in a `Data` object. If
        // there is no stream, return an empty `Data` object instead.
        guard let body = output.body,
              let data = try await body.readData() else {
            return "".data(using: .utf8)!
        }

        return data
    }
```

- Para obter detalhes da API, consulte GetObjecta referência da API AWS SDK for Swift.

Obter um objeto de um bucket do Amazon S3 usando um AWS SDK e especificando um cabeçalho If-Modified-Since

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3, mas somente se esse bucket não tiver sido modificado desde a última recuperação.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Conceitos básicos de buckets e objetos
- Conceitos básicos de criptografia

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use aws_sdk_s3::{
    error::SdkError,
    operation::head_object::HeadObjectError,
    primitives::{ByteStream, DateTime, DateTimeFormat},
    Client, Error,
};
use tracing::{error, warn};

const KEY: &str = "key";
const BODY: &str = "Hello, world!";

/// Demonstrate how `if-modified-since` reports that matching objects haven't
/// changed.
///
/// # Steps
/// - Create a bucket.
/// - Put an object in the bucket.
/// - Get the bucket headers.
/// - Get the bucket headers again but only if modified.
/// - Delete the bucket.
#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt::init();

    // Get a new UUID to use when creating a unique bucket name.
    let uuid = uuid::Uuid::new_v4();

    // Load the AWS configuration from the environment.
    let client = Client::new(&aws_config::load_from_env().await);

    // Generate a unique bucket name using the previously generated UUID.
    // Then create a new bucket with that name.
    let bucket_name = format!("if-modified-since-{uuid}");
    client
        .create_bucket()
        .bucket(bucket_name.clone())
        .send()
        .await?;

    // Create a new object in the bucket whose name is `KEY` and whose
    // contents are `BODY`.
    let put_object_output = client
        .put_object()
```

```
        .bucket(bucket_name.as_str())
        .key(KEY)
        .body(ByteStream::from_static(BODY.as_bytes()))
        .send()
        .await;

    // If the `PutObject` succeeded, get the eTag string from it. Otherwise,
    // report an error and return an empty string.
    let e_tag_1 = match put_object_output {
        Ok(put_object) => put_object.e_tag.unwrap(),
        Err(err) => {
            error!("{err:?}");
            String::new()
        }
    };

    // Request the object's headers.
    let head_object_output = client
        .head_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .send()
        .await;

    // If the `HeadObject` request succeeded, create a tuple containing the
    // values of the headers `last-modified` and `etag`. If the request
    // failed, return the error in a tuple instead.
    let (last_modified, e_tag_2) = match head_object_output {
        Ok(head_object) => (
            Ok(head_object.last_modified().cloned().unwrap()),
            head_object.e_tag.unwrap(),
        ),
        Err(err) => (Err(err), String::new()),
    };

    warn!("last modified: {last_modified:?}");
    assert_eq!(
        e_tag_1, e_tag_2,
        "PutObject and first GetObject had differing eTags"
    );

    println!("First value of last_modified: {last_modified:?}");
    println!("First tag: {}\n", e_tag_1);
```

```
    // Send a second `HeadObject` request. This time, the `if_modified_since`
    // option is specified, giving the `last_modified` value returned by the
    // first call to `HeadObject`.
    //
    // Since the object hasn't been changed, and there are no other objects in
    // the bucket, there should be no matching objects.

    let head_object_output = client
        .head_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .if_modified_since(last_modified.unwrap())
        .send()
        .await;

    // If the `HeadObject` request succeeded, the result is a typle containing
    // the `last_modified` and `e_tag_1` properties. This is _not_ the expected
    // result.
    //
    // The _expected_ result of the second call to `HeadObject` is an
    // `SdkError::ServiceError` containing the HTTP error response. If that's
    // the case and the HTTP status is 304 (not modified), the output is a
    // tuple containing the values of the HTTP `last-modified` and `etag`
    // headers.
    //
    // If any other HTTP error occurred, the error is returned as an
    // `SdkError::ServiceError`.

    let (last_modified, e_tag_2): (Result<DateTime, SdkError<HeadObjectError>>,
String) =
        match head_object_output {
            Ok(head_object) => (
                Ok(head_object.last_modified().cloned().unwrap()),
                head_object.e_tag.unwrap(),
            ),
            Err(err) => match err {
                SdkError::ServiceError(err) => {
                    // Get the raw HTTP response. If its status is 304, the
                    // object has not changed. This is the expected code path.
                    let http = err.raw();
                    match http.status().as_u16() {
                        // If the HTTP status is 304: Not Modified, return a
                        // tuple containing the values of the HTTP
                        // `last-modified` and `etag` headers.
```

```
                        304 => (
                            Ok(DateTime::from_str(
                                http.headers().get("last-modified").unwrap(),
                                DateTimeFormat::HttpDate,
                            )
                            .unwrap()),
                            http.headers().get("etag").map(|t|
t.into()).unwrap(),
                        ),
                        // Any other HTTP status code is returned as an
                        // `SdkError::ServiceError`.
                        _ => (Err(SdkError::ServiceError(err)), String::new()),
                    }
                }
                // Any other kind of error is returned in a tuple containing the
                // error and an empty string.
                _ => (Err(err), String::new()),
            },
        };

    warn!("last modified: {last_modified:?}");
    assert_eq!(
        e_tag_1, e_tag_2,
        "PutObject and second HeadObject had different eTags"
    );

    println!("Second value of last modified: {last_modified:?}");
    println!("Second tag: {}", e_tag_2);

    // Clean up by deleting the object and the bucket.
    client
        .delete_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .send()
        .await?;

    client
        .delete_bucket()
        .bucket(bucket_name.as_str())
        .send()
        .await?;

    Ok(())
```

```
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for Rust.

Obter a ACL de um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar listas de controle de acesso (ACLs)

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Get the access control list (ACL) for the new bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to get the
        /// access control list (ACL) of the bucket.</param>
        /// <param name="newBucketName">The name of the newly created bucket.</
param>
        /// <returns>An S3AccessControlList.</returns>
        public static async Task<S3AccessControlList>
 GetACLForBucketAsync(IAmazonS3 client, string newBucketName)
        {
            // Retrieve bucket ACL to show that the ACL was properly applied to
            // the new bucket.
```

```
            GetACLResponse getACLResponse = await client.GetACLAsync(new
 GetACLRequest
            {
                BucketName = newBucketName,
            });

            return getACLResponse.AccessControlList;
        }
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetBucketAcl(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketAclRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketAclOutcome outcome =
            s3_client.GetBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetBucketAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        Aws::Vector<Aws::S3::Model::Grant> grants =
```

```
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            Aws::S3::Model::Grant grant = *it;
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            std::cout << "For bucket " << bucketName << ": "
                      << std::endl << std::endl;

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << GetGranteeTypeString(grantee.GetType()) <<
 std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
                      GetPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which converts a built-in type enumeration to a human-readable
 string.
/*!
 \sa GetGranteeTypeString()
 \param type Type enumeration.
*/

Aws::String GetGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable
 string.
/*!
 \sa GetPermissionString()
 \param permission Permission enumeration.
*/

Aws::String GetPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can list objects in this bucket, create/overwrite/delete "
                   "objects in this bucket, and read/write this "
                   "bucket's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can list objects in this bucket";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this bucket's permissions";
        case Aws::S3::Model::Permission::WRITE:
            return "Can create, overwrite, and delete objects in this bucket";
        case Aws::S3::Model::Permission::WRITE_ACP:
```

```
            return "Can write this bucket's permissions";
        default:
            return "Permission unknown";
    }

    return "Permission unknown";
}
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando recupera a lista de controle de acesso do bucket `my-bucket`:

```
aws s3api get-bucket-acl --bucket my-bucket
```

Saída:

```
{
    "Owner": {
        "DisplayName": "my-username",
        "ID": "7009a8971cd538e11f6b6606438875e7c86c5b672f46db45460ddcd087d36c32"
    },
    "Grants": [
        {
            "Grantee": {
                "DisplayName": "my-username",
                "ID":
 "7009a8971cd538e11f6b6606438875e7c86c5b672f46db45460ddcd087d36c32"
            },
            "Permission": "FULL_CONTROL"
        }
    ]
}
```

- Para obter detalhes da API, consulte GetBucketAclem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectAclRequest;
import software.amazon.awssdk.services.s3.model.GetObjectAclResponse;
import software.amazon.awssdk.services.s3.model.Grant;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetAcl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <bucketName> <objectKey>

                Where:
                  bucketName - The Amazon S3 bucket to get the access control
 list (ACL) for.
                  objectKey - The object to get the ACL for.\s
                """;

        if (args.length != 2) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String objectKey = args[1];
        System.out.println("Retrieving ACL for object: " + objectKey);
        System.out.println("in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getBucketACL(s3, objectKey, bucketName);
        s3.close();
        System.out.println("Done!");
    }

    public static String getBucketACL(S3Client s3, String objectKey, String
 bucketName) {
        try {
            GetObjectAclRequest aclReq = GetObjectAclRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .build();

            GetObjectAclResponse aclRes = s3.getObjectAcl(aclReq);
            List<Grant> grants = aclRes.grants();
            String grantee = "";
            for (Grant grant : grants) {
                System.out.format("  %s: %s\n", grant.grantee().id(),
 grant.permission());
                grantee = grant.grantee().id();
            }

            return grantee;
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
}
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha as permissões de ACL.

```
import { GetBucketAclCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketAclCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_acl(self):
        """
        Get the ACL of the bucket.

        :return: The ACL of the bucket.
        """
        try:
            acl = self.bucket.Acl()
            logger.info(
                "Got ACL for bucket %s. Owner is %s.", self.bucket.name,
 acl.owner
            )
        except ClientError:
            logger.exception("Couldn't get ACL for bucket %s.", self.bucket.name)
            raise
        else:
            return acl
```

- Para obter detalhes da API, consulte a GetBucketAclReferência da API AWSSDK for Python (Boto3).

Obter a ACL de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como obter a lista de controle de acesso (ACL) de um objeto do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar listas de controle de acesso (ACLs)

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetObjectAclRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectAclOutcome outcome =
            s3_client.GetObjectAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetObjectAcl: "
```

```
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
   }
   else {
       Aws::Vector<Aws::S3::Model::Grant> grants =
               outcome.GetResult().GetGrants();

       for (auto it = grants.begin(); it != grants.end(); it++) {
           std::cout << "For object " << objectKey << ": "
                     << std::endl << std::endl;

           Aws::S3::Model::Grant grant = *it;
           Aws::S3::Model::Grantee grantee = grant.GetGrantee();

           if (grantee.TypeHasBeenSet()) {
               std::cout << "Type:          "
                         << GetGranteeTypeString(grantee.GetType()) <<
std::endl;
           }

           if (grantee.DisplayNameHasBeenSet()) {
               std::cout << "Display name:  "
                         << grantee.GetDisplayName() << std::endl;
           }

           if (grantee.EmailAddressHasBeenSet()) {
               std::cout << "Email address: "
                         << grantee.GetEmailAddress() << std::endl;
           }

           if (grantee.IDHasBeenSet()) {
               std::cout << "ID:            "
                         << grantee.GetID() << std::endl;
           }

           if (grantee.URIHasBeenSet()) {
               std::cout << "URI:           "
                         << grantee.GetURI() << std::endl;
           }

           std::cout << "Permission:    " <<
                     GetPermissionString(grant.GetPermission()) <<
                     std::endl << std::endl;
       }
```

```
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable
 string.
/*!
 \fn GetGranteeTypeString()
 \param type Type enumeration.
*/

Aws::String GetGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable
 string.
/*!
 \fn GetPermissionString()
 \param permission Permission enumeration.
*/

Aws::String GetPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can read this object's data and its metadata, "
                   "and read/write this object's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can read this object's data and its metadata";
        case Aws::S3::Model::Permission::READ_ACP:
```

```
            return "Can read this object's permissions";
            // case Aws::S3::Model::Permission::WRITE // Not applicable.
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this object's permissions";
        default:
            return "Permission unknown";
    }
}
```

- Para obter detalhes da API, consulte GetObjectAcla Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando recupera a lista de controle de acesso de um objeto em um bucket chamado `my-bucket`:

```
aws s3api get-object-acl --bucket my-bucket --key index.html
```

Saída:

```
{
    "Owner": {
        "DisplayName": "my-username",
        "ID": "7009a8971cd538e11f6b6606438875e7c86c5b672f46db45460ddcd087d36c32"
    },
    "Grants": [
        {
            "Grantee": {
                "DisplayName": "my-username",
                "ID":
 "7009a8971cd538e11f6b6606438875e7c86c5b672f46db45460ddcd087d36c32"
            },
            "Permission": "FULL_CONTROL"
        },
        {
            "Grantee": {
                "URI": "http://acs.amazonaws.com/groups/global/AllUsers"
            },
```

```
            "Permission": "READ"
        }
    ]
}
```

- Para obter detalhes da API, consulte GetObjectAclem Referência de AWS CLI Comandos.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getBucketACL(objectKey: String, bucketName: String) {
    val request = GetObjectAclRequest {
        bucket = bucketName
        key = objectKey
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.getObjectAcl(request)
        response.grants?.forEach { grant ->
            println("Grant permission is ${grant.permission}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetObjectAclreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def get_acl(self):
        """
        Gets the ACL of the object.

        :return: The ACL of the object.
        """
        try:
            acl = self.object.Acl()
            logger.info(
                "Got ACL for object %s owned by %s.",
                self.object.key,
                acl.owner["DisplayName"],
            )
        except ClientError:
            logger.exception("Couldn't get ACL for object %s.", self.object.key)
            raise
        else:
            return acl
```

- Para obter detalhes da API, consulte a GetObjectAclReferência da API AWSSDK for Python (Boto3).

Obter a região em que reside o bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como obter o local da região de um bucket do S3.

CLI

AWS CLI

O seguinte comando recupera a restrição de localização do bucket `my-bucket`, se houver uma restrição:

```
aws s3api get-bucket-location --bucket my-bucket
```

Saída:

```
{
    "LocationConstraint": "us-west-2"
}
```

- Para obter detalhes da API, consulte GetBucketLocationem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_buckets(strict: bool, client: &Client, region: &str) -> Result<(),
 Error> {
    let resp = client.list_buckets().send().await?;
    let buckets = resp.buckets();
    let num_buckets = buckets.len();

    let mut in_region = 0;

    for bucket in buckets {
        if strict {
            let r = client
                .get_bucket_location()
                .bucket(bucket.name().unwrap_or_default())
                .send()
                .await?;

            if r.location_constraint().unwrap().as_ref() == region {
                println!("{}", bucket.name().unwrap_or_default());
                in_region += 1;
            }
        } else {
            println!("{}", bucket.name().unwrap_or_default());
        }
    }

    println!();
    if strict {
        println!(
            "Found {} buckets in the {} region out of a total of {} buckets.",
            in_region, region, num_buckets
        );
    } else {
        println!("Found {} buckets in all regions.", num_buckets);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetBucketLocationreferência da API AWS SDK for Rust.

Obter a configuração de ciclo de vida de um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como obter a configuração de ciclo de vida de um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Returns a configuration object for the supplied bucket name.
        /// </summary>
        /// <param name="client">The S3 client object used to call
        /// the GetLifecycleConfigurationAsync method.</param>
        /// <param name="bucketName">The name of the S3 bucket for which a
        /// configuration will be created.</param>
        /// <returns>Returns a new LifecycleConfiguration object.</returns>
        public static async Task<LifecycleConfiguration>
RetrieveLifecycleConfigAsync(IAmazonS3 client, string bucketName)
        {
            var request = new GetLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
            };
            var response = await client.GetLifecycleConfigurationAsync(request);
            var configuration = response.Configuration;
            return configuration;
        }
```

- Para obter detalhes da API, consulte GetBucketLifecycleConfigurationa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando recupera a configuração do ciclo de vida do bucket `my-bucket`:

```
aws s3api get-bucket-lifecycle-configuration --bucket my-bucket
```

Saída:

```
{
    "Rules": [
        {
            "ID": "Move rotated logs to Glacier",
            "Prefix": "rotated/",
            "Status": "Enabled",
            "Transitions": [
                {
                    "Date": "2015-11-10T00:00:00.000Z",
                    "StorageClass": "GLACIER"
                }
            ]
        },
        {
            "Status": "Enabled",
            "Prefix": "",
            "NoncurrentVersionTransitions": [
                {
                    "NoncurrentDays": 0,
                    "StorageClass": "GLACIER"
                }
            ],
            "ID": "Move old versions to Glacier"
        }
    ]
}
```

- Para obter detalhes da API, consulte GetBucketLifecycleConfigurationem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_lifecycle_configuration(self):
        """
        Get the lifecycle configuration of the bucket.

        :return: The lifecycle rules of the specified bucket.
        """
        try:
            config = self.bucket.LifecycleConfiguration()
            logger.info(
                "Got lifecycle rules %s for bucket '%s'.",
                config.rules,
                self.bucket.name,
            )
        except:
            logger.exception(
                "Couldn't get lifecycle rules for bucket '%s'.", self.bucket.name
            )
            raise
        else:
```

```
            return config.rules
```

- Para obter detalhes da API, consulte a GetBucketLifecycleConfigurationReferência da API AWSSDK for Python (Boto3).

Obter a política de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como obter a política de um bucket do S3.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetBucketPolicy(const Aws::String &bucketName,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketPolicyOutcome outcome =
            s3_client.GetBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetBucketPolicy: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        Aws::StringStream policy_stream;
        Aws::String line;
```

```
        outcome.GetResult().GetPolicy() >> line;
        policy_stream << line;

        std::cout << "Retrieve the policy for bucket '" << bucketName << "':\n\n"
 <<
                  policy_stream.str() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando recupera política de bucket do bucket `my-bucket`:

```
aws s3api get-bucket-policy --bucket my-bucket
```

Saída:

```
{
    "Policy": "{\"Version\":\"2008-10-17\",\"Statement\":[{\"Sid\":\"\",\"Effect
\":\"Allow\",\"Principal\":\"*\",\"Action\":\"s3:GetObject\",\"Resource\":
\"arn:aws:s3:::my-bucket/*\"},{\"Sid\":\"\",\"Effect\":\"Deny\",\"Principal\":
\"*\",\"Action\":\"s3:GetObject\",\"Resource\":\"arn:aws:s3:::my-bucket/secret/*
\"}]}"
}
```

Obter e colocar uma política de bucket em vigor O exemplo a seguir mostra como fazer download de uma política do Amazon S3, fazer alterações no arquivo e usar `put-bucket-policy` para aplicar a política de bucket modificada. Para fazer o download de uma política de bucket em um arquivo, você pode executar:

```
aws s3api get-bucket-policy --bucket mybucket --query Policy --output text >
 policy.json
```

Em seguida, modifique o arquivo `policy.json` conforme necessário. Por fim, aplique essa política modificada ao bucket do S3 executando:

o arquivo `policy.json` conforme necessário. Por fim, aplique essa política modificada ao bucket do S3 executando:

conforme necessário. Por fim, aplique essa política modificada ao bucket do S3 executando:

```
aws s3api put-bucket-policy --bucket mybucket --policy file://policy.json
```

- Para obter detalhes da API, consulte GetBucketPolicyem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetBucketPolicyRequest;
import software.amazon.awssdk.services.s3.model.GetBucketPolicyResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class GetBucketPolicy {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to get the policy from.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Getting policy for bucket: \"%s\"\n\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        String polText = getPolicy(s3, bucketName);
        System.out.println("Policy Text: " + polText);
        s3.close();
    }

    public static String getPolicy(S3Client s3, String bucketName) {
        String policyText;
        System.out.format("Getting policy for bucket: \"%s\"\n\n", bucketName);
        GetBucketPolicyRequest policyReq = GetBucketPolicyRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            GetBucketPolicyResponse policyRes = s3.getBucketPolicy(policyReq);
            policyText = policyRes.policy();
            return policyText;

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
```

```
    }
}
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de bucket.

```
import { GetBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketPolicyCommand({
    Bucket: "test-bucket",
  });

  try {
    const { Policy } = await client.send(command);
    console.log(JSON.parse(Policy));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getPolicy(bucketName: String): String? {
    println("Getting policy for bucket $bucketName")

    val request = GetBucketPolicyRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val policyRes = s3.getBucketPolicy(request)
        return policyRes.policy
    }
}
```

- Para obter detalhes da API, consulte a GetBucketPolicyreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_policy(self):
        """
        Get the security policy of the bucket.

        :return: The security policy of the specified bucket, in JSON format.
        """
        try:
            policy = self.bucket.Policy()
            logger.info(
                "Got policy %s for bucket '%s'.", policy.policy, self.bucket.name
            )
        except ClientError:
            logger.exception("Couldn't get policy for bucket '%s'.",
self.bucket.name)
            raise
        else:
            return json.loads(policy.policy)
```

- Para obter detalhes da API, consulte a GetBucketPolicyReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy

  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object
 configured with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  # Gets the policy of a bucket.
  #
  # @return [Aws::S3::GetBucketPolicyOutput, nil] The current bucket policy.
  def get_policy
    policy = @bucket_policy.data.policy
    policy.respond_to?(:read) ? policy.read : policy
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get the policy for #{@bucket_policy.bucket.name}. Here's why:
 #{e.message}"
    nil
  end

end
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for Ruby da API.

Obter a configuração de site de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como obter a configuração de site de um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
                // Get the website configuration.
                GetBucketWebsiteRequest getRequest = new
GetBucketWebsiteRequest()
                {
                    BucketName = bucketName,
                };
                GetBucketWebsiteResponse getResponse = await
client.GetBucketWebsiteAsync(getRequest);
                Console.WriteLine($"Index document:
{getResponse.WebsiteConfiguration.IndexDocumentSuffix}");
                Console.WriteLine($"Error document:
{getResponse.WebsiteConfiguration.ErrorDocument}");
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetWebsiteConfig(const Aws::String &bucketName,
```

```
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketWebsiteOutcome outcome =
            s3_client.GetBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();

        std::cerr << "Error: GetBucketWebsite: "
                  << err.GetMessage() << std::endl;
    }
    else {
        Aws::S3::Model::GetBucketWebsiteResult websiteResult =
 outcome.GetResult();

        std::cout << "Success: GetBucketWebsite: "
                  << std::endl << std::endl
                  << "For bucket '" << bucketName << "':"
                  << std::endl
                  << "Index page : "
                  << websiteResult.GetIndexDocument().GetSuffix()
                  << std::endl
                  << "Error page: "
                  << websiteResult.GetErrorDocument().GetKey()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando recupera a configuração estática do site do bucket `my-bucket`:

```
aws s3api get-bucket-website --bucket my-bucket
```

Saída:

```
{
    "IndexDocument": {
        "Suffix": "index.html"
    },
    "ErrorDocument": {
        "Key": "error.html"
    }
}
```

- Para obter detalhes da API, consulte GetBucketWebsiteem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a configuração do site.

```
import { GetBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketWebsiteCommand({
    Bucket: "test-bucket",
```

```
  });

  try {
    const { ErrorDocument, IndexDocument } = await client.send(command);
    console.log(
      `Your bucket is set up to host a website. It has an error document:`,
      `${ErrorDocument.Key}, and an index document: ${IndexDocument.Suffix}.`,
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for JavaScript da API.

Listar buckets do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como listar buckets do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace ListBucketsExample
{
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example uses the AWS SDK for .NET to list the Amazon Simple Storage
```

```
    /// Service (Amazon S3) buckets belonging to the default account.
    /// </summary>
    public class ListBuckets
    {
        private static IAmazonS3 _s3Client;

        /// <summary>
        /// Get a list of the buckets owned by the default user.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <returns>The response from the ListingBuckets call that contains a
        /// list of the buckets owned by the default user.</returns>
        public static async Task<ListBucketsResponse> GetBuckets(IAmazonS3
 client)
        {
            return await client.ListBucketsAsync();
        }

        /// <summary>
        /// This method lists the name and creation date for the buckets in
        /// the passed List of S3 buckets.
        /// </summary>
        /// <param name="bucketList">A List of S3 bucket objects.</param>
        public static void DisplayBucketList(List<S3Bucket> bucketList)
        {
            bucketList
                .ForEach(b => Console.WriteLine($"Bucket name: {b.BucketName},
 created on: {b.CreationDate}"));
        }

        public static async Task Main()
        {
            // The client uses the AWS Region of the default user.
            // If the Region where the buckets were created is different,
            // pass the Region to the client constructor. For example:
            // _s3Client = new AmazonS3Client(RegionEndpoint.USEast1);
            _s3Client = new AmazonS3Client();
            var response = await GetBuckets(_s3Client);
            DisplayBucketList(response.Buckets);
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::ListBuckets(const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    auto outcome = client.ListBuckets();

    bool result = true;
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
        result = false;
    }
    else {
        std::cout << "Found " << outcome.GetResult().GetBuckets().size() << "
 buckets\n";
        for (auto &&b: outcome.GetResult().GetBuckets()) {
            std::cout << b.GetName() << std::endl;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando usa o comando `list-buckets` para exibir os nomes de todos os buckets do Amazon S3 (em todas as regiões):

```
aws s3api list-buckets --query "Buckets[].Name"
```

A opção de consulta filtra a saída de `list-buckets` até sobrar apenas os nomes dos buckets.

Para obter mais informações sobre buckets, consulte Working with Amazon S3 Buckets no Guia do desenvolvedor do Amazon S3.

- Para obter detalhes da API, consulte ListBucketsem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListBuckets lists the buckets in the current account.
```

```
func (basics BucketBasics) ListBuckets() ([]types.Bucket, error) {
 result, err := basics.S3Client.ListBuckets(context.TODO(),
 &s3.ListBucketsInput{})
 var buckets []types.Bucket
 if err != nil {
  log.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
 } else {
  buckets = result.Buckets
 }
 return buckets, err
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.Bucket;
import software.amazon.awssdk.services.s3.model.ListBucketsResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListBuckets {
```

```
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
            .region(region)
            .build();

        listAllBuckets(s3);

    }
    public static void listAllBuckets(S3Client s3) {
        ListBucketsResponse response = s3.listBuckets();
        List<Bucket> bucketList = response.buckets();
        for (Bucket bucket: bucketList) {
            System.out.println("Bucket name "+bucket.name());
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os buckets.

```
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new ListBucketsCommand({});

  try {
```

```
    const { Owner, Buckets } = await client.send(command);
    console.log(
      `${Owner.DisplayName} owns ${Buckets.length} bucket${
        Buckets.length === 1 ? "" : "s"
      }:`,
    );
    console.log(`${Buckets.map((b) => ` • ${b.Name}`).join("\n")}`);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name
```

```
    @staticmethod
    def list(s3_resource):
        """
        Get the buckets in all Regions for the current account.

        :param s3_resource: A Boto3 S3 resource. This is a high-level resource in
Boto3
                            that contains collections and factory methods to
create
                            other high-level S3 sub-resources.
        :return: The list of buckets.
        """
        try:
            buckets = list(s3_resource.buckets.all())
            logger.info("Got buckets: %s.", buckets)
        except ClientError:
            logger.exception("Couldn't get buckets.")
            raise
        else:
            return buckets
```

- Para obter detalhes da API, consulte a ListBucketsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 resource actions.
class BucketListWrapper
  attr_reader :s3_resource
```

```
  # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
  def initialize(s3_resource)
    @s3_resource = s3_resource
  end

  # Lists buckets for the current account.
  #
  # @param count [Integer] The maximum number of buckets to list.
  def list_buckets(count)
    puts "Found these buckets:"
    @s3_resource.buckets.each do |bucket|
      puts "\t#{bucket.name}"
      count -= 1
      break if count.zero?
    end
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't list buckets. Here's why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  wrapper = BucketListWrapper.new(Aws::S3::Resource.new)
  wrapper.list_buckets(25)
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_buckets(strict: bool, client: &Client, region: &str) -> Result<(),
 Error> {
    let resp = client.list_buckets().send().await?;
    let buckets = resp.buckets();
    let num_buckets = buckets.len();

    let mut in_region = 0;

    for bucket in buckets {
        if strict {
            let r = client
                .get_bucket_location()
                .bucket(bucket.name().unwrap_or_default())
                .send()
                .await?;

            if r.location_constraint().unwrap().as_ref() == region {
                println!("{}", bucket.name().unwrap_or_default());
                in_region += 1;
            }
        } else {
            println!("{}", bucket.name().unwrap_or_default());
        }
    }

    println!();
    if strict {
        println!(
            "Found {} buckets in the {} region out of a total of {} buckets.",
            in_region, region, num_buckets
        );
    } else {
        println!("Found {} buckets in all regions.", num_buckets);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListBucketsreferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Return an array containing information about every available bucket.
///
/// - Returns: An array of ``S3ClientTypes.Bucket`` objects describing
///   each bucket.
public func getAllBuckets() async throws -> [S3ClientTypes.Bucket] {
    let output = try await client.listBuckets(input: ListBucketsInput())

    guard let buckets = output.buckets else {
        return []
    }
    return buckets
}
```

- Para obter detalhes da API, consulte ListBucketsa referência da API AWS SDK for Swift.

Listar carregamentos fracionados em andamento para um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como listar uploads fracionados em andamento em um bucket do S3.

CLI

AWS CLI

O seguinte comando lista todos os uploads fracionados ativos do bucket `my-bucket`:

```
aws s3api list-multipart-uploads --bucket my-bucket
```

Saída:

```
{
    "Uploads": [
        {
            "Initiator": {
                "DisplayName": "username",
                "ID": "arn:aws:iam::0123456789012:user/username"
            },
            "Initiated": "2015-06-02T18:01:30.000Z",
            "UploadId":
 "dfRtDYU0WWCCcH43C3WFbkRONycyCpTJJvxu2i5GYkZljF.Yxwh6XG7WfS2vC4to6HiV6Yjlx.cph0gtNBtJ8P3
            "StorageClass": "STANDARD",
            "Key": "multipart/01",
            "Owner": {
                "DisplayName": "aws-account-name",
                "ID":
 "100719349fc3b6dcd7c820a124bf7aecd408092c3d7b51b38494939801fc248b"
            }
        }
    ],
    "CommonPrefixes": []
}
```

Os uploads fracionados em andamento incorrem em custos de armazenamento no Amazon S3. Conclua ou cancele um upload fracionado ativo para remover suas partes da conta.

- Para obter detalhes da API, consulte ListMultipartUploadsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListMultipartUploadsRequest;
import software.amazon.awssdk.services.s3.model.ListMultipartUploadsResponse;
import software.amazon.awssdk.services.s3.model.MultipartUpload;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class ListMultipartUploads {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The name of the Amazon S3 bucket where an in-
progress multipart upload is occurring.
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();
        listUploads(s3, bucketName);
        s3.close();
    }

    public static void listUploads(S3Client s3, String bucketName) {
        try {
            ListMultipartUploadsRequest listMultipartUploadsRequest =
 ListMultipartUploadsRequest.builder()
                    .bucket(bucketName)
                    .build();

            ListMultipartUploadsResponse response =
 s3.listMultipartUploads(listMultipartUploadsRequest);
            List<MultipartUpload> uploads = response.uploads();
            for (MultipartUpload upload : uploads) {
                System.out.println("Upload in progress: Key = \"" + upload.key()
 + "\", id = " + upload.uploadId());
            }

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMultipartUploadsa Referência AWS SDK for Java 2.x da API.

Listar a versão de objetos em um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como listar versões de objetos em um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Trabalhar com objetos versionados

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example lists the versions of the objects in a version enabled
/// Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class ListObjectVersions
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";

        // If the AWS Region where your bucket is defined is different from
        // the AWS Region where the Amazon S3 bucket is defined, pass the
constant
        // for the AWS Region to the client constructor like this:
        //      var client = new AmazonS3Client(RegionEndpoint.USWest2);
        IAmazonS3 client = new AmazonS3Client();
        await GetObjectListWithAllVersionsAsync(client, bucketName);
    }

    /// <summary>
    /// This method lists all versions of the objects within an Amazon S3
```

```
        /// version enabled bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// ListVersionsAsync.</param>
        /// <param name="bucketName">The name of the version enabled Amazon S3
 bucket
        /// for which you want to list the versions of the contained objects.</
param>
        public static async Task GetObjectListWithAllVersionsAsync(IAmazonS3
 client, string bucketName)
        {
            try
            {
                // When you instantiate the ListVersionRequest, you can
                // optionally specify a key name prefix in the request
                // if you want a list of object versions of a specific object.

                // For this example we set a small limit in MaxKeys to return
                // a small list of versions.
                ListVersionsRequest request = new ListVersionsRequest()
                {
                    BucketName = bucketName,
                    MaxKeys = 2,
                };

                do
                {
                    ListVersionsResponse response = await
 client.ListVersionsAsync(request);

                    // Process response.
                    foreach (S3ObjectVersion entry in response.Versions)
                    {
                        Console.WriteLine($"key: {entry.Key} size:
 {entry.Size}");
                    }

                    // If response is truncated, set the marker to get the next
                    // set of keys.
                    if (response.IsTruncated)
                    {
                        request.KeyMarker = response.NextKeyMarker;
                        request.VersionIdMarker = response.NextVersionIdMarker;
                    }
```

```
                    else
                    {
                        request = null;
                    }
                }
                while (request != null);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: '{ex.Message}'");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListObjectVersionsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O seguinte comando recupera as informações da versão de um objeto do bucket `my-bucket`:

```
aws s3api list-object-versions --bucket my-bucket --prefix index.html
```

Saída:

```
{
    "DeleteMarkers": [
        {
            "Owner": {
                "DisplayName": "my-username",
                "ID":
 "7009a8971cd660687538875e7c86c5b672fe116bd438f46db45460ddcd036c32"
            },
            "IsLatest": true,
            "VersionId": "B2VsEK5saUNNHKcOAJj7hIE86RozToyq",
            "Key": "index.html",
            "LastModified": "2015-11-10T00:57:03.000Z"
        },
```

```
        {
            "Owner": {
                "DisplayName": "my-username",
                "ID":
"7009a8971cd660687538875e7c86c5b672fe116bd438f46db45460ddcd036c32"
            },
            "IsLatest": false,
            "VersionId": ".FLQEZscLIcfxSq.jsFJ.szUkmng2Yw6",
            "Key": "index.html",
            "LastModified": "2015-11-09T23:32:20.000Z"
        }
    ],
    "Versions": [
        {
            "LastModified": "2015-11-10T00:20:11.000Z",
            "VersionId": "Rb_l2T8UHDkFEwCgJjhlgPOZC0qJ.vpD",
            "ETag": "\"0622528de826c0df5db1258a23b80be5\"",
            "StorageClass": "STANDARD",
            "Key": "index.html",
            "Owner": {
                "DisplayName": "my-username",
                "ID":
"7009a8971cd660687538875e7c86c5b672fe116bd438f46db45460ddcd036c32"
            },
            "IsLatest": false,
            "Size": 38
        },
        {
            "LastModified": "2015-11-09T23:26:41.000Z",
            "VersionId": "rasWWGpgk9E4s0LyTJgusGeRQKLVIAFf",
            "ETag": "\"06225825b8028de826c0df5db1a23be5\"",
            "StorageClass": "STANDARD",
            "Key": "index.html",
            "Owner": {
                "DisplayName": "my-username",
                "ID":
"7009a8971cd660687538875e7c86c5b672fe116bd438f46db45460ddcd036c32"
            },
            "IsLatest": false,
            "Size": 38
        },
        {
            "LastModified": "2015-11-09T22:50:50.000Z",
            "VersionId": "null",
```

```
            "ETag": "\"d1f45267a863c8392e07d24dd592f1b9\"",
            "StorageClass": "STANDARD",
            "Key": "index.html",
            "Owner": {
                "DisplayName": "my-username",
                "ID":
 "7009a8971cd660687538875e7c86c5b672fe116bd438f46db45460ddcd036c32"
            },
            "IsLatest": false,
            "Size": 533823
        }
    ]
}
```

- Para obter detalhes da API, consulte ListObjectVersionsem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_versions(client: &Client, bucket: &str) -> Result<(), Error> {
    let resp = client.list_object_versions().bucket(bucket).send().await?;

    for version in resp.versions() {
        println!("{}", version.key().unwrap_or_default());
        println!("  version ID: {}", version.version_id().unwrap_or_default());
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListObjectVersionsreferência da API AWS SDK for Rust.

Listar objetos em um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como listar objetos em um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de buckets e objetos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to list the objects in an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket for which to list
        /// the contents.</param>
        /// <returns>A boolean value indicating the success or failure of the
        /// copy operation.</returns>
        public static async Task<bool> ListBucketContentsAsync(IAmazonS3 client,
string bucketName)
        {
            try
            {
                var request = new ListObjectsV2Request
                {
                    BucketName = bucketName,
                    MaxKeys = 5,
```

```
                };

                Console.WriteLine("--------------------------------------");
                Console.WriteLine($"Listing the contents of {bucketName}:");
                Console.WriteLine("--------------------------------------");

                ListObjectsV2Response response;

                do
                {
                    response = await client.ListObjectsV2Async(request);

                    response.S3Objects
                        .ForEach(obj => Console.WriteLine($"{obj.Key,-35}
{obj.LastModified.ToShortDateString(),10}{obj.Size,10}"));

                    // If the response is truncated, set the request
 ContinuationToken
                    // from the NextContinuationToken property of the response.
                    request.ContinuationToken = response.NextContinuationToken;
                }
                while (response.IsTruncated);

                return true;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error encountered on server.
 Message:'{ex.Message}' getting list of objects.");
                return false;
            }
        }
```

Liste objetos com um paginador.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
```

```
    /// The following example lists objects in an Amazon Simple Storage
    /// Service (Amazon S3) bucket.
    /// </summary>
    public class ListObjectsPaginator
    {
        private const string BucketName = "doc-example-bucket";

        public static async Task Main()
        {
            IAmazonS3 s3Client = new AmazonS3Client();

            Console.WriteLine($"Listing the objects contained in {BucketName}:
\n");
            await ListingObjectsAsync(s3Client, BucketName);
        }

        /// <summary>
        /// This method uses a paginator to retrieve the list of objects in an
        /// an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the S3 bucket whose objects
        /// you want to list.</param>
        public static async Task ListingObjectsAsync(IAmazonS3 client, string
 bucketName)
        {
            var listObjectsV2Paginator = client.Paginators.ListObjectsV2(new
 ListObjectsV2Request
            {
                BucketName = bucketName,
            });

            await foreach (var response in listObjectsV2Paginator.Responses)
            {
                Console.WriteLine($"HttpStatusCode: {response.HttpStatusCode}");
                Console.WriteLine($"Number of Keys: {response.KeyCount}");
                foreach (var entry in response.S3Objects)
                {
                    Console.WriteLine($"Key = {entry.Key} Size = {entry.Size}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function list_items_in_bucket
#
# This function displays a list of the files in the bucket with each file's
# size. The function uses the --query parameter to retrieve only the key and
# size fields from the Contents collection.
#
# Parameters:
#       $1 - The name of the bucket.
#
# Returns:
#       The list of files in text format.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function list_items_in_bucket() {
```

```
  local bucket_name=$1
  local response

  response=$(aws s3api list-objects \
    --bucket "$bucket_name" \
    --output text \
    --query 'Contents[].{Key: Key, Size: Size}')

  # shellcheck disable=SC2181
  if [[ ${?} -eq 0 ]]; then
    echo "$response"
  else
    errecho "ERROR: AWS reports s3api list-objects operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::ListObjects(const Aws::String &bucketName,
                             const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::ListObjectsRequest request;
    request.WithBucket(bucketName);

    auto outcome = s3_client.ListObjects(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: ListObjects: " <<
```

```
                    outcome.GetError().GetMessage() << std::endl;
    }
    else {
        Aws::Vector<Aws::S3::Model::Object> objects =
                outcome.GetResult().GetContents();

        for (Aws::S3::Model::Object &object: objects) {
            std::cout << object.GetKey() << std::endl;
        }
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte exemplo usa o comando `list-objects` para exibir os nomes de todos os objetos presentes no bucket especificado:

```
aws s3api list-objects --bucket text-content --query 'Contents[].{Key: Key, Size:
 Size}'
```

O exemplo usa o argumento `--query` para filtrar a saída de `list-objects` até encontrar o valor e o tamanho da chave de cada objeto

Para obter mais informações sobre objetos, consulte Working with Amazon S3 Buckets no Guia do desenvolvedor do Amazon S3.

- Para obter detalhes da API, consulte ListObjectsV2 na Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListObjects lists the objects in a bucket.
func (basics BucketBasics) ListObjects(bucketName string) ([]types.Object, error)
 {
 result, err := basics.S3Client.ListObjectsV2(context.TODO(),
 &s3.ListObjectsV2Input{
  Bucket: aws.String(bucketName),
 })
 var contents []types.Object
 if err != nil {
  log.Printf("Couldn't list objects in bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
  contents = result.Contents
 }
 return contents, err
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListObjectsRequest;
import software.amazon.awssdk.services.s3.model.ListObjectsResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.S3Object;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class ListObjects {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The Amazon S3 bucket from which objects are
 read.\s
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsRequest listObjects = ListObjectsRequest
                    .builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.print("\n The name of the key is " + myValue.key());
                System.out.print("\n The object is " + calKb(myValue.size()) + "
 KBs");
                System.out.print("\n The owner is " + myValue.owner());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // convert bytes to kbs.
    private static long calKb(Long val) {
        return val / 1024;
    }
}
```

Liste objetos usando paginação.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Request;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.paginators.ListObjectsV2Iterable;

public class ListObjectsPaginated {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The Amazon S3 bucket from which objects are
 read.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsV2Request listReq = ListObjectsV2Request.builder()
                    .bucket(bucketName)
                    .maxKeys(1)
                    .build();

            ListObjectsV2Iterable listRes = s3.listObjectsV2Paginator(listReq);
            listRes.stream()
```

```
                    .flatMap(r -> r.contents().stream())
                    .forEach(content -> System.out.println(" Key: " +
 content.key() + " size = " + content.size()));

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste todos os objetos no bucket. Se houver mais de um objeto, IsTruncated NextContinuationToken ele será usado para iterar a lista completa.

```
import {
  S3Client,
  // This command supersedes the ListObjectsCommand and is the recommended way to
 list objects.
  ListObjectsV2Command,
} from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new ListObjectsV2Command({
    Bucket: "my-bucket",
    // The default and maximum number of keys returned is 1000. This limits it to
```

```
    // one for demonstration purposes.
    MaxKeys: 1,
  });

  try {
    let isTruncated = true;

    console.log("Your bucket contains the following objects:\n");
    let contents = "";

    while (isTruncated) {
      const { Contents, IsTruncated, NextContinuationToken } =
        await client.send(command);
      const contentsList = Contents.map((c) => ` • ${c.Key}`).join("\n");
      contents += contentsList + "\n";
      isTruncated = IsTruncated;
      command.input.ContinuationToken = NextContinuationToken;
    }
    console.log(contents);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBucketObjects(bucketName: String) {
    val request = ListObjectsRequest {
        bucket = bucketName
```

```
    }

    S3Client { region = "us-east-1" }.use { s3 ->

        val response = s3.listObjects(request)
        response.contents?.forEach { myObject ->
            println("The name of the key is ${myObject.key}")
            println("The object is ${myObject.size?.let { calKb(it) }} KBs")
            println("The owner is ${myObject.owner}")
        }
    }
}

private fun calKb(intValue: Long): Long {
    return intValue / 1024
}
```

- Para obter detalhes da API, consulte ListObjectsV2 no AWSSDK para referência da API Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste objetos em um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $contents = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            echo "The contents of your bucket are: \n";
            foreach ($contents['Contents'] as $content) {
```

```
                echo $content['Key'] . "\n";
            }
        } catch (Exception $exception) {
            echo "Failed to list objects in $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with listing objects before continuing.");
        }
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def list(bucket, prefix=None):
        """
        Lists the objects in a bucket, optionally filtered by a prefix.

        :param bucket: The bucket to query. This is a Boto3 Bucket resource.
```

```
        :param prefix: When specified, only objects that start with this prefix
 are listed.
        :return: The list of objects.
        """
        try:
            if not prefix:
                objects = list(bucket.objects.all())
            else:
                objects = list(bucket.objects.filter(Prefix=prefix))
            logger.info(
                "Got objects %s from bucket '%s'", [o.key for o in objects],
 bucket.name
            )
        except ClientError:
            logger.exception("Couldn't get objects for bucket '%s'.",
 bucket.name)
            raise
        else:
            return objects
```

- Para obter detalhes da API, consulte Referência da API ListObjectsV2 no AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket actions.
class BucketListObjectsWrapper
  attr_reader :bucket
```

```
  # @param bucket [Aws::S3::Bucket] An existing Amazon S3 bucket.
  def initialize(bucket)
    @bucket = bucket
  end

  # Lists object in a bucket.
  #
  # @param max_objects [Integer] The maximum number of objects to list.
  # @return [Integer] The number of objects listed.
  def list_objects(max_objects)
    count = 0
    puts "The objects in #{@bucket.name} are:"
    @bucket.objects.each do |obj|
      puts "\t#{obj.key}"
      count += 1
      break if count == max_objects
    end
    count
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't list objects in bucket #{bucket.name}. Here's why:
 #{e.message}"
    0
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"

  wrapper = BucketListObjectsWrapper.new(Aws::S3::Bucket.new(bucket_name))
  count = wrapper.list_objects(25)
  puts "Listed #{count} objects."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_objects(client: &Client, bucket: &str) -> Result<(), Error> {
    let mut response = client
        .list_objects_v2()
        .bucket(bucket.to_owned())
        .max_keys(10) // In this example, go 10 at a time.
        .into_paginator()
        .send();

    while let Some(result) = response.next().await {
        match result {
            Ok(output) => {
                for object in output.contents() {
                    println!(" - {}", object.key().unwrap_or("Unknown"));
                }
            }
            Err(err) => {
                eprintln!("{err:?}")
            }
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API AWSSDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_s3->listobjectsv2(         " oo_result is returned for
testing purposes. "
         iv_bucket = iv_bucket_name
       ).
       MESSAGE 'Retrieved list of objects in S3 bucket.' TYPE 'I'.
     CATCH /aws1/cx_s3_nosuchbucket.
       MESSAGE 'Bucket does not exist.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API ABAP do AWS SDK para SAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func listBucketFiles(bucket: String) async throws -> [String] {
        let input = ListObjectsV2Input(
            bucket: bucket
        )
        let output = try await client.listObjectsV2(input: input)
        var names: [String] = []

        guard let objList = output.contents else {
            return []
        }

        for obj in objList {
            if let objName = obj.key {
                names.append(objName)
            }
        }

        return names
    }
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API AWS SDK for Swift.

Restaurar uma cópia arquivada de um objeto em um bucket do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como restaurar uma cópia arquivada de um objeto em um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to restore an archived object in an Amazon
    /// Simple Storage Service (Amazon S3) bucket.
    /// </summary>
    public class RestoreArchivedObject
    {
        public static void Main()
        {
            string bucketName = "doc-example-bucket";
            string objectKey = "archived-object.txt";

            // Specify your bucket region (an example region is shown).
            RegionEndpoint bucketRegion = RegionEndpoint.USWest2;

            IAmazonS3 client = new AmazonS3Client(bucketRegion);
            RestoreObjectAsync(client, bucketName, objectKey).Wait();
        }

        /// <summary>
        /// This method restores an archived object from an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// RestoreObjectAsync.</param>
        /// <param name="bucketName">A string representing the name of the
        /// bucket where the object was located before it was archived.</param>
        /// <param name="objectKey">A string representing the name of the
        /// archived object to restore.</param>
        public static async Task RestoreObjectAsync(IAmazonS3 client, string
bucketName, string objectKey)
        {
            try
            {
                var restoreRequest = new RestoreObjectRequest
                {
                    BucketName = bucketName,
                    Key = objectKey,
```

```
                    Days = 2,
                };
                RestoreObjectResponse response = await
client.RestoreObjectAsync(restoreRequest);

                // Check the status of the restoration.
                await CheckRestorationStatusAsync(client, bucketName, objectKey);
            }
            catch (AmazonS3Exception amazonS3Exception)
            {
                Console.WriteLine($"Error: {amazonS3Exception.Message}");
            }
        }

        /// <summary>
        /// This method retrieves the status of the object's restoration.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// GetObjectMetadataAsync.</param>
        /// <param name="bucketName">A string representing the name of the Amazon
        /// S3 bucket which contains the archived object.</param>
        /// <param name="objectKey">A string representing the name of the
        /// archived object you want to restore.</param>
        public static async Task CheckRestorationStatusAsync(IAmazonS3 client,
string bucketName, string objectKey)
        {
            GetObjectMetadataRequest metadataRequest = new
GetObjectMetadataRequest()
            {
                BucketName = bucketName,
                Key = objectKey,
            };

            GetObjectMetadataResponse response = await
client.GetObjectMetadataAsync(metadataRequest);

            var restStatus = response.RestoreInProgress ? "in-progress" :
"finished or failed";
            Console.WriteLine($"Restoration status: {restStatus}");
        }
    }
```

- Para obter detalhes da API, consulte RestoreObjecta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar uma solicitação de restauração para um objeto

O exemplo de `restore-object` a seguir restaura o objeto Amazon S3 Glacier especificado do bucket `my-glacier-bucket` por 10 dias.

```
aws s3api restore-object \
    --bucket my-glacier-bucket \
    --key doc1.rtf \
    --restore-request Days=10
```

Este comando não produz saída.

- Para obter detalhes da API, consulte RestoreObjectem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.RestoreRequest;
import software.amazon.awssdk.services.s3.model.GlacierJobParameters;
import software.amazon.awssdk.services.s3.model.RestoreObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.Tier;
```

```
/*
 *  For more information about restoring an object, see "Restoring an archived
 object" at
 *  https://docs.aws.amazon.com/AmazonS3/latest/userguide/restoring-objects.html
 *
 *  Before running this Java V2 code example, set up your development
 environment, including your credentials.
 *
 *  For more information, see the following documentation topic:
 *
 *  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class RestoreObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <expectedBucketOwner>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name of an object with a Storage class
 value of Glacier.\s
                    expectedBucketOwner - The account that owns the bucket (you
 can obtain this value from the AWS Management Console).\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String expectedBucketOwner = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        restoreS3Object(s3, bucketName, keyName, expectedBucketOwner);
        s3.close();
    }
```

```
    public static void restoreS3Object(S3Client s3, String bucketName, String
 keyName, String expectedBucketOwner) {
        try {
            RestoreRequest restoreRequest = RestoreRequest.builder()
                    .days(10)

 .glacierJobParameters(GlacierJobParameters.builder().tier(Tier.STANDARD).build())
                    .build();

            RestoreObjectRequest objectRequest = RestoreObjectRequest.builder()
                    .expectedBucketOwner(expectedBucketOwner)
                    .bucket(bucketName)
                    .key(keyName)
                    .restoreRequest(restoreRequest)
                    .build();

            s3.restoreObject(objectRequest);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte RestoreObjecta Referência AWS SDK for Java 2.x da API.

Definir uma nova ACL para um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar listas de controle de acesso (ACLs)

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Creates an Amazon S3 bucket with an ACL to control access to the
        /// bucket and the objects stored in it.
        /// </summary>
        /// <param name="client">The initialized client object used to create
        /// an Amazon S3 bucket, with an ACL applied to the bucket.
        /// </param>
        /// <param name="region">The AWS Region where the bucket will be
created.</param>
        /// <param name="newBucketName">The name of the bucket to create.</param>
        /// <returns>A boolean value indicating success or failure.</returns>
        public static async Task<bool> CreateBucketUseCannedACLAsync(IAmazonS3
client, S3Region region, string newBucketName)
        {
            try
            {
                // Create a new Amazon S3 bucket with Canned ACL.
                var putBucketRequest = new PutBucketRequest()
                {
                    BucketName = newBucketName,
                    BucketRegion = region,
                    CannedACL = S3CannedACL.LogDeliveryWrite,
                };

                PutBucketResponse putBucketResponse = await
client.PutBucketAsync(putBucketRequest);

                return putBucketResponse.HttpStatusCode ==
System.Net.HttpStatusCode.OK;
            }
            catch (AmazonS3Exception ex)
```

```
            {
                Console.WriteLine($"Amazon S3 error: {ex.Message}");
            }

            return false;
        }
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutBucketAcl(const Aws::String &bucketName,
                              const Aws::String &ownerID,
                              const Aws::String &granteePermission,
                              const Aws::String &granteeType,
                              const Aws::String &granteeID,
                              const Aws::Client::ClientConfiguration
 &clientConfig,
                              const Aws::String &granteeDisplayName,
                              const Aws::String &granteeEmailAddress,
                              const Aws::String &granteeURI) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(SetGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }
```

```
    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeDisplayName.empty()) {
        grantee.SetDisplayName(granteeDisplayName);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(SetGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutBucketAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);

    Aws::S3::Model::PutBucketAclOutcome outcome =
            s3_client.PutBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &error = outcome.GetError();

        std::cerr << "Error: PutBucketAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully added an ACL to the bucket '" << bucketName
                  << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which converts a human-readable string to a built-in type
 enumeration.
/*!
 \sa SetGranteePermission()
 \param access Human readable string.
*/

Aws::S3::Model::Permission SetGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type
 enumeration.
/*!
 \sa SetGranteeType()
 \param type Human readable string.
*/

Aws::S3::Model::Type SetGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for C++ da API.

CLI

AWS CLI

Este exemplo concede `full control` para dois usuários da AWS (user1@example.com e user2@example.com) e permissão `read` para todos:

```
aws s3api put-bucket-acl --bucket MyBucket --grant-full-control
 emailaddress=user1@example.com,emailaddress=user2@example.com --grant-read
 uri=http://acs.amazonaws.com/groups/global/AllUsers
```

Consulte http://docs.aws.amazon.com/AmazonS3/latest/API/RESTBucketPUTacl.html para obter detalhes sobre ACLs personalizadas (os comandos da ACL s3api, como `put-bucket-acl`, usam a mesma notação abreviada de argumentos).

- Para obter detalhes da API, consulte PutBucketAclem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import java.util.ArrayList;
import java.util.List;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.s3.model.Permission;
import software.amazon.awssdk.services.s3.model.Grant;
import software.amazon.awssdk.services.s3.model.AccessControlPolicy;
import software.amazon.awssdk.services.s3.model.Type;
import software.amazon.awssdk.services.s3.model.PutBucketAclRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SetAcl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <bucketName> <id>\s

                Where:
                  bucketName - The Amazon S3 bucket to grant permissions on.\s
                  id - The ID of the owner of this bucket (you can get this value
 from the AWS Management Console).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String id = args[1];
        System.out.format("Setting access \n");
        System.out.println(" in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setBucketAcl(s3, bucketName, id);
        System.out.println("Done!");
        s3.close();
    }

    public static void setBucketAcl(S3Client s3, String bucketName, String id) {
        try {
            Grant ownerGrant = Grant.builder()
                    .grantee(builder -> builder.id(id)
                            .type(Type.CANONICAL_USER))
```

```
                .permission(Permission.FULL_CONTROL)
                .build();

            List<Grant> grantList2 = new ArrayList<>();
            grantList2.add(ownerGrant);

            AccessControlPolicy acl = AccessControlPolicy.builder()
                .owner(builder -> builder.id(id))
                .grants(grantList2)
                .build();

            PutBucketAclRequest putAclReq = PutBucketAclRequest.builder()
                .bucket(bucketName)
                .accessControlPolicy(acl)
                .build();

            s3.putBucketAcl(putAclReq);

        } catch (S3Exception e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Coloque a ACL do bucket.

```
import {
```

```
  PutBucketAclCommand,
  GetBucketAclCommand,
  S3Client,
} from "@aws-sdk/client-s3";

const client = new S3Client({});

// Most Amazon S3 use cases don't require the use of access control lists (ACLs).
// We recommend that you disable ACLs, except in unusual circumstances where
// you need to control access for each object individually.
// Consider a policy instead. For more information see https://
docs.aws.amazon.com/AmazonS3/latest/userguide/bucket-policies.html.
export const main = async () => {
  // Grant a user READ access to a bucket.
  const command = new PutBucketAclCommand({
    Bucket: "test-bucket",
    AccessControlPolicy: {
      Grants: [
        {
          Grantee: {
            // The canonical ID of the user. This ID is an obfuscated form of
 your AWS account number.
            // It's unique to Amazon S3 and can't be found elsewhere.
            // For more information, see https://docs.aws.amazon.com/AmazonS3/
latest/userguide/finding-canonical-user-id.html.
            ID: "canonical-id-1",
            Type: "CanonicalUser",
          },
          // One of FULL_CONTROL | READ | WRITE | READ_ACP | WRITE_ACP
          // https://docs.aws.amazon.com/AmazonS3/latest/API/
API_Grant.html#AmazonS3-Type-Grant-Permission
          Permission: "FULL_CONTROL",
        },
      ],
      Owner: {
        ID: "canonical-id-2",
      },
    },
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
```

```
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setBucketAcl(bucketName: String, idVal: String) {
    val myGrant = Grantee {
        id = idVal
        type = Type.CanonicalUser
    }

    val ownerGrant = Grant {
        grantee = myGrant
        permission = Permission.FullControl
    }

    val grantList = mutableListOf<Grant>()
    grantList.add(ownerGrant)

    val ownerOb = Owner {
        id = idVal
    }

    val acl = AccessControlPolicy {
        owner = ownerOb
        grants = grantList
```

```
    }

    val request = PutBucketAclRequest {
        bucket = bucketName
        accessControlPolicy = acl
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.putBucketAcl(request)
        println("An ACL was successfully set on $bucketName")
    }
}
```

- Para obter detalhes da API, consulte a PutBucketAclreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def grant_log_delivery_access(self):
        """
        Grant the AWS Log Delivery group write access to the bucket so that
```

```
        Amazon S3 can deliver access logs to the bucket. This is the only
recommended
        use of an S3 bucket ACL.
        """
        try:
            acl = self.bucket.Acl()
            # Putting an ACL overwrites the existing ACL. If you want to preserve
            # existing grants, append new grants to the list of existing grants.
            grants = acl.grants if acl.grants else []
            grants.append(
                {
                    "Grantee": {
                        "Type": "Group",
                        "URI": "http://acs.amazonaws.com/groups/s3/LogDelivery",
                    },
                    "Permission": "WRITE",
                }
            )
            acl.put(AccessControlPolicy={"Grants": grants, "Owner": acl.owner})
            logger.info("Granted log delivery access to bucket '%s'",
self.bucket.name)
        except ClientError:
            logger.exception("Couldn't add ACL to bucket '%s'.",
self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketAclReferência da API AWSSDK for Python (Boto3).

Definir a ACL de um objeto do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como definir a lista de controle de acesso (ACL) de um objeto do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Gerenciar listas de controle de acesso (ACLs)

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::String &ownerID,
                              const Aws::String &granteePermission,
                              const Aws::String &granteeType,
                              const Aws::String &granteeID,
                              const Aws::Client::ClientConfiguration
 &clientConfig,
                              const Aws::String &granteeDisplayName,
                              const Aws::String &granteeEmailAddress,
                              const Aws::String &granteeURI) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(SetGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeDisplayName.empty()) {
        grantee.SetDisplayName(granteeDisplayName);
    }

    if (!granteeURI.empty()) {
```

```
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(SetGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutObjectAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::PutObjectAclOutcome outcome =
            s3_client.PutObjectAcl(request);

    if (!outcome.IsSuccess()) {
        auto error = outcome.GetError();
        std::cerr << "Error: PutObjectAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully added an ACL to the object '" << objectKey
                  << "' in the bucket '" << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which converts a human-readable string to a built-in type
 enumeration.
/*!
 \sa SetGranteePermission()
 \param access Human readable string.
*/

Aws::S3::Model::Permission SetGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
```

```
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type
 enumeration.
/*!
 \sa SetGranteeType()
 \param type Human readable string.
*/

Aws::S3::Model::Type SetGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- Para obter detalhes da API, consulte PutObjectAcla Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte comando concede `full control` para dois usuários da AWS (user1@example.com e user2@example.com) e permissão `read` para todos:

```
aws s3api put-object-acl --bucket MyBucket --key file.txt --grant-full-control
 emailaddress=user1@example.com,emailaddress=user2@example.com --grant-read
 uri=http://acs.amazonaws.com/groups/global/AllUsers
```

Consulte http://docs.aws.amazon.com/AmazonS3/latest/API/RESTBucketPUTacl.html para obter detalhes sobre ACLs personalizadas (os comandos da ACL s3api, como `put-object-acl`, usam a mesma notação abreviada de argumentos).

- Para obter detalhes da API, consulte PutObjectAclem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def put_acl(self, email):
        """
        Applies an ACL to the object that grants read access to an AWS user
 identified
        by email address.

        :param email: The email address of the user to grant access.
        """
```

```
        try:
            acl = self.object.Acl()
            # Putting an ACL overwrites the existing ACL, so append new grants
            # if you want to preserve existing grants.
            grants = acl.grants if acl.grants else []
            grants.append(
                {
                    "Grantee": {"Type": "AmazonCustomerByEmail", "EmailAddress":
email},
                    "Permission": "READ",
                }
            )
            acl.put(AccessControlPolicy={"Grants": grants, "Owner": acl.owner})
            logger.info("Granted read access to %s.", email)
        except ClientError:
            logger.exception("Couldn't add ACL to object '%s'.", self.object.key)
            raise
```

- Para obter detalhes da API, consulte a PutObjectAclReferência da API AWSSDK for Python (Boto3).

Definir a configuração de site de um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como definir a configuração de site de um bucket do S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
                // Put the website configuration.
                PutBucketWebsiteRequest putRequest = new
PutBucketWebsiteRequest()
                {
```

```
                    BucketName = bucketName,
                    WebsiteConfiguration = new WebsiteConfiguration()
                    {
                        IndexDocumentSuffix = indexDocumentSuffix,
                        ErrorDocument = errorDocument,
                    },
                };
                PutBucketWebsiteResponse response = await
 client.PutBucketWebsiteAsync(putRequest);
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::String &indexPage, const Aws::String
 &errorPage,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::IndexDocument indexDocument;
    indexDocument.SetSuffix(indexPage);

    Aws::S3::Model::ErrorDocument errorDocument;
    errorDocument.SetKey(errorPage);

    Aws::S3::Model::WebsiteConfiguration websiteConfiguration;
    websiteConfiguration.SetIndexDocument(indexDocument);
    websiteConfiguration.SetErrorDocument(errorDocument);
```

```
    Aws::S3::Model::PutBucketWebsiteRequest request;
    request.SetBucket(bucketName);
    request.SetWebsiteConfiguration(websiteConfiguration);

    Aws::S3::Model::PutBucketWebsiteOutcome outcome =
            client.PutBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketWebsite: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Success: Set website configuration for bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Aplica uma configuração de site estático ao bucket `my-bucket`:

```
aws s3api put-bucket-website --bucket my-bucket --website-configuration file://
website.json
```

O arquivo `website.json` é um documento JSON na pasta atual que especifica páginas de índice e erro para o site:

```
{
    "IndexDocument": {
        "Suffix": "index.html"
    },
    "ErrorDocument": {
        "Key": "error.html"
```

```
    }
}
```

- Para obter detalhes da API, consulte PutBucketWebsiteem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.IndexDocument;
import software.amazon.awssdk.services.s3.model.PutBucketWebsiteRequest;
import software.amazon.awssdk.services.s3.model.WebsiteConfiguration;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class SetWebsiteConfiguration {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucketName> [indexdoc]\s

                Where:
```

```
                   bucketName   - The Amazon S3 bucket to set the website
configuration on.\s
                   indexdoc - The index document, ex. 'index.html'
                              If not specified, 'index.html' will be set.
               """;

       if (args.length != 1) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucketName = args[0];
       String indexDoc = "index.html";
       Region region = Region.US_EAST_1;
       S3Client s3 = S3Client.builder()
               .region(region)
               .build();

       setWebsiteConfig(s3, bucketName, indexDoc);
       s3.close();
   }

   public static void setWebsiteConfig(S3Client s3, String bucketName, String
indexDoc) {
       try {
           WebsiteConfiguration websiteConfig = WebsiteConfiguration.builder()

.indexDocument(IndexDocument.builder().suffix(indexDoc).build())
                   .build();

           PutBucketWebsiteRequest pubWebsiteReq =
PutBucketWebsiteRequest.builder()
                   .bucket(bucketName)
                   .websiteConfiguration(websiteConfig)
                   .build();

           s3.putBucketWebsite(pubWebsiteReq);
           System.out.println("The call was successful");

       } catch (S3Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

```
}
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina a configuração do site.

```
import { PutBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Set up a bucket as a static website.
// The bucket needs to be publicly accessible.
export const main = async () => {
  const command = new PutBucketWebsiteCommand({
    Bucket: "test-bucket",
    WebsiteConfiguration: {
      ErrorDocument: {
        // The object key name to use when a 4XX class error occurs.
        Key: "error.html",
      },
      IndexDocument: {
        // A suffix that is appended to a request that is for a directory.
        Suffix: "index.html",
      },
    },
  });

  try {
    const response = await client.send(command);
    console.log(response);
```

```
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket website actions.
class BucketWebsiteWrapper
  attr_reader :bucket_website

  # @param bucket_website [Aws::S3::BucketWebsite] A bucket website object
 configured with an existing bucket.
  def initialize(bucket_website)
    @bucket_website = bucket_website
  end

  # Sets a bucket as a static website.
  #
  # @param index_document [String] The name of the index document for the
 website.
  # @param error_document [String] The name of the error document to show for 4XX
 errors.
  # @return [Boolean] True when the bucket is configured as a website; otherwise,
 false.
```

```
  def set_website(index_document, error_document)
    @bucket_website.put(
      website_configuration: {
        index_document: { suffix: index_document },
        error_document: { key: error_document }
      }
    )
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't configure #{@bucket_website.bucket.name} as a website. Here's
 why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  index_document = "index.html"
  error_document = "404.html"

  wrapper = BucketWebsiteWrapper.new(Aws::S3::BucketWebsite.new(bucket_name))
  return unless wrapper.set_website(index_document, error_document)

  puts "Successfully configured bucket #{bucket_name} as a static website."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for Ruby da API.

Exemplos de abordagens para testes de unidade e integração com SDK da AWS

O exemplo de código a seguir mostra exemplos de técnicas de práticas recomendadas ao escrever testes de unidade e de integração usando AWS SDK.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cargo.toml para exemplos de testes.

```
[package]
name = "testing-examples"
version = "0.1.0"
authors = [
  "John Disanti <jdisanti@amazon.com>",
  "Doug Schwartz <dougsch@amazon.com>",
]
edition = "2021"

# snippet-start:[testing.rust.Cargo.toml]
[dependencies]
async-trait = "0.1.51"
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-credential-types = { version = "1.0.1", features = [ "hardcoded-
credentials", ] }
aws-sdk-s3 = { version = "1.4.0" }
aws-smithy-types = { version = "1.0.1" }
aws-smithy-runtime = { version = "1.0.1", features = ["test-util"] }
aws-smithy-runtime-api = { version = "1.0.1", features = ["test-util"] }
aws-types = { version = "1.0.1" }
clap = { version = "~4.4", features = ["derive"] }
http = "0.2.9"
mockall = "0.11.4"
serde_json = "1"
tokio = { version = "1.20.1", features = ["full"] }
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
# snippet-end:[testing.rust.Cargo.toml]

[[bin]]
name = "main"
path = "src/main.rs"
```

Exemplo de teste de unidade usando automock e um wrapper de serviço.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// snippet-start:[testing.rust.wrapper]
// snippet-start:[testing.rust.wrapper-uses]
use aws_sdk_s3 as s3;
#[allow(unused_imports)]
use mockall::automock;

use s3::operation::list_objects_v2::{ListObjectsV2Error, ListObjectsV2Output};
// snippet-end:[testing.rust.wrapper-uses]

// snippet-start:[testing.rust.wrapper-which-impl]
#[cfg(test)]
pub use MockS3Impl as S3;
#[cfg(not(test))]
pub use S3Impl as S3;
// snippet-end:[testing.rust.wrapper-which-impl]

// snippet-start:[testing.rust.wrapper-impl]
#[allow(dead_code)]
pub struct S3Impl {
    inner: s3::Client,
}

#[cfg_attr(test, automock)]
impl S3Impl {
    #[allow(dead_code)]
    pub fn new(inner: s3::Client) -> Self {
        Self { inner }
    }

    #[allow(dead_code)]
    pub async fn list_objects(
        &self,
        bucket: &str,
        prefix: &str,
        continuation_token: Option<String>,
    ) -> Result<ListObjectsV2Output, s3::error::SdkError<ListObjectsV2Error>> {
```

```
        self.inner
            .list_objects_v2()
            .bucket(bucket)
            .prefix(prefix)
            .set_continuation_token(continuation_token)
            .send()
            .await
    }
}
// snippet-end:[testing.rust.wrapper-impl]

// snippet-start:[testing.rust.wrapper-func]
#[allow(dead_code)]
pub async fn determine_prefix_file_size(
    // Now we take a reference to our trait object instead of the S3 client
    // s3_list: ListObjectsService,
    s3_list: S3,
    bucket: &str,
    prefix: &str,
) -> Result<usize, s3::Error> {
    let mut next_token: Option<String> = None;
    let mut total_size_bytes = 0;
    loop {
        let result = s3_list
            .list_objects(bucket, prefix, next_token.take())
            .await?;

        // Add up the file sizes we got back
        for object in result.contents() {
            total_size_bytes += object.size().unwrap_or(0) as usize;
        }

        // Handle pagination, and break the loop if there are no more pages
        next_token = result.next_continuation_token.clone();
        if next_token.is_none() {
            break;
        }
    }
    Ok(total_size_bytes)
}
// snippet-end:[testing.rust.wrapper-func]
// snippet-end:[testing.rust.wrapper]

// snippet-start:[testing.rust.wrapper-test-mod]
```

```
#[cfg(test)]
mod test {
    // snippet-start:[testing.rust.wrapper-tests]
    use super::*;
    use mockall::predicate::eq;

    // snippet-start:[testing.rust.wrapper-test-single]
    #[tokio::test]
    async fn test_single_page() {
        let mut mock = MockS3Impl::default();
        mock.expect_list_objects()
            .with(eq("test-bucket"), eq("test-prefix"), eq(None))
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(5).build(),
                        s3::types::Object::builder().size(2).build(),
                    ]))
                    .build())
            });

        // Run the code we want to test with it
        let size = determine_prefix_file_size(mock, "test-bucket", "test-prefix")
            .await
            .unwrap();

        // Verify we got the correct total size back
        assert_eq!(7, size);
    }
    // snippet-end:[testing.rust.wrapper-test-single]

    // snippet-start:[testing.rust.wrapper-test-multiple]
    #[tokio::test]
    async fn test_multiple_pages() {
        // Create the Mock instance with two pages of objects now
        let mut mock = MockS3Impl::default();
        mock.expect_list_objects()
            .with(eq("test-bucket"), eq("test-prefix"), eq(None))
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(5).build(),
```

```
                        s3::types::Object::builder().size(2).build(),
                    ]))
                    .set_next_continuation_token(Some("next".to_string()))
                    .build())
            });
        mock.expect_list_objects()
            .with(
                eq("test-bucket"),
                eq("test-prefix"),
                eq(Some("next".to_string())),
            )
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(3).build(),
                        s3::types::Object::builder().size(9).build(),
                    ]))
                    .build())
            });

        // Run the code we want to test with it
        let size = determine_prefix_file_size(mock, "test-bucket", "test-prefix")
            .await
            .unwrap();

        assert_eq!(19, size);
    }
    // snippet-end:[testing.rust.wrapper-test-multiple]
    // snippet-end:[testing.rust.wrapper-tests]
}
// snippet-end:[testing.rust.wrapper-test-mod]
```

Exemplo de teste de integração usando StaticReplayClient.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// snippet-start:[testing.rust.replay-uses]
use aws_sdk_s3 as s3;
// snippet-end:[testing.rust.replay-uses]
```

```
#[allow(dead_code)]
// snippet-start:[testing.rust.replay]
pub async fn determine_prefix_file_size(
    // Now we take a reference to our trait object instead of the S3 client
    // s3_list: ListObjectsService,
    s3: s3::Client,
    bucket: &str,
    prefix: &str,
) -> Result<usize, s3::Error> {
    let mut next_token: Option<String> = None;
    let mut total_size_bytes = 0;
    loop {
        let result = s3
            .list_objects_v2()
            .prefix(prefix)
            .bucket(bucket)
            .set_continuation_token(next_token.take())
            .send()
            .await?;

        // Add up the file sizes we got back
        for object in result.contents() {
            total_size_bytes += object.size().unwrap_or(0) as usize;
        }

        // Handle pagination, and break the loop if there are no more pages
        next_token = result.next_continuation_token.clone();
        if next_token.is_none() {
            break;
        }
    }
    Ok(total_size_bytes)
}
// snippet-end:[testing.rust.replay]

#[allow(dead_code)]
// snippet-start:[testing.rust.replay-tests]
// snippet-start:[testing.rust.replay-make-credentials]
fn make_s3_test_credentials() -> s3::config::Credentials {
    s3::config::Credentials::new(
        "ATESTCLIENT",
        "astestsecretkey",
        Some("atestsessiontoken".to_string()),
        None,
```

```
        "",
    )
}
// snippet-end:[testing.rust.replay-make-credentials]

// snippet-start:[testing.rust.replay-test-module]
#[cfg(test)]
mod test {
    // snippet-start:[testing.rust.replay-test-single]
    use super::*;
    use aws_config::BehaviorVersion;
    use aws_sdk_s3 as s3;
    use aws_smithy_runtime::client::http::test_util::{ReplayEvent,
 StaticReplayClient};
    use aws_smithy_types::body::SdkBody;

    #[tokio::test]
    async fn test_single_page() {
        let page_1 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/
response_1.xml")))
                    .unwrap(),
            );
        let replay_client = StaticReplayClient::new(vec![page_1]);
        let client: s3::Client = s3::Client::from_conf(
            s3::Config::builder()
                .behavior_version(BehaviorVersion::latest())
                .credentials_provider(make_s3_test_credentials())
                .region(s3::config::Region::new("us-east-1"))
                .http_client(replay_client.clone())
                .build(),
        );

        // Run the code we want to test with it
        let size = determine_prefix_file_size(client, "test-bucket", "test-
prefix")
```

```
            .await
            .unwrap();

        // Verify we got the correct total size back
        assert_eq!(7, size);
        replay_client.assert_requests_match(&[]);
    }
    // snippet-end:[testing.rust.replay-test-single]

    // snippet-start:[testing.rust.replay-test-multiple]
    #[tokio::test]
    async fn test_multiple_pages() {
        // snippet-start:[testing.rust.replay-create-replay]
        let page_1 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/
response_multi_1.xml")))
                    .unwrap(),
            );
        let page_2 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix&continuation-token=next")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/
response_multi_2.xml")))
                    .unwrap(),
            );
        let replay_client = StaticReplayClient::new(vec![page_1, page_2]);
        // snippet-end:[testing.rust.replay-create-replay]
        // snippet-start:[testing.rust.replay-create-client]
        let client: s3::Client = s3::Client::from_conf(
            s3::Config::builder()
```

```
                .behavior_version(BehaviorVersion::latest())
                .credentials_provider(make_s3_test_credentials())
                .region(s3::config::Region::new("us-east-1"))
                .http_client(replay_client.clone())
                .build(),
        );
        // snippet-end:[testing.rust.replay-create-client]

        // Run the code we want to test with it
        // snippet-start:[testing.rust.replay-test-and-verify]
        let size = determine_prefix_file_size(client, "test-bucket", "test-
prefix")
            .await
            .unwrap();

        assert_eq!(19, size);

        replay_client.assert_requests_match(&[]);
        // snippet-end:[testing.rust.replay-test-and-verify]
    }
    // snippet-end:[testing.rust.replay-test-multiple]
}
// snippet-end:[testing.rust.replay-tests]
// snippet-end:[testing.rust.replay-test-module]
```

Fazer upload de uma única parte de um carregamento fracionado usando um AWS SDK

Os exemplos de código a seguir mostram como fazer upload de uma única parte de um upload fracionado.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Realizar um carregamento fracionado
- Usar somas de verificação

CLI

AWS CLI

O seguinte comando faz o upload da primeira parte de um upload fracionado iniciado com o comando `create-multipart-upload`:

```
aws s3api upload-part --bucket my-bucket --key 'multipart/01' --part-number 1 --
body part01 --upload-id
 "dfRtDYU0WWCCcH43C3WFbkRONycyCpTJJvxu2i5GYkZljF.Yxwh6XG7WfS2vC4to6HiV6Yjlx.cph0gtNBtJ8P3
```

A opção `body` usa o nome ou o caminho de um arquivo local para upload (não use o prefixo file://). O tamanho mínimo de uma parte é de 5 MB. O ID de upload é retornado por `create-multipart-upload` e também pode ser recuperado com `list-multipart-uploads`. O bucket e a chave são especificados ao criar o upload fracionado.

Saída:

```
{
    "ETag": "\"e868e0f4719e394144ef36531ee6824c\""
}
```

Salve o valor do ETag de cada parte para etapas posteriores. Eles são necessários para concluir o upload fracionado.

- Para obter detalhes da API, consulte UploadPartem Referência de AWS CLI Comandos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let upload_part_res = client
            .upload_part()
            .key(&key)
```

```
            .bucket(&bucket_name)
            .upload_id(upload_id)
            .body(stream)
            .part_number(part_number)
            .send()
            .await?;
        upload_parts.push(
            CompletedPart::builder()
                .e_tag(upload_part_res.e_tag.unwrap_or_default())
                .part_number(part_number)
                .build(),
        );

   let completed_multipart_upload: CompletedMultipartUpload =
CompletedMultipartUpload::builder()
        .set_parts(Some(upload_parts))
        .build();
```

- Para obter detalhes da API, consulte a UploadPartreferência da API AWS SDK for Rust.

Carregar um objeto em um bucket do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como fazer upload de um objeto em um bucket do S3.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de buckets e objetos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to upload a file from the local computer to an Amazon S3
        /// bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The Amazon S3 bucket to which the object
        /// will be uploaded.</param>
        /// <param name="objectName">The object to upload.</param>
        /// <param name="filePath">The path, including file name, of the object
        /// on the local computer to upload.</param>
        /// <returns>A boolean value indicating the success or failure of the
        /// upload procedure.</returns>
        public static async Task<bool> UploadFileAsync(
            IAmazonS3 client,
            string bucketName,
            string objectName,
            string filePath)
        {
            var request = new PutObjectRequest
            {
                BucketName = bucketName,
                Key = objectName,
                FilePath = filePath,
            };

            var response = await client.PutObjectAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully uploaded {objectName} to
{bucketName}.");
                return true;
            }
            else
            {
                Console.WriteLine($"Could not upload {objectName} to
{bucketName}.");
                return false;
            }
        }
```

Faça upload de um objeto com criptografia do lado do servidor.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to upload an object to an Amazon Simple Storage
    /// Service (Amazon S3) bucket with server-side encryption enabled.
    /// </summary>
    public class ServerSideEncryption
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "samplefile.txt";

            // If the AWS Region defined for your default user is different
            // from the Region where your Amazon S3 bucket is located,
            // pass the Region name to the Amazon S3 client object's constructor.
            // For example: RegionEndpoint.USWest2.
            IAmazonS3 client = new AmazonS3Client();

            await WritingAnObjectAsync(client, bucketName, keyName);
        }

        /// <summary>
        /// Upload a sample object include a setting for encryption.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
        /// to upload a file and apply server-side encryption.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
        /// encrypted object will reside.</param>
        /// <param name="keyName">The name for the object that you want to
        /// create in the supplied bucket.</param>
        public static async Task WritingAnObjectAsync(IAmazonS3 client, string
bucketName, string keyName)
        {
            try
            {
                var putRequest = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
```

```
                    ContentBody = "sample text",
                    ServerSideEncryptionMethod =
ServerSideEncryptionMethod.AES256,
                };

                var putResponse = await client.PutObjectAsync(putRequest);

                // Determine the encryption state of an object.
                GetObjectMetadataRequest metadataRequest = new
GetObjectMetadataRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                };
                GetObjectMetadataResponse response = await
client.GetObjectMetadataAsync(metadataRequest);
                ServerSideEncryptionMethod objectEncryption =
response.ServerSideEncryptionMethod;

                Console.WriteLine($"Encryption method used: {0}",
objectEncryption.ToString());
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: '{ex.Message}' when writing an
object");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function copy_file_to_bucket
#
# This function creates a file in the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file to.
#       $2 - The path and file name of the local file to copy to the bucket.
#       $3 - The key (name) to call the copy of the file in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function copy_file_to_bucket() {
  local response bucket_name source_file destination_file_name
  bucket_name=$1
  source_file=$2
  destination_file_name=$3

  response=$(aws s3api put-object \
    --bucket "$bucket_name" \
    --body "$source_file" \
    --key "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte PutObjectem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutObject(const Aws::String &bucketName,
                           const Aws::String &fileName,
                           const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    //We are using the name of the file as the key for the object in the bucket.
    //However, this is just a string and can be set according to your retrieval
 needs.
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          fileName.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);

    if (!*inputData) {
        std::cerr << "Error unable to read file " << fileName << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3_client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
```

```
    }
    else {
        std::cout << "Added object '" << fileName << "' to bucket '"
                  << bucketName << "'.";
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for C++ da API.

CLI

AWS CLI

O seguinte exemplo usa o comando `put-object` para fazer upload de um objeto no Amazon S3:

```
aws s3api put-object --bucket text-content --key dir-1/my_images.tar.bz2 --body
 my_images.tar.bz2
```

O seguinte exemplo mostra o upload de um arquivo de vídeo (o arquivo de vídeo é especificado usando a sintaxe do sistema de arquivos do Windows):

```
aws s3api put-object --bucket text-content --key dir-1/big-video-file.mp4 --body
 e:\media\videos\f-sharp-3-data-services.mp4
```

Para obter mais informações sobre o upload de objetos, Uploading Objects in the Guia do desenvolvedor do Amazon S3.

- Para obter detalhes da API, consulte PutObjectem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// UploadFile reads from a file and puts the data into an object in a bucket.
func (basics BucketBasics) UploadFile(bucketName string, objectKey string,
 fileName string) error {
 file, err := os.Open(fileName)
 if err != nil {
  log.Printf("Couldn't open file %v to upload. Here's why: %v\n", fileName, err)
 } else {
  defer file.Close()
  _, err = basics.S3Client.PutObject(context.TODO(), &s3.PutObjectInput{
   Bucket: aws.String(bucketName),
   Key:    aws.String(objectKey),
   Body:   file,
  })
  if err != nil {
   log.Printf("Couldn't upload file %v to %v:%v. Here's why: %v\n",
    fileName, bucketName, objectKey, err)
  }
 }
 return err
```

```
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um arquivo em um bucket usando um S3Client.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class PutObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
```

```
                  <bucketName> <objectKey> <objectPath>\s

                Where:
                  bucketName - The Amazon S3 bucket to upload an object into.
                  objectKey - The object to upload (for example, book.pdf).
                  objectPath - The path where the file is located (for example,
C:/AWS/book2.pdf).\s
                """;

       if (args.length != 3) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucketName = args[0];
       String objectKey = args[1];
       String objectPath = args[2];
       Region region = Region.US_EAST_1;
       S3Client s3 = S3Client.builder()
               .region(region)
               .build();

       putS3Object(s3, bucketName, objectKey, objectPath);
       s3.close();
   }

   // This example uses RequestBody.fromFile to avoid loading the whole file
into
   // memory.
   public static void putS3Object(S3Client s3, String bucketName, String
objectKey, String objectPath) {
       try {
           Map<String, String> metadata = new HashMap<>();
           metadata.put("x-amz-meta-myVal", "test");
           PutObjectRequest putOb = PutObjectRequest.builder()
                   .bucket(bucketName)
                   .key(objectKey)
                   .metadata(metadata)
                   .build();

           s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
           System.out.println("Successfully placed " + objectKey + " into bucket
" + bucketName);
```

```
        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Use um S3 TransferManager para carregar um arquivo em um bucket. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedFileUpload;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;
import software.amazon.awssdk.transfer.s3.progress.LoggingTransferListener;

import java.net.URL;
import java.nio.file.Paths;
import java.util.UUID;

    public String uploadFile(S3TransferManager transferManager, String
 bucketName,
            String key, String filePath) {
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b.bucket(bucketName).key(key))
                .addTransferListener(LoggingTransferListener.create())
                .source(Paths.get(filePath))
                .build();

        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);

        CompletedFileUpload uploadResult = fileUpload.completionFuture().join();
        return uploadResult.response().eTag();
    }
```

Faça upload de um objeto em um bucket e defina etiquetas usando um S3Client.

```
    public static void putS3ObjectTags(S3Client s3, String bucketName, String
 objectKey, String objectPath) {
```

```
        try {
            Tag tag1 = Tag.builder()
                    .key("Tag 1")
                    .value("This is tag 1")
                    .build();

            Tag tag2 = Tag.builder()
                    .key("Tag 2")
                    .value("This is tag 2")
                    .build();

            List<Tag> tags = new ArrayList<>();
            tags.add(tag1);
            tags.add(tag2);

            Tagging allTags = Tagging.builder()
                    .tagSet(tags)
                    .build();

            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .tagging(allTags)
                    .build();

            s3.putObject(putOb,
RequestBody.fromBytes(getObjectFile(objectPath)));

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateObjectTags(S3Client s3, String bucketName, String
objectKey) {
        try {
            GetObjectTaggingRequest taggingRequest =
GetObjectTaggingRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .build();
```

```
            GetObjectTaggingResponse getTaggingRes =
s3.getObjectTagging(taggingRequest);
            List<Tag> obTags = getTaggingRes.tagSet();
            for (Tag sinTag : obTags) {
                System.out.println("The tag key is: " + sinTag.key());
                System.out.println("The tag value is: " + sinTag.value());
            }

            // Replace the object's tags with two new tags.
            Tag tag3 = Tag.builder()
                    .key("Tag 3")
                    .value("This is tag 3")
                    .build();

            Tag tag4 = Tag.builder()
                    .key("Tag 4")
                    .value("This is tag 4")
                    .build();

            List<Tag> tags = new ArrayList<>();
            tags.add(tag3);
            tags.add(tag4);

            Tagging updatedTags = Tagging.builder()
                    .tagSet(tags)
                    .build();

            PutObjectTaggingRequest taggingRequest1 =
PutObjectTaggingRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .tagging(updatedTags)
                    .build();

            s3.putObjectTagging(taggingRequest1);
            GetObjectTaggingResponse getTaggingRes2 =
s3.getObjectTagging(taggingRequest);
            List<Tag> modTags = getTaggingRes2.tagSet();
            for (Tag sinTag : modTags) {
                System.out.println("The tag key is: " + sinTag.key());
                System.out.println("The tag value is: " + sinTag.value());
            }

        } catch (S3Exception e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Return a byte array.
    private static byte[] getObjectFile(String filePath) {
        FileInputStream fileInputStream = null;
        byte[] bytesArray = null;

        try {
            File file = new File(filePath);
            bytesArray = new byte[(int) file.length()];
            fileInputStream = new FileInputStream(file);
            fileInputStream.read(bytesArray);

        } catch (IOException e) {
            e.printStackTrace();
        } finally {
            if (fileInputStream != null) {
                try {
                    fileInputStream.close();
                } catch (IOException e) {
                    e.printStackTrace();
                }
            }
        }

        return bytesArray;
    }
}
```

Faça upload de um objeto em um bucket e defina metadados usando um S3Client.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.util.HashMap;
import java.util.Map;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutObjectMetadata {
    public static void main(String[] args) {
        final String USAGE = """

                Usage:
                  <bucketName> <objectKey> <objectPath>\s

                Where:
                  bucketName - The Amazon S3 bucket to upload an object into.
                  objectKey - The object to upload (for example, book.pdf).
                  objectPath - The path where the file is located (for example,
 C:/AWS/book2.pdf).\s
                """;

        if (args.length != 3) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String bucketName = args[0];
        String objectKey = args[1];
        String objectPath = args[2];
        System.out.println("Putting object " + objectKey + " into bucket " +
 bucketName);
        System.out.println("  in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        putS3Object(s3, bucketName, objectKey, objectPath);
        s3.close();
    }
```

```
    // This example uses RequestBody.fromFile to avoid loading the whole file
 into
    // memory.
    public static void putS3Object(S3Client s3, String bucketName, String
 objectKey, String objectPath) {
        try {
            Map<String, String> metadata = new HashMap<>();
            metadata.put("author", "Mary Doe");
            metadata.put("version", "1.0.0.0");

            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .metadata(metadata)
                    .build();

            s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
            System.out.println("Successfully placed " + objectKey + " into bucket
 " + bucketName);

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Faça upload de um objeto em um bucket e defina um valor de retenção de objetos usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRetentionRequest;
import software.amazon.awssdk.services.s3.model.ObjectLockRetention;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.time.Instant;
import java.time.LocalDate;
import java.time.LocalDateTime;
import java.time.ZoneOffset;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class PutObjectRetention {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <key> <bucketName>\s

                Where:
                    key - The name of the object (for example, book.pdf).\s
                    bucketName - The Amazon S3 bucket name that contains the
 object (for example, bucket1).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String key = args[0];
        String bucketName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setRentionPeriod(s3, key, bucketName);
        s3.close();
    }

    public static void setRentionPeriod(S3Client s3, String key, String bucket) {
        try {
            LocalDate localDate = LocalDate.parse("2020-07-17");
            LocalDateTime localDateTime = localDate.atStartOfDay();
            Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

            ObjectLockRetention lockRetention = ObjectLockRetention.builder()
```

```
                    .mode("COMPLIANCE")
                    .retainUntilDate(instant)
                    .build();

            PutObjectRetentionRequest retentionRequest =
 PutObjectRetentionRequest.builder()
                    .bucket(bucket)
                    .key(key)
                    .bypassGovernanceRetention(true)
                    .retention(lockRetention)
                    .build();

            // To set Retention on an object, the Amazon S3 bucket must support
 object
            // locking, otherwise an exception is thrown.
            s3.putObjectRetention(retentionRequest);
            System.out.print("An object retention configuration was successfully
 placed on the object");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue o objeto.

```
import { PutObjectCommand, S3Client } from "@aws-sdk/client-s3";
```

```
const client = new S3Client({});

export const main = async () => {
  const command = new PutObjectCommand({
    Bucket: "test-bucket",
    Key: "hello-s3.txt",
    Body: "Hello S3!",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putS3Object(bucketName: String, objectKey: String, objectPath:
 String) {
    val metadataVal = mutableMapOf<String, String>()
    metadataVal["myVal"] = "test"

    val request = PutObjectRequest {
        bucket = bucketName
```

```
        key = objectKey
        metadata = metadataVal
        body = File(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.putObject(request)
        println("Tag information is ${response.eTag}")
    }
}
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um objeto em um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        $fileName = __DIR__ . "/local-file-" . uniqid();
        try {
            $this->s3client->putObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
                'SourceFile' => __DIR__ . '/testfile.txt'
            ]);
            echo "Uploaded $fileName to $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to upload $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with file upload before continuing.");
        }
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource
 in Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def put(self, data):
        """
        Upload data to the object.

        :param data: The data to upload. This can either be bytes or a string.
 When this
                     argument is a string, it is interpreted as a file name,
 which is
                     opened in read bytes mode.
        """
        put_data = data
        if isinstance(data, str):
            try:
                put_data = open(data, "rb")
            except IOError:
```

```
                logger.exception("Expected file name or binary data, got '%s'.",
 data)
                raise

        try:
            self.object.put(Body=put_data)
            self.object.wait_until_exists()
            logger.info(
                "Put object '%s' to bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't put object '%s' to bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
        finally:
            if getattr(put_data, "close", None):
                put_data.close()
```

- Para obter detalhes da API, consulte a PutObjectReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um arquivo usando um carregador gerenciado (Object.upload_file).

```
require "aws-sdk-s3"
```

```
# Wraps Amazon S3 object actions.
class ObjectUploadFileWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Uploads a file to an Amazon S3 object by using a managed uploader.
  #
  # @param file_path [String] The path to the file to upload.
  # @return [Boolean] True when the file is uploaded; otherwise false.
  def upload_file(file_path)
    @object.upload_file(file_path)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't upload file #{file_path} to #{@object.key}. Here's why:
 #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-uploaded-file"
  file_path = "object_upload_file.rb"

  wrapper = ObjectUploadFileWrapper.new(Aws::S3::Object.new(bucket_name,
 object_key))
  return unless wrapper.upload_file(file_path)

  puts "File #{file_path} successfully uploaded to #{bucket_name}:#{object_key}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Carregue um arquivo usando Object.put.

```
require "aws-sdk-s3"
```

```
# Wraps Amazon S3 object actions.
class ObjectPutWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  def put_object(source_file_path)
    File.open(source_file_path, "rb") do |file|
      @object.put(body: file)
    end
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't put #{source_file_path} to #{object.key}. Here's why:
 #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object-key"
  file_path = "my-local-file.txt"

  wrapper = ObjectPutWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
  success = wrapper.put_object(file_path)
  return unless success

  puts "Put file #{file_path} into #{object_key} in #{bucket_name}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Carregue um arquivo usando Object.put e adicione criptografia no lado do servidor.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectPutSseWrapper
```

```
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  def put_object_encrypted(object_content, encryption)
    @object.put(body: object_content, server_side_encryption: encryption)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't put your content to #{object.key}. Here's why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-encrypted-content"
  object_content = "This is my super-secret content."
  encryption = "AES256"

  wrapper = ObjectPutSseWrapper.new(Aws::S3::Object.new(bucket_name,
 object_content))
  return unless wrapper.put_object_encrypted(object_content, encryption)

  puts "Put your content into #{bucket_name}:#{object_key} and encrypted it with
 #{encryption}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn upload_object(
    client: &Client,
    bucket_name: &str,
    file_name: &str,
    key: &str,
) -> Result<PutObjectOutput, SdkError<PutObjectError>> {
    let body = ByteStream::from_path(Path::new(file_name)).await;
    client
        .put_object()
        .bucket(bucket_name)
        .key(key)
        .body(body.unwrap())
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Get contents of file from application server."
    DATA lv_body TYPE xstring.
    OPEN DATASET iv_file_name FOR INPUT IN BINARY MODE.
    READ DATASET iv_file_name INTO lv_body.
    CLOSE DATASET iv_file_name.

    "Upload/put an object to an S3 bucket."
    TRY.
        lo_s3->putobject(
            iv_bucket = iv_bucket_name
            iv_key = iv_file_name
            iv_body = lv_body
        ).
        MESSAGE 'Object uploaded to S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWS SDK for SAP ABAP.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um arquivo do armazenamento local para um bucket.

```
   public func uploadFile(bucket: String, key: String, file: String) async
throws {
       let fileUrl = URL(fileURLWithPath: file)
       let fileData = try Data(contentsOf: fileUrl)
       let dataStream = ByteStream.from(data: fileData)

       let input = PutObjectInput(
           body: dataStream,
           bucket: bucket,
           key: key
       )
       _ = try await client.putObject(input: input)
   }
```

Carregue o conteúdo de um objeto Swift Data para um bucket.

```
   public func createFile(bucket: String, key: String, withData data: Data)
async throws {
       let dataStream = ByteStream.from(data: data)

       let input = PutObjectInput(
           body: dataStream,
           bucket: bucket,
           key: key
       )
       _ = try await client.putObject(input: input)
   }
```

- Para obter detalhes da API, consulte PutObjecta referência da API AWS SDK for Swift.

Fazer upload recursivo de um diretório local em um bucket do Amazon Simple Storage Service (Amazon S3)

O exemplo de código a seguir mostra como fazer upload recursivo de um diretório local em um bucket do Amazon Simple Storage Service (Amazon S3).

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use um S3 TransferManager para carregar um diretório local. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedDirectoryUpload;
import software.amazon.awssdk.transfer.s3.model.DirectoryUpload;
import software.amazon.awssdk.transfer.s3.model.UploadDirectoryRequest;

import java.net.URL;
import java.nio.file.Paths;
import java.util.UUID;

    public Integer uploadDirectory(S3TransferManager transferManager,
            String sourceDirectory, String bucketName) {
        DirectoryUpload directoryUpload =
 transferManager.uploadDirectory(UploadDirectoryRequest.builder()
                .source(Paths.get(sourceDirectory))
                .bucket(bucketName)
                .build());

        CompletedDirectoryUpload completedDirectoryUpload =
 directoryUpload.completionFuture().join();
        completedDirectoryUpload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
 fail.toString()));
        return completedDirectoryUpload.failedTransfers().size();
    }
```

- Para obter detalhes da API, consulte UploadDirectorya Referência AWS SDK for Java 2.x da API.

Cenários do Amazon S3 usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Storage Service (Amazon S3) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar um URL pré-assinado para o Amazon S3 usando um AWS SDK
- Uma página da web que oferece uma lista de objetos do Amazon S3 usando um AWS SDK
- Conceitos básicos de buckets e objetos do Amazon S3 usando um AWS SDK
- Conceitos básicos de criptografia para objetos do Amazon S3 usando um AWS SDK
- Conceitos básicos de etiquetas para objetos do Amazon S3 usando um AWS SDK
- Gerenciar listas de controle de acesso (ACLs) para buckets do Amazon S3 usando um AWS SDK
- Gerenciar objetos do Amazon S3 versionados em lotes com uma função do Lambda usando um AWS SDK
- Analisar URIs do Amazon S3 usando um AWS SDK
- Executar uma cópia multipart de um objeto do Amazon S3 usando um AWS SDK
- Realizar um carregamento fracionado em um objeto do Amazon S3 usando um AWS SDK
- Fazer upload ou download de arquivos grandes de e para o Amazon S3 usando um AWS SDK
- Faça upload de um fluxo de tamanho desconhecido em um objeto do Amazon S3 usando um AWS SDK
- Usar somas de verificação para trabalhar com um objeto do Amazon S3 usando um AWS SDK
- Trabalhar com objetos versionados do Amazon S3 usando um AWS SDK

Criar um URL pré-assinado para o Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como criar um URL pré-assinado para o Amazon S3 e carregar um objeto.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado que possa executar uma ação do Amazon S3 por tempo limitado.

```
    using System;
    using Amazon;
    using Amazon.S3;
    using Amazon.S3.Model;

    public class GenPresignedUrl
    {
        public static void Main()
        {
            const string bucketName = "doc-example-bucket";
            const string objectKey = "sample.txt";

            // Specify how long the presigned URL lasts, in hours
            const double timeoutDuration = 12;

            // Specify the AWS Region of your Amazon S3 bucket. If it is
            // different from the Region defined for the default user,
            // pass the Region to the constructor for the client. For
            // example: new AmazonS3Client(RegionEndpoint.USEast1);

            // If using the Region us-east-1, and server-side encryption with AWS
 KMS, you must specify Signature Version 4.
            // Region us-east-1 defaults to Signature Version 2 unless explicitly
 set to Version 4 as shown below.
            // For more details, see https://docs.aws.amazon.com/AmazonS3/latest/
userguide/UsingAWSSDK.html#specify-signature-version
            // and https://docs.aws.amazon.com/sdkfornet/v3/apidocs/items/Amazon/
TAWSConfigsS3.html
            AWSConfigsS3.UseSignatureVersion4 = true;
            IAmazonS3 s3Client = new AmazonS3Client(RegionEndpoint.USEast1);
```

```
            string urlString = GeneratePresignedURL(s3Client, bucketName,
objectKey, timeoutDuration);
            Console.WriteLine($"The generated URL is: {urlString}.");
        }

        /// <summary>
        /// Generate a presigned URL that can be used to access the file named
        /// in the objectKey parameter for the amount of time specified in the
        /// duration parameter.
        /// </summary>
        /// <param name="client">An initialized S3 client object used to call
        /// the GetPresignedUrl method.</param>
        /// <param name="bucketName">The name of the S3 bucket containing the
        /// object for which to create the presigned URL.</param>
        /// <param name="objectKey">The name of the object to access with the
        /// presigned URL.</param>
        /// <param name="duration">The length of time for which the presigned
        /// URL will be valid.</param>
        /// <returns>A string representing the generated presigned URL.</returns>
        public static string GeneratePresignedURL(IAmazonS3 client, string
bucketName, string objectKey, double duration)
        {
            string urlString = string.Empty;
            try
            {
                var request = new GetPreSignedUrlRequest()
                {
                    BucketName = bucketName,
                    Key = objectKey,
                    Expires = DateTime.UtcNow.AddHours(duration),
                };
                urlString = client.GetPreSignedURL(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error:'{ex.Message}'");
            }

            return urlString;
        }
    }
```

Gere um URL pré-assinado e faça um upload usando esse URL.

```
    using System;
    using System.IO;
    using System.Net.Http;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to upload an object to an Amazon Simple Storage
    /// Service (Amazon S3) bucket using a presigned URL. The code first
    /// creates a presigned URL and then uses it to upload an object to an
    /// Amazon S3 bucket using that URL.
    /// </summary>
    public class UploadUsingPresignedURL
    {
        private static HttpClient httpClient = new HttpClient();

        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "samplefile.txt";
            string filePath = $"source\\{keyName}";

            // Specify how long the signed URL will be valid in hours.
            double timeoutDuration = 12;

            // Specify the AWS Region of your Amazon S3 bucket. If it is
            // different from the Region defined for the default user,
            // pass the Region to the constructor for the client. For
            // example: new AmazonS3Client(RegionEndpoint.USEast1);

            // If using the Region us-east-1, and server-side encryption with AWS
 KMS, you must specify Signature Version 4.
            // Region us-east-1 defaults to Signature Version 2 unless explicitly
 set to Version 4 as shown below.
            // For more details, see https://docs.aws.amazon.com/AmazonS3/latest/
userguide/UsingAWSSDK.html#specify-signature-version
            // and https://docs.aws.amazon.com/sdkfornet/v3/apidocs/items/Amazon/
TAWSConfigsS3.html
            AWSConfigsS3.UseSignatureVersion4 = true;
            IAmazonS3 client = new AmazonS3Client(RegionEndpoint.USEast1);
```

```
            var url = GeneratePreSignedURL(client, bucketName, keyName,
timeoutDuration);
            var success = await UploadObject(filePath, url);

            if (success)
            {
                Console.WriteLine("Upload succeeded.");
            }
            else
            {
                Console.WriteLine("Upload failed.");
            }
        }

        /// <summary>
        /// Uploads an object to an Amazon S3 bucket using the presigned URL
passed in
        /// the url parameter.
        /// </summary>
        /// <param name="filePath">The path (including file name) to the local
        /// file you want to upload.</param>
        /// <param name="url">The presigned URL that will be used to upload the
        /// file to the Amazon S3 bucket.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// operation, based on the HttpWebResponse.</returns>
        public static async Task<bool> UploadObject(string filePath, string url)
        {
            using var streamContent = new StreamContent(
                new FileStream(filePath, FileMode.Open, FileAccess.Read));

            var response = await httpClient.PutAsync(url, streamContent);
            return response.IsSuccessStatusCode;
        }

        /// <summary>
        /// Generates a presigned URL which will be used to upload an object to
        /// an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// GetPreSignedURL.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to which
the
```

```
        /// presigned URL will point.</param>
        /// <param name="objectKey">The name of the file that will be uploaded.</
param>
        /// <param name="duration">How long (in hours) the presigned URL will
        /// be valid.</param>
        /// <returns>The generated URL.</returns>
        public static string GeneratePreSignedURL(
            IAmazonS3 client,
            string bucketName,
            string objectKey,
            double duration)
        {
            var request = new GetPreSignedUrlRequest
            {
                BucketName = bucketName,
                Key = objectKey,
                Verb = HttpVerb.PUT,
                Expires = DateTime.UtcNow.AddHours(duration),
            };

            string url = client.GetPreSignedURL(request);
            return url;
        }
    }
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações de pré-assinatura do S3.

```
// Presigner encapsulates the Amazon Simple Storage Service (Amazon S3) presign
 actions
```

```
// used in the examples.
// It contains PresignClient, a client that is used to presign requests to Amazon
 S3.
// Presigned requests contain temporary credentials and can be made from any HTTP
 client.
type Presigner struct {
 PresignClient *s3.PresignClient
}



// GetObject makes a presigned request that can be used to get an object from a
 bucket.
// The presigned request is valid for the specified number of seconds.
func (presigner Presigner) GetObject(
 bucketName string, objectKey string, lifetimeSecs int64)
 (*v4.PresignedHTTPRequest, error) {
 request, err := presigner.PresignClient.PresignGetObject(context.TODO(),
 &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 }, func(opts *s3.PresignOptions) {
  opts.Expires = time.Duration(lifetimeSecs * int64(time.Second))
 })
 if err != nil {
  log.Printf("Couldn't get a presigned request to get %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return request, err
}



// PutObject makes a presigned request that can be used to put an object in a
 bucket.
// The presigned request is valid for the specified number of seconds.
func (presigner Presigner) PutObject(
 bucketName string, objectKey string, lifetimeSecs int64)
 (*v4.PresignedHTTPRequest, error) {
 request, err := presigner.PresignClient.PresignPutObject(context.TODO(),
 &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 }, func(opts *s3.PresignOptions) {
```

```
  opts.Expires = time.Duration(lifetimeSecs * int64(time.Second))
 })
 if err != nil {
  log.Printf("Couldn't get a presigned request to put %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return request, err
}



// DeleteObject makes a presigned request that can be used to delete an object
 from a bucket.
func (presigner Presigner) DeleteObject(bucketName string, objectKey string)
 (*v4.PresignedHTTPRequest, error) {
 request, err := presigner.PresignClient.PresignDeleteObject(context.TODO(),
 &s3.DeleteObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't get a presigned request to delete object %v. Here's why:
 %v\n", objectKey, err)
 }
 return request, err
}
```

Execute um exemplo interativo que gera e usa URLs pré-assinados para fazer upload, fazer download e excluir um objeto do S3.

```


// RunPresigningScenario is an interactive example that shows you how to get
 presigned
// HTTP requests that you can use to move data into and out of Amazon Simple
 Storage
// Service (Amazon S3). The presigned requests contain temporary credentials and
 can
// be used by an HTTP client.
//
// 1. Get a presigned request to put an object in a bucket.
```

```
// 2. Use the net/http package to use the presigned request to upload a local
 file to the bucket.
// 3. Get a presigned request to get an object from a bucket.
// 4. Use the net/http package to use the presigned request to download the
 object to a local file.
// 5. Get a presigned request to delete an object from a bucket.
// 6. Use the net/http package to use the presigned request to delete the object.
//
// This example creates an Amazon S3 presign client from the specified sdkConfig
 so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
//
// It uses an IHttpRequester interface to abstract HTTP requests so they can be
 mocked
// during testing.
func RunPresigningScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner, httpRequester IHttpRequester) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon S3 presigning demo.")
 log.Println(strings.Repeat("-", 88))

 s3Client := s3.NewFromConfig(sdkConfig)
 bucketBasics := actions.BucketBasics{S3Client: s3Client}
 presignClient := s3.NewPresignClient(s3Client)
 presigner := actions.Presigner{PresignClient: presignClient}

 bucketName := questioner.Ask("We'll need a bucket. Enter a name for a bucket "+
  "you own or one you want to create:", demotools.NotEmpty{})
 bucketExists, err := bucketBasics.BucketExists(bucketName)
 if err != nil {
  panic(err)
 }
 if !bucketExists {
  err = bucketBasics.CreateBucket(bucketName, sdkConfig.Region)
```

```
 if err != nil {
  panic(err)
 } else {
  log.Println("Bucket created.")
 }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's presign a request to upload a file to your bucket.")
uploadFilename := questioner.Ask("Enter the path to a file you want to upload:",
 demotools.NotEmpty{})
uploadKey := questioner.Ask("What would you like to name the uploaded object?",
 demotools.NotEmpty{})
uploadFile, err := os.Open(uploadFilename)
if err != nil {
 panic(err)
}
defer uploadFile.Close()
presignedPutRequest, err := presigner.PutObject(bucketName, uploadKey, 60)
if err != nil {
 panic(err)
}
log.Printf("Got a presigned %v request to URL:\n\t%v\n",
presignedPutRequest.Method,
 presignedPutRequest.URL)
log.Println("Using net/http to send the request...")
info, err := uploadFile.Stat()
if err != nil {
 panic(err)
}
putResponse, err := httpRequester.Put(presignedPutRequest.URL, info.Size(),
uploadFile)
if err != nil {
 panic(err)
}
log.Printf("%v object %v with presigned URL returned %v.",
presignedPutRequest.Method,
 uploadKey, putResponse.StatusCode)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's presign a request to download the object.")
questioner.Ask("Press Enter when you're ready.")
presignedGetRequest, err := presigner.GetObject(bucketName, uploadKey, 60)
if err != nil {
```

```
 panic(err)
}
log.Printf("Got a presigned %v request to URL:\n\t%v\n",
presignedGetRequest.Method,
 presignedGetRequest.URL)
log.Println("Using net/http to send the request...")
getResponse, err := httpRequester.Get(presignedGetRequest.URL)
if err != nil {
 panic(err)
}
log.Printf("%v object %v with presigned URL returned %v.",
presignedGetRequest.Method,
 uploadKey, getResponse.StatusCode)
defer getResponse.Body.Close()
downloadBody, err := io.ReadAll(getResponse.Body)
if err != nil {
 panic(err)
}
log.Printf("Downloaded %v bytes. Here are the first 100 of them:\n",
len(downloadBody))
log.Println(strings.Repeat("-", 88))
log.Println(string(downloadBody[:100]))
log.Println(strings.Repeat("-", 88))

log.Println("Let's presign a request to delete the object.")
questioner.Ask("Press Enter when you're ready.")
presignedDelRequest, err := presigner.DeleteObject(bucketName, uploadKey)
if err != nil {
 panic(err)
}
log.Printf("Got a presigned %v request to URL:\n\t%v\n",
presignedDelRequest.Method,
 presignedDelRequest.URL)
log.Println("Using net/http to send the request...")
delResponse, err := httpRequester.Delete(presignedDelRequest.URL)
if err != nil {
 panic(err)
}
log.Printf("%v object %v with presigned URL returned %v.\n",
presignedDelRequest.Method,
 uploadKey, delResponse.StatusCode)
log.Println(strings.Repeat("-", 88))

log.Println("Thanks for watching!")
```

```
 log.Println(strings.Repeat("-", 88))
}
```

Defina um wrapper de solicitação HTTP usado pelo exemplo para fazer solicitações HTTP.

```
// IHttpRequester abstracts HTTP requests into an interface so it can be mocked
 during
// unit testing.
type IHttpRequester interface {
 Get(url string) (resp *http.Response, err error)
 Put(url string, contentLength int64, body io.Reader) (resp *http.Response, err
 error)
 Delete(url string) (resp *http.Response, err error)
}

// HttpRequester uses the net/http package to make HTTP requests during the
 scenario.
type HttpRequester struct{}

func (httpReq HttpRequester) Get(url string) (resp *http.Response, err error) {
 return http.Get(url)
}
func (httpReq HttpRequester) Put(url string, contentLength int64, body io.Reader)
 (resp *http.Response, err error) {
 putRequest, err := http.NewRequest("PUT", url, body)
 if err != nil {
  return nil, err
 }
 putRequest.ContentLength = contentLength
 return http.DefaultClient.Do(putRequest)
}
func (httpReq HttpRequester) Delete(url string) (resp *http.Response, err error)
 {
 delRequest, err := http.NewRequest("DELETE", url, nil)
 if err != nil {
  return nil, err
 }
 return http.DefaultClient.Do(delRequest)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado para um objeto e baixe-o (solicitação GET).

Importações

```
import com.example.s3.util.PresignUrlUtils;
import org.slf4j.Logger;
import software.amazon.awssdk.http.HttpExecuteRequest;
import software.amazon.awssdk.http.HttpExecuteResponse;
import software.amazon.awssdk.http.SdkHttpClient;
import software.amazon.awssdk.http.SdkHttpMethod;
import software.amazon.awssdk.http.SdkHttpRequest;
import software.amazon.awssdk.http.apache.ApacheHttpClient;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import
 software.amazon.awssdk.services.s3.presigner.model.GetObjectPresignRequest;
import
 software.amazon.awssdk.services.s3.presigner.model.PresignedGetObjectRequest;
import software.amazon.awssdk.utils.IoUtils;

import java.io.ByteArrayOutputStream;
import java.io.File;
import java.io.IOException;
import java.io.InputStream;
import java.net.HttpURLConnection;
import java.net.URISyntaxException;
import java.net.URL;
import java.net.http.HttpClient;
```

```
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.file.Paths;
import java.time.Duration;
import java.util.UUID;
```

Gere o URL.

```
    /* Create a pre-signed URL to download an object in a subsequent GET request.
 */
    public String createPresignedGetUrl(String bucketName, String keyName) {
        try (S3Presigner presigner = S3Presigner.create()) {

            GetObjectRequest objectRequest = GetObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            GetObjectPresignRequest presignRequest =
 GetObjectPresignRequest.builder()
                    .signatureDuration(Duration.ofMinutes(10))  // The URL will
 expire in 10 minutes.
                    .getObjectRequest(objectRequest)
                    .build();

            PresignedGetObjectRequest presignedRequest =
 presigner.presignGetObject(presignRequest);
            logger.info("Presigned URL: [{}]",
 presignedRequest.url().toString());
            logger.info("HTTP method: [{}]",
 presignedRequest.httpRequest().method());

            return presignedRequest.url().toExternalForm();
        }
    }
```

Baixe o objeto usando uma das três abordagens a seguir.

Use a classe `HttpURLConnection` do JDK (desde a v1.1) para baixar.

```
    /* Use the JDK HttpURLConnection (since v1.1) class to do the download. */
```

```
    public byte[] useHttpUrlConnectionToGet(String presignedUrlString) {
        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.

        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpURLConnection connection = (HttpURLConnection)
presignedUrl.openConnection();
            connection.setRequestMethod("GET");
            // Download the result of executing the request.
            try (InputStream content = connection.getInputStream()) {
                IoUtils.copy(content, byteArrayOutputStream);
            }
            logger.info("HTTP response code is " + connection.getResponseCode());

        } catch (S3Exception | IOException e) {
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Use a classe `HttpClient` do JDK (desde a v11) para baixar.

```
    /* Use the JDK HttpClient (since v11) class to do the download. */
    public byte[] useHttpClientToGet(String presignedUrlString) {
        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.

        HttpRequest.Builder requestBuilder = HttpRequest.newBuilder();
        HttpClient httpClient = HttpClient.newHttpClient();
        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpResponse<InputStream> response = httpClient.send(requestBuilder
                            .uri(presignedUrl.toURI())
                            .GET()
                            .build(),
                    HttpResponse.BodyHandlers.ofInputStream());

            IoUtils.copy(response.body(), byteArrayOutputStream);

            logger.info("HTTP response code is " + response.statusCode());
```

```
        } catch (URISyntaxException | InterruptedException | IOException e) {
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Use a classe `SdkHttpClient` do SDK da AWS para Java para baixar.

```
    /* Use the AWS SDK for Java SdkHttpClient class to do the download. */
    public byte[] useSdkHttpClientToPut(String presignedUrlString) {

        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.
        try {
            URL presignedUrl = new URL(presignedUrlString);
            SdkHttpRequest request = SdkHttpRequest.builder()
                    .method(SdkHttpMethod.GET)
                    .uri(presignedUrl.toURI())
                    .build();

            HttpExecuteRequest executeRequest = HttpExecuteRequest.builder()
                    .request(request)
                    .build();

            try (SdkHttpClient sdkHttpClient = ApacheHttpClient.create()) {
                HttpExecuteResponse response =
sdkHttpClient.prepareRequest(executeRequest).call();
                response.responseBody().ifPresentOrElse(
                        abortableInputStream -> {
                            try {
                                IoUtils.copy(abortableInputStream,
byteArrayOutputStream);
                            } catch (IOException e) {
                                throw new RuntimeException(e);
                            }
                        },
                        () -> logger.error("No response body."));

                logger.info("HTTP Response code is {}",
response.httpResponse().statusCode());
            }
        } catch (URISyntaxException | IOException e) {
```

```
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Gere um URL pré-assinado para um upload e faça upload de um arquivo (solicitação PUT).

Importações

```
import com.example.s3.util.PresignUrlUtils;
import org.slf4j.Logger;
import software.amazon.awssdk.core.internal.sync.FileContentStreamProvider;
import software.amazon.awssdk.http.HttpExecuteRequest;
import software.amazon.awssdk.http.HttpExecuteResponse;
import software.amazon.awssdk.http.SdkHttpClient;
import software.amazon.awssdk.http.SdkHttpMethod;
import software.amazon.awssdk.http.SdkHttpRequest;
import software.amazon.awssdk.http.apache.ApacheHttpClient;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import
 software.amazon.awssdk.services.s3.presigner.model.PresignedPutObjectRequest;
import
 software.amazon.awssdk.services.s3.presigner.model.PutObjectPresignRequest;

import java.io.File;
import java.io.IOException;
import java.io.OutputStream;
import java.io.RandomAccessFile;
import java.net.HttpURLConnection;
import java.net.URISyntaxException;
import java.net.URL;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.ByteBuffer;
import java.nio.channels.FileChannel;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Duration;
import java.util.Map;
```

```
import java.util.UUID;
```

Gere o URL.

```
    /* Create a presigned URL to use in a subsequent PUT request */
    public String createPresignedUrl(String bucketName, String keyName,
 Map<String, String> metadata) {
        try (S3Presigner presigner = S3Presigner.create()) {

            PutObjectRequest objectRequest = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .metadata(metadata)
                    .build();

            PutObjectPresignRequest presignRequest =
 PutObjectPresignRequest.builder()
                    .signatureDuration(Duration.ofMinutes(10))  // The URL
 expires in 10 minutes.
                    .putObjectRequest(objectRequest)
                    .build();


            PresignedPutObjectRequest presignedRequest =
 presigner.presignPutObject(presignRequest);
            String myURL = presignedRequest.url().toString();
            logger.info("Presigned URL to upload a file to: [{}]", myURL);
            logger.info("HTTP method: [{}]",
 presignedRequest.httpRequest().method());

            return presignedRequest.url().toExternalForm();
        }
    }
```

Faça upload de um objeto de arquivo usando uma das três abordagens a seguir.

Use a classe `HttpURLConnection` do JDK (desde a v1.1) para fazer upload.

```
    /* Use the JDK HttpURLConnection (since v1.1) class to do the upload. */
    public void useHttpUrlConnectionToPut(String presignedUrlString, File
 fileToPut, Map<String, String> metadata) {
```

```
        logger.info("Begin [{}] upload", fileToPut.toString());
        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpURLConnection connection = (HttpURLConnection)
 presignedUrl.openConnection();
            connection.setDoOutput(true);
            metadata.forEach((k, v) -> connection.setRequestProperty("x-amz-
meta-" + k, v));
            connection.setRequestMethod("PUT");
            OutputStream out = connection.getOutputStream();

            try (RandomAccessFile file = new RandomAccessFile(fileToPut, "r");
                 FileChannel inChannel = file.getChannel()) {
                ByteBuffer buffer = ByteBuffer.allocate(8192); //Buffer size is
 8k

                while (inChannel.read(buffer) > 0) {
                    buffer.flip();
                    for (int i = 0; i < buffer.limit(); i++) {
                        out.write(buffer.get());
                    }
                    buffer.clear();
                }
            } catch (IOException e) {
                logger.error(e.getMessage(), e);
            }

            out.close();
            connection.getResponseCode();
            logger.info("HTTP response code is " + connection.getResponseCode());

        } catch (S3Exception | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

Use a classe `HttpClient` do JDK (desde a v11) para fazer upload.

```
    /* Use the JDK HttpClient (since v11) class to do the upload. */
    public void useHttpClientToPut(String presignedUrlString, File fileToPut,
 Map<String, String> metadata) {
        logger.info("Begin [{}] upload", fileToPut.toString());
```

```
        HttpRequest.Builder requestBuilder = HttpRequest.newBuilder();
        metadata.forEach((k, v) -> requestBuilder.header("x-amz-meta-" + k, v));

        HttpClient httpClient = HttpClient.newHttpClient();
        try {
            final HttpResponse<Void> response = httpClient.send(requestBuilder
                            .uri(new URL(presignedUrlString).toURI())

.PUT(HttpRequest.BodyPublishers.ofFile(Path.of(fileToPut.toURI())))
                            .build(),
                    HttpResponse.BodyHandlers.discarding());

            logger.info("HTTP response code is " + response.statusCode());

        } catch (URISyntaxException | InterruptedException | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

Use a classe `SdkHttpClient` do AWS para Java V2 para fazer upload.

```
    /* Use the AWS SDK for Java V2 SdkHttpClient class to do the upload. */
    public void useSdkHttpClientToPut(String presignedUrlString, File fileToPut,
Map<String, String> metadata) {
        logger.info("Begin [{}] upload", fileToPut.toString());

        try {
            URL presignedUrl = new URL(presignedUrlString);

            SdkHttpRequest.Builder requestBuilder = SdkHttpRequest.builder()
                    .method(SdkHttpMethod.PUT)
                    .uri(presignedUrl.toURI());
            // Add headers
            metadata.forEach((k, v) -> requestBuilder.putHeader("x-amz-meta-" +
k, v));
            // Finish building the request.
            SdkHttpRequest request = requestBuilder.build();

            HttpExecuteRequest executeRequest = HttpExecuteRequest.builder()
                    .request(request)
```

```
                    .contentStreamProvider(new
 FileContentStreamProvider(fileToPut.toPath()))
                    .build();

            try (SdkHttpClient sdkHttpClient = ApacheHttpClient.create()) {
                HttpExecuteResponse response =
 sdkHttpClient.prepareRequest(executeRequest).call();
                logger.info("Response code: {}",
 response.httpResponse().statusCode());
            }
        } catch (URISyntaxException | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um URL pré-assinado para carregar um objeto em um bucket.

```
import https from "https";
import { PutObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { fromIni } from "@aws-sdk/credential-providers";
import { HttpRequest } from "@smithy/protocol-http";
import {
  getSignedUrl,
  S3RequestPresigner,
} from "@aws-sdk/s3-request-presigner";
import { parseUrl } from "@smithy/url-parser";
import { formatUrl } from "@aws-sdk/util-format-url";
import { Hash } from "@smithy/hash-node";

const createPresignedUrlWithoutClient = async ({ region, bucket, key }) => {
  const url = parseUrl(`https://${bucket}.s3.${region}.amazonaws.com/${key}`);
```

```
  const presigner = new S3RequestPresigner({
    credentials: fromIni(),
    region,
    sha256: Hash.bind(null, "sha256"),
  });

  const signedUrlObject = await presigner.presign(
    new HttpRequest({ ...url, method: "PUT" }),
  );
  return formatUrl(signedUrlObject);
};

const createPresignedUrlWithClient = ({ region, bucket, key }) => {
  const client = new S3Client({ region });
  const command = new PutObjectCommand({ Bucket: bucket, Key: key });
  return getSignedUrl(client, command, { expiresIn: 3600 });
};

function put(url, data) {
  return new Promise((resolve, reject) => {
    const req = https.request(
      url,
      { method: "PUT", headers: { "Content-Length": new Blob([data]).size } },
      (res) => {
        let responseBody = "";
        res.on("data", (chunk) => {
          responseBody += chunk;
        });
        res.on("end", () => {
          resolve(responseBody);
        });
      },
    );
    req.on("error", (err) => {
      reject(err);
    });
    req.write(data);
    req.end();
  });
}

export const main = async () => {
  const REGION = "us-east-1";
  const BUCKET = "example_bucket";
```

```
  const KEY = "example_file.txt";

  // There are two ways to generate a presigned URL.
  // 1. Use createPresignedUrl without the S3 client.
  // 2. Use getSignedUrl in conjunction with the S3 client and GetObjectCommand.
  try {
    const noClientUrl = await createPresignedUrlWithoutClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    const clientUrl = await createPresignedUrlWithClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    // After you get the presigned URL, you can provide your own file
    // data. Refer to put() above.
    console.log("Calling PUT using presigned URL without client");
    await put(noClientUrl, "Hello World");

    console.log("Calling PUT using presigned URL with client");
    await put(clientUrl, "Hello World");

    console.log("\nDone. Check your S3 console.");
  } catch (err) {
    console.error(err);
  }
};
```

Crie um URL pré-assinado para baixar um objeto de um bucket.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { fromIni } from "@aws-sdk/credential-providers";
import { HttpRequest } from "@smithy/protocol-http";
import {
  getSignedUrl,
  S3RequestPresigner,
} from "@aws-sdk/s3-request-presigner";
import { parseUrl } from "@smithy/url-parser";
```

```
import { formatUrl } from "@aws-sdk/util-format-url";
import { Hash } from "@smithy/hash-node";

const createPresignedUrlWithoutClient = async ({ region, bucket, key }) => {
  const url = parseUrl(`https://${bucket}.s3.${region}.amazonaws.com/${key}`);
  const presigner = new S3RequestPresigner({
    credentials: fromIni(),
    region,
    sha256: Hash.bind(null, "sha256"),
  });

  const signedUrlObject = await presigner.presign(new HttpRequest(url));
  return formatUrl(signedUrlObject);
};

const createPresignedUrlWithClient = ({ region, bucket, key }) => {
  const client = new S3Client({ region });
  const command = new GetObjectCommand({ Bucket: bucket, Key: key });
  return getSignedUrl(client, command, { expiresIn: 3600 });
};

export const main = async () => {
  const REGION = "us-east-1";
  const BUCKET = "example_bucket";
  const KEY = "example_file.jpg";

  try {
    const noClientUrl = await createPresignedUrlWithoutClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    const clientUrl = await createPresignedUrlWithClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    console.log("Presigned URL without client");
    console.log(noClientUrl);
    console.log("\n");

    console.log("Presigned URL with client");
```

```
    console.log(clientUrl);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma `GetObject` solicitação pré-assinada e usar a URL para baixar um objeto.

```
suspend fun getObjectPresigned(s3: S3Client, bucketName: String, keyName:
 String): String {
    // Create a GetObjectRequest.
    val unsignedRequest = GetObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the GetObject request.
    val presignedRequest = s3.presignGetObject(unsignedRequest, 24.hours)

    // Use the URL from the presigned HttpRequest in a subsequent HTTP GET
 request to retrieve the object.
    val objectContents = URL(presignedRequest.url.toString()).readText()

    return objectContents
}
```

Crie uma solicitação `GetObject` atribuída previamente com opções avançadas.

```
suspend fun getObjectPresignedMoreOptions(s3: S3Client, bucketName: String,
 keyName: String): HttpRequest {
    // Create a GetObjectRequest.
    val unsignedRequest = GetObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the GetObject request.
    val presignedRequest = s3.presignGetObject(unsignedRequest, signer =
 CrtAwsSigner) {
        signingDate = Instant.now() + 12.hours // Presigned request can be used
 12 hours from now.
        algorithm = AwsSigningAlgorithm.SIGV4_ASYMMETRIC
        signatureType = AwsSignatureType.HTTP_REQUEST_VIA_QUERY_PARAMS
        expiresAfter = 8.hours // Presigned request expires 8 hours later.
    }
    return presignedRequest
}
```

Criar uma `PutObject` solicitação pré-assinada e usá-la para carregar um objeto.

```
suspend fun putObjectPresigned(s3: S3Client, bucketName: String, keyName: String,
 content: String) {
    // Create a PutObjectRequest.
    val unsignedRequest = PutObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the request.
    val presignedRequest = s3.presignPutObject(unsignedRequest, 24.hours)

    // Use the URL and any headers from the presigned HttpRequest in a subsequent
 HTTP PUT request to retrieve the object.
    // Create a PUT request using the OKHttpClient API.
    val putRequest = Request
        .Builder()
        .url(presignedRequest.url.toString())
        .apply {
```

```
            presignedRequest.headers.forEach { key, values ->
                header(key, values.joinToString(", "))
            }
        }
        .put(content.toRequestBody())
        .build()

    val response = OkHttpClient().newCall(putRequest).execute()
    assert(response.isSuccessful)
}
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado que possa realizar uma ação do S3 por tempo limitado. Use o pacote Requests (Solicitações) para fazer uma solicitação com o URL.

```
import argparse
import logging
import boto3
from botocore.exceptions import ClientError
import requests

logger = logging.getLogger(__name__)


def generate_presigned_url(s3_client, client_method, method_parameters,
 expires_in):
    """
    Generate a presigned Amazon S3 URL that can be used to perform an action.

    :param s3_client: A Boto3 Amazon S3 client.
```

```
    :param client_method: The name of the client method that the URL performs.
    :param method_parameters: The parameters of the specified client method.
    :param expires_in: The number of seconds the presigned URL is valid for.
    :return: The presigned URL.
    """
    try:
        url = s3_client.generate_presigned_url(
            ClientMethod=client_method, Params=method_parameters,
 ExpiresIn=expires_in
        )
        logger.info("Got presigned URL: %s", url)
    except ClientError:
        logger.exception(
            "Couldn't get a presigned URL for client method '%s'.", client_method
        )
        raise
    return url


def usage_demo():
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon S3 presigned URL demo.")
    print("-" * 88)

    parser = argparse.ArgumentParser()
    parser.add_argument("bucket", help="The name of the bucket.")
    parser.add_argument(
        "key",
        help="For a GET operation, the key of the object in Amazon S3. For a "
        "PUT operation, the name of a file to upload.",
    )
    parser.add_argument("action", choices=("get", "put"), help="The action to
 perform.")
    args = parser.parse_args()

    s3_client = boto3.client("s3")
    client_action = "get_object" if args.action == "get" else "put_object"
    url = generate_presigned_url(
        s3_client, client_action, {"Bucket": args.bucket, "Key": args.key}, 1000
    )

    print("Using the Requests package to send a request to the URL.")
```

```
    response = None
    if args.action == "get":
        response = requests.get(url)
    elif args.action == "put":
        print("Putting data to the URL.")
        try:
            with open(args.key, "r") as object_file:
                object_text = object_file.read()
            response = requests.put(url, data=object_text)
        except FileNotFoundError:
            print(
                f"Couldn't find {args.key}. For a PUT operation, the key must be
 the "
                f"name of a file that exists on your computer."
            )

    if response is not None:
        print("Got response:")
        print(f"Status: {response.status_code}")
        print(response.text)

    print("-" * 88)


if __name__ == "__main__":
    usage_demo()
```

Gere uma solicitação POST pré-assinada para carregar um arquivo.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name
```

```
    def generate_presigned_post(self, object_key, expires_in):
        """
        Generate a presigned Amazon S3 POST request to upload a file.
        A presigned POST can be used for a limited time to let someone without an
AWS
        account upload a file to a bucket.

        :param object_key: The object key to identify the uploaded object.
        :param expires_in: The number of seconds the presigned POST is valid.
        :return: A dictionary that contains the URL and form fields that contain
                 required access data.
        """
        try:
            response = self.bucket.meta.client.generate_presigned_post(
                Bucket=self.bucket.name, Key=object_key, ExpiresIn=expires_in
            )
            logger.info("Got presigned POST URL: %s", response["url"])
        except ClientError:
            logger.exception(
                "Couldn't get a presigned POST URL for bucket '%s' and object
'%s'",
                self.bucket.name,
                object_key,
            )
            raise
        return response
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"
```

```
require "net/http"

# Creates a presigned URL that can be used to upload content to an object.
#
# @param bucket [Aws::S3::Bucket] An existing Amazon S3 bucket.
# @param object_key [String] The key to give the uploaded object.
# @return [URI, nil] The parsed URI if successful; otherwise nil.
def get_presigned_url(bucket, object_key)
  url = bucket.object(object_key).presigned_url(:put)
  puts "Created presigned URL: #{url}"
  URI(url)
rescue Aws::Errors::ServiceError => e
  puts "Couldn't create presigned URL for #{bucket.name}:#{object_key}. Here's
 why: #{e.message}"
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-file.txt"
  object_content = "This is the content of my-file.txt."

  bucket = Aws::S3::Bucket.new(bucket_name)
  presigned_url = get_presigned_url(bucket, object_key)
  return unless presigned_url

  response = Net::HTTP.start(presigned_url.host) do |http|
    http.send_request("PUT", presigned_url.request_uri, object_content,
 "content_type" => "")
  end

  case response
  when Net::HTTPSuccess
    puts "Content uploaded!"
  else
    puts response.value
  end
end

run_demo if $PROGRAM_NAME == __FILE__
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie solicitações pré-assinadas para objetos GET e PUT do S3.

```
async fn get_object(
    client: &Client,
    bucket: &str,
    object: &str,
    expires_in: u64,
) -> Result<(), Box<dyn Error>> {
    let expires_in = Duration::from_secs(expires_in);
    let presigned_request = client
        .get_object()
        .bucket(bucket)
        .key(object)
        .presigned(PresigningConfig::expires_in(expires_in)?)
        .await?;

    println!("Object URI: {}", presigned_request.uri());

    Ok(())
}

async fn put_object(
    client: &Client,
    bucket: &str,
    object: &str,
    expires_in: u64,
) -> Result<(), Box<dyn Error>> {
    let expires_in = Duration::from_secs(expires_in);

    let presigned_request = client
        .put_object()
        .bucket(bucket)
        .key(object)
```

```
        .presigned(PresigningConfig::expires_in(expires_in)?)
        .await?;

    println!("Object URI: {}", presigned_request.uri());

    Ok(())
}
```

Uma página da web que oferece uma lista de objetos do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como listar objetos do Amazon S3 em uma página da web.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O código a seguir é o componente relevante do React que faz chamadas para o AWS SDK. Uma versão executável do aplicativo contendo esse componente pode ser encontrada no link anterior GitHub .

```
import { useEffect, useState } from "react";
import {
  ListObjectsCommand,
  ListObjectsCommandOutput,
  S3Client,
} from "@aws-sdk/client-s3";
import { fromCognitoIdentityPool } from "@aws-sdk/credential-providers";
import "./App.css";

function App() {
  const [objects, setObjects] = useState<
    Required<ListObjectsCommandOutput>["Contents"]
  >([]);
```

```
  useEffect(() => {
    const client = new S3Client({
      region: "us-east-1",
      // Unless you have a public bucket, you'll need access to a private bucket.
      // One way to do this is to create an Amazon Cognito identity pool, attach
 a role to the pool,
      // and grant the role access to the 's3:GetObject' action.
      //
      // You'll also need to configure the CORS settings on the bucket to allow
 traffic from
      // this example site. Here's an example configuration that allows all
 origins. Don't
      // do this in production.
      //[
      //  {
      //    "AllowedHeaders": ["*"],
      //    "AllowedMethods": ["GET"],
      //    "AllowedOrigins": ["*"],
      //    "ExposeHeaders": [],
      //  },
      //]
      //
      credentials: fromCognitoIdentityPool({
        clientConfig: { region: "us-east-1" },
        identityPoolId: "<YOUR_IDENTITY_POOL_ID>",
      }),
    });
    const command = new ListObjectsCommand({ Bucket: "bucket-name" });
    client.send(command).then(({ Contents }) => setObjects(Contents || []));
  }, []);

  return (
    <div className="App">
      {objects.map((o) => (
        <div key={o.ETag}>{o.Key}</div>
      ))}
    </div>
  );
}

export default App;
```

- Para obter detalhes da API, consulte ListObjectsa Referência AWS SDK for JavaScript da API.

Conceitos básicos de buckets e objetos do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
public class S3_Basics
{
    public static async Task Main()
    {
        // Create an Amazon S3 client object. The constructor uses the
        // default user installed on the system. To work with Amazon S3
        // features in a different AWS Region, pass the AWS Region as a
        // parameter to the client constructor.
        IAmazonS3 client = new AmazonS3Client();
        string bucketName = string.Empty;
        string filePath = string.Empty;
        string keyName = string.Empty;

        var sepBar = new string('-', Console.WindowWidth);

        Console.WriteLine(sepBar);
```

```
            Console.WriteLine("Amazon Simple Storage Service (Amazon S3) basic");
            Console.WriteLine("procedures. This application will:");
            Console.WriteLine("\n\t1. Create a bucket");
            Console.WriteLine("\n\t2. Upload an object to the new bucket");
            Console.WriteLine("\n\t3. Copy the uploaded object to a folder in the
 bucket");
            Console.WriteLine("\n\t4. List the items in the new bucket");
            Console.WriteLine("\n\t5. Delete all the items in the bucket");
            Console.WriteLine("\n\t6. Delete the bucket");
            Console.WriteLine(sepBar);

            // Create a bucket.
            Console.WriteLine($"\n{sepBar}");
            Console.WriteLine("\nCreate a new Amazon S3 bucket.\n");
            Console.WriteLine(sepBar);

            Console.Write("Please enter a name for the new bucket: ");
            bucketName = Console.ReadLine();

            var success = await S3Bucket.CreateBucketAsync(client, bucketName);
            if (success)
            {
                Console.WriteLine($"Successfully created bucket: {bucketName}.
\n");
            }
            else
            {
                Console.WriteLine($"Could not create bucket: {bucketName}.\n");
            }

            Console.WriteLine(sepBar);
            Console.WriteLine("Upload a file to the new bucket.");
            Console.WriteLine(sepBar);

            // Get the local path and filename for the file to upload.
            while (string.IsNullOrEmpty(filePath))
            {
                Console.Write("Please enter the path and filename of the file to
 upload: ");
                filePath = Console.ReadLine();

                // Confirm that the file exists on the local computer.
                if (!File.Exists(filePath))
                {
```

```
                    Console.WriteLine($"Couldn't find {filePath}. Try again.\n");
                    filePath = string.Empty;
                }
            }

            // Get the file name from the full path.
            keyName = Path.GetFileName(filePath);

            success = await S3Bucket.UploadFileAsync(client, bucketName, keyName,
filePath);

            if (success)
            {
                Console.WriteLine($"Successfully uploaded {keyName} from
{filePath} to {bucketName}.\n");
            }
            else
            {
                Console.WriteLine($"Could not upload {keyName}.\n");
            }

            // Set the file path to an empty string to avoid overwriting the
            // file we just uploaded to the bucket.
            filePath = string.Empty;

            // Now get a new location where we can save the file.
            while (string.IsNullOrEmpty(filePath))
            {
                // First get the path to which the file will be downloaded.
                Console.Write("Please enter the path where the file will be
downloaded: ");
                filePath = Console.ReadLine();

                // Confirm that the file exists on the local computer.
                if (File.Exists($"{filePath}\\{keyName}"))
                {
                    Console.WriteLine($"Sorry, the file already exists in that
location.\n");
                    filePath = string.Empty;
                }
            }

            // Download an object from a bucket.
```

```
            success = await S3Bucket.DownloadObjectFromBucketAsync(client,
bucketName, keyName, filePath);

            if (success)
            {
                Console.WriteLine($"Successfully downloaded {keyName}.\n");
            }
            else
            {
                Console.WriteLine($"Sorry, could not download {keyName}.\n");
            }

            // Copy the object to a different folder in the bucket.
            string folderName = string.Empty;

            while (string.IsNullOrEmpty(folderName))
            {
                Console.Write("Please enter the name of the folder to copy your
object to: ");
                folderName = Console.ReadLine();
            }

            while (string.IsNullOrEmpty(keyName))
            {
                // Get the name to give to the object once uploaded.
                Console.Write("Enter the name of the object to copy: ");
                keyName = Console.ReadLine();
            }

            await S3Bucket.CopyObjectInBucketAsync(client, bucketName, keyName,
folderName);

            // List the objects in the bucket.
            await S3Bucket.ListBucketContentsAsync(client, bucketName);

            // Delete the contents of the bucket.
            await S3Bucket.DeleteBucketContentsAsync(client, bucketName);

            // Deleting the bucket too quickly after deleting its contents will
            // cause an error that the bucket isn't empty. So...
            Console.WriteLine("Press <Enter> when you are ready to delete the
bucket.");
            _ = Console.ReadLine();
```

```
            // Delete the bucket.
            await S3Bucket.DeleteBucketAsync(client, bucketName);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function s3_getting_started
#
# This function creates, copies, and deletes S3 buckets and objects.
#
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
###############################################################################
function s3_getting_started() {
  {
```

```
  if [ "$BUCKET_OPERATIONS_SOURCED" != "True" ]; then
    cd bucket-lifecycle-operations || exit

    source ./bucket_operations.sh
    cd ..
  fi
}

echo_repeat "*" 88
echo "Welcome to the Amazon S3 getting started demo."
echo_repeat "*" 88

local bucket_name
bucket_name=$(generate_random_name "doc-example-bucket")

local region_code
region_code=$(aws configure get region)

if create_bucket -b "$bucket_name" -r "$region_code"; then
  echo "Created demo bucket named $bucket_name"
else
  errecho "The bucket failed to create. This demo will exit."
  return 1
fi

local file_name
while [ -z "$file_name" ]; do
  echo -n "Enter a file you want to upload to your bucket: "
  get_input
  file_name=$get_input_result

  if [ ! -f "$file_name" ]; then
    echo "Could not find file $file_name. Are you sure it exists?"
    file_name=""
  fi
done

local key
key="$(basename "$file_name")"

local result=0
if copy_file_to_bucket "$bucket_name" "$file_name" "$key"; then
  echo "Uploaded file $file_name into bucket $bucket_name with key $key."
else
```

```
    result=1
  fi

  local destination_file
  destination_file="$file_name.download"
  if yes_no_input "Would you like to download $key to the file $destination_file?
(y/n) "; then
    if download_object_from_bucket "$bucket_name" "$destination_file" "$key";
then
      echo "Downloaded $key in the bucket $bucket_name to the file
$destination_file."
    else
      result=1
    fi
  fi

  if yes_no_input "Would you like to copy $key a new object key in your bucket?
(y/n) "; then
    local to_key
    to_key="demo/$key"
    if copy_item_in_bucket "$bucket_name" "$key" "$to_key"; then
      echo "Copied $key in the bucket $bucket_name to the  $to_key."
    else
      result=1
    fi
  fi

  local bucket_items
  bucket_items=$(list_items_in_bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    result=1
  fi

  echo "Your bucket contains the following items."
  echo -e "Name\t\tSize"
  echo "$bucket_items"

  if yes_no_input "Delete the bucket, $bucket_name, as well as the objects in it?
(y/n) "; then
    bucket_items=$(echo "$bucket_items" | cut -f 1)

    if delete_items_in_bucket "$bucket_name" "$bucket_items"; then
```

```
      echo "The following items were deleted from the bucket $bucket_name"
      echo "$bucket_items"
    else
      result=1
    fi

    if delete_bucket "$bucket_name"; then
      echo "Deleted the bucket $bucket_name"
    else
      result=1
    fi
  fi

  return $result
}
```

As funções do Amazon S3 usadas nesse cenário.

```
###############################################################################
# function create-bucket
#
# This function creates the specified bucket in the specified AWS Region, unless
# it already exists.
#
# Parameters:
#       -b bucket_name  -- The name of the bucket to create.
#       -r region_code  -- The code for an AWS Region in which to
#                          create the bucket.
#
# Returns:
#       The URL of the bucket that was created.
#     And:
#       0 - If successful.
#       1 - If it fails.
################################################################################
function create_bucket() {
  local bucket_name region_code response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function create_bucket"
```

```
    echo "Creates an Amazon S3 bucket. You must supply a bucket name:"
    echo "  -b bucket_name    The name of the bucket. It must be globally
 unique."
    echo "  [-r region_code]    The code for an AWS Region in which the bucket is
 created."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "b:r:h" option; do
    case "${option}" in
      b) bucket_name="${OPTARG}" ;;
      r) region_code="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done

  if [[ -z "$bucket_name" ]]; then
    errecho "ERROR: You must provide a bucket name with the -b parameter."
    usage
    return 1
  fi

  local bucket_config_arg
  # A location constraint for "us-east-1" returns an error.
  if [[ -n "$region_code" ]] && [[ "$region_code" != "us-east-1" ]]; then
    bucket_config_arg="--create-bucket-configuration LocationConstraint=
$region_code"
  fi

  iecho "Parameters:\n"
  iecho "    Bucket name:   $bucket_name"
  iecho "    Region code:   $region_code"
  iecho ""

  # If the bucket already exists, we don't want to try to create it.
```

```
  if (bucket_exists "$bucket_name"); then
    errecho "ERROR: A bucket with that name already exists. Try again."
    return 1
  fi

  # shellcheck disable=SC2086
  response=$(aws s3api create-bucket \
    --bucket "$bucket_name" \
    $bucket_config_arg)

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports create-bucket operation failed.\n$response"
    return 1
  fi
}

###############################################################################
# function copy_file_to_bucket
#
# This function creates a file in the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file to.
#       $2 - The path and file name of the local file to copy to the bucket.
#       $3 - The key (name) to call the copy of the file in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_file_to_bucket() {
  local response bucket_name source_file destination_file_name
  bucket_name=$1
  source_file=$2
  destination_file_name=$3

  response=$(aws s3api put-object \
    --bucket "$bucket_name" \
    --body "$source_file" \
    --key "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
```

```
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}

##############################################################################
# function download_object_from_bucket
#
# This function downloads an object in a bucket to a file.
#
# Parameters:
#       $1 - The name of the bucket to download the object from.
#       $2 - The path and file name to store the downloaded bucket.
#       $3 - The key (name) of the object in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function download_object_from_bucket() {
  local bucket_name=$1
  local destination_file_name=$2
  local object_name=$3
  local response

  response=$(aws s3api get-object \
    --bucket "$bucket_name" \
    --key "$object_name" \
    "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}

##############################################################################
# function copy_item_in_bucket
#
# This function creates a copy of the specified file in the same bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file from and to.
```

```
#       $2 - The key of the source file to copy.
#       $3 - The key of the destination file.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_item_in_bucket() {
  local bucket_name=$1
  local source_key=$2
  local destination_key=$3
  local response

  response=$(aws s3api copy-object \
    --bucket "$bucket_name" \
    --copy-source "$bucket_name/$source_key" \
    --key "$destination_key")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api copy-object operation failed.\n$response"
    return 1
  fi
}

###############################################################################
# function list_items_in_bucket
#
# This function displays a list of the files in the bucket with each file's
# size. The function uses the --query parameter to retrieve only the key and
# size fields from the Contents collection.
#
# Parameters:
#       $1 - The name of the bucket.
#
# Returns:
#       The list of files in text format.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function list_items_in_bucket() {
  local bucket_name=$1
  local response
```

```
  response=$(aws s3api list-objects \
    --bucket "$bucket_name" \
    --output text \
    --query 'Contents[].{Key: Key, Size: Size}')

  # shellcheck disable=SC2181
  if [[ ${?} -eq 0 ]]; then
    echo "$response"
  else
    errecho "ERROR: AWS reports s3api list-objects operation failed.\n$response"
    return 1
  fi
}

###############################################################################
# function delete_items_in_bucket
#
# This function deletes the specified list of keys from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - A list of keys in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_items_in_bucket() {
  local bucket_name=$1
  local keys=$2
  local response

  # Create the JSON for the items to delete.
  local delete_items
  delete_items="{\"Objects\":["
  for key in $keys; do
    delete_items="$delete_items{\"Key\": \"$key\"},"
  done
  delete_items=${delete_items%?} # Remove the final comma.
  delete_items="$delete_items]}"

  response=$(aws s3api delete-objects \
    --bucket "$bucket_name" \
```

```
    --delete "$delete_items")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n
$response"
    return 1
  fi
}

##############################################################################
# function delete_bucket
#
# This function deletes the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.

# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function delete_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api delete-bucket \
    --bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR: AWS reports s3api delete-bucket failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - CopyObject
  - CreateBucket
  - DeleteBucket

- DeleteObjects
- GetObject
- ListObjectsV2
- PutObject

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
#include <iostream>
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <aws/s3/model/CopyObjectRequest.h>
#include <aws/s3/model/CreateBucketRequest.h>
#include <aws/s3/model/DeleteBucketRequest.h>
#include <aws/s3/model/DeleteObjectRequest.h>
#include <aws/s3/model/GetObjectRequest.h>
#include <aws/s3/model/ListObjectsRequest.h>
#include <aws/s3/model/PutObjectRequest.h>
#include <aws/s3/model/BucketLocationConstraint.h>
#include <aws/s3/model/CreateBucketConfiguration.h>
#include <aws/core/utils/UUID.h>
#include <aws/core/utils/StringUtils.h>
#include <aws/core/utils/memory/stl/AWSAllocator.h>
#include <aws/core/utils/memory/stl/AWSStreamFwd.h>
#include <fstream>
#include "awsdoc/s3/s3_examples.h"

namespace AwsDoc {
    namespace S3 {

        //! Delete an S3 bucket.
        /*!
          \sa DeleteBucket()
```

```
          \param bucketName The S3 bucket's name.
          \param client An S3 client.
        */
        static bool DeleteBucket(const Aws::String &bucketName, Aws::S3::S3Client
 &client);

        //! Delete an object in an S3 bucket.
        /*!          \sa DeleteObjectFromBucket()
          \param bucketName The S3 bucket's name.
          \param key The key for the object in the S3 bucket.
          \param client An S3 client.
         */
        static bool
        DeleteObjectFromBucket(const Aws::String &bucketName, const Aws::String
 &key, Aws::S3::S3Client &client);
    }
}


//! Scenario to create, copy, and delete S3 buckets and objects.
/*!
  \sa S3_GettingStartedScenario()
  \param uploadFilePath Path to file to upload to an Amazon S3 bucket.
  \param saveFilePath Path for saving a downloaded S3 object.
  \param clientConfig Aws client configuration.
 */
bool AwsDoc::S3::S3_GettingStartedScenario(const Aws::String &uploadFilePath,
 const Aws::String &saveFilePath,
                                            const Aws::Client::ClientConfiguration
 &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    // Create a unique bucket name which is only temporary and will be deleted.
    // Format: "doc-example-bucket-" + lowercase UUID.
    Aws::String uuid = Aws::Utils::UUID::RandomUUID();
    Aws::String bucketName = "doc-example-bucket-" +
                             Aws::Utils::StringUtils::ToLower(uuid.c_str());

    // 1. Create a bucket.
    {
        Aws::S3::Model::CreateBucketRequest request;
        request.SetBucket(bucketName);
```

```
        if (clientConfig.region != Aws::Region::US_EAST_1) {
            Aws::S3::Model::CreateBucketConfiguration createBucketConfiguration;
            createBucketConfiguration.WithLocationConstraint(

Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                            clientConfig.region));
            request.WithCreateBucketConfiguration(createBucketConfiguration);
        }

        Aws::S3::Model::CreateBucketOutcome outcome =
client.CreateBucket(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: CreateBucket: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
            return false;
        }
        else {
            std::cout << "Created the bucket, '" << bucketName <<
                      "', in the region, '" << clientConfig.region << "'." <<
std::endl;
        }
    }

    // 2. Upload a local file to the bucket.
    Aws::String key = "key-for-test";
    {
        Aws::S3::Model::PutObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        std::shared_ptr<Aws::FStream> input_data =
                Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                              uploadFilePath,
                                              std::ios_base::in |
std::ios_base::binary);

        if (!input_data->is_open()) {
            std::cerr << "Error: unable to open file, '" << uploadFilePath <<
"'." << std::endl;
            AwsDoc::S3::DeleteBucket(bucketName, client);
            return false;
```

```
        }

        request.SetBody(input_data);

        Aws::S3::Model::PutObjectOutcome outcome =
                client.PutObject(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: PutObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
            AwsDoc::S3::DeleteObjectFromBucket(bucketName, key, client);
            AwsDoc::S3::DeleteBucket(bucketName, client);
            return false;
        }
        else {
            std::cout << "Added the object with the key, '" << key << "', to the
bucket, '"
                      << bucketName << "'." << std::endl;
        }
    }

    // 3. Download the object to a local file.
    {
        Aws::S3::Model::GetObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        Aws::S3::Model::GetObjectOutcome outcome =
                client.GetObject(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: GetObject: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
        }
        else {
            std::cout << "Downloaded the object with the key, '" << key << "', in
the bucket, '"
                      << bucketName << "'." << std::endl;

            Aws::IOStream &ioStream = outcome.GetResultWithOwnership().
                    GetBody();
```

```
            Aws::OFStream outStream(saveFilePath, std::ios_base::out |
std::ios_base::binary);
            if (!outStream.is_open()) {
                std::cout << "Error: unable to open file, '" << saveFilePath <<
"'." << std::endl;
            }
            else {
                outStream << ioStream.rdbuf();
                std::cout << "Wrote the downloaded object to the file '"
                          << saveFilePath << "'." << std::endl;
            }
        }
    }

    // 4. Copy the object to a different "folder" in the bucket.
    Aws::String copiedToKey = "test-folder/" + key;
    {
        Aws::S3::Model::CopyObjectRequest request;
        request.WithBucket(bucketName)
                .WithKey(copiedToKey)
                .WithCopySource(bucketName + "/" + key);

        Aws::S3::Model::CopyObjectOutcome outcome =
                client.CopyObject(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error: CopyObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
        }
        else {
            std::cout << "Copied the object with the key, '" << key << "', to the
key, '" << copiedToKey
                      << ", in the bucket, '" << bucketName << "'." << std::endl;
        }
    }

    // 5. List objects in the bucket.
    {
        Aws::S3::Model::ListObjectsRequest request;
        request.WithBucket(bucketName);

        Aws::S3::Model::ListObjectsOutcome outcome = client.ListObjects(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: ListObjects: " <<
```

```
                        outcome.GetError().GetMessage() << std::endl;
        }
        else {
            Aws::Vector<Aws::S3::Model::Object> objects =
                    outcome.GetResult().GetContents();

            std::cout << objects.size() << " objects in the bucket, '" <<
 bucketName << "':" << std::endl;

            for (Aws::S3::Model::Object &object: objects) {
                std::cout << "     '" << object.GetKey() << "'" << std::endl;
            }
        }
    }

    // 6. Delete all objects in the bucket.
    // All objects in the bucket must be deleted before deleting the bucket.
    AwsDoc::S3::DeleteObjectFromBucket(bucketName, copiedToKey, client);
    AwsDoc::S3::DeleteObjectFromBucket(bucketName, key, client);

    // 7. Delete the bucket.
    return AwsDoc::S3::DeleteBucket(bucketName, client);
}

bool AwsDoc::S3::DeleteObjectFromBucket(const Aws::String &bucketName, const
 Aws::String &key,
                                        Aws::S3::S3Client &client) {
    Aws::S3::Model::DeleteObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(key);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: DeleteObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Deleted the object with the key, '" << key << "', from the
 bucket, '"
                  << bucketName << "'." << std::endl;
    }
```

```
    return outcome.IsSuccess();
}

bool AwsDoc::S3::DeleteBucket(const Aws::String &bucketName, Aws::S3::S3Client
 &client) {
    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        std::cout << "Deleted the bucket, '" << bucketName << "'." << std::endl;
    }
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina um struct que envolva as ações de bucket e objeto usadas pelo cenário.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListBuckets lists the buckets in the current account.
func (basics BucketBasics) ListBuckets() ([]types.Bucket, error) {
 result, err := basics.S3Client.ListBuckets(context.TODO(),
 &s3.ListBucketsInput{})
 var buckets []types.Bucket
 if err != nil {
  log.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
 } else {
  buckets = result.Buckets
 }
 return buckets, err
}



// BucketExists checks whether a bucket exists in the current account.
func (basics BucketBasics) BucketExists(bucketName string) (bool, error) {
 _, err := basics.S3Client.HeadBucket(context.TODO(), &s3.HeadBucketInput{
```

```
  Bucket: aws.String(bucketName),
 })
 exists := true
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NotFound:
    log.Printf("Bucket %v is available.\n", bucketName)
    exists = false
    err = nil
   default:
    log.Printf("Either you don't have access to bucket %v or another error
 occurred. "+
     "Here's what happened: %v\n", bucketName, err)
   }
  }
 } else {
  log.Printf("Bucket %v exists and you already own it.", bucketName)
 }

 return exists, err
}



// CreateBucket creates a bucket with the specified name in the specified Region.
func (basics BucketBasics) CreateBucket(name string, region string) error {
 _, err := basics.S3Client.CreateBucket(context.TODO(), &s3.CreateBucketInput{
  Bucket: aws.String(name),
  CreateBucketConfiguration: &types.CreateBucketConfiguration{
   LocationConstraint: types.BucketLocationConstraint(region),
  },
 })
 if err != nil {
  log.Printf("Couldn't create bucket %v in Region %v. Here's why: %v\n",
   name, region, err)
 }
 return err
}



// UploadFile reads from a file and puts the data into an object in a bucket.
```

```
func (basics BucketBasics) UploadFile(bucketName string, objectKey string,
 fileName string) error {
 file, err := os.Open(fileName)
 if err != nil {
  log.Printf("Couldn't open file %v to upload. Here's why: %v\n", fileName, err)
 } else {
  defer file.Close()
  _, err = basics.S3Client.PutObject(context.TODO(), &s3.PutObjectInput{
   Bucket: aws.String(bucketName),
   Key:    aws.String(objectKey),
   Body:   file,
  })
  if err != nil {
   log.Printf("Couldn't upload file %v to %v:%v. Here's why: %v\n",
    fileName, bucketName, objectKey, err)
  }
 }
 return err
}



// UploadLargeObject uses an upload manager to upload data to an object in a
 bucket.
// The upload manager breaks large data into parts and uploads the parts
 concurrently.
func (basics BucketBasics) UploadLargeObject(bucketName string, objectKey string,
 largeObject []byte) error {
 largeBuffer := bytes.NewReader(largeObject)
 var partMiBs int64 = 10
 uploader := manager.NewUploader(basics.S3Client, func(u *manager.Uploader) {
  u.PartSize = partMiBs * 1024 * 1024
 })
 _, err := uploader.Upload(context.TODO(), &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
  Body:   largeBuffer,
 })
 if err != nil {
  log.Printf("Couldn't upload large object to %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }

 return err
```

```
}



// DownloadFile gets an object from a bucket and stores it in a local file.
func (basics BucketBasics) DownloadFile(bucketName string, objectKey string,
 fileName string) error {
 result, err := basics.S3Client.GetObject(context.TODO(), &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't get object %v:%v. Here's why: %v\n", bucketName,
 objectKey, err)
  return err
 }
 defer result.Body.Close()
 file, err := os.Create(fileName)
 if err != nil {
  log.Printf("Couldn't create file %v. Here's why: %v\n", fileName, err)
  return err
 }
 defer file.Close()
 body, err := io.ReadAll(result.Body)
 if err != nil {
  log.Printf("Couldn't read object body from %v. Here's why: %v\n", objectKey,
 err)
 }
 _, err = file.Write(body)
 return err
}



// DownloadLargeObject uses a download manager to download an object from a
 bucket.
// The download manager gets the data in parts and writes them to a buffer until
 all of
// the data has been downloaded.
func (basics BucketBasics) DownloadLargeObject(bucketName string, objectKey
 string) ([]byte, error) {
 var partMiBs int64 = 10
 downloader := manager.NewDownloader(basics.S3Client, func(d *manager.Downloader)
 {
```

```
  d.PartSize = partMiBs * 1024 * 1024
 })
 buffer := manager.NewWriteAtBuffer([]byte{})
 _, err := downloader.Download(context.TODO(), buffer, &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't download large object from %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return buffer.Bytes(), err
}



// CopyToFolder copies an object in a bucket to a subfolder in the same bucket.
func (basics BucketBasics) CopyToFolder(bucketName string, objectKey string,
 folderName string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(bucketName),
  CopySource: aws.String(fmt.Sprintf("%v/%v", bucketName, objectKey)),
  Key:        aws.String(fmt.Sprintf("%v/%v", folderName, objectKey)),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v/%v. Here's why: %v\n",
   bucketName, objectKey, bucketName, folderName, objectKey, err)
 }
 return err
}



// CopyToBucket copies an object in a bucket to another bucket.
func (basics BucketBasics) CopyToBucket(sourceBucket string, destinationBucket
 string, objectKey string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(destinationBucket),
  CopySource: aws.String(fmt.Sprintf("%v/%v", sourceBucket, objectKey)),
  Key:        aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v. Here's why: %v\n",
   sourceBucket, objectKey, destinationBucket, objectKey, err)
```

```
 }
 return err
}



// ListObjects lists the objects in a bucket.
func (basics BucketBasics) ListObjects(bucketName string) ([]types.Object, error)
 {
 result, err := basics.S3Client.ListObjectsV2(context.TODO(),
 &s3.ListObjectsV2Input{
  Bucket: aws.String(bucketName),
 })
 var contents []types.Object
 if err != nil {
  log.Printf("Couldn't list objects in bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
  contents = result.Contents
 }
 return contents, err
}



// DeleteObjects deletes a list of objects from a bucket.
func (basics BucketBasics) DeleteObjects(bucketName string, objectKeys []string)
 error {
 var objectIds []types.ObjectIdentifier
 for _, key := range objectKeys {
  objectIds = append(objectIds, types.ObjectIdentifier{Key: aws.String(key)})
 }
 output, err := basics.S3Client.DeleteObjects(context.TODO(),
 &s3.DeleteObjectsInput{
  Bucket: aws.String(bucketName),
  Delete: &types.Delete{Objects: objectIds},
 })
 if err != nil {
  log.Printf("Couldn't delete objects from bucket %v. Here's why: %v\n",
 bucketName, err)
 } else {
  log.Printf("Deleted %v objects.\n", len(output.Deleted))
 }
 return err
```

```
}



// DeleteBucket deletes a bucket. The bucket must be empty or an error is
 returned.
func (basics BucketBasics) DeleteBucket(bucketName string) error {
 _, err := basics.S3Client.DeleteBucket(context.TODO(), &s3.DeleteBucketInput{
  Bucket: aws.String(bucketName)})
 if err != nil {
  log.Printf("Couldn't delete bucket %v. Here's why: %v\n", bucketName, err)
 }
 return err
}
```

Execute um cenário interativo que mostre como trabalhar com buckets e objetos do S3.

```
// RunGetStartedScenario is an interactive example that shows you how to use
 Amazon
// Simple Storage Service (Amazon S3) to create an S3 bucket and use it to store
 objects.
//
// 1. Create a bucket.
// 2. Upload a local file to the bucket.
// 3. Upload a large object to the bucket by using an upload manager.
// 4. Download an object to a local file.
// 5. Download a large object by using a download manager.
// 6. Copy an object to a different folder in the bucket.
// 7. List objects in the bucket.
// 8. Delete all objects in the bucket.
// 9. Delete the bucket.
//
// This example creates an Amazon S3 service client from the specified sdkConfig
 so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
```

```
func RunGetStartedScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Println("Something went wrong with the demo.\n", r)
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon S3 getting started demo.")
 log.Println(strings.Repeat("-", 88))

 s3Client := s3.NewFromConfig(sdkConfig)
 bucketBasics := actions.BucketBasics{S3Client: s3Client}

 count := 10
 log.Printf("Let's list up to %v buckets for your account:", count)
 buckets, err := bucketBasics.ListBuckets()
 if err != nil {
  panic(err)
 }
 if len(buckets) == 0 {
  log.Println("You don't have any buckets!")
 } else {
  if count > len(buckets) {
   count = len(buckets)
  }
  for _, bucket := range buckets[:count] {
   log.Printf("\t%v\n", *bucket.Name)
  }
 }

 bucketName := questioner.Ask("Let's create a bucket. Enter a name for your
 bucket:",
  demotools.NotEmpty{})
 bucketExists, err := bucketBasics.BucketExists(bucketName)
 if err != nil {
  panic(err)
 }
 if !bucketExists {
  err = bucketBasics.CreateBucket(bucketName, sdkConfig.Region)
  if err != nil {
   panic(err)
  } else {
```

```
  log.Println("Bucket created.")
 }
}
log.Println(strings.Repeat("-", 88))

fmt.Println("Let's upload a file to your bucket.")
smallFile := questioner.Ask("Enter the path to a file you want to upload:",
 demotools.NotEmpty{})
const smallKey = "doc-example-key"
err = bucketBasics.UploadFile(bucketName, smallKey, smallFile)
if err != nil {
 panic(err)
}
log.Printf("Uploaded %v as %v.\n", smallFile, smallKey)
log.Println(strings.Repeat("-", 88))

mibs := 30
log.Printf("Let's create a slice of %v MiB of random bytes and upload it to your
bucket. ", mibs)
questioner.Ask("Press Enter when you're ready.")
largeBytes := make([]byte, 1024*1024*mibs)
rand.Seed(time.Now().Unix())
rand.Read(largeBytes)
largeKey := "doc-example-large"
log.Println("Uploading...")
err = bucketBasics.UploadLargeObject(bucketName, largeKey, largeBytes)
if err != nil {
 panic(err)
}
log.Printf("Uploaded %v MiB object as %v", mibs, largeKey)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's download %v to a file.", smallKey)
downloadFileName := questioner.Ask("Enter a name for the downloaded file:",
demotools.NotEmpty{})
err = bucketBasics.DownloadFile(bucketName, smallKey, downloadFileName)
if err != nil {
 panic(err)
}
log.Printf("File %v downloaded.", downloadFileName)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's download the %v MiB object.", mibs)
questioner.Ask("Press Enter when you're ready.")
```

```
log.Println("Downloading...")
largeDownload, err := bucketBasics.DownloadLargeObject(bucketName, largeKey)
if err != nil {
 panic(err)
}
log.Printf("Downloaded %v bytes.", len(largeDownload))
log.Println(strings.Repeat("-", 88))

log.Printf("Let's copy %v to a folder in the same bucket.", smallKey)
folderName := questioner.Ask("Enter a folder name: ", demotools.NotEmpty{})
err = bucketBasics.CopyToFolder(bucketName, smallKey, folderName)
if err != nil {
 panic(err)
}
log.Printf("Copied %v to %v/%v.\n", smallKey, folderName, smallKey)
log.Println(strings.Repeat("-", 88))

log.Println("Let's list the objects in your bucket.")
questioner.Ask("Press Enter when you're ready.")
objects, err := bucketBasics.ListObjects(bucketName)
if err != nil {
 panic(err)
}
log.Printf("Found %v objects.\n", len(objects))
var objKeys []string
for _, object := range objects {
 objKeys = append(objKeys, *object.Key)
 log.Printf("\t%v\n", *object.Key)
}
log.Println(strings.Repeat("-", 88))

if questioner.AskBool("Do you want to delete your bucket and all of its "+
 "contents? (y/n)", "y") {
 log.Println("Deleting objects.")
 err = bucketBasics.DeleteObjects(bucketName, objKeys)
 if err != nil {
  panic(err)
 }
 log.Println("Deleting bucket.")
 err = bucketBasics.DeleteBucket(bucketName)
 if err != nil {
  panic(err)
 }
 log.Printf("Deleting downloaded file %v.\n", downloadFileName)
```

```
  err = os.Remove(downloadFileName)
  if err != nil {
   panic(err)
  }
 } else {
  log.Println("Okay. Don't forget to delete objects from your bucket to avoid
 charges.")
 }
 log.Println(strings.Repeat("-", 88))

 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java code example performs the following tasks:
 *
 * 1. Creates an Amazon S3 bucket.
 * 2. Uploads an object to the bucket.
 * 3. Downloads the object to another local file.
 * 4. Uploads an object using multipart upload.
 * 5. List all objects located in the Amazon S3 bucket.
 * 6. Copies the object to another Amazon S3 bucket.
 * 7. Deletes the object from the Amazon S3 bucket.
 * 8. Deletes the Amazon S3 bucket.
 */

public class S3Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <bucketName> <key> <objectPath> <savePath> <toBucket>

                Where:
                    bucketName - The Amazon S3 bucket to create.
                    key - The key to use.
                    objectPath - The path where the file is located (for example,
 C:/AWS/book2.pdf).
                    savePath - The path where the file is saved after it's
 downloaded (for example, C:/AWS/book2.pdf).
                    toBucket - An Amazon S3 bucket to where an object is copied
 to (for example, C:/AWS/book2.pdf).\s
                    """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String bucketName = args[0];
        String key = args[1];
        String objectPath = args[2];
        String savePath = args[3];
        String toBucket = args[4];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon S3 example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an Amazon S3 bucket.");
        createBucket(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Update a local file to the Amazon S3 bucket.");
        uploadLocalFile(s3, bucketName, key, objectPath);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Download the object to another local file.");
        getObjectBytes(s3, bucketName, key, savePath);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Perform a multipart upload.");
        String multipartKey = "multiPartKey";
        multipartUpload(s3, toBucket, multipartKey);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. List all objects located in the Amazon S3
bucket.");
        listAllObjects(s3, bucketName);
        anotherListExample(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("6. Copy the object to another Amazon S3 bucket.");
        copyBucketObject(s3, bucketName, key, toBucket);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the object from the Amazon S3 bucket.");
        deleteObjectFromBucket(s3, bucketName, key);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Delete the Amazon S3 bucket.");
        deleteBucket(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("All Amazon S3 operations were successfully
performed");
        System.out.println(DASHES);
        s3.close();
    }

    // Create a bucket by using a S3Waiter object.
    public static void createBucket(S3Client s3Client, String bucketName) {
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void deleteBucket(S3Client client, String bucket) {
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucket)
                .build();

        client.deleteBucket(deleteBucketRequest);
        System.out.println(bucket + " was deleted.");
    }

    /**
     * Upload an object in parts.
     */
    public static void multipartUpload(S3Client s3, String bucketName, String
key) {
        int mB = 1024 * 1024;
        // First create a multipart upload and get the upload id.
        CreateMultipartUploadRequest createMultipartUploadRequest =
CreateMultipartUploadRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        CreateMultipartUploadResponse response =
s3.createMultipartUpload(createMultipartUploadRequest);
        String uploadId = response.uploadId();
        System.out.println(uploadId);

        // Upload all the different parts of the object.
        UploadPartRequest uploadPartRequest1 = UploadPartRequest.builder()
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)
                .partNumber(1).build();

        String etag1 = s3.uploadPart(uploadPartRequest1,
RequestBody.fromByteBuffer(getRandomByteBuffer(5 * mB)))
                .eTag();
        CompletedPart part1 =
CompletedPart.builder().partNumber(1).eTag(etag1).build();

        UploadPartRequest uploadPartRequest2 =
UploadPartRequest.builder().bucket(bucketName).key(key)
```

```
                .uploadId(uploadId)
                .partNumber(2).build();
        String etag2 = s3.uploadPart(uploadPartRequest2,
RequestBody.fromByteBuffer(getRandomByteBuffer(3 * mB)))
                .eTag();
        CompletedPart part2 =
CompletedPart.builder().partNumber(2).eTag(etag2).build();

        // Call completeMultipartUpload operation to tell S3 to merge all
uploaded
        // parts and finish the multipart operation.
        CompletedMultipartUpload completedMultipartUpload =
CompletedMultipartUpload.builder()
                .parts(part1, part2)
                .build();

        CompleteMultipartUploadRequest completeMultipartUploadRequest =
CompleteMultipartUploadRequest.builder()
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)
                .multipartUpload(completedMultipartUpload)
                .build();

        s3.completeMultipartUpload(completeMultipartUploadRequest);
    }

    private static ByteBuffer getRandomByteBuffer(int size) {
        byte[] b = new byte[size];
        new Random().nextBytes(b);
        return ByteBuffer.wrap(b);
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
s3.getObjectAsBytes(objectRequest);
```

```
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void uploadLocalFile(S3Client s3, String bucketName, String
key, String objectPath) {
        PutObjectRequest objectRequest = PutObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        s3.putObject(objectRequest, RequestBody.fromFile(new File(objectPath)));
    }

    public static void listAllObjects(S3Client s3, String bucketName) {
        ListObjectsV2Request listObjectsReqManual =
ListObjectsV2Request.builder()
                .bucket(bucketName)
                .maxKeys(1)
                .build();

        boolean done = false;
        while (!done) {
            ListObjectsV2Response listObjResponse =
s3.listObjectsV2(listObjectsReqManual);
            for (S3Object content : listObjResponse.contents()) {
                System.out.println(content.key());
            }

            if (listObjResponse.nextContinuationToken() == null) {
                done = true;
```

```
            }

            listObjectsReqManual = listObjectsReqManual.toBuilder()
                    .continuationToken(listObjResponse.nextContinuationToken())
                    .build();
        }
    }

    public static void anotherListExample(S3Client s3, String bucketName) {
        ListObjectsV2Request listReq = ListObjectsV2Request.builder()
                .bucket(bucketName)
                .maxKeys(1)
                .build();

        ListObjectsV2Iterable listRes = s3.listObjectsV2Paginator(listReq);

        // Process response pages.
        listRes.stream()
                .flatMap(r -> r.contents().stream())
                .forEach(content -> System.out.println(" Key: " + content.key() +
" size = " + content.size()));

        // Helper method to work with paginated collection of items directly.
        listRes.contents().stream()
                .forEach(content -> System.out.println(" Key: " + content.key() +
" size = " + content.size()));

        for (S3Object content : listRes.contents()) {
            System.out.println(" Key: " + content.key() + " size = " +
content.size());
        }
    }

    public static void deleteObjectFromBucket(S3Client s3, String bucketName,
String key) {
        DeleteObjectRequest deleteObjectRequest = DeleteObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        s3.deleteObject(deleteObjectRequest);
        System.out.println(key + " was deleted");
    }
```

```
    public static String copyBucketObject(S3Client s3, String fromBucket, String
 objectKey, String toBucket) {
        String encodedUrl = null;
        try {
            encodedUrl = URLEncoder.encode(fromBucket + "/" + objectKey,
 StandardCharsets.UTF_8.toString());
        } catch (UnsupportedEncodingException e) {
            System.out.println("URL could not be encoded: " + e.getMessage());
        }
        CopyObjectRequest copyReq = CopyObjectRequest.builder()
                .copySource(encodedUrl)
                .destinationBucket(toBucket)
                .destinationKey(objectKey)
                .build();

        try {
            CopyObjectResponse copyRes = s3.copyObject(copyReq);
            System.out.println("The " + objectKey + " was copied to " +
 toBucket);
            return copyRes.copyObjectResult().toString();

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Primeiro, importe todos os módulos necessários.

```
// Used to check if currently running file is this file.
import { fileURLToPath } from "url";
import { readdirSync, readFileSync, writeFileSync } from "fs";

// Local helper utils.
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { wrapText } from "@aws-sdk-examples/libs/utils/util-string.js";

import {
  S3Client,
  CreateBucketCommand,
  PutObjectCommand,
  ListObjectsCommand,
  CopyObjectCommand,
  GetObjectCommand,
  DeleteObjectsCommand,
  DeleteBucketCommand,
} from "@aws-sdk/client-s3";
```

As importações anteriores fazem referência a alguns utilitários auxiliares. Esses utilitários são locais para o GitHub repositório vinculado no início desta seção. Para sua referência, consulte as implementações a seguir desses utilitários.

```
export const dirnameFromMetaUrl = (metaUrl) =>
  fileURLToPath(new URL(".", metaUrl));

import { select, input, confirm, checkbox } from "@inquirer/prompts";
```

```
export class Prompter {
  /**
   * @param {{ message: string, choices: { name: string, value: string }[]}}
 options
   */
  select(options) {
    return select(options);
  }

  /**
   * @param {{ message: string }} options
   */
  input(options) {
    return input(options);
  }

  /**
   * @param {string} prompt
   */
  checkContinue = async (prompt = "") => {
    const prefix = prompt && prompt + " ";
    let ok = await this.confirm({
      message: `${prefix}Continue?`,
    });
    if (!ok) throw new Error("Exiting...");
  };

  /**
   * @param {{ message: string }} options
   */
  confirm(options) {
    return confirm(options);
  }

  /**
   * @param {{ message: string, choices: { name: string, value: string }[]}}
 options
   */
  checkbox(options) {
    return checkbox(options);
  }
}

export const wrapText = (text, char = "=") => {
```

```
  const rule = char.repeat(80);
  return `${rule}\n    ${text}\n${rule}\n`;
};
```

Os objetos no S3 são armazenados em “buckets”. Vamos definir uma função para criar um bucket.

```
export const createBucket = async () => {
  const bucketName = await prompter.input({
    message: "Enter a bucket name. Bucket names must be globally unique:",
  });
  const command = new CreateBucketCommand({ Bucket: bucketName });
  await s3Client.send(command);
  console.log("Bucket created successfully.\n");
  return bucketName;
};
```

Os buckets contêm “objetos”. Essa função faz upload do conteúdo de um diretório para seu bucket como objetos.

```
export const uploadFilesToBucket = async ({ bucketName, folderPath }) => {
  console.log(`Uploading files from ${folderPath}\n`);
  const keys = readdirSync(folderPath);
  const files = keys.map((key) => {
    const filePath = `${folderPath}/${key}`;
    const fileContent = readFileSync(filePath);
    return {
      Key: key,
      Body: fileContent,
    };
  });

  for (let file of files) {
    await s3Client.send(
      new PutObjectCommand({
        Bucket: bucketName,
        Body: file.Body,
        Key: file.Key,
      }),
    );
```

```
    console.log(`${file.Key} uploaded successfully.`);
  }
};
```

Depois de fazer upload dos objetos, confira se eles foram carregados corretamente. Você pode usar ListObjects para isso. Você usará a propriedade “Key”, mas também há outras propriedades úteis na resposta.

```
export const listFilesInBucket = async ({ bucketName }) => {
  const command = new ListObjectsCommand({ Bucket: bucketName });
  const { Contents } = await s3Client.send(command);
  const contentsList = Contents.map((c) => ` • ${c.Key}`).join("\n");
  console.log("\nHere's a list of files in the bucket:");
  console.log(contentsList + "\n");
};
```

Às vezes é necessário copiar um objeto de um bucket em outro. Use o CopyObject comando para isso.

```
export const copyFileFromBucket = async ({ destinationBucket }) => {
  const proceed = await prompter.confirm({
    message: "Would you like to copy an object from another bucket?",
  });

  if (!proceed) {
    return;
  } else {
    const copy = async () => {
      try {
        const sourceBucket = await prompter.input({
          message: "Enter source bucket name:",
        });
        const sourceKey = await prompter.input({
          message: "Enter source key:",
        });
        const destinationKey = await prompter.input({
          message: "Enter destination key:",
        });

        const command = new CopyObjectCommand({
```

```
          Bucket: destinationBucket,
          CopySource: `${sourceBucket}/${sourceKey}`,
          Key: destinationKey,
        });
        await s3Client.send(command);
        await copyFileFromBucket({ destinationBucket });
      } catch (err) {
        console.error(`Copy error.`);
        console.error(err);
        const retryAnswer = await prompter.confirm({ message: "Try again?" });
        if (retryAnswer) {
          await copy();
        }
      }
    };
    await copy();
  }
};
```

Não há um método de SDK para obter vários objetos de um bucket. Em vez disso, você criará uma lista de objetos para baixar e iterar sobre eles.

```
export const downloadFilesFromBucket = async ({ bucketName }) => {
  const { Contents } = await s3Client.send(
    new ListObjectsCommand({ Bucket: bucketName }),
  );
  const path = await prompter.input({
    message: "Enter destination path for files:",
  });

  for (let content of Contents) {
    const obj = await s3Client.send(
      new GetObjectCommand({ Bucket: bucketName, Key: content.Key }),
    );
    writeFileSync(
      `${path}/${content.Key}`,
      await obj.Body.transformToByteArray(),
    );
  }
  console.log("Files downloaded successfully.\n");
};
```

É hora de limpar seus recursos. Um bucket deve estar vazio para poder ser excluído. Essas duas funções esvaziam e excluem o bucket.

```
export const emptyBucket = async ({ bucketName }) => {
  const listObjectsCommand = new ListObjectsCommand({ Bucket: bucketName });
  const { Contents } = await s3Client.send(listObjectsCommand);
  const keys = Contents.map((c) => c.Key);

  const deleteObjectsCommand = new DeleteObjectsCommand({
    Bucket: bucketName,
    Delete: { Objects: keys.map((key) => ({ Key: key })) },
  });
  await s3Client.send(deleteObjectsCommand);
  console.log(`${bucketName} emptied successfully.\n`);
};

export const deleteBucket = async ({ bucketName }) => {
  const command = new DeleteBucketCommand({ Bucket: bucketName });
  await s3Client.send(command);
  console.log(`${bucketName} deleted successfully.\n`);
};
```

A função “principal” reúne tudo. Se você executar esse arquivo diretamente, a função principal será chamada.

```
const main = async () => {
  const OBJECT_DIRECTORY = `${dirnameFromMetaUrl(
    import.meta.url,
  )}../../../../resources/sample_files/.sample_media`;

  try {
    console.log(wrapText("Welcome to the Amazon S3 getting started example."));
    console.log("Let's create a bucket.");
    const bucketName = await createBucket();
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("File upload."));
    console.log(
      "I have some default files ready to go. You can edit the source code to
 provide your own.",
    );
    await uploadFilesToBucket({
```

```
      bucketName,
      folderPath: OBJECT_DIRECTORY,
    });

    await listFilesInBucket({ bucketName });
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("Copy files."));
    await copyFileFromBucket({ destinationBucket: bucketName });
    await listFilesInBucket({ bucketName });
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("Download files."));
    await downloadFilesFromBucket({ bucketName });

    console.log(wrapText("Clean up."));
    await emptyBucket({ bucketName });
    await deleteBucket({ bucketName });
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <bucketName> <key> <objectPath> <savePath> <toBucket>

    Where:
        bucketName - The Amazon S3 bucket to create.
        key - The key to use.
        objectPath - The path where the file is located (for example, C:/AWS/
book2.pdf).
        savePath - The path where the file is saved after it's downloaded (for
 example, C:/AWS/book2.pdf).
        toBucket - An Amazon S3 bucket to where an object is copied to (for
 example, C:/AWS/book2.pdf).
        """

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val bucketName = args[0]
    val key = args[1]
    val objectPath = args[2]
    val savePath = args[3]
    val toBucket = args[4]

    // Create an Amazon S3 bucket.
    createBucket(bucketName)

    // Update a local file to the Amazon S3 bucket.
    putObject(bucketName, key, objectPath)
```

```
    // Download the object to another local file.
    getObjectFromMrap(bucketName, key, savePath)

    // List all objects located in the Amazon S3 bucket.
    listBucketObs(bucketName)

    // Copy the object to another Amazon S3 bucket
    copyBucketOb(bucketName, key, toBucket)

    // Delete the object from the Amazon S3 bucket.
    deleteBucketObs(bucketName, key)

    // Delete the Amazon S3 bucket.
    deleteBucket(bucketName)
    println("All Amazon S3 operations were successfully performed")
}

suspend fun createBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}

suspend fun putObject(bucketName: String, objectKey: String, objectPath: String)
 {
    val metadataVal = mutableMapOf<String, String>()
    metadataVal["myVal"] = "test"

    val request = PutObjectRequest {
        bucket = bucketName
        key = objectKey
        metadata = metadataVal
        this.body = Paths.get(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.putObject(request)
        println("Tag information is ${response.eTag}")
```

```
    }
}

suspend fun getObjectFromMrap(bucketName: String, keyName: String, path: String)
 {
    val request = GetObjectRequest {
        key = keyName
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.getObject(request) { resp ->
            val myFile = File(path)
            resp.body?.writeToFile(myFile)
            println("Successfully read $keyName from $bucketName")
        }
    }
}

suspend fun listBucketObs(bucketName: String) {
    val request = ListObjectsRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->

        val response = s3.listObjects(request)
        response.contents?.forEach { myObject ->
            println("The name of the key is ${myObject.key}")
            println("The owner is ${myObject.owner}")
        }
    }
}

suspend fun copyBucketOb(fromBucket: String, objectKey: String, toBucket: String)
 {
    var encodedUrl = ""
    try {
        encodedUrl = URLEncoder.encode("$fromBucket/$objectKey",
 StandardCharsets.UTF_8.toString())
    } catch (e: UnsupportedEncodingException) {
        println("URL could not be encoded: " + e.message)
    }
```

```
    val request = CopyObjectRequest {
        copySource = encodedUrl
        bucket = toBucket
        key = objectKey
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.copyObject(request)
    }
}

suspend fun deleteBucketObs(bucketName: String, objectName: String) {
    val objectId = ObjectIdentifier {
        key = objectName
    }

    val delOb = Delete {
        objects = listOf(objectId)
    }

    val request = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteObjects(request)
        println("$objectName was deleted from $bucketName")
    }
}

suspend fun deleteBucket(bucketName: String?) {
    val request = DeleteBucketRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucket(request)
        println("The $bucketName was successfully deleted!")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.

- CopyObject
- CreateBucket
- DeleteBucket
- DeleteObjects
- GetObject
- ListObjectsV2
- PutObject

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon S3 getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $region = 'us-west-2';

        $this->s3client = new S3Client([
                'region' => $region,
        ]);
        /* Inline declaration example
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);
        */

        $this->bucketName = "doc-example-bucket-" . uniqid();

        try {
            $this->s3client->createBucket([
                'Bucket' => $this->bucketName,
                'CreateBucketConfiguration' => ['LocationConstraint' => $region],
            ]);
```

```
            echo "Created bucket named: $this->bucketName \n";
        } catch (Exception $exception) {
            echo "Failed to create bucket $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with bucket creation before continuing.");
        }

        $fileName = __DIR__ . "/local-file-" . uniqid();
        try {
            $this->s3client->putObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
                'SourceFile' => __DIR__ . '/testfile.txt'
            ]);
            echo "Uploaded $fileName to $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to upload $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with file upload before continuing.");
        }

        try {
            $file = $this->s3client->getObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
            ]);
            $body = $file->get('Body');
            $body->rewind();
            echo "Downloaded the file and it begins with: {$body->read(26)}.\n";
        } catch (Exception $exception) {
            echo "Failed to download $fileName from $this->bucketName with error:
 " . $exception->getMessage();
            exit("Please fix error with file downloading before continuing.");
        }

        try {
            $folder = "copied-folder";
            $this->s3client->copyObject([
                'Bucket' => $this->bucketName,
                'CopySource' => "$this->bucketName/$fileName",
                'Key' => "$folder/$fileName-copy",
            ]);
            echo "Copied $fileName to $folder/$fileName-copy.\n";
        } catch (Exception $exception) {
```

```
            echo "Failed to copy $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with object copying before continuing.");
        }

        try {
            $contents = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            echo "The contents of your bucket are: \n";
            foreach ($contents['Contents'] as $content) {
                echo $content['Key'] . "\n";
            }
        } catch (Exception $exception) {
            echo "Failed to list objects in $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with listing objects before continuing.");
        }

        try {
            $objects = [];
            foreach ($contents['Contents'] as $content) {
                $objects[] = [
                    'Key' => $content['Key'],
                ];
            }
            $this->s3client->deleteObjects([
                'Bucket' => $this->bucketName,
                'Delete' => [
                    'Objects' => $objects,
                ],
            ]);
            $check = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            if (count($check) <= 0) {
                throw new Exception("Bucket wasn't empty.");
            }
            echo "Deleted all objects and folders from $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $fileName from $this->bucketName with error:
 " . $exception->getMessage();
            exit("Please fix error with object deletion before continuing.");
        }
```

```
        try {
            $this->s3client->deleteBucket([
                'Bucket' => $this->bucketName,
            ]);
            echo "Deleted bucket $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $this->bucketName with error: " . $exception-
>getMessage();
            exit("Please fix error with bucket deletion before continuing.");
        }

        echo "Successfully ran the Amazon S3 with PHP demo.\n";
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import io
import os
```

```
import uuid

import boto3
from boto3.s3.transfer import S3UploadFailedError
from botocore.exceptions import ClientError


def do_scenario(s3_resource):
    print("-" * 88)
    print("Welcome to the Amazon S3 getting started demo!")
    print("-" * 88)

    bucket_name = f"doc-example-bucket-{uuid.uuid4()}"
    bucket = s3_resource.Bucket(bucket_name)
    try:
        bucket.create(
            CreateBucketConfiguration={
                "LocationConstraint": s3_resource.meta.client.meta.region_name
            }
        )
        print(f"Created demo bucket named {bucket.name}.")
    except ClientError as err:
        print(f"Tried and failed to create demo bucket {bucket_name}.")
        print(f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}")
        print(f"\nCan't continue the demo without a bucket!")
        return

    file_name = None
    while file_name is None:
        file_name = input("\nEnter a file you want to upload to your bucket: ")
        if not os.path.exists(file_name):
            print(f"Couldn't find file {file_name}. Are you sure it exists?")
            file_name = None

    obj = bucket.Object(os.path.basename(file_name))
    try:
        obj.upload_file(file_name)
        print(
            f"Uploaded file {file_name} into bucket {bucket.name} with key
 {obj.key}."
        )
    except S3UploadFailedError as err:
        print(f"Couldn't upload file {file_name} to {bucket.name}.")
```

```
        print(f"\t{err}")

    answer = input(f"\nDo you want to download {obj.key} into memory (y/n)? ")
    if answer.lower() == "y":
        data = io.BytesIO()
        try:
            obj.download_fileobj(data)
            data.seek(0)
            print(f"Got your object. Here are the first 20 bytes:\n")
            print(f"\t{data.read(20)}")
        except ClientError as err:
            print(f"Couldn't download {obj.key}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    answer = input(
        f"\nDo you want to copy {obj.key} to a subfolder in your bucket (y/n)? "
    )
    if answer.lower() == "y":
        dest_obj = bucket.Object(f"demo-folder/{obj.key}")
        try:
            dest_obj.copy({"Bucket": bucket.name, "Key": obj.key})
            print(f"Copied {obj.key} to {dest_obj.key}.")
        except ClientError as err:
            print(f"Couldn't copy {obj.key} to {dest_obj.key}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    print("\nYour bucket contains the following objects:")
    try:
        for o in bucket.objects.all():
            print(f"\t{o.key}")
    except ClientError as err:
        print(f"Couldn't list the objects in bucket {bucket.name}.")
        print(f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}")

    answer = input(
        "\nDo you want to delete all of the objects as well as the bucket (y/n)?
 "
```

```
    )
    if answer.lower() == "y":
        try:
            bucket.objects.delete()
            bucket.delete()
            print(f"Emptied and deleted bucket {bucket.name}.\n")
        except ClientError as err:
            print(f"Couldn't empty and delete bucket {bucket.name}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    do_scenario(boto3.resource("s3"))
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-s3"

# Wraps the getting started scenario actions.
class ScenarioGettingStarted
  attr_reader :s3_resource

  # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
  def initialize(s3_resource)
    @s3_resource = s3_resource
  end

  # Creates a bucket with a random name in the currently configured account and
  # AWS Region.
  #
  # @return [Aws::S3::Bucket] The newly created bucket.
  def create_bucket
    bucket = @s3_resource.create_bucket(
      bucket: "doc-example-bucket-#{Random.uuid}",
      create_bucket_configuration: {
        location_constraint: "us-east-1" # Note: only certain regions permitted
      }
    )
    puts("Created demo bucket named #{bucket.name}.")
  rescue Aws::Errors::ServiceError => e
    puts("Tried and failed to create demo bucket.")
    puts("\t#{e.code}: #{e.message}")
    puts("\nCan't continue the demo without a bucket!")
    raise
  else
    bucket
  end
```

```
  # Requests a file name from the user.
  #
  # @return The name of the file.
  def create_file
    File.open("demo.txt", w) { |f| f.write("This is a demo file.") }
  end

  # Uploads a file to an Amazon S3 bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket object representing the upload
destination
  # @return [Aws::S3::Object] The Amazon S3 object that contains the uploaded
file.
  def upload_file(bucket)
    File.open("demo.txt", "w+") { |f| f.write("This is a demo file.") }
    s3_object = bucket.object(File.basename("demo.txt"))
    s3_object.upload_file("demo.txt")
    puts("Uploaded file demo.txt into bucket #{bucket.name} with key
#{s3_object.key}.")
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't upload file demo.txt to #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    s3_object
  end

  # Downloads an Amazon S3 object to a file.
  #
  # @param s3_object [Aws::S3::Object] The object to download.
  def download_file(s3_object)
    puts("\nDo you want to download #{s3_object.key} to a local file (y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      puts("Enter a name for the downloaded file: ")
      file_name = gets.chomp
      s3_object.download_file(file_name)
      puts("Object #{s3_object.key} successfully downloaded to #{file_name}.")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't download #{s3_object.key}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

```
  # Copies an Amazon S3 object to a subfolder within the same bucket.
  #
  # @param source_object [Aws::S3::Object] The source object to copy.
  # @return [Aws::S3::Object, nil] The destination object.
  def copy_object(source_object)
    dest_object = nil
    puts("\nDo you want to copy #{source_object.key} to a subfolder in your
 bucket (y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      dest_object = source_object.bucket.object("demo-folder/
#{source_object.key}")
      dest_object.copy_from(source_object)
      puts("Copied #{source_object.key} to #{dest_object.key}.")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't copy #{source_object.key}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    dest_object
  end

  # Lists the objects in an Amazon S3 bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket to query.
  def list_objects(bucket)
    puts("\nYour bucket contains the following objects:")
    bucket.objects.each do |obj|
      puts("\t#{obj.key}")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't list the objects in bucket #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end

  # Deletes the objects in an Amazon S3 bucket and deletes the bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
  def delete_bucket(bucket)
    puts("\nDo you want to delete all of the objects as well as the bucket (y/n)?
 ")
```

```
    answer = gets.chomp.downcase
    if answer == "y"
      bucket.objects.batch_delete!
      bucket.delete
      puts("Emptied and deleted bucket #{bucket.name}.\n")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't empty and delete bucket #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
end

# Runs the Amazon S3 getting started scenario.
def run_scenario(scenario)
  puts("-" * 88)
  puts("Welcome to the Amazon S3 getting started demo!")
  puts("-" * 88)

  bucket = scenario.create_bucket
  s3_object = scenario.upload_file(bucket)
  scenario.download_file(s3_object)
  scenario.copy_object(s3_object)
  scenario.list_objects(bucket)
  scenario.delete_bucket(bucket)

  puts("Thanks for watching!")
  puts("-" * 88)
rescue Aws::Errors::ServiceError
  puts("Something went wrong with the demo!")
end

run_scenario(ScenarioGettingStarted.new(Aws::S3::Resource.new)) if $PROGRAM_NAME
 == __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects

- GetObject
- ListObjectsV2
- PutObject

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para a caixa binária que executa o cenário.

```
use aws_config::meta::region::RegionProviderChain;
use aws_sdk_s3::{config::Region, Client};
use s3_service::error::Error;
use uuid::Uuid;


#[tokio::main]
async fn main() -> Result<(), Error> {
    let (region, client, bucket_name, file_name, key, target_key) =
 initialize_variables().await;

    if let Err(e) = run_s3_operations(region, client, bucket_name, file_name,
 key, target_key).await
    {
        println!("{:?}", e);
    };

    Ok(())
}

async fn initialize_variables() -> (Region, Client, String, String, String,
 String) {
```

```
    let region_provider = RegionProviderChain::first_try(Region::new("us-
west-2"));
    let region = region_provider.region().await.unwrap();

    let shared_config =
 aws_config::from_env().region(region_provider).load().await;
    let client = Client::new(&shared_config);

    let bucket_name = format!("doc-example-bucket-{}", Uuid::new_v4());

    let file_name = "s3/testfile.txt".to_string();
    let key = "test file key name".to_string();
    let target_key = "target_key".to_string();

    (region, client, bucket_name, file_name, key, target_key)
}

async fn run_s3_operations(
    region: Region,
    client: Client,
    bucket_name: String,
    file_name: String,
    key: String,
    target_key: String,
) -> Result<(), Error> {
    s3_service::create_bucket(&client, &bucket_name, region.as_ref()).await?;
    s3_service::upload_object(&client, &bucket_name, &file_name, &key).await?;
    let _object = s3_service::download_object(&client, &bucket_name, &key).await;
    s3_service::copy_object(&client, &bucket_name, &key, &target_key).await?;
    s3_service::list_objects(&client, &bucket_name).await?;
    s3_service::delete_objects(&client, &bucket_name).await?;
    s3_service::delete_bucket(&client, &bucket_name).await?;

    Ok(())
}
```

Uma caixa de biblioteca com ações comuns chamadas pelo binário.

```
use aws_sdk_s3::operation::{
    copy_object::{CopyObjectError, CopyObjectOutput},
```

```
    create_bucket::{CreateBucketError, CreateBucketOutput},
    get_object::{GetObjectError, GetObjectOutput},
    list_objects_v2::ListObjectsV2Output,
    put_object::{PutObjectError, PutObjectOutput},
};
use aws_sdk_s3::types::{
    BucketLocationConstraint, CreateBucketConfiguration, Delete,
 ObjectIdentifier,
};
use aws_sdk_s3::{error::SdkError, primitives::ByteStream, Client};
use error::Error;
use std::path::Path;
use std::str;

pub mod error;

pub async fn delete_bucket(client: &Client, bucket_name: &str) -> Result<(),
 Error> {
    client.delete_bucket().bucket(bucket_name).send().await?;
    println!("Bucket deleted");
    Ok(())
}

pub async fn delete_objects(client: &Client, bucket_name: &str) ->
 Result<Vec<String>, Error> {
    let objects = client.list_objects_v2().bucket(bucket_name).send().await?;

    let mut delete_objects: Vec<ObjectIdentifier> = vec![];
    for obj in objects.contents() {
        let obj_id = ObjectIdentifier::builder()
            .set_key(Some(obj.key().unwrap().to_string()))
            .build()
            .map_err(Error::from)?;
        delete_objects.push(obj_id);
    }

    let return_keys = delete_objects.iter().map(|o| o.key.clone()).collect();

    if !delete_objects.is_empty() {
        client
            .delete_objects()
            .bucket(bucket_name)
            .delete(
                Delete::builder()
```

```
                    .set_objects(Some(delete_objects))
                    .build()
                    .map_err(Error::from)?,
            )
            .send()
            .await?;
    }

    let objects: ListObjectsV2Output =
 client.list_objects_v2().bucket(bucket_name).send().await?;

    eprintln!("{objects:?}");

    match objects.key_count {
        Some(0) => Ok(return_keys),
        _ => Err(Error::unhandled(
            "There were still objects left in the bucket.",
        )),
    }
}

pub async fn list_objects(client: &Client, bucket: &str) -> Result<(), Error> {
    let mut response = client
        .list_objects_v2()
        .bucket(bucket.to_owned())
        .max_keys(10) // In this example, go 10 at a time.
        .into_paginator()
        .send();

    while let Some(result) = response.next().await {
        match result {
            Ok(output) => {
                for object in output.contents() {
                    println!(" - {}", object.key().unwrap_or("Unknown"));
                }
            }
            Err(err) => {
                eprintln!("{err:?}")
            }
        }
    }

    Ok(())
}
```

```
pub async fn copy_object(
    client: &Client,
    bucket_name: &str,
    object_key: &str,
    target_key: &str,
) -> Result<CopyObjectOutput, SdkError<CopyObjectError>> {
    let mut source_bucket_and_object: String = "".to_owned();
    source_bucket_and_object.push_str(bucket_name);
    source_bucket_and_object.push('/');
    source_bucket_and_object.push_str(object_key);

    client
        .copy_object()
        .copy_source(source_bucket_and_object)
        .bucket(bucket_name)
        .key(target_key)
        .send()
        .await
}

pub async fn download_object(
    client: &Client,
    bucket_name: &str,
    key: &str,
) -> Result<GetObjectOutput, SdkError<GetObjectError>> {
    client
        .get_object()
        .bucket(bucket_name)
        .key(key)
        .send()
        .await
}

pub async fn upload_object(
    client: &Client,
    bucket_name: &str,
    file_name: &str,
    key: &str,
) -> Result<PutObjectOutput, SdkError<PutObjectError>> {
    let body = ByteStream::from_path(Path::new(file_name)).await;
    client
        .put_object()
        .bucket(bucket_name)
```

```
        .key(key)
        .body(body.unwrap())
        .send()
        .await
}

pub async fn create_bucket(
    client: &Client,
    bucket_name: &str,
    region: &str,
) -> Result<CreateBucketOutput, SdkError<CreateBucketError>> {
    let constraint = BucketLocationConstraint::from(region);
    let cfg = CreateBucketConfiguration::builder()
        .location_constraint(constraint)
        .build();
    client
        .create_bucket()
        .create_bucket_configuration(cfg)
        .bucket(bucket_name)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
DATA(lo_session) = /aws1/cl_rt_session_aws=>create( cv_pfl ).
DATA(lo_s3) = /aws1/cl_s3_factory=>create( lo_session ).

" Create an Amazon Simple Storage Service (Amazon S3) bucket. "
TRY.
    lo_s3->createbucket(
        iv_bucket = iv_bucket_name
    ).
    MESSAGE 'S3 bucket created.' TYPE 'I'.
  CATCH /aws1/cx_s3_bucketalrdyexists.
    MESSAGE 'Bucket name already exists.' TYPE 'E'.
  CATCH /aws1/cx_s3_bktalrdyownedbyyou.
    MESSAGE 'Bucket already exists and is owned by you.' TYPE 'E'.
ENDTRY.


"Upload an object to an S3 bucket."
TRY.
    "Get contents of file from application server."
    DATA lv_file_content TYPE xstring.
    OPEN DATASET iv_key FOR INPUT IN BINARY MODE.
    READ DATASET iv_key INTO lv_file_content.
    CLOSE DATASET iv_key.

    lo_s3->putobject(
        iv_bucket = iv_bucket_name
        iv_key = iv_key
        iv_body = lv_file_content
    ).
    MESSAGE 'Object uploaded to S3 bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
```

```
    ENDTRY.

    " Get an object from a bucket. "
    TRY.
        DATA(lo_result) = lo_s3->getobject(
                   iv_bucket = iv_bucket_name
                   iv_key = iv_key
                ).
        DATA(lv_object_data) = lo_result->get_body( ).
        MESSAGE 'Object retrieved from S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
      CATCH /aws1/cx_s3_nosuchkey.
        MESSAGE 'Object key does not exist.' TYPE 'E'.
    ENDTRY.

    " Copy an object to a subfolder in a bucket. "
    TRY.
        lo_s3->copyobject(
          iv_bucket = iv_bucket_name
          iv_key = |{ iv_copy_to_folder }/{ iv_key }|
          iv_copysource = |{ iv_bucket_name }/{ iv_key }|
        ).
        MESSAGE 'Object copied to a subfolder.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
      CATCH /aws1/cx_s3_nosuchkey.
        MESSAGE 'Object key does not exist.' TYPE 'E'.
    ENDTRY.

    " List objects in the bucket. "
    TRY.
        DATA(lo_list) = lo_s3->listobjects(
           iv_bucket = iv_bucket_name
         ).
        MESSAGE 'Retrieved list of objects in S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
    DATA text TYPE string VALUE 'Object List - '.
    DATA lv_object_key TYPE /aws1/s3_objectkey.
    LOOP AT lo_list->get_contents( ) INTO DATA(lo_object).
      lv_object_key = lo_object->get_key( ).
      CONCATENATE lv_object_key ', ' INTO text.
```

```
    ENDLOOP.
    MESSAGE text TYPE'I'.

    " Delete the objects in a bucket. "
    TRY.
        lo_s3->deleteobject(
            iv_bucket = iv_bucket_name
            iv_key = iv_key
        ).
        lo_s3->deleteobject(
            iv_bucket = iv_bucket_name
            iv_key = |{ iv_copy_to_folder }/{ iv_key }|
        ).
        MESSAGE 'Objects deleted from S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.


    " Delete the bucket. "
    TRY.
        lo_s3->deletebucket(
            iv_bucket = iv_bucket_name
        ).
        MESSAGE 'Deleted S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma classe Swift que gerencia chamadas para o SDK para Swift.

```
import Foundation
import AWSS3
import ClientRuntime
import AWSClientRuntime

/// A class containing all the code that interacts with the AWS SDK for Swift.
public class ServiceHandler {
    let client: S3Client

    /// Initialize and return a new ``ServiceHandler`` object, which is used to
 drive the AWS calls
    /// used for the example.
    ///
    /// - Returns: A new ``ServiceHandler`` object, ready to be called to
    ///            execute AWS operations.
    public init() async {
        do {
            client = try S3Client(region: "us-east-2")
        } catch {
            print("ERROR: ", dump(error, name: "Initializing S3 client"))
            exit(1)
        }
    }
```

```
    /// Create a new user given the specified name.
    ///
    /// - Parameters:
    ///   - name: Name of the bucket to create.
    /// Throws an exception if an error occurs.
    public func createBucket(name: String) async throws {
        let config = S3ClientTypes.CreateBucketConfiguration(
            locationConstraint: .usEast2
        )
        let input = CreateBucketInput(
            bucket: name,
            createBucketConfiguration: config
        )
        _ = try await client.createBucket(input: input)
    }

    /// Delete a bucket.
    /// - Parameter name: Name of the bucket to delete.
    public func deleteBucket(name: String) async throws {
        let input = DeleteBucketInput(
            bucket: name
        )
        _ = try await client.deleteBucket(input: input)
    }

    /// Upload a file from local storage to the bucket.
    /// - Parameters:
    ///   - bucket: Name of the bucket to upload the file to.
    ///   - key: Name of the file to create.
    ///   - file: Path name of the file to upload.
    public func uploadFile(bucket: String, key: String, file: String) async
throws {
        let fileUrl = URL(fileURLWithPath: file)
        let fileData = try Data(contentsOf: fileUrl)
        let dataStream = ByteStream.from(data: fileData)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }
```

```
    /// Create a file in the specified bucket with the given name. The new
    /// file's contents are uploaded from a `Data` object.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket to create a file in.
    ///   - key: Name of the file to create.
    ///   - data: A `Data` object to write into the new file.
    public func createFile(bucket: String, key: String, withData data: Data)
 async throws {
        let dataStream = ByteStream.from(data: data)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }

    /// Download the named file to the given directory on the local device.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket that contains the file to be copied.
    ///   - key: The name of the file to copy from the bucket.
    ///   - to: The path of the directory on the local device where you want to
    ///     download the file.
    public func downloadFile(bucket: String, key: String, to: String) async
 throws {
        let fileUrl = URL(fileURLWithPath: to).appendingPathComponent(key)

        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the data stream object. Return immediately if there isn't one.
        guard let body = output.body,
              let data = try await body.readData() else {
            return
        }
        try data.write(to: fileUrl)
    }
```

```
    /// Read the specified file from the given S3 bucket into a Swift
    /// `Data` object.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket containing the file to read.
    ///   - key: Name of the file within the bucket to read.
    ///
    /// - Returns: A `Data` object containing the complete file data.
    public func readFile(bucket: String, key: String) async throws -> Data {
        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the stream and return its contents in a `Data` object. If
        // there is no stream, return an empty `Data` object instead.
        guard let body = output.body,
              let data = try await body.readData() else {
            return "".data(using: .utf8)!
        }

        return data
    }

    /// Copy a file from one bucket to another.
    ///
    /// - Parameters:
    ///   - sourceBucket: Name of the bucket containing the source file.
    ///   - name: Name of the source file.
    ///   - destBucket: Name of the bucket to copy the file into.
    public func copyFile(from sourceBucket: String, name: String, to destBucket:
 String) async throws {
        let srcUrl = ("\(sourceBucket)/
\(name)").addingPercentEncoding(withAllowedCharacters: .urlPathAllowed)

        let input = CopyObjectInput(
            bucket: destBucket,
            copySource: srcUrl,
            key: name
        )
        _ = try await client.copyObject(input: input)
    }
```

```
    /// Deletes the specified file from Amazon S3.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket containing the file to delete.
    ///   - key: Name of the file to delete.
    ///
    public func deleteFile(bucket: String, key: String) async throws {
        let input = DeleteObjectInput(
            bucket: bucket,
            key: key
        )

        do {
            _ = try await client.deleteObject(input: input)
        } catch {
            throw error
        }
    }

    /// Returns an array of strings, each naming one file in the
    /// specified bucket.
    ///
    /// - Parameter bucket: Name of the bucket to get a file listing for.
    /// - Returns: An array of `String` objects, each giving the name of
    ///            one file contained in the bucket.
    public func listBucketFiles(bucket: String) async throws -> [String] {
        let input = ListObjectsV2Input(
            bucket: bucket
        )
        let output = try await client.listObjectsV2(input: input)
        var names: [String] = []

        guard let objList = output.contents else {
            return []
        }

        for obj in objList {
            if let objName = obj.key {
                names.append(objName)
            }
        }

        return names
    }
```

```
}
```

Um programa de linha de comando Swift para gerenciar as chamadas do SDK.

```
import Foundation
import ServiceHandler
import ArgumentParser

/// The command-line arguments and options available for this
/// example command.
struct ExampleCommand: ParsableCommand {
    @Argument(help: "Name of the S3 bucket to create")
    var bucketName: String

    @Argument(help: "Pathname of the file to upload to the S3 bucket")
    var uploadSource: String

    @Argument(help: "The name (key) to give the file in the S3 bucket")
    var objName: String

    @Argument(help: "S3 bucket to copy the object to")
    var destBucket: String

    @Argument(help: "Directory where you want to download the file from the S3
 bucket")
    var downloadDir: String

    static var configuration = CommandConfiguration(
        commandName: "s3-basics",
        abstract: "Demonstrates a series of basic AWS S3 functions.",
        discussion: """
        Performs the following Amazon S3 commands:

        * `CreateBucket`
        * `PutObject`
        * `GetObject`
        * `CopyObject`
        * `ListObjects`
        * `DeleteObjects`
        * `DeleteBucket`
        """
    )
```

```
    /// Called by ``main()`` to do the actual running of the AWS
    /// example.
    func runAsync() async throws {
        let serviceHandler = await ServiceHandler()

        // 1. Create the bucket.
        print("Creating the bucket \(bucketName)...")
        try await serviceHandler.createBucket(name: bucketName)

        // 2. Upload a file to the bucket.
        print("Uploading the file \(uploadSource)...")
        try await serviceHandler.uploadFile(bucket: bucketName, key: objName,
file: uploadSource)

        // 3. Download the file.
        print("Downloading the file \(objName) to \(downloadDir)...")
        try await serviceHandler.downloadFile(bucket: bucketName, key: objName,
to: downloadDir)

        // 4. Copy the file to another bucket.
        print("Copying the file to the bucket \(destBucket)...")
        try await serviceHandler.copyFile(from: bucketName, name: objName, to:
destBucket)

        // 5. List the contents of the bucket.

        print("Getting a list of the files in the bucket \(bucketName)")
        let fileList = try await serviceHandler.listBucketFiles(bucket:
bucketName)
        let numFiles = fileList.count
        if numFiles != 0 {
            print("\(numFiles) file\((numFiles > 1) ? "s" : "") in bucket
\(bucketName):")
            for name in fileList {
                print("  \(name)")
            }
        } else {
            print("No files found in bucket \(bucketName)")
        }

        // 6. Delete the objects from the bucket.

        print("Deleting the file \(objName) from the bucket \(bucketName)...")
```

```
        try await serviceHandler.deleteFile(bucket: bucketName, key: objName)
        print("Deleting the file \(objName) from the bucket \(destBucket)...")
        try await serviceHandler.deleteFile(bucket: destBucket, key: objName)

        // 7. Delete the bucket.
        print("Deleting the bucket \(bucketName)...")
        try await serviceHandler.deleteBucket(name: bucketName)

        print("Done.")
    }
}

//
// Main program entry point.
//
@main
struct Main {
    static func main() async {
        let args = Array(CommandLine.arguments.dropFirst())

        do {
            let command = try ExampleCommand.parse(args)
            try await command.runAsync()
        } catch {
            ExampleCommand.exit(withError: error)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Conceitos básicos de criptografia para objetos do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como começar a usar a criptografia de objetos do Amazon S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
using System;
using System.IO;
using System.Security.Cryptography;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to apply client encryption to an object in an
/// Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class SSEClientEncryption
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";
        string keyName = "exampleobject.txt";
        string copyTargetKeyName = "examplecopy.txt";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USWest2.
        IAmazonS3 client = new AmazonS3Client();

        try
        {
            // Create an encryption key.
```

```
                Aes aesEncryption = Aes.Create();
                aesEncryption.KeySize = 256;
                aesEncryption.GenerateKey();
                string base64Key = Convert.ToBase64String(aesEncryption.Key);

                // Upload the object.
                PutObjectRequest putObjectRequest = await
UploadObjectAsync(client, bucketName, keyName, base64Key);

                // Download the object and verify that its contents match what
you uploaded.
                await DownloadObjectAsync(client, bucketName, keyName, base64Key,
putObjectRequest);

                // Get object metadata and verify that the object uses AES-256
encryption.
                await GetObjectMetadataAsync(client, bucketName, keyName,
base64Key);

                // Copy both the source and target objects using server-side
encryption with
                // an encryption key.
                await CopyObjectAsync(client, bucketName, keyName,
copyTargetKeyName, aesEncryption, base64Key);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }

        /// <summary>
        /// Uploads an object to an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// PutObjectAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to which
the
        /// object will be uploaded.</param>
        /// <param name="keyName">The name of the object to upload to the Amazon
S3
        /// bucket.</param>
        /// <param name="base64Key">The encryption key.</param>
```

```
        /// <returns>The PutObjectRequest object for use by
 DownloadObjectAsync.</returns>
        public static async Task<PutObjectRequest> UploadObjectAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string base64Key)
        {
            PutObjectRequest putObjectRequest = new PutObjectRequest
            {
                BucketName = bucketName,
                Key = keyName,
                ContentBody = "sample text",
                ServerSideEncryptionCustomerMethod =
 ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };
            PutObjectResponse putObjectResponse = await
 client.PutObjectAsync(putObjectRequest);
            return putObjectRequest;
        }

        /// <summary>
        /// Downloads an encrypted object from an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// GetObjectAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
 object
        /// is located.</param>
        /// <param name="keyName">The name of the Amazon S3 object to download.</
param>
        /// <param name="base64Key">The encryption key used to encrypt the
        /// object.</param>
        /// <param name="putObjectRequest">The PutObjectRequest used to upload
        /// the object.</param>
        public static async Task DownloadObjectAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string base64Key,
            PutObjectRequest putObjectRequest)
        {
```

```
            GetObjectRequest getObjectRequest = new GetObjectRequest
            {
                BucketName = bucketName,
                Key = keyName,

                // Provide encryption information for the object stored in Amazon
S3.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };

            using (GetObjectResponse getResponse = await
client.GetObjectAsync(getObjectRequest))
            using (StreamReader reader = new
StreamReader(getResponse.ResponseStream))
            {
                string content = reader.ReadToEnd();
                if (string.Compare(putObjectRequest.ContentBody, content) == 0)
                {
                    Console.WriteLine("Object content is same as we uploaded");
                }
                else
                {
                    Console.WriteLine("Error...Object content is not same.");
                }

                if (getResponse.ServerSideEncryptionCustomerMethod ==
ServerSideEncryptionCustomerMethod.AES256)
                {
                    Console.WriteLine("Object encryption method is AES256, same
as we set");
                }
                else
                {
                    Console.WriteLine("Error...Object encryption method is not
the same as AES256 we set");
                }
            }
        }

        /// <summary>
        /// Retrieves the metadata associated with an Amazon S3 object.
        /// </summary>
```

```
        /// <param name="client">The initialized Amazon S3 client object used
        /// to call GetObjectMetadataAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket containing
the
        /// object for which we want to retrieve metadata.</param>
        /// <param name="keyName">The name of the object for which we wish to
        /// retrieve the metadata.</param>
        /// <param name="base64Key">The encryption key associated with the
        /// object.</param>
        public static async Task GetObjectMetadataAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string base64Key)
        {
            GetObjectMetadataRequest getObjectMetadataRequest = new
GetObjectMetadataRequest
            {
                BucketName = bucketName,
                Key = keyName,

                // The object stored in Amazon S3 is encrypted, so provide the
necessary encryption information.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };

            GetObjectMetadataResponse getObjectMetadataResponse = await
client.GetObjectMetadataAsync(getObjectMetadataRequest);
            Console.WriteLine("The object metadata show encryption method used
is: {0}", getObjectMetadataResponse.ServerSideEncryptionCustomerMethod);
        }

        /// <summary>
        /// Copies an encrypted object from one Amazon S3 bucket to another.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// CopyObjectAsync.</param>
        /// <param name="bucketName">The Amazon S3 bucket containing the object
        /// to copy.</param>
        /// <param name="keyName">The name of the object to copy.</param>
```

```
        /// <param name="copyTargetKeyName">The Amazon S3 bucket to which the
object
        /// will be copied.</param>
        /// <param name="aesEncryption">The encryption type to use.</param>
        /// <param name="base64Key">The encryption key to use.</param>
        public static async Task CopyObjectAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string copyTargetKeyName,
            Aes aesEncryption,
            string base64Key)
        {
            aesEncryption.GenerateKey();
            string copyBase64Key = Convert.ToBase64String(aesEncryption.Key);

            CopyObjectRequest copyRequest = new CopyObjectRequest
            {
                SourceBucket = bucketName,
                SourceKey = keyName,
                DestinationBucket = bucketName,
                DestinationKey = copyTargetKeyName,

                // Information about the source object's encryption.
                CopySourceServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                CopySourceServerSideEncryptionCustomerProvidedKey = base64Key,

                // Information about the target object's encryption.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = copyBase64Key,
            };
            await client.CopyObjectAsync(copyRequest);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CopyObject

- GetObject
- GetObjectMetadata

Conceitos básicos de etiquetas para objetos do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como começar a usar etiquetas de objetos do Amazon S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to work with tags in Amazon Simple Storage
/// Service (Amazon S3) objects.
/// </summary>
public class ObjectTag
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";
        string keyName = "newobject.txt";
        string filePath = @"*** file path ***";

        // Specify your bucket region (an example region is shown).
        RegionEndpoint bucketRegion = RegionEndpoint.USWest2;

        var client = new AmazonS3Client(bucketRegion);
        await PutObjectsWithTagsAsync(client, bucketName, keyName, filePath);
```

```
        }

        /// <summary>
        /// This method uploads an object with tags. It then shows the tag
        /// values, changes the tags, and shows the new tags.
        /// </summary>
        /// <param name="client">The Initialized Amazon S3 client object used
        /// to call the methods to create and change an objects tags.</param>
        /// <param name="bucketName">A string representing the name of the
        /// bucket where the object will be stored.</param>
        /// <param name="keyName">A string representing the key name of the
        /// object to be tagged.</param>
        /// <param name="filePath">The directory location and file name of the
        /// object to be uploaded to the Amazon S3 bucket.</param>
        public static async Task PutObjectsWithTagsAsync(IAmazonS3 client, string
bucketName, string keyName, string filePath)
        {
            try
            {
                // Create an object with tags.
                var putRequest = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                    FilePath = filePath,
                    TagSet = new List<Tag>
                    {
                        new Tag { Key = "Keyx1", Value = "Value1" },
                        new Tag { Key = "Keyx2", Value = "Value2" },
                    },
                };

                PutObjectResponse response = await
client.PutObjectAsync(putRequest);

                // Now retrieve the new object's tags.
                GetObjectTaggingRequest getTagsRequest = new
GetObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                };
```

```
                GetObjectTaggingResponse objectTags = await
client.GetObjectTaggingAsync(getTagsRequest);

                // Display the tag values.
                objectTags.Tagging
                    .ForEach(t => Console.WriteLine($"Key: {t.Key}, Value:
{t.Value}"));

                Tagging newTagSet = new Tagging()
                {
                    TagSet = new List<Tag>
                    {
                        new Tag { Key = "Key3", Value = "Value3" },
                        new Tag { Key = "Key4", Value = "Value4" },
                    },
                };

                PutObjectTaggingRequest putObjTagsRequest = new
PutObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                    Tagging = newTagSet,
                };

                PutObjectTaggingResponse response2 = await
client.PutObjectTaggingAsync(putObjTagsRequest);

                // Retrieve the tags again and show the values.
                GetObjectTaggingRequest getTagsRequest2 = new
GetObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                };
                GetObjectTaggingResponse objectTags2 = await
client.GetObjectTaggingAsync(getTagsRequest2);

                objectTags2.Tagging
                    .ForEach(t => Console.WriteLine($"Key: {t.Key}, Value:
{t.Value}"));
            }
            catch (AmazonS3Exception ex)
            {
```

```
                Console.WriteLine(
                        $"Error: '{ex.Message}'");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetObjectTaggingga Referência AWS SDK for .NET da API.

Gerenciar listas de controle de acesso (ACLs) para buckets do Amazon S3 usando um AWS SDK

Os exemplos de código a seguir mostram como gerenciar listas de controle de acesso (ACLs) para buckets do Amazon S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to manage Amazon Simple Storage Service
/// (Amazon S3) access control lists (ACLs) to control Amazon S3 bucket
/// access.
/// </summary>
public class ManageACLs
{
    public static async Task Main()
```

```
        {
            string bucketName = "doc-example-bucket1";
            string newBucketName = "doc-example-bucket2";
            string keyName = "sample-object.txt";
            string emailAddress = "someone@example.com";

            // If the AWS Region where your bucket is located is different from
            // the Region defined for the default user, pass the Amazon S3
bucket's
            // name to the client constructor. It should look like this:
            // RegionEndpoint bucketRegion = RegionEndpoint.USEast1;
            IAmazonS3 client = new AmazonS3Client();

            await TestBucketObjectACLsAsync(client, bucketName, newBucketName,
keyName, emailAddress);
        }

        /// <summary>
        /// Creates a new Amazon S3 bucket with a canned ACL, then retrieves the
ACL
        /// information and then adds a new ACL to one of the objects in the
        /// Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// methods to create a bucket, get an ACL, and add a different ACL to
        /// one of the objects.</param>
        /// <param name="bucketName">A string representing the original Amazon S3
        /// bucket name.</param>
        /// <param name="newBucketName">A string representing the name of the
        /// new bucket that will be created.</param>
        /// <param name="keyName">A string representing the key name of an Amazon
S3
        /// object for which we will change the ACL.</param>
        /// <param name="emailAddress">A string representing the email address
        /// belonging to the person to whom access to the Amazon S3 bucket will
be
        /// granted.</param>
        public static async Task TestBucketObjectACLsAsync(
            IAmazonS3 client,
            string bucketName,
            string newBucketName,
            string keyName,
            string emailAddress)
```

```
        {
            try
            {
                // Create a new Amazon S3 bucket and specify canned ACL.
                var success = await CreateBucketWithCannedACLAsync(client,
 newBucketName);

                // Get the ACL on a bucket.
                await GetBucketACLAsync(client, bucketName);

                // Add (replace) the ACL on an object in a bucket.
                await AddACLToExistingObjectAsync(client, bucketName, keyName,
 emailAddress);
            }
            catch (AmazonS3Exception amazonS3Exception)
            {
                Console.WriteLine($"Exception: {amazonS3Exception.Message}");
            }
        }

        /// <summary>
        /// Creates a new Amazon S3 bucket with a canned ACL attached.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="newBucketName">A string representing the name of the
        /// new Amazon S3 bucket.</param>
        /// <returns>Returns a boolean value indicating success or failure.</
returns>
        public static async Task<bool> CreateBucketWithCannedACLAsync(IAmazonS3
 client, string newBucketName)
        {
            var request = new PutBucketRequest()
            {
                BucketName = newBucketName,
                BucketRegion = S3Region.EUWest1,

                // Add a canned ACL.
                CannedACL = S3CannedACL.LogDeliveryWrite,
            };

            var response = await client.PutBucketAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

```
        /// <summary>
        /// Retrieves the ACL associated with the Amazon S3 bucket name in the
        /// bucketName parameter.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="bucketName">The Amazon S3 bucket for which we want to
 get the
        /// ACL list.</param>
        /// <returns>Returns an S3AccessControlList returned from the call to
        /// GetACLAsync.</returns>
        public static async Task<S3AccessControlList> GetBucketACLAsync(IAmazonS3
 client, string bucketName)
        {
            GetACLResponse response = await client.GetACLAsync(new GetACLRequest
            {
                BucketName = bucketName,
            });

            return response.AccessControlList;
        }



        /// <summary>
        /// Adds a new ACL to an existing object in the Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="bucketName">A string representing the name of the Amazon
 S3
        /// bucket containing the object to which we want to apply a new ACL.</
param>
        /// <param name="keyName">A string representing the name of the object
        /// to which we want to apply the new ACL.</param>
        /// <param name="emailAddress">The email address of the person to whom
        /// we will be applying to whom access will be granted.</param>
        public static async Task AddACLToExistingObjectAsync(IAmazonS3 client,
 string bucketName, string keyName, string emailAddress)
        {
            // Retrieve the ACL for an object.
```

```
            GetACLResponse aclResponse = await client.GetACLAsync(new
 GetACLRequest
            {
                BucketName = bucketName,
                Key = keyName,
            });

            S3AccessControlList acl = aclResponse.AccessControlList;

            // Retrieve the owner.
            Owner owner = acl.Owner;

            // Clear existing grants.
            acl.Grants.Clear();

            // Add a grant to reset the owner's full permission
            // (the previous clear statement removed all permissions).
            var fullControlGrant = new S3Grant
            {
                Grantee = new S3Grantee { CanonicalUser = acl.Owner.Id },
            };
            acl.AddGrant(fullControlGrant.Grantee, S3Permission.FULL_CONTROL);

            // Specify email to identify grantee for granting permissions.
            var grantUsingEmail = new S3Grant
            {
                Grantee = new S3Grantee { EmailAddress = emailAddress },
                Permission = S3Permission.WRITE_ACP,
            };

            // Specify log delivery group as grantee.
            var grantLogDeliveryGroup = new S3Grant
            {
                Grantee = new S3Grantee { URI = "http://acs.amazonaws.com/groups/
s3/LogDelivery" },
                Permission = S3Permission.WRITE,
            };

            // Create a new ACL.
            var newAcl = new S3AccessControlList
            {
                Grants = new List<S3Grant> { grantUsingEmail,
 grantLogDeliveryGroup },
                Owner = owner,
```

```
            };

            // Set the new ACL. We're throwing away the response here.
            _ = await client.PutACLAsync(new PutACLRequest
            {
                BucketName = bucketName,
                Key = keyName,
                AccessControlList = newAcl,
            });
        }

    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - GetBucketAcl
  - GetObjectAcl
  - PutBucketAcl
  - PutObjectAcl

Gerenciar objetos do Amazon S3 versionados em lotes com uma função do Lambda usando um AWS SDK

O exemplo de código a seguir mostra como gerenciar objetos do S3 versionados em lotes com uma função do Lambda.

Python

SDK para Python (Boto3)

Mostra como manipular objetos do Amazon Simple Storage Service (Amazon S3) versionados em lotes criando trabalhos que chamam funções do AWS Lambda para executar o processamento. Este exemplo cria um bucket habilitado para versão, carrega as estrofes do poema Você é velho, padre William, de Lewis Carroll, e usa trabalhos em lote do Amazon S3 para distorcer o poema de várias maneiras.

Aprenda como:

- Criar funções do Lambda que operam em objetos versionados.
- Criar um manifesto de objetos para atualizar.
- Cria trabalhos em lote que invocam funções do Lambda para atualizar objetos.
- Excluir funções do Lambda
- Esvaziar e excluir um bucket versionado.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3

Analisar URIs do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como usar analisar URIs do Amazon S3 para extrair componentes importantes como o nome do bucket e a chave do objeto.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Analise um URI do Amazon S3 usando a classe S3Uri.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.S3Uri;
import software.amazon.awssdk.services.s3.S3Utilities;

import java.net.URI;
import java.util.List;
```

```
import java.util.Map;

    /**
     *
     * @param s3Client    - An S3Client through which you acquire an S3Uri
 instance.
     * @param s3ObjectUrl - A complex URL (String) that is used to demonstrate
 S3Uri
     *                    capabilities.
     */
    public static void parseS3UriExample(S3Client s3Client, String s3ObjectUrl) {
        logger.info(s3ObjectUrl);
        // Console output:
        // 'https://s3.us-west-1.amazonaws.com/myBucket/resources/doc.txt?
versionId=abc123&partNumber=77&partNumber=88'.

        // Create an S3Utilities object using the configuration of the s3Client.
        S3Utilities s3Utilities = s3Client.utilities();

        // From a String URL create a URI object to pass to the parseUri()
 method.
        URI uri = URI.create(s3ObjectUrl);
        S3Uri s3Uri = s3Utilities.parseUri(uri);

        // If the URI contains no value for the Region, bucket or key, the SDK
 returns
        // an empty Optional.
        // The SDK returns decoded URI values.

        Region region = s3Uri.region().orElse(null);
        log("region", region);
        // Console output: 'region: us-west-1'.

        String bucket = s3Uri.bucket().orElse(null);
        log("bucket", bucket);
        // Console output: 'bucket: myBucket'.

        String key = s3Uri.key().orElse(null);
        log("key", key);
        // Console output: 'key: resources/doc.txt'.

        Boolean isPathStyle = s3Uri.isPathStyle();
        log("isPathStyle", isPathStyle);
        // Console output: 'isPathStyle: true'.
```

```
        // If the URI contains no query parameters, the SDK returns an empty map.
        Map<String, List<String>> queryParams = s3Uri.rawQueryParameters();
        log("rawQueryParameters", queryParams);
        // Console output: 'rawQueryParameters: {versionId=[abc123],
 partNumber=[77,
        // 88]}'.

        // Retrieve the first or all values for a query parameter as shown in the
        // following code.
        String versionId =
 s3Uri.firstMatchingRawQueryParameter("versionId").orElse(null);
        log("firstMatchingRawQueryParameter-versionId", versionId);
        // Console output: 'firstMatchingRawQueryParameter-versionId: abc123'.

        String partNumber =
 s3Uri.firstMatchingRawQueryParameter("partNumber").orElse(null);
        log("firstMatchingRawQueryParameter-partNumber", partNumber);
        // Console output: 'firstMatchingRawQueryParameter-partNumber: 77'.

        List<String> partNumbers =
 s3Uri.firstMatchingRawQueryParameters("partNumber");
        log("firstMatchingRawQueryParameter", partNumbers);
        // Console output: 'firstMatchingRawQueryParameter: [77, 88]'.

        /*
         * Object keys and query parameters with reserved or unsafe characters,
 must be
         * URL-encoded.
         * For example replace whitespace " " with "%20".
         * Valid:
         * "https://s3.us-west-1.amazonaws.com/myBucket/object%20key?query=
%5Bbrackets%5D"
         * Invalid:
         * "https://s3.us-west-1.amazonaws.com/myBucket/object key?
query=[brackets]"
         *
         * Virtual-hosted-style URIs with bucket names that contain a dot, ".",
 the dot
         * must not be URL-encoded.
         * Valid: "https://my.Bucket.s3.us-west-1.amazonaws.com/key"
         * Invalid: "https://my%2EBucket.s3.us-west-1.amazonaws.com/key"
         */
    }
```

```
    private static void log(String s3UriElement, Object element) {
        if (element == null) {
            logger.info("{}: {}", s3UriElement, "null");
        } else {
            logger.info("{}: {}", s3UriElement, element.toString());
        }
    }
```

Executar uma cópia multipart de um objeto do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como executar uma cópia multipart de um objeto do Amazon S3.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to perform a multi-part copy from one Amazon
    /// Simple Storage Service (Amazon S3) bucket to another.
    /// </summary>
    public class MPUapiCopyObj
    {
        private const string SourceBucket = "doc-example-bucket1";
        private const string TargetBucket = "doc-example-bucket2";
        private const string SourceObjectKey = "example.mov";
        private const string TargetObjectKey = "copied_video_file.mov";
```

```
        /// <summary>
        /// This method starts the multi-part upload.
        /// </summary>
        public static async Task Main()
        {
            var s3Client = new AmazonS3Client();
            Console.WriteLine("Copying object...");
            await MPUCopyObjectAsync(s3Client);
        }

        /// <summary>
        /// This method uses the passed client object to perform a multipart
        /// copy operation.
        /// </summary>
        /// <param name="client">An Amazon S3 client object that will be used
        /// to perform the copy.</param>
        public static async Task MPUCopyObjectAsync(AmazonS3Client client)
        {
            // Create a list to store the copy part responses.
            var copyResponses = new List<CopyPartResponse>();

            // Setup information required to initiate the multipart upload.
            var initiateRequest = new InitiateMultipartUploadRequest
            {
                BucketName = TargetBucket,
                Key = TargetObjectKey,
            };

            // Initiate the upload.
            InitiateMultipartUploadResponse initResponse =
                await client.InitiateMultipartUploadAsync(initiateRequest);

            // Save the upload ID.
            string uploadId = initResponse.UploadId;

            try
            {
                // Get the size of the object.
                var metadataRequest = new GetObjectMetadataRequest
                {
                    BucketName = SourceBucket,
                    Key = SourceObjectKey,
                };
```

```
                GetObjectMetadataResponse metadataResponse =
                    await client.GetObjectMetadataAsync(metadataRequest);
                var objectSize = metadataResponse.ContentLength; // Length in
bytes.

                // Copy the parts.
                var partSize = 5 * (long)Math.Pow(2, 20); // Part size is 5 MB.

                long bytePosition = 0;
                for (int i = 1; bytePosition < objectSize; i++)
                {
                    var copyRequest = new CopyPartRequest
                    {
                        DestinationBucket = TargetBucket,
                        DestinationKey = TargetObjectKey,
                        SourceBucket = SourceBucket,
                        SourceKey = SourceObjectKey,
                        UploadId = uploadId,
                        FirstByte = bytePosition,
                        LastByte = bytePosition + partSize - 1 >= objectSize ?
objectSize - 1 : bytePosition + partSize - 1,
                        PartNumber = i,
                    };

                    copyResponses.Add(await client.CopyPartAsync(copyRequest));

                    bytePosition += partSize;
                }

                // Set up to complete the copy.
                var completeRequest = new CompleteMultipartUploadRequest
                {
                    BucketName = TargetBucket,
                    Key = TargetObjectKey,
                    UploadId = initResponse.UploadId,
                };
                completeRequest.AddPartETags(copyResponses);

                // Complete the copy.
                CompleteMultipartUploadResponse completeUploadResponse =
                    await client.CompleteMultipartUploadAsync(completeRequest);
            }
            catch (AmazonS3Exception e)
```

```
            {
                Console.WriteLine($"Error encountered on server.
Message:'{e.Message}' when writing an object");
            }
            catch (Exception e)
            {
                Console.WriteLine($"Unknown encountered on server.
Message:'{e.Message}' when writing an object");
            }
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - GetObjectMetadata
  - UploadPartCopy

Realizar um carregamento fracionado em um objeto do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como executar um carregamento fracionado de um objeto do Amazon S3.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos de código usam as importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CompletedMultipartUpload;
import software.amazon.awssdk.services.s3.model.CompletedPart;
import software.amazon.awssdk.services.s3.model.CreateMultipartUploadResponse;
import software.amazon.awssdk.services.s3.model.UploadPartRequest;
import software.amazon.awssdk.services.s3.model.UploadPartResponse;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;

import java.io.IOException;
import java.io.RandomAccessFile;
import java.net.URISyntaxException;
import java.net.URL;
import java.nio.ByteBuffer;
import java.nio.file.Paths;
import java.util.ArrayList;
import java.util.List;
import java.util.Objects;
import java.util.UUID;
```

Use o Gerenciador de Transferências do S3 na parte superior do cliente do S3 baseado no AWS CRT para realizar de forma transparente um carregamento fracionado quando o tamanho do conteúdo exceder um limite. O limite padrão é 8 MB.

```
    public void multipartUploadWithTransferManager(String filePath) {
        S3TransferManager transferManager = S3TransferManager.create();
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b
                        .bucket(bucketName)
                        .key(key))
                .source(Paths.get(filePath))
                .build();
        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);
        fileUpload.completionFuture().join();
        transferManager.close();
```

```
    }
```

Use a API S3Client ou (API S3AsyncClient) para realizar um upload de várias partes.

```
    public void multipartUploadWithS3Client(String filePath) {

        // Initiate the multipart upload.
        CreateMultipartUploadResponse createMultipartUploadResponse =
s3Client.createMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key));
        String uploadId = createMultipartUploadResponse.uploadId();

        // Upload the parts of the file.
        int partNumber = 1;
        List<CompletedPart> completedParts = new ArrayList<>();
        ByteBuffer bb = ByteBuffer.allocate(1024 * 1024 * 5); // 5 MB byte buffer

        try (RandomAccessFile file = new RandomAccessFile(filePath, "r")) {
            long fileSize = file.length();
            int position = 0;
            while (position < fileSize) {
                file.seek(position);
                int read = file.getChannel().read(bb);

                bb.flip(); // Swap position and limit before reading from the
buffer.
                UploadPartRequest uploadPartRequest = UploadPartRequest.builder()
                        .bucket(bucketName)
                        .key(key)
                        .uploadId(uploadId)
                        .partNumber(partNumber)
                        .build();

                UploadPartResponse partResponse = s3Client.uploadPart(
                        uploadPartRequest,
                        RequestBody.fromByteBuffer(bb));

                CompletedPart part = CompletedPart.builder()
                        .partNumber(partNumber)
                        .eTag(partResponse.eTag())
                        .build();
```

```
                completedParts.add(part);

                bb.clear();
                position += read;
                partNumber++;
            }
        } catch (IOException e) {
            logger.error(e.getMessage());
        }

        // Complete the multipart upload.
        s3Client.completeMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)

.multipartUpload(CompletedMultipartUpload.builder().parts(completedParts).build()));
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - UploadPart

Fazer upload ou download de arquivos grandes de e para o Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como fazer upload e download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chame funções que transferem arquivos de e para um bucket do S3 usando o Amazon TransferUtility S3.

```
global using System.Text;
global using Amazon.S3;
global using Amazon.S3.Model;
global using Amazon.S3.Transfer;
global using TransferUtilityBasics;



// This Amazon S3 client uses the default user credentials
// defined for this computer.
using Microsoft.Extensions.Configuration;

IAmazonS3 client = new AmazonS3Client();
var transferUtil = new TransferUtility(client);
IConfiguration _configuration;

_configuration = new ConfigurationBuilder()
    .SetBasePath(Directory.GetCurrentDirectory())
    .AddJsonFile("settings.json") // Load test settings from JSON file.
    .AddJsonFile("settings.local.json",
        true) // Optionally load local settings.
    .Build();

// Edit the values in settings.json to use an S3 bucket and files that
// exist on your AWS account and on the local computer where you
// run this scenario.
var bucketName = _configuration["BucketName"];
```

```
var localPath =
 $"{Environment.GetFolderPath(Environment.SpecialFolder.ApplicationData)}\
\TransferFolder";

DisplayInstructions();

PressEnter();

Console.WriteLine();

// Upload a single file to an S3 bucket.
DisplayTitle("Upload a single file");

var fileToUpload = _configuration["FileToUpload"];
Console.WriteLine($"Uploading {fileToUpload} to the S3 bucket, {bucketName}.");

var success = await TransferMethods.UploadSingleFileAsync(transferUtil,
 bucketName, fileToUpload, localPath);
if (success)
{
    Console.WriteLine($"Successfully uploaded the file, {fileToUpload} to
 {bucketName}.");
}

PressEnter();

// Upload a local directory to an S3 bucket.
DisplayTitle("Upload all files from a local directory");
Console.WriteLine("Upload all the files in a local folder to an S3 bucket.");
const string keyPrefix = "UploadFolder";
var uploadPath = $"{localPath}\\UploadFolder";

Console.WriteLine($"Uploading the files in {uploadPath} to {bucketName}");
DisplayTitle($"{uploadPath} files");
DisplayLocalFiles(uploadPath);
Console.WriteLine();

PressEnter();

success = await TransferMethods.UploadFullDirectoryAsync(transferUtil,
 bucketName, keyPrefix, uploadPath);
if (success)
{
```

```
    Console.WriteLine($"Successfully uploaded the files in {uploadPath} to
 {bucketName}.");
    Console.WriteLine($"{bucketName} currently contains the following files:");
    await DisplayBucketFiles(client, bucketName, keyPrefix);
    Console.WriteLine();
}

PressEnter();

// Download a single file from an S3 bucket.
DisplayTitle("Download a single file");
Console.WriteLine("Now we will download a single file from an S3 bucket.");

var keyName = _configuration["FileToDownload"];

Console.WriteLine($"Downloading {keyName} from {bucketName}.");

success = await TransferMethods.DownloadSingleFileAsync(transferUtil, bucketName,
 keyName, localPath);
if (success)
{
    Console.WriteLine("$Successfully downloaded the file, {keyName} from
 {bucketName}.");
}

PressEnter();

// Download the contents of a directory from an S3 bucket.
DisplayTitle("Download the contents of an S3 bucket");
var s3Path = _configuration["S3Path"];
var downloadPath = $"{localPath}\\{s3Path}";

Console.WriteLine($"Downloading the contents of {bucketName}\\{s3Path}");
Console.WriteLine($"{bucketName}\\{s3Path} contains the following files:");
await DisplayBucketFiles(client, bucketName, s3Path);
Console.WriteLine();

success = await TransferMethods.DownloadS3DirectoryAsync(transferUtil,
 bucketName, s3Path, downloadPath);
if (success)
{
    Console.WriteLine($"Downloaded the files in {bucketName} to
 {downloadPath}.");
    Console.WriteLine($"{downloadPath} now contains the following files:");
```

```
    DisplayLocalFiles(downloadPath);
}

Console.WriteLine("\nThe TransferUtility Basics application has completed.");
PressEnter();

// Displays the title for a section of the scenario.
static void DisplayTitle(string titleText)
{
    var sepBar = new string('-', Console.WindowWidth);

    Console.WriteLine(sepBar);
    Console.WriteLine(CenterText(titleText));
    Console.WriteLine(sepBar);
}

// Displays a description of the actions to be performed by the scenario.
static void DisplayInstructions()
{
    var sepBar = new string('-', Console.WindowWidth);

    DisplayTitle("Amazon S3 Transfer Utility Basics");
    Console.WriteLine("This program shows how to use the Amazon S3 Transfer
 Utility.");
    Console.WriteLine("It performs the following actions:");
    Console.WriteLine("\t1. Upload a single object to an S3 bucket.");
    Console.WriteLine("\t2. Upload an entire directory from the local computer to
 an\n\t  S3 bucket.");
    Console.WriteLine("\t3. Download a single object from an S3 bucket.");
    Console.WriteLine("\t4. Download the objects in an S3 bucket to a local
 directory.");
    Console.WriteLine($"\n{sepBar}");
}

// Pauses the scenario.
static void PressEnter()
{
    Console.WriteLine("Press <Enter> to continue.");
    _ = Console.ReadLine();
    Console.WriteLine("\n");
}

// Returns the string textToCenter, padded on the left with spaces
// that center the text on the console display.
```

```
static string CenterText(string textToCenter)
{
    var centeredText = new StringBuilder();
    var screenWidth = Console.WindowWidth;
    centeredText.Append(new string(' ', (int)(screenWidth -
 textToCenter.Length) / 2));
    centeredText.Append(textToCenter);
    return centeredText.ToString();
}

// Displays a list of file names included in the specified path.
static void DisplayLocalFiles(string localPath)
{
    var fileList = Directory.GetFiles(localPath);
    if (fileList.Length > 0)
    {
        foreach (var fileName in fileList)
        {
            Console.WriteLine(fileName);
        }
    }
}

// Displays a list of the files in the specified S3 bucket and prefix.
static async Task DisplayBucketFiles(IAmazonS3 client, string bucketName, string
 s3Path)
{
    ListObjectsV2Request request = new()
    {
        BucketName = bucketName,
        Prefix = s3Path,
        MaxKeys = 5,
    };

    var response = new ListObjectsV2Response();

    do
    {
        response = await client.ListObjectsV2Async(request);

        response.S3Objects
            .ForEach(obj => Console.WriteLine($"{obj.Key}"));

        // If the response is truncated, set the request ContinuationToken
```

```
        // from the NextContinuationToken property of the response.
        request.ContinuationToken = response.NextContinuationToken;
    } while (response.IsTruncated);
}
```

Carregue um único arquivo.

```
        /// <summary>
        /// Uploads a single file from the local computer to an S3 bucket.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the file
        /// will be stored.</param>
        /// <param name="fileName">The name of the file to upload.</param>
        /// <param name="localPath">The local path where the file is stored.</
param>
        /// <returns>A boolean value indicating the success of the action.</
returns>
        public static async Task<bool> UploadSingleFileAsync(
            TransferUtility transferUtil,
            string bucketName,
            string fileName,
            string localPath)
        {
            if (File.Exists($"{localPath}\\{fileName}"))
            {
                try
                {
                    await transferUtil.UploadAsync(new
 TransferUtilityUploadRequest
                    {
                        BucketName = bucketName,
                        Key = fileName,
                        FilePath = $"{localPath}\\{fileName}",
                    });

                    return true;
                }
                catch (AmazonS3Exception s3Ex)
```

```
                {
                    Console.WriteLine($"Could not upload {fileName} from
 {localPath} because:");
                    Console.WriteLine(s3Ex.Message);
                    return false;
                }
            }
            else
            {
                Console.WriteLine($"{fileName} does not exist in {localPath}");
                return false;
            }
        }
```

Carregue um diretório local inteiro.

```
        /// <summary>
        /// Uploads all the files in a local directory to a directory in an S3
        /// bucket.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the files
        /// will be stored.</param>
        /// <param name="keyPrefix">The key prefix is the S3 directory where
        /// the files will be stored.</param>
        /// <param name="localPath">The local directory that contains the files
        /// to be uploaded.</param>
        /// <returns>A Boolean value representing the success of the action.</
returns>
        public static async Task<bool> UploadFullDirectoryAsync(
            TransferUtility transferUtil,
            string bucketName,
            string keyPrefix,
            string localPath)
        {
            if (Directory.Exists(localPath))
            {
                try
                {
```

```
                    await transferUtil.UploadDirectoryAsync(new
 TransferUtilityUploadDirectoryRequest
                    {
                        BucketName = bucketName,
                        KeyPrefix = keyPrefix,
                        Directory = localPath,
                    });

                    return true;
                }
                catch (AmazonS3Exception s3Ex)
                {
                    Console.WriteLine($"Can't upload the contents of {localPath}
 because:");
                    Console.WriteLine(s3Ex?.Message);
                    return false;
                }
            }
            else
            {
                Console.WriteLine($"The directory {localPath} does not exist.");
                return false;
            }
        }
```

Baixe um único arquivo.

```
        /// <summary>
        /// Download a single file from an S3 bucket to the local computer.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket containing the
        /// file to download.</param>
        /// <param name="keyName">The name of the file to download.</param>
        /// <param name="localPath">The path on the local computer where the
        /// downloaded file will be saved.</param>
        /// <returns>A Boolean value indicating the results of the action.</
returns>
        public static async Task<bool> DownloadSingleFileAsync(
```

```
        TransferUtility transferUtil,
            string bucketName,
            string keyName,
            string localPath)
        {
            await transferUtil.DownloadAsync(new TransferUtilityDownloadRequest
            {
                BucketName = bucketName,
                Key = keyName,
                FilePath = $"{localPath}\\{keyName}",
            });

            return (File.Exists($"{localPath}\\{keyName}"));
        }
```

Baixe o conteúdo de um bucket do S3.

```
        /// <summary>
        /// Downloads the contents of a directory in an S3 bucket to a
        /// directory on the local computer.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The bucket containing the files to
 download.</param>
        /// <param name="s3Path">The S3 directory where the files are located.</
param>
        /// <param name="localPath">The local path to which the files will be
        /// saved.</param>
        /// <returns>A Boolean value representing the success of the action.</
returns>
        public static async Task<bool> DownloadS3DirectoryAsync(
            TransferUtility transferUtil,
            string bucketName,
            string s3Path,
            string localPath)
        {
            int fileCount = 0;

            // If the directory doesn't exist, it will be created.
```

```
            if (Directory.Exists(s3Path))
            {
                var files = Directory.GetFiles(localPath);
                fileCount = files.Length;
            }

            await transferUtil.DownloadDirectoryAsync(new
 TransferUtilityDownloadDirectoryRequest
            {
                BucketName = bucketName,
                LocalDirectory = localPath,
                S3Directory = s3Path,
            });

            if (Directory.Exists(localPath))
            {
                var files = Directory.GetFiles(localPath);
                if (files.Length > fileCount)
                {
                    return true;
                }

                // No change in the number of files. Assume
                // the download failed.
                return false;
            }

            // The local directory doesn't exist. No files
            // were downloaded.
            return false;
        }
```

Acompanhe o progresso de um upload usando TransferUtility o.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Transfer;

    /// <summary>
    /// This example shows how to track the progress of a multipart upload
```

```
    /// using the Amazon Simple Storage Service (Amazon S3) TransferUtility to
    /// upload to an Amazon S3 bucket.
    /// </summary>
    public class TrackMPUUsingHighLevelAPI
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "sample_pic.png";
            string path = "filepath/directory/";
            string filePath = $"{path}{keyName}";

            // If the AWS Region defined for your default user is different
            // from the Region where your Amazon S3 bucket is located,
            // pass the Region name to the Amazon S3 client object's constructor.
            // For example: RegionEndpoint.USWest2 or RegionEndpoint.USEast2.
            IAmazonS3 client = new AmazonS3Client();

            await TrackMPUAsync(client, bucketName, filePath, keyName);
        }

        /// <summary>
        /// Starts an Amazon S3 multipart upload and assigns an event handler to
        /// track the progress of the upload.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
        /// perform the multipart upload.</param>
        /// <param name="bucketName">The name of the bucket to which to upload
        /// the file.</param>
        /// <param name="filePath">The path, including the file name of the
        /// file to be uploaded to the Amazon S3 bucket.</param>
        /// <param name="keyName">The file name to be used in the
        /// destination Amazon S3 bucket.</param>
        public static async Task TrackMPUAsync(
            IAmazonS3 client,
            string bucketName,
            string filePath,
            string keyName)
        {
            try
            {
                var fileTransferUtility = new TransferUtility(client);

                // Use TransferUtilityUploadRequest to configure options.
```

```
                // In this example we subscribe to an event.
                var uploadRequest =
                    new TransferUtilityUploadRequest
                    {
                        BucketName = bucketName,
                        FilePath = filePath,
                        Key = keyName,
                    };

                uploadRequest.UploadProgressEvent +=
                    new EventHandler<UploadProgressArgs>(
                        UploadRequest_UploadPartProgressEvent);

                await fileTransferUtility.UploadAsync(uploadRequest);
                Console.WriteLine("Upload completed");
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error:: {ex.Message}");
            }
        }

        /// <summary>
        /// Event handler to check the progress of the multipart upload.
        /// </summary>
        /// <param name="sender">The object that raised the event.</param>
        /// <param name="e">The object that contains multipart upload
        /// information.</param>
        public static void UploadRequest_UploadPartProgressEvent(object sender,
UploadProgressArgs e)
        {
            // Process event.
            Console.WriteLine($"{e.TransferredBytes}/{e.TotalBytes}");
        }
    }
```

Faça upload de um objeto com criptografia.

```
    using System;
    using System.Collections.Generic;
    using System.IO;
```

```
using System.Security.Cryptography;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// Uses the Amazon Simple Storage Service (Amazon S3) low level API to
/// perform a multipart upload to an Amazon S3 bucket.
/// </summary>
public class SSECLowLevelMPUcopyObject
{
    public static async Task Main()
    {
        string existingBucketName = "doc-example-bucket";
        string sourceKeyName = "sample_file.txt";
        string targetKeyName = "sample_file_copy.txt";
        string filePath = $"sample\\{targetKeyName}";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USEast1.
        IAmazonS3 client = new AmazonS3Client();

        // Create the encryption key.
        var base64Key = CreateEncryptionKey();

        await CreateSampleObjUsingClientEncryptionKeyAsync(
            client,
            existingBucketName,
            sourceKeyName,
            filePath,
            base64Key);
    }

    /// <summary>
    /// Creates the encryption key to use with the multipart upload.
    /// </summary>
    /// <returns>A string containing the base64-encoded key for encrypting
    /// the multipart upload.</returns>
    public static string CreateEncryptionKey()
    {
        Aes aesEncryption = Aes.Create();
        aesEncryption.KeySize = 256;
```

```
            aesEncryption.GenerateKey();
            string base64Key = Convert.ToBase64String(aesEncryption.Key);
            return base64Key;
        }

        /// <summary>
        /// Creates and uploads an object using a multipart upload.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 object used to
        /// initialize and perform the multipart upload.</param>
        /// <param name="existingBucketName">The name of the bucket to which
        /// the object will be uploaded.</param>
        /// <param name="sourceKeyName">The source object name.</param>
        /// <param name="filePath">The location of the source object.</param>
        /// <param name="base64Key">The encryption key to use with the upload.</
param>
        public static async Task CreateSampleObjUsingClientEncryptionKeyAsync(
            IAmazonS3 client,
            string existingBucketName,
            string sourceKeyName,
            string filePath,
            string base64Key)
        {
            List<UploadPartResponse> uploadResponses = new
 List<UploadPartResponse>();

            InitiateMultipartUploadRequest initiateRequest = new
 InitiateMultipartUploadRequest
            {
                BucketName = existingBucketName,
                Key = sourceKeyName,
                ServerSideEncryptionCustomerMethod =
 ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };

            InitiateMultipartUploadResponse initResponse =
               await client.InitiateMultipartUploadAsync(initiateRequest);

            long contentLength = new FileInfo(filePath).Length;
            long partSize = 5 * (long)Math.Pow(2, 20); // 5 MB

            try
            {
```

```
                long filePosition = 0;
                for (int i = 1; filePosition < contentLength; i++)
                {
                    UploadPartRequest uploadRequest = new UploadPartRequest
                    {
                        BucketName = existingBucketName,
                        Key = sourceKeyName,
                        UploadId = initResponse.UploadId,
                        PartNumber = i,
                        PartSize = partSize,
                        FilePosition = filePosition,
                        FilePath = filePath,
                        ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                        ServerSideEncryptionCustomerProvidedKey = base64Key,
                    };

                    // Upload part and add response to our list.
                    uploadResponses.Add(await
client.UploadPartAsync(uploadRequest));

                    filePosition += partSize;
                }

                CompleteMultipartUploadRequest completeRequest = new
CompleteMultipartUploadRequest
                {
                    BucketName = existingBucketName,
                    Key = sourceKeyName,
                    UploadId = initResponse.UploadId,
                };
                completeRequest.AddPartETags(uploadResponses);

                CompleteMultipartUploadResponse completeUploadResponse =
                    await client.CompleteMultipartUploadAsync(completeRequest);
            }
            catch (Exception exception)
            {
                Console.WriteLine($"Exception occurred: {exception.Message}");

                // If there was an error, abort the multipart upload.
                AbortMultipartUploadRequest abortMPURequest = new
AbortMultipartUploadRequest
                {
```

```
                    BucketName = existingBucketName,
                    Key = sourceKeyName,
                    UploadId = initResponse.UploadId,
                };

                await client.AbortMultipartUploadAsync(abortMPURequest);
            }
        }
    }
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um objeto grande usando um gerenciador de uploads para dividir os dados em partes e fazer upload delas simultaneamente.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3)
 actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform
 bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// UploadLargeObject uses an upload manager to upload data to an object in a
 bucket.
```

```
// The upload manager breaks large data into parts and uploads the parts
 concurrently.
func (basics BucketBasics) UploadLargeObject(bucketName string, objectKey string,
 largeObject []byte) error {
 largeBuffer := bytes.NewReader(largeObject)
 var partMiBs int64 = 10
 uploader := manager.NewUploader(basics.S3Client, func(u *manager.Uploader) {
  u.PartSize = partMiBs * 1024 * 1024
 })
 _, err := uploader.Upload(context.TODO(), &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
  Body:   largeBuffer,
 })
 if err != nil {
  log.Printf("Couldn't upload large object to %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }

 return err
}
```

Faça download de um objeto grande usando um gerenciador de downloads para obter os dados em partes e baixá-las simultaneamente.

```
// DownloadLargeObject uses a download manager to download an object from a
 bucket.
// The download manager gets the data in parts and writes them to a buffer until
 all of
// the data has been downloaded.
func (basics BucketBasics) DownloadLargeObject(bucketName string, objectKey
 string) ([]byte, error) {
 var partMiBs int64 = 10
 downloader := manager.NewDownloader(basics.S3Client, func(d *manager.Downloader)
 {
  d.PartSize = partMiBs * 1024 * 1024
 })
 buffer := manager.NewWriteAtBuffer([]byte{})
 _, err := downloader.Download(context.TODO(), buffer, &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
```

```
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't download large object from %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return buffer.Bytes(), err
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chame funções que transferem arquivos de e para um bucket do S3 usando o TransferManager S3.

```
    public Integer downloadObjectsToDirectory(S3TransferManager transferManager,
            String destinationPath, String bucketName) {
        DirectoryDownload directoryDownload =
transferManager.downloadDirectory(DownloadDirectoryRequest.builder()
                .destination(Paths.get(destinationPath))
                .bucket(bucketName)
                .build());
        CompletedDirectoryDownload completedDirectoryDownload =
directoryDownload.completionFuture().join();

        completedDirectoryDownload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
fail.toString()));
        return completedDirectoryDownload.failedTransfers().size();
    }
```

Carregue um diretório local inteiro.

```
   public Integer uploadDirectory(S3TransferManager transferManager,
           String sourceDirectory, String bucketName) {
       DirectoryUpload directoryUpload =
transferManager.uploadDirectory(UploadDirectoryRequest.builder()
               .source(Paths.get(sourceDirectory))
               .bucket(bucketName)
               .build());

       CompletedDirectoryUpload completedDirectoryUpload =
directoryUpload.completionFuture().join();
       completedDirectoryUpload.failedTransfers()
               .forEach(fail -> logger.warn("Object [{}] failed to transfer",
fail.toString()));
       return completedDirectoryUpload.failedTransfers().size();
   }
```

Carregue um único arquivo.

```
   public String uploadFile(S3TransferManager transferManager, String
bucketName,
           String key, String filePath) {
       UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
               .putObjectRequest(b -> b.bucket(bucketName).key(key))
               .addTransferListener(LoggingTransferListener.create())
               .source(Paths.get(filePath))
               .build();

       FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);

       CompletedFileUpload uploadResult = fileUpload.completionFuture().join();
       return uploadResult.response().eTag();
   }
```

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um arquivo grande.

```
import {
  CreateMultipartUploadCommand,
  UploadPartCommand,
  CompleteMultipartUploadCommand,
  AbortMultipartUploadCommand,
  S3Client,
} from "@aws-sdk/client-s3";

const twentyFiveMB = 25 * 1024 * 1024;

export const createString = (size = twentyFiveMB) => {
  return "x".repeat(size);
};

export const main = async () => {
  const s3Client = new S3Client({});
  const bucketName = "test-bucket";
  const key = "multipart.txt";
  const str = createString();
  const buffer = Buffer.from(str, "utf8");

  let uploadId;

  try {
    const multipartUpload = await s3Client.send(
      new CreateMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
      }),
    );
```

```
    uploadId = multipartUpload.UploadId;

    const uploadPromises = [];
    // Multipart uploads require a minimum size of 5 MB per part.
    const partSize = Math.ceil(buffer.length / 5);

    // Upload each part.
    for (let i = 0; i < 5; i++) {
      const start = i * partSize;
      const end = start + partSize;
      uploadPromises.push(
        s3Client
          .send(
            new UploadPartCommand({
              Bucket: bucketName,
              Key: key,
              UploadId: uploadId,
              Body: buffer.subarray(start, end),
              PartNumber: i + 1,
            }),
          )
          .then((d) => {
            console.log("Part", i + 1, "uploaded");
            return d;
          }),
      );
    }

    const uploadResults = await Promise.all(uploadPromises);

    return await s3Client.send(
      new CompleteMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
        UploadId: uploadId,
        MultipartUpload: {
          Parts: uploadResults.map(({ ETag }, i) => ({
            ETag,
            PartNumber: i + 1,
          })),
        },
      }),
    );
```

```
    // Verify the output by downloading the file from the Amazon Simple Storage
 Service (Amazon S3) console.
    // Because the output is a 25 MB string, text editors might struggle to open
 the file.
  } catch (err) {
    console.error(err);

    if (uploadId) {
      const abortCommand = new AbortMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
        UploadId: uploadId,
      });

      await s3Client.send(abortCommand);
    }
  }
};
```

Baixe um arquivo grande.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { createWriteStream } from "fs";

const s3Client = new S3Client({});
const oneMB = 1024 * 1024;

export const getObjectRange = ({ bucket, key, start, end }) => {
  const command = new GetObjectCommand({
    Bucket: bucket,
    Key: key,
    Range: `bytes=${start}-${end}`,
  });

  return s3Client.send(command);
};

export const getRangeAndLength = (contentRange) => {
  const [range, length] = contentRange.split("/");
  const [start, end] = range.split("-");
  return {
    start: parseInt(start),
```

```
    end: parseInt(end),
    length: parseInt(length),
  };
};

export const isComplete = ({ end, length }) => end === length - 1;

// When downloading a large file, you might want to break it down into
// smaller pieces. Amazon S3 accepts a Range header to specify the start
// and end of the byte range to be downloaded.
const downloadInChunks = async ({ bucket, key }) => {
  const writeStream = createWriteStream(
    fileURLToPath(new URL(`./${key}`, import.meta.url))
  ).on("error", (err) => console.error(err));

  let rangeAndLength = { start: -1, end: -1, length: -1 };

  while (!isComplete(rangeAndLength)) {
    const { end } = rangeAndLength;
    const nextRange = { start: end + 1, end: end + oneMB };

    console.log(`Downloading bytes ${nextRange.start} to ${nextRange.end}`);

    const { ContentRange, Body } = await getObjectRange({
      bucket,
      key,
      ...nextRange,
    });

    writeStream.write(await Body.transformToByteArray());
    rangeAndLength = getRangeAndLength(ContentRange);
  }
};

export const main = async () => {
  await downloadInChunks({
    bucket: "my-cool-bucket",
    key: "my-cool-object.txt",
  });
};
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que transfiram arquivos usando várias configurações do gerenciador de transferências disponíveis. Use uma classe de retorno de chamada para gravar o andamento do retorno de chamada durante a transferência de arquivos.

```
import sys
import threading

import boto3
from boto3.s3.transfer import TransferConfig


MB = 1024 * 1024
s3 = boto3.resource("s3")


class TransferCallback:
    """
    Handle callbacks from the transfer manager.

    The transfer manager periodically calls the __call__ method throughout
    the upload and download process so that it can take action, such as
    displaying progress to the user and collecting data about the transfer.
    """

    def __init__(self, target_size):
        self._target_size = target_size
        self._total_transferred = 0
        self._lock = threading.Lock()
        self.thread_info = {}

    def __call__(self, bytes_transferred):
        """
```

```
        The callback method that is called by the transfer manager.

        Display progress during file transfer and collect per-thread transfer
        data. This method can be called by multiple threads, so shared instance
        data is protected by a thread lock.
        """
        thread = threading.current_thread()
        with self._lock:
            self._total_transferred += bytes_transferred
            if thread.ident not in self.thread_info.keys():
                self.thread_info[thread.ident] = bytes_transferred
            else:
                self.thread_info[thread.ident] += bytes_transferred

            target = self._target_size * MB
            sys.stdout.write(
                f"\r{self._total_transferred} of {target} transferred "
                f"({(self._total_transferred / target) * 100:.2f}%)."
            )
            sys.stdout.flush()


def upload_with_default_configuration(
    local_file_path, bucket_name, object_key, file_size_mb
):
    """
    Upload a file from a local folder to an Amazon S3 bucket, using the default
    configuration.
    """
    transfer_callback = TransferCallback(file_size_mb)
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def upload_with_chunksize_and_meta(
    local_file_path, bucket_name, object_key, file_size_mb, metadata=None
):
    """
    Upload a file from a local folder to an Amazon S3 bucket, setting a
    multipart chunk size and adding metadata to the Amazon S3 object.

    The multipart chunk size controls the size of the chunks of data that are
```

```
    sent in the request. A smaller chunk size typically results in the transfer
    manager using more threads for the upload.

    The metadata is a set of key-value pairs that are stored with the object
    in Amazon S3.
    """
    transfer_callback = TransferCallback(file_size_mb)

    config = TransferConfig(multipart_chunksize=1 * MB)
    extra_args = {"Metadata": metadata} if metadata else None
    s3.Bucket(bucket_name).upload_file(
        local_file_path,
        object_key,
        Config=config,
        ExtraArgs=extra_args,
        Callback=transfer_callback,
    )
    return transfer_callback.thread_info


def upload_with_high_threshold(local_file_path, bucket_name, object_key,
 file_size_mb):
    """
    Upload a file from a local folder to an Amazon S3 bucket, setting a
    multipart threshold larger than the size of the file.

    Setting a multipart threshold larger than the size of the file results
    in the transfer manager sending the file as a standard upload instead of
    a multipart upload.
    """
    transfer_callback = TransferCallback(file_size_mb)
    config = TransferConfig(multipart_threshold=file_size_mb * 2 * MB)
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, Config=config, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def upload_with_sse(
    local_file_path, bucket_name, object_key, file_size_mb, sse_key=None
):
    """
    Upload a file from a local folder to an Amazon S3 bucket, adding server-side
    encryption with customer-provided encryption keys to the object.
```

```
    When this kind of encryption is specified, Amazon S3 encrypts the object
    at rest and allows downloads only when the expected encryption key is
    provided in the download request.
    """
    transfer_callback = TransferCallback(file_size_mb)
    if sse_key:
        extra_args = {"SSECustomerAlgorithm": "AES256", "SSECustomerKey":
 sse_key}
    else:
        extra_args = None
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, ExtraArgs=extra_args,
 Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_default_configuration(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, using the
    default configuration.
    """
    transfer_callback = TransferCallback(file_size_mb)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_single_thread(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, using a
    single thread.
    """
    transfer_callback = TransferCallback(file_size_mb)
    config = TransferConfig(use_threads=False)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Config=config, Callback=transfer_callback
    )
```

```
    return transfer_callback.thread_info


def download_with_high_threshold(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, setting a
    multipart threshold larger than the size of the file.

    Setting a multipart threshold larger than the size of the file results
    in the transfer manager sending the file as a standard download instead
    of a multipart download.
    """
    transfer_callback = TransferCallback(file_size_mb)
    config = TransferConfig(multipart_threshold=file_size_mb * 2 * MB)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Config=config, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_sse(
    bucket_name, object_key, download_file_path, file_size_mb, sse_key
):
    """
    Download a file from an Amazon S3 bucket to a local folder, adding a
    customer-provided encryption key to the request.

    When this kind of encryption is specified, Amazon S3 encrypts the object
    at rest and allows downloads only when the expected encryption key is
    provided in the download request.
    """
    transfer_callback = TransferCallback(file_size_mb)

    if sse_key:
        extra_args = {"SSECustomerAlgorithm": "AES256", "SSECustomerKey":
 sse_key}
    else:
        extra_args = None
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, ExtraArgs=extra_args, Callback=transfer_callback
    )
    return transfer_callback.thread_info
```

Demonstre as funções do gerenciador de transferências e relate resultados.

```
import hashlib
import os
import platform
import shutil
import time

import boto3
from boto3.s3.transfer import TransferConfig
from botocore.exceptions import ClientError
from botocore.exceptions import ParamValidationError
from botocore.exceptions import NoCredentialsError

import file_transfer

MB = 1024 * 1024
# These configuration attributes affect both uploads and downloads.
CONFIG_ATTRS = (
    "multipart_threshold",
    "multipart_chunksize",
    "max_concurrency",
    "use_threads",
)
# These configuration attributes affect only downloads.
DOWNLOAD_CONFIG_ATTRS = ("max_io_queue", "io_chunksize", "num_download_attempts")


class TransferDemoManager:
    """
    Manages the demonstration. Collects user input from a command line, reports
    transfer results, maintains a list of artifacts created during the
    demonstration, and cleans them up after the demonstration is completed.
    """

    def __init__(self):
        self._s3 = boto3.resource("s3")
        self._chore_list = []
        self._create_file_cmd = None
```

```
        self._size_multiplier = 0
        self.file_size_mb = 30
        self.demo_folder = None
        self.demo_bucket = None
        self._setup_platform_specific()
        self._terminal_width = shutil.get_terminal_size(fallback=(80, 80))[0]

    def collect_user_info(self):
        """
        Collect local folder and Amazon S3 bucket name from the user. These
        locations are used to store files during the demonstration.
        """
        while not self.demo_folder:
            self.demo_folder = input(
                "Which file folder do you want to use to store " "demonstration
files? "
            )
            if not os.path.isdir(self.demo_folder):
                print(f"{self.demo_folder} isn't a folder!")
                self.demo_folder = None

        while not self.demo_bucket:
            self.demo_bucket = input(
                "Which Amazon S3 bucket do you want to use to store "
                "demonstration files? "
            )
            try:
                self._s3.meta.client.head_bucket(Bucket=self.demo_bucket)
            except ParamValidationError as err:
                print(err)
                self.demo_bucket = None
            except ClientError as err:
                print(err)
                print(
                    f"Either {self.demo_bucket} doesn't exist or you don't "
                    f"have access to it."
                )
                self.demo_bucket = None

    def demo(
        self, question, upload_func, download_func, upload_args=None,
download_args=None
    ):
        """Run a demonstration.
```

```
        Ask the user if they want to run this specific demonstration.
        If they say yes, create a file on the local path, upload it
        using the specified upload function, then download it using the
        specified download function.
        """
        if download_args is None:
            download_args = {}
        if upload_args is None:
            upload_args = {}
        question = question.format(self.file_size_mb)
        answer = input(f"{question} (y/n)")
        if answer.lower() == "y":
            local_file_path, object_key, download_file_path =
self._create_demo_file()

            file_transfer.TransferConfig = self._config_wrapper(
                TransferConfig, CONFIG_ATTRS
            )
            self._report_transfer_params(
                "Uploading", local_file_path, object_key, **upload_args
            )
            start_time = time.perf_counter()
            thread_info = upload_func(
                local_file_path,
                self.demo_bucket,
                object_key,
                self.file_size_mb,
                **upload_args,
            )
            end_time = time.perf_counter()
            self._report_transfer_result(thread_info, end_time - start_time)

            file_transfer.TransferConfig = self._config_wrapper(
                TransferConfig, CONFIG_ATTRS + DOWNLOAD_CONFIG_ATTRS
            )
            self._report_transfer_params(
                "Downloading", object_key, download_file_path, **download_args
            )
            start_time = time.perf_counter()
            thread_info = download_func(
                self.demo_bucket,
                object_key,
                download_file_path,
```

```
                self.file_size_mb,
                **download_args,
            )
            end_time = time.perf_counter()
            self._report_transfer_result(thread_info, end_time - start_time)

    def last_name_set(self):
        """Get the name set used for the last demo."""
        return self._chore_list[-1]

    def cleanup(self):
        """
        Remove files from the demo folder, and uploaded objects from the
        Amazon S3 bucket.
        """
        print("-" * self._terminal_width)
        for local_file_path, s3_object_key, downloaded_file_path in
self._chore_list:
            print(f"Removing {local_file_path}")
            try:
                os.remove(local_file_path)
            except FileNotFoundError as err:
                print(err)

            print(f"Removing {downloaded_file_path}")
            try:
                os.remove(downloaded_file_path)
            except FileNotFoundError as err:
                print(err)

            if self.demo_bucket:
                print(f"Removing {self.demo_bucket}:{s3_object_key}")
                try:

self._s3.Bucket(self.demo_bucket).Object(s3_object_key).delete()
                except ClientError as err:
                    print(err)

    def _setup_platform_specific(self):
        """Set up platform-specific command used to create a large file."""
        if platform.system() == "Windows":
            self._create_file_cmd = "fsutil file createnew {} {}"
            self._size_multiplier = MB
        elif platform.system() == "Linux" or platform.system() == "Darwin":
```

```
            self._create_file_cmd = f"dd if=/dev/urandom of={{}} " f"bs={MB}
count={{}}"
            self._size_multiplier = 1
        else:
            raise EnvironmentError(
                f"Demo of platform {platform.system()} isn't supported."
            )

    def _create_demo_file(self):
        """
        Create a file in the demo folder specified by the user. Store the local
        path, object name, and download path for later cleanup.

        Only the local file is created by this method. The Amazon S3 object and
        download file are created later during the demonstration.

        Returns:
        A tuple that contains the local file path, object name, and download
        file path.
        """
        file_name_template = "TestFile{}-{}.demo"
        local_suffix = "local"
        object_suffix = "s3object"
        download_suffix = "downloaded"
        file_tag = len(self._chore_list) + 1

        local_file_path = os.path.join(
            self.demo_folder, file_name_template.format(file_tag, local_suffix)
        )

        s3_object_key = file_name_template.format(file_tag, object_suffix)

        downloaded_file_path = os.path.join(
            self.demo_folder, file_name_template.format(file_tag,
download_suffix)
        )

        filled_cmd = self._create_file_cmd.format(
            local_file_path, self.file_size_mb * self._size_multiplier
        )

        print(
            f"Creating file of size {self.file_size_mb} MB "
            f"in {self.demo_folder} by running:"
```

```
        )
        print(f"{'':4}{filled_cmd}")
        os.system(filled_cmd)

        chore = (local_file_path, s3_object_key, downloaded_file_path)
        self._chore_list.append(chore)
        return chore

    def _report_transfer_params(self, verb, source_name, dest_name, **kwargs):
        """Report configuration and extra arguments used for a file transfer."""
        print("-" * self._terminal_width)
        print(f"{verb} {source_name} ({self.file_size_mb} MB) to {dest_name}")
        if kwargs:
            print("With extra args:")
            for arg, value in kwargs.items():
                print(f'{"":4}{arg:<20}: {value}')

    @staticmethod
    def ask_user(question):
        """
        Ask the user a yes or no question.

        Returns:
        True when the user answers 'y' or 'Y'; otherwise, False.
        """
        answer = input(f"{question} (y/n) ")
        return answer.lower() == "y"

    @staticmethod
    def _config_wrapper(func, config_attrs):
        def wrapper(*args, **kwargs):
            config = func(*args, **kwargs)
            print("With configuration:")
            for attr in config_attrs:
                print(f'{"":4}{attr:<20}: {getattr(config, attr)}')
            return config

        return wrapper

    @staticmethod
    def _report_transfer_result(thread_info, elapsed):
        """Report the result of a transfer, including per-thread data."""
        print(f"\nUsed {len(thread_info)} threads.")
        for ident, byte_count in thread_info.items():
```

```
            print(f"{'':4}Thread {ident} copied {byte_count} bytes.")
        print(f"Your transfer took {elapsed:.2f} seconds.")


def main():
    """
    Run the demonstration script for s3_file_transfer.
    """
    demo_manager = TransferDemoManager()
    demo_manager.collect_user_info()

    # Upload and download with default configuration. Because the file is 30 MB
    # and the default multipart_threshold is 8 MB, both upload and download are
    # multipart transfers.
    demo_manager.demo(
        "Do you want to upload and download a {} MB file "
        "using the default configuration?",
        file_transfer.upload_with_default_configuration,
        file_transfer.download_with_default_configuration,
    )

    # Upload and download with multipart_threshold set higher than the size of
    # the file. This causes the transfer manager to use standard transfers
    # instead of multipart transfers.
    demo_manager.demo(
        "Do you want to upload and download a {} MB file "
        "as a standard (not multipart) transfer?",
        file_transfer.upload_with_high_threshold,
        file_transfer.download_with_high_threshold,
    )

    # Upload with specific chunk size and additional metadata.
    # Download with a single thread.
    demo_manager.demo(
        "Do you want to upload a {} MB file with a smaller chunk size and "
        "then download the same file using a single thread?",
        file_transfer.upload_with_chunksize_and_meta,
        file_transfer.download_with_single_thread,
        upload_args={
            "metadata": {
                "upload_type": "chunky",
                "favorite_color": "aqua",
                "size": "medium",
            }
```

```
        },
    )

    # Upload using server-side encryption with customer-provided
    # encryption keys.
    # Generate a 256-bit key from a passphrase.
    sse_key = hashlib.sha256("demo_passphrase".encode("utf-8")).digest()
    demo_manager.demo(
        "Do you want to upload and download a {} MB file using "
        "server-side encryption?",
        file_transfer.upload_with_sse,
        file_transfer.download_with_sse,
        upload_args={"sse_key": sse_key},
        download_args={"sse_key": sse_key},
    )

    # Download without specifying an encryption key to show that the
    # encryption key must be included to download an encrypted object.
    if demo_manager.ask_user(
        "Do you want to try to download the encrypted "
        "object without sending the required key?"
    ):
        try:
            _, object_key, download_file_path = demo_manager.last_name_set()
            file_transfer.download_with_default_configuration(
                demo_manager.demo_bucket,
                object_key,
                download_file_path,
                demo_manager.file_size_mb,
            )
        except ClientError as err:
            print(
                "Got expected error when trying to download an encrypted "
                "object without specifying encryption info:"
            )
            print(f"{'':4}{err}")

    # Remove all created and downloaded files, remove all objects from
    # S3 storage.
    if demo_manager.ask_user(
        "Demonstration complete. Do you want to remove local files " "and S3
objects?"
    ):
        demo_manager.cleanup()
```

```
if __name__ == "__main__":
    try:
        main()
    except NoCredentialsError as error:
        print(error)
        print(
            "To run this example, you must have valid credentials in "
            "a shared credential file or set in environment variables."
        )
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use std::fs::File;
use std::io::prelude::*;
use std::path::Path;

use aws_config::meta::region::RegionProviderChain;
use aws_sdk_s3::error::DisplayErrorContext;
use aws_sdk_s3::operation::{
    create_multipart_upload::CreateMultipartUploadOutput,
 get_object::GetObjectOutput,
};
use aws_sdk_s3::types::{CompletedMultipartUpload, CompletedPart};
use aws_sdk_s3::{config::Region, Client as S3Client};
use aws_smithy_types::byte_stream::{ByteStream, Length};
use rand::distributions::Alphanumeric;
use rand::{thread_rng, Rng};
use s3_service::error::Error;
use std::process;
```

```
use uuid::Uuid;

//In bytes, minimum chunk size of 5MB. Increase CHUNK_SIZE to send larger chunks.
const CHUNK_SIZE: u64 = 1024 * 1024 * 5;
const MAX_CHUNKS: u64 = 10000;

#[tokio::main]
pub async fn main() {
    if let Err(err) = run_example().await {
        eprintln!("Error: {}", DisplayErrorContext(err));
        process::exit(1);
    }
}

async fn run_example() -> Result<(), Error> {
    let shared_config = aws_config::load_from_env().await;
    let client = S3Client::new(&shared_config);

    let bucket_name = format!("doc-example-bucket-{}", Uuid::new_v4());
    let region_provider = RegionProviderChain::first_try(Region::new("us-
west-2"));
    let region = region_provider.region().await.unwrap();
    s3_service::create_bucket(&client, &bucket_name, region.as_ref()).await?;

    let key = "sample.txt".to_string();
    let multipart_upload_res: CreateMultipartUploadOutput = client
        .create_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .send()
        .await
        .unwrap();
    let upload_id = multipart_upload_res.upload_id().unwrap();

    //Create a file of random characters for the upload.
    let mut file = File::create(&key).expect("Could not create sample file.");
    // Loop until the file is 5 chunks.
    while file.metadata().unwrap().len() <= CHUNK_SIZE * 4 {
        let rand_string: String = thread_rng()
            .sample_iter(&Alphanumeric)
            .take(256)
            .map(char::from)
            .collect();
        let return_string: String = "\n".to_string();
```

```
        file.write_all(rand_string.as_ref())
            .expect("Error writing to file.");
        file.write_all(return_string.as_ref())
            .expect("Error writing to file.");
    }

    let path = Path::new(&key);
    let file_size = tokio::fs::metadata(path)
        .await
        .expect("it exists I swear")
        .len();

    let mut chunk_count = (file_size / CHUNK_SIZE) + 1;
    let mut size_of_last_chunk = file_size % CHUNK_SIZE;
    if size_of_last_chunk == 0 {
        size_of_last_chunk = CHUNK_SIZE;
        chunk_count -= 1;
    }

    if file_size == 0 {
        panic!("Bad file size.");
    }
    if chunk_count > MAX_CHUNKS {
        panic!("Too many chunks! Try increasing your chunk size.")
    }

    let mut upload_parts: Vec<CompletedPart> = Vec::new();

    for chunk_index in 0..chunk_count {
        let this_chunk = if chunk_count - 1 == chunk_index {
            size_of_last_chunk
        } else {
            CHUNK_SIZE
        };
        let stream = ByteStream::read_from()
            .path(path)
            .offset(chunk_index * CHUNK_SIZE)
            .length(Length::Exact(this_chunk))
            .build()
            .await
            .unwrap();
        //Chunk index needs to start at 0, but part numbers start at 1.
        let part_number = (chunk_index as i32) + 1;
        let upload_part_res = client
```

```
            .upload_part()
            .key(&key)
            .bucket(&bucket_name)
            .upload_id(upload_id)
            .body(stream)
            .part_number(part_number)
            .send()
            .await?;
        upload_parts.push(
            CompletedPart::builder()
                .e_tag(upload_part_res.e_tag.unwrap_or_default())
                .part_number(part_number)
                .build(),
        );
    }
    let completed_multipart_upload: CompletedMultipartUpload =
CompletedMultipartUpload::builder()
        .set_parts(Some(upload_parts))
        .build();

    let _complete_multipart_upload_res = client
        .complete_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .multipart_upload(completed_multipart_upload)
        .upload_id(upload_id)
        .send()
        .await
        .unwrap();

    let data: GetObjectOutput = s3_service::download_object(&client,
&bucket_name, &key).await?;
    let data_length: u64 = data
        .content_length()
        .unwrap_or_default()
        .try_into()
        .unwrap();
    if file.metadata().unwrap().len() == data_length {
        println!("Data lengths match.");
    } else {
        println!("The data was not the same size!");
    }

    s3_service::delete_objects(&client, &bucket_name)
```

```
        .await
        .expect("Error emptying bucket.");
    s3_service::delete_bucket(&client, &bucket_name)
        .await
        .expect("Error deleting bucket.");

    Ok(())
}
```

Faça upload de um fluxo de tamanho desconhecido em um objeto do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como fazer upload de um fluxo de tamanho desconhecido em um objeto do Amazon S3.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use o Cliente do S3 baseado em CRT da AWS.

```
import com.example.s3.util.AsyncExampleUtils;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.async.AsyncRequestBody;
import software.amazon.awssdk.core.async.BlockingInputStreamAsyncRequestBody;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.services.s3.S3AsyncClient;
import software.amazon.awssdk.services.s3.model.PutObjectResponse;

import java.io.ByteArrayInputStream;
import java.util.UUID;
import java.util.concurrent.CompletableFuture;
```

```
    /**
     * @param s33CrtAsyncClient - To upload content from a stream of unknown
 size, use the AWS CRT-based S3 client. For more information, see
     *                          https://docs.aws.amazon.com/sdk-for-java/latest/
developer-guide/crt-based-s3-client.html.
     * @param bucketName - The name of the bucket.
     * @param key - The name of the object.
     * @return software.amazon.awssdk.services.s3.model.PutObjectResponse -
 Returns metadata pertaining to the put object operation.
     */
    public PutObjectResponse putObjectFromStream(S3AsyncClient s33CrtAsyncClient,
 String bucketName, String key) {

        BlockingInputStreamAsyncRequestBody body =
                AsyncRequestBody.forBlockingInputStream(null); // 'null'
 indicates a stream will be provided later.

        CompletableFuture<PutObjectResponse> responseFuture =
                s33CrtAsyncClient.putObject(r -> r.bucket(bucketName).key(key),
 body);

        // AsyncExampleUtils.randomString() returns a random string up to 100
 characters.
        String randomString = AsyncExampleUtils.randomString();
        logger.info("random string to upload: {}: length={}", randomString,
 randomString.length());

        // Provide the stream of data to be uploaded.
        body.writeInputStream(new ByteArrayInputStream(randomString.getBytes()));

        PutObjectResponse response = responseFuture.join(); // Wait for the
 response.
        logger.info("Object {} uploaded to bucket {}.", key, bucketName);
        return response;
    }
}
```

Use o Gerenciador de transferências do Amazon S3.

```
import com.example.s3.util.AsyncExampleUtils;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
```

```
import software.amazon.awssdk.core.async.AsyncRequestBody;
import software.amazon.awssdk.core.async.BlockingInputStreamAsyncRequestBody;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedUpload;
import software.amazon.awssdk.transfer.s3.model.Upload;

import java.io.ByteArrayInputStream;
import java.util.UUID;

    /**
     * @param transferManager - To upload content from a stream of unknown size,
 use the S3TransferManager based on the AWS CRT-based S3 client.
     *                       For more information, see https://
docs.aws.amazon.com/sdk-for-java/latest/developer-guide/transfer-manager.html.
     * @param bucketName - The name of the bucket.
     * @param key - The name of the object.
     * @return - software.amazon.awssdk.transfer.s3.model.CompletedUpload - The
 result of the completed upload.
     */
    public CompletedUpload uploadStream(S3TransferManager transferManager, String
 bucketName, String key) {

        BlockingInputStreamAsyncRequestBody body =
                AsyncRequestBody.forBlockingInputStream(null); // 'null'
 indicates a stream will be provided later.

        Upload upload = transferManager.upload(builder -> builder
                .requestBody(body)
                .putObjectRequest(req -> req.bucket(bucketName).key(key))
                .build());

        // AsyncExampleUtils.randomString() returns a random string up to 100
 characters.
        String randomString = AsyncExampleUtils.randomString();
        logger.info("random string to upload: {}: length={}", randomString,
 randomString.length());

        // Provide the stream of data to be uploaded.
        body.writeInputStream(new ByteArrayInputStream(randomString.getBytes()));

        return upload.completionFuture().join();
    }
}
```

Usar somas de verificação para trabalhar com um objeto do Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como usar somas de verificação para trabalhar com um objeto do Amazon S3.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos de código usam um subconjunto das importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ChecksumAlgorithm;
import software.amazon.awssdk.services.s3.model.ChecksumMode;
import software.amazon.awssdk.services.s3.model.CompletedMultipartUpload;
import software.amazon.awssdk.services.s3.model.CompletedPart;
import software.amazon.awssdk.services.s3.model.CreateMultipartUploadResponse;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import software.amazon.awssdk.services.s3.model.UploadPartRequest;
import software.amazon.awssdk.services.s3.model.UploadPartResponse;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;

import java.io.FileInputStream;
import java.io.IOException;
```

```
import java.io.RandomAccessFile;
import java.net.URISyntaxException;
import java.net.URL;
import java.nio.ByteBuffer;
import java.nio.file.Paths;
import java.security.DigestInputStream;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
import java.util.ArrayList;
import java.util.Base64;
import java.util.List;
import java.util.Objects;
import java.util.UUID;
```

Especifique um algoritmo de soma de verificação para o método `putObject` ao criar `PutObjectRequest`.

```
    public void putObjectWithChecksum() {
        s3Client.putObject(b -> b
                .bucket(bucketName)
                .key(key)
                .checksumAlgorithm(ChecksumAlgorithm.CRC32),
                RequestBody.fromString("This is a test"));
    }
```

Verifique a soma de verificação do `getObject` método ao criar o. GetObjectRequest

```
    public GetObjectResponse getObjectWithChecksum() {
        return s3Client.getObject(b -> b
                .bucket(bucketName)
                .key(key)
                .checksumMode(ChecksumMode.ENABLED))
                .response();
    }
```

Calcule previamente uma soma de verificação para o método `putObject` ao criar o `PutObjectRequest`.

```
    public void putObjectWithPrecalculatedChecksum(String filePath) {
```

```
        String checksum = calculateChecksum(filePath, "SHA-256");

        s3Client.putObject((b -> b
                .bucket(bucketName)
                .key(key)
                .checksumSHA256(checksum)),
                RequestBody.fromFile(Paths.get(filePath)));
    }
```

Use o Gerenciador de Transferências do S3 na parte superior do cliente do S3 baseado no AWS CRT para realizar de forma transparente um carregamento fracionado quando o tamanho do conteúdo exceder um limite. O limite padrão é 8 MB.

Você pode especificar um algoritmo de soma de verificação para o SDK usar. Por padrão, o SDK usa o algoritmo CRC32.

```
    public void multipartUploadWithChecksumTm(String filePath) {
        S3TransferManager transferManager = S3TransferManager.create();
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b
                        .bucket(bucketName)
                        .key(key)
                        .checksumAlgorithm(ChecksumAlgorithm.SHA1))
                .source(Paths.get(filePath))
                .build();
        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);
        fileUpload.completionFuture().join();
        transferManager.close();
    }
```

Use a API S3Client ou (API S3AsyncClient) para realizar um upload de várias partes. Se você especificar uma soma de verificação adicional, deverá indicar o algoritmo a ser usado no início do carregamento. Você também deve especificar o algoritmo para a solicitação de cada parte e fornecer a soma de verificação calculada para cada parte após o carregamento.

```
    public void multipartUploadWithChecksumS3Client(String filePath) {
        ChecksumAlgorithm algorithm = ChecksumAlgorithm.CRC32;

        // Initiate the multipart upload.
```

```
        CreateMultipartUploadResponse createMultipartUploadResponse =
s3Client.createMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key)
                .checksumAlgorithm(algorithm)); // Checksum specified on
initiation.
        String uploadId = createMultipartUploadResponse.uploadId();

        // Upload the parts of the file.
        int partNumber = 1;
        List<CompletedPart> completedParts = new ArrayList<>();
        ByteBuffer bb = ByteBuffer.allocate(1024 * 1024 * 5); // 5 MB byte buffer

        try (RandomAccessFile file = new RandomAccessFile(filePath, "r")) {
            long fileSize = file.length();
            int position = 0;
            while (position < fileSize) {
                file.seek(position);
                int read = file.getChannel().read(bb);

                bb.flip(); // Swap position and limit before reading from the
buffer.
                UploadPartRequest uploadPartRequest = UploadPartRequest.builder()
                        .bucket(bucketName)
                        .key(key)
                        .uploadId(uploadId)
                        .checksumAlgorithm(algorithm) // Checksum specified on
each part.
                        .partNumber(partNumber)
                        .build();

                UploadPartResponse partResponse = s3Client.uploadPart(
                        uploadPartRequest,
                        RequestBody.fromByteBuffer(bb));

                CompletedPart part = CompletedPart.builder()
                        .partNumber(partNumber)
                        .checksumCRC32(partResponse.checksumCRC32()) // Provide
the calculated checksum.
                        .eTag(partResponse.eTag())
                        .build();
                completedParts.add(part);

                bb.clear();
```

```
                position += read;
                partNumber++;
            }
        } catch (IOException e) {
            System.err.println(e.getMessage());
        }

        // Complete the multipart upload.
        s3Client.completeMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)

.multipartUpload(CompletedMultipartUpload.builder().parts(completedParts).build()));
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - UploadPart

Trabalhar com objetos versionados do Amazon S3 usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie um bucket do S3 versionado.
- Obtenha todas as versões de um objeto.
- Reverta um objeto para uma versão anterior.
- Exclua e restaure um objeto versionado.
- Exclua, permanentemente, todas as versões de um objeto.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações do S3.

```
def create_versioned_bucket(bucket_name, prefix):
    """
    Creates an Amazon S3 bucket, enables it for versioning, and configures a
 lifecycle
    that expires noncurrent object versions after 7 days.

    Adding a lifecycle configuration to a versioned bucket is a best practice.
    It helps prevent objects in the bucket from accumulating a large number of
    noncurrent versions, which can slow down request performance.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket_name: The name of the bucket to create.
    :param prefix: Identifies which objects are automatically expired under the
                   configured lifecycle rules.
    :return: The newly created bucket.
    """
    try:
        bucket = s3.create_bucket(
            Bucket=bucket_name,
            CreateBucketConfiguration={
                "LocationConstraint": s3.meta.client.meta.region_name
            },
        )
        logger.info("Created bucket %s.", bucket.name)
    except ClientError as error:
        if error.response["Error"]["Code"] == "BucketAlreadyOwnedByYou":
            logger.warning("Bucket %s already exists! Using it.", bucket_name)
            bucket = s3.Bucket(bucket_name)
        else:
```

```
            logger.exception("Couldn't create bucket %s.", bucket_name)
            raise

    try:
        bucket.Versioning().enable()
        logger.info("Enabled versioning on bucket %s.", bucket.name)
    except ClientError:
        logger.exception("Couldn't enable versioning on bucket %s.", bucket.name)
        raise

    try:
        expiration = 7
        bucket.LifecycleConfiguration().put(
            LifecycleConfiguration={
                "Rules": [
                    {
                        "Status": "Enabled",
                        "Prefix": prefix,
                        "NoncurrentVersionExpiration": {"NoncurrentDays":
 expiration},
                    }
                ]
            }
        )
        logger.info(
            "Configured lifecycle to expire noncurrent versions after %s days "
            "on bucket %s.",
            expiration,
            bucket.name,
        )
    except ClientError as error:
        logger.warning(
            "Couldn't configure lifecycle on bucket %s because %s. "
            "Continuing anyway.",
            bucket.name,
            error,
        )

    return bucket



def rollback_object(bucket, object_key, version_id):
    """
```

```
    Rolls back an object to an earlier version by deleting all versions that
    occurred after the specified rollback version.

    Usage is shown in the usage_demo_single_object function at the end of this
module.

    :param bucket: The bucket that holds the object to roll back.
    :param object_key: The object to roll back.
    :param version_id: The version ID to roll back to.
    """
    # Versions must be sorted by last_modified date because delete markers are
    # at the end of the list even when they are interspersed in time.
    versions = sorted(
        bucket.object_versions.filter(Prefix=object_key),
        key=attrgetter("last_modified"),
        reverse=True,
    )

    logger.debug(
        "Got versions:\n%s",
        "\n".join(
            [
                f"\t{version.version_id}, last modified {version.last_modified}"
                for version in versions
            ]
        ),
    )

    if version_id in [ver.version_id for ver in versions]:
        print(f"Rolling back to version {version_id}")
        for version in versions:
            if version.version_id != version_id:
                version.delete()
                print(f"Deleted version {version.version_id}")
            else:
                break

        print(f"Active version is now {bucket.Object(object_key).version_id}")
    else:
        raise KeyError(
            f"{version_id} was not found in the list of versions for "
f"{object_key}."
        )
```

```
def revive_object(bucket, object_key):
    """
    Revives a versioned object that was deleted by removing the object's active
    delete marker.
    A versioned object presents as deleted when its latest version is a delete
 marker.
    By removing the delete marker, we make the previous version the latest
 version
    and the object then presents as *not* deleted.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to revive.
    """
    # Get the latest version for the object.
    response = s3.meta.client.list_object_versions(
        Bucket=bucket.name, Prefix=object_key, MaxKeys=1
    )

    if "DeleteMarkers" in response:
        latest_version = response["DeleteMarkers"][0]
        if latest_version["IsLatest"]:
            logger.info(
                "Object %s was indeed deleted on %s. Let's revive it.",
                object_key,
                latest_version["LastModified"],
            )
            obj = bucket.Object(object_key)
            obj.Version(latest_version["VersionId"]).delete()
            logger.info(
                "Revived %s, active version is now %s  with body '%s'",
                object_key,
                obj.version_id,
                obj.get()["Body"].read(),
            )
        else:
            logger.warning(
                "Delete marker is not the latest version for %s!", object_key
            )
    elif "Versions" in response:
```

```
        logger.warning("Got an active version for %s, nothing to do.",
 object_key)
    else:
        logger.error("Couldn't get any version info for %s.", object_key)



def permanently_delete_object(bucket, object_key):
    """
    Permanently deletes a versioned object by deleting all of its versions.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to delete.
    """
    try:
        bucket.object_versions.filter(Prefix=object_key).delete()
        logger.info("Permanently deleted all versions of object %s.", object_key)
    except ClientError:
        logger.exception("Couldn't delete all versions of %s.", object_key)
        raise
```

Carregue uma estrofe de poema para um objeto versionado e realize uma série de ações nela.

```
def usage_demo_single_object(obj_prefix="demo-versioning/"):
    """
    Demonstrates usage of versioned object functions. This demo uploads a stanza
    of a poem and performs a series of revisions, deletions, and revivals on it.

    :param obj_prefix: The prefix to assign to objects created by this demo.
    """
    with open("father_william.txt") as file:
        stanzas = file.read().split("\n\n")

    width = get_terminal_size((80, 20))[0]
    print("-" * width)
    print("Welcome to the usage demonstration of Amazon S3 versioning.")
```

```
    print(
        "This demonstration uploads a single stanza of a poem to an Amazon "
        "S3 bucket and then applies various revisions to it."
    )
    print("-" * width)
    print("Creating a version-enabled bucket for the demo...")
    bucket = create_versioned_bucket("bucket-" + str(uuid.uuid1()), obj_prefix)

    print("\nThe initial version of our stanza:")
    print(stanzas[0])

    # Add the first stanza and revise it a few times.
    print("\nApplying some revisions to the stanza...")
    obj_stanza_1 = bucket.Object(f"{obj_prefix}stanza-1")
    obj_stanza_1.put(Body=bytes(stanzas[0], "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0].upper(), "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0].lower(), "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0][::-1], "utf-8"))
    print(
        "The latest version of the stanza is now:",
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
    )

    # Versions are returned in order, most recent first.
    obj_stanza_1_versions =
 bucket.object_versions.filter(Prefix=obj_stanza_1.key)
    print(
        "The version data of the stanza revisions:",
        *[
            f"    {version.version_id}, last modified {version.last_modified}"
            for version in obj_stanza_1_versions
        ],
        sep="\n",
    )

    # Rollback two versions.
    print("\nRolling back two versions...")
    rollback_object(bucket, obj_stanza_1.key, list(obj_stanza_1_versions)
[2].version_id)
    print(
        "The latest version of the stanza:",
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
```

```
    )

    # Delete the stanza
    print("\nDeleting the stanza...")
    obj_stanza_1.delete()
    try:
        obj_stanza_1.get()
    except ClientError as error:
        if error.response["Error"]["Code"] == "NoSuchKey":
            print("The stanza is now deleted (as expected).")
        else:
            raise

    # Revive the stanza
    print("\nRestoring the stanza...")
    revive_object(bucket, obj_stanza_1.key)
    print(
        "The stanza is restored! The latest version is again:",
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
    )

    # Permanently delete all versions of the object. This cannot be undone!
    print("\nPermanently deleting all versions of the stanza...")
    permanently_delete_object(bucket, obj_stanza_1.key)
    obj_stanza_1_versions =
 bucket.object_versions.filter(Prefix=obj_stanza_1.key)
    if len(list(obj_stanza_1_versions)) == 0:
        print("The stanza has been permanently deleted and now has no versions.")
    else:
        print("Something went wrong. The stanza still exists!")

    print(f"\nRemoving {bucket.name}...")
    bucket.delete()
    print(f"{bucket.name} deleted.")
    print("Demo done!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateBucket

- DeleteObject
- ListObjectVersions
- PutBucketLifecycleConfiguration

Exemplos sem servidor para o Amazon S3 usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Storage Service (Amazon S3) com SDKs da AWS.

Exemplos

- Invocar uma função do Lambda em um acionador do Amazon S3

Invocar uma função do Lambda em um acionador do Amazon S3

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando .NET.

```
using System.Threading.Tasks;
using Amazon.Lambda.Core;
using Amazon.S3;
using System;
using Amazon.Lambda.S3Events;
using System.Web;
```

```
// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace S3Integration
{
    public class Function
    {
        private static AmazonS3Client _s3Client;
        public Function() : this(null)
        {
        }

        internal Function(AmazonS3Client s3Client)
        {
            _s3Client = s3Client ?? new AmazonS3Client();
        }

        public async Task<string> Handler(S3Event evt, ILambdaContext context)
        {
            try
            {
                if (evt.Records.Count <= 0)
                {
                    context.Logger.LogLine("Empty S3 Event received");
                    return string.Empty;
                }

                var bucket = evt.Records[0].S3.Bucket.Name;
                var key = HttpUtility.UrlDecode(evt.Records[0].S3.Object.Key);

                context.Logger.LogLine($"Request is for {bucket} and {key}");

                var objectResult = await _s3Client.GetObjectAsync(bucket, key);

                context.Logger.LogLine($"Returning {objectResult.Key}");

                return objectResult.Key;
            }
            catch (Exception e)
            {
                context.Logger.LogLine($"Error processing request -
 {e.Message}");
```

```
                return string.Empty;
            }
        }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

func handler(ctx context.Context, s3Event events.S3Event) error {
 sdkConfig, err := config.LoadDefaultConfig(ctx)
 if err != nil {
  log.Printf("failed to load default config: %s", err)
  return err
 }
 s3Client := s3.NewFromConfig(sdkConfig)

 for _, record := range s3Event.Records {
  bucket := record.S3.Bucket.Name
  key := record.S3.Object.URLDecodedKey
```

```
  headOutput, err := s3Client.HeadObject(ctx, &s3.HeadObjectInput{
   Bucket: &bucket,
   Key:    &key,
  })
  if err != nil {
   log.Printf("error getting head of object %s/%s: %s", bucket, key, err)
   return err
  }
  log.Printf("successfully retrieved %s/%s of type %s", bucket, key,
 *headOutput.ContentType)
 }

 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Java.

```
package example;

import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.S3Client;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.S3Event;
```

```
import
 com.amazonaws.services.lambda.runtime.events.models.s3.S3EventNotification.S3EventNotifi

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Handler implements RequestHandler<S3Event, String> {
    private static final Logger logger = LoggerFactory.getLogger(Handler.class);
    @Override
    public String handleRequest(S3Event s3event, Context context) {
        try {
          S3EventNotificationRecord record = s3event.getRecords().get(0);
          String srcBucket = record.getS3().getBucket().getName();
          String srcKey = record.getS3().getObject().getUrlDecodedKey();

          S3Client s3Client = S3Client.builder().build();
          HeadObjectResponse headObject = getHeadObject(s3Client, srcBucket,
 srcKey);

          logger.info("Successfully retrieved " + srcBucket + "/" + srcKey + " of
 type " + headObject.contentType());

          return "Ok";
        } catch (Exception e) {
          throw new RuntimeException(e);
        }
    }

    private HeadObjectResponse getHeadObject(S3Client s3Client, String bucket,
 String key) {
        HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                .bucket(bucket)
                .key(key)
                .build();
        return s3Client.headObject(headObjectRequest);
    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do S3 com o uso do JavaScript Lambda.

```
const aws = require('aws-sdk');

const s3 = new aws.S3({ apiVersion: '2006-03-01' });

exports.handler = async (event, context) => {
    // Get the object from the event and show its content type
    const bucket = event.Records[0].s3.bucket.name;
    const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g,
 ' '));
    const params = {
        Bucket: bucket,
        Key: key,
    };
    try {
        const { ContentType } = await s3.headObject(params).promise();
        console.log('CONTENT TYPE:', ContentType);
        return ContentType;
    } catch (err) {
        console.log(err);
        const message = `Error getting object ${key} from bucket ${bucket}. Make
 sure they exist and your bucket is in the same region as this function.`;
        console.log(message);
        throw new Error(message);
    }
};
```

Consumindo um evento do S3 com o uso do TypeScript Lambda.

```
import { S3Event } from 'aws-lambda';
```

```
import { S3Client, HeadObjectCommand } from '@aws-sdk/client-s3';

const s3 = new S3Client({ region: process.env.AWS_REGION });

export const handler = async (event: S3Event): Promise<string | undefined> => {
  // Get the object from the event and show its content type
  const bucket = event.Records[0].s3.bucket.name;
  const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
  const params = {
    Bucket: bucket,
    Key: key,
  };
  try {
    const { ContentType } = await s3.send(new HeadObjectCommand(params));
    console.log('CONTENT TYPE:', ContentType);
    return ContentType;
  } catch (err) {
    console.log(err);
    const message = `Error getting object ${key} from bucket ${bucket}. Make sure
 they exist and your bucket is in the same region as this function.`;
    console.log(message);
    throw new Error(message);
  }
};
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Python.

```
import json
import urllib.parse
import boto3
```

```
print('Loading function')

s3 = boto3.client('s3')


def lambda_handler(event, context):
    #print("Received event: " + json.dumps(event, indent=2))

    # Get the object from the event and show its content type
    bucket = event['Records'][0]['s3']['bucket']['name']
    key = urllib.parse.unquote_plus(event['Records'][0]['s3']['object']['key'],
 encoding='utf-8')
    try:
        response = s3.get_object(Bucket=bucket, Key=key)
        print("CONTENT TYPE: " + response['ContentType'])
        return response['ContentType']
    except Exception as e:
        print(e)
        print('Error getting object {} from bucket {}. Make sure they exist and
 your bucket is in the same region as this function.'.format(key, bucket))
        raise e
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Rust.

```
use aws_lambda_events::event::s3::S3Event;
use aws_sdk_s3::{Client};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};


/// Main function
#[tokio::main]
```

```
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    // Initialize the AWS SDK for Rust
    let config = aws_config::load_from_env().await;
    let s3_client = Client::new(&config);

    let res = run(service_fn(|request: LambdaEvent<S3Event>| {
        function_handler(&s3_client, request)
    })).await;

    res
}

async fn function_handler(
    s3_client: &Client,
    evt: LambdaEvent<S3Event>
) -> Result<(), Error> {
    tracing::info!(records = ?evt.payload.records.len(), "Received request from
 SQS");

    if evt.payload.records.len() == 0 {
        tracing::info!("Empty S3 event received");
    }

    let bucket = evt.payload.records[0].s3.bucket.name.as_ref().expect("Bucket
 name to exist");
    let key = evt.payload.records[0].s3.object.key.as_ref().expect("Object key to
 exist");

    tracing::info!("Request is for {} and object {}", bucket, key);

    let s3_get_object_result = s3_client
        .get_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await;

    match s3_get_object_result {
```

```
        Ok(_) => tracing::info!("S3 Get Object success, the s3GetObjectResult
 contains a 'body' property of type ByteStream"),
        Err(_) => tracing::info!("Failure with S3 Get Object request")
    }

    Ok(())
}
```

Exemplos do Amazon S3 entre serviços usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Storage Service (Amazon S3) com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação Amazon Transcribe
- Converter texto em fala e de volta em texto usando um AWS SDK
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação de exploração do Amazon Textract
- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar entidades em texto extraído de uma imagem usando um AWS SDK
- Detectar faces em uma imagem usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Salvar o EXIF e outras informações de imagem usando um AWS SDK

Criar uma aplicação Amazon Transcribe

O exemplo de código a seguir mostra como usar o Amazon Transcribe para transcrever e exibir gravações de voz no navegador.

JavaScript

SDK para JavaScript (v3)

Crie uma aplicação que use o Amazon Transcribe para transcrever e exibir gravações de voz no navegador. A aplicação usa dois buckets do Amazon Simple Storage Service (Amazon S3), um para hospedar o código da aplicação e outro para armazenar transcrições. A aplicação usa um grupo de usuários do Amazon Cognito para autenticar seus usuários. Os usuários autenticados têm permissões do AWS Identity and Access Management (IAM) para acessar os serviços da AWS necessários.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon Transcribe

Converter texto em fala e de volta em texto usando um AWS SDK

O código de exemplo a seguir mostra como:

- Usar o Amazon Polly para sintetizar um arquivo de entrada de texto simples (UTF-8) para um arquivo de áudio.
- Faça upload do arquivo de áudio para um bucket do Amazon S3.
- Usar o Amazon Transcribe para converter o arquivo de áudio em texto.
- Exibir o texto.

Rust

SDK for Rust

Use o Amazon Polly para sintetizar um arquivo de texto simples (UTF-8) para um arquivo de áudio, fazer upload do arquivo de áudio para um bucket do Amazon S3, usar o Amazon Transcribe para converter esse arquivo de áudio em texto e exibir o texto.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly
- Amazon S3
- Amazon Transcribe

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB

- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação de exploração do Amazon Textract

Os exemplos de código a seguir mostram como explorar a saída do Amazon Textract por meio de uma aplicação interativa.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma

página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon Textract para detectar elementos de texto, formulários e tabelas em uma imagem de documento. A imagem de entrada e a saída do Amazon Textract são mostradas em uma aplicaçãoTkinter que permite explorar os elementos detectados.

- Envie uma imagem de documento para o Amazon Textract e explore a saída dos elementos detectados.
- Envie imagens diretamente para o Amazon Textract ou por meio de um bucket do Amazon Simple Storage Service (Amazon S3).
- Use APIs assíncronas para iniciar um trabalho que publica uma notificação em um tópico do Amazon Simple Notification Service (Amazon SNS) quando o trabalho for concluído.
- Faça uma pesquisa em uma fila do Amazon Simple Queue Service (Amazon SQS) para obter uma mensagem de conclusão do trabalho e exiba os resultados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar equipamentos de proteção individual (EPI) em imagens.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda que detecta imagens com equipamento de proteção individual.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar equipamentos de proteção individual (EPI) em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação salva os resultados em uma tabela do Amazon DynamoDB e envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Atualizar uma tabela do DynamoDB com resultados.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar entidades em texto extraído de uma imagem usando um AWS SDK

O exemplo de código a seguir mostra como usar o Amazon Comprehend para detectar entidades em texto extraído pelo Amazon Textract de uma imagem armazenada no Amazon S3.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) em um bloco de anotações Jupyter para detectar entidades em texto extraído de uma imagem. Este exemplo usa o Amazon Textract para extrair texto de uma imagem armazenada no Amazon Simple Storage Service (Amazon S3) e no Amazon Comprehend para detectar entidades no texto extraído.

Este exemplo é um bloco de anotações Jupyter e deve ser executado em um ambiente que possa hospedar blocos de anotações. Para obter instruções sobre como executar o exemplo usando a Amazon SageMaker, consulte as instruções em TextractAndComprehendNotebook.ipynb.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon S3
- Amazon Textract

Detectar faces em uma imagem usando um AWS SDK

O código de exemplo a seguir mostra como:

- Salve uma imagem em um bucket do Amazon S3.
- Use o Amazon Rekognition para detectar detalhes faciais, como faixa etária, sexo e emoções (sorriso, etc.).
- Exibir esses detalhes.

Rust

SDK for Rust

Salve a imagem em um bucket do Amazon S3 com um prefixo uploads, use o Amazon Rekognition para detectar detalhes faciais, como faixa etária, sexo e emoções (sorriso, etc.), e exiba esses detalhes.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar objetos por categoria em imagens.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de objetos usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar uma aplicação Web que permite a você fazer o seguinte:

- Carregar fotos em um bucket do Amazon Simple Storage Service (Amazon S3).
- Usar o Amazon Rekognition para analisar e rotular as fotos.
- Usar o Amazon Simple Email Service (Amazon SES) para enviar relatórios de análise da imagem por e-mail.

Este exemplo contém dois componentes principais: uma página da Web criada com o React e um serviço REST escrito em Python que é criado com o Flask-RESTful. JavaScript

Você pode usar a página da Web do React para:

- Exibir uma lista de imagens que estão armazenadas no bucket do S3.
- Carregar imagens do computador para o bucket do S3.
- Exibir imagens e rótulos que identificam os itens detectados na imagem.
- Obter um relatório de todas as imagens no bucket do S3 e enviar um relatório por e-mail.

A página da Web chama o serviço REST. O serviço envia solicitações à AWS para realizar as seguintes ações:

- Obter e filtrar a lista de imagens no bucket do S3.
- Carregar fotos no bucket do S3.
- Usar o Amazon Rekognition para analisar fotos individuais e obter uma lista dos rótulos que identifiquem os itens detectados nas fotos.
- Analisar todas as fotos no bucket do S3 e usar o Amazon SES para enviar um relatório por e-mail.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar pessoas e objetos em um vídeo com o Amazon Rekognition.

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Salvar o EXIF e outras informações de imagem usando um AWS SDK

O código de exemplo a seguir mostra como:

- Obter informações de EXIF de um arquivo JPG, JPEG ou PNG.
- Faça upload do arquivo de imagem para um bucket do Amazon S3.
- Use o Amazon Rekognition para identificar os três principais atributos (rótulos) no arquivo.
- Adicione as informações de EXIF e rótulo a uma tabela do Amazon DynamoDB na região.

Rust

SDK for Rust

Obtenha informações de EXIF de um arquivo JPG, JPEG ou PNG, faça upload do arquivo de imagem para um bucket do Amazon S3, use o Amazon Rekognition para identificar os três principais atributos (rótulos no Amazon Rekognition) no arquivo e adicione as informações de EXIF e de rótulo a uma tabela do Amazon DynamoDB na região.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon Rekognition
- Amazon S3

Exemplos de código do S3 Glacier usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon S3 Glacier com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do desenvolvedor do S3 Glacier – Mais informações sobre o S3 Glacier.
- Referência da API do S3 Glacier – Detalhes sobre todas as ações disponíveis do S3 Glacier.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Amazon S3 Glacier

O exemplo de código a seguir mostra como começar a usar o Amazon S3 Glacier.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.Glacier;
using Amazon.Glacier.Model;

namespace GlacierActions;

public static class HelloGlacier
{
    static async Task Main()
    {
        var glacierService = new AmazonGlacierClient();

        Console.WriteLine("Hello Amazon Glacier!");
        Console.WriteLine("Let's list your Glacier vaults:");

        // You can use await and any of the async methods to get a response.
        // Let's get the vaults using a paginator.
        var glacierVaultPaginator = glacierService.Paginators.ListVaults(
            new ListVaultsRequest { AccountId = "-" });

        await foreach (var vault in glacierVaultPaginator.VaultList)
        {
            Console.WriteLine($"{vault.CreationDate}:{vault.VaultName}, ARN:
{vault.VaultARN}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for .NET da API.

Exemplos de código

- Ações do S3 Glacier usando AWS SDKs
  - Adicionar tags a um cofre do Amazon S3 Glacier usando um AWS SDK
  - Crie um multipart upload em um cofre do Amazon S3 Glacier usando um SDK da AWS
  - Crie um cofre do Amazon S3 Glacier usando um SDK da AWS
  - Exclua um cofre do Amazon S3 Glacier usando um SDK da AWS
  - Exclua um arquivo do Amazon S3 Glacier usando um SDK da AWS
  - Exclua notificações do cofre do Amazon S3 Glacier usando um SDK da AWS

- Descreva um trabalho do Amazon S3 Glacier usando um SDK da AWS
- Descreva um cofre do Amazon S3 Glacier usando um SDK da AWS
- Baixe um arquivo do Amazon S3 Glacier usando um SDK da AWS
- Obtenha a saída de trabalho do Amazon S3 Glacier usando um SDK da AWS
- Obtenha uma configuração de notificação do cofre do Amazon S3 Glacier usando um SDK da AWS
- Listar trabalhos do Amazon S3 Glacier usando um AWS SDK
- Liste tags para um cofre do Amazon S3 Glacier usando um SDK da AWS
- Liste cofres do Amazon S3 Glacier usando um SDK da AWS
- Recupere um inventário de cofre do Amazon S3 Glacier usando um SDK da AWS
- Recupere um arquivo de um cofre do Amazon S3 Glacier usando um SDK da AWS
- Configure notificações do cofre do Amazon S3 Glacier usando um SDK da AWS
- Carregar um arquivo em um cofre do Amazon S3 Glacier usando um AWS SDK

- Cenários do S3 Glacier usando AWS SDKs
  - Arquive um arquivo no Amazon S3 Glacier, receba notificações e inicie um trabalho usando um AWS SDK
  - Obtenha o conteúdo do arquivo do Amazon S3 Glacier e exclua o arquivo usando um SDK da AWS

Ações do S3 Glacier usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon S3 Glacier com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários do S3 Glacier usando AWS SDKs.

Exemplos

- Adicionar tags a um cofre do Amazon S3 Glacier usando um AWS SDK
- Crie um multipart upload em um cofre do Amazon S3 Glacier usando um SDK da AWS
- Crie um cofre do Amazon S3 Glacier usando um SDK da AWS
- Exclua um cofre do Amazon S3 Glacier usando um SDK da AWS
- Exclua um arquivo do Amazon S3 Glacier usando um SDK da AWS

- Exclua notificações do cofre do Amazon S3 Glacier usando um SDK da AWS
- Descreva um trabalho do Amazon S3 Glacier usando um SDK da AWS
- Descreva um cofre do Amazon S3 Glacier usando um SDK da AWS
- Baixe um arquivo do Amazon S3 Glacier usando um SDK da AWS
- Obtenha a saída de trabalho do Amazon S3 Glacier usando um SDK da AWS
- Obtenha uma configuração de notificação do cofre do Amazon S3 Glacier usando um SDK da AWS
- Listar trabalhos do Amazon S3 Glacier usando um AWS SDK
- Liste tags para um cofre do Amazon S3 Glacier usando um SDK da AWS
- Liste cofres do Amazon S3 Glacier usando um SDK da AWS
- Recupere um inventário de cofre do Amazon S3 Glacier usando um SDK da AWS
- Recupere um arquivo de um cofre do Amazon S3 Glacier usando um SDK da AWS
- Configure notificações do cofre do Amazon S3 Glacier usando um SDK da AWS
- Carregar um arquivo em um cofre do Amazon S3 Glacier usando um AWS SDK

Adicionar tags a um cofre do Amazon S3 Glacier usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar tags a um cofre do Amazon S3 Glacier.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Add tags to the items in an Amazon S3 Glacier vault.
/// </summary>
/// <param name="vaultName">The name of the vault to add tags to.</param>
/// <param name="key">The name of the object to tag.</param>
/// <param name="value">The tag value to add.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddTagsToVaultAsync(string vaultName, string key,
 string value)
    {
        var request = new AddTagsToVaultRequest
        {
            Tags = new Dictionary<string, string>
                {
                    { key, value },
                },
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.AddTagsToVaultAsync(request);
        return response.HttpStatusCode == HttpStatusCode.NoContent;
    }
```

- Para obter detalhes da API, consulte AddTagsToVaulta Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir adiciona duas tags a um cofre chamado `my-vault`:

```
aws glacier add-tags-to-vault --account-id - --vault-name my-vault --tags
 id=1234,date=july2015
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte AddTagsToVaultem Referência de AWS CLI Comandos.

Crie um multipart upload em um cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um upload fracionado para um cofre do Amazon S3 Glacier.

CLI

AWS CLI

O comando a seguir carrega a primeira parte de 1 MiB (1024 x 1024 bytes) de um arquivamento:

```
aws glacier upload-multipart-part --body part1 --range 'bytes
 0-1048575/*' --account-id - --vault-name my-vault --upload-
id 19gaRezEXAMPLES6Ry5YYdqthHOC_kGRCT03L9yetr220UmPtBYKk-
OssZtLqyFu7sY1_lR7vgFuJV6NtcV5zpsJ
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

O parâmetro de corpo segue um caminho para um arquivo da parte no sistema de arquivos local. O parâmetro de intervalo usa um intervalo de conteúdo HTTP indicando os bytes que a peça ocupa no arquivamento concluído. O ID de upload é retornado pelo comando `aws glacier initiate-multipart-upload` e também pode ser coletado usando `aws glacier list-multipart-uploads`.

Para ter mais informações sobre uploads de várias partes para o Amazon Glacier usando a AWS CLI, consulte Using Amazon Glacier no Guia do usuário da AWS CLI.

- Para obter detalhes da API, consulte UploadMultipartPartna Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um multipart upload de pedaços de 1 megabyte de um objeto Buffer.

```
// Create a new service object and some supporting variables
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" }),
```

```
  vaultName = "YOUR_VAULT_NAME",
  buffer = new Buffer(2.5 * 1024 * 1024), // 2.5MB buffer
  partSize = 1024 * 1024, // 1MB chunks,
  numPartsLeft = Math.ceil(buffer.length / partSize),
  startTime = new Date(),
  params = { vaultName: vaultName, partSize: partSize.toString() };

// Compute the complete SHA-256 tree hash so we can pass it
// to completeMultipartUpload request at the end
var treeHash = glacier.computeChecksums(buffer).treeHash;

// Initiate the multipart upload
console.log("Initiating upload to", vaultName);
// Call Glacier to initiate the upload.
glacier.initiateMultipartUpload(params, function (mpErr, multipart) {
  if (mpErr) {
    console.log("Error!", mpErr.stack);
    return;
  }
  console.log("Got upload ID", multipart.uploadId);

  // Grab each partSize chunk and upload it as a part
  for (var i = 0; i < buffer.length; i += partSize) {
    var end = Math.min(i + partSize, buffer.length),
      partParams = {
        vaultName: vaultName,
        uploadId: multipart.uploadId,
        range: "bytes " + i + "-" + (end - 1) + "/*",
        body: buffer.slice(i, end),
      };

    // Send a single part
    console.log("Uploading part", i, "=", partParams.range);
    glacier.uploadMultipartPart(partParams, function (multiErr, mData) {
      if (multiErr) return;
      console.log("Completed part", this.request.params.range);
      if (--numPartsLeft > 0) return; // complete only when all parts uploaded

      var doneParams = {
        vaultName: vaultName,
        uploadId: multipart.uploadId,
        archiveSize: buffer.length.toString(),
        checksum: treeHash, // the computed tree hash
      };
```

```
      console.log("Completing upload...");
      glacier.completeMultipartUpload(doneParams, function (err, data) {
        if (err) {
          console.log("An error occurred while uploading the archive");
          console.log(err);
        } else {
          var delta = (new Date() - startTime) / 1000;
          console.log("Completed upload in", delta, "seconds");
          console.log("Archive ID:", data.archiveId);
          console.log("Checksum:  ", data.checksum);
        }
      });
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadMultipartPart a Referência AWS SDK for JavaScript da API.

Crie um cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to create.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateVaultAsync(string vaultName)
    {
        var request = new CreateVaultRequest
        {
            // Setting the AccountId to "-" means that
            // the account associated with the current
            // account will be used.
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.CreateVaultAsync(request);

        Console.WriteLine($"Created {vaultName} at: {response.Location}");

        return response.HttpStatusCode == HttpStatusCode.Created;
    }
```

- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir cria um cofre chamado `my-vault`.

```
aws glacier create-vault --vault-name my-vault --account-id -
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte CreateVaultna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.CreateVaultRequest;
import software.amazon.awssdk.services.glacier.model.CreateVaultResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateVault {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <vaultName>

                Where:
                   vaultName - The name of the vault to create.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
```

```
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createGlacierVault(glacier, vaultName);
        glacier.close();
    }

    public static void createGlacierVault(GlacierClient glacier, String
 vaultName) {
        try {
            CreateVaultRequest vaultRequest = CreateVaultRequest.builder()
                    .vaultName(vaultName)
                    .build();

            CreateVaultResponse createVaultResult =
 glacier.createVault(vaultRequest);
            System.out.println("The URI of the new vault is " +
 createVaultResult.location());

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Criar o cofre.

```
// Load the SDK for JavaScript
import { CreateVaultCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME
const params = { vaultName: vaultname };

const run = async () => {
  try {
    const data = await glacierClient.send(new CreateVaultCommand(params));
    console.log("Success, vault created!");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error");
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
// Call Glacier to create the vault
glacier.createVault({ vaultName: "YOUR_VAULT_NAME" }, function (err) {
  if (!err) {
    console.log("Created vault!");
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    def create_vault(self, vault_name):
        """
        Creates a vault.

        :param vault_name: The name to give the vault.
        :return: The newly created vault.
        """
        try:
            vault = self.glacier_resource.create_vault(vaultName=vault_name)
            logger.info("Created vault %s.", vault_name)
        except ClientError:
            logger.exception("Couldn't create vault %s.", vault_name)
            raise
        else:
            return vault
```

- Para obter detalhes da API, consulte a CreateVaultReferência da API AWSSDK for Python (Boto3).

Exclua um cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obtenha o conteúdo do arquivo e exclua o arquivo

CLI

AWS CLI

O comando a seguir exclui um cofre chamado `my-vault`:

```
aws glacier delete-vault --vault-name my-vault --account-id -
```

Esse comando não produz nenhuma saída. O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte DeleteVaultna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DeleteVaultRequest;
import software.amazon.awssdk.services.glacier.model.GlacierException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteVault {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <vaultName>

                Where:
                   vaultName - The name of the vault to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String vaultName = args[0];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteGlacierVault(glacier, vaultName);
        glacier.close();
    }

    public static void deleteGlacierVault(GlacierClient glacier, String
 vaultName) {
        try {
            DeleteVaultRequest delVaultRequest = DeleteVaultRequest.builder()
                    .vaultName(vaultName)
                    .build();

            glacier.deleteVault(delVaultRequest);
            System.out.println("The vault was deleted!");

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteVaulta Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
```

```
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def delete_vault(vault):
        """
        Deletes a vault.

        :param vault: The vault to delete.
        """
        try:
            vault.delete()
            logger.info("Deleted vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't delete vault %s.", vault.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteVaultReferência da API AWSSDK for Python (Boto3).

Exclua um arquivo do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um arquivo do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obtenha o conteúdo do arquivo e exclua o arquivo

CLI

AWS CLI

Para excluir um arquivamento de um cofre

O exemplo de `delete-archive` a seguir remove o arquivamento especificado de `example_vault`.

```
aws glacier delete-archive \
    --account-id 111122223333  \
    --vault-name example_vault \
    --archive-id Sc0u9ZP8yaWkmh-XGlIvAVprtLhaLCGnNwNl5I5x9HqPIkX5mjc0DrId3Ln-
Gi_k2HzmlIDZUz117KSdVMdMXLuFWi9PJUitxWO73edQ43eTlMWkH0pd9zVSAuV_XXZBVhKhyGhJ7w
```

Este comando não produz saída.

- Para obter detalhes da API, consulte DeleteArchivena Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DeleteArchiveRequest;
import software.amazon.awssdk.services.glacier.model.GlacierException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteArchive {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:    <vaultName> <accountId> <archiveId>

                Where:
                   vaultName - The name of the vault that contains the archive to
 delete.
                   accountId - The account ID value.
                   archiveId - The archive ID value.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        String accountId = args[1];
        String archiveId = args[2];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteGlacierArchive(glacier, vaultName, accountId, archiveId);
        glacier.close();
    }

    public static void deleteGlacierArchive(GlacierClient glacier, String
 vaultName, String accountId,
            String archiveId) {
        try {
            DeleteArchiveRequest delArcRequest = DeleteArchiveRequest.builder()
                    .vaultName(vaultName)
                    .accountId(accountId)
                    .archiveId(archiveId)
                    .build();

            glacier.deleteArchive(delArcRequest);
            System.out.println("The archive was deleted.");

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteArchivea Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def delete_archive(archive):
        """
        Deletes an archive from a vault.

        :param archive: The archive to delete.
        """
        try:
            archive.delete()
            logger.info(
                "Deleted archive %s from vault %s.", archive.id,
 archive.vault_name
            )
        except ClientError:
            logger.exception("Couldn't delete archive %s.", archive.id)
            raise
```

- Para obter detalhes da API, consulte a DeleteArchiveReferência da API AWSSDK for Python (Boto3).

Exclua notificações do cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir notificações do cofre do Amazon S3 Glacier.

CLI

AWS CLI

Como remover as notificações do SNS de um cofre

O comando de `delete-vault-notifications` a seguir remove as notificações enviadas pelo Amazon Simple Notification Service (Amazon SNS) para o cofre especificado.

```
aws glacier delete-vault-notifications \
    --account-id 111122223333 \
    --vault-name example_vault
```

Este comando não produz saída.

- Para obter detalhes da API, consulte DeleteVaultNotificationsna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""
```

```
    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def stop_notifications(notification):
        """
        Stops notifications to the configured Amazon SNS topic.

        :param notification: The notification configuration to remove.
        """
        try:
            notification.delete()
            logger.info("Notifications stopped.")
        except ClientError:
            logger.exception("Couldn't stop notifications.")
            raise
```

- Para obter detalhes da API, consulte a DeleteVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Descreva um trabalho do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um trabalho do Amazon S3 Glacier.

CLI

AWS CLI

O seguinte comando recupera informações sobre um trabalho de recuperação de inventário no cofre `my-vault`:

```
aws glacier describe-job --account-id - --vault-name my-
vault --job-id zbxcm3Z_3z5UkoroF7SuZKrxgGoDc3RloGduS7Eg-
RO47Yc6FxsdGBgf_Q2DK5Ejh18CnTS5XW4_XqlNHS61dsO4CnMW
```

Saída:

```
{
    "InventoryRetrievalParameters": {
        "Format": "JSON"
    },
    "VaultARN": "arn:aws:glacier:us-west-2:0123456789012:vaults/my-vault",
    "Completed": false,
    "JobId": "zbxcm3Z_3z5UkoroF7SuZKrxgGoDc3RloGduS7Eg-
RO47Yc6FxsdGBgf_Q2DK5Ejh18CnTS5XW4_XqlNHS61dsO4CnMW",
    "Action": "InventoryRetrieval",
    "CreationDate": "2015-07-17T20:23:41.616Z",
    "StatusCode": "InProgress"
}
```

O ID do trabalho pode ser encontrado na saída de `aws glacier initiate-job` e `aws glacier list-jobs`. O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte DescribeJobna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    @staticmethod
    def get_job_status(job):
        """
        Gets the status of a job.

        :param job: The job to query.
        :return: The current status of the job.
        """
        try:
            job.load()
            logger.info(
                "Job %s is performing action %s and has status %s.",
                job.id,
                job.action,
                job.status_code,
            )
        except ClientError:
            logger.exception("Couldn't get status for job %s.", job.id)
            raise
        else:
            return job.status_code
```

- Para obter detalhes da API, consulte a DescribeJobReferência da API AWSSDK for Python (Boto3).

Descreva um cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um cofre do Amazon S3 Glacier.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to describe.</param>
    /// <returns>The Amazon Resource Name (ARN) of the vault.</returns>
    public async Task<string> DescribeVaultAsync(string vaultName)
    {
        var request = new DescribeVaultRequest
        {
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.DescribeVaultAsync(request);

        // Display the information about the vault.
        Console.WriteLine($"{response.VaultName}\tARN: {response.VaultARN}");
        Console.WriteLine($"Created on: {response.CreationDate}\tNumber
 of Archives: {response.NumberOfArchives}\tSize (in bytes):
 {response.SizeInBytes}");
        if (response.LastInventoryDate != DateTime.MinValue)
        {
            Console.WriteLine($"Last inventory: {response.LastInventoryDate}");
        }

        return response.VaultARN;
    }
```

- Para obter detalhes da API, consulte DescribeVaulta Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir recupera dados sobre um cofre chamado `my-vault`:

```
aws glacier describe-vault --vault-name my-vault --account-id -
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte DescribeVaultna Referência de AWS CLI Comandos.

Baixe um arquivo do Amazon S3 Glacier usando um SDK da AWS

O exemplo de código a seguir mostra como baixar um arquivo do Amazon S3 Glacier.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo usa a ArchiveTransferManager classe. Para obter detalhes da API, consulte ArchiveTransferManager.

```
    /// <summary>
    /// Download an archive from an Amazon S3 Glacier vault using the Archive
    /// Transfer Manager.
    /// </summary>
    /// <param name="vaultName">The name of the vault containing the object.</
param>
    /// <param name="archiveId">The Id of the archive to download.</param>
    /// <param name="localFilePath">The local directory where the file will
    /// be stored after download.</param>
    /// <returns>Async Task.</returns>
    public async Task<bool> DownloadArchiveWithArchiveManagerAsync(string
 vaultName, string archiveId, string localFilePath)
    {
        try
        {
            var manager = new ArchiveTransferManager(_glacierService);

            var options = new DownloadOptions
            {
                StreamTransferProgress = Progress!,
            };

            // Download an archive.
```

```
            Console.WriteLine("Initiating the archive retrieval job and then
polling SQS queue for the archive to be available.");
            Console.WriteLine("When the archive is available, downloading will
begin.");
            await manager.DownloadAsync(vaultName, archiveId, localFilePath,
options);

            return true;
        }
        catch (AmazonGlacierException ex)
        {
            Console.WriteLine(ex.Message);
            return false;
        }
    }

    /// <summary>
    /// Event handler to track the progress of the Archive Transfer Manager.
    /// </summary>
    /// <param name="sender">The object that raised the event.</param>
    /// <param name="args">The argument values from the object that raised the
    /// event.</param>
    static void Progress(object sender, StreamTransferProgressArgs args)
    {
        if (args.PercentDone != _currentPercentage)
        {
            _currentPercentage = args.PercentDone;
            Console.WriteLine($"Downloaded {_currentPercentage}%");
        }
    }
```

Obtenha a saída de trabalho do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como receber uma saída de trabalho do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obtenha o conteúdo do arquivo e exclua o arquivo

CLI

AWS CLI

O comando a seguir salva a saída de um trabalho de inventário do cofre em um arquivo no diretório atual chamado `output.json`:

```
aws glacier get-job-output --account-id - --vault-name my-
vault --job-id zbxcm3Z_3z5UkoroF7SuZKrxgGoDc3RloGduS7Eg-
RO47Yc6FxsdGBgf_Q2DK5Ejh18CnTS5XW4_XqlNHS61dsO4CnMW output.json
```

O `job-id` está disponível na saída de `aws glacier list-jobs`. Observe que o nome do arquivo de saída é um argumento posicional que não é prefixado por um nome de opção. O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

Saída:

```
{
    "status": 200,
    "acceptRanges": "bytes",
    "contentType": "application/json"
}
```

`output.json`:

```
{"VaultARN":"arn:aws:glacier:us-west-2:0123456789012:vaults/
my-vault","InventoryDate":"2015-04-07T00:26:18Z","ArchiveList":
[{"ArchiveId":"kKB7ymWJVpPSwhGP6ycSOAekp9ZYe_--zM_mw6k76ZFGEIWQX-
ybtRDvc2VkPSDtfKmQrj0IRQLSGsNuDp-
AJVlu2ccmDSyDUmZwKbwbpAdGATGDiB3hHO0bjbGehXTcApVud_wyDw","ArchiveDescription":"multipart
 upload
 test","CreationDate":"2015-04-06T22:24:34Z","Size":3145728,"SHA256TreeHash":"9628195fcdb
```

- Para obter detalhes da API, consulte GetJobOutputna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def get_job_output(job):
        """
        Gets the output of a job, such as a vault inventory or the contents of an
        archive.

        :param job: The job to get output from.
        :return: The job output, in bytes.
        """
        try:
            response = job.get_output()
            out_bytes = response["body"].read()
            logger.info("Read %s bytes from job %s.", len(out_bytes), job.id)
            if "archiveDescription" in response:
                logger.info(
                    "These bytes are described as '%s'",
 response["archiveDescription"]
                )
        except ClientError:
            logger.exception("Couldn't get output for job %s.", job.id)
            raise
        else:
```

```
            return out_bytes
```

- Para obter detalhes da API, consulte a GetJobOutputReferência da API AWSSDK for Python (Boto3).

Obtenha uma configuração de notificação do cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como obter a configuração de notificação do cofre do Amazon S3 Glacier.

CLI

AWS CLI

O seguinte comando captura uma descrição da configuração de notificação do cofre `my-vault`:

```
aws glacier get-vault-notifications --account-id - --vault-name my-vault
```

Saída:

```
{
    "vaultNotificationConfig": {
        "Events": [
            "InventoryRetrievalCompleted",
            "ArchiveRetrievalCompleted"
        ],
        "SNSTopic": "arn:aws:sns:us-west-2:0123456789012:my-vault"
    }
}
```

Se nenhuma notificação tiver sido configurada para o cofre, será retornado um erro. O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte GetVaultNotificationsna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def get_notification(vault):
        """
        Gets the currently notification configuration for a vault.

        :param vault: The vault to query.
        :return: The notification configuration for the specified vault.
        """
        try:
            notification = vault.Notification()
            logger.info(
                "Vault %s notifies %s on %s events.",
                vault.name,
                notification.sns_topic,
                notification.events,
            )
        except ClientError:
            logger.exception("Couldn't get notification data for %s.",
 vault.name)
            raise
        else:
            return notification
```

- Para obter detalhes da API, consulte a GetVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Listar trabalhos do Amazon S3 Glacier usando um AWS SDK

Os exemplos de código a seguir mostram como listar trabalhos do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Arquive um arquivo, receba notificações e inicie um trabalho
- Obtenha o conteúdo do arquivo e exclua o arquivo

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List Amazon S3 Glacier jobs.
    /// </summary>
    /// <param name="vaultName">The name of the vault to list jobs for.</param>
    /// <returns>A list of Amazon S3 Glacier jobs.</returns>
    public async Task<List<GlacierJobDescription>> ListJobsAsync(string
vaultName)
    {
        var request = new ListJobsRequest
        {
            // Using a hyphen "-" for the Account Id will
            // cause the SDK to use the Account Id associated
            // with the current account.
```

```
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.ListJobsAsync(request);

        return response.JobList;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir lista trabalhos em andamento e concluídos recentemente para um cofre chamado `my-vault`:

```
aws glacier list-jobs --account-id - --vault-name my-vault
```

Saída:

```
{
    "JobList": [
        {
            "VaultARN": "arn:aws:glacier:us-west-2:0123456789012:vaults/my-
vault",
            "RetrievalByteRange": "0-3145727",
            "SNSTopic": "arn:aws:sns:us-west-2:0123456789012:my-vault",
            "Completed": false,
            "SHA256TreeHash":
 "9628195fcdbcbbe76cdde932d4646fa7de5f219fb39823836d81f0cc0e18aa67",
            "JobId": "l7IL5-EkXyEY9Ws95fClzIbk2O5uLYaFdAYOi-
azsX_Z8V6NH4yERHzars8wTKYQMX6nBDI9cMNHzyZJO59-8N9aHWav",
            "ArchiveId": "kKB7ymWJVpPSwhGP6ycSOAekp9ZYe_--
zM_mw6k76ZFGEIWQX-ybtRDvc2VkPSDtfKmQrj0IRQLSGsNuDp-
AJVlu2ccmDSyDUmZwKbwbpAdGATGDiB3hHO0bjbGehXTcApVud_wyDw",
            "JobDescription": "Retrieve archive on 2015-07-17",
            "ArchiveSizeInBytes": 3145728,
            "Action": "ArchiveRetrieval",
```

```
            "ArchiveSHA256TreeHash":
 "9628195fcdbcbbe76cdde932d4646fa7de5f219fb39823836d81f0cc0e18aa67",
            "CreationDate": "2015-07-17T21:16:13.840Z",
            "StatusCode": "InProgress"
        },
        {
            "InventoryRetrievalParameters": {
                "Format": "JSON"
            },
            "VaultARN": "arn:aws:glacier:us-west-2:0123456789012:vaults/my-
vault",
            "Completed": false,
            "JobId": "zbxcm3Z_3z5UkoroF7SuZKrxgGoDc3RloGduS7Eg-
RO47Yc6FxsdGBgf_Q2DK5Ejh18CnTS5XW4_XqlNHS61dsO4CnMW",
            "Action": "InventoryRetrieval",
            "CreationDate": "2015-07-17T20:23:41.616Z",
            "StatusCode": ""InProgress""
        }
    ]
}
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte ListJobsna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
```

```
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type,
vault.name)
            raise
        else:
            return job_list
```

- Para obter detalhes da API, consulte a ListJobsReferência da API AWSSDK for Python (Boto3).

Liste tags para um cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como listar as tags de um cofre do Amazon S3 Glacier.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List tags for an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to list tags for.</param>
    /// <returns>A dictionary listing the tags attached to each object in the
    /// vault and its tags.</returns>
    public async Task<Dictionary<string, string>> ListTagsForVaultAsync(string
vaultName)
    {
        var request = new ListTagsForVaultRequest
        {
            // Using a hyphen "-" for the Account Id will
            // cause the SDK to use the Account Id associated
            // with the default user.
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.ListTagsForVaultAsync(request);

        return response.Tags;
    }
```

- Para obter detalhes da API, consulte ListTagsForVaulta Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir lista as tags aplicadas a um cofre chamado `my-vault`:

```
aws glacier list-tags-for-vault --account-id - --vault-name my-vault
```

Saída:

```
{
    "Tags": {
        "date": "july2015",
        "id": "1234"
    }
}
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte ListTagsForVaultna Referência de AWS CLI Comandos.

Liste cofres do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como listar cofres do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Amazon S3 Glacier vaults associated with the current account.
    /// </summary>
    /// <returns>A list containing information about each vault.</returns>
    public async Task<List<DescribeVaultOutput>> ListVaultsAsync()
    {
        var glacierVaultPaginator = _glacierService.Paginators.ListVaults(
            new ListVaultsRequest { AccountId = "-" });
        var vaultList = new List<DescribeVaultOutput>();

        await foreach (var vault in glacierVaultPaginator.VaultList)
        {
            vaultList.Add(vault);
        }

        return vaultList;
    }
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir lista os cofres na região e conta padrão:

```
aws glacier list-vaults --account-id -
```

Saída:

```
{
    "VaultList": [
        {
            "SizeInBytes": 3178496,
            "VaultARN": "arn:aws:glacier:us-west-2:0123456789012:vaults/my-
vault",
            "LastInventoryDate": "2015-04-07T00:26:19.028Z",
            "VaultName": "my-vault",
            "NumberOfArchives": 1,
            "CreationDate": "2015-04-06T21:23:45.708Z"
```

```
        }
    ]
}
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte ListVaultsna Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.model.ListVaultsRequest;
import software.amazon.awssdk.services.glacier.model.ListVaultsResponse;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DescribeVaultOutput;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListVaults {
    public static void main(String[] args) {
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();
```

```
        listAllVault(glacier);
        glacier.close();
    }

    public static void listAllVault(GlacierClient glacier) {
        boolean listComplete = false;
        String newMarker = null;
        int totalVaults = 0;
        System.out.println("Your Amazon Glacier vaults:");
        try {
            while (!listComplete) {
                ListVaultsResponse response = null;
                if (newMarker != null) {
                    ListVaultsRequest request = ListVaultsRequest.builder()
                            .marker(newMarker)
                            .build();

                    response = glacier.listVaults(request);
                } else {
                    ListVaultsRequest request = ListVaultsRequest.builder()
                            .build();
                    response = glacier.listVaults(request);
                }

                List<DescribeVaultOutput> vaultList = response.vaultList();
                for (DescribeVaultOutput v : vaultList) {
                    totalVaults += 1;
                    System.out.println("* " + v.vaultName());
                }

                // Check for further results.
                newMarker = response.marker();
                if (newMarker == null) {
                    listComplete = true;
                }
            }

            if (totalVaults == 0) {
                System.out.println("No vaults found.");
            }

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def list_vaults(self):
        """
        Lists vaults for the current account.
        """
        try:
            for vault in self.glacier_resource.vaults.all():
                logger.info("Got vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't list vaults.")
            raise
```

- Para obter detalhes da API, consulte a ListVaultsReferência da API AWSSDK for Python (Boto3).

Recupere um inventário de cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como recuperar um inventário do cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.JobParameters;
import software.amazon.awssdk.services.glacier.model.InitiateJobResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import software.amazon.awssdk.services.glacier.model.InitiateJobRequest;
import software.amazon.awssdk.services.glacier.model.DescribeJobRequest;
import software.amazon.awssdk.services.glacier.model.DescribeJobResponse;
import software.amazon.awssdk.services.glacier.model.GetJobOutputRequest;
import software.amazon.awssdk.services.glacier.model.GetJobOutputResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
```

```
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ArchiveDownload {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <vaultName> <accountId> <path>

                Where:
                   vaultName - The name of the vault.
                   accountId - The account ID value.
                   path - The path where the file is written to.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        String accountId = args[1];
        String path = args[2];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String jobNum = createJob(glacier, vaultName, accountId);
        checkJob(glacier, jobNum, vaultName, accountId, path);
        glacier.close();
    }

    public static String createJob(GlacierClient glacier, String vaultName,
 String accountId) {
        try {
            JobParameters job = JobParameters.builder()
                    .type("inventory-retrieval")
                    .build();
```

```
            InitiateJobRequest initJob = InitiateJobRequest.builder()
                    .jobParameters(job)
                    .accountId(accountId)
                    .vaultName(vaultName)
                    .build();

            InitiateJobResponse response = glacier.initiateJob(initJob);
            System.out.println("The job ID is: " + response.jobId());
            System.out.println("The relative URI path of the job is: " +
response.location());
            return response.jobId();

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);

        }
        return "";
    }

    // Poll S3 Glacier = Polling a Job may take 4-6 hours according to the
    // Documentation.
    public static void checkJob(GlacierClient glacier, String jobId, String name,
String account, String path) {
        try {
            boolean finished = false;
            String jobStatus;
            int yy = 0;

            while (!finished) {
                DescribeJobRequest jobRequest = DescribeJobRequest.builder()
                        .jobId(jobId)
                        .accountId(account)
                        .vaultName(name)
                        .build();

                DescribeJobResponse response = glacier.describeJob(jobRequest);
                jobStatus = response.statusCodeAsString();

                if (jobStatus.compareTo("Succeeded") == 0)
                    finished = true;
                else {
                    System.out.println(yy + " status is: " + jobStatus);
```

```
                    Thread.sleep(1000);
                }
                yy++;
            }

            System.out.println("Job has Succeeded");
            GetJobOutputRequest jobOutputRequest = GetJobOutputRequest.builder()
                    .jobId(jobId)
                    .vaultName(name)
                    .accountId(account)
                    .build();

            ResponseBytes<GetJobOutputResponse> objectBytes =
 glacier.getJobOutputAsBytes(jobOutputRequest);
            // Write the data to a local file.
            byte[] data = objectBytes.asByteArray();
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from a Glacier
 vault");
            os.close();

        } catch (GlacierException | InterruptedException | IOException e) {
            System.out.println(e.getMessage());
            System.exit(1);

        }
    }
}
```

- Para obter detalhes da API, consulte InitiateJoba Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def initiate_inventory_retrieval(vault):
        """
        Initiates an inventory retrieval job. The inventory describes the
 contents
        of the vault. Standard retrievals typically complete within 3–5 hours.
        When the job completes, you can get the inventory by calling
 get_output().

        :param vault: The vault to inventory.
        :return: The inventory retrieval job.
        """
        try:
            job = vault.initiate_inventory_retrieval()
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
            logger.exception("Couldn't start job on vault %s.", vault.name)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a InitiateJobReferência da API AWSSDK for Python (Boto3).

Recupere um arquivo de um cofre do Amazon S3 Glacier usando um SDK da AWS

O exemplo de código a seguir mostra como recuperar um arquivo de um cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def initiate_archive_retrieval(archive):
        """
        Initiates an archive retrieval job. Standard retrievals typically
 complete
        within 3-5 hours. When the job completes, you can get the archive
 contents
        by calling get_output().

        :param archive: The archive to retrieve.
        :return: The archive retrieval job.
        """
        try:
            job = archive.initiate_archive_retrieval()
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
```

```
            logger.exception("Couldn't start job on archive %s.", archive.id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a InitiateJobReferência da API AWSSDK for Python (Boto3).

Configure notificações do cofre do Amazon S3 Glacier usando um SDK da AWS

Os exemplos de código a seguir mostram como definir notificações do cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

CLI

AWS CLI

O comando a seguir configura as notificações do SNS para um cofre chamado `my-vault`:

```
aws glacier set-vault-notifications --account-id - --vault-name my-vault --vault-
notification-config file://notificationconfig.json
```

`notificationconfig.json` é um arquivo JSON na pasta atual que especifica um tópico do SNS e os eventos a serem publicados:

```
{
  "SNSTopic": "arn:aws:sns:us-west-2:0123456789012:my-vault",
  "Events": ["ArchiveRetrievalCompleted", "InventoryRetrievalCompleted"]
}
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

- Para obter detalhes da API, consulte SetVaultNotificationsna Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def set_notifications(self, vault, sns_topic_arn):
        """
        Sets an Amazon Simple Notification Service (Amazon SNS) topic as a target
        for notifications. Amazon S3 Glacier publishes messages to this topic for
        the configured list of events.

        :param vault: The vault to set up to publish notifications.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of the topic that
                              receives notifications.
        :return: Data about the new notification configuration.
        """
        try:
            notification = self.glacier_resource.Notification("-", vault.name)
            notification.set(
                vaultNotificationConfig={
                    "SNSTopic": sns_topic_arn,
                    "Events": [
                        "ArchiveRetrievalCompleted",
                        "InventoryRetrievalCompleted",
                    ],
                }
            )
```

```
            logger.info(
                "Notifications will be sent to %s for events %s from %s.",
                notification.sns_topic,
                notification.events,
                notification.vault_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't set notifications to %s on %s.", sns_topic_arn,
vault.name
            )
            raise
        else:
            return notification
```

- Para obter detalhes da API, consulte a SetVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Carregar um arquivo em um cofre do Amazon S3 Glacier usando um AWS SDK

Os exemplos de código a seguir mostram como carregar um arquivo em um cofre do Amazon S3 Glacier.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Arquive um arquivo, receba notificações e inicie um trabalho

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Upload an object to an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the Amazon S3 Glacier vault to upload
    /// the archive to.</param>
    /// <param name="archiveFilePath">The file path of the archive to upload to
 the vault.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<string> UploadArchiveWithArchiveManager(string vaultName,
 string archiveFilePath)
    {
        try
        {
            var manager = new ArchiveTransferManager(_glacierService);

            // Upload an archive.
            var response = await manager.UploadAsync(vaultName, "upload archive
 test", archiveFilePath);
            return response.ArchiveId;
        }
        catch (AmazonGlacierException ex)
        {
            Console.WriteLine(ex.Message);
            return string.Empty;
        }
    }
```

- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for .NET da API.

CLI

AWS CLI

O comando a seguir faz upload um arquivamento na pasta atual chamada `archive.zip` para um cofre chamado `my-vault`:

```
aws glacier upload-archive --account-id - --vault-name my-vault --body
 archive.zip
```

Saída:

```
{
    "archiveId": "kKB7ymWJVpPSwhGP6ycSOAekp9ZYe_--
zM_mw6k76ZFGEIWQX-ybtRDvc2VkPSDtfKmQrj0IRQLSGsNuDp-
AJVlu2ccmDSyDUmZwKbwbpAdGATGDiB3hHO0bjbGehXTcApVud_wyDw",
    "checksum":
 "969fb39823836d81f0cc028195fcdbcbbe76cdde932d4646fa7de5f21e18aa67",
    "location": "/0123456789012/vaults/my-vault/archives/
kKB7ymWJVpPSwhGP6ycSOAekp9ZYe_--zM_mw6k76ZFGEIWQX-
ybtRDvc2VkPSDtfKmQrj0IRQLSGsNuDp-
AJVlu2ccmDSyDUmZwKbwbpAdGATGDiB3hHO0bjbGehXTcApVud_wyDw"
}
```

O Amazon Glacier exige um argumento de ID de conta ao realizar operações, mas você pode usar um hífen para especificar a conta em uso.

Para recuperar um arquivamento carregado, inicie um trabalho de recuperação com o comando aws glacier initiate-job.

- Para obter detalhes da API, consulte UploadArchiveem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.UploadArchiveRequest;
import software.amazon.awssdk.services.glacier.model.UploadArchiveResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import java.io.File;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.io.FileInputStream;
```

```
import java.io.IOException;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UploadArchive {

    static final int ONE_MB = 1024 * 1024;

    public static void main(String[] args) {
        final String usage = """

                Usage:   <strPath> <vaultName>\s

                Where:
                   strPath - The path to the archive to upload (for example, C:\
\AWS\\test.pdf).
                   vaultName - The name of the vault.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String strPath = args[0];
        String vaultName = args[1];
        File myFile = new File(strPath);
        Path path = Paths.get(strPath);
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String archiveId = uploadContent(glacier, path, vaultName, myFile);
        System.out.println("The ID of the archived item is " + archiveId);
        glacier.close();
```

```
    }

    public static String uploadContent(GlacierClient glacier, Path path, String
vaultName, File myFile) {
        // Get an SHA-256 tree hash value.
        String checkVal = computeSHA256(myFile);
        try {
            UploadArchiveRequest uploadRequest = UploadArchiveRequest.builder()
                    .vaultName(vaultName)
                    .checksum(checkVal)
                    .build();

            UploadArchiveResponse res = glacier.uploadArchive(uploadRequest,
path);
            return res.archiveId();

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    private static String computeSHA256(File inputFile) {
        try {
            byte[] treeHash = computeSHA256TreeHash(inputFile);
            System.out.printf("SHA-256 tree hash = %s\n", toHex(treeHash));
            return toHex(treeHash);

        } catch (IOException ioe) {
            System.err.format("Exception when reading from file %s: %s",
inputFile, ioe.getMessage());
            System.exit(-1);

        } catch (NoSuchAlgorithmException nsae) {
            System.err.format("Cannot locate MessageDigest algorithm for SHA-256:
%s", nsae.getMessage());
            System.exit(-1);
        }
        return "";
    }

    public static byte[] computeSHA256TreeHash(File inputFile) throws
IOException,
```

```
            NoSuchAlgorithmException {

        byte[][] chunkSHA256Hashes = getChunkSHA256Hashes(inputFile);
        return computeSHA256TreeHash(chunkSHA256Hashes);
    }

    /**
     * Computes an SHA256 checksum for each 1 MB chunk of the input file. This
     * includes the checksum for the last chunk, even if it's smaller than 1 MB.
     */
    public static byte[][] getChunkSHA256Hashes(File file) throws IOException,
            NoSuchAlgorithmException {

        MessageDigest md = MessageDigest.getInstance("SHA-256");
        long numChunks = file.length() / ONE_MB;
        if (file.length() % ONE_MB > 0) {
            numChunks++;
        }

        if (numChunks == 0) {
            return new byte[][] { md.digest() };
        }

        byte[][] chunkSHA256Hashes = new byte[(int) numChunks][];
        FileInputStream fileStream = null;

        try {
            fileStream = new FileInputStream(file);
            byte[] buff = new byte[ONE_MB];

            int bytesRead;
            int idx = 0;

            while ((bytesRead = fileStream.read(buff, 0, ONE_MB)) > 0) {
                md.reset();
                md.update(buff, 0, bytesRead);
                chunkSHA256Hashes[idx++] = md.digest();
            }

            return chunkSHA256Hashes;

        } finally {
            if (fileStream != null) {
                try {
```

```
                    fileStream.close();
                } catch (IOException ioe) {
                    System.err.printf("Exception while closing %s.\n %s",
file.getName(),
                            ioe.getMessage());
                }
            }
        }
    }

    /**
     * Computes the SHA-256 tree hash for the passed array of 1 MB chunk
     * checksums.
     */
    public static byte[] computeSHA256TreeHash(byte[][] chunkSHA256Hashes)
            throws NoSuchAlgorithmException {

        MessageDigest md = MessageDigest.getInstance("SHA-256");
        byte[][] prevLvlHashes = chunkSHA256Hashes;
        while (prevLvlHashes.length > 1) {
            int len = prevLvlHashes.length / 2;
            if (prevLvlHashes.length % 2 != 0) {
                len++;
            }

            byte[][] currLvlHashes = new byte[len][];
            int j = 0;
            for (int i = 0; i < prevLvlHashes.length; i = i + 2, j++) {

                // If there are at least two elements remaining.
                if (prevLvlHashes.length - i > 1) {

                    // Calculate a digest of the concatenated nodes.
                    md.reset();
                    md.update(prevLvlHashes[i]);
                    md.update(prevLvlHashes[i + 1]);
                    currLvlHashes[j] = md.digest();

                } else { // Take care of the remaining odd chunk
                    currLvlHashes[j] = prevLvlHashes[i];
                }
            }

            prevLvlHashes = currLvlHashes;
```

```
        }

        return prevLvlHashes[0];
    }

    /**
     * Returns the hexadecimal representation of the input byte array
     */
    public static String toHex(byte[] data) {
        StringBuilder sb = new StringBuilder(data.length * 2);
        for (byte datum : data) {
            String hex = Integer.toHexString(datum & 0xFF);

            if (hex.length() == 1) {
                // Append leading zero.
                sb.append("0");
            }
            sb.append(hex);
        }
        return sb.toString().toLowerCase();
    }
}
```

- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
```

```
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Carregue o arquivo.

```
// Load the SDK for JavaScript
import { UploadArchiveCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME

// Create a new service object and buffer
const buffer = new Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer
const params = { vaultName: vaultname, body: buffer };

const run = async () => {
  try {
    const data = await glacierClient.send(new UploadArchiveCommand(params));
    console.log("Archive ID", data.archiveId);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error uploading archive!", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object and buffer
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
buffer = Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer

var params = { vaultName: "YOUR_VAULT_NAME", body: buffer };
// Call Glacier to upload the archive.
glacier.uploadArchive(params, function (err, data) {
  if (err) {
    console.log("Error uploading archive!", err);
  } else {
    console.log("Archive ID", data.archiveId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
```

```
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def upload_archive(vault, archive_description, archive_file):
        """
        Uploads an archive to a vault.

        :param vault: The vault where the archive is put.
        :param archive_description: A description of the archive.
        :param archive_file: The archive file to put in the vault.
        :return: The uploaded archive.
        """
        try:
            archive = vault.upload_archive(
                archiveDescription=archive_description, body=archive_file
            )
            logger.info(
                "Uploaded %s with ID %s to vault %s.",
                archive_description,
                archive.id,
                vault.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload %s to %s.", archive_description, vault.name
            )
            raise
        else:
            return archive
```

- Para obter detalhes da API, consulte a UploadArchiveReferência da API AWSSDK for Python (Boto3).

Cenários do S3 Glacier usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon S3 Glacier com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Arquive um arquivo no Amazon S3 Glacier, receba notificações e inicie um trabalho usando um AWS SDK
- Obtenha o conteúdo do arquivo do Amazon S3 Glacier e exclua o arquivo usando um SDK da AWS

Arquive um arquivo no Amazon S3 Glacier, receba notificações e inicie um trabalho usando um AWS SDK

O código de exemplo a seguir mostra como:

- Criar um cofre do Amazon S3 Glacier.
- Configurar o cofre para publicar notificações em um tópico do Amazon SNS.
- Carregar um arquivo no cofre.
- Inicie um trabalho de recuperação de arquivo.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as operações do S3 Glacier.

```
import argparse
import logging
import os
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
```

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def create_vault(self, vault_name):
        """
        Creates a vault.

        :param vault_name: The name to give the vault.
        :return: The newly created vault.
        """
        try:
            vault = self.glacier_resource.create_vault(vaultName=vault_name)
            logger.info("Created vault %s.", vault_name)
        except ClientError:
            logger.exception("Couldn't create vault %s.", vault_name)
            raise
        else:
            return vault


    def list_vaults(self):
        """
        Lists vaults for the current account.
        """
        try:
            for vault in self.glacier_resource.vaults.all():
                logger.info("Got vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't list vaults.")
            raise


    @staticmethod
    def upload_archive(vault, archive_description, archive_file):
        """
```

```
        Uploads an archive to a vault.

        :param vault: The vault where the archive is put.
        :param archive_description: A description of the archive.
        :param archive_file: The archive file to put in the vault.
        :return: The uploaded archive.
        """
        try:
            archive = vault.upload_archive(
                archiveDescription=archive_description, body=archive_file
            )
            logger.info(
                "Uploaded %s with ID %s to vault %s.",
                archive_description,
                archive.id,
                vault.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload %s to %s.", archive_description, vault.name
            )
            raise
        else:
            return archive


    @staticmethod
    def initiate_archive_retrieval(archive):
        """
        Initiates an archive retrieval job. Standard retrievals typically
complete
        within 3-5 hours. When the job completes, you can get the archive
contents
        by calling get_output().

        :param archive: The archive to retrieve.
        :return: The archive retrieval job.
        """
        try:
            job = archive.initiate_archive_retrieval()
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
            logger.exception("Couldn't start job on archive %s.", archive.id)
            raise
```

```
        else:
            return job


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type,
vault.name)
            raise
        else:
            return job_list


    def set_notifications(self, vault, sns_topic_arn):
        """
        Sets an Amazon Simple Notification Service (Amazon SNS) topic as a target
        for notifications. Amazon S3 Glacier publishes messages to this topic for
        the configured list of events.
```

```
        :param vault: The vault to set up to publish notifications.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of the topic that
                              receives notifications.
        :return: Data about the new notification configuration.
        """
        try:
            notification = self.glacier_resource.Notification("-", vault.name)
            notification.set(
                vaultNotificationConfig={
                    "SNSTopic": sns_topic_arn,
                    "Events": [
                        "ArchiveRetrievalCompleted",
                        "InventoryRetrievalCompleted",
                    ],
                }
            )
            logger.info(
                "Notifications will be sent to %s for events %s from %s.",
                notification.sns_topic,
                notification.events,
                notification.vault_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't set notifications to %s on %s.", sns_topic_arn,
 vault.name
            )
            raise
        else:
            return notification
```

Chame funções na classe wrapper para criar um cofre e carregar um arquivo, depois configure o cofre para publicar notificações e iniciar um trabalho para recuperar o arquivo.

```
def upload_demo(glacier, vault_name, topic_arn):
    """
    Shows how to:
    * Create a vault.
    * Configure the vault to publish notifications to an Amazon SNS topic.
    * Upload an archive.
```

```
    * Start a job to retrieve the archive.

    :param glacier: A Boto3 Amazon S3 Glacier resource.
    :param vault_name: The name of the vault to create.
    :param topic_arn: The ARN of an Amazon SNS topic that receives notification
of
                      Amazon S3 Glacier events.
    """
    print(f"\nCreating vault {vault_name}.")
    vault = glacier.create_vault(vault_name)
    print("\nList of vaults in your account:")
    glacier.list_vaults()
    print(f"\nUploading glacier_basics.py to {vault.name}.")
    with open("glacier_basics.py", "rb") as upload_file:
        archive = glacier.upload_archive(vault, "glacier_basics.py", upload_file)
    print(
        "\nStarting an archive retrieval request to get the file back from the "
        "vault."
    )
    glacier.initiate_archive_retrieval(archive)
    print("\nListing in progress jobs:")
    glacier.list_jobs(vault, "in_progress")
    print(
        "\nBecause Amazon S3 Glacier is intended for infrequent retrieval, an "
        "archive request with Standard retrieval typically completes within 3-5 "
        "hours."
    )
    if topic_arn:
        notification = glacier.set_notifications(vault, topic_arn)
        print(
            f"\nVault {vault.name} is configured to notify the "
            f"{notification.sns_topic} topic when {notification.events} "
            f"events occur. You can subscribe to this topic to receive "
            f"a message when the archive retrieval completes.\n"
        )
    else:
        print(
            f"\nVault {vault.name} is not configured to notify an Amazon SNS
topic "
            f"when the archive retrieval completes so wait a few hours."
        )
    print("\nRetrieve your job output by running this script with the --retrieve
flag.")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateVault
  - InitiateJob
  - ListJobs
  - ListVaults
  - SetVaultNotifications
  - UploadArchive

Obtenha o conteúdo do arquivo do Amazon S3 Glacier e exclua o arquivo usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Liste trabalhos para um cofre do Amazon S3 Glacier e obtenha o status do trabalho.
- Obtenha a saída de um trabalho de recuperação de arquivo concluído.
- Exclua um arquivo.
- Excluir um cofre.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as operações do S3 Glacier.

```
import argparse
import logging
```

```
import os
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
```

```
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type,
vault.name)
            raise
        else:
            return job_list


    @staticmethod
    def get_job_output(job):
        """
        Gets the output of a job, such as a vault inventory or the contents of an
        archive.

        :param job: The job to get output from.
        :return: The job output, in bytes.
        """
        try:
            response = job.get_output()
            out_bytes = response["body"].read()
            logger.info("Read %s bytes from job %s.", len(out_bytes), job.id)
            if "archiveDescription" in response:
                logger.info(
                    "These bytes are described as '%s'",
response["archiveDescription"]
                )
        except ClientError:
            logger.exception("Couldn't get output for job %s.", job.id)
            raise
        else:
            return out_bytes


    @staticmethod
    def delete_archive(archive):
        """
        Deletes an archive from a vault.

        :param archive: The archive to delete.
        """
        try:
            archive.delete()
            logger.info(
```

```
                "Deleted archive %s from vault %s.", archive.id,
 archive.vault_name
            )
        except ClientError:
            logger.exception("Couldn't delete archive %s.", archive.id)
            raise


    @staticmethod
    def delete_vault(vault):
        """
        Deletes a vault.

        :param vault: The vault to delete.
        """
        try:
            vault.delete()
            logger.info("Deleted vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't delete vault %s.", vault.name)
            raise
```

Chame funções na classe wrapper para obter o conteúdo de arquivo de um trabalho concluído e, em seguida, exclua o arquivo.

```
def retrieve_demo(glacier, vault_name):
    """
    Shows how to:
    * List jobs for a vault and get job status.
    * Get the output of a completed archive retrieval job.
    * Delete an archive.
    * Delete a vault.

    :param glacier: A Boto3 Amazon S3 Glacier resource.
    :param vault_name: The name of the vault to query for jobs.
    """
    vault = glacier.glacier_resource.Vault("-", vault_name)
    try:
        vault.load()
    except ClientError as err:
        if err.response["Error"]["Code"] == "ResourceNotFoundException":
```

```
            print(
                f"\nVault {vault_name} doesn't exist. You must first run this
script "
                f"with the --upload flag to create the vault."
            )
            return
        else:
            raise

    print(f"\nGetting completed jobs for {vault.name}.")
    jobs = glacier.list_jobs(vault, "completed")
    if not jobs:
        print("\nNo completed jobs found. Give it some time and try again
later.")
        return

    retrieval_job = None
    for job in jobs:
        if job.action == "ArchiveRetrieval" and job.status_code == "Succeeded":
            retrieval_job = job
            break
    if retrieval_job is None:
        print(
            "\nNo ArchiveRetrieval jobs found. Give it some time and try again "
            "later."
        )
        return

    print(f"\nGetting output from job {retrieval_job.id}.")
    archive_bytes = glacier.get_job_output(retrieval_job)
    archive_str = archive_bytes.decode("utf-8")
    print("\nGot archive data. Printing the first 10 lines.")
    print(os.linesep.join(archive_str.split(os.linesep)[:10]))

    print(f"\nDeleting the archive from {vault.name}.")
    archive = glacier.glacier_resource.Archive(
        "-", vault.name, retrieval_job.archive_id
    )
    glacier.delete_archive(archive)

    print(f"\nDeleting {vault.name}.")
    glacier.delete_vault(vault)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeleteArchive
  - DeleteVault
  - GetJobOutput
  - ListJobs

Exemplos de código para SageMaker usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon SageMaker com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- SageMaker Guia do desenvolvedor — Mais informações sobre SageMaker.
- SageMaker Referência da API — Detalhes sobre todas as SageMaker ações disponíveis.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá SageMaker

O exemplo de código a seguir mostra como começar a usar o SageMaker.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SageMaker;
using Amazon.SageMaker.Model;

namespace SageMakerActions;

public static class HelloSageMaker
{
    static async Task Main(string[] args)
    {
        var sageMakerClient = new AmazonSageMakerClient();

        Console.WriteLine($"Hello Amazon SageMaker! Let's list some of your
 notebook instances:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five notebook instances.
        var response = await sageMakerClient.ListNotebookInstancesAsync(
            new ListNotebookInstancesRequest()
            {
                MaxResults = 5
            });

        if (!response.NotebookInstances.Any())
        {
            Console.WriteLine($"No notebook instances found.");
            Console.WriteLine("See https://docs.aws.amazon.com/sagemaker/latest/
dg/howitworks-create-ws.html to create one.");
        }

        foreach (var notebookInstance in response.NotebookInstances)
```

```
        {
            Console.WriteLine($"\tInstance:
 {notebookInstance.NotebookInstanceName}");
            Console.WriteLine($"\tArn: {notebookInstance.NotebookInstanceArn}");
            Console.WriteLine($"\tCreation Date:
 {notebookInstance.CreationTime.ToShortDateString()}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloSageMaker {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        SageMakerClient sageMakerClient = SageMakerClient.builder()
                .region(region)
                .build();
```

```
        listBooks(sageMakerClient);
        sageMakerClient.close();
    }

    public static void listBooks(SageMakerClient sageMakerClient) {
        try {
            ListNotebookInstancesResponse notebookInstancesResponse =
 sageMakerClient.listNotebookInstances();
            List<NotebookInstanceSummary> items =
 notebookInstancesResponse.notebookInstances();
            for (NotebookInstanceSummary item : items) {
                System.out.println("The notebook name is: " +
 item.notebookInstanceName());
            }

        } catch (SageMakerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  SageMakerClient,
  ListNotebookInstancesCommand,
} from "@aws-sdk/client-sagemaker";
```

```
const client = new SageMakerClient({
  region: "us-west-2",
});

export const helloSagemaker = async () => {
  const command = new ListNotebookInstancesCommand({ MaxResults: 5 });

  const response = await client.send(command);
  console.log(
    "Hello Amazon SageMaker! Let's list some of your notebook instances:",
  );

  const instances = response.NotebookInstances || [];

  if (instances.length === 0) {
    console.log(
      "• No notebook instances found. Try creating one in the AWS Management
 Console or with the CreateNotebookInstanceCommand.",
    );
  } else {
    console.log(
      instances
        .map(
          (i) =>
            `• Instance: ${i.NotebookInstanceName}\n  Arn:${
              i.NotebookInstanceArn
            } \n  Creation Date: ${i.CreationTime.toISOString()}`,
        )
        .join("\n"),
    );
  }

  return response;
};
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBooks() {

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        val response =
 sageMakerClient.listNotebookInstances(ListNotebookInstancesRequest {})
        response.notebookInstances?.forEach { item ->
            println("The notebook name is: ${item.notebookInstanceName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações para SageMaker usar AWS SDKs
  - Crie um modelo SageMaker usando um AWS SDK
  - Crie ou atualize um pipeline SageMaker usando um AWS SDK
  - Crie um SageMaker endpoint usando um SDK AWS
  - Excluir um modelo SageMaker usando um AWS SDK
  - Excluir um pipeline SageMaker usando um AWS SDK
  - Excluir um SageMaker endpoint usando um SDK AWS
  - Descrever a execução de um pipeline SageMaker usando um AWS SDK
  - Descrever um trabalho de SageMaker treinamento usando um AWS SDK
  - Execute um pipeline SageMaker usando um AWS SDK

- Listar modelos SageMaker usando um AWS SDK
- Listar as instâncias do SageMaker notebook usando um AWS SDK
- Liste os algoritmos de machine learning usando um SDK da AWS
- Listar trabalhos SageMaker de treinamento usando um AWS SDK
- Crie e inicie um trabalho SageMaker de treinamento usando um AWS SDK
- Crie e inicie um trabalho de SageMaker transformação usando um AWS SDK
- Cenários para SageMaker usar AWS SDKs
  - Comece com trabalhos SageMaker geoespaciais em um pipeline usando um SDK AWS
  - Comece a usar SageMaker modelos e endpoints usando um SDK AWS

Ações para SageMaker usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon SageMaker com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para SageMaker usar AWS SDKs.

Exemplos

- Crie um modelo SageMaker usando um AWS SDK
- Crie ou atualize um pipeline SageMaker usando um AWS SDK
- Crie um SageMaker endpoint usando um SDK AWS
- Excluir um modelo SageMaker usando um AWS SDK
- Excluir um pipeline SageMaker usando um AWS SDK
- Excluir um SageMaker endpoint usando um SDK AWS
- Descrever a execução de um pipeline SageMaker usando um AWS SDK
- Descrever um trabalho de SageMaker treinamento usando um AWS SDK
- Execute um pipeline SageMaker usando um AWS SDK
- Listar modelos SageMaker usando um AWS SDK
- Listar as instâncias do SageMaker notebook usando um AWS SDK
- Liste os algoritmos de machine learning usando um SDK da AWS
- Listar trabalhos SageMaker de treinamento usando um AWS SDK

- Crie e inicie um trabalho SageMaker de treinamento usando um AWS SDK
- Crie e inicie um trabalho de SageMaker transformação usando um AWS SDK

Crie um modelo SageMaker usando um AWS SDK

O exemplo de código a seguir mostra como criar um modelo em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   DATA lo_primarycontainer TYPE REF TO /aws1/cl_sgmcontainerdefn.

   "Create an ABAP object for the container image based on input variables."
   CREATE OBJECT lo_primarycontainer
     EXPORTING
       iv_image        = iv_container_image
       iv_modeldataurl = iv_model_data_url.

   "Create an Amazon SageMaker model."
   TRY.
       oo_result = lo_sgm->createmodel(        " oo_result is returned for
testing purposes. "
         iv_executionrolearn = iv_execution_role_arn
         iv_modelname = iv_model_name
         io_primarycontainer = lo_primarycontainer
       ).
       MESSAGE 'Model created.' TYPE 'I'.
```

```
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateModelreferência da API AWS SDK for SAP ABAP.

Crie ou atualize um pipeline SageMaker usando um AWS SDK

Os exemplos de código a seguir mostram como criar ou atualizar um pipeline em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Iniciar com trabalhos geoespaciais e pipelines

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    /// <summary>
    /// Create a pipeline from a JSON definition, or update it if the pipeline
already exists.
    /// </summary>
    /// <returns>The Amazon Resource Name (ARN) of the pipeline.</returns>
    public async Task<string> SetupPipeline(string pipelineJson, string roleArn,
string name, string description, string displayName)
    {
        try
        {
            var updateResponse = await _amazonSageMaker.UpdatePipelineAsync(
                new UpdatePipelineRequest()
```

```
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });
            return updateResponse.PipelineArn;
        }
        catch (Amazon.SageMaker.Model.ResourceNotFoundException)
        {
            var createResponse = await _amazonSageMaker.CreatePipelineAsync(
                new CreatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });

            return createResponse.PipelineArn;
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreatePipeline
  - UpdatePipeline

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    // Create a pipeline from the example pipeline JSON.
    public static void setupPipeline(SageMakerClient sageMakerClient, String
filePath, String roleArn,
            String functionArn, String pipelineName) {
        System.out.println("Setting up the pipeline.");
        JSONParser parser = new JSONParser();

        // Read JSON and get pipeline definition.
        try (FileReader reader = new FileReader(filePath)) {
            Object obj = parser.parse(reader);
            JSONObject jsonObject = (JSONObject) obj;
            JSONArray stepsArray = (JSONArray) jsonObject.get("Steps");
            for (Object stepObj : stepsArray) {
                JSONObject step = (JSONObject) stepObj;
                if (step.containsKey("FunctionArn")) {
                    step.put("FunctionArn", functionArn);
                }
            }
            System.out.println(jsonObject);

            // Create the pipeline.
            CreatePipelineRequest pipelineRequest =
CreatePipelineRequest.builder()
                    .pipelineDescription("Java SDK example pipeline")
                    .roleArn(roleArn)
                    .pipelineName(pipelineName)
                    .pipelineDefinition(jsonObject.toString())
                    .build();

            sageMakerClient.createPipeline(pipelineRequest);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException | ParseException e) {
            throw new RuntimeException(e);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.

- CreatePipeline
- UpdatePipeline

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma função que cria um SageMaker pipeline usando uma definição JSON fornecida localmente.

```
/**
 * Create the Amazon SageMaker pipeline using a JSON pipeline definition. The
 definition
 * can also be provided as an Amazon S3 object using
 PipelineDefinitionS3Location.
 * @param {{roleArn: string, name: string, sagemakerClient: import('@aws-sdk/
client-sagemaker').SageMakerClient}} props
 */
export async function createSagemakerPipeline({
  // Assumes an AWS IAM role has been created for this pipeline.
  roleArn,
  name,
  // Assumes an AWS Lambda function has been created for this pipeline.
  functionArn,
  sagemakerClient,
}) {
  const pipelineDefinition = readFileSync(
    // dirnameFromMetaUrl is a local utility function. You can find its
 implementation
    // on GitHub.
    `${dirnameFromMetaUrl(
      import.meta.url,
    )}../../../../../workflows/sagemaker_pipelines/resources/
GeoSpatialPipeline.json`,
  )
```

```
    .toString()
    .replace(/\*FUNCTION_ARN\*/g, functionArn);

  const { PipelineArn } = await sagemakerClient.send(
    new CreatePipelineCommand({
      PipelineName: name,
      PipelineDefinition: pipelineDefinition,
      RoleArn: roleArn,
    }),
  );

  return {
    arn: PipelineArn,
    cleanUp: async () => {
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
    },
  };
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreatePipeline
  - UpdatePipeline

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Create a pipeline from the example pipeline JSON.
suspend fun setupPipeline(filePath: String?, roleArnVal: String?, functionArnVal:
 String?, pipelineNameVal: String?) {
```

```
    println("Setting up the pipeline.")
    val parser = JSONParser()

    // Read JSON and get pipeline definition.
    FileReader(filePath).use { reader ->
        val obj: Any = parser.parse(reader)
        val jsonObject: JSONObject = obj as JSONObject
        val stepsArray: JSONArray = jsonObject.get("Steps") as JSONArray
        for (stepObj in stepsArray) {
            val step: JSONObject = stepObj as JSONObject
            if (step.containsKey("FunctionArn")) {
                step.put("FunctionArn", functionArnVal)
            }
        }
        println(jsonObject)

        // Create the pipeline.
        val pipelineRequest = CreatePipelineRequest {
            pipelineDescription = "Kotlin SDK example pipeline"
            roleArn = roleArnVal
            pipelineName = pipelineNameVal
            pipelineDefinition = jsonObject.toString()
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            sageMakerClient.createPipeline(pipelineRequest)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreatePipeline
  - UpdatePipeline

Crie um SageMaker endpoint usando um SDK AWS

O exemplo de código a seguir mostra como criar um SageMaker endpoint.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_production_variants TYPE /aws1/
cl_sgmproductionvariant=>tt_productionvariantlist.
    DATA lo_production_variants TYPE REF TO /aws1/cl_sgmproductionvariant.
    DATA oo_ep_config_result TYPE REF TO /aws1/cl_sgmcreateendptcfgout.

    "Create a production variant as an ABAP object."
    "Identifies a model that you want to host and the resources chosen to deploy
 for hosting it."
    CREATE OBJECT lo_production_variants
      EXPORTING
        iv_variantname          = iv_variant_name
        iv_modelname            = iv_model_name
        iv_initialinstancecount = iv_initial_instance_count
        iv_instancetype         = iv_instance_type.

    INSERT lo_production_variants INTO TABLE lt_production_variants.

    "Create an endpoint configuration."
    TRY.
        oo_ep_config_result = lo_sgm->createendpointconfig(
          iv_endpointconfigname = iv_endpoint_config_name
          it_productionvariants = lt_production_variants
        ).
        MESSAGE 'Endpoint configuration created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
 'E'.
    ENDTRY.
```

```
    "Create an endpoint."
    TRY.
        oo_result = lo_sgm->createendpoint(     " oo_result is returned for
testing purposes. "
            iv_endpointconfigname = iv_endpoint_config_name
            iv_endpointname = iv_endpoint_name
        ).
        MESSAGE 'Endpoint created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateEndpoint
  - CreateEndpointConfig

Excluir um modelo SageMaker usando um AWS SDK

O exemplo de código a seguir mostra como excluir um modelo em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        lo_sgm->deletemodel(
                  iv_modelname = iv_model_name
                ).
        MESSAGE 'Model deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteModelreferência da API AWS SDK for SAP ABAP.

Excluir um pipeline SageMaker usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um pipeline em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Iniciar com trabalhos geoespaciais e pipelines

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a SageMaker pipeline by name.
    /// </summary>
    /// <param name="pipelineName">The name of the pipeline to delete.</param>
    /// <returns>The ARN of the pipeline.</returns>
    public async Task<string> DeletePipelineByName(string pipelineName)
    {
```

```
        var deleteResponse = await _amazonSageMaker.DeletePipelineAsync(
            new DeletePipelineRequest()
            {
                PipelineName = pipelineName
            });

        return deleteResponse.PipelineArn;
    }
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Delete a SageMaker pipeline by name.
   public static void deletePipeline(SageMakerClient sageMakerClient, String
pipelineName) {
       DeletePipelineRequest pipelineRequest = DeletePipelineRequest.builder()
               .pipelineName(pipelineName)
               .build();

       sageMakerClient.deletePipeline(pipelineRequest);
       System.out.println("*** Successfully deleted " + pipelineName);
   }
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

A sintaxe para excluir um SageMaker pipeline. Esse código faz parte de uma função maior. Consulte “Criar um pipeline” ou o GitHub repositório para obter mais contexto.

```
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Delete a SageMaker pipeline by name.
suspend fun deletePipeline(pipelineNameVal: String) {
    val pipelineRequest = DeletePipelineRequest {
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        sageMakerClient.deletePipeline(pipelineRequest)
```

```
        println("*** Successfully deleted $pipelineNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeletePipelinereferência da API AWSSDK for Kotlin.

Excluir um SageMaker endpoint usando um SDK AWS

O exemplo de código a seguir mostra como excluir um SageMaker endpoint.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Delete an endpoint."
    TRY.
        lo_sgm->deleteendpoint(
            iv_endpointname = iv_endpoint_name
        ).
        MESSAGE 'Endpoint configuration deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpoint_exception).
        DATA(lv_endpoint_error) = |"{ lo_endpoint_exception->av_err_code }" -
{ lo_endpoint_exception->av_err_msg }|.
        MESSAGE lv_endpoint_error TYPE 'E'.
    ENDTRY.

    "Delete an endpoint configuration."
    TRY.
```

```
        lo_sgm->deleteendpointconfig(
          iv_endpointconfigname = iv_endpoint_config_name
        ).
        MESSAGE 'Endpoint deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpointconfig_exception).
        DATA(lv_endpointconfig_error) = |"{ lo_endpointconfig_exception-
>av_err_code }" - { lo_endpointconfig_exception->av_err_msg }|.
        MESSAGE lv_endpointconfig_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DeleteEndpoint
  - DeleteEndpointConfig

Descrever a execução de um pipeline SageMaker usando um AWS SDK

Os exemplos de código a seguir mostram como descrever a execução de um pipeline em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Iniciar com trabalhos geoespaciais e pipelines

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Check the status of a run.
    /// </summary>
```

```
    /// <param name="pipelineExecutionArn">The ARN.</param>
    /// <returns>The status of the pipeline.</returns>
    public async Task<PipelineExecutionStatus>
CheckPipelineExecutionStatus(string pipelineExecutionArn)
    {
        var describeResponse = await
_amazonSageMaker.DescribePipelineExecutionAsync(
            new DescribePipelineExecutionRequest()
            {
                PipelineExecutionArn = pipelineExecutionArn
            });

        return describeResponse.PipelineExecutionStatus;
    }
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Check the status of a pipeline execution.
    public static void waitForPipelineExecution(SageMakerClient sageMakerClient,
String executionArn)
            throws InterruptedException {
        String status;
        int index = 0;
        do {
            DescribePipelineExecutionRequest pipelineExecutionRequest =
DescribePipelineExecutionRequest.builder()
                    .pipelineExecutionArn(executionArn)
                    .build();
```

```
            DescribePipelineExecutionResponse response = sageMakerClient
                    .describePipelineExecution(pipelineExecutionRequest);
            status = response.pipelineExecutionStatusAsString();
            System.out.println(index + ". The Status of the pipeline is " +
 status);
            TimeUnit.SECONDS.sleep(4);
            index++;
        } while ("Executing".equals(status));
        System.out.println("Pipeline finished with status " + status);
    }
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Aguarde até que a execução de um SageMaker pipeline seja bem-sucedida, falhe ou pare.

```
/**
 * Poll the executing pipeline until the status is 'SUCCEEDED', 'STOPPED', or
 'FAILED'.
 * @param {{ arn: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function waitForPipelineComplete({ arn, sagemakerClient }) {
  const command = new DescribePipelineExecutionCommand({
    PipelineExecutionArn: arn,
  });

  let complete = false;
  let intervalInSeconds = 15;
  const COMPLETION_STATUSES = [
    PipelineExecutionStatus.FAILED,
```

```
    PipelineExecutionStatus.STOPPED,
    PipelineExecutionStatus.SUCCEEDED,
  ];

  do {
    const { PipelineExecutionStatus: status, FailureReason } =
      await sagemakerClient.send(command);

    complete = COMPLETION_STATUSES.includes(status);

    if (!complete) {
      console.log(
        `Pipeline is ${status}. Waiting ${intervalInSeconds} seconds before
 checking again.`,
      );
      await wait(intervalInSeconds);
    } else if (status === PipelineExecutionStatus.FAILED) {
      throw new Error(`Pipeline failed because: ${FailureReason}`);
    } else if (status === PipelineExecutionStatus.STOPPED) {
      throw new Error(`Pipeline was forcefully stopped.`);
    } else {
      console.log(`Pipeline execution ${status}.`);
    }
  } while (!complete);
}
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitForPipelineExecution(executionArn: String?) {
```

```
    var status: String
    var index = 0
    do {
        val pipelineExecutionRequest = DescribePipelineExecutionRequest {
            pipelineExecutionArn = executionArn
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            val response =
 sageMakerClient.describePipelineExecution(pipelineExecutionRequest)
            status = response.pipelineExecutionStatus.toString()
            println("$index. The status of the pipeline is $status")
            TimeUnit.SECONDS.sleep(4)
            index++
        }
    } while ("Executing" == status)
    println("Pipeline finished with status $status")
}
```

- Para obter detalhes da API, consulte a DescribePipelineExecutionreferência da API AWSSDK for Kotlin.

Descrever um trabalho de SageMaker treinamento usando um AWS SDK

O exemplo de código a seguir mostra como descrever um trabalho SageMaker de treinamento.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->describetrainingjob(      " oo_result is returned for
 testing purposes. "
          iv_trainingjobname = iv_training_job_name
        ).
        MESSAGE 'Retrieved description of training job.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTrainingJobreferência da API AWS SDK for SAP ABAP.

Execute um pipeline SageMaker usando um AWS SDK

Os exemplos de código a seguir mostram como iniciar a execução de um pipeline em SageMaker.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Iniciar com trabalhos geoespaciais e pipelines

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Run a pipeline with input and output file locations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue to use for pipeline
 callbacks.</param>
```

```
    /// <param name="inputLocationUrl">The input location in Amazon Simple
 Storage Service (Amazon S3).</param>
    /// <param name="outputLocationUrl">The output location in Amazon S3.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="executionRoleArn">The ARN of the role.</param>
    /// <returns>The ARN of the pipeline run.</returns>
    public async Task<string> ExecutePipeline(
        string queueUrl,
        string inputLocationUrl,
        string outputLocationUrl,
        string pipelineName,
        string executionRoleArn)
    {
        var inputConfig = new VectorEnrichmentJobInputConfig()
        {
            DataSourceConfig = new()
            {
                S3Data = new VectorEnrichmentJobS3Data()
                {
                    S3Uri = inputLocationUrl
                }
            },
            DocumentType = VectorEnrichmentJobDocumentType.CSV
        };

        var exportConfig = new ExportVectorEnrichmentJobOutputConfig()
        {
            S3Data = new VectorEnrichmentJobS3Data()
            {
                S3Uri = outputLocationUrl
            }
        };

        var jobConfig = new VectorEnrichmentJobConfig()
        {
            ReverseGeocodingConfig = new ReverseGeocodingConfig()
            {
                XAttributeName = "Longitude",
                YAttributeName = "Latitude"
            }
        };

#pragma warning disable SageMaker1002 // Property value does not match required
 pattern is allowed here to match the pipeline definition.
```

```
        var startExecutionResponse = await
 _amazonSageMaker.StartPipelineExecutionAsync(
            new StartPipelineExecutionRequest()
            {
                PipelineName = pipelineName,
                PipelineExecutionDisplayName = pipelineName + "-example-
execution",
                PipelineParameters = new List<Parameter>()
                {
                    new Parameter() { Name = "parameter_execution_role", Value =
 executionRoleArn },
                    new Parameter() { Name = "parameter_queue_url", Value =
 queueUrl },
                    new Parameter() { Name = "parameter_vej_input_config", Value
 = JsonSerializer.Serialize(inputConfig) },
                    new Parameter() { Name = "parameter_vej_export_config", Value
 = JsonSerializer.Serialize(exportConfig) },
                    new Parameter() { Name = "parameter_step_1_vej_config", Value
 = JsonSerializer.Serialize(jobConfig) }
                }
            });
#pragma warning restore SageMaker1002
        return startExecutionResponse.PipelineExecutionArn;
    }
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Start a pipeline run with job configurations.
```

```
    public static String executePipeline(SageMakerClient sageMakerClient, String
 bucketName, String queueUrl,
            String roleArn, String pipelineName) {
        System.out.println("Starting pipeline execution.");
        String inputBucketLocation = "s3://" + bucketName + "/samplefiles/
latlongtest.csv";
        String output = "s3://" + bucketName + "/outputfiles/";
        Gson gson = new GsonBuilder()
                .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                .setPrettyPrinting().create();

        // Set up all parameters required to start the pipeline.
        List<Parameter> parameters = new ArrayList<>();
        Parameter para1 = Parameter.builder()
                .name("parameter_execution_role")
                .value(roleArn)
                .build();

        Parameter para2 = Parameter.builder()
                .name("parameter_queue_url")
                .value(queueUrl)
                .build();

        String inputJSON = "{\n" +
                "  \"DataSourceConfig\": {\n" +
                "    \"S3Data\": {\n" +
                "      \"S3Uri\": \"s3://" + bucketName + "/samplefiles/
latlongtest.csv\"\n" +
                "    },\n" +
                "    \"Type\": \"S3_DATA\"\n" +
                "  },\n" +
                "  \"DocumentType\": \"CSV\"\n" +
                "}";

        System.out.println(inputJSON);

        Parameter para3 = Parameter.builder()
                .name("parameter_vej_input_config")
                .value(inputJSON)
                .build();

        // Create an ExportVectorEnrichmentJobOutputConfig object.
        VectorEnrichmentJobS3Data jobS3Data = VectorEnrichmentJobS3Data.builder()
                .s3Uri(output)
```

```
                .build();

        ExportVectorEnrichmentJobOutputConfig outputConfig =
 ExportVectorEnrichmentJobOutputConfig.builder()
                .s3Data(jobS3Data)
                .build();

        String gson4 = gson.toJson(outputConfig);
        Parameter para4 = Parameter.builder()
                .name("parameter_vej_export_config")
                .value(gson4)
                .build();
        System.out.println("parameter_vej_export_config:" +
 gson.toJson(outputConfig));

        // Create a VectorEnrichmentJobConfig object.
        ReverseGeocodingConfig reverseGeocodingConfig =
 ReverseGeocodingConfig.builder()
                .xAttributeName("Longitude")
                .yAttributeName("Latitude")
                .build();

        VectorEnrichmentJobConfig jobConfig = VectorEnrichmentJobConfig.builder()
                .reverseGeocodingConfig(reverseGeocodingConfig)
                .build();

        String para5JSON = "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig
\":{\"XAttributeName\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}";
        Parameter para5 = Parameter.builder()
                .name("parameter_step_1_vej_config")
                .value(para5JSON)
                .build();

        System.out.println("parameter_step_1_vej_config:" +
 gson.toJson(jobConfig));
        parameters.add(para1);
        parameters.add(para2);
        parameters.add(para3);
        parameters.add(para4);
        parameters.add(para5);

        StartPipelineExecutionRequest pipelineExecutionRequest =
 StartPipelineExecutionRequest.builder()
                .pipelineExecutionDescription("Created using Java SDK")
```

```
                .pipelineExecutionDisplayName(pipelineName + "-example-
execution")
                .pipelineParameters(parameters)
                .pipelineName(pipelineName)
                .build();

        StartPipelineExecutionResponse response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest);
        return response.pipelineExecutionArn();
    }
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicie a execução de um SageMaker pipeline.

```
/**
 * Start the execution of the Amazon SageMaker pipeline. Parameters that are
 * passed in are used in the AWS Lambda function.
 * @param {{
 *   name: string,
 *   sagemakerClient: import('@aws-sdk/client-sagemaker').SageMakerClient,
 *   roleArn: string,
 *   queueUrl: string,
 *   s3InputBucketName: string,
 * }} props
 */
export async function startPipelineExecution({
  sagemakerClient,
  name,
  bucketName,
```

```
  roleArn,
  queueUrl,
}) {
  /**
   * The Vector Enrichment Job requests CSV data. This configuration points to a
 CSV
   * file in an Amazon S3 bucket.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobInputConfig}
   */
  const inputConfig = {
    DataSourceConfig: {
      S3Data: {
        S3Uri: `s3://${bucketName}/input/sample_data.csv`,
      },
    },
    DocumentType: VectorEnrichmentJobDocumentType.CSV,
  };

  /**
   * The Vector Enrichment Job adds additional data to the source CSV. This
 configuration points
   * to an Amazon S3 prefix where the output will be stored.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").ExportVectorEnrichmentJobOutputConfig}
   */
  const outputConfig = {
    S3Data: {
      S3Uri: `s3://${bucketName}/output/`,
    },
  };

  /**
   * This job will be a Reverse Geocoding Vector Enrichment Job. Reverse
 Geocoding requires
   * latitude and longitude values.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobConfig}
   */
  const jobConfig = {
    ReverseGeocodingConfig: {
      XAttributeName: "Longitude",
      YAttributeName: "Latitude",
    },
```

```
  };

  const { PipelineExecutionArn } = await sagemakerClient.send(
    new StartPipelineExecutionCommand({
      PipelineName: name,
      PipelineExecutionDisplayName: `${name}-example-execution`,
      PipelineParameters: [
        { Name: "parameter_execution_role", Value: roleArn },
        { Name: "parameter_queue_url", Value: queueUrl },
        {
          Name: "parameter_vej_input_config",
          Value: JSON.stringify(inputConfig),
        },
        {
          Name: "parameter_vej_export_config",
          Value: JSON.stringify(outputConfig),
        },
        {
          Name: "parameter_step_1_vej_config",
          Value: JSON.stringify(jobConfig),
        },
      ],
    }),
  );

  return {
    arn: PipelineExecutionArn,
  };
}
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Start a pipeline run with job configurations.
suspend fun executePipeline(bucketName: String, queueUrl: String?, roleArn:
 String?, pipelineNameVal: String): String? {
    println("Starting pipeline execution.")
    val inputBucketLocation = "s3://$bucketName/samplefiles/latlongtest.csv"
    val output = "s3://$bucketName/outputfiles/"

    val gson = GsonBuilder()
        .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
        .setPrettyPrinting()
        .create()

    // Set up all parameters required to start the pipeline.
    val parameters: MutableList<Parameter> = java.util.ArrayList<Parameter>()

    val para1 = Parameter {
        name = "parameter_execution_role"
        value = roleArn
    }
    val para2 = Parameter {
        name = "parameter_queue_url"
        value = queueUrl
    }

    val inputJSON = """{
        "DataSourceConfig": {
        "S3Data": {
            "S3Uri": "s3://$bucketName/samplefiles/latlongtest.csv"
        },
        "Type": "S3_DATA"
        },
        "DocumentType": "CSV"
```

```
    }"""
    println(inputJSON)
    val para3 = Parameter {
        name = "parameter_vej_input_config"
        value = inputJSON
    }

    // Create an ExportVectorEnrichmentJobOutputConfig object.
    val jobS3Data = VectorEnrichmentJobS3Data {
        s3Uri = output
    }

    val outputConfig = ExportVectorEnrichmentJobOutputConfig {
        s3Data = jobS3Data
    }

    val gson4: String = gson.toJson(outputConfig)
    val para4: Parameter = Parameter {
        name = "parameter_vej_export_config"
        value = gson4
    }
    println("parameter_vej_export_config:" + gson.toJson(outputConfig))

    val para5JSON =
        "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":{\"XAttributeName
\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}"

    val para5: Parameter = Parameter {
        name = "parameter_step_1_vej_config"
        value = para5JSON
    }

    parameters.add(para1)
    parameters.add(para2)
    parameters.add(para3)
    parameters.add(para4)
    parameters.add(para5)

    val pipelineExecutionRequest = StartPipelineExecutionRequest {
        pipelineExecutionDescription = "Created using Kotlin SDK"
        pipelineExecutionDisplayName = "$pipelineName-example-execution"
        pipelineParameters = parameters
        pipelineName = pipelineNameVal
    }
```

```
    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        val response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest)
        return response.pipelineExecutionArn
    }
}
```

- Para obter detalhes da API, consulte a StartPipelineExecutionreferência da API AWSSDK for Kotlin.

Listar modelos SageMaker usando um AWS SDK

O exemplo de código a seguir mostra como listar modelos em SageMaker.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listmodels(           " oo_result is returned for
 testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of models.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListModelsreferência da API AWS SDK for SAP ABAP.

Listar as instâncias do SageMaker notebook usando um AWS SDK

Os exemplos de código a seguir mostram como listar instâncias do SageMaker notebook.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_instances(client: &Client) -> Result<(), Error> {
    let notebooks = client.list_notebook_instances().send().await?;

    println!("Notebooks:");

    for n in notebooks.notebook_instances() {
        let n_instance_type = n.instance_type().unwrap();
        let n_status = n.notebook_instance_status().unwrap();
        let n_name = n.notebook_instance_name();

        println!("  Name :          {}", n_name.unwrap_or("Unknown"));
        println!("  Status :        {}", n_status.as_ref());
        println!("  Instance Type : {}", n_instance_type.as_ref());
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listnotebookinstances(        " oo_result is returned
 for testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of notebook instances.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWS SDK for SAP ABAP.

Liste os algoritmos de machine learning usando um SDK da AWS

O exemplo de código a seguir mostra como listar algoritmos SageMaker de aprendizado de máquina.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listalgorithms(         " oo_result is returned for
 testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of algorithms.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListAlgorithmsreferência da API AWS SDK for SAP ABAP.

Listar trabalhos SageMaker de treinamento usando um AWS SDK

Os exemplos de código a seguir mostram como listar trabalhos SageMaker de treinamento.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_jobs(client: &Client) -> Result<(), Error> {
    let job_details = client.list_training_jobs().send().await?;

    println!("Jobs:");

    for j in job_details.training_job_summaries() {
        let name = j.training_job_name().unwrap_or("Unknown");
        let creation_time = j.creation_time().expect("creation
 time").to_chrono_utc()?;
        let training_end_time = j
            .training_end_time()
```

```
            .expect("Training end time")
            .to_chrono_utc()?;

        let status = j.training_job_status().expect("training status");
        let duration = training_end_time - creation_time;

        println!("  Name:               {}", name);
        println!(
            "  Creation date/time: {}",
            creation_time.format("%Y-%m-%d@%H:%M:%S")
        );
        println!("  Duration (seconds): {}", duration.num_seconds());
        println!("  Status:             {:?}", status);

        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListTrainingJobsreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listtrainingjobs(       " oo_result is returned for
testing purposes. "
          iv_namecontains = iv_name_contains
          iv_maxresults = iv_max_results
        ).
        MESSAGE 'Retrieved list of training jobs.' TYPE 'I'.
```

```
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTrainingJobsreferência da API AWS SDK for SAP ABAP.

Crie e inicie um trabalho SageMaker de treinamento usando um AWS SDK

O exemplo de código a seguir mostra como iniciar um trabalho SageMaker de treinamento.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos com modelos e endpoints

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_hyperparameters_w TYPE REF TO /aws1/cl_sgmhyperparameters_w.
    DATA lt_hyperparameters TYPE /aws1/
cl_sgmhyperparameters_w=>tt_hyperparameters.
    DATA lt_input_data_config TYPE /aws1/cl_sgmchannel=>tt_inputdataconfig.
    DATA lo_trn_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_trn_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_trn_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
    DATA lo_val_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_val_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_val_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
```

```
   DATA lo_algorithm_specification TYPE REF TO /aws1/cl_sgmalgorithmspec.
   DATA lo_resource_config  TYPE REF TO /aws1/cl_sgmresourceconfig.
   DATA lo_output_data_config TYPE REF TO  /aws1/cl_sgmoutputdataconfig.
   DATA lo_stopping_condition TYPE REF TO  /aws1/cl_sgmstoppingcondition.

   "Create ABAP internal table for hyperparameters based on input variables."
   "These hyperparameters are based on the Amazon SageMaker built-in algorithm,
XGBoost."
   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_max_depth.
   INSERT VALUE #( key = 'max_depth' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eta.
   INSERT VALUE #( key = 'eta' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eval_metric.
   INSERT VALUE #( key = 'eval_metric' value = lo_hyperparameters_w )  INTO
TABLE lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value =
iv_hp_scale_pos_weight.
   INSERT VALUE #( key = 'scale_pos_weight' value = lo_hyperparameters_w )  INTO
TABLE lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_subsample.
   INSERT VALUE #( key = 'subsample' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_objective.
   INSERT VALUE #( key = 'objective' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_num_round.
   INSERT VALUE #( key = 'num_round' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   "Create ABAP objects for training data sources."
   CREATE OBJECT lo_trn_s3datasource
     EXPORTING
       iv_s3datatype             = iv_trn_data_s3datatype
       iv_s3datadistributiontype = iv_trn_data_s3datadistribution
       iv_s3uri                  = iv_trn_data_s3uri.
```

```
    CREATE OBJECT lo_trn_datasource
      EXPORTING
        io_s3datasource = lo_trn_s3datasource.

    CREATE OBJECT lo_trn_channel
      EXPORTING
        iv_channelname     = 'train'
        io_datasource      = lo_trn_datasource
        iv_compressiontype = iv_trn_data_compressiontype
        iv_contenttype     = iv_trn_data_contenttype.

    INSERT lo_trn_channel INTO TABLE lt_input_data_config.

    "Create ABAP objects for validation data sources."
    CREATE OBJECT lo_val_s3datasource
      EXPORTING
        iv_s3datatype             = iv_val_data_s3datatype
        iv_s3datadistributiontype = iv_val_data_s3datadistribution
        iv_s3uri                  = iv_val_data_s3uri.

    CREATE OBJECT lo_val_datasource
      EXPORTING
        io_s3datasource = lo_val_s3datasource.

    CREATE OBJECT lo_val_channel
      EXPORTING
        iv_channelname     = 'validation'
        io_datasource      = lo_val_datasource
        iv_compressiontype = iv_val_data_compressiontype
        iv_contenttype     = iv_val_data_contenttype.

    INSERT lo_val_channel INTO TABLE lt_input_data_config.

    "Create an ABAP object for algorithm specification."
    CREATE OBJECT lo_algorithm_specification
      EXPORTING
        iv_trainingimage     = iv_training_image
        iv_traininginputmode = iv_training_input_mode.

    "Create an ABAP object for resource configuration."
    CREATE OBJECT lo_resource_config
      EXPORTING
        iv_instancecount  = iv_instance_count
        iv_instancetype   = iv_instance_type
```

```
        iv_volumesizeingb = iv_volume_sizeingb.

    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_output_data_config
      EXPORTING
        iv_s3outputpath = iv_s3_output_path.

    "Create an ABAP object for stopping condition."
    CREATE OBJECT lo_stopping_condition
      EXPORTING
        iv_maxruntimeinseconds = iv_max_runtime_in_seconds.

    "Create a training job."
    TRY.
        oo_result = lo_sgm->createtrainingjob(    " oo_result is returned for
testing purposes. "
          iv_trainingjobname           = iv_training_job_name
          iv_rolearn                   = iv_role_arn
          it_hyperparameters           = lt_hyperparameters
          it_inputdataconfig           = lt_input_data_config
          io_algorithmspecification    = lo_algorithm_specification
          io_outputdataconfig          = lo_output_data_config
          io_resourceconfig            = lo_resource_config
          io_stoppingcondition         = lo_stopping_condition
        ).
        MESSAGE 'Training job created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTrainingJobreferência da API AWS SDK for SAP ABAP.

Crie e inicie um trabalho de SageMaker transformação usando um AWS SDK

O exemplo de código a seguir mostra como iniciar um trabalho de SageMaker transformação.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   DATA lo_transforminput TYPE REF TO /aws1/cl_sgmtransforminput.
   DATA lo_transformoutput TYPE REF TO /aws1/cl_sgmtransformoutput.
   DATA lo_transformresources TYPE REF TO /aws1/cl_sgmtransformresources.
   DATA lo_datasource  TYPE REF TO /aws1/cl_sgmtransformdatasrc.
   DATA lo_s3datasource  TYPE REF TO /aws1/cl_sgmtransforms3datasrc.

   "Create an ABAP object for an Amazon Simple Storage Service (Amazon S3) data
source."
   CREATE OBJECT lo_s3datasource
     EXPORTING
       iv_s3uri      = iv_tf_data_s3uri
       iv_s3datatype = iv_tf_data_s3datatype.

   "Create an ABAP object for data source."
   CREATE OBJECT lo_datasource
     EXPORTING
       io_s3datasource = lo_s3datasource.

   "Create an ABAP object for transform data source."
   CREATE OBJECT lo_transforminput
     EXPORTING
       io_datasource      = lo_datasource
       iv_contenttype     = iv_tf_data_contenttype
       iv_compressiontype = iv_tf_data_compressiontype.

   "Create an ABAP object for resource configuration."
   CREATE OBJECT lo_transformresources
     EXPORTING
       iv_instancecount = iv_instance_count
       iv_instancetype  = iv_instance_type.
```

```
    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_transformoutput
      EXPORTING
        iv_s3outputpath = iv_s3_output_path.

    "Create a transform job."
    TRY.
        oo_result = lo_sgm->createtransformjob(     " oo_result is returned for
testing purposes. "
            iv_modelname = iv_tf_model_name
            iv_transformjobname = iv_tf_job_name
            io_transforminput = lo_transforminput
            io_transformoutput = lo_transformoutput
            io_transformresources = lo_transformresources
        ).
        MESSAGE 'Transform job created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTransformJobreferência da API AWS SDK for SAP ABAP.

Cenários para SageMaker usar AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon SageMaker com AWS SDKs. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece com trabalhos SageMaker geoespaciais em um pipeline usando um SDK AWS
- Comece a usar SageMaker modelos e endpoints usando um SDK AWS

Comece com trabalhos SageMaker geoespaciais em um pipeline usando um SDK AWS

Os exemplos de código a seguir mostram como:

- Configure recursos para um pipeline.
- Configurar um pipeline que execute um trabalho geoespacial.
- Inicie a execução de um pipeline.
- Monitorar o status da execução.
- Ver saída do pipeline.
- Limpe os recursos.

Para obter mais informações, consulte Criar e executar SageMaker pipelines usando AWS SDKs no Community.aws.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as SageMaker operações.

```
using System.Text.Json;
using Amazon.SageMaker;
using Amazon.SageMaker.Model;
using Amazon.SageMakerGeospatial;
using Amazon.SageMakerGeospatial.Model;

namespace SageMakerActions;

/// <summary>
/// Wrapper class for Amazon SageMaker actions and logic.
/// </summary>
```

```
public class SageMakerWrapper
{
    private readonly IAmazonSageMaker _amazonSageMaker;
    public SageMakerWrapper(IAmazonSageMaker amazonSageMaker)
    {
        _amazonSageMaker = amazonSageMaker;
    }

    /// <summary>
    /// Create a pipeline from a JSON definition, or update it if the pipeline
 already exists.
    /// </summary>
    /// <returns>The Amazon Resource Name (ARN) of the pipeline.</returns>
    public async Task<string> SetupPipeline(string pipelineJson, string roleArn,
 string name, string description, string displayName)
    {
        try
        {
            var updateResponse = await _amazonSageMaker.UpdatePipelineAsync(
                new UpdatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });
            return updateResponse.PipelineArn;
        }
        catch (Amazon.SageMaker.Model.ResourceNotFoundException)
        {
            var createResponse = await _amazonSageMaker.CreatePipelineAsync(
                new CreatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });

            return createResponse.PipelineArn;
        }
    }
```

```
    /// <summary>
    /// Run a pipeline with input and output file locations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue to use for pipeline
callbacks.</param>
    /// <param name="inputLocationUrl">The input location in Amazon Simple
Storage Service (Amazon S3).</param>
    /// <param name="outputLocationUrl">The output location in Amazon S3.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="executionRoleArn">The ARN of the role.</param>
    /// <returns>The ARN of the pipeline run.</returns>
    public async Task<string> ExecutePipeline(
        string queueUrl,
        string inputLocationUrl,
        string outputLocationUrl,
        string pipelineName,
        string executionRoleArn)
    {
        var inputConfig = new VectorEnrichmentJobInputConfig()
        {
            DataSourceConfig = new()
            {
                S3Data = new VectorEnrichmentJobS3Data()
                {
                    S3Uri = inputLocationUrl
                }
            },
            DocumentType = VectorEnrichmentJobDocumentType.CSV
        };

        var exportConfig = new ExportVectorEnrichmentJobOutputConfig()
        {
            S3Data = new VectorEnrichmentJobS3Data()
            {
                S3Uri = outputLocationUrl
            }
        };

        var jobConfig = new VectorEnrichmentJobConfig()
        {
            ReverseGeocodingConfig = new ReverseGeocodingConfig()
            {
                XAttributeName = "Longitude",
```

```
                YAttributeName = "Latitude"
            }
        };

#pragma warning disable SageMaker1002 // Property value does not match required
 pattern is allowed here to match the pipeline definition.
        var startExecutionResponse = await
 _amazonSageMaker.StartPipelineExecutionAsync(
            new StartPipelineExecutionRequest()
            {
                PipelineName = pipelineName,
                PipelineExecutionDisplayName = pipelineName + "-example-
execution",
                PipelineParameters = new List<Parameter>()
                {
                    new Parameter() { Name = "parameter_execution_role", Value =
 executionRoleArn },
                    new Parameter() { Name = "parameter_queue_url", Value =
 queueUrl },
                    new Parameter() { Name = "parameter_vej_input_config", Value
 = JsonSerializer.Serialize(inputConfig) },
                    new Parameter() { Name = "parameter_vej_export_config", Value
 = JsonSerializer.Serialize(exportConfig) },
                    new Parameter() { Name = "parameter_step_1_vej_config", Value
 = JsonSerializer.Serialize(jobConfig) }
                }
            });
#pragma warning restore SageMaker1002
        return startExecutionResponse.PipelineExecutionArn;
    }

    /// <summary>
    /// Check the status of a run.
    /// </summary>
    /// <param name="pipelineExecutionArn">The ARN.</param>
    /// <returns>The status of the pipeline.</returns>
    public async Task<PipelineExecutionStatus>
 CheckPipelineExecutionStatus(string pipelineExecutionArn)
    {
        var describeResponse = await
 _amazonSageMaker.DescribePipelineExecutionAsync(
            new DescribePipelineExecutionRequest()
            {
                PipelineExecutionArn = pipelineExecutionArn
```

```
            });

        return describeResponse.PipelineExecutionStatus;
    }

    /// <summary>
    /// Delete a SageMaker pipeline by name.
    /// </summary>
    /// <param name="pipelineName">The name of the pipeline to delete.</param>
    /// <returns>The ARN of the pipeline.</returns>
    public async Task<string> DeletePipelineByName(string pipelineName)
    {
        var deleteResponse = await _amazonSageMaker.DeletePipelineAsync(
            new DeletePipelineRequest()
            {
                PipelineName = pipelineName
            });

        return deleteResponse.PipelineArn;
    }
}
```

Crie uma função que gerencie retornos de chamada do SageMaker pipeline.

```
using System.Text.Json;
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;
using Amazon.SageMaker;
using Amazon.SageMaker.Model;
using Amazon.SageMakerGeospatial;
using Amazon.SageMakerGeospatial.Model;

// Assembly attribute to enable the AWS Lambda function's JSON input to be
 converted into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace SageMakerLambda;

/// <summary>
/// The AWS Lambda function handler for the Amazon SageMaker pipeline.
```

```
/// </summary>
public class SageMakerLambdaFunction
{
    /// <summary>
    /// Default constructor. This constructor is used by AWS Lambda to construct
 the instance. When invoked in a Lambda environment
    /// the AWS credentials will come from the AWS Identity and Access Management
 (IAM) role associated with the function. The AWS Region will be set to the
    /// Region that the Lambda function is running in.
    /// </summary>
    public SageMakerLambdaFunction()
    {
    }

    /// <summary>
    /// The AWS Lambda function handler that processes events from the SageMaker
 pipeline and starts a job or export.
    /// </summary>
    /// <param name="request">The custom SageMaker pipeline request object.</
param>
    /// <param name="context">The Lambda context.</param>
    /// <returns>The dictionary of output parameters.</returns>
    public async Task<Dictionary<string, string>> FunctionHandler(PipelineRequest
 request, ILambdaContext context)
    {
        var geoSpatialClient = new AmazonSageMakerGeospatialClient();
        var sageMakerClient = new AmazonSageMakerClient();
        var responseDictionary = new Dictionary<string, string>();
        context.Logger.LogInformation("Function handler started with request: " +
 JsonSerializer.Serialize(request));
        if (request.Records != null && request.Records.Any())
        {
            context.Logger.LogInformation("Records found, this is a queue event.
 Processing the queue records.");
            foreach (var message in request.Records)
            {
                await ProcessMessageAsync(message, context, geoSpatialClient,
 sageMakerClient);
            }
        }
        else if (!string.IsNullOrEmpty(request.vej_export_config))
        {
            context.Logger.LogInformation("Export configuration found, this is an
 export. Start the Vector Enrichment Job (VEJ) export.");
```

```
            var outputConfig =

JsonSerializer.Deserialize<ExportVectorEnrichmentJobOutputConfig>(
                    request.vej_export_config);

            var exportResponse = await
geoSpatialClient.ExportVectorEnrichmentJobAsync(
                new ExportVectorEnrichmentJobRequest()
                {
                    Arn = request.vej_arn,
                    ExecutionRoleArn = request.Role,
                    OutputConfig = outputConfig
                });
            context.Logger.LogInformation($"Export response:
{JsonSerializer.Serialize(exportResponse)}");
            responseDictionary = new Dictionary<string, string>
            {
                { "export_eoj_status", exportResponse.ExportStatus.ToString() },
                { "vej_arn", exportResponse.Arn }
            };
        }
        else if (!string.IsNullOrEmpty(request.vej_name))
        {
            context.Logger.LogInformation("Vector Enrichment Job name found,
starting the job.");
            var inputConfig =
                JsonSerializer.Deserialize<VectorEnrichmentJobInputConfig>(
                    request.vej_input_config);

            var jobConfig =
                JsonSerializer.Deserialize<VectorEnrichmentJobConfig>(
                    request.vej_config);

            var jobResponse = await
geoSpatialClient.StartVectorEnrichmentJobAsync(
                new StartVectorEnrichmentJobRequest()
                {
                    ExecutionRoleArn = request.Role,
                    InputConfig = inputConfig,
                    Name = request.vej_name,
                    JobConfig = jobConfig

                });
```

```
            context.Logger.LogInformation("Job response: " +
JsonSerializer.Serialize(jobResponse));
            responseDictionary = new Dictionary<string, string>
            {
                { "vej_arn", jobResponse.Arn },
                { "statusCode", jobResponse.HttpStatusCode.ToString() }
            };
        }
        return responseDictionary;
    }

    /// <summary>
    /// Process a queue message and check the status of a SageMaker job.
    /// </summary>
    /// <param name="message">The queue message.</param>
    /// <param name="context">The Lambda context.</param>
    /// <param name="geoClient">The SageMaker GeoSpatial client.</param>
    /// <param name="sageMakerClient">The SageMaker client.</param>
    /// <returns>Async task.</returns>
    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
ILambdaContext context,
        AmazonSageMakerGeospatialClient geoClient, AmazonSageMakerClient
sageMakerClient)
    {
        context.Logger.LogInformation($"Processed message {message.Body}");

        // Get information about the SageMaker job.
        var payload = JsonSerializer.Deserialize<QueuePayload>(message.Body);
        context.Logger.LogInformation($"Payload token {payload!.token}");
        var token = payload.token;

        if (payload.arguments.ContainsKey("vej_arn"))
        {
            // Use the job ARN and the token to get the job status.
            var job_arn = payload.arguments["vej_arn"];
            context.Logger.LogInformation($"Token: {token}, arn {job_arn}");

            var jobInfo = geoClient.GetVectorEnrichmentJobAsync(
                new GetVectorEnrichmentJobRequest()
                {
                    Arn = job_arn
                });
            context.Logger.LogInformation("Job info: " +
JsonSerializer.Serialize(jobInfo));
```

```
            if (jobInfo.Result.Status == VectorEnrichmentJobStatus.COMPLETED)
            {
                context.Logger.LogInformation($"Status completed, resuming
 pipeline...");
                await sageMakerClient.SendPipelineExecutionStepSuccessAsync(
                    new SendPipelineExecutionStepSuccessRequest()
                    {
                        CallbackToken = token,
                        OutputParameters = new List<OutputParameter>()
                        {
                            new OutputParameter()
                                { Name = "export_status", Value =
 jobInfo.Result.Status }
                        }
                    });
            }
            else if (jobInfo.Result.Status == VectorEnrichmentJobStatus.FAILED)
            {
                context.Logger.LogInformation($"Status failed, stopping
 pipeline...");
                await sageMakerClient.SendPipelineExecutionStepFailureAsync(
                    new SendPipelineExecutionStepFailureRequest()
                    {
                        CallbackToken = token,
                        FailureReason = jobInfo.Result.ErrorDetails.ErrorMessage
                    });
            }
            else if (jobInfo.Result.Status ==
 VectorEnrichmentJobStatus.IN_PROGRESS)
            {
                // Put this message back in the queue to reprocess later.
                context.Logger.LogInformation(
                    $"Status still in progress, check back later.");
                throw new("Job still running.");
            }
        }
    }
}
```

Execute um cenário interativo em um prompt de comando.

```
public static class PipelineWorkflow
```

```
{
    public static IAmazonIdentityManagementService _iamClient = null!;
    public static SageMakerWrapper _sageMakerWrapper = null!;
    public static IAmazonSQS _sqsClient = null!;
    public static IAmazonS3 _s3Client = null!;
    public static IAmazonLambda _lambdaClient = null!;
    public static IConfiguration _configuration = null!;

    public static string lambdaFunctionName = "SageMakerExampleFunction";
    public static string sageMakerRoleName = "SageMakerExampleRole";
    public static string lambdaRoleName = "SageMakerExampleLambdaRole";

    private static string[] lambdaRolePolicies = null!;
    private static string[] sageMakerRolePolicies = null!;

    static async Task Main(string[] args)
    {
        var options = new AWSOptions() { Region = RegionEndpoint.USWest2 };
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>(options)
                    .AddAWSService<IAmazonEC2>(options)
                    .AddAWSService<IAmazonSageMaker>(options)
                    .AddAWSService<IAmazonSageMakerGeospatial>(options)
                    .AddAWSService<IAmazonSQS>(options)
                    .AddAWSService<IAmazonS3>(options)
                    .AddAWSService<IAmazonLambda>(options)
                    .AddTransient<SageMakerWrapper>()
        )
        .Build();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();
```

```
        ServicesSetup(host);
        string queueUrl = "";
        string queueName = _configuration["queueName"];
        string bucketName = _configuration["bucketName"];
        var pipelineName = _configuration["pipelineName"];

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine(
                "Welcome to the Amazon SageMaker pipeline example scenario.");
            Console.WriteLine(
                "\nThis example workflow will guide you through setting up and
running an" +
                "\nAmazon SageMaker pipeline. The pipeline uses an AWS Lambda
function and an" +
                "\nAmazon SQS Queue. It runs a vector enrichment reverse geocode
job to" +
                "\nreverse geocode addresses in an input file and store the
results in an export file.");
            Console.WriteLine(new string('-', 80));

            Console.WriteLine(new string('-', 80));
            Console.WriteLine(
                "First, we will set up the roles, functions, and queue needed by
the SageMaker pipeline.");
            Console.WriteLine(new string('-', 80));

            var lambdaRoleArn = await CreateLambdaRole();
            var sageMakerRoleArn = await CreateSageMakerRole();
            var functionArn = await SetupLambda(lambdaRoleArn, true);
            queueUrl = await SetupQueue(queueName);
            await SetupBucket(bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Now we can create and run our pipeline.");
            Console.WriteLine(new string('-', 80));

            await SetupPipeline(sageMakerRoleArn, functionArn, pipelineName);
            var executionArn = await ExecutePipeline(queueUrl, sageMakerRoleArn,
pipelineName, bucketName);
            await WaitForPipelineExecution(executionArn);
```

```
            await GetOutputResults(bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("The pipeline has completed. To view the pipeline
 and runs " +
                              "in SageMaker Studio, follow these instructions:" +
                              "\nhttps://docs.aws.amazon.com/sagemaker/latest/dg/
pipelines-studio.html");
            Console.WriteLine(new string('-', 80));

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await CleanupResources(true, queueUrl, pipelineName, bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("SageMaker pipeline scenario is complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
 {ex.Message}");
            await CleanupResources(true, queueUrl, pipelineName, bucketName);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _sageMakerWrapper = host.Services.GetRequiredService<SageMakerWrapper>();
        _iamClient =
 host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _sqsClient = host.Services.GetRequiredService<IAmazonSQS>();
        _s3Client = host.Services.GetRequiredService<IAmazonS3>();
        _lambdaClient = host.Services.GetRequiredService<IAmazonLambda>();
    }
```

```
    /// <summary>
    /// Set up AWS Lambda, either by updating an existing function or creating a
new function.
    /// </summary>
    /// <param name="roleArn">The role Amazon Resource Name (ARN) to use for the
Lambda function.</param>
    /// <param name="askUser">True to ask the user before updating.</param>
    /// <returns>The ARN of the function.</returns>
    public static async Task<string> SetupLambda(string roleArn, bool askUser)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Setting up the Lambda function for the pipeline.");
        var handlerName =
"SageMakerLambda::SageMakerLambda.SageMakerLambdaFunction::FunctionHandler";
        var functionArn = "";
        try
        {
            var functionInfo = await _lambdaClient.GetFunctionAsync(new
GetFunctionRequest()
            {
                FunctionName = lambdaFunctionName
            });

            var updateFunction = true;
            if (askUser)
            {
                updateFunction = GetYesNoResponse(
                    $"\tThe Lambda function {lambdaFunctionName} already exists,
do you want to update it?");
            }

            if (updateFunction)
            {
                // Update the Lambda function.
                using var zipMemoryStream = new MemoryStream(await
File.ReadAllBytesAsync("SageMakerLambda.zip"));
                await _lambdaClient.UpdateFunctionCodeAsync(
                    new UpdateFunctionCodeRequest()
                    {
                        FunctionName = lambdaFunctionName,
                        ZipFile = zipMemoryStream,
                    });
            }
```

```
            functionArn = functionInfo.Configuration.FunctionArn;
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"\tThe Lambda function {lambdaFunctionName} was
not found, creating the new function.");

            // Create the function if it does not already exist.
            using var zipMemoryStream = new MemoryStream(await
File.ReadAllBytesAsync("SageMakerLambda.zip"));
            var createResult = await _lambdaClient.CreateFunctionAsync(
                new CreateFunctionRequest()
                {
                    FunctionName = lambdaFunctionName,
                    Runtime = Runtime.Dotnet6,
                    Description = "SageMaker example function.",
                    Code = new FunctionCode()
                    {
                        ZipFile = zipMemoryStream
                    },
                    Handler = handlerName,
                    Role = roleArn,
                    Timeout = 30
                });

            functionArn = createResult.FunctionArn;
        }

        Console.WriteLine($"\tLambda ready with ARN {functionArn}.");
        Console.WriteLine(new string('-', 80));
        return functionArn;
    }

    /// <summary>
    /// Create a role to be used by AWS Lambda. Does not create the role if it
already exists.
    /// </summary>
    /// <returns>The role ARN.</returns>
    public static async Task<string> CreateLambdaRole()
    {
        Console.WriteLine(new string('-', 80));

        lambdaRolePolicies = new string[]{
            "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess",
```

```
            "arn:aws:iam::aws:policy/AmazonSQSFullAccess",
            "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess",
            "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy",
            "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole"
        };

        var roleArn = await GetRoleArnIfExists(lambdaRoleName);
        if (!string.IsNullOrEmpty(roleArn))
        {
            return roleArn;
        }

        Console.WriteLine("\tCreating a role to for AWS Lambda to use.");

        var assumeRolePolicy = "{" +
                               "\"Version\": \"2012-10-17\"," +
                               "\"Statement\": [{" +
                                    "\"Effect\": \"Allow\"," +
                                    "\"Principal\": {" +
                                        $"\"Service\": [" +
                                            "\"sagemaker.amazonaws.com\"," +
                                            "\"sagemaker-geospatial.amazonaws.com
\"," +
                                            "\"lambda.amazonaws.com\"," +
                                            "\"s3.amazonaws.com\"" +
                                        "]" +
                                    "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                               "}]" +
                            "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
                RoleName = lambdaRoleName
            });
        foreach (var policy in lambdaRolePolicies)
        {
            await _iamClient.AttachRolePolicyAsync(
```

```
                new AttachRolePolicyRequest()
                {
                    PolicyArn = policy,
                    RoleName = lambdaRoleName
                });
        }

        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        Console.WriteLine($"\tRole ready with ARN {roleResult.Role.Arn}.");
        Console.WriteLine(new string('-', 80));

        return roleResult.Role.Arn;
    }


    /// <summary>
    /// Create a role to be used by SageMaker.
    /// </summary>
    /// <returns>The role Amazon Resource Name (ARN).</returns>
    public static async Task<string> CreateSageMakerRole()
    {
        Console.WriteLine(new string('-', 80));

        sageMakerRolePolicies = new string[]{
            "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess",
            "arn:aws:iam::aws:policy/AmazonSageMakerGeospatialFullAccess",
        };

        var roleArn = await GetRoleArnIfExists(sageMakerRoleName);
        if (!string.IsNullOrEmpty(roleArn))
        {
            return roleArn;
        }

        Console.WriteLine("\tCreating a role to use with SageMaker.");

        var assumeRolePolicy = "{" +
                                        "\"Version\": \"2012-10-17\"," +
                                        "\"Statement\": [{" +
                                            "\"Effect\": \"Allow\"," +
                                            "\"Principal\": {" +
                                                $"\"Service\": [" +
```

```
                                                        "\"sagemaker.amazonaws.com
\"," +
                                                        "\"sagemaker-
geospatial.amazonaws.com\"," +
                                                        "\"lambda.amazonaws.com\"," +
                                                        "\"s3.amazonaws.com\"" +
                                                    "]" +
                                                "}," +
                                                "\"Action\": \"sts:AssumeRole\"" +
                                            "}]" +
                                        "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
                RoleName = sageMakerRoleName
            });

        foreach (var policy in sageMakerRolePolicies)
        {
            await _iamClient.AttachRolePolicyAsync(
                new AttachRolePolicyRequest()
                {
                    PolicyArn = policy,
                    RoleName = sageMakerRoleName
                });
        }

        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        Console.WriteLine($"\tRole ready with ARN {roleResult.Role.Arn}.");
        Console.WriteLine(new string('-', 80));
        return roleResult.Role.Arn;
    }

    /// <summary>
    /// Set up the SQS queue to use with the pipeline.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <returns>The URL for the queue.</returns>
    public static async Task<string> SetupQueue(string queueName)
    {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Setting up queue {queueName}.");

        try
        {
            var queueInfo = await _sqsClient.GetQueueUrlAsync(new
GetQueueUrlRequest()
            { QueueName = queueName });
            return queueInfo.QueueUrl;
        }
        catch (QueueDoesNotExistException)
        {
            var attrs = new Dictionary<string, string>
            {
                {
                    QueueAttributeName.DelaySeconds,
                    "5"
                },
                {
                    QueueAttributeName.ReceiveMessageWaitTimeSeconds,
                    "5"
                },
                {
                    QueueAttributeName.VisibilityTimeout,
                    "300"
                },
            };

            var request = new CreateQueueRequest
            {
                Attributes = attrs,
                QueueName = queueName,
            };

            var response = await _sqsClient.CreateQueueAsync(request);
            Thread.Sleep(10000);
            await ConnectLambda(response.QueueUrl);
            Console.WriteLine($"\tQueue ready with Url {response.QueueUrl}.");
            Console.WriteLine(new string('-', 80));
            return response.QueueUrl;
        }
    }

    /// <summary>
```

```
    /// Connect the queue to the Lambda function as an event source.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue.</param>
    /// <returns>Async task.</returns>
    public static async Task ConnectLambda(string queueUrl)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Connecting the Lambda function and queue for the
pipeline.");

        var queueAttributes = await _sqsClient.GetQueueAttributesAsync(
            new GetQueueAttributesRequest() { QueueUrl = queueUrl, AttributeNames
= new List<string>() { "All" } });
        var queueArn = queueAttributes.QueueARN;

        var eventSource = await _lambdaClient.ListEventSourceMappingsAsync(
             new ListEventSourceMappingsRequest()
             {
                 FunctionName = lambdaFunctionName
             });

        if (!eventSource.EventSourceMappings.Any())
        {
            // Only add the event source mapping if it does not already exist.
            await _lambdaClient.CreateEventSourceMappingAsync(
                new CreateEventSourceMappingRequest()
                {
                    EventSourceArn = queueArn,
                    FunctionName = lambdaFunctionName,
                    Enabled = true
                });
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the bucket to use for pipeline input and output.
    /// </summary>
    /// <param name="bucketName">The name for the bucket.</param>
    /// <returns>Async task.</returns>
    public static async Task SetupBucket(string bucketName)
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine($"Setting up bucket {bucketName}.");

        var bucketExists = await
Amazon.S3.Util.AmazonS3Util.DoesS3BucketExistV2Async(_s3Client,
            bucketName);

        if (!bucketExists)
        {
            await _s3Client.PutBucketAsync(new PutBucketRequest()
            {
                BucketName = bucketName,
                BucketRegion = S3Region.USWest2
            });

            Thread.Sleep(5000);

            await _s3Client.PutObjectAsync(new PutObjectRequest()
            {
                BucketName = bucketName,
                Key = "samplefiles/latlongtest.csv",
                FilePath = "latlongtest.csv"
            });
        }

        Console.WriteLine($"\tBucket {bucketName} ready.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Display some results from the output directory.
    /// </summary>
    /// <param name="bucketName">The name for the bucket.</param>
    /// <returns>Async task.</returns>
    public static async Task<string> GetOutputResults(string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Getting output results {bucketName}.");
        string outputKey = "";
        Thread.Sleep(15000);
        var outputFiles = await _s3Client.ListObjectsAsync(
              new ListObjectsRequest()
              {
                  BucketName = bucketName,
                  Prefix = "outputfiles/"
```

```
              });

        if (outputFiles.S3Objects.Any())
        {
            var sampleOutput = outputFiles.S3Objects.OrderBy(s =>
s.LastModified).Last();
            Console.WriteLine($"\tOutput file: {sampleOutput.Key}");
            var outputSampleResponse = await _s3Client.GetObjectAsync(
                new GetObjectRequest()
                {
                    BucketName = bucketName,
                    Key = sampleOutput.Key
                });
            outputKey = sampleOutput.Key;
            StreamReader reader = new
StreamReader(outputSampleResponse.ResponseStream);
            await reader.ReadLineAsync();
            Console.WriteLine("\tOutput file contents: \n");
            for (int i = 0; i < 10; i++)
            {
                if (!reader.EndOfStream)
                {
                    Console.WriteLine("\t" + await reader.ReadLineAsync());
                }
            }
        }

        Console.WriteLine(new string('-', 80));
        return outputKey;
    }

    /// <summary>
    /// Create a pipeline from the example pipeline JSON
    /// that includes the Lambda, callback, processing, and export jobs.
    /// </summary>
    /// <param name="roleArn">The ARN of the role for the pipeline.</param>
    /// <param name="functionArn">The ARN of the Lambda function for the
pipeline.</param>
    /// <param name="pipelineName">The name for the pipeline.</param>
    /// <returns>The ARN of the pipeline.</returns>
    public static async Task<string> SetupPipeline(string roleArn, string
functionArn, string pipelineName)
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine($"Setting up the pipeline.");

        var pipelineJson = await
 File.ReadAllTextAsync("GeoSpatialPipeline.json");

        // Add the correct function ARN instead of the placeholder.
        pipelineJson = pipelineJson.Replace("*FUNCTION_ARN*", functionArn);

        var pipelineArn = await _sageMakerWrapper.SetupPipeline(pipelineJson,
 roleArn, pipelineName,
            "sdk example pipeline", pipelineName);

        Console.WriteLine($"\tPipeline set up with ARN {pipelineArn}.");
        Console.WriteLine(new string('-', 80));

        return pipelineArn;
    }

    /// <summary>
    /// Start a pipeline run with job configurations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue used in the pipeline.</
param>
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="bucketName">The name of the bucket.</param>
    /// <returns>The pipeline run ARN.</returns>
    public static async Task<string> ExecutePipeline(
        string queueUrl,
        string roleArn,
        string pipelineName,
        string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Starting pipeline execution.");

        var input = $"s3://{bucketName}/samplefiles/latlongtest.csv";
        var output = $"s3://{bucketName}/outputfiles/";

        var executionARN =
            await _sageMakerWrapper.ExecutePipeline(queueUrl, input, output,
                pipelineName, roleArn);

        Console.WriteLine($"\tRun started with ARN {executionARN}.");
```

```
        Console.WriteLine(new string('-', 80));

        return executionARN;
    }

    /// <summary>
    /// Wait for a pipeline run to complete.
    /// </summary>
    /// <param name="executionArn">The pipeline run ARN.</param>
    /// <returns>Async task.</returns>
    public static async Task WaitForPipelineExecution(string executionArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Waiting for pipeline to finish.");

        PipelineExecutionStatus status;
        do
        {
            status = await
_sageMakerWrapper.CheckPipelineExecutionStatus(executionArn);
            Thread.Sleep(30000);
            Console.WriteLine($"\tStatus is {status}.");
        } while (status == PipelineExecutionStatus.Executing);

        Console.WriteLine($"\tPipeline finished with status {status}.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="askUser">True to ask the user for cleanup.</param>
    /// <param name="queueUrl">The URL of the queue to clean up.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="bucketName">The name of the bucket.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> CleanupResources(
        bool askUser,
        string queueUrl,
        string pipelineName,
        string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");
```

```
        if (!askUser || GetYesNoResponse($"\tDelete pipeline {pipelineName}? (y/
n)"))
        {
            Console.WriteLine($"\tDeleting pipeline.");
            // Delete the pipeline.
            await _sageMakerWrapper.DeletePipelineByName(pipelineName);
        }

        if (!string.IsNullOrEmpty(queueUrl) && (!askUser ||
 GetYesNoResponse($"\tDelete queue {queueUrl}? (y/n)")))
        {
            Console.WriteLine($"\tDeleting queue.");
            // Delete the queue.
            await _sqsClient.DeleteQueueAsync(new DeleteQueueRequest(queueUrl));
        }

        if (!askUser || GetYesNoResponse($"\tDelete Amazon S3 bucket
 {bucketName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting bucket.");
            // Delete all objects in the bucket.
            var deleteList = await _s3Client.ListObjectsV2Async(new
 ListObjectsV2Request()
            {
                BucketName = bucketName
            });
            if (deleteList.KeyCount > 0)
            {
                await _s3Client.DeleteObjectsAsync(new DeleteObjectsRequest()
                {
                    BucketName = bucketName,
                    Objects = deleteList.S3Objects
                        .Select(o => new KeyVersion { Key = o.Key }).ToList()
                });
            }

            // Now delete the bucket.
            await _s3Client.DeleteBucketAsync(new DeleteBucketRequest()
            {
                BucketName = bucketName
            });
        }
```

```
        if (!askUser || GetYesNoResponse($"\tDelete lambda {lambdaFunctionName}?
 (y/n)"))
        {
            Console.WriteLine($"\tDeleting lambda function.");

            await _lambdaClient.DeleteFunctionAsync(new DeleteFunctionRequest()
            {
                FunctionName = lambdaFunctionName
            });
        }

        if (!askUser || GetYesNoResponse($"\tDelete role {lambdaRoleName}? (y/
n)"))
        {
            Console.WriteLine($"\tDetaching policies and deleting role.");

            foreach (var policy in lambdaRolePolicies)
            {
                await _iamClient!.DetachRolePolicyAsync(new
 DetachRolePolicyRequest()
                {
                    RoleName = lambdaRoleName,
                    PolicyArn = policy
                });
            }

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = lambdaRoleName
            });
        }

        if (!askUser || GetYesNoResponse($"\tDelete role {sageMakerRoleName}? (y/
n)"))
        {
            Console.WriteLine($"\tDetaching policies and deleting role.");

            foreach (var policy in sageMakerRolePolicies)
            {
                await _iamClient!.DetachRolePolicyAsync(new
 DetachRolePolicyRequest()
                {
                    RoleName = sageMakerRoleName,
                    PolicyArn = policy
```

```
                });
            }

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = sageMakerRoleName
            });
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Helper method to get a role's ARN if it already exists.
    /// </summary>
    /// <param name="roleName">The name of the AWS Identity and Access Management
 (IAM) Role to look for.</param>
    /// <returns>The role ARN if it exists, otherwise an empty string.</returns>
    private static async Task<string> GetRoleArnIfExists(string roleName)
    {
        Console.WriteLine($"Checking for role named {roleName}.");

        try
        {
            var existingRole = await _iamClient.GetRoleAsync(new GetRoleRequest()
            {
                RoleName = lambdaRoleName
            });
            return existingRole.Role.Arn;
        }
        catch (NoSuchEntityException)
        {
            return string.Empty;
        }
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
```

```
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
public class SagemakerWorkflow {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");
    private static String eventSourceMapping = "";

    public static void main(String[] args) throws InterruptedException {
        final String usage = "\n" +
                "Usage:\n" +
```

```
                "    <sageMakerRoleName> <lambdaRoleName> <functionFileLocation>
 <functionName> <queueName> <bucketName> <lnglatData> <spatialPipelinePath>
 <pipelineName>\n\n"
                +
                "Where:\n" +
                "    sageMakerRoleName - The name of the Amazon SageMaker role.\n
\n" +
                "    lambdaRoleName - The name of the AWS Lambda role.\n\n" +
                "    functionFileLocation - The file location where the JAR file
 that represents the AWS Lambda function is located.\n\n"
                +
                "    functionName - The name of the AWS Lambda function (for
 example,SageMakerExampleFunction).\n\n" +
                "    queueName - The name of the Amazon Simple Queue Service
 (Amazon SQS) queue.\n\n" +
                "    bucketName - The name of the Amazon Simple Storage Service
 (Amazon S3) bucket.\n\n" +
                "    lnglatData - The file location of the latlongtest.csv file
 required for this use case.\n\n" +
                "    spatialPipelinePath - The file location of the
 GeoSpatialPipeline.json file required for this use case.\n\n"
                +
                "    pipelineName - The name of the pipeline to create (for
 example, sagemaker-sdk-example-pipeline).\n\n";

        if (args.length != 9) {
            System.out.println(usage);
            System.exit(1);
        }

        String sageMakerRoleName = args[0];
        String lambdaRoleName = args[1];
        String functionFileLocation = args[2];
        String functionName = args[3];
        String queueName = args[4];
        String bucketName = args[5];
        String lnglatData = args[6];
        String spatialPipelinePath = args[7];
        String pipelineName = args[8];
        String handlerName =
 "org.example.SageMakerLambdaFunction::handleRequest";

        Region region = Region.US_WEST_2;
        SageMakerClient sageMakerClient = SageMakerClient.builder()
```

```
                .region(region)
                .build();

        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        LambdaClient lambdaClient = LambdaClient.builder()
                .region(region)
                .build();

        SqsClient sqsClient = SqsClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon SageMaker pipeline example
scenario.");
        System.out.println(
                "\nThis example workflow will guide you through setting up and
running an" +
                        "\nAmazon SageMaker pipeline. The pipeline uses an AWS
Lambda function and an" +
                        "\nAmazon SQS Queue. It runs a vector enrichment reverse
geocode job to" +
                        "\nreverse geocode addresses in an input file and store
the results in an export file.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("First, we will set up the roles, functions, and queue
needed by the SageMaker pipeline.");
        String lambdaRoleArn = checkLambdaRole(iam, lambdaRoleName);
        String sageMakerRoleArn = checkSageMakerRole(iam, sageMakerRoleName);

        String functionArn = checkFunction(lambdaClient, functionName,
functionFileLocation, lambdaRoleArn,
                handlerName);
        String queueUrl = checkQueue(sqsClient, lambdaClient, queueName,
functionName);
```

```
        System.out.println("The queue URL is " + queueUrl);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Setting up bucket " + bucketName);
        if (!checkBucket(s3Client, bucketName)) {
            setupBucket(s3Client, bucketName);
            System.out.println("Put " + lnglatData + " into " + bucketName);
            putS3Object(s3Client, bucketName, "latlongtest.csv", lnglatData);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Now we can create and run our pipeline.");
        setupPipeline(sageMakerClient, spatialPipelinePath, sageMakerRoleArn,
 functionArn, pipelineName);
        String pipelineExecutionARN = executePipeline(sageMakerClient,
 bucketName, queueUrl, sageMakerRoleArn,
                pipelineName);
        System.out.println("The pipeline execution ARN value is " +
 pipelineExecutionARN);
        waitForPipelineExecution(sageMakerClient, pipelineExecutionARN);
        System.out.println("Getting output results " + bucketName);
        getOutputResults(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The pipeline has completed. To view the pipeline and
 runs " +
                "in SageMaker Studio, follow these instructions:" +
                "\nhttps://docs.aws.amazon.com/sagemaker/latest/dg/pipelines-
studio.html");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Do you want to delete the AWS resources used in this
 Workflow? (y/n)");
        Scanner in = new Scanner(System.in);
        String delResources = in.nextLine();
        if (delResources.compareTo("y") == 0) {
            System.out.println("Lets clean up the AWS resources. Wait 30
 seconds");
            TimeUnit.SECONDS.sleep(30);
            deleteEventSourceMapping(lambdaClient);
```

```
            deleteSQSQueue(sqsClient, queueName);
            listBucketObjects(s3Client, bucketName);
            deleteBucket(s3Client, bucketName);
            deleteLambdaFunction(lambdaClient, functionName);
            deleteLambdaRole(iam, lambdaRoleName);
            deleteSagemakerRole(iam, sageMakerRoleName);
            deletePipeline(sageMakerClient, pipelineName);
        } else {
            System.out.println("The AWS Resources were not deleted!");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("SageMaker pipeline scenario is complete.");
        System.out.println(DASHES);
    }

    private static void readObject(S3Client s3Client, String bucketName, String
key) {
        System.out.println("Output file contents: \n");
        GetObjectRequest objectRequest = GetObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        ResponseBytes<GetObjectResponse> objectBytes =
s3Client.getObjectAsBytes(objectRequest);
        byte[] byteArray = objectBytes.asByteArray();
        String text = new String(byteArray, StandardCharsets.UTF_8);
        System.out.println("Text output: " + text);
    }

    // Display some results from the output directory.
    public static void getOutputResults(S3Client s3Client, String bucketName) {
        System.out.println("Getting output results {bucketName}.");
        ListObjectsRequest listObjectsRequest = ListObjectsRequest.builder()
                .bucket(bucketName)
                .prefix("outputfiles/")
                .build();

        ListObjectsResponse response = s3Client.listObjects(listObjectsRequest);
        List<S3Object> s3Objects = response.contents();
        for (S3Object object : s3Objects) {
            readObject(s3Client, bucketName, object.key());
```

```
        }
    }

    // Check the status of a pipeline execution.
    public static void waitForPipelineExecution(SageMakerClient sageMakerClient,
String executionArn)
            throws InterruptedException {
        String status;
        int index = 0;
        do {
            DescribePipelineExecutionRequest pipelineExecutionRequest =
DescribePipelineExecutionRequest.builder()
                    .pipelineExecutionArn(executionArn)
                    .build();

            DescribePipelineExecutionResponse response = sageMakerClient
                    .describePipelineExecution(pipelineExecutionRequest);
            status = response.pipelineExecutionStatusAsString();
            System.out.println(index + ". The Status of the pipeline is " +
status);
            TimeUnit.SECONDS.sleep(4);
            index++;
        } while ("Executing".equals(status));
        System.out.println("Pipeline finished with status " + status);
    }

    // Delete a SageMaker pipeline by name.
    public static void deletePipeline(SageMakerClient sageMakerClient, String
pipelineName) {
        DeletePipelineRequest pipelineRequest = DeletePipelineRequest.builder()
                .pipelineName(pipelineName)
                .build();

        sageMakerClient.deletePipeline(pipelineRequest);
        System.out.println("*** Successfully deleted " + pipelineName);
    }

    // Create a pipeline from the example pipeline JSON.
    public static void setupPipeline(SageMakerClient sageMakerClient, String
filePath, String roleArn,
            String functionArn, String pipelineName) {
        System.out.println("Setting up the pipeline.");
        JSONParser parser = new JSONParser();
```

```
        // Read JSON and get pipeline definition.
        try (FileReader reader = new FileReader(filePath)) {
            Object obj = parser.parse(reader);
            JSONObject jsonObject = (JSONObject) obj;
            JSONArray stepsArray = (JSONArray) jsonObject.get("Steps");
            for (Object stepObj : stepsArray) {
                JSONObject step = (JSONObject) stepObj;
                if (step.containsKey("FunctionArn")) {
                    step.put("FunctionArn", functionArn);
                }
            }
            System.out.println(jsonObject);

            // Create the pipeline.
            CreatePipelineRequest pipelineRequest =
 CreatePipelineRequest.builder()
                    .pipelineDescription("Java SDK example pipeline")
                    .roleArn(roleArn)
                    .pipelineName(pipelineName)
                    .pipelineDefinition(jsonObject.toString())
                    .build();

            sageMakerClient.createPipeline(pipelineRequest);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException | ParseException e) {
            throw new RuntimeException(e);
        }
    }

    // Start a pipeline run with job configurations.
    public static String executePipeline(SageMakerClient sageMakerClient, String
 bucketName, String queueUrl,
            String roleArn, String pipelineName) {
        System.out.println("Starting pipeline execution.");
        String inputBucketLocation = "s3://" + bucketName + "/samplefiles/
latlongtest.csv";
        String output = "s3://" + bucketName + "/outputfiles/";
        Gson gson = new GsonBuilder()
                .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                .setPrettyPrinting().create();
```

```
        // Set up all parameters required to start the pipeline.
        List<Parameter> parameters = new ArrayList<>();
        Parameter para1 = Parameter.builder()
                .name("parameter_execution_role")
                .value(roleArn)
                .build();

        Parameter para2 = Parameter.builder()
                .name("parameter_queue_url")
                .value(queueUrl)
                .build();

        String inputJSON = "{\n" +
                "  \"DataSourceConfig\": {\n" +
                "    \"S3Data\": {\n" +
                "      \"S3Uri\": \"s3://" + bucketName + "/samplefiles/
latlongtest.csv\"\n" +
                "    },\n" +
                "    \"Type\": \"S3_DATA\"\n" +
                "  },\n" +
                "  \"DocumentType\": \"CSV\"\n" +
                "}";

        System.out.println(inputJSON);

        Parameter para3 = Parameter.builder()
                .name("parameter_vej_input_config")
                .value(inputJSON)
                .build();

        // Create an ExportVectorEnrichmentJobOutputConfig object.
        VectorEnrichmentJobS3Data jobS3Data = VectorEnrichmentJobS3Data.builder()
                .s3Uri(output)
                .build();

        ExportVectorEnrichmentJobOutputConfig outputConfig =
 ExportVectorEnrichmentJobOutputConfig.builder()
                .s3Data(jobS3Data)
                .build();

        String gson4 = gson.toJson(outputConfig);
        Parameter para4 = Parameter.builder()
                .name("parameter_vej_export_config")
                .value(gson4)
```

```
                .build();
        System.out.println("parameter_vej_export_config:" +
 gson.toJson(outputConfig));

        // Create a VectorEnrichmentJobConfig object.
        ReverseGeocodingConfig reverseGeocodingConfig =
 ReverseGeocodingConfig.builder()
                .xAttributeName("Longitude")
                .yAttributeName("Latitude")
                .build();

        VectorEnrichmentJobConfig jobConfig = VectorEnrichmentJobConfig.builder()
                .reverseGeocodingConfig(reverseGeocodingConfig)
                .build();

        String para5JSON = "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig
\":{\"XAttributeName\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}";
        Parameter para5 = Parameter.builder()
                .name("parameter_step_1_vej_config")
                .value(para5JSON)
                .build();

        System.out.println("parameter_step_1_vej_config:" +
 gson.toJson(jobConfig));
        parameters.add(para1);
        parameters.add(para2);
        parameters.add(para3);
        parameters.add(para4);
        parameters.add(para5);

        StartPipelineExecutionRequest pipelineExecutionRequest =
 StartPipelineExecutionRequest.builder()
                .pipelineExecutionDescription("Created using Java SDK")
                .pipelineExecutionDisplayName(pipelineName + "-example-
execution")
                .pipelineParameters(parameters)
                .pipelineName(pipelineName)
                .build();

        StartPipelineExecutionResponse response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest);
        return response.pipelineExecutionArn();
    }
```

```
    public static void deleteEventSourceMapping(LambdaClient lambdaClient) {
        DeleteEventSourceMappingRequest eventSourceMappingRequest =
DeleteEventSourceMappingRequest.builder()
                .uuid(eventSourceMapping)
                .build();

        lambdaClient.deleteEventSourceMapping(eventSourceMappingRequest);
    }

    public static void deleteSagemakerRole(IamClient iam, String roleName) {
        String[] sageMakerRolePolicies = getSageMakerRolePolicies();
        try {
            for (String policy : sageMakerRolePolicies) {
                // First the policy needs to be detached.
                DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
                        .policyArn(policy)
                        .roleName(roleName)
                        .build();

                iam.detachRolePolicy(rolePolicyRequest);
            }

            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteLambdaRole(IamClient iam, String roleName) {
        String[] lambdaRolePolicies = getLambdaRolePolicies();
        try {
            for (String policy : lambdaRolePolicies) {
                // First the policy needs to be detached.
                DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
```

```
                        .policyArn(policy)
                        .roleName(roleName)
                        .build();

                iam.detachRolePolicy(rolePolicyRequest);
            }

            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Delete the specific AWS Lambda function.
    public static void deleteLambdaFunction(LambdaClient awsLambda, String
functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            awsLambda.deleteFunction(request);
            System.out.println("*** " + functionName + " was deleted");

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Delete the specific S3 bucket.
    public static void deleteBucket(S3Client s3Client, String bucketName) {
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucketName)
                .build();
        s3Client.deleteBucket(deleteBucketRequest);
```

```
        System.out.println("*** " + bucketName + " was deleted.");
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsRequest listObjects = ListObjectsRequest
                    .builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.print("\n The name of the key is " + myValue.key());
                deleteBucketObjects(s3, bucketName, myValue.key());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteBucketObjects(S3Client s3, String bucketName, String
 objectName) {
        ArrayList<ObjectIdentifier> toDelete = new ArrayList<>();
        toDelete.add(ObjectIdentifier.builder()
                .key(objectName)
                .build());
        try {
            DeleteObjectsRequest dor = DeleteObjectsRequest.builder()
                    .bucket(bucketName)
                    .delete(Delete.builder()
                            .objects(toDelete).build())
                    .build();

            s3.deleteObjects(dor);
            System.out.println("*** " + bucketName + " objects were deleted.");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    // Delete the specific Amazon SQS queue.
    public static void deleteSQSQueue(SqsClient sqsClient, String queueName) {
        try {
            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            DeleteQueueRequest deleteQueueRequest = DeleteQueueRequest.builder()
                    .queueUrl(queueUrl)
                    .build();

            sqsClient.deleteQueue(deleteQueueRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void putS3Object(S3Client s3, String bucketName, String
 objectKey, String objectPath) {
        try {
            Map<String, String> metadata = new HashMap<>();
            metadata.put("x-amz-meta-myVal", "test");
            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key("samplefiles/" + objectKey)
                    .metadata(metadata)
                    .build();

            s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
            System.out.println("Successfully placed " + objectKey + " into bucket
 " + bucketName);

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void setupBucket(S3Client s3Client, String bucketName) {
        try {
```

```
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Set up the SQS queue to use with the pipeline.
    public static String setupQueue(SqsClient sqsClient, LambdaClient
lambdaClient, String queueName,
            String lambdaName) {
        System.out.println("Setting up queue named " + queueName);
        try {
            Map<QueueAttributeName, String> queueAtt = new HashMap<>();
            queueAtt.put(QueueAttributeName.DELAY_SECONDS, "5");
            queueAtt.put(QueueAttributeName.RECEIVE_MESSAGE_WAIT_TIME_SECONDS,
"5");
            queueAtt.put(QueueAttributeName.VISIBILITY_TIMEOUT, "300");
            CreateQueueRequest createQueueRequest = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .attributes(queueAtt)
                    .build();

            sqsClient.createQueue(createQueueRequest);
            System.out.println("\nGet queue url");
            GetQueueUrlResponse getQueueUrlResponse = sqsClient

.getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
            TimeUnit.SECONDS.sleep(15);
```

```
            connectLambda(sqsClient, lambdaClient,
getQueueUrlResponse.queueUrl(), lambdaName);
            System.out.println("Queue ready with Url " +
getQueueUrlResponse.queueUrl());
            return getQueueUrlResponse.queueUrl();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    // Connect the queue to the Lambda function as an event source.
    public static void connectLambda(SqsClient sqsClient, LambdaClient
lambdaClient, String queueUrl,
            String lambdaName) {
        System.out.println("Connecting the Lambda function and queue for the
pipeline.");
        String queueArn = "";

        // Specify the attributes to retrieve.
        List<QueueAttributeName> atts = new ArrayList<>();
        atts.add(QueueAttributeName.QUEUE_ARN);
        GetQueueAttributesRequest attributesRequest =
GetQueueAttributesRequest.builder()
                .queueUrl(queueUrl)
                .attributeNames(atts)
                .build();

        GetQueueAttributesResponse response =
sqsClient.getQueueAttributes(attributesRequest);
        Map<String, String> queueAtts = response.attributesAsStrings();
        for (Map.Entry<String, String> queueAtt : queueAtts.entrySet()) {
            System.out.println("Key = " + queueAtt.getKey() + ", Value = " +
queueAtt.getValue());
            queueArn = queueAtt.getValue();
        }

        CreateEventSourceMappingRequest eventSourceMappingRequest =
CreateEventSourceMappingRequest.builder()
```

```
                .eventSourceArn(queueArn)
                .functionName(lambdaName)
                .build();

        CreateEventSourceMappingResponse response1 =
lambdaClient.createEventSourceMapping(eventSourceMappingRequest);
        eventSourceMapping = response1.uuid();
        System.out.println("The mapping between the event source and Lambda
function was successful");
    }

    // Create an AWS Lambda function.
    public static String createLambdaFunction(LambdaClient awsLambda, String
functionName, String filePath, String role,
            String handler) {
        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);
            FunctionCode code = FunctionCode.builder()
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest =
CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("SageMaker example function.")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA11)
                    .timeout(200)
                    .memorySize(1024)
                    .role(role)
                    .build();

            // Create a Lambda function using a waiter.
            CreateFunctionResponse functionResponse =
awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
```

```
            System.out.println("The function ARN is " +
functionResponse.functionArn());
            return functionResponse.functionArn();

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createSageMakerRole(IamClient iam, String roleName) {
        String[] sageMakerRolePolicies = getSageMakerRolePolicies();
        System.out.println("Creating a role to use with SageMaker.");
        String assumeRolePolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": [" +
                "\"sagemaker.amazonaws.com\"," +
                "\"sagemaker-geospatial.amazonaws.com\"," +
                "\"lambda.amazonaws.com\"," +
                "\"s3.amazonaws.com\"" +
                "]" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(roleName)
                    .assumeRolePolicyDocument(assumeRolePolicy)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse roleResult = iam.createRole(request);

            // Attach the policies to the role.
            for (String policy : sageMakerRolePolicies) {
                AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                        .roleName(roleName)
```

```
                        .policyArn(policy)
                        .build();

                iam.attachRolePolicy(attachRequest);
            }

            // Allow time for the role to be ready.
            TimeUnit.SECONDS.sleep(15);
            System.out.println("Role ready with ARN " + roleResult.role().arn());
            return roleResult.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    private static String createLambdaRole(IamClient iam, String roleName) {
        String[] lambdaRolePolicies = getLambdaRolePolicies();
        String assumeRolePolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": [" +
                "\"sagemaker.amazonaws.com\"," +
                "\"sagemaker-geospatial.amazonaws.com\"," +
                "\"lambda.amazonaws.com\"," +
                "\"s3.amazonaws.com\"" +
                "]" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(roleName)
                    .assumeRolePolicyDocument(assumeRolePolicy)
                    .description("Created using the AWS SDK for Java")
                    .build();
```

```
            CreateRoleResponse roleResult = iam.createRole(request);

            // Attach the policies to the role.
            for (String policy : lambdaRolePolicies) {
                AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(policy)
                        .build();

                iam.attachRolePolicy(attachRequest);
            }

            // Allow time for the role to be ready.
            TimeUnit.SECONDS.sleep(15);
            System.out.println("Role ready with ARN " + roleResult.role().arn());
            return roleResult.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());

        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    public static String checkFunction(LambdaClient lambdaClient, String
functionName, String filePath, String role,
            String handler) {
        System.out.println("Create an AWS Lambda function used in this
workflow.");
        String functionArn;
        try {
            // Does this function already exist.
            GetFunctionRequest functionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            GetFunctionResponse response =
lambdaClient.getFunction(functionRequest);
            functionArn = response.configuration().functionArn();
```

```
        } catch (LambdaException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            functionArn = createLambdaFunction(lambdaClient, functionName,
filePath, role, handler);
        }
        return functionArn;
    }

    // Check to see if the specific S3 bucket exists. If the S3 bucket exists,
this
    // method returns true.
    public static boolean checkBucket(S3Client s3, String bucketName) {
        try {
            HeadBucketRequest headBucketRequest = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3.headBucket(headBucketRequest);
            System.out.println(bucketName + " exists");
            return true;

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        return false;
    }

    // Checks to see if the Amazon SQS queue exists. If not, this method creates
a
    // new queue
    // and returns the ARN value.
    public static String checkQueue(SqsClient sqsClient, LambdaClient
lambdaClient, String queueName,
            String lambdaName) {
        System.out.println("Creating a queue for this use case.");
        String queueUrl;
        try {
            GetQueueUrlRequest request = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            GetQueueUrlResponse response = sqsClient.getQueueUrl(request);
            queueUrl = response.queueUrl();
            System.out.println(queueUrl);
```

```
        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            queueUrl = setupQueue(sqsClient, lambdaClient, queueName,
lambdaName);
        }
        return queueUrl;
    }

    // Checks to see if the Lambda role exists. If not, this method creates it.
    public static String checkLambdaRole(IamClient iam, String roleName) {
        System.out.println("Creating a role to for AWS Lambda to use.");
        String roleArn;
        try {
            GetRoleRequest roleRequest = GetRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            GetRoleResponse response = iam.getRole(roleRequest);
            roleArn = response.role().arn();
            System.out.println(roleArn);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            roleArn = createLambdaRole(iam, roleName);
        }
        return roleArn;
    }

    // Checks to see if the SageMaker role exists. If not, this method creates
it.
    public static String checkSageMakerRole(IamClient iam, String roleName) {
        System.out.println("Creating a role to for AWS SageMaker to use.");
        String roleArn;
        try {
            GetRoleRequest roleRequest = GetRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            GetRoleResponse response = iam.getRole(roleRequest);
            roleArn = response.role().arn();
            System.out.println(roleArn);

        } catch (IamException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            roleArn = createSageMakerRole(iam, roleName);
        }
        return roleArn;
    }

    private static String[] getSageMakerRolePolicies() {
        String[] sageMakerRolePolicies = new String[3];
        sageMakerRolePolicies[0] = "arn:aws:iam::aws:policy/
AmazonSageMakerFullAccess";
        sageMakerRolePolicies[1] = "arn:aws:iam::aws:policy/" +
 "AmazonSageMakerGeospatialFullAccess";
        sageMakerRolePolicies[2] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess";
        return sageMakerRolePolicies;
    }

    private static String[] getLambdaRolePolicies() {
        String[] lambdaRolePolicies = new String[5];
        lambdaRolePolicies[0] = "arn:aws:iam::aws:policy/
AmazonSageMakerFullAccess";
        lambdaRolePolicies[1] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess";
        lambdaRolePolicies[2] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess";
        lambdaRolePolicies[3] = "arn:aws:iam::aws:policy/service-role/"
                + "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy";
        lambdaRolePolicies[4] = "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole";
        return lambdaRolePolicies;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O trecho do arquivo a seguir contém funções que usam o SageMaker cliente para gerenciar um pipeline.

```
import { readFileSync } from "fs";

import {
  CreateRoleCommand,
  DeleteRoleCommand,
  CreatePolicyCommand,
  DeletePolicyCommand,
  AttachRolePolicyCommand,
  DetachRolePolicyCommand,
} from "@aws-sdk/client-iam";

import {
  PublishLayerVersionCommand,
  DeleteLayerVersionCommand,
  CreateFunctionCommand,
  Runtime,
  DeleteFunctionCommand,
  CreateEventSourceMappingCommand,
  DeleteEventSourceMappingCommand,
} from "@aws-sdk/client-lambda";

import {
  PutObjectCommand,
  CreateBucketCommand,
  DeleteBucketCommand,
  paginateListObjectsV2,
  DeleteObjectCommand,
  GetObjectCommand,
  ListObjectsV2Command,
```

```
} from "@aws-sdk/client-s3";

import {
  CreatePipelineCommand,
  DeletePipelineCommand,
  DescribePipelineExecutionCommand,
  PipelineExecutionStatus,
  StartPipelineExecutionCommand,
} from "@aws-sdk/client-sagemaker";

import { VectorEnrichmentJobDocumentType } from "@aws-sdk/client-sagemaker-
geospatial";

import {
  CreateQueueCommand,
  DeleteQueueCommand,
  GetQueueAttributesCommand,
} from "@aws-sdk/client-sqs";

import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { retry, wait } from "@aws-sdk-examples/libs/utils/util-timers.js";

/**
 * Create the AWS IAM role that will be assumed by AWS Lambda.
 * @param {{ name: string, iamClient: import('@aws-sdk/client-iam').IAMClient }}
 props
 */
export async function createLambdaExecutionRole({ name, iamClient }) {
  const { Role } = await iamClient.send(
    new CreateRoleCommand({
      RoleName: name,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Action: ["sts:AssumeRole"],
            Principal: { Service: ["lambda.amazonaws.com"] },
          },
        ],
      }),
    }),
  );
```

```
  return {
    arn: Role.Arn,
    cleanUp: async () => {
      await iamClient.send(new DeleteRoleCommand({ RoleName: name }));
    },
  };
}

/**
 * Create an AWS IAM policy that will be attached to the AWS IAM role assumed by
 the AWS Lambda function.
 * The policy grants permission to work with Amazon SQS, Amazon CloudWatch, and
 Amazon SageMaker.
 * @param {{name: string, iamClient: import('@aws-sdk/client-iam').IAMClient,
 pipelineExecutionRoleArn: string}} props
 */
export async function createLambdaExecutionPolicy({
  name,
  iamClient,
  pipelineExecutionRoleArn,
}) {
  const policy = {
    Version: "2012-10-17",
    Statement: [
      {
        Effect: "Allow",
        Action: [
          "sqs:ReceiveMessage",
          "sqs:DeleteMessage",
          "sqs:GetQueueAttributes",
          "logs:CreateLogGroup",
          "logs:CreateLogStream",
          "logs:PutLogEvents",
          "sagemaker-geospatial:StartVectorEnrichmentJob",
          "sagemaker-geospatial:GetVectorEnrichmentJob",
          "sagemaker:SendPipelineExecutionStepFailure",
          "sagemaker:SendPipelineExecutionStepSuccess",
          "sagemaker-geospatial:ExportVectorEnrichmentJob",
        ],
        Resource: "*",
      },
      {
        Effect: "Allow",
```

```
        // The AWS Lambda function needs permission to pass the pipeline
 execution role to
        // the StartVectorEnrichmentCommand. This restriction prevents an AWS
 Lambda function
        // from elevating privileges. For more information, see:
        // https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_use_passrole.html
        Action: ["iam:PassRole"],
        Resource: `${pipelineExecutionRoleArn}`,
        Condition: {
          StringEquals: {
            "iam:PassedToService": [
              "sagemaker.amazonaws.com",
              "sagemaker-geospatial.amazonaws.com",
            ],
          },
        },
      },
    ],
  };

  const createPolicyCommand = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify(policy),
    PolicyName: name,
  });

  const { Policy } = await iamClient.send(createPolicyCommand);
  return {
    arn: Policy.Arn,
    policy,
    cleanUp: async () => {
      await iamClient.send(new DeletePolicyCommand({ PolicyArn: Policy.Arn }));
    },
  };
}

/**
 * Attach an AWS IAM policy to an AWS IAM role.
 * @param {{roleName: string, policyArn: string, iamClient: import('@aws-sdk/
client-iam').IAMClient}} props
 */
export async function attachPolicy({ roleName, policyArn, iamClient }) {
  const attachPolicyCommand = new AttachRolePolicyCommand({
    RoleName: roleName,
```

```
    PolicyArn: policyArn,
  });

  await iamClient.send(attachPolicyCommand);
  return {
    cleanUp: async () => {
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: roleName,
          PolicyArn: policyArn,
        }),
      );
    },
  };
}

/**
 * Create an AWS Lambda layer that contains the Amazon SageMaker and Amazon
 SageMaker Geospatial clients
 * in the runtime. The default runtime supports v3.188.0 of the JavaScript SDK.
 The Amazon SageMaker
 * Geospatial client wasn't introduced until v3.221.0.
 * @param {{ name: string, lambdaClient: import('@aws-sdk/client-
lambda').LambdaClient }} props
 */
export async function createLambdaLayer({ name, lambdaClient }) {
  const layerPath = `${dirnameFromMetaUrl(import.meta.url)}lambda/nodejs.zip`;
  const { LayerVersionArn, Version } = await lambdaClient.send(
    new PublishLayerVersionCommand({
      LayerName: name,
      Content: {
        ZipFile: Uint8Array.from(readFileSync(layerPath)),
      },
    }),
  );

  return {
    versionArn: LayerVersionArn,
    version: Version,
    cleanUp: async () => {
      await lambdaClient.send(
        new DeleteLayerVersionCommand({
          LayerName: name,
          VersionNumber: Version,
```

```
        }),
      );
    },
  };
}

/**
 * Deploy the AWS Lambda function that will be used to respond to Amazon
 SageMaker pipeline
 * execution steps.
 * @param {{roleArn: string, name: string, lambdaClient: import('@aws-sdk/client-
lambda').LambdaClient, layerVersionArn: string}} props
 */
export async function createLambdaFunction({
  name,
  roleArn,
  lambdaClient,
  layerVersionArn,
}) {
  const lambdaPath = `${dirnameFromMetaUrl(
    import.meta.url,
  )}lambda/dist/index.mjs.zip`;

  const command = new CreateFunctionCommand({
    Code: {
      ZipFile: Uint8Array.from(readFileSync(lambdaPath)),
    },
    Runtime: Runtime.nodejs18x,
    Handler: "index.handler",
    Layers: [layerVersionArn],
    FunctionName: name,
    Role: roleArn,
  });

  // Function creation fails if the Role is not ready. This retries
  // function creation until it succeeds or it times out.
  const { FunctionArn } = await retry(
    { intervalInMs: 1000, maxRetries: 60 },
    () => lambdaClient.send(command),
  );

  return {
    arn: FunctionArn,
    cleanUp: async () => {
```

```
      await lambdaClient.send(
        new DeleteFunctionCommand({ FunctionName: name }),
      );
    },
  };
}

/**
 * This uploads some sample coordinate data to an Amazon S3 bucket.
 * The Amazon SageMaker Geospatial vector enrichment job will take the simple
 Lat/Long
 * coordinates in this file and augment them with more detailed location data.
 * @param {{bucketName: string, s3Client: import('@aws-sdk/client-s3').S3Client}}
 props
 */
export async function uploadCSVDataToS3({ bucketName, s3Client }) {
  const s3Path = `${dirnameFromMetaUrl(
    import.meta.url,
  )}../../../../../workflows/sagemaker_pipelines/resources/latlongtest.csv`;

  await s3Client.send(
    new PutObjectCommand({
      Bucket: bucketName,
      Key: "input/sample_data.csv",
      Body: readFileSync(s3Path),
    }),
  );
}

/**
 * Create the AWS IAM role that will be assumed by the Amazon SageMaker pipeline.
 * @param {{name: string, iamClient: import('@aws-sdk/client-iam').IAMClient}}
 props
 */
export async function createSagemakerRole({ name, iamClient }) {
  const command = new CreateRoleCommand({
    RoleName: name,
    AssumeRolePolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: ["sts:AssumeRole"],
          Principal: {
```

```
            Service: [
              "sagemaker.amazonaws.com",
              "sagemaker-geospatial.amazonaws.com",
            ],
          },
        },
      ],
    }),
  });

  const { Role } = await iamClient.send(command);
  // Wait for the role to be ready.
  await wait(10);

  return {
    arn: Role.Arn,
    cleanUp: async () => {
      await iamClient.send(new DeleteRoleCommand({ RoleName: name }));
    },
  };
}

/**
 * Create the Amazon SageMaker execution policy. This policy grants permission to
 * invoke the AWS Lambda function, read/write to the Amazon S3 bucket, and send
 messages to
 * the Amazon SQS queue.
 * @param {{ name: string, sqsQueueArn: string, lambdaArn: string, iamClient:
 import('@aws-sdk/client-iam').IAMClient, s3BucketName: string}} props
 */
export async function createSagemakerExecutionPolicy({
  sqsQueueArn,
  lambdaArn,
  iamClient,
  name,
  s3BucketName,
}) {
  const policy = {
    Version: "2012-10-17",
    Statement: [
      {
        Effect: "Allow",
        Action: ["lambda:InvokeFunction"],
        Resource: lambdaArn,
```

```
      },
      {
        Effect: "Allow",
        Action: ["s3:*"],
        Resource: [
          `arn:aws:s3:::${s3BucketName}`,
          `arn:aws:s3:::${s3BucketName}/*`,
        ],
      },
      {
        Effect: "Allow",
        Action: ["sqs:SendMessage"],
        Resource: sqsQueueArn,
      },
    ],
  };

  const createPolicyCommand = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify(policy),
    PolicyName: name,
  });

  const { Policy } = await iamClient.send(createPolicyCommand);
  return {
    arn: Policy.Arn,
    policy,
    cleanUp: async () => {
      await iamClient.send(new DeletePolicyCommand({ PolicyArn: Policy.Arn }));
    },
  };
}

/**
 * Create the Amazon SageMaker pipeline using a JSON pipeline definition. The
 definition
 * can also be provided as an Amazon S3 object using
 PipelineDefinitionS3Location.
 * @param {{roleArn: string, name: string, sagemakerClient: import('@aws-sdk/
client-sagemaker').SageMakerClient}} props
 */
export async function createSagemakerPipeline({
  // Assumes an AWS IAM role has been created for this pipeline.
  roleArn,
  name,
```

```
  // Assumes an AWS Lambda function has been created for this pipeline.
  functionArn,
  sagemakerClient,
}) {
  const pipelineDefinition = readFileSync(
    // dirnameFromMetaUrl is a local utility function. You can find its
 implementation
    // on GitHub.
    `${dirnameFromMetaUrl(
      import.meta.url,
    )}../../../../../workflows/sagemaker_pipelines/resources/
GeoSpatialPipeline.json`,
  )
    .toString()
    .replace(/\*FUNCTION_ARN\*/g, functionArn);

  const { PipelineArn } = await sagemakerClient.send(
    new CreatePipelineCommand({
      PipelineName: name,
      PipelineDefinition: pipelineDefinition,
      RoleArn: roleArn,
    }),
  );

  return {
    arn: PipelineArn,
    cleanUp: async () => {
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
    },
  };
}

/**
 * Create an Amazon SQS queue. The Amazon SageMaker pipeline will send messages
 * to this queue that are then processed by the AWS Lambda function.
 * @param {{name: string, sqsClient: import('@aws-sdk/client-sqs').SQSClient}}
 props
 */
export async function createSQSQueue({ name, sqsClient }) {
  const { QueueUrl } = await sqsClient.send(
    new CreateQueueCommand({
      QueueName: name,
```

```
      Attributes: {
        DelaySeconds: "5",
        ReceiveMessageWaitTimeSeconds: "5",
        VisibilityTimeout: "300",
      },
    }),
  );

  const { Attributes } = await sqsClient.send(
    new GetQueueAttributesCommand({
      QueueUrl,
      AttributeNames: ["QueueArn"],
    }),
  );

  return {
    queueUrl: QueueUrl,
    queueArn: Attributes.QueueArn,
    cleanUp: async () => {
      await sqsClient.send(new DeleteQueueCommand({ QueueUrl }));
    },
  };
}

/**
 * Configure the AWS Lambda function to long poll for messages from the Amazon
 SQS
 * queue.
 * @param {{lambdaName: string, queueArn: string, lambdaClient: import('@aws-
sdk/client-lambda').LambdaClient, sqsClient: import('@aws-sdk/client-
sqs').SQSClient}} props
 */
export async function configureLambdaSQSEventSource({
  lambdaName,
  queueArn,
  lambdaClient,
}) {
  const { UUID } = await lambdaClient.send(
    new CreateEventSourceMappingCommand({
      EventSourceArn: queueArn,
      FunctionName: lambdaName,
    }),
  );
```

```
  return {
    cleanUp: async () => {
      await lambdaClient.send(
        new DeleteEventSourceMappingCommand({
          UUID,
        }),
      );
    },
  };
}

/**
 * Create an Amazon S3 bucket that will store the simple coordinate file as input
 * and the output of the Amazon SageMaker Geospatial vector enrichment job.
 * @param {{s3Client: import('@aws-sdk/client-s3').S3Client, name: string}} props
 */
export async function createS3Bucket({ name, s3Client }) {
  await s3Client.send(new CreateBucketCommand({ Bucket: name }));

  return {
    cleanUp: async () => {
      const paginator = paginateListObjectsV2(
        { client: s3Client },
        { Bucket: name },
      );
      for await (const page of paginator) {
        const objects = page.Contents;
        if (objects) {
          for (const object of objects) {
            await s3Client.send(
              new DeleteObjectCommand({ Bucket: name, Key: object.Key }),
            );
          }
        }
      }
      await s3Client.send(new DeleteBucketCommand({ Bucket: name }));
    },
  };
}

/**
 * Start the execution of the Amazon SageMaker pipeline. Parameters that are
 * passed in are used in the AWS Lambda function.
 * @param {{
```

```
 *   name: string,
 *   sagemakerClient: import('@aws-sdk/client-sagemaker').SageMakerClient,
 *   roleArn: string,
 *   queueUrl: string,
 *   s3InputBucketName: string,
 * }} props
 */
export async function startPipelineExecution({
  sagemakerClient,
  name,
  bucketName,
  roleArn,
  queueUrl,
}) {
  /**
   * The Vector Enrichment Job requests CSV data. This configuration points to a
 CSV
   * file in an Amazon S3 bucket.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobInputConfig}
   */
  const inputConfig = {
    DataSourceConfig: {
      S3Data: {
        S3Uri: `s3://${bucketName}/input/sample_data.csv`,
      },
    },
    DocumentType: VectorEnrichmentJobDocumentType.CSV,
  };

  /**
   * The Vector Enrichment Job adds additional data to the source CSV. This
 configuration points
   * to an Amazon S3 prefix where the output will be stored.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").ExportVectorEnrichmentJobOutputConfig}
   */
  const outputConfig = {
    S3Data: {
      S3Uri: `s3://${bucketName}/output/`,
    },
  };

  /**
```

```
   * This job will be a Reverse Geocoding Vector Enrichment Job. Reverse
 Geocoding requires
   * latitude and longitude values.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobConfig}
   */
  const jobConfig = {
    ReverseGeocodingConfig: {
      XAttributeName: "Longitude",
      YAttributeName: "Latitude",
    },
  };

  const { PipelineExecutionArn } = await sagemakerClient.send(
    new StartPipelineExecutionCommand({
      PipelineName: name,
      PipelineExecutionDisplayName: `${name}-example-execution`,
      PipelineParameters: [
        { Name: "parameter_execution_role", Value: roleArn },
        { Name: "parameter_queue_url", Value: queueUrl },
        {
          Name: "parameter_vej_input_config",
          Value: JSON.stringify(inputConfig),
        },
        {
          Name: "parameter_vej_export_config",
          Value: JSON.stringify(outputConfig),
        },
        {
          Name: "parameter_step_1_vej_config",
          Value: JSON.stringify(jobConfig),
        },
      ],
    }),
  );

  return {
    arn: PipelineExecutionArn,
  };
}

/**
 * Poll the executing pipeline until the status is 'SUCCEEDED', 'STOPPED', or
 'FAILED'.
```

```
 * @param {{ arn: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function waitForPipelineComplete({ arn, sagemakerClient }) {
  const command = new DescribePipelineExecutionCommand({
    PipelineExecutionArn: arn,
  });

  let complete = false;
  let intervalInSeconds = 15;
  const COMPLETION_STATUSES = [
    PipelineExecutionStatus.FAILED,
    PipelineExecutionStatus.STOPPED,
    PipelineExecutionStatus.SUCCEEDED,
  ];

  do {
    const { PipelineExecutionStatus: status, FailureReason } =
      await sagemakerClient.send(command);

    complete = COMPLETION_STATUSES.includes(status);

    if (!complete) {
      console.log(
        `Pipeline is ${status}. Waiting ${intervalInSeconds} seconds before
 checking again.`,
      );
      await wait(intervalInSeconds);
    } else if (status === PipelineExecutionStatus.FAILED) {
      throw new Error(`Pipeline failed because: ${FailureReason}`);
    } else if (status === PipelineExecutionStatus.STOPPED) {
      throw new Error(`Pipeline was forcefully stopped.`);
    } else {
      console.log(`Pipeline execution ${status}.`);
    }
  } while (!complete);
}

/**
 * Return the string value of an Amazon S3 object.
 * @param {{ bucket: string, key: string, s3Client: import('@aws-sdk/client-
s3').S3Client}} param0
 */
export async function getObject({ bucket, s3Client }) {
```

```
  const prefix = "output/";
  const { Contents } = await s3Client.send(
    new ListObjectsV2Command({ MaxKeys: 1, Bucket: bucket, Prefix: prefix }),
  );

  if (!Contents.length) {
    throw new Error("No objects found in bucket.");
  }

  // Find the CSV file.
  const outputObject = Contents.find((obj) => obj.Key.endsWith(".csv"));

  if (!outputObject) {
    throw new Error(`No CSV file found in bucket with the prefix "${prefix}".`);
  }

  const { Body } = await s3Client.send(
    new GetObjectCommand({
      Bucket: bucket,
      Key: outputObject.Key,
    }),
  );

  return Body.transformToString();
}
```

Essa função é um trecho de um arquivo que usa as funções anteriores da biblioteca para configurar um SageMaker pipeline, executá-lo e excluir todos os recursos criados.

```
import { retry, wait } from "@aws-sdk-examples/libs/utils/util-timers.js";
import {
  attachPolicy,
  configureLambdaSQSEventSource,
  createLambdaExecutionPolicy,
  createLambdaExecutionRole,
  createLambdaFunction,
  createLambdaLayer,
  createS3Bucket,
  createSQSQueue,
  createSagemakerExecutionPolicy,
  createSagemakerPipeline,
  createSagemakerRole,
```

```
  getObject,
  startPipelineExecution,
  uploadCSVDataToS3,
  waitForPipelineComplete,
} from "./lib.js";
import { MESSAGES } from "./messages.js";

export class SageMakerPipelinesWkflw {
  names = {
    LAMBDA_EXECUTION_ROLE: "sagemaker-wkflw-lambda-execution-role",
    LAMBDA_EXECUTION_ROLE_POLICY:
      "sagemaker-wkflw-lambda-execution-role-policy",
    LAMBDA_FUNCTION: "sagemaker-wkflw-lambda-function",
    LAMBDA_LAYER: "sagemaker-wkflw-lambda-layer",
    SAGE_MAKER_EXECUTION_ROLE: "sagemaker-wkflw-pipeline-execution-role",
    SAGE_MAKER_EXECUTION_ROLE_POLICY:
      "sagemaker-wkflw-pipeline-execution-role-policy",
    SAGE_MAKER_PIPELINE: "sagemaker-wkflw-pipeline",
    SQS_QUEUE: "sagemaker-wkflw-sqs-queue",
    S3_BUCKET: `sagemaker-wkflw-s3-bucket-${Date.now()}`,
  };

  cleanUpFunctions = [];

  /**
   * @param {import("@aws-sdk-examples/libs/prompter.js").Prompter} prompter
   * @param {import("@aws-sdk-examples/libs/logger.js").Logger} logger
   * @param {{ IAM: import("@aws-sdk/client-iam").IAMClient, Lambda:
 import("@aws-sdk/client-lambda").LambdaClient, SageMaker: import("@aws-sdk/
client-sagemaker").SageMakerClient, S3: import("@aws-sdk/client-s3").S3Client,
 SQS: import("@aws-sdk/client-sqs").SQSClient }} clients
   */
  constructor(prompter, logger, clients) {
    this.prompter = prompter;
    this.logger = logger;
    this.clients = clients;
  }

  async run() {
    try {
      await this.startWorkflow();
    } catch (err) {
      console.error(err);
      throw err;
```

```
    } finally {
      // Run all of the clean up functions. If any fail, we log the error and
continue.
      // This ensures all clean up functions are run.
      this.logger.logSeparator();
      const doCleanUp = await this.prompter.confirm({
        message: "Clean up resources?",
      });
      if (doCleanUp) {
        for (let i = this.cleanUpFunctions.length - 1; i >= 0; i--) {
          await retry(
            { intervalInMs: 1000, maxRetries: 60, swallowError: true },
            this.cleanUpFunctions[i],
          );
        }
      }
    }
  }

  async startWorkflow() {
    this.logger.logSeparator(MESSAGES.greetingHeader);
    await this.logger.log(MESSAGES.greeting);

    this.logger.logSeparator();
    await this.logger.log(
      MESSAGES.creatingRole.replace(
        "${ROLE_NAME}",
        this.names.LAMBDA_EXECUTION_ROLE,
      ),
    );

    // Create an IAM role that will be assumed by the AWS Lambda function. This
function
    // is triggered by Amazon SQS messages and calls SageMaker and SageMaker
GeoSpatial actions.
    const { arn: lambdaExecutionRoleArn, cleanUp: lambdaExecutionRoleCleanUp } =
      await createLambdaExecutionRole({
        name: this.names.LAMBDA_EXECUTION_ROLE,
        iamClient: this.clients.IAM,
      });
    // Add a clean up step to a stack for every resource created.
    this.cleanUpFunctions.push(lambdaExecutionRoleCleanUp);

    await this.logger.log(
```

```
      MESSAGES.roleCreated.replace(
        "${ROLE_NAME}",
        this.names.LAMBDA_EXECUTION_ROLE,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingRole.replace(
        "${ROLE_NAME}",
        this.names.SAGE_MAKER_EXECUTION_ROLE,
      ),
    );

    // Create an IAM role that will be assumed by the SageMaker pipeline. The
pipeline
    // sends messages to an Amazon SQS queue and puts/retrieves Amazon S3
objects.
    const {
      arn: pipelineExecutionRoleArn,
      cleanUp: pipelineExecutionRoleCleanUp,
    } = await createSagemakerRole({
      iamClient: this.clients.IAM,
      name: this.names.SAGE_MAKER_EXECUTION_ROLE,
    });
    this.cleanUpFunctions.push(pipelineExecutionRoleCleanUp);

    await this.logger.log(
      MESSAGES.roleCreated.replace(
        "${ROLE_NAME}",
        this.names.SAGE_MAKER_EXECUTION_ROLE,
      ),
    );

    this.logger.logSeparator();

    // Create an IAM policy that allows the AWS Lambda function to invoke
SageMaker APIs.
    const {
      arn: lambdaExecutionPolicyArn,
      policy: lambdaPolicy,
      cleanUp: lambdaExecutionPolicyCleanUp,
    } = await createLambdaExecutionPolicy({
```

```
      name: this.names.LAMBDA_EXECUTION_ROLE_POLICY,
      s3BucketName: this.names.S3_BUCKET,
      iamClient: this.clients.IAM,
      pipelineExecutionRoleArn,
    });
    this.cleanUpFunctions.push(lambdaExecutionPolicyCleanUp);

    console.log(JSON.stringify(lambdaPolicy, null, 2), "\n");

    await this.logger.log(
      MESSAGES.attachPolicy
        .replace("${POLICY_NAME}", this.names.LAMBDA_EXECUTION_ROLE_POLICY)
        .replace("${ROLE_NAME}", this.names.LAMBDA_EXECUTION_ROLE),
    );

    await this.prompter.checkContinue();

    // Attach the Lambda execution policy to the execution role.
    const { cleanUp: lambdaExecutionRolePolicyCleanUp } = await attachPolicy({
      roleName: this.names.LAMBDA_EXECUTION_ROLE,
      policyArn: lambdaExecutionPolicyArn,
      iamClient: this.clients.IAM,
    });
    this.cleanUpFunctions.push(lambdaExecutionRolePolicyCleanUp);

    await this.logger.log(MESSAGES.policyAttached);

    this.logger.logSeparator();

    // Create Lambda layer for SageMaker packages.
    const { versionArn: layerVersionArn, cleanUp: lambdaLayerCleanUp } =
      await createLambdaLayer({
        name: this.names.LAMBDA_LAYER,
        lambdaClient: this.clients.Lambda,
      });
    this.cleanUpFunctions.push(lambdaLayerCleanUp);

    await this.logger.log(
      MESSAGES.creatingFunction.replace(
        "${FUNCTION_NAME}",
        this.names.LAMBDA_FUNCTION,
      ),
    );
```

```
    // Create the Lambda function with the execution role.
    const { arn: lambdaArn, cleanUp: lambdaCleanUp } =
      await createLambdaFunction({
        roleArn: lambdaExecutionRoleArn,
        lambdaClient: this.clients.Lambda,
        name: this.names.LAMBDA_FUNCTION,
        layerVersionArn,
      });
    this.cleanUpFunctions.push(lambdaCleanUp);

    await this.logger.log(
      MESSAGES.functionCreated.replace(
        "${FUNCTION_NAME}",
        this.names.LAMBDA_FUNCTION,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingSQSQueue.replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    // Create an SQS queue for the SageMaker pipeline.
    const {
      queueUrl,
      queueArn,
      cleanUp: queueCleanUp,
    } = await createSQSQueue({
      name: this.names.SQS_QUEUE,
      sqsClient: this.clients.SQS,
    });
    this.cleanUpFunctions.push(queueCleanUp);

    await this.logger.log(
      MESSAGES.sqsQueueCreated.replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.configuringLambdaSQSEventSource
        .replace("${LAMBDA_NAME}", this.names.LAMBDA_FUNCTION)
        .replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
```

```
    );

    // Configure the SQS queue as an event source for the Lambda.
    const { cleanUp: lambdaSQSEventSourceCleanUp } =
      await configureLambdaSQSEventSource({
        lambdaArn,
        lambdaName: this.names.LAMBDA_FUNCTION,
        queueArn,
        sqsClient: this.clients.SQS,
        lambdaClient: this.clients.Lambda,
      });
    this.cleanUpFunctions.push(lambdaSQSEventSourceCleanUp);

    await this.logger.log(
      MESSAGES.lambdaSQSEventSourceConfigured
        .replace("${LAMBDA_NAME}", this.names.LAMBDA_FUNCTION)
        .replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    this.logger.logSeparator();

    // Create an IAM policy that allows the SageMaker pipeline to invoke AWS
  Lambda
    // and send messages to the Amazon SQS queue.
    const {
      arn: pipelineExecutionPolicyArn,
      policy: sagemakerPolicy,
      cleanUp: pipelineExecutionPolicyCleanUp,
    } = await createSagemakerExecutionPolicy({
      sqsQueueArn: queueArn,
      lambdaArn,
      iamClient: this.clients.IAM,
      name: this.names.SAGE_MAKER_EXECUTION_ROLE_POLICY,
      s3BucketName: this.names.S3_BUCKET,
    });
    this.cleanUpFunctions.push(pipelineExecutionPolicyCleanUp);

    console.log(JSON.stringify(sagemakerPolicy, null, 2));

    await this.logger.log(
      MESSAGES.attachPolicy
        .replace("${POLICY_NAME}", this.names.SAGE_MAKER_EXECUTION_ROLE_POLICY)
        .replace("${ROLE_NAME}", this.names.SAGE_MAKER_EXECUTION_ROLE),
    );
```

```
    await this.prompter.checkContinue();

    // Attach the SageMaker execution policy to the execution role.
    const { cleanUp: pipelineExecutionRolePolicyCleanUp } = await attachPolicy({
      roleName: this.names.SAGE_MAKER_EXECUTION_ROLE,
      policyArn: pipelineExecutionPolicyArn,
      iamClient: this.clients.IAM,
    });
    this.cleanUpFunctions.push(pipelineExecutionRolePolicyCleanUp);
    // Wait for the role to be ready. If the role is used immediately,
    // the pipeline will fail.
    await wait(5);

    await this.logger.log(MESSAGES.policyAttached);

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingPipeline.replace(
        "${PIPELINE_NAME}",
        this.names.SAGE_MAKER_PIPELINE,
      ),
    );

    // Create the SageMaker pipeline.
    const { cleanUp: pipelineCleanUp } = await createSagemakerPipeline({
      roleArn: pipelineExecutionRoleArn,
      functionArn: lambdaArn,
      sagemakerClient: this.clients.SageMaker,
      name: this.names.SAGE_MAKER_PIPELINE,
    });
    this.cleanUpFunctions.push(pipelineCleanUp);

    await this.logger.log(
      MESSAGES.pipelineCreated.replace(
        "${PIPELINE_NAME}",
        this.names.SAGE_MAKER_PIPELINE,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
```

```
      MESSAGES.creatingS3Bucket.replace("${BUCKET_NAME}", this.names.S3_BUCKET),
    );

    // Create an S3 bucket for storing inputs and outputs.
    const { cleanUp: s3BucketCleanUp } = await createS3Bucket({
      name: this.names.S3_BUCKET,
      s3Client: this.clients.S3,
    });
    this.cleanUpFunctions.push(s3BucketCleanUp);

    await this.logger.log(
      MESSAGES.s3BucketCreated.replace("${BUCKET_NAME}", this.names.S3_BUCKET),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.uploadingInputData.replace(
        "${BUCKET_NAME}",
        this.names.S3_BUCKET,
      ),
    );

    // Upload CSV Lat/Long data to S3.
    await uploadCSVDataToS3({
      bucketName: this.names.S3_BUCKET,
      s3Client: this.clients.S3,
    });

    await this.logger.log(MESSAGES.inputDataUploaded);

    this.logger.logSeparator();

    await this.prompter.checkContinue(MESSAGES.executePipeline);

    // Execute the SageMaker pipeline.
    const { arn: pipelineExecutionArn } = await startPipelineExecution({
      name: this.names.SAGE_MAKER_PIPELINE,
      sagemakerClient: this.clients.SageMaker,
      roleArn: pipelineExecutionRoleArn,
      bucketName: this.names.S3_BUCKET,
      queueUrl,
    });
```

```
    // Wait for the pipeline execution to finish.
    await waitForPipelineComplete({
      arn: pipelineExecutionArn,
      sagemakerClient: this.clients.SageMaker,
    });

    this.logger.logSeparator();

    await this.logger.log(MESSAGES.outputDelay);

    // The getOutput function will throw an error if the output is not
    // found. The retry function will retry a failed function call once
    // ever 10 seconds for 2 minutes.
    const output = await retry({ intervalInMs: 10000, maxRetries: 12 }, () =>
      getObject({
        bucket: this.names.S3_BUCKET,
        s3Client: this.clients.S3,
      }),
    );

    this.logger.logSeparator();
    await this.logger.log(MESSAGES.outputDataRetrieved);
    console.log(output.split("\n").slice(0, 6).join("\n"));
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
val DASHES = String(CharArray(80)).replace("\u0000", "-")
private var eventSourceMapping = ""

suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
          <sageMakerRoleName> <lambdaRoleName> <functionName> <functionKey>
 <queueName> <bucketName> <bucketFunction> <lnglatData> <spatialPipelinePath>
 <pipelineName>

    Where:
        sageMakerRoleName - The name of the Amazon SageMaker role.
        lambdaRoleName - The name of the AWS Lambda role.
        functionName - The name of the AWS Lambda function (for
 example,SageMakerExampleFunction).
        functionKey - The name of the Amazon S3 key name that represents the
 Lambda function (for example, SageMakerLambda.zip).
        queueName - The name of the Amazon Simple Queue Service (Amazon SQS)
 queue.
        bucketName - The name of the Amazon Simple Storage Service (Amazon S3)
 bucket.
        bucketFunction - The name of the Amazon S3 bucket that contains the
 Lambda ZIP file.
        lnglatData - The file location of the latlongtest.csv file required for
 this use case.
        spatialPipelinePath - The file location of the GeoSpatialPipeline.json
 file required for this use case.
        pipelineName - The name of the pipeline to create (for example,
 sagemaker-sdk-example-pipeline).
    """

    if (args.size != 10) {
```

```
        println(usage)
        exitProcess(1)
    }

    val sageMakerRoleName = args[0]
    val lambdaRoleName = args[1]
    val functionKey = args[2]
    val functionName = args[3]
    val queueName = args[4]
    val bucketName = args[5]
    val bucketFunction = args[6]
    val lnglatData = args[7]
    val spatialPipelinePath = args[8]
    val pipelineName = args[9]
    val handlerName = "org.example.SageMakerLambdaFunction::handleRequest"

    println(DASHES)
    println("Welcome to the Amazon SageMaker pipeline example scenario.")
    println(
        """
         This example workflow will guide you through setting up and running an
         Amazon SageMaker pipeline. The pipeline uses an AWS Lambda function and
an
         Amazon SQS Queue. It runs a vector enrichment reverse geocode job to
         reverse geocode addresses in an input file and store the results in an
export file.
        """.trimIndent()
    )
    println(DASHES)

    println(DASHES)
    println("First, we will set up the roles, functions, and queue needed by the
SageMaker pipeline.")
    val lambdaRoleArn: String = checkLambdaRole(lambdaRoleName)
    val sageMakerRoleArn: String = checkSageMakerRole(sageMakerRoleName)
    val functionArn = checkFunction(functionName, bucketFunction, functionKey,
handlerName, lambdaRoleArn)
    val queueUrl = checkQueue(queueName, functionName)
    println(DASHES)

    println(DASHES)
    println("Setting up bucket $bucketName")
    if (!checkBucket(bucketName)) {
        setupBucket(bucketName)
```

```
        println("Put $lnglatData into $bucketName")
        val objectKey = "samplefiles/latlongtest.csv"
        putS3Object(bucketName, objectKey, lnglatData)
    }
    println(DASHES)

    println(DASHES)
    println("Now we can create and run our pipeline.")
    setupPipeline(spatialPipelinePath, sageMakerRoleArn, functionArn,
 pipelineName)
    val pipelineExecutionARN = executePipeline(bucketName, queueUrl,
 sageMakerRoleArn, pipelineName)
    println("The pipeline execution ARN value is $pipelineExecutionARN")
    waitForPipelineExecution(pipelineExecutionARN)
    println("Wait 30 secs to get output results $bucketName")
    TimeUnit.SECONDS.sleep(30)
    getOutputResults(bucketName)
    println(DASHES)

    println(DASHES)
    println(
        """
             The pipeline has completed. To view the pipeline and runs in
 SageMaker Studio, follow these instructions:
             https://docs.aws.amazon.com/sagemaker/latest/dg/pipelines-
studio.html
        """.trimIndent()
    )
    println(DASHES)

    println(DASHES)
    println("Do you want to delete the AWS resources used in this Workflow? (y/
n)")
    val `in` = Scanner(System.`in`)
    val delResources = `in`.nextLine()
    if (delResources.compareTo("y") == 0) {
        println("Lets clean up the AWS resources. Wait 30 seconds")
        TimeUnit.SECONDS.sleep(30)
        deleteEventSourceMapping(functionName)
        deleteSQSQueue(queueName)
        listBucketObjects(bucketName)
        deleteBucket(bucketName)
        delLambdaFunction(functionName)
        deleteLambdaRole(lambdaRoleName)
```

```
        deleteSagemakerRole(sageMakerRoleName)
        deletePipeline(pipelineName)
    } else {
        println("The AWS Resources were not deleted!")
    }
    println(DASHES)

    println(DASHES)
    println("SageMaker pipeline scenario is complete.")
    println(DASHES)
}

// Delete a SageMaker pipeline by name.
suspend fun deletePipeline(pipelineNameVal: String) {
    val pipelineRequest = DeletePipelineRequest {
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        sageMakerClient.deletePipeline(pipelineRequest)
        println("*** Successfully deleted $pipelineNameVal")
    }
}

suspend fun deleteSagemakerRole(roleNameVal: String) {
    val sageMakerRolePolicies = getSageMakerRolePolicies()
    IamClient { region = "us-west-2" }.use { iam ->
        for (policy in sageMakerRolePolicies) {
            // First the policy needs to be detached.
            val rolePolicyRequest = DetachRolePolicyRequest {
                policyArn = policy
                roleName = roleNameVal
            }
            iam.detachRolePolicy(rolePolicyRequest)
        }

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
            roleName = roleNameVal
        }
        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}
```

```
suspend fun deleteLambdaRole(roleNameVal: String) {
    val lambdaRolePolicies = getLambdaRolePolicies()
    IamClient { region = "us-west-2" }.use { iam ->
        for (policy in lambdaRolePolicies) {
            // First the policy needs to be detached.
            val rolePolicyRequest = DetachRolePolicyRequest {
                policyArn = policy
                roleName = roleNameVal
            }
            iam.detachRolePolicy(rolePolicyRequest)
        }

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
            roleName = roleNameVal
        }
        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}

suspend fun delLambdaFunction(myFunctionName: String) {
    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}

suspend fun deleteBucket(bucketName: String?) {
    val request = DeleteBucketRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucket(request)
        println("The $bucketName was successfully deleted!")
    }
}

suspend fun deleteBucketObjects(bucketName: String, objectName: String?) {
```

```
    val toDelete = ArrayList<ObjectIdentifier>()
    val obId = ObjectIdentifier {
        key = objectName
    }
    toDelete.add(obId)
    val delOb = Delete {
        objects = toDelete
    }
    val dor = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.deleteObjects(dor)
        println("*** $bucketName objects were deleted.")
    }
}

suspend fun listBucketObjects(bucketNameVal: String) {
    val listObjects = ListObjectsRequest {
        bucket = bucketNameVal
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        val res = s3Client.listObjects(listObjects)
        val objects = res.contents
        if (objects != null) {
            for (myValue in objects) {
                println("The name of the key is ${myValue.key}")
                deleteBucketObjects(bucketNameVal, myValue.key)
            }
        }
    }
}

// Delete the specific Amazon SQS queue.
suspend fun deleteSQSQueue(queueNameVal: String?) {
    val getQueueRequest = GetQueueUrlRequest {
        queueName = queueNameVal
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        val urlVal = sqsClient.getQueueUrl(getQueueRequest).queueUrl
```

```
        val deleteQueueRequest = DeleteQueueRequest {
            queueUrl = urlVal
        }
        sqsClient.deleteQueue(deleteQueueRequest)
    }
}

// Delete the queue event mapping.
suspend fun deleteEventSourceMapping(functionNameVal: String) {
    if (eventSourceMapping.compareTo("") == 0) {
        LambdaClient { region = "us-west-2" }.use { lambdaClient ->
            val request = ListEventSourceMappingsRequest {
                functionName = functionNameVal
            }
            val response = lambdaClient.listEventSourceMappings(request)
            val eventList = response.eventSourceMappings
            if (eventList != null) {
                for (event in eventList) {
                    eventSourceMapping = event.uuid.toString()
                }
            }
        }
    }

    val eventSourceMappingRequest = DeleteEventSourceMappingRequest {
        uuid = eventSourceMapping
    }
    LambdaClient { region = "us-west-2" }.use { lambdaClient ->
        lambdaClient.deleteEventSourceMapping(eventSourceMappingRequest)
        println("The event mapping is deleted!")
    }
}

// Reads the objects in the S3 bucket and displays the values.
private suspend fun readObject(bucketName: String, keyVal: String?) {
    println("Output file contents: \n")
    val objectRequest = GetObjectRequest {
        bucket = bucketName
        key = keyVal
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.getObject(objectRequest) { resp ->
            val byteArray = resp.body?.toByteArray()
            val text = byteArray?.let { String(it, StandardCharsets.UTF_8) }
```

```
            println("Text output: $text")
        }
    }
}

// Display the results from the output directory.
suspend fun getOutputResults(bucketName: String?) {
    println("Getting output results $bucketName.")
    val listObjectsRequest = ListObjectsRequest {
        bucket = bucketName
        prefix = "outputfiles/"
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        val response = s3Client.listObjects(listObjectsRequest)
        val s3Objects: List<Object>? = response.contents
        if (s3Objects != null) {
            for (`object` in s3Objects) {
                if (bucketName != null) {
                    readObject(bucketName, (`object`.key))
                }
            }
        }
    }
}

suspend fun waitForPipelineExecution(executionArn: String?) {
    var status: String
    var index = 0
    do {
        val pipelineExecutionRequest = DescribePipelineExecutionRequest {
            pipelineExecutionArn = executionArn
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            val response =
 sageMakerClient.describePipelineExecution(pipelineExecutionRequest)
            status = response.pipelineExecutionStatus.toString()
            println("$index. The status of the pipeline is $status")
            TimeUnit.SECONDS.sleep(4)
            index++
        }
    } while ("Executing" == status)
    println("Pipeline finished with status $status")
}
```

```
// Start a pipeline run with job configurations.
suspend fun executePipeline(bucketName: String, queueUrl: String?, roleArn:
 String?, pipelineNameVal: String): String? {
    println("Starting pipeline execution.")
    val inputBucketLocation = "s3://$bucketName/samplefiles/latlongtest.csv"
    val output = "s3://$bucketName/outputfiles/"

    val gson = GsonBuilder()
        .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
        .setPrettyPrinting()
        .create()

    // Set up all parameters required to start the pipeline.
    val parameters: MutableList<Parameter> = java.util.ArrayList<Parameter>()

    val para1 = Parameter {
        name = "parameter_execution_role"
        value = roleArn
    }
    val para2 = Parameter {
        name = "parameter_queue_url"
        value = queueUrl
    }

    val inputJSON = """{
        "DataSourceConfig": {
        "S3Data": {
            "S3Uri": "s3://$bucketName/samplefiles/latlongtest.csv"
        },
        "Type": "S3_DATA"
        },
        "DocumentType": "CSV"
    }"""
    println(inputJSON)
    val para3 = Parameter {
        name = "parameter_vej_input_config"
        value = inputJSON
    }

    // Create an ExportVectorEnrichmentJobOutputConfig object.
    val jobS3Data = VectorEnrichmentJobS3Data {
        s3Uri = output
    }
```

```
    val outputConfig = ExportVectorEnrichmentJobOutputConfig {
        s3Data = jobS3Data
    }

    val gson4: String = gson.toJson(outputConfig)
    val para4: Parameter = Parameter {
        name = "parameter_vej_export_config"
        value = gson4
    }
    println("parameter_vej_export_config:" + gson.toJson(outputConfig))

    val para5JSON =
        "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":{\"XAttributeName
\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}"

    val para5: Parameter = Parameter {
        name = "parameter_step_1_vej_config"
        value = para5JSON
    }

    parameters.add(para1)
    parameters.add(para2)
    parameters.add(para3)
    parameters.add(para4)
    parameters.add(para5)

    val pipelineExecutionRequest = StartPipelineExecutionRequest {
        pipelineExecutionDescription = "Created using Kotlin SDK"
        pipelineExecutionDisplayName = "$pipelineName-example-execution"
        pipelineParameters = parameters
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        val response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest)
        return response.pipelineExecutionArn
    }
}

// Create a pipeline from the example pipeline JSON.
suspend fun setupPipeline(filePath: String?, roleArnVal: String?, functionArnVal:
 String?, pipelineNameVal: String?) {
```

```
    println("Setting up the pipeline.")
    val parser = JSONParser()

    // Read JSON and get pipeline definition.
    FileReader(filePath).use { reader ->
        val obj: Any = parser.parse(reader)
        val jsonObject: JSONObject = obj as JSONObject
        val stepsArray: JSONArray = jsonObject.get("Steps") as JSONArray
        for (stepObj in stepsArray) {
            val step: JSONObject = stepObj as JSONObject
            if (step.containsKey("FunctionArn")) {
                step.put("FunctionArn", functionArnVal)
            }
        }
        println(jsonObject)

        // Create the pipeline.
        val pipelineRequest = CreatePipelineRequest {
            pipelineDescription = "Kotlin SDK example pipeline"
            roleArn = roleArnVal
            pipelineName = pipelineNameVal
            pipelineDefinition = jsonObject.toString()
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            sageMakerClient.createPipeline(pipelineRequest)
        }
    }
}

suspend fun putS3Object(bucketName: String, objectKey: String, objectPath:
 String) {
    val request = PutObjectRequest {
        bucket = bucketName
        key = objectKey
        body = File(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.putObject(request)
        println("Successfully placed $objectKey into bucket $bucketName")
    }
}
```

```
suspend fun setupBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}

suspend fun checkBucket(bucketName: String): Boolean {
    try {
        val headBucketRequest = HeadBucketRequest {
            bucket = bucketName
        }
        S3Client { region = "us-east-1" }.use { s3Client ->
            s3Client.headBucket(headBucketRequest)
            println("$bucketName exists")
            return true
        }
    } catch (e: S3Exception) {
        println("Bucket does not exist")
    }
    return false
}

// Connect the queue to the Lambda function as an event source.
suspend fun connectLambda(queueUrlVal: String?, lambdaNameVal: String?) {
    println("Connecting the Lambda function and queue for the pipeline.")
    var queueArn = ""

    // Specify the attributes to retrieve.
    val atts: MutableList<QueueAttributeName> = ArrayList()
    atts.add(QueueAttributeName.QueueArn)
    val attributesRequest = GetQueueAttributesRequest {
        queueUrl = queueUrlVal
        attributeNames = atts
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        val response = sqsClient.getQueueAttributes(attributesRequest)
        val queueAtts = response.attributes
        if (queueAtts != null) {
```

```
            for ((key, value) in queueAtts) {
                println("Key = $key, Value = $value")
                queueArn = value
            }
        }
    }
    val eventSourceMappingRequest = CreateEventSourceMappingRequest {
        eventSourceArn = queueArn
        functionName = lambdaNameVal
    }
    LambdaClient { region = "us-west-2" }.use { lambdaClient ->
        val response1 =
 lambdaClient.createEventSourceMapping(eventSourceMappingRequest)
        eventSourceMapping = response1.uuid.toString()
        println("The mapping between the event source and Lambda function was
 successful")
    }
}

// Set up the SQS queue to use with the pipeline.
suspend fun setupQueue(queueNameVal: String, lambdaNameVal: String): String {
    println("Setting up queue named $queueNameVal")
    val queueAtt: MutableMap<String, String> = HashMap()
    queueAtt.put("DelaySeconds", "5")
    queueAtt.put("ReceiveMessageWaitTimeSeconds", "5")
    queueAtt.put("VisibilityTimeout", "300")

    val createQueueRequest = CreateQueueRequest {
        queueName = queueNameVal
        attributes = queueAtt
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        sqsClient.createQueue(createQueueRequest)
        println("\nGet queue url")
        val getQueueUrlResponse = sqsClient.getQueueUrl(GetQueueUrlRequest
 { queueName = queueNameVal })
        TimeUnit.SECONDS.sleep(15)
        connectLambda(getQueueUrlResponse.queueUrl, lambdaNameVal)
        println("Queue ready with Url " + getQueueUrlResponse.queueUrl)
        return getQueueUrlResponse.queueUrl.toString()
    }
}
```

```
// Checks to see if the Amazon SQS queue exists. If not, this method creates a
 new queue
// and returns the ARN value.
suspend fun checkQueue(queueNameVal: String, lambdaNameVal: String): String? {
    println("Checking to see if the queue exists. If not, a new queue will be
 created for use in this workflow.")
    var queueUrl: String
    try {
        val request = GetQueueUrlRequest {
            queueName = queueNameVal
        }

        SqsClient { region = "us-west-2" }.use { sqsClient ->
            val response = sqsClient.getQueueUrl(request)
            queueUrl = response.queueUrl.toString()
            println(queueUrl)
        }
    } catch (e: SqsException) {
        println(e.message + " A new queue will be created")
        queueUrl = setupQueue(queueNameVal, lambdaNameVal)
    }
    return queueUrl
}

suspend fun createNewFunction(myFunctionName: String, s3BucketName: String,
 myS3Key: String, myHandler: String, myRole: String): String {
    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }

    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java11
        memorySize = 1024
        timeout = 200
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val functionResponse = awsLambda.createFunction(request)
```

```
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        println("${functionResponse.functionArn} was created")
        return functionResponse.functionArn.toString()
    }
}

suspend fun checkFunction(myFunctionName: String, s3BucketName: String, myS3Key:
 String, myHandler: String, myRole: String): String {
    println("Checking to see if the function exists. If not, a new AWS Lambda
 function will be created for use in this workflow.")
    var functionArn: String
    try {
        // Does this function already exist.
        val functionRequest = GetFunctionRequest {
            functionName = myFunctionName
        }
        LambdaClient { region = "us-west-2" }.use { lambdaClient ->
            val response = lambdaClient.getFunction(functionRequest)
            functionArn = response.configuration?.functionArn.toString()
            println("$functionArn exists")
        }
    } catch (e: LambdaException) {
        println(e.message + " A new function will be created")
        functionArn = createNewFunction(myFunctionName, s3BucketName, myS3Key,
 myHandler, myRole)
    }
    return functionArn
}

// Checks to see if the SageMaker role exists. If not, this method creates it.
suspend fun checkSageMakerRole(roleNameVal: String): String {
    println("Checking to see if the role exists. If not, a new role will be
 created for AWS SageMaker to use.")
    var roleArn: String
    try {
        val roleRequest = GetRoleRequest {
            roleName = roleNameVal
        }
        IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
            val response = iamClient.getRole(roleRequest)
            roleArn = response.role?.arn.toString()
            println(roleArn)
```

```
        }
    } catch (e: IamException) {
        println(e.message + " A new role will be created")
        roleArn = createSageMakerRole(roleNameVal)
    }
    return roleArn
}

suspend fun createSageMakerRole(roleNameVal: String): String {
    val sageMakerRolePolicies = getSageMakerRolePolicies()
    println("Creating a role to use with SageMaker.")
    val assumeRolePolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": [" +
        "\"sagemaker.amazonaws.com\"," +
        "\"sagemaker-geospatial.amazonaws.com\"," +
        "\"lambda.amazonaws.com\"," +
        "\"s3.amazonaws.com\"" +
        "]" +
        "}," +
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
        "}"

    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = assumeRolePolicy
        description = "Created using the AWS SDK for Kotlin"
    }
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val roleResult = iamClient.createRole(request)

        // Attach the policies to the role.
        for (policy in sageMakerRolePolicies) {
            val attachRequest = AttachRolePolicyRequest {
                roleName = roleNameVal
                policyArn = policy
            }
            iamClient.attachRolePolicy(attachRequest)
        }
```

```
        // Allow time for the role to be ready.
        TimeUnit.SECONDS.sleep(15)
        System.out.println("Role ready with ARN ${roleResult.role?.arn}")
        return roleResult.role?.arn.toString()
    }
}

// Checks to see if the Lambda role exists. If not, this method creates it.
suspend fun checkLambdaRole(roleNameVal: String): String {
    println("Checking to see if the role exists. If not, a new role will be
 created for AWS Lambda to use.")
    var roleArn: String
    val roleRequest = GetRoleRequest {
        roleName = roleNameVal
    }

    try {
        IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
            val response = iamClient.getRole(roleRequest)
            roleArn = response.role?.arn.toString()
            println(roleArn)
        }
    } catch (e: IamException) {
        println(e.message + " A new role will be created")
        roleArn = createLambdaRole(roleNameVal)
    }

    return roleArn
}

private suspend fun createLambdaRole(roleNameVal: String): String {
    val lambdaRolePolicies = getLambdaRolePolicies()
    val assumeRolePolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": [" +
        "\"sagemaker.amazonaws.com\"," +
        "\"sagemaker-geospatial.amazonaws.com\"," +
        "\"lambda.amazonaws.com\"," +
        "\"s3.amazonaws.com\"" +
        "]" +
        "}," +
```

```
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
        "}"

    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = assumeRolePolicy
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val roleResult = iamClient.createRole(request)

        // Attach the policies to the role.
        for (policy in lambdaRolePolicies) {
            val attachRequest = AttachRolePolicyRequest {
                roleName = roleNameVal
                policyArn = policy
            }
            iamClient.attachRolePolicy(attachRequest)
        }

        // Allow time for the role to be ready.
        TimeUnit.SECONDS.sleep(15)
        println("Role ready with ARN " + roleResult.role?.arn)
        return roleResult.role?.arn.toString()
    }
}

fun getLambdaRolePolicies(): Array<String?> {
    val lambdaRolePolicies = arrayOfNulls<String>(5)
    lambdaRolePolicies[0] = "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess"
    lambdaRolePolicies[1] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess"
    lambdaRolePolicies[2] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess"
    lambdaRolePolicies[3] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy"
    lambdaRolePolicies[4] = "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole"
    return lambdaRolePolicies
}

fun getSageMakerRolePolicies(): Array<String?> {
    val sageMakerRolePolicies = arrayOfNulls<String>(3)
```

```
    sageMakerRolePolicies[0] = "arn:aws:iam::aws:policy/
AmazonSageMakerFullAccess"
    sageMakerRolePolicies[1] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess"
    sageMakerRolePolicies[2] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess"
    return sageMakerRolePolicies
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Comece a usar SageMaker modelos e endpoints usando um SDK AWS

O código de exemplo a seguir mostra como:

- Comece um trabalho de treinamento e crie um SageMaker modelo.
- Criar uma configuração de endpoint
- Criar um endpoint e, em seguida, limpe os recursos.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_hyperparameters_w TYPE REF TO /aws1/cl_sgmhyperparameters_w.
```

```
    DATA lo_trn_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_trn_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_trn_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
    DATA lo_val_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_val_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_val_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
    DATA lo_algorithm_specification TYPE REF TO /aws1/cl_sgmalgorithmspec.
    DATA lo_resource_config  TYPE REF TO /aws1/cl_sgmresourceconfig.
    DATA lo_output_data_config TYPE REF TO  /aws1/cl_sgmoutputdataconfig.
    DATA lo_stopping_condition TYPE REF TO  /aws1/cl_sgmstoppingcondition.
    DATA lo_primarycontainer TYPE REF TO /aws1/cl_sgmcontainerdefn.
    DATA lo_production_variants TYPE REF TO /aws1/cl_sgmproductionvariant.
    DATA lo_ep_config_result TYPE REF TO /aws1/cl_sgmcreateendptcfgout.
    DATA lo_training_result TYPE REF TO /aws1/cl_sgmdescrtrnjobrsp.
    DATA lt_production_variants TYPE /aws1/
cl_sgmproductionvariant=>tt_productionvariantlist.
    DATA lt_input_data_config TYPE /aws1/cl_sgmchannel=>tt_inputdataconfig.
    DATA lt_hyperparameters TYPE /aws1/
cl_sgmhyperparameters_w=>tt_hyperparameters.
    DATA lv_model_data_url TYPE /aws1/sgmurl.

    lv_model_data_url = iv_s3_output_path && iv_training_job_name && '/output/
model.tar.gz'.

    "Create ABAP internal table for hyperparameters based on input variables."
    "These hyperparameters are based on Amazon SageMaker built-in algorithm -
 XGBoost"
    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_max_depth.
    INSERT VALUE #( key = 'max_depth' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eta.
    INSERT VALUE #( key = 'eta' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eval_metric.
    INSERT VALUE #( key = 'eval_metric' value = lo_hyperparameters_w )  INTO
 TABLE lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value =
 iv_hp_scale_pos_weight.
    INSERT VALUE #( key = 'scale_pos_weight' value = lo_hyperparameters_w )  INTO
 TABLE lt_hyperparameters.
```

```
   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_subsample.
   INSERT VALUE #( key = 'subsample' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_objective.
   INSERT VALUE #( key = 'objective' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_num_round.
   INSERT VALUE #( key = 'num_round' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   "Create ABAP internal table for data based on input variables."
   "Training data."
   CREATE OBJECT lo_trn_s3datasource
     EXPORTING
       iv_s3datatype             = iv_trn_data_s3datatype
       iv_s3datadistributiontype = iv_trn_data_s3datadistribution
       iv_s3uri                  = iv_trn_data_s3uri.

   CREATE OBJECT lo_trn_datasource EXPORTING io_s3datasource =
lo_trn_s3datasource.

   CREATE OBJECT lo_trn_channel
     EXPORTING
       iv_channelname     = 'train'
       io_datasource      = lo_trn_datasource
       iv_compressiontype = iv_trn_data_compressiontype
       iv_contenttype     = iv_trn_data_contenttype.
   INSERT lo_trn_channel INTO TABLE lt_input_data_config.

   "Validation data."
   CREATE OBJECT lo_val_s3datasource
     EXPORTING
       iv_s3datatype             = iv_val_data_s3datatype
       iv_s3datadistributiontype = iv_val_data_s3datadistribution
       iv_s3uri                  = iv_val_data_s3uri.

   CREATE OBJECT lo_val_datasource EXPORTING io_s3datasource =
lo_val_s3datasource.

   CREATE OBJECT lo_val_channel
     EXPORTING
       iv_channelname     = 'validation'
```

```
        io_datasource      = lo_val_datasource
        iv_compressiontype = iv_val_data_compressiontype
        iv_contenttype     = iv_val_data_contenttype.
    INSERT lo_val_channel INTO TABLE lt_input_data_config.

    "Create an ABAP object for algorithm specification based on input variables."
    CREATE OBJECT lo_algorithm_specification
      EXPORTING
        iv_trainingimage     = iv_training_image
        iv_traininginputmode = iv_training_input_mode.

    "Create an ABAP object for resource configuration."
    CREATE OBJECT lo_resource_config
      EXPORTING
        iv_instancecount  = iv_instance_count
        iv_instancetype   = iv_instance_type
        iv_volumesizeingb = iv_volume_sizeingb.

    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_output_data_config EXPORTING iv_s3outputpath =
iv_s3_output_path.

    "Create an ABAP object for stopping condition."
    CREATE OBJECT lo_stopping_condition EXPORTING iv_maxruntimeinseconds =
iv_max_runtime_in_seconds.

    TRY.
        lo_sgm->createtrainingjob(
          iv_trainingjobname           = iv_training_job_name
          iv_rolearn                   = iv_role_arn
          it_hyperparameters           = lt_hyperparameters
          it_inputdataconfig           = lt_input_data_config
          io_algorithmspecification    = lo_algorithm_specification
          io_outputdataconfig          = lo_output_data_config
          io_resourceconfig            = lo_resource_config
          io_stoppingcondition         = lo_stopping_condition
        ).
        MESSAGE 'Training job created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
```

```
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.

    "Wait for training job to be completed."
    lo_training_result = lo_sgm->describetrainingjob( iv_trainingjobname =
iv_training_job_name ).
    WHILE lo_training_result->get_trainingjobstatus( ) <> 'Completed'.
      IF sy-index = 30.
        EXIT.               "Maximum 900 seconds."
      ENDIF.
      WAIT UP TO 30 SECONDS.
      lo_training_result = lo_sgm->describetrainingjob( iv_trainingjobname =
iv_training_job_name ).
    ENDWHILE.

    "Create ABAP object for the container image based on input variables."
    CREATE OBJECT lo_primarycontainer
      EXPORTING
        iv_image        = iv_training_image
        iv_modeldataurl = lv_model_data_url.

    "Create an Amazon SageMaker model."
    TRY.
        lo_sgm->createmodel(
          iv_executionrolearn = iv_role_arn
          iv_modelname = iv_model_name
          io_primarycontainer = lo_primarycontainer
        ).
        MESSAGE 'Model created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
    ENDTRY.

    "Create an endpoint production variant."
    CREATE OBJECT lo_production_variants
      EXPORTING
        iv_variantname          = iv_ep_variant_name
        iv_modelname            = iv_model_name
        iv_initialinstancecount = iv_ep_initial_instance_count
        iv_instancetype         = iv_ep_instance_type.
    INSERT lo_production_variants INTO TABLE lt_production_variants.
```

```
   TRY.
       "Create an endpoint configuration."
       lo_ep_config_result = lo_sgm->createendpointconfig(
         iv_endpointconfigname = iv_ep_cfg_name
         it_productionvariants = lt_production_variants
       ).
       MESSAGE 'Endpoint configuration created.' TYPE 'I'.

       "Create an endpoint."
       oo_ep_output = lo_sgm->createendpoint(        " oo_ep_output is returned
for testing purposes. "
           iv_endpointconfigname = iv_ep_cfg_name
           iv_endpointname = iv_ep_name
       ).
       MESSAGE 'Endpoint created.' TYPE 'I'.
     CATCH /aws1/cx_sgmresourcelimitexcd.
       MESSAGE 'You have reached the limit on the number of resources.' TYPE
'E'.
   ENDTRY.

   "Wait for endpoint creation to be completed."
   DATA(lo_endpoint_result) = lo_sgm->describeendpoint( iv_endpointname =
iv_ep_name ).
   WHILE lo_endpoint_result->get_endpointstatus( ) <> 'InService'.
     IF sy-index = 30.
       EXIT.               "Maximum 900 seconds."
     ENDIF.
     WAIT UP TO 30 SECONDS.
     lo_endpoint_result = lo_sgm->describeendpoint( iv_endpointname =
iv_ep_name ).
   ENDWHILE.

   TRY.
       "Delete an endpoint."
       lo_sgm->deleteendpoint(
           iv_endpointname = iv_ep_name
       ).
       MESSAGE 'Endpoint deleted' TYPE 'I'.

       "Delete an endpoint configuration."
       lo_sgm->deleteendpointconfig(
         iv_endpointconfigname = iv_ep_cfg_name
       ).
       MESSAGE 'Endpoint configuration deleted.' TYPE 'I'.
```

```
        "Delete model."
        lo_sgm->deletemodel(
                  iv_modelname = iv_model_name
                ).
        MESSAGE 'Model deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpointconfig_exception).
        DATA(lv_endpointconfig_error) = |"{ lo_endpointconfig_exception-
>av_err_code }" - { lo_endpointconfig_exception->av_err_msg }|.
        MESSAGE lv_endpointconfig_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateEndpoint
  - CreateEndpointConfig
  - CreateModel
  - CreateTrainingJob
  - DeleteEndpoint
  - DeleteEndpointConfig
  - DeleteModel
  - DescribeEndpoint
  - DescribeTrainingJob

Exemplos de código para o Secrets Manager usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Secrets Manager com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, você pode ver as ações contextualizadas em seus devidos cenários e exemplos de serviços cruzados.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do usuário do Secrets Manager – Mais informações sobre o Secrets Manager.
- Referência da API do Secrets Manager – Detalhes sobre todas as ações disponíveis do Secrets Manager.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Secrets Manager usando SDKs da AWS
  - Crie e gerencie um segredo do Secrets Manager usando um SDK da AWS
  - Exclua um segredo do Secrets Manager usando um SDK da AWS
  - Descreva um segredo do Secrets Manager usando um SDK da AWS
  - Obter um lote de valores de segredo o Secrets Manager usando um SDK da AWS
  - Obtenha um segredo do Secrets Manager usando um SDK da AWS
  - Liste segredos do Secrets Manager usando um SDK da AWS
  - Modifica os detalhes de um segredo usando um SDK da AWS
  - Insira um valor em um segredo do Secrets Manager usando um SDK da AWS
- Exemplos de uso entre serviços do Amazon SES usando AWS SDKs
  - Criar uma API REST de biblioteca de empréstimos

Ações para o Secrets Manager usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Secrets Manager com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Crie e gerencie um segredo do Secrets Manager usando um SDK da AWS
- Exclua um segredo do Secrets Manager usando um SDK da AWS
- Descreva um segredo do Secrets Manager usando um SDK da AWS
- Obter um lote de valores de segredo o Secrets Manager usando um SDK da AWS

- Obtenha um segredo do Secrets Manager usando um SDK da AWS
- Liste segredos do Secrets Manager usando um SDK da AWS
- Modifica os detalhes de um segredo usando um SDK da AWS
- Insira um valor em um segredo do Secrets Manager usando um SDK da AWS

Crie e gerencie um segredo do Secrets Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um segredo do Secrets Manager.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main(int argc, const char *argv[])
{
    if (argc != 3) {
        std::cout << "Usage:\n" <<
        "    <secretName> <secretValue> \n\n" <<
        "Where:\n" <<
        "    secretName - The name of the secret (for example, tutorials/
MyFirstSecret). \n" <<
        "    secretValue - The secret value. " << std::endl;
        return 0;
    }

    SDKOptions options;
    options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;

    InitAPI(options);
    {
        Aws::Client::ClientConfiguration config;

        //TODO(user): Enter the Region where you want to create the secret.
        String region = "us-east-1";
```

```
        if (!region.empty())
        {
                config.region = region;
        }
        SecretsManager::SecretsManagerClient sm_client(config);

        String secretName = argv[1];
        String secretString = argv[2];
        SecretsManager::Model::CreateSecretRequest request;
        request.SetName(secretName);
        request.SetSecretString(secretString);

        auto createSecretOutcome = sm_client.CreateSecret(request);
        if(createSecretOutcome.IsSuccess()){
                std::cout << "Create secret with name: " <<
 createSecretOutcome.GetResult().GetName() << std::endl;
        }else{
                std::cout << "Failed with Error: " <<
 createSecretOutcome.GetError() << std::endl;
        }
    }

    ShutdownAPI(options);
    return 0;
}
```

- Para obter detalhes da API, consulte CreateSecreta Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como criar um segredo

O seguinte exemplo de `create-secret` cria um segredo com dois pares de chave/valor.

```
aws secretsmanager create-secret \
    --name MyTestSecret \
    --description "My test secret created with the CLI." \
    --secret-string "{\"user\":\"diegor\",\"password\":\"EXAMPLE-PASSWORD\"}"
```

Saída:

```
{
  "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
  "Name": "MyTestSecret",
  "VersionId": "EXAMPLE1-90ab-cdef-fedc-ba987EXAMPLE"
}
```

Para obter mais informações, consulte Criar um segredo no Guia do usuário do Secrets Manager.

Exemplo 2: como criar um segredo com base nas credenciais de um arquivo JSON

O exemplo de `create-secret` a seguir cria um segredo com base em credenciais em um arquivo. Para obter mais informações, consulte Carregar os parâmetros da AWS CLI de um arquivo no Guia do usuário da AWS CLI.

```
aws secretsmanager create-secret \
    --name MyTestSecret \
    --secret-string file://mycreds.json
```

Conteúdo de `mycreds.json`:

```
{
  "engine": "mysql",
  "username": "saanvis",
  "password": "EXAMPLE-PASSWORD",
  "host": "my-database-endpoint.us-west-2.rds.amazonaws.com",
  "dbname": "myDatabase",
  "port": "3306"
}
```

Saída:

```
{
  "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
  "Name": "MyTestSecret",
  "VersionId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111"
}
```

Para obter mais informações, consulte Criar um segredo no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte CreateSecretem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.CreateSecretRequest;
import software.amazon.awssdk.services.secretsmanager.model.CreateSecretResponse;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName> <secretValue>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                    secretValue - The secret value.\s
```

```
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        String secretARN = createNewSecret(secretsClient, secretName,
 secretValue);
        System.out.println("The secret ARN is " + secretARN);
        secretsClient.close();
    }

    public static String createNewSecret(SecretsManagerClient secretsClient,
 String secretName, String secretValue) {
        try {
            CreateSecretRequest secretRequest = CreateSecretRequest.builder()
                    .name(secretName)
                    .description("This secret was created by the AWS Secret
 Manager Java API")
                    .secretString(secretValue)
                    .build();

            CreateSecretResponse secretResponse =
 secretsClient.createSecret(secretRequest);
            return secretResponse.arn();

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateSecreta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewSecret(secretName: String?, secretValue: String?): String? {

    val request = CreateSecretRequest {
        name = secretName
        description = "This secret was created by the AWS Secrets Manager Kotlin
 API"
        secretString = secretValue
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.createSecret(request)
        return response.arn
    }
}
```

- Para obter detalhes da API, consulte a CreateSecretreferência da API AWSSDK for Kotlin.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_secret(client: &Client, name: &str, value: &str) -> Result<(),
 Error> {
    client
        .create_secret()
        .name(name)
        .secret_string(value)
        .send()
        .await?;

    println!("Created secret");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateSecretreferência da API AWS SDK for Rust.

Exclua um segredo do Secrets Manager usando um SDK da AWS

O exemplo de código a seguir mostra como excluir um segredo do Secrets Manager.

CLI

AWS CLI

Exemplo 1: como excluir um segredo

O exemplo de `delete-secret` a seguir exclui um segredo. É possível recuperar o segredo com `restore-secret` até a data e a hora presentes no campo de resposta `DeletionDate`. Para excluir um segredo que está replicado em outras regiões, primeiro remova suas réplicas com `remove-regions-from-replication` e então chame `delete-secret`.

```
aws secretsmanager delete-secret \
    --secret-id MyTestSecret \
    --recovery-window-in-days 7
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
```

```
    "Name": "MyTestSecret",
    "DeletionDate": 1524085349.095
}
```

Para obter mais informações, consulte Excluir um segredo no Guia do usuário do Secrets Manager.

Exemplo 2: como excluir um segredo instantaneamente

O exemplo de `delete-secret` a seguir exclui imediatamente um segredo sem uma janela de recuperação. Não é possível recuperar esse segredo.

```
aws secretsmanager delete-secret \
    --secret-id MyTestSecret \
    --force-delete-without-recovery
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret",
    "DeletionDate": 1508750180.309
}
```

Para obter mais informações, consulte Excluir um segredo no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte DeleteSecretem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.DeleteSecretRequest;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteSecret {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                     <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        deleteSpecificSecret(secretsClient, secretName);
        secretsClient.close();
    }

    public static void deleteSpecificSecret(SecretsManagerClient secretsClient,
 String secretName) {
```

```
        try {
            DeleteSecretRequest secretRequest = DeleteSecretRequest.builder()
                    .secretId(secretName)
                    .build();

            secretsClient.deleteSecret(secretRequest);
            System.out.println(secretName + " is deleted.");

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteSecreta Referência AWS SDK for Java 2.x da API.

Descreva um segredo do Secrets Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um segredo do Secrets Manager.

CLI

AWS CLI

Como recuperar os detalhes de um segredo

O exemplo de `describe-secret` a seguir mostra os detalhes de um segredo.

```
aws secretsmanager describe-secret \
    --secret-id MyTestSecret
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
Ca8JGt",
    "Name": "MyTestSecret",
    "Description": "My test secret",
```

```
    "KmsKeyId": "arn:aws:kms:us-west-2:123456789012:key/EXAMPLE1-90ab-cdef-fedc-
ba987EXAMPLE",
    "RotationEnabled": true,
    "RotationLambdaARN": "arn:aws:lambda:us-
west-2:123456789012:function:MyTestRotationLambda",
    "RotationRules": {
        "AutomaticallyAfterDays": 2,
        "Duration": "2h",
        "ScheduleExpression": "cron(0 16 1,15 * ? *)"
    },
    "LastRotatedDate": 1525747253.72,
    "LastChangedDate": 1523477145.729,
    "LastAccessedDate": 1524572133.25,
    "Tags": [
        {
            "Key": "SecondTag",
            "Value": "AnotherValue"
        },
        {
            "Key": "FirstTag",
            "Value": "SomeValue"
        }
    ],
    "VersionIdsToStages": {
        "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111": [
            "AWSPREVIOUS"
        ],
        "a1b2c3d4-5678-90ab-cdef-EXAMPLE22222": [
            "AWSCURRENT"
        ],
        "a1b2c3d4-5678-90ab-cdef-EXAMPLE33333": [
            "AWSPENDING"
        ]
    },
    "CreatedDate": 1521534252.66,
    "PrimaryRegion": "us-west-2",
    "ReplicationStatus": [
        {
            "Region": "eu-west-3",
            "KmsKeyId": "alias/aws/secretsmanager",
            "Status": "InSync",
            "StatusMessage": "Replication succeeded"
        }
    ]
```

```
}
```

Para obter mais informações, consulte Segredo no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte DescribeSecretem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.DescribeSecretRequest;
import
 software.amazon.awssdk.services.secretsmanager.model.DescribeSecretResponse;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeSecret {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        describeGivenSecret(secretsClient, secretName);
        secretsClient.close();
    }

    public static void describeGivenSecret(SecretsManagerClient secretsClient,
 String secretName) {
        try {
            DescribeSecretRequest secretRequest = DescribeSecretRequest.builder()
                    .secretId(secretName)
                    .build();

            DescribeSecretResponse secretResponse =
 secretsClient.describeSecret(secretRequest);
            Instant lastChangedDate = secretResponse.lastChangedDate();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(lastChangedDate);
```

```
            System.out.println("The date of the last change to " +
 secretResponse.name() + " is " + lastChangedDate);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeSecreta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeGivenSecret(secretName: String?) {

    val secretRequest = DescribeSecretRequest {
        secretId = secretName
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.describeSecret(secretRequest)
        val secArn = response.description
        println("The secret description is $secArn")
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecretreferência da API AWSSDK for Kotlin.

Obter um lote de valores de segredo o Secrets Manager usando um SDK da AWS

O exemplo de código a seguir mostra como obter um lote de valores de segredo do Secrets Manager.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BatchGetSecretsWrapper:
    def __init__(self, secretsmanager_client):
        self.client = secretsmanager_client


    def batch_get_secrets(self, filter_name):
        """
        Retrieve multiple secrets from AWS Secrets Manager using the
 batch_get_secret_value API.
        This function assumes the stack mentioned in the source code README has
 been successfully deployed.
        This stack includes 7 secrets, all of which have names beginning with
 "mySecret".

        :param filter_name: The full or partial name of secrets to be fetched.
        :type filter_name: str
        """
        try:
            secrets = []
            response = self.client.batch_get_secret_value(
                Filters=[{"Key": "name", "Values": [f"{filter_name}"]}]
            )
            for secret in response["SecretValues"]:
                secrets.append(json.loads(secret["SecretString"]))
            if secrets:
                logger.info("Secrets retrieved successfully.")
            else:
```

```
                logger.info("Zero secrets returned without error.")
            return secrets
        except self.client.exceptions.ResourceNotFoundException:
            msg = f"One or more requested secrets were not found with filter:
{filter_name}"
            logger.info(msg)
            return msg
        except Exception as e:
            logger.error(f"An unknown error occurred:\n{str(e)}.")
            raise
```

- Para obter detalhes da API, consulte a BatchGetSecretValueReferência da API AWSSDK for Python (Boto3).

Obtenha um segredo do Secrets Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como obter um valor de segredo do Secrets Manager.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.SecretsManager;
using Amazon.SecretsManager.Model;

/// <summary>
/// This example uses the Amazon Web Service Secrets Manager to retrieve
/// the secret value for the provided secret name.
/// </summary>
```

```
    public class GetSecretValue
    {
        /// <summary>
        /// The main method initializes the necessary values and then calls
        /// the GetSecretAsync and DecodeString methods to get the decoded
        /// secret value for the secret named in secretName.
        /// </summary>
        public static async Task Main()
        {
            string secretName = "<<{{MySecretName}}>>";
            string secret;

            IAmazonSecretsManager client = new AmazonSecretsManagerClient();

            var response = await GetSecretAsync(client, secretName);

            if (response is not null)
            {
                secret = DecodeString(response);

                if (!string.IsNullOrEmpty(secret))
                {
                    Console.WriteLine($"The decoded secret value is: {secret}.");
                }
                else
                {
                    Console.WriteLine("No secret value was returned.");
                }
            }
        }

        /// <summary>
        /// Retrieves the secret value given the name of the secret to
        /// retrieve.
        /// </summary>
        /// <param name="client">The client object used to retrieve the secret
        /// value for the given secret name.</param>
        /// <param name="secretName">The name of the secret value to retrieve.</
param>
        /// <returns>The GetSecretValueReponse object returned by
        /// GetSecretValueAsync.</returns>
        public static async Task<GetSecretValueResponse> GetSecretAsync(
            IAmazonSecretsManager client,
            string secretName)
```

```
        {
            GetSecretValueRequest request = new GetSecretValueRequest()
            {
                SecretId = secretName,
                VersionStage = "AWSCURRENT", // VersionStage defaults to
AWSCURRENT if unspecified.
            };

            GetSecretValueResponse response = null;

            // For the sake of simplicity, this example handles only the most
            // general SecretsManager exception.
            try
            {
                response = await client.GetSecretValueAsync(request);
            }
            catch (AmazonSecretsManagerException e)
            {
                Console.WriteLine($"Error: {e.Message}");
            }

            return response;
        }

        /// <summary>
        /// Decodes the secret returned by the call to GetSecretValueAsync and
        /// returns it to the calling program.
        /// </summary>
        /// <param name="response">A GetSecretValueResponse object containing
        /// the requested secret value returned by GetSecretValueAsync.</param>
        /// <returns>A string representing the decoded secret value.</returns>
        public static string DecodeString(GetSecretValueResponse response)
        {
            // Decrypts secret using the associated AWS Key Management Service
            // Customer Master Key (CMK.) Depending on whether the secret is a
            // string or binary value, one of these fields will be populated.
            if (response.SecretString is not null)
            {
                var secret = response.SecretString;
                return secret;
            }
            else if (response.SecretBinary is not null)
            {
                var memoryStream = response.SecretBinary;
```

```
                StreamReader reader = new StreamReader(memoryStream);
                string decodedBinarySecret =
System.Text.Encoding.UTF8.GetString(Convert.FromBase64String(reader.ReadToEnd()));
                return decodedBinarySecret;
            }
            else
            {
                return string.Empty;
            }
        }
    }
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main(int argc, const char *argv[])
{
    if (argc != 2) {
        std::cout << "Usage:\n" <<
                  "    <secretName> \n\n" <<
                  "Where:\n" <<
                  "    secretName - The name of the secret (for example,
 tutorials/MyFirstSecret). \n"
                  << std::endl;
        return 0;
    }

    SDKOptions options;
    options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
```

```
    InitAPI(options);
    {
        Aws::Client::ClientConfiguration config;

        //TODO(user): Enter the Region where you want to create the secret.
        String region = "us-east-1";
        if (!region.empty())
        {
                config.region = region;
        }
        SecretsManager::SecretsManagerClient sm_client(config);

        String secretId = argv[1];
        SecretsManager::Model::GetSecretValueRequest request;
        request.SetSecretId(secretId);

        auto getSecretValueOutcome = sm_client.GetSecretValue(request);
        if(getSecretValueOutcome.IsSuccess()){
                std::cout << "Secret is: " <<
 getSecretValueOutcome.GetResult().GetSecretString() << std::endl;
        }else{
                std::cout << "Failed with Error: " <<
 getSecretValueOutcome.GetError() << std::endl;
        }
    }

    ShutdownAPI(options);
    return 0;
}
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Exemplo 1: como recuperar o valor secreto criptografado de um segredo

O exemplo de `get-secret-value` a seguir obtém o valor atual do segredo.

```
aws secretsmanager get-secret-value \
    --secret-id MyTestSecret
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret",
    "VersionId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
    "SecretString": "{\"user\":\"diegor\",\"password\":\"EXAMPLE-PASSWORD\"}",
    "VersionStages": [
        "AWSCURRENT"
    ],
    "CreatedDate": 1523477145.713
}
```

Para obter mais informações, consulte Recuperar segredos no Guia do usuário do Secrets Manager.

Exemplo 2: como recuperar o valor secreto anterior

O seguinte exemplo de `get-secret-value` recupera o valor secreto anterior:

```
aws secretsmanager get-secret-value \
    --secret-id MyTestSecret
    --version-stage AWSPREVIOUS
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret",
    "VersionId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE22222",
    "SecretString": "{\"user\":\"diegor\",\"password\":\"PREVIOUS-EXAMPLE-
PASSWORD\"}",
    "VersionStages": [
        "AWSPREVIOUS"
    ],
    "CreatedDate": 1523477145.713
```

```
}
```

Para obter mais informações, consulte Recuperar segredos no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte GetSecretValueem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
import
 software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * We recommend that you cache your secret values by using client-side caching.
 *
 * Caching secrets improves speed and reduces your costs. For more information,
 * see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/retrieving-
secrets.html
 */
public class GetSecretValue {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        getValue(secretsClient, secretName);
        secretsClient.close();
    }

    public static void getValue(SecretsManagerClient secretsClient, String
 secretName) {
        try {
            GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                    .secretId(secretName)
                    .build();

            GetSecretValueResponse valueResponse =
 secretsClient.getSecretValue(valueRequest);
            String secret = valueResponse.secretString();
            System.out.println(secret);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  GetSecretValueCommand,
  SecretsManagerClient,
} from "@aws-sdk/client-secrets-manager";

export const getSecretValue = async (secretName = "SECRET_NAME") => {
  const client = new SecretsManagerClient();
  const response = await client.send(
    new GetSecretValueCommand({
      SecretId: secretName,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '584eb612-f8b0-48c9-855e-6d246461b604',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
```

```
  //   ARN: 'arn:aws:secretsmanager:us-east-1:xxxxxxxxxxxx:secret:binary-
secret-3873048-xxxxxx',
  //   CreatedDate: 2023-08-08T19:29:51.294Z,
  //   Name: 'binary-secret-3873048',
  //   SecretBinary: Uint8Array(11) [
  //      98, 105, 110, 97, 114,
  //     121,  32, 100, 97, 116,
  //      97
  //   ],
  //   VersionId: '712083f4-0d26-415e-8044-16735142cd6a',
  //   VersionStages: [ 'AWSCURRENT' ]
  // }

  if (response.SecretString) {
    return response.SecretString;
  }

  if (response.SecretBinary) {
    return response.SecretBinary;
  }
};
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getValue(secretName: String?) {

    val valueRequest = GetSecretValueRequest {
        secretId = secretName
    }
```

```
    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.getSecretValue(valueRequest)
        val secret = response.secretString
        println("The secret value is $secret")
    }
}
```

- Para obter detalhes da API, consulte a GetSecretValuereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GetSecretWrapper:
    def __init__(self, secretsmanager_client):
        self.client = secretsmanager_client


    def get_secret(self, secret_name):
        """
        Retrieve individual secrets from AWS Secrets Manager using the
 get_secret_value API.
        This function assumes the stack mentioned in the source code README has
 been successfully deployed.
        This stack includes 7 secrets, all of which have names beginning with
 "mySecret".

        :param secret_name: The name of the secret fetched.
        :type secret_name: str
        """
        try:
            get_secret_value_response = self.client.get_secret_value(
```

```
                SecretId=secret_name
            )
            logging.info("Secret retrieved successfully.")
            return get_secret_value_response["SecretString"]
        except self.client.exceptions.ResourceNotFoundException:
            msg = f"The requested secret {secret_name} was not found."
            logger.info(msg)
            return msg
        except Exception as e:
            logger.error(f"An unknown error occurred: {str(e)}.")
            raise
```

- Para obter detalhes da API, consulte a GetSecretValueReferência da API AWSSDK for Python (Boto3).

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_secret(client: &Client, name: &str) -> Result<(), Error> {
    let resp = client.get_secret_value().secret_id(name).send().await?;

    println!("Value: {}", resp.secret_string().unwrap_or("No value!"));

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetSecretValuereferência da API AWS SDK for Rust.

Liste segredos do Secrets Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como listar um segredo do Secrets Manager.

CLI

AWS CLI

Exemplo 1: como listar os segredos na conta

O exemplo de `list-secrets` a seguir mostra uma lista dos segredos em sua conta.

```
aws secretsmanager list-secrets
```

Saída:

```
{
    "SecretList": [
        {
            "ARN": "arn:aws:secretsmanager:us-
west-2:123456789012:secret:MyTestSecret-a1b2c3",
            "Name": "MyTestSecret",
            "LastChangedDate": 1523477145.729,
            "SecretVersionsToStages": {
                "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111": [
                    "AWSCURRENT"
                ]
            }
        },
        {
            "ARN": "arn:aws:secretsmanager:us-
west-2:123456789012:secret:AnotherSecret-d4e5f6",
            "Name": "AnotherSecret",
            "LastChangedDate": 1523482025.685,
            "SecretVersionsToStages": {
                "a1b2c3d4-5678-90ab-cdef-EXAMPLE22222": [
                    "AWSCURRENT"
                ]
            }
        }
    ]
}
```

Para obter mais informações, consulte Localizar segredos no Guia do usuário do Secrets Manager.

Exemplo 2: como filtrar os segredos na conta

O exemplo de `list-secrets` a seguir obtém uma lista dos segredos em sua conta que têm `Test` no nome. A filtragem por nome diferencia maiúsculas de minúsculas.

```
aws secretsmanager list-secrets \
    --filter Key="name",Values="Test"
```

Saída:

```
{
    "SecretList": [
        {
            "ARN": "arn:aws:secretsmanager:us-
west-2:123456789012:secret:MyTestSecret-a1b2c3",
            "Name": "MyTestSecret",
            "LastChangedDate": 1523477145.729,
            "SecretVersionsToStages": {
                "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111": [
                    "AWSCURRENT"
                ]
            }
        }
    ]
}
```

Para obter mais informações, consulte Localizar segredos no Guia do usuário do Secrets Manager.

Exemplo 3: como listar os segredos na conta gerenciada por outro serviço

O exemplo de `list-secrets` a seguir retorna os segredos da sua conta que são gerenciados pelo Amazon RDS.

```
aws secretsmanager list-secrets \
    --filter Key="owning-service",Values="rds"
```

Saída:

```
{
    "SecretList": [
        {
            "Name": "rds!cluster-a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
            "Tags": [
                {
                    "Value": "arn:aws:rds:us-
west-2:123456789012:cluster:database-1",
                    "Key": "aws:rds:primaryDBClusterArn"
                },
                {
                    "Value": "rds",
                    "Key": "aws:secretsmanager:owningService"
                }
            ],
            "RotationRules": {
                "AutomaticallyAfterDays": 1
            },
            "LastChangedDate": 1673477781.275,
            "LastRotatedDate": 1673477781.26,
            "SecretVersionsToStages": {
                "a1b2c3d4-5678-90ab-cdef-EXAMPLEaaaaa": [
                    "AWSPREVIOUS"
                ],
                "a1b2c3d4-5678-90ab-cdef-EXAMPLEbbbbb": [
                    "AWSCURRENT",
                    "AWSPENDING"
                ]
            },
            "OwningService": "rds",
            "RotationEnabled": true,
            "CreatedDate": 1673467300.7,
            "LastAccessedDate": 1673395200.0,
            "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:rds!
cluster-a1b2c3d4-5678-90ab-cdef-EXAMPLE11111-a1b2c3",
            "Description": "Secret associated with primary RDS DB cluster:
 arn:aws:rds:us-west-2:123456789012:cluster:database-1"
        }
    ]
}
```

Para obter mais informações, consulte o Segredos gerenciados por outros serviços no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte ListSecretsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.ListSecretsResponse;
import software.amazon.awssdk.services.secretsmanager.model.SecretListEntry;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListSecrets {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        listAllSecrets(secretsClient);
        secretsClient.close();
    }

    public static void listAllSecrets(SecretsManagerClient secretsClient) {
        try {
```

```
            ListSecretsResponse secretsResponse = secretsClient.listSecrets();
            List<SecretListEntry> secrets = secretsResponse.secretList();
            for (SecretListEntry secret : secrets) {
                System.out.println("The secret name is " + secret.name());
                System.out.println("The secret descreiption is " +
 secret.description());
            }

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListSecretsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllSecrets() {

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.listSecrets(ListSecretsRequest {})
        response.secretList?.forEach { secret ->
            println("The secret name is ${secret.name}")
            println("The secret description is ${secret.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListSecretsreferência da API AWSSDK for Kotlin.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_secrets(client: &Client) -> Result<(), Error> {
    let resp = client.list_secrets().send().await?;

    println!("Secret names:");

    let secrets = resp.secret_list();
    for secret in secrets {
        println!("  {}", secret.name().unwrap_or("No name!"));
    }

    println!("Found {} secrets", secrets.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListSecretsreferência da API AWS SDK for Rust.

Modifica os detalhes de um segredo usando um SDK da AWS

Os exemplos de código a seguir mostram como modificar o segredo.

CLI

AWS CLI

Exemplo 1: como atualizar a descrição de um segredo

O exemplo de `update-secret` a seguir retorna a descrição de um segredo.

```
aws secretsmanager update-secret \
    --secret-id MyTestSecret \
    --description "This is a new description for the secret."
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret"
}
```

Para obter mais informações, consulte Modificar um segredo no Guia do usuário do Secrets Manager.

Exemplo 2: como atualizar a chave de criptografia associada a um segredo

O exemplo de `update-secret` a seguir atualiza a chave do KMS usada para criptografar o valor secreto. A chave do KMS precisa estar na mesma do segredo.

```
aws secretsmanager update-secret \
    --secret-id MyTestSecret \
    --kms-key-id arn:aws:kms:us-west-2:123456789012:key/EXAMPLE1-90ab-cdef-fedc-
ba987EXAMPLE
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret"
}
```

Para obter mais informações, consulte Modificar um segredo no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte UpdateSecretem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import software.amazon.awssdk.services.secretsmanager.model.UpdateSecretRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UpdateSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName> <secretValue>

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                    secretValue - The secret value that is updated.\s
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        updateMySecret(secretsClient, secretName, secretValue);
        secretsClient.close();
    }

    public static void updateMySecret(SecretsManagerClient secretsClient, String
 secretName, String secretValue) {
        try {
            UpdateSecretRequest secretRequest = UpdateSecretRequest.builder()
                    .secretId(secretName)
                    .secretString(secretValue)
                    .build();

            secretsClient.updateSecret(secretRequest);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateSecreta Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateMySecret(secretName: String?, secretValue: String?) {

    val request = UpdateSecretRequest {
        secretId = secretName
        secretString = secretValue
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        secretsClient.updateSecret(request)
        println("The secret value was updated")
    }
}
```

- Para obter detalhes da API, consulte a UpdateSecretreferência da API AWSSDK for Kotlin.

Insira um valor em um segredo do Secrets Manager usando um SDK da AWS

O exemplo de código a seguir mostra como inserir valor em um segredo do Secrets Manager.

CLI

AWS CLI

Exemplo 1: como armazenar um novo valor secreto em um segredo

O exemplo de `put-secret-value` a seguir cria uma nova versão de um segredo com dois pares de chave/valor.

```
aws secretsmanager put-secret-value \
    --secret-id MyTestSecret \
    --secret-string "{\"user\":\"diegor\",\"password\":\"EXAMPLE-PASSWORD\"}"
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-
west-2:123456789012:secret:MyTestSecret-1a2b3c",
    "Name": "MyTestSecret",
    "VersionId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
    "VersionStages": [
        "AWSCURRENT"
```

```
    ]
}
```

Para obter mais informações, consulte Modificar um segredo no Guia do usuário do Secrets Manager.

Exemplo 2: como armazenar um novo valor secreto das credenciais em um arquivo JSON

O exemplo de `put-secret-value` a seguir cria uma nova versão de um segredo com base em credenciais em um arquivo. Para obter mais informações, consulte Carregar os parâmetros da AWS CLI de um arquivo no Guia do usuário da AWS CLI.

```
aws secretsmanager put-secret-value \
    --secret-id MyTestSecret \
    --secret-string file://mycreds.json
```

Conteúdo de `mycreds.json`:

```
{
  "engine": "mysql",
  "username": "saanvis",
  "password": "EXAMPLE-PASSWORD",
  "host": "my-database-endpoint.us-west-2.rds.amazonaws.com",
  "dbname": "myDatabase",
  "port": "3306"
}
```

Saída:

```
{
    "ARN": "arn:aws:secretsmanager:us-west-2:123456789012:secret:MyTestSecret-
a1b2c3",
    "Name": "MyTestSecret",
    "VersionId": "a1b2c3d4-5678-90ab-cdef-EXAMPLE11111",
    "VersionStages": [
        "AWSCURRENT"
    ]
}
```

Para obter mais informações, consulte Modificar um segredo no Guia do usuário do Secrets Manager.

- Para obter detalhes da API, consulte PutSecretValueem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import
 software.amazon.awssdk.services.secretsmanager.model.PutSecretValueRequest;
import
 software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PutSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName> <secretValue>

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                    secretValue - The text to encrypt and store in the new
 version of the secret.\s
```

```
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        putSecret(secretsClient, secretName, secretValue);
        secretsClient.close();
    }

    public static void putSecret(SecretsManagerClient secretsClient, String
 secretName, String secretValue) {
        try {
            PutSecretValueRequest secretRequest = PutSecretValueRequest.builder()
                    .secretId(secretName)
                    .secretString(secretValue)
                    .build();

            secretsClient.putSecretValue(secretRequest);
            System.out.println("A new version was created.");

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutSecretValuea Referência AWS SDK for Java 2.x da API.

Exemplos de uso entre serviços do Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Secrets Manager com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma API REST de biblioteca de empréstimos

Criar uma API REST de biblioteca de empréstimos

O exemplo de código abaixo mostra como criar uma biblioteca de empréstimos na qual os clientes possam pegar e devolver livros emprestados usando uma API REST com suporte por um banco de dados do Amazon Aurora.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com a API do Amazon Relational Database Service (Amazon RDS) e o AWS Chalice a fim de criar uma API REST com suporte por um banco de dados do Amazon Aurora. O serviço da Web é uma tecnologia sem servidor e representa uma biblioteca de empréstimos simples, na qual os clientes podem pegar e devolver livros emprestados. Aprenda como:

- Crie e gerencie um cluster de banco de dados Aurora com tecnologia sem servidor.
- Utilize o AWS Secrets Manager para gerenciar credenciais de bancos de dados.
- Implemente uma camada de armazenamento de dados que use o Amazon RDS para mover dados para dentro e fora do banco de dados.
- Use o AWS Chalice para implantar uma API REST com tecnologia sem servidor no Amazon API Gateway e no AWS Lambda.
- Use o pacote Requests para enviar solicitações ao serviço Web.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Aurora
- Lambda
- Secrets Manager

Exemplos de código para o Amazon SES usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Email Service (Amazon SES) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon SES – Mais informações sobre o Amazon SES.
- Referência da API do Amazon SES – Detalhes sobre todas as ações disponíveis do Amazon SES.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Amazon SES usando AWS SDKs
  - Criar um filtro de recebimento do Amazon SES usando um AWS SDK
  - Criar uma regra de recebimento do Amazon SES usando um AWS SDK
  - Criar um conjunto de regras de recebimento do Amazon SES usando um AWS SDK
  - Criar um modelo de e-mail do Amazon SES usando um AWS SDK

- Excluir um filtro de recebimento do Amazon SES usando um AWS SDK
- Excluir uma regra de recebimento do Amazon SES usando um AWS SDK
- Excluir um conjunto de regras do Amazon SES usando um AWS SDK
- Excluir um modelo de e-mail do Amazon SES usando um AWS SDK
- Excluir uma identidade do Amazon SES usando um AWS SDK
- Descrever um conjunto de regras de recebimento do Amazon SES usando um AWS SDK
- Obter um modelo existente de e-mail do Amazon SES usando um AWS SDK
- Obter limites de envio do Amazon SES usando um AWS SDK
- Obter o status de uma identidade do Amazon SES usando um AWS SDK
- Listar modelos de e-mail do Amazon SES usando um AWS SDK
- Listar identidades do Amazon SES usando um AWS SDK
- Listar filtros de recebimento do Amazon SES usando um AWS SDK
- Enviar e-mails com base em modelo para vários destinos com o Amazon SES usando um AWS SDK
- Enviar e-mails com o Amazon SES usando um AWS SDK
- Enviar e-mails brutos com o Amazon SES usando um AWS SDK
- Enviar e-mails com base em modelo com o Amazon SES usando um AWS SDK
- Atualizar um modelo de e-mail do Amazon SES usando um AWS SDK
- Verificar uma identidade de domínio com o Amazon SES usando um AWS SDK
- Verificar uma identidade de e-mail com o Amazon SES usando um AWS SDK

- Cenários para o Amazon SES usando AWS SDKs
  - Copiar identidades de domínio e e-mail do Amazon SES de uma região da AWS para outra usando um AWS SDK
  - Gerar credenciais para estabelecer conexão com um endpoint SMTP do Amazon SES
  - Verificar uma identidade de e-mail e enviar mensagens com o Amazon SES usando um AWS SDK
- Exemplos de uso entre serviços do Amazon SES usando AWS SDKs
  - Criar uma aplicação de transmissão do Amazon Transcribe
  - Criar uma aplicação Web para monitorar dados do DynamoDB
  - Criar um rastreador de itens do Amazon Redshift
  - Crie um rastreador de itens de trabalho do Aurora Sem Servidor

- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Usar Step Functions para invocar funções do Lambda

Ações para o Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Email Service (Amazon SES) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon SES usando AWS SDKs.

Exemplos

- Criar um filtro de recebimento do Amazon SES usando um AWS SDK
- Criar uma regra de recebimento do Amazon SES usando um AWS SDK
- Criar um conjunto de regras de recebimento do Amazon SES usando um AWS SDK
- Criar um modelo de e-mail do Amazon SES usando um AWS SDK
- Excluir um filtro de recebimento do Amazon SES usando um AWS SDK
- Excluir uma regra de recebimento do Amazon SES usando um AWS SDK
- Excluir um conjunto de regras do Amazon SES usando um AWS SDK
- Excluir um modelo de e-mail do Amazon SES usando um AWS SDK
- Excluir uma identidade do Amazon SES usando um AWS SDK
- Descrever um conjunto de regras de recebimento do Amazon SES usando um AWS SDK
- Obter um modelo existente de e-mail do Amazon SES usando um AWS SDK
- Obter limites de envio do Amazon SES usando um AWS SDK
- Obter o status de uma identidade do Amazon SES usando um AWS SDK
- Listar modelos de e-mail do Amazon SES usando um AWS SDK
- Listar identidades do Amazon SES usando um AWS SDK
- Listar filtros de recebimento do Amazon SES usando um AWS SDK
- Enviar e-mails com base em modelo para vários destinos com o Amazon SES usando um AWS SDK

- Enviar e-mails com o Amazon SES usando um AWS SDK
- Enviar e-mails brutos com o Amazon SES usando um AWS SDK
- Enviar e-mails com base em modelo com o Amazon SES usando um AWS SDK
- Atualizar um modelo de e-mail do Amazon SES usando um AWS SDK
- Verificar uma identidade de domínio com o Amazon SES usando um AWS SDK
- Verificar uma identidade de e-mail com o Amazon SES usando um AWS SDK

Criar um filtro de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como criar um filtro de recebimento do Amazon SES que bloqueia e-mails recebidos de um endereço IP ou de um intervalo de endereços IP.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt filter..
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param cidr: IP address or IP address range in Classless Inter-Domain Routing
 (CIDR) notation.
  \param policy: Block or allow enum of type ReceiptFilterPolicy.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::String &cidr,
                                      Aws::SES::Model::ReceiptFilterPolicy
 policy,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::CreateReceiptFilterRequest createReceiptFilterRequest;
```

```
    Aws::SES::Model::ReceiptFilter receiptFilter;
    Aws::SES::Model::ReceiptIpFilter receiptIpFilter;
    receiptIpFilter.SetCidr(cidr);
    receiptIpFilter.SetPolicy(policy);
    receiptFilter.SetName(receiptFilterName);
    receiptFilter.SetIpFilter(receiptIpFilter);
    createReceiptFilterRequest.SetFilter(receiptFilter);
    Aws::SES::Model::CreateReceiptFilterOutcome createReceiptFilterOutcome =
 sesClient.CreateReceiptFilter(
            createReceiptFilterRequest);
    if (createReceiptFilterOutcome.IsSuccess()) {
        std::cout << "Successfully created receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt filter: " <<
                  createReceiptFilterOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return createReceiptFilterOutcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptFiltera Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  CreateReceiptFilterCommand,
  ReceiptFilterPolicy,
} from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
```

```
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const createCreateReceiptFilterCommand = ({ policy, ipOrRange, name }) => {
  return new CreateReceiptFilterCommand({
    Filter: {
      IpFilter: {
        Cidr: ipOrRange, // string, either a single IP address (10.0.0.1) or an
 IP address range in CIDR notation (10.0.0.1/24)).
        Policy: policy, // enum ReceiptFilterPolicy, email traffic from the
 filtered addressesOptions.
      },
      /*
        The name of the IP address filter. Only ASCII letters, numbers,
 underscores, or dashes.
        Must be less than 64 characters and start and end with a letter or
 number.
       */
      Name: name,
    },
  });
};

const FILTER_NAME = getUniqueName("ReceiptFilter");

const run = async () => {
  const createReceiptFilterCommand = createCreateReceiptFilterCommand({
    policy: ReceiptFilterPolicy.Allow,
    ipOrRange: "10.0.0.1",
    name: FILTER_NAME,
  });

  try {
    return await sesClient.send(createReceiptFilterCommand);
  } catch (err) {
    console.log("Failed to create filter.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptFiltera Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_receipt_filter(self, filter_name, ip_address_or_range, allow):
        """
        Creates a filter that allows or blocks incoming mail from an IP address
 or
        range.

        :param filter_name: The name to give the filter.
        :param ip_address_or_range: The IP address or range to block or allow.
        :param allow: When True, incoming mail is allowed from the specified IP
                      address or range; otherwise, it is blocked.
        """
        try:
            policy = "Allow" if allow else "Block"
            self.ses_client.create_receipt_filter(
                Filter={
                    "Name": filter_name,
                    "IpFilter": {"Cidr": ip_address_or_range, "Policy": policy},
                }
            )
            logger.info(
```

```
                "Created receipt filter %s to %s IP of %s.",
                filter_name,
                policy,
                ip_address_or_range,
            )
        except ClientError:
            logger.exception("Couldn't create receipt filter %s.", filter_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptFilterReferência da API AWSSDK for Python (Boto3).

Criar uma regra de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como criar uma regra de recebimento do Amazon SES.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param s3BucketName: The name of the S3 bucket for incoming mail.
  \param s3ObjectKeyPrefix: The prefix for the objects in the S3 bucket.
  \param ruleSetName: The name of the rule set where the receipt rule is added.
  \param recipients: Aws::Vector of recipients.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &s3BucketName,
                                    const Aws::String &s3ObjectKeyPrefix,
```

```
                                    const Aws::String &ruleSetName,
                                    const Aws::Vector<Aws::String> &recipients,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleRequest createReceiptRuleRequest;

    Aws::SES::Model::S3Action s3Action;
    s3Action.SetBucketName(s3BucketName);
    s3Action.SetObjectKeyPrefix(s3ObjectKeyPrefix);

    Aws::SES::Model::ReceiptAction receiptAction;
    receiptAction.SetS3Action(s3Action);

    Aws::SES::Model::ReceiptRule receiptRule;
    receiptRule.SetName(receiptRuleName);
    receiptRule.WithRecipients(recipients);

    Aws::Vector<Aws::SES::Model::ReceiptAction> receiptActionList;
    receiptActionList.emplace_back(receiptAction);
    receiptRule.SetActions(receiptActionList);

    createReceiptRuleRequest.SetRuleSetName(ruleSetName);
    createReceiptRuleRequest.SetRule(receiptRule);

    auto outcome = sesClient.CreateReceiptRule(createReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created receipt rule." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptRulea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateReceiptRuleCommand, TlsPolicy } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");
const RULE_NAME = getUniqueName("RuleName");
const S3_BUCKET_NAME = getUniqueName("S3BucketName");

const createS3ReceiptRuleCommand = ({
  bucketName,
  emailAddresses,
  name,
  ruleSet,
}) => {
  return new CreateReceiptRuleCommand({
    Rule: {
      Actions: [
        {
          S3Action: {
            BucketName: bucketName,
            ObjectKeyPrefix: "email",
          },
        },
      ],
      Recipients: emailAddresses,
      Enabled: true,
      Name: name,
      ScanEnabled: false,
```

```
      TlsPolicy: TlsPolicy.Optional,
    },
    RuleSetName: ruleSet, // Required
  });
};

const run = async () => {
  const s3ReceiptRuleCommand = createS3ReceiptRuleCommand({
    bucketName: S3_BUCKET_NAME,
    emailAddresses: ["email@example.com"],
    name: RULE_NAME,
    ruleSet: RULE_SET_NAME,
  });

  try {
    return await sesClient.send(s3ReceiptRuleCommand);
  } catch (err) {
    console.log("Failed to create S3 receipt rule.", err);
    throw err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptRulea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um bucket do Amazon S3 no qual o Amazon SES possa colocar cópias de e-mails recebidos e crie uma regra que copia para o bucket os e-mails recebidos de uma lista específica de destinatários.

```
class SesReceiptHandler:
```

```
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_bucket_for_copy(self, bucket_name):
        """
        Creates a bucket that can receive copies of emails from Amazon SES. This
        includes adding a policy to the bucket that grants Amazon SES permission
        to put objects in the bucket.

        :param bucket_name: The name of the bucket to create.
        :return: The newly created bucket.
        """
        allow_ses_put_policy = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Sid": "AllowSESPut",
                    "Effect": "Allow",
                    "Principal": {"Service": "ses.amazonaws.com"},
                    "Action": "s3:PutObject",
                    "Resource": f"arn:aws:s3:::{bucket_name}/*",
                }
            ],
        }
        bucket = None
        try:
            bucket = self.s3_resource.create_bucket(
                Bucket=bucket_name,
                CreateBucketConfiguration={
                    "LocationConstraint":
self.s3_resource.meta.client.meta.region_name
                },
            )
            bucket.wait_until_exists()
            bucket.Policy().put(Policy=json.dumps(allow_ses_put_policy))
```

```
            logger.info("Created bucket %s to receive copies of emails.",
bucket_name)
        except ClientError:
            logger.exception("Couldn't create bucket to receive copies of
emails.")
            if bucket is not None:
                bucket.delete()
            raise
        else:
            return bucket


    def create_s3_copy_rule(
        self, rule_set_name, rule_name, recipients, bucket_name, prefix
    ):
        """
        Creates a rule so that all emails received by the specified recipients
are
        copied to an Amazon S3 bucket.

        :param rule_set_name: The name of a previously created rule set to
contain
                              this rule.
        :param rule_name: The name to give the rule.
        :param recipients: When an email is received by one of these recipients,
it
                           is copied to the Amazon S3 bucket.
        :param bucket_name: The name of the bucket to receive email copies. This
                            bucket must allow Amazon SES to put objects into it.
        :param prefix: An object key prefix to give the emails copied to the
bucket.
        """
        try:
            self.ses_client.create_receipt_rule(
                RuleSetName=rule_set_name,
                Rule={
                    "Name": rule_name,
                    "Enabled": True,
                    "Recipients": recipients,
                    "Actions": [
                        {
                            "S3Action": {
                                "BucketName": bucket_name,
                                "ObjectKeyPrefix": prefix,
```

```
                            }
                        }
                    ],
                },
            )
            logger.info(
                "Created rule %s to copy mail received by %s to bucket %s.",
                rule_name,
                recipients,
                bucket_name,
            )
        except ClientError:
            logger.exception("Couldn't create rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptRuleReferência da API AWSSDK for Python (Boto3).

Criar um conjunto de regras de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como criar um conjunto de regras de recebimento do Amazon SES para organizar as regras aplicadas aos e-mails recebidos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param ruleSetName: The name of the rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::SES::createReceiptRuleSet(const Aws::String &ruleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleSetRequest createReceiptRuleSetRequest;

    createReceiptRuleSetRequest.SetRuleSetName(ruleSetName);

    Aws::SES::Model::CreateReceiptRuleSetOutcome outcome =
 sesClient.CreateReceiptRuleSet(
            createReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created receipt rule set." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule set. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptRuleSeta Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateReceiptRuleSetCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
```

```
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");

const createCreateReceiptRuleSetCommand = (ruleSetName) => {
  return new CreateReceiptRuleSetCommand({ RuleSetName: ruleSetName });
};

const run = async () => {
  const createReceiptRuleSetCommand =
    createCreateReceiptRuleSetCommand(RULE_SET_NAME);

  try {
    return await sesClient.send(createReceiptRuleSetCommand);
  } catch (err) {
    console.log("Failed to create receipt rule set", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptRuleSeta Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
```

```
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_receipt_rule_set(self, rule_set_name):
        """
        Creates an empty rule set. Rule sets contain individual rules and can be
        used to organize rules.

        :param rule_set_name: The name to give the rule set.
        """
        try:
            self.ses_client.create_receipt_rule_set(RuleSetName=rule_set_name)
            logger.info("Created receipt rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't create receipt rule set %s.",
rule_set_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Criar um modelo de e-mail do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como criar um modelo de e-mail do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an email template.
    /// </summary>
    /// <param name="name">Name of the template.</param>
    /// <param name="subject">Email subject.</param>
    /// <param name="text">Email body text.</param>
    /// <param name="html">Email HTML body text.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> CreateEmailTemplateAsync(string name, string subject,
string text,
        string html)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.CreateTemplateAsync(
                new CreateTemplateRequest
                {
                    Template = new Template
                    {
                        TemplateName = name,
                        SubjectPart = subject,
                        TextPart = text,
                        HtmlPart = html
                    }
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
```

```
            Console.WriteLine("CreateEmailTemplateAsync failed with exception: "
 + ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateTemplateRequest createTemplateRequest;
    Aws::SES::Model::Template aTemplate;
```

```
    aTemplate.SetTemplateName(templateName);
    aTemplate.SetHtmlPart(htmlPart);
    aTemplate.SetSubjectPart(subjectPart);
    aTemplate.SetTextPart(textPart);

    createTemplateRequest.SetTemplate(aTemplate);

    Aws::SES::Model::CreateTemplateOutcome outcome = sesClient.CreateTemplate(
            createTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created template." << templateName << "."
                  << std::endl;
    }
    else {
        std::cerr << "Error creating template. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateTemplateCommand } from "@aws-sdk/client-ses";
```

```
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const TEMPLATE_NAME = getUniqueName("TestTemplateName");

const createCreateTemplateCommand = () => {
  return new CreateTemplateCommand({
    /**
     * The template feature in Amazon SES is based on the Handlebars template
 system.
     */
    Template: {
      /**
       * The name of an existing template in Amazon SES.
       */
      TemplateName: TEMPLATE_NAME,
      HtmlPart: `
        <h1>Hello, {{contact.firstName}}!</h1>
        <p>
        Did you know Amazon has a mascot named Peccy?
        </p>
      `,
      SubjectPart: "Amazon Tip",
    },
  });
};

const run = async () => {
  const createTemplateCommand = createCreateTemplateCommand();

  try {
    return await sesClient.send(createTemplateCommand);
  } catch (err) {
    console.log("Failed to create template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
 html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def create_template(self, name, subject, text, html):
        """
        Creates an email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
```

```
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.create_template(Template=template)
            logger.info("Created template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't create template %s.", name)
            raise
```

- Para obter detalhes da API, consulte a CreateTemplateReferência da API AWSSDK for Python (Boto3).

Excluir um filtro de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um filtro de recebimento do Amazon SES.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt filter.
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::SES::deleteReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptFilterRequest deleteReceiptFilterRequest;

    deleteReceiptFilterRequest.SetFilterName(receiptFilterName);

    Aws::SES::Model::DeleteReceiptFilterOutcome outcome =
 sesClient.DeleteReceiptFilter(
            deleteReceiptFilterRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error deleting receipt filter. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptFiltera Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptFilterCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
```

```
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RECEIPT_FILTER_NAME = getUniqueName("ReceiptFilterName");

const createDeleteReceiptFilterCommand = (filterName) => {
  return new DeleteReceiptFilterCommand({ FilterName: filterName });
};

const run = async () => {
  const deleteReceiptFilterCommand =
    createDeleteReceiptFilterCommand(RECEIPT_FILTER_NAME);

  try {
    return await sesClient.send(deleteReceiptFilterCommand);
  } catch (err) {
    console.log("Error deleting receipt filter.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptFiltera Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
```

```
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_filter(self, filter_name):
        """
        Deletes a receipt filter.

        :param filter_name: The name of the filter to delete.
        """
        try:
            self.ses_client.delete_receipt_filter(FilterName=filter_name)
            logger.info("Deleted receipt filter %s.", filter_name)
        except ClientError:
            logger.exception("Couldn't delete receipt filter %s.", filter_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptFilterReferência da API AWSSDK for Python (Boto3).

Excluir uma regra de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma regra de recebimento do Amazon SES.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param receiptRuleSetName: The name for the receipt rule set.
```

```
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &receiptRuleSetName,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleRequest deleteReceiptRuleRequest;

    deleteReceiptRuleRequest.SetRuleName(receiptRuleName);
    deleteReceiptRuleRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleOutcome outcome =
 sesClient.DeleteReceiptRule(
            deleteReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule." << std::endl;
    }
    else {
        std::cout << "Error deleting receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptRulea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptRuleCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const RULE_NAME = getUniqueName("RuleName");
const RULE_SET_NAME = getUniqueName("RuleSetName");

const createDeleteReceiptRuleCommand = () => {
  return new DeleteReceiptRuleCommand({
    RuleName: RULE_NAME,
    RuleSetName: RULE_SET_NAME,
  });
};

const run = async () => {
  const deleteReceiptRuleCommand = createDeleteReceiptRuleCommand();
  try {
    return await sesClient.send(deleteReceiptRuleCommand);
  } catch (err) {
    console.log("Failed to delete receipt rule.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptRulea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_rule(self, rule_set_name, rule_name):
        """
        Deletes a rule.

        :param rule_set_name: The rule set that contains the rule to delete.
        :param rule_name: The rule to delete.
        """
        try:
            self.ses_client.delete_receipt_rule(
                RuleSetName=rule_set_name, RuleName=rule_name
            )
            logger.info("Removed rule %s from rule set %s.", rule_name,
 rule_set_name)
        except ClientError:
            logger.exception(
                "Couldn't remove rule %s from rule set %s.", rule_name,
 rule_set_name
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptRuleReferência da API AWSSDK for Python (Boto3).

Excluir um conjunto de regras do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um conjunto de regras do Amazon SES e todas as regras contidas nele.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param receiptRuleSetName: The name for the receipt rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRuleSet(const Aws::String &receiptRuleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleSetRequest deleteReceiptRuleSetRequest;

    deleteReceiptRuleSetRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleSetOutcome outcome =
 sesClient.DeleteReceiptRuleSet(
            deleteReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule set." << std::endl;
```

```
    }

    else {
        std::cerr << "Error deleting receipt rule set. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptRuleSeta Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptRuleSetCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");

const createDeleteReceiptRuleSetCommand = () => {
  return new DeleteReceiptRuleSetCommand({ RuleSetName: RULE_SET_NAME });
};

const run = async () => {
  const deleteReceiptRuleSetCommand = createDeleteReceiptRuleSetCommand();

  try {
    return await sesClient.send(deleteReceiptRuleSetCommand);
  } catch (err) {
```

```
    console.log("Failed to delete receipt rule set.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptRuleSeta Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_rule_set(self, rule_set_name):
        """
        Deletes a rule set. When a rule set is deleted, all of the rules it
 contains
        are also deleted.

        :param rule_set_name: The name of the rule set to delete.
        """
        try:
            self.ses_client.delete_receipt_rule_set(RuleSetName=rule_set_name)
```

```
            logger.info("Deleted rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't delete rule set %s.", rule_set_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Excluir um modelo de e-mail do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um modelo de e-mail do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete an email template.
/// </summary>
/// <param name="templateName">Name of the template.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteEmailTemplateAsync(string templateName)
{
    var success = false;
    try
```

```
        {
            var response = await _amazonSimpleEmailService.DeleteTemplateAsync(
                new DeleteTemplateRequest
                {
                    TemplateName = templateName
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("DeleteEmailTemplateAsync failed with exception: "
 + ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteTemplate(const Aws::String &templateName,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteTemplateRequest deleteTemplateRequest;

    deleteTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::DeleteTemplateOutcome outcome = sesClient.DeleteTemplate(
            deleteTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted template." << std::endl;
    }
    else {
        std::cerr << "Error deleting template. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");
```

```
const createDeleteTemplateCommand = (templateName) =>
  new DeleteTemplateCommand({ TemplateName: templateName });

const run = async () => {
  const deleteTemplateCommand = createDeleteTemplateCommand(TEMPLATE_NAME);

  try {
    return await sesClient.send(deleteTemplateCommand);
  } catch (err) {
    console.log("Failed to delete template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
```

```
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def delete_template(self):
        """
        Deletes an email template.
        """
        try:

self.ses_client.delete_template(TemplateName=self.template["TemplateName"])
            logger.info("Deleted template %s.", self.template["TemplateName"])
            self.template = None
            self.template_tags = None
        except ClientError:
            logger.exception(
                "Couldn't delete template %s.", self.template["TemplateName"]
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTemplateReferência da API AWSSDK for Python (Boto3).

Excluir uma identidade do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como excluir uma identidade do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an email identity.
    /// </summary>
    /// <param name="identityEmail">The identity email to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteIdentityAsync(string identityEmail)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.DeleteIdentityAsync(
                new DeleteIdentityRequest
                {
                    Identity = identityEmail
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("DeleteIdentityAsync failed with exception: " +
ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete the specified identity (an email address or a domain).
/*!
  \param identity: The identity to delete.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteIdentity(const Aws::String &identity,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteIdentityRequest deleteIdentityRequest;

    deleteIdentityRequest.SetIdentity(identity);

    Aws::SES::Model::DeleteIdentityOutcome outcome = sesClient.DeleteIdentity(
            deleteIdentityRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted identity." << std::endl;
    }
    else {
        std::cerr << "Error deleting identity. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para excluir uma identidade

O exemplo a seguir usa o comando `delete-identity` para excluir uma identidade da lista de identidades verificadas com o Amazon SES:

```
aws ses delete-identity --identity user@example.com
```

Para saber mais sobre identidades verificadas, consulte Verificar endereços de e-mail e domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte DeleteIdentityem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteIdentityCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const IDENTITY_EMAIL = "fake@example.com";

const createDeleteIdentityCommand = (identityName) => {
  return new DeleteIdentityCommand({
    Identity: identityName,
  });
};

const run = async () => {
```

```
  const deleteIdentityCommand = createDeleteIdentityCommand(IDENTITY_EMAIL);

  try {
    return await sesClient.send(deleteIdentityCommand);
  } catch (err) {
    console.log("Failed to delete identity.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def delete_identity(self, identity):
        """
        Deletes an identity.

        :param identity: The identity to remove.
        """
        try:
```

```
            self.ses_client.delete_identity(Identity=identity)
            logger.info("Deleted identity %s.", identity)
        except ClientError:
            logger.exception("Couldn't delete identity %s.", identity)
            raise
```

- Para obter detalhes da API, consulte a DeleteIdentityReferência da API AWSSDK for Python (Boto3).

Descrever um conjunto de regras de recebimento do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como descrever um conjunto de regras de recebimento do Amazon SES.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def describe_receipt_rule_set(self, rule_set_name):
```

```
        """
        Gets data about a rule set.

        :param rule_set_name: The name of the rule set to retrieve.
        :return: Data about the rule set.
        """
        try:
            response = self.ses_client.describe_receipt_rule_set(
                RuleSetName=rule_set_name
            )
            logger.info("Got data for rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't get data for rule set %s.", rule_set_name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Obter um modelo existente de e-mail do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como obter um modelo existente de e-mail do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Get a template's attributes.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::getTemplate(const Aws::String &templateName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::GetTemplateRequest getTemplateRequest;

    getTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::GetTemplateOutcome outcome = sesClient.GetTemplate(
            getTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully got template." << std::endl;
    }

    else {
        std::cerr << "Error getting template. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetTemplatea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { GetTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");

const createGetTemplateCommand = (templateName) =>
  new GetTemplateCommand({ TemplateName: templateName });

const run = async () => {
  const getTemplateCommand = createGetTemplateCommand(TEMPLATE_NAME);

  try {
    return await sesClient.send(getTemplateCommand);
  } catch (err) {
    console.log("Failed to get email template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte GetTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
 html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def get_template(self, name):
        """
        Gets a previously created email template.

        :param name: The name of the template to retrieve.
        :return: The retrieved email template.
        """
        try:
```

```
            response = self.ses_client.get_template(TemplateName=name)
            self.template = response["Template"]
            logger.info("Got template %s.", name)
            self._extract_tags(
                self.template["SubjectPart"],
                self.template["TextPart"],
                self.template["HtmlPart"],
            )
        except ClientError:
            logger.exception("Couldn't get template %s.", name)
            raise
        else:
            return self.template
```

- Para obter detalhes da API, consulte a GetTemplateReferência da API AWSSDK for Python (Boto3).

Obter limites de envio do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como obter limites de envio do Amazon SES.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information on the current account's send quota.
    /// </summary>
    /// <returns>The send quota response data.</returns>
    public async Task<GetSendQuotaResponse> GetSendQuotaAsync()
    {
        var result = new GetSendQuotaResponse();
```

```
        try
        {
            var response = await _amazonSimpleEmailService.GetSendQuotaAsync(
                new GetSendQuotaRequest());
            result = response;
        }
        catch (Exception ex)
        {
            Console.WriteLine("GetSendQuotaAsync failed with exception: " +
 ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte GetSendQuotaa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para obter limites do envio do Amazon SES

O exemplo a seguir usa o comando `get-send-quota` para retornar seus limites de envio do Amazon SES:

```
aws ses get-send-quota
```

Saída:

```
{
   "Max24HourSend": 200.0,
   "SentLast24Hours": 1.0,
   "MaxSendRate": 1.0
}
```

Max24 HourSend é sua cota de envio, que é o número máximo de e-mails que você pode enviar em um período de 24 horas. A cota de envio reflete um período de tempo acumulado.

Sempre que você tenta enviar um e-mail, o Amazon SES verifica quantos e-mails foram enviados nas 24 horas anteriores. Desde que o número total de e-mails que você enviou seja menor que a sua cota, sua solicitação de envio será aceito e seus e-mails serão enviados.

SentLast24Hours é o número de e-mails que você enviou nas últimas 24 horas.

MaxSendRate é o número máximo de e-mails que você pode enviar por segundo.

Os limites de envio se baseiam em destinatários, e não em mensagens. Por exemplo, um e-mail com dez destinatários conta como dez em sua cota de envio.

Para obter mais informações, consulte Gerenciamento de limites do envio do Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte GetSendQuotaem Referência de AWS CLI Comandos.

Obter o status de uma identidade do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como obter o status de uma identidade do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get identity verification status for an email.
/// </summary>
/// <returns>The verification status of the email.</returns>
```

```
    public async Task<VerificationStatus> GetIdentityStatusAsync(string email)
    {
        var result = VerificationStatus.TemporaryFailure;
        try
        {
            var response =
                await
_amazonSimpleEmailService.GetIdentityVerificationAttributesAsync(
                    new GetIdentityVerificationAttributesRequest
                    {
                        Identities = new List<string> { email }
                    });

            if (response.VerificationAttributes.ContainsKey(email))
                result =
response.VerificationAttributes[email].VerificationStatus;
        }
        catch (Exception ex)
        {
            Console.WriteLine("GetIdentityStatusAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte GetIdentityVerificationAttributesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para obter o status de verificação do Amazon SES para uma lista de identidades

O exemplo a seguir usa o comando `get-identity-verification-attributes` para recuperar o status de verificação do Amazon SES para uma lista de identidades:

```
aws ses get-identity-verification-attributes --identities "user1@example.com"
 "user2@example.com"
```

Saída:

```
{
   "VerificationAttributes": {
       "user1@example.com": {
           "VerificationStatus": "Success"
       },
       "user2@example.com": {
           "VerificationStatus": "Pending"
       }
   }
}
```

Se você chamar esse comando com uma identidade que nunca foi enviada para verificação, essa identidade não aparecerá na saída.

Para saber mais sobre identidades verificadas, consulte Verificar endereços de e-mail e domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte GetIdentityVerificationAttributesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
```

```
    def get_identity_status(self, identity):
        """
        Gets the status of an identity. This can be used to discover whether
        an identity has been successfully verified.

        :param identity: The identity to query.
        :return: The status of the identity.
        """
        try:
            response = self.ses_client.get_identity_verification_attributes(
                Identities=[identity]
            )
            status = response["VerificationAttributes"].get(
                identity, {"VerificationStatus": "NotFound"}
            )["VerificationStatus"]
            logger.info("Got status of %s for %s.", status, identity)
        except ClientError:
            logger.exception("Couldn't get status for %s.", identity)
            raise
        else:
            return status
```

- Para obter detalhes da API, consulte a GetIdentityVerificationAttributesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'
```

```
# Create client in us-west-2 region
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
client = Aws::SES::Client.new(region: "us-west-2")

# Get up to 1000 identities
ids = client.list_identities({
  identity_type: "EmailAddress"
})

ids.identities.each do |email|
  attrs = client.get_identity_verification_attributes({
    identities: [email]
  })

  status = attrs.verification_attributes[email].verification_status

  # Display email addresses that have been verified
  if status == "Success"
    puts email
  end
end
```

- Para obter detalhes da API, consulte GetIdentityVerificationAttributesa Referência AWS SDK for Ruby da API.

Listar modelos de e-mail do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como listar modelos de e-mail do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List email templates for the current account.
    /// </summary>
    /// <returns>A list of template metadata.</returns>
    public async Task<List<TemplateMetadata>> ListEmailTemplatesAsync()
    {
        var result = new List<TemplateMetadata>();
        try
        {
            var response = await _amazonSimpleEmailService.ListTemplatesAsync(
                new ListTemplatesRequest());
            result = response.TemplatesMetadata;
        }
        catch (Exception ex)
        {
            Console.WriteLine("ListEmailTemplatesAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.SesV2Client;
import software.amazon.awssdk.services.sesv2.model.ListEmailTemplatesRequest;
import software.amazon.awssdk.services.sesv2.model.ListEmailTemplatesResponse;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;

public class ListTemplates {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SesV2Client sesv2Client = SesV2Client.builder()
                .region(region)
                .build();

        listAllTemplates(sesv2Client);
    }

    public static void listAllTemplates(SesV2Client sesv2Client) {
        try {
            ListEmailTemplatesRequest templatesRequest =
 ListEmailTemplatesRequest.builder()
                    .pageSize(1)
                    .build();

            ListEmailTemplatesResponse response =
 sesv2Client.listEmailTemplates(templatesRequest);
            response.templatesMetadata()
                    .forEach(template -> System.out.println("Template name: " +
 template.templateName()));

        } catch (SesV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListTemplatesCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListTemplatesCommand = (maxItems) =>
  new ListTemplatesCommand({ MaxItems: maxItems });

const run = async () => {
  const listTemplatesCommand = createListTemplatesCommand(10);

  try {
    return await sesClient.send(listTemplatesCommand);
  } catch (err) {
    console.log("Failed to list templates.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
 html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def list_templates(self):
        """
        Gets a list of all email templates for the current account.

        :return: The list of retrieved email templates.
        """
        try:
            response = self.ses_client.list_templates()
```

```
            templates = response["TemplatesMetadata"]
            logger.info("Got %s templates.", len(templates))
        except ClientError:
            logger.exception("Couldn't get templates.")
            raise
        else:
            return templates
```

- Para obter detalhes da API, consulte a ListTemplatesReferência da API AWSSDK for Python (Boto3).

Listar identidades do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como listar identidades do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Copiar identidades de domínio e e-mail entre regiões
- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the identities of a specified type for the current account.
    /// </summary>
    /// <param name="identityType">IdentityType to list.</param>
    /// <returns>The list of identities.</returns>
```

```
    public async Task<List<string>> ListIdentitiesAsync(IdentityType
 identityType)
    {
        var result = new List<string>();
        try
        {
            var response = await _amazonSimpleEmailService.ListIdentitiesAsync(
                new ListIdentitiesRequest
                {
                    IdentityType = identityType
                });
            result = response.Identities;
        }
        catch (Exception ex)
        {
            Console.WriteLine("ListIdentitiesAsync failed with exception: " +
 ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the identities associated with this account.
/*!
  \param identityType: The identity type enum. "NOT_SET" is a valid option.
  \param identities; A vector to receive the retrieved identities.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
```

```
 */
bool AwsDoc::SES::listIdentities(Aws::SES::Model::IdentityType identityType,
                                 Aws::Vector<Aws::String> &identities,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::ListIdentitiesRequest listIdentitiesRequest;

    if (identityType != Aws::SES::Model::IdentityType::NOT_SET) {
        listIdentitiesRequest.SetIdentityType(identityType);
    }

    Aws::String nextToken; // Used for paginated results.
    do {
        if (!nextToken.empty()) {
            listIdentitiesRequest.SetNextToken(nextToken);
        }
        Aws::SES::Model::ListIdentitiesOutcome outcome =
 sesClient.ListIdentities(
                listIdentitiesRequest);

        if (outcome.IsSuccess()) {
            const auto &retrievedIdentities =
 outcome.GetResult().GetIdentities();
            if (!retrievedIdentities.empty()) {
                identities.insert(identities.cend(),
 retrievedIdentities.cbegin(),
                                  retrievedIdentities.cend());
            }
            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error listing identities. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!nextToken.empty());

    return true;
}
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para listar todas as identidades (endereços de e-mail e domínios) de uma conta da AWS específica

O exemplo a seguir usa o comando `list-identities` para listar todas as identidades que foram enviadas para verificação com o Amazon SES:

```
aws ses list-identities
```

Saída:

```
{
    "Identities": [
      "user@example.com",
      "example.com"
    ]
}
```

A lista retornada contém todas as identidades, independentemente do status da verificação (verificada, verificação pendente, falha etc.).

Neste exemplo, endereços de e-mail e domínios são retornados porque não especificamos o parâmetro identity-type.

Para obter mais informações sobre verificação, consulte Verificar endereços de e-mail e domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte ListIdentitiesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import software.amazon.awssdk.services.ses.model.ListIdentitiesResponse;
import software.amazon.awssdk.services.ses.model.SesException;
import java.io.IOException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListIdentities {

    public static void main(String[] args) throws IOException {
        Region region = Region.US_WEST_2;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        listSESIdentities(client);
    }

    public static void listSESIdentities(SesClient client) {
        try {
            ListIdentitiesResponse identitiesResponse = client.listIdentities();
            List<String> identities = identitiesResponse.identities();
            for (String identity : identities) {
```

```
                System.out.println("The identity is " + identity);
            }

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListIdentitiesCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListIdentitiesCommand = () =>
  new ListIdentitiesCommand({ IdentityType: "EmailAddress", MaxItems: 10 });

const run = async () => {
  const listIdentitiesCommand = createListIdentitiesCommand();

  try {
    return await sesClient.send(listIdentitiesCommand);
  } catch (err) {
    console.log("Failed to list identities.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def list_identities(self, identity_type, max_items):
        """
        Gets the identities of the specified type for the current account.

        :param identity_type: The type of identity to retrieve, such as
 EmailAddress.
        :param max_items: The maximum number of identities to retrieve.
        :return: The list of retrieved identities.
        """
        try:
            response = self.ses_client.list_identities(
                IdentityType=identity_type, MaxItems=max_items
            )
            identities = response["Identities"]
            logger.info("Got %s identities for the current account.",
 len(identities))
        except ClientError:
            logger.exception("Couldn't list identities for the current account.")
```

```
            raise
        else:
            return identities
```

- Para obter detalhes da API, consulte a ListIdentitiesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Create client in us-west-2 region
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
client = Aws::SES::Client.new(region: "us-west-2")

# Get up to 1000 identities
ids = client.list_identities({
  identity_type: "EmailAddress"
})

ids.identities.each do |email|
  attrs = client.get_identity_verification_attributes({
    identities: [email]
  })

  status = attrs.verification_attributes[email].verification_status

  # Display email addresses that have been verified
  if status == "Success"
```

```
    puts email
  end
end
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for Ruby da API.

Listar filtros de recebimento do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como listar filtros de recebimento do Amazon SES.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the receipt filters associated with this account.
/*!
  \param filters; A vector of "ReceiptFilter" to receive the retrieved filters.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SES::listReceiptFilters(Aws::Vector<Aws::SES::Model::ReceiptFilter>
 &filters,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::ListReceiptFiltersRequest listReceiptFiltersRequest;

    Aws::SES::Model::ListReceiptFiltersOutcome outcome =
 sesClient.ListReceiptFilters(
            listReceiptFiltersRequest);
    if (outcome.IsSuccess()) {
        auto &retrievedFilters = outcome.GetResult().GetFilters();
        if (!retrievedFilters.empty()) {
```

```
            filters.insert(filters.cend(), retrievedFilters.cbegin(),
                           retrievedFilters.cend());
        }
    }
    else {
        std::cerr << "Error retrieving IP address filters: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListReceiptFiltersa Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListReceiptFiltersCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListReceiptFiltersCommand = () => new ListReceiptFiltersCommand({});

const run = async () => {
  const listReceiptFiltersCommand = createListReceiptFiltersCommand();

  return await sesClient.send(listReceiptFiltersCommand);
};
```

- Para obter detalhes da API, consulte ListReceiptFiltersa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def list_receipt_filters(self):
        """
        Gets the list of receipt filters for the current account.

        :return: The list of receipt filters.
        """
        try:
            response = self.ses_client.list_receipt_filters()
            filters = response["Filters"]
            logger.info("Got %s receipt filters.", len(filters))
        except ClientError:
            logger.exception("Couldn't get receipt filters.")
            raise
        else:
            return filters
```

- Para obter detalhes da API, consulte a ListReceiptFiltersReferência da API AWSSDK for Python (Boto3).

Enviar e-mails com base em modelo para vários destinos com o Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como enviar e-mails com base em modelo para vários destinos com o Amazon SES.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendBulkTemplatedEmailCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * Replace this with the name of an existing template.
 */
const TEMPLATE_NAME = getUniqueName("ReminderTemplate");

/**
 * Replace these with existing verified emails.
 */
const VERIFIED_EMAIL_1 = postfix(getUniqueName("Bilbo"), "@example.com");
const VERIFIED_EMAIL_2 = postfix(getUniqueName("Frodo"), "@example.com");

const USERS = [
  { firstName: "Bilbo", emailAddress: VERIFIED_EMAIL_1 },
  { firstName: "Frodo", emailAddress: VERIFIED_EMAIL_2 },
];

/**
 *
 * @param { { emailAddress: string, firstName: string }[] } users
```

```
 * @param { string } templateName the name of an existing template in SES
 * @returns { SendBulkTemplatedEmailCommand }
 */
const createBulkReminderEmailCommand = (users, templateName) => {
  return new SendBulkTemplatedEmailCommand({
    /**
     * Each 'Destination' uses a corresponding set of replacement data. We can
 map each user
     * to a 'Destination' and provide user specific replacement data to create
 personalized emails.
     *
     * Here's an example of how a template would be replaced with user data:
     * Template: <h1>Hello {{name}},</h1><p>Don't forget about the party gifts!</
p>
     * Destination 1: <h1>Hello Bilbo,</h1><p>Don't forget about the party gifts!
</p>
     * Destination 2: <h1>Hello Frodo,</h1><p>Don't forget about the party gifts!
</p>
     */
    Destinations: users.map((user) => ({
      Destination: { ToAddresses: [user.emailAddress] },
      ReplacementTemplateData: JSON.stringify({ name: user.firstName }),
    })),
    DefaultTemplateData: JSON.stringify({ name: "Shireling" }),
    Source: VERIFIED_EMAIL_1,
    Template: templateName,
  });
};

const run = async () => {
  const sendBulkTemplateEmailCommand = createBulkReminderEmailCommand(
    USERS,
    TEMPLATE_NAME,
  );
  try {
    return await sesClient.send(sendBulkTemplateEmailCommand);
  } catch (err) {
    console.log("Failed to send bulk template email", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte SendBulkTemplatedEmailla Referência AWS SDK for JavaScript da API.

Enviar e-mails com o Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como enviar e-mails com o Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
///  Send an email by using Amazon SES.
/// </summary>
/// <param name="toAddresses">List of recipients.</param>
/// <param name="ccAddresses">List of cc recipients.</param>
/// <param name="bccAddresses">List of bcc recipients.</param>
/// <param name="bodyHtml">Body of the email in HTML.</param>
/// <param name="bodyText">Body of the email in plain text.</param>
/// <param name="subject">Subject line of the email.</param>
/// <param name="senderAddress">From address.</param>
/// <returns>The messageId of the email.</returns>
public async Task<string> SendEmailAsync(List<string> toAddresses,
    List<string> ccAddresses, List<string> bccAddresses,
    string bodyHtml, string bodyText, string subject, string senderAddress)
{
    var messageId = "";
    try
    {
```

```
            var response = await _amazonSimpleEmailService.SendEmailAsync(
                new SendEmailRequest
                {
                    Destination = new Destination
                    {
                        BccAddresses = bccAddresses,
                        CcAddresses = ccAddresses,
                        ToAddresses = toAddresses
                    },
                    Message = new Message
                    {
                        Body = new Body
                        {
                            Html = new Content
                            {
                                Charset = "UTF-8",
                                Data = bodyHtml
                            },
                            Text = new Content
                            {
                                Charset = "UTF-8",
                                Data = bodyText
                            }
                        },
                        Subject = new Content
                        {
                            Charset = "UTF-8",
                            Data = subject
                        }
                    },
                    Source = senderAddress
                });
            messageId = response.MessageId;
        }
        catch (Exception ex)
        {
            Console.WriteLine("SendEmailAsync failed with exception: " +
ex.Message);
        }

        return messageId;
    }
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send an email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param subject: Email subject.
  \param htmlBody: Email body as HTML. At least one body data is required.
  \param textBody: Email body as plain text. At least one body data is required.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendEmail(const Aws::Vector<Aws::String> &recipients,
                            const Aws::String &subject,
                            const Aws::String &htmlBody,
                            const Aws::String &textBody,
                            const Aws::String &senderEmailAddress,
                            const Aws::Vector<Aws::String> &ccAddresses,
                            const Aws::String &replyToAddress,
                            const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Destination destination;
    if (!ccAddresses.empty()) {
        destination.WithCcAddresses(ccAddresses);
    }
    if (!recipients.empty()) {
```

```
        destination.WithToAddresses(recipients);
    }

    Aws::SES::Model::Body message_body;
    if (!htmlBody.empty()) {
        message_body.SetHtml(

Aws::SES::Model::Content().WithCharset("UTF-8").WithData(htmlBody));
    }

    if (!textBody.empty()) {
        message_body.SetText(

Aws::SES::Model::Content().WithCharset("UTF-8").WithData(textBody));
    }

    Aws::SES::Model::Message message;
    message.SetBody(message_body);
    message.SetSubject(
            Aws::SES::Model::Content().WithCharset("UTF-8").WithData(subject));

    Aws::SES::Model::SendEmailRequest sendEmailRequest;
    sendEmailRequest.SetDestination(destination);
    sendEmailRequest.SetMessage(message);
    if (!senderEmailAddress.empty()) {
        sendEmailRequest.SetSource(senderEmailAddress);
    }
    if (!replyToAddress.empty()) {
        sendEmailRequest.AddReplyToAddresses(replyToAddress);
    }

    auto outcome = sesClient.SendEmail(sendEmailRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending message. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
```

```
}
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para enviar um e-mail formatado usando o Amazon SES

O exemplo a seguir usa o comando `send-email` para enviar um e-mail formatado:

```
aws ses send-email --from sender@example.com --destination file://
destination.json --message file://message.json
```

Saída:

```
{
   "MessageId": "EXAMPLEf3a5efcd1-51adec81-d2a4-4e3f-9fe2-5d85c1b23783-000000"
}
```

O destino e a mensagem são estruturas de dados JSON salvas em arquivos .json no diretório atual. Esses arquivos são os seguintes:

`destination.json`:

```
{
  "ToAddresses":  ["recipient1@example.com", "recipient2@example.com"],
  "CcAddresses":  ["recipient3@example.com"],
  "BccAddresses": []
}
```

`message.json`:

```
{
   "Subject": {
       "Data": "Test email sent using the AWS CLI",
       "Charset": "UTF-8"
   },
   "Body": {
       "Text": {
```

```
            "Data": "This is the message body in text format.",
            "Charset": "UTF-8"
        },
        "Html": {
            "Data": "This message body contains HTML formatting. It can, for
 example, contain links like this one: <a class=\"ulink\" href=\"http://
docs.aws.amazon.com/ses/latest/DeveloperGuide\" target=\"_blank\">Amazon SES
 Developer Guide</a>.",
            "Charset": "UTF-8"
        }
    }
}
```

Substitua os endereços de e-mail do remetente e do destinatário por aqueles que você deseja usar. O endereço de e-mail do remetente deverá ser verificado com o Amazon SES. Até que você tenha acesso de produção ao Amazon SES, você também deverá verificar o endereço de e-mail de cada destinatário, a menos que o destinatário seja o simulador de caixa de correio do Amazon SES. Para obter mais informações sobre verificação, consulte Verificar endereços de e-mail e domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

O ID da mensagem na saída indica que a chamada para send-email foi bem-sucedida.

Se você não receber o e-mail, verifique a caixa de lixo eletrônico.

Para obter mais informações sobre como enviar e-mail formatado, consulte Envio de e-mail formatado usando a API do Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte SendEmailem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import software.amazon.awssdk.services.ses.model.Content;
import software.amazon.awssdk.services.ses.model.Destination;
import software.amazon.awssdk.services.ses.model.Message;
import software.amazon.awssdk.services.ses.model.Body;
import software.amazon.awssdk.services.ses.model.SendEmailRequest;
import software.amazon.awssdk.services.ses.model.SesException;

import javax.mail.MessagingException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendMessageEmailRequest {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <sender> <recipient> <subject>\s

                Where:
                    sender - An email address that represents the sender.\s
                    recipient -  An email address that represents the recipient.
\s
                    subject - The  subject line.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String sender = args[0];
        String recipient = args[1];
        String subject = args[2];
```

```
        Region region = Region.US_EAST_1;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        // The HTML body of the email.
        String bodyHTML = "<html>" + "<head></head>" + "<body>" + "<h1>Hello!</
h1>"
                + "<p> See the list of customers.</p>" + "</body>" + "</html>";

        try {
            send(client, sender, recipient, subject, bodyHTML);
            client.close();
            System.out.println("Done");

        } catch (MessagingException e) {
            e.getStackTrace();
        }
    }

    public static void send(SesClient client,
            String sender,
            String recipient,
            String subject,
            String bodyHTML) throws MessagingException {

        Destination destination = Destination.builder()
                .toAddresses(recipient)
                .build();

        Content content = Content.builder()
                .data(bodyHTML)
                .build();

        Content sub = Content.builder()
                .data(subject)
                .build();

        Body body = Body.builder()
                .html(content)
                .build();

        Message msg = Message.builder()
                .subject(sub)
```

```
                .body(body)
                .build();

        SendEmailRequest emailRequest = SendEmailRequest.builder()
                .destination(destination)
                .message(msg)
                .source(sender)
                .build();

        try {
            System.out.println("Attempting to send an email through Amazon SES "
 + "using the AWS SDK for Java...");
            client.sendEmail(emailRequest);

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import javax.activation.DataHandler;
import javax.activation.DataSource;
import javax.mail.Message;
import javax.mail.MessagingException;
import javax.mail.Session;
import javax.mail.internet.AddressException;
import javax.mail.internet.InternetAddress;
import javax.mail.internet.MimeMessage;
import javax.mail.internet.MimeMultipart;
import javax.mail.internet.MimeBodyPart;
import javax.mail.util.ByteArrayDataSource;
import java.io.ByteArrayOutputStream;
import java.io.IOException;
import java.nio.ByteBuffer;
import java.nio.file.Files;
import java.util.Properties;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.services.ses.model.SendRawEmailRequest;
import software.amazon.awssdk.services.ses.model.RawMessage;
import software.amazon.awssdk.services.ses.model.SesException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class SendMessageAttachment {
    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <sender> <recipient> <subject> <fileLocation>\s

                Where:
                    sender - An email address that represents the sender.\s
                    recipient -  An email address that represents the recipient.
\s
                    subject - The  subject line.\s
                    fileLocation - The location of a Microsoft Excel file to use
 as an attachment (C:/AWS/customers.xls).\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String sender = args[0];
        String recipient = args[1];
        String subject = args[2];
        String fileLocation = args[3];

        // The email body for recipients with non-HTML email clients.
        String bodyText = "Hello,\r\n" + "Please see the attached file for a list
 "
                + "of customers to contact.";

        // The HTML body of the email.
        String bodyHTML = "<html>" + "<head></head>" + "<body>" + "<h1>Hello!</
h1>"
```

```
                + "<p>Please see the attached file for a " + "list of customers
to contact.</p>" + "</body>"
                + "</html>";

        Region region = Region.US_WEST_2;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        try {
            sendemailAttachment(client, sender, recipient, subject, bodyText,
bodyHTML, fileLocation);
            client.close();
            System.out.println("Done");

        } catch (IOException | MessagingException e) {
            e.getStackTrace();
        }
    }

    public static void sendemailAttachment(SesClient client,
            String sender,
            String recipient,
            String subject,
            String bodyText,
            String bodyHTML,
            String fileLocation) throws AddressException, MessagingException,
IOException {

        java.io.File theFile = new java.io.File(fileLocation);
        byte[] fileContent = Files.readAllBytes(theFile.toPath());

        Session session = Session.getDefaultInstance(new Properties());

        // Create a new MimeMessage object.
        MimeMessage message = new MimeMessage(session);

        // Add subject, from and to lines.
        message.setSubject(subject, "UTF-8");
        message.setFrom(new InternetAddress(sender));
        message.setRecipients(Message.RecipientType.TO,
InternetAddress.parse(recipient));

        // Create a multipart/alternative child container.
```

```
        MimeMultipart msgBody = new MimeMultipart("alternative");

        // Create a wrapper for the HTML and text parts.
        MimeBodyPart wrap = new MimeBodyPart();

        // Define the text part.
        MimeBodyPart textPart = new MimeBodyPart();
        textPart.setContent(bodyText, "text/plain; charset=UTF-8");

        // Define the HTML part.
        MimeBodyPart htmlPart = new MimeBodyPart();
        htmlPart.setContent(bodyHTML, "text/html; charset=UTF-8");

        // Add the text and HTML parts to the child container.
        msgBody.addBodyPart(textPart);
        msgBody.addBodyPart(htmlPart);

        // Add the child container to the wrapper object.
        wrap.setContent(msgBody);

        // Create a multipart/mixed parent container.
        MimeMultipart msg = new MimeMultipart("mixed");

        // Add the parent container to the message.
        message.setContent(msg);
        msg.addBodyPart(wrap);

        // Define the attachment.
        MimeBodyPart att = new MimeBodyPart();
        DataSource fds = new ByteArrayDataSource(fileContent,
                "application/vnd.openxmlformats-
officedocument.spreadsheetml.sheet");
        att.setDataHandler(new DataHandler(fds));

        String reportName = "WorkReport.xls";
        att.setFileName(reportName);

        // Add the attachment to the message.
        msg.addBodyPart(att);

        try {
            System.out.println("Attempting to send an email through Amazon SES "
 + "using the AWS SDK for Java...");
```

```
            ByteArrayOutputStream outputStream = new ByteArrayOutputStream();
            message.writeTo(outputStream);

            ByteBuffer buf = ByteBuffer.wrap(outputStream.toByteArray());

            byte[] arr = new byte[buf.remaining()];
            buf.get(arr);

            SdkBytes data = SdkBytes.fromByteArray(arr);
            RawMessage rawMessage = RawMessage.builder()
                    .data(data)
                    .build();

            SendRawEmailRequest rawEmailRequest = SendRawEmailRequest.builder()
                    .rawMessage(rawMessage)
                    .build();

            client.sendRawEmail(rawEmailRequest);

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Email sent using SesClient with attachment");
    }
}
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendEmailCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
```

```
const createSendEmailCommand = (toAddress, fromAddress) => {
  return new SendEmailCommand({
    Destination: {
      /* required */
      CcAddresses: [
        /* more items */
      ],
      ToAddresses: [
        toAddress,
        /* more To-email addresses */
      ],
    },
    Message: {
      /* required */
      Body: {
        /* required */
        Html: {
          Charset: "UTF-8",
          Data: "HTML_FORMAT_BODY",
        },
        Text: {
          Charset: "UTF-8",
          Data: "TEXT_FORMAT_BODY",
        },
      },
      Subject: {
        Charset: "UTF-8",
        Data: "EMAIL_SUBJECT",
      },
    },
    Source: fromAddress,
    ReplyToAddresses: [
      /* more items */
    ],
  });
};

const run = async () => {
  const sendEmailCommand = createSendEmailCommand(
    "recipient@example.com",
    "sender@example.com",
  );
```

```
  try {
    return await sesClient.send(sendEmailCommand);
  } catch (e) {
    console.error("Failed to send email.");
    return e;
  }
};
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_email(self, source, destination, subject, text, html,
 reply_tos=None):
        """
        Sends an email.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.
```

```
        :param source: The source email account.
        :param destination: The destination email account.
        :param subject: The subject of the email.
        :param text: The plain text version of the body of the email.
        :param html: The HTML version of the body of the email.
        :param reply_tos: Email accounts that will receive a reply if the
recipient
                          replies to the message.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Message": {
                "Subject": {"Data": subject},
                "Body": {"Text": {"Data": text}, "Html": {"Data": html}},
            },
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent mail %s from %s to %s.", message_id, source,
destination.tos
            )
        except ClientError:
            logger.exception(
                "Couldn't send mail from %s to %s.", source, destination.tos
            )
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte a SendEmailReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Replace sender@example.com with your "From" address.
# This address must be verified with Amazon SES.
sender = "sender@example.com"

# Replace recipient@example.com with a "To" address. If your account
# is still in the sandbox, this address must be verified.
recipient = "recipient@example.com"

# Specify a configuration set. To use a configuration
# set, uncomment the next line and line 74.
#   configsetname = "ConfigSet"

# The subject line for the email.
subject = "Amazon SES test (AWS SDK for Ruby)"

# The HTML body of the email.
htmlbody =
  "<h1>Amazon SES test (AWS SDK for Ruby)</h1>"\
  '<p>This email was sent with <a href="https://aws.amazon.com/ses/">'\
  'Amazon SES</a> using the <a href="https://aws.amazon.com/sdk-for-ruby/">'\
  "AWS SDK for Ruby</a>."

# The email body for recipients with non-HTML email clients.
textbody = "This email was sent with Amazon SES using the AWS SDK for Ruby."

# Specify the text encoding scheme.
encoding = "UTF-8"

# Create a new SES client in the us-west-2 region.
```

```
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
ses = Aws::SES::Client.new(region: "us-west-2")

# Try to send the email.
begin
  # Provide the contents of the email.
  ses.send_email(
    destination: {
      to_addresses: [
        recipient
      ]
    },
    message: {
      body: {
        html: {
          charset: encoding,
          data: htmlbody
        },
        text: {
          charset: encoding,
          data: textbody
        }
      },
      subject: {
        charset: encoding,
        data: subject
      }
    },
    source: sender,
    # Uncomment the following line to use a configuration set.
    # configuration_set_name: configsetname,
    )

  puts "Email sent to " + recipient

# If something goes wrong, display an error message.
rescue Aws::SES::Errors::ServiceError => error
  puts "Email not sent. Error message: #{error}"
end
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Ruby da API.

Enviar e-mails brutos com o Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como enviar e-mails brutos com o Amazon SES.

CLI

AWS CLI

Para enviar e-mail bruto usando o Amazon SES

O exemplo a seguir usa o comando `send-raw-email` para enviar um e-mail com um anexo TXT:

```
aws ses send-raw-email --raw-message file://message.json
```

Saída:

```
{
   "MessageId": "EXAMPLEf3f73d99b-c63fb06f-d263-41f8-a0fb-d0dc67d56c07-000000"
}
```

A mensagem bruta é uma estrutura de dados JSON salva em um arquivo chamado `message.json` no diretório atual. Ele contém o seguinte:

```
{
   "Data": "From: sender@example.com\nTo: recipient@example.com\nSubject:
 Test email sent using the AWS CLI (contains an attachment)\nMIME-Version:
 1.0\nContent-type: Multipart/Mixed; boundary=\"NextPart\"\n\n--NextPart
\nContent-Type: text/plain\n\nThis is the message body.\n\n--NextPart\nContent-
Type: text/plain;\nContent-Disposition: attachment; filename=\"attachment.txt\"\n
\nThis is the text in the attachment.\n\n--NextPart--"
}
```

Como você pode ver, “Dados” é uma longa sequência de caracteres que contém todo o conteúdo bruto do e-mail no formato MIME, incluindo um anexo chamado attachment.txt.

Substitua sender@example.com e recipient@example.com pelos endereços que você deseja usar. O endereço de e-mail do remetente deverá ser verificado com o Amazon SES. Até que você tenha acesso de produção ao Amazon SES, você também deverá verificar o endereço de e-mail do destinatário, a menos que o destinatário seja o simulador de caixa de correio do

Amazon SES. Para obter mais informações sobre verificação, consulte Verificar endereços de e-mail e domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

O ID da mensagem na saída indica que a chamada para send-raw-email foi bem-sucedida.

Se você não receber o e-mail, verifique a caixa de lixo eletrônico.

Para obter mais informações sobre como enviar e-mail bruto, consulte Enviar e-mail bruto usando a API do Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte SendRawEmailem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use nodemailer para enviar um e-mail com anexo.

```
import sesClientModule from "@aws-sdk/client-ses";
/**
 * nodemailer wraps the SES SDK and calls SendRawEmail. Use this for more
 advanced
 * functionality like adding attachments to your email.
 *
 * https://nodemailer.com/transports/ses/
 */
import nodemailer from "nodemailer";

/**
 * @param {string} from An Amazon SES verified email address.
 * @param {*} to An Amazon SES verified email address.
 */
export const sendEmailWithAttachments = (
```

```
  from = "from@example.com",
  to = "to@example.com",
) => {
  const ses = new sesClientModule.SESClient({});
  const transporter = nodemailer.createTransport({
    SES: { ses, aws: sesClientModule },
  });

  return new Promise((resolve, reject) => {
    transporter.sendMail(
      {
        from,
        to,
        subject: "Hello World",
        text: "Greetings from Amazon SES!",
        attachments: [{ content: "Hello World!", filename: "hello.txt" }],
      },
      (err, info) => {
        if (err) {
          reject(err);
        } else {
          resolve(info);
        }
      },
    );
  });
};
```

- Para obter detalhes da API, consulte SendRawEmailla Referência AWS SDK for JavaScript da API.

Enviar e-mails com base em modelo com o Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como enviar e-mails com base em modelo com o Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Send an email using a template.
    /// </summary>
    /// <param name="sender">Address of the sender.</param>
    /// <param name="recipients">Addresses of the recipients.</param>
    /// <param name="templateName">Name of the email template.</param>
    /// <param name="templateDataObject">Data for the email template.</param>
    /// <returns>The messageId of the email.</returns>
    public async Task<string> SendTemplateEmailAsync(string sender, List<string>
recipients,
        string templateName, object templateDataObject)
    {
        var messageId = "";
        try
        {
            // Template data should be serialized JSON from either a class or a
dynamic object.
            var templateData = JsonSerializer.Serialize(templateDataObject);

            var response = await
_amazonSimpleEmailService.SendTemplatedEmailAsync(
                new SendTemplatedEmailRequest
                {
                    Source = sender,
                    Destination = new Destination
                    {
                        ToAddresses = recipients
                    },
                    Template = templateName,
                    TemplateData = templateData
                });
```

```
            messageId = response.MessageId;
        }
        catch (Exception ex)
        {
            Console.WriteLine("SendTemplateEmailAsync failed with exception: " +
 ex.Message);
        }

        return messageId;
    }
```

- Para obter detalhes da API, consulte SendTemplatedEmail a Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send a templated email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param templateName: The name of the template to use.
  \param templateData: Map of key-value pairs for replacing text in template.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendTemplatedEmail(const Aws::Vector<Aws::String> &recipients,
                                     const Aws::String &templateName,
                                     const Aws::Map<Aws::String, Aws::String>
 &templateData,
```

```
                                    const Aws::String &senderEmailAddress,
                                    const Aws::Vector<Aws::String> &ccAddresses,
                                    const Aws::String &replyToAddress,
                                    const Aws::Client::ClientConfiguration
&clientConfiguration) {
   Aws::SES::SESClient sesClient(clientConfiguration);

   Aws::SES::Model::Destination destination;
   if (!ccAddresses.empty()) {
       destination.WithCcAddresses(ccAddresses);
   }
   if (!recipients.empty()) {
       destination.WithToAddresses(recipients);
   }

   Aws::SES::Model::SendTemplatedEmailRequest sendTemplatedEmailRequest;
   sendTemplatedEmailRequest.SetDestination(destination);
   sendTemplatedEmailRequest.SetTemplate(templateName);

   std::ostringstream templateDataStream;
   templateDataStream << "{";
   size_t dataCount = 0;
   for (auto &pair: templateData) {
       templateDataStream << "\"" << pair.first << "\":\"" << pair.second <<
"\"";
       dataCount++;
       if (dataCount < templateData.size()) {
           templateDataStream << ",";
       }
   }
   templateDataStream << "}";

   sendTemplatedEmailRequest.SetTemplateData(templateDataStream.str());

   if (!senderEmailAddress.empty()) {
       sendTemplatedEmailRequest.SetSource(senderEmailAddress);
   }
   if (!replyToAddress.empty()) {
       sendTemplatedEmailRequest.AddReplyToAddresses(replyToAddress);
   }

   auto outcome = sesClient.SendTemplatedEmail(sendTemplatedEmailRequest);

   if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully sent templated message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending templated message. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SendTemplatedEmaila Referência AWS SDK for C++ da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.model.Destination;
import software.amazon.awssdk.services.sesv2.model.EmailContent;
import software.amazon.awssdk.services.sesv2.model.SendEmailRequest;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;
import software.amazon.awssdk.services.sesv2.SesV2Client;
import software.amazon.awssdk.services.sesv2.model.Template;

/**
 * Before running this AWS SDK for Java (v2) example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * Also, make sure that you create a template. See the following documentation
 * topic:
 *
 * https://docs.aws.amazon.com/ses/latest/dg/send-personalized-email-api.html
 */

public class SendEmailTemplate {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <template> <sender> <recipient>\s

                Where:
                    template - The name of the email template.
                    sender - An email address that represents the sender.\s
                    recipient - An email address that represents the recipient.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String templateName = args[0];
        String sender = args[1];
        String recipient = args[2];
        Region region = Region.US_EAST_1;
        SesV2Client sesv2Client = SesV2Client.builder()
                .region(region)
                .build();

        send(sesv2Client, sender, recipient, templateName);
    }

    public static void send(SesV2Client client, String sender, String recipient,
 String templateName) {
        Destination destination = Destination.builder()
                .toAddresses(recipient)
                .build();
```

```
        /*
         * Specify both name and favorite animal (favoriteanimal) in your code
 when
         * defining the Template object.
         * If you don't specify all the variables in the template, Amazon SES
 doesn't
         * send the email.
         */
        Template myTemplate = Template.builder()
                .templateName(templateName)
                .templateData("{\n" +
                        "  \"name\": \"Jason\"\n," +
                        "  \"favoriteanimal\": \"Cat\"\n" +
                        "}")
                .build();

        EmailContent emailContent = EmailContent.builder()
                .template(myTemplate)
                .build();

        SendEmailRequest emailRequest = SendEmailRequest.builder()
                .destination(destination)
                .content(emailContent)
                .fromEmailAddress(sender)
                .build();

        try {
            System.out.println("Attempting to send an email based on a template
 using the AWS SDK for Java (v2)...");
            client.sendEmail(emailRequest);
            System.out.println("email based on a template was sent");

        } catch (SesV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SendTemplatedEmaila Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendTemplatedEmailCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * Replace this with the name of an existing template.
 */
const TEMPLATE_NAME = getUniqueName("ReminderTemplate");

/**
 * Replace these with existing verified emails.
 */
const VERIFIED_EMAIL = postfix(getUniqueName("Bilbo"), "@example.com");

const USER = { firstName: "Bilbo", emailAddress: VERIFIED_EMAIL };

/**
 *
 * @param { { emailAddress: string, firstName: string } } user
 * @param { string } templateName - The name of an existing template in Amazon
 SES.
 * @returns { SendTemplatedEmailCommand }
 */
const createReminderEmailCommand = (user, templateName) => {
  return new SendTemplatedEmailCommand({
    /**
     * Here's an example of how a template would be replaced with user data:
     * Template: <h1>Hello {{contact.firstName}},</h1><p>Don't forget about the
 party gifts!</p>
```

```
     * Destination: <h1>Hello Bilbo,</h1><p>Don't forget about the party gifts!</
p>
     */
    Destination: { ToAddresses: [user.emailAddress] },
    TemplateData: JSON.stringify({ contact: { firstName: user.firstName } }),
    Source: VERIFIED_EMAIL,
    Template: templateName,
  });
};

const run = async () => {
  const sendReminderEmailCommand = createReminderEmailCommand(
    USER,
    TEMPLATE_NAME,
  );
  try {
    return await sesClient.send(sendReminderEmailCommand);
  } catch (err) {
    console.log("Failed to send template email", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte SendTemplatedEmaila Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""

    def __init__(self, ses_client):
```

```
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_templated_email(
        self, source, destination, template_name, template_data, reply_tos=None
    ):
        """
        Sends an email based on a template. A template contains replaceable tags
        each enclosed in two curly braces, such as {{name}}. The template data
passed
        in this function contains key-value pairs that define the values to
insert
        in place of the template tags.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param template_name: The name of a previously created template.
        :param template_data: JSON-formatted key-value pairs of replacement
values
                              that are inserted in the template before it is
sent.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Template": template_name,
            "TemplateData": json.dumps(template_data),
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_templated_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent templated mail %s from %s to %s.",
                message_id,
                source,
```

```
                destination.tos,
            )
        except ClientError:
            logger.exception(
                "Couldn't send templated mail from %s to %s.", source,
 destination.tos
            )
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte a SendTemplatedEmailReferência da API AWSSDK for Python (Boto3).

Atualizar um modelo de e-mail do Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como atualizar um modelo de e-mail do Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Verificar uma identidade de e-mail e enviar mensagens

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Update an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
```

```
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::updateTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Template templateValues;

    templateValues.SetTemplateName(templateName);
    templateValues.SetSubjectPart(subjectPart);
    templateValues.SetHtmlPart(htmlPart);
    templateValues.SetTextPart(textPart);

    Aws::SES::Model::UpdateTemplateRequest updateTemplateRequest;
    updateTemplateRequest.SetTemplate(templateValues);

    Aws::SES::Model::UpdateTemplateOutcome outcome =
 sesClient.UpdateTemplate(updateTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated template." << std::endl;
    } else {
        std::cerr << "Error updating template. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateTemplatea Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UpdateTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");
const HTML_PART = "<h1>Hello, World!</h1>";

const createUpdateTemplateCommand = () => {
  return new UpdateTemplateCommand({
    Template: {
      TemplateName: TEMPLATE_NAME,
      HtmlPart: HTML_PART,
      SubjectPart: "Example",
      TextPart: "Updated template text.",
    },
  });
};

const run = async () => {
  const updateTemplateCommand = createUpdateTemplateCommand();

  try {
    return await sesClient.send(updateTemplateCommand);
  } catch (err) {
    console.log("Failed to update template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte UpdateTemplatea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
 html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def update_template(self, name, subject, text, html):
        """
        Updates a previously created email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
```

```
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.update_template(Template=template)
            logger.info("Updated template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't update template %s.", name)
            raise
```

- Para obter detalhes da API, consulte a UpdateTemplateReferência da API AWSSDK for Python (Boto3).

Verificar uma identidade de domínio com o Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como verificar uma identidade de domínio com o Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Copiar identidades de domínio e e-mail entre regiões
- Verificar uma identidade de e-mail e enviar mensagens

CLI

AWS CLI

Para verificar um domínio com o Amazon SES

O exemplo a seguir usa o comando `verify-domain-identity` para verificar um domínio:

```
aws ses verify-domain-identity --domain example.com
```

Saída:

```
{
   "VerificationToken": "eoEmxw+YaYhb3h3iVJHuXMJXqeu1q1/wwmvjuEXAMPLE"
}
```

Para concluir a verificação do domínio, você deverá adicionar um registro TXT com o token de verificação retornado às configurações de DNS do seu domínio. Para obter mais informações, consulte Verificar domínios no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte VerifyDomainIdentityem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { VerifyDomainIdentityCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * You must have access to the domain's DNS settings to complete the
 * domain verification process.
 */
const DOMAIN_NAME = postfix(getUniqueName("Domain"), ".example.com");
```

```
const createVerifyDomainIdentityCommand = () => {
  return new VerifyDomainIdentityCommand({ Domain: DOMAIN_NAME });
};

const run = async () => {
  const VerifyDomainIdentityCommand = createVerifyDomainIdentityCommand();

  try {
    return await sesClient.send(VerifyDomainIdentityCommand);
  } catch (err) {
    console.log("Failed to verify domain.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte VerifyDomainIdentitya Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def verify_domain_identity(self, domain_name):
        """
```

```
        Starts verification of a domain identity. To complete verification, you
 must
        create a TXT record with a specific format through your DNS provider.

        For more information, see *Verifying a domain with Amazon SES* in the
        Amazon SES documentation:
            https://docs.aws.amazon.com/ses/latest/DeveloperGuide/verify-domain-
procedure.html

        :param domain_name: The name of the domain to verify.
        :return: The token to include in the TXT record with your DNS provider.
        """
        try:
            response = self.ses_client.verify_domain_identity(Domain=domain_name)
            token = response["VerificationToken"]
            logger.info("Got domain verification token for %s.", domain_name)
        except ClientError:
            logger.exception("Couldn't verify domain %s.", domain_name)
            raise
        else:
            return token
```

- Para obter detalhes da API, consulte a VerifyDomainIdentityReferência da API AWSSDK for Python (Boto3).

Verificar uma identidade de e-mail com o Amazon SES usando um AWS SDK

Os exemplos de código a seguir mostram como verificar uma identidade de e-mail com o Amazon SES.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Copiar identidades de domínio e e-mail entre regiões
- Verificar uma identidade de e-mail e enviar mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Starts verification of an email identity. This request sends an email
   /// from Amazon SES to the specified email address. To complete
   /// verification, follow the instructions in the email.
   /// </summary>
   /// <param name="recipientEmailAddress">Email address to verify.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> VerifyEmailIdentityAsync(string
recipientEmailAddress)
   {
       var success = false;
       try
       {
           var response = await
_amazonSimpleEmailService.VerifyEmailIdentityAsync(
               new VerifyEmailIdentityRequest
               {
                   EmailAddress = recipientEmailAddress
               });

           success = response.HttpStatusCode == HttpStatusCode.OK;
       }
       catch (Exception ex)
       {
           Console.WriteLine("VerifyEmailIdentityAsync failed with exception: "
+ ex.Message);
       }

       return success;
   }
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Add an email address to the list of identities associated with this account
 and
//! initiate verification.
/*!
  \param emailAddress; The email address to add.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::verifyEmailIdentity(const Aws::String &emailAddress,
                        const Aws::Client::ClientConfiguration
 &clientConfiguration)
{
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::VerifyEmailIdentityRequest verifyEmailIdentityRequest;

    verifyEmailIdentityRequest.SetEmailAddress(emailAddress);

    Aws::SES::Model::VerifyEmailIdentityOutcome outcome =
 sesClient.VerifyEmailIdentity(verifyEmailIdentityRequest);

    if (outcome.IsSuccess())
    {
        std::cout << "Email verification initiated." << std::endl;
    }
```

```
    else
    {
        std::cerr << "Error initiating email verification. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para verificar um endereço de e-mail com o Amazon SES

O exemplo a seguir usa o comando `verify-email-identity` para verificar um endereço de e-mail:

```
aws ses verify-email-identity --email-address user@example.com
```

Antes de enviar e-mails usando o Amazon SES, você deve verificar que o endereço ou domínio do qual você está enviando o email para provar que você é o proprietário. Se você ainda não tem acesso de produção, também precisará verificar todos os endereços de e-mail aos quais envia e-mails, exceto aqueles fornecidos pelo simulador de caixa de correio do Amazon SES.

Depois verify-email-identity de ser chamado, o endereço de e-mail receberá um e-mail de verificação. O usuário deve clicar no link do e-mail para concluir o processo de verificação.

Para saber mais, consulte Verificar endereços de e-mail no Amazon SES no Guia do desenvolvedor do Amazon Simple Email Service.

- Para obter detalhes da API, consulte VerifyEmailIdentityem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Import required AWS SDK clients and commands for Node.js
import { VerifyEmailIdentityCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const EMAIL_ADDRESS = "name@example.com";

const createVerifyEmailIdentityCommand = (emailAddress) => {
  return new VerifyEmailIdentityCommand({ EmailAddress: emailAddress });
};

const run = async () => {
  const verifyEmailIdentityCommand =
    createVerifyEmailIdentityCommand(EMAIL_ADDRESS);
  try {
    return await sesClient.send(verifyEmailIdentityCommand);
  } catch (err) {
    console.log("Failed to verify email identity.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def verify_email_identity(self, email_address):
        """
        Starts verification of an email identity. This function causes an email
        to be sent to the specified email address from Amazon SES. To complete
        verification, follow the instructions in the email.

        :param email_address: The email address to verify.
        """
        try:
            self.ses_client.verify_email_identity(EmailAddress=email_address)
            logger.info("Started verification of %s.", email_address)
        except ClientError:
            logger.exception("Couldn't start verification of %s.", email_address)
            raise
```

- Para obter detalhes da API, consulte a VerifyEmailIdentityReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Replace recipient@example.com with a "To" address.
recipient = "recipient@example.com"

# Create a new SES resource in the us-west-2 region.
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
ses = Aws::SES::Client.new(region: "us-west-2")

# Try to verify email address.
begin
  ses.verify_email_identity({
    email_address: recipient
  })

  puts "Email sent to " + recipient

# If something goes wrong, display an error message.
rescue Aws::SES::Errors::ServiceError => error
  puts "Email not sent. Error message: #{error}"
end
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for Ruby da API.

Cenários para o Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Email Service (Amazon SES) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Copiar identidades de domínio e e-mail do Amazon SES de uma região da AWS para outra usando um AWS SDK
- Gerar credenciais para estabelecer conexão com um endpoint SMTP do Amazon SES
- Verificar uma identidade de e-mail e enviar mensagens com o Amazon SES usando um AWS SDK

Copiar identidades de domínio e e-mail do Amazon SES de uma região da AWS para outra usando um AWS SDK

O exemplo de código a seguir mostra como copiar as identidades de domínio e e-mail do Amazon SES de uma região da AWS para outra. Quando as identidades de domínio são gerenciadas pelo Route 53, os registros de verificação são copiados para o domínio da região de destino.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import argparse
import json
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError
```

```
logger = logging.getLogger(__name__)


def get_identities(ses_client):
    """
    Gets the identities for the current Region. The Region is specified in the
    Boto3 Amazon SES client object.

    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of email identities and the list of domain identities.
    """
    email_identities = []
    domain_identities = []
    try:
        identity_paginator = ses_client.get_paginator("list_identities")
        identity_iterator = identity_paginator.paginate(
            PaginationConfig={"PageSize": 20}
        )
        for identity_page in identity_iterator:
            for identity in identity_page["Identities"]:
                if "@" in identity:
                    email_identities.append(identity)
                else:
                    domain_identities.append(identity)
        logger.info(
            "Found %s email and %s domain identities.",
            len(email_identities),
            len(domain_identities),
        )
    except ClientError:
        logger.exception("Couldn't get identities.")
        raise
    else:
        return email_identities, domain_identities


def verify_emails(email_list, ses_client):
    """
    Starts verification of a list of email addresses. Verification causes an
 email
    to be sent to each address. To complete verification, the recipient must
 follow
    the instructions in the email.
```

```
    :param email_list: The list of email addresses to verify.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of emails that were successfully submitted for
 verification.
    """
    verified_emails = []
    for email in email_list:
        try:
            ses_client.verify_email_identity(EmailAddress=email)
            verified_emails.append(email)
            logger.info("Started verification of %s.", email)
        except ClientError:
            logger.warning("Couldn't start verification of %s.", email)
    return verified_emails


def verify_domains(domain_list, ses_client):
    """
    Starts verification for a list of domain identities. This returns a token for
    each domain, which must be registered as a TXT record with the DNS provider
 for
    the domain.

    :param domain_list: The list of domains to verify.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The generated domain tokens to use to completed verification.
    """
    domain_tokens = {}
    for domain in domain_list:
        try:
            response = ses_client.verify_domain_identity(Domain=domain)
            token = response["VerificationToken"]
            domain_tokens[domain] = token
            logger.info("Got verification token %s for domain %s.", token,
 domain)
        except ClientError:
            logger.warning("Couldn't get verification token for domain %s.",
 domain)
    return domain_tokens


def get_hosted_zones(route53_client):
    """
    Gets the Amazon Route 53 hosted zones for the current account.
```

```
    :param route53_client: A Boto3 Route 53 client.
    :return: The list of hosted zones.
    """
    zones = []
    try:
        zone_paginator = route53_client.get_paginator("list_hosted_zones")
        zone_iterator = zone_paginator.paginate(PaginationConfig={"PageSize":
 20})
        zones = [
            zone for zone_page in zone_iterator for zone in
 zone_page["HostedZones"]
        ]
        logger.info("Found %s hosted zones.", len(zones))
    except ClientError:
        logger.warning("Couldn't get hosted zones.")
    return zones


def find_domain_zone_matches(domains, zones):
    """
    Finds matches between Amazon SES verified domains and Route 53 hosted zones.
    Subdomain matches are taken when found, otherwise root domain matches are
 taken.

    :param domains: The list of domains to match.
    :param zones: The list of hosted zones to match.
    :return: The set of matched domain-zone pairs. When a match is not found, the
             domain is included in the set with a zone value of None.
    """
    domain_zones = {}
    for domain in domains:
        domain_zones[domain] = None
        # Start at the most specific sub-domain and walk up to the root domain
 until a
        # zone match is found.
        domain_split = domain.split(".")
        for index in range(0, len(domain_split) - 1):
            sub_domain = ".".join(domain_split[index:])
            for zone in zones:
                # Normalize the zone name from Route 53 by removing the trailing
 '.'.
                zone_name = zone["Name"][:-1]
                if sub_domain == zone_name:
```

```
                    domain_zones[domain] = zone
                    break
            if domain_zones[domain] is not None:
                break
    return domain_zones


def add_route53_verification_record(domain, token, zone, route53_client):
    """
    Adds a domain verification TXT record to the specified Route 53 hosted zone.
    When a TXT record already exists in the hosted zone for the specified domain,
    the existing values are preserved and the new token is added to the list.

    :param domain: The domain to add.
    :param token: The verification token for the domain.
    :param zone: The hosted zone where the domain verification record is added.
    :param route53_client: A Boto3 Route 53 client.
    """
    domain_token_record_set_name = f"_amazonses.{domain}"
    record_set_paginator =
 route53_client.get_paginator("list_resource_record_sets")
    record_set_iterator = record_set_paginator.paginate(
        HostedZoneId=zone["Id"], PaginationConfig={"PageSize": 20}
    )
    records = []
    for record_set_page in record_set_iterator:
        try:
            txt_record_set = next(
                record_set
                for record_set in record_set_page["ResourceRecordSets"]
                if record_set["Name"][:-1] == domain_token_record_set_name
                and record_set["Type"] == "TXT"
            )
            records = txt_record_set["ResourceRecords"]
            logger.info(
                "Existing TXT record found in set %s for zone %s.",
                domain_token_record_set_name,
                zone["Name"],
            )
            break
        except StopIteration:
            pass
    records.append({"Value": json.dumps(token)})
    changes = [
```

```
        {
            "Action": "UPSERT",
            "ResourceRecordSet": {
                "Name": domain_token_record_set_name,
                "Type": "TXT",
                "TTL": 1800,
                "ResourceRecords": records,
            },
        }
    ]
    try:
        route53_client.change_resource_record_sets(
            HostedZoneId=zone["Id"], ChangeBatch={"Changes": changes}
        )
        logger.info(
            "Created or updated the TXT record in set %s for zone %s.",
            domain_token_record_set_name,
            zone["Name"],
        )
    except ClientError as err:
        logger.warning(
            "Got error %s. Couldn't create or update the TXT record for zone
 %s.",
            err.response["Error"]["Code"],
            zone["Name"],
        )


def generate_dkim_tokens(domain, ses_client):
    """
    Generates DKIM tokens for a domain. These must be added as CNAME records to
 the
    DNS provider for the domain.

    :param domain: The domain to generate tokens for.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of generated DKIM tokens.
    """
    dkim_tokens = []
    try:
        dkim_tokens = ses_client.verify_domain_dkim(Domain=domain)["DkimTokens"]
        logger.info("Generated %s DKIM tokens for domain %s.", len(dkim_tokens),
 domain)
    except ClientError:
```

```
        logger.warning("Couldn't generate DKIM tokens for domain %s.", domain)
    return dkim_tokens


def add_dkim_domain_tokens(hosted_zone, domain, tokens, route53_client):
    """
    Adds DKIM domain token CNAME records to a Route 53 hosted zone.

    :param hosted_zone: The hosted zone where the records are added.
    :param domain: The domain to add.
    :param tokens: The DKIM tokens for the domain to add.
    :param route53_client: A Boto3 Route 53 client.
    """
    try:
        changes = [
            {
                "Action": "UPSERT",
                "ResourceRecordSet": {
                    "Name": f"{token}._domainkey.{domain}",
                    "Type": "CNAME",
                    "TTL": 1800,
                    "ResourceRecords": [{"Value":
 f"{token}.dkim.amazonses.com"}],
                },
            }
            for token in tokens
        ]
        route53_client.change_resource_record_sets(
            HostedZoneId=hosted_zone["Id"], ChangeBatch={"Changes": changes}
        )
        logger.info(
            "Added %s DKIM CNAME records to %s in zone %s.",
            len(tokens),
            domain,
            hosted_zone["Name"],
        )
    except ClientError:
        logger.warning(
            "Couldn't add DKIM CNAME records for %s to zone %s.",
            domain,
            hosted_zone["Name"],
        )
```

```
def configure_sns_topics(identity, topics, ses_client):
    """
    Configures Amazon Simple Notification Service (Amazon SNS) notifications for
    an identity. The Amazon SNS topics must already exist.

    :param identity: The identity to configure.
    :param topics: The list of topics to configure. The choices are Bounce,
 Delivery,
                   or Complaint.
    :param ses_client: A Boto3 Amazon SES client.
    """
    for topic in topics:
        topic_arn = input(
            f"Enter the Amazon Resource Name (ARN) of the {topic} topic or press
 "
            f"Enter to skip: "
        )
        if topic_arn != "":
            try:
                ses_client.set_identity_notification_topic(
                    Identity=identity, NotificationType=topic, SnsTopic=topic_arn
                )
                logger.info("Configured %s for %s notifications.", identity,
 topic)
            except ClientError:
                logger.warning(
                    "Couldn't configure %s for %s notifications.", identity,
 topic
                )


def replicate(source_client, destination_client, route53_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print(
        f"Replicating Amazon SES identities and other configuration from "
        f"{source_client.meta.region_name} to
 {destination_client.meta.region_name}."
    )
    print("-" * 88)

    print(f"Retrieving identities from {source_client.meta.region_name}.")
    source_emails, source_domains = get_identities(source_client)
```

```
    print("Email addresses found:")
    print(*source_emails)
    print("Domains found:")
    print(*source_domains)

    print("Starting verification for email identities.")
    dest_emails = verify_emails(source_emails, destination_client)
    print("Getting domain tokens for domain identities.")
    dest_domain_tokens = verify_domains(source_domains, destination_client)

    # Get Route 53 hosted zones and match them with Amazon SES domains.
    answer = input(
        "Is the DNS configuration for your domains managed by Amazon Route 53 (y/
n)? "
    )
    use_route53 = answer.lower() == "y"
    hosted_zones = get_hosted_zones(route53_client) if use_route53 else []
    if use_route53:
        print("Adding or updating Route 53 TXT records for your domains.")
        domain_zones = find_domain_zone_matches(dest_domain_tokens.keys(),
 hosted_zones)
        for domain in domain_zones:
            add_route53_verification_record(
                domain, dest_domain_tokens[domain], domain_zones[domain],
 route53_client
            )
    else:
        print(
            "Use these verification tokens to create TXT records through your DNS
 "
            "provider:"
        )
        pprint(dest_domain_tokens)

    answer = input("Do you want to configure DKIM signing for your identities (y/
n)? ")
    if answer.lower() == "y":
        # Build a set of unique domains from email and domain identities.
        domains = {email.split("@")[1] for email in dest_emails}
        domains.update(dest_domain_tokens)
        domain_zones = find_domain_zone_matches(domains, hosted_zones)
        for domain, zone in domain_zones.items():
            answer = input(
                f"Do you want to configure DKIM signing for {domain} (y/n)? "
```

```
            )
            if answer.lower() == "y":
                dkim_tokens = generate_dkim_tokens(domain, destination_client)
                if use_route53 and zone is not None:
                    add_dkim_domain_tokens(zone, domain, dkim_tokens,
 route53_client)
                else:
                    print(
                        "Add the following DKIM tokens as CNAME records through
 your "
                        "DNS provider:"
                    )
                    print(*dkim_tokens, sep="\n")

    answer = input(
        "Do you want to configure Amazon SNS notifications for your identities
 (y/n)? "
    )
    if answer.lower() == "y":
        for identity in dest_emails + list(dest_domain_tokens.keys()):
            answer = input(
                f"Do you want to configure Amazon SNS topics for {identity} (y/
n)? "
            )
            if answer.lower() == "y":
                configure_sns_topics(
                    identity, ["Bounce", "Delivery", "Complaint"],
 destination_client
                )

    print(f"Replication complete for {destination_client.meta.region_name}.")
    print("-" * 88)


def main():
    boto3_session = boto3.Session()
    ses_regions = boto3_session.get_available_regions("ses")
    parser = argparse.ArgumentParser(
        description="Copies email address and domain identities from one AWS
 Region to "
        "another. Optionally adds records for domain verification and DKIM "
        "signing to domains that are managed by Amazon Route 53, "
        "and sets up Amazon SNS notifications for events of interest."
    )
```

```
    parser.add_argument(
        "source_region", choices=ses_regions, help="The region to copy from."
    )
    parser.add_argument(
        "destination_region", choices=ses_regions, help="The region to copy to."
    )
    args = parser.parse_args()
    source_client = boto3.client("ses", region_name=args.source_region)
    destination_client = boto3.client("ses", region_name=args.destination_region)
    route53_client = boto3.client("route53")
    replicate(source_client, destination_client, route53_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListIdentities
  - SetIdentityNotificationTopic
  - VerifyDomainDkim
  - VerifyDomainIdentity
  - VerifyEmailIdentity

Gerar credenciais para estabelecer conexão com um endpoint SMTP do Amazon SES

O exemplo de código a seguir mostra como gerar credenciais para estabelecer conexão com um endpoint SMTP do Amazon SES.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
#!/usr/bin/env python3

import hmac
import hashlib
import base64
import argparse

SMTP_REGIONS = [
    "us-east-2",  # US East (Ohio)
    "us-east-1",  # US East (N. Virginia)
    "us-west-2",  # US West (Oregon)
    "ap-south-1",  # Asia Pacific (Mumbai)
    "ap-northeast-2",  # Asia Pacific (Seoul)
    "ap-southeast-1",  # Asia Pacific (Singapore)
    "ap-southeast-2",  # Asia Pacific (Sydney)
    "ap-northeast-1",  # Asia Pacific (Tokyo)
    "ca-central-1",  # Canada (Central)
    "eu-central-1",  # Europe (Frankfurt)
    "eu-west-1",  # Europe (Ireland)
    "eu-west-2",  # Europe (London)
    "eu-south-1",  # Europe (Milan)
    "eu-north-1",  # Europe (Stockholm)
    "sa-east-1",  # South America (Sao Paulo)
    "us-gov-west-1",  # AWS GovCloud (US)
]

# These values are required to calculate the signature. Do not change them.
DATE = "11111111"
SERVICE = "ses"
MESSAGE = "SendRawEmail"
TERMINAL = "aws4_request"
VERSION = 0x04


def sign(key, msg):
    return hmac.new(key, msg.encode("utf-8"), hashlib.sha256).digest()


def calculate_key(secret_access_key, region):
    if region not in SMTP_REGIONS:
        raise ValueError(f"The {region} Region doesn't have an SMTP endpoint.")

    signature = sign(("AWS4" + secret_access_key).encode("utf-8"), DATE)
```

```
    signature = sign(signature, region)
    signature = sign(signature, SERVICE)
    signature = sign(signature, TERMINAL)
    signature = sign(signature, MESSAGE)
    signature_and_version = bytes([VERSION]) + signature
    smtp_password = base64.b64encode(signature_and_version)
    return smtp_password.decode("utf-8")


def main():
    parser = argparse.ArgumentParser(
        description="Convert a Secret Access Key to an SMTP password."
    )
    parser.add_argument("secret", help="The Secret Access Key to convert.")
    parser.add_argument(
        "region",
        help="The AWS Region where the SMTP password will be used.",
        choices=SMTP_REGIONS,
    )
    args = parser.parse_args()
    print(calculate_key(args.secret, args.region))


if __name__ == "__main__":
    main()
```

Verificar uma identidade de e-mail e enviar mensagens com o Amazon SES usando um AWS SDK

O código de exemplo a seguir mostra como:

- Adicione e verifique um endereço de e-mail com o Amazon SES.
- Envie uma mensagem de e-mail padrão.
- Crie um modelo e envie uma mensagem de e-mail com modelo.
- Envie uma mensagem usando um servidor SMTP do Amazon SES.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Verifique um endereço de e-mail com o Amazon SES e envie mensagens.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Simple Email Service (Amazon SES) email demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    ses_client = boto3.client("ses")
    ses_identity = SesIdentity(ses_client)
    ses_mail_sender = SesMailSender(ses_client)
    ses_template = SesTemplate(ses_client)
    email = input("Enter an email address to send mail with Amazon SES: ")
    status = ses_identity.get_identity_status(email)
    verified = status == "Success"
    if not verified:
        answer = input(
            f"The address '{email}' is not verified with Amazon SES. Unless your
 "
            f"Amazon SES account is out of sandbox, you can send mail only from "
            f"and to verified accounts. Do you want to verify this account for
 use "
            f"with Amazon SES? If yes, the address will receive a verification "
            f"email (y/n): "
        )
        if answer.lower() == "y":
            ses_identity.verify_email_identity(email)
            print(f"Follow the steps in the email to {email} to complete
 verification.")
            print("Waiting for verification...")
            try:
                ses_identity.wait_until_identity_exists(email)
```

```
                print(f"Identity verified for {email}.")
                verified = True
            except WaiterError:
                print(
                    f"Verification timeout exceeded. You must complete the "
                    f"steps in the email sent to {email} to verify the address."
                )

    if verified:
        test_message_text = "Hello from the Amazon SES mail demo!"
        test_message_html = "<p>Hello!</p><p>From the <b>Amazon SES</b> mail
demo!</p>"

        print(f"Sending mail from {email} to {email}.")
        ses_mail_sender.send_email(
            email,
            SesDestination([email]),
            "Amazon SES demo",
            test_message_text,
            test_message_html,
        )
        input("Mail sent. Check your inbox and press Enter to continue.")

        template = {
            "name": "doc-example-template",
            "subject": "Example of an email template.",
            "text": "This is what {{name}} will {{action}} if {{name}} can't
display "
            "HTML.",
            "html": "<p><i>This</i> is what {{name}} will {{action}} if {{name}}
"
            "<b>can</b> display HTML.</p>",
        }
        print("Creating a template and sending a templated email.")
        ses_template.create_template(**template)
        template_data = {"name": email.split("@")[0], "action": "read"}
        if ses_template.verify_tags(template_data):
            ses_mail_sender.send_templated_email(
                email, SesDestination([email]), ses_template.name(),
template_data
            )
            input("Mail sent. Check your inbox and press Enter to continue.")

        print("Sending mail through the Amazon SES SMTP server.")
```

```
        boto3_session = boto3.Session()
        region = boto3_session.region_name
        credentials = boto3_session.get_credentials()
        port = 587
        smtp_server = f"email-smtp.{region}.amazonaws.com"
        password = calculate_key(credentials.secret_key, region)
        message = """
Subject: Hi there

This message is sent from the Amazon SES SMTP mail demo."""
        context = ssl.create_default_context()
        with smtplib.SMTP(smtp_server, port) as server:
            server.starttls(context=context)
            server.login(credentials.access_key, password)
            server.sendmail(email, email, message)
        print("Mail sent. Check your inbox!")

    if ses_template.template is not None:
        print("Deleting demo template.")
        ses_template.delete_template()
    if verified:
        answer = input(f"Do you want to remove {email} from Amazon SES (y/n)? ")
        if answer.lower() == "y":
            ses_identity.delete_identity(email)
    print("Thanks for watching!")
    print("-" * 88)
```

Crie funções para encapsular ações de identidade do Amazon SES.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def verify_domain_identity(self, domain_name):
```

```
        """
        Starts verification of a domain identity. To complete verification, you
 must
        create a TXT record with a specific format through your DNS provider.

        For more information, see *Verifying a domain with Amazon SES* in the
        Amazon SES documentation:
            https://docs.aws.amazon.com/ses/latest/DeveloperGuide/verify-domain-
procedure.html

        :param domain_name: The name of the domain to verify.
        :return: The token to include in the TXT record with your DNS provider.
        """
        try:
            response = self.ses_client.verify_domain_identity(Domain=domain_name)
            token = response["VerificationToken"]
            logger.info("Got domain verification token for %s.", domain_name)
        except ClientError:
            logger.exception("Couldn't verify domain %s.", domain_name)
            raise
        else:
            return token


    def verify_email_identity(self, email_address):
        """
        Starts verification of an email identity. This function causes an email
        to be sent to the specified email address from Amazon SES. To complete
        verification, follow the instructions in the email.

        :param email_address: The email address to verify.
        """
        try:
            self.ses_client.verify_email_identity(EmailAddress=email_address)
            logger.info("Started verification of %s.", email_address)
        except ClientError:
            logger.exception("Couldn't start verification of %s.", email_address)
            raise


    def wait_until_identity_exists(self, identity):
        """
        Waits until an identity exists. The waiter polls Amazon SES until the
```

```
        identity has been successfully verified or until it exceeds its maximum
time.

        :param identity: The identity to wait for.
        """
        try:
            waiter = self.ses_client.get_waiter("identity_exists")
            logger.info("Waiting until %s exists.", identity)
            waiter.wait(Identities=[identity])
        except WaiterError:
            logger.error("Waiting for identity %s failed or timed out.",
identity)
            raise


    def get_identity_status(self, identity):
        """
        Gets the status of an identity. This can be used to discover whether
        an identity has been successfully verified.

        :param identity: The identity to query.
        :return: The status of the identity.
        """
        try:
            response = self.ses_client.get_identity_verification_attributes(
                Identities=[identity]
            )
            status = response["VerificationAttributes"].get(
                identity, {"VerificationStatus": "NotFound"}
            )["VerificationStatus"]
            logger.info("Got status of %s for %s.", status, identity)
        except ClientError:
            logger.exception("Couldn't get status for %s.", identity)
            raise
        else:
            return status


    def delete_identity(self, identity):
        """
        Deletes an identity.

        :param identity: The identity to remove.
        """
```

```
        try:
            self.ses_client.delete_identity(Identity=identity)
            logger.info("Deleted identity %s.", identity)
        except ClientError:
            logger.exception("Couldn't delete identity %s.", identity)
            raise


    def list_identities(self, identity_type, max_items):
        """
        Gets the identities of the specified type for the current account.

        :param identity_type: The type of identity to retrieve, such as
 EmailAddress.
        :param max_items: The maximum number of identities to retrieve.
        :return: The list of retrieved identities.
        """
        try:
            response = self.ses_client.list_identities(
                IdentityType=identity_type, MaxItems=max_items
            )
            identities = response["Identities"]
            logger.info("Got %s identities for the current account.",
 len(identities))
        except ClientError:
            logger.exception("Couldn't list identities for the current account.")
            raise
        else:
            return identities
```

Crie funções para encapsular ações com modelo do Amazon SES.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
```

```
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text +
html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def create_template(self, name, subject, text, html):
        """
        Creates an email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.create_template(Template=template)
            logger.info("Created template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't create template %s.", name)
            raise


    def delete_template(self):
        """
        Deletes an email template.
```

```
        """
        try:

self.ses_client.delete_template(TemplateName=self.template["TemplateName"])
            logger.info("Deleted template %s.", self.template["TemplateName"])
            self.template = None
            self.template_tags = None
        except ClientError:
            logger.exception(
                "Couldn't delete template %s.", self.template["TemplateName"]
            )
            raise


    def get_template(self, name):
        """
        Gets a previously created email template.

        :param name: The name of the template to retrieve.
        :return: The retrieved email template.
        """
        try:
            response = self.ses_client.get_template(TemplateName=name)
            self.template = response["Template"]
            logger.info("Got template %s.", name)
            self._extract_tags(
                self.template["SubjectPart"],
                self.template["TextPart"],
                self.template["HtmlPart"],
            )
        except ClientError:
            logger.exception("Couldn't get template %s.", name)
            raise
        else:
            return self.template


    def list_templates(self):
        """
        Gets a list of all email templates for the current account.

        :return: The list of retrieved email templates.
        """
        try:
```

```
            response = self.ses_client.list_templates()
            templates = response["TemplatesMetadata"]
            logger.info("Got %s templates.", len(templates))
        except ClientError:
            logger.exception("Couldn't get templates.")
            raise
        else:
            return templates


    def update_template(self, name, subject, text, html):
        """
        Updates a previously created email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.update_template(Template=template)
            logger.info("Updated template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't update template %s.", name)
            raise
```

Crie funções para encapsular ações de e-mail do Amazon SES.

```
class SesDestination:
    """Contains data about an email destination."""

    def __init__(self, tos, ccs=None, bccs=None):
```

```
        """
        :param tos: The list of recipients on the 'To:' line.
        :param ccs: The list of recipients on the 'CC:' line.
        :param bccs: The list of recipients on the 'BCC:' line.
        """
        self.tos = tos
        self.ccs = ccs
        self.bccs = bccs

    def to_service_format(self):
        """
        :return: The destination data in the format expected by Amazon SES.
        """
        svc_format = {"ToAddresses": self.tos}
        if self.ccs is not None:
            svc_format["CcAddresses"] = self.ccs
        if self.bccs is not None:
            svc_format["BccAddresses"] = self.bccs
        return svc_format



class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_email(self, source, destination, subject, text, html,
 reply_tos=None):
        """
        Sends an email.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param subject: The subject of the email.
        :param text: The plain text version of the body of the email.
```

```
        :param html: The HTML version of the body of the email.
        :param reply_tos: Email accounts that will receive a reply if the
recipient
                          replies to the message.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Message": {
                "Subject": {"Data": subject},
                "Body": {"Text": {"Data": text}, "Html": {"Data": html}},
            },
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent mail %s from %s to %s.", message_id, source,
destination.tos
            )
        except ClientError:
            logger.exception(
                "Couldn't send mail from %s to %s.", source, destination.tos
            )
            raise
        else:
            return message_id


    def send_templated_email(
        self, source, destination, template_name, template_data, reply_tos=None
    ):
        """
        Sends an email based on a template. A template contains replaceable tags
        each enclosed in two curly braces, such as {{name}}. The template data
passed
        in this function contains key-value pairs that define the values to
insert
        in place of the template tags.

        Note: If your account is in the Amazon SES  sandbox, the source and
```

```
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param template_name: The name of a previously created template.
        :param template_data: JSON-formatted key-value pairs of replacement
values
                                that are inserted in the template before it is
sent.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Template": template_name,
            "TemplateData": json.dumps(template_data),
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_templated_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent templated mail %s from %s to %s.",
                message_id,
                source,
                destination.tos,
            )
        except ClientError:
            logger.exception(
                "Couldn't send templated mail from %s to %s.", source,
destination.tos
            )
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTemplate

- DeleteIdentity
- DeleteTemplate
- GetIdentityVerificationAttributes
- GetTemplate
- ListIdentities
- ListTemplates
- SendEmail
- SendTemplatedEmail
- UpdateTemplate
- VerifyDomainIdentity
- VerifyEmailIdentity

Exemplos de uso entre serviços do Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Email Service (Amazon SES) com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de transmissão do Amazon Transcribe
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Criar um rastreador de itens do Amazon Redshift
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor
- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Usar Step Functions para invocar funções do Lambda

Criar uma aplicação de transmissão do Amazon Transcribe

O exemplo de código a seguir mostra como construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Transcribe para construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SES
- Amazon Transcribe
- Amazon Translate

Criar uma aplicação Web para monitorar dados do DynamoDB

O exemplo de código a seguir mostra como criar uma aplicação Web que monitora itens de trabalho em uma tabela do Amazon DynamoDB e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon SES

Java

SDK para Java 2.x

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para construir um serviço REST que monitora itens de trabalho no Amazon DynamoDB e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa a estrutura web Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST de Flask que se integre com Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em uma tabela do DynamoDB.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo no Repositório de exemplos de AWS código em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Criar um rastreador de itens do Amazon Redshift

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho usando um banco de dados do Amazon Redshift.

Java

SDK para Java 2.x

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Os exemplos de código a seguir mostram como criar uma aplicação Web que rastreia os itens de trabalho em um banco de dados do Amazon Aurora Sem Servidor e usa o Amazon Simple Email Service (Amazon SES) para enviar relatórios.

.NET

AWS SDK for .NET

Mostra como usar o AWS SDK for .NET para desenvolver uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end .NET RESTful.

- Integre uma aplicação Web do React com os serviços da AWS.

- Liste, adicione, atualize e exclua itens em uma tabela do Aurora.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

C++

SDK for C++

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Aurora Sem Servidor.

Para obter o código-fonte completo e instruções sobre como configurar uma API REST C++ que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Java

SDK para Java 2.x

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Para obter o código-fonte completo e instruções sobre como configurar e executar um exemplo que usa a API JDBC, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript (v3) para criar uma aplicação Web que rastreia itens de trabalho em um banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end Node.js Express.

- Integre uma aplicação Web React.js com Serviços da AWS.
- Liste, adicione e atualize itens em uma tabela do Aurora.
- Use o Amazon SES para enviar um relatório por e-mail dos itens de trabalho filtrados.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

PHP

SDK para PHP

Mostra como usar o AWS SDK for PHP para construir uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon RDS e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end construído com React.js para interagir com um back-end PHP RESTful.

- Integre uma aplicação Web React.js com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Amazon RDS.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS

- Serviços de dados do Amazon RDS
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar um serviço REST que rastreia itens de trabalho no banco de dados do Amazon Aurora Sem Servidor e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa o framework da Web do Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST do Flask que se integre a Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em um banco de dados do Aurora Sem Servidor.
- Crie um segredo do AWS Secrets Manager que contenha credenciais do banco de dados e use-o a fim de autenticar chamadas para o banco de dados.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar equipamentos de proteção individual (EPI) em imagens.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda que detecta imagens com equipamento de proteção individual.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar equipamentos de proteção individual (EPI) em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação salva os resultados em uma tabela do Amazon DynamoDB e envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Atualizar uma tabela do DynamoDB com resultados.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como construir uma aplicação que usa o Amazon Rekognition para detectar objetos por categoria em imagens.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de objetos usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Kotlin

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar uma aplicação Web que permite a você fazer o seguinte:

- Carregar fotos em um bucket do Amazon Simple Storage Service (Amazon S3).
- Usar o Amazon Rekognition para analisar e rotular as fotos.
- Usar o Amazon Simple Email Service (Amazon SES) para enviar relatórios de análise da imagem por e-mail.

Este exemplo contém dois componentes principais: uma página da Web criada com o React e um serviço REST escrito em Python que é criado com o Flask-RESTful. JavaScript

Você pode usar a página da Web do React para:

- Exibir uma lista de imagens que estão armazenadas no bucket do S3.
- Carregar imagens do computador para o bucket do S3.
- Exibir imagens e rótulos que identificam os itens detectados na imagem.
- Obter um relatório de todas as imagens no bucket do S3 e enviar um relatório por e-mail.

A página da Web chama o serviço REST. O serviço envia solicitações à AWS para realizar as seguintes ações:

- Obter e filtrar a lista de imagens no bucket do S3.
- Carregar fotos no bucket do S3.
- Usar o Amazon Rekognition para analisar fotos individuais e obter uma lista dos rótulos que identifiquem os itens detectados nas fotos.
- Analisar todas as fotos no bucket do S3 e usar o Amazon SES para enviar um relatório por e-mail.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar pessoas e objetos em um vídeo com o Amazon Rekognition.

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition

- Amazon S3
- Amazon SES

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Usar Step Functions para invocar funções do Lambda

Os exemplos de código a seguir mostram como criar um máquina de estado do AWS Step Functions que invoca a funções do AWS Lambda em sequência.

Java

SDK para Java 2.x

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for Java 2.x. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

JavaScript

SDK para JavaScript (v3)

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for JavaScript. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

O Lambda é um serviço computacional que permite executar código sem provisionar ou gerenciar servidores. O Step Functions é um serviço de orquestração sem servidor que permite combinar funções do Lambda e outros serviços da AWS para criar aplicações essenciais aos negócios.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Exemplos de código para a API v2 do Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon Simple Email Service API v2 com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do desenvolvedor do Amazon SES API v2 – Mais informações sobre o Amazon SES API v2.
- Referência do Amazon SES API v2 – Detalhes sobre todas as ações disponíveis do Amazon SES API v2.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para a API v2 do Amazon SES usando AWS SDKs
  - Criar um contato da API v2 do Amazon SES em uma lista de contatos usando um AWS SDK
  - Criar uma lista de contatos da API v2 do Amazon SES usando um AWS SDK
  - Obter informações sobre uma identidade da API v2 do Amazon SES usando um AWS SDK
  - Listar as listas de contatos da API v2 do Amazon SES usando um AWS SDK
  - Listar os contatos em uma lista de contatos da API v2 do Amazon SES usando um AWS SDK
  - Enviar um e-mail com a API v2 do Amazon SES usando um AWS SDK

Ações para a API v2 do Amazon SES usando AWS SDKs

Os exemplos de código a seguir mostram como usar a API v2 do Amazon Simple Email Service com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Criar um contato da API v2 do Amazon SES em uma lista de contatos usando um AWS SDK
- Criar uma lista de contatos da API v2 do Amazon SES usando um AWS SDK
- Obter informações sobre uma identidade da API v2 do Amazon SES usando um AWS SDK
- Listar as listas de contatos da API v2 do Amazon SES usando um AWS SDK
- Listar os contatos em uma lista de contatos da API v2 do Amazon SES usando um AWS SDK
- Enviar um e-mail com a API v2 do Amazon SES usando um AWS SDK

Criar um contato da API v2 do Amazon SES em uma lista de contatos usando um AWS SDK

O exemplo de código a seguir mostra como criar um contato da API v2 do Amazon SES em uma lista de contatos.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_contact(client: &Client, list: &str, email: &str) -> Result<(),
 Error> {
    client
        .create_contact()
        .contact_list_name(list)
        .email_address(email)
        .send()
        .await?;

    println!("Created contact");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateContactreferência da API AWS SDK for Rust.

Criar uma lista de contatos da API v2 do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como criar uma lista de contatos da API v2 do Amazon SES.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_list(client: &Client, contact_list: &str) -> Result<(), Error> {
    client
        .create_contact_list()
        .contact_list_name(contact_list)
        .send()
        .await?;

    println!("Created contact list.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateContactListreferência da API AWS SDK for Rust.

Obter informações sobre uma identidade da API v2 do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como obter informações de identidade da API v2 do Amazon SES.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determina se um endereço de e-mail foi verificado.

```
async fn is_verified(client: &Client, email: &str) -> Result<(), Error> {
    let resp = client
        .get_email_identity()
        .email_identity(email)
        .send()
        .await?;

    if resp.verified_for_sending_status() {
        println!("The address is verified");
    } else {
        println!("The address is not verified");
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetEmailIdentityreferência da API AWS SDK for Rust.

Listar as listas de contatos da API v2 do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como listar as listas de contatos da API v2 do Amazon SES.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_lists(client: &Client) -> Result<(), Error> {
    let resp = client.list_contact_lists().send().await?;

    println!("Contact lists:");

    for list in resp.contact_lists() {
        println!("  {}", list.contact_list_name().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListContactListsreferência da API AWS SDK for Rust.

Listar os contatos em uma lista de contatos da API v2 do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como listar os contatos em uma lista de contatos da API v2 do Amazon SES.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_contacts(client: &Client, list: &str) -> Result<(), Error> {
    let resp = client
        .list_contacts()
        .contact_list_name(list)
        .send()
        .await?;

    println!("Contacts:");

    for contact in resp.contacts() {
        println!("  {}", contact.email_address().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListContactsreferência da API AWS SDK for Rust.

Enviar um e-mail com a API v2 do Amazon SES usando um AWS SDK

O exemplo de código a seguir mostra como enviar um e-mail com a API do Amazon SES v2.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envia uma mensagem.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.model.Body;
import software.amazon.awssdk.services.sesv2.model.Content;
import software.amazon.awssdk.services.sesv2.model.Destination;
import software.amazon.awssdk.services.sesv2.model.EmailContent;
import software.amazon.awssdk.services.sesv2.model.Message;
import software.amazon.awssdk.services.sesv2.model.SendEmailRequest;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;
import software.amazon.awssdk.services.sesv2.SesV2Client;

/**
 * Before running this AWS SDK for Java (v2) example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class SendEmail {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                    <sender> <recipient> <subject>\s

                                Where:
                                    sender - An email address that represents the
 sender.\s
```

```
                                    recipient - An email address that represents
 the recipient.\s
                                    subject - The subject line.\s
                                """;

                if (args.length != 3) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String sender = args[0];
                String recipient = args[1];
                String subject = args[2];

                Region region = Region.US_EAST_1;
                SesV2Client sesv2Client = SesV2Client.builder()
                                .region(region)
                                .build();

                // The HTML body of the email.
                String bodyHTML = "<html>" + "<head></head>" + "<body>" +
 "<h1>Hello!</h1>"
                                + "<p> See the list of customers.</p>" + "</
body>" + "</html>";

                send(sesv2Client, sender, recipient, subject, bodyHTML);
        }

        public static void send(SesV2Client client,
                        String sender,
                        String recipient,
                        String subject,
                        String bodyHTML) {

                Destination destination = Destination.builder()
                                .toAddresses(recipient)
                                .build();

                Content content = Content.builder()
                                .data(bodyHTML)
                                .build();

                Content sub = Content.builder()
                                .data(subject)
```

```
                                .build();

                Body body = Body.builder()
                                .html(content)
                                .build();

                Message msg = Message.builder()
                                .subject(sub)
                                .body(body)
                                .build();

                EmailContent emailContent = EmailContent.builder()
                                .simple(msg)
                                .build();

                SendEmailRequest emailRequest = SendEmailRequest.builder()
                                .destination(destination)
                                .content(emailContent)
                                .fromEmailAddress(sender)
                                .build();

                try {
                        System.out.println("Attempting to send an email through
 Amazon SES "
                                        + "using the AWS SDK for Java...");
                        client.sendEmail(emailRequest);
                        System.out.println("email was sent");

                } catch (SesV2Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Java 2.x da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sesv2"
require_relative "config" # Recipient and sender email addresses.

# Set up the SESv2 client.
client = Aws::SESV2::Client.new(region: AWS_REGION)

def send_email(client, sender_email, recipient_email)
  response = client.send_email(
    {
       from_email_address: sender_email,
       destination: {
         to_addresses: [recipient_email]
       },
       content: {
         simple: {
           subject: {
             data: "Test email subject"
           },
           body: {
             text: {
               data: "Test email body"
             }
           }
         }
       }
    }
  )
  puts "Email sent from #{SENDER_EMAIL} to #{RECIPIENT_EMAIL} with message ID:
 #{response.message_id}"
end

send_email(client, SENDER_EMAIL, RECIPIENT_EMAIL)
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envia uma mensagem a todos os membros da lista de contatos.

```
async fn send_message(
    client: &Client,
    list: &str,
    from: &str,
    subject: &str,
    message: &str,
) -> Result<(), Error> {
    // Get list of email addresses from contact list.
    let resp = client
        .list_contacts()
        .contact_list_name(list)
        .send()
        .await?;

    let contacts = resp.contacts();

    let cs: Vec<String> = contacts
        .iter()
        .map(|i| i.email_address().unwrap_or_default().to_string())
        .collect();

    let mut dest: Destination = Destination::builder().build();
    dest.to_addresses = Some(cs);
    let subject_content = Content::builder()
        .data(subject)
        .charset("UTF-8")
```

```
        .build()
        .expect("building Content");
    let body_content = Content::builder()
        .data(message)
        .charset("UTF-8")
        .build()
        .expect("building Content");
    let body = Body::builder().text(body_content).build();

    let msg = Message::builder()
        .subject(subject_content)
        .body(body)
        .build();

    let email_content = EmailContent::builder().simple(msg).build();

    client
        .send_email()
        .from_email_address(from)
        .destination(dest)
        .content(email_content)
        .send()
        .await?;

    println!("Email sent to list");

    Ok(())
}
```

- Para obter detalhes da API, consulte a SendEmailreferência da API AWS SDK for Rust.

Exemplos de código para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Notification Service (Amazon SNS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon SNS – Mais informações sobre o Amazon SNS.
- Referência da API do Amazon SNS – Detalhes sobre todas as ações disponíveis do Amazon SNS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SimpleNotificationService;
using Amazon.SimpleNotificationService.Model;

namespace SNSActions;

public static class HelloSNS
{
    static async Task Main(string[] args)
    {
```

```
        var snsClient = new AmazonSimpleNotificationServiceClient();

        Console.WriteLine($"Hello Amazon SNS! Following are some of your
 topics:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get a list of topics.
        var response = await snsClient.ListTopicsAsync(
            new ListTopicsRequest());

        foreach (var topic in response.Topics)
        {
            Console.WriteLine($"\tTopic ARN: {topic.TopicArn}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sns)

# Set this project's name.
project("hello_sns")
```

```
# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you
 may need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_sns.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_sns.cpp.

```
#include <aws/core/Aws.h>
#include <aws/sns/SNSClient.h>
#include <aws/sns/model/ListTopicsRequest.h>
#include <iostream>
```

```
/*
 *  A "Hello SNS" starter application which initializes an Amazon Simple
 Notification
 *  Service (Amazon SNS) client and lists the SNS topics in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sns'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SNS::SNSClient snsClient(clientConfig);

        Aws::Vector<Aws::SNS::Model::Topic> allTopics;
        Aws::String nextToken; // Next token is used to handle a paginated
 response.
        do {
            Aws::SNS::Model::ListTopicsRequest request;

            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            const Aws::SNS::Model::ListTopicsOutcome outcome =
 snsClient.ListTopics(
                    request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SNS::Model::Topic> &paginatedTopics =
                        outcome.GetResult().GetTopics();
                if (!paginatedTopics.empty()) {
                    allTopics.insert(allTopics.cend(), paginatedTopics.cbegin(),
                                     paginatedTopics.cend());
```

```
                }
            }
            else {
                std::cerr << "Error listing topics " <<
 outcome.GetError().GetMessage()
                          << std::endl;
                return 1;
            }

            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());

        std::cout << "Hello Amazon SNS! You have " << allTopics.size() << "
 topic"
                  << (allTopics.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allTopics.empty()) {
            std::cout << "Here are your topic ARNs." << std::endl;
            for (const Aws::SNS::Model::Topic &topic: allTopics) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sns"
 "github.com/aws/aws-sdk-go-v2/service/sns/types"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Notification
 Service
// (Amazon SNS) client and list the topics in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 snsClient := sns.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the topics for your account.")
 var topics []types.Topic
 paginator := sns.NewListTopicsPaginator(snsClient, &sns.ListTopicsInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get topics. Here's why: %v\n", err)
   break
  } else {
   topics = append(topics, output.Topics...)
  }
 }
 if len(topics) == 0 {
  fmt.Println("You don't have any topics!")
 } else {
  for _, topic := range topics {
```

```
    fmt.Printf("\t%v\n", *topic.TopicArn)
   }
  }
 }
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.sns;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.paginators.ListTopicsIterable;

public class HelloSNS {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSNSTopics(snsClient);
        snsClient.close();
    }

    public static void listSNSTopics(SnsClient snsClient) {
        try {
            ListTopicsIterable listTopics = snsClient.listTopicsPaginator();
            listTopics.stream()
                    .flatMap(r -> r.topics().stream())
```

```
                    .forEach(content -> System.out.println(" Topic ARN: " +
 content.topicArn()));

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicialize um cliente SNS e liste tópicos em sua conta.

```
import { SNSClient, paginateListTopics } from "@aws-sdk/client-sns";

export const helloSns = async () => {
  // The configuration object (`{}`) is required. If the region and credentials
  // are omitted, the SDK uses your local configuration if it exists.
  const client = new SNSClient({});

  // You can also use `ListTopicsCommand`, but to use that command you must
  // handle the pagination yourself. You can do that by sending the
 `ListTopicsCommand`
  // with the `NextToken` parameter from the previous request.
  const paginatedTopics = paginateListTopics({ client }, {});
  const topics = [];

  for await (const page of paginatedTopics) {
    if (page.Topics?.length) {
      topics.push(...page.Topics);
```

```
    }
  }

  const suffix = topics.length === 1 ? "" : "s";

  console.log(
    `Hello, Amazon SNS! You have ${topics.length} topic${suffix} in your
 account.`,
  );
  console.log(topics.map((t) => `  * ${t.TopicArn}`).join("\n"));
};
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sns.SnsClient
import aws.sdk.kotlin.services.sns.model.ListTopicsRequest
import aws.sdk.kotlin.services.sns.paginators.listTopicsPaginated
import kotlinx.coroutines.flow.transform

/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main() {
    listTopicsPag()
}
```

```
suspend fun listTopicsPag() {
    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.listTopicsPaginated(ListTopicsRequest { })
            .transform { it.topics?.forEach { topic -> emit(topic) } }
            .collect { topic ->
                println("The topic ARN is ${topic.topicArn}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações para o Amazon SNS usando AWS SDKs
  - Adicionar tags a um tópico do Amazon SNS usando um AWS SDK
  - Verificar se um número de telefone saiu do Amazon SNS usando um AWS SDK
  - Confirmar que um proprietário de endpoint deseja receber mensagens do Amazon SNS usando um AWS SDK
  - Criar um tópico do Amazon SNS usando um AWS SDK
  - Excluir uma assinatura do Amazon SNS usando um AWS SDK
  - Excluir um tópico do Amazon SNS usando um AWS SDK
  - Obter as propriedades de um tópico do Amazon SNS usando um AWS SDK
  - Obter as configurações para enviar mensagens SMS do Amazon SNS usando um AWS SDK
  - Listar números de telefone que saíram do Amazon SNS usando um AWS SDK
  - Listar os assinantes de um tópico do Amazon SNS usando um AWS SDK
  - Listar tópicos do Amazon SNS usando um AWS SDK
  - Publicar uma mensagem de texto do Amazon SNS com um atributo usando um AWS SDK
  - Publicar uma mensagem de texto SMS do Amazon SNS usando um AWS SDK
  - Publicar em um tópico do Amazon SNS usando um AWS SDK
  - Definir uma fila de mensagens mortas para uma assinatura do Amazon SNS usando o AWS SDK
  - Definir uma política de filtro do Amazon SNS usando um AWS SDK

- Definir as configurações padrão para enviar mensagens SMS do Amazon SNS usando um AWS SDK
- Definir atributos de tópicos do Amazon SNS usando um AWS SDK
- Inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS usando um AWS SDK
- Inscrever uma aplicação móvel em um tópico do Amazon SNS usando um AWS SDK
- Inscrever um endpoint HTTP em um tópico do Amazon SNS usando um AWS SDK
- Assinar uma fila do Amazon SQS em um tópico do Amazon SNS usando um AWS SDK
- Inscrever um endereço de e-mail em um tópico do Amazon SNS usando um AWS SDK
- Assinar com um filtro em um tópico do Amazon SNS usando um AWS SDK

- Cenários para o Amazon SNS usando AWS SDKs
  - Criar um endpoint de plataforma para notificações por push do Amazon SNS usando um AWS SDK
  - Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK
  - Publicar mensagens SMS em um tópico do Amazon SNS usando um AWS SDK
  - Publicar uma mensagem grande no Amazon SNS com o Amazon S3 usando um AWS SDK
  - Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
- Exemplos sem servidor para o Amazon SNS usando AWS SDKs
  - Invocar uma função do Lambda em um acionador do Amazon SNS
- Exemplos de uso entre serviços do Amazon SNS com AWS SDKs
  - Criar uma aplicação para enviar dados para uma tabela do DynamoDB
  - Criar uma aplicação de publicação e assinatura que traduz mensagens
  - Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
  - Criar uma aplicação de exploração do Amazon Textract
  - Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
  - Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
  - Usar o API Gateway para invocar uma função do Lambda
  - Usar eventos programados para chamar uma função do Lambda

Ações para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Notification Service (Amazon SNS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon SNS usando AWS SDKs.

Exemplos

- Adicionar tags a um tópico do Amazon SNS usando um AWS SDK
- Verificar se um número de telefone saiu do Amazon SNS usando um AWS SDK
- Confirmar que um proprietário de endpoint deseja receber mensagens do Amazon SNS usando um AWS SDK
- Criar um tópico do Amazon SNS usando um AWS SDK
- Excluir uma assinatura do Amazon SNS usando um AWS SDK
- Excluir um tópico do Amazon SNS usando um AWS SDK
- Obter as propriedades de um tópico do Amazon SNS usando um AWS SDK
- Obter as configurações para enviar mensagens SMS do Amazon SNS usando um AWS SDK
- Listar números de telefone que saíram do Amazon SNS usando um AWS SDK
- Listar os assinantes de um tópico do Amazon SNS usando um AWS SDK
- Listar tópicos do Amazon SNS usando um AWS SDK
- Publicar uma mensagem de texto do Amazon SNS com um atributo usando um AWS SDK
- Publicar uma mensagem de texto SMS do Amazon SNS usando um AWS SDK
- Publicar em um tópico do Amazon SNS usando um AWS SDK
- Definir uma fila de mensagens mortas para uma assinatura do Amazon SNS usando o AWS SDK
- Definir uma política de filtro do Amazon SNS usando um AWS SDK
- Definir as configurações padrão para enviar mensagens SMS do Amazon SNS usando um AWS SDK
- Definir atributos de tópicos do Amazon SNS usando um AWS SDK
- Inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS usando um AWS SDK
- Inscrever uma aplicação móvel em um tópico do Amazon SNS usando um AWS SDK

- Inscrever um endpoint HTTP em um tópico do Amazon SNS usando um AWS SDK
- Assinar uma fila do Amazon SQS em um tópico do Amazon SNS usando um AWS SDK
- Inscrever um endereço de e-mail em um tópico do Amazon SNS usando um AWS SDK
- Assinar com um filtro em um tópico do Amazon SNS usando um AWS SDK

Adicionar tags a um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como adicionar etiquetas a um tópico do Amazon SNS.

CLI

AWS CLI

Para adicionar uma tag a um tópico

O exemplo `tag-resource` a seguir adiciona uma tag de metadados ao tópico do Amazon SNS especificado.

```
aws sns tag-resource \
    --resource-arn arn:aws:sns:us-west-2:123456789012:MyTopic \
    --tags Key=Team,Value=Alpha
```

Este comando não produz saída.

- Para obter detalhes da API, consulte TagResourceem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.Tag;
```

```
import software.amazon.awssdk.services.sns.model.TagResourceRequest;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AddTags {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic to which tags are added.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        addTopicTags(snsClient, topicArn);
        snsClient.close();
    }

    public static void addTopicTags(SnsClient snsClient, String topicArn) {
        try {
            Tag tag = Tag.builder()
                    .key("Team")
                    .value("Development")
                    .build();
```

```
            Tag tag2 = Tag.builder()
                    .key("Environment")
                    .value("Gamma")
                    .build();

            List<Tag> tagList = new ArrayList<>();
            tagList.add(tag);
            tagList.add(tag2);

            TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                    .resourceArn(topicArn)
                    .tags(tagList)
                    .build();

            snsClient.tagResource(tagResourceRequest);
            System.out.println("Tags have been added to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte TagResourcea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addTopicTags(topicArn: String) {
```

```
    val tag = Tag {
        key = "Team"
        value = "Development"
    }

    val tag2 = Tag {
        key = "Environment"
        value = "Gamma"
    }

    val tagList = mutableListOf<Tag>()
    tagList.add(tag)
    tagList.add(tag2)

    val request = TagResourceRequest {
        resourceArn = topicArn
        tags = tagList
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.tagResource(request)
        println("Tags have been added to $topicArn")
    }
}
```

- Para obter detalhes da API, consulte a TagResourcereferência da API AWSSDK for Kotlin.

Verificar se um número de telefone saiu do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como verificar se um número de telefone cancelou o recebimento de mensagens do Amazon SNS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.Threading.Tasks;
   using Amazon.SimpleNotificationService;
   using Amazon.SimpleNotificationService.Model;

   /// <summary>
   /// This example shows how to use the Amazon Simple Notification Service
   /// (Amazon SNS) to check whether a phone number has been opted out.
   /// </summary>
   public class IsPhoneNumOptedOut
   {
       public static async Task Main()
       {
           string phoneNumber = "+15551112222";

           IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();

           await CheckIfOptedOutAsync(client, phoneNumber);
       }

       /// <summary>
       /// Checks to see if the supplied phone number has been opted out.
       /// </summary>
       /// <param name="client">The initialized Amazon SNS Client object used
       /// to check if the phone number has been opted out.</param>
       /// <param name="phoneNumber">A string representing the phone number
       /// to check.</param>
       public static async Task
CheckIfOptedOutAsync(IAmazonSimpleNotificationService client, string
phoneNumber)
       {
           var request = new CheckIfPhoneNumberIsOptedOutRequest
           {
               PhoneNumber = phoneNumber,
           };

           try
           {
               var response = await
client.CheckIfPhoneNumberIsOptedOutAsync(request);

               if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
```

```
                {
                    string optOutStatus = response.IsOptedOut ? "opted out" :
 "not opted out.";
                    Console.WriteLine($"The phone number: {phoneNumber} is
 {optOutStatus}");
                }
            }
            catch (AuthorizationErrorException ex)
            {
                Console.WriteLine($"{ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para verificar o cancelamento de mensagens SMS para um número de telefone

O exemplo `check-if-phone-number-is-opted-out` a seguir verifica se o número de telefone especificado cancelou o recebimento de mensagens SMS em sua conta da AWS atual.

```
aws sns check-if-phone-number-is-opted-out \
    --phone-number +1555550100
```

Saída:

```
{
    "isOptedOut": false
}
```

- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOutem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import
 software.amazon.awssdk.services.sns.model.CheckIfPhoneNumberIsOptedOutRequest;
import
 software.amazon.awssdk.services.sns.model.CheckIfPhoneNumberIsOptedOutResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CheckOptOut {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <phoneNumber>

                Where:
                   phoneNumber - The mobile phone number to look up (for example,
 +1XXX5550100).

                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String phoneNumber = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        checkPhone(snsClient, phoneNumber);
        snsClient.close();
    }

    public static void checkPhone(SnsClient snsClient, String phoneNumber) {
        try {
            CheckIfPhoneNumberIsOptedOutRequest request =
 CheckIfPhoneNumberIsOptedOutRequest.builder()
                    .phoneNumber(phoneNumber)
                    .build();

            CheckIfPhoneNumberIsOptedOutResponse result =
 snsClient.checkIfPhoneNumberIsOptedOut(request);
            System.out.println(
                    result.isOptedOut() + "Phone Number " + phoneNumber + " has
 Opted Out of receiving sns messages." +
                            "\n\nStatus was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { CheckIfPhoneNumberIsOptedOutCommand } from "@aws-sdk/client-sns";

import { snsClient } from "../libs/snsClient.js";

export const checkIfPhoneNumberIsOptedOut = async (
  phoneNumber = "5555555555",
) => {
  const command = new CheckIfPhoneNumberIsOptedOutCommand({
    phoneNumber,
  });

  const response = await snsClient.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '3341c28a-cdc8-5b39-a3ee-9fb0ee125732',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
```

```
  //     totalRetryDelay: 0
  //   },
  //   isOptedOut: false
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Indicates whether the phone number owner has opted out of receiving SMS
 messages from your AWS SNS account.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
```

```
    'version' => '2010-03-31'
]);

$phone = '+1XXX5550100';

try {
    $result = $SnSclient->checkIfPhoneNumberIsOptedOut([
        'phoneNumber' => $phone,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for PHP da API.

Confirmar que um proprietário de endpoint deseja receber mensagens do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como confirmar que o proprietário de um endpoint deseja receber mensagens do Amazon SNS validando o token enviado para o endpoint por uma ação Subscribe anterior.

CLI

AWS CLI

Para confirmar uma assinatura

O comando `confirm-subscription` a seguir conclui o processo de confirmação iniciado quando você se inscreveu em um tópico do SNS chamado `my-topic`. O parâmetro --token vem da mensagem de confirmação enviada ao endpoint de notificação especificado na chamada de assinatura.

```
aws sns confirm-subscription \
    --topic-arn arn:aws:sns:us-west-2:123456789012:my-topic \
```

```
    --token
 2336412f37fb687f5d51e6e241d7700ae02f7124d8268910b858cb4db727ceeb2474bb937929d3bdd7ce5d0c
```

Saída:

```
{
    "SubscriptionArn": "arn:aws:sns:us-west-2:123456789012:my-
topic:8a21d249-4329-4871-acc6-7be709c6ea7f"
}
```

- Para obter detalhes da API, consulte ConfirmSubscriptionem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ConfirmSubscriptionRequest;
import software.amazon.awssdk.services.sns.model.ConfirmSubscriptionResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ConfirmSubscription {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:    <subscriptionToken> <topicArn>

                Where:
                   subscriptionToken - A short-lived token sent to an endpoint
during the Subscribe action.
                   topicArn - The ARN of the topic.\s
                """;

       if (args.length != 2) {
           System.out.println(usage);
           System.exit(1);
       }

       String subscriptionToken = args[0];
       String topicArn = args[1];
       SnsClient snsClient = SnsClient.builder()
               .region(Region.US_EAST_1)
               .build();

       confirmSub(snsClient, subscriptionToken, topicArn);
       snsClient.close();
   }

   public static void confirmSub(SnsClient snsClient, String subscriptionToken,
String topicArn) {
       try {
           ConfirmSubscriptionRequest request =
ConfirmSubscriptionRequest.builder()
                   .token(subscriptionToken)
                   .topicArn(topicArn)
                   .build();

           ConfirmSubscriptionResponse result =
snsClient.confirmSubscription(request);
           System.out.println("\n\nStatus was " +
result.sdkHttpResponse().statusCode() + "\n\nSubscription Arn: \n\n"
                   + result.subscriptionArn());

       } catch (SnsException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

```
}
```

- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ConfirmSubscriptionCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} token - This token is sent the subscriber. Only subscribers
 *                         that are not AWS services (HTTP/S, email) need to be
 confirmed.
 * @param {string} topicArn - The ARN of the topic for which you wish to confirm
 a subscription.
 */
export const confirmSubscription = async (
  token = "TOKEN",
```

```
  topicArn = "TOPIC_ARN",
) => {
  const response = await snsClient.send(
    // A subscription only needs to be confirmed if the endpoint type is
    // HTTP/S, email, or in another AWS account.
    new ConfirmSubscriptionCommand({
      Token: token,
      TopicArn: topicArn,
      // If this is true, the subscriber cannot unsubscribe while
 unauthenticated.
      AuthenticateOnUnsubscribe: "false",
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '4bb5bce9-805a-5517-8333-e1d2cface90b',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:TOPIC_NAME:xxxxxxxx-
xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for JavaScript da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Verifies an endpoint owner's intent to receive messages by
 * validating the token sent to the endpoint by an earlier Subscribe action.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$subscription_token = 'arn:aws:sns:us-east-1:111122223333:MyTopic:123456-
abcd-12ab-1234-12ba3dc1234a';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->confirmSubscription([
        'Token' => $subscription_token,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
```

```
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for PHP da API.

Criar um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como criar um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico com um nome específico.

```
using System;
using System.Threading.Tasks;
using Amazon.SimpleNotificationService;
using Amazon.SimpleNotificationService.Model;

/// <summary>
/// This example shows how to use Amazon Simple Notification Service
/// (Amazon SNS) to add a new Amazon SNS topic.
/// </summary>
```

```
    public class CreateSNSTopic
    {
        public static async Task Main()
        {
            string topicName = "ExampleSNSTopic";

            IAmazonSimpleNotificationService client = new
 AmazonSimpleNotificationServiceClient();

            var topicArn = await CreateSNSTopicAsync(client, topicName);
            Console.WriteLine($"New topic ARN: {topicArn}");
        }

        /// <summary>
        /// Creates a new SNS topic using the supplied topic name.
        /// </summary>
        /// <param name="client">The initialized SNS client object used to
        /// create the new topic.</param>
        /// <param name="topicName">A string representing the topic name.</param>
        /// <returns>The Amazon Resource Name (ARN) of the created topic.</
returns>
        public static async Task<string>
 CreateSNSTopicAsync(IAmazonSimpleNotificationService client, string topicName)
        {
            var request = new CreateTopicRequest
            {
                Name = topicName,
            };

            var response = await client.CreateTopicAsync(request);

            return response.TopicArn;
        }
    }
```

Crie um tópico com um nome e atributos específicos de FIFO e desduplicação.

```
    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
```

```
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
                { "FifoTopic", "true" }
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
 "true");
            }
        }

        var createResponse = await
 _amazonSNSClient.CreateTopicAsync(createTopicRequest);
        return createResponse.TopicArn;
    }
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicName: An Amazon SNS topic name.
  \param topicARNResult: String to return the Amazon Resource Name (ARN) for the
 topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::createTopic(const Aws::String &topicName,
                              Aws::String &topicARNResult,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::CreateTopicRequest request;
    request.SetName(topicName);

    const Aws::SNS::Model::CreateTopicOutcome outcome =
 snsClient.CreateTopic(request);

    if (outcome.IsSuccess()) {
        topicARNResult = outcome.GetResult().GetTopicArn();
        std::cout << "Successfully created an Amazon SNS topic " << topicName
                  << " with topic ARN '" << topicARNResult
                  << "'." << std::endl;

    }
    else {
        std::cerr << "Error creating topic " << topicName << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
        topicARNResult.clear();
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar um tópico do SNS

O exemplo `create-topic` a seguir cria um tópico do SNS chamado `my-topic`.

```
aws sns create-topic \
    --name my-topic
```

Saída:

```
{
    "ResponseMetadata": {
        "RequestId": "1469e8d7-1642-564e-b85d-a19b4b341f83"
    },
    "TopicArn": "arn:aws:sns:us-west-2:123456789012:my-topic"
}
```

Para obter mais informações, consulte Usar a interface da linha de comando da AWS com o Amazon SQS e o Amazon SNS no Guia do usuário da interface da linha de comando da AWS.

- Para obter detalhes da API, consulte CreateTopicem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreateTopicRequest;
import software.amazon.awssdk.services.sns.model.CreateTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicName>

                Where:
                   topicName - The name of the topic to create (for example,
 mytopic).

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String topicName = args[0];
        System.out.println("Creating a topic with name: " + topicName);
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String arnVal = createSNSTopic(snsClient, topicName);
        System.out.println("The topic ARN is" + arnVal);
        snsClient.close();
    }

    public static String createSNSTopic(SnsClient snsClient, String topicName) {
        CreateTopicResponse result;
        try {
            CreateTopicRequest request = CreateTopicRequest.builder()
                    .name(topicName)
                    .build();

            result = snsClient.createTopic(request);
            return result.topicArn();

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { CreateTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicName - The name of the topic to create.
 */
export const createTopic = async (topicName = "TOPIC_NAME") => {
  const response = await snsClient.send(
    new CreateTopicCommand({ Name: topicName }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '087b8ad2-4593-50c4-a496-d7e90b82cf3e',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:TOPIC_NAME'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createSNSTopic(topicName: String): String {

    val request = CreateTopicRequest {
        name = topicName
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.createTopic(request)
        return result.topicArn.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;
```

```
/**
 * Create a Simple Notification Service topics in your AWS account at the
 requested region.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$topicname = 'myTopic';

try {
    $result = $SnSclient->createTopic([
        'Name' => $topicname,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    def create_topic(self, name):
        """
        Creates a notification topic.

        :param name: The name of the topic to create.
        :return: The newly created topic.
        """
        try:
            topic = self.sns_resource.create_topic(Name=name)
            logger.info("Created topic %s with ARN %s.", name, topic.arn)
        except ClientError:
            logger.exception("Couldn't create topic %s.", name)
            raise
        else:
            return topic
```

- Para obter detalhes da API, consulte a CreateTopicReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# This class demonstrates how to create an Amazon Simple Notification Service
 (SNS) topic.
class SNSTopicCreator
  # Initializes an SNS client.
  #
  # Utilizes the default AWS configuration for region and credentials.
  def initialize
    @sns_client = Aws::SNS::Client.new
  end

  # Attempts to create an SNS topic with the specified name.
  #
  # @param topic_name [String] The name of the SNS topic to create.
  # @return [Boolean] true if the topic was successfully created, false
 otherwise.
  def create_topic(topic_name)
    @sns_client.create_topic(name: topic_name)
    puts "The topic '#{topic_name}' was successfully created."
    true
  rescue Aws::SNS::Errors::ServiceError => e
    # Handles SNS service errors gracefully.
    puts "Error while creating the topic named '#{topic_name}': #{e.message}"
    false
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_name = "YourTopicName" # Replace with your topic name
  sns_topic_creator = SNSTopicCreator.new

  puts "Creating the topic '#{topic_name}'..."
  unless sns_topic_creator.create_topic(topic_name)
    puts "The topic was not created. Stopping program."
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_topic(client: &Client, topic_name: &str) -> Result<(), Error> {
    let resp = client.create_topic().name(topic_name).send().await?;

    println!(
        "Created topic with ARN: {}",
        resp.topic_arn().unwrap_or_default()
    );

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->createtopic( iv_name = iv_topic_name ). " oo_result
 is returned for testing purposes. "
        MESSAGE 'SNS topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
```

```
        MESSAGE 'Unable to create more topics. You have reached the maximum
number of topics allowed.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWS SDK for SAP ABAP.

Excluir uma assinatura do Amazon SNS usando um AWS SDK

Os exemplos de códigos a seguir mostram como excluir uma assinatura do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cancele a assinatura de um tópico por meio de um ARN de assinatura.

```
    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
            {
                SubscriptionArn = subscriptionArn
```

```
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete a subscription to an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param subscriptionARN: The Amazon Resource Name (ARN) for an Amazon SNS topic
 subscription.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::unsubscribe(const Aws::String &subscriptionARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::UnsubscribeRequest request;
    request.SetSubscriptionArn(subscriptionARN);

    const Aws::SNS::Model::UnsubscribeOutcome outcome =
 snsClient.Unsubscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Unsubscribed successfully " << std::endl;
    }
    else {
```

```
        std::cerr << "Error while unsubscribing " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for C ++.

CLI

AWS CLI

Para cancelar a assinatura de um tópico

O exemplo `unsubscribe` a seguir exclui a assinatura especificada de um tópico.

```
aws sns unsubscribe \
    --subscription-arn arn:aws:sns:us-west-2:0123456789012:my-
topic:8a21d249-4329-4871-acc6-7be709c6ea7f
```

Este comando não produz saída.

- Para obter detalhes da API, consulte Unsubscribe na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
```

```
import software.amazon.awssdk.services.sns.model.UnsubscribeRequest;
import software.amazon.awssdk.services.sns.model.UnsubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class Unsubscribe {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <subscriptionArn>

                Where:
                   subscriptionArn - The ARN of the subscription to delete.
                """;

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String subscriptionArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        unSub(snsClient, subscriptionArn);
        snsClient.close();
    }

    public static void unSub(SnsClient snsClient, String subscriptionArn) {
        try {
            UnsubscribeRequest request = UnsubscribeRequest.builder()
                    .subscriptionArn(subscriptionArn)
                    .build();

            UnsubscribeResponse result = snsClient.unsubscribe(request);
```

```
            System.out.println("\n\nStatus was " +
 result.sdkHttpResponse().statusCode()
                    + "\n\nSubscription was removed for " +
 request.subscriptionArn());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { UnsubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";
```

```
/**
 * @param {string} subscriptionArn - The ARN of the subscription to cancel.
 */
const unsubscribe = async (
  subscriptionArn = "arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic:xxxxxxxx-xxxx-
xxxx-xxxx-xxxxxxxxxxxx",
) => {
  const response = await snsClient.send(
    new UnsubscribeCommand({
      SubscriptionArn: subscriptionArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '0178259a-9204-507c-b620-78a7570a44c6',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun unSub(subscriptionArnVal: String) {

    val request = UnsubscribeRequest {
        subscriptionArn = subscriptionArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.unsubscribe(request)
        println("Subscription was removed for ${request.subscriptionArn}")
    }
}
```

- Para obter detalhes da API, consulte Unsubscribe (Cancelar assinatura) na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Deletes a subscription to an Amazon SNS topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
```

```
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$subscription = 'arn:aws:sns:us-east-1:111122223333:MySubscription';

try {
    $result = $SnSclient->unsubscribe([
        'SubscriptionArn' => $subscription,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    @staticmethod
    def delete_subscription(subscription):
        """
        Unsubscribes and deletes a subscription.
        """
        try:
            subscription.delete()
            logger.info("Deleted subscription %s.", subscription.arn)
        except ClientError:
            logger.exception("Couldn't delete subscription %s.",
subscription.arn)
            raise
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sns->unsubscribe( iv_subscriptionarn = iv_subscription_arn ).
        MESSAGE 'Subscription deleted.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Subscription does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snsinvalidparameterex.
        MESSAGE 'Subscription with "PendingConfirmation" status cannot be
deleted/unsubscribed. Confirm subscription before performing unsubscribe
operation.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte Cancelar assinatura na Referência da API do AWS SDK para SAP ABAP.

Excluir um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um tópico por meio do respectivo ARN.

```
/// <summary>
/// Delete a topic by its topic ARN.
/// </summary>
/// <param name="topicArn">The ARN of the topic.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteTopicByArn(string topicArn)
{
    var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
        new DeleteTopicRequest()
        {
            TopicArn = topicArn
        });
    return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::deleteTopic(const Aws::String &topicARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::DeleteTopicRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted the Amazon SNS topic " << topicARN <<
 std::endl;
    }
    else {
        std::cerr << "Error deleting topic " << topicARN << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para excluir um tópico do SNS

O exemplo `delete-topic` a seguir exclui o tópico do SNS especificado.

```
aws sns delete-topic \
    --topic-arn "arn:aws:sns:us-west-2:123456789012:my-topic"
```

Este comando não produz saída.

- Para obter detalhes da API, consulte DeleteTopicem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
```

```
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.DeleteTopicRequest;
import software.amazon.awssdk.services.sns.model.DeleteTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:     <topicArn>
```

```
                Where:
                   topicArn - The ARN of the topic to delete.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println("Deleting a topic with name: " + topicArn);
        deleteSNSTopic(snsClient, topicArn);
        snsClient.close();
    }

    public static void deleteSNSTopic(SnsClient snsClient, String topicArn) {
        try {
            DeleteTopicRequest request = DeleteTopicRequest.builder()
                    .topicArn(topicArn)
                    .build();

            DeleteTopicResponse result = snsClient.deleteTopic(request);
            System.out.println("\n\nStatus was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { DeleteTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic to delete.
 */
export const deleteTopic = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new DeleteTopicCommand({ TopicArn: topicArn }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'a10e2886-5a8f-5114-af36-75bd39498332',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
```

```
  // }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSNSTopic(topicArnVal: String) {

    val request = DeleteTopicRequest {
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.deleteTopic(request)
        println("$topicArnVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteTopicreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Deletes an SNS topic and all its subscriptions.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->deleteTopic([
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def delete_topic(topic):
        """
        Deletes a topic. All subscriptions to the topic are also deleted.
        """
        try:
            topic.delete()
            logger.info("Deleted topic %s.", topic.arn)
        except ClientError:
            logger.exception("Couldn't delete topic %s.", topic.arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteTopicReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_sns->deletetopic( iv_topicarn = iv_topic_arn ).
    MESSAGE 'SNS topic deleted.' TYPE 'I'.
  CATCH /aws1/cx_snsnotfoundexception.
    MESSAGE 'Topic does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteTopicreferência da API AWS SDK for SAP ABAP.

Obter as propriedades de um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como obter as propriedades de um tópico do Amazon SNS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.SimpleNotificationService;
```

```
    /// <summary>
    /// This example shows how to retrieve the attributes of an Amazon Simple
    /// Notification Service (Amazon SNS) topic.
    /// </summary>
    public class GetTopicAttributes
    {
        public static async Task Main()
        {
            string topicArn = "arn:aws:sns:us-
west-2:000000000000:ExampleSNSTopic";
            IAmazonSimpleNotificationService client = new
 AmazonSimpleNotificationServiceClient();

            var attributes = await GetTopicAttributesAsync(client, topicArn);
            DisplayTopicAttributes(attributes);
        }

        /// <summary>
        /// Given the ARN of the Amazon SNS topic, this method retrieves the
 topic
        /// attributes.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object used
        /// to retrieve the attributes for the Amazon SNS topic.</param>
        /// <param name="topicArn">The ARN of the topic for which to retrieve
        /// the attributes.</param>
        /// <returns>A Dictionary of topic attributes.</returns>
        public static async Task<Dictionary<string, string>>
 GetTopicAttributesAsync(
            IAmazonSimpleNotificationService client,
            string topicArn)
        {
            var response = await client.GetTopicAttributesAsync(topicArn);

            return response.Attributes;
        }

        /// <summary>
        /// This method displays the attributes for an Amazon SNS topic.
        /// </summary>
        /// <param name="topicAttributes">A Dictionary containing the
        /// attributes for an Amazon SNS topic.</param>
```

```
        public static void DisplayTopicAttributes(Dictionary<string, string>
 topicAttributes)
        {
            foreach (KeyValuePair<string, string> entry in topicAttributes)
            {
                Console.WriteLine($"{entry.Key}: {entry.Value}\n");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the properties of an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::getTopicAttributes(const Aws::String &topicARN,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);
    Aws::SNS::Model::GetTopicAttributesRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::GetTopicAttributesOutcome outcome =
 snsClient.GetTopicAttributes(
```

```
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Topic Attributes:" << std::endl;
        for (auto const &attribute: outcome.GetResult().GetAttributes()) {
            std::cout << "  * " << attribute.first << " : " << attribute.second
                      << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting Topic attributes "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para recuperar os atributos de um tópico

O exemplo `get-topic-attributes` a seguir exibe os atributos do tópico especificado.

```
aws sns get-topic-attributes \
    --topic-arn "arn:aws:sns:us-west-2:123456789012:my-topic"
```

Saída:

```
{
    "Attributes": {
        "SubscriptionsConfirmed": "1",
        "DisplayName": "my-topic",
        "SubscriptionsDeleted": "0",
        "EffectiveDeliveryPolicy": "{\"http\":{\"defaultHealthyRetryPolicy
\":{\"minDelayTarget\":20,\"maxDelayTarget\":20,\"numRetries\":3,
```

```
\"numMaxDelayRetries\":0,\"numNoDelayRetries\":0,\"numMinDelayRetries\":0,
\"backoffFunction\":\"linear\"},\"disableSubscriptionOverrides\":false}}",
        "Owner": "123456789012",
        "Policy": "{\"Version\":\"2008-10-17\",\"Id\":\"__default_policy_ID
\",\"Statement\":[{\"Sid\":\"__default_statement_ID\",\"Effect\":
\"Allow\",\"Principal\":{\"AWS\":\"*\"},\"Action\":[\"SNS:Subscribe\",
\"SNS:ListSubscriptionsByTopic\",\"SNS:DeleteTopic\",\"SNS:GetTopicAttributes
\",\"SNS:Publish\",\"SNS:RemovePermission\",\"SNS:AddPermission\",
\"SNS:SetTopicAttributes\"],\"Resource\":\"arn:aws:sns:us-west-2:123456789012:my-
topic\",\"Condition\":{\"StringEquals\":{\"AWS:SourceOwner\":
\"0123456789012\"}}}]}",
        "TopicArn": "arn:aws:sns:us-west-2:123456789012:my-topic",
        "SubscriptionsPending": "0"
    }
}
```

- Para obter detalhes da API, consulte GetTopicAttributesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.GetTopicAttributesRequest;
import software.amazon.awssdk.services.sns.model.GetTopicAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetTopicAttributes {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic to look up.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println("Getting attributes for a topic with name: " +
 topicArn);
        getSNSTopicAttributes(snsClient, topicArn);
        snsClient.close();
    }

    public static void getSNSTopicAttributes(SnsClient snsClient, String
 topicArn) {
        try {
            GetTopicAttributesRequest request =
 GetTopicAttributesRequest.builder()
                    .topicArn(topicArn)
                    .build();

            GetTopicAttributesResponse result =
 snsClient.getTopicAttributes(request);
            System.out.println("\n\nStatus is " +
 result.sdkHttpResponse().statusCode() + "\n\nAttributes: \n\n"
                    + result.attributes());

        } catch (SnsException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { GetTopicAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic to retrieve attributes for.
 */
export const getTopicAttributes = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new GetTopicAttributesCommand({
```

```
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '36b6a24e-5473-5d4e-ac32-ff72d9a73d94',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Attributes: {
  //     Policy: '{...}',
  //     Owner: 'xxxxxxxxxxxx',
  //     SubscriptionsPending: '1',
  //     TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic',
  //     TracingConfig: 'PassThrough',
  //     EffectiveDeliveryPolicy: '{"http":{"defaultHealthyRetryPolicy":
{"minDelayTarget":20,"maxDelayTarget":20,"numRetries":3,"numMaxDelayRetries":0,"numNoDela
{"headerContentType":"text/plain; charset=UTF-8"}}}',
  //     SubscriptionsConfirmed: '0',
  //     DisplayName: '',
  //     SubscriptionsDeleted: '1'
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set region
AWS.config.update({ region: "REGION" });

// Create promise and SNS service object
var getTopicAttribsPromise = new AWS.SNS({ apiVersion: "2010-03-31" })
  .getTopicAttributes({ TopicArn: "TOPIC_ARN" })
  .promise();

// Handle promise's fulfilled/rejected states
getTopicAttribsPromise
  .then(function (data) {
    console.log(data);
  })
  .catch(function (err) {
    console.error(err, err.stack);
  });
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSNSTopicAttributes(topicArnVal: String) {

    val request = GetTopicAttributesRequest {
```

```
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.getTopicAttributes(request)
        println("${result.attributes}")
    }
}
```

- Para obter detalhes da API, consulte a GetTopicAttributesreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->getTopicAttributes([
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for PHP da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_sns->gettopicattributes( iv_topicarn = iv_topic_arn ). "
oo_result is returned for testing purposes. "
       DATA(lt_attributes) = oo_result->get_attributes( ).
       MESSAGE 'Retrieved attributes/properties of a topic.' TYPE 'I'.
     CATCH /aws1/cx_snsnotfoundexception.
       MESSAGE 'Topic does not exist.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a GetTopicAttributesreferência da API AWS SDK for SAP ABAP.

Obter as configurações para enviar mensagens SMS do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como obter as configurações para enviar mensagens SMS do Amazon SNS.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the default settings for sending SMS messages from your AWS account
 by using
//! Amazon Simple Notification Service (Amazon SNS).
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::getSMSType(const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::GetSMSAttributesRequest request;
    //Set the request to only retrieve the DefaultSMSType setting.
    //Without the following line, GetSMSAttributes would retrieve all settings.
    request.AddAttributes("DefaultSMSType");

    const Aws::SNS::Model::GetSMSAttributesOutcome outcome =
 snsClient.GetSMSAttributes(
            request);

    if (outcome.IsSuccess()) {
        const Aws::Map<Aws::String, Aws::String> attributes =
                outcome.GetResult().GetAttributes();
        if (!attributes.empty()) {
            for (auto const &att: attributes) {
                std::cout << att.first << ":  " << att.second << std::endl;
            }
        }
        else {
            std::cout
```

```
                    << "AwsDoc::SNS::getSMSType - an empty map of attributes was
 retrieved."
                    << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Para listar os atributos padrão da mensagem SMS

O exemplo `get-sms-attributes` a seguir lista os atributos padrão para o envio de mensagens SMS.

```
aws sns get-sms-attributes
```

Saída:

```
{
    "attributes": {
        "DefaultSenderID": "MyName"
    }
}
```

- Para obter detalhes da API, consulte GetSMSAttributes na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import
 software.amazon.awssdk.services.sns.model.GetSubscriptionAttributesRequest;
import
 software.amazon.awssdk.services.sns.model.GetSubscriptionAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.Iterator;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetSMSAtrributes {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic from which to retrieve
 attributes.
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        getSNSAttrutes(snsClient, topicArn);
        snsClient.close();
    }

    public static void getSNSAttrutes(SnsClient snsClient, String topicArn) {
        try {
            GetSubscriptionAttributesRequest request =
 GetSubscriptionAttributesRequest.builder()
                    .subscriptionArn(topicArn)
                    .build();

            // Get the Subscription attributes
            GetSubscriptionAttributesResponse res =
 snsClient.getSubscriptionAttributes(request);
            Map<String, String> map = res.attributes();

            // Iterate through the map
            Iterator iter = map.entrySet().iterator();
            while (iter.hasNext()) {
                Map.Entry entry = (Map.Entry) iter.next();
                System.out.println("[Key] : " + entry.getKey() + " [Value] : " +
 entry.getValue());
            }

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        System.out.println("\n\nStatus was good");
    }
}
```

- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { GetSMSAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const getSmsAttributes = async () => {
  const response = await snsClient.send(
    // If you have not modified the account-level mobile settings of SNS,
    // the DefaultSMSType is undefined. For this example, it was set to
    // Transactional.
    new GetSMSAttributesCommand({ attributes: ["DefaultSMSType"] }),
  );

  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '67ad8386-4169-58f1-bdb9-debd281d48d5',
```

```
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   attributes: { DefaultSMSType: 'Transactional' }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for JavaScript.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Get the type of SMS Message sent by default from the AWS SNS service.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
```

```
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->getSMSAttributes([
        'attributes' => ['DefaultSMSType'],
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for PHP.

Listar números de telefone que saíram do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como listar números de telefone que optaram por não receber mensagens do Amazon SNS.

CLI

AWS CLI

Para listar as opções de cancelamento de mensagens SMS

O exemplo `list-phone-numbers-opted-out` a seguir lista os números de telefone que optaram por não receber mensagens SMS.

```
aws sns list-phone-numbers-opted-out
```

Saída:

```
{
```

```
    "phoneNumbers": [
        "+15555550100"
    ]
}
```

- Para obter detalhes da API, consulte ListPhoneNumbersOptedOutem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListPhoneNumbersOptedOutRequest;
import
 software.amazon.awssdk.services.sns.model.ListPhoneNumbersOptedOutResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListOptOut {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listOpts(snsClient);
```

```
        snsClient.close();
    }

    public static void listOpts(SnsClient snsClient) {
        try {
            ListPhoneNumbersOptedOutRequest request =
 ListPhoneNumbersOptedOutRequest.builder().build();
            ListPhoneNumbersOptedOutResponse result =
 snsClient.listPhoneNumbersOptedOut(request);
            System.out.println("Status is " +
 result.sdkHttpResponse().statusCode() + "\n\nPhone Numbers: \n\n"
                    + result.phoneNumbers());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListPhoneNumbersOptedOuta Referência AWS SDK for Java 2.x da API.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
```

```
 * Returns a list of phone numbers that are opted out of receiving SMS messages
 from your AWS SNS account.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listPhoneNumbersOptedOut();
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte ListPhoneNumbersOptedOuta Referência AWS SDK for PHP da API.

Listar os assinantes de um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como recuperar a lista de assinantes de um tópico do Amazon SNS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// This example will retrieve a list of the existing Amazon Simple
    /// Notification Service (Amazon SNS) subscriptions.
    /// </summary>
    public class ListSubscriptions
    {
        public static async Task Main()
        {
            IAmazonSimpleNotificationService client = new
 AmazonSimpleNotificationServiceClient();

            Console.WriteLine("Enter a topic ARN to list subscriptions for a
 specific topic, " +
                              "or press Enter to list subscriptions for all
 topics.");
            var topicArn = Console.ReadLine();
            Console.WriteLine();

            var subscriptions = await GetSubscriptionsListAsync(client,
 topicArn);

            DisplaySubscriptionList(subscriptions);
        }

        /// <summary>
        /// Gets a list of the existing Amazon SNS subscriptions, optionally by
 specifying a topic ARN.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object used
        /// to obtain the list of subscriptions.</param>
        /// <param name="topicArn">The optional ARN of a specific topic. Defaults
 to null.</param>
        /// <returns>A list containing information about each subscription.</
returns>
        public static async Task<List<Subscription>>
 GetSubscriptionsListAsync(IAmazonSimpleNotificationService client, string
 topicArn = null)
```

```
        {
            var results = new List<Subscription>();

            if (!string.IsNullOrEmpty(topicArn))
            {
                var paginateByTopic = client.Paginators.ListSubscriptionsByTopic(
                    new ListSubscriptionsByTopicRequest()
                    {
                        TopicArn = topicArn,
                    });

                // Get the entire list using the paginator.
                await foreach (var subscription in paginateByTopic.Subscriptions)
                {
                    results.Add(subscription);
                }
            }
            else
            {
                var paginateAllSubscriptions =
client.Paginators.ListSubscriptions(new ListSubscriptionsRequest());

                // Get the entire list using the paginator.
                await foreach (var subscription in
paginateAllSubscriptions.Subscriptions)
                {
                    results.Add(subscription);
                }
            }

            return results;
        }

        /// <summary>
        /// Display a list of Amazon SNS subscription information.
        /// </summary>
        /// <param name="subscriptionList">A list containing details for existing
        /// Amazon SNS subscriptions.</param>
        public static void DisplaySubscriptionList(List<Subscription>
subscriptionList)
        {
            foreach (var subscription in subscriptionList)
            {
                Console.WriteLine($"Owner: {subscription.Owner}");
```

```
                Console.WriteLine($"Subscription ARN:
 {subscription.SubscriptionArn}");
                Console.WriteLine($"Topic ARN: {subscription.TopicArn}");
                Console.WriteLine($"Endpoint: {subscription.Endpoint}");
                Console.WriteLine($"Protocol: {subscription.Protocol}");
                Console.WriteLine();
            }
        }
    }
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS)
 subscriptions.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::listSubscriptions(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
    Aws::Vector<Aws::SNS::Model::Subscription> subscriptions;
    do {
        Aws::SNS::Model::ListSubscriptionsRequest request;
```

```
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListSubscriptionsOutcome outcome =
 snsClient.ListSubscriptions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::SNS::Model::Subscription> &newSubscriptions =
                    outcome.GetResult().GetSubscriptions();
            subscriptions.insert(subscriptions.cend(), newSubscriptions.begin(),
                                 newSubscriptions.end());
        }
        else {
            std::cerr << "Error listing subscriptions "
                      << outcome.GetError().GetMessage()
                      <<
                      std::endl;
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    if (result) {
        if (subscriptions.empty()) {
            std::cout << "No subscriptions found" << std::endl;
        }
        else {
            std::cout << "Subscriptions list:" << std::endl;
            for (auto const &subscription: subscriptions) {
                std::cout << "  * " << subscription.GetSubscriptionArn() <<
 std::endl;
            }
        }
    }
    return result;
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para listar suas assinaturas do SNS

O exemplo `list-subscriptions` a seguir exibe uma lista das assinaturas do SNS em sua conta da AWS.

```
aws sns list-subscriptions
```

Saída:

```
{
    "Subscriptions": [
        {
            "Owner": "123456789012",
            "Endpoint": "my-email@example.com",
            "Protocol": "email",
            "TopicArn": "arn:aws:sns:us-west-2:123456789012:my-topic",
            "SubscriptionArn": "arn:aws:sns:us-west-2:123456789012:my-
topic:8a21d249-4329-4871-acc6-7be709c6ea7f"
        }
    ]
}
```

- Para obter detalhes da API, consulte ListSubscriptionsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListSubscriptionsRequest;
import software.amazon.awssdk.services.sns.model.ListSubscriptionsResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListSubscriptions {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSNSSubscriptions(snsClient);
        snsClient.close();
    }

    public static void listSNSSubscriptions(SnsClient snsClient) {
        try {
            ListSubscriptionsRequest request = ListSubscriptionsRequest.builder()
                    .build();

            ListSubscriptionsResponse result =
 snsClient.listSubscriptions(request);
            System.out.println(result.subscriptions());

        } catch (SnsException e) {

            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListSubscriptionsByTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic for which you wish to list
 subscriptions.
 */
export const listSubscriptionsByTopic = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new ListSubscriptionsByTopicCommand({ TopicArn: topicArn }),
  );

  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
```

```
  //     requestId: '0934fedf-0c4b-572e-9ed2-a3e38fadb0c8',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Subscriptions: [
  //     {
  //       SubscriptionArn: 'PendingConfirmation',
  //       Owner: '901487484989',
  //       Protocol: 'email',
  //       Endpoint: 'corepyle@amazon.com',
  //       TopicArn: 'arn:aws:sns:us-east-1:901487484989:mytopic'
  //     }
  //   ]
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSNSSubscriptions() {

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.listSubscriptions(ListSubscriptionsRequest {})
        response.subscriptions?.forEach { sub ->
            println("Sub ARN is ${sub.subscriptionArn}")
```

```
            println("Sub protocol is ${sub.protocol}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListSubscriptionsreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Returns a list of Amazon SNS subscriptions in the requested region.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listSubscriptions();
```

```
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    def list_subscriptions(self, topic=None):
        """
        Lists subscriptions for the current account, optionally limited to a
        specific topic.

        :param topic: When specified, only subscriptions to this topic are
 returned.
        :return: An iterator that yields the subscriptions.
        """
        try:
```

```
            if topic is None:
                subs_iter = self.sns_resource.subscriptions.all()
            else:
                subs_iter = topic.subscriptions.all()
            logger.info("Got subscriptions.")
        except ClientError:
            logger.exception("Couldn't get subscriptions.")
            raise
        else:
            return subs_iter
```

- Para obter detalhes da API, consulte a ListSubscriptionsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# This class demonstrates how to list subscriptions to an Amazon Simple
 Notification Service (SNS) topic
class SnsSubscriptionLister
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Lists subscriptions for a given SNS topic
  # @param topic_arn [String] The ARN of the SNS topic
  # @return [Types::ListSubscriptionsResponse] subscriptions: The response object
  def list_subscriptions(topic_arn)
    @logger.info("Listing subscriptions for topic: #{topic_arn}")
    subscriptions = @sns_client.list_subscriptions_by_topic(topic_arn: topic_arn)
    subscriptions.subscriptions.each do |subscription|
```

```
      @logger.info("Subscription endpoint: #{subscription.endpoint}")
    end
    subscriptions
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error listing subscriptions: #{e.message}")
    raise
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  sns_client = Aws::SNS::Client.new
  topic_arn = "SNS_TOPIC_ARN" # Replace with your SNS topic ARN
  lister = SnsSubscriptionLister.new(sns_client)

  begin
    lister.list_subscriptions(topic_arn)
  rescue StandardError => e
    puts "Failed to list subscriptions: #{e.message}"
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->listsubscriptions( ).                " oo_result is
returned for testing purposes. "
```

```
        DATA(lt_subscriptions) = oo_result->get_subscriptions( ).
        MESSAGE 'Retrieved list of subscribers.' TYPE 'I'.
      CATCH /aws1/cx_rt_generic.
        MESSAGE 'Unable to list subscribers.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListSubscriptionsreferência da API AWS SDK for SAP ABAP.

Listar tópicos do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como listar tópicos do Amazon SNS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// Lists the Amazon Simple Notification Service (Amazon SNS)
    /// topics for the current account.
    /// </summary>
    public class ListSNSTopics
    {
        public static async Task Main()
        {
            IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();
```

```
            await GetTopicListAsync(client);
        }

        /// <summary>
        /// Retrieves the list of Amazon SNS topics in groups of up to 100
        /// topics.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object used
        /// to retrieve the list of topics.</param>
        public static async Task
GetTopicListAsync(IAmazonSimpleNotificationService client)
        {
            // If there are more than 100 Amazon SNS topics, the call to
            // ListTopicsAsync will return a value to pass to the
            // method to retrieve the next 100 (or less) topics.
            string nextToken = string.Empty;

            do
            {
                var response = await client.ListTopicsAsync(nextToken);
                DisplayTopicsList(response.Topics);
                nextToken = response.NextToken;
            }
            while (!string.IsNullOrEmpty(nextToken));
        }

        /// <summary>
        /// Displays the list of Amazon SNS Topic ARNs.
        /// </summary>
        /// <param name="topicList">The list of Topic ARNs.</param>
        public static void DisplayTopicsList(List<Topic> topicList)
        {
            foreach (var topic in topicList)
            {
                Console.WriteLine($"{topic.TopicArn}");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS) topics.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::listTopics(const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
    do {
        Aws::SNS::Model::ListTopicsRequest request;

        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListTopicsOutcome outcome = snsClient.ListTopics(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Topics list:" << std::endl;
            for (auto const &topic: outcome.GetResult().GetTopics()) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
        else {
            std::cerr << "Error listing topics " <<
 outcome.GetError().GetMessage() <<
                      std::endl;
```

```
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    return result;
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Listar os tópicos do SNS

O exemplo `list-topics` a seguir lista todos os tópicos do SNS em sua conta da AWS.

```
aws sns list-topics
```

Saída:

```
{
    "Topics": [
        {
            "TopicArn": "arn:aws:sns:us-west-2:123456789012:my-topic"
        }
    ]
}
```

- Para obter detalhes da API, consulte ListTopicsem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sns"
 "github.com/aws/aws-sdk-go-v2/service/sns/types"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Notification
 Service
// (Amazon SNS) client and list the topics in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 snsClient := sns.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the topics for your account.")
 var topics []types.Topic
 paginator := sns.NewListTopicsPaginator(snsClient, &sns.ListTopicsInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
```

```
  if err != nil {
   log.Printf("Couldn't get topics. Here's why: %v\n", err)
   break
  } else {
   topics = append(topics, output.Topics...)
  }
 }
 if len(topics) == 0 {
  fmt.Println("You don't have any topics!")
 } else {
  for _, topic := range topics {
   fmt.Printf("\t%v\n", *topic.TopicArn)
  }
 }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListTopicsRequest;
import software.amazon.awssdk.services.sns.model.ListTopicsResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListTopics {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSNSTopics(snsClient);
        snsClient.close();
    }

    public static void listSNSTopics(SnsClient snsClient) {
        try {
            ListTopicsRequest request = ListTopicsRequest.builder()
                    .build();

            ListTopicsResponse result = snsClient.listTopics(request);
            System.out.println(
                    "Status was " + result.sdkHttpResponse().statusCode() + "\n
\nTopics\n\n" + result.topics());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListTopicsCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const listTopics = async () => {
  const response = await snsClient.send(new ListTopicsCommand({}));
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '936bc5ad-83ca-53c2-b0b7-9891167b909e',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Topics: [ { TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic' } ]
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSNSTopics() {

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.listTopics(ListTopicsRequest { })
        response.topics?.forEach { topic ->
            println("The topic ARN is ${topic.topicArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
```

```
 * Returns a list of the requester's topics from your AWS SNS account in the
 region specified.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listTopics();
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for PHP da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
```

```
        """
        self.sns_resource = sns_resource


    def list_topics(self):
        """
        Lists topics for the current account.

        :return: An iterator that yields the topics.
        """
        try:
            topics_iter = self.sns_resource.topics.all()
            logger.info("Got topics.")
        except ClientError:
            logger.exception("Couldn't get topics.")
            raise
        else:
            return topics_iter
```

- Para obter detalhes da API, consulte a ListTopicsReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-sns"  # v2: require 'aws-sdk'

def list_topics?(sns_client)
  sns_client.topics.each do |topic|
    puts topic.arn
rescue StandardError => e
```

```
  puts "Error while listing the topics: #{e.message}"
  end
end

def run_me

  region = "REGION"
  sns_client = Aws::SNS::Resource.new(region: region)

  puts "Listing the topics."

  if list_topics?(sns_client)
  else
    puts "The bucket was not created. Stopping program."
    exit 1
  end
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_topics(client: &Client) -> Result<(), Error> {
    let resp = client.list_topics().send().await?;

    println!("Topic ARNs:");
```

```
    for topic in resp.topics() {
        println!("{}", topic.topic_arn().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->listtopics( ).            " oo_result is returned for
testing purposes. "
        DATA(lt_topics) = oo_result->get_topics( ).
        MESSAGE 'Retrieved list of topics.' TYPE 'I'.
      CATCH /aws1/cx_rt_generic.
        MESSAGE 'Unable to list topics.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWS SDK for SAP ABAP.

Publicar uma mensagem de texto do Amazon SNS com um atributo usando um AWS SDK

Os exemplos de código a seguir mostram como publicar uma mensagem com um atributo usando o Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico com opções de grupo, duplicação e atributo.

```
    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is
a sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must
set a message group ID." +
                                  "\r\nAll messages within the same group will be
received in the order " +
```

```
                                "they were published.");

                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID
for this message:", "1");

                if (!_useContentBasedDeduplication)
                {
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                      "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this
message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID
for this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
                    }
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?",
false);
```

```
        }
    }
```

Aplique as seleções do usuário à ação de publicação.

```
    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</
param>
    /// <param name="attributeValue">The optional attribute value for the
 message.</param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
```

```
                    { attributeName!, new MessageAttributeValue() { StringValue =
attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await
_amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        static const Aws::String TONE_ATTRIBUTE("tone");
        static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
"serious",
                                                        "sincere"};

        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
```

```
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent
 to all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered
 according to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Go.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico com opções de grupo, duplicação e atributo.

```
async publishMessages() {
  const message = await this.prompter.input({
    message: MESSAGES.publishMessagePrompt,
  });

  let groupId, deduplicationId, choices;

  if (this.isFifo) {
    await this.logger.log(MESSAGES.groupIdNotice);
    groupId = await this.prompter.input({
      message: MESSAGES.groupIdPrompt,
    });

    if (this.autoDedup === false) {
      await this.logger.log(MESSAGES.deduplicationIdNotice);
      deduplicationId = await this.prompter.input({
        message: MESSAGES.deduplicationIdPrompt,
      });
    }

    choices = await this.prompter.checkbox({
      message: MESSAGES.messageAttributesPrompt,
      choices: toneChoices,
    });
  }
```

```
    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });

    if (publishAnother) {
      await this.publishMessages();
    }
  }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for JavaScript.

Publicar uma mensagem de texto SMS do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como publicar mensagens SMS usando o Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace SNSMessageExample
{
    using System;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    public class SNSMessage
    {
        private AmazonSimpleNotificationServiceClient snsClient;

        /// <summary>
        /// Initializes a new instance of the <see cref="SNSMessage"/> class.
        /// Constructs a new SNSMessage object initializing the Amazon Simple
        /// Notification Service (Amazon SNS) client using the supplied
        /// Region endpoint.
        /// </summary>
        /// <param name="regionEndpoint">The Amazon Region endpoint to use in
        /// sending test messages with this object.</param>
        public SNSMessage(RegionEndpoint regionEndpoint)
        {
            snsClient = new
 AmazonSimpleNotificationServiceClient(regionEndpoint);
        }
```

```
        /// <summary>
        /// Sends the SMS message passed in the text parameter to the phone
 number
        /// in phoneNum.
        /// </summary>
        /// <param name="phoneNum">The ten-digit phone number to which the text
        /// message will be sent.</param>
        /// <param name="text">The text of the message to send.</param>
        /// <returns>Async task.</returns>
        public async Task SendTextMessageAsync(string phoneNum, string text)
        {
            if (string.IsNullOrEmpty(phoneNum) || string.IsNullOrEmpty(text))
            {
                return;
            }

            // Now actually send the message.
            var request = new PublishRequest
            {
                Message = text,
                PhoneNumber = phoneNum,
            };

            try
            {
                var response = await snsClient.PublishAsync(request);
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error sending message: {ex}");
            }
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Publish SMS: use Amazon Simple Notification Service (Amazon SNS) to send an
 SMS text message to a phone number.
 * Note: This requires additional AWS configuration prior to running example.
 *
 *  NOTE: When you start using Amazon SNS to send SMS messages, your AWS account
 is in the SMS sandbox and you can only
 *  use verified destination phone numbers. See https://docs.aws.amazon.com/sns/
latest/dg/sns-sms-sandbox.html.
 *  NOTE: If destination is in the US, you also have an additional restriction
 that you have use a dedicated
 *  origination ID (phone number). You can request an origination number using
 Amazon Pinpoint for a fee.
 *  See https://aws.amazon.com/blogs/compute/provisioning-and-using-10dlc-
origination-numbers-with-amazon-sns/
 *  for more information.
 *
 *  <phone_number_value> input parameter uses E.164 format.
 *  For example, in United States, this input value should be of the form:
 +12223334444
 */

//! Send an SMS text message to a phone number.
/*!
  \param message: The message to publish.
  \param phoneNumber: The phone number of the recipient in E.164 format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishSms(const Aws::String &message,
                             const Aws::String &phoneNumber,
```

```
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
    request.SetMessage(message);
    request.SetPhoneNumber(phoneNumber);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with message id, '"
                  << outcome.GetResult().GetMessageId() << "'."
                  << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PublishTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <phoneNumber>

                Where:
                   message - The message text to send.
                   phoneNumber - The mobile phone number to which a message is
 sent (for example, +1XXX5550100).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTextSMS(snsClient, message, phoneNumber);
        snsClient.close();
    }

    public static void pubTextSMS(SnsClient snsClient, String message, String
 phoneNumber) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .phoneNumber(phoneNumber)
                    .build();
```

```
            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Java 2.x.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun pubTextSMS(messageVal: String?, phoneNumberVal: String?) {

    val request = PublishRequest {
        message = messageVal
        phoneNumber = phoneNumberVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.publish(request)
        println("${result.messageId} message sent.")
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Sends a text message (SMS message) directly to a phone number using Amazon
 SNS.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$message = 'This message is sent from a Amazon SNS code sample.';
$phone = '+1XXX5550100';

try {
    $result = $SnSclient->publish([
        'Message' => $message,
        'PhoneNumber' => $phone,
```

```
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    def publish_text_message(self, phone_number, message):
        """
        Publishes a text message directly to a phone number without need for a
        subscription.

        :param phone_number: The phone number that receives the message. This
 must be
                             in E.164 format. For example, a United States phone
                             number might be +12065550101.
```

```
        :param message: The message to send.
        :return: The ID of the message.
        """
        try:
            response = self.sns_resource.meta.client.publish(
                PhoneNumber=phone_number, Message=message
            )
            message_id = response["MessageId"]
            logger.info("Published message to %s.", phone_number)
        except ClientError:
            logger.exception("Couldn't publish message to %s.", phone_number)
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Python (Boto3).

Publicar em um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como publicar mensagens em um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// This example publishes a message to an Amazon Simple Notification
    /// Service (Amazon SNS) topic.
    /// </summary>
    public class PublishToSNSTopic
    {
        public static async Task Main()
        {
            string topicArn = "arn:aws:sns:us-
east-2:000000000000:ExampleSNSTopic";
            string messageText = "This is an example message to publish to the
 ExampleSNSTopic.";

            IAmazonSimpleNotificationService client = new
 AmazonSimpleNotificationServiceClient();

            await PublishToTopicAsync(client, topicArn, messageText);
        }

        /// <summary>
        /// Publishes a message to an Amazon SNS topic.
        /// </summary>
        /// <param name="client">The initialized client object used to publish
        /// to the Amazon SNS topic.</param>
        /// <param name="topicArn">The ARN of the topic.</param>
        /// <param name="messageText">The text of the message.</param>
        public static async Task PublishToTopicAsync(
            IAmazonSimpleNotificationService client,
            string topicArn,
            string messageText)
        {
            var request = new PublishRequest
            {
                TopicArn = topicArn,
                Message = messageText,
            };
```

```
            var response = await client.PublishAsync(request);

            Console.WriteLine($"Successfully published message ID:
 {response.MessageId}");
        }
    }
```

Publique uma mensagem em um tópico com um atributo e desduplicação e IDs de grupo opcionais.

```
    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</
param>
    /// <param name="attributeValue">The optional attribute value for the
 message.</param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
```

```
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
 attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await
 _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send a message to an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param message: The message to publish.
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishToTopic(const Aws::String &message,
                                 const Aws::String &topicARN,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
```

```
    request.SetMessage(message);
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with id '"
                  << outcome.GetResult().GetMessageId() << "'." << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Exemplo 1: Para publicar uma mensagem em um tópico:

O exemplo `publish` a seguir publica a mensagem específica no tópico do SNS especificado. A mensagem é proveniente de um arquivo de texto, o que permite incluir quebras de linha.

```
aws sns publish \
    --topic-arn "arn:aws:sns:us-west-2:123456789012:my-topic" \
    --message file://message.txt
```

Conteúdo de `message.txt`:

```
Hello World
Second Line
```

Saída:

```
{
```

```
    "MessageId": "123a45b6-7890-12c3-45d6-111122223333"
}
```

Exemplo 2: Para publicar uma mensagem SMS em um número de telefone

O exemplo `publish` a seguir publica a mensagem `Hello world!` no número de telefone `+1-555-555-0100`.

```
aws sns publish \
    --message "Hello world!" \
    --phone-number +1-555-555-0100
```

Saída:

```
{
    "MessageId": "123a45b6-7890-12c3-45d6-333322221111"
}
```

- Para obter detalhes da API, consulte Publish na Referência de comandos da AWS CLI.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}
```

```
// Publish publishes a message to an Amazon SNS topic. The message is then sent
 to all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered
 according to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Go.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PublishTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <topicArn>

                Where:
                   message - The message text to send.
                   topicArn - The ARN of the topic to publish.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
```

```
        String topicArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTopic(snsClient, message, topicArn);
        snsClient.close();
    }

    public static void pubTopic(SnsClient snsClient, String message, String
 topicArn) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .topicArn(topicArn)
                    .build();

            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status is " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { PublishCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string | Record<string, any>} message - The message to send. Can be a
 plain string or an object
 *                                                    if you are using the `json`
 `MessageStructure`.
 * @param {string} topicArn - The ARN of the topic to which you would like to
 publish.
 */
export const publish = async (
  message = "Hello from SNS!",
  topicArn = "TOPIC_ARN",
) => {
  const response = await snsClient.send(
    new PublishCommand({
      Message: message,
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'e7f77526-e295-5325-9ee4-281a43ad1f05',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
```

```
  //   MessageId: 'xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun pubTopic(topicArnVal: String, messageVal: String) {

    val request = PublishRequest {
        message = messageVal
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.publish(request)
        println("${result.messageId} message sent.")
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK para Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Sends a message to an Amazon SNS topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$message = 'This message is sent from a Amazon SNS code sample.';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->publish([
        'Message' => $message,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
```

```
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem com atributos para que uma assinatura possa filtrar com base em atributos.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def publish_message(topic, message, attributes):
        """
        Publishes a message, with attributes, to a topic. Subscriptions can be
 filtered
        based on message attributes so that a subscription receives messages only
        when specified attributes are present.

        :param topic: The topic to publish to.
        :param message: The message to publish.
```

```
        :param attributes: The key-value attributes to attach to the message.
 Values
                           must be either `str` or `bytes`.
        :return: The ID of the message.
        """
        try:
            att_dict = {}
            for key, value in attributes.items():
                if isinstance(value, str):
                    att_dict[key] = {"DataType": "String", "StringValue": value}
                elif isinstance(value, bytes):
                    att_dict[key] = {"DataType": "Binary", "BinaryValue": value}
            response = topic.publish(Message=message, MessageAttributes=att_dict)
            message_id = response["MessageId"]
            logger.info(
                "Published message with attributes %s to topic %s.",
                attributes,
                topic.arn,
            )
        except ClientError:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise
        else:
            return message_id
```

Publique uma mensagem que assume diferentes formas com base no protocolo do assinante.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def publish_multi_message(
        topic, subject, default_message, sms_message, email_message
    ):
```

```
        """
        Publishes a multi-format message to a topic. A multi-format message takes
        different forms based on the protocol of the subscriber. For example,
        an SMS subscriber might receive a short version of the message
        while an email subscriber could receive a longer version.

        :param topic: The topic to publish to.
        :param subject: The subject of the message.
        :param default_message: The default version of the message. This version
is
                                sent to subscribers that have protocols that are
not
                                otherwise specified in the structured message.
        :param sms_message: The version of the message sent to SMS subscribers.
        :param email_message: The version of the message sent to email
subscribers.
        :return: The ID of the message.
        """
        try:
            message = {
                "default": default_message,
                "sms": sms_message,
                "email": email_message,
            }
            response = topic.publish(
                Message=json.dumps(message), Subject=subject,
MessageStructure="json"
            )
            message_id = response["MessageId"]
            logger.info("Published multi-format message to topic %s.", topic.arn)
        except ClientError:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# Service class for sending messages using Amazon Simple Notification Service
 (SNS)
class SnsMessageSender
  # Initializes the SnsMessageSender with an SNS client
  #
  # @param sns_client [Aws::SNS::Client] The SNS client
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Sends a message to a specified SNS topic
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param message [String] The message to send
  # @return [Boolean] true if message was successfully sent, false otherwise
  def send_message(topic_arn, message)
    @sns_client.publish(topic_arn: topic_arn, message: message)
    @logger.info("Message sent successfully to #{topic_arn}.")
    true
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error while sending the message: #{e.message}")
    false
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_arn = "SNS_TOPIC_ARN" # Should be replaced with a real topic ARN
  message = "MESSAGE"         # Should be replaced with the actual message
 content
```

```
  sns_client = Aws::SNS::Client.new
  message_sender = SnsMessageSender.new(sns_client)

  @logger.info("Sending message.")
  unless message_sender.send_message(topic_arn, message)
    @logger.error("Message sending failed. Stopping program.")
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn subscribe_and_publish(
    client: &Client,
    topic_arn: &str,
    email_address: &str,
) -> Result<(), Error> {
    println!("Receiving on topic with ARN: `{}`", topic_arn);

    let rsp = client
        .subscribe()
        .topic_arn(topic_arn)
        .protocol("email")
        .endpoint(email_address)
        .send()
        .await?;

    println!("Added a subscription: {:?}", rsp);
```

```
    let rsp = client
        .publish()
        .topic_arn(topic_arn)
        .message("hello sns!")
        .send()
        .await?;

    println!("Published message: {:?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->publish(              " oo_result is returned for
testing purposes. "
          iv_topicarn = iv_topic_arn
          iv_message = iv_message
        ).
        MESSAGE 'Message published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Publicar na Referência da API do AWS SDK para SAP ABAP.

Definir uma fila de mensagens mortas para uma assinatura do Amazon SNS usando o AWS SDK

O exemplo de código a seguir mostra como definir uma fila do Amazon SQS como uma fila de mensagens mortas para uma assinatura do Amazon SNS.

Java

SDK for Java 1.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Specify the ARN of the Amazon SNS subscription.
String subscriptionArn =
    "arn:aws:sns:us-east-2:123456789012:MyEndpoint:1234a567-
bc89-012d-3e45-6fg7h890123i";

// Specify the ARN of the Amazon SQS queue to use as a dead-letter queue.
String redrivePolicy =
    "{\"deadLetterTargetArn\":\"arn:aws:sqs:us-
east-2:123456789012:MyDeadLetterQueue\"}";

// Set the specified Amazon SQS queue as a dead-letter queue
// of the specified Amazon SNS subscription by setting the RedrivePolicy
 attribute.
SetSubscriptionAttributesRequest request = new SetSubscriptionAttributesRequest()
    .withSubscriptionArn(subscriptionArn)
    .withAttributeName("RedrivePolicy")
    .withAttributeValue(redrivePolicy);
sns.setSubscriptionAttributes(request);
```

Definir uma política de filtro do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como definir uma política de filtro do Amazon SNS.

CLI

AWS CLI

Para definir atributos de assinatura

O exemplo `set-subscription-attributes` a seguir define o atributo `RawMessageDelivery` para uma assinatura do SQS.

```
aws sns set-subscription-attributes \
    --subscription-arn arn:aws:sns:us-
east-1:123456789012:mytopic:f248de18-2cf6-578c-8592-b6f1eaa877dc \
    --attribute-name RawMessageDelivery \
    --attribute-value true
```

Este comando não produz saída.

O exemplo `set-subscription-attributes` a seguir define um atributo `FilterPolicy` para uma assinatura do SQS.

```
aws sns set-subscription-attributes \
    --subscription-arn arn:aws:sns:us-
east-1:123456789012:mytopic:f248de18-2cf6-578c-8592-b6f1eaa877dc \
    --attribute-name FilterPolicy \
    --attribute-value "{ \"anyMandatoryKey\": [\"any\", \"of\", \"these\"] }"
```

Este comando não produz saída.

O exemplo `set-subscription-attributes` a seguir remove o atributo `FilterPolicy` de uma assinatura do SQS.

```
aws sns set-subscription-attributes \
    --subscription-arn arn:aws:sns:us-
east-1:123456789012:mytopic:f248de18-2cf6-578c-8592-b6f1eaa877dc \
    --attribute-name FilterPolicy \
    --attribute-value "{}"
```

Este comando não produz saída.

- Para obter detalhes da API, consulte SetSubscriptionAttributesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class UseMessageFilterPolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <subscriptionArn>

                Where:
                   subscriptionArn - The ARN of a subscription.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String subscriptionArn = args[0];
        SnsClient snsClient = SnsClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        usePolicy(snsClient, subscriptionArn);
        snsClient.close();
    }

    public static void usePolicy(SnsClient snsClient, String subscriptionArn) {
        try {
            SNSMessageFilterPolicy fp = new SNSMessageFilterPolicy();
            // Add a filter policy attribute with a single value
            fp.addAttribute("store", "example_corp");
            fp.addAttribute("event", "order_placed");

            // Add a prefix attribute
            fp.addAttributePrefix("customer_interests", "bas");

            // Add an anything-but attribute
            fp.addAttributeAnythingBut("customer_interests", "baseball");

            // Add a filter policy attribute with a list of values
            ArrayList<String> attributeValues = new ArrayList<>();
            attributeValues.add("rugby");
            attributeValues.add("soccer");
            attributeValues.add("hockey");
            fp.addAttribute("customer_interests", attributeValues);

            // Add a numeric attribute
            fp.addAttribute("price_usd", "=", 0);

            // Add a numeric attribute with a range
            fp.addAttributeRange("price_usd", ">", 0, "<=", 100);

            // Apply the filter policy attributes to an Amazon SNS subscription
            fp.apply(snsClient, subscriptionArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SetSubscriptionAttributesa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def add_subscription_filter(subscription, attributes):
        """
        Adds a filter policy to a subscription. A filter policy is a key and a
        list of values that are allowed. When a message is published, it must
 have an
        attribute that passes the filter or it will not be sent to the
 subscription.

        :param subscription: The subscription the filter policy is attached to.
        :param attributes: A dictionary of key-value pairs that define the
 filter.
        """
        try:
            att_policy = {key: [value] for key, value in attributes.items()}
            subscription.set_attributes(
                AttributeName="FilterPolicy",
 AttributeValue=json.dumps(att_policy)
```

```
            )
            logger.info("Added filter to subscription %s.", subscription.arn)
        except ClientError:
            logger.exception(
                "Couldn't add filter to subscription %s.", subscription.arn
            )
            raise
```

- Para obter detalhes da API, consulte a SetSubscriptionAttributesReferência da API AWSSDK for Python (Boto3).

Definir as configurações padrão para enviar mensagens SMS do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como definir as configurações padrão para enviar mensagens SMS usando o Amazon SNS.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Como usar o Amazon SNS para definir o atributo defaultSMstype.

```
//! Set the default settings for sending SMS messages.
/*!
  \param smsType: The type of SMS message that you will send by default.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::setSMSType(const Aws::String &smsType,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SetSMSAttributesRequest request;
    request.AddAttributes("DefaultSMSType", smsType);

    const Aws::SNS::Model::SetSMSAttributesOutcome outcome =
 snsClient.SetSMSAttributes(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "SMS Type set successfully " << std::endl;
    }
    else {
        std::cerr << "Error while setting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Para definir atributos de mensagens SMS

O exemplo `set-sms-attributes` a seguir define o ID do remetente padrão para mensagens SMS como `MyName`.

```
aws sns set-sms-attributes \
    --attributes DefaultSenderID=MyName
```

Este comando não produz saída.

- Para encontrar detalhes da API, consulte SetSMSAttributes na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SetSMSAttributes {
    public static void main(String[] args) {
        HashMap<String, String> attributes = new HashMap<>(1);
        attributes.put("DefaultSMSType", "Transactional");
        attributes.put("UsageReportS3Bucket", "janbucket");

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        setSNSAttributes(snsClient, attributes);
        snsClient.close();
    }

    public static void setSNSAttributes(SnsClient snsClient, HashMap<String,
 String> attributes) {
        try {
```

```
            SetSmsAttributesRequest request = SetSmsAttributesRequest.builder()
                    .attributes(attributes)
                    .build();

            SetSmsAttributesResponse result =
 snsClient.setSMSAttributes(request);
            System.out.println("Set default Attributes to " + attributes + ".
 Status was "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SetSMSAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {"Transactional" | "Promotional"} defaultSmsType
 */
export const setSmsType = async (defaultSmsType = "Transactional") => {
  const response = await snsClient.send(
    new SetSMSAttributesCommand({
      attributes: {
        // Promotional - (Default) Noncritical messages, such as marketing
 messages.
        // Transactional - Critical messages that support customer transactions,
        // such as one-time passcodes for multi-factor authentication.
        DefaultSMSType: defaultSmsType,
      },
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '1885b977-2d7e-535e-8214-e44be727e265',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for JavaScript.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->SetSMSAttributes([
        'attributes' => [
            'DefaultSMSType' => 'Transactional',
        ],
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for PHP.

Definir atributos de tópicos do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como definir atributos para um tópico do Amazon SNS.

CLI

AWS CLI

Para definir um atributo para um tópico

O exemplo `set-topic-attributes` a seguir define o atributo `DisplayName` para o tópico especificado.

```
aws sns set-topic-attributes \
    --topic-arn arn:aws:sns:us-west-2:123456789012:MyTopic \
    --attribute-name DisplayName \
    --attribute-value MyTopicDisplayName
```

Este comando não produz saída.

- Para obter detalhes da API, consulte SetTopicAttributesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetTopicAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetTopicAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SetTopicAttributes {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <attribute> <topicArn> <value>

                Where:
                   attribute - The attribute action to use. Valid parameters are:
 Policy | DisplayName | DeliveryPolicy .
                   topicArn - The ARN of the topic.\s
                   value - The value for the attribute.
                """;

        if (args.length < 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String attribute = args[0];
        String topicArn = args[1];
        String value = args[2];

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        setTopAttr(snsClient, attribute, topicArn, value);
        snsClient.close();
    }

    public static void setTopAttr(SnsClient snsClient, String attribute, String
 topicArn, String value) {
        try {
            SetTopicAttributesRequest request =
 SetTopicAttributesRequest.builder()
                    .attributeName(attribute)
                    .attributeValue(value)
                    .topicArn(topicArn)
                    .build();
```

```
            SetTopicAttributesResponse result =
 snsClient.setTopicAttributes(request);
            System.out.println(
                    "\n\nStatus was " + result.sdkHttpResponse().statusCode() +
 "\n\nTopic " + request.topicArn()
                            + " updated " + request.attributeName() + " to " +
 request.attributeValue());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SetTopicAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const setTopicAttributes = async (
  topicArn = "TOPIC_ARN",
  attributeName = "DisplayName",
  attributeValue = "Test Topic",
) => {
  const response = await snsClient.send(
    new SetTopicAttributesCommand({
      AttributeName: attributeName,
      AttributeValue: attributeValue,
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'd1b08d0e-e9a4-54c3-b8b1-d03238d2b935',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setTopAttr(attribute: String?, topicArnVal: String?, value: String?)
 {

    val request = SetTopicAttributesRequest {
        attributeName = attribute
        attributeValue = value
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.setTopicAttributes(request)
        println("Topic ${request.topicArn} was updated.")
    }
}
```

- Para obter detalhes da API, consulte a SetTopicAttributesreferência da API AWSSDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';
```

```
use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Configure the message delivery status attributes for an Amazon SNS Topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);
$attribute = 'Policy | DisplayName | DeliveryPolicy';
$value = 'First Topic';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->setTopicAttributes([
        'AttributeName' => $attribute,
        'AttributeValue' => $value,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for PHP da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# Service class to enable an SNS resource with a specified policy
class SnsResourceEnabler
  # Initializes the SnsResourceEnabler with an SNS resource client
  #
  # @param sns_resource [Aws::SNS::Resource] The SNS resource client
  def initialize(sns_resource)
    @sns_resource = sns_resource
    @logger = Logger.new($stdout)
  end

  # Sets a policy on a specified SNS topic
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param resource_arn [String] The ARN of the resource to include in the policy
  # @param policy_name [String] The name of the policy attribute to set
  def enable_resource(topic_arn, resource_arn, policy_name)
    policy = generate_policy(topic_arn, resource_arn)
    topic = @sns_resource.topic(topic_arn)

    topic.set_attributes({
                           attribute_name: policy_name,
                           attribute_value: policy
                         })
    @logger.info("Policy #{policy_name} set successfully for topic
 #{topic_arn}.")
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Failed to set policy: #{e.message}")
  end

  private

  # Generates a policy string with dynamic resource ARNs
```

```
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param resource_arn [String] The ARN of the resource
  # @return [String] The policy as a JSON string
  def generate_policy(topic_arn, resource_arn)
    {
      Version: "2008-10-17",
      Id: "__default_policy_ID",
      Statement: [{
                    Sid: "__default_statement_ID",
                    Effect: "Allow",
                    Principal: { "AWS": "*" },
                    Action: ["SNS:Publish"],
                    Resource: topic_arn,
                    Condition: {
                      ArnEquals: {
                        "AWS:SourceArn": resource_arn
                      }
                    }
                  }]
    }.to_json
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_arn = "MY_TOPIC_ARN"     # Should be replaced with a real topic ARN
  resource_arn = "MY_RESOURCE_ARN" # Should be replaced with a real resource ARN
  policy_name = "POLICY_NAME"    # Typically, this is "Policy"

  sns_resource = Aws::SNS::Resource.new
  enabler = SnsResourceEnabler.new(sns_resource)

  enabler.enable_resource(topic_arn, resource_arn, policy_name)
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_sns->settopicattributes(
        iv_topicarn = iv_topic_arn
        iv_attributename  = iv_attribute_name
        iv_attributevalue = iv_attribute_value
    ).
    MESSAGE 'Set/updated SNS topic attributes.' TYPE 'I'.
  CATCH /aws1/cx_snsnotfoundexception.
    MESSAGE 'Topic does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a SetTopicAttributesreferência da API AWS SDK for SAP ABAP.

Inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an AWS Lambda function.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param lambdaFunctionARN: The ARN for an AWS Lambda function.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeLambda(const Aws::String &topicARN,
                                  const Aws::String &lambdaFunctionARN,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("lambda");
    request.SetEndpoint(lambdaFunctionARN);

    const Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " <<
 outcome.GetError().GetMessage()
```

```
                    << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SubscribeLambda {

    public static void main(String[] args) {

        final String usage = """

                Usage:    <topicArn> <lambdaArn>
```

```
                Where:
                   topicArn - The ARN of the topic to subscribe.
                   lambdaArn - The ARN of an AWS Lambda function.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String lambdaArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String arnValue = subLambda(snsClient, topicArn, lambdaArn);
        System.out.println("Subscription ARN: " + arnValue);
        snsClient.close();
    }

    public static String subLambda(SnsClient snsClient, String topicArn, String
 lambdaArn) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("lambda")
                    .endpoint(lambdaArn)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            return result.subscriptionArn();

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic the subscriber is subscribing
 to.
 * @param {string} endpoint - The Endpoint ARN of and AWS Lambda function.
 */
export const subscribeLambda = async (
  topicArn = "TOPIC_ARN",
  endpoint = "ENDPOINT",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "lambda",
      TopicArn: topicArn,
```

```
      Endpoint: endpoint,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'pending confirmation'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun subLambda(topicArnVal: String?, lambdaArn: String?) {

    val request = SubscribeRequest {
        protocol = "lambda"
        endpoint = lambdaArn
        returnSubscriptionArn = true
        topicArn = topicArnVal
```

```
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.subscribe(request)
        println(" The subscription Arn is ${result.subscriptionArn}")
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Kotlin.

Inscrever uma aplicação móvel em um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como inscrever um endpoint de aplicação móvel para receber notificações de um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to a mobile app.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param endpointARN: The ARN for a mobile app or device endpoint.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
```

```
 */
bool
AwsDoc::SNS::subscribeApp(const Aws::String &topicARN,
                          const Aws::String &endpointARN,
                          const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("application");
    request.SetEndpoint(endpointARN);

    const Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic the subscriber is subscribing
 to.
 * @param {string} endpoint - The Endpoint ARN of an application. This endpoint
 is created
 *                            when an application registers for notifications.
 */
export const subscribeApp = async (
  topicArn = "TOPIC_ARN",
  endpoint = "ENDPOINT",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "application",
      TopicArn: topicArn,
      Endpoint: endpoint,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
```

```
  //   SubscriptionArn: 'pending confirmation'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Inscrever um endpoint HTTP em um tópico do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como inscrever um endpoint HTTP ou HTTPS para receber notificações de um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
```

```
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SubscribeHTTPS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn> <url>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   url - The HTTPS endpoint that you want to receive
 notifications.
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String url = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subHTTPS(snsClient, topicArn, url);
        snsClient.close();
    }

    public static void subHTTPS(SnsClient snsClient, String topicArn, String url)
 {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("https")
                    .endpoint(url)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();
```

```
            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN is " + result.subscriptionArn()
 + "\n\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Prepares to subscribe an endpoint by sending the endpoint a confirmation
 message.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */
```

```
$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$protocol = 'https';
$endpoint = 'https://';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->subscribe([
        'Protocol' => $protocol,
        'Endpoint' => $endpoint,
        'ReturnSubscriptionArn' => true,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for PHP.

Assinar uma fila do Amazon SQS em um tópico do Amazon SNS usando um AWS SDK

O exemplo de código a seguir mostra como inscrever uma fila do Amazon SQS para receber notificações de um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inscreva uma fila em um tópico com filtros opcionais.

```
   /// <summary>
   /// Subscribe a queue to a topic with optional filters.
   /// </summary>
   /// <param name="topicArn">The ARN of the topic.</param>
   /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
   /// <param name="queueArn">The ARN of the queue.</param>
   /// <returns>The ARN of the new subscription.</returns>
   public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
   {
       var subscribeRequest = new SubscribeRequest()
       {
           TopicArn = topicArn,
           Protocol = "sqs",
           Endpoint = queueArn
       };

       if (!string.IsNullOrEmpty(filterPolicy))
       {
           subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
       }

       var subscribeResponse = await
_amazonSNSClient.SubscribeAsync(subscribeRequest);
       return subscribeResponse.SubscriptionArn;
   }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);

            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN <<
"."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
```

```
                        << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to
 an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string,
 filterMap map[string][]string) (string, error) {
```

```
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Go.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SubscribeCommand, SNSClient } from "@aws-sdk/client-sns";
```

```
const client = new SNSClient({});

export const subscribeQueue = async (
  topicArn = "TOPIC_ARN",
  queueArn = "QUEUE_ARN",
) => {
  const command = new SubscribeCommand({
    TopicArn: topicArn,
    Protocol: "sqs",
    Endpoint: queueArn,
  });

  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '931e13d9-5e2b-543f-8781-4e9e494c5ff2',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:subscribe-queue-
test-430895:xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Inscrever um endereço de e-mail em um tópico do Amazon SNS usando um AWS SDK

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Creates a new subscription to a topic.
/// </summary>
/// <param name="client">The initialized Amazon SNS client object, used
/// to create an Amazon SNS subscription.</param>
/// <param name="topicArn">The ARN of the topic to subscribe to.</param>
/// <returns>A SubscribeResponse object which includes the subscription
/// ARN for the new subscription.</returns>
public static async Task<SubscribeResponse> TopicSubscribeAsync(
    IAmazonSimpleNotificationService client,
    string topicArn)
{
    SubscribeRequest request = new SubscribeRequest()
    {
        TopicArn = topicArn,
        ReturnSubscriptionArn = true,
        Protocol = "email",
        Endpoint = "recipient@example.com",
    };

    var response = await client.SubscribeAsync(request);

    return response;
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an email address.
/*!
  \param topicARN: An SNS topic Amazon Resource Name (ARN).
  \param emailAddress: An email address.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeEmail(const Aws::String &topicARN,
                                 const Aws::String &emailAddress,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("email");
    request.SetEndpoint(emailAddress);

    const Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
```

```
    else {
        std::cerr << "Error while subscribing " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

CLI

AWS CLI

Para inscrever-se em um tópico

O comando `subscribe` a seguir inscreve um endereço de e-mail no tópico especificado.

```
aws sns subscribe \
    --topic-arn arn:aws:sns:us-west-2:123456789012:my-topic \
    --protocol email \
    --notification-endpoint my-email@example.com
```

Saída:

```
{
    "SubscriptionArn": "pending confirmation"
}
```

- Para obter detalhes da API, consulte Subscribe na Referência de comandos da AWS CLI.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SubscribeEmail {
    public static void main(String[] args) {
        final String usage = """
                Usage:     <topicArn> <email>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   email - The email address to use.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String email = args[1];
```

```
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subEmail(snsClient, topicArn, email);
        snsClient.close();
    }

    public static void subEmail(SnsClient snsClient, String topicArn, String
 email) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("email")
                    .endpoint(email)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN: " + result.subscriptionArn() +
 "\n\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave
 it blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic for which you wish to confirm
 a subscription.
 * @param {string} emailAddress - The email address that is subscribed to the
 topic.
 */
export const subscribeEmail = async (
  topicArn = "TOPIC_ARN",
  emailAddress = "usern@me.com",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "email",
      TopicArn: topicArn,
      Endpoint: emailAddress,
    }),
```

```
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'pending confirmation'
  // }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun subEmail(topicArnVal: String, email: String): String {

    val request = SubscribeRequest {
        protocol = "email"
        endpoint = email
        returnSubscriptionArn = true
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
```

```
        val result = snsClient.subscribe(request)
        return result.subscriptionArn.toString()
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Kotlin.

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Prepares to subscribe an endpoint by sending the endpoint a confirmation
 message.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/
guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$protocol = 'email';
```

```
$endpoint = 'sample@example.com';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->subscribe([
        'Protocol' => $protocol,
        'Endpoint' => $endpoint,
        'ReturnSubscriptionArn' => true,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for PHP.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    @staticmethod
    def subscribe(topic, protocol, endpoint):
        """
        Subscribes an endpoint to the topic. Some endpoint types, such as email,
        must be confirmed before their subscriptions are active. When a
subscription
        is not confirmed, its Amazon Resource Number (ARN) is set to
        'PendingConfirmation'.

        :param topic: The topic to subscribe to.
        :param protocol: The protocol of the endpoint, such as 'sms' or 'email'.
        :param endpoint: The endpoint that receives messages, such as a phone
number
                         (in E.164 format) for SMS messages, or an email address
for
                         email messages.
        :return: The newly added subscription.
        """
        try:
            subscription = topic.subscribe(
                Protocol=protocol, Endpoint=endpoint, ReturnSubscriptionArn=True
            )
            logger.info("Subscribed %s %s to topic %s.", protocol, endpoint,
topic.arn)
        except ClientError:
            logger.exception(
                "Couldn't subscribe %s %s to topic %s.", protocol, endpoint,
topic.arn
            )
            raise
        else:
            return subscription
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-sns"
require "logger"

# Represents a service for creating subscriptions in Amazon Simple Notification
 Service (SNS)
class SubscriptionService
  # Initializes the SubscriptionService with an SNS client
  #
  # @param sns_client [Aws::SNS::Client] The SNS client
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Attempts to create a subscription to a topic
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param protocol [String] The subscription protocol (e.g., email)
  # @param endpoint [String] The endpoint that receives the notifications (email
 address)
  # @return [Boolean] true if subscription was successfully created, false
 otherwise
  def create_subscription(topic_arn, protocol, endpoint)
    @sns_client.subscribe(topic_arn: topic_arn, protocol: protocol, endpoint:
 endpoint)
    @logger.info("Subscription created successfully.")
    true
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error while creating the subscription: #{e.message}")
    false
  end
end
```

```
# Main execution if the script is run directly
if $PROGRAM_NAME == __FILE__
  protocol = "email"
  endpoint = "EMAIL_ADDRESS" # Should be replaced with a real email address
  topic_arn = "TOPIC_ARN"    # Should be replaced with a real topic ARN

  sns_client = Aws::SNS::Client.new
  subscription_service = SubscriptionService.new(sns_client)

  @logger.info("Creating the subscription.")
  unless subscription_service.create_subscription(topic_arn, protocol, endpoint)
    @logger.error("Subscription creation failed. Stopping program.")
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Ruby.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn subscribe_and_publish(
    client: &Client,
    topic_arn: &str,
    email_address: &str,
) -> Result<(), Error> {
    println!("Receiving on topic with ARN: `{}`", topic_arn);

    let rsp = client
        .subscribe()
```

```
        .topic_arn(topic_arn)
        .protocol("email")
        .endpoint(email_address)
        .send()
        .await?;

    println!("Added a subscription: {:?}", rsp);

    let rsp = client
        .publish()
        .topic_arn(topic_arn)
        .message("hello sns!")
        .send()
        .await?;

    println!("Published message: {:?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->subscribe(                      "oo_result is
returned for testing purposes."
                iv_topicarn = iv_topic_arn
                iv_protocol = 'email'
                iv_endpoint = iv_email_address
                iv_returnsubscriptionarn = abap_true
```

```
            ).
        MESSAGE 'Email address subscribed to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snssubscriptionlmte00.
        MESSAGE 'Unable to create subscriptions. You have reached the maximum
number of subscriptions allowed.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte Inscrever-se na Referência da API do AWS SDK para SAP ABAP.

Assinar com um filtro em um tópico do Amazon SNS usando um AWS SDK

O exemplo de código a seguir mostra como assinar um tópico do Amazon SNS usando um filtro.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Criar e publicar em um tópico FIFO
- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inscreva uma fila em um tópico com filtros opcionais.

```
    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
```

```
    /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
_amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        static const Aws::String TONE_ATTRIBUTE("tone");
```

```
        static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
 "serious",
                                                        "sincere"};

        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have
 filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then
 only the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/
sns-message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a
 \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;
```

```
                        std::cout << "This is the filter policy for this
subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
filter "
                                << "will be added to this subscription." <<
std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN <<
"."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

```
//! Routine that lets the user select attributes for a subscription filter
 policy.
/*!
 \sa getFilterPolicyFromUser()
 \return Aws::String: The filter policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::getFilterPolicyFromUser() {
    std::cout
            << "You can filter messages by one or more of the following \""
            << TONE_ATTRIBUTE << "\" attributes." << std::endl;

    std::vector<Aws::String> filterSelections;
    int selection;
    do {
        for (size_t j = 0; j < TONES.size(); ++j) {
            std::cout << "  " << (j + 1) << ". " << TONES[j]
                      << std::endl;
        }
        selection = askQuestionForIntRange(
                "Enter a number (or enter zero to stop adding more). ",
                0, static_cast<int>(TONES.size()));

        if (selection != 0) {
            const Aws::String &selectedTone(TONES[selection - 1]);
            // Add the tone to the selection if it is not already added.
            if (std::find(filterSelections.begin(),
                          filterSelections.end(),
                          selectedTone)
                == filterSelections.end()) {
                filterSelections.push_back(selectedTone);
            }
        }
    } while (selection != 0);

    Aws::String result;
    if (!filterSelections.empty()) {
        std::ostringstream jsonPolicyStream;
        jsonPolicyStream << "{ \"" << TONE_ATTRIBUTE << "\": [";


        for (size_t j = 0; j < filterSelections.size(); ++j) {
            jsonPolicyStream << "\"" << filterSelections[j] << "\"";
            if (j < filterSelections.size() - 1) {
                jsonPolicyStream << ",";
```

```
            }
        }
        jsonPolicyStream << "] }";

        result = jsonPolicyStream.str();
    }

    return result;
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to
 an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string,
 filterMap map[string][]string) (string, error) {
 var subscriptionArn string
```

```
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Go.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SubscribeCommand, SNSClient } from "@aws-sdk/client-sns";
```

```
const client = new SNSClient({});

export const subscribeQueueFiltered = async (
  topicArn = "TOPIC_ARN",
  queueArn = "QUEUE_ARN",
) => {
  const command = new SubscribeCommand({
    TopicArn: topicArn,
    Protocol: "sqs",
    Endpoint: queueArn,
    Attributes: {
      // This subscription will only receive messages with the 'event' attribute
 set to 'order_placed'.
      FilterPolicyScope: "MessageAttributes",
      FilterPolicy: JSON.stringify({
        event: ["order_placed"],
      }),
    },
  });

  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '931e13d9-5e2b-543f-8781-4e9e494c5ff2',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:subscribe-queue-
test-430895:xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Cenários para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Notification Service (Amazon SNS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar um endpoint de plataforma para notificações por push do Amazon SNS usando um AWS SDK
- Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK
- Publicar mensagens SMS em um tópico do Amazon SNS usando um AWS SDK
- Publicar uma mensagem grande no Amazon SNS com o Amazon S3 usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Criar um endpoint de plataforma para notificações por push do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como criar um endpoint de plataforma para notificações por push do Amazon SNS.

CLI

AWS CLI

Para criar um endpoint de aplicação de plataforma

O exemplo `create-platform-endpoint` a seguir cria um endpoint para a aplicação de plataforma especificada usando o token especificado.

```
aws sns create-platform-endpoint \
    --platform-application-arn arn:aws:sns:us-west-2:123456789012:app/GCM/
MyApplication \
    --token EXAMPLE12345...
```

Saída:

```
{
      "EndpointArn": "arn:aws:sns:us-west-2:1234567890:endpoint/GCM/
MyApplication/12345678-abcd-9012-efgh-345678901234"
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreatePlatformEndpointRequest;
import software.amazon.awssdk.services.sns.model.CreatePlatformEndpointResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * In addition, create a platform application using the AWS Management Console.
 * See this doc topic:
 *
 * https://docs.aws.amazon.com/sns/latest/dg/mobile-push-send-register.html
 *
 * Without the values created by following the previous link, this code examples
 * does not work.
 */

public class RegistrationExample {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:     <token> <platformApplicationArn>

                Where:
                   token - The name of the FIFO topic.\s
                   platformApplicationArn - The ARN value of platform
 application. You can get this value from the AWS Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String token = args[0];
        String platformApplicationArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createEndpoint(snsClient, token, platformApplicationArn);
    }

    public static void createEndpoint(SnsClient snsClient, String token, String
 platformApplicationArn) {
        System.out.println("Creating platform endpoint with token " + token);
        try {
            CreatePlatformEndpointRequest endpointRequest =
 CreatePlatformEndpointRequest.builder()
                    .token(token)
                    .platformApplicationArn(platformApplicationArn)
                    .build();

            CreatePlatformEndpointResponse response =
 snsClient.createPlatformEndpoint(endpointRequest);
            System.out.println("The ARN of the endpoint is " +
 response.endpointArn());
        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como criar e publicar em um tópico FIFO do Amazon SNS.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse exemplo

- cria um tópico FIFO do Amazon SNS, duas filas FIFO do Amazon SQS e uma fila padrão.
- inscreve as filas no tópico e publica a mensagem no tópico.

O teste verifica o recebimento da mensagem em cada fila. O exemplo completo também mostra a adição de políticas de acesso e exclui os recursos no final.

```
public class PriceUpdateExample {
    public final static SnsClient snsClient = SnsClient.create();
    public final static SqsClient sqsClient = SqsClient.create();

    public static void main(String[] args) {

        final String usage = "\n" +
                "Usage: " +
                "    <topicName> <wholesaleQueueFifoName> <retailQueueFifoName>
 <analyticsQueueName>\n\n" +
                "Where:\n" +
                "   fifoTopicName - The name of the FIFO topic that you want to
 create. \n\n" +
                "   wholesaleQueueARN - The name of a SQS FIFO queue that will be
 created for the wholesale consumer. \n\n"
                +
                "   retailQueueARN - The name of a SQS FIFO queue that will
 created for the retail consumer. \n\n" +
```

```
                "   analyticsQueueARN - The name of a SQS standard queue that
will be created for the analytics consumer. \n\n";
        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        final String fifoTopicName = args[0];
        final String wholeSaleQueueName = args[1];
        final String retailQueueName = args[2];
        final String analyticsQueueName = args[3];

        // For convenience, the QueueData class holds metadata about a queue:
ARN, URL,
        // name and type.
        List<QueueData> queues = List.of(
                new QueueData(wholeSaleQueueName, QueueType.FIFO),
                new QueueData(retailQueueName, QueueType.FIFO),
                new QueueData(analyticsQueueName, QueueType.Standard));

        // Create queues.
        createQueues(queues);

        // Create a topic.
        String topicARN = createFIFOTopic(fifoTopicName);

        // Subscribe each queue to the topic.
        subscribeQueues(queues, topicARN);

        // Allow the newly created topic to send messages to the queues.
        addAccessPolicyToQueuesFINAL(queues, topicARN);

        // Publish a sample price update message with payload.
        publishPriceUpdate(topicARN, "{\"product\": 214, \"price\": 79.99}",
"Consumables");

        // Clean up resources.
        deleteSubscriptions(queues);
        deleteQueues(queues);
        deleteTopic(topicARN);
    }

    public static String createFIFOTopic(String topicName) {
        try {
```

```
            // Create a FIFO topic by using the SNS service client.
            Map<String, String> topicAttributes = Map.of(
                    "FifoTopic", "true",
                    "ContentBasedDeduplication", "false");

            CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                    .name(topicName)
                    .attributes(topicAttributes)
                    .build();

            CreateTopicResponse response = snsClient.createTopic(topicRequest);
            String topicArn = response.topicArn();
            System.out.println("The topic ARN is" + topicArn);

            return topicArn;

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void subscribeQueues(List<QueueData> queues, String topicARN) {
        queues.forEach(queue -> {
            SubscribeRequest subscribeRequest = SubscribeRequest.builder()
                    .topicArn(topicARN)
                    .endpoint(queue.queueARN)
                    .protocol("sqs")
                    .build();

            // Subscribe to the endpoint by using the SNS service client.
            // Only Amazon SQS queues can receive notifications from an Amazon
SNS FIFO
            // topic.
            SubscribeResponse subscribeResponse =
snsClient.subscribe(subscribeRequest);
            System.out.println("The queue [" + queue.queueARN + "] subscribed to
the topic [" + topicARN + "]");
            queue.subscriptionARN = subscribeResponse.subscriptionArn();
        });
    }
```

```
    public static void publishPriceUpdate(String topicArn, String payload, String
groupId) {

        try {
            // Create and publish a message that updates the wholesale price.
            String subject = "Price Update";
            String dedupId = UUID.randomUUID().toString();
            String attributeName = "business";
            String attributeValue = "wholesale";

            MessageAttributeValue msgAttValue = MessageAttributeValue.builder()
                    .dataType("String")
                    .stringValue(attributeValue)
                    .build();

            Map<String, MessageAttributeValue> attributes = new HashMap<>();
            attributes.put(attributeName, msgAttValue);
            PublishRequest pubRequest = PublishRequest.builder()
                    .topicArn(topicArn)
                    .subject(subject)
                    .message(payload)
                    .messageGroupId(groupId)
                    .messageDeduplicationId(dedupId)
                    .messageAttributes(attributes)
                    .build();

            final PublishResponse response = snsClient.publish(pubRequest);
            System.out.println(response.messageId());
            System.out.println(response.sequenceNumber());
            System.out.println("Message was published to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateTopic
  - Publicar

- Assinar

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO do Amazon SNS, inscreva filas padrão e FIFO do Amazon SQS no tópico e publique uma mensagem no tópico.

```
def usage_demo():
    """Shows how to subscribe queues to a FIFO topic."""
    print("-" * 88)
    print("Welcome to the `Subscribe queues to a FIFO topic` demo!")
    print("-" * 88)

    sns = boto3.resource("sns")
    sqs = boto3.resource("sqs")
    fifo_topic_wrapper = FifoTopicWrapper(sns)
    sns_wrapper = SnsWrapper(sns)

    prefix = "sqs-subscribe-demo-"
    queues = set()
    subscriptions = set()

    wholesale_queue = sqs.create_queue(
        QueueName=prefix + "wholesale.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(wholesale_queue)
```

```
    print(f"Created FIFO queue with URL: {wholesale_queue.url}.")

    retail_queue = sqs.create_queue(
        QueueName=prefix + "retail.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(retail_queue)
    print(f"Created FIFO queue with URL: {retail_queue.url}.")

    analytics_queue = sqs.create_queue(QueueName=prefix + "analytics",
Attributes={})
    queues.add(analytics_queue)
    print(f"Created standard queue with URL: {analytics_queue.url}.")

    topic = fifo_topic_wrapper.create_fifo_topic("price-updates-topic.fifo")
    print(f"Created FIFO topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        fifo_topic_wrapper.add_access_policy(q, topic.attributes["TopicArn"])

    print(f"Added access policies for topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        sub = fifo_topic_wrapper.subscribe_queue_to_topic(
            topic, q.attributes["QueueArn"]
        )
        subscriptions.add(sub)

    print(f"Subscribed queues to topic: {topic.attributes['TopicArn']}.")

    input("Press Enter to publish a message to the topic.")

    message_id = fifo_topic_wrapper.publish_price_update(
        topic, '{"product": 214, "price": 79.99}', "Consumables"
    )

    print(f"Published price update with message ID: {message_id}.")
```

```
    # Clean up the subscriptions, queues, and topic.
    input("Press Enter to clean up resources.")
    for s in subscriptions:
        sns_wrapper.delete_subscription(s)

    sns_wrapper.delete_topic(topic)

    for q in queues:
        fifo_topic_wrapper.delete_queue(q)

    print(f"Deleted subscriptions, queues, and topic.")

    print("Thanks for watching!")
    print("-" * 88)



class FifoTopicWrapper:
    """Encapsulates Amazon SNS FIFO topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource

    def create_fifo_topic(self, topic_name):
        """
        Create a FIFO topic.
        Topic names must be made up of only uppercase and lowercase ASCII
 letters,
        numbers, underscores, and hyphens, and must be between 1 and 256
 characters long.
        For a FIFO topic, the name must end with the .fifo suffix.

        :param topic_name: The name for the topic.
        :return: The new topic.
        """
        try:
            topic = self.sns_resource.create_topic(
                Name=topic_name,
                Attributes={
                    "FifoTopic": str(True),
                    "ContentBasedDeduplication": str(False),
```

```
                },
            )
            logger.info("Created FIFO topic with name=%s.", topic_name)
            return topic
        except ClientError as error:
            logger.exception("Couldn't create topic with name=%s!", topic_name)
            raise error


    @staticmethod
    def add_access_policy(queue, topic_arn):
        """
        Add the necessary access policy to a queue, so
        it can receive messages from a topic.

        :param queue: The queue resource.
        :param topic_arn: The ARN of the topic.
        :return: None.
        """
        try:
            queue.set_attributes(
                Attributes={
                    "Policy": json.dumps(
                        {
                            "Version": "2012-10-17",
                            "Statement": [
                                {
                                    "Sid": "test-sid",
                                    "Effect": "Allow",
                                    "Principal": {"AWS": "*"},
                                    "Action": "SQS:SendMessage",
                                    "Resource": queue.attributes["QueueArn"],
                                    "Condition": {
                                        "ArnLike": {"aws:SourceArn": topic_arn}
                                    },
                                }
                            ],
                        }
                    )
                }
            )
            logger.info("Added trust policy to the queue.")
        except ClientError as error:
            logger.exception("Couldn't add trust policy to the queue!")
```

```
            raise error


    @staticmethod
    def subscribe_queue_to_topic(topic, queue_arn):
        """
        Subscribe a queue to a topic.

        :param topic: The topic resource.
        :param queue_arn: The ARN of the queue.
        :return: The subscription resource.
        """
        try:
            subscription = topic.subscribe(
                Protocol="sqs",
                Endpoint=queue_arn,
            )
            logger.info("The queue is subscribed to the topic.")
            return subscription
        except ClientError as error:
            logger.exception("Couldn't subscribe queue to topic!")
            raise error


    @staticmethod
    def publish_price_update(topic, payload, group_id):
        """
        Compose and publish a message that updates the wholesale price.

        :param topic: The topic to publish to.
        :param payload: The message to publish.
        :param group_id: The group ID for the message.
        :return: The ID of the message.
        """
        try:
            att_dict = {"business": {"DataType": "String", "StringValue":
 "wholesale"}}
            dedup_id = uuid.uuid4()
            response = topic.publish(
                Subject="Price Update",
                Message=payload,
                MessageAttributes=att_dict,
                MessageGroupId=group_id,
                MessageDeduplicationId=str(dedup_id),
```

```
            )
            message_id = response["MessageId"]
            logger.info("Published message to topic %s.", topic.arn)
        except ClientError as error:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise error
        return message_id


    @staticmethod
    def delete_queue(queue):
        """
        Removes an SQS queue. When run against an AWS account, it can take up to
        60 seconds before the queue is actually deleted.

        :param queue: The queue to delete.
        :return: None
        """
        try:
            queue.delete()
            logger.info("Deleted queue with URL=%s.", queue.url)
        except ClientError as error:
            logger.exception("Couldn't delete queue with URL=%s!", queue.url)
            raise error
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTopic
  - Publicar
  - Assinar

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO, inscreva uma fila FIFO do Amazon SQS no tópico e publique uma mensagem em um tópico do Amazon SNS.

```
    " Creates a FIFO topic. "
    DATA lt_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>tt_topicattributesmap.
    DATA ls_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>ts_topicattributesmap_maprow.
    ls_tpc_attributes-key = 'FifoTopic'.
    ls_tpc_attributes-value = NEW /aws1/cl_snstopicattrsmap_w( iv_value =
 'true' ).
    INSERT ls_tpc_attributes INTO TABLE lt_tpc_attributes.

    TRY.
        DATA(lo_create_result) = lo_sns->createtopic(
               iv_name = iv_topic_name
               it_attributes = lt_tpc_attributes
        ).
        DATA(lv_topic_arn) = lo_create_result->get_topicarn( ).
        ov_topic_arn = lv_topic_arn.                                    "
 ov_topic_arn is returned for testing purposes. "
        MESSAGE 'FIFO topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
        MESSAGE 'Unable to create more topics. You have reached the maximum
 number of topics allowed.' TYPE 'E'.
    ENDTRY.

    " Subscribes an endpoint to an Amazon Simple Notification Service (Amazon
 SNS) topic. "
    " Only Amazon Simple Queue Service (Amazon SQS) FIFO queues can be subscribed
 to an SNS FIFO topic. "
```

```
    TRY.
        DATA(lo_subscribe_result) = lo_sns->subscribe(
               iv_topicarn = lv_topic_arn
               iv_protocol = 'sqs'
               iv_endpoint = iv_queue_arn
           ).
        DATA(lv_subscription_arn) = lo_subscribe_result->get_subscriptionarn( ).
        ov_subscription_arn = lv_subscription_arn.                      "
 ov_subscription_arn is returned for testing purposes. "
        MESSAGE 'SQS queue was subscribed to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snssubscriptionlmte00.
        MESSAGE 'Unable to create subscriptions. You have reached the maximum
 number of subscriptions allowed.' TYPE 'E'.
    ENDTRY.

    " Publish message to SNS topic. "
    TRY.
        DATA lt_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>tt_messageattributemap.
        DATA ls_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>ts_messageattributemap_maprow.
        ls_msg_attributes-key = 'Importance'.
        ls_msg_attributes-value = NEW /aws1/cl_snsmessageattrvalue( iv_datatype =
 'String' iv_stringvalue = 'High' ).
        INSERT ls_msg_attributes INTO TABLE lt_msg_attributes.

        DATA(lo_result) = lo_sns->publish(
             iv_topicarn = lv_topic_arn
             iv_message = 'The price of your mobile plan has been increased from
 $19 to $23'
             iv_subject = 'Changes to mobile plan'
             iv_messagegroupid = 'Update-2'
             iv_messagededuplicationid = 'Update-2.1'
             it_messageattributes = lt_msg_attributes
      ).
        ov_message_id = lo_result->get_messageid( ).                    "
 ov_message_id is returned for testing purposes. "
        MESSAGE 'Message was published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateTopic
  - Publicar
  - Assinar

Publicar mensagens SMS em um tópico do Amazon SNS usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie um tópico do Amazon SNS.
- Inscrever números de telefone no tópico.
- Publicar mensagens SMS no tópico para que todos os números de telefone inscritos recebam a mensagem de uma só vez.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um tópico e retorne seu ARN.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreateTopicRequest;
import software.amazon.awssdk.services.sns.model.CreateTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicName>

                Where:
                   topicName - The name of the topic to create (for example,
 mytopic).

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicName = args[0];
        System.out.println("Creating a topic with name: " + topicName);
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String arnVal = createSNSTopic(snsClient, topicName);
        System.out.println("The topic ARN is" + arnVal);
        snsClient.close();
    }

    public static String createSNSTopic(SnsClient snsClient, String topicName) {
        CreateTopicResponse result;
        try {
            CreateTopicRequest request = CreateTopicRequest.builder()
                    .name(topicName)
                    .build();

            result = snsClient.createTopic(request);
            return result.topicArn();
```

```
        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

Inscreva um endpoint em um tópico.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SubscribeTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn> <phoneNumber>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   phoneNumber - A mobile phone number that receives
 notifications (for example, +1XXX5550100).
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String topicArn = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subTextSNS(snsClient, topicArn, phoneNumber);
        snsClient.close();
    }

    public static void subTextSNS(SnsClient snsClient, String topicArn, String
 phoneNumber) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("sms")
                    .endpoint(phoneNumber)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN: " + result.subscriptionArn() +
 "\n\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Defina atributos na mensagem, como o ID do remetente, o preço máximo e seu tipo. Os atributos de mensagem são opcionais.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.HashMap;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SetSMSAttributes {
    public static void main(String[] args) {
        HashMap<String, String> attributes = new HashMap<>(1);
        attributes.put("DefaultSMSType", "Transactional");
        attributes.put("UsageReportS3Bucket", "janbucket");

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        setSNSAttributes(snsClient, attributes);
        snsClient.close();
    }

    public static void setSNSAttributes(SnsClient snsClient, HashMap<String,
 String> attributes) {
        try {
            SetSmsAttributesRequest request = SetSmsAttributesRequest.builder()
                    .attributes(attributes)
                    .build();

            SetSmsAttributesResponse result =
 snsClient.setSMSAttributes(request);
            System.out.println("Set default Attributes to " + attributes + ".
 Status was "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Publique uma mensagem em um tópico. A mensagem é enviada para todos os assinantes.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class PublishTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <phoneNumber>

                Where:
                   message - The message text to send.
                   phoneNumber - The mobile phone number to which a message is
 sent (for example, +1XXX5550100).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTextSMS(snsClient, message, phoneNumber);
        snsClient.close();
    }
```

```
    public static void pubTextSMS(SnsClient snsClient, String message, String
 phoneNumber) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .phoneNumber(phoneNumber)
                    .build();

            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Publicar uma mensagem grande no Amazon SNS com o Amazon S3 usando um AWS SDK

O exemplo de código a seguir mostra como publicar uma mensagem grande no Amazon SNS usando o Amazon S3 para armazenar a carga útil da mensagem.

Java

SDK para Java 1.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Para publicar uma mensagem grande, use a Amazon SNS Extended Client Library for Java. A mensagem que você envia faz referência a um objeto do Amazon S3 que contém o conteúdo real da mensagem.

```
import com.amazon.sqs.javamessaging.AmazonSQSExtendedClient;
import com.amazon.sqs.javamessaging.ExtendedClientConfiguration;
import com.amazonaws.regions.Region;
import com.amazonaws.regions.Regions;
import com.amazonaws.services.s3.AmazonS3;
import com.amazonaws.services.s3.AmazonS3ClientBuilder;
import com.amazonaws.services.sns.AmazonSNS;
import com.amazonaws.services.sns.AmazonSNSClientBuilder;
import com.amazonaws.services.sns.model.CreateTopicRequest;
import com.amazonaws.services.sns.model.PublishRequest;
import com.amazonaws.services.sns.model.SetSubscriptionAttributesRequest;
import com.amazonaws.services.sns.util.Topics;
import com.amazonaws.services.sqs.AmazonSQS;
import com.amazonaws.services.sqs.AmazonSQSClientBuilder;
import com.amazonaws.services.sqs.model.CreateQueueRequest;
import com.amazonaws.services.sqs.model.ReceiveMessageResult;
import software.amazon.sns.AmazonSNSExtendedClient;
import software.amazon.sns.SNSExtendedClientConfiguration;

public class Example {

        public static void main(String[] args) {
                final String BUCKET_NAME = "extended-client-bucket";
                final String TOPIC_NAME = "extended-client-topic";
                final String QUEUE_NAME = "extended-client-queue";
                final Regions region = Regions.DEFAULT_REGION;

                // Message threshold controls the maximum message size that will
 be allowed to
                // be published
                // through SNS using the extended client. Payload of messages
 exceeding this
                // value will be stored in
                // S3. The default value of this parameter is 256 KB which is the
 maximum
                // message size in SNS (and SQS).
                final int EXTENDED_STORAGE_MESSAGE_SIZE_THRESHOLD = 32;

                // Initialize SNS, SQS and S3 clients
                final AmazonSNS snsClient =
 AmazonSNSClientBuilder.standard().withRegion(region).build();
                final AmazonSQS sqsClient =
 AmazonSQSClientBuilder.standard().withRegion(region).build();
```

```
                final AmazonS3 s3Client =
AmazonS3ClientBuilder.standard().withRegion(region).build();

                // Create bucket, topic, queue and subscription
                s3Client.createBucket(BUCKET_NAME);
                final String topicArn = snsClient.createTopic(
                                new
CreateTopicRequest().withName(TOPIC_NAME)).getTopicArn();
                final String queueUrl = sqsClient.createQueue(
                                new
CreateQueueRequest().withQueueName(QUEUE_NAME)).getQueueUrl();
                final String subscriptionArn = Topics.subscribeQueue(
                                snsClient, sqsClient, topicArn, queueUrl);

                // To read message content stored in S3 transparently through SQS
extended
                // client,
                // set the RawMessageDelivery subscription attribute to TRUE
                final SetSubscriptionAttributesRequest
subscriptionAttributesRequest = new SetSubscriptionAttributesRequest();

subscriptionAttributesRequest.setSubscriptionArn(subscriptionArn);

subscriptionAttributesRequest.setAttributeName("RawMessageDelivery");
                subscriptionAttributesRequest.setAttributeValue("TRUE");

snsClient.setSubscriptionAttributes(subscriptionAttributesRequest);

                // Initialize SNS extended client
                // PayloadSizeThreshold triggers message content storage in S3
when the
                // threshold is exceeded
                // To store all messages content in S3, use AlwaysThroughS3 flag
                final SNSExtendedClientConfiguration
snsExtendedClientConfiguration = new SNSExtendedClientConfiguration()
                                .withPayloadSupportEnabled(s3Client, BUCKET_NAME)

.withPayloadSizeThreshold(EXTENDED_STORAGE_MESSAGE_SIZE_THRESHOLD);
                final AmazonSNSExtendedClient snsExtendedClient = new
AmazonSNSExtendedClient(snsClient,
                                snsExtendedClientConfiguration);

                // Publish message via SNS with storage in S3
```

```
                final String message = "This message is stored in S3 as it
 exceeds the threshold of 32 bytes set above.";
                snsExtendedClient.publish(topicArn, message);

                // Initialize SQS extended client
                final ExtendedClientConfiguration sqsExtendedClientConfiguration
 = new ExtendedClientConfiguration()
                                .withPayloadSupportEnabled(s3Client,
 BUCKET_NAME);
                final AmazonSQSExtendedClient sqsExtendedClient = new
 AmazonSQSExtendedClient(sqsClient,
                                sqsExtendedClientConfiguration);

                // Read the message from the queue
                final ReceiveMessageResult result =
 sqsExtendedClient.receiveMessage(queueUrl);
                System.out.println("Received message is " +
 result.getMessages().get(0).getBody());
        }
}
```

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Console application to run a workflow scenario for topics and queues.
/// </summary>
public static class TopicsAndQueues
{
    private static bool _useFifoTopic = false;
    private static bool _useContentBasedDeduplication = false;
    private static string _topicName = null!;
    private static string _topicArn = null!;

    private static readonly int _queueCount = 2;
    private static readonly string[] _queueUrls = new string[_queueCount];
    private static readonly string[] _subscriptionArns = new string[_queueCount];
    private static readonly string[] _tones = { "cheerful", "funny", "serious",
 "sincere" };
    public static SNSWrapper SnsWrapper { get; set; } = null!;
    public static SQSWrapper SqsWrapper { get; set; } = null!;
    public static bool UseConsole { get; set; } = true;
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EventBridge.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonSQS>()
                    .AddAWSService<IAmazonSimpleNotificationService>()
```

```
                    .AddTransient<SNSWrapper>()
                    .AddTransient<SQSWrapper>()
            )
            .Build();

        ServicesSetup(host);
        PrintDescription();

        await RunScenario();

    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        SnsWrapper = host.Services.GetRequiredService<SNSWrapper>();
        SqsWrapper = host.Services.GetRequiredService<SQSWrapper>();
    }

    /// <summary>
    /// Run the scenario for working with topics and queues.
    /// </summary>
    /// <returns>True if successful.</returns>
    public static async Task<bool> RunScenario()
    {
        try
        {
            await SetupTopic();

            await SetupQueues();

            await PublishMessages();

            foreach (var queueUrl in _queueUrls)
            {
                var messages = await PollForMessages(queueUrl);
                if (messages.Any())
                {
                    await DeleteMessages(queueUrl, messages);
                }
            }
```

```
            await CleanupResources();

            Console.WriteLine("Messaging with topics and queues workflow is
complete.");
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await CleanupResources();
            Console.WriteLine(new string('-', 80));
            return false;
        }
    }

    /// <summary>
    /// Print a description for the tasks in the workflow.
    /// </summary>
    /// <returns>Async task.</returns>
    private static void PrintDescription()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Welcome to messaging with topics and queues.");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"In this workflow, you will create an SNS topic and
subscribe {_queueCount} SQS queues to the topic." +
                          $"\r\nYou can select from several options for
configuring the topic and the subscriptions for the 2 queues." +
                          $"\r\nYou can then post to the topic and see the
results in the queues.\r\n");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the SNS topic to be used with the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> SetupTopic()
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine($"SNS topics can be configured as FIFO (First-In-First-
Out)." +
                          $"\r\nFIFO topics deliver messages in order and support
 deduplication and message filtering." +
                          $"\r\nYou can then post to the topic and see the
 results in the queues.\r\n");

        _useFifoTopic = GetYesNoResponse("Would you like to work with FIFO
 topics?");

        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            _topicName = GetUserResponse("Enter a name for your SNS topic: ",
 "example-topic");
            Console.WriteLine(
                "Because you have selected a FIFO topic, '.fifo' must be appended
 to the topic name.\r\n");

            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"Because you have chosen a FIFO topic,
 deduplication is supported." +
                              $"\r\nDeduplication IDs are either set in the
 message or automatically generated " +
                              $"\r\nfrom content using a hash function.\r\n" +
                              $"\r\nIf a message is successfully published to an
 SNS FIFO topic, any message " +
                              $"\r\npublished and determined to have the same
 deduplication ID, " +
                              $"\r\nwithin the five-minute deduplication
 interval, is accepted but not delivered.\r\n" +
                              $"\r\nFor more information about deduplication, " +
                              $"\r\nsee https://docs.aws.amazon.com/sns/latest/
dg/fifo-message-dedup.html.");

            _useContentBasedDeduplication = GetYesNoResponse("Use content-based
 deduplication instead of entering a deduplication ID?");
            Console.WriteLine(new string('-', 80));
        }

        _topicArn = await SnsWrapper.CreateTopicWithName(_topicName,
 _useFifoTopic, _useContentBasedDeduplication);

        Console.WriteLine($"Your new topic with the name {_topicName}" +
```

```
                            $"\r\nand Amazon Resource Name (ARN) {_topicArn}" +
                            $"\r\nhas been created.\r\n");

        Console.WriteLine(new string('-', 80));
        return _topicArn;
    }

    /// <summary>
    /// Set up the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task SetupQueues()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now you will create {_queueCount} Amazon Simple Queue
Service (Amazon SQS) queues to subscribe to the topic.");

        // Repeat this section for each queue.
        for (int i = 0; i < _queueCount; i++)
        {
            var queueName = GetUserResponse("Enter a name for an Amazon SQS
queue: ", $"example-queue-{i}");
            if (_useFifoTopic)
            {
                // Only explain this once.
                if (i == 0)
                {
                    Console.WriteLine(
                        "Because you have selected a FIFO topic, '.fifo' must be
appended to the queue name.");
                }

                var queueUrl = await SqsWrapper.CreateQueueWithName(queueName,
_useFifoTopic);

                _queueUrls[i] = queueUrl;

                Console.WriteLine($"Your new queue with the name {queueName}" +
                                  $"\r\nand queue URL {queueUrl}" +
                                  $"\r\nhas been created.\r\n");

                if (i == 0)
                {
                    Console.WriteLine(
```

```
                        $"The queue URL is used to retrieve the queue ARN,\r\n" +
                        $"which is used to create a subscription.");
                    Console.WriteLine(new string('-', 80));
                }

                var queueArn = await SqsWrapper.GetQueueArnByUrl(queueUrl);

                if (i == 0)
                {
                    Console.WriteLine(
                        $"An AWS Identity and Access Management (IAM) policy must
be attached to an SQS queue, enabling it to receive\r\n" +
                        $"messages from an SNS topic");
                }

                await SqsWrapper.SetQueuePolicyForTopic(queueArn, _topicArn,
queueUrl);

                await SetupFilters(i, queueArn, queueName);
            }
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up filters with user options for a queue.
    /// </summary>
    /// <param name="queueCount">The number of this queue.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="queueName">The name of the queue.</param>
    /// <returns>Async Task.</returns>
    public static async Task SetupFilters(int queueCount, string queueArn, string
queueName)
    {
        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            // Only explain this once.
            if (queueCount == 0)
            {
                Console.WriteLine(
                    "Subscriptions to a FIFO topic can have filters." +
```

```
                    "If you add a filter to this subscription, then only the
 filtered messages " +
                    "will be received in the queue.");

                Console.WriteLine(
                    "For information about message filtering, " +
                    "see https://docs.aws.amazon.com/sns/latest/dg/sns-message-
filtering.html");

                Console.WriteLine(
                    "For this example, you can filter messages by a" +
                    "TONE attribute.");
            }

            var useFilter = GetYesNoResponse($"Filter messages for {queueName}'s
 subscription to the topic?");

            string? filterPolicy = null;
            if (useFilter)
            {
                filterPolicy = CreateFilterPolicy();
            }
            var subscriptionArn = await
 SnsWrapper.SubscribeTopicWithFilter(_topicArn, filterPolicy,
                queueArn);
            _subscriptionArns[queueCount] = subscriptionArn;

            Console.WriteLine(
                $"The queue {queueName} has been subscribed to the topic
 {_topicName} " +
                $"with the subscription ARN {subscriptionArn}");
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Use user input to create a filter policy for a subscription.
    /// </summary>
    /// <returns>The serialized filter policy.</returns>
    public static string CreateFilterPolicy()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            $"You can filter messages by one or more of the following" +
```

```
            $"TONE attributes.");

        List<string> filterSelections = new List<string>();

        var selectionNumber = 0;
        do
        {
            Console.WriteLine(
                $"Enter a number to add a TONE filter, or enter 0 to stop adding
 filters.");
            for (int i = 0; i < _tones.Length; i++)
            {
                Console.WriteLine($"\t{i + 1}. {_tones[i]}");
            }

            var selection = GetUserResponse("", filterSelections.Any() ? "0" :
 "1");
            int.TryParse(selection, out selectionNumber);
            if (selectionNumber > 0 && !
filterSelections.Contains(_tones[selectionNumber - 1]))
            {
                filterSelections.Add(_tones[selectionNumber - 1]);
            }
        } while (selectionNumber != 0);

        var filters = new Dictionary<string, List<string>>
        {
            { "tone", filterSelections }
        };
        string filterPolicy = JsonSerializer.Serialize(filters);
        return filterPolicy;
    }

    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
```

```
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is
a sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must
set a message group ID." +
                                  "\r\nAll messages within the same group will be
received in the order " +
                                  "they were published.");

                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID
for this message:", "1");

                if (!_useContentBasedDeduplication)
                {
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                      "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this
message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID
for this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
```

```
                    }
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?",
false);
        }
    }

    /// <summary>
    /// Poll for the published messages to see the results of the user's choices.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task<List<Message>> PollForMessages(string queueUrl)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now the SQS queue at {queueUrl} will be polled to
retrieve the messages." +
                          "\r\nPress any key to continue.");
        if (UseConsole)
        {
            Console.ReadLine();
        }

        var moreMessages = true;
        var messages = new List<Message>();
        while (moreMessages)
        {
            var newMessages = await SqsWrapper.ReceiveMessagesByUrl(queueUrl,
10);

            moreMessages = newMessages.Any();
            if (moreMessages)
            {
                messages.AddRange(newMessages);
            }
        }
```

```
        Console.WriteLine($"{messages.Count} message(s) were received by the
queue at {queueUrl}.");

        foreach (var message in messages)
        {
            Console.WriteLine("\tMessage:" +
                              $"\n\t{message.Body}");
        }

        Console.WriteLine(new string('-', 80));
        return messages;
    }

    /// <summary>
    /// Delete the message using handles in a batch.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task DeleteMessages(string queueUrl, List<Message>
messages)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Now we can delete the messages in this queue in a
batch.");
        await SqsWrapper.DeleteMessageBatchByUrl(queueUrl, messages);
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        try
        {
            foreach (var queueUrl in _queueUrls)
            {
                if (!string.IsNullOrEmpty(queueUrl))
                {
                    var deleteQueue =
                        GetYesNoResponse($"Delete queue with url {queueUrl}?");
```

```
                    if (deleteQueue)
                    {
                        await SqsWrapper.DeleteQueueByUrl(queueUrl);
                    }
                }
            }

            foreach (var subscriptionArn in _subscriptionArns)
            {
                if (!string.IsNullOrEmpty(subscriptionArn))
                {
                    await SnsWrapper.UnsubscribeByArn(subscriptionArn);
                }
            }

            var deleteTopic = GetYesNoResponse($"Delete topic {_topicName}?");
            if (deleteTopic)
            {
                await SnsWrapper.DeleteTopicByArn(_topicArn);
            }
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Unable to clean up resources. Here's why:
 {ex.Message}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question, bool defaultAnswer =
 true)
    {
        if (UseConsole)
        {
            Console.WriteLine(question);
            var ynResponse = Console.ReadLine();
```

```
            var response = ynResponse != null &&
                           ynResponse.Equals("y",
                               StringComparison.InvariantCultureIgnoreCase);
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }

    /// <summary>
    /// Helper method to get a string response from the user through the console.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static string GetUserResponse(string question, string defaultAnswer)
    {
        if (UseConsole)
        {
            var response = "";
            while (string.IsNullOrEmpty(response))
            {
                Console.WriteLine(question);
                response = Console.ReadLine();
            }
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }
}
```

Crie uma classe que envolva as operações do Amazon SQS.

```
/// <summary>
/// Wrapper for Amazon Simple Queue Service (SQS) operations.
/// </summary>
public class SQSWrapper
{
    private readonly IAmazonSQS _amazonSQSClient;
```

```
    /// <summary>
    /// Constructor for the Amazon SQS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SQS client.</param>
    public SQSWrapper(IAmazonSQS amazonSQS)
    {
        _amazonSQSClient = amazonSQS;
    }

    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
useFifoQueue)
    {
        int maxMessage = 256 * 1024;
        var queueAttributes = new Dictionary<string, string>
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
```

```
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
            });
        return createResponse.QueueUrl;
    }

    /// <summary>
    /// Get the ARN for a queue from its URL.
    /// </summary>
    /// <param name="queueUrl">The URL of the queue.</param>
    /// <returns>The ARN of the queue.</returns>
    public async Task<string> GetQueueArnByUrl(string queueUrl)
    {
        var getAttributesRequest = new GetQueueAttributesRequest()
        {
            QueueUrl = queueUrl,
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await
_amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }

    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string
topicArn, string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
```

```
                                        "\"Effect\": \"Allow\"," +
                                        "\"Principal\": {" +
                                            $"\"Service\": " +
                                                "\"sns.amazonaws.com\"" +
                                               "}," +
                                        "\"Action\": \"sqs:SendMessage\"," +
                                        $"\"Resource\": \"{queueArn}\"," +
                                         "\"Condition\": {" +
                                              "\"ArnEquals\": {" +
                                                  $"\"aws:SourceArn\":
 \"{topicArn}\"" +
                                               "}" +
                                            "}" +
                                     "}]" +
                                  "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
                QueueUrl = queueUrl,
                Attributes = new Dictionary<string, string>() { { "Policy",
 queuePolicy } }
            });
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
```

```
        return messageResponse.Messages;
    }

    /// <summary>
    /// Delete a batch of messages from a queue by its url.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMessageBatchByUrl(string queueUrl,
 List<Message> messages)
    {
        var deleteRequest = new DeleteMessageBatchRequest()
        {
            QueueUrl = queueUrl,
            Entries = new List<DeleteMessageBatchRequestEntry>()
        };
        foreach (var message in messages)
        {
            deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
            {
                ReceiptHandle = message.ReceiptHandle,
                Id = message.MessageId
            });
        }

        var deleteResponse = await
 _amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

        return deleteResponse.Failed.Any();
    }

    /// <summary>
    /// Delete a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteQueueByUrl(string queueUrl)
    {
        var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
            new DeleteQueueRequest()
            {
                QueueUrl = queueUrl
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
```

```
    }
}
```

Crie uma classe que envolva as operações do Amazon SNS.

```
/// <summary>
/// Wrapper for Amazon Simple Notification Service (SNS) operations.
/// </summary>
public class SNSWrapper
{
    private readonly IAmazonSimpleNotificationService _amazonSNSClient;

    /// <summary>
    /// Constructor for the Amazon SNS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SNS client.</param>
    public SNSWrapper(IAmazonSimpleNotificationService amazonSNS)
    {
        _amazonSNSClient = amazonSNS;
    }

    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
```

```
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
                { "FifoTopic", "true" }
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
"true");
            }
        }

        var createResponse = await
_amazonSNSClient.CreateTopicAsync(createTopicRequest);
        return createResponse.TopicArn;
    }

    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
```

```
        }

        var subscribeResponse = await
 _amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }

    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</
param>
    /// <param name="attributeValue">The optional attribute value for the
 message.</param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
```

```
                    { attributeName!, new MessageAttributeValue() { StringValue =
 attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await
 _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }


    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
            {
                SubscriptionArn = subscriptionArn
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete a topic by its topic ARN.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTopicByArn(string topicArn)
    {
        var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
            new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon
 SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
```

```
   printAsterisksLine();
   std::cout << "In this workflow, you will create an SNS topic and subscribe "
             << NUMBER_OF_QUEUES <<
             " SQS queues to the topic." << std::endl;
   std::cout
           << "You can select from several options for configuring the topic and
the subscriptions for the "
           << NUMBER_OF_QUEUES << " queues." << std::endl;
   std::cout << "You can then post to the topic and see the results in the
queues."
             << std::endl;

   Aws::SNS::SNSClient snsClient(clientConfiguration);

   printAsterisksLine();

   std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
             << std::endl;
   std::cout
           << "FIFO topics deliver messages in order and support deduplication
and message filtering."
           << std::endl;
   bool isFifoTopic = askYesNoQuestion(
           "Would you like to work with FIFO topics? (y/n) ");

   bool contentBasedDeduplication = false;
   Aws::String topicName;
   if (isFifoTopic) {
       printAsterisksLine();
       std::cout << "Because you have chosen a FIFO topic, deduplication is
supported."
                 << std::endl;
       std::cout
               << "Deduplication IDs are either set in the message or
automatically generated "
               << "from content using a hash function." << std::endl;
       std::cout
               << "If a message is successfully published to an SNS FIFO topic,
any message "
               << "published and determined to have the same deduplication ID, "
               << std::endl;
       std::cout
               << "within the five-minute deduplication interval, is accepted
but not delivered."
```

```
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a
 deduplication ID? (y/n) ");
    }

    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
    {
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;

        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
 appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
 snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
```

```
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " <<
std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                        "true");
```

```
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue,
'.fifo' must "
                            << "be appended to the queue name." << std::endl;
                }
            }

            request.SetQueueName(queueName);
            queueNames.push_back(queueName);

            Aws::SQS::Model::CreateQueueOutcome outcome =
                    sqsClient.CreateQueue(request);

            if (outcome.IsSuccess()) {
                queueURL = outcome.GetResult().GetQueueUrl();
                std::cout << "Your new SQS queue with the name '" << queueName
                          << "' and the queue URL " << std::endl;
                std::cout << "'" << queueURL << "' has been created." <<
std::endl;
            }
            else {
                std::cerr << "Error with SQS::CreateQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
        queueURLS.push_back(queueURL);

        if (first) // Only explain this once.
        {
            std::cout
```

```
                    << "The queue URL is used to retrieve the queue ARN, which is
"
                    << "used to create a subscription." << std::endl;
        }

        Aws::String queueARN;
        {
            // 3.  Get the SQS queue ARN attribute.
            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
```

```
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        if (first) {
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling
it to receive "
                       "messages from an SNS topic." << std::endl;
        }

        {
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
```

```
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have
 filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then
 only the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/
sns-message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a
 \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;
```

```
                        std::cout << "This is the filter policy for this
subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
filter "
                                << "will be added to this subscription." <<
std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN <<
"."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

```
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
                        << "Because you are using a FIFO topic, you must set a
message group ID."
                        << std::endl;
                std::cout
                        << "All messages within the same group will be received
in the "
                        << "order they were published." << std::endl;
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
```

```
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }

        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
```

```
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
 outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
```

```
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }

        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);
```

```
                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}


bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
                                      const Aws::Vector<Aws::String>
 &subscriptionARNS,
                                      const Aws::SNS::SNSClient &snsClient,
                                      const Aws::SQS::SQSClient &sqsClient,
                                      bool askUser) {
    bool result = true;
    printAsterisksLine();
    if (!queueURLS.empty() && askUser &&
        askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

        for (const auto &queueURL: queueURLS) {
            // 9.  Delete an SQS queue.
            Aws::SQS::Model::DeleteQueueRequest request;
            request.SetQueueUrl(queueURL);

            Aws::SQS::Model::DeleteQueueOutcome outcome =
                    sqsClient.DeleteQueue(request);

            if (outcome.IsSuccess()) {
                std::cout << "The queue with URL '" << queueURL
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

```
        }

        for (const auto &subscriptionARN: subscriptionARNS) {
            // 10. Unsubscribe an SNS subscription.
            Aws::SNS::Model::UnsubscribeRequest request;
            request.SetSubscriptionArn(subscriptionARN);

            Aws::SNS::Model::UnsubscribeOutcome outcome =
                    snsClient.Unsubscribe(request);

            if (outcome.IsSuccess()) {
                std::cout << "Unsubscribe of subscription ARN '" <<
subscriptionARN
                          << "' was successful." << std::endl;
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    printAsterisksLine();
    if (!topicARN.empty() && askUser &&
        askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

        // 11. Delete an SNS topic.
        Aws::SNS::Model::DeleteTopicRequest request;
        request.SetTopicArn(topicARN);

        Aws::SNS::Model::DeleteTopicOutcome outcome =
snsClient.DeleteTopic(request);

        if (outcome.IsSuccess()) {
            std::cout << "The topic with ARN '" << topicARN
                      << "' was successfully deleted." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
```

```
        }
    }

    return result;
}

//! Create an IAM policy that gives an SQS queue permission to receive messages
 from an SNS topic.
/*!
 \sa createPolicyForQueue()
 \param queueARN: The SQS queue Amazon Resource Name (ARN).
 \param topicARN: The SNS topic ARN.
 \return Aws::String: The policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
                                                           const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.

- CreateQueue
- CreateTopic
- DeleteMessageBatch
- DeleteQueue
- DeleteTopic
- GetQueueAttributes
- Publicar
- ReceiveMessage
- SetQueueAttributes
- Assinar
- Cancelar assinatura

Go

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
const FIFO_SUFFIX = ".fifo"
const TONE_KEY = "tone"

var ToneChoices = []string{"cheerful", "funny", "serious", "sincere"}

// MessageBody is used to deserialize the body of a message from a JSON string.
type MessageBody struct {
 Message string
}

// ScenarioRunner separates the steps of this scenario into individual functions
 so that
```

```
// they are simpler to read and understand.
type ScenarioRunner struct {
 questioner demotools.IQuestioner
 snsActor   *actions.SnsActions
 sqsActor   *actions.SqsActions
}

func (runner ScenarioRunner) CreateTopic() (string, string, bool, bool) {
 log.Println("SNS topics can be configured as FIFO (First-In-First-Out) or
 standard.\n" +
  "FIFO topics deliver messages in order and support deduplication and message
 filtering.")
 isFifoTopic := runner.questioner.AskBool("\nWould you like to work with FIFO
 topics? (y/n) ", "y")

 contentBasedDeduplication := false
 if isFifoTopic {
  log.Println(strings.Repeat("-", 88))
  log.Println("Because you have chosen a FIFO topic, deduplication is supported.
\n" +
   "Deduplication IDs are either set in the message or are automatically
 generated\n" +
   "from content using a hash function. If a message is successfully published to
\n" +
   "an SNS FIFO topic, any message published and determined to have the same\n" +
   "deduplication ID, within the five-minute deduplication interval, is accepted
\n" +
   "but not delivered. For more information about deduplication, see:\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/fifo-message-dedup.html.")
  contentBasedDeduplication = runner.questioner.AskBool(
   "\nDo you want to use content-based deduplication instead of entering a
 deduplication ID? (y/n) ", "y")
 }
 log.Println(strings.Repeat("-", 88))

 topicName := runner.questioner.Ask("Enter a name for your SNS topic. ")
 if isFifoTopic {
  topicName = fmt.Sprintf("%v%v", topicName, FIFO_SUFFIX)
  log.Printf("Because you have selected a FIFO topic, '%v' must be appended to
\n"+
   "the topic name.", FIFO_SUFFIX)
 }
```

```
 topicArn, err := runner.snsActor.CreateTopic(topicName, isFifoTopic,
 contentBasedDeduplication)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new topic with the name '%v' and Amazon Resource Name (ARN)
 \n"+
  "'%v' has been created.", topicName, topicArn)

 return topicName, topicArn, isFifoTopic, contentBasedDeduplication
}

func (runner ScenarioRunner) CreateQueue(ordinal string, isFifoTopic bool)
 (string, string) {
 queueName := runner.questioner.Ask(fmt.Sprintf("Enter a name for the %v SQS
 queue. ", ordinal))
 if isFifoTopic {
  queueName = fmt.Sprintf("%v%v", queueName, FIFO_SUFFIX)
  if ordinal == "first" {
   log.Printf("Because you are creating a FIFO SQS queue, '%v' must "+
    "be appended to the queue name.\n", FIFO_SUFFIX)
  }
 }
 queueUrl, err := runner.sqsActor.CreateQueue(queueName, isFifoTopic)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new SQS queue with the name '%v' and the queue URL "+
  "'%v' has been created.", queueName, queueUrl)

 return queueName, queueUrl
}

func (runner ScenarioRunner) SubscribeQueueToTopic(
 queueName string, queueUrl string, topicName string, topicArn string, ordinal
 string,
 isFifoTopic bool) (string, bool) {

 queueArn, err := runner.sqsActor.GetQueueArn(queueUrl)
 if err != nil {
  panic(err)
 }
 log.Printf("The ARN of your queue is: %v.\n", queueArn)
```

```
err = runner.sqsActor.AttachSendMessagePolicy(queueUrl, queueArn, topicArn)
if err != nil {
 panic(err)
}
log.Println("Attached an IAM policy to the queue so the SNS topic can send " +
 "messages to it.")
log.Println(strings.Repeat("-", 88))

var filterPolicy map[string][]string
if isFifoTopic {
 if ordinal == "first" {
  log.Println("Subscriptions to a FIFO topic can have filters.\n" +
   "If you add a filter to this subscription, then only the filtered messages\n"
+
   "will be received in the queue.\n" +
   "For information about message filtering, see\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/sns-message-filtering.html\n" +
   "For this example, you can filter messages by a \"tone\" attribute.")
 }

 wantFiltering := runner.questioner.AskBool(
  fmt.Sprintf("Do you want to filter messages that are sent to \"%v\"\n"+
   "from the %v topic? (y/n) ", queueName, topicName), "y")
 if wantFiltering {
  log.Println("You can filter messages by one or more of the following \"tone\"
attributes.")

  var toneSelections []string
  askAboutTones := true
  for askAboutTones {
   toneIndex := runner.questioner.AskChoice(
    "Enter the number of the tone you want to filter by:\n", ToneChoices)
   toneSelections = append(toneSelections, ToneChoices[toneIndex])
   askAboutTones = runner.questioner.AskBool("Do you want to add another tone to
the filter? (y/n) ", "y")
  }
  log.Printf("Your subscription will be filtered to only pass the following
tones: %v\n", toneSelections)
  filterPolicy = map[string][]string{TONE_KEY: toneSelections}
 }
}

subscriptionArn, err := runner.snsActor.SubscribeQueue(topicArn, queueArn,
filterPolicy)
```

```
 if err != nil {
  panic(err)
 }
 log.Printf("The queue %v is now subscribed to the topic %v with the subscription
 ARN %v.\n",
  queueName, topicName, subscriptionArn)

 return subscriptionArn, filterPolicy != nil
}

func (runner ScenarioRunner) PublishMessages(topicArn string, isFifoTopic bool,
 contentBasedDeduplication bool, usingFilters bool) {
 var message string
 var groupId string
 var dedupId string
 var toneSelection string
 publishMore := true
 for publishMore {
  groupId = ""
  dedupId = ""
  toneSelection = ""
  message = runner.questioner.Ask("Enter a message to publish: ")
  if isFifoTopic {
   log.Println("Because you are using a FIFO topic, you must set a message group
 ID.\n" +
    "All messages within the same group will be received in the order they were
 published.")
   groupId = runner.questioner.Ask("Enter a message group ID: ")
   if !contentBasedDeduplication {
    log.Println("Because you are not using content-based deduplication,\n" +
     "you must enter a deduplication ID.")
    dedupId = runner.questioner.Ask("Enter a deduplication ID: ")
   }
  }
  if usingFilters {
   if runner.questioner.AskBool("Add a tone attribute so this message can be
 filtered? (y/n) ", "y") {
    toneIndex := runner.questioner.AskChoice(
     "Enter the number of the tone you want to filter by:\n", ToneChoices)
    toneSelection = ToneChoices[toneIndex]
   }
  }
```

```
  err := runner.snsActor.Publish(topicArn, message, groupId, dedupId, TONE_KEY,
 toneSelection)
  if err != nil {
   panic(err)
  }
  log.Println(("Your message was published."))

  publishMore = runner.questioner.AskBool("Do you want to publish another
 messsage? (y/n) ", "y")
 }
}

func (runner ScenarioRunner) PollForMessages(queueUrls []string) {
 log.Println("Polling queues for messages...")
 for _, queueUrl := range queueUrls {
  var messages []types.Message
  for {
   currentMsgs, err := runner.sqsActor.GetMessages(queueUrl, 10, 1)
   if err != nil {
    panic(err)
   }
   if len(currentMsgs) == 0 {
    break
   }
   messages = append(messages, currentMsgs...)
  }
  if len(messages) == 0 {
   log.Printf("No messages were received by queue %v.\n", queueUrl)
  } else if len(messages) == 1 {
   log.Printf("One message was received by queue %v:\n", queueUrl)

  } else {
   log.Printf("%v messages were received by queue %v:\n", len(messages),
 queueUrl)
  }
  for msgIndex, message := range messages {
   messageBody := MessageBody{}
   err := json.Unmarshal([]byte(*message.Body), &messageBody)
   if err != nil {
    panic(err)
   }
   log.Printf("Message %v: %v\n", msgIndex+1, messageBody.Message)
  }
```

```
  if len(messages) > 0 {
   log.Printf("Deleting %v messages from queue %v.\n", len(messages), queueUrl)
   err := runner.sqsActor.DeleteMessages(queueUrl, messages)
   if err != nil {
    panic(err)
   }
  }
 }
}

// RunTopicsAndQueuesScenario is an interactive example that shows you how to use
 the
// AWS SDK for Go to create and use Amazon SNS topics and Amazon SQS queues.
//
// 1. Create a topic (FIFO or non-FIFO).
// 2. Subscribe several queues to the topic with an option to apply a filter.
// 3. Publish messages to the topic.
// 4. Poll the queues for messages received.
// 5. Delete the topic and the queues.
//
// This example creates service clients from the specified sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
func RunTopicsAndQueuesScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner) {
 resources := Resources{}
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.\n" +
    "Cleaning up any resources that were created...")
   resources.Cleanup()
  }
 }()
 queueCount := 2

 log.Println(strings.Repeat("-", 88))
 log.Printf("Welcome to messaging with topics and queues.\n\n"+
  "In this workflow, you will create an SNS topic and subscribe %v SQS queues to
 the\n"+
  "topic. You can select from several options for configuring the topic and the
\n"+
```

```
  "subscriptions for the queues. You can then post to the topic and see the
 results\n"+
  "in the queues.\n", queueCount)

 log.Println(strings.Repeat("-", 88))

 runner := ScenarioRunner{
  questioner: questioner,
  snsActor:   &actions.SnsActions{SnsClient: sns.NewFromConfig(sdkConfig)},
  sqsActor:   &actions.SqsActions{SqsClient: sqs.NewFromConfig(sdkConfig)},
 }
 resources.snsActor = runner.snsActor
 resources.sqsActor = runner.sqsActor

 topicName, topicArn, isFifoTopic, contentBasedDeduplication :=
 runner.CreateTopic()
 resources.topicArn = topicArn
 log.Println(strings.Repeat("-", 88))

 log.Printf("Now you will create %v SQS queues and subscribe them to the topic.
\n", queueCount)
 ordinals := []string{"first", "next"}
 usingFilters := false
 for _, ordinal := range ordinals {
  queueName, queueUrl := runner.CreateQueue(ordinal, isFifoTopic)
  resources.queueUrls = append(resources.queueUrls, queueUrl)

  _, filtering := runner.SubscribeQueueToTopic(queueName, queueUrl, topicName,
 topicArn, ordinal, isFifoTopic)
  usingFilters = usingFilters || filtering
 }

 log.Println(strings.Repeat("-", 88))
 runner.PublishMessages(topicArn, isFifoTopic, contentBasedDeduplication,
 usingFilters)
 log.Println(strings.Repeat("-", 88))
 runner.PollForMessages(resources.queueUrls)

 log.Println(strings.Repeat("-", 88))

 wantCleanup := questioner.AskBool("Do you want to remove all AWS resources
 created for this scenario? (y/n) ", "y")
 if wantCleanup {
  log.Println("Cleaning up resources...")
```

```
  resources.Cleanup()
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura que envolva as ações do Amazon SNS usadas neste exemplo.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
```

```
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}



// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to
 an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string,
 filterMap map[string][]string) (string, error) {
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
```

```
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent
 to all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered
 according to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn,
 err)
 }
```

```
 return err
}
```

Defina uma estrutura que envolva as ações do Amazon SQS usadas neste exemplo.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// CreateQueue creates an Amazon SQS queue with the specified name. You can
 specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
}



// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
```

```
// of an Amazon SQS queue.
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}



// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy
 to an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages
 to the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
```

```
  Attributes: map[string]string{
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}

// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
```

```
 if err != nil {
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 } else {
  messages = result.Messages
 }
 return messages, err
}



// DeleteMessages uses the DeleteMessageBatch action to delete a batch of
 messages from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada para esse fluxo de trabalho.

```
import { SNSClient } from "@aws-sdk/client-sns";
import { SQSClient } from "@aws-sdk/client-sqs";

import { TopicsQueuesWkflw } from "./TopicsQueuesWkflw.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { SlowLogger } from "@aws-sdk-examples/libs/slow-logger.js";

export const startSnsWorkflow = () => {
```

```
  const noLoggerDelay = process.argv.find((arg) => arg === "--no-logger-delay");
  const snsClient = new SNSClient({});
  const sqsClient = new SQSClient({});
  const prompter = new Prompter();
  const logger = noLoggerDelay ? console : new SlowLogger(25);

  const wkflw = new TopicsQueuesWkflw(snsClient, sqsClient, prompter, logger);

  wkflw.start();
};
```

O código anterior fornece as dependências necessárias e inicia o fluxo de trabalho. A próxima seção contém a maior parte do exemplo.

```
const toneChoices = [
  { name: "cheerful", value: "cheerful" },
  { name: "funny", value: "funny" },
  { name: "serious", value: "serious" },
  { name: "sincere", value: "sincere" },
];

export class TopicsQueuesWkflw {
  // SNS topic is configured as First-In-First-Out
  isFifo = true;

  // Automatic content-based deduplication is enabled.
  autoDedup = false;

  snsClient;
  sqsClient;
  topicName;
  topicArn;
  subscriptionArns = [];
  /**
   * @type {{ queueName: string, queueArn: string, queueUrl: string, policy?:
 string }[]}
   */
  queues = [];
  prompter;
```

```
  /**
   * @param {import('@aws-sdk/client-sns').SNSClient} snsClient
   * @param {import('@aws-sdk/client-sqs').SQSClient} sqsClient
   * @param {import('../../libs/prompter.js').Prompter} prompter
   * @param {import('../../libs/logger.js').Logger} logger
   */
  constructor(snsClient, sqsClient, prompter, logger) {
    this.snsClient = snsClient;
    this.sqsClient = sqsClient;
    this.prompter = prompter;
    this.logger = logger;
  }

  async welcome() {
    await this.logger.log(MESSAGES.description);
  }

  async confirmFifo() {
    await this.logger.log(MESSAGES.snsFifoDescription);
    this.isFifo = await this.prompter.confirm({
      message: MESSAGES.snsFifoPrompt,
    });

    if (this.isFifo) {
      this.logger.logSeparator(MESSAGES.headerDedup);
      await this.logger.log(MESSAGES.deduplicationNotice);
      await this.logger.log(MESSAGES.deduplicationDescription);
      this.autoDedup = await this.prompter.confirm({
        message: MESSAGES.deduplicationPrompt,
      });
    }
  }

  async createTopic() {
    await this.logger.log(MESSAGES.creatingTopics);
    this.topicName = await this.prompter.input({
      message: MESSAGES.topicNamePrompt,
    });
    if (this.isFifo) {
      this.topicName += ".fifo";
      this.logger.logSeparator(MESSAGES.headerFifoNaming);
      await this.logger.log(MESSAGES.appendFifoNotice);
    }
```

```
    const response = await this.snsClient.send(
      new CreateTopicCommand({
        Name: this.topicName,
        Attributes: {
          FifoTopic: this.isFifo ? "true" : "false",
          ...(this.autoDedup ? { ContentBasedDeduplication: "true" } : {}),
        },
      }),
    );

    this.topicArn = response.TopicArn;

    await this.logger.log(
      MESSAGES.topicCreatedNotice
        .replace("${TOPIC_NAME}", this.topicName)
        .replace("${TOPIC_ARN}", this.topicArn),
    );
  }

  async createQueues() {
    await this.logger.log(MESSAGES.createQueuesNotice);
    // Increase this number to add more queues.
    let maxQueues = 2;

    for (let i = 0; i < maxQueues; i++) {
      await this.logger.log(MESSAGES.queueCount.replace("${COUNT}", i + 1));
      let queueName = await this.prompter.input({
        message: MESSAGES.queueNamePrompt.replace(
          "${EXAMPLE_NAME}",
          i === 0 ? "good-news" : "bad-news",
        ),
      });

      if (this.isFifo) {
        queueName += ".fifo";
        await this.logger.log(MESSAGES.appendFifoNotice);
      }

      const response = await this.sqsClient.send(
        new CreateQueueCommand({
          QueueName: queueName,
          Attributes: { ...(this.isFifo ? { FifoQueue: "true" } : {}) },
        }),
      );
```

```
      const { Attributes } = await this.sqsClient.send(
        new GetQueueAttributesCommand({
          QueueUrl: response.QueueUrl,
          AttributeNames: ["QueueArn"],
        }),
      );

      this.queues.push({
        queueName,
        queueArn: Attributes.QueueArn,
        queueUrl: response.QueueUrl,
      });

      await this.logger.log(
        MESSAGES.queueCreatedNotice
          .replace("${QUEUE_NAME}", queueName)
          .replace("${QUEUE_URL}", response.QueueUrl)
          .replace("${QUEUE_ARN}", Attributes.QueueArn),
      );
    }
  }

  async attachQueueIamPolicies() {
    for (const [index, queue] of this.queues.entries()) {
      const policy = JSON.stringify(
        {
          Statement: [
            {
              Effect: "Allow",
              Principal: {
                Service: "sns.amazonaws.com",
              },
              Action: "sqs:SendMessage",
              Resource: queue.queueArn,
              Condition: {
                ArnEquals: {
                  "aws:SourceArn": this.topicArn,
                },
              },
            },
          ],
        },
        null,
```

```
        2,
      );

      if (index !== 0) {
        this.logger.logSeparator();
      }

      await this.logger.log(MESSAGES.attachPolicyNotice);
      console.log(policy);
      const addPolicy = await this.prompter.confirm({
        message: MESSAGES.addPolicyConfirmation.replace(
          "${QUEUE_NAME}",
          queue.queueName,
        ),
      });

      if (addPolicy) {
        await this.sqsClient.send(
          new SetQueueAttributesCommand({
            QueueUrl: queue.queueUrl,
            Attributes: {
              Policy: policy,
            },
          }),
        );
        queue.policy = policy;
      } else {
        await this.logger.log(
          MESSAGES.policyNotAttachedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }
  }

  async subscribeQueuesToTopic() {
    for (const [index, queue] of this.queues.entries()) {
      /**
       * @type {import('@aws-sdk/client-sns').SubscribeCommandInput}
       */
      const subscribeParams = {
        TopicArn: this.topicArn,
```

```
        Protocol: "sqs",
        Endpoint: queue.queueArn,
      };
      let tones = [];

      if (this.isFifo) {
        if (index === 0) {
          await this.logger.log(MESSAGES.fifoFilterNotice);
        }
        tones = await this.prompter.checkbox({
          message: MESSAGES.fifoFilterSelect.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
          choices: toneChoices,
        });

        if (tones.length) {
          subscribeParams.Attributes = {
            FilterPolicyScope: "MessageAttributes",
            FilterPolicy: JSON.stringify({
              tone: tones,
            }),
          };
        }
      }

      const { SubscriptionArn } = await this.snsClient.send(
        new SubscribeCommand(subscribeParams),
      );

      this.subscriptionArns.push(SubscriptionArn);

      await this.logger.log(
        MESSAGES.queueSubscribedNotice
          .replace("${QUEUE_NAME}", queue.queueName)
          .replace("${TOPIC_NAME}", this.topicName)
          .replace("${TONES}", tones.length ? tones.join(", ") : "none"),
      );
    }
  }

  async publishMessages() {
    const message = await this.prompter.input({
```

```
      message: MESSAGES.publishMessagePrompt,
    });

    let groupId, deduplicationId, choices;

    if (this.isFifo) {
      await this.logger.log(MESSAGES.groupIdNotice);
      groupId = await this.prompter.input({
        message: MESSAGES.groupIdPrompt,
      });

      if (this.autoDedup === false) {
        await this.logger.log(MESSAGES.deduplicationIdNotice);
        deduplicationId = await this.prompter.input({
          message: MESSAGES.deduplicationIdPrompt,
        });
      }

      choices = await this.prompter.checkbox({
        message: MESSAGES.messageAttributesPrompt,
        choices: toneChoices,
      });
    }

    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
```

```
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });

    if (publishAnother) {
      await this.publishMessages();
    }
  }

  async receiveAndDeleteMessages() {
    for (const queue of this.queues) {
      const { Messages } = await this.sqsClient.send(
        new ReceiveMessageCommand({
          QueueUrl: queue.queueUrl,
        }),
      );

      if (Messages) {
        await this.logger.log(
          MESSAGES.messagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
        console.log(Messages);

        await this.sqsClient.send(
          new DeleteMessageBatchCommand({
            QueueUrl: queue.queueUrl,
            Entries: Messages.map((message) => ({
              Id: message.MessageId,
              ReceiptHandle: message.ReceiptHandle,
            })),
          }),
        );
      } else {
        await this.logger.log(
```

```
          MESSAGES.noMessagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }

    const deleteAndPoll = await this.prompter.confirm({
      message: MESSAGES.deleteAndPollConfirmation,
    });

    if (deleteAndPoll) {
      await this.receiveAndDeleteMessages();
    }
  }

  async destroyResources() {
    for (const subscriptionArn of this.subscriptionArns) {
      await this.snsClient.send(
        new UnsubscribeCommand({ SubscriptionArn: subscriptionArn }),
      );
    }

    for (const queue of this.queues) {
      await this.sqsClient.send(
        new DeleteQueueCommand({ QueueUrl: queue.queueUrl }),
      );
    }

    if (this.topicArn) {
      await this.snsClient.send(
        new DeleteTopicCommand({ TopicArn: this.topicArn }),
      );
    }
  }

  async start() {
    console.clear();

    try {
      this.logger.logSeparator(MESSAGES.headerWelcome);
      await this.welcome();
      this.logger.logSeparator(MESSAGES.headerFifo);
```

```
      await this.confirmFifo();
      this.logger.logSeparator(MESSAGES.headerCreateTopic);
      await this.createTopic();
      this.logger.logSeparator(MESSAGES.headerCreateQueues);
      await this.createQueues();
      this.logger.logSeparator(MESSAGES.headerAttachPolicy);
      await this.attachQueueIamPolicies();
      this.logger.logSeparator(MESSAGES.headerSubscribeQueues);
      await this.subscribeQueuesToTopic();
      this.logger.logSeparator(MESSAGES.headerPublishMessage);
      await this.publishMessages();
      this.logger.logSeparator(MESSAGES.headerReceiveMessages);
      await this.receiveAndDeleteMessages();
    } catch (err) {
      console.error(err);
    } finally {
      await this.destroyResources();
    }
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos sem servidor para o Amazon SNS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Notification Service (Amazon SNS) com SDKs da AWS.

Exemplos

- Invocar uma função do Lambda em um acionador do Amazon SNS

Invocar uma função do Lambda em um acionador do Amazon SNS

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SNSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace SnsIntegration;

public class Function
{
    public async Task FunctionHandler(SNSEvent evnt, ILambdaContext context)
    {
```

```
        foreach (var record in evnt.Records)
        {
            await ProcessRecordAsync(record, context);
        }
        context.Logger.LogInformation("done");
    }

    private async Task ProcessRecordAsync(SNSEvent.SNSRecord record,
 ILambdaContext context)
    {
        try
        {
            context.Logger.LogInformation($"Processed record
 {record.Sns.Message}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Go.

```
package main
```

```
import (
 "context"
 "fmt"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, snsEvent events.SNSEvent) {
 for _, record := range snsEvent.Records {
  processMessage(record)
 }
 fmt.Println("done")
}

func processMessage(record events.SNSEventRecord) {
 message := record.SNS.Message
 fmt.Printf("Processed message: %s\n", message)
 // TODO: Process your record here
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
```

```
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SNSEvent;
import com.amazonaws.services.lambda.runtime.events.SNSEvent.SNSRecord;


import java.util.Iterator;
import java.util.List;

public class SNSEventHandler implements RequestHandler<SNSEvent, Boolean> {
    LambdaLogger logger;

    @Override
    public Boolean handleRequest(SNSEvent event, Context context) {
        logger = context.getLogger();
        List<SNSRecord> records = event.getRecords();
        if (!records.isEmpty()) {
            Iterator<SNSRecord> recordsIter = records.iterator();
            while (recordsIter.hasNext()) {
                processRecord(recordsIter.next());
            }
        }
        return Boolean.TRUE;
    }

    public void processRecord(SNSRecord record) {
        try {
            String message = record.getSNS().getMessage();
            logger.log("message: " + message);
        } catch (Exception e) {
            throw new RuntimeException(e);
        }
    }

}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do SNS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};

async function processMessageAsync(record) {
  try {
    const message = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento do SNS com o TypeScript Lambda usando.

```
import { SNSEvent, Context, SNSHandler, SNSEventRecord } from "aws-lambda";

export const functionHandler: SNSHandler = async (
  event: SNSEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
```

```
  console.info("done");
};

async function processMessageAsync(record: SNSEventRecord): Promise<any> {
  try {
    const message: string = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando PHP.

```
<?php

/*
Since native PHP support for AWS Lambda is not available, we are utilizing Bref's
 PHP functions runtime for AWS Lambda.
For more information on Bref's PHP runtime for Lambda, refer to: https://bref.sh/
docs/runtimes/function

Another approach would be to create a custom runtime.
A practical example can be found here: https://aws.amazon.com/blogs/apn/aws-
lambda-custom-runtime-for-php-a-practical-example/
*/

// Additional composer packages may be required when using Bref or any other PHP
 functions runtime.
```

```
// require __DIR__ . '/vendor/autoload.php';

return function ($event, $context) {
    foreach ($event["Records"] as $record) {
        processMessage($record);
    }
    echo "Done!" . PHP_EOL;
};

function processMessage($record)
{
    try {
        $message = $record['Sns']['Message'];
        echo "Processed Message: {$message}" . PHP_EOL;
    } catch (Exception $e) {
        echo "Error occured: {$e->getMessage()}" . PHP_EOL;
        throw $e;
    }
}
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for record in event['Records']:
        process_message(record)
    print("done")

def process_message(record):
    try:
        message = record['Sns']['Message']
        print(f"Processed message {message}")
```

```
        # TODO; Process your record here

    except Exception as e:
        print("An error occurred")
        raise e
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].map { |record| process_message(record) }
end

def process_message(record)
  message = record['Sns']['Message']
  puts("Processing message: #{message}")
rescue StandardError => e
  puts("Error processing message: #{e}")
  raise
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SNS com o Lambda usando Rust.

```
use aws_lambda_events::event::sns::SnsEvent;
use aws_lambda_events::sns::SnsRecord;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};
use tracing::info;

// Built with the following dependencies:
//  aws_lambda_events = { version = "0.10.0", default-features = false, features
 = ["sns"] }
//  lambda_runtime = "0.8.1"
//  tokio = { version = "1", features = ["macros"] }
//  tracing = { version = "0.1", features = ["log"] }
//  tracing-subscriber = { version = "0.3", default-features = false, features =
 ["fmt"] }

async fn function_handler(event: LambdaEvent<SnsEvent>) -> Result<(), Error> {
    for event in event.payload.records {
        process_record(&event)?;
    }

    Ok(())
}

fn process_record(record: &SnsRecord) -> Result<(), Error> {
    info!("Processing SNS Message: {}", record.sns.message);

    // Implement your record handling code here.

    Ok(())
}

#[tokio::main]
```

```
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Exemplos de uso entre serviços do Amazon SNS com AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Simple Notification Service (Amazon SNS) com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação para enviar dados para uma tabela do DynamoDB
- Criar uma aplicação de publicação e assinatura que traduz mensagens
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação de exploração do Amazon Textract
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
- Usar o API Gateway para invocar uma função do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma aplicação para enviar dados para uma tabela do DynamoDB

Os exemplos de código a seguir mostram como criar uma aplicação que envia dados para uma tabela do Amazon DynamoDB e notifica você quando um usuário atualiza a tabela.

Java

SDK para Java 2.x

Mostra como criar uma aplicação Web dinâmica que envia dados usando a API Java do Amazon DynamoDB e envia uma mensagem de texto usando a API Java do Amazon Simple Notification Service.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Este exemplo mostra como criar uma aplicação que permite que os usuários enviem dados para uma tabela do Amazon DynamoDB e enviem uma mensagem de texto ao administrador usando o Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como criar uma aplicação Android nativa que envia dados usando a API Kotlin do Amazon DynamoDB e envia uma mensagem de texto usando a API Kotlin do Amazon SNS.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Criar uma aplicação de publicação e assinatura que traduz mensagens

Os exemplos de código a seguir mostram como criar uma aplicação que oferece funcionalidade de assinatura e publicação e tradução de mensagens.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para obter o código-fonte completo e instruções sobre como configurar e executar o exemplo que usa a API Java Async, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Kotlin

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon SNS para criar uma aplicação com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e as instruções sobre como criar um aplicativo web, veja o exemplo completo em GitHub.

Para ver o código-fonte completo e instruções sobre como criar um aplicativo Android nativo, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

O exemplo de código a seguir mostra como criar uma aplicação com tecnologia sem servidor que permite que os usuários gerenciem fotos usando rótulos.

.NET

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

C++

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Java

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway

- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Kotlin

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

PHP

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Rust

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação de exploração do Amazon Textract

Os exemplos de código a seguir mostram como explorar a saída do Amazon Textract por meio de uma aplicação interativa.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon Textract para detectar elementos de texto, formulários e tabelas em uma imagem de documento. A imagem de entrada e a saída do Amazon Textract são mostradas em uma aplicaçãoTkinter que permite explorar os elementos detectados.

- Envie uma imagem de documento para o Amazon Textract e explore a saída dos elementos detectados.

- Envie imagens diretamente para o Amazon Textract ou por meio de um bucket do Amazon Simple Storage Service (Amazon S3).
- Use APIs assíncronas para iniciar um trabalho que publica uma notificação em um tópico do Amazon Simple Notification Service (Amazon SNS) quando o trabalho for concluído.
- Faça uma pesquisa em uma fila do Amazon Simple Queue Service (Amazon SQS) para obter uma mensagem de conclusão do trabalho e exiba os resultados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar pessoas e objetos em um vídeo com o Amazon Rekognition.

Python

SDK para Python (Boto3)

Use o Amazon Rekognition para detectar rostos, objetos e pessoas em vídeos iniciando trabalhos de detecção assíncrona. Este exemplo também configura o Amazon Rekognition para notificar um tópico do Amazon Simple Notification Service (Amazon SNS) quando os trabalhos são concluídos e inscreve uma fila do Amazon Simple Queue Service (Amazon SQS) no tópico. Quando a fila recebe uma mensagem sobre um trabalho, o trabalho é recuperado e os resultados são apresentados.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition

- Amazon SNS
- Amazon SQS

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

Java

SDK para Java 2.x

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Kotlin

SDK for Kotlin

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Usar o API Gateway para invocar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma função do AWS Lambda invocada pelo Amazon API Gateway que envia mensagens de texto de aniversário.

Java

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar uma AWS Lambda função usando a API de tempo de JavaScript execução do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada

pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Usar eventos programados para chamar uma função do Lambda

Os exemplos de código a seguir mostram como criar uma AWS Lambda função invocada por um evento EventBridge agendado pela Amazon.

Java

SDK para Java 2.x

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função do Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- EventBridge
- Lambda
- Amazon SNS

JavaScript

SDK para JavaScript (v3)

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função Lambda usando a API de tempo de execução do JavaScript Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

Exemplos de código para Amazon SQS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Queue Service (Amazon SQS) com um Kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon SQS – Mais informações sobre o Amazon SQS.
- Referência da API do Amazon SQS – Detalhes sobre todas as ações disponíveis do Amazon SQS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SQS;
using Amazon.SQS.Model;

namespace SQSActions;

public static class HelloSQS
{
    static async Task Main(string[] args)
    {
```

```
        var sqsClient = new AmazonSQSClient();

        Console.WriteLine($"Hello Amazon SQS! Following are some of your
 queues:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five queues.
        var response = await sqsClient.ListQueuesAsync(
            new ListQueuesRequest()
            {
                MaxResults = 5
            });

        foreach (var queue in response.QueueUrls)
        {
            Console.WriteLine($"\tQueue Url: {queue}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sqs)
```

```
# Set this project's name.
project("hello_sqs")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed
 libraries for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if(WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory
 for running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you
 may need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif()

add_executable(${PROJECT_NAME}
        hello_sqs.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_sqs.cpp.

```
#include <aws/core/Aws.h>
```

```
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ListQueuesRequest.h>
#include <iostream>

/*
 *  A "Hello SQS" starter application that initializes an Amazon Simple Queue
 Service
 *  (Amazon SQS) client and lists the SQS queues in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sqs'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SQS::SQSClient sqsClient(clientConfig);

        Aws::Vector<Aws::String> allQueueUrls;
        Aws::String nextToken; // Next token is used to handle a paginated
 response.
        do {
            Aws::SQS::Model::ListQueuesRequest request;

            Aws::SQS::Model::ListQueuesOutcome outcome =
 sqsClient.ListQueues(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::String> &pageOfQueueUrls =
 outcome.GetResult().GetQueueUrls();
                if (!pageOfQueueUrls.empty()) {
                    allQueueUrls.insert(allQueueUrls.cend(),
 pageOfQueueUrls.cbegin(),
                                        pageOfQueueUrls.cend());
                }
```

```
            }
            else {
                std::cerr << "Error with SQS::ListQueues. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());


        std::cout << "Hello Amazon SQS! You have " << allQueueUrls.size() << "
 queue"
                  << (allQueueUrls.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allQueueUrls.empty()) {
            std::cout << "Here are your queue URLs." << std::endl;
            for (const Aws::String &queueUrl: allQueueUrls) {
                std::cout << "  * " << queueUrl << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for C++ da API.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sqs"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Queue Service
// (Amazon SQS) client and list the queues in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 sqsClient := sqs.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the queues for your account.")
 var queueUrls []string
 paginator := sqs.NewListQueuesPaginator(sqsClient, &sqs.ListQueuesInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get queues. Here's why: %v\n", err)
   break
  } else {
   queueUrls = append(queueUrls, output.QueueUrls...)
  }
 }
 if len(queueUrls) == 0 {
  fmt.Println("You don't have any queues!")
 } else {
  for _, queueUrl := range queueUrls {
   fmt.Printf("\t%v\n", queueUrl)
  }
 }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.SqsException;
import software.amazon.awssdk.services.sqs.paginators.ListQueuesIterable;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class HelloSQS {
    public static void main(String[] args) {
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        listQueues(sqsClient);
        sqsClient.close();
    }

    public static void listQueues(SqsClient sqsClient) {
        try {
            ListQueuesIterable listQueues = sqsClient.listQueuesPaginator();
```

```
            listQueues.stream()
                    .flatMap(r -> r.queueUrls().stream())
                    .forEach(content -> System.out.println(" Queue URL: " +
 content.toLowerCase()));

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicialize um cliente Amazon SQS e liste as filas.

```
import { SQSClient, paginateListQueues } from "@aws-sdk/client-sqs";

export const helloSqs = async () => {
  // The configuration object (`{}`) is required. If the region and credentials
  // are omitted, the SDK uses your local configuration if it exists.
  const client = new SQSClient({});

  // You can also use `ListQueuesCommand`, but to use that command you must
  // handle the pagination yourself. You can do that by sending the
 `ListQueuesCommand`
  // with the `NextToken` parameter from the previous request.
  const paginatedQueues = paginateListQueues({ client }, {});
  const queues = [];
```

```
  for await (const page of paginatedQueues) {
    if (page.QueueUrls?.length) {
      queues.push(...page.QueueUrls);
    }
  }

  const suffix = queues.length === 1 ? "" : "s";

  console.log(
    `Hello, Amazon SQS! You have ${queues.length} queue${suffix} in your
 account.`,
  );
  console.log(queues.map((t) => `  * ${t}`).join("\n"));
};
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.kotlin.sqs

import aws.sdk.kotlin.services.sqs.SqsClient
import aws.sdk.kotlin.services.sqs.paginators.listQueuesPaginated
import kotlinx.coroutines.flow.transform

suspend fun main() {
    listTopicsPag()
}

suspend fun listTopicsPag() {
```

```
    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.listQueuesPaginated { }
            .transform { it.queueUrls?.forEach { queue -> emit(queue) } }
            .collect { queue ->
                println("The Queue URL is $queue")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWSSDK for Kotlin.

Exemplos de código

- Ações para o Amazon SQS usando SDKs da AWS
  - Autorize um bucket do Amazon S3 a enviar mensagens para uma fila do Amazon SQS
  - Altere por quanto tempo uma fila do Amazon SQS espera por uma mensagem
  - Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.
  - Configure uma fila de mensagens não entregues no Amazon SQS
  - Crie uma fila do Amazon SQS usando um SDK da AWS
  - Exclua um lote de mensagens de uma fila do Amazon SQS usando um SDK da AWS
  - Exclua uma mensagem de uma fila do Amazon SQS usando um SDK da AWS
  - Exclua uma fila do Amazon SQS usando um SDK da AWS
  - Obtenha atributos para uma fila do Amazon SQS
  - Obtenha o URL de uma fila do Amazon SQS usando um SDK da AWS
  - Liste filas do Amazon SQS usando um SDK da AWS
  - Receba mensagens de uma fila do Amazon SQS usando um SDK da AWS
  - Envie um lote de mensagens para uma fila do Amazon SQS usando um SDK da AWS
  - Envie uma mensagem para uma fila do Amazon SQS usando um SDK da AWS
  - Defina atributos de fila do Amazon SQS
- Cenários para o Amazon SQS com SDKs da AWS
  - Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK
  - Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
  - Envie e receba lotes de mensagens com o Amazon SQS usando um SDK da AWS
- Exemplos sem servidor para o Amazon SQS usando SDKs da AWS

- Invocar uma função do Lambda em um trigger do Amazon SQS
- Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS
- Exemplos entre serviços do Amazon SQS usando SDKs da AWS
  - Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
  - Criar uma aplicação de mensageiro com o Step Functions
  - Criar uma aplicação de exploração do Amazon Textract
  - Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
  - Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Ações para o Amazon SQS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Queue Service (Amazon SQS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o Amazon SQS com SDKs da AWS.

Exemplos

- Autorize um bucket do Amazon S3 a enviar mensagens para uma fila do Amazon SQS
- Altere por quanto tempo uma fila do Amazon SQS espera por uma mensagem
- Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.
- Configure uma fila de mensagens não entregues no Amazon SQS
- Crie uma fila do Amazon SQS usando um SDK da AWS
- Exclua um lote de mensagens de uma fila do Amazon SQS usando um SDK da AWS
- Exclua uma mensagem de uma fila do Amazon SQS usando um SDK da AWS
- Exclua uma fila do Amazon SQS usando um SDK da AWS
- Obtenha atributos para uma fila do Amazon SQS
- Obtenha o URL de uma fila do Amazon SQS usando um SDK da AWS
- Liste filas do Amazon SQS usando um SDK da AWS
- Receba mensagens de uma fila do Amazon SQS usando um SDK da AWS
- Envie um lote de mensagens para uma fila do Amazon SQS usando um SDK da AWS
- Envie uma mensagem para uma fila do Amazon SQS usando um SDK da AWS

- Defina atributos de fila do Amazon SQS

Autorize um bucket do Amazon S3 a enviar mensagens para uma fila do Amazon SQS

O exemplo de código a seguir mostra como autorizar um bucket do Amazon S3 a enviar mensagens para uma fila do Amazon SQS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.SQS;

    public class AuthorizeS3ToSendMessage
    {
        /// <summary>
        /// Initializes the Amazon SQS client object and then calls the
        /// AuthorizeS3ToSendMessageAsync method to authorize the named
        /// bucket to send messages in response to S3 events.
        /// </summary>
        public static async Task Main()
        {
            string queueUrl = "https://sqs.us-east-2.amazonaws.com/0123456789ab/
Example_Queue";
            string bucketName = "doc-example-bucket";

            // Create an Amazon SQS client object using the
            // default user. If the AWS Region you want to use
            // is different, supply the AWS Region as a parameter.
            IAmazonSQS client = new AmazonSQSClient();

            var queueARN = await client.AuthorizeS3ToSendMessageAsync(queueUrl,
 bucketName);
```

```
            if (!string.IsNullOrEmpty(queueARN))
            {
                Console.WriteLine($"The Amazon S3 bucket: {bucketName} has been
successfully authorized.");
                Console.WriteLine($"{bucketName} can now send messages to the
queue with ARN: {queueARN}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for .NET da API.

Altere por quanto tempo uma fila do Amazon SQS espera por uma mensagem

O exemplo de código a seguir mostra como alterar por quanto tempo uma fila do Amazon SQS aguarda a chegada de uma mensagem.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
//! Set the wait time for an Amazon Simple Queue Service (Amazon SQS) queue poll.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param pollTimeSeconds: The receive message wait time in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueLongPollingAttribute(const Aws::String &queueURL,
                                               const Aws::String
 &pollTimeSeconds,
                                               const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::ReceiveMessageWaitTimeSeconds,
            pollTimeSeconds);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated long polling time for queue " <<
                  queueURL << " to " << pollTimeSeconds << std::endl;
    }
    else {
        std::cout << "Error updating long polling time for queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

Os exemplos de código a seguir mostram como alterar uma visibilidade de tempo limite de mensagem do Amazon SQS.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Changes the visibility timeout of a message in an Amazon Simple Queue Service
//! (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param visibilityTimeoutSeconds: Visibility timeout in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::changeMessageVisibility(
        const Aws::String &queue_url,
        const Aws::String &messageReceiptHandle,
        int visibilityTimeoutSeconds,
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ChangeMessageVisibilityRequest request;
    request.SetQueueUrl(queue_url);
    request.SetReceiptHandle(messageReceiptHandle);
    request.SetVisibilityTimeout(visibilityTimeoutSeconds);

    auto outcome = sqsClient.ChangeMessageVisibility(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully changed visibility of message " <<
                  messageReceiptHandle << " from queue " << queue_url <<
 std::endl;
    }
    else {
        std::cout << "Error changing visibility of message from queue "
                  << queue_url << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for C ++ da API.

CLI

AWS CLI

Como alterar a visibilidade do tempo limite de uma mensagem

Este exemplo altera a visibilidade do tempo limite da mensagem especificada para 10 horas (10 horas * 60 minutos * 60 segundos).

Comando:

```
aws sqs change-message-visibility --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --receipt-handle AQEBTpyI...t6HyQg== --
visibility-timeout 36000
```

Saída:

```
None.
```

- Para obter detalhes da API, consulte ChangeMessageVisibilityem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
import {
  ReceiveMessageCommand,
  ChangeMessageVisibilityCommand,
  SQSClient,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 1,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 1,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  const response = await client.send(
    new ChangeMessageVisibilityCommand({
      QueueUrl: queueUrl,
      ReceiptHandle: Messages[0].ReceiptHandle,
      VisibilityTimeout: 20,
    }),
  );
  console.log(response);
```

```
  return response;
};
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region to us-west-2
AWS.config.update({ region: "us-west-2" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "https://sqs.REGION.amazonaws.com/ACCOUNT-ID/QUEUE-NAME";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Receive Error", err);
  } else {
    // Make sure we have a message
    if (data.Messages != null) {
      var visibilityParams = {
        QueueUrl: queueURL,
        ReceiptHandle: data.Messages[0].ReceiptHandle,
```

```
        VisibilityTimeout: 20, // 20 second timeout
      };
      sqs.changeMessageVisibility(visibilityParams, function (err, data) {
        if (err) {
          console.log("Delete Error", err);
        } else {
          console.log("Timeout Changed", data);
        }
      });
    } else {
      console.log("No messages to change");
    }
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"  # v2: require 'aws-sdk'
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
sqs = Aws::SQS::Client.new(region: "us-west-2")

begin
  queue_name = "my-queue"
  queue_url = sqs.get_queue_url(queue_name: queue_name).queue_url

  receive_message_result_before = sqs.receive_message({
```

```
    queue_url: queue_url,
    max_number_of_messages: 10 # Receive up to 10 messages, if there are that
 many.
  })

  puts "Before attempting to change message visibility timeout: received
 #{receive_message_result_before.messages.count} message(s)."

  receive_message_result_before.messages.each do |message|
    sqs.change_message_visibility({
      queue_url: queue_url,
      receipt_handle: message.receipt_handle,
      visibility_timeout: 30 # This message will not be visible for 30 seconds
 after first receipt.
    })
  end

  # Try to retrieve the original messages after setting their visibility timeout.
  receive_message_result_after = sqs.receive_message({
    queue_url: queue_url,
    max_number_of_messages: 10
  })

  puts "\nAfter attempting to change message visibility timeout: received
 #{receive_message_result_after.messages.count} message(s)."

rescue Aws::SQS::Errors::NonExistentQueue
  puts "Cannot receive messages for a queue named '#{receive_queue_name}', as it
 does not exist."
end
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for Ruby da API.

Configure uma fila de mensagens não entregues no Amazon SQS

Os exemplos de código a seguir mostram como configurar uma fila de mensagens não entregues no Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Connect an Amazon Simple Queue Service (Amazon SQS) queue to an associated
//! dead-letter queue.
/*!
  \param srcQueueUrl: An Amazon SQS queue URL.
  \param deadLetterQueueARN: The Amazon Resource Name (ARN) of an Amazon SQS
 dead-letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setDeadLetterQueue(const Aws::String &srcQueueUrl,
                                     const Aws::String &deadLetterQueueARN,
                                     int maxReceiveCount,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::String redrivePolicy = MakeRedrivePolicy(deadLetterQueueARN,
 maxReceiveCount);

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(srcQueueUrl);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::RedrivePolicy,
            redrivePolicy);
```

```
    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
            sqsClient.SetQueueAttributes(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set dead letter queue for queue  " <<
                  srcQueueUrl << " to " << deadLetterQueueARN << std::endl;
    }
    else {
        std::cerr << "Error setting dead letter queue for queue " <<
                  srcQueueUrl << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}

//! Make a redrive policy for a dead-letter queue.
/*!
  \param queueArn: An Amazon SQS ARN for the dead-letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \return Aws::String: Policy as JSON string.
 */
Aws::String MakeRedrivePolicy(const Aws::String &queueArn, int maxReceiveCount) {
    Aws::Utils::Json::JsonValue redrive_arn_entry;
    redrive_arn_entry.AsString(queueArn);

    Aws::Utils::Json::JsonValue max_msg_entry;
    max_msg_entry.AsInteger(maxReceiveCount);

    Aws::Utils::Json::JsonValue policy_map;
    policy_map.WithObject("deadLetterTargetArn", redrive_arn_entry);
    policy_map.WithObject("maxReceiveCount", max_msg_entry);

    return policy_map.View().WriteReadable();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";
const DEAD_LETTER_QUEUE_ARN = "dead_letter_queue_arn";

export const main = async (
  queueUrl = SQS_QUEUE_URL,
  deadLetterQueueArn = DEAD_LETTER_QUEUE_ARN,
) => {
  const command = new SetQueueAttributesCommand({
    Attributes: {
      RedrivePolicy: JSON.stringify({
        // Amazon SQS supports dead-letter queues (DLQ), which other
        // queues (source queues) can target for messages that can't
        // be processed (consumed) successfully.
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-dead-letter-queues.html
        deadLetterTargetArn: deadLetterQueueArn,
        maxReceiveCount: "10",
      }),
    },
    QueueUrl: queueUrl,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for JavaScript da API.

Crie uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Publicar mensagens em filas
- Enviar e receber lotes de mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila com um nome específico.

```
    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
useFifoQueue)
    {
        int maxMessage = 256 * 1024;
        var queueAttributes = new Dictionary<string, string>
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
```

```
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
            });
        return createResponse.QueueUrl;
    }
```

Crie uma fila do Amazon SQS e envie uma mensagem para ela.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.SQS;
    using Amazon.SQS.Model;

    public class CreateSendExample
    {
        // Specify your AWS Region (an example Region is shown).
```

```
        private static readonly string QueueName = "Example_Queue";
        private static readonly RegionEndpoint ServiceRegion =
 RegionEndpoint.USWest2;
        private static IAmazonSQS client;

        public static async Task Main()
        {
            client = new AmazonSQSClient(ServiceRegion);
            var createQueueResponse = await CreateQueue(client, QueueName);

            string queueUrl = createQueueResponse.QueueUrl;

            Dictionary<string, MessageAttributeValue> messageAttributes = new
 Dictionary<string, MessageAttributeValue>
            {
                { "Title",   new MessageAttributeValue { DataType = "String",
 StringValue = "The Whistler" } },
                { "Author",  new MessageAttributeValue { DataType = "String",
 StringValue = "John Grisham" } },
                { "WeeksOn", new MessageAttributeValue { DataType = "Number",
 StringValue = "6" } },
            };

            string messageBody = "Information about current NY Times fiction
 bestseller for week of 12/11/2016.";

            var sendMsgResponse = await SendMessage(client, queueUrl,
 messageBody, messageAttributes);
        }

        /// <summary>
        /// Creates a new Amazon SQS queue using the queue name passed to it
        /// in queueName.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueName">A string representing the name of the queue
        /// to create.</param>
        /// <returns>A CreateQueueResponse that contains information about the
        /// newly created queue.</returns>
        public static async Task<CreateQueueResponse> CreateQueue(IAmazonSQS
 client, string queueName)
        {
            var request = new CreateQueueRequest
```

```
            {
                QueueName = queueName,
                Attributes = new Dictionary<string, string>
                {
                    { "DelaySeconds", "60" },
                    { "MessageRetentionPeriod", "86400" },
                },
            };

            var response = await client.CreateQueueAsync(request);
            Console.WriteLine($"Created a queue with URL : {response.QueueUrl}");

            return response;
        }

        /// <summary>
        /// Sends a message to an SQS queue.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueUrl">The URL of the queue to which to send the
        /// message.</param>
        /// <param name="messageBody">A string representing the body of the
        /// message to be sent to the queue.</param>
        /// <param name="messageAttributes">Attributes for the message to be
        /// sent to the queue.</param>
        /// <returns>A SendMessageResponse object that contains information
        /// about the message that was sent.</returns>
        public static async Task<SendMessageResponse> SendMessage(
            IAmazonSQS client,
            string queueUrl,
            string messageBody,
            Dictionary<string, MessageAttributeValue> messageAttributes)
        {
            var sendMessageRequest = new SendMessageRequest
            {
                DelaySeconds = 10,
                MessageAttributes = messageAttributes,
                MessageBody = messageBody,
                QueueUrl = queueUrl,
            };

            var response = await client.SendMessageAsync(sendMessageRequest);
            Console.WriteLine($"Sent a message with id : {response.MessageId}");
```

```
            return response;
        }
    }
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Create an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::createQueue(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::CreateQueueRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::CreateQueueOutcome outcome =
 sqsClient.CreateQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created queue " << queueName << " with a queue
 URL "
```

```
                    << outcome.GetResult().GetQueueUrl() << "." << std::endl;
    }
    else {
        std::cerr << "Error creating queue " << queueName << ": " <<
                    outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para criar uma fila

Este exemplo cria uma fila com o nome especificado, define o período de retenção da mensagem para 3 dias (3 dias * 24 horas * 60 minutos * 60 segundos) e define a fila de mensagens não entregues da fila especificada com uma contagem máxima de recebimento de 1.000 mensagens.

Comando:

```
aws sqs create-queue --queue-name MyQueue --attributes file://create-queue.json
```

Arquivo de entrada (create-queue.json):

```
{
  "RedrivePolicy": "{\"deadLetterTargetArn\":\"arn:aws:sqs:us-
east-1:80398EXAMPLE:MyDeadLetterQueue\",\"maxReceiveCount\":\"1000\"}",
  "MessageRetentionPeriod": "259200"
}
```

Saída:

```
{
  "QueueUrl": "https://queue.amazonaws.com/80398EXAMPLE/MyQueue"
}
```

- Para obter detalhes da API, consulte CreateQueueem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// CreateQueue creates an Amazon SQS queue with the specified name. You can
 specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
```

```
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.ChangeMessageVisibilityRequest;
import software.amazon.awssdk.services.sqs.model.CreateQueueRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlResponse;
import software.amazon.awssdk.services.sqs.model.ListQueuesRequest;
import software.amazon.awssdk.services.sqs.model.ListQueuesResponse;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageBatchRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageBatchRequestEntry;
import software.amazon.awssdk.services.sqs.model.SendMessageRequest;
import software.amazon.awssdk.services.sqs.model.SqsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class SQSExample {
    public static void main(String[] args) {
        String queueName = "queue" + System.currentTimeMillis();
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        // Perform various tasks on the Amazon SQS queue.
        String queueUrl = createQueue(sqsClient, queueName);
        listQueues(sqsClient);
        listQueuesFilter(sqsClient, queueUrl);
        List<Message> messages = receiveMessages(sqsClient, queueUrl);
        sendBatchMessages(sqsClient, queueUrl);
        changeMessages(sqsClient, queueUrl, messages);
        deleteMessages(sqsClient, queueUrl, messages);
        sqsClient.close();
    }

    public static String createQueue(SqsClient sqsClient, String queueName) {
        try {
            System.out.println("\nCreate Queue");

            CreateQueueRequest createQueueRequest = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .build();

            sqsClient.createQueue(createQueueRequest);

            System.out.println("\nGet queue url");

            GetQueueUrlResponse getQueueUrlResponse = sqsClient

 .getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
            return getQueueUrlResponse.queueUrl();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void listQueues(SqsClient sqsClient) {
```

```
        System.out.println("\nList Queues");
        String prefix = "que";

        try {
            ListQueuesRequest listQueuesRequest =
ListQueuesRequest.builder().queueNamePrefix(prefix).build();
            ListQueuesResponse listQueuesResponse =
sqsClient.listQueues(listQueuesRequest);
            for (String url : listQueuesResponse.queueUrls()) {
                System.out.println(url);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listQueuesFilter(SqsClient sqsClient, String queueUrl) {
        // List queues with filters
        String namePrefix = "queue";
        ListQueuesRequest filterListRequest = ListQueuesRequest.builder()
                .queueNamePrefix(namePrefix)
                .build();

        ListQueuesResponse listQueuesFilteredResponse =
sqsClient.listQueues(filterListRequest);
        System.out.println("Queue URLs with prefix: " + namePrefix);
        for (String url : listQueuesFilteredResponse.queueUrls()) {
            System.out.println(url);
        }

        System.out.println("\nSend message");
        try {
            sqsClient.sendMessage(SendMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .messageBody("Hello world!")
                    .delaySeconds(10)
                    .build());

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void sendBatchMessages(SqsClient sqsClient, String queueUrl) {

        System.out.println("\nSend multiple messages");
        try {
            SendMessageBatchRequest sendMessageBatchRequest =
SendMessageBatchRequest.builder()
                    .queueUrl(queueUrl)

.entries(SendMessageBatchRequestEntry.builder().id("id1").messageBody("Hello
from msg 1").build(),

SendMessageBatchRequestEntry.builder().id("id2").messageBody("msg
2").delaySeconds(10)
                                    .build())
                    .build();
            sqsClient.sendMessageBatch(sendMessageBatchRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static List<Message> receiveMessages(SqsClient sqsClient, String
queueUrl) {

        System.out.println("\nReceive messages");
        try {
            ReceiveMessageRequest receiveMessageRequest =
ReceiveMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .maxNumberOfMessages(5)
                    .build();
            return sqsClient.receiveMessage(receiveMessageRequest).messages();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
```

```
    public static void changeMessages(SqsClient sqsClient, String queueUrl,
 List<Message> messages) {

        System.out.println("\nChange Message Visibility");
        try {

            for (Message message : messages) {
                ChangeMessageVisibilityRequest req =
 ChangeMessageVisibilityRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .visibilityTimeout(100)
                        .build();
                sqsClient.changeMessageVisibility(req);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteMessages(SqsClient sqsClient, String queueUrl,
 List<Message> messages) {
        System.out.println("\nDelete Messages");

        try {
            for (Message message : messages) {
                DeleteMessageRequest deleteMessageRequest =
 DeleteMessageRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .build();
                sqsClient.deleteMessage(deleteMessageRequest);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "test-queue";

export const main = async (sqsQueueName = SQS_QUEUE_NAME) => {
  const command = new CreateQueueCommand({
    QueueName: sqsQueueName,
    Attributes: {
      DelaySeconds: "60",
      MessageRetentionPeriod: "86400",
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

Crie uma fila do Amazon SQS com sondagem longa.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "queue_name";
```

```
export const main = async (queueName = SQS_QUEUE_NAME) => {
  const response = await client.send(
    new CreateQueueCommand({
      QueueName: queueName,
      Attributes: {
        // When the wait time for the ReceiveMessage API action is greater than
 0,
        // long polling is in effect. The maximum long polling wait time is 20
        // seconds. Long polling helps reduce the cost of using Amazon SQS by,
        // eliminating the number of empty responses and false empty responses.
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        ReceiveMessageWaitTimeSeconds: "20",
      },
    }),
  );
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    DelaySeconds: "60",
    MessageRetentionPeriod: "86400",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

Crie uma fila do Amazon SQS que aguarda a chegada de uma mensagem.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    ReceiveMessageWaitTimeSeconds: "20",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
```

```
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createQueue(queueNameVal: String): String {

    println("Create Queue")
    val createQueueRequest = CreateQueueRequest {
        queueName = queueNameVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.createQueue(createQueueRequest)
        println("Get queue url")

        val getQueueUrlRequest = GetQueueUrlRequest {
            queueName = queueNameVal
        }

        val getQueueUrlResponse = sqsClient.getQueueUrl(getQueueUrlRequest)
        return getQueueUrlResponse.queueUrl.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateQueuereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_queue(name, attributes=None):
    """
    Creates an Amazon SQS queue.

    :param name: The name of the queue. This is part of the URL assigned to the
 queue.
    :param attributes: The attributes of the queue, such as maximum message size
 or
                       whether it's a FIFO queue.
    :return: A Queue object that contains metadata about the queue and that can
 be used
             to perform queue operations like sending and receiving messages.
    """
    if not attributes:
        attributes = {}

    try:
        queue = sqs.create_queue(QueueName=name, Attributes=attributes)
        logger.info("Created queue '%s' with URL=%s", name, queue.url)
    except ClientError as error:
        logger.exception("Couldn't create queue named '%s'.", name)
        raise error
    else:
        return queue
```

- Para obter detalhes da API, consulte a CreateQueueReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example demonstrates how to create a queue in Amazon Simple Queue
 Service (Amazon SQS).

require "aws-sdk-sqs"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_name [String] The name of the queue.
# @return [Boolean] true if the queue was created; otherwise, false.
# @example
#   exit 1 unless queue_created?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'my-queue'
#   )
def queue_created?(sqs_client, queue_name)
  sqs_client.create_queue(queue_name: queue_name)
  true
rescue StandardError => e
  puts "Error creating queue: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Creating the queue named '#{queue_name}'..."

  if queue_created?(sqs_client, queue_name)
    puts "Queue created."
```

```
  else
    puts "Queue not created."
  end
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
    TRY.
        oo_result = lo_sqs->createqueue( iv_queuename = iv_queue_name ).        "
 oo_result is returned for testing purposes. "
        MESSAGE 'SQS queue created.' TYPE 'I'.
      CATCH /aws1/cx_sqsqueuedeldrecently.
        MESSAGE 'After deleting a queue, wait 60 seconds before creating another
 queue with the same name.' TYPE 'E'.
      CATCH /aws1/cx_sqsqueuenameexists.
        MESSAGE 'A queue with this name already exists.' TYPE 'E'.
    ENDTRY.
```

Crie uma fila do Amazon SQS que aguarde uma mensagem chegar.

```
    TRY.
        DATA lt_attributes TYPE /aws1/cl_sqsqueueattrmap_w=>tt_queueattributemap.
        DATA ls_attribute TYPE /aws1/
cl_sqsqueueattrmap_w=>ts_queueattributemap_maprow.
```

```
        ls_attribute-key = 'ReceiveMessageWaitTimeSeconds'.               " Time
in seconds for long polling, such as how long the call waits for a message to
arrive in the queue before returning. "
        ls_attribute-value = NEW /aws1/cl_sqsqueueattrmap_w( iv_value =
iv_wait_time ).
        INSERT ls_attribute INTO TABLE lt_attributes.
        oo_result = lo_sqs->createqueue(                  " oo_result is returned
for testing purposes. "
                iv_queuename = iv_queue_name
                it_attributes = lt_attributes
            ).
        MESSAGE 'SQS queue created.' TYPE 'I'.
      CATCH /aws1/cx_sqsqueuedeldrecently.
        MESSAGE 'After deleting a queue, wait 60 seconds before creating another
queue with the same name.' TYPE 'E'.
      CATCH /aws1/cx_sqsqueuenameexists.
        MESSAGE 'A queue with this name already exists.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateQueuereferência da API AWS SDK for SAP ABAP.

Exclua um lote de mensagens de uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um lote de mensagens de uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Publicar mensagens em filas
- Enviar e receber lotes de mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Delete a batch of messages from a queue by its url.
   /// </summary>
   /// <param name="queueUrl">The url of the queue.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> DeleteMessageBatchByUrl(string queueUrl,
List<Message> messages)
   {
       var deleteRequest = new DeleteMessageBatchRequest()
       {
           QueueUrl = queueUrl,
           Entries = new List<DeleteMessageBatchRequestEntry>()
       };
       foreach (var message in messages)
       {
           deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
           {
               ReceiptHandle = message.ReceiptHandle,
               Id = message.MessageId
           });
       }

       var deleteResponse = await
_amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

       return deleteResponse.Failed.Any();
   }
```

- Para obter detalhes da API, consulte DeleteMessageBatch a Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::SQS::SQSClient sqsClient(clientConfiguration);

        Aws::SQS::Model::DeleteMessageBatchRequest request;
        request.SetQueueUrl(queueURLS[i]);
        int id = 1; // Ids must be unique within a batch delete request.
        for (const Aws::String &receiptHandle: receiptHandles) {
            Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
            entry.SetId(std::to_string(id));
            ++id;
            entry.SetReceiptHandle(receiptHandle);
            request.AddEntries(entry);
        }

        Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                sqsClient.DeleteMessageBatch(request);

        if (outcome.IsSuccess()) {
            std::cout << "The batch deletion of messages was successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with SQS::DeleteMessageBatch. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
```

```
                        sqsClient);

                return false;
            }
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir várias mensagens como um lote

Este exemplo exclui as mensagens especificadas.

Comando:

```
aws sqs delete-message-batch --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --entries file://delete-message-
batch.json
```

Arquivo de entrada (delete-message-batch.json):

```
[
  {
        "Id": "FirstMessage",
        "ReceiptHandle": "AQEB1mgl...Z4GuLw=="
  },
  {
    "Id": "SecondMessage",
        "ReceiptHandle": "AQEBLsYM...VQubAA=="
  }
]
```

Saída:

```
{
  "Successful": [
    {
      "Id": "FirstMessage"
```

```
    },
    {
      "Id": "SecondMessage"
    }
  ]
}
```

- Para obter detalhes da API, consulte DeleteMessageBatchem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// DeleteMessages uses the DeleteMessageBatch action to delete a batch of
 messages from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
```

```
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
```

```
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_messages(queue, messages):
    """
    Delete a batch of messages from a queue in a single request.

    :param queue: The queue from which to delete the messages.
    :param messages: The list of messages to delete.
    :return: The response from SQS that contains the list of successful and
 failed
             message deletions.
    """
    try:
        entries = [
            {"Id": str(ind), "ReceiptHandle": msg.receipt_handle}
            for ind, msg in enumerate(messages)
        ]
        response = queue.delete_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info("Deleted %s",
 messages[int(msg_meta["Id"])].receipt_handle)
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Could not delete %s",
 messages[int(msg_meta["Id"])].receipt_handle
                )
    except ClientError:
        logger.exception("Couldn't delete messages from queue %s", queue)
    else:
        return response
```

- Para obter detalhes da API, consulte a DeleteMessageBatchReferência da API AWSSDK for Python (Boto3).

Exclua uma mensagem de uma fila do Amazon SQS usando um SDK da AWS

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS e, em seguida, exclua a mensagem.

```
        public static async Task Main()
        {
            // If the AWS Region you want to use is different from
            // the AWS Region defined for the default user, supply
            // the specify your AWS Region to the client constructor.
            var client = new AmazonSQSClient();
            string queueName = "Example_Queue";

            var queueUrl = await GetQueueUrl(client, queueName);
            Console.WriteLine($"The SQS queue's URL is {queueUrl}");

            var response = await ReceiveAndDeleteMessage(client, queueUrl);

            Console.WriteLine($"Message: {response.Messages[0]}");
        }

        /// <summary>
        /// Retrieve the queue URL for the queue named in the queueName
        /// property using the client object.
        /// </summary>
        /// <param name="client">The Amazon SQS client used to retrieve the
```

```
        /// queue URL.</param>
        /// <param name="queueName">A string representing  name of the queue
        /// for which to retrieve the URL.</param>
        /// <returns>The URL of the queue.</returns>
        public static async Task<string> GetQueueUrl(IAmazonSQS client, string
 queueName)
        {
            var request = new GetQueueUrlRequest
            {
                QueueName = queueName,
            };

            GetQueueUrlResponse response = await
 client.GetQueueUrlAsync(request);
            return response.QueueUrl;
        }

        /// <summary>
        /// Retrieves the message from the quque at the URL passed in the
        /// queueURL parameters using the client.
        /// </summary>
        /// <param name="client">The SQS client used to retrieve a message.</
param>
        /// <param name="queueUrl">The URL of the queue from which to retrieve
        /// a message.</param>
        /// <returns>The response from the call to ReceiveMessageAsync.</returns>
        public static async Task<ReceiveMessageResponse>
 ReceiveAndDeleteMessage(IAmazonSQS client, string queueUrl)
        {
            // Receive a single message from the queue.
            var receiveMessageRequest = new ReceiveMessageRequest
            {
                AttributeNames = { "SentTimestamp" },
                MaxNumberOfMessages = 1,
                MessageAttributeNames = { "All" },
                QueueUrl = queueUrl,
                VisibilityTimeout = 0,
                WaitTimeSeconds = 0,
            };

            var receiveMessageResponse = await
 client.ReceiveMessageAsync(receiveMessageRequest);

            // Delete the received message from the queue.
```

```
            var deleteMessageRequest = new DeleteMessageRequest
            {
                QueueUrl = queueUrl,
                ReceiptHandle = receiveMessageResponse.Messages[0].ReceiptHandle,
            };

            await client.DeleteMessageAsync(deleteMessageRequest);

            return receiveMessageResponse;
        }
    }
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteMessage(const Aws::String &queueUrl,
                                const Aws::String &messageReceiptHandle,
```

```
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::DeleteMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetReceiptHandle(messageReceiptHandle);

    const Aws::SQS::Model::DeleteMessageOutcome outcome =
 sqsClient.DeleteMessage(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted message from queue " << queueUrl
                  << std::endl;
    }
    else {
        std::cerr << "Error deleting message from queue " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como excluir uma mensagem

Este exemplo exclui a mensagem especificada.

Comando:

```
aws sqs delete-message --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --receipt-handle AQEBRXTo...q2doVA==
```

Saída:

```
None.
```

- Para obter detalhes da API, consulte DeleteMessageem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        try {
            for (Message message : messages) {
                DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .build();
                sqsClient.deleteMessage(deleteMessageRequest);
            }
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
```

```
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 10,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  VisibilityTimeout: 20,
  WaitTimeSeconds: 0,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
```

```
    console.log("Receive Error", err);
  } else if (data.Messages) {
    var deleteParams = {
      QueueUrl: queueURL,
      ReceiptHandle: data.Messages[0].ReceiptHandle,
    };
    sqs.deleteMessage(deleteParams, function (err, data) {
      if (err) {
        console.log("Delete Error", err);
      } else {
        console.log("Message Deleted", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMessages(queueUrlVal: String) {
    println("Delete Messages from $queueUrlVal")

    val purgeRequest = PurgeQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.purgeQueue(purgeRequest)
```

```
        println("Messages are successfully deleted from $queueUrlVal")
    }
}

suspend fun deleteQueue(queueUrlVal: String) {

    val request = DeleteQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.deleteQueue(request)
        println("$queueUrlVal was deleted!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteMessagereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_message(message):
    """
    Delete a message from a queue. Clients must delete messages after they
    are received and processed to remove them from the queue.

    :param message: The message to delete. The message's queue URL is contained
 in
                    the message's metadata.
    :return: None
    """
    try:
```

```
        message.delete()
        logger.info("Deleted message: %s", message.message_id)
    except ClientError as error:
        logger.exception("Couldn't delete message: %s", message.message_id)
        raise error
```

- Para obter detalhes da API, consulte a DeleteMessageReferência da API AWSSDK for Python (Boto3).

Exclua uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Publicar mensagens em filas
- Enviar e receber lotes de mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila usando seu URL.

```
    /// <summary>
    /// Delete a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteQueueByUrl(string queueUrl)
```

```
    {
        var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
            new DeleteQueueRequest()
            {
                QueueUrl = queueUrl
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteQueue a Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueURL: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteQueue(const Aws::String &queueURL,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::SQS::Model::DeleteQueueRequest request;
    request.SetQueueUrl(queueURL);

    const Aws::SQS::Model::DeleteQueueOutcome outcome =
 sqsClient.DeleteQueue(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully deleted queue with url " << queueURL <<
                  std::endl;
    }
    else {
        std::cerr << "Error deleting queue " << queueURL << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para excluir uma fila

Este exemplo exclui a fila especificada.

Comando:

```
aws sqs delete-queue --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyNewerQueue
```

Saída:

```
None.
```

- Para obter detalhes da API, consulte DeleteQueueem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.DeleteQueueRequest;
import software.amazon.awssdk.services.sqs.model.SqsException;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DeleteQueue {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <queueName>

                Where:
                   queueName - The name of the Amazon SQS queue to delete.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String queueName = args[0];
        SqsClient sqs = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        deleteSQSQueue(sqs, queueName);
        sqs.close();
    }

    public static void deleteSQSQueue(SqsClient sqsClient, String queueName) {
        try {
            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            DeleteQueueRequest deleteQueueRequest = DeleteQueueRequest.builder()
                    .queueUrl(queueUrl)
                    .build();

            sqsClient.deleteQueue(deleteQueueRequest);
```

```
        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
import { DeleteQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "test-queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new DeleteQueueCommand({ QueueUrl: queueUrl });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueUrl: "SQS_QUEUE_URL",
};

sqs.deleteQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMessages(queueUrlVal: String) {
    println("Delete Messages from $queueUrlVal")

    val purgeRequest = PurgeQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.purgeQueue(purgeRequest)
        println("Messages are successfully deleted from $queueUrlVal")
    }
}

suspend fun deleteQueue(queueUrlVal: String) {

    val request = DeleteQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.deleteQueue(request)
        println("$queueUrlVal was deleted!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteQueuereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def remove_queue(queue):
    """
    Removes an SQS queue. When run against an AWS account, it can take up to
    60 seconds before the queue is actually deleted.

    :param queue: The queue to delete.
    :return: None
    """
    try:
        queue.delete()
        logger.info("Deleted queue with URL=%s.", queue.url)
    except ClientError as error:
        logger.exception("Couldn't delete queue with URL=%s!", queue.url)
        raise error
```

- Para obter detalhes da API, consulte a DeleteQueueReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"  # v2: require 'aws-sdk'
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
sqs = Aws::SQS::Client.new(region: "us-west-2")

sqs.delete_queue(queue_url: URL)
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Ruby da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sqs->deletequeue( iv_queueurl = iv_queue_url ).
        MESSAGE 'SQS queue deleted' TYPE 'I'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteQueuereferência da API AWS SDK for SAP ABAP.

Obtenha atributos para uma fila do Amazon SQS

Os exemplos de código a seguir mostram como obter atributos para uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the ARN for a queue from its URL.
    /// </summary>
    /// <param name="queueUrl">The URL of the queue.</param>
    /// <returns>The ARN of the queue.</returns>
    public async Task<string> GetQueueArnByUrl(string queueUrl)
    {
        var getAttributesRequest = new GetQueueAttributesRequest()
        {
            QueueUrl = queueUrl,
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await
_amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }

            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
```

```
            }
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter os atributos de uma fila

Este exemplo obtém todos os atributos da fila especificada.

Comando:

```
aws sqs get-queue-attributes --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --attribute-names All
```

Saída:

```
{
  "Attributes": {
    "ApproximateNumberOfMessagesNotVisible": "0",
    "RedrivePolicy": "{\"deadLetterTargetArn\":\"arn:aws:sqs:us-
east-1:80398EXAMPLE:MyDeadLetterQueue\",\"maxReceiveCount\":1000}",
    "MessageRetentionPeriod": "345600",
    "ApproximateNumberOfMessagesDelayed": "0",
    "MaximumMessageSize": "262144",
    "CreatedTimestamp": "1442426968",
    "ApproximateNumberOfMessages": "0",
    "ReceiveMessageWaitTimeSeconds": "0",
    "DelaySeconds": "0",
    "VisibilityTimeout": "30",
    "LastModifiedTimestamp": "1442426968",
    "QueueArn": "arn:aws:sqs:us-east-1:80398EXAMPLE:MyNewQueue"
  }
}
```

Este exemplo obtém somente os atributos especificados de tempo limite de visibilidade e de tamanho máximo da mensagem da fila.

Comando:

```
aws sqs get-queue-attributes --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyNewQueue --attribute-names MaximumMessageSize
 VisibilityTimeout
```

Saída:

```
{
  "Attributes": {
    "VisibilityTimeout": "30",
    "MaximumMessageSize": "262144"
  }
}
```

- Para obter detalhes da API, consulte GetQueueAttributesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}
```

```
// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
// of an Amazon SQS queue.
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { GetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const getQueueAttributes = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new GetQueueAttributesCommand({
```

```
    QueueUrl: queueUrl,
    AttributeNames: ["DelaySeconds"],
  });

  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '747a1192-c334-5682-a508-4cd5e8dc4e79',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Attributes: { DelaySeconds: '1' }
  // }
  return response;
};
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for JavaScript da API.

Obtenha o URL de uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como obter o URL de uma fila do Amazon SQS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.SQS;
```

```
    using Amazon.SQS.Model;

    public class GetQueueUrl
    {
        /// <summary>
        /// Initializes the Amazon SQS client object and then calls the
        /// GetQueueUrlAsync method to retrieve the URL of an Amazon SQS
        /// queue.
        /// </summary>
        public static async Task Main()
        {
            // If the Amazon SQS message queue is not in the same AWS Region as
your
            // default user, you need to provide the AWS Region as a parameter to
the
            // client constructor.
            var client = new AmazonSQSClient();

            string queueName = "New-Example-Queue";

            try
            {
                var response = await client.GetQueueUrlAsync(queueName);

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    Console.WriteLine($"The URL for {queueName} is:
{response.QueueUrl}");
                }
            }
            catch (QueueDoesNotExistException ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine($"The queue {queueName} was not found.");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Get the URL for an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::getQueueUrl(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::GetQueueUrlRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::GetQueueUrlOutcome outcome =
 sqsClient.GetQueueUrl(request);
    if (outcome.IsSuccess()) {
        std::cout << "Queue " << queueName << " has url " <<
                  outcome.GetResult().GetQueueUrl() << std::endl;
    }
    else {
        std::cerr << "Error getting url for queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como obter um URL de fila

Este exemplo obtém o URL da fila especificada.

Comando:

```
aws sqs get-queue-url --queue-name MyQueue
```

Saída:

```
{
  "QueueUrl": "https://queue.amazonaws.com/80398EXAMPLE/MyQueue"
}
```

- Para obter detalhes da API, consulte GetQueueUrlem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            GetQueueUrlResponse getQueueUrlResponse = sqsClient

.getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
            return getQueueUrlResponse.queueUrl();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        return "";
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
import { GetQueueUrlCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "test-queue";

export const main = async (queueName = SQS_QUEUE_NAME) => {
  const command = new GetQueueUrlCommand({ QueueName: queueName });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
};

sqs.getQueueUrl(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_queue(name):
    """
    Gets an SQS queue by name.

    :param name: The name that was used to create the queue.
    :return: A Queue object.
    """
    try:
        queue = sqs.get_queue_by_name(QueueName=name)
        logger.info("Got queue '%s' with URL=%s", name, queue.url)
    except ClientError as error:
        logger.exception("Couldn't get queue named %s.", name)
        raise error
    else:
        return queue
```

- Para obter detalhes da API, consulte a GetQueueUrlReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sqs->getqueueurl( iv_queuename = iv_queue_name ).        "
 oo_result is returned for testing purposes. "
        MESSAGE 'Queue URL retrieved.' TYPE 'I'.
      CATCH /aws1/cx_sqsqueuedoesnotexist.
        MESSAGE 'The requested queue does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetQueueUrlreferência da API AWS SDK for SAP ABAP.

Liste filas do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! List the Amazon Simple Queue Service (Amazon SQS) queues within an AWS
 account.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SQS::listQueues(const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
    Aws::SQS::Model::ListQueuesRequest lq_req;

    const Aws::SQS::Model::ListQueuesOutcome outcome =
 sqsClient.ListQueues(lq_req);
    if (outcome.IsSuccess()) {
        std::cout << "Queue Urls:" << std::endl << std::endl;
        const auto &queue_urls = outcome.GetResult().GetQueueUrls();
        for (const auto &iter: queue_urls) {
            std::cout << " " << iter << std::endl;
        }
    }
    else {
        std::cerr << "Error listing queues: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como listar filas

Este exemplo lista todas as filas.

Comando:

```
aws sqs list-queues
```

Saída:

```
{
  "QueueUrls": [
    "https://queue.amazonaws.com/80398EXAMPLE/MyDeadLetterQueue",
    "https://queue.amazonaws.com/80398EXAMPLE/MyQueue",
    "https://queue.amazonaws.com/80398EXAMPLE/MyOtherQueue",
    "https://queue.amazonaws.com/80398EXAMPLE/TestQueue1",
```

```
        "https://queue.amazonaws.com/80398EXAMPLE/TestQueue2"
  ]
}
```

Este exemplo lista somente as filas que começam com “My”.

Comando:

```
aws sqs list-queues --queue-name-prefix My
```

Saída:

```
{
  "QueueUrls": [
    "https://queue.amazonaws.com/80398EXAMPLE/MyDeadLetterQueue",
    "https://queue.amazonaws.com/80398EXAMPLE/MyQueue",
    "https://queue.amazonaws.com/80398EXAMPLE/MyOtherQueue"
  ]
}
```

- Para obter detalhes da API, consulte ListQueuesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"
```

```
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sqs"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Queue Service
// (Amazon SQS) client and list the queues in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 sqsClient := sqs.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the queues for your account.")
 var queueUrls []string
 paginator := sqs.NewListQueuesPaginator(sqsClient, &sqs.ListQueuesInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get queues. Here's why: %v\n", err)
   break
  } else {
   queueUrls = append(queueUrls, output.QueueUrls...)
  }
 }
 if len(queueUrls) == 0 {
  fmt.Println("You don't have any queues!")
 } else {
  for _, queueUrl := range queueUrls {
   fmt.Printf("\t%v\n", queueUrl)
  }
 }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        String prefix = "que";

        try {
            ListQueuesRequest listQueuesRequest =
ListQueuesRequest.builder().queueNamePrefix(prefix).build();
            ListQueuesResponse listQueuesResponse =
sqsClient.listQueues(listQueuesRequest);
            for (String url : listQueuesResponse.queueUrls()) {
                System.out.println(url);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
import { paginateListQueues, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});

export const main = async () => {
  const paginatedListQueues = paginateListQueues({ client }, {});

  /** @type {string[]} */
  const urls = [];
  for await (const page of paginatedListQueues) {
    const nextUrls = page.QueueUrls?.filter((qurl) => !!qurl) || [];
    urls.push(...nextUrls);
    urls.forEach((url) => console.log(url));
  }

  return urls;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
```

```
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {};

sqs.listQueues(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrls);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listQueues() {
    println("\nList Queues")

    val prefix = "que"
    val listQueuesRequest = ListQueuesRequest {
        queueNamePrefix = prefix
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        val response = sqsClient.listQueues(listQueuesRequest)
        response.queueUrls?.forEach { url ->
            println(url)
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_queues(prefix=None):
    """
    Gets a list of SQS queues. When a prefix is specified, only queues with names
    that start with the prefix are returned.

    :param prefix: The prefix used to restrict the list of returned queues.
    :return: A list of Queue objects.
    """
    if prefix:
        queue_iter = sqs.queues.filter(QueueNamePrefix=prefix)
    else:
        queue_iter = sqs.queues.all()
    queues = list(queue_iter)
    if queues:
        logger.info("Got queues: %s", ", ".join([q.url for q in queues]))
    else:
        logger.warning("No queues found.")
    return queues
```

- Para obter detalhes da API, consulte a ListQueuesReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @example
#   list_queue_urls(Aws::SQS::Client.new(region: 'us-west-2'))
def list_queue_urls(sqs_client)
  queues = sqs_client.list_queues

  queues.queue_urls.each do |url|
    puts url
  end
rescue StandardError => e
  puts "Error listing queue URLs: #{e.message}"
end

# Lists the attributes of a queue in Amazon Simple Queue Service (Amazon SQS).
#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @example
#   list_queue_attributes(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
#   )
def list_queue_attributes(sqs_client, queue_url)
  attributes = sqs_client.get_queue_attributes(
    queue_url: queue_url,
    attribute_names: ["All"]
  )
```

```
  attributes.attributes.each do |key, value|
    puts "#{key}: #{value}"
  end

rescue StandardError => e
  puts "Error getting queue attributes: #{e.message}"
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Listing available queue URLs..."
  list_queue_urls(sqs_client)

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  puts "\nGetting information about queue '#{queue_name}'..."
  list_queue_attributes(sqs_client, queue_url)
end
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Recuperar a primeira fila do Amazon SQS listada na região.

```
async fn find_first_queue(client: &Client) -> Result<String, Error> {
    let queues = client.list_queues().send().await?;
    let queue_urls = queues.queue_urls();
    Ok(queue_urls
        .first()
        .expect("No queues in this account and Region. Create a queue to
 proceed.")
        .to_string())
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sqs->listqueues( ).        " oo_result is returned for
 testing purposes. "
        MESSAGE 'Retrieved list of queues.' TYPE 'I'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWS SDK for SAP ABAP.

Receba mensagens de uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como receber mensagens de uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Publicar mensagens em filas
- Enviar e receber lotes de mensagens

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba mensagens de uma fila usando seu URL.

```
    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
        return messageResponse.Messages;
    }
```

Receba uma mensagem de uma fila do Amazon SQS e, em seguida, exclua a mensagem.

```
        public static async Task Main()
        {
            // If the AWS Region you want to use is different from
            // the AWS Region defined for the default user, supply
            // the specify your AWS Region to the client constructor.
            var client = new AmazonSQSClient();
            string queueName = "Example_Queue";

            var queueUrl = await GetQueueUrl(client, queueName);
            Console.WriteLine($"The SQS queue's URL is {queueUrl}");

            var response = await ReceiveAndDeleteMessage(client, queueUrl);

            Console.WriteLine($"Message: {response.Messages[0]}");
        }

        /// <summary>
        /// Retrieve the queue URL for the queue named in the queueName
        /// property using the client object.
        /// </summary>
        /// <param name="client">The Amazon SQS client used to retrieve the
        /// queue URL.</param>
        /// <param name="queueName">A string representing  name of the queue
        /// for which to retrieve the URL.</param>
        /// <returns>The URL of the queue.</returns>
        public static async Task<string> GetQueueUrl(IAmazonSQS client, string
queueName)
        {
            var request = new GetQueueUrlRequest
            {
                QueueName = queueName,
            };

            GetQueueUrlResponse response = await
client.GetQueueUrlAsync(request);
            return response.QueueUrl;
        }

        /// <summary>
        /// Retrieves the message from the quque at the URL passed in the
        /// queueURL parameters using the client.
        /// </summary>
```

```
        /// <param name="client">The SQS client used to retrieve a message.</
param>
        /// <param name="queueUrl">The URL of the queue from which to retrieve
        /// a message.</param>
        /// <returns>The response from the call to ReceiveMessageAsync.</returns>
        public static async Task<ReceiveMessageResponse>
 ReceiveAndDeleteMessage(IAmazonSQS client, string queueUrl)
        {
            // Receive a single message from the queue.
            var receiveMessageRequest = new ReceiveMessageRequest
            {
                AttributeNames = { "SentTimestamp" },
                MaxNumberOfMessages = 1,
                MessageAttributeNames = { "All" },
                QueueUrl = queueUrl,
                VisibilityTimeout = 0,
                WaitTimeSeconds = 0,
            };

            var receiveMessageResponse = await
 client.ReceiveMessageAsync(receiveMessageRequest);

            // Delete the received message from the queue.
            var deleteMessageRequest = new DeleteMessageRequest
            {
                QueueUrl = queueUrl,
                ReceiptHandle = receiveMessageResponse.Messages[0].ReceiptHandle,
            };

            await client.DeleteMessageAsync(deleteMessageRequest);

            return receiveMessageResponse;
        }
    }
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Receive a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::receiveMessage(const Aws::String &queueUrl,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ReceiveMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMaxNumberOfMessages(1);

    const Aws::SQS::Model::ReceiveMessageOutcome outcome =
 sqsClient.ReceiveMessage(
            request);
    if (outcome.IsSuccess()) {

        const Aws::Vector<Aws::SQS::Model::Message> &messages =
                outcome.GetResult().GetMessages();
        if (!messages.empty()) {
            const Aws::SQS::Model::Message &message = messages[0];
            std::cout << "Received message:" << std::endl;
            std::cout << "  MessageId: " << message.GetMessageId() << std::endl;
            std::cout << "  ReceiptHandle: " << message.GetReceiptHandle() <<
 std::endl;
```

```
            std::cout << "  Body: " << message.GetBody() << std::endl <<
 std::endl;
        }
        else {
            std::cout << "No messages received from queue " << queueUrl <<
                      std::endl;

        }
    }
    else {
        std::cerr << "Error receiving message from queue " << queueUrl << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como receber uma mensagem

Este exemplo recebe até 10 mensagens disponíveis e retorna todos os atributos disponíveis.

Comando:

```
aws sqs receive-message --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --attribute-names All --message-
attribute-names All --max-number-of-messages 10
```

Saída:

```
{
  "Messages": [
    {
      "Body": "My first message.",
      "ReceiptHandle": "AQEBzbVv...fqNzFw==",
```

```
      "MD5OfBody": "1000f835...a35411fa",
      "MD5OfMessageAttributes": "9424c491...26bc3ae7",
      "MessageId": "d6790f8d-d575-4f01-bc51-40122EXAMPLE",
      "Attributes": {
        "ApproximateFirstReceiveTimestamp": "1442428276921",
        "SenderId": "AIDAIAZKMSNQ7TEXAMPLE",
        "ApproximateReceiveCount": "5",
        "SentTimestamp": "1442428276921"
      },
      "MessageAttributes": {
        "PostalCode": {
          "DataType": "String",
          "StringValue": "ABC123"
        },
        "City": {
          "DataType": "String",
          "StringValue": "Any City"
        }
      }
    }
  ]
}
```

Este exemplo recebe a próxima mensagem disponível, retornando somente os SentTimestamp atributos SenderId e, bem como o atributo da PostalCode mensagem.

Comando:

```
aws sqs receive-message --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --attribute-names SenderId
 SentTimestamp --message-attribute-names PostalCode
```

Saída:

```
{
  "Messages": [
    {
      "Body": "My first message.",
      "ReceiptHandle": "AQEB6nR4...HzlvZQ==",
      "MD5OfBody": "1000f835...a35411fa",
      "MD5OfMessageAttributes": "b8e89563...e088e74f",
      "MessageId": "d6790f8d-d575-4f01-bc51-40122EXAMPLE",
```

```
      "Attributes": {
        "SenderId": "AIDAIAZKMSNQ7TEXAMPLE",
        "SentTimestamp": "1442428276921"
      },
      "MessageAttributes": {
        "PostalCode": {
          "DataType": "String",
          "StringValue": "ABC123"
        }
      }
    }
  ]
}
```

- Para obter detalhes da API, consulte ReceiveMessageem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
```

```
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
 if err != nil {
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 } else {
  messages = result.Messages
 }
 return messages, err
}
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Go da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            ReceiveMessageRequest receiveMessageRequest =
ReceiveMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .maxNumberOfMessages(5)
                    .build();
            return sqsClient.receiveMessage(receiveMessageRequest).messages();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
        return null;
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);
```

```
  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
import { ReceiveMessageCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new ReceiveMessageCommand({
    AttributeNames: ["SentTimestamp"],
    MaxNumberOfMessages: 1,
    MessageAttributeNames: ["All"],
    QueueUrl: queueUrl,
    // The duration (in seconds) for which the call waits for a message
    // to arrive in the queue before returning. If a message is available,
    // the call returns sooner than WaitTimeSeconds. If no messages are
```

```
    // available and the wait time expires, the call returns successfully
    // with an empty list of messages.
    // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/APIReference/
API_ReceiveMessage.html#API_ReceiveMessage_RequestSyntax
    WaitTimeSeconds: 20,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  WaitTimeSeconds: 20,
};
```

```
sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun receiveMessages(queueUrlVal: String?) {

    println("Retrieving messages from $queueUrlVal")

    val receiveMessageRequest = ReceiveMessageRequest {
        queueUrl = queueUrlVal
        maxNumberOfMessages = 5
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        val response = sqsClient.receiveMessage(receiveMessageRequest)
        response.messages?.forEach { message ->
            println(message.body)
        }
    }
}
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def receive_messages(queue, max_number, wait_time):
    """
    Receive a batch of messages in a single request from an SQS queue.

    :param queue: The queue from which to receive messages.
    :param max_number: The maximum number of messages to receive. The actual
 number
                        of messages received might be less.
    :param wait_time: The maximum time to wait (in seconds) before returning.
 When
                       this number is greater than zero, long polling is used.
 This
                       can result in reduced costs and fewer false empty
 responses.
    :return: The list of Message objects received. These each contain the body
             of the message and metadata and custom attributes.
    """
    try:
        messages = queue.receive_messages(
            MessageAttributeNames=["All"],
            MaxNumberOfMessages=max_number,
            WaitTimeSeconds=wait_time,
        )
        for msg in messages:
            logger.info("Received message: %s: %s", msg.message_id, msg.body)
    except ClientError as error:
```

```
        logger.exception("Couldn't receive messages from queue: %s", queue)
        raise error
    else:
        return messages
```

- Para obter detalhes da API, consulte a ReceiveMessageReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# Receives messages in a queue in Amazon Simple Queue Service (Amazon SQS).
#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @param max_number_of_messages [Integer] The maximum number of messages
#   to receive. This number must be 10 or less. The default is 10.
# @example
#   receive_messages(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     10
#   )
def receive_messages(sqs_client, queue_url, max_number_of_messages = 10)

  if max_number_of_messages > 10
    puts "Maximum number of messages to receive must be 10 or less. " \
```

```
      "Stopping program."
    return
  end

  response = sqs_client.receive_message(
    queue_url: queue_url,
    max_number_of_messages: max_number_of_messages
  )

  if response.messages.count.zero?
    puts "No messages to receive, or all messages have already " \
      "been previously received."
    return
  end

  response.messages.each do |message|
    puts "-" * 20
    puts "Message body: #{message.body}"
    puts "Message ID:   #{message.message_id}"
  end

rescue StandardError => e
  puts "Error receiving messages: #{e.message}"
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  max_number_of_messages = 10

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Receiving messages from queue '#{queue_name}'..."

  receive_messages(sqs_client, queue_url, max_number_of_messages)
```

```
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn receive(client: &Client, queue_url: &String) -> Result<(), Error> {
    let rcv_message_output =
 client.receive_message().queue_url(queue_url).send().await?;

    println!("Messages from queue with url: {}", queue_url);

    for message in rcv_message_output.messages.unwrap_or_default() {
        println!("Got the message: {:#?}", message);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS.

```
   TRY.
       oo_result = lo_sqs->receivemessage( iv_queueurl = iv_queue_url ).    "
oo_result is returned for testing purposes. "
       DATA(lt_messages) = oo_result->get_messages( ).
       MESSAGE 'Message received from SQS queue.' TYPE 'I'.
     CATCH /aws1/cx_sqsoverlimit.
       MESSAGE 'Maximum number of in-flight messages reached.' TYPE 'E'.
   ENDTRY.
```

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
   TRY.
       oo_result = lo_sqs->receivemessage(           " oo_result is returned for
testing purposes. "
               iv_queueurl = iv_queue_url
               iv_waittimeseconds = iv_wait_time     " Time in seconds for long
polling, such as how long the call waits for a message to arrive in the queue
before returning. "
           ).
       DATA(lt_messages) = oo_result->get_messages( ).
       MESSAGE 'Message received from SQS queue.' TYPE 'I'.
     CATCH /aws1/cx_sqsoverlimit.
       MESSAGE 'Maximum number of in-flight messages reached.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWS SDK for SAP ABAP.

Envie um lote de mensagens para uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como enviar um lote de mensagens para uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Enviar e receber lotes de mensagens

CLI

AWS CLI

Como enviar várias mensagens como um lote

Este exemplo envia duas mensagens com os corpos da mensagem, os períodos de atraso e os atributos de mensagem especificados para a fila especificada.

Comando:

```
aws sqs send-message-batch --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --entries file://send-message-
batch.json
```

Arquivo de entrada (send-message-batch.json):

```
[
  {
    "Id": "FuelReport-0001-2015-09-16T140731Z",
        "MessageBody": "Fuel report for account 0001 on 2015-09-16 at 02:07:31
 PM.",
        "DelaySeconds": 10,
        "MessageAttributes": {
          "SellerName": {
            "DataType": "String",
                "StringValue": "Example Store"
      },
          "City": {
        "DataType": "String",
        "StringValue": "Any City"
      },
```

```
          "Region": {
            "DataType": "String",
                "StringValue": "WA"
      },
          "PostalCode": {
            "DataType": "String",
                "StringValue": "99065"
          },
          "PricePerGallon": {
            "DataType": "Number",
                "StringValue": "1.99"
      }
        }
  },
  {
    "Id": "FuelReport-0002-2015-09-16T140930Z",
        "MessageBody": "Fuel report for account 0002 on 2015-09-16 at 02:09:30
 PM.",
        "DelaySeconds": 10,
        "MessageAttributes": {
          "SellerName": {
            "DataType": "String",
                "StringValue": "Example Fuels"
      },
          "City": {
        "DataType": "String",
        "StringValue": "North Town"
      },
          "Region": {
            "DataType": "String",
                "StringValue": "WA"
      },
          "PostalCode": {
            "DataType": "String",
                "StringValue": "99123"
          },
          "PricePerGallon": {
            "DataType": "Number",
                "StringValue": "1.87"
      }
        }
  }
]
```

Saída:

```
{
  "Successful": [
    {
      "MD5OfMessageBody": "203c4a38...7943237e",
      "MD5OfMessageAttributes": "10809b55...baf283ef",
      "Id": "FuelReport-0001-2015-09-16T140731Z",
      "MessageId": "d175070c-d6b8-4101-861d-adeb3EXAMPLE"
    },
    {
      "MD5OfMessageBody": "2cf0159a...c1980595",
      "MD5OfMessageAttributes": "55623928...ae354a25",
      "Id": "FuelReport-0002-2015-09-16T140930Z",
      "MessageId": "f9b7d55d-0570-413e-b9c5-a9264EXAMPLE"
    }
  ]
}
```

- Para obter detalhes da API, consulte SendMessageBatchem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            SendMessageBatchRequest sendMessageBatchRequest =
SendMessageBatchRequest.builder()
                    .queueUrl(queueUrl)

.entries(SendMessageBatchRequestEntry.builder().id("id1").messageBody("Hello
from msg 1").build(),

SendMessageBatchRequestEntry.builder().id("id2").messageBody("msg
2").delaySeconds(10)
```

```
                                        .build())
                        .build();
            sqsClient.sendMessageBatch(sendMessageBatchRequest);
```

- Para obter detalhes da API, consulte SendMessageBatcha Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def send_messages(queue, messages):
    """
    Send a batch of messages in a single request to an SQS queue.
    This request may return overall success even when some messages were not
 sent.
    The caller must inspect the Successful and Failed lists in the response and
    resend any failed messages.

    :param queue: The queue to receive the messages.
    :param messages: The messages to send to the queue. These are simplified to
                     contain only the message body and attributes.
    :return: The response from SQS that contains the list of successful and
 failed
             messages.
    """
    try:
        entries = [
            {
                "Id": str(ind),
                "MessageBody": msg["body"],
                "MessageAttributes": msg["attributes"],
            }
            for ind, msg in enumerate(messages)
```

```
        ]
        response = queue.send_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info(
                    "Message sent: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Failed to send: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
    except ClientError as error:
        logger.exception("Send messages failed to queue: %s", queue)
        raise error
    else:
        return response
```

- Para obter detalhes da API, consulte a SendMessageBatchReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"
```

```
#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @param entries [Hash] The contents of the messages to be sent,
#   in the correct format.
# @return [Boolean] true if the messages were sent; otherwise, false.
# @example
#   exit 1 unless messages_sent?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     [
#       {
#         id: 'Message1',
#         message_body: 'This is the first message.'
#       },
#       {
#         id: 'Message2',
#         message_body: 'This is the second message.'
#       }
#     ]
#   )
def messages_sent?(sqs_client, queue_url, entries)
  sqs_client.send_message_batch(
    queue_url: queue_url,
    entries: entries
  )
  true
rescue StandardError => e
  puts "Error sending messages: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  entries = [
    {
      id: "Message1",
      message_body: "This is the first message."
    },
    {
```

```
      id: "Message2",
      message_body: "This is the second message."
    }
  ]

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Sending messages to the queue named '#{queue_name}'..."

  if messages_sent?(sqs_client, queue_url, entries)
    puts "Messages sent."
  else
    puts "Messages not sent."
  end
end
```

- Para obter detalhes da API, consulte SendMessageBatcha Referência AWS SDK for Ruby da API.

Envie uma mensagem para uma fila do Amazon SQS usando um SDK da AWS

Os exemplos de código a seguir mostram como enviar uma mensagem para uma fila do Amazon SQS.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila do Amazon SQS e envie uma mensagem para ela.

```
   using System;
   using System.Collections.Generic;
   using System.Threading.Tasks;
   using Amazon;
   using Amazon.SQS;
   using Amazon.SQS.Model;

   public class CreateSendExample
   {
       // Specify your AWS Region (an example Region is shown).
       private static readonly string QueueName = "Example_Queue";
       private static readonly RegionEndpoint ServiceRegion =
RegionEndpoint.USWest2;
       private static IAmazonSQS client;

       public static async Task Main()
       {
           client = new AmazonSQSClient(ServiceRegion);
           var createQueueResponse = await CreateQueue(client, QueueName);

           string queueUrl = createQueueResponse.QueueUrl;

           Dictionary<string, MessageAttributeValue> messageAttributes = new
Dictionary<string, MessageAttributeValue>
           {
               { "Title",   new MessageAttributeValue { DataType = "String",
StringValue = "The Whistler" } },
               { "Author",  new MessageAttributeValue { DataType = "String",
StringValue = "John Grisham" } },
               { "WeeksOn", new MessageAttributeValue { DataType = "Number",
StringValue = "6" } },
           };

           string messageBody = "Information about current NY Times fiction
bestseller for week of 12/11/2016.";

           var sendMsgResponse = await SendMessage(client, queueUrl,
messageBody, messageAttributes);
       }

       /// <summary>
       /// Creates a new Amazon SQS queue using the queue name passed to it
```

```
        /// in queueName.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueName">A string representing the name of the queue
        /// to create.</param>
        /// <returns>A CreateQueueResponse that contains information about the
        /// newly created queue.</returns>
        public static async Task<CreateQueueResponse> CreateQueue(IAmazonSQS
 client, string queueName)
        {
            var request = new CreateQueueRequest
            {
                QueueName = queueName,
                Attributes = new Dictionary<string, string>
                {
                    { "DelaySeconds", "60" },
                    { "MessageRetentionPeriod", "86400" },
                },
            };

            var response = await client.CreateQueueAsync(request);
            Console.WriteLine($"Created a queue with URL : {response.QueueUrl}");

            return response;
        }

        /// <summary>
        /// Sends a message to an SQS queue.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueUrl">The URL of the queue to which to send the
        /// message.</param>
        /// <param name="messageBody">A string representing the body of the
        /// message to be sent to the queue.</param>
        /// <param name="messageAttributes">Attributes for the message to be
        /// sent to the queue.</param>
        /// <returns>A SendMessageResponse object that contains information
        /// about the message that was sent.</returns>
        public static async Task<SendMessageResponse> SendMessage(
            IAmazonSQS client,
            string queueUrl,
            string messageBody,
```

```
            Dictionary<string, MessageAttributeValue> messageAttributes)
        {
            var sendMessageRequest = new SendMessageRequest
            {
                DelaySeconds = 10,
                MessageAttributes = messageAttributes,
                MessageBody = messageBody,
                QueueUrl = queueUrl,
            };

            var response = await client.SendMessageAsync(sendMessageRequest);
            Console.WriteLine($"Sent a message with id : {response.MessageId}");

            return response;
        }
    }
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Send a message to an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageBody: A message body.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::sendMessage(const Aws::String &queueUrl,
                              const Aws::String &messageBody,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SendMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMessageBody(messageBody);

    const Aws::SQS::Model::SendMessageOutcome outcome =
 sqsClient.SendMessage(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message to " << queueUrl <<
                  std::endl;
    }
    else {
        std::cerr << "Error sending message to " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Para enviar uma mensagem

Este exemplo envia uma mensagem com o corpo da mensagem, o período de atraso e os atributos da mensagem especificados para a fila especificada.

Comando:

```
aws sqs send-message --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyQueue --message-body "Information about the
```

```
 largest city in Any Region." --delay-seconds 10 --message-attributes file://
send-message.json
```

Arquivo de entrada (send-message.json):

```
{
  "City": {
    "DataType": "String",
    "StringValue": "Any City"
  },
  "Greeting": {
    "DataType": "Binary",
    "BinaryValue": "Hello, World!"
  },
  "Population": {
    "DataType": "Number",
    "StringValue": "1250800"
  }
}
```

Saída:

```
{
  "MD5OfMessageBody": "51b0a325...39163aa0",
  "MD5OfMessageAttributes": "00484c68...59e48f06",
  "MessageId": "da68f62c-0c07-4bee-bf5f-7e856EXAMPLE"
}
```

- Para obter detalhes da API, consulte SendMessageem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
```

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.CreateQueueRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageRequest;
import software.amazon.awssdk.services.sqs.model.SqsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class SendMessages {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <queueName> <message>

                Where:
                   queueName - The name of the queue.
                   message - The message to send.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String queueName = args[0];
        String message = args[1];
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();
        sendMessage(sqsClient, queueName, message);
        sqsClient.close();
    }

    public static void sendMessage(SqsClient sqsClient, String queueName, String
 message) {
        try {
```

```
            CreateQueueRequest request = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .build();
            sqsClient.createQueue(request);

            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            SendMessageRequest sendMsgRequest = SendMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .messageBody(message)
                    .delaySeconds(5)
                    .build();

            sqsClient.sendMessage(sendMsgRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
import { SendMessageCommand, SQSClient } from "@aws-sdk/client-sqs";
```

```
const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

export const main = async (sqsQueueUrl = SQS_QUEUE_URL) => {
  const command = new SendMessageCommand({
    QueueUrl: sqsQueueUrl,
    DelaySeconds: 10,
    MessageAttributes: {
      Title: {
        DataType: "String",
        StringValue: "The Whistler",
      },
      Author: {
        DataType: "String",
        StringValue: "John Grisham",
      },
      WeeksOn: {
        DataType: "Number",
        StringValue: "6",
      },
    },
    MessageBody:
      "Information about current NY Times fiction bestseller for week of
 12/11/2016.",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  // Remove DelaySeconds parameter and value for FIFO queues
  DelaySeconds: 10,
  MessageAttributes: {
    Title: {
      DataType: "String",
      StringValue: "The Whistler",
    },
    Author: {
      DataType: "String",
      StringValue: "John Grisham",
    },
    WeeksOn: {
      DataType: "Number",
      StringValue: "6",
    },
  },
  MessageBody:
    "Information about current NY Times fiction bestseller for week of
 12/11/2016.",
  // MessageDeduplicationId: "TheWhistler",  // Required for FIFO queues
  // MessageGroupId: "Group1",  // Required for FIFO queues
  QueueUrl: "SQS_QUEUE_URL",
};
```

```
sqs.sendMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.MessageId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun sendMessages(queueUrlVal: String, message: String) {
    println("Sending multiple messages")
    println("\nSend message")
    val sendRequest = SendMessageRequest {
        queueUrl = queueUrlVal
        messageBody = message
        delaySeconds = 10
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.sendMessage(sendRequest)
        println("A single message was successfully sent.")
    }
}

suspend fun sendBatchMessages(queueUrlVal: String?) {
    println("Sending multiple messages")
```

```
    val msg1 = SendMessageBatchRequestEntry {
        id = "id1"
        messageBody = "Hello from msg 1"
    }

    val msg2 = SendMessageBatchRequestEntry {
        id = "id2"
        messageBody = "Hello from msg 2"
    }

    val sendMessageBatchRequest = SendMessageBatchRequest {
        queueUrl = queueUrlVal
        entries = listOf(msg1, msg2)
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.sendMessageBatch(sendMessageBatchRequest)
        println("Batch message were successfully sent.")
    }
}
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def send_message(queue, message_body, message_attributes=None):
    """
    Send a message to an Amazon SQS queue.

    :param queue: The queue that receives the message.
    :param message_body: The body text of the message.
```

```
    :param message_attributes: Custom attributes of the message. These are key-
value
                               pairs that can be whatever you want.
    :return: The response from SQS that contains the assigned message ID.
    """
    if not message_attributes:
        message_attributes = {}

    try:
        response = queue.send_message(
            MessageBody=message_body, MessageAttributes=message_attributes
        )
    except ClientError as error:
        logger.exception("Send message failed: %s", message_body)
        raise error
    else:
        return response
```

- Para obter detalhes da API, consulte a SendMessageReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @param message_body [String] The contents of the message to be sent.
```

```
# @return [Boolean] true if the message was sent; otherwise, false.
# @example
#   exit 1 unless message_sent?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     'This is my message.'
#   )
def message_sent?(sqs_client, queue_url, message_body)
  sqs_client.send_message(
    queue_url: queue_url,
    message_body: message_body
  )
  true
rescue StandardError => e
  puts "Error sending message: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  message_body = "This is my message."

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Sending a message to the queue named '#{queue_name}'..."

  if message_sent?(sqs_client, queue_url, message_body)
    puts "Message sent."
  else
    puts "Message not sent."
  end
end

# Example usage:
```

```
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn send(client: &Client, queue_url: &String, message: &SQSMessage) ->
 Result<(), Error> {
    println!("Sending message to queue with URL: {}", queue_url);

    let rsp = client
        .send_message()
        .queue_url(queue_url)
        .message_body(&message.body)
        // If the queue is FIFO, you need to set .message_deduplication_id
        // and message_group_id or configure the queue for
 ContentBasedDeduplication.
        .send()
        .await?;

    println!("Send message to the queue: {:#?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWS SDK for Rust.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_sqs->sendmessage(              " oo_result is returned for
testing purposes. "
          iv_queueurl = iv_queue_url
          iv_messagebody = iv_message
       ).
       MESSAGE 'Message sent to SQS queue.' TYPE 'I'.
     CATCH /aws1/cx_sqsinvalidmsgconts.
       MESSAGE 'Message contains non-valid characters.' TYPE 'E'.
     CATCH /aws1/cx_sqsunsupportedop.
       MESSAGE 'Operation not supported.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWS SDK for SAP ABAP.

Defina atributos de fila do Amazon SQS

Os exemplos de código a seguir mostram como definir os atributos para uma fila do Amazon SQS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Publicar mensagens em filas

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina o atributo de política de uma fila para um tópico.

```
    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string
topicArn, string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                         $"\"Service\": " +
                                             "\"sns.amazonaws.com\"" +
                                            "}," +
                                     "\"Action\": \"sqs:SendMessage\"," +
                                     $"\"Resource\": \"{queueArn}\"," +
                                      "\"Condition\": {" +
                                           "\"ArnEquals\": {" +
                                                $"\"aws:SourceArn\":
\"{topicArn}\"" +
                                            "}" +
                                        "}" +
                                "}]" +
                            "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
```

```
                QueueUrl = queueUrl,
                Attributes = new Dictionary<string, string>() { { "Policy",
 queuePolicy } }
            });
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for .NET da API.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Set the value for an attribute in an Amazon Simple Queue Service (Amazon SQS)
 queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param attributeName: An attribute name enum.
  \param attribute: The attribute value as a string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueAttributes(const Aws::String &queueURL,
                                     Aws::SQS::Model::QueueAttributeName
 attributeName,
                                     const Aws::String &attribute,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            attributeName,
            attribute);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set the attribute  " <<

 Aws::SQS::Model::QueueAttributeNameMapper::GetNameForQueueAttributeName(
                        attributeName)
                << " with value " << attribute << " in queue " <<
                queueURL << "." << std::endl;
    }
    else {
        std::cout << "Error setting attribute for  queue " <<
                queueURL << ": " << outcome.GetError().GetMessage() <<
                std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como definir atributos de fila

Este exemplo define a fila especificada com um atraso de entrega de 10 segundos, um tamanho máximo de mensagem de 128 KB (128 KB * 1.024 bytes), um período de retenção de mensagens de 3 dias (3 dias * 24 horas * 60 minutos * 60 segundos), um tempo de espera de recebimento de mensagens de 20 segundos e um tempo limite de visibilidade padrão de

60 segundos. Este exemplo também associa a fila de mensagens não entregues especificada a uma contagem máxima de recebimento de 1.000 mensagens.

Comando:

```
aws sqs set-queue-attributes --queue-url https://sqs.us-
east-1.amazonaws.com/80398EXAMPLE/MyNewQueue --attributes file://set-queue-
attributes.json
```

Arquivo de entrada (set-queue-attributes.json):

```
{
  "DelaySeconds": "10",
  "MaximumMessageSize": "131072",
  "MessageRetentionPeriod": "259200",
  "ReceiveMessageWaitTimeSeconds": "20",
  "RedrivePolicy": "{\"deadLetterTargetArn\":\"arn:aws:sqs:us-
east-1:80398EXAMPLE:MyDeadLetterQueue\",\"maxReceiveCount\":\"1000\"}",
  "VisibilityTimeout": "60"
}
```

Saída:

```
None.
```

- Para obter detalhes da API, consulte SetQueueAttributesem Referência de AWS CLI Comandos.

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
```

```
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy
 to an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages
 to the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
  Attributes: map[string]string{
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}
```

```
// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for Go da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new SetQueueAttributesCommand({
```

```
    QueueUrl: queueUrl,
    Attributes: {
      DelaySeconds: "1",
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

Configure uma fila do Amazon SQS para usar sondagem longa.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new SetQueueAttributesCommand({
    Attributes: {
      ReceiveMessageWaitTimeSeconds: "20",
    },
    QueueUrl: queueUrl,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for JavaScript da API.

Cenários para o Amazon SQS com SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Queue Service (Amazon SQS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
- Envie e receba lotes de mensagens com o Amazon SQS usando um SDK da AWS

Criar e publicar em um tópico FIFO do Amazon SNS usando um AWS SDK

Os exemplos de código a seguir mostram como criar e publicar em um tópico FIFO do Amazon SNS.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse exemplo

- cria um tópico FIFO do Amazon SNS, duas filas FIFO do Amazon SQS e uma fila padrão.
- inscreve as filas no tópico e publica a mensagem no tópico.

O teste verifica o recebimento da mensagem em cada fila. O exemplo completo também mostra a adição de políticas de acesso e exclui os recursos no final.

```
public class PriceUpdateExample {
    public final static SnsClient snsClient = SnsClient.create();
    public final static SqsClient sqsClient = SqsClient.create();

    public static void main(String[] args) {

        final String usage = "\n" +
                "Usage: " +
                "    <topicName> <wholesaleQueueFifoName> <retailQueueFifoName>
 <analyticsQueueName>\n\n" +
```

```
                "Where:\n" +
                "   fifoTopicName - The name of the FIFO topic that you want to
create. \n\n" +
                "   wholesaleQueueARN - The name of a SQS FIFO queue that will be
created for the wholesale consumer. \n\n"
                +
                "   retailQueueARN - The name of a SQS FIFO queue that will
created for the retail consumer. \n\n" +
                "   analyticsQueueARN - The name of a SQS standard queue that
will be created for the analytics consumer. \n\n";
        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        final String fifoTopicName = args[0];
        final String wholeSaleQueueName = args[1];
        final String retailQueueName = args[2];
        final String analyticsQueueName = args[3];

        // For convenience, the QueueData class holds metadata about a queue:
ARN, URL,
        // name and type.
        List<QueueData> queues = List.of(
                new QueueData(wholeSaleQueueName, QueueType.FIFO),
                new QueueData(retailQueueName, QueueType.FIFO),
                new QueueData(analyticsQueueName, QueueType.Standard));

        // Create queues.
        createQueues(queues);

        // Create a topic.
        String topicARN = createFIFOTopic(fifoTopicName);

        // Subscribe each queue to the topic.
        subscribeQueues(queues, topicARN);

        // Allow the newly created topic to send messages to the queues.
        addAccessPolicyToQueuesFINAL(queues, topicARN);

        // Publish a sample price update message with payload.
        publishPriceUpdate(topicARN, "{\"product\": 214, \"price\": 79.99}",
"Consumables");
```

```
        // Clean up resources.
        deleteSubscriptions(queues);
        deleteQueues(queues);
        deleteTopic(topicARN);
    }

    public static String createFIFOTopic(String topicName) {
        try {
            // Create a FIFO topic by using the SNS service client.
            Map<String, String> topicAttributes = Map.of(
                    "FifoTopic", "true",
                    "ContentBasedDeduplication", "false");

            CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                    .name(topicName)
                    .attributes(topicAttributes)
                    .build();

            CreateTopicResponse response = snsClient.createTopic(topicRequest);
            String topicArn = response.topicArn();
            System.out.println("The topic ARN is" + topicArn);

            return topicArn;

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void subscribeQueues(List<QueueData> queues, String topicARN) {
        queues.forEach(queue -> {
            SubscribeRequest subscribeRequest = SubscribeRequest.builder()
                    .topicArn(topicARN)
                    .endpoint(queue.queueARN)
                    .protocol("sqs")
                    .build();

            // Subscribe to the endpoint by using the SNS service client.
            // Only Amazon SQS queues can receive notifications from an Amazon
SNS FIFO
            // topic.
```

```
            SubscribeResponse subscribeResponse =
snsClient.subscribe(subscribeRequest);
            System.out.println("The queue [" + queue.queueARN + "] subscribed to
the topic [" + topicARN + "]");
            queue.subscriptionARN = subscribeResponse.subscriptionArn();
        });
    }

    public static void publishPriceUpdate(String topicArn, String payload, String
groupId) {

        try {
            // Create and publish a message that updates the wholesale price.
            String subject = "Price Update";
            String dedupId = UUID.randomUUID().toString();
            String attributeName = "business";
            String attributeValue = "wholesale";

            MessageAttributeValue msgAttValue = MessageAttributeValue.builder()
                    .dataType("String")
                    .stringValue(attributeValue)
                    .build();

            Map<String, MessageAttributeValue> attributes = new HashMap<>();
            attributes.put(attributeName, msgAttValue);
            PublishRequest pubRequest = PublishRequest.builder()
                    .topicArn(topicArn)
                    .subject(subject)
                    .message(payload)
                    .messageGroupId(groupId)
                    .messageDeduplicationId(dedupId)
                    .messageAttributes(attributes)
                    .build();

            final PublishResponse response = snsClient.publish(pubRequest);
            System.out.println(response.messageId());
            System.out.println(response.sequenceNumber());
            System.out.println("Message was published to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateTopic
  - Publicar
  - Assinar

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO do Amazon SNS, inscreva filas padrão e FIFO do Amazon SQS no tópico e publique uma mensagem no tópico.

```
def usage_demo():
    """Shows how to subscribe queues to a FIFO topic."""
    print("-" * 88)
    print("Welcome to the `Subscribe queues to a FIFO topic` demo!")
    print("-" * 88)

    sns = boto3.resource("sns")
    sqs = boto3.resource("sqs")
    fifo_topic_wrapper = FifoTopicWrapper(sns)
    sns_wrapper = SnsWrapper(sns)

    prefix = "sqs-subscribe-demo-"
    queues = set()
    subscriptions = set()

    wholesale_queue = sqs.create_queue(
        QueueName=prefix + "wholesale.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
```

```
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(wholesale_queue)
    print(f"Created FIFO queue with URL: {wholesale_queue.url}.")

    retail_queue = sqs.create_queue(
        QueueName=prefix + "retail.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(retail_queue)
    print(f"Created FIFO queue with URL: {retail_queue.url}.")

    analytics_queue = sqs.create_queue(QueueName=prefix + "analytics",
Attributes={})
    queues.add(analytics_queue)
    print(f"Created standard queue with URL: {analytics_queue.url}.")

    topic = fifo_topic_wrapper.create_fifo_topic("price-updates-topic.fifo")
    print(f"Created FIFO topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        fifo_topic_wrapper.add_access_policy(q, topic.attributes["TopicArn"])

    print(f"Added access policies for topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        sub = fifo_topic_wrapper.subscribe_queue_to_topic(
            topic, q.attributes["QueueArn"]
        )
        subscriptions.add(sub)

    print(f"Subscribed queues to topic: {topic.attributes['TopicArn']}.")

    input("Press Enter to publish a message to the topic.")
```

```
    message_id = fifo_topic_wrapper.publish_price_update(
        topic, '{"product": 214, "price": 79.99}', "Consumables"
    )

    print(f"Published price update with message ID: {message_id}.")

    # Clean up the subscriptions, queues, and topic.
    input("Press Enter to clean up resources.")
    for s in subscriptions:
        sns_wrapper.delete_subscription(s)

    sns_wrapper.delete_topic(topic)

    for q in queues:
        fifo_topic_wrapper.delete_queue(q)

    print(f"Deleted subscriptions, queues, and topic.")

    print("Thanks for watching!")
    print("-" * 88)



class FifoTopicWrapper:
    """Encapsulates Amazon SNS FIFO topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource

    def create_fifo_topic(self, topic_name):
        """
        Create a FIFO topic.
        Topic names must be made up of only uppercase and lowercase ASCII
 letters,
        numbers, underscores, and hyphens, and must be between 1 and 256
 characters long.
        For a FIFO topic, the name must end with the .fifo suffix.

        :param topic_name: The name for the topic.
        :return: The new topic.
```

```
        """
        try:
            topic = self.sns_resource.create_topic(
                Name=topic_name,
                Attributes={
                    "FifoTopic": str(True),
                    "ContentBasedDeduplication": str(False),
                },
            )
            logger.info("Created FIFO topic with name=%s.", topic_name)
            return topic
        except ClientError as error:
            logger.exception("Couldn't create topic with name=%s!", topic_name)
            raise error


    @staticmethod
    def add_access_policy(queue, topic_arn):
        """
        Add the necessary access policy to a queue, so
        it can receive messages from a topic.

        :param queue: The queue resource.
        :param topic_arn: The ARN of the topic.
        :return: None.
        """
        try:
            queue.set_attributes(
                Attributes={
                    "Policy": json.dumps(
                        {
                            "Version": "2012-10-17",
                            "Statement": [
                                {
                                    "Sid": "test-sid",
                                    "Effect": "Allow",
                                    "Principal": {"AWS": "*"},
                                    "Action": "SQS:SendMessage",
                                    "Resource": queue.attributes["QueueArn"],
                                    "Condition": {
                                        "ArnLike": {"aws:SourceArn": topic_arn}
                                    },
                                }
                            ],
```

```
                        }
                    )
                }
            )
            logger.info("Added trust policy to the queue.")
        except ClientError as error:
            logger.exception("Couldn't add trust policy to the queue!")
            raise error


    @staticmethod
    def subscribe_queue_to_topic(topic, queue_arn):
        """
        Subscribe a queue to a topic.

        :param topic: The topic resource.
        :param queue_arn: The ARN of the queue.
        :return: The subscription resource.
        """
        try:
            subscription = topic.subscribe(
                Protocol="sqs",
                Endpoint=queue_arn,
            )
            logger.info("The queue is subscribed to the topic.")
            return subscription
        except ClientError as error:
            logger.exception("Couldn't subscribe queue to topic!")
            raise error


    @staticmethod
    def publish_price_update(topic, payload, group_id):
        """
        Compose and publish a message that updates the wholesale price.

        :param topic: The topic to publish to.
        :param payload: The message to publish.
        :param group_id: The group ID for the message.
        :return: The ID of the message.
        """
        try:
            att_dict = {"business": {"DataType": "String", "StringValue":
"wholesale"}}
```

```
            dedup_id = uuid.uuid4()
            response = topic.publish(
                Subject="Price Update",
                Message=payload,
                MessageAttributes=att_dict,
                MessageGroupId=group_id,
                MessageDeduplicationId=str(dedup_id),
            )
            message_id = response["MessageId"]
            logger.info("Published message to topic %s.", topic.arn)
        except ClientError as error:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise error
        return message_id


    @staticmethod
    def delete_queue(queue):
        """
        Removes an SQS queue. When run against an AWS account, it can take up to
        60 seconds before the queue is actually deleted.

        :param queue: The queue to delete.
        :return: None
        """
        try:
            queue.delete()
            logger.info("Deleted queue with URL=%s.", queue.url)
        except ClientError as error:
            logger.exception("Couldn't delete queue with URL=%s!", queue.url)
            raise error
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTopic
  - Publicar
  - Assinar

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO, inscreva uma fila FIFO do Amazon SQS no tópico e publique uma mensagem em um tópico do Amazon SNS.

```
    " Creates a FIFO topic. "
    DATA lt_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>tt_topicattributesmap.
    DATA ls_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>ts_topicattributesmap_maprow.
    ls_tpc_attributes-key = 'FifoTopic'.
    ls_tpc_attributes-value = NEW /aws1/cl_snstopicattrsmap_w( iv_value =
 'true' ).
    INSERT ls_tpc_attributes INTO TABLE lt_tpc_attributes.

    TRY.
        DATA(lo_create_result) = lo_sns->createtopic(
               iv_name = iv_topic_name
               it_attributes = lt_tpc_attributes
        ).
        DATA(lv_topic_arn) = lo_create_result->get_topicarn( ).
        ov_topic_arn = lv_topic_arn.                                    "
 ov_topic_arn is returned for testing purposes. "
        MESSAGE 'FIFO topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
        MESSAGE 'Unable to create more topics. You have reached the maximum
 number of topics allowed.' TYPE 'E'.
    ENDTRY.

    " Subscribes an endpoint to an Amazon Simple Notification Service (Amazon
 SNS) topic. "
    " Only Amazon Simple Queue Service (Amazon SQS) FIFO queues can be subscribed
 to an SNS FIFO topic. "
```

```
    TRY.
        DATA(lo_subscribe_result) = lo_sns->subscribe(
               iv_topicarn = lv_topic_arn
               iv_protocol = 'sqs'
               iv_endpoint = iv_queue_arn
           ).
        DATA(lv_subscription_arn) = lo_subscribe_result->get_subscriptionarn( ).
        ov_subscription_arn = lv_subscription_arn.                      "
 ov_subscription_arn is returned for testing purposes. "
        MESSAGE 'SQS queue was subscribed to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snssubscriptionlmte00.
        MESSAGE 'Unable to create subscriptions. You have reached the maximum
 number of subscriptions allowed.' TYPE 'E'.
    ENDTRY.

    " Publish message to SNS topic. "
    TRY.
        DATA lt_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>tt_messageattributemap.
        DATA ls_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>ts_messageattributemap_maprow.
        ls_msg_attributes-key = 'Importance'.
        ls_msg_attributes-value = NEW /aws1/cl_snsmessageattrvalue( iv_datatype =
 'String' iv_stringvalue = 'High' ).
        INSERT ls_msg_attributes INTO TABLE lt_msg_attributes.

        DATA(lo_result) = lo_sns->publish(
             iv_topicarn = lv_topic_arn
             iv_message = 'The price of your mobile plan has been increased from
 $19 to $23'
             iv_subject = 'Changes to mobile plan'
             iv_messagegroupid = 'Update-2'
             iv_messagededuplicationid = 'Update-2.1'
             it_messageattributes = lt_msg_attributes
      ).
        ov_message_id = lo_result->get_messageid( ).                    "
 ov_message_id is returned for testing purposes. "
        MESSAGE 'Message was published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateTopic
  - Publicar
  - Assinar

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Console application to run a workflow scenario for topics and queues.
/// </summary>
public static class TopicsAndQueues
{
    private static bool _useFifoTopic = false;
    private static bool _useContentBasedDeduplication = false;
    private static string _topicName = null!;
```

```
    private static string _topicArn = null!;

    private static readonly int _queueCount = 2;
    private static readonly string[] _queueUrls = new string[_queueCount];
    private static readonly string[] _subscriptionArns = new string[_queueCount];
    private static readonly string[] _tones = { "cheerful", "funny", "serious",
 "sincere" };
    public static SNSWrapper SnsWrapper { get; set; } = null!;
    public static SQSWrapper SqsWrapper { get; set; } = null!;
    public static bool UseConsole { get; set; } = true;
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EventBridge.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonSQS>()
                    .AddAWSService<IAmazonSimpleNotificationService>()
                    .AddTransient<SNSWrapper>()
                    .AddTransient<SQSWrapper>()
            )
            .Build();

        ServicesSetup(host);
        PrintDescription();

        await RunScenario();

    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        SnsWrapper = host.Services.GetRequiredService<SNSWrapper>();
        SqsWrapper = host.Services.GetRequiredService<SQSWrapper>();
    }
```

```
    /// <summary>
    /// Run the scenario for working with topics and queues.
    /// </summary>
    /// <returns>True if successful.</returns>
    public static async Task<bool> RunScenario()
    {
        try
        {
            await SetupTopic();

            await SetupQueues();

            await PublishMessages();

            foreach (var queueUrl in _queueUrls)
            {
                var messages = await PollForMessages(queueUrl);
                if (messages.Any())
                {
                    await DeleteMessages(queueUrl, messages);
                }
            }
            await CleanupResources();

            Console.WriteLine("Messaging with topics and queues workflow is
complete.");
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await CleanupResources();
            Console.WriteLine(new string('-', 80));
            return false;
        }
    }

    /// <summary>
    /// Print a description for the tasks in the workflow.
    /// </summary>
    /// <returns>Async task.</returns>
```

```
    private static void PrintDescription()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Welcome to messaging with topics and queues.");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"In this workflow, you will create an SNS topic and
 subscribe {_queueCount} SQS queues to the topic." +
                          $"\r\nYou can select from several options for
 configuring the topic and the subscriptions for the 2 queues." +
                          $"\r\nYou can then post to the topic and see the
 results in the queues.\r\n");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the SNS topic to be used with the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> SetupTopic()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"SNS topics can be configured as FIFO (First-In-First-
Out)." +
                          $"\r\nFIFO topics deliver messages in order and support
 deduplication and message filtering." +
                          $"\r\nYou can then post to the topic and see the
 results in the queues.\r\n");

        _useFifoTopic = GetYesNoResponse("Would you like to work with FIFO
 topics?");

        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            _topicName = GetUserResponse("Enter a name for your SNS topic: ",
 "example-topic");
            Console.WriteLine(
                "Because you have selected a FIFO topic, '.fifo' must be appended
 to the topic name.\r\n");

            Console.WriteLine(new string('-', 80));
```

```
            Console.WriteLine($"Because you have chosen a FIFO topic,
 deduplication is supported." +
                              $"\r\nDeduplication IDs are either set in the
 message or automatically generated " +
                              $"\r\nfrom content using a hash function.\r\n" +
                              $"\r\nIf a message is successfully published to an
 SNS FIFO topic, any message " +
                              $"\r\npublished and determined to have the same
 deduplication ID, " +
                              $"\r\nwithin the five-minute deduplication
 interval, is accepted but not delivered.\r\n" +
                              $"\r\nFor more information about deduplication, " +
                              $"\r\nsee https://docs.aws.amazon.com/sns/latest/
dg/fifo-message-dedup.html.");

            _useContentBasedDeduplication = GetYesNoResponse("Use content-based
 deduplication instead of entering a deduplication ID?");
            Console.WriteLine(new string('-', 80));
        }

        _topicArn = await SnsWrapper.CreateTopicWithName(_topicName,
 _useFifoTopic, _useContentBasedDeduplication);

        Console.WriteLine($"Your new topic with the name {_topicName}" +
                          $"\r\nand Amazon Resource Name (ARN) {_topicArn}" +
                          $"\r\nhas been created.\r\n");

        Console.WriteLine(new string('-', 80));
        return _topicArn;
    }

    /// <summary>
    /// Set up the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task SetupQueues()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now you will create {_queueCount} Amazon Simple Queue
 Service (Amazon SQS) queues to subscribe to the topic.");

        // Repeat this section for each queue.
        for (int i = 0; i < _queueCount; i++)
        {
```

```
            var queueName = GetUserResponse("Enter a name for an Amazon SQS
queue: ", $"example-queue-{i}");
            if (_useFifoTopic)
            {
                // Only explain this once.
                if (i == 0)
                {
                    Console.WriteLine(
                        "Because you have selected a FIFO topic, '.fifo' must be
appended to the queue name.");
                }

                var queueUrl = await SqsWrapper.CreateQueueWithName(queueName,
_useFifoTopic);

                _queueUrls[i] = queueUrl;

                Console.WriteLine($"Your new queue with the name {queueName}" +
                                  $"\r\nand queue URL {queueUrl}" +
                                  $"\r\nhas been created.\r\n");

                if (i == 0)
                {
                    Console.WriteLine(
                        $"The queue URL is used to retrieve the queue ARN,\r\n" +
                        $"which is used to create a subscription.");
                    Console.WriteLine(new string('-', 80));
                }

                var queueArn = await SqsWrapper.GetQueueArnByUrl(queueUrl);

                if (i == 0)
                {
                    Console.WriteLine(
                        $"An AWS Identity and Access Management (IAM) policy must
be attached to an SQS queue, enabling it to receive\r\n" +
                        $"messages from an SNS topic");
                }

                await SqsWrapper.SetQueuePolicyForTopic(queueArn, _topicArn,
queueUrl);

                await SetupFilters(i, queueArn, queueName);
            }
```

```
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up filters with user options for a queue.
    /// </summary>
    /// <param name="queueCount">The number of this queue.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="queueName">The name of the queue.</param>
    /// <returns>Async Task.</returns>
    public static async Task SetupFilters(int queueCount, string queueArn, string
 queueName)
    {
        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            // Only explain this once.
            if (queueCount == 0)
            {
                Console.WriteLine(
                    "Subscriptions to a FIFO topic can have filters." +
                    "If you add a filter to this subscription, then only the
 filtered messages " +
                    "will be received in the queue.");

                Console.WriteLine(
                    "For information about message filtering, " +
                    "see https://docs.aws.amazon.com/sns/latest/dg/sns-message-
filtering.html");

                Console.WriteLine(
                    "For this example, you can filter messages by a" +
                    "TONE attribute.");
            }

            var useFilter = GetYesNoResponse($"Filter messages for {queueName}'s
 subscription to the topic?");

            string? filterPolicy = null;
            if (useFilter)
            {
                filterPolicy = CreateFilterPolicy();
```

```
            }
            var subscriptionArn = await
 SnsWrapper.SubscribeTopicWithFilter(_topicArn, filterPolicy,
                queueArn);
            _subscriptionArns[queueCount] = subscriptionArn;

            Console.WriteLine(
                $"The queue {queueName} has been subscribed to the topic
 {_topicName} " +
                $"with the subscription ARN {subscriptionArn}");
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Use user input to create a filter policy for a subscription.
    /// </summary>
    /// <returns>The serialized filter policy.</returns>
    public static string CreateFilterPolicy()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            $"You can filter messages by one or more of the following" +
            $"TONE attributes.");

        List<string> filterSelections = new List<string>();

        var selectionNumber = 0;
        do
        {
            Console.WriteLine(
                $"Enter a number to add a TONE filter, or enter 0 to stop adding
 filters.");
            for (int i = 0; i < _tones.Length; i++)
            {
                Console.WriteLine($"\t{i + 1}. {_tones[i]}");
            }

            var selection = GetUserResponse("", filterSelections.Any() ? "0" :
 "1");
            int.TryParse(selection, out selectionNumber);
            if (selectionNumber > 0 && !
filterSelections.Contains(_tones[selectionNumber - 1]))
            {
```

```
                filterSelections.Add(_tones[selectionNumber - 1]);
            }
        } while (selectionNumber != 0);

        var filters = new Dictionary<string, List<string>>
        {
            { "tone", filterSelections }
        };
        string filterPolicy = JsonSerializer.Serialize(filters);
        return filterPolicy;
    }

    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is
a sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must
set a message group ID." +
                                  "\r\nAll messages within the same group will be
received in the order " +
                                  "they were published.");

                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID
for this message:", "1");

                if (!_useContentBasedDeduplication)
                {
```

```
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                        "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this
message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID
for this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
                    }
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?",
false);
        }
    }

    /// <summary>
    /// Poll for the published messages to see the results of the user's choices.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task<List<Message>> PollForMessages(string queueUrl)
```

```
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now the SQS queue at {queueUrl} will be polled to
retrieve the messages." +
                          "\r\nPress any key to continue.");
        if (UseConsole)
        {
            Console.ReadLine();
        }

        var moreMessages = true;
        var messages = new List<Message>();
        while (moreMessages)
        {
            var newMessages = await SqsWrapper.ReceiveMessagesByUrl(queueUrl,
10);

            moreMessages = newMessages.Any();
            if (moreMessages)
            {
                messages.AddRange(newMessages);
            }
        }

        Console.WriteLine($"{messages.Count} message(s) were received by the
queue at {queueUrl}.");

        foreach (var message in messages)
        {
            Console.WriteLine("\tMessage:" +
                              $"\n\t{message.Body}");
        }

        Console.WriteLine(new string('-', 80));
        return messages;
    }

    /// <summary>
    /// Delete the message using handles in a batch.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task DeleteMessages(string queueUrl, List<Message>
messages)
    {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Now we can delete the messages in this queue in a
batch.");
        await SqsWrapper.DeleteMessageBatchByUrl(queueUrl, messages);
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        try
        {
            foreach (var queueUrl in _queueUrls)
            {
                if (!string.IsNullOrEmpty(queueUrl))
                {
                    var deleteQueue =
                        GetYesNoResponse($"Delete queue with url {queueUrl}?");
                    if (deleteQueue)
                    {
                        await SqsWrapper.DeleteQueueByUrl(queueUrl);
                    }
                }
            }

            foreach (var subscriptionArn in _subscriptionArns)
            {
                if (!string.IsNullOrEmpty(subscriptionArn))
                {
                    await SnsWrapper.UnsubscribeByArn(subscriptionArn);
                }
            }

            var deleteTopic = GetYesNoResponse($"Delete topic {_topicName}?");
            if (deleteTopic)
            {
                await SnsWrapper.DeleteTopicByArn(_topicArn);
            }
```

```
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Unable to clean up resources. Here's why:
 {ex.Message}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question, bool defaultAnswer =
 true)
    {
        if (UseConsole)
        {
            Console.WriteLine(question);
            var ynResponse = Console.ReadLine();
            var response = ynResponse != null &&
                           ynResponse.Equals("y",
                               StringComparison.InvariantCultureIgnoreCase);
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }

    /// <summary>
    /// Helper method to get a string response from the user through the console.
    /// </summary>
    /// <param name="question">The question string to print on the console.</
param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static string GetUserResponse(string question, string defaultAnswer)
    {
        if (UseConsole)
        {
```

```
            var response = "";
            while (string.IsNullOrEmpty(response))
            {
                Console.WriteLine(question);
                response = Console.ReadLine();
            }
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }
}
```

Crie uma classe que envolva as operações do Amazon SQS.

```
/// <summary>
/// Wrapper for Amazon Simple Queue Service (SQS) operations.
/// </summary>
public class SQSWrapper
{
    private readonly IAmazonSQS _amazonSQSClient;

    /// <summary>
    /// Constructor for the Amazon SQS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SQS client.</param>
    public SQSWrapper(IAmazonSQS amazonSQS)
    {
        _amazonSQSClient = amazonSQS;
    }

    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
 useFifoQueue)
    {
        int maxMessage = 256 * 1024;
```

```
        var queueAttributes = new Dictionary<string, string>
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
            });
        return createResponse.QueueUrl;
    }

    /// <summary>
    /// Get the ARN for a queue from its URL.
    /// </summary>
    /// <param name="queueUrl">The URL of the queue.</param>
    /// <returns>The ARN of the queue.</returns>
    public async Task<string> GetQueueArnByUrl(string queueUrl)
    {
        var getAttributesRequest = new GetQueueAttributesRequest()
        {
```

```
            QueueUrl = queueUrl,
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await
_amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }

    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string
topicArn, string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                         $"\"Service\": " +
                                             "\"sns.amazonaws.com\"" +
                                            "}," +
                                     "\"Action\": \"sqs:SendMessage\"," +
                                     $"\"Resource\": \"{queueArn}\"," +
                                      "\"Condition\": {" +
                                           "\"ArnEquals\": {" +
                                               $"\"aws:SourceArn\":
\"{topicArn}\"" +
                                            "}" +
                                        "}" +
                                "}]" +
                            "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
                QueueUrl = queueUrl,
```

```
                Attributes = new Dictionary<string, string>() { { "Policy",
 queuePolicy } }
            });
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
        return messageResponse.Messages;
    }

    /// <summary>
    /// Delete a batch of messages from a queue by its url.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMessageBatchByUrl(string queueUrl,
 List<Message> messages)
    {
        var deleteRequest = new DeleteMessageBatchRequest()
        {
            QueueUrl = queueUrl,
            Entries = new List<DeleteMessageBatchRequestEntry>()
        };
        foreach (var message in messages)
        {
            deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
```

```
            {
                ReceiptHandle = message.ReceiptHandle,
                Id = message.MessageId
            });
        }

        var deleteResponse = await
 _amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

        return deleteResponse.Failed.Any();
    }

    /// <summary>
    /// Delete a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteQueueByUrl(string queueUrl)
    {
        var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
            new DeleteQueueRequest()
            {
                QueueUrl = queueUrl
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

Crie uma classe que envolva as operações do Amazon SNS.

```
/// <summary>
/// Wrapper for Amazon Simple Notification Service (SNS) operations.
/// </summary>
public class SNSWrapper
{
    private readonly IAmazonSimpleNotificationService _amazonSNSClient;

    /// <summary>
    /// Constructor for the Amazon SNS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SNS client.</param>
```

```
    public SNSWrapper(IAmazonSimpleNotificationService amazonSNS)
    {
        _amazonSNSClient = amazonSNS;
    }

    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
                { "FifoTopic", "true" }
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
 "true");
            }
        }

        var createResponse = await
 _amazonSNSClient.CreateTopicAsync(createTopicRequest);
```

```
        return createResponse.TopicArn;
    }

    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
 subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
 filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
 { { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
 _amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }

    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</
param>
    /// <param name="attributeValue">The optional attribute value for the
 message.</param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
```

```
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await
_amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }


    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
```

```
            {
                SubscriptionArn = subscriptionArn
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete a topic by its topic ARN.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTopicByArn(string topicArn)
    {
        var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
            new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon
 SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
    printAsterisksLine();
    std::cout << "In this workflow, you will create an SNS topic and subscribe "
              << NUMBER_OF_QUEUES <<
              " SQS queues to the topic." << std::endl;
    std::cout
            << "You can select from several options for configuring the topic and
 the subscriptions for the "
            << NUMBER_OF_QUEUES << " queues." << std::endl;
    std::cout << "You can then post to the topic and see the results in the
 queues."
              << std::endl;

    Aws::SNS::SNSClient snsClient(clientConfiguration);

    printAsterisksLine();

    std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
              << std::endl;
    std::cout
```

```
            << "FIFO topics deliver messages in order and support deduplication
 and message filtering."
            << std::endl;
    bool isFifoTopic = askYesNoQuestion(
            "Would you like to work with FIFO topics? (y/n) ");

    bool contentBasedDeduplication = false;
    Aws::String topicName;
    if (isFifoTopic) {
        printAsterisksLine();
        std::cout << "Because you have chosen a FIFO topic, deduplication is
 supported."
                  << std::endl;
        std::cout
                << "Deduplication IDs are either set in the message or
 automatically generated "
                << "from content using a hash function." << std::endl;
        std::cout
                << "If a message is successfully published to an SNS FIFO topic,
 any message "
                << "published and determined to have the same deduplication ID, "
                << std::endl;
        std::cout
                << "within the five-minute deduplication interval, is accepted
 but not delivered."
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a
 deduplication ID? (y/n) ");
    }

    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
    {
```

```
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;

        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " <<
std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

```
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                      "true");
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue,
'.fifo' must "
                            << "be appended to the queue name." << std::endl;
                }
            }

            request.SetQueueName(queueName);
            queueNames.push_back(queueName);

            Aws::SQS::Model::CreateQueueOutcome outcome =
                    sqsClient.CreateQueue(request);

            if (outcome.IsSuccess()) {
                queueURL = outcome.GetResult().GetQueueUrl();
```

```
                std::cout << "Your new SQS queue with the name '" << queueName
                          << "' and the queue URL " << std::endl;
                std::cout << "'" << queueURL << "' has been created." <<
std::endl;
            }
            else {
                std::cerr << "Error with SQS::CreateQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
        queueURLS.push_back(queueURL);

        if (first) // Only explain this once.
        {
            std::cout
                    << "The queue URL is used to retrieve the queue ARN, which is
"
                    << "used to create a subscription." << std::endl;
        }

        Aws::String queueARN;
        {
            // 3.  Get the SQS queue ARN attribute.
            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
```

```
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        if (first) {
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling
it to receive "
                       "messages from an SNS topic." << std::endl;
        }
```

```
        {
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have
filters."
```

```
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then
 only the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/
sns-message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a
 \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
                                << "will be added to this subscription." <<
 std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);
```

```
            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
 outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN <<
 "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
                        << "Because you are using a FIFO topic, you must set a
 message group ID."
                        << std::endl;
```

```
                std::cout
                        << "All messages within the same group will be received
in the "
                        << "order they were published." << std::endl;
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
```

```
            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }

        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
 outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
```

```
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }

        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
```

```
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}


bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
                                      const Aws::Vector<Aws::String>
 &subscriptionARNS,
                                      const Aws::SNS::SNSClient &snsClient,
                                      const Aws::SQS::SQSClient &sqsClient,
```

```
                                        bool askUser) {
    bool result = true;
    printAsterisksLine();
    if (!queueURLS.empty() && askUser &&
        askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

        for (const auto &queueURL: queueURLS) {
            // 9.  Delete an SQS queue.
            Aws::SQS::Model::DeleteQueueRequest request;
            request.SetQueueUrl(queueURL);

            Aws::SQS::Model::DeleteQueueOutcome outcome =
                    sqsClient.DeleteQueue(request);

            if (outcome.IsSuccess()) {
                std::cout << "The queue with URL '" << queueURL
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        for (const auto &subscriptionARN: subscriptionARNS) {
            // 10. Unsubscribe an SNS subscription.
            Aws::SNS::Model::UnsubscribeRequest request;
            request.SetSubscriptionArn(subscriptionARN);

            Aws::SNS::Model::UnsubscribeOutcome outcome =
                    snsClient.Unsubscribe(request);

            if (outcome.IsSuccess()) {
                std::cout << "Unsubscribe of subscription ARN '" <<
subscriptionARN
                          << "' was successful." << std::endl;
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
```

```
            }
        }
    }

    printAsterisksLine();
    if (!topicARN.empty() && askUser &&
        askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

        // 11. Delete an SNS topic.
        Aws::SNS::Model::DeleteTopicRequest request;
        request.SetTopicArn(topicARN);

        Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

        if (outcome.IsSuccess()) {
            std::cout << "The topic with ARN '" << topicARN
                      << "' was successfully deleted." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Create an IAM policy that gives an SQS queue permission to receive messages
 from an SNS topic.
/*!
 \sa createPolicyForQueue()
 \param queueARN: The SQS queue Amazon Resource Name (ARN).
 \param topicARN: The SNS topic ARN.
 \return Aws::String: The policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
                                                          const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
```

```
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
const FIFO_SUFFIX = ".fifo"
const TONE_KEY = "tone"

var ToneChoices = []string{"cheerful", "funny", "serious", "sincere"}

// MessageBody is used to deserialize the body of a message from a JSON string.
type MessageBody struct {
 Message string
}

// ScenarioRunner separates the steps of this scenario into individual functions
 so that
// they are simpler to read and understand.
type ScenarioRunner struct {
 questioner demotools.IQuestioner
 snsActor   *actions.SnsActions
 sqsActor   *actions.SqsActions
}

func (runner ScenarioRunner) CreateTopic() (string, string, bool, bool) {
 log.Println("SNS topics can be configured as FIFO (First-In-First-Out) or
 standard.\n" +
  "FIFO topics deliver messages in order and support deduplication and message
 filtering.")
 isFifoTopic := runner.questioner.AskBool("\nWould you like to work with FIFO
 topics? (y/n) ", "y")

 contentBasedDeduplication := false
 if isFifoTopic {
  log.Println(strings.Repeat("-", 88))
```

```
  log.Println("Because you have chosen a FIFO topic, deduplication is supported.
\n" +
   "Deduplication IDs are either set in the message or are automatically
 generated\n" +
   "from content using a hash function. If a message is successfully published to
\n" +
   "an SNS FIFO topic, any message published and determined to have the same\n" +
   "deduplication ID, within the five-minute deduplication interval, is accepted
\n" +
   "but not delivered. For more information about deduplication, see:\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/fifo-message-dedup.html.")
  contentBasedDeduplication = runner.questioner.AskBool(
   "\nDo you want to use content-based deduplication instead of entering a
 deduplication ID? (y/n) ", "y")
 }
 log.Println(strings.Repeat("-", 88))

 topicName := runner.questioner.Ask("Enter a name for your SNS topic. ")
 if isFifoTopic {
  topicName = fmt.Sprintf("%v%v", topicName, FIFO_SUFFIX)
  log.Printf("Because you have selected a FIFO topic, '%v' must be appended to
\n"+
   "the topic name.", FIFO_SUFFIX)
 }

 topicArn, err := runner.snsActor.CreateTopic(topicName, isFifoTopic,
 contentBasedDeduplication)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new topic with the name '%v' and Amazon Resource Name (ARN)
 \n"+
  "'%v' has been created.", topicName, topicArn)

 return topicName, topicArn, isFifoTopic, contentBasedDeduplication
}

func (runner ScenarioRunner) CreateQueue(ordinal string, isFifoTopic bool)
 (string, string) {
 queueName := runner.questioner.Ask(fmt.Sprintf("Enter a name for the %v SQS
 queue. ", ordinal))
 if isFifoTopic {
  queueName = fmt.Sprintf("%v%v", queueName, FIFO_SUFFIX)
  if ordinal == "first" {
```

```
    log.Printf("Because you are creating a FIFO SQS queue, '%v' must "+
     "be appended to the queue name.\n", FIFO_SUFFIX)
   }
  }
  queueUrl, err := runner.sqsActor.CreateQueue(queueName, isFifoTopic)
  if err != nil {
   panic(err)
  }
  log.Printf("Your new SQS queue with the name '%v' and the queue URL "+
   "'%v' has been created.", queueName, queueUrl)

  return queueName, queueUrl
}

func (runner ScenarioRunner) SubscribeQueueToTopic(
 queueName string, queueUrl string, topicName string, topicArn string, ordinal
 string,
 isFifoTopic bool) (string, bool) {

 queueArn, err := runner.sqsActor.GetQueueArn(queueUrl)
 if err != nil {
  panic(err)
 }
 log.Printf("The ARN of your queue is: %v.\n", queueArn)

 err = runner.sqsActor.AttachSendMessagePolicy(queueUrl, queueArn, topicArn)
 if err != nil {
  panic(err)
 }
 log.Println("Attached an IAM policy to the queue so the SNS topic can send " +
  "messages to it.")
 log.Println(strings.Repeat("-", 88))

 var filterPolicy map[string][]string
 if isFifoTopic {
  if ordinal == "first" {
   log.Println("Subscriptions to a FIFO topic can have filters.\n" +
    "If you add a filter to this subscription, then only the filtered messages\n"
 +
    "will be received in the queue.\n" +
    "For information about message filtering, see\n" +
    "\thttps://docs.aws.amazon.com/sns/latest/dg/sns-message-filtering.html\n" +
    "For this example, you can filter messages by a \"tone\" attribute.")
  }
```

```
  wantFiltering := runner.questioner.AskBool(
   fmt.Sprintf("Do you want to filter messages that are sent to \"%v\"\n"+
    "from the %v topic? (y/n) ", queueName, topicName), "y")
  if wantFiltering {
   log.Println("You can filter messages by one or more of the following \"tone\"
 attributes.")

   var toneSelections []string
   askAboutTones := true
   for askAboutTones {
    toneIndex := runner.questioner.AskChoice(
     "Enter the number of the tone you want to filter by:\n", ToneChoices)
    toneSelections = append(toneSelections, ToneChoices[toneIndex])
    askAboutTones = runner.questioner.AskBool("Do you want to add another tone to
 the filter? (y/n) ", "y")
   }
   log.Printf("Your subscription will be filtered to only pass the following
 tones: %v\n", toneSelections)
   filterPolicy = map[string][]string{TONE_KEY: toneSelections}
  }
 }

 subscriptionArn, err := runner.snsActor.SubscribeQueue(topicArn, queueArn,
 filterPolicy)
 if err != nil {
  panic(err)
 }
 log.Printf("The queue %v is now subscribed to the topic %v with the subscription
 ARN %v.\n",
  queueName, topicName, subscriptionArn)

 return subscriptionArn, filterPolicy != nil
}

func (runner ScenarioRunner) PublishMessages(topicArn string, isFifoTopic bool,
 contentBasedDeduplication bool, usingFilters bool) {
 var message string
 var groupId string
 var dedupId string
 var toneSelection string
 publishMore := true
 for publishMore {
  groupId = ""
```

```
  dedupId = ""
  toneSelection = ""
  message = runner.questioner.Ask("Enter a message to publish: ")
  if isFifoTopic {
   log.Println("Because you are using a FIFO topic, you must set a message group
 ID.\n" +
    "All messages within the same group will be received in the order they were
 published.")
   groupId = runner.questioner.Ask("Enter a message group ID: ")
   if !contentBasedDeduplication {
    log.Println("Because you are not using content-based deduplication,\n" +
     "you must enter a deduplication ID.")
    dedupId = runner.questioner.Ask("Enter a deduplication ID: ")
   }
  }
  if usingFilters {
   if runner.questioner.AskBool("Add a tone attribute so this message can be
 filtered? (y/n) ", "y") {
    toneIndex := runner.questioner.AskChoice(
     "Enter the number of the tone you want to filter by:\n", ToneChoices)
    toneSelection = ToneChoices[toneIndex]
   }
  }

  err := runner.snsActor.Publish(topicArn, message, groupId, dedupId, TONE_KEY,
 toneSelection)
  if err != nil {
   panic(err)
  }
  log.Println(("Your message was published."))

  publishMore = runner.questioner.AskBool("Do you want to publish another
 messsage? (y/n) ", "y")
 }
}

func (runner ScenarioRunner) PollForMessages(queueUrls []string) {
 log.Println("Polling queues for messages...")
 for _, queueUrl := range queueUrls {
  var messages []types.Message
  for {
   currentMsgs, err := runner.sqsActor.GetMessages(queueUrl, 10, 1)
   if err != nil {
    panic(err)
```

```
    }
    if len(currentMsgs) == 0 {
     break
    }
    messages = append(messages, currentMsgs...)
   }
   if len(messages) == 0 {
    log.Printf("No messages were received by queue %v.\n", queueUrl)
   } else if len(messages) == 1 {
    log.Printf("One message was received by queue %v:\n", queueUrl)

   } else {
    log.Printf("%v messages were received by queue %v:\n", len(messages),
  queueUrl)
   }
   for msgIndex, message := range messages {
    messageBody := MessageBody{}
    err := json.Unmarshal([]byte(*message.Body), &messageBody)
    if err != nil {
     panic(err)
    }
    log.Printf("Message %v: %v\n", msgIndex+1, messageBody.Message)
   }

   if len(messages) > 0 {
    log.Printf("Deleting %v messages from queue %v.\n", len(messages), queueUrl)
    err := runner.sqsActor.DeleteMessages(queueUrl, messages)
    if err != nil {
     panic(err)
    }
   }
  }
}

// RunTopicsAndQueuesScenario is an interactive example that shows you how to use
 the
// AWS SDK for Go to create and use Amazon SNS topics and Amazon SQS queues.
//
// 1. Create a topic (FIFO or non-FIFO).
// 2. Subscribe several queues to the topic with an option to apply a filter.
// 3. Publish messages to the topic.
// 4. Poll the queues for messages received.
// 5. Delete the topic and the queues.
//
```

```
// This example creates service clients from the specified sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
func RunTopicsAndQueuesScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner) {
 resources := Resources{}
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.\n" +
    "Cleaning up any resources that were created...")
   resources.Cleanup()
  }
 }()
 queueCount := 2

 log.Println(strings.Repeat("-", 88))
 log.Printf("Welcome to messaging with topics and queues.\n\n"+
  "In this workflow, you will create an SNS topic and subscribe %v SQS queues to
 the\n"+
  "topic. You can select from several options for configuring the topic and the
\n"+
  "subscriptions for the queues. You can then post to the topic and see the
 results\n"+
  "in the queues.\n", queueCount)

 log.Println(strings.Repeat("-", 88))

 runner := ScenarioRunner{
  questioner: questioner,
  snsActor:   &actions.SnsActions{SnsClient: sns.NewFromConfig(sdkConfig)},
  sqsActor:   &actions.SqsActions{SqsClient: sqs.NewFromConfig(sdkConfig)},
 }
 resources.snsActor = runner.snsActor
 resources.sqsActor = runner.sqsActor

 topicName, topicArn, isFifoTopic, contentBasedDeduplication :=
 runner.CreateTopic()
 resources.topicArn = topicArn
 log.Println(strings.Repeat("-", 88))
```

```
 log.Printf("Now you will create %v SQS queues and subscribe them to the topic.
\n", queueCount)
 ordinals := []string{"first", "next"}
 usingFilters := false
 for _, ordinal := range ordinals {
  queueName, queueUrl := runner.CreateQueue(ordinal, isFifoTopic)
  resources.queueUrls = append(resources.queueUrls, queueUrl)

  _, filtering := runner.SubscribeQueueToTopic(queueName, queueUrl, topicName,
 topicArn, ordinal, isFifoTopic)
  usingFilters = usingFilters || filtering
 }

 log.Println(strings.Repeat("-", 88))
 runner.PublishMessages(topicArn, isFifoTopic, contentBasedDeduplication,
 usingFilters)
 log.Println(strings.Repeat("-", 88))
 runner.PollForMessages(resources.queueUrls)

 log.Println(strings.Repeat("-", 88))

 wantCleanup := questioner.AskBool("Do you want to remove all AWS resources
 created for this scenario? (y/n) ", "y")
 if wantCleanup {
  log.Println("Cleaning up resources...")
  resources.Cleanup()
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura que envolva as ações do Amazon SNS usadas neste exemplo.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
```

```
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}



// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}
```

```
// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to
 an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string,
 filterMap map[string][]string) (string, error) {
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent
 to all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
```

```
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered
 according to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn,
 err)
 }
 return err
}
```

Defina uma estrutura que envolva as ações do Amazon SQS usadas neste exemplo.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}
```

```
// CreateQueue creates an Amazon SQS queue with the specified name. You can
 specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
}



// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
// of an Amazon SQS queue.
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}
```

```
// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy
 to an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages
 to the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
  Attributes: map[string]string{
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}

// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
```

```
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
 if err != nil {
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 } else {
  messages = result.Messages
 }
 return messages, err
}



// DeleteMessages uses the DeleteMessageBatch action to delete a batch of
 messages from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
```

```
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage

- SetQueueAttributes
- Assinar
- Cancelar assinatura

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada para esse fluxo de trabalho.

```
import { SNSClient } from "@aws-sdk/client-sns";
import { SQSClient } from "@aws-sdk/client-sqs";

import { TopicsQueuesWkflw } from "./TopicsQueuesWkflw.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { SlowLogger } from "@aws-sdk-examples/libs/slow-logger.js";

export const startSnsWorkflow = () => {
  const noLoggerDelay = process.argv.find((arg) => arg === "--no-logger-delay");
  const snsClient = new SNSClient({});
  const sqsClient = new SQSClient({});
  const prompter = new Prompter();
  const logger = noLoggerDelay ? console : new SlowLogger(25);

  const wkflw = new TopicsQueuesWkflw(snsClient, sqsClient, prompter, logger);

  wkflw.start();
};
```

O código anterior fornece as dependências necessárias e inicia o fluxo de trabalho. A próxima seção contém a maior parte do exemplo.

```
const toneChoices = [
  { name: "cheerful", value: "cheerful" },
  { name: "funny", value: "funny" },
  { name: "serious", value: "serious" },
  { name: "sincere", value: "sincere" },
];

export class TopicsQueuesWkflw {
  // SNS topic is configured as First-In-First-Out
  isFifo = true;

  // Automatic content-based deduplication is enabled.
  autoDedup = false;

  snsClient;
  sqsClient;
  topicName;
  topicArn;
  subscriptionArns = [];
  /**
   * @type {{ queueName: string, queueArn: string, queueUrl: string, policy?:
 string }[]}
   */
  queues = [];
  prompter;

  /**
   * @param {import('@aws-sdk/client-sns').SNSClient} snsClient
   * @param {import('@aws-sdk/client-sqs').SQSClient} sqsClient
   * @param {import('../../libs/prompter.js').Prompter} prompter
   * @param {import('../../libs/logger.js').Logger} logger
   */
  constructor(snsClient, sqsClient, prompter, logger) {
    this.snsClient = snsClient;
    this.sqsClient = sqsClient;
    this.prompter = prompter;
    this.logger = logger;
  }

  async welcome() {
    await this.logger.log(MESSAGES.description);
  }
```

```
  async confirmFifo() {
    await this.logger.log(MESSAGES.snsFifoDescription);
    this.isFifo = await this.prompter.confirm({
      message: MESSAGES.snsFifoPrompt,
    });

    if (this.isFifo) {
      this.logger.logSeparator(MESSAGES.headerDedup);
      await this.logger.log(MESSAGES.deduplicationNotice);
      await this.logger.log(MESSAGES.deduplicationDescription);
      this.autoDedup = await this.prompter.confirm({
        message: MESSAGES.deduplicationPrompt,
      });
    }
  }

  async createTopic() {
    await this.logger.log(MESSAGES.creatingTopics);
    this.topicName = await this.prompter.input({
      message: MESSAGES.topicNamePrompt,
    });
    if (this.isFifo) {
      this.topicName += ".fifo";
      this.logger.logSeparator(MESSAGES.headerFifoNaming);
      await this.logger.log(MESSAGES.appendFifoNotice);
    }

    const response = await this.snsClient.send(
      new CreateTopicCommand({
        Name: this.topicName,
        Attributes: {
          FifoTopic: this.isFifo ? "true" : "false",
          ...(this.autoDedup ? { ContentBasedDeduplication: "true" } : {}),
        },
      }),
    );

    this.topicArn = response.TopicArn;

    await this.logger.log(
      MESSAGES.topicCreatedNotice
        .replace("${TOPIC_NAME}", this.topicName)
        .replace("${TOPIC_ARN}", this.topicArn),
```

```
    );
  }

  async createQueues() {
    await this.logger.log(MESSAGES.createQueuesNotice);
    // Increase this number to add more queues.
    let maxQueues = 2;

    for (let i = 0; i < maxQueues; i++) {
      await this.logger.log(MESSAGES.queueCount.replace("${COUNT}", i + 1));
      let queueName = await this.prompter.input({
        message: MESSAGES.queueNamePrompt.replace(
          "${EXAMPLE_NAME}",
          i === 0 ? "good-news" : "bad-news",
        ),
      });

      if (this.isFifo) {
        queueName += ".fifo";
        await this.logger.log(MESSAGES.appendFifoNotice);
      }

      const response = await this.sqsClient.send(
        new CreateQueueCommand({
          QueueName: queueName,
          Attributes: { ...(this.isFifo ? { FifoQueue: "true" } : {}) },
        }),
      );

      const { Attributes } = await this.sqsClient.send(
        new GetQueueAttributesCommand({
          QueueUrl: response.QueueUrl,
          AttributeNames: ["QueueArn"],
        }),
      );

      this.queues.push({
        queueName,
        queueArn: Attributes.QueueArn,
        queueUrl: response.QueueUrl,
      });

      await this.logger.log(
        MESSAGES.queueCreatedNotice
```

```
          .replace("${QUEUE_NAME}", queueName)
          .replace("${QUEUE_URL}", response.QueueUrl)
          .replace("${QUEUE_ARN}", Attributes.QueueArn),
      );
    }
  }

  async attachQueueIamPolicies() {
    for (const [index, queue] of this.queues.entries()) {
      const policy = JSON.stringify(
        {
          Statement: [
            {
              Effect: "Allow",
              Principal: {
                Service: "sns.amazonaws.com",
              },
              Action: "sqs:SendMessage",
              Resource: queue.queueArn,
              Condition: {
                ArnEquals: {
                  "aws:SourceArn": this.topicArn,
                },
              },
            },
          ],
        },
        null,
        2,
      );

      if (index !== 0) {
        this.logger.logSeparator();
      }

      await this.logger.log(MESSAGES.attachPolicyNotice);
      console.log(policy);
      const addPolicy = await this.prompter.confirm({
        message: MESSAGES.addPolicyConfirmation.replace(
          "${QUEUE_NAME}",
          queue.queueName,
        ),
      });
```

```
      if (addPolicy) {
        await this.sqsClient.send(
          new SetQueueAttributesCommand({
            QueueUrl: queue.queueUrl,
            Attributes: {
              Policy: policy,
            },
          }),
        );
        queue.policy = policy;
      } else {
        await this.logger.log(
          MESSAGES.policyNotAttachedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }
  }

  async subscribeQueuesToTopic() {
    for (const [index, queue] of this.queues.entries()) {
      /**
       * @type {import('@aws-sdk/client-sns').SubscribeCommandInput}
       */
      const subscribeParams = {
        TopicArn: this.topicArn,
        Protocol: "sqs",
        Endpoint: queue.queueArn,
      };
      let tones = [];

      if (this.isFifo) {
        if (index === 0) {
          await this.logger.log(MESSAGES.fifoFilterNotice);
        }
        tones = await this.prompter.checkbox({
          message: MESSAGES.fifoFilterSelect.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
          choices: toneChoices,
        });
```

```
      if (tones.length) {
        subscribeParams.Attributes = {
          FilterPolicyScope: "MessageAttributes",
          FilterPolicy: JSON.stringify({
            tone: tones,
          }),
        };
      }
    }

    const { SubscriptionArn } = await this.snsClient.send(
      new SubscribeCommand(subscribeParams),
    );

    this.subscriptionArns.push(SubscriptionArn);

    await this.logger.log(
      MESSAGES.queueSubscribedNotice
        .replace("${QUEUE_NAME}", queue.queueName)
        .replace("${TOPIC_NAME}", this.topicName)
        .replace("${TONES}", tones.length ? tones.join(", ") : "none"),
    );
  }
}

async publishMessages() {
  const message = await this.prompter.input({
    message: MESSAGES.publishMessagePrompt,
  });

  let groupId, deduplicationId, choices;

  if (this.isFifo) {
    await this.logger.log(MESSAGES.groupIdNotice);
    groupId = await this.prompter.input({
      message: MESSAGES.groupIdPrompt,
    });

    if (this.autoDedup === false) {
      await this.logger.log(MESSAGES.deduplicationIdNotice);
      deduplicationId = await this.prompter.input({
        message: MESSAGES.deduplicationIdPrompt,
      });
```

```
      }

      choices = await this.prompter.checkbox({
        message: MESSAGES.messageAttributesPrompt,
        choices: toneChoices,
      });
    }

    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });

    if (publishAnother) {
      await this.publishMessages();
    }
  }
```

```
  async receiveAndDeleteMessages() {
    for (const queue of this.queues) {
      const { Messages } = await this.sqsClient.send(
        new ReceiveMessageCommand({
          QueueUrl: queue.queueUrl,
        }),
      );

      if (Messages) {
        await this.logger.log(
          MESSAGES.messagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
        console.log(Messages);

        await this.sqsClient.send(
          new DeleteMessageBatchCommand({
            QueueUrl: queue.queueUrl,
            Entries: Messages.map((message) => ({
              Id: message.MessageId,
              ReceiptHandle: message.ReceiptHandle,
            })),
          }),
        );
      } else {
        await this.logger.log(
          MESSAGES.noMessagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }

    const deleteAndPoll = await this.prompter.confirm({
      message: MESSAGES.deleteAndPollConfirmation,
    });

    if (deleteAndPoll) {
      await this.receiveAndDeleteMessages();
    }
  }
```

```
  async destroyResources() {
    for (const subscriptionArn of this.subscriptionArns) {
      await this.snsClient.send(
        new UnsubscribeCommand({ SubscriptionArn: subscriptionArn }),
      );
    }

    for (const queue of this.queues) {
      await this.sqsClient.send(
        new DeleteQueueCommand({ QueueUrl: queue.queueUrl }),
      );
    }

    if (this.topicArn) {
      await this.snsClient.send(
        new DeleteTopicCommand({ TopicArn: this.topicArn }),
      );
    }
  }

  async start() {
    console.clear();

    try {
      this.logger.logSeparator(MESSAGES.headerWelcome);
      await this.welcome();
      this.logger.logSeparator(MESSAGES.headerFifo);
      await this.confirmFifo();
      this.logger.logSeparator(MESSAGES.headerCreateTopic);
      await this.createTopic();
      this.logger.logSeparator(MESSAGES.headerCreateQueues);
      await this.createQueues();
      this.logger.logSeparator(MESSAGES.headerAttachPolicy);
      await this.attachQueueIamPolicies();
      this.logger.logSeparator(MESSAGES.headerSubscribeQueues);
      await this.subscribeQueuesToTopic();
      this.logger.logSeparator(MESSAGES.headerPublishMessage);
      await this.publishMessages();
      this.logger.logSeparator(MESSAGES.headerReceiveMessages);
      await this.receiveAndDeleteMessages();
    } catch (err) {
      console.error(err);
    } finally {
```

```
      await this.destroyResources();
    }
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Envie e receba lotes de mensagens com o Amazon SQS usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Como criar uma fila do Amazon SQS.
- Enviar lotes de mensagens a uma fila.
- Receber lotes de mensagens de uma fila.
- Excluir lotes de mensagens de uma fila.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar funções para encapsular funções de mensagem do Amazon SQS.

```
import logging
import sys

import boto3
from botocore.exceptions import ClientError

import queue_wrapper

logger = logging.getLogger(__name__)
sqs = boto3.resource("sqs")

def send_messages(queue, messages):
    """
    Send a batch of messages in a single request to an SQS queue.
    This request may return overall success even when some messages were not
 sent.
    The caller must inspect the Successful and Failed lists in the response and
    resend any failed messages.

    :param queue: The queue to receive the messages.
    :param messages: The messages to send to the queue. These are simplified to
                     contain only the message body and attributes.
    :return: The response from SQS that contains the list of successful and
 failed
             messages.
    """
    try:
        entries = [
            {
                "Id": str(ind),
                "MessageBody": msg["body"],
```

```
                "MessageAttributes": msg["attributes"],
            }
            for ind, msg in enumerate(messages)
        ]
        response = queue.send_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info(
                    "Message sent: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Failed to send: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
    except ClientError as error:
        logger.exception("Send messages failed to queue: %s", queue)
        raise error
    else:
        return response



def receive_messages(queue, max_number, wait_time):
    """
    Receive a batch of messages in a single request from an SQS queue.

    :param queue: The queue from which to receive messages.
    :param max_number: The maximum number of messages to receive. The actual
 number
                        of messages received might be less.
    :param wait_time: The maximum time to wait (in seconds) before returning.
 When
                       this number is greater than zero, long polling is used.
 This
                       can result in reduced costs and fewer false empty
 responses.
    :return: The list of Message objects received. These each contain the body
             of the message and metadata and custom attributes.
    """
```

```
    try:
        messages = queue.receive_messages(
            MessageAttributeNames=["All"],
            MaxNumberOfMessages=max_number,
            WaitTimeSeconds=wait_time,
        )
        for msg in messages:
            logger.info("Received message: %s: %s", msg.message_id, msg.body)
    except ClientError as error:
        logger.exception("Couldn't receive messages from queue: %s", queue)
        raise error
    else:
        return messages



def delete_messages(queue, messages):
    """
    Delete a batch of messages from a queue in a single request.

    :param queue: The queue from which to delete the messages.
    :param messages: The list of messages to delete.
    :return: The response from SQS that contains the list of successful and
 failed
             message deletions.
    """
    try:
        entries = [
            {"Id": str(ind), "ReceiptHandle": msg.receipt_handle}
            for ind, msg in enumerate(messages)
        ]
        response = queue.delete_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info("Deleted %s",
 messages[int(msg_meta["Id"])].receipt_handle)
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Could not delete %s",
 messages[int(msg_meta["Id"])].receipt_handle
                )
    except ClientError:
        logger.exception("Couldn't delete messages from queue %s", queue)
```

```
    else:
        return response
```

Usar as funções de wrapper para enviar e receber mensagens em lotes.

```
def usage_demo():
    """
    Shows how to:
    * Read the lines from this Python file and send the lines in
      batches of 10 as messages to a queue.
    * Receive the messages in batches until the queue is empty.
    * Reassemble the lines of the file and verify they match the original file.
    """

    def pack_message(msg_path, msg_body, msg_line):
        return {
            "body": msg_body,
            "attributes": {
                "path": {"StringValue": msg_path, "DataType": "String"},
                "line": {"StringValue": str(msg_line), "DataType": "String"},
            },
        }

    def unpack_message(msg):
        return (
            msg.message_attributes["path"]["StringValue"],
            msg.body,
            int(msg.message_attributes["line"]["StringValue"]),
        )

    print("-" * 88)
    print("Welcome to the Amazon Simple Queue Service (Amazon SQS) demo!")
    print("-" * 88)

    queue = queue_wrapper.create_queue("sqs-usage-demo-message-wrapper")

    with open(__file__) as file:
        lines = file.readlines()

    line = 0
```

```
    batch_size = 10
    received_lines = [None] * len(lines)
    print(f"Sending file lines in batches of {batch_size} as messages.")
    while line < len(lines):
        messages = [
            pack_message(__file__, lines[index], index)
            for index in range(line, min(line + batch_size, len(lines)))
        ]
        line = line + batch_size
        send_messages(queue, messages)
        print(".", end="")
        sys.stdout.flush()
    print(f"Done. Sent {len(lines) - 1} messages.")

    print(f"Receiving, handling, and deleting messages in batches of
{batch_size}.")
    more_messages = True
    while more_messages:
        received_messages = receive_messages(queue, batch_size, 2)
        print(".", end="")
        sys.stdout.flush()
        for message in received_messages:
            path, body, line = unpack_message(message)
            received_lines[line] = body
        if received_messages:
            delete_messages(queue, received_messages)
        else:
            more_messages = False
    print("Done.")

    if all([lines[index] == received_lines[index] for index in
range(len(lines))]):
        print(f"Successfully reassembled all file lines!")
    else:
        print(f"Uh oh, some lines were missed!")

    queue.delete()

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateQueue
  - DeleteMessageBatch
  - DeleteQueue
  - ReceiveMessage
  - SendMessageBatch

Exemplos sem servidor para o Amazon SQS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Queue Service (Amazon SQS) com SDKs da AWS.

Exemplos

- Invocar uma função do Lambda em um trigger do Amazon SQS
- Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

Invocar uma função do Lambda em um trigger do Amazon SQS

Os exemplos de código a seguir mostram como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;
```

```
// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri

namespace SqsIntegrationSampleCode
{
    public async Task FunctionHandler(SQSEvent evnt, ILambdaContext context)
    {
        foreach (var message in evnt.Records)
        {
            await ProcessMessageAsync(message, context);
        }

        context.Logger.LogInformation("done");
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        try
        {
            context.Logger.LogInformation($"Processed message {message.Body}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }

    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Go.

```
package integration_sqs_to_lambda

import (
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(event events.SQSEvent) error {
 for _, record := range event.Records {
  err := processMessage(record)
  if err != nil {
   return err
  }
 }
 fmt.Println("done")
 return nil
}

func processMessage(record events.SQSMessage) error {
 fmt.Printf("Processed message %s\n", record.Body)
 // TODO: Do interesting work based on the new message
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando JavaScript.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSEvent.SQSMessage;

public class Function implements RequestHandler<SQSEvent, Void> {
    @Override
    public Void handleRequest(SQSEvent sqsEvent, Context context) {
        for (SQSMessage msg : sqsEvent.getRecords()) {
            processMessage(msg, context);
        }
        context.getLogger().log("done");
        return null;
    }

    private void processMessage(SQSMessage msg, Context context) {
        try {
            context.getLogger().log("Processed message " + msg.getBody());

            // TODO: Do interesting work based on the new message

        } catch (Exception e) {
            context.getLogger().log("An error occurred");
            throw e;
        }

    }
}
```

JavaScript

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento SQS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message) {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento SQS com o TypeScript Lambda usando.

```
import { SQSEvent, Context, SQSHandler, SQSRecord } from "aws-lambda";

export const functionHandler: SQSHandler = async (
  event: SQSEvent,
  context: Context
): Promise<void> => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
```

```
  console.info("done");
};

async function processMessageAsync(message: SQSRecord): Promise<any> {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for message in event['Records']:
        process_message(message)
    print("done")

def process_message(message):
    try:
        print(f"Processed message {message['body']}")
        # TODO: Do interesting work based on the new message
    except Exception as err:
        print("An error occurred")
        raise err
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].each do |message|
    process_message(message)
  end
  puts "done"
end

def process_message(message)
  begin
    puts "Processed message #{message['body']}"
    # TODO: Do interesting work based on the new message
  rescue StandardError => err
    puts "An error occurred"
    raise err
  end
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SQS com o Lambda usando Rust.

```
use aws_lambda_events::event::sqs::SqsEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<(), Error> {
    event.payload.records.iter().for_each(|record| {
        // process the record
        tracing::info!("Message body: {}",
 record.body.as_deref().unwrap_or_default())
    });

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion
 time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

Os exemplos de código a seguir mostram como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando o .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeri
namespace sqsSample;

public class Function
{
    public async Task<SQSBatchResponse> FunctionHandler(SQSEvent evnt,
 ILambdaContext context)
    {
        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 List<SQSBatchResponse.BatchItemFailure>();
        foreach(var message in evnt.Records)
        {
            try
            {
                //process your message
                await ProcessMessageAsync(message, context);
            }
            catch (System.Exception)
            {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.Add(new
 SQSBatchResponse.BatchItemFailure{ItemIdentifier=message.MessageId});
            }
        }
        return new SQSBatchResponse(batchItemFailures);
```

```
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        if (String.IsNullOrEmpty(message.Body))
        {
            throw new Exception("No Body in SQS Message.");
        }
        context.Logger.LogInformation($"Processed message {message.Body}");
        // TODO: Do interesting work based on the new message
        await Task.CompletedTask;
    }
}
```

Go

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando Go.

```
package main

import (
 "context"
 "encoding/json"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, sqsEvent events.SQSEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, message := range sqsEvent.Records {
```

```
  if /* Your message processing condition here */ {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": message.MessageId})
  }
 }

 sqsBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return sqsBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSBatchResponse;

import java.util.ArrayList;
import java.util.List;

public class ProcessSQSMessageBatch implements RequestHandler<SQSEvent,
 SQSBatchResponse> {
    @Override
    public SQSBatchResponse handleRequest(SQSEvent sqsEvent, Context context) {
```

```
        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<SQSBatchResponse.BatchItemFailure>();
        String messageId = "";
        for (SQSEvent.SQSMessage message : sqsEvent.getRecords()) {
            try {
                //process your message
                messageId = message.getMessageId();
            } catch (Exception e) {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.add(new
 SQSBatchResponse.BatchItemFailure(messageId));
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }
}
```

PHP

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando PHP.

```
<?php

use Bref\Context\Context;
use Bref\Event\Sqs\SqsEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
```

```
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $sqsEvent = new SqsEvent($event);
        $this->logger->info("Processing SQS records");
        $records = $sqsEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                // Assuming the SQS message is in JSON format
                $message = json_decode($record->getBody(), true);
                $this->logger->info(json_encode($message));
                // TODO: Implement your custom processing logic here
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getMessageId();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords SQS records");

        // Format failures for the response
        $failures = array_map(
            fn(string $messageId) => ['itemIdentifier' => $messageId],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
```

```
return new Handler($logger);

?>
```

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Python.

```
import json
def lambda_handler(event, context):
    if event:
        batch_item_failures = []
        sqs_batch_response = {}

        for record in event["Records"]:
            try:
                # process message
            except Exception as e:
                batch_item_failures.append({"itemIdentifier":
 record['messageId']})

        sqs_batch_response["batchItemFailures"] = batch_item_failures
        return sqs_batch_response
```

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Ruby.

```
require 'json'

def lambda_handler(event:, context:)
  if event
    batch_item_failures = []
    sqs_batch_response = {}

    event["Records"].each do |record|
      begin
        # process message
      rescue StandardError => e
        batch_item_failures << {"itemIdentifier" => record['messageId']}
      end
    end

    sqs_batch_response["batchItemFailures"] = batch_item_failures
    return sqs_batch_response
  end
end
```

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::sqs::{SqsBatchResponse, SqsEvent},
    sqs::{BatchItemFailure, SqsMessage},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn process_record(_: &SqsMessage) -> Result<(), Error> {
    Err(Error::from("Error processing message"))
}

async fn function_handler(event: LambdaEvent<SqsEvent>) ->
 Result<SqsBatchResponse, Error> {
    let mut batch_item_failures = Vec::new();
    for record in event.payload.records {
        match process_record(&record).await {
            Ok(_) => (),
            Err(_) => batch_item_failures.push(BatchItemFailure {
                item_identifier: record.message_id.unwrap(),
            }),
        }
    }

    Ok(SqsBatchResponse {
        batch_item_failures,
    })
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    run(service_fn(function_handler)).await
}
```

Exemplos entre serviços do Amazon SQS usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Simple Queue Service (Amazon SQS) com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
- Criar uma aplicação de mensageiro com o Step Functions
- Criar uma aplicação de exploração do Amazon Textract
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS

Os exemplos de código a seguir mostram como criar uma aplicação de mensagens usando o Amazon SQS.

Java

SDK para Java 2.x

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Kotlin

SDK for Kotlin

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Criar uma aplicação de mensageiro com o Step Functions

O exemplo de código a seguir mostra como criar uma aplicação de mensageiro do AWS Step Functions que recupera registros de mensagens de uma tabela de banco de dados.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o AWS Step Functions para criar uma aplicação de mensageiro que recupere registros de mensagens de uma tabela do Amazon DynamoDB e os envia com o Amazon Simple Queue Service (Amazon SQS). A máquina de estado se integra a uma função do AWS Lambda para verificar o banco de dados em busca de mensagens não enviadas.

- Crie uma máquina de estado que recupere e atualize registros de mensagens de uma tabela do Amazon DynamoDB.
- Atualize a definição de máquina de estado para enviar mensagens ao Amazon Simple Queue Service (Amazon SQS).
- Inicie e interrompa execuções da máquina de estado.
- Conecte-se ao Lambda, ao DynamoDB e ao Amazon SQS por meio de uma máquina de estado usando integrações de serviço.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

Criar uma aplicação de exploração do Amazon Textract

Os exemplos de código a seguir mostram como explorar a saída do Amazon Textract por meio de uma aplicação interativa.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon Textract para detectar elementos de texto, formulários e tabelas em uma imagem de documento. A imagem de entrada e a saída do Amazon Textract são mostradas em uma aplicaçãoTkinter que permite explorar os elementos detectados.

- Envie uma imagem de documento para o Amazon Textract e explore a saída dos elementos detectados.
- Envie imagens diretamente para o Amazon Textract ou por meio de um bucket do Amazon Simple Storage Service (Amazon S3).
- Use APIs assíncronas para iniciar um trabalho que publica uma notificação em um tópico do Amazon Simple Notification Service (Amazon SNS) quando o trabalho for concluído.
- Faça uma pesquisa em uma fila do Amazon Simple Queue Service (Amazon SQS) para obter uma mensagem de conclusão do trabalho e exiba os resultados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

Os exemplos de código a seguir mostram como detectar pessoas e objetos em um vídeo com o Amazon Rekognition.

Python

SDK para Python (Boto3)

Use o Amazon Rekognition para detectar rostos, objetos e pessoas em vídeos iniciando trabalhos de detecção assíncrona. Este exemplo também configura o Amazon Rekognition para notificar um tópico do Amazon Simple Notification Service (Amazon SNS) quando os trabalhos são concluídos e inscreve uma fila do Amazon Simple Queue Service (Amazon SQS) no tópico. Quando a fila recebe uma mensagem sobre um trabalho, o trabalho é recuperado e os resultados são apresentados.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon SNS
- Amazon SQS

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Os exemplos de código a seguir mostram como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

Java

SDK para Java 2.x

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Kotlin

SDK for Kotlin

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Exemplos de código para Step Functions usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Step Functions com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Step Functions – Mais informações sobre o Step Functions.
- Referência da API do Step Functions – Detalhes sobre todas as ações disponíveis do Step Functions.

- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, Step Functions

Os exemplos de código a seguir mostram como começar a usar o Step Functions.

.NET

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace StepFunctionsActions;

using Amazon.StepFunctions;
using Amazon.StepFunctions.Model;

public class HelloStepFunctions
{
    static async Task Main()
    {
        var stepFunctionsClient = new AmazonStepFunctionsClient();

        Console.Clear();
        Console.WriteLine("Welcome to AWS Step Functions");
        Console.WriteLine("Let's list up to 10 of your state machines:");
        var stateMachineListRequest = new ListStateMachinesRequest { MaxResults =
 10 };

        // Get information for up to 10 Step Functions state machines.
```

```
        var response = await
 stepFunctionsClient.ListStateMachinesAsync(stateMachineListRequest);

        if (response.StateMachines.Count > 0)
        {
            response.StateMachines.ForEach(stateMachine =>
            {
                Console.WriteLine($"State Machine
 Name: {stateMachine.Name}\tAmazon Resource Name (ARN):
 {stateMachine.StateMachineArn}");
            });
        }
        else
        {
            Console.WriteLine("\tNo state machines were found.");
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Versão Java do Olá.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListStateMachinesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.StateMachineListItem;
```

```
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListStateMachines {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listMachines(sfnClient);
        sfnClient.close();
    }

    public static void listMachines(SfnClient sfnClient) {
        try {
            ListStateMachinesResponse response = sfnClient.listStateMachines();
            List<StateMachineListItem> machines = response.stateMachines();
            for (StateMachineListItem machine : machines) {
                System.out.println("The name of the state machine is: " +
 machine.name());
                System.out.println("The ARN value is : " +
 machine.stateMachineArn());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest

/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

suspend fun main() {
    println(DASHES)
    println("Welcome to the AWS Step Functions Hello example.")
    println("Lets list up to ten of your state machines:")
    println(DASHES)

    listMachines()
}

suspend fun listMachines() {
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listStateMachines(ListStateMachinesRequest {})
        response.stateMachines?.forEach { machine ->
            println("The name of the state machine is ${machine.name}")
            println("The ARN value is ${machine.stateMachineArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListStateMachinesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_stepfunctions(stepfunctions_client):
    """
    Use the AWS SDK for Python (Boto3) to create an AWS Step Functions client and
 list
    the state machines in your account. This list might be empty if you haven't
 created
    any state machines.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param stepfunctions_client: A Boto3 Step Functions Client object.
    """
    print("Hello, Step Functions! Let's list up to 10 of your state machines:")
    state_machines = stepfunctions_client.list_state_machines(maxResults=10)
    for sm in state_machines["stateMachines"]:
        print(f"\t{sm['name']}: {sm['stateMachineArn']}")


if __name__ == "__main__":
    hello_stepfunctions(boto3.client("stepfunctions"))
```

- Para obter detalhes da API, consulte a ListStateMachinesReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações para Step Functions usando SDKs da AWS
  - Criar uma máquina de estado do Step Functions usando um SDK da AWS
  - Crie uma atividade do Step Functions usando um SDK da AWS
  - Exclua uma máquina de estado do Step Functions usando um SDK da AWS
  - Exclua uma atividade do Step Functions usando um SDK da AWS
  - Descreva uma máquina de estado do Step Functions usando um SDK da AWS
  - Descreva uma execução da máquina de estado do Step Functions usando um SDK da AWS
  - Obtenha dados de tarefa para uma atividade do Step Functions usando um SDK da AWS
  - Liste atividades do Step Functions usando um SDK da AWS
  - Liste execuções da máquina de estado do Step Functions usando um SDK da AWS
  - Liste máquinas de estado do Step Functions usando um SDK da AWS
  - Envie uma resposta de sucesso para uma tarefa do Step Functions usando um SDK da AWS
  - Inicie a execução da máquina de estado do Step Functions usando um SDK da AWS
- Cenários para Step Functions usando SDKs da AWS
  - Comece a usar máquinas de estado do Step Functions usando um SDK da AWS
  - Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions
- Exemplos entre serviços para Step Functions usando SDKs da AWS
  - Criar uma aplicação de mensageiro com o Step Functions
  - Usar Step Functions para invocar funções do Lambda

Ações para Step Functions usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Step Functions com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para Step Functions usando SDKs da AWS.

Exemplos

- Criar uma máquina de estado do Step Functions usando um SDK da AWS
- Crie uma atividade do Step Functions usando um SDK da AWS

- Exclua uma máquina de estado do Step Functions usando um SDK da AWS
- Exclua uma atividade do Step Functions usando um SDK da AWS
- Descreva uma máquina de estado do Step Functions usando um SDK da AWS
- Descreva uma execução da máquina de estado do Step Functions usando um SDK da AWS
- Obtenha dados de tarefa para uma atividade do Step Functions usando um SDK da AWS
- Liste atividades do Step Functions usando um SDK da AWS
- Liste execuções da máquina de estado do Step Functions usando um SDK da AWS
- Liste máquinas de estado do Step Functions usando um SDK da AWS
- Envie uma resposta de sucesso para uma tarefa do Step Functions usando um SDK da AWS
- Inicie a execução da máquina de estado do Step Functions usando um SDK da AWS

Criar uma máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como criar uma máquina de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create a Step Functions state machine.
/// </summary>
/// <param name="stateMachineName">Name for the new Step Functions state
/// machine.</param>
/// <param name="definition">A JSON string that defines the Step Functions
/// state machine.</param>
```

```
    /// <param name="roleArn">The Amazon Resource Name (ARN) of the role.</param>
    /// <returns></returns>
    public async Task<string> CreateStateMachine(string stateMachineName, string
definition, string roleArn)
    {
        var request = new CreateStateMachineRequest
        {
            Name = stateMachineName,
            Definition = definition,
            RoleArn = roleArn
        };

        var response =
            await _amazonStepFunctions.CreateStateMachineAsync(request);
        return response.StateMachineArn;
    }
```

- Para obter detalhes da API, consulte CreateStateMachinea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createMachine(SfnClient sfnClient, String roleARN,
String stateMachineName, String json) {
        try {
            CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                    .definition(json)
                    .name(stateMachineName)
                    .roleArn(roleARN)
                    .type(StateMachineType.STANDARD)
```

```
                    .build();

            CreateStateMachineResponse response =
sfnClient.createStateMachine(machineRequest);
            return response.stateMachineArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateStateMachinea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createMachine(SfnClient sfnClient, String roleARN,
String stateMachineName, String json) {
       try {
           CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                   .definition(json)
                   .name(stateMachineName)
                   .roleArn(roleARN)
                   .type(StateMachineType.STANDARD)
                   .build();

           CreateStateMachineResponse response =
sfnClient.createStateMachine(machineRequest);
           return response.stateMachineArn();
```

```
        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte a CreateStateMachinereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name, definition, role_arn):
        """
        Creates a state machine with the specific definition. The state machine
 assumes
        the provided role before it starts a run.

        :param name: The name to give the state machine.
        :param definition: The Amazon States Language definition of the steps in
 the
```

```
                            the state machine.
        :param role_arn: The Amazon Resource Name (ARN) of the role that is
assumed by
                         Step Functions when the state machine is run.
        :return: The ARN of the newly created state machine.
        """
        try:
            response = self.stepfunctions_client.create_state_machine(
                name=name, definition=definition, roleArn=role_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't create state machine %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["stateMachineArn"]
```

- Para obter detalhes da API, consulte a CreateStateMachineReferência da API AWSSDK for Python (Boto3).

Crie uma atividade do Step Functions usando um SDK da AWS

O exemplo de código a seguir mostra como criar uma atividade do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a Step Functions activity using the supplied name.
    /// </summary>
    /// <param name="activityName">The name for the new Step Functions
activity.</param>
    /// <returns>The Amazon Resource Name (ARN) for the new activity.</returns>
    public async Task<string> CreateActivity(string activityName)
    {
        var response = await _amazonStepFunctions.CreateActivityAsync(new
CreateActivityRequest { Name = activityName });
        return response.ActivityArn;
    }
```

- Para obter detalhes da API, consulte CreateActivitya Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createActivity(SfnClient sfnClient, String activityName)
{
        try {
```

```
            CreateActivityRequest activityRequest =
 CreateActivityRequest.builder()
                    .name(activityName)
                    .build();

            CreateActivityResponse response =
 sfnClient.createActivity(activityRequest);
            return response.activityArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateActivitya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createActivity(activityName: String): String? {
    val activityRequest = CreateActivityRequest {
        name = activityName
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createActivity(activityRequest)
        return response.activityArn
    }
}
```

- Para obter detalhes da API, consulte a CreateActivityreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name):
        """
        Create an activity.

        :param name: The name of the activity to create.
        :return: The Amazon Resource Name (ARN) of the newly created activity.
        """
        try:
            response = self.stepfunctions_client.create_activity(name=name)
        except ClientError as err:
            logger.error(
                "Couldn't create activity %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["activityArn"]
```

- Para obter detalhes da API, consulte a CreateActivityReferência da API AWSSDK for Python (Boto3).

Exclua uma máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma máquina de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// state machine.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteStateMachine(string stateMachineArn)
    {
        var response = await _amazonStepFunctions.DeleteStateMachineAsync(new
DeleteStateMachineRequest
        { StateMachineArn = stateMachineArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteStateMachinea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteMachine(SfnClient sfnClient, String stateMachineArn)
{
       try {
           DeleteStateMachineRequest deleteStateMachineRequest =
DeleteStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           sfnClient.deleteStateMachine(deleteStateMachineRequest);
           DescribeStateMachineRequest describeStateMachine =
DescribeStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           while (true) {
               DescribeStateMachineResponse response =
sfnClient.describeStateMachine(describeStateMachine);
               System.out.println("The state machine is not deleted yet. The
status is " + response.status());
               Thread.sleep(3000);
           }

       } catch (SfnException | InterruptedException e) {
           System.err.println(e.getMessage());
       }
       System.out.println(stateMachineArn + " was successfully deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteStateMachinea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMachine(stateMachineArnVal: String?) {
    val deleteStateMachineRequest = DeleteStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteStateMachine(deleteStateMachineRequest)
        println("$stateMachineArnVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteStateMachinereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
```

```
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def delete(self, state_machine_arn):
        """
        Delete a state machine and all of its run data.

        :param state_machine_arn: The ARN of the state machine to delete.
        """
        try:
            response = self.stepfunctions_client.delete_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteStateMachineReferência da API AWSSDK for Python (Boto3).

Exclua uma atividade do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir uma atividade do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a Step Machine activity.
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the activity.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteActivity(string activityArn)
    {
        var response = await _amazonStepFunctions.DeleteActivityAsync(new
DeleteActivityRequest { ActivityArn = activityArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteActivitya Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteActivity(SfnClient sfnClient, String actArn) {
        try {
            DeleteActivityRequest activityRequest =
 DeleteActivityRequest.builder()
                    .activityArn(actArn)
                    .build();

            sfnClient.deleteActivity(activityRequest);
            System.out.println("You have deleted " + actArn);

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteActivitya Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteActivity(actArn: String?) {
    val activityRequest = DeleteActivityRequest {
        activityArn = actArn
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteActivity(activityRequest)
        println("You have deleted $actArn")
    }
}
```

- Para obter detalhes da API, consulte a DeleteActivityreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def delete(self, activity_arn):
        """
        Delete an activity.

        :param activity_arn: The ARN of the activity to delete.
        """
        try:
            response = self.stepfunctions_client.delete_activity(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteActivityReferência da API AWSSDK for Python (Boto3).

Descreva uma máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma máquina de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information about the specified Step Functions state machine.
    /// </summary>
    /// <param name="StateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine to retrieve.</param>
    /// <returns>Information about the specified Step Functions state machine.</
returns>
    public async Task<DescribeStateMachineResponse>
 DescribeStateMachineAsync(string StateMachineArn)
    {
        var response = await _amazonStepFunctions.DescribeStateMachineAsync(new
 DescribeStateMachineRequest { StateMachineArn = StateMachineArn });
```

```
        return response;
    }
```

- Para obter detalhes da API, consulte DescribeStateMachinea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeStateMachine(SfnClient sfnClient, String
stateMachineArn) {
       try {
           DescribeStateMachineRequest stateMachineRequest =
DescribeStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           DescribeStateMachineResponse response =
sfnClient.describeStateMachine(stateMachineRequest);
           System.out.println("The name of the State machine is " +
response.name());
           System.out.println("The status of the State machine is " +
response.status());
           System.out.println("The ARN value of the State machine is " +
response.stateMachineArn());
           System.out.println("The role ARN value is " + response.roleArn());

       } catch (SfnException e) {
           System.err.println(e.getMessage());
       }
   }
```

- Para obter detalhes da API, consulte DescribeStateMachinea Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeStateMachine(stateMachineArnVal: String?) {
    val stateMachineRequest = DescribeStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.describeStateMachine(stateMachineRequest)
        println("The name of the State machine is ${response.name}")
        println("The status of the State machine is ${response.status}")
        println("The ARN value of the State machine is
 ${response.stateMachineArn}")
        println("The role ARN value is ${response.roleArn}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeStateMachinereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def describe(self, state_machine_arn):
        """
        Get data about a state machine.

        :param state_machine_arn: The ARN of the state machine to look up.
        :return: The retrieved state machine data.
        """
        try:
            response = self.stepfunctions_client.describe_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeStateMachineReferência da API AWSSDK for Python (Boto3).

Descreva uma execução da máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever uma execução da máquina de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information about the specified Step Functions execution.
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of the
    /// Step Functions execution.</param>
    /// <returns>The API response returned by the API.</returns>
    public async Task<DescribeExecutionResponse> DescribeExecutionAsync(string
executionArn)
    {
        var response = await _amazonStepFunctions.DescribeExecutionAsync(new
DescribeExecutionRequest { ExecutionArn = executionArn });
        return response;
    }
```

- Para obter detalhes da API, consulte DescribeExecutiona Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeExe(SfnClient sfnClient, String executionArn) {
        try {
            DescribeExecutionRequest executionRequest =
DescribeExecutionRequest.builder()
                    .executionArn(executionArn)
                    .build();

            String status = "";
            boolean hasSucceeded = false;
            while (!hasSucceeded) {
                DescribeExecutionResponse response =
sfnClient.describeExecution(executionRequest);
                status = response.statusAsString();
                if (status.compareTo("RUNNING") == 0) {
                    System.out.println("The state machine is still running, let's
wait for it to finish.");
                    Thread.sleep(2000);
                } else if (status.compareTo("SUCCEEDED") == 0) {
                    System.out.println("The Step Function workflow has
succeeded");
                    hasSucceeded = true;
                } else {
                    System.out.println("The Status is neither running or
succeeded");
                }
            }
            System.out.println("The Status is " + status);

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }
```

- Para obter detalhes da API, consulte DescribeExecutiona Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeExe(executionArnVal: String?) {
    val executionRequest = DescribeExecutionRequest {
        executionArn = executionArnVal
    }

    var status = ""
    var hasSucceeded = false
    while (!hasSucceeded) {
        SfnClient { region = "us-east-1" }.use { sfnClient ->
            val response = sfnClient.describeExecution(executionRequest)
            status = response.status.toString()
            if (status.compareTo("RUNNING") == 0) {
                println("The state machine is still running, let's wait for it to
 finish.")
                Thread.sleep(2000)
            } else if (status.compareTo("SUCCEEDED") == 0) {
                println("The Step Function workflow has succeeded")
                hasSucceeded = true
            } else {
                println("The Status is neither running or succeeded")
            }
        }
    }
    println("The Status is $status")
}
```

- Para obter detalhes da API, consulte a DescribeExecutionreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    def describe_run(self, run_arn):
        """
        Get data about a state machine run, such as its current status or final
output.

        :param run_arn: The ARN of the run to look up.
        :return: The retrieved run data.
        """
        try:
            response = self.stepfunctions_client.describe_execution(
                executionArn=run_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe run %s. Here's why: %s: %s",
                run_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeExecutionReferência da API AWSSDK for Python (Boto3).

Obtenha dados de tarefa para uma atividade do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados de tarefa para uma atividade do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a task with the specified Step Functions activity
    /// with the specified Amazon Resource Name (ARN).
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the Step Functions activity.</param>
    /// <param name="workerName">The name of the Step Functions worker.</param>
    /// <returns>The response from the Step Functions activity.</returns>
    public async Task<GetActivityTaskResponse> GetActivityTaskAsync(string
activityArn, string workerName)
    {
        var response = await _amazonStepFunctions.GetActivityTaskAsync(new
GetActivityTaskRequest
        { ActivityArn = activityArn, WorkerName = workerName });
        return response;
    }
```

- Para obter detalhes da API, consulte GetActivityTaska Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static List<String> getActivityTask(SfnClient sfnClient, String
actArn) {
       List<String> myList = new ArrayList<>();
       GetActivityTaskRequest getActivityTaskRequest =
GetActivityTaskRequest.builder()
               .activityArn(actArn)
               .build();

       GetActivityTaskResponse response =
sfnClient.getActivityTask(getActivityTaskRequest);
       myList.add(response.taskToken());
       myList.add(response.input());
       return myList;
   }

   /// <summary>
   /// Stop execution of a Step Functions workflow.
   /// </summary>
   /// <param name="executionArn">The Amazon Resource Name (ARN) of
   /// the Step Functions execution to stop.</param>
   /// <returns>A Boolean value indicating the success of the action.</returns>
   public async Task<bool> StopExecution(string executionArn)
   {
       var response =
```

```
            await _amazonStepFunctions.StopExecutionAsync(new
 StopExecutionRequest { ExecutionArn = executionArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte GetActivityTaska Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getActivityTask(actArn: String?): List<String> {
    val myList: MutableList<String> = ArrayList()
    val getActivityTaskRequest = GetActivityTaskRequest {
        activityArn = actArn
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getActivityTask(getActivityTaskRequest)
        myList.add(response.taskToken.toString())
        myList.add(response.input.toString())
        return myList
    }
}
```

- Para obter detalhes da API, consulte a GetActivityTaskreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def get_task(self, activity_arn):
        """
        Gets task data for an activity. When a state machine is waiting for the
        specified activity, a response is returned with data from the state
 machine.
        When a state machine is not waiting, this call blocks for 60 seconds.

        :param activity_arn: The ARN of the activity to get task data for.
        :return: The task data for the activity.
        """
        try:
            response = self.stepfunctions_client.get_activity_task(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't get a task for activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return response
```

- Para obter detalhes da API, consulte a GetActivityTaskReferência da API AWSSDK for Python (Boto3).

Liste atividades do Step Functions usando um SDK da AWS

O exemplo de código a seguir mostra como listar atividades do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Step Functions activities for the current account.
    /// </summary>
    /// <returns>A list of ActivityListItems.</returns>
    public async Task<List<ActivityListItem>> ListActivitiesAsync()
    {
        var request = new ListActivitiesRequest();
        var activities = new List<ActivityListItem>();

        do
        {
            var response = await
_amazonStepFunctions.ListActivitiesAsync(request);
```

```
            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }

            activities.AddRange(response.Activities);
        }
        while (request.NextToken is not null);

        return activities;
    }
```

- Para obter detalhes da API, consulte ListActivitiesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListActivitiesRequest;
import software.amazon.awssdk.services.sfn.model.ListActivitiesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.ActivityListItem;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListActivities {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listAllActivites(sfnClient);
        sfnClient.close();
    }

    public static void listAllActivites(SfnClient sfnClient) {
        try {
            ListActivitiesRequest activitiesRequest =
 ListActivitiesRequest.builder()
                    .maxResults(10)
                    .build();

            ListActivitiesResponse response =
 sfnClient.listActivities(activitiesRequest);
            List<ActivityListItem> items = response.activities();
            for (ActivityListItem item : items) {
                System.out.println("The activity ARN is " + item.activityArn());
                System.out.println("The activity name is " + item.name());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListActivitiesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllActivites() {

    val activitiesRequest = ListActivitiesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listActivities(activitiesRequest)
        response.activities?.forEach { item ->
            println("The activity ARN is ${item.activityArn}")
            println("The activity name is ${item.name}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListActivitiesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""
```

```
    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def find(self, name):
        """
        Find an activity by name. This requires listing activities until one is
found
        with a matching name.

        :param name: The name of the activity to search for.
        :return: If found, the ARN of the activity; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_activities")
            for page in paginator.paginate():
                for activity in page.get("activities", []):
                    if activity["name"] == name:
                        return activity["activityArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list activities. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListActivitiesReferência da API AWSSDK for Python (Boto3).

Liste execuções da máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como listar execuções de máquinas de estado do Step Functions.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Retrieve information about executions of a Step Functions
   /// state machine.
   /// </summary>
   /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
   /// Step Functions state machine.</param>
   /// <returns>A list of ExecutionListItem objects.</returns>
   public async Task<List<ExecutionListItem>> ListExecutionsAsync(string
stateMachineArn)
   {
       var executions = new List<ExecutionListItem>();
       ListExecutionsResponse response;
       var request = new ListExecutionsRequest { StateMachineArn =
stateMachineArn };

       do
       {
           response = await _amazonStepFunctions.ListExecutionsAsync(request);
           executions.AddRange(response.Executions);
           if (response.NextToken is not null)
           {
               request.NextToken = response.NextToken;
           }
       } while (response.NextToken is not null);

       return executions;
   }
```

- Para obter detalhes da API, consulte ListExecutionsa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getExeHistory(SfnClient sfnClient, String exeARN) {
        try {
            GetExecutionHistoryRequest historyRequest =
GetExecutionHistoryRequest.builder()
                    .executionArn(exeARN)
                    .maxResults(10)
                    .build();

            GetExecutionHistoryResponse historyResponse =
sfnClient.getExecutionHistory(historyRequest);
            List<HistoryEvent> events = historyResponse.events();
            for (HistoryEvent event : events) {
                System.out.println("The event type is " +
event.type().toString());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListExecutionsa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getExeHistory(exeARN: String?) {

    val historyRequest = GetExecutionHistoryRequest {
        executionArn = exeARN
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getExecutionHistory(historyRequest)
        response.events?.forEach { event ->
            println("The event type is ${event.type}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListExecutionsreferência da API AWSSDK for Kotlin.

Liste máquinas de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como listar máquinas de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a list of Step Functions state machines.
    /// </summary>
    /// <returns>A list of StateMachineListItem objects.</returns>
    public async Task<List<StateMachineListItem>> ListStateMachinesAsync()
    {
        var stateMachines = new List<StateMachineListItem>();
        var listStateMachinesPaginator =
            _amazonStepFunctions.Paginators.ListStateMachines(new
ListStateMachinesRequest());

        await foreach (var response in listStateMachinesPaginator.Responses)
        {
            stateMachines.AddRange(response.StateMachines);
        }

        return stateMachines;
    }
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListStateMachinesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.StateMachineListItem;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class ListStateMachines {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listMachines(sfnClient);
        sfnClient.close();
    }

    public static void listMachines(SfnClient sfnClient) {
        try {
            ListStateMachinesResponse response = sfnClient.listStateMachines();
            List<StateMachineListItem> machines = response.stateMachines();
            for (StateMachineListItem machine : machines) {
```

```
                System.out.println("The name of the state machine is: " +
 machine.name());
                System.out.println("The ARN value is : " +
 machine.stateMachineArn());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest

/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

suspend fun main() {
    println(DASHES)
    println("Welcome to the AWS Step Functions Hello example.")
```

```
    println("Lets list up to ten of your state machines:")
    println(DASHES)

    listMachines()
}

suspend fun listMachines() {
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listStateMachines(ListStateMachinesRequest {})
        response.stateMachines?.forEach { machine ->
            println("The name of the state machine is ${machine.name}")
            println("The ARN value is ${machine.stateMachineArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListStateMachinesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Encontrar uma máquina de estado pelo nome pesquisando a lista de máquinas de estado da conta.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client
```

```
    def find(self, name):
        """
        Find a state machine by name. This requires listing the state machines
until
        one is found with a matching name.

        :param name: The name of the state machine to search for.
        :return: The ARN of the state machine if found; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_state_machines")
            for page in paginator.paginate():
                for state_machine in page.get("stateMachines", []):
                    if state_machine["name"] == name:
                        return state_machine["stateMachineArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list state machines. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListStateMachinesReferência da API AWSSDK for Python (Boto3).

Envie uma resposta de sucesso para uma tarefa do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como enviar uma resposta de sucesso para uma tarefa do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Indicate that the Step Functions task, indicated by the
   /// task token, has completed successfully.
   /// </summary>
   /// <param name="taskToken">Identifies the task.</param>
   /// <param name="taskResponse">The response received from executing the
task.</param>
   /// <returns>A Boolean value indicating the success of the action.</returns>
   public async Task<bool> SendTaskSuccessAsync(string taskToken, string
taskResponse)
   {
       var response = await _amazonStepFunctions.SendTaskSuccessAsync(new
SendTaskSuccessRequest
       { TaskToken = taskToken, Output = taskResponse });

       return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
   }
```

- Para obter detalhes da API, consulte SendTaskSuccessa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void sendTaskSuccess(SfnClient sfnClient, String token, String
json) {
       try {
           SendTaskSuccessRequest successRequest =
SendTaskSuccessRequest.builder()
                   .taskToken(token)
                   .output(json)
                   .build();

           sfnClient.sendTaskSuccess(successRequest);

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte SendTaskSuccessa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun sendTaskSuccess(token: String?, json: String?) {
    val successRequest = SendTaskSuccessRequest {
        taskToken = token
        output = json
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.sendTaskSuccess(successRequest)
    }
}
```

- Para obter detalhes da API, consulte a SendTaskSuccessreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def send_task_success(self, task_token, task_response):
        """
        Sends a success response to a waiting activity step. A state machine with
 an
        activity step waits for the activity to get task data and then respond
 with
        either success or failure before it resumes processing.
```

```
        :param task_token: The token associated with the task. This is included
in the
                           response to the get_activity_task action and must be
sent
                           without modification.
        :param task_response: The response data from the activity. This data is
                              received and processed by the state machine.
        """
        try:
            self.stepfunctions_client.send_task_success(
                taskToken=task_token, output=task_response
            )
        except ClientError as err:
            logger.error(
                "Couldn't send task success. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a SendTaskSuccessReferência da API AWSSDK for Python (Boto3).

Inicie a execução da máquina de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar uma execução de máquina de estado do Step Functions.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar máquinas de estado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start execution of an AWS Step Functions state machine.
    /// </summary>
    /// <param name="executionName">The name to use for the execution.</param>
    /// <param name="executionJson">The JSON string to pass for execution.</
param>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>The Amazon Resource Name (ARN) of the AWS Step Functions
    /// execution.</returns>
    public async Task<string> StartExecutionAsync(string executionJson, string
 stateMachineArn)
    {
        var executionRequest = new StartExecutionRequest
        {
            Input = executionJson,
            StateMachineArn = stateMachineArn
        };

        var response = await
 _amazonStepFunctions.StartExecutionAsync(executionRequest);
        return response.ExecutionArn;
    }
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String startWorkflow(SfnClient sfnClient, String
stateMachineArn, String jsonEx) {
       UUID uuid = UUID.randomUUID();
       String uuidValue = uuid.toString();
       try {
           StartExecutionRequest executionRequest =
StartExecutionRequest.builder()
                   .input(jsonEx)
                   .stateMachineArn(stateMachineArn)
                   .name(uuidValue)
                   .build();

           StartExecutionResponse response =
sfnClient.startExecution(executionRequest);
           return response.executionArn();

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { SFNClient, StartExecutionCommand } from "@aws-sdk/client-sfn";

/**
 * @param {{ sfnClient: SFNClient, stateMachineArn: string }} config
 */
export async function startExecution({ sfnClient, stateMachineArn }) {
  const response = await sfnClient.send(
    new StartExecutionCommand({
      stateMachineArn,
    }),
  );
  console.log(response);
  // Example response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '202a9309-c16a-454b-adeb-c4d19afe3bf2',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   executionArn: 'arn:aws:states:us-
east-1:000000000000:execution:MyStateMachine:aaaaaaaa-f787-49fb-
a20c-1b61c64eafe6',
  //   startDate: 2024-01-04T15:54:08.362Z
  // }
  return response;
}
```

```
// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  startExecution({ sfnClient: new SFNClient({}), stateMachineArn: "ARN" });
}
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startWorkflow(stateMachineArnVal: String?, jsonEx: String?): String?
 {
    val uuid = UUID.randomUUID()
    val uuidValue = uuid.toString()
    val executionRequest = StartExecutionRequest {
        input = jsonEx
        stateMachineArn = stateMachineArnVal
        name = uuidValue
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.startExecution(executionRequest)
        return response.executionArn
    }
}
```

- Para obter detalhes da API, consulte a StartExecutionreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def start(self, state_machine_arn, run_input):
        """
        Start a run of a state machine with a specified input. A run is also
 known
        as an "execution" in Step Functions.

        :param state_machine_arn: The ARN of the state machine to run.
        :param run_input: The input to the state machine, in JSON format.
        :return: The ARN of the run. This can be used to get information about
 the run,
                 including its current status and final output.
        """
        try:
            response = self.stepfunctions_client.start_execution(
                stateMachineArn=state_machine_arn, input=run_input
            )
        except ClientError as err:
            logger.error(
                "Couldn't start state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return response["executionArn"]
```

- Para obter detalhes da API, consulte a StartExecutionReferência da API AWSSDK for Python (Boto3).

Cenários para Step Functions usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Step Functions com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar máquinas de estado do Step Functions usando um SDK da AWS
- Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

Comece a usar máquinas de estado do Step Functions usando um SDK da AWS

Os exemplos de código a seguir mostram como:

- Criar uma atividade.
- Criar uma máquina de estado a partir de uma definição da Amazon States Language que contenha a atividade criada anteriormente como uma etapa.
- Executar a máquina de estado e responder à atividade com entrada do usuário.
- Obter o status e a saída finais após a conclusão da execução e, em seguida, limpar os recursos.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
global using System.Text.Json;
global using Amazon.StepFunctions;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;
global using StepFunctionsActions;
global using LogLevel = Microsoft.Extensions.Logging.LogLevel;



using Amazon.IdentityManagement;
using Amazon.IdentityManagement.Model;
using Amazon.StepFunctions.Model;

namespace StepFunctionsBasics;

public class StepFunctionsBasics
{
    private static ILogger _logger = null!;
    private static IConfigurationRoot _configuration = null!;
    private static IAmazonIdentityManagementService _iamService = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Step Functions.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
```

```
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft",
 LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonStepFunctions>()
                    .AddAWSService<IAmazonIdentityManagementService>()
                    .AddTransient<StepFunctionsWrapper>()
            )
            .Build();

        _logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<StepFunctionsBasics>();

        // Load configuration settings.
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var activityName = _configuration["ActivityName"];
        var stateMachineName = _configuration["StateMachineName"];

        var roleName = _configuration["RoleName"];
        var repoBaseDir = _configuration["RepoBaseDir"];
        var jsonFilePath = _configuration["JsonFilePath"];
        var jsonFileName = _configuration["JsonFileName"];

        var uiMethods = new UiMethods();
        var stepFunctionsWrapper =
 host.Services.GetRequiredService<StepFunctionsWrapper>();

        _iamService =
 host.Services.GetRequiredService<IAmazonIdentityManagementService>();

        // Load definition for the state machine from a JSON file.
        var stateDefinitionJson = File.ReadAllText($"{repoBaseDir}{jsonFilePath}
{jsonFileName}");

        Console.Clear();
        uiMethods.DisplayOverview();
        uiMethods.PressEnter();
```

```
        uiMethods.DisplayTitle("Create activity");
        Console.WriteLine("Let's start by creating an activity.");
        string activityArn;
        string stateMachineArn;

        // Check to see if the activity already exists.
        var activityList = await stepFunctionsWrapper.ListActivitiesAsync();
        var existingActivity = activityList.FirstOrDefault(activity =>
activity.Name == activityName);
        if (existingActivity is not null)
        {
            activityArn = existingActivity.ActivityArn;
            Console.WriteLine($"Activity, {activityName}, already exists.");
        }
        else
        {
            activityArn = await
stepFunctionsWrapper.CreateActivity(activityName);
        }

        // Swap the placeholder in the JSON file with the Amazon Resource Name
(ARN)
        // of the recently created activity.
        var stateDefinition =
stateDefinitionJson.Replace("{{DOC_EXAMPLE_ACTIVITY_ARN}}", activityArn);

        uiMethods.DisplayTitle("Create state machine");
        Console.WriteLine("Now we'll create a state machine.");

        // Find or create an IAM role that can be assumed by Step Functions.
        var role = await GetOrCreateStateMachineRole(roleName);

        // See if the state machine already exists.
        var stateMachineList = await
stepFunctionsWrapper.ListStateMachinesAsync();
        var existingStateMachine =
            stateMachineList.FirstOrDefault(stateMachine => stateMachine.Name ==
stateMachineName);
        if (existingStateMachine is not null)
        {
            Console.WriteLine($"State machine, {stateMachineName}, already
exists.");
            stateMachineArn = existingStateMachine.StateMachineArn;
```

```
        }
        else
        {
            // Create the state machine.
            stateMachineArn =
                await stepFunctionsWrapper.CreateStateMachine(stateMachineName,
stateDefinition, role.Arn);
            uiMethods.PressEnter();
        }

        Console.WriteLine("The state machine has been created.");
        var describeStateMachineResponse = await
stepFunctionsWrapper.DescribeStateMachineAsync(stateMachineArn);


Console.WriteLine($"{describeStateMachineResponse.Name}\t{describeStateMachineResponse.S
        Console.WriteLine($"Current status:
{describeStateMachineResponse.Status}");
        Console.WriteLine($"Amazon Resource Name (ARN) of the role assumed by the
state machine: {describeStateMachineResponse.RoleArn}");

        var userName = string.Empty;
        Console.Write("Before we start the state machine, tell me what should
ChatSFN call you? ");
        userName = Console.ReadLine();

        // Keep asking until the user enters a string value.
        while (string.IsNullOrEmpty(userName))
        {
            Console.Write("Enter your name: ");
            userName = Console.ReadLine();
        }

        var executionJson = @"{""name"": """ + userName + @"""}";

        // Start the state machine execution.
        Console.WriteLine("Now we'll start execution of the state machine.");
        var executionArn = await
stepFunctionsWrapper.StartExecutionAsync(executionJson, stateMachineArn);
        Console.WriteLine("State machine started.");

        Console.WriteLine($"Thank you, {userName}. Now let's get started...");
        uiMethods.PressEnter();
```

```
        uiMethods.DisplayTitle("ChatSFN");

        var isDone = false;
        var response = new GetActivityTaskResponse();
        var taskToken = string.Empty;
        var userChoice = string.Empty;

        while (!isDone)
        {
            response = await
stepFunctionsWrapper.GetActivityTaskAsync(activityArn, "MvpWorker");
            taskToken = response.TaskToken;

            // Parse the returned JSON string.
            var taskJsonResponse = JsonDocument.Parse(response.Input);
            var taskJsonObject = taskJsonResponse.RootElement;
            var message = taskJsonObject.GetProperty("message").GetString();
            var actions =
taskJsonObject.GetProperty("actions").EnumerateArray().Select(x =>
x.ToString()).ToList();
            Console.WriteLine($"\n{message}\n");

            // Prompt the user for another choice.
            Console.WriteLine("ChatSFN: What would you like me to do?");
            actions.ForEach(action => Console.WriteLine($"\t{action}"));
            Console.Write($"\n{userName}, tell me your choice: ");
            userChoice = Console.ReadLine();
            if (userChoice?.ToLower() == "done")
            {
                isDone = true;
            }

            Console.WriteLine($"You have selected: {userChoice}");
            var jsonResponse = @"{""action"": """ + userChoice + @"""}";

            await stepFunctionsWrapper.SendTaskSuccessAsync(taskToken,
jsonResponse);
        }

        await stepFunctionsWrapper.StopExecution(executionArn);
        Console.WriteLine("Now we will wait for the execution to stop.");
        DescribeExecutionResponse executionResponse;
        do
        {
```

```
            executionResponse = await
stepFunctionsWrapper.DescribeExecutionAsync(executionArn);
        } while (executionResponse.Status == ExecutionStatus.RUNNING);

        Console.WriteLine("State machine stopped.");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("State machine executions");
        Console.WriteLine("Now let's take a look at the execution values for the
state machine.");

        // List the executions.
        var executions = await
stepFunctionsWrapper.ListExecutionsAsync(stateMachineArn);

        uiMethods.DisplayTitle("Step function execution values");
        executions.ForEach(execution =>
        {
            Console.WriteLine($"{execution.Name}\t{execution.StartDate} to
{execution.StopDate}");
        });

        uiMethods.PressEnter();

        // Now delete the state machine and the activity.
        uiMethods.DisplayTitle("Clean up resources");
        Console.WriteLine("Deleting the state machine...");

        await stepFunctionsWrapper.DeleteStateMachine(stateMachineArn);
        Console.WriteLine("State machine deleted.");

        Console.WriteLine("Deleting the activity...");
        await stepFunctionsWrapper.DeleteActivity(activityArn);
        Console.WriteLine("Activity deleted.");

        Console.WriteLine("The Amazon Step Functions scenario is now complete.");
    }

    static async Task<Role> GetOrCreateStateMachineRole(string roleName)
    {
        // Define the policy document for the role.
        var stateMachineRolePolicy = @"{
         ""Version"": ""2012-10-17"",
        ""Statement"": [{
```

```
            ""Sid"": """",
            ""Effect"": ""Allow"",
            ""Principal"": {
                ""Service"": ""states.amazonaws.com""},
            ""Action"": ""sts:AssumeRole""}]}";

        var role = new Role();
        var roleExists = false;

        try
        {
            var getRoleResponse = await _iamService.GetRoleAsync(new
 GetRoleRequest { RoleName = roleName });
            roleExists = true;
            role = getRoleResponse.Role;
        }
        catch (NoSuchEntityException)
        {
            // The role doesn't exist. Create it.
            Console.WriteLine($"Role, {roleName} doesn't exist. Creating it...");
        }

        if (!roleExists)
        {
            var request = new CreateRoleRequest
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = stateMachineRolePolicy,
            };

            var createRoleResponse = await _iamService.CreateRoleAsync(request);
            role = createRoleResponse.Role;
        }

        return role;
    }
}


namespace StepFunctionsBasics;

/// <summary>
/// Some useful methods to make screen display easier.
/// </summary>
```

```
public class UiMethods
{
    private readonly string _sepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the scenario.
    /// </summary>
    public void DisplayOverview()
    {
        Console.Clear();
        DisplayTitle("Welcome to the AWS Step Functions Demo");

        Console.WriteLine("This example application will do the following:");
        Console.WriteLine("\t 1. Create an activity.");
        Console.WriteLine("\t 2. Create a state machine.");
        Console.WriteLine("\t 3. Start an execution.");
        Console.WriteLine("\t 4. Run the worker, then stop it.");
        Console.WriteLine("\t 5. List executions.");
        Console.WriteLine("\t 6. Clean up the resources created for the
 example.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue.");
        _ = Console.ReadLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter"></param>
    /// <returns></returns>
    private string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
```

```
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(_sepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(_sepBar);
    }
}
```

Defina uma classe que envolva as ações de atividade e máquina de estado.

```
namespace StepFunctionsActions;

using Amazon.StepFunctions;
using Amazon.StepFunctions.Model;

/// <summary>
/// Wrapper that performs AWS Step Functions actions.
/// </summary>
public class StepFunctionsWrapper
{
    private readonly IAmazonStepFunctions _amazonStepFunctions;

    /// <summary>
    /// The constructor for the StepFunctionsWrapper. Initializes the
    /// client object passed to it.
    /// </summary>
    /// <param name="amazonStepFunctions">An initialized Step Functions client
 object.</param>
    public StepFunctionsWrapper(IAmazonStepFunctions amazonStepFunctions)
    {
        _amazonStepFunctions = amazonStepFunctions;
    }

    /// <summary>
    /// Create a Step Functions activity using the supplied name.
    /// </summary>
```

```
    /// <param name="activityName">The name for the new Step Functions
activity.</param>
    /// <returns>The Amazon Resource Name (ARN) for the new activity.</returns>
    public async Task<string> CreateActivity(string activityName)
    {
        var response = await _amazonStepFunctions.CreateActivityAsync(new
CreateActivityRequest { Name = activityName });
        return response.ActivityArn;
    }


    /// <summary>
    /// Create a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineName">Name for the new Step Functions state
    /// machine.</param>
    /// <param name="definition">A JSON string that defines the Step Functions
    /// state machine.</param>
    /// <param name="roleArn">The Amazon Resource Name (ARN) of the role.</param>
    /// <returns></returns>
    public async Task<string> CreateStateMachine(string stateMachineName, string
definition, string roleArn)
    {
        var request = new CreateStateMachineRequest
        {
            Name = stateMachineName,
            Definition = definition,
            RoleArn = roleArn
        };

        var response =
            await _amazonStepFunctions.CreateStateMachineAsync(request);
        return response.StateMachineArn;
    }


    /// <summary>
    /// Delete a Step Machine activity.
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the activity.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteActivity(string activityArn)
    {
```

```
        var response = await _amazonStepFunctions.DeleteActivityAsync(new
 DeleteActivityRequest { ActivityArn = activityArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// state machine.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteStateMachine(string stateMachineArn)
    {
        var response = await _amazonStepFunctions.DeleteStateMachineAsync(new
 DeleteStateMachineRequest
        { StateMachineArn = stateMachineArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Retrieve information about the specified Step Functions execution.
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of the
    /// Step Functions execution.</param>
    /// <returns>The API response returned by the API.</returns>
    public async Task<DescribeExecutionResponse> DescribeExecutionAsync(string
 executionArn)
    {
        var response = await _amazonStepFunctions.DescribeExecutionAsync(new
 DescribeExecutionRequest { ExecutionArn = executionArn });
        return response;
    }


    /// <summary>
    /// Retrieve information about the specified Step Functions state machine.
    /// </summary>
    /// <param name="StateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine to retrieve.</param>
    /// <returns>Information about the specified Step Functions state machine.</
returns>
```

```
   public async Task<DescribeStateMachineResponse>
DescribeStateMachineAsync(string StateMachineArn)
   {
       var response = await _amazonStepFunctions.DescribeStateMachineAsync(new
DescribeStateMachineRequest { StateMachineArn = StateMachineArn });
       return response;
   }


   /// <summary>
   /// Retrieve a task with the specified Step Functions activity
   /// with the specified Amazon Resource Name (ARN).
   /// </summary>
   /// <param name="activityArn">The Amazon Resource Name (ARN) of
   /// the Step Functions activity.</param>
   /// <param name="workerName">The name of the Step Functions worker.</param>
   /// <returns>The response from the Step Functions activity.</returns>
   public async Task<GetActivityTaskResponse> GetActivityTaskAsync(string
activityArn, string workerName)
   {
       var response = await _amazonStepFunctions.GetActivityTaskAsync(new
GetActivityTaskRequest
       { ActivityArn = activityArn, WorkerName = workerName });
       return response;
   }


   /// <summary>
   /// List the Step Functions activities for the current account.
   /// </summary>
   /// <returns>A list of ActivityListItems.</returns>
   public async Task<List<ActivityListItem>> ListActivitiesAsync()
   {
       var request = new ListActivitiesRequest();
       var activities = new List<ActivityListItem>();

       do
       {
           var response = await
_amazonStepFunctions.ListActivitiesAsync(request);

           if (response.NextToken is not null)
           {
               request.NextToken = response.NextToken;
```

```
            }

            activities.AddRange(response.Activities);
        }
        while (request.NextToken is not null);

        return activities;
    }


    /// <summary>
    /// Retrieve information about executions of a Step Functions
    /// state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>A list of ExecutionListItem objects.</returns>
    public async Task<List<ExecutionListItem>> ListExecutionsAsync(string
 stateMachineArn)
    {
        var executions = new List<ExecutionListItem>();
        ListExecutionsResponse response;
        var request = new ListExecutionsRequest { StateMachineArn =
 stateMachineArn };

        do
        {
            response = await _amazonStepFunctions.ListExecutionsAsync(request);
            executions.AddRange(response.Executions);
            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }
        } while (response.NextToken is not null);

        return executions;
    }


    /// <summary>
    /// Retrieve a list of Step Functions state machines.
    /// </summary>
    /// <returns>A list of StateMachineListItem objects.</returns>
    public async Task<List<StateMachineListItem>> ListStateMachinesAsync()
```

```
    {
        var stateMachines = new List<StateMachineListItem>();
        var listStateMachinesPaginator =
            _amazonStepFunctions.Paginators.ListStateMachines(new
 ListStateMachinesRequest());

        await foreach (var response in listStateMachinesPaginator.Responses)
        {
            stateMachines.AddRange(response.StateMachines);
        }

        return stateMachines;
    }


    /// <summary>
    /// Indicate that the Step Functions task, indicated by the
    /// task token, has completed successfully.
    /// </summary>
    /// <param name="taskToken">Identifies the task.</param>
    /// <param name="taskResponse">The response received from executing the
 task.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SendTaskSuccessAsync(string taskToken, string
 taskResponse)
    {
        var response = await _amazonStepFunctions.SendTaskSuccessAsync(new
 SendTaskSuccessRequest
        { TaskToken = taskToken, Output = taskResponse });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Start execution of an AWS Step Functions state machine.
    /// </summary>
    /// <param name="executionName">The name to use for the execution.</param>
    /// <param name="executionJson">The JSON string to pass for execution.</
param>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>The Amazon Resource Name (ARN) of the AWS Step Functions
    /// execution.</returns>
```

```
    public async Task<string> StartExecutionAsync(string executionJson, string
 stateMachineArn)
    {
        var executionRequest = new StartExecutionRequest
        {
            Input = executionJson,
            StateMachineArn = stateMachineArn
        };

        var response = await
 _amazonStepFunctions.StartExecutionAsync(executionRequest);
        return response.ExecutionArn;
    }


    /// <summary>
    /// Stop execution of a Step Functions workflow.
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of
    /// the Step Functions execution to stop.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> StopExecution(string executionArn)
    {
        var response =
            await _amazonStepFunctions.StopExecutionAsync(new
 StopExecutionRequest { ExecutionArn = executionArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution

- DescribeStateMachine
- GetActivityTask
- ListActivities
- ListStateMachines
- SendTaskSuccess
- StartExecution
- StopExecution

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * You can obtain the JSON file to create a state machine in the following
 * GitHub location.
 *
 * https://github.com/awsdocs/aws-doc-sdk-examples/tree/main/resources/
sample_files
 *
 * To run this code example, place the chat_sfn_state_machine.json file into
 * your project's resources folder.
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * This Java code example performs the following tasks:
 *
 * 1. Creates an activity.
 * 2. Creates a state machine.
```

```
 * 3. Describes the state machine.
 * 4. Starts execution of the state machine and interacts with it.
 * 5. Describes the execution.
 * 6. Delete the activity.
 * 7. Deletes the state machine.
 */
public class StepFunctionsScenario {
    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) throws Exception {
        final String usage = """

                Usage:
                    <roleARN> <activityName> <stateMachineName>

                Where:
                    roleName - The name of the IAM role to create for this state
 machine.
                    activityName - The name of an activity to create.
                    stateMachineName - The name of the state machine to create.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleName = args[0];
        String activityName = args[1];
        String stateMachineName = args[2];
        String polJSON = "{\n" +
                "    \"Version\": \"2012-10-17\",\n" +
                "    \"Statement\": [\n" +
                "        {\n" +
                "            \"Sid\": \"\",\n" +
                "            \"Effect\": \"Allow\",\n" +
                "            \"Principal\": {\n" +
                "                \"Service\": \"states.amazonaws.com\"\n" +
                "            },\n" +
                "            \"Action\": \"sts:AssumeRole\"\n" +
                "        }\n" +
                "    ]\n" +
                "}";
```

```
        Scanner sc = new Scanner(System.in);
        boolean action = false;

        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        Region regionGl = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(regionGl)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Step Functions example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an activity.");
        String activityArn = createActivity(sfnClient, activityName);
        System.out.println("The ARN of the activity is " + activityArn);
        System.out.println(DASHES);

        // Get JSON to use for the state machine and place the activityArn value
into
        // it.
        InputStream input = StepFunctionsScenario.class.getClassLoader()
                .getResourceAsStream("chat_sfn_state_machine.json");
        ObjectMapper mapper = new ObjectMapper();
        JsonNode jsonNode = mapper.readValue(input, JsonNode.class);
        String jsonString = mapper.writeValueAsString(jsonNode);

        // Modify the Resource node.
        ObjectMapper objectMapper = new ObjectMapper();
        JsonNode root = objectMapper.readTree(jsonString);
        ((ObjectNode) root.path("States").path("GetInput")).put("Resource",
activityArn);

        // Convert the modified Java object back to a JSON string.
        String stateDefinition = objectMapper.writeValueAsString(root);
        System.out.println(stateDefinition);
```

```
        System.out.println(DASHES);
        System.out.println("2. Create a state machine.");
        String roleARN = createIAMRole(iam, roleName, polJSON);
        String stateMachineArn = createMachine(sfnClient, roleARN,
 stateMachineName, stateDefinition);
        System.out.println("The ARN of the state machine is " + stateMachineArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Describe the state machine.");
        describeStateMachine(sfnClient, stateMachineArn);
        System.out.println("What should ChatSFN call you?");
        String userName = sc.nextLine();
        System.out.println("Hello " + userName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        // The JSON to pass to the StartExecution call.
        String executionJson = "{ \"name\" : \"" + userName + "\" }";
        System.out.println(executionJson);
        System.out.println("4. Start execution of the state machine and interact
 with it.");
        String runArn = startWorkflow(sfnClient, stateMachineArn, executionJson);
        System.out.println("The ARN of the state machine execution is " +
 runArn);
        List<String> myList;
        while (!action) {
            myList = getActivityTask(sfnClient, activityArn);
            System.out.println("ChatSFN: " + myList.get(1));
            System.out.println(userName + " please specify a value.");
            String myAction = sc.nextLine();
            if (myAction.compareTo("done") == 0)
                action = true;

            System.out.println("You have selected " + myAction);
            String taskJson = "{ \"action\" : \"" + myAction + "\" }";
            System.out.println(taskJson);
            sendTaskSuccess(sfnClient, myList.get(0), taskJson);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Describe the execution.");
        describeExe(sfnClient, runArn);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Delete the activity.");
        deleteActivity(sfnClient, activityArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the state machines.");
        deleteMachine(sfnClient, stateMachineArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS Step Functions example scenario is
complete.");
        System.out.println(DASHES);
    }

    public static String createIAMRole(IamClient iam, String rolename, String
polJSON) {
        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(polJSON)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            return response.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void describeExe(SfnClient sfnClient, String executionArn) {
        try {
            DescribeExecutionRequest executionRequest =
DescribeExecutionRequest.builder()
                    .executionArn(executionArn)
                    .build();
```

```
            String status = "";
            boolean hasSucceeded = false;
            while (!hasSucceeded) {
                DescribeExecutionResponse response =
sfnClient.describeExecution(executionRequest);
                status = response.statusAsString();
                if (status.compareTo("RUNNING") == 0) {
                    System.out.println("The state machine is still running, let's
wait for it to finish.");
                    Thread.sleep(2000);
                } else if (status.compareTo("SUCCEEDED") == 0) {
                    System.out.println("The Step Function workflow has
succeeded");
                    hasSucceeded = true;
                } else {
                    System.out.println("The Status is neither running or
succeeded");
                }
            }
            System.out.println("The Status is " + status);

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void sendTaskSuccess(SfnClient sfnClient, String token, String
json) {
        try {
            SendTaskSuccessRequest successRequest =
SendTaskSuccessRequest.builder()
                    .taskToken(token)
                    .output(json)
                    .build();

            sfnClient.sendTaskSuccess(successRequest);

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static List<String> getActivityTask(SfnClient sfnClient, String
actArn) {
       List<String> myList = new ArrayList<>();
       GetActivityTaskRequest getActivityTaskRequest =
GetActivityTaskRequest.builder()
               .activityArn(actArn)
               .build();

       GetActivityTaskResponse response =
sfnClient.getActivityTask(getActivityTaskRequest);
       myList.add(response.taskToken());
       myList.add(response.input());
       return myList;
   }

   public static void deleteActivity(SfnClient sfnClient, String actArn) {
       try {
           DeleteActivityRequest activityRequest =
DeleteActivityRequest.builder()
                   .activityArn(actArn)
                   .build();

           sfnClient.deleteActivity(activityRequest);
           System.out.println("You have deleted " + actArn);

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void describeStateMachine(SfnClient sfnClient, String
stateMachineArn) {
       try {
           DescribeStateMachineRequest stateMachineRequest =
DescribeStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           DescribeStateMachineResponse response =
sfnClient.describeStateMachine(stateMachineRequest);
           System.out.println("The name of the State machine is " +
response.name());
```

```
            System.out.println("The status of the State machine is " +
response.status());
            System.out.println("The ARN value of the State machine is " +
response.stateMachineArn());
            System.out.println("The role ARN value is " + response.roleArn());

        } catch (SfnException e) {
            System.err.println(e.getMessage());
        }
    }

    public static void deleteMachine(SfnClient sfnClient, String stateMachineArn)
{
        try {
            DeleteStateMachineRequest deleteStateMachineRequest =
DeleteStateMachineRequest.builder()
                    .stateMachineArn(stateMachineArn)
                    .build();

            sfnClient.deleteStateMachine(deleteStateMachineRequest);
            DescribeStateMachineRequest describeStateMachine =
DescribeStateMachineRequest.builder()
                    .stateMachineArn(stateMachineArn)
                    .build();

            while (true) {
                DescribeStateMachineResponse response =
sfnClient.describeStateMachine(describeStateMachine);
                System.out.println("The state machine is not deleted yet. The
status is " + response.status());
                Thread.sleep(3000);
            }

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
        }
        System.out.println(stateMachineArn + " was successfully deleted.");
    }

    public static String startWorkflow(SfnClient sfnClient, String
stateMachineArn, String jsonEx) {
        UUID uuid = UUID.randomUUID();
        String uuidValue = uuid.toString();
        try {
```

```
            StartExecutionRequest executionRequest =
StartExecutionRequest.builder()
                    .input(jsonEx)
                    .stateMachineArn(stateMachineArn)
                    .name(uuidValue)
                    .build();

            StartExecutionResponse response =
sfnClient.startExecution(executionRequest);
            return response.executionArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createMachine(SfnClient sfnClient, String roleARN,
String stateMachineName, String json) {
        try {
            CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                    .definition(json)
                    .name(stateMachineName)
                    .roleArn(roleARN)
                    .type(StateMachineType.STANDARD)
                    .build();

            CreateStateMachineResponse response =
sfnClient.createStateMachine(machineRequest);
            return response.stateMachineArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createActivity(SfnClient sfnClient, String activityName)
{
        try {
```

```
            CreateActivityRequest activityRequest =
 CreateActivityRequest.builder()
                    .name(activityName)
                    .build();

            CreateActivityResponse response =
 sfnClient.createActivity(activityRequest);
            return response.activityArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution
  - DescribeStateMachine
  - GetActivityTask
  - ListActivities
  - ListStateMachines
  - SendTaskSuccess
  - StartExecution
  - StopExecution

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.iam.IamClient
import aws.sdk.kotlin.services.iam.model.CreateRoleRequest
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.CreateActivityRequest
import aws.sdk.kotlin.services.sfn.model.CreateStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.DeleteActivityRequest
import aws.sdk.kotlin.services.sfn.model.DeleteStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.DescribeExecutionRequest
import aws.sdk.kotlin.services.sfn.model.DescribeStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.GetActivityTaskRequest
import aws.sdk.kotlin.services.sfn.model.ListActivitiesRequest
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest
import aws.sdk.kotlin.services.sfn.model.SendTaskSuccessRequest
import aws.sdk.kotlin.services.sfn.model.StartExecutionRequest
import aws.sdk.kotlin.services.sfn.model.StateMachineType
import aws.sdk.kotlin.services.sfn.paginators.listActivitiesPaginated
import aws.sdk.kotlin.services.sfn.paginators.listStateMachinesPaginated
import com.fasterxml.jackson.databind.JsonNode
import com.fasterxml.jackson.databind.ObjectMapper
import com.fasterxml.jackson.databind.node.ObjectNode
import kotlinx.coroutines.flow.transform
import java.util.Scanner
import java.util.UUID
import kotlin.collections.ArrayList
import kotlin.system.exitProcess

/**
 To run this code example, place the chat_sfn_state_machine.json file into your
 project's resources folder.

 You can obtain the JSON file to create a state machine in the following GitHub
 location:
```

```
 https://github.com/awsdocs/aws-doc-sdk-examples/tree/main/resources/sample_files

 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This Kotlin code example performs the following tasks:

 1. List activities using a paginator.
 2. List state machines using a paginator.
 3. Creates an activity.
 4. Creates a state machine.
 5. Describes the state machine.
 6. Starts execution of the state machine and interacts with it.
 7. Describes the execution.
 8. Deletes the activity.
 9. Deletes the state machine.
 */

val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <roleARN> <activityName> <stateMachineName>

    Where:
        roleName - The name of the IAM role to create for this state machine.
        activityName - The name of an activity to create.
        stateMachineName - The name of the state machine to create.
    """

    if (args.size != 3) {
        println(usage)
        exitProcess(0)
    }

    val roleName = args[0]
    val activityName = args[1]
    val stateMachineName = args[2]
    val sc = Scanner(System.`in`)
    var action = false
```

```
    val polJSON = """{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "",
            "Effect": "Allow",
            "Principal": {
                "Service": "states.amazonaws.com"
            },
            "Action": "sts:AssumeRole"
        }
    ]
    }"""

    println(DASHES)
    println("Welcome to the AWS Step Functions example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. List activities using a Paginator.")
    listActivitesPagnator()
    println(DASHES)

    println(DASHES)
    println("2. List state machines using a paginator.")
    listStatemachinesPagnator()
    println(DASHES)

    println(DASHES)
    println("3. Create a new activity.")
    val activityArn = createActivity(activityName)
    println("The ARN of the Activity is $activityArn")
    println(DASHES)

    // Get JSON to use for the state machine and place the activityArn value into
it.
    val stream = GetStream()
    val jsonString = stream.getStream()

    // Modify the Resource node.
    val objectMapper = ObjectMapper()
    val root: JsonNode = objectMapper.readTree(jsonString)
```

```
    (root.path("States").path("GetInput") as ObjectNode).put("Resource",
activityArn)

    // Convert the modified Java object back to a JSON string.
    val stateDefinition = objectMapper.writeValueAsString(root)
    println(stateDefinition)

    println(DASHES)
    println("4. Create a state machine.")
    val roleARN = createIAMRole(roleName, polJSON)
    val stateMachineArn = createMachine(roleARN, stateMachineName,
stateDefinition)
    println("The ARN of the state machine is $stateMachineArn")
    println(DASHES)

    println(DASHES)
    println("5. Describe the state machine.")
    describeStateMachine(stateMachineArn)
    println("What should ChatSFN call you?")
    val userName = sc.nextLine()
    println("Hello $userName")
    println(DASHES)

    println(DASHES)
    // The JSON to pass to the StartExecution call.
    val executionJson = "{ \"name\" : \"$userName\" }"
    println(executionJson)
    println("6. Start execution of the state machine and interact with it.")
    val runArn = startWorkflow(stateMachineArn, executionJson)
    println("The ARN of the state machine execution is $runArn")
    var myList: List<String>
    while (!action) {
        myList = getActivityTask(activityArn)
        println("ChatSFN: " + myList[1])
        println("$userName please specify a value.")
        val myAction = sc.nextLine()
        if (myAction.compareTo("done") == 0) {
            action = true
        }
        println("You have selected $myAction")
        val taskJson = "{ \"action\" : \"$myAction\" }"
        println(taskJson)
        sendTaskSuccess(myList[0], taskJson)
    }
```

```
    println(DASHES)

    println(DASHES)
    println("7. Describe the execution.")
    describeExe(runArn)
    println(DASHES)

    println(DASHES)
    println("8. Delete the activity.")
    deleteActivity(activityArn)
    println(DASHES)

    println(DASHES)
    println("9. Delete the state machines.")
    deleteMachine(stateMachineArn)
    println(DASHES)

    println(DASHES)
    println("The AWS Step Functions example scenario is complete.")
    println(DASHES)
}

suspend fun listStatemachinesPagnator() {
    val machineRequest = ListStateMachinesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.listStateMachinesPaginated(machineRequest)
            .transform { it.stateMachines?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(" The state machine ARN is ${obj.stateMachineArn}")
            }
    }
}

suspend fun listActivitesPagnator() {
    val activitiesRequest = ListActivitiesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.listActivitiesPaginated(activitiesRequest)
            .transform { it.activities?.forEach { obj -> emit(obj) } }
```

```
            .collect { obj ->
                println(" The activity ARN is ${obj.activityArn}")
            }
    }
}

suspend fun deleteMachine(stateMachineArnVal: String?) {
    val deleteStateMachineRequest = DeleteStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteStateMachine(deleteStateMachineRequest)
        println("$stateMachineArnVal was successfully deleted.")
    }
}

suspend fun deleteActivity(actArn: String?) {
    val activityRequest = DeleteActivityRequest {
        activityArn = actArn
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteActivity(activityRequest)
        println("You have deleted $actArn")
    }
}

suspend fun describeExe(executionArnVal: String?) {
    val executionRequest = DescribeExecutionRequest {
        executionArn = executionArnVal
    }

    var status = ""
    var hasSucceeded = false
    while (!hasSucceeded) {
        SfnClient { region = "us-east-1" }.use { sfnClient ->
            val response = sfnClient.describeExecution(executionRequest)
            status = response.status.toString()
            if (status.compareTo("RUNNING") == 0) {
                println("The state machine is still running, let's wait for it to
 finish.")
                Thread.sleep(2000)
            } else if (status.compareTo("SUCCEEDED") == 0) {
```

```
                println("The Step Function workflow has succeeded")
                hasSucceeded = true
            } else {
                println("The Status is neither running or succeeded")
            }
        }
    }
    println("The Status is $status")
}

suspend fun sendTaskSuccess(token: String?, json: String?) {
    val successRequest = SendTaskSuccessRequest {
        taskToken = token
        output = json
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.sendTaskSuccess(successRequest)
    }
}

suspend fun getActivityTask(actArn: String?): List<String> {
    val myList: MutableList<String> = ArrayList()
    val getActivityTaskRequest = GetActivityTaskRequest {
        activityArn = actArn
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getActivityTask(getActivityTaskRequest)
        myList.add(response.taskToken.toString())
        myList.add(response.input.toString())
        return myList
    }
}

suspend fun startWorkflow(stateMachineArnVal: String?, jsonEx: String?): String?
 {
    val uuid = UUID.randomUUID()
    val uuidValue = uuid.toString()
    val executionRequest = StartExecutionRequest {
        input = jsonEx
        stateMachineArn = stateMachineArnVal
        name = uuidValue
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.startExecution(executionRequest)
```

```
        return response.executionArn
    }
}

suspend fun describeStateMachine(stateMachineArnVal: String?) {
    val stateMachineRequest = DescribeStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.describeStateMachine(stateMachineRequest)
        println("The name of the State machine is ${response.name}")
        println("The status of the State machine is ${response.status}")
        println("The ARN value of the State machine is
 ${response.stateMachineArn}")
        println("The role ARN value is ${response.roleArn}")
    }
}

suspend fun createMachine(roleARNVal: String?, stateMachineName: String?,
 jsonVal: String?): String? {
    val machineRequest = CreateStateMachineRequest {
        definition = jsonVal
        name = stateMachineName
        roleArn = roleARNVal
        type = StateMachineType.Standard
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createStateMachine(machineRequest)
        return response.stateMachineArn
    }
}

suspend fun createIAMRole(roleNameVal: String?, polJSON: String?): String? {
    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = polJSON
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createRole(request)
        return response.role?.arn
    }
```

```
}

suspend fun createActivity(activityName: String): String? {
    val activityRequest = CreateActivityRequest {
        name = activityName
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createActivity(activityRequest)
        return response.activityArn
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution
  - DescribeStateMachine
  - GetActivityTask
  - ListActivities
  - ListStateMachines
  - SendTaskSuccess
  - StartExecution
  - StopExecution

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class StateMachineScenario:
    """Runs an interactive scenario that shows how to get started using Step
 Functions."""

    def __init__(self, activity, state_machine, iam_client):
        """
        :param activity: An object that wraps activity actions.
        :param state_machine: An object that wraps state machine actions.
        :param iam_client: A Boto3 AWS Identity and Access Management (IAM)
 client.
        """
        self.activity = activity
        self.state_machine = state_machine
        self.iam_client = iam_client
        self.state_machine_role = None

    def prerequisites(self, state_machine_role_name):
        """
        Finds or creates an IAM role that can be assumed by Step Functions.
        A role of this kind is required to create a state machine.
        The state machine used in this example does not call any additional
 services,
        so it needs no additional permissions.

        :param state_machine_role_name: The name of the role.
        :return: Data about the role.
        """
        trust_policy = {
            "Version": "2012-10-17",
            "Statement": [
                {
```

```
                    "Sid": "",
                    "Effect": "Allow",
                    "Principal": {"Service": "states.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        try:
            role = self.iam_client.get_role(RoleName=state_machine_role_name)
            print(f"Prerequisite IAM role {state_machine_role_name} already
exists.")
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                role = None
            else:
                logger.error(
                    "Couldn't get prerequisite IAM role %s. Here's why: %s: %s",
                    state_machine_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        if role is None:
            try:
                role = self.iam_client.create_role(
                    RoleName=state_machine_role_name,
                    AssumeRolePolicyDocument=json.dumps(trust_policy),
                )
            except ClientError as err:
                logger.error(
                    "Couldn't create prerequisite IAM role %s. Here's why: %s:
%s",
                    state_machine_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        self.state_machine_role = role["Role"]

    def find_or_create_activity(self, activity_name):
        """
        Finds or creates a Step Functions activity.

        :param activity_name: The name of the activity.
```

```
        :return: The Amazon Resource Name (ARN) of the activity.
        """
        print("First, let's set up an activity and state machine.")
        activity_arn = self.activity.find(activity_name)
        if activity_arn is None:
            activity_arn = self.activity.create(activity_name)
            print(
                f"Activity {activity_name} created. Its Amazon Resource Name
(ARN) is "
                f"{activity_arn}."
            )
        else:
            print(f"Activity {activity_name} already exists.")
        return activity_arn

    def find_or_create_state_machine(
        self, state_machine_name, activity_arn, state_machine_file
    ):
        """
        Finds or creates a Step Functions state machine.

        :param state_machine_name: The name of the state machine.
        :param activity_arn: The ARN of an activity that is used as a step in the
state
                                machine. This ARN is injected into the state machine
                                definition that's used to create the state machine.
        :param state_machine_file: The path to a file containing the state
machine
                                       definition.
        :return: The ARN of the state machine.
        """
        state_machine_arn = self.state_machine.find(state_machine_name)
        if state_machine_arn is None:
            with open(state_machine_file) as state_machine_file:
                state_machine_def = state_machine_file.read().replace(
                    "{{DOC_EXAMPLE_ACTIVITY_ARN}}", activity_arn
                )
                state_machine_arn = self.state_machine.create(
                    state_machine_name,
                    state_machine_def,
                    self.state_machine_role["Arn"],
                )
            print(f"State machine {state_machine_name} created.")
        else:
```

```
            print(f"State machine {state_machine_name} already exists.")
        print("-" * 88)
        print(f"Here's some information about state machine
{state_machine_name}:")
        state_machine_info = self.state_machine.describe(state_machine_arn)
        for field in ["name", "status", "stateMachineArn", "roleArn"]:
            print(f"\t{field}: {state_machine_info[field]}")
        return state_machine_arn

    def run_state_machine(self, state_machine_arn, activity_arn):
        """
        Run the state machine. The state machine used in this example is a simple
        chat simulation. It contains an activity step in a loop that is used for
user
        interaction. When the state machine gets to the activity step, it waits
for
        an external application to get task data and submit a response. This
function
        acts as the activity application by getting task input and responding
with
        user input.

        :param state_machine_arn: The ARN of the state machine.
        :param activity_arn: The ARN of the activity used as a step in the state
machine.
        :return: The ARN of the run.
        """
        print(
            f"Let's run the state machine. It's a simplistic, non-AI chat
simulator "
            f"we'll call ChatSFN."
        )
        user_name = q.ask("What should ChatSFN call you? ", q.non_empty)
        run_input = {"name": user_name}
        print("Starting state machine...")
        run_arn = self.state_machine.start(state_machine_arn,
json.dumps(run_input))
        action = None
        while action != "done":
            activity_task = self.activity.get_task(activity_arn)
            task_input = json.loads(activity_task["input"])
            print(f"ChatSFN: {task_input['message']}")
            action = task_input["actions"][
                q.choose("What now? ", task_input["actions"])
```

```
            ]
            task_response = {"action": action}
            self.activity.send_task_success(
                activity_task["taskToken"], json.dumps(task_response)
            )
        return run_arn

    def finish_state_machine_run(self, run_arn):
        """
        Wait for the state machine run to finish, then print final status and
output.

        :param run_arn: The ARN of the run to retrieve.
        """
        print(f"Let's get the final output from the state machine:")
        status = "RUNNING"
        while status == "RUNNING":
            run_output = self.state_machine.describe_run(run_arn)
            status = run_output["status"]
            if status == "RUNNING":
                print(
                    "The state machine is still running, let's wait for it to
finish."
                )
                wait(1)
            elif status == "SUCCEEDED":
                print(f"ChatSFN: {json.loads(run_output['output'])['message']}")
            else:
                print(f"Run status: {status}.")

    def cleanup(
        self,
        state_machine_name,
        state_machine_arn,
        activity_name,
        activity_arn,
        state_machine_role_name,
    ):
        """
        Clean up resources created by this example.

        :param state_machine_name: The name of the state machine.
        :param state_machine_arn: The ARN of the state machine.
        :param activity_name: The name of the activity.
```

```
        :param activity_arn: The ARN of the activity.
        :param state_machine_role_name: The name of the role used by the state
machine.
        """
        if q.ask(
            "Do you want to delete the state machine, activity, and role created
for this "
            "example? (y/n) ",
            q.is_yesno,
        ):
            self.state_machine.delete(state_machine_arn)
            print(f"Deleted state machine {state_machine_name}.")
            self.activity.delete(activity_arn)
            print(f"Deleted activity {activity_name}.")
            self.iam_client.delete_role(RoleName=state_machine_role_name)
            print(f"Deleted role {state_machine_role_name}.")

    def run_scenario(self, activity_name, state_machine_name):
        print("-" * 88)
        print("Welcome to the AWS Step Functions state machines demo.")
        print("-" * 88)

        activity_arn = self.find_or_create_activity(activity_name)
        state_machine_arn = self.find_or_create_state_machine(
            state_machine_name,
            activity_arn,
            "../../../resources/sample_files/chat_sfn_state_machine.json",
        )
        print("-" * 88)
        run_arn = self.run_state_machine(state_machine_arn, activity_arn)
        print("-" * 88)
        self.finish_state_machine_run(run_arn)
        print("-" * 88)
        self.cleanup(
            state_machine_name,
            state_machine_arn,
            activity_name,
            activity_arn,
            self.state_machine_role["RoleName"],
        )

        print("-" * 88)
        print("\nThanks for watching!")
        print("-" * 88)
```

```
if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    try:
        stepfunctions_client = boto3.client("stepfunctions")
        iam_client = boto3.client("iam")
        scenario = StateMachineScenario(
            Activity(stepfunctions_client),
            StateMachine(stepfunctions_client),
            iam_client,
        )
        scenario.prerequisites("doc-example-state-machine-chat")
        scenario.run_scenario("doc-example-activity", "doc-example-state-
machine")
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Definir uma classe que envolva as ações de máquina de estado.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name, definition, role_arn):
        """
        Creates a state machine with the specific definition. The state machine
 assumes
        the provided role before it starts a run.

        :param name: The name to give the state machine.
        :param definition: The Amazon States Language definition of the steps in
 the
                           the state machine.
        :param role_arn: The Amazon Resource Name (ARN) of the role that is
 assumed by
```

```
                        Step Functions when the state machine is run.
        :return: The ARN of the newly created state machine.
        """
        try:
            response = self.stepfunctions_client.create_state_machine(
                name=name, definition=definition, roleArn=role_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't create state machine %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["stateMachineArn"]


    def find(self, name):
        """
        Find a state machine by name. This requires listing the state machines
until
        one is found with a matching name.

        :param name: The name of the state machine to search for.
        :return: The ARN of the state machine if found; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_state_machines")
            for page in paginator.paginate():
                for state_machine in page.get("stateMachines", []):
                    if state_machine["name"] == name:
                        return state_machine["stateMachineArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list state machines. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
    def describe(self, state_machine_arn):
        """
        Get data about a state machine.

        :param state_machine_arn: The ARN of the state machine to look up.
        :return: The retrieved state machine data.
        """
        try:
            response = self.stepfunctions_client.describe_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def start(self, state_machine_arn, run_input):
        """
        Start a run of a state machine with a specified input. A run is also
known
        as an "execution" in Step Functions.

        :param state_machine_arn: The ARN of the state machine to run.
        :param run_input: The input to the state machine, in JSON format.
        :return: The ARN of the run. This can be used to get information about
the run,
                 including its current status and final output.
        """
        try:
            response = self.stepfunctions_client.start_execution(
                stateMachineArn=state_machine_arn, input=run_input
            )
        except ClientError as err:
            logger.error(
                "Couldn't start state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["executionArn"]


    def describe_run(self, run_arn):
        """
        Get data about a state machine run, such as its current status or final
output.

        :param run_arn: The ARN of the run to look up.
        :return: The retrieved run data.
        """
        try:
            response = self.stepfunctions_client.describe_execution(
                executionArn=run_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe run %s. Here's why: %s: %s",
                run_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def delete(self, state_machine_arn):
        """
        Delete a state machine and all of its run data.

        :param state_machine_arn: The ARN of the state machine to delete.
        """
        try:
            response = self.stepfunctions_client.delete_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete state machine %s. Here's why: %s: %s",
```

```
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

Definir uma classe que envolva as ações de atividade.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name):
        """
        Create an activity.

        :param name: The name of the activity to create.
        :return: The Amazon Resource Name (ARN) of the newly created activity.
        """
        try:
            response = self.stepfunctions_client.create_activity(name=name)
        except ClientError as err:
            logger.error(
                "Couldn't create activity %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["activityArn"]
```

```
    def find(self, name):
        """
        Find an activity by name. This requires listing activities until one is
found
        with a matching name.

        :param name: The name of the activity to search for.
        :return: If found, the ARN of the activity; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_activities")
            for page in paginator.paginate():
                for activity in page.get("activities", []):
                    if activity["name"] == name:
                        return activity["activityArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list activities. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_task(self, activity_arn):
        """
        Gets task data for an activity. When a state machine is waiting for the
        specified activity, a response is returned with data from the state
machine.
        When a state machine is not waiting, this call blocks for 60 seconds.

        :param activity_arn: The ARN of the activity to get task data for.
        :return: The task data for the activity.
        """
        try:
            response = self.stepfunctions_client.get_activity_task(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't get a task for activity %s. Here's why: %s: %s",
```

```
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def send_task_success(self, task_token, task_response):
        """
        Sends a success response to a waiting activity step. A state machine with
an
        activity step waits for the activity to get task data and then respond
with
        either success or failure before it resumes processing.

        :param task_token: The token associated with the task. This is included
in the
                           response to the get_activity_task action and must be
sent
                           without modification.
        :param task_response: The response data from the activity. This data is
                              received and processed by the state machine.
        """
        try:
            self.stepfunctions_client.send_task_success(
                taskToken=task_token, output=task_response
            )
        except ClientError as err:
            logger.error(
                "Couldn't send task success. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self, activity_arn):
        """
        Delete an activity.

        :param activity_arn: The ARN of the activity to delete.
        """
```

```
        try:
            response = self.stepfunctions_client.delete_activity(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution
  - DescribeStateMachine
  - GetActivityTask
  - ListActivities
  - ListStateMachines
  - SendTaskSuccess
  - StartExecution
  - StopExecution

Crie e orquestre aplicativos generativos de IA com Amazon Bedrock e Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

Python

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock

- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos entre serviços para Step Functions usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Step Functions com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de mensageiro com o Step Functions
- Usar Step Functions para invocar funções do Lambda

Criar uma aplicação de mensageiro com o Step Functions

O exemplo de código a seguir mostra como criar uma aplicação de mensageiro do AWS Step Functions que recupera registros de mensagens de uma tabela de banco de dados.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o AWS Step Functions para criar uma aplicação de mensageiro que recupere registros de mensagens de uma tabela do Amazon DynamoDB e os envia com o Amazon Simple Queue Service (Amazon SQS). A máquina de estado se integra a uma função do AWS Lambda para verificar o banco de dados em busca de mensagens não enviadas.

- Crie uma máquina de estado que recupere e atualize registros de mensagens de uma tabela do Amazon DynamoDB.
- Atualize a definição de máquina de estado para enviar mensagens ao Amazon Simple Queue Service (Amazon SQS).
- Inicie e interrompa execuções da máquina de estado.
- Conecte-se ao Lambda, ao DynamoDB e ao Amazon SQS por meio de uma máquina de estado usando integrações de serviço.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

Usar Step Functions para invocar funções do Lambda

Os exemplos de código a seguir mostram como criar um máquina de estado do AWS Step Functions que invoca a funções do AWS Lambda em sequência.

Java

SDK para Java 2.x

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for Java 2.x. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

JavaScript

SDK para JavaScript (v3)

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for JavaScript. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

O Lambda é um serviço computacional que permite executar código sem provisionar ou gerenciar servidores. O Step Functions é um serviço de orquestração sem servidor que permite combinar funções do Lambda e outros serviços da AWS para criar aplicações essenciais aos negócios.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Exemplos de código para o AWS STS usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Security Token Service (AWS STS) com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do AWS STS – Mais informações sobre o AWS STS.
- Referência da API do AWS STS – Detalhes sobre todas as ações disponíveis do AWS STS.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o AWS STS usando AWS SDKs
  - Assumir uma função com o AWS STS usando um AWS SDK
  - Obtenha um token de sessão com o AWS STS usando um AWS SDK
- Cenários para o AWS STS usando AWS SDKs
  - Assumir um perfil do IAM que exija um token de MFA com o AWS STS usando um AWS SDK
  - Crie uma URL com o AWS STS para usuários federados usando um AWS SDK
  - Obtenha um token de sessão que exija um token de MFA com o AWS STS usando um AWS SDK

Ações para o AWS STS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Security Token Service (AWS STS) com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o AWS STS usando AWS SDKs.

Exemplos

- Assumir uma função com o AWS STS usando um AWS SDK
- Obtenha um token de sessão com o AWS STS usando um AWS SDK

Assumir uma função com o AWS STS usando um AWS SDK

Os exemplos de código a seguir mostram como assumir uma função com o AWS STS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Assumir um perfil do IAM que exija um token de MFA
- Criar um URL para usuários federados usando

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.SecurityToken;
using Amazon.SecurityToken.Model;

namespace AssumeRoleExample
{
    class AssumeRole
    {
        /// <summary>
        /// This example shows how to use the AWS Security Token
        /// Service (AWS STS) to assume an IAM role.
        ///
        /// NOTE: It is important that the role that will be assumed has a
        /// trust relationship with the account that will assume the role.
        ///
        /// Before you run the example, you need to create the role you want to
        /// assume and have it trust the IAM account that will assume that role.
        ///
        /// See https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_create.html
        /// for help in working with roles.
        /// </summary>

        private static readonly RegionEndpoint REGION = RegionEndpoint.USWest2;

        static async Task Main()
        {
            // Create the SecurityToken client and then display the identity of
 the
            // default user.
```

```
            var roleArnToAssume = "arn:aws:iam::123456789012:role/
testAssumeRole";

            var client = new
 Amazon.SecurityToken.AmazonSecurityTokenServiceClient(REGION);

            // Get and display the information about the identity of the default
 user.
            var callerIdRequest = new GetCallerIdentityRequest();
            var caller = await client.GetCallerIdentityAsync(callerIdRequest);
            Console.WriteLine($"Original Caller: {caller.Arn}");

            // Create the request to use with the AssumeRoleAsync call.
            var assumeRoleReq = new AssumeRoleRequest()
            {
                DurationSeconds = 1600,
                RoleSessionName = "Session1",
                RoleArn = roleArnToAssume
            };

            var assumeRoleRes = await client.AssumeRoleAsync(assumeRoleReq);

            // Now create a new client based on the credentials of the caller
 assuming the role.
            var client2 = new AmazonSecurityTokenServiceClient(credentials:
 assumeRoleRes.Credentials);

            // Get and display information about the caller that has assumed the
 defined role.
            var caller2 = await client2.GetCallerIdentityAsync(callerIdRequest);
            Console.WriteLine($"AssumedRole Caller: {caller2.Arn}");
        }
    }
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for .NET da API.

Bash

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function sts_assume_role
#
# This function assumes a role in the AWS account and returns the temporary
#  credentials.
#
# Parameters:
#       -n role_session_name -- The name of the session.
#       -r role_arn -- The ARN of the role to assume.
#
# Returns:
```

```
#       [access_key_id, secret_access_key, session_token]
#     And:
#       0 - If successful.
#       1 - If an error occurred.
##############################################################################
function sts_assume_role() {
  local role_session_name role_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function sts_assume_role"
    echo "Assumes a role in the AWS account and returns the temporary
 credentials:"
    echo "  -n role_session_name -- The name of the session."
    echo "  -r role_arn -- The ARN of the role to assume."
    echo ""
  }

  while getopts n:r:h option; do
    case "${option}" in
      n) role_session_name=${OPTARG} ;;
      r) role_arn=${OPTARG} ;;
      h)
        usage
        return 0
        ;;
      \?)
        ech o"Invalid parameter"
        usage
        return 1
        ;;
    esac
  done

  response=$(aws sts assume-role \
    --role-session-name "$role_session_name" \
    --role-arn "$role_arn" \
    --output text \
    --query "Credentials.[AccessKeyId, SecretAccessKey, SessionToken]")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
```

```
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-role operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte AssumeRoleem Referência de AWS CLI Comandos.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::STS::assumeRole(const Aws::String &roleArn,
                             const Aws::String &roleSessionName,
                             const Aws::String &externalId,
                             Aws::Auth::AWSCredentials &credentials,
                             const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::STS::STSClient sts(clientConfig);
    Aws::STS::Model::AssumeRoleRequest sts_req;

    sts_req.SetRoleArn(roleArn);
    sts_req.SetRoleSessionName(roleSessionName);
    sts_req.SetExternalId(externalId);

    const Aws::STS::Model::AssumeRoleOutcome outcome = sts.AssumeRole(sts_req);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error assuming IAM role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

```
    else {
        std::cout << "Credentials successfully retrieved." << std::endl;
        const Aws::STS::Model::AssumeRoleResult result = outcome.GetResult();
        const Aws::STS::Model::Credentials &temp_credentials =
 result.GetCredentials();

        // Store temporary credentials in return argument.
        // Note: The credentials object returned by assumeRole differs
        // from the AWSCredentials object used in most situations.
        credentials.SetAWSAccessKeyId(temp_credentials.GetAccessKeyId());
        credentials.SetAWSSecretKey(temp_credentials.GetSecretAccessKey());
        credentials.SetSessionToken(temp_credentials.GetSessionToken());
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for C++ da API.

CLI

AWS CLI

Como assumir um perfil

O comando `assume-role`, apresentado a seguir, recupera um conjunto de credenciais de curto prazo para o perfil do IAM `s3-access-example`.

```
aws sts assume-role \
    --role-arn arn:aws:iam::123456789012:role/xaccounts3access \
    --role-session-name s3-access-example
```

Saída:

```
{
    "AssumedRoleUser": {
        "AssumedRoleId": "AROA3XFRBF535PLBIFPI4:s3-access-example",
        "Arn": "arn:aws:sts::123456789012:assumed-role/xaccounts3access/s3-
access-example"
    },
    "Credentials": {
```

```
        "SecretAccessKey": "9drTJvcXLB89EXAMPLELB8923FB892xMFI",
        "SessionToken": "AQoXdzELDDY//////////
wEaoAK1wvxJY12r2IrDFT2IvAzTCn3zHoZ7YNtpiQLF0MqZye/
qwjzP2iEXAMPLEbw/m3hsj8VBTkPORGvr9jM5sgP+w9IZWZnU+LWhmg
+a5fDi2oTGUYcdg9uexQ4mtCHIHfi4citgqZTgco40Yqr4lIlo4V2b2Dyauk0eYFNebHtYlFVgAUj
+7Indz3LU0aTWk1WKIjHmmMCIoTkyYp/k7kUG7moeEYKSitwQIi6Gjn+nyzM
+PtoA3685ixzv0R7i5rjQi0YE0lf1oeie3bDiNHncmzosRM6SFiPzSvp6h/32xQuZsjcypmwsPSDtTPYcs0+YN/8B
IcrxSpnWEXAMPLEXSDFTAQAM6Dl9zR0tXoybnlrZIwMLlMi1Kcgo5OytwU=",
        "Expiration": "2016-03-15T00:05:07Z",
        "AccessKeyId": "ASIAJEXAMPLEXEG2JICEA"
    }
}
```

A saída do comando contém uma chave de acesso, uma chave secreta e um token de sessão que você pode usar para se autenticar na AWS.

Para o uso da AWS CLI, é possível configurar um perfil nomeado associado a um perfil. Ao usar o perfil, a AWS CLI chamará assume-role e gerenciará credenciais para você. Para obter mais informações, consulte Uso de perfis do IAM na AWS CLI no Guia do usuário da AWS CLI.

- Para obter detalhes da API, consulte AssumeRoleem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sts.StsClient;
import software.amazon.awssdk.services.sts.model.AssumeRoleRequest;
import software.amazon.awssdk.services.sts.model.StsException;
import software.amazon.awssdk.services.sts.model.AssumeRoleResponse;
import software.amazon.awssdk.services.sts.model.Credentials;
import java.time.Instant;
import java.time.ZoneId;
```

```
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * To make this code example work, create a Role that you want to assume.
 * Then define a Trust Relationship in the AWS Console. You can use this as an
 * example:
 *
 * {
 * "Version": "2012-10-17",
 * "Statement": [
 * {
 * "Effect": "Allow",
 * "Principal": {
 * "AWS": "<Specify the ARN of your IAM user you are using in this code
 * example>"
 * },
 * "Action": "sts:AssumeRole"
 * }
 * ]
 * }
 *
 * For more information, see "Editing the Trust Relationship for an Existing
 * Role" in the AWS Directory Service guide.
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AssumeRole {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleArn> <roleSessionName>\s

                Where:
                    roleArn - The Amazon Resource Name (ARN) of the role to
 assume (for example, rn:aws:iam::000008047983:role/s3role).\s
```

```
                    roleSessionName - An identifier for the assumed role session
(for example, mysession).\s
               """;

       if (args.length != 2) {
           System.out.println(usage);
           System.exit(1);
       }

       String roleArn = args[0];
       String roleSessionName = args[1];
       Region region = Region.US_EAST_1;
       StsClient stsClient = StsClient.builder()
               .region(region)
               .build();

       assumeGivenRole(stsClient, roleArn, roleSessionName);
       stsClient.close();
   }

   public static void assumeGivenRole(StsClient stsClient, String roleArn,
String roleSessionName) {
       try {
           AssumeRoleRequest roleRequest = AssumeRoleRequest.builder()
                   .roleArn(roleArn)
                   .roleSessionName(roleSessionName)
                   .build();

           AssumeRoleResponse roleResponse = stsClient.assumeRole(roleRequest);
           Credentials myCreds = roleResponse.credentials();

           // Display the time when the temp creds expire.
           Instant exTime = myCreds.expiration();
           String tokenInfo = myCreds.sessionToken();

           // Convert the Instant to readable date.
           DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                   .withLocale(Locale.US)
                   .withZone(ZoneId.systemDefault());

           formatter.format(exTime);
           System.out.println("The token " + tokenInfo + "  expires on " +
exTime);
```

```
        } catch (StsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
import { STSClient } from "@aws-sdk/client-sts";
// Set the AWS Region.
const REGION = "us-east-1";
// Create an AWS STS service client object.
export const client = new STSClient({ region: REGION });
```

Assuma um perfil do IAM.

```
import { AssumeRoleCommand } from "@aws-sdk/client-sts";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Returns a set of temporary security credentials that you can use to
```

```
    // access Amazon Web Services resources that you might not normally
    // have access to.
    const command = new AssumeRoleCommand({
      // The Amazon Resource Name (ARN) of the role to assume.
      RoleArn: "ROLE_ARN",
      // An identifier for the assumed role session.
      RoleSessionName: "session1",
      // The duration, in seconds, of the role session. The value specified
      // can range from 900 seconds (15 minutes) up to the maximum session
      // duration set for the role.
      DurationSeconds: 900,
    });
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
const AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

var roleToAssume = {
  RoleArn: "arn:aws:iam::123456789012:role/RoleName",
  RoleSessionName: "session1",
  DurationSeconds: 900,
};
var roleCreds;
```

```
// Create the STS service object
var sts = new AWS.STS({ apiVersion: "2011-06-15" });

//Assume Role
sts.assumeRole(roleToAssume, function (err, data) {
  if (err) console.log(err, err.stack);
  else {
    roleCreds = {
      accessKeyId: data.Credentials.AccessKeyId,
      secretAccessKey: data.Credentials.SecretAccessKey,
      sessionToken: data.Credentials.SessionToken,
    };
    stsGetCallerIdentity(roleCreds);
  }
});

//Get Arn of current identity
function stsGetCallerIdentity(creds) {
  var stsParams = { credentials: creds };
  // Create STS service object
  var sts = new AWS.STS(stsParams);

  sts.getCallerIdentity({}, function (err, data) {
    if (err) {
      console.log(err, err.stack);
    } else {
      console.log(data.Arn);
    }
  });
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Assuma um perfil do IAM que exija um token de MFA e use credenciais temporárias para listar buckets do Amazon S3 para a conta.

```
def list_buckets_from_assumed_role_with_mfa(
    assume_role_arn, session_name, mfa_serial_number, mfa_totp, sts_client
):
    """
    Assumes a role from another account and uses the temporary credentials from
    that role to list the Amazon S3 buckets that are owned by the other account.
    Requires an MFA device serial number and token.

    The assumed role must grant permission to list the buckets in the other
 account.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    :param mfa_serial_number: The serial number of the MFA device. For a virtual
 MFA
                              device, this is an ARN.
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the
 role.
    """
    response = sts_client.assume_role(
        RoleArn=assume_role_arn,
        RoleSessionName=session_name,
        SerialNumber=mfa_serial_number,
        TokenCode=mfa_totp,
    )
    temp_credentials = response["Credentials"]
    print(f"Assumed role {assume_role_arn} and got temporary credentials.")
```

```
    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Listing buckets for the assumed role's account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Creates an AWS Security Token Service (AWS STS) client with specified
credentials.
 # This is separated into a factory function so that it can be mocked for unit
testing.
 #
 # @param key_id [String] The ID of the access key used by the STS client.
 # @param key_secret [String] The secret part of the access key used by the STS
client.
 def create_sts_client(key_id, key_secret)
   Aws::STS::Client.new(access_key_id: key_id, secret_access_key: key_secret)
 end

 # Gets temporary credentials that can be used to assume a role.
```

```
  #
  # @param role_arn [String] The ARN of the role that is assumed when these
 credentials
  #                          are used.
  # @param sts_client [AWS::STS::Client] An AWS STS client.
  # @return [Aws::AssumeRoleCredentials] The credentials that can be used to
 assume the role.
  def assume_role(role_arn, sts_client)
    credentials = Aws::AssumeRoleCredentials.new(
      client: sts_client,
      role_arn: role_arn,
      role_session_name: "create-use-assume-role-scenario"
    )
    @logger.info("Assumed role '#{role_arn}', got temporary credentials.")
    credentials
  end
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for Ruby da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn assume_role(config: &SdkConfig, role_name: String, session_name:
 Option<String>) {
    let provider = aws_config::sts::AssumeRoleProvider::builder(role_name)
        .session_name(session_name.unwrap_or("rust_sdk_example_session".into()))
        .configure(config)
        .build()
        .await;

    let local_config = aws_config::from_env()
        .credentials_provider(provider)
        .load()
        .await;
```

```
    let client = Client::new(&local_config);
    let req = client.get_caller_identity();
    let resp = req.send().await;
    match resp {
        Ok(e) => {
            println!("UserID :               {}",
 e.user_id().unwrap_or_default());
            println!("Account:               {}",
 e.account().unwrap_or_default());
            println!("Arn    :               {}", e.arn().unwrap_or_default());
        }
        Err(e) => println!("{:?}", e),
    }
}
```

- Para obter detalhes da API, consulte a AssumeRolereferência da API AWS SDK for Rust.

Swift

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func assumeRole(role: IAMClientTypes.Role, sessionName: String)
                    async throws -> STSClientTypes.Credentials {
        let input = AssumeRoleInput(
            roleArn: role.arn,
            roleSessionName: sessionName
        )
```

```
        do {
            let output = try await stsClient.assumeRole(input: input)

            guard let credentials = output.credentials else {
                throw ServiceHandlerError.authError
            }

            return credentials
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte AssumeRolea referência da API AWS SDK for Swift.

Obtenha um token de sessão com o AWS STS usando um AWS SDK

Os exemplos de códigos apresentados a seguir demonstram como obter um token de sessão com o AWS STS e usá-lo para executar uma ação de serviço que requer um token de MFA.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Obtenha um token de sessão que requeira um token de MFA

CLI

AWS CLI

Como obter um conjunto de credenciais de curto prazo para uma identidade do IAM

O comando `get-session-token`, apresentado a seguir, recupera um conjunto de credenciais de curto prazo para a identidade do IAM que executa a chamada. As credenciais resultantes podem ser usadas para solicitações em que a autenticação multifator (MFA) é requerida pela política. As credenciais expiram 15 minutos após serem geradas.

```
aws sts get-session-token \
    --duration-seconds 900 \
    --serial-number "YourMFADeviceSerialNumber" \
    --token-code 123456
```

Saída:

```
{
    "Credentials": {
        "AccessKeyId": "ASIAIOSFODNN7EXAMPLE",
        "SecretAccessKey": "wJalrXUtnFEMI/K7MDENG/bPxRfiCYzEXAMPLEKEY",
        "SessionToken": "AQoEXAMPLEH4aoAH0gNCAPyJxz4BlCFFxWNE1OPTgk5TthT
+FvwqnKwRcOIfrRh3c/LTo6UDdyJwOOvEVPvLXCrrrUtdnniCEXAMPLE/
IvU1dYUg2RVAJBanLiHb4IgRmpRV3zrkuWJOgQs8IZZaIv2BXIa2R4OlgkBN9bkUDNCJiBeb/
AXlzBBko7b15fjrBs2+cTQtpZ3CYWFXG8C5zqx37wnOE49mRl/+OtkIKGO7fAE",
        "Expiration": "2020-05-19T18:06:10+00:00"
    }
}
```

Para obter mais informações, consulte Solicitação de credenciais de segurança temporárias no Guia do usuário do AWS IAM.

- Para obter detalhes da API, consulte GetSessionTokenem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Obtenha um token de sessão passando um token de MFA e use-o para listar buckets do Amazon S3 para a conta.

```
def list_buckets_with_session_token_with_mfa(mfa_serial_number, mfa_totp,
 sts_client):
    """
    Gets a session token with MFA credentials and uses the temporary session
    credentials to list Amazon S3 buckets.

    Requires an MFA device serial number and token.
```

```
    :param mfa_serial_number: The serial number of the MFA device. For a virtual
MFA
                              device, this is an Amazon Resource Name (ARN).
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the
role.
    """
    if mfa_serial_number is not None:
        response = sts_client.get_session_token(
            SerialNumber=mfa_serial_number, TokenCode=mfa_totp
        )
    else:
        response = sts_client.get_session_token()
    temp_credentials = response["Credentials"]

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Buckets for the account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

- Para obter detalhes da API, consulte a GetSessionTokenReferência da API AWSSDK for Python (Boto3).

Cenários para o AWS STS usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Security Token Service (AWS STS) com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Assumir um perfil do IAM que exija um token de MFA com o AWS STS usando um AWS SDK
- Crie uma URL com o AWS STS para usuários federados usando um AWS SDK
- Obtenha um token de sessão que exija um token de MFA com o AWS STS usando um AWS SDK

Assumir um perfil do IAM que exija um token de MFA com o AWS STS usando um AWS SDK

O exemplo de código a seguir mostra como assumir um perfil que exige um token de MFA.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar um perfil do IAM que conceda permissão para listar os buckets do Amazon S3.
- Criar um usuário do IAM que tenha permissão para assumir o perfil somente quando as credenciais de MFA forem fornecidas.
- Registrar um dispositivo MFA para o usuário.
- Assumir o perfil e usar credenciais temporárias para listar buckets do S3.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um usuário do IAM, registre um dispositivo de MFA e crie um perfil que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função.

```
def setup(iam_resource):
```

```
    """
    Creates a new user with no permissions.
    Creates a new virtual MFA device.
    Displays the QR code to seed the device.
    Asks for two codes from the MFA device.
    Registers the MFA device for the user.
    Creates an access key pair for the user.
    Creates a role with a policy that lets the user assume the role and requires
MFA.
    Creates a policy that allows listing Amazon S3 buckets.
    Attaches the policy to the role.
    Creates an inline policy for the user that lets the user assume the role.

    For demonstration purposes, the user is created in the same account as the
role,
    but in practice the user would likely be from another account.

    Any MFA device that can scan a QR code will work with this demonstration.
    Common choices are mobile apps like LastPass Authenticator,
    Microsoft Authenticator, or Google Authenticator.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM)
resource
                         that has permissions to create users, roles, and
policies
                         in the account.
    :return: The newly created user, user key, virtual MFA device, and role.
    """
    user = iam_resource.create_user(UserName=unique_name("user"))
    print(f"Created user {user.name}.")

    virtual_mfa_device = iam_resource.create_virtual_mfa_device(
        VirtualMFADeviceName=unique_name("mfa")
    )
    print(f"Created virtual MFA device {virtual_mfa_device.serial_number}")

    print(
        f"Showing the QR code for the device. Scan this in the MFA app of your "
        f"choice."
    )
    with open("qr.png", "wb") as qr_file:
        qr_file.write(virtual_mfa_device.qr_code_png)
    webbrowser.open(qr_file.name)
```

```
    print(f"Enter two consecutive code from your MFA device.")
    mfa_code_1 = input("Enter the first code: ")
    mfa_code_2 = input("Enter the second code: ")
    user.enable_mfa(
        SerialNumber=virtual_mfa_device.serial_number,
        AuthenticationCode1=mfa_code_1,
        AuthenticationCode2=mfa_code_2,
    )
    os.remove(qr_file.name)
    print(f"MFA device is registered with the user.")

    user_key = user.create_access_key_pair()
    print(f"Created access key pair for user.")

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    role = iam_resource.create_role(
        RoleName=unique_name("role"),
        AssumeRolePolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Principal": {"AWS": user.arn},
                        "Action": "sts:AssumeRole",
                        "Condition": {"Bool": {"aws:MultiFactorAuthPresent":
True}},
                    }
                ],
            }
        ),
    )
    print(f"Created role {role.name} that requires MFA.")

    policy = iam_resource.create_policy(
        PolicyName=unique_name("policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
```

```
                        "Action": "s3:ListAllMyBuckets",
                        "Resource": "arn:aws:s3:::*",
                    }
                ],
            }
        ),
    )
    role.attach_policy(PolicyArn=policy.arn)
    print(f"Created policy {policy.policy_name} and attached it to the role.")

    user.create_policy(
        PolicyName=unique_name("user-policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Action": "sts:AssumeRole",
                        "Resource": role.arn,
                    }
                ],
            }
        ),
    )
    print(
        f"Created an inline policy for {user.name} that lets the user assume "
        f"the role."
    )

    print("Give AWS time to propagate these new resources and connections.",
end="")
    progress_bar(10)

    return user, user_key, virtual_mfa_device, role
```

Mostre que não é permitido assumir uma função sem um token de MFA.

```
def try_to_assume_role_without_mfa(assume_role_arn, session_name, sts_client):
    """
```

```
    Shows that attempting to assume the role without sending MFA credentials
results
    in an AccessDenied error.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role to assume.
    :param session_name: The name of the STS session.
    :param sts_client: A Boto3 STS instance that has permission to assume the
role.
    """
    print(f"Trying to assume the role without sending MFA credentials...")
    try:
        sts_client.assume_role(RoleArn=assume_role_arn,
RoleSessionName=session_name)
        raise RuntimeError("Expected AccessDenied error.")
    except ClientError as error:
        if error.response["Error"]["Code"] == "AccessDenied":
            print("Got AccessDenied.")
        else:
            raise
```

Assuma o perfil que concede permissão para listar buckets do S3 passando o token de MFA necessário e mostre que os buckets podem ser listados.

```
def list_buckets_from_assumed_role_with_mfa(
    assume_role_arn, session_name, mfa_serial_number, mfa_totp, sts_client
):
    """
    Assumes a role from another account and uses the temporary credentials from
    that role to list the Amazon S3 buckets that are owned by the other account.
    Requires an MFA device serial number and token.

    The assumed role must grant permission to list the buckets in the other
account.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    :param mfa_serial_number: The serial number of the MFA device. For a virtual
MFA
                              device, this is an ARN.
```

```
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the
 role.
    """
    response = sts_client.assume_role(
        RoleArn=assume_role_arn,
        RoleSessionName=session_name,
        SerialNumber=mfa_serial_number,
        TokenCode=mfa_totp,
    )
    temp_credentials = response["Credentials"]
    print(f"Assumed role {assume_role_arn} and got temporary credentials.")

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Listing buckets for the assumed role's account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

Destrua os recursos criados para a demonstração.

```
def teardown(user, virtual_mfa_device, role):
    """
    Removes all resources created during setup.

    :param user: The demo user.
    :param role: The demo role.
    """
    for attached in role.attached_policies.all():
        policy_name = attached.policy_name
        role.detach_policy(PolicyArn=attached.arn)
        attached.delete()
        print(f"Detached and deleted {policy_name}.")
    role.delete()
    print(f"Deleted {role.name}.")
```

```
    for user_pol in user.policies.all():
        user_pol.delete()
        print("Deleted inline user policy.")
    for key in user.access_keys.all():
        key.delete()
        print("Deleted user's access key.")
    for mfa in user.mfa_devices.all():
        mfa.disassociate()
    virtual_mfa_device.delete()
    user.delete()
    print(f"Deleted {user.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(
        f"Welcome to the AWS Security Token Service assume role demo, "
        f"starring multi-factor authentication (MFA)!"
    )
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    user, user_key, virtual_mfa_device, role = setup(iam_resource)
    print(f"Created {user.name} and {role.name}.")
    try:
        sts_client = boto3.client(
            "sts", aws_access_key_id=user_key.id,
 aws_secret_access_key=user_key.secret
        )
        try_to_assume_role_without_mfa(role.arn, "demo-sts-session", sts_client)
        mfa_totp = input("Enter the code from your registered MFA device: ")
        list_buckets_from_assumed_role_with_mfa(
            role.arn,
            "demo-sts-session",
            virtual_mfa_device.serial_number,
            mfa_totp,
            sts_client,
        )
    finally:
```

```
        teardown(user, virtual_mfa_device, role)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Crie uma URL com o AWS STS para usuários federados usando um AWS SDK

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM que conceda acesso somente leitura aos recursos do Amazon S3 da conta atual.
- Obtenha um token de segurança do endpoint de federação da AWS.
- Crie um URL que possa ser usado para acessar o console com credenciais federadas.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um perfil que conceda acesso somente leitura aos recursos do S3 da conta atual.

```
def setup(iam_resource):
    """
    Creates a role that can be assumed by the current user.
    Attaches a policy that allows only Amazon S3 read-only access.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM)
 instance
                         that has the permission to create a role.
    :return: The newly created role.
```

```
    """
    role = iam_resource.create_role(
        RoleName=unique_name("role"),
        AssumeRolePolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Principal": {"AWS": iam_resource.CurrentUser().arn},
                        "Action": "sts:AssumeRole",
                    }
                ],
            }
        ),
    )
    role.attach_policy(PolicyArn="arn:aws:iam::aws:policy/
AmazonS3ReadOnlyAccess")
    print(f"Created role {role.name}.")

    print("Give AWS time to propagate these new resources and connections.",
 end="")
    progress_bar(10)

    return role
```

Obtenha um token de segurança do endpoint de federação da AWS e crie um URL que possa ser usado para acessar o console com credenciais federadas.

```
def construct_federated_url(assume_role_arn, session_name, issuer, sts_client):
    """
    Constructs a URL that gives federated users direct access to the AWS
 Management
    Console.

    1. Acquires temporary credentials from AWS Security Token Service (AWS STS)
 that
       can be used to assume a role with limited permissions.
    2. Uses the temporary credentials to request a sign-in token from the
       AWS federation endpoint.
```

```
   3. Builds a URL that can be used in a browser to navigate to the AWS
federation
      endpoint, includes the sign-in token for authentication, and redirects to
      the AWS Management Console with permissions defined by the role that was
      specified in step 1.

   :param assume_role_arn: The role that specifies the permissions that are
granted.
                           The current user must have permission to assume the
role.
   :param session_name: The name for the STS session.
   :param issuer: The organization that issues the URL.
   :param sts_client: A Boto3 STS instance that can assume the role.
   :return: The federated URL.
   """
   response = sts_client.assume_role(
       RoleArn=assume_role_arn, RoleSessionName=session_name
   )
   temp_credentials = response["Credentials"]
   print(f"Assumed role {assume_role_arn} and got temporary credentials.")

   session_data = {
       "sessionId": temp_credentials["AccessKeyId"],
       "sessionKey": temp_credentials["SecretAccessKey"],
       "sessionToken": temp_credentials["SessionToken"],
   }
   aws_federated_signin_endpoint = "https://signin.aws.amazon.com/federation"

   # Make a request to the AWS federation endpoint to get a sign-in token.
   # The requests.get function URL-encodes the parameters and builds the query
string
   # before making the request.
   response = requests.get(
       aws_federated_signin_endpoint,
       params={
           "Action": "getSigninToken",
           "SessionDuration": str(datetime.timedelta(hours=12).seconds),
           "Session": json.dumps(session_data),
       },
   )
   signin_token = json.loads(response.text)
   print(f"Got a sign-in token from the AWS sign-in federation endpoint.")
```

```
    # Make a federated URL that can be used to sign into the AWS Management
 Console.
    query_string = urllib.parse.urlencode(
        {
            "Action": "login",
            "Issuer": issuer,
            "Destination": "https://console.aws.amazon.com/",
            "SigninToken": signin_token["SigninToken"],
        }
    )
    federated_url = f"{aws_federated_signin_endpoint}?{query_string}"
    return federated_url
```

Destrua os recursos criados para a demonstração.

```
def teardown(role):
    """
    Removes all resources created during setup.

    :param role: The demo role.
    """
    for attached in role.attached_policies.all():
        role.detach_policy(PolicyArn=attached.arn)
        print(f"Detached {attached.policy_name}.")
    role.delete()
    print(f"Deleted {role.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(f"Welcome to the AWS Security Token Service federated URL demo.")
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    role = setup(iam_resource)
    sts_client = boto3.client("sts")
```

```
    try:
        federated_url = construct_federated_url(
            role.arn, "AssumeRoleDemoSession", "example.org", sts_client
        )
        print(
            "Constructed a federated URL that can be used to connect to the "
            "AWS Management Console with role-defined permissions:"
        )
        print("-" * 88)
        print(federated_url)
        print("-" * 88)
        _ = input(
            "Copy and paste the above URL into a browser to open the AWS "
            "Management Console with limited permissions. When done, press "
            "Enter to clean up and complete this demo."
        )
    finally:
        teardown(role)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Obtenha um token de sessão que exija um token de MFA com o AWS STS usando um AWS SDK

O exemplo de código a seguir mostra como obter um token de sessão que exige um token de MFA.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar um perfil do IAM que conceda permissão para listar os buckets do Amazon S3.

- Criar um usuário do IAM que tenha permissão para assumir o perfil somente quando as credenciais de MFA forem fornecidas.
- Registrar um dispositivo MFA para o usuário.
- Forneça credenciais de MFA para obter um token de sessão e use credenciais temporárias para listar buckets do S3.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário do IAM, registre um dispositivo de MFA e crie um perfil que conceda permissão para deixar o usuário listar os buckets do S3 somente quando credenciais de MFA forem usadas.

```
def setup(iam_resource):
    """
    Creates a new user with no permissions.
    Creates a new virtual multi-factor authentication (MFA) device.
    Displays the QR code to seed the device.
    Asks for two codes from the MFA device.
    Registers the MFA device for the user.
    Creates an access key pair for the user.
    Creates an inline policy for the user that lets the user list Amazon S3
 buckets,
    but only when MFA credentials are used.

    Any MFA device that can scan a QR code will work with this demonstration.
    Common choices are mobile apps like LastPass Authenticator,
    Microsoft Authenticator, or Google Authenticator.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM)
 resource
                         that has permissions to create users, MFA devices, and
                         policies in the account.
```

```
    :return: The newly created user, user key, and virtual MFA device.
    """
    user = iam_resource.create_user(UserName=unique_name("user"))
    print(f"Created user {user.name}.")

    virtual_mfa_device = iam_resource.create_virtual_mfa_device(
        VirtualMFADeviceName=unique_name("mfa")
    )
    print(f"Created virtual MFA device {virtual_mfa_device.serial_number}")

    print(
        f"Showing the QR code for the device. Scan this in the MFA app of your "
        f"choice."
    )
    with open("qr.png", "wb") as qr_file:
        qr_file.write(virtual_mfa_device.qr_code_png)
    webbrowser.open(qr_file.name)

    print(f"Enter two consecutive code from your MFA device.")
    mfa_code_1 = input("Enter the first code: ")
    mfa_code_2 = input("Enter the second code: ")
    user.enable_mfa(
        SerialNumber=virtual_mfa_device.serial_number,
        AuthenticationCode1=mfa_code_1,
        AuthenticationCode2=mfa_code_2,
    )
    os.remove(qr_file.name)
    print(f"MFA device is registered with the user.")

    user_key = user.create_access_key_pair()
    print(f"Created access key pair for user.")

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    user.create_policy(
        PolicyName=unique_name("user-policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Action": "s3:ListAllMyBuckets",
```

```
                        "Resource": "arn:aws:s3:::*",
                        "Condition": {"Bool": {"aws:MultiFactorAuthPresent":
True}},
                    }
                ],
            }
        ),
    )
    print(
        f"Created an inline policy for {user.name} that lets the user list
buckets, "
        f"but only when MFA credentials are present."
    )

    print("Give AWS time to propagate these new resources and connections.",
end="")
    progress_bar(10)

    return user, user_key, virtual_mfa_device
```

Obtenha credenciais de sessão temporárias passando um token de MFA e use-as para listar buckets do S3 para a conta.

```
def list_buckets_with_session_token_with_mfa(mfa_serial_number, mfa_totp,
 sts_client):
    """
    Gets a session token with MFA credentials and uses the temporary session
    credentials to list Amazon S3 buckets.

    Requires an MFA device serial number and token.

    :param mfa_serial_number: The serial number of the MFA device. For a virtual
 MFA
                              device, this is an Amazon Resource Name (ARN).
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the
 role.
    """
    if mfa_serial_number is not None:
        response = sts_client.get_session_token(
```

```
            SerialNumber=mfa_serial_number, TokenCode=mfa_totp
        )
    else:
        response = sts_client.get_session_token()
    temp_credentials = response["Credentials"]

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Buckets for the account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

Destrua os recursos criados para a demonstração.

```
def teardown(user, virtual_mfa_device):
    """
    Removes all resources created during setup.

    :param user: The demo user.
    :param role: The demo MFA device.
    """
    for user_pol in user.policies.all():
        user_pol.delete()
        print("Deleted inline user policy.")
    for key in user.access_keys.all():
        key.delete()
        print("Deleted user's access key.")
    for mfa in user.mfa_devices.all():
        mfa.disassociate()
    virtual_mfa_device.delete()
    user.delete()
    print(f"Deleted {user.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(
        f"Welcome to the AWS Security Token Service assume role demo, "
        f"starring multi-factor authentication (MFA)!"
    )
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    user, user_key, virtual_mfa_device = setup(iam_resource)
    try:
        sts_client = boto3.client(
            "sts", aws_access_key_id=user_key.id,
 aws_secret_access_key=user_key.secret
        )
        try:
            print("Listing buckets without specifying MFA credentials.")
            list_buckets_with_session_token_with_mfa(None, None, sts_client)
        except ClientError as error:
            if error.response["Error"]["Code"] == "AccessDenied":
                print("Got expected AccessDenied error.")
        mfa_totp = input("Enter the code from your registered MFA device: ")
        list_buckets_with_session_token_with_mfa(
            virtual_mfa_device.serial_number, mfa_totp, sts_client
        )
    finally:
        teardown(user, virtual_mfa_device)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a GetSessionTokenReferência da API AWSSDK for Python (Boto3).

Exemplos de código para o AWS Support usando AWS SDKs

Os exemplos de código a seguir mostram como usar AWS Support com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Mais atributos

- Guia do usuário do AWS Support – Mais informações sobre o AWS Support.
- Referência da API do AWS Support – Detalhes sobre todas as ações disponíveis do AWS Support.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.AWSSupport;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;

public static class HelloSupport
{
    static async Task Main(string[] args)
```

```
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the AWS Support service.
        // Use your AWS profile name, or leave it blank to use the default
 profile.
        // You must have one of the following AWS Support plans: Business,
 Enterprise On-Ramp, or Enterprise. Otherwise, an exception will be thrown.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonAWSSupport>()
            ).Build();

        // Now the client is available for injection.
        var supportClient =
 host.Services.GetRequiredService<IAmazonAWSSupport>();

        // You can use await and any of the async methods to get a response.
        var response = await supportClient.DescribeServicesAsync();
        Console.WriteLine($"\tHello AWS Support! There are
 {response.Services.Count} services available.");
    }
}
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.support.SupportClient;
import software.amazon.awssdk.services.support.model.Category;
import software.amazon.awssdk.services.support.model.DescribeServicesRequest;
```

```
import software.amazon.awssdk.services.support.model.DescribeServicesResponse;
import software.amazon.awssdk.services.support.model.Service;
import software.amazon.awssdk.services.support.model.SupportException;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * In addition, you must have the AWS Business Support Plan to use the AWS
 * Support Java API. For more information, see:
 *
 * https://aws.amazon.com/premiumsupport/plans/
 *
 * This Java example performs the following task:
 *
 * 1. Gets and displays available services.
 *
 *
 * NOTE: To see multiple operations, see SupportScenario.
 */

public class HelloSupport {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        SupportClient supportClient = SupportClient.builder()
                .region(region)
                .build();

        System.out.println("***** Step 1. Get and display available services.");
        displayServices(supportClient);
    }

    // Return a List that contains a Service name and Category name.
    public static void displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
 DescribeServicesRequest.builder()
```

```
                    .language("en")
                    .build();

            DescribeServicesResponse response =
 supportClient.describeServices(servicesRequest);
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;

                System.out.println("The Service name is: " + service.name());

                // Display the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                }
                index++;
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque `main()` para executar o exemplo.

```
import {
  DescribeServicesCommand,
  SupportClient,
} from "@aws-sdk/client-support";

// Change the value of 'region' to your preferred AWS Region.
const client = new SupportClient({ region: "us-east-1" });

const getServiceCount = async () => {
  try {
    const { services } = await client.send(new DescribeServicesCommand({}));
    return services.length;
  } catch (err) {
    if (err.name === "SubscriptionRequiredException") {
      throw new Error(
        "You must be subscribed to the AWS Support plan to use this feature.",
      );
    } else {
      throw err;
    }
  }
};

export const main = async () => {
  try {
    const count = await getServiceCount();
    console.log(`Hello, AWS Support! There are ${count} services available.`);
  } catch (err) {
    console.error("Failed to get service count: ", err.message);
  }
};
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

In addition, you must have the AWS Business Support Plan to use the AWS Support
 Java API. For more information, see:

https://aws.amazon.com/premiumsupport/plans/

This Kotlin example performs the following task:

1. Gets and displays available services.
 */

suspend fun main() {
    displaySomeServices()
}

// Return a List that contains a Service name and Category name.
suspend fun displaySomeServices() {
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }
```

```
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
                return@forEach
            }

            println("The Service name is: " + service.name)

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                index++
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeServicesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError
```

```
logger = logging.getLogger(__name__)


def hello_support(support_client):
    """
    Use the AWS SDK for Python (Boto3) to create an AWS Support client and count
    the available services in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param support_client: A Boto3 Support Client object.
    """
    try:
        print("Hello, AWS Support! Let's count the available Support services:")
        response = support_client.describe_services()
        print(f"There are {len(response['services'])} services available.")
    except ClientError as err:
        if err.response["Error"]["Code"] == "SubscriptionRequiredException":
            logger.info(
                "You must have a Business, Enterprise On-Ramp, or Enterprise
 Support "
                "plan to use the AWS Support API. \n\tPlease upgrade your
 subscription to run these "
                "examples."
            )
        else:
            logger.error(
                "Couldn't count services. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


if __name__ == "__main__":
    hello_support(boto3.client("support"))
```

- Para obter detalhes da API, consulte a DescribeServicesReferência da API AWSSDK for Python (Boto3).

Exemplos de código

- Ações para o AWS Support usando AWS SDKs
  - Adicionar uma comunicação do AWS Support a um caso usando um SDK da AWS
  - Adicionar um anexo do AWS Support a um conjunto ao usar um SDK da AWS
  - Criar um caso do AWS Support ao usar um SDK da AWS
  - Descrever um anexo para um caso do AWS Support ao usar um SDK da AWS
  - Descrever casos do AWS Support usando um SDK da AWS
  - Descrever as comunicações do AWS Support de um caso usando um SDK da AWS
  - Descrever os serviços da AWS disponíveis para os casos de suporte usando um SDK da AWS
  - Descrever os níveis de gravidade do AWS Support usando um SDK da AWS
  - Resolver um caso do AWS Support usando um SDK da AWS
- Cenários para o AWS Support usando AWS SDKs
  - Conceitos básicos dos casos do AWS Support usando um SDK da AWS

Ações para o AWS Support usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Support com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para o AWS Support usando AWS SDKs.

Exemplos

- Adicionar uma comunicação do AWS Support a um caso usando um SDK da AWS
- Adicionar um anexo do AWS Support a um conjunto ao usar um SDK da AWS
- Criar um caso do AWS Support ao usar um SDK da AWS
- Descrever um anexo para um caso do AWS Support ao usar um SDK da AWS
- Descrever casos do AWS Support usando um SDK da AWS
- Descrever as comunicações do AWS Support de um caso usando um SDK da AWS
- Descrever os serviços da AWS disponíveis para os casos de suporte usando um SDK da AWS
- Descrever os níveis de gravidade do AWS Support usando um SDK da AWS
- Resolver um caso do AWS Support usando um SDK da AWS

Adicionar uma comunicação do AWS Support a um caso usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add communication to a case, including optional attachment set ID and CC
 email addresses.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <param name="body">Body text of the communication.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set.</param>
    /// <param name="ccEmailAddresses">Optional list of CC email addresses.</
param>
    /// <returns>True if successful.</returns>
    public async Task<bool> AddCommunicationToCase(string caseId, string body,
        string? attachmentSetId = null, List<string>? ccEmailAddresses = null)
    {
        var response = await _amazonSupport.AddCommunicationToCaseAsync(
            new AddCommunicationToCaseRequest()
            {
                CaseId = caseId,
                CommunicationBody = body,
                AttachmentSetId = attachmentSetId,
                CcEmailAddresses = ccEmailAddresses
```

```
            });
        return response.Result;
    }
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void addAttachSupportCase(SupportClient supportClient, String
caseId, String attachmentSetId) {
       try {
           AddCommunicationToCaseRequest caseRequest =
AddCommunicationToCaseRequest.builder()
                   .caseId(caseId)
                   .attachmentSetId(attachmentSetId)
                   .communicationBody("Please refer to attachment for details.")
                   .build();

           AddCommunicationToCaseResponse response =
supportClient.addCommunicationToCase(caseRequest);
           if (response.result())
               System.out.println("You have successfully added a communication
to an AWS Support case");
           else
               System.out.println("There was an error adding the communication
to an AWS Support case");

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AddCommunicationToCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  let attachmentSetId;

  try {
    // Add a communication to a case.
    const response = await client.send(
      new AddCommunicationToCaseCommand({
        communicationBody: "Adding an attachment.",
        // Set value to an existing support case id.
        caseId: "CASE_ID",
        // Optional. Set value to an existing attachment set id to add
 attachments to the case.
        attachmentSetId,
      }),
    );
    console.log(response);
    return response;
  } catch (err) {
    console.error(err);
  }
```

```
};
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAttachSupportCase(caseIdVal: String?, attachmentSetIdVal: String?)
 {
    val caseRequest = AddCommunicationToCaseRequest {
        caseId = caseIdVal
        attachmentSetId = attachmentSetIdVal
        communicationBody = "Please refer to attachment for details."
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addCommunicationToCase(caseRequest)
        if (response.result) {
            println("You have successfully added a communication to an AWS
 Support case")
        } else {
            println("There was an error adding the communication to an AWS
 Support case")
        }
    }
}
```

- Para obter detalhes da API, consulte a AddCommunicationToCasereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def add_communication_to_case(self, attachment_set_id, case_id):
        """
        Add a communication and an attachment set to a case.

        :param attachment_set_id: The ID of an existing attachment set.
        :param case_id: The ID of the case.
        """
        try:
            self.support_client.add_communication_to_case(
                caseId=case_id,
                communicationBody="This is an example communication added to a
 support case.",
                attachmentSetId=attachment_set_id,
            )
```

```
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add communication. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
```

- Para obter detalhes da API, consulte a AddCommunicationToCaseReferência da API AWSSDK for Python (Boto3).

Adicionar um anexo do AWS Support a um conjunto ao usar um SDK da AWS

Os exemplos de código a seguir mostram como adicionar um anexo do AWS Support a um conjunto de anexos.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add an attachment to a set, or create a new attachment set if one does
not exist.
    /// </summary>
    /// <param name="data">The data for the attachment.</param>
    /// <param name="fileName">The file name for the attachment.</param>
    /// <param name="attachmentSetId">Optional setId for the attachment. Creates
a new attachment set if empty.</param>
    /// <returns>The setId of the attachment.</returns>
    public async Task<string> AddAttachmentToSet(MemoryStream data, string
fileName, string? attachmentSetId = null)
    {
        var response = await _amazonSupport.AddAttachmentsToSetAsync(
            new AddAttachmentsToSetRequest
            {
                AttachmentSetId = attachmentSetId,
                Attachments = new List<Attachment>
                {
                    new Attachment
                    {
                        Data = data,
                        FileName = fileName
                    }
                }
            });
        return response.AttachmentSetId;
    }
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for .NET da API.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String addAttachment(SupportClient supportClient, String
fileAttachment) {
       try {
           File myFile = new File(fileAttachment);
           InputStream sourceStream = new FileInputStream(myFile);
           SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

           Attachment attachment = Attachment.builder()
                   .fileName(myFile.getName())
                   .data(sourceBytes)
                   .build();

           AddAttachmentsToSetRequest setRequest =
AddAttachmentsToSetRequest.builder()
                   .attachments(attachment)
                   .build();

           AddAttachmentsToSetResponse response =
supportClient.addAttachmentsToSet(setRequest);
           return response.attachmentSetId();

       } catch (SupportException | FileNotFoundException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AddAttachmentsToSetCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a new attachment set or add attachments to an existing set.
    // Provide an 'attachmentSetId' value to add attachments to an existing set.
    // Use AddCommunicationToCase or CreateCase to associate an attachment set
 with a support case.
    const response = await client.send(
      new AddAttachmentsToSetCommand({
        // You can add up to three attachments per set. The size limit is 5 MB
 per attachment.
        attachments: [
          {
            fileName: "example.txt",
            data: new TextEncoder().encode("some example text"),
          },
        ],
      }),
    );
    // Use this ID in AddCommunicationToCase or CreateCase.
    console.log(response.attachmentSetId);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAttachment(fileAttachment: String): String? {
    val myFile = File(fileAttachment)
    val sourceBytes = (File(fileAttachment).readBytes())
    val attachmentVal = Attachment {
        fileName = myFile.name
        data = sourceBytes
    }

    val setRequest = AddAttachmentsToSetRequest {
        attachments = listOf(attachmentVal)
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addAttachmentsToSet(setRequest)
        return response.attachmentSetId
    }
}
```

- Para obter detalhes da API, consulte a AddAttachmentsToSetreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def add_attachment_to_set(self):
        """
        Add an attachment to a set, or create a new attachment set if one does
 not exist.

        :return: The attachment set ID.
        """
        try:
            response = self.support_client.add_attachments_to_set(
                attachments=[
                    {
                        "fileName": "attachment_file.txt",
                        "data": b"This is a sample file for attachment to a
 support case.",
```

```
                    }
                ]
            )
            new_set_id = response["attachmentSetId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add attachment. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return new_set_id
```

- Para obter detalhes da API, consulte a AddAttachmentsToSetReferência da API AWSSDK for Python (Boto3).

Criar um caso do AWS Support ao usar um SDK da AWS

Os exemplos de código a seguir mostram como criar um novo caso no AWS Support.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create a new support case.
   /// </summary>
   /// <param name="serviceCode">Service code for the new case.</param>
   /// <param name="categoryCode">Category for the new case.</param>
   /// <param name="severityCode">Severity code for the new case.</param>
   /// <param name="subject">Subject of the new case.</param>
   /// <param name="body">Body text of the new case.</param>
   /// <param name="language">Optional language support for your case.
   /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
   /// <param name="attachmentSetId">Optional Id for an attachment set for the
new case.</param>
   /// <param name="issueType">Optional issue type for the new case. Options are
"customer-service" or "technical".</param>
   /// <returns>The caseId of the new support case.</returns>
   public async Task<string> CreateCase(string serviceCode, string categoryCode,
string severityCode, string subject,
       string body, string language = "en", string? attachmentSetId = null,
string issueType = "customer-service")
   {
       var response = await _amazonSupport.CreateCaseAsync(
           new CreateCaseRequest()
           {
               ServiceCode = serviceCode,
               CategoryCode = categoryCode,
               SeverityCode = severityCode,
               Subject = subject,
               Language = language,
               AttachmentSetId = attachmentSetId,
               IssueType = issueType,
               CommunicationBody = body
```

```
            });
        return response.CaseId;
    }
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como criar um caso

O exemplo de `create-case` a seguir cria um caso de suporte para a conta da AWS.

```
aws support create-case \
    --category-code "using-aws" \
    --cc-email-addresses "myemail@example.com" \
    --communication-body "I want to learn more about an AWS service." \
    --issue-type "technical" \
    --language "en" \
    --service-code "general-info" \
    --severity-code "low" \
    --subject "Question about my account"
```

Saída:

```
{
    "caseId": "case-12345678910-2013-c4c1d2bf33c5cf47"
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte CreateCaseem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createSupportCase(SupportClient supportClient,
List<String> sevCatList, String sevLevel) {
       try {
           String serviceCode = sevCatList.get(0);
           String caseCat = sevCatList.get(1);
           CreateCaseRequest caseRequest = CreateCaseRequest.builder()
                   .categoryCode(caseCat.toLowerCase())
                   .serviceCode(serviceCode.toLowerCase())
                   .severityCode(sevLevel.toLowerCase())
                   .communicationBody("Test issue with " +
serviceCode.toLowerCase())
                   .subject("Test case, please ignore")
                   .language("en")
                   .issueType("technical")
                   .build();

           CreateCaseResponse response = supportClient.createCase(caseRequest);
           return response.caseId();

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a new case and log the case id.
    // Important: This creates a real support case in your account.
    const response = await client.send(
      new CreateCaseCommand({
        // The subject line of the case.
        subject: "IGNORE: Test case",
        // Use DescribeServices to find available service codes for each service.
        serviceCode: "service-quicksight-end-user",
        // Use DescribeSecurityLevels to find available severity codes for your
 support plan.
        severityCode: "low",
        // Use DescribeServices to find available category codes for each
 service.
        categoryCode: "end-user-support",
        // The main description of the support case.
        communicationBody: "This is a test. Please ignore.",
      }),
    );
    console.log(response.caseId);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createSupportCase(sevCatListVal: List<String>, sevLevelVal: String):
 String? {
    val serCode = sevCatListVal[0]
    val caseCategory = sevCatListVal[1]
    val caseRequest = CreateCaseRequest {
        categoryCode = caseCategory.lowercase(Locale.getDefault())
        serviceCode = serCode.lowercase(Locale.getDefault())
        severityCode = sevLevelVal.lowercase(Locale.getDefault())
        communicationBody = "Test issue with
 ${serCode.lowercase(Locale.getDefault())}"
        subject = "Test case, please ignore"
        language = "en"
        issueType = "technical"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.createCase(caseRequest)
        return response.caseId
    }
}
```

- Para obter detalhes da API, consulte a CreateCasereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def create_case(self, service, category, severity):
        """
        Create a new support case.

        :param service: The service to use for the new case.
        :param category: The category to use for the new case.
        :param severity: The severity to use for the new case.
        :return: The caseId of the new case.
        """
        try:
            response = self.support_client.create_case(
                subject="Example case for testing, ignore.",
                serviceCode=service["code"],
                severityCode=severity["code"],
```

```
                categoryCode=category["code"],
                communicationBody="Example support case body.",
                language="en",
                issueType="customer-service",
            )
            case_id = response["caseId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't create case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return case_id
```

- Para obter detalhes da API, consulte a CreateCaseReferência da API AWSSDK for Python (Boto3).

Descrever um anexo para um caso do AWS Support ao usar um SDK da AWS

Os exemplos de código a seguir mostram como descrever um anexo para um caso do AWS Support.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get description of a specific attachment.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment, usually fetched by
 describing the communications of a case.</param>
    /// <returns>The attachment object.</returns>
    public async Task<Attachment> DescribeAttachment(string attachmentId)
    {
        var response = await _amazonSupport.DescribeAttachmentAsync(
            new DescribeAttachmentRequest()
            {
                AttachmentId = attachmentId
            });
        return response.Attachment;
    }
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como descrever um anexo

O exemplo de `describe-attachment` a seguir retorna informações sobre o anexo com o ID especificado.

```
aws support describe-attachment \
    --attachment-id "attachment-KBnjRNrePd9D6Jx0-Mm00xZuDEaL2JAj_0-
gJv9qqDooTipsz3V1Nb19rCfkZneeQeDPgp8X1iVJyHH7UuhZDdNeqGoduZsPrAhyMakqlc60-
iJjL5HqyYGiT1FG8EXAMPLE"
```

Saída:

```
{
    "attachment": {
        "fileName": "troubleshoot-screenshot.png",
        "data": "base64-blob"
    }
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte DescribeAttachmentem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeAttachment(SupportClient supportClient, String
 attachId) {
        try {
            DescribeAttachmentRequest attachmentRequest =
 DescribeAttachmentRequest.builder()
                    .attachmentId(attachId)
                    .build();

            DescribeAttachmentResponse response =
 supportClient.describeAttachment(attachmentRequest);
```

```
            System.out.println("The name of the file is " +
 response.attachment().fileName());

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeAttachmentCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get the metadata and content of an attachment.
    const response = await client.send(
      new DescribeAttachmentCommand({
        // Set value to an existing attachment id.
        // Use DescribeCommunications or DescribeCases to find an attachment id.
        attachmentId: "ATTACHMENT_ID",
      }),
    );
    console.log(response.attachment?.fileName);
    return response;
  } catch (err) {
    console.error(err);
```

```
  }
};
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAttachment(attachId: String?) {
    val attachmentRequest = DescribeAttachmentRequest {
        attachmentId = attachId
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeAttachment(attachmentRequest)
        println("The name of the file is ${response.attachment?.fileName}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeAttachmentreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_attachment(self, attachment_id):
        """
        Get information about an attachment by its attachmentID.

        :param attachment_id: The ID of the attachment.
        :return: The name of the attached file.
        """
        try:
            response = self.support_client.describe_attachment(
                attachmentId=attachment_id
            )
            attached_file = response["attachment"]["fileName"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
```

```
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get attachment description. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return attached_file
```

- Para obter detalhes da API, consulte a DescribeAttachmentReferência da API AWSSDK for Python (Boto3).

Descrever casos do AWS Support usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever casos do AWS Support.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get case details for a list of case ids, optionally with date filters.
    /// </summary>
    /// <param name="caseIds">The list of case IDs.</param>
    /// <param name="displayId">Optional display ID.</param>
    /// <param name="includeCommunication">True to include communication.
 Defaults to true.</param>
    /// <param name="includeResolvedCases">True to include resolved cases.
 Defaults to false.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>A list of CaseDetails.</returns>
    public async Task<List<CaseDetails>> DescribeCases(List<string> caseIds,
 string? displayId = null, bool includeCommunication = true,
        bool includeResolvedCases = false, DateTime? afterTime = null, DateTime?
 beforeTime = null,
        string language = "en")
    {
        var results = new List<CaseDetails>();
        var paginateCases = _amazonSupport.Paginators.DescribeCases(
            new DescribeCasesRequest()
            {
                CaseIdList = caseIds,
                DisplayId = displayId,
                IncludeCommunications = includeCommunication,
                IncludeResolvedCases = includeResolvedCases,
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s"),
                Language = language
            });
        // Get the entire list using the paginator.
        await foreach (var cases in paginateCases.Cases)
        {
            results.Add(cases);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como descrever um caso

O exemplo de `describe-cases` a seguir retorna informações sobre o caso de suporte especificado na conta da AWS.

```
aws support describe-cases \
    --display-id "1234567890" \
    --after-time "2020-03-23T21:31:47.774Z" \
    --include-resolved-cases \
    --language "en" \
    --no-include-communications \
    --max-item 1
```

Saída:

```
{
    "cases": [
        {
            "status": "resolved",
            "ccEmailAddresses": [],
            "timeCreated": "2020-03-23T21:31:47.774Z",
            "caseId": "case-12345678910-2013-c4c1d2bf33c5cf47",
            "severityCode": "low",
            "language": "en",
            "categoryCode": "using-aws",
            "serviceCode": "general-info",
            "submittedBy": "myemail@example.com",
            "displayId": "1234567890",
            "subject": "Question about my account"
        }
    ]
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte DescribeCasesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getOpenCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);

            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(20)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
                System.out.println("The case status is " + sinCase.status());
                System.out.println("The case Id is " + sinCase.caseId());
                System.out.println("The case subject is " + sinCase.subject());
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
```

```
    }
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeCasesCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get all of the unresolved cases in your account.
    // Filter or expand results by providing parameters to the
 DescribeCasesCommand. Refer
    // to the TypeScript definition and the API doc for more information on
 possible parameters.
    // https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/client-
support/interfaces/describecasescommandinput.html
    const response = await client.send(new DescribeCasesCommand({}));
    const caseIds = response.cases.map((supportCase) => supportCase.caseId);
    console.log(caseIds);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getOpenCase() {
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 20
        afterTime = yesterday.toString()
        beforeTime = now.toString()
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeCasesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_cases(self, after_time, before_time, resolved):
        """
        Describe support cases over a period of time, optionally filtering
        by status.

        :param after_time: The start time to include for cases.
        :param before_time: The end time to include for cases.
        :param resolved: True to include resolved cases in the results,
            otherwise results are open cases.
        :return: The final status of the case.
        """
        try:
            cases = []
            paginator = self.support_client.get_paginator("describe_cases")
```

```
            for page in paginator.paginate(
                afterTime=after_time,
                beforeTime=before_time,
                includeResolvedCases=resolved,
                language="en",
            ):
                cases += page["cases"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe cases. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            if resolved:
                cases = filter(lambda case: case["status"] == "resolved", cases)
            return cases
```

- Para obter detalhes da API, consulte a DescribeCasesReferência da API AWSSDK for Python (Boto3).

Descrever as comunicações do AWS Support de um caso usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever as comunicações do AWS Support para um caso.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the communications for a case, optionally with a date filter.
    /// </summary>
    /// <param name="caseId">The ID of the support case.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <returns>The list of communications for the case.</returns>
    public async Task<List<Communication>> DescribeCommunications(string caseId,
 DateTime? afterTime = null, DateTime? beforeTime = null)
    {
        var results = new List<Communication>();
        var paginateCommunications =
 _amazonSupport.Paginators.DescribeCommunications(
            new DescribeCommunicationsRequest()
            {
                CaseId = caseId,
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s")
            });
        // Get the entire list using the paginator.
        await foreach (var communications in
 paginateCommunications.Communications)
        {
            results.Add(communications);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como descrever a comunicação mais recente de um caso

O exemplo de `describe-communications` a seguir retorna a comunicação mais recente do caso de suporte especificado na conta da AWS.

```
aws support describe-communications \
    --case-id "case-12345678910-2013-c4c1d2bf33c5cf47" \
    --after-time "2020-03-23T21:31:47.774Z" \
    --max-item 1
```

Saída:

```
{
    "communications": [
        {
            "body": "I want to learn more about an AWS service.",
            "attachmentSet": [],
            "caseId": "case-12345678910-2013-c4c1d2bf33c5cf47",
            "timeCreated": "2020-05-12T23:12:35.000Z",
            "submittedBy": "Amazon Web Services"
        }
    ],
    "NextToken":
 "eyJuZXh0VG9rZW4iOiBudWxsLCAiYm90b190cnVuY2F0ZV9hbW91bnQEXAMPLE=="
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte DescribeCommunicationsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String listCommunications(SupportClient supportClient, String
caseId) {
       try {
           String attachId = null;
           DescribeCommunicationsRequest communicationsRequest =
DescribeCommunicationsRequest.builder()
                   .caseId(caseId)
                   .maxResults(10)
                   .build();

           DescribeCommunicationsResponse response =
supportClient.describeCommunications(communicationsRequest);
           List<Communication> communications = response.communications();
           for (Communication comm : communications) {
               System.out.println("the body is: " + comm.body());

               // Get the attachment id value.
               List<AttachmentDetails> attachments = comm.attachmentSet();
               for (AttachmentDetails detail : attachments) {
                   attachId = detail.attachmentId();
               }
           }
           return attachId;

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeCommunicationsCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get all communications for the support case.
    // Filter results by providing parameters to the
 DescribeCommunicationsCommand. Refer
    // to the TypeScript definition and the API doc for more information on
 possible parameters.
    // https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/client-
support/interfaces/describecommunicationscommandinput.html
    const response = await client.send(
      new DescribeCommunicationsCommand({
        // Set value to an existing case id.
        caseId: "CASE_ID",
      }),
    );
    const text = response.communications.map((item) => item.body).join("\n");
    console.log(text);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listCommunications(caseIdVal: String?): String? {
    val communicationsRequest = DescribeCommunicationsRequest {
        caseId = caseIdVal
        maxResults = 10
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response =
 supportClient.describeCommunications(communicationsRequest)
        response.communications?.forEach { comm ->
            println("the body is: " + comm.body)
            comm.attachmentSet?.forEach { detail ->
                return detail.attachmentId
            }
        }
    }
    return ""
}
```

- Para obter detalhes da API, consulte a DescribeCommunicationsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_all_case_communications(self, case_id):
        """
        Describe all the communications for a case using a paginator.

        :param case_id: The ID of the case.
        :return: The communications for the case.
        """
        try:
            communications = []
            paginator =
 self.support_client.get_paginator("describe_communications")
            for page in paginator.paginate(caseId=case_id):
                communications += page["communications"]
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe communications. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return communications
```

- Para obter detalhes da API, consulte a DescribeCommunicationsReferência da API AWSSDK for Python (Boto3).

Descrever os serviços da AWS disponíveis para os casos de suporte usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever a lista de serviços da AWS.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get the descriptions of AWS services.
/// </summary>
/// <param name="name">Optional language for services.
/// Currently "en" (English) and "ja" (Japanese) are supported.</param>
/// <returns>The list of AWS service descriptions.</returns>
public async Task<List<Service>> DescribeServices(string language = "en")
{
    var response = await _amazonSupport.DescribeServicesAsync(
        new DescribeServicesRequest()
        {
            Language = language
        });
    return response.Services;
}
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os serviços e categorias de serviço da AWS

O exemplo de `describe-services` a seguir lista as categorias de serviço disponíveis para a solicitação de informações gerais.

```
aws support describe-services \
    --service-code-list "general-info"
```

Saída:

```
{
    "services": [
        {
            "code": "general-info",
            "name": "General Info and Getting Started",
            "categories": [
                {
                    "code": "charges",
                    "name": "How Will I Be Charged?"
                },
                {
                    "code": "gdpr-queries",
                    "name": "Data Privacy Query"
                },
                {
                    "code": "reserved-instances",
                    "name": "Reserved Instances"
                },
                {
                    "code": "resource",
                    "name": "Where is my Resource?"
                },
                {
                    "code": "using-aws",
                    "name": "Using AWS & Services"
                },
                {
                    "code": "free-tier",
                    "name": "Free Tier"
                },
                {
                    "code": "security-and-compliance",
                    "name": "Security & Compliance"
                },
                {
                    "code": "account-structure",
                    "name": "Account Structure"
                }
```

```
            ]
        }
    ]
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte DescribeServicesem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Return a List that contains a Service name and Category name.
    public static List<String> displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
DescribeServicesRequest.builder()
                    .language("en")
                    .build();

            DescribeServicesResponse response =
supportClient.describeServices(servicesRequest);
            String serviceCode = null;
            String catName = null;
            List<String> sevCatList = new ArrayList<>();
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;
```

```
                System.out.println("The Service name is: " + service.name());
                if (service.name().compareTo("Account") == 0)
                    serviceCode = service.code();

                // Get the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                    if (cat.name().compareTo("Security") == 0)
                        catName = cat.name();
                }
                index++;
            }

            // Push the two values to the list.
            sevCatList.add(serviceCode);
            sevCatList.add(catName);
            return sevCatList;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return null;
    }
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for Java 2.x da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Return a List that contains a Service name and Category name.
```

```
suspend fun displayServices(): List<String> {
    var serviceCode = ""
    var catName = ""
    val sevCatList = mutableListOf<String>()
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
                return@forEach
            }

            println("The Service name is ${service.name}")
            if (service.name == "Account") {
                serviceCode = service.code.toString()
            }

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                if (cat.name == "Security") {
                    catName = cat.name!!
                }
            }
            index++
        }
    }

    // Push the two values to the list.
    serviceCode.let { sevCatList.add(it) }
    catName.let { sevCatList.add(it) }
    return sevCatList
}
```

- Para obter detalhes da API, consulte a DescribeServicesreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_services(self, language):
        """
        Get the descriptions of AWS services available for support for a
 language.

        :param language: The language for support services.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of AWS service descriptions.
        """
        try:
            response = self.support_client.describe_services(language=language)
            services = response["services"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
```

```
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get Support services for language %s. Here's why:
%s: %s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return services
```

- Para obter detalhes da API, consulte a DescribeServicesReferência da API AWSSDK for Python (Boto3).

Descrever os níveis de gravidade do AWS Support usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever os níveis de gravidade do AWS Support.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the descriptions of support severity levels.
    /// </summary>
    /// <param name="name">Optional language for severity levels.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of support severity levels.</returns>
    public async Task<List<SeverityLevel>> DescribeSeverityLevels(string language
 = "en")
    {
        var response = await _amazonSupport.DescribeSeverityLevelsAsync(
            new DescribeSeverityLevelsRequest()
            {
                Language = language
            });
        return response.SeverityLevels;
    }
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como listar os níveis de gravidade disponíveis

O exemplo de `describe-severity-levels` a seguir lista os níveis de gravidade disponíveis para um caso de suporte.

```
aws support describe-severity-levels
```

Saída:

```
{
    "severityLevels": [
        {
            "code": "low",
            "name": "Low"
        },
        {
            "code": "normal",
            "name": "Normal"
        },
        {
            "code": "high",
            "name": "High"
        },
        {
            "code": "urgent",
            "name": "Urgent"
        },
        {
            "code": "critical",
            "name": "Critical"
        }
    ]
}
```

Para obter mais informações, consulte Choosing a severity no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte DescribeSeverityLevelsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String displaySevLevels(SupportClient supportClient) {
       try {
           DescribeSeverityLevelsRequest severityLevelsRequest =
DescribeSeverityLevelsRequest.builder()
                   .language("en")
                   .build();

           DescribeSeverityLevelsResponse response =
supportClient.describeSeverityLevels(severityLevelsRequest);
           List<SeverityLevel> severityLevels = response.severityLevels();
           String levelName = null;
           for (SeverityLevel sevLevel : severityLevels) {
               System.out.println("The severity level name is: " +
sevLevel.name());
               if (sevLevel.name().compareTo("High") == 0)
                   levelName = sevLevel.name();
           }
           return levelName;

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSeverityLevelsCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get the list of severity levels.
    // The available values depend on the support plan for the account.
    const response = await client.send(new DescribeSeverityLevelsCommand({}));
    console.log(response.severityLevels);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun displaySevLevels(): String {
    var levelName = ""
    val severityLevelsRequest = DescribeSeverityLevelsRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response =
 supportClient.describeSeverityLevels(severityLevelsRequest)
        response.severityLevels?.forEach { sevLevel ->
            println("The severity level name is: ${sevLevel.name}")
            if (sevLevel.name == "High") {
                levelName = sevLevel.name!!
            }
        }
        return levelName
    }
}
```

- Para obter detalhes da API, consulte a DescribeSeverityLevelsreferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client
```

```
    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_severity_levels(self, language):
        """
        Get the descriptions of available severity levels for support cases for a
language.

        :param language: The language for support severity levels.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of severity levels.
        """
        try:
            response =
self.support_client.describe_severity_levels(language=language)
            severity_levels = response["severityLevels"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get severity levels for language %s. Here's why:
%s: %s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return severity_levels
```

- Para obter detalhes da API, consulte a DescribeSeverityLevelsReferência da API AWSSDK for Python (Boto3).

Resolver um caso do AWS Support usando um SDK da AWS

Os exemplos de código a seguir mostram como resolver um caso do AWS Support.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Conceitos básicos de casos

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Resolve a support case by caseId.
/// </summary>
/// <param name="caseId">Id for the support case.</param>
/// <returns>The final status of the case after resolving.</returns>
public async Task<string> ResolveCase(string caseId)
{
    var response = await _amazonSupport.ResolveCaseAsync(
        new ResolveCaseRequest()
        {
            CaseId = caseId
        });
    return response.FinalCaseStatus;
}
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for .NET da API.

CLI

AWS CLI

Como solucionar um caso de suporte

O exemplo de `resolve-case` a seguir soluciona um caso de suporte na sua conta da AWS.

```
aws support resolve-case \
    --case-id "case-12345678910-2013-c4c1d2bf33c5cf47"
```

Saída:

```
{
    "finalCaseStatus": "resolved",
    "initialCaseStatus": "work-in-progress"
}
```

Para obter mais informações, consulte Case management no Guia do usuário do AWS Support.

- Para obter detalhes da API, consulte ResolveCaseem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void resolveSupportCase(SupportClient supportClient, String
 caseId) {
        try {
```

```
            ResolveCaseRequest caseRequest = ResolveCaseRequest.builder()
                    .caseId(caseId)
                    .build();

            ResolveCaseResponse response =
 supportClient.resolveCase(caseRequest);
            System.out.println("The status of case " + caseId + " is " +
 response.finalCaseStatus());

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ResolveCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

const main = async () => {
  try {
    const response = await client.send(
      new ResolveCaseCommand({
        caseId: "CASE_ID",
      }),
    );
```

```
    console.log(response.finalCaseStatus);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for JavaScript da API.

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun resolveSupportCase(caseIdVal: String) {
    val caseRequest = ResolveCaseRequest {
        caseId = caseIdVal
    }
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.resolveCase(caseRequest)
        println("The status of case $caseIdVal is ${response.finalCaseStatus}")
    }
}
```

- Para obter detalhes da API, consulte a ResolveCasereferência da API AWSSDK for Kotlin.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def resolve_case(self, case_id):
        """
        Resolve a support case by its caseId.

        :param case_id: The ID of the case to resolve.
        :return: The final status of the case.
        """
        try:
            response = self.support_client.resolve_case(caseId=case_id)
            final_status = response["finalCaseStatus"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
```

```
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't resolve case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return final_status
```

- Para obter detalhes da API, consulte a ResolveCaseReferência da API AWSSDK for Python (Boto3).

Cenários para o AWS Support usando AWS SDKs

Os exemplos de código a seguir mostram como usar o AWS Support com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Conceitos básicos dos casos do AWS Support usando um SDK da AWS

Conceitos básicos dos casos do AWS Support usando um SDK da AWS

Os exemplos de código a seguir mostram como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.

- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Hello AWS Support example.
/// </summary>
public static class SupportCaseScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.
    To use the AWS Support API, you must have one of the following AWS Support
 plans: Business, Enterprise On-Ramp, or Enterprise.

    This .NET example performs the following tasks:
    1.  Get and display services. Select a service from the list.
    2.  Select a category from the selected service.
    3.  Get and display severity levels and select a severity level from the
 list.
    4.  Create a support case using the selected service, category, and severity
 level.
    5.  Get and display a list of open support cases for the current day.
    6.  Create an attachment set with a sample text file to add to the case.
    7.  Add a communication with the attachment to the support case.
    8.  List the communications of the support case.
    9.  Describe the attachment set.
```

```
   10. Resolve the support case.
   11. Get a list of resolved cases for the current day.
  */

   private static SupportWrapper _supportWrapper = null!;

   static async Task Main(string[] args)
   {
       // Set up dependency injection for the AWS Support service.
       // Use your AWS profile name, or leave it blank to use the default
profile.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft",
LogLevel.Trace))
           .ConfigureServices((_, services) =>
               services.AddAWSService<IAmazonAWSSupport>(new AWSOptions()
{ Profile = "default" })
                   .AddTransient<SupportWrapper>()
           )
           .Build();

       var logger = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       }).CreateLogger(typeof(SupportCaseScenario));

       _supportWrapper = host.Services.GetRequiredService<SupportWrapper>();

       Console.WriteLine(new string('-', 80));
       Console.WriteLine("Welcome to the AWS Support case example scenario.");
       Console.WriteLine(new string('-', 80));

       try
       {
           var apiSupported = await _supportWrapper.VerifySubscription();
           if (!apiSupported)
           {
               logger.LogError("You must have a Business, Enterprise On-Ramp, or
Enterprise Support " +
```

```
                                "plan to use the AWS Support API. \n\tPlease
upgrade your subscription to run these examples.");
                return;
            }

            var service = await DisplayAndSelectServices();

            var category = DisplayAndSelectCategories(service);

            var severityLevel = await DisplayAndSelectSeverity();

            var caseId = await CreateSupportCase(service, category,
severityLevel);

            await DescribeTodayOpenCases();

            var attachmentSetId = await CreateAttachmentSet();

            await AddCommunicationToCase(attachmentSetId, caseId);

            var attachmentId = await ListCommunicationsForCase(caseId);

            await DescribeCaseAttachment(attachmentId);

            await ResolveCase(caseId);

            await DescribeTodayResolvedCases();

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("AWS Support case example scenario complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// List some available services from AWS Support, and select a service for
the example.
    /// </summary>
    /// <returns>The selected service.</returns>
    private static async Task<Service> DisplayAndSelectServices()
```

```
    {
        Console.WriteLine(new string('-', 80));
        var services = await _supportWrapper.DescribeServices();
        Console.WriteLine($"AWS Support client returned {services.Count}
services.");

        Console.WriteLine($"1. Displaying first 10 services:");
        for (int i = 0; i < 10 && i < services.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {services[i].Name}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > services.Count)
        {
            Console.WriteLine(
                "Select an example support service by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        Console.WriteLine(new string('-', 80));

        return services[choiceNumber - 1];
    }

    /// <summary>
    /// List the available categories for a service and select a category for the
example.
    /// </summary>
    /// <param name="service">Service to use for displaying categories.</param>
    /// <returns>The selected category.</returns>
    private static Category DisplayAndSelectCategories(Service service)
    {
        Console.WriteLine(new string('-', 80));

        Console.WriteLine($"2. Available support categories for Service
\"{service.Name}\":");
        for (int i = 0; i < service.Categories.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {service.Categories[i].Name}");
        }

        var choiceNumber = 0;
```

```
        while (choiceNumber < 1 || choiceNumber > service.Categories.Count)
        {
            Console.WriteLine(
                "Select an example support category by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        Console.WriteLine(new string('-', 80));

        return service.Categories[choiceNumber - 1];
    }

    /// <summary>
    /// List available severity levels from AWS Support, and select a level for
the example.
    /// </summary>
    /// <returns>The selected severity level.</returns>
    private static async Task<SeverityLevel> DisplayAndSelectSeverity()
    {
        Console.WriteLine(new string('-', 80));
        var severityLevels = await _supportWrapper.DescribeSeverityLevels();

        Console.WriteLine($"3. Get and display available severity levels:");
        for (int i = 0; i < 10 && i < severityLevels.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {severityLevels[i].Name}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > severityLevels.Count)
        {
            Console.WriteLine(
                "Select an example severity level by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        Console.WriteLine(new string('-', 80));

        return severityLevels[choiceNumber - 1];
    }
```

```
    /// <summary>
    /// Create an example support case.
    /// </summary>
    /// <param name="service">Service to use for the new case.</param>
    /// <param name="category">Category to use for the new case.</param>
    /// <param name="severity">Severity to use for the new case.</param>
    /// <returns>The caseId of the new support case.</returns>
    private static async Task<string> CreateSupportCase(Service service,
        Category category, SeverityLevel severity)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. Create an example support case" +
                          $" with the following settings:" +
                          $" \n\tService: {service.Name}, Category:
{category.Name} " +
                          $"and Severity Level: {severity.Name}.");
        var caseId = await _supportWrapper.CreateCase(service.Code,
category.Code, severity.Code,
            "Example case for testing, ignore.", "This is my example support
case.");

        Console.WriteLine($"\tNew case created with ID {caseId}");

        Console.WriteLine(new string('-', 80));

        return caseId;
    }

    /// <summary>
    /// List open cases for the current day.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeTodayOpenCases()
    {
        Console.WriteLine($"5. List the open support cases for the current
day.");
        // Describe the cases. If it is empty, try again and allow time for the
new case to appear.
        List<CaseDetails> currentOpenCases = null!;
        while (currentOpenCases == null || currentOpenCases.Count == 0)
        {
            Thread.Sleep(1000);
            currentOpenCases = await _supportWrapper.DescribeCases(
                new List<string>(),
```

```
                null,
                false,
                false,
                DateTime.UtcNow.Date,
                DateTime.UtcNow);
        }

        foreach (var openCase in currentOpenCases)
        {
            Console.WriteLine($"\tCase: {openCase.CaseId} created
 {openCase.TimeCreated}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create an attachment set for a support case.
    /// </summary>
    /// <returns>The attachment set id.</returns>
    private static async Task<string> CreateAttachmentSet()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. Create an attachment set for a support case.");
        var fileName = "example_attachment.txt";

        // Create the file if it does not already exist.
        if (!File.Exists(fileName))
        {
            await using StreamWriter sw = File.CreateText(fileName);
            await sw.WriteLineAsync(
                "This is a sample file for attachment to a support case.");
        }

        await using var ms = new MemoryStream(await
 File.ReadAllBytesAsync(fileName));

        var attachmentSetId = await _supportWrapper.AddAttachmentToSet(
            ms,
            fileName);

        Console.WriteLine($"\tNew attachment set created with id: \n
\t{attachmentSetId.Substring(0, 65)}...");
```

```
        Console.WriteLine(new string('-', 80));

        return attachmentSetId;
    }

    /// <summary>
    /// Add an attachment set and communication to a case.
    /// </summary>
    /// <param name="attachmentSetId">Id of the attachment set.</param>
    /// <param name="caseId">Id of the case to receive the attachment set.</
param>
    /// <returns>Async task.</returns>
    private static async Task AddCommunicationToCase(string attachmentSetId,
 string caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Add attachment set and communication to
 {caseId}.");

        await _supportWrapper.AddCommunicationToCase(
            caseId,
            "This is an example communication added to a support case.",
            attachmentSetId);

        Console.WriteLine($"\tNew attachment set and communication added to
 {caseId}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List the communications for a case.
    /// </summary>
    /// <param name="caseId">Id of the case to describe.</param>
    /// <returns>An attachment id.</returns>
    private static async Task<string> ListCommunicationsForCase(string caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. List communications for case {caseId}.");

        var communications = await
 _supportWrapper.DescribeCommunications(caseId);
        var attachmentId = "";
        foreach (var communication in communications)
```

```
        {
            Console.WriteLine(
                $"\tCommunication created on: {communication.TimeCreated} has
{communication.AttachmentSet.Count} attachments.");
            if (communication.AttachmentSet.Any())
            {
                attachmentId = communication.AttachmentSet.First().AttachmentId;
            }
        }

        Console.WriteLine(new string('-', 80));
        return attachmentId;
    }

    /// <summary>
    /// Describe an attachment by id.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment to describe.</param>
    /// <returns>Async task.</returns>
    private static async Task DescribeCaseAttachment(string attachmentId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Describe the attachment set.");

        var attachment = await _supportWrapper.DescribeAttachment(attachmentId);
        var data = Encoding.ASCII.GetString(attachment.Data.ToArray());
        Console.WriteLine($"\tAttachment includes {attachment.FileName} with
data: \n\t{data}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Resolve the support case.
    /// </summary>
    /// <param name="caseId">Id of the case to resolve.</param>
    /// <returns>Async task.</returns>
    private static async Task ResolveCase(string caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Resolve case {caseId}.");

        var status = await _supportWrapper.ResolveCase(caseId);
        Console.WriteLine($"\tCase {caseId} has final status {status}");
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List resolved cases for the current day.
    /// </summary>
    /// <returns>Async Task.</returns>
    private static async Task DescribeTodayResolvedCases()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"11. List the resolved support cases for the current
 day.");
        var currentCases = await _supportWrapper.DescribeCases(
            new List<string>(),
            null,
            false,
            true,
            DateTime.UtcNow.Date,
            DateTime.UtcNow);

        foreach (var currentCase in currentCases)
        {
            if (currentCase.Status == "resolved")
            {
                Console.WriteLine(
                    $"\tCase: {currentCase.CaseId}: status
 {currentCase.Status}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }
}
```

Os métodos de wrapper usados pelo cenário para as ações do AWS Support.

```
/// <summary>
/// Wrapper methods to use AWS Support for working with support cases.
/// </summary>
public class SupportWrapper
```

```
{
    private readonly IAmazonAWSSupport _amazonSupport;
    public SupportWrapper(IAmazonAWSSupport amazonSupport)
    {
        _amazonSupport = amazonSupport;
    }


    /// <summary>
    /// Get the descriptions of AWS services.
    /// </summary>
    /// <param name="name">Optional language for services.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of AWS service descriptions.</returns>
    public async Task<List<Service>> DescribeServices(string language = "en")
    {
        var response = await _amazonSupport.DescribeServicesAsync(
            new DescribeServicesRequest()
            {
                Language = language
            });
        return response.Services;
    }



    /// <summary>
    /// Get the descriptions of support severity levels.
    /// </summary>
    /// <param name="name">Optional language for severity levels.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of support severity levels.</returns>
    public async Task<List<SeverityLevel>> DescribeSeverityLevels(string language
 = "en")
    {
        var response = await _amazonSupport.DescribeSeverityLevelsAsync(
            new DescribeSeverityLevelsRequest()
            {
                Language = language
            });
        return response.SeverityLevels;
    }
```

```
    /// <summary>
    /// Create a new support case.
    /// </summary>
    /// <param name="serviceCode">Service code for the new case.</param>
    /// <param name="categoryCode">Category for the new case.</param>
    /// <param name="severityCode">Severity code for the new case.</param>
    /// <param name="subject">Subject of the new case.</param>
    /// <param name="body">Body text of the new case.</param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set for the
new case.</param>
    /// <param name="issueType">Optional issue type for the new case. Options are
"customer-service" or "technical".</param>
    /// <returns>The caseId of the new support case.</returns>
    public async Task<string> CreateCase(string serviceCode, string categoryCode,
string severityCode, string subject,
        string body, string language = "en", string? attachmentSetId = null,
string issueType = "customer-service")
    {
        var response = await _amazonSupport.CreateCaseAsync(
            new CreateCaseRequest()
            {
                ServiceCode = serviceCode,
                CategoryCode = categoryCode,
                SeverityCode = severityCode,
                Subject = subject,
                Language = language,
                AttachmentSetId = attachmentSetId,
                IssueType = issueType,
                CommunicationBody = body
            });
        return response.CaseId;
    }



    /// <summary>
    /// Add an attachment to a set, or create a new attachment set if one does
not exist.
    /// </summary>
    /// <param name="data">The data for the attachment.</param>
    /// <param name="fileName">The file name for the attachment.</param>
```

```
    /// <param name="attachmentSetId">Optional setId for the attachment. Creates
a new attachment set if empty.</param>
    /// <returns>The setId of the attachment.</returns>
    public async Task<string> AddAttachmentToSet(MemoryStream data, string
fileName, string? attachmentSetId = null)
    {
        var response = await _amazonSupport.AddAttachmentsToSetAsync(
            new AddAttachmentsToSetRequest
            {
                AttachmentSetId = attachmentSetId,
                Attachments = new List<Attachment>
                {
                    new Attachment
                    {
                        Data = data,
                        FileName = fileName
                    }
                }
            });
        return response.AttachmentSetId;
    }



    /// <summary>
    /// Get description of a specific attachment.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment, usually fetched by
describing the communications of a case.</param>
    /// <returns>The attachment object.</returns>
    public async Task<Attachment> DescribeAttachment(string attachmentId)
    {
        var response = await _amazonSupport.DescribeAttachmentAsync(
            new DescribeAttachmentRequest()
            {
                AttachmentId = attachmentId
            });
        return response.Attachment;
    }



    /// <summary>
```

```
    /// Add communication to a case, including optional attachment set ID and CC
 email addresses.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <param name="body">Body text of the communication.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set.</param>
    /// <param name="ccEmailAddresses">Optional list of CC email addresses.</
param>
    /// <returns>True if successful.</returns>
    public async Task<bool> AddCommunicationToCase(string caseId, string body,
        string? attachmentSetId = null, List<string>? ccEmailAddresses = null)
    {
        var response = await _amazonSupport.AddCommunicationToCaseAsync(
            new AddCommunicationToCaseRequest()
            {
                CaseId = caseId,
                CommunicationBody = body,
                AttachmentSetId = attachmentSetId,
                CcEmailAddresses = ccEmailAddresses
            });
        return response.Result;
    }



    /// <summary>
    /// Describe the communications for a case, optionally with a date filter.
    /// </summary>
    /// <param name="caseId">The ID of the support case.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <returns>The list of communications for the case.</returns>
    public async Task<List<Communication>> DescribeCommunications(string caseId,
 DateTime? afterTime = null, DateTime? beforeTime = null)
    {
        var results = new List<Communication>();
        var paginateCommunications =
 _amazonSupport.Paginators.DescribeCommunications(
            new DescribeCommunicationsRequest()
            {
                CaseId = caseId,
                AfterTime = afterTime?.ToString("s"),
```

```
                BeforeTime = beforeTime?.ToString("s")
            });
        // Get the entire list using the paginator.
        await foreach (var communications in
 paginateCommunications.Communications)
        {
            results.Add(communications);
        }
        return results;
    }



    /// <summary>
    /// Get case details for a list of case ids, optionally with date filters.
    /// </summary>
    /// <param name="caseIds">The list of case IDs.</param>
    /// <param name="displayId">Optional display ID.</param>
    /// <param name="includeCommunication">True to include communication.
 Defaults to true.</param>
    /// <param name="includeResolvedCases">True to include resolved cases.
 Defaults to false.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>A list of CaseDetails.</returns>
    public async Task<List<CaseDetails>> DescribeCases(List<string> caseIds,
 string? displayId = null, bool includeCommunication = true,
        bool includeResolvedCases = false, DateTime? afterTime = null, DateTime?
 beforeTime = null,
        string language = "en")
    {
        var results = new List<CaseDetails>();
        var paginateCases = _amazonSupport.Paginators.DescribeCases(
            new DescribeCasesRequest()
            {
                CaseIdList = caseIds,
                DisplayId = displayId,
                IncludeCommunications = includeCommunication,
                IncludeResolvedCases = includeResolvedCases,
                AfterTime = afterTime?.ToString("s"),
```

```
                BeforeTime = beforeTime?.ToString("s"),
                Language = language
            });
        // Get the entire list using the paginator.
        await foreach (var cases in paginateCases.Cases)
        {
            results.Add(cases);
        }
        return results;
    }



    /// <summary>
    /// Resolve a support case by caseId.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <returns>The final status of the case after resolving.</returns>
    public async Task<string> ResolveCase(string caseId)
    {
        var response = await _amazonSupport.ResolveCaseAsync(
            new ResolveCaseRequest()
            {
                CaseId = caseId
            });
        return response.FinalCaseStatus;
    }


    /// <summary>
    /// Verify the support level for AWS Support API access.
    /// </summary>
    /// <returns>True if the subscription level supports API access.</returns>
    public async Task<bool> VerifySubscription()
    {
        try
        {
            var response = await _amazonSupport.DescribeServicesAsync(
                new DescribeServicesRequest()
                {
                    Language = "en"
                });
            return response.HttpStatusCode == HttpStatusCode.OK;
        }
```

```
        catch (Amazon.AWSSupport.AmazonAWSSupportException ex)
        {
            if (ex.ErrorCode == "SubscriptionRequiredException")
            {
                return false;
            }
            else throw;
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute várias operações do AWS Support.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.support.SupportClient;
import software.amazon.awssdk.services.support.model.AddAttachmentsToSetResponse;
import
 software.amazon.awssdk.services.support.model.AddCommunicationToCaseRequest;
import
 software.amazon.awssdk.services.support.model.AddCommunicationToCaseResponse;
import software.amazon.awssdk.services.support.model.Attachment;
import software.amazon.awssdk.services.support.model.AttachmentDetails;
import software.amazon.awssdk.services.support.model.CaseDetails;
import software.amazon.awssdk.services.support.model.Category;
import software.amazon.awssdk.services.support.model.Communication;
import software.amazon.awssdk.services.support.model.CreateCaseRequest;
import software.amazon.awssdk.services.support.model.CreateCaseResponse;
import software.amazon.awssdk.services.support.model.DescribeAttachmentRequest;
import software.amazon.awssdk.services.support.model.DescribeAttachmentResponse;
import software.amazon.awssdk.services.support.model.DescribeCasesRequest;
import software.amazon.awssdk.services.support.model.DescribeCasesResponse;
import
 software.amazon.awssdk.services.support.model.DescribeCommunicationsRequest;
import
 software.amazon.awssdk.services.support.model.DescribeCommunicationsResponse;
import software.amazon.awssdk.services.support.model.DescribeServicesRequest;
import software.amazon.awssdk.services.support.model.DescribeServicesResponse;
import
 software.amazon.awssdk.services.support.model.DescribeSeverityLevelsRequest;
import
 software.amazon.awssdk.services.support.model.DescribeSeverityLevelsResponse;
import software.amazon.awssdk.services.support.model.ResolveCaseRequest;
import software.amazon.awssdk.services.support.model.ResolveCaseResponse;
import software.amazon.awssdk.services.support.model.Service;
import software.amazon.awssdk.services.support.model.SeverityLevel;
import software.amazon.awssdk.services.support.model.SupportException;
import software.amazon.awssdk.services.support.model.AddAttachmentsToSetRequest;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.time.Instant;
import java.time.temporal.ChronoUnit;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 *
 * In addition, you must have the AWS Business Support Plan to use the AWS
 * Support Java API. For more information, see:
 *
 * https://aws.amazon.com/premiumsupport/plans/
 *
 * This Java example performs the following tasks:
 *
 * 1. Gets and displays available services.
 * 2. Gets and displays severity levels.
 * 3. Creates a support case by using the selected service, category, and
 * severity level.
 * 4. Gets a list of open cases for the current day.
 * 5. Creates an attachment set with a generated file.
 * 6. Adds a communication with the attachment to the support case.
 * 7. Lists the communications of the support case.
 * 8. Describes the attachment set included with the communication.
 * 9. Resolves the support case.
 * 10. Gets a list of resolved cases for the current day.
 */
public class SupportScenario {

    public static final String DASHES = new String(new char[80]).replace("\0",
 "-");

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <fileAttachment>Where:
                    fileAttachment - The file can be a simple saved .txt file to
 use as an email attachment.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String fileAttachment = args[0];
        Region region = Region.US_WEST_2;
        SupportClient supportClient = SupportClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("***** Welcome to the AWS Support case example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Get and display available services.");
        List<String> sevCatList = displayServices(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Get and display Support severity levels.");
        String sevLevel = displaySevLevels(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Create a support case using the selected service,
category, and severity level.");
        String caseId = createSupportCase(supportClient, sevCatList, sevLevel);
        if (caseId.compareTo("") == 0) {
            System.out.println("A support case was not successfully created!");
            System.exit(1);
        } else
            System.out.println("Support case " + caseId + " was successfully
created!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get open support cases.");
        getOpenCase(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create an attachment set with a generated file to
add to the case.");
        String attachmentSetId = addAttachment(supportClient, fileAttachment);
        System.out.println("The Attachment Set id value is" + attachmentSetId);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Add communication with the attachment to the
support case.");
        addAttachSupportCase(supportClient, caseId, attachmentSetId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. List the communications of the support case.");
        String attachId = listCommunications(supportClient, caseId);
        System.out.println("The Attachment id value is" + attachId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Describe the attachment set included with the
communication.");
        describeAttachment(supportClient, attachId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Resolve the support case.");
        resolveSupportCase(supportClient, caseId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a list of resolved cases for the current
day.");
        getResolvedCase(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("***** This Scenario has successfully completed");
        System.out.println(DASHES);
    }

    public static void getResolvedCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);
```

```
            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(30)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .includeResolvedCases(true)
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
                if (sinCase.status().compareTo("resolved") == 0)
                    System.out.println("The case status is " + sinCase.status());
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void resolveSupportCase(SupportClient supportClient, String
caseId) {
        try {
            ResolveCaseRequest caseRequest = ResolveCaseRequest.builder()
                    .caseId(caseId)
                    .build();

            ResolveCaseResponse response =
supportClient.resolveCase(caseRequest);
            System.out.println("The status of case " + caseId + " is " +
response.finalCaseStatus());

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeAttachment(SupportClient supportClient, String
attachId) {
        try {
```

```
            DescribeAttachmentRequest attachmentRequest =
DescribeAttachmentRequest.builder()
                    .attachmentId(attachId)
                    .build();

            DescribeAttachmentResponse response =
supportClient.describeAttachment(attachmentRequest);
            System.out.println("The name of the file is " +
response.attachment().fileName());

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String listCommunications(SupportClient supportClient, String
caseId) {
        try {
            String attachId = null;
            DescribeCommunicationsRequest communicationsRequest =
DescribeCommunicationsRequest.builder()
                    .caseId(caseId)
                    .maxResults(10)
                    .build();

            DescribeCommunicationsResponse response =
supportClient.describeCommunications(communicationsRequest);
            List<Communication> communications = response.communications();
            for (Communication comm : communications) {
                System.out.println("the body is: " + comm.body());

                // Get the attachment id value.
                List<AttachmentDetails> attachments = comm.attachmentSet();
                for (AttachmentDetails detail : attachments) {
                    attachId = detail.attachmentId();
                }
            }
            return attachId;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
```

```
        return "";
    }

    public static void addAttachSupportCase(SupportClient supportClient, String
caseId, String attachmentSetId) {
        try {
            AddCommunicationToCaseRequest caseRequest =
AddCommunicationToCaseRequest.builder()
                    .caseId(caseId)
                    .attachmentSetId(attachmentSetId)
                    .communicationBody("Please refer to attachment for details.")
                    .build();

            AddCommunicationToCaseResponse response =
supportClient.addCommunicationToCase(caseRequest);
            if (response.result())
                System.out.println("You have successfully added a communication
to an AWS Support case");
            else
                System.out.println("There was an error adding the communication
to an AWS Support case");

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String addAttachment(SupportClient supportClient, String
fileAttachment) {
        try {
            File myFile = new File(fileAttachment);
            InputStream sourceStream = new FileInputStream(myFile);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            Attachment attachment = Attachment.builder()
                    .fileName(myFile.getName())
                    .data(sourceBytes)
                    .build();

            AddAttachmentsToSetRequest setRequest =
AddAttachmentsToSetRequest.builder()
                    .attachments(attachment)
                    .build();
```

```
            AddAttachmentsToSetResponse response =
supportClient.addAttachmentsToSet(setRequest);
            return response.attachmentSetId();

        } catch (SupportException | FileNotFoundException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    public static void getOpenCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);

            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(20)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
                System.out.println("The case status is " + sinCase.status());
                System.out.println("The case Id is " + sinCase.caseId());
                System.out.println("The case subject is " + sinCase.subject());
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String createSupportCase(SupportClient supportClient,
List<String> sevCatList, String sevLevel) {
        try {
```

```
            String serviceCode = sevCatList.get(0);
            String caseCat = sevCatList.get(1);
            CreateCaseRequest caseRequest = CreateCaseRequest.builder()
                    .categoryCode(caseCat.toLowerCase())
                    .serviceCode(serviceCode.toLowerCase())
                    .severityCode(sevLevel.toLowerCase())
                    .communicationBody("Test issue with " +
serviceCode.toLowerCase())
                    .subject("Test case, please ignore")
                    .language("en")
                    .issueType("technical")
                    .build();

            CreateCaseResponse response = supportClient.createCase(caseRequest);
            return response.caseId();

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    public static String displaySevLevels(SupportClient supportClient) {
        try {
            DescribeSeverityLevelsRequest severityLevelsRequest =
DescribeSeverityLevelsRequest.builder()
                    .language("en")
                    .build();

            DescribeSeverityLevelsResponse response =
supportClient.describeSeverityLevels(severityLevelsRequest);
            List<SeverityLevel> severityLevels = response.severityLevels();
            String levelName = null;
            for (SeverityLevel sevLevel : severityLevels) {
                System.out.println("The severity level name is: " +
sevLevel.name());
                if (sevLevel.name().compareTo("High") == 0)
                    levelName = sevLevel.name();
            }
            return levelName;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
```

```
            System.exit(1);
        }
        return "";
    }

    // Return a List that contains a Service name and Category name.
    public static List<String> displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
DescribeServicesRequest.builder()
                    .language("en")
                    .build();

            DescribeServicesResponse response =
supportClient.describeServices(servicesRequest);
            String serviceCode = null;
            String catName = null;
            List<String> sevCatList = new ArrayList<>();
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;

                System.out.println("The Service name is: " + service.name());
                if (service.name().compareTo("Account") == 0)
                    serviceCode = service.code();

                // Get the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                    if (cat.name().compareTo("Security") == 0)
                        catName = cat.name();
                }
                index++;
            }

            // Push the two values to the list.
            sevCatList.add(serviceCode);
            sevCatList.add(catName);
            return sevCatList;
```

```
        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo no terminal.

```
import {
  AddAttachmentsToSetCommand,
  AddCommunicationToCaseCommand,
  CreateCaseCommand,
```

```
  DescribeAttachmentCommand,
  DescribeCasesCommand,
  DescribeCommunicationsCommand,
  DescribeServicesCommand,
  DescribeSeverityLevelsCommand,
  ResolveCaseCommand,
  SupportClient,
} from "@aws-sdk/client-support";
import inquirer from "inquirer";

// Retry an asynchronous function on failure.
const retry = async ({ intervalInMs = 500, maxRetries = 10 }, fn) => {
  try {
    return await fn();
  } catch (err) {
    console.log(`Function call failed. Retrying.`);
    console.error(err.message);
    if (maxRetries === 0) throw err;
    await new Promise((resolve) => setTimeout(resolve, intervalInMs));
    return retry({ intervalInMs, maxRetries: maxRetries - 1 }, fn);
  }
};

const wrapText = (text, char = "=") => {
  const rule = char.repeat(80);
  return `${rule}\n    ${text}\n${rule}\n`;
};

const client = new SupportClient({ region: "us-east-1" });

// Verify that the account has a Support plan.
export const verifyAccount = async () => {
  const command = new DescribeServicesCommand({});

  try {
    await client.send(command);
  } catch (err) {
    if (err.name === "SubscriptionRequiredException") {
      throw new Error(
        "You must be subscribed to the AWS Support plan to use this feature."
      );
    } else {
      throw err;
    }
```

```
  }
};

// Get the list of available services.
export const getService = async () => {
  const { services } = await client.send(new DescribeServicesCommand({}));
  const { selectedService } = await inquirer.prompt({
    name: "selectedService",
    type: "list",
    message:
      "Select a service. Your support case will be created for this service. The
 list of services is truncated for readability.",
    choices: services.slice(0, 10).map((s) => ({ name: s.name, value: s })),
  });
  return selectedService;
};

// Get the list of available support case categories for a service.
export const getCategory = async (service) => {
  const { selectedCategory } = await inquirer.prompt({
    name: "selectedCategory",
    type: "list",
    message: "Select a category.",
    choices: service.categories.map((c) => ({ name: c.name, value: c })),
  });
  return selectedCategory;
};

// Get the available severity levels for the account.
export const getSeverityLevel = async () => {
  const command = new DescribeSeverityLevelsCommand({});
  const { severityLevels } = await client.send(command);
  const { selectedSeverityLevel } = await inquirer.prompt({
    name: "selectedSeverityLevel",
    type: "list",
    message: "Select a severity level.",
    choices: severityLevels.map((s) => ({ name: s.name, value: s })),
  });
  return selectedSeverityLevel;
};

// Create a new support case and return the caseId.
export const createCase = async ({
  selectedService,
```

```
  selectedCategory,
  selectedSeverityLevel,
}) => {
  const command = new CreateCaseCommand({
    subject: "IGNORE: Test case",
    communicationBody: "This is a test. Please ignore.",
    serviceCode: selectedService.code,
    categoryCode: selectedCategory.code,
    severityCode: selectedSeverityLevel.code,
  });
  const { caseId } = await client.send(command);
  return caseId;
};

// Get a list of open support cases created today.
export const getTodaysOpenCases = async () => {
  const d = new Date();
  const startOfToday = new Date(d.getFullYear(), d.getMonth(), d.getDate());
  const command = new DescribeCasesCommand({
    includeCommunications: false,
    afterTime: startOfToday.toISOString(),
  });

  const { cases } = await client.send(command);

  if (cases.length === 0) {
    throw new Error(
      "Unexpected number of cases. Expected more than 0 open cases."
    );
  }
  return cases;
};

// Create an attachment set.
export const createAttachmentSet = async () => {
  const command = new AddAttachmentsToSetCommand({
    attachments: [
      {
        fileName: "example.txt",
        data: new TextEncoder().encode("some example text"),
      },
    ],
  });
  const { attachmentSetId } = await client.send(command);
```

```
  return attachmentSetId;
};

export const linkAttachmentSetToCase = async (attachmentSetId, caseId) => {
  const command = new AddCommunicationToCaseCommand({
    attachmentSetId,
    caseId,
    communicationBody: "Adding attachment set to case.",
  });
  await client.send(command);
};

// Get all communications for a support case.
export const getCommunications = async (caseId) => {
  const command = new DescribeCommunicationsCommand({
    caseId,
  });
  const { communications } = await client.send(command);
  return communications;
};

// Get an attachment set.
export const getFirstAttachment = (communications) => {
  const firstCommWithAttachment = communications.find(
    (c) => c.attachmentSet.length > 0
  );
  return firstCommWithAttachment?.attachmentSet[0].attachmentId;
};

// Get an attachment.
export const getAttachment = async (attachmentId) => {
  const command = new DescribeAttachmentCommand({
    attachmentId,
  });
  const { attachment } = await client.send(command);
  return attachment;
};

// Resolve the case matching the given case ID.
export const resolveCase = async (caseId) => {
  const { shouldResolve } = await inquirer.prompt({
    name: "shouldResolve",
    type: "confirm",
    message: `Do you want to resolve ${caseId}?`,
```

```
  });

  if (shouldResolve) {
    const command = new ResolveCaseCommand({
      caseId: caseId,
    });

    await client.send(command);
    return true;
  }
  return false;
};

// Find a specific case in the list of provided cases by case ID.
// If the case is not found, and the results are paginated, continue
// paging through the results.
export const findCase = async ({ caseId, cases, nextToken }) => {
  const foundCase = cases.find((c) => c.caseId === caseId);

  if (foundCase) {
    return foundCase;
  }

  if (nextToken) {
    const response = await client.send(
      new DescribeCasesCommand({
        nextToken,
        includeResolvedCases: true,
      })
    );
    return findCase({
      caseId,
      cases: response.cases,
      nextToken: response.nextToken,
    });
  }

  throw new Error(`${caseId} not found.`);
};

// Get all cases created today.
export const getTodaysResolvedCases = async (caseIdToWaitFor) => {
  const d = new Date("2023-01-18");
  const startOfToday = new Date(d.getFullYear(), d.getMonth(), d.getDate());
```

```
  const command = new DescribeCasesCommand({
    includeCommunications: false,
    afterTime: startOfToday.toISOString(),
    includeResolvedCases: true,
  });
  const { cases, nextToken } = await client.send(command);
  await findCase({ cases, caseId: caseIdToWaitFor, nextToken });
  return cases.filter((c) => c.status === "resolved");
};

const main = async () => {
  let caseId;
  try {
    console.log(wrapText("Welcome to the AWS Support basic usage scenario."));

    // Verify that the account is subscribed to support.
    await verifyAccount();

    // Provided a truncated list of services and prompt the user to select one.
    const selectedService = await getService();

    // Provided the categories for the selected service and prompt the user to
 select one.
    const selectedCategory = await getCategory(selectedService);

    // Provide the severity available severity levels for the account and prompt
 the user to select one.
    const selectedSeverityLevel = await getSeverityLevel();

    // Create a support case.
    console.log("\nCreating a support case.");
    caseId = await createCase({
      selectedService,
      selectedCategory,
      selectedSeverityLevel,
    });
    console.log(`Support case created: ${caseId}`);

    // Display a list of open support cases created today.
    const todaysOpenCases = await retry(
      { intervalInMs: 1000, maxRetries: 15 },
      getTodaysOpenCases
    );
    console.log(
```

```
      `\nOpen support cases created today: ${todaysOpenCases.length}`
    );
    console.log(todaysOpenCases.map((c) => `${c.caseId}`).join("\n"));

    // Create an attachment set.
    console.log("\nCreating an attachment set.");
    const attachmentSetId = await createAttachmentSet();
    console.log(`Attachment set created: ${attachmentSetId}`);

    // Add the attachment set to the support case.
    console.log(`\nAdding attachment set to ${caseId}`);
    await linkAttachmentSetToCase(attachmentSetId, caseId);
    console.log(`Attachment set added to ${caseId}`);

    // List the communications for a support case.
    console.log(`\nListing communications for ${caseId}`);
    const communications = await getCommunications(caseId);
    console.log(
      communications
        .map(
          (c) =>
            `Communication created on ${c.timeCreated}. Has
${c.attachmentSet.length} attachments.`
        )
        .join("\n")
    );

    // Describe the first attachment.
    console.log(`\nDescribing attachment ${attachmentSetId}`);
    const attachmentId = getFirstAttachment(communications);
    const attachment = await getAttachment(attachmentId);
    console.log(
      `Attachment is the file '${
        attachment.fileName
      }' with data: \n${new TextDecoder().decode(attachment.data)}`
    );

    // Confirm that the support case should be resolved.
    const isResolved = await resolveCase(caseId);
    if (isResolved) {
      // List the resolved cases and include the one previously created.
      // Resolved cases can take a while to appear.
      console.log(
```

```
        "\nWaiting for case status to be marked as resolved. This can take some
 time."
      );
      const resolvedCases = await retry(
        { intervalInMs: 20000, maxRetries: 15 },
        () => getTodaysResolvedCases(caseId)
      );
      console.log("Resolved cases:");
      console.log(resolvedCases.map((c) => c.caseId).join("\n"));
    }
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Kotlin

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
In addition, you must have the AWS Business Support Plan to use the AWS Support
 Java API. For more information, see:

https://aws.amazon.com/premiumsupport/plans/

This Kotlin example performs the following tasks:
1. Gets and displays available services.
2. Gets and displays severity levels.
3. Creates a support case by using the selected service, category, and severity
 level.
4. Gets a list of open cases for the current day.
5. Creates an attachment set with a generated file.
6. Adds a communication with the attachment to the support case.
7. Lists the communications of the support case.
8. Describes the attachment set included with the communication.
9. Resolves the support case.
10. Gets a list of resolved cases for the current day.
*/

suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <fileAttachment>
    Where:
         fileAttachment - The file can be a simple saved .txt file to use as an
 email attachment.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val fileAttachment = args[0]
    println("***** Welcome to the AWS Support case example scenario.")
    println("***** Step 1. Get and display available services.")
```

```
    val sevCatList = displayServices()

    println("***** Step 2. Get and display Support severity levels.")
    val sevLevel = displaySevLevels()

    println("***** Step 3. Create a support case using the selected service,
 category, and severity level.")
    val caseIdVal = createSupportCase(sevCatList, sevLevel)
    if (caseIdVal != null) {
        println("Support case $caseIdVal was successfully created!")
    } else {
        println("A support case was not successfully created!")
        exitProcess(1)
    }

    println("***** Step 4. Get open support cases.")
    getOpenCase()

    println("***** Step 5. Create an attachment set with a generated file to add
 to the case.")
    val attachmentSetId = addAttachment(fileAttachment)
    println("The Attachment Set id value is $attachmentSetId")

    println("***** Step 6. Add communication with the attachment to the support
 case.")
    addAttachSupportCase(caseIdVal, attachmentSetId)

    println("***** Step 7. List the communications of the support case.")
    val attachId = listCommunications(caseIdVal)
    println("The Attachment id value is $attachId")

    println("***** Step 8. Describe the attachment set included with the
 communication.")
    describeAttachment(attachId)

    println("***** Step 9. Resolve the support case.")
    resolveSupportCase(caseIdVal)

    println("***** Step 10. Get a list of resolved cases for the current day.")
    getResolvedCase()
    println("***** This Scenario has successfully completed")
}

suspend fun getResolvedCase() {
```

```
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 30
        afterTime = yesterday.toString()
        beforeTime = now.toString()
        includeResolvedCases = true
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}

suspend fun resolveSupportCase(caseIdVal: String) {
    val caseRequest = ResolveCaseRequest {
        caseId = caseIdVal
    }
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.resolveCase(caseRequest)
        println("The status of case $caseIdVal is ${response.finalCaseStatus}")
    }
}

suspend fun describeAttachment(attachId: String?) {
    val attachmentRequest = DescribeAttachmentRequest {
        attachmentId = attachId
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeAttachment(attachmentRequest)
        println("The name of the file is ${response.attachment?.fileName}")
    }
}

suspend fun listCommunications(caseIdVal: String?): String? {
    val communicationsRequest = DescribeCommunicationsRequest {
```

```
        caseId = caseIdVal
        maxResults = 10
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response =
 supportClient.describeCommunications(communicationsRequest)
        response.communications?.forEach { comm ->
            println("the body is: " + comm.body)
            comm.attachmentSet?.forEach { detail ->
                return detail.attachmentId
            }
        }
    }
    return ""
}

suspend fun addAttachSupportCase(caseIdVal: String?, attachmentSetIdVal: String?)
 {
    val caseRequest = AddCommunicationToCaseRequest {
        caseId = caseIdVal
        attachmentSetId = attachmentSetIdVal
        communicationBody = "Please refer to attachment for details."
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addCommunicationToCase(caseRequest)
        if (response.result) {
            println("You have successfully added a communication to an AWS
 Support case")
        } else {
            println("There was an error adding the communication to an AWS
 Support case")
        }
    }
}

suspend fun addAttachment(fileAttachment: String): String? {
    val myFile = File(fileAttachment)
    val sourceBytes = (File(fileAttachment).readBytes())
    val attachmentVal = Attachment {
        fileName = myFile.name
        data = sourceBytes
    }
```

```
    val setRequest = AddAttachmentsToSetRequest {
        attachments = listOf(attachmentVal)
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addAttachmentsToSet(setRequest)
        return response.attachmentSetId
    }
}

suspend fun getOpenCase() {
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 20
        afterTime = yesterday.toString()
        beforeTime = now.toString()
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}

suspend fun createSupportCase(sevCatListVal: List<String>, sevLevelVal: String):
 String? {
    val serCode = sevCatListVal[0]
    val caseCategory = sevCatListVal[1]
    val caseRequest = CreateCaseRequest {
        categoryCode = caseCategory.lowercase(Locale.getDefault())
        serviceCode = serCode.lowercase(Locale.getDefault())
        severityCode = sevLevelVal.lowercase(Locale.getDefault())
        communicationBody = "Test issue with
 ${serCode.lowercase(Locale.getDefault())}"
        subject = "Test case, please ignore"
        language = "en"
```

```
        issueType = "technical"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.createCase(caseRequest)
        return response.caseId
    }
}

suspend fun displaySevLevels(): String {
    var levelName = ""
    val severityLevelsRequest = DescribeSeverityLevelsRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response =
 supportClient.describeSeverityLevels(severityLevelsRequest)
        response.severityLevels?.forEach { sevLevel ->
            println("The severity level name is: ${sevLevel.name}")
            if (sevLevel.name == "High") {
                levelName = sevLevel.name!!
            }
        }
        return levelName
    }
}

// Return a List that contains a Service name and Category name.
suspend fun displayServices(): List<String> {
    var serviceCode = ""
    var catName = ""
    val sevCatList = mutableListOf<String>()
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
```

```
                return@forEach
            }

            println("The Service name is ${service.name}")
            if (service.name == "Account") {
                serviceCode = service.code.toString()
            }

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                if (cat.name == "Security") {
                    catName = cat.name!!
                }
            }
            index++
        }
    }

    // Push the two values to the list.
    serviceCode.let { sevCatList.add(it) }
    catName.let { sevCatList.add(it) }
    return sevCatList
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class SupportCasesScenario:
    """Runs an interactive scenario that shows how to get started using AWS
 Support."""

    def __init__(self, support_wrapper):
        """
        :param support_wrapper: An object that wraps AWS Support actions.
        """
        self.support_wrapper = support_wrapper

    def display_and_select_service(self):
        """
        Lists support services and prompts the user to select one.

        :return: The support service selected by the user.
        """
        print("-" * 88)
        services_list = self.support_wrapper.describe_services("en")
        print(f"AWS Support client returned {len(services_list)} services.")
        print("Displaying first 10 services:")

        service_choices = [svc["name"] for svc in services_list[:10]]
        selected_index = q.choose(
            "Select an example support service by entering a number from the
 preceding list:",
            service_choices,
        )
        selected_service = services_list[selected_index]
        print("-" * 88)
        return selected_service
```

```
    def display_and_select_category(self, service):
        """
        Lists categories for a support service and prompts the user to select
one.

        :param service: The service of the categories.
        :return: The selected category.
        """
        print("-" * 88)
        print(
            f"Available support categories for Service {service['name']}
{len(service['categories'])}:"
        )
        categories_choices = [category["name"] for category in
service["categories"]]
        selected_index = q.choose(
            "Select an example support category by entering a number from the
preceding list:",
            categories_choices,
        )
        selected_category = service["categories"][selected_index]
        print("-" * 88)
        return selected_category

    def display_and_select_severity(self):
        """
        Lists available severity levels and prompts the user to select one.

        :return: The selected severity level.
        """
        print("-" * 88)
        severity_levels_list =
self.support_wrapper.describe_severity_levels("en")
        print(f"Available severity levels:")
        severity_choices = [level["name"] for level in severity_levels_list]
        selected_index = q.choose(
            "Select an example severity level by entering a number from the
preceding list:",
            severity_choices,
        )
        selected_severity = severity_levels_list[selected_index]
        print("-" * 88)
        return selected_severity
```

```
    def create_example_case(self, service, category, severity_level):
        """
        Creates an example support case with the user's selections.

        :param service: The service for the new case.
        :param category: The category for the new case.
        :param severity_level: The severity level for the new case.
        :return: The caseId of the new support case.
        """
        print("-" * 88)
        print(f"Creating new case for service {service['name']}.")
        case_id = self.support_wrapper.create_case(service, category,
severity_level)
        print(f"\tNew case created with ID {case_id}.")
        print("-" * 88)
        return case_id

    def list_open_cases(self):
        """
        List the open cases for the current day.
        """
        print("-" * 88)
        print("Let's list the open cases for the current day.")
        start_time = str(datetime.utcnow().date())
        end_time = str(datetime.utcnow().date() + timedelta(days=1))
        open_cases = self.support_wrapper.describe_cases(start_time, end_time,
False)
        for case in open_cases:
            print(f"\tCase: {case['caseId']}: status {case['status']}.")
        print("-" * 88)

    def create_attachment_set(self):
        """
        Create an attachment set with a sample file.

        :return: The attachment set ID of the new attachment set.
        """
        print("-" * 88)
        print("Creating attachment set with a sample file.")
        attachment_set_id = self.support_wrapper.add_attachment_to_set()
        print(f"\tNew attachment set created with ID {attachment_set_id}.")
        print("-" * 88)
        return attachment_set_id
```

```
    def add_communication(self, case_id, attachment_set_id):
        """
        Add a communication with an attachment set to the case.

        :param case_id: The ID of the case for the communication.
        :param attachment_set_id: The ID of the attachment set to
        add to the communication.
        """
        print("-" * 88)
        print(f"Adding a communication and attachment set to the case.")
        self.support_wrapper.add_communication_to_case(attachment_set_id,
case_id)
        print(
            f"Added a communication and attachment set {attachment_set_id} to the
case {case_id}."
        )
        print("-" * 88)

    def list_communications(self, case_id):
        """
        List the communications associated with a case.

        :param case_id: The ID of the case.
        :return: The attachment ID of an attachment.
        """
        print("-" * 88)
        print("Let's list the communications for our case.")
        attachment_id = ""
        communications =
self.support_wrapper.describe_all_case_communications(case_id)
        for communication in communications:
            print(
                f"\tCommunication created on {communication['timeCreated']} "
                f"has {len(communication['attachmentSet'])} attachments."
            )
            if len(communication["attachmentSet"]) > 0:
                attachment_id = communication["attachmentSet"][0]["attachmentId"]
        print("-" * 88)
        return attachment_id

    def describe_case_attachment(self, attachment_id):
        """
        Describe an attachment associated with a case.
```

```
        :param attachment_id: The ID of the attachment.
        """
        print("-" * 88)
        print("Let's list the communications for our case.")
        attached_file = self.support_wrapper.describe_attachment(attachment_id)
        print(f"\tAttachment includes file {attached_file}.")
        print("-" * 88)

    def resolve_case(self, case_id):
        """
        Shows how to resolve an AWS Support case by its ID.

        :param case_id: The ID of the case to resolve.
        """
        print("-" * 88)
        print(f"Resolving case with ID {case_id}.")
        case_status = self.support_wrapper.resolve_case(case_id)
        print(f"\tFinal case status is {case_status}.")
        print("-" * 88)

    def list_resolved_cases(self):
        """
        List the resolved cases for the current day.
        """
        print("-" * 88)
        print("Let's list the resolved cases for the current day.")
        start_time = str(datetime.utcnow().date())
        end_time = str(datetime.utcnow().date() + timedelta(days=1))
        resolved_cases = self.support_wrapper.describe_cases(start_time,
end_time, True)
        for case in resolved_cases:
            print(f"\tCase: {case['caseId']}: status {case['status']}.")
        print("-" * 88)

    def run_scenario(self):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s:
%(message)s")

        print("-" * 88)
        print("Welcome to the AWS Support get started with support cases demo.")
        print("-" * 88)

        selected_service = self.display_and_select_service()
        selected_category = self.display_and_select_category(selected_service)
```

```
        selected_severity = self.display_and_select_severity()
        new_case_id = self.create_example_case(
            selected_service, selected_category, selected_severity
        )
        wait(10)
        self.list_open_cases()
        new_attachment_set_id = self.create_attachment_set()
        self.add_communication(new_case_id, new_attachment_set_id)
        new_attachment_id = self.list_communications(new_case_id)
        self.describe_case_attachment(new_attachment_id)
        self.resolve_case(new_case_id)
        wait(10)
        self.list_resolved_cases()

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = SupportCasesScenario(SupportWrapper.from_client())
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Definir uma classe que envolva ações de suporte ao cliente.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
```

```
        return cls(support_client)


    def describe_services(self, language):
        """
        Get the descriptions of AWS services available for support for a
language.

        :param language: The language for support services.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of AWS service descriptions.
        """
        try:
            response = self.support_client.describe_services(language=language)
            services = response["services"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get Support services for language %s. Here's why:
%s: %s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return services


    def describe_severity_levels(self, language):
        """
        Get the descriptions of available severity levels for support cases for a
language.

        :param language: The language for support severity levels.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
```

```
        :return: The list of severity levels.
        """
        try:
            response =
self.support_client.describe_severity_levels(language=language)
            severity_levels = response["severityLevels"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get severity levels for language %s. Here's why:
%s: %s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return severity_levels


    def create_case(self, service, category, severity):
        """
        Create a new support case.

        :param service: The service to use for the new case.
        :param category: The category to use for the new case.
        :param severity: The severity to use for the new case.
        :return: The caseId of the new case.
        """
        try:
            response = self.support_client.create_case(
                subject="Example case for testing, ignore.",
                serviceCode=service["code"],
                severityCode=severity["code"],
                categoryCode=category["code"],
                communicationBody="Example support case body.",
```

```
                language="en",
                issueType="customer-service",
            )
            case_id = response["caseId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't create case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return case_id


    def add_attachment_to_set(self):
        """
        Add an attachment to a set, or create a new attachment set if one does
not exist.

        :return: The attachment set ID.
        """
        try:
            response = self.support_client.add_attachments_to_set(
                attachments=[
                    {
                        "fileName": "attachment_file.txt",
                        "data": b"This is a sample file for attachment to a
support case.",
                    }
                ]
            )
            new_set_id = response["attachmentSetId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
```

```
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add attachment. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return new_set_id


    def add_communication_to_case(self, attachment_set_id, case_id):
        """
        Add a communication and an attachment set to a case.

        :param attachment_set_id: The ID of an existing attachment set.
        :param case_id: The ID of the case.
        """
        try:
            self.support_client.add_communication_to_case(
                caseId=case_id,
                communicationBody="This is an example communication added to a
support case.",
                attachmentSetId=attachment_set_id,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add communication. Here's why: %s: %s",
```

```
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise


    def describe_all_case_communications(self, case_id):
        """
        Describe all the communications for a case using a paginator.

        :param case_id: The ID of the case.
        :return: The communications for the case.
        """
        try:
            communications = []
            paginator =
self.support_client.get_paginator("describe_communications")
            for page in paginator.paginate(caseId=case_id):
                communications += page["communications"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe communications. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return communications


    def describe_attachment(self, attachment_id):
        """
        Get information about an attachment by its attachmentID.

        :param attachment_id: The ID of the attachment.
```

```
        :return: The name of the attached file.
        """
        try:
            response = self.support_client.describe_attachment(
                attachmentId=attachment_id
            )
            attached_file = response["attachment"]["fileName"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get attachment description. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return attached_file


    def resolve_case(self, case_id):
        """
        Resolve a support case by its caseId.

        :param case_id: The ID of the case to resolve.
        :return: The final status of the case.
        """
        try:
            response = self.support_client.resolve_case(caseId=case_id)
            final_status = response["finalCaseStatus"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
```

```
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't resolve case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return final_status


    def describe_cases(self, after_time, before_time, resolved):
        """
        Describe support cases over a period of time, optionally filtering
        by status.

        :param after_time: The start time to include for cases.
        :param before_time: The end time to include for cases.
        :param resolved: True to include resolved cases in the results,
            otherwise results are open cases.
        :return: The final status of the case.
        """
        try:
            cases = []
            paginator = self.support_client.get_paginator("describe_cases")
            for page in paginator.paginate(
                afterTime=after_time,
                beforeTime=before_time,
                includeResolvedCases=resolved,
                language="en",
            ):
                cases += page["cases"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
```

```
                logger.error(
                    "Couldn't describe cases. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            if resolved:
                cases = filter(lambda case: case["status"] == "resolved", cases)
            return cases
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Exemplos de código para o Systems Manager usando SDKs da AWS

Os exemplos de código a seguir mostram como usar AWS Systems Manager com um kit de desenvolvimento de software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia do usuário do Systems Manager – Mais informações sobre o Systems Manager.
- Referência da API do Systems Manager – Detalhes sobre todas as ações disponíveis do Systems Manager.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para o Systems Manager usando SDKs da AWS
  - Adicionar um parâmetro do Systems Manager usando um SDK da AWS
  - Crie um novo OpsItem usando um AWS SDK
  - Descrever e OpsItem usar um AWS SDK
  - Obtenha informações sobre os parâmetros do Systems Manager usando um SDK da AWS
  - Atualizações e OpsItem uso de um AWS SDK

Ações para o Systems Manager usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o AWS Systems Manager com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos

- Adicionar um parâmetro do Systems Manager usando um SDK da AWS
- Crie um novo OpsItem usando um AWS SDK
- Descrever e OpsItem usar um AWS SDK
- Obtenha informações sobre os parâmetros do Systems Manager usando um SDK da AWS
- Atualizações e OpsItem uso de um AWS SDK

Adicionar um parâmetro do Systems Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como adicionar um parâmetro do Systems Manager.

CLI

AWS CLI

Exemplo 1: como alterar o valor de um parâmetro

O exemplo de `put-parameter` a seguir altera o valor do parâmetro especificado.

```
aws ssm put-parameter \
    --name "MyStringParameter" \
    --type "String" \
    --value "Vici" \
    --overwrite
```

Saída:

```
{
    "Version": 2,
    "Tier": "Standard"
}
```

Para obter mais informações, consulte Criar um parâmetro do Systems Manager (AWSCLI), “Gerenciando camadas de parâmetros < https://docs.aws.amazon.com/systems-manager/latest/userguide/ parameter-store-advanced-parameters .html>`__ e Trabalhando com políticas de parâmetros no Guia do usuário do Systems Manager. AWS

Exemplo 2: como criar um parâmetro avançado

O exemplo de `put-parameter` a seguir cria um parâmetro avançado.

```
aws ssm put-parameter \
    --name "MyAdvancedParameter" \
    --description "This is an advanced parameter" \
    --value "Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do
 eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim
 veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo
 consequat [truncated]" \
    --type "String" \
    --tier Advanced
```

Saída:

```
{
    "Version": 1,
    "Tier": "Advanced"
}
```

Para obter mais informações, consulte Criar um parâmetro do Systems Manager (AWSCLI), “Gerenciando camadas de parâmetros < https://docs.aws.amazon.com/systems-manager/latest/userguide/ parameter-store-advanced-parameters .html>`__ e Trabalhando com políticas de parâmetros no Guia do usuário do Systems Manager. AWS

Exemplo 3: como converter um parâmetro padrão em um parâmetro avançado

O exemplo de `put-parameter` a seguir converte um parâmetro padrão existente em um parâmetro avançado.

```
aws ssm put-parameter \
    --name "MyConvertedParameter" \
    --value "abc123" \
    --type "String" \
    --tier Advanced \
    --overwrite
```

Saída:

```
{
    "Version": 2,
    "Tier": "Advanced"
}
```

Para obter mais informações, consulte Criar um parâmetro do Systems Manager (AWSCLI), “Gerenciando camadas de parâmetros < https://docs.aws.amazon.com/systems-manager/latest/userguide/ parameter-store-advanced-parameters .html>`__ e Trabalhando com políticas de parâmetros no Guia do usuário do Systems Manager. AWS

Exemplo 4: como criar um parâmetro com uma política anexada

O exemplo de `put-parameter` a seguir cria um parâmetro avançado com uma política de parâmetros anexada.

```
aws ssm put-parameter \
    --name "/Finance/Payroll/q2accesskey" \
```

```
    --value "P@sSwW)rd" \
    --type "SecureString" \
    --tier Advanced \
    --policies "[{\"Type\":\"Expiration\",\"Version\":\"1.0\",\"Attributes\":
{\"Timestamp\":\"2020-06-30T00:00:00.000Z\"}},{\"Type\":\"ExpirationNotification
\",\"Version\":\"1.0\",\"Attributes\":{\"Before\":\"5\",\"Unit\":\"Days\"}},
{\"Type\":\"NoChangeNotification\",\"Version\":\"1.0\",\"Attributes\":{\"After\":
\"60\",\"Unit\":\"Days\"}}]"
```

Saída:

```
{
    "Version": 1,
    "Tier": "Advanced"
}
```

Para obter mais informações, consulte Criar um parâmetro do Systems Manager (AWSCLI), “Gerenciando camadas de parâmetros < https://docs.aws.amazon.com/systems-manager/latest/userguide/ parameter-store-advanced-parameters .html>`__ e Trabalhando com políticas de parâmetros no Guia do usuário do Systems Manager. AWS

Exemplo 5: como adicionar uma política a um parâmetro existente

O exemplo de `put-parameter` a seguir anexa uma política a um parâmetro avançado existente.

```
aws ssm put-parameter \
    --name "/Finance/Payroll/q2accesskey" \
    --value "N3wP@sSwW)rd" \
    --type "SecureString" \
    --tier Advanced \
    --policies "[{\"Type\":\"Expiration\",\"Version\":\"1.0\",\"Attributes\":
{\"Timestamp\":\"2020-06-30T00:00:00.000Z\"}},{\"Type\":\"ExpirationNotification
\",\"Version\":\"1.0\",\"Attributes\":{\"Before\":\"5\",\"Unit\":\"Days\"}},
{\"Type\":\"NoChangeNotification\",\"Version\":\"1.0\",\"Attributes\":{\"After\":
\"60\",\"Unit\":\"Days\"}}]"
    --overwrite
```

Saída:

```
{
    "Version": 2,
```

```
    "Tier": "Advanced"
}
```

Para obter mais informações, consulte Criar um parâmetro do Systems Manager (AWSCLI), “Gerenciando camadas de parâmetros < https://docs.aws.amazon.com/systems-manager/latest/userguide/ parameter-store-advanced-parameters .html>`__ e Trabalhando com políticas de parâmetros no Guia do usuário do Systems Manager. AWS

- Para obter detalhes da API, consulte PutParameterem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.ParameterType;
import software.amazon.awssdk.services.ssm.model.PutParameterRequest;
import software.amazon.awssdk.services.ssm.model.SsmException;

public class PutParameter {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <paraName>

                Where:
                    paraName - The name of the parameter.
                    paraValue - The value of the parameter.
                """;

        if (args.length != 2) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String paraName = args[0];
        String paraValue = args[1];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        putParaValue(ssmClient, paraName, paraValue);
        ssmClient.close();
    }

    public static void putParaValue(SsmClient ssmClient, String paraName, String
 value) {
        try {
            PutParameterRequest parameterRequest = PutParameterRequest.builder()
                    .name(paraName)
                    .type(ParameterType.STRING)
                    .value(value)
                    .build();

            ssmClient.putParameter(parameterRequest);
            System.out.println("The parameter was successfully added.");

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutParameter a Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_parameter(
    client: &Client,
    name: &str,
    value: &str,
    description: &str,
) -> Result<(), Error> {
    let resp = client
        .put_parameter()
        .overwrite(true)
        .r#type(ParameterType::String)
        .name(name)
        .value(value)
        .description(description)
        .send()
        .await?;

    println!("Success! Parameter now has version: {}", resp.version());

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutParameterreferência da API AWS SDK for Rust.

Crie um novo OpsItem usando um AWS SDK

Os exemplos de código a seguir mostram como criar um novo OpsItem.

CLI

AWS CLI

Para criar um OpsItems

O `create-ops-item` exemplo a seguir usa a chave /aws/resources OperationalData para criar um OpsItem com um recurso relacionado ao Amazon DynamoDB.

```
aws ssm create-ops-item \
    --title "EC2 instance disk full" \
    --description "Log clean up may have failed which caused the disk to be full"
 \
    --priority 2 \
    --source ec2 \
    --operational-data '{"/aws/resources":{"Value":"[{\"arn
\": \"arn:aws:dynamodb:us-west-2:12345678:table/OpsItems
\"}]","Type":"SearchableString"}}' \
    --notifications Arn="arn:aws:sns:us-west-2:12345678:TestUser"
```

Saída:

```
{
    "OpsItemId": "oi-1a2b3c4d5e6f"
}
```

Para obter mais informações, consulte Creating OpsItems in the AWSSystems Manager User Guide.

- Para obter detalhes da API, consulte CreateOpsItemem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.CreateOpsItemRequest;
import software.amazon.awssdk.services.ssm.model.CreateOpsItemResponse;
import software.amazon.awssdk.services.ssm.model.SsmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class CreateOpsItem {
    public static void main(String[] args) {

        final String USAGE = """

                Usage:
                    <title> <source> <category> <severity>

                Where:
                    title - The OpsItem title.
                    source - The origin of the OpsItem, such as Amazon EC2 or AWS
 Systems Manager.
                    category - A category to assign to an OpsItem.
                    severity - A severity to assign to an OpsItem.
                """;

        if (args.length != 4) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String title = args[0];
        String source = args[1];
        String category = args[2];
        String severity = args[3];

        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
```

```
                .region(region)
                .build();

        System.out
                .println("The Id of the OpsItem is " +
 createNewOpsItem(ssmClient, title, source, category, severity));
        ssmClient.close();
    }

    public static String createNewOpsItem(SsmClient ssmClient,
            String title,
            String source,
            String category,
            String severity) {

        try {
            CreateOpsItemRequest opsItemRequest = CreateOpsItemRequest.builder()
                    .description("Created by the SSM Java API")
                    .title(title)
                    .source(source)
                    .category(category)
                    .severity(severity)
                    .build();

            CreateOpsItemResponse itemResponse =
 ssmClient.createOpsItem(opsItemRequest);
            return itemResponse.opsItemId();

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateOpsItema Referência AWS SDK for Java 2.x da API.

Descrever e OpsItem usar um AWS SDK

Os exemplos de código a seguir mostram como descrever um OpsItem.

CLI

AWS CLI

Para listar um conjunto de OpsItems

O `describe-ops-items` exemplo a seguir exibe uma lista de todos os abertos OpsItems em sua AWS conta.

```
aws ssm describe-ops-items \
    --ops-item-filters "Key=Status,Values=Open,Operator=Equal"
```

Saída:

```
{
    "OpsItemSummaries": [
        {
            "CreatedBy": "arn:aws:sts::111222333444:assumed-role/OpsItem-CWE-
Role/fbf77cbe264a33509569f23e4EXAMPLE",
            "CreatedTime": "2020-03-14T17:02:46.375000-07:00",
            "LastModifiedBy": "arn:aws:sts::111222333444:assumed-role/OpsItem-
CWE-Role/fbf77cbe264a33509569f23e4EXAMPLE",
            "LastModifiedTime": "2020-03-14T17:02:46.375000-07:00",
            "Source": "SSM",
            "Status": "Open",
            "OpsItemId": "oi-7cfc5EXAMPLE",
            "Title": "SSM Maintenance Window execution failed",
            "OperationalData": {
                "/aws/dedup": {
                    "Value": "{\"dedupString\":\"SSMOpsItems-SSM-maintenance-
window-execution-failed\"}",
                    "Type": "SearchableString"
                },
                "/aws/resources": {
                    "Value": "[{\"arn\":\"arn:aws:ssm:us-
east-2:111222333444:maintenancewindow/mw-034093d322EXAMPLE\"}]",
                    "Type": "SearchableString"
                }
            },
            "Category": "Availability",
            "Severity": "3"
        },
        {
```

```
            "CreatedBy": "arn:aws:sts::1112223233444:assumed-role/OpsItem-CWE-
Role/fbf77cbe264a33509569f23e4EXAMPLE",
            "CreatedTime": "2020-02-26T11:43:15.426000-08:00",
            "LastModifiedBy": "arn:aws:sts::111222333444:assumed-role/OpsItem-
CWE-Role/fbf77cbe264a33509569f23e4EXAMPLE",
            "LastModifiedTime": "2020-02-26T11:43:15.426000-08:00",
            "Source": "EC2",
            "Status": "Open",
            "OpsItemId": "oi-6f966EXAMPLE",
            "Title": "EC2 instance stopped",
            "OperationalData": {
                "/aws/automations": {
                    "Value": "[ { \"automationType\": \"AWS:SSM:Automation\",
 \"automationId\": \"AWS-RestartEC2Instance\" } ]",
                    "Type": "SearchableString"
                },
                "/aws/dedup": {
                    "Value": "{\"dedupString\":\"SSMOpsItems-EC2-instance-stopped
\"}",
                    "Type": "SearchableString"
                },
                "/aws/resources": {
                    "Value": "[{\"arn\":\"arn:aws:ec2:us-
east-2:111222333444:instance/i-0beccfbc02EXAMPLE\"}]",
                    "Type": "SearchableString"
                }
            },
            "Category": "Availability",
            "Severity": "3"
        }
    ]
}
```

Para obter mais informações, consulte Trabalhando com OpsItems no Guia do Usuário do AWS Systems Manager.

- Para obter detalhes da API, consulte DescribeOpsItemsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.DescribeOpsItemsRequest;
import software.amazon.awssdk.services.ssm.model.DescribeOpsItemsResponse;
import software.amazon.awssdk.services.ssm.model.OpsItemSummary;
import software.amazon.awssdk.services.ssm.model.SsmException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DescribeOpsItems {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        describeItems(ssmClient);
        ssmClient.close();
    }

    public static void describeItems(SsmClient ssmClient) {
        try {
```

```
            DescribeOpsItemsRequest itemsRequest =
 DescribeOpsItemsRequest.builder()
                    .maxResults(10)
                    .build();

            DescribeOpsItemsResponse itemsResponse =
 ssmClient.describeOpsItems(itemsRequest);
            List<OpsItemSummary> items = itemsResponse.opsItemSummaries();
            for (OpsItemSummary item : items) {
                System.out.println("The item title is " + item.title());
            }

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeOpsItemsa Referência AWS SDK for Java 2.x da API.

Obtenha informações sobre os parâmetros do Systems Manager usando um SDK da AWS

Os exemplos de código a seguir mostram como obter informações de parâmetros do Systems Manager.

CLI

AWS CLI

Exemplo 1: como listar todos os parâmetros

O exemplo de `describe-parameters` a seguir lista todos os parâmetros na conta e região atuais da AWS.

```
aws ssm describe-parameters
```

Saída:

```
{
    "Parameters": [
        {
            "Name": "MySecureStringParameter",
            "Type": "SecureString",
            "KeyId": "alias/aws/ssm",
            "LastModifiedDate": 1582155479.205,
            "LastModifiedUser": "arn:aws:sts::111222333444:assumed-role/Admin/
Richard-Roe-Managed",
            "Description": "This is a SecureString parameter",
            "Version": 2,
            "Tier": "Advanced",
            "Policies": [
                {
                    "PolicyText": "{\"Type\":\"Expiration\",\"Version\":\"1.0\",
\"Attributes\":{\"Timestamp\":\"2020-07-07T22:30:00Z\"}}",
                    "PolicyType": "Expiration",
                    "PolicyStatus": "Pending"
                },
                {
                    "PolicyText": "{\"Type\":\"ExpirationNotification\",\"Version
\":\"1.0\",\"Attributes\":{\"Before\":\"12\",\"Unit\":\"Hours\"}}",
                    "PolicyType": "ExpirationNotification",
                    "PolicyStatus": "Pending"
                }
            ]
        },
        {
            "Name": "MyStringListParameter",
            "Type": "StringList",
            "LastModifiedDate": 1582154764.222,
            "LastModifiedUser": "arn:aws:iam::111222333444:user/Mary-Major",
            "Description": "This is a StringList parameter",
            "Version": 1,
            "Tier": "Standard",
            "Policies": []
        },
        {
            "Name": "MyStringParameter",
            "Type": "String",
            "LastModifiedDate": 1582154711.976,
            "LastModifiedUser": "arn:aws:iam::111222333444:user/Alejandro-
Rosalez",
```

```
            "Description": "This is a String parameter",
            "Version": 1,
            "Tier": "Standard",
            "Policies": []
        },
        {
            "Name": "latestAmi",
            "Type": "String",
            "LastModifiedDate": 1580862415.521,
            "LastModifiedUser": "arn:aws:sts::111222333444:assumed-role/lambda-
ssm-role/Automation-UpdateSSM-Param",
            "Version": 3,
            "Tier": "Standard",
            "Policies": []
        }
    ]
}
```

Exemplo 2: como listar todos os parâmetros que correspondem a metadados específicos

Este exemplo de `describe-parameters` lista todos os parâmetros que correspondem a um filtro.

aws ssm describe-parameters --filters “Chave = Tipo, Valores =” StringList

Saída:

```
{
    "Parameters": [
        {
            "Name": "MyStringListParameter",
            "Type": "StringList",
            "LastModifiedDate": 1582154764.222,
            "LastModifiedUser": "arn:aws:iam::111222333444:user/Mary-Major",
            "Description": "This is a StringList parameter",
            "Version": 1,
            "Tier": "Standard",
            "Policies": []
        }
    ]
}
```

Para obter mais informações, consulte Pesquisando parâmetros do Systems Manager, no Guia do usuário do AWS Systems Manager.

- Para obter detalhes da API, consulte DescribeParametersem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.GetParameterRequest;
import software.amazon.awssdk.services.ssm.model.GetParameterResponse;
import software.amazon.awssdk.services.ssm.model.SsmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class GetParameter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <paraName>

                Where:
                    paraName - The name of the parameter.
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String paraName = args[0];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        getParaValue(ssmClient, paraName);
        ssmClient.close();
    }

    public static void getParaValue(SsmClient ssmClient, String paraName) {
        try {
            GetParameterRequest parameterRequest = GetParameterRequest.builder()
                    .name(paraName)
                    .build();

            GetParameterResponse parameterResponse =
 ssmClient.getParameter(parameterRequest);
            System.out.println("The parameter value is " +
 parameterResponse.parameter().value());

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeParametersa Referência AWS SDK for Java 2.x da API.

Rust

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_parameters(client: &Client) -> Result<(), Error> {
    let resp = client.describe_parameters().send().await?;

    for param in resp.parameters() {
        println!("  {}", param.name().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeParametersreferência da API AWS SDK for Rust.

Atualizações e OpsItem uso de um AWS SDK

Os exemplos de código a seguir mostram como atualizar um OpsItem.

CLI

AWS CLI

Para atualizar um OpsItem

O `update-ops-item` exemplo a seguir atualiza a descrição, a prioridade e a categoria de um OpsItem. Além disso, o comando especifica um tópico do SNS para o qual as notificações são enviadas quando isso OpsItem é editado ou alterado.

```
aws ssm update-ops-item \
    --ops-item-id "oi-287b5EXAMPLE" \
```

```
    --description "Primary OpsItem for failover event 2020-01-01-fh398yf" \
    --priority 2 \
    --category "Security" \
    --notifications "Arn=arn:aws:sns:us-east-2:111222333444:my-us-east-2-topic"
```

Saída:

```
This command produces no output.
```

Para obter mais informações, consulte Trabalhando com OpsItems no Guia do Usuário do AWS Systems Manager.

- Para obter detalhes da API, consulte UpdateOpsItemem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.SsmException;
import software.amazon.awssdk.services.ssm.model.UpdateOpsItemRequest;
import software.amazon.awssdk.services.ssm.model.OpsItemStatus;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
```

```
public class ResolveOpsItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <opsID>

                Where:
                    opsID - The Ops item ID value.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String opsID = args[0];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();
        setOpsItemStatus(ssmClient, opsID);
    }

    public static void setOpsItemStatus(SsmClient ssmClient, String opsID) {
        try {
            UpdateOpsItemRequest opsItemRequest = UpdateOpsItemRequest.builder()
                    .opsItemId(opsID)
                    .status(OpsItemStatus.RESOLVED)
                    .build();

            ssmClient.updateOpsItem(opsItemRequest);

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateOpsItema Referência AWS SDK for Java 2.x da API.

Exemplos de código para o Amazon Textract usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Textract com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Textract – Mais informações sobre o Amazon Textract.
- Referência da API do Amazon Textract – Detalhes sobre todas as ações disponíveis do Amazon Textract.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Transcribe usando SDKs da AWS
  - Analise um documento usando o Amazon Textract e um SDK da AWS
  - Detecte texto em um documento usando o Amazon Textract e um SDK da AWS
  - Obtenha dados sobre um trabalho de análise de documentos do Amazon Textract usando um SDK da AWS
  - Inicie a análise assíncrona de um documento usando o Amazon Textract e um SDK da AWS
  - Inicie a detecção assíncrona de texto usando o Amazon Textract e um SDK da AWS
- Cenários para Amazon Textract usando SDKs da AWS
  - Comece a usar a análise de documentos do Amazon Textract usando um SDK da AWS

- Exemplos entre serviços do Amazon Textract usando SDKs da AWS
  - Criar uma aplicação de exploração do Amazon Textract
  - Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
  - Detectar entidades em texto extraído de uma imagem usando um AWS SDK

Ações do Amazon Transcribe usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Textract com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para Amazon Textract usando SDKs da AWS.

Exemplos

- Analise um documento usando o Amazon Textract e um SDK da AWS
- Detecte texto em um documento usando o Amazon Textract e um SDK da AWS
- Obtenha dados sobre um trabalho de análise de documentos do Amazon Textract usando um SDK da AWS
- Inicie a análise assíncrona de um documento usando o Amazon Textract e um SDK da AWS
- Inicie a detecção assíncrona de texto usando o Amazon Textract e um SDK da AWS

Analise um documento usando o Amazon Textract e um SDK da AWS

Os exemplos de código a seguir mostram como analisar um documento usando o Amazon Textract.

CLI

AWS CLI

Como analisar texto em um documento

O exemplo de `analyze-document` a seguir mostra como analisar texto em um documento.

Linux/macOS:

```
aws textract analyze-document \
    --document '{"S3Object":{"Bucket":"bucket","Name":"document"}}' \
```

```
    --feature-types '["TABLES","FORMS"]'
```

Windows:

```
aws textract analyze-document \
    --document "{\"S3Object\":{\"Bucket\":\"bucket\",\"Name\":\"document\"}}" \
    --feature-types "[\"TABLES\",\"FORMS\"]" \
    --region region-name
```

Saída:

```
{
    "Blocks": [
        {
            "Geometry": {
                "BoundingBox": {
                    "Width": 1.0,
                    "Top": 0.0,
                    "Left": 0.0,
                    "Height": 1.0
                },
                "Polygon": [
                    {
                        "Y": 0.0,
                        "X": 0.0
                    },
                    {
                        "Y": 0.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 0.0
                    }
                ]
            },
            "Relationships": [
                {
                    "Type": "CHILD",
```

```
                    "Ids": [
                        "87586964-d50d-43e2-ace5-8a890657b9a0",
                        "a1e72126-21d9-44f4-a8d6-5c385f9002ba",
                        "e889d012-8a6b-4d2e-b7cd-7a8b327d876a"
                    ]
                }
            ],
            "BlockType": "PAGE",
            "Id": "c2227f12-b25d-4e1f-baea-1ee180d926b2"
        }
    ],
    "DocumentMetadata": {
        "Pages": 1
    }
}
```

Para obter mais informações, consulte Analyzing Document Text with Amazon Textract Guia do desenvolvedor do Amazon Textract

- Para obter detalhes da API, consulte AnalyzeDocumentem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.AnalyzeDocumentRequest;
import software.amazon.awssdk.services.textract.model.Document;
import software.amazon.awssdk.services.textract.model.FeatureType;
import software.amazon.awssdk.services.textract.model.AnalyzeDocumentResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.TextractException;
import java.io.File;
```

```
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.ArrayList;
import java.util.Iterator;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class AnalyzeDocument {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <sourceDoc>\s

                Where:
                    sourceDoc - The path where the document is located (must be
 an image, for example, C:/AWS/book.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceDoc = args[0];
        Region region = Region.US_EAST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        analyzeDoc(textractClient, sourceDoc);
        textractClient.close();
    }
```

```
    public static void analyzeDoc(TextractClient textractClient, String
 sourceDoc) {
        try {
            InputStream sourceStream = new FileInputStream(new File(sourceDoc));
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Get the input Document object as bytes
            Document myDoc = Document.builder()
                    .bytes(sourceBytes)
                    .build();

            List<FeatureType> featureTypes = new ArrayList<FeatureType>();
            featureTypes.add(FeatureType.FORMS);
            featureTypes.add(FeatureType.TABLES);

            AnalyzeDocumentRequest analyzeDocumentRequest =
 AnalyzeDocumentRequest.builder()
                    .featureTypes(featureTypes)
                    .document(myDoc)
                    .build();

            AnalyzeDocumentResponse analyzeDocument =
 textractClient.analyzeDocument(analyzeDocumentRequest);
            List<Block> docInfo = analyzeDocument.blocks();
            Iterator<Block> blockIterator = docInfo.iterator();

            while (blockIterator.hasNext()) {
                Block block = blockIterator.next();
                System.out.println("The block type is " +
 block.blockType().toString());
            }

        } catch (TextractException | FileNotFoundException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte AnalyzeDocumenta Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def analyze_file(
        self, feature_types, *, document_file_name=None, document_bytes=None
    ):
        """
        Detects text and additional elements, such as forms or tables, in a local
 image
        file or from in-memory byte data.
        The image must be in PNG or JPG format.

        :param feature_types: The types of additional document features to
 detect.
        :param document_file_name: The name of a document image file.
        :param document_bytes: In-memory byte data of a document image.
        :return: The response from Amazon Textract, including a list of blocks
                 that describe elements detected in the image.
        """
        if document_file_name is not None:
            with open(document_file_name, "rb") as document_file:
```

```
                document_bytes = document_file.read()
        try:
            response = self.textract_client.analyze_document(
                Document={"Bytes": document_bytes}, FeatureTypes=feature_types
            )
            logger.info("Detected %s blocks.", len(response["Blocks"]))
        except ClientError:
            logger.exception("Couldn't detect text.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a AnalyzeDocumentReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"Detects text and additional elements, such as forms or tables,"
"in a local image file or from in-memory byte data."
"The image must be in PNG or JPG format."


"Create ABAP objects for feature type."
"Add TABLES to return information about the tables."
"Add FORMS to return detected form data."
"To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
  ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
  ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).
```

```
   "Create an ABAP object for the Amazon Simple Storage Service (Amazon S3)
object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_document) = NEW /aws1/cl_texdocument( io_s3object = lo_s3object ).

   "Analyze document stored in Amazon S3."
   TRY.
       oo_result = lo_tex->analyzedocument(      "oo_result is returned for
testing purposes."
         io_document        = lo_document
         it_featuretypes    = lt_featuretypes ).
       LOOP AT oo_result->get_blocks( ) INTO DATA(lo_block).
         IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
           MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
         ENDIF.
       ENDLOOP.
       MESSAGE 'Analyze document completed.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texhlquotaexceededex.
       MESSAGE 'Human loop quota exceeded.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.

     CATCH /aws1/cx_texinvalids3objectex.
       MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texprovthruputexcdex.
       MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
     CATCH /aws1/cx_texthrottlingex.
       MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
     CATCH /aws1/cx_texunsupporteddocex.
       MESSAGE 'The document is not supported.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a AnalyzeDocumentreferência da API AWS SDK for SAP ABAP.

Detecte texto em um documento usando o Amazon Textract e um SDK da AWS

Os exemplos de código a seguir mostram como detectar texto em um documento usando o Amazon Textract.

CLI

AWS CLI

Como detectar texto em um documento

O exemplo de `detect-document-text` a seguir mostra como detectar texto em um documento.

Linux/macOS:

```
aws textract detect-document-text \
    --document '{"S3Object":{"Bucket":"bucket","Name":"document"}}'
```

Windows:

```
aws textract detect-document-text \
    --document "{\"S3Object\":{\"Bucket\":\"bucket\",\"Name\":\"document\"}}" \
    --region region-name
```

Saída:

```
{
    "Blocks": [
        {
            "Geometry": {
                "BoundingBox": {
                    "Width": 1.0,
                    "Top": 0.0,
                    "Left": 0.0,
                    "Height": 1.0
                },
```

```
                "Polygon": [
                    {
                        "Y": 0.0,
                        "X": 0.0
                    },
                    {
                        "Y": 0.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 0.0
                    }
                ]
            },
            "Relationships": [
                {
                    "Type": "CHILD",
                    "Ids": [
                        "896a9f10-9e70-4412-81ce-49ead73ed881",
                        "0da18623-dc4c-463d-a3d1-9ac050e9e720",
                        "167338d7-d38c-4760-91f1-79a8ec457bb2"
                    ]
                }
            ],
            "BlockType": "PAGE",
            "Id": "21f0535e-60d5-4bc7-adf2-c05dd851fa25"
        },
        {
            "Relationships": [
                {
                    "Type": "CHILD",
                    "Ids": [
                        "62490c26-37ea-49fa-8034-7a9ff9369c9c",
                        "1e4f3f21-05bd-4da9-ba10-15d01e66604c"
                    ]
                }
            ],
            "Confidence": 89.11581420898438,
            "Geometry": {
```

```
                "BoundingBox": {
                    "Width": 0.33642634749412537,
                    "Top": 0.17169663310050964,
                    "Left": 0.13885067403316498,
                    "Height": 0.49159330129623413
                },
                "Polygon": [
                    {
                        "Y": 0.17169663310050964,
                        "X": 0.13885067403316498
                    },
                    {
                        "Y": 0.17169663310050964,
                        "X": 0.47527703642845154
                    },
                    {
                        "Y": 0.6632899641990662,
                        "X": 0.47527703642845154
                    },
                    {
                        "Y": 0.6632899641990662,
                        "X": 0.13885067403316498
                    }
                ]
            },
            "Text": "He llo,",
            "BlockType": "LINE",
            "Id": "896a9f10-9e70-4412-81ce-49ead73ed881"
        },
        {
            "Relationships": [
                {
                    "Type": "CHILD",
                    "Ids": [
                        "19b28058-9516-4352-b929-64d7cef29daf"
                    ]
                }
            ],
            "Confidence": 85.5694351196289,
            "Geometry": {
                "BoundingBox": {
                    "Width": 0.33182239532470703,
                    "Top": 0.23131252825260162,
                    "Left": 0.5091826915740967,
```

```
                    "Height": 0.3766750991344452
                },
                "Polygon": [
                    {
                        "Y": 0.23131252825260162,
                        "X": 0.5091826915740967
                    },
                    {
                        "Y": 0.23131252825260162,
                        "X": 0.8410050868988037
                    },
                    {
                        "Y": 0.607987642288208,
                        "X": 0.8410050868988037
                    },
                    {
                        "Y": 0.607987642288208,
                        "X": 0.5091826915740967
                    }
                ]
            },
            "Text": "worlc",
            "BlockType": "LINE",
            "Id": "0da18623-dc4c-463d-a3d1-9ac050e9e720"
        }
    ],
    "DocumentMetadata": {
        "Pages": 1
    }
}
```

Para obter mais informações, consulte Detecting Document Text with Amazon Textract Guia do desenvolvedor do Amazon Textract

- Para obter detalhes da API, consulte DetectDocumentTextem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Detectar texto de um documento de entrada.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.Document;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextRequest;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.DocumentMetadata;
import software.amazon.awssdk.services.textract.model.TextractException;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectDocumentText {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <sourceDoc>\s
```

```
                Where:
                    sourceDoc - The path where the document is located (must be
an image, for example, C:/AWS/book.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceDoc = args[0];
        Region region = Region.US_EAST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        detectDocText(textractClient, sourceDoc);
        textractClient.close();
    }

    public static void detectDocText(TextractClient textractClient, String
sourceDoc) {
        try {
            InputStream sourceStream = new FileInputStream(new File(sourceDoc));
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Get the input Document object as bytes.
            Document myDoc = Document.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectDocumentTextRequest detectDocumentTextRequest =
DetectDocumentTextRequest.builder()
                    .document(myDoc)
                    .build();

            // Invoke the Detect operation.
            DetectDocumentTextResponse textResponse =
textractClient.detectDocumentText(detectDocumentTextRequest);
            List<Block> docInfo = textResponse.blocks();
            for (Block block : docInfo) {
                System.out.println("The block type is " +
block.blockType().toString());
            }
```

```
            DocumentMetadata documentMetadata = textResponse.documentMetadata();
            System.out.println("The number of pages in the document is " +
 documentMetadata.pages());

        } catch (TextractException | FileNotFoundException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar texto de um documento localizado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.model.S3Object;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.Document;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextRequest;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.DocumentMetadata;
import software.amazon.awssdk.services.textract.model.TextractException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class DetectDocumentTextS3 {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <docName>\s
```

```
                Where:
                    bucketName - The name of the Amazon S3 bucket that contains
the document.\s

                    docName - The document name (must be an image, i.e.,
book.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String docName = args[1];
        Region region = Region.US_WEST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        detectDocTextS3(textractClient, bucketName, docName);
        textractClient.close();
    }

    public static void detectDocTextS3(TextractClient textractClient, String
bucketName, String docName) {
        try {
            S3Object s3Object = S3Object.builder()
                    .bucket(bucketName)
                    .name(docName)
                    .build();

            // Create a Document object and reference the s3Object instance.
            Document myDoc = Document.builder()
                    .s3Object(s3Object)
                    .build();

            DetectDocumentTextRequest detectDocumentTextRequest =
DetectDocumentTextRequest.builder()
                    .document(myDoc)
                    .build();

            DetectDocumentTextResponse textResponse =
textractClient.detectDocumentText(detectDocumentTextRequest);
```

```
            for (Block block : textResponse.blocks()) {
                System.out.println("The block type is " +
 block.blockType().toString());
            }

            DocumentMetadata documentMetadata = textResponse.documentMetadata();
            System.out.println("The number of pages in the document is " +
 documentMetadata.pages());

        } catch (TextractException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectDocumentTexta Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
```

```
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def detect_file_text(self, *, document_file_name=None, document_bytes=None):
        """
        Detects text elements in a local image file or from in-memory byte data.
        The image must be in PNG or JPG format.

        :param document_file_name: The name of a document image file.
        :param document_bytes: In-memory byte data of a document image.
        :return: The response from Amazon Textract, including a list of blocks
                 that describe elements detected in the image.
        """
        if document_file_name is not None:
            with open(document_file_name, "rb") as document_file:
                document_bytes = document_file.read()
        try:
            response = self.textract_client.detect_document_text(
                Document={"Bytes": document_bytes}
            )
            logger.info("Detected %s blocks.", len(response["Blocks"]))
        except ClientError:
            logger.exception("Couldn't detect text.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DetectDocumentTextReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Detects text in the input document."
   "Amazon Textract can detect lines of text and the words that make up a line
 of text."
   "The input document must be in one of the following image formats: JPEG, PNG,
 PDF, or TIFF."

   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_document) = NEW /aws1/cl_texdocument( io_s3object = lo_s3object ).
   "Analyze document stored in Amazon S3."
   TRY.
       oo_result = lo_tex->detectdocumenttext( io_document = lo_document ).
   "oo_result is returned for testing purposes."
       LOOP AT oo_result->get_blocks( ) INTO DATA(lo_block).
         IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
           MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
         ENDIF.
       ENDLOOP.
       DATA(lo_metadata) = oo_result->get_documentmetadata( ).
       MESSAGE 'The number of pages in the document is ' && lo_metadata-
>ask_pages( ) TYPE 'I'.
       MESSAGE 'Detect document text completed.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
     CATCH /aws1/cx_texinvalids3objectex.
       MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texprovthruputexcdex.
       MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
     CATCH /aws1/cx_texthrottlingex.
       MESSAGE 'The request processing exceeded the limit' TYPE 'E'.
     CATCH /aws1/cx_texunsupporteddocex.
```

```
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DetectDocumentTextreferência da API AWS SDK for SAP ABAP.

Obtenha dados sobre um trabalho de análise de documentos do Amazon Textract usando um SDK da AWS

Os exemplos de código a seguir mostram como obter dados sobre um trabalho de análise de documento do Amazon Textract.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar análise de documentos

CLI

AWS CLI

Como obter os resultados de uma análise assíncrona de texto em um documento com várias páginas

O exemplo de `get-document-analysis` a seguir mostra como obter os resultados de uma análise assíncrona de texto em um documento com várias páginas.

```
aws textract get-document-analysis \
    --job-id df7cf32ebbd2a5de113535fcf4d921926a701b09b4e7d089f3aebadb41e0712b \
    --max-results 1000
```

Saída:

```
{
    "Blocks": [
        {
            "Geometry": {
                "BoundingBox": {
                    "Width": 1.0,
```

```
                    "Top": 0.0,
                    "Left": 0.0,
                    "Height": 1.0
                },
                "Polygon": [
                    {
                        "Y": 0.0,
                        "X": 0.0
                    },
                    {
                        "Y": 0.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 1.0
                    },
                    {
                        "Y": 1.0,
                        "X": 0.0
                    }
                ]
            },
            "Relationships": [
                {
                    "Type": "CHILD",
                    "Ids": [
                        "75966e64-81c2-4540-9649-d66ec341cd8f",
                        "bb099c24-8282-464c-a179-8a9fa0a057f0",
                        "5ebf522d-f9e4-4dc7-bfae-a288dc094595"
                    ]
                }
            ],
            "BlockType": "PAGE",
            "Id": "247c28ee-b63d-4aeb-9af0-5f7ea8ba109e",
            "Page": 1
        }
    ],
    "NextToken": "cY1W3eTFvoB0cH7YrKVudI4Gb0H8J0xAYLo8xI/JunCIPWCthaKQ+07n/
ElyutsSy0+1VOImoTRmP1zw4P0RFtaeV9Bzhnfedpx1YqwB4xaGDA==",
    "DocumentMetadata": {
        "Pages": 1
    },
    "JobStatus": "SUCCEEDED"
```

```
}
```

Para obter mais informações, consulte Detecting and Analyzing Text in Multi-Page Documents no Guia do desenvolvedor do Amazon Textract

- Para obter detalhes da API, consulte GetDocumentAnalysisem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def get_analysis_job(self, job_id):
        """
        Gets data for a previously started detection job that includes additional
        elements.

        :param job_id: The ID of the job to retrieve.
        :return: The job data, including a list of blocks that describe elements
                 detected in the image.
        """
        try:
```

```
            response = self.textract_client.get_document_analysis(JobId=job_id)
            job_status = response["JobStatus"]
            logger.info("Job %s status is %s.", job_id, job_status)
        except ClientError:
            logger.exception("Couldn't get data for job %s.", job_id)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetDocumentAnalysisReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Gets the results for an Amazon Textract"
   "asynchronous operation that analyzes text in a document."
   TRY.
       oo_result = lo_tex->getdocumentanalysis( iv_jobid = iv_jobid ).
"oo_result is returned for testing purposes."
       WHILE oo_result->get_jobstatus( ) <> 'SUCCEEDED'.
         IF sy-index = 10.
           EXIT.               "Maximum 300 seconds.
         ENDIF.
         WAIT UP TO 30 SECONDS.
         oo_result = lo_tex->getdocumentanalysis( iv_jobid = iv_jobid ).
       ENDWHILE.

       DATA(lt_blocks) = oo_result->get_blocks( ).
       LOOP AT lt_blocks INTO DATA(lo_block).
```

```
          IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
            MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
          ENDIF.
        ENDLOOP.
        MESSAGE 'Document analysis retrieved.' TYPE 'I'.
      CATCH /aws1/cx_texaccessdeniedex.
        MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
      CATCH /aws1/cx_texinternalservererr.
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidjobidex.
        MESSAGE 'Job ID is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidkmskeyex.
        MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetDocumentAnalysisreferência da API AWS SDK for SAP ABAP.

Inicie a análise assíncrona de um documento usando o Amazon Textract e um SDK da AWS

Os exemplos de código a seguir mostram como iniciar uma análise assíncrona de um documento usando o Amazon Textract.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar análise de documentos

CLI

AWS CLI

Como começar a analisar texto em um documento com várias páginas

O exemplo de `start-document-analysis` a seguir mostra como iniciar a análise assíncrona de texto em um documento com várias páginas.

Linux/macOS:

```
aws textract start-document-analysis \
    --document-location '{"S3Object":{"Bucket":"bucket","Name":"document"}}' \
    --feature-types '["TABLES","FORMS"]' \
    --notification-channel "SNSTopicArn=arn:snsTopic,RoleArn=roleArn"
```

Windows:

```
aws textract start-document-analysis \
    --document-location "{\"S3Object\":{\"Bucket\":\"bucket\",\"Name\":\"document
\"}}" \
    --feature-types "[\"TABLES\", \"FORMS\"]" \
    --region region-name \
    --notification-channel "SNSTopicArn=arn:snsTopic,RoleArn=roleArn"
```

Saída:

```
{
    "JobId": "df7cf32ebbd2a5de113535fcf4d921926a701b09b4e7d089f3aebadb41e0712b"
}
```

Para obter mais informações, consulte Detecting and Analyzing Text in Multi-Page Documents no Guia do desenvolvedor do Amazon Textract

- Para obter detalhes da API, consulte StartDocumentAnalysisem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.model.S3Object;
import software.amazon.awssdk.services.textract.TextractClient;
import
 software.amazon.awssdk.services.textract.model.StartDocumentAnalysisRequest;
import software.amazon.awssdk.services.textract.model.DocumentLocation;
import software.amazon.awssdk.services.textract.model.TextractException;
import
 software.amazon.awssdk.services.textract.model.StartDocumentAnalysisResponse;
import software.amazon.awssdk.services.textract.model.GetDocumentAnalysisRequest;
import
 software.amazon.awssdk.services.textract.model.GetDocumentAnalysisResponse;
import software.amazon.awssdk.services.textract.model.FeatureType;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */
public class StartDocumentAnalysis {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <docName>\s
```

```
                Where:
                    bucketName - The name of the Amazon S3 bucket that contains
the document.\s
                    docName - The document name (must be an image, for example,
book.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String docName = args[1];
        Region region = Region.US_WEST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        String jobId = startDocAnalysisS3(textractClient, bucketName, docName);
        System.out.println("Getting results for job " + jobId);
        String status = getJobResults(textractClient, jobId);
        System.out.println("The job status is " + status);
        textractClient.close();
    }

    public static String startDocAnalysisS3(TextractClient textractClient, String
bucketName, String docName) {
        try {
            List<FeatureType> myList = new ArrayList<>();
            myList.add(FeatureType.TABLES);
            myList.add(FeatureType.FORMS);

            S3Object s3Object = S3Object.builder()
                    .bucket(bucketName)
                    .name(docName)
                    .build();

            DocumentLocation location = DocumentLocation.builder()
                    .s3Object(s3Object)
                    .build();

            StartDocumentAnalysisRequest documentAnalysisRequest =
StartDocumentAnalysisRequest.builder()
```

```
                    .documentLocation(location)
                    .featureTypes(myList)
                    .build();

            StartDocumentAnalysisResponse response =
textractClient.startDocumentAnalysis(documentAnalysisRequest);

            // Get the job ID
            String jobId = response.jobId();
            return jobId;

        } catch (TextractException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    private static String getJobResults(TextractClient textractClient, String
jobId) {
        boolean finished = false;
        int index = 0;
        String status = "";

        try {
            while (!finished) {
                GetDocumentAnalysisRequest analysisRequest =
GetDocumentAnalysisRequest.builder()
                        .jobId(jobId)
                        .maxResults(1000)
                        .build();

                GetDocumentAnalysisResponse response =
textractClient.getDocumentAnalysis(analysisRequest);
                status = response.jobStatus().toString();

                if (status.compareTo("SUCCEEDED") == 0)
                    finished = true;
                else {
                    System.out.println(index + " status is: " + status);
                    Thread.sleep(1000);
                }
                index++;
            }
```

```
            return status;

        } catch (InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte StartDocumentAnalysisa Referência AWS SDK for Java 2.x da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Iniciar um trabalho assíncrono para analisar um documento.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def start_analysis_job(
```

```
        self,
        bucket_name,
        document_file_name,
        feature_types,
        sns_topic_arn,
        sns_role_arn,
    ):
        """
        Starts an asynchronous job to detect text and additional elements, such
as
        forms or tables, in an image stored in an Amazon S3 bucket. Textract
publishes
        a notification to the specified Amazon SNS topic when the job completes.
        The image must be in PNG, JPG, or PDF format.

        :param bucket_name: The name of the Amazon S3 bucket that contains the
image.
        :param document_file_name: The name of the document image stored in
Amazon S3.
        :param feature_types: The types of additional document features to
detect.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of an Amazon SNS
topic
                               where job completion notification is published.
        :param sns_role_arn: The ARN of an AWS Identity and Access Management
(IAM)
                              role that can be assumed by Textract and grants
permission
                              to publish to the Amazon SNS topic.
        :return: The ID of the job.
        """
        try:
            response = self.textract_client.start_document_analysis(
                DocumentLocation={
                    "S3Object": {"Bucket": bucket_name, "Name":
document_file_name}
                },
                NotificationChannel={
                    "SNSTopicArn": sns_topic_arn,
                    "RoleArn": sns_role_arn,
                },
                FeatureTypes=feature_types,
            )
            job_id = response["JobId"]
```

```
            logger.info(
                "Started text analysis job %s on %s.", job_id, document_file_name
            )
        except ClientError:
            logger.exception("Couldn't analyze text in %s.", document_file_name)
            raise
        else:
            return job_id
```

- Para obter detalhes da API, consulte a StartDocumentAnalysisReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Starts the asynchronous analysis of an input document for relationships"
   "between detected items such as key-value pairs, tables, and selection
elements."

   "Create ABAP objects for feature type."
   "Add TABLES to return information about the tables."
   "Add FORMS to return detected form data."
   "To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

   DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).
   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).
   "Create an ABAP object for the document."
```

```
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).

   "Start async document analysis."
   TRY.
       oo_result = lo_tex->startdocumentanalysis(      "oo_result is returned
for testing purposes."
         io_documentlocation     = lo_documentlocation
         it_featuretypes         = lt_featuretypes ).
       DATA(lv_jobid) = oo_result->get_jobid( ).

       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texidempotentprmmis00.
       MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidkmskeyex.
       MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
     CATCH /aws1/cx_texinvalids3objectex.
       MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texlimitexceededex.
       MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
     CATCH /aws1/cx_texprovthruputexcdex.
       MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
     CATCH /aws1/cx_texthrottlingex.
       MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
     CATCH /aws1/cx_texunsupporteddocex.
       MESSAGE 'The document is not supported.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a StartDocumentAnalysisreferência da API AWS SDK for SAP ABAP.

Inicie a detecção assíncrona de texto usando o Amazon Textract e um SDK da AWS

Os exemplos de código a seguir mostram como detectar texto em um documento usando o Amazon Textract.

CLI

AWS CLI

Como começar a detectar texto em um documento com várias páginas

O exemplo de `start-document-text-detection` a seguir mostra como iniciar a detecção assíncrona de texto em um documento com várias páginas.

Linux/macOS:

```
aws textract start-document-text-detection \
        --document-location '{"S3Object":{"Bucket":"bucket","Name":"document"}}'
 \
        --notification-channel "SNSTopicArn=arn:snsTopic,RoleArn=roleARN"
```

Windows:

```
aws textract start-document-text-detection \
    --document-location "{\"S3Object\":{\"Bucket\":\"bucket\",\"Name\":\"document
\"}}" \
    --region region-name \
    --notification-channel "SNSTopicArn=arn:snsTopic,RoleArn=roleArn"
```

Saída:

```
{
    "JobId": "57849a3dc627d4df74123dca269d69f7b89329c870c65bb16c9fd63409d200b9"
}
```

Para obter mais informações, consulte Detecting and Analyzing Text in Multi-Page Documents no Guia do desenvolvedor do Amazon Textract

- Para obter detalhes da API, consulte StartDocumentTextDetectionem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Iniciar um trabalho assíncrono para detectar texto em um documento.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def start_detection_job(
        self, bucket_name, document_file_name, sns_topic_arn, sns_role_arn
    ):
        """
        Starts an asynchronous job to detect text elements in an image stored in
 an
        Amazon S3 bucket. Textract publishes a notification to the specified
 Amazon SNS
        topic when the job completes.
        The image must be in PNG, JPG, or PDF format.

        :param bucket_name: The name of the Amazon S3 bucket that contains the
 image.
        :param document_file_name: The name of the document image stored in
 Amazon S3.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of an Amazon SNS
 topic
```

```
                                where the job completion notification is published.
        :param sns_role_arn: The ARN of an AWS Identity and Access Management
(IAM)
                               role that can be assumed by Textract and grants
permission
                               to publish to the Amazon SNS topic.
        :return: The ID of the job.
        """
        try:
            response = self.textract_client.start_document_text_detection(
                DocumentLocation={
                    "S3Object": {"Bucket": bucket_name, "Name":
document_file_name}
                },
                NotificationChannel={
                    "SNSTopicArn": sns_topic_arn,
                    "RoleArn": sns_role_arn,
                },
            )
            job_id = response["JobId"]
            logger.info(
                "Started text detection job %s on %s.", job_id,
document_file_name
            )
        except ClientError:
            logger.exception("Couldn't detect text in %s.", document_file_name)
            raise
        else:
            return job_id
```

- Para obter detalhes da API, consulte a StartDocumentTextDetectionReferência da API AWSSDK for Python (Boto3).

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Starts the asynchronous detection of text in a document."
   "Amazon Textract can detect lines of text and the words that make up a line
of text."

   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).
   "Create an ABAP object for the document."
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).
   "Start document analysis."
   TRY.
       oo_result = lo_tex->startdocumenttextdetection( io_documentlocation =
lo_documentlocation ).
       DATA(lv_jobid) = oo_result->get_jobid( ).             "oo_result is
returned for testing purposes."
       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texidempotentprmmis00.
       MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidkmskeyex.
       MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
```

```
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texlimitexceededex.
        MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartDocumentTextDetectionreferência da API AWS SDK for SAP ABAP.

Cenários para Amazon Textract usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Textract com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar a análise de documentos do Amazon Textract usando um SDK da AWS

Comece a usar a análise de documentos do Amazon Textract usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Iniciar a análise assíncrona.
- Obter análise de documentos.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Create ABAP objects for feature type."
   "Add TABLES to return information about the tables."
   "Add FORMS to return detected form data."
   "To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

   DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).

   "Create an ABAP object for the Amazon Simple Storage Service (Amazon S3)
object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).

   "Start document analysis."
   TRY.
       DATA(lo_start_result) = lo_tex->startdocumentanalysis(
         io_documentlocation     = lo_documentlocation
         it_featuretypes         = lt_featuretypes ).
       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texidempotentprmmis00.
```

```
        MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
      CATCH /aws1/cx_texinternalservererr.
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidkmskeyex.
        MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texlimitexceededex.
        MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.

    "Get job ID from the output."
    DATA(lv_jobid) = lo_start_result->get_jobid( ).

    "Wait for job to complete."
    oo_result = lo_tex->getdocumentanalysis( iv_jobid = lv_jobid ).     "
oo_result is returned for testing purposes. "
    WHILE oo_result->get_jobstatus( ) <> 'SUCCEEDED'.
      IF sy-index = 10.
        EXIT.               "Maximum 300 seconds."
      ENDIF.
      WAIT UP TO 30 SECONDS.
      oo_result = lo_tex->getdocumentanalysis( iv_jobid = lv_jobid ).
    ENDWHILE.

    DATA(lt_blocks) = oo_result->get_blocks( ).
    LOOP AT lt_blocks INTO DATA(lo_block).
      IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
        MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
      ENDIF.
    ENDLOOP.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.

- GetDocumentAnalysis
- StartDocumentAnalysis

Exemplos entre serviços do Amazon Textract usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Textract com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de exploração do Amazon Textract
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
- Detectar entidades em texto extraído de uma imagem usando um AWS SDK

Criar uma aplicação de exploração do Amazon Textract

Os exemplos de código a seguir mostram como explorar a saída do Amazon Textract por meio de uma aplicação interativa.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon Textract para detectar elementos de texto, formulários e tabelas em uma imagem de documento. A imagem de entrada e a saída do Amazon Textract são mostradas em uma aplicaçãoTkinter que permite explorar os elementos detectados.

- Envie uma imagem de documento para o Amazon Textract e explore a saída dos elementos detectados.
- Envie imagens diretamente para o Amazon Textract ou por meio de um bucket do Amazon Simple Storage Service (Amazon S3).
- Use APIs assíncronas para iniciar um trabalho que publica uma notificação em um tópico do Amazon Simple Notification Service (Amazon SNS) quando o trabalho for concluído.
- Faça uma pesquisa em uma fila do Amazon Simple Queue Service (Amazon SQS) para obter uma mensagem de conclusão do trabalho e exiba os resultados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Os exemplos de código a seguir mostram como criar uma aplicação que analisa os cartões de comentários dos clientes, os traduz do idioma original, determina seus sentimentos e gera um arquivo de áudio do texto traduzido.

.NET

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Java

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.

- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";

/**
```

```
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );

  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);

  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";

/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
 */
```

```
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
    VoiceId: "Ruth",
```

```
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});

  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });
```

```
  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Ruby

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Detectar entidades em texto extraído de uma imagem usando um AWS SDK

O exemplo de código a seguir mostra como usar o Amazon Comprehend para detectar entidades em texto extraído pelo Amazon Textract de uma imagem armazenada no Amazon S3.

Python

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) em um bloco de anotações Jupyter para detectar entidades em texto extraído de uma imagem. Este exemplo usa o Amazon Textract para extrair texto de uma imagem armazenada no Amazon Simple Storage Service (Amazon S3) e no Amazon Comprehend para detectar entidades no texto extraído.

Este exemplo é um bloco de anotações Jupyter e deve ser executado em um ambiente que possa hospedar blocos de anotações. Para obter instruções sobre como executar o exemplo usando a Amazon SageMaker, consulte as instruções em TextractAndComprehendNotebook.ipynb.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon S3
- Amazon Textract

Exemplos de código do Amazon S3 usando AWS SDKs

Os exemplos de código a seguir mostram como usar o Amazon Transcribe com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Transcribe – Mais informações sobre o Amazon Transcribe.
- Referência da API do Amazon Transcribe – Detalhes sobre todas as ações disponíveis do Amazon Transcribe.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Transcribe usando SDKs da AWS
  - Crie um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
  - Exclua um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
  - Exclua um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS
  - Exclua um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
  - Obtenha um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
  - Obtenha um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
  - Liste vocabulários personalizados do Amazon Transcribe usando um SDK da AWS
  - Liste trabalhos de transcrição do Amazon Transcribe Medical usando um SDK da AWS
  - Liste trabalhos de transcrição do Amazon Transcribe usando um SDK da AWS
  - Produza transcrições em tempo real com o Amazon Transcribe usando um SDK da AWS
  - Inicie um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS
  - Inicie um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
  - Atualize um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
- Cenários para Amazon Transcribe usando SDKs da AWS
  - Crie e refine um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
  - Transcreva áudio e obtenha dados de trabalho com o Amazon Transcribe usando um SDK da AWS
- Exemplos entre serviços do Amazon Transcribe usando SDKs da AWS
  - Criar uma aplicação Amazon Transcribe

- Criar uma aplicação de transmissão do Amazon Transcribe
- Converter texto em fala e de volta em texto usando um AWS SDK

Ações do Amazon Transcribe usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Transcribe com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para Amazon Transcribe usando SDKs da AWS.

Exemplos

- Crie um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
- Exclua um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
- Exclua um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS
- Exclua um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
- Obtenha um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
- Obtenha um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
- Liste vocabulários personalizados do Amazon Transcribe usando um SDK da AWS
- Liste trabalhos de transcrição do Amazon Transcribe Medical usando um SDK da AWS
- Liste trabalhos de transcrição do Amazon Transcribe usando um SDK da AWS
- Produza transcrições em tempo real com o Amazon Transcribe usando um SDK da AWS
- Inicie um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS
- Inicie um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS
- Atualize um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

Crie um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como criar um vocabulário personalizado do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a custom vocabulary using a list of phrases. Custom vocabularies
    /// improve transcription accuracy for one or more specific words.
    /// </summary>
    /// <param name="languageCode">The language code of the vocabulary.</param>
    /// <param name="phrases">Phrases to use in the vocabulary.</param>
    /// <param name="vocabularyName">Name for the vocabulary.</param>
    /// <returns>The state of the custom vocabulary.</returns>
    public async Task<VocabularyState> CreateCustomVocabulary(LanguageCode
languageCode,
        List<string> phrases, string vocabularyName)
    {
        var response = await _amazonTranscribeService.CreateVocabularyAsync(
            new CreateVocabularyRequest
            {
                LanguageCode = languageCode,
                Phrases = phrases,
                VocabularyName = vocabularyName
            });
        return response.VocabularyState;
    }
```

- Para obter detalhes da API, consulte CreateVocabularya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para criar um vocabulário personalizado

O exemplo de `create-vocabulary` a seguir cria um vocabulário personalizado. Para criar um vocabulário personalizado, você deve ter criado um arquivo de texto com todos os termos que deseja transcrever com mais precisão. Para vocabulary-file-uri, especifique o URI do Amazon Simple Storage Service (Amazon S3) desse arquivo de texto. Para language-code, especifique um código de idioma correspondente ao idioma do vocabulário personalizado. Para vocabulary-name, especifique como você deseja chamar seu vocabulário personalizado.

```
aws transcribe create-vocabulary \
    --language-code language-code \
    --vocabulary-name cli-vocab-example \
    --vocabulary-file-uri s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/the-text-file-
for-the-custom-vocabulary.txt
```

Saída:

```
{
    "VocabularyName": "cli-vocab-example",
    "LanguageCode": "language-code",
    "VocabularyState": "PENDING"
}
```

Consulte mais informações em Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte CreateVocabularyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None,
 table_uri=None
):
    """
    Creates a custom vocabulary that can be used to improve the accuracy of
    transcription jobs. This function returns as soon as the vocabulary
 processing
    is started. Call get_vocabulary to get the current status of the vocabulary.
    The vocabulary is ready to use when its status is 'READY'.

    :param vocabulary_name: The name of the custom vocabulary.
    :param language_code: The language code of the vocabulary.
                          For example, en-US or nl-NL.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the
 vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in
 the
                      vocabulary.
    :return: Information about the newly created vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.create_vocabulary(**vocab_args)
        logger.info("Created custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
```

```
        logger.exception("Couldn't create custom vocabulary %s.",
vocabulary_name)
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a CreateVocabularyReferência da API AWSSDK for Python (Boto3).

Exclua um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um vocabulário personalizado do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an existing custom vocabulary.
    /// </summary>
    /// <param name="vocabularyName">Name of the vocabulary to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteCustomVocabulary(string vocabularyName)
    {
```

```
        var response = await _amazonTranscribeService.DeleteVocabularyAsync(
            new DeleteVocabularyRequest
            {
                VocabularyName = vocabularyName
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteVocabularya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para excluir um vocabulário personalizado

O exemplo de `delete-vocabulary` a seguir exclui um vocabulário personalizado.

```
aws transcribe delete-vocabulary \
    --vocabulary-name vocabulary-name
```

Este comando não produz saída.

Consulte mais informações em Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte DeleteVocabularyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_vocabulary(vocabulary_name, transcribe_client):
    """
    Deletes a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Deleted vocabulary %s.", vocabulary_name)
    except ClientError:
        logger.exception("Couldn't delete vocabulary %s.", vocabulary_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteVocabularyReferência da API AWSSDK for Python (Boto3).

Exclua um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um trabalho de transcrição do Amazon Transcribe Medical.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a medical transcription job. Also deletes the transcript
 associated with the job.
```

```
    /// </summary>
    /// <param name="jobName">Name of the medical transcription job to delete.</
param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMedicalTranscriptionJob(string jobName)
    {
        var response = await
 _amazonTranscribeService.DeleteMedicalTranscriptionJobAsync(
            new DeleteMedicalTranscriptionJobRequest()
            {
                MedicalTranscriptionJobName = jobName
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteMedicalTranscriptionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para excluir um trabalho de transcrição médica

O exemplo de `delete-medical-transcription-job` a seguir exclui um trabalho de transcrição médica.

```
aws transcribe delete-medical-transcription-job \
    --medical-transcription-job-name medical-transcription-job-name
```

Este comando não produz saída.

Para obter mais informações, consulte DeleteMedicalTranscriptionJobo Amazon Transcribe Developer Guide.

- Para obter detalhes da API, consulte DeleteMedicalTranscriptionJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Exclua um trabalho de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { DeleteMedicalTranscriptionJobCommand } from "@aws-sdk/client-
transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // For example,
 'medical_transciption_demo'
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new DeleteMedicalTranscriptionJobCommand(params)
    );
    console.log("Success - deleted");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
```

```
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteMedicalTranscriptionJoba Referência AWS SDK for JavaScript da API.

Exclua um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como excluir um trabalho de transcrição do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a transcription job. Also deletes the transcript associated with
 the job.
    /// </summary>
    /// <param name="jobName">Name of the transcription job to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTranscriptionJob(string jobName)
```

```
    {
        var response = await
_amazonTranscribeService.DeleteTranscriptionJobAsync(
            new DeleteTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTranscriptionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para excluir um dos trabalhos de transcrição

O exemplo de `delete-transcription-job` a seguir exclui um dos trabalhos de transcrição.

```
aws transcribe delete-transcription-job \
    --transcription-job-name your-transcription-job
```

Este comando não produz saída.

Para obter mais informações, consulte DeleteTranscriptionJobo Amazon Transcribe Developer Guide.

- Para obter detalhes da API, consulte DeleteTranscriptionJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um trabalho de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js
import { DeleteTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  TranscriptionJobName: "JOB_NAME", // Required. For example, 'transciption_demo'
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new DeleteTranscriptionJobCommand(params)
    );
    console.log("Success - deleted");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
```

```
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTranscriptionJoba Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_job(job_name, transcribe_client):
    """
    Deletes a transcription job. This also deletes the transcript associated with
    the job.

    :param job_name: The name of the job to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_transcription_job(TranscriptionJobName=job_name)
        logger.info("Deleted job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't delete job %s.", job_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Obtenha um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como obter um vocabulário personalizado do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get information about a custom vocabulary.
/// </summary>
/// <param name="vocabularyName">Name of the vocabulary.</param>
/// <returns>The state of the custom vocabulary.</returns>
public async Task<VocabularyState> GetCustomVocabulary(string vocabularyName)
{
    var response = await _amazonTranscribeService.GetVocabularyAsync(
        new GetVocabularyRequest()
        {
            VocabularyName = vocabularyName
        });
    return response.VocabularyState;
}
```

- Para obter detalhes da API, consulte GetVocabularya Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para receber informações sobre um vocabulário personalizado

O exemplo de `get-vocabulary` a seguir coleta informações sobre um vocabulário personalizado criado anteriormente.

```
aws transcribe get-vocabulary \
    --vocabulary-name cli-vocab-1
```

Saída:

```
{
    "VocabularyName": "cli-vocab-1",
    "LanguageCode": "language-code",
    "VocabularyState": "READY",
    "LastModifiedTime": "2020-09-19T23:22:32.836000+00:00",
    "DownloadUri": "https://link-to-download-the-text-file-used-to-create-your-
custom-vocabulary"
}
```

Consulte mais informações em Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte GetVocabularyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_vocabulary(vocabulary_name, transcribe_client):
    """
    Gets information about a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: Information about the vocabulary.
    """
    try:
        response =
 transcribe_client.get_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Got vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't get vocabulary %s.", vocabulary_name)
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a GetVocabularyReferência da API AWSSDK for Python (Boto3).

Obtenha um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como obter um trabalho de transcrição do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Crie e refine um vocabulário personalizado
- Transcrever áudio e obter dados do trabalho

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details about a transcription job.
    /// </summary>
    /// <param name="jobName">A unique name for the transcription job.</param>
    /// <returns>A TranscriptionJob instance with information on the requested
job.</returns>
    public async Task<TranscriptionJob> GetTranscriptionJob(string jobName)
    {
        var response = await _amazonTranscribeService.GetTranscriptionJobAsync(
            new GetTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName
            });
        return response.TranscriptionJob;
    }
```

- Para obter detalhes da API, consulte GetTranscriptionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para ter informações sobre um trabalho de transcrição específico

O exemplo de `get-transcription-job` a seguir coleta informações sobre um trabalho de transcrição específico. Para acessar os resultados da transcrição, use o TranscriptFileUri parâmetro. Use o MediaFileUri parâmetro para ver qual arquivo de áudio você transcreveu

com esse trabalho. É possível usar o objeto Configurações para ver os recursos opcionais que você habilitou no trabalho de transcrição.

```
aws transcribe get-transcription-job \
    --transcription-job-name your-transcription-job
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "your-transcription-job",
        "TranscriptionJobStatus": "COMPLETED",
        "LanguageCode": "language-code",
        "MediaSampleRateHertz": 48000,
        "MediaFormat": "mp4",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.file-
extension"
        },
        "Transcript": {
            "TranscriptFileUri": "https://Amazon-S3-file-location-of-
transcription-output"
        },
        "StartTime": "2020-09-18T22:27:23.970000+00:00",
        "CreationTime": "2020-09-18T22:27:23.948000+00:00",
        "CompletionTime": "2020-09-18T22:28:21.197000+00:00",
        "Settings": {
            "ChannelIdentification": false,
            "ShowAlternatives": false
        },
        "IdentifyLanguage": true,
        "IdentifiedLanguageScore": 0.8672199249267578
    }
}
```

Consulte mais informações em Getting Started (AWS Command Line Interface) no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte GetTranscriptionJobem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_job(job_name, transcribe_client):
    """
    Gets details about a transcription job.

    :param job_name: The name of the job to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The retrieved transcription job.
    """
    try:
        response = transcribe_client.get_transcription_job(
            TranscriptionJobName=job_name
        )
        job = response["TranscriptionJob"]
        logger.info("Got job %s.", job["TranscriptionJobName"])
    except ClientError:
        logger.exception("Couldn't get job %s.", job_name)
        raise
    else:
        return job
```

- Para obter detalhes da API, consulte a GetTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Liste vocabulários personalizados do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como listar vocabulários personalizados do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List custom vocabularies for the current account. Optionally specify a
name
    /// filter and a specific state to filter the vocabularies list.
    /// </summary>
    /// <param name="nameContains">Optional string the vocabulary name must
contain.</param>
    /// <param name="stateEquals">Optional state of the vocabulary.</param>
    /// <returns>List of information about the vocabularies.</returns>
    public async Task<List<VocabularyInfo>> ListCustomVocabularies(string?
nameContains = null,
        VocabularyState? stateEquals = null)
    {
        var response = await _amazonTranscribeService.ListVocabulariesAsync(
            new ListVocabulariesRequest()
            {
                NameContains = nameContains,
                StateEquals = stateEquals
            });
        return response.Vocabularies;
    }
```

- Para obter detalhes da API, consulte ListVocabularies a Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para listar seus vocabulários personalizados

O exemplo de `list-vocabularies` a seguir lista os vocabulários personalizados associados à sua conta e região da AWS.

```
aws transcribe list-vocabularies
```

Saída:

```
{
    "NextToken": "NextToken",
    "Vocabularies": [
        {
            "VocabularyName": "ards-test-1",
            "LanguageCode": "language-code",
            "LastModifiedTime": "2020-04-27T22:00:27.330000+00:00",
            "VocabularyState": "READY"
        },
        {
            "VocabularyName": "sample-test",
            "LanguageCode": "language-code",
            "LastModifiedTime": "2020-04-24T23:04:11.044000+00:00",
            "VocabularyState": "READY"
        },
        {
            "VocabularyName": "CRLF-to-LF-test-3-1",
            "LanguageCode": "language-code",
            "LastModifiedTime": "2020-04-24T22:12:22.277000+00:00",
            "VocabularyState": "READY"
        },
        {
            "VocabularyName": "CRLF-to-LF-test-2",
            "LanguageCode": "language-code",
            "LastModifiedTime": "2020-04-24T21:53:50.455000+00:00",
            "VocabularyState": "READY"
```

```
        },
        {
            "VocabularyName": "CRLF-to-LF-1-1",
            "LanguageCode": "language-code",
            "LastModifiedTime": "2020-04-24T21:39:33.356000+00:00",
            "VocabularyState": "READY"
        }
    ]
}
```

Consulte mais informações em Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte ListVocabuliariesem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_vocabularies(vocabulary_filter, transcribe_client):
    """
    Lists the custom vocabularies created for this AWS account.

    :param vocabulary_filter: The returned vocabularies must contain this string
 in
                              their names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved vocabularies.
    """
    try:
        response =
 transcribe_client.list_vocabularies(NameContains=vocabulary_filter)
        vocabs = response["Vocabularies"]
        next_token = response.get("NextToken")
```

```
        while next_token is not None:
            response = transcribe_client.list_vocabularies(
                NameContains=vocabulary_filter, NextToken=next_token
            )
            vocabs += response["Vocabularies"]
            next_token = response.get("NextToken")
        logger.info(
            "Got %s vocabularies with filter %s.", len(vocabs), vocabulary_filter
        )
    except ClientError:
        logger.exception(
            "Couldn't list vocabularies with filter %s.", vocabulary_filter
        )
        raise
    else:
        return vocabs
```

- Para obter detalhes da API, consulte a ListVocabularies Referência da API AWSSDK for Python (Boto3).

Liste trabalhos de transcrição do Amazon Transcribe Medical usando um SDK da AWS

Os exemplos de código a seguir mostram como listar trabalhos de transcrição do Amazon Transcribe Medical.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// List medical transcription jobs, optionally with a name filter.
    /// </summary>
    /// <param name="jobNameContains">Optional name filter for the medical
transcription jobs.</param>
    /// <returns>A list of summaries about medical transcription jobs.</returns>
    public async Task<List<MedicalTranscriptionJobSummary>>
ListMedicalTranscriptionJobs(
        string? jobNameContains = null)
    {
        var response = await
_amazonTranscribeService.ListMedicalTranscriptionJobsAsync(
            new ListMedicalTranscriptionJobsRequest()
            {
                JobNameContains = jobNameContains
            });
        return response.MedicalTranscriptionJobSummaries;
    }
```

- Para obter detalhes da API, consulte ListMedicalTranscriptionJobsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para listar trabalhos de transcrição médica

O exemplo de `list-medical-transcription-jobs` a seguir lista os trabalhos de transcrição médica associados à sua conta e região da AWS. Para obter mais informações sobre um trabalho de transcrição específico, copie o valor de um MedicalTranscriptionJobName parâmetro na saída da transcrição e especifique esse valor para a `MedicalTranscriptionJobName` opção do `get-medical-transcription-job` comando. Para ver mais trabalhos de transcrição, copie o valor do NextToken parâmetro, execute o `list-medical-transcription-jobs` comando novamente e especifique esse valor na `--next-token` opção.

```
aws transcribe list-medical-transcription-jobs
```

Saída:

```
{
    "NextToken": "3/PblzkiGhzjER3KHuQt2fmbPLF7cDYafjFMEoGn44ON/
gsuUSTIkGyanvRE6WMXFd/ZTEc2EZj+P9eii/
z1O2FDYli6RLI0WoRX4RwMisVrh9G0Kie0Y8ikBCdtqlZB10Wa9McC+ebOl
+LaDtZPC4u6ttoHLRlEfzqstHXSgapXg3tEBtm9piIaPB6MOM5BB6t86+qtmocTR/
qrteHZBBudhTfbCwhsxaqujHiiUvFdm3BQbKKWIW06yV9b+4f38oD2lVIan
+vfUs3gBYAl5VTDmXXzQPBQOHPjtwmFI+IWX15nSUjWuN3TUylHgPWzDaYT8qBtu0Z+3UG4V6b
+K2CC0XszXg5rBq9hYgNzy4XoFh/6s5DoSnzq49Q9xHgHdT2yBADFmvFK7myZBsj75+2vQZOSVpWUPy3WT/32zFAc
+mFYfUjtTZ8n/jq7aQEjQ42A
+X/7K6JgOcdVPtEg8PlDr5kgYYG3q3OmYXX37U3FZuJmnTI63VtIXsNnOU5eGoYObtpk00Nq9UkzgSJxqj84ZD5n
+S0EGy9ZUYBJRRcGeYUM3Q4DbSJfUwSAqcFdLIWZdp8qIREMQIBWy7BLwSdyqsQo2vRrd53hm5aWM7SVf6pPq6X/
IXR5+1eUOOD8/coaTT4ES2DerbV6RkV4o0VT1d0SdVX/
MmtkNG8nYj8PqU07w7988quh1ZP6D80veJS1q73tUUR9MjnGernW2tAnvnLNhdefBcD
+sZVfYq3iBMFY7wTy1P1G6NqW9GrYDYoX3tTPWlD7phpbVSyKrh/
PdYrps5UxnsGoA1b7L/FfAXDfUoGrGUB4N3JsPYXX9D++g+6gV1qBBs/
WfF934aKqfD6UTggm/zV3GAOWiBpfvAZRvEb924i6yGHyMC7y54O1ZAwSBupmI
+FFd13CaPO4kN1vJlth6aM5vUPXg4BpyUhtbRhwD/KxCvf9K0tLJGyL1A==",
    "MedicalTranscriptionJobSummaries": [
        {
            "MedicalTranscriptionJobName": "vocabulary-dictation-medical-
transcription-job",
            "CreationTime": "2020-09-21T21:17:27.016000+00:00",
            "StartTime": "2020-09-21T21:17:27.045000+00:00",
            "CompletionTime": "2020-09-21T21:17:59.561000+00:00",
            "LanguageCode": "en-US",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "CUSTOMER_BUCKET",
            "Specialty": "PRIMARYCARE",
            "Type": "DICTATION"
        },
        {
            "MedicalTranscriptionJobName": "alternatives-dictation-medical-
transcription-job",
            "CreationTime": "2020-09-21T21:01:14.569000+00:00",
            "StartTime": "2020-09-21T21:01:14.592000+00:00",
            "CompletionTime": "2020-09-21T21:01:43.606000+00:00",
            "LanguageCode": "en-US",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "CUSTOMER_BUCKET",
            "Specialty": "PRIMARYCARE",
            "Type": "DICTATION"
        },
        {
```

```
            "MedicalTranscriptionJobName": "alternatives-conversation-medical-
transcription-job",
            "CreationTime": "2020-09-21T19:09:18.171000+00:00",
            "StartTime": "2020-09-21T19:09:18.199000+00:00",
            "CompletionTime": "2020-09-21T19:10:22.516000+00:00",
            "LanguageCode": "en-US",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "CUSTOMER_BUCKET",
            "Specialty": "PRIMARYCARE",
            "Type": "CONVERSATION"
        },
        {
            "MedicalTranscriptionJobName": "speaker-id-conversation-medical-
transcription-job",
            "CreationTime": "2020-09-21T18:43:37.157000+00:00",
            "StartTime": "2020-09-21T18:43:37.265000+00:00",
            "CompletionTime": "2020-09-21T18:44:21.192000+00:00",
            "LanguageCode": "en-US",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "CUSTOMER_BUCKET",
            "Specialty": "PRIMARYCARE",
            "Type": "CONVERSATION"
        },
        {
            "MedicalTranscriptionJobName": "multichannel-conversation-medical-
transcription-job",
            "CreationTime": "2020-09-20T23:46:44.053000+00:00",
            "StartTime": "2020-09-20T23:46:44.081000+00:00",
            "CompletionTime": "2020-09-20T23:47:35.851000+00:00",
            "LanguageCode": "en-US",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "CUSTOMER_BUCKET",
            "Specialty": "PRIMARYCARE",
            "Type": "CONVERSATION"
        }
    ]
}
```

Para obter mais informações, consulte https://docs.aws.amazon.com/transcribe/latest/dg/batch-med-transcription .html> no Amazon Transcribe Developer Guide.

- Para obter detalhes da API, consulte ListMedicalTranscriptionJobsem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Liste trabalhos de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartMedicalTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // Required
  OutputBucketName: "OUTPUT_BUCKET_NAME", // Required
  Specialty: "PRIMARYCARE", // Required. Possible values are 'PRIMARYCARE'
  Type: "JOB_TYPE", // Required. Possible values are 'CONVERSATION' and
 'DICTATION'
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_FILE_LOCATION",
    // The S3 object location of the input media file. The URI must be in the
 same region
    // as the API endpoint that you are calling.For example,
    // "https://transcribe-demo.s3-REGION.amazonaws.com/hello_world.wav"
  },
```

```
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartMedicalTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMedicalTranscriptionJobsa Referência AWS SDK for JavaScript da API.

Liste trabalhos de transcrição do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como listar trabalhos de transcrição do Amazon Transcribe.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List transcription jobs, optionally with a name filter.
    /// </summary>
```

```
    /// <param name="jobNameContains">Optional name filter for the transcription
 jobs.</param>
    /// <returns>A list of transcription job summaries.</returns>
    public async Task<List<TranscriptionJobSummary>>
 ListTranscriptionJobs(string? jobNameContains = null)
    {
        var response = await _amazonTranscribeService.ListTranscriptionJobsAsync(
            new ListTranscriptionJobsRequest()
            {
                JobNameContains = jobNameContains
            });
        return response.TranscriptionJobSummaries;
    }
```

- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para listar os trabalhos de transcrição

O exemplo de `list-transcription-jobs` a seguir lista os trabalhos de transcrição associados à sua conta e região da AWS.

```
aws transcribe list-transcription-jobs
```

Saída:

```
{
    "NextToken": "NextToken",
    "TranscriptionJobSummaries": [
        {
            "TranscriptionJobName": "speak-id-job-1",
            "CreationTime": "2020-08-17T21:06:15.391000+00:00",
            "StartTime": "2020-08-17T21:06:15.416000+00:00",
            "CompletionTime": "2020-08-17T21:07:05.098000+00:00",
            "LanguageCode": "language-code",
            "TranscriptionJobStatus": "COMPLETED",
```

```
            "OutputLocationType": "SERVICE_BUCKET"
        },
        {
            "TranscriptionJobName": "job-1",
            "CreationTime": "2020-08-17T20:50:24.207000+00:00",
            "StartTime": "2020-08-17T20:50:24.230000+00:00",
            "CompletionTime": "2020-08-17T20:52:18.737000+00:00",
            "LanguageCode": "language-code",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "SERVICE_BUCKET"
        },
        {
            "TranscriptionJobName": "sdk-test-job-4",
            "CreationTime": "2020-08-17T20:32:27.917000+00:00",
            "StartTime": "2020-08-17T20:32:27.956000+00:00",
            "CompletionTime": "2020-08-17T20:33:15.126000+00:00",
            "LanguageCode": "language-code",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "SERVICE_BUCKET"
        },
        {
            "TranscriptionJobName": "Diarization-speak-id",
            "CreationTime": "2020-08-10T22:10:09.066000+00:00",
            "StartTime": "2020-08-10T22:10:09.116000+00:00",
            "CompletionTime": "2020-08-10T22:26:48.172000+00:00",
            "LanguageCode": "language-code",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "SERVICE_BUCKET"
        },
        {
            "TranscriptionJobName": "your-transcription-job-name",
            "CreationTime": "2020-07-29T17:45:09.791000+00:00",
            "StartTime": "2020-07-29T17:45:09.826000+00:00",
            "CompletionTime": "2020-07-29T17:46:20.831000+00:00",
            "LanguageCode": "language-code",
            "TranscriptionJobStatus": "COMPLETED",
            "OutputLocationType": "SERVICE_BUCKET"
        }
    ]
}
```

Consulte mais informações em Getting Started (AWS Command Line Interface) no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte ListTranscriptionJobsem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ListTranscriptionJobs {
    public static void main(String[] args) {
        TranscribeClient transcribeClient = TranscribeClient.builder()
            .region(Region.US_EAST_1)
            .build();

            listTranscriptionJobs(transcribeClient);
        }

        public static void listTranscriptionJobs(TranscribeClient
 transcribeClient) {
            ListTranscriptionJobsRequest listJobsRequest =
 ListTranscriptionJobsRequest.builder()
                .build();


 transcribeClient.listTranscriptionJobsPaginator(listJobsRequest).stream()
                .flatMap(response ->
 response.transcriptionJobSummaries().stream())
                .forEach(jobSummary -> {
                    System.out.println("Job Name: " +
 jobSummary.transcriptionJobName());
                    System.out.println("Job Status: " +
 jobSummary.transcriptionJobStatus());
                    System.out.println("Output Location: " +
 jobSummary.outputLocationType());
                    // Add more information as needed
```

```
                    // Retrieve additional details for the job if necessary
                    GetTranscriptionJobResponse jobDetails =
transcribeClient.getTranscriptionJob(
                        GetTranscriptionJobRequest.builder()

.transcriptionJobName(jobSummary.transcriptionJobName())
                            .build());

                    // Display additional details
                    System.out.println("Language Code: " +
jobDetails.transcriptionJob().languageCode());
                    System.out.println("Media Format: " +
jobDetails.transcriptionJob().mediaFormat());
                    // Add more details as needed

                    System.out.println("--------------");
                });
        }
    }
```

- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste trabalhos de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js

import { ListTranscriptionJobsCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";
```

```
// Set the parameters
export const params = {
  JobNameContains: "KEYWORD", // Not required. Returns only transcription
  // job names containing this string
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new ListTranscriptionJobsCommand(params)
    );
    console.log("Success", data.TranscriptionJobSummaries);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_jobs(job_filter, transcribe_client):
    """
    Lists summaries of the transcription jobs for the current AWS account.

    :param job_filter: The list of returned jobs must contain this string in
 their
                        names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved transcription job summaries.
    """
    try:
        response =
 transcribe_client.list_transcription_jobs(JobNameContains=job_filter)
        jobs = response["TranscriptionJobSummaries"]
        next_token = response.get("NextToken")
        while next_token is not None:
            response = transcribe_client.list_transcription_jobs(
                JobNameContains=job_filter, NextToken=next_token
            )
            jobs += response["TranscriptionJobSummaries"]
            next_token = response.get("NextToken")
        logger.info("Got %s jobs with filter %s.", len(jobs), job_filter)
    except ClientError:
        logger.exception("Couldn't get jobs with filter %s.", job_filter)
        raise
    else:
        return jobs
```

- Para obter detalhes da API, consulte a ListTranscriptionJobsReferência da API AWSSDK for Python (Boto3).

Produza transcrições em tempo real com o Amazon Transcribe usando um SDK da AWS

O exemplo de código a seguir mostra como produzir uma transcrição em tempo real com o Amazon Transcribe.

C++

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main() {
    Aws::SDKOptions options;
    options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Trace;
    Aws::InitAPI(options);
    {
        //TODO(User): Set to the region of your AWS account.
        const Aws::String region = Aws::Region::US_WEST_2;

        //Load a profile that has been granted AmazonTranscribeFullAccess AWS
 managed permission policy.
        Aws::Client::ClientConfiguration config;
#ifdef _WIN32
        // ATTENTION: On Windows with the AWS C++ SDK, this example only runs if
 the SDK is built
        // with the curl library.
        // For more information, see the accompanying ReadMe.
        // For more information, see "Building the SDK for Windows with curl".
        // https://docs.aws.amazon.com/sdk-for-cpp/v1/developer-guide/setup-
windows.html
        //TODO(User): Update to the location of your .crt file.
        config.caFile = "C:/curl/bin/curl-ca-bundle.crt";
#endif
```

```
        config.region = region;

        TranscribeStreamingServiceClient client(config);
        StartStreamTranscriptionHandler handler;
        handler.SetOnErrorCallback(
                [](const Aws::Client::AWSError<TranscribeStreamingServiceErrors>
&error) {
                        std::cerr << "ERROR: " + error.GetMessage() << std::endl;
                });
        //SetTranscriptEventCallback called for every 'chunk' of file
transcripted.
        // Partial results are returned in real time.
        handler.SetTranscriptEventCallback([](const TranscriptEvent &ev) {
                for (auto &&r: ev.GetTranscript().GetResults()) {
                    if (r.GetIsPartial()) {
                        std::cout << "[partial] ";
                    }
                    else {
                        std::cout << "[Final] ";
                    }
                    for (auto &&alt: r.GetAlternatives()) {
                        std::cout << alt.GetTranscript() << std::endl;
                    }
                }
        });

        StartStreamTranscriptionRequest request;
        request.SetMediaSampleRateHertz(SAMPLE_RATE);
        request.SetLanguageCode(LanguageCode::en_US);
        request.SetMediaEncoding(
                MediaEncoding::pcm); // wav and aiff files are PCM formats.
        request.SetEventStreamHandler(handler);

        auto OnStreamReady = [](AudioStream &stream) {
                Aws::FStream file(FILE_NAME, std::ios_base::in |
std::ios_base::binary);
                if (!file.is_open()) {
                    std::cerr << "Failed to open " << FILE_NAME << '\n';
                }
                std::array<char, BUFFER_SIZE> buf;
                int i = 0;
                while (file) {
                    file.read(&buf[0], buf.size());
```

```
                    if (!file)
                        std::cout << "File: only " << file.gcount() << " could be
read"
                                  << std::endl;

                    Aws::Vector<unsigned char> bits{buf.begin(), buf.end()};
                    AudioEvent event(std::move(bits));
                    if (!stream) {
                        std::cerr << "Failed to create a stream" << std::endl;
                        break;
                    }
                    //The std::basic_istream::gcount() is used to count the
characters in the given string. It returns
                    //the number of characters extracted by the last read()
operation.
                    if (file.gcount() > 0) {
                        if (!stream.WriteAudioEvent(event)) {
                            std::cerr << "Failed to write an audio event" <<
std::endl;
                            break;
                        }
                    }
                    else {
                        break;
                    }
                    std::this_thread::sleep_for(std::chrono::milliseconds(
                            25)); // Slow down because we are streaming from a
file.
                }
                if (!stream.WriteAudioEvent(
                        AudioEvent())) {
                    // Per the spec, we have to send an empty event (an event
without a payload) at the end.
                    std::cerr << "Failed to send an empty frame" << std::endl;
                }
                else {
                    std::cout << "Successfully sent the empty frame" <<
std::endl;
                }
                stream.flush();
                stream.Close();
        };
```

```
        Aws::Utils::Threading::Semaphore signaling(0 /*initialCount*/, 1 /
*maxCount*/);
        auto OnResponseCallback = [&signaling](
                const TranscribeStreamingServiceClient * /*unused*/,
                const Model::StartStreamTranscriptionRequest & /*unused*/,
                const Model::StartStreamTranscriptionOutcome &outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext> & /
*unused*/) {

                if (!outcome.IsSuccess()) {
                    std::cerr << "Transcribe streaming error "
                              << outcome.GetError().GetMessage() << std::endl;
                }

                signaling.Release();
        };

        std::cout << "Starting..." << std::endl;
        client.StartStreamTranscriptionAsync(request, OnStreamReady,
 OnResponseCallback,
                                             nullptr /*context*/);
        signaling.WaitOne(); // Prevent the application from exiting until we're
 done.
        std::cout << "Done" << std::endl;
    }

    Aws::ShutdownAPI(options);

    return 0;
}
```

- Para obter detalhes da API, consulte StartStreamTranscriptionAsynca Referência AWS SDK for C++ da API.

Inicie um trabalho de transcrição do Amazon Transcribe Medical usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar um trabalho de transcrição do Amazon Transcribe Medical.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start a medical transcription job for a media file. This method returns
    /// as soon as the job is started.
    /// </summary>
    /// <param name="jobName">A unique name for the medical transcription job.</
param>
    /// <param name="mediaFileUri">The URI of the media file, typically an Amazon
 S3 location.</param>
    /// <param name="mediaFormat">The format of the media file.</param>
    /// <param name="outputBucketName">Location for the output, typically an
 Amazon S3 location.</param>
    /// <param name="transcriptionType">Conversation or dictation transcription
 type.</param>
    /// <returns>A MedicalTransactionJob instance with information on the new
 job.</returns>
    public async Task<MedicalTranscriptionJob> StartMedicalTranscriptionJob(
        string jobName, string mediaFileUri,
        MediaFormat mediaFormat, string outputBucketName,
 Amazon.TranscribeService.Type transcriptionType)
    {
        var response = await
 _amazonTranscribeService.StartMedicalTranscriptionJobAsync(
            new StartMedicalTranscriptionJobRequest()
            {
                MedicalTranscriptionJobName = jobName,
                Media = new Media()
                {
                    MediaFileUri = mediaFileUri
                },
                MediaFormat = mediaFormat,
                LanguageCode =
```

```
                    LanguageCode
                        .EnUS, // The value must be en-US for medical
transcriptions.
                OutputBucketName = outputBucketName,
                OutputKey =
                    jobName, // The value is a key used to fetch the output of
the transcription.
                Specialty = Specialty.PRIMARYCARE, // The value PRIMARYCARE must
be set.
                Type = transcriptionType
            });
        return response.MedicalTranscriptionJob;
    }
```

- Para obter detalhes da API, consulte StartMedicalTranscriptionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: transcrever um ditado médico armazenado como um arquivo de áudio

O exemplo de `start-medical-transcription-job` a seguir transcreve um arquivo de áudio. Você especifica o local da saída da transcrição no parâmetro `OutputBucketName`.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://myfile.json
```

Conteúdo de `myfile.json`:

```
{
    "MedicalTranscriptionJobName": "simple-dictation-medical-transcription-job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "DICTATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
    }
```

```
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "simple-dictation-medical-transcription-
job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-20T00:35:22.256000+00:00",
        "CreationTime": "2020-09-20T00:35:22.218000+00:00",
        "Specialty": "PRIMARYCARE",
        "Type": "DICTATION"
    }
}
```

Consulte mais informações em Batch Transcription Overview no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 2: transcrever um diálogo entre médico e paciente armazenado como um arquivo de áudio

O exemplo de `start-medical-transcription-job` a seguir transcreve um arquivo de áudio contendo um diálogo entre médico e paciente. Você especifica a localização da saída da transcrição no OutputBucketName parâmetro.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://mysecondfile.json
```

Conteúdo de `mysecondfile.json`:

```
{
    "MedicalTranscriptionJobName": "simple-dictation-medical-transcription-job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "CONVERSATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
```

```
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
    }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "simple-conversation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-20T23:19:49.965000+00:00",
        "CreationTime": "2020-09-20T23:19:49.941000+00:00",
        "Specialty": "PRIMARYCARE",
        "Type": "CONVERSATION"
    }
}
```

Consulte mais informações em Batch Transcription Overview no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 3: transcrever um arquivo de áudio multicanal de um diálogo entre médico e paciente

O exemplo de `start-medical-transcription-job` a seguir transcreve o áudio de cada canal no arquivo de áudio e mescla as transcrições separadas de cada canal em uma única saída de transcrição. Você especifica o local da saída da transcrição no parâmetro `OutputBucketName`.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://mythirdfile.json
```

Conteúdo de `mythirdfile.json`:

```
{
    "MedicalTranscriptionJobName": "multichannel-conversation-medical-
transcription-job",
```

```
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "CONVERSATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
        "Media": {
          "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "Settings":{
          "ChannelIdentification": true
        }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "multichannel-conversation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-20T23:46:44.081000+00:00",
        "CreationTime": "2020-09-20T23:46:44.053000+00:00",
        "Settings": {
            "ChannelIdentification": true
        },
        "Specialty": "PRIMARYCARE",
        "Type": "CONVERSATION"
    }
}
```

Consulte mais informações em Channel Identification no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 4: transcrever um arquivo de áudio de um diálogo entre médico e paciente e identificar quem está falando na saída da transcrição

O exemplo de `start-medical-transcription-job` a seguir transcreve um arquivo de áudio e rotula a fala de cada pessoa na saída da transcrição. Você especifica o local da saída da transcrição no parâmetro `OutputBucketName`.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://myfourthfile.json
```

Conteúdo de `myfourthfile.json`:

```
{
    "MedicalTranscriptionJobName": "speaker-id-conversation-medical-
transcription-job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "CONVERSATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
    "Settings":{
        "ShowSpeakerLabels": true,
        "MaxSpeakerLabels": 2
        }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "speaker-id-conversation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-21T18:43:37.265000+00:00",
        "CreationTime": "2020-09-21T18:43:37.157000+00:00",
        "Settings": {
            "ShowSpeakerLabels": true,
            "MaxSpeakerLabels": 2
        },
        "Specialty": "PRIMARYCARE",
        "Type": "CONVERSATION"
    }
}
```

Consulte mais informações em Identifying Speakers no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 5: transcrever uma conversa médica armazenada como um arquivo de áudio com até duas alternativas de transcrição

O exemplo de `start-medical-transcription-job` a seguir cria até duas transcrições alternativas de um único arquivo de áudio. Cada transcrição tem um nível de confiança associado a ela. Por padrão, o Amazon Transcribe retorna a transcrição com o maior nível de confiança. É possível especificar que o Amazon Transcribe retorne transcrições adicionais com níveis de confiança mais baixos. Você especifica o local da saída da transcrição no parâmetro `OutputBucketName`.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://myfifthfile.json
```

Conteúdo de `myfifthfile.json`:

```
{
    "MedicalTranscriptionJobName": "alternatives-conversation-medical-
transcription-job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "CONVERSATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
    },
    "Settings":{
        "ShowAlternatives": true,
        "MaxAlternatives": 2
    }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "alternatives-conversation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
```

```
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-21T19:09:18.199000+00:00",
        "CreationTime": "2020-09-21T19:09:18.171000+00:00",
        "Settings": {
            "ShowAlternatives": true,
            "MaxAlternatives": 2
        },
        "Specialty": "PRIMARYCARE",
        "Type": "CONVERSATION"
    }
}
```

Consulte mais informações em Alternative Transcriptions no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 6: transcrever um arquivo de áudio de um ditado médico com até duas transcrições alternativas

O exemplo de `start-medical-transcription-job` a seguir transcreve um arquivo de áudio e usa um filtro de vocabulário para mascarar qualquer palavra indesejada. Você especifica a localização da saída da transcrição no OutputBucketName parâmetro.

```
aws transcribe start-medical-transcription-job \
    --cli-input-json file://mysixthfile.json
```

Conteúdo de `mysixthfile.json`:

```
{
    "MedicalTranscriptionJobName": "alternatives-conversation-medical-
transcription-job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "DICTATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
    },
    "Settings":{
          "ShowAlternatives": true,
```

```
            "MaxAlternatives": 2
    }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "alternatives-dictation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-21T21:01:14.592000+00:00",
        "CreationTime": "2020-09-21T21:01:14.569000+00:00",
        "Settings": {
            "ShowAlternatives": true,
            "MaxAlternatives": 2
        },
        "Specialty": "PRIMARYCARE",
        "Type": "DICTATION"
    }
}
```

Consulte mais informações em Alternative Transcriptions no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 7: transcrever um arquivo de áudio de um ditado médico com maior precisão usando um vocabulário personalizado

O exemplo de `start-medical-transcription-job` a seguir transcreve um arquivo de áudio e usa um vocabulário médico personalizado que você criou anteriormente para aumentar a precisão da transcrição. Você especifica o local da saída da transcrição no parâmetro `OutputBucketName`.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myseventhfile.json
```

Conteúdo de `mysixthfile.json`:

```
{
    "MedicalTranscriptionJobName": "vocabulary-dictation-medical-transcription-
job",
    "LanguageCode": "language-code",
    "Specialty": "PRIMARYCARE",
    "Type": "DICTATION",
    "OutputBucketName":"DOC-EXAMPLE-BUCKET",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
    },
    "Settings":{
        "VocabularyName": "cli-medical-vocab-1"
    }
}
```

Saída:

```
{
    "MedicalTranscriptionJob": {
        "MedicalTranscriptionJobName": "vocabulary-dictation-medical-
transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.extension"
        },
        "StartTime": "2020-09-21T21:17:27.045000+00:00",
        "CreationTime": "2020-09-21T21:17:27.016000+00:00",
        "Settings": {
            "VocabularyName": "cli-medical-vocab-1"
        },
        "Specialty": "PRIMARYCARE",
        "Type": "DICTATION"
    }
}
```

Consulte mais informações em Medical Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte StartMedicalTranscriptionJobem Referência de AWS CLI Comandos.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Inicie um trabalho de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartMedicalTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // Required
  OutputBucketName: "OUTPUT_BUCKET_NAME", // Required
  Specialty: "PRIMARYCARE", // Required. Possible values are 'PRIMARYCARE'
  Type: "JOB_TYPE", // Required. Possible values are 'CONVERSATION' and
 'DICTATION'
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_FILE_LOCATION",
    // The S3 object location of the input media file. The URI must be in the
 same region
    // as the API endpoint that you are calling.For example,
    // "https://transcribe-demo.s3-REGION.amazonaws.com/hello_world.wav"
  },
```

```
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartMedicalTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte StartMedicalTranscriptionJoba Referência AWS SDK for JavaScript da API.

Inicie um trabalho de transcrição do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar um trabalho de transcrição do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação em contexto nos seguintes exemplos de código:

- Crie e refine um vocabulário personalizado
- Transcrever áudio e obter dados do trabalho

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start a transcription job for a media file. This method returns
    /// as soon as the job is started.
    /// </summary>
    /// <param name="jobName">A unique name for the transcription job.</param>
    /// <param name="mediaFileUri">The URI of the media file, typically an Amazon
 S3 location.</param>
    /// <param name="mediaFormat">The format of the media file.</param>
    /// <param name="languageCode">The language code of the media file, such as
 en-US.</param>
    /// <param name="vocabularyName">Optional name of a custom vocabulary.</
param>
    /// <returns>A TranscriptionJob instance with information on the new job.</
returns>
    public async Task<TranscriptionJob> StartTranscriptionJob(string jobName,
 string mediaFileUri,
        MediaFormat mediaFormat, LanguageCode languageCode, string?
 vocabularyName)
    {
        var response = await _amazonTranscribeService.StartTranscriptionJobAsync(
            new StartTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName,
                Media = new Media()
                {
                    MediaFileUri = mediaFileUri
                },
                MediaFormat = mediaFormat,
                LanguageCode = languageCode,
                Settings = vocabularyName != null ? new Settings()
                {
```

```
                    VocabularyName = vocabularyName
                } : null
            });
        return response.TranscriptionJob;
    }
```

- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for .NET da API.

CLI

AWS CLI

Exemplo 1: transcrever um arquivo de áudio

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myfile.json
```

Conteúdo de `myfile.json`:

```
{
    "TranscriptionJobName": "cli-simple-transcription-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    }
}
```

Consulte mais informações em Getting Started (AWS Command Line Interface) no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 2: transcrever um arquivo de áudio multicanal

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio multicanal.

```
aws transcribe start-transcription-job \
```

```
    --cli-input-json file://mysecondfile.json
```

Conteúdo de `mysecondfile.json`:

```
{
    "TranscriptionJobName": "cli-channelid-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    },
    "Settings":{
        "ChannelIdentification":true
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-channelid-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "the-language-of-your-transcription-job",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
        },
        "StartTime": "2020-09-17T16:07:56.817000+00:00",
        "CreationTime": "2020-09-17T16:07:56.784000+00:00",
        "Settings": {
            "ChannelIdentification": true
        }
    }
}
```

Consulte mais informações em Transcribing Multi-Channel Audio no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 3: transcrever um arquivo de áudio e identificar quem está falando

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e identifica quem está falando na saída da transcrição.

```
aws transcribe start-transcription-job \
    --cli-input-json file://mythirdfile.json
```

Conteúdo de `mythirdfile.json`:

```
{
    "TranscriptionJobName": "cli-speakerid-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    },
    "Settings":{
    "ShowSpeakerLabels": true,
    "MaxSpeakerLabels": 2
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-speakerid-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "the-language-of-your-transcription-job",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
        },
        "StartTime": "2020-09-17T16:22:59.696000+00:00",
        "CreationTime": "2020-09-17T16:22:59.676000+00:00",
        "Settings": {
            "ShowSpeakerLabels": true,
            "MaxSpeakerLabels": 2
        }
    }
}
```

Consulte mais informações em Identifying Speakers no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 4: transcrever um arquivo de áudio e mascarar palavras indesejadas na saída da transcrição

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e usa um filtro de vocabulário que você criou anteriormente para mascarar palavras indesejadas.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myfourthfile.json
```

Conteúdo de `myfourthfile.json`:

```
{
    "TranscriptionJobName": "cli-filter-mask-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
          "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    },
    "Settings":{
        "VocabularyFilterName": "your-vocabulary-filter",
        "VocabularyFilterMethod": "mask"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-filter-mask-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "the-language-of-your-transcription-job",
        "Media": {
            "MediaFileUri": "s3://Amazon-S3-Prefix/your-media-file.file-
extension"
        },
        "StartTime": "2020-09-18T16:36:18.568000+00:00",
        "CreationTime": "2020-09-18T16:36:18.547000+00:00",
        "Settings": {
            "VocabularyFilterName": "your-vocabulary-filter",
            "VocabularyFilterMethod": "mask"
        }
    }
```

```
}
```

Consulte mais informações em Filtering Transcriptions no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 5: transcrever um arquivo de áudio e remover palavras indesejadas na saída da transcrição

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e usa um filtro de vocabulário que você criou anteriormente para mascarar palavras indesejadas.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myfifthfile.json
```

Conteúdo de `myfifthfile.json`:

```
{
    "TranscriptionJobName": "cli-filter-remove-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    },
    "Settings":{
        "VocabularyFilterName": "your-vocabulary-filter",
        "VocabularyFilterMethod": "remove"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-filter-remove-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "the-language-of-your-transcription-job",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
        },
        "StartTime": "2020-09-18T16:36:18.568000+00:00",
```

```
        "CreationTime": "2020-09-18T16:36:18.547000+00:00",
        "Settings": {
            "VocabularyFilterName": "your-vocabulary-filter",
            "VocabularyFilterMethod": "remove"
        }
    }
}
```

Consulte mais informações em Filtering Transcriptions no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 6: transcrever um arquivo de áudio com maior precisão usando um vocabulário personalizado

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e usa um filtro de vocabulário que você criou anteriormente para mascarar palavras indesejadas.

```
aws transcribe start-transcription-job \
    --cli-input-json file://mysixthfile.json
```

Conteúdo de `mysixthfile.json`:

```
{
    "TranscriptionJobName": "cli-vocab-job",
    "LanguageCode": "the-language-of-your-transcription-job",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    },
    "Settings":{
        "VocabularyName": "your-vocabulary"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-vocab-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "the-language-of-your-transcription-job",
        "Media": {
```

```
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
        },
        "StartTime": "2020-09-18T16:36:18.568000+00:00",
        "CreationTime": "2020-09-18T16:36:18.547000+00:00",
        "Settings": {
            "VocabularyName": "your-vocabulary"
        }
    }
}
```

Consulte mais informações em Filtering Transcriptions no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 7: identificar o idioma de um arquivo de áudio e transcrevê-lo

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e usa um filtro de vocabulário que você criou anteriormente para mascarar palavras indesejadas.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myseventhfile.json
```

Conteúdo de `myseventhfile.json`:

```
{
    "TranscriptionJobName": "cli-identify-language-transcription-job",
    "IdentifyLanguage": true,
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-identify-language-transcription-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/Amazon-S3-prefix/your-media-
file-name.file-extension"
```

```
        },
        "StartTime": "2020-09-18T22:27:23.970000+00:00",
        "CreationTime": "2020-09-18T22:27:23.948000+00:00",
        "IdentifyLanguage": true
    }
}
```

Consulte mais informações em Identifying the Language no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 8: transcrever um arquivo de áudio com informações de identificação pessoal editadas

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio e oculta qualquer informação de identificação pessoal na saída da transcrição.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myeighthfile.json
```

Conteúdo de `myeigthfile.json`:

```
{
    "TranscriptionJobName": "cli-redaction-job",
    "LanguageCode": "language-code",
    "Media": {
        "MediaFileUri": "s3://Amazon-S3-Prefix/your-media-file.file-extension"
    },
    "ContentRedaction": {
        "RedactionOutput":"redacted",
        "RedactionType":"PII"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-redaction-job",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
```

```
            "MediaFileUri": "s3://Amazon-S3-Prefix/your-media-file.file-
extension"
        },
        "StartTime": "2020-09-25T23:49:13.195000+00:00",
        "CreationTime": "2020-09-25T23:49:13.176000+00:00",
        "ContentRedaction": {
            "RedactionType": "PII",
            "RedactionOutput": "redacted"
        }
    }
}
```

Consulte mais informações em Automatic Content Redaction no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 9: gerar uma transcrição com informações de identificação pessoal (PII) editadas e uma transcrição não editada

O exemplo de `start-transcription-job` a seguir gera duas transcrições do arquivo de áudio, uma com as informações de identificação pessoal editadas e a outra sem nenhuma edição.

```
aws transcribe start-transcription-job \
    --cli-input-json file://myninthfile.json
```

Conteúdo de `myninthfile.json`:

```
{
    "TranscriptionJobName": "cli-redaction-job-with-unredacted-transcript",
    "LanguageCode": "language-code",
    "Media": {
          "MediaFileUri": "s3://Amazon-S3-Prefix/your-media-file.file-extension"
        },
    "ContentRedaction": {
        "RedactionOutput":"redacted_and_unredacted",
        "RedactionType":"PII"
    }
}
```

Saída:

```
{
```

```
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-redaction-job-with-unredacted-transcript",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://Amazon-S3-Prefix/your-media-file.file-
extension"
        },
        "StartTime": "2020-09-25T23:59:47.677000+00:00",
        "CreationTime": "2020-09-25T23:59:47.653000+00:00",
        "ContentRedaction": {
            "RedactionType": "PII",
            "RedactionOutput": "redacted_and_unredacted"
        }
    }
}
```

Consulte mais informações em Automatic Content Redaction no Guia do desenvolvedor do Amazon Transcribe.

Exemplo 10: usar um modelo de linguagem personalizado que você criou anteriormente para transcrever um arquivo de áudio.

O exemplo de `start-transcription-job` a seguir transcreve o arquivo de áudio com um modelo de idioma personalizado que você criou anteriormente.

```
aws transcribe start-transcription-job \
    --cli-input-json file://mytenthfile.json
```

Conteúdo de `mytenthfile.json`:

```
{
    "TranscriptionJobName": "cli-clm-2-job-1",
    "LanguageCode": "language-code",
    "Media": {
        "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.file-extension"
    },
    "ModelSettings": {
        "LanguageModelName":"cli-clm-2"
    }
}
```

Saída:

```
{
    "TranscriptionJob": {
        "TranscriptionJobName": "cli-clm-2-job-1",
        "TranscriptionJobStatus": "IN_PROGRESS",
        "LanguageCode": "language-code",
        "Media": {
            "MediaFileUri": "s3://DOC-EXAMPLE-BUCKET/your-audio-file.file-
extension"
        },
        "StartTime": "2020-09-28T17:56:01.835000+00:00",
        "CreationTime": "2020-09-28T17:56:01.801000+00:00",
        "ModelSettings": {
            "LanguageModelName": "cli-clm-2"
        }
    }
}
```

Consulte mais informações em Improving Domain-Specific Transcription Accuracy with Custom Language Models no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte StartTranscriptionJobem Referência de AWS CLI Comandos.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class TranscribeStreamingDemoApp {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[])
```

```
            throws URISyntaxException, ExecutionException, InterruptedException,
LineUnavailableException {

        client = TranscribeStreamingAsyncClient.builder()
                .credentialsProvider(getCredentials())
                .region(REGION)
                .build();

        CompletableFuture<Void> result =
client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromMic()),
                getResponseHandler());

        result.get();
        client.close();
    }

    private static InputStream getStreamFromMic() throws LineUnavailableException
{

        // Signed PCM AudioFormat with 16kHz, 16 bit sample size, mono
        int sampleRate = 16000;
        AudioFormat format = new AudioFormat(sampleRate, 16, 1, true, false);
        DataLine.Info info = new DataLine.Info(TargetDataLine.class, format);

        if (!AudioSystem.isLineSupported(info)) {
            System.out.println("Line not supported");
            System.exit(0);
        }

        TargetDataLine line = (TargetDataLine) AudioSystem.getLine(info);
        line.open(format);
        line.start();

        InputStream audioStream = new AudioInputStream(line);
        return audioStream;
    }

    private static AwsCredentialsProvider getCredentials() {
        return DefaultCredentialsProvider.create();
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
mediaSampleRateHertz) {
```

```
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US.toString())
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
                    System.out.println("=== All records stream successfully
 ===");
                })
                .subscriber(event -> {
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {

 System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private InputStream getStreamFromFile(String audioFileName) {
        try {
            File inputFile = new
 File(getClass().getClassLoader().getResource(audioFileName).getFile());
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
```

```
        }
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }

        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);

        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream
 inputStream) {
            this.subscriber = s;
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
 positive"));
            }
```

```
            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];

            int len = 0;
            try {
                len = inputStream.read(audioBytes);

                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
```

```
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for Java 2.x da API.

JavaScript

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicie um trabalho de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  TranscriptionJobName: "JOB_NAME",
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_LOCATION",
    // For example, "https://transcribe-demo.s3-REGION.amazonaws.com/
hello_world.wav"
  },
  OutputBucketName: "OUTPUT_BUCKET_NAME"
```

```
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for JavaScript da API.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def start_job(
    job_name,
    media_uri,
    media_format,
    language_code,
    transcribe_client,
    vocabulary_name=None,
):
    """
    Starts a transcription job. This function returns as soon as the job is
 started.
    To get the current status of the job, call get_transcription_job. The job is
    successfully completed when the job status is 'COMPLETED'.

    :param job_name: The name of the transcription job. This must be unique for
                     your AWS account.
    :param media_uri: The URI where the audio file is stored. This is typically
                      in an Amazon S3 bucket.
    :param media_format: The format of the audio file. For example, mp3 or wav.
    :param language_code: The language code of the audio file.
                          For example, en-US or ja-JP
    :param transcribe_client: The Boto3 Transcribe client.
    :param vocabulary_name: The name of a custom vocabulary to use when
 transcribing
                             the audio file.
    :return: Data about the job.
    """
    try:
        job_args = {
            "TranscriptionJobName": job_name,
            "Media": {"MediaFileUri": media_uri},
            "MediaFormat": media_format,
            "LanguageCode": language_code,
        }
        if vocabulary_name is not None:
            job_args["Settings"] = {"VocabularyName": vocabulary_name}
        response = transcribe_client.start_transcription_job(**job_args)
        job = response["TranscriptionJob"]
        logger.info("Started transcription job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't start transcription job %s.", job_name)
        raise
    else:
```

```
        return job
```

- Para obter detalhes da API, consulte a StartTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Atualize um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como atualizar um vocabulário personalizado do Amazon Transcribe.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Crie e refine um vocabulário personalizado

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Update a custom vocabulary with new values. Update overwrites all
existing information.
   /// </summary>
   /// <param name="languageCode">The language code of the vocabulary.</param>
   /// <param name="phrases">Phrases to use in the vocabulary.</param>
   /// <param name="vocabularyName">Name for the vocabulary.</param>
   /// <returns>The state of the custom vocabulary.</returns>
   public async Task<VocabularyState> UpdateCustomVocabulary(LanguageCode
languageCode,
```

```
        List<string> phrases, string vocabularyName)
    {
        var response = await _amazonTranscribeService.UpdateVocabularyAsync(
            new UpdateVocabularyRequest()
            {
                LanguageCode = languageCode,
                Phrases = phrases,
                VocabularyName = vocabularyName
            });
        return response.VocabularyState;
    }
```

- Para obter detalhes da API, consulte UpdateVocabulary a Referência AWS SDK for .NET da API.

CLI

AWS CLI

Para atualizar um vocabulário personalizado com novos termos.

O exemplo de `update-vocabulary` a seguir substitui os termos usados para criar um vocabulário personalizado com novos que você fornece. Pré-requisito: para substituir os termos em um vocabulário personalizado, você precisa de um arquivo com novos termos.

```
aws transcribe update-vocabulary \
    --vocabulary-file-uri s3://DOC-EXAMPLE-BUCKET/Amazon-S3-Prefix/custom-
vocabulary.txt \
    --vocabulary-name custom-vocabulary \
    --language-code language-code
```

Saída:

```
{
    "VocabularyName": "custom-vocabulary",
    "LanguageCode": "language",
    "VocabularyState": "PENDING"
}
```

Consulte mais informações em Custom Vocabularies no Guia do desenvolvedor do Amazon Transcribe.

- Para obter detalhes da API, consulte UpdateVocabularyem Referência de AWS CLI Comandos.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None,
 table_uri=None
):
    """
    Updates an existing custom vocabulary. The entire vocabulary is replaced with
    the contents of the update.

    :param vocabulary_name: The name of the vocabulary to update.
    :param language_code: The language code of the vocabulary.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the
 vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in
 the
                      vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.update_vocabulary(**vocab_args)
        logger.info("Updated custom vocabulary %s.", response["VocabularyName"])
```

```
    except ClientError:
        logger.exception("Couldn't update custom vocabulary %s.",
vocabulary_name)
        raise
```

- Para obter detalhes da API, consulte a UpdateVocabularyReferência da API AWSSDK for Python (Boto3).

Cenários para Amazon Transcribe usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Transcribe com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Crie e refine um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS
- Transcreva áudio e obtenha dados de trabalho com o Amazon Transcribe usando um SDK da AWS

Crie e refine um vocabulário personalizado do Amazon Transcribe usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Fazer upload do arquivo de áudio para o Amazon S3.
- Execute um trabalho do Amazon Transcribe para transcrever o arquivo e obter os resultados.
- Crie e refine um vocabulário personalizado para melhorar a precisão da transcrição.
- Execute trabalhos com vocabulários personalizados e obtenha os resultados.

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Transcreva um arquivo de áudio que contenha uma leitura de Jabberwocky de Lewis Carroll. Comece criando funções que envolvam as ações do Amazon Transcribe.

```
def start_job(
    job_name,
    media_uri,
    media_format,
    language_code,
    transcribe_client,
    vocabulary_name=None,
):
    """
    Starts a transcription job. This function returns as soon as the job is
 started.
    To get the current status of the job, call get_transcription_job. The job is
    successfully completed when the job status is 'COMPLETED'.

    :param job_name: The name of the transcription job. This must be unique for
                     your AWS account.
    :param media_uri: The URI where the audio file is stored. This is typically
                      in an Amazon S3 bucket.
    :param media_format: The format of the audio file. For example, mp3 or wav.
    :param language_code: The language code of the audio file.
                          For example, en-US or ja-JP
    :param transcribe_client: The Boto3 Transcribe client.
    :param vocabulary_name: The name of a custom vocabulary to use when
 transcribing
                             the audio file.
    :return: Data about the job.
    """
    try:
        job_args = {
```

```
            "TranscriptionJobName": job_name,
            "Media": {"MediaFileUri": media_uri},
            "MediaFormat": media_format,
            "LanguageCode": language_code,
        }
        if vocabulary_name is not None:
            job_args["Settings"] = {"VocabularyName": vocabulary_name}
        response = transcribe_client.start_transcription_job(**job_args)
        job = response["TranscriptionJob"]
        logger.info("Started transcription job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't start transcription job %s.", job_name)
        raise
    else:
        return job



def get_job(job_name, transcribe_client):
    """
    Gets details about a transcription job.

    :param job_name: The name of the job to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The retrieved transcription job.
    """
    try:
        response = transcribe_client.get_transcription_job(
            TranscriptionJobName=job_name
        )
        job = response["TranscriptionJob"]
        logger.info("Got job %s.", job["TranscriptionJobName"])
    except ClientError:
        logger.exception("Couldn't get job %s.", job_name)
        raise
    else:
        return job



def delete_job(job_name, transcribe_client):
    """
    Deletes a transcription job. This also deletes the transcript associated with
    the job.
```

```
    :param job_name: The name of the job to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_transcription_job(TranscriptionJobName=job_name)
        logger.info("Deleted job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't delete job %s.", job_name)
        raise



def create_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None,
 table_uri=None
):
    """
    Creates a custom vocabulary that can be used to improve the accuracy of
    transcription jobs. This function returns as soon as the vocabulary
 processing
    is started. Call get_vocabulary to get the current status of the vocabulary.
    The vocabulary is ready to use when its status is 'READY'.

    :param vocabulary_name: The name of the custom vocabulary.
    :param language_code: The language code of the vocabulary.
                          For example, en-US or nl-NL.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the
 vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in
 the
                      vocabulary.
    :return: Information about the newly created vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.create_vocabulary(**vocab_args)
        logger.info("Created custom vocabulary %s.", response["VocabularyName"])
```

```
    except ClientError:
        logger.exception("Couldn't create custom vocabulary %s.",
 vocabulary_name)
        raise
    else:
        return response



def get_vocabulary(vocabulary_name, transcribe_client):
    """
    Gets information about a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: Information about the vocabulary.
    """
    try:
        response =
 transcribe_client.get_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Got vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't get vocabulary %s.", vocabulary_name)
        raise
    else:
        return response



def update_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None,
 table_uri=None
):
    """
    Updates an existing custom vocabulary. The entire vocabulary is replaced with
    the contents of the update.

    :param vocabulary_name: The name of the vocabulary to update.
    :param language_code: The language code of the vocabulary.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the
 vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in
 the
```

```
                        vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.update_vocabulary(**vocab_args)
        logger.info("Updated custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't update custom vocabulary %s.",
 vocabulary_name)
        raise



def list_vocabularies(vocabulary_filter, transcribe_client):
    """
    Lists the custom vocabularies created for this AWS account.

    :param vocabulary_filter: The returned vocabularies must contain this string
 in
                              their names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved vocabularies.
    """
    try:
        response =
 transcribe_client.list_vocabularies(NameContains=vocabulary_filter)
        vocabs = response["Vocabularies"]
        next_token = response.get("NextToken")
        while next_token is not None:
            response = transcribe_client.list_vocabularies(
                NameContains=vocabulary_filter, NextToken=next_token
            )
            vocabs += response["Vocabularies"]
            next_token = response.get("NextToken")
        logger.info(
            "Got %s vocabularies with filter %s.", len(vocabs), vocabulary_filter
        )
    except ClientError:
        logger.exception(
```

```
            "Couldn't list vocabularies with filter %s.", vocabulary_filter
        )
        raise
    else:
        return vocabs



def delete_vocabulary(vocabulary_name, transcribe_client):
    """
    Deletes a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Deleted vocabulary %s.", vocabulary_name)
    except ClientError:
        logger.exception("Couldn't delete vocabulary %s.", vocabulary_name)
        raise
```

Chame as funções do wrapper para transcrever áudio sem um vocabulário personalizado e, em seguida, com diferentes versões de um vocabulário personalizado para ver os melhores resultados.

```
def usage_demo():
    """Shows how to use the Amazon Transcribe service."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    s3_resource = boto3.resource("s3")
    transcribe_client = boto3.client("transcribe")

    print("-" * 88)
    print("Welcome to the Amazon Transcribe demo!")
    print("-" * 88)

    bucket_name = f"jabber-bucket-{time.time_ns()}"
    print(f"Creating bucket {bucket_name}.")
    bucket = s3_resource.create_bucket(
```

```
        Bucket=bucket_name,
        CreateBucketConfiguration={
            "LocationConstraint": transcribe_client.meta.region_name
        },
    )
    media_file_name = ".media/Jabberwocky.mp3"
    media_object_key = "Jabberwocky.mp3"
    print(f"Uploading media file {media_file_name}.")
    bucket.upload_file(media_file_name, media_object_key)
    media_uri = f"s3://{bucket.name}/{media_object_key}"

    job_name_simple = f"Jabber-{time.time_ns()}"
    print(f"Starting transcription job {job_name_simple}.")
    start_job(
        job_name_simple,
        f"s3://{bucket_name}/{media_object_key}",
        "mp3",
        "en-US",
        transcribe_client,
    )
    transcribe_waiter = TranscribeCompleteWaiter(transcribe_client)
    transcribe_waiter.wait(job_name_simple)
    job_simple = get_job(job_name_simple, transcribe_client)
    transcript_simple = requests.get(
        job_simple["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_simple['jobName']}:")
    print(transcript_simple["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print(
        "Creating a custom vocabulary that lists the nonsense words to try to "
        "improve the transcription."
    )
    vocabulary_name = f"Jabber-vocabulary-{time.time_ns()}"
    create_vocabulary(
        vocabulary_name,
        "en-US",
        transcribe_client,
        phrases=[
            "brillig",
            "slithy",
            "borogoves",
            "mome",
```

```
            "raths",
            "Jub-Jub",
            "frumious",
            "manxome",
            "Tumtum",
            "uffish",
            "whiffling",
            "tulgey",
            "thou",
            "frabjous",
            "callooh",
            "callay",
            "chortled",
        ],
    )
    vocabulary_ready_waiter = VocabularyReadyWaiter(transcribe_client)
    vocabulary_ready_waiter.wait(vocabulary_name)

    job_name_vocabulary_list = f"Jabber-vocabulary-list-{time.time_ns()}"
    print(f"Starting transcription job {job_name_vocabulary_list}.")
    start_job(
        job_name_vocabulary_list,
        media_uri,
        "mp3",
        "en-US",
        transcribe_client,
        vocabulary_name,
    )
    transcribe_waiter.wait(job_name_vocabulary_list)
    job_vocabulary_list = get_job(job_name_vocabulary_list, transcribe_client)
    transcript_vocabulary_list = requests.get(
        job_vocabulary_list["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_vocabulary_list['jobName']}:")
    print(transcript_vocabulary_list["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print(
        "Updating the custom vocabulary with table data that provides additional
"
        "pronunciation hints."
    )
    table_vocab_file = "jabber-vocabulary-table.txt"
    bucket.upload_file(table_vocab_file, table_vocab_file)
```

```
    update_vocabulary(
        vocabulary_name,
        "en-US",
        transcribe_client,
        table_uri=f"s3://{bucket.name}/{table_vocab_file}",
    )
    vocabulary_ready_waiter.wait(vocabulary_name)

    job_name_vocab_table = f"Jabber-vocab-table-{time.time_ns()}"
    print(f"Starting transcription job {job_name_vocab_table}.")
    start_job(
        job_name_vocab_table,
        media_uri,
        "mp3",
        "en-US",
        transcribe_client,
        vocabulary_name=vocabulary_name,
    )
    transcribe_waiter.wait(job_name_vocab_table)
    job_vocab_table = get_job(job_name_vocab_table, transcribe_client)
    transcript_vocab_table = requests.get(
        job_vocab_table["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_vocab_table['jobName']}:")
    print(transcript_vocab_table["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print("Getting data for jobs and vocabularies.")
    jabber_jobs = list_jobs("Jabber", transcribe_client)
    print(f"Found {len(jabber_jobs)} jobs:")
    for job_sum in jabber_jobs:
        job = get_job(job_sum["TranscriptionJobName"], transcribe_client)
        print(
            f"\t{job['TranscriptionJobName']}, {job['Media']['MediaFileUri']}, "
            f"{job['Settings'].get('VocabularyName')}"
        )

    jabber_vocabs = list_vocabularies("Jabber", transcribe_client)
    print(f"Found {len(jabber_vocabs)} vocabularies:")
    for vocab_sum in jabber_vocabs:
        vocab = get_vocabulary(vocab_sum["VocabularyName"], transcribe_client)
        vocab_content = requests.get(vocab["DownloadUri"]).text
        print(f"\t{vocab['VocabularyName']} contents:")
        print(vocab_content)
```

```
    print("-" * 88)
    print("Deleting demo jobs.")
    for job_name in [job_name_simple, job_name_vocabulary_list,
job_name_vocab_table]:
        delete_job(job_name, transcribe_client)
    print("Deleting demo vocabulary.")
    delete_vocabulary(vocabulary_name, transcribe_client)
    print("Deleting demo bucket.")
    bucket.objects.delete()
    bucket.delete()
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateVocabulary
  - DeleteTranscriptionJob
  - DeleteVocabulary
  - GetTranscriptionJob
  - GetVocabulary
  - ListVocabularies
  - StartTranscriptionJob
  - UpdateVocabulary

Transcreva áudio e obtenha dados de trabalho com o Amazon Transcribe usando um SDK da AWS

Os exemplos de código a seguir mostram como:

- Inicie um trabalho de transcrição com o Amazon Transcribe.
- Aguarde a conclusão do trabalho .
- Obtenha a URI em que a transcrição está armazenada.

Para obter mais informações, consulte Começar a usar o Amazon Transcribe.

Java

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Transcreve um arquivo PCM.

```
/**
 * To run this AWS code example, ensure that you have set up your development
 * environment, including your AWS credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-
started.html
 */

public class TranscribeStreamingDemoFile {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[]) throws ExecutionException,
 InterruptedException {

        final String USAGE = "\n" +
                "Usage:\n" +
                "    <file> \n\n" +
                "Where:\n" +
                "    file - the location of a PCM file to transcribe. In this
 example, ensure the PCM file is 16 hertz (Hz). \n";

        if (args.length != 1) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String file = args[0];
        client = TranscribeStreamingAsyncClient.builder()
```

```
                .region(REGION)
                .build();

        CompletableFuture<Void> result =
client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromFile(file)),
                getResponseHandler());

        result.get();
        client.close();
    }

    private static InputStream getStreamFromFile(String file) {
        try {
            File inputFile = new File(file);
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;

        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
mediaSampleRateHertz) {
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US)
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
```

```
                    System.out.println("=== All records stream successfully
 ===");
                })
                .subscriber(event -> {
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {

 System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }

        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);
```

```
        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream
inputStream) {
            this.subscriber = s;
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
positive"));
            }

            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];
```

```
            int len = 0;
            try {
                len = inputStream.read(audioBytes);

                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

Transcreve o streaming de áudio do microfone do computador.

```
public class TranscribeStreamingDemoApp {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[])
            throws URISyntaxException, ExecutionException, InterruptedException,
 LineUnavailableException {

        client = TranscribeStreamingAsyncClient.builder()
                .credentialsProvider(getCredentials())
                .region(REGION)
                .build();

        CompletableFuture<Void> result =
 client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromMic()),
```

```
                getResponseHandler());

        result.get();
        client.close();
    }

    private static InputStream getStreamFromMic() throws LineUnavailableException
{

        // Signed PCM AudioFormat with 16kHz, 16 bit sample size, mono
        int sampleRate = 16000;
        AudioFormat format = new AudioFormat(sampleRate, 16, 1, true, false);
        DataLine.Info info = new DataLine.Info(TargetDataLine.class, format);

        if (!AudioSystem.isLineSupported(info)) {
            System.out.println("Line not supported");
            System.exit(0);
        }

        TargetDataLine line = (TargetDataLine) AudioSystem.getLine(info);
        line.open(format);
        line.start();

        InputStream audioStream = new AudioInputStream(line);
        return audioStream;
    }

    private static AwsCredentialsProvider getCredentials() {
        return DefaultCredentialsProvider.create();
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
mediaSampleRateHertz) {
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US.toString())
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
```

```
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
                    System.out.println("=== All records stream successfully
 ===");
                })
                .subscriber(event -> {
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {

 System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private InputStream getStreamFromFile(String audioFileName) {
        try {
            File inputFile = new
 File(getClass().getClassLoader().getResource(audioFileName).getFile());
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }
```

```
        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);

        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream
 inputStream) {
            this.subscriber = s;
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
 positive"));
            }

            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
 audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
```

```
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];

            int len = 0;
            try {
                len = inputStream.read(audioBytes);

                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetTranscriptionJob
  - StartTranscriptionJob

Python

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import time
import boto3


def transcribe_file(job_name, file_uri, transcribe_client):
    transcribe_client.start_transcription_job(
        TranscriptionJobName=job_name,
        Media={"MediaFileUri": file_uri},
        MediaFormat="wav",
        LanguageCode="en-US",
    )

    max_tries = 60
    while max_tries > 0:
        max_tries -= 1
        job =
 transcribe_client.get_transcription_job(TranscriptionJobName=job_name)
        job_status = job["TranscriptionJob"]["TranscriptionJobStatus"]
        if job_status in ["COMPLETED", "FAILED"]:
            print(f"Job {job_name} is {job_status}.")
            if job_status == "COMPLETED":
                print(
                    f"Download the transcript from\n"
                    f"\t{job['TranscriptionJob']['Transcript']
['TranscriptFileUri']}."
                )
```

```
            break
        else:
            print(f"Waiting for {job_name}. Current status is {job_status}.")
        time.sleep(10)


def main():
    transcribe_client = boto3.client("transcribe")
    file_uri = "s3://test-transcribe/answer2.wav"
    transcribe_file("Example-job", file_uri, transcribe_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - GetTranscriptionJob
  - StartTranscriptionJob

Exemplos entre serviços do Amazon Transcribe usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Transcribe com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação Amazon Transcribe
- Criar uma aplicação de transmissão do Amazon Transcribe
- Converter texto em fala e de volta em texto usando um AWS SDK

Criar uma aplicação Amazon Transcribe

O exemplo de código a seguir mostra como usar o Amazon Transcribe para transcrever e exibir gravações de voz no navegador.

JavaScript

SDK para JavaScript (v3)

Crie uma aplicação que use o Amazon Transcribe para transcrever e exibir gravações de voz no navegador. A aplicação usa dois buckets do Amazon Simple Storage Service (Amazon S3), um para hospedar o código da aplicação e outro para armazenar transcrições. A aplicação usa um grupo de usuários do Amazon Cognito para autenticar seus usuários. Os usuários autenticados têm permissões do AWS Identity and Access Management (IAM) para acessar os serviços da AWS necessários.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon Transcribe

Criar uma aplicação de transmissão do Amazon Transcribe

O exemplo de código a seguir mostra como construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Transcribe para construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend

- Amazon SES
- Amazon Transcribe
- Amazon Translate

Converter texto em fala e de volta em texto usando um AWS SDK

O código de exemplo a seguir mostra como:

- Usar o Amazon Polly para sintetizar um arquivo de entrada de texto simples (UTF-8) para um arquivo de áudio.
- Faça upload do arquivo de áudio para um bucket do Amazon S3.
- Usar o Amazon Transcribe para converter o arquivo de áudio em texto.
- Exibir o texto.

Rust

SDK for Rust

Use o Amazon Polly para sintetizar um arquivo de texto simples (UTF-8) para um arquivo de áudio, fazer upload do arquivo de áudio para um bucket do Amazon S3, usar o Amazon Transcribe para converter esse arquivo de áudio em texto e exibir o texto.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly
- Amazon S3
- Amazon Transcribe

Exemplos de código para o Amazon Translate usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Translate com um Kit de Desenvolvimento de Software (SDK) da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do Amazon Translate – Mais informações sobre o Amazon Translate.
- Referência da API do Amazon Translate – Detalhes sobre todas as ações disponíveis do Amazon Translate.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações do Amazon Translate usando SDKs da AWS
  - Descreva um trabalho de tradução do Amazon Translate usando um SDK da AWS
  - Liste trabalhos de tradução do Amazon Translate usando um SDK da AWS
  - Inicie um trabalho de tradução do Amazon Translate usando um SDK da AWS
  - Interrompa um trabalho de tradução do Amazon Translate usando um SDK da AWS
  - Traduza textos com o Amazon Translate usando um SDK da AWS
- Cenários para Amazon Translate usando SDKs da AWS
  - Comece a usar trabalhos do Amazon Translate usando um SDK da AWS
- Exemplos entre serviços do Amazon Translate usando SDKs da AWS
  - Criar uma aplicação de transmissão do Amazon Transcribe
  - Crie um chatbot do Amazon Lex para engajar os visitantes do seu site
  - Criar uma aplicação de publicação e assinatura que traduz mensagens
  - Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Ações do Amazon Translate usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Translate com SDKs da AWS. Cada exemplo chama uma função de serviço individual.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. Você pode ver as ações em contexto em Cenários para Amazon Translate usando SDKs da AWS.

Exemplos

- Descreva um trabalho de tradução do Amazon Translate usando um SDK da AWS
- Liste trabalhos de tradução do Amazon Translate usando um SDK da AWS
- Inicie um trabalho de tradução do Amazon Translate usando um SDK da AWS
- Interrompa um trabalho de tradução do Amazon Translate usando um SDK da AWS
- Traduza textos com o Amazon Translate usando um SDK da AWS

Descreva um trabalho de tradução do Amazon Translate usando um SDK da AWS

Os exemplos de código a seguir mostram como descrever um trabalho de tradução do Amazon Translate.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar trabalhos de tradução

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
```

```
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// The following example shows how to retrieve the details of
    /// a text translation job using Amazon Translate.
    /// </summary>
    public class DescribeTextTranslation
    {
        public static async Task Main()
        {
            var client = new AmazonTranslateClient();

            // The Job Id is generated when the text translation job is started
            // with a call to the StartTextTranslationJob method.
            var jobId = "1234567890abcdef01234567890abcde";

            var request = new DescribeTextTranslationJobRequest
            {
                JobId = jobId,
            };

            var jobProperties = await DescribeTranslationJobAsync(client,
 request);

            DisplayTranslationJobDetails(jobProperties);
        }

        /// <summary>
        /// Retrieve information about an Amazon Translate text translation job.
        /// </summary>
        /// <param name="client">The initialized Amazon Translate client
 object.</param>
        /// <param name="request">The DescribeTextTranslationJobRequest object.</
param>
        /// <returns>The TextTranslationJobProperties object containing
        /// information about the text translation job..</returns>
        public static async Task<TextTranslationJobProperties>
 DescribeTranslationJobAsync(
            AmazonTranslateClient client,
            DescribeTextTranslationJobRequest request)
        {
            var response = await client.DescribeTextTranslationJobAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
```

```
            {
                return response.TextTranslationJobProperties;
            }
            else
            {
                return null;
            }
        }

        /// <summary>
        /// Displays the properties of the text translation job.
        /// </summary>
        /// <param name="jobProperties">The properties of the text translation
        /// job returned by the call to DescribeTextTranslationJobAsync.</param>
        public static void
DisplayTranslationJobDetails(TextTranslationJobProperties jobProperties)
        {
            if (jobProperties is null)
            {
                Console.WriteLine("No text translation job properties found.");
                return;
            }

            // Display the details of the text translation job.
            Console.WriteLine($"{jobProperties.JobId}: {jobProperties.JobName}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeTextTranslationJoba Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Gets the properties associated with an asynchronous batch translation job."
   "Includes properties such as name, ID, status, source and target languages,
and input/output Amazon Simple Storage Service (Amazon S3) buckets."
   TRY.
       oo_result = lo_xl8->describetexttranslationjob(      "oo_result is
returned for testing purposes."
         EXPORTING
           iv_jobid        = iv_jobid
         ).
       MESSAGE 'Job description retrieved.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE
'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Liste trabalhos de tradução do Amazon Translate usando um SDK da AWS

Os exemplos de código a seguir mostram como listar os trabalhos de tradução do Amazon Translate.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
```

```
   using System.Threading.Tasks;
   using Amazon.Translate;
   using Amazon.Translate.Model;

   /// <summary>
   /// List Amazon Translate translation jobs, along with details about each
job.
   /// </summary>
   public class ListTranslationJobs
   {
       public static async Task Main()
       {
           var client = new AmazonTranslateClient();
           var filter = new TextTranslationJobFilter
           {
               JobStatus = "COMPLETED",
           };

           var request = new ListTextTranslationJobsRequest
           {
               MaxResults = 10,
               Filter = filter,
           };

           await ListJobsAsync(client, request);
       }

       /// <summary>
       /// List Amazon Translate text translation jobs.
       /// </summary>
       /// <param name="client">The initialized Amazon Translate client
object.</param>
       /// <param name="request">An Amazon Translate
       /// ListTextTranslationJobsRequest object detailing which text
       /// translation jobs are of interest.</param>
       public static async Task ListJobsAsync(
           AmazonTranslateClient client,
           ListTextTranslationJobsRequest request)
       {
           ListTextTranslationJobsResponse response;

           do
           {
               response = await client.ListTextTranslationJobsAsync(request);
```

```
ShowTranslationJobDetails(response.TextTranslationJobPropertiesList);

                request.NextToken = response.NextToken;
            }
            while (response.NextToken is not null);
        }

        /// <summary>
        /// List existing translation job details.
        /// </summary>
        /// <param name="properties">A list of Amazon Translate text
        /// translation jobs.</param>
        public static void
ShowTranslationJobDetails(List<TextTranslationJobProperties> properties)
        {
            properties.ForEach(prop =>
            {
                Console.WriteLine($"{prop.JobId}: {prop.JobName}");
                Console.WriteLine($"Status: {prop.JobStatus}");
                Console.WriteLine($"Submitted time: {prop.SubmittedTime}");
            });
        }
    }
```

- Para obter detalhes da API, consulte ListTextTranslationJobsa Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Gets a list of the batch translation jobs that you have submitted."
```

```
   DATA lo_filter TYPE REF TO /aws1/cl_xl8textxlationjobfilt.

   "Create an ABAP object for filtering using jobname."
   CREATE OBJECT lo_filter
     EXPORTING
       iv_jobname = iv_jobname.

   TRY.
       oo_result = lo_xl8->listtexttranslationjobs(      "oo_result is returned
for testing purposes."
         EXPORTING
           io_filter        = lo_filter
         ).
       MESSAGE 'Jobs retrieved.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE
'E'.
     CATCH /aws1/cx_xl8invalidfilterex .
       MESSAGE 'The filter specified for the operation is not valid. Specify a
different filter.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex .
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListTextTranslationJobsreferência da API AWS SDK for SAP ABAP.

Inicie um trabalho de tradução do Amazon Translate usando um SDK da AWS

Os exemplos de código a seguir mostram como iniciar um trabalho de tradução do Amazon Translate.

Exemplos de ações são trechos de código de programas maiores e devem ser executados em contexto. É possível ver essa ação no contexto no seguinte exemplo de código:

- Começar a usar trabalhos de tradução

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// This example shows how to use Amazon Translate to process the files in
    /// an Amazon Simple Storage Service (Amazon S3) bucket. The translated
 results
    /// will also be stored in an Amazon S3 bucket.
    /// </summary>
    public class BatchTranslate
    {
        public static async Task Main()
        {
            var contentType = "text/plain";

            // Set this variable to an S3 bucket location with a folder."
            // Input files must be in a folder and not at the bucket root."
            var s3InputUri = "s3://DOC-EXAMPLE-BUCKET1/FOLDER/";
            var s3OutputUri = "s3://DOC-EXAMPLE-BUCKET2/";

            // This role must have permissions to read the source bucket and to
 read and
            // write to the destination bucket where the translated text will be
 stored.
            var dataAccessRoleArn = "arn:aws:iam::0123456789ab:role/
S3TranslateRole";

            var client = new AmazonTranslateClient();
```

```
            var inputConfig = new InputDataConfig
            {
                ContentType = contentType,
                S3Uri = s3InputUri,
            };

            var outputConfig = new OutputDataConfig
            {
                S3Uri = s3OutputUri,
            };

            var request = new StartTextTranslationJobRequest
            {
                JobName = "ExampleTranslationJob",
                DataAccessRoleArn = dataAccessRoleArn,
                InputDataConfig = inputConfig,
                OutputDataConfig = outputConfig,
                SourceLanguageCode = "en",
                TargetLanguageCodes = new List<string> { "fr" },
            };

            var response = await StartTextTranslationAsync(client, request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{response.JobId}: {response.JobStatus}");
            }
        }

        /// <summary>
        /// Start the Amazon Translate text translation job.
        /// </summary>
        /// <param name="client">The initialized AmazonTranslateClient object.</
param>
        /// <param name="request">The request object that includes details such
        /// as source and destination bucket names and the IAM Role that will
        /// be used to access the buckets.</param>
        /// <returns>The StartTextTranslationResponse object that includes the
        /// details of the request response.</returns>
        public static async Task<StartTextTranslationJobResponse>
 StartTextTranslationAsync(AmazonTranslateClient client,
 StartTextTranslationJobRequest request)
        {
            var response = await client.StartTextTranslationJobAsync(request);
```

```
            return response;
        }
    }
```

- Para obter detalhes da API, consulte StartTextTranslationJoba Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Starts an asynchronous batch translation job."
    "Use batch translation jobs to translate large volumes of text across
 multiple documents at once."

    DATA lo_inputdataconfig  TYPE REF TO /aws1/cl_xl8inputdataconfig.
    DATA lo_outputdataconfig TYPE REF TO /aws1/cl_xl8outputdataconfig.
    DATA lt_targetlanguagecodes TYPE /aws1/
cl_xl8tgtlanguagecodes00=>tt_targetlanguagecodestrlist.
    DATA lo_targetlanguagecodes TYPE REF TO /aws1/cl_xl8tgtlanguagecodes00.

    "Create an ABAP object for the input data config."
    CREATE OBJECT lo_inputdataconfig
      EXPORTING
        iv_s3uri       = iv_input_data_s3uri
        iv_contenttype = iv_input_data_contenttype.

    "Create an ABAP object for the output data config."
    CREATE OBJECT lo_outputdataconfig
      EXPORTING
        iv_s3uri = iv_output_data_s3uri.

    "Create an internal table for target languages."
```

```
   CREATE OBJECT lo_targetlanguagecodes
     EXPORTING
       iv_value = iv_targetlanguagecode.
   INSERT lo_targetlanguagecodes  INTO TABLE lt_targetlanguagecodes.

   TRY.
       oo_result = lo_xl8->starttexttranslationjob(      "oo_result is returned
for testing purposes."
         EXPORTING
           io_inputdataconfig = lo_inputdataconfig
           io_outputdataconfig = lo_outputdataconfig
           it_targetlanguagecodes = lt_targetlanguagecodes
           iv_dataaccessrolearn = iv_dataaccessrolearn
           iv_jobname = iv_jobname
           iv_sourcelanguagecode = iv_sourcelanguagecode
         ).
       MESSAGE 'Translation job started.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE
'E'.
     CATCH /aws1/cx_xl8invparamvalueex .
       MESSAGE 'The value of the parameter is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex.
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
     CATCH /aws1/cx_xl8unsuppedlanguage00 .
       MESSAGE 'Amazon Translate does not support translation from the language
of the source text into the requested target language.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a StartTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Interrompa um trabalho de tradução do Amazon Translate usando um SDK da AWS

Os exemplos de código a seguir mostram como interromper um trabalho de tradução do Amazon Translate.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Translate;
using Amazon.Translate.Model;

/// <summary>
/// Shows how to stop a running Amazon Translation Service text translation
/// job.
/// </summary>
public class StopTextTranslationJob
{
    public static async Task Main()
    {
        var client = new AmazonTranslateClient();
        var jobId = "1234567890abcdef01234567890abcde";

        var request = new StopTextTranslationJobRequest
        {
            JobId = jobId,
        };

        await StopTranslationJobAsync(client, request);
    }

    /// <summary>
    /// Sends a request to stop a text translation job.
    /// </summary>
    /// <param name="client">Initialized AmazonTrnslateClient object.</param>
    /// <param name="request">The request object to be passed to the
    /// StopTextJobAsync method.</param>
    public static async Task StopTranslationJobAsync(
        AmazonTranslateClient client,
```

```
            StopTextTranslationJobRequest request)
        {
            var response = await client.StopTextTranslationJobAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{response.JobId} as status:
{response.JobStatus}");
            }
        }
    }
```

- Para obter detalhes da API, consulte StopTextTranslationJoba Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Stops an asynchronous batch translation job that is in progress."

    TRY.
        oo_result = lo_xl8->stoptexttranslationjob(      "oo_result is returned
for testing purposes."
          EXPORTING
            iv_jobid        = iv_jobid
          ).
        MESSAGE 'Translation job stopped.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
        MESSAGE 'An internal server error occurred.' TYPE 'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
```

```
        MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a StopTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Traduza textos com o Amazon Translate usando um SDK da AWS

Os exemplos de código a seguir mostram como traduzir texto com o Amazon Translate.

.NET

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Transfer;
using Amazon.Translate;
using Amazon.Translate.Model;

/// <summary>
/// Take text from a file stored a Amazon Simple Storage Service (Amazon S3)
/// object and translate it using the Amazon Transfer Service.
/// </summary>
public class TranslateText
{
    public static async Task Main()
    {
        // If the region you want to use is different from the region
        // defined for the default user, supply it as a parameter to the
        // Amazon Translate client object constructor.
```

```
            var client = new AmazonTranslateClient();

            // Set the source language to "auto" to request Amazon Translate to
            // automatically detect te language of the source text.

            // You can get a list of the languages supposed by Amazon Translate
            // in the Amazon Translate Developer's Guide here:
            //      https://docs.aws.amazon.com/translate/latest/dg/what-is.html
            string srcLang = "en"; // English.
            string destLang = "fr"; // French.

            // The Amazon Simple Storage Service (Amazon S3) bucket where the
            // source text file is stored.
            string srcBucket = "DOC-EXAMPLE-BUCKET";
            string srcTextFile = "source.txt";

            var srcText = await GetSourceTextAsync(srcBucket, srcTextFile);
            var destText = await TranslatingTextAsync(client, srcLang, destLang,
srcText);

            ShowText(srcText, destText);
        }

        /// <summary>
        /// Use the Amazon S3 TransferUtility to retrieve the text to translate
        /// from an object in an S3 bucket.
        /// </summary>
        /// <param name="srcBucket">The name of the S3 bucket where the
        /// text is stored.
        /// </param>
        /// <param name="srcTextFile">The key of the S3 object that
        /// contains the text to translate.</param>
        /// <returns>A string representing the source text.</returns>
        public static async Task<string> GetSourceTextAsync(string srcBucket,
string srcTextFile)
        {
            string srcText = string.Empty;

            var s3Client = new AmazonS3Client();
            TransferUtility utility = new TransferUtility(s3Client);

            using var stream = await utility.OpenStreamAsync(srcBucket,
srcTextFile);
```

```
            StreamReader file = new System.IO.StreamReader(stream);

            srcText = file.ReadToEnd();
            return srcText;
        }

        /// <summary>
        /// Use the Amazon Translate Service to translate the document from the
        /// source language to the specified destination language.
        /// </summary>
        /// <param name="client">The Amazon Translate Service client used to
        /// perform the translation.</param>
        /// <param name="srcLang">The language of the source text.</param>
        /// <param name="destLang">The destination language for the translated
        /// text.</param>
        /// <param name="text">A string representing the text to ranslate.</
param>
        /// <returns>The text that has been translated to the destination
        /// language.</returns>
        public static async Task<string>
 TranslatingTextAsync(AmazonTranslateClient client, string srcLang, string
 destLang, string text)
        {
            var request = new TranslateTextRequest
            {
                SourceLanguageCode = srcLang,
                TargetLanguageCode = destLang,
                Text = text,
            };

            var response = await client.TranslateTextAsync(request);

            return response.TranslatedText;
        }

        /// <summary>
        /// Show the original text followed by the translated text.
        /// </summary>
        /// <param name="srcText">The original text to be translated.</param>
        /// <param name="destText">The translated text.</param>
        public static void ShowText(string srcText, string destText)
        {
            Console.WriteLine("Source text:");
            Console.WriteLine(srcText);
```

```
            Console.WriteLine();
            Console.WriteLine("Translated text:");
            Console.WriteLine(destText);
        }
    }
```

- Para obter detalhes da API, consulte TranslateTexta Referência AWS SDK for .NET da API.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Translates input text from the source language to the target language."
   TRY.
       oo_result = lo_xl8->translatetext(      "oo_result is returned for
testing purposes."
         EXPORTING
           iv_text        = iv_text
           iv_sourcelanguagecode = iv_sourcelanguagecode
           iv_targetlanguagecode = iv_targetlanguagecode
         ).
       MESSAGE 'Translation completed.' TYPE 'I'.
     CATCH /aws1/cx_xl8detectedlanguage00 .
       MESSAGE 'The confidence that Amazon Comprehend accurately detected the
source language is low.' TYPE 'E'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex .
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8serviceunavailex .
       MESSAGE 'The Amazon Translate service is temporarily unavailable.' TYPE
'E'.
```

```
      CATCH /aws1/cx_xl8textsizelmtexcdex .
        MESSAGE 'The size of the text you submitted exceeds the size limit. '
TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex .
        MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
      CATCH /aws1/cx_xl8unsuppedlanguage00 .
        MESSAGE 'Amazon Translate does not support translation from the language
of the source text into the requested target language. ' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a TranslateTextreferência da API AWS SDK for SAP ABAP.

Cenários para Amazon Translate usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Translate com SDKs da AWS. Cada exemplo mostra como realizar uma tarefa específica chamando diversas funções no mesmo serviço.

Os cenários têm como alvo um nível intermediário de experiência para ajudá-lo a entender as ações de serviço no contexto.

Exemplos

- Comece a usar trabalhos do Amazon Translate usando um SDK da AWS

Comece a usar trabalhos do Amazon Translate usando um SDK da AWS

O código de exemplo a seguir mostra como:

- Iniciar um trabalho de tradução em lote assíncrono.
- Aguardar a conclusão do trabalho assíncrono.
- Descrever o trabalho assíncrono.

SAP ABAP

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_inputdataconfig  TYPE REF TO /aws1/cl_xl8inputdataconfig.
    DATA lo_outputdataconfig TYPE REF TO /aws1/cl_xl8outputdataconfig.
    DATA lt_targetlanguagecodes TYPE /aws1/
cl_xl8tgtlanguagecodes00=>tt_targetlanguagecodestrlist.
    DATA lo_targetlanguagecodes TYPE REF TO /aws1/cl_xl8tgtlanguagecodes00.

    "Create an ABAP object for the input data config."
    CREATE OBJECT lo_inputdataconfig
      EXPORTING
        iv_s3uri       = iv_input_data_s3uri
        iv_contenttype = iv_input_data_contenttype.

    "Create an ABAP object for the output data config."
    CREATE OBJECT lo_outputdataconfig
      EXPORTING
        iv_s3uri = iv_output_data_s3uri.

    "Create an internal table for target languages."
    CREATE OBJECT lo_targetlanguagecodes
      EXPORTING
        iv_value = iv_targetlanguagecode.
    INSERT lo_targetlanguagecodes  INTO TABLE lt_targetlanguagecodes.

    TRY.
        DATA(lo_translationjob_result) = lo_xl8->starttexttranslationjob(
          EXPORTING
            io_inputdataconfig = lo_inputdataconfig
            io_outputdataconfig = lo_outputdataconfig
            it_targetlanguagecodes = lt_targetlanguagecodes
            iv_dataaccessrolearn = iv_dataaccessrolearn
            iv_jobname = iv_jobname
```

```
            iv_sourcelanguagecode = iv_sourcelanguagecode
          ).
        MESSAGE 'Translation job started.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
        MESSAGE 'An internal server error occurred. Retry your request.' TYPE
 'E'.
      CATCH /aws1/cx_xl8invparamvalueex .
        MESSAGE 'The value of the parameter is not valid.' TYPE 'E'.
      CATCH /aws1/cx_xl8invalidrequestex.
        MESSAGE 'The request that you made is not valid.' TYPE 'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
        MESSAGE 'You have made too many requests within a short period of time. '
 TYPE 'E'.
      CATCH /aws1/cx_xl8unsuppedlanguage00 .
        MESSAGE 'Amazon Translate does not support translation from the language
 of the source text into the requested target language.' TYPE 'E'.
    ENDTRY.

    "Get the job ID."
    DATA(lv_jobid) = lo_translationjob_result->get_jobid( ).

    "Wait for translate job to complete."
    DATA(lo_des_translation_result) = lo_xl8-
>describetexttranslationjob( iv_jobid = lv_jobid ).
    WHILE lo_des_translation_result->get_textxlationjobproperties( )-
>get_jobstatus( ) <> 'COMPLETED'.
      IF sy-index = 30.
        EXIT.               "Maximum 900 seconds."
      ENDIF.
      WAIT UP TO 30 SECONDS.
      lo_des_translation_result = lo_xl8->describetexttranslationjob( iv_jobid =
 lv_jobid ).
    ENDWHILE.

    TRY.
        oo_result = lo_xl8->describetexttranslationjob(      "oo_result is
 returned for testing purposes."
          EXPORTING
            iv_jobid        = lv_jobid
          ).
        MESSAGE 'Job description retrieved.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
```

```
        MESSAGE 'An internal server error occurred. Retry your request.' TYPE
'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
        MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DescribeTextTranslationJob
  - StartTextTranslationJob

Exemplos entre serviços do Amazon Translate usando SDKs da AWS

Os exemplos de código a seguir mostram como usar o Amazon Translate com SDKs da AWS. Cada exemplo contém um aplicativo de amostra que funciona em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de transmissão do Amazon Transcribe
- Crie um chatbot do Amazon Lex para engajar os visitantes do seu site
- Criar uma aplicação de publicação e assinatura que traduz mensagens
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Criar uma aplicação de transmissão do Amazon Transcribe

O exemplo de código a seguir mostra como construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail.

JavaScript

SDK para JavaScript (v3)

Mostra como usar o Amazon Transcribe para construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SES
- Amazon Transcribe
- Amazon Translate

Crie um chatbot do Amazon Lex para engajar os visitantes do seu site

Os exemplos de código a seguir mostram como criar um chatbot para engajar os visitantes do seu site.

Java

SDK para Java 2.x

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, consulte o exemplo completo Construir um chatbot Amazon Lex no guia do desenvolvedor de AWS SDK for JavaScript.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

Criar uma aplicação de publicação e assinatura que traduz mensagens

Os exemplos de código a seguir mostram como criar uma aplicação que oferece funcionalidade de assinatura e publicação e tradução de mensagens.

.NET

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Java

SDK para Java 2.x

Mostra como usar a API Java do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para obter o código-fonte completo e instruções sobre como configurar e executar o exemplo que usa a API Java Async, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Kotlin

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon SNS para criar uma aplicação com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e as instruções sobre como criar um aplicativo web, veja o exemplo completo em GitHub.

Para ver o código-fonte completo e instruções sobre como criar um aplicativo Android nativo, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Os exemplos de código a seguir mostram como criar uma aplicação que analisa os cartões de comentários dos clientes, os traduz do idioma original, determina seus sentimentos e gera um arquivo de áudio do texto traduzido.

.NET

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Java

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O

hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

JavaScript

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";

/**
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );

  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);

  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";
```

```
/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
 */
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
```

```
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
    VoiceId: "Ruth",
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});
```

```
  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });

  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Ruby

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend

- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Exemplos de código para a Amazon WorkDocs usando AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon WorkDocs com um kit de desenvolvimento de AWS software (SDK).

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Mais atributos

- Guia WorkDocs do desenvolvedor da Amazon — Mais informações sobre a Amazon WorkDocs.
- Referência de WorkDocs API da Amazon — Detalhes sobre todas as WorkDocs ações disponíveis da Amazon.
- Centro do Desenvolvedor da AWS – Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Ações para a Amazon WorkDocs usando AWS SDKs
  - Descreva o conteúdo WorkDocs da pasta raiz da Amazon usando um AWS SDK
  - Descreva WorkDocs os usuários da Amazon usando um AWS SDK

Ações para a Amazon WorkDocs usando AWS SDKs

Os exemplos de código a seguir mostram como usar a Amazon WorkDocs com AWS SDKs. Cada exemplo chama uma função de serviço individual.

Exemplos

- Descreva o conteúdo WorkDocs da pasta raiz da Amazon usando um AWS SDK
- Descreva WorkDocs os usuários da Amazon usando um AWS SDK

Descreva o conteúdo WorkDocs da pasta raiz da Amazon usando um AWS SDK

O exemplo de código a seguir mostra como descrever o conteúdo da pasta WorkDocs raiz da Amazon.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Retrieves the root folder for a user by email
 # @param users [Array<Types::User>] A list of users selected from API response
 # @param user_email [String] The email of the user.
 def get_user_folder(users, user_email)
   user = users.find { |user| user.email_address == user_email }
   if user
     user.root_folder_id
   else
     @logger.error "Could not get root folder for user with email address
#{user_email}"
     exit(1)
   end
 end

 # Describes the contents of a folder
 # @param [String] folder_id - The Id of the folder to describe.
 def describe_folder_contents(folder_id)
   resp = @client.describe_folder_contents({
                                             folder_id: folder_id, # required
                                             sort: "NAME", # accepts DATE, NAME
                                             order: "ASCENDING", # accepts
ASCENDING, DESCENDING
                                           })
```

```
    resp.documents.each do |doc|
      md = doc.latest_version_metadata
      @logger.info "Name:          #{md.name}"
      @logger.info "Size (bytes):  #{md.size}"
      @logger.info "Last modified: #{doc.modified_timestamp}"
      @logger.info "Doc ID:        #{doc.id}"
      @logger.info "Version ID:    #{md.id}"
      @logger.info ""
    end
  rescue Aws::WorkDocs::Errors::ServiceError => e
    @logger.error "Error listing folder contents: #{e.message}"
    exit(1)
  end
```

- Para obter detalhes da API, consulte DescribeRootFoldersa Referência AWS SDK for Ruby da API.

Descreva WorkDocs os usuários da Amazon usando um AWS SDK

Os exemplos de código a seguir mostram como descrever WorkDocs os usuários da Amazon.

CLI

AWS CLI

Para recuperar detalhes de usuários especificados

Este exemplo recupera detalhes de todos os usuários na organização especificada.

Comando:

```
aws workdocs describe-users --organization-id d-926726012c
```

Saída:

```
{
  "Users": [
      {
          "Id": "S-1-1-11-1111111111-2222222222-3333333333-3333&d-926726012c",
          "Username": "example1User",
          "OrganizationId": "d-926726012c",
```

```
            "RootFolderId":
 "3c0e3f849dd20a9771d937b9bbcc97e18796150ae56c26d64a4fa0320a2dedc9",
            "RecycleBinFolderId":
 "c277f4c4d647be1f5147b3184ffa96e1e2bf708278b696cacba68ba13b91f4fe",
            "Status": "INACTIVE",
            "Type": "USER",
            "CreatedTimestamp": 1535478999.452,
            "ModifiedTimestamp": 1535478999.452
        },
        {
            "Id": "S-1-1-11-1111111111-2222222222-3333333333-4444&d-926726012c",
            "Username": "example2User",
            "EmailAddress": "example2User@site.awsapps.com",
            "GivenName": "example2Name",
            "Surname": "example2Surname",
            "OrganizationId": "d-926726012c",
            "RootFolderId":
 "35b886cb17198cbd547655e58b025dff0cf34aaed638be52009567e23dc67390",
            "RecycleBinFolderId":
 "9858c3e9ed4c2460dde9aadb4c69fde998070dd46e5e985bd08ec6169ea249ff",
            "Status": "ACTIVE",
            "Type": "MINIMALUSER",
            "CreatedTimestamp": 1535478836.584,
            "ModifiedTimestamp": 1535478836.584
        }
    ]
}
```

- Para obter detalhes da API, consulte DescribeUsersem Referência de AWS CLI Comandos.

Ruby

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Describes users within an organization
# @param [String] org_id: The ID of the org.
```

```
 def describe_users(org_id)
   resp = @client.describe_users({
                                   organization_id: org_id,
                                   include: "ALL", # accepts ALL, ACTIVE_PENDING
                                   order: "ASCENDING", # accepts ASCENDING,
DESCENDING
                                   sort: "USER_NAME", # accepts USER_NAME,
FULL_NAME, STORAGE_LIMIT, USER_STATUS, STORAGE_USED
                                 })
   resp.users.each do |user|
     @logger.info "First name:  #{user.given_name}"
     @logger.info "Last name:   #{user.surname}"
     @logger.info "Email:       #{user.email_address}"
     @logger.info "Root folder: #{user.root_folder_id}"
     @logger.info ""
   end
   resp.users
 rescue Aws::WorkDocs::Errors::ServiceError => e
   @logger.error "AWS WorkDocs Service Error: #{e.message}"
   exit(1)
 end
```

- Para obter detalhes da API, consulte DescribeUsersa Referência AWS SDK for Ruby da API.

Exemplos de código por SDK usando AWS SDKs

Os exemplos de código a seguir mostram como usar Serviços da AWS com um kit de desenvolvimento de software (SDK) da AWS. Esta seção é organizada pela linguagem SDK.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- AWSCentro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos de código

- Exemplo de código para AWS SDK for .NET
- Exemplos de código para AWS CLI com Bash script
- Exemplos de código para SDK para C++
- Exemplos de código para SDK para Go V2
- Exemplos de código para SDK para JavaScript (v2)
- Exemplos de código para SDK para JavaScript (v3)
- Exemplos de código para SDK para Java 2.x
- Exemplos de código para SDK para Kotlin
- Exemplos de código para o SDK para PHP.
- Exemplos de código para o SDK para Python (Boto3)
- Exemplos de código do SDK para Ruby
- Exemplos de código para SDK para Rust

- Exemplos de código para o SDK para SAP ABAP.
- Exemplos de código para o SDK para Swift.

Exemplo de código para AWS SDK for .NET

Os exemplos a seguir mostram como usar o AWS SDK for .NET com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- AWS SDK for .NET Guia do desenvolvedor : Saiba mais sobre como usar o.NET com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando AWS SDK for .NET
- Exemplos entre serviços usando AWS SDK for .NET

Ações e cenários usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos do ACM usando AWS SDK for .NET
- Exemplos do Aurora usando AWS SDK for .NET
- Exemplos de Auto Scaling usando AWS SDK for .NET
- Exemplos do Amazon Bedrock usando o AWS SDK for .NET
- Exemplos de Amazon Bedrock Runtime usando AWS SDK for .NET
- CloudWatch exemplos usando AWS SDK for .NET
- CloudWatch Exemplos de registros usando AWS SDK for .NET
- Exemplos de provedor de identidade do Amazon Cognito usando AWS SDK for .NET
- Exemplos do Amazon Comprehend usando AWS SDK for .NET
- Exemplos do DynamoDB usando AWS SDK for .NET
- Exemplos do Amazon EC2 usando AWS SDK for .NET
- Exemplos do Amazon ECS usando AWS SDK for .NET
- Exemplos do Elastic Load Balancing usando o AWS SDK for .NET
- EventBridge exemplos usando AWS SDK for .NET
- Exemplos de AWS Glue usando AWS SDK for .NET
- Exemplos do IAM usando AWS SDK for .NET
- Exemplos do Amazon Keyspaces usando AWS SDK for .NET
- Exemplos de Kinesis usando AWS SDK for .NET
- Exemplos de AWS KMS usando AWS SDK for .NET
- Exemplos de Lambda usando AWS SDK for .NET
- MediaConvert exemplos usando AWS SDK for .NET
- Exemplos do Organizations usando AWS SDK for .NET
- Exemplos do Amazon Polly usando AWS SDK for .NET
- Exemplos do Amazon RDS usando AWS SDK for .NET
- Exemplos do Amazon Rekognition usando AWS SDK for .NET
- Exemplos do registro de domínio do Route 53 usando AWS SDK for .NET
- Exemplos do Amazon S3 usando AWS SDK for .NET

- Exemplos do S3 Glacier usando AWS SDK for .NET
- SageMaker exemplos usando AWS SDK for .NET
- Exemplos do Secrets Manager usando AWS SDK for .NET
- Exemplos do Amazon SES usando AWS SDK for .NET
- Exemplos do Amazon SNS usando AWS SDK for .NET
- Exemplos do Amazon SQS usando AWS SDK for .NET
- Exemplos de Step Functions usando AWS SDK for .NET
- Exemplos de AWS STS usando AWS SDK for .NET
- Exemplos de AWS Support usando AWS SDK for .NET
- Exemplos do Amazon Transcribe usando AWS SDK for .NET
- Exemplos do Amazon Translate usando AWS SDK for .NET

Exemplos do ACM usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o ACM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descrever um certificado

Os exemplos de código a seguir mostram como descrever certificados do ACM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.CertificateManager;
using Amazon.CertificateManager.Model;

namespace DescribeCertificate
{
    class DescribeCertificate
    {
        // The following example retrieves and displays the metadata for a
        // certificate using the AWS Certificate Manager (ACM) service.

        // Specify your AWS Region (an example Region is shown).
        private static readonly RegionEndpoint ACMRegion = RegionEndpoint.USEast1;
        private static AmazonCertificateManagerClient _client;

        static void Main(string[] args)
        {
            _client = new
 Amazon.CertificateManager.AmazonCertificateManagerClient(ACMRegion);

            var describeCertificateReq = new DescribeCertificateRequest();
            // The ARN used here is just an example. Replace it with the ARN of
            // a certificate that exists on your account.
            describeCertificateReq.CertificateArn =
                "arn:aws:acm:us-
east-1:123456789012:certificate/8cfd7dae-9b6a-2d07-92bc-1c309EXAMPLE";

            var certificateDetailResp =
                DescribeCertificateResponseAsync(client: _client, request:
 describeCertificateReq);
            var certificateDetail = certificateDetailResp.Result.Certificate;
```

```
            if (certificateDetail is not null)
            {
                DisplayCertificateDetails(certificateDetail);
            }
        }

        /// <summary>
        /// Displays detailed metadata about a certificate retrieved
        /// using the ACM service.
        /// </summary>
        /// <param name="certificateDetail">The object that contains details
        /// returned from the call to DescribeCertificateAsync.</param>
        static void DisplayCertificateDetails(CertificateDetail certificateDetail)
        {
            Console.WriteLine("\nCertificate Details: ");
            Console.WriteLine($"Certificate Domain:
{certificateDetail.DomainName}");
            Console.WriteLine($"Certificate Arn:
{certificateDetail.CertificateArn}");
            Console.WriteLine($"Certificate Subject: {certificateDetail.Subject}");
            Console.WriteLine($"Certificate Status: {certificateDetail.Status}");
            foreach (var san in certificateDetail.SubjectAlternativeNames)
            {
                Console.WriteLine($"Certificate SubjectAlternativeName: {san}");
            }
        }

        /// <summary>
        /// Retrieves the metadata associated with the ACM service certificate.
        /// </summary>
        /// <param name="client">An AmazonCertificateManagerClient object
        /// used to call DescribeCertificateResponse.</param>
        /// <param name="request">The DescribeCertificateRequest object that
        /// will be passed to the method call.</param>
        /// <returns></returns>
        static async Task<DescribeCertificateResponse>
DescribeCertificateResponseAsync(
            AmazonCertificateManagerClient client, DescribeCertificateRequest
request)
        {
            var response = new DescribeCertificateResponse();

            try
            {
```

```
                response = await client.DescribeCertificateAsync(request);
            }
            catch (InvalidArnException)
            {
                Console.WriteLine($"Error: The ARN specified is invalid.");
            }
            catch (ResourceNotFoundException)
            {
                Console.WriteLine($"Error: The specified certificate could not be
 found.");
            }

            return response;
        }
    }

}
```

- Para obter detalhes da API, consulte DescribeCertificatea Referência AWS SDK for .NET da API.

Listar certificados

O exemplo de código a seguir mostra como listar certificados do ACM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.CertificateManager;
using Amazon.CertificateManager.Model;
```

```
namespace ListCertificates
{
    // The following example retrieves and displays a list of the
    // certificates defined for the default account using the AWS
    // Certificate Manager (ACM) service.
    class ListCertificates
    {
        // Specify your AWS Region (an example Region is shown).

        private static readonly RegionEndpoint ACMRegion = RegionEndpoint.USEast1;
        private static AmazonCertificateManagerClient _client;

        static void Main(string[] args)
        {
            _client = new AmazonCertificateManagerClient(ACMRegion);
            var certificateList = ListCertificatesResponseAsync(client: _client);

            Console.WriteLine("Certificate Summary List\n");

            foreach (var certificate in
 certificateList.Result.CertificateSummaryList)
            {
                Console.WriteLine($"Certificate Domain: {certificate.DomainName}");
                Console.WriteLine($"Certificate ARN:
 {certificate.CertificateArn}\n");
            }
        }

        /// <summary>
        /// Retrieves a list of the certificates defined in this Region.
        /// </summary>
        /// <param name="client">The ACM client object passed to the
        /// ListCertificateResAsync method call.</param>
        /// <param name="request"></param>
        /// <returns>The ListCertificatesResponse.</returns>
        static async Task<ListCertificatesResponse> ListCertificatesResponseAsync(
            AmazonCertificateManagerClient client)
        {
            var request = new ListCertificatesRequest();

            var response = await client.ListCertificatesAsync(request);
            return response;
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte ListCertificatesa Referência AWS SDK for .NET da API.

Exemplos do Aurora usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
using Amazon.RDS;
using Amazon.RDS.Model;
using Microsoft.Extensions.DependencyInjection;
```

```
using Microsoft.Extensions.Hosting;

namespace AuroraActions;

public static class HelloAurora
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the
        // Amazon Relational Database Service (Amazon RDS).
        // Use your AWS profile name, or leave it blank to use the default profile.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRDS>()
            ).Build();

        // Now the client is available for injection. Fetching it directly here for
 example purposes only.
        var rdsClient = host.Services.GetRequiredService<IAmazonRDS>();

        // You can use await and any of the async methods to get a response.
        var response = await rdsClient.DescribeDBClustersAsync(new
 DescribeDBClustersRequest { IncludeShared = true });
        Console.WriteLine($"Hello Amazon RDS Aurora! Let's list some clusters in
 this account:");
        foreach (var cluster in response.DBClusters)
        {
            Console.WriteLine($"\tCluster: database: {cluster.DatabaseName}
 identifier: {cluster.DBClusterIdentifier}.");
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for .NET.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

O exemplo de código a seguir mostra como criar um cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
/// <summary>
/// Create a new cluster and database.
/// </summary>
/// <param name="dbName">The name of the new database.</param>
/// <param name="clusterIdentifier">The identifier of the cluster.</param>
/// <param name="parameterGroupName">The name of the parameter group.</param>
/// <param name="dbEngine">The engine to use for the new cluster.</param>
/// <param name="dbEngineVersion">The version of the engine to use.</param>
/// <param name="adminName">The admin username.</param>
/// <param name="adminPassword">The primary admin password.</param>
/// <returns>The cluster object.</returns>
public async Task<DBCluster> CreateDBClusterWithAdminAsync(
    string dbName,
    string clusterIdentifier,
    string parameterGroupName,
    string dbEngine,
    string dbEngineVersion,
    string adminName,
    string adminPassword)
{
    var request = new CreateDBClusterRequest
    {
        DatabaseName = dbName,
        DBClusterIdentifier = clusterIdentifier,
        DBClusterParameterGroupName = parameterGroupName,
        Engine = dbEngine,
        EngineVersion = dbEngineVersion,
        MasterUsername = adminName,
        MasterUserPassword = adminPassword,
```

```
        };

        var response = await _amazonRDS.CreateDBClusterAsync(request);
        return response.DBCluster;
    }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for .NET.

Criar um parameter group de cluster de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a custom cluster parameter group.
    /// </summary>
    /// <param name="parameterGroupFamily">The family of the parameter group.</
param>
    /// <param name="groupName">The name for the new parameter group.</param>
    /// <param name="description">A description for the new parameter group.</param>
    /// <returns>The new parameter group object.</returns>
    public async Task<DBClusterParameterGroup>
 CreateCustomClusterParameterGroupAsync(
        string parameterGroupFamily,
        string groupName,
        string description)
    {
        var request = new CreateDBClusterParameterGroupRequest
        {
            DBParameterGroupFamily = parameterGroupFamily,
            DBClusterParameterGroupName = groupName,
            Description = description,
```

```
        };

        var response = await _amazonRDS.CreateDBClusterParameterGroupAsync(request);
        return response.DBClusterParameterGroup;
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for .NET da API.

Criar um snapshot de cluster de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a snapshot of a cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBClusterSnapshot>
CreateClusterSnapshotByIdentifierAsync(string dbClusterIdentifier, string
snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBClusterSnapshotAsync(
            new CreateDBClusterSnapshotRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBClusterSnapshotIdentifier = snapshotIdentifier,
            });

        return response.DBClusterSnapshot;
    }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for .NET da API.

Criar uma instância de banco de dados em um cluster de banco de dados

O exemplo de código a seguir mostra como criar uma instância do DB em um cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Create an Amazon Relational Database Service (Amazon RDS) DB instance
    /// with a particular set of properties. Use the action DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstanceInClusterAsync(
        string dbClusterIdentifier,
        string dbInstanceIdentifier,
        string dbEngine,
        string dbEngineVersion,
        string instanceClass)
    {
        // When creating the instance within a cluster, do not specify the name or
size.
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
```

```
                DBInstanceIdentifier = dbInstanceIdentifier,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for .NET.

Excluir um cluster de banco de dados

O exemplo de código a seguir mostra como excluir um cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Delete a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>DB cluster object.</returns>
    public async Task<DBCluster> DeleteDBClusterByIdentifierAsync(string
dbClusterIdentifier)
    {
        var response = await _amazonRDS.DeleteDBClusterAsync(
            new DeleteDBClusterRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                SkipFinalSnapshot = true
            });

        return response.DBCluster;
    }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for .NET.

Excluir um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete a particular parameter group by name.
/// </summary>
/// <param name="groupName">The name of the parameter group.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteClusterParameterGroupByNameAsync(string groupName)
{
    var request = new DeleteDBClusterParameterGroupRequest
    {
        DBClusterParameterGroupName = groupName,
    };

    var response = await _amazonRDS.DeleteDBClusterParameterGroupAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for .NET Referência da API.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstanceByIdentifierAsync(string
dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for .NET.

Descrever os grupos de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever grupos de parâmetros de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the description of a DB cluster parameter group by name.
    /// </summary>
    /// <param name="name">The name of the DB parameter group to describe.</param>
    /// <returns>The parameter group description.</returns>
    public async Task<DBClusterParameterGroup?>
DescribeCustomDBClusterParameterGroupAsync(string name)
    {
        var response = await _amazonRDS.DescribeDBClusterParameterGroupsAsync(
            new DescribeDBClusterParameterGroupsRequest()
            {
                DBClusterParameterGroupName = name
            });
        return response.DBClusterParameterGroups.FirstOrDefault();
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for .NET da API.

Descrever snapshots de cluster de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Return a list of DB snapshots for a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBClusterSnapshot>>
DescribeDBClusterSnapshotsByIdentifierAsync(string dbClusterIdentifier)
    {
        var results = new List<DBClusterSnapshot>();

        DescribeDBClusterSnapshotsResponse response;
        DescribeDBClusterSnapshotsRequest request = new
DescribeDBClusterSnapshotsRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClusterSnapshotsAsync(request);
            results.AddRange(response.DBClusterSnapshots);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for .NET da API.

Descrever clusters de banco de dados

O exemplo de código a seguir mostra como descrever clusters do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Returns a list of DB clusters.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB cluster.</
param>
    /// <returns>List of DB clusters.</returns>
    public async Task<List<DBCluster>> DescribeDBClustersPagedAsync(string?
 dbClusterIdentifier = null)
    {
        var results = new List<DBCluster>();

        DescribeDBClustersResponse response;
        DescribeDBClustersRequest request = new DescribeDBClustersRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClustersAsync(request);
            results.AddRange(response.DBClusters);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for .NET.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstancesPagedAsync(string?
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

Descrever as versões de mecanismo de banco de dados

O exemplo de código a seguir mostra como descrever as versões de mecanismo de banco de dados do Aurora.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">The name of the engine.</param>
    /// <param name="parameterGroupFamily">Optional parameter group family name.</
param>
    /// <returns>A list of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>>
 DescribeDBEngineVersionsForEngineAsync(string engine,
        string? parameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = parameterGroupFamily
            });
        return response.DBEngineVersions;
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for .NET da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever as opções para instâncias Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
```

```
    public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptionsPagedAsync(string engine, string engineVersion)
    {
        // Use a paginator to get a list of DB instance options.
        var results = new List<OrderableDBInstanceOption>();
        var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
            new DescribeOrderableDBInstanceOptionsRequest()
            {
                Engine = engine,
                EngineVersion = engineVersion,
            });
        // Get the entire list using the paginator.
        await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
        {
            results.Add(instanceOptions);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for .NET API.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the cluster parameters in a parameter group.
    /// </summary>
```

```
    /// <param name="groupName">The name of the parameter group.</param>
    /// <param name="source">The optional name of the source filter.</param>
    /// <returns>The collection of parameters.</returns>
    public async Task<List<Parameter>>
DescribeDBClusterParametersInGroupAsync(string groupName, string? source = null)
    {
        var paramList = new List<Parameter>();

        DescribeDBClusterParametersResponse response;
        var request = new DescribeDBClusterParametersRequest
        {
            DBClusterParameterGroupName = groupName,
            Source = source,
        };

        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClusterParametersAsync(request);
            paramList.AddRange(response.Parameters);

            request.Marker = response.Marker;
        }
        while (response.Marker is not null);

        return paramList;
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for .NET da API.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como atualizar os parâmetros de um grupo de parâmetros de cluster do Aurora DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Modify the specified integer parameters with new values from user input.
   /// </summary>
   /// <param name="groupName">The group name for the parameters.</param>
   /// <param name="parameters">The list of integer parameters to modify.</param>
   /// <param name="newValue">Optional int value to set for parameters.</param>
   /// <returns>The name of the group that was modified.</returns>
   public async Task<string> ModifyIntegerParametersInGroupAsync(string groupName,
List<Parameter> parameters, int newValue = 0)
   {
       foreach (var p in parameters)
       {
           if (p.IsModifiable && p.DataType == "integer")
           {
               while (newValue == 0)
               {
                   Console.WriteLine(
                       $"Enter a new value for {p.ParameterName} from the allowed
values {p.AllowedValues} ");

                   var choice = Console.ReadLine();
                   int.TryParse(choice, out newValue);
               }

               p.ParameterValue = newValue.ToString();
           }
       }

       var request = new ModifyDBClusterParameterGroupRequest
       {
           Parameters = parameters,
           DBClusterParameterGroupName = groupName,
       };
```

```
        var result = await _amazonRDS.ModifyDBClusterParameterGroupAsync(request);
        return result.DBClusterParameterGroupName;
    }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for .NET da API.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
using Amazon.RDS;
using Amazon.RDS.Model;
using AuroraActions;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;
using Microsoft.Extensions.Logging;
using Microsoft.Extensions.Logging.Console;
using Microsoft.Extensions.Logging.Debug;
```

```
namespace AuroraScenario;

/// <summary>
/// Scenario for Amazon Aurora examples.
/// </summary>
public class AuroraScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks:
    1.  Return a list of the available DB engine families for Aurora MySql using the
 DescribeDBEngineVersionsAsync method.
    2.  Select an engine family and create a custom DB cluster parameter group using
 the CreateDBClusterParameterGroupAsync method.
    3.  Get the parameter group using the DescribeDBClusterParameterGroupsAsync
 method.
    4.  Get some parameters in the group using the DescribeDBClusterParametersAsync
 method.
    5.  Parse and display some parameters in the group.
    6.  Modify the auto_increment_offset and auto_increment_increment parameters
        using the ModifyDBClusterParameterGroupAsync method.
    7.  Get and display the updated parameters using the
 DescribeDBClusterParametersAsync method with a source of "user".
    8.  Get a list of allowed engine versions using the
 DescribeDBEngineVersionsAsync method.
    9.  Create an Aurora DB cluster that contains a MySql database and uses the
 parameter group.
        using the CreateDBClusterAsync method.
    10. Wait for the DB cluster to be ready using the DescribeDBClustersAsync
 method.
    11. Display and select from a list of instance classes available for the
 selected engine and version
        using the paginated DescribeOrderableDBInstanceOptions method.
    12. Create a database instance in the cluster using the CreateDBInstanceAsync
 method.
    13. Wait for the DB instance to be ready using the DescribeDBInstances method.
    14. Display the connection endpoint string for the new DB cluster.
    15. Create a snapshot of the DB cluster using the CreateDBClusterSnapshotAsync
 method.
    16. Wait for DB snapshot to be ready using the DescribeDBClusterSnapshotsAsync
 method.
    17. Delete the DB instance using the DeleteDBInstanceAsync method.
```

```
   18. Delete the DB cluster using the DeleteDBClusterAsync method.
   19. Wait for DB cluster to be deleted using the DescribeDBClustersAsync methods.
   20. Delete the cluster parameter group using the
DeleteDBClusterParameterGroupAsync.
   */

   private static readonly string sepBar = new('-', 80);
   private static AuroraWrapper auroraWrapper = null!;
   private static ILogger logger = null!;
   private static readonly string engine = "aurora-mysql";
   static async Task Main(string[] args)
   {
       // Set up dependency injection for the Amazon Relational Database Service
(Amazon RDS).
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
           .ConfigureServices((_, services) =>
               services.AddAWSService<IAmazonRDS>()
                   .AddTransient<AuroraWrapper>()
           )
           .Build();

       logger = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       }).CreateLogger<AuroraScenario>();

       auroraWrapper = host.Services.GetRequiredService<AuroraWrapper>();

       Console.WriteLine(sepBar);
       Console.WriteLine(
           "Welcome to the Amazon Aurora: get started with DB clusters example.");
       Console.WriteLine(sepBar);

       DBClusterParameterGroup parameterGroup = null!;
       DBCluster? newCluster = null;
       DBInstance? newInstance = null;

       try
       {
```

```
            var parameterGroupFamily = await ChooseParameterGroupFamilyAsync();

            parameterGroup = await
CreateDBParameterGroupAsync(parameterGroupFamily);

            var parameters = await
DescribeParametersInGroupAsync(parameterGroup.DBClusterParameterGroupName,
                new List<string> { "auto_increment_offset",
"auto_increment_increment" });

            await ModifyParametersAsync(parameterGroup.DBClusterParameterGroupName,
parameters);

            await
DescribeUserSourceParameters(parameterGroup.DBClusterParameterGroupName);

            var engineVersionChoice = await
ChooseDBEngineVersionAsync(parameterGroupFamily);

            var newClusterIdentifier = "Example-Cluster-" + DateTime.Now.Ticks;

            newCluster = await CreateNewCluster
            (
                parameterGroup,
                engine,
                engineVersionChoice.EngineVersion,
                newClusterIdentifier
            );

            var instanceClassChoice = await ChooseDBInstanceClass(engine,
engineVersionChoice.EngineVersion);

            var newInstanceIdentifier = "Example-Instance-" + DateTime.Now.Ticks;

            newInstance = await CreateNewInstance(
                newClusterIdentifier,
                engine,
                engineVersionChoice.EngineVersion,
                instanceClassChoice.DBInstanceClass,
                newInstanceIdentifier
            );

            DisplayConnectionString(newCluster!);
            await CreateSnapshot(newCluster!);
```

```
            await CleanupResources(newInstance, newCluster, parameterGroup);

            Console.WriteLine("Scenario complete.");
            Console.WriteLine(sepBar);
        }
        catch (Exception ex)

        {
            await CleanupResources(newInstance, newCluster, parameterGroup);
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// Choose the Aurora DB parameter group family from a list of available
options.
    /// </summary>
    /// <returns>The selected parameter group family.</returns>
    public static async Task<string> ChooseParameterGroupFamilyAsync()
    {
        Console.WriteLine(sepBar);
        // 1. Get a list of available engines.
        var engines = await
auroraWrapper.DescribeDBEngineVersionsForEngineAsync(engine);

        Console.WriteLine($"1. The following is a list of available DB parameter
group families for engine {engine}:");

        var parameterGroupFamilies =
            engines.GroupBy(e => e.DBParameterGroupFamily).ToList();
        for (var i = 1; i <= parameterGroupFamilies.Count; i++)
        {
            var parameterGroupFamily = parameterGroupFamilies[i - 1];
            // List the available parameter group families.
            Console.WriteLine(
                $"\t{i}. Family: {parameterGroupFamily.Key}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > parameterGroupFamilies.Count)
        {
            Console.WriteLine("2. Select an available DB parameter group family by
entering a number from the preceding list:");
            var choice = Console.ReadLine();
```

```
            Int32.TryParse(choice, out choiceNumber);
        }
        var parameterGroupFamilyChoice = parameterGroupFamilies[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return parameterGroupFamilyChoice.Key;
    }

    /// <summary>
    /// Create and get information on a DB parameter group.
    /// </summary>
    /// <param name="dbParameterGroupFamily">The DBParameterGroupFamily for the new
 DB parameter group.</param>
    /// <returns>The new DBParameterGroup.</returns>
    public static async Task<DBClusterParameterGroup>
 CreateDBParameterGroupAsync(string dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"2. Create new DB parameter group with family
 {dbParameterGroupFamily}:");

        var parameterGroup = await
 auroraWrapper.CreateCustomClusterParameterGroupAsync(
            dbParameterGroupFamily,
            "ExampleParameterGroup-" + DateTime.Now.Ticks,
            "New example parameter group");

        var groupInfo =
            await
 auroraWrapper.DescribeCustomDBClusterParameterGroupAsync(parameterGroup.DBClusterParameterG

        Console.WriteLine(
            $"3. New DB parameter group created: \n\t{groupInfo?.Description}, \n
\tARN {groupInfo?.DBClusterParameterGroupName}");
        Console.WriteLine(sepBar);
        return parameterGroup;
    }

    /// <summary>
    /// Get and describe parameters from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">The name of the DBParameterGroup.</param>
    /// <param name="parameterNames">Optional specific names of parameters to
 describe.</param>
    /// <returns>The list of requested parameters.</returns>
```

```
    public static async Task<List<Parameter>> DescribeParametersInGroupAsync(string
parameterGroupName, List<string>? parameterNames = null)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("4. Get some parameters from the group.");
        Console.WriteLine(sepBar);

        var parameters =
            await
auroraWrapper.DescribeDBClusterParametersInGroupAsync(parameterGroupName);

        var matchingParameters =
            parameters.Where(p => parameterNames == null ||
parameterNames.Contains(p.ParameterName)).ToList();

        Console.WriteLine("5. Parameter information:");
        matchingParameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);

        return matchingParameters;
    }

    /// <summary>
    /// Modify a parameter from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameters">The parameters to modify.</param>
    /// <returns>Async task.</returns>
    public static async Task ModifyParametersAsync(string parameterGroupName,
List<Parameter> parameters)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("6. Modify some parameters in the group.");

        await auroraWrapper.ModifyIntegerParametersInGroupAsync(parameterGroupName,
parameters);

        Console.WriteLine(sepBar);
```

```
    }

    /// <summary>
    /// Describe the user source parameters in the group.
    /// </summary>
    /// <param name="parameterGroupName">The name of the DBParameterGroup.</param>
    /// <returns>Async task.</returns>
    public static async Task DescribeUserSourceParameters(string parameterGroupName)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("7. Describe updated user source parameters in the
group.");

        var parameters =
            await
auroraWrapper.DescribeDBClusterParametersInGroupAsync(parameterGroupName, "user");

        parameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Choose a DB engine version.
    /// </summary>
    /// <param name="dbParameterGroupFamily">DB parameter group family for engine
choice.</param>
    /// <returns>The selected engine version.</returns>
    public static async Task<DBEngineVersion> ChooseDBEngineVersionAsync(string
dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed engines.
        var allowedEngines =
            await auroraWrapper.DescribeDBEngineVersionsForEngineAsync(engine,
dbParameterGroupFamily);

        Console.WriteLine($"Available DB engine versions for parameter group family
{dbParameterGroupFamily}:");
```

```
        int i = 1;
        foreach (var version in allowedEngines)
        {
            Console.WriteLine(
                $"\t{i}. Engine: {version.Engine} Version
 {version.EngineVersion}.");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedEngines.Count)
        {
            Console.WriteLine("8. Select an available DB engine version by entering
 a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var engineChoice = allowedEngines[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return engineChoice;
    }

    /// <summary>
    /// Create a new RDS DB cluster.
    /// </summary>
    /// <param name="parameterGroup">Parameter group to use for the DB cluster.</
param>
    /// <param name="engineName">Engine to use for the DB cluster.</param>
    /// <param name="engineVersion">Engine version to use for the DB cluster.</
param>
    /// <param name="clusterIdentifier">Cluster identifier to use for the DB
 cluster.</param>
    /// <returns>The new DB cluster.</returns>
    public static async Task<DBCluster?> CreateNewCluster(DBClusterParameterGroup
 parameterGroup,
        string engineName, string engineVersion, string clusterIdentifier)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"9. Create a new DB cluster with identifier
 {clusterIdentifier}.");

        DBCluster newCluster;
        var clusters = await auroraWrapper.DescribeDBClustersPagedAsync();
```

```
        var isClusterCreated = clusters.Any(i => i.DBClusterIdentifier ==
clusterIdentifier);

        if (isClusterCreated)
        {
            Console.WriteLine("Cluster already created.");
            newCluster = clusters.First(i => i.DBClusterIdentifier ==
clusterIdentifier);
        }
        else
        {
            Console.WriteLine("Enter an admin username:");
            var username = Console.ReadLine();

            Console.WriteLine("Enter an admin password:");
            var password = Console.ReadLine();

            newCluster = await auroraWrapper.CreateDBClusterWithAdminAsync(
                "ExampleDatabase",
                clusterIdentifier,
                parameterGroup.DBClusterParameterGroupName,
                engineName,
                engineVersion,
                username!,
                password!
            );

            Console.WriteLine("10. Waiting for DB cluster to be ready...");
            while (newCluster.Status != "available")
            {
                Console.Write(".");
                Thread.Sleep(5000);
                clusters = await
auroraWrapper.DescribeDBClustersPagedAsync(clusterIdentifier);
                newCluster = clusters.First();
            }
        }

        Console.WriteLine(sepBar);
        return newCluster;
    }

    /// <summary>
    /// Choose a DB instance class for a particular engine and engine version.
```

```
    /// </summary>
    /// <param name="engine">DB engine for DB instance choice.</param>
    /// <param name="engineVersion">DB engine version for DB instance choice.</
param>
    /// <returns>The selected orderable DB instance option.</returns>
    public static async Task<OrderableDBInstanceOption> ChooseDBInstanceClass(string
 engine, string engineVersion)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed DB instance classes.
        var allowedInstances =
            await auroraWrapper.DescribeOrderableDBInstanceOptionsPagedAsync(engine,
 engineVersion);

        Console.WriteLine($"Available DB instance classes for engine {engine} and
 version {engineVersion}:");
        int i = 1;


        foreach (var instance in allowedInstances)
        {
            Console.WriteLine(
                $"\t{i}. Instance class: {instance.DBInstanceClass} (storage type
 {instance.StorageType})");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedInstances.Count)
        {
            Console.WriteLine("11. Select an available DB instance class by entering
 a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var instanceChoice = allowedInstances[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return instanceChoice;
    }

    /// <summary>
    /// Create a new DB instance.
    /// </summary>
```

```
    /// <param name="engineName">Engine to use for the DB instance.</param>
    /// <param name="engineVersion">Engine version to use for the DB instance.</
param>
    /// <param name="instanceClass">Instance class to use for the DB instance.</
param>
    /// <param name="instanceIdentifier">Instance identifier to use for the DB
 instance.</param>
    /// <returns>The new DB instance.</returns>
    public static async Task<DBInstance?> CreateNewInstance(
        string clusterIdentifier,
        string engineName,
        string engineVersion,
        string instanceClass,
        string instanceIdentifier)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"12. Create a new DB instance with identifier
 {instanceIdentifier}.");
        bool isInstanceReady = false;
        DBInstance newInstance;
        var instances = await auroraWrapper.DescribeDBInstancesPagedAsync();
        isInstanceReady = instances.FirstOrDefault(i =>
            i.DBInstanceIdentifier == instanceIdentifier)?.DBInstanceStatus ==
 "available";

        if (isInstanceReady)
        {
            Console.WriteLine("Instance already created.");
            newInstance = instances.First(i => i.DBInstanceIdentifier ==
 instanceIdentifier);
        }
        else
        {

            newInstance = await auroraWrapper.CreateDBInstanceInClusterAsync(
                clusterIdentifier,
                instanceIdentifier,
                engineName,
                engineVersion,
                instanceClass
            );

            Console.WriteLine("13. Waiting for DB instance to be ready...");
            while (!isInstanceReady)
```

```
            {
                Console.Write(".");
                Thread.Sleep(5000);
                instances = await
 auroraWrapper.DescribeDBInstancesPagedAsync(instanceIdentifier);
                isInstanceReady = instances.FirstOrDefault()?.DBInstanceStatus ==
 "available";
                newInstance = instances.First();
            }
        }

        Console.WriteLine(sepBar);
        return newInstance;
    }

    /// <summary>
    /// Display a connection string for an Amazon RDS DB cluster.
    /// </summary>
    /// <param name="cluster">The DB cluster to use to get a connection string.</
param>
    public static void DisplayConnectionString(DBCluster cluster)
    {
        Console.WriteLine(sepBar);
        // Display the connection string.
        Console.WriteLine("14. New DB cluster connection string: ");
        Console.WriteLine(
            $"\n{engine} -h {cluster.Endpoint} -P {cluster.Port} "
            + $"-u {cluster.MasterUsername} -p [YOUR PASSWORD]\n");

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Create a snapshot from an Amazon RDS DB cluster.
    /// </summary>
    /// <param name="cluster">DB cluster to use when creating a snapshot.</param>
    /// <returns>The snapshot object.</returns>
    public static async Task<DBClusterSnapshot> CreateSnapshot(DBCluster cluster)
    {
        Console.WriteLine(sepBar);
        // Create a snapshot.
        Console.WriteLine($"15. Creating snapshot from DB cluster
 {cluster.DBClusterIdentifier}.");
        var snapshot = await auroraWrapper.CreateClusterSnapshotByIdentifierAsync(
```

```
            cluster.DBClusterIdentifier,
            "ExampleSnapshot-" + DateTime.Now.Ticks);

        // Wait for the snapshot to be available.
        bool isSnapshotReady = false;

        Console.WriteLine($"16. Waiting for snapshot to be ready...");
        while (!isSnapshotReady)
        {
            Console.Write(".");
            Thread.Sleep(5000);
            var snapshots =
                await
auroraWrapper.DescribeDBClusterSnapshotsByIdentifierAsync(cluster.DBClusterIdentifier);
            isSnapshotReady = snapshots.FirstOrDefault()?.Status == "available";
            snapshot = snapshots.First();
        }

        Console.WriteLine(
            $"Snapshot {snapshot.DBClusterSnapshotIdentifier} status is
{snapshot.Status}.");
        Console.WriteLine(sepBar);
        return snapshot;
    }

    /// <summary>
    /// Clean up resources from the scenario.
    /// </summary>
    /// <param name="newInstance">The instance to clean up.</param>
    /// <param name="newCluster">The cluster to clean up.</param>
    /// <param name="parameterGroup">The parameter group to clean up.</param>
    /// <returns>Async Task.</returns>
    private static async Task CleanupResources(
        DBInstance? newInstance,
        DBCluster? newCluster,
        DBClusterParameterGroup? parameterGroup)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        if (newInstance is not null && GetYesNoResponse($"\tClean up instance
{newInstance.DBInstanceIdentifier}? (y/n)"))
        {
            // Delete the DB instance.
```

```
            Console.WriteLine($"17. Deleting the DB instance
{newInstance.DBInstanceIdentifier}.");
            await
auroraWrapper.DeleteDBInstanceByIdentifierAsync(newInstance.DBInstanceIdentifier);
        }

        if (newCluster is not null && GetYesNoResponse($"\tClean up cluster
{newCluster.DBClusterIdentifier}? (y/n)"))
        {
            // Delete the DB cluster.
            Console.WriteLine($"18. Deleting the DB cluster
{newCluster.DBClusterIdentifier}.");
            await
auroraWrapper.DeleteDBClusterByIdentifierAsync(newCluster.DBClusterIdentifier);

            // Wait for the DB cluster to delete.
            Console.WriteLine($"19. Waiting for the DB cluster to delete...");
            bool isClusterDeleted = false;

            while (!isClusterDeleted)
            {
                Console.Write(".");
                Thread.Sleep(5000);
                var cluster = await auroraWrapper.DescribeDBClustersPagedAsync();
                isClusterDeleted = cluster.All(i => i.DBClusterIdentifier !=
newCluster.DBClusterIdentifier);
            }

            Console.WriteLine("DB cluster deleted.");
        }

        if (parameterGroup is not null && GetYesNoResponse($"\tClean up parameter
group? (y/n)"))
        {
            Console.WriteLine($"20. Deleting the DB parameter group
{parameterGroup.DBClusterParameterGroupName}.");
            await
auroraWrapper.DeleteClusterParameterGroupByNameAsync(parameterGroup.DBClusterParameterGroup
            Console.WriteLine("Parameter group deleted.");
        }

        Console.WriteLine(new string('-', 80));
    }
```

```
    /// <summary>
    /// Get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
```

Métodos de encapsulamento que são chamados pelo cenário para gerenciar as ações do Aurora.

```
using Amazon.RDS;
using Amazon.RDS.Model;

namespace AuroraActions;

/// <summary>
/// Wrapper for the Amazon Aurora cluster client operations.
/// </summary>
public class AuroraWrapper
{
    private readonly IAmazonRDS _amazonRDS;
    public AuroraWrapper(IAmazonRDS amazonRDS)
    {
        _amazonRDS = amazonRDS;
    }

    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">The name of the engine.</param>
    /// <param name="parameterGroupFamily">Optional parameter group family name.</
param>
    /// <returns>A list of DBEngineVersions.</returns>
```

```
    public async Task<List<DBEngineVersion>>
 DescribeDBEngineVersionsForEngineAsync(string engine,
        string? parameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = parameterGroupFamily
            });
        return response.DBEngineVersions;
    }

    /// <summary>
    /// Create a custom cluster parameter group.
    /// </summary>
    /// <param name="parameterGroupFamily">The family of the parameter group.</
param>
    /// <param name="groupName">The name for the new parameter group.</param>
    /// <param name="description">A description for the new parameter group.</param>
    /// <returns>The new parameter group object.</returns>
    public async Task<DBClusterParameterGroup>
 CreateCustomClusterParameterGroupAsync(
        string parameterGroupFamily,
        string groupName,
        string description)
    {
        var request = new CreateDBClusterParameterGroupRequest
        {
            DBParameterGroupFamily = parameterGroupFamily,
            DBClusterParameterGroupName = groupName,
            Description = description,
        };

        var response = await _amazonRDS.CreateDBClusterParameterGroupAsync(request);
        return response.DBClusterParameterGroup;
    }

    /// <summary>
    /// Describe the cluster parameters in a parameter group.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <param name="source">The optional name of the source filter.</param>
    /// <returns>The collection of parameters.</returns>
```

```
    public async Task<List<Parameter>>
DescribeDBClusterParametersInGroupAsync(string groupName, string? source = null)
    {
        var paramList = new List<Parameter>();

        DescribeDBClusterParametersResponse response;
        var request = new DescribeDBClusterParametersRequest
        {
            DBClusterParameterGroupName = groupName,
            Source = source,
        };

        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClusterParametersAsync(request);
            paramList.AddRange(response.Parameters);

            request.Marker = response.Marker;
        }
        while (response.Marker is not null);

        return paramList;
    }

    /// <summary>
    /// Get the description of a DB cluster parameter group by name.
    /// </summary>
    /// <param name="name">The name of the DB parameter group to describe.</param>
    /// <returns>The parameter group description.</returns>
    public async Task<DBClusterParameterGroup?>
DescribeCustomDBClusterParameterGroupAsync(string name)
    {
        var response = await _amazonRDS.DescribeDBClusterParameterGroupsAsync(
            new DescribeDBClusterParameterGroupsRequest()
            {
                DBClusterParameterGroupName = name
            });
        return response.DBClusterParameterGroups.FirstOrDefault();
    }

    /// <summary>
    /// Modify the specified integer parameters with new values from user input.
    /// </summary>
```

```
    /// <param name="groupName">The group name for the parameters.</param>
    /// <param name="parameters">The list of integer parameters to modify.</param>
    /// <param name="newValue">Optional int value to set for parameters.</param>
    /// <returns>The name of the group that was modified.</returns>
    public async Task<string> ModifyIntegerParametersInGroupAsync(string groupName,
List<Parameter> parameters, int newValue = 0)
    {
        foreach (var p in parameters)
        {
            if (p.IsModifiable && p.DataType == "integer")
            {
                while (newValue == 0)
                {
                    Console.WriteLine(
                        $"Enter a new value for {p.ParameterName} from the allowed
values {p.AllowedValues} ");

                    var choice = Console.ReadLine();
                    int.TryParse(choice, out newValue);
                }

                p.ParameterValue = newValue.ToString();
            }
        }

        var request = new ModifyDBClusterParameterGroupRequest
        {
            Parameters = parameters,
            DBClusterParameterGroupName = groupName,
        };

        var result = await _amazonRDS.ModifyDBClusterParameterGroupAsync(request);
        return result.DBClusterParameterGroupName;
    }


    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
```

```
    public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptionsPagedAsync(string engine, string engineVersion)
    {
        // Use a paginator to get a list of DB instance options.
        var results = new List<OrderableDBInstanceOption>();
        var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
            new DescribeOrderableDBInstanceOptionsRequest()
            {
                Engine = engine,
                EngineVersion = engineVersion,
            });
        // Get the entire list using the paginator.
        await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
        {
            results.Add(instanceOptions);
        }
        return results;
    }

    /// <summary>
    /// Delete a particular parameter group by name.
    /// </summary>
    /// <param name="groupName">The name of the parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteClusterParameterGroupByNameAsync(string groupName)
    {
        var request = new DeleteDBClusterParameterGroupRequest
        {
            DBClusterParameterGroupName = groupName,
        };

        var response = await _amazonRDS.DeleteDBClusterParameterGroupAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Create a new cluster and database.
    /// </summary>
    /// <param name="dbName">The name of the new database.</param>
    /// <param name="clusterIdentifier">The identifier of the cluster.</param>
    /// <param name="parameterGroupName">The name of the parameter group.</param>
    /// <param name="dbEngine">The engine to use for the new cluster.</param>
```

```
    /// <param name="dbEngineVersion">The version of the engine to use.</param>
    /// <param name="adminName">The admin username.</param>
    /// <param name="adminPassword">The primary admin password.</param>
    /// <returns>The cluster object.</returns>
    public async Task<DBCluster> CreateDBClusterWithAdminAsync(
        string dbName,
        string clusterIdentifier,
        string parameterGroupName,
        string dbEngine,
        string dbEngineVersion,
        string adminName,
        string adminPassword)
    {
        var request = new CreateDBClusterRequest
        {
            DatabaseName = dbName,
            DBClusterIdentifier = clusterIdentifier,
            DBClusterParameterGroupName = parameterGroupName,
            Engine = dbEngine,
            EngineVersion = dbEngineVersion,
            MasterUsername = adminName,
            MasterUserPassword = adminPassword,
        };

        var response = await _amazonRDS.CreateDBClusterAsync(request);
        return response.DBCluster;
    }

    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstancesPagedAsync(string?
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });
        // Get the entire list using the paginator.
```

```
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }

    /// <summary>
    /// Returns a list of DB clusters.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB cluster.</
param>
    /// <returns>List of DB clusters.</returns>
    public async Task<List<DBCluster>> DescribeDBClustersPagedAsync(string?
 dbClusterIdentifier = null)
    {
        var results = new List<DBCluster>();

        DescribeDBClustersResponse response;
        DescribeDBClustersRequest request = new DescribeDBClustersRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClustersAsync(request);
            results.AddRange(response.DBClusters);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
        return results;
    }

    /// <summary>
    /// Create an Amazon Relational Database Service (Amazon RDS) DB instance
    /// with a particular set of properties. Use the action DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
```

```
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstanceInClusterAsync(
        string dbClusterIdentifier,
        string dbInstanceIdentifier,
        string dbEngine,
        string dbEngineVersion,
        string instanceClass)
    {
        // When creating the instance within a cluster, do not specify the name or
size.
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass
            });

        return response.DBInstance;
    }

    /// <summary>
    /// Create a snapshot of a cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBClusterSnapshot>
CreateClusterSnapshotByIdentifierAsync(string dbClusterIdentifier, string
snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBClusterSnapshotAsync(
            new CreateDBClusterSnapshotRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                DBClusterSnapshotIdentifier = snapshotIdentifier,
            });

        return response.DBClusterSnapshot;
    }

    /// <summary>
```

```
    /// Return a list of DB snapshots for a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBClusterSnapshot>>
DescribeDBClusterSnapshotsByIdentifierAsync(string dbClusterIdentifier)
    {
        var results = new List<DBClusterSnapshot>();

        DescribeDBClusterSnapshotsResponse response;
        DescribeDBClusterSnapshotsRequest request = new
DescribeDBClusterSnapshotsRequest
        {
            DBClusterIdentifier = dbClusterIdentifier
        };
        // Get the full list if there are multiple pages.
        do
        {
            response = await _amazonRDS.DescribeDBClusterSnapshotsAsync(request);
            results.AddRange(response.DBClusterSnapshots);
            request.Marker = response.Marker;
        }
        while (response.Marker is not null);
        return results;
    }

    /// <summary>
    /// Delete a particular DB cluster.
    /// </summary>
    /// <param name="dbClusterIdentifier">DB cluster identifier.</param>
    /// <returns>DB cluster object.</returns>
    public async Task<DBCluster> DeleteDBClusterByIdentifierAsync(string
dbClusterIdentifier)
    {
        var response = await _amazonRDS.DeleteDBClusterAsync(
            new DeleteDBClusterRequest()
            {
                DBClusterIdentifier = dbClusterIdentifier,
                SkipFinalSnapshot = true
            });

        return response.DBCluster;
    }
```

```
    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstanceByIdentifierAsync(string
 dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - DB descrito ClusterParameterGroups
  - DB descrito ClusterParameters
  - DB descrito ClusterSnapshots
  - DescribeDBClusters
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions

- Modificar banco de dados ClusterParameterGroup

Exemplos de Auto Scaling usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace AutoScalingActions;

using Amazon.AutoScaling;

public class HelloAutoScaling
{
    /// <summary>
```

```
    /// Hello Amazon EC2 Auto Scaling. List EC2 Auto Scaling groups.
    /// </summary>
    /// <param name="args"></param>
    /// <returns>Async Task.</returns>
    static async Task Main(string[] args)
    {
        var client = new AmazonAutoScalingClient();

        Console.WriteLine("Welcome to Amazon EC2 Auto Scaling.");
        Console.WriteLine("Let's get a description of your Auto Scaling groups.");

        var response = await client.DescribeAutoScalingGroupsAsync();

        response.AutoScalingGroups.ForEach(autoScalingGroup =>
        {

 Console.WriteLine($"{autoScalingGroup.AutoScalingGroupName}\t{autoScalingGroup.Availability
        });

        if (response.AutoScalingGroups.Count == 0)
        {
            Console.WriteLine("Sorry, you don't have any Amazon EC2 Auto Scaling
 groups.");
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Anexar um grupo de destino ELB ao grupo do Auto Scaling

O exemplo de código a seguir mostra como anexar um grupo destino ELB a um grupo Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName, string
 targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
```

- Para obter detalhes da API, consulte AttachLoadBalancerTargetGroupsa Referência AWS SDK for .NET da API.

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create a new Amazon EC2 Auto Scaling group.
/// </summary>
/// <param name="groupName">The name to use for the new Auto Scaling
/// group.</param>
/// <param name="launchTemplateName">The name of the Amazon EC2 Auto Scaling
/// launch template to use to create instances in the group.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> CreateAutoScalingGroupAsync(
    string groupName,
    string launchTemplateName,
    string availabilityZone)
{
    var templateSpecification = new LaunchTemplateSpecification
    {
        LaunchTemplateName = launchTemplateName,
    };

    var zoneList = new List<string>
        {
            availabilityZone,
        };

    var request = new CreateAutoScalingGroupRequest
    {
        AutoScalingGroupName = groupName,
        AvailabilityZones = zoneList,
        LaunchTemplate = templateSpecification,
        MaxSize = 6,
        MinSize = 1
    };
```

```
        var response = await
_amazonAutoScaling.CreateAutoScalingGroupAsync(request);
        Console.WriteLine($"{groupName} Auto Scaling Group created");
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for .NET da API.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar o tamanho mínimo de um grupo do Auto Scaling para zero, encerrar todas as instâncias no grupo e excluir o grupo.

```
    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
```

```
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for {instanceId}.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }
```

```
    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }
```

```
    /// <summary>
    /// Delete an Auto Scaling group.
    /// </summary>
```

```
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAutoScalingGroupAsync(
        string groupName)
    {
        var deleteAutoScalingGroupRequest = new DeleteAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            ForceDelete = true,
        };

        var response = await
 _amazonAutoScaling.DeleteAutoScalingGroupAsync(deleteAutoScalingGroupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully deleted {groupName}");
            return true;
        }

        Console.WriteLine($"Couldn't delete {groupName}.");
        return false;
    }
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for .NET da API.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Disable the collection of metric data for an Amazon EC2 Auto Scaling
    /// group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DisableMetricsCollectionAsync(string groupName)
    {
        var request = new DisableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
        };

        var response = await
_amazonAutoScaling.DisableMetricsCollectionAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for .NET da API.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Enable the collection of metric data for an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> EnableMetricsCollectionAsync(string groupName)
    {
        var listMetrics = new List<string>
            {
                "GroupMaxSize",
            };

        var collectionRequest = new EnableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
            Metrics = listMetrics,
            Granularity = "1Minute",
        };

        var response = await
_amazonAutoScaling.EnableMetricsCollectionAsync(collectionRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for .NET da API.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informações sobre grupos do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
```

```
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
                    instanceIds.Add(instance.InstanceId);
                });
            }
        });

        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;

        return instanceDetails;
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for .NET da API.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
                    instanceIds.Add(instance.InstanceId);
                });
            }
        });

        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;
```

```
        return instanceDetails;
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for .NET da API.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informações sobre as atividades do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a list of the Amazon EC2 Auto Scaling activities for an
    /// Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling activities.</returns>
    public async Task<List<Amazon.AutoScaling.Model.Activity>>
 DescribeScalingActivitiesAsync(
        string groupName)
    {
        var scalingActivitiesRequest = new DescribeScalingActivitiesRequest
        {
            AutoScalingGroupName = groupName,
            MaxRecords = 10,
        };

        var response = await
 _amazonAutoScaling.DescribeScalingActivitiesAsync(scalingActivitiesRequest);
        return response.Activities;
```

```
    }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for .NET da API.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Set the desired capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="desiredCapacity">The desired capacity for the Auto
    /// Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SetDesiredCapacityAsync(
        string groupName,
        int desiredCapacity)
    {
        var capacityRequest = new SetDesiredCapacityRequest
        {
            AutoScalingGroupName = groupName,
            DesiredCapacity = desiredCapacity,
        };

        var response = await
_amazonAutoScaling.SetDesiredCapacityAsync(capacityRequest);
        Console.WriteLine($"You have set the DesiredCapacity to
{desiredCapacity}.");
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for .NET da API.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Terminate all instances in the Auto Scaling group in preparation for
    /// deleting the group.
    /// </summary>
    /// <param name="instanceId">The instance Id of the instance to terminate.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> TerminateInstanceInAutoScalingGroupAsync(
        string instanceId)
    {
        var request = new TerminateInstanceInAutoScalingGroupRequest
        {
            InstanceId = instanceId,
            ShouldDecrementDesiredCapacity = false,
        };

        var response = await
 _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(request);
```

```
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You have terminated the instance: {instanceId}");
            return true;
        }

        Console.WriteLine($"Could not terminate {instanceId}");
        return false;
    }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for .NET da API.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo do Auto Scaling.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <param name="maxSize">The maximum number of instances that can be
    /// created for the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        int maxSize)
    {
        var templateSpecification = new LaunchTemplateSpecification
```

```
        {
            LaunchTemplateName = launchTemplateName,
        };

        var groupRequest = new UpdateAutoScalingGroupRequest
        {
            MaxSize = maxSize,
            AutoScalingGroupName = groupName,
            LaunchTemplate = templateSpecification,
        };

        var response = await
_amazonAutoScaling.UpdateAutoScalingGroupAsync(groupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully updated the Auto Scaling group
{groupName}.");
            return true;
        }
        else
        {
            return false;
        }
    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for .NET da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.

- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
    static async Task Main(string[] args)
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
```

```
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
```

```
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper = host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several AWS
resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways to
make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");
```

```
        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide book,
movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each contain
a Python web server.");
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs 'server_startup_script.sh'
when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the `server.py`
script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
```

```
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3, _autoScalerWrapper.GroupName,
zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or continue
with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");
```

```
        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
 _autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGroupN
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.LoadB
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper.Lo
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port, ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for your
 default VPC must\n"
```

```
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management Console.
\n");

                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound traffic from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port, ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
 ipString);
                }
            }
            loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
 browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
 configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
 endpoint:\n");
```

```
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite of
these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
```

```
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
 checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service fails,
 the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
 customer with a somewhat better experience than failure.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
 "static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
 checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
 _smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in the
 target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
 _autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
```

```
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile that
contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo, a
deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not for
Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the Auto
Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load balancer
can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two for
the load balancer to detect the unhealthy");
```

```
        Console.WriteLine("instance. Sending a GET request to the load balancer
 endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
 rotation.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by an
 auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler start
 a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
 instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a successful
 recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the load
 balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance typically
 takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
 instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
 checks mean all instances report as unhealthy.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
 continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
 return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
```

```
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account, we
can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBalanc
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGroup
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupName)
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
```

```
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
```

```
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with a
specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
```

```
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to the
role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
                                         "\"Effect\": \"Allow\"," +
                                         "\"Principal\": {" +
                                         "\"Service\": [" +
                                             "\"ec2.amazonaws.com\"" +
                                         "]" +
                                         "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                                    "}]" +
                                "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
```

```
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
```

```
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
```

```
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
    /// The launch template specifies a Bash script in its user data field that runs
after
    /// the instance is started. This script installs the Python packages and starts
a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to create
and attach to the profile.</param>
```

```
    /// <returns>The template object.</returns>
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName, _instanceRoleName,
_instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new
                            LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
```

```
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with size
 {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
 exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
```

```
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
```

```
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await _amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
```

```
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }
```

```
    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
```

```
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
```

```
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for {instanceId}.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
```

```
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
```

```
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the calling
computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP address
while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
```

```
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be open
to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
```

```
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName, string
 targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
```

```
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
```

```
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened times
 and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer exists.</
param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
```

```
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
        var loadBalancerReady = false;
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
                    await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;
```

```
                loadBalancerReady = loadBalancerState ==
 LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
```

```
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
```

```
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn = targetArn });
                Console.WriteLine($"Deleted load balancing target group
{groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
```

```
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books, movies,
 and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
```

```
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };
```

```
            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await File.ReadAllTextAsync(recommendationsPath);
        var records =
            JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
```

```
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-architecture-
table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";
```

```
    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
global using Amazon.AutoScaling;
global using Amazon.AutoScaling.Model;
global using Amazon.CloudWatch;
global using AutoScalingActions;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;



using Amazon.EC2;
using Microsoft.Extensions.Configuration;
using Host = Microsoft.Extensions.Hosting.Host;

namespace AutoScalingBasics;
```

```
public class AutoScalingBasics
{

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EC2 Auto Scaling, Amazon
        // CloudWatch, and Amazon EC2.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonAutoScaling>()
                .AddAWSService<IAmazonCloudWatch>()
                .AddAWSService<IAmazonEC2>()
                .AddTransient<AutoScalingWrapper>()
                .AddTransient<CloudWatchWrapper>()
                .AddTransient<EC2Wrapper>()
                .AddTransient<UIWrapper>()
            )
            .Build();


        var autoScalingWrapper =
 host.Services.GetRequiredService<AutoScalingWrapper>();
        var cloudWatchWrapper =
 host.Services.GetRequiredService<CloudWatchWrapper>();
        var ec2Wrapper = host.Services.GetRequiredService<EC2Wrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var imageId = configuration["ImageId"];
        var instanceType = configuration["InstanceType"];
        var launchTemplateName = configuration["LaunchTemplateName"];

        launchTemplateName += Guid.NewGuid().ToString();
```

```
        // The name of the Auto Scaling group.
        var groupName = configuration["GroupName"];

        uiWrapper.DisplayTitle("Auto Scaling Basics");
        uiWrapper.DisplayAutoScalingBasicsDescription();

        // Create the launch template and save the template Id to use when deleting
the
        // launch template at the end of the application.
        var launchTemplateId = await ec2Wrapper.CreateLaunchTemplateAsync(imageId!,
instanceType!, launchTemplateName);

        // Confirm that the template was created by asking for a description of it.
        await ec2Wrapper.DescribeLaunchTemplateAsync(launchTemplateName);

        uiWrapper.PressEnter();

        var availabilityZones = await ec2Wrapper.ListAvailabilityZonesAsync();

        Console.WriteLine($"Creating an Auto Scaling group named {groupName}.");
        await autoScalingWrapper.CreateAutoScalingGroupAsync(
            groupName!,
            launchTemplateName,
            availabilityZones.First().ZoneName);

        // Keep checking the details of the new group until its lifecycle state
        // is "InService".
        Console.WriteLine($"Waiting for the Auto Scaling group to be active.");

        List<AutoScalingInstanceDetails> instanceDetails;

        do
        {
            instanceDetails = await
autoScalingWrapper.DescribeAutoScalingInstancesAsync(groupName!);
        }
        while (instanceDetails.Count <= 0);

        Console.WriteLine($"Auto scaling group {groupName} successfully created.");
        Console.WriteLine($"{instanceDetails.Count} instances were created for the
group.");

        // Display the details of the Auto Scaling group.
```

```
        instanceDetails.ForEach(detail =>
        {
            Console.WriteLine($"Group name: {detail.AutoScalingGroupName}");
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Metrics collection");
        Console.WriteLine($"Enable metrics collection for {groupName}");
        await autoScalingWrapper.EnableMetricsCollectionAsync(groupName!);

        // Show the metrics that are collected for the group.

        // Update the maximum size of the group to three instances.
        Console.WriteLine("--- Update the Auto Scaling group to increase max size to
3 ---");
        int maxSize = 3;
        await autoScalingWrapper.UpdateAutoScalingGroupAsync(groupName!,
launchTemplateName, maxSize);

        Console.WriteLine("--- Describe all Auto Scaling groups to show the current
state of the group ---");
        var groups = await
autoScalingWrapper.DescribeAutoScalingGroupsAsync(groupName!);

        uiWrapper.DisplayGroupDetails(groups!);

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Describe account limits");
        await autoScalingWrapper.DescribeAccountLimitsAsync();

        uiWrapper.WaitABit(60, "Waiting for the resources to be ready.");

        uiWrapper.DisplayTitle("Set desired capacity");
        int desiredCapacity = 2;
        await autoScalingWrapper.SetDesiredCapacityAsync(groupName!,
desiredCapacity);

        Console.WriteLine("Get the two instance Id values");

        // Empty the group before getting the details again.
        groups!.Clear();
```

```
        groups = await
autoScalingWrapper.DescribeAutoScalingGroupsAsync(groupName!);
        if (groups is not null)
        {
            foreach (AutoScalingGroup group in groups)
            {
                Console.WriteLine($"The group name is
{group.AutoScalingGroupName}");
                Console.WriteLine($"The group ARN is {group.AutoScalingGroupARN}");
                var instances = group.Instances;
                foreach (Amazon.AutoScaling.Model.Instance instance in instances)
                {
                    Console.WriteLine($"The instance id is {instance.InstanceId}");
                    Console.WriteLine($"The lifecycle state is
{instance.LifecycleState}");
                }
            }
        }

        uiWrapper.DisplayTitle("Scaling Activities");
        Console.WriteLine("Let's list the scaling activities that have occurred for
the group.");
        var activities = await
autoScalingWrapper.DescribeScalingActivitiesAsync(groupName!);
        if (activities is not null)
        {
            activities.ForEach(activity =>
            {
                Console.WriteLine($"The activity Id is {activity.ActivityId}");
                Console.WriteLine($"The activity details are {activity.Details}");
            });
        }

        // Display the Amazon CloudWatch metrics that have been collected.
        var metrics = await cloudWatchWrapper.GetCloudWatchMetricsAsync(groupName!);
        Console.WriteLine($"Metrics collected for {groupName}:");
        metrics.ForEach(metric =>
        {
            Console.Write($"Metric name: {metric.MetricName}\t");
            Console.WriteLine($"Namespace: {metric.Namespace}");
        });

        var dataPoints = await
cloudWatchWrapper.GetMetricStatisticsAsync(groupName!);
```

```
        Console.WriteLine("Details for the metrics collected:");
        dataPoints.ForEach(detail =>
        {
            Console.WriteLine(detail);
        });

        // Disable metrics collection.
        Console.WriteLine("Disabling the collection of metrics for {groupName}.");
        var success = await
autoScalingWrapper.DisableMetricsCollectionAsync(groupName!);

        if (success)
        {
            Console.WriteLine($"Successfully stopped metrics collection for
{groupName}.");
        }
        else
        {
            Console.WriteLine($"Could not stop metrics collection for
{groupName}.");
        }

        // Terminate all instances in the group.
        uiWrapper.DisplayTitle("Terminating Auto Scaling instances");
        Console.WriteLine("Now terminating all instances in the Auto Scaling
group.");

        if (groups is not null)
        {
            groups.ForEach(group =>
            {
                // Only delete instances in the AutoScaling group we created.
                if (group.AutoScalingGroupName == groupName)
                {
                    group.Instances.ForEach(async instance =>
                    {
                        await
autoScalingWrapper.TerminateInstanceInAutoScalingGroupAsync(instance.InstanceId);
                    });
                }
            });
        }

        // After all instances are terminated, delete the group.
```

```
        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("Deleting the Auto Scaling group.");
        await autoScalingWrapper.DeleteAutoScalingGroupAsync(groupName!);

        // Delete the launch template.
        var deletedLaunchTemplateName = await
 ec2Wrapper.DeleteLaunchTemplateAsync(launchTemplateId);

        if (deletedLaunchTemplateName == launchTemplateName)
        {
            Console.WriteLine("Successfully deleted the launch template.");
        }

        Console.WriteLine("The demo is now concluded.");
    }
}


namespace AutoScalingBasics;

/// <summary>
/// A class to provide user interface methods for the EC2 AutoScaling Basics
/// scenario.
/// </summary>
public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Describe the steps in the EC2 AutoScaling Basics scenario.
    /// </summary>
    public void DisplayAutoScalingBasicsDescription()
    {
        Console.WriteLine("This code example performs the following operations:");
        Console.WriteLine(" 1. Creates an Amazon EC2 launch template.");
        Console.WriteLine(" 2. Creates an Auto Scaling group.");
        Console.WriteLine(" 3. Shows the details of the new Auto Scaling group");
        Console.WriteLine("    to show that only one instance was created.");
        Console.WriteLine(" 4. Enables metrics collection.");
        Console.WriteLine(" 5. Updates the Auto Scaling group to increase the");
        Console.WriteLine("    capacity to three.");
        Console.WriteLine(" 6. Describes Auto Scaling groups again to show the");
        Console.WriteLine("    current state of the group.");
        Console.WriteLine(" 7. Changes the desired capacity of the Auto Scaling");
```

```
        Console.WriteLine("    group to use an additional instance.");
        Console.WriteLine(" 8. Shows that there are now instances in the group.");
        Console.WriteLine(" 9. Lists the scaling activities that have occurred for
 the group.");
        Console.WriteLine("10. Displays the Amazon CloudWatch metrics that have");
        Console.WriteLine("    been collected.");
        Console.WriteLine("11. Disables metrics collection.");
        Console.WriteLine("12. Terminates all instances in the Auto Scaling
 group.");
        Console.WriteLine("13. Deletes the Auto Scaling group.");
        Console.WriteLine("14. Deletes the Amazon EC2 launch template.");
        PressEnter();
    }

    /// <summary>
    /// Display information about the Amazon Ec2 AutoScaling groups passed
    /// in the list of AutoScalingGroup objects.
    /// </summary>
    /// <param name="groups">A list of AutoScalingGroup objects.</param>
    public void DisplayGroupDetails(List<AutoScalingGroup> groups)
    {
        if (groups is null)
            return;

        groups.ForEach(group =>
        {
            Console.WriteLine($"Group name:\t{group.AutoScalingGroupName}");
            Console.WriteLine($"Group created:\t{group.CreatedTime}");
            Console.WriteLine($"Maximum number of instances:\t{group.MaxSize}");
            Console.WriteLine($"Desired number of instances:
\t{group.DesiredCapacity}");
        });
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }
```

```
    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar modelos e métricas de execução. Essas funções incluem Auto Scaling, Amazon EC2 e ações. CloudWatch

```
namespace AutoScalingActions;

using Amazon.AutoScaling;
using Amazon.AutoScaling.Model;

/// <summary>
/// A class that includes methods to perform Amazon EC2 Auto Scaling
/// actions.
/// </summary>
public class AutoScalingWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;

    /// <summary>
    /// Constructor for the AutoScalingWrapper class.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected Amazon EC2 Auto Scaling
 client.</param>
    public AutoScalingWrapper(IAmazonAutoScaling amazonAutoScaling)
    {
        _amazonAutoScaling = amazonAutoScaling;
    }


    /// <summary>
    /// Create a new Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name to use for the new Auto Scaling
    /// group.</param>
    /// <param name="launchTemplateName">The name of the Amazon EC2 Auto Scaling
    /// launch template to use to create instances in the group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        string availabilityZone)
    {
```

```
        var templateSpecification = new LaunchTemplateSpecification
        {
            LaunchTemplateName = launchTemplateName,
        };

        var zoneList = new List<string>
            {
                availabilityZone,
            };

        var request = new CreateAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            AvailabilityZones = zoneList,
            LaunchTemplate = templateSpecification,
            MaxSize = 6,
            MinSize = 1
        };

        var response = await
_amazonAutoScaling.CreateAutoScalingGroupAsync(request);
        Console.WriteLine($"{groupName} Auto Scaling Group created");
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }



    /// <summary>
    /// Retrieve information about Amazon EC2 Auto Scaling quotas to the
    /// active AWS account.
    /// </summary>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DescribeAccountLimitsAsync()
    {
        var response = await _amazonAutoScaling.DescribeAccountLimitsAsync();
        Console.WriteLine("The maximum number of Auto Scaling groups is " +
response.MaxNumberOfAutoScalingGroups);
        Console.WriteLine("The current number of Auto Scaling groups is " +
response.NumberOfAutoScalingGroups);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Retrieve a list of the Amazon EC2 Auto Scaling activities for an
    /// Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling activities.</returns>
    public async Task<List<Amazon.AutoScaling.Model.Activity>>
 DescribeScalingActivitiesAsync(
        string groupName)
    {
        var scalingActivitiesRequest = new DescribeScalingActivitiesRequest
        {
            AutoScalingGroupName = groupName,
            MaxRecords = 10,
        };

        var response = await
 _amazonAutoScaling.DescribeScalingActivitiesAsync(scalingActivitiesRequest);
        return response.Activities;
    }



    /// <summary>
    /// Get data about the instances in an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling details.</returns>
    public async Task<List<AutoScalingInstanceDetails>>
 DescribeAutoScalingInstancesAsync(
        string groupName)
    {
        var groups = await DescribeAutoScalingGroupsAsync(groupName);
        var instanceIds = new List<string>();
        groups!.ForEach(group =>
        {
            if (group.AutoScalingGroupName == groupName)
            {
                group.Instances.ForEach(instance =>
                {
                    instanceIds.Add(instance.InstanceId);
                });
```

```
            }
        });

        var scalingGroupsRequest = new DescribeAutoScalingInstancesRequest
        {
            MaxRecords = 10,
            InstanceIds = instanceIds,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingInstancesAsync(scalingGroupsRequest);
        var instanceDetails = response.AutoScalingInstances;

        return instanceDetails;
    }



    /// <summary>
    /// Retrieve a list of information about Amazon EC2 Auto Scaling groups.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of Amazon EC2 Auto Scaling groups.</returns>
    public async Task<List<AutoScalingGroup>?> DescribeAutoScalingGroupsAsync(
        string groupName)
    {
        var groupList = new List<string>
            {
                groupName,
            };

        var request = new DescribeAutoScalingGroupsRequest
        {
            AutoScalingGroupNames = groupList,
        };

        var response = await
 _amazonAutoScaling.DescribeAutoScalingGroupsAsync(request);
        var groups = response.AutoScalingGroups;

        return groups;
    }
```

```
    /// <summary>
    /// Delete an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAutoScalingGroupAsync(
        string groupName)
    {
        var deleteAutoScalingGroupRequest = new DeleteAutoScalingGroupRequest
        {
            AutoScalingGroupName = groupName,
            ForceDelete = true,
        };

        var response = await
 _amazonAutoScaling.DeleteAutoScalingGroupAsync(deleteAutoScalingGroupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully deleted {groupName}");
            return true;
        }

        Console.WriteLine($"Couldn't delete {groupName}.");
        return false;
    }


    /// <summary>
    /// Disable the collection of metric data for an Amazon EC2 Auto Scaling
    /// group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DisableMetricsCollectionAsync(string groupName)
    {
        var request = new DisableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
        };
```

```
        var response = await
_amazonAutoScaling.DisableMetricsCollectionAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Enable the collection of metric data for an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> EnableMetricsCollectionAsync(string groupName)
    {
        var listMetrics = new List<string>
            {
                "GroupMaxSize",
            };

        var collectionRequest = new EnableMetricsCollectionRequest
        {
            AutoScalingGroupName = groupName,
            Metrics = listMetrics,
            Granularity = "1Minute",
        };

        var response = await
_amazonAutoScaling.EnableMetricsCollectionAsync(collectionRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Set the desired capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="desiredCapacity">The desired capacity for the Auto
    /// Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SetDesiredCapacityAsync(
        string groupName,
        int desiredCapacity)
    {
        var capacityRequest = new SetDesiredCapacityRequest
        {
```

```
            AutoScalingGroupName = groupName,
            DesiredCapacity = desiredCapacity,
        };

        var response = await
 _amazonAutoScaling.SetDesiredCapacityAsync(capacityRequest);
        Console.WriteLine($"You have set the DesiredCapacity to
 {desiredCapacity}.");

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Terminate all instances in the Auto Scaling group in preparation for
    /// deleting the group.
    /// </summary>
    /// <param name="instanceId">The instance Id of the instance to terminate.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> TerminateInstanceInAutoScalingGroupAsync(
        string instanceId)
    {
        var request = new TerminateInstanceInAutoScalingGroupRequest
        {
            InstanceId = instanceId,
            ShouldDecrementDesiredCapacity = false,
        };

        var response = await
 _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You have terminated the instance: {instanceId}");
            return true;
        }

        Console.WriteLine($"Could not terminate {instanceId}");
        return false;
    }
```

```
    /// <summary>
    /// Update the capacity of an Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <param name="maxSize">The maximum number of instances that can be
    /// created for the Auto Scaling group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateAutoScalingGroupAsync(
        string groupName,
        string launchTemplateName,
        int maxSize)
    {
        var templateSpecification = new LaunchTemplateSpecification
        {
            LaunchTemplateName = launchTemplateName,
        };

        var groupRequest = new UpdateAutoScalingGroupRequest
        {
            MaxSize = maxSize,
            AutoScalingGroupName = groupName,
            LaunchTemplate = templateSpecification,
        };

        var response = await
 _amazonAutoScaling.UpdateAutoScalingGroupAsync(groupRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"You successfully updated the Auto Scaling group
 {groupName}.");
            return true;
        }
        else
        {
            return false;
        }
    }

}


namespace AutoScalingActions;
```

```
using Amazon.EC2;
using Amazon.EC2.Model;

public class EC2Wrapper
{
    private readonly IAmazonEC2 _amazonEc2;

    /// <summary>
    /// Constructor for the EC2Wrapper class.
    /// </summary>
    /// <param name="amazonEc2">The injected Amazon EC2 client.</param>
    public EC2Wrapper(IAmazonEC2 amazonEc2)
    {
        _amazonEc2 = amazonEc2;
    }

    /// <summary>
    /// Create a new Amazon EC2 launch template.
    /// </summary>
    /// <param name="imageId">The image Id to use for instances launched
    /// using the Amazon EC2 launch template.</param>
    /// <param name="instanceType">The type of EC2 instances to create.</param>
    /// <param name="launchTemplateName">The name of the launch template.</param>
    /// <returns>Returns the TemplateID of the new launch template.</returns>
    public async Task<string> CreateLaunchTemplateAsync(
        string imageId,
        string instanceType,
        string launchTemplateName)
    {
        var request = new CreateLaunchTemplateRequest
        {
            LaunchTemplateData = new RequestLaunchTemplateData
            {
                ImageId = imageId,
                InstanceType = instanceType,
            },
            LaunchTemplateName = launchTemplateName,
        };

        var response = await _amazonEc2.CreateLaunchTemplateAsync(request);

        return response.LaunchTemplate.LaunchTemplateId;
    }
```

```
    /// <summary>
    /// Delete an Amazon EC2 launch template.
    /// </summary>
    /// <param name="launchTemplateId">The TemplateId of the launch template to
    /// delete.</param>
    /// <returns>The name of the EC2 launch template that was deleted.</returns>
    public async Task<string> DeleteLaunchTemplateAsync(string launchTemplateId)
    {
        var request = new DeleteLaunchTemplateRequest
        {
            LaunchTemplateId = launchTemplateId,
        };

        var response = await _amazonEc2.DeleteLaunchTemplateAsync(request);
        return response.LaunchTemplate.LaunchTemplateName;
    }

    /// <summary>
    /// Retrieve information about an EC2 launch template.
    /// </summary>
    /// <param name="launchTemplateName">The name of the EC2 launch template.</
param>
    /// <returns>A Boolean value that indicates the success or failure of
    /// the operation.</returns>
    public async Task<bool> DescribeLaunchTemplateAsync(string launchTemplateName)
    {
        var request = new DescribeLaunchTemplatesRequest
        {
            LaunchTemplateNames = new List<string> { launchTemplateName, },
        };

        var response = await _amazonEc2.DescribeLaunchTemplatesAsync(request);

        if (response.LaunchTemplates is not null)
        {
            response.LaunchTemplates.ForEach(template =>
            {
                Console.Write($"{template.LaunchTemplateName}\t");
                Console.WriteLine(template.LaunchTemplateId);
            });

            return true;
        }
```

```
        return false;
    }

    /// <summary>
    /// Retrieve the availability zones for the current region.
    /// </summary>
    /// <returns>A collection of availability zones.</returns>
    public async Task<List<AvailabilityZone>> ListAvailabilityZonesAsync()
    {
        var response = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());

        return response.AvailabilityZones;
    }
}


namespace AutoScalingActions;

using Amazon.CloudWatch;
using Amazon.CloudWatch.Model;

/// <summary>
/// Contains methods to access Amazon CloudWatch metrics for the
/// Amazon EC2 Auto Scaling basics scenario.
/// </summary>
public class CloudWatchWrapper
{
    private readonly IAmazonCloudWatch _amazonCloudWatch;

    /// <summary>
    /// Constructor for the CloudWatchWrapper.
    /// </summary>
    /// <param name="amazonCloudWatch">The injected CloudWatch client.</param>
    public CloudWatchWrapper(IAmazonCloudWatch amazonCloudWatch)
    {
        _amazonCloudWatch = amazonCloudWatch;
    }

    /// <summary>
    /// Retrieve the metrics information collection for the Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Auto Scaling group.</param>
```

```
    /// <returns>A list of Metrics collected for the Auto Scaling group.</returns>
    public async Task<List<Amazon.CloudWatch.Model.Metric>>
 GetCloudWatchMetricsAsync(string groupName)
    {
        var filter = new DimensionFilter
        {
            Name = "AutoScalingGroupName",
            Value = $"{groupName}",
        };

        var request = new ListMetricsRequest
        {
            MetricName = "AutoScalingGroupName",
            Dimensions = new List<DimensionFilter> { filter },
            Namespace = "AWS/AutoScaling",
        };

        var response = await _amazonCloudWatch.ListMetricsAsync(request);

        return response.Metrics;
    }

    /// <summary>
    /// Retrieve the metric data collected for an Amazon EC2 Auto Scaling group.
    /// </summary>
    /// <param name="groupName">The name of the Amazon EC2 Auto Scaling group.</
param>
    /// <returns>A list of data points.</returns>
    public async Task<List<Datapoint>> GetMetricStatisticsAsync(string groupName)
    {
        var metricDimensions = new List<Dimension>
            {
                new Dimension
                {
                    Name = "AutoScalingGroupName",
                    Value = $"{groupName}",
                },
            };

        // The start time will be yesterday.
        var startTime = DateTime.UtcNow.AddDays(-1);

        var request = new GetMetricStatisticsRequest
        {
```

```
            MetricName = "AutoScalingGroupName",
            Dimensions = metricDimensions,
            Namespace = "AWS/AutoScaling",
            Period = 60, // 60 seconds.
            Statistics = new List<string>() { "Minimum" },
            StartTimeUtc = startTime,
            EndTimeUtc = DateTime.UtcNow,
        };

        var response = await _amazonCloudWatch.GetMetricStatisticsAsync(request);

        return response.Datapoints;
    }

}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Bedrock

Os exemplos de código a seguir mostram como começar a usar o Amazon Bedrock.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon;
using Amazon.Bedrock;
using Amazon.Bedrock.Model;

namespace ListFoundationModelsExample
{
    /// <summary>
    /// This example shows how to list foundation models.
    /// </summary>
    internal class HelloBedrock
    {
        /// <summary>
        /// Main method to call the ListFoundationModelsAsync method.
        /// </summary>
        /// <param name="args"> The command line arguments. </param>
        static async Task Main(string[] args)
        {
```

```
            // Specify a region endpoint where Amazon Bedrock is available. For a
 list of supported region see https://docs.aws.amazon.com/bedrock/latest/userguide/
what-is-bedrock.html#bedrock-regions
            AmazonBedrockClient bedrockClient = new(RegionEndpoint.USWest2);

            await ListFoundationModelsAsync(bedrockClient);

        }


        /// <summary>
        /// List foundation models.
        /// </summary>
        /// <param name="bedrockClient"> The Amazon Bedrock client. </param>
        private static async Task ListFoundationModelsAsync(AmazonBedrockClient
 bedrockClient)
        {
            Console.WriteLine("List foundation models with no filter");

            try
            {
                ListFoundationModelsResponse response = await
 bedrockClient.ListFoundationModelsAsync(new ListFoundationModelsRequest()
                {
                });

                if (response?.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    foreach (var fm in response.ModelSummaries)
                    {
                        WriteToConsole(fm);
                    }
                }
                else
                {
                    Console.WriteLine("Something wrong happened");
                }
            }
            catch (AmazonBedrockException e)
            {
                Console.WriteLine(e.Message);
            }
        }
```

```
        /// <summary>
        /// Write the foundation model summary to console.
        /// </summary>
        /// <param name="foundationModel"> The foundation model summary to write to
 console. </param>
        private static void WriteToConsole(FoundationModelSummary foundationModel)
        {
            Console.WriteLine($"{foundationModel.ModelId}, Customization:
 {String.Join(", ", foundationModel.CustomizationsSupported)}, Stream:
 {foundationModel.ResponseStreamingSupported}, Input: {String.Join(",
 ", foundationModel.InputModalities)}, Output: {String.Join(", ",
 foundationModel.OutputModalities)}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for .NET da API.

Tópicos

- Ações

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base Bedrock disponíveis.

```
        /// <summary>
        /// List foundation models.
        /// </summary>
        /// <param name="bedrockClient"> The Amazon Bedrock client. </param>
        private static async Task ListFoundationModelsAsync(AmazonBedrockClient
bedrockClient)
        {
            Console.WriteLine("List foundation models with no filter");

            try
            {
                ListFoundationModelsResponse response = await
bedrockClient.ListFoundationModelsAsync(new ListFoundationModelsRequest()
                {
                });

                if (response?.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    foreach (var fm in response.ModelSummaries)
                    {
                        WriteToConsole(fm);
                    }
                }
                else
                {
                    Console.WriteLine("Something wrong happened");
                }
            }
            catch (AmazonBedrockException e)
            {
                Console.WriteLine(e.Message);
            }
        }
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for .NET da API.

Exemplos de Amazon Bedrock Runtime usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo Jurassic-2 da AI21 Labs no Amazon Bedrock para geração de texto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base Jurassic-2 da AI21 Labs.

```
        /// <summary>
        /// Asynchronously invokes the AI21 Labs Jurassic-2 model to run an
inference based on the provided input.
        /// </summary>
```

```
        /// <param name="prompt">The prompt that you want Claude to complete.</
param>
        /// <returns>The inference response from the model</returns>
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
        /// For the format, ranges, and default values for AI21 Labs Jurassic-2,
 refer to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-jurassic2.html
        /// </remarks>
        public static async Task<string> InvokeJurassic2Async(string prompt)
        {
            string jurassic2ModelId = "ai21.j2-mid-v1";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", prompt },
                { "maxTokens", 200 },
                { "temperature", 0.5 }
            }.ToJsonString();

            string generatedText = "";
            try
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
 InvokeModelRequest()
                {
                    ModelId = jurassic2ModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body)
                        .Result?["completions"]?
                        .AsArray()[0]?["data"]?
                        .AsObject()["text"]?.GetValue<string>() ?? "";
                }
                else
```

```
                {
                    Console.WriteLine("InvokeModelAsync failed with status code " +
 response.HttpStatusCode);
                }
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base Claude 2 da Anthropic para gerar texto.

```
        /// <summary>
        /// Asynchronously invokes the Anthropic Claude 2 model to run an inference
 based on the provided input.
        /// </summary>
        /// <param name="prompt">The prompt that you want Claude to complete.</
param>
        /// <returns>The inference response from the model</returns>
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
```

```
        /// For the format, ranges, and default values for Anthropic Claude, refer
 to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html
        /// </remarks>
        public static async Task<string> InvokeClaudeAsync(string prompt)
        {
            string claudeModelId = "anthropic.claude-v2";

            // Claude requires you to enclose the prompt as follows:
            string enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", enclosedPrompt },
                { "max_tokens_to_sample", 200 },
                { "temperature", 0.5 },
                { "stop_sequences", new JsonArray("\n\nHuman:") }
            }.ToJsonString();

            string generatedText = "";
            try
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
 InvokeModelRequest()
                {
                    ModelId = claudeModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body).Result?
["completion"]?.GetValue<string>() ?? "";
                }
                else
                {
                    Console.WriteLine("InvokeModelAsync failed with status code " +
 response.HttpStatusCode);
                }
```

```
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat da Meta Llama 2 no Amazon Bedrock para geração de texto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque de forma assíncrona o modelo de base da Meta Llama 2 para gerar texto.

```
        /// <summary>
        /// Asynchronously invokes the Meta Llama 2 Chat model to run an inference
 based on the provided input.
        /// </summary>
        /// <param name="prompt">The prompt that you want Llama 2 to complete.</
param>
        /// <returns>The inference response from the model</returns>
        /// <remarks>
        /// The different model providers have individual request and response
 formats.
        /// For the format, ranges, and default values for Meta Llama 2 Chat, refer
 to:
        ///     https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-meta.html
```

```
        /// </remarks>
        public static async Task<string> InvokeLlama2Async(string prompt)
        {
            string llama2ModelId = "meta.llama2-13b-chat-v1";

            AmazonBedrockRuntimeClient client = new(RegionEndpoint.USEast1);

            string payload = new JsonObject()
            {
                { "prompt", prompt },
                { "max_gen_len", 512 },
                { "temperature", 0.5 },
                { "top_p", 0.9 }
            }.ToJsonString();

            string generatedText = "";
            try
            {
                InvokeModelResponse response = await client.InvokeModelAsync(new
InvokeModelRequest()
                {
                    ModelId = llama2ModelId,
                    Body = AWSSDKUtils.GenerateMemoryStreamFromString(payload),
                    ContentType = "application/json",
                    Accept = "application/json"
                });

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    return JsonNode.ParseAsync(response.Body)
                        .Result?["generation"]?.GetValue<string>() ?? "";
                }
                else
                {
                    Console.WriteLine("InvokeModelAsync failed with status code " +
response.HttpStatusCode);
                }
            }
            catch (AmazonBedrockRuntimeException e)
            {
                Console.WriteLine(e.Message);
            }
            return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for .NET da API.

Cenários

Criar uma aplicação de playground para interagir com os modelos de base do Amazon Bedrock

O exemplo de código a seguir mostra como criar playgrounds para interagir com modelos de base do Amazon Bedrock em diferentes modalidades.

AWS SDK for .NET

O .NET Foundation Model (FM) Playground é um aplicativo de amostra do .NET MAUI Blazor que mostra como usar o Amazon Bedrock a partir do código C#. Este exemplo mostra como os desenvolvedores.NET e C# podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de bate-papo.
- Um playground de bate-papo por voz.
- Um playground de imagens.

O exemplo também lista e exibe os modelos básicos para acesso e suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock Runtime

CloudWatch exemplos usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET with CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá CloudWatch

O exemplo de código a seguir mostra como começar a usar o CloudWatch.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.CloudWatch;
using Amazon.CloudWatch.Model;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;

namespace CloudWatchActions;

public static class HelloCloudWatch
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon CloudWatch service.
        // Use your AWS profile name, or leave it blank to use the default profile.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonCloudWatch>()
            ).Build();

        // Now the client is available for injection.
        var cloudWatchClient =
 host.Services.GetRequiredService<IAmazonCloudWatch>();
```

```
        // You can use await and any of the async methods to get a response.
        var metricNamespace = "AWS/Billing";
        var response = await cloudWatchClient.ListMetricsAsync(new
 ListMetricsRequest
        {
            Namespace = metricNamespace
        });
        Console.WriteLine($"Hello Amazon CloudWatch! Following are some metrics
 available in the {metricNamespace} namespace:");
        Console.WriteLine();
        foreach (var metric in response.Metrics.Take(5))
        {
            Console.WriteLine($"\tMetric: {metric.MetricName}");
            Console.WriteLine($"\tNamespace: {metric.Namespace}");
            Console.WriteLine($"\tDimensions: {string.Join(", ",
 metric.Dimensions.Select(m => $"{m.Name}:{m.Value}"))}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar um painel

O exemplo de código a seguir mostra como criar um CloudWatch painel da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Set up a dashboard using a call to the wrapper class.
/// </summary>
/// <param name="customMetricNamespace">The metric namespace.</param>
/// <param name="customMetricName">The metric name.</param>
/// <param name="dashboardName">The name of the dashboard.</param>
/// <returns>A list of validation messages.</returns>
private static async Task<List<DashboardValidationMessage>> SetupDashboard(
    string customMetricNamespace, string customMetricName, string dashboardName)
{
    // Get the dashboard model from configuration.
    var newDashboard = new DashboardModel();
    _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);

    // Add a new metric to the dashboard.
    newDashboard.Widgets.Add(new Widget
    {
        Height = 8,
        Width = 8,
        Y = 8,
        X = 0,
        Type = "metric",
        Properties = new Properties
        {
            Metrics = new List<List<object>>
                { new() { customMetricNamespace, customMetricName } },
            View = "timeSeries",
            Region = "us-east-1",
            Stat = "Sum",
            Period = 86400,
            YAxis = new YAxis { Left = new Left { Min = 0, Max = 100 } },
            Title = "Custom Metric Widget",
            LiveData = true,
            Sparkline = true,
            Trend = true,
            Stacked = false,
            SetPeriodToTimeRange = false
        }
    });

    var newDashboardString = JsonSerializer.Serialize(newDashboard,
        new JsonSerializerOptions
```

```
            { DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull });
        var validationMessages =
            await _cloudWatchWrapper.PutDashboard(dashboardName,
 newDashboardString);

        return validationMessages;
    }

    /// <summary>
    /// Wrapper to create or add to a dashboard with metrics.
    /// </summary>
    /// <param name="dashboardName">The name for the dashboard.</param>
    /// <param name="dashboardBody">The metric data in JSON for the dashboard.</
param>
    /// <returns>A list of validation messages for the dashboard.</returns>
    public async Task<List<DashboardValidationMessage>> PutDashboard(string
 dashboardName,
        string dashboardBody)
    {
        // Updating a dashboard replaces all contents.
        // Best practice is to include a text widget indicating this dashboard was
 created programmatically.
        var dashboardResponse = await _amazonCloudWatch.PutDashboardAsync(
            new PutDashboardRequest()
            {
                DashboardName = dashboardName,
                DashboardBody = dashboardBody
            });

        return dashboardResponse.DashboardValidationMessages;
    }
```

- Para obter detalhes da API, consulte PutDashboarda Referência AWS SDK for .NET da API.

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Add a metric alarm to send an email when the metric passes a threshold.
   /// </summary>
   /// <param name="alarmDescription">A description of the alarm.</param>
   /// <param name="alarmName">The name for the alarm.</param>
   /// <param name="comparison">The type of comparison to use.</param>
   /// <param name="metricName">The name of the metric for the alarm.</param>
   /// <param name="metricNamespace">The namespace of the metric.</param>
   /// <param name="threshold">The threshold value for the alarm.</param>
   /// <param name="alarmActions">Optional actions to execute when in an alarm
state.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> PutMetricEmailAlarm(string alarmDescription, string
alarmName, ComparisonOperator comparison,
       string metricName, string metricNamespace, double threshold, List<string>
alarmActions = null!)
   {
       try
       {
           var putEmailAlarmResponse = await _amazonCloudWatch.PutMetricAlarmAsync(
               new PutMetricAlarmRequest()
               {
                   AlarmActions = alarmActions,
                   AlarmDescription = alarmDescription,
                   AlarmName = alarmName,
                   ComparisonOperator = comparison,
                   Threshold = threshold,
                   Namespace = metricNamespace,
                   MetricName = metricName,
                   EvaluationPeriods = 1,
                   Period = 10,
                   Statistic = new Statistic("Maximum"),
                   DatapointsToAlarm = 1,
                   TreatMissingData = "ignore"
```

```
                });
            return putEmailAlarmResponse.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (LimitExceededException lex)
        {
            _logger.LogError(lex, $"Unable to add alarm {alarmName}. Alarm quota has
already been reached.");
        }

        return false;
    }

    /// <summary>
    /// Add specific email actions to a list of action strings for a CloudWatch
alarm.
    /// </summary>
    /// <param name="accountId">The AccountId for the alarm.</param>
    /// <param name="region">The region for the alarm.</param>
    /// <param name="emailTopicName">An Amazon Simple Notification Service (SNS)
topic for the alarm email.</param>
    /// <param name="alarmActions">Optional list of existing alarm actions to append
to.</param>
    /// <returns>A list of string actions for an alarm.</returns>
    public List<string> AddEmailAlarmAction(string accountId, string region,
        string emailTopicName, List<string>? alarmActions = null)
    {
        alarmActions ??= new List<string>();
        var snsAlarmAction = $"arn:aws:sns:{region}:{accountId}:{emailTopicName}";
        alarmActions.Add(snsAlarmAction);
        return alarmActions;
    }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for .NET da API.

Criar um detector de anomalias

O exemplo de código a seguir mostra como criar um detector de CloudWatch anomalias da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Add an anomaly detector for a single metric.
   /// </summary>
   /// <param name="anomalyDetector">A single metric anomaly detector.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> PutAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
   {
       var putAlarmDetectorResult = await
_amazonCloudWatch.PutAnomalyDetectorAsync(
           new PutAnomalyDetectorRequest()
           {
               SingleMetricAnomalyDetector = anomalyDetector
           });

       return putAlarmDetectorResult.HttpStatusCode == HttpStatusCode.OK;
   }
```

- Para obter detalhes da API, consulte PutAnomalyDetectora Referência AWS SDK for .NET da API.

Excluir alarmes

O exemplo de código a seguir mostra como excluir CloudWatch alarmes da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAlarms(List<string> alarmNames)
    {
        var deleteAlarmsResult = await _amazonCloudWatch.DeleteAlarmsAsync(
            new DeleteAlarmsRequest()
            {
                AlarmNames = alarmNames
            });

        return deleteAlarmsResult.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for .NET da API.

Excluir um detector de anomalias

O exemplo de código a seguir mostra como excluir um detector de CloudWatch anomalias da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a single metric anomaly detector.
    /// </summary>
    /// <param name="anomalyDetector">The anomaly detector to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
    {
```

```
        var deleteAnomalyDetectorResponse = await
_amazonCloudWatch.DeleteAnomalyDetectorAsync(
            new DeleteAnomalyDetectorRequest()
            {
                SingleMetricAnomalyDetector = anomalyDetector
            });

        return deleteAnomalyDetectorResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteAnomalyDetectora Referência AWS SDK for .NET da API.

Excluir painéis

O exemplo de código a seguir mostra como excluir CloudWatch painéis da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a list of CloudWatch dashboards.
    /// </summary>
    /// <param name="dashboardNames">List of dashboard names to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDashboards(List<string> dashboardNames)
    {
        var deleteDashboardsResponse = await
_amazonCloudWatch.DeleteDashboardsAsync(
            new DeleteDashboardsRequest()
            {
                DashboardNames = dashboardNames
            });

        return deleteDashboardsResponse.HttpStatusCode == HttpStatusCode.OK;
```

```
    }
```

- Para obter detalhes da API, consulte DeleteDashboardsa Referência AWS SDK for .NET da API.

Descrever o histórico do alarme

O exemplo de código a seguir mostra como descrever um histórico de CloudWatch alarmes da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the history of an alarm for a number of days in the past.
    /// </summary>
    /// <param name="alarmName">The name of the alarm.</param>
    /// <param name="historyDays">The number of days in the past.</param>
    /// <returns>The list of alarm history data.</returns>
    public async Task<List<AlarmHistoryItem>> DescribeAlarmHistory(string alarmName,
int historyDays)
    {
        List<AlarmHistoryItem> alarmHistory = new List<AlarmHistoryItem>();
        var paginatedAlarmHistory =
_amazonCloudWatch.Paginators.DescribeAlarmHistory(
            new DescribeAlarmHistoryRequest()
            {
                AlarmName = alarmName,
                EndDateUtc = DateTime.UtcNow,
                HistoryItemType = HistoryItemType.StateUpdate,
                StartDateUtc = DateTime.UtcNow.AddDays(-historyDays)
            });

        await foreach (var data in paginatedAlarmHistory.AlarmHistoryItems)
        {
```

```
            alarmHistory.Add(data);
        }
        return alarmHistory;
    }
```

- Para obter detalhes da API, consulte DescribeAlarmHistorya Referência AWS SDK for .NET da API.

Descrever alarmes

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the current alarms, optionally filtered by state.
    /// </summary>
    /// <param name="stateValue">Optional filter for alarm state.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarms(StateValue? stateValue =
null)
    {
        List<MetricAlarm> alarms = new List<MetricAlarm>();
        var paginatedDescribeAlarms = _amazonCloudWatch.Paginators.DescribeAlarms(
            new DescribeAlarmsRequest()
            {
                StateValue = stateValue
            });

        await foreach (var data in paginatedDescribeAlarms.MetricAlarms)
        {
            alarms.Add(data);
        }
        return alarms;
```

```
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for .NET da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the current alarms for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarmsForMetric(string
metricNamespace, string metricName)
    {
        var alarmsResult = await _amazonCloudWatch.DescribeAlarmsForMetricAsync(
            new DescribeAlarmsForMetricRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName
            });

        return alarmsResult.MetricAlarms;
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for .NET da API.

Descrever detectores de anomalias

O exemplo de código a seguir mostra como descrever os detectores de CloudWatch anomalias da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Describe anomaly detectors for a metric and namespace.
   /// </summary>
   /// <param name="metricNamespace">The namespace of the metric.</param>
   /// <param name="metricName">The metric of the anomaly detectors.</param>
   /// <returns>The list of detectors.</returns>
   public async Task<List<AnomalyDetector>> DescribeAnomalyDetectors(string
metricNamespace, string metricName)
   {
       List<AnomalyDetector> detectors = new List<AnomalyDetector>();
       var paginatedDescribeAnomalyDetectors =
_amazonCloudWatch.Paginators.DescribeAnomalyDetectors(
           new DescribeAnomalyDetectorsRequest()
           {
               MetricName = metricName,
               Namespace = metricNamespace
           });

       await foreach (var data in
paginatedDescribeAnomalyDetectors.AnomalyDetectors)
       {
           detectors.Add(data);
       }

       return detectors;
   }
```

- Para obter detalhes da API, consulte DescribeAnomalyDetectorsa Referência AWS SDK for .NET da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Disable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DisableAlarmActions(List<string> alarmNames)
    {
        var disableAlarmActionsResult = await
_amazonCloudWatch.DisableAlarmActionsAsync(
            new DisableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return disableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for .NET da API.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Enable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableAlarmActions(List<string> alarmNames)
    {
        var enableAlarmActionsResult = await
_amazonCloudWatch.EnableAlarmActionsAsync(
            new EnableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return enableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for .NET da API.

Obter uma imagem de dados de métricas

O exemplo de código a seguir mostra como obter uma imagem de dados CloudWatch métricos da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get an image for a metric graphed over time.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metric">The name of the metric.</param>
    /// <param name="stat">The name of the stat to chart.</param>
    /// <param name="period">The period to use for the chart.</param>
    /// <returns>A memory stream for the chart image.</returns>
    public async Task<MemoryStream> GetTimeSeriesMetricImage(string metricNamespace,
string metric, string stat, int period)
    {
        var metricImageWidget = new
        {
            title = "Example Metric Graph",
            view = "timeSeries",
            stacked = false,
            period = period,
            width = 1400,
            height = 600,
            metrics = new List<List<object>>
                { new() { metricNamespace, metric, new { stat } } }
        };

        var metricImageWidgetString = JsonSerializer.Serialize(metricImageWidget);
        var imageResponse = await _amazonCloudWatch.GetMetricWidgetImageAsync(
            new GetMetricWidgetImageRequest()
            {
                MetricWidget = metricImageWidgetString
            });

        return imageResponse.MetricWidgetImage;
    }

    /// <summary>
    /// Save a metric image to a file.
    /// </summary>
    /// <param name="memoryStream">The MemoryStream for the metric image.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The path to the file.</returns>
    public string SaveMetricImage(MemoryStream memoryStream, string metricName)
    {
        var metricFileName = $"{metricName}_{DateTime.Now.Ticks}.png";
        using var sr = new StreamReader(memoryStream);
```

```
        // Writes the memory stream to a file.
        File.WriteAllBytes(metricFileName, memoryStream.ToArray());
        var filePath = Path.Join(AppDomain.CurrentDomain.BaseDirectory,
            metricFileName);
        return filePath;
    }
```

- Para obter detalhes da API, consulte GetMetricWidgetImagea Referência AWS SDK for .NET da API.

Obter detalhes do painel

O exemplo de código a seguir mostra como obter detalhes CloudWatch do painel da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information on a dashboard.
    /// </summary>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A JSON object with dashboard information.</returns>
    public async Task<string> GetDashboard(string dashboardName)
    {
        var dashboardResponse = await _amazonCloudWatch.GetDashboardAsync(
            new GetDashboardRequest()
            {
                DashboardName = dashboardName
            });

        return dashboardResponse.DashboardBody;
    }
```

- Para obter detalhes da API, consulte GetDashboarda Referência AWS SDK for .NET da API.

Obter dados de métricas

O exemplo de código a seguir mostra como obter dados CloudWatch métricos da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get data for CloudWatch metrics.
    /// </summary>
    /// <param name="minutesOfData">The number of minutes of data to include.</
param>
    /// <param name="useDescendingTime">True to return the data descending by
 time.</param>
    /// <param name="endDateUtc">The end date for the data, in UTC.</param>
    /// <param name="maxDataPoints">The maximum data points to include.</param>
    /// <param name="dataQueries">Optional data queries to include.</param>
    /// <returns>A list of the requested metric data.</returns>
    public async Task<List<MetricDataResult>> GetMetricData(int minutesOfData, bool
 useDescendingTime, DateTime? endDateUtc = null,
        int maxDataPoints = 0, List<MetricDataQuery>? dataQueries = null)
    {
        var metricData = new List<MetricDataResult>();
        // If no end time is provided, use the current time for the end time.
        endDateUtc ??= DateTime.UtcNow;
        var timeZoneOffset =
 TimeZoneInfo.Local.GetUtcOffset(endDateUtc.Value.ToLocalTime());
        var startTimeUtc = endDateUtc.Value.AddMinutes(-minutesOfData);
        // The timezone string should be in the format +0000, so use the timezone
 offset to format it correctly.
        var timeZoneString = $"{timeZoneOffset.Hours:D2}
{timeZoneOffset.Minutes:D2}";
        var paginatedMetricData = _amazonCloudWatch.Paginators.GetMetricData(
            new GetMetricDataRequest()
            {
```

```
                StartTimeUtc = startTimeUtc,
                EndTimeUtc = endDateUtc.Value,
                LabelOptions = new LabelOptions { Timezone = timeZoneString },
                ScanBy = useDescendingTime ? ScanBy.TimestampDescending :
ScanBy.TimestampAscending,
                MaxDatapoints = maxDataPoints,
                MetricDataQueries = dataQueries,
            });

        await foreach (var data in paginatedMetricData.MetricDataResults)
        {
            metricData.Add(data);
        }
        return metricData;
    }
```

- Para obter detalhes da API, consulte GetMetricDataa Referência AWS SDK for .NET da API.

Obter estatísticas de métricas

O exemplo de código a seguir mostra como obter estatísticas CloudWatch métricas da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get billing statistics using a call to a wrapper class.
    /// </summary>
    /// <returns>A collection of billing statistics.</returns>
    private static async Task<List<Datapoint>> SetupBillingStatistics()
    {
        // Make a request for EstimatedCharges with a period of one day for the past
seven days.
        var billingStatistics = await _cloudWatchWrapper.GetMetricStatistics(
            "AWS/Billing",
            "EstimatedCharges",
```

```
            new List<string>() { "Maximum" },
            new List<Dimension>() { new Dimension { Name = "Currency", Value =
"USD" } },
            7,
            86400);

        billingStatistics = billingStatistics.OrderBy(n => n.Timestamp).ToList();

        return billingStatistics;
    }

    /// <summary>
    /// Wrapper to get statistics for a specific CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <param name="statistics">The list of statistics to include.</param>
    /// <param name="dimensions">The list of dimensions to include.</param>
    /// <param name="days">The number of days in the past to include.</param>
    /// <param name="period">The period for the data.</param>
    /// <returns>A list of DataPoint objects for the statistics.</returns>
    public async Task<List<Datapoint>> GetMetricStatistics(string metricNamespace,
        string metricName, List<string> statistics, List<Dimension> dimensions, int
days, int period)
    {
        var metricStatistics = await _amazonCloudWatch.GetMetricStatisticsAsync(
            new GetMetricStatisticsRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName,
                Dimensions = dimensions,
                Statistics = statistics,
                StartTimeUtc = DateTime.UtcNow.AddDays(-days),
                EndTimeUtc = DateTime.UtcNow,
                Period = period
            });

        return metricStatistics.Datapoints;
    }
```

- Para obter detalhes da API, consulte GetMetricStatisticsa Referência AWS SDK for .NET da API.

Listar painéis

O exemplo de código a seguir mostra como listar os CloudWatch painéis da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of dashboards.
/// </summary>
/// <returns>A list of DashboardEntry objects.</returns>
public async Task<List<DashboardEntry>> ListDashboards()
{
    var results = new List<DashboardEntry>();
    var paginateDashboards = _amazonCloudWatch.Paginators.ListDashboards(
        new ListDashboardsRequest());
    // Get the entire list using the paginator.
    await foreach (var data in paginateDashboards.DashboardEntries)
    {
        results.Add(data);
    }

    return results;
}
```

- Para obter detalhes da API, consulte ListDashboardsa Referência AWS SDK for .NET da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List metrics available, optionally within a namespace.
    /// </summary>
    /// <param name="metricNamespace">Optional CloudWatch namespace to use when
listing metrics.</param>
    /// <param name="filter">Optional dimension filter.</param>
    /// <param name="metricName">Optional metric name filter.</param>
    /// <returns>The list of metrics.</returns>
    public async Task<List<Metric>> ListMetrics(string? metricNamespace = null,
DimensionFilter? filter = null, string? metricName = null)
    {
        var results = new List<Metric>();
        var paginateMetrics = _amazonCloudWatch.Paginators.ListMetrics(
            new ListMetricsRequest
            {
                Namespace = metricNamespace,
                Dimensions = filter != null ? new List<DimensionFilter> { filter } :
null,
                MetricName = metricName
            });
        // Get the entire list using the paginator.
        await foreach (var metric in paginateMetrics.Metrics)
        {
            results.Add(metric);
        }

        return results;
    }
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for .NET da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add some metric data using a call to a wrapper class.
    /// </summary>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <returns></returns>
    private static async Task<List<MetricDatum>> PutRandomMetricData(string
customMetricName,
        string customMetricNamespace)
    {
        List<MetricDatum> customData = new List<MetricDatum>();
        Random rnd = new Random();

        // Add 10 random values up to 100, starting with a timestamp 15 minutes in
the past.
        var utcNowMinus15 = DateTime.UtcNow.AddMinutes(-15);
        for (int i = 0; i < 10; i++)
        {
            var metricValue = rnd.Next(0, 100);
            customData.Add(
                new MetricDatum
                {
                    MetricName = customMetricName,
                    Value = metricValue,
                    TimestampUtc = utcNowMinus15.AddMinutes(i)
                }
            );
        }
```

```
        await _cloudWatchWrapper.PutMetricData(customMetricNamespace, customData);
        return customData;
    }

    /// <summary>
    /// Wrapper to add metric data to a CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricData">A data object for the metric data.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricData(string metricNamespace,
        List<MetricDatum> metricData)
    {
        var putDataResponse = await _amazonCloudWatch.PutMetricDataAsync(
            new PutMetricDataRequest()
            {
                MetricData = metricData,
                Namespace = metricNamespace,
            });

        return putDataResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for .NET da API.

Cenários

Começar a usar métricas, painéis e alarmes

O código de exemplo a seguir mostra como:

- Listar CloudWatch namespaces e métricas.
- Obtenha estatísticas para uma métrica e para faturamento estimado.
- Crie e atualize um painel.
- Crie e adicione dados a uma métrica.
- Crie e acione um alarme e, em seguida, visualize o histórico de alarmes.
- Crie um detector de anomalias.
- Obtenha uma imagem de métrica e, em seguida, limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public class CloudWatchScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    To enable billing metrics and statistics for this example, make sure billing
 alerts are enabled for your account:
    https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics

    This .NET example performs the following tasks:
        1. List and select a CloudWatch namespace.
        2. List and select a CloudWatch metric.
        3. Get statistics for a CloudWatch metric.
        4. Get estimated billing statistics for the last week.
        5. Create a new CloudWatch dashboard with two metrics.
        6. List current CloudWatch dashboards.
        7. Create a CloudWatch custom metric and add metric data.
        8. Add the custom metric to the dashboard.
        9. Create a CloudWatch alarm for the custom metric.
       10. Describe current CloudWatch alarms.
       11. Get recent data for the custom metric.
       12. Add data to the custom metric to trigger the alarm.
       13. Wait for an alarm state.
       14. Get history for the CloudWatch alarm.
       15. Add an anomaly detector.
       16. Describe current anomaly detectors.
       17. Get and display a metric image.
       18. Clean up resources.
    */

    private static ILogger logger = null!;
```

```
    private static CloudWatchWrapper _cloudWatchWrapper = null!;
    private static IConfiguration _configuration = null!;
    private static readonly List<string> _statTypes = new List<string>
{ "SampleCount", "Average", "Sum", "Minimum", "Maximum" };
    private static SingleMetricAnomalyDetector? anomalyDetector = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonCloudWatch>()
            .AddTransient<CloudWatchWrapper>()
        )
        .Build();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<CloudWatchScenario>();

        _cloudWatchWrapper = host.Services.GetRequiredService<CloudWatchWrapper>();

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon CloudWatch example scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            var selectedNamespace = await SelectNamespace();
            var selectedMetric = await SelectMetric(selectedNamespace);
            await GetAndDisplayMetricStatistics(selectedNamespace, selectedMetric);
            await GetAndDisplayEstimatedBilling();
            await CreateDashboardWithMetrics();
```

```
            await ListDashboards();
            await CreateNewCustomMetric();
            await AddMetricToDashboard();
            await CreateMetricAlarm();
            await DescribeAlarms();
            await GetCustomMetricData();
            await AddMetricDataForAlarm();
            await CheckForMetricAlarm();
            await GetAlarmHistory();
            anomalyDetector = await AddAnomalyDetector();
            await DescribeAnomalyDetectors();
            await GetAndOpenMetricImage();
            await CleanupResources();
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
            await CleanupResources();
        }

    }

    /// <summary>
    /// Select a namespace.
    /// </summary>
    /// <returns>The selected namespace.</returns>
    private static async Task<string> SelectNamespace()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. Select a CloudWatch Namespace from a list of
Namespaces.");
        var metrics = await _cloudWatchWrapper.ListMetrics();
        // Get a distinct list of namespaces.
        var namespaces = metrics.Select(m => m.Namespace).Distinct().ToList();
        for (int i = 0; i < namespaces.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {namespaces[i]}");
        }

        var namespaceChoiceNumber = 0;
        while (namespaceChoiceNumber < 1 || namespaceChoiceNumber >
namespaces.Count)
        {
            Console.WriteLine(
```

```
                "Select a namespace by entering a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out namespaceChoiceNumber);
        }

        var selectedNamespace = namespaces[namespaceChoiceNumber - 1];

        Console.WriteLine(new string('-', 80));

        return selectedNamespace;
    }

    /// <summary>
    /// Select a metric from a namespace.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <returns>The metric name.</returns>
    private static async Task<Metric> SelectMetric(string metricNamespace)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"2. Select a CloudWatch metric from a namespace.");

        var namespaceMetrics = await
_cloudWatchWrapper.ListMetrics(metricNamespace);

        for (int i = 0; i < namespaceMetrics.Count && i < 15; i++)
        {
            var dimensionsWithValues = namespaceMetrics[i].Dimensions
                .Where(d => !string.Equals("None", d.Value));
            Console.WriteLine($"\t{i + 1}. {namespaceMetrics[i].MetricName} " +
                              $"{string.Join(", :", dimensionsWithValues.Select(d =>
d.Value))}");
        }

        var metricChoiceNumber = 0;
        while (metricChoiceNumber < 1 || metricChoiceNumber >
namespaceMetrics.Count)
        {
            Console.WriteLine(
                "Select a metric by entering a number from the preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out metricChoiceNumber);
        }
```

```
        var selectedMetric = namespaceMetrics[metricChoiceNumber - 1];

        Console.WriteLine(new string('-', 80));

        return selectedMetric;
    }

    /// <summary>
    /// Get and display metric statistics for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task GetAndDisplayMetricStatistics(string metricNamespace,
Metric metric)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. Get CloudWatch metric statistics for the last day.");

        for (int i = 0; i < _statTypes.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {_statTypes[i]}");
        }

        var statisticChoiceNumber = 0;
        while (statisticChoiceNumber < 1 || statisticChoiceNumber >
_statTypes.Count)
        {
            Console.WriteLine(
                "Select a metric statistic by entering a number from the preceding
list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out statisticChoiceNumber);
        }

        var selectedStatistic = _statTypes[statisticChoiceNumber - 1];
        var statisticsList = new List<string> { selectedStatistic };

        var metricStatistics = await
_cloudWatchWrapper.GetMetricStatistics(metricNamespace, metric.MetricName,
statisticsList, metric.Dimensions, 1, 60);

        if (!metricStatistics.Any())
        {
```

```
            Console.WriteLine($"No {selectedStatistic} statistics found for {metric}
in namespace {metricNamespace}.");
        }

        metricStatistics = metricStatistics.OrderBy(s => s.Timestamp).ToList();
        for (int i = 0; i < metricStatistics.Count && i < 10; i++)
        {
            var metricStat = metricStatistics[i];
            var statValue =
metricStat.GetType().GetProperty(selectedStatistic)!.GetValue(metricStat, null);
            Console.WriteLine($"\t{i + 1}. Timestamp
{metricStatistics[i].Timestamp:G} {selectedStatistic}: {statValue}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get and display estimated billing statistics.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task GetAndDisplayEstimatedBilling()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. Get CloudWatch estimated billing for the last
week.");

        var billingStatistics = await SetupBillingStatistics();

        for (int i = 0; i < billingStatistics.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. Timestamp
{billingStatistics[i].Timestamp:G} : {billingStatistics[i].Maximum}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get billing statistics using a call to a wrapper class.
    /// </summary>
    /// <returns>A collection of billing statistics.</returns>
```

```
    private static async Task<List<Datapoint>> SetupBillingStatistics()
    {
        // Make a request for EstimatedCharges with a period of one day for the past
seven days.
        var billingStatistics = await _cloudWatchWrapper.GetMetricStatistics(
            "AWS/Billing",
            "EstimatedCharges",
            new List<string>() { "Maximum" },
            new List<Dimension>() { new Dimension { Name = "Currency", Value =
"USD" } },
            7,
            86400);

        billingStatistics = billingStatistics.OrderBy(n => n.Timestamp).ToList();

        return billingStatistics;
    }

    /// <summary>
    /// Create a dashboard with metrics.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task CreateDashboardWithMetrics()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"5. Create a new CloudWatch dashboard with metrics.");
        var dashboardName = _configuration["dashboardName"];
        var newDashboard = new DashboardModel();
        _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);
        var newDashboardString = JsonSerializer.Serialize(
            newDashboard,
            new JsonSerializerOptions
            {
                DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull
            });
        var validationMessages =
            await _cloudWatchWrapper.PutDashboard(dashboardName,
newDashboardString);

        Console.WriteLine(validationMessages.Any() ? $"\tValidation messages:" :
null);
        for (int i = 0; i < validationMessages.Count; i++)
```

```
        {
            Console.WriteLine($"\t{i + 1}. {validationMessages[i].Message}");
        }
        Console.WriteLine($"\tDashboard {dashboardName} was created.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List dashboards.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDashboards()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. List the CloudWatch dashboards in the current
account.");

        var dashboards = await _cloudWatchWrapper.ListDashboards();

        for (int i = 0; i < dashboards.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {dashboards[i].DashboardName}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create and add data for a new custom metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateNewCustomMetric()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Create and add data for a new custom metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var customData = await PutRandomMetricData(customMetricName,
customMetricNamespace);

        var valuesString = string.Join(',', customData.Select(d => d.Value));
```

```
        Console.WriteLine($"\tAdded metric values for for metric {customMetricName}:
\n\t{valuesString}");

        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// Add some metric data using a call to a wrapper class.
    /// </summary>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <returns></returns>
    private static async Task<List<MetricDatum>> PutRandomMetricData(string
customMetricName,
        string customMetricNamespace)
    {
        List<MetricDatum> customData = new List<MetricDatum>();
        Random rnd = new Random();

        // Add 10 random values up to 100, starting with a timestamp 15 minutes in
the past.
        var utcNowMinus15 = DateTime.UtcNow.AddMinutes(-15);
        for (int i = 0; i < 10; i++)
        {
            var metricValue = rnd.Next(0, 100);
            customData.Add(
                new MetricDatum
                {
                    MetricName = customMetricName,
                    Value = metricValue,
                    TimestampUtc = utcNowMinus15.AddMinutes(i)
                }
            );
        }

        await _cloudWatchWrapper.PutMetricData(customMetricNamespace, customData);
        return customData;
    }

    /// <summary>
    /// Add the custom metric to the dashboard.
    /// </summary>
    /// <returns>Async task.</returns>
```

```
    private static async Task AddMetricToDashboard()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. Add the new custom metric to the dashboard.");

        var dashboardName = _configuration["dashboardName"];

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var validationMessages = await SetupDashboard(customMetricNamespace,
customMetricName, dashboardName);

        Console.WriteLine(validationMessages.Any() ? $"\tValidation messages:" :
null);
        for (int i = 0; i < validationMessages.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {validationMessages[i].Message}");
        }
        Console.WriteLine($"\tDashboard {dashboardName} updated with metric
{customMetricName}.");
        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// Set up a dashboard using a call to the wrapper class.
    /// </summary>
    /// <param name="customMetricNamespace">The metric namespace.</param>
    /// <param name="customMetricName">The metric name.</param>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A list of validation messages.</returns>
    private static async Task<List<DashboardValidationMessage>> SetupDashboard(
        string customMetricNamespace, string customMetricName, string dashboardName)
    {
        // Get the dashboard model from configuration.
        var newDashboard = new DashboardModel();
        _configuration.GetSection("dashboardExampleBody").Bind(newDashboard);

        // Add a new metric to the dashboard.
        newDashboard.Widgets.Add(new Widget
        {
            Height = 8,
            Width = 8,
```

```
            Y = 8,
            X = 0,
            Type = "metric",
            Properties = new Properties
            {
                Metrics = new List<List<object>>
                    { new() { customMetricNamespace, customMetricName } },
                View = "timeSeries",
                Region = "us-east-1",
                Stat = "Sum",
                Period = 86400,
                YAxis = new YAxis { Left = new Left { Min = 0, Max = 100 } },
                Title = "Custom Metric Widget",
                LiveData = true,
                Sparkline = true,
                Trend = true,
                Stacked = false,
                SetPeriodToTimeRange = false
            }
        });

        var newDashboardString = JsonSerializer.Serialize(newDashboard,
            new JsonSerializerOptions
            { DefaultIgnoreCondition = JsonIgnoreCondition.WhenWritingNull });
        var validationMessages =
            await _cloudWatchWrapper.PutDashboard(dashboardName,
newDashboardString);

        return validationMessages;
    }

    /// <summary>
    /// Create a CloudWatch alarm for the new metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateMetricAlarm()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Create a CloudWatch alarm for the new metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var alarmName = _configuration["exampleAlarmName"];
```

```
        var accountId = _configuration["accountId"];
        var region = _configuration["region"];
        var emailTopic = _configuration["emailTopic"];
        var alarmActions = new List<string>();

        if (GetYesNoResponse(
                $"\tAdd an email action for topic {emailTopic} to alarm {alarmName}?
(y/n)"))
        {
            _cloudWatchWrapper.AddEmailAlarmAction(accountId, region, emailTopic,
alarmActions);
        }

        await _cloudWatchWrapper.PutMetricEmailAlarm(
            "Example metric alarm",
            alarmName,
            ComparisonOperator.GreaterThanOrEqualToThreshold,
            customMetricName,
            customMetricNamespace,
            100,
            alarmActions);

        Console.WriteLine($"\tAlarm {alarmName} added for metric
{customMetricName}.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Describe Alarms.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeAlarms()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Describe CloudWatch alarms in the current
account.");

        var alarms = await _cloudWatchWrapper.DescribeAlarms();
        alarms = alarms.OrderByDescending(a => a.StateUpdatedTimestamp).ToList();

        for (int i = 0; i < alarms.Count && i < 10; i++)
        {
            var alarm = alarms[i];
            Console.WriteLine($"\t{i + 1}. {alarm.AlarmName}");
```

```
            Console.WriteLine($"\tState: {alarm.StateValue} for {alarm.MetricName}
{alarm.ComparisonOperator} {alarm.Threshold}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get the recent data for the metric.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetCustomMetricData()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"11. Get current data for new custom metric.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var accountId = _configuration["accountId"];

        var query = new List<MetricDataQuery>
        {
            new MetricDataQuery
            {
                AccountId = accountId,
                Id = "m1",
                Label = "Custom Metric Data",
                MetricStat = new MetricStat
                {
                    Metric = new Metric
                    {
                        MetricName = customMetricName,
                        Namespace = customMetricNamespace,
                    },
                    Period = 1,
                    Stat = "Maximum"
                }
            }
        };

        var metricData = await _cloudWatchWrapper.GetMetricData(
            20,
            true,
            DateTime.UtcNow.AddMinutes(1),
```

```
            20,
            query);

        for (int i = 0; i < metricData.Count; i++)
        {
            for (int j = 0; j < metricData[i].Values.Count; j++)
            {
                Console.WriteLine(
                    $"\tTimestamp {metricData[i].Timestamps[j]:G} Value:
{metricData[i].Values[j]}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add metric data to trigger an alarm.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task AddMetricDataForAlarm()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"12. Add metric data to the custom metric to trigger an
alarm.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var nowUtc = DateTime.UtcNow;
        List<MetricDatum> customData = new List<MetricDatum>
        {
            new MetricDatum
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc.AddMinutes(-2)
            },
            new MetricDatum
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc.AddMinutes(-1)
            },
            new MetricDatum
```

```
            {
                MetricName = customMetricName,
                Value = 101,
                TimestampUtc = nowUtc
            }
        };
        var valuesString = string.Join(',', customData.Select(d => d.Value));
        Console.WriteLine($"\tAdded metric values for for metric {customMetricName}:
\n\t{valuesString}");
        await _cloudWatchWrapper.PutMetricData(customMetricNamespace, customData);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check for a metric alarm using the DescribeAlarmsForMetric action.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckForMetricAlarm()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"13. Checking for an alarm state.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];
        var hasAlarm = false;
        var retries = 10;
        while (!hasAlarm && retries > 0)
        {
            var alarms = await
_cloudWatchWrapper.DescribeAlarmsForMetric(customMetricNamespace,
customMetricName);
            hasAlarm = alarms.Any(a => a.StateValue == StateValue.ALARM);
            retries--;
            Thread.Sleep(20000);
        }

        Console.WriteLine(hasAlarm
            ? $"\tAlarm state found for {customMetricName}."
            : $"\tNo Alarm state found for {customMetricName} after 10 retries.");

        Console.WriteLine(new string('-', 80));
    }
```

```
    /// <summary>
    /// Get history for an alarm.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetAlarmHistory()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"14. Get alarm history.");

        var exampleAlarmName = _configuration["exampleAlarmName"];

        var alarmHistory = await
_cloudWatchWrapper.DescribeAlarmHistory(exampleAlarmName, 2);

        for (int i = 0; i < alarmHistory.Count; i++)
        {
            var history = alarmHistory[i];
            Console.WriteLine($"\t{i + 1}. {history.HistorySummary}, time
{history.Timestamp:g}");
        }
        if (!alarmHistory.Any())
        {
            Console.WriteLine($"\tNo alarm history data found for
{exampleAlarmName}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add an anomaly detector.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<SingleMetricAnomalyDetector> AddAnomalyDetector()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"15. Add an anomaly detector.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var detector = new SingleMetricAnomalyDetector
        {
            MetricName = customMetricName,
```

```
            Namespace = customMetricNamespace,
            Stat = "Maximum"
        };
        await _cloudWatchWrapper.PutAnomalyDetector(detector);
        Console.WriteLine($"\tAdded anomaly detector for metric
{customMetricName}.");

        Console.WriteLine(new string('-', 80));
        return detector;
    }

    /// <summary>
    /// Describe anomaly detectors.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeAnomalyDetectors()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"16. Describe anomaly detectors in the current
account.");

        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var detectors = await
_cloudWatchWrapper.DescribeAnomalyDetectors(customMetricNamespace,
customMetricName);

        for (int i = 0; i < detectors.Count; i++)
        {
            var detector = detectors[i];
            Console.WriteLine($"\t{i + 1}.
{detector.SingleMetricAnomalyDetector.MetricName}, state {detector.StateValue}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Fetch and open a metrics image for a CloudWatch metric and namespace.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetAndOpenMetricImage()
    {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("17. Get a metric image from CloudWatch.");

        Console.WriteLine($"\tGetting Image data for custom metric.");
        var customMetricNamespace = _configuration["customMetricNamespace"];
        var customMetricName = _configuration["customMetricName"];

        var memoryStream = await
_cloudWatchWrapper.GetTimeSeriesMetricImage(customMetricNamespace,
customMetricName, "Maximum", 10);
        var file = _cloudWatchWrapper.SaveMetricImage(memoryStream, "MetricImages");

        ProcessStartInfo info = new ProcessStartInfo();

        Console.WriteLine($"\tFile saved as {Path.GetFileName(file)}.");
        Console.WriteLine($"\tPress enter to open the image.");
        Console.ReadLine();
        info.FileName = Path.Combine("ms-photos://", file);
        info.UseShellExecute = true;
        info.CreateNoWindow = true;
        info.Verb = string.Empty;

        Process.Start(info);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up created resources.
    /// </summary>
    /// <param name="metricNamespace">The namespace for metrics.</param>
    /// <param name="metric">The CloudWatch metric.</param>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"18. Clean up resources.");

        var dashboardName = _configuration["dashboardName"];
        if (GetYesNoResponse($"\tDelete dashboard {dashboardName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting dashboard.");
            var dashboardList = new List<string> { dashboardName };
            await _cloudWatchWrapper.DeleteDashboards(dashboardList);
```

```
        }

        var alarmName = _configuration["exampleAlarmName"];
        if (GetYesNoResponse($"\tDelete alarm {alarmName}? (y/n)"))
        {
            Console.WriteLine($"\tCleaning up alarms.");
            var alarms = new List<string> { alarmName };
            await _cloudWatchWrapper.DeleteAlarms(alarms);
        }

        if (GetYesNoResponse($"\tDelete anomaly detector? (y/n)") &&
 anomalyDetector != null)
        {
            Console.WriteLine($"\tCleaning up anomaly detector.");

            await _cloudWatchWrapper.DeleteAnomalyDetector(
                anomalyDetector);
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

Métodos de embalagem usados pelo cenário para CloudWatch ações.

```
/// <summary>
/// Wrapper class for Amazon CloudWatch methods.
```

```
/// </summary>
public class CloudWatchWrapper
{
    private readonly IAmazonCloudWatch _amazonCloudWatch;
    private readonly ILogger<CloudWatchWrapper> _logger;

    /// <summary>
    /// Constructor for the CloudWatch wrapper.
    /// </summary>
    /// <param name="amazonCloudWatch">The injected CloudWatch client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public CloudWatchWrapper(IAmazonCloudWatch amazonCloudWatch,
 ILogger<CloudWatchWrapper> logger)

    {
        _logger = logger;
        _amazonCloudWatch = amazonCloudWatch;
    }

    /// <summary>
    /// List metrics available, optionally within a namespace.
    /// </summary>
    /// <param name="metricNamespace">Optional CloudWatch namespace to use when
 listing metrics.</param>
    /// <param name="filter">Optional dimension filter.</param>
    /// <param name="metricName">Optional metric name filter.</param>
    /// <returns>The list of metrics.</returns>
    public async Task<List<Metric>> ListMetrics(string? metricNamespace = null,
 DimensionFilter? filter = null, string? metricName = null)
    {
        var results = new List<Metric>();
        var paginateMetrics = _amazonCloudWatch.Paginators.ListMetrics(
            new ListMetricsRequest
            {
                Namespace = metricNamespace,
                Dimensions = filter != null ? new List<DimensionFilter> { filter } :
 null,
                MetricName = metricName
            });
        // Get the entire list using the paginator.
        await foreach (var metric in paginateMetrics.Metrics)
        {
            results.Add(metric);
        }
```

```
        return results;
    }

    /// <summary>
    /// Wrapper to get statistics for a specific CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <param name="statistics">The list of statistics to include.</param>
    /// <param name="dimensions">The list of dimensions to include.</param>
    /// <param name="days">The number of days in the past to include.</param>
    /// <param name="period">The period for the data.</param>
    /// <returns>A list of DataPoint objects for the statistics.</returns>
    public async Task<List<Datapoint>> GetMetricStatistics(string metricNamespace,
        string metricName, List<string> statistics, List<Dimension> dimensions, int
 days, int period)
    {
        var metricStatistics = await _amazonCloudWatch.GetMetricStatisticsAsync(
            new GetMetricStatisticsRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName,
                Dimensions = dimensions,
                Statistics = statistics,
                StartTimeUtc = DateTime.UtcNow.AddDays(-days),
                EndTimeUtc = DateTime.UtcNow,
                Period = period
            });

        return metricStatistics.Datapoints;
    }

    /// <summary>
    /// Wrapper to create or add to a dashboard with metrics.
    /// </summary>
    /// <param name="dashboardName">The name for the dashboard.</param>
    /// <param name="dashboardBody">The metric data in JSON for the dashboard.</
param>
    /// <returns>A list of validation messages for the dashboard.</returns>
    public async Task<List<DashboardValidationMessage>> PutDashboard(string
 dashboardName,
        string dashboardBody)
    {
```

```
        // Updating a dashboard replaces all contents.
        // Best practice is to include a text widget indicating this dashboard was
created programmatically.
        var dashboardResponse = await _amazonCloudWatch.PutDashboardAsync(
            new PutDashboardRequest()
            {
                DashboardName = dashboardName,
                DashboardBody = dashboardBody
            });

        return dashboardResponse.DashboardValidationMessages;
    }


    /// <summary>
    /// Get information on a dashboard.
    /// </summary>
    /// <param name="dashboardName">The name of the dashboard.</param>
    /// <returns>A JSON object with dashboard information.</returns>
    public async Task<string> GetDashboard(string dashboardName)
    {
        var dashboardResponse = await _amazonCloudWatch.GetDashboardAsync(
            new GetDashboardRequest()
            {
                DashboardName = dashboardName
            });

        return dashboardResponse.DashboardBody;
    }


    /// <summary>
    /// Get a list of dashboards.
    /// </summary>
    /// <returns>A list of DashboardEntry objects.</returns>
    public async Task<List<DashboardEntry>> ListDashboards()
    {
        var results = new List<DashboardEntry>();
        var paginateDashboards = _amazonCloudWatch.Paginators.ListDashboards(
            new ListDashboardsRequest());
        // Get the entire list using the paginator.
        await foreach (var data in paginateDashboards.DashboardEntries)
        {
            results.Add(data);
```

```
        }

        return results;
    }

    /// <summary>
    /// Wrapper to add metric data to a CloudWatch metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricData">A data object for the metric data.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricData(string metricNamespace,
        List<MetricDatum> metricData)
    {
        var putDataResponse = await _amazonCloudWatch.PutMetricDataAsync(
            new PutMetricDataRequest()
            {
                MetricData = metricData,
                Namespace = metricNamespace,
            });

        return putDataResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Get an image for a metric graphed over time.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metric">The name of the metric.</param>
    /// <param name="stat">The name of the stat to chart.</param>
    /// <param name="period">The period to use for the chart.</param>
    /// <returns>A memory stream for the chart image.</returns>
    public async Task<MemoryStream> GetTimeSeriesMetricImage(string metricNamespace,
string metric, string stat, int period)
    {
        var metricImageWidget = new
        {
            title = "Example Metric Graph",
            view = "timeSeries",
            stacked = false,
            period = period,
            width = 1400,
            height = 600,
            metrics = new List<List<object>>
```

```
                { new() { metricNamespace, metric, new { stat } } }
        };

        var metricImageWidgetString = JsonSerializer.Serialize(metricImageWidget);
        var imageResponse = await _amazonCloudWatch.GetMetricWidgetImageAsync(
            new GetMetricWidgetImageRequest()
            {
                MetricWidget = metricImageWidgetString
            });

        return imageResponse.MetricWidgetImage;
    }

    /// <summary>
    /// Save a metric image to a file.
    /// </summary>
    /// <param name="memoryStream">The MemoryStream for the metric image.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The path to the file.</returns>
    public string SaveMetricImage(MemoryStream memoryStream, string metricName)
    {
        var metricFileName = $"{metricName}_{DateTime.Now.Ticks}.png";
        using var sr = new StreamReader(memoryStream);
        // Writes the memory stream to a file.
        File.WriteAllBytes(metricFileName, memoryStream.ToArray());
        var filePath = Path.Join(AppDomain.CurrentDomain.BaseDirectory,
            metricFileName);
        return filePath;
    }

    /// <summary>
    /// Get data for CloudWatch metrics.
    /// </summary>
    /// <param name="minutesOfData">The number of minutes of data to include.</
param>
    /// <param name="useDescendingTime">True to return the data descending by
 time.</param>
    /// <param name="endDateUtc">The end date for the data, in UTC.</param>
    /// <param name="maxDataPoints">The maximum data points to include.</param>
    /// <param name="dataQueries">Optional data queries to include.</param>
    /// <returns>A list of the requested metric data.</returns>
    public async Task<List<MetricDataResult>> GetMetricData(int minutesOfData, bool
 useDescendingTime, DateTime? endDateUtc = null,
        int maxDataPoints = 0, List<MetricDataQuery>? dataQueries = null)
```

```
    {
        var metricData = new List<MetricDataResult>();
        // If no end time is provided, use the current time for the end time.
        endDateUtc ??= DateTime.UtcNow;
        var timeZoneOffset =
 TimeZoneInfo.Local.GetUtcOffset(endDateUtc.Value.ToLocalTime());
        var startTimeUtc = endDateUtc.Value.AddMinutes(-minutesOfData);
        // The timezone string should be in the format +0000, so use the timezone
 offset to format it correctly.
        var timeZoneString = $"{timeZoneOffset.Hours:D2}
{timeZoneOffset.Minutes:D2}";
        var paginatedMetricData = _amazonCloudWatch.Paginators.GetMetricData(
            new GetMetricDataRequest()
            {
                StartTimeUtc = startTimeUtc,
                EndTimeUtc = endDateUtc.Value,
                LabelOptions = new LabelOptions { Timezone = timeZoneString },
                ScanBy = useDescendingTime ? ScanBy.TimestampDescending :
 ScanBy.TimestampAscending,
                MaxDatapoints = maxDataPoints,
                MetricDataQueries = dataQueries,
            });

        await foreach (var data in paginatedMetricData.MetricDataResults)
        {
            metricData.Add(data);
        }
        return metricData;
    }

    /// <summary>
    /// Add a metric alarm to send an email when the metric passes a threshold.
    /// </summary>
    /// <param name="alarmDescription">A description of the alarm.</param>
    /// <param name="alarmName">The name for the alarm.</param>
    /// <param name="comparison">The type of comparison to use.</param>
    /// <param name="metricName">The name of the metric for the alarm.</param>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="threshold">The threshold value for the alarm.</param>
    /// <param name="alarmActions">Optional actions to execute when in an alarm
 state.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutMetricEmailAlarm(string alarmDescription, string
 alarmName, ComparisonOperator comparison,
```

```
        string metricName, string metricNamespace, double threshold, List<string>
alarmActions = null!)
    {
        try
        {
            var putEmailAlarmResponse = await _amazonCloudWatch.PutMetricAlarmAsync(
                new PutMetricAlarmRequest()
                {
                    AlarmActions = alarmActions,
                    AlarmDescription = alarmDescription,
                    AlarmName = alarmName,
                    ComparisonOperator = comparison,
                    Threshold = threshold,
                    Namespace = metricNamespace,
                    MetricName = metricName,
                    EvaluationPeriods = 1,
                    Period = 10,
                    Statistic = new Statistic("Maximum"),
                    DatapointsToAlarm = 1,
                    TreatMissingData = "ignore"
                });
            return putEmailAlarmResponse.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (LimitExceededException lex)
        {
            _logger.LogError(lex, $"Unable to add alarm {alarmName}. Alarm quota has
already been reached.");
        }

        return false;
    }

    /// <summary>
    /// Add specific email actions to a list of action strings for a CloudWatch
alarm.
    /// </summary>
    /// <param name="accountId">The AccountId for the alarm.</param>
    /// <param name="region">The region for the alarm.</param>
    /// <param name="emailTopicName">An Amazon Simple Notification Service (SNS)
topic for the alarm email.</param>
    /// <param name="alarmActions">Optional list of existing alarm actions to append
to.</param>
    /// <returns>A list of string actions for an alarm.</returns>
    public List<string> AddEmailAlarmAction(string accountId, string region,
```

```
        string emailTopicName, List<string>? alarmActions = null)
    {
        alarmActions ??= new List<string>();
        var snsAlarmAction = $"arn:aws:sns:{region}:{accountId}:{emailTopicName}";
        alarmActions.Add(snsAlarmAction);
        return alarmActions;
    }

    /// <summary>
    /// Describe the current alarms, optionally filtered by state.
    /// </summary>
    /// <param name="stateValue">Optional filter for alarm state.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarms(StateValue? stateValue =
null)
    {
        List<MetricAlarm> alarms = new List<MetricAlarm>();
        var paginatedDescribeAlarms = _amazonCloudWatch.Paginators.DescribeAlarms(
            new DescribeAlarmsRequest()
            {
                StateValue = stateValue
            });

        await foreach (var data in paginatedDescribeAlarms.MetricAlarms)
        {
            alarms.Add(data);
        }
        return alarms;
    }

    /// <summary>
    /// Describe the current alarms for a specific metric.
    /// </summary>
    /// <param name="metricNamespace">The namespace of the metric.</param>
    /// <param name="metricName">The name of the metric.</param>
    /// <returns>The list of alarm data.</returns>
    public async Task<List<MetricAlarm>> DescribeAlarmsForMetric(string
metricNamespace, string metricName)
    {
        var alarmsResult = await _amazonCloudWatch.DescribeAlarmsForMetricAsync(
            new DescribeAlarmsForMetricRequest()
            {
                Namespace = metricNamespace,
                MetricName = metricName
```

```
            });

        return alarmsResult.MetricAlarms;
    }

    /// <summary>
    /// Describe the history of an alarm for a number of days in the past.
    /// </summary>
    /// <param name="alarmName">The name of the alarm.</param>
    /// <param name="historyDays">The number of days in the past.</param>
    /// <returns>The list of alarm history data.</returns>
    public async Task<List<AlarmHistoryItem>> DescribeAlarmHistory(string alarmName,
int historyDays)
    {
        List<AlarmHistoryItem> alarmHistory = new List<AlarmHistoryItem>();
        var paginatedAlarmHistory =
_amazonCloudWatch.Paginators.DescribeAlarmHistory(
            new DescribeAlarmHistoryRequest()
            {
                AlarmName = alarmName,
                EndDateUtc = DateTime.UtcNow,
                HistoryItemType = HistoryItemType.StateUpdate,
                StartDateUtc = DateTime.UtcNow.AddDays(-historyDays)
            });

        await foreach (var data in paginatedAlarmHistory.AlarmHistoryItems)
        {
            alarmHistory.Add(data);
        }
        return alarmHistory;
    }

    /// <summary>
    /// Delete a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAlarms(List<string> alarmNames)
    {
        var deleteAlarmsResult = await _amazonCloudWatch.DeleteAlarmsAsync(
            new DeleteAlarmsRequest()
            {
                AlarmNames = alarmNames
            });
```

```
        return deleteAlarmsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Disable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DisableAlarmActions(List<string> alarmNames)
    {
        var disableAlarmActionsResult = await
_amazonCloudWatch.DisableAlarmActionsAsync(
            new DisableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return disableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Enable the actions for a list of alarms from CloudWatch.
    /// </summary>
    /// <param name="alarmNames">A list of names of alarms.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableAlarmActions(List<string> alarmNames)
    {
        var enableAlarmActionsResult = await
_amazonCloudWatch.EnableAlarmActionsAsync(
            new EnableAlarmActionsRequest()
            {
                AlarmNames = alarmNames
            });

        return enableAlarmActionsResult.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Add an anomaly detector for a single metric.
    /// </summary>
    /// <param name="anomalyDetector">A single metric anomaly detector.</param>
    /// <returns>True if successful.</returns>
```

```
   public async Task<bool> PutAnomalyDetector(SingleMetricAnomalyDetector
anomalyDetector)
   {
       var putAlarmDetectorResult = await
_amazonCloudWatch.PutAnomalyDetectorAsync(
           new PutAnomalyDetectorRequest()
           {
               SingleMetricAnomalyDetector = anomalyDetector
           });

       return putAlarmDetectorResult.HttpStatusCode == HttpStatusCode.OK;
   }

   /// <summary>
   /// Describe anomaly detectors for a metric and namespace.
   /// </summary>
   /// <param name="metricNamespace">The namespace of the metric.</param>
   /// <param name="metricName">The metric of the anomaly detectors.</param>
   /// <returns>The list of detectors.</returns>
   public async Task<List<AnomalyDetector>> DescribeAnomalyDetectors(string
metricNamespace, string metricName)
   {
       List<AnomalyDetector> detectors = new List<AnomalyDetector>();
       var paginatedDescribeAnomalyDetectors =
_amazonCloudWatch.Paginators.DescribeAnomalyDetectors(
           new DescribeAnomalyDetectorsRequest()
           {
               MetricName = metricName,
               Namespace = metricNamespace
           });

       await foreach (var data in
paginatedDescribeAnomalyDetectors.AnomalyDetectors)
       {
           detectors.Add(data);
       }

       return detectors;
   }

   /// <summary>
   /// Delete a single metric anomaly detector.
   /// </summary>
   /// <param name="anomalyDetector">The anomaly detector to delete.</param>
```

```
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteAnomalyDetector(SingleMetricAnomalyDetector
 anomalyDetector)
    {
        var deleteAnomalyDetectorResponse = await
 _amazonCloudWatch.DeleteAnomalyDetectorAsync(
            new DeleteAnomalyDetectorRequest()
            {
                SingleMetricAnomalyDetector = anomalyDetector
            });

        return deleteAnomalyDetectorResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete a list of CloudWatch dashboards.
    /// </summary>
    /// <param name="dashboardNames">List of dashboard names to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDashboards(List<string> dashboardNames)
    {
        var deleteDashboardsResponse = await
 _amazonCloudWatch.DeleteDashboardsAsync(
            new DeleteDashboardsRequest()
            {
                DashboardNames = dashboardNames
            });

        return deleteDashboardsResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric

- DescribeAnomalyDetectors
- GetMetricData
- GetMetricStatistics
- GetMetricWidgetImage
- ListMetrics
- PutAnomalyDetector
- PutDashboard
- PutMetricAlarm
- PutMetricData

CloudWatch Exemplos de registros usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET with CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Associar uma chave a um grupo de logs

O exemplo de código a seguir mostra como associar uma AWS KMS chave a um grupo de CloudWatch registros de registros existente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.CloudWatchLogs;
    using Amazon.CloudWatchLogs.Model;

    /// <summary>
    /// Shows how to associate an AWS Key Management Service (AWS KMS) key with
    /// an Amazon CloudWatch Logs log group.
    /// </summary>
    public class AssociateKmsKey
    {
        public static async Task Main()
        {
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();

            string kmsKeyId = "arn:aws:kms:us-west-2:<account-
number>:key/7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";
            string groupName = "cloudwatchlogs-example-loggroup";

            var request = new AssociateKmsKeyRequest
            {
                KmsKeyId = kmsKeyId,
                LogGroupName = groupName,
            };

            var response = await client.AssociateKmsKeyAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
```

```
                Console.WriteLine($"Successfully associated KMS key ID: {kmsKeyId}
with log group: {groupName}.");
            }
            else
            {
                Console.WriteLine("Could not make the association between:
{kmsKeyId} and {groupName}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte AssociateKmsKeya Referência AWS SDK for .NET da API.

Cancelar uma tarefa de exportação

O exemplo de código a seguir mostra como cancelar uma tarefa existente de exportação de CloudWatch registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to cancel an Amazon CloudWatch Logs export task.
/// </summary>
public class CancelExportTask
{
    public static async Task Main()
    {
```

```
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();
            string taskId = "exampleTaskId";

            var request = new CancelExportTaskRequest
            {
                TaskId = taskId,
            };

            var response = await client.CancelExportTaskAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{taskId} successfully canceled.");
            }
            else
            {
                Console.WriteLine($"{taskId} could not be canceled.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CancelExportTaska Referência AWS SDK for .NET da API.

Criar um grupo de logs

O exemplo de código a seguir mostra como criar um novo grupo de CloudWatch registros de registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to create an Amazon CloudWatch Logs log group.
/// </summary>
public class CreateLogGroup
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();

        string logGroupName = "cloudwatchlogs-example-loggroup";

        var request = new CreateLogGroupRequest
        {
            LogGroupName = logGroupName,
        };

        var response = await client.CreateLogGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"Successfully create log group with ID:
{logGroupName}.");
        }
        else
        {
            Console.WriteLine("Could not create log group.");
        }
    }
}
```

- Para obter detalhes da API, consulte CreateLogGroupa Referência AWS SDK for .NET da API.

Criar uma nova transmissão de logs

O exemplo de código a seguir mostra como criar um novo stream de CloudWatch registros de registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to create an Amazon CloudWatch Logs stream for a CloudWatch
/// log group.
/// </summary>
public class CreateLogStream
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();
        string logGroupName = "cloudwatchlogs-example-loggroup";
        string logStreamName = "cloudwatchlogs-example-logstream";

        var request = new CreateLogStreamRequest
        {
            LogGroupName = logGroupName,
            LogStreamName = logStreamName,
        };

        var response = await client.CreateLogStreamAsync(request);
```

```
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{logStreamName} successfully created for
{logGroupName}.");
            }
            else
            {
                Console.WriteLine("Could not create stream.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateLogStreama Referência AWS SDK for .NET da API.

Criar uma tarefa de exportação

O exemplo de código a seguir mostra como criar uma nova tarefa de exportação de CloudWatch registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.CloudWatchLogs;
    using Amazon.CloudWatchLogs.Model;

    /// <summary>
    /// Shows how to create an Export Task to export the contents of the Amazon
    /// CloudWatch Logs to the specified Amazon Simple Storage Service (Amazon S3)
    /// bucket.
    /// </summary>
    public class CreateExportTask
```

```
    {
        public static async Task Main()
        {
            // This client object will be associated with the same AWS Region
            // as the default user on this system. If you need to use a
            // different AWS Region, pass it as a parameter to the client
            // constructor.
            var client = new AmazonCloudWatchLogsClient();
            string taskName = "export-task-example";
            string logGroupName = "cloudwatchlogs-example-loggroup";
            string destination = "doc-example-bucket";
            var fromTime = 1437584472382;
            var toTime = 1437584472833;

            var request = new CreateExportTaskRequest
            {
                From = fromTime,
                To = toTime,
                TaskName = taskName,
                LogGroupName = logGroupName,
                Destination = destination,
            };

            var response = await client.CreateExportTaskAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"The task, {taskName} with ID: " +
                                  $"{response.TaskId} has been created
successfully.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateExportTaska Referência AWS SDK for .NET da API.

Excluir o grupo de logs.

O exemplo de código a seguir mostra como excluir um grupo de CloudWatch registros de registros existente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Uses the Amazon CloudWatch Logs Service to delete an existing
/// CloudWatch Logs log group.
/// </summary>
public class DeleteLogGroup
{
    public static async Task Main()
    {
        var client = new AmazonCloudWatchLogsClient();
        string logGroupName = "cloudwatchlogs-example-loggroup";

        var request = new DeleteLogGroupRequest
        {
            LogGroupName = logGroupName,
        };

        var response = await client.DeleteLogGroupAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"Successfully deleted CloudWatch log group,
{logGroupName}.");
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteLogGroupa Referência AWS SDK for .NET da API.

Descrever tarefas de exportação

O exemplo de código a seguir mostra como descrever CloudWatch as tarefas de exportação de registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Shows how to retrieve a list of information about Amazon CloudWatch
/// Logs export tasks.
/// </summary>
public class DescribeExportTasks
{
    public static async Task Main()
    {
        // This client object will be associated with the same AWS Region
        // as the default user on this system. If you need to use a
        // different AWS Region, pass it as a parameter to the client
        // constructor.
        var client = new AmazonCloudWatchLogsClient();

        var request = new DescribeExportTasksRequest
        {
            Limit = 5,
        };

        var response = new DescribeExportTasksResponse();

        do
        {
            response = await client.DescribeExportTasksAsync(request);
```

```
                response.ExportTasks.ForEach(t =>
                {
                    Console.WriteLine($"{t.TaskName} with ID: {t.TaskId} has status:
{t.Status}");
                });
            }
            while (response.NextToken is not null);
        }
    }
```

- Para obter detalhes da API, consulte DescribeExportTasksa Referência AWS SDK for .NET da API.

Descrever grupos de logs

O exemplo de código a seguir mostra como descrever grupos de CloudWatch registros de registros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;

/// <summary>
/// Retrieves information about existing Amazon CloudWatch Logs log groups
/// and displays the information on the console.
/// </summary>
public class DescribeLogGroups
{
    public static async Task Main()
    {
        // Creates a CloudWatch Logs client using the default
        // user. If you need to work with resources in another
```

```
            // AWS Region than the one defined for the default user,
            // pass the AWS Region as a parameter to the client constructor.
            var client = new AmazonCloudWatchLogsClient();

            bool done = false;
            string newToken = null;

            var request = new DescribeLogGroupsRequest
            {
                Limit = 5,
            };

            DescribeLogGroupsResponse response;

            do
            {
                if (newToken is not null)
                {
                    request.NextToken = newToken;
                }

                response = await client.DescribeLogGroupsAsync(request);

                response.LogGroups.ForEach(lg =>
                {
                    Console.WriteLine($"{lg.LogGroupName} is associated with the
key: {lg.KmsKeyId}.");
                    Console.WriteLine($"Created on: {lg.CreationTime.Date.Date}");
                    Console.WriteLine($"Date for this group will be stored for:
{lg.RetentionInDays} days.\n");
                });

                if (response.NextToken is null)
                {
                    done = true;
                }
                else
                {
                    newToken = response.NextToken;
                }
            }
            while (!done);
        }
    }
```

- Para obter detalhes da API, consulte DescribeLogGroupsa Referência AWS SDK for .NET da API.

Iniciar uma sessão Live Tail

O código de exemplo a seguir mostra como começar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

AWS SDK for .NET

Inclua os arquivos necessários.

```
using Amazon;
using Amazon.CloudWatchLogs;
using Amazon.CloudWatchLogs.Model;
```

Inicie a sessão do Live Tail.

```
            var client = new AmazonCloudWatchLogsClient();
            var request = new StartLiveTailRequest
            {
                LogGroupIdentifiers = logGroupIdentifiers,
                LogStreamNames = logStreamNames,
                LogEventFilterPattern = filterPattern,
            };

            var response = await client.StartLiveTailAsync(request);

            // Catch if request fails
            if (response.HttpStatusCode != System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine("Failed to start live tail session");
                return;
            }
```

Você pode lidar com os eventos da sessão do Live Tail de duas maneiras:

```
            /* Method 1
            * 1). Asynchronously loop through the event stream
            * 2). Set a timer to dispose the stream and stop the Live Tail session
at the end.
            */
            var eventStream = response.ResponseStream;
            var task = Task.Run(() =>
            {
                foreach (var item in eventStream)
                {
                    if (item is LiveTailSessionUpdate liveTailSessionUpdate)
                    {
                        foreach (var sessionResult in
liveTailSessionUpdate.SessionResults)
                        {
                            Console.WriteLine("Message : {0}",
sessionResult.Message);
                        }
                    }
                    if (item is LiveTailSessionStart)
                    {
                        Console.WriteLine("Live Tail session started");
                    }
                    // On-stream exceptions are processed here
                    if (item is CloudWatchLogsEventStreamException)
                    {
                        Console.WriteLine($"ERROR: {item}");
                    }
                }
            });
            // Close the stream to stop the session after a timeout
            if (!task.Wait(TimeSpan.FromSeconds(10))){
                eventStream.Dispose();
                Console.WriteLine("End of line");
            }
```

```
            /* Method 2
            * 1). Add event handlers to each event variable
            * 2). Start processing the stream and wait for a timeout using
AutoResetEvent
            */
            AutoResetEvent endEvent = new AutoResetEvent(false);
```

```
            var eventStream = response.ResponseStream;
            using (eventStream) // automatically disposes the stream to stop the
session after execution finishes
            {
                eventStream.SessionStartReceived += (sender, e) =>
                {
                    Console.WriteLine("LiveTail session started");
                };
                eventStream.SessionUpdateReceived += (sender, e) =>
                {
                    foreach (LiveTailSessionLogEvent logEvent in
e.EventStreamEvent.SessionResults){
                        Console.WriteLine("Message: {0}", logEvent.Message);
                    }
                };
                // On-stream exceptions are captured here
                eventStream.ExceptionReceived += (sender, e) =>
                {
                    Console.WriteLine($"ERROR: {e.EventStreamException.Message}");
                };

                eventStream.StartProcessing();
                // Stream events for this amount of time.
                endEvent.WaitOne(TimeSpan.FromSeconds(10));
                Console.WriteLine("End of line");
            }
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for .NET da API.

Exemplos de provedor de identidade do Amazon Cognito usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Confirm that the user has signed up.
   /// </summary>
   /// <param name="clientId">The Id of this application.</param>
   /// <param name="code">The confirmation code sent to the user.</param>
   /// <param name="userName">The username.</param>
   /// <returns>True if successful.</returns>
   public async Task<bool> ConfirmSignupAsync(string clientId, string code, string
userName)
   {
       var signUpRequest = new ConfirmSignUpRequest
       {
           ClientId = clientId,
           ConfirmationCode = code,
           Username = userName,
       };

       var response = await _cognitoService.ConfirmSignUpAsync(signUpRequest);
       if (response.HttpStatusCode == HttpStatusCode.OK)
       {
```

```
            Console.WriteLine($"{userName} was confirmed");
            return true;
        }
        return false;
    }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for .NET da API.

Confirme um dispositivo MFA para rastreamento

O exemplo de código a seguir mostra como confirmar um dispositivo de MFA para rastreamento pelo Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiates and confirms tracking of the device.
    /// </summary>
    /// <param name="accessToken">The user's access token.</param>
    /// <param name="deviceKey">The key of the device from Amazon Cognito.</param>
    /// <param name="deviceName">The device name.</param>
    /// <returns></returns>
    public async Task<bool> ConfirmDeviceAsync(string accessToken, string deviceKey,
string deviceName)
    {
        var request = new ConfirmDeviceRequest
        {
            AccessToken = accessToken,
            DeviceKey = deviceKey,
            DeviceName = deviceName
        };

        var response = await _cognitoService.ConfirmDeviceAsync(request);
```

```
        return response.UserConfirmationNecessary;
    }
```

- Para obter detalhes da API, consulte ConfirmDevicea Referência AWS SDK for .NET da API.

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get an MFA token to authenticate the user with the authenticator.
    /// </summary>
    /// <param name="session">The session name.</param>
    /// <returns>The session name.</returns>
    public async Task<string> AssociateSoftwareTokenAsync(string session)
    {
        var softwareTokenRequest = new AssociateSoftwareTokenRequest
        {
            Session = session,
        };

        var tokenResponse = await
_cognitoService.AssociateSoftwareTokenAsync(softwareTokenRequest);
        var secretCode = tokenResponse.SecretCode;

        Console.WriteLine($"Use the following secret code to set up the
authenticator: {secretCode}");

        return tokenResponse.Session;
    }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for .NET da API.

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Get the specified user from an Amazon Cognito user pool with administrator
access.
   /// </summary>
   /// <param name="userName">The name of the user.</param>
   /// <param name="poolId">The Id of the Amazon Cognito user pool.</param>
   /// <returns>Async task.</returns>
   public async Task<UserStatusType> GetAdminUserAsync(string userName, string
poolId)
   {
       AdminGetUserRequest userRequest = new AdminGetUserRequest
       {
           Username = userName,
           UserPoolId = poolId,
       };

       var response = await _cognitoService.AdminGetUserAsync(userRequest);

       Console.WriteLine($"User status {response.UserStatus}");
       return response.UserStatus;
   }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for .NET da API.

Listar os grupos de usuários

O exemplo de código a seguir mostra como listar os grupos de usuários do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Amazon Cognito user pools for an account.
    /// </summary>
    /// <returns>A list of UserPoolDescriptionType objects.</returns>
    public async Task<List<UserPoolDescriptionType>> ListUserPoolsAsync()
    {
        var userPools = new List<UserPoolDescriptionType>();

        var userPoolsPaginator = _cognitoService.Paginators.ListUserPools(new
ListUserPoolsRequest());

        await foreach (var response in userPoolsPaginator.Responses)
        {
            userPools.AddRange(response.UserPools);
        }

        return userPools;
    }
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for .NET da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of users for the Amazon Cognito user pool.
/// </summary>
/// <param name="userPoolId">The user pool ID.</param>
/// <returns>A list of users.</returns>
public async Task<List<UserType>> ListUsersAsync(string userPoolId)
{
    var request = new ListUsersRequest
    {
        UserPoolId = userPoolId
    };

    var users = new List<UserType>();

    var usersPaginator = _cognitoService.Paginators.ListUsers(request);
    await foreach (var response in usersPaginator.Responses)
    {
        users.AddRange(response.Users);
    }

    return users;
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for .NET da API.

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Send a new confirmation code to a user.
    /// </summary>
    /// <param name="clientId">The Id of the client application.</param>
    /// <param name="userName">The username of user who will receive the code.</
param>
    /// <returns>The delivery details.</returns>
    public async Task<CodeDeliveryDetailsType> ResendConfirmationCodeAsync(string
 clientId, string userName)
    {
        var codeRequest = new ResendConfirmationCodeRequest
        {
            ClientId = clientId,
            Username = userName,
        };

        var response = await
 _cognitoService.ResendConfirmationCodeAsync(codeRequest);

        Console.WriteLine($"Method of delivery is
 {response.CodeDeliveryDetails.DeliveryMedium}");

        return response.CodeDeliveryDetails;
    }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for .NET da API.

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Respond to an admin authentication challenge.
/// </summary>
/// <param name="userName">The name of the user.</param>
/// <param name="clientId">The client ID.</param>
/// <param name="mfaCode">The multi-factor authentication code.</param>
/// <param name="session">The current application session.</param>
/// <param name="clientId">The user pool ID.</param>
/// <returns>The result of the authentication response.</returns>
public async Task<AuthenticationResultType> AdminRespondToAuthChallengeAsync(
    string userName,
    string clientId,
    string mfaCode,
    string session,
    string userPoolId)
{
    Console.WriteLine("SOFTWARE_TOKEN_MFA challenge is generated");

    var challengeResponses = new Dictionary<string, string>();
    challengeResponses.Add("USERNAME", userName);
    challengeResponses.Add("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

    var respondToAuthChallengeRequest = new AdminRespondToAuthChallengeRequest
    {
        ChallengeName = ChallengeNameType.SOFTWARE_TOKEN_MFA,
        ClientId = clientId,
        ChallengeResponses = challengeResponses,
        Session = session,
        UserPoolId = userPoolId,
```

```
        };

        var response = await
 _cognitoService.AdminRespondToAuthChallengeAsync(respondToAuthChallengeRequest);
        Console.WriteLine($"Response to Authentication
 {response.AuthenticationResult.TokenType}");
        return response.AuthenticationResult;
    }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for .NET da API.

Inscrever um usuário

O exemplo de código a seguir mostra como inscrever um usuário no Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Sign up a new user.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The username to use.</param>
    /// <param name="password">The user's password.</param>
    /// <param name="email">The email address of the user.</param>
    /// <returns>A Boolean value indicating whether the user was confirmed.</
returns>
    public async Task<bool> SignUpAsync(string clientId, string userName, string
 password, string email)
    {
        var userAttrs = new AttributeType
        {
            Name = "email",
            Value = email,
```

```
        };

        var userAttrsList = new List<AttributeType>();

        userAttrsList.Add(userAttrs);

        var signUpRequest = new SignUpRequest
        {
            UserAttributes = userAttrsList,
            Username = userName,
            ClientId = clientId,
            Password = password
        };

        var response = await _cognitoService.SignUpAsync(signUpRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for .NET da API.

Iniciar a autenticação

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate authorization.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The name of the user who is authenticating.</param>
    /// <param name="password">The password for the user who is authenticating.</
param>
    /// <returns>The response from the initiate auth request.</returns>
```

```
    public async Task<InitiateAuthResponse> InitiateAuthAsync(string clientId,
string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var authRequest = new InitiateAuthRequest

        {
            ClientId = clientId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.InitiateAuthAsync(authRequest);
        Console.WriteLine($"Result Challenge is : {response.ChallengeName}");

        return response;
    }
```

- Para obter detalhes da API, consulte InitiateAutha Referência AWS SDK for .NET da API.

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate an admin auth request.
    /// </summary>
    /// <param name="clientId">The client ID to use.</param>
    /// <param name="userPoolId">The ID of the user pool.</param>
```

```
    /// <param name="userName">The username to authenticate.</param>
    /// <param name="password">The user's password.</param>
    /// <returns>The session to use in challenge-response.</returns>
    public async Task<string> AdminInitiateAuthAsync(string clientId, string
 userPoolId, string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var request = new AdminInitiateAuthRequest
        {
            ClientId = clientId,
            UserPoolId = userPoolId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.AdminInitiateAuthAsync(request);
        return response.Session;
    }
```

- Para obter detalhes da API, consulte AdminInitiateAuth a Referência AWS SDK for .NET da API.

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Verify the TOTP and register for MFA.
    /// </summary>
    /// <param name="session">The name of the session.</param>
```

```
    /// <param name="code">The MFA code.</param>
    /// <returns>The status of the software token.</returns>
    public async Task<VerifySoftwareTokenResponseType>
VerifySoftwareTokenAsync(string session, string code)
    {
        var tokenRequest = new VerifySoftwareTokenRequest
        {
            UserCode = code,
            Session = session,
        };

        var verifyResponse = await
_cognitoService.VerifySoftwareTokenAsync(tokenRequest);

        return verifyResponse.Status;
    }
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for .NET da API.

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace CognitoBasics;

public class CognitoBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Cognito.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonCognitoIdentityProvider>()
            .AddTransient<CognitoWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<CognitoBasics>();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var cognitoWrapper = host.Services.GetRequiredService<CognitoWrapper>();

        Console.WriteLine(new string('-', 80));
        UiMethods.DisplayOverview();
        Console.WriteLine(new string('-', 80));

        // clientId - The app client Id value that you get from the AWS CDK script.
        var clientId = configuration["ClientId"]; // "*** REPLACE WITH CLIENT ID
 VALUE FROM CDK SCRIPT";

        // poolId - The pool Id that you get from the AWS CDK script.
```

```
        var poolId = configuration["PoolId"]!; // "*** REPLACE WITH POOL ID VALUE
FROM CDK SCRIPT";
        var userName = configuration["UserName"];
        var password = configuration["Password"];
        var email = configuration["Email"];

        // If the username wasn't set in the configuration file,
        // get it from the user now.
        if (userName is null)
        {
            do
            {
                Console.Write("Username: ");
                userName = Console.ReadLine();
            }
            while (string.IsNullOrEmpty(userName));
        }
        Console.WriteLine($"\nUsername: {userName}");

        // If the password wasn't set in the configuration file,
        // get it from the user now.
        if (password is null)
        {
            do
            {
                Console.Write("Password: ");
                password = Console.ReadLine();
            }
            while (string.IsNullOrEmpty(password));
        }

        // If the email address wasn't set in the configuration file,
        // get it from the user now.
        if (email is null)
        {
            do
            {
                Console.Write("Email: ");
                email = Console.ReadLine();
            } while (string.IsNullOrEmpty(email));
        }

        // Now sign up the user.
        Console.WriteLine($"\nSigning up {userName} with email address: {email}");
```

```
        await cognitoWrapper.SignUpAsync(clientId, userName, password, email);

        // Add the user to the user pool.
        Console.WriteLine($"Adding {userName} to the user pool");
        await cognitoWrapper.GetAdminUserAsync(userName, poolId);

        UiMethods.DisplayTitle("Get confirmation code");
        Console.WriteLine($"Conformation code sent to {userName}.");
        Console.Write("Would you like to send a new code? (Y/N) ");
        var answer = Console.ReadLine();

        if (answer!.ToLower() == "y")
        {
            await cognitoWrapper.ResendConfirmationCodeAsync(clientId, userName);
            Console.WriteLine("Sending a new confirmation code");
        }

        Console.Write("Enter confirmation code (from Email): ");
        var code = Console.ReadLine();

        await cognitoWrapper.ConfirmSignupAsync(clientId, code, userName);

        UiMethods.DisplayTitle("Checking status");
        Console.WriteLine($"Rechecking the status of {userName} in the user pool");
        await cognitoWrapper.GetAdminUserAsync(userName, poolId);

        Console.WriteLine($"Setting up authenticator for {userName} in the user
pool");
        var setupResponse = await cognitoWrapper.InitiateAuthAsync(clientId,
userName, password);

        var setupSession = await
cognitoWrapper.AssociateSoftwareTokenAsync(setupResponse.Session);
        Console.Write("Enter the 6-digit code displayed in Google Authenticator: ");
        var setupCode = Console.ReadLine();

        var setupResult = await
cognitoWrapper.VerifySoftwareTokenAsync(setupSession, setupCode);
        Console.WriteLine($"Setup status: {setupResult}");

        Console.WriteLine($"Now logging in {userName} in the user pool");
        var authSession = await cognitoWrapper.AdminInitiateAuthAsync(clientId,
poolId, userName, password);
```

```
        Console.Write("Enter a new 6-digit code displayed in Google Authenticator:
 ");
        var authCode = Console.ReadLine();

        var authResult = await
 cognitoWrapper.AdminRespondToAuthChallengeAsync(userName, clientId, authCode,
 authSession, poolId);
        Console.WriteLine($"Authenticated and received access token:
 {authResult.AccessToken}");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Cognito scenario is complete.");
        Console.WriteLine(new string('-', 80));
    }
}


using System.Net;

namespace CognitoActions;

/// <summary>
/// Methods to perform Amazon Cognito Identity Provider actions.
/// </summary>
public class CognitoWrapper
{
    private readonly IAmazonCognitoIdentityProvider _cognitoService;

    /// <summary>
    /// Constructor for the wrapper class containing Amazon Cognito actions.
    /// </summary>
    /// <param name="cognitoService">The Amazon Cognito client object.</param>
    public CognitoWrapper(IAmazonCognitoIdentityProvider cognitoService)
    {
        _cognitoService = cognitoService;
    }

    /// <summary>
    /// List the Amazon Cognito user pools for an account.
    /// </summary>
    /// <returns>A list of UserPoolDescriptionType objects.</returns>
    public async Task<List<UserPoolDescriptionType>> ListUserPoolsAsync()
    {
        var userPools = new List<UserPoolDescriptionType>();
```

```
        var userPoolsPaginator = _cognitoService.Paginators.ListUserPools(new
ListUserPoolsRequest());

        await foreach (var response in userPoolsPaginator.Responses)
        {
            userPools.AddRange(response.UserPools);
        }

        return userPools;
    }


    /// <summary>
    /// Get a list of users for the Amazon Cognito user pool.
    /// </summary>
    /// <param name="userPoolId">The user pool ID.</param>
    /// <returns>A list of users.</returns>
    public async Task<List<UserType>> ListUsersAsync(string userPoolId)
    {
        var request = new ListUsersRequest
        {
            UserPoolId = userPoolId
        };

        var users = new List<UserType>();

        var usersPaginator = _cognitoService.Paginators.ListUsers(request);
        await foreach (var response in usersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }


    /// <summary>
    /// Respond to an admin authentication challenge.
    /// </summary>
    /// <param name="userName">The name of the user.</param>
    /// <param name="clientId">The client ID.</param>
    /// <param name="mfaCode">The multi-factor authentication code.</param>
    /// <param name="session">The current application session.</param>
```

```
    /// <param name="clientId">The user pool ID.</param>
    /// <returns>The result of the authentication response.</returns>
    public async Task<AuthenticationResultType> AdminRespondToAuthChallengeAsync(
        string userName,
        string clientId,
        string mfaCode,
        string session,
        string userPoolId)
    {
        Console.WriteLine("SOFTWARE_TOKEN_MFA challenge is generated");

        var challengeResponses = new Dictionary<string, string>();
        challengeResponses.Add("USERNAME", userName);
        challengeResponses.Add("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

        var respondToAuthChallengeRequest = new AdminRespondToAuthChallengeRequest
        {
            ChallengeName = ChallengeNameType.SOFTWARE_TOKEN_MFA,
            ClientId = clientId,
            ChallengeResponses = challengeResponses,
            Session = session,
            UserPoolId = userPoolId,
        };

        var response = await
_cognitoService.AdminRespondToAuthChallengeAsync(respondToAuthChallengeRequest);
        Console.WriteLine($"Response to Authentication
{response.AuthenticationResult.TokenType}");
        return response.AuthenticationResult;
    }


    /// <summary>
    /// Verify the TOTP and register for MFA.
    /// </summary>
    /// <param name="session">The name of the session.</param>
    /// <param name="code">The MFA code.</param>
    /// <returns>The status of the software token.</returns>
    public async Task<VerifySoftwareTokenResponseType>
VerifySoftwareTokenAsync(string session, string code)
    {
        var tokenRequest = new VerifySoftwareTokenRequest
        {
            UserCode = code,
```

```
            Session = session,
        };

        var verifyResponse = await
_cognitoService.VerifySoftwareTokenAsync(tokenRequest);

        return verifyResponse.Status;
    }


    /// <summary>
    /// Get an MFA token to authenticate the user with the authenticator.
    /// </summary>
    /// <param name="session">The session name.</param>
    /// <returns>The session name.</returns>
    public async Task<string> AssociateSoftwareTokenAsync(string session)
    {
        var softwareTokenRequest = new AssociateSoftwareTokenRequest
        {
            Session = session,
        };

        var tokenResponse = await
_cognitoService.AssociateSoftwareTokenAsync(softwareTokenRequest);
        var secretCode = tokenResponse.SecretCode;

        Console.WriteLine($"Use the following secret code to set up the
authenticator: {secretCode}");

        return tokenResponse.Session;
    }


    /// <summary>
    /// Initiate an admin auth request.
    /// </summary>
    /// <param name="clientId">The client ID to use.</param>
    /// <param name="userPoolId">The ID of the user pool.</param>
    /// <param name="userName">The username to authenticate.</param>
    /// <param name="password">The user's password.</param>
    /// <returns>The session to use in challenge-response.</returns>
    public async Task<string> AdminInitiateAuthAsync(string clientId, string
userPoolId, string userName, string password)
    {
```

```
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var request = new AdminInitiateAuthRequest
        {
            ClientId = clientId,
            UserPoolId = userPoolId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.AdminInitiateAuthAsync(request);
        return response.Session;
    }

    /// <summary>
    /// Initiate authorization.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The name of the user who is authenticating.</param>
    /// <param name="password">The password for the user who is authenticating.</
param>
    /// <returns>The response from the initiate auth request.</returns>
    public async Task<InitiateAuthResponse> InitiateAuthAsync(string clientId,
 string userName, string password)
    {
        var authParameters = new Dictionary<string, string>();
        authParameters.Add("USERNAME", userName);
        authParameters.Add("PASSWORD", password);

        var authRequest = new InitiateAuthRequest

        {
            ClientId = clientId,
            AuthParameters = authParameters,
            AuthFlow = AuthFlowType.USER_PASSWORD_AUTH,
        };

        var response = await _cognitoService.InitiateAuthAsync(authRequest);
        Console.WriteLine($"Result Challenge is : {response.ChallengeName}");

        return response;
    }
```

```
    /// <summary>
    /// Confirm that the user has signed up.
    /// </summary>
    /// <param name="clientId">The Id of this application.</param>
    /// <param name="code">The confirmation code sent to the user.</param>
    /// <param name="userName">The username.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> ConfirmSignupAsync(string clientId, string code, string
userName)
    {
        var signUpRequest = new ConfirmSignUpRequest
        {
            ClientId = clientId,
            ConfirmationCode = code,
            Username = userName,
        };

        var response = await _cognitoService.ConfirmSignUpAsync(signUpRequest);
        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            Console.WriteLine($"{userName} was confirmed");
            return true;
        }
        return false;
    }


    /// <summary>
    /// Initiates and confirms tracking of the device.
    /// </summary>
    /// <param name="accessToken">The user's access token.</param>
    /// <param name="deviceKey">The key of the device from Amazon Cognito.</param>
    /// <param name="deviceName">The device name.</param>
    /// <returns></returns>
    public async Task<bool> ConfirmDeviceAsync(string accessToken, string deviceKey,
string deviceName)
    {
        var request = new ConfirmDeviceRequest
        {
            AccessToken = accessToken,
            DeviceKey = deviceKey,
            DeviceName = deviceName
        };
```

```
        var response = await _cognitoService.ConfirmDeviceAsync(request);
        return response.UserConfirmationNecessary;
    }


    /// <summary>
    /// Send a new confirmation code to a user.
    /// </summary>
    /// <param name="clientId">The Id of the client application.</param>
    /// <param name="userName">The username of user who will receive the code.</
param>
    /// <returns>The delivery details.</returns>
    public async Task<CodeDeliveryDetailsType> ResendConfirmationCodeAsync(string
 clientId, string userName)
    {
        var codeRequest = new ResendConfirmationCodeRequest
        {
            ClientId = clientId,
            Username = userName,
        };

        var response = await
 _cognitoService.ResendConfirmationCodeAsync(codeRequest);

        Console.WriteLine($"Method of delivery is
 {response.CodeDeliveryDetails.DeliveryMedium}");

        return response.CodeDeliveryDetails;
    }


    /// <summary>
    /// Get the specified user from an Amazon Cognito user pool with administrator
 access.
    /// </summary>
    /// <param name="userName">The name of the user.</param>
    /// <param name="poolId">The Id of the Amazon Cognito user pool.</param>
    /// <returns>Async task.</returns>
    public async Task<UserStatusType> GetAdminUserAsync(string userName, string
 poolId)
    {
        AdminGetUserRequest userRequest = new AdminGetUserRequest
        {
```

```
            Username = userName,
            UserPoolId = poolId,
        };

        var response = await _cognitoService.AdminGetUserAsync(userRequest);

        Console.WriteLine($"User status {response.UserStatus}");
        return response.UserStatus;
    }


    /// <summary>
    /// Sign up a new user.
    /// </summary>
    /// <param name="clientId">The client Id of the application.</param>
    /// <param name="userName">The username to use.</param>
    /// <param name="password">The user's password.</param>
    /// <param name="email">The email address of the user.</param>
    /// <returns>A Boolean value indicating whether the user was confirmed.</
returns>
    public async Task<bool> SignUpAsync(string clientId, string userName, string
 password, string email)
    {
        var userAttrs = new AttributeType
        {
            Name = "email",
            Value = email,
        };

        var userAttrsList = new List<AttributeType>();

        userAttrsList.Add(userAttrs);

        var signUpRequest = new SignUpRequest
        {
            UserAttributes = userAttrsList,
            Username = userName,
            ClientId = clientId,
            Password = password
        };

        var response = await _cognitoService.SignUpAsync(signUpRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

```
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Exemplos do Amazon Comprehend usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Comprehend.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Detectar entidades em um documento

O exemplo de código a seguir mostra como detectar entidades em um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use the AmazonComprehend service detect any
/// entities in submitted text.
/// </summary>
public static class DetectEntities
{
    /// <summary>
    /// The main method calls the DetectEntitiesAsync method to find any
    /// entities in the sample code.
    /// </summary>
    public static async Task Main()
    {
        string text = "It is raining today in Seattle";

        var comprehendClient = new AmazonComprehendClient();

        Console.WriteLine("Calling DetectEntities\n");
        var detectEntitiesRequest = new DetectEntitiesRequest()
        {
```

```
                Text = text,
                LanguageCode = "en",
            };
            var detectEntitiesResponse = await
comprehendClient.DetectEntitiesAsync(detectEntitiesRequest);

            foreach (var e in detectEntitiesResponse.Entities)
            {
                Console.WriteLine($"Text: {e.Text}, Type: {e.Type}, Score:
{e.Score}, BeginOffset: {e.BeginOffset}, EndOffset: {e.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectEntiesa Referência AWS SDK for .NET da API.

Detectar frases-chave em um documento

O exemplo de código a seguir mostra como detectar frases-chave em um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Comprehend;
    using Amazon.Comprehend.Model;

    /// <summary>
    /// This example shows how to use the Amazon Comprehend service to
    /// search text for key phrases.
```

```
    /// </summary>
    public static class DetectKeyPhrase
    {
        /// <summary>
        /// This method calls the Amazon Comprehend method DetectKeyPhrasesAsync
        /// to detect any key phrases in the sample text.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            // Call DetectKeyPhrases API
            Console.WriteLine("Calling DetectKeyPhrases");
            var detectKeyPhrasesRequest = new DetectKeyPhrasesRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
            var detectKeyPhrasesResponse = await
comprehendClient.DetectKeyPhrasesAsync(detectKeyPhrasesRequest);
            foreach (var kp in detectKeyPhrasesResponse.KeyPhrases)
            {
                Console.WriteLine($"Text: {kp.Text}, Score: {kp.Score}, BeginOffset:
{kp.BeginOffset}, EndOffset: {kp.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectKeyPhrasesa Referência AWS SDK for .NET da API.

Detectar informações de identificação pessoal em um documento

O exemplo de código a seguir mostra como detectar informações de identificação pessoal (PII) em um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use the Amazon Comprehend service to find
/// personally identifiable information (PII) within text submitted to the
/// DetectPiiEntitiesAsync method.
/// </summary>
public class DetectingPII
{
    /// <summary>
    /// This method calls the DetectPiiEntitiesAsync method to locate any
    /// personally dientifiable information within the supplied text.
    /// </summary>
    public static async Task Main()
    {
        var comprehendClient = new AmazonComprehendClient();
        var text = @"Hello Paul Santos. The latest statement for your
                    credit card account 1111-0000-1111-0000 was
                    mailed to 123 Any Street, Seattle, WA 98109.";

        var request = new DetectPiiEntitiesRequest
        {
            Text = text,
            LanguageCode = "EN",
        };

        var response = await comprehendClient.DetectPiiEntitiesAsync(request);

        if (response.Entities.Count > 0)
        {
            foreach (var entity in response.Entities)
```

```
                {
                    var entityValue = text.Substring(entity.BeginOffset,
entity.EndOffset - entity.BeginOffset);
                    Console.WriteLine($"{entity.Type}: {entityValue}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectPiiEntiesa Referência AWS SDK for .NET da API.

Detectar elementos sintáticos de um documento

O exemplo de código a seguir mostra como detectar elementos sintáticos de um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Comprehend;
using Amazon.Comprehend.Model;

/// <summary>
/// This example shows how to use Amazon Comprehend to detect syntax
/// elements by calling the DetectSyntaxAsync method.
/// </summary>
public class DetectingSyntax
{
    /// <summary>
    /// This method calls DetectSynaxAsync to identify the syntax elements
    /// in the sample text.
    /// </summary>
    public static async Task Main()
```

```
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new AmazonComprehendClient();

            // Call DetectSyntax API
            Console.WriteLine("Calling DetectSyntaxAsync\n");
            var detectSyntaxRequest = new DetectSyntaxRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
            DetectSyntaxResponse detectSyntaxResponse = await
comprehendClient.DetectSyntaxAsync(detectSyntaxRequest);
            foreach (SyntaxToken s in detectSyntaxResponse.SyntaxTokens)
            {
                Console.WriteLine($"Text: {s.Text}, PartOfSpeech:
{s.PartOfSpeech.Tag}, BeginOffset: {s.BeginOffset}, EndOffset: {s.EndOffset}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectSyntaxa Referência AWS SDK for .NET da API.

Detectar o idioma dominante em um documento

O exemplo de código a seguir mostra como detectar a linguagem dominante em um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
```

```
    using System.Threading.Tasks;
    using Amazon.Comprehend;
    using Amazon.Comprehend.Model;

    /// <summary>
    /// This example calls the Amazon Comprehend service to determine the
    /// dominant language.
    /// </summary>
    public static class DetectDominantLanguage
    {
        /// <summary>
        /// Calls Amazon Comprehend to determine the dominant language used in
        /// the sample text.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle.";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            Console.WriteLine("Calling DetectDominantLanguage\n");
            var detectDominantLanguageRequest = new DetectDominantLanguageRequest()
            {
                Text = text,
            };

            var detectDominantLanguageResponse = await
comprehendClient.DetectDominantLanguageAsync(detectDominantLanguageRequest);
            foreach (var dl in detectDominantLanguageResponse.Languages)
            {
                Console.WriteLine($"Language Code: {dl.LanguageCode}, Score:
{dl.Score}");
            }

            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectDominantLanguagea Referência AWS SDK for .NET da API.

Detectar o sentimento de um documento

O exemplo de código a seguir mostra como detectar o sentimento em um documento com o Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Comprehend;
    using Amazon.Comprehend.Model;

    /// <summary>
    /// This example shows how to detect the overall sentiment of the supplied
    /// text using the Amazon Comprehend service.
    /// </summary>
    public static class DetectSentiment
    {
        /// <summary>
        /// This method calls the DetetectSentimentAsync method to analyze the
        /// supplied text and determine the overal sentiment.
        /// </summary>
        public static async Task Main()
        {
            string text = "It is raining today in Seattle";

            var comprehendClient = new
AmazonComprehendClient(Amazon.RegionEndpoint.USWest2);

            // Call DetectKeyPhrases API
            Console.WriteLine("Calling DetectSentiment");
            var detectSentimentRequest = new DetectSentimentRequest()
            {
                Text = text,
                LanguageCode = "en",
            };
```

```
            var detectSentimentResponse = await
comprehendClient.DetectSentimentAsync(detectSentimentRequest);
            Console.WriteLine($"Sentiment: {detectSentimentResponse.Sentiment}");
            Console.WriteLine("Done");
        }
    }
```

- Para obter detalhes da API, consulte DetectSentimenta Referência AWS SDK for .NET da API.

Iniciar um trabalho de modelagem de tópico

O exemplo de código a seguir mostra como iniciar uma tarefa de modelagem de tópicos do Amazon Comprehend.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Comprehend;
    using Amazon.Comprehend.Model;

    /// <summary>
    /// This example scans the documents in an Amazon Simple Storage Service
    /// (Amazon S3) bucket and analyzes it for topics. The results are stored
    /// in another bucket and then the resulting job properties are displayed
    /// on the screen. This example was created using the AWS SDK for .NEt
    /// version 3.7 and .NET Core version 5.0.
    /// </summary>
    public static class TopicModeling
    {
        /// <summary>
        /// This methos calls a topic detection job by calling the Amazon
        /// Comprehend StartTopicsDetectionJobRequest.
        /// </summary>
```

```
        public static async Task Main()
        {
            var comprehendClient = new AmazonComprehendClient();

            string inputS3Uri = "s3://input bucket/input path";
            InputFormat inputDocFormat = InputFormat.ONE_DOC_PER_FILE;
            string outputS3Uri = "s3://output bucket/output path";
            string dataAccessRoleArn = "arn:aws:iam::account ID:role/data access
role";
            int numberOfTopics = 10;

            var startTopicsDetectionJobRequest = new
StartTopicsDetectionJobRequest()
            {
                InputDataConfig = new InputDataConfig()
                {
                    S3Uri = inputS3Uri,
                    InputFormat = inputDocFormat,
                },
                OutputDataConfig = new OutputDataConfig()
                {
                    S3Uri = outputS3Uri,
                },
                DataAccessRoleArn = dataAccessRoleArn,
                NumberOfTopics = numberOfTopics,
            };

            var startTopicsDetectionJobResponse = await
comprehendClient.StartTopicsDetectionJobAsync(startTopicsDetectionJobRequest);

            var jobId = startTopicsDetectionJobResponse.JobId;
            Console.WriteLine("JobId: " + jobId);

            var describeTopicsDetectionJobRequest = new
DescribeTopicsDetectionJobRequest()
            {
                JobId = jobId,
            };

            var describeTopicsDetectionJobResponse = await
comprehendClient.DescribeTopicsDetectionJobAsync(describeTopicsDetectionJobRequest);

PrintJobProperties(describeTopicsDetectionJobResponse.TopicsDetectionJobProperties);
```

```
            var listTopicsDetectionJobsResponse = await
comprehendClient.ListTopicsDetectionJobsAsync(new
ListTopicsDetectionJobsRequest());
            foreach (var props in
listTopicsDetectionJobsResponse.TopicsDetectionJobPropertiesList)
            {
                PrintJobProperties(props);
            }
        }

        /// <summary>
        /// This method is a helper method that displays the job properties
        /// from the call to StartTopicsDetectionJobRequest.
        /// </summary>
        /// <param name="props">A list of properties from the call to
        /// StartTopicsDetectionJobRequest.</param>
        private static void PrintJobProperties(TopicsDetectionJobProperties props)
        {
            Console.WriteLine($"JobId: {props.JobId}, JobName: {props.JobName},
JobStatus: {props.JobStatus}");
            Console.WriteLine($"NumberOfTopics: {props.NumberOfTopics}\nInputS3Uri:
{props.InputDataConfig.S3Uri}");
            Console.WriteLine($"InputFormat: {props.InputDataConfig.InputFormat},
OutputS3Uri: {props.OutputDataConfig.S3Uri}");
        }
    }
```

- Para obter detalhes da API, consulte StartTopicsDetectionJoba Referência AWS SDK for .NET da API.

Exemplos do DynamoDB usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for .NET com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, DynamoDB

O exemplo de código a seguir mostra como começar a usar o DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;

namespace DynamoDB_Actions;

public static class HelloDynamoDB
{
    static async Task Main(string[] args)
    {
        var dynamoDbClient = new AmazonDynamoDBClient();

        Console.WriteLine($"Hello Amazon Dynamo DB! Following are some of your
 tables:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five tables.
        var response = await dynamoDbClient.ListTablesAsync(
            new ListTablesRequest()
            {
                Limit = 5
```

```
            });

        foreach (var table in response.TableNames)
        {
            Console.WriteLine($"\tTable: {table}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Creates a new Amazon DynamoDB table and then waits for the new
        /// table to become active.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="tableName">The name of the table to create.</param>
```

```
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
 client, string tableName)
        {
            var response = await client.CreateTableAsync(new CreateTableRequest
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                {
                    new AttributeDefinition
                    {
                        AttributeName = "title",
                        AttributeType = ScalarAttributeType.S,
                    },
                    new AttributeDefinition
                    {
                        AttributeName = "year",
                        AttributeType = ScalarAttributeType.N,
                    },
                },
                KeySchema = new List<KeySchemaElement>()
                {
                    new KeySchemaElement
                    {
                        AttributeName = "year",
                        KeyType = KeyType.HASH,
                    },
                    new KeySchemaElement
                    {
                        AttributeName = "title",
                        KeyType = KeyType.RANGE,
                    },
                },
                ProvisionedThroughput = new ProvisionedThroughput
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5,
                },
            });

            // Wait until the table is ACTIVE and then report success.
            Console.Write("Waiting for table to become active...");
```

```
            var request = new DescribeTableRequest
            {
                TableName = response.TableDescription.TableName,
            };

            TableStatus status;

            int sleepDuration = 2000;

            do
            {
                System.Threading.Thread.Sleep(sleepDuration);

                var describeTableResponse = await
client.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for .NET da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient client,
string tableName)
```

```
        {
            var request = new DeleteTableRequest
            {
                TableName = tableName,
            };

            var response = await client.DeleteTableAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Table {response.TableDescription.TableName}
successfully deleted.");
                return true;
            }
            else
            {
                Console.WriteLine("Could not delete table.");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Deletes a single item from a DynamoDB table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
```

```
        /// <param name="tableName">The name of the table from which the item
        /// will be deleted.</param>
        /// <param name="movieToDelete">A movie object containing the title and
        /// year of the movie to delete.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// delete operation.</returns>
        public static async Task<bool> DeleteItemAsync(
            AmazonDynamoDBClient client,
            string tableName,
            Movie movieToDelete)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = movieToDelete.Title },
                ["year"] = new AttributeValue { N = movieToDelete.Year.ToString() },
            };

            var request = new DeleteItemRequest
            {
                TableName = tableName,
                Key = key,
            };

            var response = await client.DeleteItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for .NET da API.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;

namespace LowLevelBatchGet
{
    public class LowLevelBatchGet
    {
        private static readonly string _table1Name = "Forum";
        private static readonly string _table2Name = "Thread";

        public static async void RetrieveMultipleItemsBatchGet(AmazonDynamoDBClient
 client)
        {
            var request = new BatchGetItemRequest
            {
                RequestItems = new Dictionary<string, KeysAndAttributes>()
            {
                { _table1Name,
                  new KeysAndAttributes
                  {
                      Keys = new List<Dictionary<string, AttributeValue> >()
                      {
                          new Dictionary<string, AttributeValue>()
                          {
                              { "Name", new AttributeValue {
                            S = "Amazon DynamoDB"
                        } }
                          },
                          new Dictionary<string, AttributeValue>()
                          {
                              { "Name", new AttributeValue {
                            S = "Amazon S3"
                        } }
                          }
                      }
                  }},
                {
                    _table2Name,
                    new KeysAndAttributes
                    {
                        Keys = new List<Dictionary<string, AttributeValue> >()
```

```
                        {
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue {
                                      S = "Amazon DynamoDB"
                                  } },
                                { "Subject", new AttributeValue {
                                      S = "DynamoDB Thread 1"
                                  } }
                            },
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue {
                                      S = "Amazon DynamoDB"
                                  } },
                                { "Subject", new AttributeValue {
                                      S = "DynamoDB Thread 2"
                                  } }
                            },
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue {
                                      S = "Amazon S3"
                                  } },
                                { "Subject", new AttributeValue {
                                      S = "S3 Thread 1"
                                  } }
                            }
                        }
                    }
                }
            }
            };

            BatchGetItemResponse response;
            do
            {
                Console.WriteLine("Making request");
                response = await client.BatchGetItemAsync(request);

                // Check the response.
                var responses = response.Responses; // Attribute list in the
response.
```

```
                foreach (var tableResponse in responses)
                {
                    var tableResults = tableResponse.Value;
                    Console.WriteLine("Items retrieved from table {0}",
tableResponse.Key);
                    foreach (var item1 in tableResults)
                    {
                        PrintItem(item1);
                    }
                }

                // Any unprocessed keys? could happen if you exceed
ProvisionedThroughput or some other error.
                Dictionary<string, KeysAndAttributes> unprocessedKeys =
response.UnprocessedKeys;
                foreach (var unprocessedTableKeys in unprocessedKeys)
                {
                    // Print table name.
                    Console.WriteLine(unprocessedTableKeys.Key);
                    // Print unprocessed primary keys.
                    foreach (var key in unprocessedTableKeys.Value.Keys)
                    {
                        PrintItem(key);
                    }
                }

                request.RequestItems = unprocessedKeys;
            } while (response.UnprocessedKeys.Count > 0);
        }

        private static void PrintItem(Dictionary<string, AttributeValue>
attributeList)
        {
            foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
            {
                string attributeName = kvp.Key;
                AttributeValue value = kvp.Value;

                Console.WriteLine(
                    attributeName + " " +
                    (value.S == null ? "" : "S=[" + value.S + "]") +
                    (value.N == null ? "" : "N=[" + value.N + "]") +
                    (value.SS == null ? "" : "SS=[" + string.Join(",",
value.SS.ToArray()) + "]") +
```

```
                    (value.NS == null ? "" : "NS=[" + string.Join(",",
 value.NS.ToArray()) + "]")
                    );
            }
            Console.WriteLine("************************************************");
        }

        static void Main()
        {
            var client = new AmazonDynamoDBClient();

            RetrieveMultipleItemsBatchGet(client);
        }
    }
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for .NET da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Gets information about an existing movie from the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information about
        /// the movie to retrieve.</param>
        /// <param name="tableName">The name of the table containing the movie.</
param>
```

```
        /// <returns>A Dictionary object containing information about the item
        /// retrieved.</returns>
        public static async Task<Dictionary<string, AttributeValue>>
GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new GetItemRequest
            {
                Key = key,
                TableName = tableName,
            };

            var response = await client.GetItemAsync(request);
            return response.Item;
        }
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for .NET da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    private static async Task GetTableInformation()
    {
        Console.WriteLine("\n*** Retrieving table information ***");
```

```
        var response = await Client.DescribeTableAsync(new DescribeTableRequest
        {
            TableName = ExampleTableName
        });

        var table = response.Table;
        Console.WriteLine($"Name: {table.TableName}");
        Console.WriteLine($"# of items: {table.ItemCount}");
        Console.WriteLine($"Provision Throughput (reads/sec): " +
                          $"{table.ProvisionedThroughput.ReadCapacityUnits}");
        Console.WriteLine($"Provision Throughput (writes/sec): " +
                          $"{table.ProvisionedThroughput.WriteCapacityUnits}");
    }
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for .NET da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    private static async Task ListMyTables()
    {
        Console.WriteLine("\n*** Listing tables ***");

        string lastTableNameEvaluated = null;
        do
        {
            var response = await Client.ListTablesAsync(new ListTablesRequest
            {
                Limit = 2,
                ExclusiveStartTableName = lastTableNameEvaluated
            });
```

```
            foreach (var name in response.TableNames)
            {
                Console.WriteLine(name);
            }

            lastTableNameEvaluated = response.LastEvaluatedTableName;
        } while (lastTableNameEvaluated != null);
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Adds a new item to the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing informtation for
        /// the movie to add to the table.</param>
        /// <param name="tableName">The name of the table where the item will be
 added.</param>
        /// <returns>A Boolean value that indicates the results of adding the
 item.</returns>
        public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
 Movie newMovie, string tableName)
        {
            var item = new Dictionary<string, AttributeValue>
```

```
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new PutItemRequest
            {
                TableName = tableName,
                Item = item,
            };

            var response = await client.PutItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for .NET da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        /// <summary>
        /// Queries the table for movies released in a particular year and
        /// then displays the information for the movies returned.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table to query.</param>
        /// <param name="year">The release year for which we want to
        /// view movies.</param>
        /// <returns>The number of movies that match the query.</returns>
```

```
        public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient client,
string tableName, int year)
        {
            var movieTable = Table.LoadTable(client, tableName);
            var filter = new QueryFilter("year", QueryOperator.Equal, year);

            Console.WriteLine("\nFind movies released in: {year}:");

            var config = new QueryOperationConfig()
            {
                Limit = 10, // 10 items per page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "title",
                  "year",
                },
                ConsistentRead = true,
                Filter = filter,
            };

            // Value used to track how many movies match the
            // supplied criteria.
            var moviesFound = 0;

            Search search = movieTable.Query(config);
            do
            {
                var movieList = await search.GetNextSetAsync();
                moviesFound += movieList.Count;

                foreach (var movie in movieList)
                {
                    DisplayDocument(movie);
                }
            }
            while (!search.IsDone);

            return moviesFound;
        }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for .NET.

Executar uma instrução PartiQL

O exemplo de código a seguir mostra como executar uma instrução PartiQL em uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
        /// <summary>
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use uma instrução SELECT para obter um item.

```
        /// <summary>
        /// Uses a PartiQL SELECT statement to retrieve a single movie from the
        /// movie database.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }
```

Use uma instrução SELECT para obter uma lista de itens.

```
        /// <summary>
        /// Retrieve multiple movies by year using a SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="year">The year the movies were released.</param>
```

```
        /// <returns></returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetMovies(string tableName, int year)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { N = year.ToString() },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }
```

Use uma instrução UPDATE para atualizar um item.

```
        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
        {
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
```

```
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use uma instrução DELETE para excluir um único filme.

```
        /// <summary>
        /// Deletes a single movie from the table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
```

```
        }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for .NET da API.

Executar lotes de instruções PartiQL

O exemplo de código a seguir mostra como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table into which the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
```

```
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
                                Parameters = new List<AttributeValue>
                                {
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
                            });
                        }

                        var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
                        {
                            Statements = statements,
                        });

                        // Wait between batches for movies to be successfully added.
                        System.Threading.Thread.Sleep(3000);

                        success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                        // Clear the list of statements for the next batch.
                        statements.Clear();
                    }
                }
                catch (AmazonDynamoDBException ex)
                {
                    Console.WriteLine(ex.Message);
```

```
            }
        }

        return success;
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the DynamoDB table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A generic list of movie objects.</returns>
    public static List<Movie> ImportMovies(string movieFileName)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();
        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

        if (allMovies is not null)
        {
            // Return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }
        else
        {
            return null!;
        }
    }
```

Use lotes de instruções SELECT para obter itens.

```
    /// <summary>
    /// Gets movies from the movie table by
    /// using an Amazon DynamoDB PartiQL SELECT statement.
    /// </summary>
    /// <param name="tableName">The name of the table.</param>
    /// <param name="title1">The title of the first movie.</param>
```

```
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year1">The year of the first movie.</param>
        /// <param name="year2">The year of the second movie.</param>
        /// <returns>True if successful.</returns>
        public static async Task<bool> GetBatch(
            string tableName,
            string title1,
            string title2,
            int year1,
            int year2)
        {
            var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            if (response.Responses.Count > 0)
            {
                response.Responses.ForEach(r =>
```

```
                {
                    Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
                });
                return true;
            }
            else
            {
                Console.WriteLine($"Couldn't find either {title1} or {title2}.");
                return false;
            }

        }
```

Use lotes de instruções UPDATE para atualizar itens.

```
        /// <summary>
        /// Updates information for multiple movies.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// movies to be updated.</param>
        /// <param name="producer1">The producer name for the first movie
        /// to update.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year that the first movie was released.</param>
        /// <param name="producer2">The producer name for the second
        /// movie to update.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year that the second movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the update.</
returns>
        public static async Task<bool> UpdateBatch(
            string tableName,
            string producer1,
            string title1,
            int year1,
            string producer2,
            string title2,
            int year2)
        {

            string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title = ?
 AND year = ?";
```

```
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer1 },
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer2 },
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
 BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Use lotes de instruções DELETE para excluir itens.

```
        /// <summary>
        /// Deletes multiple movies using a PartiQL BatchExecuteAsync
        /// statement.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// moves that will be deleted.</param>
```

```
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year the first movie was released.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year the second movie was released.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeleteBatch(
            string tableName,
            string title1,
            int year1,
            string title2,
            int year2)
        {

            string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND year
 = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
 BatchExecuteStatementRequest
            {
                Statements = statements,
            });
```

```
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for .NET da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        public static async Task<int> ScanTableAsync(
            AmazonDynamoDBClient client,
            string tableName,
            int startYear,
            int endYear)
        {
            var request = new ScanRequest
            {
                TableName = tableName,
                ExpressionAttributeNames = new Dictionary<string, string>
                {
                  { "#yr", "year" },
                },
                ExpressionAttributeValues = new Dictionary<string, AttributeValue>
                {
                    { ":y_a", new AttributeValue { N = startYear.ToString() } },
                    { ":y_z", new AttributeValue { N = endYear.ToString() } },
                },
                FilterExpression = "#yr between :y_a and :y_z",
                ProjectionExpression = "#yr, title, info.actors[0], info.directors,
info.running_time_secs",
                Limit = 10 // Set a limit to demonstrate using the LastEvaluatedKey.
```

```
            };

            // Keep track of how many movies were found.
            int foundCount = 0;

            var response = new ScanResponse();
            do
            {
                response = await client.ScanAsync(request);
                foundCount += response.Items.Count;
                response.Items.ForEach(i => DisplayItem(i));
                request.ExclusiveStartKey = response.LastEvaluatedKey;
            }
            while (response.LastEvaluatedKey.Count > 0);
            return foundCount;
        }
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for .NET.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Updates an existing item in the movies table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information for
        /// the movie to update.</param>
        /// <param name="newInfo">A MovieInfo object that contains the
```

```
        /// information that will be changed.</param>
        /// <param name="tableName">The name of the table that contains the movie.</
param>
        /// <returns>A Boolean value that indicates the success of the operation.</
returns>
        public static async Task<bool> UpdateItemAsync(
            AmazonDynamoDBClient client,
            Movie newMovie,
            MovieInfo newInfo,
            string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };
            var updates = new Dictionary<string, AttributeValueUpdate>
            {
                ["info.plot"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { S = newInfo.Plot },
                },

                ["info.rating"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { N = newInfo.Rank.ToString() },
                },
            };

            var request = new UpdateItemRequest
            {
                AttributeUpdates = updates,
                Key = key,
                TableName = tableName,
            };

            var response = await client.UpdateItemAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for .NET da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Grava um lote de itens na tabela de filmes.

```
/// <summary>
/// Loads the contents of a JSON file into a list of movies to be
/// added to the DynamoDB table.
/// </summary>
/// <param name="movieFileName">The full path to the JSON file.</param>
/// <returns>A generic list of movie objects.</returns>
public static List<Movie> ImportMovies(string movieFileName)
{
    if (!File.Exists(movieFileName))
    {
        return null;
    }

    using var sr = new StreamReader(movieFileName);
    string json = sr.ReadToEnd();
    var allMovies = JsonSerializer.Deserialize<List<Movie>>(
        json,
        new JsonSerializerOptions
        {
            PropertyNameCaseInsensitive = true
        });
```

```
            // Now return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }

        /// <summary>
        /// Writes 250 items to the movie table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="movieFileName">A string containing the full path to
        /// the JSON file containing movie data.</param>
        /// <returns>A long integer value representing the number of movies
        /// imported from the JSON file.</returns>
        public static async Task<long> BatchWriteItemsAsync(
            AmazonDynamoDBClient client,
            string movieFileName)
        {
            var movies = ImportMovies(movieFileName);
            if (movies is null)
            {
                Console.WriteLine("Couldn't find the JSON file with movie data.");
                return 0;
            }

            var context = new DynamoDBContext(client);

            var movieBatch = context.CreateBatchWrite<Movie>();
            movieBatch.AddPutItems(movies);

            Console.WriteLine("Adding imported movies to the table.");
            await movieBatch.ExecuteAsync();

            return movies.Count;
        }
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for .NET da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// This example application performs the following basic Amazon DynamoDB
// functions:
//
//     CreateTableAsync
//     PutItemAsync
//     UpdateItemAsync
//     BatchWriteItemAsync
//     GetItemAsync
//     DeleteItemAsync
//     Query
//     Scan
//     DeleteItemAsync
//
using Amazon.DynamoDBv2;
using DynamoDB_Actions;

public class DynamoDB_Basics
{
    // Separator for the console display.
    private static readonly string SepBar = new string('-', 80);

    public static async Task Main()
    {
        var client = new AmazonDynamoDBClient();
```

```
        var tableName = "movie_table";

        // Relative path to moviedata.json in the local repository.
        var movieFileName = @"..\..\..\..\..\..\..\..\resources\sample_files
\movies.json";

        DisplayInstructions();

        // Create a new table and wait for it to be active.
        Console.WriteLine($"Creating the new table: {tableName}");

        var success = await DynamoDbMethods.CreateMovieTableAsync(client,
 tableName);

        if (success)
        {
            Console.WriteLine($"\nTable: {tableName} successfully created.");
        }
        else
        {
            Console.WriteLine($"\nCould not create {tableName}.");
        }

        WaitForEnter();

        // Add a single new movie to the table.
        var newMovie = new Movie
        {
            Year = 2021,
            Title = "Spider-Man: No Way Home",
        };

        success = await DynamoDbMethods.PutItemAsync(client, newMovie, tableName);
        if (success)
        {
            Console.WriteLine($"Added {newMovie.Title} to the table.");
        }
        else
        {
            Console.WriteLine("Could not add movie to table.");
        }

        WaitForEnter();
```

```
        // Update the new movie by adding a plot and rank.
        var newInfo = new MovieInfo
        {
            Plot = "With Spider-Man's identity now revealed, Peter asks" +
                   "Doctor Strange for help. When a spell goes wrong, dangerous" +
                   "foes from other worlds start to appear, forcing Peter to" +
                   "discover what it truly means to be Spider-Man.",
            Rank = 9,
        };

        success = await DynamoDbMethods.UpdateItemAsync(client, newMovie, newInfo,
tableName);
        if (success)
        {
            Console.WriteLine($"Successfully updated the movie: {newMovie.Title}");
        }
        else
        {
            Console.WriteLine("Could not update the movie.");
        }

        WaitForEnter();

        // Add a batch of movies to the DynamoDB table from a list of
        // movies in a JSON file.
        var itemCount = await DynamoDbMethods.BatchWriteItemsAsync(client,
movieFileName);
        Console.WriteLine($"Added {itemCount} movies to the table.");

        WaitForEnter();

        // Get a movie by key. (partition + sort)
        var lookupMovie = new Movie
        {
            Title = "Jurassic Park",
            Year = 1993,
        };

        Console.WriteLine("Looking for the movie \"Jurassic Park\".");
        var item = await DynamoDbMethods.GetItemAsync(client, lookupMovie,
tableName);
        if (item.Count > 0)
        {
```

```
            DynamoDbMethods.DisplayItem(item);
        }
        else
        {
            Console.WriteLine($"Couldn't find {lookupMovie.Title}");
        }

        WaitForEnter();

        // Delete a movie.
        var movieToDelete = new Movie
        {
            Title = "The Town",
            Year = 2010,
        };

        success = await DynamoDbMethods.DeleteItemAsync(client, tableName,
movieToDelete);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {movieToDelete.Title}.");
        }
        else
        {
            Console.WriteLine($"Could not delete {movieToDelete.Title}.");
        }

        WaitForEnter();

        // Use Query to find all the movies released in 2010.
        int findYear = 2010;
        Console.WriteLine($"Movies released in {findYear}");
        var queryCount = await DynamoDbMethods.QueryMoviesAsync(client, tableName,
findYear);
        Console.WriteLine($"Found {queryCount} movies released in {findYear}");

        WaitForEnter();

        // Use Scan to get a list of movies from 2001 to 2011.
        int startYear = 2001;
        int endYear = 2011;
        var scanCount = await DynamoDbMethods.ScanTableAsync(client, tableName,
startYear, endYear);
```

```
        Console.WriteLine($"Found {scanCount} movies released between {startYear}
and {endYear}");

        WaitForEnter();

        // Delete the table.
        success = await DynamoDbMethods.DeleteTableAsync(client, tableName);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {tableName}");
        }
        else
        {
            Console.WriteLine($"Could not delete {tableName}");
        }

        Console.WriteLine("The DynamoDB Basics example application is done.");

        WaitForEnter();
    }

    /// <summary>
    /// Displays the description of the application on the console.
    /// </summary>
    private static void DisplayInstructions()
    {
        Console.Clear();
        Console.WriteLine();
        Console.Write(new string(' ', 28));
        Console.WriteLine("DynamoDB Basics Example");
        Console.WriteLine(SepBar);
        Console.WriteLine("This demo application shows the basics of using DynamoDB
with the AWS SDK.");
        Console.WriteLine(SepBar);
        Console.WriteLine("The application does the following:");
        Console.WriteLine("\t1. Creates a table with partition: year and
sort:title.");
        Console.WriteLine("\t2. Adds a single movie to the table.");
        Console.WriteLine("\t3. Adds movies to the table from moviedata.json.");
        Console.WriteLine("\t4. Updates the rating and plot of the movie that was
just added.");
        Console.WriteLine("\t5. Gets a movie using its key (partition + sort).");
        Console.WriteLine("\t6. Deletes a movie.");
```

```
        Console.WriteLine("\t7. Uses QueryAsync to return all movies released in a
 given year.");
        Console.WriteLine("\t8. Uses ScanAsync to return all movies released within
 a range of years.");
        Console.WriteLine("\t9. Finally, it deletes the table that was just
 created.");
        WaitForEnter();
    }

    /// <summary>
    /// Simple method to wait for the Enter key to be pressed.
    /// </summary>
    private static void WaitForEnter()
    {
        Console.WriteLine("\nPress <Enter> to continue.");
        Console.WriteLine(SepBar);
        _ = Console.ReadLine();
    }
}
```

Cria uma tabela para conter dados de filmes.

```
        /// <summary>
        /// Creates a new Amazon DynamoDB table and then waits for the new
        /// table to become active.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="tableName">The name of the table to create.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
 client, string tableName)
        {
            var response = await client.CreateTableAsync(new CreateTableRequest
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                {
                    new AttributeDefinition
```

```
                {
                    AttributeName = "title",
                    AttributeType = ScalarAttributeType.S,
                },
                new AttributeDefinition
                {
                    AttributeName = "year",
                    AttributeType = ScalarAttributeType.N,
                },
            },
            KeySchema = new List<KeySchemaElement>()
            {
                new KeySchemaElement
                {
                    AttributeName = "year",
                    KeyType = KeyType.HASH,
                },
                new KeySchemaElement
                {
                    AttributeName = "title",
                    KeyType = KeyType.RANGE,
                },
            },
            ProvisionedThroughput = new ProvisionedThroughput
            {
                ReadCapacityUnits = 5,
                WriteCapacityUnits = 5,
            },
        });

        // Wait until the table is ACTIVE and then report success.
        Console.Write("Waiting for table to become active...");

        var request = new DescribeTableRequest
        {
            TableName = response.TableDescription.TableName,
        };

        TableStatus status;

        int sleepDuration = 2000;

        do
        {
```

```
                System.Threading.Thread.Sleep(sleepDuration);

                var describeTableResponse = await
 client.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
```

Adiciona um único filme à tabela.

```
        /// <summary>
        /// Adds a new item to the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing informtation for
        /// the movie to add to the table.</param>
        /// <param name="tableName">The name of the table where the item will be
 added.</param>
        /// <returns>A Boolean value that indicates the results of adding the
 item.</returns>
        public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
 Movie newMovie, string tableName)
        {
            var item = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };

            var request = new PutItemRequest
            {
                TableName = tableName,
                Item = item,
            };
```

```
            var response = await client.PutItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Atualiza um item único em uma tabela.

```
        /// <summary>
        /// Updates an existing item in the movies table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information for
        /// the movie to update.</param>
        /// <param name="newInfo">A MovieInfo object that contains the
        /// information that will be changed.</param>
        /// <param name="tableName">The name of the table that contains the movie.</
param>
        /// <returns>A Boolean value that indicates the success of the operation.</
returns>
        public static async Task<bool> UpdateItemAsync(
            AmazonDynamoDBClient client,
            Movie newMovie,
            MovieInfo newInfo,
            string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };
            var updates = new Dictionary<string, AttributeValueUpdate>
            {
                ["info.plot"] = new AttributeValueUpdate
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { S = newInfo.Plot },
                },

                ["info.rating"] = new AttributeValueUpdate
```

```
                {
                    Action = AttributeAction.PUT,
                    Value = new AttributeValue { N = newInfo.Rank.ToString() },
                },
            };

            var request = new UpdateItemRequest
            {
                AttributeUpdates = updates,
                Key = key,
                TableName = tableName,
            };

            var response = await client.UpdateItemAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Recupera um único item de uma tabela de filmes.

```
        /// <summary>
        /// Gets information about an existing movie from the table.
        /// </summary>
        /// <param name="client">An initialized Amazon DynamoDB client object.</
param>
        /// <param name="newMovie">A Movie object containing information about
        /// the movie to retrieve.</param>
        /// <param name="tableName">The name of the table containing the movie.</
param>
        /// <returns>A Dictionary object containing information about the item
        /// retrieved.</returns>
        public static async Task<Dictionary<string, AttributeValue>>
 GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = newMovie.Title },
                ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
            };
```

```
        var request = new GetItemRequest
        {
            Key = key,
            TableName = tableName,
        };

        var response = await client.GetItemAsync(request);
        return response.Item;
    }
```

Grava um lote de itens na tabela de filmes.

```
    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the DynamoDB table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A generic list of movie objects.</returns>
    public static List<Movie> ImportMovies(string movieFileName)
    {
        if (!File.Exists(movieFileName))
        {
            return null;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();
        var allMovies = JsonSerializer.Deserialize<List<Movie>>(
            json,
            new JsonSerializerOptions
            {
                PropertyNameCaseInsensitive = true
            });

        // Now return the first 250 entries.
        return allMovies.GetRange(0, 250);
    }

    /// <summary>
    /// Writes 250 items to the movie table.
```

```
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="movieFileName">A string containing the full path to
        /// the JSON file containing movie data.</param>
        /// <returns>A long integer value representing the number of movies
        /// imported from the JSON file.</returns>
        public static async Task<long> BatchWriteItemsAsync(
            AmazonDynamoDBClient client,
            string movieFileName)
        {
            var movies = ImportMovies(movieFileName);
            if (movies is null)
            {
                Console.WriteLine("Couldn't find the JSON file with movie data.");
                return 0;
            }

            var context = new DynamoDBContext(client);

            var movieBatch = context.CreateBatchWrite<Movie>();
            movieBatch.AddPutItems(movies);

            Console.WriteLine("Adding imported movies to the table.");
            await movieBatch.ExecuteAsync();

            return movies.Count;
        }
```

Exclui um único item da tabela.

```
        /// <summary>
        /// Deletes a single item from a DynamoDB table.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table from which the item
        /// will be deleted.</param>
        /// <param name="movieToDelete">A movie object containing the title and
        /// year of the movie to delete.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// delete operation.</returns>
```

```
        public static async Task<bool> DeleteItemAsync(
            AmazonDynamoDBClient client,
            string tableName,
            Movie movieToDelete)
        {
            var key = new Dictionary<string, AttributeValue>
            {
                ["title"] = new AttributeValue { S = movieToDelete.Title },
                ["year"] = new AttributeValue { N = movieToDelete.Year.ToString() },
            };

            var request = new DeleteItemRequest
            {
                TableName = tableName,
                Key = key,
            };

            var response = await client.DeleteItemAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

Consulta a tabela de filmes lançados em determinado ano.

```
        /// <summary>
        /// Queries the table for movies released in a particular year and
        /// then displays the information for the movies returned.
        /// </summary>
        /// <param name="client">The initialized DynamoDB client object.</param>
        /// <param name="tableName">The name of the table to query.</param>
        /// <param name="year">The release year for which we want to
        /// view movies.</param>
        /// <returns>The number of movies that match the query.</returns>
        public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient client,
string tableName, int year)
        {
            var movieTable = Table.LoadTable(client, tableName);
            var filter = new QueryFilter("year", QueryOperator.Equal, year);

            Console.WriteLine("\nFind movies released in: {year}:");
```

```
            var config = new QueryOperationConfig()
            {
                Limit = 10, // 10 items per page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "title",
                  "year",
                },
                ConsistentRead = true,
                Filter = filter,
            };

            // Value used to track how many movies match the
            // supplied criteria.
            var moviesFound = 0;

            Search search = movieTable.Query(config);
            do
            {
                var movieList = await search.GetNextSetAsync();
                moviesFound += movieList.Count;

                foreach (var movie in movieList)
                {
                    DisplayDocument(movie);
                }
            }
            while (!search.IsDone);

            return moviesFound;
        }
```

Busca na tabela os filmes lançados em um intervalo de anos.

```
        public static async Task<int> ScanTableAsync(
            AmazonDynamoDBClient client,
            string tableName,
            int startYear,
            int endYear)
        {
```

```
            var request = new ScanRequest
            {
                TableName = tableName,
                ExpressionAttributeNames = new Dictionary<string, string>
                {
                  { "#yr", "year" },
                },
                ExpressionAttributeValues = new Dictionary<string, AttributeValue>
                {
                    { ":y_a", new AttributeValue { N = startYear.ToString() } },
                    { ":y_z", new AttributeValue { N = endYear.ToString() } },
                },
                FilterExpression = "#yr between :y_a and :y_z",
                ProjectionExpression = "#yr, title, info.actors[0], info.directors,
info.running_time_secs",
                Limit = 10 // Set a limit to demonstrate using the LastEvaluatedKey.
            };

            // Keep track of how many movies were found.
            int foundCount = 0;

            var response = new ScanResponse();
            do
            {
                response = await client.ScanAsync(request);
                foundCount += response.Items.Count;
                response.Items.ForEach(i => DisplayItem(i));
                request.ExclusiveStartKey = response.LastEvaluatedKey;
            }
            while (response.LastEvaluatedKey.Count > 0);
            return foundCount;
        }
```

Exclui a tabela de filmes.

```
        public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient client,
string tableName)
        {
            var request = new DeleteTableRequest
            {
                TableName = tableName,
```

```
            };

            var response = await client.DeleteTableAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Table {response.TableDescription.TableName}
successfully deleted.");
                return true;
            }
            else
            {
                Console.WriteLine("Could not delete table.");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.

- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Before you run this example, download 'movies.json' from
// https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
GettingStarted.Js.02.html,
// and put it in the same folder as the example.

// Separator for the console display.
var SepBar = new string('-', 80);
const string tableName = "movie_table";
const string movieFileName = "moviedata.json";

DisplayInstructions();

// Create the table and wait for it to be active.
Console.WriteLine($"Creating the movie table: {tableName}");

var success = await DynamoDBMethods.CreateMovieTableAsync(tableName);
if (success)
{
    Console.WriteLine($"Successfully created table: {tableName}.");
}

WaitForEnter();

// Add movie information to the table from moviedata.json. See the
// instructions at the top of this file to download the JSON file.
Console.WriteLine($"Inserting movies into the new table. Please wait...");
success = await PartiQLBatchMethods.InsertMovies(tableName, movieFileName);
if (success)
{
```

```
    Console.WriteLine("Movies successfully added to the table.");
}
else
{
    Console.WriteLine("Movies could not be added to the table.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var title1 = "Star Wars";
var year1 = 1977;
var title2 = "Wizard of Oz";
var year2 = 1939;

Console.WriteLine($"Updating two movies with producer information: {title1} and
 {title2}.");
success = await PartiQLBatchMethods.GetBatch(tableName, title1, title2, year1,
 year2);
if (success)
{
    Console.WriteLine($"Successfully retrieved {title1} and {title2}.");
}
else
{
    Console.WriteLine("Select statement failed.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var producer1 = "LucasFilm";
var producer2 = "MGM";

Console.WriteLine($"Updating two movies with producer information: {title1} and
 {title2}.");
success = await PartiQLBatchMethods.UpdateBatch(tableName, producer1, title1, year1,
 producer2, title2, year2);
if (success)
{
    Console.WriteLine($"Successfully updated {title1} and {title2}.");
}
else
{
```

```
    Console.WriteLine("Update failed.");
}

WaitForEnter();

// Delete multiple movies by using the BatchExecute statement.
Console.WriteLine($"Now we will delete {title1} and {title2} from the table.");
success = await PartiQLBatchMethods.DeleteBatch(tableName, title1, year1, title2,
 year2);

if (success)
{
    Console.WriteLine($"Deleted {title1} and {title2}");
}
else
{
    Console.WriteLine($"could not delete {title1} or {title2}");
}

WaitForEnter();

// DNow that the PartiQL Batch scenario is complete, delete the movie table.
success = await DynamoDBMethods.DeleteTableAsync(tableName);

if (success)
{
    Console.WriteLine($"Successfully deleted {tableName}");
}
else
{
    Console.WriteLine($"Could not delete {tableName}");
}

/// <summary>
/// Displays the description of the application on the console.
/// </summary>
void DisplayInstructions()
{
    Console.Clear();
    Console.WriteLine();
    Console.Write(new string(' ', 24));
    Console.WriteLine("DynamoDB PartiQL Basics Example");
    Console.WriteLine(SepBar);
```

```
    Console.WriteLine("This demo application shows the basics of using Amazon
 DynamoDB with the AWS SDK for");
    Console.WriteLine(".NET version 3.7 and .NET 6.");
    Console.WriteLine(SepBar);
    Console.WriteLine("Creates a table by using the CreateTable method.");
    Console.WriteLine("Gets multiple movies by using a PartiQL SELECT statement.");
    Console.WriteLine("Updates multiple movies by using the ExecuteBatch method.");
    Console.WriteLine("Deletes multiple movies by using a PartiQL DELETE
 statement.");
    Console.WriteLine("Cleans up the resources created for the demo by deleting the
 table.");
    Console.WriteLine(SepBar);

    WaitForEnter();
}

/// <summary>
/// Simple method to wait for the <Enter> key to be pressed.
/// </summary>
void WaitForEnter()
{
    Console.WriteLine("\nPress <Enter> to continue.");
    Console.Write(SepBar);
    _ = Console.ReadLine();
}


        /// <summary>
        /// Gets movies from the movie table by
        /// using an Amazon DynamoDB PartiQL SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year1">The year of the first movie.</param>
        /// <param name="year2">The year of the second movie.</param>
        /// <returns>True if successful.</returns>
        public static async Task<bool> GetBatch(
            string tableName,
            string title1,
            string title2,
            int year1,
            int year2)
        {
```

```
            var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = getBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            if (response.Responses.Count > 0)
            {
                response.Responses.ForEach(r =>
                {
                    Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
                });
                return true;
            }
            else
            {
                Console.WriteLine($"Couldn't find either {title1} or {title2}.");
                return false;
            }
```

```
        }

        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table into which the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
                                Parameters = new List<AttributeValue>
                                {
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
```

```
                        });
                    }

                    var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
                    {
                        Statements = statements,
                    });

                    // Wait between batches for movies to be successfully added.
                    System.Threading.Thread.Sleep(3000);

                    success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                    // Clear the list of statements for the next batch.
                    statements.Clear();
                }
            }
            catch (AmazonDynamoDBException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        return success;
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the DynamoDB table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A generic list of movie objects.</returns>
    public static List<Movie> ImportMovies(string movieFileName)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();
        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);
```

```
            if (allMovies is not null)
            {
                // Return the first 250 entries.
                return allMovies.GetRange(0, 250);
            }
            else
            {
                return null!;
            }
        }

        /// <summary>
        /// Updates information for multiple movies.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// movies to be updated.</param>
        /// <param name="producer1">The producer name for the first movie
        /// to update.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year that the first movie was released.</param>
        /// <param name="producer2">The producer name for the second
        /// movie to update.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year that the second movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the update.</
returns>
        public static async Task<bool> UpdateBatch(
            string tableName,
            string producer1,
            string title1,
            int year1,
            string producer2,
            string title2,
            int year2)
        {

            string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title = ?
 AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
```

```
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer1 },
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = producer2 },
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
 BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }

        /// <summary>
        /// Deletes multiple movies using a PartiQL BatchExecuteAsync
        /// statement.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// moves that will be deleted.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year the first movie was released.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year the second movie was released.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeleteBatch(
            string tableName,
            string title1,
```

```
            int year1,
            string title2,
            int year2)
        {

            string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title1 },
                        new AttributeValue { N = year1.ToString() },
                    },
                },

                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>
                    {
                        new AttributeValue { S = title2 },
                        new AttributeValue { N = year2.ToString() },
                    },
                }
            };

            var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
            {
                Statements = statements,
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for .NET da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace PartiQL_Basics_Scenario
{
    public class PartiQLMethods
    {
        private static readonly AmazonDynamoDBClient Client = new
 AmazonDynamoDBClient();


        /// <summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        /// </summary>
        /// <param name="tableName">The name of the table where the movie
        /// information will be inserted.</param>
        /// <param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
 movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);
```

```
            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";
                var statements = new List<BatchStatementRequest>();

                try
                {
                    for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
                    {
                        for (var i = indexOffset; i < indexOffset + 25; i++)
                        {
                            statements.Add(new BatchStatementRequest
                            {
                                Statement = insertBatch,
                                Parameters = new List<AttributeValue>
                                {
                                    new AttributeValue { S = movies[i].Title },
                                    new AttributeValue { N =
movies[i].Year.ToString() },
                                },
                            });
                        }

                        var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
                        {
                            Statements = statements,
                        });

                        // Wait between batches for movies to be successfully added.
                        System.Threading.Thread.Sleep(3000);

                        success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                        // Clear the list of statements for the next batch.
                        statements.Clear();
```

```
                }
            }
            catch (AmazonDynamoDBException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        return success;
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the DynamoDB table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A generic list of movie objects.</returns>
    public static List<Movie> ImportMovies(string movieFileName)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();
        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

        if (allMovies is not null)
        {
            // Return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }
        else
        {
            return null!;
        }
    }



    /// <summary>
    /// Uses a PartiQL SELECT statement to retrieve a single movie from the
    /// movie database.
```

```
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }



        /// <summary>
        /// Retrieve multiple movies by year using a SELECT statement.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="year">The year the movies were released.</param>
        /// <returns></returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetMovies(string tableName, int year)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { N = year.ToString() },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
```

```
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }


        /// <summary>
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
```

```
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
        {
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Deletes a single movie from the table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
```

```
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }


        /// <summary>
        /// Displays the list of movies returned from a database query.
        /// </summary>
        /// <param name="items">The list of movie information to display.</param>
        private static void DisplayMovies(List<Dictionary<string, AttributeValue>>
 items)
        {
            if (items.Count > 0)
            {
                Console.WriteLine($"Found {items.Count} movies.");
                items.ForEach(item =>
 Console.WriteLine($"{item["year"].N}\t{item["title"].S}"));
            }
            else
            {
                Console.WriteLine($"Didn't find a movie that matched the supplied
 criteria.");
            }
        }



    }
}




        /// <summary>
        /// Uses a PartiQL SELECT statement to retrieve a single movie from the
        /// movie database.
        /// </summary>
        /// <param name="tableName">The name of the movie table.</param>
        /// <param name="movieTitle">The title of the movie to retrieve.</param>
```

```
        /// <returns>A list of movie data. If no movie matches the supplied
        /// title, the list is empty.</returns>
        public static async Task<List<Dictionary<string, AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
        {
            string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
            var parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
            };

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = selectSingle,
                Parameters = parameters,
            });

            return response.Items;
        }



        /// <summary>
        /// Inserts a single movie into the movies table.
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to insert.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success or failure of
        /// the INSERT operation.</returns>
        public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
        {
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
```

```
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Updates a single movie in the table, adding information for the
        /// producer.
        /// </summary>
        /// <param name="tableName">the name of the table.</param>
        /// <param name="producer">The name of the producer.</param>
        /// <param name="movieTitle">The movie title.</param>
        /// <param name="year">The year the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// UPDATE operation.</returns>
        public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
        {
            string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = insertSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = producer },
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }



        /// <summary>
        /// Deletes a single movie from the table.
```

```
        /// </summary>
        /// <param name="tableName">The name of the table.</param>
        /// <param name="movieTitle">The title of the movie to delete.</param>
        /// <param name="year">The year that the movie was released.</param>
        /// <returns>A Boolean value that indicates the success of the
        /// DELETE operation.</returns>
        public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
        {
            var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

            var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
            {
                Statement = deleteSingle,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movieTitle },
                    new AttributeValue { N = year.ToString() },
                },
            });

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for .NET da API.

Usar um modelo de documento

O exemplo de código a seguir mostra como realizar operações de criação, leitura, atualização e exclusão (CRUD) e operações em lote usando um modelo de documento para o DynamoDB e um AWS SDK.

Para obter mais informações, consulte o modelo de documento.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Execute operações CRUD usando um modelo de documento.

```
/// <summary>
/// Performs CRUD operations on an Amazon DynamoDB table.
/// </summary>
public class MidlevelItemCRUD
{
    public static async Task Main()
    {
        var tableName = "ProductCatalog";
        var sampleBookId = 555;

        var client = new AmazonDynamoDBClient();
        var productCatalog = LoadTable(client, tableName);

        await CreateBookItem(productCatalog, sampleBookId);
        RetrieveBook(productCatalog, sampleBookId);

        // Couple of sample updates.
        UpdateMultipleAttributes(productCatalog, sampleBookId);
        UpdateBookPriceConditionally(productCatalog, sampleBookId);

        // Delete.
        await DeleteBook(productCatalog, sampleBookId);
    }

    /// <summary>
    /// Loads the contents of a DynamoDB table.
    /// </summary>
    /// <param name="client">An initialized DynamoDB client object.</param>
    /// <param name="tableName">The name of the table to load.</param>
    /// <returns>A DynamoDB table object.</returns>
    public static Table LoadTable(IAmazonDynamoDB client, string tableName)
    {
```

```
            Table productCatalog = Table.LoadTable(client, tableName);
            return productCatalog;
        }

        /// <summary>
        /// Creates an example book item and adds it to the DynamoDB table
        /// ProductCatalog.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async Task CreateBookItem(Table productCatalog, int
sampleBookId)
        {
            Console.WriteLine("\n*** Executing CreateBookItem() ***");
            var book = new Document
            {
                ["Id"] = sampleBookId,
                ["Title"] = "Book " + sampleBookId,
                ["Price"] = 19.99,
                ["ISBN"] = "111-1111111111",
                ["Authors"] = new List<string> { "Author 1", "Author 2", "Author
3" },
                ["PageCount"] = 500,
                ["Dimensions"] = "8.5x11x.5",
                ["InPublication"] = new DynamoDBBool(true),
                ["InStock"] = new DynamoDBBool(false),
                ["QuantityOnHand"] = 0,
            };

            // Adds the book to the ProductCatalog table.
            await productCatalog.PutItemAsync(book);
        }

        /// <summary>
        /// Retrieves an item, a book, from the DynamoDB ProductCatalog table.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async void RetrieveBook(
          Table productCatalog,
          int sampleBookId)
        {
```

```
            Console.WriteLine("\n*** Executing RetrieveBook() ***");

            // Optional configuration.
            var config = new GetItemOperationConfig
            {
                AttributesToGet = new List<string> { "Id", "ISBN", "Title",
"Authors", "Price" },
                ConsistentRead = true,
            };

            Document document = await productCatalog.GetItemAsync(sampleBookId,
config);
            Console.WriteLine("RetrieveBook: Printing book retrieved...");
            PrintDocument(document);
        }

        /// <summary>
        /// Updates multiple attributes for a book and writes the changes to the
        /// DynamoDB table ProductCatalog.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async void UpdateMultipleAttributes(
          Table productCatalog,
          int sampleBookId)
        {
            Console.WriteLine("\nUpdating multiple attributes....");
            int partitionKey = sampleBookId;

            var book = new Document
            {
                ["Id"] = partitionKey,

                // List of attribute updates.
                // The following replaces the existing authors list.
                ["Authors"] = new List<string> { "Author x", "Author y" },
                ["newAttribute"] = "New Value",
                ["ISBN"] = null, // Remove it.
            };

            // Optional parameters.
            var config = new UpdateItemOperationConfig
            {
```

```
                // Gets updated item in response.
                ReturnValues = ReturnValues.AllNewAttributes,
            };

            Document updatedBook = await productCatalog.UpdateItemAsync(book,
config);
            Console.WriteLine("UpdateMultipleAttributes: Printing item after
updates ...");
            PrintDocument(updatedBook);
        }

        /// <summary>
        /// Updates a book item if it meets the specified criteria.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async void UpdateBookPriceConditionally(
          Table productCatalog,
          int sampleBookId)
        {
            Console.WriteLine("\n*** Executing UpdateBookPriceConditionally() ***");

            int partitionKey = sampleBookId;

            var book = new Document
            {
                ["Id"] = partitionKey,
                ["Price"] = 29.99,
            };

            // For conditional price update, creating a condition expression.
            var expr = new Expression
            {
                ExpressionStatement = "Price = :val",
            };
            expr.ExpressionAttributeValues[":val"] = 19.00;

            // Optional parameters.
            var config = new UpdateItemOperationConfig
            {
                ConditionalExpression = expr,
                ReturnValues = ReturnValues.AllNewAttributes,
            };
```

```
            Document updatedBook = await productCatalog.UpdateItemAsync(book,
config);
            Console.WriteLine("UpdateBookPriceConditionally: Printing item whose
price was conditionally updated");
            PrintDocument(updatedBook);
        }

        /// <summary>
        /// Deletes the book with the supplied Id value from the DynamoDB table
        /// ProductCatalog.
        /// </summary>
        /// <param name="productCatalog">A DynamoDB table object.</param>
        /// <param name="sampleBookId">An integer value representing the book's
ID.</param>
        public static async Task DeleteBook(
          Table productCatalog,
          int sampleBookId)
        {
            Console.WriteLine("\n*** Executing DeleteBook() ***");

            // Optional configuration.
            var config = new DeleteItemOperationConfig
            {
                // Returns the deleted item.
                ReturnValues = ReturnValues.AllOldAttributes,
            };
            Document document = await productCatalog.DeleteItemAsync(sampleBookId,
config);
            Console.WriteLine("DeleteBook: Printing deleted just deleted...");

            PrintDocument(document);
        }

        /// <summary>
        /// Prints the information for the supplied DynamoDB document.
        /// </summary>
        /// <param name="updatedDocument">A DynamoDB document object.</param>
        public static void PrintDocument(Document updatedDocument)
        {
            if (updatedDocument is null)
            {
                return;
            }
```

```
            foreach (var attribute in updatedDocument.GetAttributeNames())
            {
                string stringValue = null;
                var value = updatedDocument[attribute];

                if (value is null)
                {
                    continue;
                }

                if (value is Primitive)
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                  select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}", attribute,
stringValue);
            }
        }
    }
```

Execute operações de gravação em lote usando um modelo de documento.

```
    /// <summary>
    /// Shows how to use mid-level Amazon DynamoDB API calls to perform batch
    /// operations.
    /// </summary>
    public class MidLevelBatchWriteItem
    {
        public static async Task Main()
        {
            IAmazonDynamoDB client = new AmazonDynamoDBClient();
```

```
            await SingleTableBatchWrite(client);
            await MultiTableBatchWrite(client);
        }

        /// <summary>
        /// Perform a batch operation on a single DynamoDB table.
        /// </summary>
        /// <param name="client">An initialized DynamoDB object.</param>
        public static async Task SingleTableBatchWrite(IAmazonDynamoDB client)
        {
            Table productCatalog = Table.LoadTable(client, "ProductCatalog");
            var batchWrite = productCatalog.CreateBatchWrite();

            var book1 = new Document
            {
                ["Id"] = 902,
                ["Title"] = "My book1 in batch write using .NET helper classes",
                ["ISBN"] = "902-11-11-1111",
                ["Price"] = 10,
                ["ProductCategory"] = "Book",
                ["Authors"] = new List<string> { "Author 1", "Author 2", "Author
3" },
                ["Dimensions"] = "8.5x11x.5",
                ["InStock"] = new DynamoDBBool(true),
                ["QuantityOnHand"] = new DynamoDBNull(), // Quantity is unknown at
this time.
            };

            batchWrite.AddDocumentToPut(book1);

            // Specify delete item using overload that takes PK.
            batchWrite.AddKeyToDelete(12345);
            Console.WriteLine("Performing batch write in SingleTableBatchWrite()");
            await batchWrite.ExecuteAsync();
        }

        /// <summary>
        /// Perform a batch operation involving multiple DynamoDB tables.
        /// </summary>
        /// <param name="client">An initialized DynamoDB client object.</param>
        public static async Task MultiTableBatchWrite(IAmazonDynamoDB client)
        {
            // Specify item to add in the Forum table.
```

```
            Table forum = Table.LoadTable(client, "Forum");
            var forumBatchWrite = forum.CreateBatchWrite();

            var forum1 = new Document
            {
                ["Name"] = "Test BatchWrite Forum",
                ["Threads"] = 0,
            };
            forumBatchWrite.AddDocumentToPut(forum1);

            // Specify item to add in the Thread table.
            Table thread = Table.LoadTable(client, "Thread");
            var threadBatchWrite = thread.CreateBatchWrite();

            var thread1 = new Document
            {
                ["ForumName"] = "S3 forum",
                ["Subject"] = "My sample question",
                ["Message"] = "Message text",
                ["KeywordTags"] = new List<string> { "S3", "Bucket" },
            };
            threadBatchWrite.AddDocumentToPut(thread1);

            // Specify item to delete from the Thread table.
            threadBatchWrite.AddKeyToDelete("someForumName", "someSubject");

            // Create multi-table batch.
            var superBatch = new MultiTableDocumentBatchWrite();
            superBatch.AddBatch(forumBatchWrite);
            superBatch.AddBatch(threadBatchWrite);
            Console.WriteLine("Performing batch write in MultiTableBatchWrite()");

            // Execute the batch.
            await superBatch.ExecuteAsync();
        }
    }
```

Verifique uma tabela usando um modelo de documento.

```
    /// <summary>
```

```
    /// Shows how to use mid-level Amazon DynamoDB API calls to scan a DynamoDB
    /// table for values.
    /// </summary>
    public class MidLevelScanOnly
    {
        public static async Task Main()
        {
            IAmazonDynamoDB client = new AmazonDynamoDBClient();

            Table productCatalogTable = Table.LoadTable(client, "ProductCatalog");

            await FindProductsWithNegativePrice(productCatalogTable);
            await FindProductsWithNegativePriceWithConfig(productCatalogTable);
        }

        /// <summary>
        /// Retrieves any products that have a negative price in a DynamoDB table.
        /// </summary>
        /// <param name="productCatalogTable">A DynamoDB table object.</param>
        public static async Task FindProductsWithNegativePrice(
          Table productCatalogTable)
        {
            // Assume there is a price error. So we scan to find items priced < 0.
            var scanFilter = new ScanFilter();
            scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

            Search search = productCatalogTable.Scan(scanFilter);

            do
            {
                var documentList = await search.GetNextSetAsync();
                Console.WriteLine("\nFindProductsWithNegativePrice:
printing ............");

                foreach (var document in documentList)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Finds any items in the ProductCatalog table using a DynamoDB
```

```
        /// configuration object.
        /// </summary>
        /// <param name="productCatalogTable">A DynamoDB table object.</param>
        public static async Task FindProductsWithNegativePriceWithConfig(
          Table productCatalogTable)
        {
            // Assume there is a price error. So we scan to find items priced < 0.
            var scanFilter = new ScanFilter();
            scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

            var config = new ScanOperationConfig()
            {
                Filter = scanFilter,
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string> { "Title", "Id" },
            };

            Search search = productCatalogTable.Scan(config);

            do
            {
                var documentList = await search.GetNextSetAsync();
                Console.WriteLine("\nFindProductsWithNegativePriceWithConfig:
printing ............");

                foreach (var document in documentList)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Displays the details of the passed DynamoDB document object on the
        /// console.
        /// </summary>
        /// <param name="document">A DynamoDB document object.</param>
        public static void PrintDocument(Document document)
        {
            Console.WriteLine();
            foreach (var attribute in document.GetAttributeNames())
            {
                string stringValue = null;
```

```
                var value = document[attribute];
                if (value is Primitive)
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                  select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}");
            }
        }
    }
```

Consulte e verifique uma tabela usando um modelo de documento.

```
    /// <summary>
    /// Shows how to perform mid-level query procedures on an Amazon DynamoDB
    /// table.
    /// </summary>
    public class MidLevelQueryAndScan
    {
        public static async Task Main()
        {
            IAmazonDynamoDB client = new AmazonDynamoDBClient();

            // Query examples.
            Table replyTable = Table.LoadTable(client, "Reply");
            string forumName = "Amazon DynamoDB";
            string threadSubject = "DynamoDB Thread 2";

            await FindRepliesInLast15Days(replyTable);
            await FindRepliesInLast15DaysWithConfig(replyTable, forumName,
threadSubject);
            await FindRepliesPostedWithinTimePeriod(replyTable, forumName,
threadSubject);
```

```
            // Get Example.
            Table productCatalogTable = Table.LoadTable(client, "ProductCatalog");
            int productId = 101;

            await GetProduct(productCatalogTable, productId);
        }

        /// <summary>
        /// Retrieves information about a product from the DynamoDB table
        /// ProductCatalog based on the product ID and displays the information
        /// on the console.
        /// </summary>
        /// <param name="tableName">The name of the table from which to retrieve
        /// product information.</param>
        /// <param name="productId">The ID of the product to retrieve.</param>
        public static async Task GetProduct(Table tableName, int productId)
        {
            Console.WriteLine("*** Executing GetProduct() ***");
            Document productDocument = await tableName.GetItemAsync(productId);
            if (productDocument != null)
            {
                PrintDocument(productDocument);
            }
            else
            {
                Console.WriteLine("Error: product " + productId + " does not
exist");
            }
        }

        /// <summary>
        /// Retrieves replies from the passed DynamoDB table object.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
        public static async Task FindRepliesInLast15Days(
          Table table)
        {
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
            var filter = new QueryFilter("Id", QueryOperator.Equal, "Id");
            filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);

            // Use Query overloads that take the minimum required query parameters.
```

```
            Search search = table.Query(filter);

            do
            {
                var documentSet = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesInLast15Days:
printing ............");

                foreach (var document in documentSet)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Retrieve replies made during a specific time period.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadSubject">The subject of the thread, which we are
        /// searching for replies.</param>
        public static async Task FindRepliesPostedWithinTimePeriod(
          Table table,
          string forumName,
          string threadSubject)
        {
            DateTime startDate = DateTime.UtcNow.Subtract(new TimeSpan(21, 0, 0,
0));
            DateTime endDate = DateTime.UtcNow.Subtract(new TimeSpan(1, 0, 0, 0));

            var filter = new QueryFilter("Id", QueryOperator.Equal, forumName + "#"
+ threadSubject);
            filter.AddCondition("ReplyDateTime", QueryOperator.Between, startDate,
endDate);

            var config = new QueryOperationConfig()
            {
                Limit = 2, // 2 items/page.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
        {
```

```
          "Message",
          "ReplyDateTime",
          "PostedBy",
        },
                ConsistentRead = true,
                Filter = filter,
            };

            Search search = table.Query(config);

            do
            {
                var documentList = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesPostedWithinTimePeriod: printing
replies posted within dates: {0} and {1} ............", startDate, endDate);

                foreach (var document in documentList)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Perform a query for replies made in the last 15 days using a DynamoDB
        /// QueryOperationConfig object.
        /// </summary>
        /// <param name="table">The table we want to query.</param>
        /// <param name="forumName">The name of the forum that we're interested
in.</param>
        /// <param name="threadName">The bane of the thread that we are searching
        /// for replies.</param>
        public static async Task FindRepliesInLast15DaysWithConfig(
          Table table,
          string forumName,
          string threadName)
        {
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
            var filter = new QueryFilter("Id", QueryOperator.Equal, forumName + "#"
+ threadName);
            filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);
```

```
            var config = new QueryOperationConfig()
            {
                Filter = filter,

                // Optional parameters.
                Select = SelectValues.SpecificAttributes,
                AttributesToGet = new List<string>
                {
                  "Message",
                  "ReplyDateTime",
                  "PostedBy",
                },
                ConsistentRead = true,
            };

            Search search = table.Query(config);

            do
            {
                var documentSet = await search.GetNextSetAsync();
                Console.WriteLine("\nFindRepliesInLast15DaysWithConfig:
printing ............");

                foreach (var document in documentSet)
                {
                    PrintDocument(document);
                }
            }
            while (!search.IsDone);
        }

        /// <summary>
        /// Displays the contents of the passed DynamoDB document on the console.
        /// </summary>
        /// <param name="document">A DynamoDB document to display.</param>
        public static void PrintDocument(Document document)
        {
            Console.WriteLine();
            foreach (var attribute in document.GetAttributeNames())
            {
                string stringValue = null;
                var value = document[attribute];

                if (value is Primitive)
```

```
                {
                    stringValue = value.AsPrimitive().Value.ToString();
                }
                else if (value is PrimitiveList)
                {
                    stringValue = string.Join(",", (from primitive
                      in value.AsPrimitiveList().Entries
                                                        select
primitive.Value).ToArray());
                }

                Console.WriteLine($"{attribute} - {stringValue}");
            }
        }
    }
```

Usar um modelo de persistência de objetos de alto nível

O exemplo de código a seguir mostra como realizar operações de criação, leitura, atualização e exclusão (CRUD) e operações em lote usando um modelo de persistência de objetos para o DynamoDB e um AWS SDK.

Para obter mais informações, consulte Modelo de persistência de objetos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Realize operações CRUD usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Shows how to perform high-level CRUD operations on an Amazon DynamoDB
    /// table.
    /// </summary>
```

```
    public class HighLevelItemCrud
    {
        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();
            DynamoDBContext context = new DynamoDBContext(client);
            await PerformCRUDOperations(context);
        }

        public static async Task PerformCRUDOperations(IDynamoDBContext context)
        {
            int bookId = 1001; // Some unique value.
            Book myBook = new Book
            {
                Id = bookId,
                Title = "object persistence-AWS SDK for.NET SDK-Book 1001",
                Isbn = "111-1111111001",
                BookAuthors = new List<string> { "Author 1", "Author 2" },
            };

            // Save the book to the ProductCatalog table.
            await context.SaveAsync(myBook);

            // Retrieve the book from the ProductCatalog table.
            Book bookRetrieved = await context.LoadAsync<Book>(bookId);

            // Update some properties.
            bookRetrieved.Isbn = "222-2222221001";

            // Update existing authors list with the following values.
            bookRetrieved.BookAuthors = new List<string> { " Author 1", "Author
x" };
            await context.SaveAsync(bookRetrieved);

            // Retrieve the updated book. This time, add the optional
            // ConsistentRead parameter using DynamoDBContextConfig object.
            await context.LoadAsync<Book>(bookId, new DynamoDBContextConfig
            {
                ConsistentRead = true,
            });

            // Delete the book.
            await context.DeleteAsync<Book>(bookId);
```

```
            // Try to retrieve deleted book. It should return null.
            Book deletedBook = await context.LoadAsync<Book>(bookId, new
DynamoDBContextConfig
            {
                ConsistentRead = true,
            });

            if (deletedBook == null)
            {
                Console.WriteLine("Book is deleted");
            }
        }
    }
```

Realize operações de gravação em lote usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Performs high-level batch write operations to an Amazon DynamoDB table.
    /// This example was written using the AWS SDK for .NET version 3.7 and .NET
    /// Core 5.0.
    /// </summary>
    public class HighLevelBatchWriteItem
    {
        public static async Task SingleTableBatchWrite(IDynamoDBContext context)
        {
            Book book1 = new Book
            {
                Id = 902,
                InPublication = true,
                Isbn = "902-11-11-1111",
                PageCount = "100",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book3 in batch write",
            };

            Book book2 = new Book
            {
                Id = 903,
```

```
                InPublication = true,
                Isbn = "903-11-11-1111",
                PageCount = "200",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book4 in batch write",
            };

            var bookBatch = context.CreateBatchWrite<Book>();
            bookBatch.AddPutItems(new List<Book> { book1, book2 });

            Console.WriteLine("Adding two books to ProductCatalog table.");
            await bookBatch.ExecuteAsync();
        }

        public static async Task MultiTableBatchWrite(IDynamoDBContext context)
        {
            // New Forum item.
            Forum newForum = new Forum
            {
                Name = "Test BatchWrite Forum",
                Threads = 0,
            };
            var forumBatch = context.CreateBatchWrite<Forum>();
            forumBatch.AddPutItem(newForum);

            // New Thread item.
            Thread newThread = new Thread
            {
                ForumName = "S3 forum",
                Subject = "My sample question",
                KeywordTags = new List<string> { "S3", "Bucket" },
                Message = "Message text",
            };

            DynamoDBOperationConfig config = new DynamoDBOperationConfig();
            config.SkipVersionCheck = true;
            var threadBatch = context.CreateBatchWrite<Thread>(config);
            threadBatch.AddPutItem(newThread);
            threadBatch.AddDeleteKey("some partition key value", "some sort key
value");

            var superBatch = new MultiTableBatchWrite(forumBatch, threadBatch);
```

```
            Console.WriteLine("Performing batch write in MultiTableBatchWrite().");
            await superBatch.ExecuteAsync();
        }

        public static async Task Main()
        {
            AmazonDynamoDBClient client = new AmazonDynamoDBClient();
            DynamoDBContext context = new DynamoDBContext(client);

            await SingleTableBatchWrite(context);
            await MultiTableBatchWrite(context);
        }
    }
```

Mapeie dados arbitrários em uma tabela usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Shows how to map arbitrary data to an Amazon DynamoDB table.
    /// </summary>
    public class HighLevelMappingArbitraryData
    {
        /// <summary>
        /// Creates a book, adds it to the DynamoDB ProductCatalog table, retrieves
        /// the new book from the table, updates the dimensions and writes the
        /// changed item back to the table.
        /// </summary>
        /// <param name="context">The DynamoDB context object used to write and
        /// read data from the table.</param>
        public static async Task AddRetrieveUpdateBook(IDynamoDBContext context)
        {
            // Create a book.
            DimensionType myBookDimensions = new DimensionType()
            {
                Length = 8M,
                Height = 11M,
                Thickness = 0.5M,
            };

            Book myBook = new Book
```

```
            {
                Id = 501,
                Title = "AWS SDK for .NET Object Persistence Model Handling
 Arbitrary Data",
                Isbn = "999-9999999999",
                BookAuthors = new List<string> { "Author 1", "Author 2" },
                Dimensions = myBookDimensions,
            };

            // Add the book to the DynamoDB table ProductCatalog.
            await context.SaveAsync(myBook);

            // Retrieve the book.
            Book bookRetrieved = await context.LoadAsync<Book>(501);

            // Update the book dimensions property.
            bookRetrieved.Dimensions.Height += 1;
            bookRetrieved.Dimensions.Length += 1;
            bookRetrieved.Dimensions.Thickness += 0.2M;

            // Write the changed item to the table.
            await context.SaveAsync(bookRetrieved);
        }

        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();
            DynamoDBContext context = new DynamoDBContext(client);
            await AddRetrieveUpdateBook(context);
        }
    }
```

Consulte e verifique uma tabela usando um modelo de persistência de objetos de alto nível.

```
    /// <summary>
    /// Shows how to perform high-level query and scan operations to Amazon
    /// DynamoDB tables.
    /// </summary>
    public class HighLevelQueryAndScan
    {
```

```
        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();

            DynamoDBContext context = new DynamoDBContext(client);

            // Get an item.
            await GetBook(context, 101);

            // Sample forum and thread to test queries.
            string forumName = "Amazon DynamoDB";
            string threadSubject = "DynamoDB Thread 1";

            // Sample queries.
            await FindRepliesInLast15Days(context, forumName, threadSubject);
            await FindRepliesPostedWithinTimePeriod(context, forumName,
 threadSubject);

            // Scan table.
            await FindProductsPricedLessThanZero(context);
        }

        public static async Task GetBook(IDynamoDBContext context, int productId)
        {
            Book bookItem = await context.LoadAsync<Book>(productId);

            Console.WriteLine("\nGetBook: Printing result.....");
            Console.WriteLine($"Title: {bookItem.Title} \n ISBN:{bookItem.Isbn} \n
 No. of pages: {bookItem.PageCount}");
        }

        /// <summary>
        /// Queries a DynamoDB table to find replies posted within the last 15 days.
        /// </summary>
        /// <param name="context">The DynamoDB context used to perform the query.</
param>
        /// <param name="forumName">The name of the forum that we're interested
 in.</param>
        /// <param name="threadSubject">The thread object containing the query
 parameters.</param>
        public static async Task FindRepliesInLast15Days(
          IDynamoDBContext context,
          string forumName,
          string threadSubject)
```

```
        {
            string replyId = $"{forumName} #{threadSubject}";
            DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);

            List<object> times = new List<object>();
            times.Add(twoWeeksAgoDate);

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc = new ScanCondition("PostedBy", ScanOperator.GreaterThan,
 times.ToArray());
            scs.Add(sc);

            var cfg = new DynamoDBOperationConfig
            {
                QueryFilter = scs,
            };

            AsyncSearch<Reply> response = context.QueryAsync<Reply>(replyId, cfg);
            IEnumerable<Reply> latestReplies = await response.GetRemainingAsync();

            Console.WriteLine("\nReplies in last 15 days:");

            foreach (Reply r in latestReplies)
            {

 Console.WriteLine($"{r.Id}\t{r.PostedBy}\t{r.Message}\t{r.ReplyDateTime}");
            }
        }

        /// <summary>
        /// Queries for replies posted within a specific time period.
        /// </summary>
        /// <param name="context">The DynamoDB context used to perform the query.</
param>
        /// <param name="forumName">The name of the forum that we're interested
 in.</param>
        /// <param name="threadSubject">Information about the subject that we're
        /// interested in.</param>
        public static async Task FindRepliesPostedWithinTimePeriod(
          IDynamoDBContext context,
          string forumName,
          string threadSubject)
        {
            string forumId = forumName + "#" + threadSubject;
```

```
            Console.WriteLine("\nReplies posted within time period:");

            DateTime startDate = DateTime.UtcNow - TimeSpan.FromDays(30);
            DateTime endDate = DateTime.UtcNow - TimeSpan.FromDays(1);

            List<object> times = new List<object>();
            times.Add(startDate);
            times.Add(endDate);

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc = new ScanCondition("LastPostedBy", ScanOperator.Between,
times.ToArray());
            scs.Add(sc);

            var cfg = new DynamoDBOperationConfig
            {
                QueryFilter = scs,
            };

            AsyncSearch<Reply> response = context.QueryAsync<Reply>(forumId, cfg);
            IEnumerable<Reply> repliesInAPeriod = await
response.GetRemainingAsync();

            foreach (Reply r in repliesInAPeriod)
            {

Console.WriteLine("{r.Id}\t{r.PostedBy}\t{r.Message}\t{r.ReplyDateTime}");
            }
        }

        /// <summary>
        /// Queries the DynamoDB ProductCatalog table for products costing less
        /// than zero.
        /// </summary>
        /// <param name="context">The DynamoDB context object used to perform the
        /// query.</param>
        public static async Task FindProductsPricedLessThanZero(IDynamoDBContext
context)
        {
            int price = 0;

            List<ScanCondition> scs = new List<ScanCondition>();
            var sc1 = new ScanCondition("Price", ScanOperator.LessThan, price);
```

```
            var sc2 = new ScanCondition("ProductCategory", ScanOperator.Equal,
"Book");
            scs.Add(sc1);
            scs.Add(sc2);

            AsyncSearch<Book> response = context.ScanAsync<Book>(scs);

            IEnumerable<Book> itemsWithWrongPrice = await
response.GetRemainingAsync();

            Console.WriteLine("\nFindProductsPricedLessThanZero: Printing
result.....");

            foreach (Book r in itemsWithWrongPrice)
            {
                Console.WriteLine($"{r.Id}\t{r.Title}\t{r.Price}\t{r.Isbn}");
            }
        }
    }
```

Exemplos do Amazon EC2 usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace EC2Actions;

public class HelloEc2
{
    /// <summary>
    /// HelloEc2 lists the existing security groups for the default users.
    /// </summary>
    /// <param name="args">Command line arguments</param>
    /// <returns>A Task object.</returns>
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Elastic Compute Cloud (Amazon
 EC2).
        using var host =
 Microsoft.Extensions.Hosting.Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonEC2>()
                .AddTransient<EC2Wrapper>()
            )
            .Build();

        // Now the client is available for injection.
        var ec2Client = host.Services.GetRequiredService<IAmazonEC2>();

        var request = new DescribeSecurityGroupsRequest
        {
            MaxResults = 10,
        };


        // Retrieve information about up to 10 Amazon EC2 security groups.
        var response = await ec2Client.DescribeSecurityGroupsAsync(request);
```

```
        // Now print the security groups returned by the call to
        // DescribeSecurityGroupsAsync.
        Console.WriteLine("Security Groups:");
        response.SecurityGroups.ForEach(group =>
        {
            Console.WriteLine($"Security group: {group.GroupName} ID:
 {group.GroupId}");
        });
    }
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico para o Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Allocate an Elastic IP address.
    /// </summary>
    /// <returns>The allocation Id of the allocated address.</returns>
    public async Task<string> AllocateAddress()
    {
        var request = new AllocateAddressRequest();
```

```
        var response = await _amazonEC2.AllocateAddressAsync(request);
        return response.AllocationId;
    }
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for .NET da API.

Para associar um endereço IP elástico a uma instância

O exemplo de código a seguir mostra como associar um endereço IP elástico a uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Associate an Elastic IP address to an EC2 instance.
    /// </summary>
    /// <param name="allocationId">The allocation Id of an Elastic IP address.</
param>
    /// <param name="instanceId">The instance Id of the EC2 instance to
    /// associate the address with.</param>
    /// <returns>The association Id that represents
    /// the association of the Elastic IP address with an instance.</returns>
    public async Task<string> AssociateAddress(string allocationId, string
 instanceId)
    {
        var request = new AssociateAddressRequest
        {
            AllocationId = allocationId,
            InstanceId = instanceId
        };

        var response = await _amazonEC2.AssociateAddressAsync(request);
        return response.AssociationId;
    }
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for .NET da API.

Criar um modelo de inicialização

O exemplo de código a seguir mostra como criar um modelo de execução de sub-rede do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
   /// The launch template specifies a Bash script in its user data field that runs
after
   /// the instance is started. This script installs the Python packages and starts
a Python
   /// web server on the instance.
   /// </summary>
   /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
   /// <param name="instancePolicyPath">The path to a permissions policy to create
and attach to the profile.</param>
   /// <returns>The template object.</returns>
   public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
   {
       await CreateKeyPair(_keyPairName);
       await CreateInstanceProfileWithName(_instancePolicyName, _instanceRoleName,
_instanceProfileName, instancePolicyPath);

       var startServerText = await File.ReadAllTextAsync(startupScriptPath);
       var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);
```

```
        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new
                            LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }
```

- Para obter detalhes da API, consulte CreateLaunchTemplatea Referência AWS SDK for .NET da API.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Create an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name for the new security group.</param>
    /// <param name="groupDescription">A description of the new security group.</
param>
    /// <returns>The group Id of the new security group.</returns>
    public async Task<string> CreateSecurityGroup(string groupName, string
 groupDescription)
    {
        var response = await _amazonEC2.CreateSecurityGroupAsync(
            new CreateSecurityGroupRequest(groupName, groupDescription));

        return response.GroupId;
    }
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for .NET da API.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name for the new key pair.</param>
    /// <returns>The Amazon EC2 key pair created.</returns>
    public async Task<KeyPair?> CreateKeyPair(string keyPairName)
    {
        var request = new CreateKeyPairRequest
        {
```

```
            KeyName = keyPairName,
        };

        var response = await _amazonEC2.CreateKeyPairAsync(request);

        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            var kp = response.KeyPair;
            return kp;
        }
        else
        {
            Console.WriteLine("Could not create key pair.");
            return null;
        }
    }

    /// <summary>
    /// Save KeyPair information to a temporary file.
    /// </summary>
    /// <param name="keyPair">The name of the key pair.</param>
    /// <returns>The full path to the temporary file.</returns>
    public string SaveKeyPair(KeyPair keyPair)
    {
        var tempPath = Path.GetTempPath();
        var tempFileName = $"{tempPath}\\{Path.GetRandomFileName()}";
        var pemFileName = Path.ChangeExtension(tempFileName, "pem");

        // Save the key pair to a file in a temporary folder.
        using var stream = new FileStream(pemFileName, FileMode.Create);
        using var writer = new StreamWriter(stream);
        writer.WriteLine(keyPair.KeyMaterial);

        return pemFileName;
    }
```

- Para obter detalhes da API, consulte CreateKeyPair a Referência AWS SDK for .NET da API.

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create and run an EC2 instance.
    /// </summary>
    /// <param name="ImageId">The image Id of the image used as a basis for the
    /// EC2 instance.</param>
    /// <param name="instanceType">The instance type of the EC2 instance to
create.</param>
    /// <param name="keyName">The name of the key pair to associate with the
    /// instance.</param>
    /// <param name="groupId">The Id of the Amazon EC2 security group that will be
    /// allowed to interact with the new EC2 instance.</param>
    /// <returns>The instance Id of the new EC2 instance.</returns>
    public async Task<string> RunInstances(string imageId, string instanceType,
string keyName, string groupId)
    {
        var request = new RunInstancesRequest
        {
            ImageId = imageId,
            InstanceType = instanceType,
            KeyName = keyName,
            MinCount = 1,
            MaxCount = 1,
            SecurityGroupIds = new List<string> { groupId }
        };
        var response = await _amazonEC2.RunInstancesAsync(request);
        return response.Reservation.Instances[0].InstanceId;
    }
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for .NET da API.

Excluir um modelo de execução

O exemplo de código a seguir mostra como excluir um modelo de execução de sub-rede do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete a launch template by name.
/// </summary>
/// <param name="templateName">The name of the template to delete.</param>
/// <returns>Async task.</returns>
public async Task DeleteTemplateByName(string templateName)
{
    try
    {
        await _amazonEc2.DeleteLaunchTemplateAsync(
            new DeleteLaunchTemplateRequest()
            {
                LaunchTemplateName = templateName
            });
    }
    catch (AmazonClientException)
    {
        Console.WriteLine($"Unable to delete template {templateName}.");
    }
}
```

- Para obter detalhes da API, consulte DeleteLaunchTemplatea Referência AWS SDK for .NET da API.

Exclua um grupo de segurança

O exemplo de código a seguir mostra como excluir um grupo de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteSecurityGroup(string groupId)
    {
        var response = await _amazonEC2.DeleteSecurityGroupAsync(new
DeleteSecurityGroupRequest { GroupId = groupId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for .NET da API.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair to delete.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyPair(string keyPairName)
    {
        try
        {
            await _amazonEC2.DeleteKeyPairAsync(new
DeleteKeyPairRequest(keyPairName)).ConfigureAwait(false);
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Couldn't delete the key pair because:
{ex.Message}");
            return false;
        }
    }

    /// <summary>
    /// Delete the temporary file where the key pair information was saved.
    /// </summary>
    /// <param name="tempFileName">The path to the temporary file.</param>
    public void DeleteTempFile(string tempFileName)
    {
        if (File.Exists(tempFileName))
        {
            File.Delete(tempFileName);
        }
    }
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for .NET da API.

Descrever as zonas de disponibilidade

O exemplo de código a seguir mostra como descrever as zonas de disponibilidade do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get a list of Availability Zones in the AWS Region of the Amazon EC2 Client.
/// </summary>
/// <returns>A list of availability zones.</returns>
public async Task<List<string>> DescribeAvailabilityZones()
{
    var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
        new DescribeAvailabilityZonesRequest());
    return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
}
```

- Para obter detalhes da API, consulte DescribeAvailabilityZonesa Referência AWS SDK for .NET da API.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get information about existing EC2 images.
/// </summary>
/// <returns>Async task.</returns>
public async Task DescribeInstances()
{
    // List all EC2 instances.
    await GetInstanceDescriptions();

    string tagName = "IncludeInList";
    string tagValue = "Yes";
    await GetInstanceDescriptionsFiltered(tagName, tagValue);
}
```

```
    /// <summary>
    /// Get information for all existing Amazon EC2 instances.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptions()
    {
        Console.WriteLine("Showing all instances:");
        var paginator = _amazonEC2.Paginators.DescribeInstances(new
DescribeInstancesRequest());

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId}");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Get information about EC2 instances filtered by a tag name and value.
    /// </summary>
    /// <param name="tagName">The name of the tag to filter on.</param>
    /// <param name="tagValue">The value of the tag to look for.</param>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptionsFiltered(string tagName, string
tagValue)
    {
        // This tag filters the results of the instance list.
        var filters = new List<Filter>
        {
            new Filter
            {
                Name = $"tag:{tagName}",
                Values = new List<string>
                {
                    tagValue,
                },
            },
        };
```

```
        var request = new DescribeInstancesRequest
        {
            Filters = filters,
        };

        Console.WriteLine("\nShowing instances with tag: \"IncludeInList\" set to
\"Yes\".");
        var paginator = _amazonEC2.Paginators.DescribeInstances(request);

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId} ");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for .NET da API.

Desassociar um endereço IP elástico de uma instância

O exemplo de código a seguir mostra como desassociar um endereço IP elástico de uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Disassociate an Elastic IP address from an EC2 instance.
```

```
    /// </summary>
    /// <param name="associationId">The association Id.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DisassociateIp(string associationId)
    {
        var response = await _amazonEC2.DisassociateAddressAsync(
            new DisassociateAddressRequest { AssociationId = associationId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for .NET da API.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information for an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupId">The Id of the Amazon EC2 security group.</param>
    /// <returns>A list of security group information.</returns>
    public async Task<List<SecurityGroup>> DescribeSecurityGroups(string groupId)
    {
        var request = new DescribeSecurityGroupsRequest();
        var groupIds = new List<string> { groupId };
        request.GroupIds = groupIds;

        var response = await _amazonEC2.DescribeSecurityGroupsAsync(request);
        return response.SecurityGroups;
    }
```

```
    /// <summary>
    /// Display the information returned by the call to
    /// DescribeSecurityGroupsAsync.
    /// </summary>
    /// <param name="securityGroup">A list of security group information.</param>
    public void DisplaySecurityGroupInfoAsync(SecurityGroup securityGroup)
    {
        Console.WriteLine($"{securityGroup.GroupName}");
        Console.WriteLine("Ingress permissions:");
        securityGroup.IpPermissions.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range => { Console.Write($"{range.CidrIp}
"); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
        Console.WriteLine("Egress permissions:");
        securityGroup.IpPermissionsEgress.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range => { Console.Write($"{range.CidrIp}
"); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));
```

```
            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
    }
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for .NET da API.

Obter dados sobre tipos de instâncias

O exemplo de código a seguir mostra como obter dados sobre tipos de instâncias do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the instance types available.
    /// </summary>
    /// <returns>A list of instance type information.</returns>
    public async Task<List<InstanceTypeInfo>>
DescribeInstanceTypes(ArchitectureValues architecture)
    {
        var request = new DescribeInstanceTypesRequest();

        var filters = new List<Filter>
            { new Filter("processor-info.supported-architecture", new List<string>
{ architecture.ToString() }) };
        filters.Add(new Filter("instance-type", new() { "*.micro", "*.small" }));

        request.Filters = filters;
        var instanceTypes = new List<InstanceTypeInfo>();

        var paginator = _amazonEC2.Paginators.DescribeInstanceTypes(request);
        await foreach (var instanceType in paginator.InstanceTypes)
```

```
        {
            instanceTypes.Add(instanceType);
        }
        return instanceTypes;
    }
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for .NET da API.

Obtenha dados sobre o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como obter dados sobre o perfil de instância associado a uma instância Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }
```

- Para obter detalhes da API, consulte DescribeIamInstanceProfileAssociationsa Referência AWS SDK for .NET da API.

Obtenha a VPC padrão

O exemplo de código a seguir mostra como obter o VPC padrão da conta atual.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get the default VPC for the account.
/// </summary>
/// <returns>The default VPC object.</returns>
public async Task<Vpc> GetDefaultVpc()
{
    var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
        new DescribeVpcsRequest()
        {
            Filters = new List<Amazon.EC2.Model.Filter>()
            {
                new ("is-default", new List<string>() { "true" })
            }
        });
    return vpcResponse.Vpcs[0];
}
```

- Para obter detalhes da API, consulte DescribeVpcsa Referência AWS SDK for .NET da API.

Obtenha sub-redes padrão para uma VPC

O exemplo de código a seguir mostra como obter as sub-redes padrão para uma VPC.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }
```

- Para obter detalhes da API, consulte DescribeSubnetsa Referência AWS SDK for .NET da API.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get information about an Amazon EC2 key pair.
/// </summary>
/// <param name="keyPairName">The name of the key pair.</param>
/// <returns>A list of key pair information.</returns>
public async Task<List<KeyPairInfo>> DescribeKeyPairs(string keyPairName)
{
    var request = new DescribeKeyPairsRequest();
    if (!string.IsNullOrEmpty(keyPairName))
    {
        request = new DescribeKeyPairsRequest
        {
            KeyNames = new List<string> { keyPairName }
        };
    }
    var response = await _amazonEC2.DescribeKeyPairsAsync(request);
    return response.KeyPairs.ToList();
}
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for .NET da API.

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Reboot EC2 instances.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the instances that will be
rebooted.</param>
    /// <returns>Async task.</returns>
    public async Task RebootInstances(string ec2InstanceId)
    {
        var request = new RebootInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.RebootInstancesAsync(request);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine("Instances successfully rebooted.");
        }
        else
        {
            Console.WriteLine("Could not reboot one or more instances.");
        }
    }
```

Substitua o perfil de uma instância, reinicialize e reinicie um servidor Web.

```
    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
```

```
   /// <param name="instanceId">The Id of the instance to update.</param>
   /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
   /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
   /// <returns>Async task.</returns>
   public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
   {
       await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
               new ReplaceIamInstanceProfileAssociationRequest()
               {
                   AssociationId = associationId,
                   IamInstanceProfile = new IamInstanceProfileSpecification()
                   {
                       Name = credsProfileName
                   }
               });
       // Allow time before resetting.
       Thread.Sleep(25000);
       var instanceReady = false;
       var retries = 5;
       while (retries-- > 0 && !instanceReady)
       {
           await _amazonEc2.RebootInstancesAsync(
               new RebootInstancesRequest(new List<string>() { instanceId }));
           Thread.Sleep(10000);

           var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
               new DescribeInstanceInformationRequest());
           // Get the entire list using the paginator.
           await foreach (var instance in
instancesPaginator.InstanceInformationList)
           {
               instanceReady = instance.InstanceId == instanceId;
               if (instanceReady)
               {
                   break;
               }
           }
       }
       Console.WriteLine($"Sending restart command to instance {instanceId}");
       await _amazonSsm.SendCommandAsync(
```

```
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
 server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for .NET da API.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Release an Elastic IP address.
    /// </summary>
    /// <param name="allocationId">The allocation Id of the Elastic IP address.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> ReleaseAddress(string allocationId)
    {
        var request = new ReleaseAddressRequest
        {
            AllocationId = allocationId
        };

        var response = await _amazonEC2.ReleaseAddressAsync(request);
```

```
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for .NET da API.

Subtitua o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como substituir o perfil de instância associado a uma instância Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
```

```
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }
```

- Para obter detalhes da API, consulte ReplaceIamInstanceProfileAssociationa Referência AWS SDK for .NET da API.

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Authorize the local computer ingress to EC2 instances associated
    /// with the virtual private cloud (VPC) security group.
    /// </summary>
    /// <param name="groupName">The name of the security group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AuthorizeSecurityGroupIngress(string groupName)
    {
        // Get the IP address for the local computer.
        var ipAddress = await GetIpAddress();
        Console.WriteLine($"Your IP address is: {ipAddress}");
        var ipRanges = new List<IpRange> { new IpRange { CidrIp =
$"{ipAddress}/32" } };
        var permission = new IpPermission
        {
            Ipv4Ranges = ipRanges,
            IpProtocol = "tcp",
            FromPort = 22,
            ToPort = 22
        };
        var permissions = new List<IpPermission> { permission };
        var response = await _amazonEC2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest(groupName, permissions));
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Authorize the local computer for ingress to
    /// the Amazon EC2 SecurityGroup.
    /// </summary>
    /// <returns>The IPv4 address of the computer running the scenario.</returns>
    private static async Task<string> GetIpAddress()
    {
        var httpClient = new HttpClient();
        var ipString = await httpClient.GetStringAsync("https://
checkip.amazonaws.com");

        // The IP address is returned with a new line
        // character on the end. Trim off the whitespace and
        // return the value to the caller.
        return ipString.Trim();
    }
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for .NET da API.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the Amazon EC2 instance
    /// to start.</param>
    /// <returns>Async task.</returns>
    public async Task StartInstances(string ec2InstanceId)
    {
```

```
        var request = new StartInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StartInstancesAsync(request);

        if (response.StartingInstances.Count > 0)
        {
            var instances = response.StartingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully started the EC2 instance with
instance ID: {i.InstanceId}.");
            });
        }
    }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for .NET da API.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Stop an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance to
    /// stop.</param>
    /// <returns>Async task.</returns>
    public async Task StopInstances(string ec2InstanceId)
    {
        // In addition to the list of instance Ids, the
```

```
        // request can also include the following properties:
        //     Force      When true, forces the instances to
        //                stop but you must check the integrity
        //                of the file system. Not recommended on
        //                Windows instances.
        //     Hibernate  When true, hibernates the instance if the
        //                instance was enabled for hibernation when
        //                it was launched.
        var request = new StopInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StopInstancesAsync(request);

        if (response.StoppingInstances.Count > 0)
        {
            var instances = response.StoppingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully stopped the EC2 Instance " +
                                  $"with InstanceID: {i.InstanceId}.");
            });
        }
    }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for .NET da API.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Terminate an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance
    /// to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task<List<InstanceStateChange>> TerminateInstances(string
ec2InstanceId)
    {
        var request = new TerminateInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId }
        };

        var response = await _amazonEC2.TerminateInstancesAsync(request);
        return response.TerminatingInstances;
    }
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for .NET da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.

- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
    static async Task Main(string[] args)
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
```

```
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
```

```
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper = host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several AWS
resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways to
make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide book,
movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each contain
a Python web server.");
```

```
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs 'server_startup_script.sh'
when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the `server.py`
script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
```

```
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3, _autoScalerWrapper.GroupName,
zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or continue
with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
_autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
```

```
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGroupN
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.LoadB
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper.Lo
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port, ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for your
 default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management Console.
\n");

                if (!interactive || GetYesNoResponse(
```

```
                        "Do you want to add a rule to the security group to allow
inbound traffic from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port, ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
_autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
ipString);
                }
            }
            loadBalancerAccess = await
_elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
```

```
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
 different parts of the system\n" +
                          "to create situations where the web service fails, and
 shows how using a resilient\n" +
                          "architecture can keep the web service running in spite of
 these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
 recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
 recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
 parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
 let's set this parameter to name a non-existent table.\n");
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
 checks don't check for failure of the recommendation service.");
        if (interactive)
```

```
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service fails,
the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
"static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
_smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in the
target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile that
contains\n" +
            "bad credentials...\n"
        );
```

```
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo, a
deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not for
Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the Auto
Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load balancer
can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two for
the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");

        if (interactive)
            await DemoActionChoices();
```

```
        Console.WriteLine("\nBecause the instances in this demo are controlled by an
 auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler start
 a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
 instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a successful
 recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the load
 balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance typically
 takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
 instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
 checks mean all instances report as unhealthy.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
 continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
 return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
```

```
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account, we
can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBalanc
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGroup
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupName)
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you might
incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
```

```
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with a
specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to the
role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
```

```
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                     "\"Service\": [" +
                                         "\"ec2.amazonaws.com\"" +
                                     "]" +
                                     "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                            "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
```

```
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await _amazonIam.CreateInstanceProfileAsync(
```

```
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
```

```
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
    /// The launch template specifies a Bash script in its user data field that runs
after
    /// the instance is started. This script installs the Python packages and starts
a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to create
and attach to the profile.</param>
    /// <returns>The template object.</returns>
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName, _instanceRoleName,
_instanceProfileName, instancePolicyPath);
```

```
        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new
                            LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
```

```
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with size
 {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
 exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
```

```
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
```

```
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await _amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
```

```
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
```

```
    {
        var response = await _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
```

```
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
```

```
            {
                await _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for {instanceId}.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running. Waiting...");
```

```
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
```

```
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the calling
computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP address
while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
```

```
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be open
to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
```

```
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName, string
 targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
```

```
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }
```

```
        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
```

```
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened times
 and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer exists.</
param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
```

```
   /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
   /// and forwards requests to the specified target group.
   /// </summary>
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
           {
               var describeResponse =
                   await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                       new DescribeLoadBalancersRequest()
                       {
                           Names = new List<string>() { name }
                       });

               var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

               loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
           }
           catch (LoadBalancerNotFoundException)
           {
               loadBalancerReady = false;
           }
           Thread.Sleep(10000);
```

```
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
```

```
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }
```

```
    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn = targetArn });
                Console.WriteLine($"Deleted load balancing target group
 {groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books, movies,
 and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
```

```
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
_amazonDynamoDb.DescribeTableAsync(request);
```

```
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await File.ReadAllTextAsync(recommendationsPath);
        var records =
            JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
```

```
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-architecture-
table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";

    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
```

```
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile

- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Começar a usar instâncias

O código de exemplo a seguir mostra como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.
- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.

- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário em um prompt de comando.

```
/// <summary>
/// Show Amazon Elastic Compute Cloud (Amazon EC2) Basics actions.
/// </summary>
public class EC2Basics
{
    /// <summary>
    /// Perform the actions defined for the Amazon EC2 Basics scenario.
    /// </summary>
    /// <param name="args">Command line arguments.</param>
    /// <returns>A Task object.</returns>
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EC2 and Amazon Simple Systems
        // Management Service.
        using var host =
 Microsoft.Extensions.Hosting.Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonEC2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddTransient<EC2Wrapper>()
                    .AddTransient<SsmWrapper>()
            )
            .Build();

        // Now the client is available for injection.
        var ec2Client = host.Services.GetRequiredService<IAmazonEC2>();
        var ec2Methods = new EC2Wrapper(ec2Client);

        var ssmClient =
 host.Services.GetRequiredService<IAmazonSimpleSystemsManagement>();
```

```
        var ssmMethods = new SsmWrapper(ssmClient);
        var uiMethods = new UiMethods();

        var uniqueName = Guid.NewGuid().ToString();
        var keyPairName = "mvp-example-key-pair" + uniqueName;
        var groupName = "ec2-scenario-group" + uniqueName;
        var groupDescription = "A security group created for the EC2 Basics
scenario.";

        // Start the scenario.
        uiMethods.DisplayOverview();
        uiMethods.PressEnter();

        // Create the key pair.
        uiMethods.DisplayTitle("Create RSA key pair");
        Console.Write("Let's create an RSA key pair that you can be use to ");
        Console.WriteLine("securely connect to your EC2 instance.");
        var keyPair = await ec2Methods.CreateKeyPair(keyPairName);

        // Save key pair information to a temporary file.
        var tempFileName = ec2Methods.SaveKeyPair(keyPair);

        Console.WriteLine($"Created the key pair: {keyPair.KeyName} and saved it to:
{tempFileName}");
        string? answer;
        do
        {
            Console.Write("Would you like to list your existing key pairs? ");
            answer = Console.ReadLine();
        } while (answer!.ToLower() != "y" && answer.ToLower() != "n");

        if (answer == "y")
        {
            // List existing key pairs.
            uiMethods.DisplayTitle("Existing key pairs");

            // Passing an empty string to the DescribeKeyPairs method will return
            // a list of all existing key pairs.
            var keyPairs = await ec2Methods.DescribeKeyPairs("");
            keyPairs.ForEach(kp =>
            {
                Console.WriteLine($"{kp.KeyName} created at: {kp.CreateTime}
Fingerprint: {kp.KeyFingerprint}");
            });
```

```
        }
        uiMethods.PressEnter();

        // Create the security group.
        Console.WriteLine("Let's create a security group to manage access to your
 instance.");
        var secGroupId = await ec2Methods.CreateSecurityGroup(groupName,
 groupDescription);
        Console.WriteLine("Let's add rules to allow all HTTP and HTTPS inbound
 traffic and to allow SSH only from your current IP address.");

        uiMethods.DisplayTitle("Security group information");
        var secGroups = await ec2Methods.DescribeSecurityGroups(secGroupId);

        Console.WriteLine($"Created security group {groupName} in your default
 VPC.");
        secGroups.ForEach(group =>
        {
            ec2Methods.DisplaySecurityGroupInfoAsync(group);
        });
        uiMethods.PressEnter();

        Console.WriteLine("Now we'll authorize the security group we just created so
 that it can");
        Console.WriteLine("access the EC2 instances you create.");
        var success = await ec2Methods.AuthorizeSecurityGroupIngress(groupName);

        secGroups = await ec2Methods.DescribeSecurityGroups(secGroupId);
        Console.WriteLine($"Now let's look at the permissions again.");
        secGroups.ForEach(group =>
        {
            ec2Methods.DisplaySecurityGroupInfoAsync(group);
        });
        uiMethods.PressEnter();

        // Get list of available Amazon Linux 2 Amazon Machine Images (AMIs).
        var parameters = await ssmMethods.GetParametersByPath("/aws/service/ami-
amazon-linux-latest");

        List<string> imageIds = parameters.Select(param => param.Value).ToList();

        var images = await ec2Methods.DescribeImages(imageIds);

        var i = 1;
```

```
        images.ForEach(image =>
        {
            Console.WriteLine($"\t{i++}\t{image.Description}");
        });

        int choice;
        bool validNumber = false;

        do
        {
            Console.Write("Please select an image: ");
            var selImage = Console.ReadLine();
            validNumber = int.TryParse(selImage, out choice);
        } while (!validNumber);

        var selectedImage = images[choice - 1];

        // Display available instance types.
        uiMethods.DisplayTitle("Instance Types");
        var instanceTypes = await
ec2Methods.DescribeInstanceTypes(selectedImage.Architecture);

        i = 1;
        instanceTypes.ForEach(instanceType =>
        {
            Console.WriteLine($"\t{i++}\t{instanceType.InstanceType}");
        });

        do
        {
            Console.Write("Please select an instance type: ");
            var selImage = Console.ReadLine();
            validNumber = int.TryParse(selImage, out choice);
        } while (!validNumber);

        var selectedInstanceType = instanceTypes[choice - 1].InstanceType;

        // Create an EC2 instance.
        uiMethods.DisplayTitle("Creating an EC2 Instance");
        var instanceId = await ec2Methods.RunInstances(selectedImage.ImageId,
selectedInstanceType, keyPairName, secGroupId);
        Console.Write("Waiting for the instance to start.");
        var isRunning = false;
        do
```

```
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        uiMethods.PressEnter();

        var instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nYou can use SSH to connect to your instance. For
 example:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        uiMethods.PressEnter();

        Console.WriteLine("Now we'll stop the instance and then start it again to
 see what's changed.");

        await ec2Methods.StopInstances(instanceId);
        var hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");

        Console.WriteLine("Now let's start it up again.");
        await ec2Methods.StartInstances(instanceId);
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        Console.WriteLine("\nLet's see what changed.");
```

```
        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nNotice the change in the SSH information:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        uiMethods.PressEnter();

        Console.WriteLine("Now we will stop the instance again. Then we will create
 and associate an");
        Console.WriteLine("Elastic IP address to use with our instance.");

        await ec2Methods.StopInstances(instanceId);
        hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("Allocate Elastic IP address");
        Console.WriteLine("You can allocate an Elastic IP address and associate
 it with your instance\nto keep a consistent IP address even when your instance
 restarts.");
        var allocationId = await ec2Methods.AllocateAddress();
        Console.WriteLine("Now we will associate the Elastic IP address with our
 instance.");
        var associationId = await ec2Methods.AssociateAddress(allocationId,
 instanceId);

        // Start the instance again.
        Console.WriteLine("Now let's start the instance again.");
        await ec2Methods.StartInstances(instanceId);
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
```

```
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        Console.WriteLine("\nLet's see what changed.");

        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("Instance information");
        ec2Methods.DisplayInstanceInformation(instance);

        Console.WriteLine("\nHere is the SSH information:");
        Console.WriteLine($"\tssh -i {tempFileName} ec2-
user@{instance.PublicIpAddress}");

        Console.WriteLine("Let's stop and start the instance again.");
        uiMethods.PressEnter();

        await ec2Methods.StopInstances(instanceId);

        hasStopped = false;
        do
        {
            hasStopped = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Stopped);
        } while (!hasStopped);

        Console.WriteLine("\nThe instance has stopped.");

        Console.WriteLine("Now let's start it up again.");
        await ec2Methods.StartInstances(instanceId);
        Console.Write("Waiting for instance to start. ");

        isRunning = false;
        do
        {
            isRunning = await ec2Methods.WaitForInstanceState(instanceId,
 InstanceStateName.Running);
        } while (!isRunning);

        instance = await ec2Methods.DescribeInstance(instanceId);
        uiMethods.DisplayTitle("New Instance Information");
        ec2Methods.DisplayInstanceInformation(instance);
        Console.WriteLine("Note that the IP address did not change this time.");
        uiMethods.PressEnter();
```

```
        uiMethods.DisplayTitle("Clean up resources");

        Console.WriteLine("Now let's clean up the resources we created.");

        // Terminate the instance.
        Console.WriteLine("Terminating the instance we created.");
        var stateChange = await ec2Methods.TerminateInstances(instanceId);

        // Wait for the instance state to be terminated.
        var hasTerminated = false;
        do
        {
            hasTerminated = await ec2Methods.WaitForInstanceState(instanceId,
InstanceStateName.Terminated);
        } while (!hasTerminated);

        Console.WriteLine($"\nThe instance {instanceId} has been terminated.");
        Console.WriteLine("Now we can disassociate the Elastic IP address and
release it.");

        // Disassociate the Elastic IP address.
        var disassociated = ec2Methods.DisassociateIp(associationId);

        // Delete the Elastic IP address.
        var released = ec2Methods.ReleaseAddress(allocationId);

        // Delete the security group.
        Console.WriteLine($"Deleting the Security Group: {groupName}.");
        success = await ec2Methods.DeleteSecurityGroup(secGroupId);
        if (success)
        {
            Console.WriteLine($"Successfully deleted {groupName}.");
        }

        // Delete the RSA key pair.
        Console.WriteLine($"Deleting the key pair: {keyPairName}");
        await ec2Methods.DeleteKeyPair(keyPairName);
        Console.WriteLine("Deleting the temporary file with the key information.");
        ec2Methods.DeleteTempFile(tempFileName);
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("EC2 Basics Scenario completed.");
        uiMethods.PressEnter();
```

```
    }
}
```

Defina uma classe que envolva as ações do EC2.

```
/// <summary>
/// Methods of this class perform Amazon Elastic Compute Cloud (Amazon EC2).
/// </summary>
public class EC2Wrapper
{
    private readonly IAmazonEC2 _amazonEC2;

    public EC2Wrapper(IAmazonEC2 amazonService)
    {
        _amazonEC2 = amazonService;
    }

    /// <summary>
    /// Allocate an Elastic IP address.
    /// </summary>
    /// <returns>The allocation Id of the allocated address.</returns>
    public async Task<string> AllocateAddress()
    {
        var request = new AllocateAddressRequest();

        var response = await _amazonEC2.AllocateAddressAsync(request);
        return response.AllocationId;
    }

    /// <summary>
    /// Associate an Elastic IP address to an EC2 instance.
    /// </summary>
    /// <param name="allocationId">The allocation Id of an Elastic IP address.</
param>
    /// <param name="instanceId">The instance Id of the EC2 instance to
    /// associate the address with.</param>
    /// <returns>The association Id that represents
    /// the association of the Elastic IP address with an instance.</returns>
    public async Task<string> AssociateAddress(string allocationId, string
 instanceId)
    {
        var request = new AssociateAddressRequest
```

```
        {
            AllocationId = allocationId,
            InstanceId = instanceId
        };

        var response = await _amazonEC2.AssociateAddressAsync(request);
        return response.AssociationId;
    }

    /// <summary>
    /// Authorize the local computer ingress to EC2 instances associated
    /// with the virtual private cloud (VPC) security group.
    /// </summary>
    /// <param name="groupName">The name of the security group.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AuthorizeSecurityGroupIngress(string groupName)
    {
        // Get the IP address for the local computer.
        var ipAddress = await GetIpAddress();
        Console.WriteLine($"Your IP address is: {ipAddress}");
        var ipRanges = new List<IpRange> { new IpRange { CidrIp =
$"{ipAddress}/32" } };
        var permission = new IpPermission
        {
            Ipv4Ranges = ipRanges,
            IpProtocol = "tcp",
            FromPort = 22,
            ToPort = 22
        };
        var permissions = new List<IpPermission> { permission };
        var response = await _amazonEC2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest(groupName, permissions));
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Authorize the local computer for ingress to
    /// the Amazon EC2 SecurityGroup.
    /// </summary>
    /// <returns>The IPv4 address of the computer running the scenario.</returns>
    private static async Task<string> GetIpAddress()
    {
        var httpClient = new HttpClient();
```

```
        var ipString = await httpClient.GetStringAsync("https://
checkip.amazonaws.com");

        // The IP address is returned with a new line
        // character on the end. Trim off the whitespace and
        // return the value to the caller.
        return ipString.Trim();
    }

    /// <summary>
    /// Create an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name for the new key pair.</param>
    /// <returns>The Amazon EC2 key pair created.</returns>
    public async Task<KeyPair?> CreateKeyPair(string keyPairName)
    {
        var request = new CreateKeyPairRequest
        {
            KeyName = keyPairName,
        };

        var response = await _amazonEC2.CreateKeyPairAsync(request);

        if (response.HttpStatusCode == HttpStatusCode.OK)
        {
            var kp = response.KeyPair;
            return kp;
        }
        else
        {
            Console.WriteLine("Could not create key pair.");
            return null;
        }
    }

    /// <summary>
    /// Save KeyPair information to a temporary file.
    /// </summary>
    /// <param name="keyPair">The name of the key pair.</param>
    /// <returns>The full path to the temporary file.</returns>
    public string SaveKeyPair(KeyPair keyPair)
    {
        var tempPath = Path.GetTempPath();
        var tempFileName = $"{tempPath}\\{Path.GetRandomFileName()}";
```

```
        var pemFileName = Path.ChangeExtension(tempFileName, "pem");

        // Save the key pair to a file in a temporary folder.
        using var stream = new FileStream(pemFileName, FileMode.Create);
        using var writer = new StreamWriter(stream);
        writer.WriteLine(keyPair.KeyMaterial);

        return pemFileName;
    }

    /// <summary>
    /// Create an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupName">The name for the new security group.</param>
    /// <param name="groupDescription">A description of the new security group.</
param>
    /// <returns>The group Id of the new security group.</returns>
    public async Task<string> CreateSecurityGroup(string groupName, string
 groupDescription)
    {
        var response = await _amazonEC2.CreateSecurityGroupAsync(
            new CreateSecurityGroupRequest(groupName, groupDescription));

        return response.GroupId;
    }


    /// <summary>
    /// Create a new Amazon EC2 VPC.
    /// </summary>
    /// <param name="cidrBlock">The CIDR block for the new security group.</param>
    /// <returns>The VPC Id of the new VPC.</returns>
    public async Task<string?> CreateVPC(string cidrBlock)
    {

        try
        {
            var response = await _amazonEC2.CreateVpcAsync(new CreateVpcRequest
            {
                CidrBlock = cidrBlock,
            });

            Vpc vpc = response.Vpc;
            Console.WriteLine($"Created VPC with ID: {vpc.VpcId}.");
```

```
            return vpc.VpcId;
        }
        catch (AmazonEC2Exception ex)
        {
            Console.WriteLine($"Couldn't create VPC because: {ex.Message}");
            return null;
        }
    }

    /// <summary>
    /// Delete an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyPair(string keyPairName)
    {
        try
        {
            await _amazonEC2.DeleteKeyPairAsync(new
DeleteKeyPairRequest(keyPairName)).ConfigureAwait(false);
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Couldn't delete the key pair because:
{ex.Message}");
            return false;
        }
    }

    /// <summary>
    /// Delete the temporary file where the key pair information was saved.
    /// </summary>
    /// <param name="tempFileName">The path to the temporary file.</param>
    public void DeleteTempFile(string tempFileName)
    {
        if (File.Exists(tempFileName))
        {
            File.Delete(tempFileName);
        }
    }

    /// <summary>
    /// Delete an Amazon EC2 security group.
```

```
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteSecurityGroup(string groupId)
    {
        var response = await _amazonEC2.DeleteSecurityGroupAsync(new
DeleteSecurityGroupRequest { GroupId = groupId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete an Amazon EC2 VPC.
    /// </summary>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteVpc(string vpcId)
    {
        var request = new DeleteVpcRequest
        {
            VpcId = vpcId,
        };

        var response = await _amazonEC2.DeleteVpcAsync(request);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Get information about existing Amazon EC2 images.
    /// </summary>
    /// <returns>A list of image information.</returns>
    public async Task<List<Image>> DescribeImages(List<string>? imageIds)
    {
        var request = new DescribeImagesRequest();
        if (imageIds is not null)
        {
            // If the imageIds list is not null, add the list
            // to the request object.
            request.ImageIds = imageIds;
        }

        var response = await _amazonEC2.DescribeImagesAsync(request);
        return response.Images;
    }
```

```
    /// <summary>
    /// Display the information returned by DescribeImages.
    /// </summary>
    /// <param name="images">The list of image information to display.</param>
    public void DisplayImageInfo(List<Image> images)
    {
        images.ForEach(image =>
        {
            Console.WriteLine($"{image.Name} Created on: {image.CreationDate}");
        });

    }

    /// <summary>
    /// Get information about an Amazon EC2 instance.
    /// </summary>
    /// <param name="instanceId">The instance Id of the EC2 instance.</param>
    /// <returns>An EC2 instance.</returns>
    public async Task<Instance> DescribeInstance(string instanceId)
    {
        var response = await _amazonEC2.DescribeInstancesAsync(
            new DescribeInstancesRequest { InstanceIds = new List<string>
{ instanceId } });
        return response.Reservations[0].Instances[0];
    }

    /// <summary>
    /// Display EC2 instance information.
    /// </summary>
    /// <param name="instance">The instance Id of the EC2 instance.</param>
    public void DisplayInstanceInformation(Instance instance)
    {
        Console.WriteLine($"ID: {instance.InstanceId}");
        Console.WriteLine($"Image ID: {instance.ImageId}");
        Console.WriteLine($"{instance.InstanceType}");
        Console.WriteLine($"Key Name: {instance.KeyName}");
        Console.WriteLine($"VPC ID: {instance.VpcId}");
        Console.WriteLine($"Public IP: {instance.PublicIpAddress}");
        Console.WriteLine($"State: {instance.State.Name}");
    }

    /// <summary>
    /// Get information about existing EC2 images.
    /// </summary>
```

```
    /// <returns>Async task.</returns>
    public async Task DescribeInstances()
    {
        // List all EC2 instances.
        await GetInstanceDescriptions();

        string tagName = "IncludeInList";
        string tagValue = "Yes";
        await GetInstanceDescriptionsFiltered(tagName, tagValue);
    }

    /// <summary>
    /// Get information for all existing Amazon EC2 instances.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptions()
    {
        Console.WriteLine("Showing all instances:");
        var paginator = _amazonEC2.Paginators.DescribeInstances(new
DescribeInstancesRequest());

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId}");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Get information about EC2 instances filtered by a tag name and value.
    /// </summary>
    /// <param name="tagName">The name of the tag to filter on.</param>
    /// <param name="tagValue">The value of the tag to look for.</param>
    /// <returns>Async task.</returns>
    public async Task GetInstanceDescriptionsFiltered(string tagName, string
tagValue)
    {
        // This tag filters the results of the instance list.
```

```
        var filters = new List<Filter>
        {
            new Filter
            {
                Name = $"tag:{tagName}",
                Values = new List<string>
                {
                    tagValue,
                },
            },
        };
        var request = new DescribeInstancesRequest
        {
            Filters = filters,
        };

        Console.WriteLine("\nShowing instances with tag: \"IncludeInList\" set to
\"Yes\".");
        var paginator = _amazonEC2.Paginators.DescribeInstances(request);

        await foreach (var response in paginator.Responses)
        {
            foreach (var reservation in response.Reservations)
            {
                foreach (var instance in reservation.Instances)
                {
                    Console.Write($"Instance ID: {instance.InstanceId} ");
                    Console.WriteLine($"\tCurrent State: {instance.State.Name}");
                }
            }
        }
    }

    /// <summary>
    /// Describe the instance types available.
    /// </summary>
    /// <returns>A list of instance type information.</returns>
    public async Task<List<InstanceTypeInfo>>
DescribeInstanceTypes(ArchitectureValues architecture)
    {
        var request = new DescribeInstanceTypesRequest();

        var filters = new List<Filter>
```

```
            { new Filter("processor-info.supported-architecture", new List<string>
{ architecture.ToString() }) };
        filters.Add(new Filter("instance-type", new() { "*.micro", "*.small" }));

        request.Filters = filters;
        var instanceTypes = new List<InstanceTypeInfo>();

        var paginator = _amazonEC2.Paginators.DescribeInstanceTypes(request);
        await foreach (var instanceType in paginator.InstanceTypes)
        {
            instanceTypes.Add(instanceType);
        }
        return instanceTypes;
    }

    /// <summary>
    /// Display the instance type information returned by
DescribeInstanceTypesAsync.
    /// </summary>
    /// <param name="instanceTypes">The list of instance type information.</param>
    public void DisplayInstanceTypeInfo(List<InstanceTypeInfo> instanceTypes)
    {
        instanceTypes.ForEach(type =>
        {
            Console.WriteLine($"{type.InstanceType}\t{type.MemoryInfo}");
        });
    }

    /// <summary>
    /// Get information about an Amazon EC2 key pair.
    /// </summary>
    /// <param name="keyPairName">The name of the key pair.</param>
    /// <returns>A list of key pair information.</returns>
    public async Task<List<KeyPairInfo>> DescribeKeyPairs(string keyPairName)
    {
        var request = new DescribeKeyPairsRequest();
        if (!string.IsNullOrEmpty(keyPairName))
        {
            request = new DescribeKeyPairsRequest
            {
                KeyNames = new List<string> { keyPairName }
            };
        }
        var response = await _amazonEC2.DescribeKeyPairsAsync(request);
```

```
        return response.KeyPairs.ToList();
    }


    /// <summary>
    /// Retrieve information for an Amazon EC2 security group.
    /// </summary>
    /// <param name="groupId">The Id of the Amazon EC2 security group.</param>
    /// <returns>A list of security group information.</returns>
    public async Task<List<SecurityGroup>> DescribeSecurityGroups(string groupId)
    {
        var request = new DescribeSecurityGroupsRequest();
        var groupIds = new List<string> { groupId };
        request.GroupIds = groupIds;

        var response = await _amazonEC2.DescribeSecurityGroupsAsync(request);
        return response.SecurityGroups;
    }

    /// <summary>
    /// Display the information returned by the call to
    /// DescribeSecurityGroupsAsync.
    /// </summary>
    /// <param name="securityGroup">A list of security group information.</param>
    public void DisplaySecurityGroupInfoAsync(SecurityGroup securityGroup)
    {
        Console.WriteLine($"{securityGroup.GroupName}");
        Console.WriteLine("Ingress permissions:");
        securityGroup.IpPermissions.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range => { Console.Write($"{range.CidrIp}
"); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));
```

```
            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
        Console.WriteLine("Egress permissions:");
        securityGroup.IpPermissionsEgress.ForEach(permission =>
        {
            Console.WriteLine($"\tFromPort: {permission.FromPort}");
            Console.WriteLine($"\tIpProtocol: {permission.IpProtocol}");

            Console.Write($"\tIpv4Ranges: ");
            permission.Ipv4Ranges.ForEach(range => { Console.Write($"{range.CidrIp}
"); });

            Console.WriteLine($"\n\tIpv6Ranges:");
            permission.Ipv6Ranges.ForEach(range =>
{ Console.Write($"{range.CidrIpv6} "); });

            Console.Write($"\n\tPrefixListIds: ");
            permission.PrefixListIds.ForEach(id => Console.Write($"{id.Id} "));

            Console.WriteLine($"\n\tTo Port: {permission.ToPort}");
        });
    }


    /// <summary>
    /// Disassociate an Elastic IP address from an EC2 instance.
    /// </summary>
    /// <param name="associationId">The association Id.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DisassociateIp(string associationId)
    {
        var response = await _amazonEC2.DisassociateAddressAsync(
            new DisassociateAddressRequest { AssociationId = associationId });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Retrieve a list of available Amazon Linux images.
    /// </summary>
    /// <returns>A list of image information.</returns>
    public async Task<List<Image>> GetEC2AmiList()
    {
        var filter = new Filter { Name = "architecture", Values = new List<string>
{ "x86_64" } };
```

```
        var filters = new List<Filter> { filter };
        var response = await _amazonEC2.DescribeImagesAsync(new
 DescribeImagesRequest { Filters = filters });
        return response.Images;
    }

    /// <summary>
    /// Reboot EC2 instances.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the instances that will be
 rebooted.</param>
    /// <returns>Async task.</returns>
    public async Task RebootInstances(string ec2InstanceId)
    {
        var request = new RebootInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.RebootInstancesAsync(request);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine("Instances successfully rebooted.");
        }
        else
        {
            Console.WriteLine("Could not reboot one or more instances.");
        }
    }

    /// <summary>
    /// Release an Elastic IP address.
    /// </summary>
    /// <param name="allocationId">The allocation Id of the Elastic IP address.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> ReleaseAddress(string allocationId)
    {
        var request = new ReleaseAddressRequest
        {
            AllocationId = allocationId
        };

        var response = await _amazonEC2.ReleaseAddressAsync(request);
```

```
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Create and run an EC2 instance.
    /// </summary>
    /// <param name="ImageId">The image Id of the image used as a basis for the
    /// EC2 instance.</param>
    /// <param name="instanceType">The instance type of the EC2 instance to
create.</param>
    /// <param name="keyName">The name of the key pair to associate with the
    /// instance.</param>
    /// <param name="groupId">The Id of the Amazon EC2 security group that will be
    /// allowed to interact with the new EC2 instance.</param>
    /// <returns>The instance Id of the new EC2 instance.</returns>
    public async Task<string> RunInstances(string imageId, string instanceType,
string keyName, string groupId)
    {
        var request = new RunInstancesRequest
        {
            ImageId = imageId,
            InstanceType = instanceType,
            KeyName = keyName,
            MinCount = 1,
            MaxCount = 1,
            SecurityGroupIds = new List<string> { groupId }
        };
        var response = await _amazonEC2.RunInstancesAsync(request);
        return response.Reservation.Instances[0].InstanceId;
    }


    /// <summary>
    /// Start an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the Amazon EC2 instance
    /// to start.</param>
    /// <returns>Async task.</returns>
    public async Task StartInstances(string ec2InstanceId)
    {
        var request = new StartInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };
```

```
        var response = await _amazonEC2.StartInstancesAsync(request);

        if (response.StartingInstances.Count > 0)
        {
            var instances = response.StartingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully started the EC2 instance with
instance ID: {i.InstanceId}.");
            });
        }
    }

    /// <summary>
    /// Stop an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance to
    /// stop.</param>
    /// <returns>Async task.</returns>
    public async Task StopInstances(string ec2InstanceId)
    {
        // In addition to the list of instance Ids, the
        // request can also include the following properties:
        //     Force      When true, forces the instances to
        //                stop but you must check the integrity
        //                of the file system. Not recommended on
        //                Windows instances.
        //     Hibernate  When true, hibernates the instance if the
        //                instance was enabled for hibernation when
        //                it was launched.
        var request = new StopInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId },
        };

        var response = await _amazonEC2.StopInstancesAsync(request);

        if (response.StoppingInstances.Count > 0)
        {
            var instances = response.StoppingInstances;
            instances.ForEach(i =>
            {
                Console.WriteLine($"Successfully stopped the EC2 Instance " +
```

```
                                    $"with InstanceID: {i.InstanceId}.");
            });
        }
    }

    /// <summary>
    /// Terminate an EC2 instance.
    /// </summary>
    /// <param name="ec2InstanceId">The instance Id of the EC2 instance
    /// to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task<List<InstanceStateChange>> TerminateInstances(string
ec2InstanceId)
    {
        var request = new TerminateInstancesRequest
        {
            InstanceIds = new List<string> { ec2InstanceId }
        };

        var response = await _amazonEC2.TerminateInstancesAsync(request);
        return response.TerminatingInstances;
    }

    /// <summary>
    /// Wait until an EC2 instance is in a specified state.
    /// </summary>
    /// <param name="instanceId">The instance Id.</param>
    /// <param name="stateName">The state to wait for.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitForInstanceState(string instanceId,
InstanceStateName stateName)
    {
        var request = new DescribeInstancesRequest
        {
            InstanceIds = new List<string> { instanceId }
        };

        // Wait until the instance is running.
        var hasState = false;
        do
        {
            // Wait 5 seconds.
            Thread.Sleep(5000);
```

```
            // Check for the desired state.
            var response = await _amazonEC2.DescribeInstancesAsync(request);
            var instance = response.Reservations[0].Instances[0];
            hasState = instance.State.Name == stateName;
            Console.Write(". ");
        } while (!hasState);

        return hasState;
    }

}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress
  - RunInstances
  - StartInstances
  - StopInstances
  - TerminateInstances
  - UnmonitorInstances

Exemplos do Amazon ECS usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon ECS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon ECS

O exemplo de código a seguir mostra como começar a usar o Amazon ECS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.ECS;
using Amazon.ECS.Model;
using Microsoft.Extensions.Hosting;

namespace ECSActions;

public class HelloECS
{
    static async System.Threading.Tasks.Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon ECS domain registration service.
        // Use your AWS profile name, or leave it blank to use the default profile.
```

```
        using var host = Host.CreateDefaultBuilder(args).Build();

        // Now the client is available for injection.
        var amazonECSClient = new AmazonECSClient();

        // You can use await and any of the async methods to get a response.
        var response = await amazonECSClient.ListClustersAsync(new
 ListClustersRequest { });

        Console.WriteLine($"Hello Amazon ECS! Following are some cluster ARNS
 available in the your aws account");
        Console.WriteLine();
        foreach (var arn in response.ClusterArns.Take(5))
        {
            Console.WriteLine($"\tARN: {arn}");
            Console.WriteLine($"Cluster Name: {arn.Split("/").Last()}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Listar clusters

O exemplo de código a seguir mostra como listar seus clusters do Amazon ECS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// List cluster ARNs available.
   /// </summary>
   /// <returns>The ARN list of clusters.</returns>
   public async Task<List<string>> GetClusterARNSAsync()
   {

       Console.WriteLine("Getting a list of all the clusters in your AWS
account...");
       List<string> clusterArnList = new List<string>();
       // Get a list of all the clusters in your AWS account
       try
       {

           var listClustersResponse = _ecsClient.Paginators.ListClusters(new
ListClustersRequest
           {
           });

           var clusterArns = listClustersResponse.ClusterArns;

           // Print the ARNs of the clusters
           await foreach (var clusterArn in clusterArns)
           {
               clusterArnList.Add(clusterArn);
           }

           if (clusterArnList.Count == 0)
           {
               _logger.LogWarning("No clusters found in your AWS account.");
           }
           return clusterArnList;
       }
       catch (Exception e)
       {
           _logger.LogError($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
           throw new Exception($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
       }
   }
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for .NET da API.

Liste serviços em um cluster

O exemplo de código a seguir mostra como listar os serviços do Amazon ECS em um cluster.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// List service ARNs available.
/// </summary>
/// <param name="clusterARN">The arn of the ECS cluster.</param>
/// <returns>The ARN list of services in given cluster.</returns>
public async Task<List<string>> GetServiceARNSAsync(string clusterARN)
{
    List<string> serviceArns = new List<string>();

    var request = new ListServicesRequest
    {
        Cluster = clusterARN
    };
    // Call the ListServices API operation and get the list of service ARNs
    var serviceList = _ecsClient.Paginators.ListServices(request);

    await foreach (var serviceARN in serviceList.ServiceArns)
    {
        if (serviceARN is null)
            continue;

        serviceArns.Add(serviceARN);
    }

    if (serviceArns.Count == 0)
    {
        _logger.LogWarning($"No services found in cluster {clusterARN} .");
    }
```

```
        return serviceArns;
    }
```

- Para obter detalhes da API, consulte ListServicesa Referência AWS SDK for .NET da API.

Liste tarefas em um cluster

O exemplo de código a seguir mostra como listar as tarefas do Amazon ECS em um cluster.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List task ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
    /// <returns>The ARN list of tasks in given cluster.</returns>
    public async Task<List<string>> GetTaskARNsAsync(string clusterARN)
    {
        // Set up the request to describe the tasks in the service
        var listTasksRequest = new ListTasksRequest
        {
            Cluster = clusterARN
        };
        List<string> taskArns = new List<string>();

        // Call the ListTasks API operation and get the list of task ARNs
        var tasks = _ecsClient.Paginators.ListTasks(listTasksRequest);

        await foreach (var task in tasks.TaskArns)
        {
            if (task is null)
                continue;
```

```
            taskArns.Add(task);
        }

        if (taskArns.Count == 0)
        {
            _logger.LogWarning("No tasks found in cluster: " + clusterARN);
        }

        return taskArns;
    }
```

- Para obter detalhes da API, consulte ListTasksa Referência AWS SDK for .NET da API.

Cenários

Obtenha informações de ARN para clusters, serviços e tarefas

O código de exemplo a seguir mostra como:

- Obtenha uma lista de todos os clusters.
- Obtenha serviços para um cluster.
- Obtenha tarefas para um cluster.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
using Amazon.ECS;
using ECSActions;
using Microsoft.Extensions.Hosting;
using Microsoft.Extensions.Logging;
using Microsoft.Extensions.Logging.Console;
using Microsoft.Extensions.Logging.Debug;
```

```
namespace ECSScenario;

public class ECSScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.


    This .NET example performs the following tasks:
        1. List ECS Cluster ARNs.
        2. List services in every cluster
        3. List Task ARNs in every cluster.
    */

    private static ILogger logger = null!;
    private static ECSWrapper _ecsWrapper = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
        .Build();

        ILoggerFactory loggerFactory = LoggerFactory.Create(builder =>
        {
            builder.AddConsole();
        });

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<ECSScenario>();

        var loggerECSWarpper = LoggerFactory.Create(builder =>
 { builder.AddConsole(); })
          .CreateLogger<ECSWrapper>();

        var amazonECSClient = new AmazonECSClient();
```

```
        _ecsWrapper = new ECSWrapper(amazonECSClient, loggerECSWarpper);

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon ECS example scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            await ListClusterARNs();
            await ListServiceARNs();
            await ListTaskARNs();

        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// List ECS Cluster ARNs
    /// </summary>
    private static async Task ListClusterARNs()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. List Cluster ARNs from ECS.");
        var arns = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var arn in arns)
        {
            Console.WriteLine($"Cluster arn: {arn}");
            Console.WriteLine($"Cluster name: {arn.Split("/").Last()}");
        }

        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// List services in every cluster
    /// </summary>
    private static async Task ListServiceARNs()
    {
        Console.WriteLine(new string('-', 80));
```

```
        Console.WriteLine($"2. List Service ARNs in every cluster.");
        var clusterARNs = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var clusterARN in clusterARNs)
        {
            Console.WriteLine($"Getting services for cluster name:
{clusterARN.Split("/").Last()}");
            Console.WriteLine(new string('.', 5));


            var serviceARNs = await _ecsWrapper.GetServiceARNSAsync(clusterARN);

            foreach (var serviceARN in serviceARNs)
            {
                Console.WriteLine($"Service arn: {serviceARN}");
                Console.WriteLine($"Service name: {serviceARN.Split("/").Last()}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }


    /// <summary>
    /// List tasks in every cluster
    /// </summary>
    private static async Task ListTaskARNs()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. List Task ARNs in every cluster.");
        var clusterARNs = await _ecsWrapper.GetClusterARNSAsync();

        foreach (var clusterARN in clusterARNs)
        {
            Console.WriteLine($"Getting tasks for cluster name:
{clusterARN.Split("/").Last()}");
            Console.WriteLine(new string('.', 5));

            var taskARNs = await _ecsWrapper.GetTaskARNsAsync(clusterARN);

            foreach (var taskARN in taskARNs)
            {
                Console.WriteLine($"Task arn: {taskARN}");
            }
```

```
        }
        Console.WriteLine(new string('-', 80));
    }
}
```

Métodos de encapsulamento que são chamados pelo cenário para gerenciar as ações do Amazon ECS.

```
using Amazon.ECS;
using Amazon.ECS.Model;
using Microsoft.Extensions.Logging;

namespace ECSActions;

public class ECSWrapper
{
    private readonly AmazonECSClient _ecsClient;
    private readonly ILogger<ECSWrapper> _logger;

    /// <summary>
    /// Constructor for the ECS wrapper.
    /// </summary>
    /// <param name="ecsClient">The injected ECS client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public ECSWrapper(AmazonECSClient ecsClient, ILogger<ECSWrapper> logger)

    {
        _logger = logger;
        _ecsClient = ecsClient;
    }

    /// <summary>
    /// List cluster ARNs available.
    /// </summary>
    /// <returns>The ARN list of clusters.</returns>
    public async Task<List<string>> GetClusterARNSAsync()
    {

        Console.WriteLine("Getting a list of all the clusters in your AWS
 account...");
        List<string> clusterArnList = new List<string>();
        // Get a list of all the clusters in your AWS account
```

```
        try
        {

            var listClustersResponse = _ecsClient.Paginators.ListClusters(new
ListClustersRequest
            {
            });

            var clusterArns = listClustersResponse.ClusterArns;

            // Print the ARNs of the clusters
            await foreach (var clusterArn in clusterArns)
            {
                clusterArnList.Add(clusterArn);
            }

            if (clusterArnList.Count == 0)
            {
                _logger.LogWarning("No clusters found in your AWS account.");
            }
            return clusterArnList;
        }
        catch (Exception e)
        {
            _logger.LogError($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
            throw new Exception($"An error occurred while getting a list of all the
clusters in your AWS account. {e.InnerException}");
        }
    }

    /// <summary>
    /// List service ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
    /// <returns>The ARN list of services in given cluster.</returns>
    public async Task<List<string>> GetServiceARNSAsync(string clusterARN)
    {
        List<string> serviceArns = new List<string>();

        var request = new ListServicesRequest
        {
            Cluster = clusterARN
        };
```

```
        // Call the ListServices API operation and get the list of service ARNs
        var serviceList = _ecsClient.Paginators.ListServices(request);

        await foreach (var serviceARN in serviceList.ServiceArns)
        {
            if (serviceARN is null)
                continue;

            serviceArns.Add(serviceARN);
        }

        if (serviceArns.Count == 0)
        {
            _logger.LogWarning($"No services found in cluster {clusterARN} .");
        }

        return serviceArns;
    }

    /// <summary>
    /// List task ARNs available.
    /// </summary>
    /// <param name="clusterARN">The arn of the ECS cluster.</param>
    /// <returns>The ARN list of tasks in given cluster.</returns>
    public async Task<List<string>> GetTaskARNsAsync(string clusterARN)
    {
        // Set up the request to describe the tasks in the service
        var listTasksRequest = new ListTasksRequest
        {
            Cluster = clusterARN
        };
        List<string> taskArns = new List<string>();

        // Call the ListTasks API operation and get the list of task ARNs
        var tasks = _ecsClient.Paginators.ListTasks(listTasksRequest);

        await foreach (var task in tasks.TaskArns)
        {
            if (task is null)
                continue;


            taskArns.Add(task);
        }
```

```
        if (taskArns.Count == 0)
        {
            _logger.LogWarning("No tasks found in cluster: " + clusterARN);
        }

        return taskArns;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - ListClusters
  - ListServices
  - ListTasks

Exemplos do Elastic Load Balancing usando o AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Elastic Load Balancing.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um receptor para o balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como criar um receptor que encaminha solicitações de um balanceador de carga do ELB para um grupo de destino.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
   /// and forwards requests to the specified target group.
   /// </summary>
   /// <param name="name">The name for the new load balancer.</param>
   /// <param name="subnetIds">Subnets for the load balancer.</param>
   /// <param name="targetGroup">Target group for forwarded requests.</param>
   /// <returns>The new LoadBalancer object.</returns>
   public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
   {
       var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
           new CreateLoadBalancerRequest()
           {
               Name = name,
               Subnets = subnetIds
           });
       var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

       // Wait for load balancer to be available.
       var loadBalancerReady = false;
       while (!loadBalancerReady)
       {
           try
           {
               var describeResponse =
```

```
                    await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for .NET da API.

Criar um grupo de destino

O exemplo de código a seguir mostra como criar um grupo de destino ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened times
 and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer exists.</
param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
```

```
        return targetGroup;
    }
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for .NET da API.

Criar um Application Load Balancer

O exemplo de código a seguir mostra como criar um Application Load Balancer do ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
        var loadBalancerReady = false;
```

```
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
                    await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for .NET da API.

Excluir um balanceador de carga

O exemplo de código a seguir mostra como excluir um balanceador de carga do ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
```

```
        }
    }
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for .NET da API.

Excluir um grupo de destino

O exemplo de código a seguir mostra como excluir um grupo de destino do ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn = targetArn });
```

```
                Console.WriteLine($"Deleted load balancing target group
{groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for .NET da API.

Obter o endpoint de um balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como obter um endpoint de um balanceador de carga ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
loadBalancerName)
    {
```

```
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for .NET da API.

Obter a integridade de um grupo de destino

O exemplo de código a seguir mostra como obter a integridade de instâncias em um grupo de destino do ELB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
```

```
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }
```

- Para obter detalhes da API, consulte DescribeTargetHealtha Referência AWS SDK for .NET da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.

- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
    static async Task Main(string[] args)
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();


        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
```

```
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
```

```
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper = host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several AWS
resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways to
make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");
```

```
        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide book,
movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each contain
a Python web server.");
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.

        Console.WriteLine(
            $"Creating an EC2 launch template that runs 'server_startup_script.sh'
when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the `server.py`
script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
```

```
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3, _autoScalerWrapper.GroupName,
zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or continue
with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            + "defines how the load balancer connects to instances. The load
balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
instances in the group.");
```

```
        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
 _autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGroupN
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.LoadB
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper.Lo
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();

            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port, ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for your
 default VPC must\n"
```

```
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management Console.
\n");

                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound traffic from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port, ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
 ipString);
                }
            }
            loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
            Console.WriteLine("Your load balancer is ready. You can access it by
 browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
 endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
 configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
 endpoint:\n");
```

```
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite of
these failures.");
        Console.WriteLine(new string('-', 88));
        Console.WriteLine("At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
let's set this parameter to name a non-existent table.\n");
```

```
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
 checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service fails,
 the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
 customer with a somewhat better experience than failure.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
 "static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
 checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
 _smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in the
 target group so that it can't\n" +
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
 _autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
```

```
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile that
contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo, a
deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not for
Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the Auto
Scaling group when a dependent service fails.");

        Console.WriteLine("\nBy implementing deep health checks, the load balancer
can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two for
the load balancer to detect the unhealthy");
```

```
        Console.WriteLine("instance. Sending a GET request to the load balancer
 endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
 rotation.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by an
 auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler start
 a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
 instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a successful
 recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the load
 balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance typically
 takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
 instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
 checks mean all instances report as unhealthy.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
 continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
 return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
```

```
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account, we
can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
resources? (y/n) "))
        {
            await
_elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBalanc
            await
_elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGroup
            await
_autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupName)
            await
_autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
            await
_autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
_recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
```

```
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
```

```
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with a
specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
```

```
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to the
role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                     "\"Service\": [" +
                                         "\"ec2.amazonaws.com\"" +
                                     "]" +
                                     "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                            "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
```

```
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
```

```
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
```

```
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }

    /// <summary>
    /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
    /// The launch template specifies a Bash script in its user data field that runs
after
    /// the instance is started. This script installs the Python packages and starts
a Python
    /// web server on the instance.
    /// </summary>
    /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
    /// <param name="instancePolicyPath">The path to a permissions policy to create
and attach to the profile.</param>
```

```
    /// <returns>The template object.</returns>
    public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
    {
        await CreateKeyPair(_keyPairName);
        await CreateInstanceProfileWithName(_instancePolicyName, _instanceRoleName,
_instanceProfileName, instancePolicyPath);

        var startServerText = await File.ReadAllTextAsync(startupScriptPath);
        var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

        var amiLatest = await _amazonSsm.GetParameterAsync(
            new GetParameterRequest() { Name = _amiParam });
        var amiId = amiLatest.Parameter.Value;
        var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
            new CreateLaunchTemplateRequest()
            {
                LaunchTemplateName = _launchTemplateName,
                LaunchTemplateData = new RequestLaunchTemplateData()
                {
                    InstanceType = _instanceType,
                    ImageId = amiId,
                    IamInstanceProfile =
                        new
                            LaunchTemplateIamInstanceProfileSpecificationRequest()
                        {
                            Name = _instanceProfileName
                        },
                    KeyName = _keyPairName,
                    UserData = System.Convert.ToBase64String(plainTextBytes)
                }
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
```

```
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with size
 {groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
 exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
```

```
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
```

```
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await _amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
```

```
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }
```

```
    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
    /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
    /// <returns>Async task.</returns>
    public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
    {
        await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
                new ReplaceIamInstanceProfileAssociationRequest()
                {
                    AssociationId = associationId,
                    IamInstanceProfile = new IamInstanceProfileSpecification()
                    {
                        Name = credsProfileName
                    }
```

```
                });
        // Allow time before resetting.
        Thread.Sleep(25000);
        var instanceReady = false;
        var retries = 5;
        while (retries-- > 0 && !instanceReady)
        {
            await _amazonEc2.RebootInstancesAsync(
                new RebootInstancesRequest(new List<string>() { instanceId }));
            Thread.Sleep(10000);

            var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
                new DescribeInstanceInformationRequest());
            // Get the entire list using the paginator.
            await foreach (var instance in
instancesPaginator.InstanceInformationList)
            {
                instanceReady = instance.InstanceId == instanceId;
                if (instanceReady)
                {
                    break;
                }
            }
        }
        Console.WriteLine($"Sending restart command to instance {instanceId}");
        await _amazonSsm.SendCommandAsync(
            new SendCommandRequest()
            {
                InstanceIds = new List<string>() { instanceId },
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
```

```
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for {instanceId}.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
```

```
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
```

```
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the calling
computer.
    /// This can be done by allowing ingress from this computer's IP address.
    /// In some situations, such as connecting from a corporate network, you must
instead specify
    /// a prefix list Id. You can also temporarily open the port to any IP address
while running this example.
    /// If you do, be sure to remove public access when you're done.
    /// </summary>
    /// <param name="vpc">The group to check.</param>
    /// <param name="port">The port to verify.</param>
    /// <param name="ipAddress">This computer's IP address.</param>
    /// <returns>True if the ip address is allowed on the group.</returns>
    public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
    {
        var portIsOpen = false;
        foreach (var ipPermission in group.IpPermissions)
```

```
        {
            if (ipPermission.FromPort == port)
            {
                foreach (var ipRange in ipPermission.Ipv4Ranges)
                {
                    var cidr = ipRange.CidrIp;
                    if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                    {
                        portIsOpen = true;
                    }
                }

                if (ipPermission.PrefixListIds.Any())
                {
                    portIsOpen = true;
                }

                if (!portIsOpen)
                {
                    Console.WriteLine("The inbound rule does not appear to be open
to either this computer's IP\n" +
                                      "address, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
                }
                else
                {
                    break;
                }
            }
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
```

```
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName, string
 targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
 loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
```

```
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
    public async Task<List<TargetHealthDescription>>
CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
```

```
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened times
 and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer exists.</
param>
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
 ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
 _amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
```

```
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
        var loadBalancerReady = false;
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
                    await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;
```

```
                loadBalancerReady = loadBalancerState ==
 LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
```

```
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
```

```
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
                    new DeleteTargetGroupRequest() { TargetGroupArn = targetArn });
                Console.WriteLine($"Deleted load balancing target group
{groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
```

```
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books, movies,
 and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
```

```
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };
```

```
            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await File.ReadAllTextAsync(recommendationsPath);
        var records =
            JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
```

```
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-architecture-
table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";
```

```
    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }

    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

EventBridge exemplos usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET with EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá EventBridge

O exemplo de código a seguir mostra como começar a usar o EventBridge.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.EventBridge;
using Amazon.EventBridge.Model;

namespace EventBridgeActions;

public static class HelloEventBridge
{
    static async Task Main(string[] args)
    {
        var eventBridgeClient = new AmazonEventBridgeClient();
```

```
        Console.WriteLine($"Hello Amazon EventBridge! Following are some of your
 EventBuses:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five event buses.
        var response = await eventBridgeClient.ListEventBusesAsync(
            new ListEventBusesRequest()
            {
                Limit = 5
            });

        foreach (var eventBus in response.EventBuses)
        {
            Console.WriteLine($"\tEventBus: {eventBus.Name}");
            Console.WriteLine($"\tArn: {eventBus.Arn}");
            Console.WriteLine($"\tPolicy: {eventBus.Policy}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListEventBusesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione um tópico do Amazon SNS como um destino para uma regra.

```
    /// <summary>
    /// Add an Amazon SNS target topic to a rule.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <param name="targetArn">The ARN of the Amazon SNS target.</param>
    /// <param name="eventBusArn">The optional event bus name, uses default if
empty.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> AddSnsTargetToRule(string ruleName, string targetArn,
string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        // Create the list of targets and add a new target.
        var targets = new List<Target>
        {
            new Target()
            {
                Arn = targetArn,
                Id = targetID
            }
        };

        // Add the targets to the rule.
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });

        if (response.FailedEntryCount > 0)
```

```
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }

        return targetID;
    }
```

Adicione um transformador de entrada a um destino para uma regra.

```
    /// <summary>
    /// Update an Amazon S3 object created rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the default
event bus.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateS3UploadRuleTargetWithTransform(string ruleName,
string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
                InputTransformer = new InputTransformer()
                {
                    InputPathsMap = new Dictionary<string, string>()
                    {
                        {"bucket", "$.detail.bucket.name"},
                        {"time", "$.time"}
                    },
                    InputTemplate = "\"Notification: an object was uploaded to
bucket <bucket> at <time>.\""
```

```
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }
        return targetID;
    }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for .NET da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
    /// <summary>
```

```
    /// Create a new event rule that triggers when an Amazon S3 object is created in
 a bucket.
    /// </summary>
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="ruleName">The name to give the rule.</param>
    /// <param name="bucketName">The name of the bucket to trigger the event.</
param>
    /// <returns>The ARN of the new rule.</returns>
    public async Task<string> PutS3UploadRule(string roleArn, string ruleName,
 string bucketName)
    {
        string eventPattern = "{" +
                                "\"source\": [\"aws.s3\"]," +
                                    "\"detail-type\": [\"Object Created\"]," +
                                    "\"detail\": {" +
                                        "\"bucket\": {" +
                                            "\"name\": [\"" + bucketName + "\"]" +
                                        "}" +
                                    "}" +
                                "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Example S3 upload rule for EventBridge",
                RoleArn = roleArn,
                EventPattern = eventPattern
            });

        return response.RuleArn;
    }
```

Crie uma regra que use um padrão personalizado.

```
    /// <summary>
    /// Update a rule to use a custom defined event pattern.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <returns>The ARN of the updated rule.</returns>
    public async Task<string> UpdateCustomEventPattern(string ruleName)
    {
```

```
        string customEventsPattern = "{" +
                                     "\"source\": [\"ExampleSource\"]," +
                                     "\"detail-type\": [\"ExampleType\"]" +
                                     "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Custom test rule",
                EventPattern = customEventsPattern
            });

        return response.RuleArn;
    }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for .NET da API.

Excluir uma regra

O exemplo de código a seguir mostra como excluir uma EventBridge regra da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma regra pelo nome.

```
    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteRuleByName(string ruleName)
    {
        var response = await _amazonEventBridge.DeleteRuleAsync(
```

```
            new DeleteRuleRequest()
            {
                Name = ruleName
            });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRulea Referência AWS SDK for .NET da API.

Descrever uma regra

O exemplo de código a seguir mostra como descrever uma EventBridge regra da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o estado de uma regra usando a descrição da regra.

```
    /// <summary>
    /// Get the state for a rule by the rule name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="eventBusName">The optional name of the event bus. If empty,
uses the default event bus.</param>
    /// <returns>The state of the rule.</returns>
    public async Task<RuleState> GetRuleStateByRuleName(string ruleName, string?
eventBusName = null)
    {
        var ruleResponse = await _amazonEventBridge.DescribeRuleAsync(
            new DescribeRuleRequest()
            {
                Name = ruleName,
                EventBusName = eventBusName
            });
        return ruleResponse.State;
```

```
    }
```

- Para obter detalhes da API, consulte DescribeRulea Referência AWS SDK for .NET da API.

Desabilitar uma regra

O exemplo de código a seguir mostra como desativar uma EventBridge regra da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desabilite uma regra pelo nome da regra.

```
/// <summary>
/// Disable a particular rule on an event bus.
/// </summary
/// <param name="ruleName">The name of the rule.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DisableRuleByName(string ruleName)
{
    var ruleResponse = await _amazonEventBridge.DisableRuleAsync(
        new DisableRuleRequest()
        {
            Name = ruleName
        });
    return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DisableRulea Referência AWS SDK for .NET da API.

Habilitar uma regra

O exemplo de código a seguir mostra como habilitar uma EventBridge regra da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilite uma regra pelo nome da regra.

```
/// <summary>
/// Enable a particular rule on an event bus.
/// </summary>
/// <param name="ruleName">The name of the rule.</param>
/// <returns>True if successful.</returns>
public async Task<bool> EnableRuleByName(string ruleName)
{
    var ruleResponse = await _amazonEventBridge.EnableRuleAsync(
        new EnableRuleRequest()
        {
            Name = ruleName
        });
    return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte EnableRulea Referência AWS SDK for .NET da API.

Listar nomes de regras para um destino

O exemplo de código a seguir mostra como listar nomes de EventBridge regras da Amazon para um alvo.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos os nomes das regras usando o destino.

```
/// <summary>
/// List names of all rules matching a target.
/// </summary>
/// <param name="targetArn">The ARN of the target.</param>
/// <returns>The list of rule names.</returns>
public async Task<List<string>> ListAllRuleNamesByTarget(string targetArn)
{
    var results = new List<string>();
    var request = new ListRuleNamesByTargetRequest()
    {
        TargetArn = targetArn
    };
    ListRuleNamesByTargetResponse response;
    do
    {
        response = await _amazonEventBridge.ListRuleNamesByTargetAsync(request);
        results.AddRange(response.RuleNames);
        request.NextToken = response.NextToken;

    } while (response.NextToken is not null);

    return results;
}
```

- Para obter detalhes da API, consulte ListRuleNamesByTargeta Referência AWS SDK for .NET da API.

Listar regras

O exemplo de código a seguir mostra como listar EventBridge as regras da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todas as regras para um barramento de eventos.

```
    /// <summary>
    /// List the rules on an event bus.
    /// </summary>
    /// <param name="eventBusArn">The optional ARN of the event bus. If empty, uses
the default event bus.</param>
    /// <returns>The list of rules.</returns>
    public async Task<List<Rule>> ListAllRulesForEventBus(string? eventBusArn =
null)
    {
        var results = new List<Rule>();
        var request = new ListRulesRequest()
        {
            EventBusName = eventBusArn
        };
        // Get all of the pages of rules.
        ListRulesResponse response;
        do
        {
            response = await _amazonEventBridge.ListRulesAsync(request);
            results.AddRange(response.Rules);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }
```

- Para obter detalhes da API, consulte ListRulesa Referência AWS SDK for .NET da API.

Listar destinos para uma regra

O exemplo de código a seguir mostra como listar EventBridge alvos da Amazon para uma regra.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste todos os destinos para uma regra usando o nome da regra.

```
/// <summary>
/// List all of the targets matching a rule by name.
/// </summary>
/// <param name="ruleName">The name of the rule.</param>
/// <returns>The list of targets.</returns>
public async Task<List<Target>> ListAllTargetsOnRule(string ruleName)
{
    var results = new List<Target>();
    var request = new ListTargetsByRuleRequest()
    {
        Rule = ruleName
    };
    ListTargetsByRuleResponse response;
    do
    {
        response = await _amazonEventBridge.ListTargetsByRuleAsync(request);
        results.AddRange(response.Targets);
        request.NextToken = response.NextToken;

    } while (response.NextToken is not null);

    return results;
}
```

- Para obter detalhes da API, consulte ListTargetsByRulea Referência AWS SDK for .NET da API.

Remover destinos de uma regra

O exemplo de código a seguir mostra como remover EventBridge alvos da Amazon de uma regra.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remova todos os destinos de uma regra usando o nome da regra.

```
    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> RemoveAllTargetsFromRule(string ruleName)
    {
        var targetIds = new List<string>();
        var request = new ListTargetsByRuleRequest()
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse targetsResponse;
        do
        {
            targetsResponse = await
_amazonEventBridge.ListTargetsByRuleAsync(request);
            targetIds.AddRange(targetsResponse.Targets.Select(t => t.Id));
            request.NextToken = targetsResponse.NextToken;

        } while (targetsResponse.NextToken is not null);

        var removeResponse = await _amazonEventBridge.RemoveTargetsAsync(
            new RemoveTargetsRequest()
            {
                Rule = ruleName,
                Ids = targetIds
            });

        if (removeResponse.FailedEntryCount > 0)
        {
            removeResponse.FailedEntries.ForEach(e =>
            {
```

```
                _logger.LogError(
                    $"Failed to remove target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }

        return removeResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte RemoveTargetsa Referência AWS SDK for .NET da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie um evento que corresponda a um padrão personalizado para uma regra.

```
    /// <summary>
    /// Add an event to the event bus that includes an email, message, and time.
    /// </summary>
    /// <param name="email">The email to use in the event detail of the custom
event.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutCustomEmailEvent(string email)
    {
        var eventDetail = new
        {
            UserEmail = email,
            Message = "This event was generated by example code.",
            UtcTime = DateTime.UtcNow.ToString("g")
        };
        var response = await _amazonEventBridge.PutEventsAsync(
            new PutEventsRequest()
```

```
            {
                Entries = new List<PutEventsRequestEntry>()
                {
                    new PutEventsRequestEntry()
                    {
                        Source = "ExampleSource",
                        Detail = JsonSerializer.Serialize(eventDetail),
                        DetailType = "ExampleType"
                    }
                }
            });

        return response.FailedEntryCount == 0;
    }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for .NET da API.

Cenários

Conceitos básicos de regras e destinos

O código de exemplo a seguir mostra como:

- Criar uma regra e adicione um destino a ela.
- Habilitar e desabilitar regras.
- Listar e atualizar regras e destinos.
- Enviar os eventos e limpar os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public class EventBridgeScenario
```

```
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks with Amazon EventBridge:
    - Create a rule.
    - Add a target to a rule.
    - Enable and disable rules.
    - List rules and targets.
    - Update rules and targets.
    - Send events.
    - Delete the rule.
    */

    private static ILogger logger = null!;
    private static EventBridgeWrapper _eventBridgeWrapper = null!;
    private static IConfiguration _configuration = null!;

    private static IAmazonIdentityManagementService? _iamClient = null!;
    private static IAmazonSimpleNotificationService? _snsClient = null!;
    private static IAmazonS3 _s3Client = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EventBridge.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonEventBridge>()
            .AddAWSService<IAmazonIdentityManagementService>()
            .AddAWSService<IAmazonS3>()
            .AddAWSService<IAmazonSimpleNotificationService>()
            .AddTransient<EventBridgeWrapper>()
            )
            .Build();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
```

```
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<EventBridgeScenario>();

        ServicesSetup(host);

        string topicArn = "";
        string roleArn = "";

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Welcome to the Amazon EventBridge example scenario.");
        Console.WriteLine(new string('-', 80));

        try
        {
            roleArn = await CreateRole();

            await CreateBucketWithEventBridgeEvents();

            await AddEventRule(roleArn);

            await ListEventRules();

            topicArn = await CreateSnsTopic();

            var email = await SubscribeToSnsTopic(topicArn);

            await AddSnsTarget(topicArn);

            await ListTargets();

            await ListRulesForTarget(topicArn);

            await UploadS3File(_s3Client);

            await ChangeRuleState(false);

            await GetRuleState();

            await UpdateSnsEventRule(topicArn);
```

```
            await ChangeRuleState(true);

            await UploadS3File(_s3Client);

            await UpdateToCustomRule(topicArn);

            await TriggerCustomRule(email);

            await CleanupResources(topicArn);
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
            await CleanupResources(topicArn);
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("The Amazon EventBridge example scenario is complete.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _eventBridgeWrapper =
host.Services.GetRequiredService<EventBridgeWrapper>();
        _snsClient =
host.Services.GetRequiredService<IAmazonSimpleNotificationService>();
        _s3Client = host.Services.GetRequiredService<IAmazonS3>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
    }

    /// <summary>
    /// Create a role to be used by EventBridge.
    /// </summary>
    /// <returns>The role Amazon Resource Name (ARN).</returns>
    public static async Task<string> CreateRole()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Creating a role to use with EventBridge and attaching
managed policy AmazonEventBridgeFullAccess.");
```

```
        Console.WriteLine(new string('-', 80));

        var roleName = _configuration["roleName"];

        var assumeRolePolicy = "{" +
                                   "\"Version\": \"2012-10-17\"," +
                                   "\"Statement\": [{" +
                                   "\"Effect\": \"Allow\"," +
                                   "\"Principal\": {" +
                                   $"\"Service\": \"events.amazonaws.com\"" +
                                   "}," +
                                   "\"Action\": \"sts:AssumeRole\"" +
                                   "}]" +
                                   "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
                RoleName = roleName
            });

        await _iamClient.AttachRolePolicyAsync(
            new AttachRolePolicyRequest()
            {
                PolicyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess",
                RoleName = roleName
            });
        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        return roleResult.Role.Arn;
    }

    /// <summary>
    /// Create an Amazon Simple Storage Service (Amazon S3) bucket with EventBridge
events enabled.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CreateBucketWithEventBridgeEvents()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Creating an S3 bucket with EventBridge events enabled.");
```

```
        var testBucketName = _configuration["testBucketName"];

        var bucketExists = await
Amazon.S3.Util.AmazonS3Util.DoesS3BucketExistV2Async(_s3Client,
            testBucketName);

        if (!bucketExists)
        {
            await _s3Client.PutBucketAsync(new PutBucketRequest()
            {
                BucketName = testBucketName,
                UseClientRegion = true
            });
        }

        await _s3Client.PutBucketNotificationAsync(new
PutBucketNotificationRequest()
        {
            BucketName = testBucketName,
            EventBridgeConfiguration = new EventBridgeConfiguration()
        });

        Console.WriteLine($"\tAdded bucket {testBucketName} with EventBridge events
enabled.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create and upload a file to an S3 bucket to trigger an event.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task UploadS3File(IAmazonS3 s3Client)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Uploading a file to the test bucket. This will trigger a
subscription email.");

        var testBucketName = _configuration["testBucketName"];

        var fileName = $"example_upload_{DateTime.UtcNow.Ticks}.txt";

        // Create the file if it does not already exist.
        if (!File.Exists(fileName))
```

```
        {
            await using StreamWriter sw = File.CreateText(fileName);
            await sw.WriteLineAsync(
                "This is a sample file for testing uploads.");
        }

        await s3Client.PutObjectAsync(new PutObjectRequest()
        {
            FilePath = fileName,
            BucketName = testBucketName
        });

        Console.WriteLine($"\tPress Enter to continue.");
        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create an Amazon Simple Notification Service (Amazon SNS) topic to use as an
EventBridge target.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> CreateSnsTopic()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "Creating an Amazon Simple Notification Service (Amazon SNS) topic for
email subscriptions.");

        var topicName = _configuration["topicName"];

        string topicPolicy = "{" +
                             "\"Version\": \"2012-10-17\"," +
                             "\"Statement\": [{" +
                             "\"Sid\": \"EventBridgePublishTopic\"," +
                             "\"Effect\": \"Allow\"," +
                             "\"Principal\": {" +
                             $"\"Service\": \"events.amazonaws.com\"" +
                             "}," +
                             "\"Resource\": \"*\"," +
                             "\"Action\": \"sns:Publish\"" +
                             "}]" +
                             "}";
```

```
        var topicAttributes = new Dictionary<string, string>()
        {
            { "Policy", topicPolicy }
        };

        var topicResponse = await _snsClient!.CreateTopicAsync(new
CreateTopicRequest()
        {
            Name = topicName,
            Attributes = topicAttributes

        });

        Console.WriteLine($"\tAdded topic {topicName} for email subscriptions.");

        Console.WriteLine(new string('-', 80));

        return topicResponse.TopicArn;
    }

    /// <summary>
    /// Subscribe a user email to an SNS topic.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
    /// <returns>The user's email.</returns>
    private static async Task<string> SubscribeToSnsTopic(string topicArn)
    {
        Console.WriteLine(new string('-', 80));


        string email = "";
        while (string.IsNullOrEmpty(email))
        {
            Console.WriteLine("Enter your email to subscribe to the Amazon SNS
topic:");
            email = Console.ReadLine()!;
        }

        var subscriptions = new List<string>();
        var paginatedSubscriptions =
_snsClient!.Paginators.ListSubscriptionsByTopic(
            new ListSubscriptionsByTopicRequest()
            {
```

```
                TopicArn = topicArn
            });

        // Get the entire list using the paginator.
        await foreach (var subscription in paginatedSubscriptions.Subscriptions)
        {
            subscriptions.Add(subscription.Endpoint);
        }

        if (subscriptions.Contains(email))
        {
            Console.WriteLine($"\tYour email is already subscribed.");
            Console.WriteLine(new string('-', 80));
            return email;
        }

        await _snsClient.SubscribeAsync(new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "email",
            Endpoint = email
        });

        Console.WriteLine($"Use the link in the email you received to confirm your
subscription, then press Enter to continue.");

        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
        return email;
    }

    /// <summary>
    /// Add a rule which triggers when a file is uploaded to an S3 bucket.
    /// </summary>
    /// <param name="roleArn">The ARN of the role used by EventBridge.</param>
    /// <returns>Async task.</returns>
    private static async Task AddEventRule(string roleArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Creating an EventBridge event that sends an email when an
Amazon S3 object is created.");

        var eventRuleName = _configuration["eventRuleName"];
```

```
        var testBucketName = _configuration["testBucketName"];

        await _eventBridgeWrapper.PutS3UploadRule(roleArn, eventRuleName,
testBucketName);
        Console.WriteLine($"\tAdded event rule {eventRuleName} for bucket
{testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Add an SNS target to the rule.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
    /// <returns>Async task.</returns>
    private static async Task AddSnsTarget(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Adding a target to the rule to that sends an email when
the rule is triggered.");

        var eventRuleName = _configuration["eventRuleName"];
        var testBucketName = _configuration["testBucketName"];
        var topicName = _configuration["topicName"];
        await _eventBridgeWrapper.AddSnsTargetToRule(eventRuleName, topicArn);
        Console.WriteLine($"\tAdded event rule {eventRuleName} with Amazon SNS
target {topicName} for bucket {testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List the event rules on the default event bus.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListEventRules()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Current event rules:");

        var rules = await _eventBridgeWrapper.ListAllRulesForEventBus();
        rules.ForEach(r => Console.WriteLine($"\tRule: {r.Name} Description:
{r.Description} State: {r.State}"));
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Update the event target to use a transform.
    /// </summary>
    /// <param name="topicArn">The SNS topic ARN target to update.</param>
    /// <returns>Async task.</returns>
    private static async Task UpdateSnsEventRule(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Let's update the event target with a transform.");

        var eventRuleName = _configuration["eventRuleName"];
        var testBucketName = _configuration["testBucketName"];

        await
_eventBridgeWrapper.UpdateS3UploadRuleTargetWithTransform(eventRuleName, topicArn);
        Console.WriteLine($"\tUpdated event rule {eventRuleName} with Amazon SNS
target {topicArn} for bucket {testBucketName}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Update the rule to use a custom event pattern.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task UpdateToCustomRule(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Updating the event pattern to be triggered by a custom
event instead.");

        var eventRuleName = _configuration["eventRuleName"];

        await _eventBridgeWrapper.UpdateCustomEventPattern(eventRuleName);

        Console.WriteLine($"\tUpdated event rule {eventRuleName} to custom
pattern.");
        await _eventBridgeWrapper.UpdateCustomRuleTargetWithTransform(eventRuleName,
            topicArn);

        Console.WriteLine($"\tUpdated event target {topicArn}.");
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Send rule events for a custom rule using the user's email address.
    /// </summary>
    /// <param name="email">The email address to include.</param>
    /// <returns>Async task.</returns>
    private static async Task TriggerCustomRule(string email)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Sending an event to trigger the rule. This will trigger a
subscription email.");

        await _eventBridgeWrapper.PutCustomEmailEvent(email);

        Console.WriteLine($"\tEvents have been sent. Press Enter to continue.");
        Console.ReadLine();

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List all of the targets for a rule.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListTargets()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("List all of the targets for a particular rule.");

        var eventRuleName = _configuration["eventRuleName"];
        var targets = await _eventBridgeWrapper.ListAllTargetsOnRule(eventRuleName);
        targets.ForEach(t => Console.WriteLine($"\tTarget: {t.Arn} Id: {t.Id} Input:
{t.Input}"));

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List all of the rules for a particular target.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic.</param>
```

```
    /// <returns>Async task.</returns>
    private static async Task ListRulesForTarget(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("List all of the rules for a particular target.");

        var rules = await _eventBridgeWrapper.ListAllRuleNamesByTarget(topicArn);
        rules.ForEach(r => Console.WriteLine($"\tRule: {r}"));

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Enable or disable a particular rule.
    /// </summary>
    /// <param name="isEnabled">True to enable the rule, otherwise false.</param>
    /// <returns>Async task.</returns>
    private static async Task ChangeRuleState(bool isEnabled)
    {
        Console.WriteLine(new string('-', 80));
        var eventRuleName = _configuration["eventRuleName"];

        if (!isEnabled)
        {
            Console.WriteLine($"Disabling the rule: {eventRuleName}");
            await _eventBridgeWrapper.DisableRuleByName(eventRuleName);
        }
        else
        {
            Console.WriteLine($"Enabling the rule: {eventRuleName}");
            await _eventBridgeWrapper.EnableRuleByName(eventRuleName);
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Get the current state of the rule.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetRuleState()
    {
        Console.WriteLine(new string('-', 80));
        var eventRuleName = _configuration["eventRuleName"];
```

```
        var state = await _eventBridgeWrapper.GetRuleStateByRuleName(eventRuleName);
        Console.WriteLine($"Rule {eventRuleName} is in current state {state}.");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="topicArn">The ARN of the SNS topic to clean up.</param>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources(string topicArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        var eventRuleName = _configuration["eventRuleName"];
        if (GetYesNoResponse($"\tDelete all targets and event rule {eventRuleName}?
(y/n)"))
        {
            Console.WriteLine($"\tRemoving all targets from the event rule.");
            await _eventBridgeWrapper.RemoveAllTargetsFromRule(eventRuleName);

            Console.WriteLine($"\tDeleting event rule.");
            await _eventBridgeWrapper.DeleteRuleByName(eventRuleName);
        }

        var topicName = _configuration["topicName"];
        if (GetYesNoResponse($"\tDelete Amazon SNS subscription topic {topicName}?
(y/n)"))
        {
            Console.WriteLine($"\tDeleting topic.");
            await _snsClient!.DeleteTopicAsync(new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        }

        var bucketName = _configuration["testBucketName"];
        if (GetYesNoResponse($"\tDelete Amazon S3 bucket {bucketName}? (y/n)"))
        {
            Console.WriteLine($"\tDeleting bucket.");
            // Delete all objects in the bucket.
```

```
            var deleteList = await _s3Client.ListObjectsV2Async(new
ListObjectsV2Request()
            {
                BucketName = bucketName
            });
            await _s3Client.DeleteObjectsAsync(new DeleteObjectsRequest()
            {
                BucketName = bucketName,
                Objects = deleteList.S3Objects
                    .Select(o => new KeyVersion { Key = o.Key }).ToList()
            });
            // Now delete the bucket.
            await _s3Client.DeleteBucketAsync(new DeleteBucketRequest()
            {
                BucketName = bucketName
            });
        }

        var roleName = _configuration["roleName"];
        if (GetYesNoResponse($"\tDelete role {roleName}? (y/n)"))
        {
            Console.WriteLine($"\tDetaching policy and deleting role.");

            await _iamClient!.DetachRolePolicyAsync(new DetachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess",
            });

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = roleName
            });
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
```

```
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

Crie uma classe que envolva as EventBridge operações.

```
/// <summary>
/// Wrapper for Amazon EventBridge operations.
/// </summary>
public class EventBridgeWrapper
{
    private readonly IAmazonEventBridge _amazonEventBridge;
    private readonly ILogger<EventBridgeWrapper> _logger;

    /// <summary>
    /// Constructor for the EventBridge wrapper.
    /// </summary>
    /// <param name="amazonEventBridge">The injected EventBridge client.</param>
    /// <param name="logger">The injected logger for the wrapper.</param>
    public EventBridgeWrapper(IAmazonEventBridge amazonEventBridge,
 ILogger<EventBridgeWrapper> logger)

    {
        _amazonEventBridge = amazonEventBridge;
        _logger = logger;
    }

    /// <summary>
    /// Get the state for a rule by the rule name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="eventBusName">The optional name of the event bus. If empty,
 uses the default event bus.</param>
    /// <returns>The state of the rule.</returns>
```

```
    public async Task<RuleState> GetRuleStateByRuleName(string ruleName, string?
eventBusName = null)
    {
        var ruleResponse = await _amazonEventBridge.DescribeRuleAsync(
            new DescribeRuleRequest()
            {
                Name = ruleName,
                EventBusName = eventBusName
            });
        return ruleResponse.State;
    }

    /// <summary>
    /// Enable a particular rule on an event bus.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> EnableRuleByName(string ruleName)
    {
        var ruleResponse = await _amazonEventBridge.EnableRuleAsync(
            new EnableRuleRequest()
            {
                Name = ruleName
            });
        return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Disable a particular rule on an event bus.
    /// </summary
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DisableRuleByName(string ruleName)
    {
        var ruleResponse = await _amazonEventBridge.DisableRuleAsync(
            new DisableRuleRequest()
            {
                Name = ruleName
            });
        return ruleResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// List the rules on an event bus.
```

```
    /// </summary>
    /// <param name="eventBusArn">The optional ARN of the event bus. If empty, uses
the default event bus.</param>
    /// <returns>The list of rules.</returns>
    public async Task<List<Rule>> ListAllRulesForEventBus(string? eventBusArn =
null)
    {
        var results = new List<Rule>();
        var request = new ListRulesRequest()
        {
            EventBusName = eventBusArn
        };
        // Get all of the pages of rules.
        ListRulesResponse response;
        do
        {
            response = await _amazonEventBridge.ListRulesAsync(request);
            results.AddRange(response.Rules);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// List all of the targets matching a rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <returns>The list of targets.</returns>
    public async Task<List<Target>> ListAllTargetsOnRule(string ruleName)
    {
        var results = new List<Target>();
        var request = new ListTargetsByRuleRequest()
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse response;
        do
        {
            response = await _amazonEventBridge.ListTargetsByRuleAsync(request);
            results.AddRange(response.Targets);
            request.NextToken = response.NextToken;
```

```
        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// List names of all rules matching a target.
    /// </summary>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <returns>The list of rule names.</returns>
    public async Task<List<string>> ListAllRuleNamesByTarget(string targetArn)
    {
        var results = new List<string>();
        var request = new ListRuleNamesByTargetRequest()
        {
            TargetArn = targetArn
        };
        ListRuleNamesByTargetResponse response;
        do
        {
            response = await _amazonEventBridge.ListRuleNamesByTargetAsync(request);
            results.AddRange(response.RuleNames);
            request.NextToken = response.NextToken;

        } while (response.NextToken is not null);

        return results;
    }

    /// <summary>
    /// Create a new event rule that triggers when an Amazon S3 object is created in
 a bucket.
    /// </summary>
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="ruleName">The name to give the rule.</param>
    /// <param name="bucketName">The name of the bucket to trigger the event.</
param>
    /// <returns>The ARN of the new rule.</returns>
    public async Task<string> PutS3UploadRule(string roleArn, string ruleName,
 string bucketName)
    {
        string eventPattern = "{" +
                                "\"source\": [\"aws.s3\"]," +
                                    "\"detail-type\": [\"Object Created\"]," +
```

```
                                    "\"detail\": {" +
                                        "\"bucket\": {" +
                                            "\"name\": [\"" + bucketName + "\"]" +
                                        "}" +
                                    "}" +
                                "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Example S3 upload rule for EventBridge",
                RoleArn = roleArn,
                EventPattern = eventPattern
            });

        return response.RuleArn;
    }

    /// <summary>
    /// Update an Amazon S3 object created rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the default
event bus.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateS3UploadRuleTargetWithTransform(string ruleName,
string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
                InputTransformer = new InputTransformer()
                {
                    InputPathsMap = new Dictionary<string, string>()
                    {
                        {"bucket", "$.detail.bucket.name"},
                        {"time", "$.time"}
```

```
                    },
                    InputTemplate = "\"Notification: an object was uploaded to
bucket <bucket> at <time>.\""
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }
        return targetID;
    }

    /// <summary>
    /// Update a custom rule with a transform on the target.
    /// </summary>
    /// <param name="ruleName">The name of the rule.</param>
    /// <param name="targetArn">The ARN of the target.</param>
    /// <param name="eventBusArn">Optional event bus ARN. If empty, uses the default
event bus.</param>
    /// <returns>The ID of the target.</returns>
    public async Task<string> UpdateCustomRuleTargetWithTransform(string ruleName,
string targetArn, string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        var targets = new List<Target>
        {
            new Target()
            {
                Id = targetID,
                Arn = targetArn,
```

```
                InputTransformer = new InputTransformer()
                {
                    InputTemplate = "\"Notification: sample event was received.\""
                }
            }
        };
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });
        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }
        return targetID;
    }

    /// <summary>
    /// Add an event to the event bus that includes an email, message, and time.
    /// </summary>
    /// <param name="email">The email to use in the event detail of the custom
event.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> PutCustomEmailEvent(string email)
    {
        var eventDetail = new
        {
            UserEmail = email,
            Message = "This event was generated by example code.",
            UtcTime = DateTime.UtcNow.ToString("g")
        };
        var response = await _amazonEventBridge.PutEventsAsync(
            new PutEventsRequest()
            {
                Entries = new List<PutEventsRequestEntry>()
                {
```

```
                    new PutEventsRequestEntry()
                    {
                        Source = "ExampleSource",
                        Detail = JsonSerializer.Serialize(eventDetail),
                        DetailType = "ExampleType"
                    }
                }
            });

        return response.FailedEntryCount == 0;
    }

    /// <summary>
    /// Update a rule to use a custom defined event pattern.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <returns>The ARN of the updated rule.</returns>
    public async Task<string> UpdateCustomEventPattern(string ruleName)
    {
        string customEventsPattern = "{" +
                                     "\"source\": [\"ExampleSource\"]," +
                                     "\"detail-type\": [\"ExampleType\"]" +
                                     "}";

        var response = await _amazonEventBridge.PutRuleAsync(
            new PutRuleRequest()
            {
                Name = ruleName,
                Description = "Custom test rule",
                EventPattern = customEventsPattern
            });

        return response.RuleArn;
    }

    /// <summary>
    /// Add an Amazon SNS target topic to a rule.
    /// </summary>
    /// <param name="ruleName">The name of the rule to update.</param>
    /// <param name="targetArn">The ARN of the Amazon SNS target.</param>
    /// <param name="eventBusArn">The optional event bus name, uses default if
empty.</param>
    /// <returns>The ID of the target.</returns>
```

```
    public async Task<string> AddSnsTargetToRule(string ruleName, string targetArn,
string? eventBusArn = null)
    {
        var targetID = Guid.NewGuid().ToString();

        // Create the list of targets and add a new target.
        var targets = new List<Target>
        {
            new Target()
            {
                Arn = targetArn,
                Id = targetID
            }
        };

        // Add the targets to the rule.
        var response = await _amazonEventBridge.PutTargetsAsync(
            new PutTargetsRequest()
            {
                EventBusName = eventBusArn,
                Rule = ruleName,
                Targets = targets,
            });

        if (response.FailedEntryCount > 0)
        {
            response.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to add target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }

        return targetID;
    }

    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> RemoveAllTargetsFromRule(string ruleName)
    {
```

```
        var targetIds = new List<string>();
        var request = new ListTargetsByRuleRequest()
        {
            Rule = ruleName
        };
        ListTargetsByRuleResponse targetsResponse;
        do
        {
            targetsResponse = await
_amazonEventBridge.ListTargetsByRuleAsync(request);
            targetIds.AddRange(targetsResponse.Targets.Select(t => t.Id));
            request.NextToken = targetsResponse.NextToken;

        } while (targetsResponse.NextToken is not null);

        var removeResponse = await _amazonEventBridge.RemoveTargetsAsync(
            new RemoveTargetsRequest()
            {
                Rule = ruleName,
                Ids = targetIds
            });

        if (removeResponse.FailedEntryCount > 0)
        {
            removeResponse.FailedEntries.ForEach(e =>
            {
                _logger.LogError(
                    $"Failed to remove target {e.TargetId}: {e.ErrorMessage}, code
{e.ErrorCode}");
            });
        }

        return removeResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete an event rule by name.
    /// </summary>
    /// <param name="ruleName">The name of the event rule.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteRuleByName(string ruleName)
    {
        var response = await _amazonEventBridge.DeleteRuleAsync(
            new DeleteRuleRequest()
```

```
            {
                Name = ruleName
            });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Exemplos de AWS Glue usando AWS SDK for .NET

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace GlueActions;

public class HelloGlue
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Glue.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonGlue>()
                .AddTransient<GlueWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<HelloGlue>();
        var glueClient = host.Services.GetRequiredService<IAmazonGlue>();

        var request = new ListJobsRequest();

        var jobNames = new List<string>();

        do
        {
```

```
            var response = await glueClient.ListJobsAsync(request);
            jobNames.AddRange(response.JobNames);
            request.NextToken = response.NextToken;
        }
        while (request.NextToken is not null);

        Console.Clear();
        Console.WriteLine("Hello, Glue. Let's list your existing Glue Jobs:");
        if (jobNames.Count == 0)
        {
            Console.WriteLine("You don't have any AWS Glue jobs.");
        }
        else
        {
            jobNames.ForEach(Console.WriteLine);
        }
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

O exemplo de código a seguir mostra como criar um crawler do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name for the crawler.</param>
    /// <param name="crawlerDescription">A description of the crawler.</param>
    /// <param name="role">The AWS Identity and Access Management (IAM) role to
    /// be assumed by the crawler.</param>
    /// <param name="schedule">The schedule on which the crawler will be executed.</
param>
    /// <param name="s3Path">The path to the Amazon Simple Storage Service (Amazon
 S3)
    /// bucket where the Python script has been stored.</param>
    /// <param name="dbName">The name to use for the database that will be
    /// created by the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateCrawlerAsync(
        string crawlerName,
        string crawlerDescription,
        string role,
        string schedule,
        string s3Path,
        string dbName)
    {
        var s3Target = new S3Target
        {
            Path = s3Path,
        };

        var targetList = new List<S3Target>
        {
            s3Target,
        };

        var targets = new CrawlerTargets
        {
            S3Targets = targetList,
        };

        var crawlerRequest = new CreateCrawlerRequest
        {
            DatabaseName = dbName,
            Name = crawlerName,
            Description = crawlerDescription,
```

```
            Targets = targets,
            Role = role,
            Schedule = schedule,
        };

        var response = await _amazonGlue.CreateCrawlerAsync(crawlerRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for .NET da API.

Crie uma definição de trabalho

O exemplo de código a seguir mostra como criar uma definição de trabalho do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="roleName">The name of the IAM role to be assumed by
    /// the job.</param>
    /// <param name="description">A description of the job.</param>
    /// <param name="scriptUrl">The URL to the script.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateJobAsync(string dbName, string tableName, string
 bucketUrl, string jobName, string roleName, string description, string scriptUrl)
    {
        var command = new JobCommand
        {
            PythonVersion = "3",
            Name = "glueetl",
            ScriptLocation = scriptUrl,
```

```
        };

        var arguments = new Dictionary<string, string>
        {
            { "--input_database", dbName },
            { "--input_table", tableName },
            { "--output_bucket_url", bucketUrl }
        };

        var request = new CreateJobRequest
        {
            Command = command,
            DefaultArguments = arguments,
            Description = description,
            GlueVersion = "3.0",
            Name = jobName,
            NumberOfWorkers = 10,
            Role = roleName,
            WorkerType = "G.1X"
        };

        var response = await _amazonGlue.CreateJobAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for .NET da API.

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Delete an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteCrawlerAsync(string crawlerName)
    {
        var response = await _amazonGlue.DeleteCrawlerAsync(new DeleteCrawlerRequest
{ Name = crawlerName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for .NET da API.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete the AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteDatabaseAsync(string dbName)
    {
        var response = await _amazonGlue.DeleteDatabaseAsync(new
DeleteDatabaseRequest { Name = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for .NET da API.

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteJobAsync(string jobName)
    {
        var response = await _amazonGlue.DeleteJobAsync(new DeleteJobRequest
{ JobName = jobName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for .NET da API.

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela do AWS Glue Data Catalog.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a table from an AWS Glue database.
    /// </summary>
    /// <param name="tableName">The table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTableAsync(string dbName, string tableName)
    {
        var response = await _amazonGlue.DeleteTableAsync(new DeleteTableRequest
{ Name = tableName, DatabaseName = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an AWS Glue crawler.
    /// </summary>
```

```
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Crawler object describing the crawler.</returns>
    public async Task<Crawler?> GetCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new GetCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.GetCrawlerAsync(crawlerRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            var databaseName = response.Crawler.DatabaseName;
            Console.WriteLine($"{crawlerName} has the database {databaseName}");
            return response.Crawler;
        }

        Console.WriteLine($"No information regarding {crawlerName} could be
found.");
        return null;
    }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for .NET da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
```

```
    /// <returns>A Database object containing information about the database.</
returns>
    public async Task<Database> GetDatabaseAsync(string dbName)
    {
        var databasesRequest = new GetDatabaseRequest
        {
            Name = dbName,
        };

        var response = await _amazonGlue.GetDatabaseAsync(databasesRequest);
        return response.Database;
    }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for .NET da API.

Obter uma execução de trabalho

O exemplo de código a seguir mostra como obter uma execução de trabalho do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about a specific AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="jobRunId">The Id of the job run.</param>
    /// <returns>A JobRun object with information about the job run.</returns>
    public async Task<JobRun> GetJobRunAsync(string jobName, string jobRunId)
    {
        var response = await _amazonGlue.GetJobRunAsync(new GetJobRunRequest
{ JobName = jobName, RunId = jobRunId });
        return response.JobRun;
    }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for .NET da API.

Obter execuções de um trabalho

O exemplo de código a seguir mostra como obter execuções de um trabalho do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about all AWS Glue runs of a specific job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A list of JobRun objects.</returns>
    public async Task<List<JobRun>> GetJobRunsAsync(string jobName)
    {
        var jobRuns = new List<JobRun>();

        var request = new GetJobRunsRequest
        {
            JobName = jobName,
        };

        // No need to loop to get all the log groups--the SDK does it for us behind
the scenes
        var paginatorForJobRuns =
            _amazonGlue.Paginators.GetJobRuns(request);

        await foreach (var response in paginatorForJobRuns.Responses)
        {
            response.JobRuns.ForEach(jobRun =>
            {
                jobRuns.Add(jobRun);
            });
        }
```

```
        return jobRuns;
    }
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for .NET da API.

Obter tabelas de um banco de dados

O exemplo de código a seguir mostra como obter tabelas de um banco de dados no AWS Glue Data Catalog.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of tables for an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A list of Table objects.</returns>
    public async Task<List<Table>> GetTablesAsync(string dbName)
    {
        var request = new GetTablesRequest { DatabaseName = dbName };
        var tables = new List<Table>();

        // Get a paginator for listing the tables.
        var tablePaginator = _amazonGlue.Paginators.GetTables(request);

        await foreach (var response in tablePaginator.Responses)
        {
            tables.AddRange(response.TableList);
        }

        return tables;
    }
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for .NET da API.

Listar definições de trabalho

O exemplo de código a seguir mostra como listas definições de trabalho do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List AWS Glue jobs using a paginator.
    /// </summary>
    /// <returns>A list of AWS Glue job names.</returns>
    public async Task<List<string>> ListJobsAsync()
    {
        var jobNames = new List<string>();

        var listJobsPaginator = _amazonGlue.Paginators.ListJobs(new ListJobsRequest
{ MaxResults = 10 });
        await foreach (var response in listJobsPaginator.Responses)
        {
            jobNames.AddRange(response.JobNames);
        }

        return jobNames;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Start an AWS Glue crawler.
/// </summary>
/// <param name="crawlerName">The name of the crawler.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> StartCrawlerAsync(string crawlerName)
{
    var crawlerRequest = new StartCrawlerRequest
    {
        Name = crawlerName,
    };

    var response = await _amazonGlue.StartCrawlerAsync(crawlerRequest);

    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for .NET da API.

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start an AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A string representing the job run Id.</returns>
    public async Task<string> StartJobRunAsync(
        string jobName,
        string inputDatabase,
        string inputTable,
        string bucketName)
    {
        var request = new StartJobRunRequest
        {
            JobName = jobName,
            Arguments = new Dictionary<string, string>
            {
                {"--input_database", inputDatabase},
                {"--input_table", inputTable},
                {"--output_bucket_url", $"s3://{bucketName}/"}
            }
        };

        var response = await _amazonGlue.StartJobRunAsync(request);
        return response.JobRunId;
    }
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for .NET da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.

- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que abranja as funções do AWS Glue usadas no cenário.

```
using System.Net;

namespace GlueActions;

public class GlueWrapper
{
    private readonly IAmazonGlue _amazonGlue;

    /// <summary>
    /// Constructor for the AWS Glue actions wrapper.
    /// </summary>
    /// <param name="amazonGlue"></param>
    public GlueWrapper(IAmazonGlue amazonGlue)
    {
        _amazonGlue = amazonGlue;
    }

    /// <summary>
    /// Create an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name for the crawler.</param>
    /// <param name="crawlerDescription">A description of the crawler.</param>
    /// <param name="role">The AWS Identity and Access Management (IAM) role to
    /// be assumed by the crawler.</param>
    /// <param name="schedule">The schedule on which the crawler will be executed.</
param>
```

```
    /// <param name="s3Path">The path to the Amazon Simple Storage Service (Amazon
S3)
    /// bucket where the Python script has been stored.</param>
    /// <param name="dbName">The name to use for the database that will be
    /// created by the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateCrawlerAsync(
        string crawlerName,
        string crawlerDescription,
        string role,
        string schedule,
        string s3Path,
        string dbName)
    {
        var s3Target = new S3Target
        {
            Path = s3Path,
        };

        var targetList = new List<S3Target>
        {
            s3Target,
        };

        var targets = new CrawlerTargets
        {
            S3Targets = targetList,
        };

        var crawlerRequest = new CreateCrawlerRequest
        {
            DatabaseName = dbName,
            Name = crawlerName,
            Description = crawlerDescription,
            Targets = targets,
            Role = role,
            Schedule = schedule,
        };

        var response = await _amazonGlue.CreateCrawlerAsync(crawlerRequest);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Create an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="roleName">The name of the IAM role to be assumed by
    /// the job.</param>
    /// <param name="description">A description of the job.</param>
    /// <param name="scriptUrl">The URL to the script.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> CreateJobAsync(string dbName, string tableName, string
 bucketUrl, string jobName, string roleName, string description, string scriptUrl)
    {
        var command = new JobCommand
        {
            PythonVersion = "3",
            Name = "glueetl",
            ScriptLocation = scriptUrl,
        };

        var arguments = new Dictionary<string, string>
        {
            { "--input_database", dbName },
            { "--input_table", tableName },
            { "--output_bucket_url", bucketUrl }
        };

        var request = new CreateJobRequest
        {
            Command = command,
            DefaultArguments = arguments,
            Description = description,
            GlueVersion = "3.0",
            Name = jobName,
            NumberOfWorkers = 10,
            Role = roleName,
            WorkerType = "G.1X"
        };

        var response = await _amazonGlue.CreateJobAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
```

```
    /// Delete an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteCrawlerAsync(string crawlerName)
    {
        var response = await _amazonGlue.DeleteCrawlerAsync(new DeleteCrawlerRequest
{ Name = crawlerName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete the AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteDatabaseAsync(string dbName)
    {
        var response = await _amazonGlue.DeleteDatabaseAsync(new
DeleteDatabaseRequest { Name = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an AWS Glue job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteJobAsync(string jobName)
    {
        var response = await _amazonGlue.DeleteJobAsync(new DeleteJobRequest
{ JobName = jobName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete a table from an AWS Glue database.
    /// </summary>
    /// <param name="tableName">The table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTableAsync(string dbName, string tableName)
```

```
    {
        var response = await _amazonGlue.DeleteTableAsync(new DeleteTableRequest
{ Name = tableName, DatabaseName = dbName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Get information about an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Crawler object describing the crawler.</returns>
    public async Task<Crawler?> GetCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new GetCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.GetCrawlerAsync(crawlerRequest);
        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            var databaseName = response.Crawler.DatabaseName;
            Console.WriteLine($"{crawlerName} has the database {databaseName}");
            return response.Crawler;
        }

        Console.WriteLine($"No information regarding {crawlerName} could be
found.");
        return null;
    }


    /// <summary>
    /// Get information about the state of an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A value describing the state of the crawler.</returns>
    public async Task<CrawlerState> GetCrawlerStateAsync(string crawlerName)
    {
        var response = await _amazonGlue.GetCrawlerAsync(
            new GetCrawlerRequest { Name = crawlerName });
        return response.Crawler.State;
    }
```

```
    /// <summary>
    /// Get information about an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A Database object containing information about the database.</
returns>
    public async Task<Database> GetDatabaseAsync(string dbName)
    {
        var databasesRequest = new GetDatabaseRequest
        {
            Name = dbName,
        };

        var response = await _amazonGlue.GetDatabaseAsync(databasesRequest);
        return response.Database;
    }


    /// <summary>
    /// Get information about a specific AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <param name="jobRunId">The Id of the job run.</param>
    /// <returns>A JobRun object with information about the job run.</returns>
    public async Task<JobRun> GetJobRunAsync(string jobName, string jobRunId)
    {
        var response = await _amazonGlue.GetJobRunAsync(new GetJobRunRequest
 { JobName = jobName, RunId = jobRunId });
        return response.JobRun;
    }


    /// <summary>
    /// Get information about all AWS Glue runs of a specific job.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A list of JobRun objects.</returns>
    public async Task<List<JobRun>> GetJobRunsAsync(string jobName)
    {
        var jobRuns = new List<JobRun>();

        var request = new GetJobRunsRequest
```

```
        {
            JobName = jobName,
        };

        // No need to loop to get all the log groups--the SDK does it for us behind
the scenes
        var paginatorForJobRuns =
            _amazonGlue.Paginators.GetJobRuns(request);

        await foreach (var response in paginatorForJobRuns.Responses)
        {
            response.JobRuns.ForEach(jobRun =>
            {
                jobRuns.Add(jobRun);
            });
        }

        return jobRuns;
    }


    /// <summary>
    /// Get a list of tables for an AWS Glue database.
    /// </summary>
    /// <param name="dbName">The name of the database.</param>
    /// <returns>A list of Table objects.</returns>
    public async Task<List<Table>> GetTablesAsync(string dbName)
    {
        var request = new GetTablesRequest { DatabaseName = dbName };
        var tables = new List<Table>();

        // Get a paginator for listing the tables.
        var tablePaginator = _amazonGlue.Paginators.GetTables(request);

        await foreach (var response in tablePaginator.Responses)
        {
            tables.AddRange(response.TableList);
        }

        return tables;
    }


    /// <summary>
```

```
    /// List AWS Glue jobs using a paginator.
    /// </summary>
    /// <returns>A list of AWS Glue job names.</returns>
    public async Task<List<string>> ListJobsAsync()
    {
        var jobNames = new List<string>();

        var listJobsPaginator = _amazonGlue.Paginators.ListJobs(new ListJobsRequest
{ MaxResults = 10 });
        await foreach (var response in listJobsPaginator.Responses)
        {
            jobNames.AddRange(response.JobNames);
        }

        return jobNames;
    }


    /// <summary>
    /// Start an AWS Glue crawler.
    /// </summary>
    /// <param name="crawlerName">The name of the crawler.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> StartCrawlerAsync(string crawlerName)
    {
        var crawlerRequest = new StartCrawlerRequest
        {
            Name = crawlerName,
        };

        var response = await _amazonGlue.StartCrawlerAsync(crawlerRequest);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Start an AWS Glue job run.
    /// </summary>
    /// <param name="jobName">The name of the job.</param>
    /// <returns>A string representing the job run Id.</returns>
    public async Task<string> StartJobRunAsync(
        string jobName,
        string inputDatabase,
```

```
        string inputTable,
        string bucketName)
    {
        var request = new StartJobRunRequest
        {
            JobName = jobName,
            Arguments = new Dictionary<string, string>
            {
                {"--input_database", inputDatabase},
                {"--input_table", inputTable},
                {"--output_bucket_url", $"s3://{bucketName}/"}
            }
        };

        var response = await _amazonGlue.StartJobRunAsync(request);
        return response.JobRunId;
    }

}
```

Crie uma classe que execute o cenário.

```
global using Amazon.Glue;
global using GlueActions;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;



using Amazon.Glue.Model;
using Amazon.S3;
using Amazon.S3.Model;

namespace GlueBasics;

public class GlueBasics
{
```

```
    private static ILogger logger = null!;
    private static IConfiguration _configuration = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Glue.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonGlue>()
            .AddTransient<GlueWrapper>()
            .AddTransient<UiWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
        .CreateLogger<GlueBasics>();

        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        // These values are stored in settings.json
        // Once you have run the CDK script to deploy the resources,
        // edit the file to set "BucketName", "RoleName", and "ScriptURL"
        // to the appropriate values. Also set "CrawlerName" to the name
        // you want to give the crawler when it is created.
        string bucketName = _configuration["BucketName"]!;
        string bucketUrl = _configuration["BucketUrl"]!;
        string crawlerName = _configuration["CrawlerName"]!;
        string roleName = _configuration["RoleName"]!;
        string sourceData = _configuration["SourceData"]!;
        string dbName = _configuration["DbName"]!;
        string cron = _configuration["Cron"]!;
        string scriptUrl = _configuration["ScriptURL"]!;
        string jobName = _configuration["JobName"]!;
```

```
        var wrapper = host.Services.GetRequiredService<GlueWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UiWrapper>();

        uiWrapper.DisplayOverview();
        uiWrapper.PressEnter();

        // Create the crawler and wait for it to be ready.
        uiWrapper.DisplayTitle("Create AWS Glue crawler");
        Console.WriteLine("Let's begin by creating the AWS Glue crawler.");

        var crawlerDescription = "Crawler created for the AWS Glue Basics
 scenario.";
        var crawlerCreated = await wrapper.CreateCrawlerAsync(crawlerName,
 crawlerDescription, roleName, cron, sourceData, dbName);
        if (crawlerCreated)
        {
            Console.WriteLine($"The crawler: {crawlerName} has been created. Now
 let's wait until it's ready.");
            CrawlerState crawlerState;
            do
            {
                crawlerState = await wrapper.GetCrawlerStateAsync(crawlerName);
            }
            while (crawlerState != "READY");
            Console.WriteLine($"The crawler {crawlerName} is now ready for use.");
        }
        else
        {
            Console.WriteLine($"Couldn't create crawler {crawlerName}.");
            return; // Exit the application.
        }

        uiWrapper.DisplayTitle("Start AWS Glue crawler");
        Console.WriteLine("Now let's wait until the crawler has successfully
 started.");
        var crawlerStarted = await wrapper.StartCrawlerAsync(crawlerName);
        if (crawlerStarted)
        {
            CrawlerState crawlerState;
            do
            {
                crawlerState = await wrapper.GetCrawlerStateAsync(crawlerName);
            }
            while (crawlerState != "READY");
```

```
            Console.WriteLine($"The crawler {crawlerName} is now ready for use.");
        }
        else
        {
            Console.WriteLine($"Couldn't start the crawler {crawlerName}.");
            return; // Exit the application.
        }

        uiWrapper.PressEnter();

        Console.WriteLine($"\nLet's take a look at the database: {dbName}");
        var database = await wrapper.GetDatabaseAsync(dbName);

        if (database != null)
        {
            uiWrapper.DisplayTitle($"{database.Name} Details");
            Console.WriteLine($"{database.Name} created on {database.CreateTime}");
            Console.WriteLine(database.Description);
        }

        uiWrapper.PressEnter();

        var tables = await wrapper.GetTablesAsync(dbName);
        if (tables.Count > 0)
        {
            tables.ForEach(table =>
            {
                Console.WriteLine($"{table.Name}\tCreated:
{table.CreateTime}\tUpdated: {table.UpdateTime}");
            });
        }

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Create AWS Glue job");
        Console.WriteLine("Creating a new AWS Glue job.");
        var description = "An AWS Glue job created using the AWS SDK for .NET";
        await wrapper.CreateJobAsync(dbName, tables[0].Name, bucketUrl, jobName,
roleName, description, scriptUrl);

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Starting AWS Glue job");
        Console.WriteLine("Starting the new AWS Glue job...");
```

```
        var jobRunId = await wrapper.StartJobRunAsync(jobName, dbName,
tables[0].Name, bucketName);
        var jobRunComplete = false;
        var jobRun = new JobRun();
        do
        {
            jobRun = await wrapper.GetJobRunAsync(jobName, jobRunId);
            if (jobRun.JobRunState == "SUCCEEDED" || jobRun.JobRunState == "STOPPED"
||
                jobRun.JobRunState == "FAILED" || jobRun.JobRunState == "TIMEOUT")
            {
                jobRunComplete = true;
            }
        } while (!jobRunComplete);

        uiWrapper.DisplayTitle($"Data in {bucketName}");

        // Get the list of data stored in the S3 bucket.
        var s3Client = new AmazonS3Client();

        var response = await s3Client.ListObjectsAsync(new ListObjectsRequest
{ BucketName = bucketName });
        response.S3Objects.ForEach(s3Object =>
        {
            Console.WriteLine(s3Object.Key);
        });

        uiWrapper.DisplayTitle("AWS Glue jobs");
        var jobNames = await wrapper.ListJobsAsync();
        jobNames.ForEach(jobName =>
        {
            Console.WriteLine(jobName);
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Get AWS Glue job run information");
        Console.WriteLine("Getting information about the AWS Glue job.");
        var jobRuns = await wrapper.GetJobRunsAsync(jobName);

        jobRuns.ForEach(jobRun =>
        {

Console.WriteLine($"{jobRun.JobName}\t{jobRun.JobRunState}\t{jobRun.CompletedOn}");
```

```
        });

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Deleting resources");
        Console.WriteLine("Deleting the AWS Glue job used by the example.");
        await wrapper.DeleteJobAsync(jobName);

        Console.WriteLine("Deleting the tables from the database.");
        tables.ForEach(async table =>
        {
            await wrapper.DeleteTableAsync(dbName, table.Name);
        });

        Console.WriteLine("Deleting the database.");
        await wrapper.DeleteDatabaseAsync(dbName);

        Console.WriteLine("Deleting the AWS Glue crawler.");
        await wrapper.DeleteCrawlerAsync(crawlerName);

        Console.WriteLine("The AWS Glue scenario has completed.");
        uiWrapper.PressEnter();
    }
}


namespace GlueBasics;

public class UiWrapper
{
    public readonly string SepBar = new string('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the scenario.
    /// </summary>
    public void DisplayOverview()
    {
        Console.Clear();
        DisplayTitle("Amazon Glue: get started with crawlers and jobs");

        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t 1. Create a crawler, pass it the IAM role and the URL
 to the public S3 bucket that contains the source data");
        Console.WriteLine("\t 2. Start the crawler.");
```

```
        Console.WriteLine("\t 3. Get the database created by the crawler and the
tables in the database.");
        Console.WriteLine("\t 4. Create a job.");
        Console.WriteLine("\t 5. Start a job run.");
        Console.WriteLine("\t 6. Wait for the job run to complete.");
        Console.WriteLine("\t 7. Show the data stored in the bucket.");
        Console.WriteLine("\t 8. List jobs for the account.");
        Console.WriteLine("\t 9. Get job run details for the job that was run.");
        Console.WriteLine("\t10. Delete the demo job.");
        Console.WriteLine("\t11. Delete the database and tables created for the
demo.");
        Console.WriteLine("\t12. Delete the crawler.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPlease press <Enter> to continue. ");
        _ = Console.ReadLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to center on the screen.</param>
    /// <returns>The string padded to make it center on the screen.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
```

```
        Console.WriteLine(SepBar);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

Exemplos do IAM usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for .NET com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace IAMActions;

public class HelloIAM
{
    static async Task Main(string[] args)
    {
        // Getting started with AWS Identity and Access Management (IAM). List
        // the policies for the account.
        var iamClient = new AmazonIdentityManagementServiceClient();

        var listPoliciesPaginator = iamClient.Paginators.ListPolicies(new
 ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        Console.WriteLine("Here are the policies defined for your account:\n");
        policies.ForEach(policy =>
        {
```

```
            Console.WriteLine($"Created:
 {policy.CreateDate}\t{policy.PolicyName}\t{policy.Description}");
        });
    }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar um usuário a um grupo

O exemplo de código a seguir mostra como adicionar um usuário a um grupo do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add an existing IAM user to an existing IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
 AddUserToGroupRequest
        {
```

```
            GroupName = groupName,
            UserName = userName,
        });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte AddUserToGroupa Referência AWS SDK for .NET da API.

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string roleName)
    {
        var response = await _IAMService.AttachRolePolicyAsync(new
AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for .NET da API.

Anexar uma política em linha a um perfil

Os exemplos de código a seguir mostram como anexar uma política em linha a um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the inline policy document embedded in a role.
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string roleName,
 string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for .NET da API.

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
{ GroupName = groupName });
        return response.Group;
    }
```

- Para obter detalhes da API, consulte CreateGroupa Referência AWS SDK for .NET da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });

        return response.Policy;
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for .NET da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
```

```
    public async Task<string> CreateRoleAsync(string roleName, string
 rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for .NET da API.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName, string
 description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
```

```
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
    }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for .NET da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM user.
    /// </summary>
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
{ UserName = userName });
```

```
        return response.User;
    }
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for .NET da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
    /// key.</param>
    /// <returns>The AccessKey.</returns>
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
        var response = await _IAMService.CreateAccessKeyAsync(new
CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;
```

```
    }
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for .NET da API.

Criar uma política em linha para um grupo

O exemplo de código a seguir mostra como criar uma política do IAM em linha para um grupo.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM policy.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string policyName,
 string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte PutGroupPolicya Referência AWS SDK for .NET da API.

criar um perfil de instância

O exemplo de código a seguir mostra como criar um perfil de instância do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with a
specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to the
role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                    "\"Version\": \"2012-10-17\"," +
                                    "\"Statement\": [{" +
```

```
                                    "\"Effect\": \"Allow\"," +
                                    "\"Principal\": {" +
                                    "\"Service\": [" +
                                        "\"ec2.amazonaws.com\"" +
                                    "]" +
                                    "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                            "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
```

```
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
```

```
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }
```

- Para obter detalhes da API, consulte CreateInstanceProfilea Referência AWS SDK for .NET da API.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group to delete.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
{ GroupName = groupName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteGroupa Referência AWS SDK for .NET da API.

Excluir uma política de grupo

O exemplo de código a seguir mostra como excluir uma política de grupo do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteGroupPolicya Referência AWS SDK for .NET da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new DeletePolicyRequest
{ PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for .NET da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
{ RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for .NET da API.

Excluir uma política de perfil

O exemplo de código a seguir mostra como excluir uma política de perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
```

```
    /// <param name="policyName">The name of the IAM role policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteRolePolicya Referência AWS SDK for .NET da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM user.
```

```
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
{ UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for .NET da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM user's access key.
    /// </summary>
    /// <param name="accessKeyId">The Id for the IAM access key.</param>
    /// <param name="userName">The username of the user that owns the IAM
    /// access key.</param>
```

```
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
userName)
    {
        var response = await _IAMService.DeleteAccessKeyAsync(new
DeleteAccessKeyRequest
        {
            AccessKeyId = accessKeyId,
            UserName = userName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for .NET da API.

Excluir uma política em linha de um usuário

O exemplo de código a seguir mostra como excluir uma política em linha do IAM de um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
```

```
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for .NET da API.

Excluir um perfil de instância

O exemplo de código a seguir mostra como excluir um perfil de instância do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
```

```
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await _amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }
```

- Para obter detalhes da API, consulte DeleteInstanceProfilea Referência AWS SDK for .NET da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Detach an IAM policy from an IAM role.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM policy.</
param>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DetachRolePolicyAsync(string policyArn, string roleName)
    {
        var response = await _IAMService.DetachRolePolicyAsync(new
 DetachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for .NET da API.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM policy.
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
{ PolicyArn = policyArn });
        return response.Policy;
    }
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for .NET da API.

Obter um perfil

O exemplo de código a seguir mostra como obter um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM role.
```

```
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });

        return response.Role;
    }
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for .NET da API.

Obter um usuário

O exemplo de código a seguir mostra como obter um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
```

```
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
    {
        var response = await _IAMService.GetUserAsync(new GetUserRequest { UserName
= userName });
        return response.User;
    }
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for .NET da API.

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
GetAccountPasswordPolicyRequest());
        return response.PasswordPolicy;
    }
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for .NET da API.

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for .NET.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }

        return groups;
    }
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for .NET da API.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
```

```
        var listRolePoliciesPaginator = _IAMService.Paginators.ListRolePolicies(new
ListRolePoliciesRequest { RoleName = roleName });
        var policyNames = new List<string>();

        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for .NET da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
```

```
        }

        return policies;
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas do IAM a um perfil do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
    public async Task<List<AttachedPolicyType>> ListAttachedRolePoliciesAsync(string
roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
_IAMService.Paginators.ListAttachedRolePolicies(new ListAttachedRolePoliciesRequest
{ RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for .NET da API.

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();

        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for .NET da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List IAM users.
    /// </summary>
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for .NET da API.

Remover um usuário de um grupo

O exemplo de código a seguir mostra como remover um usuário de um grupo do IAM.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
    /// <param name="groupName">The name of the IAM group to remove the user from.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
 groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
 _IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte RemoveUserFromGroupa Referência AWS SDK for .NET da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
static async Task Main(string[] args)
{
    _configuration = new ConfigurationBuilder()
        .SetBasePath(Directory.GetCurrentDirectory())
        .AddJsonFile("settings.json") // Load settings from .json file.
        .AddJsonFile("settings.local.json",
            true) // Optionally, load local settings.
        .Build();
```

```
        // Set up dependency injection for the AWS services.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>()
                    .AddAWSService<IAmazonDynamoDB>()
                    .AddAWSService<IAmazonElasticLoadBalancingV2>()
                    .AddAWSService<IAmazonSimpleSystemsManagement>()
                    .AddAWSService<IAmazonAutoScaling>()
                    .AddAWSService<IAmazonEC2>()
                    .AddTransient<AutoScalerWrapper>()
                    .AddTransient<ElasticLoadBalancerWrapper>()
                    .AddTransient<SmParameterWrapper>()
                    .AddTransient<Recommendations>()
                    .AddSingleton<IConfiguration>(_configuration)
            )
            .Build();

        ServicesSetup(host);
        ResourcesSetup();

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Welcome to the Resilient Architecture Example
Scenario.");
            Console.WriteLine(new string('-', 80));
            await Deploy(true);

            Console.WriteLine("Now let's begin the scenario.");
            Console.WriteLine(new string('-', 80));
            await Demo(true);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await DestroyResources(true);
```

```
            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Resilient Architecture Example Scenario is
complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await DestroyResources(true);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Setup any common resources, also used for integration testing.
    /// </summary>
    public static void ResourcesSetup()
    {
        _httpClient = new HttpClient();
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _elasticLoadBalancerWrapper =
host.Services.GetRequiredService<ElasticLoadBalancerWrapper>();
        _iamClient =
host.Services.GetRequiredService<IAmazonIdentityManagementService>();
        _recommendations = host.Services.GetRequiredService<Recommendations>();
        _autoScalerWrapper = host.Services.GetRequiredService<AutoScalerWrapper>();
        _smParameterWrapper =
host.Services.GetRequiredService<SmParameterWrapper>();
    }

    /// <summary>
    /// Deploy necessary resources for the scenario.
    /// </summary>
    /// <param name="interactive">True to run as interactive.</param>
    /// <returns>True if successful.</returns>
```

```
    public static async Task<bool> Deploy(bool interactive)
    {
        var protocol = "HTTP";
        var port = 80;
        var sshPort = 22;

        Console.WriteLine(
            "\nFor this demo, we'll use the AWS SDK for .NET to create several AWS
resources\n" +
            "to set up a load-balanced web service endpoint and explore some ways to
make it resilient\n" +
            "against various kinds of failures.\n\n" +
            "Some of the resources create by this demo are:\n");

        Console.WriteLine(
            "\t* A DynamoDB table that the web service depends on to provide book,
movie, and song recommendations.");
        Console.WriteLine(
            "\t* An EC2 launch template that defines EC2 instances that each contain
a Python web server.");
        Console.WriteLine(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
Availability Zones.");
        Console.WriteLine(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
Scaling group to distribute requests.");
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to start deploying
resources.");
        if (interactive)
            Console.ReadLine();

        // Create and populate the DynamoDB table.
        var databaseTableName = _configuration["databaseName"];
        var recommendationsPath = Path.Join(_configuration["resourcePath"],
            "recommendations_objects.json");
        Console.WriteLine($"Creating and populating a DynamoDB table named
{databaseTableName}.");
        await _recommendations.CreateDatabaseWithName(databaseTableName);
        await _recommendations.PopulateDatabase(databaseTableName,
recommendationsPath);
        Console.WriteLine(new string('-', 80));

        // Create the EC2 Launch Template.
```

```
        Console.WriteLine(
            $"Creating an EC2 launch template that runs 'server_startup_script.sh'
when an instance starts.\n"
            + "\nThis script starts a Python web server defined in the `server.py`
script. The web server\n"
            + "listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.\n"
            + "For demo purposes, this server is run as the root user. In
production, the best practice is to\n"
            + "run a web server, such as Apache, with least-privileged
credentials.");
        Console.WriteLine(
            "\nThe template also defines an IAM policy that each instance uses to
assume a role that grants\n"
            + "permissions to access the DynamoDB recommendation table and Systems
Manager parameters\n"
            + "that control the flow of the demo.");

        var startupScriptPath = Path.Join(_configuration["resourcePath"],
            "server_startup_script.sh");
        var instancePolicyPath = Path.Join(_configuration["resourcePath"],
            "instance_policy.json");
        await _autoScalerWrapper.CreateTemplate(startupScriptPath,
instancePolicyPath);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            + "Availability Zone.\n");
        var zones = await _autoScalerWrapper.DescribeAvailabilityZones();
        await _autoScalerWrapper.CreateGroupOfSize(3, _autoScalerWrapper.GroupName,
zones);
        Console.WriteLine(new string('-', 80));

        Console.WriteLine(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            + "HTTP requests. You can see these instances in the console or continue
with the demo.\n");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue.");
```

```
        if (interactive)
            Console.ReadLine();

        Console.WriteLine("Creating variables that control the flow of the demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine(
            "\nCreating an Elastic Load Balancing target group and load balancer.
 The target group\n"
            + "defines how the load balancer connects to instances. The load
 balancer provides a\n"
            + "single endpoint where clients connect and dispatches requests to
 instances in the group.");

        var defaultVpc = await _autoScalerWrapper.GetDefaultVpc();
        var subnets = await
 _autoScalerWrapper.GetAllVpcSubnetsForZones(defaultVpc.VpcId, zones);
        var subnetIds = subnets.Select(s => s.SubnetId).ToList();
        var targetGroup = await
 _elasticLoadBalancerWrapper.CreateTargetGroupOnVpc(_elasticLoadBalancerWrapper.TargetGroupN
 protocol, port, defaultVpc.VpcId);

        await
 _elasticLoadBalancerWrapper.CreateLoadBalancerAndListener(_elasticLoadBalancerWrapper.LoadB
 subnetIds, targetGroup);
        await
 _autoScalerWrapper.AttachLoadBalancerToGroup(_autoScalerWrapper.GroupName,
 targetGroup.TargetGroupArn);
        Console.WriteLine("\nVerifying access to the load balancer endpoint...");
        var endPoint = await
 _elasticLoadBalancerWrapper.GetEndpointForLoadBalancerByName(_elasticLoadBalancerWrapper.Lo
        var loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);

        if (!loadBalancerAccess)
        {
            Console.WriteLine("\nCouldn't connect to the load balancer, verifying
 that the port is open...");

            var ipString = await _httpClient.GetStringAsync("https://
checkip.amazonaws.com");
            ipString = ipString.Trim();
```

```
            var defaultSecurityGroup = await
 _autoScalerWrapper.GetDefaultSecurityGroupForVpc(defaultVpc);
            var portIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, port, ipString);
            var sshPortIsOpen =
 _autoScalerWrapper.VerifyInboundPortForGroup(defaultSecurityGroup, sshPort,
 ipString);

            if (!portIsOpen)
            {
                Console.WriteLine(
                    "\nFor this example to work, the default security group for your
 default VPC must\n"
                    + "allows access from this computer. You can either add it
 automatically from this\n"
                    + "example or add it yourself using the AWS Management Console.
\n");

                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound traffic from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, port, ipString);
                }
            }

            if (!sshPortIsOpen)
            {
                if (!interactive || GetYesNoResponse(
                        "Do you want to add a rule to the security group to allow
 inbound SSH traffic for debugging from your computer's IP address?"))
                {
                    await
 _autoScalerWrapper.OpenInboundPort(defaultSecurityGroup.GroupId, sshPort,
 ipString);
                }
            }
            loadBalancerAccess = await
 _elasticLoadBalancerWrapper.VerifyLoadBalancerEndpoint(endPoint);
        }

        if (loadBalancerAccess)
        {
```

```
            Console.WriteLine("Your load balancer is ready. You can access it by
browsing to:");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        else
        {
            Console.WriteLine(
                "\nCouldn't get a successful response from the load balancer
endpoint. Troubleshoot by\n"
                + "manually verifying that your VPC and security group are
configured correctly and that\n"
                + "you can successfully make a GET request to the load balancer
endpoint:\n");
            Console.WriteLine($"\thttp://{endPoint}\n");
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Press Enter when you're ready to continue with the
demo.");
        if (interactive)
            Console.ReadLine();
        return true;
    }

    /// <summary>
    /// Demonstrate the steps of the scenario.
    /// </summary>
    /// <param name="interactive">True to run as an interactive scenario.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> Demo(bool interactive)
    {
        var ssmOnlyPolicy = Path.Join(_configuration["resourcePath"],
            "ssm_only_policy.json");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Resetting parameters to starting values for demo.");
        await _smParameterWrapper.Reset();

        Console.WriteLine("\nThis part of the demonstration shows how to toggle
different parts of the system\n" +
                          "to create situations where the web service fails, and
shows how using a resilient\n" +
                          "architecture can keep the web service running in spite of
these failures.");
        Console.WriteLine(new string('-', 88));
```

```
        Console.WriteLine("At the start, the load balancer endpoint returns
 recommendations and reports that all targets are healthy.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine($"The web service running on the EC2 instances gets
 recommendations by querying a DynamoDB table.\n" +
                          $"The table name is contained in a Systems Manager
 parameter named '{_smParameterWrapper.TableParameter}'.\n" +
                          $"To simulate a failure of the recommendation service,
 let's set this parameter to name a non-existent table.\n");
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");
        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a failure code. But, the service reports as\n" +
                          "healthy to the load balancer because shallow health
 checks don't check for failure of the recommendation service.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Instead of failing when the recommendation service fails,
 the web service can return a static response.");
        Console.WriteLine("While this is not a perfect solution, it presents the
 customer with a somewhat better experience than failure.");

        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.FailureResponseParameter,
 "static");

        Console.WriteLine("\nNow, sending a GET request to the load balancer
 endpoint returns a static response.");
        Console.WriteLine("The service still reports as healthy because health
 checks are still shallow.");
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("Let's reinstate the recommendation service.\n");
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter,
 _smParameterWrapper.TableName);
        Console.WriteLine(
            "\nLet's also substitute bad credentials for one of the instances in the
 target group so that it can't\n" +
```

```
            "access the DynamoDB recommendation table.\n"
        );
        await _autoScalerWrapper.CreateInstanceProfileWithName(
            _autoScalerWrapper.BadCredsPolicyName,
            _autoScalerWrapper.BadCredsRoleName,
            _autoScalerWrapper.BadCredsProfileName,
            ssmOnlyPolicy,
            new List<string> { "AmazonSSMManagedInstanceCore" }
        );
        var instances = await
_autoScalerWrapper.GetInstancesByGroupName(_autoScalerWrapper.GroupName);
        var badInstanceId = instances.First();
        var instanceProfile = await
_autoScalerWrapper.GetInstanceProfile(badInstanceId);
        Console.WriteLine(
            $"Replacing the profile for instance {badInstanceId} with a profile that
contains\n" +
            "bad credentials...\n"
        );
        await _autoScalerWrapper.ReplaceInstanceProfile(
            badInstanceId,
            _autoScalerWrapper.BadCredsProfileName,
            instanceProfile.AssociationId
        );
        Console.WriteLine(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n" +
            "depending on which instance is selected by the load balancer.\n"
        );
        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nLet's implement a deep health check. For this demo, a
deep health check tests whether");
        Console.WriteLine("the web service can access the DynamoDB table that it
depends on for recommendations. Note that");
        Console.WriteLine("the deep health check is only for ELB routing and not for
Auto Scaling instance health.");
        Console.WriteLine("This kind of deep health check is not recommended for
Auto Scaling instance health, because it");
        Console.WriteLine("risks accidental termination of all instances in the Auto
Scaling group when a dependent service fails.");
```

```
        Console.WriteLine("\nBy implementing deep health checks, the load balancer
can detect when one of the instances is failing");
        Console.WriteLine("and take that instance out of rotation.");

        await
_smParameterWrapper.PutParameterByName(_smParameterWrapper.HealthCheckParameter,
"deep");

        Console.WriteLine($"\nNow, checking target health indicates that the
instance with bad credentials ({badInstanceId})");
        Console.WriteLine("is unhealthy. Note that it might take a minute or two for
the load balancer to detect the unhealthy");
        Console.WriteLine("instance. Sending a GET request to the load balancer
endpoint always returns a recommendation, because");
        Console.WriteLine("the load balancer takes unhealthy instances out of its
rotation.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nBecause the instances in this demo are controlled by an
auto scaler, the simplest way to fix an unhealthy");
        Console.WriteLine("instance is to terminate it and let the auto scaler start
a new instance to replace it.");

        await _autoScalerWrapper.TryTerminateInstanceById(badInstanceId);

        Console.WriteLine($"\nEven while the instance is terminating and the new
instance is starting, sending a GET");
        Console.WriteLine("request to the web service continues to get a successful
recommendation response because");
        Console.WriteLine("starts and reports as healthy, it is included in the load
balancing rotation.");
        Console.WriteLine("Note that terminating and replacing an instance typically
takes several minutes, during which time you");
        Console.WriteLine("can see the changing health check status until the new
instance is running and healthy.");

        if (interactive)
            await DemoActionChoices();

        Console.WriteLine("\nIf the recommendation service fails now, deep health
checks mean all instances report as unhealthy.");
```

```
        await
 _smParameterWrapper.PutParameterByName(_smParameterWrapper.TableParameter, "this-
is-not-a-table");

        Console.WriteLine($"\nWhen all instances are unhealthy, the load balancer
 continues to route requests even to");
        Console.WriteLine("unhealthy instances, allowing them to fail open and
 return a static response rather than fail");
        Console.WriteLine("closed and report failure to the customer.");

        if (interactive)
            await DemoActionChoices();
        await _smParameterWrapper.Reset();

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="interactive">True to ask the user for cleanup.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> DestroyResources(bool interactive)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            "To keep things tidy and to avoid unwanted charges on your account, we
 can clean up all AWS resources\n" +
            "that were created for this demo."
        );

        if (!interactive || GetYesNoResponse("Do you want to clean up all demo
 resources? (y/n) "))
        {
            await
 _elasticLoadBalancerWrapper.DeleteLoadBalancerByName(_elasticLoadBalancerWrapper.LoadBalanc
            await
 _elasticLoadBalancerWrapper.DeleteTargetGroupByName(_elasticLoadBalancerWrapper.TargetGroup
            await
 _autoScalerWrapper.TerminateAndDeleteAutoScalingGroupWithName(_autoScalerWrapper.GroupName)
            await
 _autoScalerWrapper.DeleteKeyPairByName(_autoScalerWrapper.KeyPairName);
```

```
            await
 _autoScalerWrapper.DeleteTemplateByName(_autoScalerWrapper.LaunchTemplateName);
            await _autoScalerWrapper.DeleteInstanceProfile(
                _autoScalerWrapper.BadCredsProfileName,
                _autoScalerWrapper.BadCredsRoleName
            );
            await
 _recommendations.DestroyDatabaseByName(_recommendations.TableName);
        }
        else
        {
            Console.WriteLine(
                "Ok, we'll leave the resources intact.\n" +
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            );
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
/// <summary>
/// Encapsulates Amazon EC2 Auto Scaling and EC2 management methods.
/// </summary>
public class AutoScalerWrapper
{
    private readonly IAmazonAutoScaling _amazonAutoScaling;
    private readonly IAmazonEC2 _amazonEc2;
    private readonly IAmazonSimpleSystemsManagement _amazonSsm;
    private readonly IAmazonIdentityManagementService _amazonIam;

    private readonly string _instanceType = "";
    private readonly string _amiParam = "";
    private readonly string _launchTemplateName = "";
    private readonly string _groupName = "";
    private readonly string _instancePolicyName = "";
    private readonly string _instanceRoleName = "";
    private readonly string _instanceProfileName = "";
    private readonly string _badCredsProfileName = "";
```

```
    private readonly string _badCredsRoleName = "";
    private readonly string _badCredsPolicyName = "";
    private readonly string _keyPairName = "";

    public string GroupName => _groupName;
    public string KeyPairName => _keyPairName;
    public string LaunchTemplateName => _launchTemplateName;
    public string InstancePolicyName => _instancePolicyName;
    public string BadCredsProfileName => _badCredsProfileName;
    public string BadCredsRoleName => _badCredsRoleName;
    public string BadCredsPolicyName => _badCredsPolicyName;

    /// <summary>
    /// Constructor for the AutoScalerWrapper.
    /// </summary>
    /// <param name="amazonAutoScaling">The injected AutoScaling client.</param>
    /// <param name="amazonEc2">The injected EC2 client.</param>
    /// <param name="amazonIam">The injected IAM client.</param>
    /// <param name="amazonSsm">The injected SSM client.</param>
    public AutoScalerWrapper(
        IAmazonAutoScaling amazonAutoScaling,
        IAmazonEC2 amazonEc2,
        IAmazonSimpleSystemsManagement amazonSsm,
        IAmazonIdentityManagementService amazonIam,
        IConfiguration configuration)
    {
        _amazonAutoScaling = amazonAutoScaling;
        _amazonEc2 = amazonEc2;
        _amazonSsm = amazonSsm;
        _amazonIam = amazonIam;

        var prefix = configuration["resourcePrefix"];
        _instanceType = configuration["instanceType"];
        _amiParam = configuration["amiParam"];

        _launchTemplateName = prefix + "-template";
        _groupName = prefix + "-group";
        _instancePolicyName = prefix + "-pol";
        _instanceRoleName = prefix + "-role";
        _instanceProfileName = prefix + "-prof";
        _badCredsPolicyName = prefix + "-bc-pol";
        _badCredsRoleName = prefix + "-bc-role";
        _badCredsProfileName = prefix + "-bc-prof";
        _keyPairName = prefix + "-key-pair";
```

```
    }

    /// <summary>
    /// Create a policy, role, and profile that is associated with instances with a
specified name.
    /// An instance's associated profile defines a role that is assumed by the
    /// instance.The role has attached policies that specify the AWS permissions
granted to
    /// clients that run on the instance.
    /// </summary>
    /// <param name="policyName">Name to use for the policy.</param>
    /// <param name="roleName">Name to use for the role.</param>
    /// <param name="profileName">Name to use for the profile.</param>
    /// <param name="ssmOnlyPolicyFile">Path to a policy file for SSM.</param>
    /// <param name="awsManagedPolicies">AWS Managed policies to be attached to the
role.</param>
    /// <returns>The Arn of the profile.</returns>
    public async Task<string> CreateInstanceProfileWithName(
        string policyName,
        string roleName,
        string profileName,
        string ssmOnlyPolicyFile,
        List<string>? awsManagedPolicies = null)
    {

        var assumeRoleDoc = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                     "\"Service\": [" +
                                         "\"ec2.amazonaws.com\"" +
                                     "]" +
                                     "}," +
                                "\"Action\": \"sts:AssumeRole\"" +
                                "}]" +
                            "}";

        var policyDocument = await File.ReadAllTextAsync(ssmOnlyPolicyFile);

        var policyArn = "";

        try
        {
```

```
            var createPolicyResult = await _amazonIam.CreatePolicyAsync(
                new CreatePolicyRequest
                {
                    PolicyName = policyName,
                    PolicyDocument = policyDocument
                });
            policyArn = createPolicyResult.Policy.Arn;
        }
        catch (EntityAlreadyExistsException)
        {
            // The policy already exists, so we look it up to get the Arn.
            var policiesPaginator = _amazonIam.Paginators.ListPolicies(
                new ListPoliciesRequest()
                {
                    Scope = PolicyScopeType.Local
                });
            // Get the entire list using the paginator.
            await foreach (var policy in policiesPaginator.Policies)
            {
                if (policy.PolicyName.Equals(policyName))
                {
                    policyArn = policy.Arn;
                }
            }

            if (policyArn == null)
            {
                throw new InvalidOperationException("Policy not found");
            }
        }

        try
        {
            await _amazonIam.CreateRoleAsync(new CreateRoleRequest()
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = assumeRoleDoc,
            });
            await _amazonIam.AttachRolePolicyAsync(new AttachRolePolicyRequest()
            {
                RoleName = roleName,
                PolicyArn = policyArn
            });
            if (awsManagedPolicies != null)
```

```
            {
                foreach (var awsPolicy in awsManagedPolicies)
                {
                    await _amazonIam.AttachRolePolicyAsync(new
AttachRolePolicyRequest()
                    {
                        PolicyArn = $"arn:aws:iam::aws:policy/{awsPolicy}",
                        RoleName = roleName
                    });
                }
            }
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Role already exists.");
        }

        string profileArn = "";
        try
        {
            var profileCreateResponse = await _amazonIam.CreateInstanceProfileAsync(
                new CreateInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
            // Allow time for the profile to be ready.
            profileArn = profileCreateResponse.InstanceProfile.Arn;
            Thread.Sleep(10000);
            await _amazonIam.AddRoleToInstanceProfileAsync(
                new AddRoleToInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });

        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine("Policy already exists.");
            var profileGetResponse = await _amazonIam.GetInstanceProfileAsync(
                new GetInstanceProfileRequest()
                {
                    InstanceProfileName = profileName
                });
```

```
            profileArn = profileGetResponse.InstanceProfile.Arn;
        }
        return profileArn;
    }

    /// <summary>
    /// Create a new key pair and save the file.
    /// </summary>
    /// <param name="newKeyPairName">The name of the new key pair.</param>
    /// <returns>Async task.</returns>
    public async Task CreateKeyPair(string newKeyPairName)
    {
        try
        {
            var keyResponse = await _amazonEc2.CreateKeyPairAsync(
                new CreateKeyPairRequest() { KeyName = newKeyPairName });
            await File.WriteAllTextAsync($"{newKeyPairName}.pem",
                keyResponse.KeyPair.KeyMaterial);
            Console.WriteLine($"Created key pair {newKeyPairName}.");
        }
        catch (AlreadyExistsException)
        {
            Console.WriteLine("Key pair already exists.");
        }
    }

    /// <summary>
    /// Delete the key pair and file by name.
    /// </summary>
    /// <param name="deleteKeyPairName">The key pair to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteKeyPairByName(string deleteKeyPairName)
    {
        try
        {
            await _amazonEc2.DeleteKeyPairAsync(
                new DeleteKeyPairRequest() { KeyName = deleteKeyPairName });
            File.Delete($"{deleteKeyPairName}.pem");
        }
        catch (FileNotFoundException)
        {
            Console.WriteLine($"Key pair {deleteKeyPairName} not found.");
        }
    }
```

```
   /// <summary>
   /// Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
   /// The launch template specifies a Bash script in its user data field that runs
after
   /// the instance is started. This script installs the Python packages and starts
a Python
   /// web server on the instance.
   /// </summary>
   /// <param name="startupScriptPath">The path to a Bash script file that is
run.</param>
   /// <param name="instancePolicyPath">The path to a permissions policy to create
and attach to the profile.</param>
   /// <returns>The template object.</returns>
   public async Task<Amazon.EC2.Model.LaunchTemplate> CreateTemplate(string
startupScriptPath, string instancePolicyPath)
   {
       await CreateKeyPair(_keyPairName);
       await CreateInstanceProfileWithName(_instancePolicyName, _instanceRoleName,
_instanceProfileName, instancePolicyPath);

       var startServerText = await File.ReadAllTextAsync(startupScriptPath);
       var plainTextBytes = System.Text.Encoding.UTF8.GetBytes(startServerText);

       var amiLatest = await _amazonSsm.GetParameterAsync(
           new GetParameterRequest() { Name = _amiParam });
       var amiId = amiLatest.Parameter.Value;
       var launchTemplateResponse = await _amazonEc2.CreateLaunchTemplateAsync(
           new CreateLaunchTemplateRequest()
           {
               LaunchTemplateName = _launchTemplateName,
               LaunchTemplateData = new RequestLaunchTemplateData()
               {
                   InstanceType = _instanceType,
                   ImageId = amiId,
                   IamInstanceProfile =
                       new
                           LaunchTemplateIamInstanceProfileSpecificationRequest()
                       {
                           Name = _instanceProfileName
                       },
                   KeyName = _keyPairName,
                   UserData = System.Convert.ToBase64String(plainTextBytes)
               }
```

```
            });
        return launchTemplateResponse.LaunchTemplate;

    }

    /// <summary>
    /// Get a list of Availability Zones in the AWS Region of the Amazon EC2 Client.
    /// </summary>
    /// <returns>A list of availability zones.</returns>
    public async Task<List<string>> DescribeAvailabilityZones()
    {
        var zoneResponse = await _amazonEc2.DescribeAvailabilityZonesAsync(
            new DescribeAvailabilityZonesRequest());
        return zoneResponse.AvailabilityZones.Select(z => z.ZoneName).ToList();
    }

    /// <summary>
    /// Create an EC2 Auto Scaling group of a specified size and name.
    /// </summary>
    /// <param name="groupSize">The size for the group.</param>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="availabilityZones">The availability zones for the group.</
param>
    /// <returns>Async task.</returns>
    public async Task CreateGroupOfSize(int groupSize, string groupName,
 List<string> availabilityZones)
    {
        try
        {
            await _amazonAutoScaling.CreateAutoScalingGroupAsync(
                new CreateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    AvailabilityZones = availabilityZones,
                    LaunchTemplate =
                        new Amazon.AutoScaling.Model.LaunchTemplateSpecification()
                        {
                            LaunchTemplateName = _launchTemplateName,
                            Version = "$Default"
                        },
                    MaxSize = groupSize,
                    MinSize = groupSize
                });
```

```
            Console.WriteLine($"Created EC2 Auto Scaling group {groupName} with size
{groupSize}.");
        }
        catch (EntityAlreadyExistsException)
        {
            Console.WriteLine($"EC2 Auto Scaling group {groupName} already
exists.");
        }
    }

    /// <summary>
    /// Get the default VPC for the account.
    /// </summary>
    /// <returns>The default VPC object.</returns>
    public async Task<Vpc> GetDefaultVpc()
    {
        var vpcResponse = await _amazonEc2.DescribeVpcsAsync(
            new DescribeVpcsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("is-default", new List<string>() { "true" })
                }
            });
        return vpcResponse.Vpcs[0];
    }

    /// <summary>
    /// Get all the subnets for a Vpc in a set of availability zones.
    /// </summary>
    /// <param name="vpcId">The Id of the Vpc.</param>
    /// <param name="availabilityZones">The list of availability zones.</param>
    /// <returns>The collection of subnet objects.</returns>
    public async Task<List<Subnet>> GetAllVpcSubnetsForZones(string vpcId,
List<string> availabilityZones)
    {
        var subnets = new List<Subnet>();
        var subnetPaginator = _amazonEc2.Paginators.DescribeSubnets(
            new DescribeSubnetsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("vpc-id", new List<string>() { vpcId}),
                    new ("availability-zone", availabilityZones),
```

```
                    new ("default-for-az", new List<string>() { "true" })
                }
            });

        // Get the entire list using the paginator.
        await foreach (var subnet in subnetPaginator.Subnets)
        {
            subnets.Add(subnet);
        }

        return subnets;
    }

    /// <summary>
    /// Delete a launch template by name.
    /// </summary>
    /// <param name="templateName">The name of the template to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTemplateByName(string templateName)
    {
        try
        {
            await _amazonEc2.DeleteLaunchTemplateAsync(
                new DeleteLaunchTemplateRequest()
                {
                    LaunchTemplateName = templateName
                });
        }
        catch (AmazonClientException)
        {
            Console.WriteLine($"Unable to delete template {templateName}.");
        }
    }

    /// <summary>
    /// Detaches a role from an instance profile, detaches policies from the role,
    /// and deletes all the resources.
    /// </summary>
    /// <param name="profileName">The name of the profile to delete.</param>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteInstanceProfile(string profileName, string roleName)
    {
        try
```

```
        {
            await _amazonIam.RemoveRoleFromInstanceProfileAsync(
                new RemoveRoleFromInstanceProfileRequest()
                {
                    InstanceProfileName = profileName,
                    RoleName = roleName
                });
            await _amazonIam.DeleteInstanceProfileAsync(
                new DeleteInstanceProfileRequest() { InstanceProfileName =
profileName });
            var attachedPolicies = await _amazonIam.ListAttachedRolePoliciesAsync(
                new ListAttachedRolePoliciesRequest() { RoleName = roleName });
            foreach (var policy in attachedPolicies.AttachedPolicies)
            {
                await _amazonIam.DetachRolePolicyAsync(
                    new DetachRolePolicyRequest()
                    {
                        RoleName = roleName,
                        PolicyArn = policy.PolicyArn
                    });
                // Delete the custom policies only.
                if (!policy.PolicyArn.StartsWith("arn:aws:iam::aws"))
                {
                    await _amazonIam.DeletePolicyAsync(
                        new Amazon.IdentityManagement.Model.DeletePolicyRequest()
                        {
                            PolicyArn = policy.PolicyArn
                        });
                }
            }

            await _amazonIam.DeleteRoleAsync(
                new DeleteRoleRequest() { RoleName = roleName });
        }
        catch (NoSuchEntityException)
        {
            Console.WriteLine($"Instance profile {profileName} does not exist.");
        }
    }

    /// <summary>
    /// Gets data about the instances in an EC2 Auto Scaling group by its group
name.
    /// </summary>
```

```
    /// <param name="group">The name of the auto scaling group.</param>
    /// <returns>A collection of instance Ids.</returns>
    public async Task<IEnumerable<string>> GetInstancesByGroupName(string group)
    {
        var instanceResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { group }
            });
        var instanceIds = instanceResponse.AutoScalingGroups.SelectMany(
            g => g.Instances.Select(i => i.InstanceId));
        return instanceIds;
    }

    /// <summary>
    /// Get the instance profile association data for an instance.
    /// </summary>
    /// <param name="instanceId">The Id of the instance.</param>
    /// <returns>Instance profile associations data.</returns>
    public async Task<IamInstanceProfileAssociation> GetInstanceProfile(string
instanceId)
    {
        var response = await _amazonEc2.DescribeIamInstanceProfileAssociationsAsync(
            new DescribeIamInstanceProfileAssociationsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("instance-id", new List<string>() { instanceId })
                },
            });
        return response.IamInstanceProfileAssociations[0];
    }

    /// <summary>
    /// Replace the profile associated with a running instance. After the profile is
replaced, the instance
    /// is rebooted to ensure that it uses the new profile. When the instance is
ready, Systems Manager is
    /// used to restart the Python web server.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to update.</param>
    /// <param name="credsProfileName">The name of the new profile to associate with
the specified instance.</param>
```

```
   /// <param name="associationId">The Id of the existing profile association for
the instance.</param>
   /// <returns>Async task.</returns>
   public async Task ReplaceInstanceProfile(string instanceId, string
credsProfileName, string associationId)
   {
       await _amazonEc2.ReplaceIamInstanceProfileAssociationAsync(
               new ReplaceIamInstanceProfileAssociationRequest()
               {
                   AssociationId = associationId,
                   IamInstanceProfile = new IamInstanceProfileSpecification()
                   {
                       Name = credsProfileName
                   }
               });
       // Allow time before resetting.
       Thread.Sleep(25000);
       var instanceReady = false;
       var retries = 5;
       while (retries-- > 0 && !instanceReady)
       {
           await _amazonEc2.RebootInstancesAsync(
               new RebootInstancesRequest(new List<string>() { instanceId }));
           Thread.Sleep(10000);

           var instancesPaginator =
_amazonSsm.Paginators.DescribeInstanceInformation(
               new DescribeInstanceInformationRequest());
           // Get the entire list using the paginator.
           await foreach (var instance in
instancesPaginator.InstanceInformationList)
           {
               instanceReady = instance.InstanceId == instanceId;
               if (instanceReady)
               {
                   break;
               }
           }
       }
       Console.WriteLine($"Sending restart command to instance {instanceId}");
       await _amazonSsm.SendCommandAsync(
           new SendCommandRequest()
           {
               InstanceIds = new List<string>() { instanceId },
```

```
                DocumentName = "AWS-RunShellScript",
                Parameters = new Dictionary<string, List<string>>()
                {
                        {"commands", new List<string>() { "cd / && sudo python3
server.py 80" }}
                }
            });
        Console.WriteLine($"Restarted the web server on instance {instanceId}");
    }

    /// <summary>
    /// Try to terminate an instance by its Id.
    /// </summary>
    /// <param name="instanceId">The Id of the instance to terminate.</param>
    /// <returns>Async task.</returns>
    public async Task TryTerminateInstanceById(string instanceId)
    {
        var stopping = false;
        Console.WriteLine($"Stopping {instanceId}...");
        while (!stopping)
        {
            try
            {
                await _amazonAutoScaling.TerminateInstanceInAutoScalingGroupAsync(
                    new TerminateInstanceInAutoScalingGroupRequest()
                    {
                        InstanceId = instanceId,
                        ShouldDecrementDesiredCapacity = false
                    });
                stopping = true;
            }
            catch (ScalingActivityInProgressException)
            {
                Console.WriteLine($"Scaling activity in progress for {instanceId}.
Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
    /// waits and retries until the group is successfully deleted.
```

```
    /// </summary>
    /// <param name="groupName">The name of the group to try to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TryDeleteGroupByName(string groupName)
    {
        var stopped = false;
        while (!stopped)
        {
            try
            {
                await _amazonAutoScaling.DeleteAutoScalingGroupAsync(
                    new DeleteAutoScalingGroupRequest()
                    {
                        AutoScalingGroupName = groupName
                    });
                stopped = true;
            }
            catch (Exception e)
                when ((e is ScalingActivityInProgressException)
                      || (e is Amazon.AutoScaling.Model.ResourceInUseException))
            {
                Console.WriteLine($"Some instances are still running. Waiting...");
                Thread.Sleep(10000);
            }
        }
    }

    /// <summary>
    /// Terminate instances and delete the Auto Scaling group by name.
    /// </summary>
    /// <param name="groupName">The name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task TerminateAndDeleteAutoScalingGroupWithName(string groupName)
    {
        var describeGroupsResponse = await
_amazonAutoScaling.DescribeAutoScalingGroupsAsync(
            new DescribeAutoScalingGroupsRequest()
            {
                AutoScalingGroupNames = new List<string>() { groupName }
            });
        if (describeGroupsResponse.AutoScalingGroups.Any())
        {
            // Update the size to 0.
            await _amazonAutoScaling.UpdateAutoScalingGroupAsync(
```

```
                new UpdateAutoScalingGroupRequest()
                {
                    AutoScalingGroupName = groupName,
                    MinSize = 0
                });
            var group = describeGroupsResponse.AutoScalingGroups[0];
            foreach (var instance in group.Instances)
            {
                await TryTerminateInstanceById(instance.InstanceId);
            }

            await TryDeleteGroupByName(groupName);
        }
        else
        {
            Console.WriteLine($"No groups found with name {groupName}.");
        }
    }


    /// <summary>
    /// Get the default security group for a specified Vpc.
    /// </summary>
    /// <param name="vpc">The Vpc to search.</param>
    /// <returns>The default security group.</returns>
    public async Task<SecurityGroup> GetDefaultSecurityGroupForVpc(Vpc vpc)
    {
        var groupResponse = await _amazonEc2.DescribeSecurityGroupsAsync(
            new DescribeSecurityGroupsRequest()
            {
                Filters = new List<Amazon.EC2.Model.Filter>()
                {
                    new ("group-name", new List<string>() { "default" }),
                    new ("vpc-id", new List<string>() { vpc.VpcId })
                }
            });
        return groupResponse.SecurityGroups[0];
    }

    /// <summary>
    /// Verify the default security group of a Vpc allows ingress from the calling
 computer.
    /// This can be done by allowing ingress from this computer's IP address.
```

```
   /// In some situations, such as connecting from a corporate network, you must
instead specify
   /// a prefix list Id. You can also temporarily open the port to any IP address
while running this example.
   /// If you do, be sure to remove public access when you're done.
   /// </summary>
   /// <param name="vpc">The group to check.</param>
   /// <param name="port">The port to verify.</param>
   /// <param name="ipAddress">This computer's IP address.</param>
   /// <returns>True if the ip address is allowed on the group.</returns>
   public bool VerifyInboundPortForGroup(SecurityGroup group, int port, string
ipAddress)
   {
       var portIsOpen = false;
       foreach (var ipPermission in group.IpPermissions)
       {
           if (ipPermission.FromPort == port)
           {
               foreach (var ipRange in ipPermission.Ipv4Ranges)
               {
                   var cidr = ipRange.CidrIp;
                   if (cidr.StartsWith(ipAddress) || cidr == "0.0.0.0/0")
                   {
                       portIsOpen = true;
                   }
               }

               if (ipPermission.PrefixListIds.Any())
               {
                   portIsOpen = true;
               }

               if (!portIsOpen)
               {
                   Console.WriteLine("The inbound rule does not appear to be open
to either this computer's IP\n" +
                                     "address, to all IP addresses (0.0.0.0/0), or
to a prefix list ID.");
               }
               else
               {
                   break;
               }
           }
```

```
        }

        return portIsOpen;
    }

    /// <summary>
    /// Add an ingress rule to the specified security group that allows access on
 the
    /// specified port from the specified IP address.
    /// </summary>
    /// <param name="groupId">The Id of the security group to modify.</param>
    /// <param name="port">The port to open.</param>
    /// <param name="ipAddress">The IP address to allow access.</param>
    /// <returns>Async task.</returns>
    public async Task OpenInboundPort(string groupId, int port, string ipAddress)
    {
        await _amazonEc2.AuthorizeSecurityGroupIngressAsync(
            new AuthorizeSecurityGroupIngressRequest()
            {
                GroupId = groupId,
                IpPermissions = new List<IpPermission>()
                {
                    new IpPermission()
                    {
                        FromPort = port,
                        ToPort = port,
                        IpProtocol = "tcp",
                        Ipv4Ranges = new List<IpRange>()
                        {
                            new IpRange() { CidrIp = $"{ipAddress}/32" }
                        }
                    }
                }
            });
    }

    /// <summary>
    /// Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
 Scaling group.
    /// The
    /// </summary>
    /// <param name="autoScalingGroupName">The name of the Auto Scaling group.</
param>
    /// <param name="targetGroupArn">The Arn for the target group.</param>
```

```
    /// <returns>Async task.</returns>
    public async Task AttachLoadBalancerToGroup(string autoScalingGroupName, string
 targetGroupArn)
    {
        await _amazonAutoScaling.AttachLoadBalancerTargetGroupsAsync(
            new AttachLoadBalancerTargetGroupsRequest()
            {
                AutoScalingGroupName = autoScalingGroupName,
                TargetGroupARNs = new List<string>() { targetGroupArn }
            });
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
/// <summary>
/// Encapsulates Elastic Load Balancer actions.
/// </summary>
public class ElasticLoadBalancerWrapper
{
    private readonly IAmazonElasticLoadBalancingV2 _amazonElasticLoadBalancingV2;
    private string? _endpoint = null;
    private readonly string _targetGroupName = "";
    private readonly string _loadBalancerName = "";
    HttpClient _httpClient = new();

    public string TargetGroupName => _targetGroupName;
    public string LoadBalancerName => _loadBalancerName;

    /// <summary>
    /// Constructor for the Elastic Load Balancer wrapper.
    /// </summary>
    /// <param name="amazonElasticLoadBalancingV2">The injected load balancing v2
 client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public ElasticLoadBalancerWrapper(
        IAmazonElasticLoadBalancingV2 amazonElasticLoadBalancingV2,
        IConfiguration configuration)
    {
        _amazonElasticLoadBalancingV2 = amazonElasticLoadBalancingV2;
        var prefix = configuration["resourcePrefix"];
```

```
        _targetGroupName = prefix + "-tg";
        _loadBalancerName = prefix + "-lb";
    }

    /// <summary>
    /// Get the HTTP Endpoint of a load balancer by its name.
    /// </summary>
    /// <param name="loadBalancerName">The name of the load balancer.</param>
    /// <returns>The HTTP endpoint.</returns>
    public async Task<string> GetEndpointForLoadBalancerByName(string
loadBalancerName)
    {
        if (_endpoint == null)
        {
            var endpointResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { loadBalancerName }
                    });
            _endpoint = endpointResponse.LoadBalancers[0].DNSName;
        }

        return _endpoint;
    }

    /// <summary>
    /// Return the GET response for an endpoint as text.
    /// </summary>
    /// <param name="endpoint">The endpoint for the request.</param>
    /// <returns>The request response.</returns>
    public async Task<string> GetEndPointResponse(string endpoint)
    {
        var endpointResponse = await _httpClient.GetAsync($"http://{endpoint}");
        var textResponse = await endpointResponse.Content.ReadAsStringAsync();
        return textResponse!;
    }

    /// <summary>
    /// Get the target health for a group by name.
    /// </summary>
    /// <param name="groupName">The name of the group.</param>
    /// <returns>The collection of health descriptions.</returns>
```

```
    public async Task<List<TargetHealthDescription>>
 CheckTargetHealthForGroup(string groupName)
    {
        List<TargetHealthDescription> result = null!;
        try
        {
            var groupResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                    new DescribeTargetGroupsRequest()
                    {
                        Names = new List<string>() { groupName }
                    });
            var healthResponse =
                await _amazonElasticLoadBalancingV2.DescribeTargetHealthAsync(
                    new DescribeTargetHealthRequest()
                    {
                        TargetGroupArn =
 groupResponse.TargetGroups[0].TargetGroupArn
                    });
            ;
            result = healthResponse.TargetHealthDescriptions;
        }
        catch (TargetGroupNotFoundException)
        {
            Console.WriteLine($"Target group {groupName} not found.");
        }
        return result;
    }

    /// <summary>
    /// Create an Elastic Load Balancing target group. The target group specifies
 how the load balancer forwards
    /// requests to instances in the group and how instance health is checked.
    ///
    /// To speed up this demo, the health check is configured with shortened times
 and lower thresholds. In production,
    /// you might want to decrease the sensitivity of your health checks to avoid
 unwanted failures.
    /// </summary>
    /// <param name="groupName">The name for the group.</param>
    /// <param name="protocol">The protocol, such as HTTP.</param>
    /// <param name="port">The port to use to forward requests, such as 80.</param>
    /// <param name="vpcId">The Id of the Vpc in which the load balancer exists.</
 param>
```

```
    /// <returns>The new TargetGroup object.</returns>
    public async Task<TargetGroup> CreateTargetGroupOnVpc(string groupName,
ProtocolEnum protocol, int port, string vpcId)
    {
        var createResponse = await
_amazonElasticLoadBalancingV2.CreateTargetGroupAsync(
            new CreateTargetGroupRequest()
            {
                Name = groupName,
                Protocol = protocol,
                Port = port,
                HealthCheckPath = "/healthcheck",
                HealthCheckIntervalSeconds = 10,
                HealthCheckTimeoutSeconds = 5,
                HealthyThresholdCount = 2,
                UnhealthyThresholdCount = 2,
                VpcId = vpcId
            });
        var targetGroup = createResponse.TargetGroups[0];
        return targetGroup;
    }

    /// <summary>
    /// Create an Elastic Load Balancing load balancer that uses the specified
subnets
    /// and forwards requests to the specified target group.
    /// </summary>
    /// <param name="name">The name for the new load balancer.</param>
    /// <param name="subnetIds">Subnets for the load balancer.</param>
    /// <param name="targetGroup">Target group for forwarded requests.</param>
    /// <returns>The new LoadBalancer object.</returns>
    public async Task<LoadBalancer> CreateLoadBalancerAndListener(string name,
List<string> subnetIds, TargetGroup targetGroup)
    {
        var createLbResponse = await
_amazonElasticLoadBalancingV2.CreateLoadBalancerAsync(
            new CreateLoadBalancerRequest()
            {
                Name = name,
                Subnets = subnetIds
            });
        var loadBalancerArn = createLbResponse.LoadBalancers[0].LoadBalancerArn;

        // Wait for load balancer to be available.
```

```
        var loadBalancerReady = false;
        while (!loadBalancerReady)
        {
            try
            {
                var describeResponse =
                    await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                        new DescribeLoadBalancersRequest()
                        {
                            Names = new List<string>() { name }
                        });

                var loadBalancerState =
describeResponse.LoadBalancers[0].State.Code;

                loadBalancerReady = loadBalancerState ==
LoadBalancerStateEnum.Active;
            }
            catch (LoadBalancerNotFoundException)
            {
                loadBalancerReady = false;
            }
            Thread.Sleep(10000);
        }
        // Create the listener.
        await _amazonElasticLoadBalancingV2.CreateListenerAsync(
            new CreateListenerRequest()
            {
                LoadBalancerArn = loadBalancerArn,
                Protocol = targetGroup.Protocol,
                Port = targetGroup.Port,
                DefaultActions = new List<Action>()
                {
                    new Action()
                    {
                        Type = ActionTypeEnum.Forward,
                        TargetGroupArn = targetGroup.TargetGroupArn
                    }
                }
            });
        return createLbResponse.LoadBalancers[0];
    }

    /// <summary>
```

```
    /// Verify this computer can successfully send a GET request to the
    /// load balancer endpoint.
    /// </summary>
    /// <param name="endpoint">The endpoint to check.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyLoadBalancerEndpoint(string endpoint)
    {
        var success = false;
        var retries = 3;
        while (!success && retries > 0)
        {
            try
            {
                var endpointResponse = await _httpClient.GetAsync($"http://
{endpoint}");
                Console.WriteLine($"Response: {endpointResponse.StatusCode}.");

                if (endpointResponse.IsSuccessStatusCode)
                {
                    success = true;
                }
                else
                {
                    retries = 0;
                }
            }
            catch (HttpRequestException)
            {
                Console.WriteLine("Connection error, retrying...");
                retries--;
                Thread.Sleep(10000);
            }
        }

        return success;
    }

    /// <summary>
    /// Delete a load balancer by its specified name.
    /// </summary>
    /// <param name="name">The name of the load balancer to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteLoadBalancerByName(string name)
    {
```

```
        try
        {
            var describeLoadBalancerResponse =
                await _amazonElasticLoadBalancingV2.DescribeLoadBalancersAsync(
                    new DescribeLoadBalancersRequest()
                    {
                        Names = new List<string>() { name }
                    });
            var lbArn =
describeLoadBalancerResponse.LoadBalancers[0].LoadBalancerArn;
            await _amazonElasticLoadBalancingV2.DeleteLoadBalancerAsync(
                new DeleteLoadBalancerRequest()
                {
                    LoadBalancerArn = lbArn
                }
            );
        }
        catch (LoadBalancerNotFoundException)
        {
            Console.WriteLine($"Load balancer {name} not found.");
        }
    }

    /// <summary>
    /// Delete a TargetGroup by its specified name.
    /// </summary>
    /// <param name="groupName">Name of the group to delete.</param>
    /// <returns>Async task.</returns>
    public async Task DeleteTargetGroupByName(string groupName)
    {
        var done = false;
        while (!done)
        {
            try
            {
                var groupResponse =
                    await _amazonElasticLoadBalancingV2.DescribeTargetGroupsAsync(
                        new DescribeTargetGroupsRequest()
                        {
                            Names = new List<string>() { groupName }
                        });

                var targetArn = groupResponse.TargetGroups[0].TargetGroupArn;
                await _amazonElasticLoadBalancingV2.DeleteTargetGroupAsync(
```

```
                    new DeleteTargetGroupRequest() { TargetGroupArn = targetArn });
                Console.WriteLine($"Deleted load balancing target group
 {groupName}.");
                done = true;
            }
            catch (TargetGroupNotFoundException)
            {
                Console.WriteLine(
                    $"Target group {groupName} not found, could not delete.");
                done = true;
            }
            catch (ResourceInUseException)
            {
                Console.WriteLine("Target group not yet released, waiting...");
                Thread.Sleep(10000);
            }
        }
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
/// <summary>
/// Encapsulates a DynamoDB table to use as a service that recommends books, movies,
 and songs.
/// </summary>
public class Recommendations
{
    private readonly IAmazonDynamoDB _amazonDynamoDb;
    private readonly DynamoDBContext _context;
    private readonly string _tableName;

    public string TableName => _tableName;

    /// <summary>
    /// Constructor for the Recommendations service.
    /// </summary>
    /// <param name="amazonDynamoDb">The injected DynamoDb client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public Recommendations(IAmazonDynamoDB amazonDynamoDb, IConfiguration
 configuration)
    {
```

```
        _amazonDynamoDb = amazonDynamoDb;
        _context = new DynamoDBContext(_amazonDynamoDb);
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Create the DynamoDb table with a specified name.
    /// </summary>
    /// <param name="tableName">The name for the table.</param>
    /// <returns>True when ready.</returns>
    public async Task<bool> CreateDatabaseWithName(string tableName)
    {
        try
        {
            Console.Write($"Creating table {tableName}...");
            var createRequest = new CreateTableRequest()
            {
                TableName = tableName,
                AttributeDefinitions = new List<AttributeDefinition>()
                    {
                        new AttributeDefinition()
                        {
                            AttributeName = "MediaType",
                            AttributeType = ScalarAttributeType.S
                        },
                        new AttributeDefinition()
                        {
                            AttributeName = "ItemId",
                            AttributeType = ScalarAttributeType.N
                        }
                    },
                KeySchema = new List<KeySchemaElement>()
                    {
                        new KeySchemaElement()
                        {
                            AttributeName = "MediaType",
                            KeyType = KeyType.HASH
                        },
                        new KeySchemaElement()
                        {
                            AttributeName = "ItemId",
                            KeyType = KeyType.RANGE
                        }
                    },
```

```
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 5,
                    WriteCapacityUnits = 5
                }
            };
            await _amazonDynamoDb.CreateTableAsync(createRequest);

            // Wait until the table is ACTIVE and then report success.
            Console.Write("\nWaiting for table to become active...");

            var request = new DescribeTableRequest
            {
                TableName = tableName
            };

            TableStatus status;
            do
            {
                Thread.Sleep(2000);

                var describeTableResponse = await
 _amazonDynamoDb.DescribeTableAsync(request);
                status = describeTableResponse.Table.TableStatus;

                Console.Write(".");
            }
            while (status != "ACTIVE");

            return status == TableStatus.ACTIVE;
        }
        catch (ResourceInUseException)
        {
            Console.WriteLine($"Table {tableName} already exists.");
            return false;
        }
    }

    /// <summary>
    /// Populate the database table with data from a specified path.
    /// </summary>
    /// <param name="databaseTableName">The name of the table.</param>
    /// <param name="recommendationsPath">The path of the recommendations data.</
param>
```

```
    /// <returns>Async task.</returns>
    public async Task PopulateDatabase(string databaseTableName, string
 recommendationsPath)
    {
        var recommendationsText = await File.ReadAllTextAsync(recommendationsPath);
        var records =
            JsonSerializer.Deserialize<RecommendationModel[]>(recommendationsText);
        var batchWrite = _context.CreateBatchWrite<RecommendationModel>();

        foreach (var record in records!)
        {
            batchWrite.AddPutItem(record);
        }

        await batchWrite.ExecuteAsync();
    }

    /// <summary>
    /// Delete the recommendation table by name.
    /// </summary>
    /// <param name="tableName">The name of the recommendation table.</param>
    /// <returns>Async task.</returns>
    public async Task DestroyDatabaseByName(string tableName)
    {
        try
        {
            await _amazonDynamoDb.DeleteTableAsync(
                new DeleteTableRequest() { TableName = tableName });
            Console.WriteLine($"Table {tableName} was deleted.");
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"Table {tableName} not found");
        }
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
/// <summary>
/// Encapsulates Systems Manager parameter operations. This example uses these
 parameters
```

```
/// to drive the demonstration of resilient architecture, such as failure of a
 dependency or
/// how the service responds to a health check.
/// </summary>
public class SmParameterWrapper
{
    private readonly IAmazonSimpleSystemsManagement _amazonSimpleSystemsManagement;

    private readonly string _tableParameter = "doc-example-resilient-architecture-
table";
    private readonly string _failureResponseParameter = "doc-example-resilient-
architecture-failure-response";
    private readonly string _healthCheckParameter = "doc-example-resilient-
architecture-health-check";
    private readonly string _tableName = "";

    public string TableParameter => _tableParameter;
    public string TableName => _tableName;
    public string HealthCheckParameter => _healthCheckParameter;
    public string FailureResponseParameter => _failureResponseParameter;

    /// <summary>
    /// Constructor for the SmParameterWrapper.
    /// </summary>
    /// <param name="amazonSimpleSystemsManagement">The injected Simple Systems
 Management client.</param>
    /// <param name="configuration">The injected configuration.</param>
    public SmParameterWrapper(IAmazonSimpleSystemsManagement
 amazonSimpleSystemsManagement, IConfiguration configuration)
    {
        _amazonSimpleSystemsManagement = amazonSimpleSystemsManagement;
        _tableName = configuration["databaseName"]!;
    }

    /// <summary>
    /// Reset the Systems Manager parameters to starting values for the demo.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task Reset()
    {
        await this.PutParameterByName(_tableParameter, _tableName);
        await this.PutParameterByName(_failureResponseParameter, "none");
        await this.PutParameterByName(_healthCheckParameter, "shallow");
    }
```

```
    /// <summary>
    /// Set the value of a named Systems Manager parameter.
    /// </summary>
    /// <param name="name">The name of the parameter.</param>
    /// <param name="value">The value to set.</param>
    /// <returns>Async task.</returns>
    public async Task PutParameterByName(string name, string value)
    {
        await _amazonSimpleSystemsManagement.PutParameterAsync(
            new PutParameterRequest() { Name = name, Value = value, Overwrite =
 true });
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers

- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Criar um grupo e adicionar um usuário

O código de exemplo a seguir mostra como:

- Crie um grupo e conceda permissões de acesso completo ao Amazon S3 a ele.
- Crie um novo usuário sem permissões para acessar o Amazon S3.
- Adicione o usuário ao grupo e mostre que agora ele tem permissões para o Amazon S3. Em seguida, limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using Amazon.IdentityManagement;
global using Amazon.S3;
global using Amazon.SecurityToken;
global using IAMActions;
global using IamScenariosCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;
```

```
namespace IAMActions;

public class IAMWrapper
{
    private readonly IAmazonIdentityManagementService _IAMService;

    /// <summary>
    /// Constructor for the IAMWrapper class.
    /// </summary>
    /// <param name="IAMService">An IAM client object.</param>
    public IAMWrapper(IAmazonIdentityManagementService IAMService)
    {
        _IAMService = IAMService;
    }

    /// <summary>
    /// Add an existing IAM user to an existing IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
 AddUserToGroupRequest
        {
            GroupName = groupName,
            UserName = userName,
        });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string roleName)
    {
```

```
        var response = await _IAMService.AttachRolePolicyAsync(new
AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
    /// key.</param>
    /// <returns>The AccessKey.</returns>
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
        var response = await _IAMService.CreateAccessKeyAsync(new
CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;

    }


    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
{ GroupName = groupName });
        return response.Group;
    }


    /// <summary>
```

```
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });

        return response.Policy;
    }


    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
    public async Task<string> CreateRoleAsync(string roleName, string
rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }


    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
```

```
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName, string
 description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
    }


    /// <summary>
    /// Create an IAM user.
    /// </summary>
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
 { UserName = userName });
        return response.User;
    }


    /// <summary>
    /// Delete an IAM user's access key.
    /// </summary>
    /// <param name="accessKeyId">The Id for the IAM access key.</param>
    /// <param name="userName">The username of the user that owns the IAM
    /// access key.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
 userName)
    {
        var response = await _IAMService.DeleteAccessKeyAsync(new
 DeleteAccessKeyRequest
        {
            AccessKeyId = accessKeyId,
```

```
            UserName = userName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
{ GroupName = groupName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
```

```
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new DeletePolicyRequest
{ PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
{ RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="policyName">The name of the IAM role policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Delete an IAM user.
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
 { UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
 userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
 DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Detach an IAM policy from an IAM role.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM policy.</
param>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DetachRolePolicyAsync(string policyArn, string roleName)
    {
        var response = await _IAMService.DetachRolePolicyAsync(new
 DetachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
```

```
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
GetAccountPasswordPolicyRequest());
        return response.PasswordPolicy;
    }


    /// <summary>
    /// Get information about an IAM policy.
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
{ PolicyArn = policyArn });
        return response.Policy;
    }


    /// <summary>
    /// Get information about an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });
```

```
        return response.Role;
    }


    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
    {
        var response = await _IAMService.GetUserAsync(new GetUserRequest { UserName
= userName });
        return response.User;
    }


    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
    public async Task<List<AttachedPolicyType>> ListAttachedRolePoliciesAsync(string
roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
_IAMService.Paginators.ListAttachedRolePolicies(new ListAttachedRolePoliciesRequest
{ RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }


    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
```

```
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }

        return groups;
    }


    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        return policies;
    }


    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
        var listRolePoliciesPaginator = _IAMService.Paginators.ListRolePolicies(new
ListRolePoliciesRequest { RoleName = roleName });
        var policyNames = new List<string>();
```

```
        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }


    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();

        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }


    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }


    /// <summary>
    /// List IAM users.
    /// </summary>
```

```
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
 ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }


    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
    /// <param name="groupName">The name of the IAM group to remove the user from.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
 groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
 _IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
```

```
    /// <param name="policyDocument">The policy document defining the IAM policy.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string policyName,
 string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Update the inline policy document embedded in a role.
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string roleName,
 string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM user.
    /// </summary>
```

```
    /// <param name="userName">The name of the IAM user.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM policy.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutUserPolicyAsync(string userName, string policyName,
 string policyDocument)
    {
        var request = new PutUserPolicyRequest
        {
            UserName = userName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutUserPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Wait for a new access key to be ready to use.
    /// </summary>
    /// <param name="accessKeyId">The Id of the access key.</param>
    /// <returns>A boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitUntilAccessKeyIsReady(string accessKeyId)
    {
        var keyReady = false;

        do
        {
            try
            {
                var response = await _IAMService.GetAccessKeyLastUsedAsync(
                    new GetAccessKeyLastUsedRequest { AccessKeyId = accessKeyId });
                if (response.UserName is not null)
                {
                    keyReady = true;
                }
            }
            catch (NoSuchEntityException)
            {
                keyReady = false;
            }
        } while (!keyReady);
```

```
        return keyReady;
    }
}


using Microsoft.Extensions.Configuration;

namespace IAMGroups;

public class IAMGroups
{
    private static ILogger logger = null!;

    // Represents JSON code for AWS full access policy for Amazon Simple
    // Storage Service (Amazon S3).
    private const string S3FullAccessPolicyDocument = "{" +
        " \"Statement\" : [{" +
            " \"Action\" : [\"s3:*\"]," +
            " \"Effect\" : \"Allow\"," +
            " \"Resource\" : \"*\"" +
        "}]" +
    "}";


    static async Task Main(string[] args)
    {
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<IAMWrapper>()
            .AddTransient<UIWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<IAMGroups>();
```

```
        IConfiguration configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var groupUserName = configuration["GroupUserName"];
        var groupName = configuration["GroupName"];
        var groupPolicyName = configuration["GroupPolicyName"];
        var groupBucketName = configuration["GroupBucketName"];

        var wrapper = host.Services.GetRequiredService<IAMWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        uiWrapper.DisplayGroupsOverview();
        uiWrapper.PressEnter();

        // Create an IAM group.
        uiWrapper.DisplayTitle("Create IAM group");
        Console.WriteLine("Let's begin by creating a new IAM group.");
        var group = await wrapper.CreateGroupAsync(groupName);

        // Add an inline IAM policy to the group.
        uiWrapper.DisplayTitle("Add policy to group");
        Console.WriteLine("Add an inline policy to the group that allows members to
have full access to");
        Console.WriteLine("Amazon Simple Storage Service (Amazon S3) buckets.");

        await wrapper.PutGroupPolicyAsync(group.GroupName, groupPolicyName,
S3FullAccessPolicyDocument);

        uiWrapper.PressEnter();

        // Now create a new user.
        uiWrapper.DisplayTitle("Create an IAM user");
        Console.WriteLine("Now let's create a new IAM user.");
        var groupUser = await wrapper.CreateUserAsync(groupUserName);

        // Add the new user to the group.
        uiWrapper.DisplayTitle("Add the user to the group");
        Console.WriteLine("Adding the user to the group, which will give the user
the same permissions as the group.");
        await wrapper.AddUserToGroupAsync(groupUser.UserName, group.GroupName);
```

```
        Console.WriteLine($"User, {groupUser.UserName}, has been added to the group,
{group.GroupName}.");
        uiWrapper.PressEnter();

        Console.WriteLine("Now that we have created a user, and added the user to
the group, let's create an IAM access key.");

        // Create access and secret keys for the user.
        var accessKey = await wrapper.CreateAccessKeyAsync(groupUserName);
        Console.WriteLine("Key created.");
        uiWrapper.WaitABit(15, "Waiting for the access key to be ready for use.");

        uiWrapper.DisplayTitle("List buckets");
        Console.WriteLine("To prove that the user has access to Amazon S3, list the
S3 buckets for the account.");

        var s3Client = new AmazonS3Client(accessKey.AccessKeyId,
accessKey.SecretAccessKey);
        var stsClient = new AmazonSecurityTokenServiceClient(accessKey.AccessKeyId,
accessKey.SecretAccessKey);

        var s3Wrapper = new S3Wrapper(s3Client, stsClient);

        var buckets = await s3Wrapper.ListMyBucketsAsync();

        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName}\tcreated on:
{bucket.CreationDate}");
            });
        }

        // Show that the user also has write access to Amazon S3 by creating
        // a new bucket.
        uiWrapper.DisplayTitle("Create a bucket");
        Console.WriteLine("Since group members have full access to Amazon S3, let's
create a bucket.");
        var success = await s3Wrapper.PutBucketAsync(groupBucketName);

        if (success)
        {
```

```
            Console.WriteLine($"Successfully created the bucket:
{groupBucketName}.");
        }

        uiWrapper.PressEnter();

        Console.WriteLine("Let's list the user's S3 buckets again to show the new
bucket.");

        buckets = await s3Wrapper.ListMyBucketsAsync();

        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName}\tcreated on:
{bucket.CreationDate}");
            });
        }

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("First delete the bucket we created.");
        await s3Wrapper.DeleteBucketAsync(groupBucketName);

        Console.WriteLine($"Now remove the user, {groupUserName}, from the group,
{groupName}.");
        await wrapper.RemoveUserFromGroupAsync(groupUserName, groupName);

        Console.WriteLine("Delete the user's access key.");
        await wrapper.DeleteAccessKeyAsync(accessKey.AccessKeyId, groupUserName);

        // Now we can safely delete the user.
        Console.WriteLine("Now we can delete the user.");
        await wrapper.DeleteUserAsync(groupUserName);

        uiWrapper.PressEnter();

        Console.WriteLine("Now we will delete the IAM policy attached to the
group.");
        await wrapper.DeleteGroupPolicyAsync(groupName, groupPolicyName);

        Console.WriteLine("Now we delete the IAM group.");
```

```
        await wrapper.DeleteGroupAsync(groupName);

        uiWrapper.PressEnter();

        Console.WriteLine("The IAM groups demo has completed.");

        uiWrapper.PressEnter();
    }
}


namespace IamScenariosCommon;

using System.Net;

/// <summary>
/// A class to perform Amazon Simple Storage Service (Amazon S3) actions for
/// the IAM Basics scenario.
/// </summary>
public class S3Wrapper
{
    private IAmazonS3 _s3Service;
    private IAmazonSecurityTokenService _stsService;

    /// <summary>
    /// Constructor for the S3Wrapper class.
    /// </summary>
    /// <param name="s3Service">An Amazon S3 client object.</param>
    /// <param name="stsService">An AWS Security Token Service (AWS STS)
    /// client object.</param>
    public S3Wrapper(IAmazonS3 s3Service, IAmazonSecurityTokenService stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }

    /// <summary>
    /// Assumes an AWS Identity and Access Management (IAM) role that allows
    /// Amazon S3 access for the current session.
    /// </summary>
    /// <param name="roleSession">A string representing the current session.</param>
    /// <param name="roleToAssume">The name of the IAM role to assume.</param>
    /// <returns>Credentials for the newly assumed IAM role.</returns>
```

```
    public async Task<Credentials> AssumeS3RoleAsync(string roleSession, string
roleToAssume)
    {
        // Create the request to use with the AssumeRoleAsync call.
        var request = new AssumeRoleRequest()
        {
            RoleSessionName = roleSession,
            RoleArn = roleToAssume,
        };

        var response = await _stsService.AssumeRoleAsync(request);

        return response.Credentials;
    }


    /// <summary>
    /// Delete an S3 bucket.
    /// </summary>
    /// <param name="bucketName">Name of the S3 bucket to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteBucketAsync(string bucketName)
    {
        var result = await _s3Service.DeleteBucketAsync(new DeleteBucketRequest
{ BucketName = bucketName });
        return result.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// List the buckets that are owned by the user's account.
    /// </summary>
    /// <returns>Async Task.</returns>
    public async Task<List<S3Bucket>?> ListMyBucketsAsync()
    {
        try
        {
            // Get the list of buckets accessible by the new user.
            var response = await _s3Service.ListBucketsAsync();

            return response.Buckets;
        }
        catch (AmazonS3Exception ex)
        {
            // Something else went wrong. Display the error message.
```

```
            Console.WriteLine($"Error: {ex.Message}");
            return null;
        }
    }

    /// <summary>
    /// Create a new S3 bucket.
    /// </summary>
    /// <param name="bucketName">The name for the new bucket.</param>
    /// <returns>A Boolean value indicating whether the action completed
    /// successfully.</returns>
    public async Task<bool> PutBucketAsync(string bucketName)
    {
        var response = await _s3Service.PutBucketAsync(new PutBucketRequest
 { BucketName = bucketName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Update the client objects with new client objects. This is available
    /// because the scenario uses the methods of this class without and then
    /// with the proper permissions to list S3 buckets.
    /// </summary>
    /// <param name="s3Service">The Amazon S3 client object.</param>
    /// <param name="stsService">The AWS STS client object.</param>
    public void UpdateClients(IAmazonS3 s3Service, IAmazonSecurityTokenService
 stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }
}


namespace IamScenariosCommon;

public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the IAM Groups scenario.
    /// </summary>
    public void DisplayGroupsOverview()
```

```
    {
        Console.Clear();

        DisplayTitle("Welcome to the IAM Groups Demo");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates an Amazon Identity and Access Management
(IAM) group.");
        Console.WriteLine("\t2. Adds an IAM policy to the IAM group giving it full
access to Amazon S3.");
        Console.WriteLine("\t3. Creates a new IAM user.");
        Console.WriteLine("\t4. Creates an IAM access key for the user.");
        Console.WriteLine("\t5. Adds the user to the IAM group.");
        Console.WriteLine("\t6. Lists the buckets on the account.");
        Console.WriteLine("\t7. Proves that the user has full Amazon S3 access by
creating a bucket.");
        Console.WriteLine("\t8. List the buckets again to show the new bucket.");
        Console.WriteLine("\t9. Cleans up all the resources created.");
    }

    /// <summary>
    /// Show information about the IAM Basics scenario.
    /// </summary>
    public void DisplayBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to IAM Basics");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates a user with no permissions.");
        Console.WriteLine("\t2. Creates a role and policy that grant
s3:ListAllMyBuckets permission.");
        Console.WriteLine("\t3. Grants the user permission to assume the role.");
        Console.WriteLine("\t4. Creates an S3 client object as the user and tries to
list buckets (this will fail).");
        Console.WriteLine("\t5. Gets temporary credentials by assuming the role.");
        Console.WriteLine("\t6. Creates a new S3 client object with the temporary
credentials and lists the buckets (this will succeed).");
        Console.WriteLine("\t7. Deletes all the resources.");
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
```

```
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }
```

```
        PressEnter();
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AddUserToGroup
  - AttachRolePolicy
  - CreateAccessKey
  - CreateGroup
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeleteGroup
  - DeleteGroupPolicy
  - DeleteUser
  - PutGroupPolicy
  - RemoveUserFromGroup

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.

- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using Amazon.IdentityManagement;
global using Amazon.S3;
global using Amazon.SecurityToken;
global using IAMActions;
global using IamScenariosCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;


namespace IAMActions;

public class IAMWrapper
{
    private readonly IAmazonIdentityManagementService _IAMService;

    /// <summary>
    /// Constructor for the IAMWrapper class.
    /// </summary>
    /// <param name="IAMService">An IAM client object.</param>
    public IAMWrapper(IAmazonIdentityManagementService IAMService)
    {
        _IAMService = IAMService;
    }

    /// <summary>
    /// Add an existing IAM user to an existing IAM group.
```

```
    /// </summary>
    /// <param name="userName">The username of the user to add.</param>
    /// <param name="groupName">The name of the group to add the user to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddUserToGroupAsync(string userName, string groupName)
    {
        var response = await _IAMService.AddUserToGroupAsync(new
AddUserToGroupRequest
        {
            GroupName = groupName,
            UserName = userName,
        });

        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Attach an IAM policy to a role.
    /// </summary>
    /// <param name="policyArn">The policy to attach.</param>
    /// <param name="roleName">The role that the policy will be attached to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachRolePolicyAsync(string policyArn, string roleName)
    {
        var response = await _IAMService.AttachRolePolicyAsync(new
AttachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Create an IAM access key for a user.
    /// </summary>
    /// <param name="userName">The username for which to create the IAM access
    /// key.</param>
    /// <returns>The AccessKey.</returns>
    public async Task<AccessKey> CreateAccessKeyAsync(string userName)
    {
```

```
        var response = await _IAMService.CreateAccessKeyAsync(new
CreateAccessKeyRequest
        {
            UserName = userName,
        });

        return response.AccessKey;

    }


    /// <summary>
    /// Create an IAM group.
    /// </summary>
    /// <param name="groupName">The name to give the IAM group.</param>
    /// <returns>The IAM group that was created.</returns>
    public async Task<Group> CreateGroupAsync(string groupName)
    {
        var response = await _IAMService.CreateGroupAsync(new CreateGroupRequest
{ GroupName = groupName });
        return response.Group;
    }


    /// <summary>
    /// Create an IAM policy.
    /// </summary>
    /// <param name="policyName">The name to give the new IAM policy.</param>
    /// <param name="policyDocument">The policy document for the new policy.</param>
    /// <returns>The new IAM policy object.</returns>
    public async Task<ManagedPolicy> CreatePolicyAsync(string policyName, string
policyDocument)
    {
        var response = await _IAMService.CreatePolicyAsync(new CreatePolicyRequest
        {
            PolicyDocument = policyDocument,
            PolicyName = policyName,
        });

        return response.Policy;
    }


    /// <summary>
```

```
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="rolePolicyDocument">The name of the IAM policy document
    /// for the new role.</param>
    /// <returns>The Amazon Resource Name (ARN) of the role.</returns>
    public async Task<string> CreateRoleAsync(string roleName, string
 rolePolicyDocument)
    {
        var request = new CreateRoleRequest
        {
            RoleName = roleName,
            AssumeRolePolicyDocument = rolePolicyDocument,
        };

        var response = await _IAMService.CreateRoleAsync(request);
        return response.Role.Arn;
    }


    /// <summary>
    /// Create an IAM service-linked role.
    /// </summary>
    /// <param name="serviceName">The name of the AWS Service.</param>
    /// <param name="description">A description of the IAM service-linked role.</
param>
    /// <returns>The IAM role that was created.</returns>
    public async Task<Role> CreateServiceLinkedRoleAsync(string serviceName, string
 description)
    {
        var request = new CreateServiceLinkedRoleRequest
        {
            AWSServiceName = serviceName,
            Description = description
        };

        var response = await _IAMService.CreateServiceLinkedRoleAsync(request);
        return response.Role;
    }


    /// <summary>
    /// Create an IAM user.
    /// </summary>
```

```
    /// <param name="userName">The username for the new IAM user.</param>
    /// <returns>The IAM user that was created.</returns>
    public async Task<User> CreateUserAsync(string userName)
    {
        var response = await _IAMService.CreateUserAsync(new CreateUserRequest
{ UserName = userName });
        return response.User;
    }


    /// <summary>
    /// Delete an IAM user's access key.
    /// </summary>
    /// <param name="accessKeyId">The Id for the IAM access key.</param>
    /// <param name="userName">The username of the user that owns the IAM
    /// access key.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteAccessKeyAsync(string accessKeyId, string
userName)
    {
        var response = await _IAMService.DeleteAccessKeyAsync(new
DeleteAccessKeyRequest
        {
            AccessKeyId = accessKeyId,
            UserName = userName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupAsync(string groupName)
    {
        var response = await _IAMService.DeleteGroupAsync(new DeleteGroupRequest
{ GroupName = groupName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Delete an IAM policy associated with an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group associated with the
    /// policy.</param>
    /// <param name="policyName">The name of the policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteGroupPolicyAsync(string groupName, string
policyName)
    {
        var request = new DeleteGroupPolicyRequest()
        {
            GroupName = groupName,
            PolicyName = policyName,
        };

        var response = await _IAMService.DeleteGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM policy.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the policy to
    /// delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeletePolicyAsync(string policyArn)
    {
        var response = await _IAMService.DeletePolicyAsync(new DeletePolicyRequest
{ PolicyArn = policyArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRoleAsync(string roleName)
    {
        var response = await _IAMService.DeleteRoleAsync(new DeleteRoleRequest
{ RoleName = roleName });
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM role policy.
    /// </summary>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <param name="policyName">The name of the IAM role policy to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteRolePolicyAsync(string roleName, string
policyName)
    {
        var response = await _IAMService.DeleteRolePolicyAsync(new
DeleteRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM user.
    /// </summary>
    /// <param name="userName">The username of the IAM user to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteUserAsync(string userName)
    {
        var response = await _IAMService.DeleteUserAsync(new DeleteUserRequest
{ UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete an IAM user policy.
    /// </summary>
    /// <param name="policyName">The name of the IAM policy to delete.</param>
    /// <param name="userName">The username of the IAM user.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
```

```
    public async Task<bool> DeleteUserPolicyAsync(string policyName, string
 userName)
    {
        var response = await _IAMService.DeleteUserPolicyAsync(new
 DeleteUserPolicyRequest { PolicyName = policyName, UserName = userName });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Detach an IAM policy from an IAM role.
    /// </summary>
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM policy.</
param>
    /// <param name="roleName">The name of the IAM role.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DetachRolePolicyAsync(string policyArn, string roleName)
    {
        var response = await _IAMService.DetachRolePolicyAsync(new
 DetachRolePolicyRequest
        {
            PolicyArn = policyArn,
            RoleName = roleName,
        });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Gets the IAM password policy for an AWS account.
    /// </summary>
    /// <returns>The PasswordPolicy for the AWS account.</returns>
    public async Task<PasswordPolicy> GetAccountPasswordPolicyAsync()
    {
        var response = await _IAMService.GetAccountPasswordPolicyAsync(new
 GetAccountPasswordPolicyRequest());
        return response.PasswordPolicy;
    }


    /// <summary>
    /// Get information about an IAM policy.
```

```
    /// </summary>
    /// <param name="policyArn">The IAM policy to retrieve information for.</param>
    /// <returns>The IAM policy.</returns>
    public async Task<ManagedPolicy> GetPolicyAsync(string policyArn)
    {

        var response = await _IAMService.GetPolicyAsync(new GetPolicyRequest
{ PolicyArn = policyArn });
        return response.Policy;
    }


    /// <summary>
    /// Get information about an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to retrieve information
    /// for.</param>
    /// <returns>The IAM role that was retrieved.</returns>
    public async Task<Role> GetRoleAsync(string roleName)
    {
        var response = await _IAMService.GetRoleAsync(new GetRoleRequest
        {
            RoleName = roleName,
        });

        return response.Role;
    }


    /// <summary>
    /// Get information about an IAM user.
    /// </summary>
    /// <param name="userName">The username of the user.</param>
    /// <returns>An IAM user object.</returns>
    public async Task<User> GetUserAsync(string userName)
    {
        var response = await _IAMService.GetUserAsync(new GetUserRequest { UserName
= userName });
        return response.User;
    }


    /// <summary>
    /// List the IAM role policies that are attached to an IAM role.
```

```
    /// </summary>
    /// <param name="roleName">The IAM role to list IAM policies for.</param>
    /// <returns>A list of the IAM policies attached to the IAM role.</returns>
    public async Task<List<AttachedPolicyType>> ListAttachedRolePoliciesAsync(string
roleName)
    {
        var attachedPolicies = new List<AttachedPolicyType>();
        var attachedRolePoliciesPaginator =
_IAMService.Paginators.ListAttachedRolePolicies(new ListAttachedRolePoliciesRequest
{ RoleName = roleName });

        await foreach (var response in attachedRolePoliciesPaginator.Responses)
        {
            attachedPolicies.AddRange(response.AttachedPolicies);
        }

        return attachedPolicies;
    }


    /// <summary>
    /// List IAM groups.
    /// </summary>
    /// <returns>A list of IAM groups.</returns>
    public async Task<List<Group>> ListGroupsAsync()
    {
        var groupsPaginator = _IAMService.Paginators.ListGroups(new
ListGroupsRequest());
        var groups = new List<Group>();

        await foreach (var response in groupsPaginator.Responses)
        {
            groups.AddRange(response.Groups);
        }

        return groups;
    }


    /// <summary>
    /// List IAM policies.
    /// </summary>
    /// <returns>A list of the IAM policies.</returns>
    public async Task<List<ManagedPolicy>> ListPoliciesAsync()
```

```
    {
        var listPoliciesPaginator = _IAMService.Paginators.ListPolicies(new
ListPoliciesRequest());
        var policies = new List<ManagedPolicy>();

        await foreach (var response in listPoliciesPaginator.Responses)
        {
            policies.AddRange(response.Policies);
        }

        return policies;
    }


    /// <summary>
    /// List IAM role policies.
    /// </summary>
    /// <param name="roleName">The IAM role for which to list IAM policies.</param>
    /// <returns>A list of IAM policy names.</returns>
    public async Task<List<string>> ListRolePoliciesAsync(string roleName)
    {
        var listRolePoliciesPaginator = _IAMService.Paginators.ListRolePolicies(new
ListRolePoliciesRequest { RoleName = roleName });
        var policyNames = new List<string>();

        await foreach (var response in listRolePoliciesPaginator.Responses)
        {
            policyNames.AddRange(response.PolicyNames);
        }

        return policyNames;
    }


    /// <summary>
    /// List IAM roles.
    /// </summary>
    /// <returns>A list of IAM roles.</returns>
    public async Task<List<Role>> ListRolesAsync()
    {
        var listRolesPaginator = _IAMService.Paginators.ListRoles(new
ListRolesRequest());
        var roles = new List<Role>();
```

```
        await foreach (var response in listRolesPaginator.Responses)
        {
            roles.AddRange(response.Roles);
        }

        return roles;
    }


    /// <summary>
    /// List SAML authentication providers.
    /// </summary>
    /// <returns>A list of SAML providers.</returns>
    public async Task<List<SAMLProviderListEntry>> ListSAMLProvidersAsync()
    {
        var response = await _IAMService.ListSAMLProvidersAsync(new
ListSAMLProvidersRequest());
        return response.SAMLProviderList;
    }


    /// <summary>
    /// List IAM users.
    /// </summary>
    /// <returns>A list of IAM users.</returns>
    public async Task<List<User>> ListUsersAsync()
    {
        var listUsersPaginator = _IAMService.Paginators.ListUsers(new
ListUsersRequest());
        var users = new List<User>();

        await foreach (var response in listUsersPaginator.Responses)
        {
            users.AddRange(response.Users);
        }

        return users;
    }


    /// <summary>
    /// Remove a user from an IAM group.
    /// </summary>
    /// <param name="userName">The username of the user to remove.</param>
```

```
    /// <param name="groupName">The name of the IAM group to remove the user from.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> RemoveUserFromGroupAsync(string userName, string
 groupName)
    {
        // Remove the user from the group.
        var removeUserRequest = new RemoveUserFromGroupRequest()
        {
            UserName = userName,
            GroupName = groupName,
        };

        var response = await
 _IAMService.RemoveUserFromGroupAsync(removeUserRequest);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM group.
    /// </summary>
    /// <param name="groupName">The name of the IAM group.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM policy.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutGroupPolicyAsync(string groupName, string policyName,
 string policyDocument)
    {
        var request = new PutGroupPolicyRequest
        {
            GroupName = groupName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutGroupPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Update the inline policy document embedded in a role.
```

```
    /// </summary>
    /// <param name="policyName">The name of the policy to embed.</param>
    /// <param name="roleName">The name of the role to update.</param>
    /// <param name="policyDocument">The policy document that defines the role.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutRolePolicyAsync(string policyName, string roleName,
 string policyDocument)
    {
        var request = new PutRolePolicyRequest
        {
            PolicyName = policyName,
            RoleName = roleName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutRolePolicyAsync(request);
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Add or update an inline policy document that is embedded in an IAM user.
    /// </summary>
    /// <param name="userName">The name of the IAM user.</param>
    /// <param name="policyName">The name of the IAM policy.</param>
    /// <param name="policyDocument">The policy document defining the IAM policy.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> PutUserPolicyAsync(string userName, string policyName,
 string policyDocument)
    {
        var request = new PutUserPolicyRequest
        {
            UserName = userName,
            PolicyName = policyName,
            PolicyDocument = policyDocument
        };

        var response = await _IAMService.PutUserPolicyAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
```

```
    /// Wait for a new access key to be ready to use.
    /// </summary>
    /// <param name="accessKeyId">The Id of the access key.</param>
    /// <returns>A boolean value indicating the success of the action.</returns>
    public async Task<bool> WaitUntilAccessKeyIsReady(string accessKeyId)
    {
        var keyReady = false;

        do
        {
            try
            {
                var response = await _IAMService.GetAccessKeyLastUsedAsync(
                    new GetAccessKeyLastUsedRequest { AccessKeyId = accessKeyId });
                if (response.UserName is not null)
                {
                    keyReady = true;
                }
            }
            catch (NoSuchEntityException)
            {
                keyReady = false;
            }
        } while (!keyReady);

        return keyReady;
    }
}



using Microsoft.Extensions.Configuration;

namespace IAMBasics;

public class IAMBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
```

```
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<IAMWrapper>()
            .AddTransient<UIWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<IAMBasics>();


        IConfiguration configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        // Values needed for user, role, and policies.
        string userName = configuration["UserName"]!;
        string s3PolicyName = configuration["S3PolicyName"]!;
        string roleName = configuration["RoleName"]!;


        var iamWrapper = host.Services.GetRequiredService<IAMWrapper>();
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        uiWrapper.DisplayBasicsOverview();
        uiWrapper.PressEnter();

        // First create a user. By default, the new user has
        // no permissions.
        uiWrapper.DisplayTitle("Create User");
        Console.WriteLine($"Creating a new user with user name: {userName}.");
        var user = await iamWrapper.CreateUserAsync(userName);
        var userArn = user.Arn;

        Console.WriteLine($"Successfully created user: {userName} with ARN:
{userArn}.");
        uiWrapper.WaitABit(15, "Now let's wait for the user to be ready for use.");
```

```
        // Define a role policy document that allows the new user
        // to assume the role.
        string assumeRolePolicyDocument = "{" +
          "\"Version\": \"2012-10-17\"," +
          "\"Statement\": [{" +
              "\"Effect\": \"Allow\"," +
              "\"Principal\": {" +
              $" \"AWS\": \"{userArn}\"" +
              "}," +
              "\"Action\": \"sts:AssumeRole\"" +
          "}]" +
        "}";

        // Permissions to list all buckets.
        string policyDocument = "{" +
            "\"Version\": \"2012-10-17\"," +
            " \"Statement\" : [{" +
                " \"Action\" : [\"s3:ListAllMyBuckets\"]," +
                " \"Effect\" : \"Allow\"," +
                " \"Resource\" : \"*\"" +
            "}]" +
        "}";

        // Create an AccessKey for the user.
        uiWrapper.DisplayTitle("Create access key");
        Console.WriteLine("Now let's create an access key for the new user.");
        var accessKey = await iamWrapper.CreateAccessKeyAsync(userName);

        var accessKeyId = accessKey.AccessKeyId;
        var secretAccessKey = accessKey.SecretAccessKey;

        Console.WriteLine($"We have created the access key with Access key id:
{accessKeyId}.");

        Console.WriteLine("Now let's wait until the IAM access key is ready to
use.");
        var keyReady = await iamWrapper.WaitUntilAccessKeyIsReady(accessKeyId);

        // Now try listing the Amazon Simple Storage Service (Amazon S3)
        // buckets. This should fail at this point because the user doesn't
        // have permissions to perform this task.
        uiWrapper.DisplayTitle("Try to display Amazon S3 buckets");
```

```
        Console.WriteLine("Now let's try to display a list of the user's Amazon S3
buckets.");
        var s3Client1 = new AmazonS3Client(accessKeyId, secretAccessKey);
        var stsClient1 = new AmazonSecurityTokenServiceClient(accessKeyId,
secretAccessKey);

        var s3Wrapper = new S3Wrapper(s3Client1, stsClient1);
        var buckets = await s3Wrapper.ListMyBucketsAsync();

        Console.WriteLine(buckets is null
            ? "As expected, the call to list the buckets has returned a null list."
            : "Something went wrong. This shouldn't have worked.");

        uiWrapper.PressEnter();

        uiWrapper.DisplayTitle("Create IAM role");
        Console.WriteLine($"Creating the role: {roleName}");

        // Creating an IAM role to allow listing the S3 buckets. A role name
        // is not case sensitive and must be unique to the account for which it
        // is created.
        var roleArn = await iamWrapper.CreateRoleAsync(roleName,
assumeRolePolicyDocument);

        uiWrapper.PressEnter();

        // Create a policy with permissions to list S3 buckets.
        uiWrapper.DisplayTitle("Create IAM policy");
        Console.WriteLine($"Creating the policy: {s3PolicyName}");
        Console.WriteLine("with permissions to list the Amazon S3 buckets for the
account.");
        var policy = await iamWrapper.CreatePolicyAsync(s3PolicyName,
policyDocument);

        // Wait 15 seconds for the IAM policy to be available.
        uiWrapper.WaitABit(15, "Waiting for the policy to be available.");

        // Attach the policy to the role you created earlier.
        uiWrapper.DisplayTitle("Attach new IAM policy");
        Console.WriteLine("Now let's attach the policy to the role.");
        await iamWrapper.AttachRolePolicyAsync(policy.Arn, roleName);

        // Wait 15 seconds for the role to be updated.
        Console.WriteLine();
```

```
        uiWrapper.WaitABit(15, "Waiting for the policy to be attached.");

        // Use the AWS Security Token Service (AWS STS) to have the user
        // assume the role we created.
        var stsClient2 = new AmazonSecurityTokenServiceClient(accessKeyId,
 secretAccessKey);

        // Wait for the new credentials to become valid.
        uiWrapper.WaitABit(10, "Waiting for the credentials to be valid.");

        var assumedRoleCredentials = await s3Wrapper.AssumeS3RoleAsync("temporary-
session", roleArn);

        // Try again to list the buckets using the client created with
        // the new user's credentials. This time, it should work.
        var s3Client2 = new AmazonS3Client(assumedRoleCredentials);

        s3Wrapper.UpdateClients(s3Client2, stsClient2);

        buckets = await s3Wrapper.ListMyBucketsAsync();

        uiWrapper.DisplayTitle("List Amazon S3 buckets");
        Console.WriteLine("This time we should have buckets to list.");
        if (buckets is not null)
        {
            buckets.ForEach(bucket =>
            {
                Console.WriteLine($"{bucket.BucketName} created:
 {bucket.CreationDate}");
            });
        }

        uiWrapper.PressEnter();

        // Now clean up all the resources used in the example.
        uiWrapper.DisplayTitle("Clean up resources");
        Console.WriteLine("Thank you for watching. The IAM Basics demo is
 complete.");
        Console.WriteLine("Please wait while we clean up the resources we
 created.");

        await iamWrapper.DetachRolePolicyAsync(policy.Arn, roleName);

        await iamWrapper.DeletePolicyAsync(policy.Arn);
```

```
        await iamWrapper.DeleteRoleAsync(roleName);

        await iamWrapper.DeleteAccessKeyAsync(accessKeyId, userName);

        await iamWrapper.DeleteUserAsync(userName);

        uiWrapper.PressEnter();

        Console.WriteLine("All done cleaning up our resources. Thank you for your
 patience.");
    }
}


namespace IamScenariosCommon;

using System.Net;

/// <summary>
/// A class to perform Amazon Simple Storage Service (Amazon S3) actions for
/// the IAM Basics scenario.
/// </summary>
public class S3Wrapper
{
    private IAmazonS3 _s3Service;
    private IAmazonSecurityTokenService _stsService;

    /// <summary>
    /// Constructor for the S3Wrapper class.
    /// </summary>
    /// <param name="s3Service">An Amazon S3 client object.</param>
    /// <param name="stsService">An AWS Security Token Service (AWS STS)
    /// client object.</param>
    public S3Wrapper(IAmazonS3 s3Service, IAmazonSecurityTokenService stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }

    /// <summary>
    /// Assumes an AWS Identity and Access Management (IAM) role that allows
    /// Amazon S3 access for the current session.
    /// </summary>
```

```
    /// <param name="roleSession">A string representing the current session.</param>
    /// <param name="roleToAssume">The name of the IAM role to assume.</param>
    /// <returns>Credentials for the newly assumed IAM role.</returns>
    public async Task<Credentials> AssumeS3RoleAsync(string roleSession, string
roleToAssume)
    {
        // Create the request to use with the AssumeRoleAsync call.
        var request = new AssumeRoleRequest()
        {
            RoleSessionName = roleSession,
            RoleArn = roleToAssume,
        };

        var response = await _stsService.AssumeRoleAsync(request);

        return response.Credentials;
    }


    /// <summary>
    /// Delete an S3 bucket.
    /// </summary>
    /// <param name="bucketName">Name of the S3 bucket to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteBucketAsync(string bucketName)
    {
        var result = await _s3Service.DeleteBucketAsync(new DeleteBucketRequest
{ BucketName = bucketName });
        return result.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// List the buckets that are owned by the user's account.
    /// </summary>
    /// <returns>Async Task.</returns>
    public async Task<List<S3Bucket>?> ListMyBucketsAsync()
    {
        try
        {
            // Get the list of buckets accessible by the new user.
            var response = await _s3Service.ListBucketsAsync();

            return response.Buckets;
        }
```

```
        catch (AmazonS3Exception ex)
        {
            // Something else went wrong. Display the error message.
            Console.WriteLine($"Error: {ex.Message}");
            return null;
        }
    }

    /// <summary>
    /// Create a new S3 bucket.
    /// </summary>
    /// <param name="bucketName">The name for the new bucket.</param>
    /// <returns>A Boolean value indicating whether the action completed
    /// successfully.</returns>
    public async Task<bool> PutBucketAsync(string bucketName)
    {
        var response = await _s3Service.PutBucketAsync(new PutBucketRequest
 { BucketName = bucketName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Update the client objects with new client objects. This is available
    /// because the scenario uses the methods of this class without and then
    /// with the proper permissions to list S3 buckets.
    /// </summary>
    /// <param name="s3Service">The Amazon S3 client object.</param>
    /// <param name="stsService">The AWS STS client object.</param>
    public void UpdateClients(IAmazonS3 s3Service, IAmazonSecurityTokenService
 stsService)
    {
        _s3Service = s3Service;
        _stsService = stsService;
    }
}


namespace IamScenariosCommon;

public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
```

```
    /// Show information about the IAM Groups scenario.
    /// </summary>
    public void DisplayGroupsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to the IAM Groups Demo");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates an Amazon Identity and Access Management
(IAM) group.");
        Console.WriteLine("\t2. Adds an IAM policy to the IAM group giving it full
access to Amazon S3.");
        Console.WriteLine("\t3. Creates a new IAM user.");
        Console.WriteLine("\t4. Creates an IAM access key for the user.");
        Console.WriteLine("\t5. Adds the user to the IAM group.");
        Console.WriteLine("\t6. Lists the buckets on the account.");
        Console.WriteLine("\t7. Proves that the user has full Amazon S3 access by
creating a bucket.");
        Console.WriteLine("\t8. List the buckets again to show the new bucket.");
        Console.WriteLine("\t9. Cleans up all the resources created.");
    }

    /// <summary>
    /// Show information about the IAM Basics scenario.
    /// </summary>
    public void DisplayBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to IAM Basics");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates a user with no permissions.");
        Console.WriteLine("\t2. Creates a role and policy that grant
s3:ListAllMyBuckets permission.");
        Console.WriteLine("\t3. Grants the user permission to assume the role.");
        Console.WriteLine("\t4. Creates an S3 client object as the user and tries to
list buckets (this will fail).");
        Console.WriteLine("\t5. Gets temporary credentials by assuming the role.");
        Console.WriteLine("\t6. Creates a new S3 client object with the temporary
credentials and lists the buckets (this will succeed).");
        Console.WriteLine("\t7. Deletes all the resources.");
    }

    /// <summary>
```

```
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);

        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
```

```
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos do Amazon Keyspaces usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Keyspaces.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Keyspaces

Os exemplos de código a seguir mostram como começar a usar o Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace KeyspacesActions;

public class HelloKeyspaces
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon Keyspaces (for Apache Cassandra).
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonKeyspaces>()
                .AddTransient<KeyspacesWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<HelloKeyspaces>();

        var keyspacesClient = host.Services.GetRequiredService<IAmazonKeyspaces>();
```

```
        var keyspacesWrapper = new KeyspacesWrapper(keyspacesClient);

        Console.WriteLine("Hello, Amazon Keyspaces! Let's list your keyspaces:");
        await keyspacesWrapper.ListKeyspaces();
    }
}
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar um espaço de chaves

O exemplo de código a seguir mostra como criar um espaço de chave do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name for the new keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new keyspace.</returns>
    public async Task<string> CreateKeyspace(string keyspaceName)
    {
        var response =
            await _amazonKeyspaces.CreateKeyspaceAsync(
                new CreateKeyspaceRequest { KeyspaceName = keyspaceName });
```

```
        return response.ResourceArn;
    }
```

- Para obter detalhes da API, consulte CreateKeyspacea Referência AWS SDK for .NET da API.

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace where the table will be created.</
param>
    /// <param name="schema">The schema for the new table.</param>
    /// <param name="tableName">The name of the new table.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new table.</returns>
    public async Task<string> CreateTable(string keyspaceName, SchemaDefinition
 schema, string tableName)
    {
        var request = new CreateTableRequest
        {
            KeyspaceName = keyspaceName,
            SchemaDefinition = schema,
            TableName = tableName,
            PointInTimeRecovery = new PointInTimeRecovery { Status =
 PointInTimeRecoveryStatus.ENABLED }
        };

        var response = await _amazonKeyspaces.CreateTableAsync(request);
        return response.ResourceArn;
```

```
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for .NET da API.

Excluir um keyspace

O exemplo de código a seguir mostra como excluir um espaço de chaves do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an existing keyspace.
    /// </summary>
    /// <param name="keyspaceName"></param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.DeleteKeyspaceAsync(
            new DeleteKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteKeyspacea Referência AWS SDK for .NET da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTable(string keyspaceName, string tableName)
    {
        var response = await _amazonKeyspaces.DeleteTableAsync(
            new DeleteTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for .NET da API.

Obter dados sobre um keyspace

O exemplo de código a seguir mostra como obter dados sobre um keyspace do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
```

```
    /// Get data about a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the keyspace.</returns>
    public async Task<string> GetKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.GetKeyspaceAsync(
            new GetKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.ResourceArn;
    }
```

- Para obter detalhes da API, consulte GetKeyspacea Referência AWS SDK for .NET da API.

Obter dados sobre uma tabela

O exemplo de código a seguir mostra como obter dados sobre uma tabela do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information about an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the Amazon Keyspaces table.</param>
    /// <returns>The response containing data about the table.</returns>
    public async Task<GetTableResponse> GetTable(string keyspaceName, string
tableName)
    {
        var response = await _amazonKeyspaces.GetTableAsync(
            new GetTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response;
    }
```

- Para obter detalhes da API, consulte GetTablea Referência AWS SDK for .NET da API.

Listar espaços de chaves

O exemplo de código a seguir mostra como listar espaços de chaves do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Lists all keyspaces for the account.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task ListKeyspaces()
    {
        var paginator = _amazonKeyspaces.Paginators.ListKeyspaces(new
ListKeyspacesRequest());

        Console.WriteLine("{0, -30}\t{1}", "Keyspace name", "Keyspace ARN");
        Console.WriteLine(new string('-', Console.WindowWidth));
        await foreach (var keyspace in paginator.Keyspaces)
        {

Console.WriteLine($"{keyspace.KeyspaceName,-30}\t{keyspace.ResourceArn}");
        }
    }
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for .NET da API.

Listar tabelas em um keyspace

O exemplo de código a seguir mostra como listar tabelas do Amazon Keyspaces em um espaço de chave.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Lists the Amazon Keyspaces tables in a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>A list of TableSummary objects.</returns>
    public async Task<List<TableSummary>> ListTables(string keyspaceName)
    {
        var response = await _amazonKeyspaces.ListTablesAsync(new ListTablesRequest
{ KeyspaceName = keyspaceName });
        response.Tables.ForEach(table =>
        {

Console.WriteLine($"{table.KeyspaceName}\t{table.TableName}\t{table.ResourceArn}");
        });

        return response.Tables;
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for .NET da API.

Restaurar uma tabela para um ponto no tempo

O exemplo de código a seguir mostra como restaurar uma tabela do Amazon Keyspaces em um determinado momento.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Restores the specified table to the specified point in time.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to restore.</param>
    /// <param name="timestamp">The time to which the table will be restored.</
param>
    /// <returns>The Amazon Resource Name (ARN) of the restored table.</returns>
    public async Task<string> RestoreTable(string keyspaceName, string tableName,
 string restoredTableName, DateTime timestamp)
    {
        var request = new RestoreTableRequest
        {
            RestoreTimestamp = timestamp,
            SourceKeyspaceName = keyspaceName,
            SourceTableName = tableName,
            TargetKeyspaceName = keyspaceName,
            TargetTableName = restoredTableName
        };

        var response = await _amazonKeyspaces.RestoreTableAsync(request);
        return response.RestoredTableARN;
    }
```

- Para obter detalhes da API, consulte RestoreTablea Referência AWS SDK for .NET da API.

Atualizar uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do Amazon Keyspaces.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Updates the movie table to add a boolean column named watched.
/// </summary>
/// <param name="keyspaceName">The keyspace containing the table.</param>
/// <param name="tableName">The name of the table to change.</param>
/// <returns>The Amazon Resource Name (ARN) of the updated table.</returns>
public async Task<string> UpdateTable(string keyspaceName, string tableName)
{
    var newColumn = new ColumnDefinition { Name = "watched", Type = "boolean" };
    var request = new UpdateTableRequest
    {
        KeyspaceName = keyspaceName,
        TableName = tableName,
        AddColumns = new List<ColumnDefinition> { newColumn }
    };
    var response = await _amazonKeyspaces.UpdateTableAsync(request);
    return response.ResourceArn;
}
```

- Para obter detalhes da API, consulte UpdateTablea Referência AWS SDK for .NET da API.

Cenários

Começar a usar espaços de chaves e tabelas

O código de exemplo a seguir mostra como:

- Criar um keyspace e uma tabela. O esquema da tabela contém dados do filme e tem a point-in-time recuperação ativada.
- Conectar-se ao espaço de chaves usando uma conexão TLS segura com autenticação SigV4.
- Consulte a tabela. Adicionar recuperar e atualizar dados do filme.

- Atualizar tabela. Adicionar uma coluna para rastrear os filmes assistidos.
- Restaurar a tabela ao estado anterior e limpar os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
global using System.Security.Cryptography.X509Certificates;
global using Amazon.Keyspaces;
global using Amazon.Keyspaces.Model;
global using KeyspacesActions;
global using KeyspacesScenario;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;
global using Newtonsoft.Json;


namespace KeyspacesBasics;

/// <summary>
/// Amazon Keyspaces (for Apache Cassandra) scenario. Shows some of the basic
/// actions performed with Amazon Keyspaces.
/// </summary>
public class KeyspacesBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
```

```
                    .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonKeyspaces>()
            .AddTransient<KeyspacesWrapper>()
            .AddTransient<CassandraWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<KeyspacesBasics>();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var keyspacesWrapper = host.Services.GetRequiredService<KeyspacesWrapper>();
        var uiMethods = new UiMethods();

        var keyspaceName = configuration["KeyspaceName"];
        var tableName = configuration["TableName"];

        bool success; // Used to track the results of some operations.

        uiMethods.DisplayOverview();
        uiMethods.PressEnter();

        // Create the keyspace.
        var keyspaceArn = await keyspacesWrapper.CreateKeyspace(keyspaceName);

        // Wait for the keyspace to be available. GetKeyspace results in a
        // resource not found error until it is ready for use.
        try
        {
            var getKeyspaceArn = "";
            Console.Write($"Created {keyspaceName}. Waiting for it to become
available. ");
            do
            {
                getKeyspaceArn = await keyspacesWrapper.GetKeyspace(keyspaceName);
```

```
                Console.Write(". ");
            } while (getKeyspaceArn != keyspaceArn);
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine("Waiting for keyspace to be created.");
        }

        Console.WriteLine($"\nThe keyspace {keyspaceName} is ready for use.");

        uiMethods.PressEnter();

        // Create the table.
        // First define the schema.
        var allColumns = new List<ColumnDefinition>
        {
            new ColumnDefinition { Name = "title", Type = "text" },
            new ColumnDefinition { Name = "year", Type = "int" },
            new ColumnDefinition { Name = "release_date", Type = "timestamp" },
            new ColumnDefinition { Name = "plot", Type = "text" },
        };

        var partitionKeys = new List<PartitionKey>
        {
            new PartitionKey { Name = "year", },
            new PartitionKey { Name = "title" },
        };

        var tableSchema = new SchemaDefinition
        {
            AllColumns = allColumns,
            PartitionKeys = partitionKeys,
        };

        var tableArn = await keyspacesWrapper.CreateTable(keyspaceName, tableSchema,
tableName);

        // Wait for the table to be active.
        try
        {
            var resp = new GetTableResponse();
            Console.Write("Waiting for the new table to be active. ");
            do
            {
```

```
                try
                {
                    resp = await keyspacesWrapper.GetTable(keyspaceName, tableName);
                    Console.Write(".");
                }
                catch (ResourceNotFoundException)
                {
                    Console.Write(".");
                }
            } while (resp.Status != TableStatus.ACTIVE);

            // Display the table's schema.
            Console.WriteLine($"\nTable {tableName} has been created in
{keyspaceName}");
            Console.WriteLine("Let's take a look at the schema.");
            uiMethods.DisplayTitle("All columns");
            resp.SchemaDefinition.AllColumns.ForEach(column =>
            {
                Console.WriteLine($"{column.Name,-40}\t{column.Type,-20}");
            });

            uiMethods.DisplayTitle("Cluster keys");
            resp.SchemaDefinition.ClusteringKeys.ForEach(clusterKey =>
            {

Console.WriteLine($"{clusterKey.Name,-40}\t{clusterKey.OrderBy,-20}");
            });

            uiMethods.DisplayTitle("Partition keys");
            resp.SchemaDefinition.PartitionKeys.ForEach(partitionKey =>
            {
                Console.WriteLine($"{partitionKey.Name}");
            });

            uiMethods.PressEnter();
        }
        catch (ResourceNotFoundException ex)
        {
            Console.WriteLine($"Error: {ex.Message}");
        }

        // Access Apache Cassandra using the Cassandra drive for C#.
        var cassandraWrapper = host.Services.GetRequiredService<CassandraWrapper>();
        var movieFilePath = configuration["MovieFile"];
```

```
        Console.WriteLine("Let's add some movies to the table we created.");
        var inserted = await cassandraWrapper.InsertIntoMovieTable(keyspaceName,
tableName, movieFilePath);

        uiMethods.PressEnter();

        Console.WriteLine("Added the following movies to the table:");
        var rows = await cassandraWrapper.GetMovies(keyspaceName, tableName);
        uiMethods.DisplayTitle("All Movies");

        foreach (var row in rows)
        {
            var title = row.GetValue<string>("title");
            var year = row.GetValue<int>("year");
            var plot = row.GetValue<string>("plot");
            var release_date = row.GetValue<DateTime>("release_date");
            Console.WriteLine($"{release_date}\t{title}\t{year}\n{plot}");
            Console.WriteLine(uiMethods.SepBar);
        }

        // Update the table schema
        uiMethods.DisplayTitle("Update table schema");
        Console.WriteLine("Now we will update the table to add a boolean field
called watched.");

        // First save the current time as a UTC Date so the original
        // table can be restored later.
        var timeChanged = DateTime.UtcNow;

        // Now update the schema.
        var resourceArn = await keyspacesWrapper.UpdateTable(keyspaceName,
tableName);
        uiMethods.PressEnter();

        Console.WriteLine("Now let's mark some of the movies as watched.");

        // Pick some files to mark as watched.
        var movieToWatch = rows[2].GetValue<string>("title");
        var watchedMovieYear = rows[2].GetValue<int>("year");
        var changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[6].GetValue<string>("title");
```

```
        watchedMovieYear = rows[6].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[9].GetValue<string>("title");
        watchedMovieYear = rows[9].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[10].GetValue<string>("title");
        watchedMovieYear = rows[10].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        movieToWatch = rows[13].GetValue<string>("title");
        watchedMovieYear = rows[13].GetValue<int>("year");
        changedRows = await cassandraWrapper.MarkMovieAsWatched(keyspaceName,
tableName, movieToWatch, watchedMovieYear);

        uiMethods.DisplayTitle("Watched movies");
        Console.WriteLine("These movies have been marked as watched:");
        rows = await cassandraWrapper.GetWatchedMovies(keyspaceName, tableName);
        foreach (var row in rows)
        {
            var title = row.GetValue<string>("title");
            var year = row.GetValue<int>("year");
            Console.WriteLine($"{title,-40}\t{year,8}");
        }
        uiMethods.PressEnter();

        Console.WriteLine("We can restore the table to its previous state but that
can take up to 20 minutes to complete.");
        string answer;
        do
        {
            Console.WriteLine("Do you want to restore the table? (y/n)");
            answer = Console.ReadLine();
        } while (answer.ToLower() != "y" && answer.ToLower() != "n");

        if (answer == "y")
        {
            var restoredTableName = $"{tableName}_restored";
            var restoredTableArn = await keyspacesWrapper.RestoreTable(
                keyspaceName,
```

```
                tableName,
                restoredTableName,
                timeChanged);
            // Loop and call GetTable until the table is gone. Once it has been
            // deleted completely, GetTable will raise a ResourceNotFoundException.
            bool wasRestored = false;

            try
            {
                do
                {
                    var resp = await keyspacesWrapper.GetTable(keyspaceName,
restoredTableName);
                    wasRestored = (resp.Status == TableStatus.ACTIVE);
                } while (!wasRestored);
            }
            catch (ResourceNotFoundException)
            {
                // If the restored table raised an error, it isn't
                // ready yet.
                Console.Write(".");
            }
        }

        uiMethods.DisplayTitle("Clean up resources.");

        // Delete the table.
        success = await keyspacesWrapper.DeleteTable(keyspaceName, tableName);

        Console.WriteLine($"Table {tableName} successfully deleted from
{keyspaceName}.");
        Console.WriteLine("Waiting for the table to be removed completely. ");

        // Loop and call GetTable until the table is gone. Once it has been
        // deleted completely, GetTable will raise a ResourceNotFoundException.
        bool wasDeleted = false;

        try
        {
            do
            {
                var resp = await keyspacesWrapper.GetTable(keyspaceName, tableName);
            } while (!wasDeleted);
        }
```

```
        catch (ResourceNotFoundException ex)
        {
            wasDeleted = true;
            Console.WriteLine($"{ex.Message} indicates that the table has been
 deleted.");
        }

        // Delete the keyspace.
        success = await keyspacesWrapper.DeleteKeyspace(keyspaceName);
        Console.WriteLine("The keyspace has been deleted and the demo is now
 complete.");
    }
}
```

```
namespace KeyspacesActions;

/// <summary>
/// Performs Amazon Keyspaces (for Apache Cassandra) actions.
/// </summary>
public class KeyspacesWrapper
{
    private readonly IAmazonKeyspaces _amazonKeyspaces;

    /// <summary>
    /// Constructor for the KeyspaceWrapper.
    /// </summary>
    /// <param name="amazonKeyspaces">An Amazon Keyspaces client object.</param>
    public KeyspacesWrapper(IAmazonKeyspaces amazonKeyspaces)
    {
        _amazonKeyspaces = amazonKeyspaces;
    }

    /// <summary>
    /// Create a new keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name for the new keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new keyspace.</returns>
    public async Task<string> CreateKeyspace(string keyspaceName)
    {
        var response =
            await _amazonKeyspaces.CreateKeyspaceAsync(
```

```
                new CreateKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.ResourceArn;
    }


    /// <summary>
    /// Create a new Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace where the table will be created.</
param>
    /// <param name="schema">The schema for the new table.</param>
    /// <param name="tableName">The name of the new table.</param>
    /// <returns>The Amazon Resource Name (ARN) of the new table.</returns>
    public async Task<string> CreateTable(string keyspaceName, SchemaDefinition
 schema, string tableName)
    {
        var request = new CreateTableRequest
        {
            KeyspaceName = keyspaceName,
            SchemaDefinition = schema,
            TableName = tableName,
            PointInTimeRecovery = new PointInTimeRecovery { Status =
 PointInTimeRecoveryStatus.ENABLED }
        };

        var response = await _amazonKeyspaces.CreateTableAsync(request);
        return response.ResourceArn;
    }


    /// <summary>
    /// Delete an existing keyspace.
    /// </summary>
    /// <param name="keyspaceName"></param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.DeleteKeyspaceAsync(
            new DeleteKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
```

```
    /// Delete an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to delete.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteTable(string keyspaceName, string tableName)
    {
        var response = await _amazonKeyspaces.DeleteTableAsync(
            new DeleteTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }


    /// <summary>
    /// Get data about a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>The Amazon Resource Name (ARN) of the keyspace.</returns>
    public async Task<string> GetKeyspace(string keyspaceName)
    {
        var response = await _amazonKeyspaces.GetKeyspaceAsync(
            new GetKeyspaceRequest { KeyspaceName = keyspaceName });
        return response.ResourceArn;
    }


    /// <summary>
    /// Get information about an Amazon Keyspaces table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the Amazon Keyspaces table.</param>
    /// <returns>The response containing data about the table.</returns>
    public async Task<GetTableResponse> GetTable(string keyspaceName, string
tableName)
    {
        var response = await _amazonKeyspaces.GetTableAsync(
            new GetTableRequest { KeyspaceName = keyspaceName, TableName =
tableName });
        return response;
    }


    /// <summary>
```

```
    /// Lists all keyspaces for the account.
    /// </summary>
    /// <returns>Async task.</returns>
    public async Task ListKeyspaces()
    {
        var paginator = _amazonKeyspaces.Paginators.ListKeyspaces(new
 ListKeyspacesRequest());

        Console.WriteLine("{0, -30}\t{1}", "Keyspace name", "Keyspace ARN");
        Console.WriteLine(new string('-', Console.WindowWidth));
        await foreach (var keyspace in paginator.Keyspaces)
        {

 Console.WriteLine($"{keyspace.KeyspaceName,-30}\t{keyspace.ResourceArn}");
        }
    }


    /// <summary>
    /// Lists the Amazon Keyspaces tables in a keyspace.
    /// </summary>
    /// <param name="keyspaceName">The name of the keyspace.</param>
    /// <returns>A list of TableSummary objects.</returns>
    public async Task<List<TableSummary>> ListTables(string keyspaceName)
    {
        var response = await _amazonKeyspaces.ListTablesAsync(new ListTablesRequest
 { KeyspaceName = keyspaceName });
        response.Tables.ForEach(table =>
        {

 Console.WriteLine($"{table.KeyspaceName}\t{table.TableName}\t{table.ResourceArn}");
        });

        return response.Tables;
    }


    /// <summary>
    /// Restores the specified table to the specified point in time.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to restore.</param>
    /// <param name="timestamp">The time to which the table will be restored.</
param>
```

```
    /// <returns>The Amazon Resource Name (ARN) of the restored table.</returns>
    public async Task<string> RestoreTable(string keyspaceName, string tableName,
 string restoredTableName, DateTime timestamp)
    {
        var request = new RestoreTableRequest
        {
            RestoreTimestamp = timestamp,
            SourceKeyspaceName = keyspaceName,
            SourceTableName = tableName,
            TargetKeyspaceName = keyspaceName,
            TargetTableName = restoredTableName
        };

        var response = await _amazonKeyspaces.RestoreTableAsync(request);
        return response.RestoredTableARN;
    }


    /// <summary>
    /// Updates the movie table to add a boolean column named watched.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table to change.</param>
    /// <returns>The Amazon Resource Name (ARN) of the updated table.</returns>
    public async Task<string> UpdateTable(string keyspaceName, string tableName)
    {
        var newColumn = new ColumnDefinition { Name = "watched", Type = "boolean" };
        var request = new UpdateTableRequest
        {
            KeyspaceName = keyspaceName,
            TableName = tableName,
            AddColumns = new List<ColumnDefinition> { newColumn }
        };
        var response = await _amazonKeyspaces.UpdateTableAsync(request);
        return response.ResourceArn;
    }

}
```

```
using System.Net;
using Cassandra;
```

```
namespace KeyspacesScenario;

/// <summary>
/// Class to perform CRUD methods on an Amazon Keyspaces (for Apache Cassandra)
 database.
///
/// NOTE: This sample uses a plain text authenticator for example purposes only.
/// Recommended best practice is to use a SigV4 authentication plugin, if available.
/// </summary>
public class CassandraWrapper
{
    private readonly IConfiguration _configuration;
    private readonly string _localPathToFile;
    private const string _certLocation = "https://certs.secureserver.net/repository/
sf-class2-root.crt";
    private const string _certFileName = "sf-class2-root.crt";
    private readonly X509Certificate2Collection _certCollection;
    private X509Certificate2 _amazoncert;
    private Cluster _cluster;

    // User name and password for the service.
    private string _userName = null!;
    private string _pwd = null!;

    public CassandraWrapper()
    {
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        _localPathToFile = Path.GetTempPath();

        // Get the Starfield digital certificate and save it locally.
        var client = new WebClient();
        client.DownloadFile(_certLocation, $"{_localPathToFile}/{_certFileName}");

        //var httpClient = new HttpClient();
        //var httpResult = httpClient.Get(fileUrl);
        //using var resultStream = await httpResult.Content.ReadAsStreamAsync();
        //using var fileStream = File.Create(pathToSave);
```

```
        //resultStream.CopyTo(fileStream);

        _certCollection = new X509Certificate2Collection();
        _amazoncert = new X509Certificate2($"{_localPathToFile}/{_certFileName}");

        // Get the user name and password stored in the configuration file.
        _userName = _configuration["UserName"]!;
        _pwd = _configuration["Password"]!;

        // For a list of Service Endpoints for Amazon Keyspaces, see:
        // https://docs.aws.amazon.com/keyspaces/latest/devguide/
programmatic.endpoints.html
        var awsEndpoint = _configuration["ServiceEndpoint"];

        _cluster = Cluster.Builder()
            .AddContactPoints(awsEndpoint)
            .WithPort(9142)
            .WithAuthProvider(new PlainTextAuthProvider(_userName, _pwd))
            .WithSSL(new SSLOptions().SetCertificateCollection(_certCollection))
            .WithQueryOptions(
                new QueryOptions()
                    .SetConsistencyLevel(ConsistencyLevel.LocalQuorum)
                    .SetSerialConsistencyLevel(ConsistencyLevel.LocalSerial))
            .Build();
    }

    /// <summary>
    /// Loads the contents of a JSON file into a list of movies to be
    /// added to the Apache Cassandra table.
    /// </summary>
    /// <param name="movieFileName">The full path to the JSON file.</param>
    /// <returns>A list of movie objects.</returns>
    public List<Movie> ImportMoviesFromJson(string movieFileName, int numToImport =
 0)
    {
        if (!File.Exists(movieFileName))
        {
            return null!;
        }

        using var sr = new StreamReader(movieFileName);
        string json = sr.ReadToEnd();

        var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);
```

```
        // If numToImport = 0, return all movies in the collection.
        if (numToImport == 0)
        {
            // Now return the entire list of movies.
            return allMovies;
        }
        else
        {
            // Now return the first numToImport entries.
            return allMovies.GetRange(0, numToImport);
        }
    }

    /// <summary>
    /// Insert movies into the movie table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="movieTableName">The Amazon Keyspaces table.</param>
    /// <param name="movieFilePath">The path to the resource file containing
    /// movie data to insert into the table.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> InsertIntoMovieTable(string keyspaceName, string
 movieTableName, string movieFilePath, int numToImport = 20)
    {
        // Get some movie data from the movies.json file
        var movies = ImportMoviesFromJson(movieFilePath, numToImport);

        var session = _cluster.Connect(keyspaceName);

        string insertCql;

        RowSet rs;

        // Now we insert the numToImport movies into the table.
        foreach (var movie in movies)
        {
            // Escape single quote characters in the plot.
            insertCql = $"INSERT INTO {keyspaceName}.{movieTableName}
 (title, year, release_date, plot) values($${movie.Title}$$, {movie.Year},
 '{movie.Info.Release_Date.ToString("yyyy-MM-dd")}', $${movie.Info.Plot}$$)";
            rs = await session.ExecuteAsync(new SimpleStatement(insertCql));
        }
```

```
        return true;
    }

    /// <summary>
    /// Gets all of the movies in the movies table.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <returns>A list of row objects containing movie data.</returns>
    public async Task<List<Row>> GetMovies(string keyspaceName, string tableName)
    {
        var session = _cluster.Connect();
        RowSet rs;
        try
        {
            rs = await session.ExecuteAsync(new SimpleStatement($"SELECT * FROM
{keyspaceName}.{tableName}"));

            // Extract the row data from the returned RowSet.
            var rows = rs.GetRows().ToList();
            return rows;
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            return null!;
        }
    }

    /// <summary>
    /// Mark a movie in the movie table as watched.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <param name="title">The title of the movie to mark as watched.</param>
    /// <param name="year">The year the movie was released.</param>
    /// <returns>A set of rows containing the changed data.</returns>
    public async Task<List<Row>> MarkMovieAsWatched(string keyspaceName, string
tableName, string title, int year)
    {
        var session = _cluster.Connect();
        string updateCql = $"UPDATE {keyspaceName}.{tableName} SET watched=true
WHERE title = $${title}$$ AND year = {year};";
        var rs = await session.ExecuteAsync(new SimpleStatement(updateCql));
```

```
        var rows = rs.GetRows().ToList();
        return rows;
    }

    /// <summary>
    /// Retrieve the movies in the movies table where watched is true.
    /// </summary>
    /// <param name="keyspaceName">The keyspace containing the table.</param>
    /// <param name="tableName">The name of the table.</param>
    /// <returns>A list of row objects containing information about movies
    /// where watched is true.</returns>
    public async Task<List<Row>> GetWatchedMovies(string keyspaceName, string
 tableName)
    {
        var session = _cluster.Connect();
        RowSet rs;
        try
        {
            rs = await session.ExecuteAsync(new SimpleStatement($"SELECT title,
 year, plot FROM {keyspaceName}.{tableName} WHERE watched = true ALLOW FILTERING"));

            // Extract the row data from the returned RowSet.
            var rows = rs.GetRows().ToList();
            return rows;
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            return null!;
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable

- GetKeyspace
- GetTable
- ListKeyspaces
- ListTables
- RestoreTable
- UpdateTable

Exemplos de Kinesis usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Adicionar tags

O exemplo de código a seguir mostra como adicionar tags a um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// This example shows how to apply key/value pairs to an Amazon Kinesis
/// stream.
/// </summary>
public class TagStream
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();

        string streamName = "AmazonKinesisStream";
        var tags = new Dictionary<string, string>
        {
            { "Project", "Sample Kinesis Project" },
            { "Application", "Sample Kinesis App" },
        };

        var success = await ApplyTagsToStreamAsync(client, streamName, tags);

        if (success)
        {
            Console.WriteLine($"Taggs successfully added to {streamName}.");
        }
        else
        {
            Console.WriteLine("Tags were not added to the stream.");
        }
    }
```

```
        /// <summary>
        /// Applies the set of tags to the named Kinesis stream.
        /// </summary>
        /// <param name="client">The initialized Kinesis client.</param>
        /// <param name="streamName">The name of the Kinesis stream to which
        /// the tags will be attached.</param>
        /// <param name="tags">A sictionary containing key/value pairs which
        /// will be used to create the Kinesis tags.</param>
        /// <returns>A Boolean value which represents the success or failure
        /// of AddTagsToStreamAsync.</returns>
        public static async Task<bool> ApplyTagsToStreamAsync(
            IAmazonKinesis client,
            string streamName,
            Dictionary<string, string> tags)
        {
            var request = new AddTagsToStreamRequest
            {
                StreamName = streamName,
                Tags = tags,
            };

            var response = await client.AddTagsToStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte AddTagsToStreama Referência AWS SDK for .NET da API.

Criar um stream

O exemplo de código a seguir mostra como criar um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// This example shows how to create a new Amazon Kinesis stream.
/// </summary>
public class CreateStream
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();

        string streamName = "AmazonKinesisStream";
        int shardCount = 1;

        var success = await CreateNewStreamAsync(client, streamName,
shardCount);
        if (success)
        {
            Console.WriteLine($"The stream, {streamName} successfully
created.");
        }
    }

    /// <summary>
    /// Creates a new Kinesis stream.
    /// </summary>
    /// <param name="client">An initialized Kinesis client.</param>
    /// <param name="streamName">The name for the new stream.</param>
    /// <param name="shardCount">The number of shards the new stream will
    /// use. The throughput of the stream is a function of the number of
    /// shards; more shards are required for greater provisioned
```

```
        /// throughput.</param>
        /// <returns>A Boolean value indicating whether the stream was created.</
returns>
        public static async Task<bool> CreateNewStreamAsync(IAmazonKinesis client,
 string streamName, int shardCount)
        {
            var request = new CreateStreamRequest
            {
                StreamName = streamName,
                ShardCount = shardCount,
            };

            var response = await client.CreateStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte CreateStreama Referência AWS SDK for .NET da API.

Excluir um stream

O exemplo de código a seguir mostra como excluir um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// Shows how to delete an Amazon Kinesis stream.
    /// </summary>
```

```
    public class DeleteStream
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();
            string streamName = "AmazonKinesisStream";

            var success = await DeleteStreamAsync(client, streamName);

            if (success)
            {
                Console.WriteLine($"Stream, {streamName} successfully deleted.");
            }
            else
            {
                Console.WriteLine("Stream not deleted.");
            }
        }

        /// <summary>
        /// Deletes a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamName">The name of the string to delete.</param>
        /// <returns>A Boolean value representing the success of the operation.</
returns>
        public static async Task<bool> DeleteStreamAsync(IAmazonKinesis client,
 string streamName)
        {
            // If EnforceConsumerDeletion is true, any consumers
            // of this stream will also be deleted. If it is set
            // to false and this stream has any consumers, the
            // call will fail with a ResourceInUseException.
            var request = new DeleteStreamRequest
            {
                StreamName = streamName,
                EnforceConsumerDeletion = true,
            };

            var response = await client.DeleteStreamAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeleteStreama Referência AWS SDK for .NET da API.

Cancelar um consumidor

O exemplo de código a seguir mostra como cancelar o registro de um consumidor de um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// Shows how to deregister a consumer from an Amazon Kinesis stream.
    /// </summary>
    public class DeregisterConsumer
    {
        public static async Task Main(string[] args)
        {
            IAmazonKinesis client = new AmazonKinesisClient();

            string streamARN = "arn:aws:kinesis:us-west-2:000000000000:stream/
AmazonKinesisStream";
            string consumerName = "CONSUMER_NAME";
            string consumerARN = "arn:aws:kinesis:us-west-2:000000000000:stream/
AmazonKinesisStream/consumer/CONSUMER_NAME:000000000000";

            var success = await DeregisterConsumerAsync(client, streamARN,
 consumerARN, consumerName);
```

```
            if (success)
            {
                Console.WriteLine($"{consumerName} successfully deregistered.");
            }
            else
            {
                Console.WriteLine($"{consumerName} was not successfully
 deregistered.");
            }
        }

        /// <summary>
        /// Deregisters a consumer from a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamARN">The ARN of a Kinesis stream.</param>
        /// <param name="consumerARN">The ARN of the consumer.</param>
        /// <param name="consumerName">The name of the consumer.</param>
        /// <returns>A Boolean value representing the success of the operation.</
returns>
        public static async Task<bool> DeregisterConsumerAsync(
            IAmazonKinesis client,
            string streamARN,
            string consumerARN,
            string consumerName)
        {
            var request = new DeregisterStreamConsumerRequest
            {
                StreamARN = streamARN,
                ConsumerARN = consumerARN,
                ConsumerName = consumerName,
            };

            var response = await client.DeregisterStreamConsumerAsync(request);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeregisterStreamConsumera Referência AWS SDK for .NET da API.

Listar streams

O exemplo de código a seguir mostra como listar informações em um ou mais streams do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// Retrieves and displays a list of existing Amazon Kinesis streams.
/// </summary>
public class ListStreams
{
    public static async Task Main(string[] args)
    {
        IAmazonKinesis client = new AmazonKinesisClient();
        var response = await client.ListStreamsAsync(new ListStreamsRequest());

        List<string> streamNames = response.StreamNames;

        if (streamNames.Count > 0)
        {
            streamNames
                .ForEach(s => Console.WriteLine($"Stream name: {s}"));
        }
        else
        {
            Console.WriteLine("No streams were found.");
        }
    }
}
```

- Para obter detalhes da API, consulte ListStreamsa Referência AWS SDK for .NET da API.

Listar tags

O exemplo de código a seguir mostra como listar as tags associadas a um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Kinesis;
using Amazon.Kinesis.Model;

/// <summary>
/// Shows how to list the tags that have been attached to an Amazon Kinesis
/// stream.
/// </summary>
public class ListTags
{
    public static async Task Main()
    {
        IAmazonKinesis client = new AmazonKinesisClient();
        string streamName = "AmazonKinesisStream";

        await ListTagsAsync(client, streamName);
    }

    /// <summary>
    /// List the tags attached to a Kinesis stream.
    /// </summary>
    /// <param name="client">An initialized Kinesis client object.</param>
    /// <param name="streamName">The name of the Kinesis stream for which you
```

```
        /// wish to display tags.</param>
        public static async Task ListTagsAsync(IAmazonKinesis client, string
streamName)
        {
            var request = new ListTagsForStreamRequest
            {
                StreamName = streamName,
                Limit = 10,
            };

            var response = await client.ListTagsForStreamAsync(request);
            DisplayTags(response.Tags);

            while (response.HasMoreTags)
            {
                request.ExclusiveStartTagKey = response.Tags[response.Tags.Count -
1].Key;
                response = await client.ListTagsForStreamAsync(request);
            }
        }

        /// <summary>
        /// Displays the items in a list of Kinesis tags.
        /// </summary>
        /// <param name="tags">A list of the Tag objects to be displayed.</param>
        public static void DisplayTags(List<Tag> tags)
        {
            tags
                .ForEach(t => Console.WriteLine($"Key: {t.Key} Value: {t.Value}"));
        }
    }
```

- Para obter detalhes da API, consulte ListTagsForStreama Referência AWS SDK for .NET da API.

Listar os consumidores de um stream

O exemplo de código a seguir mostra como listar os consumidores de um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// List the consumers of an Amazon Kinesis stream.
    /// </summary>
    public class ListConsumers
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();

            string streamARN = "arn:aws:kinesis:us-east-2:000000000000:stream/
AmazonKinesisStream";
            int maxResults = 10;

            var consumers = await ListConsumersAsync(client, streamARN, maxResults);

            if (consumers.Count > 0)
            {
                consumers
                    .ForEach(c => Console.WriteLine($"Name: {c.ConsumerName} ARN:
 {c.ConsumerARN}"));
            }
            else
            {
                Console.WriteLine("No consumers found.");
            }
        }

        /// <summary>
```

```
        /// Retrieve a list of the consumers for a Kinesis stream.
        /// </summary>
        /// <param name="client">An initialized Kinesis client object.</param>
        /// <param name="streamARN">The ARN of the stream for which we want to
        /// retrieve a list of clients.</param>
        /// <param name="maxResults">The maximum number of results to return.</
param>
        /// <returns>A list of Consumer objects.</returns>
        public static async Task<List<Consumer>> ListConsumersAsync(IAmazonKinesis
 client, string streamARN, int maxResults)
        {
            var request = new ListStreamConsumersRequest
            {
                StreamARN = streamARN,
                MaxResults = maxResults,
            };

            var response = await client.ListStreamConsumersAsync(request);

            return response.Consumers;
        }
    }
```

- Para obter detalhes da API, consulte ListStreamConsumersa Referência AWS SDK for .NET da API.

Registrar um consumidor

O exemplo de código a seguir mostra como registrar um consumidor para um stream do Kinesis.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
```

```
    using Amazon.Kinesis;
    using Amazon.Kinesis.Model;

    /// <summary>
    /// This example shows how to register a consumer to an Amazon Kinesis
    /// stream.
    /// </summary>
    public class RegisterConsumer
    {
        public static async Task Main()
        {
            IAmazonKinesis client = new AmazonKinesisClient();
            string consumerName = "NEW_CONSUMER_NAME";
            string streamARN = "arn:aws:kinesis:us-east-2:000000000000:stream/
AmazonKinesisStream";

            var consumer = await RegisterConsumerAsync(client, consumerName,
 streamARN);

            if (consumer is not null)
            {
                Console.WriteLine($"{consumer.ConsumerName}");
            }
        }

        /// <summary>
        /// Registers the consumer to a Kinesis stream.
        /// </summary>
        /// <param name="client">The initialized Kinesis client object.</param>
        /// <param name="consumerName">A string representing the consumer.</param>
        /// <param name="streamARN">The ARN of the stream.</param>
        /// <returns>A Consumer object that contains information about the
 consumer.</returns>
        public static async Task<Consumer> RegisterConsumerAsync(IAmazonKinesis
 client, string consumerName, string streamARN)
        {
            var request = new RegisterStreamConsumerRequest
            {
                ConsumerName = consumerName,
                StreamARN = streamARN,
            };

            var response = await client.RegisterStreamConsumerAsync(request);
            return response.Consumer;
```

```
        }
    }
```

- Para obter detalhes da API, consulte RegisterStreamConsumera Referência AWS SDK for .NET da API.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando .NET.

```
using System.Text;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace KinesisIntegrationSampleCode;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
```

```
    [Logging(LogEvent = true)]
    public async Task FunctionHandler(KinesisEvent evnt, ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return;
        }

        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                throw;
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando o .NET.

```
using System.Text;
using System.Text.Json.Serialization;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace KinesisIntegration;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task<StreamsEventResponse> FunctionHandler(KinesisEvent evnt,
 ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return new StreamsEventResponse();
        }
```

```
        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                /* Since we are working with streams, we can return the failed item
 immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                return new StreamsEventResponse
                {
                    BatchItemFailures = new
 List<StreamsEventResponse.BatchItemFailure>
                    {
                        new StreamsEventResponse.BatchItemFailure { ItemIdentifier =
 record.Kinesis.SequenceNumber }
                    }
                };
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
        return new StreamsEventResponse();
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}
```

```
public class StreamsEventResponse
{
    [JsonPropertyName("batchItemFailures")]
    public IList<BatchItemFailure> BatchItemFailures { get; set; }
    public class BatchItemFailure
    {
        [JsonPropertyName("itemIdentifier")]
        public string ItemIdentifier { get; set; }
    }
}
```

Exemplos de AWS KMS usando AWS SDK for .NET

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma concessão para uma chave

O exemplo de código a seguir mostra como criar uma concessão para uma chave KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static async Task Main()
        {
            var client = new AmazonKeyManagementServiceClient();

            // The identity that is given permission to perform the operations
            // specified in the grant.
            var grantee = "arn:aws:iam::111122223333:role/ExampleRole";

            // The identifier of the AWS KMS key to which the grant applies. You
            // can use the key ID or the Amazon Resource Name (ARN) of the KMS key.
            var keyId = "7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";

            var request = new CreateGrantRequest
            {
                GranteePrincipal = grantee,
                KeyId = keyId,

                // A list of operations that the grant allows.
                Operations = new List<string>
                {
                    "Encrypt",
                    "Decrypt",
                },
            };

            var response = await client.CreateGrantAsync(request);

            string grantId = response.GrantId; // The unique identifier of the
grant.
            string grantToken = response.GrantToken; // The grant token.

            Console.WriteLine($"Id: {grantId}, Token: {grantToken}");
        }
    }
```

- Para obter detalhes da API, consulte CreateGrant a Referência AWS SDK for .NET da API.

Criar uma chave

O exemplo de código a seguir mostra como criar uma AWS KMS key.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.KeyManagementService;
    using Amazon.KeyManagementService.Model;

    /// <summary>
    /// Shows how to create a new AWS Key Management Service (AWS KMS)
    /// key.
    /// </summary>
    public class CreateKey
    {
        public static async Task Main()
        {
            // Note that if you need to create a Key in an AWS Region
            // other than the Region defined for the default user, you need to
            // pass the Region to the client constructor.
            var client = new AmazonKeyManagementServiceClient();

            // The call to CreateKeyAsync will create a symmetrical AWS KMS
            // key. For more information about symmetrical and asymmetrical
            // keys, see:
            //
            // https://docs.aws.amazon.com/kms/latest/developerguide/symm-asymm-
choose.html
```

```
            var response = await client.CreateKeyAsync(new CreateKeyRequest());

            // The KeyMetadata object contains information about the new AWS KMS
key.
            KeyMetadata keyMetadata = response.KeyMetadata;

            if (keyMetadata is not null)
            {
                Console.WriteLine($"KMS Key: {keyMetadata.KeyId} was successfully
created.");
            }
            else
            {
                Console.WriteLine("Could not create KMS Key.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for .NET da API.

Criar um alias para uma chave

O exemplo de código a seguir mostra como criar um alias para uma chave do KMS Key.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Creates an alias for an AWS Key Management Service (AWS KMS) key.
```

```
    /// </summary>
    public class CreateAlias
    {
        public static async Task Main()
        {
            var client = new AmazonKeyManagementServiceClient();

            // The alias name must start with alias/ and can be
            // up to 256 alphanumeric characters long.
            var aliasName = "alias/ExampleAlias";

            // The value supplied as the TargetKeyId can be either
            // the key ID or key Amazon Resource Name (ARN) of the
            // AWS KMS key.
            var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

            var request = new CreateAliasRequest
            {
                AliasName = aliasName,
                TargetKeyId = keyId,
            };

            var response = await client.CreateAliasAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Alias, {aliasName}, successfully created.");
            }
            else
            {
                Console.WriteLine($"Could not create alias.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateAliasa Referência AWS SDK for .NET da API.

Descrever uma chave

O exemplo de código a seguir mostra como descrever uma chave do KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Retrieve information about an AWS Key Management Service (AWS KMS) key.
/// You can supply either the key Id or the key Amazon Resource Name (ARN)
/// to the DescribeKeyRequest KeyId property.
/// </summary>
public class DescribeKey
{
    public static async Task Main()
    {
        var keyId = "7c9eccc2-38cb-4c4f-9db3-766ee8dd3ad4";
        var request = new DescribeKeyRequest
        {
            KeyId = keyId,
        };

        var client = new AmazonKeyManagementServiceClient();

        var response = await client.DescribeKeyAsync(request);
        var metadata = response.KeyMetadata;

        Console.WriteLine($"{metadata.KeyId} created on:
{metadata.CreationDate}");
        Console.WriteLine($"State: {metadata.KeyState}");
        Console.WriteLine($"{metadata.Description}");
    }
}
```

- Para obter detalhes da API, consulte DescribeKeya Referência AWS SDK for .NET da API.

Desabilitar uma chave

O exemplo de código a seguir mostra como desativar uma chave KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Disable an AWS Key Management Service (AWS KMS) key and then retrieve
/// the key's status to show that it has been disabled.
/// </summary>
public class DisableKey
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();

        // The identifier of the AWS KMS key to disable. You can use the
        // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
        var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

        var request = new DisableKeyRequest
        {
            KeyId = keyId,
        };

        var response = await client.DisableKeyAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
```

```
                // Retrieve information about the key to show that it has now
                // been disabled.
                var describeResponse = await client.DescribeKeyAsync(new
DescribeKeyRequest
                {
                    KeyId = keyId,
                });
                Console.WriteLine($"{describeResponse.KeyMetadata.KeyId} - state:
{describeResponse.KeyMetadata.KeyState}");
            }
        }
    }
```

- Para obter detalhes da API, consulte DisableKeya Referência AWS SDK for .NET da API.

Habilitar uma chave

O exemplo de código a seguir mostra como habilitar uma chave do KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// Enable an AWS Key Management Service (AWS KMS) key.
/// </summary>
public class EnableKey
{
    public static async Task Main()
    {
```

```
            var client = new AmazonKeyManagementServiceClient();

            // The identifier of the AWS KMS key to enable. You can use the
            // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
            var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";

            var request = new EnableKeyRequest
            {
                KeyId = keyId,
            };

            var response = await client.EnableKeyAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                // Retrieve information about the key to show that it has now
                // been enabled.
                var describeResponse = await client.DescribeKeyAsync(new
DescribeKeyRequest
                {
                    KeyId = keyId,
                });
                Console.WriteLine($"{describeResponse.KeyMetadata.KeyId} - state:
{describeResponse.KeyMetadata.KeyState}");
            }
        }
    }
```

- Para obter detalhes da API, consulte EnableKeya Referência AWS SDK for .NET da API.

Listar apelidos para uma chave

O exemplo de código a seguir mostra como listar aliases para uma chave do KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.Threading.Tasks;
   using Amazon.KeyManagementService;
   using Amazon.KeyManagementService.Model;

   /// <summary>
   /// List the AWS Key Management Service (AWS KMS) aliases that have been defined
for
   /// the keys in the same AWS Region as the default user. If you want to list
   /// the aliases in a different Region, pass the Region to the client
   /// constructor.
   /// </summary>
   public class ListAliases
   {
       public static async Task Main()
       {
           var client = new AmazonKeyManagementServiceClient();
           var request = new ListAliasesRequest();
           var response = new ListAliasesResponse();

           do
           {
               response = await client.ListAliasesAsync(request);

               response.Aliases.ForEach(alias =>
               {
                   Console.WriteLine($"Created: {alias.CreationDate} Last Update:
{alias.LastUpdatedDate} Name: {alias.AliasName}");
               });

               request.Marker = response.NextMarker;
           }
           while (response.Truncated);
       }
   }
```

- Para obter detalhes da API, consulte ListAliasesa Referência AWS SDK for .NET da API.

Listar concessões para uma chave

O exemplo de código a seguir mostra como listar concessões para uma chave do KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.Threading.Tasks;
   using Amazon.KeyManagementService;
   using Amazon.KeyManagementService.Model;

   /// <summary>
   /// List the AWS Key Management Service (AWS KMS) grants that are associated
with
   /// a specific key.
   /// </summary>
   public class ListGrants
   {
       public static async Task Main()
       {
           // The identifier of the AWS KMS key to disable. You can use the
           // key Id or the Amazon Resource Name (ARN) of the AWS KMS key.
           var keyId = "1234abcd-12ab-34cd-56ef-1234567890ab";
           var client = new AmazonKeyManagementServiceClient();
           var request = new ListGrantsRequest
           {
               KeyId = keyId,
           };

           var response = new ListGrantsResponse();

           do
           {
               response = await client.ListGrantsAsync(request);

               response.Grants.ForEach(grant =>
               {
```

```
                    Console.WriteLine($"{grant.GrantId}");
                });

                request.Marker = response.NextMarker;
            }
            while (response.Truncated);
        }
    }
```

- Para obter detalhes da API, consulte ListGrantsa Referência AWS SDK for .NET da API.

Listar chaves

O exemplo de código a seguir mostra como listar chaves do KMS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.KeyManagementService;
using Amazon.KeyManagementService.Model;

/// <summary>
/// List the AWS Key Managements Service (AWS KMS) keys for the AWS Region
/// of the default user. To list keys in another AWS Region, supply the Region
/// as a parameter to the client constructor.
/// </summary>
public class ListKeys
{
    public static async Task Main()
    {
        var client = new AmazonKeyManagementServiceClient();
        var request = new ListKeysRequest();
        var response = new ListKeysResponse();
```

```
            do
            {
                response = await client.ListKeysAsync(request);

                response.Keys.ForEach(key =>
                {
                    Console.WriteLine($"ID: {key.KeyId}, {key.KeyArn}");
                });

                // Set the Marker property when response.Truncated is true
                // in order to get the next keys.
                request.Marker = response.NextMarker;
            }
            while (response.Truncated);
        }
    }
```

- Para obter detalhes da API, consulte ListKeysa Referência AWS SDK for .NET da API.

Exemplos de Lambda usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for .NET com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace LambdaActions;

using Amazon.Lambda;

public class HelloLambda
{
    static async Task Main(string[] args)
    {
        var lambdaClient = new AmazonLambdaClient();

        Console.WriteLine("Hello AWS Lambda");
        Console.WriteLine("Let's get started with AWS Lambda by listing your
 existing Lambda functions:");

        var response = await lambdaClient.ListFunctionsAsync();
        response.Functions.ForEach(function =>
        {
            Console.WriteLine($"{function.FunctionName}\t{function.Description}");
        });
    }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Creates a new Lambda function.
/// </summary>
/// <param name="functionName">The name of the function.</param>
/// <param name="s3Bucket">The Amazon Simple Storage Service (Amazon S3)
/// bucket where the zip file containing the code is located.</param>
/// <param name="s3Key">The Amazon S3 key of the zip file.</param>
/// <param name="role">The Amazon Resource Name (ARN) of a role with the
/// appropriate Lambda permissions.</param>
/// <param name="handler">The name of the handler function.</param>
/// <returns>The Amazon Resource Name (ARN) of the newly created
/// Lambda function.</returns>
public async Task<string> CreateLambdaFunctionAsync(
    string functionName,
    string s3Bucket,
    string s3Key,
    string role,
    string handler)
{
    // Defines the location for the function code.
    // S3Bucket - The S3 bucket where the file containing
    //            the source code is stored.
    // S3Key    - The name of the file containing the code.
    var functionCode = new FunctionCode
    {
        S3Bucket = s3Bucket,
        S3Key = s3Key,
    };
```

```
        var createFunctionRequest = new CreateFunctionRequest
        {
            FunctionName = functionName,
            Description = "Created by the Lambda .NET API",
            Code = functionCode,
            Handler = handler,
            Runtime = Runtime.Dotnet6,
            Role = role,
        };

        var reponse = await
_lambdaService.CreateFunctionAsync(createFunctionRequest);
        return reponse.FunctionArn;
    }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for .NET da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an AWS Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// delete.</param>
    /// <returns>A Boolean value that indicates the success of the action.</returns>
    public async Task<bool> DeleteFunctionAsync(string functionName)
    {
        var request = new DeleteFunctionRequest
```

```
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.DeleteFunctionAsync(request);

        // A return value of NoContent means that the request was processed.
        // In this case, the function was deleted, and the return value
        // is intentionally blank.
        return response.HttpStatusCode == System.Net.HttpStatusCode.NoContent;
    }
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for .NET da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Gets information about a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function for
    /// which to retrieve information.</param>
    /// <returns>Async Task.</returns>
    public async Task<FunctionConfiguration> GetFunctionAsync(string functionName)
    {
        var functionRequest = new GetFunctionRequest
        {
            FunctionName = functionName,
        };
```

```
        var response = await _lambdaService.GetFunctionAsync(functionRequest);
        return response.Configuration;
    }
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for .NET da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Invoke a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// invoke.</param
    /// <param name="parameters">The parameter values that will be passed to the
function.</param>
    /// <returns>A System Threading Task.</returns>
    public async Task<string> InvokeFunctionAsync(
        string functionName,
        string parameters)
    {
        var payload = parameters;
        var request = new InvokeRequest
        {
            FunctionName = functionName,
            Payload = payload,
        };

        var response = await _lambdaService.InvokeAsync(request);
        MemoryStream stream = response.Payload;
```

```
        string returnValue = System.Text.Encoding.UTF8.GetString(stream.ToArray());
        return returnValue;
    }
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for .NET.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of Lambda functions.
    /// </summary>
    /// <returns>A list of FunctionConfiguration objects.</returns>
    public async Task<List<FunctionConfiguration>> ListFunctionsAsync()
    {
        var functionList = new List<FunctionConfiguration>();

        var functionPaginator =
            _lambdaService.Paginators.ListFunctions(new ListFunctionsRequest());
        await foreach (var function in functionPaginator.Functions)
        {
            functionList.Add(function);
        }

        return functionList;
    }
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for .NET da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update an existing Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to update.</
param>
    /// <param name="bucketName">The bucket where the zip file containing
    /// the Lambda function code is stored.</param>
    /// <param name="key">The key name of the source code file.</param>
    /// <returns>Async Task.</returns>
    public async Task UpdateFunctionCodeAsync(
        string functionName,
        string bucketName,
        string key)
    {
        var functionCodeRequest = new UpdateFunctionCodeRequest
        {
            FunctionName = functionName,
            Publish = true,
            S3Bucket = bucketName,
            S3Key = key,
        };

        var response = await
 _lambdaService.UpdateFunctionCodeAsync(functionCodeRequest);
        Console.WriteLine($"The Function was last modified at
 {response.LastModified}.");
    }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for .NET da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update the code of a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the function to update.</param>
    /// <param name="functionHandler">The code that performs the function's
 actions.</param>
    /// <param name="environmentVariables">A dictionary of environment variables.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateFunctionConfigurationAsync(
        string functionName,
        string functionHandler,
        Dictionary<string, string> environmentVariables)
    {
        var request = new UpdateFunctionConfigurationRequest
        {
            Handler = functionHandler,
            FunctionName = functionName,
            Environment = new Amazon.Lambda.Model.Environment { Variables =
 environmentVariables },
        };

        var response = await
 _lambdaService.UpdateFunctionConfigurationAsync(request);

        Console.WriteLine(response.LastModified);
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for .NET da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie métodos que executem ações do Lambda.

```
namespace LambdaActions;

using Amazon.Lambda;
using Amazon.Lambda.Model;

/// <summary>
/// A class that implements AWS Lambda methods.
```

```
/// </summary>
public class LambdaWrapper
{
    private readonly IAmazonLambda _lambdaService;

    /// <summary>
    /// Constructor for the LambdaWrapper class.
    /// </summary>
    /// <param name="lambdaService">An initialized Lambda service client.</param>
    public LambdaWrapper(IAmazonLambda lambdaService)
    {
        _lambdaService = lambdaService;
    }

    /// <summary>
    /// Creates a new Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the function.</param>
    /// <param name="s3Bucket">The Amazon Simple Storage Service (Amazon S3)
    /// bucket where the zip file containing the code is located.</param>
    /// <param name="s3Key">The Amazon S3 key of the zip file.</param>
    /// <param name="role">The Amazon Resource Name (ARN) of a role with the
    /// appropriate Lambda permissions.</param>
    /// <param name="handler">The name of the handler function.</param>
    /// <returns>The Amazon Resource Name (ARN) of the newly created
    /// Lambda function.</returns>
    public async Task<string> CreateLambdaFunctionAsync(
        string functionName,
        string s3Bucket,
        string s3Key,
        string role,
        string handler)
    {
        // Defines the location for the function code.
        // S3Bucket - The S3 bucket where the file containing
        //            the source code is stored.
        // S3Key    - The name of the file containing the code.
        var functionCode = new FunctionCode
        {
            S3Bucket = s3Bucket,
            S3Key = s3Key,
        };

        var createFunctionRequest = new CreateFunctionRequest
```

```
        {
            FunctionName = functionName,
            Description = "Created by the Lambda .NET API",
            Code = functionCode,
            Handler = handler,
            Runtime = Runtime.Dotnet6,
            Role = role,
        };

        var reponse = await
_lambdaService.CreateFunctionAsync(createFunctionRequest);
        return reponse.FunctionArn;
    }


    /// <summary>
    /// Delete an AWS Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// delete.</param>
    /// <returns>A Boolean value that indicates the success of the action.</returns>
    public async Task<bool> DeleteFunctionAsync(string functionName)
    {
        var request = new DeleteFunctionRequest
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.DeleteFunctionAsync(request);

        // A return value of NoContent means that the request was processed.
        // In this case, the function was deleted, and the return value
        // is intentionally blank.
        return response.HttpStatusCode == System.Net.HttpStatusCode.NoContent;
    }


    /// <summary>
    /// Gets information about a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function for
    /// which to retrieve information.</param>
    /// <returns>Async Task.</returns>
    public async Task<FunctionConfiguration> GetFunctionAsync(string functionName)
```

```
    {
        var functionRequest = new GetFunctionRequest
        {
            FunctionName = functionName,
        };

        var response = await _lambdaService.GetFunctionAsync(functionRequest);
        return response.Configuration;
    }


    /// <summary>
    /// Invoke a Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to
    /// invoke.</param
    /// <param name="parameters">The parameter values that will be passed to the
function.</param>
    /// <returns>A System Threading Task.</returns>
    public async Task<string> InvokeFunctionAsync(
        string functionName,
        string parameters)
    {
        var payload = parameters;
        var request = new InvokeRequest
        {
            FunctionName = functionName,
            Payload = payload,
        };

        var response = await _lambdaService.InvokeAsync(request);
        MemoryStream stream = response.Payload;
        string returnValue = System.Text.Encoding.UTF8.GetString(stream.ToArray());
        return returnValue;
    }


    /// <summary>
    /// Get a list of Lambda functions.
    /// </summary>
    /// <returns>A list of FunctionConfiguration objects.</returns>
    public async Task<List<FunctionConfiguration>> ListFunctionsAsync()
    {
        var functionList = new List<FunctionConfiguration>();
```

```
        var functionPaginator =
            _lambdaService.Paginators.ListFunctions(new ListFunctionsRequest());
        await foreach (var function in functionPaginator.Functions)
        {
            functionList.Add(function);
        }

        return functionList;
    }


    /// <summary>
    /// Update an existing Lambda function.
    /// </summary>
    /// <param name="functionName">The name of the Lambda function to update.</
param>
    /// <param name="bucketName">The bucket where the zip file containing
    /// the Lambda function code is stored.</param>
    /// <param name="key">The key name of the source code file.</param>
    /// <returns>Async Task.</returns>
    public async Task UpdateFunctionCodeAsync(
        string functionName,
        string bucketName,
        string key)
    {
        var functionCodeRequest = new UpdateFunctionCodeRequest
        {
            FunctionName = functionName,
            Publish = true,
            S3Bucket = bucketName,
            S3Key = key,
        };

        var response = await
 _lambdaService.UpdateFunctionCodeAsync(functionCodeRequest);
        Console.WriteLine($"The Function was last modified at
 {response.LastModified}.");
    }


    /// <summary>
    /// Update the code of a Lambda function.
    /// </summary>
```

```
    /// <param name="functionName">The name of the function to update.</param>
    /// <param name="functionHandler">The code that performs the function's
 actions.</param>
    /// <param name="environmentVariables">A dictionary of environment variables.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> UpdateFunctionConfigurationAsync(
        string functionName,
        string functionHandler,
        Dictionary<string, string> environmentVariables)
    {
        var request = new UpdateFunctionConfigurationRequest
        {
            Handler = functionHandler,
            FunctionName = functionName,
            Environment = new Amazon.Lambda.Model.Environment { Variables =
 environmentVariables },
        };

        var response = await
 _lambdaService.UpdateFunctionConfigurationAsync(request);

        Console.WriteLine(response.LastModified);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


}
```

Crie uma função que execute o cenário.

```
global using System.Threading.Tasks;
global using Amazon.IdentityManagement;
global using Amazon.Lambda;
global using LambdaActions;
global using LambdaScenarioCommon;
global using Microsoft.Extensions.DependencyInjection;
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
```

```
global using Microsoft.Extensions.Logging.Debug;


using Amazon.Lambda.Model;
using Microsoft.Extensions.Configuration;

namespace LambdaBasics;

public class LambdaBasics
{
    private static ILogger logger = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for the Amazon service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
            services.AddAWSService<IAmazonLambda>()
            .AddAWSService<IAmazonIdentityManagementService>()
            .AddTransient<LambdaWrapper>()
            .AddTransient<LambdaRoleWrapper>()
            .AddTransient<UIWrapper>()
        )
        .Build();

        var configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
            .AddJsonFile("settings.local.json",
            true) // Optionally load local settings.
        .Build();


        logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<LambdaBasics>();

        var lambdaWrapper = host.Services.GetRequiredService<LambdaWrapper>();
        var lambdaRoleWrapper =
 host.Services.GetRequiredService<LambdaRoleWrapper>();
```

```
        var uiWrapper = host.Services.GetRequiredService<UIWrapper>();

        string functionName = configuration["FunctionName"]!;
        string roleName = configuration["RoleName"]!;
        string policyDocument = "{" +
            " \"Version\": \"2012-10-17\"," +
            " \"Statement\": [ " +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Principal\": {" +
            "            \"Service\": \"lambda.amazonaws.com\" " +
            "    }," +
            "        \"Action\": \"sts:AssumeRole\" " +
            "    }" +
            "]" +
        "}";

        var incrementHandler = configuration["IncrementHandler"];
        var calculatorHandler = configuration["CalculatorHandler"];
        var bucketName = configuration["BucketName"];
        var incrementKey = configuration["IncrementKey"];
        var calculatorKey = configuration["CalculatorKey"];
        var policyArn = configuration["PolicyArn"];

        uiWrapper.DisplayLambdaBasicsOverview();

        // Create the policy to use with the AWS Lambda functions and then attach
the
        // policy to a new role.
        var roleArn = await lambdaRoleWrapper.CreateLambdaRoleAsync(roleName,
policyDocument);

        Console.WriteLine("Waiting for role to become active.");
        uiWrapper.WaitABit(15, "Wait until the role is active before trying to use
it.");

        // Attach the appropriate AWS Identity and Access Management (IAM) role
policy to the new role.
        var success = await lambdaRoleWrapper.AttachLambdaRolePolicyAsync(policyArn,
roleName);
        uiWrapper.WaitABit(10, "Allow time for the IAM policy to be attached to the
role.");
```

```
        // Create the Lambda function using a zip file stored in an Amazon Simple
Storage Service
        // (Amazon S3) bucket.
        uiWrapper.DisplayTitle("Create Lambda Function");
        Console.WriteLine($"Creating the AWS Lambda function: {functionName}.");
        var lambdaArn = await lambdaWrapper.CreateLambdaFunctionAsync(
            functionName,
            bucketName,
            incrementKey,
            roleArn,
            incrementHandler);

        Console.WriteLine("Waiting for the new function to be available.");
        Console.WriteLine($"The AWS Lambda ARN is {lambdaArn}");

        // Get the Lambda function.
        Console.WriteLine($"Getting the {functionName} AWS Lambda function.");
        FunctionConfiguration config;
        do
        {
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.State != State.Active);

        Console.WriteLine($"\nThe function, {functionName} has been created.");
        Console.WriteLine($"The runtime of this Lambda function is
{config.Runtime}.");

        uiWrapper.PressEnter();

        // List the Lambda functions.
        uiWrapper.DisplayTitle("Listing all Lambda functions.");
        var functions = await lambdaWrapper.ListFunctionsAsync();
        DisplayFunctionList(functions);

        uiWrapper.DisplayTitle("Invoke increment function");
        Console.WriteLine("Now that it has been created, invoke the Lambda increment
function.");
        string? value;
        do
        {
            Console.Write("Enter a value to increment: ");
            value = Console.ReadLine();
```

```
        }
        while (string.IsNullOrEmpty(value));

        string functionParameters = "{" +
            "\"action\": \"increment\", " +
            "\"x\": \"" + value + "\"" +
        "}";
        var answer = await lambdaWrapper.InvokeFunctionAsync(functionName,
functionParameters);
        Console.WriteLine($"{value} + 1 = {answer}.");

        uiWrapper.DisplayTitle("Update function");
        Console.WriteLine("Now update the Lambda function code.");
        await lambdaWrapper.UpdateFunctionCodeAsync(functionName, bucketName,
calculatorKey);

        do
        {
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.LastUpdateStatus == LastUpdateStatus.InProgress);

        await lambdaWrapper.UpdateFunctionConfigurationAsync(
            functionName,
            calculatorHandler,
            new Dictionary<string, string> { { "LOG_LEVEL", "DEBUG" } });

        do
        {
            config = await lambdaWrapper.GetFunctionAsync(functionName);
            Console.Write(".");
        }
        while (config.LastUpdateStatus == LastUpdateStatus.InProgress);

        uiWrapper.DisplayTitle("Call updated function");
        Console.WriteLine("Now call the updated function...");

        bool done = false;

        do
        {
            string? opSelected;
```

```
            Console.WriteLine("Select the operation to perform:");
            Console.WriteLine("\t1. add");
            Console.WriteLine("\t2. subtract");
            Console.WriteLine("\t3. multiply");
            Console.WriteLine("\t4. divide");
            Console.WriteLine("\tOr enter \"q\" to quit.");
            Console.WriteLine("Enter the number (1, 2, 3, 4, or q) of the operation
you want to perform: ");
            do
            {
                Console.Write("Your choice? ");
                opSelected = Console.ReadLine();
            }
            while (opSelected == string.Empty);

            var operation = (opSelected) switch
            {
                "1" => "add",
                "2" => "subtract",
                "3" => "multiply",
                "4" => "divide",
                "q" => "quit",
                _ => "add",
            };

            if (operation == "quit")
            {
                done = true;
            }
            else
            {
                // Get two numbers and an action from the user.
                value = string.Empty;
                do
                {
                    Console.Write("Enter the first value: ");
                    value = Console.ReadLine();
                }
                while (value == string.Empty);

                string? value2;
                do
                {
                    Console.Write("Enter a second value: ");
```

```
                    value2 = Console.ReadLine();
                }
                while (value2 == string.Empty);

                functionParameters = "{" +
                    "\"action\": \"" + operation + "\", " +
                    "\"x\": \"" + value + "\"," +
                    "\"y\": \"" + value2 + "\"" +
                "}";

                answer = await lambdaWrapper.InvokeFunctionAsync(functionName,
functionParameters);
                Console.WriteLine($"The answer when we {operation} the two numbers
is: {answer}.");
            }

            uiWrapper.PressEnter();
        } while (!done);

        // Delete the function created earlier.

        uiWrapper.DisplayTitle("Clean up resources");
        // Detach the IAM policy from the IAM role.
        Console.WriteLine("First detach the IAM policy from the role.");
        success = await lambdaRoleWrapper.DetachLambdaRolePolicyAsync(policyArn,
roleName);
        uiWrapper.WaitABit(15, "Let's wait for the policy to be fully detached from
the role.");

        Console.WriteLine("Delete the AWS Lambda function.");
        success = await lambdaWrapper.DeleteFunctionAsync(functionName);
        if (success)
        {
            Console.WriteLine($"The {functionName} function was deleted.");
        }
        else
        {
            Console.WriteLine($"Could not remove the function {functionName}");
        }

        // Now delete the IAM role created for use with the functions
        // created by the application.
        Console.WriteLine("Now we can delete the role that we created.");
        success = await lambdaRoleWrapper.DeleteLambdaRoleAsync(roleName);
```

```
        if (success)
        {
            Console.WriteLine("The role has been successfully removed.");
        }
        else
        {
            Console.WriteLine("Couldn't delete the role.");
        }

        Console.WriteLine("The Lambda Scenario is now complete.");
        uiWrapper.PressEnter();

        // Displays a formatted list of existing functions returned by the
        // LambdaMethods.ListFunctions.
        void DisplayFunctionList(List<FunctionConfiguration> functions)
        {
            functions.ForEach(functionConfig =>
            {

 Console.WriteLine($"{functionConfig.FunctionName}\t{functionConfig.Description}");
            });
        }
    }
}


namespace LambdaActions;

using Amazon.IdentityManagement;
using Amazon.IdentityManagement.Model;

public class LambdaRoleWrapper
{
    private readonly IAmazonIdentityManagementService _lambdaRoleService;

    public LambdaRoleWrapper(IAmazonIdentityManagementService lambdaRoleService)
    {
        _lambdaRoleService = lambdaRoleService;
    }

    /// <summary>
    /// Attach an AWS Identity and Access Management (IAM) role policy to the
    /// IAM role to be assumed by the AWS Lambda functions created for the scenario.
    /// </summary>
```

```
    /// <param name="policyArn">The Amazon Resource Name (ARN) of the IAM policy.</
param>
    /// <param name="roleName">The name of the IAM role to attach the IAM policy
 to.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AttachLambdaRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _lambdaRoleService.AttachRolePolicyAsync(new
 AttachRolePolicyRequest { PolicyArn = policyArn, RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Create a new IAM role.
    /// </summary>
    /// <param name="roleName">The name of the IAM role to create.</param>
    /// <param name="policyDocument">The policy document for the new IAM role.</
param>
    /// <returns>A string representing the ARN for newly created role.</returns>
    public async Task<string> CreateLambdaRoleAsync(string roleName, string
 policyDocument)
    {
        var request = new CreateRoleRequest
        {
            AssumeRolePolicyDocument = policyDocument,
            RoleName = roleName,
        };

        var response = await _lambdaRoleService.CreateRoleAsync(request);
        return response.Role.Arn;
    }

    /// <summary>
    /// Deletes an IAM role.
    /// </summary>
    /// <param name="roleName">The name of the role to delete.</param>
    /// <returns>A Boolean value indicating the success of the operation.</returns>
    public async Task<bool> DeleteLambdaRoleAsync(string roleName)
    {
        var request = new DeleteRoleRequest
        {
            RoleName = roleName,
        };
```

```
        var response = await _lambdaRoleService.DeleteRoleAsync(request);
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    public async Task<bool> DetachLambdaRolePolicyAsync(string policyArn, string
 roleName)
    {
        var response = await _lambdaRoleService.DetachRolePolicyAsync(new
 DetachRolePolicyRequest { PolicyArn = policyArn, RoleName = roleName });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
}


namespace LambdaScenarioCommon;
public class UIWrapper
{
    public readonly string SepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the AWS Lambda Basics scenario.
    /// </summary>
    public void DisplayLambdaBasicsOverview()
    {
        Console.Clear();

        DisplayTitle("Welcome to AWS Lambda Basics");
        Console.WriteLine("This example application does the following:");
        Console.WriteLine("\t1. Creates an AWS Identity and Access Management (IAM)
 role that will be assumed by the functions we create.");
        Console.WriteLine("\t2. Attaches an IAM role policy that has Lambda
 permissions.");
        Console.WriteLine("\t3. Creates a Lambda function that increments the value
 passed to it.");
        Console.WriteLine("\t4. Calls the increment function and passes a value.");
        Console.WriteLine("\t5. Updates the code so that the function is a simple
 calculator.");
        Console.WriteLine("\t6. Calls the calculator function with the values
 entered.");
        Console.WriteLine("\t7. Deletes the Lambda function.");
        Console.WriteLine("\t7. Detaches the IAM role policy.");
        Console.WriteLine("\t8. Deletes the IAM role.");
        PressEnter();
```

```
    }

    /// <summary>
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue. ");
        _ = Console.ReadLine();
        Console.WriteLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter">The string to be centered.</param>
    /// <returns>The padded string.</returns>
    public string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(SepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(SepBar);
    }

    /// <summary>
    /// Display a countdown and wait for a number of seconds.
    /// </summary>
    /// <param name="numSeconds">The number of seconds to wait.</param>
    public void WaitABit(int numSeconds, string msg)
    {
        Console.WriteLine(msg);
```

```
        // Wait for the requested number of seconds.
        for (int i = numSeconds; i > 0; i--)
        {
            System.Threading.Thread.Sleep(1000);
            Console.Write($"{i}...");
        }

        PressEnter();
    }
}
```

Defina um manipulador do Lambda que aumente um número.

```
using Amazon.Lambda.Core;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace LambdaIncrement;

public class Function
{

    /// <summary>
    /// A simple function increments the integer parameter.
    /// </summary>
    /// <param name="input">A JSON string containing an action, which must be
    /// "increment" and a string representing the value to increment.</param>
    /// <param name="context">The context object passed by Lambda containing
    /// information about invocation, function, and execution environment.</param>
    /// <returns>A string representing the incremented value of the parameter.</
returns>
    public int FunctionHandler(Dictionary<string, string> input, ILambdaContext
 context)
    {
        if (input["action"] == "increment")
        {
            int inputValue = Convert.ToInt32(input["x"]);
            return inputValue + 1;
```

```
        }
        else
        {
            return 0;
        }
    }
}
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
using Amazon.Lambda.Core;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace LambdaCalculator;

public class Function
{

    /// <summary>
    /// A simple function that takes two number in string format and performs
    /// the requested arithmetic function.
    /// </summary>
    /// <param name="input">JSON data containing an action, and x and y values.
    /// Valid actions include: add, subtract, multiply, and divide.</param>
    /// <param name="context">The context object passed by Lambda containing
    /// information about invocation, function, and execution environment.</param>
    /// <returns>A string representing the results of the calculation.</returns>
    public int FunctionHandler(Dictionary<string, string> input, ILambdaContext
 context)
    {
        var action = input["action"];
        int x = Convert.ToInt32(input["x"]);
        int y = Convert.ToInt32(input["y"]);
        int result;
        switch (action)
        {
            case "add":
```

```
                result = x + y;
                break;
            case "subtract":
                result = x - y;
                break;
            case "multiply":
                result = x * y;
                break;
            case "divide":
                if (y == 0)
                {
                    Console.Error.WriteLine("Divide by zero error.");
                    result = 0;
                }
                else
                    result = x / y;
                break;
            default:
                Console.Error.WriteLine($"{action} is not a valid operation.");
                result = 0;
                break;
        }
        return result;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando .NET.

```
using System.Text;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace KinesisIntegrationSampleCode;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task FunctionHandler(KinesisEvent evnt, ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return;
        }
```

```
        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                throw;
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando .NET.

```
using System.Threading.Tasks;
using Amazon.Lambda.Core;
using Amazon.S3;
using System;
using Amazon.Lambda.S3Events;
using System.Web;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace S3Integration
{
    public class Function
    {
        private static AmazonS3Client _s3Client;
        public Function() : this(null)
        {
        }

        internal Function(AmazonS3Client s3Client)
        {
            _s3Client = s3Client ?? new AmazonS3Client();
        }

        public async Task<string> Handler(S3Event evt, ILambdaContext context)
        {
            try
            {
                if (evt.Records.Count <= 0)
                {
                    context.Logger.LogLine("Empty S3 Event received");
```

```
                    return string.Empty;
                }

                var bucket = evt.Records[0].S3.Bucket.Name;
                var key = HttpUtility.UrlDecode(evt.Records[0].S3.Object.Key);

                context.Logger.LogLine($"Request is for {bucket} and {key}");

                var objectResult = await _s3Client.GetObjectAsync(bucket, key);

                context.Logger.LogLine($"Returning {objectResult.Key}");

                return objectResult.Key;
            }
            catch (Exception e)
            {
                context.Logger.LogLine($"Error processing request - {e.Message}");

                return string.Empty;
            }
        }
    }
}
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
```

```
using Amazon.Lambda.SNSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace SnsIntegration;

public class Function
{
    public async Task FunctionHandler(SNSEvent evnt, ILambdaContext context)
    {
        foreach (var record in evnt.Records)
        {
            await ProcessRecordAsync(record, context);
        }
        context.Logger.LogInformation("done");
    }

    private async Task ProcessRecordAsync(SNSEvent.SNSRecord record, ILambdaContext
 context)
    {
        try
        {
            context.Logger.LogInformation($"Processed record {record.Sns.Message}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }
    }
}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace SqsIntegrationSampleCode
{
    public async Task FunctionHandler(SQSEvent evnt, ILambdaContext context)
    {
        foreach (var message in evnt.Records)
        {
            await ProcessMessageAsync(message, context);
        }

        context.Logger.LogInformation("done");
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        try
        {
```

```
            context.Logger.LogInformation($"Processed message {message.Body}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }

    }
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando o .NET.

```
using System.Text;
using System.Text.Json.Serialization;
using Amazon.Lambda.Core;
using Amazon.Lambda.KinesisEvents;
using AWS.Lambda.Powertools.Logging;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
```

```
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace KinesisIntegration;

public class Function
{
    // Powertools Logger requires an environment variables against your function
    // POWERTOOLS_SERVICE_NAME
    [Logging(LogEvent = true)]
    public async Task<StreamsEventResponse> FunctionHandler(KinesisEvent evnt,
 ILambdaContext context)
    {
        if (evnt.Records.Count == 0)
        {
            Logger.LogInformation("Empty Kinesis Event received");
            return new StreamsEventResponse();
        }

        foreach (var record in evnt.Records)
        {
            try
            {
                Logger.LogInformation($"Processed Event with EventId:
 {record.EventId}");
                string data = await GetRecordDataAsync(record.Kinesis, context);
                Logger.LogInformation($"Data: {data}");
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex)
            {
                Logger.LogError($"An error occurred {ex.Message}");
                /* Since we are working with streams, we can return the failed item
 immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                return new StreamsEventResponse
                {
                    BatchItemFailures = new
 List<StreamsEventResponse.BatchItemFailure>
                    {
                        new StreamsEventResponse.BatchItemFailure { ItemIdentifier =
 record.Kinesis.SequenceNumber }
                    }
```

```
                };
            }
        }
        Logger.LogInformation($"Successfully processed {evnt.Records.Count}
 records.");
        return new StreamsEventResponse();
    }

    private async Task<string> GetRecordDataAsync(KinesisEvent.Record record,
 ILambdaContext context)
    {
        byte[] bytes = record.Data.ToArray();
        string data = Encoding.UTF8.GetString(bytes);
        await Task.CompletedTask; //Placeholder for actual async work
        return data;
    }
}

public class StreamsEventResponse
{
    [JsonPropertyName("batchItemFailures")]
    public IList<BatchItemFailure> BatchItemFailures { get; set; }
    public class BatchItemFailure
    {
        [JsonPropertyName("itemIdentifier")]
        public string ItemIdentifier { get; set; }
    }
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando o .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali
namespace sqsSample;

public class Function
{
    public async Task<SQSBatchResponse> FunctionHandler(SQSEvent evnt,
 ILambdaContext context)
    {
        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 List<SQSBatchResponse.BatchItemFailure>();
        foreach(var message in evnt.Records)
        {
            try
            {
                //process your message
                await ProcessMessageAsync(message, context);
            }
            catch (System.Exception)
            {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.Add(new
 SQSBatchResponse.BatchItemFailure{ItemIdentifier=message.MessageId});
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        if (String.IsNullOrEmpty(message.Body))
        {
            throw new Exception("No Body in SQS Message.");
        }
        context.Logger.LogInformation($"Processed message {message.Body}");
        // TODO: Do interesting work based on the new message
```

```
        await Task.CompletedTask;
    }
}
```

MediaConvert exemplos usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET with MediaConvert.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá MediaConvert

O exemplo de código a seguir mostra como começar a usar o AWS Elemental MediaConvert.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.MediaConvert;
using Amazon.MediaConvert.Model;

namespace MediaConvertActions;

public static class HelloMediaConvert
```

```
{
    static async Task Main(string[] args)
    {
        // Create the client using the default profile.
        var mediaConvertClient = new AmazonMediaConvertClient();

        Console.WriteLine($"Hello AWS Elemental MediaConvert! Your MediaConvert
 Endpoints are:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the MediaConvert endpoints.
        var response = await mediaConvertClient.DescribeEndpointsAsync(
            new DescribeEndpointsRequest()
            );

        foreach (var endPoint in response.Endpoints)
        {
            Console.WriteLine($"\tEndPoint: {endPoint.Url}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeEndpointsa Referência AWS SDK for .NET da API.

Tópicos

- Ações

Ações

Criar trabalho de transcodificação

O exemplo de código a seguir mostra como criar um trabalho de transcodificação doAWS Elemental MediaConvert.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-role-
in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];

        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or set
 it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
            DescribeEndpointsRequest describeRequest = new
 DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
 client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
```

```
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };

        AmazonMediaConvertClient mcClient = new AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Creating job for input file {fileInput}.");
        var jobId = await wrapper.CreateJob(mediaConvertRole!, fileInput!,
 fileOutput!);
        Console.WriteLine($"Created job with Job ID: {jobId}");
        Console.WriteLine(new string('-', 80));
```

Crie o trabalho usando o método wrapper e retorne o ID do trabalho.

```
    /// <summary>
    /// Create a job to convert a media file.
    /// </summary>
    /// <param name="mediaConvertRole">The Amazon Resource Name (ARN) of the media
 convert role, as specified here:
    /// https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-role-in-
mediaconvert-configured.html</param>
    /// <param name="fileInput">The Amazon Simple Storage Service (Amazon S3)
 location of the input media file.</param>
    /// <param name="fileOutput">The Amazon S3 location for the output media file.</
param>
    /// <returns>The ID of the new job.</returns>
    public async Task<string> CreateJob(string mediaConvertRole, string fileInput,
        string fileOutput)
    {
        CreateJobRequest createJobRequest = new CreateJobRequest
        {
            Role = mediaConvertRole
        };
```

```
        createJobRequest.UserMetadata.Add("Customer", "Amazon");

        JobSettings jobSettings = new JobSettings
        {
            AdAvailOffset = 0,
            TimecodeConfig = new TimecodeConfig
            {
                Source = TimecodeSource.EMBEDDED
            }
        };
        createJobRequest.Settings = jobSettings;

        #region OutputGroup

        OutputGroup ofg = new OutputGroup
        {
            Name = "File Group",
            OutputGroupSettings = new OutputGroupSettings
            {
                Type = OutputGroupType.FILE_GROUP_SETTINGS,
                FileGroupSettings = new FileGroupSettings
                {
                    Destination = fileOutput
                }
            }
        };

        Output output = new Output
        {
            NameModifier = "_1"
        };

        #region VideoDescription

        VideoDescription vdes = new VideoDescription
        {
            ScalingBehavior = ScalingBehavior.DEFAULT,
            TimecodeInsertion = VideoTimecodeInsertion.DISABLED,
            AntiAlias = AntiAlias.ENABLED,
            Sharpness = 50,
            AfdSignaling = AfdSignaling.NONE,
            DropFrameTimecode = DropFrameTimecode.ENABLED,
            RespondToAfd = RespondToAfd.NONE,
            ColorMetadata = ColorMetadata.INSERT,
```

```
            CodecSettings = new VideoCodecSettings
            {
                Codec = VideoCodec.H_264
            }
        };
        output.VideoDescription = vdes;

        H264Settings h264 = new H264Settings
        {
            InterlaceMode = H264InterlaceMode.PROGRESSIVE,
            NumberReferenceFrames = 3,
            Syntax = H264Syntax.DEFAULT,
            Softness = 0,
            GopClosedCadence = 1,
            GopSize = 90,
            Slices = 1,
            GopBReference = H264GopBReference.DISABLED,
            SlowPal = H264SlowPal.DISABLED,
            SpatialAdaptiveQuantization = H264SpatialAdaptiveQuantization.ENABLED,
            TemporalAdaptiveQuantization = H264TemporalAdaptiveQuantization.ENABLED,
            FlickerAdaptiveQuantization = H264FlickerAdaptiveQuantization.DISABLED,
            EntropyEncoding = H264EntropyEncoding.CABAC,
            Bitrate = 5000000,
            FramerateControl = H264FramerateControl.SPECIFIED,
            RateControlMode = H264RateControlMode.CBR,
            CodecProfile = H264CodecProfile.MAIN,
            Telecine = H264Telecine.NONE,
            MinIInterval = 0,
            AdaptiveQuantization = H264AdaptiveQuantization.HIGH,
            CodecLevel = H264CodecLevel.AUTO,
            FieldEncoding = H264FieldEncoding.PAFF,
            SceneChangeDetect = H264SceneChangeDetect.ENABLED,
            QualityTuningLevel = H264QualityTuningLevel.SINGLE_PASS,
            FramerateConversionAlgorithm =
                H264FramerateConversionAlgorithm.DUPLICATE_DROP,
            UnregisteredSeiTimecode = H264UnregisteredSeiTimecode.DISABLED,
            GopSizeUnits = H264GopSizeUnits.FRAMES,
            ParControl = H264ParControl.SPECIFIED,
            NumberBFramesBetweenReferenceFrames = 2,
            RepeatPps = H264RepeatPps.DISABLED,
            FramerateNumerator = 30,
            FramerateDenominator = 1,
            ParNumerator = 1,
            ParDenominator = 1
```

```
        };
        output.VideoDescription.CodecSettings.H264Settings = h264;

        #endregion VideoDescription

        #region AudioDescription

        AudioDescription ades = new AudioDescription
        {
            LanguageCodeControl = AudioLanguageCodeControl.FOLLOW_INPUT,
            // This name matches one specified in the following Inputs.
            AudioSourceName = "Audio Selector 1",
            CodecSettings = new AudioCodecSettings
            {
                Codec = AudioCodec.AAC
            }
        };

        AacSettings aac = new AacSettings
        {
            AudioDescriptionBroadcasterMix =
AacAudioDescriptionBroadcasterMix.NORMAL,
            RateControlMode = AacRateControlMode.CBR,
            CodecProfile = AacCodecProfile.LC,
            CodingMode = AacCodingMode.CODING_MODE_2_0,
            RawFormat = AacRawFormat.NONE,
            SampleRate = 48000,
            Specification = AacSpecification.MPEG4,
            Bitrate = 64000
        };
        ades.CodecSettings.AacSettings = aac;
        output.AudioDescriptions.Add(ades);

        #endregion AudioDescription

        #region Mp4 Container

        output.ContainerSettings = new ContainerSettings
        {
            Container = ContainerType.MP4
        };
        Mp4Settings mp4 = new Mp4Settings
        {
            CslgAtom = Mp4CslgAtom.INCLUDE,
```

```
            FreeSpaceBox = Mp4FreeSpaceBox.EXCLUDE,
            MoovPlacement = Mp4MoovPlacement.PROGRESSIVE_DOWNLOAD
        };
        output.ContainerSettings.Mp4Settings = mp4;

        #endregion Mp4 Container

        ofg.Outputs.Add(output);
        createJobRequest.Settings.OutputGroups.Add(ofg);

        #endregion OutputGroup

        #region Input

        Input input = new Input
        {
            FilterEnable = InputFilterEnable.AUTO,
            PsiControl = InputPsiControl.USE_PSI,
            FilterStrength = 0,
            DeblockFilter = InputDeblockFilter.DISABLED,
            DenoiseFilter = InputDenoiseFilter.DISABLED,
            TimecodeSource = InputTimecodeSource.EMBEDDED,
            FileInput = fileInput
        };

        AudioSelector audsel = new AudioSelector
        {
            Offset = 0,
            DefaultSelection = AudioDefaultSelection.NOT_DEFAULT,
            ProgramSelection = 1,
            SelectorType = AudioSelectorType.TRACK
        };
        audsel.Tracks.Add(1);
        input.AudioSelectors.Add("Audio Selector 1", audsel);

        input.VideoSelector = new VideoSelector
        {
            ColorSpace = ColorSpace.FOLLOW
        };

        createJobRequest.Settings.Inputs.Add(input);

        #endregion Input
```

```
        var jobId = "";
        try
        {
            CreateJobResponse createJobResponse =
                await _amazonMediaConvert.CreateJobAsync(createJobRequest);

            jobId = createJobResponse.Job.Id;
        }
        catch (BadRequestException bre)
        {
            // If the endpoint was bad.
            if (bre.Message.StartsWith("You must use the customer-"))
            {
                // The exception contains the correct endpoint; extract it.
                var mediaConvertEndpoint = bre.Message.Split('\'')[1];
                Console.WriteLine(
                    $"Request failed, please use endpoint {mediaConvertEndpoint}.");
            }
            else
                throw;
        }

        return jobId;
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for .NET da API.

Obter um trabalho de transcodificação

O exemplo de código a seguir mostra como obter um trabalho de transcodificação do AWS Elemental MediaConvert.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-role-
in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];

        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or set
 it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
            DescribeEndpointsRequest describeRequest = new
 DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
 client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };

        AmazonMediaConvertClient mcClient = new AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

Obtenha um trabalho pelo seu ID.

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Getting job information for Job ID {jobId}");
        var job = await wrapper.GetJobById(jobId);
        Console.WriteLine($"Job {job.Id} created on {job.CreatedAt:d} has status
{job.Status}.");
        Console.WriteLine(new string('-', 80));
```

```
    /// <summary>
    /// Get the job information for a job by its ID.
    /// </summary>
    /// <param name="jobId">The ID of the job.</param>
    /// <returns>The Job object.</returns>
    public async Task<Job> GetJobById(string jobId)
    {
        var jobResponse = await _amazonMediaConvert.GetJobAsync(
                new GetJobRequest
                {
                    Id = jobId
                });

        return jobResponse.Job;
    }
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for .NET da API.

Listar trabalhos de transcodificação

O exemplo de código a seguir mostra como listar trabalhos transcodificação AWS Elemental MediaConvert.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o endpoint e configure o cliente.

```
        // MediaConvert role Amazon Resource Name (ARN).
        // For information on creating this role, see
        // https://docs.aws.amazon.com/mediaconvert/latest/ug/creating-the-iam-role-
in-mediaconvert-configured.html.
        var mediaConvertRole = _configuration["mediaConvertRoleARN"];

        // Include the file input and output locations in settings.json or
 settings.local.json.
        var fileInput = _configuration["fileInput"];
        var fileOutput = _configuration["fileOutput"];

        // Load the customer endpoint, if it is known.
        // When you know what your Region-specific endpoint is, set it here, or set
 it in your settings.local.json file.
        var mediaConvertEndpoint = _configuration["mediaConvertEndpoint"];

        Console.WriteLine("Welcome to the MediaConvert Create Job example.");
        // If you don't have the customer-specific endpoint, request it here.
        if (string.IsNullOrEmpty(mediaConvertEndpoint))
        {
            Console.WriteLine("Getting customer-specific MediaConvert endpoint.");
            AmazonMediaConvertClient client = new AmazonMediaConvertClient();
            DescribeEndpointsRequest describeRequest = new
 DescribeEndpointsRequest();
            DescribeEndpointsResponse describeResponse = await
 client.DescribeEndpointsAsync(describeRequest);
            mediaConvertEndpoint = describeResponse.Endpoints[0].Url;
        }
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Using endpoint {mediaConvertEndpoint}.");
        Console.WriteLine(new string('-', 80));
        // Because you have a service URL for MediaConvert, you don't
```

```
        // need to set RegionEndpoint. If you do, the ServiceURL will
        // be overwritten.
        AmazonMediaConvertConfig mcConfig = new AmazonMediaConvertConfig
        {
            ServiceURL = mediaConvertEndpoint,
        };

        AmazonMediaConvertClient mcClient = new AmazonMediaConvertClient(mcConfig);

        var wrapper = new MediaConvertWrapper(mcClient);
```

Liste os trabalhos com um status específico.

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Listing all complete jobs.");
        var completeJobs = await wrapper.ListAllJobsByStatus(JobStatus.COMPLETE);
        completeJobs.ForEach(j =>
        {
            Console.WriteLine($"Job {j.Id} created on {j.CreatedAt:d} has status
{j.Status}.");
        });
```

Liste os trabalhos usando um paginador.

```
    /// <summary>
    /// List all of the jobs with a particular status using a paginator.
    /// </summary>
    /// <param name="status">The status to use when listing jobs.</param>
    /// <returns>The list of jobs matching the status.</returns>
    public async Task<List<Job>> ListAllJobsByStatus(JobStatus? status = null)
    {
        var returnedJobs = new List<Job>();

        var paginatedJobs = _amazonMediaConvert.Paginators.ListJobs(
                new ListJobsRequest
                {
                    Status = status
                });

        // Get the entire list using the paginator.
        await foreach (var job in paginatedJobs.Jobs)
```

```
        {
            returnedJobs.Add(job);
        }

        return returnedJobs;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

Exemplos do Organizations usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Organizations.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Anexar uma política a uma meta

O exemplo de código a seguir mostra como anexar uma política do Organizations a um destino.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to attach an AWS Organizations policy to an organization,
/// an organizational unit, or an account.
/// </summary>
public class AttachPolicy
{
    /// <summary>
    /// Initializes the Organizations client object and then calls the
    /// AttachPolicyAsync method to attach the policy to the root
    /// organization.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();
        var policyId = "p-00000000";
        var targetId = "r-0000";

        var request = new AttachPolicyRequest
        {
            PolicyId = policyId,
            TargetId = targetId,
        };

        var response = await client.AttachPolicyAsync(request);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine($"Successfully attached Policy ID {policyId} to
Target ID: {targetId}.");
        }
        else
        {
            Console.WriteLine("Was not successful in attaching the policy.");
        }
    }
}
```

- Para obter detalhes da API, consulte AttachPolicya Referência AWS SDK for .NET da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates a new AWS Organizations Policy.
/// </summary>
public class CreatePolicy
{
    /// <summary>
    /// Initializes the AWS Organizations client object, uses it to
    /// create a new Organizations Policy, and then displays information
    /// about the newly created Policy.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();
        var policyContent = "{" +
            "   \"Version\": \"2012-10-17\"," +
            " \"Statement\" : [{" +
                " \"Action\" : [\"s3:*\"]," +
                " \"Effect\" : \"Allow\"," +
                " \"Resource\" : \"*\"" +
            "}]" +
        "}";

        try
```

```
            {
                var response = await client.CreatePolicyAsync(new
CreatePolicyRequest
                {
                    Content = policyContent,
                    Description = "Enables admins of attached accounts to delegate
all Amazon S3 permissions",
                    Name = "AllowAllS3Actions",
                    Type = "SERVICE_CONTROL_POLICY",
                });

                Policy policy = response.Policy;
                Console.WriteLine($"{policy.PolicySummary.Name} has the following
content: {policy.Content}");
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for .NET da API.

Criar uma conta da

O exemplo de código a seguir mostra como criar uma conta do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
```

```
    using Amazon.Organizations.Model;

    /// <summary>
    /// Creates a new AWS Organizations account.
    /// </summary>
    public class CreateAccount
    {
        /// <summary>
        /// Initializes an Organizations client object and uses it to create
        /// the new account with the name specified in accountName.
        /// </summary>
        public static async Task Main()
        {
            IAmazonOrganizations client = new AmazonOrganizationsClient();
            var accountName = "ExampleAccount";
            var email = "someone@example.com";

            var request = new CreateAccountRequest
            {
                AccountName = accountName,
                Email = email,
            };

            var response = await client.CreateAccountAsync(request);
            var status = response.CreateAccountStatus;

            Console.WriteLine($"The staus of {status.AccountName} is
{status.State}.");
        }
    }
```

- Para obter detalhes da API, consulte CreateAccounta Referência AWS SDK for .NET da API.

Criar uma organização

O exemplo de código a seguir mostra como criar uma organização do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates an organization in AWS Organizations.
/// </summary>
public class CreateOrganization
{
    /// <summary>
    /// Creates an Organizations client object and then uses it to create
    /// a new organization with the default user as the administrator, and
    /// then displays information about the new organization.
    /// </summary>
    public static async Task Main()
    {
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var response = await client.CreateOrganizationAsync(new
CreateOrganizationRequest
        {
            FeatureSet = "ALL",
        });

        Organization newOrg = response.Organization;

        Console.WriteLine($"Organization: {newOrg.Id} Main Accoount:
{newOrg.MasterAccountId}");
    }
}
```

- Para obter detalhes da API, consulte CreateOrganizationa Referência AWS SDK for .NET da API.

Criação de uma unidade organizacional

O exemplo de código a seguir mostra como criar uma unidade organizacional do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Creates a new organizational unit in AWS Organizations.
/// </summary>
public class CreateOrganizationalUnit
{
    /// <summary>
    /// Initializes an Organizations client object and then uses it to call
    /// the CreateOrganizationalUnit method. If the call succeeds, it
    /// displays information about the new organizational unit.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var orgUnitName = "ProductDevelopmentUnit";

        var request = new CreateOrganizationalUnitRequest
        {
            Name = orgUnitName,
            ParentId = "r-0000",
        };
```

```
            var response = await client.CreateOrganizationalUnitAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully created organizational unit:
{orgUnitName}.");
                Console.WriteLine($"Organizational unit {orgUnitName} Details");
                Console.WriteLine($"ARN: {response.OrganizationalUnit.Arn} Id:
{response.OrganizationalUnit.Id}");
            }
            else
            {
                Console.WriteLine("Could not create new organizational unit.");
            }
        }
    }
```

- Para obter detalhes da API, consulte CreateOrganizationalUnita Referência AWS SDK for .NET da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
```

```
    /// Deletes an existing AWS Organizations policy.
    /// </summary>
    public class DeletePolicy
    {
        /// <summary>
        /// Initializes the Organizations client object and then uses it to
        /// delete the policy with the specified policyId.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            var policyId = "p-00000000";

            var request = new DeletePolicyRequest
            {
                PolicyId = policyId,
            };

            var response = await client.DeletePolicyAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully deleted Policy: {policyId}.");
            }
            else
            {
                Console.WriteLine($"Could not delete Policy: {policyId}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for .NET da API.

Excluir uma organização.

O exemplo de código a seguir mostra como excluir uma organização do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to delete an existing organization using the AWS
/// Organizations Service.
/// </summary>
public class DeleteOrganization
{
    /// <summary>
    /// Initializes the Organizations client and then calls
    /// DeleteOrganizationAsync to delete the organization.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var response = await client.DeleteOrganizationAsync(new
DeleteOrganizationRequest());

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
        {
            Console.WriteLine("Successfully deleted organization.");
        }
        else
        {
            Console.WriteLine("Could not delete organization.");
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteOrganizationa Referência AWS SDK for .NET da API.

Excluir uma unidade organizacional

O exemplo de código a seguir mostra como excluir uma unidade organizacional do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to delete an existing AWS Organizations organizational unit.
/// </summary>
public class DeleteOrganizationalUnit
{
    /// <summary>
    /// Initializes the Organizations client object and calls
    /// DeleteOrganizationalUnitAsync to delete the organizational unit
    /// with the selected ID.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var orgUnitId = "ou-0000-00000000";

        var request = new DeleteOrganizationalUnitRequest
        {
```

```
                OrganizationalUnitId = orgUnitId,
            };

            var response = await client.DeleteOrganizationalUnitAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully deleted the organizational unit
with ID: {orgUnitId}.");
            }
            else
            {
                Console.WriteLine($"Could not delete the organizational unit with
ID: {orgUnitId}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DeleteOrganizationalUnita Referência AWS SDK for .NET da API.

Desanexar uma política de uma meta

O exemplo de código a seguir mostra como desanexar uma política do Organizations de um destino.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to detach a policy from an AWS Organizations organization,
```

```
    /// organizational unit, or account.
    /// </summary>
    public class DetachPolicy
    {
        /// <summary>
        /// Initializes the Organizations client object and uses it to call
        /// DetachPolicyAsync to detach the policy.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            var policyId = "p-00000000";
            var targetId = "r-0000";

            var request = new DetachPolicyRequest
            {
                PolicyId = policyId,
                TargetId = targetId,
            };

            var response = await client.DetachPolicyAsync(request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully detached policy with Policy Id:
{policyId}.");
            }
            else
            {
                Console.WriteLine("Could not detach the policy.");
            }
        }
    }
```

- Para obter detalhes da API, consulte DetachPolicya Referência AWS SDK for .NET da API.

Listar contas

O exemplo de código a seguir mostra como listar contas de uma organização do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Uses the AWS Organizations service to list the accounts associated
/// with the default account.
/// </summary>
public class ListAccounts
{
    /// <summary>
    /// Creates the Organizations client and then calls its
    /// ListAccountsAsync method.
    /// </summary>
    public static async Task Main()
    {
        // Create the client object using the default account.
        IAmazonOrganizations client = new AmazonOrganizationsClient();

        var request = new ListAccountsRequest
        {
            MaxResults = 5,
        };

        var response = new ListAccountsResponse();
        try
        {
            do
            {
                response = await client.ListAccountsAsync(request);
                response.Accounts.ForEach(a => DisplayAccounts(a));
                if (response.NextToken is not null)
                {
```

```
                        request.NextToken = response.NextToken;
                    }
                }
                while (response.NextToken is not null);
            }
            catch (AWSOrganizationsNotInUseException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Displays information about an Organizations account.
        /// </summary>
        /// <param name="account">An Organizations account for which to display
        /// information on the console.</param>
        private static void DisplayAccounts(Account account)
        {
            string accountInfo = $"{account.Id} {account.Name}\t{account.Status}";

            Console.WriteLine(accountInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListAccountsa Referência AWS SDK for .NET da API.

Adicionar unidades organizacionais

O exemplo de código a seguir mostra como listar unidades organizacionais do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
```

```
    using Amazon.Organizations;
    using Amazon.Organizations.Model;

    /// <summary>
    /// Lists the AWS Organizations organizational units that belong to an
    /// organization.
    /// </summary>
    public class ListOrganizationalUnitsForParent
    {
        /// <summary>
        /// Initializes the Organizations client object and then uses it to
        /// call the ListOrganizationalUnitsForParentAsync method to retrieve
        /// the list of organizational units.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            var parentId = "r-0000";

            var request = new ListOrganizationalUnitsForParentRequest
            {
                ParentId = parentId,
                MaxResults = 5,
            };

            var response = new ListOrganizationalUnitsForParentResponse();
            try
            {
                do
                {
                    response = await
client.ListOrganizationalUnitsForParentAsync(request);
                    response.OrganizationalUnits.ForEach(u =>
DisplayOrganizationalUnit(u));
                    if (response.NextToken is not null)
                    {
                        request.NextToken = response.NextToken;
                    }
                }
                while (response.NextToken is not null);
            }
            catch (Exception ex)
```

```
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Displays information about an Organizations organizational unit.
        /// </summary>
        /// <param name="unit">The OrganizationalUnit for which to display
        /// information.</param>
        public static void DisplayOrganizationalUnit(OrganizationalUnit unit)
        {
            string accountInfo = $"{unit.Id} {unit.Name}\t{unit.Arn}";

            Console.WriteLine(accountInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListOrganizationalUnitsForParenta Referência AWS SDK for .NET da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do Organizations.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Organizations;
using Amazon.Organizations.Model;

/// <summary>
/// Shows how to list the AWS Organizations policies associated with an
```

```
    /// organization.
    /// </summary>
    public class ListPolicies
    {
        /// <summary>
        /// Initializes an Organizations client object, and then calls its
        /// ListPoliciesAsync method.
        /// </summary>
        public static async Task Main()
        {
            // Create the client object using the default account.
            IAmazonOrganizations client = new AmazonOrganizationsClient();

            // The value for the Filter parameter is required and must must be
            // one of the following:
            //     AISERVICES_OPT_OUT_POLICY
            //     BACKUP_POLICY
            //     SERVICE_CONTROL_POLICY
            //     TAG_POLICY
            var request = new ListPoliciesRequest
            {
                Filter = "SERVICE_CONTROL_POLICY",
                MaxResults = 5,
            };

            var response = new ListPoliciesResponse();
            try
            {
                do
                {
                    response = await client.ListPoliciesAsync(request);
                    response.Policies.ForEach(p => DisplayPolicies(p));
                    if (response.NextToken is not null)
                    {
                        request.NextToken = response.NextToken;
                    }
                }
                while (response.NextToken is not null);
            }
            catch (AWSOrganizationsNotInUseException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
```

```
        /// <summary>
        /// Displays information about the Organizations policies associated
        /// with an organization.
        /// </summary>
        /// <param name="policy">An Organizations policy summary to display
        /// information on the console.</param>
        private static void DisplayPolicies(PolicySummary policy)
        {
            string policyInfo = $"{policy.Id} {policy.Name}\t{policy.Description}";

            Console.WriteLine(policyInfo);
        }
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for .NET da API.

Exemplos do Amazon Polly usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Polly.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir um léxico

O exemplo de código a seguir mostra como excluir um léxico do Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

/// <summary>
/// Deletes an existing Amazon Polly lexicon using the AWS SDK for .NET.
/// </summary>
public class DeleteLexicon
{
    public static async Task Main()
    {
        string lexiconName = "SampleLexicon";

        var client = new AmazonPollyClient();

        var success = await DeletePollyLexiconAsync(client, lexiconName);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {lexiconName}.");
        }
        else
        {
            Console.WriteLine($"Could not delete {lexiconName}.");
        }
    }

    /// <summary>
```

```
        /// Deletes the named Amazon Polly lexicon.
        /// </summary>
        /// <param name="client">The initialized Amazon Polly client object.</param>
        /// <param name="lexiconName">The name of the Amazon Polly lexicon to
        /// delete.</param>
        /// <returns>A Boolean value indicating the success of the operation.</
returns>
        public static async Task<bool> DeletePollyLexiconAsync(
            AmazonPollyClient client,
            string lexiconName)
        {
            var deleteLexiconRequest = new DeleteLexiconRequest()
            {
                Name = lexiconName,
            };

            var response = await client.DeleteLexiconAsync(deleteLexiconRequest);

            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
    }
```

- Para obter detalhes da API, consulte DeleteLexicona Referência AWS SDK for .NET da API.

Obter um léxico

O exemplo de código a seguir mostra como obter um léxico do Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Polly;
    using Amazon.Polly.Model;
```

```
    /// <summary>
    /// Retrieves information about a specific Amazon Polly lexicon.
    /// </summary>
    public class GetLexicon
    {
        public static async Task Main(string[] args)
        {
            string lexiconName = "SampleLexicon";

            var client = new AmazonPollyClient();

            await GetPollyLexiconAsync(client, lexiconName);
        }

        public static async Task GetPollyLexiconAsync(AmazonPollyClient client,
string lexiconName)
        {
            var getLexiconRequest = new GetLexiconRequest()
            {
                Name = lexiconName,
            };

            try
            {
                var response = await client.GetLexiconAsync(getLexiconRequest);
                Console.WriteLine($"Lexicon:\n Name: {response.Lexicon.Name}");
                Console.WriteLine($"Content: {response.Lexicon.Content}");
            }
            catch (Exception ex)
            {
                Console.WriteLine("Error: " + ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte GetLexicona Referência AWS SDK for .NET da API.

Obter vozes disponíveis para síntese

O exemplo de código a seguir mostra como obter vozes disponíveis para síntese do Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

public class DescribeVoices
{
    public static async Task Main()
    {
        var client = new AmazonPollyClient();

        var allVoicesRequest = new DescribeVoicesRequest();
        var enUsVoicesRequest = new DescribeVoicesRequest()
        {
            LanguageCode = "en-US",
        };

        try
        {
            string nextToken;
            do
            {
                var allVoicesResponse = await
client.DescribeVoicesAsync(allVoicesRequest);
                nextToken = allVoicesResponse.NextToken;
                allVoicesRequest.NextToken = nextToken;

                Console.WriteLine("\nAll voices: ");
                allVoicesResponse.Voices.ForEach(voice =>
                {
                    DisplayVoiceInfo(voice);
                });
            }
            while (nextToken is not null);
```

```
                do
                {
                    var enUsVoicesResponse = await
client.DescribeVoicesAsync(enUsVoicesRequest);
                    nextToken = enUsVoicesResponse.NextToken;
                    enUsVoicesRequest.NextToken = nextToken;

                    Console.WriteLine("\nen-US voices: ");
                    enUsVoicesResponse.Voices.ForEach(voice =>
                    {
                        DisplayVoiceInfo(voice);
                    });
                }
                while (nextToken is not null);
            }
            catch (Exception ex)
            {
                Console.WriteLine("Exception caught: " + ex.Message);
            }
        }

        public static void DisplayVoiceInfo(Voice voice)
        {
            Console.WriteLine($" Name: {voice.Name}\tGender:
{voice.Gender}\tLanguageName: {voice.LanguageName}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for .NET da API.

Listar léxicos de pronúncia

O exemplo de código a seguir mostra como listar os léxicos de pronúncia do Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

/// <summary>
/// Lists the Amazon Polly lexicons that have been defined. By default,
/// lists the lexicons that are defined in the same AWS Region as the default
/// user. To view Amazon Polly lexicons that are defined in a different AWS
/// Region, supply it as a parameter to the Amazon Polly constructor.
/// </summary>
public class ListLexicons
{
    public static async Task Main()
    {
        var client = new AmazonPollyClient();
        var request = new ListLexiconsRequest();

        try
        {
            Console.WriteLine("All voices: ");

            do
            {
                var response = await client.ListLexiconsAsync(request);
                request.NextToken = response.NextToken;

                response.Lexicons.ForEach(lexicon =>
                {
                    var attributes = lexicon.Attributes;
                    Console.WriteLine($"Name: {lexicon.Name}");
                    Console.WriteLine($"\tAlphabet: {attributes.Alphabet}");
                    Console.WriteLine($"\tLanguageCode:
{attributes.LanguageCode}");
```

```
                        Console.WriteLine($"\tLastModified:
{attributes.LastModified}");
                        Console.WriteLine($"\tLexemesCount:
{attributes.LexemesCount}");
                        Console.WriteLine($"\tLexiconArn: {attributes.LexiconArn}");
                        Console.WriteLine($"\tSize: {attributes.Size}");
                    });
                }
                while (request.NextToken is not null);
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for .NET da API.

Armazenar léxicos de pronúncia

O exemplo de código a seguir mostra como armazenar um léxico de pronúncia do Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

/// <summary>
/// Creates a new Amazon Polly lexicon using the AWS SDK for .NET.
/// </summary>
```

```
    public class PutLexicon
    {
        public static async Task Main()
        {
            string lexiconContent = "<?xml version=\"1.0\" encoding=\"UTF-8\"?>" +
                "<lexicon version=\"1.0\" xmlns=\"http://www.w3.org/2005/01/
pronunciation-lexicon\" xmlns:xsi=\"http://www.w3.org/2001/XMLSchema-instance\" " +
                "xsi:schemaLocation=\"http://www.w3.org/2005/01/pronunciation-
lexicon http://www.w3.org/TR/2007/CR-pronunciation-lexicon-20071212/pls.xsd\" " +
                "alphabet=\"ipa\" xml:lang=\"en-US\">" +
                "<lexeme><grapheme>test1</grapheme><alias>test2</alias></lexeme>" +
                "</lexicon>";
            string lexiconName = "SampleLexicon";

            var client = new AmazonPollyClient();
            var putLexiconRequest = new PutLexiconRequest()
            {
                Name = lexiconName,
                Content = lexiconContent,
            };

            try
            {
                var response = await client.PutLexiconAsync(putLexiconRequest);
                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    Console.WriteLine($"Successfully created Lexicon:
 {lexiconName}.");
                }
                else
                {
                    Console.WriteLine($"Could not create Lexicon: {lexiconName}.");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine("Exception caught: " + ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte PutLexicona Referência AWS SDK for .NET da API.

Sintetizar fala a partir de texto

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   using System;
   using System.IO;
   using System.Threading.Tasks;
   using Amazon.Polly;
   using Amazon.Polly.Model;

   public class SynthesizeSpeech
   {
       public static async Task Main()
       {
           string outputFileName = "speech.mp3";
           string text = "Twas brillig, and the slithy toves did gyre and gimbol in
the wabe";

           var client = new AmazonPollyClient();
           var response = await PollySynthesizeSpeech(client, text);

           WriteSpeechToStream(response.AudioStream, outputFileName);
       }

       /// <summary>
       /// Calls the Amazon Polly SynthesizeSpeechAsync method to convert text
       /// to speech.
       /// </summary>
       /// <param name="client">The Amazon Polly client object used to connect
       /// to the Amazon Polly service.</param>
       /// <param name="text">The text to convert to speech.</param>
       /// <returns>A SynthesizeSpeechResponse object that includes an AudioStream
       /// object with the converted text.</returns>
       private static async Task<SynthesizeSpeechResponse>
PollySynthesizeSpeech(IAmazonPolly client, string text)
```

```
        {
            var synthesizeSpeechRequest = new SynthesizeSpeechRequest()
            {
                OutputFormat = OutputFormat.Mp3,
                VoiceId = VoiceId.Joanna,
                Text = text,
            };

            var synthesizeSpeechResponse =
                await client.SynthesizeSpeechAsync(synthesizeSpeechRequest);

            return synthesizeSpeechResponse;
        }

        /// <summary>
        /// Writes the AudioStream returned from the call to
        /// SynthesizeSpeechAsync to a file in MP3 format.
        /// </summary>
        /// <param name="audioStream">The AudioStream returned from the
        /// call to the SynthesizeSpeechAsync method.</param>
        /// <param name="outputFileName">The full path to the file in which to
        /// save the audio stream.</param>
        private static void WriteSpeechToStream(Stream audioStream, string
outputFileName)
        {
            var outputStream = new FileStream(
                outputFileName,
                FileMode.Create,
                FileAccess.Write);
            byte[] buffer = new byte[2 * 1024];
            int readBytes;

            while ((readBytes = audioStream.Read(buffer, 0, 2 * 1024)) > 0)
            {
                outputStream.Write(buffer, 0, readBytes);
            }

            // Flushes the buffer to avoid losing the last second or so of
            // the synthesized text.
            outputStream.Flush();
            Console.WriteLine($"Saved {outputFileName} to disk.");
        }
    }
```

Sintetize fala a partir de texto usando marcas de fala com o Amazon Polly usando um SDK da AWS.

```
using System;
using System.Collections.Generic;
using System.IO;
using System.Threading.Tasks;
using Amazon.Polly;
using Amazon.Polly.Model;

public class SynthesizeSpeechMarks
{
    public static async Task Main()
    {
        var client = new AmazonPollyClient();
        string outputFileName = "speechMarks.json";

        var synthesizeSpeechRequest = new SynthesizeSpeechRequest()
        {
            OutputFormat = OutputFormat.Json,
            SpeechMarkTypes = new List<string>
            {
                SpeechMarkType.Viseme,
                SpeechMarkType.Word,
            },
            VoiceId = VoiceId.Joanna,
            Text = "This is a sample text to be synthesized.",
        };

        try
        {
            using (var outputStream = new FileStream(outputFileName,
FileMode.Create, FileAccess.Write))
            {
                var synthesizeSpeechResponse = await
client.SynthesizeSpeechAsync(synthesizeSpeechRequest);
                var buffer = new byte[2 * 1024];
                int readBytes;

                var inputStream = synthesizeSpeechResponse.AudioStream;
                while ((readBytes = inputStream.Read(buffer, 0, 2 * 1024)) > 0)
```

```
                    {
                        outputStream.Write(buffer, 0, readBytes);
                    }
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte SynthesizeSpeech a Referência AWS SDK for .NET da API.

Exemplos do Amazon RDS usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon RDS

O exemplo de código a seguir mostra como começar a usar o Amazon RDS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.RDS;
using Amazon.RDS.Model;

namespace RDSActions;

public static class HelloRds
{
    static async Task Main(string[] args)
    {
        var rdsClient = new AmazonRDSClient();

        Console.WriteLine($"Hello Amazon RDS! Following are some of your DB
 instances:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first twenty DB instances.
        var response = await rdsClient.DescribeDBInstancesAsync(
            new DescribeDBInstancesRequest()
            {
                MaxRecords = 20 // Must be between 20 and 100.
            });

        foreach (var instance in response.DBInstances)
        {
            Console.WriteLine($"\tDB name: {instance.DBName}");
            Console.WriteLine($"\tArn: {instance.DBInstanceArn}");
            Console.WriteLine($"\tIdentifier: {instance.DBInstanceIdentifier}");
            Console.WriteLine();
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

O exemplo de código a seguir mostra como criar uma instância do Amazon RDS DB e aguardar até que se torne disponível.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   /// <summary>
   /// Create an RDS DB instance with a particular set of properties. Use the
action DescribeDBInstancesAsync
   /// to determine when the DB instance is ready to use.
   /// </summary>
   /// <param name="dbName">Name for the DB instance.</param>
   /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
   /// <param name="parameterGroupName">DB parameter group to associate with the
instance.</param>
   /// <param name="dbEngine">The engine for the DB instance.</param>
   /// <param name="dbEngineVersion">Version for the DB instance.</param>
   /// <param name="instanceClass">Class for the DB instance.</param>
   /// <param name="allocatedStorage">The amount of storage in gibibytes (GiB) to
allocate to the DB instance.</param>
```

```
    /// <param name="adminName">Admin user name.</param>
    /// <param name="adminPassword">Admin user password.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstance(string dbName, string
dbInstanceIdentifier,
        string parameterGroupName, string dbEngine, string dbEngineVersion,
        string instanceClass, int allocatedStorage, string adminName, string
adminPassword)
    {
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBName = dbName,
                DBInstanceIdentifier = dbInstanceIdentifier,
                DBParameterGroupName = parameterGroupName,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass,
                AllocatedStorage = allocatedStorage,
                MasterUsername = adminName,
                MasterUserPassword = adminPassword
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for .NET.

Criar um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a new DB parameter group. Use the action
DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="family">Family of the DB parameter group.</param>
    /// <param name="description">Description of the DB parameter group.</param>
    /// <returns>The new DB parameter group.</returns>
    public async Task<DBParameterGroup> CreateDBParameterGroup(
        string name, string family, string description)
    {
        var response = await _amazonRDS.CreateDBParameterGroupAsync(
            new CreateDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                DBParameterGroupFamily = family,
                Description = description
            });
        return response.DBParameterGroup;
    }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for .NET da API.

Criar um snapshot de uma instância de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de uma instância do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a snapshot of a DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBSnapshot> CreateDBSnapshot(string dbInstanceIdentifier,
string snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBSnapshotAsync(
            new CreateDBSnapshotRequest()
            {
                DBSnapshotIdentifier = snapshotIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        return response.DBSnapshot;
    }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for .NET.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
```

```
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstance(string dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for .NET.

Excluir um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a DB parameter group. The group cannot be a default DB parameter
group
    /// or be associated with any DB instances.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDBParameterGroup(string name)
```

```
    {
        var response = await _amazonRDS.DeleteDBParameterGroupAsync(
            new DeleteDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for .NET Referência da API.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Returns a list of DB instances.
    /// </summary>
    /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
    /// <returns>List of DB instances.</returns>
    public async Task<List<DBInstance>> DescribeDBInstances(string
dbInstanceIdentifier = null)
    {
        var results = new List<DBInstance>();
        var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
            new DescribeDBInstancesRequest
            {
                DBInstanceIdentifier = dbInstanceIdentifier
```

```
            });
        // Get the entire list using the paginator.
        await foreach (var instances in instancesPaginator.DBInstances)
        {
            results.Add(instances);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for .NET.

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get descriptions of DB parameter groups.
    /// </summary>
    /// <param name="name">Optional name of the DB parameter group to describe.</
param>
    /// <returns>The list of DB parameter group descriptions.</returns>
    public async Task<List<DBParameterGroup>> DescribeDBParameterGroups(string name
 = null)
    {
        var response = await _amazonRDS.DescribeDBParameterGroupsAsync(
            new DescribeDBParameterGroupsRequest()
            {
                DBParameterGroupName = name
            });
        return response.DBParameterGroups;
```

```
    }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for .NET da API.

Descrever as versões de mecanismo de banco de dados

O exemplo de código a seguir mostra como descrever as versões de mecanismo de banco de dados do Amazon RDS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="dbParameterGroupFamily">Optional parameter group family name.</
param>
    /// <returns>List of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>> DescribeDBEngineVersions(string engine,
        string dbParameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = dbParameterGroupFamily
            });
        return response.DBEngineVersions;
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for .NET da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever opções para instâncias do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Get a list of orderable DB instance options for a specific
   /// engine and engine version.
   /// </summary>
   /// <param name="engine">Name of the engine.</param>
   /// <param name="engineVersion">Version of the engine.</param>
   /// <returns>List of OrderableDBInstanceOptions.</returns>
   public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptions(string engine, string engineVersion)
   {
       // Use a paginator to get a list of DB instance options.
       var results = new List<OrderableDBInstanceOption>();
       var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
           new DescribeOrderableDBInstanceOptionsRequest()
           {
               Engine = engine,
               EngineVersion = engineVersion,
           });
       // Get the entire list using the paginator.
       await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
       {
           results.Add(instanceOptions);
       }
       return results;
```

```
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for .NET API.

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get a list of DB parameters from a specific parameter group.
    /// </summary>
    /// <param name="dbParameterGroupName">Name of a specific DB parameter group.</
param>
    /// <param name="source">Optional source for selecting parameters.</param>
    /// <returns>List of parameter values.</returns>
    public async Task<List<Parameter>> DescribeDBParameters(string
 dbParameterGroupName, string source = null)
    {
        var results = new List<Parameter>();
        var paginateParameters = _amazonRDS.Paginators.DescribeDBParameters(
            new DescribeDBParametersRequest()
            {
                DBParameterGroupName = dbParameterGroupName,
                Source = source
            });
        // Get the entire list using the paginator.
        await foreach (var parameters in paginateParameters.Parameters)
        {
```

```
            results.Add(parameters);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for .NET.

Descrever os snapshots das instâncias de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de instâncias de banco de dados do Amazon RDS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Return a list of DB snapshots for a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBSnapshot>> DescribeDBSnapshots(string
dbInstanceIdentifier)
    {
        var results = new List<DBSnapshot>();
        var snapshotsPaginator = _amazonRDS.Paginators.DescribeDBSnapshots(
            new DescribeDBSnapshotsRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        // Get the entire list using the paginator.
        await foreach (var snapshots in snapshotsPaginator.DBSnapshots)
```

```
        {
            results.Add(snapshots);
        }
        return results;
    }
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for .NET.

Atualizar os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como atualizar os parâmetros em um grupo de parâmetros do Amazon RDS DB.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update a DB parameter group. Use the action DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="parameters">List of parameters. Maximum of 20 per request.</
param>
    /// <returns>The updated DB parameter group name.</returns>
    public async Task<string> ModifyDBParameterGroup(
        string name, List<Parameter> parameters)
    {
        var response = await _amazonRDS.ModifyDBParameterGroupAsync(
            new ModifyDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                Parameters = parameters,
```

```
            });
        return response.DBParameterGroupName;
    }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for .NET da API.

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Scenario for RDS DB instance example.
/// </summary>
public class RDSInstanceScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.
```

```
   This .NET example performs the following tasks:
   1.  Returns a list of the available DB engine families using the
DescribeDBEngineVersionsAsync method.
   2.  Selects an engine family and creates a custom DB parameter group using the
CreateDBParameterGroupAsync method.
   3.  Gets the parameter groups using the DescribeDBParameterGroupsAsync method.
   4.  Gets parameters in the group using the DescribeDBParameters method.
   5.  Parses and displays parameters in the group.
   6.  Modifies both the auto_increment_offset and auto_increment_increment
parameters
       using the ModifyDBParameterGroupAsync method.
   7.  Gets and displays the updated parameters using the DescribeDBParameters
method with a source of "user".
   8.  Gets a list of allowed engine versions using the
DescribeDBEngineVersionsAsync method.
   9.  Displays and selects from a list of micro instance classes available for the
selected engine and version.
   10. Creates an RDS DB instance that contains a MySql database and uses the
parameter group
       using the CreateDBInstanceAsync method.
   11. Waits for DB instance to be ready using the DescribeDBInstancesAsync method.
   12. Prints out the connection endpoint string for the new DB instance.
   13. Creates a snapshot of the DB instance using the CreateDBSnapshotAsync
method.
   14. Waits for DB snapshot to be ready using the DescribeDBSnapshots method.
   15. Deletes the DB instance using the DeleteDBInstanceAsync method.
   16. Waits for DB instance to be deleted using the DescribeDbInstances method.
   17. Deletes the parameter group using the DeleteDBParameterGroupAsync.
   */

   private static readonly string sepBar = new('-', 80);
   private static RDSWrapper rdsWrapper = null!;
   private static ILogger logger = null!;
   private static readonly string engine = "mysql";
   static async Task Main(string[] args)
   {
       // Set up dependency injection for the Amazon RDS service.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
```

```
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRDS>()
                    .AddTransient<RDSWrapper>()
            )
            .Build();

        logger = LoggerFactory.Create(builder =>
        {
            builder.AddConsole();
        }).CreateLogger<RDSInstanceScenario>();

        rdsWrapper = host.Services.GetRequiredService<RDSWrapper>();

        Console.WriteLine(sepBar);
        Console.WriteLine(
            "Welcome to the Amazon Relational Database Service (Amazon RDS) DB
instance scenario example.");
        Console.WriteLine(sepBar);

        try
        {
            var parameterGroupFamily = await ChooseParameterGroupFamily();

            var parameterGroup = await CreateDbParameterGroup(parameterGroupFamily);

            var parameters = await
DescribeParametersInGroup(parameterGroup.DBParameterGroupName,
                new List<string> { "auto_increment_offset",
"auto_increment_increment" });

            await ModifyParameters(parameterGroup.DBParameterGroupName, parameters);

            await DescribeUserSourceParameters(parameterGroup.DBParameterGroupName);

            var engineVersionChoice = await
ChooseDbEngineVersion(parameterGroupFamily);

            var instanceChoice = await ChooseDbInstanceClass(engine,
engineVersionChoice.EngineVersion);

            var newInstanceIdentifier = "Example-Instance-" + DateTime.Now.Ticks;

            var newInstance = await CreateRdsNewInstance(parameterGroup, engine,
engineVersionChoice.EngineVersion,
```

```
                instanceChoice.DBInstanceClass, newInstanceIdentifier);
            if (newInstance != null)
            {
                DisplayConnectionString(newInstance);

                await CreateSnapshot(newInstance);

                await DeleteRdsInstance(newInstance);
            }

            await DeleteParameterGroup(parameterGroup);

            Console.WriteLine("Scenario complete.");
            Console.WriteLine(sepBar);
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// Choose the RDS DB parameter group family from a list of available options.
    /// </summary>
    /// <returns>The selected parameter group family.</returns>
    public static async Task<string> ChooseParameterGroupFamily()
    {
        Console.WriteLine(sepBar);
        // 1. Get a list of available engines.
        var engines = await rdsWrapper.DescribeDBEngineVersions(engine);

        Console.WriteLine("1. The following is a list of available DB parameter
group families:");
        int i = 1;
        var parameterGroupFamilies = engines.GroupBy(e =>
e.DBParameterGroupFamily).ToList();
        foreach (var parameterGroupFamily in parameterGroupFamilies)
        {
            // List the available parameter group families.
            Console.WriteLine(
                $"\t{i}. Family: {parameterGroupFamily.Key}");
            i++;
        }
```

```
        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > parameterGroupFamilies.Count)
        {
            Console.WriteLine("Select an available DB parameter group family by
entering a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        var parameterGroupFamilyChoice = parameterGroupFamilies[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return parameterGroupFamilyChoice.Key;
    }

    /// <summary>
    /// Create and get information on a DB parameter group.
    /// </summary>
    /// <param name="dbParameterGroupFamily">The DBParameterGroupFamily for the new
DB parameter group.</param>
    /// <returns>The new DBParameterGroup.</returns>
    public static async Task<DBParameterGroup> CreateDbParameterGroup(string
dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"2. Create new DB parameter group with family
{dbParameterGroupFamily}:");

        var parameterGroup = await rdsWrapper.CreateDBParameterGroup(
            "ExampleParameterGroup-" + DateTime.Now.Ticks,
            dbParameterGroupFamily, "New example parameter group");

        var groupInfo =
            await rdsWrapper.DescribeDBParameterGroups(parameterGroup
                .DBParameterGroupName);

        Console.WriteLine(
            $"3. New DB parameter group: \n\t{groupInfo[0].Description}, \n\tARN
{groupInfo[0].DBParameterGroupArn}");
        Console.WriteLine(sepBar);
        return parameterGroup;
    }

    /// <summary>
    /// Get and describe parameters from a DBParameterGroup.
    /// </summary>
```

```
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameterNames">Optional specific names of parameters to
describe.</param>
    /// <returns>The list of requested parameters.</returns>
    public static async Task<List<Parameter>> DescribeParametersInGroup(string
parameterGroupName, List<string>? parameterNames = null)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("4. Get some parameters from the group.");
        Console.WriteLine(sepBar);

        var parameters =
            await rdsWrapper.DescribeDBParameters(parameterGroupName);

        var matchingParameters =
            parameters.Where(p => parameterNames == null ||
parameterNames.Contains(p.ParameterName)).ToList();

        Console.WriteLine("5. Parameter information:");
        matchingParameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));

        Console.WriteLine(sepBar);

        return matchingParameters;
    }

    /// <summary>
    /// Modify a parameter from a DBParameterGroup.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <param name="parameters">The parameters to modify.</param>
    /// <returns>Async task.</returns>
    public static async Task ModifyParameters(string parameterGroupName,
List<Parameter> parameters)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("6. Modify some parameters in the group.");

        foreach (var p in parameters)
```

```
        {
            if (p.IsModifiable && p.DataType == "integer")
            {
                int newValue = 0;
                while (newValue == 0)
                {
                    Console.WriteLine(
                        $"Enter a new value for {p.ParameterName} from the allowed
values {p.AllowedValues} ");

                    var choice = Console.ReadLine();
                    Int32.TryParse(choice, out newValue);
                }

                p.ParameterValue = newValue.ToString();
            }
        }

        await rdsWrapper.ModifyDBParameterGroup(parameterGroupName, parameters);

        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Describe the user source parameters in the group.
    /// </summary>
    /// <param name="parameterGroupName">Name of the DBParameterGroup.</param>
    /// <returns>Async task.</returns>
    public static async Task DescribeUserSourceParameters(string parameterGroupName)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine("7. Describe user source parameters in the group.");

        var parameters =
            await rdsWrapper.DescribeDBParameters(parameterGroupName, "user");


        parameters.ForEach(p =>
            Console.WriteLine(
                $"\n\tParameter: {p.ParameterName}." +
                $"\n\tDescription: {p.Description}." +
                $"\n\tAllowed Values: {p.AllowedValues}." +
                $"\n\tValue: {p.ParameterValue}."));
```

```
        Console.WriteLine(sepBar);
    }


    /// <summary>
    /// Choose a DB engine version.
    /// </summary>
    /// <param name="dbParameterGroupFamily">DB parameter group family for engine
choice.</param>
    /// <returns>The selected engine version.</returns>
    public static async Task<DBEngineVersion> ChooseDbEngineVersion(string
dbParameterGroupFamily)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed engines.
        var allowedEngines =
            await rdsWrapper.DescribeDBEngineVersions(engine,
dbParameterGroupFamily);

        Console.WriteLine($"Available DB engine versions for parameter group family
{dbParameterGroupFamily}:");
        int i = 1;
        foreach (var version in allowedEngines)
        {
            Console.WriteLine(
                $"\t{i}. Engine: {version.Engine} Version
{version.EngineVersion}.");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedEngines.Count)
        {
            Console.WriteLine("8. Select an available DB engine version by entering
a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var engineChoice = allowedEngines[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return engineChoice;
    }
```

```
    /// <summary>
    /// Choose a DB instance class for a particular engine and engine version.
    /// </summary>
    /// <param name="engine">DB engine for DB instance choice.</param>
    /// <param name="engineVersion">DB engine version for DB instance choice.</
param>
    /// <returns>The selected orderable DB instance option.</returns>
    public static async Task<OrderableDBInstanceOption> ChooseDbInstanceClass(string
 engine, string engineVersion)
    {
        Console.WriteLine(sepBar);
        // Get a list of allowed DB instance classes.
        var allowedInstances =
            await rdsWrapper.DescribeOrderableDBInstanceOptions(engine,
 engineVersion);

        Console.WriteLine($"8. Available micro DB instance classes for engine
 {engine} and version {engineVersion}:");
        int i = 1;

        // Filter to micro instances for this example.
        allowedInstances = allowedInstances
            .Where(i => i.DBInstanceClass.Contains("micro")).ToList();

        foreach (var instance in allowedInstances)
        {
            Console.WriteLine(
                $"\t{i}. Instance class: {instance.DBInstanceClass} (storage type
 {instance.StorageType})");
            i++;
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > allowedInstances.Count)
        {
            Console.WriteLine("9. Select an available DB instance class by entering
 a number from the list above:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        var instanceChoice = allowedInstances[choiceNumber - 1];
        Console.WriteLine(sepBar);
        return instanceChoice;
```

```
    }

    /// <summary>
    /// Create a new RDS DB instance.
    /// </summary>
    /// <param name="parameterGroup">Parameter group to use for the DB instance.</
param>
    /// <param name="engineName">Engine to use for the DB instance.</param>
    /// <param name="engineVersion">Engine version to use for the DB instance.</
param>
    /// <param name="instanceClass">Instance class to use for the DB instance.</
param>
    /// <param name="instanceIdentifier">Instance identifier to use for the DB
 instance.</param>
    /// <returns>The new DB instance.</returns>
    public static async Task<DBInstance?> CreateRdsNewInstance(DBParameterGroup
 parameterGroup,
        string engineName, string engineVersion, string instanceClass, string
 instanceIdentifier)
    {
        Console.WriteLine(sepBar);
        Console.WriteLine($"10. Create a new DB instance with identifier
 {instanceIdentifier}.");
        bool isInstanceReady = false;
        DBInstance newInstance;
        var instances = await rdsWrapper.DescribeDBInstances();
        isInstanceReady = instances.FirstOrDefault(i =>
            i.DBInstanceIdentifier == instanceIdentifier)?.DBInstanceStatus ==
 "available";

        if (isInstanceReady)
        {
            Console.WriteLine("Instance already created.");
            newInstance = instances.First(i => i.DBInstanceIdentifier ==
 instanceIdentifier);
        }
        else
        {
            Console.WriteLine("Please enter an admin user name:");
            var username = Console.ReadLine();

            Console.WriteLine("Please enter an admin password:");
            var password = Console.ReadLine();
```

```
            newInstance = await rdsWrapper.CreateDBInstance(
                "ExampleInstance",
                instanceIdentifier,
                parameterGroup.DBParameterGroupName,
                engineName,
                engineVersion,
                instanceClass,
                20,
                username,
                password
            );

            // 11. Wait for the DB instance to be ready.

            Console.WriteLine("11. Waiting for DB instance to be ready...");
            while (!isInstanceReady)
            {
                instances = await
 rdsWrapper.DescribeDBInstances(instanceIdentifier);
                isInstanceReady = instances.FirstOrDefault()?.DBInstanceStatus ==
 "available";
                newInstance = instances.First();
                Thread.Sleep(30000);
            }
        }

        Console.WriteLine(sepBar);
        return newInstance;
    }

    /// <summary>
    /// Display a connection string for an RDS DB instance.
    /// </summary>
    /// <param name="instance">The DB instance to use to get a connection string.</
param>
    public static void DisplayConnectionString(DBInstance instance)
    {
        Console.WriteLine(sepBar);
        // Display the connection string.
        Console.WriteLine("12. New DB instance connection string: ");
        Console.WriteLine(
            $"\n{engine} -h {instance.Endpoint.Address} -P {instance.Endpoint.Port}
 "
            + $"-u {instance.MasterUsername} -p [YOUR PASSWORD]\n");
```

```
        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Create a snapshot from an RDS DB instance.
    /// </summary>
    /// <param name="instance">DB instance to use when creating a snapshot.</param>
    /// <returns>The snapshot object.</returns>
    public static async Task<DBSnapshot> CreateSnapshot(DBInstance instance)
    {
        Console.WriteLine(sepBar);
        // Create a snapshot.
        Console.WriteLine($"13. Creating snapshot from DB instance
{instance.DBInstanceIdentifier}.");
        var snapshot = await
rdsWrapper.CreateDBSnapshot(instance.DBInstanceIdentifier, "ExampleSnapshot-" +
DateTime.Now.Ticks);

        // Wait for the snapshot to be available
        bool isSnapshotReady = false;

        Console.WriteLine($"14. Waiting for snapshot to be ready...");
        while (!isSnapshotReady)
        {
            var snapshots = await
rdsWrapper.DescribeDBSnapshots(instance.DBInstanceIdentifier);
            isSnapshotReady = snapshots.FirstOrDefault()?.Status == "available";
            snapshot = snapshots.First();
            Thread.Sleep(30000);
        }

        Console.WriteLine(
            $"Snapshot {snapshot.DBSnapshotIdentifier} status is
{snapshot.Status}.");
        Console.WriteLine(sepBar);
        return snapshot;
    }

    /// <summary>
    /// Delete an RDS DB instance.
    /// </summary>
    /// <param name="instance">The DB instance to delete.</param>
    /// <returns>Async task.</returns>
```

```
    public static async Task DeleteRdsInstance(DBInstance newInstance)
    {
        Console.WriteLine(sepBar);
        // Delete the DB instance.
        Console.WriteLine($"15. Delete the DB instance
{newInstance.DBInstanceIdentifier}.");
        await rdsWrapper.DeleteDBInstance(newInstance.DBInstanceIdentifier);

        // Wait for the DB instance to delete.
        Console.WriteLine($"16. Waiting for the DB instance to delete...");
        bool isInstanceDeleted = false;

        while (!isInstanceDeleted)
        {
            var instance = await rdsWrapper.DescribeDBInstances();
            isInstanceDeleted = instance.All(i => i.DBInstanceIdentifier !=
newInstance.DBInstanceIdentifier);
            Thread.Sleep(30000);
        }

        Console.WriteLine("DB instance deleted.");
        Console.WriteLine(sepBar);
    }

    /// <summary>
    /// Delete a DB parameter group.
    /// </summary>
    /// <param name="parameterGroup">The parameter group to delete.</param>
    /// <returns>Async task.</returns>
    public static async Task DeleteParameterGroup(DBParameterGroup parameterGroup)
    {
        Console.WriteLine(sepBar);
        // Delete the parameter group.
        Console.WriteLine($"17. Delete the DB parameter group
{parameterGroup.DBParameterGroupName}.");
        await
rdsWrapper.DeleteDBParameterGroup(parameterGroup.DBParameterGroupName);

        Console.WriteLine(sepBar);
    }
```

Os métodos de wrapper usados pelo cenário para as ações de instância de banco de dados.

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with DB
 instance operations.
/// </summary>
public partial class RDSWrapper
{
    private readonly IAmazonRDS _amazonRDS;
    public RDSWrapper(IAmazonRDS amazonRDS)
    {
        _amazonRDS = amazonRDS;
    }


    /// <summary>
    /// Get a list of DB engine versions for a particular DB engine.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="dbParameterGroupFamily">Optional parameter group family name.</
param>
    /// <returns>List of DBEngineVersions.</returns>
    public async Task<List<DBEngineVersion>> DescribeDBEngineVersions(string engine,
        string dbParameterGroupFamily = null)
    {
        var response = await _amazonRDS.DescribeDBEngineVersionsAsync(
            new DescribeDBEngineVersionsRequest()
            {
                Engine = engine,
                DBParameterGroupFamily = dbParameterGroupFamily
            });
        return response.DBEngineVersions;
    }



    /// <summary>
    /// Get a list of orderable DB instance options for a specific
    /// engine and engine version.
    /// </summary>
    /// <param name="engine">Name of the engine.</param>
    /// <param name="engineVersion">Version of the engine.</param>
    /// <returns>List of OrderableDBInstanceOptions.</returns>
```

```
   public async Task<List<OrderableDBInstanceOption>>
DescribeOrderableDBInstanceOptions(string engine, string engineVersion)
   {
       // Use a paginator to get a list of DB instance options.
       var results = new List<OrderableDBInstanceOption>();
       var paginateInstanceOptions =
_amazonRDS.Paginators.DescribeOrderableDBInstanceOptions(
           new DescribeOrderableDBInstanceOptionsRequest()
           {
               Engine = engine,
               EngineVersion = engineVersion,
           });
       // Get the entire list using the paginator.
       await foreach (var instanceOptions in
paginateInstanceOptions.OrderableDBInstanceOptions)
       {
           results.Add(instanceOptions);
       }
       return results;
   }



   /// <summary>
   /// Returns a list of DB instances.
   /// </summary>
   /// <param name="dbInstanceIdentifier">Optional name of a specific DB
instance.</param>
   /// <returns>List of DB instances.</returns>
   public async Task<List<DBInstance>> DescribeDBInstances(string
dbInstanceIdentifier = null)
   {
       var results = new List<DBInstance>();
       var instancesPaginator = _amazonRDS.Paginators.DescribeDBInstances(
           new DescribeDBInstancesRequest
           {
               DBInstanceIdentifier = dbInstanceIdentifier
           });
       // Get the entire list using the paginator.
       await foreach (var instances in instancesPaginator.DBInstances)
       {
           results.Add(instances);
       }
       return results;
```

```
    }



    /// <summary>
    /// Create an RDS DB instance with a particular set of properties. Use the
action DescribeDBInstancesAsync
    /// to determine when the DB instance is ready to use.
    /// </summary>
    /// <param name="dbName">Name for the DB instance.</param>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="parameterGroupName">DB parameter group to associate with the
instance.</param>
    /// <param name="dbEngine">The engine for the DB instance.</param>
    /// <param name="dbEngineVersion">Version for the DB instance.</param>
    /// <param name="instanceClass">Class for the DB instance.</param>
    /// <param name="allocatedStorage">The amount of storage in gibibytes (GiB) to
allocate to the DB instance.</param>
    /// <param name="adminName">Admin user name.</param>
    /// <param name="adminPassword">Admin user password.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> CreateDBInstance(string dbName, string
dbInstanceIdentifier,
        string parameterGroupName, string dbEngine, string dbEngineVersion,
        string instanceClass, int allocatedStorage, string adminName, string
adminPassword)
    {
        var response = await _amazonRDS.CreateDBInstanceAsync(
            new CreateDBInstanceRequest()
            {
                DBName = dbName,
                DBInstanceIdentifier = dbInstanceIdentifier,
                DBParameterGroupName = parameterGroupName,
                Engine = dbEngine,
                EngineVersion = dbEngineVersion,
                DBInstanceClass = instanceClass,
                AllocatedStorage = allocatedStorage,
                MasterUsername = adminName,
                MasterUserPassword = adminPassword
            });

        return response.DBInstance;
    }
```

```
    /// <summary>
    /// Delete a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>DB instance object.</returns>
    public async Task<DBInstance> DeleteDBInstance(string dbInstanceIdentifier)
    {
        var response = await _amazonRDS.DeleteDBInstanceAsync(
            new DeleteDBInstanceRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier,
                SkipFinalSnapshot = true,
                DeleteAutomatedBackups = true
            });

        return response.DBInstance;
    }
```

Os métodos de wrapper usados pelo cenário para o grupos de parâmetros de banco de dados

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with
 parameter groups.
/// </summary>
public partial class RDSWrapper
{

    /// <summary>
    /// Get descriptions of DB parameter groups.
    /// </summary>
    /// <param name="name">Optional name of the DB parameter group to describe.</
param>
    /// <returns>The list of DB parameter group descriptions.</returns>
    public async Task<List<DBParameterGroup>> DescribeDBParameterGroups(string name
 = null)
    {
        var response = await _amazonRDS.DescribeDBParameterGroupsAsync(
            new DescribeDBParameterGroupsRequest()
```

```
            {
                DBParameterGroupName = name
            });
        return response.DBParameterGroups;
    }



    /// <summary>
    /// Create a new DB parameter group. Use the action
 DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="family">Family of the DB parameter group.</param>
    /// <param name="description">Description of the DB parameter group.</param>
    /// <returns>The new DB parameter group.</returns>
    public async Task<DBParameterGroup> CreateDBParameterGroup(
        string name, string family, string description)
    {
        var response = await _amazonRDS.CreateDBParameterGroupAsync(
            new CreateDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                DBParameterGroupFamily = family,
                Description = description
            });
        return response.DBParameterGroup;
    }



    /// <summary>
    /// Update a DB parameter group. Use the action DescribeDBParameterGroupsAsync
    /// to determine when the DB parameter group is ready to use.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <param name="parameters">List of parameters. Maximum of 20 per request.</
param>
    /// <returns>The updated DB parameter group name.</returns>
    public async Task<string> ModifyDBParameterGroup(
        string name, List<Parameter> parameters)
    {
        var response = await _amazonRDS.ModifyDBParameterGroupAsync(
```

```
            new ModifyDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
                Parameters = parameters,
            });
        return response.DBParameterGroupName;
    }



    /// <summary>
    /// Delete a DB parameter group. The group cannot be a default DB parameter
 group
    /// or be associated with any DB instances.
    /// </summary>
    /// <param name="name">Name of the DB parameter group.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteDBParameterGroup(string name)
    {
        var response = await _amazonRDS.DeleteDBParameterGroupAsync(
            new DeleteDBParameterGroupRequest()
            {
                DBParameterGroupName = name,
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }



    /// <summary>
    /// Get a list of DB parameters from a specific parameter group.
    /// </summary>
    /// <param name="dbParameterGroupName">Name of a specific DB parameter group.</
param>
    /// <param name="source">Optional source for selecting parameters.</param>
    /// <returns>List of parameter values.</returns>
    public async Task<List<Parameter>> DescribeDBParameters(string
 dbParameterGroupName, string source = null)
    {
        var results = new List<Parameter>();
        var paginateParameters = _amazonRDS.Paginators.DescribeDBParameters(
            new DescribeDBParametersRequest()
            {
                DBParameterGroupName = dbParameterGroupName,
```

```
                Source = source
            });
        // Get the entire list using the paginator.
        await foreach (var parameters in paginateParameters.Parameters)
        {
            results.Add(parameters);
        }
        return results;
    }
```

Os métodos de wrapper usados pelo cenário para as ações de snapshot de banco de dados.

```
/// <summary>
/// Wrapper methods to use Amazon Relational Database Service (Amazon RDS) with
 snapshots.
/// </summary>
public partial class RDSWrapper
{

    /// <summary>
    /// Create a snapshot of a DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <param name="snapshotIdentifier">Identifier for the snapshot.</param>
    /// <returns>DB snapshot object.</returns>
    public async Task<DBSnapshot> CreateDBSnapshot(string dbInstanceIdentifier,
 string snapshotIdentifier)
    {
        var response = await _amazonRDS.CreateDBSnapshotAsync(
            new CreateDBSnapshotRequest()
            {
                DBSnapshotIdentifier = snapshotIdentifier,
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        return response.DBSnapshot;
    }
```

```
    /// <summary>
    /// Return a list of DB snapshots for a particular DB instance.
    /// </summary>
    /// <param name="dbInstanceIdentifier">DB instance identifier.</param>
    /// <returns>List of DB snapshots.</returns>
    public async Task<List<DBSnapshot>> DescribeDBSnapshots(string
 dbInstanceIdentifier)
    {
        var results = new List<DBSnapshot>();
        var snapshotsPaginator = _amazonRDS.Paginators.DescribeDBSnapshots(
            new DescribeDBSnapshotsRequest()
            {
                DBInstanceIdentifier = dbInstanceIdentifier
            });

        // Get the entire list using the paginator.
        await foreach (var snapshots in snapshotsPaginator.DBSnapshots)
        {
            results.Add(snapshots);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions

- Modificar banco de dados ParameterGroup

Exemplos do Amazon Rekognition usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for .NET com Amazon Rekognition.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Comparar faces em uma imagem com uma imagem de referência

O exemplo de código a seguir mostra como comparar faces em uma imagem com uma imagem de referência usando o Amazon Rekognition.

Para obter mais informações, consulte Comparar faces em imagens.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
```

```
   using Amazon.Rekognition;
   using Amazon.Rekognition.Model;

   /// <summary>
   /// Uses the Amazon Rekognition Service to compare faces in two images.
   /// </summary>
   public class CompareFaces
   {
       public static async Task Main()
       {
           float similarityThreshold = 70F;
           string sourceImage = "source.jpg";
           string targetImage = "target.jpg";

           var rekognitionClient = new AmazonRekognitionClient();

           Amazon.Rekognition.Model.Image imageSource = new
Amazon.Rekognition.Model.Image();

           try
           {
               using FileStream fs = new FileStream(sourceImage, FileMode.Open,
FileAccess.Read);
               byte[] data = new byte[fs.Length];
               fs.Read(data, 0, (int)fs.Length);
               imageSource.Bytes = new MemoryStream(data);
           }
           catch (Exception)
           {
               Console.WriteLine($"Failed to load source image: {sourceImage}");
               return;
           }

           Amazon.Rekognition.Model.Image imageTarget = new
Amazon.Rekognition.Model.Image();

           try
           {
               using FileStream fs = new FileStream(targetImage, FileMode.Open,
FileAccess.Read);
               byte[] data = new byte[fs.Length];
               data = new byte[fs.Length];
               fs.Read(data, 0, (int)fs.Length);
               imageTarget.Bytes = new MemoryStream(data);
```

```
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Failed to load target image: {targetImage}");
                Console.WriteLine(ex.Message);
                return;
            }

            var compareFacesRequest = new CompareFacesRequest
            {
                SourceImage = imageSource,
                TargetImage = imageTarget,
                SimilarityThreshold = similarityThreshold,
            };

            // Call operation
            var compareFacesResponse = await
rekognitionClient.CompareFacesAsync(compareFacesRequest);

            // Display results
            compareFacesResponse.FaceMatches.ForEach(match =>
            {
                ComparedFace face = match.Face;
                BoundingBox position = face.BoundingBox;
                Console.WriteLine($"Face at {position.Left} {position.Top} matches
with {match.Similarity}% confidence.");
            });

            Console.WriteLine($"Found {compareFacesResponse.UnmatchedFaces.Count}
face(s) that did not match.");
        }
    }
```

- Para obter detalhes da API, consulte CompareFacesa Referência AWS SDK for .NET da API.

Criar uma coleção

O exemplo de código a seguir mostra como criar uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Criar uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses Amazon Rekognition to create a collection to which you can add
/// faces using the IndexFaces operation.
/// </summary>
public class CreateCollection
{
    public static async Task Main()
    {
        var rekognitionClient = new AmazonRekognitionClient();

        string collectionId = "MyCollection";
        Console.WriteLine("Creating collection: " + collectionId);

        var createCollectionRequest = new CreateCollectionRequest
        {
            CollectionId = collectionId,
        };

        CreateCollectionResponse createCollectionResponse = await
rekognitionClient.CreateCollectionAsync(createCollectionRequest);
        Console.WriteLine($"CollectionArn :
{createCollectionResponse.CollectionArn}");
        Console.WriteLine($"Status code :
{createCollectionResponse.StatusCode}");
    }
}
```

- Para obter detalhes da API, consulte CreateCollectiona Referência AWS SDK for .NET da API.

Excluir uma coleção.

O exemplo de código a seguir mostra como excluir uma coleção do Amazon Rekognition.

Para mais informações, consulte Excluir uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to delete an existing collection.
/// </summary>
public class DeleteCollection
{
    public static async Task Main()
    {
        var rekognitionClient = new AmazonRekognitionClient();

        string collectionId = "MyCollection";
        Console.WriteLine("Deleting collection: " + collectionId);

        var deleteCollectionRequest = new DeleteCollectionRequest()
        {
            CollectionId = collectionId,
        };

        var deleteCollectionResponse = await
rekognitionClient.DeleteCollectionAsync(deleteCollectionRequest);
        Console.WriteLine($"{collectionId}:
{deleteCollectionResponse.StatusCode}");
```

```
        }
    }
```

- Para obter detalhes da API, consulte DeleteCollectiona Referência AWS SDK for .NET da API.

Excluir faces de uma coleção

O exemplo de código a seguir mostra como excluir faces de uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir faces de uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to delete one or more faces from
/// a Rekognition collection.
/// </summary>
public class DeleteFaces
{
    public static async Task Main()
    {
        string collectionId = "MyCollection";
        var faces = new List<string> { "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx" };

        var rekognitionClient = new AmazonRekognitionClient();

        var deleteFacesRequest = new DeleteFacesRequest()
```

```
            {
                CollectionId = collectionId,
                FaceIds = faces,
            };

            DeleteFacesResponse deleteFacesResponse = await
rekognitionClient.DeleteFacesAsync(deleteFacesRequest);
            deleteFacesResponse.DeletedFaces.ForEach(face =>
            {
                Console.WriteLine($"FaceID: {face}");
            });
        }
    }
```

- Para obter detalhes da API, consulte DeleteFacesa Referência AWS SDK for .NET da API.

Descrever uma coleção

O exemplo de código a seguir mostra como descrever uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Descrever uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to describe the contents of a
/// collection.
/// </summary>
```

```
    public class DescribeCollection
    {
        public static async Task Main()
        {
            var rekognitionClient = new AmazonRekognitionClient();

            string collectionId = "MyCollection";
            Console.WriteLine($"Describing collection: {collectionId}");

            var describeCollectionRequest = new DescribeCollectionRequest()
            {
                CollectionId = collectionId,
            };

            var describeCollectionResponse = await
rekognitionClient.DescribeCollectionAsync(describeCollectionRequest);
            Console.WriteLine($"Collection ARN:
{describeCollectionResponse.CollectionARN}");
            Console.WriteLine($"Face count:
{describeCollectionResponse.FaceCount}");
            Console.WriteLine($"Face model version:
{describeCollectionResponse.FaceModelVersion}");
            Console.WriteLine($"Created:
{describeCollectionResponse.CreationTimestamp}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeCollectiona Referência AWS SDK for .NET da API.

Detectar faces em uma imagem

O exemplo de código a seguir mostra como detectar faces em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar faces em uma imagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to detect faces within an image
    /// stored in an Amazon Simple Storage Service (Amazon S3) bucket.
    /// </summary>
    public class DetectFaces
    {
        public static async Task Main()
        {
            string photo = "input.jpg";
            string bucket = "bucket";

            var rekognitionClient = new AmazonRekognitionClient();

            var detectFacesRequest = new DetectFacesRequest()
            {
                Image = new Image()
                {
                    S3Object = new S3Object()
                    {
                        Name = photo,
                        Bucket = bucket,
                    },
                },

                // Attributes can be "ALL" or "DEFAULT".
                // "DEFAULT": BoundingBox, Confidence, Landmarks, Pose, and Quality.
                // "ALL": See https://docs.aws.amazon.com/sdkfornet/v3/apidocs/
items/Rekognition/TFaceDetail.html
```

```
                Attributes = new List<string>() { "ALL" },
            };

            try
            {
                DetectFacesResponse detectFacesResponse = await
rekognitionClient.DetectFacesAsync(detectFacesRequest);
                bool hasAll = detectFacesRequest.Attributes.Contains("ALL");
                foreach (FaceDetail face in detectFacesResponse.FaceDetails)
                {
                    Console.WriteLine($"BoundingBox: top={face.BoundingBox.Left}
left={face.BoundingBox.Top} width={face.BoundingBox.Width}
height={face.BoundingBox.Height}");
                    Console.WriteLine($"Confidence: {face.Confidence}");
                    Console.WriteLine($"Landmarks: {face.Landmarks.Count}");
                    Console.WriteLine($"Pose: pitch={face.Pose.Pitch}
roll={face.Pose.Roll} yaw={face.Pose.Yaw}");
                    Console.WriteLine($"Brightness:
{face.Quality.Brightness}\tSharpness: {face.Quality.Sharpness}");

                    if (hasAll)
                    {
                        Console.WriteLine($"Estimated age is between
{face.AgeRange.Low} and {face.AgeRange.High} years old.");
                    }
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

Exiba as informações da caixa delimitadora de todas as faces em uma imagem.

```
    using System;
    using System.Collections.Generic;
    using System.Drawing;
    using System.IO;
    using System.Threading.Tasks;
```

```
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to display the details of the
    /// bounding boxes around the faces detected in an image.
    /// </summary>
    public class ImageOrientationBoundingBox
    {
        public static async Task Main()
        {
            string photo = @"D:\Development\AWS-Examples\Rekognition\target.jpg"; //
"photo.jpg";

            var rekognitionClient = new AmazonRekognitionClient();

            var image = new Amazon.Rekognition.Model.Image();
            try
            {
                using var fs = new FileStream(photo, FileMode.Open,
FileAccess.Read);
                byte[] data = null;
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                image.Bytes = new MemoryStream(data);
            }
            catch (Exception)
            {
                Console.WriteLine("Failed to load file " + photo);
                return;
            }

            int height;
            int width;

            // Used to extract original photo width/height
            using (var imageBitmap = new Bitmap(photo))
            {
                height = imageBitmap.Height;
                width = imageBitmap.Width;
            }

            Console.WriteLine("Image Information:");
            Console.WriteLine(photo);
```

```
            Console.WriteLine("Image Height: " + height);
            Console.WriteLine("Image Width: " + width);

            try
            {
                var detectFacesRequest = new DetectFacesRequest()
                {
                    Image = image,
                    Attributes = new List<string>() { "ALL" },
                };

                DetectFacesResponse detectFacesResponse = await
 rekognitionClient.DetectFacesAsync(detectFacesRequest);
                detectFacesResponse.FaceDetails.ForEach(face =>
                {
                    Console.WriteLine("Face:");
                    ShowBoundingBoxPositions(
                        height,
                        width,
                        face.BoundingBox,
                        detectFacesResponse.OrientationCorrection);

                    Console.WriteLine($"BoundingBox: top={face.BoundingBox.Left}
 left={face.BoundingBox.Top} width={face.BoundingBox.Width}
 height={face.BoundingBox.Height}");
                    Console.WriteLine($"The detected face is estimated to be between
 {face.AgeRange.Low} and {face.AgeRange.High} years old.\n");
                });
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }

        /// <summary>
        /// Display the bounding box information for an image.
        /// </summary>
        /// <param name="imageHeight">The height of the image.</param>
        /// <param name="imageWidth">The width of the image.</param>
        /// <param name="box">The bounding box for a face found within the image.</
param>
        /// <param name="rotation">The rotation of the face's bounding box.</param>
```

```
        public static void ShowBoundingBoxPositions(int imageHeight, int imageWidth,
BoundingBox box, string rotation)
        {
            float left;
            float top;

            if (rotation == null)
            {
                Console.WriteLine("No estimated orientation. Check Exif data.");
                return;
            }

            // Calculate face position based on image orientation.
            switch (rotation)
            {
                case "ROTATE_0":
                    left = imageWidth * box.Left;
                    top = imageHeight * box.Top;
                    break;
                case "ROTATE_90":
                    left = imageHeight * (1 - (box.Top + box.Height));
                    top = imageWidth * box.Left;
                    break;
                case "ROTATE_180":
                    left = imageWidth - (imageWidth * (box.Left + box.Width));
                    top = imageHeight * (1 - (box.Top + box.Height));
                    break;
                case "ROTATE_270":
                    left = imageHeight * box.Top;
                    top = imageWidth * (1 - box.Left - box.Width);
                    break;
                default:
                    Console.WriteLine("No estimated orientation information. Check
Exif data.");
                    return;
            }

            // Display face location information.
            Console.WriteLine($"Left: {left}");
            Console.WriteLine($"Top: {top}");
            Console.WriteLine($"Face Width: {imageWidth * box.Width}");
            Console.WriteLine($"Face Height: {imageHeight * box.Height}");
        }
    }
```

- Para obter detalhes da API, consulte DetectFacesa Referência AWS SDK for .NET da API.

Para detectar rótulos em uma imagem

O exemplo de código a seguir mostra como detectar rótulos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar rótulos em uma imagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect labels within an image
/// stored in an Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class DetectLabels
{
    public static async Task Main()
    {
        string photo = "del_river_02092020_01.jpg"; // "input.jpg";
        string bucket = "igsmiths3photos"; // "bucket";

        var rekognitionClient = new AmazonRekognitionClient();

        var detectlabelsRequest = new DetectLabelsRequest
        {
            Image = new Image()
```

```
                {
                    S3Object = new S3Object()
                    {
                        Name = photo,
                        Bucket = bucket,
                    },
                },
                MaxLabels = 10,
                MinConfidence = 75F,
            };

            try
            {
                DetectLabelsResponse detectLabelsResponse = await
rekognitionClient.DetectLabelsAsync(detectlabelsRequest);
                Console.WriteLine("Detected labels for " + photo);
                foreach (Label label in detectLabelsResponse.Labels)
                {
                    Console.WriteLine($"Name: {label.Name} Confidence:
{label.Confidence}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

Detecte rótulos em um arquivo de imagem armazenado em seu computador.

```
    using System;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to detect labels within an image
    /// stored locally.
    /// </summary>
```

```
    public class DetectLabelsLocalFile
    {
        public static async Task Main()
        {
            string photo = "input.jpg";

            var image = new Amazon.Rekognition.Model.Image();
            try
            {
                using var fs = new FileStream(photo, FileMode.Open,
FileAccess.Read);
                byte[] data = null;
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
                image.Bytes = new MemoryStream(data);
            }
            catch (Exception)
            {
                Console.WriteLine("Failed to load file " + photo);
                return;
            }

            var rekognitionClient = new AmazonRekognitionClient();

            var detectlabelsRequest = new DetectLabelsRequest
            {
                Image = image,
                MaxLabels = 10,
                MinConfidence = 77F,
            };

            try
            {
                DetectLabelsResponse detectLabelsResponse = await
rekognitionClient.DetectLabelsAsync(detectlabelsRequest);
                Console.WriteLine($"Detected labels for {photo}");
                foreach (Label label in detectLabelsResponse.Labels)
                {
                    Console.WriteLine($"{label.Name}: {label.Confidence}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
```

```
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectLabelsa Referência AWS SDK for .NET da API.

Detectar rótulos de moderação em uma imagem

O exemplo de código a seguir mostra como detectar rótulos de moderação em uma imagem com o Amazon Rekognition. Os rótulos de moderação identificam o conteúdo que pode ser inadequado para alguns públicos.

Para obter mais informações, consulte Detectar imagens inapropriadas.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect unsafe content in a
/// JPEG or PNG format image.
/// </summary>
public class DetectModerationLabels
{
    public static async Task Main(string[] args)
    {
        string photo = "input.jpg";
        string bucket = "bucket";

        var rekognitionClient = new AmazonRekognitionClient();
```

```
            var detectModerationLabelsRequest = new DetectModerationLabelsRequest()
            {
                Image = new Image()
                {
                    S3Object = new S3Object()
                    {
                        Name = photo,
                        Bucket = bucket,
                    },
                },
                MinConfidence = 60F,
            };

            try
            {
                var detectModerationLabelsResponse = await
rekognitionClient.DetectModerationLabelsAsync(detectModerationLabelsRequest);
                Console.WriteLine("Detected labels for " + photo);
                foreach (ModerationLabel label in
detectModerationLabelsResponse.ModerationLabels)
                {
                    Console.WriteLine($"Label: {label.Name}");
                    Console.WriteLine($"Confidence: {label.Confidence}");
                    Console.WriteLine($"Parent: {label.ParentName}");
                }
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectModerationLabelsa Referência AWS SDK for .NET da API.

Detectar texto em uma imagem

O exemplo de código a seguir mostra como detectar texto em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar texto em uma imagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect text in an image. The
/// example was created using the AWS SDK for .NET version 3.7 and .NET
/// Core 5.0.
/// </summary>
public class DetectText
{
    public static async Task Main()
    {
        string photo = "Dad_photographer.jpg"; // "input.jpg";
        string bucket = "igsmiths3photos"; // "bucket";

        var rekognitionClient = new AmazonRekognitionClient();

        var detectTextRequest = new DetectTextRequest()
        {
            Image = new Image()
            {
                S3Object = new S3Object()
                {
                    Name = photo,
                    Bucket = bucket,
                },
            },
        };

        try
```

```
            {
                DetectTextResponse detectTextResponse = await
rekognitionClient.DetectTextAsync(detectTextRequest);
                Console.WriteLine($"Detected lines and words for {photo}");
                detectTextResponse.TextDetections.ForEach(text =>
                {
                    Console.WriteLine($"Detected: {text.DetectedText}");
                    Console.WriteLine($"Confidence: {text.Confidence}");
                    Console.WriteLine($"Id : {text.Id}");
                    Console.WriteLine($"Parent Id: {text.ParentId}");
                    Console.WriteLine($"Type: {text.Type}");
                });
            }
            catch (Exception e)
            {
                Console.WriteLine(e.Message);
            }
        }
    }
```

- Para obter detalhes da API, consulte DetectTexta Referência AWS SDK for .NET da API.

Obter informações sobre celebridades

O exemplo de código a seguir mostra como obter informações sobre celebridades usando o Amazon Rekognition.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;
```

```
    /// <summary>
    /// Shows how to use Amazon Rekognition to retrieve information about the
    /// celebrity identified by the supplied celebrity Id.
    /// </summary>
    public class CelebrityInfo
    {
        public static async Task Main()
        {
            string celebId = "nnnnnnnn";

            var rekognitionClient = new AmazonRekognitionClient();

            var celebrityInfoRequest = new GetCelebrityInfoRequest
            {
                Id = celebId,
            };

            Console.WriteLine($"Getting information for celebrity: {celebId}");

            var celebrityInfoResponse = await
rekognitionClient.GetCelebrityInfoAsync(celebrityInfoRequest);

            // Display celebrity information.
            Console.WriteLine($"celebrity name: {celebrityInfoResponse.Name}");
            Console.WriteLine("Further information (if available):");
            celebrityInfoResponse.Urls.ForEach(url =>
            {
                Console.WriteLine(url);
            });
        }
    }
```

- Para obter detalhes da API, consulte GetCelebrityInfoa Referência AWS SDK for .NET da API.

Indexar faces de uma coleção

O exemplo de código a seguir mostra como indexar faces em uma imagem e adicioná-las a uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Adicionar faces a uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to detect faces in an image
/// that has been uploaded to an Amazon Simple Storage Service (Amazon S3)
/// bucket and then adds the information to a collection.
/// </summary>
public class AddFaces
{
    public static async Task Main()
    {
        string collectionId = "MyCollection2";
        string bucket = "doc-example-bucket";
        string photo = "input.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        var image = new Image
        {
            S3Object = new S3Object
            {
                Bucket = bucket,
                Name = photo,
            },
        };

        var indexFacesRequest = new IndexFacesRequest
        {
            Image = image,
            CollectionId = collectionId,
```

```
                ExternalImageId = photo,
                DetectionAttributes = new List<string>() { "ALL" },
            };

            IndexFacesResponse indexFacesResponse = await
rekognitionClient.IndexFacesAsync(indexFacesRequest);

            Console.WriteLine($"{photo} added");
            foreach (FaceRecord faceRecord in indexFacesResponse.FaceRecords)
            {
                Console.WriteLine($"Face detected: Faceid is
{faceRecord.Face.FaceId}");
            }
        }
    }
```

- Para obter detalhes da API, consulte IndexFacesa Referência AWS SDK for .NET da API.

Listar coleções

O exemplo de código a seguir mostra como listar coleções do Amazon Rekognition.

Para obter mais informações, consulte Listar coleções.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses Amazon Rekognition to list the collection IDs in the
```

```
    /// current account.
    /// </summary>
    public class ListCollections
    {
        public static async Task Main()
        {
            var rekognitionClient = new AmazonRekognitionClient();

            Console.WriteLine("Listing collections");
            int limit = 10;

            var listCollectionsRequest = new ListCollectionsRequest
            {
                MaxResults = limit,
            };

            var listCollectionsResponse = new ListCollectionsResponse();

            do
            {
                if (listCollectionsResponse is not null)
                {
                    listCollectionsRequest.NextToken =
listCollectionsResponse.NextToken;
                }

                listCollectionsResponse = await
rekognitionClient.ListCollectionsAsync(listCollectionsRequest);

                listCollectionsResponse.CollectionIds.ForEach(id =>
                {
                    Console.WriteLine(id);
                });
            }
            while (listCollectionsResponse.NextToken is not null);
        }
    }
```

- Para obter detalhes da API, consulte ListCollectionsa Referência AWS SDK for .NET da API.

Listar faces em uma coleção

O exemplo de código a seguir mostra como lista faces em uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Listar faces em uma coleção.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to retrieve the list of faces
/// stored in a collection.
/// </summary>
public class ListFaces
{
    public static async Task Main()
    {
        string collectionId = "MyCollection2";

        var rekognitionClient = new AmazonRekognitionClient();

        var listFacesResponse = new ListFacesResponse();
        Console.WriteLine($"Faces in collection {collectionId}");

        var listFacesRequest = new ListFacesRequest
        {
            CollectionId = collectionId,
            MaxResults = 1,
        };

        do
        {
```

```
                listFacesResponse = await
rekognitionClient.ListFacesAsync(listFacesRequest);
                listFacesResponse.Faces.ForEach(face =>
                {
                    Console.WriteLine(face.FaceId);
                });

                listFacesRequest.NextToken = listFacesResponse.NextToken;
            }
            while (!string.IsNullOrEmpty(listFacesResponse.NextToken));
        }
    }
```

- Para obter detalhes da API, consulte ListFacesa Referência AWS SDK for .NET da API.

Reconhecer celebridades em uma imagem

O exemplo de código a seguir mostra como reconhecer celebridades em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Reconhecer celebridades em uma imagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Shows how to use Amazon Rekognition to identify celebrities in a photo.
    /// </summary>
    public class CelebritiesInImage
```

```
    {
        public static async Task Main(string[] args)
        {
            string photo = "moviestars.jpg";

            var rekognitionClient = new AmazonRekognitionClient();

            var recognizeCelebritiesRequest = new RecognizeCelebritiesRequest();

            var img = new Amazon.Rekognition.Model.Image();
            byte[] data = null;
            try
            {
                using var fs = new FileStream(photo, FileMode.Open,
FileAccess.Read);
                data = new byte[fs.Length];
                fs.Read(data, 0, (int)fs.Length);
            }
            catch (Exception)
            {
                Console.WriteLine($"Failed to load file {photo}");
                return;
            }

            img.Bytes = new MemoryStream(data);
            recognizeCelebritiesRequest.Image = img;

            Console.WriteLine($"Looking for celebrities in image {photo}\n");

            var recognizeCelebritiesResponse = await
rekognitionClient.RecognizeCelebritiesAsync(recognizeCelebritiesRequest);

            Console.WriteLine($"{recognizeCelebritiesResponse.CelebrityFaces.Count}
celebrity(s) were recognized.\n");
            recognizeCelebritiesResponse.CelebrityFaces.ForEach(celeb =>
            {
                Console.WriteLine($"Celebrity recognized: {celeb.Name}");
                Console.WriteLine($"Celebrity ID: {celeb.Id}");
                BoundingBox boundingBox = celeb.Face.BoundingBox;
                Console.WriteLine($"position: {boundingBox.Left}
{boundingBox.Top}");
                Console.WriteLine("Further information (if available):");
                celeb.Urls.ForEach(url =>
                {
```

```
                    Console.WriteLine(url);
                });
            });


Console.WriteLine($"{recognizeCelebritiesResponse.UnrecognizedFaces.Count} face(s)
were unrecognized.");
        }
    }
```

- Para obter detalhes da API, consulte RecognizeCelebritiesa Referência AWS SDK for .NET da API.

Pesquisar faces em uma coleção

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition que correspondam a outra face da coleção.

Para obter mais informações, consulte Pesquisar uma face (Face ID).

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Rekognition;
    using Amazon.Rekognition.Model;

    /// <summary>
    /// Uses the Amazon Rekognition Service to find faces in an image that
    /// match the face Id provided in the method request.
    /// </summary>
    public class SearchFacesMatchingId
    {
```

```
        public static async Task Main()
        {
            string collectionId = "MyCollection";
            string faceId = "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx";

            var rekognitionClient = new AmazonRekognitionClient();

            // Search collection for faces matching the face id.
            var searchFacesRequest = new SearchFacesRequest
            {
                CollectionId = collectionId,
                FaceId = faceId,
                FaceMatchThreshold = 70F,
                MaxFaces = 2,
            };

            SearchFacesResponse searchFacesResponse = await
rekognitionClient.SearchFacesAsync(searchFacesRequest);

            Console.WriteLine("Face matching faceId " + faceId);

            Console.WriteLine("Matche(s): ");
            searchFacesResponse.FaceMatches.ForEach(face =>
            {
                Console.WriteLine($"FaceId: {face.Face.FaceId} Similarity:
{face.Similarity}");
            });
        }
    }
```

- Para obter detalhes da API, consulte SearchFacesa Referência AWS SDK for .NET da API.

Pesquisar faces em uma coleção em comparação com uma imagem de referência

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition em comparação com uma imagem de referência.

Para obter mais informações, consulte Pesquisar uma face (imagem).

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Rekognition;
using Amazon.Rekognition.Model;

/// <summary>
/// Uses the Amazon Rekognition Service to search for images matching those
/// in a collection.
/// </summary>
public class SearchFacesMatchingImage
{
    public static async Task Main()
    {
        string collectionId = "MyCollection";
        string bucket = "bucket";
        string photo = "input.jpg";

        var rekognitionClient = new AmazonRekognitionClient();

        // Get an image object from S3 bucket.
        var image = new Image()
        {
            S3Object = new S3Object()
            {
                Bucket = bucket,
                Name = photo,
            },
        };

        var searchFacesByImageRequest = new SearchFacesByImageRequest()
        {
            CollectionId = collectionId,
            Image = image,
            FaceMatchThreshold = 70F,
```

```
                MaxFaces = 2,
            };

            SearchFacesByImageResponse searchFacesByImageResponse = await
rekognitionClient.SearchFacesByImageAsync(searchFacesByImageRequest);

            Console.WriteLine("Faces matching largest face in image from " + photo);
            searchFacesByImageResponse.FaceMatches.ForEach(face =>
            {
                Console.WriteLine($"FaceId: {face.Face.FaceId}, Similarity:
{face.Similarity}");
            });
        }
    }
```

- Para obter detalhes da API, consulte SearchFacesByImagea Referência AWS SDK for .NET da API.

Exemplos do registro de domínio do Route 53 usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o registro de domínios do Route 53.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Registro de domínios do Hello Route 53

O exemplo de código a seguir mostra como começar a usar o registro de domínios do Route 53.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static class HelloRoute53Domains
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the Amazon Route 53 domain registration service.
        // Use your AWS profile name, or leave it blank to use the default profile.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonRoute53Domains>()
            ).Build();

        // Now the client is available for injection.
        var route53Client =
 host.Services.GetRequiredService<IAmazonRoute53Domains>();

        // You can use await and any of the async methods to get a response.
        var response = await route53Client.ListPricesAsync(new ListPricesRequest
 { Tld = "com" });
        Console.WriteLine($"Hello Amazon Route 53 Domains! Following are prices
 for .com domain operations:");
        var comPrices = response.Prices.FirstOrDefault();
        if (comPrices != null)
        {
            Console.WriteLine($"\tRegistration: {comPrices.RegistrationPrice?.Price}
 {comPrices.RegistrationPrice?.Currency}");
            Console.WriteLine($"\tRenewal: {comPrices.RenewalPrice?.Price}
 {comPrices.RenewalPrice?.Currency}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Verificar disponibilidade de domínios

O exemplo de código a seguir mostra como verificar a disponibilidade de um domínio.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Check the availability of a domain name.
/// </summary>
/// <param name="domain">The domain to check for availability.</param>
/// <returns>An availability result string.</returns>
public async Task<string> CheckDomainAvailability(string domain)
{
    var result = await _amazonRoute53Domains.CheckDomainAvailabilityAsync(
        new CheckDomainAvailabilityRequest
        {
            DomainName = domain
        }
    );
    return result.Availability.Value;
}
```

- Para obter detalhes da API, consulte CheckDomainAvailabilitya Referência AWS SDK for .NET da API.

Verificar a transferibilidade de um domínio

O exemplo de código a seguir mostra como verificar o potencial para transferência de um domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Check the transferability of a domain name.
/// </summary>
/// <param name="domain">The domain to check for transferability.</param>
/// <returns>A transferability result string.</returns>
public async Task<string> CheckDomainTransferability(string domain)
{
    var result = await _amazonRoute53Domains.CheckDomainTransferabilityAsync(
        new CheckDomainTransferabilityRequest
        {
            DomainName = domain
        }
    );
    return result.Transferability.Transferable.Value;
}
```

- Para obter detalhes da API, consulte CheckDomainTransferabilitya Referência AWS SDK for .NET da API.

Obter detalhes de um domínio

O exemplo de código a seguir mostra como obter os detalhes de um domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details for a domain.
    /// </summary>
    /// <returns>A string with detail information about the domain.</returns>
    public async Task<string> GetDomainDetail(string domainName)
    {
        try
        {
            var result = await _amazonRoute53Domains.GetDomainDetailAsync(
                new GetDomainDetailRequest()
                {
                    DomainName = domainName
                });
            var details = $"\tDomain {domainName}:\n" +
                          $"\tCreated on {result.CreationDate.ToShortDateString()}.
\n" +
                          $"\tAdmin contact is {result.AdminContact.Email}.\n" +
                          $"\tAuto-renew is {result.AutoRenew}.\n";

            return details;
        }
        catch (InvalidInputException)
        {
            return $"Domain {domainName} was not found in your account.";
        }
    }
```

- Para obter detalhes da API, consulte GetDomainDetaila Referência AWS SDK for .NET da API.

Obter detalhes de uma operação

O exemplo de código a seguir mostra como obter os detalhes de uma operação.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details for a domain action operation.
    /// </summary>
    /// <param name="operationId">The operational Id.</param>
    /// <returns>A string describing the operational details.</returns>
    public async Task<string> GetOperationDetail(string? operationId)
    {
        if (operationId == null)
            return "Unable to get operational details because ID is null.";
        try
        {
            var operationDetails =
                await _amazonRoute53Domains.GetOperationDetailAsync(
                    new GetOperationDetailRequest
                    {
                        OperationId = operationId
                    }
                );

            var details = $"\tOperation {operationId}:\n" +
                          $"\tFor domain {operationDetails.DomainName} on
{operationDetails.SubmittedDate.ToShortDateString()}.\n" +
                          $"\tMessage is {operationDetails.Message}.\n" +
                          $"\tStatus is {operationDetails.Status}.\n";

            return details;
        }
        catch (AmazonRoute53DomainsException ex)
        {
            return $"Unable to get operation details. Here's why: {ex.Message}.";
        }
    }
```

- Para obter detalhes da API, consulte GetOperationDetaila Referência AWS SDK for .NET da API.

Obter nomes de domínio sugeridos

O exemplo de código a seguir mostra como obter sugestões de nomes de domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Get a list of suggestions for a given domain.
   /// </summary>
   /// <param name="domain">The domain to check for suggestions.</param>
   /// <param name="onlyAvailable">If true, only returns available domains.</param>
   /// <param name="suggestionCount">The number of suggestions to return. Defaults
to the max of 50.</param>
   /// <returns>A collection of domain suggestions.</returns>
   public async Task<List<DomainSuggestion>> GetDomainSuggestions(string domain,
bool onlyAvailable, int suggestionCount = 50)
   {
       var result = await _amazonRoute53Domains.GetDomainSuggestionsAsync(
           new GetDomainSuggestionsRequest
           {
               DomainName = domain,
               OnlyAvailable = onlyAvailable,
               SuggestionCount = suggestionCount
           }
       );
       return result.SuggestionsList;
   }
```

- Para obter detalhes da API, consulte GetDomainSuggestionsa Referência AWS SDK for .NET da API.

Listar preços de domínios

O exemplo de código a seguir mostra como listar preços de domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List prices for domain type operations.
    /// </summary>
    /// <param name="domainTypes">Domain types to include in the results.</param>
    /// <returns>The list of domain prices.</returns>
    public async Task<List<DomainPrice>> ListPrices(List<string> domainTypes)
    {
        var results = new List<DomainPrice>();
        var paginatePrices = _amazonRoute53Domains.Paginators.ListPrices(new
ListPricesRequest());
        // Get the entire list using the paginator.
        await foreach (var prices in paginatePrices.Prices)
        {
            results.Add(prices);
        }
        return results.Where(p => domainTypes.Contains(p.Name)).ToList();
    }
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for .NET da API.

Listar domínios

O exemplo de código a seguir mostra como listar os domínios registrados.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// List the domains for the account.
/// </summary>
/// <returns>A collection of domain summary records.</returns>
public async Task<List<DomainSummary>> ListDomains()
{
    var results = new List<DomainSummary>();
    var paginateDomains = _amazonRoute53Domains.Paginators.ListDomains(
        new ListDomainsRequest());

    // Get the entire list using the paginator.
    await foreach (var domain in paginateDomains.Domains)
    {
        results.Add(domain);
    }
    return results;
}
```

- Para obter detalhes da API, consulte ListDomainsa Referência AWS SDK for .NET da API.

Operações de lista

O exemplo de código a seguir mostra como listar operações.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List operations for the account that are submitted after a specified date.
    /// </summary>
    /// <returns>A collection of operation summary records.</returns>
    public async Task<List<OperationSummary>> ListOperations(DateTime
submittedSince)
    {
        var results = new List<OperationSummary>();
        var paginateOperations = _amazonRoute53Domains.Paginators.ListOperations(
            new ListOperationsRequest()
            {
                SubmittedSince = submittedSince
            });

        // Get the entire list using the paginator.
        await foreach (var operations in paginateOperations.Operations)
        {
            results.Add(operations);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte ListOperationsa Referência AWS SDK for .NET da API.

Registrar um domínio

O exemplo de código a seguir mostra como registrar um domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Initiate a domain registration request.
```

```
    /// </summary>
    /// <param name="contact">Contact details.</param>
    /// <param name="domainName">The domain name to register.</param>
    /// <param name="autoRenew">True if the domain should automatically renew.</
param>
    /// <param name="duration">The duration in years for the domain registration.</
param>
    /// <returns>The operation Id.</returns>
    public async Task<string?> RegisterDomain(string domainName, bool autoRenew, int
 duration, ContactDetail contact)
    {
        // This example uses the same contact information for admin, registrant, and
 tech contacts.
        try
        {
            var result = await _amazonRoute53Domains.RegisterDomainAsync(
                new RegisterDomainRequest()
                {
                    AdminContact = contact,
                    RegistrantContact = contact,
                    TechContact = contact,
                    DomainName = domainName,
                    AutoRenew = autoRenew,
                    DurationInYears = duration,
                    PrivacyProtectAdminContact = false,
                    PrivacyProtectRegistrantContact = false,
                    PrivacyProtectTechContact = false
                }
            );
            return result.OperationId;
        }
        catch (InvalidInputException)
        {
            _logger.LogInformation($"Unable to request registration for domain
 {domainName}");
            return null;
        }
    }
```

- Para obter detalhes da API, consulte RegisterDomaina Referência AWS SDK for .NET da API.

Exibir faturamento

O exemplo de código a seguir mostra como visualizar registros de cobrança.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// View billing records for the account between a start and end date.
    /// </summary>
    /// <param name="startDate">The start date for billing results.</param>
    /// <param name="endDate">The end date for billing results.</param>
    /// <returns>A collection of billing records.</returns>
    public async Task<List<BillingRecord>> ViewBilling(DateTime startDate, DateTime
endDate)
    {
        var results = new List<BillingRecord>();
        var paginateBilling = _amazonRoute53Domains.Paginators.ViewBilling(
            new ViewBillingRequest()
            {
                Start = startDate,
                End = endDate
            });

        // Get the entire list using the paginator.
        await foreach (var billingRecords in paginateBilling.BillingRecords)
        {
            results.Add(billingRecords);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte ViewBillinga Referência AWS SDK for .NET da API.

Cenários

Conceitos básicos de domínios

O código de exemplo a seguir mostra como:

- Liste os domínios atuais e as operações do ano passado.
- Veja o faturamento do ano passado e os preços dos tipos de domínio.
- Receba sugestões de domínio.
- Verifique a disponibilidade e a transferibilidade de um domínio.
- Opcionalmente, solicite o registro de um domínio.
- Obtenha os detalhes de uma operação.
- Opcionalmente, obtenha os detalhes de um domínio.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
public static class Route53DomainScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.

    This .NET example performs the following tasks:
        1. List current domains.
        2. List operations in the past year.
        3. View billing for the account in the past year.
        4. View prices for domain types.
        5. Get domain suggestions.
        6. Check domain availability.
        7. Check domain transferability.
        8. Optionally, request a domain registration.
```

```
        9. Get an operation detail.
       10. Optionally, get a domain detail.
  */

   private static Route53Wrapper _route53Wrapper = null!;
   private static IConfiguration _configuration = null!;

   static async Task Main(string[] args)
   {
       // Set up dependency injection for the Amazon service.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
                   .ConfigureServices((_, services) =>
           services.AddAWSService<IAmazonRoute53Domains>()
               .AddTransient<Route53Wrapper>()
           )
           .Build();

       _configuration = new ConfigurationBuilder()
           .SetBasePath(Directory.GetCurrentDirectory())
           .AddJsonFile("settings.json") // Load settings from .json file.
           .AddJsonFile("settings.local.json",
               true) // Optionally, load local settings.
           .Build();

       var logger = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       }).CreateLogger(typeof(Route53DomainScenario));

       _route53Wrapper = host.Services.GetRequiredService<Route53Wrapper>();

       Console.WriteLine(new string('-', 80));
       Console.WriteLine("Welcome to the Amazon Route 53 domains example
scenario.");
       Console.WriteLine(new string('-', 80));

       try
       {
           await ListDomains();
```

```
            await ListOperations();
            await ListBillingRecords();
            await ListPrices();
            await ListDomainSuggestions();
            await CheckDomainAvailability();
            await CheckDomainTransferability();
            var operationId = await RequestDomainRegistration();
            await GetOperationalDetail(operationId);
            await GetDomainDetails();
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }

        Console.WriteLine(new string('-', 80));
        Console.WriteLine("The Amazon Route 53 domains example scenario is
complete.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List account registered domains.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDomains()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"1. List account domains.");
        var domains = await _route53Wrapper.ListDomains();
        for (int i = 0; i < domains.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {domains[i].DomainName}");
        }

        if (!domains.Any())
        {
            Console.WriteLine("\tNo domains found in this account.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
```

```
    /// List domain operations in the past year.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListOperations()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"2. List account domain operations in the past year.");
        var operations = await _route53Wrapper.ListOperations(
            DateTime.Today.AddYears(-1));
        for (int i = 0; i < operations.Count; i++)
        {
            Console.WriteLine($"\tOperation Id: {operations[i].OperationId}");
            Console.WriteLine($"\tStatus: {operations[i].Status}");
            Console.WriteLine($"\tDate: {operations[i].SubmittedDate}");
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List billing in the past year.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListBillingRecords()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"3. View billing for the account in the past year.");
        var billingRecords = await _route53Wrapper.ViewBilling(
            DateTime.Today.AddYears(-1),
            DateTime.Today);
        for (int i = 0; i < billingRecords.Count; i++)
        {
            Console.WriteLine($"\tBill Date:
{billingRecords[i].BillDate.ToShortDateString()}");
            Console.WriteLine($"\tOperation: {billingRecords[i].Operation}");
            Console.WriteLine($"\tPrice: {billingRecords[i].Price}");
        }
        if (!billingRecords.Any())
        {
            Console.WriteLine("\tNo billing records found in this account for the
past year.");
        }
        Console.WriteLine(new string('-', 80));
    }
```

```
    /// <summary>
    /// List prices for a few domain types.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListPrices()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. View prices for domain types.");
        var domainTypes = new List<string> { "net", "com", "org", "co" };

        var prices = await _route53Wrapper.ListPrices(domainTypes);
        foreach (var pr in prices)
        {
            Console.WriteLine($"\tName: {pr.Name}");
            Console.WriteLine($"\tRegistration: {pr.RegistrationPrice?.Price}
{pr.RegistrationPrice?.Currency}");
            Console.WriteLine($"\tRenewal: {pr.RenewalPrice?.Price}
{pr.RenewalPrice?.Currency}");
            Console.WriteLine($"\tTransfer: {pr.TransferPrice?.Price}
{pr.TransferPrice?.Currency}");
            Console.WriteLine($"\tChange Ownership: {pr.ChangeOwnershipPrice?.Price}
{pr.ChangeOwnershipPrice?.Currency}");
            Console.WriteLine($"\tRestoration: {pr.RestorationPrice?.Price}
{pr.RestorationPrice?.Currency}");
            Console.WriteLine();
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List domain suggestions for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task ListDomainSuggestions()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"5. Get domain suggestions.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
            Console.WriteLine($"Enter a domain name to get available domain
suggestions.");
            domainName = Console.ReadLine();
        }
```

```
        var suggestions = await _route53Wrapper.GetDomainSuggestions(domainName,
true, 5);
        foreach (var suggestion in suggestions)
        {
            Console.WriteLine($"\tSuggestion Name: {suggestion.DomainName}");
            Console.WriteLine($"\tAvailability: {suggestion.Availability}");
        }
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check availability for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckDomainAvailability()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. Check domain availability.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
            Console.WriteLine($"Enter a domain name to check domain availability.");
            domainName = Console.ReadLine();
        }

        var availability = await
_route53Wrapper.CheckDomainAvailability(domainName);
        Console.WriteLine($"\tAvailability: {availability}");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check transferability for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CheckDomainTransferability()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Check domain transferability.");
        string? domainName = null;
        while (domainName == null || string.IsNullOrWhiteSpace(domainName))
        {
```

```
            Console.WriteLine($"Enter a domain name to check domain
 transferability.");
            domainName = Console.ReadLine();
        }

        var transferability = await
 _route53Wrapper.CheckDomainTransferability(domainName);
        Console.WriteLine($"\tTransferability: {transferability}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Check transferability for a domain name.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string?> RequestDomainRegistration()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. Optionally, request a domain registration.");

        Console.WriteLine($"\tNote: This example uses domain request settings in
 settings.json.");
        Console.WriteLine($"\tTo change the domain registration settings, set the
 values in that file.");
        Console.WriteLine($"\tRemember, registering an actual domain will incur an
 account billing cost.");
        Console.WriteLine($"\tWould you like to begin a domain registration? (y/
n)");
        var ynResponse = Console.ReadLine();
        if (ynResponse != null && ynResponse.Equals("y",
 StringComparison.InvariantCultureIgnoreCase))
        {
            string domainName = _configuration["DomainName"];
            ContactDetail contact = new ContactDetail();
            contact.CountryCode =
 CountryCode.FindValue(_configuration["Contact:CountryCode"]);
            contact.ContactType =
 ContactType.FindValue(_configuration["Contact:ContactType"]);

            _configuration.GetSection("Contact").Bind(contact);

            var operationId = await _route53Wrapper.RegisterDomain(
                domainName,
```

```
                Convert.ToBoolean(_configuration["AutoRenew"]),
                Convert.ToInt32(_configuration["DurationInYears"]),
                contact);
            if (operationId != null)
            {
                Console.WriteLine(
                    $"\tRegistration requested. Operation Id: {operationId}");
            }

            return operationId;
        }

        Console.WriteLine(new string('-', 80));
        return null;
    }

    /// <summary>
    /// Get details for an operation.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task GetOperationalDetail(string? operationId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Get an operation detail.");

        var operationDetails =
            await _route53Wrapper.GetOperationDetail(operationId);

        Console.WriteLine(operationDetails);

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Optionally, get details for a registered domain.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string?> GetDomainDetails()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Get details on a domain.");

        Console.WriteLine($"\tNote: you must have a registered domain to get
details.");
```

```
        Console.WriteLine($"\tWould you like to get domain details? (y/n)");
        var ynResponse = Console.ReadLine();
        if (ynResponse != null && ynResponse.Equals("y",
 StringComparison.InvariantCultureIgnoreCase))
        {
            string? domainName = null;
            while (domainName == null)
            {
                Console.WriteLine($"\tEnter a domain name to get details.");
                domainName = Console.ReadLine();
            }

            var domainDetails = await _route53Wrapper.GetDomainDetail(domainName);
            Console.WriteLine(domainDetails);
        }

        Console.WriteLine(new string('-', 80));
        return null;
    }
}
```

Os métodos de wrapper usados pelo cenário para as ações do registro de domínios do Route 53.

```
public class Route53Wrapper
{
    private readonly IAmazonRoute53Domains _amazonRoute53Domains;
    private readonly ILogger<Route53Wrapper> _logger;
    public Route53Wrapper(IAmazonRoute53Domains amazonRoute53Domains,
 ILogger<Route53Wrapper> logger)
    {
        _amazonRoute53Domains = amazonRoute53Domains;
        _logger = logger;
    }


    /// <summary>
    /// List prices for domain type operations.
    /// </summary>
    /// <param name="domainTypes">Domain types to include in the results.</param>
    /// <returns>The list of domain prices.</returns>
    public async Task<List<DomainPrice>> ListPrices(List<string> domainTypes)
```

```
    {
        var results = new List<DomainPrice>();
        var paginatePrices = _amazonRoute53Domains.Paginators.ListPrices(new
ListPricesRequest());
        // Get the entire list using the paginator.
        await foreach (var prices in paginatePrices.Prices)
        {
            results.Add(prices);
        }
        return results.Where(p => domainTypes.Contains(p.Name)).ToList();
    }


    /// <summary>
    /// Check the availability of a domain name.
    /// </summary>
    /// <param name="domain">The domain to check for availability.</param>
    /// <returns>An availability result string.</returns>
    public async Task<string> CheckDomainAvailability(string domain)
    {
        var result = await _amazonRoute53Domains.CheckDomainAvailabilityAsync(
            new CheckDomainAvailabilityRequest
            {
                DomainName = domain
            }
        );
        return result.Availability.Value;
    }


    /// <summary>
    /// Check the transferability of a domain name.
    /// </summary>
    /// <param name="domain">The domain to check for transferability.</param>
    /// <returns>A transferability result string.</returns>
    public async Task<string> CheckDomainTransferability(string domain)
    {
        var result = await _amazonRoute53Domains.CheckDomainTransferabilityAsync(
            new CheckDomainTransferabilityRequest
            {
                DomainName = domain
            }
        );
        return result.Transferability.Transferable.Value;
```

```
    }


    /// <summary>
    /// Get a list of suggestions for a given domain.
    /// </summary>
    /// <param name="domain">The domain to check for suggestions.</param>
    /// <param name="onlyAvailable">If true, only returns available domains.</param>
    /// <param name="suggestionCount">The number of suggestions to return. Defaults
 to the max of 50.</param>
    /// <returns>A collection of domain suggestions.</returns>
    public async Task<List<DomainSuggestion>> GetDomainSuggestions(string domain,
 bool onlyAvailable, int suggestionCount = 50)
    {
        var result = await _amazonRoute53Domains.GetDomainSuggestionsAsync(
            new GetDomainSuggestionsRequest
            {
                DomainName = domain,
                OnlyAvailable = onlyAvailable,
                SuggestionCount = suggestionCount
            }
        );
        return result.SuggestionsList;
    }


    /// <summary>
    /// Get details for a domain action operation.
    /// </summary>
    /// <param name="operationId">The operational Id.</param>
    /// <returns>A string describing the operational details.</returns>
    public async Task<string> GetOperationDetail(string? operationId)
    {
        if (operationId == null)
            return "Unable to get operational details because ID is null.";
        try
        {
            var operationDetails =
                await _amazonRoute53Domains.GetOperationDetailAsync(
                    new GetOperationDetailRequest
                    {
                        OperationId = operationId
                    }
                );
```

```
            var details = $"\tOperation {operationId}:\n" +
                          $"\tFor domain {operationDetails.DomainName} on
 {operationDetails.SubmittedDate.ToShortDateString()}.\n" +
                          $"\tMessage is {operationDetails.Message}.\n" +
                          $"\tStatus is {operationDetails.Status}.\n";

            return details;
        }
        catch (AmazonRoute53DomainsException ex)
        {
            return $"Unable to get operation details. Here's why: {ex.Message}.";
        }
    }


    /// <summary>
    /// Initiate a domain registration request.
    /// </summary>
    /// <param name="contact">Contact details.</param>
    /// <param name="domainName">The domain name to register.</param>
    /// <param name="autoRenew">True if the domain should automatically renew.</
param>
    /// <param name="duration">The duration in years for the domain registration.</
param>
    /// <returns>The operation Id.</returns>
    public async Task<string?> RegisterDomain(string domainName, bool autoRenew, int
 duration, ContactDetail contact)
    {
        // This example uses the same contact information for admin, registrant, and
 tech contacts.
        try
        {
            var result = await _amazonRoute53Domains.RegisterDomainAsync(
                new RegisterDomainRequest()
                {
                    AdminContact = contact,
                    RegistrantContact = contact,
                    TechContact = contact,
                    DomainName = domainName,
                    AutoRenew = autoRenew,
                    DurationInYears = duration,
                    PrivacyProtectAdminContact = false,
                    PrivacyProtectRegistrantContact = false,
```

```
                    PrivacyProtectTechContact = false
                }
            );
            return result.OperationId;
        }
        catch (InvalidInputException)
        {
            _logger.LogInformation($"Unable to request registration for domain
{domainName}");
            return null;
        }
    }


    /// <summary>
    /// View billing records for the account between a start and end date.
    /// </summary>
    /// <param name="startDate">The start date for billing results.</param>
    /// <param name="endDate">The end date for billing results.</param>
    /// <returns>A collection of billing records.</returns>
    public async Task<List<BillingRecord>> ViewBilling(DateTime startDate, DateTime
endDate)
    {
        var results = new List<BillingRecord>();
        var paginateBilling = _amazonRoute53Domains.Paginators.ViewBilling(
            new ViewBillingRequest()
            {
                Start = startDate,
                End = endDate
            });

        // Get the entire list using the paginator.
        await foreach (var billingRecords in paginateBilling.BillingRecords)
        {
            results.Add(billingRecords);
        }
        return results;
    }


    /// <summary>
    /// List the domains for the account.
    /// </summary>
    /// <returns>A collection of domain summary records.</returns>
```

```
    public async Task<List<DomainSummary>> ListDomains()
    {
        var results = new List<DomainSummary>();
        var paginateDomains = _amazonRoute53Domains.Paginators.ListDomains(
            new ListDomainsRequest());

        // Get the entire list using the paginator.
        await foreach (var domain in paginateDomains.Domains)
        {
            results.Add(domain);
        }
        return results;
    }


    /// <summary>
    /// List operations for the account that are submitted after a specified date.
    /// </summary>
    /// <returns>A collection of operation summary records.</returns>
    public async Task<List<OperationSummary>> ListOperations(DateTime
submittedSince)
    {
        var results = new List<OperationSummary>();
        var paginateOperations = _amazonRoute53Domains.Paginators.ListOperations(
            new ListOperationsRequest()
            {
                SubmittedSince = submittedSince
            });

        // Get the entire list using the paginator.
        await foreach (var operations in paginateOperations.Operations)
        {
            results.Add(operations);
        }
        return results;
    }


    /// <summary>
    /// Get details for a domain.
    /// </summary>
    /// <returns>A string with detail information about the domain.</returns>
    public async Task<string> GetDomainDetail(string domainName)
    {
```

```
        try
        {
            var result = await _amazonRoute53Domains.GetDomainDetailAsync(
                new GetDomainDetailRequest()
                {
                    DomainName = domainName
                });
            var details = $"\tDomain {domainName}:\n" +
                          $"\tCreated on {result.CreationDate.ToShortDateString()}.
\n" +
                          $"\tAdmin contact is {result.AdminContact.Email}.\n" +
                          $"\tAuto-renew is {result.AutoRenew}.\n";

            return details;
        }
        catch (InvalidInputException)
        {
            return $"Domain {domainName} was not found in your account.";
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Exemplos do Amazon S3 usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for .NET com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Adicionar regras de CORS a um bucket

O exemplo de código a seguir mostra como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Add CORS configuration to the Amazon S3 bucket.
        /// </summary>
```

```
        /// <param name="client">The initialized Amazon S3 client object used
        /// to apply the CORS configuration to an Amazon S3 bucket.</param>
        /// <param name="configuration">The CORS configuration to apply.</param>
        private static async Task PutCORSConfigurationAsync(AmazonS3Client client,
CORSConfiguration configuration)
        {
            PutCORSConfigurationRequest request = new PutCORSConfigurationRequest()
            {
                BucketName = BucketName,
                Configuration = configuration,
            };

            _ = await client.PutCORSConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for .NET da API.

Adicionar uma configuração de ciclo de vida a um bucket

O exemplo de código a seguir mostra como adicionar a configuração de ciclo de vida a um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Adds lifecycle configuration information to the S3 bucket named in
        /// the bucketName parameter.
        /// </summary>
        /// <param name="client">The S3 client used to call the
        /// PutLifecycleConfigurationAsync method.</param>
        /// <param name="bucketName">A string representing the S3 bucket to
        /// which configuration information will be added.</param>
```

```
        /// <param name="configuration">A LifecycleConfiguration object that
        /// will be applied to the S3 bucket.</param>
        public static async Task AddExampleLifecycleConfigAsync(IAmazonS3 client,
 string bucketName, LifecycleConfiguration configuration)
        {
            var request = new PutLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
                Configuration = configuration,
            };
            var response = await client.PutLifecycleConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte PutBucketLifecycleConfigurationa Referência AWS SDK for .NET da API.

Cancelar multipart uploads

O exemplo de código a seguir mostra como cancelar multipart uploads.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Transfer;

    /// <summary>
    /// This example shows how to use the Amazon Simple Storage Service
    /// (Amazon S3) to stop a multi-part upload process using the Amazon S3
    /// TransferUtility.
    /// </summary>
    public class AbortMPU
```

```
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";

            // If the AWS Region defined for your default user is different
            // from the Region where your Amazon S3 bucket is located,
            // pass the Region name to the S3 client object's constructor.
            // For example: RegionEndpoint.USWest2.
            IAmazonS3 client = new AmazonS3Client();

            await AbortMPUAsync(client, bucketName);
        }

        /// <summary>
        /// Cancels the multi-part copy process.
        /// </summary>
        /// <param name="client">The initialized client object used to create
        /// the TransferUtility object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the
        /// multi-part copy operation is in progress.</param>
        public static async Task AbortMPUAsync(IAmazonS3 client, string bucketName)
        {
            try
            {
                var transferUtility = new TransferUtility(client);

                // Cancel all in-progress uploads initiated before the specified
date.
                await transferUtility.AbortMultipartUploadsAsync(
                    bucketName, DateTime.Now.AddDays(-7));
            }
            catch (AmazonS3Exception e)
            {
                Console.WriteLine($"Error: {e.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte AbortMultipartUploadsa Referência AWS SDK for .NET da API.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

public class CopyObject
{
    public static async Task Main()
    {
        // Specify the AWS Region where your buckets are located if it is
        // different from the AWS Region of the default user.
        IAmazonS3 s3Client = new AmazonS3Client();

        // Remember to change these values to refer to your Amazon S3 objects.
        string sourceBucketName = "doc-example-bucket1";
        string destinationBucketName = "doc-example-bucket2";
        string sourceObjectKey = "testfile.txt";
        string destinationObjectKey = "testfilecopy.txt";

        Console.WriteLine($"Copying {sourceObjectKey} from {sourceBucketName} to
");
        Console.WriteLine($"{destinationBucketName} as {destinationObjectKey}");

        var response = await CopyingObjectAsync(
            s3Client,
            sourceObjectKey,
            destinationObjectKey,
            sourceBucketName,
            destinationBucketName);

        if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
```

```
            {
                Console.WriteLine("\nCopy complete.");
            }
        }

        /// <summary>
        /// This method calls the AWS SDK for .NET to copy an
        /// object from one Amazon S3 bucket to another.
        /// </summary>
        /// <param name="client">The Amazon S3 client object.</param>
        /// <param name="sourceKey">The name of the object to be copied.</param>
        /// <param name="destinationKey">The name under which to save the copy.</
param>
        /// <param name="sourceBucketName">The name of the Amazon S3 bucket
        /// where the file is located now.</param>
        /// <param name="destinationBucketName">The name of the Amazon S3
        /// bucket where the copy should be saved.</param>
        /// <returns>Returns a CopyObjectResponse object with the results from
        /// the async call.</returns>
        public static async Task<CopyObjectResponse> CopyingObjectAsync(
            IAmazonS3 client,
            string sourceKey,
            string destinationKey,
            string sourceBucketName,
            string destinationBucketName)
        {
            var response = new CopyObjectResponse();
            try
            {
                var request = new CopyObjectRequest
                {
                    SourceBucket = sourceBucketName,
                    SourceKey = sourceKey,
                    DestinationBucket = destinationBucketName,
                    DestinationKey = destinationKey,
                };
                response = await client.CopyObjectAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error copying object: '{ex.Message}'");
            }

            return response;
```

```
        }
    }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for .NET da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to create a new Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket to create.</param>
        /// <returns>A boolean value representing the success or failure of
        /// the bucket creation process.</returns>
        public static async Task<bool> CreateBucketAsync(IAmazonS3 client, string
bucketName)
        {
            try
            {
                var request = new PutBucketRequest
                {
                    BucketName = bucketName,
                    UseClientRegion = true,
                };

                var response = await client.PutBucketAsync(request);
                return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
            }
```

```
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error creating bucket: '{ex.Message}'");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for .NET da API.

Excluir regras de CORS de um bucket

O exemplo de código a seguir mostra como excluir regras de CORS de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Deletes a CORS configuration from an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to delete the CORS configuration from the bucket.</param>
        private static async Task DeleteCORSConfigurationAsync(AmazonS3Client
client)
        {
            DeleteCORSConfigurationRequest request = new
DeleteCORSConfigurationRequest()
            {
                BucketName = BucketName,
            };
            await client.DeleteCORSConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte DeleteBucketCorsa Referência AWS SDK for .NET da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to delete an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to delete.</
param>
        /// <returns>A boolean value that represents the success or failure of
        /// the delete operation.</returns>
        public static async Task<bool> DeleteBucketAsync(IAmazonS3 client, string
 bucketName)
        {
            var request = new DeleteBucketRequest
            {
                BucketName = bucketName,
            };

            var response = await client.DeleteBucketAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for .NET da API.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto de um bucket do S3 sem versionamento.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to delete an object from a non-versioned Amazon
/// Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class DeleteObject
{
    /// <summary>
    /// The Main method initializes the necessary variables and then calls
    /// the DeleteObjectNonVersionedBucketAsync method to delete the object
    /// named by the keyName parameter.
    /// </summary>
    public static async Task Main()
    {
        const string bucketName = "doc-example-bucket";
        const string keyName = "testfile.txt";

        // If the Amazon S3 bucket is located in an AWS Region other than the
        // Region of the default account, define the AWS Region for the
        // Amazon S3 bucket in your call to the AmazonS3Client constructor.
        // For example RegionEndpoint.USWest2.
        IAmazonS3 client = new AmazonS3Client();
        await DeleteObjectNonVersionedBucketAsync(client, bucketName, keyName);
    }
```

```
        /// <summary>
        /// The DeleteObjectNonVersionedBucketAsync takes care of deleting the
        /// desired object from the named bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client used to delete
        /// an object from an Amazon S3 bucket.</param>
        /// <param name="bucketName">The name of the bucket from which the
        /// object will be deleted.</param>
        /// <param name="keyName">The name of the object to delete.</param>
        public static async Task DeleteObjectNonVersionedBucketAsync(IAmazonS3
 client, string bucketName, string keyName)
        {
            try
            {
                var deleteObjectRequest = new DeleteObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                };

                Console.WriteLine($"Deleting object: {keyName}");
                await client.DeleteObjectAsync(deleteObjectRequest);
                Console.WriteLine($"Object: {keyName} deleted from {bucketName}.");
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error encountered on server.
 Message:'{ex.Message}' when deleting an object.");
            }
        }
    }
```

Exclua um objeto de um bucket do S3 com versionamento.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example creates an object in an Amazon Simple Storage Service
```

```
    /// (Amazon S3) bucket and then deletes the object version that was
    /// created.
    /// </summary>
    public class DeleteObjectVersion
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "verstioned-object.txt";

            // If the AWS Region of the default user is different from the AWS
            // Region of the Amazon S3 bucket, pass the AWS Region of the
            // bucket region to the Amazon S3 client object's constructor.
            // Define it like this:
            //      RegionEndpoint bucketRegion = RegionEndpoint.USWest2;
            IAmazonS3 client = new AmazonS3Client();

            await CreateAndDeleteObjectVersionAsync(client, bucketName, keyName);
        }

        /// <summary>
        /// This method creates and then deletes a versioned object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
        /// create and delete the object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
        /// object will be created and deleted.</param>
        /// <param name="keyName">The key name of the object to create.</param>
        public static async Task CreateAndDeleteObjectVersionAsync(IAmazonS3 client,
string bucketName, string keyName)
        {
            try
            {
                // Add a sample object.
                string versionID = await PutAnObject(client, bucketName, keyName);

                // Delete the object by specifying an object key and a version ID.
                DeleteObjectRequest request = new DeleteObjectRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                    VersionId = versionID,
                };
```

```
                Console.WriteLine("Deleting an object");
                await client.DeleteObjectAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }

        /// <summary>
        /// This method is used to create the temporary Amazon S3 object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 object which will be used
        /// to create the temporary Amazon S3 object.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
 object
        /// will be created.</param>
        /// <param name="objectKey">The name of the Amazon S3 object co create.</
param>
        /// <returns>The Version ID of the created object.</returns>
        public static async Task<string> PutAnObject(IAmazonS3 client, string
 bucketName, string objectKey)
        {
            PutObjectRequest request = new PutObjectRequest()
            {
                BucketName = bucketName,
                Key = objectKey,
                ContentBody = "This is the content body!",
            };

            PutObjectResponse response = await client.PutObjectAsync(request);
            return response.VersionId;
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for .NET da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua todos os objetos de um bucket do S3.

```
        /// <summary>
        /// Delete all of the objects stored in an existing Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket from which the
        /// contents will be deleted.</param>
        /// <returns>A boolean value that represents the success or failure of
        /// deleting all of the objects in the bucket.</returns>
        public static async Task<bool> DeleteBucketContentsAsync(IAmazonS3 client,
string bucketName)
        {
            // Iterate over the contents of the bucket and delete all objects.
            var request = new ListObjectsV2Request
            {
                BucketName = bucketName,
            };

            try
            {
                ListObjectsV2Response response;

                do
                {
                    response = await client.ListObjectsV2Async(request);
                    response.S3Objects
                        .ForEach(async obj => await
client.DeleteObjectAsync(bucketName, obj.Key));

                    // If the response is truncated, set the request
ContinuationToken
                    // from the NextContinuationToken property of the response.
                    request.ContinuationToken = response.NextContinuationToken;
```

```
                }
                while (response.IsTruncated);

                return true;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error deleting objects: {ex.Message}");
                return false;
            }
        }
```

Exclua vários objetos de um bucket do S3 sem versionamento.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to delete multiple objects from an Amazon Simple
    /// Storage Service (Amazon S3) bucket.
    /// </summary>
    public class DeleteMultipleObjects
    {
        /// <summary>
        /// The Main method initializes the Amazon S3 client and the name of
        /// the bucket and then passes those values to MultiObjectDeleteAsync.
        /// </summary>
        public static async Task Main()
        {
            const string bucketName = "doc-example-bucket";

            // If the Amazon S3 bucket from which you wish to delete objects is not
            // located in the same AWS Region as the default user, define the
            // AWS Region for the Amazon S3 bucket as a parameter to the client
            // constructor.
            IAmazonS3 s3Client = new AmazonS3Client();

            await MultiObjectDeleteAsync(s3Client, bucketName);
```

```
        }

        /// <summary>
        /// This method uses the passed Amazon S3 client to first create and then
        /// delete three files from the named bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// Amazon S3 methods.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where objects
        /// will be created and then deleted.</param>
        public static async Task MultiObjectDeleteAsync(IAmazonS3 client, string
bucketName)
        {
            // Create three sample objects which we will then delete.
            var keysAndVersions = await PutObjectsAsync(client, 3, bucketName);

            // Now perform the multi-object delete, passing the key names and
            // version IDs. Since we are working with a non-versioned bucket,
            // the object keys collection includes null version IDs.
            DeleteObjectsRequest multiObjectDeleteRequest = new DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keysAndVersions,
            };

            // You can add a specific object key to the delete request using the
            // AddKey method of the multiObjectDeleteRequest.
            try
            {
                DeleteObjectsResponse response = await
client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine("Successfully deleted all the {0} items",
response.DeletedObjects.Count);
            }
            catch (DeleteObjectsException e)
            {
                PrintDeletionErrorStatus(e);
            }
        }

        /// <summary>
        /// Prints the list of errors raised by the call to DeleteObjectsAsync.
        /// </summary>
```

```
        /// <param name="ex">A collection of exceptions returned by the call to
        /// DeleteObjectsAsync.</param>
        public static void PrintDeletionErrorStatus(DeleteObjectsException ex)
        {
            DeleteObjectsResponse errorResponse = ex.Response;
            Console.WriteLine("x {0}", errorResponse.DeletedObjects.Count);

            Console.WriteLine($"Successfully deleted
 {errorResponse.DeletedObjects.Count}.");
            Console.WriteLine($"No. of objects failed to delete =
 {errorResponse.DeleteErrors.Count}");

            Console.WriteLine("Printing error data...");
            foreach (DeleteError deleteError in errorResponse.DeleteErrors)
            {
                Console.WriteLine($"Object Key:
 {deleteError.Key}\t{deleteError.Code}\t{deleteError.Message}");
            }
        }

        /// <summary>
        /// This method creates simple text file objects that can be used in
        /// the delete method.
        /// </summary>
        /// <param name="client">The Amazon S3 client used to call PutObjectAsync.</
param>
        /// <param name="number">The number of objects to create.</param>
        /// <param name="bucketName">The name of the bucket where the objects
        /// will be created.</param>
        /// <returns>A list of keys (object keys) and versions that the calling
        /// method will use to delete the newly created files.</returns>
        public static async Task<List<KeyVersion>> PutObjectsAsync(IAmazonS3 client,
 int number, string bucketName)
        {
            List<KeyVersion> keys = new List<KeyVersion>();
            for (int i = 0; i < number; i++)
            {
                string key = "ExampleObject-" + new System.Random().Next();
                PutObjectRequest request = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = key,
                    ContentBody = "This is the content body!",
                };
```

```
            PutObjectResponse response = await client.PutObjectAsync(request);

            // For non-versioned bucket operations, we only need the
            // object key.
            KeyVersion keyVersion = new KeyVersion
            {
                Key = key,
            };
            keys.Add(keyVersion);
        }

        return keys;
    }
}
```

Exclua vários objetos de um bucket do S3 com versionamento.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to delete objects in a version-enabled Amazon
/// Simple StorageService (Amazon S3) bucket.
/// </summary>
public class DeleteMultipleObjects
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";

        // If the AWS Region for your Amazon S3 bucket is different from
        // the AWS Region of the default user, define the AWS Region for
        // the Amazon S3 bucket and pass it to the client constructor
        // like this:
        // RegionEndpoint bucketRegion = RegionEndpoint.USWest2;
        IAmazonS3 s3Client;
```

```
            s3Client = new AmazonS3Client();
            await DeleteMultipleObjectsFromVersionedBucketAsync(s3Client,
bucketName);
        }

        /// <summary>
        /// This method removes multiple versions and objects from a
        /// version-enabled Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        public static async Task
DeleteMultipleObjectsFromVersionedBucketAsync(IAmazonS3 client, string bucketName)
        {
            // Delete objects (specifying object version in the request).
            await DeleteObjectVersionsAsync(client, bucketName);

            // Delete objects (without specifying object version in the request).
            var deletedObjects = await DeleteObjectsAsync(client, bucketName);

            // Additional exercise - remove the delete markers Amazon S3 returned
from
            // the preceding response. This results in the objects reappearing
            // in the bucket (you can verify the appearance/disappearance of
            // objects in the console).
            await RemoveDeleteMarkersAsync(client, bucketName, deletedObjects);
        }

        /// <summary>
        /// Creates and then deletes non-versioned Amazon S3 objects and then
deletes
        /// them again. The method returns a list of the Amazon S3 objects deleted.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// PubObjectsAsync and NonVersionedDeleteAsync.</param>
        /// <param name="bucketName">The name of the bucket where the objects
        /// will be created and then deleted.</param>
        /// <returns>A list of DeletedObjects.</returns>
```

```
        public static async Task<List<DeletedObject>> DeleteObjectsAsync(IAmazonS3
client, string bucketName)
        {
            // Upload the sample objects.
            var keysAndVersions2 = await PutObjectsAsync(client, bucketName, 3);

            // Delete objects using only keys. Amazon S3 creates a delete marker and
            // returns its version ID in the response.
            List<DeletedObject> deletedObjects = await
NonVersionedDeleteAsync(client, bucketName, keysAndVersions2);
            return deletedObjects;
        }

        /// <summary>
        /// This method creates several temporary objects and then deletes them.
        /// </summary>
        /// <param name="client">The S3 client.</param>
        /// <param name="bucketName">Name of the bucket.</param>
        /// <returns>Async task.</returns>
        public static async Task DeleteObjectVersionsAsync(IAmazonS3 client, string
bucketName)
        {
            // Upload the sample objects.
            var keysAndVersions1 = await PutObjectsAsync(client, bucketName, 3);

            // Delete the specific object versions.
            await VersionedDeleteAsync(client, bucketName, keysAndVersions1);
        }

        /// <summary>
        /// Displays the list of information about deleted files to the console.
        /// </summary>
        /// <param name="e">Error information from the delete process.</param>
        private static void DisplayDeletionErrors(DeleteObjectsException e)
        {
            var errorResponse = e.Response;
            Console.WriteLine($"No. of objects successfully deleted =
{errorResponse.DeletedObjects.Count}");
            Console.WriteLine($"No. of objects failed to delete =
{errorResponse.DeleteErrors.Count}");
            Console.WriteLine("Printing error data...");
            foreach (var deleteError in errorResponse.DeleteErrors)
            {
```

```
                Console.WriteLine($"Object Key:
 {deleteError.Key}\t{deleteError.Code}\t{deleteError.Message}");
            }
        }

        /// <summary>
        /// Delete multiple objects from a version-enabled bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="keys">A list of key names for the objects to delete.</
param>
        private static async Task VersionedDeleteAsync(IAmazonS3 client, string
 bucketName, List<KeyVersion> keys)
        {
            var multiObjectDeleteRequest = new DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keys, // This includes the object keys and specific
 version IDs.
            };

            try
            {
                Console.WriteLine("Executing VersionedDelete...");
                DeleteObjectsResponse response = await
 client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine($"Successfully deleted all the
 {response.DeletedObjects.Count} items");
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
            }
        }

        /// <summary>
        /// Deletes multiple objects from a non-versioned Amazon S3 bucket.
        /// </summary>
```

```
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="keys">A list of key names for the objects to delete.</
param>
        /// <returns>A list of the deleted objects.</returns>
        private static async Task<List<DeletedObject>>
 NonVersionedDeleteAsync(IAmazonS3 client, string bucketName, List<KeyVersion> keys)
        {
            // Create a request that includes only the object key names.
            DeleteObjectsRequest multiObjectDeleteRequest = new
 DeleteObjectsRequest();
            multiObjectDeleteRequest.BucketName = bucketName;

            foreach (var key in keys)
            {
                multiObjectDeleteRequest.AddKey(key.Key);
            }

            // Execute DeleteObjectsAsync.
            // The DeleteObjectsAsync method adds a delete marker for each
            // object deleted. You can verify that the objects were removed
            // using the Amazon S3 console.
            DeleteObjectsResponse response;
            try
            {
                Console.WriteLine("Executing NonVersionedDelete...");
                response = await
 client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine("Successfully deleted all the {0} items",
 response.DeletedObjects.Count);
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
                throw; // Some deletions failed. Investigate before continuing.
            }

            // This response contains the DeletedObjects list which we use to delete
 the delete markers.
            return response.DeletedObjects;
```

```
        }

        /// <summary>
        /// Deletes the markers left after deleting the temporary objects.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// DeleteObjectVersionsAsync, DeleteObjectsAsync, and
        /// RemoveDeleteMarkersAsync.</param>
        /// <param name="bucketName">The name of the bucket from which to delete
        /// objects.</param>
        /// <param name="deletedObjects">A list of the objects that were deleted.</
param>
        private static async Task RemoveDeleteMarkersAsync(IAmazonS3 client, string
 bucketName, List<DeletedObject> deletedObjects)
        {
            var keyVersionList = new List<KeyVersion>();

            foreach (var deletedObject in deletedObjects)
            {
                KeyVersion keyVersion = new KeyVersion
                {
                    Key = deletedObject.Key,
                    VersionId = deletedObject.DeleteMarkerVersionId,
                };
                keyVersionList.Add(keyVersion);
            }

            // Create another request to delete the delete markers.
            var multiObjectDeleteRequest = new DeleteObjectsRequest
            {
                BucketName = bucketName,
                Objects = keyVersionList,
            };

            // Now, delete the delete marker to bring your objects back to the
 bucket.
            try
            {
                Console.WriteLine("Removing the delete markers .....");
                var deleteObjectResponse = await
 client.DeleteObjectsAsync(multiObjectDeleteRequest);
                Console.WriteLine($"Successfully deleted the
 {deleteObjectResponse.DeletedObjects.Count} delete markers");
```

```
            }
            catch (DeleteObjectsException ex)
            {
                DisplayDeletionErrors(ex);
            }
        }

        /// <summary>
        /// Create temporary Amazon S3 objects to show how object deletion wors in
an
        /// Amazon S3 bucket with versioning enabled.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// PutObjectAsync to create temporary objects for the example.</param>
        /// <param name="bucketName">A string representing the name of the S3
        /// bucket where we will create the temporary objects.</param>
        /// <param name="number">The number of temporary objects to create.</param>
        /// <returns>A list of the KeyVersion objects.</returns>
        private static async Task<List<KeyVersion>> PutObjectsAsync(IAmazonS3
client, string bucketName, int number)
        {
            var keys = new List<KeyVersion>();

            for (var i = 0; i < number; i++)
            {
                string key = "ObjectToDelete-" + new System.Random().Next();
                PutObjectRequest request = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = key,
                    ContentBody = "This is the content body!",
                };

                var response = await client.PutObjectAsync(request);
                KeyVersion keyVersion = new KeyVersion
                {
                    Key = key,
                    VersionId = response.VersionId,
                };

                keys.Add(keyVersion);
            }
```

```
            return keys;
        }
    }
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for .NET da API.

Excluir a configuração de ciclo de vida de um bucket

O exemplo de código a seguir mostra como excluir a configuração de ciclo de vida de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// This method removes the Lifecycle configuration from the named
        /// S3 bucket.
        /// </summary>
        /// <param name="client">The S3 client object used to call
        /// the RemoveLifecycleConfigAsync method.</param>
        /// <param name="bucketName">A string representing the name of the
        /// S3 bucket from which the configuration will be removed.</param>
        public static async Task RemoveLifecycleConfigAsync(IAmazonS3 client, string
bucketName)
        {
            var request = new DeleteLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
            };
            await client.DeleteLifecycleConfigurationAsync(request);
        }
```

- Para obter detalhes da API, consulte DeleteBucketLifecyclea Referência AWS SDK for .NET da API.

Habilitar registro em log

O exemplo de código a seguir mostra como habilitar o registro em log em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;
using Microsoft.Extensions.Configuration;

/// <summary>
/// This example shows how to enable logging on an Amazon Simple Storage
/// Service (Amazon S3) bucket. You need to have two Amazon S3 buckets for
/// this example. The first is the bucket for which you wish to enable
/// logging, and the second is the location where you want to store the
/// logs.
/// </summary>
public class ServerAccessLogging
{
    private static IConfiguration _configuration = null!;

    public static async Task Main()
    {
        LoadConfig();

        string bucketName = _configuration["BucketName"];
        string logBucketName = _configuration["LogBucketName"];
        string logObjectKeyPrefix = _configuration["LogObjectKeyPrefix"];
        string accountId = _configuration["AccountId"];
```

```
            // If the AWS Region defined for your default user is different
            // from the Region where your Amazon S3 bucket is located,
            // pass the Region name to the Amazon S3 client object's constructor.
            // For example: RegionEndpoint.USWest2 or RegionEndpoint.USEast2.
            IAmazonS3 client = new AmazonS3Client();

            try
            {
                // Update bucket policy for target bucket to allow delivery of logs
to it.
                await SetBucketPolicyToAllowLogDelivery(
                    client,
                    bucketName,
                    logBucketName,
                    logObjectKeyPrefix,
                    accountId);

                // Enable logging on the source bucket.
                await EnableLoggingAsync(
                    client,
                    bucketName,
                    logBucketName,
                    logObjectKeyPrefix);
            }
            catch (AmazonS3Exception e)
            {
                Console.WriteLine($"Error: {e.Message}");
            }
        }

        /// <summary>
        /// This method grants appropriate permissions for logging to the
        /// Amazon S3 bucket where the logs will be stored.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client which will be used
        /// to apply the bucket policy.</param>
        /// <param name="sourceBucketName">The name of the source bucket.</param>
        /// <param name="logBucketName">The name of the bucket where logging
        /// information will be stored.</param>
        /// <param name="logPrefix">The logging prefix where the logs should be
delivered.</param>
        /// <param name="accountId">The account id of the account where the source
bucket exists.</param>
        /// <returns>Async task.</returns>
```

```
        public static async Task SetBucketPolicyToAllowLogDelivery(
            IAmazonS3 client,
            string sourceBucketName,
            string logBucketName,
            string logPrefix,
            string accountId)
        {
            var resourceArn = @"""arn:aws:s3:::" + logBucketName + "/" + logPrefix +
@"*""";

            var newPolicy = @"{
                                ""Statement"":[{
                                ""Sid"": ""S3ServerAccessLogsPolicy"",
                                ""Effect"": ""Allow"",
                                ""Principal"": { ""Service"":
""logging.s3.amazonaws.com"" },
                                ""Action"": [""s3:PutObject""],
                                ""Resource"": [" + resourceArn + @"],
                                ""Condition"": {
                                ""ArnLike"": { ""aws:SourceArn"": ""arn:aws:s3:::" +
sourceBucketName + @""" },
                                ""StringEquals"": { ""aws:SourceAccount"": """ +
accountId + @""" }
                                        }
                                    }]
                                }";
            Console.WriteLine($"The policy to apply to bucket {logBucketName} to
enable logging:");
            Console.WriteLine(newPolicy);

            PutBucketPolicyRequest putRequest = new PutBucketPolicyRequest
            {
                BucketName = logBucketName,
                Policy = newPolicy,
            };
            await client.PutBucketPolicyAsync(putRequest);
            Console.WriteLine("Policy applied.");
        }

        /// <summary>
        /// This method enables logging for an Amazon S3 bucket. Logs will be stored
        /// in the bucket you selected for logging. Selected prefix
        /// will be prepended to each log object.
        /// </summary>
```

```
        /// <param name="client">The initialized Amazon S3 client which will be used
        /// to configure and apply logging to the selected Amazon S3 bucket.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket for which you
        /// wish to enable logging.</param>
        /// <param name="logBucketName">The name of the Amazon S3 bucket where
logging
        /// information will be stored.</param>
        /// <param name="logObjectKeyPrefix">The prefix to prepend to each
        /// object key.</param>
        /// <returns>Async task.</returns>
        public static async Task EnableLoggingAsync(
            IAmazonS3 client,
            string bucketName,
            string logBucketName,
            string logObjectKeyPrefix)
        {
            Console.WriteLine($"Enabling logging for bucket {bucketName}.");
            var loggingConfig = new S3BucketLoggingConfig
            {
                TargetBucketName = logBucketName,
                TargetPrefix = logObjectKeyPrefix,
            };

            var putBucketLoggingRequest = new PutBucketLoggingRequest
            {
                BucketName = bucketName,
                LoggingConfig = loggingConfig,
            };
            await client.PutBucketLoggingAsync(putBucketLoggingRequest);
            Console.WriteLine($"Logging enabled.");
        }

        /// <summary>
        /// Loads configuration from settings files.
        /// </summary>
        public static void LoadConfig()
        {
            _configuration = new ConfigurationBuilder()
                .SetBasePath(Directory.GetCurrentDirectory())
                .AddJsonFile("settings.json") // Load settings from .json file.
                .AddJsonFile("settings.local.json", true) // Optionally, load local
settings.
                .Build();
        }
```

```
    }
```

- Para obter detalhes da API, consulte PutBucketLoggingga Referência AWS SDK for .NET da API.

Habilitar notificações

O exemplo de código a seguir mostra como habilitar notificações para um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to enable notifications for an Amazon Simple
    /// Storage Service (Amazon S3) bucket.
    /// </summary>
    public class EnableNotifications
    {
        public static async Task Main()
        {
            const string bucketName = "doc-example-bucket1";
            const string snsTopic = "arn:aws:sns:us-east-2:0123456789ab:bucket-
notify";
            const string sqsQueue = "arn:aws:sqs:us-
east-2:0123456789ab:Example_Queue";

            IAmazonS3 client = new AmazonS3Client(Amazon.RegionEndpoint.USEast2);
            await EnableNotificationAsync(client, bucketName, snsTopic, sqsQueue);
        }
```

```
        /// <summary>
        /// This method makes the call to the PutBucketNotificationAsync method.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client used to call
        /// the PutBucketNotificationAsync method.</param>
        /// <param name="bucketName">The name of the bucket for which
        /// notifications will be turned on.</param>
        /// <param name="snsTopic">The ARN for the Amazon Simple Notification
        /// Service (Amazon SNS) topic associated with the S3 bucket.</param>
        /// <param name="sqsQueue">The ARN of the Amazon Simple Queue Service
        /// (Amazon SQS) queue to which notifications will be pushed.</param>
        public static async Task EnableNotificationAsync(
            IAmazonS3 client,
            string bucketName,
            string snsTopic,
            string sqsQueue)
        {
            try
            {
                // The bucket for which we are setting up notifications.
                var request = new PutBucketNotificationRequest()
                {
                    BucketName = bucketName,
                };

                // Defines the topic to use when sending a notification.
                var topicConfig = new TopicConfiguration()
                {
                    Events = new List<EventType> { EventType.ObjectCreatedCopy },
                    Topic = snsTopic,
                };
                request.TopicConfigurations = new List<TopicConfiguration>
                {
                    topicConfig,
                };
                request.QueueConfigurations = new List<QueueConfiguration>
                {
                    new QueueConfiguration()
                    {
                        Events = new List<EventType> { EventType.ObjectCreatedPut },
                        Queue = sqsQueue,
                    },
                };
```

```
                // Now apply the notification settings to the bucket.
                PutBucketNotificationResponse response = await
client.PutBucketNotificationAsync(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutBucketNotificationConfigurationa Referência AWS SDK for .NET da API.

Habilitar a aceleração de transferência

O exemplo a seguir mostra como habilitar a aceleração de transferência para um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// Amazon Simple Storage Service (Amazon S3) Transfer Acceleration is a
/// bucket-level feature that enables you to perform faster data transfers
/// to Amazon S3. This example shows how to configure Transfer
/// Acceleration.
/// </summary>
public class TransferAcceleration
{
```

```
        /// <summary>
        /// The main method initializes the client object and sets the
        /// Amazon Simple Storage Service (Amazon S3) bucket name before
        /// calling EnableAccelerationAsync.
        /// </summary>
        public static async Task Main()
        {
            var s3Client = new AmazonS3Client();
            const string bucketName = "doc-example-bucket";

            await EnableAccelerationAsync(s3Client, bucketName);
        }

        /// <summary>
        /// This method sets the configuration to enable transfer acceleration
        /// for the bucket referred to in the bucketName parameter.
        /// </summary>
        /// <param name="client">An Amazon S3 client used to enable the
        /// acceleration on an Amazon S3 bucket.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket for which the
        /// method will be enabling acceleration.</param>
        private static async Task EnableAccelerationAsync(AmazonS3Client client,
string bucketName)
        {
            try
            {
                var putRequest = new PutBucketAccelerateConfigurationRequest
                {
                    BucketName = bucketName,
                    AccelerateConfiguration = new AccelerateConfiguration
                    {
                        Status = BucketAccelerateStatus.Enabled,
                    },
                };
                await client.PutBucketAccelerateConfigurationAsync(putRequest);

                var getRequest = new GetBucketAccelerateConfigurationRequest
                {
                    BucketName = bucketName,
                };
                var response = await
client.GetBucketAccelerateConfigurationAsync(getRequest);

                Console.WriteLine($"Acceleration state = '{response.Status}' ");
```

```
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error occurred. Message:'{ex.Message}' when
setting transfer acceleration");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutBucketAccelerateConfigurationa Referência AWS SDK for .NET da API.

Obter regras de CORS para um bucket

O exemplos de código a seguir mostra como obter regras de compartilhamento de recursos de origem cruzada (CORS) para um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Retrieve the CORS configuration applied to the Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to retrieve the CORS configuration.</param>
        /// <returns>The created CORS configuration object.</returns>
        private static async Task<CORSConfiguration>
RetrieveCORSConfigurationAsync(AmazonS3Client client)
        {
            GetCORSConfigurationRequest request = new GetCORSConfigurationRequest()
            {
                BucketName = BucketName,
            };
```

```
        var response = await client.GetCORSConfigurationAsync(request);
        var configuration = response.Configuration;
        PrintCORSRules(configuration);
        return configuration;
    }
```

- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for .NET da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Shows how to download an object from an Amazon S3 bucket to the
    /// local computer.
    /// </summary>
    /// <param name="client">An initialized Amazon S3 client object.</param>
    /// <param name="bucketName">The name of the bucket where the object is
    /// currently stored.</param>
    /// <param name="objectName">The name of the object to download.</param>
    /// <param name="filePath">The path, including filename, where the
    /// downloaded object will be stored.</param>
    /// <returns>A boolean value indicating the success or failure of the
    /// download process.</returns>
    public static async Task<bool> DownloadObjectFromBucketAsync(
        IAmazonS3 client,
        string bucketName,
        string objectName,
        string filePath)
    {
        // Create a GetObject request
```

```
            var request = new GetObjectRequest
            {
                BucketName = bucketName,
                Key = objectName,
            };

            // Issue request and remember to dispose of the response
            using GetObjectResponse response = await client.GetObjectAsync(request);

            try
            {
                // Save object to local file
                await response.WriteResponseStreamToFileAsync($"{filePath}\
\{objectName}", true, CancellationToken.None);
                return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error saving {objectName}: {ex.Message}");
                return false;
            }
        }
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for .NET da API.

Obter a ACL de um bucket

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Get the access control list (ACL) for the new bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to get the
        /// access control list (ACL) of the bucket.</param>
        /// <param name="newBucketName">The name of the newly created bucket.</
param>
        /// <returns>An S3AccessControlList.</returns>
        public static async Task<S3AccessControlList> GetACLForBucketAsync(IAmazonS3
 client, string newBucketName)
        {
            // Retrieve bucket ACL to show that the ACL was properly applied to
            // the new bucket.
            GetACLResponse getACLResponse = await client.GetACLAsync(new
 GetACLRequest
            {
                BucketName = newBucketName,
            });

            return getACLResponse.AccessControlList;
        }
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for .NET da API.

Obter a configuração de ciclo de vida de um bucket

O exemplo de código a seguir mostra como obter a configuração de ciclo de vida de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
```

```
        /// Returns a configuration object for the supplied bucket name.
        /// </summary>
        /// <param name="client">The S3 client object used to call
        /// the GetLifecycleConfigurationAsync method.</param>
        /// <param name="bucketName">The name of the S3 bucket for which a
        /// configuration will be created.</param>
        /// <returns>Returns a new LifecycleConfiguration object.</returns>
        public static async Task<LifecycleConfiguration>
RetrieveLifecycleConfigAsync(IAmazonS3 client, string bucketName)
        {
            var request = new GetLifecycleConfigurationRequest()
            {
                BucketName = bucketName,
            };
            var response = await client.GetLifecycleConfigurationAsync(request);
            var configuration = response.Configuration;
            return configuration;
        }
```

- Para obter detalhes da API, consulte GetBucketLifecycleConfigurationa Referência AWS SDK for .NET da API.

Obter a configuração do site de um bucket

O exemplo de código a seguir mostra como obter a configuração de site de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
                // Get the website configuration.
                GetBucketWebsiteRequest getRequest = new GetBucketWebsiteRequest()
                {
                    BucketName = bucketName,
                };
```

```
                GetBucketWebsiteResponse getResponse = await
 client.GetBucketWebsiteAsync(getRequest);
                Console.WriteLine($"Index document:
 {getResponse.WebsiteConfiguration.IndexDocumentSuffix}");
                Console.WriteLine($"Error document:
 {getResponse.WebsiteConfiguration.ErrorDocument}");
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for .NET da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace ListBucketsExample
{
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example uses the AWS SDK for .NET to list the Amazon Simple Storage
    /// Service (Amazon S3) buckets belonging to the default account.
    /// </summary>
    public class ListBuckets
    {
        private static IAmazonS3 _s3Client;

        /// <summary>
```

```
        /// Get a list of the buckets owned by the default user.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <returns>The response from the ListingBuckets call that contains a
        /// list of the buckets owned by the default user.</returns>
        public static async Task<ListBucketsResponse> GetBuckets(IAmazonS3 client)
        {
            return await client.ListBucketsAsync();
        }

        /// <summary>
        /// This method lists the name and creation date for the buckets in
        /// the passed List of S3 buckets.
        /// </summary>
        /// <param name="bucketList">A List of S3 bucket objects.</param>
        public static void DisplayBucketList(List<S3Bucket> bucketList)
        {
            bucketList
                .ForEach(b => Console.WriteLine($"Bucket name: {b.BucketName},
 created on: {b.CreationDate}"));
        }

        public static async Task Main()
        {
            // The client uses the AWS Region of the default user.
            // If the Region where the buckets were created is different,
            // pass the Region to the client constructor. For example:
            // _s3Client = new AmazonS3Client(RegionEndpoint.USEast1);
            _s3Client = new AmazonS3Client();
            var response = await GetBuckets(_s3Client);
            DisplayBucketList(response.Buckets);
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for .NET da API.

Listar as versões de objeto em um bucket

O exemplo de código a seguir mostra como listar versões de objeto em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example lists the versions of the objects in a version enabled
    /// Amazon Simple Storage Service (Amazon S3) bucket.
    /// </summary>
    public class ListObjectVersions
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";

            // If the AWS Region where your bucket is defined is different from
            // the AWS Region where the Amazon S3 bucket is defined, pass the
 constant
            // for the AWS Region to the client constructor like this:
            //      var client = new AmazonS3Client(RegionEndpoint.USWest2);
            IAmazonS3 client = new AmazonS3Client();
            await GetObjectListWithAllVersionsAsync(client, bucketName);
        }

        /// <summary>
        /// This method lists all versions of the objects within an Amazon S3
        /// version enabled bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// ListVersionsAsync.</param>
        /// <param name="bucketName">The name of the version enabled Amazon S3
 bucket
        /// for which you want to list the versions of the contained objects.</
param>
```

```
        public static async Task GetObjectListWithAllVersionsAsync(IAmazonS3 client,
string bucketName)
        {
            try
            {
                // When you instantiate the ListVersionRequest, you can
                // optionally specify a key name prefix in the request
                // if you want a list of object versions of a specific object.

                // For this example we set a small limit in MaxKeys to return
                // a small list of versions.
                ListVersionsRequest request = new ListVersionsRequest()
                {
                    BucketName = bucketName,
                    MaxKeys = 2,
                };

                do
                {
                    ListVersionsResponse response = await
client.ListVersionsAsync(request);

                    // Process response.
                    foreach (S3ObjectVersion entry in response.Versions)
                    {
                        Console.WriteLine($"key: {entry.Key} size: {entry.Size}");
                    }

                    // If response is truncated, set the marker to get the next
                    // set of keys.
                    if (response.IsTruncated)
                    {
                        request.KeyMarker = response.NextKeyMarker;
                        request.VersionIdMarker = response.NextVersionIdMarker;
                    }
                    else
                    {
                        request = null;
                    }
                }
                while (request != null);
            }
            catch (AmazonS3Exception ex)
            {
```

```
                Console.WriteLine($"Error: '{ex.Message}'");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListObjectVersionsa Referência AWS SDK for .NET da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to list the objects in an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the bucket for which to list
        /// the contents.</param>
        /// <returns>A boolean value indicating the success or failure of the
        /// copy operation.</returns>
        public static async Task<bool> ListBucketContentsAsync(IAmazonS3 client,
string bucketName)
        {
            try
            {
                var request = new ListObjectsV2Request
                {
                    BucketName = bucketName,
                    MaxKeys = 5,
                };
```

```
                Console.WriteLine("--------------------------------------");
                Console.WriteLine($"Listing the contents of {bucketName}:");
                Console.WriteLine("--------------------------------------");

                ListObjectsV2Response response;

                do
                {
                    response = await client.ListObjectsV2Async(request);

                    response.S3Objects
                        .ForEach(obj => Console.WriteLine($"{obj.Key,-35}
{obj.LastModified.ToShortDateString(),10}{obj.Size,10}"));

                    // If the response is truncated, set the request
 ContinuationToken
                    // from the NextContinuationToken property of the response.
                    request.ContinuationToken = response.NextContinuationToken;
                }
                while (response.IsTruncated);

                return true;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error encountered on server.
 Message:'{ex.Message}' getting list of objects.");
                return false;
            }
        }
```

Liste objetos com um paginador.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// The following example lists objects in an Amazon Simple Storage
```

```
    /// Service (Amazon S3) bucket.
    /// </summary>
    public class ListObjectsPaginator
    {
        private const string BucketName = "doc-example-bucket";

        public static async Task Main()
        {
            IAmazonS3 s3Client = new AmazonS3Client();

            Console.WriteLine($"Listing the objects contained in {BucketName}:\n");
            await ListingObjectsAsync(s3Client, BucketName);
        }

        /// <summary>
        /// This method uses a paginator to retrieve the list of objects in an
        /// an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">An Amazon S3 client object.</param>
        /// <param name="bucketName">The name of the S3 bucket whose objects
        /// you want to list.</param>
        public static async Task ListingObjectsAsync(IAmazonS3 client, string
bucketName)
        {
            var listObjectsV2Paginator = client.Paginators.ListObjectsV2(new
ListObjectsV2Request
            {
                BucketName = bucketName,
            });

            await foreach (var response in listObjectsV2Paginator.Responses)
            {
                Console.WriteLine($"HttpStatusCode: {response.HttpStatusCode}");
                Console.WriteLine($"Number of Keys: {response.KeyCount}");
                foreach (var entry in response.S3Objects)
                {
                    Console.WriteLine($"Key = {entry.Key} Size = {entry.Size}");
                }
            }
        }
    }
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for .NET da API.

Restaurar uma cópia arquivada de um objeto

O exemplo de código a seguir mostra como restaurar uma cópia arquivada de um objeto em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to restore an archived object in an Amazon
/// Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class RestoreArchivedObject
{
    public static void Main()
    {
        string bucketName = "doc-example-bucket";
        string objectKey = "archived-object.txt";

        // Specify your bucket region (an example region is shown).
        RegionEndpoint bucketRegion = RegionEndpoint.USWest2;

        IAmazonS3 client = new AmazonS3Client(bucketRegion);
        RestoreObjectAsync(client, bucketName, objectKey).Wait();
    }

    /// <summary>
    /// This method restores an archived object from an Amazon S3 bucket.
    /// </summary>
```

```
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// RestoreObjectAsync.</param>
        /// <param name="bucketName">A string representing the name of the
        /// bucket where the object was located before it was archived.</param>
        /// <param name="objectKey">A string representing the name of the
        /// archived object to restore.</param>
        public static async Task RestoreObjectAsync(IAmazonS3 client, string
bucketName, string objectKey)
        {
            try
            {
                var restoreRequest = new RestoreObjectRequest
                {
                    BucketName = bucketName,
                    Key = objectKey,
                    Days = 2,
                };
                RestoreObjectResponse response = await
client.RestoreObjectAsync(restoreRequest);

                // Check the status of the restoration.
                await CheckRestorationStatusAsync(client, bucketName, objectKey);
            }
            catch (AmazonS3Exception amazonS3Exception)
            {
                Console.WriteLine($"Error: {amazonS3Exception.Message}");
            }
        }

        /// <summary>
        /// This method retrieves the status of the object's restoration.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// GetObjectMetadataAsync.</param>
        /// <param name="bucketName">A string representing the name of the Amazon
        /// S3 bucket which contains the archived object.</param>
        /// <param name="objectKey">A string representing the name of the
        /// archived object you want to restore.</param>
        public static async Task CheckRestorationStatusAsync(IAmazonS3 client,
string bucketName, string objectKey)
        {
```

```
            GetObjectMetadataRequest metadataRequest = new
GetObjectMetadataRequest()
            {
                BucketName = bucketName,
                Key = objectKey,
            };

            GetObjectMetadataResponse response = await
client.GetObjectMetadataAsync(metadataRequest);

            var restStatus = response.RestoreInProgress ? "in-progress" : "finished
or failed";
            Console.WriteLine($"Restoration status: {restStatus}");
        }
    }
```

- Para obter detalhes da API, consulte RestoreObjecta Referência AWS SDK for .NET da API.

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Creates an Amazon S3 bucket with an ACL to control access to the
        /// bucket and the objects stored in it.
        /// </summary>
        /// <param name="client">The initialized client object used to create
        /// an Amazon S3 bucket, with an ACL applied to the bucket.
        /// </param>
```

```
        /// <param name="region">The AWS Region where the bucket will be created.</
param>
        /// <param name="newBucketName">The name of the bucket to create.</param>
        /// <returns>A boolean value indicating success or failure.</returns>
        public static async Task<bool> CreateBucketUseCannedACLAsync(IAmazonS3
 client, S3Region region, string newBucketName)
        {
            try
            {
                // Create a new Amazon S3 bucket with Canned ACL.
                var putBucketRequest = new PutBucketRequest()
                {
                    BucketName = newBucketName,
                    BucketRegion = region,
                    CannedACL = S3CannedACL.LogDeliveryWrite,
                };

                PutBucketResponse putBucketResponse = await
 client.PutBucketAsync(putBucketRequest);

                return putBucketResponse.HttpStatusCode ==
 System.Net.HttpStatusCode.OK;
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Amazon S3 error: {ex.Message}");
            }

            return false;
        }
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for .NET da API.

Definir a configuração de site de um bucket

O exemplo de código a seguir mostra como definir a configuração de site de um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
                // Put the website configuration.
                PutBucketWebsiteRequest putRequest = new PutBucketWebsiteRequest()
                {
                    BucketName = bucketName,
                    WebsiteConfiguration = new WebsiteConfiguration()
                    {
                        IndexDocumentSuffix = indexDocumentSuffix,
                        ErrorDocument = errorDocument,
                    },
                };
                PutBucketWebsiteResponse response = await
client.PutBucketWebsiteAsync(putRequest);
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for .NET da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Shows how to upload a file from the local computer to an Amazon S3
        /// bucket.
        /// </summary>
        /// <param name="client">An initialized Amazon S3 client object.</param>
        /// <param name="bucketName">The Amazon S3 bucket to which the object
        /// will be uploaded.</param>
        /// <param name="objectName">The object to upload.</param>
        /// <param name="filePath">The path, including file name, of the object
        /// on the local computer to upload.</param>
        /// <returns>A boolean value indicating the success or failure of the
        /// upload procedure.</returns>
        public static async Task<bool> UploadFileAsync(
            IAmazonS3 client,
            string bucketName,
            string objectName,
            string filePath)
        {
            var request = new PutObjectRequest
            {
                BucketName = bucketName,
                Key = objectName,
                FilePath = filePath,
            };

            var response = await client.PutObjectAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"Successfully uploaded {objectName} to
{bucketName}.");
                return true;
            }
            else
            {
                Console.WriteLine($"Could not upload {objectName} to
{bucketName}.");
                return false;
            }
        }
```

Faça upload de um objeto com criptografia do lado do servidor.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to upload an object to an Amazon Simple Storage
    /// Service (Amazon S3) bucket with server-side encryption enabled.
    /// </summary>
    public class ServerSideEncryption
    {
        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "samplefile.txt";

            // If the AWS Region defined for your default user is different
            // from the Region where your Amazon S3 bucket is located,
            // pass the Region name to the Amazon S3 client object's constructor.
            // For example: RegionEndpoint.USWest2.
            IAmazonS3 client = new AmazonS3Client();

            await WritingAnObjectAsync(client, bucketName, keyName);
        }

        /// <summary>
        /// Upload a sample object include a setting for encryption.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
        /// to upload a file and apply server-side encryption.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
        /// encrypted object will reside.</param>
        /// <param name="keyName">The name for the object that you want to
        /// create in the supplied bucket.</param>
        public static async Task WritingAnObjectAsync(IAmazonS3 client, string
bucketName, string keyName)
        {
            try
            {
                var putRequest = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
```

```
                    ContentBody = "sample text",
                    ServerSideEncryptionMethod = ServerSideEncryptionMethod.AES256,
                };

                var putResponse = await client.PutObjectAsync(putRequest);

                // Determine the encryption state of an object.
                GetObjectMetadataRequest metadataRequest = new
GetObjectMetadataRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                };
                GetObjectMetadataResponse response = await
client.GetObjectMetadataAsync(metadataRequest);
                ServerSideEncryptionMethod objectEncryption =
response.ServerSideEncryptionMethod;

                Console.WriteLine($"Encryption method used: {0}",
objectEncryption.ToString());
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: '{ex.Message}' when writing an object");
            }
        }
    }
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for .NET da API.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado que possa executar uma ação do Amazon S3 por tempo limitado.

```
    using System;
    using Amazon;
    using Amazon.S3;
    using Amazon.S3.Model;

    public class GenPresignedUrl
    {
        public static void Main()
        {
            const string bucketName = "doc-example-bucket";
            const string objectKey = "sample.txt";

            // Specify how long the presigned URL lasts, in hours
            const double timeoutDuration = 12;

            // Specify the AWS Region of your Amazon S3 bucket. If it is
            // different from the Region defined for the default user,
            // pass the Region to the constructor for the client. For
            // example: new AmazonS3Client(RegionEndpoint.USEast1);

            // If using the Region us-east-1, and server-side encryption with AWS
 KMS, you must specify Signature Version 4.
            // Region us-east-1 defaults to Signature Version 2 unless explicitly
 set to Version 4 as shown below.
            // For more details, see https://docs.aws.amazon.com/AmazonS3/latest/
userguide/UsingAWSSDK.html#specify-signature-version
            // and https://docs.aws.amazon.com/sdkfornet/v3/apidocs/items/Amazon/
TAWSConfigsS3.html
            AWSConfigsS3.UseSignatureVersion4 = true;
            IAmazonS3 s3Client = new AmazonS3Client(RegionEndpoint.USEast1);

            string urlString = GeneratePresignedURL(s3Client, bucketName, objectKey,
 timeoutDuration);
```

```
            Console.WriteLine($"The generated URL is: {urlString}.");
        }

        /// <summary>
        /// Generate a presigned URL that can be used to access the file named
        /// in the objectKey parameter for the amount of time specified in the
        /// duration parameter.
        /// </summary>
        /// <param name="client">An initialized S3 client object used to call
        /// the GetPresignedUrl method.</param>
        /// <param name="bucketName">The name of the S3 bucket containing the
        /// object for which to create the presigned URL.</param>
        /// <param name="objectKey">The name of the object to access with the
        /// presigned URL.</param>
        /// <param name="duration">The length of time for which the presigned
        /// URL will be valid.</param>
        /// <returns>A string representing the generated presigned URL.</returns>
        public static string GeneratePresignedURL(IAmazonS3 client, string
bucketName, string objectKey, double duration)
        {
            string urlString = string.Empty;
            try
            {
                var request = new GetPreSignedUrlRequest()
                {
                    BucketName = bucketName,
                    Key = objectKey,
                    Expires = DateTime.UtcNow.AddHours(duration),
                };
                urlString = client.GetPreSignedURL(request);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error:'{ex.Message}'");
            }

            return urlString;
        }
    }
```

Gere um URL pré-assinado e faça um upload usando esse URL.

```
    using System;
    using System.IO;
    using System.Net.Http;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.S3;
    using Amazon.S3.Model;

    /// <summary>
    /// This example shows how to upload an object to an Amazon Simple Storage
    /// Service (Amazon S3) bucket using a presigned URL. The code first
    /// creates a presigned URL and then uses it to upload an object to an
    /// Amazon S3 bucket using that URL.
    /// </summary>
    public class UploadUsingPresignedURL
    {
        private static HttpClient httpClient = new HttpClient();

        public static async Task Main()
        {
            string bucketName = "doc-example-bucket";
            string keyName = "samplefile.txt";
            string filePath = $"source\\{keyName}";

            // Specify how long the signed URL will be valid in hours.
            double timeoutDuration = 12;

            // Specify the AWS Region of your Amazon S3 bucket. If it is
            // different from the Region defined for the default user,
            // pass the Region to the constructor for the client. For
            // example: new AmazonS3Client(RegionEndpoint.USEast1);

            // If using the Region us-east-1, and server-side encryption with AWS
 KMS, you must specify Signature Version 4.
            // Region us-east-1 defaults to Signature Version 2 unless explicitly
 set to Version 4 as shown below.
            // For more details, see https://docs.aws.amazon.com/AmazonS3/latest/
userguide/UsingAWSSDK.html#specify-signature-version
            // and https://docs.aws.amazon.com/sdkfornet/v3/apidocs/items/Amazon/
TAWSConfigsS3.html
            AWSConfigsS3.UseSignatureVersion4 = true;
            IAmazonS3 client = new AmazonS3Client(RegionEndpoint.USEast1);
```

```
            var url = GeneratePreSignedURL(client, bucketName, keyName,
timeoutDuration);
            var success = await UploadObject(filePath, url);

            if (success)
            {
                Console.WriteLine("Upload succeeded.");
            }
            else
            {
                Console.WriteLine("Upload failed.");
            }
        }

        /// <summary>
        /// Uploads an object to an Amazon S3 bucket using the presigned URL passed
in
        /// the url parameter.
        /// </summary>
        /// <param name="filePath">The path (including file name) to the local
        /// file you want to upload.</param>
        /// <param name="url">The presigned URL that will be used to upload the
        /// file to the Amazon S3 bucket.</param>
        /// <returns>A Boolean value indicating the success or failure of the
        /// operation, based on the HttpWebResponse.</returns>
        public static async Task<bool> UploadObject(string filePath, string url)
        {
            using var streamContent = new StreamContent(
                new FileStream(filePath, FileMode.Open, FileAccess.Read));

            var response = await httpClient.PutAsync(url, streamContent);
            return response.IsSuccessStatusCode;
        }

        /// <summary>
        /// Generates a presigned URL which will be used to upload an object to
        /// an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// GetPreSignedURL.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to which the
        /// presigned URL will point.</param>
```

```
        /// <param name="objectKey">The name of the file that will be uploaded.</
param>
        /// <param name="duration">How long (in hours) the presigned URL will
        /// be valid.</param>
        /// <returns>The generated URL.</returns>
        public static string GeneratePreSignedURL(
            IAmazonS3 client,
            string bucketName,
            string objectKey,
            double duration)
        {
            var request = new GetPreSignedUrlRequest
            {
                BucketName = bucketName,
                Key = objectKey,
                Verb = HttpVerb.PUT,
                Expires = DateTime.UtcNow.AddHours(duration),
            };

            string url = client.GetPreSignedURL(request);
            return url;
        }
    }
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    public class S3_Basics
    {
        public static async Task Main()
        {
            // Create an Amazon S3 client object. The constructor uses the
            // default user installed on the system. To work with Amazon S3
            // features in a different AWS Region, pass the AWS Region as a
            // parameter to the client constructor.
            IAmazonS3 client = new AmazonS3Client();
            string bucketName = string.Empty;
            string filePath = string.Empty;
            string keyName = string.Empty;

            var sepBar = new string('-', Console.WindowWidth);

            Console.WriteLine(sepBar);
            Console.WriteLine("Amazon Simple Storage Service (Amazon S3) basic");
            Console.WriteLine("procedures. This application will:");
            Console.WriteLine("\n\t1. Create a bucket");
            Console.WriteLine("\n\t2. Upload an object to the new bucket");
            Console.WriteLine("\n\t3. Copy the uploaded object to a folder in the
bucket");
            Console.WriteLine("\n\t4. List the items in the new bucket");
            Console.WriteLine("\n\t5. Delete all the items in the bucket");
            Console.WriteLine("\n\t6. Delete the bucket");
            Console.WriteLine(sepBar);

            // Create a bucket.
            Console.WriteLine($"\n{sepBar}");
            Console.WriteLine("\nCreate a new Amazon S3 bucket.\n");
            Console.WriteLine(sepBar);

            Console.Write("Please enter a name for the new bucket: ");
            bucketName = Console.ReadLine();
```

```
            var success = await S3Bucket.CreateBucketAsync(client, bucketName);
            if (success)
            {
                Console.WriteLine($"Successfully created bucket: {bucketName}.\n");
            }
            else
            {
                Console.WriteLine($"Could not create bucket: {bucketName}.\n");
            }

            Console.WriteLine(sepBar);
            Console.WriteLine("Upload a file to the new bucket.");
            Console.WriteLine(sepBar);

            // Get the local path and filename for the file to upload.
            while (string.IsNullOrEmpty(filePath))
            {
                Console.Write("Please enter the path and filename of the file to
upload: ");
                filePath = Console.ReadLine();

                // Confirm that the file exists on the local computer.
                if (!File.Exists(filePath))
                {
                    Console.WriteLine($"Couldn't find {filePath}. Try again.\n");
                    filePath = string.Empty;
                }
            }

            // Get the file name from the full path.
            keyName = Path.GetFileName(filePath);

            success = await S3Bucket.UploadFileAsync(client, bucketName, keyName,
filePath);

            if (success)
            {
                Console.WriteLine($"Successfully uploaded {keyName} from {filePath}
to {bucketName}.\n");
            }
            else
            {
                Console.WriteLine($"Could not upload {keyName}.\n");
```

```
            }

            // Set the file path to an empty string to avoid overwriting the
            // file we just uploaded to the bucket.
            filePath = string.Empty;

            // Now get a new location where we can save the file.
            while (string.IsNullOrEmpty(filePath))
            {
                // First get the path to which the file will be downloaded.
                Console.Write("Please enter the path where the file will be
downloaded: ");
                filePath = Console.ReadLine();

                // Confirm that the file exists on the local computer.
                if (File.Exists($"{filePath}\\{keyName}"))
                {
                    Console.WriteLine($"Sorry, the file already exists in that
location.\n");
                    filePath = string.Empty;
                }
            }

            // Download an object from a bucket.
            success = await S3Bucket.DownloadObjectFromBucketAsync(client,
bucketName, keyName, filePath);

            if (success)
            {
                Console.WriteLine($"Successfully downloaded {keyName}.\n");
            }
            else
            {
                Console.WriteLine($"Sorry, could not download {keyName}.\n");
            }

            // Copy the object to a different folder in the bucket.
            string folderName = string.Empty;

            while (string.IsNullOrEmpty(folderName))
            {
                Console.Write("Please enter the name of the folder to copy your
object to: ");
                folderName = Console.ReadLine();
```

```
            }

            while (string.IsNullOrEmpty(keyName))
            {
                // Get the name to give to the object once uploaded.
                Console.Write("Enter the name of the object to copy: ");
                keyName = Console.ReadLine();
            }

            await S3Bucket.CopyObjectInBucketAsync(client, bucketName, keyName,
folderName);

            // List the objects in the bucket.
            await S3Bucket.ListBucketContentsAsync(client, bucketName);

            // Delete the contents of the bucket.
            await S3Bucket.DeleteBucketContentsAsync(client, bucketName);

            // Deleting the bucket too quickly after deleting its contents will
            // cause an error that the bucket isn't empty. So...
            Console.WriteLine("Press <Enter> when you are ready to delete the
bucket.");
            _ = Console.ReadLine();

            // Delete the bucket.
            await S3Bucket.DeleteBucketAsync(client, bucketName);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Conceitos básicos de criptografia

O exemplo de código a seguir mostra como começar a usar a criptografia de objetos do Amazon S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
using System;
using System.IO;
using System.Security.Cryptography;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to apply client encryption to an object in an
/// Amazon Simple Storage Service (Amazon S3) bucket.
/// </summary>
public class SSEClientEncryption
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";
        string keyName = "exampleobject.txt";
        string copyTargetKeyName = "examplecopy.txt";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USWest2.
        IAmazonS3 client = new AmazonS3Client();

        try
        {
            // Create an encryption key.
            Aes aesEncryption = Aes.Create();
            aesEncryption.KeySize = 256;
            aesEncryption.GenerateKey();
```

```
                string base64Key = Convert.ToBase64String(aesEncryption.Key);

                // Upload the object.
                PutObjectRequest putObjectRequest = await UploadObjectAsync(client,
 bucketName, keyName, base64Key);

                // Download the object and verify that its contents match what you
 uploaded.
                await DownloadObjectAsync(client, bucketName, keyName, base64Key,
 putObjectRequest);

                // Get object metadata and verify that the object uses AES-256
 encryption.
                await GetObjectMetadataAsync(client, bucketName, keyName,
 base64Key);

                // Copy both the source and target objects using server-side
 encryption with
                // an encryption key.
                await CopyObjectAsync(client, bucketName, keyName,
 copyTargetKeyName, aesEncryption, base64Key);
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error: {ex.Message}");
            }
        }

        /// <summary>
        /// Uploads an object to an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// PutObjectAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket to which the
        /// object will be uploaded.</param>
        /// <param name="keyName">The name of the object to upload to the Amazon S3
        /// bucket.</param>
        /// <param name="base64Key">The encryption key.</param>
        /// <returns>The PutObjectRequest object for use by DownloadObjectAsync.</
returns>
        public static async Task<PutObjectRequest> UploadObjectAsync(
            IAmazonS3 client,
            string bucketName,
```

```
            string keyName,
            string base64Key)
        {
            PutObjectRequest putObjectRequest = new PutObjectRequest
            {
                BucketName = bucketName,
                Key = keyName,
                ContentBody = "sample text",
                ServerSideEncryptionCustomerMethod =
 ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };
            PutObjectResponse putObjectResponse = await
 client.PutObjectAsync(putObjectRequest);
            return putObjectRequest;
        }

        /// <summary>
        /// Downloads an encrypted object from an Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
 call
        /// GetObjectAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket where the
 object
        /// is located.</param>
        /// <param name="keyName">The name of the Amazon S3 object to download.</
param>
        /// <param name="base64Key">The encryption key used to encrypt the
        /// object.</param>
        /// <param name="putObjectRequest">The PutObjectRequest used to upload
        /// the object.</param>
        public static async Task DownloadObjectAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string base64Key,
            PutObjectRequest putObjectRequest)
        {
            GetObjectRequest getObjectRequest = new GetObjectRequest
            {
                BucketName = bucketName,
                Key = keyName,
```

```
                // Provide encryption information for the object stored in Amazon
S3.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };

            using (GetObjectResponse getResponse = await
client.GetObjectAsync(getObjectRequest))
            using (StreamReader reader = new
StreamReader(getResponse.ResponseStream))
            {
                string content = reader.ReadToEnd();
                if (string.Compare(putObjectRequest.ContentBody, content) == 0)
                {
                    Console.WriteLine("Object content is same as we uploaded");
                }
                else
                {
                    Console.WriteLine("Error...Object content is not same.");
                }

                if (getResponse.ServerSideEncryptionCustomerMethod ==
ServerSideEncryptionCustomerMethod.AES256)
                {
                    Console.WriteLine("Object encryption method is AES256, same as
we set");
                }
                else
                {
                    Console.WriteLine("Error...Object encryption method is not the
same as AES256 we set");
                }
            }
        }

        /// <summary>
        /// Retrieves the metadata associated with an Amazon S3 object.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used
        /// to call GetObjectMetadataAsync.</param>
        /// <param name="bucketName">The name of the Amazon S3 bucket containing the
        /// object for which we want to retrieve metadata.</param>
        /// <param name="keyName">The name of the object for which we wish to
```

```
        /// retrieve the metadata.</param>
        /// <param name="base64Key">The encryption key associated with the
        /// object.</param>
        public static async Task GetObjectMetadataAsync(
            IAmazonS3 client,
            string bucketName,
            string keyName,
            string base64Key)
        {
            GetObjectMetadataRequest getObjectMetadataRequest = new
GetObjectMetadataRequest
            {
                BucketName = bucketName,
                Key = keyName,

                // The object stored in Amazon S3 is encrypted, so provide the
necessary encryption information.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };

            GetObjectMetadataResponse getObjectMetadataResponse = await
client.GetObjectMetadataAsync(getObjectMetadataRequest);
            Console.WriteLine("The object metadata show encryption method used is:
{0}", getObjectMetadataResponse.ServerSideEncryptionCustomerMethod);
        }

        /// <summary>
        /// Copies an encrypted object from one Amazon S3 bucket to another.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// CopyObjectAsync.</param>
        /// <param name="bucketName">The Amazon S3 bucket containing the object
        /// to copy.</param>
        /// <param name="keyName">The name of the object to copy.</param>
        /// <param name="copyTargetKeyName">The Amazon S3 bucket to which the object
        /// will be copied.</param>
        /// <param name="aesEncryption">The encryption type to use.</param>
        /// <param name="base64Key">The encryption key to use.</param>
        public static async Task CopyObjectAsync(
            IAmazonS3 client,
            string bucketName,
```

```
            string keyName,
            string copyTargetKeyName,
            Aes aesEncryption,
            string base64Key)
        {
            aesEncryption.GenerateKey();
            string copyBase64Key = Convert.ToBase64String(aesEncryption.Key);

            CopyObjectRequest copyRequest = new CopyObjectRequest
            {
                SourceBucket = bucketName,
                SourceKey = keyName,
                DestinationBucket = bucketName,
                DestinationKey = copyTargetKeyName,

                // Information about the source object's encryption.
                CopySourceServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                CopySourceServerSideEncryptionCustomerProvidedKey = base64Key,

                // Information about the target object's encryption.
                ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = copyBase64Key,
            };
            await client.CopyObjectAsync(copyRequest);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CopyObject
  - GetObject
  - GetObjectMetadata

Conceitos básicos de etiquetas

O exemplo de código a seguir mostra como começar a usar etiquetas de objetos do Amazon S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to work with tags in Amazon Simple Storage
/// Service (Amazon S3) objects.
/// </summary>
public class ObjectTag
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";
        string keyName = "newobject.txt";
        string filePath = @"*** file path ***";

        // Specify your bucket region (an example region is shown).
        RegionEndpoint bucketRegion = RegionEndpoint.USWest2;

        var client = new AmazonS3Client(bucketRegion);
        await PutObjectsWithTagsAsync(client, bucketName, keyName, filePath);
    }

    /// <summary>
    /// This method uploads an object with tags. It then shows the tag
    /// values, changes the tags, and shows the new tags.
    /// </summary>
    /// <param name="client">The Initialized Amazon S3 client object used
    /// to call the methods to create and change an objects tags.</param>
    /// <param name="bucketName">A string representing the name of the
    /// bucket where the object will be stored.</param>
```

```
        /// <param name="keyName">A string representing the key name of the
        /// object to be tagged.</param>
        /// <param name="filePath">The directory location and file name of the
        /// object to be uploaded to the Amazon S3 bucket.</param>
        public static async Task PutObjectsWithTagsAsync(IAmazonS3 client, string
bucketName, string keyName, string filePath)
        {
            try
            {
                // Create an object with tags.
                var putRequest = new PutObjectRequest
                {
                    BucketName = bucketName,
                    Key = keyName,
                    FilePath = filePath,
                    TagSet = new List<Tag>
                    {
                        new Tag { Key = "Keyx1", Value = "Value1" },
                        new Tag { Key = "Keyx2", Value = "Value2" },
                    },
                };

                PutObjectResponse response = await
client.PutObjectAsync(putRequest);

                // Now retrieve the new object's tags.
                GetObjectTaggingRequest getTagsRequest = new
GetObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                };

                GetObjectTaggingResponse objectTags = await
client.GetObjectTaggingAsync(getTagsRequest);

                // Display the tag values.
                objectTags.Tagging
                    .ForEach(t => Console.WriteLine($"Key: {t.Key}, Value:
{t.Value}"));

                Tagging newTagSet = new Tagging()
                {
                    TagSet = new List<Tag>
```

```
                    {
                        new Tag { Key = "Key3", Value = "Value3" },
                        new Tag { Key = "Key4", Value = "Value4" },
                    },
                };

                PutObjectTaggingRequest putObjTagsRequest = new
PutObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                    Tagging = newTagSet,
                };

                PutObjectTaggingResponse response2 = await
client.PutObjectTaggingAsync(putObjTagsRequest);

                // Retrieve the tags again and show the values.
                GetObjectTaggingRequest getTagsRequest2 = new
GetObjectTaggingRequest()
                {
                    BucketName = bucketName,
                    Key = keyName,
                };
                GetObjectTaggingResponse objectTags2 = await
client.GetObjectTaggingAsync(getTagsRequest2);

                objectTags2.Tagging
                    .ForEach(t => Console.WriteLine($"Key: {t.Key}, Value:
{t.Value}"));
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine(
                        $"Error: '{ex.Message}'");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetObjectTaggingga Referência AWS SDK for .NET da API.

Gerenciar listas de controle de acesso (ACLs)

Os exemplos de código a seguir mostram como gerenciar listas de controle de acesso (ACLs) para buckets do Amazon S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to manage Amazon Simple Storage Service
/// (Amazon S3) access control lists (ACLs) to control Amazon S3 bucket
/// access.
/// </summary>
public class ManageACLs
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket1";
        string newBucketName = "doc-example-bucket2";
        string keyName = "sample-object.txt";
        string emailAddress = "someone@example.com";

        // If the AWS Region where your bucket is located is different from
        // the Region defined for the default user, pass the Amazon S3 bucket's
        // name to the client constructor. It should look like this:
        // RegionEndpoint bucketRegion = RegionEndpoint.USEast1;
        IAmazonS3 client = new AmazonS3Client();

        await TestBucketObjectACLsAsync(client, bucketName, newBucketName,
keyName, emailAddress);
    }
```

```
        /// <summary>
        /// Creates a new Amazon S3 bucket with a canned ACL, then retrieves the ACL
        /// information and then adds a new ACL to one of the objects in the
        /// Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 client object used to
call
        /// methods to create a bucket, get an ACL, and add a different ACL to
        /// one of the objects.</param>
        /// <param name="bucketName">A string representing the original Amazon S3
        /// bucket name.</param>
        /// <param name="newBucketName">A string representing the name of the
        /// new bucket that will be created.</param>
        /// <param name="keyName">A string representing the key name of an Amazon S3
        /// object for which we will change the ACL.</param>
        /// <param name="emailAddress">A string representing the email address
        /// belonging to the person to whom access to the Amazon S3 bucket will be
        /// granted.</param>
        public static async Task TestBucketObjectACLsAsync(
            IAmazonS3 client,
            string bucketName,
            string newBucketName,
            string keyName,
            string emailAddress)
        {
            try
            {
                // Create a new Amazon S3 bucket and specify canned ACL.
                var success = await CreateBucketWithCannedACLAsync(client,
newBucketName);

                // Get the ACL on a bucket.
                await GetBucketACLAsync(client, bucketName);

                // Add (replace) the ACL on an object in a bucket.
                await AddACLToExistingObjectAsync(client, bucketName, keyName,
emailAddress);
            }
            catch (AmazonS3Exception amazonS3Exception)
            {
                Console.WriteLine($"Exception: {amazonS3Exception.Message}");
            }
        }
```

```
        /// <summary>
        /// Creates a new Amazon S3 bucket with a canned ACL attached.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="newBucketName">A string representing the name of the
        /// new Amazon S3 bucket.</param>
        /// <returns>Returns a boolean value indicating success or failure.</
returns>
        public static async Task<bool> CreateBucketWithCannedACLAsync(IAmazonS3
 client, string newBucketName)
        {
            var request = new PutBucketRequest()
            {
                BucketName = newBucketName,
                BucketRegion = S3Region.EUWest1,

                // Add a canned ACL.
                CannedACL = S3CannedACL.LogDeliveryWrite,
            };

            var response = await client.PutBucketAsync(request);
            return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
        }


        /// <summary>
        /// Retrieves the ACL associated with the Amazon S3 bucket name in the
        /// bucketName parameter.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="bucketName">The Amazon S3 bucket for which we want to get
 the
        /// ACL list.</param>
        /// <returns>Returns an S3AccessControlList returned from the call to
        /// GetACLAsync.</returns>
        public static async Task<S3AccessControlList> GetBucketACLAsync(IAmazonS3
 client, string bucketName)
        {
            GetACLResponse response = await client.GetACLAsync(new GetACLRequest
            {
                BucketName = bucketName,
```

```
            });

            return response.AccessControlList;
        }



        /// <summary>
        /// Adds a new ACL to an existing object in the Amazon S3 bucket.
        /// </summary>
        /// <param name="client">The initialized client object used to call
        /// PutBucketAsync.</param>
        /// <param name="bucketName">A string representing the name of the Amazon S3
        /// bucket containing the object to which we want to apply a new ACL.</
param>
        /// <param name="keyName">A string representing the name of the object
        /// to which we want to apply the new ACL.</param>
        /// <param name="emailAddress">The email address of the person to whom
        /// we will be applying to whom access will be granted.</param>
        public static async Task AddACLToExistingObjectAsync(IAmazonS3 client,
 string bucketName, string keyName, string emailAddress)
        {
            // Retrieve the ACL for an object.
            GetACLResponse aclResponse = await client.GetACLAsync(new GetACLRequest
            {
                BucketName = bucketName,
                Key = keyName,
            });

            S3AccessControlList acl = aclResponse.AccessControlList;

            // Retrieve the owner.
            Owner owner = acl.Owner;

            // Clear existing grants.
            acl.Grants.Clear();

            // Add a grant to reset the owner's full permission
            // (the previous clear statement removed all permissions).
            var fullControlGrant = new S3Grant
            {
                Grantee = new S3Grantee { CanonicalUser = acl.Owner.Id },
            };
            acl.AddGrant(fullControlGrant.Grantee, S3Permission.FULL_CONTROL);
```

```
            // Specify email to identify grantee for granting permissions.
            var grantUsingEmail = new S3Grant
            {
                Grantee = new S3Grantee { EmailAddress = emailAddress },
                Permission = S3Permission.WRITE_ACP,
            };

            // Specify log delivery group as grantee.
            var grantLogDeliveryGroup = new S3Grant
            {
                Grantee = new S3Grantee { URI = "http://acs.amazonaws.com/groups/s3/
LogDelivery" },
                Permission = S3Permission.WRITE,
            };

            // Create a new ACL.
            var newAcl = new S3AccessControlList
            {
                Grants = new List<S3Grant> { grantUsingEmail,
 grantLogDeliveryGroup },
                Owner = owner,
            };

            // Set the new ACL. We're throwing away the response here.
            _ = await client.PutACLAsync(new PutACLRequest
            {
                BucketName = bucketName,
                Key = keyName,
                AccessControlList = newAcl,
            });
        }

    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - GetBucketAcl
  - GetObjectAcl
  - PutBucketAcl

- PutObjectAcl

Executar uma cópia multipart

O exemplo de código a seguir mostra como executar uma cópia multipart de um objeto do Amazon S3.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// This example shows how to perform a multi-part copy from one Amazon
/// Simple Storage Service (Amazon S3) bucket to another.
/// </summary>
public class MPUapiCopyObj
{
    private const string SourceBucket = "doc-example-bucket1";
    private const string TargetBucket = "doc-example-bucket2";
    private const string SourceObjectKey = "example.mov";
    private const string TargetObjectKey = "copied_video_file.mov";

    /// <summary>
    /// This method starts the multi-part upload.
    /// </summary>
    public static async Task Main()
    {
        var s3Client = new AmazonS3Client();
        Console.WriteLine("Copying object...");
        await MPUCopyObjectAsync(s3Client);
    }
```

```
        /// <summary>
        /// This method uses the passed client object to perform a multipart
        /// copy operation.
        /// </summary>
        /// <param name="client">An Amazon S3 client object that will be used
        /// to perform the copy.</param>
        public static async Task MPUCopyObjectAsync(AmazonS3Client client)
        {
            // Create a list to store the copy part responses.
            var copyResponses = new List<CopyPartResponse>();

            // Setup information required to initiate the multipart upload.
            var initiateRequest = new InitiateMultipartUploadRequest
            {
                BucketName = TargetBucket,
                Key = TargetObjectKey,
            };

            // Initiate the upload.
            InitiateMultipartUploadResponse initResponse =
                await client.InitiateMultipartUploadAsync(initiateRequest);

            // Save the upload ID.
            string uploadId = initResponse.UploadId;

            try
            {
                // Get the size of the object.
                var metadataRequest = new GetObjectMetadataRequest
                {
                    BucketName = SourceBucket,
                    Key = SourceObjectKey,
                };

                GetObjectMetadataResponse metadataResponse =
                    await client.GetObjectMetadataAsync(metadataRequest);
                var objectSize = metadataResponse.ContentLength; // Length in bytes.

                // Copy the parts.
                var partSize = 5 * (long)Math.Pow(2, 20); // Part size is 5 MB.

                long bytePosition = 0;
                for (int i = 1; bytePosition < objectSize; i++)
```

```
                {
                    var copyRequest = new CopyPartRequest
                    {
                        DestinationBucket = TargetBucket,
                        DestinationKey = TargetObjectKey,
                        SourceBucket = SourceBucket,
                        SourceKey = SourceObjectKey,
                        UploadId = uploadId,
                        FirstByte = bytePosition,
                        LastByte = bytePosition + partSize - 1 >= objectSize ?
objectSize - 1 : bytePosition + partSize - 1,
                        PartNumber = i,
                    };

                    copyResponses.Add(await client.CopyPartAsync(copyRequest));

                    bytePosition += partSize;
                }

                // Set up to complete the copy.
                var completeRequest = new CompleteMultipartUploadRequest
                {
                    BucketName = TargetBucket,
                    Key = TargetObjectKey,
                    UploadId = initResponse.UploadId,
                };
                completeRequest.AddPartETags(copyResponses);

                // Complete the copy.
                CompleteMultipartUploadResponse completeUploadResponse =
                    await client.CompleteMultipartUploadAsync(completeRequest);
            }
            catch (AmazonS3Exception e)
            {
                Console.WriteLine($"Error encountered on server.
Message:'{e.Message}' when writing an object");
            }
            catch (Exception e)
            {
                Console.WriteLine($"Unknown encountered on server.
Message:'{e.Message}' when writing an object");
            }
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - GetObjectMetadata
  - UploadPartCopy

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chame funções que transferem arquivos de e para um bucket do S3 usando o Amazon TransferUtility S3.

```
global using System.Text;
global using Amazon.S3;
global using Amazon.S3.Model;
global using Amazon.S3.Transfer;
global using TransferUtilityBasics;



// This Amazon S3 client uses the default user credentials
// defined for this computer.
using Microsoft.Extensions.Configuration;
```

```
IAmazonS3 client = new AmazonS3Client();
var transferUtil = new TransferUtility(client);
IConfiguration _configuration;

_configuration = new ConfigurationBuilder()
    .SetBasePath(Directory.GetCurrentDirectory())
    .AddJsonFile("settings.json") // Load test settings from JSON file.
    .AddJsonFile("settings.local.json",
        true) // Optionally load local settings.
    .Build();

// Edit the values in settings.json to use an S3 bucket and files that
// exist on your AWS account and on the local computer where you
// run this scenario.
var bucketName = _configuration["BucketName"];
var localPath =
 $"{Environment.GetFolderPath(Environment.SpecialFolder.ApplicationData)}\
\TransferFolder";

DisplayInstructions();

PressEnter();

Console.WriteLine();

// Upload a single file to an S3 bucket.
DisplayTitle("Upload a single file");

var fileToUpload = _configuration["FileToUpload"];
Console.WriteLine($"Uploading {fileToUpload} to the S3 bucket, {bucketName}.");

var success = await TransferMethods.UploadSingleFileAsync(transferUtil, bucketName,
 fileToUpload, localPath);
if (success)
{
    Console.WriteLine($"Successfully uploaded the file, {fileToUpload} to
 {bucketName}.");
}

PressEnter();

// Upload a local directory to an S3 bucket.
DisplayTitle("Upload all files from a local directory");
Console.WriteLine("Upload all the files in a local folder to an S3 bucket.");
```

```
const string keyPrefix = "UploadFolder";
var uploadPath = $"{localPath}\\UploadFolder";

Console.WriteLine($"Uploading the files in {uploadPath} to {bucketName}");
DisplayTitle($"{uploadPath} files");
DisplayLocalFiles(uploadPath);
Console.WriteLine();

PressEnter();

success = await TransferMethods.UploadFullDirectoryAsync(transferUtil, bucketName,
 keyPrefix, uploadPath);
if (success)
{
    Console.WriteLine($"Successfully uploaded the files in {uploadPath} to
 {bucketName}.");
    Console.WriteLine($"{bucketName} currently contains the following files:");
    await DisplayBucketFiles(client, bucketName, keyPrefix);
    Console.WriteLine();
}

PressEnter();

// Download a single file from an S3 bucket.
DisplayTitle("Download a single file");
Console.WriteLine("Now we will download a single file from an S3 bucket.");

var keyName = _configuration["FileToDownload"];

Console.WriteLine($"Downloading {keyName} from {bucketName}.");

success = await TransferMethods.DownloadSingleFileAsync(transferUtil, bucketName,
 keyName, localPath);
if (success)
{
    Console.WriteLine("$Successfully downloaded the file, {keyName} from
 {bucketName}.");
}

PressEnter();

// Download the contents of a directory from an S3 bucket.
DisplayTitle("Download the contents of an S3 bucket");
var s3Path = _configuration["S3Path"];
```

```
var downloadPath = $"{localPath}\\{s3Path}";

Console.WriteLine($"Downloading the contents of {bucketName}\\{s3Path}");
Console.WriteLine($"{bucketName}\\{s3Path} contains the following files:");
await DisplayBucketFiles(client, bucketName, s3Path);
Console.WriteLine();

success = await TransferMethods.DownloadS3DirectoryAsync(transferUtil, bucketName,
 s3Path, downloadPath);
if (success)
{
    Console.WriteLine($"Downloaded the files in {bucketName} to {downloadPath}.");
    Console.WriteLine($"{downloadPath} now contains the following files:");
    DisplayLocalFiles(downloadPath);
}

Console.WriteLine("\nThe TransferUtility Basics application has completed.");
PressEnter();

// Displays the title for a section of the scenario.
static void DisplayTitle(string titleText)
{
    var sepBar = new string('-', Console.WindowWidth);

    Console.WriteLine(sepBar);
    Console.WriteLine(CenterText(titleText));
    Console.WriteLine(sepBar);
}

// Displays a description of the actions to be performed by the scenario.
static void DisplayInstructions()
{
    var sepBar = new string('-', Console.WindowWidth);

    DisplayTitle("Amazon S3 Transfer Utility Basics");
    Console.WriteLine("This program shows how to use the Amazon S3 Transfer
 Utility.");
    Console.WriteLine("It performs the following actions:");
    Console.WriteLine("\t1. Upload a single object to an S3 bucket.");
    Console.WriteLine("\t2. Upload an entire directory from the local computer to an
\n\t  S3 bucket.");
    Console.WriteLine("\t3. Download a single object from an S3 bucket.");
    Console.WriteLine("\t4. Download the objects in an S3 bucket to a local
 directory.");
```

```
    Console.WriteLine($"\n{sepBar}");
}

// Pauses the scenario.
static void PressEnter()
{
    Console.WriteLine("Press <Enter> to continue.");
    _ = Console.ReadLine();
    Console.WriteLine("\n");
}

// Returns the string textToCenter, padded on the left with spaces
// that center the text on the console display.
static string CenterText(string textToCenter)
{
    var centeredText = new StringBuilder();
    var screenWidth = Console.WindowWidth;
    centeredText.Append(new string(' ', (int)(screenWidth - textToCenter.Length) /
 2));
    centeredText.Append(textToCenter);
    return centeredText.ToString();
}

// Displays a list of file names included in the specified path.
static void DisplayLocalFiles(string localPath)
{
    var fileList = Directory.GetFiles(localPath);
    if (fileList.Length > 0)
    {
        foreach (var fileName in fileList)
        {
            Console.WriteLine(fileName);
        }
    }
}

// Displays a list of the files in the specified S3 bucket and prefix.
static async Task DisplayBucketFiles(IAmazonS3 client, string bucketName, string
 s3Path)
{
    ListObjectsV2Request request = new()
    {
        BucketName = bucketName,
        Prefix = s3Path,
```

```
        MaxKeys = 5,
    };

    var response = new ListObjectsV2Response();

    do
    {
        response = await client.ListObjectsV2Async(request);

        response.S3Objects
            .ForEach(obj => Console.WriteLine($"{obj.Key}"));

        // If the response is truncated, set the request ContinuationToken
        // from the NextContinuationToken property of the response.
        request.ContinuationToken = response.NextContinuationToken;
    } while (response.IsTruncated);
}
```

Carregue um único arquivo.

```
        /// <summary>
        /// Uploads a single file from the local computer to an S3 bucket.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the file
        /// will be stored.</param>
        /// <param name="fileName">The name of the file to upload.</param>
        /// <param name="localPath">The local path where the file is stored.</param>
        /// <returns>A boolean value indicating the success of the action.</returns>
        public static async Task<bool> UploadSingleFileAsync(
            TransferUtility transferUtil,
            string bucketName,
            string fileName,
            string localPath)
        {
            if (File.Exists($"{localPath}\\{fileName}"))
            {
                try
                {
```

```
                    await transferUtil.UploadAsync(new TransferUtilityUploadRequest
                    {
                        BucketName = bucketName,
                        Key = fileName,
                        FilePath = $"{localPath}\\{fileName}",
                    });

                    return true;
                }
                catch (AmazonS3Exception s3Ex)
                {
                    Console.WriteLine($"Could not upload {fileName} from {localPath}
 because:");
                    Console.WriteLine(s3Ex.Message);
                    return false;
                }
            }
            else
            {
                Console.WriteLine($"{fileName} does not exist in {localPath}");
                return false;
            }
        }
```

Carregue um diretório local inteiro.

```
        /// <summary>
        /// Uploads all the files in a local directory to a directory in an S3
        /// bucket.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket where the files
        /// will be stored.</param>
        /// <param name="keyPrefix">The key prefix is the S3 directory where
        /// the files will be stored.</param>
        /// <param name="localPath">The local directory that contains the files
        /// to be uploaded.</param>
        /// <returns>A Boolean value representing the success of the action.</
returns>
        public static async Task<bool> UploadFullDirectoryAsync(
```

```
            TransferUtility transferUtil,
            string bucketName,
            string keyPrefix,
            string localPath)
        {
            if (Directory.Exists(localPath))
            {
                try
                {
                    await transferUtil.UploadDirectoryAsync(new
TransferUtilityUploadDirectoryRequest
                    {
                        BucketName = bucketName,
                        KeyPrefix = keyPrefix,
                        Directory = localPath,
                    });

                    return true;
                }
                catch (AmazonS3Exception s3Ex)
                {
                    Console.WriteLine($"Can't upload the contents of {localPath}
because:");
                    Console.WriteLine(s3Ex?.Message);
                    return false;
                }
            }
            else
            {
                Console.WriteLine($"The directory {localPath} does not exist.");
                return false;
            }
        }
```

Baixe um único arquivo.

```
        /// <summary>
        /// Download a single file from an S3 bucket to the local computer.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
```

```
        /// object.</param>
        /// <param name="bucketName">The name of the S3 bucket containing the
        /// file to download.</param>
        /// <param name="keyName">The name of the file to download.</param>
        /// <param name="localPath">The path on the local computer where the
        /// downloaded file will be saved.</param>
        /// <returns>A Boolean value indicating the results of the action.</returns>
        public static async Task<bool> DownloadSingleFileAsync(
        TransferUtility transferUtil,
            string bucketName,
            string keyName,
            string localPath)
        {
            await transferUtil.DownloadAsync(new TransferUtilityDownloadRequest
            {
                BucketName = bucketName,
                Key = keyName,
                FilePath = $"{localPath}\\{keyName}",
            });

            return (File.Exists($"{localPath}\\{keyName}"));
        }
```

Baixe o conteúdo de um bucket do S3.

```
        /// <summary>
        /// Downloads the contents of a directory in an S3 bucket to a
        /// directory on the local computer.
        /// </summary>
        /// <param name="transferUtil">The transfer initialized TransferUtility
        /// object.</param>
        /// <param name="bucketName">The bucket containing the files to download.</
param>
        /// <param name="s3Path">The S3 directory where the files are located.</
param>
        /// <param name="localPath">The local path to which the files will be
        /// saved.</param>
        /// <returns>A Boolean value representing the success of the action.</
returns>
        public static async Task<bool> DownloadS3DirectoryAsync(
```

```
            TransferUtility transferUtil,
            string bucketName,
            string s3Path,
            string localPath)
        {
            int fileCount = 0;

            // If the directory doesn't exist, it will be created.
            if (Directory.Exists(s3Path))
            {
                var files = Directory.GetFiles(localPath);
                fileCount = files.Length;
            }

            await transferUtil.DownloadDirectoryAsync(new
TransferUtilityDownloadDirectoryRequest
            {
                BucketName = bucketName,
                LocalDirectory = localPath,
                S3Directory = s3Path,
            });

            if (Directory.Exists(localPath))
            {
                var files = Directory.GetFiles(localPath);
                if (files.Length > fileCount)
                {
                    return true;
                }

                // No change in the number of files. Assume
                // the download failed.
                return false;
            }

            // The local directory doesn't exist. No files
            // were downloaded.
            return false;
        }
```

Acompanhe o progresso de um upload usando TransferUtility o.

```
using System;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Transfer;

/// <summary>
/// This example shows how to track the progress of a multipart upload
/// using the Amazon Simple Storage Service (Amazon S3) TransferUtility to
/// upload to an Amazon S3 bucket.
/// </summary>
public class TrackMPUUsingHighLevelAPI
{
    public static async Task Main()
    {
        string bucketName = "doc-example-bucket";
        string keyName = "sample_pic.png";
        string path = "filepath/directory/";
        string filePath = $"{path}{keyName}";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USWest2 or RegionEndpoint.USEast2.
        IAmazonS3 client = new AmazonS3Client();

        await TrackMPUAsync(client, bucketName, filePath, keyName);
    }

    /// <summary>
    /// Starts an Amazon S3 multipart upload and assigns an event handler to
    /// track the progress of the upload.
    /// </summary>
    /// <param name="client">The initialized Amazon S3 client object used to
    /// perform the multipart upload.</param>
    /// <param name="bucketName">The name of the bucket to which to upload
    /// the file.</param>
    /// <param name="filePath">The path, including the file name of the
    /// file to be uploaded to the Amazon S3 bucket.</param>
    /// <param name="keyName">The file name to be used in the
    /// destination Amazon S3 bucket.</param>
    public static async Task TrackMPUAsync(
        IAmazonS3 client,
        string bucketName,
```

```
            string filePath,
            string keyName)
        {
            try
            {
                var fileTransferUtility = new TransferUtility(client);

                // Use TransferUtilityUploadRequest to configure options.
                // In this example we subscribe to an event.
                var uploadRequest =
                    new TransferUtilityUploadRequest
                    {
                        BucketName = bucketName,
                        FilePath = filePath,
                        Key = keyName,
                    };

                uploadRequest.UploadProgressEvent +=
                    new EventHandler<UploadProgressArgs>(
                        UploadRequest_UploadPartProgressEvent);

                await fileTransferUtility.UploadAsync(uploadRequest);
                Console.WriteLine("Upload completed");
            }
            catch (AmazonS3Exception ex)
            {
                Console.WriteLine($"Error:: {ex.Message}");
            }
        }

        /// <summary>
        /// Event handler to check the progress of the multipart upload.
        /// </summary>
        /// <param name="sender">The object that raised the event.</param>
        /// <param name="e">The object that contains multipart upload
        /// information.</param>
        public static void UploadRequest_UploadPartProgressEvent(object sender,
UploadProgressArgs e)
        {
            // Process event.
            Console.WriteLine($"{e.TransferredBytes}/{e.TotalBytes}");
        }
    }
```

Faça upload de um objeto com criptografia.

```
using System;
using System.Collections.Generic;
using System.IO;
using System.Security.Cryptography;
using System.Threading.Tasks;
using Amazon.S3;
using Amazon.S3.Model;

/// <summary>
/// Uses the Amazon Simple Storage Service (Amazon S3) low level API to
/// perform a multipart upload to an Amazon S3 bucket.
/// </summary>
public class SSECLowLevelMPUcopyObject
{
    public static async Task Main()
    {
        string existingBucketName = "doc-example-bucket";
        string sourceKeyName = "sample_file.txt";
        string targetKeyName = "sample_file_copy.txt";
        string filePath = $"sample\\{targetKeyName}";

        // If the AWS Region defined for your default user is different
        // from the Region where your Amazon S3 bucket is located,
        // pass the Region name to the Amazon S3 client object's constructor.
        // For example: RegionEndpoint.USEast1.
        IAmazonS3 client = new AmazonS3Client();

        // Create the encryption key.
        var base64Key = CreateEncryptionKey();

        await CreateSampleObjUsingClientEncryptionKeyAsync(
            client,
            existingBucketName,
            sourceKeyName,
            filePath,
            base64Key);
    }

    /// <summary>
```

```
        /// Creates the encryption key to use with the multipart upload.
        /// </summary>
        /// <returns>A string containing the base64-encoded key for encrypting
        /// the multipart upload.</returns>
        public static string CreateEncryptionKey()
        {
            Aes aesEncryption = Aes.Create();
            aesEncryption.KeySize = 256;
            aesEncryption.GenerateKey();
            string base64Key = Convert.ToBase64String(aesEncryption.Key);
            return base64Key;
        }

        /// <summary>
        /// Creates and uploads an object using a multipart upload.
        /// </summary>
        /// <param name="client">The initialized Amazon S3 object used to
        /// initialize and perform the multipart upload.</param>
        /// <param name="existingBucketName">The name of the bucket to which
        /// the object will be uploaded.</param>
        /// <param name="sourceKeyName">The source object name.</param>
        /// <param name="filePath">The location of the source object.</param>
        /// <param name="base64Key">The encryption key to use with the upload.</
param>
        public static async Task CreateSampleObjUsingClientEncryptionKeyAsync(
            IAmazonS3 client,
            string existingBucketName,
            string sourceKeyName,
            string filePath,
            string base64Key)
        {
            List<UploadPartResponse> uploadResponses = new
 List<UploadPartResponse>();

            InitiateMultipartUploadRequest initiateRequest = new
 InitiateMultipartUploadRequest
            {
                BucketName = existingBucketName,
                Key = sourceKeyName,
                ServerSideEncryptionCustomerMethod =
 ServerSideEncryptionCustomerMethod.AES256,
                ServerSideEncryptionCustomerProvidedKey = base64Key,
            };
```

```
            InitiateMultipartUploadResponse initResponse =
               await client.InitiateMultipartUploadAsync(initiateRequest);

            long contentLength = new FileInfo(filePath).Length;
            long partSize = 5 * (long)Math.Pow(2, 20); // 5 MB

            try
            {
                long filePosition = 0;
                for (int i = 1; filePosition < contentLength; i++)
                {
                    UploadPartRequest uploadRequest = new UploadPartRequest
                    {
                        BucketName = existingBucketName,
                        Key = sourceKeyName,
                        UploadId = initResponse.UploadId,
                        PartNumber = i,
                        PartSize = partSize,
                        FilePosition = filePosition,
                        FilePath = filePath,
                        ServerSideEncryptionCustomerMethod =
ServerSideEncryptionCustomerMethod.AES256,
                        ServerSideEncryptionCustomerProvidedKey = base64Key,
                    };

                    // Upload part and add response to our list.
                    uploadResponses.Add(await
client.UploadPartAsync(uploadRequest));

                    filePosition += partSize;
                }

                CompleteMultipartUploadRequest completeRequest = new
CompleteMultipartUploadRequest
                {
                    BucketName = existingBucketName,
                    Key = sourceKeyName,
                    UploadId = initResponse.UploadId,
                };
                completeRequest.AddPartETags(uploadResponses);

                CompleteMultipartUploadResponse completeUploadResponse =
                    await client.CompleteMultipartUploadAsync(completeRequest);
            }
```

```
            catch (Exception exception)
            {
                Console.WriteLine($"Exception occurred: {exception.Message}");

                // If there was an error, abort the multipart upload.
                AbortMultipartUploadRequest abortMPURequest = new
 AbortMultipartUploadRequest
                {
                    BucketName = existingBucketName,
                    Key = sourceKeyName,
                    UploadId = initResponse.UploadId,
                };

                await client.AbortMultipartUploadAsync(abortMPURequest);
            }
        }
    }
```

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando .NET.

```
using System.Threading.Tasks;
using Amazon.Lambda.Core;
```

```
using Amazon.S3;
using System;
using Amazon.Lambda.S3Events;
using System.Web;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace S3Integration
{
    public class Function
    {
        private static AmazonS3Client _s3Client;
        public Function() : this(null)
        {
        }

        internal Function(AmazonS3Client s3Client)
        {
            _s3Client = s3Client ?? new AmazonS3Client();
        }

        public async Task<string> Handler(S3Event evt, ILambdaContext context)
        {
            try
            {
                if (evt.Records.Count <= 0)
                {
                    context.Logger.LogLine("Empty S3 Event received");
                    return string.Empty;
                }

                var bucket = evt.Records[0].S3.Bucket.Name;
                var key = HttpUtility.UrlDecode(evt.Records[0].S3.Object.Key);

                context.Logger.LogLine($"Request is for {bucket} and {key}");

                var objectResult = await _s3Client.GetObjectAsync(bucket, key);

                context.Logger.LogLine($"Returning {objectResult.Key}");

                return objectResult.Key;
```

```
            }
            catch (Exception e)
            {
                context.Logger.LogLine($"Error processing request - {e.Message}");

                return string.Empty;
            }
        }
    }
}
```

Exemplos do S3 Glacier usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o S3 Glacier.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3 Glacier

O exemplo de código a seguir mostra como começar a usar o Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.Glacier;
using Amazon.Glacier.Model;

namespace GlacierActions;

public static class HelloGlacier
{
    static async Task Main()
    {
        var glacierService = new AmazonGlacierClient();

        Console.WriteLine("Hello Amazon Glacier!");
        Console.WriteLine("Let's list your Glacier vaults:");

        // You can use await and any of the async methods to get a response.
        // Let's get the vaults using a paginator.
        var glacierVaultPaginator = glacierService.Paginators.ListVaults(
            new ListVaultsRequest { AccountId = "-" });

        await foreach (var vault in glacierVaultPaginator.VaultList)
        {
            Console.WriteLine($"{vault.CreationDate}:{vault.VaultName}, ARN:
{vault.VaultARN}");
        }
    }
}
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for .NET da API.

Tópicos

- Ações

Ações

Adicionar tags

O exemplo de código a seguir mostra como adicionar tags a um cofre do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add tags to the items in an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to add tags to.</param>
    /// <param name="key">The name of the object to tag.</param>
    /// <param name="value">The tag value to add.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> AddTagsToVaultAsync(string vaultName, string key, string
value)
    {
        var request = new AddTagsToVaultRequest
        {
            Tags = new Dictionary<string, string>
                {
                    { key, value },
                },
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.AddTagsToVaultAsync(request);
        return response.HttpStatusCode == HttpStatusCode.NoContent;
    }
```

- Para obter detalhes da API, consulte AddTagsToVaulta Referência AWS SDK for .NET da API.

Crie um cofre

O exemplo de código a seguir mostra como criar um vault (cofre) do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create an Amazon S3 Glacier vault.
/// </summary>
/// <param name="vaultName">The name of the vault to create.</param>
/// <returns>A Boolean value indicating the success of the action.</returns>
public async Task<bool> CreateVaultAsync(string vaultName)
{
    var request = new CreateVaultRequest
    {
        // Setting the AccountId to "-" means that
        // the account associated with the current
        // account will be used.
        AccountId = "-",
        VaultName = vaultName,
    };

    var response = await _glacierService.CreateVaultAsync(request);

    Console.WriteLine($"Created {vaultName} at: {response.Location}");

    return response.HttpStatusCode == HttpStatusCode.Created;
}
```

- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for .NET da API.

Descreva um cofre

O exemplo de código a seguir mostra como descrever um cofre do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to describe.</param>
    /// <returns>The Amazon Resource Name (ARN) of the vault.</returns>
    public async Task<string> DescribeVaultAsync(string vaultName)
    {
        var request = new DescribeVaultRequest
        {
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.DescribeVaultAsync(request);

        // Display the information about the vault.
        Console.WriteLine($"{response.VaultName}\tARN: {response.VaultARN}");
        Console.WriteLine($"Created on: {response.CreationDate}\tNumber of Archives:
{response.NumberOfArchives}\tSize (in bytes): {response.SizeInBytes}");
        if (response.LastInventoryDate != DateTime.MinValue)
        {
            Console.WriteLine($"Last inventory: {response.LastInventoryDate}");
        }

        return response.VaultARN;
    }
```

- Para obter detalhes da API, consulte DescribeVaulta Referência AWS SDK for .NET da API.

Baixe um arquivo.

O exemplo de código a seguir mostra como baixar um arquivo do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo usa a ArchiveTransferManager classe. Para obter detalhes da API, consulte ArchiveTransferManager.

```
   /// <summary>
   /// Download an archive from an Amazon S3 Glacier vault using the Archive
   /// Transfer Manager.
   /// </summary>
   /// <param name="vaultName">The name of the vault containing the object.</param>
   /// <param name="archiveId">The Id of the archive to download.</param>
   /// <param name="localFilePath">The local directory where the file will
   /// be stored after download.</param>
   /// <returns>Async Task.</returns>
   public async Task<bool> DownloadArchiveWithArchiveManagerAsync(string vaultName,
string archiveId, string localFilePath)
   {
       try
       {
           var manager = new ArchiveTransferManager(_glacierService);

           var options = new DownloadOptions
           {
               StreamTransferProgress = Progress!,
           };

           // Download an archive.
           Console.WriteLine("Initiating the archive retrieval job and then polling
SQS queue for the archive to be available.");
           Console.WriteLine("When the archive is available, downloading will
begin.");
           await manager.DownloadAsync(vaultName, archiveId, localFilePath,
options);

           return true;
       }
```

```
        catch (AmazonGlacierException ex)
        {
            Console.WriteLine(ex.Message);
            return false;
        }
    }

    /// <summary>
    /// Event handler to track the progress of the Archive Transfer Manager.
    /// </summary>
    /// <param name="sender">The object that raised the event.</param>
    /// <param name="args">The argument values from the object that raised the
    /// event.</param>
    static void Progress(object sender, StreamTransferProgressArgs args)
    {
        if (args.PercentDone != _currentPercentage)
        {
            _currentPercentage = args.PercentDone;
            Console.WriteLine($"Downloaded {_currentPercentage}%");
        }
    }
```

Listar trabalhos

O exemplo de código a seguir mostra como listar trabalhos do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List Amazon S3 Glacier jobs.
    /// </summary>
    /// <param name="vaultName">The name of the vault to list jobs for.</param>
    /// <returns>A list of Amazon S3 Glacier jobs.</returns>
```

```
    public async Task<List<GlacierJobDescription>> ListJobsAsync(string vaultName)
    {
        var request = new ListJobsRequest
        {
            // Using a hyphen "-" for the Account Id will
            // cause the SDK to use the Account Id associated
            // with the current account.
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.ListJobsAsync(request);

        return response.JobList;
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for .NET da API.

Listar tags

O exemplo de código a seguir mostra como listar tags para um cofre do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List tags for an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the vault to list tags for.</param>
    /// <returns>A dictionary listing the tags attached to each object in the
    /// vault and its tags.</returns>
    public async Task<Dictionary<string, string>> ListTagsForVaultAsync(string
vaultName)
    {
        var request = new ListTagsForVaultRequest
```

```
        {
            // Using a hyphen "-" for the Account Id will
            // cause the SDK to use the Account Id associated
            // with the default user.
            AccountId = "-",
            VaultName = vaultName,
        };

        var response = await _glacierService.ListTagsForVaultAsync(request);

        return response.Tags;
    }
```

- Para obter detalhes da API, consulte ListTagsForVaulta Referência AWS SDK for .NET da API.

Liste cofres

O exemplo de código a seguir mostra como listar cofres do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Amazon S3 Glacier vaults associated with the current account.
    /// </summary>
    /// <returns>A list containing information about each vault.</returns>
    public async Task<List<DescribeVaultOutput>> ListVaultsAsync()
    {
        var glacierVaultPaginator = _glacierService.Paginators.ListVaults(
            new ListVaultsRequest { AccountId = "-" });
        var vaultList = new List<DescribeVaultOutput>();

        await foreach (var vault in glacierVaultPaginator.VaultList)
        {
            vaultList.Add(vault);
```

```
        }

        return vaultList;
    }
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for .NET da API.

Baixe um arquivo em um cofre

O exemplo de código a seguir mostra como fazer upload de um arquivo em um cofre do Amazon S3 Glacier.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Upload an object to an Amazon S3 Glacier vault.
    /// </summary>
    /// <param name="vaultName">The name of the Amazon S3 Glacier vault to upload
    /// the archive to.</param>
    /// <param name="archiveFilePath">The file path of the archive to upload to the
vault.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<string> UploadArchiveWithArchiveManager(string vaultName,
string archiveFilePath)
    {
        try
        {
            var manager = new ArchiveTransferManager(_glacierService);

            // Upload an archive.
            var response = await manager.UploadAsync(vaultName, "upload archive
test", archiveFilePath);
            return response.ArchiveId;
        }
```

```
        catch (AmazonGlacierException ex)
        {
            Console.WriteLine(ex.Message);
            return string.Empty;
        }
    }
```

- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for .NET da API.

SageMaker exemplos usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET with SageMaker.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá SageMaker

O exemplo de código a seguir mostra como começar a usar o SageMaker.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SageMaker;
using Amazon.SageMaker.Model;

namespace SageMakerActions;

public static class HelloSageMaker
{
    static async Task Main(string[] args)
    {
        var sageMakerClient = new AmazonSageMakerClient();

        Console.WriteLine($"Hello Amazon SageMaker! Let's list some of your notebook
 instances:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five notebook instances.
        var response = await sageMakerClient.ListNotebookInstancesAsync(
            new ListNotebookInstancesRequest()
            {
                MaxResults = 5
            });

        if (!response.NotebookInstances.Any())
        {
            Console.WriteLine($"No notebook instances found.");
            Console.WriteLine("See https://docs.aws.amazon.com/sagemaker/latest/dg/
howitworks-create-ws.html to create one.");
        }

        foreach (var notebookInstance in response.NotebookInstances)
        {
            Console.WriteLine($"\tInstance:
 {notebookInstance.NotebookInstanceName}");
            Console.WriteLine($"\tArn: {notebookInstance.NotebookInstanceArn}");
            Console.WriteLine($"\tCreation Date:
 {notebookInstance.CreationTime.ToShortDateString()}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar um pipeline

O exemplo de código a seguir mostra como criar ou atualizar um pipeline em SageMaker.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
   /// <summary>
   /// Create a pipeline from a JSON definition, or update it if the pipeline
already exists.
   /// </summary>
   /// <returns>The Amazon Resource Name (ARN) of the pipeline.</returns>
   public async Task<string> SetupPipeline(string pipelineJson, string roleArn,
string name, string description, string displayName)
   {
       try
       {
           var updateResponse = await _amazonSageMaker.UpdatePipelineAsync(
               new UpdatePipelineRequest()
               {
                   PipelineDefinition = pipelineJson,
                   PipelineDescription = description,
                   PipelineDisplayName = displayName,
                   PipelineName = name,
                   RoleArn = roleArn
               });
```

```
            return updateResponse.PipelineArn;
        }
        catch (Amazon.SageMaker.Model.ResourceNotFoundException)
        {
            var createResponse = await _amazonSageMaker.CreatePipelineAsync(
                new CreatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });

            return createResponse.PipelineArn;
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreatePipeline
  - UpdatePipeline

Excluir um pipeline

O exemplo de código a seguir mostra como excluir um pipeline em SageMaker.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a SageMaker pipeline by name.
    /// </summary>
    /// <param name="pipelineName">The name of the pipeline to delete.</param>
    /// <returns>The ARN of the pipeline.</returns>
```

```
    public async Task<string> DeletePipelineByName(string pipelineName)
    {
        var deleteResponse = await _amazonSageMaker.DeletePipelineAsync(
            new DeletePipelineRequest()
            {
                PipelineName = pipelineName
            });

        return deleteResponse.PipelineArn;
    }
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for .NET da API.

Descrever uma execução de pipeline

O exemplo de código a seguir mostra como descrever a execução de um pipeline em SageMaker.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Check the status of a run.
    /// </summary>
    /// <param name="pipelineExecutionArn">The ARN.</param>
    /// <returns>The status of the pipeline.</returns>
    public async Task<PipelineExecutionStatus> CheckPipelineExecutionStatus(string
pipelineExecutionArn)
    {
        var describeResponse = await
_amazonSageMaker.DescribePipelineExecutionAsync(
            new DescribePipelineExecutionRequest()
            {
                PipelineExecutionArn = pipelineExecutionArn
            });

        return describeResponse.PipelineExecutionStatus;
```

```
    }
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for .NET da API.

Executar pipeline

O exemplo de código a seguir mostra como iniciar a execução de um pipeline em SageMaker.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Run a pipeline with input and output file locations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue to use for pipeline
callbacks.</param>
    /// <param name="inputLocationUrl">The input location in Amazon Simple Storage
Service (Amazon S3).</param>
    /// <param name="outputLocationUrl">The output location in Amazon S3.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="executionRoleArn">The ARN of the role.</param>
    /// <returns>The ARN of the pipeline run.</returns>
    public async Task<string> ExecutePipeline(
        string queueUrl,
        string inputLocationUrl,
        string outputLocationUrl,
        string pipelineName,
        string executionRoleArn)
    {
        var inputConfig = new VectorEnrichmentJobInputConfig()
        {
            DataSourceConfig = new()
            {
                S3Data = new VectorEnrichmentJobS3Data()
                {
```

```
                    S3Uri = inputLocationUrl
                }
            },
            DocumentType = VectorEnrichmentJobDocumentType.CSV
        };

        var exportConfig = new ExportVectorEnrichmentJobOutputConfig()
        {
            S3Data = new VectorEnrichmentJobS3Data()
            {
                S3Uri = outputLocationUrl
            }
        };

        var jobConfig = new VectorEnrichmentJobConfig()
        {
            ReverseGeocodingConfig = new ReverseGeocodingConfig()
            {
                XAttributeName = "Longitude",
                YAttributeName = "Latitude"
            }
        };

#pragma warning disable SageMaker1002 // Property value does not match required
 pattern is allowed here to match the pipeline definition.
        var startExecutionResponse = await
 _amazonSageMaker.StartPipelineExecutionAsync(
            new StartPipelineExecutionRequest()
            {
                PipelineName = pipelineName,
                PipelineExecutionDisplayName = pipelineName + "-example-execution",
                PipelineParameters = new List<Parameter>()
                {
                    new Parameter() { Name = "parameter_execution_role", Value =
 executionRoleArn },
                    new Parameter() { Name = "parameter_queue_url", Value =
 queueUrl },
                    new Parameter() { Name = "parameter_vej_input_config", Value =
 JsonSerializer.Serialize(inputConfig) },
                    new Parameter() { Name = "parameter_vej_export_config", Value =
 JsonSerializer.Serialize(exportConfig) },
                    new Parameter() { Name = "parameter_step_1_vej_config", Value =
 JsonSerializer.Serialize(jobConfig) }
                }
```

```
            });
#pragma warning restore SageMaker1002
        return startExecutionResponse.PipelineExecutionArn;
    }
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for .NET da API.

Cenários

Iniciar com trabalhos geoespaciais e pipelines

O código de exemplo a seguir mostra como:

- Configurar recursos para um pipeline.
- Configurar um pipeline que execute um trabalho geoespacial.
- Inicie a execução de um pipeline.
- Monitorar o status da execução.
- Ver saída do pipeline.
- Limpe os recursos.

Para obter mais informações, consulte Criar e executar SageMaker pipelines usando AWS SDKs no Community.aws.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as SageMaker operações.

```
using System.Text.Json;
using Amazon.SageMaker;
using Amazon.SageMaker.Model;
```

```
using Amazon.SageMakerGeospatial;
using Amazon.SageMakerGeospatial.Model;

namespace SageMakerActions;

/// <summary>
/// Wrapper class for Amazon SageMaker actions and logic.
/// </summary>
public class SageMakerWrapper
{
    private readonly IAmazonSageMaker _amazonSageMaker;
    public SageMakerWrapper(IAmazonSageMaker amazonSageMaker)
    {
        _amazonSageMaker = amazonSageMaker;
    }

    /// <summary>
    /// Create a pipeline from a JSON definition, or update it if the pipeline
 already exists.
    /// </summary>
    /// <returns>The Amazon Resource Name (ARN) of the pipeline.</returns>
    public async Task<string> SetupPipeline(string pipelineJson, string roleArn,
 string name, string description, string displayName)
    {
        try
        {
            var updateResponse = await _amazonSageMaker.UpdatePipelineAsync(
                new UpdatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });
            return updateResponse.PipelineArn;
        }
        catch (Amazon.SageMaker.Model.ResourceNotFoundException)
        {
            var createResponse = await _amazonSageMaker.CreatePipelineAsync(
                new CreatePipelineRequest()
                {
                    PipelineDefinition = pipelineJson,
                    PipelineDescription = description,
```

```
                    PipelineDisplayName = displayName,
                    PipelineName = name,
                    RoleArn = roleArn
                });

            return createResponse.PipelineArn;
        }
    }

    /// <summary>
    /// Run a pipeline with input and output file locations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue to use for pipeline
callbacks.</param>
    /// <param name="inputLocationUrl">The input location in Amazon Simple Storage
Service (Amazon S3).</param>
    /// <param name="outputLocationUrl">The output location in Amazon S3.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="executionRoleArn">The ARN of the role.</param>
    /// <returns>The ARN of the pipeline run.</returns>
    public async Task<string> ExecutePipeline(
        string queueUrl,
        string inputLocationUrl,
        string outputLocationUrl,
        string pipelineName,
        string executionRoleArn)
    {
        var inputConfig = new VectorEnrichmentJobInputConfig()
        {
            DataSourceConfig = new()
            {
                S3Data = new VectorEnrichmentJobS3Data()
                {
                    S3Uri = inputLocationUrl
                }
            },
            DocumentType = VectorEnrichmentJobDocumentType.CSV
        };

        var exportConfig = new ExportVectorEnrichmentJobOutputConfig()
        {
            S3Data = new VectorEnrichmentJobS3Data()
            {
                S3Uri = outputLocationUrl
```

```
            }
        };

        var jobConfig = new VectorEnrichmentJobConfig()
        {
            ReverseGeocodingConfig = new ReverseGeocodingConfig()
            {
                XAttributeName = "Longitude",
                YAttributeName = "Latitude"
            }
        };

#pragma warning disable SageMaker1002 // Property value does not match required
 pattern is allowed here to match the pipeline definition.
        var startExecutionResponse = await
 _amazonSageMaker.StartPipelineExecutionAsync(
            new StartPipelineExecutionRequest()
            {
                PipelineName = pipelineName,
                PipelineExecutionDisplayName = pipelineName + "-example-execution",
                PipelineParameters = new List<Parameter>()
                {
                    new Parameter() { Name = "parameter_execution_role", Value =
 executionRoleArn },
                    new Parameter() { Name = "parameter_queue_url", Value =
 queueUrl },
                    new Parameter() { Name = "parameter_vej_input_config", Value =
 JsonSerializer.Serialize(inputConfig) },
                    new Parameter() { Name = "parameter_vej_export_config", Value =
 JsonSerializer.Serialize(exportConfig) },
                    new Parameter() { Name = "parameter_step_1_vej_config", Value =
 JsonSerializer.Serialize(jobConfig) }
                }
            });
#pragma warning restore SageMaker1002
        return startExecutionResponse.PipelineExecutionArn;
    }

    /// <summary>
    /// Check the status of a run.
    /// </summary>
    /// <param name="pipelineExecutionArn">The ARN.</param>
    /// <returns>The status of the pipeline.</returns>
```

```
    public async Task<PipelineExecutionStatus> CheckPipelineExecutionStatus(string
 pipelineExecutionArn)
    {
        var describeResponse = await
 _amazonSageMaker.DescribePipelineExecutionAsync(
            new DescribePipelineExecutionRequest()
            {
                PipelineExecutionArn = pipelineExecutionArn
            });

        return describeResponse.PipelineExecutionStatus;
    }

    /// <summary>
    /// Delete a SageMaker pipeline by name.
    /// </summary>
    /// <param name="pipelineName">The name of the pipeline to delete.</param>
    /// <returns>The ARN of the pipeline.</returns>
    public async Task<string> DeletePipelineByName(string pipelineName)
    {
        var deleteResponse = await _amazonSageMaker.DeletePipelineAsync(
            new DeletePipelineRequest()
            {
                PipelineName = pipelineName
            });

        return deleteResponse.PipelineArn;
    }
}
```

Crie uma função que gerencie retornos de chamada do SageMaker pipeline.

```
using System.Text.Json;
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;
using Amazon.SageMaker;
using Amazon.SageMaker.Model;
using Amazon.SageMakerGeospatial;
using Amazon.SageMakerGeospatial.Model;
```

```
// Assembly attribute to enable the AWS Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace SageMakerLambda;

/// <summary>
/// The AWS Lambda function handler for the Amazon SageMaker pipeline.
/// </summary>
public class SageMakerLambdaFunction
{
    /// <summary>
    /// Default constructor. This constructor is used by AWS Lambda to construct the
 instance. When invoked in a Lambda environment
    /// the AWS credentials will come from the AWS Identity and Access Management
 (IAM) role associated with the function. The AWS Region will be set to the
    /// Region that the Lambda function is running in.
    /// </summary>
    public SageMakerLambdaFunction()
    {
    }

    /// <summary>
    /// The AWS Lambda function handler that processes events from the SageMaker
 pipeline and starts a job or export.
    /// </summary>
    /// <param name="request">The custom SageMaker pipeline request object.</param>
    /// <param name="context">The Lambda context.</param>
    /// <returns>The dictionary of output parameters.</returns>
    public async Task<Dictionary<string, string>> FunctionHandler(PipelineRequest
 request, ILambdaContext context)
    {
        var geoSpatialClient = new AmazonSageMakerGeospatialClient();
        var sageMakerClient = new AmazonSageMakerClient();
        var responseDictionary = new Dictionary<string, string>();
        context.Logger.LogInformation("Function handler started with request: " +
 JsonSerializer.Serialize(request));
        if (request.Records != null && request.Records.Any())
        {
            context.Logger.LogInformation("Records found, this is a queue event.
 Processing the queue records.");
            foreach (var message in request.Records)
            {
```

```
                await ProcessMessageAsync(message, context, geoSpatialClient,
sageMakerClient);
            }
        }
        else if (!string.IsNullOrEmpty(request.vej_export_config))
        {
            context.Logger.LogInformation("Export configuration found, this is an
export. Start the Vector Enrichment Job (VEJ) export.");

            var outputConfig =
                JsonSerializer.Deserialize<ExportVectorEnrichmentJobOutputConfig>(
                    request.vej_export_config);

            var exportResponse = await
geoSpatialClient.ExportVectorEnrichmentJobAsync(
                new ExportVectorEnrichmentJobRequest()
                {
                    Arn = request.vej_arn,
                    ExecutionRoleArn = request.Role,
                    OutputConfig = outputConfig
                });
            context.Logger.LogInformation($"Export response:
{JsonSerializer.Serialize(exportResponse)}");
            responseDictionary = new Dictionary<string, string>
            {
                { "export_eoj_status", exportResponse.ExportStatus.ToString() },
                { "vej_arn", exportResponse.Arn }
            };
        }
        else if (!string.IsNullOrEmpty(request.vej_name))
        {
            context.Logger.LogInformation("Vector Enrichment Job name found,
starting the job.");
            var inputConfig =
                JsonSerializer.Deserialize<VectorEnrichmentJobInputConfig>(
                    request.vej_input_config);

            var jobConfig =
                JsonSerializer.Deserialize<VectorEnrichmentJobConfig>(
                    request.vej_config);

            var jobResponse = await geoSpatialClient.StartVectorEnrichmentJobAsync(
                new StartVectorEnrichmentJobRequest()
                {
```

```
                    ExecutionRoleArn = request.Role,
                    InputConfig = inputConfig,
                    Name = request.vej_name,
                    JobConfig = jobConfig

                });
            context.Logger.LogInformation("Job response: " +
JsonSerializer.Serialize(jobResponse));
            responseDictionary = new Dictionary<string, string>
            {
                { "vej_arn", jobResponse.Arn },
                { "statusCode", jobResponse.HttpStatusCode.ToString() }
            };
        }
        return responseDictionary;
    }

    /// <summary>
    /// Process a queue message and check the status of a SageMaker job.
    /// </summary>
    /// <param name="message">The queue message.</param>
    /// <param name="context">The Lambda context.</param>
    /// <param name="geoClient">The SageMaker GeoSpatial client.</param>
    /// <param name="sageMakerClient">The SageMaker client.</param>
    /// <returns>Async task.</returns>
    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
ILambdaContext context,
        AmazonSageMakerGeospatialClient geoClient, AmazonSageMakerClient
sageMakerClient)
    {
        context.Logger.LogInformation($"Processed message {message.Body}");

        // Get information about the SageMaker job.
        var payload = JsonSerializer.Deserialize<QueuePayload>(message.Body);
        context.Logger.LogInformation($"Payload token {payload!.token}");
        var token = payload.token;

        if (payload.arguments.ContainsKey("vej_arn"))
        {
            // Use the job ARN and the token to get the job status.
            var job_arn = payload.arguments["vej_arn"];
            context.Logger.LogInformation($"Token: {token}, arn {job_arn}");

            var jobInfo = geoClient.GetVectorEnrichmentJobAsync(
```

```
                new GetVectorEnrichmentJobRequest()
                {
                    Arn = job_arn
                });
            context.Logger.LogInformation("Job info: " +
 JsonSerializer.Serialize(jobInfo));
            if (jobInfo.Result.Status == VectorEnrichmentJobStatus.COMPLETED)
            {
                context.Logger.LogInformation($"Status completed, resuming
 pipeline...");
                await sageMakerClient.SendPipelineExecutionStepSuccessAsync(
                    new SendPipelineExecutionStepSuccessRequest()
                    {
                        CallbackToken = token,
                        OutputParameters = new List<OutputParameter>()
                        {
                            new OutputParameter()
                                { Name = "export_status", Value =
 jobInfo.Result.Status }
                        }
                    });
            }
            else if (jobInfo.Result.Status == VectorEnrichmentJobStatus.FAILED)
            {
                context.Logger.LogInformation($"Status failed, stopping
 pipeline...");
                await sageMakerClient.SendPipelineExecutionStepFailureAsync(
                    new SendPipelineExecutionStepFailureRequest()
                    {
                        CallbackToken = token,
                        FailureReason = jobInfo.Result.ErrorDetails.ErrorMessage
                    });
            }
            else if (jobInfo.Result.Status == VectorEnrichmentJobStatus.IN_PROGRESS)
            {
                // Put this message back in the queue to reprocess later.
                context.Logger.LogInformation(
                    $"Status still in progress, check back later.");
                throw new("Job still running.");
            }
        }
    }
}
```

Execute um cenário interativo em um prompt de comando.

```
public static class PipelineWorkflow
{
    public static IAmazonIdentityManagementService _iamClient = null!;
    public static SageMakerWrapper _sageMakerWrapper = null!;
    public static IAmazonSQS _sqsClient = null!;
    public static IAmazonS3 _s3Client = null!;
    public static IAmazonLambda _lambdaClient = null!;
    public static IConfiguration _configuration = null!;

    public static string lambdaFunctionName = "SageMakerExampleFunction";
    public static string sageMakerRoleName = "SageMakerExampleRole";
    public static string lambdaRoleName = "SageMakerExampleLambdaRole";

    private static string[] lambdaRolePolicies = null!;
    private static string[] sageMakerRolePolicies = null!;

    static async Task Main(string[] args)
    {
        var options = new AWSOptions() { Region = RegionEndpoint.USWest2 };
        // Set up dependency injection for the AWS service.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonIdentityManagementService>(options)
                    .AddAWSService<IAmazonEC2>(options)
                    .AddAWSService<IAmazonSageMaker>(options)
                    .AddAWSService<IAmazonSageMakerGeospatial>(options)
                    .AddAWSService<IAmazonSQS>(options)
                    .AddAWSService<IAmazonS3>(options)
                    .AddAWSService<IAmazonLambda>(options)
                    .AddTransient<SageMakerWrapper>()
        )
        .Build();

        _configuration = new ConfigurationBuilder()
```

```
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load settings from .json file.
            .AddJsonFile("settings.local.json",
                true) // Optionally, load local settings.
            .Build();

        ServicesSetup(host);
        string queueUrl = "";
        string queueName = _configuration["queueName"];
        string bucketName = _configuration["bucketName"];
        var pipelineName = _configuration["pipelineName"];

        try
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine(
                "Welcome to the Amazon SageMaker pipeline example scenario.");
            Console.WriteLine(
                "\nThis example workflow will guide you through setting up and
running an" +
                "\nAmazon SageMaker pipeline. The pipeline uses an AWS Lambda
function and an" +
                "\nAmazon SQS Queue. It runs a vector enrichment reverse geocode job
to" +
                "\nreverse geocode addresses in an input file and store the results
in an export file.");
            Console.WriteLine(new string('-', 80));

            Console.WriteLine(new string('-', 80));
            Console.WriteLine(
                "First, we will set up the roles, functions, and queue needed by the
SageMaker pipeline.");
            Console.WriteLine(new string('-', 80));

            var lambdaRoleArn = await CreateLambdaRole();
            var sageMakerRoleArn = await CreateSageMakerRole();
            var functionArn = await SetupLambda(lambdaRoleArn, true);
            queueUrl = await SetupQueue(queueName);
            await SetupBucket(bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Now we can create and run our pipeline.");
            Console.WriteLine(new string('-', 80));
```

```
            await SetupPipeline(sageMakerRoleArn, functionArn, pipelineName);
            var executionArn = await ExecutePipeline(queueUrl, sageMakerRoleArn,
 pipelineName, bucketName);
            await WaitForPipelineExecution(executionArn);

            await GetOutputResults(bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("The pipeline has completed. To view the pipeline and
 runs " +
                              "in SageMaker Studio, follow these instructions:" +
                              "\nhttps://docs.aws.amazon.com/sagemaker/latest/dg/
pipelines-studio.html");
            Console.WriteLine(new string('-', 80));

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("Finally, let's clean up our resources.");
            Console.WriteLine(new string('-', 80));

            await CleanupResources(true, queueUrl, pipelineName, bucketName);

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("SageMaker pipeline scenario is complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
 {ex.Message}");
            await CleanupResources(true, queueUrl, pipelineName, bucketName);
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        _sageMakerWrapper = host.Services.GetRequiredService<SageMakerWrapper>();
        _iamClient =
 host.Services.GetRequiredService<IAmazonIdentityManagementService>();
```

```
        _sqsClient = host.Services.GetRequiredService<IAmazonSQS>();
        _s3Client = host.Services.GetRequiredService<IAmazonS3>();
        _lambdaClient = host.Services.GetRequiredService<IAmazonLambda>();
    }

    /// <summary>
    /// Set up AWS Lambda, either by updating an existing function or creating a new
function.
    /// </summary>
    /// <param name="roleArn">The role Amazon Resource Name (ARN) to use for the
Lambda function.</param>
    /// <param name="askUser">True to ask the user before updating.</param>
    /// <returns>The ARN of the function.</returns>
    public static async Task<string> SetupLambda(string roleArn, bool askUser)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Setting up the Lambda function for the pipeline.");
        var handlerName =
"SageMakerLambda::SageMakerLambda.SageMakerLambdaFunction::FunctionHandler";
        var functionArn = "";
        try
        {
            var functionInfo = await _lambdaClient.GetFunctionAsync(new
GetFunctionRequest()
            {
                FunctionName = lambdaFunctionName
            });

            var updateFunction = true;
            if (askUser)
            {
                updateFunction = GetYesNoResponse(
                    $"\tThe Lambda function {lambdaFunctionName} already exists, do
you want to update it?");
            }

            if (updateFunction)
            {
                // Update the Lambda function.
                using var zipMemoryStream = new MemoryStream(await
File.ReadAllBytesAsync("SageMakerLambda.zip"));
                await _lambdaClient.UpdateFunctionCodeAsync(
                    new UpdateFunctionCodeRequest()
                    {
```

```
                        FunctionName = lambdaFunctionName,
                        ZipFile = zipMemoryStream,
                    });
            }

            functionArn = functionInfo.Configuration.FunctionArn;
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine($"\tThe Lambda function {lambdaFunctionName} was not
found, creating the new function.");

            // Create the function if it does not already exist.
            using var zipMemoryStream = new MemoryStream(await
File.ReadAllBytesAsync("SageMakerLambda.zip"));
            var createResult = await _lambdaClient.CreateFunctionAsync(
                new CreateFunctionRequest()
                {
                    FunctionName = lambdaFunctionName,
                    Runtime = Runtime.Dotnet6,
                    Description = "SageMaker example function.",
                    Code = new FunctionCode()
                    {
                        ZipFile = zipMemoryStream
                    },
                    Handler = handlerName,
                    Role = roleArn,
                    Timeout = 30
                });

            functionArn = createResult.FunctionArn;
        }

        Console.WriteLine($"\tLambda ready with ARN {functionArn}.");
        Console.WriteLine(new string('-', 80));
        return functionArn;
    }

    /// <summary>
    /// Create a role to be used by AWS Lambda. Does not create the role if it
already exists.
    /// </summary>
    /// <returns>The role ARN.</returns>
    public static async Task<string> CreateLambdaRole()
```

```
    {
        Console.WriteLine(new string('-', 80));

        lambdaRolePolicies = new string[]{
            "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess",
            "arn:aws:iam::aws:policy/AmazonSQSFullAccess",
            "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess",
            "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy",
            "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole"
        };

        var roleArn = await GetRoleArnIfExists(lambdaRoleName);
        if (!string.IsNullOrEmpty(roleArn))
        {
            return roleArn;
        }

        Console.WriteLine("\tCreating a role to for AWS Lambda to use.");

        var assumeRolePolicy = "{" +
                               "\"Version\": \"2012-10-17\"," +
                               "\"Statement\": [{" +
                                    "\"Effect\": \"Allow\"," +
                                    "\"Principal\": {" +
                                        $"\"Service\": [" +
                                            "\"sagemaker.amazonaws.com\"," +
                                            "\"sagemaker-geospatial.amazonaws.com
\"," +
                                            "\"lambda.amazonaws.com\"," +
                                            "\"s3.amazonaws.com\"" +
                                        "]" +
                                    "}," +
                                    "\"Action\": \"sts:AssumeRole\"" +
                               "}]" +
                           "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
```

```
                RoleName = lambdaRoleName
            });
        foreach (var policy in lambdaRolePolicies)
        {
            await _iamClient.AttachRolePolicyAsync(
                new AttachRolePolicyRequest()
                {
                    PolicyArn = policy,
                    RoleName = lambdaRoleName
                });
        }

        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        Console.WriteLine($"\tRole ready with ARN {roleResult.Role.Arn}.");
        Console.WriteLine(new string('-', 80));

        return roleResult.Role.Arn;
    }


    /// <summary>
    /// Create a role to be used by SageMaker.
    /// </summary>
    /// <returns>The role Amazon Resource Name (ARN).</returns>
    public static async Task<string> CreateSageMakerRole()
    {
        Console.WriteLine(new string('-', 80));

        sageMakerRolePolicies = new string[]{
            "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess",
            "arn:aws:iam::aws:policy/AmazonSageMakerGeospatialFullAccess",
        };

        var roleArn = await GetRoleArnIfExists(sageMakerRoleName);
        if (!string.IsNullOrEmpty(roleArn))
        {
            return roleArn;
        }

        Console.WriteLine("\tCreating a role to use with SageMaker.");

        var assumeRolePolicy = "{" +
                                        "\"Version\": \"2012-10-17\"," +
```

```
                                        "\"Statement\": [{" +
                                            "\"Effect\": \"Allow\"," +
                                            "\"Principal\": {" +
                                                $"\"Service\": [" +
                                                    "\"sagemaker.amazonaws.com\"," +
                                                    "\"sagemaker-
geospatial.amazonaws.com\"," +
                                                    "\"lambda.amazonaws.com\"," +
                                                    "\"s3.amazonaws.com\"" +
                                                "]" +
                                            "}," +
                                            "\"Action\": \"sts:AssumeRole\"" +
                                        "}]" +
                                    "}";

        var roleResult = await _iamClient!.CreateRoleAsync(
            new CreateRoleRequest()
            {
                AssumeRolePolicyDocument = assumeRolePolicy,
                Path = "/",
                RoleName = sageMakerRoleName
            });

        foreach (var policy in sageMakerRolePolicies)
        {
            await _iamClient.AttachRolePolicyAsync(
                new AttachRolePolicyRequest()
                {
                    PolicyArn = policy,
                    RoleName = sageMakerRoleName
                });
        }

        // Allow time for the role to be ready.
        Thread.Sleep(10000);
        Console.WriteLine($"\tRole ready with ARN {roleResult.Role.Arn}.");
        Console.WriteLine(new string('-', 80));
        return roleResult.Role.Arn;
    }

    /// <summary>
    /// Set up the SQS queue to use with the pipeline.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
```

```
    /// <returns>The URL for the queue.</returns>
    public static async Task<string> SetupQueue(string queueName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Setting up queue {queueName}.");

        try
        {
            var queueInfo = await _sqsClient.GetQueueUrlAsync(new
GetQueueUrlRequest()
            { QueueName = queueName });
            return queueInfo.QueueUrl;
        }
        catch (QueueDoesNotExistException)
        {
            var attrs = new Dictionary<string, string>
            {
                {
                    QueueAttributeName.DelaySeconds,
                    "5"
                },
                {
                    QueueAttributeName.ReceiveMessageWaitTimeSeconds,
                    "5"
                },
                {
                    QueueAttributeName.VisibilityTimeout,
                    "300"
                },
            };

            var request = new CreateQueueRequest
            {
                Attributes = attrs,
                QueueName = queueName,
            };

            var response = await _sqsClient.CreateQueueAsync(request);
            Thread.Sleep(10000);
            await ConnectLambda(response.QueueUrl);
            Console.WriteLine($"\tQueue ready with Url {response.QueueUrl}.");
            Console.WriteLine(new string('-', 80));
            return response.QueueUrl;
        }
```

```
    }

    /// <summary>
    /// Connect the queue to the Lambda function as an event source.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue.</param>
    /// <returns>Async task.</returns>
    public static async Task ConnectLambda(string queueUrl)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Connecting the Lambda function and queue for the
pipeline.");

        var queueAttributes = await _sqsClient.GetQueueAttributesAsync(
            new GetQueueAttributesRequest() { QueueUrl = queueUrl, AttributeNames =
new List<string>() { "All" } });
        var queueArn = queueAttributes.QueueARN;

        var eventSource = await _lambdaClient.ListEventSourceMappingsAsync(
             new ListEventSourceMappingsRequest()
             {
                 FunctionName = lambdaFunctionName
             });

        if (!eventSource.EventSourceMappings.Any())
        {
            // Only add the event source mapping if it does not already exist.
            await _lambdaClient.CreateEventSourceMappingAsync(
                new CreateEventSourceMappingRequest()
                {
                    EventSourceArn = queueArn,
                    FunctionName = lambdaFunctionName,
                    Enabled = true
                });
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the bucket to use for pipeline input and output.
    /// </summary>
    /// <param name="bucketName">The name for the bucket.</param>
    /// <returns>Async task.</returns>
```

```
    public static async Task SetupBucket(string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Setting up bucket {bucketName}.");

        var bucketExists = await
Amazon.S3.Util.AmazonS3Util.DoesS3BucketExistV2Async(_s3Client,
            bucketName);

        if (!bucketExists)
        {
            await _s3Client.PutBucketAsync(new PutBucketRequest()
            {
                BucketName = bucketName,
                BucketRegion = S3Region.USWest2
            });

            Thread.Sleep(5000);

            await _s3Client.PutObjectAsync(new PutObjectRequest()
            {
                BucketName = bucketName,
                Key = "samplefiles/latlongtest.csv",
                FilePath = "latlongtest.csv"
            });
        }

        Console.WriteLine($"\tBucket {bucketName} ready.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Display some results from the output directory.
    /// </summary>
    /// <param name="bucketName">The name for the bucket.</param>
    /// <returns>Async task.</returns>
    public static async Task<string> GetOutputResults(string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Getting output results {bucketName}.");
        string outputKey = "";
        Thread.Sleep(15000);
        var outputFiles = await _s3Client.ListObjectsAsync(
              new ListObjectsRequest()
```

```
                {
                    BucketName = bucketName,
                    Prefix = "outputfiles/"
                });

        if (outputFiles.S3Objects.Any())
        {
            var sampleOutput = outputFiles.S3Objects.OrderBy(s =>
 s.LastModified).Last();
            Console.WriteLine($"\tOutput file: {sampleOutput.Key}");
            var outputSampleResponse = await _s3Client.GetObjectAsync(
                new GetObjectRequest()
                {
                    BucketName = bucketName,
                    Key = sampleOutput.Key
                });
            outputKey = sampleOutput.Key;
            StreamReader reader = new
 StreamReader(outputSampleResponse.ResponseStream);
            await reader.ReadLineAsync();
            Console.WriteLine("\tOutput file contents: \n");
            for (int i = 0; i < 10; i++)
            {
                if (!reader.EndOfStream)
                {
                    Console.WriteLine("\t" + await reader.ReadLineAsync());
                }
            }
        }

        Console.WriteLine(new string('-', 80));
        return outputKey;
    }

    /// <summary>
    /// Create a pipeline from the example pipeline JSON
    /// that includes the Lambda, callback, processing, and export jobs.
    /// </summary>
    /// <param name="roleArn">The ARN of the role for the pipeline.</param>
    /// <param name="functionArn">The ARN of the Lambda function for the pipeline.</
param>
    /// <param name="pipelineName">The name for the pipeline.</param>
    /// <returns>The ARN of the pipeline.</returns>
```

```
    public static async Task<string> SetupPipeline(string roleArn, string
functionArn, string pipelineName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Setting up the pipeline.");

        var pipelineJson = await File.ReadAllTextAsync("GeoSpatialPipeline.json");

        // Add the correct function ARN instead of the placeholder.
        pipelineJson = pipelineJson.Replace("*FUNCTION_ARN*", functionArn);

        var pipelineArn = await _sageMakerWrapper.SetupPipeline(pipelineJson,
roleArn, pipelineName,
            "sdk example pipeline", pipelineName);

        Console.WriteLine($"\tPipeline set up with ARN {pipelineArn}.");
        Console.WriteLine(new string('-', 80));

        return pipelineArn;
    }

    /// <summary>
    /// Start a pipeline run with job configurations.
    /// </summary>
    /// <param name="queueUrl">The URL for the queue used in the pipeline.</param>
    /// <param name="roleArn">The ARN of the role.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="bucketName">The name of the bucket.</param>
    /// <returns>The pipeline run ARN.</returns>
    public static async Task<string> ExecutePipeline(
        string queueUrl,
        string roleArn,
        string pipelineName,
        string bucketName)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Starting pipeline execution.");

        var input = $"s3://{bucketName}/samplefiles/latlongtest.csv";
        var output = $"s3://{bucketName}/outputfiles/";

        var executionARN =
            await _sageMakerWrapper.ExecutePipeline(queueUrl, input, output,
                pipelineName, roleArn);
```

```
        Console.WriteLine($"\tRun started with ARN {executionARN}.");
        Console.WriteLine(new string('-', 80));

        return executionARN;
    }

    /// <summary>
    /// Wait for a pipeline run to complete.
    /// </summary>
    /// <param name="executionArn">The pipeline run ARN.</param>
    /// <returns>Async task.</returns>
    public static async Task WaitForPipelineExecution(string executionArn)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Waiting for pipeline to finish.");

        PipelineExecutionStatus status;
        do
        {
            status = await
_sageMakerWrapper.CheckPipelineExecutionStatus(executionArn);
            Thread.Sleep(30000);
            Console.WriteLine($"\tStatus is {status}.");
        } while (status == PipelineExecutionStatus.Executing);

        Console.WriteLine($"\tPipeline finished with status {status}.");
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <param name="askUser">True to ask the user for cleanup.</param>
    /// <param name="queueUrl">The URL of the queue to clean up.</param>
    /// <param name="pipelineName">The name of the pipeline.</param>
    /// <param name="bucketName">The name of the bucket.</param>
    /// <returns>Async task.</returns>
    public static async Task<bool> CleanupResources(
        bool askUser,
        string queueUrl,
        string pipelineName,
        string bucketName)
    {
```

```
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        if (!askUser || GetYesNoResponse($"\tDelete pipeline {pipelineName}? (y/
n)"))
        {
            Console.WriteLine($"\tDeleting pipeline.");
            // Delete the pipeline.
            await _sageMakerWrapper.DeletePipelineByName(pipelineName);
        }

        if (!string.IsNullOrEmpty(queueUrl) && (!askUser ||
 GetYesNoResponse($"\tDelete queue {queueUrl}? (y/n)")))
        {
            Console.WriteLine($"\tDeleting queue.");
            // Delete the queue.
            await _sqsClient.DeleteQueueAsync(new DeleteQueueRequest(queueUrl));
        }

        if (!askUser || GetYesNoResponse($"\tDelete Amazon S3 bucket {bucketName}?
 (y/n)"))
        {
            Console.WriteLine($"\tDeleting bucket.");
            // Delete all objects in the bucket.
            var deleteList = await _s3Client.ListObjectsV2Async(new
 ListObjectsV2Request()
            {
                BucketName = bucketName
            });
            if (deleteList.KeyCount > 0)
            {
                await _s3Client.DeleteObjectsAsync(new DeleteObjectsRequest()
                {
                    BucketName = bucketName,
                    Objects = deleteList.S3Objects
                        .Select(o => new KeyVersion { Key = o.Key }).ToList()
                });
            }

            // Now delete the bucket.
            await _s3Client.DeleteBucketAsync(new DeleteBucketRequest()
            {
                BucketName = bucketName
            });
```

```
        }

        if (!askUser || GetYesNoResponse($"\tDelete lambda {lambdaFunctionName}? (y/
n)"))
        {
            Console.WriteLine($"\tDeleting lambda function.");

            await _lambdaClient.DeleteFunctionAsync(new DeleteFunctionRequest()
            {
                FunctionName = lambdaFunctionName
            });
        }

        if (!askUser || GetYesNoResponse($"\tDelete role {lambdaRoleName}? (y/n)"))
        {
            Console.WriteLine($"\tDetaching policies and deleting role.");

            foreach (var policy in lambdaRolePolicies)
            {
                await _iamClient!.DetachRolePolicyAsync(new
 DetachRolePolicyRequest()
                {
                    RoleName = lambdaRoleName,
                    PolicyArn = policy
                });
            }

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = lambdaRoleName
            });
        }

        if (!askUser || GetYesNoResponse($"\tDelete role {sageMakerRoleName}? (y/
n)"))
        {
            Console.WriteLine($"\tDetaching policies and deleting role.");

            foreach (var policy in sageMakerRolePolicies)
            {
                await _iamClient!.DetachRolePolicyAsync(new
 DetachRolePolicyRequest()
                {
                    RoleName = sageMakerRoleName,
```

```
                    PolicyArn = policy
                });
            }

            await _iamClient!.DeleteRoleAsync(new DeleteRoleRequest()
            {
                RoleName = sageMakerRoleName
            });
        }

        Console.WriteLine(new string('-', 80));
        return true;
    }

    /// <summary>
    /// Helper method to get a role's ARN if it already exists.
    /// </summary>
    /// <param name="roleName">The name of the AWS Identity and Access Management
(IAM) Role to look for.</param>
    /// <returns>The role ARN if it exists, otherwise an empty string.</returns>
    private static async Task<string> GetRoleArnIfExists(string roleName)
    {
        Console.WriteLine($"Checking for role named {roleName}.");

        try
        {
            var existingRole = await _iamClient.GetRoleAsync(new GetRoleRequest()
            {
                RoleName = lambdaRoleName
            });
            return existingRole.Role.Arn;
        }
        catch (NoSuchEntityException)
        {
            return string.Empty;
        }
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question)
```

```
    {
        Console.WriteLine(question);
        var ynResponse = Console.ReadLine();
        var response = ynResponse != null &&
                       ynResponse.Equals("y",
                           StringComparison.InvariantCultureIgnoreCase);
        return response;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Exemplos do Secrets Manager usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.IO;
using System.Threading.Tasks;
using Amazon.SecretsManager;
using Amazon.SecretsManager.Model;

/// <summary>
/// This example uses the Amazon Web Service Secrets Manager to retrieve
/// the secret value for the provided secret name.
/// </summary>
public class GetSecretValue
{
    /// <summary>
    /// The main method initializes the necessary values and then calls
    /// the GetSecretAsync and DecodeString methods to get the decoded
    /// secret value for the secret named in secretName.
    /// </summary>
    public static async Task Main()
    {
        string secretName = "<<{{MySecretName}}>>";
        string secret;

        IAmazonSecretsManager client = new AmazonSecretsManagerClient();

        var response = await GetSecretAsync(client, secretName);

        if (response is not null)
        {
            secret = DecodeString(response);
```

```
                if (!string.IsNullOrEmpty(secret))
                {
                    Console.WriteLine($"The decoded secret value is: {secret}.");
                }
                else
                {
                    Console.WriteLine("No secret value was returned.");
                }
            }
        }

        /// <summary>
        /// Retrieves the secret value given the name of the secret to
        /// retrieve.
        /// </summary>
        /// <param name="client">The client object used to retrieve the secret
        /// value for the given secret name.</param>
        /// <param name="secretName">The name of the secret value to retrieve.</
param>
        /// <returns>The GetSecretValueReponse object returned by
        /// GetSecretValueAsync.</returns>
        public static async Task<GetSecretValueResponse> GetSecretAsync(
            IAmazonSecretsManager client,
            string secretName)
        {
            GetSecretValueRequest request = new GetSecretValueRequest()
            {
                SecretId = secretName,
                VersionStage = "AWSCURRENT", // VersionStage defaults to AWSCURRENT
 if unspecified.
            };

            GetSecretValueResponse response = null;

            // For the sake of simplicity, this example handles only the most
            // general SecretsManager exception.
            try
            {
                response = await client.GetSecretValueAsync(request);
            }
            catch (AmazonSecretsManagerException e)
            {
                Console.WriteLine($"Error: {e.Message}");
```

```
            }

            return response;
        }

        /// <summary>
        /// Decodes the secret returned by the call to GetSecretValueAsync and
        /// returns it to the calling program.
        /// </summary>
        /// <param name="response">A GetSecretValueResponse object containing
        /// the requested secret value returned by GetSecretValueAsync.</param>
        /// <returns>A string representing the decoded secret value.</returns>
        public static string DecodeString(GetSecretValueResponse response)
        {
            // Decrypts secret using the associated AWS Key Management Service
            // Customer Master Key (CMK.) Depending on whether the secret is a
            // string or binary value, one of these fields will be populated.
            if (response.SecretString is not null)
            {
                var secret = response.SecretString;
                return secret;
            }
            else if (response.SecretBinary is not null)
            {
                var memoryStream = response.SecretBinary;
                StreamReader reader = new StreamReader(memoryStream);
                string decodedBinarySecret =
System.Text.Encoding.UTF8.GetString(Convert.FromBase64String(reader.ReadToEnd()));
                return decodedBinarySecret;
            }
            else
            {
                return string.Empty;
            }
        }
    }
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for .NET da API.

Exemplos do Amazon SES usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um modelo de e-mail

O exemplo de código a seguir mostra como criar um modelo de e-mail do Amazon SES.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Create an email template.
/// </summary>
/// <param name="name">Name of the template.</param>
/// <param name="subject">Email subject.</param>
/// <param name="text">Email body text.</param>
```

```
    /// <param name="html">Email HTML body text.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> CreateEmailTemplateAsync(string name, string subject,
string text,
        string html)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.CreateTemplateAsync(
                new CreateTemplateRequest
                {
                    Template = new Template
                    {
                        TemplateName = name,
                        SubjectPart = subject,
                        TextPart = text,
                        HtmlPart = html
                    }
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("CreateEmailTemplateAsync failed with exception: " +
ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for .NET da API.

Excluir um modelo de e-mail

O exemplo de código a seguir mostra como excluir um modelo de e-mail do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an email template.
    /// </summary>
    /// <param name="templateName">Name of the template.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteEmailTemplateAsync(string templateName)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.DeleteTemplateAsync(
                new DeleteTemplateRequest
                {
                    TemplateName = templateName
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("DeleteEmailTemplateAsync failed with exception: " +
ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for .NET da API.

Excluir uma identidade

O exemplo de código a seguir mostra como excluir uma identidade do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete an email identity.
    /// </summary>
    /// <param name="identityEmail">The identity email to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteIdentityAsync(string identityEmail)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.DeleteIdentityAsync(
                new DeleteIdentityRequest
                {
                    Identity = identityEmail
                });
            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("DeleteIdentityAsync failed with exception: " +
ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for .NET da API.

Obter limites de envio

O exemplo de código a seguir mostra como obter limites de envio do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get information on the current account's send quota.
    /// </summary>
    /// <returns>The send quota response data.</returns>
    public async Task<GetSendQuotaResponse> GetSendQuotaAsync()
    {
        var result = new GetSendQuotaResponse();
        try
        {
            var response = await _amazonSimpleEmailService.GetSendQuotaAsync(
                new GetSendQuotaRequest());
            result = response;
        }
        catch (Exception ex)
        {
            Console.WriteLine("GetSendQuotaAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte GetSendQuotaa Referência AWS SDK for .NET da API.

Obter o status de uma identidade

O exemplo de código a seguir mostra como excluir o status de uma identidade do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get identity verification status for an email.
    /// </summary>
    /// <returns>The verification status of the email.</returns>
    public async Task<VerificationStatus> GetIdentityStatusAsync(string email)
    {
        var result = VerificationStatus.TemporaryFailure;
        try
        {
            var response =
                await
_amazonSimpleEmailService.GetIdentityVerificationAttributesAsync(
                    new GetIdentityVerificationAttributesRequest
                    {
                        Identities = new List<string> { email }
                    });

            if (response.VerificationAttributes.ContainsKey(email))
                result = response.VerificationAttributes[email].VerificationStatus;
        }
        catch (Exception ex)
        {
            Console.WriteLine("GetIdentityStatusAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte GetIdentityVerificationAttributesa Referência AWS SDK for .NET da API.

Listar modelos de e-mail

O exemplo de código a seguir mostra como lista modelos existentes de e-mail do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List email templates for the current account.
    /// </summary>
    /// <returns>A list of template metadata.</returns>
    public async Task<List<TemplateMetadata>> ListEmailTemplatesAsync()
    {
        var result = new List<TemplateMetadata>();
        try
        {
            var response = await _amazonSimpleEmailService.ListTemplatesAsync(
                new ListTemplatesRequest());
            result = response.TemplatesMetadata;
        }
        catch (Exception ex)
        {
            Console.WriteLine("ListEmailTemplatesAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for .NET da API.

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the identities of a specified type for the current account.
    /// </summary>
    /// <param name="identityType">IdentityType to list.</param>
    /// <returns>The list of identities.</returns>
    public async Task<List<string>> ListIdentitiesAsync(IdentityType identityType)
    {
        var result = new List<string>();
        try
        {
            var response = await _amazonSimpleEmailService.ListIdentitiesAsync(
                new ListIdentitiesRequest
                {
                    IdentityType = identityType
                });
            result = response.Identities;
        }
        catch (Exception ex)
        {
            Console.WriteLine("ListIdentitiesAsync failed with exception: " +
ex.Message);
        }

        return result;
    }
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for .NET da API.

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
///  Send an email by using Amazon SES.
/// </summary>
/// <param name="toAddresses">List of recipients.</param>
/// <param name="ccAddresses">List of cc recipients.</param>
/// <param name="bccAddresses">List of bcc recipients.</param>
/// <param name="bodyHtml">Body of the email in HTML.</param>
/// <param name="bodyText">Body of the email in plain text.</param>
/// <param name="subject">Subject line of the email.</param>
/// <param name="senderAddress">From address.</param>
/// <returns>The messageId of the email.</returns>
public async Task<string> SendEmailAsync(List<string> toAddresses,
    List<string> ccAddresses, List<string> bccAddresses,
    string bodyHtml, string bodyText, string subject, string senderAddress)
{
    var messageId = "";
    try
    {
        var response = await _amazonSimpleEmailService.SendEmailAsync(
            new SendEmailRequest
            {
                Destination = new Destination
                {
                    BccAddresses = bccAddresses,
                    CcAddresses = ccAddresses,
                    ToAddresses = toAddresses
                },
                Message = new Message
                {
                    Body = new Body
                    {
                        Html = new Content
                        {
```

```
                                Charset = "UTF-8",
                                Data = bodyHtml
                            },
                            Text = new Content
                            {
                                Charset = "UTF-8",
                                Data = bodyText
                            }
                        },
                        Subject = new Content
                        {
                            Charset = "UTF-8",
                            Data = subject
                        }
                    },
                    Source = senderAddress
                });
            messageId = response.MessageId;
        }
        catch (Exception ex)
        {
            Console.WriteLine("SendEmailAsync failed with exception: " +
ex.Message);
        }

        return messageId;
    }
```

- Para obter detalhes da API, consulte SendEmail a Referência AWS SDK for .NET da API.

Enviar e-mails com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo com o Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Send an email using a template.
   /// </summary>
   /// <param name="sender">Address of the sender.</param>
   /// <param name="recipients">Addresses of the recipients.</param>
   /// <param name="templateName">Name of the email template.</param>
   /// <param name="templateDataObject">Data for the email template.</param>
   /// <returns>The messageId of the email.</returns>
   public async Task<string> SendTemplateEmailAsync(string sender, List<string>
recipients,
       string templateName, object templateDataObject)
   {
       var messageId = "";
       try
       {
           // Template data should be serialized JSON from either a class or a
dynamic object.
           var templateData = JsonSerializer.Serialize(templateDataObject);

           var response = await _amazonSimpleEmailService.SendTemplatedEmailAsync(
               new SendTemplatedEmailRequest
               {
                   Source = sender,
                   Destination = new Destination
                   {
                       ToAddresses = recipients
                   },
                   Template = templateName,
                   TemplateData = templateData
               });
           messageId = response.MessageId;
       }
       catch (Exception ex)
```

```
        {
            Console.WriteLine("SendTemplateEmailAsync failed with exception: " +
ex.Message);
        }

        return messageId;
    }
```

- Para obter detalhes da API, consulte SendTemplatedEmail a Referência AWS SDK for .NET da API.

Verificar uma identidade de e-mail

O exemplo de código a seguir mostra como verificar uma identidade de e-mail com o Amazon SES.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Starts verification of an email identity. This request sends an email
    /// from Amazon SES to the specified email address. To complete
    /// verification, follow the instructions in the email.
    /// </summary>
    /// <param name="recipientEmailAddress">Email address to verify.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> VerifyEmailIdentityAsync(string recipientEmailAddress)
    {
        var success = false;
        try
        {
            var response = await _amazonSimpleEmailService.VerifyEmailIdentityAsync(
                new VerifyEmailIdentityRequest
                {
```

```
                    EmailAddress = recipientEmailAddress
                });

            success = response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Exception ex)
        {
            Console.WriteLine("VerifyEmailIdentityAsync failed with exception: " +
ex.Message);
        }

        return success;
    }
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for .NET da API.

Exemplos do Amazon SNS usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SimpleNotificationService;
using Amazon.SimpleNotificationService.Model;

namespace SNSActions;

public static class HelloSNS
{
    static async Task Main(string[] args)
    {
        var snsClient = new AmazonSimpleNotificationServiceClient();

        Console.WriteLine($"Hello Amazon SNS! Following are some of your topics:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get a list of topics.
        var response = await snsClient.ListTopicsAsync(
            new ListTopicsRequest());

        foreach (var topic in response.Topics)
        {
            Console.WriteLine($"\tTopic ARN: {topic.TopicArn}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for .NET da API.

Tópicos

- Ações

- Cenários
- Exemplos sem servidor

Ações

Verificar se um número de telefone saiu

O exemplo de código a seguir mostra como verificar se um número de telefone cancelou o recebimento de mensagens do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.SimpleNotificationService;
using Amazon.SimpleNotificationService.Model;

/// <summary>
/// This example shows how to use the Amazon Simple Notification Service
/// (Amazon SNS) to check whether a phone number has been opted out.
/// </summary>
public class IsPhoneNumOptedOut
{
    public static async Task Main()
    {
        string phoneNumber = "+15551112222";

        IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();

        await CheckIfOptedOutAsync(client, phoneNumber);
    }

    /// <summary>
    /// Checks to see if the supplied phone number has been opted out.
```

```
        /// </summary>
        /// <param name="client">The initialized Amazon SNS Client object used
        /// to check if the phone number has been opted out.</param>
        /// <param name="phoneNumber">A string representing the phone number
        /// to check.</param>
        public static async Task
CheckIfOptedOutAsync(IAmazonSimpleNotificationService client, string phoneNumber)
        {
            var request = new CheckIfPhoneNumberIsOptedOutRequest
            {
                PhoneNumber = phoneNumber,
            };

            try
            {
                var response = await
client.CheckIfPhoneNumberIsOptedOutAsync(request);

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    string optOutStatus = response.IsOptedOut ? "opted out" : "not
opted out.";
                    Console.WriteLine($"The phone number: {phoneNumber} is
{optOutStatus}");
                }
            }
            catch (AuthorizationErrorException ex)
            {
                Console.WriteLine($"{ex.Message}");
            }
        }
    }
```

- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for .NET da API.

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico com um nome específico.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// This example shows how to use Amazon Simple Notification Service
    /// (Amazon SNS) to add a new Amazon SNS topic.
    /// </summary>
    public class CreateSNSTopic
    {
        public static async Task Main()
        {
            string topicName = "ExampleSNSTopic";

            IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();

            var topicArn = await CreateSNSTopicAsync(client, topicName);
            Console.WriteLine($"New topic ARN: {topicArn}");
        }

        /// <summary>
        /// Creates a new SNS topic using the supplied topic name.
        /// </summary>
        /// <param name="client">The initialized SNS client object used to
        /// create the new topic.</param>
        /// <param name="topicName">A string representing the topic name.</param>
        /// <returns>The Amazon Resource Name (ARN) of the created topic.</returns>
        public static async Task<string>
CreateSNSTopicAsync(IAmazonSimpleNotificationService client, string topicName)
        {
            var request = new CreateTopicRequest
```

```
            {
                Name = topicName,
            };

            var response = await client.CreateTopicAsync(request);

            return response.TopicArn;
        }
    }
```

Crie um tópico com um nome e atributos específicos de FIFO e desduplicação.

```
    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
                { "FifoTopic", "true" }
```

```
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
"true");
            }
        }

        var createResponse = await
_amazonSNSClient.CreateTopicAsync(createTopicRequest);
        return createResponse.TopicArn;
    }
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for .NET da API.

Excluir uma assinatura

O exemplo de código a seguir mostra como excluir uma assinatura do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cancele a assinatura de um tópico por meio de um ARN de assinatura.

```
    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
            {
                SubscriptionArn = subscriptionArn
```

```
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for .NET.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um tópico por meio do respectivo ARN.

```
    /// <summary>
    /// Delete a topic by its topic ARN.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTopicByArn(string topicArn)
    {
        var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
            new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for .NET da API.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.SimpleNotificationService;

/// <summary>
/// This example shows how to retrieve the attributes of an Amazon Simple
/// Notification Service (Amazon SNS) topic.
/// </summary>
public class GetTopicAttributes
{
    public static async Task Main()
    {
        string topicArn = "arn:aws:sns:us-west-2:000000000000:ExampleSNSTopic";
        IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();

        var attributes = await GetTopicAttributesAsync(client, topicArn);
        DisplayTopicAttributes(attributes);
    }

    /// <summary>
    /// Given the ARN of the Amazon SNS topic, this method retrieves the topic
    /// attributes.
    /// </summary>
    /// <param name="client">The initialized Amazon SNS client object used
    /// to retrieve the attributes for the Amazon SNS topic.</param>
    /// <param name="topicArn">The ARN of the topic for which to retrieve
    /// the attributes.</param>
    /// <returns>A Dictionary of topic attributes.</returns>
```

```
        public static async Task<Dictionary<string, string>>
GetTopicAttributesAsync(
            IAmazonSimpleNotificationService client,
            string topicArn)
        {
            var response = await client.GetTopicAttributesAsync(topicArn);

            return response.Attributes;
        }

        /// <summary>
        /// This method displays the attributes for an Amazon SNS topic.
        /// </summary>
        /// <param name="topicAttributes">A Dictionary containing the
        /// attributes for an Amazon SNS topic.</param>
        public static void DisplayTopicAttributes(Dictionary<string, string>
topicAttributes)
        {
            foreach (KeyValuePair<string, string> entry in topicAttributes)
            {
                Console.WriteLine($"{entry.Key}: {entry.Value}\n");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for .NET da API.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// This example will retrieve a list of the existing Amazon Simple
    /// Notification Service (Amazon SNS) subscriptions.
    /// </summary>
    public class ListSubscriptions
    {
        public static async Task Main()
        {
            IAmazonSimpleNotificationService client = new
 AmazonSimpleNotificationServiceClient();

            Console.WriteLine("Enter a topic ARN to list subscriptions for a
 specific topic, " +
                              "or press Enter to list subscriptions for all
 topics.");
            var topicArn = Console.ReadLine();
            Console.WriteLine();

            var subscriptions = await GetSubscriptionsListAsync(client, topicArn);

            DisplaySubscriptionList(subscriptions);
        }

        /// <summary>
        /// Gets a list of the existing Amazon SNS subscriptions, optionally by
 specifying a topic ARN.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object used
        /// to obtain the list of subscriptions.</param>
        /// <param name="topicArn">The optional ARN of a specific topic. Defaults to
 null.</param>
        /// <returns>A list containing information about each subscription.</
returns>
        public static async Task<List<Subscription>>
 GetSubscriptionsListAsync(IAmazonSimpleNotificationService client, string topicArn
 = null)
        {
```

```
            var results = new List<Subscription>();

            if (!string.IsNullOrEmpty(topicArn))
            {
                var paginateByTopic = client.Paginators.ListSubscriptionsByTopic(
                    new ListSubscriptionsByTopicRequest()
                    {
                        TopicArn = topicArn,
                    });

                // Get the entire list using the paginator.
                await foreach (var subscription in paginateByTopic.Subscriptions)
                {
                    results.Add(subscription);
                }
            }
            else
            {
                var paginateAllSubscriptions =
client.Paginators.ListSubscriptions(new ListSubscriptionsRequest());

                // Get the entire list using the paginator.
                await foreach (var subscription in
paginateAllSubscriptions.Subscriptions)
                {
                    results.Add(subscription);
                }
            }

            return results;
        }

        /// <summary>
        /// Display a list of Amazon SNS subscription information.
        /// </summary>
        /// <param name="subscriptionList">A list containing details for existing
        /// Amazon SNS subscriptions.</param>
        public static void DisplaySubscriptionList(List<Subscription>
subscriptionList)
        {
            foreach (var subscription in subscriptionList)
            {
                Console.WriteLine($"Owner: {subscription.Owner}");
```

```
                Console.WriteLine($"Subscription ARN:
{subscription.SubscriptionArn}");
                Console.WriteLine($"Topic ARN: {subscription.TopicArn}");
                Console.WriteLine($"Endpoint: {subscription.Endpoint}");
                Console.WriteLine($"Protocol: {subscription.Protocol}");
                Console.WriteLine();
            }
        }
    }
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for .NET da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    /// <summary>
    /// Lists the Amazon Simple Notification Service (Amazon SNS)
    /// topics for the current account.
    /// </summary>
    public class ListSNSTopics
    {
        public static async Task Main()
        {
            IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();
```

```
            await GetTopicListAsync(client);
        }

        /// <summary>
        /// Retrieves the list of Amazon SNS topics in groups of up to 100
        /// topics.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object used
        /// to retrieve the list of topics.</param>
        public static async Task GetTopicListAsync(IAmazonSimpleNotificationService
client)
        {
            // If there are more than 100 Amazon SNS topics, the call to
            // ListTopicsAsync will return a value to pass to the
            // method to retrieve the next 100 (or less) topics.
            string nextToken = string.Empty;

            do
            {
                var response = await client.ListTopicsAsync(nextToken);
                DisplayTopicsList(response.Topics);
                nextToken = response.NextToken;
            }
            while (!string.IsNullOrEmpty(nextToken));
        }

        /// <summary>
        /// Displays the list of Amazon SNS Topic ARNs.
        /// </summary>
        /// <param name="topicList">The list of Topic ARNs.</param>
        public static void DisplayTopicsList(List<Topic> topicList)
        {
            foreach (var topic in topicList)
            {
                Console.WriteLine($"{topic.TopicArn}");
            }
        }
    }
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for .NET da API.

Publicar uma mensagem com um atributo

O exemplo de código a seguir mostra como publicar uma mensagem com um atributo usando o Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico com opções de grupo, duplicação e atributo.

```
    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is a
sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must set
a message group ID." +
                                  "\r\nAll messages within the same group will be
received in the order " +
                                  "they were published.");

                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID for
this message:", "1");
```

```
                if (!_useContentBasedDeduplication)
                {
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                      "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID for
this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
                    }
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?", false);
        }
    }
```

Aplique as seleções do usuário à ação de publicação.

```
    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</param>
    /// <param name="attributeValue">The optional attribute value for the message.</
param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
 attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

Publicar uma mensagem de texto SMS

O exemplo de código a seguir mostra como publicar mensagens SMS usando o Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace SNSMessageExample
{
    using System;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.SimpleNotificationService;
    using Amazon.SimpleNotificationService.Model;

    public class SNSMessage
    {
        private AmazonSimpleNotificationServiceClient snsClient;

        /// <summary>
        /// Initializes a new instance of the <see cref="SNSMessage"/> class.
        /// Constructs a new SNSMessage object initializing the Amazon Simple
        /// Notification Service (Amazon SNS) client using the supplied
        /// Region endpoint.
        /// </summary>
        /// <param name="regionEndpoint">The Amazon Region endpoint to use in
        /// sending test messages with this object.</param>
        public SNSMessage(RegionEndpoint regionEndpoint)
        {
            snsClient = new AmazonSimpleNotificationServiceClient(regionEndpoint);
        }
```

```
        /// <summary>
        /// Sends the SMS message passed in the text parameter to the phone number
        /// in phoneNum.
        /// </summary>
        /// <param name="phoneNum">The ten-digit phone number to which the text
        /// message will be sent.</param>
        /// <param name="text">The text of the message to send.</param>
        /// <returns>Async task.</returns>
        public async Task SendTextMessageAsync(string phoneNum, string text)
        {
            if (string.IsNullOrEmpty(phoneNum) || string.IsNullOrEmpty(text))
            {
                return;
            }

            // Now actually send the message.
            var request = new PublishRequest
            {
                Message = text,
                PhoneNumber = phoneNum,
            };

            try
            {
                var response = await snsClient.PublishAsync(request);
            }
            catch (Exception ex)
            {
                Console.WriteLine($"Error sending message: {ex}");
            }
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico.

```
using System;
using System.Threading.Tasks;
using Amazon.SimpleNotificationService;
using Amazon.SimpleNotificationService.Model;

/// <summary>
/// This example publishes a message to an Amazon Simple Notification
/// Service (Amazon SNS) topic.
/// </summary>
public class PublishToSNSTopic
{
    public static async Task Main()
    {
        string topicArn = "arn:aws:sns:us-east-2:000000000000:ExampleSNSTopic";
        string messageText = "This is an example message to publish to the
ExampleSNSTopic.";

        IAmazonSimpleNotificationService client = new
AmazonSimpleNotificationServiceClient();

        await PublishToTopicAsync(client, topicArn, messageText);
    }

    /// <summary>
    /// Publishes a message to an Amazon SNS topic.
    /// </summary>
    /// <param name="client">The initialized client object used to publish
    /// to the Amazon SNS topic.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="messageText">The text of the message.</param>
    public static async Task PublishToTopicAsync(
        IAmazonSimpleNotificationService client,
        string topicArn,
```

```
            string messageText)
        {
            var request = new PublishRequest
            {
                TopicArn = topicArn,
                Message = messageText,
            };

            var response = await client.PublishAsync(request);

            Console.WriteLine($"Successfully published message ID:
 {response.MessageId}");
        }
    }
```

Publique uma mensagem em um tópico com um atributo e desduplicação e IDs de grupo opcionais.

```
    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</param>
    /// <param name="attributeValue">The optional attribute value for the message.</
param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
```

```
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for .NET.

Assinar uma fila do SQS em um tópico

O exemplo de código a seguir mostra como inscrever uma fila do Amazon SQS para receber notificações de um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inscreva uma fila em um tópico com filtros opcionais.

```
    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
```

```
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
_amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

Inscrever um endereço de e-mail em um tópico

O exemplo do código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        /// <summary>
        /// Creates a new subscription to a topic.
        /// </summary>
        /// <param name="client">The initialized Amazon SNS client object, used
        /// to create an Amazon SNS subscription.</param>
        /// <param name="topicArn">The ARN of the topic to subscribe to.</param>
        /// <returns>A SubscribeResponse object which includes the subscription
        /// ARN for the new subscription.</returns>
        public static async Task<SubscribeResponse> TopicSubscribeAsync(
            IAmazonSimpleNotificationService client,
            string topicArn)
        {
            SubscribeRequest request = new SubscribeRequest()
            {
                TopicArn = topicArn,
                ReturnSubscriptionArn = true,
                Protocol = "email",
                Endpoint = "recipient@example.com",
            };

            var response = await client.SubscribeAsync(request);

            return response;
        }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

Assinar com um filtro em um tópico

O exemplo de código a seguir mostra como assinar com um filtro um tópico do Amazon SNS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inscreva uma fila em um tópico com filtros opcionais.

```
    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
_amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for .NET.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.

- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Console application to run a workflow scenario for topics and queues.
/// </summary>
public static class TopicsAndQueues
{
    private static bool _useFifoTopic = false;
    private static bool _useContentBasedDeduplication = false;
    private static string _topicName = null!;
    private static string _topicArn = null!;

    private static readonly int _queueCount = 2;
    private static readonly string[] _queueUrls = new string[_queueCount];
    private static readonly string[] _subscriptionArns = new string[_queueCount];
    private static readonly string[] _tones = { "cheerful", "funny", "serious",
 "sincere" };
    public static SNSWrapper SnsWrapper { get; set; } = null!;
    public static SQSWrapper SqsWrapper { get; set; } = null!;
    public static bool UseConsole { get; set; } = true;
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EventBridge.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
```

```
                services.AddAWSService<IAmazonSQS>()
                    .AddAWSService<IAmazonSimpleNotificationService>()
                    .AddTransient<SNSWrapper>()
                    .AddTransient<SQSWrapper>()
            )
            .Build();

        ServicesSetup(host);
        PrintDescription();

        await RunScenario();

    }

    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        SnsWrapper = host.Services.GetRequiredService<SNSWrapper>();
        SqsWrapper = host.Services.GetRequiredService<SQSWrapper>();
    }

    /// <summary>
    /// Run the scenario for working with topics and queues.
    /// </summary>
    /// <returns>True if successful.</returns>
    public static async Task<bool> RunScenario()
    {
        try
        {
            await SetupTopic();

            await SetupQueues();

            await PublishMessages();

            foreach (var queueUrl in _queueUrls)
            {
                var messages = await PollForMessages(queueUrl);
                if (messages.Any())
                {
                    await DeleteMessages(queueUrl, messages);
```

```
                }
            }
            await CleanupResources();

            Console.WriteLine("Messaging with topics and queues workflow is
complete.");
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await CleanupResources();
            Console.WriteLine(new string('-', 80));
            return false;
        }
    }

    /// <summary>
    /// Print a description for the tasks in the workflow.
    /// </summary>
    /// <returns>Async task.</returns>
    private static void PrintDescription()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Welcome to messaging with topics and queues.");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"In this workflow, you will create an SNS topic and
subscribe {_queueCount} SQS queues to the topic." +
                          $"\r\nYou can select from several options for configuring
the topic and the subscriptions for the 2 queues." +
                          $"\r\nYou can then post to the topic and see the results
in the queues.\r\n");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the SNS topic to be used with the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> SetupTopic()
```

```
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"SNS topics can be configured as FIFO (First-In-First-
Out)." +
                          $"\r\nFIFO topics deliver messages in order and support
 deduplication and message filtering." +
                          $"\r\nYou can then post to the topic and see the results
 in the queues.\r\n");

        _useFifoTopic = GetYesNoResponse("Would you like to work with FIFO
 topics?");

        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            _topicName = GetUserResponse("Enter a name for your SNS topic: ",
 "example-topic");
            Console.WriteLine(
                "Because you have selected a FIFO topic, '.fifo' must be appended to
 the topic name.\r\n");

            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"Because you have chosen a FIFO topic, deduplication
 is supported." +
                              $"\r\nDeduplication IDs are either set in the message
 or automatically generated " +
                              $"\r\nfrom content using a hash function.\r\n" +
                              $"\r\nIf a message is successfully published to an SNS
 FIFO topic, any message " +
                              $"\r\npublished and determined to have the same
 deduplication ID, " +
                              $"\r\nwithin the five-minute deduplication interval,
 is accepted but not delivered.\r\n" +
                              $"\r\nFor more information about deduplication, " +
                              $"\r\nsee https://docs.aws.amazon.com/sns/latest/dg/
fifo-message-dedup.html.");

            _useContentBasedDeduplication = GetYesNoResponse("Use content-based
 deduplication instead of entering a deduplication ID?");
            Console.WriteLine(new string('-', 80));
        }

        _topicArn = await SnsWrapper.CreateTopicWithName(_topicName, _useFifoTopic,
 _useContentBasedDeduplication);
```

```
        Console.WriteLine($"Your new topic with the name {_topicName}" +
                          $"\r\nand Amazon Resource Name (ARN) {_topicArn}" +
                          $"\r\nhas been created.\r\n");

        Console.WriteLine(new string('-', 80));
        return _topicArn;
    }

    /// <summary>
    /// Set up the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task SetupQueues()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now you will create {_queueCount} Amazon Simple Queue
Service (Amazon SQS) queues to subscribe to the topic.");

        // Repeat this section for each queue.
        for (int i = 0; i < _queueCount; i++)
        {
            var queueName = GetUserResponse("Enter a name for an Amazon SQS queue:
", $"example-queue-{i}");
            if (_useFifoTopic)
            {
                // Only explain this once.
                if (i == 0)
                {
                    Console.WriteLine(
                        "Because you have selected a FIFO topic, '.fifo' must be
appended to the queue name.");
                }

                var queueUrl = await SqsWrapper.CreateQueueWithName(queueName,
_useFifoTopic);

                _queueUrls[i] = queueUrl;

                Console.WriteLine($"Your new queue with the name {queueName}" +
                                  $"\r\nand queue URL {queueUrl}" +
                                  $"\r\nhas been created.\r\n");

                if (i == 0)
```

```
                {
                    Console.WriteLine(
                        $"The queue URL is used to retrieve the queue ARN,\r\n" +
                        $"which is used to create a subscription.");
                    Console.WriteLine(new string('-', 80));
                }

                var queueArn = await SqsWrapper.GetQueueArnByUrl(queueUrl);

                if (i == 0)
                {
                    Console.WriteLine(
                        $"An AWS Identity and Access Management (IAM) policy must be
attached to an SQS queue, enabling it to receive\r\n" +
                        $"messages from an SNS topic");
                }

                await SqsWrapper.SetQueuePolicyForTopic(queueArn, _topicArn,
queueUrl);

                await SetupFilters(i, queueArn, queueName);
            }
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up filters with user options for a queue.
    /// </summary>
    /// <param name="queueCount">The number of this queue.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="queueName">The name of the queue.</param>
    /// <returns>Async Task.</returns>
    public static async Task SetupFilters(int queueCount, string queueArn, string
queueName)
    {
        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            // Only explain this once.
            if (queueCount == 0)
            {
                Console.WriteLine(
```

```
                    "Subscriptions to a FIFO topic can have filters." +
                    "If you add a filter to this subscription, then only the
 filtered messages " +
                    "will be received in the queue.");

                Console.WriteLine(
                    "For information about message filtering, " +
                    "see https://docs.aws.amazon.com/sns/latest/dg/sns-message-
filtering.html");

                Console.WriteLine(
                    "For this example, you can filter messages by a" +
                    "TONE attribute.");
            }

            var useFilter = GetYesNoResponse($"Filter messages for {queueName}'s
 subscription to the topic?");

            string? filterPolicy = null;
            if (useFilter)
            {
                filterPolicy = CreateFilterPolicy();
            }
            var subscriptionArn = await
 SnsWrapper.SubscribeTopicWithFilter(_topicArn, filterPolicy,
                queueArn);
            _subscriptionArns[queueCount] = subscriptionArn;

            Console.WriteLine(
                $"The queue {queueName} has been subscribed to the topic
 {_topicName} " +
                $"with the subscription ARN {subscriptionArn}");
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Use user input to create a filter policy for a subscription.
    /// </summary>
    /// <returns>The serialized filter policy.</returns>
    public static string CreateFilterPolicy()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
```

```
            $"You can filter messages by one or more of the following" +
            $"TONE attributes.");

        List<string> filterSelections = new List<string>();

        var selectionNumber = 0;
        do
        {
            Console.WriteLine(
                $"Enter a number to add a TONE filter, or enter 0 to stop adding
 filters.");
            for (int i = 0; i < _tones.Length; i++)
            {
                Console.WriteLine($"\t{i + 1}. {_tones[i]}");
            }

            var selection = GetUserResponse("", filterSelections.Any() ? "0" : "1");
            int.TryParse(selection, out selectionNumber);
            if (selectionNumber > 0 && !
filterSelections.Contains(_tones[selectionNumber - 1]))
            {
                filterSelections.Add(_tones[selectionNumber - 1]);
            }
        } while (selectionNumber != 0);

        var filters = new Dictionary<string, List<string>>
        {
            { "tone", filterSelections }
        };
        string filterPolicy = JsonSerializer.Serialize(filters);
        return filterPolicy;
    }

    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
```

```
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is a
sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must set
a message group ID." +
                                  "\r\nAll messages within the same group will be
received in the order " +
                                  "they were published.");

                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID for
this message:", "1");

                if (!_useContentBasedDeduplication)
                {
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                      "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID for
this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
                    }
```

```
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?", false);
        }
    }

    /// <summary>
    /// Poll for the published messages to see the results of the user's choices.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task<List<Message>> PollForMessages(string queueUrl)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now the SQS queue at {queueUrl} will be polled to
retrieve the messages." +
                          "\r\nPress any key to continue.");
        if (UseConsole)
        {
            Console.ReadLine();
        }

        var moreMessages = true;
        var messages = new List<Message>();
        while (moreMessages)
        {
            var newMessages = await SqsWrapper.ReceiveMessagesByUrl(queueUrl, 10);

            moreMessages = newMessages.Any();
            if (moreMessages)
            {
                messages.AddRange(newMessages);
            }
        }

        Console.WriteLine($"{messages.Count} message(s) were received by the queue
at {queueUrl}.");
```

```
        foreach (var message in messages)
        {
            Console.WriteLine("\tMessage:" +
                              $"\n\t{message.Body}");
        }

        Console.WriteLine(new string('-', 80));
        return messages;
    }

    /// <summary>
    /// Delete the message using handles in a batch.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task DeleteMessages(string queueUrl, List<Message> messages)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Now we can delete the messages in this queue in a
batch.");
        await SqsWrapper.DeleteMessageBatchByUrl(queueUrl, messages);
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        try
        {
            foreach (var queueUrl in _queueUrls)
            {
                if (!string.IsNullOrEmpty(queueUrl))
                {
                    var deleteQueue =
                        GetYesNoResponse($"Delete queue with url {queueUrl}?");
                    if (deleteQueue)
                    {
                        await SqsWrapper.DeleteQueueByUrl(queueUrl);
                    }
```

```
                }
            }

            foreach (var subscriptionArn in _subscriptionArns)
            {
                if (!string.IsNullOrEmpty(subscriptionArn))
                {
                    await SnsWrapper.UnsubscribeByArn(subscriptionArn);
                }
            }

            var deleteTopic = GetYesNoResponse($"Delete topic {_topicName}?");
            if (deleteTopic)
            {
                await SnsWrapper.DeleteTopicByArn(_topicArn);
            }
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Unable to clean up resources. Here's why:
{ex.Message}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question, bool defaultAnswer = true)
    {
        if (UseConsole)
        {
            Console.WriteLine(question);
            var ynResponse = Console.ReadLine();
            var response = ynResponse != null &&
                           ynResponse.Equals("y",
                               StringComparison.InvariantCultureIgnoreCase);
            return response;
        }
        // If not using the console, use the default.
```

```
        return defaultAnswer;
    }

    /// <summary>
    /// Helper method to get a string response from the user through the console.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static string GetUserResponse(string question, string defaultAnswer)
    {
        if (UseConsole)
        {
            var response = "";
            while (string.IsNullOrEmpty(response))
            {
                Console.WriteLine(question);
                response = Console.ReadLine();
            }
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }
}
```

Crie uma classe que envolva as operações do Amazon SQS.

```
/// <summary>
/// Wrapper for Amazon Simple Queue Service (SQS) operations.
/// </summary>
public class SQSWrapper
{
    private readonly IAmazonSQS _amazonSQSClient;

    /// <summary>
    /// Constructor for the Amazon SQS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SQS client.</param>
    public SQSWrapper(IAmazonSQS amazonSQS)
    {
```

```
        _amazonSQSClient = amazonSQS;
    }

    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
useFifoQueue)
    {
        int maxMessage = 256 * 1024;
        var queueAttributes = new Dictionary<string, string>
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
```

```
            });
        return createResponse.QueueUrl;
    }

    /// <summary>
    /// Get the ARN for a queue from its URL.
    /// </summary>
    /// <param name="queueUrl">The URL of the queue.</param>
    /// <returns>The ARN of the queue.</returns>
    public async Task<string> GetQueueArnByUrl(string queueUrl)
    {
        var getAttributesRequest = new GetQueueAttributesRequest()
        {
            QueueUrl = queueUrl,
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await _amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }

    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string topicArn,
string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                         $"\"Service\": " +
                                             "\"sns.amazonaws.com\"" +
                                            "}," +
                                     "\"Action\": \"sqs:SendMessage\"," +
                                     $"\"Resource\": \"{queueArn}\"," +
                                      "\"Condition\": {" +
```

```
                                                "\"ArnEquals\": {" +
                                                     $"\"aws:SourceArn\": \"{topicArn}\""
 +
                                                 "}" +
                                            "}" +
                                 "}]" +
                              "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
                QueueUrl = queueUrl,
                Attributes = new Dictionary<string, string>() { { "Policy",
 queuePolicy } }
            });
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
        return messageResponse.Messages;
    }

    /// <summary>
    /// Delete a batch of messages from a queue by its url.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
```

```
    public async Task<bool> DeleteMessageBatchByUrl(string queueUrl, List<Message>
 messages)
    {
        var deleteRequest = new DeleteMessageBatchRequest()
        {
            QueueUrl = queueUrl,
            Entries = new List<DeleteMessageBatchRequestEntry>()
        };
        foreach (var message in messages)
        {
            deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
            {
                ReceiptHandle = message.ReceiptHandle,
                Id = message.MessageId
            });
        }

        var deleteResponse = await
 _amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

        return deleteResponse.Failed.Any();
    }

    /// <summary>
    /// Delete a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteQueueByUrl(string queueUrl)
    {
        var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
            new DeleteQueueRequest()
            {
                QueueUrl = queueUrl
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

Crie uma classe que envolva as operações do Amazon SNS.

```
/// <summary>
/// Wrapper for Amazon Simple Notification Service (SNS) operations.
/// </summary>
public class SNSWrapper
{
    private readonly IAmazonSimpleNotificationService _amazonSNSClient;

    /// <summary>
    /// Constructor for the Amazon SNS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SNS client.</param>
    public SNSWrapper(IAmazonSimpleNotificationService amazonSNS)
    {
        _amazonSNSClient = amazonSNS;
    }

    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
```

```
                { "FifoTopic", "true" }
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
"true");
            }
        }

        var createResponse = await
_amazonSNSClient.CreateTopicAsync(createTopicRequest);
        return createResponse.TopicArn;
    }

    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
{ { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
_amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }

    /// <summary>
```

```
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</param>
    /// <param name="attributeValue">The optional attribute value for the message.</
param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
 attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }
```

```
    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
            {
                SubscriptionArn = subscriptionArn
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Delete a topic by its topic ARN.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTopicByArn(string topicArn)
    {
        var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
            new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes

- Publicar
- ReceiveMessage
- SetQueueAttributes
- Assinar
- Cancelar assinatura

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SNSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace SnsIntegration;

public class Function
{
    public async Task FunctionHandler(SNSEvent evnt, ILambdaContext context)
    {
        foreach (var record in evnt.Records)
```

```
        {
            await ProcessRecordAsync(record, context);
        }
        context.Logger.LogInformation("done");
    }

    private async Task ProcessRecordAsync(SNSEvent.SNSRecord record, ILambdaContext
 context)
    {
        try
        {
            context.Logger.LogInformation($"Processed record {record.Sns.Message}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }
    }
}
```

Exemplos do Amazon SQS usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.SQS;
using Amazon.SQS.Model;

namespace SQSActions;

public static class HelloSQS
{
    static async Task Main(string[] args)
    {
        var sqsClient = new AmazonSQSClient();

        Console.WriteLine($"Hello Amazon SQS! Following are some of your queues:");
        Console.WriteLine();

        // You can use await and any of the async methods to get a response.
        // Let's get the first five queues.
        var response = await sqsClient.ListQueuesAsync(
            new ListQueuesRequest()
            {
                MaxResults = 5
            });

        foreach (var queue in response.QueueUrls)
        {
            Console.WriteLine($"\tQueue Url: {queue}");
            Console.WriteLine();
        }
    }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Autorizar um bucket a enviar mensagens para uma fila

O exemplo de código a seguir mostra como autorizar um bucket do Amazon S3 a enviar mensagens para uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.SQS;

    public class AuthorizeS3ToSendMessage
    {
        /// <summary>
        /// Initializes the Amazon SQS client object and then calls the
        /// AuthorizeS3ToSendMessageAsync method to authorize the named
        /// bucket to send messages in response to S3 events.
        /// </summary>
        public static async Task Main()
        {
            string queueUrl = "https://sqs.us-east-2.amazonaws.com/0123456789ab/
Example_Queue";
```

```
            string bucketName = "doc-example-bucket";

            // Create an Amazon SQS client object using the
            // default user. If the AWS Region you want to use
            // is different, supply the AWS Region as a parameter.
            IAmazonSQS client = new AmazonSQSClient();

            var queueARN = await client.AuthorizeS3ToSendMessageAsync(queueUrl,
bucketName);

            if (!string.IsNullOrEmpty(queueARN))
            {
                Console.WriteLine($"The Amazon S3 bucket: {bucketName} has been
successfully authorized.");
                Console.WriteLine($"{bucketName} can now send messages to the queue
with ARN: {queueARN}.");
            }
        }
    }
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for .NET da API.

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila com um nome específico.

```
    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
```

```
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
useFifoQueue)
    {
        int maxMessage = 256 * 1024;
        var queueAttributes = new Dictionary<string, string>
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
            });
        return createResponse.QueueUrl;
    }
```

Crie uma fila do Amazon SQS e envie uma mensagem para ela.

```
   using System;
   using System.Collections.Generic;
   using System.Threading.Tasks;
   using Amazon;
   using Amazon.SQS;
   using Amazon.SQS.Model;

   public class CreateSendExample
   {
       // Specify your AWS Region (an example Region is shown).
       private static readonly string QueueName = "Example_Queue";
       private static readonly RegionEndpoint ServiceRegion =
RegionEndpoint.USWest2;
       private static IAmazonSQS client;

       public static async Task Main()
       {
           client = new AmazonSQSClient(ServiceRegion);
           var createQueueResponse = await CreateQueue(client, QueueName);

           string queueUrl = createQueueResponse.QueueUrl;

           Dictionary<string, MessageAttributeValue> messageAttributes = new
Dictionary<string, MessageAttributeValue>
           {
               { "Title",   new MessageAttributeValue { DataType = "String",
StringValue = "The Whistler" } },
               { "Author",  new MessageAttributeValue { DataType = "String",
StringValue = "John Grisham" } },
               { "WeeksOn", new MessageAttributeValue { DataType = "Number",
StringValue = "6" } },
           };

           string messageBody = "Information about current NY Times fiction
bestseller for week of 12/11/2016.";

           var sendMsgResponse = await SendMessage(client, queueUrl, messageBody,
messageAttributes);
       }

       /// <summary>
       /// Creates a new Amazon SQS queue using the queue name passed to it
       /// in queueName.
```

```
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueName">A string representing the name of the queue
        /// to create.</param>
        /// <returns>A CreateQueueResponse that contains information about the
        /// newly created queue.</returns>
        public static async Task<CreateQueueResponse> CreateQueue(IAmazonSQS client,
 string queueName)
        {
            var request = new CreateQueueRequest
            {
                QueueName = queueName,
                Attributes = new Dictionary<string, string>
                {
                    { "DelaySeconds", "60" },
                    { "MessageRetentionPeriod", "86400" },
                },
            };

            var response = await client.CreateQueueAsync(request);
            Console.WriteLine($"Created a queue with URL : {response.QueueUrl}");

            return response;
        }

        /// <summary>
        /// Sends a message to an SQS queue.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueUrl">The URL of the queue to which to send the
        /// message.</param>
        /// <param name="messageBody">A string representing the body of the
        /// message to be sent to the queue.</param>
        /// <param name="messageAttributes">Attributes for the message to be
        /// sent to the queue.</param>
        /// <returns>A SendMessageResponse object that contains information
        /// about the message that was sent.</returns>
        public static async Task<SendMessageResponse> SendMessage(
            IAmazonSQS client,
            string queueUrl,
            string messageBody,
            Dictionary<string, MessageAttributeValue> messageAttributes)
```

```
        {
            var sendMessageRequest = new SendMessageRequest
            {
                DelaySeconds = 10,
                MessageAttributes = messageAttributes,
                MessageBody = messageBody,
                QueueUrl = queueUrl,
            };

            var response = await client.SendMessageAsync(sendMessageRequest);
            Console.WriteLine($"Sent a message with id : {response.MessageId}");

            return response;
        }
    }
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for .NET da API.

Excluir um lote de mensagens de uma fila

O exemplo de código a seguir mostra como excluir um lote de mensagens de uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a batch of messages from a queue by its url.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMessageBatchByUrl(string queueUrl, List<Message>
messages)
    {
        var deleteRequest = new DeleteMessageBatchRequest()
```

```
        {
            QueueUrl = queueUrl,
            Entries = new List<DeleteMessageBatchRequestEntry>()
        };
        foreach (var message in messages)
        {
            deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
            {
                ReceiptHandle = message.ReceiptHandle,
                Id = message.MessageId
            });
        }

        var deleteResponse = await
_amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

        return deleteResponse.Failed.Any();
    }
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for .NET da API.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS e, em seguida, exclua a mensagem.

```
        public static async Task Main()
        {
            // If the AWS Region you want to use is different from
            // the AWS Region defined for the default user, supply
            // the specify your AWS Region to the client constructor.
```

```
            var client = new AmazonSQSClient();
            string queueName = "Example_Queue";

            var queueUrl = await GetQueueUrl(client, queueName);
            Console.WriteLine($"The SQS queue's URL is {queueUrl}");

            var response = await ReceiveAndDeleteMessage(client, queueUrl);

            Console.WriteLine($"Message: {response.Messages[0]}");
        }

        /// <summary>
        /// Retrieve the queue URL for the queue named in the queueName
        /// property using the client object.
        /// </summary>
        /// <param name="client">The Amazon SQS client used to retrieve the
        /// queue URL.</param>
        /// <param name="queueName">A string representing  name of the queue
        /// for which to retrieve the URL.</param>
        /// <returns>The URL of the queue.</returns>
        public static async Task<string> GetQueueUrl(IAmazonSQS client, string
queueName)
        {
            var request = new GetQueueUrlRequest
            {
                QueueName = queueName,
            };

            GetQueueUrlResponse response = await client.GetQueueUrlAsync(request);
            return response.QueueUrl;
        }

        /// <summary>
        /// Retrieves the message from the quque at the URL passed in the
        /// queueURL parameters using the client.
        /// </summary>
        /// <param name="client">The SQS client used to retrieve a message.</param>
        /// <param name="queueUrl">The URL of the queue from which to retrieve
        /// a message.</param>
        /// <returns>The response from the call to ReceiveMessageAsync.</returns>
        public static async Task<ReceiveMessageResponse>
ReceiveAndDeleteMessage(IAmazonSQS client, string queueUrl)
        {
            // Receive a single message from the queue.
```

```
            var receiveMessageRequest = new ReceiveMessageRequest
            {
                AttributeNames = { "SentTimestamp" },
                MaxNumberOfMessages = 1,
                MessageAttributeNames = { "All" },
                QueueUrl = queueUrl,
                VisibilityTimeout = 0,
                WaitTimeSeconds = 0,
            };

            var receiveMessageResponse = await
client.ReceiveMessageAsync(receiveMessageRequest);

            // Delete the received message from the queue.
            var deleteMessageRequest = new DeleteMessageRequest
            {
                QueueUrl = queueUrl,
                ReceiptHandle = receiveMessageResponse.Messages[0].ReceiptHandle,
            };

            await client.DeleteMessageAsync(deleteMessageRequest);

            return receiveMessageResponse;
        }
    }
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for .NET da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila usando seu URL.

```
/// <summary>
/// Delete a queue by its URL.
/// </summary>
/// <param name="queueUrl">The url of the queue.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteQueueByUrl(string queueUrl)
{
    var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
        new DeleteQueueRequest()
        {
            QueueUrl = queueUrl
        });
    return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for .NET da API.

Obter atributos para uma fila

O exemplo de código a seguir mostra como obter atributos para uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get the ARN for a queue from its URL.
/// </summary>
/// <param name="queueUrl">The URL of the queue.</param>
/// <returns>The ARN of the queue.</returns>
public async Task<string> GetQueueArnByUrl(string queueUrl)
{
    var getAttributesRequest = new GetQueueAttributesRequest()
    {
```

```
            QueueUrl = queueUrl,
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await _amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for .NET da API.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.SQS;
using Amazon.SQS.Model;

public class GetQueueUrl
{
    /// <summary>
    /// Initializes the Amazon SQS client object and then calls the
    /// GetQueueUrlAsync method to retrieve the URL of an Amazon SQS
    /// queue.
    /// </summary>
    public static async Task Main()
    {
        // If the Amazon SQS message queue is not in the same AWS Region as your
```

```
            // default user, you need to provide the AWS Region as a parameter to
the
            // client constructor.
            var client = new AmazonSQSClient();

            string queueName = "New-Example-Queue";

            try
            {
                var response = await client.GetQueueUrlAsync(queueName);

                if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
                {
                    Console.WriteLine($"The URL for {queueName} is:
{response.QueueUrl}");
                }
            }
            catch (QueueDoesNotExistException ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine($"The queue {queueName} was not found.");
            }
        }
    }
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for .NET da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba mensagens de uma fila usando seu URL.

```
    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
        return messageResponse.Messages;
    }
```

Receba uma mensagem de uma fila do Amazon SQS e, em seguida, exclua a mensagem.

```
        public static async Task Main()
        {
            // If the AWS Region you want to use is different from
            // the AWS Region defined for the default user, supply
            // the specify your AWS Region to the client constructor.
            var client = new AmazonSQSClient();
            string queueName = "Example_Queue";

            var queueUrl = await GetQueueUrl(client, queueName);
            Console.WriteLine($"The SQS queue's URL is {queueUrl}");

            var response = await ReceiveAndDeleteMessage(client, queueUrl);

            Console.WriteLine($"Message: {response.Messages[0]}");
        }

        /// <summary>
        /// Retrieve the queue URL for the queue named in the queueName
```

```
        /// property using the client object.
        /// </summary>
        /// <param name="client">The Amazon SQS client used to retrieve the
        /// queue URL.</param>
        /// <param name="queueName">A string representing  name of the queue
        /// for which to retrieve the URL.</param>
        /// <returns>The URL of the queue.</returns>
        public static async Task<string> GetQueueUrl(IAmazonSQS client, string
queueName)
        {
            var request = new GetQueueUrlRequest
            {
                QueueName = queueName,
            };

            GetQueueUrlResponse response = await client.GetQueueUrlAsync(request);
            return response.QueueUrl;
        }

        /// <summary>
        /// Retrieves the message from the quque at the URL passed in the
        /// queueURL parameters using the client.
        /// </summary>
        /// <param name="client">The SQS client used to retrieve a message.</param>
        /// <param name="queueUrl">The URL of the queue from which to retrieve
        /// a message.</param>
        /// <returns>The response from the call to ReceiveMessageAsync.</returns>
        public static async Task<ReceiveMessageResponse>
ReceiveAndDeleteMessage(IAmazonSQS client, string queueUrl)
        {
            // Receive a single message from the queue.
            var receiveMessageRequest = new ReceiveMessageRequest
            {
                AttributeNames = { "SentTimestamp" },
                MaxNumberOfMessages = 1,
                MessageAttributeNames = { "All" },
                QueueUrl = queueUrl,
                VisibilityTimeout = 0,
                WaitTimeSeconds = 0,
            };

            var receiveMessageResponse = await
client.ReceiveMessageAsync(receiveMessageRequest);
```

```
            // Delete the received message from the queue.
            var deleteMessageRequest = new DeleteMessageRequest
            {
                QueueUrl = queueUrl,
                ReceiptHandle = receiveMessageResponse.Messages[0].ReceiptHandle,
            };

            await client.DeleteMessageAsync(deleteMessageRequest);

            return receiveMessageResponse;
        }
    }
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for .NET da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila do Amazon SQS e envie uma mensagem para ela.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon;
    using Amazon.SQS;
    using Amazon.SQS.Model;

    public class CreateSendExample
    {
        // Specify your AWS Region (an example Region is shown).
        private static readonly string QueueName = "Example_Queue";
```

```
        private static readonly RegionEndpoint ServiceRegion =
 RegionEndpoint.USWest2;
        private static IAmazonSQS client;

        public static async Task Main()
        {
            client = new AmazonSQSClient(ServiceRegion);
            var createQueueResponse = await CreateQueue(client, QueueName);

            string queueUrl = createQueueResponse.QueueUrl;

            Dictionary<string, MessageAttributeValue> messageAttributes = new
 Dictionary<string, MessageAttributeValue>
            {
                { "Title",   new MessageAttributeValue { DataType = "String",
 StringValue = "The Whistler" } },
                { "Author",  new MessageAttributeValue { DataType = "String",
 StringValue = "John Grisham" } },
                { "WeeksOn", new MessageAttributeValue { DataType = "Number",
 StringValue = "6" } },
            };

            string messageBody = "Information about current NY Times fiction
 bestseller for week of 12/11/2016.";

            var sendMsgResponse = await SendMessage(client, queueUrl, messageBody,
 messageAttributes);
        }

        /// <summary>
        /// Creates a new Amazon SQS queue using the queue name passed to it
        /// in queueName.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueName">A string representing the name of the queue
        /// to create.</param>
        /// <returns>A CreateQueueResponse that contains information about the
        /// newly created queue.</returns>
        public static async Task<CreateQueueResponse> CreateQueue(IAmazonSQS client,
 string queueName)
        {
            var request = new CreateQueueRequest
            {
```

```
                QueueName = queueName,
                Attributes = new Dictionary<string, string>
                {
                    { "DelaySeconds", "60" },
                    { "MessageRetentionPeriod", "86400" },
                },
            };

            var response = await client.CreateQueueAsync(request);
            Console.WriteLine($"Created a queue with URL : {response.QueueUrl}");

            return response;
        }

        /// <summary>
        /// Sends a message to an SQS queue.
        /// </summary>
        /// <param name="client">An SQS client object used to send the message.</
param>
        /// <param name="queueUrl">The URL of the queue to which to send the
        /// message.</param>
        /// <param name="messageBody">A string representing the body of the
        /// message to be sent to the queue.</param>
        /// <param name="messageAttributes">Attributes for the message to be
        /// sent to the queue.</param>
        /// <returns>A SendMessageResponse object that contains information
        /// about the message that was sent.</returns>
        public static async Task<SendMessageResponse> SendMessage(
            IAmazonSQS client,
            string queueUrl,
            string messageBody,
            Dictionary<string, MessageAttributeValue> messageAttributes)
        {
            var sendMessageRequest = new SendMessageRequest
            {
                DelaySeconds = 10,
                MessageAttributes = messageAttributes,
                MessageBody = messageBody,
                QueueUrl = queueUrl,
            };

            var response = await client.SendMessageAsync(sendMessageRequest);
            Console.WriteLine($"Sent a message with id : {response.MessageId}");
```

```
            return response;
        }
    }
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for .NET da API.

Definir atributos de fila

O exemplo de código a seguir mostra como definir os atributos para uma fila do Amazon SQS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina o atributo de política de uma fila para um tópico.

```
    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string topicArn,
string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                         $"\"Service\": " +
                                             "\"sns.amazonaws.com\"" +
                                            "}," +
                                     "\"Action\": \"sqs:SendMessage\"," +
                                     $"\"Resource\": \"{queueArn}\"," +
```

```
                                        "\"Condition\": {" +
                                             "\"ArnEquals\": {" +
                                                  $"\"aws:SourceArn\": \"{topicArn}\""
+
                                              "}" +
                                          "}" +
                                     "}]" +
                                 "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
                QueueUrl = queueUrl,
                Attributes = new Dictionary<string, string>() { { "Policy",
queuePolicy } }
            });
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for .NET da API.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Console application to run a workflow scenario for topics and queues.
/// </summary>
public static class TopicsAndQueues
{
    private static bool _useFifoTopic = false;
    private static bool _useContentBasedDeduplication = false;
    private static string _topicName = null!;
    private static string _topicArn = null!;

    private static readonly int _queueCount = 2;
    private static readonly string[] _queueUrls = new string[_queueCount];
    private static readonly string[] _subscriptionArns = new string[_queueCount];
    private static readonly string[] _tones = { "cheerful", "funny", "serious",
 "sincere" };
    public static SNSWrapper SnsWrapper { get; set; } = null!;
    public static SQSWrapper SqsWrapper { get; set; } = null!;
    public static bool UseConsole { get; set; } = true;
    static async Task Main(string[] args)
    {
        // Set up dependency injection for Amazon EventBridge.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonSQS>()
                    .AddAWSService<IAmazonSimpleNotificationService>()
                    .AddTransient<SNSWrapper>()
                    .AddTransient<SQSWrapper>()
            )
            .Build();

        ServicesSetup(host);
        PrintDescription();

        await RunScenario();

    }
```

```
    /// <summary>
    /// Populate the services for use within the console application.
    /// </summary>
    /// <param name="host">The services host.</param>
    private static void ServicesSetup(IHost host)
    {
        SnsWrapper = host.Services.GetRequiredService<SNSWrapper>();
        SqsWrapper = host.Services.GetRequiredService<SQSWrapper>();
    }

    /// <summary>
    /// Run the scenario for working with topics and queues.
    /// </summary>
    /// <returns>True if successful.</returns>
    public static async Task<bool> RunScenario()
    {
        try
        {
            await SetupTopic();

            await SetupQueues();

            await PublishMessages();

            foreach (var queueUrl in _queueUrls)
            {
                var messages = await PollForMessages(queueUrl);
                if (messages.Any())
                {
                    await DeleteMessages(queueUrl, messages);
                }
            }
            await CleanupResources();

            Console.WriteLine("Messaging with topics and queues workflow is
complete.");
            return true;
        }
        catch (Exception ex)
        {
            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"There was a problem running the scenario:
{ex.Message}");
            await CleanupResources();
```

```
            Console.WriteLine(new string('-', 80));
            return false;
        }
    }

    /// <summary>
    /// Print a description for the tasks in the workflow.
    /// </summary>
    /// <returns>Async task.</returns>
    private static void PrintDescription()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Welcome to messaging with topics and queues.");

        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"In this workflow, you will create an SNS topic and
 subscribe {_queueCount} SQS queues to the topic." +
                          $"\r\nYou can select from several options for configuring
 the topic and the subscriptions for the 2 queues." +
                          $"\r\nYou can then post to the topic and see the results
 in the queues.\r\n");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up the SNS topic to be used with the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task<string> SetupTopic()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"SNS topics can be configured as FIFO (First-In-First-
Out)." +
                          $"\r\nFIFO topics deliver messages in order and support
 deduplication and message filtering." +
                          $"\r\nYou can then post to the topic and see the results
 in the queues.\r\n");

        _useFifoTopic = GetYesNoResponse("Would you like to work with FIFO
 topics?");

        if (_useFifoTopic)
        {
```

```
            Console.WriteLine(new string('-', 80));
            _topicName = GetUserResponse("Enter a name for your SNS topic: ",
 "example-topic");
            Console.WriteLine(
                "Because you have selected a FIFO topic, '.fifo' must be appended to
 the topic name.\r\n");

            Console.WriteLine(new string('-', 80));
            Console.WriteLine($"Because you have chosen a FIFO topic, deduplication
 is supported." +
                              $"\r\nDeduplication IDs are either set in the message
 or automatically generated " +
                              $"\r\nfrom content using a hash function.\r\n" +
                              $"\r\nIf a message is successfully published to an SNS
 FIFO topic, any message " +
                              $"\r\npublished and determined to have the same
 deduplication ID, " +
                              $"\r\nwithin the five-minute deduplication interval,
 is accepted but not delivered.\r\n" +
                              $"\r\nFor more information about deduplication, " +
                              $"\r\nsee https://docs.aws.amazon.com/sns/latest/dg/
fifo-message-dedup.html.");

            _useContentBasedDeduplication = GetYesNoResponse("Use content-based
 deduplication instead of entering a deduplication ID?");
            Console.WriteLine(new string('-', 80));
        }

        _topicArn = await SnsWrapper.CreateTopicWithName(_topicName, _useFifoTopic,
 _useContentBasedDeduplication);

        Console.WriteLine($"Your new topic with the name {_topicName}" +
                          $"\r\nand Amazon Resource Name (ARN) {_topicArn}" +
                          $"\r\nhas been created.\r\n");

        Console.WriteLine(new string('-', 80));
        return _topicArn;
    }

    /// <summary>
    /// Set up the queues.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task SetupQueues()
```

```
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now you will create {_queueCount} Amazon Simple Queue
Service (Amazon SQS) queues to subscribe to the topic.");

        // Repeat this section for each queue.
        for (int i = 0; i < _queueCount; i++)
        {
            var queueName = GetUserResponse("Enter a name for an Amazon SQS queue:
", $"example-queue-{i}");
            if (_useFifoTopic)
            {
                // Only explain this once.
                if (i == 0)
                {
                    Console.WriteLine(
                        "Because you have selected a FIFO topic, '.fifo' must be
appended to the queue name.");
                }

                var queueUrl = await SqsWrapper.CreateQueueWithName(queueName,
_useFifoTopic);

                _queueUrls[i] = queueUrl;

                Console.WriteLine($"Your new queue with the name {queueName}" +
                                  $"\r\nand queue URL {queueUrl}" +
                                  $"\r\nhas been created.\r\n");

                if (i == 0)
                {
                    Console.WriteLine(
                        $"The queue URL is used to retrieve the queue ARN,\r\n" +
                        $"which is used to create a subscription.");
                    Console.WriteLine(new string('-', 80));
                }

                var queueArn = await SqsWrapper.GetQueueArnByUrl(queueUrl);

                if (i == 0)
                {
                    Console.WriteLine(
                        $"An AWS Identity and Access Management (IAM) policy must be
attached to an SQS queue, enabling it to receive\r\n" +
```

```
                        $"messages from an SNS topic");
                }

                await SqsWrapper.SetQueuePolicyForTopic(queueArn, _topicArn,
 queueUrl);

                await SetupFilters(i, queueArn, queueName);
            }
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Set up filters with user options for a queue.
    /// </summary>
    /// <param name="queueCount">The number of this queue.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="queueName">The name of the queue.</param>
    /// <returns>Async Task.</returns>
    public static async Task SetupFilters(int queueCount, string queueArn, string
 queueName)
    {
        if (_useFifoTopic)
        {
            Console.WriteLine(new string('-', 80));
            // Only explain this once.
            if (queueCount == 0)
            {
                Console.WriteLine(
                    "Subscriptions to a FIFO topic can have filters." +
                    "If you add a filter to this subscription, then only the
 filtered messages " +
                    "will be received in the queue.");

                Console.WriteLine(
                    "For information about message filtering, " +
                    "see https://docs.aws.amazon.com/sns/latest/dg/sns-message-
filtering.html");

                Console.WriteLine(
                    "For this example, you can filter messages by a" +
                    "TONE attribute.");
            }
```

```
            var useFilter = GetYesNoResponse($"Filter messages for {queueName}'s
subscription to the topic?");

            string? filterPolicy = null;
            if (useFilter)
            {
                filterPolicy = CreateFilterPolicy();
            }
            var subscriptionArn = await
SnsWrapper.SubscribeTopicWithFilter(_topicArn, filterPolicy,
                queueArn);
            _subscriptionArns[queueCount] = subscriptionArn;

            Console.WriteLine(
                $"The queue {queueName} has been subscribed to the topic
{_topicName} " +
                $"with the subscription ARN {subscriptionArn}");
            Console.WriteLine(new string('-', 80));
        }
    }

    /// <summary>
    /// Use user input to create a filter policy for a subscription.
    /// </summary>
    /// <returns>The serialized filter policy.</returns>
    public static string CreateFilterPolicy()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine(
            $"You can filter messages by one or more of the following" +
            $"TONE attributes.");

        List<string> filterSelections = new List<string>();

        var selectionNumber = 0;
        do
        {
            Console.WriteLine(
                $"Enter a number to add a TONE filter, or enter 0 to stop adding
filters.");
            for (int i = 0; i < _tones.Length; i++)
            {
                Console.WriteLine($"\t{i + 1}. {_tones[i]}");
```

```
            }

            var selection = GetUserResponse("", filterSelections.Any() ? "0" : "1");
            int.TryParse(selection, out selectionNumber);
            if (selectionNumber > 0 && !
filterSelections.Contains(_tones[selectionNumber - 1]))
            {
                filterSelections.Add(_tones[selectionNumber - 1]);
            }
        } while (selectionNumber != 0);

        var filters = new Dictionary<string, List<string>>
        {
            { "tone", filterSelections }
        };
        string filterPolicy = JsonSerializer.Serialize(filters);
        return filterPolicy;
    }

    /// <summary>
    /// Publish messages using user settings.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task PublishMessages()
    {
        Console.WriteLine("Now we can publish messages.");

        var keepSendingMessages = true;
        string? deduplicationId = null;
        string? toneAttribute = null;
        while (keepSendingMessages)
        {
            Console.WriteLine();
            var message = GetUserResponse("Enter a message to publish.", "This is a
 sample message");

            if (_useFifoTopic)
            {
                Console.WriteLine("Because you are using a FIFO topic, you must set
 a message group ID." +
                                  "\r\nAll messages within the same group will be
 received in the order " +
                                  "they were published.");
```

```
                Console.WriteLine();
                var messageGroupId = GetUserResponse("Enter a message group ID for
this message:", "1");

                if (!_useContentBasedDeduplication)
                {
                    Console.WriteLine("Because you are not using content-based
deduplication, " +
                                      "you must enter a deduplication ID.");

                    Console.WriteLine("Enter a deduplication ID for this message.");
                    deduplicationId = GetUserResponse("Enter a deduplication ID for
this message.", "1");
                }

                if (GetYesNoResponse("Add an attribute to this message?"))
                {
                    Console.WriteLine("Enter a number for an attribute.");
                    for (int i = 0; i < _tones.Length; i++)
                    {
                        Console.WriteLine($"\t{i + 1}. {_tones[i]}");
                    }

                    var selection = GetUserResponse("", "1");
                    int.TryParse(selection, out var selectionNumber);

                    if (selectionNumber > 0 && selectionNumber < _tones.Length)
                    {
                        toneAttribute = _tones[selectionNumber - 1];
                    }
                }

                var messageID = await SnsWrapper.PublishToTopicWithAttribute(
                    _topicArn, message, "tone", toneAttribute, deduplicationId,
messageGroupId);

                Console.WriteLine($"Message published with id {messageID}.");
            }

            keepSendingMessages = GetYesNoResponse("Send another message?", false);
        }
    }

    /// <summary>
```

```
    /// Poll for the published messages to see the results of the user's choices.
    /// </summary>
    /// <returns>Async task.</returns>
    public static async Task<List<Message>> PollForMessages(string queueUrl)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Now the SQS queue at {queueUrl} will be polled to
retrieve the messages." +
                          "\r\nPress any key to continue.");
        if (UseConsole)
        {
            Console.ReadLine();
        }

        var moreMessages = true;
        var messages = new List<Message>();
        while (moreMessages)
        {
            var newMessages = await SqsWrapper.ReceiveMessagesByUrl(queueUrl, 10);

            moreMessages = newMessages.Any();
            if (moreMessages)
            {
                messages.AddRange(newMessages);
            }
        }

        Console.WriteLine($"{messages.Count} message(s) were received by the queue
at {queueUrl}.");

        foreach (var message in messages)
        {
            Console.WriteLine("\tMessage:" +
                              $"\n\t{message.Body}");
        }

        Console.WriteLine(new string('-', 80));
        return messages;
    }

    /// <summary>
    /// Delete the message using handles in a batch.
    /// </summary>
    /// <returns>Async task.</returns>
```

```
    public static async Task DeleteMessages(string queueUrl, List<Message> messages)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine("Now we can delete the messages in this queue in a
batch.");
        await SqsWrapper.DeleteMessageBatchByUrl(queueUrl, messages);
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Clean up the resources from the scenario.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task CleanupResources()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"Clean up resources.");

        try
        {
            foreach (var queueUrl in _queueUrls)
            {
                if (!string.IsNullOrEmpty(queueUrl))
                {
                    var deleteQueue =
                        GetYesNoResponse($"Delete queue with url {queueUrl}?");
                    if (deleteQueue)
                    {
                        await SqsWrapper.DeleteQueueByUrl(queueUrl);
                    }
                }
            }

            foreach (var subscriptionArn in _subscriptionArns)
            {
                if (!string.IsNullOrEmpty(subscriptionArn))
                {
                    await SnsWrapper.UnsubscribeByArn(subscriptionArn);
                }
            }

            var deleteTopic = GetYesNoResponse($"Delete topic {_topicName}?");
            if (deleteTopic)
            {
```

```
                await SnsWrapper.DeleteTopicByArn(_topicArn);
            }
        }
        catch (Exception ex)
        {
            Console.WriteLine($"Unable to clean up resources. Here's why:
{ex.Message}.");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Helper method to get a yes or no response from the user.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static bool GetYesNoResponse(string question, bool defaultAnswer = true)
    {
        if (UseConsole)
        {
            Console.WriteLine(question);
            var ynResponse = Console.ReadLine();
            var response = ynResponse != null &&
                           ynResponse.Equals("y",
                               StringComparison.InvariantCultureIgnoreCase);
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }

    /// <summary>
    /// Helper method to get a string response from the user through the console.
    /// </summary>
    /// <param name="question">The question string to print on the console.</param>
    /// <param name="defaultAnswer">Optional default answer to use.</param>
    /// <returns>True if the user responds with a yes.</returns>
    private static string GetUserResponse(string question, string defaultAnswer)
    {
        if (UseConsole)
        {
            var response = "";
```

```
            while (string.IsNullOrEmpty(response))
            {
                Console.WriteLine(question);
                response = Console.ReadLine();
            }
            return response;
        }
        // If not using the console, use the default.
        return defaultAnswer;
    }
}
```

Crie uma classe que envolva as operações do Amazon SQS.

```
/// <summary>
/// Wrapper for Amazon Simple Queue Service (SQS) operations.
/// </summary>
public class SQSWrapper
{
    private readonly IAmazonSQS _amazonSQSClient;

    /// <summary>
    /// Constructor for the Amazon SQS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SQS client.</param>
    public SQSWrapper(IAmazonSQS amazonSQS)
    {
        _amazonSQSClient = amazonSQS;
    }

    /// <summary>
    /// Create a queue with a specific name.
    /// </summary>
    /// <param name="queueName">The name for the queue.</param>
    /// <param name="useFifoQueue">True to use a FIFO queue.</param>
    /// <returns>The url for the queue.</returns>
    public async Task<string> CreateQueueWithName(string queueName, bool
 useFifoQueue)
    {
        int maxMessage = 256 * 1024;
        var queueAttributes = new Dictionary<string, string>
```

```
        {
            {
                QueueAttributeName.MaximumMessageSize,
                maxMessage.ToString()
            }
        };

        var createQueueRequest = new CreateQueueRequest()
        {
            QueueName = queueName,
            Attributes = queueAttributes
        };

        if (useFifoQueue)
        {
            // Update the name if it is not correct for a FIFO queue.
            if (!queueName.EndsWith(".fifo"))
            {
                createQueueRequest.QueueName = queueName + ".fifo";
            }

            // Add an attribute for a FIFO queue.
            createQueueRequest.Attributes.Add(
                QueueAttributeName.FifoQueue, "true");
        }

        var createResponse = await _amazonSQSClient.CreateQueueAsync(
            new CreateQueueRequest()
            {
                QueueName = queueName
            });
        return createResponse.QueueUrl;
    }

    /// <summary>
    /// Get the ARN for a queue from its URL.
    /// </summary>
    /// <param name="queueUrl">The URL of the queue.</param>
    /// <returns>The ARN of the queue.</returns>
    public async Task<string> GetQueueArnByUrl(string queueUrl)
    {
        var getAttributesRequest = new GetQueueAttributesRequest()
        {
            QueueUrl = queueUrl,
```

```
            AttributeNames = new List<string>() { QueueAttributeName.QueueArn }
        };

        var getAttributesResponse = await _amazonSQSClient.GetQueueAttributesAsync(
            getAttributesRequest);

        return getAttributesResponse.QueueARN;
    }

    /// <summary>
    /// Set the policy attribute of a queue for a topic.
    /// </summary>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="queueUrl">The url for the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> SetQueuePolicyForTopic(string queueArn, string topicArn,
string queueUrl)
    {
        var queuePolicy = "{" +
                                "\"Version\": \"2012-10-17\"," +
                                "\"Statement\": [{" +
                                     "\"Effect\": \"Allow\"," +
                                     "\"Principal\": {" +
                                         $"\"Service\": " +
                                             "\"sns.amazonaws.com\"" +
                                            "}," +
                                     "\"Action\": \"sqs:SendMessage\"," +
                                     $"\"Resource\": \"{queueArn}\"," +
                                      "\"Condition\": {" +
                                           "\"ArnEquals\": {" +
                                                $"\"aws:SourceArn\": \"{topicArn}\""
+
                                            "}" +
                                        "}" +
                                "}]" +
                            "}";
        var attributesResponse = await _amazonSQSClient.SetQueueAttributesAsync(
            new SetQueueAttributesRequest()
            {
                QueueUrl = queueUrl,
                Attributes = new Dictionary<string, string>() { { "Policy",
queuePolicy } }
            });
```

```
        return attributesResponse.HttpStatusCode == HttpStatusCode.OK;
    }

    /// <summary>
    /// Receive messages from a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>The list of messages.</returns>
    public async Task<List<Message>> ReceiveMessagesByUrl(string queueUrl, int
 maxMessages)
    {
        // Setting WaitTimeSeconds to non-zero enables long polling.
        // For information about long polling, see
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        var messageResponse = await _amazonSQSClient.ReceiveMessageAsync(
            new ReceiveMessageRequest()
            {
                QueueUrl = queueUrl,
                MaxNumberOfMessages = maxMessages,
                WaitTimeSeconds = 1
            });
        return messageResponse.Messages;
    }

    /// <summary>
    /// Delete a batch of messages from a queue by its url.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMessageBatchByUrl(string queueUrl, List<Message>
 messages)
    {
        var deleteRequest = new DeleteMessageBatchRequest()
        {
            QueueUrl = queueUrl,
            Entries = new List<DeleteMessageBatchRequestEntry>()
        };
        foreach (var message in messages)
        {
            deleteRequest.Entries.Add(new DeleteMessageBatchRequestEntry()
            {
                ReceiptHandle = message.ReceiptHandle,
                Id = message.MessageId
```

```
            });
        }

        var deleteResponse = await
 _amazonSQSClient.DeleteMessageBatchAsync(deleteRequest);

        return deleteResponse.Failed.Any();
    }

    /// <summary>
    /// Delete a queue by its URL.
    /// </summary>
    /// <param name="queueUrl">The url of the queue.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteQueueByUrl(string queueUrl)
    {
        var deleteResponse = await _amazonSQSClient.DeleteQueueAsync(
            new DeleteQueueRequest()
            {
                QueueUrl = queueUrl
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

Crie uma classe que envolva as operações do Amazon SNS.

```
/// <summary>
/// Wrapper for Amazon Simple Notification Service (SNS) operations.
/// </summary>
public class SNSWrapper
{
    private readonly IAmazonSimpleNotificationService _amazonSNSClient;

    /// <summary>
    /// Constructor for the Amazon SNS wrapper.
    /// </summary>
    /// <param name="amazonSQS">The injected Amazon SNS client.</param>
    public SNSWrapper(IAmazonSimpleNotificationService amazonSNS)
    {
        _amazonSNSClient = amazonSNS;
```

```
    }

    /// <summary>
    /// Create a new topic with a name and specific FIFO and de-duplication
 attributes.
    /// </summary>
    /// <param name="topicName">The name for the topic.</param>
    /// <param name="useFifoTopic">True to use a FIFO topic.</param>
    /// <param name="useContentBasedDeduplication">True to use content-based de-
duplication.</param>
    /// <returns>The ARN of the new topic.</returns>
    public async Task<string> CreateTopicWithName(string topicName, bool
 useFifoTopic, bool useContentBasedDeduplication)
    {
        var createTopicRequest = new CreateTopicRequest()
        {
            Name = topicName,
        };

        if (useFifoTopic)
        {
            // Update the name if it is not correct for a FIFO topic.
            if (!topicName.EndsWith(".fifo"))
            {
                createTopicRequest.Name = topicName + ".fifo";
            }

            // Add the attributes from the method parameters.
            createTopicRequest.Attributes = new Dictionary<string, string>
            {
                { "FifoTopic", "true" }
            };
            if (useContentBasedDeduplication)
            {
                createTopicRequest.Attributes.Add("ContentBasedDeduplication",
 "true");
            }
        }

        var createResponse = await
 _amazonSNSClient.CreateTopicAsync(createTopicRequest);
        return createResponse.TopicArn;
    }
```

```
    /// <summary>
    /// Subscribe a queue to a topic with optional filters.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="useFifoTopic">The optional filtering policy for the
 subscription.</param>
    /// <param name="queueArn">The ARN of the queue.</param>
    /// <returns>The ARN of the new subscription.</returns>
    public async Task<string> SubscribeTopicWithFilter(string topicArn, string?
 filterPolicy, string queueArn)
    {
        var subscribeRequest = new SubscribeRequest()
        {
            TopicArn = topicArn,
            Protocol = "sqs",
            Endpoint = queueArn
        };

        if (!string.IsNullOrEmpty(filterPolicy))
        {
            subscribeRequest.Attributes = new Dictionary<string, string>
 { { "FilterPolicy", filterPolicy } };
        }

        var subscribeResponse = await
 _amazonSNSClient.SubscribeAsync(subscribeRequest);
        return subscribeResponse.SubscriptionArn;
    }

    /// <summary>
    /// Publish a message to a topic with an attribute and optional deduplication
 and group IDs.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <param name="message">The message to publish.</param>
    /// <param name="attributeName">The optional attribute for the message.</param>
    /// <param name="attributeValue">The optional attribute value for the message.</
param>
    /// <param name="deduplicationId">The optional deduplication ID for the
 message.</param>
    /// <param name="groupId">The optional group ID for the message.</param>
    /// <returns>The ID of the message published.</returns>
    public async Task<string> PublishToTopicWithAttribute(
        string topicArn,
```

```
        string message,
        string? attributeName = null,
        string? attributeValue = null,
        string? deduplicationId = null,
        string? groupId = null)
    {
        var publishRequest = new PublishRequest()
        {
            TopicArn = topicArn,
            Message = message,
            MessageDeduplicationId = deduplicationId,
            MessageGroupId = groupId
        };

        if (attributeValue != null)
        {
            // Add the string attribute if it exists.
            publishRequest.MessageAttributes =
                new Dictionary<string, MessageAttributeValue>
                {
                    { attributeName!, new MessageAttributeValue() { StringValue =
attributeValue, DataType = "String"} }
                };
        }

        var publishResponse = await _amazonSNSClient.PublishAsync(publishRequest);
        return publishResponse.MessageId;
    }


    /// <summary>
    /// Unsubscribe from a topic by a subscription ARN.
    /// </summary>
    /// <param name="subscriptionArn">The ARN of the subscription.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> UnsubscribeByArn(string subscriptionArn)
    {
        var unsubscribeResponse = await _amazonSNSClient.UnsubscribeAsync(
            new UnsubscribeRequest()
            {
                SubscriptionArn = subscriptionArn
            });
        return unsubscribeResponse.HttpStatusCode == HttpStatusCode.OK;
    }
```

```
    /// <summary>
    /// Delete a topic by its topic ARN.
    /// </summary>
    /// <param name="topicArn">The ARN of the topic.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTopicByArn(string topicArn)
    {
        var deleteResponse = await _amazonSNSClient.DeleteTopicAsync(
            new DeleteTopicRequest()
            {
                TopicArn = topicArn
            });
        return deleteResponse.HttpStatusCode == HttpStatusCode.OK;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;


// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali

namespace SqsIntegrationSampleCode
{
    public async Task FunctionHandler(SQSEvent evnt, ILambdaContext context)
    {
        foreach (var message in evnt.Records)
        {
            await ProcessMessageAsync(message, context);
        }

        context.Logger.LogInformation("done");
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        try
```

```
        {
            context.Logger.LogInformation($"Processed message {message.Body}");

            // TODO: Do interesting work based on the new message
            await Task.CompletedTask;
        }
        catch (Exception e)
        {
            //You can use Dead Letter Queue to handle failures. By configuring a
 Lambda DLQ.
            context.Logger.LogError($"An error occurred");
            throw;
        }

    }
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando o .NET.

```
using Amazon.Lambda.Core;
using Amazon.Lambda.SQSEvents;

// Assembly attribute to enable the Lambda function's JSON input to be converted
 into a .NET class.
[assembly:
 LambdaSerializer(typeof(Amazon.Lambda.Serialization.SystemTextJson.DefaultLambdaJsonSeriali
```

```
namespace sqsSample;

public class Function
{
    public async Task<SQSBatchResponse> FunctionHandler(SQSEvent evnt,
 ILambdaContext context)
    {
        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 List<SQSBatchResponse.BatchItemFailure>();
        foreach(var message in evnt.Records)
        {
            try
            {
                //process your message
                await ProcessMessageAsync(message, context);
            }
            catch (System.Exception)
            {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.Add(new
 SQSBatchResponse.BatchItemFailure{ItemIdentifier=message.MessageId});
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }

    private async Task ProcessMessageAsync(SQSEvent.SQSMessage message,
 ILambdaContext context)
    {
        if (String.IsNullOrEmpty(message.Body))
        {
            throw new Exception("No Body in SQS Message.");
        }
        context.Logger.LogInformation($"Processed message {message.Body}");
        // TODO: Do interesting work based on the new message
        await Task.CompletedTask;
    }
}
```

Exemplos de Step Functions usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Step Functions.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Step Functions

Os exemplos de código a seguir mostram como começar a usar o Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace StepFunctionsActions;

using Amazon.StepFunctions;
using Amazon.StepFunctions.Model;

public class HelloStepFunctions
{
    static async Task Main()
    {
        var stepFunctionsClient = new AmazonStepFunctionsClient();
```

```
        Console.Clear();
        Console.WriteLine("Welcome to AWS Step Functions");
        Console.WriteLine("Let's list up to 10 of your state machines:");
        var stateMachineListRequest = new ListStateMachinesRequest { MaxResults =
 10 };

        // Get information for up to 10 Step Functions state machines.
        var response = await
 stepFunctionsClient.ListStateMachinesAsync(stateMachineListRequest);

        if (response.StateMachines.Count > 0)
        {
            response.StateMachines.ForEach(stateMachine =>
            {
                Console.WriteLine($"State Machine Name: {stateMachine.Name}\tAmazon
 Resource Name (ARN): {stateMachine.StateMachineArn}");
            });
        }
        else
        {
            Console.WriteLine("\tNo state machines were found.");
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma máquina de estado

O exemplo de código a seguir mostra como criar uma máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineName">Name for the new Step Functions state
    /// machine.</param>
    /// <param name="definition">A JSON string that defines the Step Functions
    /// state machine.</param>
    /// <param name="roleArn">The Amazon Resource Name (ARN) of the role.</param>
    /// <returns></returns>
    public async Task<string> CreateStateMachine(string stateMachineName, string
definition, string roleArn)
    {
        var request = new CreateStateMachineRequest
        {
            Name = stateMachineName,
            Definition = definition,
            RoleArn = roleArn
        };

        var response =
            await _amazonStepFunctions.CreateStateMachineAsync(request);
        return response.StateMachineArn;
    }
```

- Para obter detalhes da API, consulte CreateStateMachinea Referência AWS SDK for .NET da API.

Criar uma atividade

O exemplo de código a seguir mostra como criar uma atividade do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a Step Functions activity using the supplied name.
    /// </summary>
    /// <param name="activityName">The name for the new Step Functions activity.</
param>
    /// <returns>The Amazon Resource Name (ARN) for the new activity.</returns>
    public async Task<string> CreateActivity(string activityName)
    {
        var response = await _amazonStepFunctions.CreateActivityAsync(new
 CreateActivityRequest { Name = activityName });
        return response.ActivityArn;
    }
```

- Para obter detalhes da API, consulte CreateActivitya Referência AWS SDK for .NET da API.

Excluir uma máquina de estado

O exemplo de código a seguir mostra como excluir uma máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a Step Functions state machine.
    /// </summary>
```

```
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// state machine.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteStateMachine(string stateMachineArn)
    {
        var response = await _amazonStepFunctions.DeleteStateMachineAsync(new
DeleteStateMachineRequest
        { StateMachineArn = stateMachineArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteStateMachinea Referência AWS SDK for .NET da API.

Excluir uma atividade.

Os exemplos de código a seguir mostram como excluir uma atividade do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a Step Machine activity.
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the activity.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteActivity(string activityArn)
    {
        var response = await _amazonStepFunctions.DeleteActivityAsync(new
DeleteActivityRequest { ActivityArn = activityArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteActivitya Referência AWS SDK for .NET da API.

Descrever uma máquina de estado

O exemplo de código a seguir mostra como descrever uma máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information about the specified Step Functions state machine.
    /// </summary>
    /// <param name="StateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine to retrieve.</param>
    /// <returns>Information about the specified Step Functions state machine.</
returns>
    public async Task<DescribeStateMachineResponse> DescribeStateMachineAsync(string
 StateMachineArn)
    {
        var response = await _amazonStepFunctions.DescribeStateMachineAsync(new
 DescribeStateMachineRequest { StateMachineArn = StateMachineArn });
        return response;
    }
```

- Para obter detalhes da API, consulte DescribeStateMachinea Referência AWS SDK for .NET da API.

Descrever a execução de uma máquina de estado

O exemplo de código a seguir mostra como descrever uma execução de máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information about the specified Step Functions execution.
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of the
    /// Step Functions execution.</param>
    /// <returns>The API response returned by the API.</returns>
    public async Task<DescribeExecutionResponse> DescribeExecutionAsync(string
executionArn)
    {
        var response = await _amazonStepFunctions.DescribeExecutionAsync(new
DescribeExecutionRequest { ExecutionArn = executionArn });
        return response;
    }
```

- Para obter detalhes da API, consulte DescribeExecutiona Referência AWS SDK for .NET da API.

Obter dados de tarefas para uma atividade

O exemplo de código a seguir mostra como obter dados de tarefa para uma atividade de Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a task with the specified Step Functions activity
    /// with the specified Amazon Resource Name (ARN).
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the Step Functions activity.</param>
    /// <param name="workerName">The name of the Step Functions worker.</param>
    /// <returns>The response from the Step Functions activity.</returns>
    public async Task<GetActivityTaskResponse> GetActivityTaskAsync(string
activityArn, string workerName)
    {
        var response = await _amazonStepFunctions.GetActivityTaskAsync(new
GetActivityTaskRequest
        { ActivityArn = activityArn, WorkerName = workerName });
        return response;
    }
```

- Para obter detalhes da API, consulte GetActivityTaska Referência AWS SDK for .NET da API.

Listar atividades

O exemplo de código a seguir mostra como listar atividades do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List the Step Functions activities for the current account.
    /// </summary>
    /// <returns>A list of ActivityListItems.</returns>
    public async Task<List<ActivityListItem>> ListActivitiesAsync()
    {
        var request = new ListActivitiesRequest();
        var activities = new List<ActivityListItem>();
```

```
        do
        {
            var response = await _amazonStepFunctions.ListActivitiesAsync(request);

            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }

            activities.AddRange(response.Activities);
        }
        while (request.NextToken is not null);

        return activities;
    }
```

- Para obter detalhes da API, consulte ListActivitiesa Referência AWS SDK for .NET da API.

Listar execuções de máquinas de estado

O exemplo de código a seguir mostra como listar execuções de máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve information about executions of a Step Functions
    /// state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>A list of ExecutionListItem objects.</returns>
```

```
    public async Task<List<ExecutionListItem>> ListExecutionsAsync(string
stateMachineArn)
    {
        var executions = new List<ExecutionListItem>();
        ListExecutionsResponse response;
        var request = new ListExecutionsRequest { StateMachineArn =
stateMachineArn };

        do
        {
            response = await _amazonStepFunctions.ListExecutionsAsync(request);
            executions.AddRange(response.Executions);
            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }
        } while (response.NextToken is not null);

        return executions;
    }
```

- Para obter detalhes da API, consulte ListExecutionsa Referência AWS SDK for .NET da API.

Listar máquinas de estado

O exemplo de código a seguir mostra como listar estado de máquinas do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Retrieve a list of Step Functions state machines.
    /// </summary>
    /// <returns>A list of StateMachineListItem objects.</returns>
```

```
    public async Task<List<StateMachineListItem>> ListStateMachinesAsync()
    {
        var stateMachines = new List<StateMachineListItem>();
        var listStateMachinesPaginator =
            _amazonStepFunctions.Paginators.ListStateMachines(new
 ListStateMachinesRequest());

        await foreach (var response in listStateMachinesPaginator.Responses)
        {
            stateMachines.AddRange(response.StateMachines);
        }

        return stateMachines;
    }
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for .NET da API.

Enviar uma resposta bem-sucedida para uma tarefa

O exemplo de código a seguir mostra como enviar uma resposta de sucesso para uma tarefa de Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Indicate that the Step Functions task, indicated by the
    /// task token, has completed successfully.
    /// </summary>
    /// <param name="taskToken">Identifies the task.</param>
    /// <param name="taskResponse">The response received from executing the task.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
```

```
    public async Task<bool> SendTaskSuccessAsync(string taskToken, string
taskResponse)
    {
        var response = await _amazonStepFunctions.SendTaskSuccessAsync(new
SendTaskSuccessRequest
        { TaskToken = taskToken, Output = taskResponse });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte SendTaskSuccessa Referência AWS SDK for .NET da API.

Iniciar execução de máquina de estado

O exemplo de código a seguir mostra como iniciar uma execução de máquina de estado do Step Functions.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start execution of an AWS Step Functions state machine.
    /// </summary>
    /// <param name="executionName">The name to use for the execution.</param>
    /// <param name="executionJson">The JSON string to pass for execution.</param>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>The Amazon Resource Name (ARN) of the AWS Step Functions
    /// execution.</returns>
    public async Task<string> StartExecutionAsync(string executionJson, string
stateMachineArn)
    {
        var executionRequest = new StartExecutionRequest
```

```
        {
            Input = executionJson,
            StateMachineArn = stateMachineArn
        };

        var response = await
_amazonStepFunctions.StartExecutionAsync(executionRequest);
        return response.ExecutionArn;
    }
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for .NET da API.

Cenários

Começar a usar máquinas de estado

O código de exemplo a seguir mostra como:

- Criar uma atividade.
- Criar uma máquina de estado a partir de uma definição da Amazon States Language que contenha a atividade criada anteriormente como uma etapa.
- Executar a máquina de estado e responder à atividade com entrada do usuário.
- Obter o status e a saída finais após a conclusão da execução e, em seguida, limpar os recursos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
global using System.Text.Json;
global using Amazon.StepFunctions;
global using Microsoft.Extensions.Configuration;
global using Microsoft.Extensions.DependencyInjection;
```

```
global using Microsoft.Extensions.Hosting;
global using Microsoft.Extensions.Logging;
global using Microsoft.Extensions.Logging.Console;
global using Microsoft.Extensions.Logging.Debug;
global using StepFunctionsActions;
global using LogLevel = Microsoft.Extensions.Logging.LogLevel;



using Amazon.IdentityManagement;
using Amazon.IdentityManagement.Model;
using Amazon.StepFunctions.Model;

namespace StepFunctionsBasics;

public class StepFunctionsBasics
{
    private static ILogger _logger = null!;
    private static IConfigurationRoot _configuration = null!;
    private static IAmazonIdentityManagementService _iamService = null!;

    static async Task Main(string[] args)
    {
        // Set up dependency injection for AWS Step Functions.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureLogging(logging =>
                logging.AddFilter("System", LogLevel.Debug)
                    .AddFilter<DebugLoggerProvider>("Microsoft",
 LogLevel.Information)
                    .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonStepFunctions>()
                    .AddAWSService<IAmazonIdentityManagementService>()
                    .AddTransient<StepFunctionsWrapper>()
            )
            .Build();

        _logger = LoggerFactory.Create(builder => { builder.AddConsole(); })
            .CreateLogger<StepFunctionsBasics>();

        // Load configuration settings.
        _configuration = new ConfigurationBuilder()
            .SetBasePath(Directory.GetCurrentDirectory())
            .AddJsonFile("settings.json") // Load test settings from .json file.
```

```
            .AddJsonFile("settings.local.json",
                true) // Optionally load local settings.
            .Build();

        var activityName = _configuration["ActivityName"];
        var stateMachineName = _configuration["StateMachineName"];

        var roleName = _configuration["RoleName"];
        var repoBaseDir = _configuration["RepoBaseDir"];
        var jsonFilePath = _configuration["JsonFilePath"];
        var jsonFileName = _configuration["JsonFileName"];

        var uiMethods = new UiMethods();
        var stepFunctionsWrapper =
 host.Services.GetRequiredService<StepFunctionsWrapper>();

        _iamService =
 host.Services.GetRequiredService<IAmazonIdentityManagementService>();

        // Load definition for the state machine from a JSON file.
        var stateDefinitionJson = File.ReadAllText($"{repoBaseDir}{jsonFilePath}
{jsonFileName}");

        Console.Clear();
        uiMethods.DisplayOverview();
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("Create activity");
        Console.WriteLine("Let's start by creating an activity.");
        string activityArn;
        string stateMachineArn;

        // Check to see if the activity already exists.
        var activityList = await stepFunctionsWrapper.ListActivitiesAsync();
        var existingActivity = activityList.FirstOrDefault(activity => activity.Name
 == activityName);
        if (existingActivity is not null)
        {
            activityArn = existingActivity.ActivityArn;
            Console.WriteLine($"Activity, {activityName}, already exists.");
        }
        else
        {
            activityArn = await stepFunctionsWrapper.CreateActivity(activityName);
```

```
        }

        // Swap the placeholder in the JSON file with the Amazon Resource Name (ARN)
        // of the recently created activity.
        var stateDefinition =
stateDefinitionJson.Replace("{{DOC_EXAMPLE_ACTIVITY_ARN}}", activityArn);

        uiMethods.DisplayTitle("Create state machine");
        Console.WriteLine("Now we'll create a state machine.");

        // Find or create an IAM role that can be assumed by Step Functions.
        var role = await GetOrCreateStateMachineRole(roleName);

        // See if the state machine already exists.
        var stateMachineList = await stepFunctionsWrapper.ListStateMachinesAsync();
        var existingStateMachine =
            stateMachineList.FirstOrDefault(stateMachine => stateMachine.Name ==
stateMachineName);
        if (existingStateMachine is not null)
        {
            Console.WriteLine($"State machine, {stateMachineName}, already
exists.");
            stateMachineArn = existingStateMachine.StateMachineArn;
        }
        else
        {
            // Create the state machine.
            stateMachineArn =
                await stepFunctionsWrapper.CreateStateMachine(stateMachineName,
stateDefinition, role.Arn);
            uiMethods.PressEnter();
        }

        Console.WriteLine("The state machine has been created.");
        var describeStateMachineResponse = await
stepFunctionsWrapper.DescribeStateMachineAsync(stateMachineArn);


Console.WriteLine($"{describeStateMachineResponse.Name}\t{describeStateMachineResponse.Stat
        Console.WriteLine($"Current status: {describeStateMachineResponse.Status}");
        Console.WriteLine($"Amazon Resource Name (ARN) of the role assumed by the
state machine: {describeStateMachineResponse.RoleArn}");

        var userName = string.Empty;
```

```
        Console.Write("Before we start the state machine, tell me what should
ChatSFN call you? ");
        userName = Console.ReadLine();

        // Keep asking until the user enters a string value.
        while (string.IsNullOrEmpty(userName))
        {
            Console.Write("Enter your name: ");
            userName = Console.ReadLine();
        }

        var executionJson = @"{""name"": """ + userName + @"""}";

        // Start the state machine execution.
        Console.WriteLine("Now we'll start execution of the state machine.");
        var executionArn = await
stepFunctionsWrapper.StartExecutionAsync(executionJson, stateMachineArn);
        Console.WriteLine("State machine started.");

        Console.WriteLine($"Thank you, {userName}. Now let's get started...");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("ChatSFN");

        var isDone = false;
        var response = new GetActivityTaskResponse();
        var taskToken = string.Empty;
        var userChoice = string.Empty;

        while (!isDone)
        {
            response = await stepFunctionsWrapper.GetActivityTaskAsync(activityArn,
"MvpWorker");
            taskToken = response.TaskToken;

            // Parse the returned JSON string.
            var taskJsonResponse = JsonDocument.Parse(response.Input);
            var taskJsonObject = taskJsonResponse.RootElement;
            var message = taskJsonObject.GetProperty("message").GetString();
            var actions =
taskJsonObject.GetProperty("actions").EnumerateArray().Select(x =>
x.ToString()).ToList();
            Console.WriteLine($"\n{message}\n");
```

```
            // Prompt the user for another choice.
            Console.WriteLine("ChatSFN: What would you like me to do?");
            actions.ForEach(action => Console.WriteLine($"\t{action}"));
            Console.Write($"\n{userName}, tell me your choice: ");
            userChoice = Console.ReadLine();
            if (userChoice?.ToLower() == "done")
            {
                isDone = true;
            }

            Console.WriteLine($"You have selected: {userChoice}");
            var jsonResponse = @"{""action"": """ + userChoice + @"""}";

            await stepFunctionsWrapper.SendTaskSuccessAsync(taskToken,
jsonResponse);
        }

        await stepFunctionsWrapper.StopExecution(executionArn);
        Console.WriteLine("Now we will wait for the execution to stop.");
        DescribeExecutionResponse executionResponse;
        do
        {
            executionResponse = await
stepFunctionsWrapper.DescribeExecutionAsync(executionArn);
        } while (executionResponse.Status == ExecutionStatus.RUNNING);

        Console.WriteLine("State machine stopped.");
        uiMethods.PressEnter();

        uiMethods.DisplayTitle("State machine executions");
        Console.WriteLine("Now let's take a look at the execution values for the
state machine.");

        // List the executions.
        var executions = await
stepFunctionsWrapper.ListExecutionsAsync(stateMachineArn);

        uiMethods.DisplayTitle("Step function execution values");
        executions.ForEach(execution =>
        {
            Console.WriteLine($"{execution.Name}\t{execution.StartDate} to
{execution.StopDate}");
        });
```

```
        uiMethods.PressEnter();

        // Now delete the state machine and the activity.
        uiMethods.DisplayTitle("Clean up resources");
        Console.WriteLine("Deleting the state machine...");

        await stepFunctionsWrapper.DeleteStateMachine(stateMachineArn);
        Console.WriteLine("State machine deleted.");

        Console.WriteLine("Deleting the activity...");
        await stepFunctionsWrapper.DeleteActivity(activityArn);
        Console.WriteLine("Activity deleted.");

        Console.WriteLine("The Amazon Step Functions scenario is now complete.");
    }

    static async Task<Role> GetOrCreateStateMachineRole(string roleName)
    {
        // Define the policy document for the role.
        var stateMachineRolePolicy = @"{
         ""Version"": ""2012-10-17"",
        ""Statement"": [{
            ""Sid"": """",
            ""Effect"": ""Allow"",
            ""Principal"": {
                ""Service"": ""states.amazonaws.com""},
            ""Action"": ""sts:AssumeRole""}]}";

        var role = new Role();
        var roleExists = false;

        try
        {
            var getRoleResponse = await _iamService.GetRoleAsync(new GetRoleRequest
{ RoleName = roleName });
            roleExists = true;
            role = getRoleResponse.Role;
        }
        catch (NoSuchEntityException)
        {
            // The role doesn't exist. Create it.
            Console.WriteLine($"Role, {roleName} doesn't exist. Creating it...");
        }
```

```
        if (!roleExists)
        {
            var request = new CreateRoleRequest
            {
                RoleName = roleName,
                AssumeRolePolicyDocument = stateMachineRolePolicy,
            };

            var createRoleResponse = await _iamService.CreateRoleAsync(request);
            role = createRoleResponse.Role;
        }

        return role;
    }
}


namespace StepFunctionsBasics;

/// <summary>
/// Some useful methods to make screen display easier.
/// </summary>
public class UiMethods
{
    private readonly string _sepBar = new('-', Console.WindowWidth);

    /// <summary>
    /// Show information about the scenario.
    /// </summary>
    public void DisplayOverview()
    {
        Console.Clear();
        DisplayTitle("Welcome to the AWS Step Functions Demo");

        Console.WriteLine("This example application will do the following:");
        Console.WriteLine("\t 1. Create an activity.");
        Console.WriteLine("\t 2. Create a state machine.");
        Console.WriteLine("\t 3. Start an execution.");
        Console.WriteLine("\t 4. Run the worker, then stop it.");
        Console.WriteLine("\t 5. List executions.");
        Console.WriteLine("\t 6. Clean up the resources created for the example.");
    }

    /// <summary>
```

```
    /// Display a message and wait until the user presses enter.
    /// </summary>
    public void PressEnter()
    {
        Console.Write("\nPress <Enter> to continue.");
        _ = Console.ReadLine();
    }

    /// <summary>
    /// Pad a string with spaces to center it on the console display.
    /// </summary>
    /// <param name="strToCenter"></param>
    /// <returns></returns>
    private string CenterString(string strToCenter)
    {
        var padAmount = (Console.WindowWidth - strToCenter.Length) / 2;
        var leftPad = new string(' ', padAmount);
        return $"{leftPad}{strToCenter}";
    }

    /// <summary>
    /// Display a line of hyphens, the centered text of the title, and another
    /// line of hyphens.
    /// </summary>
    /// <param name="strTitle">The string to be displayed.</param>
    public void DisplayTitle(string strTitle)
    {
        Console.WriteLine(_sepBar);
        Console.WriteLine(CenterString(strTitle));
        Console.WriteLine(_sepBar);
    }
}
```

Defina uma classe que envolva as ações de atividade e máquina de estado.

```
namespace StepFunctionsActions;

using Amazon.StepFunctions;
using Amazon.StepFunctions.Model;
```

```
/// <summary>
/// Wrapper that performs AWS Step Functions actions.
/// </summary>
public class StepFunctionsWrapper
{
    private readonly IAmazonStepFunctions _amazonStepFunctions;

    /// <summary>
    /// The constructor for the StepFunctionsWrapper. Initializes the
    /// client object passed to it.
    /// </summary>
    /// <param name="amazonStepFunctions">An initialized Step Functions client
 object.</param>
    public StepFunctionsWrapper(IAmazonStepFunctions amazonStepFunctions)
    {
        _amazonStepFunctions = amazonStepFunctions;
    }

    /// <summary>
    /// Create a Step Functions activity using the supplied name.
    /// </summary>
    /// <param name="activityName">The name for the new Step Functions activity.</
param>
    /// <returns>The Amazon Resource Name (ARN) for the new activity.</returns>
    public async Task<string> CreateActivity(string activityName)
    {
        var response = await _amazonStepFunctions.CreateActivityAsync(new
 CreateActivityRequest { Name = activityName });
        return response.ActivityArn;
    }


    /// <summary>
    /// Create a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineName">Name for the new Step Functions state
    /// machine.</param>
    /// <param name="definition">A JSON string that defines the Step Functions
    /// state machine.</param>
    /// <param name="roleArn">The Amazon Resource Name (ARN) of the role.</param>
    /// <returns></returns>
    public async Task<string> CreateStateMachine(string stateMachineName, string
 definition, string roleArn)
    {
```

```
        var request = new CreateStateMachineRequest
        {
            Name = stateMachineName,
            Definition = definition,
            RoleArn = roleArn
        };

        var response =
            await _amazonStepFunctions.CreateStateMachineAsync(request);
        return response.StateMachineArn;
    }


    /// <summary>
    /// Delete a Step Machine activity.
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the activity.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteActivity(string activityArn)
    {
        var response = await _amazonStepFunctions.DeleteActivityAsync(new
DeleteActivityRequest { ActivityArn = activityArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Delete a Step Functions state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// state machine.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> DeleteStateMachine(string stateMachineArn)
    {
        var response = await _amazonStepFunctions.DeleteStateMachineAsync(new
DeleteStateMachineRequest
        { StateMachineArn = stateMachineArn });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Retrieve information about the specified Step Functions execution.
```

```
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of the
    /// Step Functions execution.</param>
    /// <returns>The API response returned by the API.</returns>
    public async Task<DescribeExecutionResponse> DescribeExecutionAsync(string
 executionArn)
    {
        var response = await _amazonStepFunctions.DescribeExecutionAsync(new
 DescribeExecutionRequest { ExecutionArn = executionArn });
        return response;
    }


    /// <summary>
    /// Retrieve information about the specified Step Functions state machine.
    /// </summary>
    /// <param name="StateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine to retrieve.</param>
    /// <returns>Information about the specified Step Functions state machine.</
returns>
    public async Task<DescribeStateMachineResponse> DescribeStateMachineAsync(string
 StateMachineArn)
    {
        var response = await _amazonStepFunctions.DescribeStateMachineAsync(new
 DescribeStateMachineRequest { StateMachineArn = StateMachineArn });
        return response;
    }


    /// <summary>
    /// Retrieve a task with the specified Step Functions activity
    /// with the specified Amazon Resource Name (ARN).
    /// </summary>
    /// <param name="activityArn">The Amazon Resource Name (ARN) of
    /// the Step Functions activity.</param>
    /// <param name="workerName">The name of the Step Functions worker.</param>
    /// <returns>The response from the Step Functions activity.</returns>
    public async Task<GetActivityTaskResponse> GetActivityTaskAsync(string
 activityArn, string workerName)
    {
        var response = await _amazonStepFunctions.GetActivityTaskAsync(new
 GetActivityTaskRequest
        { ActivityArn = activityArn, WorkerName = workerName });
        return response;
```

```
    }


    /// <summary>
    /// List the Step Functions activities for the current account.
    /// </summary>
    /// <returns>A list of ActivityListItems.</returns>
    public async Task<List<ActivityListItem>> ListActivitiesAsync()
    {
        var request = new ListActivitiesRequest();
        var activities = new List<ActivityListItem>();

        do
        {
            var response = await _amazonStepFunctions.ListActivitiesAsync(request);

            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }

            activities.AddRange(response.Activities);
        }
        while (request.NextToken is not null);

        return activities;
    }


    /// <summary>
    /// Retrieve information about executions of a Step Functions
    /// state machine.
    /// </summary>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>A list of ExecutionListItem objects.</returns>
    public async Task<List<ExecutionListItem>> ListExecutionsAsync(string
stateMachineArn)
    {
        var executions = new List<ExecutionListItem>();
        ListExecutionsResponse response;
        var request = new ListExecutionsRequest { StateMachineArn =
stateMachineArn };
```

```
        do
        {
            response = await _amazonStepFunctions.ListExecutionsAsync(request);
            executions.AddRange(response.Executions);
            if (response.NextToken is not null)
            {
                request.NextToken = response.NextToken;
            }
        } while (response.NextToken is not null);

        return executions;
    }


    /// <summary>
    /// Retrieve a list of Step Functions state machines.
    /// </summary>
    /// <returns>A list of StateMachineListItem objects.</returns>
    public async Task<List<StateMachineListItem>> ListStateMachinesAsync()
    {
        var stateMachines = new List<StateMachineListItem>();
        var listStateMachinesPaginator =
            _amazonStepFunctions.Paginators.ListStateMachines(new
 ListStateMachinesRequest());

        await foreach (var response in listStateMachinesPaginator.Responses)
        {
            stateMachines.AddRange(response.StateMachines);
        }

        return stateMachines;
    }


    /// <summary>
    /// Indicate that the Step Functions task, indicated by the
    /// task token, has completed successfully.
    /// </summary>
    /// <param name="taskToken">Identifies the task.</param>
    /// <param name="taskResponse">The response received from executing the task.</
param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> SendTaskSuccessAsync(string taskToken, string
 taskResponse)
```

```
    {
        var response = await _amazonStepFunctions.SendTaskSuccessAsync(new
SendTaskSuccessRequest
        { TaskToken = taskToken, Output = taskResponse });

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


    /// <summary>
    /// Start execution of an AWS Step Functions state machine.
    /// </summary>
    /// <param name="executionName">The name to use for the execution.</param>
    /// <param name="executionJson">The JSON string to pass for execution.</param>
    /// <param name="stateMachineArn">The Amazon Resource Name (ARN) of the
    /// Step Functions state machine.</param>
    /// <returns>The Amazon Resource Name (ARN) of the AWS Step Functions
    /// execution.</returns>
    public async Task<string> StartExecutionAsync(string executionJson, string
stateMachineArn)
    {
        var executionRequest = new StartExecutionRequest
        {
            Input = executionJson,
            StateMachineArn = stateMachineArn
        };

        var response = await
_amazonStepFunctions.StartExecutionAsync(executionRequest);
        return response.ExecutionArn;
    }


    /// <summary>
    /// Stop execution of a Step Functions workflow.
    /// </summary>
    /// <param name="executionArn">The Amazon Resource Name (ARN) of
    /// the Step Functions execution to stop.</param>
    /// <returns>A Boolean value indicating the success of the action.</returns>
    public async Task<bool> StopExecution(string executionArn)
    {
        var response =
            await _amazonStepFunctions.StopExecutionAsync(new StopExecutionRequest
{ ExecutionArn = executionArn });
```

```
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }


}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution
  - DescribeStateMachine
  - GetActivityTask
  - ListActivities
  - ListStateMachines
  - SendTaskSuccess
  - StartExecution
  - StopExecution

Exemplos de AWS STS usando AWS SDK for .NET

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon;
using Amazon.SecurityToken;
using Amazon.SecurityToken.Model;

namespace AssumeRoleExample
{
    class AssumeRole
    {
        /// <summary>
        /// This example shows how to use the AWS Security Token
        /// Service (AWS STS) to assume an IAM role.
        ///
        /// NOTE: It is important that the role that will be assumed has a
        /// trust relationship with the account that will assume the role.
        ///
        /// Before you run the example, you need to create the role you want to
        /// assume and have it trust the IAM account that will assume that role.
        ///
        /// See https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_create.html
        /// for help in working with roles.
        /// </summary>
```

```
        private static readonly RegionEndpoint REGION = RegionEndpoint.USWest2;

        static async Task Main()
        {
            // Create the SecurityToken client and then display the identity of the
            // default user.
            var roleArnToAssume = "arn:aws:iam::123456789012:role/testAssumeRole";

            var client = new
 Amazon.SecurityToken.AmazonSecurityTokenServiceClient(REGION);

            // Get and display the information about the identity of the default
 user.
            var callerIdRequest = new GetCallerIdentityRequest();
            var caller = await client.GetCallerIdentityAsync(callerIdRequest);
            Console.WriteLine($"Original Caller: {caller.Arn}");

            // Create the request to use with the AssumeRoleAsync call.
            var assumeRoleReq = new AssumeRoleRequest()
            {
                DurationSeconds = 1600,
                RoleSessionName = "Session1",
                RoleArn = roleArnToAssume
            };

            var assumeRoleRes = await client.AssumeRoleAsync(assumeRoleReq);

            // Now create a new client based on the credentials of the caller
 assuming the role.
            var client2 = new AmazonSecurityTokenServiceClient(credentials:
 assumeRoleRes.Credentials);

            // Get and display information about the caller that has assumed the
 defined role.
            var caller2 = await client2.GetCallerIdentityAsync(callerIdRequest);
            Console.WriteLine($"AssumedRole Caller: {caller2.Arn}");
        }
    }
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for .NET da API.

Exemplos de AWS Support usando AWS SDK for .NET

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com AWS Support.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using Amazon.AWSSupport;
using Microsoft.Extensions.DependencyInjection;
using Microsoft.Extensions.Hosting;

public static class HelloSupport
{
    static async Task Main(string[] args)
    {
        // Use the AWS .NET Core Setup package to set up dependency injection for
 the AWS Support service.
        // Use your AWS profile name, or leave it blank to use the default profile.
```

```
        // You must have one of the following AWS Support plans: Business,
 Enterprise On-Ramp, or Enterprise. Otherwise, an exception will be thrown.
        using var host = Host.CreateDefaultBuilder(args)
            .ConfigureServices((_, services) =>
                services.AddAWSService<IAmazonAWSSupport>()
            ).Build();

        // Now the client is available for injection.
        var supportClient = host.Services.GetRequiredService<IAmazonAWSSupport>();

        // You can use await and any of the async methods to get a response.
        var response = await supportClient.DescribeServicesAsync();
        Console.WriteLine($"\tHello AWS Support! There are {response.Services.Count}
 services available.");
    }
}
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for .NET da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma comunicação a um caso

O exemplo de código a seguir mostra como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add communication to a case, including optional attachment set ID and CC
email addresses.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <param name="body">Body text of the communication.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set.</param>
    /// <param name="ccEmailAddresses">Optional list of CC email addresses.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> AddCommunicationToCase(string caseId, string body,
        string? attachmentSetId = null, List<string>? ccEmailAddresses = null)
    {
        var response = await _amazonSupport.AddCommunicationToCaseAsync(
            new AddCommunicationToCaseRequest()
            {
                CaseId = caseId,
                CommunicationBody = body,
                AttachmentSetId = attachmentSetId,
                CcEmailAddresses = ccEmailAddresses
            });
        return response.Result;
    }
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for .NET da API.

Adicionar um anexo a um conjunto

O exemplo de código a seguir mostra como adicionar um anexo do AWS Support a um conjunto de anexos.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Add an attachment to a set, or create a new attachment set if one does not
exist.
    /// </summary>
    /// <param name="data">The data for the attachment.</param>
    /// <param name="fileName">The file name for the attachment.</param>
    /// <param name="attachmentSetId">Optional setId for the attachment. Creates a
new attachment set if empty.</param>
    /// <returns>The setId of the attachment.</returns>
    public async Task<string> AddAttachmentToSet(MemoryStream data, string fileName,
string? attachmentSetId = null)
    {
        var response = await _amazonSupport.AddAttachmentsToSetAsync(
            new AddAttachmentsToSetRequest
            {
                AttachmentSetId = attachmentSetId,
                Attachments = new List<Attachment>
                {
                    new Attachment
                    {
                        Data = data,
                        FileName = fileName
                    }
                }
            });
        return response.AttachmentSetId;
    }
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for .NET da API.

Criar um caso

O exemplo de código a seguir mostra como criar um novo caso do AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /// <summary>
   /// Create a new support case.
   /// </summary>
   /// <param name="serviceCode">Service code for the new case.</param>
   /// <param name="categoryCode">Category for the new case.</param>
   /// <param name="severityCode">Severity code for the new case.</param>
   /// <param name="subject">Subject of the new case.</param>
   /// <param name="body">Body text of the new case.</param>
   /// <param name="language">Optional language support for your case.
   /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
   /// <param name="attachmentSetId">Optional Id for an attachment set for the new
case.</param>
   /// <param name="issueType">Optional issue type for the new case. Options are
"customer-service" or "technical".</param>
   /// <returns>The caseId of the new support case.</returns>
   public async Task<string> CreateCase(string serviceCode, string categoryCode,
string severityCode, string subject,
       string body, string language = "en", string? attachmentSetId = null, string
issueType = "customer-service")
   {
       var response = await _amazonSupport.CreateCaseAsync(
           new CreateCaseRequest()
           {
               ServiceCode = serviceCode,
               CategoryCode = categoryCode,
               SeverityCode = severityCode,
               Subject = subject,
               Language = language,
               AttachmentSetId = attachmentSetId,
               IssueType = issueType,
               CommunicationBody = body
           });
       return response.CaseId;
```

```
    }
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for .NET da API.

Descrever um anexo

O exemplo de código a seguir mostra como descrever um anexo para um caso do AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get description of a specific attachment.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment, usually fetched by
describing the communications of a case.</param>
    /// <returns>The attachment object.</returns>
    public async Task<Attachment> DescribeAttachment(string attachmentId)
    {
        var response = await _amazonSupport.DescribeAttachmentAsync(
            new DescribeAttachmentRequest()
            {
                AttachmentId = attachmentId
            });
        return response.Attachment;
    }
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for .NET da API.

Descrever casos

O exemplo de código a seguir mostra como descrever casos do AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get case details for a list of case ids, optionally with date filters.
    /// </summary>
    /// <param name="caseIds">The list of case IDs.</param>
    /// <param name="displayId">Optional display ID.</param>
    /// <param name="includeCommunication">True to include communication. Defaults
 to true.</param>
    /// <param name="includeResolvedCases">True to include resolved cases. Defaults
 to false.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>A list of CaseDetails.</returns>
    public async Task<List<CaseDetails>> DescribeCases(List<string> caseIds, string?
 displayId = null, bool includeCommunication = true,
        bool includeResolvedCases = false, DateTime? afterTime = null, DateTime?
 beforeTime = null,
        string language = "en")
    {
        var results = new List<CaseDetails>();
        var paginateCases = _amazonSupport.Paginators.DescribeCases(
            new DescribeCasesRequest()
            {
                CaseIdList = caseIds,
                DisplayId = displayId,
                IncludeCommunications = includeCommunication,
                IncludeResolvedCases = includeResolvedCases,
```

```
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s"),
                Language = language
            });
        // Get the entire list using the paginator.
        await foreach (var cases in paginateCases.Cases)
        {
            results.Add(cases);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for .NET da API.

Descrever as comunicações

O exemplo de código a seguir mostra como descrever as comunicações do AWS Support para um caso.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Describe the communications for a case, optionally with a date filter.
    /// </summary>
    /// <param name="caseId">The ID of the support case.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <returns>The list of communications for the case.</returns>
    public async Task<List<Communication>> DescribeCommunications(string caseId,
 DateTime? afterTime = null, DateTime? beforeTime = null)
```

```
    {
        var results = new List<Communication>();
        var paginateCommunications =
_amazonSupport.Paginators.DescribeCommunications(
            new DescribeCommunicationsRequest()
            {
                CaseId = caseId,
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s")
            });
        // Get the entire list using the paginator.
        await foreach (var communications in paginateCommunications.Communications)
        {
            results.Add(communications);
        }
        return results;
    }
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for .NET da API.

Descrever os serviços

O exemplo de código a seguir mostra como descrever a lista de serviços do AWS.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the descriptions of AWS services.
    /// </summary>
    /// <param name="name">Optional language for services.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
```

```
    /// <returns>The list of AWS service descriptions.</returns>
    public async Task<List<Service>> DescribeServices(string language = "en")
    {
        var response = await _amazonSupport.DescribeServicesAsync(
            new DescribeServicesRequest()
            {
                Language = language
            });
        return response.Services;
    }
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for .NET da API.

Descrever os níveis de gravidade

O exemplo de código a seguir mostra como descrever os níveis de gravidade do AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get the descriptions of support severity levels.
    /// </summary>
    /// <param name="name">Optional language for severity levels.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of support severity levels.</returns>
    public async Task<List<SeverityLevel>> DescribeSeverityLevels(string language =
"en")
    {
        var response = await _amazonSupport.DescribeSeverityLevelsAsync(
            new DescribeSeverityLevelsRequest()
            {
                Language = language
```

```
            });
        return response.SeverityLevels;
    }
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for .NET da API.

Resolver caso

O exemplo de código a seguir mostra como resolver um caso do AWS Support.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Resolve a support case by caseId.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <returns>The final status of the case after resolving.</returns>
    public async Task<string> ResolveCase(string caseId)
    {
        var response = await _amazonSupport.ResolveCaseAsync(
            new ResolveCaseRequest()
            {
                CaseId = caseId
            });
        return response.FinalCaseStatus;
    }
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for .NET da API.

Cenários

Conceitos básicos de casos

O código de exemplo a seguir mostra como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.
- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
/// <summary>
/// Hello AWS Support example.
/// </summary>
public static class SupportCaseScenario
{
    /*
    Before running this .NET code example, set up your development environment,
 including your credentials.
    To use the AWS Support API, you must have one of the following AWS Support
 plans: Business, Enterprise On-Ramp, or Enterprise.

    This .NET example performs the following tasks:
    1.  Get and display services. Select a service from the list.
    2.  Select a category from the selected service.
    3.  Get and display severity levels and select a severity level from the list.
```

```
   4.  Create a support case using the selected service, category, and severity
level.
   5.  Get and display a list of open support cases for the current day.
   6.  Create an attachment set with a sample text file to add to the case.
   7.  Add a communication with the attachment to the support case.
   8.  List the communications of the support case.
   9.  Describe the attachment set.
   10. Resolve the support case.
   11. Get a list of resolved cases for the current day.
  */

   private static SupportWrapper _supportWrapper = null!;

   static async Task Main(string[] args)
   {
       // Set up dependency injection for the AWS Support service.
       // Use your AWS profile name, or leave it blank to use the default profile.
       using var host = Host.CreateDefaultBuilder(args)
           .ConfigureLogging(logging =>
               logging.AddFilter("System", LogLevel.Debug)
                   .AddFilter<DebugLoggerProvider>("Microsoft",
LogLevel.Information)
                   .AddFilter<ConsoleLoggerProvider>("Microsoft", LogLevel.Trace))
           .ConfigureServices((_, services) =>
               services.AddAWSService<IAmazonAWSSupport>(new AWSOptions() { Profile
= "default" })
                   .AddTransient<SupportWrapper>()
           )
           .Build();

       var logger = LoggerFactory.Create(builder =>
       {
           builder.AddConsole();
       }).CreateLogger(typeof(SupportCaseScenario));

       _supportWrapper = host.Services.GetRequiredService<SupportWrapper>();

       Console.WriteLine(new string('-', 80));
       Console.WriteLine("Welcome to the AWS Support case example scenario.");
       Console.WriteLine(new string('-', 80));

       try
       {
           var apiSupported = await _supportWrapper.VerifySubscription();
```

```
            if (!apiSupported)
            {
                logger.LogError("You must have a Business, Enterprise On-Ramp, or
Enterprise Support " +
                                "plan to use the AWS Support API. \n\tPlease
upgrade your subscription to run these examples.");
                return;
            }

            var service = await DisplayAndSelectServices();

            var category = DisplayAndSelectCategories(service);

            var severityLevel = await DisplayAndSelectSeverity();

            var caseId = await CreateSupportCase(service, category, severityLevel);

            await DescribeTodayOpenCases();

            var attachmentSetId = await CreateAttachmentSet();

            await AddCommunicationToCase(attachmentSetId, caseId);

            var attachmentId = await ListCommunicationsForCase(caseId);

            await DescribeCaseAttachment(attachmentId);

            await ResolveCase(caseId);

            await DescribeTodayResolvedCases();

            Console.WriteLine(new string('-', 80));
            Console.WriteLine("AWS Support case example scenario complete.");
            Console.WriteLine(new string('-', 80));
        }
        catch (Exception ex)
        {
            logger.LogError(ex, "There was a problem executing the scenario.");
        }
    }

    /// <summary>
    /// List some available services from AWS Support, and select a service for the
example.
```

```
    /// </summary>
    /// <returns>The selected service.</returns>
    private static async Task<Service> DisplayAndSelectServices()
    {
        Console.WriteLine(new string('-', 80));
        var services = await _supportWrapper.DescribeServices();
        Console.WriteLine($"AWS Support client returned {services.Count}
services.");

        Console.WriteLine($"1. Displaying first 10 services:");
        for (int i = 0; i < 10 && i < services.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {services[i].Name}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > services.Count)
        {
            Console.WriteLine(
                "Select an example support service by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        Console.WriteLine(new string('-', 80));

        return services[choiceNumber - 1];
    }

    /// <summary>
    /// List the available categories for a service and select a category for the
example.
    /// </summary>
    /// <param name="service">Service to use for displaying categories.</param>
    /// <returns>The selected category.</returns>
    private static Category DisplayAndSelectCategories(Service service)
    {
        Console.WriteLine(new string('-', 80));

        Console.WriteLine($"2. Available support categories for Service
\"{service.Name}\":");
        for (int i = 0; i < service.Categories.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {service.Categories[i].Name}");
```

```
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > service.Categories.Count)
        {
            Console.WriteLine(
                "Select an example support category by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }

        Console.WriteLine(new string('-', 80));

        return service.Categories[choiceNumber - 1];
    }

    /// <summary>
    /// List available severity levels from AWS Support, and select a level for the
example.
    /// </summary>
    /// <returns>The selected severity level.</returns>
    private static async Task<SeverityLevel> DisplayAndSelectSeverity()
    {
        Console.WriteLine(new string('-', 80));
        var severityLevels = await _supportWrapper.DescribeSeverityLevels();

        Console.WriteLine($"3. Get and display available severity levels:");
        for (int i = 0; i < 10 && i < severityLevels.Count; i++)
        {
            Console.WriteLine($"\t{i + 1}. {severityLevels[i].Name}");
        }

        var choiceNumber = 0;
        while (choiceNumber < 1 || choiceNumber > severityLevels.Count)
        {
            Console.WriteLine(
                "Select an example severity level by entering a number from the
preceding list:");
            var choice = Console.ReadLine();
            Int32.TryParse(choice, out choiceNumber);
        }
        Console.WriteLine(new string('-', 80));
```

```
        return severityLevels[choiceNumber - 1];
    }

    /// <summary>
    /// Create an example support case.
    /// </summary>
    /// <param name="service">Service to use for the new case.</param>
    /// <param name="category">Category to use for the new case.</param>
    /// <param name="severity">Severity to use for the new case.</param>
    /// <returns>The caseId of the new support case.</returns>
    private static async Task<string> CreateSupportCase(Service service,
        Category category, SeverityLevel severity)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"4. Create an example support case" +
                          $" with the following settings:" +
                          $" \n\tService: {service.Name}, Category: {category.Name}
" +
                          $"and Severity Level: {severity.Name}.");
        var caseId = await _supportWrapper.CreateCase(service.Code, category.Code,
severity.Code,
            "Example case for testing, ignore.", "This is my example support
case.");

        Console.WriteLine($"\tNew case created with ID {caseId}");

        Console.WriteLine(new string('-', 80));

        return caseId;
    }

    /// <summary>
    /// List open cases for the current day.
    /// </summary>
    /// <returns>Async task.</returns>
    private static async Task DescribeTodayOpenCases()
    {
        Console.WriteLine($"5. List the open support cases for the current day.");
        // Describe the cases. If it is empty, try again and allow time for the new
case to appear.
        List<CaseDetails> currentOpenCases = null!;
        while (currentOpenCases == null || currentOpenCases.Count == 0)
        {
            Thread.Sleep(1000);
```

```
            currentOpenCases = await _supportWrapper.DescribeCases(
                new List<string>(),
                null,
                false,
                false,
                DateTime.UtcNow.Date,
                DateTime.UtcNow);
        }

        foreach (var openCase in currentOpenCases)
        {
            Console.WriteLine($"\tCase: {openCase.CaseId} created
{openCase.TimeCreated}");
        }

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Create an attachment set for a support case.
    /// </summary>
    /// <returns>The attachment set id.</returns>
    private static async Task<string> CreateAttachmentSet()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"6. Create an attachment set for a support case.");
        var fileName = "example_attachment.txt";

        // Create the file if it does not already exist.
        if (!File.Exists(fileName))
        {
            await using StreamWriter sw = File.CreateText(fileName);
            await sw.WriteLineAsync(
                "This is a sample file for attachment to a support case.");
        }

        await using var ms = new MemoryStream(await
File.ReadAllBytesAsync(fileName));

        var attachmentSetId = await _supportWrapper.AddAttachmentToSet(
            ms,
            fileName);
```

```
        Console.WriteLine($"\tNew attachment set created with id: \n
\t{attachmentSetId.Substring(0, 65)}...");

        Console.WriteLine(new string('-', 80));

        return attachmentSetId;
    }

    /// <summary>
    /// Add an attachment set and communication to a case.
    /// </summary>
    /// <param name="attachmentSetId">Id of the attachment set.</param>
    /// <param name="caseId">Id of the case to receive the attachment set.</param>
    /// <returns>Async task.</returns>
    private static async Task AddCommunicationToCase(string attachmentSetId, string
 caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"7. Add attachment set and communication to {caseId}.");

        await _supportWrapper.AddCommunicationToCase(
            caseId,
            "This is an example communication added to a support case.",
            attachmentSetId);

        Console.WriteLine($"\tNew attachment set and communication added to
 {caseId}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List the communications for a case.
    /// </summary>
    /// <param name="caseId">Id of the case to describe.</param>
    /// <returns>An attachment id.</returns>
    private static async Task<string> ListCommunicationsForCase(string caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"8. List communications for case {caseId}.");

        var communications = await _supportWrapper.DescribeCommunications(caseId);
        var attachmentId = "";
        foreach (var communication in communications)
```

```
        {
            Console.WriteLine(
                $"\tCommunication created on: {communication.TimeCreated} has
{communication.AttachmentSet.Count} attachments.");
            if (communication.AttachmentSet.Any())
            {
                attachmentId = communication.AttachmentSet.First().AttachmentId;
            }
        }

        Console.WriteLine(new string('-', 80));
        return attachmentId;
    }

    /// <summary>
    /// Describe an attachment by id.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment to describe.</param>
    /// <returns>Async task.</returns>
    private static async Task DescribeCaseAttachment(string attachmentId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"9. Describe the attachment set.");

        var attachment = await _supportWrapper.DescribeAttachment(attachmentId);
        var data = Encoding.ASCII.GetString(attachment.Data.ToArray());
        Console.WriteLine($"\tAttachment includes {attachment.FileName} with data:
\n\t{data}");

        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// Resolve the support case.
    /// </summary>
    /// <param name="caseId">Id of the case to resolve.</param>
    /// <returns>Async task.</returns>
    private static async Task ResolveCase(string caseId)
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"10. Resolve case {caseId}.");

        var status = await _supportWrapper.ResolveCase(caseId);
        Console.WriteLine($"\tCase {caseId} has final status {status}");
```

```
        Console.WriteLine(new string('-', 80));
    }

    /// <summary>
    /// List resolved cases for the current day.
    /// </summary>
    /// <returns>Async Task.</returns>
    private static async Task DescribeTodayResolvedCases()
    {
        Console.WriteLine(new string('-', 80));
        Console.WriteLine($"11. List the resolved support cases for the current
 day.");
        var currentCases = await _supportWrapper.DescribeCases(
            new List<string>(),
            null,
            false,
            true,
            DateTime.UtcNow.Date,
            DateTime.UtcNow);

        foreach (var currentCase in currentCases)
        {
            if (currentCase.Status == "resolved")
            {
                Console.WriteLine(
                    $"\tCase: {currentCase.CaseId}: status {currentCase.Status}");
            }
        }

        Console.WriteLine(new string('-', 80));
    }
}
```

Os métodos de wrapper usados pelo cenário para as ações do AWS Support.

```
/// <summary>
/// Wrapper methods to use AWS Support for working with support cases.
/// </summary>
public class SupportWrapper
{
```

```
    private readonly IAmazonAWSSupport _amazonSupport;
    public SupportWrapper(IAmazonAWSSupport amazonSupport)
    {
        _amazonSupport = amazonSupport;
    }


    /// <summary>
    /// Get the descriptions of AWS services.
    /// </summary>
    /// <param name="name">Optional language for services.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of AWS service descriptions.</returns>
    public async Task<List<Service>> DescribeServices(string language = "en")
    {
        var response = await _amazonSupport.DescribeServicesAsync(
            new DescribeServicesRequest()
            {
                Language = language
            });
        return response.Services;
    }



    /// <summary>
    /// Get the descriptions of support severity levels.
    /// </summary>
    /// <param name="name">Optional language for severity levels.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>The list of support severity levels.</returns>
    public async Task<List<SeverityLevel>> DescribeSeverityLevels(string language =
"en")
    {
        var response = await _amazonSupport.DescribeSeverityLevelsAsync(
            new DescribeSeverityLevelsRequest()
            {
                Language = language
            });
        return response.SeverityLevels;
    }
```

```
    /// <summary>
    /// Create a new support case.
    /// </summary>
    /// <param name="serviceCode">Service code for the new case.</param>
    /// <param name="categoryCode">Category for the new case.</param>
    /// <param name="severityCode">Severity code for the new case.</param>
    /// <param name="subject">Subject of the new case.</param>
    /// <param name="body">Body text of the new case.</param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set for the new
case.</param>
    /// <param name="issueType">Optional issue type for the new case. Options are
"customer-service" or "technical".</param>
    /// <returns>The caseId of the new support case.</returns>
    public async Task<string> CreateCase(string serviceCode, string categoryCode,
string severityCode, string subject,
        string body, string language = "en", string? attachmentSetId = null, string
issueType = "customer-service")
    {
        var response = await _amazonSupport.CreateCaseAsync(
            new CreateCaseRequest()
            {
                ServiceCode = serviceCode,
                CategoryCode = categoryCode,
                SeverityCode = severityCode,
                Subject = subject,
                Language = language,
                AttachmentSetId = attachmentSetId,
                IssueType = issueType,
                CommunicationBody = body
            });
        return response.CaseId;
    }



    /// <summary>
    /// Add an attachment to a set, or create a new attachment set if one does not
exist.
    /// </summary>
    /// <param name="data">The data for the attachment.</param>
    /// <param name="fileName">The file name for the attachment.</param>
```

```
    /// <param name="attachmentSetId">Optional setId for the attachment. Creates a
new attachment set if empty.</param>
    /// <returns>The setId of the attachment.</returns>
    public async Task<string> AddAttachmentToSet(MemoryStream data, string fileName,
string? attachmentSetId = null)
    {
        var response = await _amazonSupport.AddAttachmentsToSetAsync(
            new AddAttachmentsToSetRequest
            {
                AttachmentSetId = attachmentSetId,
                Attachments = new List<Attachment>
                {
                    new Attachment
                    {
                        Data = data,
                        FileName = fileName
                    }
                }
            });
        return response.AttachmentSetId;
    }



    /// <summary>
    /// Get description of a specific attachment.
    /// </summary>
    /// <param name="attachmentId">Id of the attachment, usually fetched by
describing the communications of a case.</param>
    /// <returns>The attachment object.</returns>
    public async Task<Attachment> DescribeAttachment(string attachmentId)
    {
        var response = await _amazonSupport.DescribeAttachmentAsync(
            new DescribeAttachmentRequest()
            {
                AttachmentId = attachmentId
            });
        return response.Attachment;
    }



    /// <summary>
```

```
    /// Add communication to a case, including optional attachment set ID and CC
 email addresses.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <param name="body">Body text of the communication.</param>
    /// <param name="attachmentSetId">Optional Id for an attachment set.</param>
    /// <param name="ccEmailAddresses">Optional list of CC email addresses.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> AddCommunicationToCase(string caseId, string body,
        string? attachmentSetId = null, List<string>? ccEmailAddresses = null)
    {
        var response = await _amazonSupport.AddCommunicationToCaseAsync(
            new AddCommunicationToCaseRequest()
            {
                CaseId = caseId,
                CommunicationBody = body,
                AttachmentSetId = attachmentSetId,
                CcEmailAddresses = ccEmailAddresses
            });
        return response.Result;
    }



    /// <summary>
    /// Describe the communications for a case, optionally with a date filter.
    /// </summary>
    /// <param name="caseId">The ID of the support case.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <returns>The list of communications for the case.</returns>
    public async Task<List<Communication>> DescribeCommunications(string caseId,
 DateTime? afterTime = null, DateTime? beforeTime = null)
    {
        var results = new List<Communication>();
        var paginateCommunications =
 _amazonSupport.Paginators.DescribeCommunications(
            new DescribeCommunicationsRequest()
            {
                CaseId = caseId,
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s")
```

```
            });
        // Get the entire list using the paginator.
        await foreach (var communications in paginateCommunications.Communications)
        {
            results.Add(communications);
        }
        return results;
    }



    /// <summary>
    /// Get case details for a list of case ids, optionally with date filters.
    /// </summary>
    /// <param name="caseIds">The list of case IDs.</param>
    /// <param name="displayId">Optional display ID.</param>
    /// <param name="includeCommunication">True to include communication. Defaults
 to true.</param>
    /// <param name="includeResolvedCases">True to include resolved cases. Defaults
 to false.</param>
    /// <param name="afterTime">The optional start date for a filtered search.</
param>
    /// <param name="beforeTime">The optional end date for a filtered search.</
param>
    /// <param name="language">Optional language support for your case.
    /// Currently "en" (English) and "ja" (Japanese) are supported.</param>
    /// <returns>A list of CaseDetails.</returns>
    public async Task<List<CaseDetails>> DescribeCases(List<string> caseIds, string?
 displayId = null, bool includeCommunication = true,
        bool includeResolvedCases = false, DateTime? afterTime = null, DateTime?
 beforeTime = null,
        string language = "en")
    {
        var results = new List<CaseDetails>();
        var paginateCases = _amazonSupport.Paginators.DescribeCases(
            new DescribeCasesRequest()
            {
                CaseIdList = caseIds,
                DisplayId = displayId,
                IncludeCommunications = includeCommunication,
                IncludeResolvedCases = includeResolvedCases,
                AfterTime = afterTime?.ToString("s"),
                BeforeTime = beforeTime?.ToString("s"),
                Language = language
```

```
            });
        // Get the entire list using the paginator.
        await foreach (var cases in paginateCases.Cases)
        {
            results.Add(cases);
        }
        return results;
    }



    /// <summary>
    /// Resolve a support case by caseId.
    /// </summary>
    /// <param name="caseId">Id for the support case.</param>
    /// <returns>The final status of the case after resolving.</returns>
    public async Task<string> ResolveCase(string caseId)
    {
        var response = await _amazonSupport.ResolveCaseAsync(
            new ResolveCaseRequest()
            {
                CaseId = caseId
            });
        return response.FinalCaseStatus;
    }


    /// <summary>
    /// Verify the support level for AWS Support API access.
    /// </summary>
    /// <returns>True if the subscription level supports API access.</returns>
    public async Task<bool> VerifySubscription()
    {
        try
        {
            var response = await _amazonSupport.DescribeServicesAsync(
                new DescribeServicesRequest()
                {
                    Language = "en"
                });
            return response.HttpStatusCode == HttpStatusCode.OK;
        }
        catch (Amazon.AWSSupport.AmazonAWSSupportException ex)
        {
```

```
            if (ex.ErrorCode == "SubscriptionRequiredException")
            {
                return false;
            }
            else throw;
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for .NET.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Exemplos do Amazon Transcribe usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Transcribe.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um vocabulário personalizado

O exemplo de código a seguir mostra como criar um vocabulário personalizado do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Create a custom vocabulary using a list of phrases. Custom vocabularies
    /// improve transcription accuracy for one or more specific words.
    /// </summary>
    /// <param name="languageCode">The language code of the vocabulary.</param>
    /// <param name="phrases">Phrases to use in the vocabulary.</param>
    /// <param name="vocabularyName">Name for the vocabulary.</param>
    /// <returns>The state of the custom vocabulary.</returns>
    public async Task<VocabularyState> CreateCustomVocabulary(LanguageCode
languageCode,
        List<string> phrases, string vocabularyName)
    {
        var response = await _amazonTranscribeService.CreateVocabularyAsync(
            new CreateVocabularyRequest
            {
                LanguageCode = languageCode,
                Phrases = phrases,
                VocabularyName = vocabularyName
            });
        return response.VocabularyState;
    }
```

- Para obter detalhes da API, consulte CreateVocabulary a Referência AWS SDK for .NET da API.

Excluir um vocabulário personalizado

O exemplo de código a seguir mostra como excluir um vocabulário personalizado do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Delete an existing custom vocabulary.
/// </summary>
/// <param name="vocabularyName">Name of the vocabulary to delete.</param>
/// <returns>True if successful.</returns>
public async Task<bool> DeleteCustomVocabulary(string vocabularyName)
{
    var response = await _amazonTranscribeService.DeleteVocabularyAsync(
        new DeleteVocabularyRequest
        {
            VocabularyName = vocabularyName
        });
    return response.HttpStatusCode == HttpStatusCode.OK;
}
```

- Para obter detalhes da API, consulte DeleteVocabulary a Referência AWS SDK for .NET da API.

Excluir um trabalho de transcrição médica

O exemplo de código a seguir mostra como excluir um trabalho de transcrição do Amazon Transcribe Medical.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a medical transcription job. Also deletes the transcript associated
 with the job.
    /// </summary>
    /// <param name="jobName">Name of the medical transcription job to delete.</
param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteMedicalTranscriptionJob(string jobName)
    {
        var response = await
 _amazonTranscribeService.DeleteMedicalTranscriptionJobAsync(
            new DeleteMedicalTranscriptionJobRequest()
            {
                MedicalTranscriptionJobName = jobName
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteMedicalTranscriptionJoba Referência AWS SDK for .NET da API.

Criar um trabalho de transcrição

O exemplo de código a seguir mostra como excluir um trabalho de transcrição do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Delete a transcription job. Also deletes the transcript associated with the
job.
    /// </summary>
    /// <param name="jobName">Name of the transcription job to delete.</param>
    /// <returns>True if successful.</returns>
    public async Task<bool> DeleteTranscriptionJob(string jobName)
    {
        var response = await _amazonTranscribeService.DeleteTranscriptionJobAsync(
            new DeleteTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName
            });
        return response.HttpStatusCode == HttpStatusCode.OK;
    }
```

- Para obter detalhes da API, consulte DeleteTranscriptionJoba Referência AWS SDK for .NET da API.

Obter um vocabulário personalizado

O exemplo de código a seguir mostra como obter um vocabulário personalizado do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// <summary>
/// Get information about a custom vocabulary.
/// </summary>
/// <param name="vocabularyName">Name of the vocabulary.</param>
/// <returns>The state of the custom vocabulary.</returns>
public async Task<VocabularyState> GetCustomVocabulary(string vocabularyName)
{
    var response = await _amazonTranscribeService.GetVocabularyAsync(
        new GetVocabularyRequest()
        {
            VocabularyName = vocabularyName
        });
    return response.VocabularyState;
}
```

- Para obter detalhes da API, consulte GetVocabulary a Referência AWS SDK for .NET da API.

Obter trabalho de transcrição

O exemplo de código a seguir mostra como obter um trabalho de transcrição do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Get details about a transcription job.
    /// </summary>
    /// <param name="jobName">A unique name for the transcription job.</param>
    /// <returns>A TranscriptionJob instance with information on the requested
job.</returns>
    public async Task<TranscriptionJob> GetTranscriptionJob(string jobName)
    {
        var response = await _amazonTranscribeService.GetTranscriptionJobAsync(
            new GetTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName
            });
        return response.TranscriptionJob;
    }
```

- Para obter detalhes da API, consulte GetTranscriptionJoba Referência AWS SDK for .NET da API.

Listar vocabulários personalizados

O exemplo de código a seguir mostra como listar vocabulários personalizados do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List custom vocabularies for the current account. Optionally specify a name
    /// filter and a specific state to filter the vocabularies list.
    /// </summary>
```

```
    /// <param name="nameContains">Optional string the vocabulary name must
contain.</param>
    /// <param name="stateEquals">Optional state of the vocabulary.</param>
    /// <returns>List of information about the vocabularies.</returns>
    public async Task<List<VocabularyInfo>> ListCustomVocabularies(string?
nameContains = null,
        VocabularyState? stateEquals = null)
    {
        var response = await _amazonTranscribeService.ListVocabulariesAsync(
            new ListVocabulariesRequest()
            {
                NameContains = nameContains,
                StateEquals = stateEquals
            });
        return response.Vocabularies;
    }
```

- Para obter detalhes da API, consulte ListVocabularies a Referência AWS SDK for .NET da API.

Listar trabalhos de transcrição médica

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe Medical.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List medical transcription jobs, optionally with a name filter.
    /// </summary>
    /// <param name="jobNameContains">Optional name filter for the medical
transcription jobs.</param>
    /// <returns>A list of summaries about medical transcription jobs.</returns>
```

```
    public async Task<List<MedicalTranscriptionJobSummary>>
ListMedicalTranscriptionJobs(
        string? jobNameContains = null)
    {
        var response = await
_amazonTranscribeService.ListMedicalTranscriptionJobsAsync(
            new ListMedicalTranscriptionJobsRequest()
            {
                JobNameContains = jobNameContains
            });
        return response.MedicalTranscriptionJobSummaries;
    }
```

- Para obter detalhes da API, consulte ListMedicalTranscriptionJobsa Referência AWS SDK for .NET da API.

Listar trabalhos de transcrição

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// List transcription jobs, optionally with a name filter.
    /// </summary>
    /// <param name="jobNameContains">Optional name filter for the transcription
jobs.</param>
    /// <returns>A list of transcription job summaries.</returns>
    public async Task<List<TranscriptionJobSummary>> ListTranscriptionJobs(string?
jobNameContains = null)
    {
        var response = await _amazonTranscribeService.ListTranscriptionJobsAsync(
            new ListTranscriptionJobsRequest()
```

```
            {
                JobNameContains = jobNameContains
            });
        return response.TranscriptionJobSummaries;
    }
```

- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for .NET da API.

Iniciar um trabalho de transcrição médica

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe Medical.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start a medical transcription job for a media file. This method returns
    /// as soon as the job is started.
    /// </summary>
    /// <param name="jobName">A unique name for the medical transcription job.</
param>
    /// <param name="mediaFileUri">The URI of the media file, typically an Amazon S3
 location.</param>
    /// <param name="mediaFormat">The format of the media file.</param>
    /// <param name="outputBucketName">Location for the output, typically an Amazon
 S3 location.</param>
    /// <param name="transcriptionType">Conversation or dictation transcription
 type.</param>
    /// <returns>A MedicalTransactionJob instance with information on the new job.</
returns>
    public async Task<MedicalTranscriptionJob> StartMedicalTranscriptionJob(
```

```
        string jobName, string mediaFileUri,
        MediaFormat mediaFormat, string outputBucketName,
Amazon.TranscribeService.Type transcriptionType)
    {
        var response = await
_amazonTranscribeService.StartMedicalTranscriptionJobAsync(
            new StartMedicalTranscriptionJobRequest()
            {
                MedicalTranscriptionJobName = jobName,
                Media = new Media()
                {
                    MediaFileUri = mediaFileUri
                },
                MediaFormat = mediaFormat,
                LanguageCode =
                    LanguageCode
                        .EnUS, // The value must be en-US for medical
transcriptions.
                OutputBucketName = outputBucketName,
                OutputKey =
                    jobName, // The value is a key used to fetch the output of the
transcription.
                Specialty = Specialty.PRIMARYCARE, // The value PRIMARYCARE must be
set.
                Type = transcriptionType
            });
        return response.MedicalTranscriptionJob;
    }
```

- Para obter detalhes da API, consulte StartMedicalTranscriptionJoba Referência AWS SDK for .NET da API.

Iniciar um trabalho de transcrição

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Start a transcription job for a media file. This method returns
    /// as soon as the job is started.
    /// </summary>
    /// <param name="jobName">A unique name for the transcription job.</param>
    /// <param name="mediaFileUri">The URI of the media file, typically an Amazon S3
 location.</param>
    /// <param name="mediaFormat">The format of the media file.</param>
    /// <param name="languageCode">The language code of the media file, such as en-
US.</param>
    /// <param name="vocabularyName">Optional name of a custom vocabulary.</param>
    /// <returns>A TranscriptionJob instance with information on the new job.</
returns>
    public async Task<TranscriptionJob> StartTranscriptionJob(string jobName, string
 mediaFileUri,
        MediaFormat mediaFormat, LanguageCode languageCode, string? vocabularyName)
    {
        var response = await _amazonTranscribeService.StartTranscriptionJobAsync(
            new StartTranscriptionJobRequest()
            {
                TranscriptionJobName = jobName,
                Media = new Media()
                {
                    MediaFileUri = mediaFileUri
                },
                MediaFormat = mediaFormat,
                LanguageCode = languageCode,
                Settings = vocabularyName != null ? new Settings()
                {
                    VocabularyName = vocabularyName
                } : null
            });
        return response.TranscriptionJob;
```

```
    }
```

- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for .NET da API.

Atualizar um vocabulário personalizado

O exemplo de código a seguir mostra como atualizar um vocabulário personalizado do Amazon Transcribe.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// <summary>
    /// Update a custom vocabulary with new values. Update overwrites all existing
information.
    /// </summary>
    /// <param name="languageCode">The language code of the vocabulary.</param>
    /// <param name="phrases">Phrases to use in the vocabulary.</param>
    /// <param name="vocabularyName">Name for the vocabulary.</param>
    /// <returns>The state of the custom vocabulary.</returns>
    public async Task<VocabularyState> UpdateCustomVocabulary(LanguageCode
languageCode,
        List<string> phrases, string vocabularyName)
    {
        var response = await _amazonTranscribeService.UpdateVocabularyAsync(
            new UpdateVocabularyRequest()
            {
                LanguageCode = languageCode,
                Phrases = phrases,
                VocabularyName = vocabularyName
            });
        return response.VocabularyState;
```

```
    }
```

- Para obter detalhes da API, consulte UpdateVocabularya Referência AWS SDK for .NET da API.

Exemplos do Amazon Translate usando AWS SDK for .NET

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for .NET com o Amazon Translate.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descrever um trabalho de tradução

O exemplo de código a seguir mostra como descrever um trabalho de tradução do Amazon Translate.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Threading.Tasks;
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// The following example shows how to retrieve the details of
    /// a text translation job using Amazon Translate.
    /// </summary>
    public class DescribeTextTranslation
    {
        public static async Task Main()
        {
            var client = new AmazonTranslateClient();

            // The Job Id is generated when the text translation job is started
            // with a call to the StartTextTranslationJob method.
            var jobId = "1234567890abcdef01234567890abcde";

            var request = new DescribeTextTranslationJobRequest
            {
                JobId = jobId,
            };

            var jobProperties = await DescribeTranslationJobAsync(client, request);

            DisplayTranslationJobDetails(jobProperties);
        }

        /// <summary>
        /// Retrieve information about an Amazon Translate text translation job.
        /// </summary>
        /// <param name="client">The initialized Amazon Translate client object.</
param>
        /// <param name="request">The DescribeTextTranslationJobRequest object.</
param>
        /// <returns>The TextTranslationJobProperties object containing
        /// information about the text translation job..</returns>
        public static async Task<TextTranslationJobProperties>
 DescribeTranslationJobAsync(
            AmazonTranslateClient client,
            DescribeTextTranslationJobRequest request)
        {
```

```
            var response = await client.DescribeTextTranslationJobAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                return response.TextTranslationJobProperties;
            }
            else
            {
                return null;
            }
        }

        /// <summary>
        /// Displays the properties of the text translation job.
        /// </summary>
        /// <param name="jobProperties">The properties of the text translation
        /// job returned by the call to DescribeTextTranslationJobAsync.</param>
        public static void DisplayTranslationJobDetails(TextTranslationJobProperties
jobProperties)
        {
            if (jobProperties is null)
            {
                Console.WriteLine("No text translation job properties found.");
                return;
            }

            // Display the details of the text translation job.
            Console.WriteLine($"{jobProperties.JobId}: {jobProperties.JobName}");
        }
    }
```

- Para obter detalhes da API, consulte DescribeTextTranslationJoba Referência AWS SDK for .NET da API.

Listar trabalhos de tradução

O exemplo de código a seguir mostra como listar trabalhos de tradução do Amazon Translate.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// List Amazon Translate translation jobs, along with details about each job.
    /// </summary>
    public class ListTranslationJobs
    {
        public static async Task Main()
        {
            var client = new AmazonTranslateClient();
            var filter = new TextTranslationJobFilter
            {
                JobStatus = "COMPLETED",
            };

            var request = new ListTextTranslationJobsRequest
            {
                MaxResults = 10,
                Filter = filter,
            };

            await ListJobsAsync(client, request);
        }

        /// <summary>
        /// List Amazon Translate text translation jobs.
        /// </summary>
        /// <param name="client">The initialized Amazon Translate client object.</
param>
        /// <param name="request">An Amazon Translate
```

```
        /// ListTextTranslationJobsRequest object detailing which text
        /// translation jobs are of interest.</param>
        public static async Task ListJobsAsync(
            AmazonTranslateClient client,
            ListTextTranslationJobsRequest request)
        {
            ListTextTranslationJobsResponse response;

            do
            {
                response = await client.ListTextTranslationJobsAsync(request);

ShowTranslationJobDetails(response.TextTranslationJobPropertiesList);

                request.NextToken = response.NextToken;
            }
            while (response.NextToken is not null);
        }

        /// <summary>
        /// List existing translation job details.
        /// </summary>
        /// <param name="properties">A list of Amazon Translate text
        /// translation jobs.</param>
        public static void
ShowTranslationJobDetails(List<TextTranslationJobProperties> properties)
        {
            properties.ForEach(prop =>
            {
                Console.WriteLine($"{prop.JobId}: {prop.JobName}");
                Console.WriteLine($"Status: {prop.JobStatus}");
                Console.WriteLine($"Submitted time: {prop.SubmittedTime}");
            });
        }
    }
```

- Para obter detalhes da API, consulte ListTextTranslationJobsa Referência AWS SDK for .NET da API.

Iniciar um trabalho de tradução

O exemplo de código a seguir mostra como começar um trabalho de tradução com o Amazon Translate.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    using System;
    using System.Collections.Generic;
    using System.Threading.Tasks;
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// This example shows how to use Amazon Translate to process the files in
    /// an Amazon Simple Storage Service (Amazon S3) bucket. The translated results
    /// will also be stored in an Amazon S3 bucket.
    /// </summary>
    public class BatchTranslate
    {
        public static async Task Main()
        {
            var contentType = "text/plain";

            // Set this variable to an S3 bucket location with a folder."
            // Input files must be in a folder and not at the bucket root."
            var s3InputUri = "s3://DOC-EXAMPLE-BUCKET1/FOLDER/";
            var s3OutputUri = "s3://DOC-EXAMPLE-BUCKET2/";

            // This role must have permissions to read the source bucket and to read
 and
            // write to the destination bucket where the translated text will be
 stored.
            var dataAccessRoleArn = "arn:aws:iam::0123456789ab:role/
S3TranslateRole";
```

```
            var client = new AmazonTranslateClient();

            var inputConfig = new InputDataConfig
            {
                ContentType = contentType,
                S3Uri = s3InputUri,
            };

            var outputConfig = new OutputDataConfig
            {
                S3Uri = s3OutputUri,
            };

            var request = new StartTextTranslationJobRequest
            {
                JobName = "ExampleTranslationJob",
                DataAccessRoleArn = dataAccessRoleArn,
                InputDataConfig = inputConfig,
                OutputDataConfig = outputConfig,
                SourceLanguageCode = "en",
                TargetLanguageCodes = new List<string> { "fr" },
            };

            var response = await StartTextTranslationAsync(client, request);

            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{response.JobId}: {response.JobStatus}");
            }
        }

        /// <summary>
        /// Start the Amazon Translate text translation job.
        /// </summary>
        /// <param name="client">The initialized AmazonTranslateClient object.</
param>
        /// <param name="request">The request object that includes details such
        /// as source and destination bucket names and the IAM Role that will
        /// be used to access the buckets.</param>
        /// <returns>The StartTextTranslationResponse object that includes the
        /// details of the request response.</returns>
        public static async Task<StartTextTranslationJobResponse>
 StartTextTranslationAsync(AmazonTranslateClient client,
 StartTextTranslationJobRequest request)
```

```
        {
            var response = await client.StartTextTranslationJobAsync(request);
            return response;
        }
    }
```

- Para obter detalhes da API, consulte StartTextTranslationJoba Referência AWS SDK for .NET da API.

Interromper um trabalho de tradução

O exemplo de código a seguir mostra como excluir um grupo do Amazon Translate.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
using System.Threading.Tasks;
using Amazon.Translate;
using Amazon.Translate.Model;

/// <summary>
/// Shows how to stop a running Amazon Translation Service text translation
/// job.
/// </summary>
public class StopTextTranslationJob
{
    public static async Task Main()
    {
        var client = new AmazonTranslateClient();
        var jobId = "1234567890abcdef01234567890abcde";

        var request = new StopTextTranslationJobRequest
        {
            JobId = jobId,
```

```
            };

            await StopTranslationJobAsync(client, request);
        }

        /// <summary>
        /// Sends a request to stop a text translation job.
        /// </summary>
        /// <param name="client">Initialized AmazonTrnslateClient object.</param>
        /// <param name="request">The request object to be passed to the
        /// StopTextJobAsync method.</param>
        public static async Task StopTranslationJobAsync(
            AmazonTranslateClient client,
            StopTextTranslationJobRequest request)
        {
            var response = await client.StopTextTranslationJobAsync(request);
            if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
            {
                Console.WriteLine($"{response.JobId} as status:
{response.JobStatus}");
            }
        }
    }
```

- Para obter detalhes da API, consulte StopTextTranslationJoba Referência AWS SDK for .NET da API.

Traduzir texto

O exemplo de código a seguir mostra como traduzir texto com o Amazon Translate.

AWS SDK for .NET

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
using System;
```

```
    using System.IO;
    using System.Threading.Tasks;
    using Amazon.S3;
    using Amazon.S3.Transfer;
    using Amazon.Translate;
    using Amazon.Translate.Model;

    /// <summary>
    /// Take text from a file stored a Amazon Simple Storage Service (Amazon S3)
    /// object and translate it using the Amazon Transfer Service.
    /// </summary>
    public class TranslateText
    {
        public static async Task Main()
        {
            // If the region you want to use is different from the region
            // defined for the default user, supply it as a parameter to the
            // Amazon Translate client object constructor.
            var client = new AmazonTranslateClient();

            // Set the source language to "auto" to request Amazon Translate to
            // automatically detect te language of the source text.

            // You can get a list of the languages supposed by Amazon Translate
            // in the Amazon Translate Developer's Guide here:
            //      https://docs.aws.amazon.com/translate/latest/dg/what-is.html
            string srcLang = "en"; // English.
            string destLang = "fr"; // French.

            // The Amazon Simple Storage Service (Amazon S3) bucket where the
            // source text file is stored.
            string srcBucket = "DOC-EXAMPLE-BUCKET";
            string srcTextFile = "source.txt";

            var srcText = await GetSourceTextAsync(srcBucket, srcTextFile);
            var destText = await TranslatingTextAsync(client, srcLang, destLang,
srcText);

            ShowText(srcText, destText);
        }

        /// <summary>
        /// Use the Amazon S3 TransferUtility to retrieve the text to translate
        /// from an object in an S3 bucket.
```

```
        /// </summary>
        /// <param name="srcBucket">The name of the S3 bucket where the
        /// text is stored.
        /// </param>
        /// <param name="srcTextFile">The key of the S3 object that
        /// contains the text to translate.</param>
        /// <returns>A string representing the source text.</returns>
        public static async Task<string> GetSourceTextAsync(string srcBucket, string
srcTextFile)
        {
            string srcText = string.Empty;

            var s3Client = new AmazonS3Client();
            TransferUtility utility = new TransferUtility(s3Client);

            using var stream = await utility.OpenStreamAsync(srcBucket,
srcTextFile);

            StreamReader file = new System.IO.StreamReader(stream);

            srcText = file.ReadToEnd();
            return srcText;
        }

        /// <summary>
        /// Use the Amazon Translate Service to translate the document from the
        /// source language to the specified destination language.
        /// </summary>
        /// <param name="client">The Amazon Translate Service client used to
        /// perform the translation.</param>
        /// <param name="srcLang">The language of the source text.</param>
        /// <param name="destLang">The destination language for the translated
        /// text.</param>
        /// <param name="text">A string representing the text to ranslate.</param>
        /// <returns>The text that has been translated to the destination
        /// language.</returns>
        public static async Task<string> TranslatingTextAsync(AmazonTranslateClient
client, string srcLang, string destLang, string text)
        {
            var request = new TranslateTextRequest
            {
                SourceLanguageCode = srcLang,
                TargetLanguageCode = destLang,
                Text = text,
```

```
            };

            var response = await client.TranslateTextAsync(request);

            return response.TranslatedText;
        }

        /// <summary>
        /// Show the original text followed by the translated text.
        /// </summary>
        /// <param name="srcText">The original text to be translated.</param>
        /// <param name="destText">The translated text.</param>
        public static void ShowText(string srcText, string destText)
        {
            Console.WriteLine("Source text:");
            Console.WriteLine(srcText);
            Console.WriteLine();
            Console.WriteLine("Translated text:");
            Console.WriteLine(destText);
        }
    }
```

- Para obter detalhes da API, consulte TranslateTexta Referência AWS SDK for .NET da API.

Exemplos entre serviços usando AWS SDK for .NET

Os aplicativos de exemplo a seguir usam o AWS SDK for .NET para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de publicação e assinatura que traduz mensagens
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

Criar uma aplicação de publicação e assinatura que traduz mensagens

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

AWS SDK for .NET

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition

- Amazon S3
- Amazon SNS

Criar uma aplicação Web para monitorar dados do DynamoDB

AWS SDK for .NET

Mostra como usar a API .NET do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

AWS SDK for .NET

Mostra como usar o AWS SDK for .NET para desenvolver uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end .NET RESTful.

- Integre uma aplicação Web do React com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Aurora.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS

- Amazon SES

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

AWS SDK for .NET

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

AWS SDK for .NET

Mostra como usar a API .NET do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Exemplos de código para AWS CLI com Bash script

Os exemplos de código neste tópico mostram como usar AWS Command Line Interface com Bash script mais AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- AWS CLI com o Guia do Desenvolvedor Bash script : Saiba mais sobre como usar o Bash com AWS.
- AWSCentro do Desenvolvedor : Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários de uso da AWS CLI com script Bash

Ações e cenários de uso da AWS CLI com script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio de Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos do DynamoDB de uso da AWS CLI com script Bash
- HealthImaging exemplos de uso AWS CLI com o script Bash
- Exemplos do IAM que usam a AWS CLI com script Bash
- Exemplos do Amazon S3 de uso da AWS CLI com script Bash
- Exemplos do AWS STS de uso da AWS CLI com script Bash

Exemplos do DynamoDB de uso da AWS CLI com script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio do DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_create_table
#
# This function creates an Amazon DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to create.
#       -a attribute_definitions -- JSON file path of a list of attributes and their
 types.
#       -k key_schema -- JSON file path of a list of attributes and their key types.
#       -p provisioned_throughput -- Provisioned throughput settings for the table.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_create_table() {
  local table_name attribute_definitions key_schema provisioned_throughput response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_create_table"
    echo "Creates an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to create."
    echo " -a attribute_definitions -- JSON file path of a list of attributes and
 their types."
    echo " -k key_schema -- JSON file path of a list of attributes and their key
 types."
    echo " -p provisioned_throughput -- Provisioned throughput settings for the
 table."
    echo ""
```

```
  }

  # Retrieve the calling parameters.
  while getopts "n:a:k:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      a) attribute_definitions="${OPTARG}" ;;
      k) key_schema="${OPTARG}" ;;
      p) provisioned_throughput="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_definitions" ]]; then
    errecho "ERROR: You must provide an attribute definitions json file path the -a
parameter."
    usage
    return 1
  fi

  if [[ -z "$key_schema" ]]; then
    errecho "ERROR: You must provide a key schema json file path the -k parameter."
    usage
    return 1
  fi

  if [[ -z "$provisioned_throughput" ]]; then
    errecho "ERROR: You must provide a provisioned throughput json file path the -p
parameter."
```

```
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    attribute_definitions:   $attribute_definitions"
  iecho "    key_schema:   $key_schema"
  iecho "    provisioned_throughput:   $provisioned_throughput"
  iecho ""

  response=$(aws dynamodb create-table \
    --table-name "$table_name" \
    --attribute-definitions file://"$attribute_definitions" \
    --key-schema file://"$key_schema" \
    --provisioned-throughput "$provisioned_throughput")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-table operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}
```

```
##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
```

```
}
```

- Para obter detalhes da API, consulte CreateTableem Referência de AWS CLI Comandos.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_delete_table
#
# This function deletes a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
################################################################################
function dynamodb_delete_table() {
  local table_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function dynamodb_delete_table"
    echo "Deletes an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to delete."
    echo ""
  }
```

```
  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho ""

  response=$(aws dynamodb delete-table \
    --table-name "$table_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-table operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
```

```
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteTableem Referência de AWS CLI Comandos.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###########################################################################
# function dynamodb_delete_item
#
# This function deletes an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 delete.
#
#  Returns:
#       0 - If successful.
```

```
#       1 - If it fails.
##############################################################################
function dynamodb_delete_item() {
  local table_name keys response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_delete_item"
    echo "Delete an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to delete."
    echo ""
  }
  while getopts "n:k:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
    return 1
```

```
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    keys:   $keys"
  iecho ""

  response=$(aws dynamodb delete-item \
    --table-name "$table_name" \
    --key file://"$keys")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-item operation failed.$response"
    return 1
  fi

  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
```

```
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteItemem Referência de AWS CLI Comandos.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###########################################################################
# function dynamodb_batch_get_item
#
# This function gets a batch of items from a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the keys of the items to get.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##########################################################################
function dynamodb_batch_get_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_get_item"
    echo "Get a batch of items from a DynamoDB table."
    echo " -i item  -- Path to json file containing the keys of the items to get."
    echo ""
  }

  while getopts "i:h" option; do
    case "${option}" in
      i) item="${OPTARG}" ;;
```

```
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  response=$(aws dynamodb batch-get-item \
    --request-items file://"$item")
  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-get-item operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
```

```
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte BatchGetItemem Referência de AWS CLI Comandos.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###########################################################################
# function dynamodb_get_item
#
# This function gets an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 get.
#       [-q query]  -- Optional JMESPath query expression.
#
#  Returns:
#       The item as text output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###########################################################################
function dynamodb_get_item() {
  local table_name keys query response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_get_item"
    echo "Get an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to get."
    echo " [-q query]  -- Optional JMESPath query expression."
```

```
  echo ""
}
query=""
while getopts "n:k:q:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    k) keys="${OPTARG}" ;;
    q) query="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi

if [[ -n "$query" ]]; then
  response=$(aws dynamodb get-item \
    --table-name "$table_name" \
    --key file://"$keys" \
    --output text \
    --query "$query")
else
  response=$(
    aws dynamodb get-item \
      --table-name "$table_name" \
      --key file://"$keys" \
```

```
        --output text
    )
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports get-item operation failed.$response"
    return 1
  fi

  if [[ -n "$query" ]]; then
    echo "$response" | sed "/^\t/s/\t//1" # Remove initial tab that the JMSEPath
 query inserts on some strings.
  else
    echo "$response"
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
```

```
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte GetItemem Referência de AWS CLI Comandos.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_describe_table
#
# This function returns the status of a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#
#  Response:
#       - TableStatus:
#     And:
#       0 - Table is active.
#       1 - If it fails.
###############################################################################
function dynamodb_describe_table {
  local table_name
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_describe_table"
    echo "Describe the status of a DynamoDB table."
    echo "  -n table_name  -- The name of the table."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
```

```
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  local table_status
    table_status=$(
      aws dynamodb describe-table \
        --table-name "$table_name" \
        --output text \
        --query 'Table.TableStatus'
    )

   local error_code=${?}

    if [[ $error_code -ne 0 ]]; then
      aws_cli_error_log "$error_code"
      errecho "ERROR: AWS reports describe-table operation failed.$table_status"
      return 1
    fi

  echo "$table_status"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

################################################################################
# function aws_cli_error_log()
```

```
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DescribeTableem Referência de AWS CLI Comandos.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_list_tables
#
# This function lists all the tables in a DynamoDB.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
#############################################################################
function dynamodb_list_tables() {
  response=$(aws dynamodb list-tables \
    --output text \
    --query "TableNames")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi

  echo "$response" | tr -s "[:space:]" "\n"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
```

```
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte ListTablesem Referência de AWS CLI Comandos.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_put_item
#
# This function puts an item into a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -i item  -- Path to json file containing the item values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_put_item() {
  local table_name item response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_put_item"
    echo "Put an item into a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -i item  -- Path to json file containing the item values."
    echo ""
  }

  while getopts "n:i:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
```

```
    i) item="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$item" ]]; then
  errecho "ERROR: You must provide an item with the -i parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    item:   $item"
iecho ""
iecho ""

response=$(aws dynamodb put-item \
  --table-name "$table_name" \
  --item file://"$item")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports put-item operation failed.$response"
  return 1
fi
```

```
  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
```

```
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte PutItemem Referência de AWS CLI Comandos.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_query
#
# This function queries a DynamoDB table.
#
```

```
# Parameters:
#       -n table_name  -- The name of the table.
#       -k key_condition_expression -- The key condition expression.
#       -a attribute_names -- Path to JSON file containing the attribute names.
#       -v attribute_values -- Path to JSON file containing the attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_query() {
  local table_name key_condition_expression attribute_names attribute_values
 projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_query"
    echo "Query a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k key_condition_expression -- The key condition expression."
    echo " -a attribute_names -- Path to JSON file containing the attribute names."
    echo " -v attribute_values -- Path to JSON file containing the attribute
 values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:k:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) key_condition_expression="${OPTARG}" ;;
      a) attribute_names="${OPTARG}" ;;
      v) attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
```

```
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$key_condition_expression" ]]; then
    errecho "ERROR: You must provide a key condition expression with the -k
parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_names" ]]; then
    errecho "ERROR: You must provide a attribute names with the -a parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_values" ]]; then
    errecho "ERROR: You must provide a attribute values with the -v parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values")
  else
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
```

```
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports query operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

################################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
```

```
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte Query na Referência de comandos da AWS CLI.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_scan
#
```

```
# This function scans a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -f filter_expression  -- The filter expression.
#       -a expression_attribute_names -- Path to JSON file containing the expression
 attribute names.
#       -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
###########################################################################
function dynamodb_scan() {
  local table_name filter_expression expression_attribute_names
 expression_attribute_values projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_scan"
    echo "Scan a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -f filter_expression  -- The filter expression."
    echo " -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names."
    echo " -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:f:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      f) filter_expression="${OPTARG}" ;;
      a) expression_attribute_names="${OPTARG}" ;;
      v) expression_attribute_values="${OPTARG}" ;;
```

```
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$filter_expression" ]]; then
    errecho "ERROR: You must provide a filter expression with the -f parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_names" ]]; then
    errecho "ERROR: You must provide expression attribute names with the -a
parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_values" ]]; then
    errecho "ERROR: You must provide expression attribute values with the -v
parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
```

```
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values")
  else
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports scan operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

################################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
```

```
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte Scan na Referência de comandos da AWS CLI.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_update_item
#
# This function updates an item in a DynamoDB table.
#
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 update.
#       -e update expression  -- An expression that defines one or more attributes
 to be updated.
#       -v values  -- Path to json file containing the update values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_update_item() {
  local table_name keys update_expression values response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_update_item"
    echo "Update an item in a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to update."
    echo " -e update expression  -- An expression that defines one or more
 attributes to be updated."
    echo " -v values  -- Path to json file containing the update values."
```

```
  echo ""
}

while getopts "n:k:e:v:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    k) keys="${OPTARG}" ;;
    e) update_expression="${OPTARG}" ;;
    v) values="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi
if [[ -z "$update_expression" ]]; then
  errecho "ERROR: You must provide an update expression with the -e parameter."
  usage
  return 1
fi

if [[ -z "$values" ]]; then
  errecho "ERROR: You must provide a values json file path the -v parameter."
  usage
  return 1
fi
```

```
  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    keys:   $keys"
  iecho "    update_expression:   $update_expression"
  iecho "    values:   $values"

  response=$(aws dynamodb update-item \
    --table-name "$table_name" \
    --key file://"$keys" \
    --update-expression "$update_expression" \
    --expression-attribute-values file://"$values")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports update-item operation failed.$response"
    return 1
  fi

  return 0

}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
```

```
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte UpdateItemem Referência de AWS CLI Comandos.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function dynamodb_batch_write_item
#
# This function writes a batch of items into a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the items to write.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_batch_write_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_write_item"
    echo "Write a batch of items into a DynamoDB table."
    echo " -i item  -- Path to json file containing the items to write."
    echo ""
  }
  while getopts "i:h" option; do
    case "${option}" in
      i) item="${OPTARG}" ;;
```

```
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    item:   $item"
  iecho ""

  response=$(aws dynamodb batch-write-item \
    --request-items file://"$item")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas neste exemplo.

```
###############################################################################
# function iecho
```

```
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

##############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
##############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

##############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
##############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
```

```
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte BatchWriteItemem Referência de AWS CLI Comandos.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O cenário de conceitos básicos do DynamoDB.

```
###############################################################################
```

```
# function dynamodb_getting_started_movies
#
# Scenario to create an Amazon DynamoDB table and perform a series of operations on
 the table.
#
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
###############################################################################
function dynamodb_getting_started_movies() {

  source ./dynamodb_operations.sh

  key_schema_json_file="dynamodb_key_schema.json"
  attribute_definitions_json_file="dynamodb_attr_def.json"
  item_json_file="movie_item.json"
  key_json_file="movie_key.json"
  batch_json_file="batch.json"
  attribute_names_json_file="attribute_names.json"
  attributes_values_json_file="attribute_values.json"

  echo_repeat "*" 88
  echo
  echo "Welcome to the Amazon DynamoDB getting started demo."
  echo
  echo_repeat "*" 88
  echo

  local table_name
  echo -n "Enter a name for a new DynamoDB table: "
  get_input
  table_name=$get_input_result

  local provisioned_throughput="ReadCapacityUnits=5,WriteCapacityUnits=5"

  echo '[
  {"AttributeName": "year", "KeyType": "HASH"},
   {"AttributeName": "title", "KeyType": "RANGE"}
  ]' >"$key_schema_json_file"

  echo '[
  {"AttributeName": "year", "AttributeType": "N"},
   {"AttributeName": "title", "AttributeType": "S"}
  ]' >"$attribute_definitions_json_file"
```

```
if dynamodb_create_table -n "$table_name" -a "$attribute_definitions_json_file" \
  -k "$key_schema_json_file" -p "$provisioned_throughput" 1>/dev/null; then
  echo "Created a DynamoDB table named $table_name"
else
  errecho "The table failed to create. This demo will exit."
  clean_up
  return 1
fi

echo "Waiting for the table to become active...."

if dynamodb_wait_table_active -n "$table_name"; then
  echo "The table is now active."
else
  errecho "The table failed to become active. This demo will exit."
  cleanup "$table_name"
  return 1
fi

echo
echo_repeat "*" 88
echo

echo -n "Enter the title of a movie you want to add to the table: "
get_input
local added_title
added_title=$get_input_result

local added_year
get_int_input "What year was it released? "
added_year=$get_input_result

local rating
get_float_input "On a scale of 1 - 10, how do you rate it? " "1" "10"
rating=$get_input_result

local plot
echo -n "Summarize the plot for me: "
get_input
plot=$get_input_result

echo '{
  "year": {"N" :"'"$added_year"'"},
```

```
    "title": {"S" :  "'"$added_title"'"},
    "info": {"M" : {"plot": {"S" : "'"$plot"'"}, "rating": {"N" :"'"$rating"'"} } }
   }' >"$item_json_file"

  if dynamodb_put_item -n "$table_name" -i "$item_json_file"; then
    echo "The movie '$added_title' was successfully added to the table
'$table_name'."
  else
    errecho "Put item failed. This demo will exit."
    clean_up "$table_name"
    return 1
  fi

  echo
  echo_repeat "*" 88
  echo

  echo "Let's update your movie '$added_title'."
  get_float_input "You rated it $rating, what new rating would you give it? " "1"
"10"
  rating=$get_input_result

  echo -n "You summarized the plot as '$plot'."
  echo "What would you say now? "
  get_input
  plot=$get_input_result

  echo '{
    "year": {"N" :"'"$added_year"'"},
    "title": {"S" :  "'"$added_title"'"}
    }' >"$key_json_file"

  echo '{
    ":r": {"N" :"'"$rating"'"},
    ":p": {"S" : "'"$plot"'"}
   }' >"$item_json_file"

  local update_expression="SET info.rating = :r, info.plot = :p"

  if dynamodb_update_item -n "$table_name" -k "$key_json_file" -e
"$update_expression" -v "$item_json_file"; then
    echo "Updated '$added_title' with new attributes."
  else
    errecho "Update item failed. This demo will exit."
```

```
    clean_up "$table_name"
    return 1
  fi

  echo
  echo_repeat "*" 88
  echo

  echo "We will now use batch write to upload 150 movie entries into the table."

  local batch_json
  for batch_json in movie_files/movies_*.json; do
    echo "{ \"$table_name\" : $(<"$batch_json") }" >"$batch_json_file"
    if dynamodb_batch_write_item -i "$batch_json_file" 1>/dev/null; then
      echo "Entries in $batch_json added to table."
    else
      errecho "Batch write failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi
  done

  local title="The Lord of the Rings: The Fellowship of the Ring"
  local year="2001"

  if get_yes_no_input "Let's move on...do you want to get info about '$title'? (y/n)
"; then
    echo '{
  "year": {"N" :"'"$year"'"},
  "title": {"S" :  "'"$title"'"}
  }' >"$key_json_file"
    local info
    info=$(dynamodb_get_item -n "$table_name" -k "$key_json_file")

    # shellcheck disable=SC2181
    if [[ ${?} -ne 0 ]]; then
      errecho "Get item failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi

    echo "Here is what I found:"
    echo "$info"
  fi
```

```
  local ask_for_year=true
  while [[ "$ask_for_year" == true ]]; do
    echo "Let's get a list of movies released in a given year."
    get_int_input "Enter a year between 1972 and 2018: " "1972" "2018"
    year=$get_input_result
    echo '{
    "#n": "year"
    }' >"$attribute_names_json_file"

    echo '{
    ":v": {"N" :"'"$year"'"}
    }' >"$attributes_values_json_file"

    response=$(dynamodb_query -n "$table_name" -k "#n=:v" -a
"$attribute_names_json_file" -v "$attributes_values_json_file")

    # shellcheck disable=SC2181
    if [[ ${?} -ne 0 ]]; then
      errecho "Query table failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi

    echo "Here is what I found:"
    echo "$response"

    if ! get_yes_no_input "Try another year? (y/n) "; then
      ask_for_year=false
    fi
  done

  echo "Now let's scan for movies released in a range of years. Enter a year: "
  get_int_input "Enter a year between 1972 and 2018: " "1972" "2018"
  local start=$get_input_result

  get_int_input "Enter another year: " "1972" "2018"
  local end=$get_input_result

  echo '{
    "#n": "year"
    }' >"$attribute_names_json_file"

  echo '{
```

```
    ":v1": {"N" : "'"$start"'"},
    ":v2": {"N" : "'"$end"'"}
    }' >"$attributes_values_json_file"

  response=$(dynamodb_scan -n "$table_name" -f "#n BETWEEN :v1 AND :v2" -a
"$attribute_names_json_file" -v "$attributes_values_json_file")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "Scan table failed. This demo will exit."
    clean_up "$table_name"
    return 1
  fi

  echo "Here is what I found:"
  echo "$response"

  echo
  echo_repeat "*" 88
  echo

  echo "Let's remove your movie '$added_title' from the table."

  if get_yes_no_input "Do you want to remove '$added_title'? (y/n) "; then
    echo '{
  "year": {"N" :"'"$added_year"'"},
  "title": {"S" :  "'"$added_title"'"}
  }' >"$key_json_file"

    if ! dynamodb_delete_item -n "$table_name" -k "$key_json_file"; then
      errecho "Delete item failed. This demo will exit."
      clean_up "$table_name"
      return 1
    fi
  fi

  if get_yes_no_input "Do you want to delete the table '$table_name'? (y/n) "; then
    if ! clean_up "$table_name"; then
      return 1
    fi
  else
    if ! clean_up; then
      return 1
    fi
```

```
  fi

  return 0
}
```

As funções do DynamoDB usadas nesse cenário.

```
###############################################################################
# function dynamodb_create_table
#
# This function creates an Amazon DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to create.
#       -a attribute_definitions -- JSON file path of a list of attributes and their
 types.
#       -k key_schema -- JSON file path of a list of attributes and their key types.
#       -p provisioned_throughput -- Provisioned throughput settings for the table.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_create_table() {
  local table_name attribute_definitions key_schema provisioned_throughput response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_create_table"
    echo "Creates an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to create."
    echo " -a attribute_definitions -- JSON file path of a list of attributes and
 their types."
    echo " -k key_schema -- JSON file path of a list of attributes and their key
 types."
    echo " -p provisioned_throughput -- Provisioned throughput settings for the
 table."
    echo ""
  }
```

```
# Retrieve the calling parameters.
while getopts "n:a:k:p:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    a) attribute_definitions="${OPTARG}" ;;
    k) key_schema="${OPTARG}" ;;
    p) provisioned_throughput="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$attribute_definitions" ]]; then
  errecho "ERROR: You must provide an attribute definitions json file path the -a
parameter."
  usage
  return 1
fi

if [[ -z "$key_schema" ]]; then
  errecho "ERROR: You must provide a key schema json file path the -k parameter."
  usage
  return 1
fi

if [[ -z "$provisioned_throughput" ]]; then
  errecho "ERROR: You must provide a provisioned throughput json file path the -p
parameter."
  usage
```

```
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    attribute_definitions:   $attribute_definitions"
  iecho "    key_schema:   $key_schema"
  iecho "    provisioned_throughput:   $provisioned_throughput"
  iecho ""

  response=$(aws dynamodb create-table \
    --table-name "$table_name" \
    --attribute-definitions file://"$attribute_definitions" \
    --key-schema file://"$key_schema" \
    --provisioned-throughput "$provisioned_throughput")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-table operation failed.$response"
    return 1
  fi

  return 0
}

###############################################################################
# function dynamodb_describe_table
#
# This function returns the status of a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#
#  Response:
#       - TableStatus:
#     And:
#       0 - Table is active.
#       1 - If it fails.
###############################################################################
function dynamodb_describe_table {
  local table_name
  local option OPTARG # Required to use getopts command in a function.
```

```
#######################################
# Function usage explanation
#######################################
function usage() {
  echo "function dynamodb_describe_table"
  echo "Describe the status of a DynamoDB table."
  echo "  -n table_name  -- The name of the table."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:h" option; do
  case "${option}" in
    n) table_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

local table_status
  table_status=$(
    aws dynamodb describe-table \
      --table-name "$table_name" \
      --output text \
      --query 'Table.TableStatus'
  )

 local error_code=${?}
```

```
    if [[ $error_code -ne 0 ]]; then
      aws_cli_error_log "$error_code"
      errecho "ERROR: AWS reports describe-table operation failed.$table_status"
      return 1
    fi

  echo "$table_status"

  return 0
}

###############################################################################
# function dynamodb_put_item
#
# This function puts an item into a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -i item  -- Path to json file containing the item values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_put_item() {
  local table_name item response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_put_item"
    echo "Put an item into a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -i item  -- Path to json file containing the item values."
    echo ""
  }

  while getopts "n:i:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      i) item="${OPTARG}" ;;
      h)
```

```
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$item" ]]; then
  errecho "ERROR: You must provide an item with the -i parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    item:   $item"
iecho ""
iecho ""

response=$(aws dynamodb put-item \
  --table-name "$table_name" \
  --item file://"$item")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports put-item operation failed.$response"
  return 1
fi

return 0
```

```
}

###############################################################################
# function dynamodb_update_item
#
# This function updates an item in a DynamoDB table.
#
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 update.
#       -e update expression  -- An expression that defines one or more attributes
 to be updated.
#       -v values  -- Path to json file containing the update values.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_update_item() {
  local table_name keys update_expression values response
  local option OPTARG # Required to use getopts command in a function.

  ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_update_item"
    echo "Update an item in a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to update."
    echo " -e update expression  -- An expression that defines one or more
 attributes to be updated."
    echo " -v values  -- Path to json file containing the update values."
    echo ""
  }

  while getopts "n:k:e:v:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      e) update_expression="${OPTARG}" ;;
```

```
    v) values="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$table_name" ]]; then
  errecho "ERROR: You must provide a table name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$keys" ]]; then
  errecho "ERROR: You must provide a keys json file path the -k parameter."
  usage
  return 1
fi
if [[ -z "$update_expression" ]]; then
  errecho "ERROR: You must provide an update expression with the -e parameter."
  usage
  return 1
fi

if [[ -z "$values" ]]; then
  errecho "ERROR: You must provide a values json file path the -v parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    table_name:   $table_name"
iecho "    keys:   $keys"
iecho "    update_expression:   $update_expression"
iecho "    values:   $values"

response=$(aws dynamodb update-item \
```

```
    --table-name "$table_name" \
    --key file://"$keys" \
    --update-expression "$update_expression" \
    --expression-attribute-values file://"$values")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports update-item operation failed.$response"
    return 1
  fi

  return 0

}

###############################################################################
# function dynamodb_batch_write_item
#
# This function writes a batch of items into a DynamoDB table.
#
# Parameters:
#       -i item  -- Path to json file containing the items to write.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_batch_write_item() {
  local item response
  local option OPTARG # Required to use getopts command in a function.

  ########################################
  # Function usage explanation
  ########################################
  function usage() {
    echo "function dynamodb_batch_write_item"
    echo "Write a batch of items into a DynamoDB table."
    echo " -i item  -- Path to json file containing the items to write."
    echo ""
  }
  while getopts "i:h" option; do
    case "${option}" in
```

```
      i) item="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$item" ]]; then
    errecho "ERROR: You must provide an item with the -i parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    item:   $item"
  iecho ""

  response=$(aws dynamodb batch-write-item \
    --request-items file://"$item")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports batch-write-item operation failed.$response"
    return 1
  fi

  return 0
}

###############################################################################
# function dynamodb_get_item
#
# This function gets an item from a DynamoDB table.
#
```

```
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 get.
#       [-q query]  -- Optional JMESPath query expression.
#
#  Returns:
#       The item as text output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_get_item() {
  local table_name keys query response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_get_item"
    echo "Get an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to get."
    echo " [-q query]  -- Optional JMESPath query expression."
    echo ""
  }
  query=""
  while getopts "n:k:q:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      q) query="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
```

```
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
    return 1
  fi

  if [[ -n "$query" ]]; then
    response=$(aws dynamodb get-item \
      --table-name "$table_name" \
      --key file://"$keys" \
      --output text \
      --query "$query")
  else
    response=$(
      aws dynamodb get-item \
        --table-name "$table_name" \
        --key file://"$keys" \
        --output text
    )
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports get-item operation failed.$response"
    return 1
  fi

  if [[ -n "$query" ]]; then
    echo "$response" | sed "/^\t/s/\t//1" # Remove initial tab that the JMSEPath
query inserts on some strings.
  else
    echo "$response"
  fi
```

```
  return 0
}

##############################################################################
# function dynamodb_query
#
# This function queries a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k key_condition_expression -- The key condition expression.
#       -a attribute_names -- Path to JSON file containing the attribute names.
#       -v attribute_values -- Path to JSON file containing the attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_query() {
  local table_name key_condition_expression attribute_names attribute_values
 projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_query"
    echo "Query a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k key_condition_expression -- The key condition expression."
    echo " -a attribute_names -- Path to JSON file containing the attribute names."
    echo " -v attribute_values -- Path to JSON file containing the attribute
 values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:k:a:v:p:h" option; do
    case "${option}" in
```

```
      n) table_name="${OPTARG}" ;;
      k) key_condition_expression="${OPTARG}" ;;
      a) attribute_names="${OPTARG}" ;;
      v) attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$key_condition_expression" ]]; then
    errecho "ERROR: You must provide a key condition expression with the -k
parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_names" ]]; then
    errecho "ERROR: You must provide a attribute names with the -a parameter."
    usage
    return 1
  fi

  if [[ -z "$attribute_values" ]]; then
    errecho "ERROR: You must provide a attribute values with the -v parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
```

```
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values")
  else
    response=$(aws dynamodb query \
      --table-name "$table_name" \
      --key-condition-expression "$key_condition_expression" \
      --expression-attribute-names file://"$attribute_names" \
      --expression-attribute-values file://"$attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports query operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function dynamodb_scan
#
# This function scans a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -f filter_expression  -- The filter expression.
#       -a expression_attribute_names -- Path to JSON file containing the expression
 attribute names.
#       -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values.
#       [-p projection_expression]  -- Optional projection expression.
#
#  Returns:
#       The items as json output.
#  And:
```

```
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_scan() {
  local table_name filter_expression expression_attribute_names
 expression_attribute_values projection_expression response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_scan"
    echo "Scan a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -f filter_expression  -- The filter expression."
    echo " -a expression_attribute_names -- Path to JSON file containing the
 expression attribute names."
    echo " -v expression_attribute_values -- Path to JSON file containing the
 expression attribute values."
    echo " [-p projection_expression]  -- Optional projection expression."
    echo ""
  }

  while getopts "n:f:a:v:p:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      f) filter_expression="${OPTARG}" ;;
      a) expression_attribute_names="${OPTARG}" ;;
      v) expression_attribute_values="${OPTARG}" ;;
      p) projection_expression="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1
```

```
  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$filter_expression" ]]; then
    errecho "ERROR: You must provide a filter expression with the -f parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_names" ]]; then
    errecho "ERROR: You must provide expression attribute names with the -a
parameter."
    usage
    return 1
  fi

  if [[ -z "$expression_attribute_values" ]]; then
    errecho "ERROR: You must provide expression attribute values with the -v
parameter."
    usage
    return 1
  fi

  if [[ -z "$projection_expression" ]]; then
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values")
  else
    response=$(aws dynamodb scan \
      --table-name "$table_name" \
      --filter-expression "$filter_expression" \
      --expression-attribute-names file://"$expression_attribute_names" \
      --expression-attribute-values file://"$expression_attribute_values" \
      --projection-expression "$projection_expression")
  fi

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
```

```
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports scan operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function dynamodb_delete_item
#
# This function deletes an item from a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table.
#       -k keys  -- Path to json file containing the keys that identify the item to
 delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function dynamodb_delete_item() {
  local table_name keys response
  local option OPTARG # Required to use getopts command in a function.

  # ######################################
  # Function usage explanation
  ######################################
  function usage() {
    echo "function dynamodb_delete_item"
    echo "Delete an item from a DynamoDB table."
    echo " -n table_name  -- The name of the table."
    echo " -k keys  -- Path to json file containing the keys that identify the item
 to delete."
    echo ""
  }
  while getopts "n:k:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      k) keys="${OPTARG}" ;;
      h)
```

```
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$keys" ]]; then
    errecho "ERROR: You must provide a keys json file path the -k parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho "    keys:   $keys"
  iecho ""

  response=$(aws dynamodb delete-item \
    --table-name "$table_name" \
    --key file://"$keys")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-item operation failed.$response"
    return 1
  fi

  return 0

}
```

```
##############################################################################
# function dynamodb_delete_table
#
# This function deletes a DynamoDB table.
#
# Parameters:
#       -n table_name  -- The name of the table to delete.
#
#  Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function dynamodb_delete_table() {
  local table_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function dynamodb_delete_table"
    echo "Deletes an Amazon DynamoDB table."
    echo " -n table_name  -- The name of the table to delete."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) table_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$table_name" ]]; then
    errecho "ERROR: You must provide a table name with the -n parameter."
```

```
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    table_name:   $table_name"
  iecho ""

  response=$(aws dynamodb delete-table \
    --table-name "$table_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-table operation failed.$response"
    return 1
  fi

  return 0
}
```

As funções utilitárias usadas nesse cenário.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
```

```
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function aws_cli_error_log()
#
# This function is used to log the error messages from the AWS CLI.
#
# See https://docs.aws.amazon.com/cli/latest/topic/return-codes.html#cli-aws-help-
return-codes.
#
# The function expects the following argument:
#         $1 - The error code returned by the AWS CLI.
#
#  Returns:
#          0: - Success.
#
###############################################################################
function aws_cli_error_log() {
  local err_code=$1
  errecho "Error code : $err_code"
  if [ "$err_code" == 1 ]; then
    errecho "  One or more S3 transfers failed."
  elif [ "$err_code" == 2 ]; then
    errecho "  Command line failed to parse."
  elif [ "$err_code" == 130 ]; then
    errecho "  Process received SIGINT."
  elif [ "$err_code" == 252 ]; then
    errecho "  Command syntax invalid."
  elif [ "$err_code" == 253 ]; then
    errecho "  The system environment or configuration was invalid."
  elif [ "$err_code" == 254 ]; then
    errecho "  The service returned an error."
  elif [ "$err_code" == 255 ]; then
    errecho "  255 is a catch-all error."
  fi

  return 0
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.

- BatchWriteItem
- CreateTable
- DeleteItem
- DeleteTable
- DescribeTable
- GetItem
- PutItem
- Query
- Scan
- UpdateItem

HealthImaging exemplos de uso AWS CLI com o script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio do HealthImaging.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um datastore

O exemplo de código a seguir mostra como criar um armazenamento HealthImaging de dados.

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_create_datastore
#
# This function creates an AWS HealthImaging data store for importing DICOM P10
 files.
#
# Parameters:
#       -n data_store_name - The name of the data store.
#
# Returns:
#       The datastore ID.
#    And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function imaging_create_datastore() {
  local datastore_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_create_datastore"
    echo "Creates an AWS HealthImaging data store for importing DICOM P10 files."
    echo "  -n data_store_name - The name of the data store."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) datastore_name="${OPTARG}" ;;
      h)
        usage
```

```
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$datastore_name" ]]; then
    errecho "ERROR: You must provide a data store name with the -n parameter."
    usage
    return 1
  fi

  response=$(aws medical-imaging create-datastore \
    --datastore-name "$datastore_name" \
    --output text \
    --query 'datastoreId')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports medical-imaging create-datastore operation failed.
$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um datastore

O exemplo de código a seguir mostra como excluir um armazenamento HealthImaging de dados.

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_delete_datastore
#
# This function deletes an AWS HealthImaging data store.
#
# Parameters:
#       -i datastore_id - The ID of the data store.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function imaging_delete_datastore() {
  local datastore_id response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_delete_datastore"
    echo "Deletes an AWS HealthImaging data store."
    echo "  -i datastore_id - The ID of the data store."
    echo ""
```

```
  }

  # Retrieve the calling parameters.
  while getopts "i:h" option; do
    case "${option}" in
      i) datastore_id="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$datastore_id" ]]; then
    errecho "ERROR: You must provide a data store ID with the -i parameter."
    usage
    return 1
  fi

  response=$(aws medical-imaging delete-datastore \
    --datastore-id "$datastore_id")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports medical-imaging delete-datastore operation failed.
$response"
    return 1
  fi

  return 0
}
```

- Para obter detalhes da API, consulte DeleteDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do datastore

O exemplo de código a seguir mostra como obter propriedades do armazenamento de HealthImaging dados.

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_get_datastore
#
# Get a data store's properties.
#
# Parameters:
#       -i data_store_id - The ID of the data store.
#
# Returns:
#       [datastore_name, datastore_id, datastore_status, datastore_arn,  created_at,
 updated_at]
#    And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function imaging_get_datastore() {
  local datastore_id option OPTARG # Required to use getopts command in a function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
```

```
    echo "function imaging_get_datastore"
    echo "Gets a data store's properties."
    echo "  -i datastore_id - The ID of the data store."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "i:h" option; do
    case "${option}" in
      i) datastore_id="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$datastore_id" ]]; then
    errecho "ERROR: You must provide a data store ID with the -i parameter."
    usage
    return 1
  fi

  local response

  response=$(
    aws medical-imaging get-datastore \
      --datastore-id "$datastore_id" \
      --output text \
      --query "[ datastoreProperties.datastoreName,
datastoreProperties.datastoreId, datastoreProperties.datastoreStatus,
datastoreProperties.datastoreArn,  datastoreProperties.createdAt,
datastoreProperties.updatedAt]"
  )
  error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
```

```
    errecho "ERROR: AWS reports list-datastores operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte GetDatastoreem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar datastores

O exemplo de código a seguir mostra como listar armazenamentos HealthImaging de dados.

AWS CLI com script Bash

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function imaging_list_datastores
#
# List the HealthImaging data stores in the account.
#
# Returns:
#       [[datastore_name, datastore_id, datastore_status]]
#    And:
#       0 - If successful.
#       1 - If it fails.
```

```
###############################################################################
function imaging_list_datastores() {
  local option OPTARG # Required to use getopts command in a function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
    echo "function imaging_list_datastores"
    echo "Lists the AWS HealthImaging data stores in the account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "h" option; do
    case "${option}" in
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  local response
  response=$(aws medical-imaging list-datastores \
    --output text \
    --query "datastoreSummaries[*][datastoreName, datastoreId, datastoreStatus]")
  error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-datastores operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListDatastoresem Referência de AWS CLI Comandos.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos do IAM que usam a AWS CLI com script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio do IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_attach_role_policy
#
# This function attaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_attach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_attach_role_policy"
    echo "Attaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
```

```
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) role_name="${OPTARG}" ;;
    p) policy_arn="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$role_name" ]]; then
  errecho "ERROR: You must provide a role name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_arn" ]]; then
  errecho "ERROR: You must provide a policy ARN with the -p parameter."
  usage
  return 1
fi

response=$(aws iam attach-role-policy \
  --role-name "$role_name" \
  --policy-arn "$policy_arn")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports attach-role-policy operation failed.\n$response"
  return 1
fi
```

```
  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte AttachRolePolicyem Referência de AWS CLI Comandos.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_policy
#
# This function creates an IAM policy.
#
# Parameters:
#       -n policy_name -- The name of the IAM policy.
#       -p policy_json -- The policy document.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
```

```
function iam_create_policy() {
  local policy_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_policy"
    echo "Creates an AWS Identity and Access Management (IAM) policy."
    echo "  -n policy_name   The name of the IAM policy."
    echo "  -p policy_json -- The policy document."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) policy_name="${OPTARG}" ;;
      p) policy_document="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$policy_name" ]]; then
    errecho "ERROR: You must provide a policy name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_document" ]]; then
    errecho "ERROR: You must provide a policy document with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam create-policy \
```

```
    --policy-name "$policy_name" \
    --policy-document "$policy_document" \
    --output text \
    --query Policy.Arn)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"
}
```

- Para obter detalhes da API, consulte CreatePolicyem Referência de AWS CLI Comandos.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_role
```

```
#
# This function creates an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_json -- The assume role policy document.
#
# Returns:
#       The ARN of the role.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_role() {
  local role_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_json -- The assume role policy document."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_document="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1
```

```
  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_document" ]]; then
    errecho "ERROR: You must provide a policy document with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam create-role \
    --role-name "$role_name" \
    --assume-role-policy-document "$policy_document" \
    --output text \
    --query Role.Arn)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-role operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateRoleem Referência de AWS CLI Comandos.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_user
#
# This function creates the specified IAM user, unless
# it already exists.
```

```
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       The ARN of the user.
#     And:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_create_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user"
    echo "Creates an WS Identity and Access Management (IAM) user. You must supply a
 username:"
    echo "  -u user_name    The name of the user. It must be unique within the
 account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
```

```
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""

  # If the user already exists, we don't want to try to create it.
  if (iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name already exists in the account."
    return 1
  fi

  response=$(aws iam create-user --user-name "$user_name" \
    --output text \
    --query 'User.Arn')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-user operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte CreateUserem Referência de AWS CLI Comandos.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_create_user_access_key
#
# This function creates an IAM access key for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#       [-f file_name] -- The optional file name for the access key output.
#
# Returns:
#       [access_key_id access_key_secret]
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_user_access_key() {
  local user_name file_name response
```

```
local option OPTARG # Required to use getopts command in a function.

# bashsupport disable=BP5008
function usage() {
  echo "function iam_create_user_access_key"
  echo "Creates an AWS Identity and Access Management (IAM) key pair."
  echo "  -u user_name   The name of the IAM user."
  echo "  [-f file_name]   Optional file name for the access key output."
  echo ""
}

# Retrieve the calling parameters.
while getopts "u:f:h" option; do
  case "${option}" in
    u) user_name="${OPTARG}" ;;
    f) file_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$user_name" ]]; then
  errecho "ERROR: You must provide a username with the -u parameter."
  usage
  return 1
fi

response=$(aws iam create-access-key \
  --user-name "$user_name" \
  --output text)

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports create-access-key operation failed.$response"
```

```
    return 1
  fi

  if [[ -n "$file_name" ]]; then
    echo "$response" >"$file_name"
  fi

  local key_id key_secret
  # shellcheck disable=SC2086
  key_id=$(echo $response | cut -f 2 -d ' ')
  # shellcheck disable=SC2086
  key_secret=$(echo $response | cut -f 4 -d ' ')

  echo "$key_id $key_secret"

  return 0
}
```

- Para obter detalhes da API, consulte CreateAccessKeyem Referência de AWS CLI Comandos.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
```

```
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_policy
#
# This function deletes an IAM policy.
#
# Parameters:
#       -n policy_arn -- The name of the IAM policy arn.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_policy() {
  local policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_policy"
    echo "Deletes an WS Identity and Access Management (IAM) policy"
    echo "  -n policy_arn -- The name of the IAM policy arn."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
```

```
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy arn with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Policy arn:  $policy_arn"
  iecho ""

  response=$(aws iam delete-policy \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-policy operation failed.\n$response"
    return 1
  fi

  iecho "delete-policy response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeletePolicyem Referência de AWS CLI Comandos.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_role
#
# This function deletes an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_role() {
```

```
local role_name response
local option OPTARG # Required to use getopts command in a function.

# bashsupport disable=BP5008
function usage() {
  echo "function iam_delete_role"
  echo "Deletes an WS Identity and Access Management (IAM) role"
  echo "  -n role_name -- The name of the IAM role."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:h" option; do
  case "${option}" in
    n) role_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

echo "role_name:$role_name"
if [[ -z "$role_name" ]]; then
  errecho "ERROR: You must provide a role name with the -n parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    Role name:  $role_name"
iecho ""

response=$(aws iam delete-role \
  --role-name "$role_name")

local error_code=${?}
```

```
  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-role operation failed.\n$response"
    return 1
  fi

  iecho "delete-role response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteRoleem Referência de AWS CLI Comandos.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
```

```
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_user
#
# This function deletes the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_user"
    echo "Deletes an WS Identity and Access Management (IAM) user. You must supply a
 username:"
    echo "  -u user_name    The name of the user."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
```

```
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""

  # If the user does not exist, we don't want to try to delete it.
  if (! iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name does not exist in the account."
    return 1
  fi

  response=$(aws iam delete-user \
    --user-name "$user_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-user operation failed.$response"
    return 1
  fi

  iecho "delete-user response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteUserem Referência de AWS CLI Comandos.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_delete_access_key
#
# This function deletes an IAM access key for the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user.
#       -k access_key -- The access key to delete.
#
```

```
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_delete_access_key() {
  local user_name access_key response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_access_key"
    echo "Deletes an WS Identity and Access Management (IAM) access key for the
 specified IAM user"
    echo "  -u user_name    The name of the user."
    echo "  -k access_key   The access key to delete."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:k:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      k) access_key="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  if [[ -z "$access_key" ]]; then
    errecho "ERROR: You must provide an access key with the -k parameter."
```

```
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Username:   $user_name"
  iecho "    Access key:   $access_key"
  iecho ""

  response=$(aws iam delete-access-key \
    --user-name "$user_name" \
    --access-key-id "$access_key")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-access-key operation failed.\n$response"
    return 1
  fi

  iecho "delete-access-key response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte DeleteAccessKeyem Referência de AWS CLI Comandos.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_detach_role_policy
#
# This function detaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_detach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_detach_role_policy"
    echo "Detaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
```

```
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam detach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports detach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte DetachRolePolicyem Referência de AWS CLI Comandos.

Obter um usuário

O exemplo de código a seguir mostra como obter um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_user_exists
#
# This function checks to see if the specified AWS Identity and Access Management
 (IAM) user already exists.
#
# Parameters:
#       $1 - The name of the IAM user to check.
#
# Returns:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
###############################################################################
```

```
function iam_user_exists() {
  local user_name
  user_name=$1

  # Check whether the IAM user already exists.
  # We suppress all output - we're interested only in the return code.

  local errors
  errors=$(aws iam get-user \
    --user-name "$user_name" 2>&1 >/dev/null)

  local error_code=${?}

  if [[ $error_code -eq 0 ]]; then
    return 0 # 0 in Bash script means true.
  else
    if [[ $errors != *"error"*"(NoSuchEntity)"* ]]; then
      aws_cli_error_log $error_code
      errecho "Error calling iam get-user $errors"
    fi

    return 1 # 1 in Bash script means false.
  fi
}
```

- Para obter detalhes da API, consulte GetUserem Referência de AWS CLI Comandos.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_list_access_keys
#
# This function lists the access keys for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#
# Returns:
#       access_key_ids
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_list_access_keys() {

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_list_access_keys"
    echo "Lists the AWS Identity and Access Management (IAM) access key IDs for the
 specified user."
    echo "  -u user_name   The name of the IAM user."
    echo ""
  }
```

```
  local user_name response
  local option OPTARG # Required to use getopts command in a function.
  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  response=$(aws iam list-access-keys \
    --user-name "$user_name" \
    --output text \
    --query 'AccessKeyMetadata[].AccessKeyId')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-access-keys operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListAccessKeysem Referência de AWS CLI Comandos.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function iam_list_users
#
# List the IAM users in the account.
#
# Returns:
#       The list of users names
#    And:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
###############################################################################
```

```
function iam_list_users() {
  local option OPTARG # Required to use getopts command in a function.
  local error_code
  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_list_users"
    echo "Lists the AWS Identity and Access Management (IAM) user in the account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "h" option; do
    case "${option}" in
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  local response

  response=$(aws iam list-users \
    --output text \
    --query "Users[].UserName")
  error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports list-users operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte ListUsersem Referência de AWS CLI Comandos.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

AWS CLI com script Bash

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iam_create_user_assume_role
#
# Scenario to create an IAM user, create an IAM role, and apply the role to the
 user.
#
#     "IAM access" permissions are needed to run this code.
#     "STS assume role" permissions are needed to run this code. (Note: It might be
 necessary to
```

```
#           create a custom policy).
#
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
##############################################################################
function iam_create_user_assume_role() {
  {
    if [ "$IAM_OPERATIONS_SOURCED" != "True" ]; then

      source ./iam_operations.sh
    fi
  }

  echo_repeat "*" 88
  echo "Welcome to the IAM create user and assume role demo."
  echo
  echo "This demo will create an IAM user, create an IAM role, and apply the role to
 the user."
  echo_repeat "*" 88
  echo

  echo -n "Enter a name for a new IAM user: "
  get_input
  user_name=$get_input_result

  local user_arn
  user_arn=$(iam_create_user -u "$user_name")

  # shellcheck disable=SC2181
  if [[ ${?} == 0 ]]; then
    echo "Created demo IAM user named $user_name"
  else
    errecho "$user_arn"
    errecho "The user failed to create. This demo will exit."
    return 1
  fi

  local access_key_response
  access_key_response=$(iam_create_user_access_key -u "$user_name")
  # shellcheck disable=SC2181
  if [[ ${?} != 0 ]]; then
    errecho "The access key failed to create. This demo will exit."
    clean_up "$user_name"
```

```
  return 1
fi

IFS=$'\t ' read -r -a access_key_values <<<"$access_key_response"
local key_name=${access_key_values[0]}
local key_secret=${access_key_values[1]}

echo "Created access key named $key_name"

echo "Wait 10 seconds for the user to be ready."
sleep 10
echo_repeat "*" 88
echo

local iam_role_name
iam_role_name=$(generate_random_name "test-role")
echo "Creating a role named $iam_role_name with user $user_name as the principal."

local assume_role_policy_document="{
  \"Version\": \"2012-10-17\",
  \"Statement\": [{
      \"Effect\": \"Allow\",
      \"Principal\": {\"AWS\": \"$user_arn\"},
      \"Action\": \"sts:AssumeRole\"
      }]
  }"

local role_arn
role_arn=$(iam_create_role -n "$iam_role_name" -p "$assume_role_policy_document")

# shellcheck disable=SC2181
if [ ${?} == 0 ]; then
  echo "Created IAM role named $iam_role_name"
else
  errecho "The role failed to create. This demo will exit."
  clean_up "$user_name" "$key_name"
  return 1
fi

local policy_name
policy_name=$(generate_random_name "test-policy")
local policy_document="{
              \"Version\": \"2012-10-17\",
              \"Statement\": [{
```

```
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]}"

  local policy_arn
  policy_arn=$(iam_create_policy -n "$policy_name" -p "$policy_document")
  # shellcheck disable=SC2181
  if [[ ${?} == 0 ]]; then
    echo "Created  IAM policy named $policy_name"
  else
    errecho "The policy failed to create."
    clean_up "$user_name" "$key_name" "$iam_role_name"
    return 1
  fi

  if (iam_attach_role_policy -n "$iam_role_name" -p "$policy_arn"); then
    echo "Attached policy $policy_arn to role $iam_role_name"
  else
    errecho "The policy failed to attach."
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn"
    return 1
  fi

  local assume_role_policy_document="{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"$role_arn\"}]}"

  local assume_role_policy_name
  assume_role_policy_name=$(generate_random_name "test-assume-role-")

  # shellcheck disable=SC2181
  local assume_role_policy_arn
  assume_role_policy_arn=$(iam_create_policy -n "$assume_role_policy_name" -p
"$assume_role_policy_document")
  # shellcheck disable=SC2181
  if [ ${?} == 0 ]; then
    echo "Created  IAM policy named $assume_role_policy_name for sts assume role"
  else
    errecho "The policy failed to create."
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn" "$policy_arn"
    return 1
```

```
 fi

 echo "Wait 10 seconds to give AWS time to propagate these new resources and
connections."
 sleep 10
 echo_repeat "*" 88
 echo

 echo "Try to list buckets without the new user assuming the role."
 echo_repeat "*" 88
 echo

 # Set the environment variables for the created user.
 # bashsupport disable=BP2001
 export AWS_ACCESS_KEY_ID=$key_name
 # bashsupport disable=BP2001
 export AWS_SECRET_ACCESS_KEY=$key_secret

 local buckets
 buckets=$(s3_list_buckets)

 # shellcheck disable=SC2181
 if [ ${?} == 0 ]; then
   local bucket_count
   bucket_count=$(echo "$buckets" | wc -w | xargs)
   echo "There are $bucket_count buckets in the account. This should not have
happened."
 else
   errecho "Because the role with permissions has not been assumed, listing buckets
failed."
 fi

 echo
 echo_repeat "*" 88
 echo "Now assume the role $iam_role_name and list the buckets."
 echo_repeat "*" 88
 echo

 local credentials

 credentials=$(sts_assume_role -r "$role_arn" -n "AssumeRoleDemoSession")
 # shellcheck disable=SC2181
 if [ ${?} == 0 ]; then
   echo "Assumed role $iam_role_name"
```

```
  else
    errecho "Failed to assume role."
    export AWS_ACCESS_KEY_ID=""
    export AWS_SECRET_ACCESS_KEY=""
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn" "$policy_arn"
"$assume_role_policy_arn"
    return 1
  fi

  IFS=$'\t ' read -r -a credentials <<<"$credentials"

  export AWS_ACCESS_KEY_ID=${credentials[0]}
  export AWS_SECRET_ACCESS_KEY=${credentials[1]}
  # bashsupport disable=BP2001
  export AWS_SESSION_TOKEN=${credentials[2]}

  buckets=$(s3_list_buckets)

  # shellcheck disable=SC2181
  if [ ${?} == 0 ]; then
    local bucket_count
    bucket_count=$(echo "$buckets" | wc -w | xargs)
    echo "There are $bucket_count buckets in the account. Listing buckets succeeded
because of "
    echo "the assumed role."
  else
    errecho "Failed to list buckets. This should not happen."
    export AWS_ACCESS_KEY_ID=""
    export AWS_SECRET_ACCESS_KEY=""
    export AWS_SESSION_TOKEN=""
    clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn" "$policy_arn"
"$assume_role_policy_arn"
    return 1
  fi

  local result=0
  export AWS_ACCESS_KEY_ID=""
  export AWS_SECRET_ACCESS_KEY=""

  echo
  echo_repeat "*" 88
  echo "The created resources will now be deleted."
  echo_repeat "*" 88
  echo
```

```
  clean_up "$user_name" "$key_name" "$iam_role_name" "$policy_arn" "$policy_arn"
 "$assume_role_policy_arn"

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    result=1
  fi

  return $result
}
```

As funções do IAM usadas nesse cenário.

```
###############################################################################
# function iam_user_exists
#
# This function checks to see if the specified AWS Identity and Access Management
 (IAM) user already exists.
#
# Parameters:
#       $1 - The name of the IAM user to check.
#
# Returns:
#       0 - If the user already exists.
#       1 - If the user doesn't exist.
###############################################################################
function iam_user_exists() {
  local user_name
  user_name=$1

  # Check whether the IAM user already exists.
  # We suppress all output - we're interested only in the return code.

  local errors
  errors=$(aws iam get-user \
    --user-name "$user_name" 2>&1 >/dev/null)

  local error_code=${?}

  if [[ $error_code -eq 0 ]]; then
    return 0 # 0 in Bash script means true.
```

```
  else
    if [[ $errors != *"error"*"(NoSuchEntity)"* ]]; then
      aws_cli_error_log $error_code
      errecho "Error calling iam get-user $errors"
    fi

    return 1 # 1 in Bash script means false.
  fi
}

###############################################################################
# function iam_create_user
#
# This function creates the specified IAM user, unless
# it already exists.
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       The ARN of the user.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user"
    echo "Creates an WS Identity and Access Management (IAM) user. You must supply a
 username:"
    echo "  -u user_name    The name of the user. It must be unique within the
 account."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      h)
```

```
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    User name:   $user_name"
  iecho ""

  # If the user already exists, we don't want to try to create it.
  if (iam_user_exists "$user_name"); then
    errecho "ERROR: A user with that name already exists in the account."
    return 1
  fi

  response=$(aws iam create-user --user-name "$user_name" \
    --output text \
    --query 'User.Arn')

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-user operation failed.$response"
    return 1
  fi

  echo "$response"

  return 0
}
```

```
###############################################################################
# function iam_create_user_access_key
#
# This function creates an IAM access key for the specified user.
#
# Parameters:
#       -u user_name -- The name of the IAM user.
#       [-f file_name] -- The optional file name for the access key output.
#
# Returns:
#       [access_key_id access_key_secret]
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_user_access_key() {
  local user_name file_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) key pair."
    echo "  -u user_name   The name of the IAM user."
    echo "  [-f file_name]   Optional file name for the access key output."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:f:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      f) file_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
```

```
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  response=$(aws iam create-access-key \
    --user-name "$user_name" \
    --output text)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-access-key operation failed.$response"
    return 1
  fi

  if [[ -n "$file_name" ]]; then
    echo "$response" >"$file_name"
  fi

  local key_id key_secret
  # shellcheck disable=SC2086
  key_id=$(echo $response | cut -f 2 -d ' ')
  # shellcheck disable=SC2086
  key_secret=$(echo $response | cut -f 4 -d ' ')

  echo "$key_id $key_secret"

  return 0
}

###############################################################################
# function iam_create_role
#
# This function creates an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_json -- The assume role policy document.
```

```
#
# Returns:
#       The ARN of the role.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_role() {
  local role_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_create_user_access_key"
    echo "Creates an AWS Identity and Access Management (IAM) role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_json -- The assume role policy document."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_document="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi
```

```
  if [[ -z "$policy_document" ]]; then
    errecho "ERROR: You must provide a policy document with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam create-role \
    --role-name "$role_name" \
    --assume-role-policy-document "$policy_document" \
    --output text \
    --query Role.Arn)

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-role operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_create_policy
#
# This function creates an IAM policy.
#
# Parameters:
#       -n policy_name -- The name of the IAM policy.
#       -p policy_json -- The policy document.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_create_policy() {
  local policy_name policy_document response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
```

```
  echo "function iam_create_policy"
  echo "Creates an AWS Identity and Access Management (IAM) policy."
  echo "  -n policy_name   The name of the IAM policy."
  echo "  -p policy_json -- The policy document."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:p:h" option; do
  case "${option}" in
    n) policy_name="${OPTARG}" ;;
    p) policy_document="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$policy_name" ]]; then
  errecho "ERROR: You must provide a policy name with the -n parameter."
  usage
  return 1
fi

if [[ -z "$policy_document" ]]; then
  errecho "ERROR: You must provide a policy document with the -p parameter."
  usage
  return 1
fi

response=$(aws iam create-policy \
  --policy-name "$policy_name" \
  --policy-document "$policy_document" \
  --output text \
  --query Policy.Arn)

local error_code=${?}
```

```
  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"
}

###############################################################################
# function iam_attach_role_policy
#
# This function attaches an IAM policy to a tole.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_attach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_attach_role_policy"
    echo "Attaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
```

```
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam attach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports attach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_detach_role_policy
#
# This function detaches an IAM policy to a tole.
```

```
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#       -p policy_ARN -- The IAM policy document ARN..
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_detach_role_policy() {
  local role_name policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_detach_role_policy"
    echo "Detaches an AWS Identity and Access Management (IAM) policy to an IAM
 role."
    echo "  -n role_name   The name of the IAM role."
    echo "  -p policy_ARN -- The IAM policy document ARN."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:p:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      p) policy_arn="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
```

```
    return 1
  fi

  if [[ -z "$policy_arn" ]]; then
    errecho "ERROR: You must provide a policy ARN with the -p parameter."
    usage
    return 1
  fi

  response=$(aws iam detach-role-policy \
    --role-name "$role_name" \
    --policy-arn "$policy_arn")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports detach-role-policy operation failed.\n$response"
    return 1
  fi

  echo "$response"

  return 0
}

###############################################################################
# function iam_delete_policy
#
# This function deletes an IAM policy.
#
# Parameters:
#       -n policy_arn -- The name of the IAM policy arn.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_policy() {
  local policy_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
```

```
  echo "function iam_delete_policy"
  echo "Deletes an WS Identity and Access Management (IAM) policy"
  echo "  -n policy_arn -- The name of the IAM policy arn."
  echo ""
}

# Retrieve the calling parameters.
while getopts "n:h" option; do
  case "${option}" in
    n) policy_arn="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$policy_arn" ]]; then
  errecho "ERROR: You must provide a policy arn with the -n parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    Policy arn:  $policy_arn"
iecho ""

response=$(aws iam delete-policy \
  --policy-arn "$policy_arn")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
  errecho "ERROR: AWS reports delete-policy operation failed.\n$response"
  return 1
fi
```

```
  iecho "delete-policy response:$response"
  iecho

  return 0
}

##############################################################################
# function iam_delete_role
#
# This function deletes an IAM role.
#
# Parameters:
#       -n role_name -- The name of the IAM role.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function iam_delete_role() {
  local role_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_role"
    echo "Deletes an WS Identity and Access Management (IAM) role"
    echo "  -n role_name -- The name of the IAM role."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "n:h" option; do
    case "${option}" in
      n) role_name="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
```

```
  done
  export OPTIND=1

  echo "role_name:$role_name"
  if [[ -z "$role_name" ]]; then
    errecho "ERROR: You must provide a role name with the -n parameter."
    usage
    return 1
  fi

  iecho "Parameters:\n"
  iecho "    Role name:  $role_name"
  iecho ""

  response=$(aws iam delete-role \
    --role-name "$role_name")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-role operation failed.\n$response"
    return 1
  fi

  iecho "delete-role response:$response"
  iecho

  return 0
}

###############################################################################
# function iam_delete_access_key
#
# This function deletes an IAM access key for the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user.
#       -k access_key -- The access key to delete.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
```

```
function iam_delete_access_key() {
  local user_name access_key response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_access_key"
    echo "Deletes an WS Identity and Access Management (IAM) access key for the
 specified IAM user"
    echo "  -u user_name    The name of the user."
    echo "  -k access_key   The access key to delete."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "u:k:h" option; do
    case "${option}" in
      u) user_name="${OPTARG}" ;;
      k) access_key="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done
  export OPTIND=1

  if [[ -z "$user_name" ]]; then
    errecho "ERROR: You must provide a username with the -u parameter."
    usage
    return 1
  fi

  if [[ -z "$access_key" ]]; then
    errecho "ERROR: You must provide an access key with the -k parameter."
    usage
    return 1
  fi
```

```
  iecho "Parameters:\n"
  iecho "    Username:   $user_name"
  iecho "    Access key:   $access_key"
  iecho ""

  response=$(aws iam delete-access-key \
    --user-name "$user_name" \
    --access-key-id "$access_key")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports delete-access-key operation failed.\n$response"
    return 1
  fi

  iecho "delete-access-key response:$response"
  iecho

  return 0
}

###############################################################################
# function iam_delete_user
#
# This function deletes the specified IAM user.
#
# Parameters:
#       -u user_name  -- The name of the user to create.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function iam_delete_user() {
  local user_name response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function iam_delete_user"
    echo "Deletes an WS Identity and Access Management (IAM) user. You must supply a
 username:"
```

```
  echo "  -u user_name    The name of the user."
  echo ""
}

# Retrieve the calling parameters.
while getopts "u:h" option; do
  case "${option}" in
    u) user_name="${OPTARG}" ;;
    h)
      usage
      return 0
      ;;
    \?)
      echo "Invalid parameter"
      usage
      return 1
      ;;
  esac
done
export OPTIND=1

if [[ -z "$user_name" ]]; then
  errecho "ERROR: You must provide a username with the -u parameter."
  usage
  return 1
fi

iecho "Parameters:\n"
iecho "    User name:   $user_name"
iecho ""

# If the user does not exist, we don't want to try to delete it.
if (! iam_user_exists "$user_name"); then
  errecho "ERROR: A user with that name does not exist in the account."
  return 1
fi

response=$(aws iam delete-user \
  --user-name "$user_name")

local error_code=${?}

if [[ $error_code -ne 0 ]]; then
  aws_cli_error_log $error_code
```

```
    errecho "ERROR: AWS reports delete-user operation failed.$response"
    return 1
  fi

  iecho "delete-user response:$response"
  iecho

  return 0
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos do Amazon S3 de uso da AWS CLI com script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio do Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function copy_item_in_bucket
#
# This function creates a copy of the specified file in the same bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file from and to.
#       $2 - The key of the source file to copy.
#       $3 - The key of the destination file.
#
# Returns:
```

```
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function copy_item_in_bucket() {
  local bucket_name=$1
  local source_key=$2
  local destination_key=$3
  local response

  response=$(aws s3api copy-object \
    --bucket "$bucket_name" \
    --copy-source "$bucket_name/$source_key" \
    --key "$destination_key")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api copy-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte CopyObjectem Referência de AWS CLI Comandos.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
##############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
##############################################################################
```

```
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function create-bucket
#
# This function creates the specified bucket in the specified AWS Region, unless
# it already exists.
#
# Parameters:
#       -b bucket_name  -- The name of the bucket to create.
#       -r region_code  -- The code for an AWS Region in which to
#                          create the bucket.
#
# Returns:
#       The URL of the bucket that was created.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function create_bucket() {
  local bucket_name region_code response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function create_bucket"
    echo "Creates an Amazon S3 bucket. You must supply a bucket name:"
    echo "  -b bucket_name    The name of the bucket. It must be globally unique."
    echo "  [-r region_code]    The code for an AWS Region in which the bucket is
 created."
    echo ""
```

```
  }

  # Retrieve the calling parameters.
  while getopts "b:r:h" option; do
    case "${option}" in
      b) bucket_name="${OPTARG}" ;;
      r) region_code="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done

  if [[ -z "$bucket_name" ]]; then
    errecho "ERROR: You must provide a bucket name with the -b parameter."
    usage
    return 1
  fi

  local bucket_config_arg
  # A location constraint for "us-east-1" returns an error.
  if [[ -n "$region_code" ]] && [[ "$region_code" != "us-east-1" ]]; then
    bucket_config_arg="--create-bucket-configuration LocationConstraint=
$region_code"
  fi

  iecho "Parameters:\n"
  iecho "    Bucket name:   $bucket_name"
  iecho "    Region code:   $region_code"
  iecho ""

  # If the bucket already exists, we don't want to try to create it.
  if (bucket_exists "$bucket_name"); then
    errecho "ERROR: A bucket with that name already exists. Try again."
    return 1
  fi

  # shellcheck disable=SC2086
```

```
  response=$(aws s3api create-bucket \
    --bucket "$bucket_name" \
    $bucket_config_arg)

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports create-bucket operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte CreateBucketem Referência de AWS CLI Comandos.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function delete_bucket
#
# This function deletes the specified bucket.
#
# Parameters:
```

```
#       $1 - The name of the bucket.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api delete-bucket \
    --bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR: AWS reports s3api delete-bucket failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteBucketem Referência de AWS CLI Comandos.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
```

```
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function delete_item_in_bucket
#
# This function deletes the specified file from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - The key (file name) in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_item_in_bucket() {
  local bucket_name=$1
  local key=$2
  local response

  response=$(aws s3api delete-object \
    --bucket "$bucket_name" \
    --key "$key")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteObjectem Referência de AWS CLI Comandos.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function delete_items_in_bucket
#
# This function deletes the specified list of keys from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - A list of keys in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function delete_items_in_bucket() {
  local bucket_name=$1
  local keys=$2
  local response

  # Create the JSON for the items to delete.
  local delete_items
  delete_items="{\"Objects\":["
  for key in $keys; do
    delete_items="$delete_items{\"Key\": \"$key\"},"
  done
  delete_items=${delete_items%?} # Remove the final comma.
```

```
  delete_items="$delete_items]}"

  response=$(aws s3api delete-objects \
    --bucket "$bucket_name" \
    --delete "$delete_items")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte DeleteObjectsem Referência de AWS CLI Comandos.

Determinar a existência de um bucket

O exemplo de código a seguir mostra como determinar a existência de um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function bucket_exists
#
# This function checks to see if the specified bucket already exists.
#
# Parameters:
#       $1 - The name of the bucket to check.
#
# Returns:
#       0 - If the bucket already exists.
#       1 - If the bucket doesn't exist.
###############################################################################
function bucket_exists() {
  local bucket_name
```

```
  bucket_name=$1

  # Check whether the bucket already exists.
  # We suppress all output - we're interested only in the return code.

  if aws s3api head-bucket \
    --bucket "$bucket_name" \
    >/dev/null 2>&1; then
    return 0 # 0 in Bash script means true.
  else
    return 1 # 1 in Bash script means false.
  fi
}
```

- Para obter detalhes da API, consulte HeadBucketem Referência de AWS CLI Comandos.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function download_object_from_bucket
#
# This function downloads an object in a bucket to a file.
```

```
#
# Parameters:
#       $1 - The name of the bucket to download the object from.
#       $2 - The path and file name to store the downloaded bucket.
#       $3 - The key (name) of the object in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function download_object_from_bucket() {
  local bucket_name=$1
  local destination_file_name=$2
  local object_name=$3
  local response

  response=$(aws s3api get-object \
    --bucket "$bucket_name" \
    --key "$object_name" \
    "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte GetObjectem Referência de AWS CLI Comandos.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function list_items_in_bucket
#
# This function displays a list of the files in the bucket with each file's
# size. The function uses the --query parameter to retrieve only the key and
# size fields from the Contents collection.
#
# Parameters:
#       $1 - The name of the bucket.
#
# Returns:
#       The list of files in text format.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function list_items_in_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api list-objects \
    --bucket "$bucket_name" \
    --output text \
    --query 'Contents[].{Key: Key, Size: Size}')

  # shellcheck disable=SC2181
  if [[ ${?} -eq 0 ]]; then
    echo "$response"
  else
    errecho "ERROR: AWS reports s3api list-objects operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência de AWS CLI Comandos.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function copy_file_to_bucket
#
# This function creates a file in the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file to.
#       $2 - The path and file name of the local file to copy to the bucket.
#       $3 - The key (name) to call the copy of the file in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_file_to_bucket() {
  local response bucket_name source_file destination_file_name
  bucket_name=$1
  source_file=$2
  destination_file_name=$3
```

```
  response=$(aws s3api put-object \
    --bucket "$bucket_name" \
    --body "$source_file" \
    --key "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte PutObjectem Referência de AWS CLI Comandos.

Cenários

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function s3_getting_started
#
```

```
# This function creates, copies, and deletes S3 buckets and objects.
#
# Returns:
#       0 - If successful.
#       1 - If an error occurred.
###############################################################################
function s3_getting_started() {
  {
    if [ "$BUCKET_OPERATIONS_SOURCED" != "True" ]; then
      cd bucket-lifecycle-operations || exit

      source ./bucket_operations.sh
      cd ..
    fi
  }

  echo_repeat "*" 88
  echo "Welcome to the Amazon S3 getting started demo."
  echo_repeat "*" 88

  local bucket_name
  bucket_name=$(generate_random_name "doc-example-bucket")

  local region_code
  region_code=$(aws configure get region)

  if create_bucket -b "$bucket_name" -r "$region_code"; then
    echo "Created demo bucket named $bucket_name"
  else
    errecho "The bucket failed to create. This demo will exit."
    return 1
  fi

  local file_name
  while [ -z "$file_name" ]; do
    echo -n "Enter a file you want to upload to your bucket: "
    get_input
    file_name=$get_input_result

    if [ ! -f "$file_name" ]; then
      echo "Could not find file $file_name. Are you sure it exists?"
      file_name=""
    fi
  done
```

```
  local key
  key="$(basename "$file_name")"

  local result=0
  if copy_file_to_bucket "$bucket_name" "$file_name" "$key"; then
    echo "Uploaded file $file_name into bucket $bucket_name with key $key."
  else
    result=1
  fi

  local destination_file
  destination_file="$file_name.download"
  if yes_no_input "Would you like to download $key to the file $destination_file?
 (y/n) "; then
    if download_object_from_bucket "$bucket_name" "$destination_file" "$key"; then
      echo "Downloaded $key in the bucket $bucket_name to the file
 $destination_file."
    else
      result=1
    fi
  fi

  if yes_no_input "Would you like to copy $key a new object key in your bucket? (y/
n) "; then
    local to_key
    to_key="demo/$key"
    if copy_item_in_bucket "$bucket_name" "$key" "$to_key"; then
      echo "Copied $key in the bucket $bucket_name to the  $to_key."
    else
      result=1
    fi
  fi

  local bucket_items
  bucket_items=$(list_items_in_bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    result=1
  fi

  echo "Your bucket contains the following items."
  echo -e "Name\t\tSize"
```

```
  echo "$bucket_items"

  if yes_no_input "Delete the bucket, $bucket_name, as well as the objects in it?
 (y/n) "; then
    bucket_items=$(echo "$bucket_items" | cut -f 1)

    if delete_items_in_bucket "$bucket_name" "$bucket_items"; then
      echo "The following items were deleted from the bucket $bucket_name"
      echo "$bucket_items"
    else
      result=1
    fi

    if delete_bucket "$bucket_name"; then
      echo "Deleted the bucket $bucket_name"
    else
      result=1
    fi
  fi

  return $result
}
```

As funções do Amazon S3 usadas nesse cenário.

```
###############################################################################
# function create-bucket
#
# This function creates the specified bucket in the specified AWS Region, unless
# it already exists.
#
# Parameters:
#       -b bucket_name  -- The name of the bucket to create.
#       -r region_code  -- The code for an AWS Region in which to
#                          create the bucket.
#
# Returns:
#       The URL of the bucket that was created.
#     And:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
```

```
function create_bucket() {
  local bucket_name region_code response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function create_bucket"
    echo "Creates an Amazon S3 bucket. You must supply a bucket name:"
    echo "  -b bucket_name    The name of the bucket. It must be globally unique."
    echo "  [-r region_code]    The code for an AWS Region in which the bucket is
 created."
    echo ""
  }

  # Retrieve the calling parameters.
  while getopts "b:r:h" option; do
    case "${option}" in
      b) bucket_name="${OPTARG}" ;;
      r) region_code="${OPTARG}" ;;
      h)
        usage
        return 0
        ;;
      \?)
        echo "Invalid parameter"
        usage
        return 1
        ;;
    esac
  done

  if [[ -z "$bucket_name" ]]; then
    errecho "ERROR: You must provide a bucket name with the -b parameter."
    usage
    return 1
  fi

  local bucket_config_arg
  # A location constraint for "us-east-1" returns an error.
  if [[ -n "$region_code" ]] && [[ "$region_code" != "us-east-1" ]]; then
    bucket_config_arg="--create-bucket-configuration LocationConstraint=
$region_code"
  fi
```

```
  iecho "Parameters:\n"
  iecho "    Bucket name:   $bucket_name"
  iecho "    Region code:   $region_code"
  iecho ""

  # If the bucket already exists, we don't want to try to create it.
  if (bucket_exists "$bucket_name"); then
    errecho "ERROR: A bucket with that name already exists. Try again."
    return 1
  fi

  # shellcheck disable=SC2086
  response=$(aws s3api create-bucket \
    --bucket "$bucket_name" \
    $bucket_config_arg)

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports create-bucket operation failed.\n$response"
    return 1
  fi
}

###############################################################################
# function copy_file_to_bucket
#
# This function creates a file in the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file to.
#       $2 - The path and file name of the local file to copy to the bucket.
#       $3 - The key (name) to call the copy of the file in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_file_to_bucket() {
  local response bucket_name source_file destination_file_name
  bucket_name=$1
  source_file=$2
  destination_file_name=$3

  response=$(aws s3api put-object \
```

```
    --bucket "$bucket_name" \
    --body "$source_file" \
    --key "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}

################################################################################
# function download_object_from_bucket
#
# This function downloads an object in a bucket to a file.
#
# Parameters:
#       $1 - The name of the bucket to download the object from.
#       $2 - The path and file name to store the downloaded bucket.
#       $3 - The key (name) of the object in the bucket.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
################################################################################
function download_object_from_bucket() {
  local bucket_name=$1
  local destination_file_name=$2
  local object_name=$3
  local response

  response=$(aws s3api get-object \
    --bucket "$bucket_name" \
    --key "$object_name" \
    "$destination_file_name")

  # shellcheck disable=SC2181
  if [[ ${?} -ne 0 ]]; then
    errecho "ERROR: AWS reports put-object operation failed.\n$response"
    return 1
  fi
}

################################################################################
```

```
# function copy_item_in_bucket
#
# This function creates a copy of the specified file in the same bucket.
#
# Parameters:
#       $1 - The name of the bucket to copy the file from and to.
#       $2 - The key of the source file to copy.
#       $3 - The key of the destination file.
#
# Returns:
#       0 - If successful.
#       1 - If it fails.
###############################################################################
function copy_item_in_bucket() {
  local bucket_name=$1
  local source_key=$2
  local destination_key=$3
  local response

  response=$(aws s3api copy-object \
    --bucket "$bucket_name" \
    --copy-source "$bucket_name/$source_key" \
    --key "$destination_key")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api copy-object operation failed.\n$response"
    return 1
  fi
}

###############################################################################
# function list_items_in_bucket
#
# This function displays a list of the files in the bucket with each file's
# size. The function uses the --query parameter to retrieve only the key and
# size fields from the Contents collection.
#
# Parameters:
#       $1 - The name of the bucket.
#
# Returns:
#       The list of files in text format.
#     And:
```

```
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function list_items_in_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api list-objects \
    --bucket "$bucket_name" \
    --output text \
    --query 'Contents[].{Key: Key, Size: Size}')

  # shellcheck disable=SC2181
  if [[ ${?} -eq 0 ]]; then
    echo "$response"
  else
    errecho "ERROR: AWS reports s3api list-objects operation failed.\n$response"
    return 1
  fi
}

##############################################################################
# function delete_items_in_bucket
#
# This function deletes the specified list of keys from the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.
#       $2 - A list of keys in the bucket to delete.

# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function delete_items_in_bucket() {
  local bucket_name=$1
  local keys=$2
  local response

  # Create the JSON for the items to delete.
  local delete_items
  delete_items="{\"Objects\":["
  for key in $keys; do
    delete_items="$delete_items{\"Key\": \"$key\"},"
```

```
  done
  delete_items=${delete_items%?} # Remove the final comma.
  delete_items="$delete_items]}"

  response=$(aws s3api delete-objects \
    --bucket "$bucket_name" \
    --delete "$delete_items")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR:  AWS reports s3api delete-object operation failed.\n$response"
    return 1
  fi
}

##############################################################################
# function delete_bucket
#
# This function deletes the specified bucket.
#
# Parameters:
#       $1 - The name of the bucket.

# Returns:
#       0 - If successful.
#       1 - If it fails.
##############################################################################
function delete_bucket() {
  local bucket_name=$1
  local response

  response=$(aws s3api delete-bucket \
    --bucket "$bucket_name")

  # shellcheck disable=SC2181
  if [[ $? -ne 0 ]]; then
    errecho "ERROR: AWS reports s3api delete-bucket failed.\n$response"
    return 1
  fi
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência de comandos da AWS CLI.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Exemplos do AWS STS de uso da AWS CLI com script Bash

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS Command Line Interface com script Bash por meio do AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

AWS CLI com script Bash

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
###############################################################################
# function iecho
#
# This function enables the script to display the specified text only if
# the global variable $VERBOSE is set to true.
###############################################################################
function iecho() {
  if [[ $VERBOSE == true ]]; then
    echo "$@"
  fi
}

###############################################################################
# function errecho
#
# This function outputs everything sent to it to STDERR (standard error output).
###############################################################################
function errecho() {
  printf "%s\n" "$*" 1>&2
}

###############################################################################
# function sts_assume_role
#
# This function assumes a role in the AWS account and returns the temporary
#  credentials.
#
# Parameters:
#       -n role_session_name -- The name of the session.
#       -r role_arn -- The ARN of the role to assume.
#
# Returns:
#       [access_key_id, secret_access_key, session_token]
#     And:
```

```
#       0 - If successful.
#       1 - If an error occurred.
##############################################################################
function sts_assume_role() {
  local role_session_name role_arn response
  local option OPTARG # Required to use getopts command in a function.

  # bashsupport disable=BP5008
  function usage() {
    echo "function sts_assume_role"
    echo "Assumes a role in the AWS account and returns the temporary credentials:"
    echo "  -n role_session_name -- The name of the session."
    echo "  -r role_arn -- The ARN of the role to assume."
    echo ""
  }

  while getopts n:r:h option; do
    case "${option}" in
      n) role_session_name=${OPTARG} ;;
      r) role_arn=${OPTARG} ;;
      h)
        usage
        return 0
        ;;
      \?)
        ech o"Invalid parameter"
        usage
        return 1
        ;;
    esac
  done

  response=$(aws sts assume-role \
    --role-session-name "$role_session_name" \
    --role-arn "$role_arn" \
    --output text \
    --query "Credentials.[AccessKeyId, SecretAccessKey, SessionToken]")

  local error_code=${?}

  if [[ $error_code -ne 0 ]]; then
    aws_cli_error_log $error_code
    errecho "ERROR: AWS reports create-role operation failed.\n$response"
    return 1
```

```
  fi

  echo "$response"

  return 0
}
```

- Para obter detalhes da API, consulte AssumeRoleem Referência de AWS CLI Comandos.

Exemplos de código para SDK para C++

Os exemplos a seguir mostram como usar o AWS SDK for C++ com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para C++ : Saiba mais sobre como usar o C++ com AWS.
- AWS Centro do desenvolvedor : Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando SDK para C++
- Exemplos de serviços cruzados usando SDK para C++

Ações e cenários usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK for C++ com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de código para SDKs C++
- Exemplos do Auto Scaling usando SDK para C++
- CloudWatch exemplos de uso do SDK para C++
- CloudWatch Exemplos de registros usando o SDK for C++
- Exemplos do Provedor de Identidade do Amazon Cognito usando SDK para C++
- Exemplos do DynamoDB usando SDK para C++
- Exemplos do Amazon EC2 usando SDK para C++
- EventBridge exemplos de uso do SDK para C++
- Exemplos de AWS Glue usando SDK para C++
- HealthImaging exemplos de uso do SDK para C++
- Exemplos IAM usando SDKs para C++
- Exemplos de Lambda usando SDKs para C++
- MediaConvert exemplos de uso do SDK para C++
- Exemplos Amazon RDS usando SDK para C++
- Exemplos Amazon S3 usando SDK para C++
- Exemplos do Secrets Manager usando SDK para C++
- Exemplos Amazon SES usando SDK para C++
- Exemplos Amazon SNS usando SDK para C++
- Exemplos do Amazon SQS usando SDK para C++
- Exemplos de AWS STS usando SDK para C++

- Exemplos do Amazon Transcribe usando SDK para C++

Exemplos de código para SDKs C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_aurora")
```

```
# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_aurora.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_aurora.cpp.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBClustersRequest.h>
```

```
#include <iostream>

/*
 *  A "Hello Aurora" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client
 *  and describes the Amazon Aurora (Aurora) clusters.
 *
 *  main function
 *
 *  Usage: 'hello_aurora'
 *
 */
int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::RDS::RDSClient rdsClient(clientConfig);

        Aws::String marker; // Used for pagination.
        std::vector<Aws::String> clusterIds;
        do {
            Aws::RDS::Model::DescribeDBClustersRequest request;

            Aws::RDS::Model::DescribeDBClustersOutcome outcome =
                    rdsClient.DescribeDBClusters(request);

            if (outcome.IsSuccess()) {
                for (auto &cluster: outcome.GetResult().GetDBClusters()) {
                    clusterIds.push_back(cluster.GetDBClusterIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
                result = 1;
                std::cerr << "Error with Aurora::GDescribeDBClusters. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
```

```
            }
        } while (!marker.empty());

        std::cout << clusterIds.size() << " Aurora clusters found." << std::endl;
        for (auto &clusterId: clusterIds) {
            std::cout << "  clusterId " << clusterId << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for C++.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

Os exemplos de código a seguir mostram como criar um cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBClusterRequest request;
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetEngine(engineName);
        request.SetEngineVersion(engineVersionName);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBClusterOutcome outcome =
                client.CreateDBCluster(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBCluster. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for C++.

Criar um parameter group de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um grupo de parâmetros de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example cluster parameter group.");

        Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
                client.CreateDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for C++ da API.

Criar um snapshot de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
            request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                    client.CreateDBClusterSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for C++ da API.

Criar uma instância de banco de dados em um cluster de banco de dados

Os exemplos de código a seguir mostram como criar uma instância DB em um cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for C ++.

Excluir um cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);

            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for C++.

Excluir um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
    request.SetDBClusterParameterGroupName(parameterGroupName);

    Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
            client.DeleteDBClusterParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully deleted."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        result = false;
    }
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for C++ Referência da API.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
parameter group."
                        << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for C ++.

Descrever os grupos de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever grupos de parâmetros de cluster de banco de dados do Aurora.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
std::endl;
            dbParameterGroupFamily =
outcome.GetResult().GetDBClusterParameterGroups()[0].GetDBParameterGroupFamily();
        }

        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
```

```
        }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for C++ da API.

Descrever snapshots de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever snapshots de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
```

```
            }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for C++ da API.

Descrever clusters de banco de dados

Os exemplos de código a seguir mostram como descrever clusters do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);
```

```
    bool result = true;
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for C++.

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismos do banco de dados do Aurora.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }
```

```
    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for C++ da API.

Descrever as opções de instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever as opções de instâncias do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseDBInstanceClass()
```

```
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                instanceClasses.push_back(instanceClass);
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
```

```
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for C++ API.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBCLusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
```

```
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBClusterParameters(const Aws::String &parameterGroupName,
                                            const Aws::String &namePrefix,
                                            const Aws::String &source,
                                            Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                            const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
```

```
        }
    } while (!marker.empty());

    return true;
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for C++ da API.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros em um grupo de parâmetros de cluster do Aurora DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
                client.ModifyDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully modified."
                      << std::endl;
        }
        else {
```

```
            std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for C++ da API.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon Aurora DB cluster and demonstrates several
 operations
//! on that cluster.
/*!
 \sa gettingStartedWithDBClusters()
 \param clientConfiguration: AWS client configuration.
```

```
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::gettingStartedWithDBClusters(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);

    printAsterisksLine();
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon Aurora)"
              << std::endl;
    std::cout << "get started with DB clusters demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB cluster parameter group named '" <<
              CLUSTER_PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB cluster parameter group already exists.
        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
 std::endl;
            dbParameterGroupFamily =
 outcome.GetResult().GetDBClusterParameterGroups()[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' does not exist." <<
 std::endl;
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

```
    }

    if (!parameterGroupFound) {
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available parameter group families for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
        }

        std::cout << "Getting available parameter group families for " << DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family << std::endl;
            }
        }

        int choice = askQuestionForIntRange("Which family do you want to use? ", 1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB cluster parameter group.
        Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example cluster parameter group.");

        Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
                client.CreateDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your cluster parameter group."
              << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB cluster parameter group.
    if (!getDBCLusterParameters(CLUSTER_PARAMETER_GROUP_NAME, AUTO_INCREMENT_PREFIX,
                                NO_SOURCE,
                                autoIncrementParameters,
                                client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;

    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value between ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
                updateParameters.push_back(autoIncParameter);

            }
```

```
            else {
                std::cerr << "Error parsing " << autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the DB cluster parameter
group.
        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
                client.ModifyDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a source
of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the DB cluster parameter group.
    if (!getDBClusterParameters(CLUSTER_PARAMETER_GROUP_NAME, NO_NAME_PREFIX,
"user",
                                userParameters,
                                client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
```

```
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB Cluster." << std::endl;

    Aws::RDS::Model::DBCluster dbCluster;
    // 7.  Check if the DB cluster already exists.
    if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::String engineVersionName;
    Aws::String engineName;
    if (dbCluster.DBClusterIdentifierHasBeenSet()) {
        std::cout << "The DB cluster already exists." << std::endl;
        engineVersionName = dbCluster.GetEngineVersion();
        engineName = dbCluster.GetEngine();

    }
    else {
        std::cout << "Let's create a DB cluster." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters): ");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of engine versions for the parameter group family.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily, engineVersions,
                                 client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }

        std::cout << "The available engines for your parameter group family are:"
                  << std::endl;

        int index = 1;
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion: engineVersions)
{
```

```
            std::cout << "  " << index << ": " << engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ", 1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion = engineVersions[choice
-
                                                                                1];

        engineName = engineVersion.GetEngine();
        engineVersionName = engineVersion.GetEngineVersion();
        std::cout << "Creating a DB cluster named '" << DB_CLUSTER_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
                  << "The DB cluster is configured to use your custom cluster
parameter group '"
                  << CLUSTER_PARAMETER_GROUP_NAME << "', and \n"
                  << "selected engine version " << engineVersion.GetEngineVersion()
                  << ".\nThis typically takes several minutes." << std::endl;

        Aws::RDS::Model::CreateDBClusterRequest request;
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetEngine(engineName);
        request.SetEngineVersion(engineVersionName);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBClusterOutcome outcome =
                client.CreateDBCluster(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBCluster. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }
    }
```

```
    std::cout << "Waiting for the DB cluster to become available." << std::endl;

    int counter = 0;
    // 11. Wait for the DB cluster to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for cluster to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }

        dbCluster = Aws::RDS::Model::DBCluster();
        if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB cluster status is '"
                      << dbCluster.GetStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbCluster.GetStatus() != "available");

    if (dbCluster.GetStatus() == "available") {
        std::cout << "The DB cluster has been created." << std::endl;
    }

    printAsterisksLine();
    Aws::RDS::Model::DBInstance dbInstance;
    // 11.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER, "",
                         client);
        return false;
    }
```

```
    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;

        Aws::String dbInstanceClass;
        // 12.  Get a list of instance classes.
        if (!chooseDBInstanceClass(engineName,
                                   engineVersionName,
                                   dbInstanceClass,
                                   client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' with selected DB instance class '" << dbInstanceClass
                  << "'.\nThis typically takes several minutes." << std::endl;

        // 13. Create a DB instance.
        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
```

```
        }
    }

    std::cout << "Waiting for the DB instance to become available." << std::endl;

    counter = 0;
    // 14. Wait for the DB instance to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");

    if (dbInstance.GetDBInstanceStatus() == "available") {
        std::cout << "The DB instance has been created." << std::endl;
    }

    // 15. Display the connection string that can be used to connect a 'mysql' shell
 to the database.
    displayConnection(dbCluster);

    printAsterisksLine();

    if (askYesNoQuestion(
```

```
            "Do you want to create a snapshot of your DB cluster (y/n)? ")) {
        Aws::String snapshotID(DB_CLUSTER_IDENTIFIER + "-" +
                               Aws::String(Aws::Utils::UUID::RandomUUID()));
        {
            std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
            std::cout << "This typically takes a few minutes." << std::endl;

            // 16. Create a snapshot of the DB cluster. (CreateDBClusterSnapshot)
            Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
            request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                    client.CreateDBClusterSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
        }

        std::cout << "Waiting for the snapshot to become available." << std::endl;

        Aws::RDS::Model::DBClusterSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
```

```
                                DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            // 17. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");

        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB cluster, DB instance, and parameter group
(y/n)? ")) {
        result = cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
```

```
                                    DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
                                    client);
    }

    return result;
}

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}
```

```
//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBCLusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBCLusterParameters(const Aws::String &parameterGroupName,
                                            const Aws::String &namePrefix,
                                            const Aws::String &source,
                                            Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                            const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
```

```
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
```

```
    else {
        std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}


//! Routine which gets a DB instance description.
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }
```

```
    return result;
}


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                instanceClasses.push_back(instanceClass);
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
```

```
                        << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
*/
bool AwsDoc::Aurora::cleanUpResources(const Aws::String &parameterGroupName,
                                      const Aws::String &dbClusterIdentifier,
                                      const Aws::String &dbInstanceIdentifier,
                                      const Aws::RDS::RDSClient &client) {
    bool result = true;
    bool instanceDeleting = false;
    bool clusterDeleting = false;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 18. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);
```

```
            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
parameter group."
                        << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    if (!dbClusterIdentifier.empty()) {
        {
            // 19. Delete the DB cluster.
            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);

            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

```
        }
    }
    int counter = 0;

    while (clusterDeleting || instanceDeleting) {
        // 20. Wait for the DB cluster and instance to be deleted.
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 800) {
            std::cerr << "Wait for instance to delete timed out ofter " << counter
                      << " seconds." << std::endl;
            return false;
        }

        Aws::RDS::Model::DBInstance dbInstance = Aws::RDS::Model::DBInstance();
        if (instanceDeleting) {
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }
            instanceDeleting = dbInstance.DBInstanceIdentifierHasBeenSet();
        }

        Aws::RDS::Model::DBCluster dbCluster = Aws::RDS::Model::DBCluster();
        if (clusterDeleting) {
            if (!describeDBCluster(dbClusterIdentifier, dbCluster, client)) {
                return false;
            }

            clusterDeleting = dbCluster.DBClusterIdentifierHasBeenSet();
        }

        if ((counter % 20) == 0) {
            if (instanceDeleting) {
                std::cout << "Current DB instance status is '"
                          << dbInstance.GetDBInstanceStatus() << "." << std::endl;
            }

            if (clusterDeleting) {
                std::cout << "Current DB cluster status is '"
                          << dbCluster.GetStatus() << "." << std::endl;
            }
        }
    }
```

```
    if (!parameterGroupName.empty()) {
        // 21. Delete the DB cluster parameter group.
        Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
                client.DeleteDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - DB descrito ClusterParameterGroups
  - DB descrito ClusterParameters
  - DB descrito ClusterSnapshots
  - DescribeDBClusters
  - DB descrito EngineVersions

- DescribeDBInstances
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ClusterParameterGroup

Exemplos do Auto Scaling usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS autoscaling)
```

```
# Set this project's name.
project("hello_autoscaling")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_autoscaling.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem ola_autoscalling.cpp.

```
#include <aws/core/Aws.h>
```

```
#include <aws/autoscaling/AutoScalingClient.h>
#include <aws/autoscaling/model/DescribeAutoScalingGroupsRequest.h>
#include <iostream>

/*
 *  A "Hello Autoscaling" starter application which initializes an Amazon EC2 Auto
 Scaling client and describes the
 *  Amazon EC2 Auto Scaling groups.
 *
 *  main function
 *
 *  Usage: 'hello_autoscaling'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::AutoScaling::AutoScalingClient autoscalingClient(clientConfig);

        std::vector<Aws::String> groupNames;
        Aws::String nextToken; // Used for pagination.

        do {

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
                    autoscalingClient.DescribeAutoScalingGroups(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup>
 &autoScalingGroups =
```

```
                        outcome.GetResult().GetAutoScalingGroups();
                for (auto &group: autoScalingGroups) {
                    groupNames.push_back(group.GetAutoScalingGroupName());
                }
                nextToken = outcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "Found " << groupNames.size() << " AutoScaling groups." <<
 std::endl;
        for (auto &groupName: groupNames) {
            std::cout << "AutoScaling group: " << groupName << std::endl;
        }

    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for C ++ da API.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        Aws::Vector<Aws::String> availabilityGroupZones;
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;

    }
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for C++ da API.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
                autoScalingClient.DeleteAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling group '" << groupName << "' was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
```

```
                result = false;
            }
        }
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for C++ da API.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

    Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
    request.SetAutoScalingGroupName(groupName);

    Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
            autoScalingClient.DisableMetricsCollection(request);

    if (outcome.IsSuccess()) {
        std::cout << "Metrics collection has been disabled." << std::endl;
    }
    else {
        std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
```

```
        }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for C++ da API.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        request.AddMetrics("GroupMinSize");
        request.AddMetrics("GroupMaxSize");
        request.AddMetrics("GroupDesiredCapacity");
        request.AddMetrics("GroupInServiceInstances");
        request.AddMetrics("GroupTotalInstances");
        request.SetGranularity("1Minute");

        Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
                autoScalingClient.EnableMetricsCollection(request);
        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling metrics have been enabled."
                      << std::endl;
        }
```

```
        else {
            std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for C++ da API.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informações sobre grupos do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

    Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
    Aws::Vector<Aws::String> groupNames;
    groupNames.push_back(groupName);
    request.SetAutoScalingGroupNames(groupNames);

    Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
            client.DescribeAutoScalingGroups(request);

    if (outcome.IsSuccess()) {
        autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
    }
    else {
        std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
```

```
                << outcome.GetError().GetMessage()
                << std::endl;
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for C ++ da API.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
&instancesDetails =
                    outcome.GetResult().GetAutoScalingInstances();

        }
        else {
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
```

```
            return false;
        }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for C++ da API.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informações sobre as atividades do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                autoScalingClient.DescribeScalingActivities(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                    outcome.GetResult().GetActivities();
            std::cout << "Found " << activities.size() << " activities." <<
std::endl;
            std::cout << "Activities are ordered with the most recent first."
                      << std::endl;
            for (const Aws::AutoScaling::Model::Activity &activity: activities) {
                std::cout << activity.GetDescription() << std::endl;
                std::cout << activity.GetDetails() << std::endl;
            }
```

```
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for C++ da API.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetDesiredCapacity(2);

        Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
                autoScalingClient.SetDesiredCapacity(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                      << outcome.GetError().GetMessage()
```

```
                        << std::endl;

        }
```

- Para obter detalhes da API, consulte SetDesiredCapacity a Referência AWS SDK for C++ da API.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
        request.SetInstanceId(instanceIDs[instanceNumber - 1]);
        request.SetShouldDecrementDesiredCapacity(false);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome
=
                autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Waiting for EC2 instance with ID '"
                      << instanceIDs[instanceNumber - 1] << "' to terminate..."
                      << std::endl;
        }
        else {
            std::cerr << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;

    }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for C++ da API.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo do Auto Scaling.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

    Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
    request.SetAutoScalingGroupName(groupName);
    request.SetMaxSize(3);

    Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
            autoScalingClient.UpdateAutoScalingGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;

    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for C++ da API.

Cenários

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Routine which demonstrates using an Auto Scaling group
//! to manage Amazon EC2 instances.
/*!
  \sa groupsAndInstancesScenario()
  \param clientConfig: AWS client configuration.
  \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::groupsAndInstancesScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::String templateName;
    Aws::EC2::EC2Client ec2Client(clientConfig);
```

```
   std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
             << std::endl;
   std::cout
           << "Welcome to the Amazon Elastic Compute Cloud (Amazon EC2) Auto
Scaling "
           << "demo for managing groups and instances." << std::endl;
   std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " \n"
             << std::endl;

   std::cout << "This example requires an EC2 launch template." << std::endl;
   if (askYesNoQuestion(
           "Would you like to use an existing EC2 launch template (y/n)?  ")) {

       // 1. Specify the name of an existing EC2 launch template.
       templateName = askQuestion(
               "Enter the name of the existing EC2 launch template.  ");

       Aws::EC2::Model::DescribeLaunchTemplatesRequest request;
       request.AddLaunchTemplateNames(templateName);
       Aws::EC2::Model::DescribeLaunchTemplatesOutcome outcome =
               ec2Client.DescribeLaunchTemplates(request);

       if (outcome.IsSuccess()) {
           std::cout << "Validated the EC2 launch template '" << templateName
                     << "' exists by calling DescribeLaunchTemplate." << std::endl;
       }
       else {
           std::cerr << "Error validating the existence of the launch template. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
       }
   }
   else { // 2.  Or create a new EC2 launch template.
       templateName = askQuestion("Enter the name for a new EC2 launch template:
");

       Aws::EC2::Model::CreateLaunchTemplateRequest request;
       request.SetLaunchTemplateName(templateName);

       Aws::EC2::Model::RequestLaunchTemplateData requestLaunchTemplateData;

requestLaunchTemplateData.SetInstanceType(EC2_LAUNCH_TEMPLATE_INSTANCE_TYPE);
       requestLaunchTemplateData.SetImageId(EC2_LAUNCH_TEMPLATE_IMAGE_ID);
```

```
        request.SetLaunchTemplateData(requestLaunchTemplateData);

        Aws::EC2::Model::CreateLaunchTemplateOutcome outcome =
                ec2Client.CreateLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "The EC2 launch template '" << templateName << " was
created."
                      << std::endl;
        }
        else if (outcome.GetError().GetExceptionName() ==
                 "InvalidLaunchTemplateName.AlreadyExistsException") {
            std::cout << "The EC2 template '" << templateName << "' already exists"
                      << std::endl;
        }
        else {
            std::cerr << "Error with EC2::CreateLaunchTemplate. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }
    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);
    std::cout << "Let's create an Auto Scaling group." << std::endl;
    Aws::String groupName = askQuestion(
            "Enter a name for the Auto Scaling group:  ");
    // 3. Retrieve a list of EC2 Availability Zones.
    Aws::Vector<Aws::EC2::Model::AvailabilityZone> availabilityZones;
    {
        Aws::EC2::Model::DescribeAvailabilityZonesRequest request;

        Aws::EC2::Model::DescribeAvailabilityZonesOutcome outcome =
                ec2Client.DescribeAvailabilityZones(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "EC2 instances can be created in the following Availability
Zones:"
                    << std::endl;

            availabilityZones = outcome.GetResult().GetAvailabilityZones();
            for (size_t i = 0; i < availabilityZones.size(); ++i) {
                std::cout << "   " << i + 1 << ".  "
                          << availabilityZones[i].GetZoneName() << std::endl;
            }
```

```
        }
        else {
            std::cerr << "Error with EC2::DescribeAvailabilityZones. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    int availabilityZoneChoice = askQuestionForIntRange(
            "Choose an Availability Zone:  ", 1,
            static_cast<int>(availabilityZones.size()));
    // 4. Create an Auto Scaling group with the specified Availability Zone.
    {
        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        Aws::Vector<Aws::String> availabilityGroupZones;
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
```

```
                    << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        std::cout << "Here is the Auto Scaling group description." << std::endl;
        if (!autoScalingGroups.empty()) {
            logAutoScalingGroupInfo(autoScalingGroups);
        }
    }
    else {
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
        return false;
    }

    std::cout
            << "Waiting for the EC2 instance in the Auto Scaling group to become
active..."
            << std::endl;
    if (!waitForInstances(groupName, autoScalingGroups, autoScalingClient)) {
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
        return false;
    }

    bool enableMetrics = askYesNoQuestion(
            "Do you want to collect metrics about the A"
            "Auto Scaling group during this demo (y/n)?  ");
    // 7. Optionally enable metrics collection for the Auto Scaling group.
    if (enableMetrics) {
        Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        request.AddMetrics("GroupMinSize");
        request.AddMetrics("GroupMaxSize");
        request.AddMetrics("GroupDesiredCapacity");
        request.AddMetrics("GroupInServiceInstances");
        request.AddMetrics("GroupTotalInstances");
        request.SetGranularity("1Minute");

        Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
```

```
                autoScalingClient.EnableMetricsCollection(request);
        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling metrics have been enabled."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "Let's update the maximum number of EC2 instances in '" <<
groupName <<
              "' from 1 to 3." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    // 8. Update the Auto Scaling group, setting a new maximum size.
    {
        Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetMaxSize(3);

        Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                autoScalingClient.UpdateAutoScalingGroup(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        if (!autoScalingGroups.empty()) {
            const auto &instances = autoScalingGroups[0].GetInstances();
            std::cout
                    << "The group still has one running EC2 instance, but it can
have up to 3.\n"
                    << std::endl;
```

```
            logAutoScalingGroupInfo(autoScalingGroups);
        }
        else {
            std::cerr
                    << "No EC2 launch groups were retrieved from DescribeGroup
request."
                    << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;
    std::cout << "Let's update the desired capacity in '" << groupName <<
              "' from 1 to 2." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    //  9. Update the Auto Scaling group, setting a new desired capacity.
    {
        Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetDesiredCapacity(2);

        Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
                autoScalingClient.SetDesiredCapacity(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        if (!autoScalingGroups.empty()) {
            std::cout
                    << "Here is the current state of the group." << std::endl;
            logAutoScalingGroupInfo(autoScalingGroups);
        }
        else {
            std::cerr
```

```
                    << "No EC2 launch groups were retrieved from DescribeGroup
request."
                    << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "Waiting for the new EC2 instance to start..." << std::endl;
    waitForInstances(groupName, autoScalingGroups, autoScalingClient);

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;

    std::cout << "Let's terminate one of the EC2 instances in " << groupName << "."
              << std::endl;
    std::cout << "Because the desired capacity is 2, another EC2 instance will start
"
              << "to replace the terminated EC2 instance."
              << std::endl;
    std::cout << "The currently running EC2 instances are:" << std::endl;

    if (autoScalingGroups.empty()) {
        std::cerr << "Error describing groups. No groups returned." << std::endl;
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
        return false;
    }

    int instanceNumber = 1;
    Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
            autoScalingGroups[0].GetInstances());
    for (const Aws::String &instanceID: instanceIDs) {
        std::cout << "   " << instanceNumber << ". " << instanceID << std::endl;
        ++instanceNumber;
    }

    instanceNumber = askQuestionForIntRange("Which EC2 instance do you want to stop?
",
                                            1,
                                            static_cast<int>(instanceIDs.size()));

    // 10. Terminate an EC2 instance in the Auto Scaling group.
    {
        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
```

```
        request.SetInstanceId(instanceIDs[instanceNumber - 1]);
        request.SetShouldDecrementDesiredCapacity(false);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome
=
                autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Waiting for EC2 instance with ID '"
                      << instanceIDs[instanceNumber - 1] << "' to terminate..."
                      << std::endl;
        }
        else {
            std::cerr << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    waitForInstances(groupName, autoScalingGroups, autoScalingClient);

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;
    std::cout << "Let's get a report of scaling activities for EC2 launch group '"
              << groupName << "'."
              << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    // 11. Get a description of activities for the Auto Scaling group.
    {
        Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                autoScalingClient.DescribeScalingActivities(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                    outcome.GetResult().GetActivities();
            std::cout << "Found " << activities.size() << " activities." <<
std::endl;
            std::cout << "Activities are ordered with the most recent first."
```

```
                    << std::endl;
            for (const Aws::AutoScaling::Model::Activity &activity: activities) {
                std::cout << activity.GetDescription() << std::endl;
                std::cout << activity.GetDetails() << std::endl;
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    if (enableMetrics) {
        if (!logAutoScalingMetrics(groupName, clientConfig)) {
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "Let's  clean up." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);

    // 13. Disable metrics collection if enabled.
    if (enableMetrics) {
        Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
                autoScalingClient.DisableMetricsCollection(request);

        if (outcome.IsSuccess()) {
            std::cout << "Metrics collection has been disabled." << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }
```

```
    return cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
}

//! Routine which waits for EC2 instances in an Auto Scaling group to
//! complete startup or shutdown.
/*!
 \sa waitForInstances()
 \param groupName: An Auto Scaling group name.
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::waitForInstances(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroups,
                                            const Aws::AutoScaling::AutoScalingClient
 &client) {
    bool ready = false;
    const std::vector<Aws::String> READY_STATES = {"InService", "Terminated"};

    int count = 0;
    int desiredCapacity = 0;
    std::this_thread::sleep_for(std::chrono::seconds(4));
    while (!ready) {
        if (WAIT_FOR_INSTANCES_TIMEOUT < count) {
            std::cerr << "Wait for instance timed out." << std::endl;
            return false;
        }

        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++count;
        if (!describeGroup(groupName, autoScalingGroups, client)) {
            return false;
        }
        Aws::Vector<Aws::String> instanceIDs;
        if (!autoScalingGroups.empty()) {
            instanceIDs =
 instancesToInstanceIDs(autoScalingGroups[0].GetInstances());
            desiredCapacity = autoScalingGroups[0].GetDesiredCapacity();
        }

        if (instanceIDs.empty()) {
            if (desiredCapacity == 0) {
```

```
                break;
            }
            else {
                if ((count % 5) == 0) {
                    std::cout << "No instance IDs returned for group." << std::endl;
                }

                continue;
            }
        }

        // 6.  Check lifecycle state of the instances using
DescribeAutoScalingInstances.
        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
&instancesDetails =
                    outcome.GetResult().GetAutoScalingInstances();
            ready = instancesDetails.size() >= desiredCapacity;
            for (const Aws::AutoScaling::Model::AutoScalingInstanceDetails &details:
instancesDetails) {
                if (!stringInVector(details.GetLifecycleState(), READY_STATES)) {
                    ready = false;
                    break;
                }
            }
            // Log the status while waiting.
            if (((count % 5) == 1) || ready) {
                logInstancesLifecycleState(instancesDetails);
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

```
    if (!describeGroup(groupName, autoScalingGroups, client)) {
        return false;
    }

    return true;
}

//! Routine to cleanup resources created in 'groupsAndInstancesScenario'.
/*!
 \sa cleanupResources()
 \param groupName: Optional Auto Scaling group name.
 \param templateName: Optional EC2 launch template name.
 \param autoScalingClient: 'AutoScalingClient' instance.
 \param ec2Client: 'EC2Client' instance.
\return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::cleanupResources(const Aws::String &groupName,
                                           const Aws::String &templateName,
                                           const Aws::AutoScaling::AutoScalingClient
 &autoScalingClient,
                                           const Aws::EC2::EC2Client &ec2Client) {
    bool result = true;

    // 14. Delete the Auto Scaling group.
    if (!groupName.empty() &&
        (askYesNoQuestion(
                Aws::String("Delete the Auto Scaling group '") + groupName +
                "'  (y/n)?"))) {
        {
            Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);
            request.SetMinSize(0);
            request.SetDesiredCapacity(0);

            Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                    autoScalingClient.UpdateAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout
                        << "The minimum size and desired capacity of the Auto
 Scaling group "
                        << "was set to zero before terminating the instances."
                        << std::endl;
            }
```

```
            else {
                std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                          << outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
        }

        Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
        if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                               autoScalingClient)) {
            if (!autoScalingGroups.empty()) {
                Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
                        autoScalingGroups[0].GetInstances());
                for (const Aws::String &instanceID: instanceIDs) {

Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
                    request.SetInstanceId(instanceID);
                    request.SetShouldDecrementDesiredCapacity(true);


Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome =
                            autoScalingClient.TerminateInstanceInAutoScalingGroup(
                                    request);

                    if (outcome.IsSuccess()) {
                        std::cout << "Initiating termination of EC2 instance '"
                                  << instanceID << "'." << std::endl;
                    }
                    else {
                        std::cerr
                                << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                                << outcome.GetError().GetMessage() << std::endl;
                        result = false;
                    }
                }
            }

            std::cout
                    << "Waiting for the EC2 instances to terminate before deleting
the "
                    << "Auto Scaling group..." << std::endl;
            waitForInstances(groupName, autoScalingGroups, autoScalingClient);
        }
```

```
        {
            Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);

            Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
                    autoScalingClient.DeleteAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout << "Auto Scaling group '" << groupName << "' was deleted."
                          << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    // 15. Delete the EC2 launch template.
    if (!templateName.empty() && (askYesNoQuestion(
            Aws::String("Delete the EC2 launch template '") + templateName +
            "' (y/n)?"))) {
        Aws::EC2::Model::DeleteLaunchTemplateRequest request;
        request.SetLaunchTemplateName(templateName);

        Aws::EC2::Model::DeleteLaunchTemplateOutcome outcome =
                ec2Client.DeleteLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "EC2 launch template '" << templateName << "' was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with EC2::DeleteLaunchTemplate. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
```

```
}

//! Routine which retrieves Auto Scaling group descriptions.
/*!
 \sa describeGroup()
 \param groupName: An Auto Scaling group name.
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::describeGroup(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroup,
                                        const Aws::AutoScaling::AutoScalingClient
 &client) {
    // 5. Retrieve a description of the Auto Scaling group.
    Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
    Aws::Vector<Aws::String> groupNames;
    groupNames.push_back(groupName);
    request.SetAutoScalingGroupNames(groupNames);

    Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
            client.DescribeAutoScalingGroups(request);

    if (outcome.IsSuccess()) {
        autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
    }
    else {
        std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups

- DescribeAutoScalingInstances
- DescribeScalingActivities
- DisableMetricsCollection
- EnableMetricsCollection
- SetDesiredCapacity
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

CloudWatch exemplos de uso do SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ with CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Crie o alarme para vigiar a métrica.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::PutMetricAlarmRequest request;
        request.SetAlarmName(alarm_name);
        request.SetComparisonOperator(
            Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
        request.SetEvaluationPeriods(1);
        request.SetMetricName("CPUUtilization");
        request.SetNamespace("AWS/EC2");
        request.SetPeriod(60);
        request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
        request.SetThreshold(70.0);
        request.SetActionsEnabled(false);
        request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
        request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);

        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("InstanceId");
        dimension.SetValue(instanceId);

        request.AddDimensions(dimension);

        auto outcome = cw.PutMetricAlarm(request);
        if (!outcome.IsSuccess())
        {
```

```
            std::cout << "Failed to create CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for C++ da API.

Excluir alarmes

O exemplo de código a seguir mostra como excluir CloudWatch alarmes da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DeleteAlarmsRequest.h>
#include <iostream>
```

Exclua o alarme.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DeleteAlarmsRequest request;
        request.AddAlarmNames(alarm_name);

        auto outcome = cw.DeleteAlarms(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to delete CloudWatch alarm:" <<
```

```
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully deleted CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for C++ da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DescribeAlarmsRequest.h>
#include <aws/monitoring/model/DescribeAlarmsResult.h>
#include <iomanip>
#include <iostream>
```

Descreva os alarmes.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DescribeAlarmsRequest request;
        request.SetMaxRecords(1);

        bool done = false;
```

```
        bool header = false;
        while (!done)
        {
            auto outcome = cw.DescribeAlarms(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to describe CloudWatch alarms:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left <<
                    std::setw(32) << "Name" <<
                    std::setw(64) << "Arn" <<
                    std::setw(64) << "Description" <<
                    std::setw(20) << "LastUpdated" <<
                    std::endl;
                header = true;
            }

            const auto &alarms = outcome.GetResult().GetMetricAlarms();
            for (const auto &alarm : alarms)
            {
                std::cout << std::left <<
                    std::setw(32) << alarm.GetAlarmName() <<
                    std::setw(64) << alarm.GetAlarmArn() <<
                    std::setw(64) << alarm.GetAlarmDescription() <<
                    std::setw(20) << 
                    alarm.GetAlarmConfigurationUpdatedTimestamp().ToGmtString(
                        SIMPLE_DATE_FORMAT_STR) <<
                    std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for C++ da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DisableAlarmActionsRequest.h>
#include <iostream>
```

Desabilite as ações de alarme.

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::DisableAlarmActionsRequest
 disableAlarmActionsRequest;
        disableAlarmActionsRequest.AddAlarmNames(alarm_name);

        auto disableAlarmActionsOutcome =
 cw.DisableAlarmActions(disableAlarmActionsRequest);
        if (!disableAlarmActionsOutcome.IsSuccess())
        {
            std::cout << "Failed to disable actions for alarm " << alarm_name <<
                ": " << disableAlarmActionsOutcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully disabled actions for alarm " <<
                alarm_name << std::endl;
        }
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for C++ da API.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/EnableAlarmActionsRequest.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Habilite as ações de alarme.

```
    Aws::CloudWatch::CloudWatchClient cw;
    Aws::CloudWatch::Model::PutMetricAlarmRequest request;
    request.SetAlarmName(alarm_name);
    request.SetComparisonOperator(
        Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
    request.SetEvaluationPeriods(1);
    request.SetMetricName("CPUUtilization");
    request.SetNamespace("AWS/EC2");
    request.SetPeriod(60);
    request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
    request.SetThreshold(70.0);
    request.SetActionsEnabled(false);
    request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
    request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);
    request.AddAlarmActions(actionArn);
```

```
    Aws::CloudWatch::Model::Dimension dimension;
    dimension.SetName("InstanceId");
    dimension.SetValue(instanceId);
    request.AddDimensions(dimension);

    auto outcome = cw.PutMetricAlarm(request);
    if (!outcome.IsSuccess())
    {
        std::cout << "Failed to create CloudWatch alarm:" <<
            outcome.GetError().GetMessage() << std::endl;
        return;
    }

    Aws::CloudWatch::Model::EnableAlarmActionsRequest enable_request;
    enable_request.AddAlarmNames(alarm_name);

    auto enable_outcome = cw.EnableAlarmActions(enable_request);
    if (!enable_outcome.IsSuccess())
    {
        std::cout << "Failed to enable alarm actions:" <<
            enable_outcome.GetError().GetMessage() << std::endl;
        return;
    }

    std::cout << "Successfully created alarm " << alarm_name <<
        " and enabled actions on it." << std::endl;
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for C++ da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/ListMetricsRequest.h>
#include <aws/monitoring/model/ListMetricsResult.h>
#include <iomanip>
#include <iostream>
```

Liste as métricas.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::ListMetricsRequest request;

        if (argc > 1)
        {
            request.SetMetricName(argv[1]);
        }

        if (argc > 2)
        {
            request.SetNamespace(argv[2]);
        }

        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.ListMetrics(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to list CloudWatch metrics:" <<
                    outcome.GetError().GetMessage() << std::endl;
```

```
                break;
            }

            if (!header)
            {
                std::cout << std::left << std::setw(48) << "MetricName" <<
                    std::setw(32) << "Namespace" << "DimensionNameValuePairs" <<
                    std::endl;
                header = true;
            }

            const auto &metrics = outcome.GetResult().GetMetrics();
            for (const auto &metric : metrics)
            {
                std::cout << std::left << std::setw(48) <<
                    metric.GetMetricName() << std::setw(32) <<
                    metric.GetNamespace();
                const auto &dimensions = metric.GetDimensions();
                for (auto iter = dimensions.cbegin();
                    iter != dimensions.cend(); ++iter)
                {
                    const auto &dimkv = *iter;
                    std::cout << dimkv.GetName() << " = " << dimkv.GetValue();
                    if (iter + 1 != dimensions.cend())
                    {
                        std::cout << ", ";
                    }
                }
                std::cout << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for C++ da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricDataRequest.h>
#include <iostream>
```

Insira dados na métrica.

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("UNIQUE_PAGES");
        dimension.SetValue("URLS");

        Aws::CloudWatch::Model::MetricDatum datum;
        datum.SetMetricName("PAGES_VISITED");
        datum.SetUnit(Aws::CloudWatch::Model::StandardUnit::None);
        datum.SetValue(data_point);
        datum.AddDimensions(dimension);

        Aws::CloudWatch::Model::PutMetricDataRequest request;
        request.SetNamespace("SITE/TRAFFIC");
        request.AddMetricData(datum);

        auto outcome = cw.PutMetricData(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to put sample metric data:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
```

```
            std::cout << "Successfully put sample metric data" << std::endl;
        }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for C++ da API.

CloudWatch Exemplos de registros usando o SDK for C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ with CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um filtro de assinatura

O exemplo de código a seguir mostra como criar um filtro de assinatura do Amazon CloudWatch Logs.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/PutSubscriptionFilterRequest.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Crie o filtro de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::PutSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetFilterPattern(filter_pattern);
        request.SetLogGroupName(log_group);
        request.SetDestinationArn(dest_arn);
        auto outcome = cwl.PutSubscriptionFilter(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch logs subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for C++ da API.

Excluir um filtro de assinatura

O exemplo de código a seguir mostra como excluir um filtro de assinatura do Amazon CloudWatch Logs.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DeleteSubscriptionFilterRequest.h>
#include <iostream>
```

Excluir o filtro de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DeleteSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetLogGroupName(log_group);

        auto outcome = cwl.DeleteSubscriptionFilter(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Failed to delete CloudWatch log subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        } else {
            std::cout << "Successfully deleted CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for C++ da API.

Descreva os filtros de assinatura existentes

O exemplo de código a seguir mostra como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DescribeSubscriptionFiltersRequest.h>
#include <aws/logs/model/DescribeSubscriptionFiltersResult.h>
#include <iostream>
#include <iomanip>
```

Liste os filtros de assinatura.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DescribeSubscriptionFiltersRequest request;
        request.SetLogGroupName(log_group);
        request.SetLimit(1);

        bool done = false;
        bool header = false;
        while (!done) {
            auto outcome = cwl.DescribeSubscriptionFilters(
                    request);
            if (!outcome.IsSuccess()) {
                std::cout << "Failed to describe CloudWatch subscription filters "
                    << "for log group " << log_group << ": " <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }
```

```
            if (!header) {
                std::cout << std::left << std::setw(32) << "Name" <<
                    std::setw(64) << "FilterPattern" << std::setw(64) <<
                    "DestinationArn" << std::endl;
                header = true;
            }

            const auto &filters = outcome.GetResult().GetSubscriptionFilters();
            for (const auto &filter : filters) {
                std::cout << std::left << std::setw(32) <<
                    filter.GetFilterName() << std::setw(64) <<
                    filter.GetFilterPattern() << std::setw(64) <<
                    filter.GetDestinationArn() << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for C++ da API.

Exemplos do Provedor de Identidade do Amazon Cognito usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Cognito

Os exemplos de código a seguir mostram como começar a usar o Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS cognito-idp)

# Set this project's name.
project("hello_cognito")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.
```

```
    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                    # and set the proper subdirectory to the
 executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_cognito.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_cognito.cpp.

```
#include <aws/core/Aws.h>
#include <aws/cognito-idp/CognitoIdentityProviderClient.h>
#include <aws/cognito-idp/model/ListUserPoolsRequest.h>
#include <iostream>

/*
 *  A "Hello Cognito" starter application which initializes an Amazon Cognito client
 and lists the Amazon Cognito
 *  user pools.
 *
 *  main function
 *
 *  Usage: 'hello_cognito'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
```

```
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
cognitoClient(clientConfig);

        Aws::String nextToken; // Used for pagination.
        std::vector<Aws::String> userPools;

        do {
            Aws::CognitoIdentityProvider::Model::ListUserPoolsRequest
listUserPoolsRequest;
            if (!nextToken.empty()) {
                listUserPoolsRequest.SetNextToken(nextToken);
            }

            Aws::CognitoIdentityProvider::Model::ListUserPoolsOutcome
listUserPoolsOutcome =
                    cognitoClient.ListUserPools(listUserPoolsRequest);

            if (listUserPoolsOutcome.IsSuccess()) {
                for (auto &userPool:
listUserPoolsOutcome.GetResult().GetUserPools()) {

                    userPools.push_back(userPool.GetName());
                }

                nextToken = listUserPoolsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "ListUserPools error: " <<
listUserPoolsOutcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }


        } while (!nextToken.empty());
        std::cout << userPools.size() << " user pools found." << std::endl;
        for (auto &userPool: userPools) {
            std::cout << "   user pool: " << userPool << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
```

```
    return result;
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 client(clientConfig);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
        request.SetClientId(clientID);
        request.SetConfirmationCode(confirmationCode);
        request.SetUsername(userName);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
```

```
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for C++ da API.

Excluir um usuário

Os exemplos de código a seguir mostram como excluir um usuário do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
        request.SetAccessToken(accessToken);

        Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
                client.DeleteUser(request);

        if (outcome.IsSuccess()) {
            std::cout << "The user " << userName << " was deleted."
                      << std::endl;
        }
```

```
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for C++ da API.

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest request;
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome outcome =
                client.AssociateSoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for example
Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
```

```
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::AssociateSoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for C++ da API.

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 client(clientConfig);
```

```
    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);

    Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
            client.AdminGetUser(request);

    if (outcome.IsSuccess()) {
        std::cout << "The status for " << userName << " is " <<

Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                        outcome.GetResult().GetUserStatus()) << std::endl;
        std::cout << "Enabled is " << outcome.GetResult().GetEnabled() << std::endl;
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for C++ da API.

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);
```

```
        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest request;
        request.SetUsername(userName);
        request.SetClientId(clientID);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome outcome =
                client.ResendConfirmationCode(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "CognitoIdentityProvider::ResendConfirmationCode was
successful."
                    << std::endl;
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::ResendConfirmationCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for C++ da API.

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
       request.AddChallengeResponses("USERNAME", userName);
       request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
       request.SetChallengeName(

Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
       request.SetClientId(clientID);
       request.SetUserPoolId(userPoolID);
       request.SetSession(session);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
               client.AdminRespondToAuthChallenge(request);

       if (outcome.IsSuccess()) {
           std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                     << std::endl;

           accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for C++ da API.

Inscrever um usuário

Os exemplos de código a seguir mostram como inscrever um usuário com o Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::SignUpRequest request;
        request.AddUserAttributes(
                Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                        "email").WithValue(email));
        request.SetUsername(userName);
        request.SetPassword(password);
        request.SetClientId(clientID);
        Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
                client.SignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "The signup request for " << userName << " was successful."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==

Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
            std::cout
                    << "The username already exists. Please enter a different
username."
                    << std::endl;
            userExists = true;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
```

```
            return false;
        }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for C++ da API.

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
    request.SetClientId(clientID);
    request.SetUserPoolId(userPoolID);
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(

Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);


    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
            client.AdminInitiateAuth(request);

    if (outcome.IsSuccess()) {
        std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
        sessionResult = outcome.GetResult().GetSession();
```

```
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte AdminInitiateAuth a Referência AWS SDK for C++ da API.

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout << "Verification of the code was successful."
                      << std::endl;
            session = outcome.GetResult().GetSession();
        }
```

```
        else {
            std::cerr << "Error with CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for C++ da API.

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Scenario that adds a user to an Amazon Cognito user pool.
/*!
  \sa gettingStartedWithUserPools()
  \param clientID: Client ID associated with an Amazon Cognito user pool.
  \param userPoolID: An Amazon Cognito user pool ID.
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
```

```
 */
bool AwsDoc::Cognito::gettingStartedWithUserPools(const Aws::String &clientID,
                                                  const Aws::String &userPoolID,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    printAsterisksLine();
    std::cout
            << "Welcome to the Amazon Cognito example scenario."
            << std::endl;
    printAsterisksLine();

    std::cout
            << "This scenario will add a user to an Amazon Cognito user pool."
            << std::endl;
    const Aws::String userName = askQuestion("Enter a new username: ");
    const Aws::String password = askQuestion("Enter a new password: ");
    const Aws::String email = askQuestion("Enter a valid email for the user: ");

    std::cout << "Signing up " << userName << std::endl;

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 client(clientConfig);
    bool userExists = false;
    do {
        // 1. Add a user with a username, password, and email address.
        Aws::CognitoIdentityProvider::Model::SignUpRequest request;
        request.AddUserAttributes(
                Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                        "email").WithValue(email));
        request.SetUsername(userName);
        request.SetPassword(password);
        request.SetClientId(clientID);
        Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
                client.SignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "The signup request for " << userName << " was successful."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==

 Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
            std::cout
```

```
                    << "The username already exists. Please enter a different
username."
                    << std::endl;
            userExists = true;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (userExists);

    printAsterisksLine();
    std::cout << "Retrieving status of " << userName << " in the user pool."
              << std::endl;
    // 2. Confirm that the user was added to the user pool.
    if (!checkAdminUserStatus(userName, userPoolID, client)) {
        return false;
    }

    std::cout << "A confirmation code was sent to " << email << "." << std::endl;

    bool resend = askYesNoQuestion("Would you like to send a new code? (y/n) ");
    if (resend) {
        // Request a resend of the confirmation code to the email address.
(ResendConfirmationCode)
        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest request;
        request.SetUsername(userName);
        request.SetClientId(clientID);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome outcome =
                client.ResendConfirmationCode(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "CognitoIdentityProvider::ResendConfirmationCode was
successful."
                    << std::endl;
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::ResendConfirmationCode. "
                      << outcome.GetError().GetMessage()
```

```
                    << std::endl;
            return false;
        }
    }

    printAsterisksLine();

    {
        // 4. Send the confirmation code that's received in the email.
(ConfirmSignUp)
        const Aws::String confirmationCode = askQuestion(
                "Enter the confirmation code that was emailed: ");
        Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
        request.SetClientId(clientID);
        request.SetConfirmationCode(confirmationCode);
        request.SetUsername(userName);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "Rechecking the status of " << userName << " in the user pool."
              << std::endl;
    if (!checkAdminUserStatus(userName, userPoolID, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout << "Initiating authorization using the username and password."
              << std::endl;

    Aws::String session;
```

```
    // 5. Initiate authorization with username and password. (AdminInitiateAuth)
    if (!adminInitiateAuthorization(clientID, userPoolID,  userName, password,
 session, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout
            << "Starting setup of time-based one-time password (TOTP) multi-factor
 authentication (MFA)."
            << std::endl;

    {
        // 6. Request a setup key for one-time password (TOTP)
        //    multi-factor authentication (MFA). (AssociateSoftwareToken)
        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest request;
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome outcome =
                client.AssociateSoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for example
 Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::AssociateSoftwareToken. "
                      << outcome.GetError().GetMessage()
```

```
                    << std::endl;
            return false;
        }
    }
    askQuestion("Type enter to continue...", alwaysTrueTest);

    printAsterisksLine();

    {
        Aws::String userCode = askQuestion(
                "Enter the 6 digit code displayed in the authenticator app: ");

        //  7. Send the MFA code copied from an authenticator app.
(VerifySoftwareToken)
        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout << "Verification of the code was successful."
                      << std::endl;
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "You have completed the MFA authentication setup." << std::endl;
    std::cout << "Now, sign in." << std::endl;

    // 8. Initiate authorization again with username and password.
(AdminInitiateAuth)
    if (!adminInitiateAuthorization(clientID, userPoolID, userName, password,
session, client)) {
        return false;
    }
```

```
   Aws::String accessToken;
   {
       Aws::String mfaCode = askQuestion(
               "Re-enter the 6 digit code displayed in the authenticator app: ");

       // 9. Send a new MFA code copied from an authenticator app.
(AdminRespondToAuthChallenge)
       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
       request.AddChallengeResponses("USERNAME", userName);
       request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
       request.SetChallengeName(

Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
       request.SetClientId(clientID);
       request.SetUserPoolId(userPoolID);
       request.SetSession(session);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
               client.AdminRespondToAuthChallenge(request);

       if (outcome.IsSuccess()) {
           std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                     << std::endl;

           accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }

       std::cout << "You have successfully added a user to Amazon Cognito."
                 << std::endl;
   }
```

```
    if (askYesNoQuestion("Would you like to delete the user that you just added? (y/
n) ")) {
        // 10. Delete the user that you just added. (DeleteUser)
        Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
        request.SetAccessToken(accessToken);

        Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
                client.DeleteUser(request);

        if (outcome.IsSuccess()) {
            std::cout << "The user " << userName << " was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    return true;
}

//! Routine which checks the user status in an Amazon Cognito user pool.
/*!
 \sa checkAdminUserStatus()
 \param userName: A username.
 \param userPoolID: An Amazon Cognito user pool ID.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::checkAdminUserStatus(const Aws::String &userName,
                                           const Aws::String &userPoolID,
                                           const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);

    Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
            client.AdminGetUser(request);

    if (outcome.IsSuccess()) {
        std::cout << "The status for " << userName << " is " <<
```

```
 Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                          outcome.GetResult().GetUserStatus()) << std::endl;
        std::cout << "Enabled is " << outcome.GetResult().GetEnabled() << std::endl;
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which starts authorization of an Amazon Cognito user.
//! This routine requires administrator credentials.
/*!
 \sa adminInitiateAuthorization()
 \param clientID: Client ID of tracked device.
 \param userPoolID: An Amazon Cognito user pool ID.
 \param userName: A username.
 \param password: A password.
 \param sessionResult: String to receive a session token.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::adminInitiateAuthorization(const Aws::String &clientID,
                                                 const Aws::String &userPoolID,
                                                 const Aws::String &userName,
                                                 const Aws::String &password,
                                                 Aws::String &sessionResult,
                                                 const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
    request.SetClientId(clientID);
    request.SetUserPoolId(userPoolID);
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(

 Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);


    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
            client.AdminInitiateAuth(request);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
        sessionResult = outcome.GetResult().GetSession();
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Exemplos do DynamoDB usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for C++ com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, DynamoDB

O exemplo de código a seguir mostra como começar a usar o DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS dynamodb)

# Set this project's name.
project("hello_dynamodb")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})
```

```
if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_dynamodb.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_dynamodb.cpp.

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/ListTablesRequest.h>
#include <iostream>

/*
 *  A "Hello DynamoDB" starter application which initializes an Amazon DynamoDB
 (DynamoDB) client and lists the
 *  DynamoDB tables.
 *
 *  main function
```

```
 *
 *  Usage: 'hello_dynamodb'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.

    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::DynamoDB::DynamoDBClient dynamodbClient(clientConfig);
        Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
        listTablesRequest.SetLimit(50);
        do {
            const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamodbClient.ListTables(
                    listTablesRequest);
            if (!outcome.IsSuccess()) {
                std::cout << "Error: " << outcome.GetError().GetMessage() <<
 std::endl;
                result = 1;
                break;
            }

            for (const auto &tableName: outcome.GetResult().GetTableNames()) {
                std::cout << tableName << std::endl;
            }

            listTablesRequest.SetExclusiveStartTableName(
                    outcome.GetResult().GetLastEvaluatedTableName());

        } while (!listTablesRequest.GetExclusiveStartTableName().empty());
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
```

```
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon DynamoDB table.
/*!
  \sa createTable()
  \param tableName: Name for the DynamoDB table.
  \param primaryKey: Primary key for the DynamoDB table.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::createTable(const Aws::String &tableName,
                                   const Aws::String &primaryKey,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Creating table " << tableName <<
              " with a simple primary key: \"" << primaryKey << "\"." << std::endl;
```

```
    Aws::DynamoDB::Model::CreateTableRequest request;

    Aws::DynamoDB::Model::AttributeDefinition hashKey;
    hashKey.SetAttributeName(primaryKey);
    hashKey.SetAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
    request.AddAttributeDefinitions(hashKey);

    Aws::DynamoDB::Model::KeySchemaElement keySchemaElement;
    keySchemaElement.WithAttributeName(primaryKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::HASH);
    request.AddKeySchema(keySchemaElement);

    Aws::DynamoDB::Model::ProvisionedThroughput throughput;
    throughput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
    request.SetProvisionedThroughput(throughput);
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::CreateTableOutcome &outcome =
 dynamoClient.CreateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Table \""
                  << outcome.GetResult().GetTableDescription().GetTableName() <<
                  " created!" << std::endl;
    }
    else {
        std::cerr << "Failed to create table: " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for C++ da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon DynamoDB table.
/*!
  \sa deleteTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteTable(const Aws::String &tableName,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for C++ da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an item from an Amazon DynamoDB table.
/*!
  \sa deleteItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::deleteItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteItemRequest request;

    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteItemOutcome &outcome =
 dynamoClient.DeleteItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item \"" << partitionValue << "\" deleted!" << std::endl;
    }
    else {
        std::cerr << "Failed to delete item: " << outcome.GetError().GetMessage()
```

```
                    << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for C++ da API.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Batch get items from different Amazon DynamoDB tables.
/*!
  \sa batchGetItem()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::batchGetItem(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchGetItemRequest request;

    // Table1: Forum.
    Aws::String table1Name = "Forum";
    Aws::DynamoDB::Model::KeysAndAttributes table1KeysAndAttributes;

    // Table1: Projection expression.
    table1KeysAndAttributes.SetProjectionExpression("#n, Category, Messages, #v");

    // Table1: Expression attribute names.
    Aws::Http::HeaderValueCollection headerValueCollection;
```

```
    headerValueCollection.emplace("#n", "Name");
    headerValueCollection.emplace("#v", "Views");
    table1KeysAndAttributes.SetExpressionAttributeNames(headerValueCollection);

    // Table1: Set key name, type, and value to search.
    std::vector<Aws::String> nameValues = {"Amazon DynamoDB", "Amazon S3"};
    for (const Aws::String &name: nameValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetS(name);
        keys.emplace("Name", key);
        table1KeysAndAttributes.AddKeys(keys);
    }

    Aws::Map<Aws::String, Aws::DynamoDB::Model::KeysAndAttributes> requestItems;
    requestItems.emplace(table1Name, table1KeysAndAttributes);

    // Table2: ProductCatalog.
    Aws::String table2Name = "ProductCatalog";
    Aws::DynamoDB::Model::KeysAndAttributes table2KeysAndAttributes;
    table2KeysAndAttributes.SetProjectionExpression("Title, Price, Color");

    // Table2: Set key name, type, and value to search.
    std::vector<Aws::String> idValues = {"102", "103", "201"};
    for (const Aws::String &id: idValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetN(id);
        keys.emplace("Id", key);
        table2KeysAndAttributes.AddKeys(keys);
    }

    requestItems.emplace(table2Name, table2KeysAndAttributes);

    bool result = true;
    do {  // Use a do loop to handle pagination.
        request.SetRequestItems(requestItems);
        const Aws::DynamoDB::Model::BatchGetItemOutcome &outcome =
dynamoClient.BatchGetItem(
                request);

        if (outcome.IsSuccess()) {
            for (const auto &responsesMapEntry: outcome.GetResult().GetResponses())
{
```

```
                Aws::String tableName = responsesMapEntry.first;
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &tableResults = responsesMapEntry.second;
                std::cout << "Retrieved " << tableResults.size()
                          << " responses for table '" << tableName << "'.\n"
                          << std::endl;
                if (tableName == "Forum") {

                    std::cout << "Name | Category | Message | Views" << std::endl;
                    for (const Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Name").GetS() << " | ";
                        std::cout << item.at("Category").GetS() << " | ";
                        std::cout << (item.count("Message") == 0 ? "" : item.at(
                                "Messages").GetN()) << " | ";
                        std::cout << (item.count("Views") == 0 ? "" : item.at(
                                "Views").GetN()) << std::endl;
                    }
                }
                else {
                    std::cout << "Title | Price | Color" << std::endl;
                    for (const Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Title").GetS() << " | ";
                        std::cout << (item.count("Price") == 0 ? "" : item.at(
                                "Price").GetN());
                        if (item.count("Color")) {
                            std::cout << " | ";
                            for (const
std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> &listItem: item.at(
                                    "Color").GetL())
                                std::cout << listItem->GetS() << " ";
                        }
                        std::cout << std::endl;
                    }
                }
                std::cout << std::endl;
            }

            // If necessary, repeat request for remaining items.
            requestItems = outcome.GetResult().GetUnprocessedKeys();
        }
        else {
```

```
            std::cerr << "Batch get item failed: " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;
        }
    } while (!requestItems.empty());

    return result;
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for C++ da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Get an item from an Amazon DynamoDB table.
/*!
  \sa getItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::getItem(const Aws::String &tableName,
                               const Aws::String &partitionKey,
                               const Aws::String &partitionValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::GetItemRequest request;

    // Set up the request.
    request.SetTableName(tableName);
    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));

    // Retrieve the item's fields and values.
    const Aws::DynamoDB::Model::GetItemOutcome &outcome =
 dynamoClient.GetItem(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved fields/values.
        const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> &item =
 outcome.GetResult().GetItem();
        if (!item.empty()) {
            // Output each retrieved field and its value.
            for (const auto &i: item)
                std::cout << "Values: " << i.first << ": " << i.second.GetS()
                          << std::endl;
        }
        else {
            std::cout << "No item found with the key " << partitionKey << std::endl;
        }
    }
    else {
        std::cerr << "Failed to get item: " << outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for C++ da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Describe an Amazon DynamoDB table.
/*!
  \sa describeTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::describeTable(const Aws::String &tableName,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DescribeTableOutcome &outcome =
 dynamoClient.DescribeTable(
            request);

    if (outcome.IsSuccess()) {
        const Aws::DynamoDB::Model::TableDescription &td =
 outcome.GetResult().GetTable();
        std::cout << "Table name  : " << td.GetTableName() << std::endl;
        std::cout << "Table ARN   : " << td.GetTableArn() << std::endl;
        std::cout << "Status      : "
                  << Aws::DynamoDB::Model::TableStatusMapper::GetNameForTableStatus(
                          td.GetTableStatus()) << std::endl;
        std::cout << "Item count  : " << td.GetItemCount() << std::endl;
        std::cout << "Size (bytes): " << td.GetTableSizeBytes() << std::endl;

        const Aws::DynamoDB::Model::ProvisionedThroughputDescription &ptd =
 td.GetProvisionedThroughput();
        std::cout << "Throughput" << std::endl;
```

```
        std::cout << "  Read Capacity : " << ptd.GetReadCapacityUnits() <<
 std::endl;
        std::cout << "  Write Capacity: " << ptd.GetWriteCapacityUnits() <<
 std::endl;

        const Aws::Vector<Aws::DynamoDB::Model::AttributeDefinition> &ad =
 td.GetAttributeDefinitions();
        std::cout << "Attributes" << std::endl;
        for (const auto &a: ad)
            std::cout << "  " << a.GetAttributeName() << " (" <<

 Aws::DynamoDB::Model::ScalarAttributeTypeMapper::GetNameForScalarAttributeType(
                              a.GetAttributeType()) <<
                      ")" << std::endl;
    }
    else {
        std::cerr << "Failed to describe table: " <<
 outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for C++ da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the Amazon DynamoDB tables for the current AWS account.
/*!
  \sa listTables()
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::listTables(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
    listTablesRequest.SetLimit(50);
    do {
        const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamoClient.ListTables(
                listTablesRequest);
        if (!outcome.IsSuccess()) {
            std::cout << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        for (const auto &tableName: outcome.GetResult().GetTableNames())
            std::cout << tableName << std::endl;
        listTablesRequest.SetExclusiveStartTableName(
                outcome.GetResult().GetLastEvaluatedTableName());

    } while (!listTablesRequest.GetExclusiveStartTableName().empty());

    return true;
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for C++ da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Put an item in an Amazon DynamoDB table.
/*!
  \sa putItem()
  \param tableName: The table name.
  \param artistKey: The artist key. This is the partition key for the table.
  \param artistValue: The artist value.
  \param albumTitleKey: The album title key.
  \param albumTitleValue: The album title value.
  \param awardsKey: The awards key.
  \param awardsValue: The awards value.
  \param songTitleKey: The song title key.
  \param songTitleValue: The song title value.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::putItem(const Aws::String &tableName,
                               const Aws::String &artistKey,
                               const Aws::String &artistValue,
                               const Aws::String &albumTitleKey,
                               const Aws::String &albumTitleValue,
                               const Aws::String &awardsKey,
                               const Aws::String &awardsValue,
                               const Aws::String &songTitleKey,
                               const Aws::String &songTitleValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::PutItemRequest putItemRequest;
    putItemRequest.SetTableName(tableName);

    putItemRequest.AddItem(artistKey, Aws::DynamoDB::Model::AttributeValue().SetS(
            artistValue)); // This is the hash key.
    putItemRequest.AddItem(albumTitleKey,
 Aws::DynamoDB::Model::AttributeValue().SetS(
            albumTitleValue));
    putItemRequest.AddItem(awardsKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(awardsValue));
    putItemRequest.AddItem(songTitleKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(songTitleValue));
```

```
    const Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
            putItemRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully added Item!" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for C++ da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
//! Perform a query on an Amazon DynamoDB Table and retrieve items.
/*!
  \sa queryItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param projectionExpression: The projections expression, which is ignored if
 empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
```

```
 * The partition key attribute is searched with the specified value. By default, all
 fields and values
 * contained in the item are returned. If an optional projection expression is
 * specified on the command line, only the specified fields and values are
 * returned.
 */

bool AwsDoc::DynamoDB::queryItems(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &projectionExpression,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::QueryRequest request;

    request.SetTableName(tableName);

    if (!projectionExpression.empty()) {
        request.SetProjectionExpression(projectionExpression);
    }

    // Set query key condition expression.
    request.SetKeyConditionExpression(partitionKey + "= :valueToMatch");

    // Set Expression AttributeValues.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> attributeValues;
    attributeValues.emplace(":valueToMatch", partitionValue);

    request.SetExpressionAttributeValues(attributeValues);

    bool result = true;

    // "exclusiveStartKey" is used for pagination.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> exclusiveStartKey;
    do {
        if (!exclusiveStartKey.empty()) {
            request.SetExclusiveStartKey(exclusiveStartKey);
            exclusiveStartKey.clear();
        }
        // Perform Query operation.
        const Aws::DynamoDB::Model::QueryOutcome &outcome =
 dynamoClient.Query(request);
        if (outcome.IsSuccess()) {
```

```
            // Reference the retrieved items.
            const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
            if (!items.empty()) {
                std::cout << "Number of items retrieved from Query: " <<
 items.size()
                          << std::endl;
                // Iterate each item and print.
                for (const auto &item: items) {
                    std::cout
                            <<
 "*****************************************************"
                            << std::endl;
                    // Output each retrieved field and its value.
                    for (const auto &i: item)
                        std::cout << i.first << ": " << i.second.GetS() <<
 std::endl;
                }
            }
            else {
                std::cout << "No item found in table: " << tableName << std::endl;
            }

            exclusiveStartKey = outcome.GetResult().GetLastEvaluatedKey();
        }
        else {
            std::cerr << "Failed to Query items: " <<
 outcome.GetError().GetMessage();
            result = false;
            break;
        }
    } while (!exclusiveStartKey.empty());

    return result;
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for C++.

Executar uma instrução PartiQL

Os exemplos de código a seguir mostram como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        request.SetStatement(sqlStream.str());

        // Create the parameter attributes.
        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
```

```
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
        attributes.push_back(infoMapAttribute);
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

Use uma instrução SELECT para obter um item.

```
    //  3. Get the data for the movie using a "Select" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
```

```
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            // Print the retrieved movie information.
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }
```

Use uma instrução UPDATE para atualizar um item.

```
    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());
```

```
        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
        }
    }
```

Use uma instrução DELETE para excluir um item.

```
    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
```

```
        }
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for C++ da API.

Executar lotes de instruções PartiQL

Os exemplos de código a seguir mostram como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);
```

```
        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/n)
"));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));

            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
```

```
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

Use lotes de instruções SELECT para obter itens.

```
    // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;
```

```
        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Use lotes de instruções UPDATE para atualizar itens.

```
    // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)

    for (size_t i = 0; i < titles.size(); ++i) {
        ratings[i] = askQuestionForFloatRange(
                Aws::String("\nLet's update your the movie, \"") + titles[i] +
                ".\nYou rated it  " + std::to_string(ratings[i])
                + ", what new rating would you give it? ", 1, 10);
    }

    std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;
```

```
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);
        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Use lotes de instruções DELETE para excluir itens.

```
    // 6. Delete multiple movies using "Delete" statements. (BatchExecuteStatement)
    {
```

```
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for C++ da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
//! Scan an Amazon DynamoDB table.
/*!
  \sa scanTable()
  \param tableName: Name for the DynamoDB table.
  \param projectionExpression: An optional projection expression, ignored if empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::scanTable(const Aws::String &tableName,
                                 const Aws::String &projectionExpression,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::ScanRequest request;
    request.SetTableName(tableName);

    if (!projectionExpression.empty())
        request.SetProjectionExpression(projectionExpression);

    // Perform scan on table.
    const Aws::DynamoDB::Model::ScanOutcome &outcome = dynamoClient.Scan(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved items.
        const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
        if (!items.empty()) {
            std::cout << "Number of items retrieved from scan: " << items.size()
                      << std::endl;
            // Iterate each item and print.
            for (const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 &itemMap: items) {
                std::cout <<
 "*****************************************************"
```

```
                            << std::endl;
                // Output each retrieved field and its value.
                for (const auto &itemEntry: itemMap)
                    std::cout << itemEntry.first << ": " << itemEntry.second.GetS()
                              << std::endl;
            }
        }

        else {
            std::cout << "No item found in table: " << tableName << std::endl;
        }
    }
    else {
        std::cerr << "Failed to Scan items: " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for C++.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Update an Amazon DynamoDB table item.
/*!
  \sa updateItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
```

```
  \param attributeKey: The key for the attribute to be updated.
  \param attributeValue: The value for the attribute to be updated.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 *  The example code only sets/updates an attribute value. It processes
 *  the attribute value as a string, even if the value could be interpreted
 *  as a number. Also, the example code does not remove an existing attribute
 *  from the key value.
 */

bool AwsDoc::DynamoDB::updateItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &attributeKey,
                                  const Aws::String &attributeValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // *** Define UpdateItem request arguments.
    // Define TableName argument.
    Aws::DynamoDB::Model::UpdateItemRequest request;
    request.SetTableName(tableName);

    // Define KeyName argument.
    Aws::DynamoDB::Model::AttributeValue attribValue;
    attribValue.SetS(partitionValue);
    request.AddKey(partitionKey, attribValue);

    // Construct the SET update expression argument.
    Aws::String update_expression("SET #a = :valueA");
    request.SetUpdateExpression(update_expression);

    // Construct attribute name argument.
    Aws::Map<Aws::String, Aws::String> expressionAttributeNames;
    expressionAttributeNames["#a"] = attributeKey;
    request.SetExpressionAttributeNames(expressionAttributeNames);

    // Construct attribute value argument.
    Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
    attributeUpdatedValue.SetS(attributeValue);
```

```
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 expressionAttributeValues;
    expressionAttributeValues[":valueA"] = attributeUpdatedValue;
    request.SetExpressionAttributeValues(expressionAttributeValues);

    // Update the item.
    const Aws::DynamoDB::Model::UpdateItemOutcome &outcome =
 dynamoClient.UpdateItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item was updated" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for C++ da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Batch write items from a JSON file.
/*!
  \sa batchWriteItem()
  \param jsonFilePath: JSON file path.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
/*
 * The input for this routine is a JSON file that you can download from the
 following URL:
 * https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SampleData.html.
 *
 * The JSON data uses the BatchWriteItem API request syntax. The JSON strings are
 * converted to AttributeValue objects. These AttributeValue objects will then
 generate
 * JSON strings when constructing the BatchWriteItem request, essentially outputting
 * their input.
 *
 * This is perhaps an artificial example, but it demonstrates the APIs.
 */

bool AwsDoc::DynamoDB::batchWriteItem(const Aws::String &jsonFilePath,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    std::ifstream fileStream(jsonFilePath);

    if (!fileStream) {
        std::cerr << "Error: could not open file '" << jsonFilePath << "'."
                  << std::endl;
    }

    std::stringstream stringStream;
    stringStream << fileStream.rdbuf();
    Aws::Utils::Json::JsonValue jsonValue(stringStream);

    Aws::DynamoDB::Model::BatchWriteItemRequest batchWriteItemRequest;
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> level1Map =
 jsonValue.View().GetAllObjects();
    for (const auto &level1Entry: level1Map) {
        const Aws::Utils::Json::JsonView &entriesView = level1Entry.second;
        const Aws::String &tableName = level1Entry.first;
        // The JSON entries at this level are as follows:
        //  key - table name
        //  value - list of request objects
        if (!entriesView.IsListType()) {
            std::cerr << "Error: JSON file entry '"
                      << tableName << "' is not a list." << std::endl;
            continue;
        }
```

```
        Aws::Utils::Array<Aws::Utils::Json::JsonView> entries =
 entriesView.AsArray();

        Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;
        if (AwsDoc::DynamoDB::addWriteRequests(tableName, entries,
                                               writeRequests)) {
            batchWriteItemRequest.AddRequestItems(tableName, writeRequests);
        }
    }

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchWriteItemOutcome outcome =
 dynamoClient.BatchWriteItem(
            batchWriteItemRequest);

    if (outcome.IsSuccess()) {
        std::cout << "DynamoDB::BatchWriteItem was successful." << std::endl;
    }
    else {
        std::cerr << "Error with DynamoDB::BatchWriteItem. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return true;
}

//! Convert requests in JSON format to a vector of WriteRequest objects.
/*!
  \sa addWriteRequests()
  \param tableName: Name of the table for the write operations.
  \param requestsJson: Request data in JSON format.
  \param writeRequests: Vector to receive the WriteRequest objects.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::addWriteRequests(const Aws::String &tableName,
                                        const
 Aws::Utils::Array<Aws::Utils::Json::JsonView> &requestsJson,

 Aws::Vector<Aws::DynamoDB::Model::WriteRequest> &writeRequests) {
    for (size_t i = 0; i < requestsJson.GetLength(); ++i) {
        const Aws::Utils::Json::JsonView &requestsEntry = requestsJson[i];
        if (!requestsEntry.IsObject()) {
```

```
            std::cerr << "Error: incorrect requestsEntry type "
                      << requestsEntry.WriteReadable() << std::endl;
            return false;
        }

        Aws::Map<Aws::String, Aws::Utils::Json::JsonView> requestsMap =
 requestsEntry.GetAllObjects();

        for (const auto &request: requestsMap) {
            const Aws::String &requestType = request.first;
            const Aws::Utils::Json::JsonView &requestJsonView = request.second;

            if (requestType == "PutRequest") {
                if (!requestJsonView.ValueExists("Item")) {
                    std::cerr << "Error: item key missing for requests "
                              << requestJsonView.WriteReadable() << std::endl;
                    return false;
                }
                Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 attributes;
                if (!getAttributeObjectsMap(requestJsonView.GetObject("Item"),
                                            attributes)) {
                    std::cerr << "Error getting attributes "
                              << requestJsonView.WriteReadable() << std::endl;
                    return false;
                }

                Aws::DynamoDB::Model::PutRequest putRequest;
                putRequest.SetItem(attributes);
                writeRequests.push_back(
                        Aws::DynamoDB::Model::WriteRequest().WithPutRequest(
                                putRequest));
            }
            else {
                std::cerr << "Error: unimplemented request type '" << requestType
                          << "'." << std::endl;
            }
        }
    }

    return true;
}

//! Generate a map of AttributeValue objects from JSON records.
```

```
/*!
  \sa getAttributeObjectsMap()
  \param jsonView: JSONView of attribute records.
  \param writeRequests: Map to receive the AttributeValue objects.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::getAttributeObjectsMap(const Aws::Utils::Json::JsonView &jsonView,
                                         Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &attributes) {
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> objectsMap =
 jsonView.GetAllObjects();
    for (const auto &entry: objectsMap) {
        const Aws::String &attributeKey = entry.first;
        const Aws::Utils::Json::JsonView &attributeJsonView = entry.second;

        if (!attributeJsonView.IsObject()) {
            std::cerr << "Error: attribute not an object "
                      << attributeJsonView.WriteReadable() << std::endl;
            return false;
        }

        attributes.emplace(attributeKey,
                           Aws::DynamoDB::Model::AttributeValue(attributeJsonView));
    }

    return true;
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for C++ da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.

- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
    {
        Aws::Client::ClientConfiguration clientConfig;
        //  1. Create a table with partition: year (N) and sort: title (S).
 (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::dynamodbGettingStartedScenario(clientConfig);

            // 9. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }
    }

//! Scenario to modify and query a DynamoDB table.
/*!
  \sa dynamodbGettingStartedScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::dynamodbGettingStartedScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;
    std::cout << "Welcome to the Amazon DynamoDB getting started demo." <<
 std::endl;
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
```

```
    // 2. Add a new movie.
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::PutItemRequest putItemRequest;
        putItemRequest.SetTableName(MOVIE_TABLE_NAME);

        putItemRequest.AddItem(YEAR_KEY,
                               Aws::DynamoDB::Model::AttributeValue().SetN(year));
        putItemRequest.AddItem(TITLE_KEY,
                               Aws::DynamoDB::Model::AttributeValue().SetS(title));

        // Create attribute for the info map.
        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);

        putItemRequest.AddItem(INFO_KEY, infoMapAttribute);

        Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
                putItemRequest);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add an item: " <<
outcome.GetError().GetMessage()
```

```
                    << std::endl;
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    // 3. Update the rating and plot of the movie by using an update expression.
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);
        plot = askQuestion(Aws::String("You summarized the plot as '") + plot +
                           "'.\nWhat would you say now? ");

        Aws::DynamoDB::Model::UpdateItemRequest request;
        request.SetTableName(MOVIE_TABLE_NAME);
        request.AddKey(TITLE_KEY,
Aws::DynamoDB::Model::AttributeValue().SetS(title));
        request.AddKey(YEAR_KEY, Aws::DynamoDB::Model::AttributeValue().SetN(year));
        std::stringstream expressionStream;
        expressionStream << "set " << INFO_KEY << "." << RATING_KEY << " =:r, "
                         << INFO_KEY << "." << PLOT_KEY << " =:p";
        request.SetUpdateExpression(expressionStream.str());
        request.SetExpressionAttributeValues({
                                                        {":r",
Aws::DynamoDB::Model::AttributeValue().SetN(
                                                                rating)},
                                                        {":p",
Aws::DynamoDB::Model::AttributeValue().SetS(
                                                                plot)}
                                                }});

        request.SetReturnValues(Aws::DynamoDB::Model::ReturnValue::UPDATED_NEW);

        const Aws::DynamoDB::Model::UpdateItemOutcome &result =
dynamoClient.UpdateItem(
                request);
        if (!result.IsSuccess()) {
            std::cerr << "Error updating movie " + result.GetError().GetMessage()
                      << std::endl;
            return false;
```

```
        }
    }

    std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

    // 4. Put 250 movies in the table from moviedata.json.
    {
        std::cout << "Adding movies from a json file to the database." << std::endl;
        const size_t MAX_SIZE_FOR_BATCH_WRITE = 25;
        const size_t MOVIES_TO_WRITE = 10 * MAX_SIZE_FOR_BATCH_WRITE;
        Aws::String jsonString = getMovieJSON();
        if (!jsonString.empty()) {
            Aws::Utils::Json::JsonValue json(jsonString);
            Aws::Utils::Array<Aws::Utils::Json::JsonView> movieJsons =
json.View().AsArray();
            Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;

            // To add movies with a cross-section of years, use an appropriate
increment
            // value for iterating through the database.
            size_t increment = movieJsons.GetLength() / MOVIES_TO_WRITE;
            for (size_t i = 0; i < movieJsons.GetLength(); i += increment) {
                writeRequests.push_back(Aws::DynamoDB::Model::WriteRequest());
                Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> putItems
= movieJsonViewToAttributeMap(
                        movieJsons[i]);
                Aws::DynamoDB::Model::PutRequest putRequest;
                putRequest.SetItem(putItems);
                writeRequests.back().SetPutRequest(putRequest);
                if (writeRequests.size() == MAX_SIZE_FOR_BATCH_WRITE) {
                    Aws::DynamoDB::Model::BatchWriteItemRequest request;
                    request.AddRequestItems(MOVIE_TABLE_NAME, writeRequests);
                    const Aws::DynamoDB::Model::BatchWriteItemOutcome &outcome =
dynamoClient.BatchWriteItem(
                            request);
                    if (!outcome.IsSuccess()) {
                        std::cerr << "Unable to batch write movie data: "
                                  << outcome.GetError().GetMessage()
                                  << std::endl;
                        writeRequests.clear();
                        break;
                    }
                    else {
                        std::cout << "Added batch of " << writeRequests.size()
```

```
                                << " movies to the database."
                                << std::endl;
                    }
                    writeRequests.clear();
                }
            }
        }
    }

    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    // 5. Get a movie by Key (partition + sort).
    {
        Aws::String titleToGet("King Kong");
        Aws::String answer = askQuestion(Aws::String(
                "Let's move on...Would you like to get info about '" + titleToGet +
                "'? (y/n) "));
        if (answer == "y") {
            Aws::DynamoDB::Model::GetItemRequest request;
            request.SetTableName(MOVIE_TABLE_NAME);
            request.AddKey(TITLE_KEY,
                           Aws::DynamoDB::Model::AttributeValue().SetS(titleToGet));
            request.AddKey(YEAR_KEY,
Aws::DynamoDB::Model::AttributeValue().SetN(1933));

            const Aws::DynamoDB::Model::GetItemOutcome &result =
dynamoClient.GetItem(
                    request);
            if (!result.IsSuccess()) {
                std::cerr << "Error " << result.GetError().GetMessage();
            }
            else {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = result.GetResult().GetItem();
                if (!item.empty()) {
                    std::cout << "\nHere's what I found:" << std::endl;
                    printMovieInfo(item);
                }
                else {
                    std::cout << "\nThe movie was not found in the database."
                              << std::endl;
                }
            }
```

```
        }
    }

    // 6. Use Query with a key condition expression to return all movies
    //    released in a given year.
    Aws::String doAgain = "n";
    do {
        Aws::DynamoDB::Model::QueryRequest req;

        req.SetTableName(MOVIE_TABLE_NAME);

        // "year" is a DynamoDB reserved keyword and must be replaced with an
        // expression attribute name.
        req.SetKeyConditionExpression("#dynobase_year = :valueToMatch");
        req.SetExpressionAttributeNames({{"#dynobase_year", YEAR_KEY}});

        int yearToMatch = askQuestionForIntRange(
                "\nLet's get a list of movies released in"
                " a given year. Enter a year between 1972 and 2018 ",
                1972, 2018);
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> attributeValues;
        attributeValues.emplace(":valueToMatch",
                                Aws::DynamoDB::Model::AttributeValue().SetN(
                                        yearToMatch));
        req.SetExpressionAttributeValues(attributeValues);

        const Aws::DynamoDB::Model::QueryOutcome &result = dynamoClient.Query(req);
        if (result.IsSuccess()) {
            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
            if (!items.empty()) {
                std::cout << "\nThere were " << items.size()
                          << " movies in the database from "
                          << yearToMatch << "." << std::endl;
                for (const auto &item: items) {
                    printMovieInfo(item);
                }
                doAgain = "n";
            }
            else {
                std::cout << "\nNo movies from " << yearToMatch
                          << " were found in the database"
                          << std::endl;
                doAgain = askQuestion(Aws::String("Try another year? (y/n) "));
```

```
            }
        }
        else {
            std::cerr << "Failed to Query items: " << result.GetError().GetMessage()
                      << std::endl;
        }

    } while (doAgain == "y");

    //  7. Use Scan to return movies released within a range of years.
    //     Show how to paginate data using ExclusiveStartKey. (Scan +
FilterExpression)
    {
        int startYear = askQuestionForIntRange("\nNow let's scan a range of years "
                                               "for movies in the database. Enter a
start year: ",
                                               1972, 2018);
        int endYear = askQuestionForIntRange("\nEnter an end year: ",
                                             startYear, 2018);
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
exclusiveStartKey;
        do {
            Aws::DynamoDB::Model::ScanRequest scanRequest;
            scanRequest.SetTableName(MOVIE_TABLE_NAME);
            scanRequest.SetFilterExpression(
                    "#dynobase_year >= :startYear AND #dynobase_year <= :endYear");
            scanRequest.SetExpressionAttributeNames({{"#dynobase_year", YEAR_KEY}});

            Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
            attributeValues.emplace(":startYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            startYear));
            attributeValues.emplace(":endYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            endYear));
            scanRequest.SetExpressionAttributeValues(attributeValues);

            if (!exclusiveStartKey.empty()) {
                scanRequest.SetExclusiveStartKey(exclusiveStartKey);
            }

            const Aws::DynamoDB::Model::ScanOutcome &result = dynamoClient.Scan(
                    scanRequest);
```

```
            if (result.IsSuccess()) {
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
                if (!items.empty()) {
                    std::stringstream stringStream;
                    stringStream << "\nFound " << items.size() << " movies in one
scan."
                                 << " How many would you like to see? ";
                    size_t count = askQuestionForInt(stringStream.str());
                    for (size_t i = 0; i < count && i < items.size(); ++i) {
                        printMovieInfo(items[i]);
                    }
                }
                else {
                    std::cout << "\nNo movies in the database between " << startYear
<<
                              " and " << endYear << "." << std::endl;
                }

                exclusiveStartKey = result.GetResult().GetLastEvaluatedKey();
                if (!exclusiveStartKey.empty()) {
                    std::cout << "Not all movies were retrieved. Scanning for more."
                              << std::endl;
                }
                else {
                    std::cout << "All movies were retrieved with this scan."
                              << std::endl;
                }
            }
            else {
                std::cerr << "Failed to Scan movies: "
                          << result.GetError().GetMessage() << std::endl;
            }
        } while (!exclusiveStartKey.empty());
    }

    // 8. Delete a movie. (DeleteItem)
    {
        std::stringstream stringStream;
        stringStream << "\nWould you like to delete the movie " << title
                     << " from the database? (y/n) ";
        Aws::String answer = askQuestion(stringStream.str());
        if (answer == "y") {
            Aws::DynamoDB::Model::DeleteItemRequest request;
```

```
            request.AddKey(YEAR_KEY,
 Aws::DynamoDB::Model::AttributeValue().SetN(year));
            request.AddKey(TITLE_KEY,
                           Aws::DynamoDB::Model::AttributeValue().SetS(title));
            request.SetTableName(MOVIE_TABLE_NAME);

            const Aws::DynamoDB::Model::DeleteItemOutcome &result =
 dynamoClient.DeleteItem(
                    request);
            if (result.IsSuccess()) {
                std::cout << "\nRemoved \"" << title << "\" from the database."
                          << std::endl;
            }
            else {
                std::cerr << "Failed to delete the movie: "
                          << result.GetError().GetMessage()
                          << std::endl;
            }
        }
    }

    return true;
}

//! Routine to convert a JsonView object to an attribute map.
/*!
  \sa movieJsonViewToAttributeMap()
  \param jsonView: Json view object.
  \return map: Map that can be used in a DynamoDB request.
 */
Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
AwsDoc::DynamoDB::movieJsonViewToAttributeMap(
        const Aws::Utils::Json::JsonView &jsonView) {
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> result;

    if (jsonView.KeyExists(YEAR_KEY)) {
        result[YEAR_KEY].SetN(jsonView.GetInteger(YEAR_KEY));
    }
    if (jsonView.KeyExists(TITLE_KEY)) {
        result[TITLE_KEY].SetS(jsonView.GetString(TITLE_KEY));
    }
    if (jsonView.KeyExists(INFO_KEY)) {
        Aws::Map<Aws::String, const
 std::shared_ptr<Aws::DynamoDB::Model::AttributeValue>> infoMap;
```

```
        Aws::Utils::Json::JsonView infoView = jsonView.GetObject(INFO_KEY);
        if (infoView.KeyExists(RATING_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue =
 std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetN(infoView.GetDouble(RATING_KEY));
            infoMap.emplace(std::make_pair(RATING_KEY, attributeValue));
        }
        if (infoView.KeyExists(PLOT_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue =
 std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetS(infoView.GetString(PLOT_KEY));
            infoMap.emplace(std::make_pair(PLOT_KEY, attributeValue));
        }

        result[INFO_KEY].SetM(infoMap);
    }

    return result;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
```

```
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
clientConfiguration)) {
```

```
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
```

```
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - BatchWriteItem
  - CreateTable
  - DeleteItem

- DeleteTable
- DescribeTable
- GetItem
- PutItem
- Query
- Scan
- UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlBatchExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using PartiQL batch statements.
/*!
```

```
  \sa partiqlBatchExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::partiqlBatchExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);

        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/n)
 "));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";
```

```
        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));

            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

```
   std::cout << "Retrieving the movie data with a batch \"SELECT\" statement."
             << std::endl;

   // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
   {
       Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
               titles.size());
       std::stringstream sqlStream;
       sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                 << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

       std::string sql(sqlStream.str());

       for (size_t i = 0; i < statements.size(); ++i) {
           statements[i].SetStatement(sql);
           Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
           attributes.push_back(
                   Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
           statements[i].SetParameters(attributes);
       }

       Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

       request.SetStatements(statements);

       Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
               request);
       if (outcome.IsSuccess()) {
           const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

           const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

           for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
               const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();
```

```
                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)

    for (size_t i = 0; i < titles.size(); ++i) {
        ratings[i] = askQuestionForFloatRange(
                Aws::String("\nLet's update your the movie, \"") + titles[i] +
                ".\nYou rated it  " + std::to_string(ratings[i])
                + ", what new rating would you give it? ", 1, 10);
    }

    std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));
```

```
attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);
        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Retrieving the updated movie data with a batch \"SELECT\"
statement."
              << std::endl;

    // 5. Get the updated data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;
```

```
        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movies information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Deleting the movie data with a batch \"DELETE\" statement."
              << std::endl;

    // 6. Delete multiple movies using "Delete" statements. (BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
```

```
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

 attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
 dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
```

```
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
```

```
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
```

```
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for C++ da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using single PartiQL statements.
/*!
  \sa partiqlExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::partiqlExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
```

```
    // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        request.SetStatement(sqlStream.str());

        // Create the parameter attributes.
        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
        attributes.push_back(infoMapAttribute);
        request.SetParameters(attributes);
```

```
        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    //  3. Get the data for the movie using a "Select" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            // Print the retrieved movie information.
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();
```

```
            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }

    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
```

```
        }
    }

    std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

    //  5. Get the updated data for the movie using a "Select" statement.
(ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }
```

```
    std::cout << "Deleting the movie" << std::endl;

    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
 dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Movie successfully deleted." << std::endl;
    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
```

```
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
```

```
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
```

```
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
```

```
    return false;
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for C++ da API.

Exemplos do Amazon EC2 usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
```

```
set(SERVICE_COMPONENTS ec2)

# Set this project's name.
project("hello_ec2")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_ec2.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo fonte hello_ec2.cpp.

```
#include <aws/core/Aws.h>
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeInstancesRequest.h>
#include <iomanip>
#include <iostream>

/*
 *  A "Hello EC2" starter application which initializes an Amazon Elastic Compute
 Cloud (Amazon EC2) client and describes
 *  the Amazon EC2 instances.
 *
 *  main function
 *
 *  Usage: 'hello_ec2'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::EC2::EC2Client ec2Client(clientConfig);
        Aws::EC2::Model::DescribeInstancesRequest request;
        bool header = false;
        bool done = false;
        while (!done) {
            auto outcome = ec2Client.DescribeInstances(request);
            if (outcome.IsSuccess()) {
                if (!header) {
                    std::cout << std::left <<
                              std::setw(48) << "Name" <<
                              std::setw(20) << "ID" <<
                              std::setw(25) << "Ami" <<
                              std::setw(15) << "Type" <<
                              std::setw(15) << "State" <<
                              std::setw(15) << "Monitoring" << std::endl;
```

```
                    header = true;
                }

                const std::vector<Aws::EC2::Model::Reservation> &reservations =
                        outcome.GetResult().GetReservations();

                for (const auto &reservation: reservations) {
                    const std::vector<Aws::EC2::Model::Instance> &instances =
                            reservation.GetInstances();
                    for (const auto &instance: instances) {
                        Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                        instance.GetState().GetName());

                        Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                        instance.GetInstanceType());

                        Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                        instance.GetMonitoring().GetState());
                        Aws::String name = "Unknown";

                        const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                        auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                     [](const Aws::EC2::Model::Tag
&tag) {
                                                         return tag.GetKey() ==
"Name";
                                                     });
                        if (nameIter != tags.cend()) {
                            name = nameIter->GetValue();
                        }
                        std::cout <<
                                  std::setw(48) << name <<
                                  std::setw(20) << instance.GetInstanceId() <<
                                  std::setw(25) << instance.GetImageId() <<
                                  std::setw(15) << typeString <<
                                  std::setw(15) << instanceStateString <<
                                  std::setw(15) << monitorString << std::endl;
```

```
                    }
                }

                if (!outcome.GetResult().GetNextToken().empty()) {
                    request.SetNextToken(outcome.GetResult().GetNextToken());
                } else {
                    done = true;
                }
            } else {
                std::cerr << "Failed to describe EC2 instances:" <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for C++ da API.

Tópicos

- Ações

Ações

Adicionar tags a recursos

O exemplo de código a seguir mostra como adicionar tags a recursos do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::Tag nameTag;
nameTag.SetKey("Name");
nameTag.SetValue(instanceName);

Aws::EC2::Model::CreateTagsRequest createRequest;
createRequest.AddResources(instanceID);
createRequest.AddTags(nameTag);

Aws::EC2::Model::CreateTagsOutcome createOutcome = ec2Client.CreateTags(
        createRequest);
if (!createOutcome.IsSuccess()) {
    std::cerr << "Failed to tag ec2 instance " << instanceID <<
              " with name " << instanceName << ":" <<
              createOutcome.GetError().GetMessage() << std::endl;
    return false;
}
```

- Para obter detalhes da API, consulte CreateTagsa Referência AWS SDK for C++ da API.

Alocar um endereço IP elástico

Os exemplos de código a seguir mostram como alocar um endereço IP elástico ao Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::AllocateAddressRequest request;
    request.SetDomain(Aws::EC2::Model::DomainType::vpc);

    const Aws::EC2::Model::AllocateAddressOutcome outcome =
            ec2Client.AllocateAddress(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to allocate Elastic IP address:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    allocationId = outcome.GetResult().GetAllocationId();
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for C++ da API.

Para associar um endereço IP elástico a uma instância

Os exemplos de código a seguir mostram como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::AssociateAddressRequest associate_request;
    associate_request.SetInstanceId(instanceId);
    associate_request.SetAllocationId(allocationId);

    const Aws::EC2::Model::AssociateAddressOutcome associate_outcome =
            ec2Client.AssociateAddress(associate_request);
    if (!associate_outcome.IsSuccess()) {
        std::cerr << "Failed to associate Elastic IP address " << allocationId
```

```
                << " with instance " << instanceId << ":" <<
                associate_outcome.GetError().GetMessage() << std::endl;
    return false;
}

std::cout << "Successfully associated Elastic IP address " << allocationId
          << " with instance " << instanceId << std::endl;
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for C++ da API.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);

Aws::EC2::Model::CreateSecurityGroupRequest request;

request.SetGroupName(groupName);
request.SetDescription(description);
request.SetVpcId(vpcID);

const Aws::EC2::Model::CreateSecurityGroupOutcome outcome =
        ec2Client.CreateSecurityGroup(request);

if (!outcome.IsSuccess()) {
    std::cerr << "Failed to create security group:" <<
              outcome.GetError().GetMessage() << std::endl;
    return false;
}

std::cout << "Successfully created security group named " << groupName <<
```

```
                std::endl;
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for C++ da API.

Criar um par de chaves de segurança

Os exemplos de código a seguir mostram como criar um par de chaves de segurança para Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   Aws::EC2::EC2Client ec2Client(clientConfiguration);
   Aws::EC2::Model::CreateKeyPairRequest request;
   request.SetKeyName(keyPairName);

   Aws::EC2::Model::CreateKeyPairOutcome outcome =
ec2Client.CreateKeyPair(request);
   if (!outcome.IsSuccess()) {
       std::cerr << "Failed to create key pair:" <<
                 outcome.GetError().GetMessage() << std::endl;
   }
   else {
       std::cout << "Successfully created key pair named " <<
                 keyPairName << std::endl;
   }
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for C++ da API.

Criar e executar uma instância

Os exemplos de código a seguir mostram como criar e executar uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   Aws::EC2::EC2Client ec2Client(clientConfiguration);

   Aws::EC2::Model::RunInstancesRequest runRequest;
   runRequest.SetImageId(amiId);
   runRequest.SetInstanceType(Aws::EC2::Model::InstanceType::t1_micro);
   runRequest.SetMinCount(1);
   runRequest.SetMaxCount(1);

   Aws::EC2::Model::RunInstancesOutcome runOutcome = ec2Client.RunInstances(
           runRequest);
   if (!runOutcome.IsSuccess()) {
       std::cerr << "Failed to launch EC2 instance " << instanceName <<
                 " based on ami " << amiId << ":" <<
                 runOutcome.GetError().GetMessage() << std::endl;
       return false;
   }

   const Aws::Vector<Aws::EC2::Model::Instance> &instances =
runOutcome.GetResult().GetInstances();
   if (instances.empty()) {
       std::cerr << "Failed to launch EC2 instance " << instanceName <<
                 " based on ami " << amiId << ":" <<
                 runOutcome.GetError().GetMessage() << std::endl;
       return false;
   }

   instanceID = instances[0].GetInstanceId();
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for C++ da API.

Exclua um grupo de segurança

Os exemplos de código a seguir mostram como excluir um grupo de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DeleteSecurityGroupRequest request;

request.SetGroupId(securityGroupID);
auto outcome = ec2Client.DeleteSecurityGroup(request);

if (!outcome.IsSuccess()) {
    std::cerr << "Failed to delete security group " << securityGroupID <<
              ":" << outcome.GetError().GetMessage() << std::endl;
}
else {
    std::cout << "Successfully deleted security group " << securityGroupID <<
              std::endl;
}
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for C++ da API.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
```

```
    Aws::EC2::Model::DeleteKeyPairRequest request;

    request.SetKeyName(keyPairName);
    const Aws::EC2::Model::DeleteKeyPairOutcome outcome = ec2Client.DeleteKeyPair(
            request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to delete key pair " << keyPairName <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted key pair named " << keyPairName <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for C++ da API.

Descrever as zonas de disponibilidade

Os exemplos de código a seguir mostram como descrever as zonas de disponibilidade do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::DescribeAvailabilityZonesRequest describe_request;
    auto describe_outcome = ec2Client.DescribeAvailabilityZones(describe_request);

    if (describe_outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "ZoneName" <<
                  std::setw(20) << "State" <<
                  std::setw(32) << "Region" << std::endl;
```

```
        const auto &zones =
                describe_outcome.GetResult().GetAvailabilityZones();

        for (const auto &zone: zones) {
            Aws::String stateString =

Aws::EC2::Model::AvailabilityZoneStateMapper::GetNameForAvailabilityZoneState(
                            zone.GetState());
            std::cout << std::left <<
                      std::setw(32) << zone.GetZoneName() <<
                      std::setw(20) << stateString <<
                      std::setw(32) << zone.GetRegionName() << std::endl;
        }
    }
    else {
        std::cerr << "Failed to describe availability zones:" <<
                  describe_outcome.GetError().GetMessage() << std::endl;
        result = false;
    }
```

- Para obter detalhes da API, consulte DescribeAvailabilityZonesa Referência AWS SDK for C++ da API.

Descrever regiões

Os exemplos de código a seguir mostram como descrever regiões do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::DescribeRegionsRequest request;
    auto outcome = ec2Client.DescribeRegions(request);
    bool result = true;
    if (outcome.IsSuccess()) {
```

```
        std::cout << std::left <<
                  std::setw(32) << "RegionName" <<
                  std::setw(64) << "Endpoint" << std::endl;

        const auto &regions = outcome.GetResult().GetRegions();
        for (const auto &region: regions) {
            std::cout << std::left <<
                      std::setw(32) << region.GetRegionName() <<
                      std::setw(64) << region.GetEndpoint() << std::endl;
        }
    }
    else {
        std::cerr << "Failed to describe regions:" <<
                  outcome.GetError().GetMessage() << std::endl;
        result = false;
    }
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for C++ da API.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeInstancesRequest request;
    bool header = false;
    bool done = false;
    while (!done) {
        auto outcome = ec2Client.DescribeInstances(request);
        if (outcome.IsSuccess()) {
            if (!header) {
                std::cout << std::left <<
                          std::setw(48) << "Name" <<
```

```
                        std::setw(20) << "ID" <<
                        std::setw(25) << "Ami" <<
                        std::setw(15) << "Type" <<
                        std::setw(15) << "State" <<
                        std::setw(15) << "Monitoring" << std::endl;
                header = true;
            }

            const std::vector<Aws::EC2::Model::Reservation> &reservations =
                    outcome.GetResult().GetReservations();

            for (const auto &reservation: reservations) {
                const std::vector<Aws::EC2::Model::Instance> &instances =
                        reservation.GetInstances();
                for (const auto &instance: instances) {
                    Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                    instance.GetState().GetName());

                    Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                    instance.GetInstanceType());

                    Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                    instance.GetMonitoring().GetState());
                    Aws::String name = "Unknown";

                    const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                    auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                 [](const Aws::EC2::Model::Tag &tag)
{
                                                         return tag.GetKey() ==
"Name";
                                                 });
                    if (nameIter != tags.cend()) {
                        name = nameIter->GetValue();
                    }
                    std::cout <<
                              std::setw(48) << name <<
```

```
                                std::setw(20) << instance.GetInstanceId() <<
                                std::setw(25) << instance.GetImageId() <<
                                std::setw(15) << typeString <<
                                std::setw(15) << instanceStateString <<
                                std::setw(15) << monitorString << std::endl;
                            }
                        }

                        if (!outcome.GetResult().GetNextToken().empty()) {
                            request.SetNextToken(outcome.GetResult().GetNextToken());
                        }
                        else {
                            done = true;
                        }
                    }
                    else {
                        std::cerr << "Failed to describe EC2 instances:" <<
                                  outcome.GetError().GetMessage() << std::endl;
                        return false;
                    }
                }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for C++ da API.

Desabilitar monitoramento detalhado

Os exemplos de código a seguir mostram como desabilitar o monitoramento detalhado em uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::UnmonitorInstancesRequest unrequest;
    unrequest.AddInstanceIds(instanceId);
```

```
    unrequest.SetDryRun(true);

    auto undryRunOutcome = ec2Client.UnmonitorInstances(unrequest);
    if (undryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to disable monitoring on instance. A dry run
should trigger an error."
                <<
                std::endl;
        return false;
    }
    else if (undryRunOutcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to disable monitoring on instance " <<
                  instanceId << ": " << undryRunOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    unrequest.SetDryRun(false);
    auto unmonitorInstancesOutcome = ec2Client.UnmonitorInstances(unrequest);
    if (!unmonitorInstancesOutcome.IsSuccess()) {
        std::cout << "Failed to disable monitoring on instance " << instanceId
                  << ": " << unmonitorInstancesOutcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully disable monitoring on instance " <<
                  instanceId << std::endl;
    }
```

- Para obter detalhes da API, consulte UnmonitorInstancesa Referência AWS SDK for C++ da API.

Habilitar monitoramento

Os exemplos de código a seguir mostram como habilitar o monitoramento em uma instância do Amazon EC2 em execução.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::MonitorInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.MonitorInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to enable monitoring on instance. A dry run
should trigger an error."
                <<
                std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType()
             != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cerr << "Failed dry run to enable monitoring on instance " <<
                  instanceId << ": " << dry_run_outcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto monitorInstancesOutcome = ec2Client.MonitorInstances(request);
    if (!monitorInstancesOutcome.IsSuccess()) {
        std::cerr << "Failed to enable monitoring on instance " <<
                  instanceId << ": " <<
                  monitorInstancesOutcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully enabled monitoring on instance " <<
                  instanceId << std::endl;
    }
```

- Para obter detalhes da API, consulte MonitorInstancesa Referência AWS SDK for C++ da API.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::EC2::EC2Client ec2Client(clientConfiguration);
Aws::EC2::Model::DescribeSecurityGroupsRequest request;

if (!groupID.empty()) {
    request.AddGroupIds(groupID);
}

Aws::String nextToken;
do {
    if (!nextToken.empty()) {
        request.SetNextToken(nextToken);
    }

    auto outcome = ec2Client.DescribeSecurityGroups(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "Name" <<
                  std::setw(30) << "GroupId" <<
                  std::setw(30) << "VpcId" <<
                  std::setw(64) << "Description" << std::endl;

        const std::vector<Aws::EC2::Model::SecurityGroup> &securityGroups =
                outcome.GetResult().GetSecurityGroups();

        for (const auto &securityGroup: securityGroups) {
            std::cout << std::left <<
                      std::setw(32) << securityGroup.GetGroupName() <<
```

```
                        std::setw(30) << securityGroup.GetGroupId() <<
                        std::setw(30) << securityGroup.GetVpcId() <<
                        std::setw(64) << securityGroup.GetDescription() <<
                        std::endl;
            }
        }
        else {
            std::cerr << "Failed to describe security groups:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for C++ da API.

Obter detalhes sobre endereços IP elásticos

Os exemplos de código a seguir mostram como obter detalhes sobre endereços IP elásticos.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeAddressesRequest request;
    auto outcome = ec2Client.DescribeAddresses(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left << std::setw(20) << "InstanceId" <<
                  std::setw(15) << "Public IP" << std::setw(10) << "Domain" <<
                  std::setw(30) << "Allocation ID" << std::setw(25) <<
                  "NIC ID" << std::endl;

        const auto &addresses = outcome.GetResult().GetAddresses();
```

```
        for (const auto &address: addresses) {
            Aws::String domainString =
                    Aws::EC2::Model::DomainTypeMapper::GetNameForDomainType(
                            address.GetDomain());

            std::cout << std::left << std::setw(20) <<
                      address.GetInstanceId() << std::setw(15) <<
                      address.GetPublicIp() << std::setw(10) << domainString <<
                      std::setw(30) << address.GetAllocationId() << std::setw(25)
                      << address.GetNetworkInterfaceId() << std::endl;
        }
    }
    else {
        std::cerr << "Failed to describe Elastic IP addresses:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

- Para obter detalhes da API, consulte DescribeAddressesa Referência AWS SDK for C++ da API.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeKeyPairsRequest request;

    auto outcome = ec2Client.DescribeKeyPairs(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "Name" <<
                  std::setw(64) << "Fingerprint" << std::endl;
```

```
        const std::vector<Aws::EC2::Model::KeyPairInfo> &key_pairs =
                outcome.GetResult().GetKeyPairs();
        for (const auto &key_pair: key_pairs) {
            std::cout << std::left <<
                      std::setw(32) << key_pair.GetKeyName() <<
                      std::setw(64) << key_pair.GetKeyFingerprint() << std::endl;
        }
    }
    else {
        std::cerr << "Failed to describe key pairs:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for C++ da API.

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RebootInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.RebootInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to reboot on instance. A dry run should trigger
an error."
                <<
                std::endl;
```

```
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType()
             != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to reboot instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto outcome = ec2Client.RebootInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to reboot instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully rebooted instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for C++ da API.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2(clientConfiguration);

    Aws::EC2::Model::ReleaseAddressRequest request;
    request.SetAllocationId(allocationID);

    auto outcome = ec2.ReleaseAddress(request);
    if (!outcome.IsSuccess()) {
```

```
        std::cerr << "Failed to release Elastic IP address " <<
                  allocationID << ":" << outcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully released Elastic IP address " <<
                  allocationID << std::endl;
    }
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for C++ da API.

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::IpRange ip_range;
    ip_range.SetCidrIp("0.0.0.0/0");

    Aws::EC2::Model::IpPermission permission1;
    permission1.SetIpProtocol("tcp");
    permission1.SetToPort(80);
    permission1.SetFromPort(80);
    permission1.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission1);

    Aws::EC2::Model::IpPermission permission2;
    permission2.SetIpProtocol("tcp");
    permission2.SetToPort(22);
    permission2.SetFromPort(22);
```

```
    permission2.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission2);

    const Aws::EC2::Model::AuthorizeSecurityGroupIngressOutcome authorizeOutcome =
            ec2Client.AuthorizeSecurityGroupIngress(authorizeRequest);

    if (!authorizeOutcome.IsSuccess()) {
        std::cerr << "Failed to set ingress policy for security group " <<
                  groupName << ":" << authorizeOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    std::cout << "Successfully added ingress policy to security group " <<
              groupName << std::endl;
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for C++ da API.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::StartInstancesRequest start_request;
    start_request.AddInstanceIds(instanceId);
    start_request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.StartInstances(start_request);
    if (dry_run_outcome.IsSuccess()) {
```

```
        std::cerr
                << "Failed dry run to start instance. A dry run should trigger an
error."
                << std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to start instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    start_request.SetDryRun(false);
    auto start_instancesOutcome = ec2Client.StartInstances(start_request);

    if (!start_instancesOutcome.IsSuccess()) {
        std::cout << "Failed to start instance " << instanceId << ": " <<
                  start_instancesOutcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully started instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for C++ da API.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::StopInstancesRequest request;
```

```
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    auto dry_run_outcome = ec2Client.StopInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to stop instance. A dry run should trigger an
error."
                << std::endl;
        return false;
    }
    else if (dry_run_outcome.GetError().GetErrorType() !=
             Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to stop instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    auto outcome = ec2Client.StopInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to stop instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully stopped instance " << instanceId <<
                  std::endl;
    }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for C++ da API.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::TerminateInstancesRequest request;
    request.SetInstanceIds({instanceID});

    Aws::EC2::Model::TerminateInstancesOutcome outcome =
            ec2Client.TerminateInstances(request);
    if (outcome.IsSuccess()) {
        std::cout << "Ec2 instance '" << instanceID <<
                  "' was terminated." << std::endl;
    }
    else {
        std::cerr << "Failed to terminate ec2 instance " << instanceID <<
                  ", " <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for C++ da API.

EventBridge exemplos de uso do SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ with EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutTargetsRequest.h>
#include <aws/events/model/PutTargetsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Adicionar o destino.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::Target target;
        target.SetArn(lambda_arn);
        target.SetId(target_id);

        Aws::CloudWatchEvents::Model::PutTargetsRequest request;
        request.SetRule(rule_name);
        request.AddTargets(target);

        auto putTargetsOutcome = cwe.PutTargets(request);
        if (!putTargetsOutcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events target for rule "
                << rule_name << ": " <<
                putTargetsOutcome.GetError().GetMessage() << std::endl;
        }
```

```
        else
        {
            std::cout <<
                "Successfully created CloudWatch events target for rule "
                << rule_name << std::endl;
        }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for C++ da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutRuleRequest.h>
#include <aws/events/model/PutRuleResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Crie a regra.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;
        Aws::CloudWatchEvents::Model::PutRuleRequest request;
        request.SetName(rule_name);
        request.SetRoleArn(role_arn);
        request.SetScheduleExpression("rate(5 minutes)");
        request.SetState(Aws::CloudWatchEvents::Model::RuleState::ENABLED);

        auto outcome = cwe.PutRule(request);
```

```
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events rule " <<
                rule_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch events rule " <<
                rule_name << " with resulting Arn " <<
                outcome.GetResult().GetRuleArn() << std::endl;
        }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for C++ da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inclua os arquivos necessários.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutEventsRequest.h>
#include <aws/events/model/PutEventsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Enviar evento.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;
```

```
        Aws::CloudWatchEvents::Model::PutEventsRequestEntry event_entry;
        event_entry.SetDetail(MakeDetails(event_key, event_value));
        event_entry.SetDetailType("sampleSubmitted");
        event_entry.AddResources(resource_arn);
        event_entry.SetSource("aws-sdk-cpp-cloudwatch-example");

        Aws::CloudWatchEvents::Model::PutEventsRequest request;
        request.AddEntries(event_entry);

        auto outcome = cwe.PutEvents(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to post CloudWatch event: " <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully posted CloudWatch event" << std::endl;
        }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for C++ da API.

Exemplos de AWS Glue usando SDK para C++

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS glue)

# Set this project's name.
project("hello_glue")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
```

```
                                    # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_glue.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_glue.cpp.

```
#include <aws/core/Aws.h>
#include <aws/glue/GlueClient.h>
#include <aws/glue/model/ListJobsRequest.h>
#include <iostream>

/*
 *  A "Hello Glue" starter application which initializes an AWS Glue client and
 lists the
 *  AWS Glue job definitions.
 *
 *  main function
 *
 *  Usage: 'hello_glue'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
        Aws::Glue::GlueClient glueClient(clientConfig);

        std::vector<Aws::String> jobs;

        Aws::String nextToken;  // Used for pagination.
        do {
            Aws::Glue::Model::ListJobsRequest listJobsRequest;
            if (!nextToken.empty()) {
                listJobsRequest.SetNextToken(nextToken);
            }

            Aws::Glue::Model::ListJobsOutcome listRunsOutcome = glueClient.ListJobs(
                    listJobsRequest);

            if (listRunsOutcome.IsSuccess()) {
                const std::vector<Aws::String> &jobNames =
 listRunsOutcome.GetResult().GetJobNames();
                jobs.insert(jobs.end(), jobNames.begin(), jobNames.end());

                nextToken = listRunsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error listing jobs. "
                          << listRunsOutcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "Your account has " << jobs.size() << " jobs."
                  << std::endl;
        for (size_t i = 0; i < jobs.size(); ++i) {
            std::cout << "   " << i + 1 << ". " << jobs[i] << std::endl;
        }
    }
    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

Os exemplos de código a seguir mostram como criar um AWS Glue crawler.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::S3Target s3Target;
        s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
        Aws::Glue::Model::CrawlerTargets crawlerTargets;
        crawlerTargets.AddS3Targets(s3Target);

        Aws::Glue::Model::CreateCrawlerRequest request;
        request.SetTargets(crawlerTargets);
        request.SetName(CRAWLER_NAME);
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);
        request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
        request.SetRole(roleArn);

        Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the crawler." << std::endl;
```

```
        }
        else {
            std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName, clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for C++ da API.

Crie uma definição de trabalho

Os exemplos de código a seguir mostram como criar uma definição de trabalho AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
```

```
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for C++ da API.

Excluir um crawler

Os exemplos de código a seguir mostram como excluir um crawler AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteCrawlerRequest request;
        request.SetName(crawler);
```

```
        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for C++ da API.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteDatabaseRequest request;
        request.SetName(database);

        Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
                request);

        if (outcome.IsSuccess()) {
```

```
            std::cout << "Successfully deleted the database." << std::endl;
        }
        else {
            std::cerr << "Error deleting database. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for C++ da API.

Excluir uma definição de trabalho

Os exemplos de código a seguir mostram como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteJobRequest request;
        request.SetJobName(job);

        Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the job." << std::endl;
        }
```

```
        else {
            std::cerr << "Error deleting the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for C++ da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

        if (outcome.IsSuccess()) {
            Aws::Glue::Model::CrawlerState crawlerState =
outcome.GetResult().GetCrawler().GetState();
            std::cout << "Retrieved crawler with state " <<
                      Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                              crawlerState)
                      << "." << std::endl;
        }
```

```
        else {
            std::cerr << "Error retrieving a crawler.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for C++ da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetDatabaseRequest request;
        request.SetName(CRAWLER_DATABASE_NAME);

        Aws::Glue::Model::GetDatabaseOutcome outcome = client.GetDatabase(request);

        if (outcome.IsSuccess()) {
            const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

            std::cout << "Successfully retrieve the database\n" <<
                      database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
```

```
        }
        else {
            std::cerr << "Error getting the database.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for C++ da API.

Obter uma execução de trabalho

Os exemplos de código a seguir mostram como obter uma execução de trabalho AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetJobRunRequest jobRunRequest;
        jobRunRequest.SetJobName(jobName);
        jobRunRequest.SetRunId(jobRunID);

        Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                jobRunRequest);

        if (jobRunOutcome.IsSuccess()) {
            std::cout << "Displaying the job run JSON description." << std::endl;
            std::cout
```

```
                    <<
jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                    << std::endl;
        }
        else {
            std::cerr << "Error get a job run. "
                      << jobRunOutcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for C++ da API.

Obter execuções de um trabalho

Os exemplos de código a seguir mostram como obter execuções de um trabalho AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);

        Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                getJobRunsRequest);

        if (jobRunsOutcome.IsSuccess()) {
            std::vector<Aws::Glue::Model::JobRun> jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
            std::cout << "There are " << jobRuns.size() << " runs in the job '"
```

```
                    <<
                    jobName << "'." << std::endl;

            for (size_t i = 0; i < jobRuns.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobRuns[i].GetJobName()
                          << std::endl;
            }

            int runIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobRuns.size()) +
                    " to see details for a run: ",
                    1, static_cast<int>(jobRuns.size()));
            jobRunID = jobRuns[runIndex - 1].GetId();
        }
        else {
            std::cerr << "Error getting job runs. "
                      << jobRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for C++ da API.

Obter tabelas de um banco de dados

Os exemplos de código a seguir mostram como obter tabelas de um banco de dados em AWS Glue Data Catalog.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";
```

```
    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetTablesRequest request;
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);

        Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

        if (outcome.IsSuccess()) {
            const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
            std::cout << "The database contains " << tables.size()
                      << (tables.size() == 1 ?
                          " table." : "tables.") << std::endl;
            std::cout << "Here is a list of the tables in the database.";
            for (size_t index = 0; index < tables.size(); ++index) {
                std::cout << "    " << index + 1 << ":  " << tables[index].GetName()
                          << std::endl;
            }

            if (!tables.empty()) {
                int tableIndex = askQuestionForIntRange(
                        "Enter an index to display the database detail ",
                        1, static_cast<int>(tables.size()));
                std::cout << tables[tableIndex - 1].Jsonize().View().WriteReadable()
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error getting the tables. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for C++ da API.

Listar definições de trabalho

Os exemplos de código a seguir mostram como listas definições de trabalho AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::ListJobsRequest listJobsRequest;
        Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
                listJobsRequest);

        if (listRunsOutcome.IsSuccess()) {
            const std::vector<Aws::String> &jobNames =
listRunsOutcome.GetResult().GetJobNames();
            std::cout << "Your account has " << jobNames.size() << " jobs."
                      << std::endl;
            for (size_t i = 0; i < jobNames.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobNames[i] << std::endl;
            }
            int jobIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobNames.size()) +
                    " to see the list of runs for a job: ",
                    1, static_cast<int>(jobNames.size()));

            jobName = jobNames[jobIndex - 1];
        }
        else {
            std::cerr << "Error listing jobs. "
                      << listRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

Iniciar um crawler

Os exemplos de código a seguir mostram como iniciar um crawler AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::StartCrawlerRequest request;
       request.SetName(CRAWLER_NAME);

       Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


       if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
                                   outcome.GetError().GetErrorType())) {
           if (!outcome.IsSuccess()) {
               std::cout << "Crawler was already started." << std::endl;
           }
           else {
               std::cout << "Successfully started crawler." << std::endl;
           }

           std::cout << "This may take a while to run." << std::endl;

           Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
           int iterations = 0;
```

```
            while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
                ++iterations;
                if ((iterations % 10) == 0) { // Log status every 10 seconds.
                    std::cout << "Crawler status " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                    crawlerState)
                            << ". After " << iterations
                            << " seconds elapsed."
                            << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);

                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                            << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }

            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
```

```
            return false;
        }
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for C++ da API.

Iniciar uma execução de trabalho

Os exemplos de código a seguir mostram como iniciar uma execução de trabalho AWS Glue.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName + "/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome = client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;

            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
```

```
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
                jobRunRequest.SetRunId(jobRunId);

                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();

                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT)) {
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10 seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                          jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
                    }
                }
                else {
```

```
                    std::cerr << "Error retrieving job run state. "
                              << jobRunOutcome.GetError().GetMessage()
                              << std::endl;
                    deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                 bucketName, clientConfig);
                    return false;
                }
            }
        }
        else {
            std::cerr << "Error starting a job. " << outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                         clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for C++ da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Scenario which demonstrates using AWS Glue to add a crawler and run a job.
/*!
 \\sa runGettingStartedWithGlueScenario()
 \param bucketName: An S3 bucket created in the setup.
 \param roleName: An AWS Identity and Access Management (IAM) role created in the
 setup.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */

bool AwsDoc::Glue::runGettingStartedWithGlueScenario(const Aws::String &bucketName,
                                                     const Aws::String &roleName,
                                                     const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::Glue::GlueClient client(clientConfig);

    Aws::String roleArn;
    if (!getRoleArn(roleName, roleArn, clientConfig)) {
        std::cerr << "Error getting role ARN for role." << std::endl;
        return false;
    }

    // 1. Upload the job script to the S3 bucket.
    {
        std::cout << "Uploading the job script '"
                  << AwsDoc::Glue::PYTHON_SCRIPT
                  << "'." << std::endl;

        if (!AwsDoc::Glue::uploadFile(bucketName,
                                      AwsDoc::Glue::PYTHON_SCRIPT_PATH,
                                      AwsDoc::Glue::PYTHON_SCRIPT,
                                      clientConfig)) {
            std::cerr << "Error uploading the job file." << std::endl;
            return false;
```

```
        }
    }

    // 2. Create a crawler.
    {
        Aws::Glue::Model::S3Target s3Target;
        s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
        Aws::Glue::Model::CrawlerTargets crawlerTargets;
        crawlerTargets.AddS3Targets(s3Target);

        Aws::Glue::Model::CreateCrawlerRequest request;
        request.SetTargets(crawlerTargets);
        request.SetName(CRAWLER_NAME);
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);
        request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
        request.SetRole(roleArn);

        Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the crawler." << std::endl;
        }
        else {
            std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName, clientConfig);
            return false;
        }
    }

    // 3. Get a crawler.
    {
        Aws::Glue::Model::GetCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

        if (outcome.IsSuccess()) {
            Aws::Glue::Model::CrawlerState crawlerState =
outcome.GetResult().GetCrawler().GetState();
            std::cout << "Retrieved crawler with state " <<
                      Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
```

```
                              crawlerState)
                      << "." << std::endl;
        }
        else {
            std::cerr << "Error retrieving a crawler.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 4. Start a crawler.
    {
        Aws::Glue::Model::StartCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


        if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
                                    outcome.GetError().GetErrorType())) {
            if (!outcome.IsSuccess()) {
                std::cout << "Crawler was already started." << std::endl;
            }
            else {
                std::cout << "Successfully started crawler." << std::endl;
            }

            std::cout << "This may take a while to run." << std::endl;

            Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
            int iterations = 0;
            while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
                ++iterations;
                if ((iterations % 10) == 0) { // Log status every 10 seconds.
                    std::cout << "Crawler status " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                        crawlerState)
                              << ". After " << iterations
```

```
                            << " seconds elapsed."
                            << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);

                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                            << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }

            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 5. Get a database.
    {
        Aws::Glue::Model::GetDatabaseRequest request;
        request.SetName(CRAWLER_DATABASE_NAME);
```

```
        Aws::Glue::Model::GetDatabaseOutcome outcome = client.GetDatabase(request);

        if (outcome.IsSuccess()) {
            const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

            std::cout << "Successfully retrieve the database\n" <<
                      database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
        }
        else {
            std::cerr << "Error getting the database.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 6. Get tables.
    Aws::String tableName;
    {
        Aws::Glue::Model::GetTablesRequest request;
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);

        Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

        if (outcome.IsSuccess()) {
            const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
            std::cout << "The database contains " << tables.size()
                      << (tables.size() == 1 ?
                          " table." : "tables.") << std::endl;
            std::cout << "Here is a list of the tables in the database.";
            for (size_t index = 0; index < tables.size(); ++index) {
                std::cout << "    " << index + 1 << ":  " << tables[index].GetName()
                          << std::endl;
            }

            if (!tables.empty()) {
                int tableIndex = askQuestionForIntRange(
                        "Enter an index to display the database detail ",
                        1, static_cast<int>(tables.size()));
                std::cout << tables[tableIndex - 1].Jsonize().View().WriteReadable()
```

```
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error getting the tables. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 7. Create a job.
    {
        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 8. Start a job run.
    {
```

```
        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName + "/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome = client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;

            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
                jobRunRequest.SetRunId(jobRunId);

                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();

                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT)) {
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
```

```
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10 seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                         jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
                    }
                }
                else {
                    std::cerr << "Error retrieving job run state. "
                              << jobRunOutcome.GetError().GetMessage()
                              << std::endl;
                    deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                 bucketName, clientConfig);
                    return false;
                }
            }
        }
        else {
            std::cerr << "Error starting a job. " << outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                         clientConfig);
            return false;
        }
    }

    // 9. List the output data stored in the S3 bucket.
    {
        Aws::S3::S3Client s3Client;
        Aws::S3::Model::ListObjectsRequest request;
        request.SetBucket(bucketName);
        request.SetPrefix(OUTPUT_FILE_PREFIX);

        Aws::S3::Model::ListObjectsOutcome outcome = s3Client.ListObjects(request);
```

```
        if (outcome.IsSuccess()) {
            const std::vector<Aws::S3::Model::Object> &objects =
 outcome.GetResult().GetContents();
            std::cout << "Data from your job is in " << objects.size() <<
                      " files in the S3 bucket, " << bucketName << "." << std::endl;

            for (size_t i = 0; i < objects.size(); ++i) {
                std::cout << "    " << i + 1 << ". " << objects[i].GetKey()
                          << std::endl;
            }

            int objectIndex = askQuestionForIntRange(
                    std::string(
                            "Enter the number of a block to download it and see the
 first ") +
                    std::to_string(LINES_OF_RUN_FILE_TO_DISPLAY) +
                    " lines of JSON output in the block: ", 1,
                    static_cast<int>(objects.size()));

            Aws::String objectKey = objects[objectIndex - 1].GetKey();

            std::stringstream stringStream;
            if (getObjectFromBucket(bucketName, objectKey, stringStream,
                                    clientConfig)) {
                for (int i = 0; i < LINES_OF_RUN_FILE_TO_DISPLAY && stringStream; +
+i) {
                    std::string line;
                    std::getline(stringStream, line);
                    std::cout << "    " << line << std::endl;
                }
            }
            else {
                deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
 bucketName,
                             clientConfig);
                return false;
            }
        }
        else {
            std::cerr << "Error listing objects. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
        }
    }
```

```
    // 10. List all the jobs.
    Aws::String jobName;
    {
        Aws::Glue::Model::ListJobsRequest listJobsRequest;
        Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
                listJobsRequest);

        if (listRunsOutcome.IsSuccess()) {
            const std::vector<Aws::String> &jobNames =
listRunsOutcome.GetResult().GetJobNames();
            std::cout << "Your account has " << jobNames.size() << " jobs."
                      << std::endl;
            for (size_t i = 0; i < jobNames.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobNames[i] << std::endl;
            }
            int jobIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobNames.size()) +
                    " to see the list of runs for a job: ",
                    1, static_cast<int>(jobNames.size()));

            jobName = jobNames[jobIndex - 1];
        }
        else {
            std::cerr << "Error listing jobs. "
                      << listRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    // 11. Get the job runs for a job.
    Aws::String jobRunID;
    if (!jobName.empty()) {
        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);

        Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                getJobRunsRequest);

        if (jobRunsOutcome.IsSuccess()) {
            std::vector<Aws::Glue::Model::JobRun> jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
            std::cout << "There are " << jobRuns.size() << " runs in the job '"
```

```
                      <<
                      jobName << "'." << std::endl;

            for (size_t i = 0; i < jobRuns.size(); ++i) {
                std::cout << "   " << i + 1 << ". " << jobRuns[i].GetJobName()
                          << std::endl;
            }

            int runIndex = askQuestionForIntRange(
                    Aws::String("Enter a number between 1 and ") +
                    std::to_string(jobRuns.size()) +
                    " to see details for a run: ",
                    1, static_cast<int>(jobRuns.size()));
            jobRunID = jobRuns[runIndex - 1].GetId();
        }
        else {
            std::cerr << "Error getting job runs. "
                      << jobRunsOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    // 12. Get a single job run.
    if (!jobRunID.empty()) {
        Aws::Glue::Model::GetJobRunRequest jobRunRequest;
        jobRunRequest.SetJobName(jobName);
        jobRunRequest.SetRunId(jobRunID);

        Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                jobRunRequest);

        if (jobRunOutcome.IsSuccess()) {
            std::cout << "Displaying the job run JSON description." << std::endl;
            std::cout
                    <<
jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                    << std::endl;
        }
        else {
            std::cerr << "Error get a job run. "
                      << jobRunOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }
```

```
    return deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                        clientConfig);
}

//! Cleanup routine to delete created assets.
/*!
 \\sa deleteAssets()
 \param crawler: Name of an AWS Glue crawler.
 \param database: The name of an AWS Glue database.
 \param job: The name of an AWS Glue job.
 \param bucketName: The name of an S3 bucket.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAssets(const Aws::String &crawler, const Aws::String
 &database,
                                const Aws::String &job, const Aws::String
 &bucketName,
                                const Aws::Client::ClientConfiguration
 &clientConfig) {
    const Aws::Glue::GlueClient client(clientConfig);
    bool result = true;

    // 13. Delete a job.
    if (!job.empty()) {
        Aws::Glue::Model::DeleteJobRequest request;
        request.SetJobName(job);

        Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the job." << std::endl;
        }
        else {
            std::cerr << "Error deleting the job. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    // 14. Delete a database.
```

```
    if (!database.empty()) {
        Aws::Glue::Model::DeleteDatabaseRequest request;
        request.SetName(database);

        Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the database." << std::endl;
        }
        else {
            std::cerr << "Error deleting database. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    // 15. Delete a crawler.
    if (!crawler.empty()) {
        Aws::Glue::Model::DeleteCrawlerRequest request;
        request.SetName(crawler);

        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
 client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
    }

    // 16. Delete the job script and run data from the S3 bucket.
    result &= AwsDoc::Glue::deleteAllObjectsInS3Bucket(bucketName,
                                                       clientConfig);
    return result;
}

//! Routine which uploads a file to an S3 bucket.
/*!
```

```
 \\sa uploadFile()
 \param bucketName: An S3 bucket created in the setup.
 \param filePath: The path of the file to upload.
 \param fileName The name for the uploaded file.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool
AwsDoc::Glue::uploadFile(const Aws::String &bucketName,
                         const Aws::String &filePath,
                         const Aws::String &fileName,
                         const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          filePath.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);

    if (!*inputData) {
        std::cerr << "Error unable to read file " << filePath << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3_client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Added object '" << filePath << "' to bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
```

```
}

//! Routine which deletes all objects in an S3 bucket.
/*!
 \\sa deleteAllObjectsInS3Bucket()
 \param bucketName: The S3 bucket name.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAllObjectsInS3Bucket(const Aws::String &bucketName,
                                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::ListObjectsRequest listObjectsRequest;
    listObjectsRequest.SetBucket(bucketName);


    Aws::S3::Model::ListObjectsOutcome listObjectsOutcome = client.ListObjects(
            listObjectsRequest);

    bool result = false;
    if (listObjectsOutcome.IsSuccess()) {
        const std::vector<Aws::S3::Model::Object> &objects =
 listObjectsOutcome.GetResult().GetContents();
        if (!objects.empty()) {
            Aws::S3::Model::DeleteObjectsRequest deleteObjectsRequest;
            deleteObjectsRequest.SetBucket(bucketName);

            std::vector<Aws::S3::Model::ObjectIdentifier> objectIdentifiers;
            for (const Aws::S3::Model::Object &object: objects) {
                objectIdentifiers.push_back(

 Aws::S3::Model::ObjectIdentifier().WithKey(object.GetKey()));
            }
            Aws::S3::Model::Delete objectsDelete;
            objectsDelete.SetObjects(objectIdentifiers);
            objectsDelete.SetQuiet(true);
            deleteObjectsRequest.SetDelete(objectsDelete);

            Aws::S3::Model::DeleteObjectsOutcome deleteObjectsOutcome =
                    client.DeleteObjects(deleteObjectsRequest);

            if (!deleteObjectsOutcome.IsSuccess()) {
                std::cerr << "Error deleting objects. " <<
```

```
                            deleteObjectsOutcome.GetError().GetMessage() << std::endl;
            }
            else {
                std::cout << "Successfully deleted the objects." << std::endl;
                result = true;
            }
        }
        else {
            std::cout << "No objects to delete in '" << bucketName << "'." <<
 std::endl;
        }
    }
    else {
        std::cerr << "Error listing objects. "
                  << listObjectsOutcome.GetError().GetMessage() << std::endl;
    }

    return result;
}

//! Routine which retrieves an object from an S3 bucket.
/*!
 \\sa getObjectFromBucket()
 \param bucketName: The S3 bucket name.
 \param objectKey: The object's name.
 \param objectStream: A stream to receive the retrieved data.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::getObjectFromBucket(const Aws::String &bucketName,
                                       const Aws::String &objectKey,
                                       std::ostream &objectStream,
                                       const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome = client.GetObject(request);


    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved '" << objectKey << "'." << std::endl;
```

```
        auto &body = outcome.GetResult().GetBody();
        objectStream << body.rdbuf();
    }
    else {
        std::cerr << "Error retrieving object. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

HealthImaging exemplos de uso do SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ with HealthImaging.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá HealthImaging

O exemplo de código a seguir mostra como começar a usar o HealthImaging.

SDK for C++

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS medical-imaging)

# Set this project's name.
project("hello_health-imaging")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
```

```
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you may
 need to uncomment this
    # and set the proper subdirectory to the executable location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS "" ${CMAKE_CURRENT_BINARY_DIR}
 ${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_health_imaging.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_health_imaging.cpp.

```
#include <aws/core/Aws.h>
#include <aws/medical-imaging/MedicalImagingClient.h>
#include <aws/medical-imaging/model/ListDatastoresRequest.h>

#include <iostream>

/*
 *  A "Hello HealthImaging" starter application which initializes an AWS
 HealthImaging (HealthImaging) client
 *  and lists the HealthImaging data stores in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_health-imaging'
```

```
 *
 */
#include <aws/core/auth/AWSCredentialsProviderChain.h>
#include <aws/core/platform/Environment.h>

int main(int argc, char **argv) {
    (void) argc;
    (void) argv;
    Aws::SDKOptions options;
    //   Optional: change the log level for debugging.
    //   options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Debug;

    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::MedicalImaging::MedicalImagingClient
 medicalImagingClient(clientConfig);
        Aws::MedicalImaging::Model::ListDatastoresRequest listDatastoresRequest;

        Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
 allDataStoreSummaries;
        Aws::String nextToken; // Used for paginated results.
        do {
            if (!nextToken.empty()) {
                listDatastoresRequest.SetNextToken(nextToken);
            }
            Aws::MedicalImaging::Model::ListDatastoresOutcome listDatastoresOutcome
 =
                    medicalImagingClient.ListDatastores(listDatastoresRequest);
            if (listDatastoresOutcome.IsSuccess()) {
                const Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
 &dataStoreSummaries =
                        listDatastoresOutcome.GetResult().GetDatastoreSummaries();
                allDataStoreSummaries.insert(allDataStoreSummaries.cend(),
                                             dataStoreSummaries.cbegin(),
                                             dataStoreSummaries.cend());
                nextToken = listDatastoresOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "ListDatastores error: "
```

```
                            << listDatastoresOutcome.GetError().GetMessage() <<
 std::endl;
                break;
            }
        } while (!nextToken.empty());

        std::cout << allDataStoreSummaries.size() << " HealthImaging data "
                  << ((allDataStoreSummaries.size() == 1) ?
                      "store was retrieved." : "stores were retrieved.") <<
 std::endl;

        for (auto const &dataStoreSummary: allDataStoreSummaries) {
            std::cout << "  Datastore: " << dataStoreSummary.GetDatastoreName()
                      << std::endl;
            std::cout << "  Datastore ID: " << dataStoreSummary.GetDatastoreId()
                      << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Tópicos

- Ações
- Cenários

Ações

Excluir um conjunto de imagens

O exemplo de código a seguir mostra como excluir um conjunto de HealthImaging imagens.

SDK for C++

```
//! Routine which deletes an AWS HealthImaging image set.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::deleteImageSet(
        const Aws::String &dataStoreID, const Aws::String &imageSetID,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::DeleteImageSetRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    Aws::MedicalImaging::Model::DeleteImageSetOutcome outcome =
 client.DeleteImageSet(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted image set " << imageSetID
                  << " from data store " << dataStoreID << std::endl;
    }
    else {
        std::cerr << "Error deleting image set " << imageSetID << " from data store
 "
                  << dataStoreID << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter um quadro de imagem

O exemplo de código a seguir mostra como obter um quadro de imagem.

SDK for C++

```
//! Routine which downloads an AWS HealthImaging image frame.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param frameID: The image frame ID.
  \param jphFile: File to store the downloaded frame.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageFrame(const Aws::String &dataStoreID,
                                            const Aws::String &imageSetID,
                                            const Aws::String &frameID,
                                            const Aws::String &jphFile,
                                            const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);

    Aws::MedicalImaging::Model::GetImageFrameRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);

    Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
    imageFrameInformation.SetImageFrameId(frameID);
    request.SetImageFrameInformation(imageFrameInformation);

    Aws::MedicalImaging::Model::GetImageFrameOutcome outcome = client.GetImageFrame(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved image frame." << std::endl;
        auto &buffer = outcome.GetResult().GetImageFrameBlob();

        std::ofstream outfile(jphFile, std::ios::binary);
        outfile << buffer.rdbuf();
    }
    else {
        std::cout << "Error retrieving image frame." <<
 outcome.GetError().GetMessage()
```

```
                  << std::endl;

    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do trabalho de importação

O exemplo de código a seguir mostra como obter as propriedades do trabalho de importação.

SDK for C++

```
//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
                                           const Aws::String &importJobID,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
```

```
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome;
}
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter metadados para um conjunto de imagem

O exemplo de código a seguir mostra como obter metadados para um conjunto de HealthImaging imagens.

SDK for C++

Função de utilitário para obter metadados do conjunto de imagens.

```
//! Routine which gets a HealthImaging image set's metadata.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
```

```
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Obtenha metadados do conjunto de imagens sem versão.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 "", outputFilePath, clientConfig))
        {
            std::cout << "Successfully retrieved image set metadata." << std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

Obtenha metadados do conjunto de imagens com versão.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 versionID, outputFilePath, clientConfig))
        {
            std::cout << "Successfully retrieved image set metadata." << std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importar dados em massa para um datastore

O exemplo de código a seguir mostra como importar dados em massa para um armazenamento HealthImaging de dados.

SDK for C++

```
//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
  \param inputDirectory: The directory in the S3 bucket containing the DICOM files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory + "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
```

```
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for C++ Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Pesquisar conjuntos de imagens

O exemplo de código a seguir mostra como pesquisar conjuntos de HealthImaging imagens.

SDK for C++

A função de utilitário para pesquisar conjuntos de imagens.

```
//! Routine which searches for image sets based on defined input attributes.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param searchCriteria: A search criteria instance.
```

```
  \param imageSetResults: Vector to receive the image set IDs.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::searchImageSets(
        const Aws::String &dataStoreID,
        const Aws::MedicalImaging::Model::SearchCriteria &searchCriteria,
        Aws::Vector<Aws::String> &imageSetResults,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::SearchImageSetsRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetSearchCriteria(searchCriteria);

    Aws::String nextToken; // Used for paginated results.
    bool result = true;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::MedicalImaging::Model::SearchImageSetsOutcome outcome =
 client.SearchImageSets(
                request);
        if (outcome.IsSuccess()) {
            for (auto &imageSetMetadataSummary:
 outcome.GetResult().GetImageSetsMetadataSummaries()) {
                imageSetResults.push_back(imageSetMetadataSummary.GetImageSetId());
            }

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error: " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
    } while (!nextToken.empty());

    return result;
}
```

Caso de uso nº 1: operador EQUAL.

```
        Aws::Vector<Aws::String> imageIDsForPatientID;
        Aws::MedicalImaging::Model::SearchCriteria searchCriteriaEqualsPatientID;
        Aws::Vector<Aws::MedicalImaging::Model::SearchFilter> patientIDSearchFilters
 = {

 Aws::MedicalImaging::Model::SearchFilter().WithOperator(Aws::MedicalImaging::Model::Operato

 .WithValues({Aws::MedicalImaging::Model::SearchByAttributeValue().WithDICOMPatientId(patien
        };
        searchCriteriaEqualsPatientID.SetFilters(patientIDSearchFilters);
        bool result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
 searchCriteriaEqualsPatientID, imageIDsForPatientID,
                                                                clientConfig);
        if (result) {
            std::cout << imageIDsForPatientID.size() << " image sets found for the
 patient with ID '"
            <<  patientID << "'." << std::endl;
            for (auto &imageSetResult : imageIDsForPatientID) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
         Aws::MedicalImaging::Model::SearchByAttributeValue useCase2StartDate;

 useCase2StartDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAndTim
        .WithDICOMStudyDate("19990101")
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchByAttributeValue useCase2EndDate;

 useCase2EndDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAndTime(

 .WithDICOMStudyDate(Aws::Utils::DateTime(std::chrono::system_clock::now()).ToLocalTimeStrin
%m%d"))
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchFilter useCase2SearchFilter;
        useCase2SearchFilter.SetValues({useCase2StartDate, useCase2EndDate});
```

```
useCase2SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

       Aws::MedicalImaging::Model::SearchCriteria useCase2SearchCriteria;
       useCase2SearchCriteria.SetFilters({useCase2SearchFilter});

       Aws::Vector<Aws::String> usesCase2Results;
       result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
useCase2SearchCriteria, usesCase2Results,
                                                                clientConfig);
       if (result) {
           std::cout << usesCase2Results.size() << " image sets found for between
1999/01/01 and present."
                     <<  std::endl;
           for (auto &imageSetResult : usesCase2Results) {
               std::cout << "  Image set with ID '" << imageSetResult << std::endl;
           }
       }
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
       Aws::MedicalImaging::Model::SearchByAttributeValue useCase3StartDate;

useCase3StartDate.SetCreatedAt(Aws::Utils::DateTime("20231130T000000000Z",Aws::Utils::DateF

       Aws::MedicalImaging::Model::SearchByAttributeValue useCase3EndDate;

useCase3EndDate.SetCreatedAt(Aws::Utils::DateTime(std::chrono::system_clock::now()));

       Aws::MedicalImaging::Model::SearchFilter useCase3SearchFilter;
       useCase3SearchFilter.SetValues({useCase3StartDate, useCase3EndDate});

useCase3SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

       Aws::MedicalImaging::Model::SearchCriteria useCase3SearchCriteria;
       useCase3SearchCriteria.SetFilters({useCase3SearchFilter});

       Aws::Vector<Aws::String> usesCase3Results;
       result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
useCase3SearchCriteria, usesCase3Results,
                                                            clientConfig);
```

```
        if (result) {
            std::cout << usesCase3Results.size() << " image sets found for created
between 2023/11/30 and present."
                      <<  std::endl;
            for (auto &imageSetResult : usesCase3Results) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for C++ da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cenários

Começar a usar conjuntos de imagens e quadros de imagem

O exemplo de código a seguir mostra como importar arquivos DICOM e baixar molduras de imagem em HealthImaging.

A implementação é estruturada como um aplicativo de linha de comando de fluxo de trabalho.

- Configurar recursos para uma importação DICOM.
- Importe arquivos DICOM para um armazenamento de dados.
- Recupere os IDs do conjunto de imagens para o trabalho de importação.
- Recupere os IDs do quadro de imagem para o conjunto de imagens.
- Baixe, decodifique e verifique os quadros de imagem.
- Limpe os recursos.

SDK for C++

Crie uma AWS CloudFormation pilha com os recursos necessários.

```
    Aws::String inputBucketName;
    Aws::String outputBucketName;
```

```
    Aws::String dataStoreId;
    Aws::String roleArn;
    Aws::String stackName;

    if (askYesNoQuestion(
            "Would you like to let this workflow create the resources for you? (y/n)
")) {
        stackName = askQuestion(
                "Enter a name for the AWS CloudFormation stack to create. ");
        Aws::String dataStoreName = askQuestion(
                "Enter a name for the HealthImaging datastore to create. ");

        Aws::Map<Aws::String, Aws::String> outputs = createCloudFormationStack(
                stackName,
                dataStoreName,
                clientConfiguration);

        if (!retrieveOutputs(outputs, dataStoreId, inputBucketName,
outputBucketName,
                             roleArn)) {
            return false;
        }

        std::cout << "The following resources have been created." << std::endl;
        std::cout << "A HealthImaging datastore with ID: " << dataStoreId << "."
                  << std::endl;
        std::cout << "An Amazon S3 input bucket named: " << inputBucketName << "."
                  << std::endl;
        std::cout << "An Amazon S3 output bucket named: " << outputBucketName << "."
                  << std::endl;
        std::cout << "An IAM role with the ARN: " << roleArn << "." << std::endl;
        askQuestion("Enter return to continue.", alwaysTrueTest);
    }
    else {
        std::cout << "You have chosen to use preexisting resources:" << std::endl;
        dataStoreId = askQuestion(
                "Enter the data store ID of the HealthImaging datastore you wish to
use: ");
        inputBucketName = askQuestion(
                "Enter the name of the S3 input bucket you wish to use: ");
        outputBucketName = askQuestion(
                "Enter the name of the S3 output bucket you wish to use: ");
        roleArn = askQuestion(
```

```
                "Enter the ARN for the IAM role with the proper permissions to
import a DICOM series: ");
   }
```

Copie arquivos DICOM para o bucket de importação do Amazon S3.

```
   std::cout
           << "This workflow uses DICOM files from the National Cancer Institute
Imaging Data\n"
           << "Commons (IDC) Collections." << std::endl;
   std::cout << "Here is the link to their website." << std::endl;
   std::cout << "https://registry.opendata.aws/nci-imaging-data-commons/" <<
std::endl;
   std::cout << "We will use DICOM files stored in an S3 bucket managed by the
IDC."
             << std::endl;
   std::cout
           << "First one of the DICOM folders in the IDC collection must be copied
to your\n"
              "input S3 bucket."
           << std::endl;
   std::cout << "You have the choice of one of the following "
             << IDC_ImageChoices.size() << " folders to copy." << std::endl;

   int index = 1;
   for (auto &idcChoice: IDC_ImageChoices) {
       std::cout << index << " - " << idcChoice.mDescription << std::endl;
       index++;
   }
   int choice = askQuestionForIntRange("Choose DICOM files to import: ", 1, 4);

   Aws::String fromDirectory = IDC_ImageChoices[choice - 1].mDirectory;
   Aws::String inputDirectory = "input";

   std::cout << "The files in the directory '" << fromDirectory << "' in the bucket
'"
             << IDC_S3_BucketName << "' will be copied " << std::endl;
   std::cout << "to the folder '" << inputDirectory << "/" << fromDirectory
             << "' in the bucket '" << inputBucketName << "'." << std::endl;
   askQuestion("Enter return to start the copy.", alwaysTrueTest);

   if (!AwsDoc::Medical_Imaging::copySeriesBetweenBuckets(
```

```
            IDC_S3_BucketName,
            fromDirectory,
            inputBucketName,
            inputDirectory, clientConfiguration)) {
        std::cerr << "This workflow will exit because of an error." << std::endl;
        cleanup(stackName, dataStoreId, clientConfiguration);
        return false;
    }
```

Importe os arquivos DICOM para o armazenamento de dados do Amazon S3.

```
bool AwsDoc::Medical_Imaging::startDicomImport(const Aws::String &dataStoreID,
                                               const Aws::String &inputBucketName,
                                               const Aws::String &inputDirectory,
                                               const Aws::String &outputBucketName,
                                               const Aws::String &outputDirectory,
                                               const Aws::String &roleArn,
                                               Aws::String &importJobId,
                                               const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    bool result = false;
    if (startDICOMImportJob(dataStoreID, inputBucketName, inputDirectory,
                            outputBucketName, outputDirectory, roleArn, importJobId,
                            clientConfiguration)) {
        std::cout << "DICOM import job started with job ID " << importJobId << "."
                  << std::endl;
        result = waitImportJobCompleted(dataStoreID, importJobId,
 clientConfiguration);
        if (result) {
            std::cout << "DICOM import job completed." << std::endl;

        }
    }

    return result;
}

//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
```

```
  \param inputDirectory: The directory in the S3 bucket containing the DICOM files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory + "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}


//! Routine which waits for a DICOM import job to complete.
/*!
```

```
 * @param dataStoreID: The HealthImaging data store ID.
 * @param importJobId: The import job ID.
 * @param clientConfiguration : Aws client configuration.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::waitImportJobCompleted(const Aws::String &datastoreID,
                                                     const Aws::String &importJobId,
                                                     const
 Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MedicalImaging::Model::JobStatus jobStatus =
 Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS;
    while (jobStatus == Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS) {
        std::this_thread::sleep_for(std::chrono::seconds(1));

        Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
 getDicomImportJobOutcome = getDICOMImportJob(
                datastoreID, importJobId,
                clientConfiguration);

        if (getDicomImportJobOutcome.IsSuccess()) {
            jobStatus =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetJobStatus();

            std::cout << "DICOM import job status: " <<

 Aws::MedicalImaging::Model::JobStatusMapper::GetNameForJobStatus(
                              jobStatus) << std::endl;
        }
        else {
            std::cerr << "Failed to get import job status because "
                      << getDicomImportJobOutcome.GetError().GetMessage() <<
 std::endl;
            return false;
        }
    }

    return jobStatus == Aws::MedicalImaging::Model::JobStatus::COMPLETED;
}

//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
```

```
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
                                           const Aws::String &importJobID,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome;
}
```

Obtenha conjuntos de imagens criados pelo trabalho de importação DICOM.

```
bool
AwsDoc::Medical_Imaging::getImageSetsForDicomImportJob(const Aws::String
 &datastoreID,
                                                       const Aws::String
 &importJobId,
                                                       Aws::Vector<Aws::String>
 &imageSets,
                                                       const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome getDicomImportJobOutcome =
 getDICOMImportJob(
            datastoreID, importJobId, clientConfiguration);
    bool result = false;
    if (getDicomImportJobOutcome.IsSuccess()) {
        auto outputURI =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetOutputS3Uri();
        Aws::Http::URI uri(outputURI);
```

```
        const Aws::String &bucket = uri.GetAuthority();
        Aws::String key = uri.GetPath();

        Aws::S3::S3Client s3Client(clientConfiguration);
        Aws::S3::Model::GetObjectRequest objectRequest;
        objectRequest.SetBucket(bucket);
        objectRequest.SetKey(key + "/" + IMPORT_JOB_MANIFEST_FILE_NAME);

        auto getObjectOutcome = s3Client.GetObject(objectRequest);
        if (getObjectOutcome.IsSuccess()) {
            auto &data = getObjectOutcome.GetResult().GetBody();

            std::stringstream stringStream;
            stringStream << data.rdbuf();

            try {
                // Use JMESPath to extract the image set IDs.
                // https://jmespath.org/specification.html
                std::string jmesPathExpression =
"jobSummary.imageSetsSummary[].imageSetId";
                jsoncons::json doc = jsoncons::json::parse(stringStream.str());

                jsoncons::json imageSetsJson = jsoncons::jmespath::search(doc,

jmesPathExpression);\
                for (auto &imageSet: imageSetsJson.array_range()) {
                    imageSets.push_back(imageSet.as_string());
                }

                result = true;
            }
            catch (const std::exception &e) {
                std::cerr << e.what() << '\n';
            }

        }
        else {
            std::cerr << "Failed to get object because "
                      << getObjectOutcome.GetError().GetMessage() << std::endl;
        }

    }
    else {
        std::cerr << "Failed to get import job status because "
```

```
                  << getDicomImportJobOutcome.GetError().GetMessage() << std::endl;
    }

    return result;
}
```

Obtenha informações sobre os quadros de imagem de conjuntos de imagens.

```
bool AwsDoc::Medical_Imaging::getImageFramesForImageSet(const Aws::String
 &dataStoreID,
                                                         const Aws::String
 &imageSetID,
                                                         const Aws::String
 &outDirectory,
                                                         Aws::Vector<ImageFrameInfo>
 &imageFrames,
                                                         const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::String fileName = outDirectory + "/" + imageSetID + "_metadata.json.gzip";
    bool result = false;
    if (getImageSetMetadata(dataStoreID, imageSetID, "", // Empty string for version
 ID.
                            fileName, clientConfiguration)) {
        try {
            std::string metadataGZip;
            {
                std::ifstream inFileStream(fileName.c_str(), std::ios::binary);
                if (!inFileStream) {
                    throw std::runtime_error("Failed to open file " + fileName);
                }

                std::stringstream stringStream;
                stringStream << inFileStream.rdbuf();
                metadataGZip = stringStream.str();
            }
            std::string metadataJson = gzip::decompress(metadataGZip.data(),
                                                         metadataGZip.size());
            // Use JMESPath to extract the image set IDs.
            // https://jmespath.org/specification.html
            jsoncons::json doc = jsoncons::json::parse(metadataJson);
            std::string jmesPathExpression = "Study.Series.*.Instances[].*[]";
            jsoncons::json instances = jsoncons::jmespath::search(doc,
```

```
jmesPathExpression);
           for (auto &instance: instances.array_range()) {
               jmesPathExpression = "DICOM.RescaleSlope";
               std::string rescaleSlope = jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();
               jmesPathExpression = "DICOM.RescaleIntercept";
               std::string rescaleIntercept = jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();

               jmesPathExpression = "ImageFrames[][]";
               jsoncons::json imageFramesJson =
jsoncons::jmespath::search(instance,

jmesPathExpression);

               for (auto &imageFrame: imageFramesJson.array_range()) {
                   ImageFrameInfo imageFrameIDs;
                   imageFrameIDs.mImageSetId = imageSetID;
                   imageFrameIDs.mImageFrameId = imageFrame.find(
                           "ID")->value().as_string();
                   imageFrameIDs.mRescaleIntercept = rescaleIntercept;
                   imageFrameIDs.mRescaleSlope = rescaleSlope;
                   imageFrameIDs.MinPixelValue = imageFrame.find(
                           "MinPixelValue")->value().as_string();
                   imageFrameIDs.MaxPixelValue = imageFrame.find(
                           "MaxPixelValue")->value().as_string();

                   jmesPathExpression =
"max_by(PixelDataChecksumFromBaseToFullResolution, &Width).Checksum";
                   jsoncons::json checksumJson =
jsoncons::jmespath::search(imageFrame,

jmesPathExpression);
                   imageFrameIDs.mFullResolutionChecksum =
checksumJson.as_integer<uint32_t>();

                   imageFrames.emplace_back(imageFrameIDs);
               }
           }

           result = true;
```

```
        }
        catch (const std::exception &e) {
            std::cerr << "getImageFramesForImageSet failed because " << e.what()
                      << std::endl;
        }
    }

    return result;
}

//! Routine which gets a HealthImaging image set's metadata.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

Baixe, decodifique e verifique os quadros de imagem.

```
bool AwsDoc::Medical_Imaging::downloadDecodeAndCheckImageFrames(
        const Aws::String &dataStoreID,
        const Aws::Vector<ImageFrameInfo> &imageFrames,
        const Aws::String &outDirectory,
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::Client::ClientConfiguration clientConfiguration1(clientConfiguration);
    clientConfiguration1.executor =
 Aws::MakeShared<Aws::Utils::Threading::PooledThreadExecutor>(
            "executor", 25);
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(
            clientConfiguration1);

    Aws::Utils::Threading::Semaphore semaphore(0, 1);
    std::atomic<size_t> count(imageFrames.size());

    bool result = true;
    for (auto &imageFrame: imageFrames) {
        Aws::MedicalImaging::Model::GetImageFrameRequest getImageFrameRequest;
        getImageFrameRequest.SetDatastoreId(dataStoreID);
        getImageFrameRequest.SetImageSetId(imageFrame.mImageSetId);

        Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
        imageFrameInformation.SetImageFrameId(imageFrame.mImageFrameId);
        getImageFrameRequest.SetImageFrameInformation(imageFrameInformation);

        auto getImageFrameAsyncLambda = [&semaphore, &result, &count, imageFrame,
 outDirectory](
                const Aws::MedicalImaging::MedicalImagingClient *client,
                const Aws::MedicalImaging::Model::GetImageFrameRequest &request,
                Aws::MedicalImaging::Model::GetImageFrameOutcome outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext>
 &context) {

                if (!handleGetImageFrameResult(outcome, outDirectory, imageFrame)) {
                    std::cerr << "Failed to download and convert image frame: "
```

```
                                << imageFrame.mImageFrameId << " from image set: "
                                << imageFrame.mImageSetId << std::endl;
                    result = false;
                }

                count--;
                if (count <= 0) {

                    semaphore.ReleaseAll();
                }
        }; // End of 'getImageFrameAsyncLambda' lambda.

        medicalImagingClient.GetImageFrameAsync(getImageFrameRequest,
                                                getImageFrameAsyncLambda);
    }

    if (count > 0) {
        semaphore.WaitOne();
    }

    if (result) {
        std::cout << imageFrames.size() << " image files were downloaded."
                  << std::endl;
    }

    return result;
}

bool AwsDoc::Medical_Imaging::decodeJPHFileAndValidateWithChecksum(
        const Aws::String &jphFile,
        uint32_t crc32Checksum) {
    opj_image_t *outputImage = jphImageToOpjBitmap(jphFile);
    if (!outputImage) {
        return false;
    }

    bool result = true;
    if (!verifyChecksumForImage(outputImage, crc32Checksum)) {
        std::cerr << "The checksum for the image does not match the expected value."
                  << std::endl;
        std::cerr << "File :" << jphFile << std::endl;
        result = false;
    }
```

```
    opj_image_destroy(outputImage);

    return result;
}

opj_image *
AwsDoc::Medical_Imaging::jphImageToOpjBitmap(const Aws::String &jphFile) {
    opj_stream_t *inFileStream = nullptr;
    opj_codec_t *decompressorCodec = nullptr;
    opj_image_t *outputImage = nullptr;
    try {
        std::shared_ptr<opj_dparameters> decodeParameters =
 std::make_shared<opj_dparameters>();
        memset(decodeParameters.get(), 0, sizeof(opj_dparameters));

        opj_set_default_decoder_parameters(decodeParameters.get());

        decodeParameters->decod_format = 1; // JP2 image format.
        decodeParameters->cod_format = 2; // BMP image format.

        std::strncpy(decodeParameters->infile, jphFile.c_str(),
                     OPJ_PATH_LEN);

        inFileStream = opj_stream_create_default_file_stream(
                decodeParameters->infile, true);
        if (!inFileStream) {
            throw std::runtime_error(
                    "Unable to create input file stream for file '" + jphFile +
 "'.");
        }

        decompressorCodec = opj_create_decompress(OPJ_CODEC_JP2);
        if (!decompressorCodec) {
            throw std::runtime_error("Failed to create decompression codec.");
        }

        int decodeMessageLevel = 1;
        if (!setupCodecLogging(decompressorCodec, &decodeMessageLevel)) {
            std::cerr << "Failed to setup codec logging." << std::endl;
        }

        if (!opj_setup_decoder(decompressorCodec, decodeParameters.get())) {
            throw std::runtime_error("Failed to setup decompression codec.");
        }
```

```
        if (!opj_codec_set_threads(decompressorCodec, 4)) {
            throw std::runtime_error("Failed to set decompression codec threads.");
        }

        if (!opj_read_header(inFileStream, decompressorCodec, &outputImage)) {
            throw std::runtime_error("Failed to read header.");
        }

        if (!opj_decode(decompressorCodec, inFileStream,
                        outputImage)) {
            throw std::runtime_error("Failed to decode.");
        }

        if (DEBUGGING) {
            std::cout << "image width : " << outputImage->x1 - outputImage->x0
                      << std::endl;
            std::cout << "image height : " << outputImage->y1 - outputImage->y0
                      << std::endl;
            std::cout << "number of channels: " << outputImage->numcomps
                      << std::endl;
            std::cout << "colorspace : " << outputImage->color_space << std::endl;
        }

    } catch (const std::exception &e) {
        std::cerr << e.what() << std::endl;
        if (outputImage) {
            opj_image_destroy(outputImage);
            outputImage = nullptr;
        }
    }
    if (inFileStream) {
        opj_stream_destroy(inFileStream);
    }
    if (decompressorCodec) {
        opj_destroy_codec(decompressorCodec);
    }

    return outputImage;
}

//! Template function which converts a planar image bitmap to an interleaved image
 bitmap and
//! then verifies the checksum of the bitmap.
/*!
```

```
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
template<class myType>
bool verifyChecksumForImageForType(opj_image_t *image, uint32_t crc32Checksum) {
    uint32_t width = image->x1 - image->x0;
    uint32_t height = image->y1 - image->y0;
    uint32_t numOfChannels = image->numcomps;

    // Buffer for interleaved bitmap.
    std::vector<myType> buffer(width * height * numOfChannels);

    // Convert planar bitmap to interleaved bitmap.
    for (uint32_t channel = 0; channel < numOfChannels; channel++) {
        for (uint32_t row = 0; row < height; row++) {
            uint32_t fromRowStart = row / image->comps[channel].dy * width /
                                    image->comps[channel].dx;
            uint32_t toIndex = (row * width) * numOfChannels + channel;

            for (uint32_t col = 0; col < width; col++) {
                uint32_t fromIndex = fromRowStart + col / image->comps[channel].dx;

                buffer[toIndex] = static_cast<myType>(image-
>comps[channel].data[fromIndex]);

                toIndex += numOfChannels;
            }
        }
    }

    // Verify checksum.
    boost::crc_32_type crc32;
    crc32.process_bytes(reinterpret_cast<char *>(buffer.data()),
                        buffer.size() * sizeof(myType));

    bool result = crc32.checksum() == crc32Checksum;
    if (!result) {
        std::cerr << "verifyChecksumForImage, checksum mismatch, expected - "
                  << crc32Checksum << ", actual - " << crc32.checksum()
                  << std::endl;
    }

    return result;
```

```
}

//! Routine which verifies the checksum of an OpenJPEG image struct.
/*!
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::verifyChecksumForImage(opj_image_t *image,
                                                     uint32_t crc32Checksum) {
    uint32_t channels = image->numcomps;
    bool result = false;
    if (0 < channels) {
        // Assume the precision is the same for all channels.
        uint32_t precision = image->comps[0].prec;
        bool signedData = image->comps[0].sgnd;
        uint32_t bytes = (precision + 7) / 8;

        if (signedData) {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<int8_t>(image,
                                                                   crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<int16_t>(image,
                                                                    crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<int32_t>(image,
                                                                    crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
 signed bytes - "
                            << bytes << std::endl;
                    break;
            }
        }
        else {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<uint8_t>(image,
```

```
                                                                    crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<uint16_t>(image,
                                                                     crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<uint32_t>(image,
                                                                     crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
 unsigned bytes - "
                            << bytes << std::endl;
                    break;
            }
        }

        if (!result) {
            std::cerr << "verifyChecksumForImage, error bytes " << bytes
                      << " signed "
                      << signedData << std::endl;
        }
    }
    else {
        std::cerr << "'verifyChecksumForImage', no channels in the image."
                  << std::endl;
    }
    return result;
}
```

Limpe os recursos.

```
bool AwsDoc::Medical_Imaging::cleanup(const Aws::String &stackName,
                                      const Aws::String &dataStoreId,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    bool result = true;

    if (!stackName.empty() && askYesNoQuestion(
            "Would you like to delete the stack " + stackName + "? (y/n)")) {
```

```
        std::cout << "Deleting the image sets in the stack." << std::endl;
        result &= emptyDatastore(dataStoreId, clientConfiguration);
        printAsterisksLine();
        std::cout << "Deleting the stack." << std::endl;
        result &= deleteStack(stackName, clientConfiguration);
    }
    return result;
}

bool AwsDoc::Medical_Imaging::emptyDatastore(const Aws::String &datastoreID,
                                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {

    Aws::MedicalImaging::Model::SearchCriteria emptyCriteria;
    Aws::Vector<Aws::String> imageSetIDs;
    bool result = false;
    if (searchImageSets(datastoreID, emptyCriteria, imageSetIDs,
                        clientConfiguration)) {
        result = true;
        for (auto &imageSetID: imageSetIDs) {
            result &= deleteImageSet(datastoreID, imageSetID, clientConfiguration);
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - DeleteImageSet
  - Obtenha o DICOM ImportJob
  - GetImageFrame
  - GetImageSetMetadata
  - SearchImageSets
  - Inicie o DICOM ImportJob

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos IAM usando SDKs para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for C++ com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)
```

```
# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS iam)

# Set this project's name.
project("hello_iam")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_iam.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem iam.cpp.

```
#include <aws/core/Aws.h>
#include <aws/iam/IAMClient.h>
#include <aws/iam/model/ListPoliciesRequest.h>
#include <iostream>
#include <iomanip>

/*
 *  A "Hello IAM" starter application which initializes an AWS Identity and Access
 Management (IAM) client
 *  and lists the IAM policies.
 *
 *  main function
 *
 *  Usage: 'hello_iam'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        const Aws::String DATE_FORMAT("%Y-%m-%d");
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::IAM::IAMClient iamClient(clientConfig);
        Aws::IAM::Model::ListPoliciesRequest request;

        bool done = false;
        bool header = false;
        while (!done) {
            auto outcome = iamClient.ListPolicies(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Failed to list iam policies: " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }
```

```
            if (!header) {
                std::cout << std::left << std::setw(55) << "Name" <<
                          std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                          std::setw(64) << "Description" << std::setw(12) <<
                          "CreateDate" << std::endl;
                header = true;
            }

            const auto &policies = outcome.GetResult().GetPolicies();
            for (const auto &policy: policies) {
                std::cout << std::left << std::setw(55) <<
                          policy.GetPolicyName() << std::setw(30) <<
                          policy.GetPolicyId() << std::setw(80) << policy.GetArn()
 <<
                          std::setw(64) << policy.GetDescription() << std::setw(12)
 <<
                          policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
                          std::endl;
            }

            if (outcome.GetResult().GetIsTruncated()) {
                request.SetMarker(outcome.GetResult().GetMarker());
            } else {
                done = true;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::attachRolePolicy(const Aws::String &roleName,
                                   const Aws::String &policyArn,
                                   const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::ListAttachedRolePoliciesRequest list_request;
    list_request.SetRoleName(roleName);

    bool done = false;
    while (!done) {
        auto list_outcome = iam.ListAttachedRolePolicies(list_request);
        if (!list_outcome.IsSuccess()) {
            std::cerr << "Failed to list attached policies of role " <<
                      roleName << ": " << list_outcome.GetError().GetMessage() <<
                      std::endl;
            return false;
        }

        const auto &policies = list_outcome.GetResult().GetAttachedPolicies();
        if (std::any_of(policies.cbegin(), policies.cend(),
                        [=](const Aws::IAM::Model::AttachedPolicy &policy) {
                                return policy.GetPolicyArn() == policyArn;
                        })) {
            std::cout << "Policy " << policyArn <<
                      " is already attached to role " << roleName << std::endl;
            return true;
        }
```

```
        done = !list_outcome.GetResult().GetIsTruncated();
        list_request.SetMarker(list_outcome.GetResult().GetMarker());
    }

    Aws::IAM::Model::AttachRolePolicyRequest request;
    request.SetRoleName(roleName);
    request.SetPolicyArn(policyArn);

    Aws::IAM::Model::AttachRolePolicyOutcome outcome =
 iam.AttachRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to attach policy " << policyArn << " to role " <<
                  roleName << ": " << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully attached policy " << policyArn << " to role " <<
                  roleName << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for C++ da API.

Anexar uma política em linha a um perfil

Os exemplos de código a seguir mostram como anexar uma política em linha a um perfil do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::putRolePolicy(
        const Aws::String &roleName,
        const Aws::String &policyName,
        const Aws::String &policyDocument,
        const Aws::Client::ClientConfiguration &clientConfig) {
```

```
    Aws::IAM::IAMClient iamClient(clientConfig);
    Aws::IAM::Model::PutRolePolicyRequest request;

    request.SetRoleName(roleName);
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(policyDocument);

    Aws::IAM::Model::PutRolePolicyOutcome outcome =
 iamClient.PutRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error putting policy on role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully put the role policy." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for C++ da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createPolicy(const Aws::String &policyName,
                                      const Aws::String &rsrcArn,
                                      const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreatePolicyRequest request;
```

```
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(BuildSamplePolicyDocument(rsrcArn));

    Aws::IAM::Model::CreatePolicyOutcome outcome = iam.CreatePolicy(request);
    Aws::String result;
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating policy " << policyName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        result = outcome.GetResult().GetPolicy().GetArn();
        std::cout << "Successfully created policy " << policyName <<
                  std::endl;
    }

    return result;
}

Aws::String AwsDoc::IAM::BuildSamplePolicyDocument(const Aws::String &rsrc_arn) {
    std::stringstream stringStream;
    stringStream << "{"
                 << "  \"Version\": \"2012-10-17\","
                 << "  \"Statement\": ["
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": \"logs:CreateLogGroup\","
                 << "        \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    },"
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": ["
                 << "            \"dynamodb:DeleteItem\","
                 << "            \"dynamodb:GetItem\","
                 << "            \"dynamodb:PutItem\","
                 << "            \"dynamodb:Scan\","
                 << "            \"dynamodb:UpdateItem\""
                 << "       ],"
                 << "       \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    }"
                 << "   ]"
```

```
                << "}";

    return stringStream.str();
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for C++ da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::createIamRole(
        const Aws::String &roleName,
        const Aws::String &policy,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::CreateRoleRequest request;

    request.SetRoleName(roleName);
    request.SetAssumeRolePolicyDocument(policy);

    Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const Aws::IAM::Model::Role iamRole = outcome.GetResult().GetRole();
        std::cout << "Created role " << iamRole.GetRoleName() << "\n";
        std::cout << "ID: " << iamRole.GetRoleId() << "\n";
        std::cout << "ARN: " << iamRole.GetArn() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for C++ da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreateUserRequest create_request;
    create_request.SetUserName(userName);

    auto create_outcome = iam.CreateUser(create_request);
    if (!create_outcome.IsSuccess()) {
        std::cerr << "Error creating IAM user " << userName << ":" <<
                  create_outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created IAM user " << userName << std::endl;
    }
```

```
    return create_outcome.IsSuccess();
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for C++ da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createAccessKey(const Aws::String &userName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreateAccessKeyRequest request;
    request.SetUserName(userName);

    Aws::String result;
    Aws::IAM::Model::CreateAccessKeyOutcome outcome = iam.CreateAccessKey(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating access key for IAM user " << userName
                  << ":" << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const auto &accessKey = outcome.GetResult().GetAccessKey();
```

```
        std::cout << "Successfully created access key for IAM user " <<
                  userName << std::endl << "  aws_access_key_id = " <<
                  accessKey.GetAccessKeyId() << std::endl <<
                  " aws_secret_access_key = " << accessKey.GetSecretAccessKey() <<
                  std::endl;
        result = accessKey.GetAccessKeyId();
    }

    return result;
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for C++ da API.

Criar um alias para uma conta

Os exemplos de código a seguir mostram como criar um alias para uma conta IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::createAccountAlias(const Aws::String &aliasName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::CreateAccountAliasRequest request;
    request.SetAccountAlias(aliasName);

    Aws::IAM::Model::CreateAccountAliasOutcome outcome = iam.CreateAccountAlias(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating account alias " << aliasName << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created account alias " << aliasName <<
                  std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for C++ da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deletePolicy(const Aws::String &policyArn,
                               const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeletePolicyRequest request;
    request.SetPolicyArn(policyArn);

    auto outcome = iam.DeletePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting policy with arn " << policyArn << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted policy with arn " << policyArn
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for C++ da API.

Excluir um certificado do servidor

Os exemplos de código a seguir mostram como excluir certificado de servidor do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteServerCertificate(const Aws::String &certificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeleteServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);

    const auto outcome = iam.DeleteServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error deleting server certificate " << certificateName <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
        std::cout << "Successfully deleted server certificate " << certificateName
                  << std::endl;
    }

    return result;
}
```

- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for C++ da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::IAM::IAMClient iam(clientConfig);

Aws::IAM::Model::DeleteUserRequest request;
request.SetUserName(userName);
auto outcome = iam.DeleteUser(request);
if (!outcome.IsSuccess()) {
    std::cerr << "Error deleting IAM user " << userName << ": " <<
              outcome.GetError().GetMessage() << std::endl;;
}
else {
    std::cout << "Successfully deleted IAM user " << userName << std::endl;
}

return outcome.IsSuccess();
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for C++ da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);

    auto outcome = iam.DeleteAccessKey(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting access key " << accessKeyID << " from user "
                  << userName << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully deleted access key " << accessKeyID
                  << " for IAM user " << userName << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for C++ da API.

Excluir um alias de conta

Os exemplos de código a seguir mostram como excluir um alias de conta IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccountAlias(const Aws::String &accountAlias,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccountAliasRequest request;
    request.SetAccountAlias(accountAlias);

    const auto outcome = iam.DeleteAccountAlias(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting account alias " << accountAlias << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted account alias " << accountAlias <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for C++ da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
Aws::IAM::IAMClient iam(clientConfig);

Aws::IAM::Model::DetachRolePolicyRequest detachRequest;
detachRequest.SetRoleName(roleName);
detachRequest.SetPolicyArn(policyArn);

auto detachOutcome = iam.DetachRolePolicy(detachRequest);
if (!detachOutcome.IsSuccess()) {
    std::cerr << "Failed to detach policy " << policyArn << " from role "
              << roleName << ": " << detachOutcome.GetError().GetMessage() <<
              std::endl;
}
else {
    std::cout << "Successfully detached policy " << policyArn << " from role "
              << roleName << std::endl;
}

return detachOutcome.IsSuccess();
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for C++ da API.

Obter uma política

Os exemplos de código a seguir mostram como obter a política do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::getPolicy(const Aws::String &policyArn,
                            const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetPolicyRequest request;
    request.SetPolicyArn(policyArn);

    auto outcome = iam.GetPolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error getting policy " << policyArn << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const auto &policy = outcome.GetResult().GetPolicy();
        std::cout << "Name: " << policy.GetPolicyName() << std::endl <<
                  "ID: " << policy.GetPolicyId() << std::endl << "Arn: " <<
                  policy.GetArn() << std::endl << "Description: " <<
                  policy.GetDescription() << std::endl << "CreateDate: " <<

 policy.GetCreateDate().ToGmtString(Aws::Utils::DateFormat::ISO_8601)
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for C++ da API.

Obter um certificado do servidor

O exemplo de código a seguir mostram como obter um certificado de servidor do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::getServerCertificate(const Aws::String &certificateName,
                                       const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);

    auto outcome = iam.GetServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error getting server certificate " << certificateName <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
        const auto &certificate = outcome.GetResult().GetServerCertificate();
        std::cout << "Name: " <<

 certificate.GetServerCertificateMetadata().GetServerCertificateName()
                 << std::endl << "Body: " << certificate.GetCertificateBody() <<
                 std::endl << "Chain: " << certificate.GetCertificateChain() <<
                 std::endl;
    }

    return result;
}
```

- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for C++ da API.

Obter dados sobre a última utilização de uma chave de acesso

O exemplo de código a seguir mostra como obter dados sobre a última utilização de uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::accessKeyLastUsed(const Aws::String &secretKeyID,
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetAccessKeyLastUsedRequest request;

    request.SetAccessKeyId(secretKeyID);

    Aws::IAM::Model::GetAccessKeyLastUsedOutcome outcome = iam.GetAccessKeyLastUsed(
            request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error querying last used time for access key " <<
                  secretKeyID << ":" << outcome.GetError().GetMessage() <<
 std::endl;
    }
    else {
```

```
        Aws::String lastUsedTimeString =
                outcome.GetResult()
                        .GetAccessKeyLastUsed()
                        .GetLastUsedDate()
                        .ToGmtString(Aws::Utils::DateFormat::ISO_8601);
        std::cout << "Access key " << secretKeyID << " last used at time " <<
                  lastUsedTimeString << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetAccessKeyLastUsedda Referência AWS SDK for C++ da API.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listAccessKeys(const Aws::String &userName,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccessKeysRequest request;
```

```
    request.SetUserName(userName);

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccessKeys(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list access keys for user " << userName
                      << ": " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(32) << "UserName" <<
                      std::setw(30) << "KeyID" << std::setw(20) << "Status" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &keys = outcome.GetResult().GetAccessKeyMetadata();
        const Aws::String DATE_FORMAT = "%Y-%m-%d";

        for (const auto &key: keys) {
            Aws::String statusString =
                    Aws::IAM::Model::StatusTypeMapper::GetNameForStatusType(
                            key.GetStatus());
            std::cout << std::left << std::setw(32) << key.GetUserName() <<
                      std::setw(30) << key.GetAccessKeyId() << std::setw(20) <<
                      statusString << std::setw(20) <<
                      key.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
 std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for C++ da API.

Listar aliases de conta

Os exemplos de código a seguir mostram como listar aliases de conta IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool
AwsDoc::IAM::listAccountAliases(const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccountAliasesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccountAliases(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list account aliases: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        const auto &aliases = outcome.GetResult().GetAccountAliases();
        if (!header) {
            if (aliases.size() == 0) {
                std::cout << "Account has no aliases" << std::endl;
                break;
            }
            std::cout << std::left << std::setw(32) << "Alias" << std::endl;
            header = true;
        }
```

```
        for (const auto &alias: aliases) {
            std::cout << std::left << std::setw(32) << alias << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for C++ da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listPolicies(const Aws::Client::ClientConfiguration &clientConfig)
 {
    const Aws::String DATE_FORMAT("%Y-%m-%d");
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListPoliciesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
```

```
        auto outcome = iam.ListPolicies(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam policies: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(64) << "Description" << std::setw(12) <<
                      "CreateDate" << std::endl;
            header = true;
        }

        const auto &policies = outcome.GetResult().GetPolicies();
        for (const auto &policy: policies) {
            std::cout << std::left << std::setw(55) <<
                      policy.GetPolicyName() << std::setw(30) <<
                      policy.GetPolicyId() << std::setw(80) << policy.GetArn() <<
                      std::setw(64) << policy.GetDescription() << std::setw(12) <<
                      policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
                      std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for C++ da API.

Listar certificados do servidor

Os exemplos de código a seguir mostram como listar certificados de servidor do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listServerCertificates(
        const Aws::Client::ClientConfiguration &clientConfig) {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";

    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListServerCertificatesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListServerCertificates(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list server certificates: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(14) << "UploadDate" << std::setw(14) <<
                      "ExpirationDate" << std::endl;
            header = true;
        }

        const auto &certificates =
                outcome.GetResult().GetServerCertificateMetadataList();

        for (const auto &certificate: certificates) {
            std::cout << std::left << std::setw(55) <<
                      certificate.GetServerCertificateName() << std::setw(30) <<
                      certificate.GetServerCertificateId() << std::setw(80) <<
                      certificate.GetArn() << std::setw(14) <<
```

```
                        certificate.GetUploadDate().ToGmtString(DATE_FORMAT.c_str())
 <<
                        std::setw(14) <<
                        certificate.GetExpiration().ToGmtString(DATE_FORMAT.c_str())
 <<
                        std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for C++ da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::listUsers(const Aws::Client::ClientConfiguration &clientConfig) {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListUsersRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListUsers(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam users:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(32) << "Name" <<
                      std::setw(30) << "ID" << std::setw(64) << "Arn" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &users = outcome.GetResult().GetUsers();
        for (const auto &user: users) {
            std::cout << std::left << std::setw(32) << user.GetUserName() <<
                      std::setw(30) << user.GetUserId() << std::setw(64) <<
                      user.GetArn() << std::setw(20) <<
                      user.GetCreateDate().ToGmtString(DATE_FORMAT.c_str())
                      << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for C++ da API.

Atualizar um certificado do servidor

O exemplo de código a seguir mostra como atualizar um certificado de servidor do IAM.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateServerCertificate(const Aws::String &currentCertificateName,
                                          const Aws::String &newCertificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::UpdateServerCertificateRequest request;
    request.SetServerCertificateName(currentCertificateName);
    request.SetNewServerCertificateName(newCertificateName);

    auto outcome = iam.UpdateServerCertificate(request);
    bool result = true;
    if (outcome.IsSuccess()) {
        std::cout << "Server certificate " << currentCertificateName
                  << " successfully renamed as " << newCertificateName
                  << std::endl;
    }
    else {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error changing name of server certificate " <<
                      currentCertificateName << " to " << newCertificateName << ":"
 <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << currentCertificateName
                      << "' not found." << std::endl;
```

```
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for C++ da API.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateUser(const Aws::String &currentUserName,
                             const Aws::String &newUserName,
                             const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::UpdateUserRequest request;
    request.SetUserName(currentUserName);
    request.SetNewUserName(newUserName);

    auto outcome = iam.UpdateUser(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "IAM user " << currentUserName <<
                  " successfully updated with new user name " << newUserName <<
                  std::endl;
    }
    else {
        std::cerr << "Error updating user name for IAM user " << currentUserName <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for C++ da API.

Atualizar uma chave de acesso

O exemplo de código a seguir mostra como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  Aws::IAM::Model::StatusType status,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
```

```
    Aws::IAM::Model::UpdateAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);
    request.SetStatus(status);

    auto outcome = iam.UpdateAccessKey(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated status of access key "
                  << accessKeyID << " for user " << userName << std::endl;
    }
    else {
        std::cerr << "Error updated status of access key " << accessKeyID <<
                  " for user " << userName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for C++ da API.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace AwsDoc {
    namespace IAM {

        //! Cleanup by deleting created entities.
        /*!
          \sa DeleteCreatedEntities
          \param client: IAM client.
          \param role: IAM role.
          \param user: IAM user.
          \param policy: IAM policy.
        */
        static bool DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                          const Aws::IAM::Model::Role &role,
                                          const Aws::IAM::Model::User &user,
                                          const Aws::IAM::Model::Policy &policy);
    }

    static const int LIST_BUCKETS_WAIT_SEC = 20;

    static const char ALLOCATION_TAG[] = "example_code";
}

//! Scenario to create an IAM user, create an IAM role, and apply the role to the
 user.
// "IAM access" permissions are needed to run this code.
// "STS assume role" permissions are needed to run this code. (Note: It might be
 necessary to
//    create a custom policy).
/*!
  \sa iamCreateUserAssumeRoleScenario
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
*/
bool AwsDoc::IAM::iamCreateUserAssumeRoleScenario(
```

```
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::User user;
    Aws::IAM::Model::Role role;
    Aws::IAM::Model::Policy policy;

    // 1. Create a user.
    {
        Aws::IAM::Model::CreateUserRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String userName = "iam-demo-user-" +
                               Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetUserName(userName);

        Aws::IAM::Model::CreateUserOutcome outcome = client.CreateUser(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Error creating IAM user " << userName << ":" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            std::cout << "Successfully created IAM user " << userName << std::endl;
        }

        user = outcome.GetResult().GetUser();
    }

    // 2. Create a role.
    {
        // Get the IAM user for the current client in order to access its ARN.
        Aws::String iamUserArn;
        {
            Aws::IAM::Model::GetUserRequest request;
            Aws::IAM::Model::GetUserOutcome outcome = client.GetUser(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error getting Iam user. " <<
                          outcome.GetError().GetMessage() << std::endl;

                DeleteCreatedEntities(client, role, user, policy);
                return false;
            }
            else {
                std::cout << "Successfully retrieved Iam user "
```

```
                        << outcome.GetResult().GetUser().GetUserName()
                        << std::endl;
            }

            iamUserArn = outcome.GetResult().GetUser().GetArn();
        }

        Aws::IAM::Model::CreateRoleRequest request;

        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String roleName = "iam-demo-role-" +
                               Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetRoleName(roleName);

        // Build policy document for role.
        Aws::Utils::Document jsonStatement;
        jsonStatement.WithString("Effect", "Allow");

        Aws::Utils::Document jsonPrincipal;
        jsonPrincipal.WithString("AWS", iamUserArn);
        jsonStatement.WithObject("Principal", jsonPrincipal);
        jsonStatement.WithString("Action", "sts:AssumeRole");
        jsonStatement.WithObject("Condition", Aws::Utils::Document());

        Aws::Utils::Document policyDocument;
        policyDocument.WithString("Version", "2012-10-17");

        Aws::Utils::Array<Aws::Utils::Document> statements(1);
        statements[0] = jsonStatement;
        policyDocument.WithArray("Statement", statements);

        std::cout << "Setting policy for role\n   "
                  << policyDocument.View().WriteCompact() << std::endl;

        // Set role policy document as JSON string.
        request.SetAssumeRolePolicyDocument(policyDocument.View().WriteCompact());

        Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating role. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
```

```
        }
        else {
            std::cout << "Successfully created a role with name " << roleName
                      << std::endl;
        }

        role = outcome.GetResult().GetRole();
    }

    // 3. Create an IAM policy.
    {
        Aws::IAM::Model::CreatePolicyRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String policyName = "iam-demo-policy-" +
                                 Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetPolicyName(policyName);

        // Build IAM policy document.
        Aws::Utils::Document jsonStatement;
        jsonStatement.WithString("Effect", "Allow");
        jsonStatement.WithString("Action", "s3:ListAllMyBuckets");
        jsonStatement.WithString("Resource", "arn:aws:s3:::*");

        Aws::Utils::Document policyDocument;
        policyDocument.WithString("Version", "2012-10-17");

        Aws::Utils::Array<Aws::Utils::Document> statements(1);
        statements[0] = jsonStatement;
        policyDocument.WithArray("Statement", statements);

        std::cout << "Creating a policy.\n   " <<
policyDocument.View().WriteCompact()
                  << std::endl;

        // Set IAM policy document as JSON string.
        request.SetPolicyDocument(policyDocument.View().WriteCompact());

        Aws::IAM::Model::CreatePolicyOutcome outcome = client.CreatePolicy(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
```

```
        }
        else {
            std::cout << "Successfully created a policy with name, " << policyName
<<
                      "." << std::endl;
        }

        policy = outcome.GetResult().GetPolicy();
    }

    // 4. Assume the new role using the AWS Security Token Service (STS).
    Aws::STS::Model::Credentials credentials;
    {
        Aws::STS::STSClient stsClient(clientConfig);

        Aws::STS::Model::AssumeRoleRequest request;
        request.SetRoleArn(role.GetArn());
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String roleSessionName = "iam-demo-role-session-" +

Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetRoleSessionName(roleSessionName);

        Aws::STS::Model::AssumeRoleOutcome assumeRoleOutcome;

        // Repeatedly call AssumeRole, because there is often a delay
        // before the role is available to be assumed.
        // Repeat at most 20 times when access is denied.
        int count = 0;
        while (true) {
            assumeRoleOutcome = stsClient.AssumeRole(request);
            if (!assumeRoleOutcome.IsSuccess()) {
                if (count > 20 ||
                    assumeRoleOutcome.GetError().GetErrorType() !=
                    Aws::STS::STSErrors::ACCESS_DENIED) {
                    std::cerr << "Error assuming role after 20 tries. " <<
                              assumeRoleOutcome.GetError().GetMessage() <<
std::endl;

                    DeleteCreatedEntities(client, role, user, policy);
                    return false;
                }
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
```

```
            else {
                std::cout << "Successfully assumed the role after " << count
                          << " seconds." << std::endl;
                break;
            }
            count++;
        }

        credentials = assumeRoleOutcome.GetResult().GetCredentials();
    }


    // 5. List objects in the bucket (This should fail).
    {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
s3Client.ListBuckets();
        if (!listBucketsOutcome.IsSuccess()) {
            if (listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets. " <<
                          listBucketsOutcome.GetError().GetMessage() << std::endl;
            }
            else {
                std::cout
                        << "Access to list buckets denied because privileges have
not been applied."
                        << std::endl;
            }
        }
        else {
            std::cerr
                    << "Successfully retrieved bucket lists when this should not
happen."
                    << std::endl;
        }
    }

    // 6. Attach the policy to the role.
```

```
    {
        Aws::IAM::Model::AttachRolePolicyRequest request;
        request.SetRoleName(role.GetRoleName());
        request.WithPolicyArn(policy.GetArn());

        Aws::IAM::Model::AttachRolePolicyOutcome outcome = client.AttachRolePolicy(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
        }
        else {
            std::cout << "Successfully attached the policy with name, "
                      << policy.GetPolicyName() <<
                      ", to the role, " << role.GetRoleName() << "." << std::endl;
        }
    }

    int count = 0;
    // 7. List objects in the bucket (this should succeed).
    // Repeatedly call ListBuckets, because there is often a delay
    // before the policy with ListBucket permissions has been applied to the role.
    // Repeat at most LIST_BUCKETS_WAIT_SEC times when access is denied.
    while (true) {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
s3Client.ListBuckets();
        if (!listBucketsOutcome.IsSuccess()) {
            if ((count > LIST_BUCKETS_WAIT_SEC) ||
                listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets after " <<
LIST_BUCKETS_WAIT_SEC << " seconds. " <<
                          listBucketsOutcome.GetError().GetMessage() << std::endl;
                DeleteCreatedEntities(client, role, user, policy);
                return false;
```

```
            }

            std::this_thread::sleep_for(std::chrono::seconds(1));
        }
        else {

            std::cout << "Successfully retrieved bucket lists after " << count
                      << " seconds." << std::endl;
            break;
        }
        count++;
    }

    // 8. Delete all the created resources.
    return DeleteCreatedEntities(client, role, user, policy);
}

bool AwsDoc::IAM::DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                        const Aws::IAM::Model::Role &role,
                                        const Aws::IAM::Model::User &user,
                                        const Aws::IAM::Model::Policy &policy) {
    bool result = true;
    if (policy.ArnHasBeenSet()) {
        // Detach the policy from the role.
        {
            Aws::IAM::Model::DetachRolePolicyRequest request;
            request.SetPolicyArn(policy.GetArn());
            request.SetRoleName(role.GetRoleName());

            Aws::IAM::Model::DetachRolePolicyOutcome outcome =
 client.DetachRolePolicy(
                    request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error Detaching policy from roles. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully detached the policy with arn "
                          << policy.GetArn()
                          << " from role " << role.GetRoleName() << "." <<
 std::endl;
            }
        }
```

```
        // Delete the policy.
        {
            Aws::IAM::Model::DeletePolicyRequest request;
            request.WithPolicyArn(policy.GetArn());

            Aws::IAM::Model::DeletePolicyOutcome outcome =
client.DeletePolicy(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error deleting policy. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully deleted the policy with arn "
                          << policy.GetArn() << std::endl;
            }
        }

    }

    if (role.RoleIdHasBeenSet()) {
        // Delete the role.
        Aws::IAM::Model::DeleteRoleRequest request;
        request.SetRoleName(role.GetRoleName());

        Aws::IAM::Model::DeleteRoleOutcome outcome = client.DeleteRole(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting role. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the role with name "
                      << role.GetRoleName() << std::endl;
        }
    }

    if (user.ArnHasBeenSet()) {
        // Delete the user.
        Aws::IAM::Model::DeleteUserRequest request;
        request.WithUserName(user.GetUserName());

        Aws::IAM::Model::DeleteUserOutcome outcome = client.DeleteUser(request);
```

```
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting user. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the user with name "
                      << user.GetUserName() << std::endl;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos de Lambda usando SDKs para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for C++ com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS lambda)

# Set this project's name.
project("hello_lambda")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})
```

```
if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_lambda.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_lambda.cpp.

```
#include <aws/core/Aws.h>
#include <aws/lambda/LambdaClient.h>
#include <aws/lambda/model/ListFunctionsRequest.h>
#include <iostream>

/*
 *  A "Hello Lambda" starter application which initializes an AWS Lambda (Lambda)
 client and lists the Lambda functions.
 *
 *  main function
 *
```

```
 *  Usage: 'hello_lambda'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Lambda::LambdaClient lambdaClient(clientConfig);
        std::vector<Aws::String> functions;
        Aws::String marker; // Used for pagination.

        do {
            Aws::Lambda::Model::ListFunctionsRequest request;
            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::Lambda::Model::ListFunctionsOutcome outcome =
 lambdaClient.ListFunctions(
                    request);

            if (outcome.IsSuccess()) {
                const Aws::Lambda::Model::ListFunctionsResult &listFunctionsResult =
 outcome.GetResult();
                std::cout << listFunctionsResult.GetFunctions().size()
                          << " lambda functions were retrieved." << std::endl;

                for (const Aws::Lambda::Model::FunctionConfiguration
 &functionConfiguration: listFunctionsResult.GetFunctions()) {
                    functions.push_back(functionConfiguration.GetFunctionName());
                    std::cout << functions.size() << "  "
                              << functionConfiguration.GetDescription() <<
 std::endl;
                    std::cout << "   "
                              <<
 Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
```

```
                                        functionConfiguration.GetRuntime()) << ": "
                                << functionConfiguration.GetHandler()
                                << std::endl;
                }
                marker = listFunctionsResult.GetNextMarker();
            } else {
                std::cerr << "Error with Lambda::ListFunctions. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!marker.empty());
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_8);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
```

```
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
buffer.str().c_str(),
                                                buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome = client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " << seconds
                      << " seconds elapsed." << std::endl;
            break;
        }

        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for C++ da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    Aws::Lambda::Model::DeleteFunctionRequest request;
    request.SetFunctionName(LAMBDA_NAME);

    Aws::Lambda::Model::DeleteFunctionOutcome outcome = client.DeleteFunction(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "The lambda function was successfully deleted." << std::endl;
    }
    else {
        std::cerr << "Error with Lambda::DeleteFunction. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for C++ da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";
```

```
   Aws::Lambda::LambdaClient client(clientConfig);

       Aws::Lambda::Model::GetFunctionRequest request;
       request.SetFunctionName(functionName);

       Aws::Lambda::Model::GetFunctionOutcome outcome =
client.GetFunction(request);

       if (outcome.IsSuccess()) {
           std::cout << "Function retrieve.\n" <<

outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                     << std::endl;
       }
       else {
           std::cerr << "Error with Lambda::GetFunction. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
       }
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for C++ da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Lambda::LambdaClient client(clientConfig);
```

```
        Aws::Lambda::Model::InvokeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetLogType(logType);
        std::shared_ptr<Aws::IOStream> payload = Aws::MakeShared<Aws::StringStream>(
                "FunctionTest");
        *payload << jsonPayload.View().WriteReadable();
        request.SetBody(payload);
        request.SetContentType("application/json");
        Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

        if (outcome.IsSuccess()) {
            invokeResult = std::move(outcome.GetResult());
            result = true;
            break;
        }

        else {
            std::cerr << "Error with Lambda::InvokeRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            break;
        }
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for C++.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
```

```
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    std::vector<Aws::String> functions;
    Aws::String marker;

    do {
        Aws::Lambda::Model::ListFunctionsRequest request;
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
            std::cout << result.GetFunctions().size()
                      << " lambda functions were retrieved." << std::endl;

            for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
                functions.push_back(functionConfiguration.GetFunctionName());
                std::cout << functions.size() << "  "
                          << functionConfiguration.GetDescription() << std::endl;
                std::cout << "   "
                          << Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                  functionConfiguration.GetRuntime()) << ": "
                          << functionConfiguration.GetHandler()
                          << std::endl;
            }
            marker = result.GetNextMarker();
        }
        else {
            std::cerr << "Error with Lambda::ListFunctions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for C++ da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
```

```
        request.SetPublish(true);

        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for C++ da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
```

```
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);

        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
        }

        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for C++ da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
//! Get started with functions scenario.
/*!
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Lambda::getStartedWithFunctionsScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::Lambda::LambdaClient client(clientConfig);

    // 1. Create an AWS Identity and Access Management (IAM) role for Lambda
 function.
    Aws::String roleArn;
    if (!getIamRoleArn(roleArn, clientConfig)) {
        return false;
    }

    // 2. Create a Lambda function.
    int seconds = 0;
    do {
        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
```

```
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_8);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
 buffer.str().c_str(),
                                               buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome = client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " << seconds
                      << " seconds elapsed." << std::endl;
            break;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::INVALID_PARAMETER_VALUE &&
```

```
                 outcome.GetError().GetMessage().find("role") >= 0) {
            if ((seconds % 5) == 0) { // Log status every 10 seconds.
                std::cout
                        << "Waiting for the IAM role to become available as a
CreateFunction parameter. "
                        << seconds
                        << " seconds elapsed." << std::endl;

                std::cout << outcome.GetError().GetMessage() << std::endl;
            }
        }
        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (60 > seconds);

    std::cout << "The current Lambda function increments 1 by an input." <<
std::endl;

    // 3.  Invoke the Lambda function.
    {
        int increment = askQuestionForInt("Enter an increment integer: ");

        Aws::Lambda::Model::InvokeResult invokeResult;
        Aws::Utils::Json::JsonValue jsonPayload;
        jsonPayload.WithString("action", "increment");
        jsonPayload.WithInteger("number", increment);
        if (invokeLambdaFunction(jsonPayload, Aws::Lambda::Model::LogType::Tail,
                                 invokeResult, client)) {
            Aws::Utils::Json::JsonValue jsonValue(invokeResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                {
                    std::cout << INCREMENT_RESULT_PREFIX
                              << iter->second.AsInteger() << std::endl;
                }
```

```
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
 Aws::Utils::HashingUtils::Base64Decode(
                        invokeResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() << std::endl;
            }
        }
    }

    std::cout
            << "The Lambda function will now be updated with new code. Press return
 to continue, ";
    Aws::String answer;
    std::getline(std::cin, answer);

    // 4.  Update the Lambda function code.
    {
        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
```

```
        request.SetPublish(true);

        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "This function uses an environment variable to control the logging
level."
            << std::endl;
    std::cout
            << "UpdateFunctionConfiguration will be used to set the LOG_LEVEL to
DEBUG."
            << std::endl;
    seconds = 0;

    // 5.  Update the Lambda function configuration.
    do {
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);

        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
```

```
        }

            // RESOURCE_IN_USE: function code update not completed.
        else if (outcome.GetError().GetErrorType() !=
                 Aws::Lambda::LambdaErrors::RESOURCE_IN_USE) {
            if ((seconds % 10) == 0) { // Log status every 10 seconds.
                std::cout << "Lambda function update in progress . After " <<
seconds
                          << " seconds elapsed." << std::endl;
            }
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }

    } while (0 < seconds);

    if (0 > seconds) {
        std::cerr << "Function failed to become active." << std::endl;
    }
    else {
        std::cout << "Updated function active after " << seconds << " seconds."
                  << std::endl;
    }

    std::cout
            << "\nThe new code applies an arithmetic operator to two variables, x an
y."
            << std::endl;
    std::vector<Aws::String> operators = {"plus", "minus", "times", "divided-by"};
    for (size_t i = 0; i < operators.size(); ++i) {
        std::cout << "   " << i + 1 << " " << operators[i] << std::endl;
    }

    // 6.  Invoke the updated Lambda function.
    do {
        int operatorIndex = askQuestionForIntRange("Select an operator index 1 - 4
", 1,
                                                   4);
        int x = askQuestionForInt("Enter an integer for the x value ");
        int y = askQuestionForInt("Enter an integer for the y value ");
```

```
        Aws::Utils::Json::JsonValue calculateJsonPayload;
        calculateJsonPayload.WithString("action", operators[operatorIndex - 1]);
        calculateJsonPayload.WithInteger("x", x);
        calculateJsonPayload.WithInteger("y", y);
        Aws::Lambda::Model::InvokeResult calculatedResult;
        if (invokeLambdaFunction(calculateJsonPayload,
                                 Aws::Lambda::Model::LogType::Tail,
                                 calculatedResult, client)) {
            Aws::Utils::Json::JsonValue jsonValue(calculatedResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                std::cout << ARITHMETIC_RESULT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsInteger() << std::endl;
            }
            else if (iter != values.end() && iter->second.IsFloatingPointType()) {
                std::cout << ARITHMETIC_RESULT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsDouble() << std::endl;
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
Aws::Utils::HashingUtils::Base64Decode(
                        calculatedResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() << std::endl;
            }
        }

        answer = askQuestion("Would you like to try another operation? (y/n) ");
    } while (answer == "y");

    std::cout
            << "A list of the lambda functions will be retrieved. Press return to
continue, ";
    std::getline(std::cin, answer);

    // 7.  List the Lambda functions.

    std::vector<Aws::String> functions;
    Aws::String marker;
```

```
   do {
       Aws::Lambda::Model::ListFunctionsRequest request;
       if (!marker.empty()) {
           request.SetMarker(marker);
       }

       Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
               request);

       if (outcome.IsSuccess()) {
           const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
           std::cout << result.GetFunctions().size()
                     << " lambda functions were retrieved." << std::endl;

           for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
               functions.push_back(functionConfiguration.GetFunctionName());
               std::cout << functions.size() << "  "
                         << functionConfiguration.GetDescription() << std::endl;
               std::cout << "   "
                         << Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                 functionConfiguration.GetRuntime()) << ": "
                         << functionConfiguration.GetHandler()
                         << std::endl;
           }
           marker = result.GetNextMarker();
       }
       else {
           std::cerr << "Error with Lambda::ListFunctions. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
       }
   } while (!marker.empty());

   // 8.  Get a Lambda function.
   if (!functions.empty()) {
       std::stringstream question;
       question << "Choose a function to retrieve between 1 and " <<
functions.size()
                << " ";
       int functionIndex = askQuestionForIntRange(question.str(), 1,
```

```
 static_cast<int>(functions.size()));

        Aws::String functionName = functions[functionIndex - 1];

        Aws::Lambda::Model::GetFunctionRequest request;
        request.SetFunctionName(functionName);

        Aws::Lambda::Model::GetFunctionOutcome outcome =
 client.GetFunction(request);

        if (outcome.IsSuccess()) {
            std::cout << "Function retrieve.\n" <<

 outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                      << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::GetFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout << "The resources will be deleted. Press return to continue, ";
    std::getline(std::cin, answer);

    // 9.  Delete the Lambda function.
    bool result = deleteLambdaFunction(client);

    // 10. Delete the IAM role.
    return result && deleteIamRole(clientConfig);
}

//! Routine which invokes a Lambda function and returns the result.
/*!
 \param jsonPayload: Payload for invoke function.
 \param logType: Log type setting for invoke function.
 \param invokeResult: InvokeResult object to receive the result.
 \param client: Lambda client.
 \return bool: Successful completion.
 */
bool
AwsDoc::Lambda::invokeLambdaFunction(const Aws::Utils::Json::JsonValue &jsonPayload,
```

```
                                    Aws::Lambda::Model::LogType logType,
                                    Aws::Lambda::Model::InvokeResult &invokeResult,
                                    const Aws::Lambda::LambdaClient &client) {
   int seconds = 0;
   bool result = false;
   /*
    * In this example, the Invoke function can be called before recently created
resources are
    * available.  The Invoke function is called repeatedly until the resources are
    * available.
    */
   do {
       Aws::Lambda::Model::InvokeRequest request;
       request.SetFunctionName(LAMBDA_NAME);
       request.SetLogType(logType);
       std::shared_ptr<Aws::IOStream> payload = Aws::MakeShared<Aws::StringStream>(
               "FunctionTest");
       *payload << jsonPayload.View().WriteReadable();
       request.SetBody(payload);
       request.SetContentType("application/json");
       Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

       if (outcome.IsSuccess()) {
           invokeResult = std::move(outcome.GetResult());
           result = true;
           break;
       }

           // ACCESS_DENIED: because the role is not available yet.
           // RESOURCE_CONFLICT: because the Lambda function is being created or
updated.
       else if ((outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::ACCESS_DENIED) ||
                (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::RESOURCE_CONFLICT)) {
           if ((seconds % 5) == 0) { // Log status every 10 seconds.
               std::cout << "Waiting for the invoke api to be available, status "
<<
                         ((outcome.GetError().GetErrorType() ==
                           Aws::Lambda::LambdaErrors::ACCESS_DENIED ?
                           "ACCESS_DENIED" : "RESOURCE_CONFLICT")) << ". " <<
seconds
                         << " seconds elapsed." << std::endl;
           }
```

```
        }
        else {
            std::cerr << "Error with Lambda::InvokeRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            break;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (seconds < 60);

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

MediaConvert exemplos de uso do SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ with MediaConvert.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar trabalho de transcodificação

O exemplo de código a seguir mostra como criar um trabalho de transcodificação AWS Elemental MediaConvert.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an AWS Elemental MediaConvert job.
/*!
  \param mediaConvertRole: An Amazon Resource Name (ARN) for the AWS Identity and
                           Access Management (IAM) role for the job.
  \param fileInput: A URI to an input file that is stored in Amazon Simple Storage
 Service
                    (Amazon S3) or on an HTTP(S) server.
  \param fileOutput: A URI for an Amazon S3 output location and the output file name
 base.
  \param jobSettingsFile: An optional JSON settings file.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::MediaConvert::createJob(const Aws::String &mediaConvertRole,
                                     const Aws::String &fileInput,
                                     const Aws::String &fileOutput,
                                     const Aws::String &jobSettingsFile,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::MediaConvert::Model::CreateJobRequest createJobRequest;

    createJobRequest.SetRole(mediaConvertRole);
```

```
    Aws::Http::HeaderValueCollection hvc;
    hvc.emplace("Customer", "Amazon");
    createJobRequest.SetUserMetadata(hvc);

    if (!jobSettingsFile.empty()) // Use a JSON file for the job settings.
    {
        std::ifstream jobSettingsStream(jobSettingsFile, std::ios::ate);
        if (!jobSettingsStream) {
            std::cerr << "Unable to open the job template file." << std::endl;
            return false;
        }
        std::vector<char> buffer(jobSettingsStream.tellg());
        jobSettingsStream.seekg(0);
        jobSettingsStream.read(buffer.data(), buffer.size());
        std::string jobSettingsJSON(buffer.data(), buffer.size());
        size_t pos = jobSettingsJSON.find(INPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(INPUT_FILE_PLACEHOLDER), fileInput);
        }

        pos = jobSettingsJSON.find(OUTPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(OUTPUT_FILE_PLACEHOLDER),
fileOutput);
        }
        Aws::Utils::Json::JsonValue jsonValue(jobSettingsJSON);
        Aws::MediaConvert::Model::JobSettings jobSettings(jsonValue);

        createJobRequest.SetSettings(jobSettings);
    }
    else { // Configure the job settings programmatically.
        Aws::MediaConvert::Model::JobSettings jobSettings;
        jobSettings.SetAdAvailOffset(0);
        Aws::MediaConvert::Model::TimecodeConfig timecodeConfig;

timecodeConfig.SetSource(Aws::MediaConvert::Model::TimecodeSource::EMBEDDED);
        jobSettings.SetTimecodeConfig(timecodeConfig);

        // Configure the output group.
        Aws::MediaConvert::Model::OutputGroup outputGroup;
        outputGroup.SetName("File Group");
        Aws::MediaConvert::Model::OutputGroupSettings outputGroupSettings;
        outputGroupSettings.SetType(
                Aws::MediaConvert::Model::OutputGroupType::FILE_GROUP_SETTINGS);
```

```
        Aws::MediaConvert::Model::FileGroupSettings fileGroupSettings;
        fileGroupSettings.SetDestination(fileOutput);
        outputGroupSettings.SetFileGroupSettings(fileGroupSettings);
        outputGroup.SetOutputGroupSettings(outputGroupSettings);

        Aws::MediaConvert::Model::Output output;
        output.SetNameModifier("_1");

        Aws::MediaConvert::Model::VideoDescription videoDescription;
        videoDescription.SetScalingBehavior(
                Aws::MediaConvert::Model::ScalingBehavior::DEFAULT);
        videoDescription.SetTimecodeInsertion(
                Aws::MediaConvert::Model::VideoTimecodeInsertion::DISABLED);
        videoDescription.SetAntiAlias(Aws::MediaConvert::Model::AntiAlias::ENABLED);
        videoDescription.SetSharpness(50);

videoDescription.SetAfdSignaling(Aws::MediaConvert::Model::AfdSignaling::NONE);
        videoDescription.SetDropFrameTimecode(
                Aws::MediaConvert::Model::DropFrameTimecode::ENABLED);

videoDescription.SetRespondToAfd(Aws::MediaConvert::Model::RespondToAfd::NONE);
        videoDescription.SetColorMetadata(
                Aws::MediaConvert::Model::ColorMetadata::INSERT);

        Aws::MediaConvert::Model::VideoCodecSettings videoCodecSettings;
        videoCodecSettings.SetCodec(Aws::MediaConvert::Model::VideoCodec::H_264);
        Aws::MediaConvert::Model::H264Settings h264Settings;
        h264Settings.SetNumberReferenceFrames(3);
        h264Settings.SetSyntax(Aws::MediaConvert::Model::H264Syntax::DEFAULT);
        h264Settings.SetSoftness(0);
        h264Settings.SetGopClosedCadence(1);
        h264Settings.SetGopSize(90);
        h264Settings.SetSlices(1);
        h264Settings.SetGopBReference(
                Aws::MediaConvert::Model::H264GopBReference::DISABLED);
        h264Settings.SetSlowPal(Aws::MediaConvert::Model::H264SlowPal::DISABLED);
        h264Settings.SetSpatialAdaptiveQuantization(
                Aws::MediaConvert::Model::H264SpatialAdaptiveQuantization::ENABLED);
        h264Settings.SetTemporalAdaptiveQuantization(

Aws::MediaConvert::Model::H264TemporalAdaptiveQuantization::ENABLED);
        h264Settings.SetFlickerAdaptiveQuantization(

Aws::MediaConvert::Model::H264FlickerAdaptiveQuantization::DISABLED);
```

```
        h264Settings.SetEntropyEncoding(
                Aws::MediaConvert::Model::H264EntropyEncoding::CABAC);
        h264Settings.SetBitrate(5000000);
        h264Settings.SetFramerateControl(
                Aws::MediaConvert::Model::H264FramerateControl::SPECIFIED);
        h264Settings.SetRateControlMode(
                Aws::MediaConvert::Model::H264RateControlMode::CBR);

h264Settings.SetCodecProfile(Aws::MediaConvert::Model::H264CodecProfile::MAIN);
        h264Settings.SetTelecine(Aws::MediaConvert::Model::H264Telecine::NONE);
        h264Settings.SetMinIInterval(0);
        h264Settings.SetAdaptiveQuantization(
                Aws::MediaConvert::Model::H264AdaptiveQuantization::HIGH);
        h264Settings.SetCodecLevel(Aws::MediaConvert::Model::H264CodecLevel::AUTO);
        h264Settings.SetFieldEncoding(
                Aws::MediaConvert::Model::H264FieldEncoding::PAFF);
        h264Settings.SetSceneChangeDetect(
                Aws::MediaConvert::Model::H264SceneChangeDetect::ENABLED);
        h264Settings.SetQualityTuningLevel(
                Aws::MediaConvert::Model::H264QualityTuningLevel::SINGLE_PASS);
        h264Settings.SetFramerateConversionAlgorithm(

Aws::MediaConvert::Model::H264FramerateConversionAlgorithm::DUPLICATE_DROP);
        h264Settings.SetUnregisteredSeiTimecode(
                Aws::MediaConvert::Model::H264UnregisteredSeiTimecode::DISABLED);
        h264Settings.SetGopSizeUnits(
                Aws::MediaConvert::Model::H264GopSizeUnits::FRAMES);

h264Settings.SetParControl(Aws::MediaConvert::Model::H264ParControl::SPECIFIED);
        h264Settings.SetNumberBFramesBetweenReferenceFrames(2);

h264Settings.SetRepeatPps(Aws::MediaConvert::Model::H264RepeatPps::DISABLED);
        h264Settings.SetFramerateNumerator(30);
        h264Settings.SetFramerateDenominator(1);
        h264Settings.SetParNumerator(1);
        h264Settings.SetParDenominator(1);
        videoCodecSettings.SetH264Settings(h264Settings);
        videoDescription.SetCodecSettings(videoCodecSettings);
        output.SetVideoDescription(videoDescription);

        Aws::MediaConvert::Model::AudioDescription audioDescription;
        audioDescription.SetLanguageCodeControl(
                Aws::MediaConvert::Model::AudioLanguageCodeControl::FOLLOW_INPUT);
        audioDescription.SetAudioSourceName(AUDIO_SOURCE_NAME);
```

```
        Aws::MediaConvert::Model::AudioCodecSettings audioCodecSettings;
        audioCodecSettings.SetCodec(Aws::MediaConvert::Model::AudioCodec::AAC);
        Aws::MediaConvert::Model::AacSettings aacSettings;
        aacSettings.SetAudioDescriptionBroadcasterMix(

Aws::MediaConvert::Model::AacAudioDescriptionBroadcasterMix::NORMAL);
        aacSettings.SetRateControlMode(
                Aws::MediaConvert::Model::AacRateControlMode::CBR);
        aacSettings.SetCodecProfile(Aws::MediaConvert::Model::AacCodecProfile::LC);
        aacSettings.SetCodingMode(
                Aws::MediaConvert::Model::AacCodingMode::CODING_MODE_2_0);
        aacSettings.SetRawFormat(Aws::MediaConvert::Model::AacRawFormat::NONE);
        aacSettings.SetSampleRate(48000);

aacSettings.SetSpecification(Aws::MediaConvert::Model::AacSpecification::MPEG4);
        aacSettings.SetBitrate(64000);
        audioCodecSettings.SetAacSettings(aacSettings);
        audioDescription.SetCodecSettings(audioCodecSettings);
        Aws::Vector<Aws::MediaConvert::Model::AudioDescription> audioDescriptions;
        audioDescriptions.emplace_back(audioDescription);
        output.SetAudioDescriptions(audioDescriptions);

        Aws::MediaConvert::Model::ContainerSettings mp4container;
        mp4container.SetContainer(Aws::MediaConvert::Model::ContainerType::MP4);
        Aws::MediaConvert::Model::Mp4Settings mp4Settings;
        mp4Settings.SetCslgAtom(Aws::MediaConvert::Model::Mp4CslgAtom::INCLUDE);

mp4Settings.SetFreeSpaceBox(Aws::MediaConvert::Model::Mp4FreeSpaceBox::EXCLUDE);
        mp4Settings.SetMoovPlacement(
                Aws::MediaConvert::Model::Mp4MoovPlacement::PROGRESSIVE_DOWNLOAD);
        mp4container.SetMp4Settings(mp4Settings);
        output.SetContainerSettings(mp4container);

        outputGroup.AddOutputs(output);
        jobSettings.AddOutputGroups(outputGroup);

        // Configure inputs.
        Aws::MediaConvert::Model::Input input;
        input.SetFilterEnable(Aws::MediaConvert::Model::InputFilterEnable::AUTO);
        input.SetPsiControl(Aws::MediaConvert::Model::InputPsiControl::USE_PSI);
        input.SetFilterStrength(0);

input.SetDeblockFilter(Aws::MediaConvert::Model::InputDeblockFilter::DISABLED);
```

```
 input.SetDenoiseFilter(Aws::MediaConvert::Model::InputDenoiseFilter::DISABLED);
        input.SetTimecodeSource(
                Aws::MediaConvert::Model::InputTimecodeSource::EMBEDDED);
        input.SetFileInput(fileInput);

        Aws::MediaConvert::Model::AudioSelector audioSelector;
        audioSelector.SetOffset(0);
        audioSelector.SetDefaultSelection(
                Aws::MediaConvert::Model::AudioDefaultSelection::NOT_DEFAULT);
        audioSelector.SetProgramSelection(1);
        audioSelector.SetSelectorType(
                Aws::MediaConvert::Model::AudioSelectorType::TRACK);
        audioSelector.AddTracks(1);
        input.AddAudioSelectors(AUDIO_SOURCE_NAME, audioSelector);

        Aws::MediaConvert::Model::VideoSelector videoSelector;
        videoSelector.SetColorSpace(Aws::MediaConvert::Model::ColorSpace::FOLLOW);
        input.SetVideoSelector(videoSelector);

        jobSettings.AddInputs(input);

        createJobRequest.SetSettings(jobSettings);
    }

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);
    Aws::MediaConvert::Model::CreateJobOutcome outcome = client.CreateJob(
            createJobRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Job successfully created with ID - "
                  << outcome.GetResult().GetJob().GetId() << std::endl;
    }
    else {
        std::cerr << "Error CreateJob - " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for C++ da API.

Obter um trabalho de transcodificação

Os exemplos de código a seguir mostram como obter um trabalho de transcodificação AWS Elemental MediaConvert.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the information for a specific completed transcoding job.
/*!
  \param jobID: A job ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::getJob(const Aws::String &jobID,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    Aws::MediaConvert::Model::GetJobRequest request;
    request.SetId(jobID);
    const Aws::MediaConvert::Model::GetJobOutcome outcome = client.GetJob(
            request);
    if (outcome.IsSuccess()) {
        std::cout << outcome.GetResult().GetJob().Jsonize().View().WriteReadable()
                  << std::endl;
    }
    else {
        std::cerr << "DescribeEndpoints error - " << outcome.GetError().GetMessage()
                  << std::endl;
    }


    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for C++ da API.

Listar trabalhos de transcodificação

O exemplo de código a seguir mostra como listar trabalhos transcodificação AWS Elemental MediaConvert.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of created jobs.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::listJobs(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    bool result = true;
    Aws::String nextToken; // Used to handle paginated results.
    do {
        Aws::MediaConvert::Model::ListJobsRequest request;
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }
        const Aws::MediaConvert::Model::ListJobsOutcome outcome = client.ListJobs(
                request);
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::MediaConvert::Model::Job> &jobs =
                    outcome.GetResult().GetJobs();
            std::cout << jobs.size() << " jobs retrieved." << std::endl;
            for (const Aws::MediaConvert::Model::Job &job: jobs) {
                std::cout << "  " << job.Jsonize().View().WriteReadable() <<
 std::endl;
            }
```

```
            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "DescribeEndpoints error - " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;

        }
    } while (!nextToken.empty());


    return result;
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for C++ da API.

Exemplos Amazon RDS usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon RDS

O exemplo de código a seguir mostra como começar a usar o Amazon RDS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_rds")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
```

```
                                    # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_rds.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_rds.cpp.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBInstancesRequest.h>
#include <iostream>

/*
 *  A "Hello Rds" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client and
 *  describes the Amazon RDS instances.
 *
 *  main function
 *
 *  Usage: 'hello_rds'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
        Aws::RDS::RDSClient rdsClient(clientConfig);
        Aws::String marker;
        std::vector<Aws::String> instanceDBIDs;

        do {
            Aws::RDS::Model::DescribeDBInstancesRequest request;

            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
                    rdsClient.DescribeDBInstances(request);

            if (outcome.IsSuccess()) {
                for (auto &instance: outcome.GetResult().GetDBInstances()) {
                    instanceDBIDs.push_back(instance.GetDBInstanceIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
                result = 1;
                std::cerr << "Error with RDS::DescribeDBInstances. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!marker.empty());

        std::cout << instanceDBIDs.size() << " RDS instances found." << std::endl;
        for (auto &instanceDBID: instanceDBIDs) {
            std::cout << "   Instance: " << instanceDBID << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

Os códigos de exemplo a seguir mostram como criar uma instância do Amazon RDS e aguardar até que se torne disponível.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBInstanceRequest request;
    request.SetDBName(DB_NAME);
    request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetEngine(engineVersion.GetEngine());
    request.SetEngineVersion(engineVersion.GetEngineVersion());
    request.SetDBInstanceClass(dbInstanceClass);
    request.SetStorageType(DB_STORAGE_TYPE);
    request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
    request.SetMasterUsername(administratorName);
    request.SetMasterUserPassword(administratorPassword);

    Aws::RDS::Model::CreateDBInstanceOutcome outcome =
            client.CreateDBInstance(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB instance creation has started."
```

```
                    << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for C ++.

Criar um grupo de parâmetros de banco de dados

Os exemplos de código a seguir mostram como criar um grupo de parâmetros do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example parameter group.");

        Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
                client.CreateDBParameterGroup(request);

        if (outcome.IsSuccess()) {
```

```
            std::cout << "The DB parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for C++ da API.

Criar um snapshot de uma instância de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de uma instância do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
```

```
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for C++.

Excluir uma instância de banco de dados

Os exemplos de código a seguir mostram como excluir uma instância do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);
```

```
            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for C ++.

Excluir um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DeleteDBParameterGroupRequest request;
        request.SetDBParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
                client.DeleteDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
```

```
        }
        else {
            std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for C++ Referência da API.

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
```

```
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for C++.

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros de do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
        }

        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for C++ da API.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Amazon RDS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,
                                      Aws::Vector<Aws::RDS::Model::DBEngineVersion>
 &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
        std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for C++ da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever opções para instâncias do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
```

```
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
{
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available micro DB instance classes for your database engine
are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
```

```
    return true;
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for C++ API.

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
                                  const Aws::String &namePrefix,
                                  const Aws::String &source,
```

```
                                    Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                    const Aws::RDS::RDSClient &client) {
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeDBParametersRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBParametersOutcome outcome =
                client.DescribeDBParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for C++.

Descrever os snapshots das instâncias de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de instâncias do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for C++.

Atualizar os parâmetros em um grupo de parâmetros de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::ModifyDBParameterGroupRequest request;
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetParameters(updateParameters);

    Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
            client.ModifyDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully modified."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for C++ da API.

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon RDS instance and demonstrates several operations
//! on that instance.
/*!
 \sa gettingStartedWithDBInstances()
 \param clientConfiguration: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::gettingStartedWithDBInstances(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);

    printAsterisksLine();
```

```
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon RDS)"
              << std::endl;
    std::cout << "get started with DB instances demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB parameter group named '" <<
              PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB parameter group already exists.
        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' does not exist." << std::endl;
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!parameterGroupFound) {
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available engine versions for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
```

```
        }

        std::cout << "Getting available database engine versions for " << DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family << std::endl;
            }
        }

        int choice = askQuestionForIntRange("Which family do you want to use? ", 1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB parameter group.
        Aws::RDS::Model::CreateDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example parameter group.");

        Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
                client.CreateDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your parameter group."
              << std::endl;
```

```
    Aws::String marker;
    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB parameter group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, AUTO_INCREMENT_PREFIX, NO_SOURCE,
                         autoIncrementParameters,
                         client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;

    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value in the range ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
                updateParameters.push_back(autoIncParameter);

            }
            else {
                std::cerr << "Error parsing " << autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the group.
```

```
        Aws::RDS::Model::ModifyDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
                client.ModifyDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a source
of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, NO_NAME_PREFIX, "user",
userParameters,
                         client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB instance." << std::endl;

    Aws::RDS::Model::DBInstance dbInstance;
    // 7.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
```

```
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters): ");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of available engine versions.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily, engineVersions,
                                 client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "The available engines for your parameter group are:" <<
std::endl;

        int index = 1;
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion: engineVersions)
{
            std::cout << "  " << index << ": " << engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ", 1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion = engineVersions[choice
-
                                                                                1];

        Aws::String dbInstanceClass;
        // 9.  Get a list of micro instance classes.
        if (!chooseMicroDBInstanceClass(engineVersion.GetEngine(),
                                        engineVersion.GetEngineVersion(),
                                        dbInstanceClass,
```

```
                                        client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
                  << "The DB instance is configured to use your custom parameter
group '"
                  << PARAMETER_GROUP_NAME << "',\n"
                  << "selected engine version " << engineVersion.GetEngineVersion()
                  << ",\n"
                  << "selected DB instance class '" << dbInstanceClass << "',"
                  << " and " << DB_ALLOCATED_STORAGE << " GiB of " <<
DB_STORAGE_TYPE
                  << " storage.\nThis typically takes several minutes." <<
std::endl;

        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBName(DB_NAME);
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetEngine(engineVersion.GetEngine());
        request.SetEngineVersion(engineVersion.GetEngineVersion());
        request.SetDBInstanceClass(dbInstanceClass);
        request.SetStorageType(DB_STORAGE_TYPE);
        request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }
```

```
    }

    std::cout << "Waiting for the DB instance to become available." << std::endl;

    int counter = 0;
    // 11. Wait for the DB instance to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");

    if (dbInstance.GetDBInstanceStatus() == "available") {
        std::cout << "The DB instance has been created." << std::endl;
    }

    printAsterisksLine();

    // 12. Display the connection string that can be used to connect a 'mysql' shell
 to the database.
    displayConnection(dbInstance);

    printAsterisksLine();

    if (askYesNoQuestion(
            "Do you want to create a snapshot of your DB instance (y/n)? ")) {
```

```
        Aws::String snapshotID(DB_INSTANCE_IDENTIFIER + "-" +
                               Aws::String(Aws::Utils::UUID::RandomUUID()));
        {
            std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
            std::cout << "This typically takes a few minutes." << std::endl;

            // 13. Create a snapshot of the DB instance.
            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
        }

        std::cout << "Waiting for snapshot to become available." << std::endl;

        Aws::RDS::Model::DBSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

```
            // 14. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
                return false;
            }

            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");

        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB instance and parameter group (y/n)? ")) {
        result = cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
    }

    return result;
}
```

```
//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
                                  const Aws::String &namePrefix,
                                  const Aws::String &source,
                                  Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                  const Aws::RDS::RDSClient &client) {
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeDBParametersRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBParametersOutcome outcome =
                client.DescribeDBParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }
```

```
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,
                                      Aws::Vector<Aws::RDS::Model::DBEngineVersion>
 &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
            client.DescribeDBEngineVersions(request);

    if (outcome.IsSuccess()) {
        engineVersionsResult = outcome.GetResult().GetDBEngineVersions();
    }
    else {
```

```
        std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}


//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
```

```
}


//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
```

```
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available micro DB instance classes for your database engine
 are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
*/
bool AwsDoc::RDS::cleanUpResources(const Aws::String &parameterGroupName,
                                   const Aws::String &dbInstanceIdentifier,
                                   const Aws::RDS::RDSClient &client) {
    bool result = true;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 15. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);
```

```
            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        std::cout
                << "Waiting for DB instance to delete before deleting the parameter
group."
                << std::endl;
        std::cout << "This may take a while." << std::endl;

        int counter = 0;
        Aws::RDS::Model::DBInstance dbInstance;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 800) {
                std::cerr << "Wait for instance to delete timed out ofter " <<
counter
                          << " seconds." << std::endl;
                return false;
            }

            dbInstance = Aws::RDS::Model::DBInstance();
            // 16. Wait for the DB instance to be deleted.
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }

            if (dbInstance.DBInstanceIdentifierHasBeenSet() && (counter % 20) == 0)
{
                std::cout << "Current DB instance status is '"
                          << dbInstance.GetDBInstanceStatus()
                          << "' after " << counter << " seconds." << std::endl;
```

```
            }
        } while (dbInstance.DBInstanceIdentifierHasBeenSet());
    }

    if (!parameterGroupName.empty()) {
        // 17. Delete the parameter group.
        Aws::RDS::Model::DeleteDBParameterGroupRequest request;
        request.SetDBParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
                client.DeleteDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters

- DescribeDBSnapshots
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ParameterGroup

Exemplos Amazon S3 usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for C++ com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS s3)
```

```
# Set this project's name.
project("hello_s3")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_s3.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_s3.cpp.

```
#include <aws/core/Aws.h>
```

```
#include <aws/s3/S3Client.h>
#include <iostream>
#include <aws/core/auth/AWSCredentialsProviderChain.h>
using namespace Aws;
using namespace Aws::Auth;

/*
 *  A "Hello S3" starter application which initializes an Amazon Simple Storage
 Service (Amazon S3) client
 *  and lists the Amazon S3 buckets in the selected region.
 *
 *  main function
 *
 *  Usage: 'hello_s3'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        // You don't normally have to test that you are authenticated. But the S3
 service permits anonymous requests, thus the s3Client will return "success" and 0
 buckets even if you are unauthenticated, which can be confusing to a new user.
        auto provider = Aws::MakeShared<DefaultAWSCredentialsProviderChain>("alloc-
tag");
        auto creds = provider->GetAWSCredentials();
        if (creds.IsEmpty()) {
            std::cerr << "Failed authentication" << std::endl;
        }

        Aws::S3::S3Client s3Client(clientConfig);
        auto outcome = s3Client.ListBuckets();

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
            result = 1;
```

```
        } else {
            std::cout << "Found " << outcome.GetResult().GetBuckets().size()
                      << " buckets\n";
            for (auto &bucket: outcome.GetResult().GetBuckets()) {
                std::cout << bucket.GetName() << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma política a um bucket

Os exemplos de código a seguir mostram como adicionar uma política a um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutBucketPolicy(const Aws::String &bucketName,
                                 const Aws::String &policyBody,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);
```

```
    std::shared_ptr<Aws::StringStream> request_body =
            Aws::MakeShared<Aws::StringStream>("");
    *request_body << policyBody;

    Aws::S3::Model::PutBucketPolicyRequest request;
    request.SetBucket(bucketName);
    request.SetBody(request_body);

    Aws::S3::Model::PutBucketPolicyOutcome outcome =
            s3_client.PutBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketPolicy: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Set the following policy body for the bucket '" <<
                  bucketName << "':" << std::endl << std::endl;
        std::cout << policyBody << std::endl;
    }

    return outcome.IsSuccess();
}


//! Build a policy JSON string.
/*!
  \sa GetPolicyString()
  \param userArn Aws user Amazon Resource Name (ARN).
      For more information, see https://docs.aws.amazon.com/IAM/latest/UserGuide/
reference_identifiers.html#identifiers-arns.
  \param bucketName Name of a bucket.
*/

Aws::String GetPolicyString(const Aws::String &userArn,
                            const Aws::String &bucketName) {
    return
            "{\n"
            "   \"Version\":\"2012-10-17\",\n"
            "   \"Statement\":[\n"
            "       {\n"
            "           \"Sid\": \"1\",\n"
            "           \"Effect\": \"Allow\",\n"
            "           \"Principal\": {\n"
```

```
            "                \"AWS\": \""
            + userArn +
            "\"\n""            },\n"
            "            \"Action\": [ \"s3:GetObject\" ],\n"
            "            \"Resource\": [ \"arn:aws:s3:::"
            + bucketName +
            "/*\" ]\n"
            "        }\n"
            "    ]\n"
            "}";
}
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for C++ da API.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::CopyObject(const Aws::String &objectKey, const Aws::String
 &fromBucket, const Aws::String &toBucket,
                            const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CopyObjectRequest request;

    request.WithCopySource(fromBucket + "/" + objectKey)
            .WithKey(objectKey)
            .WithBucket(toBucket);

    Aws::S3::Model::CopyObjectOutcome outcome = client.CopyObject(request);
    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: CopyObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
```

```
    }
    else {
        std::cout << "Successfully copied " << objectKey << " from " << fromBucket
 <<
                  " to " << toBucket << "." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for C++ da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::CreateBucket(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CreateBucketRequest request;
    request.SetBucket(bucketName);

    //TODO(user): Change the bucket location constraint enum to your target Region.
    if (clientConfig.region != "us-east-1") {
        Aws::S3::Model::CreateBucketConfiguration createBucketConfig;
        createBucketConfig.SetLocationConstraint(

 Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                        clientConfig.region));
        request.SetCreateBucketConfiguration(createBucketConfig);
    }
```

```
    Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);
    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: CreateBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Created bucket " << bucketName <<
                  " in the specified AWS Region." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for C++ da API.

Excluir uma política de um bucket

Os exemplos de código a seguir mostram como excluir uma política de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucketPolicy(const Aws::String &bucketName,
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketPolicyOutcome outcome =
 client.DeleteBucketPolicy(request);

    if (!outcome.IsSuccess()) {
```

```
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucketPolicy: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Policy was deleted from the bucket." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for C++ da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucket(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration &clientConfig)
 {

    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucket: " <<
```

```
                    err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "The bucket was deleted" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for C++ da API.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteObject(const Aws::String &objectKey,
                              const Aws::String &fromBucket,
                              const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectRequest request;

    request.WithKey(objectKey)
            .WithBucket(fromBucket);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: DeleteObject: " <<
                    err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
```

```
    else {
        std::cout << "Successfully deleted the object." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for C++ da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteObjects(const std::vector<Aws::String> &objectKeys,
                               const Aws::String &fromBucket,
                               const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectsRequest request;

    Aws::S3::Model::Delete deleteObject;
    for (const Aws::String& objectKey : objectKeys)
    {

 deleteObject.AddObjects(Aws::S3::Model::ObjectIdentifier().WithKey(objectKey));
    }

    request.SetDelete(deleteObject);
    request.SetBucket(fromBucket);

    Aws::S3::Model::DeleteObjectsOutcome outcome =
            client.DeleteObjects(request);
```

```
    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error deleting objects. " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted the objects.";
        for (size_t i = 0; i < objectKeys.size(); ++i)
        {
            std::cout << objectKeys[i];
            if (i < objectKeys.size() - 1)
            {
                std::cout << ", ";
            }
        }

        std::cout << " from bucket " << fromBucket << "." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for C++ da API.

Excluir a configuração de site de um bucket

Os exemplos de código a seguir mostram como excluir a configuração de site de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::DeleteBucketWebsite(const Aws::String &bucketName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteBucketWebsiteRequest request;
```

```
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketWebsiteOutcome outcome =
            client.DeleteBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: DeleteBucketWebsite: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Website configuration was removed." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for C++ da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetObject(const Aws::String &objectKey,
                           const Aws::String &fromBucket,
                           const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(fromBucket);
    request.SetKey(objectKey);
```

```
    Aws::S3::Model::GetObjectOutcome outcome =
            client.GetObject(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully retrieved '" << objectKey << "' from '"
                  << fromBucket << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for C++ da API.

Obter a ACL de um bucket

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetBucketAcl(const Aws::String &bucketName,
                              const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketAclRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketAclOutcome outcome =
            s3_client.GetBucketAcl(request);
```

```
    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetBucketAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
    }
    else {
        Aws::Vector<Aws::S3::Model::Grant> grants =
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            Aws::S3::Model::Grant grant = *it;
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            std::cout << "For bucket " << bucketName << ": "
                      << std::endl << std::endl;

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << GetGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
```

```
                        GetPermissionString(grant.GetPermission()) <<
                        std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \sa GetGranteeTypeString()
 \param type Type enumeration.
*/

Aws::String GetGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \sa GetPermissionString()
 \param permission Permission enumeration.
*/

Aws::String GetPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can list objects in this bucket, create/overwrite/delete "
                   "objects in this bucket, and read/write this "
                   "bucket's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
```

```
            return "Can list objects in this bucket";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this bucket's permissions";
        case Aws::S3::Model::Permission::WRITE:
            return "Can create, overwrite, and delete objects in this bucket";
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this bucket's permissions";
        default:
            return "Permission unknown";
    }

    return "Permission unknown";
}
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for C++ da API.

Obter a ACL de um objeto

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um objeto do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetObjectAclRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectAclOutcome outcome =
```

```
            s3_client.GetObjectAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetObjectAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
    }
    else {
        Aws::Vector<Aws::S3::Model::Grant> grants =
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            std::cout << "For object " << objectKey << ": "
                      << std::endl << std::endl;

            Aws::S3::Model::Grant grant = *it;
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << GetGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }
```

```
            std::cout << "Permission:    " <<
                      GetPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \fn GetGranteeTypeString()
 \param type Type enumeration.
*/

Aws::String GetGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \fn GetPermissionString()
 \param permission Permission enumeration.
*/

Aws::String GetPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can read this object's data and its metadata, "
                   "and read/write this object's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
```

```
            return "Can read this object's data and its metadata";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this object's permissions";
            // case Aws::S3::Model::Permission::WRITE // Not applicable.
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this object's permissions";
        default:
            return "Permission unknown";
    }
}
```

- Para obter detalhes da API, consulte GetObjectAcla Referência AWS SDK for C++ da API.

Obter a política de um bucket

Os exemplos de código a seguir mostram como obter a política para um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetBucketPolicy(const Aws::String &bucketName,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketPolicyOutcome outcome =
            s3_client.GetBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: GetBucketPolicy: "
```

```
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    }
    else {
        Aws::StringStream policy_stream;
        Aws::String line;

        outcome.GetResult().GetPolicy() >> line;
        policy_stream << line;

        std::cout << "Retrieve the policy for bucket '" << bucketName << "':\n\n" <<
                  policy_stream.str() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for C++ da API.

Obter a configuração do site de um bucket

O exemplo de código a seguir mostra como obter a configuração de site de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::GetWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::GetBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketWebsiteOutcome outcome =
            s3_client.GetBucketWebsite(request);
```

```
    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();

        std::cerr << "Error: GetBucketWebsite: "
                  << err.GetMessage() << std::endl;
    }
    else {
        Aws::S3::Model::GetBucketWebsiteResult websiteResult = outcome.GetResult();

        std::cout << "Success: GetBucketWebsite: "
                  << std::endl << std::endl
                  << "For bucket '" << bucketName << "':"
                  << std::endl
                  << "Index page : "
                  << websiteResult.GetIndexDocument().GetSuffix()
                  << std::endl
                  << "Error page: "
                  << websiteResult.GetErrorDocument().GetKey()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for C++ da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::ListBuckets(const Aws::Client::ClientConfiguration &clientConfig) {
```

```
    Aws::S3::S3Client client(clientConfig);

    auto outcome = client.ListBuckets();

    bool result = true;
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
        result = false;
    }
    else {
        std::cout << "Found " << outcome.GetResult().GetBuckets().size() << "
 buckets\n";
        for (auto &&b: outcome.GetResult().GetBuckets()) {
            std::cout << b.GetName() << std::endl;
        }
    }

    return result;
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for C++ da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::ListObjects(const Aws::String &bucketName,
                             const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::ListObjectsRequest request;
    request.WithBucket(bucketName);
```

```
    auto outcome = s3_client.ListObjects(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: ListObjects: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        Aws::Vector<Aws::S3::Model::Object> objects =
                outcome.GetResult().GetContents();

        for (Aws::S3::Model::Object &object: objects) {
            std::cout << object.GetKey() << std::endl;
        }
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for C++ da API.

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutBucketAcl(const Aws::String &bucketName,
                              const Aws::String &ownerID,
                              const Aws::String &granteePermission,
                              const Aws::String &granteeType,
                              const Aws::String &granteeID,
                              const Aws::Client::ClientConfiguration &clientConfig,
                              const Aws::String &granteeDisplayName,
                              const Aws::String &granteeEmailAddress,
```

```
                                const Aws::String &granteeURI) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(SetGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeDisplayName.empty()) {
        grantee.SetDisplayName(granteeDisplayName);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(SetGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutBucketAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);

    Aws::S3::Model::PutBucketAclOutcome outcome =
            s3_client.PutBucketAcl(request);

    if (!outcome.IsSuccess()) {
```

```
        const Aws::S3::S3Error &error = outcome.GetError();

        std::cerr << "Error: PutBucketAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully added an ACL to the bucket '" << bucketName
                  << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \sa SetGranteePermission()
 \param access Human readable string.
*/

Aws::S3::Model::Permission SetGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \sa SetGranteeType()
 \param type Human readable string.
*/

Aws::S3::Model::Type SetGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
```

```
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for C++ da API.

Definir a ACL de um objeto

O exemplo de código a seguir mostra como definir a lista de controle de acesso (ACL) de um objeto do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::String &ownerID,
                              const Aws::String &granteePermission,
                              const Aws::String &granteeType,
                              const Aws::String &granteeID,
                              const Aws::Client::ClientConfiguration &clientConfig,
                              const Aws::String &granteeDisplayName,
                              const Aws::String &granteeEmailAddress,
                              const Aws::String &granteeURI) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(SetGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }
```

```
    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeDisplayName.empty()) {
        grantee.SetDisplayName(granteeDisplayName);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(SetGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutObjectAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::PutObjectAclOutcome outcome =
            s3_client.PutObjectAcl(request);

    if (!outcome.IsSuccess()) {
        auto error = outcome.GetError();
        std::cerr << "Error: PutObjectAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully added an ACL to the object '" << objectKey
                  << "' in the bucket '" << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \sa SetGranteePermission()
 \param access Human readable string.
*/

Aws::S3::Model::Permission SetGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \sa SetGranteeType()
 \param type Human readable string.
*/

Aws::S3::Model::Type SetGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- Para obter detalhes da API, consulte PutObjectAcla Referência AWS SDK for C++ da API.

Definir a configuração de site de um bucket

O exemplo de código a seguir mostra como definir a configuração de site de um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::String &indexPage, const Aws::String
 &errorPage,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::IndexDocument indexDocument;
    indexDocument.SetSuffix(indexPage);

    Aws::S3::Model::ErrorDocument errorDocument;
    errorDocument.SetKey(errorPage);

    Aws::S3::Model::WebsiteConfiguration websiteConfiguration;
    websiteConfiguration.SetIndexDocument(indexDocument);
    websiteConfiguration.SetErrorDocument(errorDocument);

    Aws::S3::Model::PutBucketWebsiteRequest request;
    request.SetBucket(bucketName);
    request.SetWebsiteConfiguration(websiteConfiguration);

    Aws::S3::Model::PutBucketWebsiteOutcome outcome =
            client.PutBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketWebsite: "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Success: Set website configuration for bucket '"
                  << bucketName << "'." << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for C++ da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::S3::PutObject(const Aws::String &bucketName,
                           const Aws::String &fileName,
                           const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    //We are using the name of the file as the key for the object in the bucket.
    //However, this is just a string and can be set according to your retrieval
 needs.
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          fileName.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);

    if (!*inputData) {
        std::cerr << "Error unable to read file " << fileName << std::endl;
        return false;
    }
```

```
    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3_client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Added object '" << fileName << "' to bucket '"
                  << bucketName << "'.";
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for C++ da API.

Cenários

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
#include <iostream>
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <aws/s3/model/CopyObjectRequest.h>
#include <aws/s3/model/CreateBucketRequest.h>
#include <aws/s3/model/DeleteBucketRequest.h>
#include <aws/s3/model/DeleteObjectRequest.h>
#include <aws/s3/model/GetObjectRequest.h>
#include <aws/s3/model/ListObjectsRequest.h>
#include <aws/s3/model/PutObjectRequest.h>
#include <aws/s3/model/BucketLocationConstraint.h>
#include <aws/s3/model/CreateBucketConfiguration.h>
#include <aws/core/utils/UUID.h>
#include <aws/core/utils/StringUtils.h>
#include <aws/core/utils/memory/stl/AWSAllocator.h>
#include <aws/core/utils/memory/stl/AWSStreamFwd.h>
#include <fstream>
#include "awsdoc/s3/s3_examples.h"

namespace AwsDoc {
    namespace S3 {

        //! Delete an S3 bucket.
        /*!
          \sa DeleteBucket()
          \param bucketName The S3 bucket's name.
          \param client An S3 client.
        */
        static bool DeleteBucket(const Aws::String &bucketName, Aws::S3::S3Client
 &client);

        //! Delete an object in an S3 bucket.
        /*!          \sa DeleteObjectFromBucket()
          \param bucketName The S3 bucket's name.
          \param key The key for the object in the S3 bucket.
          \param client An S3 client.
         */
        static bool
        DeleteObjectFromBucket(const Aws::String &bucketName, const Aws::String
 &key, Aws::S3::S3Client &client);
    }
}
```

```
//! Scenario to create, copy, and delete S3 buckets and objects.
/*!
  \sa S3_GettingStartedScenario()
  \param uploadFilePath Path to file to upload to an Amazon S3 bucket.
  \param saveFilePath Path for saving a downloaded S3 object.
  \param clientConfig Aws client configuration.
 */
bool AwsDoc::S3::S3_GettingStartedScenario(const Aws::String &uploadFilePath, const
 Aws::String &saveFilePath,
                                            const Aws::Client::ClientConfiguration
 &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    // Create a unique bucket name which is only temporary and will be deleted.
    // Format: "doc-example-bucket-" + lowercase UUID.
    Aws::String uuid = Aws::Utils::UUID::RandomUUID();
    Aws::String bucketName = "doc-example-bucket-" +
                             Aws::Utils::StringUtils::ToLower(uuid.c_str());

    // 1. Create a bucket.
    {
        Aws::S3::Model::CreateBucketRequest request;
        request.SetBucket(bucketName);

        if (clientConfig.region != Aws::Region::US_EAST_1) {
            Aws::S3::Model::CreateBucketConfiguration createBucketConfiguration;
            createBucketConfiguration.WithLocationConstraint(

 Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                             clientConfig.region));
            request.WithCreateBucketConfiguration(createBucketConfiguration);
        }

        Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: CreateBucket: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
            return false;
        }
```

```
        else {
            std::cout << "Created the bucket, '" << bucketName <<
                      "', in the region, '" << clientConfig.region << "'." <<
std::endl;
        }
    }

    // 2. Upload a local file to the bucket.
    Aws::String key = "key-for-test";
    {
        Aws::S3::Model::PutObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        std::shared_ptr<Aws::FStream> input_data =
                Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                              uploadFilePath,
                                              std::ios_base::in |
std::ios_base::binary);

        if (!input_data->is_open()) {
            std::cerr << "Error: unable to open file, '" << uploadFilePath << "'."
<< std::endl;
            AwsDoc::S3::DeleteBucket(bucketName, client);
            return false;
        }

        request.SetBody(input_data);

        Aws::S3::Model::PutObjectOutcome outcome =
                client.PutObject(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: PutObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
            AwsDoc::S3::DeleteObjectFromBucket(bucketName, key, client);
            AwsDoc::S3::DeleteBucket(bucketName, client);
            return false;
        }
        else {
            std::cout << "Added the object with the key, '" << key << "', to the
bucket, '"
                      << bucketName << "'." << std::endl;
        }
```

```
    }

    // 3. Download the object to a local file.
    {
        Aws::S3::Model::GetObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        Aws::S3::Model::GetObjectOutcome outcome =
                client.GetObject(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: GetObject: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
        }
        else {
            std::cout << "Downloaded the object with the key, '" << key << "', in
the bucket, '"
                      << bucketName << "'." << std::endl;

            Aws::IOStream &ioStream = outcome.GetResultWithOwnership().
                    GetBody();
            Aws::OFStream outStream(saveFilePath, std::ios_base::out |
std::ios_base::binary);
            if (!outStream.is_open()) {
                std::cout << "Error: unable to open file, '" << saveFilePath << "'."
<< std::endl;
            }
            else {
                outStream << ioStream.rdbuf();
                std::cout << "Wrote the downloaded object to the file '"
                          << saveFilePath << "'." << std::endl;
            }
        }
    }

    // 4. Copy the object to a different "folder" in the bucket.
    Aws::String copiedToKey = "test-folder/" + key;
    {
        Aws::S3::Model::CopyObjectRequest request;
        request.WithBucket(bucketName)
                .WithKey(copiedToKey)
```

```
                .WithCopySource(bucketName + "/" + key);

        Aws::S3::Model::CopyObjectOutcome outcome =
                client.CopyObject(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error: CopyObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
        }
        else {
            std::cout << "Copied the object with the key, '" << key << "', to the
key, '" << copiedToKey
                      << ", in the bucket, '" << bucketName << "'." << std::endl;
        }
    }

    // 5. List objects in the bucket.
    {
        Aws::S3::Model::ListObjectsRequest request;
        request.WithBucket(bucketName);

        Aws::S3::Model::ListObjectsOutcome outcome = client.ListObjects(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: ListObjects: " <<
                      outcome.GetError().GetMessage() << std::endl;
        }
        else {
            Aws::Vector<Aws::S3::Model::Object> objects =
                    outcome.GetResult().GetContents();

            std::cout << objects.size() << " objects in the bucket, '" << bucketName
<< "':" << std::endl;

            for (Aws::S3::Model::Object &object: objects) {
                std::cout << "     '" << object.GetKey() << "'" << std::endl;
            }
        }
    }

    // 6. Delete all objects in the bucket.
    // All objects in the bucket must be deleted before deleting the bucket.
    AwsDoc::S3::DeleteObjectFromBucket(bucketName, copiedToKey, client);
    AwsDoc::S3::DeleteObjectFromBucket(bucketName, key, client);
```

```
    // 7. Delete the bucket.
    return AwsDoc::S3::DeleteBucket(bucketName, client);
}

bool AwsDoc::S3::DeleteObjectFromBucket(const Aws::String &bucketName, const
 Aws::String &key,
                                        Aws::S3::S3Client &client) {
    Aws::S3::Model::DeleteObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(key);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: DeleteObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Deleted the object with the key, '" << key << "', from the
 bucket, '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

bool AwsDoc::S3::DeleteBucket(const Aws::String &bucketName, Aws::S3::S3Client
 &client) {
    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: DeleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    }
    else {
        std::cout << "Deleted the bucket, '" << bucketName << "'." << std::endl;
    }
    return outcome.IsSuccess();
```

```
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Exemplos do Secrets Manager usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um segredo

O exemplo de código a seguir mostra como criar um segredo do Secrets Manager.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main(int argc, const char *argv[])
{
    if (argc != 3) {
        std::cout << "Usage:\n" <<
        "    <secretName> <secretValue> \n\n" <<
        "Where:\n" <<
        "    secretName - The name of the secret (for example, tutorials/
MyFirstSecret). \n" <<
        "    secretValue - The secret value. " << std::endl;
        return 0;
    }

    SDKOptions options;
    options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;

    InitAPI(options);
    {
        Aws::Client::ClientConfiguration config;

        //TODO(user): Enter the Region where you want to create the secret.
        String region = "us-east-1";
        if (!region.empty())
        {
                config.region = region;
        }
        SecretsManager::SecretsManagerClient sm_client(config);

        String secretName = argv[1];
        String secretString = argv[2];
        SecretsManager::Model::CreateSecretRequest request;
        request.SetName(secretName);
        request.SetSecretString(secretString);

        auto createSecretOutcome = sm_client.CreateSecret(request);
```

```
        if(createSecretOutcome.IsSuccess()){
                std::cout << "Create secret with name: " <<
 createSecretOutcome.GetResult().GetName() << std::endl;
        }else{
                std::cout << "Failed with Error: " << createSecretOutcome.GetError()
 << std::endl;
        }
    }

    ShutdownAPI(options);
    return 0;
}
```

- Para obter detalhes da API, consulte CreateSecreta Referência AWS SDK for C++ da API.

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main(int argc, const char *argv[])
{
    if (argc != 2) {
        std::cout << "Usage:\n" <<
                  "    <secretName> \n\n" <<
                  "Where:\n" <<
                  "    secretName - The name of the secret (for example, tutorials/
MyFirstSecret). \n"
                  << std::endl;
        return 0;
    }

    SDKOptions options;
    options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
```

```
    InitAPI(options);
    {
        Aws::Client::ClientConfiguration config;

        //TODO(user): Enter the Region where you want to create the secret.
        String region = "us-east-1";
        if (!region.empty())
        {
                config.region = region;
        }
        SecretsManager::SecretsManagerClient sm_client(config);

        String secretId = argv[1];
        SecretsManager::Model::GetSecretValueRequest request;
        request.SetSecretId(secretId);

        auto getSecretValueOutcome = sm_client.GetSecretValue(request);
        if(getSecretValueOutcome.IsSuccess()){
                std::cout << "Secret is: " <<
 getSecretValueOutcome.GetResult().GetSecretString() << std::endl;
        }else{
                std::cout << "Failed with Error: " <<
 getSecretValueOutcome.GetError() << std::endl;
        }
    }

    ShutdownAPI(options);
    return 0;
}
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for C++ da API.

Exemplos Amazon SES usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um filtro de recebimento

O exemplo de código a seguir mostra como criar um filtro de recebimento do Amazon SES que bloqueia e-mails recebidos de um endereço IP ou de um intervalo de endereços IP.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt filter..
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param cidr: IP address or IP address range in Classless Inter-Domain Routing
 (CIDR) notation.
  \param policy: Block or allow enum of type ReceiptFilterPolicy.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::String &cidr,
                                      Aws::SES::Model::ReceiptFilterPolicy policy,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::CreateReceiptFilterRequest createReceiptFilterRequest;
    Aws::SES::Model::ReceiptFilter receiptFilter;
```

```
    Aws::SES::Model::ReceiptIpFilter receiptIpFilter;
    receiptIpFilter.SetCidr(cidr);
    receiptIpFilter.SetPolicy(policy);
    receiptFilter.SetName(receiptFilterName);
    receiptFilter.SetIpFilter(receiptIpFilter);
    createReceiptFilterRequest.SetFilter(receiptFilter);
    Aws::SES::Model::CreateReceiptFilterOutcome createReceiptFilterOutcome =
 sesClient.CreateReceiptFilter(
            createReceiptFilterRequest);
    if (createReceiptFilterOutcome.IsSuccess()) {
        std::cout << "Successfully created receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt filter: " <<
                  createReceiptFilterOutcome.GetError().GetMessage() << std::endl;
    }

    return createReceiptFilterOutcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptFiltera Referência AWS SDK for C++ da API.

Criar uma regra de recebimento

O exemplo de código a seguir mostra como criar uma regra de recebimento do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param s3BucketName: The name of the S3 bucket for incoming mail.
  \param s3ObjectKeyPrefix: The prefix for the objects in the S3 bucket.
  \param ruleSetName: The name of the rule set where the receipt rule is added.
```

```
  \param recipients: Aws::Vector of recipients.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &s3BucketName,
                                    const Aws::String &s3ObjectKeyPrefix,
                                    const Aws::String &ruleSetName,
                                    const Aws::Vector<Aws::String> &recipients,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleRequest createReceiptRuleRequest;

    Aws::SES::Model::S3Action s3Action;
    s3Action.SetBucketName(s3BucketName);
    s3Action.SetObjectKeyPrefix(s3ObjectKeyPrefix);

    Aws::SES::Model::ReceiptAction receiptAction;
    receiptAction.SetS3Action(s3Action);

    Aws::SES::Model::ReceiptRule receiptRule;
    receiptRule.SetName(receiptRuleName);
    receiptRule.WithRecipients(recipients);

    Aws::Vector<Aws::SES::Model::ReceiptAction> receiptActionList;
    receiptActionList.emplace_back(receiptAction);
    receiptRule.SetActions(receiptActionList);

    createReceiptRuleRequest.SetRuleSetName(ruleSetName);
    createReceiptRuleRequest.SetRule(receiptRule);

    auto outcome = sesClient.CreateReceiptRule(createReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created receipt rule." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptRulea Referência AWS SDK for C++ da API.

Criar um conjunto de regras de recebimento

O exemplo de código a seguir mostra como criar um conjunto de regras de recebimento do Amazon SES para organizar as regras aplicadas aos e-mails recebidos.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param ruleSetName: The name of the rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptRuleSet(const Aws::String &ruleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleSetRequest createReceiptRuleSetRequest;

    createReceiptRuleSetRequest.SetRuleSetName(ruleSetName);

    Aws::SES::Model::CreateReceiptRuleSetOutcome outcome =
 sesClient.CreateReceiptRuleSet(
            createReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully created receipt rule set." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule set. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateReceiptRuleSeta Referência AWS SDK for C++ da API.

Criar um modelo de e-mail

O exemplo de código a seguir mostra como criar um modelo de e-mail do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateTemplateRequest createTemplateRequest;
    Aws::SES::Model::Template aTemplate;

    aTemplate.SetTemplateName(templateName);
    aTemplate.SetHtmlPart(htmlPart);
    aTemplate.SetSubjectPart(subjectPart);
    aTemplate.SetTextPart(textPart);

    createTemplateRequest.SetTemplate(aTemplate);

    Aws::SES::Model::CreateTemplateOutcome outcome = sesClient.CreateTemplate(
            createTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created template." << templateName << "."
                  << std::endl;
    }
    else {
        std::cerr << "Error creating template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for C++ da API.

Excluir um filtro de recebimento

O exemplo de código a seguir mostra como excluir um filtro de recebimento do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt filter.
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptFilterRequest deleteReceiptFilterRequest;

    deleteReceiptFilterRequest.SetFilterName(receiptFilterName);

    Aws::SES::Model::DeleteReceiptFilterOutcome outcome =
 sesClient.DeleteReceiptFilter(
            deleteReceiptFilterRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error deleting receipt filter. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptFiltera Referência AWS SDK for C++ da API.

Excluir uma regra de recebimento

O exemplo de código a seguir mostra como excluir uma regra de recebimento do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param receiptRuleSetName: The name for the receipt rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &receiptRuleSetName,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleRequest deleteReceiptRuleRequest;

    deleteReceiptRuleRequest.SetRuleName(receiptRuleName);
    deleteReceiptRuleRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleOutcome outcome = sesClient.DeleteReceiptRule(
            deleteReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule." << std::endl;
    }
    else {
        std::cout << "Error deleting receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptRulea Referência AWS SDK for C++ da API.

Excluir um conjunto de regras

O exemplo de código a seguir mostra como excluir um conjunto de regras do Amazon SES e todas as regras contidas nesse conjunto.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param receiptRuleSetName: The name for the receipt rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRuleSet(const Aws::String &receiptRuleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleSetRequest deleteReceiptRuleSetRequest;

    deleteReceiptRuleSetRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleSetOutcome outcome =
 sesClient.DeleteReceiptRuleSet(
            deleteReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule set." << std::endl;
    }

    else {
        std::cerr << "Error deleting receipt rule set. "
```

```
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteReceiptRuleSeta Referência AWS SDK for C++ da API.

Excluir um modelo de e-mail

O exemplo de código a seguir mostra como excluir um modelo de e-mail do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteTemplate(const Aws::String &templateName,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteTemplateRequest deleteTemplateRequest;

    deleteTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::DeleteTemplateOutcome outcome = sesClient.DeleteTemplate(
            deleteTemplateRequest);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted template." << std::endl;
    }
    else {
        std::cerr << "Error deleting template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for C++ da API.

Excluir uma identidade

O exemplo de código a seguir mostra como excluir uma identidade do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete the specified identity (an email address or a domain).
/*!
  \param identity: The identity to delete.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteIdentity(const Aws::String &identity,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteIdentityRequest deleteIdentityRequest;

    deleteIdentityRequest.SetIdentity(identity);
```

```
    Aws::SES::Model::DeleteIdentityOutcome outcome = sesClient.DeleteIdentity(
            deleteIdentityRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted identity." << std::endl;
    }
    else {
        std::cerr << "Error deleting identity. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for C++ da API.

Obter um modelo existente de e-mail

O exemplo de código a seguir mostra como obter um modelo existente de e-mail do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Get a template's attributes.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::getTemplate(const Aws::String &templateName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
```

```
    Aws::SES::Model::GetTemplateRequest getTemplateRequest;

    getTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::GetTemplateOutcome outcome = sesClient.GetTemplate(
            getTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully got template." << std::endl;
    }

    else {
        std::cerr << "Error getting template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetTemplatea Referência AWS SDK for C++ da API.

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the identities associated with this account.
/*!
  \param identityType: The identity type enum. "NOT_SET" is a valid option.
  \param identities; A vector to receive the retrieved identities.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::listIdentities(Aws::SES::Model::IdentityType identityType,
                                 Aws::Vector<Aws::String> &identities,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::ListIdentitiesRequest listIdentitiesRequest;

    if (identityType != Aws::SES::Model::IdentityType::NOT_SET) {
        listIdentitiesRequest.SetIdentityType(identityType);
    }

    Aws::String nextToken; // Used for paginated results.
    do {
        if (!nextToken.empty()) {
            listIdentitiesRequest.SetNextToken(nextToken);
        }
        Aws::SES::Model::ListIdentitiesOutcome outcome = sesClient.ListIdentities(
                listIdentitiesRequest);

        if (outcome.IsSuccess()) {
            const auto &retrievedIdentities = outcome.GetResult().GetIdentities();
            if (!retrievedIdentities.empty()) {
                identities.insert(identities.cend(), retrievedIdentities.cbegin(),
                                  retrievedIdentities.cend());
            }
            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error listing identities. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!nextToken.empty());

    return true;
}
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for C++ da API.

Listar filtros de recebimento

O exemplo de código a seguir mostra como listar filtros de recebimento do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! List the receipt filters associated with this account.
/*!
  \param filters; A vector of "ReceiptFilter" to receive the retrieved filters.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SES::listReceiptFilters(Aws::Vector<Aws::SES::Model::ReceiptFilter>
 &filters,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::ListReceiptFiltersRequest listReceiptFiltersRequest;

    Aws::SES::Model::ListReceiptFiltersOutcome outcome =
 sesClient.ListReceiptFilters(
            listReceiptFiltersRequest);
    if (outcome.IsSuccess()) {
        auto &retrievedFilters = outcome.GetResult().GetFilters();
        if (!retrievedFilters.empty()) {
            filters.insert(filters.cend(), retrievedFilters.cbegin(),
                           retrievedFilters.cend());
        }
    }
    else {
        std::cerr << "Error retrieving IP address filters: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListReceiptFiltersa Referência AWS SDK for C++ da API.

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send an email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param subject: Email subject.
  \param htmlBody: Email body as HTML. At least one body data is required.
  \param textBody: Email body as plain text. At least one body data is required.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendEmail(const Aws::Vector<Aws::String> &recipients,
                            const Aws::String &subject,
                            const Aws::String &htmlBody,
                            const Aws::String &textBody,
                            const Aws::String &senderEmailAddress,
                            const Aws::Vector<Aws::String> &ccAddresses,
                            const Aws::String &replyToAddress,
                            const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Destination destination;
    if (!ccAddresses.empty()) {
        destination.WithCcAddresses(ccAddresses);
```

```
    }
    if (!recipients.empty()) {
        destination.WithToAddresses(recipients);
    }

    Aws::SES::Model::Body message_body;
    if (!htmlBody.empty()) {
        message_body.SetHtml(
                Aws::SES::Model::Content().WithCharset("UTF-8").WithData(htmlBody));
    }

    if (!textBody.empty()) {
        message_body.SetText(
                Aws::SES::Model::Content().WithCharset("UTF-8").WithData(textBody));
    }

    Aws::SES::Model::Message message;
    message.SetBody(message_body);
    message.SetSubject(
            Aws::SES::Model::Content().WithCharset("UTF-8").WithData(subject));

    Aws::SES::Model::SendEmailRequest sendEmailRequest;
    sendEmailRequest.SetDestination(destination);
    sendEmailRequest.SetMessage(message);
    if (!senderEmailAddress.empty()) {
        sendEmailRequest.SetSource(senderEmailAddress);
    }
    if (!replyToAddress.empty()) {
        sendEmailRequest.AddReplyToAddresses(replyToAddress);
    }

    auto outcome = sesClient.SendEmail(sendEmailRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending message. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
```

```
}
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for C++ da API.

Enviar e-mails com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo com o Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send a templated email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param templateName: The name of the template to use.
  \param templateData: Map of key-value pairs for replacing text in template.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendTemplatedEmail(const Aws::Vector<Aws::String> &recipients,
                                     const Aws::String &templateName,
                                     const Aws::Map<Aws::String, Aws::String>
 &templateData,
                                     const Aws::String &senderEmailAddress,
                                     const Aws::Vector<Aws::String> &ccAddresses,
                                     const Aws::String &replyToAddress,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Destination destination;
    if (!ccAddresses.empty()) {
```

```
        destination.WithCcAddresses(ccAddresses);
    }
    if (!recipients.empty()) {
        destination.WithToAddresses(recipients);
    }

    Aws::SES::Model::SendTemplatedEmailRequest sendTemplatedEmailRequest;
    sendTemplatedEmailRequest.SetDestination(destination);
    sendTemplatedEmailRequest.SetTemplate(templateName);

    std::ostringstream templateDataStream;
    templateDataStream << "{";
    size_t dataCount = 0;
    for (auto &pair: templateData) {
        templateDataStream << "\"" << pair.first << "\":\"" << pair.second << "\"";
        dataCount++;
        if (dataCount < templateData.size()) {
            templateDataStream << ",";
        }
    }
    templateDataStream << "}";

    sendTemplatedEmailRequest.SetTemplateData(templateDataStream.str());

    if (!senderEmailAddress.empty()) {
        sendTemplatedEmailRequest.SetSource(senderEmailAddress);
    }
    if (!replyToAddress.empty()) {
        sendTemplatedEmailRequest.AddReplyToAddresses(replyToAddress);
    }

    auto outcome = sesClient.SendTemplatedEmail(sendTemplatedEmailRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent templated message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending templated message. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SendTemplatedEmaila Referência AWS SDK for C++ da API.

Atualizar um modelo de e-mail

O exemplo de código a seguir mostra como atualizar um modelo de e-mail do Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Update an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::updateTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Template templateValues;

    templateValues.SetTemplateName(templateName);
    templateValues.SetSubjectPart(subjectPart);
    templateValues.SetHtmlPart(htmlPart);
```

```
    templateValues.SetTextPart(textPart);

    Aws::SES::Model::UpdateTemplateRequest updateTemplateRequest;
    updateTemplateRequest.SetTemplate(templateValues);

    Aws::SES::Model::UpdateTemplateOutcome outcome =
 sesClient.UpdateTemplate(updateTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated template." << std::endl;
    } else {
        std::cerr << "Error updating template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte UpdateTemplatea Referência AWS SDK for C++ da API.

Verificar uma identidade de e-mail

O exemplo de código a seguir mostra como verificar uma identidade de e-mail com o Amazon SES.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Add an email address to the list of identities associated with this account and
//! initiate verification.
/*!
  \param emailAddress; The email address to add.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::verifyEmailIdentity(const Aws::String &emailAddress,
```

```
                        const Aws::Client::ClientConfiguration
 &clientConfiguration)
{
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::VerifyEmailIdentityRequest verifyEmailIdentityRequest;

    verifyEmailIdentityRequest.SetEmailAddress(emailAddress);

    Aws::SES::Model::VerifyEmailIdentityOutcome outcome =
 sesClient.VerifyEmailIdentity(verifyEmailIdentityRequest);

    if (outcome.IsSuccess())
    {
        std::cout << "Email verification initiated." << std::endl;
    }

    else
    {
        std::cerr << "Error initiating email verification. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for C++ da API.

Exemplos Amazon SNS usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sns)

# Set this project's name.
project("hello_sns")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
```

```
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_sns.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_sns.cpp.

```
#include <aws/core/Aws.h>
#include <aws/sns/SNSClient.h>
#include <aws/sns/model/ListTopicsRequest.h>
#include <iostream>

/*
 *  A "Hello SNS" starter application which initializes an Amazon Simple
 Notification
 *  Service (Amazon SNS) client and lists the SNS topics in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sns'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
```

```
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SNS::SNSClient snsClient(clientConfig);

        Aws::Vector<Aws::SNS::Model::Topic> allTopics;
        Aws::String nextToken; // Next token is used to handle a paginated response.
        do {
            Aws::SNS::Model::ListTopicsRequest request;

            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            const Aws::SNS::Model::ListTopicsOutcome outcome = snsClient.ListTopics(
                    request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SNS::Model::Topic> &paginatedTopics =
                        outcome.GetResult().GetTopics();
                if (!paginatedTopics.empty()) {
                    allTopics.insert(allTopics.cend(), paginatedTopics.cbegin(),
                                     paginatedTopics.cend());
                }
            }
            else {
                std::cerr << "Error listing topics " <<
outcome.GetError().GetMessage()
                          << std::endl;
                return 1;
            }

            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());

        std::cout << "Hello Amazon SNS! You have " << allTopics.size() << " topic"
                  << (allTopics.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allTopics.empty()) {
            std::cout << "Here are your topic ARNs." << std::endl;
```

```
            for (const Aws::SNS::Model::Topic &topic: allTopics) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Criar um tópico

Os exemplos de código a seguir mostram como criar um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Create an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicName: An Amazon SNS topic name.
  \param topicARNResult: String to return the Amazon Resource Name (ARN) for the
 topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::SNS::createTopic(const Aws::String &topicName,
                              Aws::String &topicARNResult,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::CreateTopicRequest request;
    request.SetName(topicName);

    const Aws::SNS::Model::CreateTopicOutcome outcome =
 snsClient.CreateTopic(request);

    if (outcome.IsSuccess()) {
        topicARNResult = outcome.GetResult().GetTopicArn();
        std::cout << "Successfully created an Amazon SNS topic " << topicName
                  << " with topic ARN '" << topicARNResult
                  << "'." << std::endl;

    }
    else {
        std::cerr << "Error creating topic " << topicName << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
        topicARNResult.clear();
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for C++ da API.

Excluir uma assinatura

O exemplo de código a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete a subscription to an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param subscriptionARN: The Amazon Resource Name (ARN) for an Amazon SNS topic
 subscription.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::unsubscribe(const Aws::String &subscriptionARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::UnsubscribeRequest request;
    request.SetSubscriptionArn(subscriptionARN);

    const Aws::SNS::Model::UnsubscribeOutcome outcome =
 snsClient.Unsubscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Unsubscribed successfully " << std::endl;
    }
    else {
        std::cerr << "Error while unsubscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for C++.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Delete an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::deleteTopic(const Aws::String &topicARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::DeleteTopicRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted the Amazon SNS topic " << topicARN <<
 std::endl;
    }
    else {
        std::cerr << "Error deleting topic " << topicARN << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for C++ da API.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the properties of an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::getTopicAttributes(const Aws::String &topicARN,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);
    Aws::SNS::Model::GetTopicAttributesRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::GetTopicAttributesOutcome outcome =
 snsClient.GetTopicAttributes(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Topic Attributes:" << std::endl;
        for (auto const &attribute: outcome.GetResult().GetAttributes()) {
            std::cout << "  * " << attribute.first << " : " << attribute.second
                      << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting Topic attributes "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for C++ da API.

Obter as configurações para enviar mensagens SMS

Os exemplos de código a seguir mostram como obter as configurações para enviar mensagens SMS do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve the default settings for sending SMS messages from your AWS account by
 using
//! Amazon Simple Notification Service (Amazon SNS).
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::getSMSType(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::GetSMSAttributesRequest request;
    //Set the request to only retrieve the DefaultSMSType setting.
    //Without the following line, GetSMSAttributes would retrieve all settings.
    request.AddAttributes("DefaultSMSType");

    const Aws::SNS::Model::GetSMSAttributesOutcome outcome =
 snsClient.GetSMSAttributes(
            request);
```

```
    if (outcome.IsSuccess()) {
        const Aws::Map<Aws::String, Aws::String> attributes =
                outcome.GetResult().GetAttributes();
        if (!attributes.empty()) {
            for (auto const &att: attributes) {
                std::cout << att.first << ":  " << att.second << std::endl;
            }
        }
        else {
            std::cout
                    << "AwsDoc::SNS::getSMSType - an empty map of attributes was
 retrieved."
                    << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for C++.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS)
 subscriptions.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::listSubscriptions(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
    Aws::Vector<Aws::SNS::Model::Subscription> subscriptions;
    do {
        Aws::SNS::Model::ListSubscriptionsRequest request;

        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListSubscriptionsOutcome outcome =
 snsClient.ListSubscriptions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::SNS::Model::Subscription> &newSubscriptions =
                    outcome.GetResult().GetSubscriptions();
            subscriptions.insert(subscriptions.cend(), newSubscriptions.begin(),
                                 newSubscriptions.end());
        }
        else {
            std::cerr << "Error listing subscriptions "
                      << outcome.GetError().GetMessage()
                      <<
                      std::endl;
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    if (result) {
```

```
        if (subscriptions.empty()) {
            std::cout << "No subscriptions found" << std::endl;
        }
        else {
            std::cout << "Subscriptions list:" << std::endl;
            for (auto const &subscription: subscriptions) {
                std::cout << "  * " << subscription.GetSubscriptionArn() <<
 std::endl;
            }
        }
    }
    return result;
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for C++ da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS) topics.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::listTopics(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
```

```
    do {
        Aws::SNS::Model::ListTopicsRequest request;

        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListTopicsOutcome outcome = snsClient.ListTopics(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Topics list:" << std::endl;
            for (auto const &topic: outcome.GetResult().GetTopics()) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
        else {
            std::cerr << "Error listing topics " << outcome.GetError().GetMessage()
 <<
                      std::endl;
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    return result;
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for C++ da API.

Publicar uma mensagem com um atributo

O exemplo de código a seguir mostra como publicar uma mensagem com um atributo usando o Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        static const Aws::String TONE_ATTRIBUTE("tone");
        static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
"serious",
                                                       "sincere"};

        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
```

```
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

Publicar uma mensagem de texto SMS

Os exemplos de código a seguir mostram como publicar mensagens SMS usando o Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Publish SMS: use Amazon Simple Notification Service (Amazon SNS) to send an SMS
 text message to a phone number.
 * Note: This requires additional AWS configuration prior to running example.
 *
 *  NOTE: When you start using Amazon SNS to send SMS messages, your AWS account is
 in the SMS sandbox and you can only
 *  use verified destination phone numbers. See https://docs.aws.amazon.com/sns/
latest/dg/sns-sms-sandbox.html.
 *  NOTE: If destination is in the US, you also have an additional restriction that
 you have use a dedicated
```

```
 *  origination ID (phone number). You can request an origination number using
 Amazon Pinpoint for a fee.
 *  See https://aws.amazon.com/blogs/compute/provisioning-and-using-10dlc-
origination-numbers-with-amazon-sns/
 *  for more information.
 *
 *  <phone_number_value> input parameter uses E.164 format.
 *  For example, in United States, this input value should be of the form:
 +12223334444
 */

//! Send an SMS text message to a phone number.
/*!
  \param message: The message to publish.
  \param phoneNumber: The phone number of the recipient in E.164 format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishSms(const Aws::String &message,
                             const Aws::String &phoneNumber,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
    request.SetMessage(message);
    request.SetPhoneNumber(phoneNumber);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with message id, '"
                  << outcome.GetResult().GetMessageId() << "'."
                  << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Send a message to an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param message: The message to publish.
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishToTopic(const Aws::String &message,
                                 const Aws::String &topicARN,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
    request.SetMessage(message);
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with id '"
                  << outcome.GetResult().GetMessageId() << "'." << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
```

```
                    << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for C++.

Definir as configurações padrão para enviar mensagens SMS

Os exemplos de código a seguir mostram como definir as configurações padrão para enviar mensagens SMS usando o Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Como usar o Amazon SNS para definir o atributo defaultSMstype.

```
//! Set the default settings for sending SMS messages.
/*!
  \param smsType: The type of SMS message that you will send by default.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::setSMSType(const Aws::String &smsType,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SetSMSAttributesRequest request;
    request.AddAttributes("DefaultSMSType", smsType);

    const Aws::SNS::Model::SetSMSAttributesOutcome outcome =
 snsClient.SetSMSAttributes(
            request);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "SMS Type set successfully " << std::endl;
    }
    else {
        std::cerr << "Error while setting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for C++.

Inscrever uma função do Lambda em um tópico

Os exemplos de código a seguir mostram como inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an AWS Lambda function.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param lambdaFunctionARN: The ARN for an AWS Lambda function.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeLambda(const Aws::String &topicARN,
                                  const Aws::String &lambdaFunctionARN,
```

```
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("lambda");
    request.SetEndpoint(lambdaFunctionARN);

    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Inscrever uma aplicação móvel em um tópico

Os exemplos de código a seguir mostram como inscrever um endpoint de aplicação móvel para receber notificações de um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to a mobile app.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param endpointARN: The ARN for a mobile app or device endpoint.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::subscribeApp(const Aws::String &topicARN,
                          const Aws::String &endpointARN,
                          const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("application");
    request.SetEndpoint(endpointARN);

    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Assinar uma fila do SQS em um tópico

O exemplo de código a seguir mostra como inscrever uma fila do Amazon SQS para receber notificações de um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);

            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
```

```
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Inscrever um endereço de e-mail em um tópico

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an email address.
/*!
  \param topicARN: An SNS topic Amazon Resource Name (ARN).
  \param emailAddress: An email address.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeEmail(const Aws::String &topicARN,
                                 const Aws::String &emailAddress,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("email");
    request.SetEndpoint(emailAddress);
```

```
    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Assinar com um filtro em um tópico

O exemplo de código a seguir mostra como assinar com um filtro um tópico do Amazon SNS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        static const Aws::String TONE_ATTRIBUTE("tone");
        static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
 "serious",
                                                       "sincere"};

        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);
```

```
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then only
 the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
```

```
                                << "will be added to this subscription." <<
 std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
 outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }

//! Routine that lets the user select attributes for a subscription filter policy.
/*!
 \sa getFilterPolicyFromUser()
 \return Aws::String: The filter policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::getFilterPolicyFromUser() {
    std::cout
            << "You can filter messages by one or more of the following \""
            << TONE_ATTRIBUTE << "\" attributes." << std::endl;

    std::vector<Aws::String> filterSelections;
    int selection;
```

```
    do {
        for (size_t j = 0; j < TONES.size(); ++j) {
            std::cout << "  " << (j + 1) << ". " << TONES[j]
                      << std::endl;
        }
        selection = askQuestionForIntRange(
                "Enter a number (or enter zero to stop adding more). ",
                0, static_cast<int>(TONES.size()));

        if (selection != 0) {
            const Aws::String &selectedTone(TONES[selection - 1]);
            // Add the tone to the selection if it is not already added.
            if (std::find(filterSelections.begin(),
                          filterSelections.end(),
                          selectedTone)
                == filterSelections.end()) {
                filterSelections.push_back(selectedTone);
            }
        }
    } while (selection != 0);

    Aws::String result;
    if (!filterSelections.empty()) {
        std::ostringstream jsonPolicyStream;
        jsonPolicyStream << "{ \"" << TONE_ATTRIBUTE << "\": [";


        for (size_t j = 0; j < filterSelections.size(); ++j) {
            jsonPolicyStream << "\"" << filterSelections[j] << "\"";
            if (j < filterSelections.size() - 1) {
                jsonPolicyStream << ",";
            }
        }
        jsonPolicyStream << "] }";

        result = jsonPolicyStream.str();
    }

    return result;
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for C++.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
    printAsterisksLine();
    std::cout << "In this workflow, you will create an SNS topic and subscribe "
              << NUMBER_OF_QUEUES <<
              " SQS queues to the topic." << std::endl;
    std::cout
            << "You can select from several options for configuring the topic and
 the subscriptions for the "
            << NUMBER_OF_QUEUES << " queues." << std::endl;
    std::cout << "You can then post to the topic and see the results in the queues."
              << std::endl;
```

```
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    printAsterisksLine();

    std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
              << std::endl;
    std::cout
            << "FIFO topics deliver messages in order and support deduplication and
 message filtering."
            << std::endl;
    bool isFifoTopic = askYesNoQuestion(
            "Would you like to work with FIFO topics? (y/n) ");

    bool contentBasedDeduplication = false;
    Aws::String topicName;
    if (isFifoTopic) {
        printAsterisksLine();
        std::cout << "Because you have chosen a FIFO topic, deduplication is
 supported."
                  << std::endl;
        std::cout
                << "Deduplication IDs are either set in the message or automatically
 generated "
                << "from content using a hash function." << std::endl;
        std::cout
                << "If a message is successfully published to an SNS FIFO topic, any
 message "
                << "published and determined to have the same deduplication ID, "
                << std::endl;
        std::cout
                << "within the five-minute deduplication interval, is accepted but
 not delivered."
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a deduplication
 ID? (y/n) ");
    }
```

```
    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
    {
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;

        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " << std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
```

```
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                      "true");
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue, '.fifo'
must "
                            << "be appended to the queue name." << std::endl;
                }
            }

            request.SetQueueName(queueName);
```

```
            queueNames.push_back(queueName);

            Aws::SQS::Model::CreateQueueOutcome outcome =
                    sqsClient.CreateQueue(request);

            if (outcome.IsSuccess()) {
                queueURL = outcome.GetResult().GetQueueUrl();
                std::cout << "Your new SQS queue with the name '" << queueName
                          << "' and the queue URL " << std::endl;
                std::cout << "'" << queueURL << "' has been created." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::CreateQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
        queueURLS.push_back(queueURL);

        if (first) // Only explain this once.
        {
            std::cout
                    << "The queue URL is used to retrieve the queue ARN, which is "
                    << "used to create a subscription." << std::endl;
        }

        Aws::String queueARN;
        {
            // 3.  Get the SQS queue ARN attribute.
            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);
```

```
            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        if (first) {
```

```
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling it
to receive "
                       "messages from an SNS topic." << std::endl;
        }

        {
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
```

```
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then only
 the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
                                << "will be added to this subscription." <<
 std::endl;
                    }
                }
            }  // if (isFifoTopic)
```

```
            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
```

```
                        << "Because you are using a FIFO topic, you must set a
message group ID."
                        << std::endl;
                std::cout
                        << "All messages within the same group will be received in
the "
                        << "order they were published." << std::endl;
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
```

```
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }

        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
 outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
```

```
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }

        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
```

```
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}


bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
```

```
                                        const Aws::Vector<Aws::String>
&subscriptionARNS,
                                        const Aws::SNS::SNSClient &snsClient,
                                        const Aws::SQS::SQSClient &sqsClient,
                                        bool askUser) {
   bool result = true;
   printAsterisksLine();
   if (!queueURLS.empty() && askUser &&
       askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

       for (const auto &queueURL: queueURLS) {
           // 9.  Delete an SQS queue.
           Aws::SQS::Model::DeleteQueueRequest request;
           request.SetQueueUrl(queueURL);

           Aws::SQS::Model::DeleteQueueOutcome outcome =
                   sqsClient.DeleteQueue(request);

           if (outcome.IsSuccess()) {
               std::cout << "The queue with URL '" << queueURL
                         << "' was successfully deleted." << std::endl;
           }
           else {
               std::cerr << "Error with SQS::DeleteQueue. "
                         << outcome.GetError().GetMessage()
                         << std::endl;
               result = false;
           }
       }

       for (const auto &subscriptionARN: subscriptionARNS) {
           // 10. Unsubscribe an SNS subscription.
           Aws::SNS::Model::UnsubscribeRequest request;
           request.SetSubscriptionArn(subscriptionARN);

           Aws::SNS::Model::UnsubscribeOutcome outcome =
                   snsClient.Unsubscribe(request);

           if (outcome.IsSuccess()) {
               std::cout << "Unsubscribe of subscription ARN '" << subscriptionARN
                         << "' was successful." << std::endl;
           }
           else {
               std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
```

```
                            << outcome.GetError().GetMessage()
                            << std::endl;
                    result = false;
                }
            }
        }

        printAsterisksLine();
        if (!topicARN.empty() && askUser &&
            askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

            // 11. Delete an SNS topic.
            Aws::SNS::Model::DeleteTopicRequest request;
            request.SetTopicArn(topicARN);

            Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

            if (outcome.IsSuccess()) {
                std::cout << "The topic with ARN '" << topicARN
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        return result;
    }

    //! Create an IAM policy that gives an SQS queue permission to receive messages from
 an SNS topic.
    /*!
     \sa createPolicyForQueue()
     \param queueARN: The SQS queue Amazon Resource Name (ARN).
     \param topicARN: The SNS topic ARN.
     \return Aws::String: The policy as JSON.
     */
    Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
```

```
                                                                const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos do Amazon SQS usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para o arquivo CMake C MakeLists .txt.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sqs)

# Set this project's name.
project("hello_sqs")

# Set the C++ standard to use to build this target.
```

```
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if(WINDOWS_BUILD)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif()

add_executable(${PROJECT_NAME}
        hello_sqs.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Código para o arquivo de origem hello_sqs.cpp.

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ListQueuesRequest.h>
#include <iostream>

/*
```

```
 *  A "Hello SQS" starter application that initializes an Amazon Simple Queue
 Service
 *  (Amazon SQS) client and lists the SQS queues in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sqs'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SQS::SQSClient sqsClient(clientConfig);

        Aws::Vector<Aws::String> allQueueUrls;
        Aws::String nextToken; // Next token is used to handle a paginated response.
        do {
            Aws::SQS::Model::ListQueuesRequest request;

            Aws::SQS::Model::ListQueuesOutcome outcome =
 sqsClient.ListQueues(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::String> &pageOfQueueUrls =
 outcome.GetResult().GetQueueUrls();
                if (!pageOfQueueUrls.empty()) {
                    allQueueUrls.insert(allQueueUrls.cend(),
 pageOfQueueUrls.cbegin(),
                                        pageOfQueueUrls.cend());
                }
            }
            else {
                std::cerr << "Error with SQS::ListQueues. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
```

```
            }
            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());


        std::cout << "Hello Amazon SQS! You have " << allQueueUrls.size() << "
 queue"
                  << (allQueueUrls.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allQueueUrls.empty()) {
            std::cout << "Here are your queue URLs." << std::endl;
            for (const Aws::String &queueUrl: allQueueUrls) {
                std::cout << "  * " << queueUrl << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for C++ da API.

Tópicos

- Ações
- Cenários

Ações

Alterar quanto tempo uma fila espera por uma mensagem

O exemplo de código a seguir mostra como alterar por quanto tempo uma fila do Amazon SQS aguarda a chegada de uma mensagem.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Set the wait time for an Amazon Simple Queue Service (Amazon SQS) queue poll.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param pollTimeSeconds: The receive message wait time in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueLongPollingAttribute(const Aws::String &queueURL,
                                               const Aws::String &pollTimeSeconds,
                                               const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::ReceiveMessageWaitTimeSeconds,
            pollTimeSeconds);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated long polling time for queue " <<
                  queueURL << " to " << pollTimeSeconds << std::endl;
    }
    else {
        std::cout << "Error updating long polling time for queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

Alterar a visibilidade do tempo limite da mensagem

O exemplo de código a seguir mostra como alterar uma visibilidade de tempo limite de mensagem do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Changes the visibility timeout of a message in an Amazon Simple Queue Service
//! (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param visibilityTimeoutSeconds: Visibility timeout in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::changeMessageVisibility(
        const Aws::String &queue_url,
        const Aws::String &messageReceiptHandle,
        int visibilityTimeoutSeconds,
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
    Aws::SQS::Model::ChangeMessageVisibilityRequest request;
    request.SetQueueUrl(queue_url);
    request.SetReceiptHandle(messageReceiptHandle);
    request.SetVisibilityTimeout(visibilityTimeoutSeconds);

    auto outcome = sqsClient.ChangeMessageVisibility(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully changed visibility of message " <<
                  messageReceiptHandle << " from queue " << queue_url << std::endl;
    }
    else {
        std::cout << "Error changing visibility of message from queue "
                  << queue_url << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for C++ da API.

Configurar uma fila de mensagens não entregues

O exemplo de código a seguir mostra como configurar uma fila de mensagens mortas no Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
//! Connect an Amazon Simple Queue Service (Amazon SQS) queue to an associated
//! dead-letter queue.
/*!
  \param srcQueueUrl: An Amazon SQS queue URL.
  \param deadLetterQueueARN: The Amazon Resource Name (ARN) of an Amazon SQS dead-
letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setDeadLetterQueue(const Aws::String &srcQueueUrl,
                                     const Aws::String &deadLetterQueueARN,
                                     int maxReceiveCount,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::String redrivePolicy = MakeRedrivePolicy(deadLetterQueueARN,
 maxReceiveCount);

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(srcQueueUrl);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::RedrivePolicy,
            redrivePolicy);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
            sqsClient.SetQueueAttributes(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set dead letter queue for queue  " <<
                  srcQueueUrl << " to " << deadLetterQueueARN << std::endl;
    }
    else {
        std::cerr << "Error setting dead letter queue for queue " <<
                  srcQueueUrl << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}

//! Make a redrive policy for a dead-letter queue.
/*!
```

```
  \param queueArn: An Amazon SQS ARN for the dead-letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \return Aws::String: Policy as JSON string.
 */
Aws::String MakeRedrivePolicy(const Aws::String &queueArn, int maxReceiveCount) {
    Aws::Utils::Json::JsonValue redrive_arn_entry;
    redrive_arn_entry.AsString(queueArn);

    Aws::Utils::Json::JsonValue max_msg_entry;
    max_msg_entry.AsInteger(maxReceiveCount);

    Aws::Utils::Json::JsonValue policy_map;
    policy_map.WithObject("deadLetterTargetArn", redrive_arn_entry);
    policy_map.WithObject("maxReceiveCount", max_msg_entry);

    return policy_map.View().WriteReadable();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

Criar uma fila

Os exemplos de código a seguir mostram como criar uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Create an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
```

```
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::createQueue(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::CreateQueueRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::CreateQueueOutcome outcome =
 sqsClient.CreateQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created queue " << queueName << " with a queue
 URL "
                  << outcome.GetResult().GetQueueUrl() << "." << std::endl;
    }
    else {
        std::cerr << "Error creating queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for C++ da API.

Excluir um lote de mensagens de uma fila

O exemplo de código a seguir mostra como excluir um lote de mensagens de uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for C++ da API.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteMessage(const Aws::String &queueUrl,
                                const Aws::String &messageReceiptHandle,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::DeleteMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetReceiptHandle(messageReceiptHandle);

    const Aws::SQS::Model::DeleteMessageOutcome outcome = sqsClient.DeleteMessage(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted message from queue " << queueUrl
                  << std::endl;
    }
    else {
        std::cerr << "Error deleting message from queue " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for C++ da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueURL: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteQueue(const Aws::String &queueURL,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::SQS::Model::DeleteQueueRequest request;
    request.SetQueueUrl(queueURL);

    const Aws::SQS::Model::DeleteQueueOutcome outcome =
 sqsClient.DeleteQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted queue with url " << queueURL <<
                  std::endl;
    }
```

```
    else {
        std::cerr << "Error deleting queue " << queueURL << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for C++ da API.

Obter atributos para uma fila

O exemplo de código a seguir mostra como obter atributos para uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
```

```
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }

            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;


            }
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for C++ da API.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Get the URL for an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
```

```
 */
bool AwsDoc::SQS::getQueueUrl(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::GetQueueUrlRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::GetQueueUrlOutcome outcome =
 sqsClient.GetQueueUrl(request);
    if (outcome.IsSuccess()) {
        std::cout << "Queue " << queueName << " has url " <<
                  outcome.GetResult().GetQueueUrl() << std::endl;
    }
    else {
        std::cerr << "Error getting url for queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for C++ da API.

Listar filas

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
//! List the Amazon Simple Queue Service (Amazon SQS) queues within an AWS account.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SQS::listQueues(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ListQueuesRequest lq_req;

    const Aws::SQS::Model::ListQueuesOutcome outcome = sqsClient.ListQueues(lq_req);
    if (outcome.IsSuccess()) {
        std::cout << "Queue Urls:" << std::endl << std::endl;
        const auto &queue_urls = outcome.GetResult().GetQueueUrls();
        for (const auto &iter: queue_urls) {
            std::cout << " " << iter << std::endl;
        }
    }
    else {
        std::cerr << "Error listing queues: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for C++ da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Receive a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::receiveMessage(const Aws::String &queueUrl,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ReceiveMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMaxNumberOfMessages(1);

    const Aws::SQS::Model::ReceiveMessageOutcome outcome = sqsClient.ReceiveMessage(
            request);
    if (outcome.IsSuccess()) {

        const Aws::Vector<Aws::SQS::Model::Message> &messages =
                outcome.GetResult().GetMessages();
        if (!messages.empty()) {
            const Aws::SQS::Model::Message &message = messages[0];
            std::cout << "Received message:" << std::endl;
            std::cout << "  MessageId: " << message.GetMessageId() << std::endl;
            std::cout << "  ReceiptHandle: " << message.GetReceiptHandle() <<
 std::endl;
            std::cout << "  Body: " << message.GetBody() << std::endl << std::endl;
        }
        else {
            std::cout << "No messages received from queue " << queueUrl <<
                      std::endl;

        }
    }
    else {
        std::cerr << "Error receiving message from queue " << queueUrl << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for C++ da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Send a message to an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageBody: A message body.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::sendMessage(const Aws::String &queueUrl,
                              const Aws::String &messageBody,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SendMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMessageBody(messageBody);

    const Aws::SQS::Model::SendMessageOutcome outcome =
 sqsClient.SendMessage(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully sent message to " << queueUrl <<
                  std::endl;
    }
    else {
        std::cerr << "Error sending message to " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for C++ da API.

Definir atributos de fila

O exemplo de código a seguir mostra como definir os atributos para uma fila do Amazon SQS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Set the value for an attribute in an Amazon Simple Queue Service (Amazon SQS)
 queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param attributeName: An attribute name enum.
  \param attribute: The attribute value as a string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueAttributes(const Aws::String &queueURL,
                                     Aws::SQS::Model::QueueAttributeName
 attributeName,
```

```
                                        const Aws::String &attribute,
                                        const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            attributeName,
            attribute);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set the attribute  " <<

 Aws::SQS::Model::QueueAttributeNameMapper::GetNameForQueueAttributeName(
                         attributeName)
                  << " with value " << attribute << " in queue " <<
                  queueURL << "." << std::endl;
    }
    else {
        std::cout << "Error setting attribute for  queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for C++ da API.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).

- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
    printAsterisksLine();
    std::cout << "In this workflow, you will create an SNS topic and subscribe "
              << NUMBER_OF_QUEUES <<
              " SQS queues to the topic." << std::endl;
    std::cout
            << "You can select from several options for configuring the topic and
 the subscriptions for the "
            << NUMBER_OF_QUEUES << " queues." << std::endl;
    std::cout << "You can then post to the topic and see the results in the queues."
              << std::endl;

    Aws::SNS::SNSClient snsClient(clientConfiguration);

    printAsterisksLine();

    std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
              << std::endl;
```

```
    std::cout
            << "FIFO topics deliver messages in order and support deduplication and
 message filtering."
            << std::endl;
    bool isFifoTopic = askYesNoQuestion(
            "Would you like to work with FIFO topics? (y/n) ");

    bool contentBasedDeduplication = false;
    Aws::String topicName;
    if (isFifoTopic) {
        printAsterisksLine();
        std::cout << "Because you have chosen a FIFO topic, deduplication is
 supported."
                  << std::endl;
        std::cout
                << "Deduplication IDs are either set in the message or automatically
 generated "
                << "from content using a hash function." << std::endl;
        std::cout
                << "If a message is successfully published to an SNS FIFO topic, any
 message "
                << "published and determined to have the same deduplication ID, "
                << std::endl;
        std::cout
                << "within the five-minute deduplication interval, is accepted but
 not delivered."
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a deduplication
 ID? (y/n) ");
    }

    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
```

```
    {
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;

        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " << std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

```
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                  "true");
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue, '.fifo'
must "
                            << "be appended to the queue name." << std::endl;
                }
            }

            request.SetQueueName(queueName);
            queueNames.push_back(queueName);

            Aws::SQS::Model::CreateQueueOutcome outcome =
                    sqsClient.CreateQueue(request);

            if (outcome.IsSuccess()) {
                queueURL = outcome.GetResult().GetQueueUrl();
```

```
                std::cout << "Your new SQS queue with the name '" << queueName
                          << "' and the queue URL " << std::endl;
                std::cout << "'" << queueURL << "' has been created." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::CreateQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
        queueURLS.push_back(queueURL);

        if (first) // Only explain this once.
        {
            std::cout
                    << "The queue URL is used to retrieve the queue ARN, which is "
                    << "used to create a subscription." << std::endl;
        }

        Aws::String queueARN;
        {
            // 3.  Get the SQS queue ARN attribute.
            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
```

```
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        if (first) {
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling it
to receive "
                       "messages from an SNS topic." << std::endl;
        }

        {
```

```
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have filters."
                              << std::endl;
                    std::cout
```

```
                            << "If you add a filter to this subscription, then only
 the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
                                << "will be added to this subscription." <<
 std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
 outcome.GetResult().GetSubscriptionArn();
```

```
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
                        << "Because you are using a FIFO topic, you must set a
message group ID."
                        << std::endl;
                std::cout
                        << "All messages within the same group will be received in
the "
                        << "order they were published." << std::endl;
```

```
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
```

```
                    snsClient,
                    sqsClient);

            return false;
        }

        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
 outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
```

```
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }

        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
```

```
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}


bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
                                      const Aws::Vector<Aws::String>
 &subscriptionARNS,
                                      const Aws::SNS::SNSClient &snsClient,
                                      const Aws::SQS::SQSClient &sqsClient,
                                      bool askUser) {
    bool result = true;
    printAsterisksLine();
    if (!queueURLS.empty() && askUser &&
```

```
        askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

        for (const auto &queueURL: queueURLS) {
            // 9.  Delete an SQS queue.
            Aws::SQS::Model::DeleteQueueRequest request;
            request.SetQueueUrl(queueURL);

            Aws::SQS::Model::DeleteQueueOutcome outcome =
                    sqsClient.DeleteQueue(request);

            if (outcome.IsSuccess()) {
                std::cout << "The queue with URL '" << queueURL
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        for (const auto &subscriptionARN: subscriptionARNS) {
            // 10. Unsubscribe an SNS subscription.
            Aws::SNS::Model::UnsubscribeRequest request;
            request.SetSubscriptionArn(subscriptionARN);

            Aws::SNS::Model::UnsubscribeOutcome outcome =
                    snsClient.Unsubscribe(request);

            if (outcome.IsSuccess()) {
                std::cout << "Unsubscribe of subscription ARN '" << subscriptionARN
                          << "' was successful." << std::endl;
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    printAsterisksLine();
```

```
    if (!topicARN.empty() && askUser &&
        askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

        // 11. Delete an SNS topic.
        Aws::SNS::Model::DeleteTopicRequest request;
        request.SetTopicArn(topicARN);

        Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

        if (outcome.IsSuccess()) {
            std::cout << "The topic with ARN '" << topicARN
                      << "' was successfully deleted." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Create an IAM policy that gives an SQS queue permission to receive messages from
 an SNS topic.
/*!
 \sa createPolicyForQueue()
 \param queueARN: The SQS queue Amazon Resource Name (ARN).
 \param topicARN: The SNS topic ARN.
 \return Aws::String: The policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
                                                          const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
```

```
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for C++.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos de AWS STS usando SDK para C++

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
bool AwsDoc::STS::assumeRole(const Aws::String &roleArn,
                             const Aws::String &roleSessionName,
                             const Aws::String &externalId,
                             Aws::Auth::AWSCredentials &credentials,
                             const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::STS::STSClient sts(clientConfig);
    Aws::STS::Model::AssumeRoleRequest sts_req;

    sts_req.SetRoleArn(roleArn);
    sts_req.SetRoleSessionName(roleSessionName);
    sts_req.SetExternalId(externalId);

    const Aws::STS::Model::AssumeRoleOutcome outcome = sts.AssumeRole(sts_req);
```

```
    if (!outcome.IsSuccess()) {
        std::cerr << "Error assuming IAM role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Credentials successfully retrieved." << std::endl;
        const Aws::STS::Model::AssumeRoleResult result = outcome.GetResult();
        const Aws::STS::Model::Credentials &temp_credentials =
 result.GetCredentials();

        // Store temporary credentials in return argument.
        // Note: The credentials object returned by assumeRole differs
        // from the AWSCredentials object used in most situations.
        credentials.SetAWSAccessKeyId(temp_credentials.GetAccessKeyId());
        credentials.SetAWSSecretKey(temp_credentials.GetSecretAccessKey());
        credentials.SetSessionToken(temp_credentials.GetSessionToken());
    }

    return outcome.IsSuccess();
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for C++ da API.

Exemplos do Amazon Transcribe usando SDK para C++

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for C++ com o Amazon Transcribe.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Produzir transcrições em tempo real

O exemplo de código a seguir mostra como produzir uma transcrição em tempo real com o Amazon Transcribe.

SDK for C++

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
int main() {
    Aws::SDKOptions options;
    options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Trace;
    Aws::InitAPI(options);
    {
        //TODO(User): Set to the region of your AWS account.
        const Aws::String region = Aws::Region::US_WEST_2;

        //Load a profile that has been granted AmazonTranscribeFullAccess AWS
 managed permission policy.
        Aws::Client::ClientConfiguration config;
#ifdef _WIN32
        // ATTENTION: On Windows with the AWS C++ SDK, this example only runs if the
 SDK is built
        // with the curl library.
        // For more information, see the accompanying ReadMe.
        // For more information, see "Building the SDK for Windows with curl".
        // https://docs.aws.amazon.com/sdk-for-cpp/v1/developer-guide/setup-
windows.html
        //TODO(User): Update to the location of your .crt file.
        config.caFile = "C:/curl/bin/curl-ca-bundle.crt";
#endif
        config.region = region;

        TranscribeStreamingServiceClient client(config);
        StartStreamTranscriptionHandler handler;
        handler.SetOnErrorCallback(
```

```
                []( const Aws::Client::AWSError<TranscribeStreamingServiceErrors>
&error) {
                        std::cerr << "ERROR: " + error.GetMessage() << std::endl;
                });
        //SetTranscriptEventCallback called for every 'chunk' of file transcripted.
        // Partial results are returned in real time.
        handler.SetTranscriptEventCallback([](const TranscriptEvent &ev) {
                for (auto &&r: ev.GetTranscript().GetResults()) {
                    if (r.GetIsPartial()) {
                        std::cout << "[partial] ";
                    }
                    else {
                        std::cout << "[Final] ";
                    }
                    for (auto &&alt: r.GetAlternatives()) {
                        std::cout << alt.GetTranscript() << std::endl;
                    }
                }
        });

        StartStreamTranscriptionRequest request;
        request.SetMediaSampleRateHertz(SAMPLE_RATE);
        request.SetLanguageCode(LanguageCode::en_US);
        request.SetMediaEncoding(
                MediaEncoding::pcm); // wav and aiff files are PCM formats.
        request.SetEventStreamHandler(handler);

        auto OnStreamReady = [](AudioStream &stream) {
                Aws::FStream file(FILE_NAME, std::ios_base::in |
std::ios_base::binary);
                if (!file.is_open()) {
                    std::cerr << "Failed to open " << FILE_NAME << '\n';
                }
                std::array<char, BUFFER_SIZE> buf;
                int i = 0;
                while (file) {
                    file.read(&buf[0], buf.size());

                    if (!file)
                        std::cout << "File: only " << file.gcount() << " could be
read"
                                  << std::endl;

                    Aws::Vector<unsigned char> bits{buf.begin(), buf.end()};
```

```
                    AudioEvent event(std::move(bits));
                    if (!stream) {
                        std::cerr << "Failed to create a stream" << std::endl;
                        break;
                    }
                    //The std::basic_istream::gcount() is used to count the
 characters in the given string. It returns
                    //the number of characters extracted by the last read()
 operation.
                    if (file.gcount() > 0) {
                        if (!stream.WriteAudioEvent(event)) {
                            std::cerr << "Failed to write an audio event" <<
 std::endl;
                            break;
                        }
                    }
                    else {
                        break;
                    }
                    std::this_thread::sleep_for(std::chrono::milliseconds(
                            25)); // Slow down because we are streaming from a file.
                }
                if (!stream.WriteAudioEvent(
                        AudioEvent())) {
                    // Per the spec, we have to send an empty event (an event
 without a payload) at the end.
                    std::cerr << "Failed to send an empty frame" << std::endl;
                }
                else {
                    std::cout << "Successfully sent the empty frame" << std::endl;
                }
                stream.flush();
                stream.Close();
        };

        Aws::Utils::Threading::Semaphore signaling(0 /*initialCount*/, 1 /
*maxCount*/);
        auto OnResponseCallback = [&signaling](
                const TranscribeStreamingServiceClient * /*unused*/,
                const Model::StartStreamTranscriptionRequest & /*unused*/,
                const Model::StartStreamTranscriptionOutcome &outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext> & /
*unused*/) {
```

```
                if (!outcome.IsSuccess()) {
                    std::cerr << "Transcribe streaming error "
                              << outcome.GetError().GetMessage() << std::endl;
                }

                signaling.Release();
        };

        std::cout << "Starting..." << std::endl;
        client.StartStreamTranscriptionAsync(request, OnStreamReady,
 OnResponseCallback,
                                             nullptr /*context*/);
        signaling.WaitOne(); // Prevent the application from exiting until we're
 done.
        std::cout << "Done" << std::endl;
    }

    Aws::ShutdownAPI(options);

    return 0;
}
```

- Para obter detalhes da API, consulte StartStreamTranscriptionAsynca Referência AWS SDK for C++ da API.

Exemplos de serviços cruzados usando SDK para C++

Os aplicativos de exemplo a seguir usam o AWS SDK for C++ para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK for C++

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK for C++

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Aurora Sem Servidor.

Para obter o código-fonte completo e instruções sobre como configurar uma API REST C++ que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS

- Amazon SES

Exemplos de código para SDK para Go V2

Os exemplos de código a seguir mostram como usar V2 AWS SDK for Go com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do Desenvolvedor do SDK para Go V2 : Saiba mais sobre como usar o Go com AWS.
- AWS Centro do Desenvolvedor : Exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando SDK para Go V2

Ações e cenários usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK for Go V2 com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos Aurora usando SDK para Go V2
- Exemplos do Amazon Bedrock usando SDK para Go V2
- Exemplos do Amazon Bedrock Runtime usando o SDK para Go V2
- CloudWatch Exemplos de registros usando o SDK for Go V2
- Exemplos do DynamoDB usando SDK para Go V2
- Exemplos do IAM usando SDK para Go V2
- Exemplos do Kinesis usando o SDK para Go V2
- Exemplos de código do Lambda usando SDK para Go V2
- Exemplos de código para o Amazon RDS usando SDK para Go V2
- Exemplos de código do Amazon S3 usando SDK para Go V2
- Exemplos de código para o Amazon SNS usando SDK para Go V2
- Exemplos do Amazon SQS usando SDK para Go V2

Exemplos Aurora usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/rds"
)

// main uses the AWS SDK for Go V2 to create an Amazon Aurora client and list up to
 20
// DB clusters in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 auroraClient := rds.NewFromConfig(sdkConfig)
 const maxClusters = 20
 fmt.Printf("Let's list up to %v DB clusters.\n", maxClusters)
 output, err := auroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{MaxRecords: aws.Int32(maxClusters)})
 if err != nil {
  fmt.Printf("Couldn't list DB clusters: %v\n", err)
  return
 }
```

```
 if len(output.DBClusters) == 0 {
  fmt.Println("No DB clusters found.")
 } else {
  for _, cluster := range output.DBClusters {
   fmt.Printf("DB cluster %v has database %v.\n", *cluster.DBClusterIdentifier,
    *cluster.DatabaseName)
  }
 }
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Go.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

Os exemplos de código a seguir mostram como criar um cluster do Aurora DB.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}
```

```
// CreateDbCluster creates a DB cluster that is configured to use the specified
 parameter group.
// The newly created DB cluster contains a database that uses the specified engine
 and
// engine version.
func (clusters *DbClusters) CreateDbCluster(clusterName string, parameterGroupName
 string,
 dbName string, dbEngine string, dbEngineVersion string, adminName string,
 adminPassword string) (
 *types.DBCluster, error) {

 output, err := clusters.AuroraClient.CreateDBCluster(context.TODO(),
 &rds.CreateDBClusterInput{
  DBClusterIdentifier:         aws.String(clusterName),
  Engine:                      aws.String(dbEngine),
  DBClusterParameterGroupName: aws.String(parameterGroupName),
  DatabaseName:                aws.String(dbName),
  EngineVersion:               aws.String(dbEngineVersion),
  MasterUserPassword:          aws.String(adminPassword),
  MasterUsername:              aws.String(adminName),
 })
 if err != nil {
  log.Printf("Couldn't create DB cluster %v: %v\n", clusterName, err)
  return nil, err
 } else {
  return output.DBCluster, err
 }
}
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for Go.

Criar um parameter group de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um grupo de parâmetros de cluster do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateParameterGroup creates a DB cluster parameter group that is based on the
 specified
// parameter group family.
func (clusters *DbClusters) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBClusterParameterGroup, error) {

 output, err := clusters.AuroraClient.CreateDBClusterParameterGroup(context.TODO(),
  &rds.CreateDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   DBParameterGroupFamily:      aws.String(parameterGroupFamily),
   Description:                 aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBClusterParameterGroup, err
 }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for Go da API.

Criar um snapshot de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de cluster do Aurora DB

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateClusterSnapshot creates a snapshot of a DB cluster.
func (clusters *DbClusters) CreateClusterSnapshot(clusterName string, snapshotName
 string) (
 *types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.CreateDBClusterSnapshot(context.TODO(),
 &rds.CreateDBClusterSnapshotInput{
  DBClusterIdentifier:         aws.String(clusterName),
  DBClusterSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBClusterSnapshot, nil
 }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for Go da API.

Criar uma instância de banco de dados em um cluster de banco de dados

Os exemplos de código a seguir mostram como criar uma instância DB em um cluster Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// CreateInstanceInCluster creates a database instance in an existing DB cluster.
 The first database that is
// created defaults to a read-write DB instance.
func (clusters *DbClusters) CreateInstanceInCluster(clusterName string, instanceName
 string,
 dbEngine string, dbInstanceClass string) (*types.DBInstance, error) {
 output, err := clusters.AuroraClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBClusterIdentifier:  aws.String(clusterName),
  Engine:               aws.String(dbEngine),
  DBInstanceClass:      aws.String(dbInstanceClass),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Go.

Excluir um cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um cluster do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteDbCluster deletes a DB cluster without keeping a final snapshot.
func (clusters *DbClusters) DeleteDbCluster(clusterName string) error {
 _, err := clusters.AuroraClient.DeleteDBCluster(context.TODO(),
 &rds.DeleteDBClusterInput{
  DBClusterIdentifier: aws.String(clusterName),
  SkipFinalSnapshot:   true,
 })
 if err != nil {
  log.Printf("Couldn't delete DB cluster %v: %v\n", clusterName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for Go.

Excluir um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteParameterGroup deletes the named DB cluster parameter group.
func (clusters *DbClusters) DeleteParameterGroup(parameterGroupName string) error {
 _, err := clusters.AuroraClient.DeleteDBClusterParameterGroup(context.TODO(),
  &rds.DeleteDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for Go Referência da API.

Excluir uma instância de banco de dados

Os exemplos de código a seguir mostram como excluir uma instância do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// DeleteInstance deletes a DB instance.
func (clusters *DbClusters) DeleteInstance(instanceName string) error {
 _, err := clusters.AuroraClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Go.

Descrever os grupos de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever grupos de parâmetros de cluster do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetParameterGroup gets a DB cluster parameter group by name.
func (clusters *DbClusters) GetParameterGroup(parameterGroupName string) (
 *types.DBClusterParameterGroup, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterParameterGroups(
  context.TODO(), &rds.DescribeDBClusterParameterGroupsInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBClusterParameterGroups[0], err
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for Go da API.

Descrever snapshots de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever snapshots de cluster do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetClusterSnapshot gets a DB cluster snapshot.
func (clusters *DbClusters) GetClusterSnapshot(snapshotName string)
 (*types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterSnapshots(context.TODO(),
  &rds.DescribeDBClusterSnapshotsInput{
   DBClusterSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBClusterSnapshots[0], nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for Go da API.

Descrever clusters de banco de dados

Os exemplos de código a seguir mostram como descrever clusters do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetDbCluster gets data about an Aurora DB cluster.
func (clusters *DbClusters) GetDbCluster(clusterName string) (*types.DBCluster,
 error) {
 output, err := clusters.AuroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{
   DBClusterIdentifier: aws.String(clusterName),
  })
 if err != nil {
  var notFoundError *types.DBClusterNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB cluster %v does not exist.\n", clusterName)
   err = nil
  } else {
   log.Printf("Couldn't get DB cluster %v: %v\n", clusterName, err)
  }
  return nil, err
 } else {
  return &output.DBClusters[0], err
 }
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Go.

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetInstance gets data about a DB instance.
func (clusters *DbClusters) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := clusters.AuroraClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo do banco de dados do Aurora.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (clusters *DbClusters) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := clusters.AuroraClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
```

```
  return output.DBEngineVersions, nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Go da API.

Descrever as opções de instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever opções para instâncias do Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (clusters *DbClusters) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instances []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(clusters.AuroraClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
```

```
    EngineVersion: aws.String(engineVersion),
   })
  for orderablePaginator.HasMorePages() {
   output, err = orderablePaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't get orderable DB instances: %v\n", err)
    break
   } else {
    instances = append(instances, output.OrderableDBInstanceOptions...)
   }
  }
  return instances, err
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Go API.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever parâmetros de um grupo de parâmetros de cluster Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// GetParameters gets the parameters that are contained in a DB cluster parameter
 group.
```

```
func (clusters *DbClusters) GetParameters(parameterGroupName string, source string)
 (
 []types.Parameter, error) {

 var output *rds.DescribeDBClusterParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator :=
 rds.NewDescribeDBClusterParametersPaginator(clusters.AuroraClient,
  &rds.DescribeDBClusterParametersInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Source:                      aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get paramaeters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for Go da API.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros de um grupo de parâmetros de cluster Aurora DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbClusters struct {
 AuroraClient *rds.Client
}



// UpdateParameters updates parameters in a named DB cluster parameter group.
func (clusters *DbClusters) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := clusters.AuroraClient.ModifyDBClusterParameterGroup(context.TODO(),
  &rds.ModifyDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Parameters:                  params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for Go da API.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// GetStartedClusters is an interactive example that shows you how to use the AWS
 SDK for Go
// with Amazon Aurora to do the following:
//
// 1. Create a custom DB cluster parameter group and set parameter values.
// 2. Create an Aurora DB cluster that is configured to use the parameter group.
// 3. Create a DB instance in the DB cluster that contains a database.
// 4. Take a snapshot of the DB cluster.
// 5. Delete the DB instance, DB cluster, and parameter group.
type GetStartedClusters struct {
 sdkConfig  aws.Config
 dbClusters actions.DbClusters
 questioner demotools.IQuestioner
 helper     IScenarioHelper
 isTestRun  bool
}

// NewGetStartedClusters constructs a GetStartedClusters instance from a
 configuration.
// It uses the specified config to get an Amazon Relational Database Service (Amazon
 RDS)
// client and create wrappers for the actions used in the scenario.
func NewGetStartedClusters(sdkConfig aws.Config, questioner demotools.IQuestioner,
 helper IScenarioHelper) GetStartedClusters {
 auroraClient := rds.NewFromConfig(sdkConfig)
 return GetStartedClusters{
  sdkConfig:  sdkConfig,
  dbClusters: actions.DbClusters{AuroraClient: auroraClient},
  questioner: questioner,
  helper:     helper,
 }
}
```

```
// Run runs the interactive scenario.
func (scenario GetStartedClusters) Run(dbEngine string, parameterGroupName string,
 clusterName string, dbName string) {
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon Aurora DB Cluster demo.")
 log.Println(strings.Repeat("-", 88))

 parameterGroup := scenario.CreateParameterGroup(dbEngine, parameterGroupName)
 scenario.SetUserParameters(parameterGroupName)
 cluster := scenario.CreateCluster(clusterName, dbEngine, dbName, parameterGroup)
 scenario.helper.Pause(5)
 dbInstance := scenario.CreateInstance(cluster)
 scenario.DisplayConnection(cluster)
 scenario.CreateSnapshot(clusterName)
 scenario.Cleanup(dbInstance, cluster, parameterGroup)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateParameterGroup shows how to get available engine versions for a specified
// database engine and create a DB cluster parameter group that is compatible with a
// selected engine family.
func (scenario GetStartedClusters) CreateParameterGroup(dbEngine string,
 parameterGroupName string) *types.DBClusterParameterGroup {

 log.Printf("Checking for an existing DB cluster parameter group named %v.\n",
  parameterGroupName)
 parameterGroup, err := scenario.dbClusters.GetParameterGroup(parameterGroupName)
 if err != nil {
  panic(err)
 }
 if parameterGroup == nil {
  log.Printf("Getting available database engine versions for %v.\n", dbEngine)
  engineVersions, err := scenario.dbClusters.GetEngineVersions(dbEngine, "")
  if err != nil {
```

```
    panic(err)
   }

   familySet := map[string]struct{}{}
   for _, family := range engineVersions {
    familySet[*family.DBParameterGroupFamily] = struct{}{}
   }
   var families []string
   for family := range familySet {
    families = append(families, family)
   }
   sort.Strings(families)
   familyIndex := scenario.questioner.AskChoice("Which family do you want to use?\n",
  families)
   log.Println("Creating a DB cluster parameter group.")
   _, err = scenario.dbClusters.CreateParameterGroup(
    parameterGroupName, families[familyIndex], "Example parameter group.")
   if err != nil {
    panic(err)
   }
   parameterGroup, err = scenario.dbClusters.GetParameterGroup(parameterGroupName)
   if err != nil {
    panic(err)
   }
  }
  log.Printf("Parameter group %v:\n", *parameterGroup.DBParameterGroupFamily)
  log.Printf("\tName: %v\n", *parameterGroup.DBClusterParameterGroupName)
  log.Printf("\tARN: %v\n", *parameterGroup.DBClusterParameterGroupArn)
  log.Printf("\tFamily: %v\n", *parameterGroup.DBParameterGroupFamily)
  log.Printf("\tDescription: %v\n", *parameterGroup.Description)
  log.Println(strings.Repeat("-", 88))
  return parameterGroup

}

// SetUserParameters shows how to get the parameters contained in a custom parameter
// group and update some of the parameter values in the group.
func (scenario GetStartedClusters) SetUserParameters(parameterGroupName string) {
 log.Println("Let's set some parameter values in your parameter group.")
 dbParameters, err := scenario.dbClusters.GetParameters(parameterGroupName, "")
 if err != nil {
  panic(err)
 }
 var updateParams []types.Parameter
```

```
 for _, dbParam := range dbParameters {
  if strings.HasPrefix(*dbParam.ParameterName, "auto_increment") &&
   dbParam.IsModifiable && *dbParam.DataType == "integer" {
   log.Printf("The %v parameter is described as:\n\t%v",
    *dbParam.ParameterName, *dbParam.Description)
   rangeSplit := strings.Split(*dbParam.AllowedValues, "-")
   lower, _ := strconv.Atoi(rangeSplit[0])
   upper, _ := strconv.Atoi(rangeSplit[1])
   newValue := scenario.questioner.AskInt(
    fmt.Sprintf("Enter a value between %v and %v:", lower, upper),
    demotools.InIntRange{Lower: lower, Upper: upper})
   dbParam.ParameterValue = aws.String(strconv.Itoa(newValue))
   updateParams = append(updateParams, dbParam)
  }
 }
 err = scenario.dbClusters.UpdateParameters(parameterGroupName, updateParams)
 if err != nil {
  panic(err)
 }
 log.Println("You can get a list of parameters you've set by specifying a source of
 'user'.")
 userParameters, err := scenario.dbClusters.GetParameters(parameterGroupName,
 "user")
 if err != nil {
  panic(err)
 }
 log.Println("Here are the parameters you've set:")
 for _, param := range userParameters {
  log.Printf("\t%v: %v\n", *param.ParameterName, *param.ParameterValue)
 }
 log.Println(strings.Repeat("-", 88))
}

// CreateCluster shows how to create an Aurora DB cluster that contains a database
// of a specified type. The database is also configured to use a custom DB cluster
// parameter group.
func (scenario GetStartedClusters) CreateCluster(clusterName string, dbEngine
 string,
 dbName string, parameterGroup *types.DBClusterParameterGroup) *types.DBCluster {

 log.Println("Checking for an existing DB cluster.")
 cluster, err := scenario.dbClusters.GetDbCluster(clusterName)
 if err != nil {
  panic(err)
```

```
 }
 if cluster == nil {
  adminUsername := scenario.questioner.Ask(
   "Enter an administrator user name for the database: ", demotools.NotEmpty{})
  adminPassword := scenario.questioner.Ask(
   "Enter a password for the administrator (at least 8 characters): ",
 demotools.NotEmpty{})
  engineVersions, err := scenario.dbClusters.GetEngineVersions(dbEngine,
 *parameterGroup.DBParameterGroupFamily)
  if err != nil {
   panic(err)
  }
  var engineChoices []string
  for _, engine := range engineVersions {
   engineChoices = append(engineChoices, *engine.EngineVersion)
  }
  log.Println("The available engines for your parameter group are:")
  engineIndex := scenario.questioner.AskChoice("Which engine do you want to use?\n",
 engineChoices)
  log.Printf("Creating DB cluster %v and database %v.\n", clusterName, dbName)
  log.Printf("The DB cluster is configured to use\nyour custom parameter group %v
\n",
   *parameterGroup.DBClusterParameterGroupName)
  log.Printf("and selected engine %v.\n", engineChoices[engineIndex])
  log.Println("This typically takes several minutes.")
  cluster, err = scenario.dbClusters.CreateDbCluster(
   clusterName, *parameterGroup.DBClusterParameterGroupName, dbName, dbEngine,
   engineChoices[engineIndex], adminUsername, adminPassword)
  if err != nil {
   panic(err)
  }
  for *cluster.Status != "available" {
   scenario.helper.Pause(30)
   cluster, err = scenario.dbClusters.GetDbCluster(clusterName)
   if err != nil {
    panic(err)
   }
   log.Println("Cluster created and available.")
  }
 }
 log.Println("Cluster data:")
 log.Printf("\tDBClusterIdentifier: %v\n", *cluster.DBClusterIdentifier)
 log.Printf("\tARN: %v\n", *cluster.DBClusterArn)
 log.Printf("\tStatus: %v\n", *cluster.Status)
```

```
 log.Printf("\tEngine: %v\n", *cluster.Engine)
 log.Printf("\tEngine version: %v\n", *cluster.EngineVersion)
 log.Printf("\tDBClusterParameterGroup: %v\n", *cluster.DBClusterParameterGroup)
 log.Printf("\tEngineMode: %v\n", *cluster.EngineMode)
 log.Println(strings.Repeat("-", 88))
 return cluster
}

// CreateInstance shows how to create a DB instance in an existing Aurora DB
 cluster.
// A new DB cluster contains no DB instances, so you must add one. The first DB
 instance
// that is added to a DB cluster defaults to a read-write DB instance.
func (scenario GetStartedClusters) CreateInstance(cluster *types.DBCluster)
 *types.DBInstance {
 log.Println("Checking for an existing database instance.")
 dbInstance, err := scenario.dbClusters.GetInstance(*cluster.DBClusterIdentifier)
 if err != nil {
  panic(err)
 }
 if dbInstance == nil {
  log.Println("Let's create a database instance in your DB cluster.")
  log.Println("First, choose a DB instance type:")
  instOpts, err := scenario.dbClusters.GetOrderableInstances(
   *cluster.Engine, *cluster.EngineVersion)
  if err != nil {
   panic(err)
  }
  var instChoices []string
  for _, opt := range instOpts {
   instChoices = append(instChoices, *opt.DBInstanceClass)
  }
  instIndex := scenario.questioner.AskChoice(
   "Which DB instance class do you want to use?\n", instChoices)
  log.Println("Creating a database instance. This typically takes several minutes.")
  dbInstance, err = scenario.dbClusters.CreateInstanceInCluster(
   *cluster.DBClusterIdentifier, *cluster.DBClusterIdentifier, *cluster.Engine,
   instChoices[instIndex])
  if err != nil {
   panic(err)
  }
  for *dbInstance.DBInstanceStatus != "available" {
   scenario.helper.Pause(30)
   dbInstance, err = scenario.dbClusters.GetInstance(*cluster.DBClusterIdentifier)
```

```
    if err != nil {
     panic(err)
    }
   }
  }
  log.Println("Instance data:")
  log.Printf("\tDBInstanceIdentifier: %v\n", *dbInstance.DBInstanceIdentifier)
  log.Printf("\tARN: %v\n", *dbInstance.DBInstanceArn)
  log.Printf("\tStatus: %v\n", *dbInstance.DBInstanceStatus)
  log.Printf("\tEngine: %v\n", *dbInstance.Engine)
  log.Printf("\tEngine version: %v\n", *dbInstance.EngineVersion)
  log.Println(strings.Repeat("-", 88))
  return dbInstance
}

// DisplayConnection displays connection information about an Aurora DB cluster and
 tips
// on how to connect to it.
func (scenario GetStartedClusters) DisplayConnection(cluster *types.DBCluster) {
  log.Println(
   "You can now connect to your database using your favorite MySql client.\n" +
    "One way to connect is by using the 'mysql' shell on an Amazon EC2 instance\n" +
    "that is running in the same VPC as your database cluster. Pass the endpoint,\n"
  +
    "port, and administrator user name to 'mysql' and enter your password\n" +
    "when prompted:")
  log.Printf("\n\tmysql -h %v -P %v -u %v -p\n",
   *cluster.Endpoint, *cluster.Port, *cluster.MasterUsername)
  log.Println("For more information, see the User Guide for Aurora:\n" +
   "\thttps://docs.aws.amazon.com/AmazonRDS/latest/AuroraUserGuide/
CHAP_GettingStartedAurora.CreatingConnecting.Aurora.html#CHAP_GettingStartedAurora.Aurora.Co
  log.Println(strings.Repeat("-", 88))
}

// CreateSnapshot shows how to create a DB cluster snapshot and wait until it's
 available.
func (scenario GetStartedClusters) CreateSnapshot(clusterName string) {
  if scenario.questioner.AskBool(
   "Do you want to create a snapshot of your DB cluster (y/n)? ", "y") {
   snapshotId := fmt.Sprintf("%v-%v", clusterName, scenario.helper.UniqueId())
   log.Printf("Creating a snapshot named %v. This typically takes a few minutes.\n",
  snapshotId)
   snapshot, err := scenario.dbClusters.CreateClusterSnapshot(clusterName,
  snapshotId)
```

```
  if err != nil {
   panic(err)
  }
  for *snapshot.Status != "available" {
   scenario.helper.Pause(30)
   snapshot, err = scenario.dbClusters.GetClusterSnapshot(snapshotId)
   if err != nil {
    panic(err)
   }
  }
  log.Println("Snapshot data:")
  log.Printf("\tDBClusterSnapshotIdentifier: %v\n",
 *snapshot.DBClusterSnapshotIdentifier)
  log.Printf("\tARN: %v\n", *snapshot.DBClusterSnapshotArn)
  log.Printf("\tStatus: %v\n", *snapshot.Status)
  log.Printf("\tEngine: %v\n", *snapshot.Engine)
  log.Printf("\tEngine version: %v\n", *snapshot.EngineVersion)
  log.Printf("\tDBClusterIdentifier: %v\n", *snapshot.DBClusterIdentifier)
  log.Printf("\tSnapshotCreateTime: %v\n", *snapshot.SnapshotCreateTime)
  log.Println(strings.Repeat("-", 88))
 }
}

// Cleanup shows how to clean up a DB instance, DB cluster, and DB cluster parameter
 group.
// Before the DB cluster parameter group can be deleted, all associated DB instances
 and
// DB clusters must first be deleted.
func (scenario GetStartedClusters) Cleanup(dbInstance *types.DBInstance, cluster
 *types.DBCluster,
 parameterGroup *types.DBClusterParameterGroup) {

 if scenario.questioner.AskBool(
  "\nDo you want to delete the database instance, DB cluster, and parameter group
 (y/n)? ", "y") {
  log.Printf("Deleting database instance %v.\n", *dbInstance.DBInstanceIdentifier)
  err := scenario.dbClusters.DeleteInstance(*dbInstance.DBInstanceIdentifier)
  if err != nil {
   panic(err)
  }
  log.Printf("Deleting database cluster %v.\n", *cluster.DBClusterIdentifier)
  err = scenario.dbClusters.DeleteDbCluster(*cluster.DBClusterIdentifier)
  if err != nil {
   panic(err)
```

```
  }
  log.Println(
   "Waiting for the DB instance and DB cluster to delete. This typically takes
 several minutes.")
  for dbInstance != nil || cluster != nil {
   scenario.helper.Pause(30)
   if dbInstance != nil {
    dbInstance, err =
 scenario.dbClusters.GetInstance(*dbInstance.DBInstanceIdentifier)
    if err != nil {
     panic(err)
    }
   }
   if cluster != nil {
    cluster, err = scenario.dbClusters.GetDbCluster(*cluster.DBClusterIdentifier)
    if err != nil {
     panic(err)
    }
   }
  }
  log.Printf("Deleting parameter group %v.",
 *parameterGroup.DBClusterParameterGroupName)
  err =
 scenario.dbClusters.DeleteParameterGroup(*parameterGroup.DBClusterParameterGroupName)
  if err != nil {
   panic(err)
  }
 }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Aurora.

```
type DbClusters struct {
 AuroraClient *rds.Client
}


// GetParameterGroup gets a DB cluster parameter group by name.
func (clusters *DbClusters) GetParameterGroup(parameterGroupName string) (
 *types.DBClusterParameterGroup, error) {
```

```
 output, err := clusters.AuroraClient.DescribeDBClusterParameterGroups(
  context.TODO(), &rds.DescribeDBClusterParameterGroupsInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBClusterParameterGroups[0], err
 }
}


// CreateParameterGroup creates a DB cluster parameter group that is based on the
 specified
// parameter group family.
func (clusters *DbClusters) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBClusterParameterGroup, error) {

 output, err := clusters.AuroraClient.CreateDBClusterParameterGroup(context.TODO(),
  &rds.CreateDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   DBParameterGroupFamily:      aws.String(parameterGroupFamily),
   Description:                 aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBClusterParameterGroup, err
 }
}



// DeleteParameterGroup deletes the named DB cluster parameter group.
func (clusters *DbClusters) DeleteParameterGroup(parameterGroupName string) error {
```

```
 _, err := clusters.AuroraClient.DeleteDBClusterParameterGroup(context.TODO(),
  &rds.DeleteDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// GetParameters gets the parameters that are contained in a DB cluster parameter
 group.
func (clusters *DbClusters) GetParameters(parameterGroupName string, source string)
 (
 []types.Parameter, error) {

 var output *rds.DescribeDBClusterParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator :=
 rds.NewDescribeDBClusterParametersPaginator(clusters.AuroraClient,
  &rds.DescribeDBClusterParametersInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Source:                      aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get paramaeters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}



// UpdateParameters updates parameters in a named DB cluster parameter group.
```

```
func (clusters *DbClusters) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := clusters.AuroraClient.ModifyDBClusterParameterGroup(context.TODO(),
  &rds.ModifyDBClusterParameterGroupInput{
   DBClusterParameterGroupName: aws.String(parameterGroupName),
   Parameters:                  params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}



// GetDbCluster gets data about an Aurora DB cluster.
func (clusters *DbClusters) GetDbCluster(clusterName string) (*types.DBCluster,
 error) {
 output, err := clusters.AuroraClient.DescribeDBClusters(context.TODO(),
  &rds.DescribeDBClustersInput{
   DBClusterIdentifier: aws.String(clusterName),
  })
 if err != nil {
  var notFoundError *types.DBClusterNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB cluster %v does not exist.\n", clusterName)
   err = nil
  } else {
   log.Printf("Couldn't get DB cluster %v: %v\n", clusterName, err)
  }
  return nil, err
 } else {
  return &output.DBClusters[0], err
 }
}



// CreateDbCluster creates a DB cluster that is configured to use the specified
 parameter group.
// The newly created DB cluster contains a database that uses the specified engine
 and
```

```
// engine version.
func (clusters *DbClusters) CreateDbCluster(clusterName string, parameterGroupName
 string,
 dbName string, dbEngine string, dbEngineVersion string, adminName string,
 adminPassword string) (
 *types.DBCluster, error) {

 output, err := clusters.AuroraClient.CreateDBCluster(context.TODO(),
 &rds.CreateDBClusterInput{
  DBClusterIdentifier:         aws.String(clusterName),
  Engine:                      aws.String(dbEngine),
  DBClusterParameterGroupName: aws.String(parameterGroupName),
  DatabaseName:                aws.String(dbName),
  EngineVersion:               aws.String(dbEngineVersion),
  MasterUserPassword:          aws.String(adminPassword),
  MasterUsername:              aws.String(adminName),
 })
 if err != nil {
  log.Printf("Couldn't create DB cluster %v: %v\n", clusterName, err)
  return nil, err
 } else {
  return output.DBCluster, err
 }
}



// DeleteDbCluster deletes a DB cluster without keeping a final snapshot.
func (clusters *DbClusters) DeleteDbCluster(clusterName string) error {
 _, err := clusters.AuroraClient.DeleteDBCluster(context.TODO(),
 &rds.DeleteDBClusterInput{
  DBClusterIdentifier: aws.String(clusterName),
  SkipFinalSnapshot:   true,
 })
 if err != nil {
  log.Printf("Couldn't delete DB cluster %v: %v\n", clusterName, err)
  return err
 } else {
  return nil
 }
}
```

```
// CreateClusterSnapshot creates a snapshot of a DB cluster.
func (clusters *DbClusters) CreateClusterSnapshot(clusterName string, snapshotName
 string) (
 *types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.CreateDBClusterSnapshot(context.TODO(),
 &rds.CreateDBClusterSnapshotInput{
  DBClusterIdentifier:         aws.String(clusterName),
  DBClusterSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBClusterSnapshot, nil
 }
}



// GetClusterSnapshot gets a DB cluster snapshot.
func (clusters *DbClusters) GetClusterSnapshot(snapshotName string)
 (*types.DBClusterSnapshot, error) {
 output, err := clusters.AuroraClient.DescribeDBClusterSnapshots(context.TODO(),
  &rds.DescribeDBClusterSnapshotsInput{
   DBClusterSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBClusterSnapshots[0], nil
 }
}



// CreateInstanceInCluster creates a database instance in an existing DB cluster.
 The first database that is
// created defaults to a read-write DB instance.
func (clusters *DbClusters) CreateInstanceInCluster(clusterName string, instanceName
 string,
 dbEngine string, dbInstanceClass string) (*types.DBInstance, error) {
 output, err := clusters.AuroraClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
```

```
  DBInstanceIdentifier: aws.String(instanceName),
  DBClusterIdentifier:  aws.String(clusterName),
  Engine:               aws.String(dbEngine),
  DBInstanceClass:      aws.String(dbInstanceClass),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}



// GetInstance gets data about a DB instance.
func (clusters *DbClusters) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := clusters.AuroraClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}



// DeleteInstance deletes a DB instance.
func (clusters *DbClusters) DeleteInstance(instanceName string) error {
 _, err := clusters.AuroraClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
```

```
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (clusters *DbClusters) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := clusters.AuroraClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (clusters *DbClusters) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instances []types.OrderableDBInstanceOption
 var err error
```

```
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(clusters.AuroraClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instances: %v\n", err)
   break
  } else {
   instances = append(instances, output.OrderableDBInstanceOptions...)
  }
 }
 return instances, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - DB descrito ClusterParameterGroups
  - DB descrito ClusterParameters
  - DB descrito ClusterSnapshots
  - DescribeDBClusters
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Exemplos do Amazon Bedrock usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Bedrock

Os exemplos de código a seguir mostram como começar a usar o Amazon Bedrock.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/bedrock"
)

const region = "us-east-1"
```

```
// main uses the AWS SDK for Go (v2) to create an Amazon Bedrock client and
// list the available foundation models in your account and the chosen region.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
    sdkConfig, err := config.LoadDefaultConfig(context.TODO(),
 config.WithRegion(region))
    if err != nil {
        fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
        fmt.Println(err)
        return
    }
    bedrockClient := bedrock.NewFromConfig(sdkConfig)
    result, err := bedrockClient.ListFoundationModels(context.TODO(),
 &bedrock.ListFoundationModelsInput{})
    if err != nil {
  fmt.Printf("Couldn't list foundation models. Here's why: %v\n", err)
  return
    }
    if len(result.ModelSummaries) == 0 {
    fmt.Println("There are no foundation models.")}
    for _, modelSummary := range result.ModelSummaries {
        fmt.Println(*modelSummary.ModelId)
    }
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Go da API.

Tópicos

- Ações

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base do Amazon Bedrock disponíveis.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base Bedrock disponíveis.

```
// FoundationModelWrapper encapsulates Amazon Bedrock actions used in the examples.
// It contains a Bedrock service client that is used to perform foundation model
 actions.
type FoundationModelWrapper struct {
 BedrockClient *bedrock.Client
}



// ListPolicies lists Bedrock foundation models that you can use.
func (wrapper FoundationModelWrapper) ListFoundationModels()
 ([]types.FoundationModelSummary, error) {

    var models []types.FoundationModelSummary

    result, err := wrapper.BedrockClient.ListFoundationModels(context.TODO(),
 &bedrock.ListFoundationModelsInput{})

    if err != nil {
        log.Printf("Couldn't list foundation models. Here's why: %v\n", err)
    } else {
        models = result.ModelSummaries
    }
    return models, err
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Go da API.

Exemplos do Amazon Bedrock Runtime usando o SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Go V2 com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Bedrock

O exemplo de código a seguir mostra como começar a usar o Amazon Bedrock.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "encoding/json"
 "flag"
 "fmt"
 "log"
 "os"
 "strings"

 "github.com/aws/aws-sdk-go-v2/aws"
```

```
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/bedrockruntime"
)

// Each model provider defines their own individual request and response formats.
// For the format, ranges, and default values for the different models, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters.html

type ClaudeRequest struct {
 Prompt            string `json:"prompt"`
 MaxTokensToSample int    `json:"max_tokens_to_sample"`
 // Omitting optional request parameters
}

type ClaudeResponse struct {
 Completion string `json:"completion"`
}

// main uses the AWS SDK for Go (v2) to create an Amazon Bedrock Runtime client
// and invokes Anthropic Claude 2 inside your account and the chosen region.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {

 region := flag.String("region", "us-east-1", "The AWS region")
 flag.Parse()

 fmt.Printf("Using AWS region: %s\n", *region)

 sdkConfig, err := config.LoadDefaultConfig(context.Background(),
 config.WithRegion(*region))
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }

 client := bedrockruntime.NewFromConfig(sdkConfig)

 modelId := "anthropic.claude-v2"

 prompt := "Hello, how are you today?"
```

```
 // Anthropic Claude requires you to enclose the prompt as follows:
 prefix := "Human: "
 postfix := "\n\nAssistant:"
 wrappedPrompt := prefix + prompt + postfix

 request := ClaudeRequest{
  Prompt:            wrappedPrompt,
  MaxTokensToSample: 200,
 }

 body, err := json.Marshal(request)
 if err != nil {
  log.Panicln("Couldn't marshal the request: ", err)
 }

 result, err := client.InvokeModel(context.Background(),
 &bedrockruntime.InvokeModelInput{
  ModelId:     aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body:        body,
 })

 if err != nil {
  errMsg := err.Error()
  if strings.Contains(errMsg, "no such host") {
   fmt.Printf("Error: The Bedrock service is not available in the selected
 region. Please double-check the service availability for your region at https://
aws.amazon.com/about-aws/global-infrastructure/regional-product-services/.\n")
  } else if strings.Contains(errMsg, "Could not resolve the foundation model") {
   fmt.Printf("Error: Could not resolve the foundation model from model identifier:
 \"%v\". Please verify that the requested model exists and is accessible within the
 specified region.\n", modelId)
  } else {
   fmt.Printf("Error: Couldn't invoke Anthropic Claude. Here's why: %v\n", err)
  }
  os.Exit(1)
 }

 var response ClaudeResponse

 err = json.Unmarshal(result.Body, &response)

 if err != nil {
  log.Fatal("failed to unmarshal", err)
```

```
 }
 fmt.Println("Prompt:\n", prompt)
 fmt.Println("Response from Anthropic Claude:\n", response.Completion)
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários

Ações

Geração de imagens com o Image Generator G1 do Amazon Titan

O exemplo de código a seguir mostra como invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
type TitanImageRequest struct {
    TaskType              string                `json:"taskType"`
    TextToImageParams     TextToImageParams     `json:"textToImageParams"`
    ImageGenerationConfig ImageGenerationConfig `json:"imageGenerationConfig"`
}
type TextToImageParams struct {
    Text string `json:"text"`
}
type ImageGenerationConfig struct {
```

```
    NumberOfImages int     `json:"numberOfImages"`
    Quality        string  `json:"quality"`
    CfgScale       float64 `json:"cfgScale"`
    Height         int     `json:"height"`
    Width          int     `json:"width"`
    Seed           int64   `json:"seed"`
}

type TitanImageResponse struct {
    Images []string `json:"images"`
}

// Invokes the Titan Image model to create an image using the input provided
// in the request body.
func (wrapper InvokeModelWrapper) InvokeTitanImage(prompt string, seed int64)
 (string, error) {
    modelId := "amazon.titan-image-generator-v1"

    body, err := json.Marshal(TitanImageRequest {
        TaskType: "TEXT_IMAGE",
        TextToImageParams: TextToImageParams {
            Text: prompt,
        },
        ImageGenerationConfig: ImageGenerationConfig {
            NumberOfImages: 1,
            Quality: "standard",
            CfgScale: 8.0,
            Height: 512,
            Width: 512,
            Seed: seed,
        },
    })

    if err != nil { log.Fatal("failed to marshal", err) }

    output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
        ModelId: aws.String(modelId),
        ContentType: aws.String("application/json"),
        Body: body,
    })

    if err != nil { ProcessError(err, modelId) }
```

```
    var response TitanImageResponse
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

    base64ImageData := response.Images[0]

    return base64ImageData, nil

}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for AI21 Labs Jurassic-2, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html

type Jurassic2Request struct {
 Prompt      string   `json:"prompt"`
 MaxTokens   int      `json:"maxTokens,omitempty"`
 Temperature float64  `json:"temperature,omitempty"`
}
```

```
type Jurassic2Response struct {
    Completions []Completion `json:"completions"`
}
type Completion struct {
    Data Data `json:"data"`
}
type Data struct {
    Text string `json:"text"`
}

// Invokes AI21 Labs Jurassic-2 on Amazon Bedrock to run an inference using the
 input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeJurassic2(prompt string) (string, error) {
    modelId := "ai21.j2-mid-v1"

 body, err := json.Marshal(Jurassic2Request {
  Prompt:            prompt,
  MaxTokens:      200,
  Temperature:       0.5,
 })

 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
 })

 if err != nil { ProcessError(err, modelId) }

 var response Jurassic2Response
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

 return response.Completions[0].Data.Text, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for Anthropic Claude, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-claude.html

type ClaudeRequest struct {
 Prompt            string   `json:"prompt"`
 MaxTokensToSample int      `json:"max_tokens_to_sample"`
 Temperature       float64  `json:"temperature,omitempty"`
 StopSequences     []string `json:"stop_sequences,omitempty"`
}

type ClaudeResponse struct {
 Completion string `json:"completion"`
}

// Invokes Anthropic Claude on Amazon Bedrock to run an inference using the input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeClaude(prompt string) (string, error) {
    modelId := "anthropic.claude-v2"

 // Anthropic Claude requires enclosing the prompt as follows:
 enclosedPrompt := "Human: " + prompt + "\n\nAssistant:"

 body, err := json.Marshal(ClaudeRequest {
  Prompt:            enclosedPrompt,
  MaxTokensToSample: 200,
  Temperature:       0.5,
```

```
  StopSequences:     []string{"\n\nHuman:"},
 })

 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
 })

 if err != nil { ProcessError(err, modelId) }

 var response ClaudeResponse
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }

 return response.Completion, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Geração de texto com Claude 2 da Anthropic com fluxo de resposta

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
// Each model provider defines their own individual request and response formats.
```

```
// For the format, ranges, and default values for the different models, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters.html

type Request struct {
 Prompt            string  `json:"prompt"`
 MaxTokensToSample int     `json:"max_tokens_to_sample"`
 Temperature       float64 `json:"temperature,omitempty"`
}

type Response struct {
 Completion string `json:"completion"`
}

// Invokes Anthropic Claude on Amazon Bedrock to run an inference and asynchronously
// process the response stream.

func (wrapper InvokeModelWithResponseStreamWrapper)
 InvokeModelWithResponseStream(prompt string) (string, error) {

 modelId := "anthropic.claude-v2"

 // Anthropic Claude requires you to enclose the prompt as follows:
 prefix := "Human: "
 postfix := "\n\nAssistant:"
 prompt = prefix + prompt + postfix

 request := ClaudeRequest{
  Prompt:            prompt,
  MaxTokensToSample: 200,
  Temperature:       0.5,
  StopSequences:     []string{"\n\nHuman:"},
 }

 body, err := json.Marshal(request)
 if err != nil {
  log.Panicln("Couldn't marshal the request: ", err)
 }

 output, err :=
 wrapper.BedrockRuntimeClient.InvokeModelWithResponseStream(context.Background(),
 &bedrockruntime.InvokeModelWithResponseStreamInput{
  Body:        body,
  ModelId:     aws.String(modelId),
  ContentType: aws.String("application/json"),
```

```
 })

 if err != nil {
  errMsg := err.Error()
  if strings.Contains(errMsg, "no such host") {
   log.Printf("The Bedrock service is not available in the selected region. Please
 double-check the service availability for your region at https://aws.amazon.com/
about-aws/global-infrastructure/regional-product-services/.\n")
  } else if strings.Contains(errMsg, "Could not resolve the foundation model") {
   log.Printf("Could not resolve the foundation model from model identifier: \"%v
\". Please verify that the requested model exists and is accessible within the
 specified region.\n", modelId)
  } else {
   log.Printf("Couldn't invoke Anthropic Claude. Here's why: %v\n", err)
  }
 }

 resp, err := processStreamingOutput(output, func(ctx context.Context, part []byte)
 error {
  fmt.Print(string(part))
  return nil
 })

 if err != nil {
  log.Fatal("streaming output processing error: ", err)
 }

 return resp.Completion, nil

}

type StreamingOutputHandler func(ctx context.Context, part []byte) error

func processStreamingOutput(output
 *bedrockruntime.InvokeModelWithResponseStreamOutput, handler
 StreamingOutputHandler) (Response, error) {

 var combinedResult string
 resp := Response{}

 for event := range output.GetStream().Events() {
  switch v := event.(type) {
  case *types.ResponseStreamMemberChunk:
```

```
    //fmt.Println("payload", string(v.Value.Bytes))

    var resp Response
    err := json.NewDecoder(bytes.NewReader(v.Value.Bytes)).Decode(&resp)
    if err != nil {
     return resp, err
    }

    err = handler(context.Background(), []byte(resp.Completion))
    if err != nil {
     return resp, err
    }

    combinedResult += resp.Completion

   case *types.UnknownUnionMember:
    fmt.Println("unknown tag:", v.Tag)

   default:
    fmt.Println("union is nil or unknown type")
   }
  }

  resp.Completion = combinedResult

  return resp, nil
}
```

- Para obter detalhes da API, consulte InvokeModelWithResponseStreama Referência AWS SDK for Go da API.

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
// Each model provider has their own individual request and response formats.
// For the format, ranges, and default values for Meta Llama 2 Chat, refer to:
// https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-meta.html

type Llama2Request struct {
 Prompt            string   `json:"prompt"`
 MaxGenLength    int      `json:"max_gen_len,omitempty"`
 Temperature       float64  `json:"temperature,omitempty"`
}

type Llama2Response struct {
 Generation string `json:"generation"`
}

// Invokes Meta Llama 2 Chat on Amazon Bedrock to run an inference using the input
// provided in the request body.
func (wrapper InvokeModelWrapper) InvokeLlama2(prompt string) (string, error) {
    modelId := "meta.llama2-13b-chat-v1"

 body, err := json.Marshal(Llama2Request {
  Prompt:            prompt,
  MaxGenLength:    512,
  Temperature:       0.5,
 })

 if err != nil { log.Fatal("failed to marshal", err) }

 output, err := wrapper.BedrockRuntimeClient.InvokeModel(context.TODO(),
 &bedrockruntime.InvokeModelInput{
  ModelId: aws.String(modelId),
  ContentType: aws.String("application/json"),
  Body: body,
```

```
 })

 if err != nil { ProcessError(err, modelId) }

 var response Llama2Response
    if err := json.Unmarshal(output.Body, &response); err != nil {
        log.Fatal("failed to unmarshal", err)
    }



 return response.Generation, nil
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Go da API.

Cenários

Invocar vários modelos de base no Amazon Bedrock

O exemplo de código a seguir mostra como invocar vários modelos de base no Amazon Bedrock.

- Gere texto com Claude da Anthropic.
- Gere texto com o AI21 Labs Jurassic-2.
- Gere texto com o Chat Llama 2 da Meta.
- Processe o fluxo de resposta do Claude da Anthropic de forma assíncrona.
- Gere uma imagem com o Amazon Titan Image Generator.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque vários modelos de base no Amazon Bedrock.

```
// InvokeModelsScenario demonstrates how to use the Amazon Bedrock Runtime client
// to invoke various foundation models for text and image generation
//
// 1. Generate text with Anthropic Claude 2
// 2. Generate text with AI21 Labs Jurassic-2
// 3. Generate text with Meta Llama 2 Chat
// 4. Generate text and asynchronously process the response stream with Anthropic
 Claude 2
// 5. Generate and image with the Amazon Titan image generation model
type InvokeModelsScenario struct {
 sdkConfig             aws.Config
 invokeModelWrapper    actions.InvokeModelWrapper
 responseStreamWrapper actions.InvokeModelWithResponseStreamWrapper
 questioner            demotools.IQuestioner
}

// NewInvokeModelsScenario constructs an InvokeModelsScenario instance from a
 configuration.
// It uses the specified config to get a Bedrock Runtime client and create wrappers
 for the
// actions used in the scenario.
func NewInvokeModelsScenario(sdkConfig aws.Config, questioner demotools.IQuestioner)
 InvokeModelsScenario {
 client := bedrockruntime.NewFromConfig(sdkConfig)
 return InvokeModelsScenario{
  sdkConfig:             sdkConfig,
  invokeModelWrapper:    actions.InvokeModelWrapper{BedrockRuntimeClient: client},
  responseStreamWrapper:
 actions.InvokeModelWithResponseStreamWrapper{BedrockRuntimeClient: client},
  questioner:            questioner,
 }
}

// Runs the interactive scenario.
func (scenario InvokeModelsScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo: %v\n", r)
  }
 }()

 log.Println(strings.Repeat("=", 77))
 log.Println("Welcome to the Amazon Bedrock Runtime model invocation demo.")
 log.Println(strings.Repeat("=", 77))
```

```
 log.Printf("First, let's invoke a few large-language models using the synchronous
 client:\n\n")

 text2textPrompt := "In one paragraph, who are you?"

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Claude with prompt: %v\n", text2textPrompt)
 scenario.InvokeClaude(text2textPrompt)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Jurassic-2 with prompt: %v\n", text2textPrompt)
 scenario.InvokeJurassic2(text2textPrompt)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Llama2 with prompt: %v\n", text2textPrompt)
 scenario.InvokeLlama2(text2textPrompt)

 log.Println(strings.Repeat("=", 77))
 log.Printf("Now, let's invoke Claude with the asynchronous client and process the
 response stream:\n\n")

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Claude with prompt: %v\n", text2textPrompt)
 scenario.InvokeWithResponseStream(text2textPrompt)

 log.Println(strings.Repeat("=", 77))
 log.Printf("Now, let's create an image with the Amazon Titan image generation
 model:\n\n")

 text2ImagePrompt := "stylized picture of a cute old steampunk robot"
 seed := rand.Int63n(2147483648)

 log.Println(strings.Repeat("-", 77))
 log.Printf("Invoking Amazon Titan with prompt: %v\n", text2ImagePrompt)
 scenario.InvokeTitanImage(text2ImagePrompt, seed)

 log.Println(strings.Repeat("=", 77))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("=", 77))
}

func (scenario InvokeModelsScenario) InvokeClaude(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeClaude(prompt)
```

```
 if err != nil {
  panic(err)
 }
 log.Printf("\nClaude     : %v\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeJurassic2(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeJurassic2(prompt)
 if err != nil {
  panic(err)
 }
 log.Printf("\nJurassic-2 : %v\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeLlama2(prompt string) {
 completion, err := scenario.invokeModelWrapper.InvokeLlama2(prompt)
 if err != nil {
  panic(err)
 }
 log.Printf("\nLlama 2    : %v\n\n", strings.TrimSpace(completion))
}

func (scenario InvokeModelsScenario) InvokeWithResponseStream(prompt string) {
 log.Println("\nClaude with response stream:")
 _, err := scenario.responseStreamWrapper.InvokeModelWithResponseStream(prompt)
 if err != nil {
  panic(err)
 }
 log.Println()
}

func (scenario InvokeModelsScenario) InvokeTitanImage(prompt string, seed int64) {
 base64ImageData, err := scenario.invokeModelWrapper.InvokeTitanImage(prompt, seed)
 if err != nil {
  panic(err)
 }
 imagePath := saveImage(base64ImageData, "amazon.titan-image-generator-v1")
 fmt.Printf("The generated image has been saved to %s\n", imagePath)
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - InvokeModel
  - InvokeModelWithResponseStream

CloudWatch Exemplos de registros usando o SDK for Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Go V2 com CloudWatch registros.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Iniciar uma sessão Live Tail

O exemplo de código a seguir mostra como iniciar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

SDK for Go V2

Inclua os arquivos necessários.

```
import (
 "context"
 "log"
 "time"

 "github.com/aws/aws-sdk-go-v2/config"
```

```
 "github.com/aws/aws-sdk-go-v2/service/cloudwatchlogs"
 "github.com/aws/aws-sdk-go-v2/service/cloudwatchlogs/types"
)
```

Gerencie os eventos da sessão do Live Tail.

```
func handleEventStreamAsync(stream *cloudwatchlogs.StartLiveTailEventStream) {
 eventsChan := stream.Events()
 for {
  event := <-eventsChan
  switch e := event.(type) {
  case *types.StartLiveTailResponseStreamMemberSessionStart:
   log.Println("Received SessionStart event")
  case *types.StartLiveTailResponseStreamMemberSessionUpdate:
   for _, logEvent := range e.Value.SessionResults {
    log.Println(*logEvent.Message)
   }
  default:
   // Handle on-stream exceptions
   if err := stream.Err(); err != nil {
    log.Fatalf("Error occured during streaming: %v", err)
   } else if event == nil {
    log.Println("Stream is Closed")
    return
   } else {
    log.Fatalf("Unknown event type: %T", e)
   }
  }
 }
}
```

Inicie a sessão do Live Tail.

```
 cfg, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  panic("configuration error, " + err.Error())
 }
 client := cloudwatchlogs.NewFromConfig(cfg)

 request := &cloudwatchlogs.StartLiveTailInput{
  LogGroupIdentifiers:   logGroupIdentifiers,
```

```
 LogStreamNames:        logStreamNames,
 LogEventFilterPattern: logEventFilterPattern,
}

response, err := client.StartLiveTail(context.TODO(), request)
// Handle pre-stream Exceptions
if err != nil {
 log.Fatalf("Failed to start streaming: %v", err)
}

// Start a Goroutine to handle events over stream
stream := response.GetStream()
go handleEventStreamAsync(stream)
```

Interrompa a sessão do Live Tail após um período decorrido.

```
// Close the stream (which ends the session) after a timeout
time.Sleep(10 * time.Second)
stream.Close()
log.Println("Event stream closed")
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for Go da API.

Exemplos do DynamoDB usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// CreateMovieTable creates a DynamoDB table with a composite primary key defined as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
 var tableDesc *types.TableDescription
 table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
 &dynamodb.CreateTableInput{
  AttributeDefinitions: []types.AttributeDefinition{{
   AttributeName: aws.String("year"),
   AttributeType: types.ScalarAttributeTypeN,
  }, {
   AttributeName: aws.String("title"),
   AttributeType: types.ScalarAttributeTypeS,
```

```
  }},
  KeySchema: []types.KeySchemaElement{{
   AttributeName: aws.String("year"),
   KeyType:       types.KeyTypeHash,
  }, {
   AttributeName: aws.String("title"),
   KeyType:       types.KeyTypeRange,
  }},
  TableName: aws.String(basics.TableName),
  ProvisionedThroughput: &types.ProvisionedThroughput{
   ReadCapacityUnits:  aws.Int64(10),
   WriteCapacityUnits: aws.Int64(10),
  },
 })
 if err != nil {
  log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
 } else {
  waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
  err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
   TableName: aws.String(basics.TableName)}, 5*time.Minute)
  if err != nil {
   log.Printf("Wait for table exists failed. Here's why: %v\n", err)
  }
  tableDesc = table.TableDescription
 }
 return tableDesc, err
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Go da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
 _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
 &dynamodb.DeleteTableInput{
  TableName: aws.String(basics.TableName)})
 if err != nil {
  log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Go da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
```

```
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
 _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
 &dynamodb.DeleteItemInput{
  TableName: aws.String(basics.TableName), Key: movie.GetKey(),
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
```

```
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte DeleteItem a Referência AWS SDK for Go da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// GetMovie gets movie data from the DynamoDB table by using the primary composite
 key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
```

```
 movie := Movie{Title: title, Year: year}
 response, err := basics.DynamoDbClient.GetItem(context.TODO(),
 &dynamodb.GetItemInput{
  Key: movie.GetKey(), TableName: aws.String(basics.TableName),
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Item, &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}
```

```
// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Go da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
 exists := true
 _, err := basics.DynamoDbClient.DescribeTable(
  context.TODO(), &dynamodb.DescribeTableInput{TableName:
 aws.String(basics.TableName)},
 )
 if err != nil {
```

```
  var notFoundEx *types.ResourceNotFoundException
  if errors.As(err, &notFoundEx) {
   log.Printf("Table %v does not exist.\n", basics.TableName)
   err = nil
  } else {
   log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
 basics.TableName, err)
  }
  exists = false
 }
 return exists, err
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Go da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
```

```
 var tableNames []string
 var output *dynamodb.ListTablesOutput
 var err error
 tablePaginator := dynamodb.NewListTablesPaginator(basics.DynamoDbClient,
 &dynamodb.ListTablesInput{})
 for tablePaginator.HasMorePages() {
  output, err = tablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't list tables. Here's why: %v\n", err)
   break
  } else {
   tableNames = append(tableNames, output.TableNames...)
  }
 }
 return tableNames, err
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Go da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}
```

```
// AddMovie adds a movie the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
 item, err := attributevalue.MarshalMap(movie)
 if err != nil {
  panic(err)
 }
 _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
  TableName: aws.String(basics.TableName), Item: item,
 })
 if err != nil {
  log.Printf("Couldn't add item to table. Here's why: %v\n", err)
 }
 return err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                `dynamodbav:"title"`
 Year  int                   `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}
```

```
// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte PutItem a Referência AWS SDK for Go da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// Query gets all movies in the DynamoDB table that were released in the specified
 year.
// The function uses the `expression` package to build the key condition expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
 var err error
 var response *dynamodb.QueryOutput
 var movies []Movie
```

```
 keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
 expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
 if err != nil {
  log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
 } else {
  queryPaginator := dynamodb.NewQueryPaginator(basics.DynamoDbClient,
 &dynamodb.QueryInput{
   TableName:                 aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   KeyConditionExpression:    expr.KeyCondition(),
  })
  for queryPaginator.HasMorePages() {
   response, err = queryPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
 releaseYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
```

```
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Go.

Executar uma instrução PartiQL

Os exemplos de código a seguir mostram como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use uma instrução INSERT para adicionar um item.

```
// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
func (runner PartiQLRunner) AddMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
 }
 return err
}
```

Use uma instrução SELECT para obter um item.

```
// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB table
 by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
 var movie Movie
 params, err := attributevalue.MarshalList([]interface{}{title, year})
 if err != nil {
  panic(err)
 }
 response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
```

```
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Items[0], &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}
```

Use uma instrução SELECT para obter uma lista de itens e projetar os resultados.

```
// GetAllMovies runs a PartiQL SELECT statement to get all movies from the DynamoDB
 table.
// pageSize is not typically required and is used to show how to paginate the
 results.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies(pageSize int32) ([]map[string]interface{},
 error) {
 var output []map[string]interface{}
 var response *dynamodb.ExecuteStatementOutput
 var err error
 var nextToken *string
 for moreData := true; moreData; {
  response, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
   Statement: aws.String(
    fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
   Limit:     aws.Int32(pageSize),
   NextToken: nextToken,
  })
  if err != nil {
   log.Printf("Couldn't get movies. Here's why: %v\n", err)
   moreData = false
  } else {
   var pageOutput []map[string]interface{}
   err = attributevalue.UnmarshalListOfMaps(response.Items, &pageOutput)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
```

```
    log.Printf("Got a page of length %v.\n", len(response.Items))
    output = append(output, pageOutput...)
   }
   nextToken = response.NextToken
   moreData = nextToken != nil
  }
 }
 return output, err
}
```

Use uma instrução UPDATE para atualizar um item.

```
// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
 params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
 }
 return err
}
```

Use uma instrução DELETE para excluir um item.

```
// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the DynamoDB
 table.
```

```
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
```

```
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Go da API.

Executar lotes de instruções PartiQL

Os exemplos de código a seguir mostram como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

Use lotes de instruções INSERT para adicionar itens.

```
// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies to
 the
// DynamoDB table.
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
```

```
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(fmt.Sprintf(
    "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n", err)
 }
 return err
}
```

Use lotes de instruções SELECT para obter itens.

```
// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies
 from
// the DynamoDB table by title and year.
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
   Parameters: params,
  }
 }
```

```
 output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 var outMovies []Movie
 if err != nil {
  log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
 } else {
  for _, response := range output.Responses {
   var movie Movie
   err = attributevalue.UnmarshalMap(response.Item, &movie)
   if err != nil {
    log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
   } else {
    outMovies = append(outMovies, movie)
   }
  }
 }
 return outMovies, err
}
```

Use lotes de instruções UPDATE para atualizar itens.

```
// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the rating
 of
// multiple movies that already exist in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64)
 error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{ratings[index],
 movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
```

```
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
 }
 return err
}
```

Use lotes de instruções DELETE para excluir itens.

```
// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
 movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
 }
 return err
```

```
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Go da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// Scan gets all movies in the DynamoDB table that were released in a range of years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
 var movies []Movie
 var err error
 var response *dynamodb.ScanOutput
 filtEx := expression.Name("year").Between(expression.Value(startYear),
 expression.Value(endYear))
 projEx := expression.NamesList(
  expression.Name("year"), expression.Name("title"), expression.Name("info.rating"))
 expr, err :=
 expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
 if err != nil {
  log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
 } else {
  scanPaginator := dynamodb.NewScanPaginator(basics.DynamoDbClient,
 &dynamodb.ScanInput{
   TableName:                 aws.String(basics.TableName),
```

```
    ExpressionAttributeNames:  expr.Names(),
    ExpressionAttributeValues: expr.Values(),
    FilterExpression:          expr.Filter(),
    ProjectionExpression:      expr.Projection(),
   })
   for scanPaginator.HasMorePages() {
    response, err = scanPaginator.NextPage(context.TODO())
    if err != nil {
     log.Printf("Couldn't scan for movies released between %v and %v. Here's why: %v
\n",
      startYear, endYear, err)
     break
    } else {
     var moviePage []Movie
     err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
     if err != nil {
      log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
      break
     } else {
      movies = append(movies, moviePage...)
     }
    }
   }
  }
  return movies, err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
```

```
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Go.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}
```

```
// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
 (map[string]map[string]interface{}, error) {
 var err error
 var response *dynamodb.UpdateItemOutput
 var attributeMap map[string]map[string]interface{}
 update := expression.Set(expression.Name("info.rating"),
 expression.Value(movie.Info["rating"]))
 update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
 expr, err := expression.NewBuilder().WithUpdate(update).Build()
 if err != nil {
  log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
 } else {
  response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
 &dynamodb.UpdateItemInput{
   TableName:                aws.String(basics.TableName),
   Key:                      movie.GetKey(),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   UpdateExpression:         expr.Update(),
   ReturnValues:             types.ReturnValueUpdatedNew,
  })
  if err != nil {
   log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
  } else {
   err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
   if err != nil {
    log.Printf("Couldn't unmarshall update response. Here's why: %v\n", err)
   }
  }
 }
 return attributeMap, err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
```

```
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Go da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int, error)
 {
 var err error
 var item map[string]types.AttributeValue
 written := 0
 batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
 start := 0
 end := start + batchSize
 for start < maxMovies && start < len(movies) {
  var writeReqs []types.WriteRequest
  if end > len(movies) {
   end = len(movies)
  }
  for _, movie := range movies[start:end] {
   item, err = attributevalue.MarshalMap(movie)
   if err != nil {
    log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
 movie.Title, err)
   } else {
    writeReqs = append(
     writeReqs,
     types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
    )
   }
  }
  _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
 &dynamodb.BatchWriteItemInput{
   RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
  if err != nil {
```

```
   log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
 basics.TableName, err)
  } else {
   written += len(writeReqs)
  }
  start = end
  end += batchSize
 }

 return written, err
}



// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
```

```
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for Go da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo para criar a tabela e executar ações nela.

```
// RunMovieScenario is an interactive example that shows you how to use the AWS SDK
 for Go
// to create and use an Amazon DynamoDB table that stores data about movies.
//
//   1. Create a table that can hold movie data.
//   2. Put, get, and update a single movie in the table.
//   3. Write movie data to the table from a sample JSON file.
//   4. Query for movies that were released in a given year.
//   5. Scan for movies that were released in a range of years.
```

```
//   6. Delete a movie from the table.
//   7. Delete the table.
//
// This example creates a DynamoDB service client from the specified sdkConfig so
 that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
//
// The specified movie sampler is used to get sample data from a URL that is loaded
// into the named table.
func RunMovieScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner, tableName string,
 movieSampler actions.IMovieSampler) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon DynamoDB getting started demo.")
 log.Println(strings.Repeat("-", 88))

 tableBasics := actions.TableBasics{TableName: tableName,
  DynamoDbClient: dynamodb.NewFromConfig(sdkConfig)}

 exists, err := tableBasics.TableExists()
 if err != nil {
  panic(err)
 }
 if !exists {
  log.Printf("Creating table %v...\n", tableName)
  _, err = tableBasics.CreateMovieTable()
  if err != nil {
   panic(err)
  } else {
   log.Printf("Created table %v.\n", tableName)
  }
 } else {
  log.Printf("Table %v already exists.\n", tableName)
 }
```

```
var customMovie actions.Movie
customMovie.Title = questioner.Ask("Enter a movie title to add to the table:",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
customMovie.Year = questioner.AskInt("What year was it released?",
 []demotools.IAnswerValidator{demotools.NotEmpty{}, demotools.InIntRange{
  Lower: 1900, Upper: 2030}})
customMovie.Info = map[string]interface{}{}
customMovie.Info["rating"] = questioner.AskFloat64(
 "Enter a rating between 1 and 10:", []demotools.IAnswerValidator{
  demotools.NotEmpty{}, demotools.InFloatRange{Lower: 1, Upper: 10}})
customMovie.Info["plot"] = questioner.Ask("What's the plot? ",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
err = tableBasics.AddMovie(customMovie)
if err == nil {
 log.Printf("Added %v to the movie table.\n", customMovie.Title)
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's update your movie. You previously rated it %v.\n",
customMovie.Info["rating"])
customMovie.Info["rating"] = questioner.AskFloat64(
 "What new rating would you give it?", []demotools.IAnswerValidator{
  demotools.NotEmpty{}, demotools.InFloatRange{Lower: 1, Upper: 10}})
log.Printf("You summarized the plot as '%v'.\n", customMovie.Info["plot"])
customMovie.Info["plot"] = questioner.Ask("What would you say now?",
 []demotools.IAnswerValidator{demotools.NotEmpty{}})
attributes, err := tableBasics.UpdateMovie(customMovie)
if err == nil {
 log.Printf("Updated %v with new values.\n", customMovie.Title)
 for _, attVal := range attributes {
  for valKey, val := range attVal {
   log.Printf("\t%v: %v\n", valKey, val)
  }
 }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Getting movie data from %v and adding 250 movies to the table...\n",
 movieSampler.GetURL())
movies := movieSampler.GetSampleMovies()
written, err := tableBasics.AddMovieBatch(movies, 250)
if err != nil {
 panic(err)
```

```
} else {
 log.Printf("Added %v movies to the table.\n", written)
}

show := 10
if show > written {
 show = written
}
log.Printf("The first %v movies in the table are:", show)
for index, movie := range movies[:show] {
 log.Printf("\t%v. %v\n", index+1, movie.Title)
}
movieIndex := questioner.AskInt(
 "Enter the number of a movie to get info about it: ",
[]demotools.IAnswerValidator{
  demotools.InIntRange{Lower: 1, Upper: show}},
)
movie, err := tableBasics.GetMovie(movies[movieIndex-1].Title,
movies[movieIndex-1].Year)
if err == nil {
 log.Println(movie)
}
log.Println(strings.Repeat("-", 88))

log.Println("Let's get a list of movies released in a given year.")
releaseYear := questioner.AskInt("Enter a year between 1972 and 2018: ",
 []demotools.IAnswerValidator{demotools.InIntRange{Lower: 1972, Upper: 2018}},
)
releases, err := tableBasics.Query(releaseYear)
if err == nil {
 if len(releases) == 0 {
  log.Printf("I couldn't find any movies released in %v!\n", releaseYear)
 } else {
  for _, movie = range releases {
   log.Println(movie)
  }
 }
}
log.Println(strings.Repeat("-", 88))

log.Println("Now let's scan for movies released in a range of years.")
startYear := questioner.AskInt("Enter a year: ", []demotools.IAnswerValidator{
 demotools.InIntRange{Lower: 1972, Upper: 2018}})
endYear := questioner.AskInt("Enter another year: ", []demotools.IAnswerValidator{
```

```
 demotools.InIntRange{Lower: 1972, Upper: 2018}})
releases, err = tableBasics.Scan(startYear, endYear)
if err == nil {
 if len(releases) == 0 {
  log.Printf("I couldn't find any movies released between %v and %v!\n", startYear,
endYear)
 } else {
  log.Printf("Found %v movies. In this list, the plot is <nil> because "+
   "we used a projection expression when scanning for items to return only "+
   "the title, year, and rating.\n", len(releases))
  for _, movie = range releases {
   log.Println(movie)
  }
 }
}
log.Println(strings.Repeat("-", 88))

var tables []string
if questioner.AskBool("Do you want to list all of your tables? (y/n) ", "y") {
 tables, err = tableBasics.ListTables()
 if err == nil {
  log.Printf("Found %v tables:", len(tables))
  for _, table := range tables {
   log.Printf("\t%v", table)
  }
 }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's remove your movie '%v'.\n", customMovie.Title)
if questioner.AskBool("Do you want to delete it from the table? (y/n) ", "y") {
 err = tableBasics.DeleteMovie(customMovie)
}
if err == nil {
 log.Printf("Deleted %v.\n", customMovie.Title)
}

if questioner.AskBool("Delete the table, too? (y/n)", "y") {
 err = tableBasics.DeleteTable()
} else {
 log.Println("Don't forget to delete the table when you're done or you might " +
  "incur charges on your account.")
}
if err == nil {
```

```
  log.Printf("Deleted table %v.\n", tableBasics.TableName)
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
```

```
}
```

Crie uma estrutura e métodos que chamem ações do DynamoDB.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
 examples.
// It contains a DynamoDB service client that is used to act on the specified table.
type TableBasics struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
 exists := true
 _, err := basics.DynamoDbClient.DescribeTable(
  context.TODO(), &dynamodb.DescribeTableInput{TableName:
 aws.String(basics.TableName)},
 )
 if err != nil {
  var notFoundEx *types.ResourceNotFoundException
  if errors.As(err, &notFoundEx) {
   log.Printf("Table %v does not exist.\n", basics.TableName)
   err = nil
  } else {
   log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
 basics.TableName, err)
  }
  exists = false
 }
 return exists, err
}



// CreateMovieTable creates a DynamoDB table with a composite primary key defined as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
```

```
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
 var tableDesc *types.TableDescription
 table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
 &dynamodb.CreateTableInput{
  AttributeDefinitions: []types.AttributeDefinition{{
   AttributeName: aws.String("year"),
   AttributeType: types.ScalarAttributeTypeN,
  }, {
   AttributeName: aws.String("title"),
   AttributeType: types.ScalarAttributeTypeS,
  }},
  KeySchema: []types.KeySchemaElement{{
   AttributeName: aws.String("year"),
   KeyType:       types.KeyTypeHash,
  }, {
   AttributeName: aws.String("title"),
   KeyType:       types.KeyTypeRange,
  }},
  TableName: aws.String(basics.TableName),
  ProvisionedThroughput: &types.ProvisionedThroughput{
   ReadCapacityUnits:  aws.Int64(10),
   WriteCapacityUnits: aws.Int64(10),
  },
 })
 if err != nil {
  log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
 } else {
  waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
  err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
   TableName: aws.String(basics.TableName)}, 5*time.Minute)
  if err != nil {
   log.Printf("Wait for table exists failed. Here's why: %v\n", err)
  }
  tableDesc = table.TableDescription
 }
 return tableDesc, err
}



// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
 var tableNames []string
```

```
 var output *dynamodb.ListTablesOutput
 var err error
 tablePaginator := dynamodb.NewListTablesPaginator(basics.DynamoDbClient,
 &dynamodb.ListTablesInput{})
 for tablePaginator.HasMorePages() {
  output, err = tablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't list tables. Here's why: %v\n", err)
   break
  } else {
   tableNames = append(tableNames, output.TableNames...)
  }
 }
 return tableNames, err
}



// AddMovie adds a movie the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
 item, err := attributevalue.MarshalMap(movie)
 if err != nil {
  panic(err)
 }
 _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
  TableName: aws.String(basics.TableName), Item: item,
 })
 if err != nil {
  log.Printf("Couldn't add item to table. Here's why: %v\n", err)
 }
 return err
}



// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
 (map[string]map[string]interface{}, error) {
 var err error
 var response *dynamodb.UpdateItemOutput
 var attributeMap map[string]map[string]interface{}
```

```
 update := expression.Set(expression.Name("info.rating"),
 expression.Value(movie.Info["rating"]))
 update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
 expr, err := expression.NewBuilder().WithUpdate(update).Build()
 if err != nil {
  log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
 } else {
  response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
 &dynamodb.UpdateItemInput{
   TableName:                aws.String(basics.TableName),
   Key:                      movie.GetKey(),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   UpdateExpression:         expr.Update(),
   ReturnValues:             types.ReturnValueUpdatedNew,
  })
  if err != nil {
   log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
  } else {
   err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
   if err != nil {
    log.Printf("Couldn't unmarshall update response. Here's why: %v\n", err)
   }
  }
 }
 return attributeMap, err
}



// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int, error)
 {
 var err error
 var item map[string]types.AttributeValue
 written := 0
 batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
 start := 0
 end := start + batchSize
 for start < maxMovies && start < len(movies) {
  var writeReqs []types.WriteRequest
  if end > len(movies) {
```

```
    end = len(movies)
   }
   for _, movie := range movies[start:end] {
    item, err = attributevalue.MarshalMap(movie)
    if err != nil {
     log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
 movie.Title, err)
    } else {
     writeReqs = append(
      writeReqs,
      types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
     )
    }
   }
   _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
 &dynamodb.BatchWriteItemInput{
    RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
   if err != nil {
    log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
 basics.TableName, err)
   } else {
    written += len(writeReqs)
   }
   start = end
   end += batchSize
  }

  return written, err
}



// GetMovie gets movie data from the DynamoDB table by using the primary composite
 key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
 movie := Movie{Title: title, Year: year}
 response, err := basics.DynamoDbClient.GetItem(context.TODO(),
 &dynamodb.GetItemInput{
  Key: movie.GetKey(), TableName: aws.String(basics.TableName),
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
```

```
  err = attributevalue.UnmarshalMap(response.Item, &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}



// Query gets all movies in the DynamoDB table that were released in the specified
 year.
// The function uses the `expression` package to build the key condition expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
 var err error
 var response *dynamodb.QueryOutput
 var movies []Movie
 keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
 expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
 if err != nil {
  log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
 } else {
  queryPaginator := dynamodb.NewQueryPaginator(basics.DynamoDbClient,
 &dynamodb.QueryInput{
   TableName:                 aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   KeyConditionExpression:    expr.KeyCondition(),
  })
  for queryPaginator.HasMorePages() {
   response, err = queryPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
 releaseYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
```

```
    }
   }
  }
 }
 return movies, err
}



// Scan gets all movies in the DynamoDB table that were released in a range of years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
 var movies []Movie
 var err error
 var response *dynamodb.ScanOutput
 filtEx := expression.Name("year").Between(expression.Value(startYear),
 expression.Value(endYear))
 projEx := expression.NamesList(
  expression.Name("year"), expression.Name("title"), expression.Name("info.rating"))
 expr, err :=
 expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
 if err != nil {
  log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
 } else {
  scanPaginator := dynamodb.NewScanPaginator(basics.DynamoDbClient,
 &dynamodb.ScanInput{
   TableName:                aws.String(basics.TableName),
   ExpressionAttributeNames:  expr.Names(),
   ExpressionAttributeValues: expr.Values(),
   FilterExpression:         expr.Filter(),
   ProjectionExpression:     expr.Projection(),
  })
  for scanPaginator.HasMorePages() {
   response, err = scanPaginator.NextPage(context.TODO())
   if err != nil {
    log.Printf("Couldn't scan for movies released between %v and %v. Here's why: %v
\n",
     startYear, endYear, err)
    break
   } else {
    var moviePage []Movie
    err = attributevalue.UnmarshalListOfMaps(response.Items, &moviePage)
```

```
    if err != nil {
     log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
     break
    } else {
     movies = append(movies, moviePage...)
    }
   }
  }
 }
 return movies, err
}



// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
 _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
 &dynamodb.DeleteItemInput{
  TableName: aws.String(basics.TableName), Key: movie.GetKey(),
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}



// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
 _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
 &dynamodb.DeleteTableInput{
  TableName: aws.String(basics.TableName)})
 if err != nil {
  log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute lotes de consultas do PartiQL.

```
// RunPartiQLBatchScenario shows you how to use the AWS SDK for Go
```

```
// to run batches of PartiQL statements to query a table that stores data about
 movies.
//
//   - Use batches of PartiQL statements to add, get, update, and delete data for
//     individual movies.
//
// This example creates an Amazon DynamoDB service client from the specified
 sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLBatchScenario(sdkConfig aws.Config, tableName string) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon DynamoDB PartiQL batch demo.")
 log.Println(strings.Repeat("-", 88))

 tableBasics := actions.TableBasics{
  DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
  TableName:      tableName,
 }
 runner := actions.PartiQLRunner{
  DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
  TableName:      tableName,
 }

 exists, err := tableBasics.TableExists()
 if err != nil {
  panic(err)
 }
 if !exists {
  log.Printf("Creating table %v...\n", tableName)
  _, err = tableBasics.CreateMovieTable()
  if err != nil {
   panic(err)
  } else {
   log.Printf("Created table %v.\n", tableName)
  }
 } else {
```

```
 log.Printf("Table %v already exists.\n", tableName)
}
log.Println(strings.Repeat("-", 88))

currentYear, _, _ := time.Now().Date()
customMovies := []actions.Movie{{
 Title: "House PartiQL",
 Year:  currentYear - 5,
 Info: map[string]interface{}{
  "plot":   "Wacky high jinks result from querying a mysterious database.",
  "rating": 8.5}}, {
 Title: "House PartiQL 2",
 Year:  currentYear - 3,
 Info: map[string]interface{}{
  "plot":   "Moderate high jinks result from querying another mysterious
database.",
  "rating": 6.5}}, {
 Title: "House PartiQL 3",
 Year:  currentYear - 1,
 Info: map[string]interface{}{
  "plot":   "Tepid high jinks result from querying yet another mysterious
database.",
  "rating": 2.5},
},
}

log.Printf("Inserting a batch of movies into table '%v'.\n", tableName)
err = runner.AddMovieBatch(customMovies)
if err == nil {
 log.Printf("Added %v movies to the table.\n", len(customMovies))
}
log.Println(strings.Repeat("-", 88))

log.Println("Getting data for a batch of movies.")
movies, err := runner.GetMovieBatch(customMovies)
if err == nil {
 for _, movie := range movies {
  log.Println(movie)
 }
}
log.Println(strings.Repeat("-", 88))

newRatings := []float64{7.7, 4.4, 1.1}
log.Println("Updating a batch of movies with new ratings.")
```

```
 err = runner.UpdateMovieBatch(customMovies, newRatings)
 if err == nil {
  log.Printf("Updated %v movies with new ratings.\n", len(customMovies))
 }
 log.Println(strings.Repeat("-", 88))

 log.Println("Getting projected data from the table to verify our update.")
 log.Println("Using a page size of 2 to demonstrate paging.")
 projections, err := runner.GetAllMovies(2)
 if err == nil {
  log.Println("All movies:")
  for _, projection := range projections {
   log.Println(projection)
  }
 }
 log.Println(strings.Repeat("-", 88))

 log.Println("Deleting a batch of movies.")
 err = runner.DeleteMovieBatch(customMovies)
 if err == nil {
  log.Printf("Deleted %v movies.\n", len(customMovies))
 }

 err = tableBasics.DeleteTable()
 if err == nil {
  log.Printf("Deleted table %v.\n", tableBasics.TableName)
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
```

```
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

Crie uma estrutura e métodos que executem instruções partiQL.

```
// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
// PartiQL examples. It contains a DynamoDB service client that is used to act on
 the
// specified table.
type PartiQLRunner struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}
```

```
// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies to
 the
// DynamoDB table.
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(fmt.Sprintf(
    "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
 runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n", err)
 }
 return err
}



// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies
 from
// the DynamoDB table by title and year.
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
```

```
    Parameters: params,
   }
  }

  output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
  &dynamodb.BatchExecuteStatementInput{
   Statements: statementRequests,
  })
  var outMovies []Movie
  if err != nil {
   log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
  } else {
   for _, response := range output.Responses {
    var movie Movie
    err = attributevalue.UnmarshalMap(response.Item, &movie)
    if err != nil {
     log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
    } else {
     outMovies = append(outMovies, movie)
    }
   }
  }
  return outMovies, err
}



// GetAllMovies runs a PartiQL SELECT statement to get all movies from the DynamoDB
 table.
// pageSize is not typically required and is used to show how to paginate the
 results.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies(pageSize int32) ([]map[string]interface{},
 error) {
 var output []map[string]interface{}
 var response *dynamodb.ExecuteStatementOutput
 var err error
 var nextToken *string
 for moreData := true; moreData; {
  response, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
   Statement: aws.String(
    fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
   Limit:     aws.Int32(pageSize),
```

```
    NextToken: nextToken,
   })
   if err != nil {
    log.Printf("Couldn't get movies. Here's why: %v\n", err)
    moreData = false
   } else {
    var pageOutput []map[string]interface{}
    err = attributevalue.UnmarshalListOfMaps(response.Items, &pageOutput)
    if err != nil {
     log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
    } else {
     log.Printf("Got a page of length %v.\n", len(response.Items))
     output = append(output, pageOutput...)
    }
    nextToken = response.NextToken
    moreData = nextToken != nil
   }
  }
  return output, err
}



// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the rating
 of
// multiple movies that already exist in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64)
 error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{ratings[index],
 movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
 runner.TableName)),
   Parameters: params,
  }
 }
```

```
 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
 }
 return err
}



// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
 movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
 statementRequests := make([]types.BatchStatementRequest, len(movies))
 for index, movie := range movies {
  params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
  if err != nil {
   panic(err)
  }
  statementRequests[index] = types.BatchStatementRequest{
   Statement: aws.String(
    fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
   Parameters: params,
  }
 }

 _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
 &dynamodb.BatchExecuteStatementInput{
  Statements: statementRequests,
 })
 if err != nil {
  log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
 }
 return err
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Go da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
// RunPartiQLSingleScenario shows you how to use the AWS SDK for Go
// to use PartiQL to query a table that stores data about movies.
//
// * Use PartiQL statements to add, get, update, and delete data for individual
 movies.
//
// This example creates an Amazon DynamoDB service client from the specified
 sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLSingleScenario(sdkConfig aws.Config, tableName string) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Printf("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon DynamoDB PartiQL single action demo.")
 log.Println(strings.Repeat("-", 88))
```

```
tableBasics := actions.TableBasics{
 DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
 TableName:      tableName,
}
runner := actions.PartiQLRunner{
 DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
 TableName:      tableName,
}

exists, err := tableBasics.TableExists()
if err != nil {
 panic(err)
}
if !exists {
 log.Printf("Creating table %v...\n", tableName)
 _, err = tableBasics.CreateMovieTable()
 if err != nil {
  panic(err)
 } else {
  log.Printf("Created table %v.\n", tableName)
 }
} else {
 log.Printf("Table %v already exists.\n", tableName)
}
log.Println(strings.Repeat("-", 88))

currentYear, _, _ := time.Now().Date()
customMovie := actions.Movie{
 Title: "24 Hour PartiQL People",
 Year:  currentYear,
 Info: map[string]interface{}{
  "plot":   "A group of data developers discover a new query language they can't
stop using.",
  "rating": 9.9,
 },
}

log.Printf("Inserting movie '%v' released in %v.", customMovie.Title,
customMovie.Year)
err = runner.AddMovie(customMovie)
if err == nil {
 log.Printf("Added %v to the movie table.\n", customMovie.Title)
}
```

```
 log.Println(strings.Repeat("-", 88))

 log.Printf("Getting data for movie '%v' released in %v.", customMovie.Title,
 customMovie.Year)
 movie, err := runner.GetMovie(customMovie.Title, customMovie.Year)
 if err == nil {
  log.Println(movie)
 }
 log.Println(strings.Repeat("-", 88))

 newRating := 6.6
 log.Printf("Updating movie '%v' with a rating of %v.", customMovie.Title,
 newRating)
 err = runner.UpdateMovie(customMovie, newRating)
 if err == nil {
  log.Printf("Updated %v with a new rating.\n", customMovie.Title)
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Getting data again to verify the update.")
 movie, err = runner.GetMovie(customMovie.Title, customMovie.Year)
 if err == nil {
  log.Println(movie)
 }
 log.Println(strings.Repeat("-", 88))

 log.Printf("Deleting movie '%v'.\n", customMovie.Title)
 err = runner.DeleteMovie(customMovie)
 if err == nil {
  log.Printf("Deleted %v.\n", customMovie.Title)
 }

 err = tableBasics.DeleteTable()
 if err == nil {
  log.Printf("Deleted table %v.\n", tableBasics.TableName)
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura de filme usada neste exemplo.

```
// Movie encapsulates data about a movie. Title and Year are the composite primary
 key
// of the movie in Amazon DynamoDB. Title is the sort key, Year is the partition
 key,
// and Info is additional data.
type Movie struct {
 Title string                 `dynamodbav:"title"`
 Year  int                    `dynamodbav:"year"`
 Info  map[string]interface{} `dynamodbav:"info"`
}

// GetKey returns the composite primary key of the movie in a format that can be
// sent to DynamoDB.
func (movie Movie) GetKey() map[string]types.AttributeValue {
 title, err := attributevalue.Marshal(movie.Title)
 if err != nil {
  panic(err)
 }
 year, err := attributevalue.Marshal(movie.Year)
 if err != nil {
  panic(err)
 }
 return map[string]types.AttributeValue{"title": title, "year": year}
}

// String returns the title, year, rating, and plot of a movie, formatted for the
 example.
func (movie Movie) String() string {
 return fmt.Sprintf("%v\n\tReleased: %v\n\tRating: %v\n\tPlot: %v\n",
  movie.Title, movie.Year, movie.Info["rating"], movie.Info["plot"])
}
```

Crie uma estrutura e métodos que executem instruções partiQL.

```
// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
// PartiQL examples. It contains a DynamoDB service client that is used to act on
 the
```

```
// specified table.
type PartiQLRunner struct {
 DynamoDbClient *dynamodb.Client
 TableName      string
}



// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
func (runner PartiQLRunner) AddMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
 movie.Info})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
 }
 return err
}



// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB table
 by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
 var movie Movie
 params, err := attributevalue.MarshalList([]interface{}{title, year})
 if err != nil {
  panic(err)
 }
 response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
```

```
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
 } else {
  err = attributevalue.UnmarshalMap(response.Items[0], &movie)
  if err != nil {
   log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
  }
 }
 return movie, err
}



// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
 params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
 movie.Year})
 if err != nil {
  panic(err)
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
 }
 return err
}



// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the DynamoDB
 table.
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
 params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
 if err != nil {
  panic(err)
```

```
 }
 _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
 &dynamodb.ExecuteStatementInput{
  Statement: aws.String(
   fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
    runner.TableName)),
  Parameters: params,
 })
 if err != nil {
  log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Go da API.

Exemplos do IAM usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/iam"
)

// main uses the AWS SDK for Go (v2) to create an AWS Identity and Access Management
 (IAM)
// client and list up to 10 policies in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 iamClient := iam.NewFromConfig(sdkConfig)
 const maxPols = 10
 fmt.Printf("Let's list up to %v policies for your account.\n", maxPols)
 result, err := iamClient.ListPolicies(context.TODO(), &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPols),
 })
 if err != nil {
  fmt.Printf("Couldn't list policies for your account. Here's why: %v\n", err)
  return
```

```
 }
 if len(result.Policies) == 0 {
  fmt.Println("You don't have any policies!")
 } else {
  for _, policy := range result.Policies {
   fmt.Printf("\t%v\n", *policy.PolicyName)
  }
 }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}
```

```
// AttachRolePolicy attaches a policy to a role.
func (wrapper RoleWrapper) AttachRolePolicy(policyArn string, roleName string) error
 {
 _, err := wrapper.IamClient.AttachRolePolicy(context.TODO(),
 &iam.AttachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't attach policy %v to role %v. Here's why: %v\n", policyArn,
 roleName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Go da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}
```

```
// CreatePolicy creates a policy that grants a list of actions to the specified
 resource.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper PolicyWrapper) CreatePolicy(policyName string, actions []string,
  resourceArn string) (*types.Policy, error) {
 var policy *types.Policy
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(resourceArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n",
 resourceArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreatePolicy(context.TODO(),
 &iam.CreatePolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
 })
 if err != nil {
  log.Printf("Couldn't create policy %v. Here's why: %v\n", policyName, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Go da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// CreateRole creates a role that trusts a specified user. The trusted user can
 assume
// the role to acquire its permissions.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper RoleWrapper) CreateRole(roleName string, trustedUserArn string)
 (*types.Role, error) {
 var role *types.Role
 trustPolicy := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Principal: map[string]string{"AWS": trustedUserArn},
   Action: []string{"sts:AssumeRole"},
  }},
 }
 policyBytes, err := json.Marshal(trustPolicy)
 if err != nil {
  log.Printf("Couldn't create trust policy for %v. Here's why: %v\n",
 trustedUserArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreateRole(context.TODO(), &iam.CreateRoleInput{
  AssumeRolePolicyDocument: aws.String(string(policyBytes)),
```

```
  RoleName:                 aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't create role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Go da API.

Criar um perfil vinculado ao serviço

Os exemplos de código a seguir mostram como criar uma função vinculada ao serviço do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// CreateServiceLinkedRole creates a service-linked role that is owned by the
 specified service.
func (wrapper RoleWrapper) CreateServiceLinkedRole(serviceName string, description
 string) (*types.Role, error) {
 var role *types.Role
```

```
 result, err := wrapper.IamClient.CreateServiceLinkedRole(context.TODO(),
 &iam.CreateServiceLinkedRoleInput{
  AWSServiceName: aws.String(serviceName),
  Description:    aws.String(description),
 })
 if err != nil {
  log.Printf("Couldn't create service-linked role %v. Here's why: %v\n",
 serviceName, err)
 } else {
  role = result.Role
 }
 return role, err
}
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for Go da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
```

```
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateUser creates a new user with the specified name.
func (wrapper UserWrapper) CreateUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.CreateUser(context.TODO(), &iam.CreateUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create user %v. Here's why: %v\n", userName, err)
 } else {
  user = result.User
 }
 return user, err
}
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Go da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateAccessKeyPair creates an access key for a user. The returned access key
 contains
// the ID and secret credentials needed to use the key.
func (wrapper UserWrapper) CreateAccessKeyPair(userName string) (*types.AccessKey,
 error) {
 var key *types.AccessKey
 result, err := wrapper.IamClient.CreateAccessKey(context.TODO(),
 &iam.CreateAccessKeyInput{
  UserName: aws.String(userName)})
 if err != nil {
  log.Printf("Couldn't create access key pair for user %v. Here's why: %v\n",
 userName, err)
 } else {
  key = result.AccessKey
 }
 return key, err
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Go da API.

Para criar uma política em linha para um usuário

O exemplo de código a seguir mostra como criar uma política em linha do IAM para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// CreateUserPolicy adds an inline policy to a user. This example creates a policy
 that
// grants a list of actions on a specified role.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper UserWrapper) CreateUserPolicy(userName string, policyName string,
 actions []string,
  roleArn string) error {
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(roleArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
```

```
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n", roleArn,
 err)
  return err
 }
 _, err = wrapper.IamClient.PutUserPolicy(context.TODO(), &iam.PutUserPolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
  UserName:       aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create policy for user %v. Here's why: %v\n", userName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte PutUserPolicya Referência AWS SDK for Go da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}
```

```
// DeletePolicy deletes a policy.
func (wrapper PolicyWrapper) DeletePolicy(policyArn string) error {
 _, err := wrapper.IamClient.DeletePolicy(context.TODO(), &iam.DeletePolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't delete policy %v. Here's why: %v\n", policyArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for Go da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// DeleteRole deletes a role. All attached policies must be detached before a
// role can be deleted.
func (wrapper RoleWrapper) DeleteRole(roleName string) error {
```

```
 _, err := wrapper.IamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't delete role %v. Here's why: %v\n", roleName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for Go da API.

Excluir um perfil vinculado ao serviço

Os exemplos de código a seguir mostram como excluir um perfil vinculado ao serviço do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// DeleteServiceLinkedRole deletes a service-linked role.
func (wrapper RoleWrapper) DeleteServiceLinkedRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteServiceLinkedRole(context.TODO(),
 &iam.DeleteServiceLinkedRoleInput{
  RoleName: aws.String(roleName)},
 )
 if err != nil {
```

```
  log.Printf("Couldn't delete service-linked role %v. Here's why: %v\n", roleName,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for Go da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// DeleteUser deletes a user.
```

```
func (wrapper UserWrapper) DeleteUser(userName string) error {
 _, err := wrapper.IamClient.DeleteUser(context.TODO(), &iam.DeleteUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete user %v. Here's why: %v\n", userName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Go da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}
```

```
// DeleteAccessKey deletes an access key from a user.
func (wrapper UserWrapper) DeleteAccessKey(userName string, keyId string) error {
 _, err := wrapper.IamClient.DeleteAccessKey(context.TODO(),
 &iam.DeleteAccessKeyInput{
  AccessKeyId: aws.String(keyId),
  UserName:    aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete access key %v. Here's why: %v\n", keyId, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Go da API.

Excluir uma política em linha de um usuário

O exemplo de código a seguir mostra como excluir uma política em linha do IAM de um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
```

```
 IamClient *iam.Client
}



// DeleteUserPolicy deletes an inline policy from a user.
func (wrapper UserWrapper) DeleteUserPolicy(userName string, policyName string)
 error {
 _, err := wrapper.IamClient.DeleteUserPolicy(context.TODO(),
 &iam.DeleteUserPolicyInput{
  PolicyName: aws.String(policyName),
  UserName:   aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete policy from user %v. Here's why: %v\n", userName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for Go da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}
```

```
// DetachRolePolicy detaches a policy from a role.
func (wrapper RoleWrapper) DetachRolePolicy(roleName string, policyArn string) error
 {
 _, err := wrapper.IamClient.DetachRolePolicy(context.TODO(),
 &iam.DetachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't detach policy from role %v. Here's why: %v\n", roleName, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Go da API.

Obter uma política

Os exemplos de código a seguir mostram como obter a política do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}
```

```
// GetPolicy gets data about a policy.
func (wrapper PolicyWrapper) GetPolicy(policyArn string) (*types.Policy, error) {
 var policy *types.Policy
 result, err := wrapper.IamClient.GetPolicy(context.TODO(), &iam.GetPolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't get policy %v. Here's why: %v\n", policyArn, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for Go da API.

Obter um perfil

Os exemplos de código a seguir mostram como obter um perfil do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}
```

```
// GetRole gets data about a role.
func (wrapper RoleWrapper) GetRole(roleName string) (*types.Role, error) {
 var role *types.Role
 result, err := wrapper.IamClient.GetRole(context.TODO(),
  &iam.GetRoleInput{RoleName: aws.String(roleName)})
 if err != nil {
  log.Printf("Couldn't get role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for Go da API.

Obter um usuário

O exemplo de código a seguir mostra como obter um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
```

```
}



// GetUser gets data about a user.
func (wrapper UserWrapper) GetUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.GetUser(context.TODO(), &iam.GetUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NoSuchEntityException:
    log.Printf("User %v does not exist.\n", userName)
    err = nil
   default:
    log.Printf("Couldn't get user %v. Here's why: %v\n", userName, err)
   }
  }
 } else {
  user = result.User
 }
 return user, err
}
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for Go da API.

Obter a política de senha da conta

Os exemplos de código a seguir mostram como obter a política de senha da conta do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
}



// GetAccountPasswordPolicy gets the account password policy for the current
 account.
// If no policy has been set, a NoSuchEntityException is error is returned.
func (wrapper AccountWrapper) GetAccountPasswordPolicy() (*types.PasswordPolicy,
 error) {
 var pwPolicy *types.PasswordPolicy
 result, err := wrapper.IamClient.GetAccountPasswordPolicy(context.TODO(),
  &iam.GetAccountPasswordPolicyInput{})
 if err != nil {
  log.Printf("Couldn't get account password policy. Here's why: %v\n", err)
 } else {
  pwPolicy = result.PasswordPolicy
 }
 return pwPolicy, err
}
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for Go da API.

Listar provedores SAML

Os exemplos de código a seguir mostram como listar provedores SAML para o IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
}



// ListSAMLProviders gets the SAML providers for the account.
func (wrapper AccountWrapper) ListSAMLProviders() ([]types.SAMLProviderListEntry,
 error) {
 var providers []types.SAMLProviderListEntry
 result, err := wrapper.IamClient.ListSAMLProviders(context.TODO(),
 &iam.ListSAMLProvidersInput{})
 if err != nil {
  log.Printf("Couldn't list SAML providers. Here's why: %v\n", err)
 } else {
  providers = result.SAMLProviderList
 }
 return providers, err
}
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Go.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListAccessKeys lists the access keys for the specified user.
func (wrapper UserWrapper) ListAccessKeys(userName string)
 ([]types.AccessKeyMetadata, error) {
 var keys []types.AccessKeyMetadata
 result, err := wrapper.IamClient.ListAccessKeys(context.TODO(),
 &iam.ListAccessKeysInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list access keys for user %v. Here's why: %v\n", userName,
 err)
 } else {
  keys = result.AccessKeyMetadata
 }
 return keys, err
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Go da API.

Listar grupos

Os exemplos de código a seguir mostram como listar grupos do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// GroupWrapper encapsulates AWS Identity and Access Management (IAM) group actions
// used in the examples.
// It contains an IAM service client that is used to perform group actions.
type GroupWrapper struct {
 IamClient *iam.Client
}



// ListGroups lists up to maxGroups number of groups.
func (wrapper GroupWrapper) ListGroups(maxGroups int32) ([]types.Group, error) {
 var groups []types.Group
 result, err := wrapper.IamClient.ListGroups(context.TODO(), &iam.ListGroupsInput{
  MaxItems: aws.Int32(maxGroups),
 })
 if err != nil {
  log.Printf("Couldn't list groups. Here's why: %v\n", err)
 } else {
  groups = result.Groups
 }
 return groups, err
}
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for Go da API.

Listar políticas em linha para uma função

Os exemplos de código a seguir mostram como listar políticas em linha para um perfil do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRolePolicies lists the inline policies for a role.
func (wrapper RoleWrapper) ListRolePolicies(roleName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListRolePolicies(context.TODO(),
 &iam.ListRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for role %v. Here's why: %v\n", roleName, err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for Go da API.

Listar políticas em linha para um usuário

O exemplo de código a seguir mostra como listar políticas do IAM em linha para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUserPolicies lists the inline policies for the specified user.
func (wrapper UserWrapper) ListUserPolicies(userName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListUserPolicies(context.TODO(),
 &iam.ListUserPoliciesInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for user %v. Here's why: %v\n", userName, err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
```

```
}
```

- Para obter detalhes da API, consulte ListUserPoliciesa Referência AWS SDK for Go da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// ListPolicies gets up to maxPolicies policies.
func (wrapper PolicyWrapper) ListPolicies(maxPolicies int32) ([]types.Policy, error)
 {
 var policies []types.Policy
 result, err := wrapper.IamClient.ListPolicies(context.TODO(),
 &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPolicies),
 })
 if err != nil {
  log.Printf("Couldn't list policies. Here's why: %v\n", err)
 } else {
  policies = result.Policies
 }
```

```
 return policies, err
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Go da API.

Listar políticas anexadas a uma função

Os exemplos de código a seguir mostram como listar políticas a um perfil do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListAttachedRolePolicies lists the policies that are attached to the specified
 role.
func (wrapper RoleWrapper) ListAttachedRolePolicies(roleName string)
 ([]types.AttachedPolicy, error) {
 var policies []types.AttachedPolicy
 result, err := wrapper.IamClient.ListAttachedRolePolicies(context.TODO(),
 &iam.ListAttachedRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list attached policies for role %v. Here's why: %v\n",
 roleName, err)
 } else {
```

```
  policies = result.AttachedPolicies
 }
 return policies, err
}
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for Go da API.

Listar a funções

Os exemplos de código a seguir mostram como listar perfis do IAM.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRoles gets up to maxRoles roles.
func (wrapper RoleWrapper) ListRoles(maxRoles int32) ([]types.Role, error) {
 var roles []types.Role
 result, err := wrapper.IamClient.ListRoles(context.TODO(),
  &iam.ListRolesInput{MaxItems: aws.Int32(maxRoles)},
 )
 if err != nil {
  log.Printf("Couldn't list roles. Here's why: %v\n", err)
 } else {
```

```
  roles = result.Roles
 }
 return roles, err
}
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for Go da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUsers gets up to maxUsers number of users.
func (wrapper UserWrapper) ListUsers(maxUsers int32) ([]types.User, error) {
 var users []types.User
```

```
 result, err := wrapper.IamClient.ListUsers(context.TODO(), &iam.ListUsersInput{
  MaxItems: aws.Int32(maxUsers),
 })
 if err != nil {
  log.Printf("Couldn't list users. Here's why: %v\n", err)
 } else {
  users = result.Users
 }
 return users, err
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Go da API.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// AssumeRoleScenario shows you how to use the AWS Identity and Access Management
 (IAM)
// service to perform the following actions:
//
// 1. Create a user who has no permissions.
// 2. Create a role that grants permission to list Amazon Simple Storage Service
//    (Amazon S3) buckets for the account.
// 3. Add a policy to let the user assume the role.
// 4. Try and fail to list buckets without permissions.
// 5. Assume the role and list S3 buckets using temporary credentials.
// 6. Delete the policy, role, and user.
type AssumeRoleScenario struct {
 sdkConfig aws.Config
 accountWrapper actions.AccountWrapper
 policyWrapper actions.PolicyWrapper
 roleWrapper actions.RoleWrapper
 userWrapper actions.UserWrapper
 questioner demotools.IQuestioner
 helper IScenarioHelper
 isTestRun bool
}

// NewAssumeRoleScenario constructs an AssumeRoleScenario instance from a
 configuration.
// It uses the specified config to get an IAM client and create wrappers for the
 actions
// used in the scenario.
func NewAssumeRoleScenario(sdkConfig aws.Config, questioner demotools.IQuestioner,
  helper IScenarioHelper) AssumeRoleScenario {
 iamClient := iam.NewFromConfig(sdkConfig)
 return AssumeRoleScenario{
  sdkConfig:   sdkConfig,
  accountWrapper: actions.AccountWrapper{IamClient: iamClient},
  policyWrapper:  actions.PolicyWrapper{IamClient: iamClient},
  roleWrapper:    actions.RoleWrapper{IamClient: iamClient},
  userWrapper:    actions.UserWrapper{IamClient: iamClient},
  questioner:     questioner,
  helper:         helper,
 }
}
```

```
// addTestOptions appends the API options specified in the original configuration to
// another configuration. This is used to attach the middleware stubber to clients
// that are constructed during the scenario, which is needed for unit testing.
func (scenario AssumeRoleScenario) addTestOptions(scenarioConfig *aws.Config) {
 if scenario.isTestRun {
  scenarioConfig.APIOptions = append(scenarioConfig.APIOptions,
 scenario.sdkConfig.APIOptions...)
 }
}

// Run runs the interactive scenario.
func (scenario AssumeRoleScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo.\n")
   log.Println(r)
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the AWS Identity and Access Management (IAM) assume role
 demo.")
 log.Println(strings.Repeat("-", 88))

 user := scenario.CreateUser()
 accessKey := scenario.CreateAccessKey(user)
 role := scenario.CreateRoleAndPolicies(user)
 noPermsConfig := scenario.ListBucketsWithoutPermissions(accessKey)
 scenario.ListBucketsWithAssumedRole(noPermsConfig, role)
 scenario.Cleanup(user, role)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateUser creates a new IAM user. This user has no permissions.
func (scenario AssumeRoleScenario) CreateUser() *types.User {
 log.Println("Let's create an example user with no permissions.")
 userName := scenario.questioner.Ask("Enter a name for the example user:",
 demotools.NotEmpty{})
 user, err := scenario.userWrapper.GetUser(userName)
 if err != nil {
  panic(err)
```

```
 }
 if user == nil {
  user, err = scenario.userWrapper.CreateUser(userName)
  if err != nil {
   panic(err)
  }
  log.Printf("Created user %v.\n", *user.UserName)
 } else {
  log.Printf("User %v already exists.\n", *user.UserName)
 }
 log.Println(strings.Repeat("-", 88))
 return user
}

// CreateAccessKey creates an access key for the user.
func (scenario AssumeRoleScenario) CreateAccessKey(user *types.User)
 *types.AccessKey {
 accessKey, err := scenario.userWrapper.CreateAccessKeyPair(*user.UserName)
 if err != nil {
  panic(err)
 }
 log.Printf("Created access key %v for your user.", *accessKey.AccessKeyId)
 log.Println("Waiting a few seconds for your user to be ready...")
 scenario.helper.Pause(10)
 log.Println(strings.Repeat("-", 88))
 return accessKey
}

// CreateRoleAndPolicies creates a policy that grants permission to list S3 buckets
 for
// the current account and attaches the policy to a newly created role. It also adds
 an
// inline policy to the specified user that grants the user permission to assume the
 role.
func (scenario AssumeRoleScenario) CreateRoleAndPolicies(user *types.User)
 *types.Role {
 log.Println("Let's create a role and policy that grant permission to list S3
 buckets.")
 scenario.questioner.Ask("Press Enter when you're ready.")
 listBucketsRole, err := scenario.roleWrapper.CreateRole(scenario.helper.GetName(),
 *user.Arn)
 if err != nil {panic(err)}
 log.Printf("Created role %v.\n", *listBucketsRole.RoleName)
 listBucketsPolicy, err := scenario.policyWrapper.CreatePolicy(
```

```
  scenario.helper.GetName(), []string{"s3:ListAllMyBuckets"}, "arn:aws:s3:::*")
 if err != nil {panic(err)}
 log.Printf("Created policy %v.\n", *listBucketsPolicy.PolicyName)
 err = scenario.roleWrapper.AttachRolePolicy(*listBucketsPolicy.Arn,
 *listBucketsRole.RoleName)
 if err != nil {panic(err)}
 log.Printf("Attached policy %v to role %v.\n", *listBucketsPolicy.PolicyName,
  *listBucketsRole.RoleName)
 err = scenario.userWrapper.CreateUserPolicy(*user.UserName,
 scenario.helper.GetName(),
  []string{"sts:AssumeRole"}, *listBucketsRole.Arn)
 if err != nil {panic(err)}
 log.Printf("Created an inline policy for user %v that lets the user assume the
 role.\n",
  *user.UserName)
 log.Println("Let's give AWS a few seconds to propagate these new resources and
 connections...")
 scenario.helper.Pause(10)
 log.Println(strings.Repeat("-", 88))
 return listBucketsRole
}

// ListBucketsWithoutPermissions creates an Amazon S3 client from the user's access
 key
// credentials and tries to list buckets for the account. Because the user does not
 have
// permission to perform this action, the action fails.
func (scenario AssumeRoleScenario) ListBucketsWithoutPermissions(accessKey
 *types.AccessKey) *aws.Config {
  log.Println("Let's try to list buckets without permissions. This should return an
 AccessDenied error.")
  scenario.questioner.Ask("Press Enter when you're ready.")
  noPermsConfig, err := config.LoadDefaultConfig(context.TODO(),
  config.WithCredentialsProvider(credentials.NewStaticCredentialsProvider(
   *accessKey.AccessKeyId, *accessKey.SecretAccessKey, ""),
 ))
  if err != nil {panic(err)}

  // Add test options if this is a test run. This is needed only for testing
 purposes.
 scenario.addTestOptions(&noPermsConfig)

  s3Client := s3.NewFromConfig(noPermsConfig)
  _, err = s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
```

```
  if err != nil {
   // The SDK for Go does not model the AccessDenied error, so check ErrorCode
 directly.
  var ae smithy.APIError
  if errors.As(err, &ae) {
   switch ae.ErrorCode() {
   case "AccessDenied":
    log.Println("Got AccessDenied error, which is the expected result because\n" +
     "the ListBuckets call was made without permissions.")
   default:
    log.Println("Expected AccessDenied, got something else.")
    panic(err)
   }
  }
  } else {
   log.Println("Expected AccessDenied error when calling ListBuckets without
 permissions,\n" +
    "but the call succeeded. Continuing the example anyway...")
 }
 log.Println(strings.Repeat("-", 88))
  return &noPermsConfig
}

// ListBucketsWithAssumedRole performs the following actions:
//
// 1. Creates an AWS Security Token Service (AWS STS) client from the config created
 from
//   the user's access key credentials.
// 2. Gets temporary credentials by assuming the role that grants permission to list
 the
//    buckets.
// 3. Creates an Amazon S3 client from the temporary credentials.
// 4. Lists buckets for the account. Because the temporary credentials are generated
 by
//    assuming the role that grants permission, the action succeeds.
func (scenario AssumeRoleScenario) ListBucketsWithAssumedRole(noPermsConfig
 *aws.Config, role *types.Role) {
 log.Println("Let's assume the role that grants permission to list buckets and try
 again.")
 scenario.questioner.Ask("Press Enter when you're ready.")
 stsClient := sts.NewFromConfig(*noPermsConfig)
 tempCredentials, err := stsClient.AssumeRole(context.TODO(), &sts.AssumeRoleInput{
  RoleArn:           role.Arn,
  RoleSessionName:   aws.String("AssumeRoleExampleSession"),
```

```
  DurationSeconds:   aws.Int32(900),
 })
 if err != nil {
  log.Printf("Couldn't assume role %v.\n", *role.RoleName)
  panic(err)
 }
 log.Printf("Assumed role %v, got temporary credentials.\n", *role.RoleName)
 assumeRoleConfig, err := config.LoadDefaultConfig(context.TODO(),
  config.WithCredentialsProvider(credentials.NewStaticCredentialsProvider(
   *tempCredentials.Credentials.AccessKeyId,
   *tempCredentials.Credentials.SecretAccessKey,
   *tempCredentials.Credentials.SessionToken),
  ),
 )
 if err != nil {panic(err)}

 // Add test options if this is a test run. This is needed only for testing
 purposes.
 scenario.addTestOptions(&assumeRoleConfig)

 s3Client := s3.NewFromConfig(assumeRoleConfig)
 result, err := s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 if err != nil {
  log.Println("Couldn't list buckets with assumed role credentials.")
  panic(err)
 }
 log.Println("Successfully called ListBuckets with assumed role credentials, \n" +
  "here are some of them:")
 for i := 0; i < len(result.Buckets) && i < 5; i++ {
  log.Printf("\t%v\n", *result.Buckets[i].Name)
 }
 log.Println(strings.Repeat("-", 88))
}

// Cleanup deletes all resources created for the scenario.
func (scenario AssumeRoleScenario) Cleanup(user *types.User, role *types.Role) {
 if scenario.questioner.AskBool(
  "Do you want to delete the resources created for this example? (y/n)", "y",
 ) {
   policies, err := scenario.roleWrapper.ListAttachedRolePolicies(*role.RoleName)
   if err != nil {panic(err)}
   for _, policy := range policies {
    err = scenario.roleWrapper.DetachRolePolicy(*role.RoleName, *policy.PolicyArn)
    if err != nil {panic(err)}
```

```
    err = scenario.policyWrapper.DeletePolicy(*policy.PolicyArn)
    if err != nil {panic(err)}
    log.Printf("Detached policy %v from role %v and deleted the policy.\n",
     *policy.PolicyName, *role.RoleName)
   }
   err = scenario.roleWrapper.DeleteRole(*role.RoleName)
   if err != nil {panic(err)}
   log.Printf("Deleted role %v.\n", *role.RoleName)

   userPols, err := scenario.userWrapper.ListUserPolicies(*user.UserName)
   if err != nil {panic(err)}
   for _, userPol := range userPols {
    err = scenario.userWrapper.DeleteUserPolicy(*user.UserName, userPol)
    if err != nil {panic(err)}
    log.Printf("Deleted policy %v from user %v.\n", userPol, *user.UserName)
   }
   keys, err := scenario.userWrapper.ListAccessKeys(*user.UserName)
   if err != nil {panic(err)}
   for _, key := range keys {
    err = scenario.userWrapper.DeleteAccessKey(*user.UserName, *key.AccessKeyId)
    if err != nil {panic(err)}
    log.Printf("Deleted access key %v from user %v.\n", *key.AccessKeyId,
 *user.UserName)
   }
   err = scenario.userWrapper.DeleteUser(*user.UserName)
   if err != nil {panic(err)}
   log.Printf("Deleted user %v.\n", *user.UserName)
   log.Println(strings.Repeat("-", 88))
 }

}
```

Defina um struct que encapsule as ações de conta.

```
// AccountWrapper encapsulates AWS Identity and Access Management (IAM) account
 actions
// used in the examples.
// It contains an IAM service client that is used to perform account actions.
type AccountWrapper struct {
 IamClient *iam.Client
```

```
}



// GetAccountPasswordPolicy gets the account password policy for the current
 account.
// If no policy has been set, a NoSuchEntityException is error is returned.
func (wrapper AccountWrapper) GetAccountPasswordPolicy() (*types.PasswordPolicy,
 error) {
 var pwPolicy *types.PasswordPolicy
 result, err := wrapper.IamClient.GetAccountPasswordPolicy(context.TODO(),
  &iam.GetAccountPasswordPolicyInput{})
 if err != nil {
  log.Printf("Couldn't get account password policy. Here's why: %v\n", err)
 } else {
  pwPolicy = result.PasswordPolicy
 }
 return pwPolicy, err
}



// ListSAMLProviders gets the SAML providers for the account.
func (wrapper AccountWrapper) ListSAMLProviders() ([]types.SAMLProviderListEntry,
 error) {
 var providers []types.SAMLProviderListEntry
 result, err := wrapper.IamClient.ListSAMLProviders(context.TODO(),
 &iam.ListSAMLProvidersInput{})
 if err != nil {
  log.Printf("Couldn't list SAML providers. Here's why: %v\n", err)
 } else {
  providers = result.SAMLProviderList
 }
 return providers, err
}
```

Defina um struct que encapsule as ações de política.

```
// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
```

```
type PolicyDocument struct {
 Version string
 Statement []PolicyStatement
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect string
 Action []string
 Principal map[string]string `json:",omitempty"`
 Resource *string `json:",omitempty"`
}



// PolicyWrapper encapsulates AWS Identity and Access Management (IAM) policy
 actions
// used in the examples.
// It contains an IAM service client that is used to perform policy actions.
type PolicyWrapper struct {
 IamClient *iam.Client
}



// ListPolicies gets up to maxPolicies policies.
func (wrapper PolicyWrapper) ListPolicies(maxPolicies int32) ([]types.Policy, error)
 {
 var policies []types.Policy
 result, err := wrapper.IamClient.ListPolicies(context.TODO(),
 &iam.ListPoliciesInput{
  MaxItems: aws.Int32(maxPolicies),
 })
 if err != nil {
  log.Printf("Couldn't list policies. Here's why: %v\n", err)
 } else {
  policies = result.Policies
 }
 return policies, err
}
```

```
// CreatePolicy creates a policy that grants a list of actions to the specified
 resource.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper PolicyWrapper) CreatePolicy(policyName string, actions []string,
  resourceArn string) (*types.Policy, error) {
 var policy *types.Policy
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(resourceArn),
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n",
 resourceArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreatePolicy(context.TODO(),
 &iam.CreatePolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
 })
 if err != nil {
  log.Printf("Couldn't create policy %v. Here's why: %v\n", policyName, err)
 } else {
  policy = result.Policy
 }
 return policy, err
}



// GetPolicy gets data about a policy.
func (wrapper PolicyWrapper) GetPolicy(policyArn string) (*types.Policy, error) {
 var policy *types.Policy
 result, err := wrapper.IamClient.GetPolicy(context.TODO(), &iam.GetPolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't get policy %v. Here's why: %v\n", policyArn, err)
```

```
 } else {
  policy = result.Policy
 }
 return policy, err
}



// DeletePolicy deletes a policy.
func (wrapper PolicyWrapper) DeletePolicy(policyArn string) error {
 _, err := wrapper.IamClient.DeletePolicy(context.TODO(), &iam.DeletePolicyInput{
  PolicyArn: aws.String(policyArn),
 })
 if err != nil {
  log.Printf("Couldn't delete policy %v. Here's why: %v\n", policyArn, err)
 }
 return err
}
```

Defina um struct que encapsule as ações de perfil.

```
// RoleWrapper encapsulates AWS Identity and Access Management (IAM) role actions
// used in the examples.
// It contains an IAM service client that is used to perform role actions.
type RoleWrapper struct {
 IamClient *iam.Client
}



// ListRoles gets up to maxRoles roles.
func (wrapper RoleWrapper) ListRoles(maxRoles int32) ([]types.Role, error) {
 var roles []types.Role
 result, err := wrapper.IamClient.ListRoles(context.TODO(),
  &iam.ListRolesInput{MaxItems: aws.Int32(maxRoles)},
 )
 if err != nil {
  log.Printf("Couldn't list roles. Here's why: %v\n", err)
 } else {
  roles = result.Roles
```

```
 }
 return roles, err
}



// CreateRole creates a role that trusts a specified user. The trusted user can
 assume
// the role to acquire its permissions.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper RoleWrapper) CreateRole(roleName string, trustedUserArn string)
 (*types.Role, error) {
 var role *types.Role
 trustPolicy := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Principal: map[string]string{"AWS": trustedUserArn},
   Action: []string{"sts:AssumeRole"},
  }},
 }
 policyBytes, err := json.Marshal(trustPolicy)
 if err != nil {
  log.Printf("Couldn't create trust policy for %v. Here's why: %v\n",
 trustedUserArn, err)
  return nil, err
 }
 result, err := wrapper.IamClient.CreateRole(context.TODO(), &iam.CreateRoleInput{
  AssumeRolePolicyDocument: aws.String(string(policyBytes)),
  RoleName:                 aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't create role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// GetRole gets data about a role.
func (wrapper RoleWrapper) GetRole(roleName string) (*types.Role, error) {
```

```
 var role *types.Role
 result, err := wrapper.IamClient.GetRole(context.TODO(),
  &iam.GetRoleInput{RoleName: aws.String(roleName)})
 if err != nil {
  log.Printf("Couldn't get role %v. Here's why: %v\n", roleName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// CreateServiceLinkedRole creates a service-linked role that is owned by the
 specified service.
func (wrapper RoleWrapper) CreateServiceLinkedRole(serviceName string, description
 string) (*types.Role, error) {
 var role *types.Role
 result, err := wrapper.IamClient.CreateServiceLinkedRole(context.TODO(),
 &iam.CreateServiceLinkedRoleInput{
  AWSServiceName: aws.String(serviceName),
  Description:    aws.String(description),
 })
 if err != nil {
  log.Printf("Couldn't create service-linked role %v. Here's why: %v\n",
 serviceName, err)
 } else {
  role = result.Role
 }
 return role, err
}



// DeleteServiceLinkedRole deletes a service-linked role.
func (wrapper RoleWrapper) DeleteServiceLinkedRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteServiceLinkedRole(context.TODO(),
 &iam.DeleteServiceLinkedRoleInput{
  RoleName: aws.String(roleName)},
 )
 if err != nil {
  log.Printf("Couldn't delete service-linked role %v. Here's why: %v\n", roleName,
 err)
 }
```

```
 return err
}



// AttachRolePolicy attaches a policy to a role.
func (wrapper RoleWrapper) AttachRolePolicy(policyArn string, roleName string) error
 {
 _, err := wrapper.IamClient.AttachRolePolicy(context.TODO(),
 &iam.AttachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't attach policy %v to role %v. Here's why: %v\n", policyArn,
 roleName, err)
 }
 return err
}



// ListAttachedRolePolicies lists the policies that are attached to the specified
 role.
func (wrapper RoleWrapper) ListAttachedRolePolicies(roleName string)
 ([]types.AttachedPolicy, error) {
 var policies []types.AttachedPolicy
 result, err := wrapper.IamClient.ListAttachedRolePolicies(context.TODO(),
 &iam.ListAttachedRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list attached policies for role %v. Here's why: %v\n",
 roleName, err)
 } else {
  policies = result.AttachedPolicies
 }
 return policies, err
}



// DetachRolePolicy detaches a policy from a role.
```

```
func (wrapper RoleWrapper) DetachRolePolicy(roleName string, policyArn string) error
 {
 _, err := wrapper.IamClient.DetachRolePolicy(context.TODO(),
 &iam.DetachRolePolicyInput{
  PolicyArn: aws.String(policyArn),
  RoleName:  aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't detach policy from role %v. Here's why: %v\n", roleName, err)
 }
 return err
}



// ListRolePolicies lists the inline policies for a role.
func (wrapper RoleWrapper) ListRolePolicies(roleName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListRolePolicies(context.TODO(),
 &iam.ListRolePoliciesInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for role %v. Here's why: %v\n", roleName, err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}



// DeleteRole deletes a role. All attached policies must be detached before a
// role can be deleted.
func (wrapper RoleWrapper) DeleteRole(roleName string) error {
 _, err := wrapper.IamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{
  RoleName: aws.String(roleName),
 })
 if err != nil {
  log.Printf("Couldn't delete role %v. Here's why: %v\n", roleName, err)
 }
 return err
}
```

Defina um struct que encapsule as ações de usuário.

```
// UserWrapper encapsulates user actions used in the examples.
// It contains an IAM service client that is used to perform user actions.
type UserWrapper struct {
 IamClient *iam.Client
}



// ListUsers gets up to maxUsers number of users.
func (wrapper UserWrapper) ListUsers(maxUsers int32) ([]types.User, error) {
 var users []types.User
 result, err := wrapper.IamClient.ListUsers(context.TODO(), &iam.ListUsersInput{
  MaxItems: aws.Int32(maxUsers),
 })
 if err != nil {
  log.Printf("Couldn't list users. Here's why: %v\n", err)
 } else {
  users = result.Users
 }
 return users, err
}



// GetUser gets data about a user.
func (wrapper UserWrapper) GetUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.GetUser(context.TODO(), &iam.GetUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NoSuchEntityException:
    log.Printf("User %v does not exist.\n", userName)
    err = nil
```

```
    default:
     log.Printf("Couldn't get user %v. Here's why: %v\n", userName, err)
    }
   }
  } else {
   user = result.User
  }
  return user, err
}



// CreateUser creates a new user with the specified name.
func (wrapper UserWrapper) CreateUser(userName string) (*types.User, error) {
 var user *types.User
 result, err := wrapper.IamClient.CreateUser(context.TODO(), &iam.CreateUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create user %v. Here's why: %v\n", userName, err)
 } else {
  user = result.User
 }
 return user, err
}



// CreateUserPolicy adds an inline policy to a user. This example creates a policy
 that
// grants a list of actions on a specified role.
// PolicyDocument shows how to work with a policy document as a data structure and
// serialize it to JSON by using Go's JSON marshaler.
func (wrapper UserWrapper) CreateUserPolicy(userName string, policyName string,
 actions []string,
  roleArn string) error {
 policyDoc := PolicyDocument{
  Version:   "2012-10-17",
  Statement: []PolicyStatement{{
   Effect: "Allow",
   Action: actions,
   Resource: aws.String(roleArn),
  }},
 }
```

```
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document for %v. Here's why: %v\n", roleArn,
 err)
  return err
 }
 _, err = wrapper.IamClient.PutUserPolicy(context.TODO(), &iam.PutUserPolicyInput{
  PolicyDocument: aws.String(string(policyBytes)),
  PolicyName:     aws.String(policyName),
  UserName:       aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't create policy for user %v. Here's why: %v\n", userName, err)
 }
 return err
}



// ListUserPolicies lists the inline policies for the specified user.
func (wrapper UserWrapper) ListUserPolicies(userName string) ([]string, error) {
 var policies []string
 result, err := wrapper.IamClient.ListUserPolicies(context.TODO(),
 &iam.ListUserPoliciesInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list policies for user %v. Here's why: %v\n", userName, err)
 } else {
  policies = result.PolicyNames
 }
 return policies, err
}



// DeleteUserPolicy deletes an inline policy from a user.
func (wrapper UserWrapper) DeleteUserPolicy(userName string, policyName string)
 error {
 _, err := wrapper.IamClient.DeleteUserPolicy(context.TODO(),
 &iam.DeleteUserPolicyInput{
  PolicyName: aws.String(policyName),
  UserName:   aws.String(userName),
 })
```

```
 if err != nil {
  log.Printf("Couldn't delete policy from user %v. Here's why: %v\n", userName, err)
 }
 return err
}



// DeleteUser deletes a user.
func (wrapper UserWrapper) DeleteUser(userName string) error {
 _, err := wrapper.IamClient.DeleteUser(context.TODO(), &iam.DeleteUserInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete user %v. Here's why: %v\n", userName, err)
 }
 return err
}



// CreateAccessKeyPair creates an access key for a user. The returned access key
 contains
// the ID and secret credentials needed to use the key.
func (wrapper UserWrapper) CreateAccessKeyPair(userName string) (*types.AccessKey,
 error) {
 var key *types.AccessKey
 result, err := wrapper.IamClient.CreateAccessKey(context.TODO(),
 &iam.CreateAccessKeyInput{
  UserName: aws.String(userName)})
 if err != nil {
  log.Printf("Couldn't create access key pair for user %v. Here's why: %v\n",
 userName, err)
 } else {
  key = result.AccessKey
 }
 return key, err
}



// DeleteAccessKey deletes an access key from a user.
func (wrapper UserWrapper) DeleteAccessKey(userName string, keyId string) error {
```

```
 _, err := wrapper.IamClient.DeleteAccessKey(context.TODO(),
 &iam.DeleteAccessKeyInput{
  AccessKeyId: aws.String(keyId),
  UserName:    aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't delete access key %v. Here's why: %v\n", keyId, err)
 }
 return err
}



// ListAccessKeys lists the access keys for the specified user.
func (wrapper UserWrapper) ListAccessKeys(userName string)
 ([]types.AccessKeyMetadata, error) {
 var keys []types.AccessKeyMetadata
 result, err := wrapper.IamClient.ListAccessKeys(context.TODO(),
 &iam.ListAccessKeysInput{
  UserName: aws.String(userName),
 })
 if err != nil {
  log.Printf("Couldn't list access keys for user %v. Here's why: %v\n", userName,
 err)
 } else {
  keys = result.AccessKeyMetadata
 }
 return keys, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey

- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Exemplos do Kinesis usando o SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Go V2 com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent) error {
 if len(kinesisEvent.Records) == 0 {
  log.Printf("empty Kinesis event received")
  return nil
 }

 for _, record := range kinesisEvent.Records {
  log.Printf("processed Kinesis event with EventId: %v", record.EventID)
  recordDataBytes := record.Kinesis.Data
  recordDataText := string(recordDataBytes)
  log.Printf("record data: %v", recordDataText)
  // TODO: Do interesting work based on the new data
 }
 log.Printf("successfully processed %v records", len(kinesisEvent.Records))
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, record := range kinesisEvent.Records {
  curRecordSequenceNumber := ""

  // Process your record
  if /* Your record processing condition here */ {
   curRecordSequenceNumber = record.Kinesis.SequenceNumber
  }

  // Add a condition to check if the record processing failed
  if curRecordSequenceNumber != "" {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": curRecordSequenceNumber})
  }
```

```
 }

 kinesisBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return kinesisBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Exemplos de código do Lambda usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/lambda"
)

// main uses the AWS SDK for Go (v2) to create an AWS Lambda client and list up to
 10
// functions in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 lambdaClient := lambda.NewFromConfig(sdkConfig)

 maxItems := 10
 fmt.Printf("Let's list up to %v functions for your account.\n", maxItems)
 result, err := lambdaClient.ListFunctions(context.TODO(),
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
 })
 if err != nil {
  fmt.Printf("Couldn't list functions for your account. Here's why: %v\n", err)
  return
 }
 if len(result.Functions) == 0 {
  fmt.Println("You don't have any functions!")
 } else {
  for _, function := range result.Functions {
   fmt.Printf("\t%v\n", *function.FunctionName)
  }
```

```
 }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// CreateFunction creates a new Lambda function from code contained in the
 zipPackage
// buffer. The specified handlerName must match the name of the file and function
// contained in the uploaded code. The role specified by iamRoleArn is assumed by
```

```
// Lambda and grants specific permissions.
// When the function already exists, types.StateActive is returned.
// When the function is created, a lambda.FunctionActiveV2Waiter is used to wait
 until the
// function is active.
func (wrapper FunctionWrapper) CreateFunction(functionName string, handlerName
 string,
 iamRoleArn *string, zipPackage *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.CreateFunction(context.TODO(),
 &lambda.CreateFunctionInput{
  Code:         &types.FunctionCode{ZipFile: zipPackage.Bytes()},
  FunctionName: aws.String(functionName),
  Role:         iamRoleArn,
  Handler:      aws.String(handlerName),
  Publish:      true,
  Runtime:      types.RuntimePython38,
 })
 if err != nil {
  var resConflict *types.ResourceConflictException
  if errors.As(err, &resConflict) {
   log.Printf("Function %v already exists.\n", functionName)
   state = types.StateActive
  } else {
   log.Panicf("Couldn't create function %v. Here's why: %v\n", functionName, err)
  }
 } else {
  waiter := lambda.NewFunctionActiveV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(), &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Go da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// DeleteFunction deletes the Lambda function specified by functionName.
func (wrapper FunctionWrapper) DeleteFunction(functionName string) {
 _, err := wrapper.LambdaClient.DeleteFunction(context.TODO(),
 &lambda.DeleteFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't delete function %v. Here's why: %v\n", functionName, err)
 }
}
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Go da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// GetFunction gets data about the Lambda function specified by functionName.
func (wrapper FunctionWrapper) GetFunction(functionName string) types.State {
 var state types.State
 funcOutput, err := wrapper.LambdaClient.GetFunction(context.TODO(),
 &lambda.GetFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't get function %v. Here's why: %v\n", functionName, err)
 } else {
  state = funcOutput.Configuration.State
 }
 return state
}
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for Go da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// Invoke invokes the Lambda function specified by functionName, passing the
 parameters
// as a JSON payload. When getLog is true, types.LogTypeTail is specified, which
 tells
// Lambda to include the last few log lines in the returned result.
func (wrapper FunctionWrapper) Invoke(functionName string, parameters any, getLog
 bool) *lambda.InvokeOutput {
 logType := types.LogTypeNone
 if getLog {
  logType = types.LogTypeTail
 }
 payload, err := json.Marshal(parameters)
 if err != nil {
  log.Panicf("Couldn't marshal parameters to JSON. Here's why %v\n", err)
 }
 invokeOutput, err := wrapper.LambdaClient.Invoke(context.TODO(),
 &lambda.InvokeInput{
  FunctionName: aws.String(functionName),
  LogType:      logType,
  Payload:      payload,
 })
 if err != nil {
  log.Panicf("Couldn't invoke function %v. Here's why: %v\n", functionName, err)
 }
 return invokeOutput
```

```
}
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Go.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// ListFunctions lists up to maxItems functions for the account. This function uses
 a
// lambda.ListFunctionsPaginator to paginate the results.
func (wrapper FunctionWrapper) ListFunctions(maxItems int)
 []types.FunctionConfiguration {
 var functions []types.FunctionConfiguration
 paginator := lambda.NewListFunctionsPaginator(wrapper.LambdaClient,
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
 })
 for paginator.HasMorePages() && len(functions) < maxItems {
  pageOutput, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Panicf("Couldn't list functions for your account. Here's why: %v\n", err)
```

```
  }
  functions = append(functions, pageOutput.Functions...)
 }
 return functions
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Go da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}



// UpdateFunctionCode updates the code for the Lambda function specified by
 functionName.
// The existing code for the Lambda function is entirely replaced by the code in the
// zipPackage buffer. After the update action is called, a
 lambda.FunctionUpdatedV2Waiter
// is used to wait until the update is successful.
func (wrapper FunctionWrapper) UpdateFunctionCode(functionName string, zipPackage
 *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.UpdateFunctionCode(context.TODO(),
 &lambda.UpdateFunctionCodeInput{
```

```
  FunctionName: aws.String(functionName), ZipFile: zipPackage.Bytes(),
 })
 if err != nil {
  log.Panicf("Couldn't update code for function %v. Here's why: %v\n", functionName,
 err)
 } else {
  waiter := lambda.NewFunctionUpdatedV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(), &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for Go da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
type FunctionWrapper struct {
 LambdaClient *lambda.Client
```

```
}



// UpdateFunctionConfiguration updates a map of environment variables configured for
// the Lambda function specified by functionName.
func (wrapper FunctionWrapper) UpdateFunctionConfiguration(functionName string,
 envVars map[string]string) {
 _, err := wrapper.LambdaClient.UpdateFunctionConfiguration(context.TODO(),
 &lambda.UpdateFunctionConfigurationInput{
  FunctionName: aws.String(functionName),
  Environment:  &types.Environment{Variables: envVars},
 })
 if err != nil {
  log.Panicf("Couldn't update configuration for %v. Here's why: %v", functionName,
 err)
 }
}
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for Go da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um cenário interativo para mostrar como começar a usar funções do Lambda.

```
// GetStartedFunctionsScenario shows you how to use AWS Lambda to perform the
 following
// actions:
//
//  1. Create an AWS Identity and Access Management (IAM) role and Lambda function,
 then upload handler code.
//  2. Invoke the function with a single parameter and get results.
//  3. Update the function code and configure with an environment variable.
//  4. Invoke the function with new parameters and get results. Display the returned
 execution log.
//  5. List the functions for your account, then clean up resources.
type GetStartedFunctionsScenario struct {
 sdkConfig       aws.Config
 functionWrapper actions.FunctionWrapper
 questioner      demotools.IQuestioner
 helper          IScenarioHelper
 isTestRun       bool
}

// NewGetStartedFunctionsScenario constructs a GetStartedFunctionsScenario instance
 from a configuration.
// It uses the specified config to get a Lambda client and create wrappers for the
 actions
// used in the scenario.
func NewGetStartedFunctionsScenario(sdkConfig aws.Config, questioner
 demotools.IQuestioner,
 helper IScenarioHelper) GetStartedFunctionsScenario {
 lambdaClient := lambda.NewFromConfig(sdkConfig)
 return GetStartedFunctionsScenario{
  sdkConfig:       sdkConfig,
  functionWrapper: actions.FunctionWrapper{LambdaClient: lambdaClient},
  questioner:      questioner,
```

```
  helper:          helper,
 }
}

// Run runs the interactive scenario.
func (scenario GetStartedFunctionsScenario) Run() {
 defer func() {
  if r := recover(); r != nil {
   log.Printf("Something went wrong with the demo.\n")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the AWS Lambda get started with functions demo.")
 log.Println(strings.Repeat("-", 88))

 role := scenario.GetOrCreateRole()
 funcName := scenario.CreateFunction(role)
 scenario.InvokeIncrement(funcName)
 scenario.UpdateFunction(funcName)
 scenario.InvokeCalculator(funcName)
 scenario.ListFunctions()
 scenario.Cleanup(role, funcName)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// GetOrCreateRole checks whether the specified role exists and returns it if it
 does.
// Otherwise, a role is created that specifies Lambda as a trusted principal.
// The AWSLambdaBasicExecutionRole managed policy is attached to the role and the
 role
// is returned.
func (scenario GetStartedFunctionsScenario) GetOrCreateRole() *iamtypes.Role {
 var role *iamtypes.Role
 iamClient := iam.NewFromConfig(scenario.sdkConfig)
 log.Println("First, we need an IAM role that Lambda can assume.")
 roleName := scenario.questioner.Ask("Enter a name for the role:",
 demotools.NotEmpty{})
 getOutput, err := iamClient.GetRole(context.TODO(), &iam.GetRoleInput{
  RoleName: aws.String(roleName)})
 if err != nil {
```

```
  var noSuch *iamtypes.NoSuchEntityException
  if errors.As(err, &noSuch) {
   log.Printf("Role %v doesn't exist. Creating it....\n", roleName)
  } else {
   log.Panicf("Couldn't check whether role %v exists. Here's why: %v\n",
    roleName, err)
  }
 } else {
  role = getOutput.Role
  log.Printf("Found role %v.\n", *role.RoleName)
 }
 if role == nil {
  trustPolicy := PolicyDocument{
   Version: "2012-10-17",
   Statement: []PolicyStatement{{
    Effect:    "Allow",
    Principal: map[string]string{"Service": "lambda.amazonaws.com"},
    Action:    []string{"sts:AssumeRole"},
   }},
  }
  policyArn := "arn:aws:iam::aws:policy/service-role/AWSLambdaBasicExecutionRole"
  createOutput, err := iamClient.CreateRole(context.TODO(), &iam.CreateRoleInput{
   AssumeRolePolicyDocument: aws.String(trustPolicy.String()),
   RoleName:                 aws.String(roleName),
  })
  if err != nil {
   log.Panicf("Couldn't create role %v. Here's why: %v\n", roleName, err)
  }
  role = createOutput.Role
  _, err = iamClient.AttachRolePolicy(context.TODO(), &iam.AttachRolePolicyInput{
   PolicyArn: aws.String(policyArn),
   RoleName:  aws.String(roleName),
  })
  if err != nil {
   log.Panicf("Couldn't attach a policy to role %v. Here's why: %v\n", roleName,
 err)
  }
  log.Printf("Created role %v.\n", *role.RoleName)
  log.Println("Let's give AWS a few seconds to propagate resources...")
  scenario.helper.Pause(10)
 }
 log.Println(strings.Repeat("-", 88))
 return role
}
```

```
// CreateFunction creates a Lambda function and uploads a handler written in Python.
// The code for the Python handler is packaged as a []byte in .zip format.
func (scenario GetStartedFunctionsScenario) CreateFunction(role *iamtypes.Role)
 string {
 log.Println("Let's create a function that increments a number.\n" +
  "The function uses the 'lambda_handler_basic.py' script found in the \n" +
  "'handlers' directory of this project.")
 funcName := scenario.questioner.Ask("Enter a name for the Lambda function:",
 demotools.NotEmpty{})
 zipPackage := scenario.helper.CreateDeploymentPackage("lambda_handler_basic.py",
 fmt.Sprintf("%v.py", funcName))
 log.Printf("Creating function %v and waiting for it to be ready.", funcName)
 funcState := scenario.functionWrapper.CreateFunction(funcName,
 fmt.Sprintf("%v.lambda_handler", funcName),
  role.Arn, zipPackage)
 log.Printf("Your function is %v.", funcState)
 log.Println(strings.Repeat("-", 88))
 return funcName
}

// InvokeIncrement invokes a Lambda function that increments a number. The function
// parameters are contained in a Go struct that is used to serialize the parameters
 to
// a JSON payload that is passed to the function.
// The result payload is deserialized into a Go struct that contains an int value.
func (scenario GetStartedFunctionsScenario) InvokeIncrement(funcName string) {
 parameters := actions.IncrementParameters{Action: "increment"}
 log.Println("Let's invoke our function. This function increments a number.")
 parameters.Number = scenario.questioner.AskInt("Enter a number to increment:",
 demotools.NotEmpty{})
 log.Printf("Invoking %v with %v...\n", funcName, parameters.Number)
 invokeOutput := scenario.functionWrapper.Invoke(funcName, parameters, false)
 var payload actions.LambdaResultInt
 err := json.Unmarshal(invokeOutput.Payload, &payload)
 if err != nil {
  log.Panicf("Couldn't unmarshal payload from invoking %v. Here's why: %v\n",
   funcName, err)
 }
 log.Printf("Invoking %v with %v returned %v.\n", funcName, parameters.Number,
 payload)
 log.Println(strings.Repeat("-", 88))
}
```

```
// UpdateFunction updates the code for a Lambda function by uploading a simple
 arithmetic
// calculator written in Python. The code for the Python handler is packaged as a
// []byte in .zip format.
// After the code is updated, the configuration is also updated with a new log
// level that instructs the handler to log additional information.
func (scenario GetStartedFunctionsScenario) UpdateFunction(funcName string) {
 log.Println("Let's update the function to an arithmetic calculator.\n" +
  "The function uses the 'lambda_handler_calculator.py' script found in the \n" +
  "'handlers' directory of this project.")
 scenario.questioner.Ask("Press Enter when you're ready.")
 log.Println("Creating deployment package...")
 zipPackage :=
 scenario.helper.CreateDeploymentPackage("lambda_handler_calculator.py",
  fmt.Sprintf("%v.py", funcName))
 log.Println("...and updating the Lambda function and waiting for it to be ready.")
 funcState := scenario.functionWrapper.UpdateFunctionCode(funcName, zipPackage)
 log.Printf("Updated function %v. Its current state is %v.", funcName, funcState)
 log.Println("This function uses an environment variable to control logging level.")
 log.Println("Let's set it to DEBUG to get the most logging.")
 scenario.functionWrapper.UpdateFunctionConfiguration(funcName,
  map[string]string{"LOG_LEVEL": "DEBUG"})
 log.Println(strings.Repeat("-", 88))
}

// InvokeCalculator invokes the Lambda calculator function. The parameters are
 stored in a
// Go struct that is used to serialize the parameters to a JSON payload. That
 payload is then passed
// to the function.
// The result payload is deserialized to a Go struct that stores the result as
 either an
// int or float32, depending on the kind of operation that was specified.
func (scenario GetStartedFunctionsScenario) InvokeCalculator(funcName string) {
 wantInvoke := true
 choices := []string{"plus", "minus", "times", "divided-by"}
 for wantInvoke {
  choice := scenario.questioner.AskChoice("Select an arithmetic operation:\n",
 choices)
  x := scenario.questioner.AskInt("Enter a value for x:", demotools.NotEmpty{})
  y := scenario.questioner.AskInt("Enter a value for y:", demotools.NotEmpty{})
  log.Printf("Invoking %v %v %v...", x, choices[choice], y)
  calcParameters := actions.CalculatorParameters{
   Action: choices[choice],
```

```
    X:      x,
    Y:      y,
   }
   invokeOutput := scenario.functionWrapper.Invoke(funcName, calcParameters, true)
   var payload any
   if choice == 3 { // divide-by results in a float.
    payload = actions.LambdaResultFloat{}
   } else {
    payload = actions.LambdaResultInt{}
   }
   err := json.Unmarshal(invokeOutput.Payload, &payload)
   if err != nil {
    log.Panicf("Couldn't unmarshal payload from invoking %v. Here's why: %v\n",
     funcName, err)
   }
   log.Printf("Invoking %v with %v %v %v returned %v.\n", funcName,
    calcParameters.X, calcParameters.Action, calcParameters.Y, payload)
   scenario.questioner.Ask("Press Enter to see the logs from the call.")
   logRes, err := base64.StdEncoding.DecodeString(*invokeOutput.LogResult)
   if err != nil {
    log.Panicf("Couldn't decode log result. Here's why: %v\n", err)
   }
   log.Println(string(logRes))
   wantInvoke = scenario.questioner.AskBool("Do you want to calculate again? (y/n)",
  "y")
  }
  log.Println(strings.Repeat("-", 88))
 }

 // ListFunctions lists up to the specified number of functions for your account.
 func (scenario GetStartedFunctionsScenario) ListFunctions() {
  count := scenario.questioner.AskInt(
   "Let's list functions for your account. How many do you want to see?",
  demotools.NotEmpty{})
  functions := scenario.functionWrapper.ListFunctions(count)
  log.Printf("Found %v functions:", len(functions))
  for _, function := range functions {
   log.Printf("\t%v", *function.FunctionName)
  }
  log.Println(strings.Repeat("-", 88))
 }

 // Cleanup removes the IAM and Lambda resources created by the example.
```

```
func (scenario GetStartedFunctionsScenario) Cleanup(role *iamtypes.Role, funcName
 string) {
 if scenario.questioner.AskBool("Do you want to clean up resources created for this
 example? (y/n)",
  "y") {
  iamClient := iam.NewFromConfig(scenario.sdkConfig)
  policiesOutput, err := iamClient.ListAttachedRolePolicies(context.TODO(),
   &iam.ListAttachedRolePoliciesInput{RoleName: role.RoleName})
  if err != nil {
   log.Panicf("Couldn't get policies attached to role %v. Here's why: %v\n",
    *role.RoleName, err)
  }
  for _, policy := range policiesOutput.AttachedPolicies {
   _, err = iamClient.DetachRolePolicy(context.TODO(), &iam.DetachRolePolicyInput{
    PolicyArn: policy.PolicyArn, RoleName: role.RoleName,
   })
   if err != nil {
    log.Panicf("Couldn't detach policy %v from role %v. Here's why: %v\n",
     *policy.PolicyArn, *role.RoleName, err)
   }
  }
  _, err = iamClient.DeleteRole(context.TODO(), &iam.DeleteRoleInput{RoleName:
 role.RoleName})
  if err != nil {
   log.Panicf("Couldn't delete role %v. Here's why: %v\n", *role.RoleName, err)
  }
  log.Printf("Deleted role %v.\n", *role.RoleName)

  scenario.functionWrapper.DeleteFunction(funcName)
  log.Printf("Deleted function %v.\n", funcName)
 } else {
  log.Println("Okay. Don't forget to delete the resources when you're done with
 them.")
 }
}
```

Crie uma estrutura que encapsule ações individuais do Lambda.

```
// FunctionWrapper encapsulates function actions used in the examples.
// It contains an AWS Lambda service client that is used to perform user actions.
```

```
type FunctionWrapper struct {
 LambdaClient *lambda.Client
}


// GetFunction gets data about the Lambda function specified by functionName.
func (wrapper FunctionWrapper) GetFunction(functionName string) types.State {
 var state types.State
 funcOutput, err := wrapper.LambdaClient.GetFunction(context.TODO(),
 &lambda.GetFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't get function %v. Here's why: %v\n", functionName, err)
 } else {
  state = funcOutput.Configuration.State
 }
 return state
}



// CreateFunction creates a new Lambda function from code contained in the
 zipPackage
// buffer. The specified handlerName must match the name of the file and function
// contained in the uploaded code. The role specified by iamRoleArn is assumed by
// Lambda and grants specific permissions.
// When the function already exists, types.StateActive is returned.
// When the function is created, a lambda.FunctionActiveV2Waiter is used to wait
 until the
// function is active.
func (wrapper FunctionWrapper) CreateFunction(functionName string, handlerName
 string,
 iamRoleArn *string, zipPackage *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.CreateFunction(context.TODO(),
 &lambda.CreateFunctionInput{
  Code:         &types.FunctionCode{ZipFile: zipPackage.Bytes()},
  FunctionName: aws.String(functionName),
  Role:         iamRoleArn,
  Handler:      aws.String(handlerName),
  Publish:      true,
  Runtime:      types.RuntimePython38,
 })
```

```
 if err != nil {
  var resConflict *types.ResourceConflictException
  if errors.As(err, &resConflict) {
   log.Printf("Function %v already exists.\n", functionName)
   state = types.StateActive
  } else {
   log.Panicf("Couldn't create function %v. Here's why: %v\n", functionName, err)
  }
 } else {
  waiter := lambda.NewFunctionActiveV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(), &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}



// UpdateFunctionCode updates the code for the Lambda function specified by
 functionName.
// The existing code for the Lambda function is entirely replaced by the code in the
// zipPackage buffer. After the update action is called, a
 lambda.FunctionUpdatedV2Waiter
// is used to wait until the update is successful.
func (wrapper FunctionWrapper) UpdateFunctionCode(functionName string, zipPackage
 *bytes.Buffer) types.State {
 var state types.State
 _, err := wrapper.LambdaClient.UpdateFunctionCode(context.TODO(),
 &lambda.UpdateFunctionCodeInput{
  FunctionName: aws.String(functionName), ZipFile: zipPackage.Bytes(),
 })
 if err != nil {
  log.Panicf("Couldn't update code for function %v. Here's why: %v\n", functionName,
 err)
 } else {
  waiter := lambda.NewFunctionUpdatedV2Waiter(wrapper.LambdaClient)
  funcOutput, err := waiter.WaitForOutput(context.TODO(), &lambda.GetFunctionInput{
   FunctionName: aws.String(functionName)}, 1*time.Minute)
```

```
  if err != nil {
   log.Panicf("Couldn't wait for function %v to be active. Here's why: %v\n",
 functionName, err)
  } else {
   state = funcOutput.Configuration.State
  }
 }
 return state
}



// UpdateFunctionConfiguration updates a map of environment variables configured for
// the Lambda function specified by functionName.
func (wrapper FunctionWrapper) UpdateFunctionConfiguration(functionName string,
 envVars map[string]string) {
 _, err := wrapper.LambdaClient.UpdateFunctionConfiguration(context.TODO(),
 &lambda.UpdateFunctionConfigurationInput{
  FunctionName: aws.String(functionName),
  Environment:  &types.Environment{Variables: envVars},
 })
 if err != nil {
  log.Panicf("Couldn't update configuration for %v. Here's why: %v", functionName,
 err)
 }
}



// ListFunctions lists up to maxItems functions for the account. This function uses
 a
// lambda.ListFunctionsPaginator to paginate the results.
func (wrapper FunctionWrapper) ListFunctions(maxItems int)
 []types.FunctionConfiguration {
 var functions []types.FunctionConfiguration
 paginator := lambda.NewListFunctionsPaginator(wrapper.LambdaClient,
 &lambda.ListFunctionsInput{
  MaxItems: aws.Int32(int32(maxItems)),
 })
 for paginator.HasMorePages() && len(functions) < maxItems {
  pageOutput, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Panicf("Couldn't list functions for your account. Here's why: %v\n", err)
  }
```

```
  functions = append(functions, pageOutput.Functions...)
 }
 return functions
}



// DeleteFunction deletes the Lambda function specified by functionName.
func (wrapper FunctionWrapper) DeleteFunction(functionName string) {
 _, err := wrapper.LambdaClient.DeleteFunction(context.TODO(),
 &lambda.DeleteFunctionInput{
  FunctionName: aws.String(functionName),
 })
 if err != nil {
  log.Panicf("Couldn't delete function %v. Here's why: %v\n", functionName, err)
 }
}



// Invoke invokes the Lambda function specified by functionName, passing the
 parameters
// as a JSON payload. When getLog is true, types.LogTypeTail is specified, which
 tells
// Lambda to include the last few log lines in the returned result.
func (wrapper FunctionWrapper) Invoke(functionName string, parameters any, getLog
 bool) *lambda.InvokeOutput {
 logType := types.LogTypeNone
 if getLog {
  logType = types.LogTypeTail
 }
 payload, err := json.Marshal(parameters)
 if err != nil {
  log.Panicf("Couldn't marshal parameters to JSON. Here's why %v\n", err)
 }
 invokeOutput, err := wrapper.LambdaClient.Invoke(context.TODO(),
 &lambda.InvokeInput{
  FunctionName: aws.String(functionName),
  LogType:      logType,
  Payload:      payload,
 })
 if err != nil {
  log.Panicf("Couldn't invoke function %v. Here's why: %v\n", functionName, err)
 }
```

```
 return invokeOutput
}



// IncrementParameters is used to serialize parameters to the increment Lambda
 handler.
type IncrementParameters struct {
 Action string `json:"action"`
 Number int    `json:"number"`
}

// CalculatorParameters is used to serialize parameters to the calculator Lambda
 handler.
type CalculatorParameters struct {
 Action string `json:"action"`
 X      int    `json:"x"`
 Y      int    `json:"y"`
}

// LambdaResultInt is used to deserialize an int result from a Lambda handler.
type LambdaResultInt struct {
 Result int `json:"result"`
}

// LambdaResultFloat is used to deserialize a float32 result from a Lambda handler.
type LambdaResultFloat struct {
 Result float32 `json:"result"`
}
```

Crie uma estrutura que implemente funções para ajudar a executar o cenário.

```
// IScenarioHelper abstracts I/O and wait functions from a scenario so that they
// can be mocked for unit testing.
type IScenarioHelper interface {
 Pause(secs int)
 CreateDeploymentPackage(sourceFile string, destinationFile string) *bytes.Buffer
}

// ScenarioHelper lets the caller specify the path to Lambda handler functions.
```

```
type ScenarioHelper struct {
 HandlerPath string
}

// Pause waits for the specified number of seconds.
func (helper *ScenarioHelper) Pause(secs int) {
 time.Sleep(time.Duration(secs) * time.Second)
}

// CreateDeploymentPackage creates an AWS Lambda deployment package from a source
 file. The
// deployment package is stored in .zip format in a bytes.Buffer. The buffer can be
// used to pass a []byte to Lambda when creating the function.
// The specified destinationFile is the name to give the file when it's deployed to
 Lambda.
func (helper *ScenarioHelper) CreateDeploymentPackage(sourceFile string,
 destinationFile string) *bytes.Buffer {
 var err error
 buffer := &bytes.Buffer{}
 writer := zip.NewWriter(buffer)
 zFile, err := writer.Create(destinationFile)
 if err != nil {
  log.Panicf("Couldn't create destination archive %v. Here's why: %v\n",
 destinationFile, err)
 }
 sourceBody, err := os.ReadFile(fmt.Sprintf("%v/%v", helper.HandlerPath,
 sourceFile))
 if err != nil {
  log.Panicf("Couldn't read handler source file %v. Here's why: %v\n",
   sourceFile, err)
 } else {
  _, err = zFile.Write(sourceBody)
  if err != nil {
   log.Panicf("Couldn't write handler %v to zip archive. Here's why: %v\n",
    sourceFile, err)
  }
 }
 err = writer.Close()
 if err != nil {
  log.Panicf("Couldn't close zip writer. Here's why: %v\n", err)
 }
 return buffer
}
```

Defina um manipulador do Lambda que aumente um número.

```
import logging

logger = logging.getLogger()
logger.setLevel(logging.INFO)


def lambda_handler(event, context):
    """
    Accepts an action and a single number, performs the specified action on the
 number,
    and returns the result. The only allowable action is 'increment'.

    :param event: The event dict that contains the parameters sent when the function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the action.
    """
    result = None
    action = event.get("action")
    if action == "increment":
        result = event.get("number", 0) + 1
        logger.info("Calculated result of %s", result)
    else:
        logger.error("%s is not a valid action.", action)

    response = {"result": result}
    return response
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
import logging
import os


logger = logging.getLogger()
```

```
# Define a list of Python lambda functions that are called by this AWS Lambda
 function.
ACTIONS = {
    "plus": lambda x, y: x + y,
    "minus": lambda x, y: x - y,
    "times": lambda x, y: x * y,
    "divided-by": lambda x, y: x / y,
}


def lambda_handler(event, context):
    """
    Accepts an action and two numbers, performs the specified action on the numbers,
    and returns the result.

    :param event: The event dict that contains the parameters sent when the function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the specified action.
    """
    # Set the log level based on a variable configured in the Lambda environment.
    logger.setLevel(os.environ.get("LOG_LEVEL", logging.INFO))
    logger.debug("Event: %s", event)

    action = event.get("action")
    func = ACTIONS.get(action)
    x = event.get("x")
    y = event.get("y")
    result = None
    try:
        if func is not None and x is not None and y is not None:
            result = func(x, y)
            logger.info("%s %s %s is %s", x, action, y, result)
        else:
            logger.error("I can't calculate %s %s %s.", x, action, y)
    except ZeroDivisionError:
        logger.warning("I can't divide %s by 0!", x)

    response = {"result": result}
    return response
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent) error {
```

```
 if len(kinesisEvent.Records) == 0 {
  log.Printf("empty Kinesis event received")
  return nil
 }

 for _, record := range kinesisEvent.Records {
  log.Printf("processed Kinesis event with EventId: %v", record.EventID)
  recordDataBytes := record.Kinesis.Data
  recordDataText := string(recordDataBytes)
  log.Printf("record data: %v", recordDataText)
  // TODO: Do interesting work based on the new data
 }
 log.Printf("successfully processed %v records", len(kinesisEvent.Records))
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Go.

```
package main

import (
```

```
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

func handler(ctx context.Context, s3Event events.S3Event) error {
 sdkConfig, err := config.LoadDefaultConfig(ctx)
 if err != nil {
  log.Printf("failed to load default config: %s", err)
  return err
 }
 s3Client := s3.NewFromConfig(sdkConfig)

 for _, record := range s3Event.Records {
  bucket := record.S3.Bucket.Name
  key := record.S3.Object.URLDecodedKey
  headOutput, err := s3Client.HeadObject(ctx, &s3.HeadObjectInput{
   Bucket: &bucket,
   Key:    &key,
  })
  if err != nil {
   log.Printf("error getting head of object %s/%s: %s", bucket, key, err)
   return err
  }
  log.Printf("successfully retrieved %s/%s of type %s", bucket, key,
 *headOutput.ContentType)
 }

 return nil
}

func main() {
 lambda.Start(handler)
}
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Go.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, snsEvent events.SNSEvent) {
 for _, record := range snsEvent.Records {
  processMessage(record)
 }
 fmt.Println("done")
}

func processMessage(record events.SNSEventRecord) {
 message := record.SNS.Message
 fmt.Printf("Processed message: %s\n", message)
 // TODO: Process your record here
}

func main() {
 lambda.Start(handler)
}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Go.

```
package integration_sqs_to_lambda

import (
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(event events.SQSEvent) error {
 for _, record := range event.Records {
  err := processMessage(record)
  if err != nil {
   return err
  }
 }
 fmt.Println("done")
 return nil
}

func processMessage(record events.SQSMessage) error {
 fmt.Printf("Processed message %s\n", record.Body)
 // TODO: Do interesting work based on the new message
 return nil
```

```
}

func main() {
 lambda.Start(handler)
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando Go.

```
package main

import (
 "context"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, kinesisEvent events.KinesisEvent)
 (map[string]interface{}, error) {
 batchItemFailures := []map[string]interface{}{}

 for _, record := range kinesisEvent.Records {
  curRecordSequenceNumber := ""

  // Process your record
  if /* Your record processing condition here */ {
```

```
    curRecordSequenceNumber = record.Kinesis.SequenceNumber
   }

   // Add a condition to check if the record processing failed
   if curRecordSequenceNumber != "" {
    batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": curRecordSequenceNumber})
   }
  }

  kinesisBatchResponse := map[string]interface{}{
   "batchItemFailures": batchItemFailures,
  }
  return kinesisBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando Go.

```
package main

import (
 "context"
```

```
 "encoding/json"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, sqsEvent events.SQSEvent) (map[string]interface{},
 error) {
 batchItemFailures := []map[string]interface{}{}

 for _, message := range sqsEvent.Records {

  if /* Your message processing condition here */ {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": message.MessageId})
  }
 }

 sqsBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return sqsBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Exemplos de código para o Amazon RDS usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon RDS

O exemplo de código a seguir mostra como começar a usar o Amazon RDS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/aws"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/rds"
)

// main uses the AWS SDK for Go V2 to create an Amazon Relational Database Service
 (Amazon RDS)
// client and list up to 20 DB instances in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 rdsClient := rds.NewFromConfig(sdkConfig)
```

```
 const maxInstances = 20
 fmt.Printf("Let's list up to %v DB instances.\n", maxInstances)
 output, err := rdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{MaxRecords: aws.Int32(maxInstances)})
 if err != nil {
  fmt.Printf("Couldn't list DB instances: %v\n", err)
  return
 }
 if len(output.DBInstances) == 0 {
  fmt.Println("No DB instances found.")
 } else {
  for _, instance := range output.DBInstances {
   fmt.Printf("DB instance %v has database %v.\n", *instance.DBInstanceIdentifier,
    *instance.DBName)
  }
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

Os códigos de exemplo a seguir mostram como criar uma instância do Amazon RDS e aguardar até que se torne disponível.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateInstance creates a DB instance.
func (instances *DbInstances) CreateInstance(instanceName string, dbName string,
 dbEngine string, dbEngineVersion string, parameterGroupName string, dbInstanceClass
 string,
 storageType string, allocatedStorage int32, adminName string, adminPassword string)
 (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBName:               aws.String(dbName),
  DBParameterGroupName: aws.String(parameterGroupName),
  Engine:               aws.String(dbEngine),
  EngineVersion:        aws.String(dbEngineVersion),
  DBInstanceClass:      aws.String(dbInstanceClass),
  StorageType:          aws.String(storageType),
  AllocatedStorage:     aws.Int32(allocatedStorage),
  MasterUsername:       aws.String(adminName),
  MasterUserPassword:   aws.String(adminPassword),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Go.

Criar um grupo de parâmetros de banco de dados

Os exemplos de código a seguir mostram como criar um grupo de parâmetros do Amazon RDS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateParameterGroup creates a DB parameter group that is based on the specified
// parameter group family.
func (instances *DbInstances) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBParameterGroup, error) {

 output, err := instances.RdsClient.CreateDBParameterGroup(context.TODO(),
  &rds.CreateDBParameterGroupInput{
   DBParameterGroupName:   aws.String(parameterGroupName),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
   Description:            aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBParameterGroup, err
 }
}
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for Go da API.

Criar um snapshot de uma instância de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de uma instância do Amazon RDS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// CreateSnapshot creates a snapshot of a DB instance.
func (instances *DbInstances) CreateSnapshot(instanceName string, snapshotName
 string) (
 *types.DBSnapshot, error) {
 output, err := instances.RdsClient.CreateDBSnapshot(context.TODO(),
 &rds.CreateDBSnapshotInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBSnapshot, nil
 }
}
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Go.

Excluir uma instância de banco de dados

Os exemplos de código a seguir mostram como excluir uma instância do Amazon RDS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// DeleteInstance deletes a DB instance.
func (instances *DbInstances) DeleteInstance(instanceName string) error {
 _, err := instances.RdsClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Go.

Excluir um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// DeleteParameterGroup deletes the named DB parameter group.
func (instances *DbInstances) DeleteParameterGroup(parameterGroupName string) error
 {
 _, err := instances.RdsClient.DeleteDBParameterGroup(context.TODO(),
  &rds.DeleteDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for Go Referência da API.

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetInstance gets data about a DB instance.
func (instances *DbInstances) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Go.

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros de do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetParameterGroup gets a DB parameter group by name.
func (instances *DbInstances) GetParameterGroup(parameterGroupName string) (
 *types.DBParameterGroup, error) {
 output, err := instances.RdsClient.DescribeDBParameterGroups(
  context.TODO(), &rds.DescribeDBParameterGroupsInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBParameterGroups[0], err
```

```
 }
}
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Go da API.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Amazon RDS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (instances *DbInstances) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := instances.RdsClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
```

```
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Go da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever opções para instâncias do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (instances *DbInstances) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instanceOptions []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(instances.RdsClient,
```

```
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instance options: %v\n", err)
   break
  } else {
   instanceOptions = append(instanceOptions, output.OrderableDBInstanceOptions...)
  }
 }
 return instanceOptions, err
}
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Go API.

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}
```

```
// GetParameters gets the parameters that are contained in a DB parameter group.
func (instances *DbInstances) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator := rds.NewDescribeDBParametersPaginator(instances.RdsClient,
  &rds.DescribeDBParametersInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Source:               aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get parameters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Go.

Descrever os snapshots das instâncias de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de instâncias do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// GetSnapshot gets a DB instance snapshot.
func (instances *DbInstances) GetSnapshot(snapshotName string) (*types.DBSnapshot,
 error) {
 output, err := instances.RdsClient.DescribeDBSnapshots(context.TODO(),
  &rds.DescribeDBSnapshotsInput{
   DBSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBSnapshots[0], nil
 }
}
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for Go.

Atualizar os parâmetros em um grupo de parâmetros de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
type DbInstances struct {
 RdsClient *rds.Client
}



// UpdateParameters updates parameters in a named DB parameter group.
func (instances *DbInstances) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := instances.RdsClient.ModifyDBParameterGroup(context.TODO(),
  &rds.ModifyDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Parameters:           params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
 } else {
  return nil
 }
}
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for Go da API.

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
// GetStartedInstances is an interactive example that shows you how to use the AWS
 SDK for Go
// with Amazon Relation Database Service (Amazon RDS) to do the following:
//
//  1. Create a custom DB parameter group and set parameter values.
//  2. Create a DB instance that is configured to use the parameter group. The DB
 instance
//     also contains a database.
//  3. Take a snapshot of the DB instance.
//  4. Delete the DB instance and parameter group.
type GetStartedInstances struct {
 sdkConfig  aws.Config
 instances  actions.DbInstances
 questioner demotools.IQuestioner
 helper     IScenarioHelper
 isTestRun  bool
}

// NewGetStartedInstances constructs a GetStartedInstances instance from a
 configuration.
// It uses the specified config to get an Amazon RDS
// client and create wrappers for the actions used in the scenario.
func NewGetStartedInstances(sdkConfig aws.Config, questioner demotools.IQuestioner,
 helper IScenarioHelper) GetStartedInstances {
 rdsClient := rds.NewFromConfig(sdkConfig)
 return GetStartedInstances{
  sdkConfig:  sdkConfig,
  instances:  actions.DbInstances{RdsClient: rdsClient},
  questioner: questioner,
  helper:     helper,
 }
}
```

```
// Run runs the interactive scenario.
func (scenario GetStartedInstances) Run(dbEngine string, parameterGroupName string,
 instanceName string, dbName string) {
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.")
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon Relational Database Service (Amazon RDS) DB
 Instance demo.")
 log.Println(strings.Repeat("-", 88))

 parameterGroup := scenario.CreateParameterGroup(dbEngine, parameterGroupName)
 scenario.SetUserParameters(parameterGroupName)
 instance := scenario.CreateInstance(instanceName, dbEngine, dbName, parameterGroup)
 scenario.DisplayConnection(instance)
 scenario.CreateSnapshot(instance)
 scenario.Cleanup(instance, parameterGroup)

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}

// CreateParameterGroup shows how to get available engine versions for a specified
// database engine and create a DB parameter group that is compatible with a
// selected engine family.
func (scenario GetStartedInstances) CreateParameterGroup(dbEngine string,
 parameterGroupName string) *types.DBParameterGroup {

 log.Printf("Checking for an existing DB parameter group named %v.\n",
  parameterGroupName)
 parameterGroup, err := scenario.instances.GetParameterGroup(parameterGroupName)
 if err != nil {
  panic(err)
 }
 if parameterGroup == nil {
  log.Printf("Getting available database engine versions for %v.\n", dbEngine)
  engineVersions, err := scenario.instances.GetEngineVersions(dbEngine, "")
  if err != nil {
   panic(err)
```

```
  }

  familySet := map[string]struct{}{}
  for _, family := range engineVersions {
   familySet[*family.DBParameterGroupFamily] = struct{}{}
  }
  var families []string
  for family := range familySet {
   families = append(families, family)
  }
  sort.Strings(families)
  familyIndex := scenario.questioner.AskChoice("Which family do you want to use?\n",
 families)
  log.Println("Creating a DB parameter group.")
  _, err = scenario.instances.CreateParameterGroup(
   parameterGroupName, families[familyIndex], "Example parameter group.")
  if err != nil {
   panic(err)
  }
  parameterGroup, err = scenario.instances.GetParameterGroup(parameterGroupName)
  if err != nil {
   panic(err)
  }
 }
 log.Printf("Parameter group %v:\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tName: %v\n", *parameterGroup.DBParameterGroupName)
 log.Printf("\tARN: %v\n", *parameterGroup.DBParameterGroupArn)
 log.Printf("\tFamily: %v\n", *parameterGroup.DBParameterGroupFamily)
 log.Printf("\tDescription: %v\n", *parameterGroup.Description)
 log.Println(strings.Repeat("-", 88))
 return parameterGroup
}

// SetUserParameters shows how to get the parameters contained in a custom parameter
// group and update some of the parameter values in the group.
func (scenario GetStartedInstances) SetUserParameters(parameterGroupName string) {
 log.Println("Let's set some parameter values in your parameter group.")
 dbParameters, err := scenario.instances.GetParameters(parameterGroupName, "")
 if err != nil {
  panic(err)
 }
 var updateParams []types.Parameter
 for _, dbParam := range dbParameters {
  if strings.HasPrefix(*dbParam.ParameterName, "auto_increment") &&
```

```
    dbParam.IsModifiable && *dbParam.DataType == "integer" {
    log.Printf("The %v parameter is described as:\n\t%v",
     *dbParam.ParameterName, *dbParam.Description)
    rangeSplit := strings.Split(*dbParam.AllowedValues, "-")
    lower, _ := strconv.Atoi(rangeSplit[0])
    upper, _ := strconv.Atoi(rangeSplit[1])
    newValue := scenario.questioner.AskInt(
     fmt.Sprintf("Enter a value between %v and %v:", lower, upper),
     demotools.InIntRange{Lower: lower, Upper: upper})
    dbParam.ParameterValue = aws.String(strconv.Itoa(newValue))
    updateParams = append(updateParams, dbParam)
   }
  }
  err = scenario.instances.UpdateParameters(parameterGroupName, updateParams)
  if err != nil {
   panic(err)
  }
  log.Println("To get a list of parameters that you set previously, specify a source
  of 'user'.")
  userParameters, err := scenario.instances.GetParameters(parameterGroupName, "user")
  if err != nil {
   panic(err)
  }
  log.Println("Here are the parameters you set:")
  for _, param := range userParameters {
   log.Printf("\t%v: %v\n", *param.ParameterName, *param.ParameterValue)
  }
  log.Println(strings.Repeat("-", 88))
}

// CreateInstance shows how to create a DB instance that contains a database of a
// specified type. The database is also configured to use a custom DB parameter
 group.
func (scenario GetStartedInstances) CreateInstance(instanceName string, dbEngine
 string,
 dbName string, parameterGroup *types.DBParameterGroup) *types.DBInstance {

 log.Println("Checking for an existing DB instance.")
 instance, err := scenario.instances.GetInstance(instanceName)
 if err != nil {
  panic(err)
 }
 if instance == nil {
  adminUsername := scenario.questioner.Ask(
```

```
  "Enter an administrator username for the database: ", demotools.NotEmpty{})
 adminPassword := scenario.questioner.AskPassword(
  "Enter a password for the administrator (at least 8 characters): ", 7)
 engineVersions, err := scenario.instances.GetEngineVersions(dbEngine,
  *parameterGroup.DBParameterGroupFamily)
 if err != nil {
  panic(err)
 }
 var engineChoices []string
 for _, engine := range engineVersions {
  engineChoices = append(engineChoices, *engine.EngineVersion)
 }
 engineIndex := scenario.questioner.AskChoice(
  "The available engines for your parameter group are:\n", engineChoices)
 engineSelection := engineVersions[engineIndex]
 instOpts, err := scenario.instances.GetOrderableInstances(*engineSelection.Engine,
  *engineSelection.EngineVersion)
 if err != nil {
  panic(err)
 }
 optSet := map[string]struct{}{}
 for _, opt := range instOpts {
  if strings.Contains(*opt.DBInstanceClass, "micro") {
   optSet[*opt.DBInstanceClass] = struct{}{}
  }
 }
 var optChoices []string
 for opt := range optSet {
  optChoices = append(optChoices, opt)
 }
 sort.Strings(optChoices)
 optIndex := scenario.questioner.AskChoice(
  "The available micro DB instance classes for your database engine are:\n",
optChoices)
 storageType := "standard"
 allocatedStorage := int32(5)
 log.Printf("Creating a DB instance named %v and database %v.\n"+
  "The DB instance is configured to use your custom parameter group %v,\n"+
  "selected engine %v,\n"+
  "selected DB instance class %v,"+
  "and %v GiB of %v storage.\n"+
  "This typically takes several minutes.",
  instanceName, dbName, *parameterGroup.DBParameterGroupName,
*engineSelection.EngineVersion,
```

```
    optChoices[optIndex], allocatedStorage, storageType)
   instance, err = scenario.instances.CreateInstance(
    instanceName, dbName, *engineSelection.Engine, *engineSelection.EngineVersion,
    *parameterGroup.DBParameterGroupName, optChoices[optIndex], storageType,
    allocatedStorage, adminUsername, adminPassword)
   if err != nil {
    panic(err)
   }
   for *instance.DBInstanceStatus != "available" {
    scenario.helper.Pause(30)
    instance, err = scenario.instances.GetInstance(instanceName)
    if err != nil {
     panic(err)
    }
   }
   log.Println("Instance created and available.")
  }
  log.Println("Instance data:")
  log.Printf("\tDBInstanceIdentifier: %v\n", *instance.DBInstanceIdentifier)
  log.Printf("\tARN: %v\n", *instance.DBInstanceArn)
  log.Printf("\tStatus: %v\n", *instance.DBInstanceStatus)
  log.Printf("\tEngine: %v\n", *instance.Engine)
  log.Printf("\tEngine version: %v\n", *instance.EngineVersion)
  log.Println(strings.Repeat("-", 88))
  return instance
}

// DisplayConnection displays connection information about a DB instance and tips
// on how to connect to it.
func (scenario GetStartedInstances) DisplayConnection(instance *types.DBInstance) {
  log.Println(
   "You can now connect to your database by using your favorite MySQL client.\n" +
    "One way to connect is by using the 'mysql' shell on an Amazon EC2 instance\n" +
    "that is running in the same VPC as your DB instance. Pass the endpoint,\n" +
    "port, and administrator username to 'mysql'. Then, enter your password\n" +
    "when prompted:")
  log.Printf("\n\tmysql -h %v -P %v -u %v -p\n",
   *instance.Endpoint.Address, instance.Endpoint.Port, *instance.MasterUsername)
  log.Println("For more information, see the User Guide for RDS:\n" +
   "\thttps://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/
CHAP_GettingStarted.CreatingConnecting.MySQL.html#CHAP_GettingStarted.Connecting.MySQL")
  log.Println(strings.Repeat("-", 88))
}
```

```
// CreateSnapshot shows how to create a DB instance snapshot and wait until it's
 available.
func (scenario GetStartedInstances) CreateSnapshot(instance *types.DBInstance) {
 if scenario.questioner.AskBool(
  "Do you want to create a snapshot of your DB instance (y/n)? ", "y") {
  snapshotId := fmt.Sprintf("%v-%v", *instance.DBInstanceIdentifier,
 scenario.helper.UniqueId())
  log.Printf("Creating a snapshot named %v. This typically takes a few minutes.\n",
 snapshotId)
  snapshot, err := scenario.instances.CreateSnapshot(*instance.DBInstanceIdentifier,
 snapshotId)
  if err != nil {
   panic(err)
  }
  for *snapshot.Status != "available" {
   scenario.helper.Pause(30)
   snapshot, err = scenario.instances.GetSnapshot(snapshotId)
   if err != nil {
    panic(err)
   }
  }
  log.Println("Snapshot data:")
  log.Printf("\tDBSnapshotIdentifier: %v\n", *snapshot.DBSnapshotIdentifier)
  log.Printf("\tARN: %v\n", *snapshot.DBSnapshotArn)
  log.Printf("\tStatus: %v\n", *snapshot.Status)
  log.Printf("\tEngine: %v\n", *snapshot.Engine)
  log.Printf("\tEngine version: %v\n", *snapshot.EngineVersion)
  log.Printf("\tDBInstanceIdentifier: %v\n", *snapshot.DBInstanceIdentifier)
  log.Printf("\tSnapshotCreateTime: %v\n", *snapshot.SnapshotCreateTime)
  log.Println(strings.Repeat("-", 88))
 }
}

// Cleanup shows how to clean up a DB instance and DB parameter group.
// Before the DB parameter group can be deleted, all associated DB instances must
 first be deleted.
func (scenario GetStartedInstances) Cleanup(
 instance *types.DBInstance, parameterGroup *types.DBParameterGroup) {

 if scenario.questioner.AskBool(
  "\nDo you want to delete the database instance and parameter group (y/n)? ", "y")
 {
  log.Printf("Deleting database instance %v.\n", *instance.DBInstanceIdentifier)
  err := scenario.instances.DeleteInstance(*instance.DBInstanceIdentifier)
```

```
  if err != nil {
   panic(err)
  }
  log.Println(
   "Waiting for the DB instance to delete. This typically takes several minutes.")
  for instance != nil {
   scenario.helper.Pause(30)
   instance, err = scenario.instances.GetInstance(*instance.DBInstanceIdentifier)
   if err != nil {
    panic(err)
   }
  }
  log.Printf("Deleting parameter group %v.", *parameterGroup.DBParameterGroupName)
  err =
 scenario.instances.DeleteParameterGroup(*parameterGroup.DBParameterGroupName)
  if err != nil {
   panic(err)
  }
 }
}
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Amazon RDS.

```
type DbInstances struct {
 RdsClient *rds.Client
}


// GetParameterGroup gets a DB parameter group by name.
func (instances *DbInstances) GetParameterGroup(parameterGroupName string) (
 *types.DBParameterGroup, error) {
 output, err := instances.RdsClient.DescribeDBParameterGroups(
  context.TODO(), &rds.DescribeDBParameterGroupsInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  var notFoundError *types.DBParameterGroupNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("Parameter group %v does not exist.\n", parameterGroupName)
   err = nil
```

```
  } else {
   log.Printf("Error getting parameter group %v: %v\n", parameterGroupName, err)
  }
  return nil, err
 } else {
  return &output.DBParameterGroups[0], err
 }
}



// CreateParameterGroup creates a DB parameter group that is based on the specified
// parameter group family.
func (instances *DbInstances) CreateParameterGroup(
 parameterGroupName string, parameterGroupFamily string, description string) (
 *types.DBParameterGroup, error) {

 output, err := instances.RdsClient.CreateDBParameterGroup(context.TODO(),
  &rds.CreateDBParameterGroupInput{
   DBParameterGroupName:   aws.String(parameterGroupName),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
   Description:            aws.String(description),
  })
 if err != nil {
  log.Printf("Couldn't create parameter group %v: %v\n", parameterGroupName, err)
  return nil, err
 } else {
  return output.DBParameterGroup, err
 }
}



// DeleteParameterGroup deletes the named DB parameter group.
func (instances *DbInstances) DeleteParameterGroup(parameterGroupName string) error
 {
 _, err := instances.RdsClient.DeleteDBParameterGroup(context.TODO(),
  &rds.DeleteDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
  })
 if err != nil {
  log.Printf("Couldn't delete parameter group %v: %v\n", parameterGroupName, err)
  return err
 } else {
```

```
  return nil
 }
}



// GetParameters gets the parameters that are contained in a DB parameter group.
func (instances *DbInstances) GetParameters(parameterGroupName string, source
 string) (
 []types.Parameter, error) {

 var output *rds.DescribeDBParametersOutput
 var params []types.Parameter
 var err error
 parameterPaginator := rds.NewDescribeDBParametersPaginator(instances.RdsClient,
  &rds.DescribeDBParametersInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Source:               aws.String(source),
  })
 for parameterPaginator.HasMorePages() {
  output, err = parameterPaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get parameters for %v: %v\n", parameterGroupName, err)
   break
  } else {
   params = append(params, output.Parameters...)
  }
 }
 return params, err
}



// UpdateParameters updates parameters in a named DB parameter group.
func (instances *DbInstances) UpdateParameters(parameterGroupName string, params
 []types.Parameter) error {
 _, err := instances.RdsClient.ModifyDBParameterGroup(context.TODO(),
  &rds.ModifyDBParameterGroupInput{
   DBParameterGroupName: aws.String(parameterGroupName),
   Parameters:           params,
  })
 if err != nil {
  log.Printf("Couldn't update parameters in %v: %v\n", parameterGroupName, err)
  return err
```

```
 } else {
  return nil
 }
}



// CreateSnapshot creates a snapshot of a DB instance.
func (instances *DbInstances) CreateSnapshot(instanceName string, snapshotName
 string) (
 *types.DBSnapshot, error) {
 output, err := instances.RdsClient.CreateDBSnapshot(context.TODO(),
 &rds.CreateDBSnapshotInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBSnapshotIdentifier: aws.String(snapshotName),
 })
 if err != nil {
  log.Printf("Couldn't create snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return output.DBSnapshot, nil
 }
}



// GetSnapshot gets a DB instance snapshot.
func (instances *DbInstances) GetSnapshot(snapshotName string) (*types.DBSnapshot,
 error) {
 output, err := instances.RdsClient.DescribeDBSnapshots(context.TODO(),
  &rds.DescribeDBSnapshotsInput{
   DBSnapshotIdentifier: aws.String(snapshotName),
  })
 if err != nil {
  log.Printf("Couldn't get snapshot %v: %v\n", snapshotName, err)
  return nil, err
 } else {
  return &output.DBSnapshots[0], nil
 }
}



// CreateInstance creates a DB instance.
```

```
func (instances *DbInstances) CreateInstance(instanceName string, dbName string,
 dbEngine string, dbEngineVersion string, parameterGroupName string, dbInstanceClass
 string,
 storageType string, allocatedStorage int32, adminName string, adminPassword string)
 (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.CreateDBInstance(context.TODO(),
 &rds.CreateDBInstanceInput{
  DBInstanceIdentifier: aws.String(instanceName),
  DBName:               aws.String(dbName),
  DBParameterGroupName: aws.String(parameterGroupName),
  Engine:               aws.String(dbEngine),
  EngineVersion:        aws.String(dbEngineVersion),
  DBInstanceClass:      aws.String(dbInstanceClass),
  StorageType:          aws.String(storageType),
  AllocatedStorage:     aws.Int32(allocatedStorage),
  MasterUsername:       aws.String(adminName),
  MasterUserPassword:   aws.String(adminPassword),
 })
 if err != nil {
  log.Printf("Couldn't create instance %v: %v\n", instanceName, err)
  return nil, err
 } else {
  return output.DBInstance, nil
 }
}



// GetInstance gets data about a DB instance.
func (instances *DbInstances) GetInstance(instanceName string) (
 *types.DBInstance, error) {
 output, err := instances.RdsClient.DescribeDBInstances(context.TODO(),
  &rds.DescribeDBInstancesInput{
   DBInstanceIdentifier: aws.String(instanceName),
  })
 if err != nil {
  var notFoundError *types.DBInstanceNotFoundFault
  if errors.As(err, &notFoundError) {
   log.Printf("DB instance %v does not exist.\n", instanceName)
   err = nil
  } else {
   log.Printf("Couldn't get instance %v: %v\n", instanceName, err)
  }
```

```
  return nil, err
 } else {
  return &output.DBInstances[0], nil
 }
}



// DeleteInstance deletes a DB instance.
func (instances *DbInstances) DeleteInstance(instanceName string) error {
 _, err := instances.RdsClient.DeleteDBInstance(context.TODO(),
 &rds.DeleteDBInstanceInput{
  DBInstanceIdentifier:   aws.String(instanceName),
  SkipFinalSnapshot:      true,
  DeleteAutomatedBackups: aws.Bool(true),
 })
 if err != nil {
  log.Printf("Couldn't delete instance %v: %v\n", instanceName, err)
  return err
 } else {
  return nil
 }
}



// GetEngineVersions gets database engine versions that are available for the
 specified engine
// and parameter group family.
func (instances *DbInstances) GetEngineVersions(engine string, parameterGroupFamily
 string) (
 []types.DBEngineVersion, error) {
 output, err := instances.RdsClient.DescribeDBEngineVersions(context.TODO(),
  &rds.DescribeDBEngineVersionsInput{
   Engine:                 aws.String(engine),
   DBParameterGroupFamily: aws.String(parameterGroupFamily),
  })
 if err != nil {
  log.Printf("Couldn't get engine versions for %v: %v\n", engine, err)
  return nil, err
 } else {
  return output.DBEngineVersions, nil
 }
}
```

```
// GetOrderableInstances uses a paginator to get DB instance options that can be
 used to create DB instances that are
// compatible with a set of specifications.
func (instances *DbInstances) GetOrderableInstances(engine string, engineVersion
 string) (
 []types.OrderableDBInstanceOption, error) {

 var output *rds.DescribeOrderableDBInstanceOptionsOutput
 var instanceOptions []types.OrderableDBInstanceOption
 var err error
 orderablePaginator :=
 rds.NewDescribeOrderableDBInstanceOptionsPaginator(instances.RdsClient,
  &rds.DescribeOrderableDBInstanceOptionsInput{
   Engine:        aws.String(engine),
   EngineVersion: aws.String(engineVersion),
  })
 for orderablePaginator.HasMorePages() {
  output, err = orderablePaginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get orderable DB instance options: %v\n", err)
   break
  } else {
   instanceOptions = append(instanceOptions, output.OrderableDBInstanceOptions...)
  }
 }
 return instanceOptions, err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions

- DescribeDBInstances
- DB descrito ParameterGroups
- DescribeDBParameters
- DescribeDBSnapshots
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ParameterGroup

Exemplos de código do Amazon S3 usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main
```

```
import (
 "context"
 "fmt"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Storage Service
// (Amazon S3) client and list up to 10 buckets in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 s3Client := s3.NewFromConfig(sdkConfig)
 count := 10
 fmt.Printf("Let's list up to %v buckets for your account.\n", count)
 result, err := s3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 if err != nil {
  fmt.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
  return
 }
 if len(result.Buckets) == 0 {
  fmt.Println("You don't have any buckets!")
 } else {
  if count > len(result.Buckets) {
   count = len(result.Buckets)
  }
  for _, bucket := range result.Buckets[:count] {
   fmt.Printf("\t%v\n", *bucket.Name)
  }
 }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// CopyToBucket copies an object in a bucket to another bucket.
func (basics BucketBasics) CopyToBucket(sourceBucket string, destinationBucket
 string, objectKey string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(destinationBucket),
  CopySource: aws.String(fmt.Sprintf("%v/%v", sourceBucket, objectKey)),
  Key:        aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v. Here's why: %v\n",
```

```
    sourceBucket, objectKey, destinationBucket, objectKey, err)
  }
  return err
}
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Go da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// CreateBucket creates a bucket with the specified name in the specified Region.
func (basics BucketBasics) CreateBucket(name string, region string) error {
 _, err := basics.S3Client.CreateBucket(context.TODO(), &s3.CreateBucketInput{
  Bucket: aws.String(name),
  CreateBucketConfiguration: &types.CreateBucketConfiguration{
   LocationConstraint: types.BucketLocationConstraint(region),
  },
 })
 if err != nil {
```

```
  log.Printf("Couldn't create bucket %v in Region %v. Here's why: %v\n",
   name, region, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Go da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DeleteBucket deletes a bucket. The bucket must be empty or an error is returned.
func (basics BucketBasics) DeleteBucket(bucketName string) error {
 _, err := basics.S3Client.DeleteBucket(context.TODO(), &s3.DeleteBucketInput{
  Bucket: aws.String(bucketName)})
 if err != nil {
  log.Printf("Couldn't delete bucket %v. Here's why: %v\n", bucketName, err)
 }
 return err
```

```
}
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Go da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DeleteObjects deletes a list of objects from a bucket.
func (basics BucketBasics) DeleteObjects(bucketName string, objectKeys []string)
 error {
 var objectIds []types.ObjectIdentifier
 for _, key := range objectKeys {
  objectIds = append(objectIds, types.ObjectIdentifier{Key: aws.String(key)})
 }
 output, err := basics.S3Client.DeleteObjects(context.TODO(),
 &s3.DeleteObjectsInput{
  Bucket: aws.String(bucketName),
  Delete: &types.Delete{Objects: objectIds},
 })
```

```
 if err != nil {
  log.Printf("Couldn't delete objects from bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
  log.Printf("Deleted %v objects.\n", len(output.Deleted))
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Go da API.

Determinar a existência de um bucket

O exemplo de código a seguir mostra como determinar a existência de um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// BucketExists checks whether a bucket exists in the current account.
func (basics BucketBasics) BucketExists(bucketName string) (bool, error) {
 _, err := basics.S3Client.HeadBucket(context.TODO(), &s3.HeadBucketInput{
  Bucket: aws.String(bucketName),
 })
```

```
 exists := true
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NotFound:
    log.Printf("Bucket %v is available.\n", bucketName)
    exists = false
    err = nil
   default:
    log.Printf("Either you don't have access to bucket %v or another error occurred.
 "+
     "Here's what happened: %v\n", bucketName, err)
   }
  }
 } else {
  log.Printf("Bucket %v exists and you already own it.", bucketName)
 }

 return exists, err
}
```

- Para obter detalhes da API, consulte HeadBucketa Referência AWS SDK for Go da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
```

```
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// DownloadFile gets an object from a bucket and stores it in a local file.
func (basics BucketBasics) DownloadFile(bucketName string, objectKey string,
 fileName string) error {
 result, err := basics.S3Client.GetObject(context.TODO(), &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't get object %v:%v. Here's why: %v\n", bucketName, objectKey,
 err)
  return err
 }
 defer result.Body.Close()
 file, err := os.Create(fileName)
 if err != nil {
  log.Printf("Couldn't create file %v. Here's why: %v\n", fileName, err)
  return err
 }
 defer file.Close()
 body, err := io.ReadAll(result.Body)
 if err != nil {
  log.Printf("Couldn't read object body from %v. Here's why: %v\n", objectKey, err)
 }
 _, err = file.Write(body)
 return err
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Go da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListBuckets lists the buckets in the current account.
func (basics BucketBasics) ListBuckets() ([]types.Bucket, error) {
 result, err := basics.S3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 var buckets []types.Bucket
 if err != nil {
  log.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
 } else {
  buckets = result.Buckets
 }
 return buckets, err
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Go da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListObjects lists the objects in a bucket.
func (basics BucketBasics) ListObjects(bucketName string) ([]types.Object, error) {
 result, err := basics.S3Client.ListObjectsV2(context.TODO(),
 &s3.ListObjectsV2Input{
  Bucket: aws.String(bucketName),
 })
 var contents []types.Object
 if err != nil {
  log.Printf("Couldn't list objects in bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
  contents = result.Contents
 }
 return contents, err
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Go da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// UploadFile reads from a file and puts the data into an object in a bucket.
func (basics BucketBasics) UploadFile(bucketName string, objectKey string, fileName
 string) error {
 file, err := os.Open(fileName)
 if err != nil {
  log.Printf("Couldn't open file %v to upload. Here's why: %v\n", fileName, err)
 } else {
  defer file.Close()
  _, err = basics.S3Client.PutObject(context.TODO(), &s3.PutObjectInput{
   Bucket: aws.String(bucketName),
   Key:    aws.String(objectKey),
   Body:   file,
  })
  if err != nil {
   log.Printf("Couldn't upload file %v to %v:%v. Here's why: %v\n",
    fileName, bucketName, objectKey, err)
  }
 }
 return err
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Go da API.

Cenários

Criar um URL pré-assinado

Os exemplos de código a seguir mostram como criar uma URL pré-assinada para o Amazon S3 e carregar um objeto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações de pré-assinatura do S3.

```
// Presigner encapsulates the Amazon Simple Storage Service (Amazon S3) presign
 actions
// used in the examples.
// It contains PresignClient, a client that is used to presign requests to Amazon
 S3.
// Presigned requests contain temporary credentials and can be made from any HTTP
 client.
type Presigner struct {
 PresignClient *s3.PresignClient
}



// GetObject makes a presigned request that can be used to get an object from a
 bucket.
// The presigned request is valid for the specified number of seconds.
func (presigner Presigner) GetObject(
 bucketName string, objectKey string, lifetimeSecs int64) (*v4.PresignedHTTPRequest,
 error) {
 request, err := presigner.PresignClient.PresignGetObject(context.TODO(),
 &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
```

```
  Key:    aws.String(objectKey),
 }, func(opts *s3.PresignOptions) {
  opts.Expires = time.Duration(lifetimeSecs * int64(time.Second))
 })
 if err != nil {
  log.Printf("Couldn't get a presigned request to get %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return request, err
}



// PutObject makes a presigned request that can be used to put an object in a
 bucket.
// The presigned request is valid for the specified number of seconds.
func (presigner Presigner) PutObject(
 bucketName string, objectKey string, lifetimeSecs int64) (*v4.PresignedHTTPRequest,
 error) {
 request, err := presigner.PresignClient.PresignPutObject(context.TODO(),
 &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 }, func(opts *s3.PresignOptions) {
  opts.Expires = time.Duration(lifetimeSecs * int64(time.Second))
 })
 if err != nil {
  log.Printf("Couldn't get a presigned request to put %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return request, err
}



// DeleteObject makes a presigned request that can be used to delete an object from
 a bucket.
func (presigner Presigner) DeleteObject(bucketName string, objectKey string)
 (*v4.PresignedHTTPRequest, error) {
 request, err := presigner.PresignClient.PresignDeleteObject(context.TODO(),
 &s3.DeleteObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
```

```
 if err != nil {
  log.Printf("Couldn't get a presigned request to delete object %v. Here's why: %v
\n", objectKey, err)
 }
 return request, err
}
```

Execute um exemplo interativo que gera e usa URLs pré-assinados para fazer upload, fazer download e excluir um objeto do S3.

```
// RunPresigningScenario is an interactive example that shows you how to get
 presigned
// HTTP requests that you can use to move data into and out of Amazon Simple Storage
// Service (Amazon S3). The presigned requests contain temporary credentials and can
// be used by an HTTP client.
//
// 1. Get a presigned request to put an object in a bucket.
// 2. Use the net/http package to use the presigned request to upload a local file
 to the bucket.
// 3. Get a presigned request to get an object from a bucket.
// 4. Use the net/http package to use the presigned request to download the object
 to a local file.
// 5. Get a presigned request to delete an object from a bucket.
// 6. Use the net/http package to use the presigned request to delete the object.
//
// This example creates an Amazon S3 presign client from the specified sdkConfig so
 that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
//
// It uses an IHttpRequester interface to abstract HTTP requests so they can be
 mocked
// during testing.
func RunPresigningScenario(sdkConfig aws.Config, questioner demotools.IQuestioner,
 httpRequester IHttpRequester) {
 defer func() {
  if r := recover(); r != nil {
```

```
  fmt.Printf("Something went wrong with the demo.")
 }
}()

log.Println(strings.Repeat("-", 88))
log.Println("Welcome to the Amazon S3 presigning demo.")
log.Println(strings.Repeat("-", 88))

s3Client := s3.NewFromConfig(sdkConfig)
bucketBasics := actions.BucketBasics{S3Client: s3Client}
presignClient := s3.NewPresignClient(s3Client)
presigner := actions.Presigner{PresignClient: presignClient}

bucketName := questioner.Ask("We'll need a bucket. Enter a name for a bucket "+
 "you own or one you want to create:", demotools.NotEmpty{})
bucketExists, err := bucketBasics.BucketExists(bucketName)
if err != nil {
 panic(err)
}
if !bucketExists {
 err = bucketBasics.CreateBucket(bucketName, sdkConfig.Region)
 if err != nil {
  panic(err)
 } else {
  log.Println("Bucket created.")
 }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's presign a request to upload a file to your bucket.")
uploadFilename := questioner.Ask("Enter the path to a file you want to upload:",
 demotools.NotEmpty{})
uploadKey := questioner.Ask("What would you like to name the uploaded object?",
 demotools.NotEmpty{})
uploadFile, err := os.Open(uploadFilename)
if err != nil {
 panic(err)
}
defer uploadFile.Close()
presignedPutRequest, err := presigner.PutObject(bucketName, uploadKey, 60)
if err != nil {
 panic(err)
}
```

```
log.Printf("Got a presigned %v request to URL:\n\t%v\n",
presignedPutRequest.Method,
 presignedPutRequest.URL)
log.Println("Using net/http to send the request...")
info, err := uploadFile.Stat()
if err != nil {
 panic(err)
}
putResponse, err := httpRequester.Put(presignedPutRequest.URL, info.Size(),
uploadFile)
if err != nil {
 panic(err)
}
log.Printf("%v object %v with presigned URL returned %v.",
presignedPutRequest.Method,
 uploadKey, putResponse.StatusCode)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's presign a request to download the object.")
questioner.Ask("Press Enter when you're ready.")
presignedGetRequest, err := presigner.GetObject(bucketName, uploadKey, 60)
if err != nil {
 panic(err)
}
log.Printf("Got a presigned %v request to URL:\n\t%v\n",
presignedGetRequest.Method,
 presignedGetRequest.URL)
log.Println("Using net/http to send the request...")
getResponse, err := httpRequester.Get(presignedGetRequest.URL)
if err != nil {
 panic(err)
}
log.Printf("%v object %v with presigned URL returned %v.",
presignedGetRequest.Method,
 uploadKey, getResponse.StatusCode)
defer getResponse.Body.Close()
downloadBody, err := io.ReadAll(getResponse.Body)
if err != nil {
 panic(err)
}
log.Printf("Downloaded %v bytes. Here are the first 100 of them:\n",
len(downloadBody))
log.Println(strings.Repeat("-", 88))
log.Println(string(downloadBody[:100]))
```

```
 log.Println(strings.Repeat("-", 88))

 log.Println("Let's presign a request to delete the object.")
 questioner.Ask("Press Enter when you're ready.")
 presignedDelRequest, err := presigner.DeleteObject(bucketName, uploadKey)
 if err != nil {
  panic(err)
 }
 log.Printf("Got a presigned %v request to URL:\n\t%v\n",
 presignedDelRequest.Method,
  presignedDelRequest.URL)
 log.Println("Using net/http to send the request...")
 delResponse, err := httpRequester.Delete(presignedDelRequest.URL)
 if err != nil {
  panic(err)
 }
 log.Printf("%v object %v with presigned URL returned %v.\n",
 presignedDelRequest.Method,
  uploadKey, delResponse.StatusCode)
 log.Println(strings.Repeat("-", 88))

 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina um wrapper de solicitação HTTP usado pelo exemplo para fazer solicitações HTTP.

```
// IHttpRequester abstracts HTTP requests into an interface so it can be mocked
 during
// unit testing.
type IHttpRequester interface {
 Get(url string) (resp *http.Response, err error)
 Put(url string, contentLength int64, body io.Reader) (resp *http.Response, err
 error)
 Delete(url string) (resp *http.Response, err error)
}

// HttpRequester uses the net/http package to make HTTP requests during the
 scenario.
type HttpRequester struct{}
```

```
func (httpReq HttpRequester) Get(url string) (resp *http.Response, err error) {
 return http.Get(url)
}
func (httpReq HttpRequester) Put(url string, contentLength int64, body io.Reader)
 (resp *http.Response, err error) {
 putRequest, err := http.NewRequest("PUT", url, body)
 if err != nil {
  return nil, err
 }
 putRequest.ContentLength = contentLength
 return http.DefaultClient.Do(putRequest)
}
func (httpReq HttpRequester) Delete(url string) (resp *http.Response, err error) {
 delRequest, err := http.NewRequest("DELETE", url, nil)
 if err != nil {
  return nil, err
 }
 return http.DefaultClient.Do(delRequest)
}
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina um struct que envolva as ações de bucket e objeto usadas pelo cenário.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// ListBuckets lists the buckets in the current account.
func (basics BucketBasics) ListBuckets() ([]types.Bucket, error) {
 result, err := basics.S3Client.ListBuckets(context.TODO(), &s3.ListBucketsInput{})
 var buckets []types.Bucket
 if err != nil {
  log.Printf("Couldn't list buckets for your account. Here's why: %v\n", err)
 } else {
  buckets = result.Buckets
 }
 return buckets, err
}



// BucketExists checks whether a bucket exists in the current account.
func (basics BucketBasics) BucketExists(bucketName string) (bool, error) {
 _, err := basics.S3Client.HeadBucket(context.TODO(), &s3.HeadBucketInput{
  Bucket: aws.String(bucketName),
 })
 exists := true
 if err != nil {
  var apiError smithy.APIError
  if errors.As(err, &apiError) {
   switch apiError.(type) {
   case *types.NotFound:
    log.Printf("Bucket %v is available.\n", bucketName)
    exists = false
    err = nil
   default:
    log.Printf("Either you don't have access to bucket %v or another error occurred.
 "+
```

```
      "Here's what happened: %v\n", bucketName, err)
    }
   }
  } else {
   log.Printf("Bucket %v exists and you already own it.", bucketName)
  }

  return exists, err
}



// CreateBucket creates a bucket with the specified name in the specified Region.
func (basics BucketBasics) CreateBucket(name string, region string) error {
  _, err := basics.S3Client.CreateBucket(context.TODO(), &s3.CreateBucketInput{
   Bucket: aws.String(name),
   CreateBucketConfiguration: &types.CreateBucketConfiguration{
    LocationConstraint: types.BucketLocationConstraint(region),
   },
  })
  if err != nil {
   log.Printf("Couldn't create bucket %v in Region %v. Here's why: %v\n",
    name, region, err)
  }
  return err
}



// UploadFile reads from a file and puts the data into an object in a bucket.
func (basics BucketBasics) UploadFile(bucketName string, objectKey string, fileName
 string) error {
  file, err := os.Open(fileName)
  if err != nil {
   log.Printf("Couldn't open file %v to upload. Here's why: %v\n", fileName, err)
  } else {
   defer file.Close()
   _, err = basics.S3Client.PutObject(context.TODO(), &s3.PutObjectInput{
    Bucket: aws.String(bucketName),
    Key:    aws.String(objectKey),
    Body:   file,
   })
   if err != nil {
    log.Printf("Couldn't upload file %v to %v:%v. Here's why: %v\n",
```

```
    fileName, bucketName, objectKey, err)
  }
 }
 return err
}



// UploadLargeObject uses an upload manager to upload data to an object in a bucket.
// The upload manager breaks large data into parts and uploads the parts
 concurrently.
func (basics BucketBasics) UploadLargeObject(bucketName string, objectKey string,
 largeObject []byte) error {
 largeBuffer := bytes.NewReader(largeObject)
 var partMiBs int64 = 10
 uploader := manager.NewUploader(basics.S3Client, func(u *manager.Uploader) {
  u.PartSize = partMiBs * 1024 * 1024
 })
 _, err := uploader.Upload(context.TODO(), &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
  Body:   largeBuffer,
 })
 if err != nil {
  log.Printf("Couldn't upload large object to %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }

 return err
}



// DownloadFile gets an object from a bucket and stores it in a local file.
func (basics BucketBasics) DownloadFile(bucketName string, objectKey string,
 fileName string) error {
 result, err := basics.S3Client.GetObject(context.TODO(), &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't get object %v:%v. Here's why: %v\n", bucketName, objectKey,
 err)
  return err
```

```
 }
 defer result.Body.Close()
 file, err := os.Create(fileName)
 if err != nil {
  log.Printf("Couldn't create file %v. Here's why: %v\n", fileName, err)
  return err
 }
 defer file.Close()
 body, err := io.ReadAll(result.Body)
 if err != nil {
  log.Printf("Couldn't read object body from %v. Here's why: %v\n", objectKey, err)
 }
 _, err = file.Write(body)
 return err
}



// DownloadLargeObject uses a download manager to download an object from a bucket.
// The download manager gets the data in parts and writes them to a buffer until all
 of
// the data has been downloaded.
func (basics BucketBasics) DownloadLargeObject(bucketName string, objectKey string)
 ([]byte, error) {
 var partMiBs int64 = 10
 downloader := manager.NewDownloader(basics.S3Client, func(d *manager.Downloader) {
  d.PartSize = partMiBs * 1024 * 1024
 })
 buffer := manager.NewWriteAtBuffer([]byte{})
 _, err := downloader.Download(context.TODO(), buffer, &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't download large object from %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
 return buffer.Bytes(), err
}



// CopyToFolder copies an object in a bucket to a subfolder in the same bucket.
```

```
func (basics BucketBasics) CopyToFolder(bucketName string, objectKey string,
 folderName string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(bucketName),
  CopySource: aws.String(fmt.Sprintf("%v/%v", bucketName, objectKey)),
  Key:        aws.String(fmt.Sprintf("%v/%v", folderName, objectKey)),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v/%v. Here's why: %v\n",
   bucketName, objectKey, bucketName, folderName, objectKey, err)
 }
 return err
}



// CopyToBucket copies an object in a bucket to another bucket.
func (basics BucketBasics) CopyToBucket(sourceBucket string, destinationBucket
 string, objectKey string) error {
 _, err := basics.S3Client.CopyObject(context.TODO(), &s3.CopyObjectInput{
  Bucket:     aws.String(destinationBucket),
  CopySource: aws.String(fmt.Sprintf("%v/%v", sourceBucket, objectKey)),
  Key:        aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't copy object from %v:%v to %v:%v. Here's why: %v\n",
   sourceBucket, objectKey, destinationBucket, objectKey, err)
 }
 return err
}



// ListObjects lists the objects in a bucket.
func (basics BucketBasics) ListObjects(bucketName string) ([]types.Object, error) {
 result, err := basics.S3Client.ListObjectsV2(context.TODO(),
 &s3.ListObjectsV2Input{
  Bucket: aws.String(bucketName),
 })
 var contents []types.Object
 if err != nil {
  log.Printf("Couldn't list objects in bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
```

```
  contents = result.Contents
 }
 return contents, err
}



// DeleteObjects deletes a list of objects from a bucket.
func (basics BucketBasics) DeleteObjects(bucketName string, objectKeys []string)
 error {
 var objectIds []types.ObjectIdentifier
 for _, key := range objectKeys {
  objectIds = append(objectIds, types.ObjectIdentifier{Key: aws.String(key)})
 }
 output, err := basics.S3Client.DeleteObjects(context.TODO(),
 &s3.DeleteObjectsInput{
  Bucket: aws.String(bucketName),
  Delete: &types.Delete{Objects: objectIds},
 })
 if err != nil {
  log.Printf("Couldn't delete objects from bucket %v. Here's why: %v\n", bucketName,
 err)
 } else {
  log.Printf("Deleted %v objects.\n", len(output.Deleted))
 }
 return err
}



// DeleteBucket deletes a bucket. The bucket must be empty or an error is returned.
func (basics BucketBasics) DeleteBucket(bucketName string) error {
 _, err := basics.S3Client.DeleteBucket(context.TODO(), &s3.DeleteBucketInput{
  Bucket: aws.String(bucketName)})
 if err != nil {
  log.Printf("Couldn't delete bucket %v. Here's why: %v\n", bucketName, err)
 }
 return err
}
```

Execute um cenário interativo que mostre como trabalhar com buckets e objetos do S3.

```
// RunGetStartedScenario is an interactive example that shows you how to use Amazon
// Simple Storage Service (Amazon S3) to create an S3 bucket and use it to store
 objects.
//
// 1. Create a bucket.
// 2. Upload a local file to the bucket.
// 3. Upload a large object to the bucket by using an upload manager.
// 4. Download an object to a local file.
// 5. Download a large object by using a download manager.
// 6. Copy an object to a different folder in the bucket.
// 7. List objects in the bucket.
// 8. Delete all objects in the bucket.
// 9. Delete the bucket.
//
// This example creates an Amazon S3 service client from the specified sdkConfig so
 that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
func RunGetStartedScenario(sdkConfig aws.Config, questioner demotools.IQuestioner) {
 defer func() {
  if r := recover(); r != nil {
   fmt.Println("Something went wrong with the demo.\n", r)
  }
 }()

 log.Println(strings.Repeat("-", 88))
 log.Println("Welcome to the Amazon S3 getting started demo.")
 log.Println(strings.Repeat("-", 88))

 s3Client := s3.NewFromConfig(sdkConfig)
 bucketBasics := actions.BucketBasics{S3Client: s3Client}

 count := 10
 log.Printf("Let's list up to %v buckets for your account:", count)
 buckets, err := bucketBasics.ListBuckets()
 if err != nil {
  panic(err)
 }
 if len(buckets) == 0 {
```

```
 log.Println("You don't have any buckets!")
} else {
 if count > len(buckets) {
  count = len(buckets)
 }
 for _, bucket := range buckets[:count] {
  log.Printf("\t%v\n", *bucket.Name)
 }
}

bucketName := questioner.Ask("Let's create a bucket. Enter a name for your
bucket:",
 demotools.NotEmpty{})
bucketExists, err := bucketBasics.BucketExists(bucketName)
if err != nil {
 panic(err)
}
if !bucketExists {
 err = bucketBasics.CreateBucket(bucketName, sdkConfig.Region)
 if err != nil {
  panic(err)
 } else {
  log.Println("Bucket created.")
 }
}
log.Println(strings.Repeat("-", 88))

fmt.Println("Let's upload a file to your bucket.")
smallFile := questioner.Ask("Enter the path to a file you want to upload:",
 demotools.NotEmpty{})
const smallKey = "doc-example-key"
err = bucketBasics.UploadFile(bucketName, smallKey, smallFile)
if err != nil {
 panic(err)
}
log.Printf("Uploaded %v as %v.\n", smallFile, smallKey)
log.Println(strings.Repeat("-", 88))

mibs := 30
log.Printf("Let's create a slice of %v MiB of random bytes and upload it to your
bucket. ", mibs)
questioner.Ask("Press Enter when you're ready.")
largeBytes := make([]byte, 1024*1024*mibs)
rand.Seed(time.Now().Unix())
```

```
rand.Read(largeBytes)
largeKey := "doc-example-large"
log.Println("Uploading...")
err = bucketBasics.UploadLargeObject(bucketName, largeKey, largeBytes)
if err != nil {
 panic(err)
}
log.Printf("Uploaded %v MiB object as %v", mibs, largeKey)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's download %v to a file.", smallKey)
downloadFileName := questioner.Ask("Enter a name for the downloaded file:",
demotools.NotEmpty{})
err = bucketBasics.DownloadFile(bucketName, smallKey, downloadFileName)
if err != nil {
 panic(err)
}
log.Printf("File %v downloaded.", downloadFileName)
log.Println(strings.Repeat("-", 88))

log.Printf("Let's download the %v MiB object.", mibs)
questioner.Ask("Press Enter when you're ready.")
log.Println("Downloading...")
largeDownload, err := bucketBasics.DownloadLargeObject(bucketName, largeKey)
if err != nil {
 panic(err)
}
log.Printf("Downloaded %v bytes.", len(largeDownload))
log.Println(strings.Repeat("-", 88))

log.Printf("Let's copy %v to a folder in the same bucket.", smallKey)
folderName := questioner.Ask("Enter a folder name: ", demotools.NotEmpty{})
err = bucketBasics.CopyToFolder(bucketName, smallKey, folderName)
if err != nil {
 panic(err)
}
log.Printf("Copied %v to %v/%v.\n", smallKey, folderName, smallKey)
log.Println(strings.Repeat("-", 88))

log.Println("Let's list the objects in your bucket.")
questioner.Ask("Press Enter when you're ready.")
objects, err := bucketBasics.ListObjects(bucketName)
if err != nil {
 panic(err)
```

```
 }
 log.Printf("Found %v objects.\n", len(objects))
 var objKeys []string
 for _, object := range objects {
  objKeys = append(objKeys, *object.Key)
  log.Printf("\t%v\n", *object.Key)
 }
 log.Println(strings.Repeat("-", 88))

 if questioner.AskBool("Do you want to delete your bucket and all of its "+
  "contents? (y/n)", "y") {
  log.Println("Deleting objects.")
  err = bucketBasics.DeleteObjects(bucketName, objKeys)
  if err != nil {
   panic(err)
  }
  log.Println("Deleting bucket.")
  err = bucketBasics.DeleteBucket(bucketName)
  if err != nil {
   panic(err)
  }
  log.Printf("Deleting downloaded file %v.\n", downloadFileName)
  err = os.Remove(downloadFileName)
  if err != nil {
   panic(err)
  }
 } else {
  log.Println("Okay. Don't forget to delete objects from your bucket to avoid
 charges.")
 }
 log.Println(strings.Repeat("-", 88))

 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CopyObject
  - CreateBucket

- DeleteBucket
- DeleteObjects
- GetObject
- ListObjectsV2
- PutObject

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

SDK for Go V2

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um objeto grande usando um gerenciador de uploads para dividir os dados em partes e fazer upload delas simultaneamente.

```
// BucketBasics encapsulates the Amazon Simple Storage Service (Amazon S3) actions
// used in the examples.
// It contains S3Client, an Amazon S3 service client that is used to perform bucket
// and object actions.
type BucketBasics struct {
 S3Client *s3.Client
}



// UploadLargeObject uses an upload manager to upload data to an object in a bucket.
// The upload manager breaks large data into parts and uploads the parts
 concurrently.
func (basics BucketBasics) UploadLargeObject(bucketName string, objectKey string,
 largeObject []byte) error {
```

```
 largeBuffer := bytes.NewReader(largeObject)
 var partMiBs int64 = 10
 uploader := manager.NewUploader(basics.S3Client, func(u *manager.Uploader) {
  u.PartSize = partMiBs * 1024 * 1024
 })
 _, err := uploader.Upload(context.TODO(), &s3.PutObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
  Body:   largeBuffer,
 })
 if err != nil {
  log.Printf("Couldn't upload large object to %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }

 return err
}
```

Faça download de um objeto grande usando um gerenciador de downloads para obter os dados em partes e baixá-las simultaneamente.

```
// DownloadLargeObject uses a download manager to download an object from a bucket.
// The download manager gets the data in parts and writes them to a buffer until all
 of
// the data has been downloaded.
func (basics BucketBasics) DownloadLargeObject(bucketName string, objectKey string)
 ([]byte, error) {
 var partMiBs int64 = 10
 downloader := manager.NewDownloader(basics.S3Client, func(d *manager.Downloader) {
  d.PartSize = partMiBs * 1024 * 1024
 })
 buffer := manager.NewWriteAtBuffer([]byte{})
 _, err := downloader.Download(context.TODO(), buffer, &s3.GetObjectInput{
  Bucket: aws.String(bucketName),
  Key:    aws.String(objectKey),
 })
 if err != nil {
  log.Printf("Couldn't download large object from %v:%v. Here's why: %v\n",
   bucketName, objectKey, err)
 }
```

```
 return buffer.Bytes(), err
}
```

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Go.

```
package main

import (
 "context"
 "log"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/s3"
)

func handler(ctx context.Context, s3Event events.S3Event) error {
 sdkConfig, err := config.LoadDefaultConfig(ctx)
 if err != nil {
  log.Printf("failed to load default config: %s", err)
  return err
```

```
 }
 s3Client := s3.NewFromConfig(sdkConfig)

 for _, record := range s3Event.Records {
  bucket := record.S3.Bucket.Name
  key := record.S3.Object.URLDecodedKey
  headOutput, err := s3Client.HeadObject(ctx, &s3.HeadObjectInput{
   Bucket: &bucket,
   Key:    &key,
  })
  if err != nil {
   log.Printf("error getting head of object %s/%s: %s", bucket, key, err)
   return err
  }
  log.Printf("successfully retrieved %s/%s of type %s", bucket, key,
 *headOutput.ContentType)
 }

 return nil
}

func main() {
 lambda.Start(handler)
}
```

Exemplos de código para o Amazon SNS usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sns"
 "github.com/aws/aws-sdk-go-v2/service/sns/types"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Notification Service
// (Amazon SNS) client and list the topics in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 snsClient := sns.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the topics for your account.")
 var topics []types.Topic
 paginator := sns.NewListTopicsPaginator(snsClient, &sns.ListTopicsInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
```

```
  if err != nil {
   log.Printf("Couldn't get topics. Here's why: %v\n", err)
   break
  } else {
   topics = append(topics, output.Topics...)
  }
 }
 if len(topics) == 0 {
  fmt.Println("You don't have any topics!")
 } else {
  for _, topic := range topics {
   fmt.Printf("\t%v\n", *topic.TopicArn)
  }
 }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar um tópico

Os exemplos de código a seguir mostram como criar um tópico do Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Go da API.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for Go da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sns"
 "github.com/aws/aws-sdk-go-v2/service/sns/types"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Notification Service
// (Amazon SNS) client and list the topics in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 snsClient := sns.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the topics for your account.")
 var topics []types.Topic
 paginator := sns.NewListTopicsPaginator(snsClient, &sns.ListTopicsInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get topics. Here's why: %v\n", err)
   break
```

```
  } else {
   topics = append(topics, output.Topics...)
  }
 }
 if len(topics) == 0 {
  fmt.Println("You don't have any topics!")
 } else {
  for _, topic := range topics {
   fmt.Printf("\t%v\n", *topic.TopicArn)
  }
 }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Go da API.

Publicar uma mensagem com um atributo

O exemplo de código a seguir mostra como publicar uma mensagem com um atributo usando o Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent to
 all
```

```
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered according
 to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Go.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent to
 all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered according
 to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
```

```
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Go.

Assinar uma fila do SQS em um tópico

O exemplo de código a seguir mostra como inscrever uma fila do Amazon SQS para receber notificações de um tópico do Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string, filterMap
 map[string][]string) (string, error) {
```

```
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Go.

Assinar com um filtro em um tópico

O exemplo de código a seguir mostra como assinar com um filtro um tópico do Amazon SNS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string, filterMap
 map[string][]string) (string, error) {
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Go.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
const FIFO_SUFFIX = ".fifo"
const TONE_KEY = "tone"

var ToneChoices = []string{"cheerful", "funny", "serious", "sincere"}

// MessageBody is used to deserialize the body of a message from a JSON string.
type MessageBody struct {
 Message string
}

// ScenarioRunner separates the steps of this scenario into individual functions so
 that
// they are simpler to read and understand.
```

```
type ScenarioRunner struct {
 questioner demotools.IQuestioner
 snsActor   *actions.SnsActions
 sqsActor   *actions.SqsActions
}

func (runner ScenarioRunner) CreateTopic() (string, string, bool, bool) {
 log.Println("SNS topics can be configured as FIFO (First-In-First-Out) or standard.
\n" +
  "FIFO topics deliver messages in order and support deduplication and message
 filtering.")
 isFifoTopic := runner.questioner.AskBool("\nWould you like to work with FIFO
 topics? (y/n) ", "y")

 contentBasedDeduplication := false
 if isFifoTopic {
  log.Println(strings.Repeat("-", 88))
  log.Println("Because you have chosen a FIFO topic, deduplication is supported.\n"
 +
   "Deduplication IDs are either set in the message or are automatically generated
\n" +
   "from content using a hash function. If a message is successfully published to\n"
 +
   "an SNS FIFO topic, any message published and determined to have the same\n" +
   "deduplication ID, within the five-minute deduplication interval, is accepted\n"
 +
   "but not delivered. For more information about deduplication, see:\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/fifo-message-dedup.html.")
  contentBasedDeduplication = runner.questioner.AskBool(
   "\nDo you want to use content-based deduplication instead of entering a
 deduplication ID? (y/n) ", "y")
 }
 log.Println(strings.Repeat("-", 88))

 topicName := runner.questioner.Ask("Enter a name for your SNS topic. ")
 if isFifoTopic {
  topicName = fmt.Sprintf("%v%v", topicName, FIFO_SUFFIX)
  log.Printf("Because you have selected a FIFO topic, '%v' must be appended to\n"+
   "the topic name.", FIFO_SUFFIX)
 }

 topicArn, err := runner.snsActor.CreateTopic(topicName, isFifoTopic,
 contentBasedDeduplication)
 if err != nil {
```

```
  panic(err)
 }
 log.Printf("Your new topic with the name '%v' and Amazon Resource Name (ARN) \n"+
  "'%v' has been created.", topicName, topicArn)

 return topicName, topicArn, isFifoTopic, contentBasedDeduplication
}

func (runner ScenarioRunner) CreateQueue(ordinal string, isFifoTopic bool) (string,
 string) {
 queueName := runner.questioner.Ask(fmt.Sprintf("Enter a name for the %v SQS queue.
 ", ordinal))
 if isFifoTopic {
  queueName = fmt.Sprintf("%v%v", queueName, FIFO_SUFFIX)
  if ordinal == "first" {
   log.Printf("Because you are creating a FIFO SQS queue, '%v' must "+
    "be appended to the queue name.\n", FIFO_SUFFIX)
  }
 }
 queueUrl, err := runner.sqsActor.CreateQueue(queueName, isFifoTopic)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new SQS queue with the name '%v' and the queue URL "+
  "'%v' has been created.", queueName, queueUrl)

 return queueName, queueUrl
}

func (runner ScenarioRunner) SubscribeQueueToTopic(
 queueName string, queueUrl string, topicName string, topicArn string, ordinal
 string,
 isFifoTopic bool) (string, bool) {

 queueArn, err := runner.sqsActor.GetQueueArn(queueUrl)
 if err != nil {
  panic(err)
 }
 log.Printf("The ARN of your queue is: %v.\n", queueArn)

 err = runner.sqsActor.AttachSendMessagePolicy(queueUrl, queueArn, topicArn)
 if err != nil {
  panic(err)
 }
```

```
log.Println("Attached an IAM policy to the queue so the SNS topic can send " +
 "messages to it.")
log.Println(strings.Repeat("-", 88))

var filterPolicy map[string][]string
if isFifoTopic {
 if ordinal == "first" {
  log.Println("Subscriptions to a FIFO topic can have filters.\n" +
   "If you add a filter to this subscription, then only the filtered messages\n" +
   "will be received in the queue.\n" +
   "For information about message filtering, see\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/sns-message-filtering.html\n" +
   "For this example, you can filter messages by a \"tone\" attribute.")
 }

 wantFiltering := runner.questioner.AskBool(
  fmt.Sprintf("Do you want to filter messages that are sent to \"%v\"\n"+
   "from the %v topic? (y/n) ", queueName, topicName), "y")
 if wantFiltering {
  log.Println("You can filter messages by one or more of the following \"tone\"
attributes.")

  var toneSelections []string
  askAboutTones := true
  for askAboutTones {
   toneIndex := runner.questioner.AskChoice(
    "Enter the number of the tone you want to filter by:\n", ToneChoices)
   toneSelections = append(toneSelections, ToneChoices[toneIndex])
   askAboutTones = runner.questioner.AskBool("Do you want to add another tone to
the filter? (y/n) ", "y")
  }
  log.Printf("Your subscription will be filtered to only pass the following tones:
%v\n", toneSelections)
  filterPolicy = map[string][]string{TONE_KEY: toneSelections}
 }
}

subscriptionArn, err := runner.snsActor.SubscribeQueue(topicArn, queueArn,
filterPolicy)
if err != nil {
 panic(err)
}
log.Printf("The queue %v is now subscribed to the topic %v with the subscription
ARN %v.\n",
```

```
  queueName, topicName, subscriptionArn)

 return subscriptionArn, filterPolicy != nil
}

func (runner ScenarioRunner) PublishMessages(topicArn string, isFifoTopic bool,
 contentBasedDeduplication bool, usingFilters bool) {
 var message string
 var groupId string
 var dedupId string
 var toneSelection string
 publishMore := true
 for publishMore {
  groupId = ""
  dedupId = ""
  toneSelection = ""
  message = runner.questioner.Ask("Enter a message to publish: ")
  if isFifoTopic {
   log.Println("Because you are using a FIFO topic, you must set a message group ID.
\n" +
    "All messages within the same group will be received in the order they were
 published.")
   groupId = runner.questioner.Ask("Enter a message group ID: ")
   if !contentBasedDeduplication {
    log.Println("Because you are not using content-based deduplication,\n" +
     "you must enter a deduplication ID.")
    dedupId = runner.questioner.Ask("Enter a deduplication ID: ")
   }
  }
  if usingFilters {
   if runner.questioner.AskBool("Add a tone attribute so this message can be
 filtered? (y/n) ", "y") {
    toneIndex := runner.questioner.AskChoice(
     "Enter the number of the tone you want to filter by:\n", ToneChoices)
    toneSelection = ToneChoices[toneIndex]
   }
  }

  err := runner.snsActor.Publish(topicArn, message, groupId, dedupId, TONE_KEY,
 toneSelection)
  if err != nil {
   panic(err)
  }
  log.Println(("Your message was published."))
```

```
  publishMore = runner.questioner.AskBool("Do you want to publish another messsage?
 (y/n) ", "y")
 }
}

func (runner ScenarioRunner) PollForMessages(queueUrls []string) {
 log.Println("Polling queues for messages...")
 for _, queueUrl := range queueUrls {
  var messages []types.Message
  for {
   currentMsgs, err := runner.sqsActor.GetMessages(queueUrl, 10, 1)
   if err != nil {
    panic(err)
   }
   if len(currentMsgs) == 0 {
    break
   }
   messages = append(messages, currentMsgs...)
  }
  if len(messages) == 0 {
   log.Printf("No messages were received by queue %v.\n", queueUrl)
  } else if len(messages) == 1 {
   log.Printf("One message was received by queue %v:\n", queueUrl)

  } else {
   log.Printf("%v messages were received by queue %v:\n", len(messages), queueUrl)
  }
  for msgIndex, message := range messages {
   messageBody := MessageBody{}
   err := json.Unmarshal([]byte(*message.Body), &messageBody)
   if err != nil {
    panic(err)
   }
   log.Printf("Message %v: %v\n", msgIndex+1, messageBody.Message)
  }

  if len(messages) > 0 {
   log.Printf("Deleting %v messages from queue %v.\n", len(messages), queueUrl)
   err := runner.sqsActor.DeleteMessages(queueUrl, messages)
   if err != nil {
    panic(err)
   }
  }
```

```
 }
}

// RunTopicsAndQueuesScenario is an interactive example that shows you how to use
 the
// AWS SDK for Go to create and use Amazon SNS topics and Amazon SQS queues.
//
// 1. Create a topic (FIFO or non-FIFO).
// 2. Subscribe several queues to the topic with an option to apply a filter.
// 3. Publish messages to the topic.
// 4. Poll the queues for messages received.
// 5. Delete the topic and the queues.
//
// This example creates service clients from the specified sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
func RunTopicsAndQueuesScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner) {
 resources := Resources{}
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.\n" +
    "Cleaning up any resources that were created...")
   resources.Cleanup()
  }
 }()
 queueCount := 2

 log.Println(strings.Repeat("-", 88))
 log.Printf("Welcome to messaging with topics and queues.\n\n"+
  "In this workflow, you will create an SNS topic and subscribe %v SQS queues to the
\n"+
  "topic. You can select from several options for configuring the topic and the\n"+
  "subscriptions for the queues. You can then post to the topic and see the results
\n"+
  "in the queues.\n", queueCount)

 log.Println(strings.Repeat("-", 88))

 runner := ScenarioRunner{
  questioner: questioner,
```

```
  snsActor:   &actions.SnsActions{SnsClient: sns.NewFromConfig(sdkConfig)},
  sqsActor:   &actions.SqsActions{SqsClient: sqs.NewFromConfig(sdkConfig)},
 }
 resources.snsActor = runner.snsActor
 resources.sqsActor = runner.sqsActor

 topicName, topicArn, isFifoTopic, contentBasedDeduplication := runner.CreateTopic()
 resources.topicArn = topicArn
 log.Println(strings.Repeat("-", 88))

 log.Printf("Now you will create %v SQS queues and subscribe them to the topic.\n",
 queueCount)
 ordinals := []string{"first", "next"}
 usingFilters := false
 for _, ordinal := range ordinals {
  queueName, queueUrl := runner.CreateQueue(ordinal, isFifoTopic)
  resources.queueUrls = append(resources.queueUrls, queueUrl)

  _, filtering := runner.SubscribeQueueToTopic(queueName, queueUrl, topicName,
 topicArn, ordinal, isFifoTopic)
  usingFilters = usingFilters || filtering
 }

 log.Println(strings.Repeat("-", 88))
 runner.PublishMessages(topicArn, isFifoTopic, contentBasedDeduplication,
 usingFilters)
 log.Println(strings.Repeat("-", 88))
 runner.PollForMessages(resources.queueUrls)

 log.Println(strings.Repeat("-", 88))

 wantCleanup := questioner.AskBool("Do you want to remove all AWS resources created
 for this scenario? (y/n) ", "y")
 if wantCleanup {
  log.Println("Cleaning up resources...")
  resources.Cleanup()
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura que envolva as ações do Amazon SNS usadas neste exemplo.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}
```

```
// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string, filterMap
 map[string][]string) (string, error) {
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }
```

```
 return subscriptionArn, err
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent to
 all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered according
 to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn, err)
 }
 return err
}
```

Defina uma estrutura que envolva as ações do Amazon SQS usadas neste exemplo.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
```

```
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// CreateQueue creates an Amazon SQS queue with the specified name. You can specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
}



// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
// of an Amazon SQS queue.
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
```

```
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}



// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy to
 an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages to
 the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
  Attributes: map[string]string{
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}
```

```
// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
 if err != nil {
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  messages = result.Messages
 }
 return messages, err
}
```

```
// DeleteMessages uses the DeleteMessageBatch action to delete a batch of messages
 from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 }
 return err
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue

- DeleteTopic
- GetQueueAttributes
- Publicar
- ReceiveMessage
- SetQueueAttributes
- Assinar
- Cancelar assinatura

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Go.

```
package main

import (
 "context"
 "fmt"

 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, snsEvent events.SNSEvent) {
 for _, record := range snsEvent.Records {
```

```
  processMessage(record)
 }
 fmt.Println("done")
}

func processMessage(record events.SNSEventRecord) {
 message := record.SNS.Message
 fmt.Printf("Processed message: %s\n", message)
 // TODO: Process your record here
}

func main() {
 lambda.Start(handler)
}
```

Exemplos do Amazon SQS usando SDK para Go V2

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando V2 AWS SDK for Go com Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sqs"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Queue Service
// (Amazon SQS) client and list the queues in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 sqsClient := sqs.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the queues for your account.")
 var queueUrls []string
 paginator := sqs.NewListQueuesPaginator(sqsClient, &sqs.ListQueuesInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
   log.Printf("Couldn't get queues. Here's why: %v\n", err)
   break
  } else {
```

```
    queueUrls = append(queueUrls, output.QueueUrls...)
   }
  }
  if len(queueUrls) == 0 {
   fmt.Println("You don't have any queues!")
  } else {
   for _, queueUrl := range queueUrls {
    fmt.Printf("\t%v\n", queueUrl)
   }
  }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Go da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma fila

Os exemplos de código a seguir mostram como criar uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
```

```
}



// CreateQueue creates an Amazon SQS queue with the specified name. You can specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Go da API.

Excluir um lote de mensagens de uma fila

O exemplo de código a seguir mostra como excluir um lote de mensagens de uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// DeleteMessages uses the DeleteMessageBatch action to delete a batch of messages
 from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for Go da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Go da API.

Obter atributos para uma fila

O exemplo de código a seguir mostra como obter atributos para uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
// of an Amazon SQS queue.
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for Go da API.

Listar filas

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package main

import (
 "context"
 "fmt"
 "log"

 "github.com/aws/aws-sdk-go-v2/config"
 "github.com/aws/aws-sdk-go-v2/service/sqs"
)

// main uses the AWS SDK for Go V2 to create an Amazon Simple Queue Service
// (Amazon SQS) client and list the queues in your account.
// This example uses the default settings specified in your shared credentials
// and config files.
func main() {
 sdkConfig, err := config.LoadDefaultConfig(context.TODO())
 if err != nil {
  fmt.Println("Couldn't load default configuration. Have you set up your AWS
 account?")
  fmt.Println(err)
  return
 }
 sqsClient := sqs.NewFromConfig(sdkConfig)
 fmt.Println("Let's list the queues for your account.")
 var queueUrls []string
 paginator := sqs.NewListQueuesPaginator(sqsClient, &sqs.ListQueuesInput{})
 for paginator.HasMorePages() {
  output, err := paginator.NextPage(context.TODO())
  if err != nil {
```

```
    log.Printf("Couldn't get queues. Here's why: %v\n", err)
    break
   } else {
    queueUrls = append(queueUrls, output.QueueUrls...)
   }
  }
  if len(queueUrls) == 0 {
   fmt.Println("You don't have any queues!")
  } else {
   for _, queueUrl := range queueUrls {
    fmt.Printf("\t%v\n", queueUrl)
   }
  }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Go da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
```

```
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
 if err != nil {
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  messages = result.Messages
 }
 return messages, err
}
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Go da API.

Definir atributos de fila

O exemplo de código a seguir mostra como definir os atributos para uma fila do Amazon SQS.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}
```

```
// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy to
 an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages to
 the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
  Attributes: map[string]string{
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}

// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
}
```

```
// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for Go da API.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
const FIFO_SUFFIX = ".fifo"
const TONE_KEY = "tone"
```

```
var ToneChoices = []string{"cheerful", "funny", "serious", "sincere"}

// MessageBody is used to deserialize the body of a message from a JSON string.
type MessageBody struct {
 Message string
}

// ScenarioRunner separates the steps of this scenario into individual functions so
 that
// they are simpler to read and understand.
type ScenarioRunner struct {
 questioner demotools.IQuestioner
 snsActor   *actions.SnsActions
 sqsActor   *actions.SqsActions
}

func (runner ScenarioRunner) CreateTopic() (string, string, bool, bool) {
 log.Println("SNS topics can be configured as FIFO (First-In-First-Out) or standard.
\n" +
  "FIFO topics deliver messages in order and support deduplication and message
 filtering.")
 isFifoTopic := runner.questioner.AskBool("\nWould you like to work with FIFO
 topics? (y/n) ", "y")

 contentBasedDeduplication := false
 if isFifoTopic {
  log.Println(strings.Repeat("-", 88))
  log.Println("Because you have chosen a FIFO topic, deduplication is supported.\n"
 +
   "Deduplication IDs are either set in the message or are automatically generated
\n" +
   "from content using a hash function. If a message is successfully published to\n"
 +
   "an SNS FIFO topic, any message published and determined to have the same\n" +
   "deduplication ID, within the five-minute deduplication interval, is accepted\n"
 +
   "but not delivered. For more information about deduplication, see:\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/fifo-message-dedup.html.")
  contentBasedDeduplication = runner.questioner.AskBool(
   "\nDo you want to use content-based deduplication instead of entering a
 deduplication ID? (y/n) ", "y")
 }
 log.Println(strings.Repeat("-", 88))
```

```
 topicName := runner.questioner.Ask("Enter a name for your SNS topic. ")
 if isFifoTopic {
  topicName = fmt.Sprintf("%v%v", topicName, FIFO_SUFFIX)
  log.Printf("Because you have selected a FIFO topic, '%v' must be appended to\n"+
   "the topic name.", FIFO_SUFFIX)
 }

 topicArn, err := runner.snsActor.CreateTopic(topicName, isFifoTopic,
 contentBasedDeduplication)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new topic with the name '%v' and Amazon Resource Name (ARN) \n"+
  "'%v' has been created.", topicName, topicArn)

 return topicName, topicArn, isFifoTopic, contentBasedDeduplication
}

func (runner ScenarioRunner) CreateQueue(ordinal string, isFifoTopic bool) (string,
 string) {
 queueName := runner.questioner.Ask(fmt.Sprintf("Enter a name for the %v SQS queue.
 ", ordinal))
 if isFifoTopic {
  queueName = fmt.Sprintf("%v%v", queueName, FIFO_SUFFIX)
  if ordinal == "first" {
   log.Printf("Because you are creating a FIFO SQS queue, '%v' must "+
    "be appended to the queue name.\n", FIFO_SUFFIX)
  }
 }
 queueUrl, err := runner.sqsActor.CreateQueue(queueName, isFifoTopic)
 if err != nil {
  panic(err)
 }
 log.Printf("Your new SQS queue with the name '%v' and the queue URL "+
  "'%v' has been created.", queueName, queueUrl)

 return queueName, queueUrl
}

func (runner ScenarioRunner) SubscribeQueueToTopic(
 queueName string, queueUrl string, topicName string, topicArn string, ordinal
 string,
 isFifoTopic bool) (string, bool) {
```

```
queueArn, err := runner.sqsActor.GetQueueArn(queueUrl)
if err != nil {
 panic(err)
}
log.Printf("The ARN of your queue is: %v.\n", queueArn)

err = runner.sqsActor.AttachSendMessagePolicy(queueUrl, queueArn, topicArn)
if err != nil {
 panic(err)
}
log.Println("Attached an IAM policy to the queue so the SNS topic can send " +
 "messages to it.")
log.Println(strings.Repeat("-", 88))

var filterPolicy map[string][]string
if isFifoTopic {
 if ordinal == "first" {
  log.Println("Subscriptions to a FIFO topic can have filters.\n" +
   "If you add a filter to this subscription, then only the filtered messages\n" +
   "will be received in the queue.\n" +
   "For information about message filtering, see\n" +
   "\thttps://docs.aws.amazon.com/sns/latest/dg/sns-message-filtering.html\n" +
   "For this example, you can filter messages by a \"tone\" attribute.")
 }

 wantFiltering := runner.questioner.AskBool(
  fmt.Sprintf("Do you want to filter messages that are sent to \"%v\"\n"+
   "from the %v topic? (y/n) ", queueName, topicName), "y")
 if wantFiltering {
  log.Println("You can filter messages by one or more of the following \"tone\"
attributes.")

  var toneSelections []string
  askAboutTones := true
  for askAboutTones {
   toneIndex := runner.questioner.AskChoice(
    "Enter the number of the tone you want to filter by:\n", ToneChoices)
   toneSelections = append(toneSelections, ToneChoices[toneIndex])
   askAboutTones = runner.questioner.AskBool("Do you want to add another tone to
the filter? (y/n) ", "y")
  }
  log.Printf("Your subscription will be filtered to only pass the following tones:
%v\n", toneSelections)
```

```
    filterPolicy = map[string][]string{TONE_KEY: toneSelections}
   }
  }

  subscriptionArn, err := runner.snsActor.SubscribeQueue(topicArn, queueArn,
  filterPolicy)
  if err != nil {
   panic(err)
  }
  log.Printf("The queue %v is now subscribed to the topic %v with the subscription
  ARN %v.\n",
   queueName, topicName, subscriptionArn)

  return subscriptionArn, filterPolicy != nil
}

func (runner ScenarioRunner) PublishMessages(topicArn string, isFifoTopic bool,
 contentBasedDeduplication bool, usingFilters bool) {
 var message string
 var groupId string
 var dedupId string
 var toneSelection string
 publishMore := true
 for publishMore {
  groupId = ""
  dedupId = ""
  toneSelection = ""
  message = runner.questioner.Ask("Enter a message to publish: ")
  if isFifoTopic {
   log.Println("Because you are using a FIFO topic, you must set a message group ID.
\n" +
    "All messages within the same group will be received in the order they were
 published.")
   groupId = runner.questioner.Ask("Enter a message group ID: ")
   if !contentBasedDeduplication {
    log.Println("Because you are not using content-based deduplication,\n" +
     "you must enter a deduplication ID.")
    dedupId = runner.questioner.Ask("Enter a deduplication ID: ")
   }
  }
  if usingFilters {
   if runner.questioner.AskBool("Add a tone attribute so this message can be
 filtered? (y/n) ", "y") {
    toneIndex := runner.questioner.AskChoice(
```

```
      "Enter the number of the tone you want to filter by:\n", ToneChoices)
     toneSelection = ToneChoices[toneIndex]
    }
   }

   err := runner.snsActor.Publish(topicArn, message, groupId, dedupId, TONE_KEY,
  toneSelection)
   if err != nil {
    panic(err)
   }
   log.Println(("Your message was published."))

   publishMore = runner.questioner.AskBool("Do you want to publish another messsage?
  (y/n) ", "y")
  }
 }

 func (runner ScenarioRunner) PollForMessages(queueUrls []string) {
  log.Println("Polling queues for messages...")
  for _, queueUrl := range queueUrls {
   var messages []types.Message
   for {
    currentMsgs, err := runner.sqsActor.GetMessages(queueUrl, 10, 1)
    if err != nil {
     panic(err)
    }
    if len(currentMsgs) == 0 {
     break
    }
    messages = append(messages, currentMsgs...)
   }
   if len(messages) == 0 {
    log.Printf("No messages were received by queue %v.\n", queueUrl)
   } else if len(messages) == 1 {
    log.Printf("One message was received by queue %v:\n", queueUrl)

   } else {
    log.Printf("%v messages were received by queue %v:\n", len(messages), queueUrl)
   }
   for msgIndex, message := range messages {
    messageBody := MessageBody{}
    err := json.Unmarshal([]byte(*message.Body), &messageBody)
    if err != nil {
     panic(err)
```

```
    }
    log.Printf("Message %v: %v\n", msgIndex+1, messageBody.Message)
   }

   if len(messages) > 0 {
    log.Printf("Deleting %v messages from queue %v.\n", len(messages), queueUrl)
    err := runner.sqsActor.DeleteMessages(queueUrl, messages)
    if err != nil {
     panic(err)
    }
   }
  }
}

// RunTopicsAndQueuesScenario is an interactive example that shows you how to use
 the
// AWS SDK for Go to create and use Amazon SNS topics and Amazon SQS queues.
//
// 1. Create a topic (FIFO or non-FIFO).
// 2. Subscribe several queues to the topic with an option to apply a filter.
// 3. Publish messages to the topic.
// 4. Poll the queues for messages received.
// 5. Delete the topic and the queues.
//
// This example creates service clients from the specified sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
 example.
// This package can be found in the ..\..\demotools folder of this repo.
func RunTopicsAndQueuesScenario(
 sdkConfig aws.Config, questioner demotools.IQuestioner) {
 resources := Resources{}
 defer func() {
  if r := recover(); r != nil {
   log.Println("Something went wrong with the demo.\n" +
    "Cleaning up any resources that were created...")
   resources.Cleanup()
  }
 }()
 queueCount := 2

 log.Println(strings.Repeat("-", 88))
 log.Printf("Welcome to messaging with topics and queues.\n\n"+
```

```
  "In this workflow, you will create an SNS topic and subscribe %v SQS queues to the
\n"+
  "topic. You can select from several options for configuring the topic and the\n"+
  "subscriptions for the queues. You can then post to the topic and see the results
\n"+
  "in the queues.\n", queueCount)

 log.Println(strings.Repeat("-", 88))

 runner := ScenarioRunner{
  questioner: questioner,
  snsActor:   &actions.SnsActions{SnsClient: sns.NewFromConfig(sdkConfig)},
  sqsActor:   &actions.SqsActions{SqsClient: sqs.NewFromConfig(sdkConfig)},
 }
 resources.snsActor = runner.snsActor
 resources.sqsActor = runner.sqsActor

 topicName, topicArn, isFifoTopic, contentBasedDeduplication := runner.CreateTopic()
 resources.topicArn = topicArn
 log.Println(strings.Repeat("-", 88))

 log.Printf("Now you will create %v SQS queues and subscribe them to the topic.\n",
 queueCount)
 ordinals := []string{"first", "next"}
 usingFilters := false
 for _, ordinal := range ordinals {
  queueName, queueUrl := runner.CreateQueue(ordinal, isFifoTopic)
  resources.queueUrls = append(resources.queueUrls, queueUrl)

  _, filtering := runner.SubscribeQueueToTopic(queueName, queueUrl, topicName,
 topicArn, ordinal, isFifoTopic)
  usingFilters = usingFilters || filtering
 }

 log.Println(strings.Repeat("-", 88))
 runner.PublishMessages(topicArn, isFifoTopic, contentBasedDeduplication,
 usingFilters)
 log.Println(strings.Repeat("-", 88))
 runner.PollForMessages(resources.queueUrls)

 log.Println(strings.Repeat("-", 88))

 wantCleanup := questioner.AskBool("Do you want to remove all AWS resources created
 for this scenario? (y/n) ", "y")
```

```
 if wantCleanup {
  log.Println("Cleaning up resources...")
  resources.Cleanup()
 }

 log.Println(strings.Repeat("-", 88))
 log.Println("Thanks for watching!")
 log.Println(strings.Repeat("-", 88))
}
```

Defina uma estrutura que envolva as ações do Amazon SNS usadas neste exemplo.

```
// SnsActions encapsulates the Amazon Simple Notification Service (Amazon SNS)
 actions
// used in the examples.
type SnsActions struct {
 SnsClient *sns.Client
}



// CreateTopic creates an Amazon SNS topic with the specified name. You can
 optionally
// specify that the topic is created as a FIFO topic and whether it uses content-
based
// deduplication instead of ID-based deduplication.
func (actor SnsActions) CreateTopic(topicName string, isFifoTopic bool,
 contentBasedDeduplication bool) (string, error) {
 var topicArn string
 topicAttributes := map[string]string{}
 if isFifoTopic {
  topicAttributes["FifoTopic"] = "true"
 }
 if contentBasedDeduplication {
  topicAttributes["ContentBasedDeduplication"] = "true"
 }
 topic, err := actor.SnsClient.CreateTopic(context.TODO(), &sns.CreateTopicInput{
  Name:       aws.String(topicName),
  Attributes: topicAttributes,
 })
```

```
 if err != nil {
  log.Printf("Couldn't create topic %v. Here's why: %v\n", topicName, err)
 } else {
  topicArn = *topic.TopicArn
 }

 return topicArn, err
}



// DeleteTopic delete an Amazon SNS topic.
func (actor SnsActions) DeleteTopic(topicArn string) error {
 _, err := actor.SnsClient.DeleteTopic(context.TODO(), &sns.DeleteTopicInput{
  TopicArn: aws.String(topicArn)})
 if err != nil {
  log.Printf("Couldn't delete topic %v. Here's why: %v\n", topicArn, err)
 }
 return err
}



// SubscribeQueue subscribes an Amazon Simple Queue Service (Amazon SQS) queue to an
// Amazon SNS topic. When filterMap is not nil, it is used to specify a filter
 policy
// so that messages are only sent to the queue when the message has the specified
 attributes.
func (actor SnsActions) SubscribeQueue(topicArn string, queueArn string, filterMap
 map[string][]string) (string, error) {
 var subscriptionArn string
 var attributes map[string]string
 if filterMap != nil {
  filterBytes, err := json.Marshal(filterMap)
  if err != nil {
   log.Printf("Couldn't create filter policy, here's why: %v\n", err)
   return "", err
  }
  attributes = map[string]string{"FilterPolicy": string(filterBytes)}
 }
 output, err := actor.SnsClient.Subscribe(context.TODO(), &sns.SubscribeInput{
  Protocol:              aws.String("sqs"),
  TopicArn:              aws.String(topicArn),
  Attributes:            attributes,
```

```
  Endpoint:              aws.String(queueArn),
  ReturnSubscriptionArn: true,
 })
 if err != nil {
  log.Printf("Couldn't susbscribe queue %v to topic %v. Here's why: %v\n",
   queueArn, topicArn, err)
 } else {
  subscriptionArn = *output.SubscriptionArn
 }

 return subscriptionArn, err
}



// Publish publishes a message to an Amazon SNS topic. The message is then sent to
 all
// subscribers. When the topic is a FIFO topic, the message must also contain a
 group ID
// and, when ID-based deduplication is used, a deduplication ID. An optional key-
value
// filter attribute can be specified so that the message can be filtered according
 to
// a filter policy.
func (actor SnsActions) Publish(topicArn string, message string, groupId string,
 dedupId string, filterKey string, filterValue string) error {
 publishInput := sns.PublishInput{TopicArn: aws.String(topicArn), Message:
 aws.String(message)}
 if groupId != "" {
  publishInput.MessageGroupId = aws.String(groupId)
 }
 if dedupId != "" {
  publishInput.MessageDeduplicationId = aws.String(dedupId)
 }
 if filterKey != "" && filterValue != "" {
  publishInput.MessageAttributes = map[string]types.MessageAttributeValue{
   filterKey: {DataType: aws.String("String"), StringValue:
 aws.String(filterValue)},
  }
 }
 _, err := actor.SnsClient.Publish(context.TODO(), &publishInput)
 if err != nil {
  log.Printf("Couldn't publish message to topic %v. Here's why: %v", topicArn, err)
 }
```

```
 return err
}
```

Defina uma estrutura que envolva as ações do Amazon SQS usadas neste exemplo.

```
// SqsActions encapsulates the Amazon Simple Queue Service (Amazon SQS) actions
// used in the examples.
type SqsActions struct {
 SqsClient *sqs.Client
}



// CreateQueue creates an Amazon SQS queue with the specified name. You can specify
// whether the queue is created as a FIFO queue.
func (actor SqsActions) CreateQueue(queueName string, isFifoQueue bool) (string,
 error) {
 var queueUrl string
 queueAttributes := map[string]string{}
 if isFifoQueue {
  queueAttributes["FifoQueue"] = "true"
 }
 queue, err := actor.SqsClient.CreateQueue(context.TODO(), &sqs.CreateQueueInput{
  QueueName:  aws.String(queueName),
  Attributes: queueAttributes,
 })
 if err != nil {
  log.Printf("Couldn't create queue %v. Here's why: %v\n", queueName, err)
 } else {
  queueUrl = *queue.QueueUrl
 }

 return queueUrl, err
}



// GetQueueArn uses the GetQueueAttributes action to get the Amazon Resource Name
 (ARN)
// of an Amazon SQS queue.
```

```
func (actor SqsActions) GetQueueArn(queueUrl string) (string, error) {
 var queueArn string
 arnAttributeName := types.QueueAttributeNameQueueArn
 attribute, err := actor.SqsClient.GetQueueAttributes(context.TODO(),
 &sqs.GetQueueAttributesInput{
  QueueUrl:       aws.String(queueUrl),
  AttributeNames: []types.QueueAttributeName{arnAttributeName},
 })
 if err != nil {
  log.Printf("Couldn't get ARN for queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  queueArn = attribute.Attributes[string(arnAttributeName)]
 }
 return queueArn, err
}



// AttachSendMessagePolicy uses the SetQueueAttributes action to attach a policy to
 an
// Amazon SQS queue that allows the specified Amazon SNS topic to send messages to
 the
// queue.
func (actor SqsActions) AttachSendMessagePolicy(queueUrl string, queueArn string,
 topicArn string) error {
 policyDoc := PolicyDocument{
  Version: "2012-10-17",
  Statement: []PolicyStatement{{
   Effect:    "Allow",
   Action:    "sqs:SendMessage",
   Principal: map[string]string{"Service": "sns.amazonaws.com"},
   Resource:  aws.String(queueArn),
   Condition: PolicyCondition{"ArnEquals": map[string]string{"aws:SourceArn":
 topicArn}},
  }},
 }
 policyBytes, err := json.Marshal(policyDoc)
 if err != nil {
  log.Printf("Couldn't create policy document. Here's why: %v\n", err)
  return err
 }
 _, err = actor.SqsClient.SetQueueAttributes(context.TODO(),
 &sqs.SetQueueAttributesInput{
  Attributes: map[string]string{
```

```
   string(types.QueueAttributeNamePolicy): string(policyBytes),
  },
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't set send message policy on queue %v. Here's why: %v\n",
 queueUrl, err)
 }
 return err
}

// PolicyDocument defines a policy document as a Go struct that can be serialized
// to JSON.
type PolicyDocument struct {
 Version   string
 Statement []PolicyStatement
}

// PolicyStatement defines a statement in a policy document.
type PolicyStatement struct {
 Effect    string
 Action    string
 Principal map[string]string `json:",omitempty"`
 Resource  *string           `json:",omitempty"`
 Condition PolicyCondition   `json:",omitempty"`
}

// PolicyCondition defines a condition in a policy.
type PolicyCondition map[string]map[string]string



// GetMessages uses the ReceiveMessage action to get messages from an Amazon SQS
 queue.
func (actor SqsActions) GetMessages(queueUrl string, maxMessages int32, waitTime
 int32) ([]types.Message, error) {
 var messages []types.Message
 result, err := actor.SqsClient.ReceiveMessage(context.TODO(),
 &sqs.ReceiveMessageInput{
  QueueUrl:            aws.String(queueUrl),
  MaxNumberOfMessages: maxMessages,
  WaitTimeSeconds:     waitTime,
 })
 if err != nil {
```

```
  log.Printf("Couldn't get messages from queue %v. Here's why: %v\n", queueUrl, err)
 } else {
  messages = result.Messages
 }
 return messages, err
}



// DeleteMessages uses the DeleteMessageBatch action to delete a batch of messages
 from
// an Amazon SQS queue.
func (actor SqsActions) DeleteMessages(queueUrl string, messages []types.Message)
 error {
 entries := make([]types.DeleteMessageBatchRequestEntry, len(messages))
 for msgIndex := range messages {
  entries[msgIndex].Id = aws.String(fmt.Sprintf("%v", msgIndex))
  entries[msgIndex].ReceiptHandle = messages[msgIndex].ReceiptHandle
 }
 _, err := actor.SqsClient.DeleteMessageBatch(context.TODO(),
 &sqs.DeleteMessageBatchInput{
  Entries:  entries,
  QueueUrl: aws.String(queueUrl),
 })
 if err != nil {
  log.Printf("Couldn't delete messages from queue %v. Here's why: %v\n", queueUrl,
 err)
 }
 return err
}



// DeleteQueue deletes an Amazon SQS queue.
func (actor SqsActions) DeleteQueue(queueUrl string) error {
 _, err := actor.SqsClient.DeleteQueue(context.TODO(), &sqs.DeleteQueueInput{
  QueueUrl: aws.String(queueUrl)})
 if err != nil {
  log.Printf("Couldn't delete queue %v. Here's why: %v\n", queueUrl, err)
 }
 return err
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Go.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Go.

```
package integration_sqs_to_lambda
```

```
import (
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(event events.SQSEvent) error {
 for _, record := range event.Records {
  err := processMessage(record)
  if err != nil {
   return err
  }
 }
 fmt.Println("done")
 return nil
}

func processMessage(record events.SQSMessage) error {
 fmt.Printf("Processed message %s\n", record.Body)
 // TODO: Do interesting work based on the new message
 return nil
}

func main() {
 lambda.Start(handler)
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Go V2

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando Go.

```
package main

import (
 "context"
 "encoding/json"
 "fmt"
 "github.com/aws/aws-lambda-go/events"
 "github.com/aws/aws-lambda-go/lambda"
)

func handler(ctx context.Context, sqsEvent events.SQSEvent) (map[string]interface{},
 error) {
 batchItemFailures := []map[string]interface{}{}

 for _, message := range sqsEvent.Records {

  if /* Your message processing condition here */ {
   batchItemFailures = append(batchItemFailures, map[string]interface{}
{"itemIdentifier": message.MessageId})
  }
 }

 sqsBatchResponse := map[string]interface{}{
  "batchItemFailures": batchItemFailures,
 }
 return sqsBatchResponse, nil
}

func main() {
 lambda.Start(handler)
}
```

Exemplos de código para SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como usar (v2) AWS SDK for JavaScript com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para JavaScript (v2) — Saiba mais sobre como usar JavaScript com. AWS
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para JavaScript (v2)
- Exemplos de serviços cruzados usando o SDK para JavaScript (v2)

Ações e cenários usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- CloudWatch exemplos usando o SDK para JavaScript (v2)
- CloudWatch Exemplos de eventos usando o SDK para JavaScript (v2)
- CloudWatch Exemplos de registros usando o SDK para JavaScript (v2)
- Exemplos do DynamoDB usando o SDK JavaScript para (v2)
- EventBridge exemplos usando o SDK para JavaScript (v2)

- Exemplos de IAM usando SDK para JavaScript (v2)
- Exemplos do Kinesis usando o SDK para JavaScript (v2)
- Exemplos de Lambda usando SDK para JavaScript (v2)
- Exemplos do Amazon Pinpoint usando o SDK para JavaScript (v2)
- Exemplos de API de voz e SMS do Amazon Pinpoint usando SDK para JavaScript (v2)
- Exemplos do Amazon RDS usando SDK para JavaScript (v2)
- Exemplos do Amazon S3 usando SDK para JavaScript (v2)
- Exemplos do S3 Glacier usando SDK para JavaScript (v2)
- Exemplos do Amazon SNS usando SDK para JavaScript (v2)
- Exemplos do Amazon SQS usando SDK para JavaScript (v2)
- AWS STSexemplos usando o SDK para JavaScript (v2)

CloudWatch exemplos usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v2) com CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricAlarmCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  // This alarm triggers when CPUUtilization exceeds 70% for one minute.
  const command = new PutMetricAlarmCommand({
    AlarmName: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
    ComparisonOperator: "GreaterThanThreshold",
    EvaluationPeriods: 1,
    MetricName: "CPUUtilization",
    Namespace: "AWS/EC2",
    Period: 60,
    Statistic: "Average",
    Threshold: 70.0,
    ActionsEnabled: false,
    AlarmDescription: "Alarm when server CPU exceeds 70%",
    Dimensions: [
      {
        Name: "InstanceId",
        Value: process.env.EC2_INSTANCE_ID, // Set the value of EC_INSTANCE_ID to
 the Id of an existing Amazon EC2 instance.
      },
    ],
    Unit: "Percent",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: false,
  AlarmDescription: "Alarm when server CPU exceeds 70%",
```

```
  Dimensions: [
    {
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
};

cw.putMetricAlarm(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

Excluir alarmes

O exemplo de código a seguir mostra como excluir CloudWatch alarmes da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DeleteAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteAlarmsCommand({
```

```
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });
```

```
var params = {
  AlarmNames: ["Web_Server_CPU_Utilization"],
};

cw.deleteAlarms(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DescribeAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DescribeAlarmsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });
```

```
  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.describeAlarms({ StateValue: "INSUFFICIENT_DATA" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
```

```
    // List the names of all current alarms in the console
    data.MetricAlarms.forEach(function (item, index, array) {
      console.log(item.AlarmName);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DisableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DisableAlarmActionsCommand({
    AlarmNames: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.disableAlarmActions(
  { AlarmNames: ["Web_Server_CPU_Utilization"] },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
```

```
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EnableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new EnableAlarmActionsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: true,
  AlarmActions: ["ACTION_ARN"],
  AlarmDescription: "Alarm when server CPU exceeds 70%",
  Dimensions: [
    {
```

```
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
};

cw.putMetricAlarm(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Alarm action added", data);
    var paramsEnableAlarmAction = {
      AlarmNames: [params.AlarmName],
    };
    cw.enableAlarmActions(paramsEnableAlarmAction, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Alarm action enabled", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListMetricsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

export const main = () => {
  // Use the AWS console to see available namespaces and metric names. Custom
 metrics can also be created.
  // https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
viewing_metrics_with_cloudwatch.html
  const command = new ListMetricsCommand({
    Dimensions: [
      {
        Name: "LogGroupName",
      },
    ],
    MetricName: "IncomingLogEvents",
    Namespace: "AWS/Logs",
  });

  return client.send(command);
};
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  Dimensions: [
    {
      Name: "LogGroupName" /* required */,
    },
  ],
  MetricName: "IncomingLogEvents",
  Namespace: "AWS/Logs",
};

cw.listMetrics(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Metrics", JSON.stringify(data.Metrics));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricDataCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  // See https://docs.aws.amazon.com/AmazonCloudWatch/latest/APIReference/
API_PutMetricData.html#API_PutMetricData_RequestParameters
  // and https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
publishingMetrics.html
  // for more information about the parameters in this command.
  const command = new PutMetricDataCommand({
    MetricData: [
      {
        MetricName: "PAGES_VISITED",
        Dimensions: [
          {
            Name: "UNIQUE_PAGES",
            Value: "URLS",
          },
        ],
        Unit: "None",
        Value: 1.0,
      },
    ],
    Namespace: "SITE/TRAFFIC",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

// Create parameters JSON for putMetricData
var params = {
  MetricData: [
    {
      MetricName: "PAGES_VISITED",
      Dimensions: [
        {
          Name: "UNIQUE_PAGES",
          Value: "URLS",
        },
      ],
      Unit: "None",
      Value: 1.0,
    },
  ],
  Namespace: "SITE/TRAFFIC",
};

cw.putMetricData(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", JSON.stringify(data));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

CloudWatch Exemplos de eventos usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v2) com CloudWatch Eventos.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adição de um destino

O exemplo de código a seguir mostra como adicionar um alvo a um evento da Amazon CloudWatch Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutTargetsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutTargetsCommand({
    // The name of the Amazon CloudWatch Events rule.
    Rule: process.env.CLOUDWATCH_EVENTS_RULE,

    // The targets to add to the rule.
    Targets: [
      {
        Arn: process.env.CLOUDWATCH_EVENTS_TARGET_ARN,
        // The ID of the target. Choose a unique ID for each target.
        Id: process.env.CLOUDWATCH_EVENTS_TARGET_ID,
      },
    ],
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";
```

```
export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myCloudWatchEventsTarget",
    },
  ],
};

cwevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Criar uma regra agendada

O exemplo de código a seguir mostra como criar uma regra programada do Amazon CloudWatch Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutRuleCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  // Request parameters for PutRule.
  // https://docs.aws.amazon.com/eventbridge/latest/APIReference/
API_PutRule.html#API_PutRule_RequestParameters
  const command = new PutRuleCommand({
    Name: process.env.CLOUDWATCH_EVENTS_RULE,

    // The event pattern for the rule.
    //  Example: {"source": ["my.app"]}
    EventPattern: process.env.CLOUDWATCH_EVENTS_RULE_PATTERN,

    // The state of the rule. Valid values: ENABLED, DISABLED
    State: "ENABLED",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};
```

```
export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

cwevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.RuleArn);
  }
```

```
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar CloudWatch eventos da Amazon Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutEventsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutEventsCommand({
    // The list of events to send to Amazon CloudWatch Events.
    Entries: [
      {
        // The name of the application or service that is sending the event.
        Source: "my.app",

        // The name of the event that is being sent.
        DetailType: "My Custom Event",

        // The data that is sent with the event.
        Detail: JSON.stringify({ timeOfEvent: new Date().toISOString() }),
      },
    ],
  });

  try {
```

```
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
```

```
    },
  ],
};

cwevents.putEvents(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

CloudWatch Exemplos de registros usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v2) com o CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um filtro de assinatura

O exemplo de código a seguir mostra como criar um filtro de assinatura do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { PutSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutSubscriptionFilterCommand({
    // An ARN of a same-account Kinesis stream, Kinesis Firehose
    // delivery stream, or Lambda function.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
SubscriptionFilters.html
    destinationArn: process.env.CLOUDWATCH_LOGS_DESTINATION_ARN,

    // A name for the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,

    // A filter pattern for subscribing to a filtered stream of log events.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
FilterAndPatternSyntax.html
    filterPattern: process.env.CLOUDWATCH_LOGS_FILTER_PATTERN,

    // The name of the log group. Messages in this group matching the filter pattern
    // will be sent to the destination ARN.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  destinationArn: "LAMBDA_FUNCTION_ARN",
  filterName: "FILTER_NAME",
  filterPattern: "ERROR",
  logGroupName: "LOG_GROUP",
};

cwl.putSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Excluir um filtro de assinatura

O exemplo de código a seguir mostra como excluir um filtro de assinatura do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteSubscriptionFilterCommand({
    // The name of the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  filterName: "FILTER",
  logGroupName: "LOG_GROUP",
};

cwl.deleteSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Descreva os filtros de assinatura existentes

O exemplo de código a seguir mostra como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSubscriptionFiltersCommand } from "@aws-sdk/client-cloudwatch-
logs";
import { client } from "../libs/client.js";

const run = async () => {
  // This will return a list of all subscription filters in your account
  // matching the log group name.
  const command = new DescribeSubscriptionFiltersCommand({
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
    limit: 1,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  logGroupName: "GROUP_NAME",
  limit: 5,
};

cwl.describeSubscriptionFilters(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.subscriptionFilters);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for JavaScript da API.

Exemplos do DynamoDB usando o SDK JavaScript para (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a (v2) AWS SDK for JavaScript com DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { CreateTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new CreateTableCommand({
    TableName: "EspressoDrinks",
    // For more information about data types,
    // see https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
HowItWorks.NamingRulesDataTypes.html#HowItWorks.DataTypes and
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
    AttributeDefinitions: [
      {
        AttributeName: "DrinkName",
        AttributeType: "S",
      },
    ],
    KeySchema: [
      {
        AttributeName: "DrinkName",
        KeyType: "HASH",
      },
    ],
    ProvisionedThroughput: {
```

```
      ReadCapacityUnits: 1,
      WriteCapacityUnits: 1,
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  AttributeDefinitions: [
    {
      AttributeName: "CUSTOMER_ID",
      AttributeType: "N",
    },
    {
      AttributeName: "CUSTOMER_NAME",
      AttributeType: "S",
    },
  ],
```

```
  KeySchema: [
    {
      AttributeName: "CUSTOMER_ID",
      KeType: "HASH",
    },
    {
      AttributeName: "CUSTOMER_NAME",
      KeyType: "RANGE",
    },
  ],
  ProvisionedThroughput: {
    ReadCapacityUnits: 1,
    WriteCapacityUnits: 1,
  },
  TableName: "CUSTOMER_LIST",
  StreamSpecification: {
    StreamEnabled: false,
  },
};

// Call DynamoDB to create the table
ddb.createTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Table Created", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new DeleteTableCommand({
    TableName: "DecafCoffees",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });
```

```
var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to delete the specified table
ddb.deleteTable(params, function (err, data) {
  if (err && err.code === "ResourceNotFoundException") {
    console.log("Error: Table not found");
  } else if (err && err.code === "ResourceInUseException") {
    console.log("Error: Table in use");
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte DeleteCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, DeleteCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
```

```
  const command = new DeleteCommand({
    TableName: "Sodas",
    Key: {
      Flavor: "Cola",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Exclua um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "VALUE" },
  },
};

// Call DynamoDB to delete the item from the table
```

```
ddb.deleteItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Exclua um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  Key: {
    HASH_KEY: VALUE,
  },
  TableName: "TABLE",
};

docClient.delete(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchGet.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { BatchGetCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchGetCommand({
    // Each key in this object is the name of a table. This example refers
    // to a Books table.
    RequestItems: {
      Books: {
        // Each entry in Keys is an object that specifies a primary key.
        Keys: [
          {
            Title: "How to AWS",
          },
          {
            Title: "DynamoDB for DBAs",
          },
        ],
        // Only return the "Title" and "PageCount" attributes.
        ProjectionExpression: "Title, PageCount",
      },
    },
  });

  const response = await docClient.send(command);
  console.log(response.Responses["Books"]);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: {
      Keys: [
        { KEY_NAME: { N: "KEY_VALUE_1" } },
        { KEY_NAME: { N: "KEY_VALUE_2" } },
        { KEY_NAME: { N: "KEY_VALUE_3" } },
      ],
      ProjectionExpression: "KEY_NAME, ATTRIBUTE",
    },
  },
};

ddb.batchGetItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    data.Responses.TABLE_NAME.forEach(function (element, index, array) {
      console.log(element);
    });
```

```
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte GetCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, GetCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new GetCommand({
    TableName: "AngryAnimals",
    Key: {
      CommonName: "Shoebill",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Obtenha um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "001" },
  },
  ProjectionExpression: "ATTRIBUTE_NAME",
};

// Call DynamoDB to read the item from the table
ddb.getItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

Obtenha um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
```

```
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "EPISODES_TABLE",
  Key: { KEY_NAME: VALUE },
};

docClient.get(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { DescribeTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
```

```
  const command = new DescribeTableCommand({
    TableName: "Pastries",
  });

  const response = await client.send(command);
  console.log(`TABLE NAME: ${response.Table.TableName}`);
  console.log(`TABLE ITEM COUNT: ${response.Table.ItemCount}`);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to retrieve the selected table descriptions
ddb.describeTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Table.KeySchema);
  }
```

```
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { ListTablesCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new ListTablesCommand({});

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

// Call DynamoDB to retrieve the list of tables
ddb.listTables({ Limit: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err.code);
  } else {
    console.log("Table names are ", data.TableNames);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte PutCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { PutCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new PutCommand({
    TableName: "HappyAnimals",
    Item: {
      CommonName: "Shiba Inu",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Coloque um item em uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });
```

```
var params = {
  TableName: "CUSTOMER_LIST",
  Item: {
    CUSTOMER_ID: { N: "001" },
    CUSTOMER_NAME: { S: "Richard Roe" },
  },
};

// Call DynamoDB to add the item to the table
ddb.putItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Coloque um item em uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Item: {
    HASHKEY: VALUE,
    ATTRIBUTE_1: "STRING_VALUE",
    ATTRIBUTE_2: VALUE_2,
  },
};

docClient.put(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
```

```
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte QueryCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { QueryCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new QueryCommand({
    TableName: "CoffeeCrop",
    KeyConditionExpression:
      "OriginCountry = :originCountry AND RoastDate > :roastDate",
    ExpressionAttributeValues: {
      ":originCountry": "Ethiopia",
      ":roastDate": "2023-05-01",
    },
    ConsistentRead: true,
  });

  const response = await docClient.send(command);
```

```
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  ExpressionAttributeValues: {
    ":s": 2,
    ":e": 9,
    ":topic": "PHRASE",
  },
  KeyConditionExpression: "Season = :s and Episode > :e",
  FilterExpression: "contains (Subtitle, :topic)",
  TableName: "EPISODES_TABLE",
};

docClient.query(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Items);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte ScanCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, ScanCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ScanCommand({
    ProjectionExpression: "#Name, Color, AvgLifeSpan",
    ExpressionAttributeNames: { "#Name": "Name" },
    TableName: "Birds",
  });

  const response = await docClient.send(command);
  for (const bird of response.Items) {
    console.log(`${bird.Name} - (${bird.Color}, ${bird.AvgLifeSpan})`);
  }
  return response;
};
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js.
var AWS = require("aws-sdk");
// Set the AWS Region.
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object.
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

const params = {
  // Specify which items in the results are returned.
  FilterExpression: "Subtitle = :topic AND Season = :s AND Episode = :e",
  // Define the expression attribute value, which are substitutes for the values you
 want to compare.
  ExpressionAttributeValues: {
    ":topic": { S: "SubTitle2" },
    ":s": { N: 1 },
    ":e": { N: 2 },
  },
  // Set the projection expression, which are the attributes that you want.
  ProjectionExpression: "Season, Episode, Title, Subtitle",
  TableName: "EPISODES_TABLE",
};

ddb.scan(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
    data.Items.forEach(function (element, index, array) {
      console.log(
        "printing",
        element.Title.S + " (" + element.Subtitle.S + ")"
      );
```

```
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchWrite.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import {
  BatchWriteCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";
import { readFileSync } from "fs";

// These modules are local to our GitHub repository. We recommend cloning
// the project from GitHub if you want to run this example.
// For more information, see https://github.com/awsdocs/aws-doc-sdk-examples.
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { chunkArray } from "@aws-sdk-examples/libs/utils/util-array.js";

const dirname = dirnameFromMetaUrl(import.meta.url);

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);
```

```
export const main = async () => {
  const file = readFileSync(
    `${dirname}../../../../../resources/sample_files/movies.json`,
  );

  const movies = JSON.parse(file.toString());

  // chunkArray is a local convenience function. It takes an array and returns
  // a generator function. The generator function yields every N items.
  const movieChunks = chunkArray(movies, 25);

  // For every chunk of 25 movies, make one BatchWrite request.
  for (const chunk of movieChunks) {
    const putRequests = chunk.map((movie) => ({
      PutRequest: {
        Item: movie,
      },
    }));

    const command = new BatchWriteCommand({
      RequestItems: {
        // An existing table is required. A composite key of 'title' and 'year' is
 recommended
        // to account for duplicate titles.
        ["BatchWriteMoviesTable"]: putRequests,
      },
    });

    await docClient.send(command);
  }
};
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: [
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
          },
        },
      },
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
          },
        },
      },
    ],
  },
};

ddb.batchWriteItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

EventBridge exemplos usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v2) com EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
```

```
  EventBridgeClient,
  PutTargetsCommand,
} from "@aws-sdk/client-eventbridge";

export const putTarget = async (
  existingRuleName = "some-rule",
  targetArn = "arn:aws:lambda:us-east-1:000000000000:function:test-func",
  uniqueId = Date.now().toString(),
) => {
  const client = new EventBridgeClient({});
  const response = await client.send(
    new PutTargetsCommand({
      Rule: existingRuleName,
      Targets: [
        {
          Arn: targetArn,
          Id: uniqueId,
        },
      ],
    }),
  );

  console.log("PutTargets response:");
  console.log(response);
  // PutTargets response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'f5b23b9a-2c17-45c1-ad5c-f926c3692e3d',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   FailedEntries: [],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myEventBridgeTarget",
    },
  ],
};

ebevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EventBridgeClient, PutRuleCommand } from "@aws-sdk/client-eventbridge";

export const putRule = async (
  ruleName = "some-rule",
  source = "some-source",
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutRuleCommand({
      Name: ruleName,
      EventPattern: JSON.stringify({ source: [source] }),
      State: "ENABLED",
      EventBusName: "default",
    }),
  );

  console.log("PutRule response:");
  console.log(response);
  // PutRule response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'd7292ced-1544-421b-842f-596326bc7072',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   RuleArn: 'arn:aws:events:us-east-1:xxxxxxxxxxxx:rule/
EventBridgeTestRule-1696280037720'
  // }
  return response;
```

```
};
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

ebevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.RuleArn);
  }
});
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
  EventBridgeClient,
  PutEventsCommand,
} from "@aws-sdk/client-eventbridge";

export const putEvents = async (
  source = "eventbridge.integration.test",
  detailType = "greeting",
  resources = [],
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutEventsCommand({
      Entries: [
        {
          Detail: JSON.stringify({ greeting: "Hello there." }),
          DetailType: detailType,
          Resources: resources,
          Source: source,
        },
      ],
    }),
  );

  console.log("PutEvents response:");
  console.log(response);
  // PutEvents response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '3d0df73d-dcea-4a23-ae0d-f5556a3ac109',
  //     extendedRequestId: undefined,
```

```
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Entries: [ { EventId: '51620841-5af4-6402-d9bc-b77734991eb5' } ],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
    },
  ],
};

ebevents.putEvents(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

Exemplos de IAM usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Anexe a política.

```
import { AttachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const attachRolePolicy = (policyArn, roleName) => {
  const command = new AttachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });
```

```
var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        console.log(
          "AmazonDynamoDBFullAccess is already attached to this role."
        );
        process.exit();
      }
    });
    var params = {
      PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
      RoleName: process.argv[2],
    };
    iam.attachRolePolicy(params, function (err, data) {
      if (err) {
        console.log("Unable to attach policy to role", err);
      } else {
        console.log("Role attached successfully");
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a política do

```
import { CreatePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyName
 */
export const createPolicy = (policyName) => {
  const command = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: "*",
          Resource: "*",
        },
      ],
    }),
    PolicyName: policyName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var myManagedPolicy = {
  Version: "2012-10-17",
  Statement: [
    {
      Effect: "Allow",
      Action: "logs:CreateLogGroup",
      Resource: "RESOURCE_ARN",
    },
    {
      Effect: "Allow",
      Action: [
        "dynamodb:DeleteItem",
        "dynamodb:GetItem",
        "dynamodb:PutItem",
        "dynamodb:Scan",
        "dynamodb:UpdateItem",
      ],
      Resource: "RESOURCE_ARN",
    },
  ],
};

var params = {
  PolicyDocument: JSON.stringify(myManagedPolicy),
  PolicyName: "myDynamoDBPolicy",
};
```

```
iam.createPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o usuário.

```
import { CreateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});
```

```
/**
 *
 * @param {string} name
 */
export const createUser = (name) => {
  const command = new CreateUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    iam.createUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Success", data);
      }
    });
```

```
  } else {
    console.log(
      "User " + process.argv[2] + " already exists",
      data.User.UserId
    );
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a chave de acesso.

```
import { CreateAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
```

```
 * @param {string} userName
 */
export const createAccessKey = (userName) => {
  const command = new CreateAccessKeyCommand({ UserName: userName });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccessKey({ UserName: "IAM_USER_NAME" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.AccessKey);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

Criar um alias para uma conta

O exemplo de código a seguir mostra como criar um alias para uma conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o alias da conta.

```
import { CreateAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} alias - A unique name for the account alias.
 * @returns
 */
export const createAccountAlias = (alias) => {
  const command = new CreateAccountAliasCommand({
    AccountAlias: alias,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

Excluir um certificado do servidor

Os exemplos de código a seguir mostram como excluir certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um certificado de servidor.

```
import { DeleteServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
 */
export const deleteServerCertificate = (certName) => {
  const command = new DeleteServerCertificateCommand({
    ServerCertificateName: certName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
```

```
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o usuário.

```
import { DeleteUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});
```

```
/**
 *
 * @param {string} name
 */
export const deleteUser = (name) => {
  const command = new DeleteUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    console.log("User " + process.argv[2] + " does not exist.");
  } else {
    iam.deleteUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Success", data);
```

```
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a chave de acesso.

```
import { DeleteAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
```

```
export const deleteAccessKey = (userName, accessKeyId) => {
  const command = new DeleteAccessKeyCommand({
    AccessKeyId: accessKeyId,
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  UserName: "USER_NAME",
};

iam.deleteAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

Excluir um alias de conta

O exemplo de código a seguir mostra como excluir um alias da conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o alias da conta.

```
import { DeleteAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} alias
 */
export const deleteAccountAlias = (alias) => {
  const command = new DeleteAccountAliasCommand({ AccountAlias: alias });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desanexe a política.

```
import { DetachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const detachRolePolicy = (policyArn, roleName) => {
  const command = new DetachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });
```

```
var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        var params = {
          PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
          RoleName: process.argv[2],
        };
        iam.detachRolePolicy(params, function (err, data) {
          if (err) {
            console.log("Unable to detach policy from role", err);
          } else {
            console.log("Policy detached from role successfully");
            process.exit();
          }
        });
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política.

```
import { GetPolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 */
export const getPolicy = (policyArn) => {
  const command = new GetPolicyCommand({
    PolicyArn: policyArn,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
```

```
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  PolicyArn: "arn:aws:iam::aws:policy/AWSLambdaExecute",
};

iam.getPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Policy.Description);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

Obter um certificado do servidor

O exemplo de código a seguir mostram como obter um certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um certificado do servidor.

```
import { GetServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
```

```
 * @returns
 */
export const getServerCertificate = async (certName) => {
  const command = new GetServerCertificateCommand({
    ServerCertificateName: certName,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
```

```
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

Obter dados sobre a última utilização de uma chave de acesso

O exemplo de código a seguir mostra como obter dados sobre a última utilização de uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a chave de acesso.

```
import { GetAccessKeyLastUsedCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} accessKeyId
 */
export const getAccessKeyLastUsed = async (accessKeyId) => {
  const command = new GetAccessKeyLastUsedCommand({
    AccessKeyId: accessKeyId,
```

```
  });

  const response = await client.send(command);

  if (response.AccessKeyLastUsed?.LastUsedDate) {
    console.log(`
    ${accessKeyId} was last used by ${response.UserName} via
    the ${response.AccessKeyLastUsed.ServiceName} service on
    ${response.AccessKeyLastUsed.LastUsedDate.toISOString()}
    `);
  }

  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUseda Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getAccessKeyLastUsed(
  { AccessKeyId: "ACCESS_KEY_ID" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
```

```
      console.log("Success", data.AccessKeyLastUsed);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUseda Referência AWS SDK for JavaScript da API.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as chaves de acesso.

```
import { ListAccessKeysCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
```

```
 *
 * @param {string} userName
 */
export async function* listAccessKeys(userName) {
  const command = new ListAccessKeysCommand({
    MaxItems: 5,
    UserName: userName,
  });

  /**
   * @type {import("@aws-sdk/client-iam").ListAccessKeysCommandOutput | undefined}
   */
  let response = await client.send(command);

  while (response?.AccessKeyMetadata?.length) {
    for (const key of response.AccessKeyMetadata) {
      yield key;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccessKeysCommand({
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 5,
  UserName: "IAM_USER_NAME",
};

iam.listAccessKeys(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os aliases de conta.

```
import { ListAccountAliasesCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 */
export async function* listAccountAliases() {
  const command = new ListAccountAliasesCommand({ MaxItems: 5 });

  let response = await client.send(command);

  while (response.AccountAliases?.length) {
    for (const alias of response.AccountAliases) {
      yield alias;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccountAliasesCommand({
          Marker: response.Marker,
          MaxItems: 5,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listAccountAliases({ MaxItems: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

Listar certificados do servidor

Os exemplos de código a seguir mostram como listar certificados de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os certificados.

```
import { ListServerCertificatesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 */
export async function* listServerCertificates() {
  const command = new ListServerCertificatesCommand({});
  let response = await client.send(command);

  while (response.ServerCertificateMetadataList?.length) {
    for await (const cert of response.ServerCertificateMetadataList) {
      yield cert;
    }

    if (response.IsTruncated) {
      response = await client.send(new ListServerCertificatesCommand({}));
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listServerCertificates({}, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os usuários.

```
import { ListUsersCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listUsers = async () => {
  const command = new ListUsersCommand({ MaxItems: 10 });

  const response = await client.send(command);
  response.Users?.forEach(({ UserName, CreateDate }) => {
    console.log(`${UserName} created on: ${CreateDate}`);
  });
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 10,
};

iam.listUsers(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    var users = data.Users || [];
    users.forEach(function (user) {
      console.log("User " + user.UserName + " created", user.CreateDate);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

Atualizar um certificado do servidor

O exemplo de código a seguir mostra como atualizar um certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize um certificado do servidor.

```
import { UpdateServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentName
 * @param {string} newName
 */
export const updateServerCertificate = (currentName, newName) => {
  const command = new UpdateServerCertificateCommand({
    ServerCertificateName: currentName,
    NewServerCertificateName: newName,
  });
```

```
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  ServerCertificateName: "CERTIFICATE_NAME",
  NewServerCertificateName: "NEW_CERTIFICATE_NAME",
};

iam.updateServerCertificate(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize o usuário.

```
import { UpdateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentUserName
 * @param {string} newUserName
 */
export const updateUser = (currentUserName, newUserName) => {
  const command = new UpdateUserCommand({
    UserName: currentUserName,
    NewUserName: newUserName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
  NewUserName: process.argv[3],
};

iam.updateUser(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

Atualizar uma chave de acesso

O exemplo de código a seguir mostra como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize a chave de acesso.

```
import {
  UpdateAccessKeyCommand,
  IAMClient,
  StatusType,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
export const updateAccessKey = (userName, accessKeyId) => {
  const command = new UpdateAccessKeyCommand({
    AccessKeyId: accessKeyId,
    Status: StatusType.Inactive,
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  Status: "Active",
  UserName: "USER_NAME",
};

iam.updateAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

Exemplos do Kinesis usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a (v2) AWS SDK for JavaScript com Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do Kinesis com o uso do Lambda. JavaScript

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
```

```
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      throw err;
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Consumindo um evento do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
```

```
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      throw err;
    }
    logger.info(`Successfully processed ${event.Records.length} records.`);
  }
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
```

```
    } catch (err) {
      console.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
           Lambda will immediately begin to retry processing from this failed item
 onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Relatando falhas de itens em lote do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
  KinesisStreamBatchResponse,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<KinesisStreamBatchResponse> => {
```

```
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
           Lambda will immediately begin to retry processing from this failed item
 onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  logger.info(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Exemplos de Lambda usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a (v2) AWS SDK for JavaScript com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Conectando-se a um banco de dados do Amazon RDS em uma função Lambda

O exemplo de código a seguir mostra como implementar uma função Lambda que se conecta a um banco de dados do RDS. A função faz uma solicitação simples ao banco de dados e retorna o resultado.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
/*
Node.js code here.
*/
// ES6+ example
import { Signer } from "@aws-sdk/rds-signer";
import mysql from 'mysql2/promise';

async function createAuthToken() {
  // Define connection authentication parameters
  const dbinfo = {

    hostname: process.env.ProxyHostName,
    port: process.env.Port,
    username: process.env.DBUserName,
    region: process.env.AWS_REGION,

  }
```

```
  // Create RDS Signer object
  const signer = new Signer(dbinfo);

  // Request authorization token from RDS, specifying the username
  const token = await signer.getAuthToken();
  return token;
}

async function dbOps() {

  // Obtain auth token
  const token = await createAuthToken();
  // Define connection configuration
  let connectionConfig = {
    host: process.env.ProxyHostName,
    user: process.env.DBUserName,
    password: token,
    database: process.env.DBName,
    ssl: 'Amazon RDS'
  }
  // Create the connection to the DB
  const conn = await mysql.createConnection(connectionConfig);
  // Obtain the result of the query
  const [res,] = await conn.execute('select ?+? as sum', [3, 2]);
  return res;

}

export const handler = async (event) => {
  // Execute database flow
  const result = await dbOps();
  // Return result
  return {
    statusCode: 200,
    body: JSON.stringify("The selected sum is: " + result[0].sum)
  }
};
```

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do Kinesis com o uso do Lambda. JavaScript

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      throw err;
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Consumindo um evento do Kinesis com o uso do Lambda. TypeScript

```
import {
  KinesisStreamEvent,
```

```
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      throw err;
    }
    logger.info(`Successfully processed ${event.Records.length} records.`);
  }
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do S3 com o uso do JavaScript Lambda.

```
const aws = require('aws-sdk');

const s3 = new aws.S3({ apiVersion: '2006-03-01' });

exports.handler = async (event, context) => {
    // Get the object from the event and show its content type
    const bucket = event.Records[0].s3.bucket.name;
    const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
    const params = {
        Bucket: bucket,
        Key: key,
    };
    try {
        const { ContentType } = await s3.headObject(params).promise();
        console.log('CONTENT TYPE:', ContentType);
        return ContentType;
    } catch (err) {
        console.log(err);
        const message = `Error getting object ${key} from bucket ${bucket}. Make
 sure they exist and your bucket is in the same region as this function.`;
        console.log(message);
        throw new Error(message);
    }
};
```

Consumindo um evento do S3 com o uso do TypeScript Lambda.

```
import { S3Event } from 'aws-lambda';
import { S3Client, HeadObjectCommand } from '@aws-sdk/client-s3';

const s3 = new S3Client({ region: process.env.AWS_REGION });

export const handler = async (event: S3Event): Promise<string | undefined> => {
  // Get the object from the event and show its content type
  const bucket = event.Records[0].s3.bucket.name;
  const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
  const params = {
    Bucket: bucket,
    Key: key,
  };
  try {
    const { ContentType } = await s3.send(new HeadObjectCommand(params));
    console.log('CONTENT TYPE:', ContentType);
    return ContentType;
  } catch (err) {
    console.log(err);
    const message = `Error getting object ${key} from bucket ${bucket}. Make sure
 they exist and your bucket is in the same region as this function.`;
    console.log(message);
    throw new Error(message);
  }
};
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do SNS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};

async function processMessageAsync(record) {
  try {
    const message = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento do SNS com o TypeScript Lambda usando.

```
import { SNSEvent, Context, SNSHandler, SNSEventRecord } from "aws-lambda";

export const functionHandler: SNSHandler = async (
  event: SNSEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};
```

```
async function processMessageAsync(record: SNSEventRecord): Promise<any> {
  try {
    const message: string = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento SQS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message) {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
```

```
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento SQS com o TypeScript Lambda usando.

```
import { SQSEvent, Context, SQSHandler, SQSRecord } from "aws-lambda";

export const functionHandler: SQSHandler = async (
  event: SQSEvent,
  context: Context
): Promise<void> => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message: SQSRecord): Promise<any> {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    try {
      console.log(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      console.log(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      console.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
           Lambda will immediately begin to retry processing from this failed item
 onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  console.log(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(payload) {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
  return data;
}
```

Relatando falhas de itens em lote do Kinesis com o uso do Lambda. TypeScript

```
import {
```

```
  KinesisStreamEvent,
  Context,
  KinesisStreamHandler,
  KinesisStreamRecordPayload,
  KinesisStreamBatchResponse,
} from "aws-lambda";
import { Buffer } from "buffer";
import { Logger } from "@aws-lambda-powertools/logger";

const logger = new Logger({
  logLevel: "INFO",
  serviceName: "kinesis-stream-handler-sample",
});

export const functionHandler: KinesisStreamHandler = async (
  event: KinesisStreamEvent,
  context: Context
): Promise<KinesisStreamBatchResponse> => {
  for (const record of event.Records) {
    try {
      logger.info(`Processed Kinesis Event - EventID: ${record.eventID}`);
      const recordData = await getRecordDataAsync(record.kinesis);
      logger.info(`Record Data: ${recordData}`);
      // TODO: Do interesting work based on the new data
    } catch (err) {
      logger.error(`An error occurred ${err}`);
      /* Since we are working with streams, we can return the failed item
 immediately.
           Lambda will immediately begin to retry processing from this failed item
 onwards. */
      return {
        batchItemFailures: [{ itemIdentifier: record.kinesis.sequenceNumber }],
      };
    }
  }
  logger.info(`Successfully processed ${event.Records.length} records.`);
  return { batchItemFailures: [] };
};

async function getRecordDataAsync(
  payload: KinesisStreamRecordPayload
): Promise<string> {
  var data = Buffer.from(payload.data, "base64").toString("utf-8");
  await Promise.resolve(1); //Placeholder for actual async work
```

```
  return data;
}
```

Exemplos do Amazon Pinpoint usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar e-mails e mensagens de texto

O exemplo de código a seguir mostra como enviar e-mail e mensagens de texto com o Amazon Pinpoint.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { PinpointClient } from "@aws-sdk/client-pinpoint";
// Set the AWS Region.
const REGION = "us-east-1";
//Set the MediaConvert Service Object
const pinClient = new PinpointClient({ region: REGION });
export { pinClient };
```

Envie uma mensagem de e-mail.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

// The FromAddress must be verified in SES.
const fromAddress = "FROM_ADDRESS";
const toAddress = "TO_ADDRESS";
const projectId = "PINPOINT_PROJECT_ID";

// The subject line of the email.
var subject = "Amazon Pinpoint Test (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https://aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
var body_html = `<html>
<head></head>
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint Email API</a>
 using the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding for the subject line and message body of the email.
```

```
var charset = "UTF-8";

const params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: fromAddress,
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};

const run = async () => {
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));

    const {
      MessageResponse: { Result },
    } = data;

    const recipientResult = Result[toAddress];

    if (recipientResult.StatusCode !== 200) {
      throw new Error(recipientResult.StatusMessage);
```

```
    } else {
      console.log(recipientResult.MessageId);
    }
  } catch (err) {
    console.log(err.message);
  }
};

run();
```

Envie uma mensagem SMS.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

("use strict");

/* The phone number or short code to send the message from. The phone number
 or short code that you specify has to be associated with your Amazon Pinpoint
account. For best results, specify long codes in E.164 format. */
const originationNumber = "SENDER_NUMBER"; //e.g., +1XXXXXXXXXX

// The recipient's phone number.  For best results, you should specify the phone
 number in E.164 format.
const destinationNumber = "RECEIVER_NUMBER"; //e.g., +1XXXXXXXXXX

// The content of the SMS message.
const message =
  "This message was sent through Amazon Pinpoint " +
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

/*The Amazon Pinpoint project/application ID to use when you send this message.
Make sure that the SMS channel is enabled for the project or application
that you choose.*/
const projectId = "PINPOINT_PROJECT_ID"; //e.g., XXXXXXXX66e4e9986478cXXXXXXXXX

/* The type of SMS message that you want to send. If you plan to send
time-sensitive content, specify TRANSACTIONAL. If you plan to send
marketing-related content, specify PROMOTIONAL.*/
```

```
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
var registeredKeyword = "myKeyword";

/* The sender ID to use when sending the message. Support for sender ID
// varies by country or region. For more information, see
https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-countries.html.*/

var senderId = "MySenderID";

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
};

const run = async () => {
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));
    return data; // For unit tests.
    console.log(
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  } catch (err) {
    console.log(err);
  }
};
```

```
run();
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
"use strict";

const AWS = require("aws-sdk");

// The AWS Region that you want to use to send the email. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
// https://docs.aws.amazon.com/pinpoint/latest/apireference/
const aws_region = "us-west-2";

// The "From" address. This address has to be verified in Amazon Pinpoint
// in the region that you use to send email.
const senderAddress = "sender@example.com";

// The address on the "To" line. If your Amazon Pinpoint account is in
// the sandbox, this address also has to be verified.
var toAddress = "recipient@example.com";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
const appId = "ce796be37f32f178af652b26eexample";

// The subject line of the email.
var subject = "Amazon Pinpoint (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
```

```
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https:\/\/aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
var body_html = `<html>
<head></head>
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint API</a> using the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding the you want to use for the subject line and
// message body of the email.
var charset = "UTF-8";

// Specify that you're using a shared credentials file.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: appId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: senderAddress,
```

```
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};

//Try to send the email.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
  } else {
    console.log(
      "Email sent! Message ID: ",
      data["MessageResponse"]["Result"][toAddress]["MessageId"]
    );
  }
});
```

Envie uma mensagem SMS.

```
"use strict";

var AWS = require("aws-sdk");

// The AWS Region that you want to use to send the message. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
```

```
// https://docs.aws.amazon.com/pinpoint/latest/apireference/.
var aws_region = "us-east-1";

// The phone number or short code to send the message from. The phone number
// or short code that you specify has to be associated with your Amazon Pinpoint
// account. For best results, specify long codes in E.164 format.
var originationNumber = "+12065550199";

// The recipient's phone number.  For best results, you should specify the
// phone number in E.164 format.
var destinationNumber = "+14255550142";

// The content of the SMS message.
var message =
  "This message was sent through Amazon Pinpoint " +
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
var applicationId = "ce796be37f32f178af652b26eexample";

// The type of SMS message that you want to send. If you plan to send
// time-sensitive content, specify TRANSACTIONAL. If you plan to send
// marketing-related content, specify PROMOTIONAL.
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
var registeredKeyword = "myKeyword";

// The sender ID to use when sending the message. Support for sender ID
// varies by country or region. For more information, see
// https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-countries.html
var senderId = "MySenderID";

// Specify that you're using a shared credentials file, and optionally specify
// the profile that you want to use.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });
```

```
//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: applicationId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
};

//Try to send the message.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
    // Otherwise, show the unique ID for the message.
  } else {
    console.log(
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  }
});
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

Exemplos de API de voz e SMS do Amazon Pinpoint usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a (v2) AWS SDK for JavaScript com SMS e Voice API do Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar uma mensagem de voz com Amazon Pinpoint SMS e Voice API

O exemplo de código a seguir mostra como enviar uma mensagem de voz com a API SMS and Voice do Amazon Pinpoint.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"use strict";

var AWS = require("aws-sdk");

// The AWS Region that you want to use to send the voice message. For a list of
// AWS Regions where the Amazon Pinpoint SMS and Voice API is available, see
// https://docs.aws.amazon.com/pinpoint-sms-voice/latest/APIReference/
```

```
var aws_region = "us-east-1";

// The phone number that the message is sent from. The phone number that you
// specify has to be associated with your Amazon Pinpoint account. For best results,
 you
// should specify the phone number in E.164 format.
var originationNumber = "+12065550110";

// The recipient's phone number. For best results, you should specify the phone
// number in E.164 format.
var destinationNumber = "+12065550142";

// The language to use when sending the message. For a list of supported
// languages, see https://docs.aws.amazon.com/polly/latest/dg/SupportedLanguage.html
var languageCode = "en-US";

// The Amazon Polly voice that you want to use to send the message. For a list
// of voices, see https://docs.aws.amazon.com/polly/latest/dg/voicelist.html
var voiceId = "Matthew";

// The content of the message. This example uses SSML to customize and control
// certain aspects of the message, such as the volume or the speech rate.
// The message can't contain any line breaks.
var ssmlMessage =
  "<speak>" +
  "This is a test message sent from <emphasis>Amazon Pinpoint</emphasis> " +
  "using the <break strength='weak'/>AWS SDK for JavaScript in Node.js. " +
  "<amazon:effect phonation='soft'>Thank you for listening." +
  "</amazon:effect>" +
  "</speak>";

// The phone number that you want to appear on the recipient's device. The phone
// number that you specify has to be associated with your Amazon Pinpoint account.
var callerId = "+12065550199";

// The configuration set that you want to use to send the message.
var configurationSet = "ConfigSet";

// Specify that you're using a shared credentials file, and optionally specify
// the profile that you want to use.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
```

```
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpointsmsvoice = new AWS.PinpointSMSVoice();

var params = {
  CallerId: callerId,
  ConfigurationSetName: configurationSet,
  Content: {
    SSMLMessage: {
      LanguageCode: languageCode,
      Text: ssmlMessage,
      VoiceId: voiceId,
    },
  },
  DestinationPhoneNumber: destinationNumber,
  OriginationPhoneNumber: originationNumber,
};

//Try to send the message.
pinpointsmsvoice.sendVoiceMessage(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
    // Otherwise, show the unique ID for the message.
  } else {
    console.log("Message sent! Message ID: " + data["MessageId"]);
  }
});
```

- Para obter detalhes da API, consulte SendVoiceMessagea Referência AWS SDK for JavaScript da API.

Exemplos do Amazon RDS usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v2) com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Conectando-se a um banco de dados do Amazon RDS em uma função Lambda

O exemplo de código a seguir mostra como implementar uma função Lambda que se conecta a um banco de dados do RDS. A função faz uma solicitação simples ao banco de dados e retorna o resultado.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Javascript.

```
/*
Node.js code here.
*/
// ES6+ example
import { Signer } from "@aws-sdk/rds-signer";
import mysql from 'mysql2/promise';

async function createAuthToken() {
  // Define connection authentication parameters
  const dbinfo = {
```

```
    hostname: process.env.ProxyHostName,
    port: process.env.Port,
    username: process.env.DBUserName,
    region: process.env.AWS_REGION,

  }

  // Create RDS Signer object
  const signer = new Signer(dbinfo);

  // Request authorization token from RDS, specifying the username
  const token = await signer.getAuthToken();
  return token;
}

async function dbOps() {

  // Obtain auth token
  const token = await createAuthToken();
  // Define connection configuration
  let connectionConfig = {
    host: process.env.ProxyHostName,
    user: process.env.DBUserName,
    password: token,
    database: process.env.DBName,
    ssl: 'Amazon RDS'
  }
  // Create the connection to the DB
  const conn = await mysql.createConnection(connectionConfig);
  // Obtain the result of the query
  const [res,] = await conn.execute('select ?+? as sum', [3, 2]);
  return res;

}

export const handler = async (event) => {
  // Execute database flow
  const result = await dbOps();
  // Return result
  return {
    statusCode: 200,
    body: JSON.stringify("The selected sum is: " + result[0].sum)
  }
```

```
};
```

Exemplos do Amazon S3 usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usand (v2) AWS SDK for JavaScript com Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do S3 com o uso do JavaScript Lambda.

```
const aws = require('aws-sdk');

const s3 = new aws.S3({ apiVersion: '2006-03-01' });

exports.handler = async (event, context) => {
    // Get the object from the event and show its content type
    const bucket = event.Records[0].s3.bucket.name;
    const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
    const params = {
        Bucket: bucket,
        Key: key,
    };
    try {
        const { ContentType } = await s3.headObject(params).promise();
        console.log('CONTENT TYPE:', ContentType);
        return ContentType;
    } catch (err) {
        console.log(err);
        const message = `Error getting object ${key} from bucket ${bucket}. Make
 sure they exist and your bucket is in the same region as this function.`;
        console.log(message);
        throw new Error(message);
    }
};
```

Consumindo um evento do S3 com o uso do TypeScript Lambda.

```
import { S3Event } from 'aws-lambda';
import { S3Client, HeadObjectCommand } from '@aws-sdk/client-s3';

const s3 = new S3Client({ region: process.env.AWS_REGION });

export const handler = async (event: S3Event): Promise<string | undefined> => {
  // Get the object from the event and show its content type
  const bucket = event.Records[0].s3.bucket.name;
  const key = decodeURIComponent(event.Records[0].s3.object.key.replace(/\+/g, '
 '));
  const params = {
    Bucket: bucket,
    Key: key,
  };
```

```
  try {
    const { ContentType } = await s3.send(new HeadObjectCommand(params));
    console.log('CONTENT TYPE:', ContentType);
    return ContentType;
  } catch (err) {
    console.log(err);
    const message = `Error getting object ${key} from bucket ${bucket}. Make sure
 they exist and your bucket is in the same region as this function.`;
    console.log(message);
    throw new Error(message);
  }
};
```

Exemplos do S3 Glacier usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com S3 Glacier.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um carregamento fracionado

O exemplo de código a seguir mostra como executar um upload multipartes de um vault do Amazon S3 Glacier.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um multipart upload de pedaços de 1 megabyte de um objeto Buffer.

```
// Create a new service object and some supporting variables
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" }),
  vaultName = "YOUR_VAULT_NAME",
  buffer = new Buffer(2.5 * 1024 * 1024), // 2.5MB buffer
  partSize = 1024 * 1024, // 1MB chunks,
  numPartsLeft = Math.ceil(buffer.length / partSize),
  startTime = new Date(),
  params = { vaultName: vaultName, partSize: partSize.toString() };

// Compute the complete SHA-256 tree hash so we can pass it
// to completeMultipartUpload request at the end
var treeHash = glacier.computeChecksums(buffer).treeHash;

// Initiate the multipart upload
console.log("Initiating upload to", vaultName);
// Call Glacier to initiate the upload.
glacier.initiateMultipartUpload(params, function (mpErr, multipart) {
  if (mpErr) {
    console.log("Error!", mpErr.stack);
    return;
  }
  console.log("Got upload ID", multipart.uploadId);

  // Grab each partSize chunk and upload it as a part
  for (var i = 0; i < buffer.length; i += partSize) {
    var end = Math.min(i + partSize, buffer.length),
      partParams = {
        vaultName: vaultName,
        uploadId: multipart.uploadId,
        range: "bytes " + i + "-" + (end - 1) + "/*",
        body: buffer.slice(i, end),
      };
```

```
    // Send a single part
    console.log("Uploading part", i, "=", partParams.range);
    glacier.uploadMultipartPart(partParams, function (multiErr, mData) {
      if (multiErr) return;
      console.log("Completed part", this.request.params.range);
      if (--numPartsLeft > 0) return; // complete only when all parts uploaded

      var doneParams = {
        vaultName: vaultName,
        uploadId: multipart.uploadId,
        archiveSize: buffer.length.toString(),
        checksum: treeHash, // the computed tree hash
      };

      console.log("Completing upload...");
      glacier.completeMultipartUpload(doneParams, function (err, data) {
        if (err) {
          console.log("An error occurred while uploading the archive");
          console.log(err);
        } else {
          var delta = (new Date() - startTime) / 1000;
          console.log("Completed upload in", delta, "seconds");
          console.log("Archive ID:", data.archiveId);
          console.log("Checksum:  ", data.checksum);
        }
      });
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadMultipartPart a Referência AWS SDK for JavaScript da API.

Crie um cofre

O exemplo de código a seguir mostra como criar um vault (cofre) do Amazon S3 Glacier.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Criar o cofre.

```
// Load the SDK for JavaScript
import { CreateVaultCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME
const params = { vaultName: vaultname };

const run = async () => {
  try {
    const data = await glacierClient.send(new CreateVaultCommand(params));
    console.log("Success, vault created!");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error");
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
// Call Glacier to create the vault
glacier.createVault({ vaultName: "YOUR_VAULT_NAME" }, function (err) {
  if (!err) {
    console.log("Created vault!");
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

Baixe um arquivo em um cofre

O exemplo de código a seguir mostra como fazer upload de um arquivo em um cofre do Amazon S3 Glacier.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Carregue o arquivo.

```
// Load the SDK for JavaScript
import { UploadArchiveCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME

// Create a new service object and buffer
const buffer = new Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer
const params = { vaultName: vaultname, body: buffer };

const run = async () => {
  try {
    const data = await glacierClient.send(new UploadArchiveCommand(params));
    console.log("Archive ID", data.archiveId);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error uploading archive!", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object and buffer
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
buffer = Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer

var params = { vaultName: "YOUR_VAULT_NAME", body: buffer };
// Call Glacier to upload the archive.
glacier.uploadArchive(params, function (err, data) {
  if (err) {
    console.log("Error uploading archive!", err);
  } else {
    console.log("Archive ID", data.archiveId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

Exemplos do Amazon SNS usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a (v2) AWS SDK for JavaScript com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { GetTopicAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";
```

```
/**
 * @param {string} topicArn - The ARN of the topic to retrieve attributes for.
 */
export const getTopicAttributes = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new GetTopicAttributesCommand({
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '36b6a24e-5473-5d4e-ac32-ff72d9a73d94',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Attributes: {
  //     Policy: '{...}',
  //     Owner: 'xxxxxxxxxxxx',
  //     SubscriptionsPending: '1',
  //     TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic',
  //     TracingConfig: 'PassThrough',
  //     EffectiveDeliveryPolicy: '{"http":{"defaultHealthyRetryPolicy":
{"minDelayTarget":20,"maxDelayTarget":20,"numRetries":3,"numMaxDelayRetries":0,"numNoDelayRe
{"headerContentType":"text/plain; charset=UTF-8"}}}',
  //     SubscriptionsConfirmed: '0',
  //     DisplayName: '',
  //     SubscriptionsDeleted: '1'
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set region
AWS.config.update({ region: "REGION" });

// Create promise and SNS service object
var getTopicAttribsPromise = new AWS.SNS({ apiVersion: "2010-03-31" })
  .getTopicAttributes({ TopicArn: "TOPIC_ARN" })
  .promise();

// Handle promise's fulfilled/rejected states
getTopicAttribsPromise
  .then(function (data) {
    console.log(data);
  })
  .catch(function (err) {
    console.error(err, err.stack);
  });
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento do SNS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};

async function processMessageAsync(record) {
  try {
    const message = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento do SNS com o TypeScript Lambda usando.

```
import { SNSEvent, Context, SNSHandler, SNSEventRecord } from "aws-lambda";

export const functionHandler: SNSHandler = async (
  event: SNSEvent,
  context: Context
): Promise<void> => {
  for (const record of event.Records) {
    await processMessageAsync(record);
  }
  console.info("done");
};
```

```
async function processMessageAsync(record: SNSEventRecord): Promise<any> {
  try {
    const message: string = JSON.stringify(record.Sns.Message);
    console.log(`Processed message ${message}`);
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Exemplos do Amazon SQS usando SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Alterar a visibilidade do tempo limite da mensagem

O exemplo de código a seguir mostra como alterar a visibilidade do tempo limite da mensagem do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
import {
  ReceiveMessageCommand,
  ChangeMessageVisibilityCommand,
  SQSClient,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 1,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 1,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  const response = await client.send(
    new ChangeMessageVisibilityCommand({
      QueueUrl: queueUrl,
      ReceiptHandle: Messages[0].ReceiptHandle,
      VisibilityTimeout: 20,
    }),
  );
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region to us-west-2
AWS.config.update({ region: "us-west-2" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "https://sqs.REGION.amazonaws.com/ACCOUNT-ID/QUEUE-NAME";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Receive Error", err);
  } else {
    // Make sure we have a message
    if (data.Messages != null) {
      var visibilityParams = {
        QueueUrl: queueURL,
        ReceiptHandle: data.Messages[0].ReceiptHandle,
        VisibilityTimeout: 20, // 20 second timeout
      };
```

```
      sqs.changeMessageVisibility(visibilityParams, function (err, data) {
        if (err) {
          console.log("Delete Error", err);
        } else {
          console.log("Timeout Changed", data);
        }
      });
    } else {
      console.log("No messages to change");
    }
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "test-queue";

export const main = async (sqsQueueName = SQS_QUEUE_NAME) => {
  const command = new CreateQueueCommand({
    QueueName: sqsQueueName,
    Attributes: {
```

```
      DelaySeconds: "60",
      MessageRetentionPeriod: "86400",
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

Crie uma fila do Amazon SQS com sondagem longa.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "queue_name";

export const main = async (queueName = SQS_QUEUE_NAME) => {
  const response = await client.send(
    new CreateQueueCommand({
      QueueName: queueName,
      Attributes: {
        // When the wait time for the ReceiveMessage API action is greater than 0,
        // long polling is in effect. The maximum long polling wait time is 20
        // seconds. Long polling helps reduce the cost of using Amazon SQS by,
        // eliminating the number of empty responses and false empty responses.
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        ReceiveMessageWaitTimeSeconds: "20",
      },
    }),
  );
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    DelaySeconds: "60",
    MessageRetentionPeriod: "86400",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

Crie uma fila do Amazon SQS que aguarda a chegada de uma mensagem.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    ReceiveMessageWaitTimeSeconds: "20",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
```

```
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
```

```
};
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 10,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  VisibilityTimeout: 20,
  WaitTimeSeconds: 0,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Receive Error", err);
  } else if (data.Messages) {
    var deleteParams = {
      QueueUrl: queueURL,
      ReceiptHandle: data.Messages[0].ReceiptHandle,
    };
```

```
    sqs.deleteMessage(deleteParams, function (err, data) {
      if (err) {
        console.log("Delete Error", err);
      } else {
        console.log("Message Deleted", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
import { DeleteQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "test-queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new DeleteQueueCommand({ QueueUrl: queueUrl });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueUrl: "SQS_QUEUE_URL",
};

sqs.deleteQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
import { GetQueueUrlCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "test-queue";

export const main = async (queueName = SQS_QUEUE_NAME) => {
  const command = new GetQueueUrlCommand({ QueueName: queueName });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
};

sqs.getQueueUrl(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

Listar filas

O exemplo de código a seguir mostra como listar filas do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
import { paginateListQueues, SQSClient } from "@aws-sdk/client-sqs";
```

```
const client = new SQSClient({});

export const main = async () => {
  const paginatedListQueues = paginateListQueues({ client }, {});

  /** @type {string[]} */
  const urls = [];
  for await (const page of paginatedListQueues) {
    const nextUrls = page.QueueUrls?.filter((qurl) => !!qurl) || [];
    urls.push(...nextUrls);
    urls.forEach((url) => console.log(url));
  }

  return urls;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {};

sqs.listQueues(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrls);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
```

```
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
import { ReceiveMessageCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new ReceiveMessageCommand({
```

```
    AttributeNames: ["SentTimestamp"],
    MaxNumberOfMessages: 1,
    MessageAttributeNames: ["All"],
    QueueUrl: queueUrl,
    // The duration (in seconds) for which the call waits for a message
    // to arrive in the queue before returning. If a message is available,
    // the call returns sooner than WaitTimeSeconds. If no messages are
    // available and the wait time expires, the call returns successfully
    // with an empty list of messages.
    // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/APIReference/
API_ReceiveMessage.html#API_ReceiveMessage_RequestSyntax
    WaitTimeSeconds: 20,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";
```

```
var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  WaitTimeSeconds: 20,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
import { SendMessageCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

export const main = async (sqsQueueUrl = SQS_QUEUE_URL) => {
```

```
  const command = new SendMessageCommand({
    QueueUrl: sqsQueueUrl,
    DelaySeconds: 10,
    MessageAttributes: {
      Title: {
        DataType: "String",
        StringValue: "The Whistler",
      },
      Author: {
        DataType: "String",
        StringValue: "John Grisham",
      },
      WeeksOn: {
        DataType: "Number",
        StringValue: "6",
      },
    },
    MessageBody:
      "Information about current NY Times fiction bestseller for week of
 12/11/2016.",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
```

```
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  // Remove DelaySeconds parameter and value for FIFO queues
  DelaySeconds: 10,
  MessageAttributes: {
    Title: {
      DataType: "String",
      StringValue: "The Whistler",
    },
    Author: {
      DataType: "String",
      StringValue: "John Grisham",
    },
    WeeksOn: {
      DataType: "Number",
      StringValue: "6",
    },
  },
  MessageBody:
    "Information about current NY Times fiction bestseller for week of 12/11/2016.",
  // MessageDeduplicationId: "TheWhistler",  // Required for FIFO queues
  // MessageGroupId: "Group1",  // Required for FIFO queues
  QueueUrl: "SQS_QUEUE_URL",
};

sqs.sendMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.MessageId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumindo um evento SQS com o JavaScript Lambda usando.

```
exports.handler = async (event, context) => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message) {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

Consumindo um evento SQS com o TypeScript Lambda usando.

```
import { SQSEvent, Context, SQSHandler, SQSRecord } from "aws-lambda";
```

```
export const functionHandler: SQSHandler = async (
  event: SQSEvent,
  context: Context
): Promise<void> => {
  for (const message of event.Records) {
    await processMessageAsync(message);
  }
  console.info("done");
};

async function processMessageAsync(message: SQSRecord): Promise<any> {
  try {
    console.log(`Processed message ${message.body}`);
    // TODO: Do interesting work based on the new message
    await Promise.resolve(1); //Placeholder for actual async work
  } catch (err) {
    console.error("An error occurred");
    throw err;
  }
}
```

AWS STSexemplos usando o SDK para JavaScript (v2)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando (v2) AWS SDK for JavaScript com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
import { STSClient } from "@aws-sdk/client-sts";
// Set the AWS Region.
const REGION = "us-east-1";
// Create an AWS STS service client object.
export const client = new STSClient({ region: REGION });
```

Assuma um perfil do IAM.

```
import { AssumeRoleCommand } from "@aws-sdk/client-sts";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Returns a set of temporary security credentials that you can use to
    // access Amazon Web Services resources that you might not normally
    // have access to.
    const command = new AssumeRoleCommand({
      // The Amazon Resource Name (ARN) of the role to assume.
      RoleArn: "ROLE_ARN",
      // An identifier for the assumed role session.
      RoleSessionName: "session1",
      // The duration, in seconds, of the role session. The value specified
      // can range from 900 seconds (15 minutes) up to the maximum session
      // duration set for the role.
      DurationSeconds: 900,
```

```
    });
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
const AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

var roleToAssume = {
  RoleArn: "arn:aws:iam::123456789012:role/RoleName",
  RoleSessionName: "session1",
  DurationSeconds: 900,
};
var roleCreds;

// Create the STS service object
var sts = new AWS.STS({ apiVersion: "2011-06-15" });

//Assume Role
sts.assumeRole(roleToAssume, function (err, data) {
  if (err) console.log(err, err.stack);
  else {
    roleCreds = {
      accessKeyId: data.Credentials.AccessKeyId,
      secretAccessKey: data.Credentials.SecretAccessKey,
      sessionToken: data.Credentials.SessionToken,
```

```
    };
    stsGetCallerIdentity(roleCreds);
  }
});

//Get Arn of current identity
function stsGetCallerIdentity(creds) {
  var stsParams = { credentials: creds };
  // Create STS service object
  var sts = new AWS.STS(stsParams);

  sts.getCallerIdentity({}, function (err, data) {
    if (err) {
      console.log(err, err.stack);
    } else {
      console.log(data.Arn);
    }
  });
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

Exemplos de serviços cruzados usando o SDK para JavaScript (v2)

Os aplicativos de exemplo a seguir usam o AWS SDK for JavaScript (v2) para trabalhar em váriosServiços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Chamar uma função do Lambda em um navegador

Chamar uma função do Lambda em um navegador

SDK para JavaScript (v2)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

SDK para JavaScript (v3)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário. Essa aplicação usa o AWS SDK for JavaScript v3.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

Exemplos de código para SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como usar o (v3) AWS SDK for JavaScript com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para JavaScript (v3) — Saiba mais sobre como usar JavaScript com. AWS
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.

- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para JavaScript (v3)
- Exemplos de serviços cruzados usando o SDK para JavaScript (v3)

Ações e cenários usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de Auto Scaling usando SDK para JavaScript (v3)
- Exemplos do Amazon Bedrock usando o SDK para JavaScript (v3)
- Exemplos do Amazon Bedrock Runtime usando SDK para JavaScript (v3)
- CloudWatch exemplos usando o SDK para JavaScript (v3)
- CloudWatch Exemplos de eventos usando o SDK para JavaScript (v3)
- CloudWatch Exemplos de registros usando o SDK para JavaScript (v3)
- CodeBuild exemplos usando o SDK para JavaScript (v3)
- Exemplos de provedores de identidade Amazon Cognito usando SDK para JavaScript (v3)
- Exemplos do DynamoDB usando o SDK JavaScript para (v3)
- Exemplos do Amazon EC2 usando SDK para JavaScript (v3)
- Exemplos de Elastic Load Balancing usando SDK para JavaScript (v3)
- EventBridge exemplos usando o SDK para JavaScript (v3)
- AWS Glueexemplos usando o SDK para JavaScript (v3)
- HealthImaging exemplos usando o SDK para JavaScript (v3)

- Exemplos de IAM usando SDK para JavaScript (v3)
- Exemplos de Lambda usando SDK para JavaScript (v3)
- Exemplos do Amazon Personalize usando SDK para JavaScript (v3)
- Exemplos de eventos do Amazon Personalize usando SDK para JavaScript (v3)
- Exemplos do Amazon Personalize Runtime usando SDK para JavaScript (v3)
- Exemplos do Amazon Pinpoint usando SDK para JavaScript (v3)
- Exemplos do Amazon Redshift usando SDK para JavaScript (v3)
- Exemplos do Amazon S3 usando SDK para JavaScript (v3)
- Exemplos do S3 Glacier usando SDK para JavaScript (v3)
- SageMaker exemplos usando o SDK para JavaScript (v3)
- Exemplos de Secrets Manager usando SDK para JavaScript (v3)
- Exemplos do Amazon SES usando SDK para JavaScript (v3)
- Exemplos do Amazon SNS usando SDK para JavaScript (v3)
- Exemplos do Amazon SQS usando SDK para JavaScript (v3)
- Exemplos de Step Functions usando o SDK para JavaScript (v3)
- AWS STSexemplos usando o SDK para JavaScript (v3)
- AWS Supportexemplos usando o SDK para JavaScript (v3)
- Exemplos do Amazon Transcribe usando SDK JavaScript para (v3)

Exemplos de Auto Scaling usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar um grupo de destino ELB ao grupo do Auto Scaling

O exemplo de código a seguir mostra como anexar um grupo destino ELB a um grupo Auto Scaling.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new AutoScalingClient({});
await client.send(
  new AttachLoadBalancerTargetGroupsCommand({
    AutoScalingGroupName: NAMES.autoScalingGroupName,
    TargetGroupARNs: [state.targetGroupArn],
  }),
);
```

- Para obter detalhes da API, consulte AttachLoadBalancerTargetGroupsa Referência AWS SDK for JavaScript da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.

- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
```

```
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
```

```
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
```

```
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
```

```
            KeyType: "RANGE",
          },
        ],
      }),
    );
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item'][] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
```

```
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
```

```
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
```

```
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
```

```
    ),
    ...initParamsSteps,
    new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
    new ScenarioAction("createLaunchTemplate", async () => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
      const ssmClient = new SSMClient({});
      const { Parameter } = await ssmClient.send(
        new GetParameterCommand({
          Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
        }),
      );
      const ec2Client = new EC2Client({});
      await ec2Client.send(
        new CreateLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
          LaunchTemplateData: {
            InstanceType: "t3.micro",
            ImageId: Parameter.Value,
            IamInstanceProfile: { Name: NAMES.instanceProfileName },
            UserData: readFileSync(
              join(RESOURCES_PATH, "server_startup_script.sh"),
            ).toString("base64"),
            KeyName: NAMES.keyPairName,
          },
        }),
        // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
      );
    }),
    new ScenarioOutput(
      "createdLaunchTemplate",
      MESSAGES.createdLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      ),
    ),
    new ScenarioOutput(
      "creatingAutoScalingGroup",
      MESSAGES.creatingAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      ),
    ),
    new ScenarioAction("createAutoScalingGroup", async (state) => {
      const ec2Client = new EC2Client({});
```

```
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
```

```
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
  }),
  new ScenarioOutput("gotVpc", (state) =>
    MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
  ),
  new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
  new ScenarioAction("getSubnets", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
```

```
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
```

```
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
```

```
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-ec2').SecurityGroup}}
state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
```

```
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
```

```
        return;
      }

      const client = new EC2Client({});
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
```

```
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
```

```
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
```

```
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
```

```
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
```

```
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
```

```
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-scaling').Instance }}
 state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
```

```
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
```

```
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-ssm').InstanceInformation}}
 state
     */
    (state) =>
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
```

```
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
```

```
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
```

```
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );
```

```
  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
```

```
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
```

```
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
```

```
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
```

```
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
```

```
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
```

```
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
```

```
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
```

```
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
```

```
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
```

```
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
```

```
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
```

```
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
```

```
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate

- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Bedrock

Os exemplos de código a seguir mostram como começar a usar o Amazon Bedrock.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { fileURLToPath } from 'url';

import { BedrockClient, ListFoundationModelsCommand } from '@aws-sdk/client-
bedrock';

const REGION = 'us-east-1';
const client = new BedrockClient({ region: REGION });

export const main = async () => {
    const command = new ListFoundationModelsCommand({});

    const response = await client.send(command);
    const models = response.modelSummaries;

    console.log('Listing the available Bedrock foundation models:');

    for (let model of models) {
        console.log('='.repeat(42));
        console.log(` Model: ${model.modelId}`);
        console.log('-'.repeat(42));
        console.log(` Name: ${model.modelName}`);
        console.log(` Provider: ${model.providerName}`);
        console.log(` Model ARN: ${model.modelArn}`);
        console.log(` Input modalities: ${model.inputModalities}`);
        console.log(` Output modalities: ${model.outputModalities}`);
        console.log(` Supported customizations: ${model.customizationsSupported}`);
        console.log(` Supported inference types: ${model.inferenceTypesSupported}`);
        console.log(` Lifecycle status: ${model.modelLifecycle.status}`);
        console.log('='.repeat(42) + '\n');
    }
```

```
    const active = models.filter(m => m.modelLifecycle.status === 'ACTIVE').length;
    const legacy = models.filter(m => m.modelLifecycle.status === 'LEGACY').length;

    console.log(`There are ${active} active and ${legacy} legacy foundation models
 in ${REGION}.`);

    return response;
};

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    await main();
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações

Ações

Ver detalhes sobre um modelo de base do Amazon Bedrock

O exemplo de código a seguir mostra como ver detalhes de um modelo de base do Amazon Bedrock.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Veja detalhes sobre um modelo de base.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
```

```
import { fileURLToPath } from 'url';

import { BedrockClient, GetFoundationModelCommand } from '@aws-sdk/client-bedrock';

/**
 * Get details about an Amazon Bedrock foundation model.
 *
 * @return {FoundationModelDetails} - The list of available bedrock foundation
 models.
 */
export const getFoundationModel = async () => {
    const client = new BedrockClient();

    const command = new GetFoundationModelCommand({
        modelIdentifier: 'amazon.titan-embed-text-v1'
    });

    const response = await client.send(command);

    return response.modelDetails;
};

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const model = await getFoundationModel();
    console.log(model);
}
```

- Para obter detalhes da API, consulte GetFoundationModela Referência AWS SDK for JavaScript da API.

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { fileURLToPath } from 'url';

import { BedrockClient, ListFoundationModelsCommand } from '@aws-sdk/client-
bedrock';

/**
 * List the available Amazon Bedrock foundation models.
 *
 * @return {FoundationModelSummary[]} - The list of available bedrock foundation
 models.
 */
export const listFoundationModels = async () => {
    const client = new BedrockClient();

    const input = {
        // byProvider: 'STRING_VALUE',
        // byCustomizationType: 'FINE_TUNING' || 'CONTINUED_PRE_TRAINING',
        // byOutputModality: 'TEXT' || 'IMAGE' || 'EMBEDDING',
        // byInferenceType: 'ON_DEMAND' || 'PROVISIONED',
    };

    const command = new ListFoundationModelsCommand(input);

    const response = await client.send(command);

    return response.modelSummaries;
}

// Invoke main function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
```

```
    const models = await listFoundationModels();
    console.log(models);
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for JavaScript da API.

Exemplos do Amazon Bedrock Runtime usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo Jurassic-2 da AI21 Labs no Amazon Bedrock para geração de texto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} Data
 * @property {string} text
 *
 * @typedef {Object} Completion
 * @property {Data} data
 *
 * @typedef {Object} ResponseBody
 * @property {Completion[]} completions
 */

/**
 * Invokes the AI21 Labs Jurassic-2 large-language model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Jurassic-2 to complete.
 * @returns {string} The inference response (completion) from the model.
 */
export const invokeJurassic2 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'ai21.j2-mid-v1';

    /* The different model providers have individual request and response formats.
     * For the format, ranges, and default values for AI21 Labs Jurassic-2, refer
 to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html
     */
    const payload = {
        prompt,
        maxTokens: 500,
        temperature: 0.5,
    };
```

```
    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.completions[0].data.text;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: AI21 Labs Jurassic-2');
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeJurassic2(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

Geração de texto com o Amazon Titan Text G1

O exemplo de código a seguir mostra como invocar o modelo Amazon Titan Text G1 no Amazon Bedrock para geração de texto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo básico Amazon Titan Text G1 para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} ResponseBody
 * @property {Object[]} results
 */

/**
 * Invokes the Titan Text G1 - Express model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Titan Text Express to complete.
 * @returns {object[]} The inference response (results) from the model.
 */
export const invokeTitanTextExpressV1 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'amazon.titan-text-express-v1';

    /* The different model providers have individual request and response formats.
     * For the format, ranges, and default values for Titan text, refer to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-titan-
text.html
     */
    const textGenerationConfig = {
        maxTokenCount: 4096,
        stopSequences: [],
```

```
        temperature: 0,
        topP: 1,
    };

    const payload = {
        inputText: prompt,
        textGenerationConfig,
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);
        return responseBody.results

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = `Meeting transcript: Miguel: Hi Brant, I want to discuss the
 workstream
    for our new product launch Brant: Sure Miguel, is there anything in particular
 you want
    to discuss? Miguel: Yes, I want to talk about how users enter into the product.
    Brant: Ok, in that case let me add in Namita. Namita: Hey everyone
    Brant: Hi Namita, Miguel wants to discuss how users enter into the product.
    Miguel: its too complicated and we should remove friction.
    for example, why do I need to fill out additional forms?
    I also find it difficult to find where to access the product
    when I first land on the landing page. Brant: I would also add that
    I think there are too many steps. Namita: Ok, I can work on the
    landing page to make the product more discoverable but brant
```

```
    can you work on the additonal forms? Brant: Yes but I would need
    to work with James from another team as he needs to unblock the sign up
 workflow.
    Miguel can you document any other concerns so that I can discuss with James only
 once?
    Miguel: Sure.
    From the meeting transcript above, Create a list of action items for each
 person.`;

    console.log('\nModel: Titan Text Express v1');
    console.log(`Prompt: ${prompt}`);

    const results = await invokeTitanTextExpressV1(prompt);
    console.log('Completion:');
    for (const result of results) {
        console.log(result.outputText);
    }
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
```

```
import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} ResponseBody
 * @property {string} completion
 */

/**
 * Invokes the Anthropic Claude 2 model to run an inference using the input
 * provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Claude to complete.
 * @returns {string} The inference response (completion) from the model.
 */
export const invokeClaude = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'anthropic.claude-v2';

    /* Claude requires you to enclose the prompt as follows: */
    const enclosedPrompt = `Human: ${prompt}\n\nAssistant:`;

    /* The different model providers have individual request and response formats.
     * For the format, ranges, and default values for Anthropic Claude, refer to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
     */
    const payload = {
        prompt: enclosedPrompt,
        max_tokens_to_sample: 500,
        temperature: 0.5,
        stop_sequences: [ '\n\nHuman:' ],
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
    });
```

```
    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.completion;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: Anthropic Claude v2');
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeClaude(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat da Meta Llama 2 no Amazon Bedrock para geração de texto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {fileURLToPath} from "url";

import {BedrockRuntimeClient, InvokeModelCommand} from "@aws-sdk/client-bedrock-
runtime";

/**
 * @typedef {Object} ResponseBody
 * @property {generation} text
 */

/**
 * Invokes the Meta Llama 2 Chat model to run an inference
 * using the input provided in the request body.
 *
 * @param {string} prompt - The prompt that you want Llama-2 to complete.
 * @returns {string} The inference response (generation) from the model.
 */
export const invokeLlama2 = async (prompt) => {
    const client = new BedrockRuntimeClient( { region: 'us-east-1' } );

    const modelId = 'meta.llama2-13b-chat-v1';

    /* The different model providers have individual request and response formats.
     * For the format, ranges, and default values for Meta Llama 2 Chat, refer to:
     * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html
     */
    const payload = {
        prompt,
        temperature: 0.5,
        top_p: 0.9,
        max_gen_len: 512,
    };

    const command = new InvokeModelCommand({
        body: JSON.stringify(payload),
        contentType: 'application/json',
        accept: 'application/json',
        modelId,
```

```
    });

    try {
        const response = await client.send(command);
        const decodedResponseBody = new TextDecoder().decode(response.body);

        /** @type {ResponseBody} */
        const responseBody = JSON.parse(decodedResponseBody);

        return responseBody.generation;

    } catch (err) {
        console.error(err);
    }
};

// Invoke the function if this file was run directly.
if (process.argv[1] === fileURLToPath(import.meta.url)) {
    const prompt = 'Complete the following: "Once upon a time..."';
    console.log('\nModel: Meta Llama 2 Chat');
    console.log(`Prompt: ${prompt}`);

    const completion = await invokeLlama2(prompt);
    console.log('Completion:');
    console.log(completion);
    console.log('\n');
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for JavaScript da API.

CloudWatch exemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricAlarmCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  // This alarm triggers when CPUUtilization exceeds 70% for one minute.
  const command = new PutMetricAlarmCommand({
    AlarmName: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
    ComparisonOperator: "GreaterThanThreshold",
    EvaluationPeriods: 1,
    MetricName: "CPUUtilization",
    Namespace: "AWS/EC2",
    Period: 60,
```

```
    Statistic: "Average",
    Threshold: 70.0,
    ActionsEnabled: false,
    AlarmDescription: "Alarm when server CPU exceeds 70%",
    Dimensions: [
      {
        Name: "InstanceId",
        Value: process.env.EC2_INSTANCE_ID, // Set the value of EC_INSTANCE_ID to
 the Id of an existing Amazon EC2 instance.
      },
    ],
    Unit: "Percent",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: false,
  AlarmDescription: "Alarm when server CPU exceeds 70%",
  Dimensions: [
    {
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
};

cw.putMetricAlarm(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for JavaScript da API.

Excluir alarmes

O exemplo de código a seguir mostra como excluir CloudWatch alarmes da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DeleteAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteAlarmsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmNames: ["Web_Server_CPU_Utilization"],
};

cw.deleteAlarms(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for JavaScript da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DescribeAlarmsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DescribeAlarmsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.describeAlarms({ StateValue: "INSUFFICIENT_DATA" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    // List the names of all current alarms in the console
    data.MetricAlarms.forEach(function (item, index, array) {
      console.log(item.AlarmName);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for JavaScript da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { DisableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DisableAlarmActionsCommand({
    AlarmNames: process.env.CLOUDWATCH_ALARM_NAME, // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

cw.disableAlarmActions(
  { AlarmNames: ["Web_Server_CPU_Utilization"] },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for JavaScript da API.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EnableAlarmActionsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new EnableAlarmActionsCommand({
    AlarmNames: [process.env.CLOUDWATCH_ALARM_NAME], // Set the value of
 CLOUDWATCH_ALARM_NAME to the name of an existing alarm.
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

var params = {
  AlarmName: "Web_Server_CPU_Utilization",
  ComparisonOperator: "GreaterThanThreshold",
  EvaluationPeriods: 1,
  MetricName: "CPUUtilization",
  Namespace: "AWS/EC2",
  Period: 60,
  Statistic: "Average",
  Threshold: 70.0,
  ActionsEnabled: true,
  AlarmActions: ["ACTION_ARN"],
  AlarmDescription: "Alarm when server CPU exceeds 70%",
  Dimensions: [
    {
      Name: "InstanceId",
      Value: "INSTANCE_ID",
    },
  ],
  Unit: "Percent",
};

cw.putMetricAlarm(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
```

```
    console.log("Alarm action added", data);
    var paramsEnableAlarmAction = {
      AlarmNames: [params.AlarmName],
    };
    cw.enableAlarmActions(paramsEnableAlarmAction, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Alarm action enabled", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for JavaScript da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListMetricsCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

export const main = () => {
  // Use the AWS console to see available namespaces and metric names. Custom
 metrics can also be created.
```

```
  // https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
viewing_metrics_with_cloudwatch.html
  const command = new ListMetricsCommand({
    Dimensions: [
      {
        Name: "LogGroupName",
      },
    ],
    MetricName: "IncomingLogEvents",
    Namespace: "AWS/Logs",
  });

  return client.send(command);
};
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });
```

```
var params = {
  Dimensions: [
    {
      Name: "LogGroupName" /* required */,
    },
  ],
  MetricName: "IncomingLogEvents",
  Namespace: "AWS/Logs",
};

cw.listMetrics(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Metrics", JSON.stringify(data.Metrics));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for JavaScript da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutMetricDataCommand } from "@aws-sdk/client-cloudwatch";
import { client } from "../libs/client.js";

const run = async () => {
```

```
  // See https://docs.aws.amazon.com/AmazonCloudWatch/latest/APIReference/
API_PutMetricData.html#API_PutMetricData_RequestParameters
  // and https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
publishingMetrics.html
  // for more information about the parameters in this command.
  const command = new PutMetricDataCommand({
    MetricData: [
      {
        MetricName: "PAGES_VISITED",
        Dimensions: [
          {
            Name: "UNIQUE_PAGES",
            Value: "URLS",
          },
        ],
        Unit: "None",
        Value: 1.0,
      },
    ],
    Namespace: "SITE/TRAFFIC",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchClient } from "@aws-sdk/client-cloudwatch";

export const client = new CloudWatchClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatch service object
var cw = new AWS.CloudWatch({ apiVersion: "2010-08-01" });

// Create parameters JSON for putMetricData
var params = {
  MetricData: [
    {
      MetricName: "PAGES_VISITED",
      Dimensions: [
        {
          Name: "UNIQUE_PAGES",
          Value: "URLS",
        },
      ],
      Unit: "None",
      Value: 1.0,
    },
  ],
  Namespace: "SITE/TRAFFIC",
};

cw.putMetricData(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", JSON.stringify(data));
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for JavaScript da API.

CloudWatch Exemplos de eventos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com CloudWatch Eventos.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adição de um destino

O exemplo de código a seguir mostra como adicionar um alvo a um evento da Amazon CloudWatch Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutTargetsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutTargetsCommand({
    // The name of the Amazon CloudWatch Events rule.
    Rule: process.env.CLOUDWATCH_EVENTS_RULE,

    // The targets to add to the rule.
    Targets: [
      {
        Arn: process.env.CLOUDWATCH_EVENTS_TARGET_ARN,
        // The ID of the target. Choose a unique ID for each target.
        Id: process.env.CLOUDWATCH_EVENTS_TARGET_ID,
      },
    ],
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myCloudWatchEventsTarget",
    },
  ],
};

cwevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Criar uma regra agendada

O exemplo de código a seguir mostra como criar uma regra programada do Amazon CloudWatch Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutRuleCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  // Request parameters for PutRule.
  // https://docs.aws.amazon.com/eventbridge/latest/APIReference/
API_PutRule.html#API_PutRule_RequestParameters
  const command = new PutRuleCommand({
    Name: process.env.CLOUDWATCH_EVENTS_RULE,

    // The event pattern for the rule.
    //  Example: {"source": ["my.app"]}
    EventPattern: process.env.CLOUDWATCH_EVENTS_RULE_PATTERN,

    // The state of the rule. Valid values: ENABLED, DISABLED
    State: "ENABLED",
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

cwevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.RuleArn);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar CloudWatch eventos da Amazon Events.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { PutEventsCommand } from "@aws-sdk/client-cloudwatch-events";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutEventsCommand({
    // The list of events to send to Amazon CloudWatch Events.
    Entries: [
      {
        // The name of the application or service that is sending the event.
        Source: "my.app",

        // The name of the event that is being sent.
        DetailType: "My Custom Event",

        // The data that is sent with the event.
        Detail: JSON.stringify({ timeOfEvent: new Date().toISOString() }),
      },
    ],
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
```

```
  }
};

export default run();
```

Crie o cliente em um módulo separado e exporte-o.

```
import { CloudWatchEventsClient } from "@aws-sdk/client-cloudwatch-events";

export const client = new CloudWatchEventsClient({});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var cwevents = new AWS.CloudWatchEvents({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
    },
  ],
```

```
};

cwevents.putEvents(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

CloudWatch Exemplos de registros usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo de logs

O exemplo de código a seguir mostra como criar um novo grupo de CloudWatch registros de registros.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateLogGroupCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new CreateLogGroupCommand({
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte CreateLogGroupa Referência AWS SDK for JavaScript da API.

Criar um filtro de assinatura

O exemplo de código a seguir mostra como criar um filtro de assinatura do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { PutSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new PutSubscriptionFilterCommand({
    // An ARN of a same-account Kinesis stream, Kinesis Firehose
    // delivery stream, or Lambda function.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
SubscriptionFilters.html
    destinationArn: process.env.CLOUDWATCH_LOGS_DESTINATION_ARN,

    // A name for the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,

    // A filter pattern for subscribing to a filtered stream of log events.
    // https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/
FilterAndPatternSyntax.html
    filterPattern: process.env.CLOUDWATCH_LOGS_FILTER_PATTERN,

    // The name of the log group. Messages in this group matching the filter pattern
    // will be sent to the destination ARN.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  destinationArn: "LAMBDA_FUNCTION_ARN",
  filterName: "FILTER_NAME",
  filterPattern: "ERROR",
  logGroupName: "LOG_GROUP",
};

cwl.putSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Excluir o grupo de logs.

O exemplo de código a seguir mostra como excluir um grupo de CloudWatch registros de registros existente.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteLogGroupCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteLogGroupCommand({
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DeleteLogGroupa Referência AWS SDK for JavaScript da API.

Excluir um filtro de assinatura

O exemplo de código a seguir mostra como excluir um filtro de assinatura do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSubscriptionFilterCommand } from "@aws-sdk/client-cloudwatch-logs";
import { client } from "../libs/client.js";

const run = async () => {
  const command = new DeleteSubscriptionFilterCommand({
    // The name of the filter.
    filterName: process.env.CLOUDWATCH_LOGS_FILTER_NAME,
    // The name of the log group.
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
```

```
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  filterName: "FILTER",
  logGroupName: "LOG_GROUP",
};

cwl.deleteSubscriptionFilter(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for JavaScript da API.

Descreva os filtros de assinatura existentes

O exemplo de código a seguir mostra como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSubscriptionFiltersCommand } from "@aws-sdk/client-cloudwatch-
logs";
```

```
import { client } from "../libs/client.js";

const run = async () => {
  // This will return a list of all subscription filters in your account
  // matching the log group name.
  const command = new DescribeSubscriptionFiltersCommand({
    logGroupName: process.env.CLOUDWATCH_LOGS_LOG_GROUP,
    limit: 1,
  });

  try {
    return await client.send(command);
  } catch (err) {
    console.error(err);
  }
};

export default run();
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the CloudWatchLogs service object
var cwl = new AWS.CloudWatchLogs({ apiVersion: "2014-03-28" });

var params = {
  logGroupName: "GROUP_NAME",
  limit: 5,
};
```

```
cwl.describeSubscriptionFilters(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.subscriptionFilters);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeSubscriptionFilterssa Referência AWS SDK for JavaScript da API.

Descrever grupos de logs

O exemplo de código a seguir mostra como descrever grupos de CloudWatch registros de registros.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateDescribeLogGroups,
  CloudWatchLogsClient,
} from "@aws-sdk/client-cloudwatch-logs";

const client = new CloudWatchLogsClient({});

export const main = async () => {
  const paginatedLogGroups = paginateDescribeLogGroups({ client }, {});
  const logGroups = [];

  for await (const page of paginatedLogGroups) {
    if (page.logGroups && page.logGroups.every((lg) => !!lg)) {
      logGroups.push(...page.logGroups);
    }
```

```
  }

  console.log(logGroups);
  return logGroups;
};
```

- Para obter detalhes da API, consulte DescribeLogGroupsa Referência AWS SDK for JavaScript da API.

Receber resultados de uma consulta

O exemplo de código a seguir mostra como receber os resultados de uma consulta.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Simple wrapper for the GetQueryResultsCommand.
 * @param {string} queryId
 */
_getQueryResults(queryId) {
  return this.client.send(new GetQueryResultsCommand({ queryId }));
}
```

- Para obter detalhes da API, consulte GetQueryResultsa Referência AWS SDK for JavaScript da API.

Iniciar uma sessão Live Tail

O código de exemplo a seguir mostra como começar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

SDK para JavaScript (v3)

Inclua os arquivos necessários.

```
import { CloudWatchLogsClient, StartLiveTailCommand } from "@aws-sdk/client-
cloudwatch-logs";
```

Gerencie os eventos da sessão do Live Tail.

```
async function handleResponseAsync(response) {
    try {
      for await (const event of response.responseStream) {
        if (event.sessionStart !== undefined) {
          console.log(event.sessionStart);
        } else if (event.sessionUpdate !== undefined) {
          for (const logEvent of event.sessionUpdate.sessionResults) {
            const timestamp = logEvent.timestamp;
            const date = new Date(timestamp);
            console.log("[" + date + "] " + logEvent.message);
          }
        } else {
            console.error("Unknown event type");
        }
      }
    } catch (err) {
        // On-stream exceptions are captured here
        console.error(err)
    }
}
```

Inicie a sessão do Live Tail.

```
    const client = new CloudWatchLogsClient();

    const command = new StartLiveTailCommand({
        logGroupIdentifiers: logGroupIdentifiers,
        logStreamNames: logStreamNames,
        logEventFilterPattern: filterPattern
    });
    try{
```

```
        const response = await client.send(command);
        handleResponseAsync(response);
    } catch (err){
        // Pre-stream exceptions are captured here
        console.log(err);
    }
```

Interrompa a sessão do Live Tail após um período decorrido.

```
    /* Set a timeout to close the client. This will stop the Live Tail session. */
    setTimeout(function() {
        console.log("Client timeout");
        client.destroy();
      }, 10000);
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for JavaScript da API.

Iniciar uma consulta

O exemplo de código a seguir mostra como iniciar uma consulta.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  /**
   * Wrapper for the StartQueryCommand. Uses a static query string
   * for consistency.
   * @param {[Date, Date]} dateRange
   * @param {number} maxLogs
   * @returns {Promise<{ queryId: string }>}
   */
  async _startQuery([startDate, endDate], maxLogs = 10000) {
```

```
    try {
      return await this.client.send(
        new StartQueryCommand({
          logGroupNames: this.logGroupNames,
          queryString: "fields @timestamp, @message | sort @timestamp asc",
          startTime: startDate.valueOf(),
          endTime: endDate.valueOf(),
          limit: maxLogs,
        }),
      );
    } catch (err) {
      /** @type {string} */
      const message = err.message;
      if (message.startsWith("Query's end date and time")) {
        // This error indicates that the query's start or end date occur
        // before the log group was created.
        throw new DateOutOfBoundsError(message);
      }

      throw err;
    }
  }
```

- Para obter detalhes da API, consulte StartQuerya Referência AWS SDK for JavaScript da API.

Cenários

Executar uma consulta grande

O exemplo de código a seguir mostra como usar o CloudWatch Logs para consultar mais de 10.000 registros.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { CloudWatchLogsClient } from "@aws-sdk/client-cloudwatch-logs";
import { CloudWatchQuery } from "./cloud-watch-query.js";

console.log("Starting a recursive query...");

if (!process.env.QUERY_START_DATE || !process.env.QUERY_END_DATE) {
  throw new Error(
    "QUERY_START_DATE and QUERY_END_DATE environment variables are required.",
  );
}

const cloudWatchQuery = new CloudWatchQuery(new CloudWatchLogsClient({}), {
  logGroupNames: ["/workflows/cloudwatch-logs/large-query"],
  dateRange: [
    new Date(parseInt(process.env.QUERY_START_DATE)),
    new Date(parseInt(process.env.QUERY_END_DATE)),
  ],
});

await cloudWatchQuery.run();

console.log(
  `Queries finished in ${cloudWatchQuery.secondsElapsed} seconds.\nTotal logs found:
 ${cloudWatchQuery.results.length}`,
);
```

Essa é uma classe que divide as consultas em várias etapas, se necessário.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import {
  StartQueryCommand,
  GetQueryResultsCommand,
} from "@aws-sdk/client-cloudwatch-logs";
import { splitDateRange } from "@aws-sdk-examples/libs/utils/util-date.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

class DateOutOfBoundsError extends Error {}

export class CloudWatchQuery {
```

```
  /**
   * Run a query for all CloudWatch Logs within a certain date range.
   * CloudWatch logs return a max of 10,000 results. This class
   * performs a binary search across all of the logs in the provided
   * date range if a query returns the maximum number of results.
   *
   * @param {import('@aws-sdk/client-cloudwatch-logs').CloudWatchLogsClient} client
   * @param {{ logGroupNames: string[], dateRange: [Date, Date], queryConfig:
{ limit: number } }} config
   */
  constructor(client, { logGroupNames, dateRange, queryConfig }) {
    this.client = client;
    /**
     * All log groups are queried.
     */
    this.logGroupNames = logGroupNames;

    /**
     * The inclusive date range that is queried.
     */
    this.dateRange = dateRange;

    /**
     * CloudWatch Logs never returns more than 10,000 logs.
     */
    this.limit = queryConfig?.limit ?? 10000;

    /**
     * @type {import("@aws-sdk/client-cloudwatch-logs").ResultField[][]}
     */
    this.results = [];
  }

  /**
   * Run the query.
   */
  async run() {
    this.secondsElapsed = 0;
    const start = new Date();
    this.results = await this._largeQuery(this.dateRange);
    const end = new Date();
    this.secondsElapsed = (end - start) / 1000;
    return this.results;
  }
```

```
/**
 * Recursively query for logs.
 * @param {[Date, Date]} dateRange
 * @returns {Promise<import("@aws-sdk/client-cloudwatch-logs").ResultField[][]>}
 */
async _largeQuery(dateRange) {
  const logs = await this._query(dateRange, this.limit);

  console.log(
    `Query date range: ${dateRange
      .map((d) => d.toISOString())
      .join(" to ")}. Found ${logs.length} logs.`,
  );

  if (logs.length < this.limit) {
    return logs;
  }

  const lastLogDate = this._getLastLogDate(logs);
  const offsetLastLogDate = new Date(lastLogDate);
  offsetLastLogDate.setMilliseconds(lastLogDate.getMilliseconds() + 1);
  const subDateRange = [offsetLastLogDate, dateRange[1]];
  const [r1, r2] = splitDateRange(subDateRange);
  const results = await Promise.all([
    this._largeQuery(r1),
    this._largeQuery(r2),
  ]);
  return [logs, ...results].flat();
}

/**
 * Find the most recent log in a list of logs.
 * @param {import("@aws-sdk/client-cloudwatch-logs").ResultField[][]} logs
 */
_getLastLogDate(logs) {
  const timestamps = logs
    .map(
      (log) =>
        log.find((fieldMeta) => fieldMeta.field === "@timestamp")?.value,
    )
    .filter((t) => !!t)
    .map((t) => `${t}Z`)
    .sort();
```

```
  if (!timestamps.length) {
    throw new Error("No timestamp found in logs.");
  }

  return new Date(timestamps[timestamps.length - 1]);
}

// snippet-start:[javascript.v3.cloudwatch-logs.actions.GetQueryResults]
/**
 * Simple wrapper for the GetQueryResultsCommand.
 * @param {string} queryId
 */
_getQueryResults(queryId) {
  return this.client.send(new GetQueryResultsCommand({ queryId }));
}
// snippet-end:[javascript.v3.cloudwatch-logs.actions.GetQueryResults]

/**
 * Starts a query and waits for it to complete.
 * @param {[Date, Date]} dateRange
 * @param {number} maxLogs
 */
async _query(dateRange, maxLogs) {
  try {
    const { queryId } = await this._startQuery(dateRange, maxLogs);
    const { results } = await this._waitUntilQueryDone(queryId);
    return results ?? [];
  } catch (err) {
    /**
     * This error is thrown when StartQuery returns an error indicating
     * that the query's start or end date occur before the log group was
     * created.
     */
    if (err instanceof DateOutOfBoundsError) {
      return [];
    } else {
      throw err;
    }
  }
}

// snippet-start:[javascript.v3.cloudwatch-logs.actions.StartQuery]
/**
```

```
 * Wrapper for the StartQueryCommand. Uses a static query string
 * for consistency.
 * @param {[Date, Date]} dateRange
 * @param {number} maxLogs
 * @returns {Promise<{ queryId: string }>}
 */
async _startQuery([startDate, endDate], maxLogs = 10000) {
  try {
    return await this.client.send(
      new StartQueryCommand({
        logGroupNames: this.logGroupNames,
        queryString: "fields @timestamp, @message | sort @timestamp asc",
        startTime: startDate.valueOf(),
        endTime: endDate.valueOf(),
        limit: maxLogs,
      }),
    );
  } catch (err) {
    /** @type {string} */
    const message = err.message;
    if (message.startsWith("Query's end date and time")) {
      // This error indicates that the query's start or end date occur
      // before the log group was created.
      throw new DateOutOfBoundsError(message);
    }

    throw err;
  }
}
// snippet-end:[javascript.v3.cloudwatch-logs.actions.StartQuery]

/**
 * Call GetQueryResultsCommand until the query is done.
 * @param {string} queryId
 */
_waitUntilQueryDone(queryId) {
  const getResults = async () => {
    const results = await this._getQueryResults(queryId);
    const queryDone = [
      "Complete",
      "Failed",
      "Cancelled",
      "Timeout",
      "Unknown",
```

```
      ].includes(results.status);

      return { queryDone, results };
    };

    return retry(
      { intervalInMs: 1000, maxRetries: 60, quiet: true },
      async () => {
        const { queryDone, results } = await getResults();
        if (!queryDone) {
          throw new Error("Query not done.");
        }

        return results;
      },
    );
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - GetQueryResults
  - StartQuery

CodeBuild exemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com CodeBuild.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um projeto

O exemplo de código a seguir mostra como criar um CodeBuild projeto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um projeto.

```
import {
  ArtifactsType,
  CodeBuildClient,
  ComputeType,
  CreateProjectCommand,
  EnvironmentType,
  SourceType,
} from "@aws-sdk/client-codebuild";

// Create the AWS CodeBuild project.
export const createProject = async (
  projectName = "MyCodeBuilder",
  roleArn = "arn:aws:iam::xxxxxxxxxxxx:role/CodeBuildAdmin",
  buildOutputBucket = "xxxx",
  githubUrl = "https://...",
) => {
  const codeBuildClient = new CodeBuildClient({});

  const response = await codeBuildClient.send(
    new CreateProjectCommand({
      artifacts: {
        // The destination of the build artifacts.
        type: ArtifactsType.S3,
        location: buildOutputBucket,
```

```
      },
      // Information about the build environment. The combination of "computeType"
 and "type" determines the
      // requirements for the environment such as CPU, memory, and disk space.
      environment: {
        // Build environment compute types.
        // https://docs.aws.amazon.com/codebuild/latest/userguide/build-env-ref-
compute-types.html
        computeType: ComputeType.BUILD_GENERAL1_SMALL,
        // Docker image identifier.
        // See https://docs.aws.amazon.com/codebuild/latest/userguide/build-env-ref-
available.html
        image: "aws/codebuild/standard:7.0",
        // Build environment type.
        type: EnvironmentType.LINUX_CONTAINER,
      },
      name: projectName,
      // A role ARN with permission to create a CodeBuild project, write to the
 artifact location, and write CloudWatch logs.
      serviceRole: roleArn,
      source: {
        // The type of repository that contains the source code to be built.
        type: SourceType.GITHUB,
        // The location of the repository that contains the source code to be built.
        location: githubUrl,
      },
    }),
  );
  console.log(response);
  //   {
  //     '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: 'b428b244-777b-49a6-a48d-5dffedced8e7',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //     },
  //     project: {
  //       arn: 'arn:aws:codebuild:us-east-1:xxxxxxxxxxxx:project/MyCodeBuilder',
  //       artifacts: {
  //         encryptionDisabled: false,
  //         location: 'xxxxxx-xxxxxxx-xxxxxx',
  //         name: 'MyCodeBuilder',
```

```
  //         namespaceType: 'NONE',
  //         packaging: 'NONE',
  //         type: 'S3'
  //       },
  //       badge: { badgeEnabled: false },
  //       cache: { type: 'NO_CACHE' },
  //       created: 2023-08-18T14:46:48.979Z,
  //       encryptionKey: 'arn:aws:kms:us-east-1:xxxxxxxxxxxx:alias/aws/s3',
  //       environment: {
  //         computeType: 'BUILD_GENERAL1_SMALL',
  //         environmentVariables: [],
  //         image: 'aws/codebuild/standard:7.0',
  //         imagePullCredentialsType: 'CODEBUILD',
  //         privilegedMode: false,
  //         type: 'LINUX_CONTAINER'
  //       },
  //       lastModified: 2023-08-18T14:46:48.979Z,
  //       name: 'MyCodeBuilder',
  //       projectVisibility: 'PRIVATE',
  //       queuedTimeoutInMinutes: 480,
  //       serviceRole: 'arn:aws:iam::xxxxxxxxxxxx:role/CodeBuildAdmin',
  //       source: {
  //         insecureSsl: false,
  //         location: 'https://...',
  //         reportBuildStatus: false,
  //         type: 'GITHUB'
  //       },
  //       timeoutInMinutes: 60
  //     }
  //   }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateProjecta Referência AWS SDK for JavaScript da API.

Exemplos de provedores de identidade Amazon Cognito usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Cognito

Os exemplos de código a seguir mostram como começar a usar o Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateListUserPools,
  CognitoIdentityProviderClient,
} from "@aws-sdk/client-cognito-identity-provider";

const client = new CognitoIdentityProviderClient({});

export const helloCognito = async () => {
  const paginator = paginateListUserPools({ client }, {});

  const userPoolNames = [];
```

```
  for await (const page of paginator) {
    const names = page.UserPools.map((pool) => pool.Name);
    userPoolNames.push(...names);
  }

  console.log("User pool names: ");
  console.log(userPoolNames.join("\n"));
  return userPoolNames;
};
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const confirmSignUp = ({ clientId, username, code }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ConfirmSignUpCommand({
    ClientId: clientId,
    Username: username,
```

```
    ConfirmationCode: code,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for JavaScript da API.

Confirme um dispositivo MFA para rastreamento

O exemplo de código a seguir mostra como confirmar um dispositivo de MFA para rastreamento pelo Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const confirmDevice = ({ deviceKey, accessToken, passwordVerifier, salt }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ConfirmDeviceCommand({
    DeviceKey: deviceKey,
    AccessToken: accessToken,
    DeviceSecretVerifierConfig: {
      PasswordVerifier: passwordVerifier,
      Salt: salt,
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ConfirmDevicea Referência AWS SDK for JavaScript da API.

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const associateSoftwareToken = (session) => {
  const client = new CognitoIdentityProviderClient({});
  const command = new AssociateSoftwareTokenCommand({
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for JavaScript da API.

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminGetUser = ({ userPoolId, username }) => {
  const client = new CognitoIdentityProviderClient({});
```

```
  const command = new AdminGetUserCommand({
    UserPoolId: userPoolId,
    Username: username,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for JavaScript da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listUsers = ({ userPoolId }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ListUsersCommand({
    UserPoolId: userPoolId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const resendConfirmationCode = ({ clientId, username }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ResendConfirmationCodeCommand({
    ClientId: clientId,
    Username: username,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for JavaScript da API.

Responder aos desafios de autenticação SRP

O exemplo de código a seguir mostra como responder aos desafios de autenticação SRP do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const respondToAuthChallenge = ({
  clientId,
  username,
  session,
```

```
  userPoolId,
  code,
}) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new RespondToAuthChallengeCommand({
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: code,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte RespondToAuthChallengea Referência AWS SDK for JavaScript da API.

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminRespondToAuthChallenge = ({
  userPoolId,
  clientId,
  username,
  totp,
```

```
  session,
}) => {
  const client = new CognitoIdentityProviderClient({});
  const command = new AdminRespondToAuthChallengeCommand({
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: totp,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for JavaScript da API.

Inscrever um usuário

O exemplo de código a seguir mostra como inscrever um usuário no Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const signUp = ({ clientId, username, password, email }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new SignUpCommand({
    ClientId: clientId,
    Username: username,
    Password: password,
    UserAttributes: [{ Name: "email", Value: email }],
  });
```

```
  return client.send(command);
};
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for JavaScript da API.

Iniciar a autenticação

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const initiateAuth = ({ username, password, clientId }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new InitiateAuthCommand({
    AuthFlow: AuthFlowType.USER_PASSWORD_AUTH,
    AuthParameters: {
      USERNAME: username,
      PASSWORD: password,
    },
    ClientId: clientId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte InitiateAutha Referência AWS SDK for JavaScript da API.

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const adminInitiateAuth = ({ clientId, userPoolId, username, password }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new AdminInitiateAuthCommand({
    ClientId: clientId,
    UserPoolId: userPoolId,
    AuthFlow: AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
    AuthParameters: { USERNAME: username, PASSWORD: password },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte AdminInitiateAuth a Referência AWS SDK for JavaScript da API.

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const verifySoftwareToken = (totp) => {
```

```
  const client = new CognitoIdentityProviderClient({});

  // The 'Session' is provided in the response to 'AssociateSoftwareToken'.
  const session = process.env.SESSION;

  if (!session) {
    throw new Error(
      "Missing a valid Session. Did you run 'admin-initiate-auth'?",
    );
  }

  const command = new VerifySoftwareTokenCommand({
    Session: session,
    UserCode: totp,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte VerifySoftwareTokena Referência AWS SDK for JavaScript da API.

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Para obter a melhor experiência, clone o GitHub repositório e execute este exemplo. O código a seguir representa uma amostra da aplicação de exemplo completa.

```
import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { signUp } from "../../../actions/sign-up.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getSecondValuesFromEntries } from "@aws-sdk-examples/libs/utils/util-
csv.js";

const validateClient = (clientId) => {
  if (!clientId) {
    throw new Error(
      `App client id is missing. Did you run 'create-user-pool'?`,
    );
  }
};

const validateUser = (username, password, email) => {
  if (!(username && password && email)) {
    throw new Error(
      `Username, password, and email must be provided as arguments to the 'sign-up'
 command.`,
    );
  }
};

const signUpHandler = async (commands) => {
  const [_, username, password, email] = commands;

  try {
    validateUser(username, password, email);
    /**
     * @type {string[]}
     */
    const values = getSecondValuesFromEntries(FILE_USER_POOLS);
    const clientId = values[0];
    validateClient(clientId);
    log(`Signing up.`);
    await signUp({ clientId, username, password, email });
    log(`Signed up. A confirmation email has been sent to: ${email}.`);
    log(`Run 'confirm-sign-up ${username} <code>' to confirm your account.`);
  } catch (err) {
    log(err);
```

```
  }
};

export { signUpHandler };

const signUp = ({ clientId, username, password, email }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new SignUpCommand({
    ClientId: clientId,
    Username: username,
    Password: password,
    UserAttributes: [{ Name: "email", Value: email }],
  });

  return client.send(command);
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { confirmSignUp } from "../../../actions/confirm-sign-up.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getSecondValuesFromEntries } from "@aws-sdk-examples/libs/utils/util-
csv.js";

const validateClient = (clientId) => {
  if (!clientId) {
    throw new Error(
      `App client id is missing. Did you run 'create-user-pool'?`,
    );
  }
};

const validateUser = (username) => {
  if (!username) {
    throw new Error(
      `Username name is missing. It must be provided as an argument to the 'confirm-
sign-up' command.`,
    );
  }
};

const validateCode = (code) => {
  if (!code) {
    throw new Error(
```

```
      `Verification code is missing. It must be provided as an argument to the
 'confirm-sign-up' command.`,
    );
  }
};

const confirmSignUpHandler = async (commands) => {
  const [_, username, code] = commands;

  try {
    validateUser(username);
    validateCode(code);
    /**
     * @type {string[]}
     */
    const values = getSecondValuesFromEntries(FILE_USER_POOLS);
    const clientId = values[0];
    validateClient(clientId);
    log(`Confirming user.`);
    await confirmSignUp({ clientId, username, code });
    log(
      `User confirmed. Run 'admin-initiate-auth ${username} <password>' to sign
 in.`,
    );
  } catch (err) {
    log(err);
  }
};

export { confirmSignUpHandler };

const confirmSignUp = ({ clientId, username, code }) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new ConfirmSignUpCommand({
    ClientId: clientId,
    Username: username,
    ConfirmationCode: code,
  });

  return client.send(command);
};

import qrcode from "qrcode-terminal";
```

```
import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { adminInitiateAuth } from "../../../actions/admin-initiate-auth.js";
import { associateSoftwareToken } from "../../../actions/associate-software-
token.js";
import { FILE_USER_POOLS } from "./constants.js";
import { getFirstEntry } from "@aws-sdk-examples/libs/utils/util-csv.js";

const handleMfaSetup = async (session, username) => {
  const { SecretCode, Session } = await associateSoftwareToken(session);

  // Store the Session for use with 'VerifySoftwareToken'.
  process.env.SESSION = Session;

  console.log(
    "Scan this code in your preferred authenticator app, then run 'verify-software-
token' to finish the setup.",
  );
  qrcode.generate(
    `otpauth://totp/${username}?secret=${SecretCode}`,
    { small: true },
    console.log,
  );
};

const handleSoftwareTokenMfa = (session) => {
  // Store the Session for use with 'AdminRespondToAuthChallenge'.
  process.env.SESSION = session;
};

const validateClient = (id) => {
  if (!id) {
    throw new Error(
      `User pool client id is missing. Did you run 'create-user-pool'?`,
    );
  }
};

const validateId = (id) => {
  if (!id) {
    throw new Error(`User pool id is missing. Did you run 'create-user-pool'?`);
  }
};

const validateUser = (username, password) => {
```

```
  if (!(username && password)) {
    throw new Error(
      `Username and password must be provided as arguments to the 'admin-initiate-
auth' command.`,
    );
  }
};

const adminInitiateAuthHandler = async (commands) => {
  const [_, username, password] = commands;

  try {
    validateUser(username, password);

    const [userPoolId, clientId] = getFirstEntry(FILE_USER_POOLS);
    validateId(userPoolId);
    validateClient(clientId);

    log("Signing in.");
    const { ChallengeName, Session } = await adminInitiateAuth({
      clientId,
      userPoolId,
      username,
      password,
    });

    if (ChallengeName === "MFA_SETUP") {
      log("MFA setup is required.");
      return handleMfaSetup(Session, username);
    }

    if (ChallengeName === "SOFTWARE_TOKEN_MFA") {
      handleSoftwareTokenMfa(Session);
      log(`Run 'admin-respond-to-auth-challenge ${username} <totp>'`);
    }
  } catch (err) {
    log(err);
  }
};

export { adminInitiateAuthHandler };

const adminInitiateAuth = ({ clientId, userPoolId, username, password }) => {
  const client = new CognitoIdentityProviderClient({});
```

```
  const command = new AdminInitiateAuthCommand({
    ClientId: clientId,
    UserPoolId: userPoolId,
    AuthFlow: AuthFlowType.ADMIN_USER_PASSWORD_AUTH,
    AuthParameters: { USERNAME: username, PASSWORD: password },
  });

  return client.send(command);
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { adminRespondToAuthChallenge } from "../../../actions/admin-respond-to-auth-
challenge.js";
import { getFirstEntry } from "@aws-sdk-examples/libs/utils/util-csv.js";
import { FILE_USER_POOLS } from "./constants.js";

const verifyUsername = (username) => {
  if (!username) {
    throw new Error(
      `Username is missing. It must be provided as an argument to the 'admin-
respond-to-auth-challenge' command.`,
    );
  }
};

const verifyTotp = (totp) => {
  if (!totp) {
    throw new Error(
      `Time-based one-time password (TOTP) is missing. It must be provided as an
 argument to the 'admin-respond-to-auth-challenge' command.`,
    );
  }
};

const storeAccessToken = (token) => {
  process.env.AccessToken = token;
};

const adminRespondToAuthChallengeHandler = async (commands) => {
  const [_, username, totp] = commands;

  try {
    verifyUsername(username);
```

```
    verifyTotp(totp);

    const [userPoolId, clientId] = getFirstEntry(FILE_USER_POOLS);
    const session = process.env.SESSION;

    const { AuthenticationResult } = await adminRespondToAuthChallenge({
      clientId,
      userPoolId,
      username,
      totp,
      session,
    });

    storeAccessToken(AuthenticationResult.AccessToken);

    log("Successfully authenticated.");
  } catch (err) {
    log(err);
  }
};

export { adminRespondToAuthChallengeHandler };

const respondToAuthChallenge = ({
  clientId,
  username,
  session,
  userPoolId,
  code,
}) => {
  const client = new CognitoIdentityProviderClient({});

  const command = new RespondToAuthChallengeCommand({
    ChallengeName: ChallengeNameType.SOFTWARE_TOKEN_MFA,
    ChallengeResponses: {
      SOFTWARE_TOKEN_MFA_CODE: code,
      USERNAME: username,
    },
    ClientId: clientId,
    UserPoolId: userPoolId,
    Session: session,
  });

  return client.send(command);
```

```
};

import { log } from "@aws-sdk-examples/libs/utils/util-log.js";
import { verifySoftwareToken } from "../../../actions/verify-software-token.js";

const validateTotp = (totp) => {
  if (!totp) {
    throw new Error(
      `Time-based one-time password (TOTP) must be provided to the 'validate-
software-token' command.`,
    );
  }
};
const verifySoftwareTokenHandler = async (commands) => {
  const [_, totp] = commands;

  try {
    validateTotp(totp);

    log("Verifying TOTP.");
    await verifySoftwareToken(totp);
    log("TOTP Verified. Run 'admin-initiate-auth' again to sign-in.");
  } catch (err) {
    console.log(err);
  }
};

export { verifySoftwareTokenHandler };

const verifySoftwareToken = (totp) => {
  const client = new CognitoIdentityProviderClient({});

  // The 'Session' is provided in the response to 'AssociateSoftwareToken'.
  const session = process.env.SESSION;

  if (!session) {
    throw new Error(
      "Missing a valid Session. Did you run 'admin-initiate-auth'?",
    );
  }

  const command = new VerifySoftwareTokenCommand({
    Session: session,
    UserCode: totp,
```

```
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Exemplos do DynamoDB usando o SDK JavaScript para (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, DynamoDB

O exemplo de código a seguir mostra como começar a usar o DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListTablesCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new ListTablesCommand({});

  const response = await client.send(command);
  console.log(response.TableNames.join("\n"));
  return response;
};
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { CreateTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new CreateTableCommand({
    TableName: "EspressoDrinks",
    // For more information about data types,
    // see https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
HowItWorks.NamingRulesDataTypes.html#HowItWorks.DataTypes and
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
    AttributeDefinitions: [
      {
        AttributeName: "DrinkName",
        AttributeType: "S",
      },
    ],
    KeySchema: [
      {
        AttributeName: "DrinkName",
        KeyType: "HASH",
      },
    ],
    ProvisionedThroughput: {
      ReadCapacityUnits: 1,
      WriteCapacityUnits: 1,
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  AttributeDefinitions: [
    {
      AttributeName: "CUSTOMER_ID",
      AttributeType: "N",
    },
    {
      AttributeName: "CUSTOMER_NAME",
      AttributeType: "S",
    },
  ],
  KeySchema: [
    {
      AttributeName: "CUSTOMER_ID",
      KeyType: "HASH",
    },
    {
      AttributeName: "CUSTOMER_NAME",
      KeyType: "RANGE",
    },
```

```
  ],
  ProvisionedThroughput: {
    ReadCapacityUnits: 1,
    WriteCapacityUnits: 1,
  },
  TableName: "CUSTOMER_LIST",
  StreamSpecification: {
    StreamEnabled: false,
  },
};

// Call DynamoDB to create the table
ddb.createTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Table Created", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for JavaScript da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});
```

```
export const main = async () => {
  const command = new DeleteTableCommand({
    TableName: "DecafCoffees",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to delete the specified table
ddb.deleteTable(params, function (err, data) {
  if (err && err.code === "ResourceNotFoundException") {
    console.log("Error: Table not found");
  } else if (err && err.code === "ResourceInUseException") {
    console.log("Error: Table in use");
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte DeleteCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, DeleteCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new DeleteCommand({
    TableName: "Sodas",
    Key: {
      Flavor: "Cola",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Exclua um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "VALUE" },
  },
};

// Call DynamoDB to delete the item from the table
ddb.deleteItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Exclua um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  Key: {
    HASH_KEY: VALUE,
  },
  TableName: "TABLE",
};

docClient.delete(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for JavaScript da API.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchGet.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { BatchGetCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
```

```
const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchGetCommand({
    // Each key in this object is the name of a table. This example refers
    // to a Books table.
    RequestItems: {
      Books: {
        // Each entry in Keys is an object that specifies a primary key.
        Keys: [
          {
            Title: "How to AWS",
          },
          {
            Title: "DynamoDB for DBAs",
          },
        ],
        // Only return the "Title" and "PageCount" attributes.
        ProjectionExpression: "Title, PageCount",
      },
    },
  });

  const response = await docClient.send(command);
  console.log(response.Responses["Books"]);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: {
      Keys: [
        { KEY_NAME: { N: "KEY_VALUE_1" } },
        { KEY_NAME: { N: "KEY_VALUE_2" } },
        { KEY_NAME: { N: "KEY_VALUE_3" } },
      ],
      ProjectionExpression: "KEY_NAME, ATTRIBUTE",
    },
  },
};

ddb.batchGetItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    data.Responses.TABLE_NAME.forEach(function (element, index, array) {
      console.log(element);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for JavaScript da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte GetCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, GetCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new GetCommand({
    TableName: "AngryAnimals",
    Key: {
      CommonName: "Shoebill",
    },
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Obtenha um item de uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Key: {
    KEY_NAME: { N: "001" },
  },
  ProjectionExpression: "ATTRIBUTE_NAME",
};

// Call DynamoDB to read the item from the table
ddb.getItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

Obtenha um item de uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "EPISODES_TABLE",
  Key: { KEY_NAME: VALUE },
};

docClient.get(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetItema Referência AWS SDK for JavaScript da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { DescribeTableCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new DescribeTableCommand({
    TableName: "Pastries",
  });

  const response = await client.send(command);
  console.log(`TABLE NAME: ${response.Table.TableName}`);
  console.log(`TABLE ITEM COUNT: ${response.Table.ItemCount}`);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: process.argv[2],
};

// Call DynamoDB to retrieve the selected table descriptions
ddb.describeTable(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Table.KeySchema);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for JavaScript da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { ListTablesCommand, DynamoDBClient } from "@aws-sdk/client-dynamodb";

const client = new DynamoDBClient({});

export const main = async () => {
  const command = new ListTablesCommand({});

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

// Call DynamoDB to retrieve the list of tables
```

```
ddb.listTables({ Limit: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err.code);
  } else {
    console.log("Table names are ", data.TableNames);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for JavaScript da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte PutCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { PutCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new PutCommand({
    TableName: "HappyAnimals",
    Item: {
      CommonName: "Shiba Inu",
    },
  });
```

```
  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Coloque um item em uma tabela.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  TableName: "CUSTOMER_LIST",
  Item: {
    CUSTOMER_ID: { N: "001" },
    CUSTOMER_NAME: { S: "Richard Roe" },
  },
};

// Call DynamoDB to add the item to the table
ddb.putItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Coloque um item em uma tabela usando o cliente de documento do DynamoDB.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  TableName: "TABLE",
  Item: {
    HASHKEY: VALUE,
    ATTRIBUTE_1: "STRING_VALUE",
    ATTRIBUTE_2: VALUE_2,
  },
};

docClient.put(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutItema Referência AWS SDK for JavaScript da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte QueryCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { QueryCommand, DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new QueryCommand({
    TableName: "CoffeeCrop",
    KeyConditionExpression:
      "OriginCountry = :originCountry AND RoastDate > :roastDate",
    ExpressionAttributeValues: {
      ":originCountry": "Ethiopia",
      ":roastDate": "2023-05-01",
    },
    ConsistentRead: true,
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });
```

```
// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({ apiVersion: "2012-08-10" });

var params = {
  ExpressionAttributeValues: {
    ":s": 2,
    ":e": 9,
    ":topic": "PHRASE",
  },
  KeyConditionExpression: "Season = :s and Episode > :e",
  FilterExpression: "contains (Subtitle, :topic)",
  TableName: "EPISODES_TABLE",
};

docClient.query(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Items);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for JavaScript.

Executar uma instrução PartiQL

O exemplo de código a seguir mostra como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: `INSERT INTO Flowers value {'Name':?}`,
    Parameters: ["Rose"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Obtenha um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: "SELECT * FROM CloudTypes WHERE IsStorm=?",
    Parameters: [false],
    ConsistentRead: true,
  });

  const response = await docClient.send(command);
  console.log(response);
```

```
  return response;
};
```

Atualize um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: "UPDATE EyeColors SET IsRecessive=? where Color=?",
    Parameters: [true, "blue"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Exclua um item usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  ExecuteStatementCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new ExecuteStatementCommand({
    Statement: "DELETE FROM PaintColors where Name=?",
```

```
    Parameters: ["Purple"],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for JavaScript da API.

Executar lotes de instruções PartiQL

O exemplo de código a seguir mostra como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const breakfastFoods = ["Eggs", "Bacon", "Sausage"];
  const command = new BatchExecuteStatementCommand({
    Statements: breakfastFoods.map((food) => ({
      Statement: `INSERT INTO BreakfastFoods value {'Name':?}`,
```

```
      Parameters: [food],
    })),
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Obtenha um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new BatchExecuteStatementCommand({
    Statements: [
      {
        Statement: "SELECT * FROM PepperMeasurements WHERE Unit=?",
        Parameters: ["Teaspoons"],
        ConsistentRead: true,
      },
      {
        Statement: "SELECT * FROM PepperMeasurements WHERE Unit=?",
        Parameters: ["Grams"],
        ConsistentRead: true,
      },
    ],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Atualize um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const eggUpdates = [
    ["duck", "fried"],
    ["chicken", "omelette"],
  ];
  const command = new BatchExecuteStatementCommand({
    Statements: eggUpdates.map((change) => ({
      Statement: "UPDATE Eggs SET Style=? where Variety=?",
      Parameters: [change[1], change[0]],
    })),
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

Exclua um lote de itens usando o PartiQL.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";

import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
```

```
  const command = new BatchExecuteStatementCommand({
    Statements: [
      {
        Statement: "DELETE FROM Flavors where Name=?",
        Parameters: ["Grape"],
      },
      {
        Statement: "DELETE FROM Flavors where Name=?",
        Parameters: ["Strawberry"],
      },
    ],
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for JavaScript da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte ScanCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
import { DynamoDBDocumentClient, ScanCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);
```

```
export const main = async () => {
  const command = new ScanCommand({
    ProjectionExpression: "#Name, Color, AvgLifeSpan",
    ExpressionAttributeNames: { "#Name": "Name" },
    TableName: "Birds",
  });

  const response = await docClient.send(command);
  for (const bird of response.Items) {
    console.log(`${bird.Name} - (${bird.Color}, ${bird.AvgLifeSpan})`);
  }
  return response;
};
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js.
var AWS = require("aws-sdk");
// Set the AWS Region.
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object.
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

const params = {
  // Specify which items in the results are returned.
  FilterExpression: "Subtitle = :topic AND Season = :s AND Episode = :e",
  // Define the expression attribute value, which are substitutes for the values you
 want to compare.
  ExpressionAttributeValues: {
    ":topic": { S: "SubTitle2" },
    ":s": { N: 1 },
    ":e": { N: 2 },
```

```
  },
  // Set the projection expression, which are the attributes that you want.
  ProjectionExpression: "Season, Episode, Title, Subtitle",
  TableName: "EPISODES_TABLE",
};

ddb.scan(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
    data.Items.forEach(function (element, index, array) {
      console.log(
        "printing",
        element.Title.S + " (" + element.Subtitle.S + ")"
      );
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for JavaScript.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte UpdateCommand.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
```

```
import { DynamoDBDocumentClient, UpdateCommand } from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const command = new UpdateCommand({
    TableName: "Dogs",
    Key: {
      Breed: "Labrador",
    },
    UpdateExpression: "set Color = :color",
    ExpressionAttributeValues: {
      ":color": "black",
    },
    ReturnValues: "ALL_NEW",
  });

  const response = await docClient.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for JavaScript da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Neste exemplo, é usado o cliente de documentos para simplificar o trabalho com itens no DynamoDB. Para obter detalhes da API, consulte BatchWrite.

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
```

```
import {
  BatchWriteCommand,
  DynamoDBDocumentClient,
} from "@aws-sdk/lib-dynamodb";
import { readFileSync } from "fs";

// These modules are local to our GitHub repository. We recommend cloning
// the project from GitHub if you want to run this example.
// For more information, see https://github.com/awsdocs/aws-doc-sdk-examples.
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { chunkArray } from "@aws-sdk-examples/libs/utils/util-array.js";

const dirname = dirnameFromMetaUrl(import.meta.url);

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

export const main = async () => {
  const file = readFileSync(
    `${dirname}../../../../../resources/sample_files/movies.json`,
  );

  const movies = JSON.parse(file.toString());

  // chunkArray is a local convenience function. It takes an array and returns
  // a generator function. The generator function yields every N items.
  const movieChunks = chunkArray(movies, 25);

  // For every chunk of 25 movies, make one BatchWrite request.
  for (const chunk of movieChunks) {
    const putRequests = chunk.map((movie) => ({
      PutRequest: {
        Item: movie,
      },
    }));

    const command = new BatchWriteCommand({
      RequestItems: {
        // An existing table is required. A composite key of 'title' and 'year' is
 recommended
        // to account for duplicate titles.
        ["BatchWriteMoviesTable"]: putRequests,
      },
    });
```

```
    await docClient.send(command);
  }
};
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

var params = {
  RequestItems: {
    TABLE_NAME: [
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
          },
        },
      },
      {
        PutRequest: {
          Item: {
            KEY: { N: "KEY_VALUE" },
            ATTRIBUTE_1: { S: "ATTRIBUTE_1_VALUE" },
            ATTRIBUTE_2: { N: "ATTRIBUTE_2_VALUE" },
```

```
          },
        },
      },
    ],
  },
};

ddb.batchWriteItem(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for JavaScript da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import { readFileSync } from "fs";
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";

/**
 * This module is a convenience library. It abstracts Amazon DynamoDB's data type
 * descriptors (such as S, N, B, and BOOL) by marshalling JavaScript objects into
 * AttributeValue shapes.
 */
import {
  BatchWriteCommand,
  DeleteCommand,
  DynamoDBDocumentClient,
  GetCommand,
  PutCommand,
  UpdateCommand,
  paginateQuery,
  paginateScan,
} from "@aws-sdk/lib-dynamodb";

// These modules are local to our GitHub repository. We recommend cloning
// the project from GitHub if you want to run this example.
// For more information, see https://github.com/awsdocs/aws-doc-sdk-examples.
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { chunkArray } from "@aws-sdk-examples/libs/utils/util-array.js";

const dirname = dirnameFromMetaUrl(import.meta.url);
const tableName = getUniqueName("Movies");
```

```
const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);

export const main = async () => {
  /**
   * Create a table.
   */

  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
    // Set the billing mode to PAY_PER_REQUEST to
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
    AttributeDefinitions: [
      {
        AttributeName: "year",
        // 'N' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "N",
      },
      { AttributeName: "title", AttributeType: "S" },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [
      // The way your data is accessed determines how you structure your keys.
      // The movies table will be queried for movies by year. It makes sense
      // to make year our partition (HASH) key.
      { AttributeName: "year", KeyType: "HASH" },
      { AttributeName: "title", KeyType: "RANGE" },
    ],
  });

  log("Creating a table.");
  const createTableResponse = await client.send(createTableCommand);
```

```
  log(`Table created: ${JSON.stringify(createTableResponse.TableDescription)}`);

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Add a movie to the table.
   */

  log("Adding a single movie to the table.");
  // PutCommand is the first example usage of 'lib-dynamodb'.
  const putCommand = new PutCommand({
    TableName: tableName,
    Item: {
      // In 'client-dynamodb', the AttributeValue would be required (`year: { N:
1981 }`)
      // 'lib-dynamodb' simplifies the usage ( `year: 1981` )
      year: 1981,
      // The preceding KeySchema defines 'title' as our sort (RANGE) key, so 'title'
      // is required.
      title: "The Evil Dead",
      // Every other attribute is optional.
      info: {
        genres: ["Horror"],
      },
    },
  });
  await docClient.send(putCommand);
  log("The movie was added.");

  /**
   * Get a movie from the table.
   */

  log("Getting a single movie from the table.");
  const getCommand = new GetCommand({
    TableName: tableName,
    // Requires the complete primary key. For the movies table, the primary key
    // is only the id (partition key).
    Key: {
      year: 1981,
```

```
      title: "The Evil Dead",
    },
    // Set this to make sure that recent writes are reflected.
    // For more information, see https://docs.aws.amazon.com/amazondynamodb/latest/
developerguide/HowItWorks.ReadConsistency.html.
    ConsistentRead: true,
  });
  const getResponse = await docClient.send(getCommand);
  log(`Got the movie: ${JSON.stringify(getResponse.Item)}`);

  /**
   * Update a movie in the table.
   */

  log("Updating a single movie in the table.");
  const updateCommand = new UpdateCommand({
    TableName: tableName,
    Key: { year: 1981, title: "The Evil Dead" },
    // This update expression appends "Comedy" to the list of genres.
    // For more information on update expressions, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Expressions.UpdateExpressions.html
    UpdateExpression: "set #i.#g = list_append(#i.#g, :vals)",
    ExpressionAttributeNames: { "#i": "info", "#g": "genres" },
    ExpressionAttributeValues: {
      ":vals": ["Comedy"],
    },
    ReturnValues: "ALL_NEW",
  });
  const updateResponse = await docClient.send(updateCommand);
  log(`Movie updated: ${JSON.stringify(updateResponse.Attributes)}`);

  /**
   * Delete a movie from the table.
   */

  log("Deleting a single movie from the table.");
  const deleteCommand = new DeleteCommand({
    TableName: tableName,
    Key: { year: 1981, title: "The Evil Dead" },
  });
  await client.send(deleteCommand);
  log("Movie deleted.");
```

```
  /**
   * Upload a batch of movies.
   */

  log("Adding movies from local JSON file.");
  const file = readFileSync(
    `${dirname}../../../../resources/sample_files/movies.json`,
  );
  const movies = JSON.parse(file.toString());
  // chunkArray is a local convenience function. It takes an array and returns
  // a generator function. The generator function yields every N items.
  const movieChunks = chunkArray(movies, 25);
  // For every chunk of 25 movies, make one BatchWrite request.
  for (const chunk of movieChunks) {
    const putRequests = chunk.map((movie) => ({
      PutRequest: {
        Item: movie,
      },
    }));

    const command = new BatchWriteCommand({
      RequestItems: {
        [tableName]: putRequests,
      },
    });

    await docClient.send(command);
  }
  log("Movies added.");

  /**
   * Query for movies by year.
   */

  log("Querying for all movies from 1981.");
  const paginatedQuery = paginateQuery(
    { client: docClient },
    {
      TableName: tableName,
      //For more information about query expressions, see
      // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Query.html#Query.KeyConditionExpressions
      KeyConditionExpression: "#y = :y",
      // 'year' is a reserved word in DynamoDB. Indicate that it's an attribute
```

```
      // name by using an expression attribute name.
      ExpressionAttributeNames: { "#y": "year" },
      ExpressionAttributeValues: { ":y": 1981 },
      ConsistentRead: true,
    },
  );
  /**
   * @type { Record<string, any>[] };
   */
  const movies1981 = [];
  for await (const page of paginatedQuery) {
    movies1981.push(...page.Items);
  }
  log(`Movies: ${movies1981.map((m) => m.title).join(", ")}`);

  /**
   * Scan the table for movies between 1980 and 1990.
   */

  log(`Scan for movies released between 1980 and 1990`);
  // A 'Scan' operation always reads every item in the table. If your design
 requires
  // the use of 'Scan', consider indexing your table or changing your design.
  // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/bp-query-
scan.html
  const paginatedScan = paginateScan(
    { client: docClient },
    {
      TableName: tableName,
      // Scan uses a filter expression instead of a key condition expression. Scan
 will
      // read the entire table and then apply the filter.
      FilterExpression: "#y between :y1 and :y2",
      ExpressionAttributeNames: { "#y": "year" },
      ExpressionAttributeValues: { ":y1": 1980, ":y2": 1990 },
      ConsistentRead: true,
    },
  );
  /**
   * @type { Record<string, any>[] };
   */
  const movies1980to1990 = [];
  for await (const page of paginatedScan) {
    movies1980to1990.push(...page.Items);
```

```
  }
  log(
    `Movies: ${movies1980to1990
      .map((m) => `${m.title} (${m.year})`)
      .join(", ")}`,
  );

  /**
   * Delete the table.
   */

  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
  log(`Deleting table ${tableName}.`);
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.

- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute instruções PartiQL em lote.

```
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  DynamoDBDocumentClient,
  BatchExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);
const tableName = "Cities";

export const main = async () => {
  /**
   * Create a table.
   */

  log("Creating a table.");
  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
    // Set the billing mode to PAY_PER_REQUEST to
```

```
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
    AttributeDefinitions: [
      {
        AttributeName: "name",
        // 'S' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "S",
      },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [{ AttributeName: "name", KeyType: "HASH" }],
  });
  await client.send(createTableCommand);
  log(`Table created: ${tableName}.`);

  /**
   * Wait until the table is active.
   */

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Insert items.
   */

  log("Inserting cities into the table.");
  const addItemsStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.insert.html
    Statements: [
      {
        Statement: `INSERT INTO ${tableName} value {'name':?, 'population':?}`,
```

```
        Parameters: ["Alachua", 10712],
      },
      {
        Statement: `INSERT INTO ${tableName} value {'name':?, 'population':?}`,
        Parameters: ["High Springs", 6415],
      },
    ],
  });
  await docClient.send(addItemsStatementCommand);
  log(`Cities inserted.`);

  /**
   * Select items.
   */

  log("Selecting cities from the table.");
  const selectItemsStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.select.html
    Statements: [
      {
        Statement: `SELECT * FROM ${tableName} WHERE name=?`,
        Parameters: ["Alachua"],
      },
      {
        Statement: `SELECT * FROM ${tableName} WHERE name=?`,
        Parameters: ["High Springs"],
      },
    ],
  });
  const selectItemResponse = await docClient.send(selectItemsStatementCommand);
  log(
    `Got cities: ${selectItemResponse.Responses.map(
      (r) => `${r.Item.name} (${r.Item.population})`,
    ).join(", ")}`,
  );

  /**
   * Update items.
   */

  log("Modifying the populations.");
  const updateItemStatementCommand = new BatchExecuteStatementCommand({
```

```
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.update.html
    Statements: [
      {
        Statement: `UPDATE ${tableName} SET population=? WHERE name=?`,
        Parameters: [10, "Alachua"],
      },
      {
        Statement: `UPDATE ${tableName} SET population=? WHERE name=?`,
        Parameters: [5, "High Springs"],
      },
    ],
  });
  await docClient.send(updateItemStatementCommand);
  log(`Updated cities.`);

  /**
   * Delete the items.
   */

  log("Deleting the cities.");
  const deleteItemStatementCommand = new BatchExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.delete.html
    Statements: [
      {
        Statement: `DELETE FROM ${tableName} WHERE name=?`,
        Parameters: ["Alachua"],
      },
      {
        Statement: `DELETE FROM ${tableName} WHERE name=?`,
        Parameters: ["High Springs"],
      },
    ],
  });
  await docClient.send(deleteItemStatementCommand);
  log("Cities deleted.");

  /**
   * Delete the table.
   */

  log("Deleting the table.");
  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
```

```
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for JavaScript da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute instruções PartiQL individuais.

```
import {
  BillingMode,
  CreateTableCommand,
  DeleteTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  DynamoDBDocumentClient,
  ExecuteStatementCommand,
} from "@aws-sdk/lib-dynamodb";

const client = new DynamoDBClient({});
```

```
const docClient = DynamoDBDocumentClient.from(client);

const log = (msg) => console.log(`[SCENARIO] ${msg}`);
const tableName = "SingleOriginCoffees";

export const main = async () => {
  /**
   * Create a table.
   */

  log("Creating a table.");
  const createTableCommand = new CreateTableCommand({
    TableName: tableName,
    // This example performs a large write to the database.
    // Set the billing mode to PAY_PER_REQUEST to
    // avoid throttling the large write.
    BillingMode: BillingMode.PAY_PER_REQUEST,
    // Define the attributes that are necessary for the key schema.
    AttributeDefinitions: [
      {
        AttributeName: "varietal",
        // 'S' is a data type descriptor that represents a number type.
        // For a list of all data type descriptors, see the following link.
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Programming.LowLevelAPI.html#Programming.LowLevelAPI.DataTypeDescriptors
        AttributeType: "S",
      },
    ],
    // The KeySchema defines the primary key. The primary key can be
    // a partition key, or a combination of a partition key and a sort key.
    // Key schema design is important. For more info, see
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/best-
practices.html
    KeySchema: [{ AttributeName: "varietal", KeyType: "HASH" }],
  });
  await client.send(createTableCommand);
  log(`Table created: ${tableName}.`);

  /**
   * Wait until the table is active.
   */

  // This polls with DescribeTableCommand until the requested table is 'ACTIVE'.
  // You can't write to a table before it's active.
```

```
  log("Waiting for the table to be active.");
  await waitUntilTableExists({ client }, { TableName: tableName });
  log("Table active.");

  /**
   * Insert an item.
   */

  log("Inserting a coffee into the table.");
  const addItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.insert.html
    Statement: `INSERT INTO ${tableName} value {'varietal':?, 'profile':?}`,
    Parameters: ["arabica", ["chocolate", "floral"]],
  });
  await client.send(addItemStatementCommand);
  log(`Coffee inserted.`);

  /**
   * Select an item.
   */

  log("Selecting the coffee from the table.");
  const selectItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.select.html
    Statement: `SELECT * FROM ${tableName} WHERE varietal=?`,
    Parameters: ["arabica"],
  });
  const selectItemResponse = await docClient.send(selectItemStatementCommand);
  log(`Got coffee: ${JSON.stringify(selectItemResponse.Items[0])}`);

  /**
   * Update the item.
   */

  log("Add a flavor profile to the coffee.");
  const updateItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.update.html
    Statement: `UPDATE ${tableName} SET profile=list_append(profile, ?) WHERE
 varietal=?`,
    Parameters: [["fruity"], "arabica"],
  });
```

```
  await client.send(updateItemStatementCommand);
  log(`Updated coffee`);

  /**
   * Delete the item.
   */

  log("Deleting the coffee.");
  const deleteItemStatementCommand = new ExecuteStatementCommand({
    // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ql-
reference.delete.html
    Statement: `DELETE FROM ${tableName} WHERE varietal=?`,
    Parameters: ["arabica"],
  });
  await docClient.send(deleteItemStatementCommand);
  log("Coffee deleted.");

  /**
   * Delete the table.
   */

  log("Deleting the table.");
  const deleteTableCommand = new DeleteTableCommand({ TableName: tableName });
  await client.send(deleteTableCommand);
  log("Table deleted.");
};
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for JavaScript da API.

Exemplos do Amazon EC2 usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSecurityGroupsCommand } from "@aws-sdk/client-ec2";

import { client } from "./libs/client.js";

// Call DescribeSecurityGroups and display the result.
export const main = async () => {
  try {
    const { SecurityGroups } = await client.send(
      new DescribeSecurityGroupsCommand({}),
    );

    const securityGroupList = SecurityGroups.slice(0, 9)
      .map((sg) => ` • ${sg.GroupId}: ${sg.GroupName}`)
      .join("\n");

    console.log(
      "Hello, Amazon EC2! Let's list up to 10 of your security groups:",
    );
    console.log(securityGroupList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico para o Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AllocateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new AllocateAddressCommand({});

  try {
    const { AllocationId, PublicIp } = await client.send(command);
    console.log("A new IP address has been allocated to your account:");
    console.log(`ID: ${AllocationId} Public IP: ${PublicIp}`);
    console.log(
      "You can view your IP addresses in the AWS Management Console for Amazon EC2.
 Look under Network & Security > Elastic IPs",
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for JavaScript da API.

Para associar um endereço IP elástico a uma instância

O exemplo de código a seguir mostra como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AssociateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  // You need to allocate an Elastic IP address before associating it with an
 instance.
  // You can do that with the AllocateAddressCommand.
  const allocationId = "ALLOCATION_ID";
  // You need to create an EC2 instance before an IP address can be associated with
 it.
  // You can do that with the RunInstancesCommand.
  const instanceId = "INSTANCE_ID";
  const command = new AssociateAddressCommand({
    AllocationId: allocationId,
    InstanceId: instanceId,
  });

  try {
    const { AssociationId } = await client.send(command);
    console.log(
      `Address with allocation ID ${allocationId} is now associated with instance
 ${instanceId}.`,
```

```
      `The association ID is ${AssociationId}.`,
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for JavaScript da API.

Criar um modelo de inicialização

O exemplo de código a seguir mostra como criar um modelo de execução de sub-rede do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
```

```
          KeyName: NAMES.keyPairName,
        },
      }),
```

- Para obter detalhes da API, consulte CreateLaunchTemplatea Referência AWS SDK for JavaScript da API.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateSecurityGroupCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new CreateSecurityGroupCommand({
    // Up to 255 characters in length. Cannot start with sg-.
    GroupName: "SECURITY_GROUP_NAME",
    // Up to 255 characters in length.
    Description: "DESCRIPTION",
  });

  try {
    const { GroupId } = await client.send(command);
    console.log(GroupId);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for JavaScript da API.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateKeyPairCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a key pair in Amazon EC2.
    const { KeyMaterial, KeyName } = await client.send(
      // A unique name for the key pair. Up to 255 ASCII characters.
      new CreateKeyPairCommand({ KeyName: "KEY_PAIR_NAME" }),
    );
    // This logs your private key. Be sure to save it.
    console.log(KeyName);
    console.log(KeyMaterial);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for JavaScript da API.

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { RunInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Create a new EC2 instance.
export const main = async () => {
  const command = new RunInstancesCommand({
    // Your key pair name.
    KeyName: "KEY_PAIR_NAME",
    // Your security group.
    SecurityGroupIds: ["SECURITY_GROUP_ID"],
    // An x86_64 compatible image.
    ImageId: "ami-0001a0d1a04bfcc30",
    // An x86_64 compatible free-tier instance type.
    InstanceType: "t1.micro",
    // Ensure only 1 instance launches.
    MinCount: 1,
    MaxCount: 1,
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for JavaScript da API.

Excluir um modelo de execução

O exemplo de código a seguir mostra como excluir um modelo de execução de sub-rede do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    await client.send(
      new DeleteLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
      }),
    );
```

- Para obter detalhes da API, consulte DeleteLaunchTemplatea Referência AWS SDK for JavaScript da API.

Exclua um grupo de segurança

O exemplo de código a seguir mostra como excluir um grupo de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSecurityGroupCommand } from "@aws-sdk/client-ec2";
```

```
import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DeleteSecurityGroupCommand({
    GroupId: "GROUP_ID",
  });

  try {
    await client.send(command);
    console.log("Security group deleted successfully.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for JavaScript da API.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteKeyPairCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DeleteKeyPairCommand({
    KeyName: "KEY_PAIR_NAME",
  });

  try {
```

```
    await client.send(command);
    console.log("Successfully deleted key pair.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for JavaScript da API.

Descrever regiões

O exemplo de código a seguir mostra como descrever as regiões do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeRegionsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DescribeRegionsCommand({
    // By default this command will not show regions that require you to opt-in.
    // When AllRegions true even the regions that require opt-in will be returned.
    AllRegions: true,
    // You can omit the Filters property if you want to get all regions.
    Filters: [
      {
        Name: "region-name",
        // You can specify multiple values for a filter.
        // You can also use '*' as a wildcard. This will return all
        // of the regions that start with `us-east-`.
        Values: ["ap-southeast-4"],
      },
    ],
```

```
  });

  try {
    const { Regions } = await client.send(command);
    const regionsList = Regions.map((reg) => ` • ${reg.RegionName}`);
    console.log("Found regions:");
    console.log(regionsList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for JavaScript da API.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List all of your EC2 instances running with x86_64 architecture that were
// launched this month.
export const main = async () => {
  const d = new Date();
  const year = d.getFullYear();
  const month = `0${d.getMonth() + 1}`.slice(-2);
  const launchTimePattern = `${year}-${month}-*`;
  const command = new DescribeInstancesCommand({
    Filters: [
      { Name: "architecture", Values: ["x86_64"] },
```

```
      { Name: "instance-state-name", Values: ["running"] },
      {
        Name: "launch-time",
        Values: [launchTimePattern],
      },
    ],
  });

  try {
    const { Reservations } = await client.send(command);
    const instanceList = Reservations.reduce((prev, current) => {
      return prev.concat(current.Instances);
    }, []);

    console.log(instanceList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for JavaScript da API.

Desabilitar monitoramento detalhado

O exemplo de código a seguir mostra como desabilitar o monitoramento detalhado em uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UnmonitorInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";
```

```
export const main = async () => {
  const command = new UnmonitorInstancesCommand({
    InstanceIds: ["i-09a3dfe7ae00e853f"],
  });

  try {
    const { InstanceMonitorings } = await client.send(command);
    const instanceMonitoringsList = InstanceMonitorings.map(
      (im) =>
        ` • Detailed monitoring state for ${im.InstanceId} is
 ${im.Monitoring.State}.`,
    );
    console.log("Monitoring status:");
    console.log(instanceMonitoringsList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte UnmonitorInstancesa Referência AWS SDK for JavaScript da API.

Desassociar um endereço IP elástico de uma instância

O exemplo de código a seguir mostra como desassociar um endereço IP elástico de uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DisassociateAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Disassociate an Elastic IP address from an instance.
```

```
export const main = async () => {
  const command = new DisassociateAddressCommand({
    // You can also use PublicIp, but that is for EC2 classic which is being
 retired.
    AssociationId: "ASSOCIATION_ID",
  });

  try {
    await client.send(command);
    console.log("Successfully disassociated address");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for JavaScript da API.

Habilitar monitoramento

O exemplo de código a seguir mostra como habilitar o monitoramento em uma instância do Amazon EC2 em execução.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { MonitorInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Turn on detailed monitoring for the selected instance.
// By default, metrics are sent to Amazon CloudWatch every 5 minutes.
// For a cost you can enable detailed monitoring which sends metrics every minute.
export const main = async () => {
  const command = new MonitorInstancesCommand({
```

```
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { InstanceMonitorings } = await client.send(command);
    const instancesBeingMonitored = InstanceMonitorings.map(
      (im) =>
        ` • Detailed monitoring state for ${im.InstanceId} is
 ${im.Monitoring.State}.`,
    );
    console.log("Monitoring status:");
    console.log(instancesBeingMonitored.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte MonitorInstancesa Referência AWS SDK for JavaScript da API.

Obter dados sobre imagens de máquina da Amazon

O exemplo de código a seguir mostra como obter dados sobre imagens de máquina da Amazon (AMIs).

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { paginateDescribeImages } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List at least the first i386 image available for EC2 instances.
export const main = async () => {
  // The paginate function is a wrapper around the base command.
```

```
  const paginator = paginateDescribeImages(
    // Without limiting the page size, this call can take a long time. pageSize is
 just sugar for
    // the MaxResults property in the base command.
    { client, pageSize: 25 },
    {
      // There are almost 70,000 images available. Be specific with your filtering
      // to increase efficiency.
      // See https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/client-
ec2/interfaces/describeimagescommandinput.html#filters
      Filters: [{ Name: "architecture", Values: ["x86_64"] }],
    },
  );

  try {
    const arm64Images = [];
    for await (const page of paginator) {
      if (page.Images.length) {
        arm64Images.push(...page.Images);
        // Once we have at least 1 result, we can stop.
        if (arm64Images.length >= 1) {
          break;
        }
      }
    }
    console.log(arm64Images);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeImagesa Referência AWS SDK for JavaScript da API.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSecurityGroupsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Log the details of a specific security group.
export const main = async () => {
  const command = new DescribeSecurityGroupsCommand({
    GroupIds: ["SECURITY_GROUP_ID"],
  });

  try {
    const { SecurityGroups } = await client.send(command);
    console.log(JSON.stringify(SecurityGroups, null, 2));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for JavaScript da API.

Obter dados sobre tipos de instâncias

O exemplo de código a seguir mostra como obter dados sobre tipos de instâncias do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  paginateDescribeInstanceTypes,
  DescribeInstanceTypesCommand,
} from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// List at least the first arm64 EC2 instance type available.
export const main = async () => {
  // The paginate function is a wrapper around the underlying command.
  const paginator = paginateDescribeInstanceTypes(
    // Without limiting the page size, this call can take a long time. pageSize is
 just sugar for
    // the MaxResults property in the underlying command.
    { client, pageSize: 25 },
    {
      Filters: [
        { Name: "processor-info.supported-architecture", Values: ["x86_64"] },
        { Name: "free-tier-eligible", Values: ["true"] },
      ],
    }
  );

  try {
    const instanceTypes = [];

    for await (const page of paginator) {
      if (page.InstanceTypes.length) {
        instanceTypes.push(...page.InstanceTypes);

        // When we have at least 1 result, we can stop.
        if (instanceTypes.length >= 1) {
          break;
        }
      }
    }
    console.log(instanceTypes);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for JavaScript da API.

Obtenha dados sobre o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como obter dados sobre o perfil de instância associado a uma instância Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const ec2Client = new EC2Client({});
const { IamInstanceProfileAssociations } = await ec2Client.send(
  new DescribeIamInstanceProfileAssociationsCommand({
    Filters: [
      { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
    ],
  }),
);
```

- Para obter detalhes da API, consulte DescribeIamInstanceProfileAssociationsa Referência AWS SDK for JavaScript da API.

Obter detalhes sobre endereços IP elásticos

O exemplo de código a seguir mostra como obter detalhes sobre endereços IP elásticos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeAddressesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DescribeAddressesCommand({
    // You can omit this property to show all addresses.
    AllocationIds: ["ALLOCATION_ID"],
  });

  try {
    const { Addresses } = await client.send(command);
    const addressList = Addresses.map((address) => ` • ${address.PublicIp}`);
    console.log("Elastic IP addresses:");
    console.log(addressList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeAddressesa Referência AWS SDK for JavaScript da API.

Obtenha a VPC padrão

O exemplo de código a seguir mostra como obter o VPC padrão da conta atual.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
```

```
);
```

- Para obter detalhes da API, consulte DescribeVpcsa Referência AWS SDK for JavaScript da API.

Obtenha sub-redes padrão para uma VPC

O exemplo de código a seguir mostra como obter as sub-redes padrão para uma VPC.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new EC2Client({});
const { Subnets } = await client.send(
  new DescribeSubnetsCommand({
    Filters: [
      { Name: "vpc-id", Values: [state.defaultVpc] },
      { Name: "availability-zone", Values: state.availabilityZoneNames },
      { Name: "default-for-az", Values: ["true"] },
    ],
  }),
);
```

- Para obter detalhes da API, consulte DescribeSubnetsa Referência AWS SDK for JavaScript da API.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeKeyPairsCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new DescribeKeyPairsCommand({});

  try {
    const { KeyPairs } = await client.send(command);
    const keyPairList = KeyPairs.map(
      (kp) => ` • ${kp.KeyPairId}: ${kp.KeyName}`,
    ).join("\n");
    console.log("The following key pairs were found in your account:");
    console.log(keyPairList);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for JavaScript da API.

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { RebootInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new RebootInstancesCommand({
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    await client.send(command);
    console.log("Instance rebooted successfully.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte RebootInstancesa Referência AWS SDK for JavaScript da API.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ReleaseAddressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new ReleaseAddressCommand({
    // You can also use PublicIp, but that is for EC2 classic which is being
 retired.
    AllocationId: "ALLOCATION_ID",
  });

  try {
    await client.send(command);
    console.log("Successfully released address.");
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for JavaScript da API.

Subtitua o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como substituir o perfil de instância associado a uma instância Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
```

```
          }),
        ),
      );
```

- Para obter detalhes da API, consulte ReplaceIamInstanceProfileAssociationa Referência AWS SDK for JavaScript da API.

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AuthorizeSecurityGroupIngressCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

// Grant permissions for a single IP address to ssh into instances
// within the provided security group.
export const main = async () => {
  const command = new AuthorizeSecurityGroupIngressCommand({
    // Replace with a security group ID from the AWS console or
    // the DescribeSecurityGroupsCommand.
    GroupId: "SECURITY_GROUP_ID",
    IpPermissions: [
      {
        IpProtocol: "tcp",
        FromPort: 22,
        ToPort: 22,
        // Replace 0.0.0.0 with the IP address to authorize.
        // For more information on this notation, see
        // https://en.wikipedia.org/wiki/Classless_Inter-
Domain_Routing#CIDR_notation
```

```
        IpRanges: [{ CidrIp: "0.0.0.0/32" }],
      },
    ],
  });

  try {
    const { SecurityGroupRules } = await client.send(command);
    console.log(JSON.stringify(SecurityGroupRules, null, 2));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for JavaScript da API.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { StartInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new StartInstancesCommand({
    // Use DescribeInstancesCommand to find InstanceIds
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { StartingInstances } = await client.send(command);
```

```
    const instanceIdList = StartingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Starting instances:");
    console.log(instanceIdList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for JavaScript da API.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { StopInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new StopInstancesCommand({
    // Use DescribeInstancesCommand to find InstanceIds
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { StoppingInstances } = await client.send(command);
    const instanceIdList = StoppingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Stopping instances:");
```

```
    console.log(instanceIdList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for JavaScript da API.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { TerminateInstancesCommand } from "@aws-sdk/client-ec2";

import { client } from "../libs/client.js";

export const main = async () => {
  const command = new TerminateInstancesCommand({
    InstanceIds: ["INSTANCE_ID"],
  });

  try {
    const { TerminatingInstances } = await client.send(command);
    const instanceList = TerminatingInstances.map(
      (instance) => ` • ${instance.InstanceId}`,
    );
    console.log("Terminating instances:");
    console.log(instanceList.join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for JavaScript da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
```

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";
```

```
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
```

```
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
```

```
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item'][] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
```

```
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      },
    );
  },
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
```

```
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
```

```
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
```

```
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
```

```
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
```

```
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
  }),
  new ScenarioOutput("gotVpc", (state) =>
    MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
  ),
  new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
  new ScenarioAction("getSubnets", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
```

```
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
```

```
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioOutput(
    "creatingListener",
    MESSAGES.creatingLoadBalancerListener
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
  ),
  new ScenarioAction("createListener", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
    const client = new ElasticLoadBalancingV2Client({});
    const { Listeners } = await client.send(
      new CreateListenerCommand({
        LoadBalancerArn: state.loadBalancerArn,
        Protocol: state.targetGroupProtocol,
        Port: state.targetGroupPort,
        DefaultActions: [
          { Type: "forward", TargetGroupArn: state.targetGroupArn },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
```

```
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-ec2').SecurityGroup}}
state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
```

```
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
```

```
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
```

```
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
```

```
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
```

```
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
```

```
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
```

```
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
```

```
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-scaling').Instance }}
state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
```

```
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );
```

```
        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-ssm').InstanceInformation}}
state
     */
    (state) =>
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
```

```
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
```

```
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
```

```
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
```

```
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
```

```
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
```

```
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
```

```
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
```

```
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
```

```
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
```

```
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
```

```
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
```

```
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
```

```
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
```

```
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
```

```
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
```

```
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
```

```
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Começar a usar instâncias

O código de exemplo a seguir mostra como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.
- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.
- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
import { mkdtempSync, writeFileSync, rmSync } from "fs";
import { tmpdir } from "os";
import { join } from "path";
import { get } from "http";

import {
  AllocateAddressCommand,
  AssociateAddressCommand,
  AuthorizeSecurityGroupIngressCommand,
  CreateKeyPairCommand,
  CreateSecurityGroupCommand,
  DeleteKeyPairCommand,
  DeleteSecurityGroupCommand,
  DescribeInstancesCommand,
  DescribeKeyPairsCommand,
  DescribeSecurityGroupsCommand,
  DisassociateAddressCommand,
  EC2Client,
  paginateDescribeImages,
  paginateDescribeInstanceTypes,
  ReleaseAddressCommand,
  RunInstancesCommand,
  StartInstancesCommand,
```

```
  StopInstancesCommand,
  TerminateInstancesCommand,
  waitUntilInstanceStatusOk,
  waitUntilInstanceStopped,
  waitUntilInstanceTerminated,
} from "@aws-sdk/client-ec2";
import { paginateGetParametersByPath, SSMClient } from "@aws-sdk/client-ssm";

import { wrapText } from "@aws-sdk-examples/libs/utils/util-string.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";

const ec2Client = new EC2Client();
const ssmClient = new SSMClient();

const prompter = new Prompter();
const confirmMessage = "Continue?";
const tmpDirectory = mkdtempSync(join(tmpdir(), "ec2-scenario-tmp"));

const createKeyPair = async (keyPairName) => {
  // Create a key pair in Amazon EC2.
  const { KeyMaterial, KeyPairId } = await ec2Client.send(
    // A unique name for the key pair. Up to 255 ASCII characters.
    new CreateKeyPairCommand({ KeyName: keyPairName }),
  );

  // Save the private key in a temporary location.
  writeFileSync(`${tmpDirectory}/${keyPairName}.pem`, KeyMaterial, {
    mode: 0o400,
  });

  return KeyPairId;
};

const describeKeyPair = async (keyPairName) => {
  const command = new DescribeKeyPairsCommand({
    KeyNames: [keyPairName],
  });
  const { KeyPairs } = await ec2Client.send(command);
  return KeyPairs[0];
};

const createSecurityGroup = async (securityGroupName) => {
  const command = new CreateSecurityGroupCommand({
    GroupName: securityGroupName,
```

```
    Description: "A security group for the Amazon EC2 example.",
  });
  const { GroupId } = await ec2Client.send(command);
  return GroupId;
};

const allocateIpAddress = async () => {
  const command = new AllocateAddressCommand({});
  const { PublicIp, AllocationId } = await ec2Client.send(command);
  return { PublicIp, AllocationId };
};

const getLocalIpAddress = () => {
  return new Promise((res, rej) => {
    get("http://checkip.amazonaws.com", (response) => {
      let data = "";
      response.on("data", (chunk) => (data += chunk));
      response.on("end", () => res(data.trim()));
    }).on("error", (err) => {
      rej(err);
    });
  });
};

const authorizeSecurityGroupIngress = async (securityGroupId) => {
  const ipAddress = await getLocalIpAddress();
  const command = new AuthorizeSecurityGroupIngressCommand({
    GroupId: securityGroupId,
    IpPermissions: [
      {
        IpProtocol: "tcp",
        FromPort: 22,
        ToPort: 22,
        IpRanges: [{ CidrIp: `${ipAddress}/32` }],
      },
    ],
  });

  await ec2Client.send(command);
  return ipAddress;
};

const describeSecurityGroup = async (securityGroupName) => {
  const command = new DescribeSecurityGroupsCommand({
```

```
    GroupNames: [securityGroupName],
  });
  const { SecurityGroups } = await ec2Client.send(command);

  return SecurityGroups[0];
};

const getAmznLinux2AMIs = async () => {
  const AMIs = [];
  for await (const page of paginateGetParametersByPath(
    {
      client: ssmClient,
    },
    { Path: "/aws/service/ami-amazon-linux-latest" },
  )) {
    page.Parameters.forEach((param) => {
      if (param.Name.includes("amzn2")) {
        AMIs.push(param.Value);
      }
    });
  }

  const imageDetails = [];

  for await (const page of paginateDescribeImages(
    { client: ec2Client },
    { ImageIds: AMIs },
  )) {
    imageDetails.push(...(page.Images || []));
  }

  const choices = imageDetails.map((image, index) => ({
    name: `${image.ImageId} - ${image.Description}`,
    value: index,
  }));

  /**
   * @type {number}
   */
  const selectedIndex = await prompter.select({
    message: "Select an image.",
    choices,
  });
```

```
  return imageDetails[selectedIndex];
};

/**
 * @param {import('@aws-sdk/client-ec2').Image} imageDetails
 */
const getCompatibleInstanceTypes = async (imageDetails) => {
  const paginator = paginateDescribeInstanceTypes(
    { client: ec2Client, pageSize: 25 },
    {
      Filters: [
        {
          Name: "processor-info.supported-architecture",
          Values: [imageDetails.Architecture],
        },
        { Name: "instance-type", Values: ["*.micro", "*.small"] },
      ],
    },
  );

  const instanceTypes = [];

  for await (const page of paginator) {
    if (page.InstanceTypes.length) {
      instanceTypes.push(...(page.InstanceTypes || []));
    }
  }

  const choices = instanceTypes.map((type, index) => ({
    name: `${type.InstanceType} - Memory:${type.MemoryInfo.SizeInMiB}`,
    value: index,
  }));

  /**
   * @type {number}
   */
  const selectedIndex = await prompter.select({
    message: "Select an instance type.",
    choices,
  });
  return instanceTypes[selectedIndex];
};

const runInstance = async ({
```

```
  keyPairName,
  securityGroupId,
  imageId,
  instanceType,
}) => {
  const command = new RunInstancesCommand({
    KeyName: keyPairName,
    SecurityGroupIds: [securityGroupId],
    ImageId: imageId,
    InstanceType: instanceType,
    MinCount: 1,
    MaxCount: 1,
  });

  const { Instances } = await ec2Client.send(command);
  await waitUntilInstanceStatusOk(
    { client: ec2Client },
    { InstanceIds: [Instances[0].InstanceId] },
  );
  return Instances[0].InstanceId;
};

const describeInstance = async (instanceId) => {
  const command = new DescribeInstancesCommand({
    InstanceIds: [instanceId],
  });

  const { Reservations } = await ec2Client.send(command);
  return Reservations[0].Instances[0];
};

const displaySSHConnectionInfo = ({ publicIp, keyPairName }) => {
  return `ssh -i ${tmpDirectory}/${keyPairName}.pem ec2-user@${publicIp}`;
};

const stopInstance = async (instanceId) => {
  const command = new StopInstancesCommand({ InstanceIds: [instanceId] });
  await ec2Client.send(command);
  await waitUntilInstanceStopped(
    { client: ec2Client },
    { InstanceIds: [instanceId] },
  );
};
```

```
const startInstance = async (instanceId) => {
  const startCommand = new StartInstancesCommand({ InstanceIds: [instanceId] });
  await ec2Client.send(startCommand);
  await waitUntilInstanceStatusOk(
    { client: ec2Client },
    { InstanceIds: [instanceId] },
  );
  return await describeInstance(instanceId);
};

const associateAddress = async ({ allocationId, instanceId }) => {
  const command = new AssociateAddressCommand({
    AllocationId: allocationId,
    InstanceId: instanceId,
  });

  const { AssociationId } = await ec2Client.send(command);
  return AssociationId;
};

const disassociateAddress = async (associationId) => {
  const command = new DisassociateAddressCommand({
    AssociationId: associationId,
  });
  try {
    await ec2Client.send(command);
  } catch (err) {
    console.warn(
      `Failed to disassociated address with association id: ${associationId}`,
      err,
    );
  }
};

const releaseAddress = async (allocationId) => {
  const command = new ReleaseAddressCommand({
    AllocationId: allocationId,
  });

  try {
    await ec2Client.send(command);
    console.log(`# Address with allocation ID ${allocationId} released.\n`);
  } catch (err) {
    console.log(
```

```
      `Failed to release address with allocation id: ${allocationId}.`,
      err,
    );
  }
};

const restartInstance = async (instanceId) => {
  console.log("Stopping instance.");
  await stopInstance(instanceId);
  console.log("Instance stopped.");
  console.log("Starting instance.");
  const { PublicIpAddress } = await startInstance(instanceId);
  return PublicIpAddress;
};

const terminateInstance = async (instanceId) => {
  const command = new TerminateInstancesCommand({
    InstanceIds: [instanceId],
  });

  try {
    await ec2Client.send(command);
    await waitUntilInstanceTerminated(
      { client: ec2Client },
      { InstanceIds: [instanceId] },
    );
    console.log(`# Instance with ID ${instanceId} terminated.\n`);
  } catch (err) {
    console.warn(`Failed to terminate instance ${instanceId}.`, err);
  }
};

const deleteSecurityGroup = async (securityGroupId) => {
  const command = new DeleteSecurityGroupCommand({
    GroupId: securityGroupId,
  });

  try {
    await ec2Client.send(command);
    console.log(`# Security group ${securityGroupId} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete security group ${securityGroupId}.`, err);
  }
};
```

```
const deleteKeyPair = async (keyPairName) => {
  const command = new DeleteKeyPairCommand({
    KeyName: keyPairName,
  });

  try {
    await ec2Client.send(command);
    console.log(`# Key pair ${keyPairName} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete key pair ${keyPairName}.`, err);
  }
};

const deleteTemporaryDirectory = () => {
  try {
    rmSync(tmpDirectory, { recursive: true });
    console.log(`# Temporary directory ${tmpDirectory} deleted.\n`);
  } catch (err) {
    console.warn(`Failed to delete temporary directory ${tmpDirectory}.`, err);
  }
};

export const main = async () => {
  const keyPairName = "ec2-scenario-key-pair";
  const securityGroupName = "ec2-scenario-security-group";

  let securityGroupId, ipAllocationId, publicIp, instanceId, associationId;

  console.log(wrapText("Welcome to the Amazon EC2 basic usage scenario."));

  try {
    // Prerequisites
    console.log(
      "Before you launch an instance, you'll need a few things:",
      "\n - A Key Pair",
      "\n - A Security Group",
      "\n - An IP Address",
      "\n - An AMI",
      "\n - A compatible instance type",
      "\n\n I'll go ahead and take care of the first three, but I'll need your help
 for the rest.",
    );
```

```
    await prompter.confirm({ message: confirmMessage });

    await createKeyPair(keyPairName);
    securityGroupId = await createSecurityGroup(securityGroupName);
    const { PublicIp, AllocationId } = await allocateIpAddress();
    ipAllocationId = AllocationId;
    publicIp = PublicIp;
    const ipAddress = await authorizeSecurityGroupIngress(securityGroupId);

    const { KeyName } = await describeKeyPair(keyPairName);
    const { GroupName } = await describeSecurityGroup(securityGroupName);
    console.log(`# created the key pair ${KeyName}.\n`);
    console.log(
      `# created the security group ${GroupName}`,
      `and allowed SSH access from ${ipAddress} (your IP).\n`,
    );
    console.log(`# allocated ${publicIp} to be used for your EC2 instance.\n`);

    await prompter.confirm({ message: confirmMessage });

    // Creating the instance
    console.log(wrapText("Create the instance."));
    console.log(
      "You get to choose which image you want. Select an amazon-linux-2 image from
the following:",
    );
    const imageDetails = await getAmznLinux2AMIs();
    const instanceTypeDetails = await getCompatibleInstanceTypes(imageDetails);
    console.log("Creating your instance. This can take a few seconds.");
    instanceId = await runInstance({
      keyPairName,
      securityGroupId,
      imageId: imageDetails.ImageId,
      instanceType: instanceTypeDetails.InstanceType,
    });
    const instanceDetails = await describeInstance(instanceId);
    console.log(`# instance ${instanceId}.\n`);
    console.log(instanceDetails);
    console.log(
      `\nYou should now be able to SSH into your instance from another terminal:`,
      `\n${displaySSHConnectionInfo({
        publicIp: instanceDetails.PublicIpAddress,
        keyPairName,
      })}`,
```

```
    );

    await prompter.confirm({ message: confirmMessage });

    // Understanding the IP address.
    console.log(wrapText("Understanding the IP address."));
    console.log(
      "When you stop and start an instance, the IP address will change. I'll restart
your",
      "instance for you. Notice how the IP address changes.",
    );
    const ipAddressAfterRestart = await restartInstance(instanceId);
    console.log(
      `\n Instance started. The IP address changed from
${instanceDetails.PublicIpAddress} to ${ipAddressAfterRestart}`,
      `\n${displaySSHConnectionInfo({
        publicIp: ipAddressAfterRestart,
        keyPairName,
      })}`,
    );
    await prompter.confirm({ message: confirmMessage });
    console.log(
      `If you want to the IP address to be static, you can associate an allocated`,
      `IP address to your instance. I allocated ${publicIp} for you earlier, and now
I'll associate it to your instance.`,
    );
    associationId = await associateAddress({
      allocationId: ipAllocationId,
      instanceId,
    });
    console.log(
      "Done. Now you should be able to SSH using the new IP.\n",
      `${displaySSHConnectionInfo({ publicIp, keyPairName })}`,
    );
    await prompter.confirm({ message: confirmMessage });
    console.log(
      "I'll restart the server again so you can see the IP address remains the
same.",
    );
    const ipAddressAfterAssociated = await restartInstance(instanceId);
    console.log(
      `Done. Here's your SSH info. Notice the IP address hasn't changed.`,
      `\n${displaySSHConnectionInfo({
        publicIp: ipAddressAfterAssociated,
```

```
        keyPairName,
      })}`,
    );
    await prompter.confirm({ message: confirmMessage });
  } catch (err) {
    console.error(err);
  } finally {
    // Clean up.
    console.log(wrapText("Clean up."));
    console.log("Now I'll clean up all of the stuff I created.");
    await prompter.confirm({ message: confirmMessage });
    console.log("Cleaning up. Some of these steps can take a bit of time.");
    await disassociateAddress(associationId);
    await terminateInstance(instanceId);
    await releaseAddress(ipAllocationId);
    await deleteSecurityGroup(securityGroupId);
    deleteTemporaryDirectory();
    await deleteKeyPair(keyPairName);
    console.log(
      "Done cleaning up. Thanks for staying until the end!",
      "If you have any feedback please use the feedback button in the docs",
      "or create an issue on GitHub.",
    );
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances

- DescribeKeyPairs
- DescribeSecurityGroups
- DisassociateAddress
- ReleaseAddress
- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

Exemplos de Elastic Load Balancing usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Elastic Load Balancing.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Elastic Load Balancing

Os exemplos de código a seguir mostram como começar a usar o Elastic Load Balancing.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  ElasticLoadBalancingV2Client,
  DescribeLoadBalancersCommand,
} from "@aws-sdk/client-elastic-load-balancing-v2";

export async function main() {
  const client = new ElasticLoadBalancingV2Client({});
  const { LoadBalancers } = await client.send(
    new DescribeLoadBalancersCommand({}),
  );
  const loadBalancersList = LoadBalancers.map(
    (lb) => `• ${lb.LoadBalancerName}: ${lb.DNSName}`,
  ).join("\n");
  console.log(
    "Hello, Elastic Load Balancing! Let's list some of your load balancers:\n",
    loadBalancersList,
  );
}

// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  main();
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Criar um receptor para o balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como criar um receptor que encaminha solicitações de um balanceador de carga do ELB para um grupo de destino.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const { Listeners } = await client.send(
  new CreateListenerCommand({
    LoadBalancerArn: state.loadBalancerArn,
    Protocol: state.targetGroupProtocol,
    Port: state.targetGroupPort,
    DefaultActions: [
      { Type: "forward", TargetGroupArn: state.targetGroupArn },
    ],
  }),
);
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for JavaScript da API.

Criar um grupo de destino

O exemplo de código a seguir mostra como criar um grupo de destino ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const { TargetGroups } = await client.send(
  new CreateTargetGroupCommand({
    Name: NAMES.loadBalancerTargetGroupName,
    Protocol: "HTTP",
    Port: 80,
    HealthCheckPath: "/healthcheck",
    HealthCheckIntervalSeconds: 10,
    HealthCheckTimeoutSeconds: 5,
    HealthyThresholdCount: 2,
    UnhealthyThresholdCount: 2,
    VpcId: state.defaultVpc,
  }),
);
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for JavaScript da API.

Criar um Application Load Balancer

O exemplo de código a seguir mostra como criar um Application Load Balancer do ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
```

```
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for JavaScript da API.

Excluir um balanceador de carga

O exemplo de código a seguir mostra como excluir um balanceador de carga do ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    const client = new ElasticLoadBalancingV2Client({});
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    await client.send(
      new DeleteLoadBalancerCommand({
        LoadBalancerArn: loadBalancer.LoadBalancerArn,
      }),
    );
    await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
      const lb = await findLoadBalancer(NAMES.loadBalancerName);
      if (lb) {
        throw new Error("Load balancer still exists.");
      }
```

```
  });
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for JavaScript da API.

Excluir um grupo de destino

O exemplo de código a seguir mostra como excluir um grupo de destino do ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
try {
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );

  await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
    client.send(
      new DeleteTargetGroupCommand({
        TargetGroupArn: TargetGroups[0].TargetGroupArn,
      }),
    ),
  );
} catch (e) {
  state.deleteLoadBalancerTargetGroupError = e;
}
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for JavaScript da API.

Descrever grupos de destino

O exemplo de código a seguir mostra como descrever grupos de destino específicos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new ElasticLoadBalancingV2Client({});
const { TargetGroups } = await client.send(
  new DescribeTargetGroupsCommand({
    Names: [NAMES.loadBalancerTargetGroupName],
  }),
);
```

- Para obter detalhes da API, consulte DescribeTargetGroupsa Referência AWS SDK for JavaScript da API.

Obter o endpoint de um balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como obter um endpoint de um balanceador de carga ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  ElasticLoadBalancingV2Client,
```

```
  DescribeLoadBalancersCommand,
} from "@aws-sdk/client-elastic-load-balancing-v2";

export async function main() {
  const client = new ElasticLoadBalancingV2Client({});
  const { LoadBalancers } = await client.send(
    new DescribeLoadBalancersCommand({}),
  );
  const loadBalancersList = LoadBalancers.map(
    (lb) => `• ${lb.LoadBalancerName}: ${lb.DNSName}`,
  ).join("\n");
  console.log(
    "Hello, Elastic Load Balancing! Let's list some of your load balancers:\n",
    loadBalancersList,
  );
}

// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  main();
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for JavaScript da API.

Obter a integridade de um grupo de destino

O exemplo de código a seguir mostra como obter a integridade de instâncias em um grupo de destino do ELB.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  const { TargetHealthDescriptions } = await client.send(
```

```
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
```

- Para obter detalhes da API, consulte DescribeTargetHealtha Referência AWS SDK for JavaScript da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};
```

```
// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
```

```
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
```

```
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item'][] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );
```

```
    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );

    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
```

```
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
```

```
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
```

```
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
```

```
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
```

```
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
  }),
  new ScenarioOutput("gotVpc", (state) =>
    MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
  ),
  new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
  new ScenarioAction("getSubnets", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
```

```
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
```

```
    ),
    new ScenarioOutput(
      "creatingLoadBalancer",
      MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
    ),
    new ScenarioAction("createLoadBalancer", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const { LoadBalancers } = await client.send(
        new CreateLoadBalancerCommand({
          Name: NAMES.loadBalancerName,
          Subnets: state.subnets,
        }),
      );
      state.loadBalancerDns = LoadBalancers[0].DNSName;
      state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
      await waitUntilLoadBalancerAvailable(
        { client },
        { Names: [NAMES.loadBalancerName] },
      );
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    }),
    new ScenarioOutput("createdLoadBalancer", (state) =>
      MESSAGES.createdLoadBalancer
        .replace("${LB_NAME}", NAMES.loadBalancerName)
        .replace("${DNS_NAME}", state.loadBalancerDns),
    ),
    new ScenarioOutput(
      "creatingListener",
      MESSAGES.creatingLoadBalancerListener
        .replace("${LB_NAME}", NAMES.loadBalancerName)
        .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
    ),
    new ScenarioAction("createListener", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
      const client = new ElasticLoadBalancingV2Client({});
      const { Listeners } = await client.send(
        new CreateListenerCommand({
          LoadBalancerArn: state.loadBalancerArn,
          Protocol: state.targetGroupProtocol,
          Port: state.targetGroupPort,
          DefaultActions: [
            { Type: "forward", TargetGroupArn: state.targetGroupArn },
          ],
```

```
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
    const listener = Listeners[0];
    state.loadBalancerListenerArn = listener.ListenerArn;
  }),
  new ScenarioOutput("createdListener", (state) =>
    MESSAGES.createdLoadBalancerListener.replace(
      "${LB_LISTENER_ARN}",
      state.loadBalancerListenerArn,
    ),
  ),
  new ScenarioOutput(
    "attachingLoadBalancerTargetGroup",
    MESSAGES.attachingLoadBalancerTargetGroup
      .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
      .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
  ),
  new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
    const client = new AutoScalingClient({});
    await client.send(
      new AttachLoadBalancerTargetGroupsCommand({
        AutoScalingGroupName: NAMES.autoScalingGroupName,
        TargetGroupARNs: [state.targetGroupArn],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-ec2').SecurityGroup}}
state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
```

```
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
```

```
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
      await client.send(
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
```

```
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
```

```
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
```

```
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
```

```
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];
```

```
/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
```

```
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-scaling').Instance }}
state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
```

```
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );
```

```
        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-ssm').InstanceInformation}}
state
     */
    (state) =>
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
```

```
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
```

```
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
```

```
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
```

```
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
```

```
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
```

```
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
```

```
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
```

```
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
```

```
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
```

```
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
```

```
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
```

```
new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  const client = new ElasticLoadBalancingV2Client({});
  try {
    const { TargetGroups } = await client.send(
      new DescribeTargetGroupsCommand({
        Names: [NAMES.loadBalancerTargetGroupName],
      }),
    );

    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      client.send(
        new DeleteTargetGroupCommand({
          TargetGroupArn: TargetGroups[0].TargetGroupArn,
        }),
      ),
    );
  } catch (e) {
    state.deleteLoadBalancerTargetGroupError = e;
  }
  // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
}),
new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
  if (state.deleteLoadBalancerTargetGroupError) {
    console.error(state.deleteLoadBalancerTargetGroupError);
    return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    );
  } else {
    return MESSAGES.deletedLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    );
  }
}),
new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
  try {
    const client = new IAMClient({});
    await client.send(
      new RemoveRoleFromInstanceProfileCommand({
        InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        RoleName: NAMES.ssmOnlyRoleName,
      }),
```

```
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
```

```
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
```

```
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
```

```
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
```

```
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
```

```
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

EventBridge exemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
  EventBridgeClient,
  PutTargetsCommand,
} from "@aws-sdk/client-eventbridge";
```

```
export const putTarget = async (
  existingRuleName = "some-rule",
  targetArn = "arn:aws:lambda:us-east-1:000000000000:function:test-func",
  uniqueId = Date.now().toString(),
) => {
  const client = new EventBridgeClient({});
  const response = await client.send(
    new PutTargetsCommand({
      Rule: existingRuleName,
      Targets: [
        {
          Arn: targetArn,
          Id: uniqueId,
        },
      ],
    }),
  );

  console.log("PutTargets response:");
  console.log(response);
  // PutTargets response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'f5b23b9a-2c17-45c1-ad5c-f926c3692e3d',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   FailedEntries: [],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Rule: "DEMO_EVENT",
  Targets: [
    {
      Arn: "LAMBDA_FUNCTION_ARN",
      Id: "myEventBridgeTarget",
    },
  ],
};

ebevents.putTargets(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for JavaScript da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import { EventBridgeClient, PutRuleCommand } from "@aws-sdk/client-eventbridge";

export const putRule = async (
  ruleName = "some-rule",
  source = "some-source",
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutRuleCommand({
      Name: ruleName,
      EventPattern: JSON.stringify({ source: [source] }),
      State: "ENABLED",
      EventBusName: "default",
    }),
  );

  console.log("PutRule response:");
  console.log(response);
  // PutRule response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'd7292ced-1544-421b-842f-596326bc7072',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   RuleArn: 'arn:aws:events:us-east-1:xxxxxxxxxxxx:rule/
EventBridgeTestRule-1696280037720'
  // }
  return response;
```

```
};
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Name: "DEMO_EVENT",
  RoleArn: "IAM_ROLE_ARN",
  ScheduleExpression: "rate(5 minutes)",
  State: "ENABLED",
};

ebevents.putRule(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.RuleArn);
  }
});
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for JavaScript da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
import {
  EventBridgeClient,
  PutEventsCommand,
} from "@aws-sdk/client-eventbridge";

export const putEvents = async (
  source = "eventbridge.integration.test",
  detailType = "greeting",
  resources = [],
) => {
  const client = new EventBridgeClient({});

  const response = await client.send(
    new PutEventsCommand({
      Entries: [
        {
          Detail: JSON.stringify({ greeting: "Hello there." }),
          DetailType: detailType,
          Resources: resources,
          Source: source,
        },
      ],
    }),
  );

  console.log("PutEvents response:");
  console.log(response);
  // PutEvents response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '3d0df73d-dcea-4a23-ae0d-f5556a3ac109',
  //     extendedRequestId: undefined,
```

```
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Entries: [ { EventId: '51620841-5af4-6402-d9bc-b77734991eb5' } ],
  //   FailedEntryCount: 0
  // }

  return response;
};
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create CloudWatchEvents service object
var ebevents = new AWS.EventBridge({ apiVersion: "2015-10-07" });

var params = {
  Entries: [
    {
      Detail: '{ "key1": "value1", "key2": "value2" }',
      DetailType: "appRequestSubmitted",
      Resources: ["RESOURCE_ARN"],
      Source: "com.company.app",
    },
  ],
};

ebevents.putEvents(params, function (err, data) {
  if (err) {
```

```
    console.log("Error", err);
  } else {
    console.log("Success", data.Entries);
  }
});
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

AWS Glueexemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListJobsCommand, GlueClient } from "@aws-sdk/client-glue";

const client = new GlueClient({});
```

```
export const main = async () => {
  const command = new ListJobsCommand({});

  const { JobNames } = await client.send(command);
  const formattedJobNames = JobNames.join("\n");
  console.log("Job names: ");
  console.log(formattedJobNames);
  return JobNames;
};
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

O exemplo de código a seguir mostra como criar um crawler do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createCrawler = (name, role, dbName, tablePrefix, s3TargetPath) => {
  const client = new GlueClient({});

  const command = new CreateCrawlerCommand({
    Name: name,
    Role: role,
    DatabaseName: dbName,
    TablePrefix: tablePrefix,
```

```
    Targets: {
      S3Targets: [{ Path: s3TargetPath }],
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for JavaScript da API.

Crie uma definição de trabalho

O exemplo de código a seguir mostra como criar uma definição de trabalho do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createJob = (name, role, scriptBucketName, scriptKey) => {
  const client = new GlueClient({});

  const command = new CreateJobCommand({
    Name: name,
    Role: role,
    Command: {
      Name: "glueetl",
      PythonVersion: "3",
      ScriptLocation: `s3:///${scriptBucketName}/${scriptKey}`,
    },
    GlueVersion: "3.0",
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for JavaScript da API.

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteCrawler = (crawlerName) => {
  const client = new GlueClient({});

  const command = new DeleteCrawlerCommand({
    Name: crawlerName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for JavaScript da API.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteDatabase = (databaseName) => {
  const client = new GlueClient({});

  const command = new DeleteDatabaseCommand({
    Name: databaseName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for JavaScript da API.

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteJob = (jobName) => {
  const client = new GlueClient({});

  const command = new DeleteJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for JavaScript da API.

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela do AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const deleteTable = (databaseName, tableName) => {
  const client = new GlueClient({});

  const command = new DeleteTableCommand({
    DatabaseName: databaseName,
    Name: tableName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for JavaScript da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getCrawler = (name) => {
  const client = new GlueClient({});
```

```
  const command = new GetCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for JavaScript da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getDatabase = (name) => {
  const client = new GlueClient({});

  const command = new GetDatabaseCommand({
    Name: name,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for JavaScript da API.

Obter uma execução de trabalho

O exemplo de código a seguir mostra como obter uma execução de trabalho do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJobRun = (jobName, jobRunId) => {
  const client = new GlueClient({});
  const command = new GetJobRunCommand({
    JobName: jobName,
    RunId: jobRunId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for JavaScript da API.

Obter uma lista de bancos de dados do Data Catalog

Os exemplos de código a seguir mostram como obter uma lista de bancos de dados do AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getDatabases = () => {
  const client = new GlueClient({});

  const command = new GetDatabasesCommand({});
```

```
  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetDatabasesa Referência AWS SDK for JavaScript da API.

Obter um trabalho do Data Catalog

Os exemplos de código a seguir mostram como obter um trabalho do AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJob = (jobName) => {
  const client = new GlueClient({});

  const command = new GetJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for JavaScript da API.

Obter execuções de um trabalho

O exemplo de código a seguir mostra como obter execuções de um trabalho do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getJobRuns = (jobName) => {
  const client = new GlueClient({});
  const command = new GetJobRunsCommand({
    JobName: jobName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for JavaScript da API.

Obter tabelas de um banco de dados

O exemplo de código a seguir mostra como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getTables = (databaseName) => {
  const client = new GlueClient({});

  const command = new GetTablesCommand({
    DatabaseName: databaseName,
  });
```

```
  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for JavaScript da API.

Listar definições de trabalho

O exemplo de código a seguir mostra como listas definições de trabalho do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listJobs = () => {
  const client = new GlueClient({});

  const command = new ListJobsCommand({});

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for JavaScript da API.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const startCrawler = (name) => {
  const client = new GlueClient({});

  const command = new StartCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for JavaScript da API.

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const startJobRun = (jobName, dbName, tableName, bucketName) => {
  const client = new GlueClient({});

  const command = new StartJobRunCommand({
    JobName: jobName,
    Arguments: {
      "--input_database": dbName,
      "--input_table": tableName,
      "--output_bucket_url": `s3://${bucketName}/`,
    },
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for JavaScript da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e execute um crawler que examine um bucket público do Amazon Simple Storage Service (Amazon S3) e gere um banco de dados de metadados que descreva os dados no formato CSV que encontrar.

```
const createCrawler = (name, role, dbName, tablePrefix, s3TargetPath) => {
  const client = new GlueClient({});

  const command = new CreateCrawlerCommand({
    Name: name,
    Role: role,
    DatabaseName: dbName,
```

```
    TablePrefix: tablePrefix,
    Targets: {
      S3Targets: [{ Path: s3TargetPath }],
    },
  });

  return client.send(command);
};

const getCrawler = (name) => {
  const client = new GlueClient({});

  const command = new GetCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};

const startCrawler = (name) => {
  const client = new GlueClient({});

  const command = new StartCrawlerCommand({
    Name: name,
  });

  return client.send(command);
};

const crawlerExists = async ({ getCrawler }, crawlerName) => {
  try {
    await getCrawler(crawlerName);
    return true;
  } catch {
    return false;
  }
};

const makeCreateCrawlerStep = (actions) => async (context) => {
  if (await crawlerExists(actions, process.env.CRAWLER_NAME)) {
    log("Crawler already exists. Skipping creation.");
  } else {
    await actions.createCrawler(
      process.env.CRAWLER_NAME,
```

```
      process.env.ROLE_NAME,
      process.env.DATABASE_NAME,
      process.env.TABLE_PREFIX,
      process.env.S3_TARGET_PATH
    );

    log("Crawler created successfully.", { type: "success" });
  }

  return { ...context };
};

/**
 * @param {(name: string) => Promise<import('@aws-sdk/client-
glue').GetCrawlerCommandOutput>} getCrawler
 * @param {string} crawlerName
 */
const waitForCrawler = async (getCrawler, crawlerName) => {
  const waitTimeInSeconds = 30;
  const { Crawler } = await getCrawler(crawlerName);

  if (!Crawler) {
    throw new Error(`Crawler with name ${crawlerName} not found.`);
  }

  if (Crawler.State === "READY") {
    return;
  }

  log(`Crawler is ${Crawler.State}. Waiting ${waitTimeInSeconds} seconds...`);
  await wait(waitTimeInSeconds);
  return waitForCrawler(getCrawler, crawlerName);
};

const makeStartCrawlerStep =
  ({ startCrawler, getCrawler }) =>
  async (context) => {
    log("Starting crawler.");
    await startCrawler(process.env.CRAWLER_NAME);
    log("Crawler started.", { type: "success" });

    log("Waiting for crawler to finish running. This can take a while.");
    await waitForCrawler(getCrawler, process.env.CRAWLER_NAME);
    log("Crawler ready.", { type: "success" });
```

```
    return { ...context };
  };
```

Liste informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.

```
const getDatabase = (name) => {
  const client = new GlueClient({});

  const command = new GetDatabaseCommand({
    Name: name,
  });

  return client.send(command);
};

const getTables = (databaseName) => {
  const client = new GlueClient({});

  const command = new GetTablesCommand({
    DatabaseName: databaseName,
  });

  return client.send(command);
};

const makeGetDatabaseStep =
  ({ getDatabase }) =>
  async (context) => {
    const {
      Database: { Name },
    } = await getDatabase(process.env.DATABASE_NAME);
    log(`Database: ${Name}`);
    return { ...context };
  };

const makeGetTablesStep =
  ({ getTables }) =>
  async (context) => {
    const { TableList } = await getTables(process.env.DATABASE_NAME);
    log("Tables:");
    log(TableList.map((table) => `  • ${table.Name}\n`));
```

```
    return { ...context };
  };
```

Crie e execute um trabalho que extraia dados em CSV do bucket do Amazon S3 de origem, transforme-os removendo e renomeando campos, e carregue a saída formatada em JSON em outro bucket do Amazon S3.

```
const createJob = (name, role, scriptBucketName, scriptKey) => {
  const client = new GlueClient({});

  const command = new CreateJobCommand({
    Name: name,
    Role: role,
    Command: {
      Name: "glueetl",
      PythonVersion: "3",
      ScriptLocation: `s3://${scriptBucketName}/${scriptKey}`,
    },
    GlueVersion: "3.0",
  });

  return client.send(command);
};

const startJobRun = (jobName, dbName, tableName, bucketName) => {
  const client = new GlueClient({});

  const command = new StartJobRunCommand({
    JobName: jobName,
    Arguments: {
      "--input_database": dbName,
      "--input_table": tableName,
      "--output_bucket_url": `s3://${bucketName}/`,
    },
  });

  return client.send(command);
};

const makeCreateJobStep =
  ({ createJob }) =>
  async (context) => {
```

```
    log("Creating Job.");
    await createJob(
      process.env.JOB_NAME,
      process.env.ROLE_NAME,
      process.env.BUCKET_NAME,
      process.env.PYTHON_SCRIPT_KEY,
    );
    log("Job created.", { type: "success" });

    return { ...context };
  };

/**
 * @param {(name: string, runId: string) => Promise<import('@aws-sdk/client-
glue').GetJobRunCommandOutput> }  getJobRun
 * @param {string} jobName
 * @param {string} jobRunId
 */
const waitForJobRun = async (getJobRun, jobName, jobRunId) => {
  const waitTimeInSeconds = 30;
  const { JobRun } = await getJobRun(jobName, jobRunId);

  if (!JobRun) {
    throw new Error(`Job run with id ${jobRunId} not found.`);
  }

  switch (JobRun.JobRunState) {
    case "FAILED":
    case "TIMEOUT":
    case "STOPPED":
      throw new Error(
        `Job ${JobRun.JobRunState}. Error: ${JobRun.ErrorMessage}`,
      );
    case "RUNNING":
      break;
    case "SUCCEEDED":
      return;
    default:
      throw new Error(`Unknown job run state: ${JobRun.JobRunState}`);
  }

  log(
    `Job ${JobRun.JobRunState}. Waiting ${waitTimeInSeconds} more seconds...`,
  );
```

```
  await wait(waitTimeInSeconds);
  return waitForJobRun(getJobRun, jobName, jobRunId);
};

/**
 * @param {{ prompter: { prompt: () => Promise<{ shouldOpen: boolean }>} }} context
 */
const promptToOpen = async (context) => {
  const { shouldOpen } = await context.prompter.prompt({
    name: "shouldOpen",
    type: "confirm",
    message: "Open the output bucket in your browser?",
  });

  if (shouldOpen) {
    return open(
      `https://s3.console.aws.amazon.com/s3/buckets/${process.env.BUCKET_NAME} to
 view the output.`,
    );
  }
};

const makeStartJobRunStep =
  ({ startJobRun, getJobRun }) =>
  async (context) => {
    log("Starting job.");
    const { JobRunId } = await startJobRun(
      process.env.JOB_NAME,
      process.env.DATABASE_NAME,
      process.env.TABLE_NAME,
      process.env.BUCKET_NAME,
    );
    log("Job started.", { type: "success" });

    log("Waiting for job to finish running. This can take a while.");
    await waitForJobRun(getJobRun, process.env.JOB_NAME, JobRunId);
    log("Job run succeeded.", { type: "success" });

    await promptToOpen(context);

    return { ...context };
  };
```

Liste informações sobre execuções de tarefas e visualize alguns dos dados transformados.

```
const getJobRuns = (jobName) => {
  const client = new GlueClient({});
  const command = new GetJobRunsCommand({
    JobName: jobName,
  });

  return client.send(command);
};

const getJobRun = (jobName, jobRunId) => {
  const client = new GlueClient({});
  const command = new GetJobRunCommand({
    JobName: jobName,
    RunId: jobRunId,
  });

  return client.send(command);
};

const logJobRunDetails = async (getJobRun, jobName, jobRunId) => {
  const { JobRun } = await getJobRun(jobName, jobRunId);
  log(JobRun, { type: "object" });
};

const makePickJobRunStep =
  ({ getJobRuns, getJobRun }) =>
  async (context) => {
    if (context.selectedJobName) {
      const { JobRuns } = await getJobRuns(context.selectedJobName);

      const { jobRunId } = await context.prompter.prompt({
        name: "jobRunId",
        type: "list",
        message: "Select a job run to see details.",
        choices: JobRuns.map((run) => run.Id),
      });

      logJobRunDetails(getJobRun, context.selectedJobName, jobRunId);
    }

    return { ...context };
  };
```

Exclua todos os recursos criados pela demonstração.

```
const deleteJob = (jobName) => {
  const client = new GlueClient({});

  const command = new DeleteJobCommand({
    JobName: jobName,
  });

  return client.send(command);
};

const deleteTable = (databaseName, tableName) => {
  const client = new GlueClient({});

  const command = new DeleteTableCommand({
    DatabaseName: databaseName,
    Name: tableName,
  });

  return client.send(command);
};

const deleteDatabase = (databaseName) => {
  const client = new GlueClient({});

  const command = new DeleteDatabaseCommand({
    Name: databaseName,
  });

  return client.send(command);
};

const deleteCrawler = (crawlerName) => {
  const client = new GlueClient({});

  const command = new DeleteCrawlerCommand({
    Name: crawlerName,
  });

  return client.send(command);
```

```
};

const handleDeleteJobs = async (deleteJobFn, jobNames, context) => {
  const { selectedJobNames } = await context.prompter.prompt({
    name: "selectedJobNames",
    type: "checkbox",
    message: "Let's clean up jobs. Select jobs to delete.",
    choices: jobNames,
  });

  if (selectedJobNames.length === 0) {
    log("No jobs selected.");
  } else {
    log("Deleting jobs.");
    await Promise.all(
      selectedJobNames.map((n) => deleteJobFn(n).catch(console.error))
    );
    log("Jobs deleted.", { type: "success" });
  }
};

const makeCleanUpJobsStep =
  ({ listJobs, deleteJob }) =>
  async (context) => {
    const { JobNames } = await listJobs();
    if (JobNames.length > 0) {
      await handleDeleteJobs(deleteJob, JobNames, context);
    }

    return { ...context };
  };

const deleteTables = (deleteTable, databaseName, tableNames) =>
  Promise.all(
    tableNames.map((tableName) =>
      deleteTable(databaseName, tableName).catch(console.error)
    )
  );

const makeCleanUpTablesStep =
  ({ getTables, deleteTable }) =>
  async (context) => {
    const { TableList } = await getTables(process.env.DATABASE_NAME).catch(
      () => ({ TableList: null })
```

```
    );

    if (TableList && TableList.length > 0) {
      const { tableNames } = await context.prompter.prompt({
        name: "tableNames",
        type: "checkbox",
        message: "Let's clean up tables. Select tables to delete.",
        choices: TableList.map((t) => t.Name),
      });

      if (tableNames.length === 0) {
        log("No tables selected.");
      } else {
        log("Deleting tables.");
        await deleteTables(deleteTable, process.env.DATABASE_NAME, tableNames);
        log("Tables deleted.", { type: "success" });
      }
    }

    return { ...context };
  };

const deleteDatabases = (deleteDatabase, databaseNames) =>
  Promise.all(
    databaseNames.map((dbName) => deleteDatabase(dbName).catch(console.error))
  );

const makeCleanUpDatabasesStep =
  ({ getDatabases, deleteDatabase }) =>
  async (context) => {
    const { DatabaseList } = await getDatabases();

    if (DatabaseList.length > 0) {
      const { dbNames } = await context.prompter.prompt({
        name: "dbNames",
        type: "checkbox",
        message: "Let's clean up databases. Select databases to delete.",
        choices: DatabaseList.map((db) => db.Name),
      });

      if (dbNames.length === 0) {
        log("No databases selected.");
      } else {
        log("Deleting databases.");
```

```
        await deleteDatabases(deleteDatabase, dbNames);
        log("Databases deleted.", { type: "success" });
      }
    }

    return { ...context };
  };

const cleanUpCrawlerStep = async (context) => {
  log(`Deleting crawler.`);

  try {
    await deleteCrawler(process.env.CRAWLER_NAME);
    log("Crawler deleted.", { type: "success" });
  } catch (err) {
    if (err.name === "EntityNotFoundException") {
      log(`Crawler is already deleted.`);
    } else {
      throw err;
    }
  }

  return { ...context };
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun

- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

HealthImaging exemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com HealthImaging.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá HealthImaging

O exemplo de código a seguir mostra como começar a usar o HealthImaging.

SDK para JavaScript (v3)

```
import {
  ListDatastoresCommand,
  MedicalImagingClient,
} from "@aws-sdk/client-medical-imaging";

// When no region or credentials are provided, the SDK will use the
// region and credentials from the local AWS config.
const client = new MedicalImagingClient({});

export const helloMedicalImaging = async () => {
  const command = new ListDatastoresCommand({});
```

```
  const { datastoreSummaries } = await client.send(command);
  console.log("Datastores: ");
  console.log(datastoreSummaries.map((item) => item.datastoreName).join("\n"));
  return datastoreSummaries;
};
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma tag a um recurso

O exemplo de código a seguir mostra como adicionar uma tag a um HealthImaging recurso.

SDK para JavaScript (v3)

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tags = {}
```

```
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte TagResourcea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copiar um conjunto de imagens

O exemplo de código a seguir mostra como copiar um conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

Função de utilitário para copiar um conjunto de imagens.

```
import { CopyImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imageSetId - The source image set ID.
```

```
 * @param {string} sourceVersionId - The source version ID.
 * @param {string} destinationImageSetId - The optional ID of the destination image
 set.
 * @param {string} destinationVersionId - The optional version ID of the destination
 image set.
 */
export const copyImageSet = async (
  datastoreId = "xxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxx",
  sourceVersionId = "1",
  destinationImageSetId = "",
  destinationVersionId = ""
) => {
  const params = {
    datastoreId: datastoreId,
    sourceImageSetId: imageSetId,
    copyImageSetInformation: {
      sourceImageSet: { latestVersionId: sourceVersionId },
    },
  };
  if (destinationImageSetId !== "" && destinationVersionId !== "") {
    params.copyImageSetInformation.destinationImageSet = {
      imageSetId: destinationImageSetId,
      latestVersionId: destinationVersionId,
    };
  }

  const response = await medicalImagingClient.send(
    new CopyImageSetCommand(params)
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'd9b219ce-cc48-4a44-a5b2-c5c3068f1ee8',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //      },
  //       datastoreId: 'xxxxxxxxxxxxxx',
  //       destinationImageSetProperties: {
  //             createdAt: 2023-09-27T19:46:21.824Z,
```

```
  //             imageSetArn: 'arn:aws:medical-imaging:us-
east-1:xxxxxxxxxxx:datastore/xxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxxxx',
  //             imageSetId: 'xxxxxxxxxxxxxxx',
  //             imageSetState: 'LOCKED',
  //             imageSetWorkflowStatus: 'COPYING',
  //             latestVersionId: '1',
  //             updatedAt: 2023-09-27T19:46:21.824Z
  //       },
  //       sourceImageSetProperties: {
  //             createdAt: 2023-09-22T14:49:26.427Z,
  //             imageSetArn: 'arn:aws:medical-imaging:us-
east-1:xxxxxxxxxxx:datastore/xxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxx',
  //             imageSetId: 'xxxxxxxxxxxxxxxx',
  //             imageSetState: 'LOCKED',
  //             imageSetWorkflowStatus: 'COPYING_WITH_READ_ONLY_ACCESS',
  //             latestVersionId: '4',
  //             updatedAt: 2023-09-27T19:46:21.824Z
  //      }
  // }
  return response;
};
```

Copie um conjunto de imagens sem um destino.

```
  try {
    await copyImageSet(
      "12345678901234567890123456789012",
      "12345678901234567890123456789012",
      "1"
    );
  } catch (err) {
    console.error(err);
  }
```

Copie um conjunto de imagens com um destino.

```
  try {
    await copyImageSet(
      "12345678901234567890123456789012",
      "12345678901234567890123456789012",
      "4",
```

```
      "12345678901234567890123456789012",
      "1"
    );
  } catch (err) {
    console.error(err);
  }
```

- Para obter detalhes da API, consulte CopyImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um datastore

O exemplo de código a seguir mostra como criar um armazenamento HealthImaging de dados.

SDK para JavaScript (v3)

```
import { CreateDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreName - The name of the data store to create.
 */
export const createDatastore = async (datastoreName = "DATASTORE_NAME") => {
  const response = await medicalImagingClient.send(
    new CreateDatastoreCommand({ datastoreName: datastoreName })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: 'a71cd65f-2382-49bf-b682-f9209d8d399b',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
```

```
  //    },
  //    datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //    datastoreStatus: 'CREATING'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte CreateDatastorea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um datastore

O exemplo de código a seguir mostra como excluir um armazenamento HealthImaging de dados.

SDK para JavaScript (v3)

```
import { DeleteDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store to delete.
 */
export const deleteDatastore = async (datastoreId = "DATASTORE_ID") => {
  const response = await medicalImagingClient.send(
    new DeleteDatastoreCommand({ datastoreId })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //           httpStatusCode: 200,
  //           requestId: 'f5beb409-678d-48c9-9173-9a001ee1ebb1',
  //           extendedRequestId: undefined,
  //           cfId: undefined,
  //           attempts: 1,
  //           totalRetryDelay: 0
```

```
  //        },
  //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //     datastoreStatus: 'DELETING'
  // }

  return response;
};
```

- Para obter detalhes da API, consulte DeleteDatastoreа Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um conjunto de imagens

O exemplo de código a seguir mostra como excluir um conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

```
import { DeleteImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The data store ID.
 * @param {string} imageSetId - The image set ID.
 */
export const deleteImageSet = async (
  datastoreId = "xxxxxxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxxxxxx"
) => {
  const response = await medicalImagingClient.send(
    new DeleteImageSetCommand({
      datastoreId: datastoreId,
      imageSetId: imageSetId,
    })
  );
  console.log(response);
```

```
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '6267bbd2-eaa5-4a50-8ee8-8fddf535cf73',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     datastoreId: 'xxxxxxxxxxxxxxxx',
  //     imageSetId: 'xxxxxxxxxxxxxxx',
  //     imageSetState: 'LOCKED',
  //     imageSetWorkflowStatus: 'DELETING'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter um quadro de imagem

O exemplo de código a seguir mostra como obter um quadro de imagem.

SDK para JavaScript (v3)

```
import { GetImageFrameCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} imageFrameFileName - The name of the file for the HTJ2K-encoded
 image frame.
 * @param {string} datastoreID - The data store's ID.
 * @param {string} imageSetID - The image set's ID.
 * @param {string} imageFrameID - The image frame's ID.
```

```
 */
export const getImageFrame = async (
  imageFrameFileName = "image.jph",
  datastoreID = "DATASTORE_ID",
  imageSetID = "IMAGE_SET_ID",
  imageFrameID = "IMAGE_FRAME_ID"
) => {
  const response = await medicalImagingClient.send(
    new GetImageFrameCommand({
      datastoreId: datastoreID,
      imageSetId: imageSetID,
      imageFrameInformation: { imageFrameId: imageFrameID },
    })
  );
  const buffer = await response.imageFrameBlob.transformToByteArray();
  writeFileSync(imageFrameFileName, buffer);

  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'e4ab42a5-25a3-4377-873f-374ecf4380e1',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     contentType: 'application/octet-stream',
  //     imageFrameBlob: <ref *1> IncomingMessage {}
  // }
  return response;
};
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do datastore

O exemplo de código a seguir mostra como obter propriedades do armazenamento de HealthImaging dados.

SDK para JavaScript (v3)

```
import { GetDatastoreCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreID - The ID of the data store.
 */
export const getDatastore = async (datastoreID = "DATASTORE_ID") => {
  const response = await medicalImagingClient.send(
    new GetDatastoreCommand({ datastoreId: datastoreID })
  );
  console.log(response);
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: '55ea7d2e-222c-4a6a-871e-4f591f40cadb',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //    },
  //   datastoreProperties: {
  //        createdAt: 2023-08-04T18:50:36.239Z,
  //         datastoreArn: 'arn:aws:medical-imaging:us-east-1:xxxxxxxxx:datastore/
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //         datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //         datastoreName: 'my_datastore',
  //         datastoreStatus: 'ACTIVE',
  //         updatedAt: 2023-08-04T18:50:36.239Z
  //   }
  // }
  return response["datastoreProperties"];
};
```

- Para obter detalhes da API, consulte GetDatastorea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do conjunto de imagens

O exemplo de código a seguir mostra como obter as propriedades do conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

```
import { GetImageSetCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imageSetId - The ID of the image set.
 * @param {string} imageSetVersion - The optional version of the image set.
 *
 */
export const getImageSet = async (
  datastoreId = "xxxxxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxxxxx",
  imageSetVersion = ""
) => {
  let params = { datastoreId: datastoreId, imageSetId: imageSetId };
  if (imageSetVersion !== "") {
    params.imageSetVersion = imageSetVersion;
  }
  const response = await medicalImagingClient.send(
    new GetImageSetCommand(params)
  );
  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '0615c161-410d-4d06-9d8c-6e1241bb0a5a',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
```

```
  //         totalRetryDelay: 0
  // },
  //     createdAt: 2023-09-22T14:49:26.427Z,
  //     datastoreId: 'xxxxxxxxxxxxxxx',
  //     imageSetArn: 'arn:aws:medical-imaging:us-east-1:xxxxxxxxxx:datastore/
xxxxxxxxxxxxxxxxxxxx/imageset/xxxxxxxxxxxxxxxxxxx',
  //     imageSetId: 'xxxxxxxxxxxxxxx',
  //     imageSetState: 'ACTIVE',
  //     imageSetWorkflowStatus: 'CREATED',
  //     updatedAt: 2023-09-22T14:49:26.427Z,
  //     versionId: '1'
  // }

  return response;
};
```

- Para obter detalhes da API, consulte GetImageSeta Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do trabalho de importação

O exemplo de código a seguir mostra como obter as propriedades do trabalho de importação.

SDK para JavaScript (v3)

```
import { GetDICOMImportJobCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} jobId - The ID of the import job.
 */
export const getDICOMImportJob = async (
  datastoreId = "xxxxxxxxxxxxxxxxxxxx",
```

```
  jobId = "xxxxxxxxxxxxxxxxxxxx"
) => {
  const response = await medicalImagingClient.send(
    new GetDICOMImportJobCommand({ datastoreId: datastoreId, jobId: jobId })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: 'a2637936-78ea-44e7-98b8-7a87d95dfaee',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     jobProperties: {
  //         dataAccessRoleArn: 'arn:aws:iam::xxxxxxxxxxxx:role/dicom_import',
  //             datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxx',
  //             endedAt: 2023-09-19T17:29:21.753Z,
  //             inputS3Uri: 's3://healthimaging-source/CTStudy/',
  //             jobId: ''xxxxxxxxxxxxxxxxxxxxxxxx'',
  //             jobName: 'job_1',
  //             jobStatus: 'COMPLETED',
  //             outputS3Uri: 's3://health-imaging-dest/
ouput_ct/'xxxxxxxxxxxxxxxxxxxxxxxx'-DicomImport-'xxxxxxxxxxxxxxxxxxxxxxxx'/',
  //             submittedAt: 2023-09-19T17:27:25.143Z
  //     }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter metadados para um conjunto de imagem

O exemplo de código a seguir mostra como obter metadados para um conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

Função de utilitário para obter metadados do conjunto de imagens.

```
import { GetImageSetMetadataCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";
import { writeFileSync } from "fs";

/**
 * @param {string} metadataFileName - The name of the file for the gzipped metadata.
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imagesetId - The ID of the image set.
 * @param {string} versionID - The optional version ID of the image set.
 */
export const getImageSetMetadata = async (
  metadataFileName = "metadata.json.gzip",
  datastoreId = "xxxxxxxxxxxxxx",
  imagesetId = "xxxxxxxxxxxxxx",
  versionID = ""
) => {
  const params = { datastoreId: datastoreId, imageSetId: imagesetId };

  if (versionID) {
    params.versionID = versionID;
  }

  const response = await medicalImagingClient.send(
    new GetImageSetMetadataCommand(params)
  );
  const buffer = await response.imageSetMetadataBlob.transformToByteArray();
  writeFileSync(metadataFileName, buffer);

  console.log(response);
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '5219b274-30ff-4986-8cab-48753de3a599',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
```

```
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     contentType: 'application/json',
  //     contentEncoding: 'gzip',
  //     imageSetMetadataBlob: <ref *1> IncomingMessage {}
  // }

  return response;
};
```

Obtenha metadados do conjunto de imagens sem versão.

```
  try {
    await getImageSetMetadata(
      "metadata.json.gzip",
      "12345678901234567890123456789012",
      "12345678901234567890123456789012"
    );
  } catch (err) {
    console.log("Error", err);
  }
```

Obtenha metadados do conjunto de imagens com versão.

```
  try {
    await getImageSetMetadata(
      "metadata2.json.gzip",
      "12345678901234567890123456789012",
      "12345678901234567890123456789012",
      "1"
    );
  } catch (err) {
    console.log("Error", err);
  }
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importar dados em massa para um datastore

O exemplo de código a seguir mostra como importar dados em massa para um armazenamento HealthImaging de dados.

SDK para JavaScript (v3)

```
import { StartDICOMImportJobCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} jobName - The name of the import job.
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} dataAccessRoleArn - The Amazon Resource Name (ARN) of the role
 that grants permission.
 * @param {string} inputS3Uri - The URI of the S3 bucket containing the input files.
 * @param {string} outputS3Uri - The URI of the S3 bucket where the output files are
 stored.
 */
export const startDicomImportJob = async (
  jobName = "test-1",
  datastoreId = "12345678901234567890123456789012",
  dataAccessRoleArn = "arn:aws:iam::xxxxxxxxxxxx:role/ImportJobDataAccessRole",
  inputS3Uri = "s3://medical-imaging-dicom-input/dicom_input/",
  outputS3Uri = "s3://medical-imaging-output/job_output/"
) => {
  const response = await medicalImagingClient.send(
    new StartDICOMImportJobCommand({
      jobName: jobName,
      datastoreId: datastoreId,
      dataAccessRoleArn: dataAccessRoleArn,
      inputS3Uri: inputS3Uri,
      outputS3Uri: outputS3Uri,
    })
  );
  console.log(response);
```

```
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '6e81d191-d46b-4e48-a08a-cdcc7e11eb79',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //     jobId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //     jobStatus: 'SUBMITTED',
  //     submittedAt: 2023-09-22T14:48:45.767Z
  // }
  return response;
};
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for JavaScript Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar datastores

O exemplo de código a seguir mostra como listar armazenamentos HealthImaging de dados.

SDK para JavaScript (v3)

```
import { paginateListDatastores } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

export const listDatastores = async () => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };
```

```
  const commandParams = {};
  const paginator = paginateListDatastores(paginatorConfig, commandParams);

  /**
   * @type {import("@aws-sdk/client-medical-imaging").DatastoreSummary[]}
   */
  const datastoreSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    datastoreSummaries.push(...page["datastoreSummaries"]);
    console.log(page);
  }
  // {
  //   '$metadata': {
  //       httpStatusCode: 200,
  //       requestId: '6aa99231-d9c2-4716-a46e-edb830116fa3',
  //       extendedRequestId: undefined,
  //       cfId: undefined,
  //       attempts: 1,
  //       totalRetryDelay: 0
  //   },
  //   datastoreSummaries: [
  //     {
  //       createdAt: 2023-08-04T18:49:54.429Z,
  //       datastoreArn: 'arn:aws:medical-imaging:us-east-1:xxxxxxxxx:datastore/
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //       datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
  //       datastoreName: 'my_datastore',
  //       datastoreStatus: 'ACTIVE',
  //       updatedAt: 2023-08-04T18:49:54.429Z
  //     }
  //     ...
  //   ]
  // }

  return datastoreSummaries;
};
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar versões do conjunto de imagens

O exemplo de código a seguir mostra como listar as versões do conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

```
import { paginateListImageSetVersions } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 * @param {string} imageSetId - The ID of the image set.
 */
export const listImageSetVersions = async (
  datastoreId = "xxxxxxxxxxxx",
  imageSetId = "xxxxxxxxxxxx"
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };

  const commandParams = { datastoreId, imageSetId };
  const paginator = paginateListImageSetVersions(
    paginatorConfig,
    commandParams
  );

  let imageSetPropertiesList = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    imageSetPropertiesList.push(...page["imageSetPropertiesList"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
```

```
  //         httpStatusCode: 200,
  //         requestId: '74590b37-a002-4827-83f2-3c590279c742',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     imageSetPropertiesList: [
  //         {
  //             ImageSetWorkflowStatus: 'CREATED',
  //             createdAt: 2023-09-22T14:49:26.427Z,
  //             imageSetId: 'xxxxxxxxxxxxxxxxxxxxxx',
  //             imageSetState: 'ACTIVE',
  //             versionId: '1'
  //         }]
  // }
  return imageSetPropertiesList;
};
```

- Para obter detalhes da API, consulte ListImageSetVersionsa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar trabalhos de importação para um datastore

O exemplo de código a seguir mostra como listar trabalhos de importação para um armazenamento HealthImaging de dados.

SDK para JavaScript (v3)

```
import { paginateListDICOMImportJobs } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the data store.
 */
```

```
export const listDICOMImportJobs = async (
  datastoreId = "xxxxxxxxxxxxxxxxxx"
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };

  const commandParams = { datastoreId: datastoreId };
  const paginator = paginateListDICOMImportJobs(paginatorConfig, commandParams);

  let jobSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    jobSummaries.push(...page["jobSummaries"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
  //     httpStatusCode: 200,
  //         requestId: '3c20c66e-0797-446a-a1d8-91b742fd15a0',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  // },
  //     jobSummaries: [
  //         {
  //             dataAccessRoleArn: 'arn:aws:iam::xxxxxxxxxxxx:role/dicom_import',
  //             datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxx',
  //             endedAt: 2023-09-22T14:49:51.351Z,
  //             jobId: 'xxxxxxxxxxxxxxxxxxxxxxxxx',
  //             jobName: 'test-1',
  //             jobStatus: 'COMPLETED',
  //             submittedAt: 2023-09-22T14:48:45.767Z
  // }
  // ]}

  return jobSummaries;
};
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar as tags para um recurso

O exemplo de código a seguir mostra como listar tags para um HealthImaging recurso.

SDK para JavaScript (v3)

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
  // }

  return response;
```

```
};
```

- Para obter detalhes da API, consulte ListTagsForResourcea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover tag de um recurso

O exemplo de código a seguir mostra como remover uma tag de um HealthImaging recurso.

SDK para JavaScript (v3)

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tagKeys = []
) => {
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
```

```
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte UntagResourcea Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Pesquisar conjuntos de imagens

O exemplo de código a seguir mostra como pesquisar conjuntos de HealthImaging imagens.

SDK para JavaScript (v3)

A função de utilitário para pesquisar conjuntos de imagens.

```
import { paginateSearchImageSets } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The data store's ID.
 * @param { import('@aws-sdk/client-medical-imaging').SearchFilter[] } filters - The
 search criteria filters.
 */
export const searchImageSets = async (
  datastoreId = "xxxxxxxx",
  filters = []
) => {
  const paginatorConfig = {
    client: medicalImagingClient,
    pageSize: 50,
  };
```

```
  const commandParams = {
    datastoreId: datastoreId,
    searchCriteria: {
      filters,
    },
  };

  const paginator = paginateSearchImageSets(paginatorConfig, commandParams);

  const imageSetsMetadataSummaries = [];
  for await (const page of paginator) {
    // Each page contains a list of `jobSummaries`. The list is truncated if is
 larger than `pageSize`.
    imageSetsMetadataSummaries.push(...page["imageSetsMetadataSummaries"]);
    console.log(page);
  }
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: 'f009ea9c-84ca-4749-b5b6-7164f00a5ada',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     imageSetsMetadataSummaries: [
  //         {
  //             DICOMTags: [Object],
  //             createdAt: "2023-09-19T16:59:40.551Z",
  //             imageSetId: '7f75e1b5c0f40eac2b24cf712f485f50',
  //             updatedAt: "2023-09-19T16:59:40.551Z",
  //             version: 1
  //         }]
  // }

  return imageSetsMetadataSummaries;
};
```

Caso de uso nº 1: operador EQUAL.

```
  const datastoreId = "12345678901234567890123456789012";
```

```
try {
  const filters = [
    {
      values: [{ DICOMPatientId: "9227465" }],
      operator: "EQUAL",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
}
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
const datastoreId = "12345678901234567890123456789012";

try {
  const filters = [
    {
      values: [
        {
          DICOMStudyDateAndTime: {
            DICOMStudyDate: "19900101",
            DICOMStudyTime: "000000",
          },
        },
        {
          DICOMStudyDateAndTime: {
            DICOMStudyDate: "20230901",
            DICOMStudyTime: "000000",
          },
        },
      ],
      operator: "BETWEEN",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
}
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
const datastoreId = "12345678901234567890123456789012";

try {
  const filters = [
    {
      values: [
        { createdAt: new Date("1985-04-12T23:20:50.52Z") },
        { createdAt: new Date("2023-09-12T23:20:50.52Z") },
      ],
      operator: "BETWEEN",
    },
  ];

  await searchImageSets(datastoreId, filters);
} catch (err) {
  console.error(err);
}
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar metadados do conjunto de imagens

O exemplo de código a seguir mostra como atualizar os metadados do conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

```
import {UpdateImageSetMetadataCommand} from "@aws-sdk/client-medical-imaging";
```

```
import {medicalImagingClient} from "../libs/medicalImagingClient.js";

/**
 * @param {string} datastoreId - The ID of the HealthImaging data store.
 * @param {string} imageSetId - The ID of the HealthImaging image set.
 * @param {string} latestVersionId - The ID of the HealthImaging image set version.
 * @param {{}} updateMetadata - The metadata to update.
 */
export const updateImageSetMetadata = async (datastoreId = "xxxxxxxxxx",
                                             imageSetId = "xxxxxxxxxx",
                                             latestVersionId = "1",
                                             updateMetadata = '{}') => {
    const response = await medicalImagingClient.send(
        new UpdateImageSetMetadataCommand({
            datastoreId: datastoreId,
            imageSetId: imageSetId,
            latestVersionId: latestVersionId,
            updateImageSetMetadataUpdates: updateMetadata
        })
    );
    console.log(response);
    // {
    //     '$metadata': {
    //     httpStatusCode: 200,
    //         requestId: '7966e869-e311-4bff-92ec-56a61d3003ea',
    //         extendedRequestId: undefined,
    //         cfId: undefined,
    //         attempts: 1,
    //         totalRetryDelay: 0
    // },
    //     createdAt: 2023-09-22T14:49:26.427Z,
    //     datastoreId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
    //     imageSetId: 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx',
    //     imageSetState: 'LOCKED',
    //     imageSetWorkflowStatus: 'UPDATING',
    //     latestVersionId: '4',
    //     updatedAt: 2023-09-27T19:41:43.494Z
    // }
    return response;
};
```

Codifique os metadados.

```
    const updatableAttributes =
JSON.stringify({
  "SchemaVersion": 1.1,
  "Patient": {
    "DICOM": {
      "PatientName": "Garcia^Gloria"
    }
  }
})

    const updateMetadata = {
        "DICOMUpdates": {
            "updatableAttributes":
                new TextEncoder().encode(updatableAttributes)
        }
    };

    await updateImageSetMetadata("12345678901234567890123456789012",
 "12345678901234567890123456789012",
        "1", updateMetadata);
```

- Para obter detalhes da API, consulte UpdateImageSetMetadataa Referência AWS SDK for JavaScript da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cenários

Marcar um datastore

O exemplo de código a seguir mostra como marcar um armazenamento HealthImaging de dados.

SDK para JavaScript (v3)

Para marcar um armazenamento de dados

```
  try {
```

```
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const tags = {
      Deployment: "Development",
    };
    await tagResource(datastoreArn, tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para marcar um recurso.

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tags = {}
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }
```

```
  return response;
};
```

Para listar tags para um armazenamento de dados

```
  try {
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const { tags } = await listTagsForResource(datastoreArn);
    console.log(tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para listar as tags de um recurso.

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
```

```
  // }

  return response;
};
```

Para desmarcar um armazenamento de dados

```
  try {
    const datastoreArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";
    const keys = ["Deployment"];
    await untagResource(datastoreArn, keys);
  } catch (e) {
    console.log(e);
  }
```

A função de utilitário para desmarcar um recurso.

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tagKeys = []
) => {
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
```

```
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Marcar um conjunto de imagens

O exemplo de código a seguir mostra como marcar um conjunto de HealthImaging imagens.

SDK para JavaScript (v3)

Para marcar um conjunto de imagens

```
  try {
    const imagesetArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const tags = {
      Deployment: "Development",
    };
    await tagResource(imagesetArn, tags);
  } catch (e) {
    console.log(e);
```

```
  }
```

A função utilitária para marcar um recurso.

```
import { TagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {Record<string,string>} tags - The tags to add to the resource as JSON.
 *                      - For example: {"Deployment" : "Development"}
 */
export const tagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tags = {}
) => {
  const response = await medicalImagingClient.send(
    new TagResourceCommand({ resourceArn: resourceArn, tags: tags })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
};
```

Para listar tags para um conjunto de imagens

```
  try {
    const imagesetArn =
```

```
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const { tags } = await listTagsForResource(imagesetArn);
    console.log(tags);
  } catch (e) {
    console.log(e);
  }
```

A função utilitária para listar as tags de um recurso.

```
import { ListTagsForResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 */
export const listTagsForResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:abc:datastore/def/imageset/ghi"
) => {
  const response = await medicalImagingClient.send(
    new ListTagsForResourceCommand({ resourceArn: resourceArn })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //         httpStatusCode: 200,
  //         requestId: '008fc6d3-abec-4870-a155-20fa3631e645',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //     },
  //     tags: { Deployment: 'Development' }
  // }

  return response;
};
```

Para desmarcar um conjunto de imagens

```
  try {
    const imagesetArn =
      "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
    const keys = ["Deployment"];
    await untagResource(imagesetArn, keys);
  } catch (e) {
    console.log(e);
  }
```

A função de utilitário para desmarcar um recurso.

```
import { UntagResourceCommand } from "@aws-sdk/client-medical-imaging";
import { medicalImagingClient } from "../libs/medicalImagingClient.js";

/**
 * @param {string} resourceArn - The Amazon Resource Name (ARN) for the data store
 or image set.
 * @param {string[]} tagKeys - The keys of the tags to remove.
 */
export const untagResource = async (
  resourceArn = "arn:aws:medical-imaging:us-east-1:xxxxxx:datastore/xxxxx/imageset/
xxx",
  tagKeys = []
) => {
  const response = await medicalImagingClient.send(
    new UntagResourceCommand({ resourceArn: resourceArn, tagKeys: tagKeys })
  );
  console.log(response);
  // {
  //     '$metadata': {
  //        httpStatusCode: 204,
  //         requestId: '8a6de9a3-ec8e-47ef-8643-473518b19d45',
  //         extendedRequestId: undefined,
  //         cfId: undefined,
  //         attempts: 1,
  //         totalRetryDelay: 0
  //    }
  // }

  return response;
```

```
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos de IAM usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { IAMClient, paginateListPolicies } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listLocalPolicies = async () => {
  /**
   * In v3, the clients expose paginateOperationName APIs that are written using
 async generators so that you can use async iterators in a for await..of loop.
   * https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/index.html#paginators
   */
  const paginator = paginateListPolicies(
    { client, pageSize: 10 },
    // List only customer managed policies.
    { Scope: "Local" },
  );

  console.log("IAM policies defined in your account:");
  let policyCount = 0;
  for await (const page of paginator) {
    if (page.Policies) {
      page.Policies.forEach((p) => {
        console.log(`${p.PolicyName}`);
        policyCount++;
      });
    }
  }
  console.log(`Found ${policyCount} policies.`);
};
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Anexe a política.

```
import { AttachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const attachRolePolicy = (policyArn, roleName) => {
  const command = new AttachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        console.log(
          "AmazonDynamoDBFullAccess is already attached to this role."
        );
        process.exit();
      }
    });
    var params = {
      PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
      RoleName: process.argv[2],
    };
    iam.attachRolePolicy(params, function (err, data) {
      if (err) {
        console.log("Unable to attach policy to role", err);
      } else {
        console.log("Role attached successfully");
```

```
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for JavaScript da API.

Anexar uma política em linha a um perfil

Os exemplos de código a seguir mostram como anexar uma política em linha a um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { PutRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const examplePolicyDocument = JSON.stringify({
  Version: "2012-10-17",
  Statement: [
    {
      Sid: "VisualEditor0",
      Effect: "Allow",
      Action: [
        "s3:ListBucketMultipartUploads",
        "s3:ListBucketVersions",
        "s3:ListBucket",
        "s3:ListMultipartUploadParts",
      ],
      Resource: "arn:aws:s3:::some-test-bucket",
    },
    {
      Sid: "VisualEditor1",
      Effect: "Allow",
```

```
      Action: [
        "s3:ListStorageLensConfigurations",
        "s3:ListAccessPointsForObjectLambda",
        "s3:ListAllMyBuckets",
        "s3:ListAccessPoints",
        "s3:ListJobs",
        "s3:ListMultiRegionAccessPoints",
      ],
      Resource: "*",
    },
  ],
});

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 * @param {string} policyName
 * @param {string} policyDocument
 */
export const putRolePolicy = async (roleName, policyName, policyDocument) => {
  const command = new PutRolePolicyCommand({
    RoleName: roleName,
    PolicyName: policyName,
    PolicyDocument: policyDocument,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte PutRolePolicya Referência AWS SDK for JavaScript da API.

Criar um provedor SAML

O exemplo de código a seguir mostra como criar um provedor SAML do AWS Identity and Access Management (IAM).

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateSAMLProviderCommand, IAMClient } from "@aws-sdk/client-iam";
import { readFileSync } from "fs";
import * as path from "path";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";

const client = new IAMClient({});

/**
 * This sample document was generated using Auth0.
 * For more information on generating this document,
 see https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_providers_create_saml.html#samlstep1.
 */
const sampleMetadataDocument = readFileSync(
  path.join(
    dirnameFromMetaUrl(import.meta.url),
    "../../../../resources/sample_files/sample_saml_metadata.xml",
  ),
);

/**
 *
 * @param {*} providerName
 * @returns
 */
export const createSAMLProvider = async (providerName) => {
  const command = new CreateSAMLProviderCommand({
    Name: providerName,
    SAMLMetadataDocument: sampleMetadataDocument.toString(),
  });

  const response = await client.send(command);
  console.log(response);
  return response;
```

```
};
```

- Para obter detalhes da API, consulte CreateSAMLProvider na Referência da API do AWS SDK for JavaScript.

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateGroupCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} groupName
 */
export const createGroup = async (groupName) => {
  const command = new CreateGroupCommand({ GroupName: groupName });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte CreateGroupa Referência AWS SDK for JavaScript da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a política do

```
import { CreatePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyName
 */
export const createPolicy = (policyName) => {
  const command = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: "*",
          Resource: "*",
        },
      ],
    }),
    PolicyName: policyName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var myManagedPolicy = {
  Version: "2012-10-17",
  Statement: [
    {
      Effect: "Allow",
      Action: "logs:CreateLogGroup",
      Resource: "RESOURCE_ARN",
    },
    {
      Effect: "Allow",
      Action: [
        "dynamodb:DeleteItem",
        "dynamodb:GetItem",
        "dynamodb:PutItem",
        "dynamodb:Scan",
        "dynamodb:UpdateItem",
      ],
      Resource: "RESOURCE_ARN",
    },
  ],
};

var params = {
  PolicyDocument: JSON.stringify(myManagedPolicy),
```

```
  PolicyName: "myDynamoDBPolicy",
};

iam.createPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for JavaScript da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a função.

```
import { CreateRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const createRole = (roleName) => {
  const command = new CreateRoleCommand({
    AssumeRolePolicyDocument: JSON.stringify({
```

```
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Principal: {
            Service: "lambda.amazonaws.com",
          },
          Action: "sts:AssumeRole",
        },
      ],
    }),
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for JavaScript da API.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma função vinculada ao serviço.

```
import { CreateServiceLinkedRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} serviceName
 */
```

```
export const createServiceLinkedRole = async (serviceName) => {
  const command = new CreateServiceLinkedRoleCommand({
    // For a list of AWS services that support service-linked roles,
    // see https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_aws-services-
that-work-with-iam.html.
    //
    // For a list of AWS service endpoints, see https://docs.aws.amazon.com/general/
latest/gr/aws-service-information.html.
    AWSServiceName: serviceName,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for JavaScript da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o usuário.

```
import { CreateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} name
 */
export const createUser = (name) => {
  const command = new CreateUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    iam.createUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
```

```
      } else {
        console.log("Success", data);
      }
    });
  } else {
    console.log(
      "User " + process.argv[2] + " already exists",
      data.User.UserId
    );
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for JavaScript da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a chave de acesso.

```
import { CreateAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 *
 * @param {string} userName
 */
export const createAccessKey = (userName) => {
  const command = new CreateAccessKeyCommand({ UserName: userName });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccessKey({ UserName: "IAM_USER_NAME" }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.AccessKey);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for JavaScript da API.

Criar um alias para uma conta

O exemplo de código a seguir mostra como criar um alias para uma conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o alias da conta.

```
import { CreateAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} alias - A unique name for the account alias.
 * @returns
 */
export const createAccountAlias = (alias) => {
  const command = new CreateAccountAliasCommand({
    AccountAlias: alias,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.createAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for JavaScript da API.

criar um perfil de instância

O exemplo de código a seguir mostra como criar um perfil de instância do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
```

- Para obter detalhes da API, consulte CreateInstanceProfilea Referência AWS SDK for JavaScript da API.

Excluir um provedor SAML

O exemplo de código a seguir mostra como excluir um provedor SAML do AWS Identity and Access Management (IAM).

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteSAMLProviderCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} providerArn
 * @returns
 */
export const deleteSAMLProvider = async (providerArn) => {
  const command = new DeleteSAMLProviderCommand({
    SAMLProviderArn: providerArn,
  });
```

```
  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteSAMLProvider na Referência da API do AWS SDK for JavaScript.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteGroupCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} groupName
 */
export const deleteGroup = async (groupName) => {
  const command = new DeleteGroupCommand({
    GroupName: groupName,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte DeleteGroupa Referência AWS SDK for JavaScript da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a política.

```
import { DeletePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 */
export const deletePolicy = (policyArn) => {
  const command = new DeletePolicyCommand({ PolicyArn: policyArn });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for JavaScript da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a função.

```
import { DeleteRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const deleteRole = (roleName) => {
  const command = new DeleteRoleCommand({ RoleName: roleName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for JavaScript da API.

Excluir uma política de perfil

O exemplo de código a seguir mostra como excluir uma política de perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});
```

```
/**
 *
 * @param {string} roleName
 * @param {string} policyName
 */
export const deleteRolePolicy = (roleName, policyName) => {
  const command = new DeleteRolePolicyCommand({
    RoleName: roleName,
    PolicyName: policyName,
  });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteRolePolicya Referência AWS SDK for JavaScript da API.

Excluir um certificado do servidor

Os exemplos de código a seguir mostram como excluir certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um certificado de servidor.

```
import { DeleteServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
 */
export const deleteServerCertificate = (certName) => {
  const command = new DeleteServerCertificateCommand({
```

```
    ServerCertificateName: certName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for JavaScript da API.

Excluir um perfil vinculado ao serviço

O exemplo de código a seguir mostra como excluir um perfil vinculado ao serviço do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteServiceLinkedRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} roleName
 */
export const deleteServiceLinkedRole = (roleName) => {
  const command = new DeleteServiceLinkedRoleCommand({ RoleName: roleName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for JavaScript da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o usuário.

```
import { DeleteUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} name
 */
export const deleteUser = (name) => {
  const command = new DeleteUserCommand({ UserName: name });
  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
};

iam.getUser(params, function (err, data) {
  if (err && err.code === "NoSuchEntity") {
    console.log("User " + process.argv[2] + " does not exist.");
  } else {
    iam.deleteUser(params, function (err, data) {
      if (err) {
        console.log("Error", err);
      } else {
        console.log("Success", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for JavaScript da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a chave de acesso.

```
import { DeleteAccessKeyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
export const deleteAccessKey = (userName, accessKeyId) => {
  const command = new DeleteAccessKeyCommand({
    AccessKeyId: accessKeyId,
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  UserName: "USER_NAME",
};

iam.deleteAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for JavaScript da API.

Excluir um alias de conta

O exemplo de código a seguir mostra como excluir um alias da conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o alias da conta.

```
import { DeleteAccountAliasCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 *
 * @param {string} alias
 */
export const deleteAccountAlias = (alias) => {
  const command = new DeleteAccountAliasCommand({ AccountAlias: alias });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.deleteAccountAlias({ AccountAlias: process.argv[2] }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for JavaScript da API.

Excluir um perfil de instância

O exemplo de código a seguir mostra como excluir um perfil de instância do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const client = new IAMClient({});
await client.send(
  new DeleteInstanceProfileCommand({
    InstanceProfileName: NAMES.instanceProfileName,
  }),
);
```

- Para obter detalhes da API, consulte DeleteInstanceProfilea Referência AWS SDK for JavaScript da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desanexe a política.

```
import { DetachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const detachRolePolicy = (policyArn, roleName) => {
  const command = new DetachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });
```

```
var paramsRoleList = {
  RoleName: process.argv[2],
};

iam.listAttachedRolePolicies(paramsRoleList, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    var myRolePolicies = data.AttachedPolicies;
    myRolePolicies.forEach(function (val, index, array) {
      if (myRolePolicies[index].PolicyName === "AmazonDynamoDBFullAccess") {
        var params = {
          PolicyArn: "arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess",
          RoleName: process.argv[2],
        };
        iam.detachRolePolicy(params, function (err, data) {
          if (err) {
            console.log("Unable to detach policy from role", err);
          } else {
            console.log("Policy detached from role successfully");
            process.exit();
          }
        });
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for JavaScript da API.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política.

```
import { GetPolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 */
export const getPolicy = (policyArn) => {
  const command = new GetPolicyCommand({
    PolicyArn: policyArn,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
```

```
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  PolicyArn: "arn:aws:iam::aws:policy/AWSLambdaExecute",
};

iam.getPolicy(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Policy.Description);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for JavaScript da API.

Obter um perfil

O exemplo de código a seguir mostra como obter um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a função.

```
import { GetRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
```

```
 *
 * @param {string} roleName
 */
export const getRole = (roleName) => {
  const command = new GetRoleCommand({
    RoleName: roleName,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for JavaScript da API.

Obter um certificado do servidor

O exemplo de código a seguir mostram como obter um certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um certificado do servidor.

```
import { GetServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} certName
 * @returns
 */
export const getServerCertificate = async (certName) => {
  const command = new GetServerCertificateCommand({
    ServerCertificateName: certName,
  });
```

```
  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getServerCertificate(
  { ServerCertificateName: "CERTIFICATE_NAME" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetServerCertificatea Referência AWS SDK for JavaScript da API.

Obter o status de exclusão do perfil vinculado ao serviço

Os exemplos de código a seguir mostram como obter o status de exclusão de um perfil vinculado ao serviço do AWS Identity and Access Management (IAM).

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  GetServiceLinkedRoleDeletionStatusCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} deletionTaskId
 */
export const getServiceLinkedRoleDeletionStatus = (deletionTaskId) => {
  const command = new GetServiceLinkedRoleDeletionStatusCommand({
    DeletionTaskId: deletionTaskId,
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetServiceLinkedRoleDeletionStatusa Referência AWS SDK for JavaScript da API.

Obter dados sobre a última utilização de uma chave de acesso

O exemplo de código a seguir mostra como obter dados sobre a última utilização de uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a chave de acesso.

```
import { GetAccessKeyLastUsedCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} accessKeyId
 */
export const getAccessKeyLastUsed = async (accessKeyId) => {
  const command = new GetAccessKeyLastUsedCommand({
    AccessKeyId: accessKeyId,
  });

  const response = await client.send(command);

  if (response.AccessKeyLastUsed?.LastUsedDate) {
    console.log(`
    ${accessKeyId} was last used by ${response.UserName} via
    the ${response.AccessKeyLastUsed.ServiceName} service on
    ${response.AccessKeyLastUsed.LastUsedDate.toISOString()}
    `);
  }

  return response;
```

```
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUseda Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.getAccessKeyLastUsed(
  { AccessKeyId: "ACCESS_KEY_ID" },
  function (err, data) {
    if (err) {
      console.log("Error", err);
    } else {
      console.log("Success", data.AccessKeyLastUsed);
    }
  }
);
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetAccessKeyLastUseda Referência AWS SDK for JavaScript da API.

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de senha da conta.

```
import {
  GetAccountPasswordPolicyCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const getAccountPasswordPolicy = async () => {
  const command = new GetAccountPasswordPolicyCommand({});

  const response = await client.send(command);
  console.log(response.PasswordPolicy);
  return response;
};
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for JavaScript da API.

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os provedores SAML.

```
import { ListSAMLProvidersCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listSamlProviders = async () => {
  const command = new ListSAMLProvidersCommand({});

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for JavaScript.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as chaves de acesso.

```
import { ListAccessKeysCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 * @param {string} userName
 */
export async function* listAccessKeys(userName) {
  const command = new ListAccessKeysCommand({
    MaxItems: 5,
    UserName: userName,
  });

  /**
   * @type {import("@aws-sdk/client-iam").ListAccessKeysCommandOutput | undefined}
   */
  let response = await client.send(command);

  while (response?.AccessKeyMetadata?.length) {
    for (const key of response.AccessKeyMetadata) {
      yield key;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccessKeysCommand({
          Marker: response.Marker,
        }),
```

```
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 5,
  UserName: "IAM_USER_NAME",
};

iam.listAccessKeys(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for JavaScript da API.

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de conta do IAM.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os aliases de conta.

```
import { ListAccountAliasesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 */
export async function* listAccountAliases() {
  const command = new ListAccountAliasesCommand({ MaxItems: 5 });

  let response = await client.send(command);

  while (response.AccountAliases?.length) {
    for (const alias of response.AccountAliases) {
      yield alias;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAccountAliasesCommand({
```

```
          Marker: response.Marker,
          MaxItems: 5,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listAccountAliases({ MaxItems: 10 }, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for JavaScript da API.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os grupos.

```
import { ListGroupsCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 */
export async function* listGroups() {
  const command = new ListGroupsCommand({
    MaxItems: 10,
  });

  let response = await client.send(command);

  while (response.Groups?.length) {
    for (const group of response.Groups) {
      yield group;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListGroupsCommand({
```

```
          Marker: response.Marker,
          MaxItems: 10,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for JavaScript da API.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as políticas.

```
import { ListRolePoliciesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 * @param {string} roleName
 */
export async function* listRolePolicies(roleName) {
  const command = new ListRolePoliciesCommand({
    RoleName: roleName,
```

```
    MaxItems: 10,
  });

  let response = await client.send(command);

  while (response.PolicyNames?.length) {
    for (const policyName of response.PolicyNames) {
      yield policyName;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListRolePoliciesCommand({
          RoleName: roleName,
          MaxItems: 10,
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for JavaScript da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as políticas.

```
import { ListPoliciesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 */
export async function* listPolicies() {
  const command = new ListPoliciesCommand({
    MaxItems: 10,
    OnlyAttached: false,
    // List only the customer managed policies in your Amazon Web Services account.
    Scope: "Local",
  });

  let response = await client.send(command);

  while (response.Policies?.length) {
    for (const policy of response.Policies) {
      yield policy;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListPoliciesCommand({
          Marker: response.Marker,
          MaxItems: 10,
          OnlyAttached: false,
          Scope: "Local",
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for JavaScript da API.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas do IAM a um perfil do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Lista as políticas que estão anexadas a uma função.

```
import {
  ListAttachedRolePoliciesCommand,
  IAMClient,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 * @param {string} roleName
 */
export async function* listAttachedRolePolicies(roleName) {
  const command = new ListAttachedRolePoliciesCommand({
    RoleName: roleName,
  });

  let response = await client.send(command);

  while (response.AttachedPolicies?.length) {
    for (const policy of response.AttachedPolicies) {
      yield policy;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListAttachedRolePoliciesCommand({
```

```
          RoleName: roleName,
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for JavaScript da API.

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os perfis.

```
import { ListRolesCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 */
export async function* listRoles() {
  const command = new ListRolesCommand({
    MaxItems: 10,
```

```
  });

  /**
   * @type {import("@aws-sdk/client-iam").ListRolesCommandOutput | undefined}
   */
  let response = await client.send(command);

  while (response?.Roles?.length) {
    for (const role of response.Roles) {
      yield role;
    }

    if (response.IsTruncated) {
      response = await client.send(
        new ListRolesCommand({
          Marker: response.Marker,
        }),
      );
    } else {
      break;
    }
  }
}
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for JavaScript da API.

Listar certificados do servidor

Os exemplos de código a seguir mostram como listar certificados de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os certificados.

```
import { ListServerCertificatesCommand, IAMClient } from "@aws-sdk/client-iam";
```

```
const client = new IAMClient({});

/**
 * A generator function that handles paginated results.
 * The AWS SDK for JavaScript (v3) provides {@link https://docs.aws.amazon.com/
AWSJavaScriptSDK/v3/latest/index.html#paginators | paginator} functions to simplify
 this.
 *
 */
export async function* listServerCertificates() {
  const command = new ListServerCertificatesCommand({});
  let response = await client.send(command);

  while (response.ServerCertificateMetadataList?.length) {
    for await (const cert of response.ServerCertificateMetadataList) {
      yield cert;
    }

    if (response.IsTruncated) {
      response = await client.send(new ListServerCertificatesCommand({}));
    } else {
      break;
    }
  }
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
```

```
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

iam.listServerCertificates({}, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for JavaScript da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os usuários.

```
import { ListUsersCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

export const listUsers = async () => {
  const command = new ListUsersCommand({ MaxItems: 10 });

  const response = await client.send(command);
  response.Users?.forEach(({ UserName, CreateDate }) => {
    console.log(`${UserName} created on: ${CreateDate}`);
  });
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  MaxItems: 10,
};

iam.listUsers(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
```

```
    var users = data.Users || [];
    users.forEach(function (user) {
      console.log("User " + user.UserName + " created", user.CreateDate);
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for JavaScript da API.

Atualizar um certificado do servidor

O exemplo de código a seguir mostra como atualizar um certificado de servidor do IAM.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize um certificado do servidor.

```
import { UpdateServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentName
 * @param {string} newName
 */
export const updateServerCertificate = (currentName, newName) => {
  const command = new UpdateServerCertificateCommand({
    ServerCertificateName: currentName,
    NewServerCertificateName: newName,
  });

  return client.send(command);
```

```
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  ServerCertificateName: "CERTIFICATE_NAME",
  NewServerCertificateName: "NEW_CERTIFICATE_NAME",
};

iam.updateServerCertificate(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for JavaScript da API.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize o usuário.

```
import { UpdateUserCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} currentUserName
 * @param {string} newUserName
 */
export const updateUser = (currentUserName, newUserName) => {
  const command = new UpdateUserCommand({
    UserName: currentUserName,
    NewUserName: newUserName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  UserName: process.argv[2],
  NewUserName: process.argv[3],
};

iam.updateUser(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for JavaScript da API.

Atualizar uma chave de acesso

O exemplo de código a seguir mostra como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualize a chave de acesso.

```
import {
  UpdateAccessKeyCommand,
  IAMClient,
  StatusType,
} from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} userName
 * @param {string} accessKeyId
 */
export const updateAccessKey = (userName, accessKeyId) => {
  const command = new UpdateAccessKeyCommand({
    AccessKeyId: accessKeyId,
    Status: StatusType.Inactive,
    UserName: userName,
  });

  return client.send(command);
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the IAM service object
var iam = new AWS.IAM({ apiVersion: "2010-05-08" });

var params = {
  AccessKeyId: "ACCESS_KEY_ID",
  Status: "Active",
  UserName: "USER_NAME",
};

iam.updateAccessKey(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for JavaScript da API.

Fazer upload de um certificado de servidor

O exemplo de código a seguir mostra como fazer upload de um certificado de servidor do AWS Identity and Access Management (IAM)

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UploadServerCertificateCommand, IAMClient } from "@aws-sdk/client-iam";
import { readFileSync } from "fs";
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import * as path from "path";

const client = new IAMClient({});

const certMessage = `Generate a certificate and key with the following command, or
 the equivalent for your system.

openssl req -x509 -newkey rsa:4096 -sha256 -days 3650 -nodes \
-keyout example.key -out example.crt -subj "/CN=example.com" \
-addext "subjectAltName=DNS:example.com,DNS:www.example.net,IP:10.0.0.1"
`;

const getCertAndKey = () => {
  try {
    const cert = readFileSync(
      path.join(dirnameFromMetaUrl(import.meta.url), "./example.crt")
    );
    const key = readFileSync(
      path.join(dirnameFromMetaUrl(import.meta.url), "./example.key")
    );
    return { cert, key };
  } catch (err) {
    if (err.code === "ENOENT") {
      throw new Error(
        `Certificate and/or private key not found. ${certMessage}`
      );
```

```
    }

    throw err;
  }
};

/**
 *
 * @param {string} certificateName
 */
export const uploadServerCertificate = (certificateName) => {
  const { cert, key } = getCertAndKey();
  const command = new UploadServerCertificateCommand({
    ServerCertificateName: certificateName,
    CertificateBody: cert.toString(),
    PrivateKey: key.toString(),
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte UploadServerCertificatea Referência AWS SDK for JavaScript da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.

- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
#!/usr/bin/env node
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import {
  Scenario,
  parseScenarioArgs,
} from "@aws-sdk-examples/libs/scenario/index.js";

/**
 * The workflow steps are split into three stages:
 *   - deploy
 *   - demo
 *   - destroy
 *
 * Each of these stages has a corresponding file prefixed with steps-*.
 */
import { deploySteps } from "./steps-deploy.js";
import { demoSteps } from "./steps-demo.js";
import { destroySteps } from "./steps-destroy.js";

/**
```

```
 * The context is passed to every scenario. Scenario steps
 * will modify the context.
 */
const context = {};

/**
 * Three Scenarios are created for the workflow. A Scenario is an orchestration
 class
 * that simplifies running a series of steps.
 */
export const scenarios = {
  // Deploys all resources necessary for the workflow.
  deploy: new Scenario("Resilient Workflow - Deploy", deploySteps, context),
  // Demonstrates how a fragile web service can be made more resilient.
  demo: new Scenario("Resilient Workflow - Demo", demoSteps, context),
  // Destroys the resources created for the workflow.
  destroy: new Scenario("Resilient Workflow - Destroy", destroySteps, context),
};

// Call function if run directly
import { fileURLToPath } from "url";

if (process.argv[1] === fileURLToPath(import.meta.url)) {
  parseScenarioArgs(scenarios);
}
```

Criar etapas para implantar todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { join } from "node:path";
import { readFileSync, writeFileSync } from "node:fs";
import axios from "axios";

import {
  BatchWriteItemCommand,
  CreateTableCommand,
  DynamoDBClient,
  waitUntilTableExists,
} from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
```

```
  CreateKeyPairCommand,
  CreateLaunchTemplateCommand,
  DescribeAvailabilityZonesCommand,
  DescribeVpcsCommand,
  DescribeSubnetsCommand,
  DescribeSecurityGroupsCommand,
  AuthorizeSecurityGroupIngressCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  AttachRolePolicyCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import { SSMClient, GetParameterCommand } from "@aws-sdk/client-ssm";
import {
  CreateAutoScalingGroupCommand,
  AutoScalingClient,
  AttachLoadBalancerTargetGroupsCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  CreateListenerCommand,
  CreateLoadBalancerCommand,
  CreateTargetGroupCommand,
  ElasticLoadBalancingV2Client,
  waitUntilLoadBalancerAvailable,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH, ROOT } from "./constants.js";
import { initParamsSteps } from "./steps-reset-params.js";

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
```

```
export const deploySteps = [
  new ScenarioOutput("introduction", MESSAGES.introduction, { header: true }),
  new ScenarioInput("confirmDeployment", MESSAGES.confirmDeployment, {
    type: "confirm",
  }),
  new ScenarioAction(
    "handleConfirmDeployment",
    (c) => c.confirmDeployment === false && process.exit(),
  ),
  new ScenarioOutput(
    "creatingTable",
    MESSAGES.creatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("createTable", async () => {
    const client = new DynamoDBClient({});
    await client.send(
      new CreateTableCommand({
        TableName: NAMES.tableName,
        ProvisionedThroughput: {
          ReadCapacityUnits: 5,
          WriteCapacityUnits: 5,
        },
        AttributeDefinitions: [
          {
            AttributeName: "MediaType",
            AttributeType: "S",
          },
          {
            AttributeName: "ItemId",
            AttributeType: "N",
          },
        ],
        KeySchema: [
          {
            AttributeName: "MediaType",
            KeyType: "HASH",
          },
          {
            AttributeName: "ItemId",
            KeyType: "RANGE",
          },
        ],
      }),
    );
```

```
    await waitUntilTableExists({ client }, { TableName: NAMES.tableName });
  }),
  new ScenarioOutput(
    "createdTable",
    MESSAGES.createdTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "populatingTable",
    MESSAGES.populatingTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioAction("populateTable", () => {
    const client = new DynamoDBClient({});
    /**
     * @type {{ default: import("@aws-sdk/client-dynamodb").PutRequest['Item'][] }}
     */
    const recommendations = JSON.parse(
      readFileSync(join(RESOURCES_PATH, "recommendations.json")),
    );

    return client.send(
      new BatchWriteItemCommand({
        RequestItems: {
          [NAMES.tableName]: recommendations.map((item) => ({
            PutRequest: { Item: item },
          })),
        },
      }),
    );
  }),
  new ScenarioOutput(
    "populatedTable",
    MESSAGES.populatedTable.replace("${TABLE_NAME}", NAMES.tableName),
  ),
  new ScenarioOutput(
    "creatingKeyPair",
    MESSAGES.creatingKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioAction("createKeyPair", async () => {
    const client = new EC2Client({});
    const { KeyMaterial } = await client.send(
      new CreateKeyPairCommand({
        KeyName: NAMES.keyPairName,
      }),
    );
```

```
    writeFileSync(`${NAMES.keyPairName}.pem`, KeyMaterial, { mode: 0o600 });
  }),
  new ScenarioOutput(
    "createdKeyPair",
    MESSAGES.createdKeyPair.replace("${KEY_PAIR_NAME}", NAMES.keyPairName),
  ),
  new ScenarioOutput(
    "creatingInstancePolicy",
    MESSAGES.creatingInstancePolicy.replace(
      "${INSTANCE_POLICY_NAME}",
      NAMES.instancePolicyName,
    ),
  ),
  new ScenarioAction("createInstancePolicy", async (state) => {
    const client = new IAMClient({});
    const {
      Policy: { Arn },
    } = await client.send(
      new CreatePolicyCommand({
        PolicyName: NAMES.instancePolicyName,
        PolicyDocument: readFileSync(
          join(RESOURCES_PATH, "instance_policy.json"),
        ),
      }),
    );
    state.instancePolicyArn = Arn;
  }),
  new ScenarioOutput("createdInstancePolicy", (state) =>
    MESSAGES.createdInstancePolicy
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_POLICY_ARN}", state.instancePolicyArn),
  ),
  new ScenarioOutput(
    "creatingInstanceRole",
    MESSAGES.creatingInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioAction("createInstanceRole", () => {
    const client = new IAMClient({});
    return client.send(
      new CreateRoleCommand({
```

```
        RoleName: NAMES.instanceRoleName,
        AssumeRolePolicyDocument: readFileSync(
          join(ROOT, "assume-role-policy.json"),
        ),
      }),
    );
  }),
  new ScenarioOutput(
    "createdInstanceRole",
    MESSAGES.createdInstanceRole.replace(
      "${INSTANCE_ROLE_NAME}",
      NAMES.instanceRoleName,
    ),
  ),
  new ScenarioOutput(
    "attachingPolicyToRole",
    MESSAGES.attachingPolicyToRole
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName)
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName),
  ),
  new ScenarioAction("attachPolicyToRole", async (state) => {
    const client = new IAMClient({});
    await client.send(
      new AttachRolePolicyCommand({
        RoleName: NAMES.instanceRoleName,
        PolicyArn: state.instancePolicyArn,
      }),
    );
  }),
  new ScenarioOutput(
    "attachedPolicyToRole",
    MESSAGES.attachedPolicyToRole
      .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioOutput(
    "creatingInstanceProfile",
    MESSAGES.creatingInstanceProfile.replace(
      "${INSTANCE_PROFILE_NAME}",
      NAMES.instanceProfileName,
    ),
  ),
  new ScenarioAction("createInstanceProfile", async (state) => {
    const client = new IAMClient({});
```

```
    const {
      InstanceProfile: { Arn },
    } = await client.send(
      new CreateInstanceProfileCommand({
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
    state.instanceProfileArn = Arn;

    await waitUntilInstanceProfileExists(
      { client },
      { InstanceProfileName: NAMES.instanceProfileName },
    );
  }),
  new ScenarioOutput("createdInstanceProfile", (state) =>
    MESSAGES.createdInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_PROFILE_ARN}", state.instanceProfileArn),
  ),
  new ScenarioOutput(
    "addingRoleToInstanceProfile",
    MESSAGES.addingRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  new ScenarioAction("addRoleToInstanceProfile", () => {
    const client = new IAMClient({});
    return client.send(
      new AddRoleToInstanceProfileCommand({
        RoleName: NAMES.instanceRoleName,
        InstanceProfileName: NAMES.instanceProfileName,
      }),
    );
  }),
  new ScenarioOutput(
    "addedRoleToInstanceProfile",
    MESSAGES.addedRoleToInstanceProfile
      .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
      .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName),
  ),
  ...initParamsSteps,
  new ScenarioOutput("creatingLaunchTemplate", MESSAGES.creatingLaunchTemplate),
  new ScenarioAction("createLaunchTemplate", async () => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
```

```
    const ssmClient = new SSMClient({});
    const { Parameter } = await ssmClient.send(
      new GetParameterCommand({
        Name: "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
      }),
    );
    const ec2Client = new EC2Client({});
    await ec2Client.send(
      new CreateLaunchTemplateCommand({
        LaunchTemplateName: NAMES.launchTemplateName,
        LaunchTemplateData: {
          InstanceType: "t3.micro",
          ImageId: Parameter.Value,
          IamInstanceProfile: { Name: NAMES.instanceProfileName },
          UserData: readFileSync(
            join(RESOURCES_PATH, "server_startup_script.sh"),
          ).toString("base64"),
          KeyName: NAMES.keyPairName,
        },
      }),
      // snippet-end:[javascript.v3.wkflw.resilient.CreateLaunchTemplate]
    );
  }),
  new ScenarioOutput(
    "createdLaunchTemplate",
    MESSAGES.createdLaunchTemplate.replace(
      "${LAUNCH_TEMPLATE_NAME}",
      NAMES.launchTemplateName,
    ),
  ),
  new ScenarioOutput(
    "creatingAutoScalingGroup",
    MESSAGES.creatingAutoScalingGroup.replace(
      "${AUTO_SCALING_GROUP_NAME}",
      NAMES.autoScalingGroupName,
    ),
  ),
  new ScenarioAction("createAutoScalingGroup", async (state) => {
    const ec2Client = new EC2Client({});
    const { AvailabilityZones } = await ec2Client.send(
      new DescribeAvailabilityZonesCommand({}),
    );
    state.availabilityZoneNames = AvailabilityZones.map((az) => az.ZoneName);
    const autoScalingClient = new AutoScalingClient({});
```

```
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new CreateAutoScalingGroupCommand({
          AvailabilityZones: state.availabilityZoneNames,
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          LaunchTemplate: {
            LaunchTemplateName: NAMES.launchTemplateName,
            Version: "$Default",
          },
          MinSize: 3,
          MaxSize: 3,
        }),
      ),
    );
  }),
  new ScenarioOutput(
    "createdAutoScalingGroup",
    /**
     * @param {{ availabilityZoneNames: string[] }} state
     */
    (state) =>
      MESSAGES.createdAutoScalingGroup
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName)
        .replace(
          "${AVAILABILITY_ZONE_NAMES}",
          state.availabilityZoneNames.join(", "),
        ),
  ),
  new ScenarioInput("confirmContinue", MESSAGES.confirmContinue, {
    type: "confirm",
  }),
  new ScenarioOutput("loadBalancer", MESSAGES.loadBalancer),
  new ScenarioOutput("gettingVpc", MESSAGES.gettingVpc),
  new ScenarioAction("getVpc", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeVpcs]
    const client = new EC2Client({});
    const { Vpcs } = await client.send(
      new DescribeVpcsCommand({
        Filters: [{ Name: "is-default", Values: ["true"] }],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeVpcs]
    state.defaultVpc = Vpcs[0].VpcId;
  }),
```

```
  new ScenarioOutput("gotVpc", (state) =>
    MESSAGES.gotVpc.replace("${VPC_ID}", state.defaultVpc),
  ),
  new ScenarioOutput("gettingSubnets", MESSAGES.gettingSubnets),
  new ScenarioAction("getSubnets", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DescribeSubnets]
    const client = new EC2Client({});
    const { Subnets } = await client.send(
      new DescribeSubnetsCommand({
        Filters: [
          { Name: "vpc-id", Values: [state.defaultVpc] },
          { Name: "availability-zone", Values: state.availabilityZoneNames },
          { Name: "default-for-az", Values: ["true"] },
        ],
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.DescribeSubnets]
    state.subnets = Subnets.map((subnet) => subnet.SubnetId);
  }),
  new ScenarioOutput(
    "gotSubnets",
    /**
     * @param {{ subnets: string[] }} state
     */
    (state) =>
      MESSAGES.gotSubnets.replace("${SUBNETS}", state.subnets.join(", ")),
  ),
  new ScenarioOutput(
    "creatingLoadBalancerTargetGroup",
    MESSAGES.creatingLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioAction("createLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    const { TargetGroups } = await client.send(
      new CreateTargetGroupCommand({
        Name: NAMES.loadBalancerTargetGroupName,
        Protocol: "HTTP",
        Port: 80,
        HealthCheckPath: "/healthcheck",
        HealthCheckIntervalSeconds: 10,
```

```
        HealthCheckTimeoutSeconds: 5,
        HealthyThresholdCount: 2,
        UnhealthyThresholdCount: 2,
        VpcId: state.defaultVpc,
      }),
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateTargetGroup]
    const targetGroup = TargetGroups[0];
    state.targetGroupArn = targetGroup.TargetGroupArn;
    state.targetGroupProtocol = targetGroup.Protocol;
    state.targetGroupPort = targetGroup.Port;
  }),
  new ScenarioOutput(
    "createdLoadBalancerTargetGroup",
    MESSAGES.createdLoadBalancerTargetGroup.replace(
      "${TARGET_GROUP_NAME}",
      NAMES.loadBalancerTargetGroupName,
    ),
  ),
  new ScenarioOutput(
    "creatingLoadBalancer",
    MESSAGES.creatingLoadBalancer.replace("${LB_NAME}", NAMES.loadBalancerName),
  ),
  new ScenarioAction("createLoadBalancer", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
    const client = new ElasticLoadBalancingV2Client({});
    const { LoadBalancers } = await client.send(
      new CreateLoadBalancerCommand({
        Name: NAMES.loadBalancerName,
        Subnets: state.subnets,
      }),
    );
    state.loadBalancerDns = LoadBalancers[0].DNSName;
    state.loadBalancerArn = LoadBalancers[0].LoadBalancerArn;
    await waitUntilLoadBalancerAvailable(
      { client },
      { Names: [NAMES.loadBalancerName] },
    );
    // snippet-end:[javascript.v3.wkflw.resilient.CreateLoadBalancer]
  }),
  new ScenarioOutput("createdLoadBalancer", (state) =>
    MESSAGES.createdLoadBalancer
      .replace("${LB_NAME}", NAMES.loadBalancerName)
      .replace("${DNS_NAME}", state.loadBalancerDns),
```

```
    ),
    new ScenarioOutput(
      "creatingListener",
      MESSAGES.creatingLoadBalancerListener
        .replace("${LB_NAME}", NAMES.loadBalancerName)
        .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName),
    ),
    new ScenarioAction("createListener", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.CreateListener]
      const client = new ElasticLoadBalancingV2Client({});
      const { Listeners } = await client.send(
        new CreateListenerCommand({
          LoadBalancerArn: state.loadBalancerArn,
          Protocol: state.targetGroupProtocol,
          Port: state.targetGroupPort,
          DefaultActions: [
            { Type: "forward", TargetGroupArn: state.targetGroupArn },
          ],
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.CreateListener]
      const listener = Listeners[0];
      state.loadBalancerListenerArn = listener.ListenerArn;
    }),
    new ScenarioOutput("createdListener", (state) =>
      MESSAGES.createdLoadBalancerListener.replace(
        "${LB_LISTENER_ARN}",
        state.loadBalancerListenerArn,
      ),
    ),
    new ScenarioOutput(
      "attachingLoadBalancerTargetGroup",
      MESSAGES.attachingLoadBalancerTargetGroup
        .replace("${TARGET_GROUP_NAME}", NAMES.loadBalancerTargetGroupName)
        .replace("${AUTO_SCALING_GROUP_NAME}", NAMES.autoScalingGroupName),
    ),
    new ScenarioAction("attachLoadBalancerTargetGroup", async (state) => {
      // snippet-start:[javascript.v3.wkflw.resilient.AttachTargetGroup]
      const client = new AutoScalingClient({});
      await client.send(
        new AttachLoadBalancerTargetGroupsCommand({
          AutoScalingGroupName: NAMES.autoScalingGroupName,
          TargetGroupARNs: [state.targetGroupArn],
        }),
```

```
    );
    // snippet-end:[javascript.v3.wkflw.resilient.AttachTargetGroup]
  }),
  new ScenarioOutput(
    "attachedLoadBalancerTargetGroup",
    MESSAGES.attachedLoadBalancerTargetGroup,
  ),
  new ScenarioOutput("verifyingInboundPort", MESSAGES.verifyingInboundPort),
  new ScenarioAction(
    "verifyInboundPort",
    /**
     *
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-ec2').SecurityGroup}}
state
     */
    async (state) => {
      const client = new EC2Client({});
      const { SecurityGroups } = await client.send(
        new DescribeSecurityGroupsCommand({
          Filters: [{ Name: "group-name", Values: ["default"] }],
        }),
      );
      if (!SecurityGroups) {
        state.verifyInboundPortError = new Error(MESSAGES.noSecurityGroups);
      }
      state.defaultSecurityGroup = SecurityGroups[0];

      /**
       * @type {string}
       */
      const ipResponse = (await axios.get("http://checkip.amazonaws.com")).data;
      state.myIp = ipResponse.trim();
      const myIpRules = state.defaultSecurityGroup.IpPermissions.filter(
        ({ IpRanges }) =>
          IpRanges.some(
            ({ CidrIp }) =>
              CidrIp.startsWith(state.myIp) || CidrIp === "0.0.0.0/0",
          ),
      )
        .filter(({ IpProtocol }) => IpProtocol === "tcp")
        .filter(({ FromPort }) => FromPort === 80);

      state.myIpRules = myIpRules;
    },
```

```
  ),
  new ScenarioOutput(
    "verifiedInboundPort",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return MESSAGES.foundIpRules.replace(
          "${IP_RULES}",
          JSON.stringify(state.myIpRules, null, 2),
        );
      } else {
        return MESSAGES.noIpRules;
      }
    },
  ),
  new ScenarioInput(
    "shouldAddInboundRule",
    /**
     * @param {{ myIpRules: any[] }} state
     */
    (state) => {
      if (state.myIpRules.length > 0) {
        return false;
      } else {
        return MESSAGES.noIpRules;
      }
    },
    { type: "confirm" },
  ),
  new ScenarioAction(
    "addInboundRule",
    /**
     * @param {{ defaultSecurityGroup: import('@aws-sdk/client-
ec2').SecurityGroup }} state
     */
    async (state) => {
      if (!state.shouldAddInboundRule) {
        return;
      }

      const client = new EC2Client({});
      await client.send(
```

```
        new AuthorizeSecurityGroupIngressCommand({
          GroupId: state.defaultSecurityGroup.GroupId,
          CidrIp: `${state.myIp}/32`,
          FromPort: 80,
          ToPort: 80,
          IpProtocol: "tcp",
        }),
      );
    },
  ),
  new ScenarioOutput("addedInboundRule", (state) => {
    if (state.shouldAddInboundRule) {
      return MESSAGES.addedInboundRule.replace("${IP_ADDRESS}", state.myIp);
    } else {
      return false;
    }
  }),
  new ScenarioOutput("verifyingEndpoint", (state) =>
    MESSAGES.verifyingEndpoint.replace("${DNS_NAME}", state.loadBalancerDns),
  ),
  new ScenarioAction("verifyEndpoint", async (state) => {
    try {
      const response = await retry({ intervalInMs: 2000, maxRetries: 30 }, () =>
        axios.get(`http://${state.loadBalancerDns}`),
      );
      state.endpointResponse = JSON.stringify(response.data, null, 2);
    } catch (e) {
      state.verifyEndpointError = e;
    }
  }),
  new ScenarioOutput("verifiedEndpoint", (state) => {
    if (state.verifyEndpointError) {
      console.error(state.verifyEndpointError);
    } else {
      return MESSAGES.verifiedEndpoint.replace(
        "${ENDPOINT_RESPONSE}",
        state.endpointResponse,
      );
    }
  }),
];
```

Criar etapas para executar a demonstração.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { readFileSync } from "node:fs";
import { join } from "node:path";

import axios from "axios";

import {
  DescribeTargetGroupsCommand,
  DescribeTargetHealthCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";
import {
  DescribeInstanceInformationCommand,
  PutParameterCommand,
  SSMClient,
  SendCommandCommand,
} from "@aws-sdk/client-ssm";
import {
  IAMClient,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  CreateInstanceProfileCommand,
  AddRoleToInstanceProfileCommand,
  waitUntilInstanceProfileExists,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DescribeAutoScalingGroupsCommand,
  TerminateInstanceInAutoScalingGroupCommand,
} from "@aws-sdk/client-auto-scaling";
import {
  DescribeIamInstanceProfileAssociationsCommand,
  EC2Client,
  RebootInstancesCommand,
  ReplaceIamInstanceProfileAssociationCommand,
} from "@aws-sdk/client-ec2";

import {
  ScenarioAction,
  ScenarioInput,
```

```
  ScenarioOutput,
} from "@aws-sdk-examples/libs/scenario/scenario.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES, RESOURCES_PATH } from "./constants.js";
import { findLoadBalancer } from "./shared.js";

const getRecommendation = new ScenarioAction(
  "getRecommendation",
  async (state) => {
    const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
    if (loadBalancer) {
      state.loadBalancerDnsName = loadBalancer.DNSName;
      try {
        state.recommendation = (
          await axios.get(`http://${state.loadBalancerDnsName}`)
        ).data;
      } catch (e) {
        state.recommendation = e instanceof Error ? e.message : e;
      }
    } else {
      throw new Error(MESSAGES.demoFindLoadBalancerError);
    }
  },
);

const getRecommendationResult = new ScenarioOutput(
  "getRecommendationResult",
  (state) =>
    `Recommendation:\n${JSON.stringify(state.recommendation, null, 2)}`,
  { preformatted: true },
);

const getHealthCheck = new ScenarioAction("getHealthCheck", async (state) => {
  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetGroups]
  const client = new ElasticLoadBalancingV2Client({});
  const { TargetGroups } = await client.send(
    new DescribeTargetGroupsCommand({
      Names: [NAMES.loadBalancerTargetGroupName],
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetGroups]

  // snippet-start:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
```

```
  const { TargetHealthDescriptions } = await client.send(
    new DescribeTargetHealthCommand({
      TargetGroupArn: TargetGroups[0].TargetGroupArn,
    }),
  );
  // snippet-end:[javascript.v3.wkflw.resilient.DescribeTargetHealth]
  state.targetHealthDescriptions = TargetHealthDescriptions;
});

const getHealthCheckResult = new ScenarioOutput(
  "getHealthCheckResult",
  /**
   * @param {{ targetHealthDescriptions: import('@aws-sdk/client-elastic-load-
balancing-v2').TargetHealthDescription[]}} state
   */
  (state) => {
    const status = state.targetHealthDescriptions
      .map((th) => `${th.Target.Id}: ${th.TargetHealth.State}`)
      .join("\n");
    return `Health check:\n${status}`;
  },
  { preformatted: true },
);

const loadBalancerLoop = new ScenarioAction(
  "loadBalancerLoop",
  getRecommendation.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput(
        "loadBalancerCheck",
        MESSAGES.demoLoadBalancerCheck,
        {
          type: "confirm",
        },
      ),
      output: getRecommendationResult,
    },
  },
);

const healthCheckLoop = new ScenarioAction(
  "healthCheckLoop",
```

```
  getHealthCheck.action,
  {
    whileConfig: {
      inputEquals: true,
      input: new ScenarioInput("healthCheck", MESSAGES.demoHealthCheck, {
        type: "confirm",
      }),
      output: getHealthCheckResult,
    },
  },
);

const statusSteps = [
  getRecommendation,
  getRecommendationResult,
  getHealthCheck,
  getHealthCheckResult,
];

/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const demoSteps = [
  new ScenarioOutput("header", MESSAGES.demoHeader, { header: true }),
  new ScenarioOutput("sanityCheck", MESSAGES.demoSanityCheck),
  ...statusSteps,
  new ScenarioInput(
    "brokenDependencyConfirmation",
    MESSAGES.demoBrokenDependencyConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("brokenDependency", async (state) => {
    if (!state.brokenDependencyConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      state.badTableName = `fake-table-${Date.now()}`;
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmTableNameKey,
          Value: state.badTableName,
          Overwrite: true,
          Type: "String",
        }),
```

```
      );
    }
  }),
  new ScenarioOutput("testBrokenDependency", (state) =>
    MESSAGES.demoTestBrokenDependency.replace(
      "${TABLE_NAME}",
      state.badTableName,
    ),
  ),
  ...statusSteps,
  new ScenarioInput(
    "staticResponseConfirmation",
    MESSAGES.demoStaticResponseConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("staticResponse", async (state) => {
    if (!state.staticResponseConfirmation) {
      process.exit();
    } else {
      const client = new SSMClient({});
      await client.send(
        new PutParameterCommand({
          Name: NAMES.ssmFailureResponseKey,
          Value: "static",
          Overwrite: true,
          Type: "String",
        }),
      );
    }
  }),
  new ScenarioOutput("testStaticResponse", MESSAGES.demoTestStaticResponse),
  ...statusSteps,
  new ScenarioInput(
    "badCredentialsConfirmation",
    MESSAGES.demoBadCredentialsConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("badCredentialsExit", (state) => {
    if (!state.badCredentialsConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("fixDynamoDBName", async () => {
    const client = new SSMClient({});
```

```
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioAction(
    "badCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-auto-scaling').Instance }}
 state
     */
    async (state) => {
      await createSsmOnlyInstanceProfile();
      const autoScalingClient = new AutoScalingClient({});
      const { AutoScalingGroups } = await autoScalingClient.send(
        new DescribeAutoScalingGroupsCommand({
          AutoScalingGroupNames: [NAMES.autoScalingGroupName],
        }),
      );
      state.targetInstance = AutoScalingGroups[0].Instances[0];
      // snippet-start:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      const ec2Client = new EC2Client({});
      const { IamInstanceProfileAssociations } = await ec2Client.send(
        new DescribeIamInstanceProfileAssociationsCommand({
          Filters: [
            { Name: "instance-id", Values: [state.targetInstance.InstanceId] },
          ],
        }),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.DescribeIamInstanceProfileAssociations]
      state.instanceProfileAssociationId =
        IamInstanceProfileAssociations[0].AssociationId;
      // snippet-start:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]
      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        ec2Client.send(
          new ReplaceIamInstanceProfileAssociationCommand({
            AssociationId: state.instanceProfileAssociationId,
```

```
            IamInstanceProfile: { Name: NAMES.ssmOnlyInstanceProfileName },
          }),
        ),
      );
      // snippet-end:
[javascript.v3.wkflw.resilient.ReplaceIamInstanceProfileAssociation]

      await ec2Client.send(
        new RebootInstancesCommand({
          InstanceIds: [state.targetInstance.InstanceId],
        }),
      );

      const ssmClient = new SSMClient({});
      await retry({ intervalInMs: 20000, maxRetries: 15 }, async () => {
        const { InstanceInformationList } = await ssmClient.send(
          new DescribeInstanceInformationCommand({}),
        );

        const instance = InstanceInformationList.find(
          (info) => info.InstanceId === state.targetInstance.InstanceId,
        );

        if (!instance) {
          throw new Error("Instance not found.");
        }
      });

      await ssmClient.send(
        new SendCommandCommand({
          InstanceIds: [state.targetInstance.InstanceId],
          DocumentName: "AWS-RunShellScript",
          Parameters: { commands: ["cd / && sudo python3 server.py 80"] },
        }),
      );
    },
  ),
  new ScenarioOutput(
    "testBadCredentials",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-ssm').InstanceInformation}}
 state
     */
    (state) =>
```

```
      MESSAGES.demoTestBadCredentials.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
  ),
  loadBalancerLoop,
  new ScenarioInput(
    "deepHealthCheckConfirmation",
    MESSAGES.demoDeepHealthCheckConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("deepHealthCheckExit", (state) => {
    if (!state.deepHealthCheckConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("deepHealthCheck", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmHealthCheckKey,
        Value: "deep",
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testDeepHealthCheck", MESSAGES.demoTestDeepHealthCheck),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput(
    "killInstanceConfirmation",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    (state) =>
      MESSAGES.demoKillInstanceConfirmation.replace(
        "${INSTANCE_ID}",
        state.targetInstance.InstanceId,
      ),
    { type: "confirm" },
  ),
  new ScenarioAction("killInstanceExit", (state) => {
```

```
    if (!state.killInstanceConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction(
    "killInstance",
    /**
     * @param {{ targetInstance: import('@aws-sdk/client-
ssm').InstanceInformation }} state
     */
    async (state) => {
      const client = new AutoScalingClient({});
      await client.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: state.targetInstance.InstanceId,
          ShouldDecrementDesiredCapacity: false,
        }),
      );
    },
  ),
  new ScenarioOutput("testKillInstance", MESSAGES.demoTestKillInstance),
  healthCheckLoop,
  loadBalancerLoop,
  new ScenarioInput("failOpenConfirmation", MESSAGES.demoFailOpenConfirmation, {
    type: "confirm",
  }),
  new ScenarioAction("failOpenExit", (state) => {
    if (!state.failOpenConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("failOpen", () => {
    const client = new SSMClient({});
    return client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: `fake-table-${Date.now()}`,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testFailOpen", MESSAGES.demoFailOpenTest),
  healthCheckLoop,
```

```
  loadBalancerLoop,
  new ScenarioInput(
    "resetTableConfirmation",
    MESSAGES.demoResetTableConfirmation,
    { type: "confirm" },
  ),
  new ScenarioAction("resetTableExit", (state) => {
    if (!state.resetTableConfirmation) {
      process.exit();
    }
  }),
  new ScenarioAction("resetTable", async () => {
    const client = new SSMClient({});
    await client.send(
      new PutParameterCommand({
        Name: NAMES.ssmTableNameKey,
        Value: NAMES.tableName,
        Overwrite: true,
        Type: "String",
      }),
    );
  }),
  new ScenarioOutput("testResetTable", MESSAGES.demoTestResetTable),
  healthCheckLoop,
  loadBalancerLoop,
];

async function createSsmOnlyInstanceProfile() {
  const iamClient = new IAMClient({});
  const { Policy } = await iamClient.send(
    new CreatePolicyCommand({
      PolicyName: NAMES.ssmOnlyPolicyName,
      PolicyDocument: readFileSync(
        join(RESOURCES_PATH, "ssm_only_policy.json"),
      ),
    }),
  );
  await iamClient.send(
    new CreateRoleCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
```

```
            Effect: "Allow",
            Principal: { Service: "ec2.amazonaws.com" },
            Action: "sts:AssumeRole",
          },
        ],
      }),
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: Policy.Arn,
    }),
  );
  await iamClient.send(
    new AttachRolePolicyCommand({
      RoleName: NAMES.ssmOnlyRoleName,
      PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
    }),
  );
  // snippet-start:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  const { InstanceProfile } = await iamClient.send(
    new CreateInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
    }),
  );
  await waitUntilInstanceProfileExists(
    { client: iamClient },
    { InstanceProfileName: NAMES.ssmOnlyInstanceProfileName },
  );
  // snippet-end:[javascript.v3.wkflw.resilient.CreateInstanceProfile]
  await iamClient.send(
    new AddRoleToInstanceProfileCommand({
      InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
      RoleName: NAMES.ssmOnlyRoleName,
    }),
  );

  return InstanceProfile;
}
```

Criar etapas para destruir todos os recursos.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
import { unlinkSync } from "node:fs";

import { DynamoDBClient, DeleteTableCommand } from "@aws-sdk/client-dynamodb";
import {
  EC2Client,
  DeleteKeyPairCommand,
  DeleteLaunchTemplateCommand,
} from "@aws-sdk/client-ec2";
import {
  IAMClient,
  DeleteInstanceProfileCommand,
  RemoveRoleFromInstanceProfileCommand,
  DeletePolicyCommand,
  DeleteRoleCommand,
  DetachRolePolicyCommand,
  paginateListPolicies,
} from "@aws-sdk/client-iam";
import {
  AutoScalingClient,
  DeleteAutoScalingGroupCommand,
  TerminateInstanceInAutoScalingGroupCommand,
  UpdateAutoScalingGroupCommand,
  paginateDescribeAutoScalingGroups,
} from "@aws-sdk/client-auto-scaling";
import {
  DeleteLoadBalancerCommand,
  DeleteTargetGroupCommand,
  DescribeTargetGroupsCommand,
  ElasticLoadBalancingV2Client,
} from "@aws-sdk/client-elastic-load-balancing-v2";

import {
  ScenarioOutput,
  ScenarioInput,
  ScenarioAction,
} from "@aws-sdk-examples/libs/scenario/index.js";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

import { MESSAGES, NAMES } from "./constants.js";
import { findLoadBalancer } from "./shared.js";
```

```
/**
 * @type {import('@aws-sdk-examples/libs/scenario.js').Step[]}
 */
export const destroySteps = [
  new ScenarioInput("destroy", MESSAGES.destroy, { type: "confirm" }),
  new ScenarioAction(
    "abort",
    (state) => state.destroy === false && process.exit(),
  ),
  new ScenarioAction("deleteTable", async (c) => {
    try {
      const client = new DynamoDBClient({});
      await client.send(new DeleteTableCommand({ TableName: NAMES.tableName }));
    } catch (e) {
      c.deleteTableError = e;
    }
  }),
  new ScenarioOutput("deleteTableResult", (state) => {
    if (state.deleteTableError) {
      console.error(state.deleteTableError);
      return MESSAGES.deleteTableError.replace(
        "${TABLE_NAME}",
        NAMES.tableName,
      );
    } else {
      return MESSAGES.deletedTable.replace("${TABLE_NAME}", NAMES.tableName);
    }
  }),
  new ScenarioAction("deleteKeyPair", async (state) => {
    try {
      const client = new EC2Client({});
      await client.send(
        new DeleteKeyPairCommand({ KeyName: NAMES.keyPairName }),
      );
      unlinkSync(`${NAMES.keyPairName}.pem`);
    } catch (e) {
      state.deleteKeyPairError = e;
    }
  }),
  new ScenarioOutput("deleteKeyPairResult", (state) => {
    if (state.deleteKeyPairError) {
      console.error(state.deleteKeyPairError);
      return MESSAGES.deleteKeyPairError.replace(
        "${KEY_PAIR_NAME}",
```

```
        NAMES.keyPairName,
      );
    } else {
      return MESSAGES.deletedKeyPair.replace(
        "${KEY_PAIR_NAME}",
        NAMES.keyPairName,
      );
    }
  }),
  new ScenarioAction("detachPolicyFromRole", async (state) => {
    try {
      const client = new IAMClient({});
      const policy = await findPolicy(NAMES.instancePolicyName);

      if (!policy) {
        state.detachPolicyFromRoleError = new Error(
          `Policy ${NAMES.instancePolicyName} not found.`,
        );
      } else {
        await client.send(
          new DetachRolePolicyCommand({
            RoleName: NAMES.instanceRoleName,
            PolicyArn: policy.Arn,
          }),
        );
      }
    } catch (e) {
      state.detachPolicyFromRoleError = e;
    }
  }),
  new ScenarioOutput("detachedPolicyFromRole", (state) => {
    if (state.detachPolicyFromRoleError) {
      console.error(state.detachPolicyFromRoleError);
      return MESSAGES.detachPolicyFromRoleError
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.detachedPolicyFromRole
        .replace("${INSTANCE_POLICY_NAME}", NAMES.instancePolicyName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstancePolicy", async (state) => {
    const client = new IAMClient({});
```

```
    const policy = await findPolicy(NAMES.instancePolicyName);

    if (!policy) {
      state.deletePolicyError = new Error(
        `Policy ${NAMES.instancePolicyName} not found.`,
      );
    } else {
      return client.send(
        new DeletePolicyCommand({
          PolicyArn: policy.Arn,
        }),
      );
    }
  }),
  new ScenarioOutput("deletePolicyResult", (state) => {
    if (state.deletePolicyError) {
      console.error(state.deletePolicyError);
      return MESSAGES.deletePolicyError.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    } else {
      return MESSAGES.deletedPolicy.replace(
        "${INSTANCE_POLICY_NAME}",
        NAMES.instancePolicyName,
      );
    }
  }),
  new ScenarioAction("removeRoleFromInstanceProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          RoleName: NAMES.instanceRoleName,
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
    } catch (e) {
      state.removeRoleFromInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("removeRoleFromInstanceProfileResult", (state) => {
    if (state.removeRoleFromInstanceProfile) {
      console.error(state.removeRoleFromInstanceProfileError);
```

```
      return MESSAGES.removeRoleFromInstanceProfileError
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    } else {
      return MESSAGES.removedRoleFromInstanceProfile
        .replace("${INSTANCE_PROFILE_NAME}", NAMES.instanceProfileName)
        .replace("${INSTANCE_ROLE_NAME}", NAMES.instanceRoleName);
    }
  }),
  new ScenarioAction("deleteInstanceRole", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new DeleteRoleCommand({
          RoleName: NAMES.instanceRoleName,
        }),
      );
    } catch (e) {
      state.deleteInstanceRoleError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceRoleResult", (state) => {
    if (state.deleteInstanceRoleError) {
      console.error(state.deleteInstanceRoleError);
      return MESSAGES.deleteInstanceRoleError.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    } else {
      return MESSAGES.deletedInstanceRole.replace(
        "${INSTANCE_ROLE_NAME}",
        NAMES.instanceRoleName,
      );
    }
  }),
  new ScenarioAction("deleteInstanceProfile", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
      const client = new IAMClient({});
      await client.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.instanceProfileName,
        }),
      );
```

```
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteInstanceProfile]
    } catch (e) {
      state.deleteInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteInstanceProfileResult", (state) => {
    if (state.deleteInstanceProfileError) {
      console.error(state.deleteInstanceProfileError);
      return MESSAGES.deleteInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    } else {
      return MESSAGES.deletedInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.instanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteAutoScalingGroup", async (state) => {
    try {
      await terminateGroupInstances(NAMES.autoScalingGroupName);
      await retry({ intervalInMs: 60000, maxRetries: 60 }, async () => {
        await deleteAutoScalingGroup(NAMES.autoScalingGroupName);
      });
    } catch (e) {
      state.deleteAutoScalingGroupError = e;
    }
  }),
  new ScenarioOutput("deleteAutoScalingGroupResult", (state) => {
    if (state.deleteAutoScalingGroupError) {
      console.error(state.deleteAutoScalingGroupError);
      return MESSAGES.deleteAutoScalingGroupError.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    } else {
      return MESSAGES.deletedAutoScalingGroup.replace(
        "${AUTO_SCALING_GROUP_NAME}",
        NAMES.autoScalingGroupName,
      );
    }
  }),
  new ScenarioAction("deleteLaunchTemplate", async (state) => {
```

```
    const client = new EC2Client({});
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
      await client.send(
        new DeleteLaunchTemplateCommand({
          LaunchTemplateName: NAMES.launchTemplateName,
        }),
      );
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLaunchTemplate]
    } catch (e) {
      state.deleteLaunchTemplateError = e;
    }
  }),
  new ScenarioOutput("deleteLaunchTemplateResult", (state) => {
    if (state.deleteLaunchTemplateError) {
      console.error(state.deleteLaunchTemplateError);
      return MESSAGES.deleteLaunchTemplateError.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    } else {
      return MESSAGES.deletedLaunchTemplate.replace(
        "${LAUNCH_TEMPLATE_NAME}",
        NAMES.launchTemplateName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancer", async (state) => {
    try {
      // snippet-start:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
      const client = new ElasticLoadBalancingV2Client({});
      const loadBalancer = await findLoadBalancer(NAMES.loadBalancerName);
      await client.send(
        new DeleteLoadBalancerCommand({
          LoadBalancerArn: loadBalancer.LoadBalancerArn,
        }),
      );
      await retry({ intervalInMs: 1000, maxRetries: 60 }, async () => {
        const lb = await findLoadBalancer(NAMES.loadBalancerName);
        if (lb) {
          throw new Error("Load balancer still exists.");
        }
      });
      // snippet-end:[javascript.v3.wkflw.resilient.DeleteLoadBalancer]
```

```
    } catch (e) {
      state.deleteLoadBalancerError = e;
    }
  }),
  new ScenarioOutput("deleteLoadBalancerResult", (state) => {
    if (state.deleteLoadBalancerError) {
      console.error(state.deleteLoadBalancerError);
      return MESSAGES.deleteLoadBalancerError.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    } else {
      return MESSAGES.deletedLoadBalancer.replace(
        "${LB_NAME}",
        NAMES.loadBalancerName,
      );
    }
  }),
  new ScenarioAction("deleteLoadBalancerTargetGroup", async (state) => {
    // snippet-start:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
    const client = new ElasticLoadBalancingV2Client({});
    try {
      const { TargetGroups } = await client.send(
        new DescribeTargetGroupsCommand({
          Names: [NAMES.loadBalancerTargetGroupName],
        }),
      );

      await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
        client.send(
          new DeleteTargetGroupCommand({
            TargetGroupArn: TargetGroups[0].TargetGroupArn,
          }),
        ),
      );
    } catch (e) {
      state.deleteLoadBalancerTargetGroupError = e;
    }
    // snippet-end:[javascript.v3.wkflw.resilient.DeleteTargetGroup]
  }),
  new ScenarioOutput("deleteLoadBalancerTargetGroupResult", (state) => {
    if (state.deleteLoadBalancerTargetGroupError) {
      console.error(state.deleteLoadBalancerTargetGroupError);
      return MESSAGES.deleteLoadBalancerTargetGroupError.replace(
```

```
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    } else {
      return MESSAGES.deletedLoadBalancerTargetGroup.replace(
        "${TARGET_GROUP_NAME}",
        NAMES.loadBalancerTargetGroupName,
      );
    }
  }),
  new ScenarioAction("detachSsmOnlyRoleFromProfile", async (state) => {
    try {
      const client = new IAMClient({});
      await client.send(
        new RemoveRoleFromInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.detachSsmOnlyRoleFromProfileError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyRoleFromProfileResult", (state) => {
    if (state.detachSsmOnlyRoleFromProfileError) {
      console.error(state.detachSsmOnlyRoleFromProfileError);
      return MESSAGES.detachSsmOnlyRoleFromProfileError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    } else {
      return MESSAGES.detachedSsmOnlyRoleFromProfile
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${PROFILE_NAME}", NAMES.ssmOnlyInstanceProfileName);
    }
  }),
  new ScenarioAction("detachSsmOnlyCustomRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
```

```
      );
    } catch (e) {
      state.detachSsmOnlyCustomRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyCustomRolePolicyResult", (state) => {
    if (state.detachSsmOnlyCustomRolePolicyError) {
      console.error(state.detachSsmOnlyCustomRolePolicyError);
      return MESSAGES.detachSsmOnlyCustomRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    } else {
      return MESSAGES.detachedSsmOnlyCustomRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", NAMES.ssmOnlyPolicyName);
    }
  }),
  new ScenarioAction("detachSsmOnlyAWSRolePolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: NAMES.ssmOnlyRoleName,
          PolicyArn: "arn:aws:iam::aws:policy/AmazonSSMManagedInstanceCore",
        }),
      );
    } catch (e) {
      state.detachSsmOnlyAWSRolePolicyError = e;
    }
  }),
  new ScenarioOutput("detachSsmOnlyAWSRolePolicyResult", (state) => {
    if (state.detachSsmOnlyAWSRolePolicyError) {
      console.error(state.detachSsmOnlyAWSRolePolicyError);
      return MESSAGES.detachSsmOnlyAWSRolePolicyError
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    } else {
      return MESSAGES.detachedSsmOnlyAWSRolePolicy
        .replace("${ROLE_NAME}", NAMES.ssmOnlyRoleName)
        .replace("${POLICY_NAME}", "AmazonSSMManagedInstanceCore");
    }
  }),
  new ScenarioAction("deleteSsmOnlyInstanceProfile", async (state) => {
    try {
```

```
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteInstanceProfileCommand({
          InstanceProfileName: NAMES.ssmOnlyInstanceProfileName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyInstanceProfileError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyInstanceProfileResult", (state) => {
    if (state.deleteSsmOnlyInstanceProfileError) {
      console.error(state.deleteSsmOnlyInstanceProfileError);
      return MESSAGES.deleteSsmOnlyInstanceProfileError.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyInstanceProfile.replace(
        "${INSTANCE_PROFILE_NAME}",
        NAMES.ssmOnlyInstanceProfileName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyPolicy", async (state) => {
    try {
      const iamClient = new IAMClient({});
      const ssmOnlyPolicy = await findPolicy(NAMES.ssmOnlyPolicyName);
      await iamClient.send(
        new DeletePolicyCommand({
          PolicyArn: ssmOnlyPolicy.Arn,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyPolicyError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyPolicyResult", (state) => {
    if (state.deleteSsmOnlyPolicyError) {
      console.error(state.deleteSsmOnlyPolicyError);
      return MESSAGES.deleteSsmOnlyPolicyError.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
```

```
    } else {
      return MESSAGES.deletedSsmOnlyPolicy.replace(
        "${POLICY_NAME}",
        NAMES.ssmOnlyPolicyName,
      );
    }
  }),
  new ScenarioAction("deleteSsmOnlyRole", async (state) => {
    try {
      const iamClient = new IAMClient({});
      await iamClient.send(
        new DeleteRoleCommand({
          RoleName: NAMES.ssmOnlyRoleName,
        }),
      );
    } catch (e) {
      state.deleteSsmOnlyRoleError = e;
    }
  }),
  new ScenarioOutput("deleteSsmOnlyRoleResult", (state) => {
    if (state.deleteSsmOnlyRoleError) {
      console.error(state.deleteSsmOnlyRoleError);
      return MESSAGES.deleteSsmOnlyRoleError.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    } else {
      return MESSAGES.deletedSsmOnlyRole.replace(
        "${ROLE_NAME}",
        NAMES.ssmOnlyRoleName,
      );
    }
  }),
];

/**
 * @param {string} policyName
 */
async function findPolicy(policyName) {
  const client = new IAMClient({});
  const paginatedPolicies = paginateListPolicies({ client }, {});
  for await (const page of paginatedPolicies) {
    const policy = page.Policies.find((p) => p.PolicyName === policyName);
    if (policy) {
```

```
      return policy;
    }
  }
}

/**
 * @param {string} groupName
 */
async function deleteAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  try {
    await client.send(
      new DeleteAutoScalingGroupCommand({
        AutoScalingGroupName: groupName,
      }),
    );
  } catch (err) {
    if (!(err instanceof Error)) {
      throw err;
    } else {
      console.log(err.name);
      throw err;
    }
  }
}

/**
 * @param {string} groupName
 */
async function terminateGroupInstances(groupName) {
  const autoScalingClient = new AutoScalingClient({});
  const group = await findAutoScalingGroup(groupName);
  await autoScalingClient.send(
    new UpdateAutoScalingGroupCommand({
      AutoScalingGroupName: group.AutoScalingGroupName,
      MinSize: 0,
    }),
  );
  for (const i of group.Instances) {
    await retry({ intervalInMs: 1000, maxRetries: 30 }, () =>
      autoScalingClient.send(
        new TerminateInstanceInAutoScalingGroupCommand({
          InstanceId: i.InstanceId,
          ShouldDecrementDesiredCapacity: true,
```

```
        }),
      ),
    );
  }
}

async function findAutoScalingGroup(groupName) {
  const client = new AutoScalingClient({});
  const paginatedGroups = paginateDescribeAutoScalingGroups({ client }, {});
  for await (const page of paginatedGroups) {
    const group = page.AutoScalingGroups.find(
      (g) => g.AutoScalingGroupName === groupName,
    );
    if (group) {
      return group;
    }
  }
  throw new Error(`Auto scaling group ${groupName} not found.`);
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones

- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
import {
  CreateUserCommand,
  CreateAccessKeyCommand,
  CreatePolicyCommand,
  CreateRoleCommand,
  AttachRolePolicyCommand,
  DeleteAccessKeyCommand,
  DeleteUserCommand,
  DeleteRoleCommand,
  DeletePolicyCommand,
  DetachRolePolicyCommand,
  IAMClient,
} from "@aws-sdk/client-iam";
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";
import { AssumeRoleCommand, STSClient } from "@aws-sdk/client-sts";
import { retry } from "@aws-sdk-examples/libs/utils/util-timers.js";

// Set the parameters.
const iamClient = new IAMClient({});
const userName = "test_name";
const policyName = "test_policy";
const roleName = "test_role";

export const main = async () => {
  // Create a user. The user has no permissions by default.
  const { User } = await iamClient.send(
    new CreateUserCommand({ UserName: userName }),
  );

  if (!User) {
    throw new Error("User not created");
  }

  // Create an access key. This key is used to authenticate the new user to
  // Amazon Simple Storage Service (Amazon S3) and AWS Security Token Service (AWS
 STS).
  // It's not best practice to use access keys. For more information, see https://
aws.amazon.com/iam/resources/best-practices/.
  const createAccessKeyResponse = await iamClient.send(
```

```
    new CreateAccessKeyCommand({ UserName: userName }),
  );

  if (
    !createAccessKeyResponse.AccessKey?.AccessKeyId ||
    !createAccessKeyResponse.AccessKey?.SecretAccessKey
  ) {
    throw new Error("Access key not created");
  }

  const {
    AccessKey: { AccessKeyId, SecretAccessKey },
  } = createAccessKeyResponse;

  let s3Client = new S3Client({
    credentials: {
      accessKeyId: AccessKeyId,
      secretAccessKey: SecretAccessKey,
    },
  });

  // Retry the list buckets operation until it succeeds. InvalidAccessKeyId is
  // thrown while the user and access keys are still stabilizing.
  await retry({ intervalInMs: 1000, maxRetries: 300 }, async () => {
    try {
      return await listBuckets(s3Client);
    } catch (err) {
      if (err instanceof Error && err.name === "InvalidAccessKeyId") {
        throw err;
      }
    }
  });

  // Retry the create role operation until it succeeds. A MalformedPolicyDocument
error
  // is thrown while the user and access keys are still stabilizing.
  const { Role } = await retry(
    {
      intervalInMs: 2000,
      maxRetries: 60,
    },
    () =>
      iamClient.send(
        new CreateRoleCommand({
```

```
        AssumeRolePolicyDocument: JSON.stringify({
          Version: "2012-10-17",
          Statement: [
            {
              Effect: "Allow",
              Principal: {
                // Allow the previously created user to assume this role.
                AWS: User.Arn,
              },
              Action: "sts:AssumeRole",
            },
          ],
        }),
        RoleName: roleName,
      }),
    ),
);

if (!Role) {
  throw new Error("Role not created");
}

// Create a policy that allows the user to list S3 buckets.
const { Policy: listBucketPolicy } = await iamClient.send(
  new CreatePolicyCommand({
    PolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: ["s3:ListAllMyBuckets"],
          Resource: "*",
        },
      ],
    }),
    PolicyName: policyName,
  }),
);

if (!listBucketPolicy) {
  throw new Error("Policy not created");
}

// Attach the policy granting the 's3:ListAllMyBuckets' action to the role.
```

```
  await iamClient.send(
    new AttachRolePolicyCommand({
      PolicyArn: listBucketPolicy.Arn,
      RoleName: Role.RoleName,
    }),
  );

  // Assume the role.
  const stsClient = new STSClient({
    credentials: {
      accessKeyId: AccessKeyId,
      secretAccessKey: SecretAccessKey,
    },
  });

  // Retry the assume role operation until it succeeds.
  const { Credentials } = await retry(
    { intervalInMs: 2000, maxRetries: 60 },
    () =>
      stsClient.send(
        new AssumeRoleCommand({
          RoleArn: Role.Arn,
          RoleSessionName: `iamBasicScenarioSession-${Math.floor(
            Math.random() * 1000000,
          )}`,
          DurationSeconds: 900,
        }),
      ),
  );

  if (!Credentials?.AccessKeyId || !Credentials?.SecretAccessKey) {
    throw new Error("Credentials not created");
  }

  s3Client = new S3Client({
    credentials: {
      accessKeyId: Credentials.AccessKeyId,
      secretAccessKey: Credentials.SecretAccessKey,
      sessionToken: Credentials.SessionToken,
    },
  });

  // List the S3 buckets again.
  // Retry the list buckets operation until it succeeds. AccessDenied might
```

```
  // be thrown while the role policy is still stabilizing.
  await retry({ intervalInMs: 2000, maxRetries: 60 }, () =>
    listBuckets(s3Client),
  );

  // Clean up.
  await iamClient.send(
    new DetachRolePolicyCommand({
      PolicyArn: listBucketPolicy.Arn,
      RoleName: Role.RoleName,
    }),
  );

  await iamClient.send(
    new DeletePolicyCommand({
      PolicyArn: listBucketPolicy.Arn,
    }),
  );

  await iamClient.send(
    new DeleteRoleCommand({
      RoleName: Role.RoleName,
    }),
  );

  await iamClient.send(
    new DeleteAccessKeyCommand({
      UserName: userName,
      AccessKeyId,
    }),
  );

  await iamClient.send(
    new DeleteUserCommand({
      UserName: userName,
    }),
  );
};

/**
 *
 * @param {S3Client} s3Client
 */
const listBuckets = async (s3Client) => {
```

```
  const { Buckets } = await s3Client.send(new ListBucketsCommand({}));

  if (!Buckets) {
    throw new Error("Buckets not listed");
  }

  console.log(Buckets.map((bucket) => bucket.Name).join("\n"));
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos de Lambda usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { LambdaClient, paginateListFunctions } from "@aws-sdk/client-lambda";

const client = new LambdaClient({});

export const helloLambda = async () => {
  const paginator = paginateListFunctions({ client }, {});
  const functions = [];

  for await (const page of paginator) {
    const funcNames = page.Functions.map((f) => f.FunctionName);
    functions.push(...funcNames);
  }

  console.log("Functions:");
  console.log(functions.join("\n"));
  return functions;
};
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações

- Cenários

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const createFunction = async (funcName, roleArn) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${funcName}.zip`);

  const command = new CreateFunctionCommand({
    Code: { ZipFile: code },
    FunctionName: funcName,
    Role: roleArn,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for JavaScript da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * @param {string} funcName
 */
const deleteFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new DeleteFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for JavaScript da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const getFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new GetFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for JavaScript da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const invoke = async (funcName, payload) => {
  const client = new LambdaClient({});
  const command = new InvokeCommand({
    FunctionName: funcName,
    Payload: JSON.stringify(payload),
    LogType: LogType.Tail,
  });

  const { Payload, LogResult } = await client.send(command);
  const result = Buffer.from(Payload).toString();
  const logs = Buffer.from(LogResult, "base64").toString();
  return { logs, result };
};
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for JavaScript.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const listFunctions = () => {
  const client = new LambdaClient({});
  const command = new ListFunctionsCommand({});

  return client.send(command);
};
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for JavaScript da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const updateFunctionCode = async (funcName, newFunc) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${newFunc}.zip`);
  const command = new UpdateFunctionCodeCommand({
    ZipFile: code,
    FunctionName: funcName,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
```

```
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for JavaScript da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
const updateFunctionConfiguration = (funcName) => {
  const client = new LambdaClient({});
  const config = readFileSync(`${dirname}../functions/config.json`).toString();
  const command = new UpdateFunctionConfigurationCommand({
    ...JSON.parse(config),
    FunctionName: funcName,
  });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for JavaScript da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um perfil do AWS Identity and Access Management (IAM) que concede permissão ao Lambda para gravar em logs.

```
    log(`Creating role (${NAME_ROLE_LAMBDA})...`);
    const response = await createRole(NAME_ROLE_LAMBDA);

import { AttachRolePolicyCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});

/**
 *
 * @param {string} policyArn
 * @param {string} roleName
 */
export const attachRolePolicy = (policyArn, roleName) => {
  const command = new AttachRolePolicyCommand({
    PolicyArn: policyArn,
    RoleName: roleName,
  });

  return client.send(command);
};
```

Crie uma função do Lambda e carregue o código de manipulador.

```
const createFunction = async (funcName, roleArn) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${funcName}.zip`);

  const command = new CreateFunctionCommand({
    Code: { ZipFile: code },
    FunctionName: funcName,
    Role: roleArn,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};
```

Invoque essa função com um único parâmetro e receba resultados.

```
const invoke = async (funcName, payload) => {
  const client = new LambdaClient({});
  const command = new InvokeCommand({
    FunctionName: funcName,
    Payload: JSON.stringify(payload),
    LogType: LogType.Tail,
  });

  const { Payload, LogResult } = await client.send(command);
  const result = Buffer.from(Payload).toString();
  const logs = Buffer.from(LogResult, "base64").toString();
  return { logs, result };
};
```

Atualize o código de função e configure seu ambiente do Lambda usando uma variável de ambiente.

```
const updateFunctionCode = async (funcName, newFunc) => {
  const client = new LambdaClient({});
  const code = await readFile(`${dirname}../functions/${newFunc}.zip`);
  const command = new UpdateFunctionCodeCommand({
    ZipFile: code,
    FunctionName: funcName,
    Architectures: [Architecture.arm64],
    Handler: "index.handler", // Required when sending a .zip file
    PackageType: PackageType.Zip, // Required when sending a .zip file
    Runtime: Runtime.nodejs16x, // Required when sending a .zip file
  });

  return client.send(command);
};

const updateFunctionConfiguration = (funcName) => {
  const client = new LambdaClient({});
  const config = readFileSync(`${dirname}../functions/config.json`).toString();
  const command = new UpdateFunctionConfigurationCommand({
    ...JSON.parse(config),
    FunctionName: funcName,
  });
  return client.send(command);
};
```

Liste as funções para a sua conta.

```
const listFunctions = () => {
  const client = new LambdaClient({});
  const command = new ListFunctionsCommand({});

  return client.send(command);
};
```

Exclua o perfil do IAM e a função do Lambda.

```
import { DeleteRoleCommand, IAMClient } from "@aws-sdk/client-iam";

const client = new IAMClient({});
```

```
/**
 *
 * @param {string} roleName
 */
export const deleteRole = (roleName) => {
  const command = new DeleteRoleCommand({ RoleName: roleName });
  return client.send(command);
};

/**
 * @param {string} funcName
 */
const deleteFunction = (funcName) => {
  const client = new LambdaClient({});
  const command = new DeleteFunctionCommand({ FunctionName: funcName });
  return client.send(command);
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos do Amazon Personalize usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Personalize.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um trabalho de interface em lote

O exemplo de código a seguir mostra como criar um trabalho de interface em lote do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateBatchInferenceJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the batch inference job's parameters.

export const createBatchInferenceJobParam = {
  jobName: 'JOB_NAME',
  jobInput: {         /* required */
    s3DataSource: {   /* required */
      path: 'INPUT_PATH', /* required */
      // kmsKeyArn: 'INPUT_KMS_KEY_ARN' /* optional */'
```

```
    }
  },
  jobOutput: {         /* required */
    s3DataDestination: {   /* required */
      path: 'OUTPUT_PATH', /* required */
      // kmsKeyArn: 'OUTPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  roleArn: 'ROLE_ARN', /* required */
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  numResults: 20 /* optional integer*/
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateBatchInferenceJobCommand(createBatchInferenceJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateBatchInferenceJoba Referência AWS SDK for JavaScript da API.

Criar um trabalho de segmento em lote

O exemplo de código a seguir mostra como criar um trabalho de segmento em lote do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateBatchSegmentJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the batch segment job's parameters.

export const createBatchSegmentJobParam = {
  jobName: 'NAME',
  jobInput: {         /* required */
    s3DataSource: {   /* required */
      path: 'INPUT_PATH', /* required */
      // kmsKeyArn: 'INPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  jobOutput: {         /* required */
    s3DataDestination: {   /* required */
      path: 'OUTPUT_PATH', /* required */
      // kmsKeyArn: 'OUTPUT_KMS_KEY_ARN' /* optional */'
    }
  },
  roleArn: 'ROLE_ARN', /* required */
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  numResults: 20 /* optional */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateBatchSegmentJobCommand(createBatchSegmentJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateBatchSegmentJoba Referência AWS SDK for JavaScript da API.

Criar uma campanha

O exemplo de código a seguir mostra como criar uma campanha do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.

import { CreateCampaignCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the campaign's parameters.
export const createCampaignParam = {
  solutionVersionArn: 'SOLUTION_VERSION_ARN', /* required */
  name: 'NAME',  /* required */
  minProvisionedTPS: 1    /* optional integer */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateCampaignCommand(createCampaignParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for JavaScript da API.

Criar um conjunto de dados

O exemplo de código a seguir mostra como criar um conjunto de dados do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateDatasetCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the dataset's parameters.
export const createDatasetParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  datasetType: 'DATASET_TYPE', /* required */
  name: 'NAME', /* required */
  schemaArn: 'SCHEMA_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetCommand(createDatasetParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
```

```
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetA Referência AWS SDK for JavaScript da API.

Criar um trabalho de exportação de conjunto de dados

O exemplo de código a seguir mostra como criar um trabalho de exportação de conjunto de dados do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateDatasetExportJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the export job parameters.
export const datasetExportJobParam = {
  datasetArn: 'DATASET_ARN', /* required */
  jobOutput: {
    s3DataDestination: {
        path: 'S3_DESTINATION_PATH' /* required */
        //kmsKeyArn: 'ARN'  /* include if your bucket uses AWS KMS for encryption
    }
  },
  jobName: 'NAME',/* required */
  roleArn: 'ROLE_ARN' /* required */
}
```

```
export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetExportJobCommand(datasetExportJobParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetExportJoba Referência AWS SDK for JavaScript da API.

Criar um grupo de conjuntos de dados

O exemplo de código a seguir mostra como criar um grupo de conjuntos de dados do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.

import { CreateDatasetGroupCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the dataset group parameters.
export const createDatasetGroupParam = {
  name: 'NAME' /* required */
```

```
}

export const run = async (createDatasetGroupParam) => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetGroupCommand(createDatasetGroupParam));
    console.log("Success", response);
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run(createDatasetGroupParam);
```

Criar um grupo de conjunto de dados de domínio.

```
// Get service clients module and commands using ES6 syntax.
import {  CreateDatasetGroupCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the domain dataset group parameters.
export const domainDatasetGroupParams = {
  name: 'NAME',  /* required */
  domain: 'DOMAIN'   /* required for a domain dsg, specify ECOMMERCE or
 VIDEO_ON_DEMAND */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetGroupCommand(domainDatasetGroupParams));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetGroupa Referência AWS SDK for JavaScript da API.

Criar um trabalho de importação de conjunto de dados

O exemplo de código a seguir mostra como criar um trabalho de importação de conjunto de dados do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import {CreateDatasetImportJobCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the dataset import job parameters.
export const datasetImportJobParam = {
  datasetArn: 'DATASET_ARN', /* required */
  dataSource: {  /* required */
    dataLocation: 'S3_PATH'
  },
  jobName: 'NAME',/* required */
  roleArn: 'ROLE_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateDatasetImportJobCommand(datasetImportJobParam));
    console.log("Success", response);
```

```
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateDatasetImportJoba Referência AWS SDK for JavaScript da API.

Criar um esquema de domínio

O exemplo de código a seguir mostra como criar um esquema de domínio do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSchemaCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

import fs from 'fs';

let schemaFilePath = "SCHEMA_PATH";
let mySchema = "";

try {
  mySchema = fs.readFileSync(schemaFilePath).toString();
} catch (err) {
  mySchema = 'TEST' // for unit tests.
}
```

```
// Set the domain schema parameters.
export const createDomainSchemaParam = {
  name: 'NAME', /* required */
  schema: mySchema, /* required */
  domain: 'DOMAIN'   /* required for a domain dataset group, specify ECOMMERCE or
 VIDEO_ON_DEMAND */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSchemaCommand(createDomainSchemaParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for JavaScript da API.

Criar um filtro

O exemplo de código a seguir mostra como criar um filtro do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateFilterCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
```

```
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the filter's parameters.
export const createFilterParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  name: 'NAME', /* required */
  filterExpression: 'FILTER_EXPRESSION' /*required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateFilterCommand(createFilterParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateFiltera Referência AWS SDK for JavaScript da API.

Criar um recomendador

O exemplo de código a seguir mostra como criar um recomendador do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateRecommenderCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
```

```
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the recommender's parameters.
export const createRecommenderParam = {
  name: 'NAME', /* required */
  recipeArn: 'RECIPE_ARN', /* required */
  datasetGroupArn: 'DATASET_GROUP_ARN'  /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateRecommenderCommand(createRecommenderParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateRecommendera Referência AWS SDK for JavaScript da API.

Criar um esquema

O exemplo de código a seguir mostra como criar um esquema do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSchemaCommand } from
```

```
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

import fs from 'fs';

let schemaFilePath = "SCHEMA_PATH";
let mySchema = "";

try {
  mySchema = fs.readFileSync(schemaFilePath).toString();
} catch (err) {
  mySchema = 'TEST' // For unit tests.
}
// Set the schema parameters.
export const createSchemaParam = {
  name: 'NAME', /* required */
  schema: mySchema /* required */
};

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSchemaCommand(createSchemaParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for JavaScript da API.

Criar uma solução

O exemplo de código a seguir mostra como criar uma solução do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSolutionCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the solution parameters.
export const createSolutionParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  recipeArn: 'RECIPE_ARN', /* required */
  name: 'NAME' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSolutionCommand(createSolutionParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSolutiona Referência AWS SDK for JavaScript da API.

Criar uma versão da solução

O exemplo de código a seguir mostra como criar uma solução do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateSolutionVersionCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the solution version parameters.
export const solutionVersionParam = {
  solutionArn: 'SOLUTION_ARN' /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateSolutionVersionCommand(solutionVersionParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateSolutionVersiona Referência AWS SDK for JavaScript da API.

Criar um rastreador de eventos

O exemplo de código a seguir mostra como criar um rastreador de eventos do Amazon Personalize.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { CreateEventTrackerCommand } from
  "@aws-sdk/client-personalize";
import { personalizeClient } from "./libs/personalizeClients.js";

// Or, create the client here.
// const personalizeClient = new PersonalizeClient({ region: "REGION"});

// Set the event tracker's parameters.
export const createEventTrackerParam = {
  datasetGroupArn: 'DATASET_GROUP_ARN', /* required */
  name: 'NAME', /* required */
}

export const run = async () => {
  try {
    const response = await personalizeClient.send(new
 CreateEventTrackerCommand(createEventTrackerParam));
    console.log("Success", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateEventTrackera Referência AWS SDK for JavaScript da API.

Exemplos de eventos do Amazon Personalize usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Personalize Events.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Importar itens para um conjunto de dados

O exemplo de código a seguir mostra como importar incrementalmente itens para um conjunto de dados do Amazon Personalize Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { PutItemsCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region: "REGION"});

// Set the put items parameters. For string properties and values, use the \
 character to escape quotes.
```

```
var putItemsParam = {
  datasetArn: "DATASET_ARN" /* required */,
  items: [
    /* required */
    {
      itemId: "ITEM_ID" /*  required */,
      properties:
        '{"PROPERTY1_NAME": "PROPERTY1_VALUE", "PROPERTY2_NAME": "PROPERTY2_VALUE",
 "PROPERTY3_NAME": "PROPERTY3_VALUE"}' /* optional */,
    },
  ],
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutItemsCommand(putItemsParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutItemsa Referência AWS SDK for JavaScript da API.

Importar dados de eventos de interação em tempo real

O exemplo de código a seguir mostra como importar dados de eventos de interação em tempo real para o Amazon Personalize Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
```

```
import { PutEventsCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region: "REGION"});

// Convert your UNIX timestamp to a Date.
const sentAtDate = new Date(1613443801 * 1000); // 1613443801 is a testing value.
 Replace it with your sentAt timestamp in UNIX format.

// Set put events parameters.
var putEventsParam = {
  eventList: [
    /* required */
    {
      eventType: "EVENT_TYPE" /* required */,
      sentAt: sentAtDate /* required, must be a Date with js */,
      eventId: "EVENT_ID" /* optional */,
      itemId: "ITEM_ID" /* optional */,
    },
  ],
  sessionId: "SESSION_ID" /* required */,
  trackingId: "TRACKING_ID" /* required */,
  userId: "USER_ID" /* required */,
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutEventsCommand(putEventsParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for JavaScript da API.

Importar incrementalmente um usuário

O exemplo de código a seguir mostra como importar incrementalmente um usuário para eventos do Amazon Personalize Events.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { PutUsersCommand } from "@aws-sdk/client-personalize-events";
import { personalizeEventsClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeEventsClient = new PersonalizeEventsClient({ region: "REGION"});

// Set the put users parameters. For string properties and values, use the \
 character to escape quotes.
var putUsersParam = {
  datasetArn: "DATASET_ARN",
  users: [
    {
      userId: "USER_ID",
      properties: '{"PROPERTY1_NAME": "PROPERTY1_VALUE"}',
    },
  ],
};
export const run = async () => {
  try {
    const response = await personalizeEventsClient.send(
      new PutUsersCommand(putUsersParam),
    );
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte PutUsersa Referência AWS SDK for JavaScript da API.

Exemplos do Amazon Personalize Runtime usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Personalize Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter recomendações (grupo de conjunto de dados personalizados)

O exemplo de código a seguir mostra como obter recomendações de classificação do Amazon Personalize Runtime.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { GetPersonalizedRankingCommand } from
```

```
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the ranking request parameters.
export const getPersonalizedRankingParam = {
  campaignArn: "CAMPAIGN_ARN", /* required */
  userId: 'USER_ID',      /* required */
  inputList: ["ITEM_ID_1", "ITEM_ID_2", "ITEM_ID_3", "ITEM_ID_4"]
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetPersonalizedRankingCommand(getPersonalizedRankingParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte GetPersonalizedRankinga Referência AWS SDK for JavaScript da API.

Receber recomendações de um recomendador (grupo de conjunto de dados de domínio)

O exemplo de código a seguir mostra como obter recomendações de runtime do Amazon Personalize Runtime.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
  "@aws-sdk/client-personalize-runtime";

import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the recommendation request parameters.
export const getRecommendationsParam = {
  campaignArn: 'CAMPAIGN_ARN', /* required */
  userId: 'USER_ID',      /* required */
  numResults: 15    /* optional */
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Obter recomendações com um filtro (grupo de conjunto de dados personalizados).

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here.
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set the recommendation request parameters.
export const getRecommendationsParam = {
  recommenderArn: 'RECOMMENDER_ARN', /* required */
```

```
  userId: 'USER_ID',       /* required */
  numResults: 15    /* optional */
}

export const run = async () => {
  try {
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Obtenha as recomendações filtradas de um recomendador criado em um grupo de conjuntos de dados de domínio.

```
// Get service clients module and commands using ES6 syntax.
import { GetRecommendationsCommand } from
  "@aws-sdk/client-personalize-runtime";
import { personalizeRuntimeClient } from "./libs/personalizeClients.js";
// Or, create the client here:
// const personalizeRuntimeClient = new PersonalizeRuntimeClient({ region:
 "REGION"});

// Set recommendation request parameters.
export const getRecommendationsParam = {
  campaignArn: 'CAMPAIGN_ARN', /* required */
  userId: 'USER_ID',      /* required */
  numResults: 15,    /* optional */
  filterArn: 'FILTER_ARN',   /* required to filter recommendations */
  filterValues: {
    "PROPERTY": "\"VALUE\""  /* Only required if your filter has a placeholder
 parameter */
  }
}

export const run = async () => {
  try {
```

```
    const response = await personalizeRuntimeClient.send(new
 GetRecommendationsCommand(getRecommendationsParam));
    console.log("Success!", response);
    return response; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte GetRecommendationsa Referência AWS SDK for JavaScript da API.

Exemplos do Amazon Pinpoint usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar e-mails e mensagens de texto

O exemplo de código a seguir mostra como enviar e-mail e mensagens de texto com o Amazon Pinpoint.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { PinpointClient } from "@aws-sdk/client-pinpoint";
// Set the AWS Region.
const REGION = "us-east-1";
//Set the MediaConvert Service Object
const pinClient = new PinpointClient({ region: REGION });
export { pinClient };
```

Envie uma mensagem de e-mail.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

// The FromAddress must be verified in SES.
const fromAddress = "FROM_ADDRESS";
const toAddress = "TO_ADDRESS";
const projectId = "PINPOINT_PROJECT_ID";

// The subject line of the email.
var subject = "Amazon Pinpoint Test (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https://aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
var body_html = `<html>
<head></head>
```

```
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint Email API</a>
 using the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding for the subject line and message body of the email.
var charset = "UTF-8";

const params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: fromAddress,
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};

const run = async () => {
```

```
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));

    const {
      MessageResponse: { Result },
    } = data;

    const recipientResult = Result[toAddress];

    if (recipientResult.StatusCode !== 200) {
      throw new Error(recipientResult.StatusMessage);
    } else {
      console.log(recipientResult.MessageId);
    }
  } catch (err) {
    console.log(err.message);
  }
};

run();
```

Envie uma mensagem SMS.

```
// Import required AWS SDK clients and commands for Node.js
import { SendMessagesCommand } from "@aws-sdk/client-pinpoint";
import { pinClient } from "./libs/pinClient.js";

("use strict");

/* The phone number or short code to send the message from. The phone number
 or short code that you specify has to be associated with your Amazon Pinpoint
account. For best results, specify long codes in E.164 format. */
const originationNumber = "SENDER_NUMBER"; //e.g., +1XXXXXXXXXX

// The recipient's phone number.  For best results, you should specify the phone
 number in E.164 format.
const destinationNumber = "RECEIVER_NUMBER"; //e.g., +1XXXXXXXXXX

// The content of the SMS message.
const message =
  "This message was sent through Amazon Pinpoint " +
```

```
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

/*The Amazon Pinpoint project/application ID to use when you send this message.
Make sure that the SMS channel is enabled for the project or application
that you choose.*/
const projectId = "PINPOINT_PROJECT_ID"; //e.g., XXXXXXXX66e4e9986478cXXXXXXXXX

/* The type of SMS message that you want to send. If you plan to send
time-sensitive content, specify TRANSACTIONAL. If you plan to send
marketing-related content, specify PROMOTIONAL.*/
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
var registeredKeyword = "myKeyword";

/* The sender ID to use when sending the message. Support for sender ID
// varies by country or region. For more information, see
https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-countries.html.*/

var senderId = "MySenderID";

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: projectId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
};

const run = async () => {
```

```
  try {
    const data = await pinClient.send(new SendMessagesCommand(params));
    return data; // For unit tests.
    console.log(
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  } catch (err) {
    console.log(err);
  }
};
run();
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
"use strict";

const AWS = require("aws-sdk");

// The AWS Region that you want to use to send the email. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
// https://docs.aws.amazon.com/pinpoint/latest/apireference/
const aws_region = "us-west-2";

// The "From" address. This address has to be verified in Amazon Pinpoint
// in the region that you use to send email.
const senderAddress = "sender@example.com";

// The address on the "To" line. If your Amazon Pinpoint account is in
// the sandbox, this address also has to be verified.
```

```
var toAddress = "recipient@example.com";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
const appId = "ce796be37f32f178af652b26eexample";

// The subject line of the email.
var subject = "Amazon Pinpoint (AWS SDK for JavaScript in Node.js)";

// The email body for recipients with non-HTML email clients.
var body_text = `Amazon Pinpoint Test (SDK for JavaScript in Node.js)
----------------------------------------------------
This email was sent with Amazon Pinpoint using the AWS SDK for JavaScript in
 Node.js.
For more information, see https:\/\/aws.amazon.com/sdk-for-node-js/`;

// The body of the email for recipients whose email clients support HTML content.
var body_html = `<html>
<head></head>
<body>
  <h1>Amazon Pinpoint Test (SDK for JavaScript in Node.js)</h1>
  <p>This email was sent with
    <a href='https://aws.amazon.com/pinpoint/'>the Amazon Pinpoint API</a> using the
    <a href='https://aws.amazon.com/sdk-for-node-js/'>
      AWS SDK for JavaScript in Node.js</a>.</p>
</body>
</html>`;

// The character encoding the you want to use for the subject line and
// message body of the email.
var charset = "UTF-8";

// Specify that you're using a shared credentials file.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
```

```
var params = {
  ApplicationId: appId,
  MessageRequest: {
    Addresses: {
      [toAddress]: {
        ChannelType: "EMAIL",
      },
    },
    MessageConfiguration: {
      EmailMessage: {
        FromAddress: senderAddress,
        SimpleEmail: {
          Subject: {
            Charset: charset,
            Data: subject,
          },
          HtmlPart: {
            Charset: charset,
            Data: body_html,
          },
          TextPart: {
            Charset: charset,
            Data: body_text,
          },
        },
      },
    },
  },
};

//Try to send the email.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
  } else {
    console.log(
      "Email sent! Message ID: ",
      data["MessageResponse"]["Result"][toAddress]["MessageId"]
    );
  }
});
```

Envie uma mensagem SMS.

```
"use strict";

var AWS = require("aws-sdk");

// The AWS Region that you want to use to send the message. For a list of
// AWS Regions where the Amazon Pinpoint API is available, see
// https://docs.aws.amazon.com/pinpoint/latest/apireference/.
var aws_region = "us-east-1";

// The phone number or short code to send the message from. The phone number
// or short code that you specify has to be associated with your Amazon Pinpoint
// account. For best results, specify long codes in E.164 format.
var originationNumber = "+12065550199";

// The recipient's phone number.  For best results, you should specify the
// phone number in E.164 format.
var destinationNumber = "+14255550142";

// The content of the SMS message.
var message =
  "This message was sent through Amazon Pinpoint " +
  "using the AWS SDK for JavaScript in Node.js. Reply STOP to " +
  "opt out.";

// The Amazon Pinpoint project/application ID to use when you send this message.
// Make sure that the SMS channel is enabled for the project or application
// that you choose.
var applicationId = "ce796be37f32f178af652b26eexample";

// The type of SMS message that you want to send. If you plan to send
// time-sensitive content, specify TRANSACTIONAL. If you plan to send
// marketing-related content, specify PROMOTIONAL.
var messageType = "TRANSACTIONAL";

// The registered keyword associated with the originating short code.
var registeredKeyword = "myKeyword";

// The sender ID to use when sending the message. Support for sender ID
```

```
// varies by country or region. For more information, see
// https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-countries.html
var senderId = "MySenderID";

// Specify that you're using a shared credentials file, and optionally specify
// the profile that you want to use.
var credentials = new AWS.SharedIniFileCredentials({ profile: "default" });
AWS.config.credentials = credentials;

// Specify the region.
AWS.config.update({ region: aws_region });

//Create a new Pinpoint object.
var pinpoint = new AWS.Pinpoint();

// Specify the parameters to pass to the API.
var params = {
  ApplicationId: applicationId,
  MessageRequest: {
    Addresses: {
      [destinationNumber]: {
        ChannelType: "SMS",
      },
    },
    MessageConfiguration: {
      SMSMessage: {
        Body: message,
        Keyword: registeredKeyword,
        MessageType: messageType,
        OriginationNumber: originationNumber,
        SenderId: senderId,
      },
    },
  },
};

//Try to send the message.
pinpoint.sendMessages(params, function (err, data) {
  // If something goes wrong, print an error message.
  if (err) {
    console.log(err.message);
    // Otherwise, show the unique ID for the message.
  } else {
    console.log(
```

```
      "Message sent! " +
        data["MessageResponse"]["Result"][destinationNumber]["StatusMessage"]
    );
  }
});
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for JavaScript da API.

Exemplos do Amazon Redshift usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Redshift.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um cluster

O exemplo de código a seguir mostra como criar um cluster do Amazon Redshift.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Crie o cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { CreateClusterCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME", // Required
  NodeType: "NODE_TYPE", //Required
  MasterUsername: "MASTER_USER_NAME", // Required - must be lowercase
  MasterUserPassword: "MASTER_USER_PASSWORD", // Required - must contain at least
 one uppercase letter, and one number
  ClusterType: "CLUSTER_TYPE", // Required
  IAMRoleARN: "IAM_ROLE_ARN", // Optional - the ARN of an IAM role with permissions
 your cluster needs to access other AWS services on your behalf, such as Amazon S3.
  ClusterSubnetGroupName: "CLUSTER_SUBNET_GROUPNAME", //Optional - the name of a
 cluster subnet group to be associated with this cluster. Defaults to 'default' if
 not specified.
  DBName: "DATABASE_NAME", // Optional - defaults to 'dev' if not specified
  Port: "PORT_NUMBER", // Optional - defaults to '5439' if not specified
};

const run = async () => {
  try {
```

```
    const data = await redshiftClient.send(new CreateClusterCommand(params));
    console.log(
      "Cluster " + data.Cluster.ClusterIdentifier + " successfully created",
    );
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte CreateClustera Referência AWS SDK for JavaScript da API.

Excluir um cluster

O exemplo de código a seguir mostra como excluir um cluster do Amazon Redshift.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Crie o cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { DeleteClusterCommand } from "@aws-sdk/client-redshift";
```

```
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME",
  SkipFinalClusterSnapshot: false,
  FinalClusterSnapshotIdentifier: "CLUSTER_SNAPSHOT_ID",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new DeleteClusterCommand(params));
    console.log("Success, cluster deleted. ", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte DeleteCluster a Referência AWS SDK for JavaScript da API.

Descrever seus clusters

O exemplo de código a seguir mostra como descrever clusters do Amazon Redshift.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
```

```
export { redshiftClient };
```

Descreva seus clusters.

```
// Import required AWS SDK clients and commands for Node.js
import { DescribeClustersCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

const params = {
  ClusterIdentifier: "CLUSTER_NAME",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new DescribeClustersCommand(params));
    console.log("Success", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for JavaScript da API.

Modificar um cluster

O exemplo de código a seguir mostra como modificar um cluster do Amazon Redshift.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { RedshiftClient } = require("@aws-sdk/client-redshift");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const redshiftClient = new RedshiftClient({ region: REGION });
export { redshiftClient };
```

Modifique um cluster.

```
// Import required AWS SDK clients and commands for Node.js
import { ModifyClusterCommand } from "@aws-sdk/client-redshift";
import { redshiftClient } from "./libs/redshiftClient.js";

// Set the parameters
const params = {
  ClusterIdentifier: "CLUSTER_NAME",
  MasterUserPassword: "NEW_MASTER_USER_PASSWORD",
};

const run = async () => {
  try {
    const data = await redshiftClient.send(new ModifyClusterCommand(params));
    console.log("Success was modified.", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter detalhes da API, consulte ModifyClustera Referência AWS SDK for JavaScript da API.

Exemplos do Amazon S3 usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";

// When no region or credentials are provided, the SDK will use the
// region and credentials from the local AWS config.
const client = new S3Client({});

export const helloS3 = async () => {
  const command = new ListBucketsCommand({});

  const { Buckets } = await client.send(command);
  console.log("Buckets: ");
  console.log(Buckets.map((bucket) => bucket.Name).join("\n"));
  return Buckets;
};
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar regras de CORS a um bucket

O exemplo de código a seguir mostra como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione uma regra de CORS.

```
import { PutBucketCorsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// By default, Amazon S3 doesn't allow cross-origin requests. Use this command
// to explicitly allow cross-origin requests.
export const main = async () => {
  const command = new PutBucketCorsCommand({
    Bucket: "test-bucket",
    CORSConfiguration: {
      CORSRules: [
        {
          // Allow all headers to be sent to this bucket.
          AllowedHeaders: ["*"],
          // Allow only GET and PUT methods to be sent to this bucket.
          AllowedMethods: ["GET", "PUT"],
          // Allow only requests from the specified origin.
          AllowedOrigins: ["https://www.example.com"],
          // Allow the entity tag (ETag) header to be returned in the response. The
 ETag header
```

```
          // The entity tag represents a specific version of the object. The ETag
 reflects
          // changes only to the contents of an object, not its metadata.
          ExposeHeaders: ["ETag"],
          // How long the requesting browser should cache the preflight response.
 After
          // this time, the preflight request will have to be made again.
          MaxAgeSeconds: 3600,
        },
      ],
    },
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for JavaScript da API.

Adicionar uma política a um bucket

O exemplo de código a seguir mostra como adicionar uma política a um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione a política.

```
import { PutBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";
```

```
const client = new S3Client({});

export const main = async () => {
  const command = new PutBucketPolicyCommand({
    Policy: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Sid: "AllowGetObject",
          // Allow this particular user to call GetObject on any object in this
 bucket.
          Effect: "Allow",
          Principal: {
            AWS: "arn:aws:iam::ACCOUNT-ID:user/USERNAME",
          },
          Action: "s3:GetObject",
          Resource: "arn:aws:s3:::BUCKET-NAME/*",
        },
      ],
    }),
    // Apply the preceding policy to this bucket.
    Bucket: "BUCKET-NAME",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for JavaScript da API.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie o objeto.

```
import { S3Client, CopyObjectCommand } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new CopyObjectCommand({
    CopySource: "SOURCE_BUCKET/SOURCE_OBJECT_KEY",
    Bucket: "DESTINATION_BUCKET",
    Key: "NEW_OBJECT_KEY",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for JavaScript da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o bucket.

```
import { CreateBucketCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new CreateBucketCommand({
    // The name of the bucket. Bucket names are unique and have several other
 constraints.
    // See https://docs.aws.amazon.com/AmazonS3/latest/userguide/
bucketnamingrules.html
    Bucket: "bucket-name",
  });

  try {
    const { Location } = await client.send(command);
    console.log(`Bucket created with location ${Location}`);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for JavaScript da API.

Excluir uma política de um bucket

O exemplo de código a seguir mostra como excluir uma política de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a política de bucket.

```
import { DeleteBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// This will remove the policy from the bucket.
export const main = async () => {
  const command = new DeleteBucketPolicyCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for JavaScript da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o bucket.

```
import { DeleteBucketCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Delete a bucket.
export const main = async () => {
  const command = new DeleteBucketCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for JavaScript da API.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto.

```
import { DeleteObjectCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new DeleteObjectCommand({
    Bucket: "test-bucket",
    Key: "test-key.txt",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for JavaScript da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua vários objetos.

```
import { DeleteObjectsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new DeleteObjectsCommand({
    Bucket: "test-bucket",
    Delete: {
      Objects: [{ Key: "object1.txt" }, { Key: "object2.txt" }],
    },
  });

  try {
    const { Deleted } = await client.send(command);
    console.log(
      `Successfully deleted ${Deleted.length} objects from S3 bucket. Deleted
 objects:`,
    );
    console.log(Deleted.map((d) => ` • ${d.Key}`).join("\n"));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for JavaScript da API.

Excluir a configuração de site de um bucket

O exemplo de código a seguir mostra como excluir a configuração de site de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua a configuração de site do bucket.

```
import { DeleteBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Disable static website hosting on the bucket.
export const main = async () => {
  const command = new DeleteBucketWebsiteCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for JavaScript da API.

Obter regras de CORS para um bucket

O exemplos de código a seguir mostra como obter regras de compartilhamento de recursos de origem cruzada (CORS) para um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de CORS para o bucket.

```
import { GetBucketCorsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketCorsCommand({
    Bucket: "test-bucket",
  });

  try {
    const { CORSRules } = await client.send(command);
    CORSRules.forEach((cr, i) => {
      console.log(
        `\nCORSRule ${i + 1}`,
        `\n${"-".repeat(10)}`,
        `\nAllowedHeaders: ${cr.AllowedHeaders.join(" ")}`,
        `\nAllowedMethods: ${cr.AllowedMethods.join(" ")}`,
        `\nAllowedOrigins: ${cr.AllowedOrigins.join(" ")}`,
        `\nExposeHeaders: ${cr.ExposeHeaders.join(" ")}`,
        `\nMaxAgeSeconds: ${cr.MaxAgeSeconds}`,
      );
    });
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for JavaScript da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Baixe o objeto.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetObjectCommand({
    Bucket: "test-bucket",
    Key: "hello-s3.txt",
  });

  try {
    const response = await client.send(command);
    // The Body object also has 'transformToByteArray' and 'transformToWebStream'
 methods.
    const str = await response.Body.transformToString();
    console.log(str);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for JavaScript da API.

Obter a ACL de um bucket

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha as permissões de ACL.

```
import { GetBucketAclCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketAclCommand({
    Bucket: "test-bucket",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for JavaScript da API.

Obter a política de um bucket

O exemplo de código a seguir mostra como obter a política de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a política de bucket.

```
import { GetBucketPolicyCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketPolicyCommand({
    Bucket: "test-bucket",
  });

  try {
    const { Policy } = await client.send(command);
    console.log(JSON.parse(Policy));
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for JavaScript da API.

Obter a configuração do site de um bucket

O exemplo de código a seguir mostra como obter a configuração de site de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha a configuração do site.

```
import { GetBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new GetBucketWebsiteCommand({
    Bucket: "test-bucket",
  });

  try {
    const { ErrorDocument, IndexDocument } = await client.send(command);
    console.log(
      `Your bucket is set up to host a website. It has an error document:`,
      `${ErrorDocument.Key}, and an index document: ${IndexDocument.Suffix}.`,
    );
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte GetBucketWebsitea Referência AWS SDK for JavaScript da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os buckets.

```
import { ListBucketsCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new ListBucketsCommand({});

  try {
    const { Owner, Buckets } = await client.send(command);
    console.log(
      `${Owner.DisplayName} owns ${Buckets.length} bucket${
        Buckets.length === 1 ? "" : "s"
      }:`,
    );
    console.log(`${Buckets.map((b) => ` • ${b.Name}`).join("\n")}`);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for JavaScript da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste todos os objetos no bucket. Se houver mais de um objeto, IsTruncated NextContinuationToken ele será usado para iterar a lista completa.

```
import {
  S3Client,
  // This command supersedes the ListObjectsCommand and is the recommended way to
 list objects.
  ListObjectsV2Command,
} from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new ListObjectsV2Command({
    Bucket: "my-bucket",
    // The default and maximum number of keys returned is 1000. This limits it to
    // one for demonstration purposes.
    MaxKeys: 1,
  });

  try {
    let isTruncated = true;

    console.log("Your bucket contains the following objects:\n");
    let contents = "";

    while (isTruncated) {
      const { Contents, IsTruncated, NextContinuationToken } =
        await client.send(command);
      const contentsList = Contents.map((c) => ` • ${c.Key}`).join("\n");
      contents += contentsList + "\n";
      isTruncated = IsTruncated;
      command.input.ContinuationToken = NextContinuationToken;
    }
```

```
    console.log(contents);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for JavaScript da API.

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Coloque a ACL do bucket.

```
import {
  PutBucketAclCommand,
  GetBucketAclCommand,
  S3Client,
} from "@aws-sdk/client-s3";

const client = new S3Client({});

// Most Amazon S3 use cases don't require the use of access control lists (ACLs).
// We recommend that you disable ACLs, except in unusual circumstances where
// you need to control access for each object individually.
// Consider a policy instead. For more information see https://docs.aws.amazon.com/
AmazonS3/latest/userguide/bucket-policies.html.
export const main = async () => {
  // Grant a user READ access to a bucket.
  const command = new PutBucketAclCommand({
```

```
    Bucket: "test-bucket",
    AccessControlPolicy: {
      Grants: [
        {
          Grantee: {
            // The canonical ID of the user. This ID is an obfuscated form of your
 AWS account number.
            // It's unique to Amazon S3 and can't be found elsewhere.
            // For more information, see https://docs.aws.amazon.com/AmazonS3/
latest/userguide/finding-canonical-user-id.html.
            ID: "canonical-id-1",
            Type: "CanonicalUser",
          },
          // One of FULL_CONTROL | READ | WRITE | READ_ACP | WRITE_ACP
          // https://docs.aws.amazon.com/AmazonS3/latest/API/
API_Grant.html#AmazonS3-Type-Grant-Permission
          Permission: "FULL_CONTROL",
        },
      ],
      Owner: {
        ID: "canonical-id-2",
      },
    },
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for JavaScript da API.

Definir a configuração de site de um bucket

O exemplo de código a seguir mostra como definir a configuração de site de um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina a configuração do site.

```
import { PutBucketWebsiteCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

// Set up a bucket as a static website.
// The bucket needs to be publicly accessible.
export const main = async () => {
  const command = new PutBucketWebsiteCommand({
    Bucket: "test-bucket",
    WebsiteConfiguration: {
      ErrorDocument: {
        // The object key name to use when a 4XX class error occurs.
        Key: "error.html",
      },
      IndexDocument: {
        // A suffix that is appended to a request that is for a directory.
        Suffix: "index.html",
      },
    },
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for JavaScript da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue o objeto.

```
import { PutObjectCommand, S3Client } from "@aws-sdk/client-s3";

const client = new S3Client({});

export const main = async () => {
  const command = new PutObjectCommand({
    Bucket: "test-bucket",
    Key: "hello-s3.txt",
    Body: "Hello S3!",
  });

  try {
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for JavaScript da API.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um URL pré-assinado para carregar um objeto em um bucket.

```
import https from "https";
import { PutObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { fromIni } from "@aws-sdk/credential-providers";
import { HttpRequest } from "@smithy/protocol-http";
import {
  getSignedUrl,
  S3RequestPresigner,
} from "@aws-sdk/s3-request-presigner";
import { parseUrl } from "@smithy/url-parser";
import { formatUrl } from "@aws-sdk/util-format-url";
import { Hash } from "@smithy/hash-node";

const createPresignedUrlWithoutClient = async ({ region, bucket, key }) => {
  const url = parseUrl(`https://${bucket}.s3.${region}.amazonaws.com/${key}`);
  const presigner = new S3RequestPresigner({
    credentials: fromIni(),
    region,
    sha256: Hash.bind(null, "sha256"),
  });

  const signedUrlObject = await presigner.presign(
    new HttpRequest({ ...url, method: "PUT" }),
  );
  return formatUrl(signedUrlObject);
};
```

```
const createPresignedUrlWithClient = ({ region, bucket, key }) => {
  const client = new S3Client({ region });
  const command = new PutObjectCommand({ Bucket: bucket, Key: key });
  return getSignedUrl(client, command, { expiresIn: 3600 });
};

function put(url, data) {
  return new Promise((resolve, reject) => {
    const req = https.request(
      url,
      { method: "PUT", headers: { "Content-Length": new Blob([data]).size } },
      (res) => {
        let responseBody = "";
        res.on("data", (chunk) => {
          responseBody += chunk;
        });
        res.on("end", () => {
          resolve(responseBody);
        });
      },
    );
    req.on("error", (err) => {
      reject(err);
    });
    req.write(data);
    req.end();
  });
}

export const main = async () => {
  const REGION = "us-east-1";
  const BUCKET = "example_bucket";
  const KEY = "example_file.txt";

  // There are two ways to generate a presigned URL.
  // 1. Use createPresignedUrl without the S3 client.
  // 2. Use getSignedUrl in conjunction with the S3 client and GetObjectCommand.
  try {
    const noClientUrl = await createPresignedUrlWithoutClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });
```

```
    const clientUrl = await createPresignedUrlWithClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    // After you get the presigned URL, you can provide your own file
    // data. Refer to put() above.
    console.log("Calling PUT using presigned URL without client");
    await put(noClientUrl, "Hello World");

    console.log("Calling PUT using presigned URL with client");
    await put(clientUrl, "Hello World");

    console.log("\nDone. Check your S3 console.");
  } catch (err) {
    console.error(err);
  }
};
```

Crie um URL pré-assinado para baixar um objeto de um bucket.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { fromIni } from "@aws-sdk/credential-providers";
import { HttpRequest } from "@smithy/protocol-http";
import {
  getSignedUrl,
  S3RequestPresigner,
} from "@aws-sdk/s3-request-presigner";
import { parseUrl } from "@smithy/url-parser";
import { formatUrl } from "@aws-sdk/util-format-url";
import { Hash } from "@smithy/hash-node";

const createPresignedUrlWithoutClient = async ({ region, bucket, key }) => {
  const url = parseUrl(`https://${bucket}.s3.${region}.amazonaws.com/${key}`);
  const presigner = new S3RequestPresigner({
    credentials: fromIni(),
    region,
    sha256: Hash.bind(null, "sha256"),
  });

  const signedUrlObject = await presigner.presign(new HttpRequest(url));
```

```
  return formatUrl(signedUrlObject);
};

const createPresignedUrlWithClient = ({ region, bucket, key }) => {
  const client = new S3Client({ region });
  const command = new GetObjectCommand({ Bucket: bucket, Key: key });
  return getSignedUrl(client, command, { expiresIn: 3600 });
};

export const main = async () => {
  const REGION = "us-east-1";
  const BUCKET = "example_bucket";
  const KEY = "example_file.jpg";

  try {
    const noClientUrl = await createPresignedUrlWithoutClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    const clientUrl = await createPresignedUrlWithClient({
      region: REGION,
      bucket: BUCKET,
      key: KEY,
    });

    console.log("Presigned URL without client");
    console.log(noClientUrl);
    console.log("\n");

    console.log("Presigned URL with client");
    console.log(clientUrl);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

Criar uma página da web que oferece uma lista de objetos do Amazon S3

O exemplo de código a seguir mostra como listar objetos do Amazon S3 em uma página da web.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O código a seguir é o componente relevante do React que faz chamadas para o AWS SDK. Uma versão executável do aplicativo contendo esse componente pode ser encontrada no link anterior GitHub .

```
import { useEffect, useState } from "react";
import {
  ListObjectsCommand,
  ListObjectsCommandOutput,
  S3Client,
} from "@aws-sdk/client-s3";
import { fromCognitoIdentityPool } from "@aws-sdk/credential-providers";
import "./App.css";

function App() {
  const [objects, setObjects] = useState<
    Required<ListObjectsCommandOutput>["Contents"]
  >([]);

  useEffect(() => {
    const client = new S3Client({
      region: "us-east-1",
      // Unless you have a public bucket, you'll need access to a private bucket.
      // One way to do this is to create an Amazon Cognito identity pool, attach a
 role to the pool,
      // and grant the role access to the 's3:GetObject' action.
      //
      // You'll also need to configure the CORS settings on the bucket to allow
 traffic from
      // this example site. Here's an example configuration that allows all origins.
 Don't
```

```
      // do this in production.
      //[
      //  {
      //    "AllowedHeaders": ["*"],
      //    "AllowedMethods": ["GET"],
      //    "AllowedOrigins": ["*"],
      //    "ExposeHeaders": [],
      //  },
      //]
      //
      credentials: fromCognitoIdentityPool({
        clientConfig: { region: "us-east-1" },
        identityPoolId: "<YOUR_IDENTITY_POOL_ID>",
      }),
    });
    const command = new ListObjectsCommand({ Bucket: "bucket-name" });
    client.send(command).then(({ Contents }) => setObjects(Contents || []));
  }, []);

  return (
    <div className="App">
      {objects.map((o) => (
        <div key={o.ETag}>{o.Key}</div>
      ))}
    </div>
  );
}

export default App;
```

- Para obter detalhes da API, consulte ListObjectsa Referência AWS SDK for JavaScript da API.

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.

- Exclua os objetos do bucket e o bucket.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Primeiro, importe todos os módulos necessários.

```
// Used to check if currently running file is this file.
import { fileURLToPath } from "url";
import { readdirSync, readFileSync, writeFileSync } from "fs";

// Local helper utils.
import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { wrapText } from "@aws-sdk-examples/libs/utils/util-string.js";

import {
  S3Client,
  CreateBucketCommand,
  PutObjectCommand,
  ListObjectsCommand,
  CopyObjectCommand,
  GetObjectCommand,
  DeleteObjectsCommand,
  DeleteBucketCommand,
} from "@aws-sdk/client-s3";
```

As importações anteriores fazem referência a alguns utilitários auxiliares. Esses utilitários são locais para o GitHub repositório vinculado no início desta seção. Para sua referência, consulte as implementações a seguir desses utilitários.

```
export const dirnameFromMetaUrl = (metaUrl) =>
  fileURLToPath(new URL(".", metaUrl));

import { select, input, confirm, checkbox } from "@inquirer/prompts";
```

```
export class Prompter {
  /**
   * @param {{ message: string, choices: { name: string, value: string }[]}} options
   */
  select(options) {
    return select(options);
  }

  /**
   * @param {{ message: string }} options
   */
  input(options) {
    return input(options);
  }

  /**
   * @param {string} prompt
   */
  checkContinue = async (prompt = "") => {
    const prefix = prompt && prompt + " ";
    let ok = await this.confirm({
      message: `${prefix}Continue?`,
    });
    if (!ok) throw new Error("Exiting...");
  };

  /**
   * @param {{ message: string }} options
   */
  confirm(options) {
    return confirm(options);
  }

  /**
   * @param {{ message: string, choices: { name: string, value: string }[]}} options
   */
  checkbox(options) {
    return checkbox(options);
  }
}

export const wrapText = (text, char = "=") => {
  const rule = char.repeat(80);
```

```
  return `${rule}\n    ${text}\n${rule}\n`;
};
```

Os objetos no S3 são armazenados em “buckets”. Vamos definir uma função para criar um bucket.

```
export const createBucket = async () => {
  const bucketName = await prompter.input({
    message: "Enter a bucket name. Bucket names must be globally unique:",
  });
  const command = new CreateBucketCommand({ Bucket: bucketName });
  await s3Client.send(command);
  console.log("Bucket created successfully.\n");
  return bucketName;
};
```

Os buckets contêm “objetos”. Essa função faz upload do conteúdo de um diretório para seu bucket como objetos.

```
export const uploadFilesToBucket = async ({ bucketName, folderPath }) => {
  console.log(`Uploading files from ${folderPath}\n`);
  const keys = readdirSync(folderPath);
  const files = keys.map((key) => {
    const filePath = `${folderPath}/${key}`;
    const fileContent = readFileSync(filePath);
    return {
      Key: key,
      Body: fileContent,
    };
  });

  for (let file of files) {
    await s3Client.send(
      new PutObjectCommand({
        Bucket: bucketName,
        Body: file.Body,
        Key: file.Key,
      }),
    );
    console.log(`${file.Key} uploaded successfully.`);
  }
```

```
};
```

Depois de fazer upload dos objetos, confira se eles foram carregados corretamente. Você pode usar ListObjects para isso. Você usará a propriedade “Key”, mas também há outras propriedades úteis na resposta.

```
export const listFilesInBucket = async ({ bucketName }) => {
  const command = new ListObjectsCommand({ Bucket: bucketName });
  const { Contents } = await s3Client.send(command);
  const contentsList = Contents.map((c) => ` • ${c.Key}`).join("\n");
  console.log("\nHere's a list of files in the bucket:");
  console.log(contentsList + "\n");
};
```

Às vezes é necessário copiar um objeto de um bucket em outro. Use o CopyObject comando para isso.

```
export const copyFileFromBucket = async ({ destinationBucket }) => {
  const proceed = await prompter.confirm({
    message: "Would you like to copy an object from another bucket?",
  });

  if (!proceed) {
    return;
  } else {
    const copy = async () => {
      try {
        const sourceBucket = await prompter.input({
          message: "Enter source bucket name:",
        });
        const sourceKey = await prompter.input({
          message: "Enter source key:",
        });
        const destinationKey = await prompter.input({
          message: "Enter destination key:",
        });

        const command = new CopyObjectCommand({
          Bucket: destinationBucket,
          CopySource: `${sourceBucket}/${sourceKey}`,
```

```
          Key: destinationKey,
        });
        await s3Client.send(command);
        await copyFileFromBucket({ destinationBucket });
      } catch (err) {
        console.error(`Copy error.`);
        console.error(err);
        const retryAnswer = await prompter.confirm({ message: "Try again?" });
        if (retryAnswer) {
          await copy();
        }
      }
    };
    await copy();
  }
};
```

Não há um método de SDK para obter vários objetos de um bucket. Em vez disso, você criará uma lista de objetos para baixar e iterar sobre eles.

```
export const downloadFilesFromBucket = async ({ bucketName }) => {
  const { Contents } = await s3Client.send(
    new ListObjectsCommand({ Bucket: bucketName }),
  );
  const path = await prompter.input({
    message: "Enter destination path for files:",
  });

  for (let content of Contents) {
    const obj = await s3Client.send(
      new GetObjectCommand({ Bucket: bucketName, Key: content.Key }),
    );
    writeFileSync(
      `${path}/${content.Key}`,
      await obj.Body.transformToByteArray(),
    );
  }
  console.log("Files downloaded successfully.\n");
};
```

É hora de limpar seus recursos. Um bucket deve estar vazio para poder ser excluído. Essas duas funções esvaziam e excluem o bucket.

```
export const emptyBucket = async ({ bucketName }) => {
  const listObjectsCommand = new ListObjectsCommand({ Bucket: bucketName });
  const { Contents } = await s3Client.send(listObjectsCommand);
  const keys = Contents.map((c) => c.Key);

  const deleteObjectsCommand = new DeleteObjectsCommand({
    Bucket: bucketName,
    Delete: { Objects: keys.map((key) => ({ Key: key })) },
  });
  await s3Client.send(deleteObjectsCommand);
  console.log(`${bucketName} emptied successfully.\n`);
};

export const deleteBucket = async ({ bucketName }) => {
  const command = new DeleteBucketCommand({ Bucket: bucketName });
  await s3Client.send(command);
  console.log(`${bucketName} deleted successfully.\n`);
};
```

A função “principal” reúne tudo. Se você executar esse arquivo diretamente, a função principal será chamada.

```
const main = async () => {
  const OBJECT_DIRECTORY = `${dirnameFromMetaUrl(
    import.meta.url,
  )}../../../../resources/sample_files/.sample_media`;

  try {
    console.log(wrapText("Welcome to the Amazon S3 getting started example."));
    console.log("Let's create a bucket.");
    const bucketName = await createBucket();
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("File upload."));
    console.log(
      "I have some default files ready to go. You can edit the source code to
 provide your own.",
    );
    await uploadFilesToBucket({
```

```
      bucketName,
      folderPath: OBJECT_DIRECTORY,
    });

    await listFilesInBucket({ bucketName });
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("Copy files."));
    await copyFileFromBucket({ destinationBucket: bucketName });
    await listFilesInBucket({ bucketName });
    await prompter.confirm({ message: continueMessage });

    console.log(wrapText("Download files."));
    await downloadFilesFromBucket({ bucketName });

    console.log(wrapText("Clean up."));
    await emptyBucket({ bucketName });
    await deleteBucket({ bucketName });
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um arquivo grande.

```
import {
  CreateMultipartUploadCommand,
  UploadPartCommand,
  CompleteMultipartUploadCommand,
  AbortMultipartUploadCommand,
  S3Client,
} from "@aws-sdk/client-s3";

const twentyFiveMB = 25 * 1024 * 1024;

export const createString = (size = twentyFiveMB) => {
  return "x".repeat(size);
};

export const main = async () => {
  const s3Client = new S3Client({});
  const bucketName = "test-bucket";
  const key = "multipart.txt";
  const str = createString();
  const buffer = Buffer.from(str, "utf8");

  let uploadId;

  try {
    const multipartUpload = await s3Client.send(
      new CreateMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
      }),
    );

    uploadId = multipartUpload.UploadId;
```

```
    const uploadPromises = [];
    // Multipart uploads require a minimum size of 5 MB per part.
    const partSize = Math.ceil(buffer.length / 5);

    // Upload each part.
    for (let i = 0; i < 5; i++) {
      const start = i * partSize;
      const end = start + partSize;
      uploadPromises.push(
        s3Client
          .send(
            new UploadPartCommand({
              Bucket: bucketName,
              Key: key,
              UploadId: uploadId,
              Body: buffer.subarray(start, end),
              PartNumber: i + 1,
            }),
          )
          .then((d) => {
            console.log("Part", i + 1, "uploaded");
            return d;
          }),
      );
    }

    const uploadResults = await Promise.all(uploadPromises);

    return await s3Client.send(
      new CompleteMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
        UploadId: uploadId,
        MultipartUpload: {
          Parts: uploadResults.map(({ ETag }, i) => ({
            ETag,
            PartNumber: i + 1,
          })),
        },
      }),
    );

    // Verify the output by downloading the file from the Amazon Simple Storage
  Service (Amazon S3) console.
```

```
    // Because the output is a 25 MB string, text editors might struggle to open the
 file.
  } catch (err) {
    console.error(err);

    if (uploadId) {
      const abortCommand = new AbortMultipartUploadCommand({
        Bucket: bucketName,
        Key: key,
        UploadId: uploadId,
      });

      await s3Client.send(abortCommand);
    }
  }
};
```

Baixe um arquivo grande.

```
import { GetObjectCommand, S3Client } from "@aws-sdk/client-s3";
import { createWriteStream } from "fs";

const s3Client = new S3Client({});
const oneMB = 1024 * 1024;

export const getObjectRange = ({ bucket, key, start, end }) => {
  const command = new GetObjectCommand({
    Bucket: bucket,
    Key: key,
    Range: `bytes=${start}-${end}`,
  });

  return s3Client.send(command);
};

export const getRangeAndLength = (contentRange) => {
  const [range, length] = contentRange.split("/");
  const [start, end] = range.split("-");
  return {
    start: parseInt(start),
    end: parseInt(end),
    length: parseInt(length),
```

```
  };
};

export const isComplete = ({ end, length }) => end === length - 1;

// When downloading a large file, you might want to break it down into
// smaller pieces. Amazon S3 accepts a Range header to specify the start
// and end of the byte range to be downloaded.
const downloadInChunks = async ({ bucket, key }) => {
  const writeStream = createWriteStream(
    fileURLToPath(new URL(`./${key}`, import.meta.url))
  ).on("error", (err) => console.error(err));

  let rangeAndLength = { start: -1, end: -1, length: -1 };

  while (!isComplete(rangeAndLength)) {
    const { end } = rangeAndLength;
    const nextRange = { start: end + 1, end: end + oneMB };

    console.log(`Downloading bytes ${nextRange.start} to ${nextRange.end}`);

    const { ContentRange, Body } = await getObjectRange({
      bucket,
      key,
      ...nextRange,
    });

    writeStream.write(await Body.transformToByteArray());
    rangeAndLength = getRangeAndLength(ContentRange);
  }
};

export const main = async () => {
  await downloadInChunks({
    bucket: "my-cool-bucket",
    key: "my-cool-object.txt",
  });
};
```

Exemplos do S3 Glacier usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o S3 Glacier.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um vault

O exemplo de código a seguir mostra como criar um vault (cofre) do Amazon S3 Glacier.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Criar o cofre.

```
// Load the SDK for JavaScript
import { CreateVaultCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME
const params = { vaultName: vaultname };

const run = async () => {
  try {
    const data = await glacierClient.send(new CreateVaultCommand(params));
    console.log("Success, vault created!");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error");
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
// Call Glacier to create the vault
glacier.createVault({ vaultName: "YOUR_VAULT_NAME" }, function (err) {
```

```
  if (!err) {
    console.log("Created vault!");
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for JavaScript da API.

Baixe um arquivo em um cofre

O exemplo de código a seguir mostra como fazer upload de um arquivo em um cofre do Amazon S3 Glacier.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { GlacierClient } = require("@aws-sdk/client-glacier");
// Set the AWS Region.
const REGION = "REGION";
//Set the Redshift Service Object
const glacierClient = new GlacierClient({ region: REGION });
export { glacierClient };
```

Carregue o arquivo.

```
// Load the SDK for JavaScript
import { UploadArchiveCommand } from "@aws-sdk/client-glacier";
import { glacierClient } from "./libs/glacierClient.js";

// Set the parameters
const vaultname = "VAULT_NAME"; // VAULT_NAME
```

```
// Create a new service object and buffer
const buffer = new Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer
const params = { vaultName: vaultname, body: buffer };

const run = async () => {
  try {
    const data = await glacierClient.send(new UploadArchiveCommand(params));
    console.log("Archive ID", data.archiveId);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error uploading archive!", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
// Load the SDK for JavaScript
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create a new service object and buffer
var glacier = new AWS.Glacier({ apiVersion: "2012-06-01" });
buffer = Buffer.alloc(2.5 * 1024 * 1024); // 2.5MB buffer

var params = { vaultName: "YOUR_VAULT_NAME", body: buffer };
// Call Glacier to upload the archive.
glacier.uploadArchive(params, function (err, data) {
  if (err) {
    console.log("Error uploading archive!", err);
```

```
  } else {
    console.log("Archive ID", data.archiveId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for JavaScript da API.

SageMaker exemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com SageMaker.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá SageMaker

O exemplo de código a seguir mostra como começar a usar o SageMaker.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  SageMakerClient,
```

```
  ListNotebookInstancesCommand,
} from "@aws-sdk/client-sagemaker";

const client = new SageMakerClient({
  region: "us-west-2",
});

export const helloSagemaker = async () => {
  const command = new ListNotebookInstancesCommand({ MaxResults: 5 });

  const response = await client.send(command);
  console.log(
    "Hello Amazon SageMaker! Let's list some of your notebook instances:",
  );

  const instances = response.NotebookInstances || [];

  if (instances.length === 0) {
    console.log(
      "• No notebook instances found. Try creating one in the AWS Management Console
 or with the CreateNotebookInstanceCommand.",
    );
  } else {
    console.log(
      instances
        .map(
          (i) =>
            `• Instance: ${i.NotebookInstanceName}\n  Arn:${
              i.NotebookInstanceArn
            } \n  Creation Date: ${i.CreationTime.toISOString()}`,
        )
        .join("\n"),
    );
  }

  return response;
};
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Criar um pipeline

O exemplo de código a seguir mostra como criar ou atualizar um pipeline em SageMaker.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma função que cria um SageMaker pipeline usando uma definição JSON fornecida localmente.

```
/**
 * Create the Amazon SageMaker pipeline using a JSON pipeline definition. The
 definition
 * can also be provided as an Amazon S3 object using PipelineDefinitionS3Location.
 * @param {{roleArn: string, name: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function createSagemakerPipeline({
  // Assumes an AWS IAM role has been created for this pipeline.
  roleArn,
  name,
  // Assumes an AWS Lambda function has been created for this pipeline.
  functionArn,
  sagemakerClient,
}) {
  const pipelineDefinition = readFileSync(
    // dirnameFromMetaUrl is a local utility function. You can find its
 implementation
    // on GitHub.
    `${dirnameFromMetaUrl(
      import.meta.url,
    )}../../../../../workflows/sagemaker_pipelines/resources/
GeoSpatialPipeline.json`,
```

```
  )
    .toString()
    .replace(/\*FUNCTION_ARN\*/g, functionArn);

  const { PipelineArn } = await sagemakerClient.send(
    new CreatePipelineCommand({
      PipelineName: name,
      PipelineDefinition: pipelineDefinition,
      RoleArn: roleArn,
    }),
  );

  return {
    arn: PipelineArn,
    cleanUp: async () => {
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
    },
  };
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreatePipeline
  - UpdatePipeline

Excluir um pipeline

O exemplo de código a seguir mostra como excluir um pipeline em SageMaker.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

A sintaxe para excluir um SageMaker pipeline. Esse código faz parte de uma função maior. Consulte “Criar um pipeline” ou o GitHub repositório para obter mais contexto.

```
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for JavaScript da API.

Descrever uma execução de pipeline

O exemplo de código a seguir mostra como descrever a execução de um pipeline em SageMaker.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Aguarde até que a execução de um SageMaker pipeline seja bem-sucedida, falhe ou pare.

```
/**
 * Poll the executing pipeline until the status is 'SUCCEEDED', 'STOPPED', or
 'FAILED'.
 * @param {{ arn: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function waitForPipelineComplete({ arn, sagemakerClient }) {
  const command = new DescribePipelineExecutionCommand({
    PipelineExecutionArn: arn,
  });

  let complete = false;
  let intervalInSeconds = 15;
  const COMPLETION_STATUSES = [
    PipelineExecutionStatus.FAILED,
    PipelineExecutionStatus.STOPPED,
```

```
    PipelineExecutionStatus.SUCCEEDED,
  ];

  do {
    const { PipelineExecutionStatus: status, FailureReason } =
      await sagemakerClient.send(command);

    complete = COMPLETION_STATUSES.includes(status);

    if (!complete) {
      console.log(
        `Pipeline is ${status}. Waiting ${intervalInSeconds} seconds before checking
 again.`,
      );
      await wait(intervalInSeconds);
    } else if (status === PipelineExecutionStatus.FAILED) {
      throw new Error(`Pipeline failed because: ${FailureReason}`);
    } else if (status === PipelineExecutionStatus.STOPPED) {
      throw new Error(`Pipeline was forcefully stopped.`);
    } else {
      console.log(`Pipeline execution ${status}.`);
    }
  } while (!complete);
}
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for JavaScript da API.

Executar pipeline

O exemplo de código a seguir mostra como iniciar a execução de um pipeline em SageMaker.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicie a execução de um SageMaker pipeline.

```
/**
 * Start the execution of the Amazon SageMaker pipeline. Parameters that are
 * passed in are used in the AWS Lambda function.
 * @param {{
 *   name: string,
 *   sagemakerClient: import('@aws-sdk/client-sagemaker').SageMakerClient,
 *   roleArn: string,
 *   queueUrl: string,
 *   s3InputBucketName: string,
 * }} props
 */
export async function startPipelineExecution({
  sagemakerClient,
  name,
  bucketName,
  roleArn,
  queueUrl,
}) {
  /**
   * The Vector Enrichment Job requests CSV data. This configuration points to a CSV
   * file in an Amazon S3 bucket.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobInputConfig}
   */
  const inputConfig = {
    DataSourceConfig: {
      S3Data: {
        S3Uri: `s3://${bucketName}/input/sample_data.csv`,
      },
    },
    DocumentType: VectorEnrichmentJobDocumentType.CSV,
  };

  /**
   * The Vector Enrichment Job adds additional data to the source CSV. This
 configuration points
   * to an Amazon S3 prefix where the output will be stored.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").ExportVectorEnrichmentJobOutputConfig}
   */
  const outputConfig = {
    S3Data: {
      S3Uri: `s3://${bucketName}/output/`,
```

```
    },
  };

  /**
   * This job will be a Reverse Geocoding Vector Enrichment Job. Reverse Geocoding
 requires
   * latitude and longitude values.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobConfig}
   */
  const jobConfig = {
    ReverseGeocodingConfig: {
      XAttributeName: "Longitude",
      YAttributeName: "Latitude",
    },
  };

  const { PipelineExecutionArn } = await sagemakerClient.send(
    new StartPipelineExecutionCommand({
      PipelineName: name,
      PipelineExecutionDisplayName: `${name}-example-execution`,
      PipelineParameters: [
        { Name: "parameter_execution_role", Value: roleArn },
        { Name: "parameter_queue_url", Value: queueUrl },
        {
          Name: "parameter_vej_input_config",
          Value: JSON.stringify(inputConfig),
        },
        {
          Name: "parameter_vej_export_config",
          Value: JSON.stringify(outputConfig),
        },
        {
          Name: "parameter_step_1_vej_config",
          Value: JSON.stringify(jobConfig),
        },
      ],
    }),
  );

  return {
    arn: PipelineExecutionArn,
  };
}
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for JavaScript da API.

Cenários

Iniciar com trabalhos geoespaciais e pipelines

O código de exemplo a seguir mostra como:

- Configurar recursos para um pipeline.
- Configurar um pipeline que execute um trabalho geoespacial.
- Inicie a execução de um pipeline.
- Monitorar o status da execução.
- Ver saída do pipeline.
- Limpe os recursos.

Para obter mais informações, consulte Criar e executar SageMaker pipelines usando AWS SDKs no Community.aws.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O trecho do arquivo a seguir contém funções que usam o SageMaker cliente para gerenciar um pipeline.

```
import { readFileSync } from "fs";

import {
  CreateRoleCommand,
  DeleteRoleCommand,
  CreatePolicyCommand,
  DeletePolicyCommand,
```

```
  AttachRolePolicyCommand,
  DetachRolePolicyCommand,
} from "@aws-sdk/client-iam";

import {
  PublishLayerVersionCommand,
  DeleteLayerVersionCommand,
  CreateFunctionCommand,
  Runtime,
  DeleteFunctionCommand,
  CreateEventSourceMappingCommand,
  DeleteEventSourceMappingCommand,
} from "@aws-sdk/client-lambda";

import {
  PutObjectCommand,
  CreateBucketCommand,
  DeleteBucketCommand,
  paginateListObjectsV2,
  DeleteObjectCommand,
  GetObjectCommand,
  ListObjectsV2Command,
} from "@aws-sdk/client-s3";

import {
  CreatePipelineCommand,
  DeletePipelineCommand,
  DescribePipelineExecutionCommand,
  PipelineExecutionStatus,
  StartPipelineExecutionCommand,
} from "@aws-sdk/client-sagemaker";

import { VectorEnrichmentJobDocumentType } from "@aws-sdk/client-sagemaker-
geospatial";

import {
  CreateQueueCommand,
  DeleteQueueCommand,
  GetQueueAttributesCommand,
} from "@aws-sdk/client-sqs";

import { dirnameFromMetaUrl } from "@aws-sdk-examples/libs/utils/util-fs.js";
import { retry, wait } from "@aws-sdk-examples/libs/utils/util-timers.js";
```

```
/**
 * Create the AWS IAM role that will be assumed by AWS Lambda.
 * @param {{ name: string, iamClient: import('@aws-sdk/client-iam').IAMClient }}
 props
 */
export async function createLambdaExecutionRole({ name, iamClient }) {
  const { Role } = await iamClient.send(
    new CreateRoleCommand({
      RoleName: name,
      AssumeRolePolicyDocument: JSON.stringify({
        Version: "2012-10-17",
        Statement: [
          {
            Effect: "Allow",
            Action: ["sts:AssumeRole"],
            Principal: { Service: ["lambda.amazonaws.com"] },
          },
        ],
      }),
    }),
  );

  return {
    arn: Role.Arn,
    cleanUp: async () => {
      await iamClient.send(new DeleteRoleCommand({ RoleName: name }));
    },
  };
}

/**
 * Create an AWS IAM policy that will be attached to the AWS IAM role assumed by the
 AWS Lambda function.
 * The policy grants permission to work with Amazon SQS, Amazon CloudWatch, and
 Amazon SageMaker.
 * @param {{name: string, iamClient: import('@aws-sdk/client-iam').IAMClient,
 pipelineExecutionRoleArn: string}} props
 */
export async function createLambdaExecutionPolicy({
  name,
  iamClient,
  pipelineExecutionRoleArn,
}) {
  const policy = {
```

```
    Version: "2012-10-17",
    Statement: [
      {
        Effect: "Allow",
        Action: [
          "sqs:ReceiveMessage",
          "sqs:DeleteMessage",
          "sqs:GetQueueAttributes",
          "logs:CreateLogGroup",
          "logs:CreateLogStream",
          "logs:PutLogEvents",
          "sagemaker-geospatial:StartVectorEnrichmentJob",
          "sagemaker-geospatial:GetVectorEnrichmentJob",
          "sagemaker:SendPipelineExecutionStepFailure",
          "sagemaker:SendPipelineExecutionStepSuccess",
          "sagemaker-geospatial:ExportVectorEnrichmentJob",
        ],
        Resource: "*",
      },
      {
        Effect: "Allow",
        // The AWS Lambda function needs permission to pass the pipeline execution
 role to
        // the StartVectorEnrichmentCommand. This restriction prevents an AWS Lambda
 function
        // from elevating privileges. For more information, see:
        // https://docs.aws.amazon.com/IAM/latest/UserGuide/
id_roles_use_passrole.html
        Action: ["iam:PassRole"],
        Resource: `${pipelineExecutionRoleArn}`,
        Condition: {
          StringEquals: {
            "iam:PassedToService": [
              "sagemaker.amazonaws.com",
              "sagemaker-geospatial.amazonaws.com",
            ],
          },
        },
      },
    ],
  };

  const createPolicyCommand = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify(policy),
```

```
    PolicyName: name,
  });

  const { Policy } = await iamClient.send(createPolicyCommand);
  return {
    arn: Policy.Arn,
    policy,
    cleanUp: async () => {
      await iamClient.send(new DeletePolicyCommand({ PolicyArn: Policy.Arn }));
    },
  };
}

/**
 * Attach an AWS IAM policy to an AWS IAM role.
 * @param {{roleName: string, policyArn: string, iamClient: import('@aws-sdk/client-
iam').IAMClient}} props
 */
export async function attachPolicy({ roleName, policyArn, iamClient }) {
  const attachPolicyCommand = new AttachRolePolicyCommand({
    RoleName: roleName,
    PolicyArn: policyArn,
  });

  await iamClient.send(attachPolicyCommand);
  return {
    cleanUp: async () => {
      await iamClient.send(
        new DetachRolePolicyCommand({
          RoleName: roleName,
          PolicyArn: policyArn,
        }),
      );
    },
  };
}

/**
 * Create an AWS Lambda layer that contains the Amazon SageMaker and Amazon
 SageMaker Geospatial clients
 * in the runtime. The default runtime supports v3.188.0 of the JavaScript SDK. The
 Amazon SageMaker
 * Geospatial client wasn't introduced until v3.221.0.
```

```
 * @param {{ name: string, lambdaClient: import('@aws-sdk/client-
lambda').LambdaClient }} props
 */
export async function createLambdaLayer({ name, lambdaClient }) {
  const layerPath = `${dirnameFromMetaUrl(import.meta.url)}lambda/nodejs.zip`;
  const { LayerVersionArn, Version } = await lambdaClient.send(
    new PublishLayerVersionCommand({
      LayerName: name,
      Content: {
        ZipFile: Uint8Array.from(readFileSync(layerPath)),
      },
    }),
  );

  return {
    versionArn: LayerVersionArn,
    version: Version,
    cleanUp: async () => {
      await lambdaClient.send(
        new DeleteLayerVersionCommand({
          LayerName: name,
          VersionNumber: Version,
        }),
      );
    },
  };
}

/**
 * Deploy the AWS Lambda function that will be used to respond to Amazon SageMaker
 pipeline
 * execution steps.
 * @param {{roleArn: string, name: string, lambdaClient: import('@aws-sdk/client-
lambda').LambdaClient, layerVersionArn: string}} props
 */
export async function createLambdaFunction({
  name,
  roleArn,
  lambdaClient,
  layerVersionArn,
}) {
  const lambdaPath = `${dirnameFromMetaUrl(
    import.meta.url,
  )}lambda/dist/index.mjs.zip`;
```

```
  const command = new CreateFunctionCommand({
    Code: {
      ZipFile: Uint8Array.from(readFileSync(lambdaPath)),
    },
    Runtime: Runtime.nodejs18x,
    Handler: "index.handler",
    Layers: [layerVersionArn],
    FunctionName: name,
    Role: roleArn,
  });

  // Function creation fails if the Role is not ready. This retries
  // function creation until it succeeds or it times out.
  const { FunctionArn } = await retry(
    { intervalInMs: 1000, maxRetries: 60 },
    () => lambdaClient.send(command),
  );

  return {
    arn: FunctionArn,
    cleanUp: async () => {
      await lambdaClient.send(
        new DeleteFunctionCommand({ FunctionName: name }),
      );
    },
  };
}

/**
 * This uploads some sample coordinate data to an Amazon S3 bucket.
 * The Amazon SageMaker Geospatial vector enrichment job will take the simple Lat/
Long
 * coordinates in this file and augment them with more detailed location data.
 * @param {{bucketName: string, s3Client: import('@aws-sdk/client-s3').S3Client}}
 props
 */
export async function uploadCSVDataToS3({ bucketName, s3Client }) {
  const s3Path = `${dirnameFromMetaUrl(
    import.meta.url,
  )}../../../../../workflows/sagemaker_pipelines/resources/latlongtest.csv`;

  await s3Client.send(
    new PutObjectCommand({
```

```
      Bucket: bucketName,
      Key: "input/sample_data.csv",
      Body: readFileSync(s3Path),
    }),
  );
}

/**
 * Create the AWS IAM role that will be assumed by the Amazon SageMaker pipeline.
 * @param {{name: string, iamClient: import('@aws-sdk/client-iam').IAMClient}} props
 */
export async function createSagemakerRole({ name, iamClient }) {
  const command = new CreateRoleCommand({
    RoleName: name,
    AssumeRolePolicyDocument: JSON.stringify({
      Version: "2012-10-17",
      Statement: [
        {
          Effect: "Allow",
          Action: ["sts:AssumeRole"],
          Principal: {
            Service: [
              "sagemaker.amazonaws.com",
              "sagemaker-geospatial.amazonaws.com",
            ],
          },
        },
      ],
    }),
  });

  const { Role } = await iamClient.send(command);
  // Wait for the role to be ready.
  await wait(10);

  return {
    arn: Role.Arn,
    cleanUp: async () => {
      await iamClient.send(new DeleteRoleCommand({ RoleName: name }));
    },
  };
}

/**
```

```
 * Create the Amazon SageMaker execution policy. This policy grants permission to
 * invoke the AWS Lambda function, read/write to the Amazon S3 bucket, and send
 messages to
 * the Amazon SQS queue.
 * @param {{ name: string, sqsQueueArn: string, lambdaArn: string, iamClient:
 import('@aws-sdk/client-iam').IAMClient, s3BucketName: string}} props
 */
export async function createSagemakerExecutionPolicy({
  sqsQueueArn,
  lambdaArn,
  iamClient,
  name,
  s3BucketName,
}) {
  const policy = {
    Version: "2012-10-17",
    Statement: [
      {
        Effect: "Allow",
        Action: ["lambda:InvokeFunction"],
        Resource: lambdaArn,
      },
      {
        Effect: "Allow",
        Action: ["s3:*"],
        Resource: [
          `arn:aws:s3:::${s3BucketName}`,
          `arn:aws:s3:::${s3BucketName}/*`,
        ],
      },
      {
        Effect: "Allow",
        Action: ["sqs:SendMessage"],
        Resource: sqsQueueArn,
      },
    ],
  };

  const createPolicyCommand = new CreatePolicyCommand({
    PolicyDocument: JSON.stringify(policy),
    PolicyName: name,
  });

  const { Policy } = await iamClient.send(createPolicyCommand);
```

```
  return {
    arn: Policy.Arn,
    policy,
    cleanUp: async () => {
      await iamClient.send(new DeletePolicyCommand({ PolicyArn: Policy.Arn }));
    },
  };
}

/**
 * Create the Amazon SageMaker pipeline using a JSON pipeline definition. The
 definition
 * can also be provided as an Amazon S3 object using PipelineDefinitionS3Location.
 * @param {{roleArn: string, name: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function createSagemakerPipeline({
  // Assumes an AWS IAM role has been created for this pipeline.
  roleArn,
  name,
  // Assumes an AWS Lambda function has been created for this pipeline.
  functionArn,
  sagemakerClient,
}) {
  const pipelineDefinition = readFileSync(
    // dirnameFromMetaUrl is a local utility function. You can find its
 implementation
    // on GitHub.
    `${dirnameFromMetaUrl(
      import.meta.url,
    )}../../../../../workflows/sagemaker_pipelines/resources/
GeoSpatialPipeline.json`,
  )
    .toString()
    .replace(/\*FUNCTION_ARN\*/g, functionArn);

  const { PipelineArn } = await sagemakerClient.send(
    new CreatePipelineCommand({
      PipelineName: name,
      PipelineDefinition: pipelineDefinition,
      RoleArn: roleArn,
    }),
  );
```

```
  return {
    arn: PipelineArn,
    cleanUp: async () => {
      await sagemakerClient.send(
        new DeletePipelineCommand({ PipelineName: name }),
      );
    },
  };
}

/**
 * Create an Amazon SQS queue. The Amazon SageMaker pipeline will send messages
 * to this queue that are then processed by the AWS Lambda function.
 * @param {{name: string, sqsClient: import('@aws-sdk/client-sqs').SQSClient}} props
 */
export async function createSQSQueue({ name, sqsClient }) {
  const { QueueUrl } = await sqsClient.send(
    new CreateQueueCommand({
      QueueName: name,
      Attributes: {
        DelaySeconds: "5",
        ReceiveMessageWaitTimeSeconds: "5",
        VisibilityTimeout: "300",
      },
    }),
  );

  const { Attributes } = await sqsClient.send(
    new GetQueueAttributesCommand({
      QueueUrl,
      AttributeNames: ["QueueArn"],
    }),
  );

  return {
    queueUrl: QueueUrl,
    queueArn: Attributes.QueueArn,
    cleanUp: async () => {
      await sqsClient.send(new DeleteQueueCommand({ QueueUrl }));
    },
  };
}

/**
```

```
 * Configure the AWS Lambda function to long poll for messages from the Amazon SQS
 * queue.
 * @param {{lambdaName: string, queueArn: string, lambdaClient: import('@aws-sdk/
client-lambda').LambdaClient, sqsClient: import('@aws-sdk/client-sqs').SQSClient}}
 props
 */
export async function configureLambdaSQSEventSource({
  lambdaName,
  queueArn,
  lambdaClient,
}) {
  const { UUID } = await lambdaClient.send(
    new CreateEventSourceMappingCommand({
      EventSourceArn: queueArn,
      FunctionName: lambdaName,
    }),
  );

  return {
    cleanUp: async () => {
      await lambdaClient.send(
        new DeleteEventSourceMappingCommand({
          UUID,
        }),
      );
    },
  };
}

/**
 * Create an Amazon S3 bucket that will store the simple coordinate file as input
 * and the output of the Amazon SageMaker Geospatial vector enrichment job.
 * @param {{s3Client: import('@aws-sdk/client-s3').S3Client, name: string}} props
 */
export async function createS3Bucket({ name, s3Client }) {
  await s3Client.send(new CreateBucketCommand({ Bucket: name }));

  return {
    cleanUp: async () => {
      const paginator = paginateListObjectsV2(
        { client: s3Client },
        { Bucket: name },
      );
      for await (const page of paginator) {
```

```
        const objects = page.Contents;
        if (objects) {
          for (const object of objects) {
            await s3Client.send(
              new DeleteObjectCommand({ Bucket: name, Key: object.Key }),
            );
          }
        }
      }
      await s3Client.send(new DeleteBucketCommand({ Bucket: name }));
    },
  };
}

/**
 * Start the execution of the Amazon SageMaker pipeline. Parameters that are
 * passed in are used in the AWS Lambda function.
 * @param {{
 *   name: string,
 *   sagemakerClient: import('@aws-sdk/client-sagemaker').SageMakerClient,
 *   roleArn: string,
 *   queueUrl: string,
 *   s3InputBucketName: string,
 * }} props
 */
export async function startPipelineExecution({
  sagemakerClient,
  name,
  bucketName,
  roleArn,
  queueUrl,
}) {
  /**
   * The Vector Enrichment Job requests CSV data. This configuration points to a CSV
   * file in an Amazon S3 bucket.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobInputConfig}
   */
  const inputConfig = {
    DataSourceConfig: {
      S3Data: {
        S3Uri: `s3://${bucketName}/input/sample_data.csv`,
      },
    },
```

```
    DocumentType: VectorEnrichmentJobDocumentType.CSV,
  };

  /**
   * The Vector Enrichment Job adds additional data to the source CSV. This
 configuration points
   * to an Amazon S3 prefix where the output will be stored.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").ExportVectorEnrichmentJobOutputConfig}
   */
  const outputConfig = {
    S3Data: {
      S3Uri: `s3://${bucketName}/output/`,
    },
  };

  /**
   * This job will be a Reverse Geocoding Vector Enrichment Job. Reverse Geocoding
 requires
   * latitude and longitude values.
   * @type {import("@aws-sdk/client-sagemaker-
geospatial").VectorEnrichmentJobConfig}
   */
  const jobConfig = {
    ReverseGeocodingConfig: {
      XAttributeName: "Longitude",
      YAttributeName: "Latitude",
    },
  };

  const { PipelineExecutionArn } = await sagemakerClient.send(
    new StartPipelineExecutionCommand({
      PipelineName: name,
      PipelineExecutionDisplayName: `${name}-example-execution`,
      PipelineParameters: [
        { Name: "parameter_execution_role", Value: roleArn },
        { Name: "parameter_queue_url", Value: queueUrl },
        {
          Name: "parameter_vej_input_config",
          Value: JSON.stringify(inputConfig),
        },
        {
          Name: "parameter_vej_export_config",
          Value: JSON.stringify(outputConfig),
```

```
        },
        {
          Name: "parameter_step_1_vej_config",
          Value: JSON.stringify(jobConfig),
        },
      ],
    }),
  );

  return {
    arn: PipelineExecutionArn,
  };
}

/**
 * Poll the executing pipeline until the status is 'SUCCEEDED', 'STOPPED', or
 'FAILED'.
 * @param {{ arn: string, sagemakerClient: import('@aws-sdk/client-
sagemaker').SageMakerClient}} props
 */
export async function waitForPipelineComplete({ arn, sagemakerClient }) {
  const command = new DescribePipelineExecutionCommand({
    PipelineExecutionArn: arn,
  });

  let complete = false;
  let intervalInSeconds = 15;
  const COMPLETION_STATUSES = [
    PipelineExecutionStatus.FAILED,
    PipelineExecutionStatus.STOPPED,
    PipelineExecutionStatus.SUCCEEDED,
  ];

  do {
    const { PipelineExecutionStatus: status, FailureReason } =
      await sagemakerClient.send(command);

    complete = COMPLETION_STATUSES.includes(status);

    if (!complete) {
      console.log(
        `Pipeline is ${status}. Waiting ${intervalInSeconds} seconds before checking
 again.`,
      );
```

```
      await wait(intervalInSeconds);
    } else if (status === PipelineExecutionStatus.FAILED) {
      throw new Error(`Pipeline failed because: ${FailureReason}`);
    } else if (status === PipelineExecutionStatus.STOPPED) {
      throw new Error(`Pipeline was forcefully stopped.`);
    } else {
      console.log(`Pipeline execution ${status}.`);
    }
  } while (!complete);
}

/**
 * Return the string value of an Amazon S3 object.
 * @param {{ bucket: string, key: string, s3Client: import('@aws-sdk/client-
s3').S3Client}} param0
 */
export async function getObject({ bucket, s3Client }) {
  const prefix = "output/";
  const { Contents } = await s3Client.send(
    new ListObjectsV2Command({ MaxKeys: 1, Bucket: bucket, Prefix: prefix }),
  );

  if (!Contents.length) {
    throw new Error("No objects found in bucket.");
  }

  // Find the CSV file.
  const outputObject = Contents.find((obj) => obj.Key.endsWith(".csv"));

  if (!outputObject) {
    throw new Error(`No CSV file found in bucket with the prefix "${prefix}".`);
  }

  const { Body } = await s3Client.send(
    new GetObjectCommand({
      Bucket: bucket,
      Key: outputObject.Key,
    }),
  );

  return Body.transformToString();
}
```

Essa função é um trecho de um arquivo que usa as funções anteriores da biblioteca para configurar um SageMaker pipeline, executá-lo e excluir todos os recursos criados.

```
import { retry, wait } from "@aws-sdk-examples/libs/utils/util-timers.js";
import {
  attachPolicy,
  configureLambdaSQSEventSource,
  createLambdaExecutionPolicy,
  createLambdaExecutionRole,
  createLambdaFunction,
  createLambdaLayer,
  createS3Bucket,
  createSQSQueue,
  createSagemakerExecutionPolicy,
  createSagemakerPipeline,
  createSagemakerRole,
  getObject,
  startPipelineExecution,
  uploadCSVDataToS3,
  waitForPipelineComplete,
} from "./lib.js";
import { MESSAGES } from "./messages.js";

export class SageMakerPipelinesWkflw {
  names = {
    LAMBDA_EXECUTION_ROLE: "sagemaker-wkflw-lambda-execution-role",
    LAMBDA_EXECUTION_ROLE_POLICY:
      "sagemaker-wkflw-lambda-execution-role-policy",
    LAMBDA_FUNCTION: "sagemaker-wkflw-lambda-function",
    LAMBDA_LAYER: "sagemaker-wkflw-lambda-layer",
    SAGE_MAKER_EXECUTION_ROLE: "sagemaker-wkflw-pipeline-execution-role",
    SAGE_MAKER_EXECUTION_ROLE_POLICY:
      "sagemaker-wkflw-pipeline-execution-role-policy",
    SAGE_MAKER_PIPELINE: "sagemaker-wkflw-pipeline",
    SQS_QUEUE: "sagemaker-wkflw-sqs-queue",
    S3_BUCKET: `sagemaker-wkflw-s3-bucket-${Date.now()}`,
  };

  cleanUpFunctions = [];

  /**
   * @param {import("@aws-sdk-examples/libs/prompter.js").Prompter} prompter
   * @param {import("@aws-sdk-examples/libs/logger.js").Logger} logger
```

```
   * @param {{ IAM: import("@aws-sdk/client-iam").IAMClient, Lambda: import("@aws-
sdk/client-lambda").LambdaClient, SageMaker: import("@aws-sdk/client-
sagemaker").SageMakerClient, S3: import("@aws-sdk/client-s3").S3Client, SQS:
 import("@aws-sdk/client-sqs").SQSClient }} clients
   */
  constructor(prompter, logger, clients) {
    this.prompter = prompter;
    this.logger = logger;
    this.clients = clients;
  }

  async run() {
    try {
      await this.startWorkflow();
    } catch (err) {
      console.error(err);
      throw err;
    } finally {
      // Run all of the clean up functions. If any fail, we log the error and
 continue.
      // This ensures all clean up functions are run.
      this.logger.logSeparator();
      const doCleanUp = await this.prompter.confirm({
        message: "Clean up resources?",
      });
      if (doCleanUp) {
        for (let i = this.cleanUpFunctions.length - 1; i >= 0; i--) {
          await retry(
            { intervalInMs: 1000, maxRetries: 60, swallowError: true },
            this.cleanUpFunctions[i],
          );
        }
      }
    }
  }

  async startWorkflow() {
    this.logger.logSeparator(MESSAGES.greetingHeader);
    await this.logger.log(MESSAGES.greeting);

    this.logger.logSeparator();
    await this.logger.log(
      MESSAGES.creatingRole.replace(
        "${ROLE_NAME}",
```

```
        this.names.LAMBDA_EXECUTION_ROLE,
      ),
    );

    // Create an IAM role that will be assumed by the AWS Lambda function. This
function
    // is triggered by Amazon SQS messages and calls SageMaker and SageMaker
GeoSpatial actions.
    const { arn: lambdaExecutionRoleArn, cleanUp: lambdaExecutionRoleCleanUp } =
      await createLambdaExecutionRole({
        name: this.names.LAMBDA_EXECUTION_ROLE,
        iamClient: this.clients.IAM,
      });
    // Add a clean up step to a stack for every resource created.
    this.cleanUpFunctions.push(lambdaExecutionRoleCleanUp);

    await this.logger.log(
      MESSAGES.roleCreated.replace(
        "${ROLE_NAME}",
        this.names.LAMBDA_EXECUTION_ROLE,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingRole.replace(
        "${ROLE_NAME}",
        this.names.SAGE_MAKER_EXECUTION_ROLE,
      ),
    );

    // Create an IAM role that will be assumed by the SageMaker pipeline. The
pipeline
    // sends messages to an Amazon SQS queue and puts/retrieves Amazon S3 objects.
    const {
      arn: pipelineExecutionRoleArn,
      cleanUp: pipelineExecutionRoleCleanUp,
    } = await createSagemakerRole({
      iamClient: this.clients.IAM,
      name: this.names.SAGE_MAKER_EXECUTION_ROLE,
    });
    this.cleanUpFunctions.push(pipelineExecutionRoleCleanUp);
```

```
    await this.logger.log(
      MESSAGES.roleCreated.replace(
        "${ROLE_NAME}",
        this.names.SAGE_MAKER_EXECUTION_ROLE,
      ),
    );

    this.logger.logSeparator();

    // Create an IAM policy that allows the AWS Lambda function to invoke SageMaker
APIs.
    const {
      arn: lambdaExecutionPolicyArn,
      policy: lambdaPolicy,
      cleanUp: lambdaExecutionPolicyCleanUp,
    } = await createLambdaExecutionPolicy({
      name: this.names.LAMBDA_EXECUTION_ROLE_POLICY,
      s3BucketName: this.names.S3_BUCKET,
      iamClient: this.clients.IAM,
      pipelineExecutionRoleArn,
    });
    this.cleanUpFunctions.push(lambdaExecutionPolicyCleanUp);

    console.log(JSON.stringify(lambdaPolicy, null, 2), "\n");

    await this.logger.log(
      MESSAGES.attachPolicy
        .replace("${POLICY_NAME}", this.names.LAMBDA_EXECUTION_ROLE_POLICY)
        .replace("${ROLE_NAME}", this.names.LAMBDA_EXECUTION_ROLE),
    );

    await this.prompter.checkContinue();

    // Attach the Lambda execution policy to the execution role.
    const { cleanUp: lambdaExecutionRolePolicyCleanUp } = await attachPolicy({
      roleName: this.names.LAMBDA_EXECUTION_ROLE,
      policyArn: lambdaExecutionPolicyArn,
      iamClient: this.clients.IAM,
    });
    this.cleanUpFunctions.push(lambdaExecutionRolePolicyCleanUp);

    await this.logger.log(MESSAGES.policyAttached);

    this.logger.logSeparator();
```

```
    // Create Lambda layer for SageMaker packages.
    const { versionArn: layerVersionArn, cleanUp: lambdaLayerCleanUp } =
      await createLambdaLayer({
        name: this.names.LAMBDA_LAYER,
        lambdaClient: this.clients.Lambda,
      });
    this.cleanUpFunctions.push(lambdaLayerCleanUp);

    await this.logger.log(
      MESSAGES.creatingFunction.replace(
        "${FUNCTION_NAME}",
        this.names.LAMBDA_FUNCTION,
      ),
    );

    // Create the Lambda function with the execution role.
    const { arn: lambdaArn, cleanUp: lambdaCleanUp } =
      await createLambdaFunction({
        roleArn: lambdaExecutionRoleArn,
        lambdaClient: this.clients.Lambda,
        name: this.names.LAMBDA_FUNCTION,
        layerVersionArn,
      });
    this.cleanUpFunctions.push(lambdaCleanUp);

    await this.logger.log(
      MESSAGES.functionCreated.replace(
        "${FUNCTION_NAME}",
        this.names.LAMBDA_FUNCTION,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingSQSQueue.replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    // Create an SQS queue for the SageMaker pipeline.
    const {
      queueUrl,
      queueArn,
      cleanUp: queueCleanUp,
```

```
    } = await createSQSQueue({
      name: this.names.SQS_QUEUE,
      sqsClient: this.clients.SQS,
    });
    this.cleanUpFunctions.push(queueCleanUp);

    await this.logger.log(
      MESSAGES.sqsQueueCreated.replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.configuringLambdaSQSEventSource
        .replace("${LAMBDA_NAME}", this.names.LAMBDA_FUNCTION)
        .replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    // Configure the SQS queue as an event source for the Lambda.
    const { cleanUp: lambdaSQSEventSourceCleanUp } =
      await configureLambdaSQSEventSource({
        lambdaArn,
        lambdaName: this.names.LAMBDA_FUNCTION,
        queueArn,
        sqsClient: this.clients.SQS,
        lambdaClient: this.clients.Lambda,
      });
    this.cleanUpFunctions.push(lambdaSQSEventSourceCleanUp);

    await this.logger.log(
      MESSAGES.lambdaSQSEventSourceConfigured
        .replace("${LAMBDA_NAME}", this.names.LAMBDA_FUNCTION)
        .replace("${QUEUE_NAME}", this.names.SQS_QUEUE),
    );

    this.logger.logSeparator();

    // Create an IAM policy that allows the SageMaker pipeline to invoke AWS Lambda
    // and send messages to the Amazon SQS queue.
    const {
      arn: pipelineExecutionPolicyArn,
      policy: sagemakerPolicy,
      cleanUp: pipelineExecutionPolicyCleanUp,
    } = await createSagemakerExecutionPolicy({
```

```
      sqsQueueArn: queueArn,
      lambdaArn,
      iamClient: this.clients.IAM,
      name: this.names.SAGE_MAKER_EXECUTION_ROLE_POLICY,
      s3BucketName: this.names.S3_BUCKET,
    });
    this.cleanUpFunctions.push(pipelineExecutionPolicyCleanUp);

    console.log(JSON.stringify(sagemakerPolicy, null, 2));

    await this.logger.log(
      MESSAGES.attachPolicy
        .replace("${POLICY_NAME}", this.names.SAGE_MAKER_EXECUTION_ROLE_POLICY)
        .replace("${ROLE_NAME}", this.names.SAGE_MAKER_EXECUTION_ROLE),
    );

    await this.prompter.checkContinue();

    // Attach the SageMaker execution policy to the execution role.
    const { cleanUp: pipelineExecutionRolePolicyCleanUp } = await attachPolicy({
      roleName: this.names.SAGE_MAKER_EXECUTION_ROLE,
      policyArn: pipelineExecutionPolicyArn,
      iamClient: this.clients.IAM,
    });
    this.cleanUpFunctions.push(pipelineExecutionRolePolicyCleanUp);
    // Wait for the role to be ready. If the role is used immediately,
    // the pipeline will fail.
    await wait(5);

    await this.logger.log(MESSAGES.policyAttached);

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingPipeline.replace(
        "${PIPELINE_NAME}",
        this.names.SAGE_MAKER_PIPELINE,
      ),
    );

    // Create the SageMaker pipeline.
    const { cleanUp: pipelineCleanUp } = await createSagemakerPipeline({
      roleArn: pipelineExecutionRoleArn,
      functionArn: lambdaArn,
```

```
      sagemakerClient: this.clients.SageMaker,
      name: this.names.SAGE_MAKER_PIPELINE,
    });
    this.cleanUpFunctions.push(pipelineCleanUp);

    await this.logger.log(
      MESSAGES.pipelineCreated.replace(
        "${PIPELINE_NAME}",
        this.names.SAGE_MAKER_PIPELINE,
      ),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.creatingS3Bucket.replace("${BUCKET_NAME}", this.names.S3_BUCKET),
    );

    // Create an S3 bucket for storing inputs and outputs.
    const { cleanUp: s3BucketCleanUp } = await createS3Bucket({
      name: this.names.S3_BUCKET,
      s3Client: this.clients.S3,
    });
    this.cleanUpFunctions.push(s3BucketCleanUp);

    await this.logger.log(
      MESSAGES.s3BucketCreated.replace("${BUCKET_NAME}", this.names.S3_BUCKET),
    );

    this.logger.logSeparator();

    await this.logger.log(
      MESSAGES.uploadingInputData.replace(
        "${BUCKET_NAME}",
        this.names.S3_BUCKET,
      ),
    );

    // Upload CSV Lat/Long data to S3.
    await uploadCSVDataToS3({
      bucketName: this.names.S3_BUCKET,
      s3Client: this.clients.S3,
    });
```

```
    await this.logger.log(MESSAGES.inputDataUploaded);

    this.logger.logSeparator();

    await this.prompter.checkContinue(MESSAGES.executePipeline);

    // Execute the SageMaker pipeline.
    const { arn: pipelineExecutionArn } = await startPipelineExecution({
      name: this.names.SAGE_MAKER_PIPELINE,
      sagemakerClient: this.clients.SageMaker,
      roleArn: pipelineExecutionRoleArn,
      bucketName: this.names.S3_BUCKET,
      queueUrl,
    });

    // Wait for the pipeline execution to finish.
    await waitForPipelineComplete({
      arn: pipelineExecutionArn,
      sagemakerClient: this.clients.SageMaker,
    });

    this.logger.logSeparator();

    await this.logger.log(MESSAGES.outputDelay);

    // The getOutput function will throw an error if the output is not
    // found. The retry function will retry a failed function call once
    // ever 10 seconds for 2 minutes.
    const output = await retry({ intervalInMs: 10000, maxRetries: 12 }, () =>
      getObject({
        bucket: this.names.S3_BUCKET,
        s3Client: this.clients.S3,
      }),
    );

    this.logger.logSeparator();
    await this.logger.log(MESSAGES.outputDataRetrieved);
    console.log(output.split("\n").slice(0, 6).join("\n"));
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Exemplos de Secrets Manager usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  GetSecretValueCommand,
  SecretsManagerClient,
} from "@aws-sdk/client-secrets-manager";

export const getSecretValue = async (secretName = "SECRET_NAME") => {
  const client = new SecretsManagerClient();
  const response = await client.send(
    new GetSecretValueCommand({
      SecretId: secretName,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '584eb612-f8b0-48c9-855e-6d246461b604',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   ARN: 'arn:aws:secretsmanager:us-east-1:xxxxxxxxxxxx:secret:binary-
secret-3873048-xxxxxx',
  //   CreatedDate: 2023-08-08T19:29:51.294Z,
  //   Name: 'binary-secret-3873048',
  //   SecretBinary: Uint8Array(11) [
  //      98, 105, 110, 97, 114,
  //     121,  32, 100, 97, 116,
  //      97
  //   ],
  //   VersionId: '712083f4-0d26-415e-8044-16735142cd6a',
  //   VersionStages: [ 'AWSCURRENT' ]
  // }

  if (response.SecretString) {
    return response.SecretString;
  }

  if (response.SecretBinary) {
    return response.SecretBinary;
  }
};
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for JavaScript da API.

Exemplos do Amazon SES usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um filtro de recebimento

O exemplo de código a seguir mostra como criar um filtro de recebimento do Amazon SES que bloqueia e-mails recebidos de um endereço IP ou de um intervalo de endereços IP.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
  CreateReceiptFilterCommand,
```

```
  ReceiptFilterPolicy,
} from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const createCreateReceiptFilterCommand = ({ policy, ipOrRange, name }) => {
  return new CreateReceiptFilterCommand({
    Filter: {
      IpFilter: {
        Cidr: ipOrRange, // string, either a single IP address (10.0.0.1) or an IP
 address range in CIDR notation (10.0.0.1/24)).
        Policy: policy, // enum ReceiptFilterPolicy, email traffic from the filtered
 addressesOptions.
      },
      /*
        The name of the IP address filter. Only ASCII letters, numbers, underscores,
 or dashes.
        Must be less than 64 characters and start and end with a letter or number.
       */
      Name: name,
    },
  });
};

const FILTER_NAME = getUniqueName("ReceiptFilter");

const run = async () => {
  const createReceiptFilterCommand = createCreateReceiptFilterCommand({
    policy: ReceiptFilterPolicy.Allow,
    ipOrRange: "10.0.0.1",
    name: FILTER_NAME,
  });

  try {
    return await sesClient.send(createReceiptFilterCommand);
  } catch (err) {
    console.log("Failed to create filter.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptFiltera Referência AWS SDK for JavaScript da API.

Criar uma regra de recebimento

O exemplo de código a seguir mostra como criar uma regra de recebimento do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateReceiptRuleCommand, TlsPolicy } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");
const RULE_NAME = getUniqueName("RuleName");
const S3_BUCKET_NAME = getUniqueName("S3BucketName");

const createS3ReceiptRuleCommand = ({
  bucketName,
  emailAddresses,
  name,
  ruleSet,
}) => {
  return new CreateReceiptRuleCommand({
    Rule: {
      Actions: [
        {
          S3Action: {
            BucketName: bucketName,
            ObjectKeyPrefix: "email",
          },
        },
      ],
      Recipients: emailAddresses,
      Enabled: true,
      Name: name,
```

```
      ScanEnabled: false,
      TlsPolicy: TlsPolicy.Optional,
    },
    RuleSetName: ruleSet, // Required
  });
};

const run = async () => {
  const s3ReceiptRuleCommand = createS3ReceiptRuleCommand({
    bucketName: S3_BUCKET_NAME,
    emailAddresses: ["email@example.com"],
    name: RULE_NAME,
    ruleSet: RULE_SET_NAME,
  });

  try {
    return await sesClient.send(s3ReceiptRuleCommand);
  } catch (err) {
    console.log("Failed to create S3 receipt rule.", err);
    throw err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptRulea Referência AWS SDK for JavaScript da API.

Criar um conjunto de regras de recebimento

O exemplo de código a seguir mostra como criar um conjunto de regras de recebimento do Amazon SES para organizar as regras aplicadas aos e-mails recebidos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateReceiptRuleSetCommand } from "@aws-sdk/client-ses";
```

```
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");

const createCreateReceiptRuleSetCommand = (ruleSetName) => {
  return new CreateReceiptRuleSetCommand({ RuleSetName: ruleSetName });
};

const run = async () => {
  const createReceiptRuleSetCommand =
    createCreateReceiptRuleSetCommand(RULE_SET_NAME);

  try {
    return await sesClient.send(createReceiptRuleSetCommand);
  } catch (err) {
    console.log("Failed to create receipt rule set", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateReceiptRuleSeta Referência AWS SDK for JavaScript da API.

Criar um modelo de e-mail

O exemplo de código a seguir mostra como criar um modelo de e-mail do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateTemplateCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
```

```
const TEMPLATE_NAME = getUniqueName("TestTemplateName");

const createCreateTemplateCommand = () => {
  return new CreateTemplateCommand({
    /**
     * The template feature in Amazon SES is based on the Handlebars template
 system.
     */
    Template: {
      /**
       * The name of an existing template in Amazon SES.
       */
      TemplateName: TEMPLATE_NAME,
      HtmlPart: `
        <h1>Hello, {{contact.firstName}}!</h1>
        <p>
        Did you know Amazon has a mascot named Peccy?
        </p>
      `,
      SubjectPart: "Amazon Tip",
    },
  });
};

const run = async () => {
  const createTemplateCommand = createCreateTemplateCommand();

  try {
    return await sesClient.send(createTemplateCommand);
  } catch (err) {
    console.log("Failed to create template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte CreateTemplatea Referência AWS SDK for JavaScript da API.

Excluir um filtro de recebimento

O exemplo de código a seguir mostra como excluir um filtro de recebimento do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptFilterCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";

const RECEIPT_FILTER_NAME = getUniqueName("ReceiptFilterName");

const createDeleteReceiptFilterCommand = (filterName) => {
  return new DeleteReceiptFilterCommand({ FilterName: filterName });
};

const run = async () => {
  const deleteReceiptFilterCommand =
    createDeleteReceiptFilterCommand(RECEIPT_FILTER_NAME);

  try {
    return await sesClient.send(deleteReceiptFilterCommand);
  } catch (err) {
    console.log("Error deleting receipt filter.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptFiltera Referência AWS SDK for JavaScript da API.

Excluir uma regra de recebimento

O exemplo de código a seguir mostra como excluir uma regra de recebimento do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptRuleCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const RULE_NAME = getUniqueName("RuleName");
const RULE_SET_NAME = getUniqueName("RuleSetName");

const createDeleteReceiptRuleCommand = () => {
  return new DeleteReceiptRuleCommand({
    RuleName: RULE_NAME,
    RuleSetName: RULE_SET_NAME,
  });
};

const run = async () => {
  const deleteReceiptRuleCommand = createDeleteReceiptRuleCommand();
  try {
    return await sesClient.send(deleteReceiptRuleCommand);
  } catch (err) {
    console.log("Failed to delete receipt rule.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptRulea Referência AWS SDK for JavaScript da API.

Excluir um conjunto de regras

O exemplo de código a seguir mostra como excluir um conjunto de regras do Amazon SES e todas as regras contidas nesse conjunto.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteReceiptRuleSetCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const RULE_SET_NAME = getUniqueName("RuleSetName");

const createDeleteReceiptRuleSetCommand = () => {
  return new DeleteReceiptRuleSetCommand({ RuleSetName: RULE_SET_NAME });
};

const run = async () => {
  const deleteReceiptRuleSetCommand = createDeleteReceiptRuleSetCommand();

  try {
    return await sesClient.send(deleteReceiptRuleSetCommand);
  } catch (err) {
    console.log("Failed to delete receipt rule set.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteReceiptRuleSeta Referência AWS SDK for JavaScript da API.

Excluir um modelo de e-mail

O exemplo de código a seguir mostra como excluir um modelo de e-mail do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");

const createDeleteTemplateCommand = (templateName) =>
  new DeleteTemplateCommand({ TemplateName: templateName });

const run = async () => {
  const deleteTemplateCommand = createDeleteTemplateCommand(TEMPLATE_NAME);

  try {
    return await sesClient.send(deleteTemplateCommand);
  } catch (err) {
    console.log("Failed to delete template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteTemplatea Referência AWS SDK for JavaScript da API.

Excluir uma identidade

O exemplo de código a seguir mostra como excluir uma identidade do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DeleteIdentityCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const IDENTITY_EMAIL = "fake@example.com";

const createDeleteIdentityCommand = (identityName) => {
  return new DeleteIdentityCommand({
    Identity: identityName,
  });
};

const run = async () => {
  const deleteIdentityCommand = createDeleteIdentityCommand(IDENTITY_EMAIL);

  try {
    return await sesClient.send(deleteIdentityCommand);
  } catch (err) {
    console.log("Failed to delete identity.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte DeleteIdentitya Referência AWS SDK for JavaScript da API.

Obter um modelo existente de e-mail

O exemplo de código a seguir mostra como obter um modelo existente de e-mail do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { GetTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");

const createGetTemplateCommand = (templateName) =>
  new GetTemplateCommand({ TemplateName: templateName });

const run = async () => {
  const getTemplateCommand = createGetTemplateCommand(TEMPLATE_NAME);

  try {
    return await sesClient.send(getTemplateCommand);
  } catch (err) {
    console.log("Failed to get email template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte GetTemplatea Referência AWS SDK for JavaScript da API.

Listar modelos de e-mail

O exemplo de código a seguir mostra como lista modelos existentes de e-mail do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListTemplatesCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListTemplatesCommand = (maxItems) =>
  new ListTemplatesCommand({ MaxItems: maxItems });

const run = async () => {
  const listTemplatesCommand = createListTemplatesCommand(10);

  try {
    return await sesClient.send(listTemplatesCommand);
  } catch (err) {
    console.log("Failed to list templates.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for JavaScript da API.

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListIdentitiesCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListIdentitiesCommand = () =>
  new ListIdentitiesCommand({ IdentityType: "EmailAddress", MaxItems: 10 });

const run = async () => {
  const listIdentitiesCommand = createListIdentitiesCommand();

  try {
    return await sesClient.send(listIdentitiesCommand);
  } catch (err) {
    console.log("Failed to list identities.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for JavaScript da API.

Listar filtros de recebimento

O exemplo de código a seguir mostra como listar filtros de recebimento do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ListReceiptFiltersCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createListReceiptFiltersCommand = () => new ListReceiptFiltersCommand({});

const run = async () => {
  const listReceiptFiltersCommand = createListReceiptFiltersCommand();
```

```
  return await sesClient.send(listReceiptFiltersCommand);
};
```

- Para obter detalhes da API, consulte ListReceiptFiltersa Referência AWS SDK for JavaScript da API.

Enviar e-mails em massa com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo para vários destinos com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendBulkTemplatedEmailCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * Replace this with the name of an existing template.
 */
const TEMPLATE_NAME = getUniqueName("ReminderTemplate");

/**
 * Replace these with existing verified emails.
 */
const VERIFIED_EMAIL_1 = postfix(getUniqueName("Bilbo"), "@example.com");
const VERIFIED_EMAIL_2 = postfix(getUniqueName("Frodo"), "@example.com");

const USERS = [
  { firstName: "Bilbo", emailAddress: VERIFIED_EMAIL_1 },
  { firstName: "Frodo", emailAddress: VERIFIED_EMAIL_2 },
```

```
];

/**
 *
 * @param { { emailAddress: string, firstName: string }[] } users
 * @param { string } templateName the name of an existing template in SES
 * @returns { SendBulkTemplatedEmailCommand }
 */
const createBulkReminderEmailCommand = (users, templateName) => {
  return new SendBulkTemplatedEmailCommand({
    /**
     * Each 'Destination' uses a corresponding set of replacement data. We can map
 each user
     * to a 'Destination' and provide user specific replacement data to create
 personalized emails.
     *
     * Here's an example of how a template would be replaced with user data:
     * Template: <h1>Hello {{name}},</h1><p>Don't forget about the party gifts!</p>
     * Destination 1: <h1>Hello Bilbo,</h1><p>Don't forget about the party gifts!</
p>
     * Destination 2: <h1>Hello Frodo,</h1><p>Don't forget about the party gifts!</
p>
     */
    Destinations: users.map((user) => ({
      Destination: { ToAddresses: [user.emailAddress] },
      ReplacementTemplateData: JSON.stringify({ name: user.firstName }),
    })),
    DefaultTemplateData: JSON.stringify({ name: "Shireling" }),
    Source: VERIFIED_EMAIL_1,
    Template: templateName,
  });
};

const run = async () => {
  const sendBulkTemplateEmailCommand = createBulkReminderEmailCommand(
    USERS,
    TEMPLATE_NAME,
  );
  try {
    return await sesClient.send(sendBulkTemplateEmailCommand);
  } catch (err) {
    console.log("Failed to send bulk template email", err);
    return err;
  }
```

```
};
```

- Para obter detalhes da API, consulte SendBulkTemplatedEmaila Referência AWS SDK for JavaScript da API.

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendEmailCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const createSendEmailCommand = (toAddress, fromAddress) => {
  return new SendEmailCommand({
    Destination: {
      /* required */
      CcAddresses: [
        /* more items */
      ],
      ToAddresses: [
        toAddress,
        /* more To-email addresses */
      ],
    },
    Message: {
      /* required */
      Body: {
        /* required */
        Html: {
          Charset: "UTF-8",
          Data: "HTML_FORMAT_BODY",
        },
```

```
        Text: {
          Charset: "UTF-8",
          Data: "TEXT_FORMAT_BODY",
        },
      },
      Subject: {
        Charset: "UTF-8",
        Data: "EMAIL_SUBJECT",
      },
    },
    Source: fromAddress,
    ReplyToAddresses: [
      /* more items */
    ],
  });
};

const run = async () => {
  const sendEmailCommand = createSendEmailCommand(
    "recipient@example.com",
    "sender@example.com",
  );

  try {
    return await sesClient.send(sendEmailCommand);
  } catch (e) {
    console.error("Failed to send email.");
    return e;
  }
};
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for JavaScript da API.

Enviar e-mail bruto

O exemplo de código a seguir mostra como enviar e-mails brutos com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use nodemailer para enviar um e-mail com anexo.

```
import sesClientModule from "@aws-sdk/client-ses";
/**
 * nodemailer wraps the SES SDK and calls SendRawEmail. Use this for more advanced
 * functionality like adding attachments to your email.
 *
 * https://nodemailer.com/transports/ses/
 */
import nodemailer from "nodemailer";

/**
 * @param {string} from An Amazon SES verified email address.
 * @param {*} to An Amazon SES verified email address.
 */
export const sendEmailWithAttachments = (
  from = "from@example.com",
  to = "to@example.com",
) => {
  const ses = new sesClientModule.SESClient({});
  const transporter = nodemailer.createTransport({
    SES: { ses, aws: sesClientModule },
  });

  return new Promise((resolve, reject) => {
    transporter.sendMail(
      {
        from,
        to,
        subject: "Hello World",
        text: "Greetings from Amazon SES!",
        attachments: [{ content: "Hello World!", filename: "hello.txt" }],
      },
      (err, info) => {
        if (err) {
```

```
          reject(err);
        } else {
          resolve(info);
        }
      },
    );
  });
};
```

- Para obter detalhes da API, consulte SendRawEmaila Referência AWS SDK for JavaScript da API.

Enviar e-mails com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SendTemplatedEmailCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * Replace this with the name of an existing template.
 */
const TEMPLATE_NAME = getUniqueName("ReminderTemplate");

/**
 * Replace these with existing verified emails.
 */
```

```
const VERIFIED_EMAIL = postfix(getUniqueName("Bilbo"), "@example.com");

const USER = { firstName: "Bilbo", emailAddress: VERIFIED_EMAIL };

/**
 *
 * @param { { emailAddress: string, firstName: string } } user
 * @param { string } templateName - The name of an existing template in Amazon SES.
 * @returns { SendTemplatedEmailCommand }
 */
const createReminderEmailCommand = (user, templateName) => {
  return new SendTemplatedEmailCommand({
    /**
     * Here's an example of how a template would be replaced with user data:
     * Template: <h1>Hello {{contact.firstName}},</h1><p>Don't forget about the
 party gifts!</p>
     * Destination: <h1>Hello Bilbo,</h1><p>Don't forget about the party gifts!</p>
     */
    Destination: { ToAddresses: [user.emailAddress] },
    TemplateData: JSON.stringify({ contact: { firstName: user.firstName } }),
    Source: VERIFIED_EMAIL,
    Template: templateName,
  });
};

const run = async () => {
  const sendReminderEmailCommand = createReminderEmailCommand(
    USER,
    TEMPLATE_NAME,
  );
  try {
    return await sesClient.send(sendReminderEmailCommand);
  } catch (err) {
    console.log("Failed to send template email", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte SendTemplatedEmail a Referência AWS SDK for JavaScript da API.

Atualizar um modelo de e-mail

O exemplo de código a seguir mostra como atualizar um modelo de e-mail do Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { UpdateTemplateCommand } from "@aws-sdk/client-ses";
import { getUniqueName } from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

const TEMPLATE_NAME = getUniqueName("TemplateName");
const HTML_PART = "<h1>Hello, World!</h1>";

const createUpdateTemplateCommand = () => {
  return new UpdateTemplateCommand({
    Template: {
      TemplateName: TEMPLATE_NAME,
      HtmlPart: HTML_PART,
      SubjectPart: "Example",
      TextPart: "Updated template text.",
    },
  });
};

const run = async () => {
  const updateTemplateCommand = createUpdateTemplateCommand();

  try {
    return await sesClient.send(updateTemplateCommand);
  } catch (err) {
    console.log("Failed to update template.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte UpdateTemplatea Referência AWS SDK for JavaScript da API.

Verificar uma identidade de domínio

O exemplo de código a seguir mostra como verificar uma identidade de domínio com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { VerifyDomainIdentityCommand } from "@aws-sdk/client-ses";
import {
  getUniqueName,
  postfix,
} from "@aws-sdk-examples/libs/utils/util-string.js";
import { sesClient } from "./libs/sesClient.js";

/**
 * You must have access to the domain's DNS settings to complete the
 * domain verification process.
 */
const DOMAIN_NAME = postfix(getUniqueName("Domain"), ".example.com");

const createVerifyDomainIdentityCommand = () => {
  return new VerifyDomainIdentityCommand({ Domain: DOMAIN_NAME });
};

const run = async () => {
  const VerifyDomainIdentityCommand = createVerifyDomainIdentityCommand();

  try {
    return await sesClient.send(VerifyDomainIdentityCommand);
  } catch (err) {
    console.log("Failed to verify domain.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte VerifyDomainIdentitya Referência AWS SDK for JavaScript da API.

Verificar uma identidade de e-mail

O exemplo de código a seguir mostra como verificar uma identidade de e-mail com o Amazon SES.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Import required AWS SDK clients and commands for Node.js
import { VerifyEmailIdentityCommand } from "@aws-sdk/client-ses";
import { sesClient } from "./libs/sesClient.js";

const EMAIL_ADDRESS = "name@example.com";

const createVerifyEmailIdentityCommand = (emailAddress) => {
  return new VerifyEmailIdentityCommand({ EmailAddress: emailAddress });
};

const run = async () => {
  const verifyEmailIdentityCommand =
    createVerifyEmailIdentityCommand(EMAIL_ADDRESS);
  try {
    return await sesClient.send(verifyEmailIdentityCommand);
  } catch (err) {
    console.log("Failed to verify email identity.", err);
    return err;
  }
};
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for JavaScript da API.

Exemplos do Amazon SNS usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicialize um cliente SNS e liste tópicos em sua conta.

```
import { SNSClient, paginateListTopics } from "@aws-sdk/client-sns";

export const helloSns = async () => {
  // The configuration object (`{}`) is required. If the region and credentials
  // are omitted, the SDK uses your local configuration if it exists.
  const client = new SNSClient({});

  // You can also use `ListTopicsCommand`, but to use that command you must
  // handle the pagination yourself. You can do that by sending the
 `ListTopicsCommand`
  // with the `NextToken` parameter from the previous request.
```

```
  const paginatedTopics = paginateListTopics({ client }, {});
  const topics = [];

  for await (const page of paginatedTopics) {
    if (page.Topics?.length) {
      topics.push(...page.Topics);
    }
  }

  const suffix = topics.length === 1 ? "" : "s";

  console.log(
    `Hello, Amazon SNS! You have ${topics.length} topic${suffix} in your account.`,
  );
  console.log(topics.map((t) => `  * ${t.TopicArn}`).join("\n"));
};
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Verificar se um número de telefone saiu

O exemplo de código a seguir mostra como verificar se um número de telefone cancelou o recebimento de mensagens do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { CheckIfPhoneNumberIsOptedOutCommand } from "@aws-sdk/client-sns";

import { snsClient } from "../libs/snsClient.js";

export const checkIfPhoneNumberIsOptedOut = async (
  phoneNumber = "5555555555",
) => {
  const command = new CheckIfPhoneNumberIsOptedOutCommand({
    phoneNumber,
  });

  const response = await snsClient.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '3341c28a-cdc8-5b39-a3ee-9fb0ee125732',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   isOptedOut: false
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for JavaScript da API.

Confirmar que um proprietário de endpoint deseja receber mensagens

O exemplo de código a seguir mostra como confirmar que o proprietário de um endpoint deseja receber mensagens do Amazon SNS validando o token enviado para o endpoint por uma ação Subscribe anterior.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ConfirmSubscriptionCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} token - This token is sent the subscriber. Only subscribers
 *                         that are not AWS services (HTTP/S, email) need to be
 confirmed.
 * @param {string} topicArn - The ARN of the topic for which you wish to confirm a
 subscription.
 */
export const confirmSubscription = async (
  token = "TOKEN",
  topicArn = "TOPIC_ARN",
) => {
  const response = await snsClient.send(
```

```
    // A subscription only needs to be confirmed if the endpoint type is
    // HTTP/S, email, or in another AWS account.
    new ConfirmSubscriptionCommand({
      Token: token,
      TopicArn: topicArn,
      // If this is true, the subscriber cannot unsubscribe while unauthenticated.
      AuthenticateOnUnsubscribe: "false",
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '4bb5bce9-805a-5517-8333-e1d2cface90b',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:TOPIC_NAME:xxxxxxxx-
xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for JavaScript da API.

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { CreateTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicName - The name of the topic to create.
 */
export const createTopic = async (topicName = "TOPIC_NAME") => {
  const response = await snsClient.send(
    new CreateTopicCommand({ Name: topicName }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '087b8ad2-4593-50c4-a496-d7e90b82cf3e',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:TOPIC_NAME'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for JavaScript da API.

Excluir uma assinatura

O exemplo de código a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { UnsubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} subscriptionArn - The ARN of the subscription to cancel.
 */
const unsubscribe = async (
  subscriptionArn = "arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic:xxxxxxxx-xxxx-xxxx-
xxxx-xxxxxxxxxxxx",
) => {
  const response = await snsClient.send(
    new UnsubscribeCommand({
      SubscriptionArn: subscriptionArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
```

```
  //     httpStatusCode: 200,
  //     requestId: '0178259a-9204-507c-b620-78a7570a44c6',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for JavaScript.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { DeleteTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic to delete.
 */
export const deleteTopic = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new DeleteTopicCommand({ TopicArn: topicArn }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'a10e2886-5a8f-5114-af36-75bd39498332',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for JavaScript da API.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { GetTopicAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic to retrieve attributes for.
 */
export const getTopicAttributes = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new GetTopicAttributesCommand({
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '36b6a24e-5473-5d4e-ac32-ff72d9a73d94',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Attributes: {
  //     Policy: '{...}',
  //     Owner: 'xxxxxxxxxxxx',
  //     SubscriptionsPending: '1',
  //     TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic',
  //     TracingConfig: 'PassThrough',
  //     EffectiveDeliveryPolicy: '{"http":{"defaultHealthyRetryPolicy":
{"minDelayTarget":20,"maxDelayTarget":20,"numRetries":3,"numMaxDelayRetries":0,"numNoDelayRe
{"headerContentType":"text/plain; charset=UTF-8"}}}',
  //     SubscriptionsConfirmed: '0',
  //     DisplayName: '',
```

```
  //     SubscriptionsDeleted: '1'
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe o SDK e os módulos do cliente e chame a API.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set region
AWS.config.update({ region: "REGION" });

// Create promise and SNS service object
var getTopicAttribsPromise = new AWS.SNS({ apiVersion: "2010-03-31" })
  .getTopicAttributes({ TopicArn: "TOPIC_ARN" })
  .promise();

// Handle promise's fulfilled/rejected states
getTopicAttribsPromise
  .then(function (data) {
    console.log(data);
  })
  .catch(function (err) {
    console.error(err, err.stack);
  });
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for JavaScript da API.

Obter as configurações para enviar mensagens SMS

O exemplo de código a seguir mostra como obter as configurações para enviar mensagens SMS do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { GetSMSAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const getSmsAttributes = async () => {
  const response = await snsClient.send(
    // If you have not modified the account-level mobile settings of SNS,
    // the DefaultSMSType is undefined. For this example, it was set to
    // Transactional.
    new GetSMSAttributesCommand({ attributes: ["DefaultSMSType"] }),
  );

  console.log(response);
  // {
```

```
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '67ad8386-4169-58f1-bdb9-debd281d48d5',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   attributes: { DefaultSMSType: 'Transactional' }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for JavaScript.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListSubscriptionsByTopicCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic for which you wish to list
 subscriptions.
 */
export const listSubscriptionsByTopic = async (topicArn = "TOPIC_ARN") => {
  const response = await snsClient.send(
    new ListSubscriptionsByTopicCommand({ TopicArn: topicArn }),
  );

  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '0934fedf-0c4b-572e-9ed2-a3e38fadb0c8',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Subscriptions: [
  //     {
  //       SubscriptionArn: 'PendingConfirmation',
  //       Owner: '901487484989',
  //       Protocol: 'email',
  //       Endpoint: 'corepyle@amazon.com',
  //       TopicArn: 'arn:aws:sns:us-east-1:901487484989:mytopic'
  //     }
  //   ]
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for JavaScript da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { ListTopicsCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const listTopics = async () => {
  const response = await snsClient.send(new ListTopicsCommand({}));
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '936bc5ad-83ca-53c2-b0b7-9891167b909e',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Topics: [ { TopicArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:mytopic' } ]
  // }
  return response;
```

```
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for JavaScript da API.

Publicar uma mensagem com um atributo

O exemplo de código a seguir mostra como publicar uma mensagem com um atributo usando o Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem em um tópico com opções de grupo, duplicação e atributo.

```
async publishMessages() {
  const message = await this.prompter.input({
    message: MESSAGES.publishMessagePrompt,
  });

  let groupId, deduplicationId, choices;

  if (this.isFifo) {
    await this.logger.log(MESSAGES.groupIdNotice);
    groupId = await this.prompter.input({
      message: MESSAGES.groupIdPrompt,
    });

    if (this.autoDedup === false) {
      await this.logger.log(MESSAGES.deduplicationIdNotice);
      deduplicationId = await this.prompter.input({
        message: MESSAGES.deduplicationIdPrompt,
      });
    }
```

```
      choices = await this.prompter.checkbox({
        message: MESSAGES.messageAttributesPrompt,
        choices: toneChoices,
      });
    }

    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });

    if (publishAnother) {
      await this.publishMessages();
    }
  }
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for JavaScript.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { PublishCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string | Record<string, any>} message - The message to send. Can be a
 plain string or an object
 *                                                    if you are using the `json`
 `MessageStructure`.
 * @param {string} topicArn - The ARN of the topic to which you would like to
 publish.
 */
export const publish = async (
  message = "Hello from SNS!",
  topicArn = "TOPIC_ARN",
```

```
) => {
  const response = await snsClient.send(
    new PublishCommand({
      Message: message,
      TopicArn: topicArn,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'e7f77526-e295-5325-9ee4-281a43ad1f05',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   MessageId: 'xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for JavaScript.

Definir as configurações padrão para enviar mensagens SMS

O exemplo de código a seguir mostra como definir as configurações padrão para enviar mensagens SMS usando o Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SetSMSAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {"Transactional" | "Promotional"} defaultSmsType
 */
export const setSmsType = async (defaultSmsType = "Transactional") => {
  const response = await snsClient.send(
    new SetSMSAttributesCommand({
      attributes: {
        // Promotional - (Default) Noncritical messages, such as marketing messages.
        // Transactional - Critical messages that support customer transactions,
        // such as one-time passcodes for multi-factor authentication.
        DefaultSMSType: defaultSmsType,
      },
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '1885b977-2d7e-535e-8214-e44be727e265',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.

- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for JavaScript.

Definir atributos de tópicos

O exemplo de código a seguir mostra como definir atributos para um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SetTopicAttributesCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

export const setTopicAttributes = async (
  topicArn = "TOPIC_ARN",
  attributeName = "DisplayName",
  attributeValue = "Test Topic",
) => {
  const response = await snsClient.send(
    new SetTopicAttributesCommand({
      AttributeName: attributeName,
      AttributeValue: attributeValue,
      TopicArn: topicArn,
    }),
```

```
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'd1b08d0e-e9a4-54c3-b8b1-d03238d2b935',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   }
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for JavaScript da API.

Inscrever uma função do Lambda em um tópico

O exemplo de código a seguir mostra como inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
```

```
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic the subscriber is subscribing to.
 * @param {string} endpoint - The Endpoint ARN of and AWS Lambda function.
 */
export const subscribeLambda = async (
  topicArn = "TOPIC_ARN",
  endpoint = "ENDPOINT",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "lambda",
      TopicArn: topicArn,
      Endpoint: endpoint,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'pending confirmation'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Inscrever uma aplicação móvel em um tópico

O exemplo de código a seguir mostra como inscrever um endpoint de aplicativo móvel para receber notificações de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic the subscriber is subscribing to.
 * @param {string} endpoint - The Endpoint ARN of an application. This endpoint is
 created
 *                            when an application registers for notifications.
 */
export const subscribeApp = async (
  topicArn = "TOPIC_ARN",
  endpoint = "ENDPOINT",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "application",
      TopicArn: topicArn,
```

```
      Endpoint: endpoint,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'pending confirmation'
  // }
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Assinar uma fila do SQS em um tópico

O exemplo de código a seguir mostra como inscrever uma fila do Amazon SQS para receber notificações de um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SubscribeCommand, SNSClient } from "@aws-sdk/client-sns";

const client = new SNSClient({});

export const subscribeQueue = async (
```

```
  topicArn = "TOPIC_ARN",
  queueArn = "QUEUE_ARN",
) => {
  const command = new SubscribeCommand({
    TopicArn: topicArn,
    Protocol: "sqs",
    Endpoint: queueArn,
  });

  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '931e13d9-5e2b-543f-8781-4e9e494c5ff2',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:subscribe-queue-
test-430895:xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Inscrever um endereço de e-mail em um tópico

O exemplo do código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente em um módulo separado e exporte-o.

```
import { SNSClient } from "@aws-sdk/client-sns";

// The AWS Region can be provided here using the `region` property. If you leave it
 blank
// the SDK will default to the region set in your AWS config.
export const snsClient = new SNSClient({});
```

Importe o SDK e os módulos do cliente e chame a API.

```
import { SubscribeCommand } from "@aws-sdk/client-sns";
import { snsClient } from "../libs/snsClient.js";

/**
 * @param {string} topicArn - The ARN of the topic for which you wish to confirm a
 subscription.
 * @param {string} emailAddress - The email address that is subscribed to the topic.
 */
export const subscribeEmail = async (
  topicArn = "TOPIC_ARN",
  emailAddress = "usern@me.com",
) => {
  const response = await snsClient.send(
    new SubscribeCommand({
      Protocol: "email",
      TopicArn: topicArn,
      Endpoint: emailAddress,
    }),
  );
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: 'c8e35bcd-b3c0-5940-9f66-06f6fcc108f0',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'pending confirmation'
```

```
  // }
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Assinar com um filtro em um tópico

O exemplo de código a seguir mostra como assinar com um filtro um tópico do Amazon SNS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SubscribeCommand, SNSClient } from "@aws-sdk/client-sns";

const client = new SNSClient({});

export const subscribeQueueFiltered = async (
  topicArn = "TOPIC_ARN",
  queueArn = "QUEUE_ARN",
) => {
  const command = new SubscribeCommand({
    TopicArn: topicArn,
    Protocol: "sqs",
    Endpoint: queueArn,
    Attributes: {
      // This subscription will only receive messages with the 'event' attribute set
 to 'order_placed'.
      FilterPolicyScope: "MessageAttributes",
      FilterPolicy: JSON.stringify({
        event: ["order_placed"],
      }),
    },
  });
```

```
  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '931e13d9-5e2b-543f-8781-4e9e494c5ff2',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   SubscriptionArn: 'arn:aws:sns:us-east-1:xxxxxxxxxxxx:subscribe-queue-
test-430895:xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx'
  // }
  return response;
};
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for JavaScript.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada para esse fluxo de trabalho.

```
import { SNSClient } from "@aws-sdk/client-sns";
import { SQSClient } from "@aws-sdk/client-sqs";

import { TopicsQueuesWkflw } from "./TopicsQueuesWkflw.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { SlowLogger } from "@aws-sdk-examples/libs/slow-logger.js";

export const startSnsWorkflow = () => {
  const noLoggerDelay = process.argv.find((arg) => arg === "--no-logger-delay");
  const snsClient = new SNSClient({});
  const sqsClient = new SQSClient({});
  const prompter = new Prompter();
  const logger = noLoggerDelay ? console : new SlowLogger(25);

  const wkflw = new TopicsQueuesWkflw(snsClient, sqsClient, prompter, logger);

  wkflw.start();
};
```

O código anterior fornece as dependências necessárias e inicia o fluxo de trabalho. A próxima seção contém a maior parte do exemplo.

```
const toneChoices = [
  { name: "cheerful", value: "cheerful" },
  { name: "funny", value: "funny" },
  { name: "serious", value: "serious" },
  { name: "sincere", value: "sincere" },
];

export class TopicsQueuesWkflw {
  // SNS topic is configured as First-In-First-Out
  isFifo = true;

  // Automatic content-based deduplication is enabled.
  autoDedup = false;

  snsClient;
  sqsClient;
```

```
  topicName;
  topicArn;
  subscriptionArns = [];
  /**
   * @type {{ queueName: string, queueArn: string, queueUrl: string, policy?:
string }[]}
   */
  queues = [];
  prompter;

  /**
   * @param {import('@aws-sdk/client-sns').SNSClient} snsClient
   * @param {import('@aws-sdk/client-sqs').SQSClient} sqsClient
   * @param {import('../../libs/prompter.js').Prompter} prompter
   * @param {import('../../libs/logger.js').Logger} logger
   */
  constructor(snsClient, sqsClient, prompter, logger) {
    this.snsClient = snsClient;
    this.sqsClient = sqsClient;
    this.prompter = prompter;
    this.logger = logger;
  }

  async welcome() {
    await this.logger.log(MESSAGES.description);
  }

  async confirmFifo() {
    await this.logger.log(MESSAGES.snsFifoDescription);
    this.isFifo = await this.prompter.confirm({
      message: MESSAGES.snsFifoPrompt,
    });

    if (this.isFifo) {
      this.logger.logSeparator(MESSAGES.headerDedup);
      await this.logger.log(MESSAGES.deduplicationNotice);
      await this.logger.log(MESSAGES.deduplicationDescription);
      this.autoDedup = await this.prompter.confirm({
        message: MESSAGES.deduplicationPrompt,
      });
    }
  }

  async createTopic() {
```

```
    await this.logger.log(MESSAGES.creatingTopics);
    this.topicName = await this.prompter.input({
      message: MESSAGES.topicNamePrompt,
    });
    if (this.isFifo) {
      this.topicName += ".fifo";
      this.logger.logSeparator(MESSAGES.headerFifoNaming);
      await this.logger.log(MESSAGES.appendFifoNotice);
    }

    const response = await this.snsClient.send(
      new CreateTopicCommand({
        Name: this.topicName,
        Attributes: {
          FifoTopic: this.isFifo ? "true" : "false",
          ...(this.autoDedup ? { ContentBasedDeduplication: "true" } : {}),
        },
      }),
    );

    this.topicArn = response.TopicArn;

    await this.logger.log(
      MESSAGES.topicCreatedNotice
        .replace("${TOPIC_NAME}", this.topicName)
        .replace("${TOPIC_ARN}", this.topicArn),
    );
  }

  async createQueues() {
    await this.logger.log(MESSAGES.createQueuesNotice);
    // Increase this number to add more queues.
    let maxQueues = 2;

    for (let i = 0; i < maxQueues; i++) {
      await this.logger.log(MESSAGES.queueCount.replace("${COUNT}", i + 1));
      let queueName = await this.prompter.input({
        message: MESSAGES.queueNamePrompt.replace(
          "${EXAMPLE_NAME}",
          i === 0 ? "good-news" : "bad-news",
        ),
      });

      if (this.isFifo) {
```

```
        queueName += ".fifo";
        await this.logger.log(MESSAGES.appendFifoNotice);
      }

      const response = await this.sqsClient.send(
        new CreateQueueCommand({
          QueueName: queueName,
          Attributes: { ...(this.isFifo ? { FifoQueue: "true" } : {}) },
        }),
      );

      const { Attributes } = await this.sqsClient.send(
        new GetQueueAttributesCommand({
          QueueUrl: response.QueueUrl,
          AttributeNames: ["QueueArn"],
        }),
      );

      this.queues.push({
        queueName,
        queueArn: Attributes.QueueArn,
        queueUrl: response.QueueUrl,
      });

      await this.logger.log(
        MESSAGES.queueCreatedNotice
          .replace("${QUEUE_NAME}", queueName)
          .replace("${QUEUE_URL}", response.QueueUrl)
          .replace("${QUEUE_ARN}", Attributes.QueueArn),
      );
    }
  }

  async attachQueueIamPolicies() {
    for (const [index, queue] of this.queues.entries()) {
      const policy = JSON.stringify(
        {
          Statement: [
            {
              Effect: "Allow",
              Principal: {
                Service: "sns.amazonaws.com",
              },
              Action: "sqs:SendMessage",
```

```
            Resource: queue.queueArn,
            Condition: {
              ArnEquals: {
                "aws:SourceArn": this.topicArn,
              },
            },
          },
        ],
      },
      null,
      2,
    );

    if (index !== 0) {
      this.logger.logSeparator();
    }

    await this.logger.log(MESSAGES.attachPolicyNotice);
    console.log(policy);
    const addPolicy = await this.prompter.confirm({
      message: MESSAGES.addPolicyConfirmation.replace(
        "${QUEUE_NAME}",
        queue.queueName,
      ),
    });

    if (addPolicy) {
      await this.sqsClient.send(
        new SetQueueAttributesCommand({
          QueueUrl: queue.queueUrl,
          Attributes: {
            Policy: policy,
          },
        }),
      );
      queue.policy = policy;
    } else {
      await this.logger.log(
        MESSAGES.policyNotAttachedNotice.replace(
          "${QUEUE_NAME}",
          queue.queueName,
        ),
      );
    }
```

```
    }
  }

  async subscribeQueuesToTopic() {
    for (const [index, queue] of this.queues.entries()) {
      /**
       * @type {import('@aws-sdk/client-sns').SubscribeCommandInput}
       */
      const subscribeParams = {
        TopicArn: this.topicArn,
        Protocol: "sqs",
        Endpoint: queue.queueArn,
      };
      let tones = [];

      if (this.isFifo) {
        if (index === 0) {
          await this.logger.log(MESSAGES.fifoFilterNotice);
        }
        tones = await this.prompter.checkbox({
          message: MESSAGES.fifoFilterSelect.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
          choices: toneChoices,
        });

        if (tones.length) {
          subscribeParams.Attributes = {
            FilterPolicyScope: "MessageAttributes",
            FilterPolicy: JSON.stringify({
              tone: tones,
            }),
          };
        }
      }

      const { SubscriptionArn } = await this.snsClient.send(
        new SubscribeCommand(subscribeParams),
      );

      this.subscriptionArns.push(SubscriptionArn);

      await this.logger.log(
```

```
        MESSAGES.queueSubscribedNotice
          .replace("${QUEUE_NAME}", queue.queueName)
          .replace("${TOPIC_NAME}", this.topicName)
          .replace("${TONES}", tones.length ? tones.join(", ") : "none"),
      );
    }
  }

  async publishMessages() {
    const message = await this.prompter.input({
      message: MESSAGES.publishMessagePrompt,
    });

    let groupId, deduplicationId, choices;

    if (this.isFifo) {
      await this.logger.log(MESSAGES.groupIdNotice);
      groupId = await this.prompter.input({
        message: MESSAGES.groupIdPrompt,
      });

      if (this.autoDedup === false) {
        await this.logger.log(MESSAGES.deduplicationIdNotice);
        deduplicationId = await this.prompter.input({
          message: MESSAGES.deduplicationIdPrompt,
        });
      }

      choices = await this.prompter.checkbox({
        message: MESSAGES.messageAttributesPrompt,
        choices: toneChoices,
      });
    }

    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
```

```
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });

    if (publishAnother) {
      await this.publishMessages();
    }
  }

  async receiveAndDeleteMessages() {
    for (const queue of this.queues) {
      const { Messages } = await this.sqsClient.send(
        new ReceiveMessageCommand({
          QueueUrl: queue.queueUrl,
        }),
      );

      if (Messages) {
        await this.logger.log(
          MESSAGES.messagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
        console.log(Messages);

        await this.sqsClient.send(
```

```
          new DeleteMessageBatchCommand({
            QueueUrl: queue.queueUrl,
            Entries: Messages.map((message) => ({
              Id: message.MessageId,
              ReceiptHandle: message.ReceiptHandle,
            })),
          }),
        );
      } else {
        await this.logger.log(
          MESSAGES.noMessagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }

    const deleteAndPoll = await this.prompter.confirm({
      message: MESSAGES.deleteAndPollConfirmation,
    });

    if (deleteAndPoll) {
      await this.receiveAndDeleteMessages();
    }
  }

  async destroyResources() {
    for (const subscriptionArn of this.subscriptionArns) {
      await this.snsClient.send(
        new UnsubscribeCommand({ SubscriptionArn: subscriptionArn }),
      );
    }

    for (const queue of this.queues) {
      await this.sqsClient.send(
        new DeleteQueueCommand({ QueueUrl: queue.queueUrl }),
      );
    }

    if (this.topicArn) {
      await this.snsClient.send(
        new DeleteTopicCommand({ TopicArn: this.topicArn }),
      );
```

```
    }
  }

  async start() {
    console.clear();

    try {
      this.logger.logSeparator(MESSAGES.headerWelcome);
      await this.welcome();
      this.logger.logSeparator(MESSAGES.headerFifo);
      await this.confirmFifo();
      this.logger.logSeparator(MESSAGES.headerCreateTopic);
      await this.createTopic();
      this.logger.logSeparator(MESSAGES.headerCreateQueues);
      await this.createQueues();
      this.logger.logSeparator(MESSAGES.headerAttachPolicy);
      await this.attachQueueIamPolicies();
      this.logger.logSeparator(MESSAGES.headerSubscribeQueues);
      await this.subscribeQueuesToTopic();
      this.logger.logSeparator(MESSAGES.headerPublishMessage);
      await this.publishMessages();
      this.logger.logSeparator(MESSAGES.headerReceiveMessages);
      await this.receiveAndDeleteMessages();
    } catch (err) {
      console.error(err);
    } finally {
      await this.destroyResources();
    }
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes

- Publicar
- ReceiveMessage
- SetQueueAttributes
- Assinar
- Cancelar assinatura

Exemplos do Amazon SQS usando SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicialize um cliente Amazon SQS e liste as filas.

```
import { SQSClient, paginateListQueues } from "@aws-sdk/client-sqs";
```

```
export const helloSqs = async () => {
  // The configuration object (`{}`) is required. If the region and credentials
  // are omitted, the SDK uses your local configuration if it exists.
  const client = new SQSClient({});

  // You can also use `ListQueuesCommand`, but to use that command you must
  // handle the pagination yourself. You can do that by sending the
 `ListQueuesCommand`
  // with the `NextToken` parameter from the previous request.
  const paginatedQueues = paginateListQueues({ client }, {});
  const queues = [];

  for await (const page of paginatedQueues) {
    if (page.QueueUrls?.length) {
      queues.push(...page.QueueUrls);
    }
  }

  const suffix = queues.length === 1 ? "" : "s";

  console.log(
    `Hello, Amazon SQS! You have ${queues.length} queue${suffix} in your account.`,
  );
  console.log(queues.map((t) => `  * ${t}`).join("\n"));
};
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Alterar a visibilidade do tempo limite da mensagem

O exemplo de código a seguir mostra como alterar a visibilidade do tempo limite da mensagem do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
import {
  ReceiveMessageCommand,
  ChangeMessageVisibilityCommand,
  SQSClient,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 1,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 1,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  const response = await client.send(
    new ChangeMessageVisibilityCommand({
      QueueUrl: queueUrl,
      ReceiptHandle: Messages[0].ReceiptHandle,
      VisibilityTimeout: 20,
    }),
  );
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem do Amazon SQS e altere sua visibilidade de tempo limite.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region to us-west-2
AWS.config.update({ region: "us-west-2" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "https://sqs.REGION.amazonaws.com/ACCOUNT-ID/QUEUE-NAME";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Receive Error", err);
  } else {
    // Make sure we have a message
    if (data.Messages != null) {
      var visibilityParams = {
        QueueUrl: queueURL,
        ReceiptHandle: data.Messages[0].ReceiptHandle,
        VisibilityTimeout: 20, // 20 second timeout
      };
```

```
      sqs.changeMessageVisibility(visibilityParams, function (err, data) {
        if (err) {
          console.log("Delete Error", err);
        } else {
          console.log("Timeout Changed", data);
        }
      });
    } else {
      console.log("No messages to change");
    }
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for JavaScript da API.

Configurar uma fila de mensagens não entregues

O exemplo de código a seguir mostra como configurar uma fila de mensagens não entregues no Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";
const DEAD_LETTER_QUEUE_ARN = "dead_letter_queue_arn";

export const main = async (
  queueUrl = SQS_QUEUE_URL,
  deadLetterQueueArn = DEAD_LETTER_QUEUE_ARN,
) => {
```

```
  const command = new SetQueueAttributesCommand({
    Attributes: {
      RedrivePolicy: JSON.stringify({
        // Amazon SQS supports dead-letter queues (DLQ), which other
        // queues (source queues) can target for messages that can't
        // be processed (consumed) successfully.
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-dead-letter-queues.html
        deadLetterTargetArn: deadLetterQueueArn,
        maxReceiveCount: "10",
      }),
    },
    QueueUrl: queueUrl,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for JavaScript da API.

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
```

```
const SQS_QUEUE_NAME = "test-queue";

export const main = async (sqsQueueName = SQS_QUEUE_NAME) => {
  const command = new CreateQueueCommand({
    QueueName: sqsQueueName,
    Attributes: {
      DelaySeconds: "60",
      MessageRetentionPeriod: "86400",
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

Crie uma fila do Amazon SQS com sondagem longa.

```
import { CreateQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_NAME = "queue_name";

export const main = async (queueName = SQS_QUEUE_NAME) => {
  const response = await client.send(
    new CreateQueueCommand({
      QueueName: queueName,
      Attributes: {
        // When the wait time for the ReceiveMessage API action is greater than 0,
        // long polling is in effect. The maximum long polling wait time is 20
        // seconds. Long polling helps reduce the cost of using Amazon SQS by,
        // eliminating the number of empty responses and false empty responses.
        // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
        ReceiveMessageWaitTimeSeconds: "20",
      },
    }),
  );
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    DelaySeconds: "60",
    MessageRetentionPeriod: "86400",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

Crie uma fila do Amazon SQS que aguarda a chegada de uma mensagem.

```
// Load the AWS SDK for Node.js
```

```
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
  Attributes: {
    ReceiveMessageWaitTimeSeconds: "20",
  },
};

sqs.createQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for JavaScript da API.

Excluir um lote de mensagens de uma fila

O exemplo de código a seguir mostra como excluir um lote de mensagens de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import {
```

```
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
```

```
      }),
    );
  }
};
```

- Para obter detalhes da API, consulte DeleteMessageBatcha Referência AWS SDK for JavaScript da API.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
```

```
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba e exclua mensagens do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 10,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  VisibilityTimeout: 20,
  WaitTimeSeconds: 0,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Receive Error", err);
  } else if (data.Messages) {
    var deleteParams = {
      QueueUrl: queueURL,
      ReceiptHandle: data.Messages[0].ReceiptHandle,
    };
    sqs.deleteMessage(deleteParams, function (err, data) {
      if (err) {
        console.log("Delete Error", err);
      } else {
        console.log("Message Deleted", data);
      }
    });
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for JavaScript da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
import { DeleteQueueCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "test-queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new DeleteQueueCommand({ QueueUrl: queueUrl });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueUrl: "SQS_QUEUE_URL",
};

sqs.deleteQueue(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for JavaScript da API.

Obter atributos para uma fila

O exemplo de código a seguir mostra como obter atributos para uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { GetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";
```

```
export const getQueueAttributes = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new GetQueueAttributesCommand({
    QueueUrl: queueUrl,
    AttributeNames: ["DelaySeconds"],
  });

  const response = await client.send(command);
  console.log(response);
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '747a1192-c334-5682-a508-4cd5e8dc4e79',
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   Attributes: { DelaySeconds: '1' }
  // }
  return response;
};
```

- Para obter detalhes da API, consulte GetQueueAttributesa Referência AWS SDK for JavaScript da API.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
import { GetQueueUrlCommand, SQSClient } from "@aws-sdk/client-sqs";
```

```
const client = new SQSClient({});
const SQS_QUEUE_NAME = "test-queue";

export const main = async (queueName = SQS_QUEUE_NAME) => {
  const command = new GetQueueUrlCommand({ QueueName: queueName });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha o URL para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  QueueName: "SQS_QUEUE_NAME",
};

sqs.getQueueUrl(params, function (err, data) {
  if (err) {
    console.log("Error", err);
```

```
  } else {
    console.log("Success", data.QueueUrl);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for JavaScript da API.

Listar filas

O exemplo de código a seguir mostra como listar filas do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
import { paginateListQueues, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});

export const main = async () => {
  const paginatedListQueues = paginateListQueues({ client }, {});

  /** @type {string[]} */
  const urls = [];
  for await (const page of paginatedListQueues) {
    const nextUrls = page.QueueUrls?.filter((qurl) => !!qurl) || [];
    urls.push(...nextUrls);
    urls.forEach((url) => console.log(url));
  }

  return urls;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste suas filas do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {};

sqs.listQueues(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.QueueUrls);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for JavaScript da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS.

```
import {
  ReceiveMessageCommand,
  DeleteMessageCommand,
  SQSClient,
  DeleteMessageBatchCommand,
} from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

const receiveMessage = (queueUrl) =>
  client.send(
    new ReceiveMessageCommand({
      AttributeNames: ["SentTimestamp"],
      MaxNumberOfMessages: 10,
      MessageAttributeNames: ["All"],
      QueueUrl: queueUrl,
      WaitTimeSeconds: 20,
      VisibilityTimeout: 20,
    }),
  );

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const { Messages } = await receiveMessage(queueUrl);

  if (!Messages) {
    return;
  }

  if (Messages.length === 1) {
    console.log(Messages[0].Body);
    await client.send(
      new DeleteMessageCommand({
```

```
        QueueUrl: queueUrl,
        ReceiptHandle: Messages[0].ReceiptHandle,
      }),
    );
  } else {
    await client.send(
      new DeleteMessageBatchCommand({
        QueueUrl: queueUrl,
        Entries: Messages.map((message) => ({
          Id: message.MessageId,
          ReceiptHandle: message.ReceiptHandle,
        })),
      }),
    );
  }
};
```

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
import { ReceiveMessageCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new ReceiveMessageCommand({
    AttributeNames: ["SentTimestamp"],
    MaxNumberOfMessages: 1,
    MessageAttributeNames: ["All"],
    QueueUrl: queueUrl,
    // The duration (in seconds) for which the call waits for a message
    // to arrive in the queue before returning. If a message is available,
    // the call returns sooner than WaitTimeSeconds. If no messages are
    // available and the wait time expires, the call returns successfully
    // with an empty list of messages.
    // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/APIReference/
API_ReceiveMessage.html#API_ReceiveMessage_RequestSyntax
    WaitTimeSeconds: 20,
  });

  const response = await client.send(command);
  console.log(response);
```

```
  return response;
};
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create the SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var queueURL = "SQS_QUEUE_URL";

var params = {
  AttributeNames: ["SentTimestamp"],
  MaxNumberOfMessages: 1,
  MessageAttributeNames: ["All"],
  QueueUrl: queueURL,
  WaitTimeSeconds: 20,
};

sqs.receiveMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for JavaScript da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
import { SendMessageCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

export const main = async (sqsQueueUrl = SQS_QUEUE_URL) => {
  const command = new SendMessageCommand({
    QueueUrl: sqsQueueUrl,
    DelaySeconds: 10,
    MessageAttributes: {
      Title: {
        DataType: "String",
        StringValue: "The Whistler",
      },
      Author: {
        DataType: "String",
        StringValue: "John Grisham",
      },
      WeeksOn: {
        DataType: "Number",
        StringValue: "6",
```

```
      },
    },
    MessageBody:
      "Information about current NY Times fiction bestseller for week of
 12/11/2016.",
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem para uma fila do Amazon SQS.

```
// Load the AWS SDK for Node.js
var AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

// Create an SQS service object
var sqs = new AWS.SQS({ apiVersion: "2012-11-05" });

var params = {
  // Remove DelaySeconds parameter and value for FIFO queues
  DelaySeconds: 10,
  MessageAttributes: {
    Title: {
      DataType: "String",
      StringValue: "The Whistler",
```

```
    },
    Author: {
      DataType: "String",
      StringValue: "John Grisham",
    },
    WeeksOn: {
      DataType: "Number",
      StringValue: "6",
    },
  },
  MessageBody:
    "Information about current NY Times fiction bestseller for week of 12/11/2016.",
  // MessageDeduplicationId: "TheWhistler",  // Required for FIFO queues
  // MessageGroupId: "Group1",  // Required for FIFO queues
  QueueUrl: "SQS_QUEUE_URL",
};

sqs.sendMessage(params, function (err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.MessageId);
  }
});
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for JavaScript da API.

Definir atributos de fila

O exemplo de código a seguir mostra como definir os atributos para uma fila do Amazon SQS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue-url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new SetQueueAttributesCommand({
    QueueUrl: queueUrl,
    Attributes: {
      DelaySeconds: "1",
    },
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

Configure uma fila do Amazon SQS para usar sondagem longa.

```
import { SetQueueAttributesCommand, SQSClient } from "@aws-sdk/client-sqs";

const client = new SQSClient({});
const SQS_QUEUE_URL = "queue_url";

export const main = async (queueUrl = SQS_QUEUE_URL) => {
  const command = new SetQueueAttributesCommand({
    Attributes: {
      ReceiveMessageWaitTimeSeconds: "20",
    },
    QueueUrl: queueUrl,
  });

  const response = await client.send(command);
  console.log(response);
  return response;
};
```

- Para obter detalhes da API, consulte SetQueueAttributesa Referência AWS SDK for JavaScript da API.

Cenários

Publicar mensagens em filas

O código de exemplo a seguir mostra como:

- Crie um tópico (FIFO ou não FIFO).
- Assine várias filas no tópico com a opção de aplicar um filtro.
- Publique mensagens no tópico.
- Pesquise as filas para ver as mensagens recebidas.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse é o ponto de entrada para esse fluxo de trabalho.

```
import { SNSClient } from "@aws-sdk/client-sns";
import { SQSClient } from "@aws-sdk/client-sqs";

import { TopicsQueuesWkflw } from "./TopicsQueuesWkflw.js";
import { Prompter } from "@aws-sdk-examples/libs/prompter.js";
import { SlowLogger } from "@aws-sdk-examples/libs/slow-logger.js";

export const startSnsWorkflow = () => {
  const noLoggerDelay = process.argv.find((arg) => arg === "--no-logger-delay");
  const snsClient = new SNSClient({});
  const sqsClient = new SQSClient({});
  const prompter = new Prompter();
  const logger = noLoggerDelay ? console : new SlowLogger(25);

  const wkflw = new TopicsQueuesWkflw(snsClient, sqsClient, prompter, logger);

  wkflw.start();
};
```

O código anterior fornece as dependências necessárias e inicia o fluxo de trabalho. A próxima seção contém a maior parte do exemplo.

```
const toneChoices = [
  { name: "cheerful", value: "cheerful" },
  { name: "funny", value: "funny" },
  { name: "serious", value: "serious" },
  { name: "sincere", value: "sincere" },
];

export class TopicsQueuesWkflw {
  // SNS topic is configured as First-In-First-Out
  isFifo = true;

  // Automatic content-based deduplication is enabled.
  autoDedup = false;

  snsClient;
  sqsClient;
  topicName;
  topicArn;
  subscriptionArns = [];
  /**
   * @type {{ queueName: string, queueArn: string, queueUrl: string, policy?:
 string }[]}
   */
  queues = [];
  prompter;

  /**
   * @param {import('@aws-sdk/client-sns').SNSClient} snsClient
   * @param {import('@aws-sdk/client-sqs').SQSClient} sqsClient
   * @param {import('../../libs/prompter.js').Prompter} prompter
   * @param {import('../../libs/logger.js').Logger} logger
   */
  constructor(snsClient, sqsClient, prompter, logger) {
    this.snsClient = snsClient;
    this.sqsClient = sqsClient;
    this.prompter = prompter;
    this.logger = logger;
```

```
  }

  async welcome() {
    await this.logger.log(MESSAGES.description);
  }

  async confirmFifo() {
    await this.logger.log(MESSAGES.snsFifoDescription);
    this.isFifo = await this.prompter.confirm({
      message: MESSAGES.snsFifoPrompt,
    });

    if (this.isFifo) {
      this.logger.logSeparator(MESSAGES.headerDedup);
      await this.logger.log(MESSAGES.deduplicationNotice);
      await this.logger.log(MESSAGES.deduplicationDescription);
      this.autoDedup = await this.prompter.confirm({
        message: MESSAGES.deduplicationPrompt,
      });
    }
  }

  async createTopic() {
    await this.logger.log(MESSAGES.creatingTopics);
    this.topicName = await this.prompter.input({
      message: MESSAGES.topicNamePrompt,
    });
    if (this.isFifo) {
      this.topicName += ".fifo";
      this.logger.logSeparator(MESSAGES.headerFifoNaming);
      await this.logger.log(MESSAGES.appendFifoNotice);
    }

    const response = await this.snsClient.send(
      new CreateTopicCommand({
        Name: this.topicName,
        Attributes: {
          FifoTopic: this.isFifo ? "true" : "false",
          ...(this.autoDedup ? { ContentBasedDeduplication: "true" } : {}),
        },
      }),
    );

    this.topicArn = response.TopicArn;
```

```
    await this.logger.log(
      MESSAGES.topicCreatedNotice
        .replace("${TOPIC_NAME}", this.topicName)
        .replace("${TOPIC_ARN}", this.topicArn),
    );
  }

  async createQueues() {
    await this.logger.log(MESSAGES.createQueuesNotice);
    // Increase this number to add more queues.
    let maxQueues = 2;

    for (let i = 0; i < maxQueues; i++) {
      await this.logger.log(MESSAGES.queueCount.replace("${COUNT}", i + 1));
      let queueName = await this.prompter.input({
        message: MESSAGES.queueNamePrompt.replace(
          "${EXAMPLE_NAME}",
          i === 0 ? "good-news" : "bad-news",
        ),
      });

      if (this.isFifo) {
        queueName += ".fifo";
        await this.logger.log(MESSAGES.appendFifoNotice);
      }

      const response = await this.sqsClient.send(
        new CreateQueueCommand({
          QueueName: queueName,
          Attributes: { ...(this.isFifo ? { FifoQueue: "true" } : {}) },
        }),
      );

      const { Attributes } = await this.sqsClient.send(
        new GetQueueAttributesCommand({
          QueueUrl: response.QueueUrl,
          AttributeNames: ["QueueArn"],
        }),
      );

      this.queues.push({
        queueName,
        queueArn: Attributes.QueueArn,
```

```
        queueUrl: response.QueueUrl,
      });

      await this.logger.log(
        MESSAGES.queueCreatedNotice
          .replace("${QUEUE_NAME}", queueName)
          .replace("${QUEUE_URL}", response.QueueUrl)
          .replace("${QUEUE_ARN}", Attributes.QueueArn),
      );
    }
  }

  async attachQueueIamPolicies() {
    for (const [index, queue] of this.queues.entries()) {
      const policy = JSON.stringify(
        {
          Statement: [
            {
              Effect: "Allow",
              Principal: {
                Service: "sns.amazonaws.com",
              },
              Action: "sqs:SendMessage",
              Resource: queue.queueArn,
              Condition: {
                ArnEquals: {
                  "aws:SourceArn": this.topicArn,
                },
              },
            },
          ],
        },
        null,
        2,
      );

      if (index !== 0) {
        this.logger.logSeparator();
      }

      await this.logger.log(MESSAGES.attachPolicyNotice);
      console.log(policy);
      const addPolicy = await this.prompter.confirm({
        message: MESSAGES.addPolicyConfirmation.replace(
```

```
          "${QUEUE_NAME}",
          queue.queueName,
        ),
      });

      if (addPolicy) {
        await this.sqsClient.send(
          new SetQueueAttributesCommand({
            QueueUrl: queue.queueUrl,
            Attributes: {
              Policy: policy,
            },
          }),
        );
        queue.policy = policy;
      } else {
        await this.logger.log(
          MESSAGES.policyNotAttachedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }
  }

  async subscribeQueuesToTopic() {
    for (const [index, queue] of this.queues.entries()) {
      /**
       * @type {import('@aws-sdk/client-sns').SubscribeCommandInput}
       */
      const subscribeParams = {
        TopicArn: this.topicArn,
        Protocol: "sqs",
        Endpoint: queue.queueArn,
      };
      let tones = [];

      if (this.isFifo) {
        if (index === 0) {
          await this.logger.log(MESSAGES.fifoFilterNotice);
        }
        tones = await this.prompter.checkbox({
          message: MESSAGES.fifoFilterSelect.replace(
```

```
            "${QUEUE_NAME}",
            queue.queueName,
          ),
          choices: toneChoices,
        });

        if (tones.length) {
          subscribeParams.Attributes = {
            FilterPolicyScope: "MessageAttributes",
            FilterPolicy: JSON.stringify({
              tone: tones,
            }),
          };
        }
      }

      const { SubscriptionArn } = await this.snsClient.send(
        new SubscribeCommand(subscribeParams),
      );

      this.subscriptionArns.push(SubscriptionArn);

      await this.logger.log(
        MESSAGES.queueSubscribedNotice
          .replace("${QUEUE_NAME}", queue.queueName)
          .replace("${TOPIC_NAME}", this.topicName)
          .replace("${TONES}", tones.length ? tones.join(", ") : "none"),
      );
    }
  }

  async publishMessages() {
    const message = await this.prompter.input({
      message: MESSAGES.publishMessagePrompt,
    });

    let groupId, deduplicationId, choices;

    if (this.isFifo) {
      await this.logger.log(MESSAGES.groupIdNotice);
      groupId = await this.prompter.input({
        message: MESSAGES.groupIdPrompt,
      });
```

```
      if (this.autoDedup === false) {
        await this.logger.log(MESSAGES.deduplicationIdNotice);
        deduplicationId = await this.prompter.input({
          message: MESSAGES.deduplicationIdPrompt,
        });
      }

      choices = await this.prompter.checkbox({
        message: MESSAGES.messageAttributesPrompt,
        choices: toneChoices,
      });
    }

    await this.snsClient.send(
      new PublishCommand({
        TopicArn: this.topicArn,
        Message: message,
        ...(groupId
          ? {
              MessageGroupId: groupId,
            }
          : {}),
        ...(deduplicationId
          ? {
              MessageDeduplicationId: deduplicationId,
            }
          : {}),
        ...(choices
          ? {
              MessageAttributes: {
                tone: {
                  DataType: "String.Array",
                  StringValue: JSON.stringify(choices),
                },
              },
            }
          : {}),
      }),
    );

    const publishAnother = await this.prompter.confirm({
      message: MESSAGES.publishAnother,
    });
```

```
    if (publishAnother) {
      await this.publishMessages();
    }
  }

  async receiveAndDeleteMessages() {
    for (const queue of this.queues) {
      const { Messages } = await this.sqsClient.send(
        new ReceiveMessageCommand({
          QueueUrl: queue.queueUrl,
        }),
      );

      if (Messages) {
        await this.logger.log(
          MESSAGES.messagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
        console.log(Messages);

        await this.sqsClient.send(
          new DeleteMessageBatchCommand({
            QueueUrl: queue.queueUrl,
            Entries: Messages.map((message) => ({
              Id: message.MessageId,
              ReceiptHandle: message.ReceiptHandle,
            })),
          }),
        );
      } else {
        await this.logger.log(
          MESSAGES.noMessagesReceivedNotice.replace(
            "${QUEUE_NAME}",
            queue.queueName,
          ),
        );
      }
    }

    const deleteAndPoll = await this.prompter.confirm({
      message: MESSAGES.deleteAndPollConfirmation,
    });
```

```
    if (deleteAndPoll) {
      await this.receiveAndDeleteMessages();
    }
  }

  async destroyResources() {
    for (const subscriptionArn of this.subscriptionArns) {
      await this.snsClient.send(
        new UnsubscribeCommand({ SubscriptionArn: subscriptionArn }),
      );
    }

    for (const queue of this.queues) {
      await this.sqsClient.send(
        new DeleteQueueCommand({ QueueUrl: queue.queueUrl }),
      );
    }

    if (this.topicArn) {
      await this.snsClient.send(
        new DeleteTopicCommand({ TopicArn: this.topicArn }),
      );
    }
  }

  async start() {
    console.clear();

    try {
      this.logger.logSeparator(MESSAGES.headerWelcome);
      await this.welcome();
      this.logger.logSeparator(MESSAGES.headerFifo);
      await this.confirmFifo();
      this.logger.logSeparator(MESSAGES.headerCreateTopic);
      await this.createTopic();
      this.logger.logSeparator(MESSAGES.headerCreateQueues);
      await this.createQueues();
      this.logger.logSeparator(MESSAGES.headerAttachPolicy);
      await this.attachQueueIamPolicies();
      this.logger.logSeparator(MESSAGES.headerSubscribeQueues);
      await this.subscribeQueuesToTopic();
      this.logger.logSeparator(MESSAGES.headerPublishMessage);
      await this.publishMessages();
```

```
      this.logger.logSeparator(MESSAGES.headerReceiveMessages);
      await this.receiveAndDeleteMessages();
    } catch (err) {
      console.error(err);
    } finally {
      await this.destroyResources();
    }
  }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publicar
  - ReceiveMessage
  - SetQueueAttributes
  - Assinar
  - Cancelar assinatura

Exemplos de Step Functions usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Step Functions.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Iniciar execução de máquina de estado

O exemplo de código a seguir mostra como iniciar uma execução de máquina de estado do Step Functions.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

import { SFNClient, StartExecutionCommand } from "@aws-sdk/client-sfn";

/**
 * @param {{ sfnClient: SFNClient, stateMachineArn: string }} config
 */
export async function startExecution({ sfnClient, stateMachineArn }) {
  const response = await sfnClient.send(
    new StartExecutionCommand({
      stateMachineArn,
    }),
  );
  console.log(response);
  // Example response:
  // {
  //   '$metadata': {
  //     httpStatusCode: 200,
  //     requestId: '202a9309-c16a-454b-adeb-c4d19afe3bf2',
```

```
  //     extendedRequestId: undefined,
  //     cfId: undefined,
  //     attempts: 1,
  //     totalRetryDelay: 0
  //   },
  //   executionArn: 'arn:aws:states:us-
east-1:000000000000:execution:MyStateMachine:aaaaaaaa-f787-49fb-a20c-1b61c64eafe6',
  //   startDate: 2024-01-04T15:54:08.362Z
  // }
  return response;
}

// Call function if run directly
import { fileURLToPath } from "url";
if (process.argv[1] === fileURLToPath(import.meta.url)) {
  startExecution({ sfnClient: new SFNClient({}), stateMachineArn: "ARN" });
}
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for JavaScript da API.

AWS STSexemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
import { STSClient } from "@aws-sdk/client-sts";
// Set the AWS Region.
const REGION = "us-east-1";
// Create an AWS STS service client object.
export const client = new STSClient({ region: REGION });
```

Assuma um perfil do IAM.

```
import { AssumeRoleCommand } from "@aws-sdk/client-sts";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Returns a set of temporary security credentials that you can use to
    // access Amazon Web Services resources that you might not normally
    // have access to.
    const command = new AssumeRoleCommand({
      // The Amazon Resource Name (ARN) of the role to assume.
      RoleArn: "ROLE_ARN",
      // An identifier for the assumed role session.
      RoleSessionName: "session1",
      // The duration, in seconds, of the role session. The value specified
      // can range from 900 seconds (15 minutes) up to the maximum session
      // duration set for the role.
```

```
      DurationSeconds: 900,
    });
    const response = await client.send(command);
    console.log(response);
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

SDK para JavaScript (v2)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Load the AWS SDK for Node.js
const AWS = require("aws-sdk");
// Set the region
AWS.config.update({ region: "REGION" });

var roleToAssume = {
  RoleArn: "arn:aws:iam::123456789012:role/RoleName",
  RoleSessionName: "session1",
  DurationSeconds: 900,
};
var roleCreds;

// Create the STS service object
var sts = new AWS.STS({ apiVersion: "2011-06-15" });

//Assume Role
sts.assumeRole(roleToAssume, function (err, data) {
  if (err) console.log(err, err.stack);
  else {
    roleCreds = {
      accessKeyId: data.Credentials.AccessKeyId,
      secretAccessKey: data.Credentials.SecretAccessKey,
```

```
      sessionToken: data.Credentials.SessionToken,
    };
    stsGetCallerIdentity(roleCreds);
  }
});

//Get Arn of current identity
function stsGetCallerIdentity(creds) {
  var stsParams = { credentials: creds };
  // Create STS service object
  var sts = new AWS.STS(stsParams);

  sts.getCallerIdentity({}, function (err, data) {
    if (err) {
      console.log(err, err.stack);
    } else {
      console.log(data.Arn);
    }
  });
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for JavaScript da API.

AWS Supportexemplos usando o SDK para JavaScript (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com AWS Support.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque `main()` para executar o exemplo.

```
import {
  DescribeServicesCommand,
  SupportClient,
} from "@aws-sdk/client-support";

// Change the value of 'region' to your preferred AWS Region.
const client = new SupportClient({ region: "us-east-1" });

const getServiceCount = async () => {
  try {
    const { services } = await client.send(new DescribeServicesCommand({}));
    return services.length;
  } catch (err) {
    if (err.name === "SubscriptionRequiredException") {
      throw new Error(
        "You must be subscribed to the AWS Support plan to use this feature.",
      );
    } else {
      throw err;
    }
  }
};

export const main = async () => {
  try {
    const count = await getServiceCount();
    console.log(`Hello, AWS Support! There are ${count} services available.`);
  } catch (err) {
    console.error("Failed to get service count: ", err.message);
```

```
  }
};
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for JavaScript da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma comunicação a um caso

O exemplo de código a seguir mostra como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AddCommunicationToCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  let attachmentSetId;

  try {
    // Add a communication to a case.
    const response = await client.send(
      new AddCommunicationToCaseCommand({
        communicationBody: "Adding an attachment.",
        // Set value to an existing support case id.
        caseId: "CASE_ID",
```

```
        // Optional. Set value to an existing attachment set id to add attachments
 to the case.
        attachmentSetId,
      }),
    );
    console.log(response);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for JavaScript da API.

Adicionar um anexo a um conjunto

O exemplo de código a seguir mostra como adicionar um anexo do AWS Support a um conjunto de anexos.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { AddAttachmentsToSetCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a new attachment set or add attachments to an existing set.
    // Provide an 'attachmentSetId' value to add attachments to an existing set.
    // Use AddCommunicationToCase or CreateCase to associate an attachment set with
 a support case.
    const response = await client.send(
      new AddAttachmentsToSetCommand({
```

```
        // You can add up to three attachments per set. The size limit is 5 MB per
 attachment.
        attachments: [
          {
            fileName: "example.txt",
            data: new TextEncoder().encode("some example text"),
          },
        ],
      }),
    );
    // Use this ID in AddCommunicationToCase or CreateCase.
    console.log(response.attachmentSetId);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for JavaScript da API.

Criar um caso

O exemplo de código a seguir mostra como criar um novo caso do AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { CreateCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Create a new case and log the case id.
```

```
    // Important: This creates a real support case in your account.
    const response = await client.send(
      new CreateCaseCommand({
        // The subject line of the case.
        subject: "IGNORE: Test case",
        // Use DescribeServices to find available service codes for each service.
        serviceCode: "service-quicksight-end-user",
        // Use DescribeSecurityLevels to find available severity codes for your
 support plan.
        severityCode: "low",
        // Use DescribeServices to find available category codes for each service.
        categoryCode: "end-user-support",
        // The main description of the support case.
        communicationBody: "This is a test. Please ignore.",
      }),
    );
    console.log(response.caseId);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for JavaScript da API.

Descrever um anexo

O exemplo de código a seguir mostra como descrever um anexo para um caso do AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeAttachmentCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";
```

```
export const main = async () => {
  try {
    // Get the metadata and content of an attachment.
    const response = await client.send(
      new DescribeAttachmentCommand({
        // Set value to an existing attachment id.
        // Use DescribeCommunications or DescribeCases to find an attachment id.
        attachmentId: "ATTACHMENT_ID",
      }),
    );
    console.log(response.attachment?.fileName);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for JavaScript da API.

Descrever casos

O exemplo de código a seguir mostra como descrever casos do AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeCasesCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get all of the unresolved cases in your account.
    // Filter or expand results by providing parameters to the DescribeCasesCommand.
 Refer
```

```
    // to the TypeScript definition and the API doc for more information on possible
 parameters.
    // https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/client-
support/interfaces/describecasescommandinput.html
    const response = await client.send(new DescribeCasesCommand({}));
    const caseIds = response.cases.map((supportCase) => supportCase.caseId);
    console.log(caseIds);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for JavaScript da API.

Descrever as comunicações

O exemplo de código a seguir mostra como descrever as comunicações do AWS Support para um caso.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeCommunicationsCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get all communications for the support case.
    // Filter results by providing parameters to the DescribeCommunicationsCommand.
 Refer
    // to the TypeScript definition and the API doc for more information on possible
 parameters.
```

```
    // https://docs.aws.amazon.com/AWSJavaScriptSDK/v3/latest/clients/client-
support/interfaces/describecommunicationscommandinput.html
    const response = await client.send(
      new DescribeCommunicationsCommand({
        // Set value to an existing case id.
        caseId: "CASE_ID",
      }),
    );
    const text = response.communications.map((item) => item.body).join("\n");
    console.log(text);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for JavaScript da API.

Descrever os níveis de gravidade

O exemplo de código a seguir mostra como descrever os níveis de gravidade do AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { DescribeSeverityLevelsCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

export const main = async () => {
  try {
    // Get the list of severity levels.
    // The available values depend on the support plan for the account.
    const response = await client.send(new DescribeSeverityLevelsCommand({}));
    console.log(response.severityLevels);
```

```
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for JavaScript da API.

Resolver caso

O exemplo de código a seguir mostra como resolver um caso do AWS Support.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import { ResolveCaseCommand } from "@aws-sdk/client-support";

import { client } from "../libs/client.js";

const main = async () => {
  try {
    const response = await client.send(
      new ResolveCaseCommand({
        caseId: "CASE_ID",
      }),
    );

    console.log(response.finalCaseStatus);
    return response;
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for JavaScript da API.

Cenários

Conceitos básicos de casos

O código de exemplo a seguir mostra como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.
- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo no terminal.

```
import {
  AddAttachmentsToSetCommand,
  AddCommunicationToCaseCommand,
  CreateCaseCommand,
  DescribeAttachmentCommand,
  DescribeCasesCommand,
  DescribeCommunicationsCommand,
  DescribeServicesCommand,
  DescribeSeverityLevelsCommand,
  ResolveCaseCommand,
  SupportClient,
} from "@aws-sdk/client-support";
```

```
import inquirer from "inquirer";

// Retry an asynchronous function on failure.
const retry = async ({ intervalInMs = 500, maxRetries = 10 }, fn) => {
  try {
    return await fn();
  } catch (err) {
    console.log(`Function call failed. Retrying.`);
    console.error(err.message);
    if (maxRetries === 0) throw err;
    await new Promise((resolve) => setTimeout(resolve, intervalInMs));
    return retry({ intervalInMs, maxRetries: maxRetries - 1 }, fn);
  }
};

const wrapText = (text, char = "=") => {
  const rule = char.repeat(80);
  return `${rule}\n    ${text}\n${rule}\n`;
};

const client = new SupportClient({ region: "us-east-1" });

// Verify that the account has a Support plan.
export const verifyAccount = async () => {
  const command = new DescribeServicesCommand({});

  try {
    await client.send(command);
  } catch (err) {
    if (err.name === "SubscriptionRequiredException") {
      throw new Error(
        "You must be subscribed to the AWS Support plan to use this feature."
      );
    } else {
      throw err;
    }
  }
};

// Get the list of available services.
export const getService = async () => {
  const { services } = await client.send(new DescribeServicesCommand({}));
  const { selectedService } = await inquirer.prompt({
    name: "selectedService",
```

```
    type: "list",
    message:
      "Select a service. Your support case will be created for this service. The
 list of services is truncated for readability.",
    choices: services.slice(0, 10).map((s) => ({ name: s.name, value: s })),
  });
  return selectedService;
};

// Get the list of available support case categories for a service.
export const getCategory = async (service) => {
  const { selectedCategory } = await inquirer.prompt({
    name: "selectedCategory",
    type: "list",
    message: "Select a category.",
    choices: service.categories.map((c) => ({ name: c.name, value: c })),
  });
  return selectedCategory;
};

// Get the available severity levels for the account.
export const getSeverityLevel = async () => {
  const command = new DescribeSeverityLevelsCommand({});
  const { severityLevels } = await client.send(command);
  const { selectedSeverityLevel } = await inquirer.prompt({
    name: "selectedSeverityLevel",
    type: "list",
    message: "Select a severity level.",
    choices: severityLevels.map((s) => ({ name: s.name, value: s })),
  });
  return selectedSeverityLevel;
};

// Create a new support case and return the caseId.
export const createCase = async ({
  selectedService,
  selectedCategory,
  selectedSeverityLevel,
}) => {
  const command = new CreateCaseCommand({
    subject: "IGNORE: Test case",
    communicationBody: "This is a test. Please ignore.",
    serviceCode: selectedService.code,
    categoryCode: selectedCategory.code,
```

```
    severityCode: selectedSeverityLevel.code,
  });
  const { caseId } = await client.send(command);
  return caseId;
};

// Get a list of open support cases created today.
export const getTodaysOpenCases = async () => {
  const d = new Date();
  const startOfToday = new Date(d.getFullYear(), d.getMonth(), d.getDate());
  const command = new DescribeCasesCommand({
    includeCommunications: false,
    afterTime: startOfToday.toISOString(),
  });

  const { cases } = await client.send(command);

  if (cases.length === 0) {
    throw new Error(
      "Unexpected number of cases. Expected more than 0 open cases."
    );
  }
  return cases;
};

// Create an attachment set.
export const createAttachmentSet = async () => {
  const command = new AddAttachmentsToSetCommand({
    attachments: [
      {
        fileName: "example.txt",
        data: new TextEncoder().encode("some example text"),
      },
    ],
  });
  const { attachmentSetId } = await client.send(command);
  return attachmentSetId;
};

export const linkAttachmentSetToCase = async (attachmentSetId, caseId) => {
  const command = new AddCommunicationToCaseCommand({
    attachmentSetId,
    caseId,
    communicationBody: "Adding attachment set to case.",
```

```
  });
  await client.send(command);
};

// Get all communications for a support case.
export const getCommunications = async (caseId) => {
  const command = new DescribeCommunicationsCommand({
    caseId,
  });
  const { communications } = await client.send(command);
  return communications;
};

// Get an attachment set.
export const getFirstAttachment = (communications) => {
  const firstCommWithAttachment = communications.find(
    (c) => c.attachmentSet.length > 0
  );
  return firstCommWithAttachment?.attachmentSet[0].attachmentId;
};

// Get an attachment.
export const getAttachment = async (attachmentId) => {
  const command = new DescribeAttachmentCommand({
    attachmentId,
  });
  const { attachment } = await client.send(command);
  return attachment;
};

// Resolve the case matching the given case ID.
export const resolveCase = async (caseId) => {
  const { shouldResolve } = await inquirer.prompt({
    name: "shouldResolve",
    type: "confirm",
    message: `Do you want to resolve ${caseId}?`,
  });

  if (shouldResolve) {
    const command = new ResolveCaseCommand({
      caseId: caseId,
    });

    await client.send(command);
```

```
    return true;
  }
  return false;
};

// Find a specific case in the list of provided cases by case ID.
// If the case is not found, and the results are paginated, continue
// paging through the results.
export const findCase = async ({ caseId, cases, nextToken }) => {
  const foundCase = cases.find((c) => c.caseId === caseId);

  if (foundCase) {
    return foundCase;
  }

  if (nextToken) {
    const response = await client.send(
      new DescribeCasesCommand({
        nextToken,
        includeResolvedCases: true,
      })
    );
    return findCase({
      caseId,
      cases: response.cases,
      nextToken: response.nextToken,
    });
  }

  throw new Error(`${caseId} not found.`);
};

// Get all cases created today.
export const getTodaysResolvedCases = async (caseIdToWaitFor) => {
  const d = new Date("2023-01-18");
  const startOfToday = new Date(d.getFullYear(), d.getMonth(), d.getDate());
  const command = new DescribeCasesCommand({
    includeCommunications: false,
    afterTime: startOfToday.toISOString(),
    includeResolvedCases: true,
  });
  const { cases, nextToken } = await client.send(command);
  await findCase({ cases, caseId: caseIdToWaitFor, nextToken });
  return cases.filter((c) => c.status === "resolved");
```

```
};

const main = async () => {
  let caseId;
  try {
    console.log(wrapText("Welcome to the AWS Support basic usage scenario."));

    // Verify that the account is subscribed to support.
    await verifyAccount();

    // Provided a truncated list of services and prompt the user to select one.
    const selectedService = await getService();

    // Provided the categories for the selected service and prompt the user to
 select one.
    const selectedCategory = await getCategory(selectedService);

    // Provide the severity available severity levels for the account and prompt the
 user to select one.
    const selectedSeverityLevel = await getSeverityLevel();

    // Create a support case.
    console.log("\nCreating a support case.");
    caseId = await createCase({
      selectedService,
      selectedCategory,
      selectedSeverityLevel,
    });
    console.log(`Support case created: ${caseId}`);

    // Display a list of open support cases created today.
    const todaysOpenCases = await retry(
      { intervalInMs: 1000, maxRetries: 15 },
      getTodaysOpenCases
    );
    console.log(
      `\nOpen support cases created today: ${todaysOpenCases.length}`
    );
    console.log(todaysOpenCases.map((c) => `${c.caseId}`).join("\n"));

    // Create an attachment set.
    console.log("\nCreating an attachment set.");
    const attachmentSetId = await createAttachmentSet();
    console.log(`Attachment set created: ${attachmentSetId}`);
```

```
  // Add the attachment set to the support case.
  console.log(`\nAdding attachment set to ${caseId}`);
  await linkAttachmentSetToCase(attachmentSetId, caseId);
  console.log(`Attachment set added to ${caseId}`);

  // List the communications for a support case.
  console.log(`\nListing communications for ${caseId}`);
  const communications = await getCommunications(caseId);
  console.log(
    communications
      .map(
        (c) =>
          `Communication created on ${c.timeCreated}. Has
${c.attachmentSet.length} attachments.`
      )
      .join("\n")
  );

  // Describe the first attachment.
  console.log(`\nDescribing attachment ${attachmentSetId}`);
  const attachmentId = getFirstAttachment(communications);
  const attachment = await getAttachment(attachmentId);
  console.log(
    `Attachment is the file '${
      attachment.fileName
    }' with data: \n${new TextDecoder().decode(attachment.data)}`
  );

  // Confirm that the support case should be resolved.
  const isResolved = await resolveCase(caseId);
  if (isResolved) {
    // List the resolved cases and include the one previously created.
    // Resolved cases can take a while to appear.
    console.log(
      "\nWaiting for case status to be marked as resolved. This can take some
time."
    );
    const resolvedCases = await retry(
      { intervalInMs: 20000, maxRetries: 15 },
      () => getTodaysResolvedCases(caseId)
    );
    console.log("Resolved cases:");
    console.log(resolvedCases.map((c) => c.caseId).join("\n"));
```

```
    }
  } catch (err) {
    console.error(err);
  }
};
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for JavaScript.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Exemplos do Amazon Transcribe usando SDK JavaScript para (v3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for JavaScript (v3) com o Amazon Transcribe.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir um trabalho de transcrição médica

O exemplo de código a seguir mostra como excluir um trabalho de transcrição do Amazon Transcribe Medical.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Exclua um trabalho de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { DeleteMedicalTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // For example,
 'medical_transciption_demo'
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new DeleteMedicalTranscriptionJobCommand(params)
    );
```

```
    console.log("Success - deleted");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteMedicalTranscriptionJoba Referência AWS SDK for JavaScript da API.

Criar um trabalho de transcrição

O exemplo de código a seguir mostra como excluir um trabalho de transcrição do Amazon Transcribe.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um trabalho de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js
import { DeleteTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  TranscriptionJobName: "JOB_NAME", // Required. For example, 'transciption_demo'
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
```

```
      new DeleteTranscriptionJobCommand(params)
    );
    console.log("Success - deleted");
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte DeleteTranscriptionJoba Referência AWS SDK for JavaScript da API.

Listar trabalhos de transcrição médica

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe Medical.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Liste trabalhos de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartMedicalTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // Required
  OutputBucketName: "OUTPUT_BUCKET_NAME", // Required
  Specialty: "PRIMARYCARE", // Required. Possible values are 'PRIMARYCARE'
  Type: "JOB_TYPE", // Required. Possible values are 'CONVERSATION' and 'DICTATION'
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_FILE_LOCATION",
    // The S3 object location of the input media file. The URI must be in the same
 region
    // as the API endpoint that you are calling.For example,
    // "https://transcribe-demo.s3-REGION.amazonaws.com/hello_world.wav"
  },
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartMedicalTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListMedicalTranscriptionJobsa Referência AWS SDK for JavaScript da API.

Listar trabalhos de transcrição

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste trabalhos de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js

import { ListTranscriptionJobsCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  JobNameContains: "KEYWORD", // Not required. Returns only transcription
  // job names containing this string
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new ListTranscriptionJobsCommand(params)
    );
    console.log("Success", data.TranscriptionJobSummaries);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
```

```
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for JavaScript da API.

Iniciar um trabalho de transcrição médica

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe Medical.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

Inicie um trabalho de transcrição médica.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartMedicalTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  MedicalTranscriptionJobName: "MEDICAL_JOB_NAME", // Required
  OutputBucketName: "OUTPUT_BUCKET_NAME", // Required
  Specialty: "PRIMARYCARE", // Required. Possible values are 'PRIMARYCARE'
  Type: "JOB_TYPE", // Required. Possible values are 'CONVERSATION' and 'DICTATION'
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_FILE_LOCATION",
    // The S3 object location of the input media file. The URI must be in the same
 region
    // as the API endpoint that you are calling.For example,
    // "https://transcribe-demo.s3-REGION.amazonaws.com/hello_world.wav"
  },
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartMedicalTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte StartMedicalTranscriptionJoba Referência AWS SDK for JavaScript da API.

Iniciar um trabalho de transcrição

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe.

SDK para JavaScript (v3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Inicie um trabalho de transcrição.

```
// Import the required AWS SDK clients and commands for Node.js
import { StartTranscriptionJobCommand } from "@aws-sdk/client-transcribe";
import { transcribeClient } from "./libs/transcribeClient.js";

// Set the parameters
export const params = {
  TranscriptionJobName: "JOB_NAME",
  LanguageCode: "LANGUAGE_CODE", // For example, 'en-US'
  MediaFormat: "SOURCE_FILE_FORMAT", // For example, 'wav'
  Media: {
    MediaFileUri: "SOURCE_LOCATION",
    // For example, "https://transcribe-demo.s3-REGION.amazonaws.com/
hello_world.wav"
  },
  OutputBucketName: "OUTPUT_BUCKET_NAME"
};

export const run = async () => {
  try {
    const data = await transcribeClient.send(
      new StartTranscriptionJobCommand(params)
    );
    console.log("Success - put", data);
    return data; // For unit tests.
  } catch (err) {
    console.log("Error", err);
  }
};
run();
```

Crie o cliente.

```
const { TranscribeClient } = require("@aws-sdk/client-transcribe");
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon Transcribe service client object.
const transcribeClient = new TranscribeClient({ region: REGION });
export { transcribeClient };
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for JavaScript.
- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for JavaScript da API.

Exemplos de serviços cruzados usando o SDK para JavaScript (v3)

Os aplicativos de exemplo a seguir usam o AWS SDK for JavaScript (v3) para trabalhar em vários Serviços da AWS.

Os exemplos entre serviços visam um nível avançado de experiência para ajudar a começar a criar aplicativos.

Exemplos

- Criar uma aplicação Amazon Transcribe
- Criar uma aplicação de transmissão do Amazon Transcribe
- Criar uma aplicação para enviar dados para uma tabela do DynamoDB
- Criar um chatbot Amazon Lex para engajar os visitantes do site
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor
- Criar uma aplicação de exploração do Amazon Textract
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Chamar uma função do Lambda em um navegador
- Usar o API Gateway para invocar uma função do Lambda
- Usar Step Functions para invocar funções do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma aplicação Amazon Transcribe

SDK para JavaScript (v3)

Crie uma aplicação que use o Amazon Transcribe para transcrever e exibir gravações de voz no navegador. A aplicação usa dois buckets do Amazon Simple Storage Service (Amazon S3), um para hospedar o código da aplicação e outro para armazenar transcrições. A aplicação usa um grupo de usuários do Amazon Cognito para autenticar seus usuários. Os usuários autenticados têm permissões do AWS Identity and Access Management (IAM) para acessar os serviços da AWS necessários.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon Transcribe

Criar uma aplicação de transmissão do Amazon Transcribe

SDK para JavaScript (v3)

Mostra como usar o Amazon Transcribe para construir uma aplicação que registra, transcreve e traduz áudio ao vivo em tempo real, e envia os resultados por e-mail usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SES
- Amazon Transcribe
- Amazon Translate

Criar uma aplicação para enviar dados para uma tabela do DynamoDB

SDK para JavaScript (v3)

Este exemplo mostra como criar uma aplicação que permite que os usuários enviem dados para uma tabela do Amazon DynamoDB e enviem uma mensagem de texto ao administrador usando o Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Criar um chatbot Amazon Lex para engajar os visitantes do site

SDK para JavaScript (v3)

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, consulte o exemplo completo Construir um chatbot Amazon Lex no guia do desenvolvedor de AWS SDK for JavaScript.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK para JavaScript (v3)

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação Web para monitorar dados do DynamoDB

SDK para JavaScript (v3)

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript (v3) para criar uma aplicação Web que rastreia itens de trabalho em um banco de dados do Amazon Aurora e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end criado com React.js para interagir com um back-end Node.js Express.

- Integre uma aplicação Web React.js com Serviços da AWS.
- Liste, adicione e atualize itens em uma tabela do Aurora.
- Use o Amazon SES para enviar um relatório por e-mail dos itens de trabalho filtrados.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Criar uma aplicação de exploração do Amazon Textract

SDK para JavaScript (v3)

Mostra como usar o AWS SDK for JavaScript para criar uma aplicação React que usa o Amazon Textract para extrair dados de uma imagem de documento e exibi-los em uma página da Web interativa. Este exemplo é executado em um navegador da Web e requer uma identidade autenticada do Amazon Cognito como credenciais. Ele usa o Amazon Simple Storage Service (Amazon S3) para armazenamento e, para notificações, pesquisa uma fila do Amazon Simple

Queue Service (Amazon SQS) que está inscrita em um tópico do Amazon Simple Notification Service (Amazon SNS).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Cognito Identity
- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

SDK para JavaScript (v3)

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub. Os trechos a seguir mostram como o AWS SDK for JavaScript é usado nas funções do Lambda.

```
import {
  ComprehendClient,
  DetectDominantLanguageCommand,
  DetectSentimentCommand,
} from "@aws-sdk/client-comprehend";
```

```
/**
 * Determine the language and sentiment of the extracted text.
 *
 * @param {{ source_text: string}} extractTextOutput
 */
export const handler = async (extractTextOutput) => {
  const comprehendClient = new ComprehendClient({});

  const detectDominantLanguageCommand = new DetectDominantLanguageCommand({
    Text: extractTextOutput.source_text,
  });

  // The source language is required for sentiment analysis and
  // translation in the next step.
  const { Languages } = await comprehendClient.send(
    detectDominantLanguageCommand,
  );

  const languageCode = Languages[0].LanguageCode;

  const detectSentimentCommand = new DetectSentimentCommand({
    Text: extractTextOutput.source_text,
    LanguageCode: languageCode,
  });

  const { Sentiment } = await comprehendClient.send(detectSentimentCommand);

  return {
    sentiment: Sentiment,
    language_code: languageCode,
  };
};
```

```
import {
  DetectDocumentTextCommand,
  TextractClient,
} from "@aws-sdk/client-textract";

/**
 * Fetch the S3 object from the event and analyze it using Amazon Textract.
 *
 * @param {import("@types/aws-lambda").EventBridgeEvent<"Object Created">}
 eventBridgeS3Event
```

```
 */
export const handler = async (eventBridgeS3Event) => {
  const textractClient = new TextractClient();

  const detectDocumentTextCommand = new DetectDocumentTextCommand({
    Document: {
      S3Object: {
        Bucket: eventBridgeS3Event.bucket,
        Name: eventBridgeS3Event.object,
      },
    },
  });

  // Textract returns a list of blocks. A block can be a line, a page, word, etc.
  // Each block also contains geometry of the detected text.
  // For more information on the Block type, see https://docs.aws.amazon.com/
textract/latest/dg/API_Block.html.
  const { Blocks } = await textractClient.send(detectDocumentTextCommand);

  // For the purpose of this example, we are only interested in words.
  const extractedWords = Blocks.filter((b) => b.BlockType === "WORD").map(
    (b) => b.Text,
  );

  return extractedWords.join(" ");
};
```

```
import { PollyClient, SynthesizeSpeechCommand } from "@aws-sdk/client-polly";
import { S3Client } from "@aws-sdk/client-s3";
import { Upload } from "@aws-sdk/lib-storage";

/**
 * Synthesize an audio file from text.
 *
 * @param {{ bucket: string, translated_text: string, object: string}}
 sourceDestinationConfig
 */
export const handler = async (sourceDestinationConfig) => {
  const pollyClient = new PollyClient({});

  const synthesizeSpeechCommand = new SynthesizeSpeechCommand({
    Engine: "neural",
    Text: sourceDestinationConfig.translated_text,
```

```
    VoiceId: "Ruth",
    OutputFormat: "mp3",
  });

  const { AudioStream } = await pollyClient.send(synthesizeSpeechCommand);

  const audioKey = `${sourceDestinationConfig.object}.mp3`;

  // Store the audio file in S3.
  const s3Client = new S3Client();
  const upload = new Upload({
    client: s3Client,
    params: {
      Bucket: sourceDestinationConfig.bucket,
      Key: audioKey,
      Body: AudioStream,
      ContentType: "audio/mp3",
    },
  });

  await upload.done();
  return audioKey;
};
```

```
import {
  TranslateClient,
  TranslateTextCommand,
} from "@aws-sdk/client-translate";

/**
 * Translate the extracted text to English.
 *
 * @param {{ extracted_text: string, source_language_code: string}}
 textAndSourceLanguage
 */
export const handler = async (textAndSourceLanguage) => {
  const translateClient = new TranslateClient({});

  const translateCommand = new TranslateTextCommand({
    SourceLanguageCode: textAndSourceLanguage.source_language_code,
    TargetLanguageCode: "en",
    Text: textAndSourceLanguage.extracted_text,
  });
```

```
  const { TranslatedText } = await translateClient.send(translateCommand);

  return { translated_text: TranslatedText };
};
```

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar equipamentos de proteção individual (EPI) em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação salva os resultados em uma tabela do Amazon DynamoDB e envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Atualizar uma tabela do DynamoDB com resultados.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de objetos usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

SDK para JavaScript (v3)

Mostra como usar o Amazon Rekognition com o AWS SDK for JavaScript a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple

Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Aprenda como:

- Criar um usuário não autenticado usando o Amazon Cognito.
- Analisar imagens em busca de EPI usando o Amazon Rekognition.
- Verificar um endereço de e-mail para o Amazon SES.
- Enviar uma notificação por e-mail usando o Amazon SES.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Chamar uma função do Lambda em um navegador

SDK para JavaScript (v2)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

SDK para JavaScript (v3)

É possível criar uma aplicação baseada em navegador que usa uma função do AWS Lambda para atualizar uma tabela do Amazon DynamoDB com seleções de usuário. Essa aplicação usa o AWS SDK for JavaScript v3.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda

Usar o API Gateway para invocar uma função do Lambda

SDK para JavaScript (v3)

Mostra como criar uma AWS Lambda função usando a API de tempo de JavaScript execução do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Usar Step Functions para invocar funções do Lambda

SDK para JavaScript (v3)

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for JavaScript. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

O Lambda é um serviço computacional que permite executar código sem provisionar ou gerenciar servidores. O Step Functions é um serviço de orquestração sem servidor que permite combinar funções do Lambda e outros serviços da AWS para criar aplicações essenciais aos negócios.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Usar eventos programados para chamar uma função do Lambda

SDK para JavaScript (v3)

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função Lambda usando a API de tempo de execução do JavaScript Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Esse exemplo também está disponível no Guia do desenvolvedor do AWS SDK for JavaScript v3.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda

- Amazon SNS

Exemplos de código para SDK para Java 2.x

Os exemplos a seguir mostram como usar o AWS SDK for Java 2.x com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do Desenvolvedor do SDK for Java 2.x : Saiba mais sobre como usar o Java com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Java 2.x
- Exemplos de serviço cruzado usando o SDK para Java 2.x

Ações e cenários usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de API Gateway usando o SDK para Java 2.x
- Exemplos de Application Auto Scaling usando o SDK for Java 2.x
- Exemplos do Application Recovery Controller usando o SDK para Java 2.x
- Exemplos de Aurora usando o SDK para Java 2.x
- Exemplos de Auto Scaling usando o SDK para Java 2.x
- Exemplos do Amazon Bedrock usando o SDK para Java 2.x
- Exemplos de Amazon Bedrock Runtime usando o SDK para Java 2.x
- CloudFront exemplos usando o SDK for Java 2.x
- CloudWatch exemplos usando o SDK for Java 2.x
- CloudWatch Exemplos de eventos usando o SDK for Java 2.x
- CloudWatch Exemplos de registros usando o SDK for Java 2.x
- Exemplos do Amazon Cognito Identity usando o SDK para Java 2.x
- Exemplos do provedor de identidade do Amazon Cognito usando o SDK para Java 2.x
- Exemplos do Amazon Comprehend usando o SDK para Java 2.x
- Exemplos do DynamoDB usando o SDK para Java 2.x
- Exemplos do Amazon EC2 usando o SDK para Java 2.x
- Exemplos do Amazon ECS usando o SDK para Java 2.x
- Exemplos do Elastic Load Balancing usando o SDK for Java 2.x
- MediaStore exemplos usando o SDK for Java 2.x
- OpenSearch Exemplos de serviços usando o SDK for Java 2.x
- EventBridge exemplos usando o SDK for Java 2.x
- Exemplos do Forecast usando o SDK para Java 2.x
- Exemplos do AWS Glue usando o SDK para Java 2.x
- HealthImaging exemplos usando o SDK for Java 2.x
- Exemplos do IAM usando o SDK para Java 2.x
- Exemplos do AWS IoT usando o SDK para Java 2.x
- Exemplos do AWS IoT data usando o SDK para Java 2.x
- Exemplos do Amazon Keyspaces usando o SDK para Java 2.x

- Exemplos do Kinesis usando o SDK para Java 2.x
- Exemplos do AWS KMS usando o SDK para Java 2.x
- Exemplos do Lambda usando o SDK para Java 2.x
- MediaConvert exemplos usando o SDK for Java 2.x
- Exemplos do Migration Hub usando o SDK para Java 2.x
- Exemplos do Amazon Personalize usando o SDK para Java 2.x
- Exemplos de eventos do Amazon Personalize usando o SDK for Java 2.x
- Exemplos do Amazon Personalize Runtime usando o SDK para Java 2.x
- Exemplos do Amazon Pinpoint usando o SDK para Java 2.x
- Exemplos da API SMS and Voice do Amazon Pinpoint usando o SDK para Java 2.x
- Exemplos do Amazon Polly usando o SDK para Java 2.x
- Exemplos do Amazon RDS usando o SDK para Java 2.x
- Exemplos do Amazon Redshift usando o SDK para Java 2.x
- Exemplos do Amazon Rekognition usando o SDK for Java 2.x
- Exemplos de registro de domínios do Route 53 usando o SDK para Java 2.x
- Exemplos do Amazon S3 usando o SDK para Java 2.x
- Exemplos do S3 Glacier usando o SDK para Java 2.x
- SageMaker exemplos usando o SDK for Java 2.x
- Exemplos do Secrets Manager usando o SDK para Java 2.x
- Exemplos do Amazon SES usando o SDK para Java 2.x
- Exemplos de API v2 do Amazon SES usando o SDK para Java 2.x
- Exemplos do Amazon SNS usando o SDK para Java 2.x
- Exemplos do Amazon SQS usando o SDK para Java 2.x
- Exemplos do Step Functions usando o SDK para Java 2.x
- Exemplos do AWS STS usando o SDK para Java 2.x
- Exemplos do AWS Support usando o SDK para Java 2.x
- Exemplos do Systems Manager usando o SDK para Java 2.x
- Exemplos do Amazon Textract usando o SDK para Java 2.x
- Exemplos do Amazon Transcribe usando o SDK para Java 2.x

Exemplos de API Gateway usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com o API Gateway.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma API REST

O exemplo de código a seguir mostra como criar uma API REST do API Gateway.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createAPI(ApiGatewayClient apiGateway, String restApiId,
String restApiName) {

       try {
           CreateRestApiRequest request = CreateRestApiRequest.builder()
                   .cloneFrom(restApiId)
                   .description("Created using the Gateway Java API")
                   .name(restApiName)
```

```
                .build();

        CreateRestApiResponse response = apiGateway.createRestApi(request);
        System.out.println("The id of the new api is " + response.id());
        return response.id();

    } catch (ApiGatewayException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
    return "";
}
```

- Para obter detalhes da API, consulte CreateRestApia Referência AWS SDK for Java 2.x da API.

Excluir uma API REST

O exemplo de código a seguir mostra como excluir uma API REST do API Gateway.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void deleteAPI(ApiGatewayClient apiGateway, String restApiId) {

    try {
        DeleteRestApiRequest request = DeleteRestApiRequest.builder()
                .restApiId(restApiId)
                .build();

        apiGateway.deleteRestApi(request);
        System.out.println("The API was successfully deleted");

    } catch (ApiGatewayException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteRestApia Referência AWS SDK for Java 2.x da API.

Excluir uma implantação

O exemplo de código a seguir mostra como excluir uma implantação.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteSpecificDeployment(ApiGatewayClient apiGateway, String
restApiId, String deploymentId) {

       try {
           DeleteDeploymentRequest request = DeleteDeploymentRequest.builder()
                   .restApiId(restApiId)
                   .deploymentId(deploymentId)
                   .build();

           apiGateway.deleteDeployment(request);
           System.out.println("Deployment was deleted");

       } catch (ApiGatewayException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteDeploymenta Referência AWS SDK for Java 2.x da API.

Implantar uma API REST

O exemplo de código a seguir mostra como implantar uma API REST do API Gateway.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createNewDeployment(ApiGatewayClient apiGateway, String
restApiId, String stageName) {

       try {
           CreateDeploymentRequest request = CreateDeploymentRequest.builder()
                   .restApiId(restApiId)
                   .description("Created using the AWS API Gateway Java API")
                   .stageName(stageName)
                   .build();

           CreateDeploymentResponse response =
apiGateway.createDeployment(request);
           System.out.println("The id of the deployment is " + response.id());
           return response.id();

       } catch (ApiGatewayException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateDeploymenta Referência AWS SDK for Java 2.x da API.

Exemplos de Application Auto Scaling usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with Application Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Desativa um recurso

O exemplo de código a seguir mostra como desativar um recurso do Application Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.applicationautoscaling.ApplicationAutoScalingClient;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ApplicationAutoScalingExceptio
import
 software.amazon.awssdk.services.applicationautoscaling.model.DeleteScalingPolicyRequest;
import
 software.amazon.awssdk.services.applicationautoscaling.model.DeregisterScalableTargetReques
```

```
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRequest
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRespons
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRequest
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRespons
import
 software.amazon.awssdk.services.applicationautoscaling.model.ScalableDimension;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ServiceNamespace;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DisableDynamoDBAutoscaling {
    public static void main(String[] args) {
        final String usage = """

            Usage:
               <tableId> <policyName>\s

            Where:
               tableId - The table Id value (for example, table/Music).\s
               policyName - The name of the policy (for example, $Music5-scaling-
policy).

            """;
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        ApplicationAutoScalingClient appAutoScalingClient =
 ApplicationAutoScalingClient.builder()
            .region(Region.US_EAST_1)
            .build();
```

```
        ServiceNamespace ns = ServiceNamespace.DYNAMODB;
        ScalableDimension tableWCUs =
ScalableDimension.DYNAMODB_TABLE_WRITE_CAPACITY_UNITS;
        String tableId = args[0];
        String policyName = args[1];

        deletePolicy(appAutoScalingClient, policyName, tableWCUs, ns, tableId);
        verifyScalingPolicies(appAutoScalingClient, tableId, ns, tableWCUs);
        deregisterScalableTarget(appAutoScalingClient, tableId, ns, tableWCUs);
        verifyTarget(appAutoScalingClient, tableId, ns, tableWCUs);
    }

    public static void deletePolicy(ApplicationAutoScalingClient
appAutoScalingClient, String policyName, ScalableDimension tableWCUs,
ServiceNamespace ns, String tableId) {
        try {
            DeleteScalingPolicyRequest delSPRequest =
DeleteScalingPolicyRequest.builder()
                .policyName(policyName)
                .scalableDimension(tableWCUs)
                .serviceNamespace(ns)
                .resourceId(tableId)
                .build();

            appAutoScalingClient.deleteScalingPolicy(delSPRequest);
            System.out.println(policyName +" was deleted successfully.");

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    // Verify that the scaling policy was deleted
    public static void verifyScalingPolicies(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
tableWCUs) {
        DescribeScalingPoliciesRequest dscRequest =
DescribeScalingPoliciesRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceId(tableId)
            .build();
```

```
        DescribeScalingPoliciesResponse response =
 appAutoScalingClient.describeScalingPolicies(dscRequest);
        System.out.println("DescribeScalableTargets result: ");
        System.out.println(response);
    }

    public static void deregisterScalableTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
 tableWCUs) {
        try {
            DeregisterScalableTargetRequest targetRequest =
 DeregisterScalableTargetRequest.builder()
                .scalableDimension(tableWCUs)
                .serviceNamespace(ns)
                .resourceId(tableId)
                .build();

            appAutoScalingClient.deregisterScalableTarget(targetRequest);
            System.out.println("The scalable target was deregistered.");

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    public static void verifyTarget(ApplicationAutoScalingClient
 appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
 tableWCUs) {
        DescribeScalableTargetsRequest dscRequest =
 DescribeScalableTargetsRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceIds(tableId)
            .build();

        DescribeScalableTargetsResponse response =
 appAutoScalingClient.describeScalableTargets(dscRequest);
        System.out.println("DescribeScalableTargets result: ");
        System.out.println(response);
    }
}
```

- Para obter detalhes da API, consulte DeleteScalingPolicya Referência AWS SDK for Java 2.x da API.

Registra um recurso

O exemplo de código a seguir mostra como registrar um recurso do Application Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.applicationautoscaling.ApplicationAutoScalingClient;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ApplicationAutoScalingExceptio
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRequest
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalableTargetsRespons
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRequest
import
 software.amazon.awssdk.services.applicationautoscaling.model.DescribeScalingPoliciesRespons
import software.amazon.awssdk.services.applicationautoscaling.model.PolicyType;
import
 software.amazon.awssdk.services.applicationautoscaling.model.PredefinedMetricSpecification;
import
 software.amazon.awssdk.services.applicationautoscaling.model.PutScalingPolicyRequest;
import
 software.amazon.awssdk.services.applicationautoscaling.model.RegisterScalableTargetRequest;
import software.amazon.awssdk.services.applicationautoscaling.model.ScalingPolicy;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ServiceNamespace;
import
 software.amazon.awssdk.services.applicationautoscaling.model.ScalableDimension;
import software.amazon.awssdk.services.applicationautoscaling.model.MetricType;
```

```
import
 software.amazon.awssdk.services.applicationautoscaling.model.TargetTrackingScalingPolicyCon
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class EnableDynamoDBAutoscaling {
    public static void main(String[] args) {
        final String usage = """

            Usage:
               <tableId> <roleARN> <policyName>\s

            Where:
               tableId - The table Id value (for example, table/Music).
               roleARN - The ARN of the role that has ApplicationAutoScaling
 permissions.
               policyName - The name of the policy to create.

            """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        System.out.println("This example registers an Amazon DynamoDB table, which
 is the resource to scale.");
        String tableId = args[0];
        String roleARN = args[1];
        String policyName = args[2];
        ServiceNamespace ns = ServiceNamespace.DYNAMODB;
        ScalableDimension tableWCUs =
 ScalableDimension.DYNAMODB_TABLE_WRITE_CAPACITY_UNITS;
        ApplicationAutoScalingClient appAutoScalingClient =
 ApplicationAutoScalingClient.builder()
            .region(Region.US_EAST_1)
            .build();
```

```
        registerScalableTarget(appAutoScalingClient, tableId, roleARN, ns,
tableWCUs);
        verifyTarget(appAutoScalingClient, tableId, ns, tableWCUs);
        configureScalingPolicy(appAutoScalingClient, tableId, ns, tableWCUs,
policyName);
    }

    public static void registerScalableTarget(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, String roleARN, ServiceNamespace ns,
ScalableDimension tableWCUs) {
        try {
            RegisterScalableTargetRequest targetRequest =
RegisterScalableTargetRequest.builder()
                .serviceNamespace(ns)
                .scalableDimension(tableWCUs)
                .resourceId(tableId)
                .roleARN(roleARN)
                .minCapacity(5)
                .maxCapacity(10)
                .build();

            appAutoScalingClient.registerScalableTarget(targetRequest);
            System.out.println("You have registered " + tableId);

        } catch (ApplicationAutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
    }

    // Verify that the target was created.
    public static void verifyTarget(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
tableWCUs) {
        DescribeScalableTargetsRequest dscRequest =
DescribeScalableTargetsRequest.builder()
            .scalableDimension(tableWCUs)
            .serviceNamespace(ns)
            .resourceIds(tableId)
            .build();

        DescribeScalableTargetsResponse response =
appAutoScalingClient.describeScalableTargets(dscRequest);
        System.out.println("DescribeScalableTargets result: ");
```

```
        System.out.println(response);
    }

    // Configure a scaling policy.
    public static void configureScalingPolicy(ApplicationAutoScalingClient
appAutoScalingClient, String tableId, ServiceNamespace ns, ScalableDimension
tableWCUs, String policyName) {
        // Check if the policy exists before creating a new one.
        DescribeScalingPoliciesResponse describeScalingPoliciesResponse =
appAutoScalingClient.describeScalingPolicies(DescribeScalingPoliciesRequest.builder()
            .serviceNamespace(ns)
            .resourceId(tableId)
            .scalableDimension(tableWCUs)
            .build());

        if (!describeScalingPoliciesResponse.scalingPolicies().isEmpty()) {
            // If policies exist, consider updating an existing policy instead of
creating a new one.
            System.out.println("Policy already exists. Consider updating it
instead.");
            List<ScalingPolicy> polList =
describeScalingPoliciesResponse.scalingPolicies();
            for (ScalingPolicy pol : polList) {
                System.out.println("Policy name:" +pol.policyName());
            }
        } else {
            // If no policies exist, proceed with creating a new policy.
            PredefinedMetricSpecification specification =
PredefinedMetricSpecification.builder()

.predefinedMetricType(MetricType.DYNAMO_DB_WRITE_CAPACITY_UTILIZATION)
                .build();

            TargetTrackingScalingPolicyConfiguration policyConfiguration =
TargetTrackingScalingPolicyConfiguration.builder()
                .predefinedMetricSpecification(specification)
                .targetValue(50.0)
                .scaleInCooldown(60)
                .scaleOutCooldown(60)
                .build();

            PutScalingPolicyRequest putScalingPolicyRequest =
PutScalingPolicyRequest.builder()
                .targetTrackingScalingPolicyConfiguration(policyConfiguration)
```

```
                .serviceNamespace(ns)
                .scalableDimension(tableWCUs)
                .resourceId(tableId)
                .policyName(policyName)
                .policyType(PolicyType.TARGET_TRACKING_SCALING)
                .build();

            try {
                appAutoScalingClient.putScalingPolicy(putScalingPolicyRequest);
                System.out.println("You have successfully created a scaling policy
 for an Application Auto Scaling scalable target");
            } catch (ApplicationAutoScalingException e) {
                System.err.println("Error: " + e.awsErrorDetails().errorMessage());
            }
        }
    }
}
```

- Para obter detalhes da API, consulte RegisterScalableTargeta Referência AWS SDK for Java 2.x da API.

Exemplos do Application Recovery Controller usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Application Recovery Controller.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter o estado de um controle de roteamento

O exemplo de código a seguir mostra como obter o estado do controle de roteamento do Application Recovery Controller.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static GetRoutingControlStateResponse
 getRoutingControlState(List<ClusterEndpoint> clusterEndpoints,
            String routingControlArn) {
        // As a best practice, we recommend choosing a random cluster endpoint to
 get or
        // set routing control states.
        // For more information, see
        // https://docs.aws.amazon.com/r53recovery/latest/dg/route53-arc-best-
practices.html#route53-arc-best-practices.regional
        Collections.shuffle(clusterEndpoints);
        for (ClusterEndpoint clusterEndpoint : clusterEndpoints) {
            try {
                System.out.println(clusterEndpoint);
                Route53RecoveryClusterClient client =
 Route53RecoveryClusterClient.builder()
                        .endpointOverride(URI.create(clusterEndpoint.endpoint()))
                        .region(Region.of(clusterEndpoint.region())).build();
                return client.getRoutingControlState(
                        GetRoutingControlStateRequest.builder()
                                .routingControlArn(routingControlArn).build());
            } catch (Exception exception) {
                System.out.println(exception);
            }
        }
        return null;
    }
```

- Para obter detalhes da API, consulte GetRoutingControlStatea Referência AWS SDK for Java 2.x da API.

Atualizar o estado de um controle de roteamento

O exemplo de código a seguir mostra como atualizar o estado de um controle de roteamento do Application Recovery Controller.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static UpdateRoutingControlStateResponse
 updateRoutingControlState(List<ClusterEndpoint> clusterEndpoints,
            String routingControlArn,
            String routingControlState) {
        // As a best practice, we recommend choosing a random cluster endpoint to
 get or
        // set routing control states.
        // For more information, see
        // https://docs.aws.amazon.com/r53recovery/latest/dg/route53-arc-best-
practices.html#route53-arc-best-practices.regional
        Collections.shuffle(clusterEndpoints);
        for (ClusterEndpoint clusterEndpoint : clusterEndpoints) {
            try {
                System.out.println(clusterEndpoint);
                Route53RecoveryClusterClient client =
 Route53RecoveryClusterClient.builder()
                        .endpointOverride(URI.create(clusterEndpoint.endpoint()))
                        .region(Region.of(clusterEndpoint.region()))
                        .build();
                return client.updateRoutingControlState(
                        UpdateRoutingControlStateRequest.builder()

 .routingControlArn(routingControlArn).routingControlState(routingControlState).build());
            } catch (Exception exception) {
                System.out.println(exception);
```

```
            }
        }
        return null;
    }
```

- Para obter detalhes da API, consulte UpdateRoutingControlStatea Referência AWS SDK for Java 2.x da API.

Exemplos de Aurora usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.paginators.DescribeDBClustersIterable;

public class DescribeDbClusters {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeClusters(rdsClient);
        rdsClient.close();
    }

    public static void describeClusters(RdsClient rdsClient) {
        DescribeDBClustersIterable clustersIterable =
 rdsClient.describeDBClustersPaginator();
        clustersIterable.stream()
                .flatMap(r -> r.dbClusters().stream())
                .forEach(cluster -> System.out
                        .println("Database name: " + cluster.databaseName() + " Arn
 = " + cluster.dbClusterArn()));
    }
}
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Java 2.x.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

O exemplo de código a seguir mostra como criar um cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static String createDBCluster(RdsClient rdsClient, String
dbParameterGroupFamily, String dbName,
           String dbClusterIdentifier, String userName, String password) {
       try {
           CreateDbClusterRequest clusterRequest = CreateDbClusterRequest.builder()
                   .databaseName(dbName)
                   .dbClusterIdentifier(dbClusterIdentifier)
                   .dbClusterParameterGroupName(dbParameterGroupFamily)
                   .engine("aurora-mysql")
                   .masterUsername(userName)
                   .masterUserPassword(password)
                   .build();

           CreateDbClusterResponse response =
rdsClient.createDBCluster(clusterRequest);
           return response.dbCluster().dbClusterArn();

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK for Java 2.x.

Criar um parameter group de cluster de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDBClusterParameterGroup(RdsClient rdsClient, String
dbClusterGroupName,
           String dbParameterGroupFamily) {
       try {
           CreateDbClusterParameterGroupRequest groupRequest =
CreateDbClusterParameterGroupRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .description("Created by using the AWS SDK for Java")
                   .build();

           CreateDbClusterParameterGroupResponse response =
rdsClient.createDBClusterParameterGroup(groupRequest);
           System.out.println("The group name is " +
response.dbClusterParameterGroup().dbClusterParameterGroupName());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na Referência AWS SDK for Java 2.x da API.

Criar um snapshot de cluster de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDBClusterSnapshot(RdsClient rdsClient, String
dbInstanceClusterIdentifier,
           String dbSnapshotIdentifier) {
       try {
           CreateDbClusterSnapshotRequest snapshotRequest =
CreateDbClusterSnapshotRequest.builder()
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                   .build();

           CreateDbClusterSnapshotResponse response =
rdsClient.createDBClusterSnapshot(snapshotRequest);
           System.out.println("The Snapshot ARN is " +
response.dbClusterSnapshot().dbClusterSnapshotArn());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na Referência AWS SDK for Java 2.x da API.

Criar uma instância de banco de dados em um cluster de banco de dados

O exemplo de código a seguir mostra como criar uma instância do DB em um cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static String createDBInstanceCluster(RdsClient rdsClient,
           String dbInstanceIdentifier,
           String dbInstanceClusterIdentifier,
           String instanceClass) {
       try {
           CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .engine("aurora-mysql")
                   .dbInstanceClass(instanceClass)
                   .build();

           CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
           System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
           return response.dbInstance().dbInstanceArn();

       } catch (RdsException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Java 2.x.

Excluir um cluster de banco de dados

O exemplo de código a seguir mostra como excluir um cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void deleteCluster(RdsClient rdsClient, String
dbInstanceClusterIdentifier) {
       try {
           DeleteDbClusterRequest deleteDbClusterRequest =
DeleteDbClusterRequest.builder()
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .skipFinalSnapshot(true)
                   .build();

           rdsClient.deleteDBCluster(deleteDbClusterRequest);
           System.out.println(dbInstanceClusterIdentifier + " was deleted!");

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK for Java 2.x.

Excluir um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteDBClusterGroup(RdsClient rdsClient, String
dbClusterGroupName, String clusterDBARN)
           throws InterruptedException {
       try {
           boolean isDataDel = false;
           boolean didFind;
           String instanceARN;

           // Make sure that the database has been deleted.
           while (!isDataDel) {
               DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
               List<DBInstance> instanceList = response.dbInstances();
               int listSize = instanceList.size();
               didFind = false;
               int index = 1;
               for (DBInstance instance : instanceList) {
                   instanceARN = instance.dbInstanceArn();
                   if (instanceARN.compareTo(clusterDBARN) == 0) {
                       System.out.println(clusterDBARN + " still exists");
                       didFind = true;
                   }
                   if ((index == listSize) && (!didFind)) {
                       // Went through the entire list and did not find the
database ARN.
                       isDataDel = true;
                   }
                   Thread.sleep(sleepTime * 1000);
                   index++;
               }
           }

           DeleteDbClusterParameterGroupRequest clusterParameterGroupRequest =
DeleteDbClusterParameterGroupRequest
                   .builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .build();

           rdsClient.deleteDBClusterParameterGroup(clusterParameterGroupRequest);
           System.out.println(dbClusterGroupName + " was deleted.");

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na AWS SDK for Java 2.x Referência da API.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
       try {
           DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .deleteAutomatedBackups(true)
                   .skipFinalSnapshot(true)
                   .build();

           DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
           System.out.println("The status of the database is " +
response.dbInstance().dbInstanceStatus());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Java 2.x.

Descrever os grupos de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever grupos de parâmetros de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameterGroups(RdsClient rdsClient, String
dbClusterGroupName) {
       try {
           DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .maxRecords(20)
                   .build();

           List<DBClusterParameterGroup> groups =
rdsClient.describeDBClusterParameterGroups(groupsRequest)
                   .dbClusterParameterGroups();
           for (DBClusterParameterGroup group : groups) {
               System.out.println("The group name is " +
group.dbClusterParameterGroupName());
               System.out.println("The group ARN is " +
group.dbClusterParameterGroupArn());
           }

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups em Referência AWS SDK for Java 2.x da API.

Descrever snapshots de cluster de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void waitForSnapshotReady(RdsClient rdsClient, String
dbSnapshotIdentifier,
           String dbInstanceClusterIdentifier) {
       try {
           boolean snapshotReady = false;
           String snapshotReadyStr;
           System.out.println("Waiting for the snapshot to become available.");

           DescribeDbClusterSnapshotsRequest snapshotsRequest =
DescribeDbClusterSnapshotsRequest.builder()
                   .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .build();

           while (!snapshotReady) {
               DescribeDbClusterSnapshotsResponse response =
rdsClient.describeDBClusterSnapshots(snapshotsRequest);
               List<DBClusterSnapshot> snapshotList =
response.dbClusterSnapshots();
               for (DBClusterSnapshot snapshot : snapshotList) {
                   snapshotReadyStr = snapshot.status();
                   if (snapshotReadyStr.contains("available")) {
                       snapshotReady = true;
                   } else {
                       System.out.println(".");
                       Thread.sleep(sleepTime * 5000);
                   }
```

```
                }
            }

            System.out.println("The Snapshot is available!");

        } catch (RdsException | InterruptedException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots em Referência AWS SDK for Java 2.x da API.

Descrever clusters de banco de dados

O exemplo de código a seguir mostra como descrever clusters do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
   public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
       try {
           DescribeDbClusterParametersRequest dbParameterGroupsRequest;
           if (flag == 0) {
               dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                       .dbClusterParameterGroupName(dbCLusterGroupName)
                       .build();
           } else {
               dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                       .dbClusterParameterGroupName(dbCLusterGroupName)
                       .source("user")
```

```
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") == 0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK for Java 2.x.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Waits until the database instance is available.
   public static void waitForInstanceReady(RdsClient rdsClient, String
dbClusterIdentifier) {
       boolean instanceReady = false;
       String instanceReadyStr;
       System.out.println("Waiting for instance to become available.");
       try {
           DescribeDbClustersRequest instanceRequest =
DescribeDbClustersRequest.builder()
                   .dbClusterIdentifier(dbClusterIdentifier)
                   .build();

           while (!instanceReady) {
               DescribeDbClustersResponse response =
rdsClient.describeDBClusters(instanceRequest);
               List<DBCluster> clusterList = response.dbClusters();
               for (DBCluster cluster : clusterList) {
                   instanceReadyStr = cluster.status();
                   if (instanceReadyStr.contains("available")) {
                       instanceReady = true;
                   } else {
                       System.out.print(".");
                       Thread.sleep(sleepTime * 1000);
                   }
               }
           }
           System.out.println("Database cluster is available!");

       } catch (RdsException | InterruptedException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Descrever as versões de mecanismo de banco de dados

O exemplo de código a seguir mostra como descrever as versões de mecanismo de banco de dados do Aurora.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDBEngines(RdsClient rdsClient) {
       try {
           DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                   .engine("aurora-mysql")
                   .defaultOnly(true)
                   .maxRecords(20)
                   .build();

           DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
           List<DBEngineVersion> engines = response.dbEngineVersions();

           // Get all DBEngineVersion objects.
           for (DBEngineVersion engineOb : engines) {
               System.out.println("The name of the DB parameter group family for
the database engine is "
                       + engineOb.dbParameterGroupFamily());
               System.out.println("The name of the database engine " +
engineOb.engine());
               System.out.println("The version number of the database engine " +
engineOb.engineVersion());
           }

       } catch (RdsException e) {
```

```
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Java 2.x da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever as opções para instâncias Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .engine("aurora-mysql")
                    .defaultOnly(true)
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
engineOb.engine());
```

```
                System.out.println("The version number of the database engine " +
engineOb.engineVersion());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Java 2.x API.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
        try {
            DescribeDbClusterParametersRequest dbParameterGroupsRequest;
            if (flag == 0) {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .source("user")
```

```
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") == 0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters em Referência AWS SDK for Java 2.x da API.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como atualizar os parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeDbClusterParameterGroups(RdsClient rdsClient, String
dbClusterGroupName) {
       try {
           DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                   .dbClusterParameterGroupName(dbClusterGroupName)
                   .maxRecords(20)
                   .build();

           List<DBClusterParameterGroup> groups =
rdsClient.describeDBClusterParameterGroups(groupsRequest)
                   .dbClusterParameterGroups();
           for (DBClusterParameterGroup group : groups) {
               System.out.println("The group name is " +
group.dbClusterParameterGroupName());
               System.out.println("The group ARN is " +
group.dbClusterParameterGroupArn());
           }

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na Referência AWS SDK for Java 2.x da API.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For details, see:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 * This Java example performs the following tasks:
 *
 * 1. Gets available engine families for Amazon Aurora MySQL-Compatible Edition
 * by calling the DescribeDbEngineVersions(Engine='aurora-mysql') method.
 * 2. Selects an engine family and creates a custom DB cluster parameter group
```

```
 * by invoking the describeDBClusterParameters method.
 * 3. Gets the parameter groups by invoking the describeDBClusterParameterGroups
 * method.
 * 4. Gets parameters in the group by invoking the describeDBClusterParameters
 * method.
 * 5. Modifies the auto_increment_offset parameter by invoking the
 * modifyDbClusterParameterGroupRequest method.
 * 6. Gets and displays the updated parameters.
 * 7. Gets a list of allowed engine versions by invoking the
 * describeDbEngineVersions method.
 * 8. Creates an Aurora DB cluster database cluster that contains a MySQL
 * database.
 * 9. Waits for DB instance to be ready.
 * 10. Gets a list of instance classes available for the selected engine.
 * 11. Creates a database instance in the cluster.
 * 12. Waits for DB instance to be ready.
 * 13. Creates a snapshot.
 * 14. Waits for DB snapshot to be ready.
 * 15. Deletes the DB cluster.
 * 16. Deletes the DB cluster group.
 */
public class AuroraScenario {
    public static long sleepTime = 20;
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = "\n" +
                "Usage:\n" +
                "    <dbClusterGroupName> <dbParameterGroupFamily>
 <dbInstanceClusterIdentifier> <dbInstanceIdentifier> <dbName>
 <dbSnapshotIdentifier><secretName>"
                +
                "Where:\n" +
                "    dbClusterGroupName - The name of the DB cluster parameter
 group. \n" +
                "    dbParameterGroupFamily - The DB cluster parameter group family
 name (for example, aurora-mysql5.7). \n"
                +
                "    dbInstanceClusterIdentifier - The instance cluster identifier
 value.\n" +
                "    dbInstanceIdentifier - The database instance identifier.\n" +
                "    dbName - The database name.\n" +
                "    dbSnapshotIdentifier - The snapshot identifier.\n" +
```

```
                "    secretName - The name of the AWS Secrets Manager secret that
contains the database credentials\"\n";
        ;

        if (args.length != 7) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbClusterGroupName = args[0];
        String dbParameterGroupFamily = args[1];
        String dbInstanceClusterIdentifier = args[2];
        String dbInstanceIdentifier = args[3];
        String dbName = args[4];
        String dbSnapshotIdentifier = args[5];
        String secretName = args[6];

        // Retrieve the database credentials using AWS Secrets Manager.
        Gson gson = new Gson();
        User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
User.class);
        String username = user.getUsername();
        String userPassword = user.getPassword();

        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Aurora example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Return a list of the available DB engines");
        describeDBEngines(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a custom parameter group");
        createDBClusterParameterGroup(rdsClient, dbClusterGroupName,
dbParameterGroupFamily);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("3. Get the parameter group");
        describeDbClusterParameterGroups(rdsClient, dbClusterGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get the parameters in the group");
        describeDbClusterParameters(rdsClient, dbClusterGroupName, 0);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Modify the auto_increment_offset parameter");
        modifyDBClusterParas(rdsClient, dbClusterGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Display the updated parameter value");
        describeDbClusterParameters(rdsClient, dbClusterGroupName, -1);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of allowed engine versions");
        getAllowedEngines(rdsClient, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Create an Aurora DB cluster database");
        String arnClusterVal = createDBCluster(rdsClient, dbClusterGroupName,
dbName, dbInstanceClusterIdentifier,
                username, userPassword);
        System.out.println("The ARN of the cluster is " + arnClusterVal);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Wait for DB instance to be ready");
        waitForInstanceReady(rdsClient, dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a list of instance classes available for the
selected engine");
        String instanceClass = getListInstanceClasses(rdsClient);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("11. Create a database instance in the cluster.");
        String clusterDBARN = createDBInstanceCluster(rdsClient,
dbInstanceIdentifier, dbInstanceClusterIdentifier,
                instanceClass);
        System.out.println("The ARN of the database is " + clusterDBARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Wait for DB instance to be ready");
        waitDBInstanceReady(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Create a snapshot");
        createDBClusterSnapshot(rdsClient, dbInstanceClusterIdentifier,
dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Wait for DB snapshot to be ready");
        waitForSnapshotReady(rdsClient, dbSnapshotIdentifier,
dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Delete the DB instance");
        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Delete the DB cluster");
        deleteCluster(rdsClient, dbInstanceClusterIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete the DB cluster group");
        deleteDBClusterGroup(rdsClient, dbClusterGroupName, clusterDBARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);
        rdsClient.close();
```

```
    }

    private static SecretsManagerClient getSecretClient() {
        Region region = Region.US_WEST_2;
        return SecretsManagerClient.builder()
                .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
                .build();
    }

    private static String getSecretValues(String secretName) {
        SecretsManagerClient secretClient = getSecretClient();
        GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                .secretId(secretName)
                .build();

        GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
        return valueResponse.secretString();
    }

    public static void deleteDBClusterGroup(RdsClient rdsClient, String
dbClusterGroupName, String clusterDBARN)
            throws InterruptedException {
        try {
            boolean isDataDel = false;
            boolean didFind;
            String instanceARN;

            // Make sure that the database has been deleted.
            while (!isDataDel) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
                List<DBInstance> instanceList = response.dbInstances();
                int listSize = instanceList.size();
                didFind = false;
                int index = 1;
                for (DBInstance instance : instanceList) {
                    instanceARN = instance.dbInstanceArn();
                    if (instanceARN.compareTo(clusterDBARN) == 0) {
                        System.out.println(clusterDBARN + " still exists");
                        didFind = true;
                    }
```

```
                    if ((index == listSize) && (!didFind)) {
                        // Went through the entire list and did not find the
database ARN.
                        isDataDel = true;
                    }
                    Thread.sleep(sleepTime * 1000);
                    index++;
                }
            }

            DeleteDbClusterParameterGroupRequest clusterParameterGroupRequest =
DeleteDbClusterParameterGroupRequest
                    .builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .build();

            rdsClient.deleteDBClusterParameterGroup(clusterParameterGroupRequest);
            System.out.println(dbClusterGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void deleteCluster(RdsClient rdsClient, String
dbInstanceClusterIdentifier) {
        try {
            DeleteDbClusterRequest deleteDbClusterRequest =
DeleteDbClusterRequest.builder()
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .skipFinalSnapshot(true)
                    .build();

            rdsClient.deleteDBCluster(deleteDbClusterRequest);
            System.out.println(dbInstanceClusterIdentifier + " was deleted!");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

```
   public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
       try {
           DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .deleteAutomatedBackups(true)
                   .skipFinalSnapshot(true)
                   .build();

           DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
           System.out.println("The status of the database is " +
response.dbInstance().dbInstanceStatus());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }

   public static void waitForSnapshotReady(RdsClient rdsClient, String
dbSnapshotIdentifier,
           String dbInstanceClusterIdentifier) {
       try {
           boolean snapshotReady = false;
           String snapshotReadyStr;
           System.out.println("Waiting for the snapshot to become available.");

           DescribeDbClusterSnapshotsRequest snapshotsRequest =
DescribeDbClusterSnapshotsRequest.builder()
                   .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                   .dbClusterIdentifier(dbInstanceClusterIdentifier)
                   .build();

           while (!snapshotReady) {
               DescribeDbClusterSnapshotsResponse response =
rdsClient.describeDBClusterSnapshots(snapshotsRequest);
               List<DBClusterSnapshot> snapshotList =
response.dbClusterSnapshots();
               for (DBClusterSnapshot snapshot : snapshotList) {
                   snapshotReadyStr = snapshot.status();
                   if (snapshotReadyStr.contains("available")) {
                       snapshotReady = true;
```

```
                    } else {
                        System.out.println(".");
                        Thread.sleep(sleepTime * 5000);
                    }
                }
            }

            System.out.println("The Snapshot is available!");

        } catch (RdsException | InterruptedException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void createDBClusterSnapshot(RdsClient rdsClient, String
dbInstanceClusterIdentifier,
            String dbSnapshotIdentifier) {
        try {
            CreateDbClusterSnapshotRequest snapshotRequest =
CreateDbClusterSnapshotRequest.builder()
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .dbClusterSnapshotIdentifier(dbSnapshotIdentifier)
                    .build();

            CreateDbClusterSnapshotResponse response =
rdsClient.createDBClusterSnapshot(snapshotRequest);
            System.out.println("The Snapshot ARN is " +
response.dbClusterSnapshot().dbClusterSnapshotArn());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void waitDBInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
```

```
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            String endpoint = "";
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint().address();
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database instance is available! The connection
endpoint is " + endpoint);

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String createDBInstanceCluster(RdsClient rdsClient,
            String dbInstanceIdentifier,
            String dbInstanceClusterIdentifier,
            String instanceClass) {
        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .dbClusterIdentifier(dbInstanceClusterIdentifier)
                    .engine("aurora-mysql")
                    .dbInstanceClass(instanceClass)
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
```

```
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
            return response.dbInstance().dbInstanceArn();

        } catch (RdsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static String getListInstanceClasses(RdsClient rdsClient) {
        try {
            DescribeOrderableDbInstanceOptionsRequest optionsRequest =
DescribeOrderableDbInstanceOptionsRequest
                    .builder()
                    .engine("aurora-mysql")
                    .maxRecords(20)
                    .build();

            DescribeOrderableDbInstanceOptionsResponse response = rdsClient
                    .describeOrderableDBInstanceOptions(optionsRequest);
            List<OrderableDBInstanceOption> instanceOptions =
response.orderableDBInstanceOptions();
            String instanceClass = "";
            for (OrderableDBInstanceOption instanceOption : instanceOptions) {
                instanceClass = instanceOption.dbInstanceClass();
                System.out.println("The instance class is " +
instanceOption.dbInstanceClass());
                System.out.println("The engine version is " +
instanceOption.engineVersion());
            }
            return instanceClass;

        } catch (RdsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Waits until the database instance is available.
    public static void waitForInstanceReady(RdsClient rdsClient, String
dbClusterIdentifier) {
```

```
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbClustersRequest instanceRequest =
DescribeDbClustersRequest.builder()
                    .dbClusterIdentifier(dbClusterIdentifier)
                    .build();

            while (!instanceReady) {
                DescribeDbClustersResponse response =
rdsClient.describeDBClusters(instanceRequest);
                List<DBCluster> clusterList = response.dbClusters();
                for (DBCluster cluster : clusterList) {
                    instanceReadyStr = cluster.status();
                    if (instanceReadyStr.contains("available")) {
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database cluster is available!");

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String createDBCluster(RdsClient rdsClient, String
dbParameterGroupFamily, String dbName,
            String dbClusterIdentifier, String userName, String password) {
        try {
            CreateDbClusterRequest clusterRequest = CreateDbClusterRequest.builder()
                    .databaseName(dbName)
                    .dbClusterIdentifier(dbClusterIdentifier)
                    .dbClusterParameterGroupName(dbParameterGroupFamily)
                    .engine("aurora-mysql")
                    .masterUsername(userName)
                    .masterUserPassword(password)
                    .build();
```

```
            CreateDbClusterResponse response =
rdsClient.createDBCluster(clusterRequest);
            return response.dbCluster().dbClusterArn();

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    // Get a list of allowed engine versions.
    public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
        try {
            DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .engine("aurora-mysql")
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
            List<DBEngineVersion> dbEngines = response.dbEngineVersions();
            for (DBEngineVersion dbEngine : dbEngines) {
                System.out.println("The engine version is " +
dbEngine.engineVersion());
                System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Modify the auto_increment_offset parameter.
    public static void modifyDBClusterParas(RdsClient rdsClient, String
dClusterGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
```

```
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
            paraList.add(parameter1);
            ModifyDbClusterParameterGroupRequest groupRequest =
ModifyDbClusterParameterGroupRequest.builder()
                    .dbClusterParameterGroupName(dClusterGroupName)
                    .parameters(paraList)
                    .build();

            ModifyDbClusterParameterGroupResponse response =
rdsClient.modifyDBClusterParameterGroup(groupRequest);
            System.out.println(
                    "The parameter group " + response.dbClusterParameterGroupName()
+ " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDbClusterParameters(RdsClient rdsClient, String
dbCLusterGroupName, int flag) {
        try {
            DescribeDbClusterParametersRequest dbParameterGroupsRequest;
            if (flag == 0) {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest =
DescribeDbClusterParametersRequest.builder()
                        .dbClusterParameterGroupName(dbCLusterGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbClusterParametersResponse response = rdsClient
                    .describeDBClusterParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
```

```
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") == 0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDbClusterParameterGroups(RdsClient rdsClient, String
dbClusterGroupName) {
        try {
            DescribeDbClusterParameterGroupsRequest groupsRequest =
DescribeDbClusterParameterGroupsRequest.builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .maxRecords(20)
                    .build();

            List<DBClusterParameterGroup> groups =
rdsClient.describeDBClusterParameterGroups(groupsRequest)
                    .dbClusterParameterGroups();
            for (DBClusterParameterGroup group : groups) {
                System.out.println("The group name is " +
group.dbClusterParameterGroupName());
                System.out.println("The group ARN is " +
group.dbClusterParameterGroupArn());
            }

        } catch (RdsException e) {
```

```
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void createDBClusterParameterGroup(RdsClient rdsClient, String
dbClusterGroupName,
            String dbParameterGroupFamily) {
        try {
            CreateDbClusterParameterGroupRequest groupRequest =
CreateDbClusterParameterGroupRequest.builder()
                    .dbClusterParameterGroupName(dbClusterGroupName)
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .description("Created by using the AWS SDK for Java")
                    .build();

            CreateDbClusterParameterGroupResponse response =
rdsClient.createDBClusterParameterGroup(groupRequest);
            System.out.println("The group name is " +
response.dbClusterParameterGroup().dbClusterParameterGroupName());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .engine("aurora-mysql")
                    .defaultOnly(true)
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
```

```
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
 engineOb.engine());
                System.out.println("The version number of the database engine " +
 engineOb.engineVersion());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - Descreva o DB ClusterParameterGroups
  - Descreva o DB ClusterParameters
  - Descreva o DB ClusterSnapshots
  - DescribeDBClusters
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ClusterParameterGroup

Exemplos de Auto Scaling usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingGroup;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import java.util.List;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeAutoScalingGroups {
    public static void main(String[] args) throws InterruptedException {
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        describeGroups(autoScalingClient);
    }

    public static void describeGroups(AutoScalingClient autoScalingClient) {
        DescribeAutoScalingGroupsResponse response =
 autoScalingClient.describeAutoScalingGroups();
        List<AutoScalingGroup> groups = response.autoScalingGroups();
        groups.forEach(group -> {
            System.out.println("Group Name: " + group.autoScalingGroupName());
            System.out.println("Group ARN: " + group.autoScalingGroupARN());
        });
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import
 software.amazon.awssdk.services.autoscaling.model.CreateAutoScalingGroupRequest;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsRequest;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import
 software.amazon.awssdk.services.autoscaling.model.LaunchTemplateSpecification;
import software.amazon.awssdk.services.autoscaling.waiters.AutoScalingWaiter;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateAutoScalingGroup {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <groupName> <launchTemplateName> <serviceLinkedRoleARN>
 <vpcZoneId>

                Where:
                    groupName - The name of the Auto Scaling group.
                    launchTemplateName - The name of the launch template.\s
```

```
                    vpcZoneId - A subnet Id for a virtual private cloud (VPC) where
instances in the Auto Scaling group can be created.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        String launchTemplateName = args[1];
        String vpcZoneId = args[2];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createAutoScalingGroup(autoScalingClient, groupName, launchTemplateName,
vpcZoneId);
        autoScalingClient.close();
    }

    public static void createAutoScalingGroup(AutoScalingClient autoScalingClient,
            String groupName,
            String launchTemplateName,
            String vpcZoneId) {

        try {
            AutoScalingWaiter waiter = autoScalingClient.waiter();
            LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                    .launchTemplateName(launchTemplateName)
                    .build();

            CreateAutoScalingGroupRequest request =
CreateAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .availabilityZones("us-east-1a")
                    .launchTemplate(templateSpecification)
                    .maxSize(1)
                    .minSize(1)
                    .vpcZoneIdentifier(vpcZoneId)
                    .build();

            autoScalingClient.createAutoScalingGroup(request);
```

```
            DescribeAutoScalingGroupsRequest groupsRequest =
 DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
 waiter
                    .waitUntilGroupExists(groupsRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Auto Scaling Group created");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import
 software.amazon.awssdk.services.autoscaling.model.DeleteAutoScalingGroupRequest;

/**
 * Before running this SDK for Java (v2) code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteAutoScalingGroup {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <groupName>

                Where:
                    groupName - The name of the Auto Scaling group.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteAutoScalingGroup(autoScalingClient, groupName);
        autoScalingClient.close();
    }

    public static void deleteAutoScalingGroup(AutoScalingClient autoScalingClient,
 String groupName) {
        try {
            DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
 DeleteAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .forceDelete(true)
                    .build();

            autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
            System.out.println("You successfully deleted " + groupName);

        } catch (AutoScalingException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void disableMetricsCollection(AutoScalingClient autoScalingClient,
String groupName) {
       try {
           DisableMetricsCollectionRequest disableMetricsCollectionRequest =
DisableMetricsCollectionRequest.builder()
                   .autoScalingGroupName(groupName)
                   .metrics("GroupMaxSize")
                   .build();


autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest);
           System.out.println("The disable metrics collection operation was
successful");

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for Java 2.x da API.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void enableMetricsCollection(AutoScalingClient autoScalingClient,
String groupName) {
       try {
           EnableMetricsCollectionRequest collectionRequest =
EnableMetricsCollectionRequest.builder()
                   .autoScalingGroupName(groupName)
                   .metrics("GroupMaxSize")
                   .granularity("1Minute")
                   .build();

           autoScalingClient.enableMetricsCollection(collectionRequest);
           System.out.println("The enable metrics collection operation was
successful");

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for Java 2.x da API.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informação sobre grupos do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.autoscaling.AutoScalingClient;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingException;
import software.amazon.awssdk.services.autoscaling.model.AutoScalingGroup;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsResponse;
import
 software.amazon.awssdk.services.autoscaling.model.DescribeAutoScalingGroupsRequest;
import software.amazon.awssdk.services.autoscaling.model.Instance;
import java.util.List;

/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeAutoScalingInstances {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <groupName>

                Where:
```

```
                    groupName - The name of the Auto Scaling group.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String instanceId = getAutoScaling(autoScalingClient, groupName);
        System.out.println(instanceId);
        autoScalingClient.close();
    }

    public static String getAutoScaling(AutoScalingClient autoScalingClient, String
groupName) {
        try {
            String instanceId = "";
            DescribeAutoScalingGroupsRequest scalingGroupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            DescribeAutoScalingGroupsResponse response = autoScalingClient
                    .describeAutoScalingGroups(scalingGroupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("The group name is " +
group.autoScalingGroupName());
                System.out.println("The group ARN is " +
group.autoScalingGroupARN());

                List<Instance> instances = group.instances();
                for (Instance instance : instances) {
                    instanceId = instance.instanceId();
                }
            }
            return instanceId;
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for Java 2.x da API.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeAutoScalingInstance(AutoScalingClient
autoScalingClient, String id) {
        try {
            DescribeAutoScalingInstancesRequest describeAutoScalingInstancesRequest
= DescribeAutoScalingInstancesRequest
                    .builder()
                    .instanceIds(id)
                    .build();

            DescribeAutoScalingInstancesResponse response = autoScalingClient

.describeAutoScalingInstances(describeAutoScalingInstancesRequest);
            List<AutoScalingInstanceDetails> instances =
response.autoScalingInstances();
            for (AutoScalingInstanceDetails instance : instances) {
                System.out.println("The instance lifecycle state is: " +
instance.lifecycleState());
            }

        } catch (AutoScalingException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for Java 2.x da API.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informação sobre atividades do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeScalingActivities(AutoScalingClient
autoScalingClient, String groupName) {
       try {
           DescribeScalingActivitiesRequest scalingActivitiesRequest =
DescribeScalingActivitiesRequest.builder()
                   .autoScalingGroupName(groupName)
                   .maxRecords(10)
                   .build();

           DescribeScalingActivitiesResponse response = autoScalingClient
                   .describeScalingActivities(scalingActivitiesRequest);
           List<Activity> activities = response.activities();
           for (Activity activity : activities) {
               System.out.println("The activity Id is " + activity.activityId());
               System.out.println("The activity details are " +
activity.details());
           }

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for Java 2.x da API.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo de Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void setDesiredCapacity(AutoScalingClient autoScalingClient,
String groupName) {
       try {
           SetDesiredCapacityRequest capacityRequest =
SetDesiredCapacityRequest.builder()
                   .autoScalingGroupName(groupName)
                   .desiredCapacity(2)
                   .build();

           autoScalingClient.setDesiredCapacity(capacityRequest);
           System.out.println("You have set the DesiredCapacity to 2");

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for Java 2.x da API.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void terminateInstanceInAutoScalingGroup(AutoScalingClient
autoScalingClient, String instanceId) {
       try {
           TerminateInstanceInAutoScalingGroupRequest request =
TerminateInstanceInAutoScalingGroupRequest.builder()
                   .instanceId(instanceId)
                   .shouldDecrementDesiredCapacity(false)
                   .build();

           autoScalingClient.terminateInstanceInAutoScalingGroup(request);
           System.out.println("You have terminated instance " + instanceId);

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo de Auto Scaling.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void updateAutoScalingGroup(AutoScalingClient autoScalingClient,
String groupName,
           String launchTemplateName) {
       try {
           AutoScalingWaiter waiter = autoScalingClient.waiter();
           LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                   .launchTemplateName(launchTemplateName)
                   .build();

           UpdateAutoScalingGroupRequest groupRequest =
UpdateAutoScalingGroupRequest.builder()
                   .maxSize(3)
                   .autoScalingGroupName(groupName)
                   .launchTemplate(templateSpecification)
                   .build();

           autoScalingClient.updateAutoScalingGroup(groupRequest);
           DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                   .autoScalingGroupNames(groupName)
                   .build();

           WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                   .waitUntilGroupInService(groupsRequest);
           waiterResponse.matched().response().ifPresent(System.out::println);
           System.out.println("You successfully updated the auto scaling group  " +
groupName);

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for Java 2.x da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {
```

```
    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-prof-
bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException, InterruptedException
 {
        Scanner in = new Scanner(System.in);
        Database database = new Database();
        AutoScaler autoScaler = new AutoScaler();
        LoadBalancer loadBalancer = new LoadBalancer();

        System.out.println(DASHES);
        System.out.println("Welcome to the demonstration of How to Build and Manage
 a Resilient Service!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("A - SETUP THE RESOURCES");
```

```
        System.out.println("Press Enter when you're ready to start deploying
resources.");
        in.nextLine();
        deploy(loadBalancer);
        System.out.println(DASHES);
        System.out.println(DASHES);
        System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
        System.out.println("Press Enter when you're ready.");
        in.nextLine();
        demo(loadBalancer);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("C - DELETE THE RESOURCES");
        System.out.println("""
                This concludes the demo of how to build and manage a resilient
service.
                To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources
                that were created for this demo.
                """);

        System.out.println("\n Do you want to delete the resources (y/n)? ");
        String userInput = in.nextLine().trim().toLowerCase(); // Capture user input

        if (userInput.equals("y")) {
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }
```

```
   // Deletes the AWS resources used in this example.
   private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
           throws IOException, InterruptedException {
       loadBalancer.deleteLoadBalancer(lbName);
       System.out.println("*** Wait 30 secs for resource to be deleted");
       TimeUnit.SECONDS.sleep(30);
       loadBalancer.deleteTargetGroup(targetGroupName);
       autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
       autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
       autoScaler.deleteTemplate(templateName);
       database.deleteTable(tableName);
   }

   private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
       Scanner in = new Scanner(System.in);
       System.out.println(
               """
                       For this demo, we'll use the AWS SDK for Java (v2) to create
several AWS resources
                       to set up a load-balanced web service endpoint and explore
some ways to make it resilient
                       against various kinds of failures.

                       Some of the resources create by this demo are:
                       \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                       \t* An EC2 launch template that defines EC2 instances that
each contain a Python web server.
                       \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                       \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                       """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
```

```
        database.createTable(tableName, fileName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an EC2 launch template that runs '{startup_script}' when an
instance starts.
                This script starts a Python web server defined in the `server.py`
script. The web server
                listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.
                For demo purposes, this server is run as the root user. In
production, the best practice is to
                run a web server, such as Apache, with least-privileged credentials.

                The template also defines an IAM policy that each instance uses to
assume a role that grants
                permissions to access the DynamoDB recommendation table and Systems
Manager parameters
                that control the flow of the demo.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);
```

```
        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load balancer.
The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets, targetGroupArn,
lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul = loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
```

```
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(), StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group for
your default VPC must
                            allow access from this computer. You can either add it
automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security group
are configured correctly and that");
```

```
            System.out.println("you can successfully make a GET request to the load
balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and shows
how using a resilient
                        architecture can keep the web service running in spite of
these failures.

                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager parameter
named self.param_helper.table.
                        To simulate a failure of the recommendation service, let's
set this parameter to name a non-existent table.
                       """);
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");
```

```
        System.out.println(
                """
                        \nNow, sending a GET request to the load balancer endpoint
returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health checks
don't check for failure of the recommendation service.
                        """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                        Instead of failing when the recommendation service fails,
the web service can return a static response.
                        While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                        """);
        paramHelper.put(paramHelper.failureResponse, "static");

        System.out.println("""
                Now, sending a GET request to the load balancer endpoint returns a
static response.
                The service still reports as healthy because health checks are still
shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance id
value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
```

```
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId = autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " + profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on for
recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto Scaling
instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
```

```
                is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start a
new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load balancing
rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance is
running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }
```

```
   public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
       String[] actions = {
               "Send a GET request to the load balancer endpoint.",
               "Check the health of load balancer targets.",
               "Go to the next part of the demo."
       };
       Scanner scanner = new Scanner(System.in);

       while (true) {
           System.out.println("-".repeat(88));
           System.out.println("See the current state of the service by selecting
one of the following choices:");
           for (int i = 0; i < actions.length; i++) {
               System.out.println(i + ": " + actions[i]);
           }

           try {
               System.out.print("\nWhich action would you like to take? ");
               int choice = scanner.nextInt();
               System.out.println("-".repeat(88));

               switch (choice) {
                   case 0 -> {
                       System.out.println("Request:\n");
                       System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                       CloseableHttpClient httpClient =
HttpClients.createDefault();

                       // Create an HTTP GET request to the ELB.
                       HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                       // Execute the request and get the response.
                       HttpResponse response = httpClient.execute(httpGet);
                       int statusCode = response.getStatusLine().getStatusCode();
                       System.out.println("HTTP Status Code: " + statusCode);

                       // Display the JSON response
                       BufferedReader reader = new BufferedReader(
                               new
InputStreamReader(response.getEntity().getContent()));
                       StringBuilder jsonResponse = new StringBuilder();
```

```
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load balancer
targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
target.target().id(),
                                        target.target().port(),
target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the health
check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value between
0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
```

```
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
```

```
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
```

```
                .builder()
                .name(newInstanceProfileName) // Make sure 'newInstanceProfileName'
is a valid IAM Instance Profile
                                              // name.
                .build();

        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();

        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with profile
%s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }
```

```
            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress) {
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
```

```
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);

            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
```

```
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network, you
     * must instead specify a prefix list ID. You can also temporarily open the port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
```

```
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();

            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse = getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup : securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " + secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " + ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }
```

```
                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to be
open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or to
a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
        software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();

        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
```

```
                .build();

        DescribeSubnetsResponse response = getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
```

```
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
 InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to the
 policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
 DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
```

```
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
 ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
 iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
 listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
 RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance profile
 " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
 DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
```

```
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()
                .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
```

```
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws IOException,
InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();
```

```
        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId, String
targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
                .protocol(protocol)
                .build();
```

```
        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }

    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
    public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
            String protocol) {
        try {
            List<String> subnetIdStrings = subnetIds.stream()
                    .map(Subnet::subnetId)
                    .collect(Collectors.toList());

            CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                    .subnets(subnetIdStrings)
                    .name(lbName)
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();
```

```
            System.out.println("Waiting for Load Balancer " + lbName + " to become
 available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
 loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

 .loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " + e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended, such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
```

```
    public void createTable(String tableName, String fileName) throws IOException {
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");
```

```
            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws IOException
 {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable = enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate

- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.

- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this SDK for Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * In addition, create a launch template. For more information, see the
 * following topic:
 *
 * https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-
templates.html#create-launch-template
 *
 * This code example performs the following operations:
 * 1. Creates an Auto Scaling group using an AutoScalingWaiter.
 * 2. Gets a specific Auto Scaling group and returns an instance Id value.
 * 3. Describes Auto Scaling with the Id value.
 * 4. Enables metrics collection.
 * 5. Update an Auto Scaling group.
 * 6. Describes Account details.
 * 7. Describe account details"
 * 8. Updates an Auto Scaling group to use an additional instance.
 * 9. Gets the specific Auto Scaling group and gets the number of instances.
 * 10. List the scaling activities that have occurred for the group.
 * 11. Terminates an instance in the Auto Scaling group.
 * 12. Stops the metrics collection.
 * 13. Deletes the Auto Scaling group.
 */
```

```
public class AutoScalingScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <groupName> <launchTemplateName> <vpcZoneId>

                Where:
                    groupName - The name of the Auto Scaling group.
                    launchTemplateName - The name of the launch template.\s
                    vpcZoneId - A subnet Id for a virtual private cloud (VPC) where
 instances in the Auto Scaling group can be created.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupName = args[0];
        String launchTemplateName = args[1];
        String vpcZoneId = args[2];
        AutoScalingClient autoScalingClient = AutoScalingClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon EC2 Auto Scaling example
 scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an Auto Scaling group named " + groupName);
        createAutoScalingGroup(autoScalingClient, groupName, launchTemplateName,
 vpcZoneId);
        System.out.println(
                "Wait 1 min for the resources, including the instance. Otherwise, an
 empty instance Id is returned");
        Thread.sleep(60000);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("2. Get Auto Scale group Id value");
        String instanceId = getSpecificAutoScalingGroups(autoScalingClient,
groupName);
        if (instanceId.compareTo("") == 0) {
            System.out.println("Error - no instance Id value");
            System.exit(1);
        } else {
            System.out.println("The instance Id value is " + instanceId);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Describe Auto Scaling with the Id value " +
instanceId);
        describeAutoScalingInstance(autoScalingClient, instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Enable metrics collection " + instanceId);
        enableMetricsCollection(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Update an Auto Scaling group to update max size to
3");
        updateAutoScalingGroup(autoScalingClient, groupName, launchTemplateName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Describe Auto Scaling groups");
        describeAutoScalingGroups(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Describe account details");
        describeAccountLimits(autoScalingClient);
        System.out.println(
                "Wait 1 min for the resources, including the instance. Otherwise, an
empty instance Id is returned");
        Thread.sleep(60000);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("8. Set desired capacity to 2");
        setDesiredCapacity(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get the two instance Id values and state");
        getSpecificAutoScalingGroups(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. List the scaling activities that have occurred for
the group");
        describeScalingActivities(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Terminate an instance in the Auto Scaling group");
        terminateInstanceInAutoScalingGroup(autoScalingClient, instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Stop the metrics collection");
        disableMetricsCollection(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Delete the Auto Scaling group");
        deleteAutoScalingGroup(autoScalingClient, groupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);

        autoScalingClient.close();
    }

    public static void describeScalingActivities(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DescribeScalingActivitiesRequest scalingActivitiesRequest =
DescribeScalingActivitiesRequest.builder()
                    .autoScalingGroupName(groupName)
                    .maxRecords(10)
```

```
                    .build();

            DescribeScalingActivitiesResponse response = autoScalingClient
                    .describeScalingActivities(scalingActivitiesRequest);
            List<Activity> activities = response.activities();
            for (Activity activity : activities) {
                System.out.println("The activity Id is " + activity.activityId());
                System.out.println("The activity details are " +
activity.details());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void setDesiredCapacity(AutoScalingClient autoScalingClient,
String groupName) {
        try {
            SetDesiredCapacityRequest capacityRequest =
SetDesiredCapacityRequest.builder()
                    .autoScalingGroupName(groupName)
                    .desiredCapacity(2)
                    .build();

            autoScalingClient.setDesiredCapacity(capacityRequest);
            System.out.println("You have set the DesiredCapacity to 2");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createAutoScalingGroup(AutoScalingClient autoScalingClient,
            String groupName,
            String launchTemplateName,
            String vpcZoneId) {
        try {
            AutoScalingWaiter waiter = autoScalingClient.waiter();
            LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                    .launchTemplateName(launchTemplateName)
```

```
                    .build();

            CreateAutoScalingGroupRequest request =
CreateAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .availabilityZones("us-east-1a")
                    .launchTemplate(templateSpecification)
                    .maxSize(1)
                    .minSize(1)
                    .vpcZoneIdentifier(vpcZoneId)
                    .build();

            autoScalingClient.createAutoScalingGroup(request);
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                    .waitUntilGroupExists(groupsRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Auto Scaling Group created");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void describeAutoScalingInstance(AutoScalingClient
autoScalingClient, String id) {
        try {
            DescribeAutoScalingInstancesRequest describeAutoScalingInstancesRequest
= DescribeAutoScalingInstancesRequest
                    .builder()
                    .instanceIds(id)
                    .build();

            DescribeAutoScalingInstancesResponse response = autoScalingClient

.describeAutoScalingInstances(describeAutoScalingInstancesRequest);
            List<AutoScalingInstanceDetails> instances =
response.autoScalingInstances();
```

```
            for (AutoScalingInstanceDetails instance : instances) {
                System.out.println("The instance lifecycle state is: " +
instance.lifecycleState());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void describeAutoScalingGroups(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .maxRecords(10)
                    .build();

            DescribeAutoScalingGroupsResponse response =
autoScalingClient.describeAutoScalingGroups(groupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("*** The service to use for the health checks: "
+ group.healthCheckType());
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String getSpecificAutoScalingGroups(AutoScalingClient
autoScalingClient, String groupName) {
        try {
            String instanceId = "";
            DescribeAutoScalingGroupsRequest scalingGroupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            DescribeAutoScalingGroupsResponse response = autoScalingClient
```

```
                    .describeAutoScalingGroups(scalingGroupsRequest);
            List<AutoScalingGroup> groups = response.autoScalingGroups();
            for (AutoScalingGroup group : groups) {
                System.out.println("The group name is " +
group.autoScalingGroupName());
                System.out.println("The group ARN is " +
group.autoScalingGroupARN());
                List<Instance> instances = group.instances();

                for (Instance instance : instances) {
                    instanceId = instance.instanceId();
                    System.out.println("The instance id is " + instanceId);
                    System.out.println("The lifecycle state is " +
instance.lifecycleState());
                }
            }

            return instanceId;
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void enableMetricsCollection(AutoScalingClient autoScalingClient,
String groupName) {
        try {
            EnableMetricsCollectionRequest collectionRequest =
EnableMetricsCollectionRequest.builder()
                    .autoScalingGroupName(groupName)
                    .metrics("GroupMaxSize")
                    .granularity("1Minute")
                    .build();

            autoScalingClient.enableMetricsCollection(collectionRequest);
            System.out.println("The enable metrics collection operation was
successful");

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static void disableMetricsCollection(AutoScalingClient autoScalingClient,
String groupName) {
       try {
           DisableMetricsCollectionRequest disableMetricsCollectionRequest =
DisableMetricsCollectionRequest.builder()
                   .autoScalingGroupName(groupName)
                   .metrics("GroupMaxSize")
                   .build();


autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest);
           System.out.println("The disable metrics collection operation was
successful");

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void describeAccountLimits(AutoScalingClient autoScalingClient) {
       try {
           DescribeAccountLimitsResponse response =
autoScalingClient.describeAccountLimits();
           System.out.println("The max number of auto scaling groups is " +
response.maxNumberOfAutoScalingGroups());
           System.out.println("The current number of auto scaling groups is " +
response.numberOfAutoScalingGroups());

       } catch (AutoScalingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void updateAutoScalingGroup(AutoScalingClient autoScalingClient,
String groupName,
           String launchTemplateName) {
       try {
           AutoScalingWaiter waiter = autoScalingClient.waiter();
           LaunchTemplateSpecification templateSpecification =
LaunchTemplateSpecification.builder()
                   .launchTemplateName(launchTemplateName)
```

```
                    .build();

            UpdateAutoScalingGroupRequest groupRequest =
UpdateAutoScalingGroupRequest.builder()
                    .maxSize(3)
                    .autoScalingGroupName(groupName)
                    .launchTemplate(templateSpecification)
                    .build();

            autoScalingClient.updateAutoScalingGroup(groupRequest);
            DescribeAutoScalingGroupsRequest groupsRequest =
DescribeAutoScalingGroupsRequest.builder()
                    .autoScalingGroupNames(groupName)
                    .build();

            WaiterResponse<DescribeAutoScalingGroupsResponse> waiterResponse =
waiter
                    .waitUntilGroupInService(groupsRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("You successfully updated the auto scaling group  " +
groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void terminateInstanceInAutoScalingGroup(AutoScalingClient
autoScalingClient, String instanceId) {
        try {
            TerminateInstanceInAutoScalingGroupRequest request =
TerminateInstanceInAutoScalingGroupRequest.builder()
                    .instanceId(instanceId)
                    .shouldDecrementDesiredCapacity(false)
                    .build();

            autoScalingClient.terminateInstanceInAutoScalingGroup(request);
            System.out.println("You have terminated instance " + instanceId);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void deleteAutoScalingGroup(AutoScalingClient autoScalingClient,
 String groupName) {
        try {
            DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
 DeleteAutoScalingGroupRequest.builder()
                    .autoScalingGroupName(groupName)
                    .forceDelete(true)
                    .build();

            autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
            System.out.println("You successfully deleted " + groupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
    public static void listFoundationModels(BedrockClient bedrockClient) {

        try {
            ListFoundationModelsRequest request =
ListFoundationModelsRequest.builder().build();
```

```
            ListFoundationModelsResponse response =
bedrockClient.listFoundationModels(request);

            List<FoundationModelSummary> models = response.modelSummaries();

            for (FoundationModelSummary model : models) {
                System.out.println("Model ID: " + model.modelId());
                System.out.println("Provider: " + model.providerName());
                System.out.println("Name:     " + model.modelName());
                System.out.println();
            }

        } catch (BedrockException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for Java 2.x da API.

Exemplos de Amazon Bedrock Runtime usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Geração de imagens com o Image Generator G1 do Amazon Titan

O exemplo de código a seguir mostra como invocar o modelo Image Generator G1 do Amazon Titan no Amazon Bedrock para geração de imagens.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Image Generator G1 do Amazon Titan de forma assíncrona para gerar imagens.

```
    /**
     * Invokes the Amazon Titan image generation model to create an image using the
     * input
     * provided in the request body.
     *
     * @param prompt The prompt that you want Amazon Titan to use for image
     *               generation.
     * @param seed   The random noise seed for image generation (Range: 0 to
     *               2147483647).
     * @return A Base64-encoded string representing the generated image.
     */
    public static String invokeTitanImage(String prompt, long seed) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Titan Image models refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-
         * image.html
         */
        String titanImageModelId = "amazon.titan-image-generator-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
```

```
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        var textToImageParams = new JSONObject().put("text", prompt);

        var imageGenerationConfig = new JSONObject()
                .put("numberOfImages", 1)
                .put("quality", "standard")
                .put("cfgScale", 8.0)
                .put("height", 512)
                .put("width", 512)
                .put("seed", seed);

        JSONObject payload = new JSONObject()
                .put("taskType", "TEXT_IMAGE")
                .put("textToImageParams", textToImageParams)
                .put("imageGenerationConfig", imageGenerationConfig);

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload.toString()))
                .modelId(titanImageModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " + exception);
                    }
                });

        String base64ImageData = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            base64ImageData = responseBody
                    .getJSONArray("images")
                    .getString(0);

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
```

```
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return base64ImageData;
    }
```

Invoque o modelo Image Generator G1 do Amazon Titan para gerar imagens.

```
        /**
         * Invokes the Amazon Titan image generation model to create an image using
 the
         * input
         * provided in the request body.
         *
         * @param prompt The prompt that you want Amazon Titan to use for image
         *               generation.
         * @param seed   The random noise seed for image generation (Range: 0 to
         *               2147483647).
         * @return A Base64-encoded string representing the generated image.
         */
        public static String invokeTitanImage(String prompt, long seed) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Titan Image models
 refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-titan-
                 * image.html
                 */
                String titanImageModelId = "amazon.titan-image-generator-v1";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                var textToImageParams = new JSONObject().put("text", prompt);
```

```
                var imageGenerationConfig = new JSONObject()
                                .put("numberOfImages", 1)
                                .put("quality", "standard")
                                .put("cfgScale", 8.0)
                                .put("height", 512)
                                .put("width", 512)
                                .put("seed", seed);

                JSONObject payload = new JSONObject()
                                .put("taskType", "TEXT_IMAGE")
                                .put("textToImageParams", textToImageParams)
                                .put("imageGenerationConfig",
imageGenerationConfig);

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload.toString()))
                                .modelId(titanImageModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
JSONObject(response.body().asUtf8String());

                String base64ImageData = responseBody
                                .getJSONArray("images")
                                .getString(0);

                return base64ImageData;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

Geração de imagens com o Stable Diffusion XL da Stability.ai

O exemplo de código a seguir mostra como invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para a geração de imagens.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai de forma assíncrona para gerar imagens.

```
    /**
     * Asynchronously invokes the Stability.ai Stable Diffusion XL model to create
     * an image based on the provided input.
     *
     * @param prompt      The prompt that guides the Stable Diffusion model.
     * @param seed        The random noise seed for image generation (use 0 or omit
     *                    for a random seed).
     * @param stylePreset The style preset to guide the image model towards a
     *                    specific style.
     * @return A Base64-encoded string representing the generated image.
     */
    public static String invokeStableDiffusion(String prompt, long seed, String
 stylePreset) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and available style_presets of Stable Diffusion
         * models refer to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
stability-diffusion.html
         */

        String stableDiffusionModelId = "stability.stable-diffusion-xl";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        JSONArray wrappedPrompt = new JSONArray().put(new JSONObject().put("text",
 prompt));
```

```
        JSONObject payload = new JSONObject()
                .put("text_prompts", wrappedPrompt)
                .put("seed", seed);

        if (stylePreset != null && !stylePreset.isEmpty()) {
            payload.put("style_preset", stylePreset);
        }

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload.toString()))
                .modelId(stableDiffusionModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " + exception);
                    }
                });

        String base64ImageData = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            base64ImageData = responseBody
                    .getJSONArray("artifacts")
                    .getJSONObject(0)
                    .getString("base64");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return base64ImageData;
    }
```

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
        /**
         * Invokes the Stability.ai Stable Diffusion XL model to create an image
 based
         * on the provided input.
         *
         * @param prompt      The prompt that guides the Stable Diffusion model.
         * @param seed        The random noise seed for image generation (use 0 or
 omit
         *                    for a random seed).
         * @param stylePreset The style preset to guide the image model towards a
         *                    specific style.
         * @return A Base64-encoded string representing the generated image.
         */
        public static String invokeStableDiffusion(String prompt, long seed, String
 stylePreset) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and available style_presets of Stable
 Diffusion
                 * models refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-stability-diffusion.html
                 */

                String stableDiffusionModelId = "stability.stable-diffusion-xl";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                JSONArray wrappedPrompt = new JSONArray().put(new
 JSONObject().put("text", prompt));

                JSONObject payload = new JSONObject()
                                .put("text_prompts", wrappedPrompt)
                                .put("seed", seed);

                if (!(stylePreset == null || stylePreset.isEmpty())) {
                        payload.put("style_preset", stylePreset);
```

```
                }

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload.toString()))
                                .modelId(stableDiffusionModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
JSONObject(response.body().asUtf8String());

                String base64ImageData = responseBody
                                .getJSONArray("artifacts")
                                .getJSONObject(0)
                                .getString("base64");

                return base64ImageData;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base Jurassic-2 da AI21 Labs de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the AI21 Labs Jurassic-2 model to run an inference
```

```
     * based on the provided input.
     *
     * @param prompt The prompt that you want Jurassic to complete.
     * @return The inference response generated by the model.
     */
    public static String invokeJurassic2(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Anthropic Claude, refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
         */

        String jurassic2ModelId = "ai21.j2-mid-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", prompt)
                .put("temperature", 0.5)
                .put("maxTokens", 200)
                .toString();

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(jurassic2ModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
 client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " + exception);
                    }
                });

        String generatedText = "";
```

```
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());
            generatedText = responseBody
                    .getJSONArray("completions")
                    .getJSONObject(0)
                    .getJSONObject("data")
                    .getString("text");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
        /**
         * Invokes the AI21 Labs Jurassic-2 model to run an inference based on the
         * provided input.
         *
         * @param prompt The prompt for Jurassic to complete.
         * @return The generated response.
         */
        public static String invokeJurassic2(String prompt) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for AI21 Labs
 Jurassic-2, refer
                 * to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-jurassic2.html
                 */

                String jurassic2ModelId = "ai21.j2-mid-v1";
```

```
                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

.credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", prompt)
                                .put("temperature", 0.5)
                                .put("maxTokens", 200)
                                .toString();

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(jurassic2ModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
JSONObject(response.body().asUtf8String());

                String generatedText = responseBody
                                .getJSONArray("completions")
                                .getJSONObject(0)
                                .getJSONObject("data")
                                .getString("text");

                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base Claude 2 da Anthropic de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the Anthropic Claude 2 model to run an inference based
     * on the provided input.
     *
     * @param prompt The prompt that you want Claude to complete.
     * @return The inference response from the model.
     */
    public static String invokeClaude(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Anthropic Claude, refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html
         */

        String claudeModelId = "anthropic.claude-v2";

        // Claude requires you to enclose the prompt as follows:
        String enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", enclosedPrompt)
                .put("max_tokens_to_sample", 200)
                .put("temperature", 0.5)
                .put("stop_sequences", List.of("\n\nHuman:"))
                .toString();
```

```
        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(claudeModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " + exception);
                    }
                });

        String generatedText = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            generatedText = responseBody.getString("completion");
        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
        /**
         * Invokes the Anthropic Claude 2 model to run an inference based on the
         * provided input.
         *
         * @param prompt The prompt for Claude to complete.
         * @return The generated response.
         */
        public static String invokeClaude(String prompt) {
```

```
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Anthropic Claude,
 refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-claude.html
                 */

                String claudeModelId = "anthropic.claude-v2";

                // Claude requires you to enclose the prompt as follows:
                String enclosedPrompt = "Human: " + prompt + "\n\nAssistant:";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", enclosedPrompt)
                                .put("max_tokens_to_sample", 200)
                                .put("temperature", 0.5)
                                .put("stop_sequences", List.of("\n\nHuman:"))
                                .toString();

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(claudeModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());

                String generatedText = responseBody.getString("completion");

                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

Geração de texto com Claude 2 da Anthropic com fluxo de resposta

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
        /**
         * Invokes the Anthropic Claude 2 model and processes the response stream.
         *
         * @param prompt The prompt for Claude to complete.
         * @param silent Suppress console output of the individual response stream
         *               chunks.
         * @return The generated response.
         */
        public static String invokeClaude(String prompt, boolean silent) {

                BedrockRuntimeAsyncClient client =
BedrockRuntimeAsyncClient.builder()
                                .region(Region.US_EAST_1)

.credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                var finalCompletion = new AtomicReference<>("");

                var payload = new JSONObject()
                                .put("prompt", "Human: " + prompt + " Assistant:")
                                .put("temperature", 0.8)
```

```
                                .put("max_tokens_to_sample", 300)
                                .toString();

                var request = InvokeModelWithResponseStreamRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId("anthropic.claude-v2")
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                var visitor =
InvokeModelWithResponseStreamResponseHandler.Visitor.builder()
                                .onChunk(chunk -> {
                                        var json = new
JSONObject(chunk.bytes().asUtf8String());
                                        var completion =
json.getString("completion");
                                        finalCompletion.set(finalCompletion.get() +
completion);
                                        if (!silent) {
                                                System.out.print(completion);
                                        }
                                })
                                .build();

                var handler = InvokeModelWithResponseStreamResponseHandler.builder()
                                .onEventStream(stream -> stream.subscribe(event ->
event.accept(visitor)))
                                .onComplete(() -> {
                                })
                                .onError(e -> System.out.println("\n\nError: " +
e.getMessage()))
                                .build();

                client.invokeModelWithResponseStream(request, handler).join();

                return finalCompletion.get();
        }
```

- Para obter detalhes da API, consulte InvokeModelWithResponseStreama Referência AWS SDK for Java 2.x da API.

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base do Llama 2 Chat da Meta de forma assíncrona para gerar texto.

```
    /**
     * Asynchronously invokes the Meta Llama 2 Chat model to run an inference based
     * on the provided input.
     *
     * @param prompt The prompt that you want Llama 2 to complete.
     * @return The inference response generated by the model.
     */
    public static String invokeLlama2(String prompt) {
        /*
         * The different model providers have individual request and response
 formats.
         * For the format, ranges, and default values for Meta Llama 2 Chat, refer
 to:
         * https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.
         * html
         */

        String llama2ModelId = "meta.llama2-13b-chat-v1";

        BedrockRuntimeAsyncClient client = BedrockRuntimeAsyncClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        String payload = new JSONObject()
                .put("prompt", prompt)
                .put("max_gen_len", 512)
```

```
                .put("temperature", 0.5)
                .put("top_p", 0.9)
                .toString();

        InvokeModelRequest request = InvokeModelRequest.builder()
                .body(SdkBytes.fromUtf8String(payload))
                .modelId(llama2ModelId)
                .contentType("application/json")
                .accept("application/json")
                .build();

        CompletableFuture<InvokeModelResponse> completableFuture =
client.invokeModel(request)
                .whenComplete((response, exception) -> {
                    if (exception != null) {
                        System.out.println("Model invocation failed: " + exception);
                    }
                });

        String generatedText = "";
        try {
            InvokeModelResponse response = completableFuture.get();
            JSONObject responseBody = new
JSONObject(response.body().asUtf8String());
            generatedText = responseBody.getString("generation");

        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            System.err.println(e.getMessage());
        } catch (ExecutionException e) {
            System.err.println(e.getMessage());
        }

        return generatedText;
    }
```

Invoque o modelo base do Llama 2 Chat da Meta para gerar texto.

```
        /**
         * Invokes the Meta Llama 2 Chat model to run an inference based on the
provided
         * input.
```

```
         *
         * @param prompt The prompt for Llama 2 to complete.
         * @return The generated response.
         */
        public static String invokeLlama2(String prompt) {
                /*
                 * The different model providers have individual request and
 response formats.
                 * For the format, ranges, and default values for Meta Llama 2 Chat,
 refer to:
                 * https://docs.aws.amazon.com/bedrock/latest/userguide/model-
parameters-meta.
                 * html
                 */

                String llama2ModelId = "meta.llama2-13b-chat-v1";

                BedrockRuntimeClient client = BedrockRuntimeClient.builder()
                                .region(Region.US_EAST_1)

 .credentialsProvider(ProfileCredentialsProvider.create())
                                .build();

                String payload = new JSONObject()
                                .put("prompt", prompt)
                                .put("max_gen_len", 512)
                                .put("temperature", 0.5)
                                .put("top_p", 0.9)
                                .toString();

                InvokeModelRequest request = InvokeModelRequest.builder()
                                .body(SdkBytes.fromUtf8String(payload))
                                .modelId(llama2ModelId)
                                .contentType("application/json")
                                .accept("application/json")
                                .build();

                InvokeModelResponse response = client.invokeModel(request);

                JSONObject responseBody = new
 JSONObject(response.body().asUtf8String());

                String generatedText = responseBody.getString("generation");
```

```
                return generatedText;
        }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for Java 2.x da API.

Cenários

Criar uma aplicação de playground para interagir com os modelos de base do Amazon Bedrock

O exemplo de código a seguir mostra como criar playgrounds para interagir com modelos de base do Amazon Bedrock em diferentes modalidades.

SDK para Java 2.x

O modelo de base (FM) Java Playground é um aplicativo de amostra do Spring Boot que mostra como usar o Amazon Bedrock com Java. Este exemplo mostra como os desenvolvedores Java podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de conversa.
- Um playground de imagens.

O exemplo também lista e exibe os modelos de base aos quais tem-se acesso, junto com suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock Runtime

CloudFront exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with CloudFront.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma distribuição

O exemplo de código a seguir mostra como criar uma CloudFront distribuição.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo a seguir usa um bucket do Amazon Simple Storage Service (Amazon S3) como origem de conteúdo.

Depois de criar a distribuição, o código cria um CloudFrontWaiterpara esperar até que a distribuição seja implantada antes de retornar a distribuição

.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.internal.waiters.ResponseOrException;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.CreateDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.Distribution;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.ItemSelection;
```

```
import software.amazon.awssdk.services.cloudfront.model.Method;
import software.amazon.awssdk.services.cloudfront.model.ViewerProtocolPolicy;
import software.amazon.awssdk.services.cloudfront.waiters.CloudFrontWaiter;
import software.amazon.awssdk.services.s3.S3Client;

import java.time.Instant;

public class CreateDistribution {

        private static final Logger logger =
 LoggerFactory.getLogger(CreateDistribution.class);

        public static Distribution createDistribution(CloudFrontClient
 cloudFrontClient, S3Client s3Client,
                        final String bucketName, final String keyGroupId, final
 String originAccessControlId) {

                final String region = s3Client.headBucket(b ->
 b.bucket(bucketName)).sdkHttpResponse().headers()
                                .get("x-amz-bucket-region").get(0);
                final String originDomain = bucketName + ".s3." + region +
 ".amazonaws.com";
                String originId = originDomain; // Use the originDomain value for
 the originId.

                // The service API requires some deprecated methods, such as
                // DefaultCacheBehavior.Builder#minTTL and #forwardedValue.
                CreateDistributionResponse createDistResponse =
 cloudFrontClient.createDistribution(builder -> builder
                                .distributionConfig(b1 -> b1
                                                .origins(b2 -> b2
                                                                .quantity(1)
                                                                .items(b3 -> b3

 .domainName(originDomain)

 .id(originId)

 .s3OriginConfig(builder4 -> builder4

            .originAccessIdentity(

                            ""))
```

```
.originAccessControlId(

          originAccessControlId)))
                                                .defaultCacheBehavior(b2 -> b2

.viewerProtocolPolicy(ViewerProtocolPolicy.ALLOW_ALL)

.targetOriginId(originId)
                                                                .minTTL(200L)
                                                                .forwardedValues(b5
-> b5

.cookies(cp -> cp

          .forward(ItemSelection.NONE))

.queryString(true))
                                                                .trustedKeyGroups(b3
-> b3

.quantity(1)

.items(keyGroupId)

.enabled(true))
                                                                .allowedMethods(b4 -
> b4

.quantity(2)

.items(Method.HEAD, Method.GET)

.cachedMethods(b5 -> b5

          .quantity(2)

          .items(Method.HEAD,

                         Method.GET))))
                                                .cacheBehaviors(b -> b
                                                                .quantity(1)
                                                                .items(b2 -> b2
```

```
.pathPattern("/index.html")

.viewerProtocolPolicy(

           ViewerProtocolPolicy.ALLOW_ALL)

.targetOriginId(originId)

.trustedKeyGroups(b3 -> b3

           .quantity(1)

           .items(keyGroupId)

           .enabled(true))

.minTTL(200L)

.forwardedValues(b4 -> b4

           .cookies(cp -> cp

                           .forward(ItemSelection.NONE))

           .queryString(true))

.allowedMethods(b5 -> b5.quantity(2)

           .items(Method.HEAD,

                           Method.GET)

           .cachedMethods(b6 -> b6

                           .quantity(2)

                           .items(Method.HEAD,

                                           Method.GET)))))
                                               .enabled(true)
                                               .comment("Distribution built with
java")
```

```
 .callerReference(Instant.now().toString())));

                final Distribution distribution = createDistResponse.distribution();
                logger.info("Distribution created. DomainName: [{}]  Id: [{}]",
 distribution.domainName(),
                               distribution.id());
                logger.info("Waiting for distribution to be deployed ...");
                try (CloudFrontWaiter cfWaiter =
 CloudFrontWaiter.builder().client(cloudFrontClient).build()) {
                        ResponseOrException<GetDistributionResponse>
 responseOrException = cfWaiter
                                        .waitUntilDistributionDeployed(builder ->
 builder.id(distribution.id()))
                                        .matched();
                        responseOrException.response()
                                        .orElseThrow(() -> new
 RuntimeException("Distribution not created"));
                        logger.info("Distribution deployed. DomainName: [{}]  Id:
 [{}]", distribution.domainName(),
                                        distribution.id());
                }
                return distribution;
        }
}
```

- Para obter detalhes da API, consulte CreateDistributiona Referência AWS SDK for Java 2.x da API.

Criar uma função

O exemplo de código a seguir mostra como criar uma CloudFront função da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.CloudFrontException;
import software.amazon.awssdk.services.cloudfront.model.CreateFunctionRequest;
import software.amazon.awssdk.services.cloudfront.model.CreateFunctionResponse;
import software.amazon.awssdk.services.cloudfront.model.FunctionConfig;
import software.amazon.awssdk.services.cloudfront.model.FunctionRuntime;

import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateFunction {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName> <filePath>

                Where:
                    functionName - The name of the function to create.\s
                    filePath - The path to a file that contains the application
 logic for the function.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
        String functionName = args[0];
        String filePath = args[1];
        CloudFrontClient cloudFrontClient = CloudFrontClient.builder()
                .region(Region.AWS_GLOBAL)
```

```
                .build();

        String funArn = createNewFunction(cloudFrontClient, functionName, filePath);
        System.out.println("The function ARN is " + funArn);
        cloudFrontClient.close();
    }

    public static String createNewFunction(CloudFrontClient cloudFrontClient, String
 functionName, String filePath) {
        try {
            InputStream fileIs = new FileInputStream(filePath);
            SdkBytes functionCode = SdkBytes.fromInputStream(fileIs);

            FunctionConfig config = FunctionConfig.builder()
                    .comment("Created by using the CloudFront Java API")
                    .runtime(FunctionRuntime.CLOUDFRONT_JS_1_0)
                    .build();

            CreateFunctionRequest functionRequest = CreateFunctionRequest.builder()
                    .name(functionName)
                    .functionCode(functionCode)
                    .functionConfig(config)
                    .build();

            CreateFunctionResponse response =
 cloudFrontClient.createFunction(functionRequest);
            return response.functionSummary().functionMetadata().functionARN();

        } catch (CloudFrontException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Java 2.x da API.

Criar um grupo de chaves

O exemplo de código a seguir mostra como criar um grupo de chaves que você pode usar com URLs e cookies assinados.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Um grupo de chaves exige pelo menos uma chave pública usada para verificar URLs ou cookies assinados.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;

import java.util.UUID;

public class CreateKeyGroup {
    private static final Logger logger =
 LoggerFactory.getLogger(CreateKeyGroup.class);

    public static String createKeyGroup(CloudFrontClient cloudFrontClient, String
 publicKeyId) {
        String keyGroupId = cloudFrontClient.createKeyGroup(b -> b.keyGroupConfig(c
 -> c
                .items(publicKeyId)
                .name("JavaKeyGroup" + UUID.randomUUID())))
                .keyGroup().id();
        logger.info("KeyGroup created with ID: [{}]", keyGroupId);
        return keyGroupId;
    }
}
```

- Para obter detalhes da API, consulte CreateKeyGroupa Referência AWS SDK for Java 2.x da API.

Excluir uma distribuição do

O exemplo de código a seguir mostra como excluir uma CloudFront distribuição.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo de código a seguir atualiza uma distribuição para desabilitada, usa um agente de espera que aguarda a implantação da alteração e, em seguida, exclui a distribuição.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.internal.waiters.ResponseOrException;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.DeleteDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.DistributionConfig;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
import software.amazon.awssdk.services.cloudfront.waiters.CloudFrontWaiter;

public class DeleteDistribution {
        private static final Logger logger =
 LoggerFactory.getLogger(DeleteDistribution.class);

        public static void deleteDistribution(final CloudFrontClient
 cloudFrontClient, final String distributionId) {
                // First, disable the distribution by updating it.
                GetDistributionResponse response =
 cloudFrontClient.getDistribution(b -> b
                                .id(distributionId));
                String etag = response.eTag();
                DistributionConfig distConfig =
 response.distribution().distributionConfig();

                cloudFrontClient.updateDistribution(builder -> builder
                                .id(distributionId)
                                .distributionConfig(builder1 -> builder1

 .cacheBehaviors(distConfig.cacheBehaviors())
```

```
.defaultCacheBehavior(distConfig.defaultCacheBehavior())
                                                .enabled(false)
                                                .origins(distConfig.origins())
                                                .comment(distConfig.comment())

.callerReference(distConfig.callerReference())

.defaultCacheBehavior(distConfig.defaultCacheBehavior())
                                                .priceClass(distConfig.priceClass())
                                                .aliases(distConfig.aliases())
                                                .logging(distConfig.logging())

.defaultRootObject(distConfig.defaultRootObject())

.customErrorResponses(distConfig.customErrorResponses())

.httpVersion(distConfig.httpVersion())

.isIPV6Enabled(distConfig.isIPV6Enabled())

.restrictions(distConfig.restrictions())

.viewerCertificate(distConfig.viewerCertificate())
                                                .webACLId(distConfig.webACLId())

.originGroups(distConfig.originGroups()))
                                .ifMatch(etag));

               logger.info("Distribution [{}] is DISABLED, waiting for deployment
before deleting ...",
                                distributionId);
               GetDistributionResponse distributionResponse;
               try (CloudFrontWaiter cfWaiter =
CloudFrontWaiter.builder().client(cloudFrontClient).build()) {
                       ResponseOrException<GetDistributionResponse>
responseOrException = cfWaiter
                                       .waitUntilDistributionDeployed(builder ->
builder.id(distributionId)).matched();
                       distributionResponse = responseOrException.response()
                                       .orElseThrow(() -> new
RuntimeException("Could not disable distribution"));
               }
```

```
                DeleteDistributionResponse deleteDistributionResponse =
 cloudFrontClient
                                .deleteDistribution(builder -> builder
                                                .id(distributionId)

 .ifMatch(distributionResponse.eTag()));
                if (deleteDistributionResponse.sdkHttpResponse().isSuccessful()) {
                        logger.info("Distribution [{}] DELETED", distributionId);
                }
        }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteDistribution
  - UpdateDistribution

Excluir recursos de assinatura

O exemplo de código a seguir mostra como excluir recursos que são usados para obter acesso a conteúdo restrito em um bucket do Amazon Simple Storage Service (Amazon S3).

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.DeleteKeyGroupResponse;
import
 software.amazon.awssdk.services.cloudfront.model.DeleteOriginAccessControlResponse;
import software.amazon.awssdk.services.cloudfront.model.DeletePublicKeyResponse;
import software.amazon.awssdk.services.cloudfront.model.GetKeyGroupResponse;
```

```
import
 software.amazon.awssdk.services.cloudfront.model.GetOriginAccessControlResponse;
import software.amazon.awssdk.services.cloudfront.model.GetPublicKeyResponse;

public class DeleteSigningResources {
    private static final Logger logger =
 LoggerFactory.getLogger(DeleteSigningResources.class);

    public static void deleteOriginAccessControl(final CloudFrontClient
 cloudFrontClient,
            final String originAccessControlId) {
        GetOriginAccessControlResponse getResponse = cloudFrontClient
                .getOriginAccessControl(b -> b.id(originAccessControlId));
        DeleteOriginAccessControlResponse deleteResponse =
 cloudFrontClient.deleteOriginAccessControl(builder -> builder
                .id(originAccessControlId)
                .ifMatch(getResponse.eTag()));
        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Origin Access Control [{}]",
 originAccessControlId);
        }
    }

    public static void deleteKeyGroup(final CloudFrontClient cloudFrontClient, final
 String keyGroupId) {

        GetKeyGroupResponse getResponse = cloudFrontClient.getKeyGroup(b ->
 b.id(keyGroupId));
        DeleteKeyGroupResponse deleteResponse =
 cloudFrontClient.deleteKeyGroup(builder -> builder
                .id(keyGroupId)
                .ifMatch(getResponse.eTag()));
        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Key Group [{}]", keyGroupId);
        }
    }

    public static void deletePublicKey(final CloudFrontClient cloudFrontClient,
 final String publicKeyId) {
        GetPublicKeyResponse getResponse = cloudFrontClient.getPublicKey(b ->
 b.id(publicKeyId));

        DeletePublicKeyResponse deleteResponse =
 cloudFrontClient.deletePublicKey(builder -> builder
```

```
                .id(publicKeyId)
                .ifMatch(getResponse.eTag()));

        if (deleteResponse.sdkHttpResponse().isSuccessful()) {
            logger.info("Successfully deleted Public Key [{}]", publicKeyId);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteKeyGroup
  - DeleteOriginAccessControl
  - DeletePublicKey

Atualizar uma distribuição

O exemplo de código a seguir mostra como atualizar uma CloudFront distribuição da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionRequest;
import software.amazon.awssdk.services.cloudfront.model.GetDistributionResponse;
import software.amazon.awssdk.services.cloudfront.model.Distribution;
import software.amazon.awssdk.services.cloudfront.model.DistributionConfig;
import software.amazon.awssdk.services.cloudfront.model.UpdateDistributionRequest;
import software.amazon.awssdk.services.cloudfront.model.CloudFrontException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ModifyDistribution {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <id>\s

                Where:
                    id - the id value of the distribution.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String id = args[0];
        CloudFrontClient cloudFrontClient = CloudFrontClient.builder()
                .region(Region.AWS_GLOBAL)
                .build();

        modDistribution(cloudFrontClient, id);
        cloudFrontClient.close();
    }

    public static void modDistribution(CloudFrontClient cloudFrontClient, String
 idVal) {
        try {
            // Get the Distribution to modify.
            GetDistributionRequest disRequest = GetDistributionRequest.builder()
                    .id(idVal)
                    .build();

            GetDistributionResponse response =
 cloudFrontClient.getDistribution(disRequest);
            Distribution disObject = response.distribution();
            DistributionConfig config = disObject.distributionConfig();
```

```
            // Create a new DistributionConfig object and add new values to comment
 and
            // aliases
            DistributionConfig config1 = DistributionConfig.builder()
                    .aliases(config.aliases()) // You can pass in new values here
                    .comment("New Comment")
                    .cacheBehaviors(config.cacheBehaviors())
                    .priceClass(config.priceClass())
                    .defaultCacheBehavior(config.defaultCacheBehavior())
                    .enabled(config.enabled())
                    .callerReference(config.callerReference())
                    .logging(config.logging())
                    .originGroups(config.originGroups())
                    .origins(config.origins())
                    .restrictions(config.restrictions())
                    .defaultRootObject(config.defaultRootObject())
                    .webACLId(config.webACLId())
                    .httpVersion(config.httpVersion())
                    .viewerCertificate(config.viewerCertificate())
                    .customErrorResponses(config.customErrorResponses())
                    .build();

            UpdateDistributionRequest updateDistributionRequest =
 UpdateDistributionRequest.builder()
                    .distributionConfig(config1)
                    .id(disObject.id())
                    .ifMatch(response.eTag())
                    .build();

            cloudFrontClient.updateDistribution(updateDistributionRequest);

        } catch (CloudFrontException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateDistributiona Referência AWS SDK for Java 2.x da API.

Carregar uma chave pública

O exemplo de código a seguir mostra como fazer o upload de uma chave pública.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O exemplo de código a seguir lê uma chave pública e a carrega na Amazon CloudFront.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontClient;
import software.amazon.awssdk.services.cloudfront.model.CreatePublicKeyResponse;
import software.amazon.awssdk.utils.IoUtils;

import java.io.IOException;
import java.io.InputStream;
import java.util.UUID;

public class CreatePublicKey {
    private static final Logger logger =
 LoggerFactory.getLogger(CreatePublicKey.class);

    public static String createPublicKey(CloudFrontClient cloudFrontClient, String
 publicKeyFileName) {
        try (InputStream is =
 CreatePublicKey.class.getClassLoader().getResourceAsStream(publicKeyFileName)) {
            String publicKeyString = IoUtils.toUtf8String(is);
            CreatePublicKeyResponse createPublicKeyResponse = cloudFrontClient
                    .createPublicKey(b -> b.publicKeyConfig(c -> c
                            .name("JavaCreatedPublicKey" + UUID.randomUUID())
                            .encodedKey(publicKeyString)
                            .callerReference(UUID.randomUUID().toString())));
            String createdPublicKeyId = createPublicKeyResponse.publicKey().id();
            logger.info("Public key created with id: [{}]", createdPublicKeyId);
            return createdPublicKeyId;

        } catch (IOException e) {
```

```
            throw new RuntimeException(e);
        }
    }
}
```

- Para obter detalhes da API, consulte CreatePublicKeya Referência AWS SDK for Java 2.x da API.

Cenários

Assinar URLs e cookies

O exemplo de código a seguir mostra como criar URLs e cookies assinados que permitem acesso a recursos restritos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use a CannedSignerRequestclasse para assinar URLs ou cookies com uma política predefinida.

```
import software.amazon.awssdk.services.cloudfront.model.CannedSignerRequest;

import java.net.URL;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.temporal.ChronoUnit;

public class CreateCannedPolicyRequest {

    public static CannedSignerRequest createRequestForCannedPolicy(String
 distributionDomainName,
            String fileNameToUpload,
            String privateKeyFullPath, String publicKeyId) throws Exception {
        String protocol = "https";
```

```
        String resourcePath = "/" + fileNameToUpload;

        String cloudFrontUrl = new URL(protocol, distributionDomainName,
 resourcePath).toString();
        Instant expirationDate = Instant.now().plus(7, ChronoUnit.DAYS);
        Path path = Paths.get(privateKeyFullPath);

        return CannedSignerRequest.builder()
                .resourceUrl(cloudFrontUrl)
                .privateKey(path)
                .keyPairId(publicKeyId)
                .expirationDate(expirationDate)
                .build();
    }
}
```

Use a CustomSignerRequestclasse para assinar URLs ou cookies com uma política personalizada. O `activeDate` e `ipRange` são métodos opcionais.

```
import software.amazon.awssdk.services.cloudfront.model.CustomSignerRequest;

import java.net.URL;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.temporal.ChronoUnit;

public class CreateCustomPolicyRequest {

    public static CustomSignerRequest createRequestForCustomPolicy(String
 distributionDomainName,
            String fileNameToUpload,
            String privateKeyFullPath, String publicKeyId) throws Exception {
        String protocol = "https";
        String resourcePath = "/" + fileNameToUpload;

        String cloudFrontUrl = new URL(protocol, distributionDomainName,
 resourcePath).toString();
        Instant expireDate = Instant.now().plus(7, ChronoUnit.DAYS);
        // URL will be accessible tomorrow using the signed URL.
        Instant activeDate = Instant.now().plus(1, ChronoUnit.DAYS);
        Path path = Paths.get(privateKeyFullPath);
```

```
        return CustomSignerRequest.builder()
                .resourceUrl(cloudFrontUrl)
                .privateKey(path)
                .keyPairId(publicKeyId)
                .expirationDate(expireDate)
                .activeDate(activeDate) // Optional.
                // .ipRange("192.168.0.1/24") // Optional.
                .build();
    }
}
```

O exemplo a seguir demonstra o uso da CloudFrontUtilitiesclasse para produzir cookies e URLs assinados. Veja este exemplo de código em GitHub.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.cloudfront.CloudFrontUtilities;
import software.amazon.awssdk.services.cloudfront.cookie.CookiesForCannedPolicy;
import software.amazon.awssdk.services.cloudfront.cookie.CookiesForCustomPolicy;
import software.amazon.awssdk.services.cloudfront.model.CannedSignerRequest;
import software.amazon.awssdk.services.cloudfront.model.CustomSignerRequest;
import software.amazon.awssdk.services.cloudfront.url.SignedUrl;

public class SigningUtilities {
    private static final Logger logger =
 LoggerFactory.getLogger(SigningUtilities.class);
    private static final CloudFrontUtilities cloudFrontUtilities =
 CloudFrontUtilities.create();

    public static SignedUrl signUrlForCannedPolicy(CannedSignerRequest
 cannedSignerRequest) {
        SignedUrl signedUrl =
 cloudFrontUtilities.getSignedUrlWithCannedPolicy(cannedSignerRequest);
        logger.info("Signed URL: [{}]", signedUrl.url());
        return signedUrl;
    }

    public static SignedUrl signUrlForCustomPolicy(CustomSignerRequest
 customSignerRequest) {
        SignedUrl signedUrl =
 cloudFrontUtilities.getSignedUrlWithCustomPolicy(customSignerRequest);
```

```
        logger.info("Signed URL: [{}]", signedUrl.url());
        return signedUrl;
    }

    public static CookiesForCannedPolicy
 getCookiesForCannedPolicy(CannedSignerRequest cannedSignerRequest) {
        CookiesForCannedPolicy cookiesForCannedPolicy = cloudFrontUtilities
                .getCookiesForCannedPolicy(cannedSignerRequest);
        logger.info("Cookie EXPIRES header [{}]",
 cookiesForCannedPolicy.expiresHeaderValue());
        logger.info("Cookie KEYPAIR header [{}]",
 cookiesForCannedPolicy.keyPairIdHeaderValue());
        logger.info("Cookie SIGNATURE header [{}]",
 cookiesForCannedPolicy.signatureHeaderValue());
        return cookiesForCannedPolicy;
    }

    public static CookiesForCustomPolicy
 getCookiesForCustomPolicy(CustomSignerRequest customSignerRequest) {
        CookiesForCustomPolicy cookiesForCustomPolicy = cloudFrontUtilities
                .getCookiesForCustomPolicy(customSignerRequest);
        logger.info("Cookie POLICY header [{}]",
 cookiesForCustomPolicy.policyHeaderValue());
        logger.info("Cookie KEYPAIR header [{}]",
 cookiesForCustomPolicy.keyPairIdHeaderValue());
        logger.info("Cookie SIGNATURE header [{}]",
 cookiesForCustomPolicy.signatureHeaderValue());
        return cookiesForCustomPolicy;
    }
}
```

- Para obter detalhes da API, consulte CloudFrontUtilitiesa Referência AWS SDK for Java 2.x da API.

CloudWatch exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá CloudWatch

O exemplo de código a seguir mostra como começar a usar o CloudWatch.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.paginators.ListMetricsIterable;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloService {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                  <namespace>\s

                Where:
                  namespace - The namespace to filter against (for example, AWS/
EC2).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String namespace = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        listMets(cw, namespace);
        cw.close();
    }

    public static void listMets(CloudWatchClient cw, String namespace) {
        try {
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();

            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> System.out.println(" Retrieved metric is: "
 + metrics.metricName()));

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um painel

O exemplo de código a seguir mostra como criar um CloudWatch painel da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDashboardWithMetrics(CloudWatchClient cw, String
dashboardName, String fileName) {
       try {
           PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                   .dashboardName(dashboardName)
                   .dashboardBody(readFileAsString(fileName))
                   .build();

           PutDashboardResponse response = cw.putDashboard(dashboardRequest);
           System.out.println(dashboardName + " was successfully created.");
           List<DashboardValidationMessage> messages =
response.dashboardValidationMessages();
           if (messages.isEmpty()) {
               System.out.println("There are no messages in the new Dashboard");
           } else {
               for (DashboardValidationMessage message : messages) {
                   System.out.println("Message is: " + message.message());
               }
           }

       } catch (CloudWatchException | IOException e) {
           System.err.println(e.getMessage());
           System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte PutDashboarda Referência AWS SDK for Java 2.x da API.

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            String alarmName = rootNode.findValue("exampleAlarmName").asText();
            String emailTopic = rootNode.findValue("emailTopic").asText();
            String accountId = rootNode.findValue("accountId").asText();
            String region = rootNode.findValue("region").asText();

            // Create a List for alarm actions.
            List<String> alarmActions = new ArrayList<>();
            alarmActions.add("arn:aws:sns:" + region + ":" + accountId + ":" +
emailTopic);
            PutMetricAlarmRequest alarmRequest = PutMetricAlarmRequest.builder()
                    .alarmActions(alarmActions)
```

```
                    .alarmDescription("Example metric alarm")
                    .alarmName(alarmName)

.comparisonOperator(ComparisonOperator.GREATER_THAN_OR_EQUAL_TO_THRESHOLD)
                    .threshold(100.00)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .evaluationPeriods(1)
                    .period(10)
                    .statistic("Maximum")
                    .datapointsToAlarm(1)
                    .treatMissingData("ignore")
                    .build();

            cw.putMetricAlarm(alarmRequest);
            System.out.println(alarmName + " was successfully created!");
            return alarmName;

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for Java 2.x da API.

Criar um detector de anomalias

O exemplo de código a seguir mostra como criar um detector de CloudWatch anomalias da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void addAnomalyDetector(CloudWatchClient cw, String fileName) {
```

```
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            PutAnomalyDetectorRequest anomalyDetectorRequest =
PutAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.putAnomalyDetector(anomalyDetectorRequest);
            System.out.println("Added anomaly detector for metric " +
customMetricName + ".");

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutAnomalyDetectora Referência AWS SDK for Java 2.x da API.

Excluir alarmes

O exemplo de código a seguir mostra como excluir CloudWatch alarmes da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.DeleteAlarmsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteAlarm {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <alarmName>

                Where:
                  alarmName - An alarm name to delete (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarmName = args[0];
        Region region = Region.US_EAST_2;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
```

```
                .build();

        deleteCWAlarm(cw, alarmName);
        cw.close();
    }

    public static void deleteCWAlarm(CloudWatchClient cw, String alarmName) {
        try {
            DeleteAlarmsRequest request = DeleteAlarmsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.deleteAlarms(request);
            System.out.printf("Successfully deleted alarm %s", alarmName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAlarmsa Referência AWS SDK for Java 2.x da API.

Excluir um detector de anomalias

O exemplo de código a seguir mostra como excluir um detector de CloudWatch anomalias da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteAnomalyDetector(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
```

```
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            DeleteAnomalyDetectorRequest request =
DeleteAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.deleteAnomalyDetector(request);
            System.out.println("Successfully deleted the Anomaly Detector.");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
```

- Para obter detalhes da API, consulte DeleteAnomalyDetectora Referência AWS SDK for Java 2.x da API.

Excluir painéis

O exemplo de código a seguir mostra como excluir CloudWatch painéis da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteDashboard(CloudWatchClient cw, String dashboardName) {
        try {
            DeleteDashboardsRequest dashboardsRequest =
DeleteDashboardsRequest.builder()
                    .dashboardNames(dashboardName)
                    .build();
            cw.deleteDashboards(dashboardsRequest);
            System.out.println(dashboardName + " was successfully deleted.");

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDashboardsa Referência AWS SDK for Java 2.x da API.

Descrever o histórico do alarme

O exemplo de código a seguir mostra como descrever um histórico de CloudWatch alarmes da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAlarmHistory(CloudWatchClient cw, String fileName, String
date) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String alarmName = rootNode.findValue("exampleAlarmName").asText();

           Instant start = Instant.parse(date);
           Instant endDate = Instant.now();
           DescribeAlarmHistoryRequest historyRequest =
DescribeAlarmHistoryRequest.builder()
                   .startDate(start)
                   .endDate(endDate)
                   .alarmName(alarmName)
                   .historyItemType(HistoryItemType.ACTION)
                   .build();

           DescribeAlarmHistoryResponse response =
cw.describeAlarmHistory(historyRequest);
           List<AlarmHistoryItem> historyItems = response.alarmHistoryItems();
           if (historyItems.isEmpty()) {
               System.out.println("No alarm history data found for " + alarmName +
".");
           } else {
               for (AlarmHistoryItem item : historyItems) {
                   System.out.println("History summary: " + item.historySummary());
                   System.out.println("Time stamp: " + item.timestamp());
               }
           }

       } catch (CloudWatchException | IOException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeAlarmHistorya Referência AWS SDK for Java 2.x da API.

Descrever alarmes

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeAlarms(CloudWatchClient cw) {
        try {
            List<AlarmType> typeList = new ArrayList<>();
            typeList.add(AlarmType.METRIC_ALARM);

            DescribeAlarmsRequest alarmsRequest = DescribeAlarmsRequest.builder()
                    .alarmTypes(typeList)
                    .maxRecords(10)
                    .build();

            DescribeAlarmsResponse response = cw.describeAlarms(alarmsRequest);
            List<MetricAlarm> alarmList = response.metricAlarms();
            for (MetricAlarm alarm : alarmList) {
                System.out.println("Alarm name: " + alarm.alarmName());
                System.out.println("Alarm description: " +
alarm.alarmDescription());
            }
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for Java 2.x da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkForMetricAlarm(CloudWatchClient cw, String fileName) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();
           boolean hasAlarm = false;
           int retries = 10;

           DescribeAlarmsForMetricRequest metricRequest =
DescribeAlarmsForMetricRequest.builder()
                   .metricName(customMetricName)
                   .namespace(customMetricNamespace)
                   .build();

           while (!hasAlarm && retries > 0) {
               DescribeAlarmsForMetricResponse response =
cw.describeAlarmsForMetric(metricRequest);
               hasAlarm = response.hasMetricAlarms();
               retries--;
               Thread.sleep(20000);
               System.out.println(".");
           }
           if (!hasAlarm)
```

```
                System.out.println("No Alarm state found for " + customMetricName +
" after 10 retries.");
            else
                System.out.println("Alarm state found for " + customMetricName +
".");

        } catch (CloudWatchException | IOException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for Java 2.x da API.

Descrever detectores de anomalias

O exemplo de código a seguir mostra como descrever os detectores de CloudWatch anomalias da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeAnomalyDetectors(CloudWatchClient cw, String
fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
```

```
            DescribeAnomalyDetectorsRequest detectorsRequest =
DescribeAnomalyDetectorsRequest.builder()
                    .maxResults(10)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            DescribeAnomalyDetectorsResponse response =
cw.describeAnomalyDetectors(detectorsRequest);
            List<AnomalyDetector> anomalyDetectorList = response.anomalyDetectors();
            for (AnomalyDetector detector : anomalyDetectorList) {
                System.out.println("Metric name: " +
detector.singleMetricAnomalyDetector().metricName());
                System.out.println("State: " + detector.stateValue());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAnomalyDetectorsa Referência AWS SDK for Java 2.x da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.DisableAlarmActionsRequest;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DisableAlarmActions {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <alarmName>

                Where:
                  alarmName - An alarm name to disable (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarmName = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        disableActions(cw, alarmName);
        cw.close();
    }

    public static void disableActions(CloudWatchClient cw, String alarmName) {
        try {
            DisableAlarmActionsRequest request =
 DisableAlarmActionsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.disableAlarmActions(request);
```

```
            System.out.printf("Successfully disabled actions on alarm %s",
 alarmName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for Java 2.x da API.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.EnableAlarmActionsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class EnableAlarmActions {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                  <alarmName>

                Where:
                  alarmName - An alarm name to enable (for example, MyAlarm).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alarm = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        enableActions(cw, alarm);
        cw.close();
    }

    public static void enableActions(CloudWatchClient cw, String alarm) {
        try {
            EnableAlarmActionsRequest request = EnableAlarmActionsRequest.builder()
                    .alarmNames(alarm)
                    .build();

            cw.enableAlarmActions(request);
            System.out.printf("Successfully enabled actions on alarm %s", alarm);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte EnableAlarmActionsa Referência AWS SDK for Java 2.x da API.

Obter uma imagem de dados de métricas

O exemplo de código a seguir mostra como obter uma imagem de dados CloudWatch métricos da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getAndOpenMetricImage(CloudWatchClient cw, String fileName) {
        System.out.println("Getting Image data for custom metric.");
        try {
            String myJSON = "{\n" +
                    "  \"title\": \"Example Metric Graph\",\n" +
                    "  \"view\": \"timeSeries\",\n" +
                    "  \"stacked \": false,\n" +
                    "  \"period\": 10,\n" +
                    "  \"width\": 1400,\n" +
                    "  \"height\": 600,\n" +
                    "  \"metrics\": [\n" +
                    "    [\n" +
                    "      \"AWS/Billing\",\n" +
                    "      \"EstimatedCharges\",\n" +
                    "      \"Currency\",\n" +
                    "      \"USD\"\n" +
                    "    ]\n" +
                    "  ]\n" +
                    "}";

            GetMetricWidgetImageRequest imageRequest =
GetMetricWidgetImageRequest.builder()
                    .metricWidget(myJSON)
                    .build();

            GetMetricWidgetImageResponse response =
cw.getMetricWidgetImage(imageRequest);
            SdkBytes sdkBytes = response.metricWidgetImage();
            byte[] bytes = sdkBytes.asByteArray();
```

```
            File outputFile = new File(fileName);
            try (FileOutputStream outputStream = new FileOutputStream(outputFile)) {
                outputStream.write(bytes);
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetMetricWidgetImagea Referência AWS SDK for Java 2.x da API.

Obter dados de métricas

O exemplo de código a seguir mostra como obter dados CloudWatch métricos da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getCustomMetricData(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set the date.
            Instant nowDate = Instant.now();

            long hours = 1;
```

```
            long minutes = 30;
            Instant date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(minutes,
                    ChronoUnit.MINUTES);

            Metric met = Metric.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            MetricStat metStat = MetricStat.builder()
                    .stat("Maximum")
                    .period(1)
                    .metric(met)
                    .build();

            MetricDataQuery dataQUery = MetricDataQuery.builder()
                    .metricStat(metStat)
                    .id("foo2")
                    .returnData(true)
                    .build();

            List<MetricDataQuery> dq = new ArrayList<>();
            dq.add(dataQUery);

            GetMetricDataRequest getMetReq = GetMetricDataRequest.builder()
                    .maxDatapoints(10)
                    .scanBy(ScanBy.TIMESTAMP_DESCENDING)
                    .startTime(nowDate)
                    .endTime(date2)
                    .metricDataQueries(dq)
                    .build();

            GetMetricDataResponse response = cw.getMetricData(getMetReq);
            List<MetricDataResult> data = response.metricDataResults();
            for (MetricDataResult item : data) {
                System.out.println("The label is " + item.label());
                System.out.println("The status code is " +
item.statusCode().toString());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }
```

- Para obter detalhes da API, consulte GetMetricDataa Referência AWS SDK for Java 2.x da API.

Obter estatísticas de métricas

O exemplo de código a seguir mostra como obter estatísticas CloudWatch métricas da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAndDisplayMetricStatistics(CloudWatchClient cw, String
nameSpace, String metVal,
           String metricOption, String date, Dimension myDimension) {
       try {
           Instant start = Instant.parse(date);
           Instant endDate = Instant.now();

           GetMetricStatisticsRequest statisticsRequest =
GetMetricStatisticsRequest.builder()
                   .endTime(endDate)
                   .startTime(start)
                   .dimensions(myDimension)
                   .metricName(metVal)
                   .namespace(nameSpace)
                   .period(86400)
                   .statistics(Statistic.fromValue(metricOption))
                   .build();

           GetMetricStatisticsResponse response =
cw.getMetricStatistics(statisticsRequest);
           List<Datapoint> data = response.datapoints();
           if (!data.isEmpty()) {
               for (Datapoint datapoint : data) {
                   System.out
```

```
                            .println("Timestamp: " + datapoint.timestamp() + "
Maximum value: " + datapoint.maximum());
                }
            } else {
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetMetricStatisticsa Referência AWS SDK for Java 2.x da API.

Listar painéis

O exemplo de código a seguir mostra como listar os CloudWatch painéis da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listDashboards(CloudWatchClient cw) {
        try {
            ListDashboardsIterable listRes = cw.listDashboardsPaginator();
            listRes.stream()
                    .flatMap(r -> r.dashboardEntries().stream())
                    .forEach(entry -> {
                        System.out.println("Dashboard name is: " +
entry.dashboardName());
                        System.out.println("Dashboard ARN is: " +
entry.dashboardArn());
                    });

        } catch (CloudWatchException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListDashboardsa Referência AWS SDK for Java 2.x da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Metric;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListMetrics {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                  <namespace>\s

                Where:
                  namespace - The namespace to filter against (for example, AWS/
EC2).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String namespace = args[0];
        Region region = Region.US_EAST_1;
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .build();

        listMets(cw, namespace);
        cw.close();
    }

    public static void listMets(CloudWatchClient cw, String namespace) {
        boolean done = false;
        String nextToken = null;

        try {
            while (!done) {

                ListMetricsResponse response;
                if (nextToken == null) {
                    ListMetricsRequest request = ListMetricsRequest.builder()
                            .namespace(namespace)
                            .build();

                    response = cw.listMetrics(request);
                } else {
                    ListMetricsRequest request = ListMetricsRequest.builder()
                            .namespace(namespace)
                            .nextToken(nextToken)
                            .build();

                    response = cw.listMetrics(request);
```

```
                }

                for (Metric metric : response.metrics()) {
                    System.out.printf("Retrieved metric %s", metric.metricName());
                    System.out.println();
                }

                if (response.nextToken() == null) {
                    done = true;
                } else {
                    nextToken = response.nextToken();
                }
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Java 2.x da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void addMetricDataForAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
```

```
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set an Instant object.
            String time =
ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
            Instant instant = Instant.parse(time);

            MetricDatum datum = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1001.00)
                    .timestamp(instant)
                    .build();

            MetricDatum datum2 = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1002.00)
                    .timestamp(instant)
                    .build();

            List<MetricDatum> metricDataList = new ArrayList<>();
            metricDataList.add(datum);
            metricDataList.add(datum2);

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace(customMetricNamespace)
                    .metricData(metricDataList)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric " +
customMetricName);

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for Java 2.x da API.

Cenários

Começar a usar métricas, painéis e alarmes

O código de exemplo a seguir mostra como:

- Listar CloudWatch namespaces e métricas.
- Obtenha estatísticas para uma métrica e para faturamento estimado.
- Crie e atualize um painel.
- Crie e adicione dados a uma métrica.
- Crie e acione um alarme e, em seguida, visualize o histórico de alarmes.
- Crie um detector de anomalias.
- Obtenha uma imagem de métrica e, em seguida, limpe os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import com.fasterxml.jackson.core.JsonFactory;
import com.fasterxml.jackson.core.JsonParser;
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatch.CloudWatchClient;
import software.amazon.awssdk.services.cloudwatch.model.AlarmHistoryItem;
import software.amazon.awssdk.services.cloudwatch.model.AlarmType;
import software.amazon.awssdk.services.cloudwatch.model.AnomalyDetector;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatch.model.ComparisonOperator;
```

```
import software.amazon.awssdk.services.cloudwatch.model.DashboardValidationMessage;
import software.amazon.awssdk.services.cloudwatch.model.Datapoint;
import software.amazon.awssdk.services.cloudwatch.model.DeleteAlarmsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DeleteAnomalyDetectorRequest;
import software.amazon.awssdk.services.cloudwatch.model.DeleteDashboardsRequest;
import software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmHistoryRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmHistoryResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsForMetricRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsForMetricResponse;
import software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsRequest;
import software.amazon.awssdk.services.cloudwatch.model.DescribeAlarmsResponse;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAnomalyDetectorsRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.DescribeAnomalyDetectorsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Dimension;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricDataRequest;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricDataResponse;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricStatisticsRequest;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricStatisticsResponse;
import software.amazon.awssdk.services.cloudwatch.model.GetMetricWidgetImageRequest;
import
 software.amazon.awssdk.services.cloudwatch.model.GetMetricWidgetImageResponse;
import software.amazon.awssdk.services.cloudwatch.model.HistoryItemType;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsRequest;
import software.amazon.awssdk.services.cloudwatch.model.ListMetricsResponse;
import software.amazon.awssdk.services.cloudwatch.model.Metric;
import software.amazon.awssdk.services.cloudwatch.model.MetricAlarm;
import software.amazon.awssdk.services.cloudwatch.model.MetricDataQuery;
import software.amazon.awssdk.services.cloudwatch.model.MetricDataResult;
import software.amazon.awssdk.services.cloudwatch.model.MetricDatum;
import software.amazon.awssdk.services.cloudwatch.model.MetricStat;
import software.amazon.awssdk.services.cloudwatch.model.PutAnomalyDetectorRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutDashboardRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutDashboardResponse;
import software.amazon.awssdk.services.cloudwatch.model.PutMetricAlarmRequest;
import software.amazon.awssdk.services.cloudwatch.model.PutMetricDataRequest;
import software.amazon.awssdk.services.cloudwatch.model.ScanBy;
import software.amazon.awssdk.services.cloudwatch.model.SingleMetricAnomalyDetector;
import software.amazon.awssdk.services.cloudwatch.model.StandardUnit;
```

```
import software.amazon.awssdk.services.cloudwatch.model.Statistic;
import software.amazon.awssdk.services.cloudwatch.paginators.ListDashboardsIterable;
import software.amazon.awssdk.services.cloudwatch.paginators.ListMetricsIterable;
import java.io.BufferedReader;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.InputStreamReader;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.time.Instant;
import java.time.ZoneOffset;
import java.time.ZonedDateTime;
import java.time.format.DateTimeFormatter;
import java.time.temporal.ChronoUnit;
import java.util.ArrayList;
import java.util.List;
import java.util.Scanner;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To enable billing metrics and statistics for this example, make sure billing
 * alerts are enabled for your account:
 * https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics
 *
 * This Java code example performs the following tasks:
 *
 * 1. List available namespaces from Amazon CloudWatch.
 * 2. List available metrics within the selected Namespace.
 * 3. Get statistics for the selected metric over the last day.
 * 4. Get CloudWatch estimated billing for the last week.
 * 5. Create a new CloudWatch dashboard with metrics.
 * 6. List dashboards using a paginator.
 * 7. Create a new custom metric by adding data for it.
 * 8. Add the custom metric to the dashboard.
 * 9. Create an alarm for the custom metric.
 * 10. Describe current alarms.
```

```
 * 11. Get current data for the new custom metric.
 * 12. Push data into the custom metric to trigger the alarm.
 * 13. Check the alarm state using the action DescribeAlarmsForMetric.
 * 14. Get alarm history for the new alarm.
 * 15. Add an anomaly detector for the custom metric.
 * 16. Describe current anomaly detectors.
 * 17. Get a metric image for the custom metric.
 * 18. Clean up the Amazon CloudWatch resources.
 */
public class CloudWatchScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                  <myDate> <costDateWeek> <dashboardName> <dashboardJson>
 <dashboardAdd> <settings> <metricImage> \s

                Where:
                  myDate - The start date to use to get metric statistics. (For
 example, 2023-01-11T18:35:24.00Z.)\s
                  costDateWeek - The start date to use to get AWS/Billinget
 statistics. (For example, 2023-01-11T18:35:24.00Z.)\s
                  dashboardName - The name of the dashboard to create.\s
                  dashboardJson - The location of a JSON file to use to create a
 dashboard. (See Readme file.)\s
                  dashboardAdd - The location of a JSON file to use to update a
 dashboard. (See Readme file.)\s
                  settings - The location of a JSON file from which various values
 are read. (See Readme file.)\s
                  metricImage - The location of a BMP file that is used to create a
 graph.\s
                """;

        if (args.length != 7) {
            System.out.println(usage);
            System.exit(1);
        }

        Region region = Region.US_EAST_1;
        String myDate = args[0];
        String costDateWeek = args[1];
        String dashboardName = args[2];
```

```
        String dashboardJson = args[3];
        String dashboardAdd = args[4];
        String settings = args[5];
        String metricImage = args[6];

        Double dataPoint = Double.parseDouble("10.0");
        Scanner sc = new Scanner(System.in);
        CloudWatchClient cw = CloudWatchClient.builder()
                .region(region)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon CloudWatch example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "1. List at least five available unique namespaces from Amazon
CloudWatch. Select one from the list.");
        ArrayList<String> list = listNameSpaces(cw);
        for (int z = 0; z < 5; z++) {
            int index = z + 1;
            System.out.println("    " + index + ". " + list.get(z));
        }

        String selectedNamespace = "";
        String selectedMetrics = "";
        int num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            selectedNamespace = list.get(num - 1);
        } else {
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + selectedNamespace);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. List available metrics within the selected namespace
and select one from the list.");
        ArrayList<String> metList = listMets(cw, selectedNamespace);
        for (int z = 0; z < 5; z++) {
            int index = z + 1;
```

```
            System.out.println("    " + index + ". " + metList.get(z));
        }
        num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            selectedMetrics = metList.get(num - 1);
        } else {
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + selectedMetrics);
        Dimension myDimension = getSpecificMet(cw, selectedNamespace);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get statistics for the selected metric over the last
day.");
        String metricOption = "";
        ArrayList<String> statTypes = new ArrayList<>();
        statTypes.add("SampleCount");
        statTypes.add("Average");
        statTypes.add("Sum");
        statTypes.add("Minimum");
        statTypes.add("Maximum");

        for (int t = 0; t < 5; t++) {
            System.out.println("    " + (t + 1) + ". " + statTypes.get(t));
        }
        System.out.println("Select a metric statistic by entering a number from the
preceding list:");
        num = Integer.parseInt(sc.nextLine());
        if (1 <= num && num <= 5) {
            metricOption = statTypes.get(num - 1);
        } else {
            System.out.println("You did not select a valid option.");
            System.exit(1);
        }
        System.out.println("You selected " + metricOption);
        getAndDisplayMetricStatistics(cw, selectedNamespace, selectedMetrics,
metricOption, myDate, myDimension);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get CloudWatch estimated billing for the last
week.");
```

```
        getMetricStatistics(cw, costDateWeek);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create a new CloudWatch dashboard with metrics.");
        createDashboardWithMetrics(cw, dashboardName, dashboardJson);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. List dashboards using a paginator.");
        listDashboards(cw);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Create a new custom metric by adding data to it.");
        createNewCustomMetric(cw, dataPoint);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Add an additional metric to the dashboard.");
        addMetricToDashboard(cw, dashboardAdd, dashboardName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Create an alarm for the custom metric.");
        String alarmName = createAlarm(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Describe ten current alarms.");
        describeAlarms(cw);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Get current data for new custom metric.");
        getCustomMetricData(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Push data into the custom metric to trigger the
alarm.");
        addMetricDataForAlarm(cw, settings);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("13. Check the alarm state using the action
DescribeAlarmsForMetric.");
        checkForMetricAlarm(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Get alarm history for the new alarm.");
        getAlarmHistory(cw, settings, myDate);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Add an anomaly detector for the custom metric.");
        addAnomalyDetector(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Describe current anomaly detectors.");
        describeAnomalyDetectors(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Get a metric image for the custom metric.");
        getAndOpenMetricImage(cw, metricImage);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Clean up the Amazon CloudWatch resources.");
        deleteDashboard(cw, dashboardName);
        deleteCWAlarm(cw, alarmName);
        deleteAnomalyDetector(cw, settings);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Amazon CloudWatch example scenario is complete.");
        System.out.println(DASHES);
        cw.close();
    }

    public static void deleteAnomalyDetector(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
```

```
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .stat("Maximum")
                    .build();

            DeleteAnomalyDetectorRequest request =
DeleteAnomalyDetectorRequest.builder()
                    .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                    .build();

            cw.deleteAnomalyDetector(request);
            System.out.println("Successfully deleted the Anomaly Detector.");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException e) {
            e.printStackTrace();
        }
    }

    public static void deleteCWAlarm(CloudWatchClient cw, String alarmName) {
        try {
            DeleteAlarmsRequest request = DeleteAlarmsRequest.builder()
                    .alarmNames(alarmName)
                    .build();

            cw.deleteAlarms(request);
            System.out.println("Successfully deleted alarm " + alarmName);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static void deleteDashboard(CloudWatchClient cw, String dashboardName) {
        try {
            DeleteDashboardsRequest dashboardsRequest =
DeleteDashboardsRequest.builder()
                    .dashboardNames(dashboardName)
                    .build();
            cw.deleteDashboards(dashboardsRequest);
            System.out.println(dashboardName + " was successfully deleted.");

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getAndOpenMetricImage(CloudWatchClient cw, String fileName) {
        System.out.println("Getting Image data for custom metric.");
        try {
            String myJSON = "{\n" +
                    "  \"title\": \"Example Metric Graph\",\n" +
                    "  \"view\": \"timeSeries\",\n" +
                    "  \"stacked \": false,\n" +
                    "  \"period\": 10,\n" +
                    "  \"width\": 1400,\n" +
                    "  \"height\": 600,\n" +
                    "  \"metrics\": [\n" +
                    "    [\n" +
                    "      \"AWS/Billing\",\n" +
                    "      \"EstimatedCharges\",\n" +
                    "      \"Currency\",\n" +
                    "      \"USD\"\n" +
                    "    ]\n" +
                    "  ]\n" +
                    "}";

            GetMetricWidgetImageRequest imageRequest =
GetMetricWidgetImageRequest.builder()
                    .metricWidget(myJSON)
                    .build();

            GetMetricWidgetImageResponse response =
cw.getMetricWidgetImage(imageRequest);
            SdkBytes sdkBytes = response.metricWidgetImage();
```

```
            byte[] bytes = sdkBytes.asByteArray();
            File outputFile = new File(fileName);
            try (FileOutputStream outputStream = new FileOutputStream(outputFile)) {
                outputStream.write(bytes);
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void describeAnomalyDetectors(CloudWatchClient cw, String
fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            DescribeAnomalyDetectorsRequest detectorsRequest =
DescribeAnomalyDetectorsRequest.builder()
                    .maxResults(10)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            DescribeAnomalyDetectorsResponse response =
cw.describeAnomalyDetectors(detectorsRequest);
            List<AnomalyDetector> anomalyDetectorList = response.anomalyDetectors();
            for (AnomalyDetector detector : anomalyDetectorList) {
                System.out.println("Metric name: " +
detector.singleMetricAnomalyDetector().metricName());
                System.out.println("State: " + detector.stateValue());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
   public static void addAnomalyDetector(CloudWatchClient cw, String fileName) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
           String customMetricName =
rootNode.findValue("customMetricName").asText();

           SingleMetricAnomalyDetector singleMetricAnomalyDetector =
SingleMetricAnomalyDetector.builder()
                   .metricName(customMetricName)
                   .namespace(customMetricNamespace)
                   .stat("Maximum")
                   .build();

           PutAnomalyDetectorRequest anomalyDetectorRequest =
PutAnomalyDetectorRequest.builder()
                   .singleMetricAnomalyDetector(singleMetricAnomalyDetector)
                   .build();

           cw.putAnomalyDetector(anomalyDetectorRequest);
           System.out.println("Added anomaly detector for metric " +
customMetricName + ".");

       } catch (CloudWatchException | IOException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }

   public static void getAlarmHistory(CloudWatchClient cw, String fileName, String
date) {
       try {
           // Read values from the JSON file.
           JsonParser parser = new JsonFactory().createParser(new File(fileName));
           com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
           String alarmName = rootNode.findValue("exampleAlarmName").asText();

           Instant start = Instant.parse(date);
```

```
            Instant endDate = Instant.now();
            DescribeAlarmHistoryRequest historyRequest =
DescribeAlarmHistoryRequest.builder()
                    .startDate(start)
                    .endDate(endDate)
                    .alarmName(alarmName)
                    .historyItemType(HistoryItemType.ACTION)
                    .build();

            DescribeAlarmHistoryResponse response =
cw.describeAlarmHistory(historyRequest);
            List<AlarmHistoryItem> historyItems = response.alarmHistoryItems();
            if (historyItems.isEmpty()) {
                System.out.println("No alarm history data found for " + alarmName +
".");
            } else {
                for (AlarmHistoryItem item : historyItems) {
                    System.out.println("History summary: " + item.historySummary());
                    System.out.println("Time stamp: " + item.timestamp());
                }
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void checkForMetricAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            boolean hasAlarm = false;
            int retries = 10;

            DescribeAlarmsForMetricRequest metricRequest =
DescribeAlarmsForMetricRequest.builder()
                    .metricName(customMetricName)
```

```
                    .namespace(customMetricNamespace)
                    .build();

            while (!hasAlarm && retries > 0) {
                DescribeAlarmsForMetricResponse response =
cw.describeAlarmsForMetric(metricRequest);
                hasAlarm = response.hasMetricAlarms();
                retries--;
                Thread.sleep(20000);
                System.out.println(".");
            }
            if (!hasAlarm)
                System.out.println("No Alarm state found for " + customMetricName +
" after 10 retries.");
            else
                System.out.println("Alarm state found for " + customMetricName +
".");

        } catch (CloudWatchException | IOException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void addMetricDataForAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set an Instant object.
            String time =
ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
            Instant instant = Instant.parse(time);

            MetricDatum datum = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1001.00)
```

```
                    .timestamp(instant)
                    .build();

            MetricDatum datum2 = MetricDatum.builder()
                    .metricName(customMetricName)
                    .unit(StandardUnit.NONE)
                    .value(1002.00)
                    .timestamp(instant)
                    .build();

            List<MetricDatum> metricDataList = new ArrayList<>();
            metricDataList.add(datum);
            metricDataList.add(datum2);

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace(customMetricNamespace)
                    .metricData(metricDataList)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric " +
customMetricName);

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getCustomMetricData(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();

            // Set the date.
            Instant nowDate = Instant.now();

            long hours = 1;
```

```
            long minutes = 30;
            Instant date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(minutes,
                    ChronoUnit.MINUTES);

            Metric met = Metric.builder()
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .build();

            MetricStat metStat = MetricStat.builder()
                    .stat("Maximum")
                    .period(1)
                    .metric(met)
                    .build();

            MetricDataQuery dataQUery = MetricDataQuery.builder()
                    .metricStat(metStat)
                    .id("foo2")
                    .returnData(true)
                    .build();

            List<MetricDataQuery> dq = new ArrayList<>();
            dq.add(dataQUery);

            GetMetricDataRequest getMetReq = GetMetricDataRequest.builder()
                    .maxDatapoints(10)
                    .scanBy(ScanBy.TIMESTAMP_DESCENDING)
                    .startTime(nowDate)
                    .endTime(date2)
                    .metricDataQueries(dq)
                    .build();

            GetMetricDataResponse response = cw.getMetricData(getMetReq);
            List<MetricDataResult> data = response.metricDataResults();
            for (MetricDataResult item : data) {
                System.out.println("The label is " + item.label());
                System.out.println("The status code is " +
item.statusCode().toString());
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }

    public static void describeAlarms(CloudWatchClient cw) {
        try {
            List<AlarmType> typeList = new ArrayList<>();
            typeList.add(AlarmType.METRIC_ALARM);

            DescribeAlarmsRequest alarmsRequest = DescribeAlarmsRequest.builder()
                    .alarmTypes(typeList)
                    .maxRecords(10)
                    .build();

            DescribeAlarmsResponse response = cw.describeAlarms(alarmsRequest);
            List<MetricAlarm> alarmList = response.metricAlarms();
            for (MetricAlarm alarm : alarmList) {
                System.out.println("Alarm name: " + alarm.alarmName());
                System.out.println("Alarm description: " +
alarm.alarmDescription());
            }
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createAlarm(CloudWatchClient cw, String fileName) {
        try {
            // Read values from the JSON file.
            JsonParser parser = new JsonFactory().createParser(new File(fileName));
            com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
            String customMetricNamespace =
rootNode.findValue("customMetricNamespace").asText();
            String customMetricName =
rootNode.findValue("customMetricName").asText();
            String alarmName = rootNode.findValue("exampleAlarmName").asText();
            String emailTopic = rootNode.findValue("emailTopic").asText();
            String accountId = rootNode.findValue("accountId").asText();
            String region = rootNode.findValue("region").asText();

            // Create a List for alarm actions.
            List<String> alarmActions = new ArrayList<>();
            alarmActions.add("arn:aws:sns:" + region + ":" + accountId + ":" +
emailTopic);
```

```
            PutMetricAlarmRequest alarmRequest = PutMetricAlarmRequest.builder()
                    .alarmActions(alarmActions)
                    .alarmDescription("Example metric alarm")
                    .alarmName(alarmName)

.comparisonOperator(ComparisonOperator.GREATER_THAN_OR_EQUAL_TO_THRESHOLD)
                    .threshold(100.00)
                    .metricName(customMetricName)
                    .namespace(customMetricNamespace)
                    .evaluationPeriods(1)
                    .period(10)
                    .statistic("Maximum")
                    .datapointsToAlarm(1)
                    .treatMissingData("ignore")
                    .build();

            cw.putMetricAlarm(alarmRequest);
            System.out.println(alarmName + " was successfully created!");
            return alarmName;

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void addMetricToDashboard(CloudWatchClient cw, String fileName,
String dashboardName) {
        try {
            PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                    .dashboardName(dashboardName)
                    .dashboardBody(readFileAsString(fileName))
                    .build();

            cw.putDashboard(dashboardRequest);
            System.out.println(dashboardName + " was successfully updated.");

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
    public static void createNewCustomMetric(CloudWatchClient cw, Double dataPoint)
{
        try {
            Dimension dimension = Dimension.builder()
                    .name("UNIQUE_PAGES")
                    .value("URLS")
                    .build();

            // Set an Instant object.
            String time =
ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT);
            Instant instant = Instant.parse(time);

            MetricDatum datum = MetricDatum.builder()
                    .metricName("PAGES_VISITED")
                    .unit(StandardUnit.NONE)
                    .value(dataPoint)
                    .timestamp(instant)
                    .dimensions(dimension)
                    .build();

            PutMetricDataRequest request = PutMetricDataRequest.builder()
                    .namespace("SITE/TRAFFIC")
                    .metricData(datum)
                    .build();

            cw.putMetricData(request);
            System.out.println("Added metric values for for metric PAGES_VISITED");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listDashboards(CloudWatchClient cw) {
        try {
            ListDashboardsIterable listRes = cw.listDashboardsPaginator();
            listRes.stream()
                    .flatMap(r -> r.dashboardEntries().stream())
                    .forEach(entry -> {
                        System.out.println("Dashboard name is: " +
entry.dashboardName());
```

```
                        System.out.println("Dashboard ARN is: " +
entry.dashboardArn());
                    });

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createDashboardWithMetrics(CloudWatchClient cw, String
dashboardName, String fileName) {
        try {
            PutDashboardRequest dashboardRequest = PutDashboardRequest.builder()
                    .dashboardName(dashboardName)
                    .dashboardBody(readFileAsString(fileName))
                    .build();

            PutDashboardResponse response = cw.putDashboard(dashboardRequest);
            System.out.println(dashboardName + " was successfully created.");
            List<DashboardValidationMessage> messages =
response.dashboardValidationMessages();
            if (messages.isEmpty()) {
                System.out.println("There are no messages in the new Dashboard");
            } else {
                for (DashboardValidationMessage message : messages) {
                    System.out.println("Message is: " + message.message());
                }
            }

        } catch (CloudWatchException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String readFileAsString(String file) throws IOException {
        return new String(Files.readAllBytes(Paths.get(file)));
    }

    public static void getMetricStatistics(CloudWatchClient cw, String costDateWeek)
{
        try {
            Instant start = Instant.parse(costDateWeek);
```

```
            Instant endDate = Instant.now();
            Dimension dimension = Dimension.builder()
                    .name("Currency")
                    .value("USD")
                    .build();

            List<Dimension> dimensionList = new ArrayList<>();
            dimensionList.add(dimension);
            GetMetricStatisticsRequest statisticsRequest =
GetMetricStatisticsRequest.builder()
                    .metricName("EstimatedCharges")
                    .namespace("AWS/Billing")
                    .dimensions(dimensionList)
                    .statistics(Statistic.MAXIMUM)
                    .startTime(start)
                    .endTime(endDate)
                    .period(86400)
                    .build();

            GetMetricStatisticsResponse response =
cw.getMetricStatistics(statisticsRequest);
            List<Datapoint> data = response.datapoints();
            if (!data.isEmpty()) {
                for (Datapoint datapoint : data) {
                    System.out
                            .println("Timestamp: " + datapoint.timestamp() + "
Maximum value: " + datapoint.maximum());
                }
            } else {
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getAndDisplayMetricStatistics(CloudWatchClient cw, String
nameSpace, String metVal,
            String metricOption, String date, Dimension myDimension) {
        try {
            Instant start = Instant.parse(date);
            Instant endDate = Instant.now();
```

```
            GetMetricStatisticsRequest statisticsRequest =
GetMetricStatisticsRequest.builder()
                    .endTime(endDate)
                    .startTime(start)
                    .dimensions(myDimension)
                    .metricName(metVal)
                    .namespace(nameSpace)
                    .period(86400)
                    .statistics(Statistic.fromValue(metricOption))
                    .build();

            GetMetricStatisticsResponse response =
cw.getMetricStatistics(statisticsRequest);
            List<Datapoint> data = response.datapoints();
            if (!data.isEmpty()) {
                for (Datapoint datapoint : data) {
                    System.out
                            .println("Timestamp: " + datapoint.timestamp() + "
Maximum value: " + datapoint.maximum());
                }
            } else {
                System.out.println("The returned data list is empty");
            }

        } catch (CloudWatchException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static Dimension getSpecificMet(CloudWatchClient cw, String namespace) {
        try {
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();

            ListMetricsResponse response = cw.listMetrics(request);
            List<Metric> myList = response.metrics();
            Metric metric = myList.get(0);
            return metric.dimensions().get(0);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
        return null;
    }

    public static ArrayList<String> listMets(CloudWatchClient cw, String namespace)
{
        try {
            ArrayList<String> metList = new ArrayList<>();
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .namespace(namespace)
                    .build();

            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> metList.add(metrics.metricName()));

            return metList;

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static ArrayList<String> listNameSpaces(CloudWatchClient cw) {
        try {
            ArrayList<String> nameSpaceList = new ArrayList<>();
            ListMetricsRequest request = ListMetricsRequest.builder()
                    .build();

            ListMetricsIterable listRes = cw.listMetricsPaginator(request);
            listRes.stream()
                    .flatMap(r -> r.metrics().stream())
                    .forEach(metrics -> {
                        String data = metrics.namespace();
                        if (!nameSpaceList.contains(data)) {
                            nameSpaceList.add(data);
                        }
                    });

            return nameSpaceList;
```

```
        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric
  - DescribeAnomalyDetectors
  - GetMetricData
  - GetMetricStatistics
  - GetMetricWidgetImage
  - ListMetrics
  - PutAnomalyDetector
  - PutDashboard
  - PutMetricAlarm
  - PutMetricData

CloudWatch Exemplos de eventos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with CloudWatch Events.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adição de um destino

O exemplo de código a seguir mostra como adicionar um alvo a um evento da Amazon CloudWatch Events.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutTargetsRequest;
import software.amazon.awssdk.services.cloudwatchevents.model.Target;

/**
 * To run this Java V2 code example, ensure that you have setup your development
 * environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutTargets {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                  <ruleName> <functionArn> <targetId>\s

                Where:
                  ruleName - A rule name (for example, myrule).
                  functionArn - An AWS Lambda function ARN (for example,
arn:aws:lambda:us-west-2:xxxxxx047983:function:lamda1).
                  targetId - A target id value.
                """;

       if (args.length != 3) {
           System.out.println(usage);
           System.exit(1);
       }

       String ruleName = args[0];
       String functionArn = args[1];
       String targetId = args[2];
       CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
               .build();

       putCWTargets(cwe, ruleName, functionArn, targetId);
       cwe.close();
   }

   public static void putCWTargets(CloudWatchEventsClient cwe, String ruleName,
String functionArn, String targetId) {
       try {
           Target target = Target.builder()
                   .arn(functionArn)
                   .id(targetId)
                   .build();

           PutTargetsRequest request = PutTargetsRequest.builder()
                   .targets(target)
                   .rule(ruleName)
                   .build();

           cwe.putTargets(request);
           System.out.printf(
                   "Successfully created CloudWatch events target for rule %s",
                   ruleName);

       } catch (CloudWatchException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for Java 2.x da API.

Criar uma regra agendada

O exemplo de código a seguir mostra como criar uma regra programada do Amazon CloudWatch Events.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutRuleRequest;
import software.amazon.awssdk.services.cloudwatchevents.model.PutRuleResponse;
import software.amazon.awssdk.services.cloudwatchevents.model.RuleState;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutRule {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <ruleName> roleArn>\s
```

```
                Where:
                  ruleName - A rule name (for example, myrule).
                  roleArn - A role ARN value (for example,
 arn:aws:iam::xxxxxx047983:user/MyUser).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String ruleName = args[0];
        String roleArn = args[1];
        CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
                .build();

        putCWRule(cwe, ruleName, roleArn);
        cwe.close();
    }

    public static void putCWRule(CloudWatchEventsClient cwe, String ruleName, String
 roleArn) {
        try {
            PutRuleRequest request = PutRuleRequest.builder()
                    .name(ruleName)
                    .roleArn(roleArn)
                    .scheduleExpression("rate(5 minutes)")
                    .state(RuleState.ENABLED)
                    .build();

            PutRuleResponse response = cwe.putRule(request);
            System.out.printf(
                    "Successfully created CloudWatch events rule %s with arn %s",
                    roleArn, response.ruleArn());

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for Java 2.x da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar CloudWatch eventos da Amazon Events.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchevents.CloudWatchEventsClient;
import software.amazon.awssdk.services.cloudwatchevents.model.PutEventsRequest;
import software.amazon.awssdk.services.cloudwatchevents.model.PutEventsRequestEntry;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutEvents {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <resourceArn>

                Where:
                   resourceArn - An Amazon Resource Name (ARN) related to the
 events.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String resourceArn = args[0];
        CloudWatchEventsClient cwe = CloudWatchEventsClient.builder()
                .build();

        putCWEvents(cwe, resourceArn);
        cwe.close();
    }

    public static void putCWEvents(CloudWatchEventsClient cwe, String resourceArn) {
        try {
            final String EVENT_DETAILS = "{ \"key1\": \"value1\", \"key2\":
 \"value2\" }";

            PutEventsRequestEntry requestEntry = PutEventsRequestEntry.builder()
                    .detail(EVENT_DETAILS)
                    .detailType("sampleSubmitted")
                    .resources(resourceArn)
                    .source("aws-sdk-java-cloudwatch-example")
                    .build();

            PutEventsRequest request = PutEventsRequest.builder()
                    .entries(requestEntry)
                    .build();

            cwe.putEvents(request);
            System.out.println("Successfully put CloudWatch event");

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

CloudWatch Exemplos de registros usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um filtro de assinatura

O exemplo de código a seguir mostra como criar um filtro de assinatura do Amazon CloudWatch Logs.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import software.amazon.awssdk.services.cloudwatchlogs.model.CloudWatchLogsException;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.PutSubscriptionFilterRequest;

/**
 * Before running this code example, you need to grant permission to CloudWatch
 * Logs the right to execute your Lambda function.
 * To perform this task, you can use this CLI command:
 *
 * aws lambda add-permission --function-name "lamda1" --statement-id "lamda1"
 * --principal "logs.us-west-2.amazonaws.com" --action "lambda:InvokeFunction"
```

```
 * --source-arn "arn:aws:logs:us-west-2:111111111111:log-group:testgroup:*"
 * --source-account "111111111111"
 *
 * Make sure you replace the function name with your function name and replace
 * '111111111111' with your account details.
 * For more information, see "Subscription Filters with AWS Lambda" in the
 * Amazon CloudWatch Logs Guide.
 *
 *
 * Also, before running this Java V2 code example,set up your development
 * environment,including your credentials.
 *
 * For more information,see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 */

public class PutSubscriptionFilter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <filter> <pattern> <logGroup> <functionArn>\s

                Where:
                  filter - A filter name (for example, myfilter).
                  pattern - A filter pattern (for example, ERROR).
                  logGroup - A log group name (testgroup).
                  functionArn - An AWS Lambda function ARN (for example,
 arn:aws:lambda:us-west-2:111111111111:function:lambda1) .
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String filter = args[0];
        String pattern = args[1];
        String logGroup = args[2];
        String functionArn = args[3];
        Region region = Region.US_WEST_2;
        CloudWatchLogsClient cwl = CloudWatchLogsClient.builder()
```

```
                .region(region)
                .build();

        putSubFilters(cwl, filter, pattern, logGroup, functionArn);
        cwl.close();
    }

    public static void putSubFilters(CloudWatchLogsClient cwl,
            String filter,
            String pattern,
            String logGroup,
            String functionArn) {

        try {
            PutSubscriptionFilterRequest request =
 PutSubscriptionFilterRequest.builder()
                    .filterName(filter)
                    .filterPattern(pattern)
                    .logGroupName(logGroup)
                    .destinationArn(functionArn)
                    .build();

            cwl.putSubscriptionFilter(request);
            System.out.printf(
                    "Successfully created CloudWatch logs subscription filter %s",
                    filter);

        } catch (CloudWatchLogsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutSubscriptionFiltera Referência AWS SDK for Java 2.x da API.

Excluir um filtro de assinatura

O exemplo de código a seguir mostra como excluir um filtro de assinatura do Amazon CloudWatch Logs.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DeleteSubscriptionFilterRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteSubscriptionFilter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <filter> <logGroup>

                Where:
                  filter - The name of the subscription filter (for example,
 MyFilter).
                  logGroup - The name of the log group. (for example, testgroup).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String filter = args[0];
        String logGroup = args[1];
        CloudWatchLogsClient logs = CloudWatchLogsClient.builder()
```

```
                .build();

        deleteSubFilter(logs, filter, logGroup);
        logs.close();
    }

    public static void deleteSubFilter(CloudWatchLogsClient logs, String filter,
 String logGroup) {
        try {
            DeleteSubscriptionFilterRequest request =
 DeleteSubscriptionFilterRequest.builder()
                    .filterName(filter)
                    .logGroupName(logGroup)
                    .build();

            logs.deleteSubscriptionFilter(request);
            System.out.printf("Successfully deleted CloudWatch logs subscription
 filter %s", filter);

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteSubscriptionFiltera Referência AWS SDK for Java 2.x da API.

Descreva os filtros de assinatura existentes

O exemplo de código a seguir mostra como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.cloudwatch.model.CloudWatchException;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsClient;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DescribeSubscriptionFiltersRequest;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.DescribeSubscriptionFiltersResponse;
import software.amazon.awssdk.services.cloudwatchlogs.model.SubscriptionFilter;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeSubscriptionFilters {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                  <logGroup>

                Where:
                  logGroup - A log group name (for example, myloggroup).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String logGroup = args[0];
        CloudWatchLogsClient logs = CloudWatchLogsClient.builder()
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        describeFilters(logs, logGroup);
        logs.close();
    }
```

```
    public static void describeFilters(CloudWatchLogsClient logs, String logGroup) {
        try {
            boolean done = false;
            String newToken = null;

            while (!done) {
                DescribeSubscriptionFiltersResponse response;
                if (newToken == null) {
                    DescribeSubscriptionFiltersRequest request =
DescribeSubscriptionFiltersRequest.builder()
                            .logGroupName(logGroup)
                            .limit(1).build();

                    response = logs.describeSubscriptionFilters(request);
                } else {
                    DescribeSubscriptionFiltersRequest request =
DescribeSubscriptionFiltersRequest.builder()
                            .nextToken(newToken)
                            .logGroupName(logGroup)
                            .limit(1).build();
                    response = logs.describeSubscriptionFilters(request);
                }

                for (SubscriptionFilter filter : response.subscriptionFilters()) {
                    System.out.printf("Retrieved filter with name %s, " + "pattern
%s " + "and destination arn %s",
                            filter.filterName(),
                            filter.filterPattern(),
                            filter.destinationArn());
                }

                if (response.nextToken() == null) {
                    done = true;
                } else {
                    newToken = response.nextToken();
                }
            }

        } catch (CloudWatchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.printf("Done");
    }
```

```
}
```

- Para obter detalhes da API, consulte DescribeSubscriptionFiltersa Referência AWS SDK for Java 2.x da API.

Iniciar uma sessão Live Tail

O exemplo de código a seguir mostra como iniciar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

SDK para Java 2.x

Inclua os arquivos necessários.

```
import io.reactivex.FlowableSubscriber;
import io.reactivex.annotations.NonNull;
import org.reactivestreams.Subscription;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.cloudwatchlogs.CloudWatchLogsAsyncClient;
import software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionLogEvent;
import software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionStart;
import software.amazon.awssdk.services.cloudwatchlogs.model.LiveTailSessionUpdate;
import software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailRequest;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailResponseHandler;
import software.amazon.awssdk.services.cloudwatchlogs.model.CloudWatchLogsException;
import
 software.amazon.awssdk.services.cloudwatchlogs.model.StartLiveTailResponseStream;

import java.util.Date;
import java.util.List;
import java.util.concurrent.atomic.AtomicReference;
```

Gerencie os eventos da sessão do Live Tail.

```
    private static StartLiveTailResponseHandler
 getStartLiveTailResponseStreamHandler(
            AtomicReference<Subscription> subscriptionAtomicReference) {
        return StartLiveTailResponseHandler.builder()
            .onResponse(r -> System.out.println("Received initial response"))
```

```
            .onError(throwable -> {
                CloudWatchLogsException e = (CloudWatchLogsException)
throwable.getCause();
                System.err.println(e.awsErrorDetails().errorMessage());
                System.exit(1);
            })
            .subscriber(() -> new FlowableSubscriber<>() {
                @Override
                public void onSubscribe(@NonNull Subscription s) {
                    subscriptionAtomicReference.set(s);
                    s.request(Long.MAX_VALUE);
                }

                @Override
                public void onNext(StartLiveTailResponseStream event) {
                    if (event instanceof LiveTailSessionStart) {
                        LiveTailSessionStart sessionStart = (LiveTailSessionStart)
event;
                        System.out.println(sessionStart);
                    } else if (event instanceof LiveTailSessionUpdate) {
                        LiveTailSessionUpdate sessionUpdate =
(LiveTailSessionUpdate) event;
                        List<LiveTailSessionLogEvent> logEvents =
sessionUpdate.sessionResults();
                        logEvents.forEach(e -> {
                            long timestamp = e.timestamp();
                            Date date = new Date(timestamp);
                            System.out.println("[" + date + "] " + e.message());
                        });
                    } else {
                        throw CloudWatchLogsException.builder().message("Unknown
event type").build();
                    }
                }

                @Override
                public void onError(Throwable throwable) {
                    System.out.println(throwable.getMessage());
                    System.exit(1);
                }

                @Override
                public void onComplete() {
                    System.out.println("Completed Streaming Session");
```

```
                }
            })
            .build();
    }
```

Inicie a sessão do Live Tail.

```
        CloudWatchLogsAsyncClient cloudWatchLogsAsyncClient =
                CloudWatchLogsAsyncClient.builder()
                    .credentialsProvider(ProfileCredentialsProvider.create())
                    .build();

        StartLiveTailRequest request =
                StartLiveTailRequest.builder()
                    .logGroupIdentifiers(logGroupIdentifiers)
                    .logStreamNames(logStreamNames)
                    .logEventFilterPattern(logEventFilterPattern)
                    .build();

        /* Create a reference to store the subscription */
        final AtomicReference<Subscription> subscriptionAtomicReference = new
 AtomicReference<>(null);

        cloudWatchLogsAsyncClient.startLiveTail(request,
 getStartLiveTailResponseStreamHandler(subscriptionAtomicReference));
```

Interrompa a sessão do Live Tail após um período decorrido.

```
        /* Set a timeout for the session and cancel the subscription. This will:
         * 1). Close the stream
         * 2). Stop the Live Tail session
         */
        try {
            Thread.sleep(10000);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        if (subscriptionAtomicReference.get() != null) {
            subscriptionAtomicReference.get().cancel();
            System.out.println("Subscription to stream closed");
        }
```

- Para obter detalhes da API, consulte StartLiveTaila Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Cognito Identity usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Cognito Identity.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um banco de identidades do

O exemplo de código a seguir mostra como criar um banco de identidades do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.CreateIdentityPoolRequest;
```

```
import
 software.amazon.awssdk.services.cognitoidentity.model.CreateIdentityPoolResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateIdentityPool {
    public static void main(String[] args) {
        final String usage = """
                Usage:
                    <identityPoolName>\s

                Where:
                    identityPoolName - The name to give your identity pool.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String identityPoolName = args[0];
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String identityPoolId = createIdPool(cognitoClient, identityPoolName);
        System.out.println("Unity pool ID " + identityPoolId);
        cognitoClient.close();
    }

    public static String createIdPool(CognitoIdentityClient cognitoClient, String
 identityPoolName) {
        try {
            CreateIdentityPoolRequest poolRequest =
 CreateIdentityPoolRequest.builder()
                    .allowUnauthenticatedIdentities(false)
```

```
                    .identityPoolName(identityPoolName)
                    .build();

            CreateIdentityPoolResponse response =
 cognitoClient.createIdentityPool(poolRequest);
            return response.identityPoolId();

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateIdentityPool
  - ListIdentityPools

Excluir um grupo de identidades

O exemplo de código a seguir mostra como excluir um banco de identidades do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.awscore.exception.AwsServiceException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.DeleteIdentityPoolRequest;

/**
```

```
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteIdentityPool {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <identityPoolId>\s

                Where:
                    identityPoolId - The Id value of your identity pool.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String identityPoold = args[0];
        CognitoIdentityClient cognitoIdClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();

        deleteIdPool(cognitoIdClient, identityPoold);
        cognitoIdClient.close();
    }

    public static void deleteIdPool(CognitoIdentityClient cognitoIdClient, String
 identityPoold) {
        try {

            DeleteIdentityPoolRequest identityPoolRequest =
 DeleteIdentityPoolRequest.builder()
                    .identityPoolId(identityPoold)
                    .build();

            cognitoIdClient.deleteIdentityPool(identityPoolRequest);
```

```
            System.out.println("Done");

        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteIdentityPoola Referência AWS SDK for Java 2.x da API.

Receber credenciais para uma identidade

O exemplo de código a seguir mostra como receber credenciais de uma identidade do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.GetCredentialsForIdentityRequest;
import
 software.amazon.awssdk.services.cognitoidentity.model.GetCredentialsForIdentityResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetIdentityCredentials {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <identityId>\s

            Where:
                identityId - The Id of an existing identity in the format
 REGION:GUID.
            """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String identityId = args[0];
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        getCredsForIdentity(cognitoClient, identityId);
        cognitoClient.close();
    }

    public static void getCredsForIdentity(CognitoIdentityClient cognitoClient,
 String identityId) {
        try {
            GetCredentialsForIdentityRequest getCredentialsForIdentityRequest =
 GetCredentialsForIdentityRequest
                    .builder()
                    .identityId(identityId)
                    .build();

            GetCredentialsForIdentityResponse response = cognitoClient
                    .getCredentialsForIdentity(getCredentialsForIdentityRequest);
            System.out.println(
                    "Identity ID " + response.identityId() + ", Access key ID " +
 response.credentials().accessKeyId());
```

```
        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetCredentialsForIdentity a Referência AWS SDK for Java 2.x da API.

Listar grupos de identidades

O exemplo de código a seguir mostra como ter uma lista de bancos de identidades do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.cognitoidentity.CognitoIdentityClient;
import
 software.amazon.awssdk.services.cognitoidentity.model.ListIdentityPoolsRequest;
import
 software.amazon.awssdk.services.cognitoidentity.model.ListIdentityPoolsResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class ListIdentityPools {
    public static void main(String[] args) {
        CognitoIdentityClient cognitoClient = CognitoIdentityClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listIdPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listIdPools(CognitoIdentityClient cognitoClient) {
        try {
            ListIdentityPoolsRequest poolsRequest =
 ListIdentityPoolsRequest.builder()
                    .maxResults(15)
                    .build();

            ListIdentityPoolsResponse response =
 cognitoClient.listIdentityPools(poolsRequest);
            response.identityPools().forEach(pool -> {
                System.out.println("Pool ID: " + pool.identityPoolId());
                System.out.println("Pool name: " + pool.identityPoolName());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateIdentityPool
  - ListIdentityPools

Exemplos do provedor de identidade do Amazon Cognito usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Cognito

Os exemplos de código a seguir mostram como começar a usar o Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
```

```
 */
public class ListUserPools {
    public static void main(String[] args) {
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUserPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listAllUserPools(CognitoIdentityProviderClient cognitoClient)
 {
        try {
            ListUserPoolsRequest request = ListUserPoolsRequest.builder()
                    .maxResults(10)
                    .build();

            ListUserPoolsResponse response = cognitoClient.listUserPools(request);
            response.userPools().forEach(userpool -> {
                System.out.println("User pool " + userpool.name() + ", User ID " +
 userpool.id());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void confirmSignUp(CognitoIdentityProviderClient
identityProviderClient, String clientId, String code,
           String userName) {
       try {
           ConfirmSignUpRequest signUpRequest = ConfirmSignUpRequest.builder()
                   .clientId(clientId)
                   .confirmationCode(code)
                   .username(userName)
                   .build();

           identityProviderClient.confirmSignUp(signUpRequest);
           System.out.println(userName + " was confirmed");

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ConfirmSignUpa Referência AWS SDK for Java 2.x da API.

Criar um grupo de usuários

O exemplo de código a seguir mostra como criar um grupo de usuários do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateUserPool {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <userPoolName>\s

                Where:
                    userPoolName - The name to give your user pool when it's
 created.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String userPoolName = args[0];
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String id = createPool(cognitoClient, userPoolName);
        System.out.println("User pool ID: " + id);
        cognitoClient.close();
    }

    public static String createPool(CognitoIdentityProviderClient cognitoClient,
 String userPoolName) {
        try {
            CreateUserPoolRequest request = CreateUserPoolRequest.builder()
                    .poolName(userPoolName)
                    .build();

            CreateUserPoolResponse response = cognitoClient.createUserPool(request);
            return response.userPool().id();

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateUserPoola Referência AWS SDK for Java 2.x da API.

Criar um cliente da aplicação

O exemplo de código a seguir mostra como criar uma aplicação de cliente do grupo de usuários do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolClientRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CreateUserPoolClientResponse;

/**
 * A user pool client app is an application that authenticates with Amazon
 * Cognito user pools.
 * When you create a user pool, you can configure app clients that allow mobile
 * or web applications
 * to call API operations to authenticate users, manage user attributes and
 * profiles,
 * and implement sign-up and sign-in flows.
 *
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateUserPoolClient {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <clientName> <userPoolId>\s

                Where:
                    clientName - The name for the user pool client to create.
```

```
                    userPoolId - The ID for the user pool.
                """";

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clientName = args[0];
        String userPoolId = args[1];
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createPoolClient(cognitoClient, clientName, userPoolId);
        cognitoClient.close();
    }

    public static void createPoolClient(CognitoIdentityProviderClient cognitoClient,
 String clientName,
            String userPoolId) {
        try {
            CreateUserPoolClientRequest request =
 CreateUserPoolClientRequest.builder()
                    .clientName(clientName)
                    .userPoolId(userPoolId)
                    .build();

            CreateUserPoolClientResponse response =
 cognitoClient.createUserPoolClient(request);
            System.out.println("User pool " + response.userPoolClient().clientName()
 + " created. ID: "
                    + response.userPoolClient().clientId());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateUserPoolClienta Referência AWS SDK for Java 2.x da API.

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String getSecretForAppMFA(CognitoIdentityProviderClient
identityProviderClient, String session) {
       AssociateSoftwareTokenRequest softwareTokenRequest =
AssociateSoftwareTokenRequest.builder()
               .session(session)
               .build();

       AssociateSoftwareTokenResponse tokenResponse = identityProviderClient
               .associateSoftwareToken(softwareTokenRequest);
       String secretCode = tokenResponse.secretCode();
       System.out.println("Enter this token into Google Authenticator");
       System.out.println(secretCode);
       return tokenResponse.session();
   }
```

- Para obter detalhes da API, consulte AssociateSoftwareTokena Referência AWS SDK for Java 2.x da API.

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getAdminUser(CognitoIdentityProviderClient
identityProviderClient, String userName,
           String poolId) {
       try {
           AdminGetUserRequest userRequest = AdminGetUserRequest.builder()
                   .username(userName)
                   .userPoolId(poolId)
                   .build();

           AdminGetUserResponse response =
identityProviderClient.adminGetUser(userRequest);
           System.out.println("User status " + response.userStatusAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte AdminGetUsera Referência AWS SDK for Java 2.x da API.

Listar os grupos de usuários

O exemplo de código a seguir mostra como listar os grupos de usuários do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUserPoolsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListUserPools {
    public static void main(String[] args) {
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUserPools(cognitoClient);
        cognitoClient.close();
    }

    public static void listAllUserPools(CognitoIdentityProviderClient cognitoClient)
 {
        try {
            ListUserPoolsRequest request = ListUserPoolsRequest.builder()
                    .maxResults(10)
```

```
                    .build();

            ListUserPoolsResponse response = cognitoClient.listUserPools(request);
            response.userPools().forEach(userpool -> {
                System.out.println("User pool " + userpool.name() + ", User ID " +
 userpool.id());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUserPoolsa Referência AWS SDK for Java 2.x da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUsersRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ListUsersResponse;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListUsers {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <userPoolId>\s

                Where:
                    userPoolId - The ID given to your user pool when it's created.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userPoolId = args[0];
        CognitoIdentityProviderClient cognitoClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllUsers(cognitoClient, userPoolId);
        listUsersFilter(cognitoClient, userPoolId);
        cognitoClient.close();
    }

    public static void listAllUsers(CognitoIdentityProviderClient cognitoClient,
 String userPoolId) {
        try {
            ListUsersRequest usersRequest = ListUsersRequest.builder()
                    .userPoolId(userPoolId)
                    .build();

            ListUsersResponse response = cognitoClient.listUsers(usersRequest);
            response.users().forEach(user -> {
```

```
                System.out.println("User " + user.username() + " Status " +
 user.userStatus() + " Created "
                        + user.userCreateDate());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Shows how to list users by using a filter.
    public static void listUsersFilter(CognitoIdentityProviderClient cognitoClient,
 String userPoolId) {

        try {
            String filter = "email = \"tblue@noserver.com\"";
            ListUsersRequest usersRequest = ListUsersRequest.builder()
                    .userPoolId(userPoolId)
                    .filter(filter)
                    .build();

            ListUsersResponse response = cognitoClient.listUsers(usersRequest);
            response.users().forEach(user -> {
                System.out.println("User with filter applied " + user.username() + "
 Status " + user.userStatus()
                        + " Created " + user.userCreateDate());
            });

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Java 2.x da API.

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void resendConfirmationCode(CognitoIdentityProviderClient
identityProviderClient, String clientId,
           String userName) {
       try {
           ResendConfirmationCodeRequest codeRequest =
ResendConfirmationCodeRequest.builder()
                   .clientId(clientId)
                   .username(userName)
                   .build();

           ResendConfirmationCodeResponse response =
identityProviderClient.resendConfirmationCode(codeRequest);
           System.out.println("Method of delivery is " +
response.codeDeliveryDetails().deliveryMediumAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ResendConfirmationCodea Referência AWS SDK for Java 2.x da API.

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Respond to an authentication challenge.
   public static void adminRespondToAuthChallenge(CognitoIdentityProviderClient
identityProviderClient,
           String userName, String clientId, String mfaCode, String session) {
       System.out.println("SOFTWARE_TOKEN_MFA challenge is generated");
       Map<String, String> challengeResponses = new HashMap<>();

       challengeResponses.put("USERNAME", userName);
       challengeResponses.put("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

       AdminRespondToAuthChallengeRequest respondToAuthChallengeRequest =
AdminRespondToAuthChallengeRequest.builder()
               .challengeName(ChallengeNameType.SOFTWARE_TOKEN_MFA)
               .clientId(clientId)
               .challengeResponses(challengeResponses)
               .session(session)
               .build();

       AdminRespondToAuthChallengeResponse respondToAuthChallengeResult =
identityProviderClient
               .adminRespondToAuthChallenge(respondToAuthChallengeRequest);
       System.out.println("respondToAuthChallengeResult.getAuthenticationResult()"
               + respondToAuthChallengeResult.authenticationResult());
   }
```

- Para obter detalhes da API, consulte AdminRespondToAuthChallengea Referência AWS SDK for Java 2.x da API.

Inscrever um usuário

O exemplo de código a seguir mostra como inscrever um usuário no Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void signUp(CognitoIdentityProviderClient identityProviderClient,
String clientId, String userName,
           String password, String email) {
       AttributeType userAttrs = AttributeType.builder()
               .name("email")
               .value(email)
               .build();

       List<AttributeType> userAttrsList = new ArrayList<>();
       userAttrsList.add(userAttrs);
       try {
           SignUpRequest signUpRequest = SignUpRequest.builder()
                   .userAttributes(userAttrsList)
                   .username(userName)
                   .clientId(clientId)
                   .password(password)
                   .build();

           identityProviderClient.signUp(signUpRequest);
           System.out.println("User has been signed up ");

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte SignUpa Referência AWS SDK for Java 2.x da API.

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static AdminInitiateAuthResponse
initiateAuth(CognitoIdentityProviderClient identityProviderClient,
           String clientId, String userName, String password, String userPoolId) {
       try {
           Map<String, String> authParameters = new HashMap<>();
           authParameters.put("USERNAME", userName);
           authParameters.put("PASSWORD", password);

           AdminInitiateAuthRequest authRequest =
AdminInitiateAuthRequest.builder()
                   .clientId(clientId)
                   .userPoolId(userPoolId)
                   .authParameters(authParameters)
                   .authFlow(AuthFlowType.ADMIN_USER_PASSWORD_AUTH)
                   .build();

           AdminInitiateAuthResponse response =
identityProviderClient.adminInitiateAuth(authRequest);
           System.out.println("Result Challenge is : " + response.challengeName());
           return response;

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte AdminInitiateAuth a Referência AWS SDK for Java 2.x da API.

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Verify the TOTP and register for MFA.
   public static void verifyTOTP(CognitoIdentityProviderClient
identityProviderClient, String session, String code) {
       try {
           VerifySoftwareTokenRequest tokenRequest =
VerifySoftwareTokenRequest.builder()
                   .userCode(code)
                   .session(session)
                   .build();

           VerifySoftwareTokenResponse verifyResponse =
identityProviderClient.verifySoftwareToken(tokenRequest);
           System.out.println("The status of the token is " +
verifyResponse.statusAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte VerifySoftwareToken a Referência AWS SDK for Java 2.x da API.

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.regions.Region;
import
 software.amazon.awssdk.services.cognitoidentityprovider.CognitoIdentityProviderClient;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminGetUserRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminGetUserResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminInitiateAuthRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminInitiateAuthResponse;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminRespondToAuthChallengeRe
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AdminRespondToAuthChallengeRe
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AssociateSoftwareTokenRequest
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.AssociateSoftwareTokenRespons
import software.amazon.awssdk.services.cognitoidentityprovider.model.AttributeType;
import software.amazon.awssdk.services.cognitoidentityprovider.model.AuthFlowType;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ChallengeNameType;
```

```
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.CognitoIdentityProviderExcept
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ConfirmSignUpRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ResendConfirmationCodeRequest
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.ResendConfirmationCodeRespons
import software.amazon.awssdk.services.cognitoidentityprovider.model.SignUpRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.VerifySoftwareTokenRequest;
import
 software.amazon.awssdk.services.cognitoidentityprovider.model.VerifySoftwareTokenResponse;
import java.security.InvalidKeyException;
import java.security.NoSuchAlgorithmException;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;
import java.util.Scanner;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * TIP: To set up the required user pool, run the AWS Cloud Development Kit (AWS
 * CDK) script provided in this GitHub repo at
 * resources/cdk/cognito_scenario_user_pool_with_mfa.
 *
 * This code example performs the following operations:
 *
 * 1. Invokes the signUp method to sign up a user.
 * 2. Invokes the adminGetUser method to get the user's confirmation status.
 * 3. Invokes the ResendConfirmationCode method if the user requested another
 * code.
 * 4. Invokes the confirmSignUp method.
 * 5. Invokes the AdminInitiateAuth to sign in. This results in being prompted
 * to set up TOTP (time-based one-time password). (The response is
 * “ChallengeName”: “MFA_SETUP”).
 * 6. Invokes the AssociateSoftwareToken method to generate a TOTP MFA private
```

```
 * key. This can be used with Google Authenticator.
 * 7. Invokes the VerifySoftwareToken method to verify the TOTP and register for
 * MFA.
 * 8. Invokes the AdminInitiateAuth to sign in again. This results in being
 * prompted to submit a TOTP (Response: “ChallengeName”: “SOFTWARE_TOKEN_MFA”).
 * 9. Invokes the AdminRespondToAuthChallenge to get back a token.
 */

public class CognitoMVP {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws NoSuchAlgorithmException,
 InvalidKeyException {
        final String usage = """

                Usage:
                    <clientId> <poolId>

                Where:
                    clientId - The app client Id value that you can get from the AWS
 CDK script.
                    poolId - The pool Id that you can get from the AWS CDK script.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clientId = args[0];
        String poolId = args[1];
        CognitoIdentityProviderClient identityProviderClient =
 CognitoIdentityProviderClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Cognito example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Enter your user name");
        Scanner in = new Scanner(System.in);
        String userName = in.nextLine();
```

```
        System.out.println("*** Enter your password");
        String password = in.nextLine();

        System.out.println("*** Enter your email");
        String email = in.nextLine();

        System.out.println("1. Signing up " + userName);
        signUp(identityProviderClient, clientId, userName, password, email);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Getting " + userName + " in the user pool");
        getAdminUser(identityProviderClient, userName, poolId);

        System.out
                .println("*** Conformation code sent to " + userName + ". Would you
like to send a new code? (Yes/No)");
        System.out.println(DASHES);

        System.out.println(DASHES);
        String ans = in.nextLine();

        if (ans.compareTo("Yes") == 0) {
            resendConfirmationCode(identityProviderClient, clientId, userName);
            System.out.println("3. Sending a new confirmation code");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Enter confirmation code that was emailed");
        String code = in.nextLine();
        confirmSignUp(identityProviderClient, clientId, code, userName);
        System.out.println("Rechecking the status of " + userName + " in the user
pool");
        getAdminUser(identityProviderClient, userName, poolId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Invokes the initiateAuth to sign in");
        AdminInitiateAuthResponse authResponse =
initiateAuth(identityProviderClient, clientId, userName, password,
                poolId);
        String mySession = authResponse.session();
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Invokes the AssociateSoftwareToken method to generate
a TOTP key");
        String newSession = getSecretForAppMFA(identityProviderClient, mySession);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Enter the 6-digit code displayed in Google
Authenticator");
        String myCode = in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Verify the TOTP and register for MFA");
        verifyTOTP(identityProviderClient, newSession, myCode);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Re-enter a 6-digit code displayed in Google
Authenticator");
        String mfaCode = in.nextLine();
        AdminInitiateAuthResponse authResponse1 =
initiateAuth(identityProviderClient, clientId, userName, password,
                poolId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9.  Invokes the AdminRespondToAuthChallenge");
        String session2 = authResponse1.session();
        adminRespondToAuthChallenge(identityProviderClient, userName, clientId,
mfaCode, session2);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("All Amazon Cognito operations were successfully
performed");
        System.out.println(DASHES);
    }

    // Respond to an authentication challenge.
    public static void adminRespondToAuthChallenge(CognitoIdentityProviderClient
identityProviderClient,
```

```
            String userName, String clientId, String mfaCode, String session) {
        System.out.println("SOFTWARE_TOKEN_MFA challenge is generated");
        Map<String, String> challengeResponses = new HashMap<>();

        challengeResponses.put("USERNAME", userName);
        challengeResponses.put("SOFTWARE_TOKEN_MFA_CODE", mfaCode);

        AdminRespondToAuthChallengeRequest respondToAuthChallengeRequest =
AdminRespondToAuthChallengeRequest.builder()
                .challengeName(ChallengeNameType.SOFTWARE_TOKEN_MFA)
                .clientId(clientId)
                .challengeResponses(challengeResponses)
                .session(session)
                .build();

        AdminRespondToAuthChallengeResponse respondToAuthChallengeResult =
identityProviderClient
                .adminRespondToAuthChallenge(respondToAuthChallengeRequest);
        System.out.println("respondToAuthChallengeResult.getAuthenticationResult()"
                + respondToAuthChallengeResult.authenticationResult());
    }

    // Verify the TOTP and register for MFA.
    public static void verifyTOTP(CognitoIdentityProviderClient
identityProviderClient, String session, String code) {
        try {
            VerifySoftwareTokenRequest tokenRequest =
VerifySoftwareTokenRequest.builder()
                    .userCode(code)
                    .session(session)
                    .build();

            VerifySoftwareTokenResponse verifyResponse =
identityProviderClient.verifySoftwareToken(tokenRequest);
            System.out.println("The status of the token is " +
verifyResponse.statusAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
   public static AdminInitiateAuthResponse
initiateAuth(CognitoIdentityProviderClient identityProviderClient,
           String clientId, String userName, String password, String userPoolId) {
       try {
           Map<String, String> authParameters = new HashMap<>();
           authParameters.put("USERNAME", userName);
           authParameters.put("PASSWORD", password);

           AdminInitiateAuthRequest authRequest =
AdminInitiateAuthRequest.builder()
                   .clientId(clientId)
                   .userPoolId(userPoolId)
                   .authParameters(authParameters)
                   .authFlow(AuthFlowType.ADMIN_USER_PASSWORD_AUTH)
                   .build();

           AdminInitiateAuthResponse response =
identityProviderClient.adminInitiateAuth(authRequest);
           System.out.println("Result Challenge is : " + response.challengeName());
           return response;

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }

   public static String getSecretForAppMFA(CognitoIdentityProviderClient
identityProviderClient, String session) {
       AssociateSoftwareTokenRequest softwareTokenRequest =
AssociateSoftwareTokenRequest.builder()
               .session(session)
               .build();

       AssociateSoftwareTokenResponse tokenResponse = identityProviderClient
               .associateSoftwareToken(softwareTokenRequest);
       String secretCode = tokenResponse.secretCode();
       System.out.println("Enter this token into Google Authenticator");
       System.out.println(secretCode);
       return tokenResponse.session();
   }
```

```
   public static void confirmSignUp(CognitoIdentityProviderClient
identityProviderClient, String clientId, String code,
           String userName) {
       try {
           ConfirmSignUpRequest signUpRequest = ConfirmSignUpRequest.builder()
                   .clientId(clientId)
                   .confirmationCode(code)
                   .username(userName)
                   .build();

           identityProviderClient.confirmSignUp(signUpRequest);
           System.out.println(userName + " was confirmed");

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void resendConfirmationCode(CognitoIdentityProviderClient
identityProviderClient, String clientId,
           String userName) {
       try {
           ResendConfirmationCodeRequest codeRequest =
ResendConfirmationCodeRequest.builder()
                   .clientId(clientId)
                   .username(userName)
                   .build();

           ResendConfirmationCodeResponse response =
identityProviderClient.resendConfirmationCode(codeRequest);
           System.out.println("Method of delivery is " +
response.codeDeliveryDetails().deliveryMediumAsString());

       } catch (CognitoIdentityProviderException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }

   public static void signUp(CognitoIdentityProviderClient identityProviderClient,
String clientId, String userName,
           String password, String email) {
       AttributeType userAttrs = AttributeType.builder()
```

```
                .name("email")
                .value(email)
                .build();

        List<AttributeType> userAttrsList = new ArrayList<>();
        userAttrsList.add(userAttrs);
        try {
            SignUpRequest signUpRequest = SignUpRequest.builder()
                    .userAttributes(userAttrsList)
                    .username(userName)
                    .clientId(clientId)
                    .password(password)
                    .build();

            identityProviderClient.signUp(signUpRequest);
            System.out.println("User has been signed up ");

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getAdminUser(CognitoIdentityProviderClient
 identityProviderClient, String userName,
            String poolId) {
        try {
            AdminGetUserRequest userRequest = AdminGetUserRequest.builder()
                    .username(userName)
                    .userPoolId(poolId)
                    .build();

            AdminGetUserResponse response =
 identityProviderClient.adminGetUser(userRequest);
            System.out.println("User status " + response.userStatusAsString());

        } catch (CognitoIdentityProviderException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

Exemplos do Amazon Comprehend usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Comprehend.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um classificador de documentos

O exemplo de código a seguir mostra como criar um classificador de documentos do Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import
 software.amazon.awssdk.services.comprehend.model.CreateDocumentClassifierRequest;
import
 software.amazon.awssdk.services.comprehend.model.CreateDocumentClassifierResponse;
import
 software.amazon.awssdk.services.comprehend.model.DocumentClassifierInputDataConfig;

/**
 * Before running this code example, you can setup the necessary resources, such
 * as the CSV file and IAM Roles, by following this document:
 * https://aws.amazon.com/blogs/machine-learning/building-a-custom-classifier-using-
amazon-comprehend/
 *
 * Also, set up your development environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DocumentClassifierDemo {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <dataAccessRoleArn> <s3Uri> <documentClassifierName>
```

```
                Where:
                  dataAccessRoleArn - The ARN value of the role used for this
operation.
                  s3Uri - The Amazon S3 bucket that contains the CSV file.
                  documentClassifierName - The name of the document classifier.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String dataAccessRoleArn = args[0];
        String s3Uri = args[1];
        String documentClassifierName = args[2];

        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        createDocumentClassifier(comClient, dataAccessRoleArn, s3Uri,
documentClassifierName);
        comClient.close();
    }

    public static void createDocumentClassifier(ComprehendClient comClient, String
dataAccessRoleArn, String s3Uri,
            String documentClassifierName) {
        try {
            DocumentClassifierInputDataConfig config =
DocumentClassifierInputDataConfig.builder()
                    .s3Uri(s3Uri)
                    .build();

            CreateDocumentClassifierRequest createDocumentClassifierRequest =
CreateDocumentClassifierRequest.builder()
                    .documentClassifierName(documentClassifierName)
                    .dataAccessRoleArn(dataAccessRoleArn)
                    .languageCode("en")
                    .inputDataConfig(config)
                    .build();
```

```
            CreateDocumentClassifierResponse createDocumentClassifierResult =
 comClient
                    .createDocumentClassifier(createDocumentClassifierRequest);
            String documentClassifierArn =
 createDocumentClassifierResult.documentClassifierArn();
            System.out.println("Document Classifier ARN: " + documentClassifierArn);

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateDocumentClassifiera Referência AWS SDK for Java 2.x da API.

Detectar entidades em um documento

O exemplo de código a seguir mostra como detectar entidades em um documento com o Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.DetectEntitiesRequest;
import software.amazon.awssdk.services.comprehend.model.DetectEntitiesResponse;
import software.amazon.awssdk.services.comprehend.model.Entity;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectEntities {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectEntities");
        detectAllEntities(comClient, text);
        comClient.close();
    }

    public static void detectAllEntities(ComprehendClient comClient, String text) {
        try {
            DetectEntitiesRequest detectEntitiesRequest =
 DetectEntitiesRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectEntitiesResponse detectEntitiesResult =
 comClient.detectEntities(detectEntitiesRequest);
            List<Entity> entList = detectEntitiesResult.entities();
            for (Entity entity : entList) {
                System.out.println("Entity text is " + entity.text());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectEntiesa Referência AWS SDK for Java 2.x da API.

Detectar frases-chave em um documento

O exemplo de código a seguir mostra como detectar frases-chave em um documento com o Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.DetectKeyPhrasesRequest;
import software.amazon.awssdk.services.comprehend.model.DetectKeyPhrasesResponse;
import software.amazon.awssdk.services.comprehend.model.KeyPhrase;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectKeyPhrases {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
```

```
                .region(region)
                .build();

        System.out.println("Calling DetectKeyPhrases");
        detectAllKeyPhrases(comClient, text);
        comClient.close();
    }

    public static void detectAllKeyPhrases(ComprehendClient comClient, String text)
 {
        try {
            DetectKeyPhrasesRequest detectKeyPhrasesRequest =
 DetectKeyPhrasesRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectKeyPhrasesResponse detectKeyPhrasesResult =
 comClient.detectKeyPhrases(detectKeyPhrasesRequest);
            List<KeyPhrase> phraseList = detectKeyPhrasesResult.keyPhrases();
            for (KeyPhrase keyPhrase : phraseList) {
                System.out.println("Key phrase text is " + keyPhrase.text());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectKeyPhrasesa Referência AWS SDK for Java 2.x da API.

Detectar elementos sintáticos de um documento

O exemplo de código a seguir mostra como detectar elementos sintáticos de um documento com o Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import software.amazon.awssdk.services.comprehend.model.DetectSyntaxRequest;
import software.amazon.awssdk.services.comprehend.model.DetectSyntaxResponse;
import software.amazon.awssdk.services.comprehend.model.SyntaxToken;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectSyntax {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectSyntax");
        detectAllSyntax(comClient, text);
        comClient.close();
    }

    public static void detectAllSyntax(ComprehendClient comClient, String text) {
        try {
```

```
            DetectSyntaxRequest detectSyntaxRequest = DetectSyntaxRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectSyntaxResponse detectSyntaxResult =
 comClient.detectSyntax(detectSyntaxRequest);
            List<SyntaxToken> syntaxTokens = detectSyntaxResult.syntaxTokens();
            for (SyntaxToken token : syntaxTokens) {
                System.out.println("Language is " + token.text());
                System.out.println("Part of speech is " +
 token.partOfSpeech().tagAsString());
            }

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectSyntaxa Referência AWS SDK for Java 2.x da API.

Detectar o idioma dominante em um documento

O exemplo de código a seguir mostra como detectar a linguagem dominante em um documento com o Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import
 software.amazon.awssdk.services.comprehend.model.DetectDominantLanguageRequest;
```

```
import
 software.amazon.awssdk.services.comprehend.model.DetectDominantLanguageResponse;
import software.amazon.awssdk.services.comprehend.model.DominantLanguage;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectLanguage {
    public static void main(String[] args) {
        // Specify French text - "It is raining today in Seattle".
        String text = "Il pleut aujourd'hui à Seattle";
        Region region = Region.US_EAST_1;

        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectDominantLanguage");
        detectTheDominantLanguage(comClient, text);
        comClient.close();
    }

    public static void detectTheDominantLanguage(ComprehendClient comClient, String
 text) {
        try {
            DetectDominantLanguageRequest request =
 DetectDominantLanguageRequest.builder()
                    .text(text)
                    .build();

            DetectDominantLanguageResponse resp =
 comClient.detectDominantLanguage(request);
            List<DominantLanguage> allLanList = resp.languages();
            for (DominantLanguage lang : allLanList) {
                System.out.println("Language is " + lang.languageCode());
            }

        } catch (ComprehendException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectDominantLanguagea Referência AWS SDK for Java 2.x da API.

Detectar o sentimento de um documento

O exemplo de código a seguir mostra como detectar o sentimento em um documento com o Amazon Comprehend.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.comprehend.ComprehendClient;
import software.amazon.awssdk.services.comprehend.model.ComprehendException;
import software.amazon.awssdk.services.comprehend.model.DetectSentimentRequest;
import software.amazon.awssdk.services.comprehend.model.DetectSentimentResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectSentiment {
    public static void main(String[] args) {
        String text = "Amazon.com, Inc. is located in Seattle, WA and was founded
 July 5th, 1994 by Jeff Bezos, allowing customers to buy everything from books to
```

```
 blenders. Seattle is north of Portland and south of Vancouver, BC. Other notable
 Seattle - based companies are Starbucks and Boeing.";
        Region region = Region.US_EAST_1;
        ComprehendClient comClient = ComprehendClient.builder()
                .region(region)
                .build();

        System.out.println("Calling DetectSentiment");
        detectSentiments(comClient, text);
        comClient.close();
    }

    public static void detectSentiments(ComprehendClient comClient, String text) {
        try {
            DetectSentimentRequest detectSentimentRequest =
 DetectSentimentRequest.builder()
                    .text(text)
                    .languageCode("en")
                    .build();

            DetectSentimentResponse detectSentimentResult =
 comClient.detectSentiment(detectSentimentRequest);
            System.out.println("The Neutral value is " +
 detectSentimentResult.sentimentScore().neutral());

        } catch (ComprehendException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectSentimenta Referência AWS SDK for Java 2.x da API.

Exemplos do DynamoDB usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, DynamoDB

O exemplo de código a seguir mostra como começar a usar o DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ListTablesRequest;
import software.amazon.awssdk.services.dynamodb.model.ListTablesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListTables {
    public static void main(String[] args) {
        System.out.println("Listing your Amazon DynamoDB tables:\n");
```

```
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
        listAllTables(ddb);
        ddb.close();
    }

    public static void listAllTables(DynamoDbClient ddb) {
        boolean moreTables = true;
        String lastName = null;

        while (moreTables) {
            try {
                ListTablesResponse response = null;
                if (lastName == null) {
                    ListTablesRequest request = ListTablesRequest.builder().build();
                    response = ddb.listTables(request);
                } else {
                    ListTablesRequest request = ListTablesRequest.builder()
                            .exclusiveStartTableName(lastName).build();
                    response = ddb.listTables(request);
                }

                List<String> tableNames = response.tableNames();
                if (tableNames.size() > 0) {
                    for (String curName : tableNames) {
                        System.out.format("* %s\n", curName);
                    }
                } else {
                    System.out.println("No tables found!");
                    System.exit(0);
                }

                lastName = response.lastEvaluatedTableName();
                if (lastName == null) {
                    moreTables = false;
                }

            } catch (DynamoDbException e) {
                System.err.println(e.getMessage());
                System.exit(1);
            }
        }
```

```
        System.out.println("\nDone!");
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeDefinition;
import software.amazon.awssdk.services.dynamodb.model.CreateTableRequest;
import software.amazon.awssdk.services.dynamodb.model.CreateTableResponse;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableRequest;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableResponse;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.KeySchemaElement;
import software.amazon.awssdk.services.dynamodb.model.KeyType;
import software.amazon.awssdk.services.dynamodb.model.ProvisionedThroughput;
import software.amazon.awssdk.services.dynamodb.model.ScalarAttributeType;
import software.amazon.awssdk.services.dynamodb.waiters.DynamoDbWaiter;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key>

                Where:
                    tableName - The Amazon DynamoDB table to create (for example,
 Music3).
                    key - The key for the Amazon DynamoDB table (for example,
 Artist).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        System.out.println("Creating an Amazon DynamoDB table " + tableName + " with
 a simple primary key: " + key);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        String result = createTable(ddb, tableName, key);
        System.out.println("New table is " + result);
        ddb.close();
    }

    public static String createTable(DynamoDbClient ddb, String tableName, String
 key) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
```

```
        CreateTableRequest request = CreateTableRequest.builder()
                .attributeDefinitions(AttributeDefinition.builder()
                        .attributeName(key)
                        .attributeType(ScalarAttributeType.S)
                        .build())
                .keySchema(KeySchemaElement.builder()
                        .attributeName(key)
                        .keyType(KeyType.HASH)
                        .build())
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .tableName(tableName)
                .build();

        String newTable;
        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
 dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            newTable = response.tableDescription().tableName();
            return newTable;

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Java 2.x da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DeleteTableRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table to delete (for example,
 Music3).

                **Warning** This program will delete the table that you specify!
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String tableName = args[0];
        System.out.format("Deleting the Amazon DynamoDB table %s...\n", tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        deleteDynamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {
        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Java 2.x da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DeleteItemRequest;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyval>

                Where:
                    tableName - The Amazon DynamoDB table to delete the item from
 (for example, Music3).
                    key - The key used in the Amazon DynamoDB table (for example,
 Artist).\s
                    keyval - The key value that represents the item to delete (for
 example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        System.out.format("Deleting item \"%s\" from %s\n", keyVal, tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
```

```
                .build();

        deleteDynamoDBItem(ddb, tableName, key, keyVal);
        ddb.close();
    }

    public static void deleteDynamoDBItem(DynamoDbClient ddb, String tableName,
 String key, String keyVal) {
        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());

        DeleteItemRequest deleteReq = DeleteItemRequest.builder()
                .tableName(tableName)
                .key(keyToGet)
                .build();

        try {
            ddb.deleteItem(deleteReq);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for Java 2.x da API.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

mostra como obter itens em lote usando o cliente de serviço.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemRequest;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemResponse;
import software.amazon.awssdk.services.dynamodb.model.KeysAndAttributes;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class BatchReadItems {
    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """;

        String tableName = "Music";
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        getBatchItems(dynamoDbClient, tableName);
    }

    public static void getBatchItems(DynamoDbClient dynamoDbClient, String
 tableName) {
        // Define the primary key values for the items you want to retrieve.
        Map<String, AttributeValue> key1 = new HashMap<>();
```

```
        key1.put("Artist", AttributeValue.builder().s("Artist1").build());

        Map<String, AttributeValue> key2 = new HashMap<>();
        key2.put("Artist", AttributeValue.builder().s("Artist2").build());

        // Construct the batchGetItem request.
        Map<String, KeysAndAttributes> requestItems = new HashMap<>();
        requestItems.put(tableName, KeysAndAttributes.builder()
            .keys(List.of(key1, key2))
            .projectionExpression("Artist, SongTitle")
            .build());

        BatchGetItemRequest batchGetItemRequest = BatchGetItemRequest.builder()
            .requestItems(requestItems)
            .build();

        // Make the batchGetItem request.
        BatchGetItemResponse batchGetItemResponse =
 dynamoDbClient.batchGetItem(batchGetItemRequest);

        // Extract and print the retrieved items.
        Map<String, List<Map<String, AttributeValue>>> responses =
 batchGetItemResponse.responses();
        if (responses.containsKey(tableName)) {
            List<Map<String, AttributeValue>> musicItems = responses.get(tableName);
            for (Map<String, AttributeValue> item : musicItems) {
                System.out.println("Artist: " + item.get("Artist").s() +
                    ", SongTitle: " + item.get("SongTitle").s());
            }
        } else {
            System.out.println("No items retrieved.");
        }
    }
}
```

mostra como obter itens em lote usando o cliente de serviço e um paginador.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchGetItemRequest;
import software.amazon.awssdk.services.dynamodb.model.KeysAndAttributes;
```

```
import java.util.Collections;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

public class BatchGetItemsPaginator {

    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """;

        String tableName = "Music";
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        getBatchItemsPaginator(dynamoDbClient, tableName) ;
    }

    public static void getBatchItemsPaginator(DynamoDbClient dynamoDbClient, String
 tableName) {
        // Define the primary key values for the items you want to retrieve.
        Map<String, AttributeValue> key1 = new HashMap<>();
        key1.put("Artist", AttributeValue.builder().s("Artist1").build());

        Map<String, AttributeValue> key2 = new HashMap<>();
        key2.put("Artist", AttributeValue.builder().s("Artist2").build());

        // Construct the batchGetItem request.
        Map<String, KeysAndAttributes> requestItems = new HashMap<>();
        requestItems.put(tableName, KeysAndAttributes.builder()
            .keys(List.of(key1, key2))
            .projectionExpression("Artist, SongTitle")
            .build());

        BatchGetItemRequest batchGetItemRequest = BatchGetItemRequest.builder()
            .requestItems(requestItems)
```

```
            .build();

        // Use batchGetItemPaginator for paginated requests.
        dynamoDbClient.batchGetItemPaginator(batchGetItemRequest).stream()
            .flatMap(response -> response.responses().getOrDefault(tableName,
 Collections.emptyList()).stream())
            .forEach(item -> {
                System.out.println("Artist: " + item.get("Artist").s() +
                    ", SongTitle: " + item.get("SongTitle").s());
            });
    }
}
```

- Para obter detalhes da API, consulte BatchGetItema Referência AWS SDK for Java 2.x da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtém um item de uma tabela usando DynamoDbClient o.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.GetItemRequest;
import java.util.HashMap;
import java.util.Map;
import java.util.Set;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To get an item from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client, see the EnhancedGetItem example.
 */
public class GetItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyVal>

                Where:
                    tableName - The Amazon DynamoDB table from which an item is
 retrieved (for example, Music3).\s
                    key - The key used in the Amazon DynamoDB table (for example,
 Artist).\s
                    keyval - The key value that represents the item to get (for
 example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        System.out.format("Retrieving item \"%s\" from \"%s\"\n", keyVal,
 tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        getDynamoDBItem(ddb, tableName, key, keyVal);
        ddb.close();
    }
```

```
    public static void getDynamoDBItem(DynamoDbClient ddb, String tableName, String
 key, String keyVal) {
        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());

        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName(tableName)
                .build();

        try {
            // If there is no matching item, GetItem does not return any data.
            Map<String, AttributeValue> returnedItem = ddb.getItem(request).item();
            if (returnedItem.isEmpty())
                System.out.format("No item found with the key %s!\n", key);
            else {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");
                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
 returnedItem.get(key1).toString());
                }
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Java 2.x da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeDefinition;
import software.amazon.awssdk.services.dynamodb.model.DescribeTableRequest;
import
 software.amazon.awssdk.services.dynamodb.model.ProvisionedThroughputDescription;
import software.amazon.awssdk.services.dynamodb.model.TableDescription;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeTable {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table to get information about
 (for example, Music3).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String tableName = args[0];
        System.out.format("Getting description for %s\n\n", tableName);
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        describeDymamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void describeDymamoDBTable(DynamoDbClient ddb, String tableName) {
        DescribeTableRequest request = DescribeTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            TableDescription tableInfo = ddb.describeTable(request).table();
            if (tableInfo != null) {
                System.out.format("Table name  : %s\n", tableInfo.tableName());
                System.out.format("Table ARN   : %s\n", tableInfo.tableArn());
                System.out.format("Status      : %s\n", tableInfo.tableStatus());
                System.out.format("Item count  : %d\n", tableInfo.itemCount());
                System.out.format("Size (bytes): %d\n", tableInfo.tableSizeBytes());

                ProvisionedThroughputDescription throughputInfo =
tableInfo.provisionedThroughput();
                System.out.println("Throughput");
                System.out.format("  Read Capacity : %d\n",
throughputInfo.readCapacityUnits());
                System.out.format("  Write Capacity: %d\n",
throughputInfo.writeCapacityUnits());

                List<AttributeDefinition> attributes =
tableInfo.attributeDefinitions();
                System.out.println("Attributes");
                for (AttributeDefinition a : attributes) {
                    System.out.format("  %s (%s)\n", a.attributeName(),
a.attributeType());
                }
            }

        } catch (DynamoDbException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("\nDone!");
    }
}
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Java 2.x da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ListTablesRequest;
import software.amazon.awssdk.services.dynamodb.model.ListTablesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListTables {
    public static void main(String[] args) {
        System.out.println("Listing your Amazon DynamoDB tables:\n");
        Region region = Region.US_EAST_1;
```

```
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();
        listAllTables(ddb);
        ddb.close();
    }

    public static void listAllTables(DynamoDbClient ddb) {
        boolean moreTables = true;
        String lastName = null;

        while (moreTables) {
            try {
                ListTablesResponse response = null;
                if (lastName == null) {
                    ListTablesRequest request = ListTablesRequest.builder().build();
                    response = ddb.listTables(request);
                } else {
                    ListTablesRequest request = ListTablesRequest.builder()
                            .exclusiveStartTableName(lastName).build();
                    response = ddb.listTables(request);
                }

                List<String> tableNames = response.tableNames();
                if (tableNames.size() > 0) {
                    for (String curName : tableNames) {
                        System.out.format("* %s\n", curName);
                    }
                } else {
                    System.out.println("No tables found!");
                    System.exit(0);
                }

                lastName = response.lastEvaluatedTableName();
                if (lastName == null) {
                    moreTables = false;
                }

            } catch (DynamoDbException e) {
                System.err.println(e.getMessage());
                System.exit(1);
            }
        }
        System.out.println("\nDone!");
```

```
    }
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Coloca um item em uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.PutItemRequest;
import software.amazon.awssdk.services.dynamodb.model.PutItemResponse;
import software.amazon.awssdk.services.dynamodb.model.ResourceNotFoundException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To place items into an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client. See the EnhancedPutItem example.
 */
public class PutItem {
```

```
   public static void main(String[] args) {
       final String usage = """

               Usage:
                   <tableName> <key> <keyVal> <albumtitle> <albumtitleval> <awards>
<awardsval> <Songtitle> <songtitleval>

               Where:
                   tableName - The Amazon DynamoDB table in which an item is placed
(for example, Music3).
                   key - The key used in the Amazon DynamoDB table (for example,
Artist).
                   keyval - The key value that represents the item to get (for
example, Famous Band).
                   albumTitle - The Album title (for example, AlbumTitle).
                   AlbumTitleValue - The name of the album (for example, Songs
About Life ).
                   Awards - The awards column (for example, Awards).
                   AwardVal - The value of the awards (for example, 10).
                   SongTitle - The song title (for example, SongTitle).
                   SongTitleVal - The value of the song title (for example, Happy
Day).
               **Warning** This program will  place an item that you specify into a
table!
               """;

       if (args.length != 9) {
           System.out.println(usage);
           System.exit(1);
       }

       String tableName = args[0];
       String key = args[1];
       String keyVal = args[2];
       String albumTitle = args[3];
       String albumTitleValue = args[4];
       String awards = args[5];
       String awardVal = args[6];
       String songTitle = args[7];
       String songTitleVal = args[8];

       Region region = Region.US_EAST_1;
       DynamoDbClient ddb = DynamoDbClient.builder()
               .region(region)
```

```
                .build();

        putItemInTable(ddb, tableName, key, keyVal, albumTitle, albumTitleValue,
awards, awardVal, songTitle,
                songTitleVal);
        System.out.println("Done!");
        ddb.close();
    }

    public static void putItemInTable(DynamoDbClient ddb,
            String tableName,
            String key,
            String keyVal,
            String albumTitle,
            String albumTitleValue,
            String awards,
            String awardVal,
            String songTitle,
            String songTitleVal) {

        HashMap<String, AttributeValue> itemValues = new HashMap<>();
        itemValues.put(key, AttributeValue.builder().s(keyVal).build());
        itemValues.put(songTitle, AttributeValue.builder().s(songTitleVal).build());
        itemValues.put(albumTitle,
AttributeValue.builder().s(albumTitleValue).build());
        itemValues.put(awards, AttributeValue.builder().s(awardVal).build());

        PutItemRequest request = PutItemRequest.builder()
                .tableName(tableName)
                .item(itemValues)
                .build();

        try {
            PutItemResponse response = ddb.putItem(request);
            System.out.println(tableName + " was successfully updated. The request
id is "
                    + response.responseMetadata().requestId());

        } catch (ResourceNotFoundException e) {
            System.err.format("Error: The Amazon DynamoDB table \"%s\" can't be
found.\n", tableName);
            System.err.println("Be sure that it exists and that you've typed its
name correctly!");
            System.exit(1);
```

```
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for Java 2.x da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Consulta uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.QueryRequest;
import software.amazon.awssdk.services.dynamodb.model.QueryResponse;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To query items from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
```

```
 * Enhanced Client. See the EnhancedQueryRecords example.
 */
public class Query {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <partitionKeyName> <partitionKeyVal>

                Where:
                    tableName - The Amazon DynamoDB table to put the item in (for
 example, Music3).
                    partitionKeyName - The partition key name of the Amazon DynamoDB
 table (for example, Artist).
                    partitionKeyVal - The value of the partition key that should
 match (for example, Famous Band).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String partitionKeyName = args[1];
        String partitionKeyVal = args[2];

        // For more information about an alias, see:
        // https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
Expressions.ExpressionAttributeNames.html
        String partitionAlias = "#a";

        System.out.format("Querying %s", tableName);
        System.out.println("");
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        int count = queryTable(ddb, tableName, partitionKeyName, partitionKeyVal,
 partitionAlias);
        System.out.println("There were " + count + "  record(s) returned");
        ddb.close();
    }
```

```
    public static int queryTable(DynamoDbClient ddb, String tableName, String
 partitionKeyName, String partitionKeyVal,
            String partitionAlias) {
        // Set up an alias for the partition key name in case it's a reserved word.
        HashMap<String, String> attrNameAlias = new HashMap<String, String>();
        attrNameAlias.put(partitionAlias, partitionKeyName);

        // Set up mapping of the partition name with the value.
        HashMap<String, AttributeValue> attrValues = new HashMap<>();
        attrValues.put(":" + partitionKeyName, AttributeValue.builder()
                .s(partitionKeyVal)
                .build());

        QueryRequest queryReq = QueryRequest.builder()
                .tableName(tableName)
                .keyConditionExpression(partitionAlias + " = :" + partitionKeyName)
                .expressionAttributeNames(attrNameAlias)
                .expressionAttributeValues(attrValues)
                .build();

        try {
            QueryResponse response = ddb.query(queryReq);
            return response.count();

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return -1;
    }
}
```

Consulta uma tabela usando o `DynamoDbClient` e um índice secundário.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.QueryRequest;
import software.amazon.awssdk.services.dynamodb.model.QueryResponse;
import java.util.HashMap;
```

```
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * Create the Movies table by running the Scenario example and loading the Movie
 * data from the JSON file. Next create a secondary
 * index for the Movies table that uses only the year column. Name the index
 * **year-index**. For more information, see:
 *
 * https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GSI.html
 */
public class QueryItemsUsingIndex {
    public static void main(String[] args) {
        String tableName = "Movies";
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        queryIndex(ddb, tableName);
        ddb.close();
    }

    public static void queryIndex(DynamoDbClient ddb, String tableName) {
        try {
            Map<String, String> expressionAttributesNames = new HashMap<>();
            expressionAttributesNames.put("#year", "year");
            Map<String, AttributeValue> expressionAttributeValues = new HashMap<>();
            expressionAttributeValues.put(":yearValue",
 AttributeValue.builder().n("2013").build());

            QueryRequest request = QueryRequest.builder()
                    .tableName(tableName)
                    .indexName("year-index")
                    .keyConditionExpression("#year = :yearValue")
                    .expressionAttributeNames(expressionAttributesNames)
                    .expressionAttributeValues(expressionAttributeValues)
                    .build();
```

```
            System.out.println("=== Movie Titles ===");
            QueryResponse response = ddb.query(request);
            response.items()
                    .forEach(movie -> System.out.println(movie.get("title").s()));

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Java 2.x.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Escaneia uma tabela do Amazon DynamoDB DynamoDbClientusando.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.ScanRequest;
import software.amazon.awssdk.services.dynamodb.model.ScanResponse;
import java.util.Map;
import java.util.Set;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To scan items from an Amazon DynamoDB table using the AWS SDK for Java V2,
 * its better practice to use the
 * Enhanced Client, See the EnhancedScanRecords example.
 */

public class DynamoDBScanItems {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <tableName>

                Where:
                    tableName - The Amazon DynamoDB table to get information from
 (for example, Music3).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        scanItems(ddb, tableName);
        ddb.close();
    }

    public static void scanItems(DynamoDbClient ddb, String tableName) {
        try {
            ScanRequest scanRequest = ScanRequest.builder()
                    .tableName(tableName)
                    .build();
```

```
            ScanResponse response = ddb.scan(scanRequest);
            for (Map<String, AttributeValue> item : response.items()) {
                Set<String> keys = item.keySet();
                for (String key : keys) {
                    System.out.println("The key name is " + key + "\n");
                    System.out.println("The value is " + item.get(key).s());
                }
            }

        } catch (DynamoDbException e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Java 2.x.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualiza um item em uma tabela usando DynamoDbClient.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.AttributeAction;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.AttributeValueUpdate;
import software.amazon.awssdk.services.dynamodb.model.UpdateItemRequest;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import java.util.HashMap;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To update an Amazon DynamoDB table using the AWS SDK for Java V2, its better
 * practice to use the
 * Enhanced Client, See the EnhancedModifyItem example.
 */
public class UpdateItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <tableName> <key> <keyVal> <name> <updateVal>

                Where:
                    tableName - The Amazon DynamoDB table (for example, Music3).
                    key - The name of the key in the table (for example, Artist).
                    keyVal - The value of the key (for example, Famous Band).
                    name - The name of the column where the value is updated (for
 example, Awards).
                    updateVal - The value used to update an item (for example, 14).
                 Example:
                    UpdateItem Music3 Artist Famous Band Awards 14
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = args[0];
        String key = args[1];
        String keyVal = args[2];
        String name = args[3];
        String updateVal = args[4];

        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
```

```
                .build();
        updateTableItem(ddb, tableName, key, keyVal, name, updateVal);
        ddb.close();
    }

    public static void updateTableItem(DynamoDbClient ddb,
            String tableName,
            String key,
            String keyVal,
            String name,
            String updateVal) {

        HashMap<String, AttributeValue> itemKey = new HashMap<>();
        itemKey.put(key, AttributeValue.builder()
                .s(keyVal)
                .build());

        HashMap<String, AttributeValueUpdate> updatedValues = new HashMap<>();
        updatedValues.put(name, AttributeValueUpdate.builder()
                .value(AttributeValue.builder().s(updateVal).build())
                .action(AttributeAction.PUT)
                .build());

        UpdateItemRequest request = UpdateItemRequest.builder()
                .tableName(tableName)
                .key(itemKey)
                .attributeUpdates(updatedValues)
                .build();

        try {
            ddb.updateItem(request);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("The Amazon DynamoDB table was updated!");
    }
}
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Java 2.x da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Insere muitos itens em uma tabela usando o cliente de serviço.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;
import software.amazon.awssdk.services.dynamodb.model.BatchWriteItemRequest;
import software.amazon.awssdk.services.dynamodb.model.BatchWriteItemResponse;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import software.amazon.awssdk.services.dynamodb.model.PutRequest;
import software.amazon.awssdk.services.dynamodb.model.WriteRequest;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class BatchWriteItems {
    public static void main(String[] args){
        final String usage = """

                Usage:
                    <tableName>

                Where:
```

```
                    tableName - The Amazon DynamoDB table (for example, Music).\s
                """";

        String tableName = "Music";
        Region region = Region.US_EAST_1;
        DynamoDbClient dynamoDbClient = DynamoDbClient.builder()
            .region(region)
            .build();

        addBatchItems(dynamoDbClient, tableName);
    }

    public static void addBatchItems(DynamoDbClient dynamoDbClient, String
 tableName) {
        // Specify the updates you want to perform.
        List<WriteRequest> writeRequests = new ArrayList<>();

        // Set item 1.
        Map<String, AttributeValue> item1Attributes = new HashMap<>();
        item1Attributes.put("Artist",
 AttributeValue.builder().s("Artist1").build());
        item1Attributes.put("Rating", AttributeValue.builder().s("5").build());
        item1Attributes.put("Comments", AttributeValue.builder().s("Great
 song!").build());
        item1Attributes.put("SongTitle",
 AttributeValue.builder().s("SongTitle1").build());

 writeRequests.add(WriteRequest.builder().putRequest(PutRequest.builder().item(item1Attribut

        // Set item 2.
        Map<String, AttributeValue> item2Attributes = new HashMap<>();
        item2Attributes.put("Artist",
 AttributeValue.builder().s("Artist2").build());
        item2Attributes.put("Rating", AttributeValue.builder().s("4").build());
        item2Attributes.put("Comments", AttributeValue.builder().s("Nice
 melody.").build());
        item2Attributes.put("SongTitle",
 AttributeValue.builder().s("SongTitle2").build());

 writeRequests.add(WriteRequest.builder().putRequest(PutRequest.builder().item(item2Attribut

        try {
            // Create the BatchWriteItemRequest.
```

```
            BatchWriteItemRequest batchWriteItemRequest =
 BatchWriteItemRequest.builder()
                .requestItems(Map.of(tableName, writeRequests))
                .build();

            // Execute the BatchWriteItem operation.
            BatchWriteItemResponse batchWriteItemResponse =
 dynamoDbClient.batchWriteItem(batchWriteItemRequest);

            // Process the response.
            System.out.println("Batch write successful: " + batchWriteItemResponse);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Insira vários itens em uma tabela usando o cliente aprimorado.

```
import com.example.dynamodb.Customer;
import com.example.dynamodb.Music;
import software.amazon.awssdk.enhanced.dynamodb.DynamoDbEnhancedClient;
import software.amazon.awssdk.enhanced.dynamodb.DynamoDbTable;
import software.amazon.awssdk.enhanced.dynamodb.Key;
import software.amazon.awssdk.enhanced.dynamodb.TableSchema;
import software.amazon.awssdk.enhanced.dynamodb.model.BatchWriteItemEnhancedRequest;
import software.amazon.awssdk.enhanced.dynamodb.model.WriteBatch;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.dynamodb.DynamoDbClient;
import software.amazon.awssdk.services.dynamodb.model.DynamoDbException;
import java.time.Instant;
import java.time.LocalDate;
import java.time.LocalDateTime;
import java.time.ZoneOffset;

/*
 * Before running this code example, create an Amazon DynamoDB table named Customer
 with these columns:
 *   - id - the id of the record that is the key
 *   - custName - the customer name
```

```
 *   - email - the email value
 *   - registrationDate - an instant value when the item was added to the table
 *
 * Also, ensure that you have set up your development environment, including your
 credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class EnhancedBatchWriteItems {
        public static void main(String[] args) {
                Region region = Region.US_EAST_1;
                DynamoDbClient ddb = DynamoDbClient.builder()
                                .region(region)
                                .build();
                DynamoDbEnhancedClient enhancedClient =
 DynamoDbEnhancedClient.builder()
                                .dynamoDbClient(ddb)
                                .build();
                putBatchRecords(enhancedClient);
                ddb.close();
        }

        public static void putBatchRecords(DynamoDbEnhancedClient enhancedClient) {
                try {
                        DynamoDbTable<Customer> customerMappedTable =
 enhancedClient.table("Customer",
                                        TableSchema.fromBean(Customer.class));
                        DynamoDbTable<Music> musicMappedTable =
 enhancedClient.table("Music",
                                        TableSchema.fromBean(Music.class));
                        LocalDate localDate = LocalDate.parse("2020-04-07");
                        LocalDateTime localDateTime = localDate.atStartOfDay();
                        Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

                        Customer record2 = new Customer();
                        record2.setCustName("Fred Pink");
                        record2.setId("id110");
                        record2.setEmail("fredp@noserver.com");
                        record2.setRegistrationDate(instant);

                        Customer record3 = new Customer();
                        record3.setCustName("Susan Pink");
```

```
                        record3.setId("id120");
                        record3.setEmail("spink@noserver.com");
                        record3.setRegistrationDate(instant);

                        Customer record4 = new Customer();
                        record4.setCustName("Jerry orange");
                        record4.setId("id101");
                        record4.setEmail("jorange@noserver.com");
                        record4.setRegistrationDate(instant);

                        BatchWriteItemEnhancedRequest batchWriteItemEnhancedRequest
= BatchWriteItemEnhancedRequest
                                        .builder()
                                        .writeBatches(

WriteBatch.builder(Customer.class) // add items to the Customer

      // table

.mappedTableResource(customerMappedTable)

.addPutItem(builder -> builder.item(record2))

.addPutItem(builder -> builder.item(record3))

.addPutItem(builder -> builder.item(record4))
                                                                        .build(),

WriteBatch.builder(Music.class) // delete an item from the Music

   // table

.mappedTableResource(musicMappedTable)

.addDeleteItem(builder -> builder.key(

   Key.builder().partitionValue(

                    "Famous Band")

                    .build()))
                                                                        .build())
                                        .build();
```

```
                        // Add three items to the Customer table and delete one item
 from the Music
                        // table.

 enhancedClient.batchWriteItem(batchWriteItemEnhancedRequest);
                        System.out.println("done");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for Java 2.x da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela do DynamoDB.

```
    // Create a table with a Sort key.
    public static void createTable(DynamoDbClient ddb, String tableName) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("year")
                .attributeType("N")
                .build());

        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("title")
                .attributeType("S")
                .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
                .attributeName("year")
                .keyType(KeyType.HASH)
                .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
                .attributeName("title")
                .keyType(KeyType.RANGE)
                .build();

        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
```

```
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(ddb)
                .build();

        DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        while (iter.hasNext()) {
            // Only add 200 Movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
```

```
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            Movies movies = new Movies();
            movies.setYear(year);
            movies.setTitle(title);
            movies.setInfo(info);

            // Put the data into the Amazon DynamoDB Movie table.
            mappedTable.putItem(movies);
            t++;
        }
    }
```

Obtenha um item de uma tabela.

```
    public static void getItem(DynamoDbClient ddb) {

        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put("year", AttributeValue.builder()
                .n("1933")
                .build());

        keyToGet.put("title", AttributeValue.builder()
                .s("King Kong")
                .build());

        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName("Movies")
                .build();

        try {
            Map<String, AttributeValue> returnedItem = ddb.getItem(request).item();

            if (returnedItem != null) {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");

                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
returnedItem.get(key1).toString());
```

```
                }
            } else {
                System.out.format("No item found with the key %s!\n", "year");
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

Exemplo completo.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java example performs these tasks:
 *
 * 1. Creates the Amazon DynamoDB Movie table with partition and sort key.
 * 2. Puts data into the Amazon DynamoDB table from a JSON document using the
 * Enhanced client.
 * 3. Gets data from the Movie table.
 * 4. Adds a new item.
 * 5. Updates an item.
 * 6. Uses a Scan to query items using the Enhanced client.
 * 7. Queries all items where the year is 2013 using the Enhanced Client.
 * 8. Deletes the table.
 */

public class Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <fileName>
```

```
                Where:
                    fileName - The path to the moviedata.json file that you can
download from the Amazon DynamoDB Developer Guide.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = "Movies";
        String fileName = args[0];
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon DynamoDB example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "1. Creating an Amazon DynamoDB table named Movies with a key named
year and a sort key named title.");
        createTable(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Loading data into the Amazon DynamoDB table.");
        loadData(ddb, tableName, fileName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Getting data from the Movie table.");
        getItem(ddb);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Putting a record into the Amazon DynamoDB table.");
        putRecord(ddb);
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("5. Updating a record.");
        updateTableItem(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Scanning the Amazon DynamoDB table.");
        scanMovies(ddb, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Querying the Movies released in 2013.");
        queryTable(ddb);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
        System.out.println(DASHES);

        ddb.close();
    }

    // Create a table with a Sort key.
    public static void createTable(DynamoDbClient ddb, String tableName) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("year")
                .attributeType("N")
                .build());

        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("title")
                .attributeType("S")
                .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
                .attributeName("year")
                .keyType(KeyType.HASH)
                .build();
```

```
        KeySchemaElement key2 = KeySchemaElement.builder()
                .attributeName("title")
                .keyType(KeyType.RANGE)
                .build();

        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(10L)
                        .writeCapacityUnits(10L)
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Query the table.
    public static void queryTable(DynamoDbClient ddb) {
        try {
            DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
```

```
                    .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            QueryConditional queryConditional = QueryConditional
                    .keyEqualTo(Key.builder()
                            .partitionValue(2013)
                            .build());

            // Get items in the table and write out the ID value.
            Iterator<Movies> results =
custTable.query(queryConditional).items().iterator();
            String result = "";

            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The title of the movie is " + rec.getTitle());
                System.out.println("The movie information  is " + rec.getInfo());
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Scan the table.
    public static void scanMovies(DynamoDbClient ddb, String tableName) {
        System.out.println("******* Scanning all movies.\n");
        try {
            DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
                    .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            Iterator<Movies> results = custTable.scan().items().iterator();
            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The movie title is " + rec.getTitle());
                System.out.println("The movie year is " + rec.getYear());
            }

        } catch (DynamoDbException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(ddb)
                .build();

        DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        while (iter.hasNext()) {
            // Only add 200 Movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            Movies movies = new Movies();
            movies.setYear(year);
            movies.setTitle(title);
            movies.setInfo(info);

            // Put the data into the Amazon DynamoDB Movie table.
            mappedTable.putItem(movies);
            t++;
        }
    }

    // Update the record to include show only directors.
    public static void updateTableItem(DynamoDbClient ddb, String tableName) {
        HashMap<String, AttributeValue> itemKey = new HashMap<>();
```

```
        itemKey.put("year", AttributeValue.builder().n("1933").build());
        itemKey.put("title", AttributeValue.builder().s("King Kong").build());

        HashMap<String, AttributeValueUpdate> updatedValues = new HashMap<>();
        updatedValues.put("info", AttributeValueUpdate.builder()
                .value(AttributeValue.builder().s("{\"directors\":[\"Merian C.
Cooper\",\"Ernest B. Schoedsack\"]")
                        .build())
                .action(AttributeAction.PUT)
                .build());

        UpdateItemRequest request = UpdateItemRequest.builder()
                .tableName(tableName)
                .key(itemKey)
                .attributeUpdates(updatedValues)
                .build();

        try {
            ddb.updateItem(request);
        } catch (ResourceNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }

        System.out.println("Item was updated!");
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {
        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }
```

```
    public static void putRecord(DynamoDbClient ddb) {
        try {
            DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                    .dynamoDbClient(ddb)
                    .build();

            DynamoDbTable<Movies> table = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));

            // Populate the Table.
            Movies record = new Movies();
            record.setYear(2020);
            record.setTitle("My Movie2");
            record.setInfo("no info");
            table.putItem(record);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("Added a new movie to the table.");
    }

    public static void getItem(DynamoDbClient ddb) {

        HashMap<String, AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put("year", AttributeValue.builder()
                .n("1933")
                .build());

        keyToGet.put("title", AttributeValue.builder()
                .s("King Kong")
                .build());

        GetItemRequest request = GetItemRequest.builder()
                .key(keyToGet)
                .tableName("Movies")
                .build();

        try {
            Map<String, AttributeValue> returnedItem = ddb.getItem(request).item();

            if (returnedItem != null) {
```

```
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");

                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
 returnedItem.get(key1).toString());
                }
            } else {
                System.out.format("No item found with the key %s!\n", "year");
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.

- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ScenarioPartiQLBatch {
        public static void main(String[] args) throws IOException {
                String tableName = "MoviesPartiQBatch";
                Region region = Region.US_EAST_1;
                DynamoDbClient ddb = DynamoDbClient.builder()
                                .region(region)
                                .build();

                System.out.println("******* Creating an Amazon DynamoDB table named
 " + tableName
                                + " with a key named year and a sort key named
 title.");
                createTable(ddb, tableName);

                System.out.println("******* Adding multiple records into the " +
 tableName
                                + " table using a batch command.");
                putRecordBatch(ddb);

                System.out.println("******* Updating multiple records using a batch
 command.");
                updateTableItemBatch(ddb);

                System.out.println("******* Deleting multiple records using a batch
 command.");
                deleteItemBatch(ddb);

                System.out.println("******* Deleting the Amazon DynamoDB table.");
                deleteDynamoDBTable(ddb, tableName);
                ddb.close();
```

```
        }

        public static void createTable(DynamoDbClient ddb, String tableName) {
                DynamoDbWaiter dbWaiter = ddb.waiter();
                ArrayList<AttributeDefinition> attributeDefinitions = new
ArrayList<>();

                // Define attributes.
                attributeDefinitions.add(AttributeDefinition.builder()
                                .attributeName("year")
                                .attributeType("N")
                                .build());

                attributeDefinitions.add(AttributeDefinition.builder()
                                .attributeName("title")
                                .attributeType("S")
                                .build());

                ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
                KeySchemaElement key = KeySchemaElement.builder()
                                .attributeName("year")
                                .keyType(KeyType.HASH)
                                .build();

                KeySchemaElement key2 = KeySchemaElement.builder()
                                .attributeName("title")
                                .keyType(KeyType.RANGE) // Sort
                                .build();

                // Add KeySchemaElement objects to the list.
                tableKey.add(key);
                tableKey.add(key2);

                CreateTableRequest request = CreateTableRequest.builder()
                                .keySchema(tableKey)

.provisionedThroughput(ProvisionedThroughput.builder()
                                                .readCapacityUnits(new Long(10))
                                                .writeCapacityUnits(new Long(10))
                                                .build())
                                .attributeDefinitions(attributeDefinitions)
                                .tableName(tableName)
                                .build();
```

```
                try {
                        CreateTableResponse response = ddb.createTable(request);
                        DescribeTableRequest tableRequest =
DescribeTableRequest.builder()
                                        .tableName(tableName)
                                        .build();

                        // Wait until the Amazon DynamoDB table is created.
                        WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter
                                        .waitUntilTableExists(tableRequest);

waiterResponse.matched().response().ifPresent(System.out::println);
                        String newTable = response.tableDescription().tableName();
                        System.out.println("The " + newTable + " was successfully
created.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void putRecordBatch(DynamoDbClient ddb) {
                String sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE
{'year':?, 'title' : ?, 'info' : ?}";
                try {
                        // Create three movies to add to the Amazon DynamoDB table.
                        // Set data for Movie 1.
                        List<AttributeValue> parameters = new ArrayList<>();

                        AttributeValue att1 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue att2 = AttributeValue.builder()
                                        .s("My Movie 1")
                                        .build();

                        AttributeValue att3 = AttributeValue.builder()
                                        .s("No Information")
                                        .build();

                        parameters.add(att1);
```

```
                        parameters.add(att2);
                        parameters.add(att3);

                        BatchStatementRequest statementRequestMovie1 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parameters)
                                        .build();

                        // Set data for Movie 2.
                        List<AttributeValue> parametersMovie2 = new ArrayList<>();
                        AttributeValue attMovie2 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue attMovie2A = AttributeValue.builder()
                                        .s("My Movie 2")
                                        .build();

                        AttributeValue attMovie2B = AttributeValue.builder()
                                        .s("No Information")
                                        .build();

                        parametersMovie2.add(attMovie2);
                        parametersMovie2.add(attMovie2A);
                        parametersMovie2.add(attMovie2B);

                        BatchStatementRequest statementRequestMovie2 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parametersMovie2)
                                        .build();

                        // Set data for Movie 3.
                        List<AttributeValue> parametersMovie3 = new ArrayList<>();
                        AttributeValue attMovie3 = AttributeValue.builder()
                                        .n(String.valueOf("2022"))
                                        .build();

                        AttributeValue attMovie3A = AttributeValue.builder()
                                        .s("My Movie 3")
                                        .build();

                        AttributeValue attMovie3B = AttributeValue.builder()
```

```
                                        .s("No Information")
                                        .build();

                        parametersMovie3.add(attMovie3);
                        parametersMovie3.add(attMovie3A);
                        parametersMovie3.add(attMovie3B);

                        BatchStatementRequest statementRequestMovie3 =
BatchStatementRequest.builder()
                                        .statement(sqlStatement)
                                        .parameters(parametersMovie3)
                                        .build();

                        // Add all three movies to the list.
                        List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                        myBatchStatementList.add(statementRequestMovie1);
                        myBatchStatementList.add(statementRequestMovie2);
                        myBatchStatementList.add(statementRequestMovie3);

                        BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                        .statements(myBatchStatementList)
                                        .build();

                        BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
                        System.out.println("ExecuteStatement successful: " +
response.toString());
                        System.out.println("Added new movies using a batch
command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void updateTableItemBatch(DynamoDbClient ddb) {
                String sqlStatement = "UPDATE MoviesPartiQBatch SET info =
'directors\":[\"Merian C. Cooper\",\"Ernest B. Schoedsack' where year=? and
title=?";
                List<AttributeValue> parametersRec1 = new ArrayList<>();
```

```
                // Update three records.
                AttributeValue att1 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue att2 = AttributeValue.builder()
                                .s("My Movie 1")
                                .build();

                parametersRec1.add(att1);
                parametersRec1.add(att2);

                BatchStatementRequest statementRequestRec1 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec1)
                                .build();

                // Update record 2.
                List<AttributeValue> parametersRec2 = new ArrayList<>();
                AttributeValue attRec2 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec2a = AttributeValue.builder()
                                .s("My Movie 2")
                                .build();

                parametersRec2.add(attRec2);
                parametersRec2.add(attRec2a);
                BatchStatementRequest statementRequestRec2 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec2)
                                .build();

                // Update record 3.
                List<AttributeValue> parametersRec3 = new ArrayList<>();
                AttributeValue attRec3 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec3a = AttributeValue.builder()
                                .s("My Movie 3")
```

```
                                .build();

                parametersRec3.add(attRec3);
                parametersRec3.add(attRec3a);
                BatchStatementRequest statementRequestRec3 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec3)
                                .build();

                // Add all three movies to the list.
                List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                myBatchStatementList.add(statementRequestRec1);
                myBatchStatementList.add(statementRequestRec2);
                myBatchStatementList.add(statementRequestRec3);

                BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                .statements(myBatchStatementList)
                                .build();

                try {
                        BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
                        System.out.println("ExecuteStatement successful: " +
response.toString());
                        System.out.println("Updated three movies using a batch
command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
                System.out.println("Item was updated!");
        }

        public static void deleteItemBatch(DynamoDbClient ddb) {
                String sqlStatement = "DELETE FROM MoviesPartiQBatch WHERE year = ?
and title=?";
                List<AttributeValue> parametersRec1 = new ArrayList<>();

                // Specify three records to delete.
                AttributeValue att1 = AttributeValue.builder()
```

```
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue att2 = AttributeValue.builder()
                                .s("My Movie 1")
                                .build();

                parametersRec1.add(att1);
                parametersRec1.add(att2);

                BatchStatementRequest statementRequestRec1 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec1)
                                .build();

                // Specify record 2.
                List<AttributeValue> parametersRec2 = new ArrayList<>();
                AttributeValue attRec2 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec2a = AttributeValue.builder()
                                .s("My Movie 2")
                                .build();

                parametersRec2.add(attRec2);
                parametersRec2.add(attRec2a);
                BatchStatementRequest statementRequestRec2 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec2)
                                .build();

                // Specify record 3.
                List<AttributeValue> parametersRec3 = new ArrayList<>();
                AttributeValue attRec3 = AttributeValue.builder()
                                .n(String.valueOf("2022"))
                                .build();

                AttributeValue attRec3a = AttributeValue.builder()
                                .s("My Movie 3")
                                .build();
```

```
                parametersRec3.add(attRec3);
                parametersRec3.add(attRec3a);

                BatchStatementRequest statementRequestRec3 =
BatchStatementRequest.builder()
                                .statement(sqlStatement)
                                .parameters(parametersRec3)
                                .build();

                // Add all three movies to the list.
                List<BatchStatementRequest> myBatchStatementList = new
ArrayList<>();
                myBatchStatementList.add(statementRequestRec1);
                myBatchStatementList.add(statementRequestRec2);
                myBatchStatementList.add(statementRequestRec3);

                BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
                                .statements(myBatchStatementList)
                                .build();

                try {
                        ddb.batchExecuteStatement(batchRequest);
                        System.out.println("Deleted three movies using a batch
command.");

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
                }
        }

        public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName)
{
                DeleteTableRequest request = DeleteTableRequest.builder()
                                .tableName(tableName)
                                .build();

                try {
                        ddb.deleteTable(request);

                } catch (DynamoDbException e) {
                        System.err.println(e.getMessage());
                        System.exit(1);
```

```
                }
                System.out.println(tableName + " was successfully deleted!");
        }

        private static ExecuteStatementResponse
 executeStatementRequest(DynamoDbClient ddb, String statement,
                        List<AttributeValue> parameters) {
                ExecuteStatementRequest request = ExecuteStatementRequest.builder()
                                .statement(statement)
                                .parameters(parameters)
                                .build();

                return ddb.executeStatement(request);
        }
}
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Java 2.x da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ScenarioPartiQ {
    public static void main(String[] args) throws IOException {
```

```
        final String usage = """

                Usage:
                    <fileName>

                Where:
                    fileName - The path to the moviedata.json file that you can
download from the Amazon DynamoDB Developer Guide.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String fileName = args[0];
        String tableName = "MoviesPartiQ";
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
                .region(region)
                .build();

        System.out.println(
                "******* Creating an Amazon DynamoDB table named MoviesPartiQ with a
key named year and a sort key named title.");
        createTable(ddb, tableName);

        System.out.println("******* Loading data into the MoviesPartiQ table.");
        loadData(ddb, fileName);

        System.out.println("******* Getting data from the MoviesPartiQ table.");
        getItem(ddb);

        System.out.println("******* Putting a record into the MoviesPartiQ table.");
        putRecord(ddb);

        System.out.println("******* Updating a record.");
        updateTableItem(ddb);

        System.out.println("******* Querying the movies released in 2013.");
        queryTable(ddb);

        System.out.println("******* Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
```

```
        ddb.close();
    }

    public static void createTable(DynamoDbClient ddb, String tableName) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("year")
                .attributeType("N")
                .build());

        attributeDefinitions.add(AttributeDefinition.builder()
                .attributeName("title")
                .attributeType("S")
                .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
                .attributeName("year")
                .keyType(KeyType.HASH)
                .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
                .attributeName("title")
                .keyType(KeyType.RANGE) // Sort
                .build();

        // Add KeySchemaElement objects to the list.
        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
                .keySchema(tableKey)
                .provisionedThroughput(ProvisionedThroughput.builder()
                        .readCapacityUnits(new Long(10))
                        .writeCapacityUnits(new Long(10))
                        .build())
                .attributeDefinitions(attributeDefinitions)
                .tableName(tableName)
                .build();

        try {
```

```
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " + newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String fileName) throws
IOException {

        String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?,
'title' : ?, 'info' : ?}";
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        List<AttributeValue> parameters = new ArrayList<>();
        while (iter.hasNext()) {

            // Add 200 movies to the table.
            if (t == 200)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf(year))
```

```
                .build();

            AttributeValue att2 = AttributeValue.builder()
                    .s(title)
                    .build();

            AttributeValue att3 = AttributeValue.builder()
                    .s(info)
                    .build();

            parameters.add(att1);
            parameters.add(att2);
            parameters.add(att3);

            // Insert the movie into the Amazon DynamoDB table.
            executeStatementRequest(ddb, sqlStatement, parameters);
            System.out.println("Added Movie " + title);

            parameters.remove(att1);
            parameters.remove(att2);
            parameters.remove(att3);
            t++;
        }
    }

    public static void getItem(DynamoDbClient ddb) {

        String sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and title=?";
        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
                .n("2012")
                .build();

        AttributeValue att2 = AttributeValue.builder()
                .s("The Perks of Being a Wallflower")
                .build();

        parameters.add(att1);
        parameters.add(att2);

        try {
            ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
```

```
            System.out.println("ExecuteStatement successful: " +
 response.toString());

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void putRecord(DynamoDbClient ddb) {

        String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?,
 'title' : ?, 'info' : ?}";
        try {
            List<AttributeValue> parameters = new ArrayList<>();

            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf("2020"))
                    .build();

            AttributeValue att2 = AttributeValue.builder()
                    .s("My Movie")
                    .build();

            AttributeValue att3 = AttributeValue.builder()
                    .s("No Information")
                    .build();

            parameters.add(att1);
            parameters.add(att2);
            parameters.add(att3);

            executeStatementRequest(ddb, sqlStatement, parameters);
            System.out.println("Added new movie.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateTableItem(DynamoDbClient ddb) {
```

```
        String sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\":[\"Merian
C. Cooper\",\"Ernest B. Schoedsack' where year=? and title=?";
        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
                .n(String.valueOf("2013"))
                .build();

        AttributeValue att2 = AttributeValue.builder()
                .s("The East")
                .build();

        parameters.add(att1);
        parameters.add(att2);

        try {
            executeStatementRequest(ddb, sqlStatement, parameters);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println("Item was updated!");
    }

    // Query the table where the year is 2013.
    public static void queryTable(DynamoDbClient ddb) {
        String sqlStatement = "SELECT * FROM MoviesPartiQ where year = ? ORDER BY
year";
        try {

            List<AttributeValue> parameters = new ArrayList<>();
            AttributeValue att1 = AttributeValue.builder()
                    .n(String.valueOf("2013"))
                    .build();
            parameters.add(att1);

            // Get items in the table and write out the ID value.
            ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
            System.out.println("ExecuteStatement successful: " +
response.toString());

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
```

```
            System.exit(1);
        }
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {

        DeleteTableRequest request = DeleteTableRequest.builder()
                .tableName(tableName)
                .build();

        try {
            ddb.deleteTable(request);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }

    private static ExecuteStatementResponse executeStatementRequest(DynamoDbClient
 ddb, String statement,
            List<AttributeValue> parameters) {
        ExecuteStatementRequest request = ExecuteStatementRequest.builder()
                .statement(statement)
                .parameters(parameters)
                .build();

        return ddb.executeStatement(request);
    }

    private static void processResults(ExecuteStatementResponse
 executeStatementResult) {
        System.out.println("ExecuteStatement successful: " +
 executeStatementResult.toString());
    }
}
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon EC2 usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DescribeSecurityGroupsRequest;
import software.amazon.awssdk.services.ec2.model.DescribeSecurityGroupsResponse;
import software.amazon.awssdk.services.ec2.model.SecurityGroup;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeSecurityGroups {
    public static void main(String[] args) {
        final String usage = "To run this example, supply a group id\n" +
                "Ex: DescribeSecurityGroups <groupId>\n";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        describeEC2SecurityGroups(ec2, groupId);
        ec2.close();
    }

    public static void describeEC2SecurityGroups(Ec2Client ec2, String groupId) {
        try {
            DescribeSecurityGroupsRequest request =
 DescribeSecurityGroupsRequest.builder()
                    .groupIds(groupId)
                    .build();

            DescribeSecurityGroupsResponse response =
 ec2.describeSecurityGroups(request);
            for (SecurityGroup group : response.securityGroups()) {
                System.out.printf(
                        "Found Security Group with id %s, " +
                                "vpc id %s " +
                                "and description %s",
                        group.groupId(),
                        group.vpcId(),
                        group.description());
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico para o Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.AllocateAddressRequest;
import software.amazon.awssdk.services.ec2.model.DomainType;
import software.amazon.awssdk.services.ec2.model.AllocateAddressResponse;
import software.amazon.awssdk.services.ec2.model.AssociateAddressRequest;
import software.amazon.awssdk.services.ec2.model.AssociateAddressResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class AllocateAddress {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <instanceId>

                Where:
                    instanceId - An instance id value that you can obtain from the
 AWS Console.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String instanceId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        System.out.println(getAllocateAddress(ec2, instanceId));
        ec2.close();
    }

    public static String getAllocateAddress(Ec2Client ec2, String instanceId) {
        try {
            AllocateAddressRequest allocateRequest =
 AllocateAddressRequest.builder()
                    .domain(DomainType.VPC)
                    .build();

            AllocateAddressResponse allocateResponse =
 ec2.allocateAddress(allocateRequest);
            String allocationId = allocateResponse.allocationId();
            AssociateAddressRequest associateRequest =
 AssociateAddressRequest.builder()
                    .instanceId(instanceId)
```

```
                    .allocationId(allocationId)
                    .build();

            AssociateAddressResponse associateResponse =
 ec2.associateAddress(associateRequest);
            return associateResponse.associationId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for Java 2.x da API.

Para associar um endereço IP elástico a uma instância

O exemplo de código a seguir mostra como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String associateAddress(Ec2Client ec2, String instanceId, String
 allocationId) {
        try {
            AssociateAddressRequest associateRequest =
 AssociateAddressRequest.builder()
                    .instanceId(instanceId)
                    .allocationId(allocationId)
                    .build();
```

```
            AssociateAddressResponse associateResponse =
 ec2.associateAddress(associateRequest);
            return associateResponse.associationId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for Java 2.x da API.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.CreateSecurityGroupRequest;
import
 software.amazon.awssdk.services.ec2.model.AuthorizeSecurityGroupIngressRequest;
import
 software.amazon.awssdk.services.ec2.model.AuthorizeSecurityGroupIngressResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import software.amazon.awssdk.services.ec2.model.IpPermission;
import software.amazon.awssdk.services.ec2.model.CreateSecurityGroupResponse;
import software.amazon.awssdk.services.ec2.model.IpRange;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateSecurityGroup {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                   <groupName> <groupDesc> <vpcId>\s

                                Where:
                                   groupName - A group name (for example,
 TestKeyPair).\s
                                   groupDesc - A group description  (for example,
 TestKeyPair).\s
                                   vpcId - A VPC ID that you can obtain from the AWS
 Management Console (for example, vpc-xxxxxf2f).\s

                                """;

                if (args.length != 3) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String groupName = args[0];
                String groupDesc = args[1];
                String vpcId = args[2];

                Region region = Region.US_EAST_1;
                Ec2Client ec2 = Ec2Client.builder()
                                .region(region)
                                .build();

                String id = createEC2SecurityGroup(ec2, groupName, groupDesc,
 vpcId);
                System.out.printf("Successfully created Security Group with this ID
 %s", id);
                ec2.close();
        }
```

```
        public static String createEC2SecurityGroup(Ec2Client ec2, String groupName,
String groupDesc, String vpcId) {
                try {
                        CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                                        .groupName(groupName)
                                        .description(groupDesc)
                                        .vpcId(vpcId)
                                        .build();

                        CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);

                        IpRange ipRange = IpRange.builder()
                                        .cidrIp("0.0.0.0/0").build();

                        IpPermission ipPerm = IpPermission.builder()
                                        .ipProtocol("tcp")
                                        .toPort(80)
                                        .fromPort(80)
                                        .ipRanges(ipRange)
                                        .build();

                        IpPermission ipPerm2 = IpPermission.builder()
                                        .ipProtocol("tcp")
                                        .toPort(22)
                                        .fromPort(22)
                                        .ipRanges(ipRange)
                                        .build();

                        AuthorizeSecurityGroupIngressRequest authRequest =
AuthorizeSecurityGroupIngressRequest
                                        .builder()
                                        .groupName(groupName)
                                        .ipPermissions(ipPerm, ipPerm2)
                                        .build();

                        AuthorizeSecurityGroupIngressResponse authResponse = ec2
                                        .authorizeSecurityGroupIngress(authRequest);
                        System.out.printf("Successfully added ingress policy to
Security Group %s", groupName);
                        return resp.groupId();

                } catch (Ec2Exception e) {
```

```
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
                return "";
        }
}
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for Java 2.x da API.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.CreateKeyPairRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateKeyPair {

    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                   <keyName>\s

                Where:
                   keyName - A key pair name (for example, TestKeyPair).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyName = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        createEC2KeyPair(ec2, keyName);
        ec2.close();
    }

    public static void createEC2KeyPair(Ec2Client ec2, String keyName) {
        try {
            CreateKeyPairRequest request = CreateKeyPairRequest.builder()
                    .keyName(keyName)
                    .build();

            ec2.createKeyPair(request);
            System.out.printf("Successfully created key pair named %s", keyName);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateKeyPair a Referência AWS SDK for Java 2.x da API.

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.InstanceType;
import software.amazon.awssdk.services.ec2.model.RunInstancesRequest;
import software.amazon.awssdk.services.ec2.model.RunInstancesResponse;
import software.amazon.awssdk.services.ec2.model.Tag;
import software.amazon.awssdk.services.ec2.model.CreateTagsRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This code example requires an AMI value. You can learn more about this value
 * by reading this documentation topic:
 *
 * https://docs.aws.amazon.com/AWSEC2/latest/WindowsGuide/AMIs.html
 */
public class CreateInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <name> <amiId>

                Where:
```

```
                  name - An instance name value that you can obtain from the AWS
Console (for example, ami-xxxxxx5c8b987b1a0).\s
                  amiId - An Amazon Machine Image (AMI) value that you can obtain
from the AWS Console (for example, i-xxxxxx2734106d0ab).\s
               """;

       if (args.length != 2) {
           System.out.println(usage);
           System.exit(1);
       }

       String name = args[0];
       String amiId = args[1];
       Region region = Region.US_EAST_1;
       Ec2Client ec2 = Ec2Client.builder()
               .region(region)
               .build();

       String instanceId = createEC2Instance(ec2, name, amiId);
       System.out.println("The Amazon EC2 Instance ID is " + instanceId);
       ec2.close();
   }

   public static String createEC2Instance(Ec2Client ec2, String name, String amiId)
{
       RunInstancesRequest runRequest = RunInstancesRequest.builder()
               .imageId(amiId)
               .instanceType(InstanceType.T1_MICRO)
               .maxCount(1)
               .minCount(1)
               .build();

       RunInstancesResponse response = ec2.runInstances(runRequest);
       String instanceId = response.instances().get(0).instanceId();
       Tag tag = Tag.builder()
               .key("Name")
               .value(name)
               .build();

       CreateTagsRequest tagRequest = CreateTagsRequest.builder()
               .resources(instanceId)
               .tags(tag)
               .build();
```

```
        try {
            ec2.createTags(tagRequest);
            System.out.printf("Successfully started EC2 Instance %s based on AMI
 %s", instanceId, amiId);
            return instanceId;

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
}
```

- Para obter detalhes da API, consulte RunInstancesa Referência AWS SDK for Java 2.x da API.

Exclua um grupo de segurança

O exemplo de código a seguir mostra como excluir um grupo de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DeleteSecurityGroupRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
```

```
 */
public class DeleteSecurityGroup {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <groupId>\s

                Where:
                   groupId - A security group id that you can obtain from the AWS
 Console (for example, sg-xxxxxx1c0b65785c3).""";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String groupId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        deleteEC2SecGroup(ec2, groupId);
        ec2.close();
    }

    public static void deleteEC2SecGroup(Ec2Client ec2, String groupId) {
        try {
            DeleteSecurityGroupRequest request =
 DeleteSecurityGroupRequest.builder()
                    .groupId(groupId)
                    .build();

            ec2.deleteSecurityGroup(request);
            System.out.printf("Successfully deleted Security Group with id %s",
 groupId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteSecurityGroupa Referência AWS SDK for Java 2.x da API.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DeleteKeyPairRequest;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteKeyPair {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <keyPair>\s

                Where:
                   keyPair - A key pair name (for example, TestKeyPair).""";
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyPair = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        deleteKeys(ec2, keyPair);
        ec2.close();
    }

    public static void deleteKeys(Ec2Client ec2, String keyPair) {
        try {
            DeleteKeyPairRequest request = DeleteKeyPairRequest.builder()
                    .keyName(keyPair)
                    .build();

            ec2.deleteKeyPair(request);
            System.out.printf("Successfully deleted key pair named %s", keyPair);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteKeyPaira Referência AWS SDK for Java 2.x da API.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String describeEC2Instances(Ec2Client ec2, String newInstanceId) {
        try {
            String pubAddress = "";
            boolean isRunning = false;
            DescribeInstancesRequest request = DescribeInstancesRequest.builder()
                    .instanceIds(newInstanceId)
                    .build();

            while (!isRunning) {
                DescribeInstancesResponse response = ec2.describeInstances(request);
                String state =
response.reservations().get(0).instances().get(0).state().name().name();
                if (state.compareTo("RUNNING") == 0) {
                    System.out.println("Image id is " +
response.reservations().get(0).instances().get(0).imageId());
                    System.out.println(
                            "Instance type is " +
response.reservations().get(0).instances().get(0).instanceType());
                    System.out.println(
                            "Instance state is " +
response.reservations().get(0).instances().get(0).state().name());
                    pubAddress =
response.reservations().get(0).instances().get(0).publicIpAddress();
                    System.out.println("Instance address is " + pubAddress);
                    isRunning = true;
                }
            }
            return pubAddress;
        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for Java 2.x da API.

Desassociar um endereço IP elástico de uma instância

O exemplo de código a seguir mostra como desassociar um endereço IP elástico de uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void disassociateAddress(Ec2Client ec2, String associationId) {
        try {
            DisassociateAddressRequest addressRequest =
DisassociateAddressRequest.builder()
                    .associationId(associationId)
                    .build();

            ec2.disassociateAddress(addressRequest);
            System.out.println("You successfully disassociated the address!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DisassociateAddressa Referência AWS SDK for Java 2.x da API.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeSecurityGroups(Ec2Client ec2, String groupId) {
       try {
           DescribeSecurityGroupsRequest request =
DescribeSecurityGroupsRequest.builder()
                   .groupIds(groupId)
                   .build();

           DescribeSecurityGroupsResponse response =
ec2.describeSecurityGroups(request);
           for (SecurityGroup group : response.securityGroups()) {
               System.out
                       .println("Found Security Group with Id " + group.groupId() +
" and group VPC " + group.vpcId());
           }

       } catch (Ec2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeSecurityGroupsa Referência AWS SDK for Java 2.x da API.

Obter dados sobre tipos de instâncias

O exemplo de código a seguir mostra como obter dados sobre tipos de instâncias do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of instance types.
   public static String getInstanceTypes(Ec2Client ec2) {
       String instanceType = "";
       try {
           List<Filter> filters = new ArrayList<>();
           Filter filter = Filter.builder()
                   .name("processor-info.supported-architecture")
                   .values("arm64")
                   .build();

           filters.add(filter);
           DescribeInstanceTypesRequest typesRequest =
DescribeInstanceTypesRequest.builder()
                   .filters(filters)
                   .maxResults(10)
                   .build();

           DescribeInstanceTypesResponse response =
ec2.describeInstanceTypes(typesRequest);
           List<InstanceTypeInfo> instanceTypes = response.instanceTypes();
           for (InstanceTypeInfo type : instanceTypes) {
               System.out.println("The memory information of this type is " +
type.memoryInfo().sizeInMiB());
               System.out.println("Network information is " +
type.networkInfo().toString());
               instanceType = type.instanceType().toString();
           }

           return instanceType;

       } catch (SsmException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
```

```
        return "";
    }
```

- Para obter detalhes da API, consulte DescribeInstanceTypesa Referência AWS SDK for Java 2.x da API.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.DescribeKeyPairsResponse;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeKeyPairs {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        describeEC2Keys(ec2);
        ec2.close();
    }
```

```
    public static void describeEC2Keys(Ec2Client ec2) {
        try {
            DescribeKeyPairsResponse response = ec2.describeKeyPairs();
            response.keyPairs().forEach(keyPair -> System.out.printf(
                    "Found key pair with name %s " +
                            "and fingerprint %s",
                    keyPair.keyName(),
                    keyPair.keyFingerprint()));

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeKeyPairsa Referência AWS SDK for Java 2.x da API.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import software.amazon.awssdk.services.ec2.model.ReleaseAddressRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ReleaseAddress {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <allocId>

                Where:
                   allocId - An allocation ID value that you can obtain from the AWS
 Console.\s

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String allocId = args[0];
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        releaseEC2Address(ec2, allocId);
        ec2.close();
    }

    public static void releaseEC2Address(Ec2Client ec2, String allocId) {
        try {
            ReleaseAddressRequest request = ReleaseAddressRequest.builder()
                    .allocationId(allocId)
                    .build();

            ec2.releaseAddress(request);
            System.out.printf("Successfully released elastic IP address %s",
 allocId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for Java 2.x da API.

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createSecurityGroup(Ec2Client ec2, String groupName, String
groupDesc, String vpcId,
           String myIpAddress) {
       try {
           CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                   .groupName(groupName)
                   .description(groupDesc)
                   .vpcId(vpcId)
                   .build();

           CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);
           IpRange ipRange = IpRange.builder()
                   .cidrIp(myIpAddress + "/0")
                   .build();

           IpPermission ipPerm = IpPermission.builder()
                   .ipProtocol("tcp")
```

```
                    .toPort(80)
                    .fromPort(80)
                    .ipRanges(ipRange)
                    .build();

            IpPermission ipPerm2 = IpPermission.builder()
                    .ipProtocol("tcp")
                    .toPort(22)
                    .fromPort(22)
                    .ipRanges(ipRange)
                    .build();

            AuthorizeSecurityGroupIngressRequest authRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                    .groupName(groupName)
                    .ipPermissions(ipPerm, ipPerm2)
                    .build();

            ec2.authorizeSecurityGroupIngress(authRequest);
            System.out.println("Successfully added ingress policy to security group
" + groupName);
            return resp.groupId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte AuthorizeSecurityGroupIngressa Referência AWS SDK for Java 2.x da API.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void startInstance(Ec2Client ec2, String instanceId) {
       Ec2Waiter ec2Waiter = Ec2Waiter.builder()
               .overrideConfiguration(b -> b.maxAttempts(100))
               .client(ec2)
               .build();

       StartInstancesRequest request = StartInstancesRequest.builder()
               .instanceIds(instanceId)
               .build();

       System.out.println("Use an Ec2Waiter to wait for the instance to run. This
will take a few minutes.");
       ec2.startInstances(request);
       DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
               .instanceIds(instanceId)
               .build();

       WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceRunning(instanceRequest);
       waiterResponse.matched().response().ifPresent(System.out::println);
       System.out.println("Successfully started instance " + instanceId);
   }
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for Java 2.x da API.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void stopInstance(Ec2Client ec2, String instanceId) {
       Ec2Waiter ec2Waiter = Ec2Waiter.builder()
               .overrideConfiguration(b -> b.maxAttempts(100))
               .client(ec2)
               .build();
       StopInstancesRequest request = StopInstancesRequest.builder()
               .instanceIds(instanceId)
               .build();

       System.out.println("Use an Ec2Waiter to wait for the instance to stop. This
will take a few minutes.");
       ec2.stopInstances(request);
       DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
               .instanceIds(instanceId)
               .build();

       WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceStopped(instanceRequest);
       waiterResponse.matched().response().ifPresent(System.out::println);
       System.out.println("Successfully stopped instance " + instanceId);
   }
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for Java 2.x da API.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ec2.Ec2Client;
import software.amazon.awssdk.services.ec2.model.TerminateInstancesRequest;
import software.amazon.awssdk.services.ec2.model.TerminateInstancesResponse;
import software.amazon.awssdk.services.ec2.model.InstanceStateChange;
import software.amazon.awssdk.services.ec2.model.Ec2Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class TerminateInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <instanceId>

                Where:
                   instanceId - An instance id value that you can obtain from the
 AWS Console.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String instanceId = args[0];
```

```
        Region region = Region.US_EAST_1;
        Ec2Client ec2 = Ec2Client.builder()
                .region(region)
                .build();

        terminateEC2(ec2, instanceId);
        ec2.close();
    }

    public static void terminateEC2(Ec2Client ec2, String instanceID) {
        try {
            TerminateInstancesRequest ti = TerminateInstancesRequest.builder()
                    .instanceIds(instanceID)
                    .build();

            TerminateInstancesResponse response = ec2.terminateInstances(ti);
            List<InstanceStateChange> list = response.terminatingInstances();
            for (InstanceStateChange sc : list) {
                System.out.println("The ID of the terminated instance is " +
 sc.instanceId());
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for Java 2.x da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
```

```
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-prof-
bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException, InterruptedException
 {
        Scanner in = new Scanner(System.in);
        Database database = new Database();
        AutoScaler autoScaler = new AutoScaler();
        LoadBalancer loadBalancer = new LoadBalancer();

        System.out.println(DASHES);
        System.out.println("Welcome to the demonstration of How to Build and Manage
 a Resilient Service!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("A - SETUP THE RESOURCES");
        System.out.println("Press Enter when you're ready to start deploying
 resources.");
        in.nextLine();
        deploy(loadBalancer);
        System.out.println(DASHES);
        System.out.println(DASHES);
        System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
        System.out.println("Press Enter when you're ready.");
        in.nextLine();
        demo(loadBalancer);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("C - DELETE THE RESOURCES");
        System.out.println("""
```

```
                This concludes the demo of how to build and manage a resilient
service.
                To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources
                that were created for this demo.
                """);

        System.out.println("\n Do you want to delete the resources (y/n)? ");
        String userInput = in.nextLine().trim().toLowerCase(); // Capture user input

        if (userInput.equals("y")) {
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }
```

```
   private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
       Scanner in = new Scanner(System.in);
       System.out.println(
               """
                       For this demo, we'll use the AWS SDK for Java (v2) to create
several AWS resources
                       to set up a load-balanced web service endpoint and explore
some ways to make it resilient
                       against various kinds of failures.

                       Some of the resources create by this demo are:
                       \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                       \t* An EC2 launch template that defines EC2 instances that
each contain a Python web server.
                       \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                       \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                       """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when an
instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
               run a web server, such as Apache, with least-privileged credentials.
```

```
                The template also defines an IAM policy that each instance uses to
assume a role that grants
                permissions to access the DynamoDB recommendation table and Systems
Manager parameters
                that control the flow of the demo.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load balancer.
The target group
```

```
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets, targetGroupArn,
lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul = loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(), StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group for
your default VPC must
                            allow access from this computer. You can either add it
automatically from this
```

```
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security group
are configured correctly and that");
            System.out.println("you can successfully make a GET request to the load
balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
```

```
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and shows
how using a resilient
                        architecture can keep the web service running in spite of
these failures.

                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager parameter
named self.param_helper.table.
                        To simulate a failure of the recommendation service, let's
set this parameter to name a non-existent table.
                       """);
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        System.out.println(
                """
                        \nNow, sending a GET request to the load balancer endpoint
returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health checks
don't check for failure of the recommendation service.
                       """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                       Instead of failing when the recommendation service fails,
the web service can return a static response.
```

```
                        While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                        """);
        paramHelper.put(paramHelper.failureResponse, "static");

        System.out.println("""
                Now, sending a GET request to the load balancer endpoint returns a
static response.
                The service still reports as healthy because health checks are still
shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance id
value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId = autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " + profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
```

```
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on for
recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto Scaling
instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy
```

```
                        instance is to terminate it and let the auto scaler start a
new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load balancing
rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
                can see the changing health check status until the new instance is
running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);

        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
```

```
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode = response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
```

```
                    case 1 -> {
                        System.out.println("\nChecking the health of load balancer
 targets:\n");
                        List<TargetHealthDescription> health =
 loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
 target.target().id(),
                                        target.target().port(),
 target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the health
 check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value between
 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {
```

```
    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
```

```
     * Terminates and instances in an EC2 Auto Scaling group. After an instance is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure 'newInstanceProfileName'
is a valid IAM Instance Profile
                                              // name.
                .build();

        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();
```

```
        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with profile
%s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
```

```
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress) {
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);
```

```
            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network, you
     * must instead specify a prefix list ID. You can also temporarily open the port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();
```

```
            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse = getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup : securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " + secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " + ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to be
open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or to
a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }
```

```
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
        software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();
```

```
        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();
```

```
        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response = getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();
```

```
        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to the
policy.
```

```
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
 DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
 ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
 iamClient.listInstanceProfilesForRole(listRolesRequest);
```

```
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
 listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
 RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance profile
 " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
 DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
```

```
    public List<TargetHealthDescription> checkTargetHealth(String targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()
                .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
```

```
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws IOException,
InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
```

```
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId, String
targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }

    /*
```

```
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();

           // Create and wait for the load balancer to become available.
           CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
           String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

           ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
           DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                   .loadBalancerArns(lbARN)
                   .build();

           System.out.println("Waiting for Load Balancer " + lbName + " to become
available.");
           WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                   .waitUntilLoadBalancerAvailable(request);
           waiterResponse.matched().response().ifPresent(System.out::println);
           System.out.println("Load Balancer " + lbName + " is available.");

           // Get the DNS name (endpoint) of the load balancer.
           String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
           System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

           // Create a listener for the load balance.
```

```
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

 .loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
```

```
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " + e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended, such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException {
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
```

```
                                .attributeName("ItemId")
                                .attributeType(ScalarAttributeType.N)
                                .build())
                .keySchema(
                        KeySchemaElement.builder()
                                .attributeName("MediaType")
                                .keyType(KeyType.HASH)
                                .build(),
                        KeySchemaElement.builder()
                                .attributeName("ItemId")
                                .keyType(KeyType.RANGE)
                                .build())
                .provisionedThroughput(
                        ProvisionedThroughput.builder()
                                .readCapacityUnits(5L)
                                .writeCapacityUnits(5L)
                                .build())
                .build();

        getDynamoDbClient().createTable(createTableRequest);
        System.out.println("Creating table " + tableName + "...");

        // Wait until the Amazon DynamoDB table is created.
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                .tableName(tableName)
                .build();

        WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Table " + tableName + " created.");

        // Add records to the table.
        populateTable(fileName, tableName);
    }
}

public void deleteTable(String tableName) {
    getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
    System.out.println("Table " + tableName + " deleted.");
}

// Populates the table with data located in a JSON file using the DynamoDB
// enhanced client.
```

```
    public void populateTable(String fileName, String tableName) throws IOException
 {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable = enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
```

```
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups

- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Começar a usar instâncias

O código de exemplo a seguir mostra como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.
- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.
- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java example performs the following tasks:
 *
 * 1. Creates an RSA key pair and saves the private key data as a .pem file.
 * 2. Lists key pairs.
 * 3. Creates a security group for the default VPC.
 * 4. Displays security group information.
 * 5. Gets a list of Amazon Linux 2 AMIs and selects one.
 * 6. Gets more information about the image.
 * 7. Gets a list of instance types that are compatible with the selected AMI’s
 * architecture.
 * 8. Creates an instance with the key pair, security group, AMI, and an
 * instance type.
 * 9. Displays information about the instance.
 * 10. Stops the instance and waits for it to stop.
 * 11. Starts the instance and waits for it to start.
 * 12. Allocates an Elastic IP address and associates it with the instance.
 * 13. Displays SSH connection info for the instance.
 * 14. Disassociates and deletes the Elastic IP address.
 * 15. Terminates the instance and waits for it to terminate.
 * 16. Deletes the security group.
 * 17. Deletes the key pair.
 */
public class EC2Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {

        final String usage = """

                Usage:
                   <keyName> <fileName> <groupName> <groupDesc> <vpcId>

                Where:
                   keyName -  A key pair name (for example, TestKeyPair).\s
                   fileName -  A file name where the key information is written to.
\s
                   groupName - The name of the security group.\s
                   groupDesc - The description of the security group.\s
```

```
                  vpcId - A VPC Id value. You can get this value from the AWS
Management Console.\s
                  myIpAddress - The IP address of your development machine.\s

               """;

       if (args.length != 6) {
           System.out.println(usage);
           System.exit(1);
       }

       String keyName = args[0];
       String fileName = args[1];
       String groupName = args[2];
       String groupDesc = args[3];
       String vpcId = args[4];
       String myIpAddress = args[5];

       Region region = Region.US_WEST_2;
       Ec2Client ec2 = Ec2Client.builder()
               .region(region)
               .build();

       SsmClient ssmClient = SsmClient.builder()
               .region(region)
               .build();

       System.out.println(DASHES);
       System.out.println("Welcome to the Amazon EC2 example scenario.");
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("1. Create an RSA key pair and save the private key
material as a .pem file.");
       createKeyPair(ec2, keyName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("2. List key pairs.");
       describeKeys(ec2);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("3. Create a security group.");
```

```
        String groupId = createSecurityGroup(ec2, groupName, groupDesc, vpcId,
myIpAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Display security group info for the newly created
security group.");
        describeSecurityGroups(ec2, groupId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get a list of Amazon Linux 2 AMIs and selects one
with amzn2 in the name.");
        String instanceId = getParaValues(ssmClient);
        System.out.println("The instance Id is " + instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Get more information about an amzn2 image.");
        String amiValue = describeImage(ec2, instanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of instance types.");
        String instanceType = getInstanceTypes(ec2);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Create an instance.");
        String newInstanceId = runInstance(ec2, instanceType, keyName, groupName,
amiValue);
        System.out.println("The instance Id is " + newInstanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Display information about the running instance. ");
        String ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Stop the instance and use a waiter.");
        stopInstance(ec2, newInstanceId);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Start the instance and use a waiter.");
        startInstance(ec2, newInstanceId);
        ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Allocate an Elastic IP address and associate it with
 the instance.");
        String allocationId = allocateAddress(ec2);
        System.out.println("The allocation Id value is " + allocationId);
        String associationId = associateAddress(ec2, newInstanceId, allocationId);
        System.out.println("The associate Id value is " + associationId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Describe the instance again.");
        ipAddress = describeEC2Instances(ec2, newInstanceId);
        System.out.println("You can SSH to the instance using this command:");
        System.out.println("ssh -i " + fileName + "ec2-user@" + ipAddress);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Disassociate and release the Elastic IP address.");
        disassociateAddress(ec2, associationId);
        releaseEC2Address(ec2, allocationId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Terminate the instance and use a waiter.");
        terminateEC2(ec2, newInstanceId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete the security group.");
        deleteEC2SecGroup(ec2, groupId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Delete the key.");
```

```
        deleteKeys(ec2, keyName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("You successfully completed the Amazon EC2 scenario.");
        System.out.println(DASHES);
        ec2.close();
    }

    public static void deleteEC2SecGroup(Ec2Client ec2, String groupId) {
        try {
            DeleteSecurityGroupRequest request =
DeleteSecurityGroupRequest.builder()
                    .groupId(groupId)
                    .build();

            ec2.deleteSecurityGroup(request);
            System.out.println("Successfully deleted security group with Id " +
groupId);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void terminateEC2(Ec2Client ec2, String instanceId) {
        try {
            Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                    .overrideConfiguration(b -> b.maxAttempts(100))
                    .client(ec2)
                    .build();

            TerminateInstancesRequest ti = TerminateInstancesRequest.builder()
                    .instanceIds(instanceId)
                    .build();

            System.out.println("Use an Ec2Waiter to wait for the instance to
terminate. This will take a few minutes.");
            ec2.terminateInstances(ti);
            DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                    .instanceIds(instanceId)
                    .build();
```

```
            WaiterResponse<DescribeInstancesResponse> waiterResponse = ec2Waiter
                    .waitUntilInstanceTerminated(instanceRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Successfully started instance " + instanceId);
            System.out.println(instanceId + " is terminated!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteKeys(Ec2Client ec2, String keyPair) {
        try {
            DeleteKeyPairRequest request = DeleteKeyPairRequest.builder()
                    .keyName(keyPair)
                    .build();

            ec2.deleteKeyPair(request);
            System.out.println("Successfully deleted key pair named " + keyPair);

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void releaseEC2Address(Ec2Client ec2, String allocId) {
        try {
            ReleaseAddressRequest request = ReleaseAddressRequest.builder()
                    .allocationId(allocId)
                    .build();

            ec2.releaseAddress(request);
            System.out.println("Successfully released Elastic IP address " +
allocId);
        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void disassociateAddress(Ec2Client ec2, String associationId) {
```

```
        try {
            DisassociateAddressRequest addressRequest =
DisassociateAddressRequest.builder()
                    .associationId(associationId)
                    .build();

            ec2.disassociateAddress(addressRequest);
            System.out.println("You successfully disassociated the address!");

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String associateAddress(Ec2Client ec2, String instanceId, String
allocationId) {
        try {
            AssociateAddressRequest associateRequest =
AssociateAddressRequest.builder()
                    .instanceId(instanceId)
                    .allocationId(allocationId)
                    .build();

            AssociateAddressResponse associateResponse =
ec2.associateAddress(associateRequest);
            return associateResponse.associationId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String allocateAddress(Ec2Client ec2) {
        try {
            AllocateAddressRequest allocateRequest =
AllocateAddressRequest.builder()
                    .domain(DomainType.VPC)
                    .build();

            AllocateAddressResponse allocateResponse =
ec2.allocateAddress(allocateRequest);
```

```
            return allocateResponse.allocationId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void startInstance(Ec2Client ec2, String instanceId) {
        Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                .overrideConfiguration(b -> b.maxAttempts(100))
                .client(ec2)
                .build();

        StartInstancesRequest request = StartInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to run. This
will take a few minutes.");
        ec2.startInstances(request);
        DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceRunning(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully started instance " + instanceId);
    }

    public static void stopInstance(Ec2Client ec2, String instanceId) {
        Ec2Waiter ec2Waiter = Ec2Waiter.builder()
                .overrideConfiguration(b -> b.maxAttempts(100))
                .client(ec2)
                .build();
        StopInstancesRequest request = StopInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        System.out.println("Use an Ec2Waiter to wait for the instance to stop. This
will take a few minutes.");
```

```
        ec2.stopInstances(request);
        DescribeInstancesRequest instanceRequest =
DescribeInstancesRequest.builder()
                .instanceIds(instanceId)
                .build();

        WaiterResponse<DescribeInstancesResponse> waiterResponse =
ec2Waiter.waitUntilInstanceStopped(instanceRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Successfully stopped instance " + instanceId);
    }

    public static String describeEC2Instances(Ec2Client ec2, String newInstanceId) {
        try {
            String pubAddress = "";
            boolean isRunning = false;
            DescribeInstancesRequest request = DescribeInstancesRequest.builder()
                    .instanceIds(newInstanceId)
                    .build();

            while (!isRunning) {
                DescribeInstancesResponse response = ec2.describeInstances(request);
                String state =
response.reservations().get(0).instances().get(0).state().name().name();
                if (state.compareTo("RUNNING") == 0) {
                    System.out.println("Image id is " +
response.reservations().get(0).instances().get(0).imageId());
                    System.out.println(
                            "Instance type is " +
response.reservations().get(0).instances().get(0).instanceType());
                    System.out.println(
                            "Instance state is " +
response.reservations().get(0).instances().get(0).state().name());
                    pubAddress =
response.reservations().get(0).instances().get(0).publicIpAddress();
                    System.out.println("Instance address is " + pubAddress);
                    isRunning = true;
                }
            }
            return pubAddress;
        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
        return "";
    }

    public static String runInstance(Ec2Client ec2, String instanceType, String
keyName, String groupName,
            String amiId) {
        try {
            RunInstancesRequest runRequest = RunInstancesRequest.builder()
                    .instanceType(instanceType)
                    .keyName(keyName)
                    .securityGroups(groupName)
                    .maxCount(1)
                    .minCount(1)
                    .imageId(amiId)
                    .build();

            RunInstancesResponse response = ec2.runInstances(runRequest);
            String instanceId = response.instances().get(0).instanceId();
            System.out.println("Successfully started EC2 instance " + instanceId + "
based on AMI " + amiId);
            return instanceId;

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Get a list of instance types.
    public static String getInstanceTypes(Ec2Client ec2) {
        String instanceType = "";
        try {
            List<Filter> filters = new ArrayList<>();
            Filter filter = Filter.builder()
                    .name("processor-info.supported-architecture")
                    .values("arm64")
                    .build();

            filters.add(filter);
            DescribeInstanceTypesRequest typesRequest =
DescribeInstanceTypesRequest.builder()
                    .filters(filters)
                    .maxResults(10)
```

```
                    .build();

            DescribeInstanceTypesResponse response =
ec2.describeInstanceTypes(typesRequest);
            List<InstanceTypeInfo> instanceTypes = response.instanceTypes();
            for (InstanceTypeInfo type : instanceTypes) {
                System.out.println("The memory information of this type is " +
type.memoryInfo().sizeInMiB());
                System.out.println("Network information is " +
type.networkInfo().toString());
                instanceType = type.instanceType().toString();
            }

            return instanceType;

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Display the Description field that corresponds to the instance Id value.
    public static String describeImage(Ec2Client ec2, String instanceId) {
        try {
            DescribeImagesRequest imagesRequest = DescribeImagesRequest.builder()
                    .imageIds(instanceId)
                    .build();

            DescribeImagesResponse response = ec2.describeImages(imagesRequest);
            System.out.println("The description of the first image is " +
response.images().get(0).description());
            System.out.println("The name of the first image is " +
response.images().get(0).name());

            // Return the image Id value.
            return response.images().get(0).imageId();

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
```

```
    // Get the Id value of an instance with amzn2 in the name.
    public static String getParaValues(SsmClient ssmClient) {
        try {
            GetParametersByPathRequest parameterRequest =
GetParametersByPathRequest.builder()
                    .path("/aws/service/ami-amazon-linux-latest")
                    .build();

            GetParametersByPathIterable responses =
ssmClient.getParametersByPathPaginator(parameterRequest);
            for
(software.amazon.awssdk.services.ssm.model.GetParametersByPathResponse response :
responses) {
                System.out.println("Test " + response.nextToken());
                List<Parameter> parameterList = response.parameters();
                for (Parameter para : parameterList) {
                    System.out.println("The name of the para is: " + para.name());
                    System.out.println("The type of the para is: " + para.type());
                    if (filterName(para.name())) {
                        return para.value();
                    }
                }
            }

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    // Return true if the name has amzn2 in it. For example:
    // /aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-arm64-gp2
    private static boolean filterName(String name) {
        String[] parts = name.split("/");
        String myValue = parts[4];
        return myValue.contains("amzn2");
    }

    public static void describeSecurityGroups(Ec2Client ec2, String groupId) {
        try {
            DescribeSecurityGroupsRequest request =
DescribeSecurityGroupsRequest.builder()
```

```
                    .groupIds(groupId)
                    .build();

            DescribeSecurityGroupsResponse response =
ec2.describeSecurityGroups(request);
            for (SecurityGroup group : response.securityGroups()) {
                System.out
                        .println("Found Security Group with Id " + group.groupId() +
" and group VPC " + group.vpcId());
            }

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createSecurityGroup(Ec2Client ec2, String groupName, String
groupDesc, String vpcId,
            String myIpAddress) {
        try {
            CreateSecurityGroupRequest createRequest =
CreateSecurityGroupRequest.builder()
                    .groupName(groupName)
                    .description(groupDesc)
                    .vpcId(vpcId)
                    .build();

            CreateSecurityGroupResponse resp =
ec2.createSecurityGroup(createRequest);
            IpRange ipRange = IpRange.builder()
                    .cidrIp(myIpAddress + "/0")
                    .build();

            IpPermission ipPerm = IpPermission.builder()
                    .ipProtocol("tcp")
                    .toPort(80)
                    .fromPort(80)
                    .ipRanges(ipRange)
                    .build();

            IpPermission ipPerm2 = IpPermission.builder()
                    .ipProtocol("tcp")
                    .toPort(22)
```

```
                    .fromPort(22)
                    .ipRanges(ipRange)
                    .build();

            AuthorizeSecurityGroupIngressRequest authRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                    .groupName(groupName)
                    .ipPermissions(ipPerm, ipPerm2)
                    .build();

            ec2.authorizeSecurityGroupIngress(authRequest);
            System.out.println("Successfully added ingress policy to security group
" + groupName);
            return resp.groupId();

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void describeKeys(Ec2Client ec2) {
        try {
            DescribeKeyPairsResponse response = ec2.describeKeyPairs();
            response.keyPairs().forEach(keyPair -> System.out.printf(
                    "Found key pair with name %s " +
                            "and fingerprint %s",
                    keyPair.keyName(),
                    keyPair.keyFingerprint()));

        } catch (Ec2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createKeyPair(Ec2Client ec2, String keyName, String fileName)
{
        try {
            CreateKeyPairRequest request = CreateKeyPairRequest.builder()
                    .keyName(keyName)
                    .build();
```

```
            CreateKeyPairResponse response = ec2.createKeyPair(request);
            String content = response.keyMaterial();
            BufferedWriter writer = new BufferedWriter(new FileWriter(fileName));
            writer.write(content);
            writer.close();
            System.out.println("Successfully created key pair named " + keyName);

        } catch (Ec2Exception | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs
  - DescribeSecurityGroups
  - DisassociateAddress
  - ReleaseAddress
  - RunInstances
  - StartInstances
  - StopInstances
  - TerminateInstances

- UnmonitorInstances

Exemplos do Amazon ECS usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon ECS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um cluster

O exemplo de código a seguir mostra como criar um cluster do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.ExecuteCommandConfiguration;
import software.amazon.awssdk.services.ecs.model.ExecuteCommandLogging;
import software.amazon.awssdk.services.ecs.model.ClusterConfiguration;
import software.amazon.awssdk.services.ecs.model.CreateClusterResponse;
```

```
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.CreateClusterRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateCluster {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <clusterName>\s

                Where:
                   clusterName - The name of the ECS cluster to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterName = args[0];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        String clusterArn = createGivenCluster(ecsClient, clusterName);
        System.out.println("The cluster ARN is " + clusterArn);
        ecsClient.close();
    }

    public static String createGivenCluster(EcsClient ecsClient, String clusterName)
 {
        try {
            ExecuteCommandConfiguration commandConfiguration =
 ExecuteCommandConfiguration.builder()
                    .logging(ExecuteCommandLogging.DEFAULT)
```

```
                    .build();

            ClusterConfiguration clusterConfiguration =
 ClusterConfiguration.builder()
                    .executeCommandConfiguration(commandConfiguration)
                    .build();

            CreateClusterRequest clusterRequest = CreateClusterRequest.builder()
                    .clusterName(clusterName)
                    .configuration(clusterConfiguration)
                    .build();

            CreateClusterResponse response =
 ecsClient.createCluster(clusterRequest);
            return response.cluster().clusterArn();

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateCluster a Referência AWS SDK for Java 2.x da API.

Criar um serviço

O exemplo de código a seguir mostra como criar um serviço do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.AwsVpcConfiguration;
```

```
import software.amazon.awssdk.services.ecs.model.NetworkConfiguration;
import software.amazon.awssdk.services.ecs.model.CreateServiceRequest;
import software.amazon.awssdk.services.ecs.model.LaunchType;
import software.amazon.awssdk.services.ecs.model.CreateServiceResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateService {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                  <clusterName> <serviceName> <securityGroups>
 <subnets> <taskDefinition>

                                Where:
                                  clusterName - The name of the ECS cluster.
                                  serviceName - The name of the ECS service to
 create.
                                  securityGroups - The name of the security group.
                                  subnets - The name of the subnet.
                                  taskDefinition - The name of the task definition.
                                """;

                if (args.length != 5) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String clusterName = args[0];
                String serviceName = args[1];
                String securityGroups = args[2];
                String subnets = args[3];
                String taskDefinition = args[4];
                Region region = Region.US_EAST_1;
                EcsClient ecsClient = EcsClient.builder()
                                .region(region)
```

```
                                .build();

                String serviceArn = createNewService(ecsClient, clusterName,
serviceName, securityGroups, subnets,
                                taskDefinition);
                System.out.println("The ARN of the service is " + serviceArn);
                ecsClient.close();
        }

        public static String createNewService(EcsClient ecsClient,
                        String clusterName,
                        String serviceName,
                        String securityGroups,
                        String subnets,
                        String taskDefinition) {

                try {
                        AwsVpcConfiguration vpcConfiguration =
AwsVpcConfiguration.builder()
                                        .securityGroups(securityGroups)
                                        .subnets(subnets)
                                        .build();

                        NetworkConfiguration configuration =
NetworkConfiguration.builder()
                                        .awsvpcConfiguration(vpcConfiguration)
                                        .build();

                        CreateServiceRequest serviceRequest =
CreateServiceRequest.builder()
                                        .cluster(clusterName)
                                        .networkConfiguration(configuration)
                                        .desiredCount(1)
                                        .launchType(LaunchType.FARGATE)
                                        .serviceName(serviceName)
                                        .taskDefinition(taskDefinition)
                                        .build();

                        CreateServiceResponse response =
ecsClient.createService(serviceRequest);
                        return response.service().serviceArn();

                } catch (EcsException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
```

```
                        System.exit(1);
                }
                return "";
        }
}
```

- Para obter detalhes da API, consulte CreateServicea Referência AWS SDK for Java 2.x da API.

Excluir um serviço

O exemplo de código a seguir mostra como excluir um serviço do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DeleteServiceRequest;
import software.amazon.awssdk.services.ecs.model.EcsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteService {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterName> <serviceArn>\s
```

```
                Where:
                  clusterName - The name of the ECS cluster.
                  serviceArn - The ARN of the ECS service.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterName = args[0];
        String serviceArn = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        deleteSpecificService(ecsClient, clusterName, serviceArn);
        ecsClient.close();
    }

    public static void deleteSpecificService(EcsClient ecsClient, String
 clusterName, String serviceArn) {
        try {
            DeleteServiceRequest serviceRequest = DeleteServiceRequest.builder()
                    .cluster(clusterName)
                    .service(serviceArn)
                    .build();

            ecsClient.deleteService(serviceRequest);
            System.out.println("The Service was successfully deleted");

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteServicea Referência AWS SDK for Java 2.x da API.

Descrever clusters

O exemplo de código a seguir mostra como descrever clusters do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DescribeClustersRequest;
import software.amazon.awssdk.services.ecs.model.DescribeClustersResponse;
import software.amazon.awssdk.services.ecs.model.Cluster;
import software.amazon.awssdk.services.ecs.model.EcsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeClusters {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterArn> \s

                Where:
                  clusterArn - The ARN of the ECS cluster to describe.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String clusterArn = args[0];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        descCluster(ecsClient, clusterArn);
    }

    public static void descCluster(EcsClient ecsClient, String clusterArn) {
        try {
            DescribeClustersRequest clustersRequest =
 DescribeClustersRequest.builder()
                    .clusters(clusterArn)
                    .build();

            DescribeClustersResponse response =
 ecsClient.describeClusters(clustersRequest);
            List<Cluster> clusters = response.clusters();
            for (Cluster cluster : clusters) {
                System.out.println("The cluster name is " + cluster.clusterName());
            }

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for Java 2.x da API.

Descrever tarefas

O exemplo de código a seguir mostra como descrever suas tarefas do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.DescribeTasksRequest;
import software.amazon.awssdk.services.ecs.model.DescribeTasksResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.Task;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListTaskDefinitions {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <clusterArn> <taskId>\s

                Where:
                  clusterArn - The ARN of an ECS cluster.
                  taskId - The task Id value.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterArn = args[0];
```

```
        String taskId = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        getAllTasks(ecsClient, clusterArn, taskId);
        ecsClient.close();
    }

    public static void getAllTasks(EcsClient ecsClient, String clusterArn, String
 taskId) {
        try {
            DescribeTasksRequest tasksRequest = DescribeTasksRequest.builder()
                    .cluster(clusterArn)
                    .tasks(taskId)
                    .build();

            DescribeTasksResponse response = ecsClient.describeTasks(tasksRequest);
            List<Task> tasks = response.tasks();
            for (Task task : tasks) {
                System.out.println("The task ARN is " + task.taskDefinitionArn());
            }

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeTasksa Referência AWS SDK for Java 2.x da API.

Listar clusters

O exemplo de código a seguir mostra como listar seus clusters do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.ListClustersResponse;
import software.amazon.awssdk.services.ecs.model.EcsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class ListClusters {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        listAllClusters(ecsClient);
        ecsClient.close();
    }

    public static void listAllClusters(EcsClient ecsClient) {
        try {
            ListClustersResponse response = ecsClient.listClusters();
            List<String> clusters = response.clusterArns();
            for (String cluster : clusters) {
                System.out.println("The cluster arn is " + cluster);
            }
```

```
        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListClustersa Referência AWS SDK for Java 2.x da API.

Atualizar um serviço

O exemplo de código a seguir mostra como atualizar um serviço do Amazon ECS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ecs.EcsClient;
import software.amazon.awssdk.services.ecs.model.EcsException;
import software.amazon.awssdk.services.ecs.model.UpdateServiceRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class UpdateService {

    public static void main(String[] args) {

        final String usage = """
```

```
                Usage:
                   <clusterName> <serviceArn>\s

                Where:
                  clusterName - The cluster name.
                  serviceArn - The service ARN value.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterName = args[0];
        String serviceArn = args[1];
        Region region = Region.US_EAST_1;
        EcsClient ecsClient = EcsClient.builder()
                .region(region)
                .build();

        updateSpecificService(ecsClient, clusterName, serviceArn);
        ecsClient.close();
    }

    public static void updateSpecificService(EcsClient ecsClient, String
 clusterName, String serviceArn) {
        try {
            UpdateServiceRequest serviceRequest = UpdateServiceRequest.builder()
                    .cluster(clusterName)
                    .service(serviceArn)
                    .desiredCount(0)
                    .build();

            ecsClient.updateService(serviceRequest);
            System.out.println("The service was modified");

        } catch (EcsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateServicea Referência AWS SDK for Java 2.x da API.

Exemplos do Elastic Load Balancing usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Elastic Load Balancing.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Elastic Load Balancing

Os exemplos de código a seguir mostram como começar a usar o Elastic Load Balancing.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class HelloLoadBalancer {

        public static void main(String[] args) {
                ElasticLoadBalancingV2Client loadBalancingV2Client =
 ElasticLoadBalancingV2Client.builder()
                                .region(Region.US_EAST_1)
                                .build();
```

```
                DescribeLoadBalancersResponse loadBalancersResponse =
 loadBalancingV2Client
                                .describeLoadBalancers(r -> r.pageSize(10));
                List<LoadBalancer> loadBalancerList =
 loadBalancersResponse.loadBalancers();
                for (LoadBalancer lb : loadBalancerList)
                        System.out.println("Load Balancer DNS name = " +
 lb.dnsName());
        }
}
```

- Para obter detalhes da API, consulte DescribeLoadBalancersa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um receptor para o balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como criar um receptor que encaminha solicitações de um balanceador de carga do ELB para um grupo de destino.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
```

```
   public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();

           // Create and wait for the load balancer to become available.
           CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
           String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

           ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
           DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                   .loadBalancerArns(lbARN)
                   .build();

           System.out.println("Waiting for Load Balancer " + lbName + " to become
available.");
           WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                   .waitUntilLoadBalancerAvailable(request);
           waiterResponse.matched().response().ifPresent(System.out::println);
           System.out.println("Load Balancer " + lbName + " is available.");

           // Get the DNS name (endpoint) of the load balancer.
           String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
           System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

           // Create a listener for the load balance.
           Action action = Action.builder()
                   .targetGroupArn(targetGroupARN)
                   .type("forward")
                   .build();
```

```
            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateListenera Referência AWS SDK for Java 2.x da API.

Criar um grupo de destino

O exemplo de código a seguir mostra como criar um grupo de destino ELB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
```

```
     * how
     * the load balancer forward requests to instances in the group and how instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId, String
targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }
```

- Para obter detalhes da API, consulte CreateTargetGroupa Referência AWS SDK for Java 2.x da API.

Criar um Application Load Balancer

O exemplo de código a seguir mostra como criar um Application Load Balancer do ELB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /*
     * Creates an Elastic Load Balancing load balancer that uses the specified
     * subnets
     * and forwards requests to the specified target group.
     */
    public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
            String protocol) {
        try {
            List<String> subnetIdStrings = subnetIds.stream()
                    .map(Subnet::subnetId)
                    .collect(Collectors.toList());

            CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                    .subnets(subnetIdStrings)
                    .name(lbName)
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to become
available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);
```

```
            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateLoadBalancera Referência AWS SDK for Java 2.x da API.

Excluir um balanceador de carga

O exemplo de código a seguir mostra como excluir um balanceador de carga do ELB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Deletes a load balancer.
   public void deleteLoadBalancer(String lbName) {
       try {
           // Use a waiter to delete the Load Balancer.
           DescribeLoadBalancersResponse res = getLoadBalancerClient()
                   .describeLoadBalancers(describe -> describe.names(lbName));
           ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
           DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                   .loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                   .build();

           getLoadBalancerClient().deleteLoadBalancer(
                   builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
           WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                   .waitUntilLoadBalancersDeleted(request);
           waiterResponse.matched().response().ifPresent(System.out::println);

       } catch (ElasticLoadBalancingV2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
       }
       System.out.println(lbName + " was deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteLoadBalancera Referência AWS SDK for Java 2.x da API.

Excluir um grupo de destino

O exemplo de código a seguir mostra como excluir um grupo de destino do ELB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Deletes the target group.
   public void deleteTargetGroup(String targetGroupName) {
       try {
           DescribeTargetGroupsResponse res = getLoadBalancerClient()
                   .describeTargetGroups(describe ->
describe.names(targetGroupName));
           getLoadBalancerClient()
                   .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
       } catch (ElasticLoadBalancingV2Exception e) {
           System.err.println(e.awsErrorDetails().errorMessage());
       }
       System.out.println(targetGroupName + " was deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteTargetGroupa Referência AWS SDK for Java 2.x da API.

Obter a integridade de um grupo de destino

O exemplo de código a seguir mostra como obter a integridade de instâncias em um grupo de destino do ELB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Checks the health of the instances in the target group.
   public List<TargetHealthDescription> checkTargetHealth(String targetGroupName) {
       DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
               .names(targetGroupName)
               .build();

       DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

       DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()
               .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
               .build();

       DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
       return healthResponse.targetHealthDescriptions();
   }
```

- Para obter detalhes da API, consulte DescribeTargetHealtha Referência AWS SDK for Java 2.x da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
```

```
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-prof-
bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException, InterruptedException
 {
        Scanner in = new Scanner(System.in);
        Database database = new Database();
        AutoScaler autoScaler = new AutoScaler();
        LoadBalancer loadBalancer = new LoadBalancer();

        System.out.println(DASHES);
        System.out.println("Welcome to the demonstration of How to Build and Manage
 a Resilient Service!");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("A - SETUP THE RESOURCES");
        System.out.println("Press Enter when you're ready to start deploying
 resources.");
        in.nextLine();
        deploy(loadBalancer);
        System.out.println(DASHES);
        System.out.println(DASHES);
        System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
        System.out.println("Press Enter when you're ready.");
        in.nextLine();
        demo(loadBalancer);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("C - DELETE THE RESOURCES");
        System.out.println("""
```

```
                This concludes the demo of how to build and manage a resilient
service.
                To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources
                that were created for this demo.
                """);

        System.out.println("\n Do you want to delete the resources (y/n)? ");
        String userInput = in.nextLine().trim().toLowerCase(); // Capture user input

        if (userInput.equals("y")) {
            // Delete resources here
            deleteResources(loadBalancer, autoScaler, database);
            System.out.println("Resources deleted.");
        } else {
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }
```

```
   private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
       Scanner in = new Scanner(System.in);
       System.out.println(
               """
                       For this demo, we'll use the AWS SDK for Java (v2) to create
several AWS resources
                       to set up a load-balanced web service endpoint and explore
some ways to make it resilient
                       against various kinds of failures.

                       Some of the resources create by this demo are:
                       \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                       \t* An EC2 launch template that defines EC2 instances that
each contain a Python web server.
                       \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                       \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                       """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when an
instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
               run a web server, such as Apache, with least-privileged credentials.
```

```
                The template also defines an IAM policy that each instance uses to
assume a role that grants
                permissions to access the DynamoDB recommendation table and Systems
Manager parameters
                that control the flow of the demo.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load balancer.
The target group
```

```
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets, targetGroupArn,
lbName, port, protocol);
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul = loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(), StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group for
your default VPC must
                            allow access from this computer. You can either add it
automatically from this
```

```
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security group
are configured correctly and that");
            System.out.println("you can successfully make a GET request to the load
balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
```

```
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and shows
how using a resilient
                        architecture can keep the web service running in spite of
these failures.

                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager parameter
named self.param_helper.table.
                        To simulate a failure of the recommendation service, let's
set this parameter to name a non-existent table.
                       """);
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        System.out.println(
                """
                        \nNow, sending a GET request to the load balancer endpoint
returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health checks
don't check for failure of the recommendation service.
                       """);
        demoChoices(loadBalancer);

        System.out.println(
                """
                       Instead of failing when the recommendation service fails,
the web service can return a static response.
```

```
                        While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                        """);
        paramHelper.put(paramHelper.failureResponse, "static");

        System.out.println("""
                Now, sending a GET request to the load balancer endpoint returns a
static response.
                The service still reports as healthy because health checks are still
shallow.
                """);
        demoChoices(loadBalancer);

        System.out.println("Let's reinstate the recommendation service.");
        paramHelper.put(paramHelper.tableName, paramHelper.dyntable);

        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance id
value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId = autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " + profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
```

```
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on for
recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto Scaling
instance health, because it
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy
```

```
                        instance is to terminate it and let the auto scaler start a
new instance to replace it.
                        """);
       autoScaler.terminateInstance(badInstanceId);

       System.out.println("""
               Even while the instance is terminating and the new instance is
starting, sending a GET
               request to the web service continues to get a successful
recommendation response because
               the load balancer routes requests to the healthy instances. After
the replacement instance
               starts and reports as healthy, it is included in the load balancing
rotation.
               Note that terminating and replacing an instance typically takes
several minutes, during which time you
               can see the changing health check status until the new instance is
running and healthy.
               """);

       demoChoices(loadBalancer);
       System.out.println(
               "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       demoChoices(loadBalancer);
       paramHelper.reset();
   }

   public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
       String[] actions = {
               "Send a GET request to the load balancer endpoint.",
               "Check the health of load balancer targets.",
               "Go to the next part of the demo."
       };
       Scanner scanner = new Scanner(System.in);

       while (true) {
           System.out.println("-".repeat(88));
           System.out.println("See the current state of the service by selecting
one of the following choices:");
           for (int i = 0; i < actions.length; i++) {
```

```
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();

                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode = response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
```

```
                    case 1 -> {
                        System.out.println("\nChecking the health of load balancer
 targets:\n");
                        List<TargetHealthDescription> health =
 loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
 target.target().id(),
                                        target.target().port(),
 target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the health
 check to update
                                after changes are made.
                                """);
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value between
 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {
```

```
    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }

    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
```

```
     * Terminates and instances in an EC2 Auto Scaling group. After an instance is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }

    /**
     * Replaces the profile associated with a running instance. After the profile is
     * replaced, the instance is rebooted to ensure that it uses the new profile.
     * When
     * the instance is ready, Systems Manager is used to restart the Python web
     * server.
     */
    public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
            throws InterruptedException {
        // Create an IAM instance profile specification.
        software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
                .builder()
                .name(newInstanceProfileName) // Make sure 'newInstanceProfileName'
is a valid IAM Instance Profile
                                              // name.
                .build();

        // Replace the IAM instance profile association for the EC2 instance.
        ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
                .builder()
                .iamInstanceProfile(iamInstanceProfile)
                .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
                .build();
```

```
        try {
            getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
            // Handle the response as needed.
        } catch (Ec2Exception e) {
            // Handle exceptions, log, or report the error.
            System.err.println("Error: " + e.getMessage());
        }
        System.out.format("Replaced instance profile for association %s with profile
%s.", profileAssociationId,
                newInstanceProfileName);
        TimeUnit.SECONDS.sleep(15);
        boolean instReady = false;
        int tries = 0;

        // Reboot after 60 seconds
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
```

```
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress) {
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);
```

```
            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }

    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network, you
     * must instead specify a prefix list ID. You can also temporarily open the port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();
```

```
            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse = getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup : securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " + secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " + ipPermission);
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to be
open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or to
a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }
```

```
        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
        software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();
```

```
        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();
```

```
        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response = getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();
```

```
        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to the
policy.
```

```
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM role
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
 DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
 ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
 iamClient.listInstanceProfilesForRole(listRolesRequest);
```

```
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
 listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
 RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance profile
 " + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
 DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
```

```
    public List<TargetHealthDescription> checkTargetHealth(String targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
DescribeTargetHealthRequest.builder()
                .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
```

```
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws IOException,
InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
```

```
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
     * how
     * the load balancer forward requests to instances in the group and how instance
     * health is checked.
     */
    public String createTargetGroup(String protocol, int port, String vpcId, String
targetGroupName) {
        CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
                .healthCheckPath("/healthcheck")
                .healthCheckTimeoutSeconds(5)
                .port(port)
                .vpcId(vpcId)
                .name(targetGroupName)
                .protocol(protocol)
                .build();

        CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
        String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
        String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
        System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
        return targetGroupArn;
    }

    /*
```

```
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
                   .scheme("internet-facing")
                   .build();

           // Create and wait for the load balancer to become available.
           CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
           String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

           ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
           DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                   .loadBalancerArns(lbARN)
                   .build();

           System.out.println("Waiting for Load Balancer " + lbName + " to become
available.");
           WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                   .waitUntilLoadBalancerAvailable(request);
           waiterResponse.matched().response().ifPresent(System.out::println);
           System.out.println("Load Balancer " + lbName + " is available.");

           // Get the DNS name (endpoint) of the load balancer.
           String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
           System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

           // Create a listener for the load balance.
```

```
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

 .loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
```

```
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;

        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " + e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended, such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException {
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
```

```
                                .attributeName("ItemId")
                                .attributeType(ScalarAttributeType.N)
                                .build())
                .keySchema(
                        KeySchemaElement.builder()
                                .attributeName("MediaType")
                                .keyType(KeyType.HASH)
                                .build(),
                        KeySchemaElement.builder()
                                .attributeName("ItemId")
                                .keyType(KeyType.RANGE)
                                .build())
                .provisionedThroughput(
                        ProvisionedThroughput.builder()
                                .readCapacityUnits(5L)
                                .writeCapacityUnits(5L)
                                .build())
                .build();

        getDynamoDbClient().createTable(createTableRequest);
        System.out.println("Creating table " + tableName + "...");

        // Wait until the Amazon DynamoDB table is created.
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                .tableName(tableName)
                .build();

        WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        System.out.println("Table " + tableName + " created.");

        // Add records to the table.
        populateTable(fileName, tableName);
    }
}

public void deleteTable(String tableName) {
    getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
    System.out.println("Table " + tableName + " deleted.");
}

// Populates the table with data located in a JSON file using the DynamoDB
// enhanced client.
```

```
    public void populateTable(String fileName, String tableName) throws IOException
 {
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable = enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
```

```
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();

        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups

- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

MediaStore exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with MediaStore.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Cria um contêiner

O exemplo de código a seguir mostra como criar um contêiner do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.model.CreateContainerRequest;
import software.amazon.awssdk.services.mediastore.model.CreateContainerResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateContainer {
    public static long sleepTime = 10;

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
```

```
                .region(region)
                .build();

        createMediaContainer(mediaStoreClient, containerName);
        mediaStoreClient.close();
    }

    public static void createMediaContainer(MediaStoreClient mediaStoreClient,
 String containerName) {
        try {
            CreateContainerRequest containerRequest =
 CreateContainerRequest.builder()
                    .containerName(containerName)
                    .build();

            CreateContainerResponse containerResponse =
 mediaStoreClient.createContainer(containerRequest);
            String status = containerResponse.container().status().toString();
            while (!status.equalsIgnoreCase("Active")) {
                status = DescribeContainer.checkContainer(mediaStoreClient,
 containerName);
                System.out.println("Status - " + status);
                Thread.sleep(sleepTime * 1000);
            }

            System.out.println("The container ARN value is " +
 containerResponse.container().arn());
            System.out.println("Finished ");

        } catch (MediaStoreException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateContainera Referência AWS SDK for Java 2.x da API.

Excluir um contêiner

O exemplo de código a seguir mostra como excluir um contêiner do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.model.CreateContainerRequest;
import software.amazon.awssdk.services.mediastore.model.CreateContainerResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateContainer {
    public static long sleepTime = 10;

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to create.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
```

```
                .region(region)
                .build();

        createMediaContainer(mediaStoreClient, containerName);
        mediaStoreClient.close();
    }

    public static void createMediaContainer(MediaStoreClient mediaStoreClient,
 String containerName) {
        try {
            CreateContainerRequest containerRequest =
 CreateContainerRequest.builder()
                    .containerName(containerName)
                    .build();

            CreateContainerResponse containerResponse =
 mediaStoreClient.createContainer(containerRequest);
            String status = containerResponse.container().status().toString();
            while (!status.equalsIgnoreCase("Active")) {
                status = DescribeContainer.checkContainer(mediaStoreClient,
 containerName);
                System.out.println("Status - " + status);
                Thread.sleep(sleepTime * 1000);
            }

            System.out.println("The container ARN value is " +
 containerResponse.container().arn());
            System.out.println("Finished ");

        } catch (MediaStoreException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteContainera Referência AWS SDK for Java 2.x da API.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.services.mediastoredata.model.DeleteObjectRequest;
import software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteObject {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """

                Usage:    <completePath> <containerName>

                Where:
                   completePath - The path (including the container) of the item to
 delete.
                   containerName - The name of the container.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String completePath = args[0];
        String containerName = args[1];
        Region region = Region.US_EAST_1;
        URI uri = new URI(getEndpoint(containerName));

        MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
                .endpointOverride(uri)
                .region(region)
                .build();

        deleteMediaObject(mediaStoreData, completePath);
        mediaStoreData.close();
    }

    public static void deleteMediaObject(MediaStoreDataClient mediaStoreData, String
completePath) {
        try {
            DeleteObjectRequest deleteObjectRequest = DeleteObjectRequest.builder()
                    .path(completePath)
                    .build();

            mediaStoreData.deleteObject(deleteObjectRequest);

        } catch (MediaStoreDataException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    private static String getEndpoint(String containerName) {
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        DescribeContainerRequest containerRequest =
DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
mediaStoreClient.describeContainer(containerRequest);
        mediaStoreClient.close();
```

```
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte DeleteObjecta Referência AWS SDK for Java 2.x da API.

Descrever um contêiner

O exemplo de código a seguir mostra como descrever um contêiner do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeContainer {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <containerName>

                Where:
                   containerName - The name of the container to describe.
```

```
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String containerName = args[0];
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        System.out.println("Status is " + checkContainer(mediaStoreClient,
 containerName));
        mediaStoreClient.close();
    }

    public static String checkContainer(MediaStoreClient mediaStoreClient, String
 containerName) {
        try {
            DescribeContainerRequest describeContainerRequest =
 DescribeContainerRequest.builder()
                    .containerName(containerName)
                    .build();

            DescribeContainerResponse containerResponse =
 mediaStoreClient.describeContainer(describeContainerRequest);
            System.out.println("The container name is " +
 containerResponse.container().name());
            System.out.println("The container ARN is " +
 containerResponse.container().arn());
            return containerResponse.container().status().toString();

        } catch (MediaStoreException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte DescribeContainera Referência AWS SDK for Java 2.x da API.

Receber um objeto

O exemplo de código a seguir mostra como receber um objeto do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.ResponseInputStream;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.services.mediastoredata.model.GetObjectRequest;
import software.amazon.awssdk.services.mediastoredata.model.GetObjectResponse;
import software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetObject {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """
```

```
                Usage:    <completePath> <containerName> <savePath>

                Where:
                   completePath - The path of the object in the container (for
example, Videos5/sampleVideo.mp4).
                   containerName - The name of the container.
                   savePath - The path on the local drive where the file is saved,
including the file name (for example, C:/AWS/myvid.mp4).
                """;

       if (args.length != 3) {
           System.out.println(usage);
           System.exit(1);
       }

       String completePath = args[0];
       String containerName = args[1];
       String savePath = args[2];

       Region region = Region.US_EAST_1;
       URI uri = new URI(getEndpoint(containerName));
       MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
               .endpointOverride(uri)
               .region(region)
               .build();

       getMediaObject(mediaStoreData, completePath, savePath);
       mediaStoreData.close();
   }

   public static void getMediaObject(MediaStoreDataClient mediaStoreData, String
completePath, String savePath) {

       try {
           GetObjectRequest objectRequest = GetObjectRequest.builder()
                   .path(completePath)
                   .build();

           // Write out the data to a file.
           ResponseInputStream<GetObjectResponse> data =
mediaStoreData.getObject(objectRequest);
           byte[] buffer = new byte[data.available()];
           data.read(buffer);
```

```
            File targetFile = new File(savePath);
            OutputStream outStream = new FileOutputStream(targetFile);
            outStream.write(buffer);
            System.out.println("The data was written to " + savePath);

        } catch (MediaStoreDataException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    private static String getEndpoint(String containerName) {
        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        DescribeContainerRequest containerRequest =
 DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
 mediaStoreClient.describeContainer(containerRequest);
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Java 2.x da API.

Listar contêineres

O exemplo de código a seguir mostra como listar contêineres do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastore.model.Container;
import software.amazon.awssdk.services.mediastore.model.ListContainersResponse;
import software.amazon.awssdk.services.mediastore.model.MediaStoreException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListContainers {

    public static void main(String[] args) {

        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        listAllContainers(mediaStoreClient);
        mediaStoreClient.close();
    }

    public static void listAllContainers(MediaStoreClient mediaStoreClient) {
        try {
            ListContainersResponse containersResponse =
 mediaStoreClient.listContainers();
            List<Container> containers = containersResponse.containers();
            for (Container container : containers) {
                System.out.println("Container name is " + container.name());
            }

        } catch (MediaStoreException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte ListContainersa Referência AWS SDK for Java 2.x da API.

Colocar um objeto em um contêiner

O exemplo de código a seguir mostra como colocar um objeto em um contêiner do AWS Elemental MediaStore.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediastore.MediaStoreClient;
import software.amazon.awssdk.services.mediastoredata.MediaStoreDataClient;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.mediastoredata.model.PutObjectRequest;
import software.amazon.awssdk.services.mediastoredata.model.MediaStoreDataException;
import software.amazon.awssdk.services.mediastoredata.model.PutObjectResponse;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerRequest;
import software.amazon.awssdk.services.mediastore.model.DescribeContainerResponse;
import java.io.File;
import java.net.URI;
import java.net.URISyntaxException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutObject {
    public static void main(String[] args) throws URISyntaxException {
        final String USAGE = """
```

```
                To run this example, supply the name of a container, a file location
to use, and path in the container\s

                Ex: <containerName> <filePath> <completePath>
                """;

        if (args.length < 3) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String containerName = args[0];
        String filePath = args[1];
        String completePath = args[2];

        Region region = Region.US_EAST_1;
        URI uri = new URI(getEndpoint(containerName));
        MediaStoreDataClient mediaStoreData = MediaStoreDataClient.builder()
                .endpointOverride(uri)
                .region(region)
                .build();

        putMediaObject(mediaStoreData, filePath, completePath);
        mediaStoreData.close();
    }

    public static void putMediaObject(MediaStoreDataClient mediaStoreData, String
filePath, String completePath) {
        try {
            File myFile = new File(filePath);
            RequestBody requestBody = RequestBody.fromFile(myFile);

            PutObjectRequest objectRequest = PutObjectRequest.builder()
                    .path(completePath)
                    .contentType("video/mp4")
                    .build();

            PutObjectResponse response = mediaStoreData.putObject(objectRequest,
requestBody);
            System.out.println("The saved object is " +
response.storageClass().toString());

        } catch (MediaStoreDataException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String getEndpoint(String containerName) {

        Region region = Region.US_EAST_1;
        MediaStoreClient mediaStoreClient = MediaStoreClient.builder()
                .region(region)
                .build();

        DescribeContainerRequest containerRequest =
 DescribeContainerRequest.builder()
                .containerName(containerName)
                .build();

        DescribeContainerResponse response =
 mediaStoreClient.describeContainer(containerRequest);
        return response.container().endpoint();
    }
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Java 2.x da API.

OpenSearch Exemplos de serviços usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with OpenSearch Service.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um domínio

O exemplo de código a seguir mostra como criar um domínio OpenSearch de serviço.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.ClusterConfig;
import software.amazon.awssdk.services.opensearch.model.EBSOptions;
import software.amazon.awssdk.services.opensearch.model.VolumeType;
import software.amazon.awssdk.services.opensearch.model.NodeToNodeEncryptionOptions;
import software.amazon.awssdk.services.opensearch.model.CreateDomainRequest;
import software.amazon.awssdk.services.opensearch.model.CreateDomainResponse;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
```

```
                    domainName - The name of the domain to create.
                """";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        createNewDomain(searchClient, domainName);
        System.out.println("Done");
    }

    public static void createNewDomain(OpenSearchClient searchClient, String
domainName) {
        try {
            ClusterConfig clusterConfig = ClusterConfig.builder()
                    .dedicatedMasterEnabled(true)
                    .dedicatedMasterCount(3)
                    .dedicatedMasterType("t2.small.search")
                    .instanceType("t2.small.search")
                    .instanceCount(5)
                    .build();

            EBSOptions ebsOptions = EBSOptions.builder()
                    .ebsEnabled(true)
                    .volumeSize(10)
                    .volumeType(VolumeType.GP2)
                    .build();

            NodeToNodeEncryptionOptions encryptionOptions =
NodeToNodeEncryptionOptions.builder()
                    .enabled(true)
                    .build();

            CreateDomainRequest domainRequest = CreateDomainRequest.builder()
                    .domainName(domainName)
                    .engineVersion("OpenSearch_1.0")
                    .clusterConfig(clusterConfig)
```

```
                    .ebsOptions(ebsOptions)
                    .nodeToNodeEncryptionOptions(encryptionOptions)
                    .build();

            System.out.println("Sending domain creation request...");
            CreateDomainResponse createResponse =
 searchClient.createDomain(domainRequest);
            System.out.println("Domain status is " +
 createResponse.domainStatus().toString());
            System.out.println("Domain Id is " +
 createResponse.domainStatus().domainId());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateDomaina Referência AWS SDK for Java 2.x da API.

Excluir um domínio

O exemplo de código a seguir mostra como excluir um domínio OpenSearch de serviço.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;
import software.amazon.awssdk.services.opensearch.model.DeleteDomainRequest;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
                    domainName - The name of the domain to delete.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        deleteSpecificDomain(searchClient, domainName);
        System.out.println("Done");
    }

    public static void deleteSpecificDomain(OpenSearchClient searchClient, String
 domainName) {
        try {
            DeleteDomainRequest domainRequest = DeleteDomainRequest.builder()
                    .domainName(domainName)
                    .build();

            searchClient.deleteDomain(domainRequest);
            System.out.println(domainName + " was successfully deleted.");

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteDomaina Referência AWS SDK for Java 2.x da API.

Listar domínios

O exemplo de código a seguir mostra como listar domínios OpenSearch de serviço.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.DomainInfo;
import software.amazon.awssdk.services.opensearch.model.ListDomainNamesRequest;
import software.amazon.awssdk.services.opensearch.model.ListDomainNamesResponse;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;

import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListDomainNames {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
```

```
                .region(region)
                .credentialsProvider(ProfileCredentialsProvider.create())
                .build();
        listAllDomains(searchClient);
        System.out.println("Done");
    }

    public static void listAllDomains(OpenSearchClient searchClient) {
        try {
            ListDomainNamesRequest namesRequest = ListDomainNamesRequest.builder()
                    .engineType("OpenSearch")
                    .build();

            ListDomainNamesResponse response =
 searchClient.listDomainNames(namesRequest);
            List<DomainInfo> domainInfoList = response.domainNames();
            for (DomainInfo domain : domainInfoList)
                System.out.println("Domain name is " + domain.domainName());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListDomainNamesa Referência AWS SDK for Java 2.x da API.

Modificar uma configuração de cluster

O exemplo de código a seguir mostra como modificar a configuração de um cluster de um domínio de OpenSearch serviço.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.opensearch.OpenSearchClient;
import software.amazon.awssdk.services.opensearch.model.ClusterConfig;
import software.amazon.awssdk.services.opensearch.model.OpenSearchException;
import software.amazon.awssdk.services.opensearch.model.UpdateDomainConfigRequest;
import software.amazon.awssdk.services.opensearch.model.UpdateDomainConfigResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateDomain {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainName>

                Where:
                    domainName - The name of the domain to update.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainName = args[0];
        Region region = Region.US_EAST_1;
        OpenSearchClient searchClient = OpenSearchClient.builder()
                .region(region)
                .build();

        updateSpecificDomain(searchClient, domainName);
        System.out.println("Done");
    }
```

```
    public static void updateSpecificDomain(OpenSearchClient searchClient, String
 domainName) {
        try {
            ClusterConfig clusterConfig = ClusterConfig.builder()
                    .instanceCount(3)
                    .build();

            UpdateDomainConfigRequest updateDomainConfigRequest =
 UpdateDomainConfigRequest.builder()
                    .domainName(domainName)
                    .clusterConfig(clusterConfig)
                    .build();

            System.out.println("Sending domain update request...");
            UpdateDomainConfigResponse updateResponse =
 searchClient.updateDomainConfig(updateDomainConfigRequest);
            System.out.println("Domain update response from Amazon OpenSearch
 Service:");
            System.out.println(updateResponse.toString());

        } catch (OpenSearchException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateDomainConfiga Referência AWS SDK for Java 2.x da API.

EventBridge exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá EventBridge

O exemplo de código a seguir mostra como começar a usar o EventBridge.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 */
public class HelloEventBridge {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        EventBridgeClient eventBrClient = EventBridgeClient.builder()
                .region(region)
                .build();

        listBuses(eventBrClient);
        eventBrClient.close();
    }

    public static void listBuses(EventBridgeClient eventBrClient) {
        try {
            ListEventBusesRequest busesRequest = ListEventBusesRequest.builder()
                    .limit(10)
                    .build();
```

```
            ListEventBusesResponse response =
 eventBrClient.listEventBuses(busesRequest);
            List<EventBus> buses = response.eventBuses();
            for (EventBus bus : buses) {
                System.out.println("The name of the event bus is: " + bus.name());
                System.out.println("The ARN of the event bus is: " + bus.arn());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListEventBusesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicione um tópico do Amazon SNS como um destino para uma regra.

```
   // Add a rule which triggers an SNS target when a file is uploaded to an S3
   // bucket.
   public static void addSnsEventRule(EventBridgeClient eventBrClient, String
ruleName, String topicArn,
           String topicName, String eventRuleName, String bucketName) {
       String targetID = java.util.UUID.randomUUID().toString();
       Target myTarget = Target.builder()
               .id(targetID)
               .arn(topicArn)
               .build();

       List<Target> targets = new ArrayList<>();
       targets.add(myTarget);
       PutTargetsRequest request = PutTargetsRequest.builder()
               .eventBusName(null)
               .targets(targets)
               .rule(ruleName)
               .build();

       eventBrClient.putTargets(request);
       System.out.println("Added event rule " + eventRuleName + " with Amazon SNS
target " + topicName + " for bucket "
               + bucketName + ".");
   }
```

Adicione um transformador de entrada a um destino para uma regra.

```
   public static void updateCustomRuleTargetWithTransform(EventBridgeClient
eventBrClient, String topicArn,
           String ruleName) {
       String targetId = java.util.UUID.randomUUID().toString();
       InputTransformer inputTransformer = InputTransformer.builder()
               .inputTemplate("\"Notification: sample event was received.\"")
               .build();

       Target target = Target.builder()
               .id(targetId)
               .arn(topicArn)
               .inputTransformer(inputTransformer)
               .build();

       try {
```

```
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);
        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutTargetsa Referência AWS SDK for Java 2.x da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma regra agendada

```
   public static void createEBRule(EventBridgeClient eventBrClient, String
ruleName, String cronExpression) {
       try {
           PutRuleRequest ruleRequest = PutRuleRequest.builder()
                   .name(ruleName)
                   .eventBusName("default")
                   .scheduleExpression(cronExpression)
                   .state("ENABLED")
                   .description("A test rule that runs on a schedule created by the
Java API")
                   .build();
```

```
            PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
            System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Criar uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
    // Create a new event rule that triggers when an Amazon S3 object is created in
    // a bucket.
    public static void addEventRule(EventBridgeClient eventBrClient, String roleArn,
String bucketName,
            String eventRuleName) {
        String pattern = "{\n" +
                "  \"source\": [\"aws.s3\"],\n" +
                "  \"detail-type\": [\"Object Created\"],\n" +
                "  \"detail\": {\n" +
                "    \"bucket\": {\n" +
                "      \"name\": [\"" + bucketName + "\"]\n" +
                "    }\n" +
                "  }\n" +
                "}";

        try {
            PutRuleRequest ruleRequest = PutRuleRequest.builder()
                    .description("Created by using the AWS SDK for Java v2")
                    .name(eventRuleName)
                    .eventPattern(pattern)
                    .roleArn(roleArn)
                    .build();

            PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
            System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte PutRulea Referência AWS SDK for Java 2.x da API.

Excluir uma regra

O exemplo de código a seguir mostra como excluir uma EventBridge regra da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteRuleByName(EventBridgeClient eventBrClient, String
ruleName) {
       DeleteRuleRequest ruleRequest = DeleteRuleRequest.builder()
               .name(ruleName)
               .build();

       eventBrClient.deleteRule(ruleRequest);
       System.out.println("Successfully deleted the rule");
   }
```

- Para obter detalhes da API, consulte DeleteRulea Referência AWS SDK for Java 2.x da API.

Descrever uma regra

O exemplo de código a seguir mostra como descrever uma EventBridge regra da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkRule(EventBridgeClient eventBrClient, String
eventRuleName) {
       try {
           DescribeRuleRequest ruleRequest = DescribeRuleRequest.builder()
                   .name(eventRuleName)
                   .build();

           DescribeRuleResponse response = eventBrClient.describeRule(ruleRequest);
           System.out.println("The state of the rule is " +
response.stateAsString());

       } catch (EventBridgeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DescribeRulea Referência AWS SDK for Java 2.x da API.

Desabilitar uma regra

O exemplo de código a seguir mostra como desativar uma EventBridge regra da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desabilitar uma regra usando o nome da regra.

```
    public static void changeRuleState(EventBridgeClient eventBrClient, String
eventRuleName, Boolean isEnabled) {
        try {
            if (!isEnabled) {
                System.out.println("Disabling the rule: " + eventRuleName);
                DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();

                eventBrClient.disableRule(ruleRequest);
            } else {
                System.out.println("Enabling the rule: " + eventRuleName);
                EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();
                eventBrClient.enableRule(ruleRequest);
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DisableRulea Referência AWS SDK for Java 2.x da API.

Habilitar uma regra

O exemplo de código a seguir mostra como habilitar uma EventBridge regra da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilitar uma regra usando o nome da regra.

```
    public static void changeRuleState(EventBridgeClient eventBrClient, String
eventRuleName, Boolean isEnabled) {
        try {
            if (!isEnabled) {
                System.out.println("Disabling the rule: " + eventRuleName);
                DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();

                eventBrClient.disableRule(ruleRequest);
            } else {
                System.out.println("Enabling the rule: " + eventRuleName);
                EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();
                eventBrClient.enableRule(ruleRequest);
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte EnableRulea Referência AWS SDK for Java 2.x da API.

Listar nomes de regras para um destino

O exemplo de código a seguir mostra como listar nomes de EventBridge regras da Amazon para um alvo.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos os nomes das regras usando a destino.

```
   public static void listTargetRules(EventBridgeClient eventBrClient, String
topicArn) {
       ListRuleNamesByTargetRequest ruleNamesByTargetRequest =
ListRuleNamesByTargetRequest.builder()
               .targetArn(topicArn)
               .build();

       ListRuleNamesByTargetResponse response =
eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest);
       List<String> rules = response.ruleNames();
       for (String rule : rules) {
           System.out.println("The rule name is " + rule);
       }
   }
```

- Para obter detalhes da API, consulte ListRuleNamesByTargeta Referência AWS SDK for Java 2.x da API.

Listar regras

O exemplo de código a seguir mostra como listar EventBridge as regras da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Habilitar uma regra usando o nome da regra.

```
   public static void listRules(EventBridgeClient eventBrClient) {
       try {
           ListRulesRequest rulesRequest = ListRulesRequest.builder()
                   .eventBusName("default")
                   .limit(10)
                   .build();

           ListRulesResponse response = eventBrClient.listRules(rulesRequest);
```

```
            List<Rule> rules = response.rules();
            for (Rule rule : rules) {
                System.out.println("The rule name is : " + rule.name());
                System.out.println("The rule description is : " +
rule.description());
                System.out.println("The rule state is : " + rule.stateAsString());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListRulesa Referência AWS SDK for Java 2.x da API.

Listar destinos para uma regra

O exemplo de código a seguir mostra como listar EventBridge alvos da Amazon para uma regra.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar todos as destinos de uma regra usando o nome da regra.

```
    public static void listTargets(EventBridgeClient eventBrClient, String ruleName)
{
        ListTargetsByRuleRequest ruleRequest = ListTargetsByRuleRequest.builder()
                .rule(ruleName)
                .build();

        ListTargetsByRuleResponse res =
eventBrClient.listTargetsByRule(ruleRequest);
        List<Target> targetsList = res.targets();
        for (Target target: targetsList) {
            System.out.println("Target ARN: "+target.arn());
```

```
        }
    }
```

- Para obter detalhes da API, consulte ListTargetsByRulea Referência AWS SDK for Java 2.x da API.

Remover destinos de uma regra

O exemplo de código a seguir mostra como remover EventBridge alvos da Amazon de uma regra.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover todos as destinos de uma regra usando o nome da regra.

```
   public static void deleteTargetsFromRule(EventBridgeClient eventBrClient, String
eventRuleName) {
       // First, get all targets that will be deleted.
       ListTargetsByRuleRequest request = ListTargetsByRuleRequest.builder()
               .rule(eventRuleName)
               .build();

       ListTargetsByRuleResponse response =
eventBrClient.listTargetsByRule(request);
       List<Target> allTargets = response.targets();

       // Get all targets and delete them.
       for (Target myTarget : allTargets) {
           RemoveTargetsRequest removeTargetsRequest =
RemoveTargetsRequest.builder()
                   .rule(eventRuleName)
                   .ids(myTarget.id())
                   .build();

           eventBrClient.removeTargets(removeTargetsRequest);
```

```
            System.out.println("Successfully removed the target");
        }
    }
```

- Para obter detalhes da API, consulte RemoveTargetsa Referência AWS SDK for Java 2.x da API.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void triggerCustomRule(EventBridgeClient eventBrClient, String
email) {
        String json = "{" +
                "\"UserEmail\": \"" + email + "\"," +
                "\"Message\": \"This event was generated by example code.\"," +
                "\"UtcTime\": \"Now.\"" +
                "}";

        PutEventsRequestEntry entry = PutEventsRequestEntry.builder()
                .source("ExampleSource")
                .detail(json)
                .detailType("ExampleType")
                .build();

        PutEventsRequest eventsRequest = PutEventsRequest.builder()
                .entries(entry)
                .build();

        eventBrClient.putEvents(eventsRequest);
    }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

Cenários

Conceitos básicos de regras e destinos

O código de exemplo a seguir mostra como:

- Criar uma regra e adicione um destino a ela.
- Habilitar e desabilitar regras.
- Listar e atualizar regras e destinos.
- Enviar eventos e limpar os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java code example performs the following tasks:
 *
 * This Java V2 example performs the following tasks with Amazon EventBridge:
 *
 * 1. Creates an AWS Identity and Access Management (IAM) role to use with
 * Amazon EventBridge.
 * 2. Amazon Simple Storage Service (Amazon S3) bucket with EventBridge events
 * enabled.
 * 3. Creates a rule that triggers when an object is uploaded to Amazon S3.
 * 4. Lists rules on the event bus.
 * 5. Creates a new Amazon Simple Notification Service (Amazon SNS) topic and
```

```
 * lets the user subscribe to it.
 * 6. Adds a target to the rule that sends an email to the specified topic.
 * 7. Creates an EventBridge event that sends an email when an Amazon S3 object
 * is created.
 * 8. Lists Targets.
 * 9. Lists the rules for the same target.
 * 10. Triggers the rule by uploading a file to the Amazon S3 bucket.
 * 11. Disables a specific rule.
 * 12. Checks and print the state of the rule.
 * 13. Adds a transform to the rule to change the text of the email.
 * 14. Enables a specific rule.
 * 15. Triggers the updated rule by uploading a file to the Amazon S3 bucket.
 * 16. Updates the rule to be a custom rule pattern.
 * 17. Sending an event to trigger the rule.
 * 18. Cleans up resources.
 *
 */
public class EventbridgeMVP {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException, IOException
 {
        final String usage = """

                Usage:
                    <roleName> <bucketName> <topicName> <eventRuleName>

                Where:
                    roleName - The name of the role to create.
                    bucketName - The Amazon Simple Storage Service (Amazon S3)
 bucket name to create.
                    topicName - The name of the Amazon Simple Notification Service
 (Amazon SNS) topic to create.
                    eventRuleName - The Amazon EventBridge rule name to create.
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String polJSON = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
```

```
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": \"events.amazonaws.com\"" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        Scanner sc = new Scanner(System.in);
        String roleName = args[0];
        String bucketName = args[1];
        String topicName = args[2];
        String eventRuleName = args[3];

        Region region = Region.US_EAST_1;
        EventBridgeClient eventBrClient = EventBridgeClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        Region regionGl = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(regionGl)
                .build();

        SnsClient snsClient = SnsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon EventBridge example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out
                .println("1. Create an AWS Identity and Access Management (IAM) role
to use with Amazon EventBridge.");
        String roleArn = createIAMRole(iam, roleName, polJSON);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("2. Create an S3 bucket with EventBridge events
enabled.");
        if (checkBucket(s3Client, bucketName)) {
            System.out.println("Bucket " + bucketName + " already exists. Ending
this scenario.");
            System.exit(1);
        }

        createBucket(s3Client, bucketName);
        Thread.sleep(3000);
        setBucketNotification(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Create a rule that triggers when an object is
uploaded to Amazon S3.");
        Thread.sleep(10000);
        addEventRule(eventBrClient, roleArn, bucketName, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. List rules on the event bus.");
        listRules(eventBrClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create a new SNS topic for testing and let the user
subscribe to the topic.");
        String topicArn = createSnsTopic(snsClient, topicName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Add a target to the rule that sends an email to the
specified topic.");
        System.out.println("Enter your email to subscribe to the Amazon SNS
topic:");
        String email = sc.nextLine();
        subEmail(snsClient, topicArn, email);
        System.out.println(
                "Use the link in the email you received to confirm your
subscription. Then, press Enter to continue.");
        sc.nextLine();
        System.out.println(DASHES);
```

```
        System.out.println(DASHES);
        System.out.println("7. Create an EventBridge event that sends an email when
an Amazon S3 object is created.");
        addSnsEventRule(eventBrClient, eventRuleName, topicArn, topicName,
eventRuleName, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 8. List Targets.");
        listTargets(eventBrClient, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 9. List the rules for the same target.");
        listTargetRules(eventBrClient, topicArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 10. Trigger the rule by uploading a file to the S3
bucket.");
        System.out.println("Press Enter to continue.");
        sc.nextLine();
        uploadTextFiletoS3(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Disable a specific rule.");
        changeRuleState(eventBrClient, eventRuleName, false);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Check and print the state of the rule.");
        checkRule(eventBrClient, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Add a transform to the rule to change the text of
the email.");
        updateSnsEventRule(eventBrClient, topicArn, eventRuleName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Enable a specific rule.");
        changeRuleState(eventBrClient, eventRuleName, true);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 15. Trigger the updated rule by uploading a file to the
S3 bucket.");
        System.out.println("Press Enter to continue.");
        sc.nextLine();
        uploadTextFiletoS3(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 16. Update the rule to be a custom rule pattern.");
        updateToCustomRule(eventBrClient, eventRuleName);
        System.out.println("Updated event rule " + eventRuleName + " to use a custom
pattern.");
        updateCustomRuleTargetWithTransform(eventBrClient, topicArn, eventRuleName);
        System.out.println("Updated event target " + topicArn + ".");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Sending an event to trigger the rule. This will
trigger a subscription email.");
        triggerCustomRule(eventBrClient, email);
        System.out.println("Events have been sent. Press Enter to continue.");
        sc.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Clean up resources.");
        System.out.println("Do you want to clean up resources (y/n)");
        String ans = sc.nextLine();
        if (ans.compareTo("y") == 0) {
            cleanupResources(eventBrClient, snsClient, s3Client, iam, topicArn,
eventRuleName, bucketName, roleName);
        } else {
            System.out.println("The resources will not be cleaned up. ");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Amazon EventBridge example scenario has successfully
completed.");
        System.out.println(DASHES);
    }
```

```
   public static void cleanupResources(EventBridgeClient eventBrClient, SnsClient
snsClient, S3Client s3Client,
           IamClient iam, String topicArn, String eventRuleName, String bucketName,
String roleName) {
       System.out.println("Removing all targets from the event rule.");
       deleteTargetsFromRule(eventBrClient, eventRuleName);
       deleteRuleByName(eventBrClient, eventRuleName);
       deleteSNSTopic(snsClient, topicArn);
       deleteS3Bucket(s3Client, bucketName);
       deleteRole(iam, roleName);
   }

   public static void deleteRole(IamClient iam, String roleName) {
       String policyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess";
       DetachRolePolicyRequest policyRequest = DetachRolePolicyRequest.builder()
               .policyArn(policyArn)
               .roleName(roleName)
               .build();

       iam.detachRolePolicy(policyRequest);
       System.out.println("Successfully detached policy " + policyArn + " from role
" + roleName);

       // Delete the role.
       DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
               .roleName(roleName)
               .build();

       iam.deleteRole(roleRequest);
       System.out.println("*** Successfully deleted " + roleName);
   }

   public static void deleteS3Bucket(S3Client s3Client, String bucketName) {
       // Remove all the objects from the S3 bucket.
       ListObjectsRequest listObjects = ListObjectsRequest.builder()
               .bucket(bucketName)
               .build();

       ListObjectsResponse res = s3Client.listObjects(listObjects);
       List<S3Object> objects = res.contents();
       ArrayList<ObjectIdentifier> toDelete = new ArrayList<>();

       for (S3Object myValue : objects) {
```

```
            toDelete.add(ObjectIdentifier.builder()
                    .key(myValue.key())
                    .build());
        }

        DeleteObjectsRequest dor = DeleteObjectsRequest.builder()
                .bucket(bucketName)
                .delete(Delete.builder()
                        .objects(toDelete).build())
                .build();

        s3Client.deleteObjects(dor);

        // Delete the S3 bucket.
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucketName)
                .build();

        s3Client.deleteBucket(deleteBucketRequest);
        System.out.println("You have deleted the bucket and the objects");
    }

    // Delete the SNS topic.
    public static void deleteSNSTopic(SnsClient snsClient, String topicArn) {
        try {
            DeleteTopicRequest request = DeleteTopicRequest.builder()
                    .topicArn(topicArn)
                    .build();

            DeleteTopicResponse result = snsClient.deleteTopic(request);
            System.out.println("\n\nStatus was " +
result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteRuleByName(EventBridgeClient eventBrClient, String
ruleName) {
        DeleteRuleRequest ruleRequest = DeleteRuleRequest.builder()
                .name(ruleName)
                .build();
```

```
        eventBrClient.deleteRule(ruleRequest);
        System.out.println("Successfully deleted the rule");
    }

    public static void deleteTargetsFromRule(EventBridgeClient eventBrClient, String
eventRuleName) {
        // First, get all targets that will be deleted.
        ListTargetsByRuleRequest request = ListTargetsByRuleRequest.builder()
                .rule(eventRuleName)
                .build();

        ListTargetsByRuleResponse response =
eventBrClient.listTargetsByRule(request);
        List<Target> allTargets = response.targets();

        // Get all targets and delete them.
        for (Target myTarget : allTargets) {
            RemoveTargetsRequest removeTargetsRequest =
RemoveTargetsRequest.builder()
                    .rule(eventRuleName)
                    .ids(myTarget.id())
                    .build();

            eventBrClient.removeTargets(removeTargetsRequest);
            System.out.println("Successfully removed the target");
        }
    }

    public static void triggerCustomRule(EventBridgeClient eventBrClient, String
email) {
        String json = "{" +
                "\"UserEmail\": \"" + email + "\"," +
                "\"Message\": \"This event was generated by example code.\"," +
                "\"UtcTime\": \"Now.\"" +
                "}";

        PutEventsRequestEntry entry = PutEventsRequestEntry.builder()
                .source("ExampleSource")
                .detail(json)
                .detailType("ExampleType")
                .build();

        PutEventsRequest eventsRequest = PutEventsRequest.builder()
```

```
                .entries(entry)
                .build();

        eventBrClient.putEvents(eventsRequest);
    }

    public static void updateCustomRuleTargetWithTransform(EventBridgeClient
 eventBrClient, String topicArn,
            String ruleName) {
        String targetId = java.util.UUID.randomUUID().toString();
        InputTransformer inputTransformer = InputTransformer.builder()
                .inputTemplate("\"Notification: sample event was received.\"")
                .build();

        Target target = Target.builder()
                .id(targetId)
                .arn(topicArn)
                .inputTransformer(inputTransformer)
                .build();

        try {
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);
        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void updateToCustomRule(EventBridgeClient eventBrClient, String
 ruleName) {
        String customEventsPattern = "{" +
                "\"source\": [\"ExampleSource\"]," +
                "\"detail-type\": [\"ExampleType\"]" +
                "}";

        PutRuleRequest request = PutRuleRequest.builder()
                .name(ruleName)
                .description("Custom test rule")
```

```
                .eventPattern(customEventsPattern)
                .build();

        eventBrClient.putRule(request);
    }

    // Update an Amazon S3 object created rule with a transform on the target.
    public static void updateSnsEventRule(EventBridgeClient eventBrClient, String
 topicArn, String ruleName) {
        String targetId = java.util.UUID.randomUUID().toString();
        Map<String, String> myMap = new HashMap<>();
        myMap.put("bucket", "$.detail.bucket.name");
        myMap.put("time", "$.time");

        InputTransformer inputTransformer = InputTransformer.builder()
                .inputTemplate("\"Notification: an object was uploaded to bucket
 <bucket> at <time>.\"")
                .inputPathsMap(myMap)
                .build();

        Target target = Target.builder()
                .id(targetId)
                .arn(topicArn)
                .inputTransformer(inputTransformer)
                .build();

        try {
            PutTargetsRequest targetsRequest = PutTargetsRequest.builder()
                    .rule(ruleName)
                    .targets(target)
                    .eventBusName(null)
                    .build();

            eventBrClient.putTargets(targetsRequest);

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkRule(EventBridgeClient eventBrClient, String
 eventRuleName) {
        try {
```

```
            DescribeRuleRequest ruleRequest = DescribeRuleRequest.builder()
                    .name(eventRuleName)
                    .build();

            DescribeRuleResponse response = eventBrClient.describeRule(ruleRequest);
            System.out.println("The state of the rule is " +
response.stateAsString());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void changeRuleState(EventBridgeClient eventBrClient, String
eventRuleName, Boolean isEnabled) {
        try {
            if (!isEnabled) {
                System.out.println("Disabling the rule: " + eventRuleName);
                DisableRuleRequest ruleRequest = DisableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();

                eventBrClient.disableRule(ruleRequest);
            } else {
                System.out.println("Enabling the rule: " + eventRuleName);
                EnableRuleRequest ruleRequest = EnableRuleRequest.builder()
                        .name(eventRuleName)
                        .build();
                eventBrClient.enableRule(ruleRequest);
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Create and upload a file to an S3 bucket to trigger an event.
    public static void uploadTextFiletoS3(S3Client s3Client, String bucketName)
throws IOException {
        // Create a unique file name.
        String fileSuffix = new SimpleDateFormat("yyyyMMddHHmmss").format(new
Date());
```

```
        String fileName = "TextFile" + fileSuffix + ".txt";

        File myFile = new File(fileName);
        FileWriter fw = new FileWriter(myFile.getAbsoluteFile());
        BufferedWriter bw = new BufferedWriter(fw);
        bw.write("This is a sample file for testing uploads.");
        bw.close();

        try {
            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(fileName)
                    .build();

            s3Client.putObject(putOb, RequestBody.fromFile(myFile));

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listTargetRules(EventBridgeClient eventBrClient, String
 topicArn) {
        ListRuleNamesByTargetRequest ruleNamesByTargetRequest =
 ListRuleNamesByTargetRequest.builder()
                .targetArn(topicArn)
                .build();

        ListRuleNamesByTargetResponse response =
 eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest);
        List<String> rules = response.ruleNames();
        for (String rule : rules) {
            System.out.println("The rule name is " + rule);
        }
    }

    public static void listTargets(EventBridgeClient eventBrClient, String ruleName)
 {
        ListTargetsByRuleRequest ruleRequest = ListTargetsByRuleRequest.builder()
                .rule(ruleName)
                .build();
```

```
        ListTargetsByRuleResponse res =
eventBrClient.listTargetsByRule(ruleRequest);
        List<Target> targetsList = res.targets();
        for (Target target: targetsList) {
            System.out.println("Target ARN: "+target.arn());
        }
    }

    // Add a rule which triggers an SNS target when a file is uploaded to an S3
    // bucket.
    public static void addSnsEventRule(EventBridgeClient eventBrClient, String
ruleName, String topicArn,
            String topicName, String eventRuleName, String bucketName) {
        String targetID = java.util.UUID.randomUUID().toString();
        Target myTarget = Target.builder()
                .id(targetID)
                .arn(topicArn)
                .build();

        List<Target> targets = new ArrayList<>();
        targets.add(myTarget);
        PutTargetsRequest request = PutTargetsRequest.builder()
                .eventBusName(null)
                .targets(targets)
                .rule(ruleName)
                .build();

        eventBrClient.putTargets(request);
        System.out.println("Added event rule " + eventRuleName + " with Amazon SNS
target " + topicName + " for bucket "
                + bucketName + ".");
    }

    public static void subEmail(SnsClient snsClient, String topicArn, String email)
{
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("email")
                    .endpoint(email)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
```

```
            System.out.println("Subscription ARN: " + result.subscriptionArn() + "\n
\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listRules(EventBridgeClient eventBrClient) {
        try {
            ListRulesRequest rulesRequest = ListRulesRequest.builder()
                    .eventBusName("default")
                    .limit(10)
                    .build();

            ListRulesResponse response = eventBrClient.listRules(rulesRequest);
            List<Rule> rules = response.rules();
            for (Rule rule : rules) {
                System.out.println("The rule name is : " + rule.name());
                System.out.println("The rule description is : " +
 rule.description());
                System.out.println("The rule state is : " + rule.stateAsString());
            }

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createSnsTopic(SnsClient snsClient, String topicName) {
        String topicPolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Sid\": \"EventBridgePublishTopic\"," +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": \"events.amazonaws.com\"" +
                "}," +
                "\"Resource\": \"*\"," +
                "\"Action\": \"sns:Publish\"" +
                "}]" +
```

```
                "}";

        Map<String, String> topicAttributes = new HashMap<>();
        topicAttributes.put("Policy", topicPolicy);
        CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                .name(topicName)
                .attributes(topicAttributes)
                .build();

        CreateTopicResponse response = snsClient.createTopic(topicRequest);
        System.out.println("Added topic " + topicName + " for email
subscriptions.");
        return response.topicArn();
    }

    // Create a new event rule that triggers when an Amazon S3 object is created in
    // a bucket.
    public static void addEventRule(EventBridgeClient eventBrClient, String roleArn,
String bucketName,
            String eventRuleName) {
        String pattern = "{\n" +
                "  \"source\": [\"aws.s3\"],\n" +
                "  \"detail-type\": [\"Object Created\"],\n" +
                "  \"detail\": {\n" +
                "    \"bucket\": {\n" +
                "      \"name\": [\"" + bucketName + "\"]\n" +
                "    }\n" +
                "  }\n" +
                "}";

        try {
            PutRuleRequest ruleRequest = PutRuleRequest.builder()
                    .description("Created by using the AWS SDK for Java v2")
                    .name(eventRuleName)
                    .eventPattern(pattern)
                    .roleArn(roleArn)
                    .build();

            PutRuleResponse ruleResponse = eventBrClient.putRule(ruleRequest);
            System.out.println("The ARN of the new rule is " +
ruleResponse.ruleArn());

        } catch (EventBridgeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }

    // Determine if the S3 bucket exists.
    public static Boolean checkBucket(S3Client s3Client, String bucketName) {
        try {
            HeadBucketRequest headBucketRequest = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.headBucket(headBucketRequest);
            return true;
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        return false;
    }

    // Set the S3 bucket notification configuration.
    public static void setBucketNotification(S3Client s3Client, String bucketName) {
        try {
            EventBridgeConfiguration eventBridgeConfiguration =
EventBridgeConfiguration.builder()
                    .build();

            NotificationConfiguration configuration =
NotificationConfiguration.builder()
                    .eventBridgeConfiguration(eventBridgeConfiguration)
                    .build();

            PutBucketNotificationConfigurationRequest configurationRequest =
PutBucketNotificationConfigurationRequest
                    .builder()
                    .bucket(bucketName)
                    .notificationConfiguration(configuration)
                    .skipDestinationValidation(true)
                    .build();

            s3Client.putBucketNotificationConfiguration(configurationRequest);
            System.out.println("Added bucket " + bucketName + " with EventBridge
events enabled.");

        } catch (S3Exception e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createBucket(S3Client s3Client, String bucketName) {
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
 s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String createIAMRole(IamClient iam, String rolename, String
 polJSON) {
        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(polJSON)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            AttachRolePolicyRequest rolePolicyRequest =
 AttachRolePolicyRequest.builder()
                    .roleName(rolename)
                    .policyArn("arn:aws:iam::aws:policy/
AmazonEventBridgeFullAccess")
```

```
                    .build();

            iam.attachRolePolicy(rolePolicyRequest);
            return response.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Exemplos do Forecast usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Forecast.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um conjunto de dados

O exemplo de código a seguir mostra como criar um conjunto de dados do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.CreateDatasetRequest;
import software.amazon.awssdk.services.forecast.model.Schema;
import software.amazon.awssdk.services.forecast.model.SchemaAttribute;
import software.amazon.awssdk.services.forecast.model.CreateDatasetResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateDataSet {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <name>\s

                Where:
                    name - The name of the data set.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String name = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        String myDataSetARN = createForecastDataSet(forecast, name);
        System.out.println("The ARN of the new data set is " + myDataSetARN);
        forecast.close();
    }

    public static String createForecastDataSet(ForecastClient forecast, String name)
{
        try {
            Schema schema = Schema.builder()
                    .attributes(getSchema())
                    .build();

            CreateDatasetRequest datasetRequest = CreateDatasetRequest.builder()
                    .datasetName(name)
                    .domain("CUSTOM")
                    .datasetType("RELATED_TIME_SERIES")
                    .dataFrequency("D")
                    .schema(schema)
                    .build();

            CreateDatasetResponse response = forecast.createDataset(datasetRequest);
            return response.datasetArn();

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }

        return "";
    }

    // Create a SchemaAttribute list required to create a data set.
    private static List<SchemaAttribute> getSchema() {

        List<SchemaAttribute> schemaList = new ArrayList<>();
        SchemaAttribute att1 = SchemaAttribute.builder()
                .attributeName("item_id")
                .attributeType("string")
                .build();

        SchemaAttribute att2 = SchemaAttribute.builder()
                .attributeName("timestamp")
                .attributeType("timestamp")
                .build();

        SchemaAttribute att3 = SchemaAttribute.builder()
                .attributeName("target_value")
                .attributeType("float")
                .build();

        // Push the SchemaAttribute objects to the List.
        schemaList.add(att1);
        schemaList.add(att2);
        schemaList.add(att3);
        return schemaList;
    }
}
```

- Para obter detalhes da API, consulte CreateDataseta Referência AWS SDK for Java 2.x da API.

Criar uma previsão

O exemplo de código a seguir mostra como criar uma previsão do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.CreateForecastRequest;
import software.amazon.awssdk.services.forecast.model.CreateForecastResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateForecast {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <name> <predictorArn>\s

                Where:
                    name - The name of the forecast.\s
                    predictorArn - The arn of the predictor to use.\s

                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String name = args[0];
        String predictorArn = args[1];
```

```
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        String forecastArn = createNewForecast(forecast, name, predictorArn);
        System.out.println("The ARN of the new forecast is " + forecastArn);
        forecast.close();
    }

    public static String createNewForecast(ForecastClient forecast, String name,
 String predictorArn) {
        try {
            CreateForecastRequest forecastRequest = CreateForecastRequest.builder()
                    .forecastName(name)
                    .predictorArn(predictorArn)
                    .build();

            CreateForecastResponse response =
 forecast.createForecast(forecastRequest);
            return response.forecastArn();

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateForecasta Referência AWS SDK for Java 2.x da API.

Excluir um conjunto de dados

O exemplo de código a seguir mostra como excluir um conjunto de dados do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DeleteDatasetRequest;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteDataset {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <datasetARN>\s

                Where:
                    datasetARN - The ARN of the data set to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String datasetARN = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
```

```
                .build();

        deleteForecastDataSet(forecast, datasetARN);
        forecast.close();
    }

    public static void deleteForecastDataSet(ForecastClient forecast, String
 myDataSetARN) {
        try {
            DeleteDatasetRequest deleteRequest = DeleteDatasetRequest.builder()
                    .datasetArn(myDataSetARN)
                    .build();

            forecast.deleteDataset(deleteRequest);
            System.out.println("The Data Set was deleted");

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteDataseta Referência AWS SDK for Java 2.x da API.

Excluir uma previsão

O exemplo de código a seguir mostra como excluir uma previsão do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DeleteDatasetRequest;
import software.amazon.awssdk.services.forecast.model.ForecastException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteDataset {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <datasetARN>\s

                Where:
                    datasetARN - The ARN of the data set to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String datasetARN = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        deleteForecastDataSet(forecast, datasetARN);
        forecast.close();
    }

    public static void deleteForecastDataSet(ForecastClient forecast, String
 myDataSetARN) {
        try {
            DeleteDatasetRequest deleteRequest = DeleteDatasetRequest.builder()
                    .datasetArn(myDataSetARN)
                    .build();

            forecast.deleteDataset(deleteRequest);
```

```
            System.out.println("The Data Set was deleted");

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteForecasta Referência AWS SDK for Java 2.x da API.

Descrever uma previsão

O exemplo de código a seguir mostra como descrever uma previsão do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DescribeForecastRequest;
import software.amazon.awssdk.services.forecast.model.DescribeForecastResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeForecast {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <forecastarn>\s

                Where:
                    forecastarn - The arn of the forecast (for example,
 "arn:aws:forecast:us-west-2:xxxxx322:forecast/my_forecast)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String forecastarn = args[0];
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        describe(forecast, forecastarn);
        forecast.close();
    }

    public static void describe(ForecastClient forecast, String forecastarn) {
        try {
            DescribeForecastRequest request = DescribeForecastRequest.builder()
                    .forecastArn(forecastarn)
                    .build();

            DescribeForecastResponse response = forecast.describeForecast(request);
            System.out.println("The name of the forecast is " +
 response.forecastName());

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeForecasta Referência AWS SDK for Java 2.x da API.

Listar os grupos de conjuntos de dados

O exemplo de código a seguir mostra como listar grupos de conjuntos de dados do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.DatasetGroupSummary;
import software.amazon.awssdk.services.forecast.model.ListDatasetGroupsRequest;
import software.amazon.awssdk.services.forecast.model.ListDatasetGroupsResponse;
import software.amazon.awssdk.services.forecast.model.ForecastException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListDataSetGroups {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        listDataGroups(forecast);
        forecast.close();
    }
```

```
    public static void listDataGroups(ForecastClient forecast) {
        try {
            ListDatasetGroupsRequest group = ListDatasetGroupsRequest.builder()
                    .maxResults(10)
                    .build();

            ListDatasetGroupsResponse response = forecast.listDatasetGroups(group);
            List<DatasetGroupSummary> groups = response.datasetGroups();
            for (DatasetGroupSummary myGroup : groups) {
                System.out.println("The Data Set name is " +
 myGroup.datasetGroupName());
            }

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListDatasetGroupsa Referência AWS SDK for Java 2.x da API.

Listar previsões

O exemplo de código a seguir mostra como listar previsões do Forecast.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.forecast.ForecastClient;
import software.amazon.awssdk.services.forecast.model.ListForecastsResponse;
import software.amazon.awssdk.services.forecast.model.ListForecastsRequest;
import software.amazon.awssdk.services.forecast.model.ForecastSummary;
import software.amazon.awssdk.services.forecast.model.ForecastException;
```

```
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListForecasts {

    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        ForecastClient forecast = ForecastClient.builder()
                .region(region)
                .build();

        listAllForeCasts(forecast);
        forecast.close();
    }

    public static void listAllForeCasts(ForecastClient forecast) {
        try {
            ListForecastsRequest request = ListForecastsRequest.builder()
                    .maxResults(10)
                    .build();

            ListForecastsResponse response = forecast.listForecasts(request);
            List<ForecastSummary> forecasts = response.forecasts();
            for (ForecastSummary forecastSummary : forecasts) {
                System.out.println("The name of the forecast is " +
 forecastSummary.forecastName());
            }

        } catch (ForecastException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListForecastsa Referência AWS SDK for Java 2.x da API.

Exemplos do AWS Glue usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.glue;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.ListJobsRequest;
import software.amazon.awssdk.services.glue.model.ListJobsResponse;
import java.util.List;

public class HelloGlue {
    public static void main(String[] args) {
        GlueClient glueClient = GlueClient.builder()
                .region(Region.US_EAST_1)
                .build();
```

```
        listJobs(glueClient);
    }

    public static void listJobs(GlueClient glueClient) {
        ListJobsRequest request = ListJobsRequest.builder()
                .maxResults(10)
                .build();
        ListJobsResponse response = glueClient.listJobs(request);
        List<String> jobList = response.jobNames();
        jobList.forEach(job -> {
            System.out.println("Job Name: " + job);
        });
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

O exemplo de código a seguir mostra como criar um crawler do AWS Glue.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.CreateCrawlerRequest;
```

```
import software.amazon.awssdk.services.glue.model.CrawlerTargets;
import software.amazon.awssdk.services.glue.model.GlueException;
import software.amazon.awssdk.services.glue.model.S3Target;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <IAM> <s3Path> <cron> <dbName> <crawlerName>

                Where:
                    IAM - The ARN of the IAM role that has AWS Glue and S3
 permissions.\s
                    s3Path - The Amazon Simple Storage Service (Amazon S3) target
 that contains data (for example, CSV data).
                    cron - A cron expression used to specify the schedule  (i.e.,
 cron(15 12 * * ? *).
                    dbName - The database name.\s
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String iam = args[0];
        String s3Path = args[1];
        String cron = args[2];
        String dbName = args[3];
        String crawlerName = args[4];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
```

```
                .region(region)
                .build();

        createGlueCrawler(glueClient, iam, s3Path, cron, dbName, crawlerName);
        glueClient.close();
    }

    public static void createGlueCrawler(GlueClient glueClient,
            String iam,
            String s3Path,
            String cron,
            String dbName,
            String crawlerName) {

        try {
            S3Target s3Target = S3Target.builder()
                    .path(s3Path)
                    .build();

            // Add the S3Target to a list.
            List<S3Target> targetList = new ArrayList<>();
            targetList.add(s3Target);

            CrawlerTargets targets = CrawlerTargets.builder()
                    .s3Targets(targetList)
                    .build();

            CreateCrawlerRequest crawlerRequest = CreateCrawlerRequest.builder()
                    .databaseName(dbName)
                    .name(crawlerName)
                    .description("Created by the AWS Glue Java API")
                    .targets(targets)
                    .role(iam)
                    .schedule(cron)
                    .build();

            glueClient.createCrawler(crawlerRequest);
            System.out.println(crawlerName + " was successfully created");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for Java 2.x da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler do AWS Glue.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetCrawlerRequest;
import software.amazon.awssdk.services.glue.model.GetCrawlerResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
```

```
                    <crawlerName>

                Where:
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String crawlerName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getSpecificCrawler(glueClient, crawlerName);
        glueClient.close();
    }

    public static void getSpecificCrawler(GlueClient glueClient, String crawlerName)
{
        try {
            GetCrawlerRequest crawlerRequest = GetCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            GetCrawlerResponse response = glueClient.getCrawler(crawlerRequest);
            Instant createDate = response.crawler().creationTime();

            // Convert the Instant to readable date
            DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the Crawler is " + createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for Java 2.x da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetDatabaseRequest;
import software.amazon.awssdk.services.glue.model.GetDatabaseResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetDatabase {
    public static void main(String[] args) {
        final String usage = """

                Usage:
```

```
                    <databaseName>

                Where:
                    databaseName - The name of the database.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String databaseName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getSpecificDatabase(glueClient, databaseName);
        glueClient.close();
    }

    public static void getSpecificDatabase(GlueClient glueClient, String
databaseName) {
        try {
            GetDatabaseRequest databasesRequest = GetDatabaseRequest.builder()
                    .name(databaseName)
                    .build();

            GetDatabaseResponse response = glueClient.getDatabase(databasesRequest);
            Instant createDate = response.database().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the database is " + createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for Java 2.x da API.

Obter tabelas de um banco de dados

O exemplo de código a seguir mostra como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GetTableRequest;
import software.amazon.awssdk.services.glue.model.GetTableResponse;
import software.amazon.awssdk.services.glue.model.GlueException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetTable {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <dbName> <tableName>

                Where:
                    dbName - The database name.\s
                    tableName - The name of the table.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbName = args[0];
        String tableName = args[1];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        getGlueTable(glueClient, dbName, tableName);
        glueClient.close();
    }

    public static void getGlueTable(GlueClient glueClient, String dbName, String
tableName) {
        try {
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .databaseName(dbName)
                    .name(tableName)
                    .build();

            GetTableResponse tableResponse = glueClient.getTable(tableRequest);
            Instant createDate = tableResponse.table().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the table is " + createDate);
```

```
        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for Java 2.x da API.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glue.GlueClient;
import software.amazon.awssdk.services.glue.model.GlueException;
import software.amazon.awssdk.services.glue.model.StartCrawlerRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class StartCrawler {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <crawlerName>
```

```
                Where:
                    crawlerName - The name of the crawler.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String crawlerName = args[0];
        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();

        startSpecificCrawler(glueClient, crawlerName);
        glueClient.close();
    }

    public static void startSpecificCrawler(GlueClient glueClient, String
 crawlerName) {
        try {
            StartCrawlerRequest crawlerRequest = StartCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.startCrawler(crawlerRequest);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for Java 2.x da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 *
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * To set up the resources, see this documentation topic:
 *
 * https://docs.aws.amazon.com/glue/latest/ug/tutorial-add-crawler.html
 *
 * This example performs the following tasks:
 *
 * 1. Create a database.
 * 2. Create a crawler.
 * 3. Get a crawler.
 * 4. Start a crawler.
 * 5. Get a database.
 * 6. Get tables.
 * 7. Create a job.
 * 8. Start a job run.
```

```
 * 9. List all jobs.
 * 10. Get job runs.
 * 11. Delete a job.
 * 12. Delete a database.
 * 13. Delete a crawler.
 */

public class GlueScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <iam> <s3Path> <cron> <dbName> <crawlerName> <jobName>\s

                Where:
                    iam - The ARN of the IAM role that has AWS Glue and S3
 permissions.\s
                    s3Path - The Amazon Simple Storage Service (Amazon S3) target
 that contains data (for example, CSV data).
                    cron - A cron expression used to specify the schedule  (i.e.,
 cron(15 12 * * ? *).
                    dbName - The database name.\s
                    crawlerName - The name of the crawler.\s
                    jobName - The name you assign to this job definition.
                    scriptLocation - The Amazon S3 path to a script that runs a job.
                    locationUri - The location of the database
                    bucketNameSc - The Amazon S3 bucket name used when creating a
 job
                    """;

        if (args.length != 9) {
            System.out.println(usage);
            System.exit(1);
        }

        String iam = args[0];
        String s3Path = args[1];
        String cron = args[2];
        String dbName = args[3];
        String crawlerName = args[4];
        String jobName = args[5];
        String scriptLocation = args[6];
```

```
        String locationUri = args[7];
        String bucketNameSc = args[8];

        Region region = Region.US_EAST_1;
        GlueClient glueClient = GlueClient.builder()
                .region(region)
                .build();
        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Glue scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create a database.");
        createDatabase(glueClient, dbName, locationUri);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a crawler.");
        createGlueCrawler(glueClient, iam, s3Path, cron, dbName, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get a crawler.");
        getSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Start a crawler.");
        startSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get a database.");
        getSpecificDatabase(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Wait 5 min for the tables to become available");
        TimeUnit.MINUTES.sleep(5);
        System.out.println("6. Get tables.");
        String myTableName = getGlueTables(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("7. Create a job.");
        createJob(glueClient, jobName, iam, scriptLocation);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Start a Job run.");
        startJob(glueClient, jobName, dbName, myTableName, bucketNameSc);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. List all jobs.");
        getAllJobs(glueClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get job runs.");
        getJobRuns(glueClient, jobName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Delete a job.");
        deleteJob(glueClient, jobName);
        System.out.println("*** Wait 5 MIN for the " + crawlerName + " to stop");
        TimeUnit.MINUTES.sleep(5);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Delete a database.");
        deleteDatabase(glueClient, dbName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Delete a crawler.");
        deleteSpecificCrawler(glueClient, crawlerName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Successfully completed the AWS Glue Scenario");
        System.out.println(DASHES);
    }

    public static void createDatabase(GlueClient glueClient, String dbName, String
 locationUri) {
        try {
```

```
            DatabaseInput input = DatabaseInput.builder()
                    .description("Built with the AWS SDK for Java V2")
                    .name(dbName)
                    .locationUri(locationUri)
                    .build();

            CreateDatabaseRequest request = CreateDatabaseRequest.builder()
                    .databaseInput(input)
                    .build();

            glueClient.createDatabase(request);
            System.out.println(dbName + " was successfully created");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createGlueCrawler(GlueClient glueClient,
            String iam,
            String s3Path,
            String cron,
            String dbName,
            String crawlerName) {

        try {
            S3Target s3Target = S3Target.builder()
                    .path(s3Path)
                    .build();

            List<S3Target> targetList = new ArrayList<>();
            targetList.add(s3Target);
            CrawlerTargets targets = CrawlerTargets.builder()
                    .s3Targets(targetList)
                    .build();

            CreateCrawlerRequest crawlerRequest = CreateCrawlerRequest.builder()
                    .databaseName(dbName)
                    .name(crawlerName)
                    .description("Created by the AWS Glue Java API")
                    .targets(targets)
                    .role(iam)
                    .schedule(cron)
```

```
                    .build();

            glueClient.createCrawler(crawlerRequest);
            System.out.println(crawlerName + " was successfully created");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getSpecificCrawler(GlueClient glueClient, String crawlerName)
{
        try {
            GetCrawlerRequest crawlerRequest = GetCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            boolean ready = false;
            while (!ready) {
                GetCrawlerResponse response = glueClient.getCrawler(crawlerRequest);
                String status = response.crawler().stateAsString();
                if (status.compareTo("READY") == 0) {
                    ready = true;
                }
                Thread.sleep(3000);
            }

            System.out.println("The crawler is now ready");

        } catch (GlueException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void startSpecificCrawler(GlueClient glueClient, String
crawlerName) {
        try {
            StartCrawlerRequest crawlerRequest = StartCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.startCrawler(crawlerRequest);
```

```
            System.out.println(crawlerName + " was successfully started!");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getSpecificDatabase(GlueClient glueClient, String
databaseName) {
        try {
            GetDatabaseRequest databasesRequest = GetDatabaseRequest.builder()
                    .name(databaseName)
                    .build();

            GetDatabaseResponse response = glueClient.getDatabase(databasesRequest);
            Instant createDate = response.database().createTime();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(createDate);
            System.out.println("The create date of the database is " + createDate);

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String getGlueTables(GlueClient glueClient, String dbName) {
        String myTableName = "";
        try {
            GetTablesRequest tableRequest = GetTablesRequest.builder()
                    .databaseName(dbName)
                    .build();

            GetTablesResponse response = glueClient.getTables(tableRequest);
            List<Table> tables = response.tableList();
            if (tables.isEmpty()) {
                System.out.println("No tables were returned");
```

```
            } else {
                for (Table table : tables) {
                    myTableName = table.name();
                    System.out.println("Table name is: " + myTableName);
                }
            }

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return myTableName;
    }

    public static void startJob(GlueClient glueClient, String jobName, String
 inputDatabase, String inputTable,
            String outBucket) {
        try {
            Map<String, String> myMap = new HashMap<>();
            myMap.put("--input_database", inputDatabase);
            myMap.put("--input_table", inputTable);
            myMap.put("--output_bucket_url", outBucket);

            StartJobRunRequest runRequest = StartJobRunRequest.builder()
                    .workerType(WorkerType.G_1_X)
                    .numberOfWorkers(10)
                    .arguments(myMap)
                    .jobName(jobName)
                    .build();

            StartJobRunResponse response = glueClient.startJobRun(runRequest);
            System.out.println("The request Id of the job is " +
 response.responseMetadata().requestId());

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createJob(GlueClient glueClient, String jobName, String iam,
 String scriptLocation) {
        try {
            JobCommand command = JobCommand.builder()
```

```
                    .pythonVersion("3")
                    .name("glueetl")
                    .scriptLocation(scriptLocation)
                    .build();

            CreateJobRequest jobRequest = CreateJobRequest.builder()
                    .description("A Job created by using the AWS SDK for Java V2")
                    .glueVersion("2.0")
                    .workerType(WorkerType.G_1_X)
                    .numberOfWorkers(10)
                    .name(jobName)
                    .role(iam)
                    .command(command)
                    .build();

            glueClient.createJob(jobRequest);
            System.out.println(jobName + " was successfully created.");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getAllJobs(GlueClient glueClient) {
        try {
            GetJobsRequest jobsRequest = GetJobsRequest.builder()
                    .maxResults(10)
                    .build();

            GetJobsResponse jobsResponse = glueClient.getJobs(jobsRequest);
            List<Job> jobs = jobsResponse.jobs();
            for (Job job : jobs) {
                System.out.println("Job name is : " + job.name());
                System.out.println("The job worker type is : " +
job.workerType().name());
            }

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static void getJobRuns(GlueClient glueClient, String jobName) {
        try {
            GetJobRunsRequest runsRequest = GetJobRunsRequest.builder()
                    .jobName(jobName)
                    .maxResults(20)
                    .build();

            boolean jobDone = false;
            while (!jobDone) {
                GetJobRunsResponse response = glueClient.getJobRuns(runsRequest);
                List<JobRun> jobRuns = response.jobRuns();
                for (JobRun jobRun : jobRuns) {
                    String jobState = jobRun.jobRunState().name();
                    if (jobState.compareTo("SUCCEEDED") == 0) {
                        System.out.println(jobName + " has succeeded");
                        jobDone = true;

                    } else if (jobState.compareTo("STOPPED") == 0) {
                        System.out.println("Job run has stopped");
                        jobDone = true;

                    } else if (jobState.compareTo("FAILED") == 0) {
                        System.out.println("Job run has failed");
                        jobDone = true;

                    } else if (jobState.compareTo("TIMEOUT") == 0) {
                        System.out.println("Job run has timed out");
                        jobDone = true;

                    } else {
                        System.out.println("*** Job run state is " +
jobRun.jobRunState().name());
                        System.out.println("Job run Id is " + jobRun.id());
                        System.out.println("The Glue version is " +
jobRun.glueVersion());
                    }
                    TimeUnit.SECONDS.sleep(5);
                }
            }

        } catch (GlueException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }

    public static void deleteJob(GlueClient glueClient, String jobName) {
        try {
            DeleteJobRequest jobRequest = DeleteJobRequest.builder()
                    .jobName(jobName)
                    .build();

            glueClient.deleteJob(jobRequest);
            System.out.println(jobName + " was successfully deleted");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteDatabase(GlueClient glueClient, String databaseName) {
        try {
            DeleteDatabaseRequest request = DeleteDatabaseRequest.builder()
                    .name(databaseName)
                    .build();

            glueClient.deleteDatabase(request);
            System.out.println(databaseName + " was successfully deleted");

        } catch (GlueException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteSpecificCrawler(GlueClient glueClient, String
crawlerName) {
        try {
            DeleteCrawlerRequest deleteCrawlerRequest =
DeleteCrawlerRequest.builder()
                    .name(crawlerName)
                    .build();

            glueClient.deleteCrawler(deleteCrawlerRequest);
            System.out.println(crawlerName + " was deleted");

        } catch (GlueException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

HealthImaging exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with HealthImaging.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma tag a um recurso

O exemplo de código a seguir mostra como adicionar uma tag a um HealthImaging recurso.

SDK para Java 2.x

```
   public static void tagMedicalImagingResource(MedicalImagingClient
medicalImagingClient,
           String resourceArn,
           Map<String, String> tags) {
       try {
           TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .tags(tags)
                   .build();

           medicalImagingClient.tagResource(tagResourceRequest);

           System.out.println("Tags have been added to the resource.");
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte TagResourcea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copiar um conjunto de imagens

O exemplo de código a seguir mostra como copiar um conjunto de HealthImaging imagens.

SDK para Java 2.x

```
   public static String copyMedicalImageSet(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String imageSetId,
           String latestVersionId,
           String destinationImageSetId,
           String destinationVersionId) {

       try {
           CopySourceImageSetInformation copySourceImageSetInformation =
CopySourceImageSetInformation.builder()
                   .latestVersionId(latestVersionId)
                   .build();

           CopyImageSetInformation.Builder copyImageSetBuilder =
CopyImageSetInformation.builder()
                   .sourceImageSet(copySourceImageSetInformation);

           if (destinationImageSetId != null) {
               copyImageSetBuilder =
copyImageSetBuilder.destinationImageSet(CopyDestinationImageSet.builder()
                       .imageSetId(destinationImageSetId)
                       .latestVersionId(destinationVersionId)
                       .build());
           }

           CopyImageSetRequest copyImageSetRequest = CopyImageSetRequest.builder()
                   .datastoreId(datastoreId)
                   .sourceImageSetId(imageSetId)
                   .copyImageSetInformation(copyImageSetBuilder.build())
                   .build();
```

```
            CopyImageSetResponse response =
medicalImagingClient.copyImageSet(copyImageSetRequest);

            return response.destinationImageSetProperties().imageSetId();
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
```

- Para obter detalhes da API, consulte CopyImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um datastore

O exemplo de código a seguir mostra como criar um armazenamento HealthImaging de dados.

SDK para Java 2.x

```
    public static String createMedicalImageDatastore(MedicalImagingClient
medicalImagingClient,
            String datastoreName) {
        try {
            CreateDatastoreRequest datastoreRequest =
CreateDatastoreRequest.builder()
                    .datastoreName(datastoreName)
                    .build();
            CreateDatastoreResponse response =
medicalImagingClient.createDatastore(datastoreRequest);
            return response.datastoreId();
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }

        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um datastore

O exemplo de código a seguir mostra como excluir um armazenamento HealthImaging de dados.

SDK para Java 2.x

```
   public static void deleteMedicalImagingDatastore(MedicalImagingClient
medicalImagingClient,
           String datastoreID) {
       try {
           DeleteDatastoreRequest datastoreRequest =
DeleteDatastoreRequest.builder()
                   .datastoreId(datastoreID)
                   .build();
           medicalImagingClient.deleteDatastore(datastoreRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um conjunto de imagens

O exemplo de código a seguir mostra como excluir um conjunto de HealthImaging imagens.

SDK para Java 2.x

```
   public static void deleteMedicalImageSet(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String imagesetId) {
       try {
           DeleteImageSetRequest deleteImageSetRequest =
DeleteImageSetRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId)
                   .build();

           medicalImagingClient.deleteImageSet(deleteImageSetRequest);

           System.out.println("The image set was deleted.");
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter um quadro de imagem

O exemplo de código a seguir mostra como obter um quadro de imagem.

SDK para Java 2.x

```
        public static void getMedicalImageSetFrame(MedicalImagingClient
medicalImagingClient,
                        String destinationPath,
                        String datastoreId,
                        String imagesetId,
                        String imageFrameId) {

                try {
                        GetImageFrameRequest getImageSetMetadataRequest =
GetImageFrameRequest.builder()
                                        .datastoreId(datastoreId)
                                        .imageSetId(imagesetId)

.imageFrameInformation(ImageFrameInformation.builder()
                                                        .imageFrameId(imageFrameId)
                                                        .build())
                                        .build();

medicalImagingClient.getImageFrame(getImageSetMetadataRequest,

FileSystems.getDefault().getPath(destinationPath));

                        System.out.println("Image frame downloaded to " +
destinationPath);
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
```

- Para obter detalhes da API, consulte GetImageFramea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do datastore

O exemplo de código a seguir mostra como obter propriedades do armazenamento de HealthImaging dados.

SDK para Java 2.x

```
   public static DatastoreProperties getMedicalImageDatastore(MedicalImagingClient
medicalImagingClient,
           String datastoreID) {
       try {
           GetDatastoreRequest datastoreRequest = GetDatastoreRequest.builder()
                   .datastoreId(datastoreID)
                   .build();
           GetDatastoreResponse response =
medicalImagingClient.getDatastore(datastoreRequest);
           return response.datastoreProperties();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte GetDatastorea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do conjunto de imagens

O exemplo de código a seguir mostra como obter as propriedades do conjunto de HealthImaging imagens.

SDK para Java 2.x

```
   public static GetImageSetResponse getMedicalImageSet(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String imagesetId,
           String versionId) {
       try {
           GetImageSetRequest.Builder getImageSetRequestBuilder =
GetImageSetRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId);

           if (versionId != null) {
               getImageSetRequestBuilder =
getImageSetRequestBuilder.versionId(versionId);
           }

           return
medicalImagingClient.getImageSet(getImageSetRequestBuilder.build());
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte GetImageSeta Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do trabalho de importação

O exemplo de código a seguir mostra como obter as propriedades do trabalho de importação.

SDK para Java 2.x

```
   public static DICOMImportJobProperties getDicomImportJob(MedicalImagingClient
medicalImagingClient,
           String datastoreId,
           String jobId) {

       try {
           GetDicomImportJobRequest getDicomImportJobRequest =
GetDicomImportJobRequest.builder()
                   .datastoreId(datastoreId)
                   .jobId(jobId)
                   .build();
           GetDicomImportJobResponse response =
medicalImagingClient.getDICOMImportJob(getDicomImportJobRequest);
           return response.jobProperties();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter metadados para um conjunto de imagem

O exemplo de código a seguir mostra como obter metadados para um conjunto de HealthImaging imagens.

SDK para Java 2.x

```
   public static void getMedicalImageSetMetadata(MedicalImagingClient
medicalImagingClient,
           String destinationPath,
           String datastoreId,
           String imagesetId,
           String versionId) {

       try {
           GetImageSetMetadataRequest.Builder getImageSetMetadataRequestBuilder =
GetImageSetMetadataRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId);

           if (versionId != null) {
               getImageSetMetadataRequestBuilder =
getImageSetMetadataRequestBuilder.versionId(versionId);
           }


medicalImagingClient.getImageSetMetadata(getImageSetMetadataRequestBuilder.build(),
                   FileSystems.getDefault().getPath(destinationPath));

           System.out.println("Metadata downloaded to " + destinationPath);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetImageSetMetadataa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importar dados em massa para um datastore

O exemplo de código a seguir mostra como importar dados em massa para um armazenamento HealthImaging de dados.

SDK para Java 2.x

```
   public static String startDicomImportJob(MedicalImagingClient
medicalImagingClient,
           String jobName,
           String datastoreId,
           String dataAccessRoleArn,
           String inputS3Uri,
           String outputS3Uri) {

       try {
           StartDicomImportJobRequest startDicomImportJobRequest =
StartDicomImportJobRequest.builder()
                   .jobName(jobName)
                   .datastoreId(datastoreId)
                   .dataAccessRoleArn(dataAccessRoleArn)
                   .inputS3Uri(inputS3Uri)
                   .outputS3Uri(outputS3Uri)
                   .build();
           StartDicomImportJobResponse response =
medicalImagingClient.startDICOMImportJob(startDicomImportJobRequest);
           return response.jobId();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return "";
   }
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na AWS SDK for Java 2.x Referência da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar datastores

O exemplo de código a seguir mostra como listar armazenamentos HealthImaging de dados.

SDK para Java 2.x

```
   public static List<DatastoreSummary>
listMedicalImagingDatastores(MedicalImagingClient medicalImagingClient) {
       try {
           ListDatastoresRequest datastoreRequest = ListDatastoresRequest.builder()
                   .build();
           ListDatastoresIterable responses =
medicalImagingClient.listDatastoresPaginator(datastoreRequest);
           List<DatastoreSummary> datastoreSummaries = new ArrayList<>();

           responses.stream().forEach(response ->
datastoreSummaries.addAll(response.datastoreSummaries()));

           return datastoreSummaries;
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte ListDatastoresa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar versões do conjunto de imagens

O exemplo de código a seguir mostra como listar as versões do conjunto de HealthImaging imagens.

SDK para Java 2.x

```
   public static List<ImageSetProperties>
listMedicalImageSetVersions(MedicalImagingClient medicalImagingClient,
           String datastoreId,
           String imagesetId) {
       try {
           ListImageSetVersionsRequest getImageSetRequest =
ListImageSetVersionsRequest.builder()
                   .datastoreId(datastoreId)
                   .imageSetId(imagesetId)
                   .build();

           ListImageSetVersionsIterable responses = medicalImagingClient
                   .listImageSetVersionsPaginator(getImageSetRequest);
           List<ImageSetProperties> imageSetProperties = new ArrayList<>();
           responses.stream().forEach(response ->
imageSetProperties.addAll(response.imageSetPropertiesList()));

           return imageSetProperties;
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte ListImageSetVersionsa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar trabalhos de importação para um datastore

O exemplo de código a seguir mostra como listar trabalhos de importação para um armazenamento HealthImaging de dados.

SDK para Java 2.x

```
   public static List<DICOMImportJobSummary>
listDicomImportJobs(MedicalImagingClient medicalImagingClient,
           String datastoreId) {

       try {
           ListDicomImportJobsRequest listDicomImportJobsRequest =
ListDicomImportJobsRequest.builder()
                   .datastoreId(datastoreId)
                   .build();
           ListDicomImportJobsResponse response =
medicalImagingClient.listDICOMImportJobs(listDicomImportJobsRequest);
           return response.jobSummaries();
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return new ArrayList<>();
   }
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar as tags para um recurso

O exemplo de código a seguir mostra como listar tags para um HealthImaging recurso.

SDK para Java 2.x

```
   public static ListTagsForResourceResponse
listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
           String resourceArn) {
       try {
           ListTagsForResourceRequest listTagsForResourceRequest =
ListTagsForResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .build();

           return
medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

- Para obter detalhes da API, consulte ListTagsForResourcea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover tag de um recurso

O exemplo de código a seguir mostra como remover uma tag de um HealthImaging recurso.

SDK para Java 2.x

```
   public static void untagMedicalImagingResource(MedicalImagingClient
medicalImagingClient,
           String resourceArn,
           Collection<String> tagKeys) {
       try {
```

```
            UntagResourceRequest untagResourceRequest =
UntagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tagKeys(tagKeys)
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte UntagResourcea Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Pesquisar conjuntos de imagens

O exemplo de código a seguir mostra como pesquisar conjuntos de HealthImaging imagens.

SDK para Java 2.x

A função de utilitário para pesquisar conjuntos de imagens.

```
        public static List<ImageSetsMetadataSummary> searchMedicalImagingImageSets(
                        MedicalImagingClient medicalImagingClient,
                        String datastoreId, List<SearchFilter> searchFilters) {
                try {
                        SearchImageSetsRequest datastoreRequest =
SearchImageSetsRequest.builder()
                                        .datastoreId(datastoreId)

.searchCriteria(SearchCriteria.builder().filters(searchFilters).build())
                                        .build();
```

```
                        SearchImageSetsIterable responses = medicalImagingClient
                                        .searchImageSetsPaginator(datastoreRequest);
                        List<ImageSetsMetadataSummary> imageSetsMetadataSummaries =
new ArrayList<>();

                        responses.stream().forEach(response ->
imageSetsMetadataSummaries

.addAll(response.imageSetsMetadataSummaries()));

                        return imageSetsMetadataSummaries;
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }

                return null;
        }
```

Caso de uso nº 1: operador EQUAL.

```
                List<SearchFilter> searchFilters =
Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.EQUAL)
                                .values(SearchByAttributeValue.builder()
                                                .dicomPatientId(patientId)
                                                .build())
                                .build());

                List<ImageSetsMetadataSummary> imageSetsMetadataSummaries =
searchMedicalImagingImageSets(
                                medicalImagingClient,
                                datastoreId, searchFilters);
                if (imageSetsMetadataSummaries != null) {
                        System.out.println("The image sets for patient " + patientId
+ " are:\n"
                                        + imageSetsMetadataSummaries);
                        System.out.println();
                }
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
                DateTimeFormatter formatter =
DateTimeFormatter.ofPattern("yyyyMMdd");
                searchFilters = Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.BETWEEN)
                                .values(SearchByAttributeValue.builder()

.dicomStudyDateAndTime(DICOMStudyDateAndTime.builder()

.dicomStudyDate("19990101")

.dicomStudyTime("000000.000")
                                                                        .build())
                                                .build(),
                                                SearchByAttributeValue.builder()

.dicomStudyDateAndTime(DICOMStudyDateAndTime.builder()

.dicomStudyDate((LocalDate.now()

           .format(formatter)))

.dicomStudyTime("000000.000")

.build())
                                                                        .build())
                                .build());

                imageSetsMetadataSummaries =
searchMedicalImagingImageSets(medicalImagingClient,
                                datastoreId, searchFilters);
                if (imageSetsMetadataSummaries != null) {
                        System.out.println(
                                        "The image sets searched with BETWEEN
operator using DICOMStudyDate and DICOMStudyTime are:\n"
                                                        +
                                                        imageSetsMetadataSummaries);
                        System.out.println();
                }
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
                searchFilters = Collections.singletonList(SearchFilter.builder()
                                .operator(Operator.BETWEEN)
                                .values(SearchByAttributeValue.builder()

.createdAt(Instant.parse("1985-04-12T23:20:50.52Z"))
                                                .build(),
                                                SearchByAttributeValue.builder()

.createdAt(Instant.now())
                                                                .build())
                                .build());

                imageSetsMetadataSummaries =
searchMedicalImagingImageSets(medicalImagingClient,
                                datastoreId, searchFilters);
                if (imageSetsMetadataSummaries != null) {
                        System.out.println("The image sets searched with BETWEEN
operator using createdAt are:\n "
                                        + imageSetsMetadataSummaries);
                        System.out.println();
                }
```

- Para obter detalhes da API, consulte SearchImageSetsa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar metadados do conjunto de imagens

O exemplo de código a seguir mostra como atualizar os metadados do conjunto de HealthImaging imagens.

SDK para Java 2.x

```
        public static void updateMedicalImageSetMetadata(MedicalImagingClient
medicalImagingClient,
                        String datastoreId,
```

```
                        String imagesetId,
                        String versionId,
                        MetadataUpdates metadataUpdates) {
                try {
                        UpdateImageSetMetadataRequest updateImageSetMetadataRequest
= UpdateImageSetMetadataRequest
                                        .builder()
                                        .datastoreId(datastoreId)
                                        .imageSetId(imagesetId)
                                        .latestVersionId(versionId)

.updateImageSetMetadataUpdates(metadataUpdates)
                                        .build();


medicalImagingClient.updateImageSetMetadata(updateImageSetMetadataRequest);

                        System.out.println("The image set metadata was updated");
                } catch (MedicalImagingException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
```

- Para obter detalhes da API, consulte UpdateImageSetMetadataa Referência AWS SDK for Java 2.x da API.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cenários

Marcar um datastore

O exemplo de código a seguir mostra como marcar um armazenamento HealthImaging de dados.

SDK para Java 2.x

Para marcar um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                TagResource.tagMedicalImagingResource(medicalImagingClient,
 datastoreArn,
                                ImmutableMap.of("Deployment", "Development"));
```

A função utilitária para marcar um recurso.

```
    public static void tagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Map<String, String> tags) {
        try {
            TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tags(tags)
                    .build();

            medicalImagingClient.tagResource(tagResourceRequest);

            System.out.println("Tags have been added to the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Para listar tags para um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                ListTagsForResourceResponse result =
 ListTagsForResource.listMedicalImagingResourceTags(
                                medicalImagingClient,
                                datastoreArn);
                if (result != null) {
                        System.out.println("Tags for resource: " + result.tags());
                }
```

A função utilitária para listar as tags de um recurso.

```
   public static ListTagsForResourceResponse
listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
           String resourceArn) {
       try {
           ListTagsForResourceRequest listTagsForResourceRequest =
ListTagsForResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .build();

           return
medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

Para desmarcar um armazenamento de dados

```
                final String datastoreArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012";

                UntagResource.untagMedicalImagingResource(medicalImagingClient,
 datastoreArn,
                               Collections.singletonList("Deployment"));
```

A função de utilitário para desmarcar um recurso.

```
   public static void untagMedicalImagingResource(MedicalImagingClient
medicalImagingClient,
           String resourceArn,
           Collection<String> tagKeys) {
       try {
```

```
            UntagResourceRequest untagResourceRequest =
 UntagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tagKeys(tagKeys)
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Marcar um conjunto de imagens

O exemplo de código a seguir mostra como marcar um conjunto de HealthImaging imagens.

SDK para Java 2.x

Para marcar um conjunto de imagens

```
                final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";
```

```
                TagResource.tagMedicalImagingResource(medicalImagingClient,
 imageSetArn,
                                ImmutableMap.of("Deployment", "Development"));
```

A função utilitária para marcar um recurso.

```
    public static void tagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
            String resourceArn,
            Map<String, String> tags) {
        try {
            TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                    .resourceArn(resourceArn)
                    .tags(tags)
                    .build();

            medicalImagingClient.tagResource(tagResourceRequest);

            System.out.println("Tags have been added to the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Para listar tags para um conjunto de imagens

```
                final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";

                ListTagsForResourceResponse result =
 ListTagsForResource.listMedicalImagingResourceTags(
                                medicalImagingClient,
                                imageSetArn);
                if (result != null) {
                        System.out.println("Tags for resource: " + result.tags());
                }
```

A função utilitária para listar as tags de um recurso.

```
   public static ListTagsForResourceResponse
 listMedicalImagingResourceTags(MedicalImagingClient medicalImagingClient,
           String resourceArn) {
       try {
           ListTagsForResourceRequest listTagsForResourceRequest =
 ListTagsForResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .build();

           return
 medicalImagingClient.listTagsForResource(listTagsForResourceRequest);
       } catch (MedicalImagingException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }

       return null;
   }
```

Para desmarcar um conjunto de imagens

```
               final String imageSetArn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/
imageset/12345678901234567890123456789012";

               UntagResource.untagMedicalImagingResource(medicalImagingClient,
 imageSetArn,
                               Collections.singletonList("Deployment"));
```

A função de utilitário para desmarcar um recurso.

```
   public static void untagMedicalImagingResource(MedicalImagingClient
 medicalImagingClient,
           String resourceArn,
           Collection<String> tagKeys) {
       try {
           UntagResourceRequest untagResourceRequest =
 UntagResourceRequest.builder()
                   .resourceArn(resourceArn)
                   .tagKeys(tagKeys)
```

```
                    .build();

            medicalImagingClient.untagResource(untagResourceRequest);

            System.out.println("Tags have been removed from the resource.");
        } catch (MedicalImagingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos do IAM usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.ListPoliciesResponse;
import software.amazon.awssdk.services.iam.model.Policy;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloIAM {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listPolicies(iam);
    }

    public static void listPolicies(IamClient iam) {
        ListPoliciesResponse response = iam.listPolicies();
        List<Policy> polList = response.policies();
        polList.forEach(policy -> {
            System.out.println("Policy Name: " + policy.policyName());
        });
    }
```

```
}
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.AttachRolePolicyRequest;
import software.amazon.awssdk.services.iam.model.AttachedPolicy;
import software.amazon.awssdk.services.iam.model.ListAttachedRolePoliciesRequest;
import software.amazon.awssdk.services.iam.model.ListAttachedRolePoliciesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class AttachRolePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleName> <policyArn>\s

                Where:
                    roleName - A role name that you can obtain from the AWS
 Management Console.\s
                    policyArn - A policy ARN that you can obtain from the AWS
 Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleName = args[0];
        String policyArn = args[1];

        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        attachIAMRolePolicy(iam, roleName, policyArn);
        iam.close();
    }

    public static void attachIAMRolePolicy(IamClient iam, String roleName, String
 policyArn) {
        try {
            ListAttachedRolePoliciesRequest request =
 ListAttachedRolePoliciesRequest.builder()
                    .roleName(roleName)
                    .build();

            ListAttachedRolePoliciesResponse response =
 iam.listAttachedRolePolicies(request);
            List<AttachedPolicy> attachedPolicies = response.attachedPolicies();

            // Ensure that the policy is not attached to this role
```

```
            String polArn = "";
            for (AttachedPolicy policy : attachedPolicies) {
                polArn = policy.policyArn();
                if (polArn.compareTo(policyArn) == 0) {
                    System.out.println(roleName + " policy is already attached to
 this role.");
                    return;
                }
            }

            AttachRolePolicyRequest attachRequest =
 AttachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.attachRolePolicy(attachRequest);

            System.out.println("Successfully attached policy " + policyArn +
                    " to role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Java 2.x da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.services.iam.model.CreatePolicyRequest;
import software.amazon.awssdk.services.iam.model.CreatePolicyResponse;
import software.amazon.awssdk.services.iam.model.GetPolicyRequest;
import software.amazon.awssdk.services.iam.model.GetPolicyResponse;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.waiters.IamWaiter;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreatePolicy {

    public static final String PolicyDocument = "{" +
            "  \"Version\": \"2012-10-17\"," +
            "  \"Statement\": [" +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Action\": [" +
            "            \"dynamodb:DeleteItem\"," +
            "            \"dynamodb:GetItem\"," +
            "            \"dynamodb:PutItem\"," +
            "            \"dynamodb:Scan\"," +
            "            \"dynamodb:UpdateItem\"" +
            "        ]," +
            "        \"Resource\": \"*\"" +
            "    }" +
```

```
            "   ]" +
            "}";

    public static void main(String[] args) {

        final String usage = """
                Usage:
                    CreatePolicy <policyName>\s

                Where:
                    policyName - A unique policy name.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String policyName = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String result = createIAMPolicy(iam, policyName);
        System.out.println("Successfully created a policy with this ARN value: " +
result);
        iam.close();
    }

    public static String createIAMPolicy(IamClient iam, String policyName) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();

            CreatePolicyRequest request = CreatePolicyRequest.builder()
                    .policyName(policyName)
                    .policyDocument(PolicyDocument)
                    .build();

            CreatePolicyResponse response = iam.createPolicy(request);

            // Wait until the policy is created.
            GetPolicyRequest polRequest = GetPolicyRequest.builder()
```

```
                    .policyArn(response.policy().arn())
                    .build();

            WaiterResponse<GetPolicyResponse> waitUntilPolicyExists =
 iamWaiter.waitUntilPolicyExists(polRequest);

 waitUntilPolicyExists.matched().response().ifPresent(System.out::println);
            return response.policy().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Java 2.x da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import org.json.simple.JSONObject;
import org.json.simple.parser.JSONParser;
import software.amazon.awssdk.services.iam.model.CreateRoleRequest;
import software.amazon.awssdk.services.iam.model.CreateRoleResponse;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import java.io.FileReader;

/*
```

```
*   This example requires a trust policy document. For more information, see:
*   https://aws.amazon.com/blogs/security/how-to-use-trust-policies-with-iam-roles/
*
*
*  In addition, set up your development environment, including your credentials.
*
*  For information, see this documentation topic:
*
*  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class CreateRole {
    public static void main(String[] args) throws Exception {
        final String usage = """
                Usage:
                    <rolename> <fileLocation>\s

                Where:
                    rolename - The name of the role to create.\s
                    fileLocation - The location of the JSON document that represents
 the trust policy.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String rolename = args[0];
        String fileLocation = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String result = createIAMRole(iam, rolename, fileLocation);
        System.out.println("Successfully created user: " + result);
        iam.close();
    }

    public static String createIAMRole(IamClient iam, String rolename, String
 fileLocation) throws Exception {
        try {
            JSONObject jsonObject = (JSONObject) readJsonSimpleDemo(fileLocation);
```

```
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(jsonObject.toJSONString())
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse response = iam.createRole(request);
            System.out.println("The ARN of the role is " + response.role().arn());

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static Object readJsonSimpleDemo(String filename) throws Exception {
        FileReader reader = new FileReader(filename);
        JSONParser jsonParser = new JSONParser();
        return jsonParser.parse(reader);
    }
}
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Java 2.x da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.services.iam.model.CreateUserRequest;
import software.amazon.awssdk.services.iam.model.CreateUserResponse;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.waiters.IamWaiter;
import software.amazon.awssdk.services.iam.model.GetUserRequest;
import software.amazon.awssdk.services.iam.model.GetUserResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <username>\s

                Where:
                    username - The name of the user to create.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String username = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String result = createIAMUser(iam, username);
        System.out.println("Successfully created user: " + result);
        iam.close();
    }

    public static String createIAMUser(IamClient iam, String username) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();

            CreateUserRequest request = CreateUserRequest.builder()
                    .userName(username)
                    .build();

            CreateUserResponse response = iam.createUser(request);

            // Wait until the user is created.
            GetUserRequest userRequest = GetUserRequest.builder()
                    .userName(response.user().userName())
                    .build();

            WaiterResponse<GetUserResponse> waitUntilUserExists =
 iamWaiter.waitUntilUserExists(userRequest);
            waitUntilUserExists.matched().response().ifPresent(System.out::println);
            return response.user().userName();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Java 2.x da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.CreateAccessKeyRequest;
import software.amazon.awssdk.services.iam.model.CreateAccessKeyResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateAccessKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                   <user>\s

                Where:
```

```
                    user - An AWS IAM user that you can obtain from the AWS
 Management Console.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String user = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        String keyId = createIAMAccessKey(iam, user);
        System.out.println("The Key Id is " + keyId);
        iam.close();
    }

    public static String createIAMAccessKey(IamClient iam, String user) {
        try {
            CreateAccessKeyRequest request = CreateAccessKeyRequest.builder()
                    .userName(user)
                    .build();

            CreateAccessKeyResponse response = iam.createAccessKey(request);
            return response.accessKey().accessKeyId();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Java 2.x da API.

Criar um alias para uma conta

O exemplo de código a seguir mostra como criar um alias para uma conta do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.CreateAccountAliasRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateAccountAlias {
    public static void main(String[] args) {
        final String usage = """
                Usage:
                    <alias>\s

                Where:
                    alias - The account alias to create (for example, myawsaccount).
\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alias = args[0];
        Region region = Region.AWS_GLOBAL;
```

```
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        createIAMAccountAlias(iam, alias);
        iam.close();
        System.out.println("Done");
    }

    public static void createIAMAccountAlias(IamClient iam, String alias) {
        try {
            CreateAccountAliasRequest request = CreateAccountAliasRequest.builder()
                    .accountAlias(alias)
                    .build();

            iam.createAccountAlias(request);
            System.out.println("Successfully created account alias: " + alias);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for Java 2.x da API.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DeletePolicyRequest;
```

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeletePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <policyARN>\s

                Where:
                    policyARN - A policy ARN value to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String policyARN = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMPolicy(iam, policyARN);
        iam.close();
    }

    public static void deleteIAMPolicy(IamClient iam, String policyARN) {
        try {
            DeletePolicyRequest request = DeletePolicyRequest.builder()
                    .policyArn(policyARN)
                    .build();
```

```
            iam.deletePolicy(request);
            System.out.println("Successfully deleted the policy");

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeletePolicya Referência AWS SDK for Java 2.x da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.DeleteUserRequest;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <userName>\s

                Where:
                    userName - The name of the user to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userName = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMUser(iam, userName);
        System.out.println("Done");
        iam.close();
    }

    public static void deleteIAMUser(IamClient iam, String userName) {
        try {
            DeleteUserRequest request = DeleteUserRequest.builder()
                    .userName(userName)
                    .build();

            iam.deleteUser(request);
            System.out.println("Successfully deleted IAM user " + userName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Java 2.x da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.DeleteAccessKeyRequest;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteAccessKey {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <username> <accessKey>\s

                Where:
                    username - The name of the user.\s
                    accessKey - The access key ID for the secret access key you want
 to delete.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String username = args[0];
        String accessKey = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();
        deleteKey(iam, username, accessKey);
        iam.close();
    }

    public static void deleteKey(IamClient iam, String username, String accessKey) {
        try {
            DeleteAccessKeyRequest request = DeleteAccessKeyRequest.builder()
                    .accessKeyId(accessKey)
                    .userName(username)
                    .build();

            iam.deleteAccessKey(request);
            System.out.println("Successfully deleted access key " + accessKey +
                    " from user " + username);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Java 2.x da API.

Excluir um alias de conta

O exemplo de código a seguir mostra como excluir um alias da conta do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DeleteAccountAliasRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteAccountAlias {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <alias>\s

                Where:
                    alias - The account alias to delete.\s
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String alias = args[0];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        deleteIAMAccountAlias(iam, alias);
        iam.close();
    }

    public static void deleteIAMAccountAlias(IamClient iam, String alias) {
        try {
            DeleteAccountAliasRequest request = DeleteAccountAliasRequest.builder()
                    .accountAlias(alias)
                    .build();

            iam.deleteAccountAlias(request);
            System.out.println("Successfully deleted account alias " + alias);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for Java 2.x da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.DetachRolePolicyRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetachRolePolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleName> <policyArn>\s

                Where:
                    roleName - A role name that you can obtain from the AWS
 Management Console.\s
                    policyArn - A policy ARN that you can obtain from the AWS
 Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleName = args[0];
        String policyArn = args[1];
```

```
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();
        detachPolicy(iam, roleName, policyArn);
        System.out.println("Done");
        iam.close();
    }

    public static void detachPolicy(IamClient iam, String roleName, String
 policyArn) {
        try {
            DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.detachRolePolicy(request);
            System.out.println("Successfully detached policy " + policyArn +
                    " from role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Java 2.x da API.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.AccessKeyMetadata;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListAccessKeysRequest;
import software.amazon.awssdk.services.iam.model.ListAccessKeysResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListAccessKeys {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <userName>\s

                Where:
                    userName - The name of the user for which access keys are
 retrieved.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String userName = args[0];
        Region region = Region.AWS_GLOBAL;
```

```
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listKeys(iam, userName);
        System.out.println("Done");
        iam.close();
    }

    public static void listKeys(IamClient iam, String userName) {
        try {
            boolean done = false;
            String newMarker = null;

            while (!done) {
                ListAccessKeysResponse response;

                if (newMarker == null) {
                    ListAccessKeysRequest request = ListAccessKeysRequest.builder()
                            .userName(userName)
                            .build();

                    response = iam.listAccessKeys(request);

                } else {
                    ListAccessKeysRequest request = ListAccessKeysRequest.builder()
                            .userName(userName)
                            .marker(newMarker)
                            .build();

                    response = iam.listAccessKeys(request);
                }

                for (AccessKeyMetadata metadata : response.accessKeyMetadata()) {
                    System.out.format("Retrieved access key %s",
metadata.accessKeyId());
                }

                if (!response.isTruncated()) {
                    done = true;
                } else {
                    newMarker = response.marker();
                }
            }
```

```
        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Java 2.x da API.

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de conta do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListAccountAliasesResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListAccountAliases {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
```

```
                .region(region)
                .build();

        listAliases(iam);
        System.out.println("Done");
        iam.close();
    }

    public static void listAliases(IamClient iam) {
        try {
            ListAccountAliasesResponse response = iam.listAccountAliases();
            for (String alias : response.accountAliases()) {
                System.out.printf("Retrieved account alias %s", alias);
            }

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for Java 2.x da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.AttachedPermissionsBoundary;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.ListUsersRequest;
import software.amazon.awssdk.services.iam.model.ListUsersResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.User;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListUsers {
    public static void main(String[] args) {
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        listAllUsers(iam);
        System.out.println("Done");
        iam.close();
    }

    public static void listAllUsers(IamClient iam) {
        try {
            boolean done = false;
            String newMarker = null;
            while (!done) {
                ListUsersResponse response;
```

```
                if (newMarker == null) {
                    ListUsersRequest request = ListUsersRequest.builder().build();
                    response = iam.listUsers(request);
                } else {
                    ListUsersRequest request = ListUsersRequest.builder()
                            .marker(newMarker)
                            .build();

                    response = iam.listUsers(request);
                }

                for (User user : response.users()) {
                    System.out.format("\n Retrieved user %s", user.userName());
                    AttachedPermissionsBoundary permissionsBoundary =
 user.permissionsBoundary();
                    if (permissionsBoundary != null)
                        System.out.format("\n Permissions boundary details %s",

 permissionsBoundary.permissionsBoundaryTypeAsString());
                }

                if (!response.isTruncated()) {
                    done = true;
                } else {
                    newMarker = response.marker();
                }
            }

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Java 2.x da API.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.UpdateUserRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateUser {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <curName> <newName>\s

                Where:
                    curName - The current user name.\s
                    newName - An updated user name.\s
                """;

        if (args.length != 2) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String curName = args[0];
        String newName = args[1];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        updateIAMUser(iam, curName, newName);
        System.out.println("Done");
        iam.close();
    }

    public static void updateIAMUser(IamClient iam, String curName, String newName)
 {
        try {
            UpdateUserRequest request = UpdateUserRequest.builder()
                    .userName(curName)
                    .newUserName(newName)
                    .build();

            iam.updateUser(request);
            System.out.printf("Successfully updated user to username %s", newName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for Java 2.x da API.

Atualizar uma chave de acesso

O exemplo de código a seguir mostra como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.iam.model.IamException;
import software.amazon.awssdk.services.iam.model.StatusType;
import software.amazon.awssdk.services.iam.model.UpdateAccessKeyRequest;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateAccessKey {

    private static StatusType statusType;

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <username> <accessId> <status>\s

                Where:
                    username - The name of the user whose key you want to update.\s
```

```
                    accessId - The access key ID of the secret access key you want
 to update.\s
                    status - The status you want to assign to the secret access key.
\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String username = args[0];
        String accessId = args[1];
        String status = args[2];
        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        updateKey(iam, username, accessId, status);
        System.out.println("Done");
        iam.close();
    }

    public static void updateKey(IamClient iam, String username, String accessId,
 String status) {
        try {
            if (status.toLowerCase().equalsIgnoreCase("active")) {
                statusType = StatusType.ACTIVE;
            } else if (status.toLowerCase().equalsIgnoreCase("inactive")) {
                statusType = StatusType.INACTIVE;
            } else {
                statusType = StatusType.UNKNOWN_TO_SDK_VERSION;
            }

            UpdateAccessKeyRequest request = UpdateAccessKeyRequest.builder()
                    .accessKeyId(accessId)
                    .userName(username)
                    .status(statusType)
                    .build();

            iam.updateAccessKey(request);
            System.out.printf("Successfully updated the status of access key %s to"
 +
```

```
                    "status %s for user %s", accessId, status, username);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateAccessKeya Referência AWS SDK for Java 2.x da API.

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
public class Main {

    public static final String fileName = "C:\\AWS\\resworkflow\
\recommendations.json"; // Modify file location.
    public static final String tableName = "doc-example-recommendation-service";
    public static final String startScript = "C:\\AWS\\resworkflow\
\server_startup_script.sh"; // Modify file location.
    public static final String policyFile = "C:\\AWS\\resworkflow\
\instance_policy.json"; // Modify file location.
    public static final String ssmJSON = "C:\\AWS\\resworkflow\
\ssm_only_policy.json"; // Modify file location.
    public static final String failureResponse = "doc-example-resilient-
architecture-failure-response";
    public static final String healthCheck = "doc-example-resilient-architecture-
health-check";
    public static final String templateName = "doc-example-resilience-template";
    public static final String roleName = "doc-example-resilience-role";
    public static final String policyName = "doc-example-resilience-pol";
    public static final String profileName = "doc-example-resilience-prof";

    public static final String badCredsProfileName = "doc-example-resilience-prof-
bc";

    public static final String targetGroupName = "doc-example-resilience-tg";
    public static final String autoScalingGroupName = "doc-example-resilience-
group";
    public static final String lbName = "doc-example-resilience-lb";
    public static final String protocol = "HTTP";
    public static final int port = 80;

    public static final String DASHES = new String(new char[80]).replace("\0", "-");
```

```
   public static void main(String[] args) throws IOException, InterruptedException
{
       Scanner in = new Scanner(System.in);
       Database database = new Database();
       AutoScaler autoScaler = new AutoScaler();
       LoadBalancer loadBalancer = new LoadBalancer();

       System.out.println(DASHES);
       System.out.println("Welcome to the demonstration of How to Build and Manage
a Resilient Service!");
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("A - SETUP THE RESOURCES");
       System.out.println("Press Enter when you're ready to start deploying
resources.");
       in.nextLine();
       deploy(loadBalancer);
       System.out.println(DASHES);
       System.out.println(DASHES);
       System.out.println("B - DEMO THE RESILIENCE FUNCTIONALITY");
       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       demo(loadBalancer);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("C - DELETE THE RESOURCES");
       System.out.println("""
               This concludes the demo of how to build and manage a resilient
service.
               To keep things tidy and to avoid unwanted charges on your account,
we can clean up all AWS resources
               that were created for this demo.
               """);

       System.out.println("\n Do you want to delete the resources (y/n)? ");
       String userInput = in.nextLine().trim().toLowerCase(); // Capture user input

       if (userInput.equals("y")) {
           // Delete resources here
           deleteResources(loadBalancer, autoScaler, database);
           System.out.println("Resources deleted.");
       } else {
```

```
            System.out.println("""
                    Okay, we'll leave the resources intact.
                    Don't forget to delete them when you're done with them or you
might incur unexpected charges.
                    """);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The example has completed. ");
        System.out.println("\n Thanks for watching!");
        System.out.println(DASHES);
    }

    // Deletes the AWS resources used in this example.
    private static void deleteResources(LoadBalancer loadBalancer, AutoScaler
autoScaler, Database database)
            throws IOException, InterruptedException {
        loadBalancer.deleteLoadBalancer(lbName);
        System.out.println("*** Wait 30 secs for resource to be deleted");
        TimeUnit.SECONDS.sleep(30);
        loadBalancer.deleteTargetGroup(targetGroupName);
        autoScaler.deleteAutoScaleGroup(autoScalingGroupName);
        autoScaler.deleteRolesPolicies(policyName, roleName, profileName);
        autoScaler.deleteTemplate(templateName);
        database.deleteTable(tableName);
    }

    private static void deploy(LoadBalancer loadBalancer) throws
InterruptedException, IOException {
        Scanner in = new Scanner(System.in);
        System.out.println(
                """
                        For this demo, we'll use the AWS SDK for Java (v2) to create
several AWS resources
                        to set up a load-balanced web service endpoint and explore
some ways to make it resilient
                        against various kinds of failures.

                        Some of the resources create by this demo are:
                        \t* A DynamoDB table that the web service depends on to
provide book, movie, and song recommendations.
                        \t* An EC2 launch template that defines EC2 instances that
each contain a Python web server.
```

```
                        \t* An EC2 Auto Scaling group that manages EC2 instances
across several Availability Zones.
                        \t* An Elastic Load Balancing (ELB) load balancer that
targets the Auto Scaling group to distribute requests.
                        """);

       System.out.println("Press Enter when you're ready.");
       in.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("Creating and populating a DynamoDB table named " +
tableName);
       Database database = new Database();
       database.createTable(tableName, fileName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("""
               Creating an EC2 launch template that runs '{startup_script}' when an
instance starts.
               This script starts a Python web server defined in the `server.py`
script. The web server
               listens to HTTP requests on port 80 and responds to requests to '/'
and to '/healthcheck'.
               For demo purposes, this server is run as the root user. In
production, the best practice is to
               run a web server, such as Apache, with least-privileged credentials.

               The template also defines an IAM policy that each instance uses to
assume a role that grants
               permissions to access the DynamoDB recommendation table and Systems
Manager parameters
               that control the flow of the demo.
               """);

       LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
       templateCreator.createTemplate(policyFile, policyName, profileName,
startScript, templateName, roleName);
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println(
```

```
                "Creating an EC2 Auto Scaling group that maintains three EC2
instances, each in a different Availability Zone.");
        System.out.println("*** Wait 30 secs for the VPC to be created");
        TimeUnit.SECONDS.sleep(30);
        AutoScaler autoScaler = new AutoScaler();
        String[] zones = autoScaler.createGroup(3, templateName,
autoScalingGroupName);

        System.out.println("""
                At this point, you have EC2 instances created. Once each instance
starts, it listens for
                HTTP requests. You can see these instances in the console or
continue with the demo.
                Press Enter when you're ready to continue.
                """);

        in.nextLine();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Creating variables that control the flow of the demo.");
        ParameterHelper paramHelper = new ParameterHelper();
        paramHelper.reset();
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("""
                Creating an Elastic Load Balancing target group and load balancer.
The target group
                defines how the load balancer connects to instances. The load
balancer provides a
                single endpoint where clients connect and dispatches requests to
instances in the group.
                """);

        String vpcId = autoScaler.getDefaultVPC();
        List<Subnet> subnets = autoScaler.getSubnets(vpcId, zones);
        System.out.println("You have retrieved a list with " + subnets.size() + "
subnets");
        String targetGroupArn = loadBalancer.createTargetGroup(protocol, port,
vpcId, targetGroupName);
        String elbDnsName = loadBalancer.createLoadBalancer(subnets, targetGroupArn,
lbName, port, protocol);
```

```
        autoScaler.attachLoadBalancerTargetGroup(autoScalingGroupName,
targetGroupArn);
        System.out.println("Verifying access to the load balancer endpoint...");
        boolean wasSuccessul = loadBalancer.verifyLoadBalancerEndpoint(elbDnsName);
        if (!wasSuccessul) {
            System.out.println("Couldn't connect to the load balancer, verifying
that the port is open...");
            CloseableHttpClient httpClient = HttpClients.createDefault();

            // Create an HTTP GET request to "http://checkip.amazonaws.com"
            HttpGet httpGet = new HttpGet("http://checkip.amazonaws.com");
            try {
                // Execute the request and get the response
                HttpResponse response = httpClient.execute(httpGet);

                // Read the response content.
                String ipAddress =
IOUtils.toString(response.getEntity().getContent(), StandardCharsets.UTF_8).trim();

                // Print the public IP address.
                System.out.println("Public IP Address: " + ipAddress);
                GroupInfo groupInfo = autoScaler.verifyInboundPort(vpcId, port,
ipAddress);
                if (!groupInfo.isPortOpen()) {
                    System.out.println("""
                            For this example to work, the default security group for
your default VPC must
                            allow access from this computer. You can either add it
automatically from this
                            example or add it yourself using the AWS Management
Console.
                            """);

                    System.out.println(
                            "Do you want to add a rule to security group " +
groupInfo.getGroupName() + " to allow");
                    System.out.println("inbound traffic on port " + port + " from
your computer's IP address (y/n) ");
                    String ans = in.nextLine();
                    if ("y".equalsIgnoreCase(ans)) {
                        autoScaler.openInboundPort(groupInfo.getGroupName(),
String.valueOf(port), ipAddress);
                        System.out.println("Security group rule added.");
                    } else {
```

```
                        System.out.println("No security group rule added.");
                    }
                }

            } catch (AutoScalingException e) {
                e.printStackTrace();
            }
        } else if (wasSuccessul) {
            System.out.println("Your load balancer is ready. You can access it by
browsing to:");
            System.out.println("\t http://" + elbDnsName);
        } else {
            System.out.println("Couldn't get a successful response from the load
balancer endpoint. Troubleshoot by");
            System.out.println("manually verifying that your VPC and security group
are configured correctly and that");
            System.out.println("you can successfully make a GET request to the load
balancer.");
        }

        System.out.println("Press Enter when you're ready to continue with the
demo.");
        in.nextLine();
    }

    // A method that controls the demo part of the Java program.
    public static void demo(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        ParameterHelper paramHelper = new ParameterHelper();
        System.out.println("Read the ssm_only_policy.json file");
        String ssmOnlyPolicy = readFileAsString(ssmJSON);

        System.out.println("Resetting parameters to starting values for demo.");
        paramHelper.reset();

        System.out.println(
                """
                        This part of the demonstration shows how to toggle
different parts of the system
                        to create situations where the web service fails, and shows
how using a resilient
                        architecture can keep the web service running in spite of
these failures.
```

```
                        At the start, the load balancer endpoint returns
recommendations and reports that all targets are healthy.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                        The web service running on the EC2 instances gets
recommendations by querying a DynamoDB table.
                        The table name is contained in a Systems Manager parameter
named self.param_helper.table.
                        To simulate a failure of the recommendation service, let's
set this parameter to name a non-existent table.
                       """);
       paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

       System.out.println(
               """
                        \nNow, sending a GET request to the load balancer endpoint
returns a failure code. But, the service reports as
                        healthy to the load balancer because shallow health checks
don't check for failure of the recommendation service.
                       """);
       demoChoices(loadBalancer);

       System.out.println(
               """
                       Instead of failing when the recommendation service fails,
the web service can return a static response.
                       While this is not a perfect solution, it presents the
customer with a somewhat better experience than failure.
                       """);
       paramHelper.put(paramHelper.failureResponse, "static");

       System.out.println("""
               Now, sending a GET request to the load balancer endpoint returns a
static response.
               The service still reports as healthy because health checks are still
shallow.
               """);
       demoChoices(loadBalancer);

       System.out.println("Let's reinstate the recommendation service.");
       paramHelper.put(paramHelper.tableName, paramHelper.dyntable);
```

```
        System.out.println("""
                Let's also substitute bad credentials for one of the instances in
the target group so that it can't
                access the DynamoDB recommendation table. We will get an instance id
value.
                """);

        LaunchTemplateCreator templateCreator = new LaunchTemplateCreator();
        AutoScaler autoScaler = new AutoScaler();

        // Create a new instance profile based on badCredsProfileName.
        templateCreator.createInstanceProfile(policyFile, policyName,
badCredsProfileName, roleName);
        String badInstanceId = autoScaler.getBadInstance(autoScalingGroupName);
        System.out.println("The bad instance id values used for this demo is " +
badInstanceId);

        String profileAssociationId = autoScaler.getInstanceProfile(badInstanceId);
        System.out.println("The association Id value is " + profileAssociationId);
        System.out.println("Replacing the profile for instance " + badInstanceId
                + " with a profile that contains bad credentials");
        autoScaler.replaceInstanceProfile(badInstanceId, badCredsProfileName,
profileAssociationId);

        System.out.println(
                """
                        Now, sending a GET request to the load balancer endpoint
returns either a recommendation or a static response,
                        depending on which instance is selected by the load
balancer.
                        """);

        demoChoices(loadBalancer);

        System.out.println("""
                Let's implement a deep health check. For this demo, a deep health
check tests whether
                the web service can access the DynamoDB table that it depends on for
recommendations. Note that
                the deep health check is only for ELB routing and not for Auto
Scaling instance health.
                This kind of deep health check is not recommended for Auto Scaling
instance health, because it
```

```
                risks accidental termination of all instances in the Auto Scaling
group when a dependent service fails.
                """);

        System.out.println("""
                By implementing deep health checks, the load balancer can detect
when one of the instances is failing
                and take that instance out of rotation.
                """);

        paramHelper.put(paramHelper.healthCheck, "deep");

        System.out.println("""
                Now, checking target health indicates that the instance with bad
credentials
                is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy
                instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because
                the load balancer takes unhealthy instances out of its rotation.
                """);

        demoChoices(loadBalancer);

        System.out.println(
                """
                        Because the instances in this demo are controlled by an auto
scaler, the simplest way to fix an unhealthy
                        instance is to terminate it and let the auto scaler start a
new instance to replace it.
                        """);
        autoScaler.terminateInstance(badInstanceId);

        System.out.println("""
                Even while the instance is terminating and the new instance is
starting, sending a GET
                request to the web service continues to get a successful
recommendation response because
                the load balancer routes requests to the healthy instances. After
the replacement instance
                starts and reports as healthy, it is included in the load balancing
rotation.
                Note that terminating and replacing an instance typically takes
several minutes, during which time you
```

```
                can see the changing health check status until the new instance is
running and healthy.
                """);

        demoChoices(loadBalancer);
        System.out.println(
                "If the recommendation service fails now, deep health checks mean
all instances report as unhealthy.");
        paramHelper.put(paramHelper.tableName, "this-is-not-a-table");

        demoChoices(loadBalancer);
        paramHelper.reset();
    }

    public static void demoChoices(LoadBalancer loadBalancer) throws IOException,
InterruptedException {
        String[] actions = {
                "Send a GET request to the load balancer endpoint.",
                "Check the health of load balancer targets.",
                "Go to the next part of the demo."
        };
        Scanner scanner = new Scanner(System.in);

        while (true) {
            System.out.println("-".repeat(88));
            System.out.println("See the current state of the service by selecting
one of the following choices:");
            for (int i = 0; i < actions.length; i++) {
                System.out.println(i + ": " + actions[i]);
            }

            try {
                System.out.print("\nWhich action would you like to take? ");
                int choice = scanner.nextInt();
                System.out.println("-".repeat(88));

                switch (choice) {
                    case 0 -> {
                        System.out.println("Request:\n");
                        System.out.println("GET http://" +
loadBalancer.getEndpoint(lbName));
                        CloseableHttpClient httpClient =
HttpClients.createDefault();
```

```
                        // Create an HTTP GET request to the ELB.
                        HttpGet httpGet = new HttpGet("http://" +
loadBalancer.getEndpoint(lbName));

                        // Execute the request and get the response.
                        HttpResponse response = httpClient.execute(httpGet);
                        int statusCode = response.getStatusLine().getStatusCode();
                        System.out.println("HTTP Status Code: " + statusCode);

                        // Display the JSON response
                        BufferedReader reader = new BufferedReader(
                                new
InputStreamReader(response.getEntity().getContent()));
                        StringBuilder jsonResponse = new StringBuilder();
                        String line;
                        while ((line = reader.readLine()) != null) {
                            jsonResponse.append(line);
                        }
                        reader.close();

                        // Print the formatted JSON response.
                        System.out.println("Full Response:\n");
                        System.out.println(jsonResponse.toString());

                        // Close the HTTP client.
                        httpClient.close();

                    }
                    case 1 -> {
                        System.out.println("\nChecking the health of load balancer
targets:\n");
                        List<TargetHealthDescription> health =
loadBalancer.checkTargetHealth(targetGroupName);
                        for (TargetHealthDescription target : health) {
                            System.out.printf("\tTarget %s on port %d is %s%n",
target.target().id(),
                                        target.target().port(),
target.targetHealth().stateAsString());
                        }
                        System.out.println("""
                                Note that it can take a minute or two for the health
check to update
                                after changes are made.
                                """);
```

```
                    }
                    case 2 -> {
                        System.out.println("\nOkay, let's move on.");
                        System.out.println("-".repeat(88));
                        return; // Exit the method when choice is 2
                    }
                    default -> System.out.println("You must choose a value between
 0-2. Please select again.");
                }

            } catch (java.util.InputMismatchException e) {
                System.out.println("Invalid input. Please select again.");
                scanner.nextLine(); // Clear the input buffer.
            }
        }
    }

    public static String readFileAsString(String filePath) throws IOException {
        byte[] bytes = Files.readAllBytes(Paths.get(filePath));
        return new String(bytes);
    }
}
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
public class AutoScaler {

    private static Ec2Client ec2Client;
    private static AutoScalingClient autoScalingClient;
    private static IamClient iamClient;

    private static SsmClient ssmClient;

    private IamClient getIAMClient() {
        if (iamClient == null) {
            iamClient = IamClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return iamClient;
    }
```

```
    private SsmClient getSSMClient() {
        if (ssmClient == null) {
            ssmClient = SsmClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ssmClient;
    }

    private Ec2Client getEc2Client() {
        if (ec2Client == null) {
            ec2Client = Ec2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return ec2Client;
    }

    private AutoScalingClient getAutoScalingClient() {
        if (autoScalingClient == null) {
            autoScalingClient = AutoScalingClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return autoScalingClient;
    }

    /**
     * Terminates and instances in an EC2 Auto Scaling group. After an instance is
     * terminated, it can no longer be accessed.
     */
    public void terminateInstance(String instanceId) {
        TerminateInstanceInAutoScalingGroupRequest terminateInstanceIRequest =
 TerminateInstanceInAutoScalingGroupRequest
                .builder()
                .instanceId(instanceId)
                .shouldDecrementDesiredCapacity(false)
                .build();


 getAutoScalingClient().terminateInstanceInAutoScalingGroup(terminateInstanceIRequest);
        System.out.format("Terminated instance %s.", instanceId);
    }
```

```
   /**
    * Replaces the profile associated with a running instance. After the profile is
    * replaced, the instance is rebooted to ensure that it uses the new profile.
    * When
    * the instance is ready, Systems Manager is used to restart the Python web
    * server.
    */
   public void replaceInstanceProfile(String instanceId, String
newInstanceProfileName, String profileAssociationId)
           throws InterruptedException {
       // Create an IAM instance profile specification.
       software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
iamInstanceProfile =
software.amazon.awssdk.services.ec2.model.IamInstanceProfileSpecification
               .builder()
               .name(newInstanceProfileName) // Make sure 'newInstanceProfileName'
is a valid IAM Instance Profile
                                             // name.
               .build();

       // Replace the IAM instance profile association for the EC2 instance.
       ReplaceIamInstanceProfileAssociationRequest replaceRequest =
ReplaceIamInstanceProfileAssociationRequest
               .builder()
               .iamInstanceProfile(iamInstanceProfile)
               .associationId(profileAssociationId) // Make sure
'profileAssociationId' is a valid association ID.
               .build();

       try {
           getEc2Client().replaceIamInstanceProfileAssociation(replaceRequest);
           // Handle the response as needed.
       } catch (Ec2Exception e) {
           // Handle exceptions, log, or report the error.
           System.err.println("Error: " + e.getMessage());
       }
       System.out.format("Replaced instance profile for association %s with profile
%s.", profileAssociationId,
               newInstanceProfileName);
       TimeUnit.SECONDS.sleep(15);
       boolean instReady = false;
       int tries = 0;

       // Reboot after 60 seconds
```

```
        while (!instReady) {
            if (tries % 6 == 0) {
                getEc2Client().rebootInstances(RebootInstancesRequest.builder()
                        .instanceIds(instanceId)
                        .build());
                System.out.println("Rebooting instance " + instanceId + " and
waiting for it to be ready.");
            }
            tries++;
            try {
                TimeUnit.SECONDS.sleep(10);
            } catch (InterruptedException e) {
                e.printStackTrace();
            }

            DescribeInstanceInformationResponse informationResponse =
getSSMClient().describeInstanceInformation();
            List<InstanceInformation> instanceInformationList =
informationResponse.instanceInformationList();
            for (InstanceInformation info : instanceInformationList) {
                if (info.instanceId().equals(instanceId)) {
                    instReady = true;
                    break;
                }
            }
        }

        SendCommandRequest sendCommandRequest = SendCommandRequest.builder()
                .instanceIds(instanceId)
                .documentName("AWS-RunShellScript")
                .parameters(Collections.singletonMap("commands",
                        Collections.singletonList("cd / && sudo python3 server.py
80")))
                .build();

        getSSMClient().sendCommand(sendCommandRequest);
        System.out.println("Restarted the Python web server on instance " +
instanceId + ".");
    }

    public void openInboundPort(String secGroupId, String port, String ipAddress) {
        AuthorizeSecurityGroupIngressRequest ingressRequest =
AuthorizeSecurityGroupIngressRequest.builder()
                .groupName(secGroupId)
```

```
                .cidrIp(ipAddress)
                .fromPort(Integer.parseInt(port))
                .build();

        getEc2Client().authorizeSecurityGroupIngress(ingressRequest);
        System.out.format("Authorized ingress to %s on port %s from %s.",
secGroupId, port, ipAddress);
    }

    /**
     * Detaches a role from an instance profile, detaches policies from the role,
     * and deletes all the resources.
     */
    public void deleteInstanceProfile(String roleName, String profileName) {
        try {
            software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
getInstanceProfileRequest =
software.amazon.awssdk.services.iam.model.GetInstanceProfileRequest
                    .builder()
                    .instanceProfileName(profileName)
                    .build();

            GetInstanceProfileResponse response =
getIAMClient().getInstanceProfile(getInstanceProfileRequest);
            String name = response.instanceProfile().instanceProfileName();
            System.out.println(name);

            RemoveRoleFromInstanceProfileRequest profileRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .roleName(roleName)
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(profileRequest);
            DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                    .instanceProfileName(profileName)
                    .build();

            getIAMClient().deleteInstanceProfile(deleteInstanceProfileRequest);
            System.out.println("Deleted instance profile " + profileName);

            DeleteRoleRequest deleteRoleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
```

```
                    .build();

            // List attached role policies.
            ListAttachedRolePoliciesResponse rolesResponse = getIAMClient()
                    .listAttachedRolePolicies(role -> role.roleName(roleName));
            List<AttachedPolicy> attachedPolicies =
rolesResponse.attachedPolicies();
            for (AttachedPolicy attachedPolicy : attachedPolicies) {
                DetachRolePolicyRequest request = DetachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(attachedPolicy.policyArn())
                        .build();

                getIAMClient().detachRolePolicy(request);
                System.out.println("Detached and deleted policy " +
attachedPolicy.policyName());
            }

            getIAMClient().deleteRole(deleteRoleRequest);
            System.out.println("Instance profile and role deleted.");

        } catch (IamException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public void deleteTemplate(String templateName) {
        getEc2Client().deleteLaunchTemplate(name ->
name.launchTemplateName(templateName));
        System.out.format(templateName + " was deleted.");
    }

    public void deleteAutoScaleGroup(String groupName) {
        DeleteAutoScalingGroupRequest deleteAutoScalingGroupRequest =
DeleteAutoScalingGroupRequest.builder()
                .autoScalingGroupName(groupName)
                .forceDelete(true)
                .build();


getAutoScalingClient().deleteAutoScalingGroup(deleteAutoScalingGroupRequest);
        System.out.println(groupName + " was deleted.");
    }
```

```
    /*
     * Verify the default security group of the specified VPC allows ingress from
     * this
     * computer. This can be done by allowing ingress from this computer's IP
     * address. In some situations, such as connecting from a corporate network, you
     * must instead specify a prefix list ID. You can also temporarily open the port
     * to
     * any IP address while running this example. If you do, be sure to remove
     * public
     * access when you're done.
     *
     */
    public GroupInfo verifyInboundPort(String VPC, int port, String ipAddress) {
        boolean portIsOpen = false;
        GroupInfo groupInfo = new GroupInfo();
        try {
            Filter filter = Filter.builder()
                    .name("group-name")
                    .values("default")
                    .build();

            Filter filter1 = Filter.builder()
                    .name("vpc-id")
                    .values(VPC)
                    .build();

            DescribeSecurityGroupsRequest securityGroupsRequest =
DescribeSecurityGroupsRequest.builder()
                    .filters(filter, filter1)
                    .build();

            DescribeSecurityGroupsResponse securityGroupsResponse = getEc2Client()
                    .describeSecurityGroups(securityGroupsRequest);
            String securityGroup =
securityGroupsResponse.securityGroups().get(0).groupName();
            groupInfo.setGroupName(securityGroup);

            for (SecurityGroup secGroup : securityGroupsResponse.securityGroups()) {
                System.out.println("Found security group: " + secGroup.groupId());

                for (IpPermission ipPermission : secGroup.ipPermissions()) {
                    if (ipPermission.fromPort() == port) {
                        System.out.println("Found inbound rule: " + ipPermission);
```

```
                        for (IpRange ipRange : ipPermission.ipRanges()) {
                            String cidrIp = ipRange.cidrIp();
                            if (cidrIp.startsWith(ipAddress) ||
cidrIp.equals("0.0.0.0/0")) {
                                System.out.println(cidrIp + " is applicable");
                                portIsOpen = true;
                            }
                        }

                        if (!ipPermission.prefixListIds().isEmpty()) {
                            System.out.println("Prefix lList is applicable");
                            portIsOpen = true;
                        }

                        if (!portIsOpen) {
                            System.out
                                    .println("The inbound rule does not appear to be
open to either this computer's IP,"
                                            + " all IP addresses (0.0.0.0/0), or to
a prefix list ID.");
                        } else {
                            break;
                        }
                    }
                }
            }

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }

        groupInfo.setPortOpen(portIsOpen);
        return groupInfo;
    }

    /*
     * Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
     * Scaling group.
     * The target group specifies how the load balancer forward requests to the
     * instances
     * in the group.
     */
    public void attachLoadBalancerTargetGroup(String asGroupName, String
targetGroupARN) {
```

```
        try {
            AttachLoadBalancerTargetGroupsRequest targetGroupsRequest =
AttachLoadBalancerTargetGroupsRequest.builder()
                    .autoScalingGroupName(asGroupName)
                    .targetGroupARNs(targetGroupARN)
                    .build();


getAutoScalingClient().attachLoadBalancerTargetGroups(targetGroupsRequest);
            System.out.println("Attached load balancer to " + asGroupName);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Creates an EC2 Auto Scaling group with the specified size.
    public String[] createGroup(int groupSize, String templateName, String
autoScalingGroupName) {

        // Get availability zones.
        software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
zonesRequest =
software.amazon.awssdk.services.ec2.model.DescribeAvailabilityZonesRequest
                .builder()
                .build();

        DescribeAvailabilityZonesResponse zonesResponse =
getEc2Client().describeAvailabilityZones(zonesRequest);
        List<String> availabilityZoneNames =
zonesResponse.availabilityZones().stream()

.map(software.amazon.awssdk.services.ec2.model.AvailabilityZone::zoneName)
                .collect(Collectors.toList());

        String availabilityZones = String.join(",", availabilityZoneNames);
        LaunchTemplateSpecification specification =
LaunchTemplateSpecification.builder()
                .launchTemplateName(templateName)
                .version("$Default")
                .build();

        String[] zones = availabilityZones.split(",");
```

```
        CreateAutoScalingGroupRequest groupRequest =
CreateAutoScalingGroupRequest.builder()
                .launchTemplate(specification)
                .availabilityZones(zones)
                .maxSize(groupSize)
                .minSize(groupSize)
                .autoScalingGroupName(autoScalingGroupName)
                .build();

        try {
            getAutoScalingClient().createAutoScalingGroup(groupRequest);

        } catch (AutoScalingException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Created an EC2 Auto Scaling group named " +
autoScalingGroupName);
        return zones;
    }

    public String getDefaultVPC() {
        // Define the filter.
        Filter defaultFilter = Filter.builder()
                .name("is-default")
                .values("true")
                .build();

        software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest request =
software.amazon.awssdk.services.ec2.model.DescribeVpcsRequest
                .builder()
                .filters(defaultFilter)
                .build();

        DescribeVpcsResponse response = getEc2Client().describeVpcs(request);
        return response.vpcs().get(0).vpcId();
    }

    // Gets the default subnets in a VPC for a specified list of Availability Zones.
    public List<Subnet> getSubnets(String vpcId, String[] availabilityZones) {
        List<Subnet> subnets = null;
        Filter vpcFilter = Filter.builder()
                .name("vpc-id")
                .values(vpcId)
```

```
                .build();

        Filter azFilter = Filter.builder()
                .name("availability-zone")
                .values(availabilityZones)
                .build();

        Filter defaultForAZ = Filter.builder()
                .name("default-for-az")
                .values("true")
                .build();

        DescribeSubnetsRequest request = DescribeSubnetsRequest.builder()
                .filters(vpcFilter, azFilter, defaultForAZ)
                .build();

        DescribeSubnetsResponse response = getEc2Client().describeSubnets(request);
        subnets = response.subnets();
        return subnets;
    }

    // Gets data about the instances in the EC2 Auto Scaling group.
    public String getBadInstance(String groupName) {
        DescribeAutoScalingGroupsRequest request =
DescribeAutoScalingGroupsRequest.builder()
                .autoScalingGroupNames(groupName)
                .build();

        DescribeAutoScalingGroupsResponse response =
getAutoScalingClient().describeAutoScalingGroups(request);
        AutoScalingGroup autoScalingGroup = response.autoScalingGroups().get(0);
        List<String> instanceIds = autoScalingGroup.instances().stream()
                .map(instance -> instance.instanceId())
                .collect(Collectors.toList());

        String[] instanceIdArray = instanceIds.toArray(new String[0]);
        for (String instanceId : instanceIdArray) {
            System.out.println("Instance ID: " + instanceId);
            return instanceId;
        }
        return "";
    }

    // Gets data about the profile associated with an instance.
```

```
    public String getInstanceProfile(String instanceId) {
        Filter filter = Filter.builder()
                .name("instance-id")
                .values(instanceId)
                .build();

        DescribeIamInstanceProfileAssociationsRequest associationsRequest =
 DescribeIamInstanceProfileAssociationsRequest
                .builder()
                .filters(filter)
                .build();

        DescribeIamInstanceProfileAssociationsResponse response = getEc2Client()
                .describeIamInstanceProfileAssociations(associationsRequest);
        return response.iamInstanceProfileAssociations().get(0).associationId();
    }

    public void deleteRolesPolicies(String policyName, String roleName, String
 InstanceProfile) {
        ListPoliciesRequest listPoliciesRequest =
 ListPoliciesRequest.builder().build();
        ListPoliciesResponse listPoliciesResponse =
 getIAMClient().listPolicies(listPoliciesRequest);
        for (Policy policy : listPoliciesResponse.policies()) {
            if (policy.policyName().equals(policyName)) {
                // List the entities (users, groups, roles) that are attached to the
 policy.

 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
 listEntitiesRequest =
 software.amazon.awssdk.services.iam.model.ListEntitiesForPolicyRequest
                        .builder()
                        .policyArn(policy.arn())
                        .build();
                ListEntitiesForPolicyResponse listEntitiesResponse = iamClient
                        .listEntitiesForPolicy(listEntitiesRequest);
                if (!listEntitiesResponse.policyGroups().isEmpty() || !
listEntitiesResponse.policyUsers().isEmpty()
                        || !listEntitiesResponse.policyRoles().isEmpty()) {
                    // Detach the policy from any entities it is attached to.
                    DetachRolePolicyRequest detachPolicyRequest =
 DetachRolePolicyRequest.builder()
                            .policyArn(policy.arn())
                            .roleName(roleName) // Specify the name of the IAM role
```

```
                            .build();

                    getIAMClient().detachRolePolicy(detachPolicyRequest);
                    System.out.println("Policy detached from entities.");
                }

                // Now, you can delete the policy.
                DeletePolicyRequest deletePolicyRequest =
DeletePolicyRequest.builder()
                        .policyArn(policy.arn())
                        .build();

                getIAMClient().deletePolicy(deletePolicyRequest);
                System.out.println("Policy deleted successfully.");
                break;
            }
        }

        // List the roles associated with the instance profile
        ListInstanceProfilesForRoleRequest listRolesRequest =
ListInstanceProfilesForRoleRequest.builder()
                .roleName(roleName)
                .build();

        // Detach the roles from the instance profile
        ListInstanceProfilesForRoleResponse listRolesResponse =
iamClient.listInstanceProfilesForRole(listRolesRequest);
        for (software.amazon.awssdk.services.iam.model.InstanceProfile profile :
listRolesResponse.instanceProfiles()) {
            RemoveRoleFromInstanceProfileRequest removeRoleRequest =
RemoveRoleFromInstanceProfileRequest.builder()
                    .instanceProfileName(InstanceProfile)
                    .roleName(roleName) // Remove the extra dot here
                    .build();

            getIAMClient().removeRoleFromInstanceProfile(removeRoleRequest);
            System.out.println("Role " + roleName + " removed from instance profile
" + InstanceProfile);
        }

        // Delete the instance profile after removing all roles
        DeleteInstanceProfileRequest deleteInstanceProfileRequest =
DeleteInstanceProfileRequest.builder()
                .instanceProfileName(InstanceProfile)
```

```
                .build();

        getIAMClient().deleteInstanceProfile(r ->
 r.instanceProfileName(InstanceProfile));
        System.out.println(InstanceProfile + " Deleted");
        System.out.println("All roles and policies are deleted.");
    }
}
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
public class LoadBalancer {
    public ElasticLoadBalancingV2Client elasticLoadBalancingV2Client;

    public ElasticLoadBalancingV2Client getLoadBalancerClient() {
        if (elasticLoadBalancingV2Client == null) {
            elasticLoadBalancingV2Client = ElasticLoadBalancingV2Client.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }

        return elasticLoadBalancingV2Client;
    }

    // Checks the health of the instances in the target group.
    public List<TargetHealthDescription> checkTargetHealth(String targetGroupName) {
        DescribeTargetGroupsRequest targetGroupsRequest =
 DescribeTargetGroupsRequest.builder()
                .names(targetGroupName)
                .build();

        DescribeTargetGroupsResponse tgResponse =
 getLoadBalancerClient().describeTargetGroups(targetGroupsRequest);

        DescribeTargetHealthRequest healthRequest =
 DescribeTargetHealthRequest.builder()
                .targetGroupArn(tgResponse.targetGroups().get(0).targetGroupArn())
                .build();

        DescribeTargetHealthResponse healthResponse =
 getLoadBalancerClient().describeTargetHealth(healthRequest);
        return healthResponse.targetHealthDescriptions();
```

```
    }

    // Gets the HTTP endpoint of the load balancer.
    public String getEndpoint(String lbName) {
        DescribeLoadBalancersResponse res = getLoadBalancerClient()
                .describeLoadBalancers(describe -> describe.names(lbName));
        return res.loadBalancers().get(0).dnsName();
    }

    // Deletes a load balancer.
    public void deleteLoadBalancer(String lbName) {
        try {
            // Use a waiter to delete the Load Balancer.
            DescribeLoadBalancersResponse res = getLoadBalancerClient()
                    .describeLoadBalancers(describe -> describe.names(lbName));
            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(res.loadBalancers().get(0).loadBalancerArn())
                    .build();

            getLoadBalancerClient().deleteLoadBalancer(
                    builder ->
builder.loadBalancerArn(res.loadBalancers().get(0).loadBalancerArn()));
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancersDeleted(request);
            waiterResponse.matched().response().ifPresent(System.out::println);

        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(lbName + " was deleted.");
    }

    // Deletes the target group.
    public void deleteTargetGroup(String targetGroupName) {
        try {
            DescribeTargetGroupsResponse res = getLoadBalancerClient()
                    .describeTargetGroups(describe ->
describe.names(targetGroupName));
            getLoadBalancerClient()
```

```
                    .deleteTargetGroup(builder ->
builder.targetGroupArn(res.targetGroups().get(0).targetGroupArn()));
        } catch (ElasticLoadBalancingV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println(targetGroupName + " was deleted.");
    }

    // Verify this computer can successfully send a GET request to the load balancer
    // endpoint.
    public boolean verifyLoadBalancerEndpoint(String elbDnsName) throws IOException,
InterruptedException {
        boolean success = false;
        int retries = 3;
        CloseableHttpClient httpClient = HttpClients.createDefault();

        // Create an HTTP GET request to the ELB.
        HttpGet httpGet = new HttpGet("http://" + elbDnsName);
        try {
            while ((!success) && (retries > 0)) {
                // Execute the request and get the response.
                HttpResponse response = httpClient.execute(httpGet);
                int statusCode = response.getStatusLine().getStatusCode();
                System.out.println("HTTP Status Code: " + statusCode);
                if (statusCode == 200) {
                    success = true;
                } else {
                    retries--;
                    System.out.println("Got connection error from load balancer
endpoint, retrying...");
                    TimeUnit.SECONDS.sleep(15);
                }
            }

        } catch (org.apache.http.conn.HttpHostConnectException e) {
            System.out.println(e.getMessage());
        }

        System.out.println("Status.." + success);
        return success;
    }

    /*
     * Creates an Elastic Load Balancing target group. The target group specifies
```

```
    * how
    * the load balancer forward requests to instances in the group and how instance
    * health is checked.
    */
   public String createTargetGroup(String protocol, int port, String vpcId, String
targetGroupName) {
       CreateTargetGroupRequest targetGroupRequest =
CreateTargetGroupRequest.builder()
               .healthCheckPath("/healthcheck")
               .healthCheckTimeoutSeconds(5)
               .port(port)
               .vpcId(vpcId)
               .name(targetGroupName)
               .protocol(protocol)
               .build();

       CreateTargetGroupResponse targetGroupResponse =
getLoadBalancerClient().createTargetGroup(targetGroupRequest);
       String targetGroupArn =
targetGroupResponse.targetGroups().get(0).targetGroupArn();
       String targetGroup =
targetGroupResponse.targetGroups().get(0).targetGroupName();
       System.out.println("The " + targetGroup + " was created with ARN" +
targetGroupArn);
       return targetGroupArn;
   }

   /*
    * Creates an Elastic Load Balancing load balancer that uses the specified
    * subnets
    * and forwards requests to the specified target group.
    */
   public String createLoadBalancer(List<Subnet> subnetIds, String targetGroupARN,
String lbName, int port,
           String protocol) {
       try {
           List<String> subnetIdStrings = subnetIds.stream()
                   .map(Subnet::subnetId)
                   .collect(Collectors.toList());

           CreateLoadBalancerRequest balancerRequest =
CreateLoadBalancerRequest.builder()
                   .subnets(subnetIdStrings)
                   .name(lbName)
```

```
                    .scheme("internet-facing")
                    .build();

            // Create and wait for the load balancer to become available.
            CreateLoadBalancerResponse lsResponse =
getLoadBalancerClient().createLoadBalancer(balancerRequest);
            String lbARN = lsResponse.loadBalancers().get(0).loadBalancerArn();

            ElasticLoadBalancingV2Waiter loadBalancerWaiter =
getLoadBalancerClient().waiter();
            DescribeLoadBalancersRequest request =
DescribeLoadBalancersRequest.builder()
                    .loadBalancerArns(lbARN)
                    .build();

            System.out.println("Waiting for Load Balancer " + lbName + " to become
available.");
            WaiterResponse<DescribeLoadBalancersResponse> waiterResponse =
loadBalancerWaiter
                    .waitUntilLoadBalancerAvailable(request);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Load Balancer " + lbName + " is available.");

            // Get the DNS name (endpoint) of the load balancer.
            String lbDNSName = lsResponse.loadBalancers().get(0).dnsName();
            System.out.println("*** Load Balancer DNS Name: " + lbDNSName);

            // Create a listener for the load balance.
            Action action = Action.builder()
                    .targetGroupArn(targetGroupARN)
                    .type("forward")
                    .build();

            CreateListenerRequest listenerRequest = CreateListenerRequest.builder()

.loadBalancerArn(lsResponse.loadBalancers().get(0).loadBalancerArn())
                    .defaultActions(action)
                    .port(port)
                    .protocol(protocol)
                    .defaultActions(action)
                    .build();

            getLoadBalancerClient().createListener(listenerRequest);
```

```
            System.out.println("Created listener to forward traffic from load
 balancer " + lbName + " to target group "
                    + targetGroupARN);

            // Return the load balancer DNS name.
            return lbDNSName;

        } catch (ElasticLoadBalancingV2Exception e) {
            e.printStackTrace();
        }
        return "";
    }
}
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
public class Database {

    private static DynamoDbClient dynamoDbClient;

    public static DynamoDbClient getDynamoDbClient() {
        if (dynamoDbClient == null) {
            dynamoDbClient = DynamoDbClient.builder()
                    .region(Region.US_EAST_1)
                    .build();
        }
        return dynamoDbClient;
    }

    // Checks to see if the Amazon DynamoDB table exists.
    private boolean doesTableExist(String tableName) {
        try {
            // Describe the table and catch any exceptions.
            DescribeTableRequest describeTableRequest =
 DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            getDynamoDbClient().describeTable(describeTableRequest);
            System.out.println("Table '" + tableName + "' exists.");
            return true;
```

```
        } catch (ResourceNotFoundException e) {
            System.out.println("Table '" + tableName + "' does not exist.");
        } catch (DynamoDbException e) {
            System.err.println("Error checking table existence: " + e.getMessage());
        }
        return false;
    }

    /*
     * Creates a DynamoDB table to use a recommendation service. The table has a
     * hash key named 'MediaType' that defines the type of media recommended, such
     * as
     * Book or Movie, and a range key named 'ItemId' that, combined with the
     * MediaType,
     * forms a unique identifier for the recommended item.
     */
    public void createTable(String tableName, String fileName) throws IOException {
        // First check to see if the table exists.
        boolean doesExist = doesTableExist(tableName);
        if (!doesExist) {
            DynamoDbWaiter dbWaiter = getDynamoDbClient().waiter();
            CreateTableRequest createTableRequest = CreateTableRequest.builder()
                    .tableName(tableName)
                    .attributeDefinitions(
                            AttributeDefinition.builder()
                                    .attributeName("MediaType")
                                    .attributeType(ScalarAttributeType.S)
                                    .build(),
                            AttributeDefinition.builder()
                                    .attributeName("ItemId")
                                    .attributeType(ScalarAttributeType.N)
                                    .build())
                    .keySchema(
                            KeySchemaElement.builder()
                                    .attributeName("MediaType")
                                    .keyType(KeyType.HASH)
                                    .build(),
                            KeySchemaElement.builder()
                                    .attributeName("ItemId")
                                    .keyType(KeyType.RANGE)
                                    .build())
                    .provisionedThroughput(
                            ProvisionedThroughput.builder()
                                    .readCapacityUnits(5L)
```

```
                                    .writeCapacityUnits(5L)
                                    .build())
                    .build();

            getDynamoDbClient().createTable(createTableRequest);
            System.out.println("Creating table " + tableName + "...");

            // Wait until the Amazon DynamoDB table is created.
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                    .tableName(tableName)
                    .build();

            WaiterResponse<DescribeTableResponse> waiterResponse =
dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("Table " + tableName + " created.");

            // Add records to the table.
            populateTable(fileName, tableName);
        }
    }

    public void deleteTable(String tableName) {
        getDynamoDbClient().deleteTable(table -> table.tableName(tableName));
        System.out.println("Table " + tableName + " deleted.");
    }

    // Populates the table with data located in a JSON file using the DynamoDB
    // enhanced client.
    public void populateTable(String fileName, String tableName) throws IOException
{
        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
                .dynamoDbClient(getDynamoDbClient())
                .build();
        ObjectMapper objectMapper = new ObjectMapper();
        File jsonFile = new File(fileName);
        JsonNode rootNode = objectMapper.readTree(jsonFile);

        DynamoDbTable<Recommendation> mappedTable = enhancedClient.table(tableName,
                TableSchema.fromBean(Recommendation.class));
        for (JsonNode currentNode : rootNode) {
            String mediaType = currentNode.path("MediaType").path("S").asText();
            int itemId = currentNode.path("ItemId").path("N").asInt();
            String title = currentNode.path("Title").path("S").asText();
```

```
            String creator = currentNode.path("Creator").path("S").asText();

            // Create a Recommendation object and set its properties.
            Recommendation rec = new Recommendation();
            rec.setMediaType(mediaType);
            rec.setItemId(itemId);
            rec.setTitle(title);
            rec.setCreator(creator);

            // Put the item into the DynamoDB table.
            mappedTable.putItem(rec); // Add the Recommendation to the list.
        }
        System.out.println("Added all records to the " + tableName);
    }
}
```

Crie uma classe que envolva as ações do Systems Manager.

```
public class ParameterHelper {

    String tableName = "doc-example-resilient-architecture-table";
    String dyntable = "doc-example-recommendation-service";
    String failureResponse = "doc-example-resilient-architecture-failure-response";
    String healthCheck = "doc-example-resilient-architecture-health-check";

    public void reset() {
        put(dyntable, tableName);
        put(failureResponse, "none");
        put(healthCheck, "shallow");
    }

    public void put(String name, String value) {
        SsmClient ssmClient = SsmClient.builder()
                .region(Region.US_EAST_1)
                .build();

        PutParameterRequest parameterRequest = PutParameterRequest.builder()
                .name(name)
                .value(value)
                .overwrite(true)
                .type("String")
                .build();
```

```
        ssmClient.putParameter(parameterRequest);
        System.out.printf("Setting demo parameter %s to '%s'.", name, value);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances
  - DescribeLoadBalancers
  - DescribeSubnets
  - DescribeTargetGroups
  - DescribeTargetHealth
  - DescribeVpcs
  - RebootInstances
  - ReplaceIamInstanceProfileAssociation
  - TerminateInstanceInAutoScalingGroup

- UpdateAutoScalingGroup

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
/*
  To run this Java V2 code example, set up your development environment, including
 your credentials.

  For information, see this documentation topic:

  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html

  This example performs these operations:

  1. Creates a user that has no permissions.
```

```
  2. Creates a role and policy that grants Amazon S3 permissions.
  3. Creates a role.
  4. Grants the user permissions.
  5. Gets temporary credentials by assuming the role.  Creates an Amazon S3 Service
 client object with the temporary credentials.
  6. Deletes the resources.
 */

public class IAMScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");
    public static final String PolicyDocument = "{" +
            "  \"Version\": \"2012-10-17\"," +
            "  \"Statement\": [" +
            "    {" +
            "        \"Effect\": \"Allow\"," +
            "        \"Action\": [" +
            "            \"s3:*\"" +
            "       ]," +
            "       \"Resource\": \"*\"" +
            "    }" +
            "   ]" +
            "}";

    public static String userArn;

    public static void main(String[] args) throws Exception {

        final String usage = """

                Usage:
                    <username> <policyName> <roleName> <roleSessionName>
 <bucketName>\s

                Where:
                    username - The name of the IAM user to create.\s
                    policyName - The name of the policy to create.\s
                    roleName - The name of the role to create.\s
                    roleSessionName - The name of the session required for the
 assumeRole operation.\s
                    bucketName - The name of the Amazon S3 bucket from which objects
 are read.\s
                """;

        if (args.length != 5) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String userName = args[0];
        String policyName = args[1];
        String roleName = args[2];
        String roleSessionName = args[3];
        String bucketName = args[4];

        Region region = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS IAM example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(" 1. Create the IAM user.");
        User createUser = createIAMUser(iam, userName);

        System.out.println(DASHES);
        userArn = createUser.arn();

        AccessKey myKey = createIAMAccessKey(iam, userName);
        String accessKey = myKey.accessKeyId();
        String secretKey = myKey.secretAccessKey();
        String assumeRolePolicyDocument = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                " \"AWS\": \"" + userArn + "\"" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        System.out.println(assumeRolePolicyDocument);
        System.out.println(userName + " was successfully created.");
        System.out.println(DASHES);
        System.out.println("2. Creates a policy.");
```

```
        String polArn = createIAMPolicy(iam, policyName);
        System.out.println("The policy " + polArn + " was successfully created.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Creates a role.");
        TimeUnit.SECONDS.sleep(30);
        String roleArn = createIAMRole(iam, roleName, assumeRolePolicyDocument);
        System.out.println(roleArn + " was successfully created.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Grants the user permissions.");
        attachIAMRolePolicy(iam, roleName, polArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("*** Wait for 30 secs so the resource is available");
        TimeUnit.SECONDS.sleep(30);
        System.out.println("5. Gets temporary credentials by assuming the role.");
        System.out.println("Perform an Amazon S3 Service operation using the
temporary credentials.");
        assumeRole(roleArn, roleSessionName, bucketName, accessKey, secretKey);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6 Getting ready to delete the AWS resources");
        deleteKey(iam, userName, accessKey);
        deleteRole(iam, roleName, polArn);
        deleteIAMUser(iam, userName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("This IAM Scenario has successfully completed");
        System.out.println(DASHES);
    }

    public static AccessKey createIAMAccessKey(IamClient iam, String user) {
        try {
            CreateAccessKeyRequest request = CreateAccessKeyRequest.builder()
                    .userName(user)
                    .build();

            CreateAccessKeyResponse response = iam.createAccessKey(request);
```

```
            return response.accessKey();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static User createIAMUser(IamClient iam, String username) {
        try {
            // Create an IamWaiter object
            IamWaiter iamWaiter = iam.waiter();
            CreateUserRequest request = CreateUserRequest.builder()
                    .userName(username)
                    .build();

            // Wait until the user is created.
            CreateUserResponse response = iam.createUser(request);
            GetUserRequest userRequest = GetUserRequest.builder()
                    .userName(response.user().userName())
                    .build();

            WaiterResponse<GetUserResponse> waitUntilUserExists =
iamWaiter.waitUntilUserExists(userRequest);
            waitUntilUserExists.matched().response().ifPresent(System.out::println);
            return response.user();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static String createIAMRole(IamClient iam, String rolename, String json)
{

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(rolename)
                    .assumeRolePolicyDocument(json)
                    .description("Created using the AWS SDK for Java")
                    .build();
```

```
            CreateRoleResponse response = iam.createRole(request);
            System.out.println("The ARN of the role is " + response.role().arn());
            return response.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createIAMPolicy(IamClient iam, String policyName) {
        try {
            // Create an IamWaiter object.
            IamWaiter iamWaiter = iam.waiter();
            CreatePolicyRequest request = CreatePolicyRequest.builder()
                    .policyName(policyName)
                    .policyDocument(PolicyDocument).build();

            CreatePolicyResponse response = iam.createPolicy(request);
            GetPolicyRequest polRequest = GetPolicyRequest.builder()
                    .policyArn(response.policy().arn())
                    .build();

            WaiterResponse<GetPolicyResponse> waitUntilPolicyExists =
iamWaiter.waitUntilPolicyExists(polRequest);

waitUntilPolicyExists.matched().response().ifPresent(System.out::println);
            return response.policy().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void attachIAMRolePolicy(IamClient iam, String roleName, String
policyArn) {
        try {
            ListAttachedRolePoliciesRequest request =
ListAttachedRolePoliciesRequest.builder()
                    .roleName(roleName)
```

```
                    .build();

            ListAttachedRolePoliciesResponse response =
iam.listAttachedRolePolicies(request);
            List<AttachedPolicy> attachedPolicies = response.attachedPolicies();
            String polArn;
            for (AttachedPolicy policy : attachedPolicies) {
                polArn = policy.policyArn();
                if (polArn.compareTo(policyArn) == 0) {
                    System.out.println(roleName + " policy is already attached to
this role.");
                    return;
                }
            }

            AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                    .roleName(roleName)
                    .policyArn(policyArn)
                    .build();

            iam.attachRolePolicy(attachRequest);
            System.out.println("Successfully attached policy " + policyArn + " to
role " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Invoke an Amazon S3 operation using the Assumed Role.
    public static void assumeRole(String roleArn, String roleSessionName, String
bucketName, String keyVal,
            String keySecret) {

        // Use the creds of the new IAM user that was created in this code example.
        AwsBasicCredentials credentials = AwsBasicCredentials.create(keyVal,
keySecret);
        StsClient stsClient = StsClient.builder()
                .region(Region.US_EAST_1)
                .credentialsProvider(StaticCredentialsProvider.create(credentials))
                .build();
```

```
        try {
            AssumeRoleRequest roleRequest = AssumeRoleRequest.builder()
                    .roleArn(roleArn)
                    .roleSessionName(roleSessionName)
                    .build();

            AssumeRoleResponse roleResponse = stsClient.assumeRole(roleRequest);
            Credentials myCreds = roleResponse.credentials();
            String key = myCreds.accessKeyId();
            String secKey = myCreds.secretAccessKey();
            String secToken = myCreds.sessionToken();

            // List all objects in an Amazon S3 bucket using the temp creds
retrieved by
            // invoking assumeRole.
            Region region = Region.US_EAST_1;
            S3Client s3 = S3Client.builder()
                    .credentialsProvider(

StaticCredentialsProvider.create(AwsSessionCredentials.create(key, secKey,
secToken)))
                    .region(region)
                    .build();

            System.out.println("Created a S3Client using temp credentials.");
            System.out.println("Listing objects in " + bucketName);
            ListObjectsRequest listObjects = ListObjectsRequest.builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.println("The name of the key is " + myValue.key());
                System.out.println("The owner is " + myValue.owner());
            }

        } catch (StsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void deleteRole(IamClient iam, String roleName, String polArn) {
```

```
        try {
            // First the policy needs to be detached.
            DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
                    .policyArn(polArn)
                    .roleName(roleName)
                    .build();

            iam.detachRolePolicy(rolePolicyRequest);

            // Delete the policy.
            DeletePolicyRequest request = DeletePolicyRequest.builder()
                    .policyArn(polArn)
                    .build();

            iam.deletePolicy(request);
            System.out.println("*** Successfully deleted " + polArn);

            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteKey(IamClient iam, String username, String accessKey) {
        try {
            DeleteAccessKeyRequest request = DeleteAccessKeyRequest.builder()
                    .accessKeyId(accessKey)
                    .userName(username)
                    .build();

            iam.deleteAccessKey(request);
            System.out.println("Successfully deleted access key " + accessKey +
                    " from user " + username);
```

```
        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteIAMUser(IamClient iam, String userName) {
        try {
            DeleteUserRequest request = DeleteUserRequest.builder()
                    .userName(userName)
                    .build();

            iam.deleteUser(request);
            System.out.println("*** Successfully deleted " + userName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Trabalhar com a API IAM Policy Builder

O código de exemplo a seguir mostra como:

- Crie políticas do IAM usando a API orientada por objetos.
- Use a API IAM Policy Builder com o serviço do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos usam as importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.policybuilder.iam.IamConditionOperator;
import software.amazon.awssdk.policybuilder.iam.IamEffect;
import software.amazon.awssdk.policybuilder.iam.IamPolicy;
import software.amazon.awssdk.policybuilder.iam.IamPolicyWriter;
import software.amazon.awssdk.policybuilder.iam.IamPrincipal;
import software.amazon.awssdk.policybuilder.iam.IamPrincipalType;
import software.amazon.awssdk.policybuilder.iam.IamResource;
import software.amazon.awssdk.policybuilder.iam.IamStatement;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iam.IamClient;
import software.amazon.awssdk.services.iam.model.GetPolicyResponse;
import software.amazon.awssdk.services.iam.model.GetPolicyVersionResponse;
import software.amazon.awssdk.services.sts.StsClient;

import java.net.URLDecoder;
import java.nio.charset.StandardCharsets;
import java.util.Arrays;
import java.util.List;
```

Crie uma política com base no tempo.

```
        public String timeBasedPolicyExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:GetItem")
                                                .addResource(IamResource.ALL)
                                                .addCondition(b1 -> b1

.operator(IamConditionOperator.DATE_GREATER_THAN)

.key("aws:CurrentTime")

.value("2020-04-01T00:00:00Z"))
                                                .addCondition(b1 -> b1

.operator(IamConditionOperator.DATE_LESS_THAN)

.key("aws:CurrentTime")

.value("2020-06-30T23:59:59Z")))
                                .build();

                // Use an IamPolicyWriter to write out the JSON string to a more
readable
                // format.
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true)
                                .build());
        }
```

Crie uma política com várias condições.

```
        public String multipleConditionsExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:GetItem")
                                                .addAction("dynamodb:BatchGetItem")
                                                .addAction("dynamodb:Query")
                                                .addAction("dynamodb:PutItem")
                                                .addAction("dynamodb:UpdateItem")
                                                .addAction("dynamodb:DeleteItem")
```

```
 .addAction("dynamodb:BatchWriteItem")

 .addResource("arn:aws:dynamodb:*:*:table/table-name")

 .addConditions(IamConditionOperator.STRING_EQUALS

 .addPrefix("ForAllValues:"),

 "dynamodb:Attributes",
                                                                    List.of("column-
name1", "column-name2", "column-name3"))
                                                  .addCondition(b1 -> b1

 .operator(IamConditionOperator.STRING_EQUALS

 .addSuffix("IfExists"))

 .key("dynamodb:Select")

 .value("SPECIFIC_ATTRIBUTES")))
                                .build();

                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Use entidades principais em uma política.

```
        public String specifyPrincipalsExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.DENY)
                                                .addAction("s3:*")
                                                .addPrincipal(IamPrincipal.ALL)

 .addResource("arn:aws:s3:::BUCKETNAME/*")

 .addResource("arn:aws:s3:::BUCKETNAME")
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.ARN_NOT_EQUALS)
```

```
 .key("aws:PrincipalArn")

 .value("arn:aws:iam::444455556666:user/user-name")))
                                .build();
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Permitir o acesso entre contas ao .

```
        public String allowCrossAccountAccessExample() {
                IamPolicy policy = IamPolicy.builder()
                                .addStatement(b -> b
                                                .effect(IamEffect.ALLOW)
                                                .addPrincipal(IamPrincipalType.AWS,
 "111122223333")
                                                .addAction("s3:PutObject")
                                                .addResource("arn:aws:s3:::DOC-
EXAMPLE-BUCKET/*")
                                                .addCondition(b1 -> b1

 .operator(IamConditionOperator.STRING_EQUALS)
                                                                .key("s3:x-amz-acl")
                                                                .value("bucket-
owner-full-control")))
                                .build();
                return policy.toJson(IamPolicyWriter.builder()
                                .prettyPrint(true).build());
        }
```

Crie e carregue uma `IamPolicy`.

```
        public String createAndUploadPolicyExample(IamClient iam, String accountID,
 String policyName) {
                // Build the policy.
                IamPolicy policy = IamPolicy.builder() // 'version' defaults to
 "2012-10-17".
                                .addStatement(IamStatement.builder()
                                                .effect(IamEffect.ALLOW)
                                                .addAction("dynamodb:PutItem")
```

```
                                                    .addResource("arn:aws:dynamodb:us-
east-1:" + accountID
                                                                 + ":table/
exampleTableName")
                                                    .build())
                                .build();
                // Upload the policy.
                iam.createPolicy(r ->
 r.policyName(policyName).policyDocument(policy.toJson()));
                return
 policy.toJson(IamPolicyWriter.builder().prettyPrint(true).build());
        }
```

Baixe e trabalhe com uma `IamPolicy`.

```
        public String createNewBasedOnExistingPolicyExample(IamClient iam, String
 accountID, String policyName,
                        String newPolicyName) {

                String policyArn = "arn:aws:iam::" + accountID + ":policy/" +
 policyName;
                GetPolicyResponse getPolicyResponse = iam.getPolicy(r ->
 r.policyArn(policyArn));

                String policyVersion =
 getPolicyResponse.policy().defaultVersionId();
                GetPolicyVersionResponse getPolicyVersionResponse = iam
                                .getPolicyVersion(r ->
 r.policyArn(policyArn).versionId(policyVersion));

                // Create an IamPolicy instance from the JSON string returned from
 IAM.
                String decodedPolicy =
 URLDecoder.decode(getPolicyVersionResponse.policyVersion().document(),
                                StandardCharsets.UTF_8);
                IamPolicy policy = IamPolicy.fromJson(decodedPolicy);

                /*
                 * All IamPolicy components are immutable, so use the copy method
 that creates a
                 * new instance that
                 * can be altered in the same method call.
```

```
                 *
                 * Add the ability to get an item from DynamoDB as an additional
action.
                 */
                IamStatement newStatement = policy.statements().get(0).copy(s ->
s.addAction("dynamodb:GetItem"));

                // Create a new statement that replaces the original statement.
                IamPolicy newPolicy = policy.copy(p ->
p.statements(Arrays.asList(newStatement)));

                // Upload the new policy. IAM now has both policies.
                iam.createPolicy(r -> r.policyName(newPolicyName)
                                .policyDocument(newPolicy.toJson()));

                return
newPolicy.toJson(IamPolicyWriter.builder().prettyPrint(true).build());
        }
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Java 2.x.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreatePolicy
  - GetPolicy
  - GetPolicyVersion

Exemplos do AWS IoT usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS IoT.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS IoT

O exemplo de código a seguir mostra como começar a usar o AWS IoT.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iot.IotClient;
import software.amazon.awssdk.services.iot.model.ListThingsRequest;
import software.amazon.awssdk.services.iot.model.ListThingsResponse;
import software.amazon.awssdk.services.iot.model.ThingAttribute;
import java.util.List;

public class HelloIoT {
    public static void main(String[] args) {
        System.out.println("Hello AWS IoT. Here is a listing of your AWS IoT
 Things:");
        IotClient iotClient = IotClient.builder()
            .region(Region.US_EAST_1)
            .build();

        listAllThings(iotClient);
    }

    public static void listAllThings( IotClient iotClient) {
        ListThingsRequest thingsRequest = ListThingsRequest.builder()
            .maxResults(10)
            .build();

        ListThingsResponse response = iotClient.listThings(thingsRequest) ;
        List<ThingAttribute> thingList = response.things();
        for (ThingAttribute attribute : thingList) {
```

```
            System.out.println("Thing name: "+attribute.thingName());
            System.out.println("Thing ARN: "+attribute.thingArn());
        }
    }
}
```

- Para obter detalhes da API, consulte ListThings na Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Anexar um certificado

O exemplo de código a seguir mostra como anexar um AWS IoT certificado.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void attachCertificateToThing(IotClient iotClient, String
thingName, String certificateArn) {
       // Attach the certificate to the thing.
       AttachThingPrincipalRequest principalRequest =
AttachThingPrincipalRequest.builder()
           .thingName(thingName)
           .principal(certificateArn)
           .build();

       AttachThingPrincipalResponse attachResponse =
iotClient.attachThingPrincipal(principalRequest);

       // Verify the attachment was successful.
```

```
        if (attachResponse.sdkHttpResponse().isSuccessful()) {
            System.out.println("Certificate attached to Thing successfully.");

            // Print additional information about the Thing.
            describeThing(iotClient, thingName);
        } else {
            System.err.println("Failed to attach certificate to Thing. HTTP Status
Code: " +
                attachResponse.sdkHttpResponse().statusCode());
        }
    }
```

- Para obter detalhes da API, consulte AttachThingPrincipala Referência AWS SDK for Java 2.x da API.

Criar um certificado

O exemplo de código a seguir mostra como criar um AWS IoT certificado.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createCertificate(IotClient iotClient) {
        try {
            CreateKeysAndCertificateResponse response =
iotClient.createKeysAndCertificate();
            String certificatePem = response.certificatePem();
            String certificateArn = response.certificateArn();

            // Print the details.
            System.out.println("\nCertificate:");
            System.out.println(certificatePem);
            System.out.println("\nCertificate ARN:");
            System.out.println(certificateArn);
            return certificateArn;
```

```
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
```

- Para obter detalhes da API, consulte CreateKeysAndCertificatea Referência AWS SDK for Java 2.x da API.

Criar uma regra

O exemplo de código a seguir mostra como criar uma AWS IoT regra.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void createIoTRule(IotClient iotClient, String roleARN, String
ruleName, String action) {
        try {
            String sql = "SELECT * FROM '" + TOPIC + "'";
            SnsAction action1 = SnsAction.builder()
                .targetArn(action)
                .roleArn(roleARN)
                .build();

            // Create the action.
            Action myAction = Action.builder()
                .sns(action1)
                .build();

            // Create the topic rule payload.
            TopicRulePayload topicRulePayload = TopicRulePayload.builder()
```

```
                .sql(sql)
                .actions(myAction)
                .build();

            // Create the topic rule request.
            CreateTopicRuleRequest topicRuleRequest =
CreateTopicRuleRequest.builder()
                .ruleName(ruleName)
                .topicRulePayload(topicRulePayload)
                .build();

            // Create the rule.
            iotClient.createTopicRule(topicRuleRequest);
            System.out.println("IoT Rule created successfully.");

        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateTopicRulea Referência AWS SDK for Java 2.x da API.

Criar um objeto

O exemplo de código a seguir mostra como criar AWS IoT algo.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void createIoTThing(IotClient iotClient, String thingName) {
        try {
            CreateThingRequest createThingRequest = CreateThingRequest.builder()
                .thingName(thingName)
                .build();
```

```
            CreateThingResponse createThingResponse =
iotClient.createThing(createThingRequest);
            System.out.println(thingName +" was successfully created. The ARN value
is " + createThingResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateThinga Referência AWS SDK for Java 2.x da API.

Excluir um certificado

O exemplo de código a seguir mostra como excluir um AWS IoT certificado.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void deleteCertificate(IotClient iotClient, String
certificateArn ) {
        DeleteCertificateRequest certificateProviderRequest =
DeleteCertificateRequest.builder()
            .certificateId(extractCertificateId(certificateArn))
            .build();

        iotClient.deleteCertificate(certificateProviderRequest);
        System.out.println(certificateArn +" was successfully deleted.");
    }
```

- Para obter detalhes da API, consulte DeleteCertificatea Referência AWS SDK for Java 2.x da API.

Excluir um objeto

O exemplo de código a seguir mostra como excluir AWS IoT algo.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void deleteIoTThing(IotClient iotClient, String thingName) {
    try {
        DeleteThingRequest deleteThingRequest = DeleteThingRequest.builder()
            .thingName(thingName)
            .build();

        iotClient.deleteThing(deleteThingRequest);
        System.out.println("Deleted Thing " + thingName);

    } catch (IotException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}
```

- Para obter detalhes da API, consulte DeleteThinga Referência AWS SDK for Java 2.x da API.

Descreva uma coisa

O exemplo de código a seguir mostra como descrever qualquer AWS IoT coisa.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    private static void describeThing(IotClient iotClient, String thingName) {
        try {
            DescribeThingRequest thingRequest = DescribeThingRequest.builder()
                .thingName(thingName)
                .build() ;

            // Print Thing details.
            DescribeThingResponse describeResponse =
iotClient.describeThing(thingRequest);
            System.out.println("Thing Details:");
            System.out.println("Thing Name: " + describeResponse.thingName());
            System.out.println("Thing ARN: " + describeResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeThinga Referência AWS SDK for Java 2.x da API.

Desanexar um certificado

O exemplo de código a seguir mostra como desanexar um AWS IoT certificado.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void detachThingPrincipal(IotClient iotClient, String thingName,
String certificateArn){
        try {
            DetachThingPrincipalRequest thingPrincipalRequest =
DetachThingPrincipalRequest.builder()
                .principal(certificateArn)
```

```
                .thingName(thingName)
                .build();

            iotClient.detachThingPrincipal(thingPrincipalRequest);
            System.out.println(certificateArn +" was successfully removed from "
+thingName);

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DetachThingPrincipala Referência AWS SDK for Java 2.x da API.

Obter informações do endpoint

O exemplo de código a seguir mostra como obter informação de endpoint AWS IoT.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String describeEndpoint(IotClient iotClient) {
        try {
            DescribeEndpointResponse endpointResponse =
iotClient.describeEndpoint(DescribeEndpointRequest.builder().build());

            // Get the endpoint URL.
            String endpointUrl = endpointResponse.endpointAddress();
            String exString = getValue(endpointUrl);
            String fullEndpoint = "https://"+exString+"-ats.iot.us-
east-1.amazonaws.com";

            System.out.println("Full Endpoint URL: "+fullEndpoint);
            return fullEndpoint;
```

```
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "" ;
    }
```

- Para obter detalhes da API, consulte DescribeEndpointa Referência AWS SDK for Java 2.x da API.

Liste seus certificados

O exemplo de código a seguir mostra como listar seus AWS IoT certificados.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listCertificates(IotClient iotClient) {
        ListCertificatesResponse response = iotClient.listCertificates();
        List<Certificate> certList = response.certificates();
        for (Certificate cert : certList) {
            System.out.println("Cert id: " + cert.certificateId());
            System.out.println("Cert Arn: " + cert.certificateArn());
        }
    }
```

- Para obter detalhes da API, consulte ListCertificatesa Referência AWS SDK for Java 2.x da API.

Consulte o índice de pesquisa

O exemplo de código a seguir mostra como consultar o índice AWS IoT de pesquisa.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void searchThings(IotClient iotClient, String queryString){
       SearchIndexRequest searchIndexRequest = SearchIndexRequest.builder()
           .queryString(queryString)
           .build();

       try {
           // Perform the search and get the result.
           SearchIndexResponse searchIndexResponse =
iotClient.searchIndex(searchIndexRequest);

           // Process the result.
           if (searchIndexResponse.things().isEmpty()) {
               System.out.println("No things found.");
           } else {
               searchIndexResponse.things().forEach(thing ->
System.out.println("Thing id found using search is " + thing.thingId()));
           }
       } catch (IotException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte SearchIndexa Referência AWS SDK for Java 2.x da API.

Atualizar um objeto

O exemplo de código a seguir mostra como atualizar qualquer AWS IoT coisa.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void updateThing(IotClient iotClient, String thingName) {
    // Specify the new attribute values.
    String newLocation = "Office";
    String newFirmwareVersion = "v2.0";

    Map<String, String> attMap = new HashMap<>();
    attMap.put("location", newLocation);
    attMap.put("firmwareVersion", newFirmwareVersion);

    AttributePayload attributePayload = AttributePayload.builder()
        .attributes(attMap)
        .build();

    UpdateThingRequest updateThingRequest = UpdateThingRequest.builder()
        .thingName(thingName)
        .attributePayload(attributePayload)
        .build();

    try {
        // Update the IoT Thing attributes.
        iotClient.updateThing(updateThingRequest);
        System.out.println("Thing attributes updated successfully.");

    } catch (IotException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}
```

- Para obter detalhes da API, consulte UpdateThinga Referência AWS SDK for Java 2.x da API.

Cenários

Trabalhando com casos de uso de gerenciamento de dispositivos

O exemplo de código a seguir mostra como trabalhar com casos de uso de gerenciamento de AWS IoT dispositivos usando o AWS IoT SDK

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.iot.IotClient;
import software.amazon.awssdk.services.iot.model.Action;
import software.amazon.awssdk.services.iot.model.AttachThingPrincipalRequest;
import software.amazon.awssdk.services.iot.model.AttachThingPrincipalResponse;
import software.amazon.awssdk.services.iot.model.AttributePayload;
import software.amazon.awssdk.services.iot.model.Certificate;
import software.amazon.awssdk.services.iot.model.CreateKeysAndCertificateResponse;
import software.amazon.awssdk.services.iot.model.CreateThingRequest;
import software.amazon.awssdk.services.iot.model.CreateTopicRuleRequest;
import software.amazon.awssdk.services.iot.model.DeleteCertificateRequest;
import software.amazon.awssdk.services.iot.model.CreateThingResponse;
import software.amazon.awssdk.services.iot.model.DeleteThingRequest;
import software.amazon.awssdk.services.iot.model.DescribeEndpointRequest;
import software.amazon.awssdk.services.iot.model.DescribeEndpointResponse;
import software.amazon.awssdk.services.iot.model.DescribeThingRequest;
import software.amazon.awssdk.services.iot.model.DescribeThingResponse;
import software.amazon.awssdk.services.iot.model.DetachThingPrincipalRequest;
import software.amazon.awssdk.services.iot.model.IotException;
import software.amazon.awssdk.services.iot.model.ListCertificatesResponse;
import software.amazon.awssdk.services.iot.model.ListTopicRulesRequest;
import software.amazon.awssdk.services.iot.model.ListTopicRulesResponse;
import software.amazon.awssdk.services.iot.model.SearchIndexRequest;
import software.amazon.awssdk.services.iot.model.SearchIndexResponse;
import software.amazon.awssdk.services.iot.model.SnsAction;
import software.amazon.awssdk.services.iot.model.TopicRuleListItem;
import software.amazon.awssdk.services.iot.model.TopicRulePayload;
```

```
import software.amazon.awssdk.services.iot.model.UpdateThingRequest;
import software.amazon.awssdk.services.iotdataplane.IotDataPlaneClient;
import software.amazon.awssdk.services.iotdataplane.model.GetThingShadowRequest;
import software.amazon.awssdk.services.iotdataplane.model.GetThingShadowResponse;
import software.amazon.awssdk.services.iotdataplane.model.UpdateThingShadowRequest;
import java.net.URI;
import java.nio.charset.StandardCharsets;
import java.util.HashMap;
import java.util.List;
import java.util.Map;
import java.util.Scanner;
import java.util.regex.Matcher;
import java.util.regex.Pattern;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java example performs these tasks:
 *
 * 1. Creates an AWS IoT Thing.
 * 2. Generate and attach a device certificate.
 * 3. Update an AWS IoT Thing with Attributes.
 * 4. Get an AWS IoT Endpoint.
 * 5. List your certificates.
 * 6. Updates the shadow for the specified thing..
 * 7. Write out the state information, in JSON format
 * 8. Creates a rule
 * 9. List rules
 * 10. Search things
 * 11. Detach amd delete the certificate.
 * 12. Delete Thing.
 */
public class IotScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");
    private static final String TOPIC = "your-iot-topic";
    public static void main(String[] args) {
        final String usage =
            """
                Usage:
```

```
                    <roleARN> <snsAction>

                Where:
                    roleARN - The ARN of an IAM role that has permission to work
with AWS IOT.
                    snsAction  - An ARN of an SNS topic.
                """;

      if (args.length != 2) {
          System.out.println(usage);
          System.exit(1);
      }

       String thingName;
       String ruleName;
       String roleARN = args[0];
       String snsAction = args[1];
       Scanner scanner = new Scanner(System.in);
       IotClient iotClient = IotClient.builder()
           .region(Region.US_EAST_1)
           .build();

       System.out.println(DASHES);
       System.out.println("Welcome to the AWS IoT example workflow.");
       System.out.println("""
           This example program demonstrates various interactions with the AWS
Internet of Things (IoT) Core service. The program guides you through a series of
steps,
           including creating an IoT Thing, generating a device certificate,
updating the Thing with attributes, and so on.
           It utilizes the AWS SDK for Java V2 and incorporates functionality for
creating and managing IoT Things, certificates, rules,
           shadows, and performing searches. The program aims to showcase AWS IoT
capabilities and provides a comprehensive example for
           developers working with AWS IoT in a Java environment.

           """);
       System.out.print("Press Enter to continue...");
       scanner.nextLine();
       System.out.println(DASHES);

       System.out.println(DASHES);
       System.out.println("1. Create an AWS IoT Thing.");
       System.out.println("""
```

```
            An AWS IoT Thing represents a virtual entity in the AWS IoT service that
can be associated with a physical device.
            """);
        // Prompt the user for input.
        System.out.print("Enter Thing name: ");
        thingName = scanner.nextLine();
        createIoTThing(iotClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Generate a device certificate.");
        System.out.println("""
            A device certificate performs a role in securing the communication
between devices (Things) and the AWS IoT platform.
            """);

        System.out.print("Do you want to create a certificate for " +thingName +"?
(y/n)");
        String certAns = scanner.nextLine();
        String certificateArn="" ;
        if (certAns != null && certAns.trim().equalsIgnoreCase("y")) {
            certificateArn = createCertificate(iotClient);
            System.out.println("Attach the certificate to the AWS IoT Thing.");
            attachCertificateToThing(iotClient, thingName, certificateArn);
        } else {
            System.out.println("A device certificate was not created.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Update an AWS IoT Thing with Attributes.");
        System.out.println("""
             IoT Thing attributes, represented as key-value pairs, offer a pivotal
advantage in facilitating efficient data
             management and retrieval within the AWS IoT ecosystem.
            """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        updateThing(iotClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Return a unique endpoint specific to the Amazon Web
Services account.");
```

```
        System.out.println("""
            An IoT Endpoint refers to a specific URL or Uniform Resource Locator
that serves as the entry point for communication between IoT devices and the AWS
IoT service.
           """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        String endpointUrl = describeEndpoint(iotClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. List your AWS IoT certificates");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        if (certificateArn.length() > 0) {
            listCertificates(iotClient);
        } else {
            System.out.println("You did not create a certificates. Skipping this
step.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Create an IoT shadow that refers to a digital
representation or virtual twin of a physical IoT device");
        System.out.println("""
            A Thing Shadow refers to a feature that enables you to create a virtual
representation, or "shadow,"
            of a physical device or thing. The Thing Shadow allows you to
synchronize and control the state of a device between
            the cloud and the device itself. and the AWS IoT service. For example,
you can write and retrieve JSON data from a Thing Shadow.
           """);
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        IotDataPlaneClient iotPlaneClient = IotDataPlaneClient.builder()
            .region(Region.US_EAST_1)
            .endpointOverride(URI.create(endpointUrl))
            .build();

        updateShadowThing(iotPlaneClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("7. Write out the state information, in JSON format.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        getPayload(iotPlaneClient, thingName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Creates a rule");
        System.out.println("""
        Creates a rule that is an administrator-level action.
        Any user who has permission to create rules will be able to access data
processed by the rule.
        """);
        System.out.print("Enter Rule name: ");
        ruleName = scanner.nextLine();
        createIoTRule(iotClient, roleARN, ruleName, snsAction);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. List your rules.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        listIoTRules(iotClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Search things using the Thing name.");
        System.out.print("Press Enter to continue...");
        scanner.nextLine();
        String queryString = "thingName:"+thingName ;
        searchThings(iotClient, queryString);
        System.out.println(DASHES);

        System.out.println(DASHES);
        if (certificateArn.length() > 0) {
            System.out.print("Do you want to detach and delete the certificate for "
+thingName +"? (y/n)");
            String delAns = scanner.nextLine();
            if (delAns != null && delAns.trim().equalsIgnoreCase("y")) {
                System.out.println("11. You selected to detach amd delete the
certificate.");
                System.out.print("Press Enter to continue...");
                scanner.nextLine();
                detachThingPrincipal(iotClient, thingName, certificateArn);
```

```
                deleteCertificate(iotClient, certificateArn);
            } else {
                System.out.println("11. You selected not to delete the
certificate.");
            }
        } else {
            System.out.println("11. You did not create a certificate so there is
nothing to delete.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Delete the AWS IoT Thing.");
        System.out.print("Do you want to delete the IoT Thing? (y/n)");
        String delAns = scanner.nextLine();
        if (delAns != null && delAns.trim().equalsIgnoreCase("y")) {
            deleteIoTThing(iotClient, thingName);
        } else {
            System.out.println("The IoT Thing was not deleted.");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS IoT workflow has successfully completed.");
        System.out.println(DASHES);
    }

    public static void listCertificates(IotClient iotClient) {
        ListCertificatesResponse response = iotClient.listCertificates();
        List<Certificate> certList = response.certificates();
        for (Certificate cert : certList) {
            System.out.println("Cert id: " + cert.certificateId());
            System.out.println("Cert Arn: " + cert.certificateArn());
        }
    }

    public static void listIoTRules(IotClient iotClient) {
        try {
            ListTopicRulesRequest listTopicRulesRequest =
ListTopicRulesRequest.builder().build();
            ListTopicRulesResponse listTopicRulesResponse =
iotClient.listTopicRules(listTopicRulesRequest);
            System.out.println("List of IoT Rules:");
            List<TopicRuleListItem> ruleList = listTopicRulesResponse.rules();
```

```
            for (TopicRuleListItem rule : ruleList) {
                System.out.println("Rule Name: " + rule.ruleName());
                System.out.println("Rule ARN: " + rule.ruleArn());
                System.out.println("--------------");
            }

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createIoTRule(IotClient iotClient, String roleARN, String
ruleName, String action) {
        try {
            String sql = "SELECT * FROM '" + TOPIC + "'";
            SnsAction action1 = SnsAction.builder()
                .targetArn(action)
                .roleArn(roleARN)
                .build();

            // Create the action.
            Action myAction = Action.builder()
                .sns(action1)
                .build();

            // Create the topic rule payload.
            TopicRulePayload topicRulePayload = TopicRulePayload.builder()
                .sql(sql)
                .actions(myAction)
                .build();

            // Create the topic rule request.
            CreateTopicRuleRequest topicRuleRequest =
CreateTopicRuleRequest.builder()
                .ruleName(ruleName)
                .topicRulePayload(topicRulePayload)
                .build();

            // Create the rule.
            iotClient.createTopicRule(topicRuleRequest);
            System.out.println("IoT Rule created successfully.");

        } catch (IotException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getPayload(IotDataPlaneClient iotPlaneClient, String
thingName) {
        try {
            GetThingShadowRequest getThingShadowRequest =
GetThingShadowRequest.builder()
                .thingName(thingName)
                .build();

            GetThingShadowResponse getThingShadowResponse =
iotPlaneClient.getThingShadow(getThingShadowRequest);

            // Extracting payload from response.
            SdkBytes payload = getThingShadowResponse.payload();
            String payloadString = payload.asUtf8String();
            System.out.println("Received Shadow Data: " + payloadString);

        } catch (IotException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateShadowThing(IotDataPlaneClient iotPlaneClient, String
thingName) {
        try {
            // Create Thing Shadow State Document.
            String stateDocument = "{\"state\":{\"reported\":{\"temperature\":25,
\"humidity\":50}}}";
            SdkBytes data= SdkBytes.fromString(stateDocument,
StandardCharsets.UTF_8 );
            UpdateThingShadowRequest updateThingShadowRequest =
UpdateThingShadowRequest.builder()
                .thingName(thingName)
                .payload(data)
                .build();

            // Update Thing Shadow.
            iotPlaneClient.updateThingShadow(updateThingShadowRequest);
            System.out.println("Thing Shadow updated successfully.");
```

```
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void updateThing(IotClient iotClient, String thingName) {
        // Specify the new attribute values.
        String newLocation = "Office";
        String newFirmwareVersion = "v2.0";

        Map<String, String> attMap = new HashMap<>();
        attMap.put("location", newLocation);
        attMap.put("firmwareVersion", newFirmwareVersion);

        AttributePayload attributePayload = AttributePayload.builder()
            .attributes(attMap)
            .build();

        UpdateThingRequest updateThingRequest = UpdateThingRequest.builder()
            .thingName(thingName)
            .attributePayload(attributePayload)
            .build();

        try {
            // Update the IoT Thing attributes.
            iotClient.updateThing(updateThingRequest);
            System.out.println("Thing attributes updated successfully.");

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static String describeEndpoint(IotClient iotClient) {
        try {
            DescribeEndpointResponse endpointResponse =
iotClient.describeEndpoint(DescribeEndpointRequest.builder().build());

            // Get the endpoint URL.
            String endpointUrl = endpointResponse.endpointAddress();
            String exString = getValue(endpointUrl);
```

```
            String fullEndpoint = "https://"+exString+"-ats.iot.us-
east-1.amazonaws.com";

            System.out.println("Full Endpoint URL: "+fullEndpoint);
            return fullEndpoint;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "" ;
    }

    public static void detachThingPrincipal(IotClient iotClient, String thingName,
 String certificateArn){
        try {
            DetachThingPrincipalRequest thingPrincipalRequest =
 DetachThingPrincipalRequest.builder()
                .principal(certificateArn)
                .thingName(thingName)
                .build();

            iotClient.detachThingPrincipal(thingPrincipalRequest);
            System.out.println(certificateArn +" was successfully removed from "
 +thingName);

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteCertificate(IotClient iotClient, String
 certificateArn ) {
        DeleteCertificateRequest certificateProviderRequest =
 DeleteCertificateRequest.builder()
            .certificateId(extractCertificateId(certificateArn))
            .build();

        iotClient.deleteCertificate(certificateProviderRequest);
        System.out.println(certificateArn +" was successfully deleted.");
    }

    // Get the cert Id  from the Cert ARN value.
```

```
    private static String extractCertificateId(String certificateArn) {
        // Example ARN: arn:aws:iot:region:account-id:cert/certificate-id.
        String[] arnParts = certificateArn.split(":");
        String certificateIdPart = arnParts[arnParts.length - 1];
        return certificateIdPart.substring(certificateIdPart.lastIndexOf("/") + 1);
    }

    public static String createCertificate(IotClient iotClient) {
        try {
            CreateKeysAndCertificateResponse response =
iotClient.createKeysAndCertificate();
            String certificatePem = response.certificatePem();
            String certificateArn = response.certificateArn();

            // Print the details.
            System.out.println("\nCertificate:");
            System.out.println(certificatePem);
            System.out.println("\nCertificate ARN:");
            System.out.println(certificateArn);
            return certificateArn;

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }

    public static void attachCertificateToThing(IotClient iotClient, String
thingName, String certificateArn) {
        // Attach the certificate to the thing.
        AttachThingPrincipalRequest principalRequest =
AttachThingPrincipalRequest.builder()
            .thingName(thingName)
            .principal(certificateArn)
            .build();

        AttachThingPrincipalResponse attachResponse =
iotClient.attachThingPrincipal(principalRequest);

        // Verify the attachment was successful.
        if (attachResponse.sdkHttpResponse().isSuccessful()) {
            System.out.println("Certificate attached to Thing successfully.");
```

```
            // Print additional information about the Thing.
            describeThing(iotClient, thingName);
        } else {
            System.err.println("Failed to attach certificate to Thing. HTTP Status
Code: " +
                attachResponse.sdkHttpResponse().statusCode());
        }
    }

    private static void describeThing(IotClient iotClient, String thingName) {
        try {
            DescribeThingRequest thingRequest = DescribeThingRequest.builder()
                .thingName(thingName)
                .build() ;

            // Print Thing details.
            DescribeThingResponse describeResponse =
iotClient.describeThing(thingRequest);
            System.out.println("Thing Details:");
            System.out.println("Thing Name: " + describeResponse.thingName());
            System.out.println("Thing ARN: " + describeResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteIoTThing(IotClient iotClient, String thingName) {
        try {
            DeleteThingRequest deleteThingRequest = DeleteThingRequest.builder()
                .thingName(thingName)
                .build();

            iotClient.deleteThing(deleteThingRequest);
            System.out.println("Deleted Thing " + thingName);

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
    public static void createIoTThing(IotClient iotClient, String thingName) {
        try {
            CreateThingRequest createThingRequest = CreateThingRequest.builder()
                .thingName(thingName)
                .build();

            CreateThingResponse createThingResponse =
 iotClient.createThing(createThingRequest);
            System.out.println(thingName +" was successfully created. The ARN value
 is " + createThingResponse.thingArn());

        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    private static String getValue(String input) {
        // Define a regular expression pattern for extracting the subdomain.
        Pattern pattern = Pattern.compile("^(.*?)\\.iot\\.us-east-1\\.amazonaws\
\.com");

        // Match the pattern against the input string.
        Matcher matcher = pattern.matcher(input);

        // Check if a match is found.
        if (matcher.find()) {
            // Extract the subdomain from the first capturing group.
            String subdomain = matcher.group(1);
            System.out.println("Extracted subdomain: " + subdomain);
            return subdomain ;
        } else {
            System.out.println("No match found");
        }
        return "" ;
    }

    public static void searchThings(IotClient iotClient, String queryString){
        SearchIndexRequest searchIndexRequest = SearchIndexRequest.builder()
            .queryString(queryString)
            .build();

        try {
            // Perform the search and get the result.
```

```
            SearchIndexResponse searchIndexResponse =
 iotClient.searchIndex(searchIndexRequest);

            // Process the result.
            if (searchIndexResponse.things().isEmpty()) {
                System.out.println("No things found.");
            } else {
                searchIndexResponse.things().forEach(thing ->
 System.out.println("Thing id found using search is " + thing.thingId()));
            }
        } catch (IotException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Exemplos do AWS IoT data usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS IoT data.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Pegue a sombra

O exemplo de código a seguir mostra como obter a sombra de uma AWS IoT coisa.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getPayload(IotDataPlaneClient iotPlaneClient, String
thingName) {
       try {
           GetThingShadowRequest getThingShadowRequest =
GetThingShadowRequest.builder()
               .thingName(thingName)
               .build();

           GetThingShadowResponse getThingShadowResponse =
iotPlaneClient.getThingShadow(getThingShadowRequest);

           // Extracting payload from response.
           SdkBytes payload = getThingShadowResponse.payload();
           String payloadString = payload.asUtf8String();
           System.out.println("Received Shadow Data: " + payloadString);

       } catch (IotException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetThingShadowa Referência AWS SDK for Java 2.x da API.

Atualize a sombra

O exemplo de código a seguir mostra como atualizar a sombra de qualquer AWS IoT coisa.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void updateShadowThing(IotDataPlaneClient iotPlaneClient, String
thingName) {
       try {
           // Create Thing Shadow State Document.
           String stateDocument = "{\"state\":{\"reported\":{\"temperature\":25,
\"humidity\":50}}}";
           SdkBytes data= SdkBytes.fromString(stateDocument,
StandardCharsets.UTF_8 );
           UpdateThingShadowRequest updateThingShadowRequest =
UpdateThingShadowRequest.builder()
               .thingName(thingName)
               .payload(data)
               .build();

           // Update Thing Shadow.
           iotPlaneClient.updateThingShadow(updateThingShadowRequest);
           System.out.println("Thing Shadow updated successfully.");

       } catch (IotException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte UpdateThingShadowa Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Keyspaces usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Keyspaces.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Keyspaces

Os exemplos de código a seguir mostram como começar a usar o Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.keyspaces.KeyspacesClient;
import software.amazon.awssdk.services.keyspaces.model.KeyspaceSummary;
import software.amazon.awssdk.services.keyspaces.model.KeyspacesException;
import software.amazon.awssdk.services.keyspaces.model.ListKeyspacesRequest;
import software.amazon.awssdk.services.keyspaces.model.ListKeyspacesResponse;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloKeyspaces {
```

```
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        KeyspacesClient keyClient = KeyspacesClient.builder()
                .region(region)
                .build();

        listKeyspaces(keyClient);
    }

    public static void listKeyspaces(KeyspacesClient keyClient) {
        try {
            ListKeyspacesRequest keyspacesRequest = ListKeyspacesRequest.builder()
                    .maxResults(10)
                    .build();

            ListKeyspacesResponse response =
 keyClient.listKeyspaces(keyspacesRequest);
            List<KeyspaceSummary> keyspaces = response.keyspaces();
            for (KeyspaceSummary keyspace : keyspaces) {
                System.out.println("The name of the keyspace is " +
 keyspace.keyspaceName());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um espaço de chaves

O exemplo de código a seguir mostra como criar um espaço de chave do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createKeySpace(KeyspacesClient keyClient, String
keyspaceName) {
       try {
           CreateKeyspaceRequest keyspaceRequest = CreateKeyspaceRequest.builder()
                   .keyspaceName(keyspaceName)
                   .build();

           CreateKeyspaceResponse response =
keyClient.createKeyspace(keyspaceRequest);
           System.out.println("The ARN of the KeySpace is " +
response.resourceArn());

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte CreateKeyspacea Referência AWS SDK for Java 2.x da API.

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createTable(KeyspacesClient keyClient, String keySpace,
String tableName) {
       try {
           // Set the columns.
           ColumnDefinition defTitle = ColumnDefinition.builder()
                   .name("title")
                   .type("text")
                   .build();

           ColumnDefinition defYear = ColumnDefinition.builder()
                   .name("year")
                   .type("int")
                   .build();

           ColumnDefinition defReleaseDate = ColumnDefinition.builder()
                   .name("release_date")
                   .type("timestamp")
                   .build();

           ColumnDefinition defPlot = ColumnDefinition.builder()
                   .name("plot")
                   .type("text")
                   .build();

           List<ColumnDefinition> colList = new ArrayList<>();
           colList.add(defTitle);
           colList.add(defYear);
           colList.add(defReleaseDate);
           colList.add(defPlot);

           // Set the keys.
           PartitionKey yearKey = PartitionKey.builder()
                   .name("year")
                   .build();
```

```
            PartitionKey titleKey = PartitionKey.builder()
                    .name("title")
                    .build();

            List<PartitionKey> keyList = new ArrayList<>();
            keyList.add(yearKey);
            keyList.add(titleKey);

            SchemaDefinition schemaDefinition = SchemaDefinition.builder()
                    .partitionKeys(keyList)
                    .allColumns(colList)
                    .build();

            PointInTimeRecovery timeRecovery = PointInTimeRecovery.builder()
                    .status(PointInTimeRecoveryStatus.ENABLED)
                    .build();

            CreateTableRequest tableRequest = CreateTableRequest.builder()
                    .keyspaceName(keySpace)
                    .tableName(tableName)
                    .schemaDefinition(schemaDefinition)
                    .pointInTimeRecovery(timeRecovery)
                    .build();

            CreateTableResponse response = keyClient.createTable(tableRequest);
            System.out.println("The table ARN is " + response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Java 2.x da API.

Excluir um keyspace

O exemplo de código a seguir mostra como excluir um espaço de chaves do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteKeyspace(KeyspacesClient keyClient, String
keyspaceName) {
       try {
           DeleteKeyspaceRequest deleteKeyspaceRequest =
DeleteKeyspaceRequest.builder()
                   .keyspaceName(keyspaceName)
                   .build();

           keyClient.deleteKeyspace(deleteKeyspaceRequest);

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteKeyspacea Referência AWS SDK for Java 2.x da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteTable(KeyspacesClient keyClient, String keyspaceName,
String tableName) {
       try {
           DeleteTableRequest tableRequest = DeleteTableRequest.builder()
                   .keyspaceName(keyspaceName)
                   .tableName(tableName)
                   .build();

           keyClient.deleteTable(tableRequest);

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Java 2.x da API.

Obter dados sobre um keyspace

O exemplo de código a seguir mostra como obter dados sobre um keyspace do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkKeyspaceExistence(KeyspacesClient keyClient, String
keyspaceName) {
       try {
           GetKeyspaceRequest keyspaceRequest = GetKeyspaceRequest.builder()
                   .keyspaceName(keyspaceName)
                   .build();

           GetKeyspaceResponse response = keyClient.getKeyspace(keyspaceRequest);
           String name = response.keyspaceName();
           System.out.println("The " + name + " KeySpace is ready");
```

```
        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetKeyspacea Referência AWS SDK for Java 2.x da API.

Obter dados sobre uma tabela

O exemplo de código a seguir mostra como obter dados sobre uma tabela do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkTable(KeyspacesClient keyClient, String keyspaceName,
String tableName)
            throws InterruptedException {
        try {
            boolean tableStatus = false;
            String status;
            GetTableResponse response = null;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            while (!tableStatus) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println(". The table status is " + status);

                if (status.compareTo("ACTIVE") == 0) {
                    tableStatus = true;
```

```
                }
                Thread.sleep(500);
            }

            List<ColumnDefinition> cols = response.schemaDefinition().allColumns();
            for (ColumnDefinition def : cols) {
                System.out.println("The column name is " + def.name());
                System.out.println("The column type is " + def.type());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetTablea Referência AWS SDK for Java 2.x da API.

Listar espaços de chaves

O exemplo de código a seguir mostra como listar espaços de chaves do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listKeyspacesPaginator(KeyspacesClient keyClient) {
        try {
            ListKeyspacesRequest keyspacesRequest = ListKeyspacesRequest.builder()
                    .maxResults(10)
                    .build();

            ListKeyspacesIterable listRes =
keyClient.listKeyspacesPaginator(keyspacesRequest);
            listRes.stream()
                    .flatMap(r -> r.keyspaces().stream())
```

```
                    .forEach(content -> System.out.println(" Name: " +
content.keyspaceName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListKeyspacesa Referência AWS SDK for Java 2.x da API.

Listar tabelas em um keyspace

O exemplo de código a seguir mostra como listar tabelas do Amazon Keyspaces em um espaço de chave.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listTables(KeyspacesClient keyClient, String keyspaceName) {
        try {
            ListTablesRequest tablesRequest = ListTablesRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            ListTablesIterable listRes =
keyClient.listTablesPaginator(tablesRequest);
            listRes.stream()
                    .flatMap(r -> r.tables().stream())
                    .forEach(content -> System.out.println(" ARN: " +
content.resourceArn() +
                            " Table name: " + content.tableName()));

        } catch (KeyspacesException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Java 2.x da API.

Restaurar uma tabela para um ponto no tempo

O exemplo de código a seguir mostra como restaurar uma tabela do Amazon Keyspaces em um determinado momento.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void restoreTable(KeyspacesClient keyClient, String keyspaceName,
ZonedDateTime utc) {
       try {
           Instant myTime = utc.toInstant();
           RestoreTableRequest restoreTableRequest = RestoreTableRequest.builder()
                   .restoreTimestamp(myTime)
                   .sourceTableName("Movie")
                   .targetKeyspaceName(keyspaceName)
                   .targetTableName("MovieRestore")
                   .sourceKeyspaceName(keyspaceName)
                   .build();

           RestoreTableResponse response =
keyClient.restoreTable(restoreTableRequest);
           System.out.println("The ARN of the restored table is " +
response.restoredTableARN());

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
    }
```

- Para obter detalhes da API, consulte RestoreTablea Referência AWS SDK for Java 2.x da API.

Atualizar uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do Amazon Keyspaces.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void updateTable(KeyspacesClient keyClient, String keySpace,
String tableName) {
       try {
           ColumnDefinition def = ColumnDefinition.builder()
                   .name("watched")
                   .type("boolean")
                   .build();

           UpdateTableRequest tableRequest = UpdateTableRequest.builder()
                   .keyspaceName(keySpace)
                   .tableName(tableName)
                   .addColumns(def)
                   .build();

           keyClient.updateTable(tableRequest);

       } catch (KeyspacesException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte UpdateTablea Referência AWS SDK for Java 2.x da API.

Cenários

Começar a usar espaços de chaves e tabelas

O código de exemplo a seguir mostra como:

- Criar um keyspace e uma tabela. O esquema da tabela contém dados do filme e tem a point-in-time recuperação ativada.
- Conectar-se ao espaço de chaves usando uma conexão TLS segura com autenticação SigV4.
- Consulte a tabela. Adicionar recuperar e atualizar dados do filme.
- Atualizar tabela. Adicionar uma coluna para rastrear os filmes assistidos.
- Restaurar a tabela ao estado anterior e limpar os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * Before running this Java code example, you must create a
 * Java keystore (JKS) file and place it in your project's resources folder.
 *
 * This file is a secure file format used to hold certificate information for
 * Java applications. This is required to make a connection to Amazon Keyspaces.
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/keyspaces/latest/devguide/using_java_driver.html
 *
 * This Java example performs the following tasks:
 *
```

```
 * 1. Create a keyspace.
 * 2. Check for keyspace existence.
 * 3. List keyspaces using a paginator.
 * 4. Create a table with a simple movie data schema and enable point-in-time
 * recovery.
 * 5. Check for the table to be in an Active state.
 * 6. List all tables in the keyspace.
 * 7. Use a Cassandra driver to insert some records into the Movie table.
 * 8. Get all records from the Movie table.
 * 9. Get a specific Movie.
 * 10. Get a UTC timestamp for the current time.
 * 11. Update the table schema to add a ‘watched’ Boolean column.
 * 12. Update an item as watched.
 * 13. Query for items with watched = True.
 * 14. Restore the table back to the previous state using the timestamp.
 * 15. Check for completion of the restore action.
 * 16. Delete the table.
 * 17. Confirm that both tables are deleted.
 * 18. Delete the keyspace.
 */

public class ScenarioKeyspaces {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    /*
     * Usage:
     * fileName - The name of the JSON file that contains movie data. (Get this file
     * from the GitHub repo at resources/sample_file.)
     * keyspaceName - The name of the keyspace to create.
     */
    public static void main(String[] args) throws InterruptedException, IOException
 {
        String fileName = "<Replace with the JSON file that contains movie data>";
        String configFilePath = "C:\\AWS\\application.conf";
        String keyspaceName = "<Replace with the name of the keyspace to create>";
        String titleUpdate = "The Family";
        int yearUpdate = 2013;
        String tableName = "Movie";
        String tableNameRestore = "MovieRestore";
        Region region = Region.US_EAST_1;
        KeyspacesClient keyClient = KeyspacesClient.builder()
                .region(region)
                .build();
```

```
        DriverConfigLoader loader = DriverConfigLoader.fromFile(new
File(configFilePath));
        CqlSession session = CqlSession.builder()
                .withConfigLoader(loader)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Keyspaces example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create a keyspace.");
        createKeySpace(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        Thread.sleep(5000);
        System.out.println("2. Check for keyspace existence.");
        checkKeyspaceExistence(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. List keyspaces using a paginator.");
        listKeyspacesPaginator(keyClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Create a table with a simple movie data schema and
enable point-in-time recovery.");
        createTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Check for the table to be in an Active state.");
        Thread.sleep(6000);
        checkTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. List all tables in the keyspace.");
        listTables(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("7. Use a Cassandra driver to insert some records into
the Movie table.");
        Thread.sleep(6000);
        loadData(session, fileName, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Get all records from the Movie table.");
        getMovieData(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get a specific Movie.");
        getSpecificMovie(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a UTC timestamp for the current time.");
        ZonedDateTime utc = ZonedDateTime.now(ZoneOffset.UTC);
        System.out.println("DATETIME = " + Date.from(utc.toInstant()));
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Update the table schema to add a watched Boolean
column.");
        updateTable(keyClient, keyspaceName, tableName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("12. Update an item as watched.");
        Thread.sleep(10000); // Wait 10 secs for the update.
        updateRecord(session, keyspaceName, titleUpdate, yearUpdate);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Query for items with watched = True.");
        getWatchedData(session, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Restore the table back to the previous state using
the timestamp.");
        System.out.println("Note that the restore operation can take up to 20
minutes.");
```

```
        restoreTable(keyClient, keyspaceName, utc);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("15. Check for completion of the restore action.");
        Thread.sleep(5000);
        checkRestoredTable(keyClient, keyspaceName, "MovieRestore");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("16. Delete both tables.");
        deleteTable(keyClient, keyspaceName, tableName);
        deleteTable(keyClient, keyspaceName, tableNameRestore);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("17. Confirm that both tables are deleted.");
        checkTableDelete(keyClient, keyspaceName, tableName);
        checkTableDelete(keyClient, keyspaceName, tableNameRestore);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("18. Delete the keyspace.");
        deleteKeyspace(keyClient, keyspaceName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The scenario has completed successfully.");
        System.out.println(DASHES);
    }

    public static void deleteKeyspace(KeyspacesClient keyClient, String
keyspaceName) {
        try {
            DeleteKeyspaceRequest deleteKeyspaceRequest =
DeleteKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            keyClient.deleteKeyspace(deleteKeyspaceRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }

    public static void checkTableDelete(KeyspacesClient keyClient, String
keyspaceName, String tableName)
            throws InterruptedException {
        try {
            String status;
            GetTableResponse response;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            // Keep looping until table cannot be found and a
ResourceNotFoundException is
            // thrown.
            while (true) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println(". The table status is " + status);
                Thread.sleep(500);
            }

        } catch (ResourceNotFoundException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        System.out.println("The table is deleted");
    }

    public static void deleteTable(KeyspacesClient keyClient, String keyspaceName,
String tableName) {
        try {
            DeleteTableRequest tableRequest = DeleteTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            keyClient.deleteTable(tableRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

```
    }

    public static void checkRestoredTable(KeyspacesClient keyClient, String
keyspaceName, String tableName)
            throws InterruptedException {
        try {
            boolean tableStatus = false;
            String status;
            GetTableResponse response = null;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            while (!tableStatus) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println("The table status is " + status);

                if (status.compareTo("ACTIVE") == 0) {
                    tableStatus = true;
                }
                Thread.sleep(500);
            }

            List<ColumnDefinition> cols = response.schemaDefinition().allColumns();
            for (ColumnDefinition def : cols) {
                System.out.println("The column name is " + def.name());
                System.out.println("The column type is " + def.type());
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void restoreTable(KeyspacesClient keyClient, String keyspaceName,
ZonedDateTime utc) {
        try {
            Instant myTime = utc.toInstant();
            RestoreTableRequest restoreTableRequest = RestoreTableRequest.builder()
                    .restoreTimestamp(myTime)
                    .sourceTableName("Movie")
```

```
                    .targetKeyspaceName(keyspaceName)
                    .targetTableName("MovieRestore")
                    .sourceKeyspaceName(keyspaceName)
                    .build();

            RestoreTableResponse response =
keyClient.restoreTable(restoreTableRequest);
            System.out.println("The ARN of the restored table is " +
response.restoredTableARN());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getWatchedData(CqlSession session, String keyspaceName) {
        ResultSet resultSet = session
                .execute("SELECT * FROM \"" + keyspaceName + "\".\"Movie\" WHERE
watched = true ALLOW FILTERING;");
        resultSet.forEach(item -> {
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }

    public static void updateRecord(CqlSession session, String keySpace, String
titleUpdate, int yearUpdate) {
        String sqlStatement = "UPDATE \"" + keySpace
                + "\".\"Movie\" SET watched=true WHERE title = :k0 AND year = :k1;";
        BatchStatementBuilder builder =
BatchStatement.builder(DefaultBatchType.UNLOGGED);
        builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM);
        PreparedStatement preparedStatement = session.prepare(sqlStatement);
        builder.addStatement(preparedStatement.boundStatementBuilder()
                .setString("k0", titleUpdate)
                .setInt("k1", yearUpdate)
                .build());

        BatchStatement batchStatement = builder.build();
        session.execute(batchStatement);
    }
```

```
    public static void updateTable(KeyspacesClient keyClient, String keySpace,
String tableName) {
        try {
            ColumnDefinition def = ColumnDefinition.builder()
                    .name("watched")
                    .type("boolean")
                    .build();

            UpdateTableRequest tableRequest = UpdateTableRequest.builder()
                    .keyspaceName(keySpace)
                    .tableName(tableName)
                    .addColumns(def)
                    .build();

            keyClient.updateTable(tableRequest);

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getSpecificMovie(CqlSession session, String keyspaceName) {
        ResultSet resultSet = session.execute(
                "SELECT * FROM \"" + keyspaceName + "\".\"Movie\" WHERE title = 'The
Family' ALLOW FILTERING ;");
        resultSet.forEach(item -> {
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }

    // Get records from the Movie table.
    public static void getMovieData(CqlSession session, String keyspaceName) {
        ResultSet resultSet = session.execute("SELECT * FROM \"" + keyspaceName +
"\".\"Movie\";");
        resultSet.forEach(item -> {
            System.out.println("The Movie title is " + item.getString("title"));
            System.out.println("The Movie year is " + item.getInt("year"));
            System.out.println("The plot is " + item.getString("plot"));
        });
    }
```

```
    // Load data into the table.
    public static void loadData(CqlSession session, String fileName, String
keySpace) throws IOException {
        String sqlStatement = "INSERT INTO \"" + keySpace + "\".\"Movie\" (title,
year, plot) values (:k0, :k1, :k2)";
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0;
        while (iter.hasNext()) {

            // Add 20 movies to the table.
            if (t == 20)
                break;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String plot = currentNode.path("info").path("plot").toString();

            // Insert the data into the Amazon Keyspaces table.
            BatchStatementBuilder builder =
BatchStatement.builder(DefaultBatchType.UNLOGGED);
            builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM);
            PreparedStatement preparedStatement = session.prepare(sqlStatement);
            builder.addStatement(preparedStatement.boundStatementBuilder()
                    .setString("k0", title)
                    .setInt("k1", year)
                    .setString("k2", plot)
                    .build());

            BatchStatement batchStatement = builder.build();
            session.execute(batchStatement);
            t++;
        }

        System.out.println("You have added " + t + " records successfully!");
    }

    public static void listTables(KeyspacesClient keyClient, String keyspaceName) {
        try {
            ListTablesRequest tablesRequest = ListTablesRequest.builder()
```

```
                    .keyspaceName(keyspaceName)
                    .build();

            ListTablesIterable listRes =
keyClient.listTablesPaginator(tablesRequest);
            listRes.stream()
                    .flatMap(r -> r.tables().stream())
                    .forEach(content -> System.out.println(" ARN: " +
content.resourceArn() +
                            " Table name: " + content.tableName()));

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkTable(KeyspacesClient keyClient, String keyspaceName,
String tableName)
            throws InterruptedException {
        try {
            boolean tableStatus = false;
            String status;
            GetTableResponse response = null;
            GetTableRequest tableRequest = GetTableRequest.builder()
                    .keyspaceName(keyspaceName)
                    .tableName(tableName)
                    .build();

            while (!tableStatus) {
                response = keyClient.getTable(tableRequest);
                status = response.statusAsString();
                System.out.println(". The table status is " + status);

                if (status.compareTo("ACTIVE") == 0) {
                    tableStatus = true;
                }
                Thread.sleep(500);
            }

            List<ColumnDefinition> cols = response.schemaDefinition().allColumns();
            for (ColumnDefinition def : cols) {
                System.out.println("The column name is " + def.name());
                System.out.println("The column type is " + def.type());
```

```
            }

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createTable(KeyspacesClient keyClient, String keySpace,
 String tableName) {
        try {
            // Set the columns.
            ColumnDefinition defTitle = ColumnDefinition.builder()
                    .name("title")
                    .type("text")
                    .build();

            ColumnDefinition defYear = ColumnDefinition.builder()
                    .name("year")
                    .type("int")
                    .build();

            ColumnDefinition defReleaseDate = ColumnDefinition.builder()
                    .name("release_date")
                    .type("timestamp")
                    .build();

            ColumnDefinition defPlot = ColumnDefinition.builder()
                    .name("plot")
                    .type("text")
                    .build();

            List<ColumnDefinition> colList = new ArrayList<>();
            colList.add(defTitle);
            colList.add(defYear);
            colList.add(defReleaseDate);
            colList.add(defPlot);

            // Set the keys.
            PartitionKey yearKey = PartitionKey.builder()
                    .name("year")
                    .build();

            PartitionKey titleKey = PartitionKey.builder()
```

```
                .name("title")
                .build();

        List<PartitionKey> keyList = new ArrayList<>();
        keyList.add(yearKey);
        keyList.add(titleKey);

        SchemaDefinition schemaDefinition = SchemaDefinition.builder()
                .partitionKeys(keyList)
                .allColumns(colList)
                .build();

        PointInTimeRecovery timeRecovery = PointInTimeRecovery.builder()
                .status(PointInTimeRecoveryStatus.ENABLED)
                .build();

        CreateTableRequest tableRequest = CreateTableRequest.builder()
                .keyspaceName(keySpace)
                .tableName(tableName)
                .schemaDefinition(schemaDefinition)
                .pointInTimeRecovery(timeRecovery)
                .build();

        CreateTableResponse response = keyClient.createTable(tableRequest);
        System.out.println("The table ARN is " + response.resourceArn());

    } catch (KeyspacesException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}

public static void listKeyspacesPaginator(KeyspacesClient keyClient) {
    try {
        ListKeyspacesRequest keyspacesRequest = ListKeyspacesRequest.builder()
                .maxResults(10)
                .build();

        ListKeyspacesIterable listRes =
keyClient.listKeyspacesPaginator(keyspacesRequest);
        listRes.stream()
                .flatMap(r -> r.keyspaces().stream())
                .forEach(content -> System.out.println(" Name: " +
content.keyspaceName()));
```

```
        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void checkKeyspaceExistence(KeyspacesClient keyClient, String
 keyspaceName) {
        try {
            GetKeyspaceRequest keyspaceRequest = GetKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            GetKeyspaceResponse response = keyClient.getKeyspace(keyspaceRequest);
            String name = response.keyspaceName();
            System.out.println("The " + name + " KeySpace is ready");

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void createKeySpace(KeyspacesClient keyClient, String
 keyspaceName) {
        try {
            CreateKeyspaceRequest keyspaceRequest = CreateKeyspaceRequest.builder()
                    .keyspaceName(keyspaceName)
                    .build();

            CreateKeyspaceResponse response =
 keyClient.createKeyspace(keyspaceRequest);
            System.out.println("The ARN of the KeySpace is " +
 response.resourceArn());

        } catch (KeyspacesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable
  - UpdateTable

Exemplos do Kinesis usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Criar um stream

O exemplo de código a seguir mostra como criar um stream do Kinesis.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.CreateStreamRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateDataStream {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream (for example,
 StockTradeStream).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();
        createStream(kinesisClient, streamName);
        System.out.println("Done");
        kinesisClient.close();
    }

    public static void createStream(KinesisClient kinesisClient, String streamName)
 {
        try {
            CreateStreamRequest streamReq = CreateStreamRequest.builder()
                    .streamName(streamName)
                    .shardCount(1)
                    .build();

            kinesisClient.createStream(streamReq);

        } catch (KinesisException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateStreama Referência AWS SDK for Java 2.x da API.

Excluir um stream

O exemplo de código a seguir mostra como excluir um stream do Kinesis.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.DeleteStreamRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteDataStream {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream (for example,
 StockTradeStream)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        deleteStream(kinesisClient, streamName);
        kinesisClient.close();
        System.out.println("Done");
    }
```

```
    public static void deleteStream(KinesisClient kinesisClient, String streamName)
 {
        try {
            DeleteStreamRequest delStream = DeleteStreamRequest.builder()
                    .streamName(streamName)
                    .build();

            kinesisClient.deleteStream(delStream);

        } catch (KinesisException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteStreama Referência AWS SDK for Java 2.x da API.

Obter dados em lotes de um stream

O exemplo de código a seguir mostra como obter dados em lotes de um stream do Kinesis.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamResponse;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamRequest;
import software.amazon.awssdk.services.kinesis.model.Shard;
import software.amazon.awssdk.services.kinesis.model.GetShardIteratorRequest;
import software.amazon.awssdk.services.kinesis.model.GetShardIteratorResponse;
import software.amazon.awssdk.services.kinesis.model.Record;
import software.amazon.awssdk.services.kinesis.model.GetRecordsRequest;
import software.amazon.awssdk.services.kinesis.model.GetRecordsResponse;
```

```
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetRecords {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream to read from (for
 example, StockTradeStream).
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        getStockTrades(kinesisClient, streamName);
        kinesisClient.close();
    }

    public static void getStockTrades(KinesisClient kinesisClient, String
 streamName) {
        String shardIterator;
        String lastShardId = null;
        DescribeStreamRequest describeStreamRequest =
 DescribeStreamRequest.builder()
```

```
                .streamName(streamName)
                .build();

        List<Shard> shards = new ArrayList<>();
        DescribeStreamResponse streamRes;
        do {
            streamRes = kinesisClient.describeStream(describeStreamRequest);
            shards.addAll(streamRes.streamDescription().shards());

            if (shards.size() > 0) {
                lastShardId = shards.get(shards.size() - 1).shardId();
            }
        } while (streamRes.streamDescription().hasMoreShards());

        GetShardIteratorRequest itReq = GetShardIteratorRequest.builder()
                .streamName(streamName)
                .shardIteratorType("TRIM_HORIZON")
                .shardId(lastShardId)
                .build();

        GetShardIteratorResponse shardIteratorResult =
kinesisClient.getShardIterator(itReq);
        shardIterator = shardIteratorResult.shardIterator();

        // Continuously read data records from shard.
        List<Record> records;

        // Create new GetRecordsRequest with existing shardIterator.
        // Set maximum records to return to 1000.
        GetRecordsRequest recordsRequest = GetRecordsRequest.builder()
                .shardIterator(shardIterator)
                .limit(1000)
                .build();

        GetRecordsResponse result = kinesisClient.getRecords(recordsRequest);

        // Put result into record list. Result may be empty.
        records = result.records();

        // Print records
        for (Record record : records) {
            SdkBytes byteBuffer = record.data();
            System.out.printf("Seq No: %s - %s%n", record.sequenceNumber(), new
String(byteBuffer.asByteArray()));
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetRecords
  - GetShardIterator

Inserir dados em um stream

O exemplo de código a seguir mostra como inserir dados em um stream do Kinesis.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kinesis.KinesisClient;
import software.amazon.awssdk.services.kinesis.model.PutRecordRequest;
import software.amazon.awssdk.services.kinesis.model.KinesisException;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamRequest;
import software.amazon.awssdk.services.kinesis.model.DescribeStreamResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class StockTradesWriter {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <streamName>

                Where:
                    streamName - The Amazon Kinesis data stream to which records are
written (for example, StockTradeStream)
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String streamName = args[0];
        Region region = Region.US_EAST_1;
        KinesisClient kinesisClient = KinesisClient.builder()
                .region(region)
                .build();

        // Ensure that the Kinesis Stream is valid.
        validateStream(kinesisClient, streamName);
        setStockData(kinesisClient, streamName);
        kinesisClient.close();
    }

    public static void setStockData(KinesisClient kinesisClient, String streamName)
{
        try {
            // Repeatedly send stock trades with a 100 milliseconds wait in between.
            StockTradeGenerator stockTradeGenerator = new StockTradeGenerator();

            // Put in 50 Records for this example.
            int index = 50;
            for (int x = 0; x < index; x++) {
                StockTrade trade = stockTradeGenerator.getRandomTrade();
                sendStockTrade(trade, kinesisClient, streamName);
                Thread.sleep(100);
            }

        } catch (KinesisException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
        System.out.println("Done");
    }

    private static void sendStockTrade(StockTrade trade, KinesisClient
kinesisClient,
            String streamName) {
        byte[] bytes = trade.toJsonAsBytes();

        // The bytes could be null if there is an issue with the JSON serialization
by
        // the Jackson JSON library.
        if (bytes == null) {
            System.out.println("Could not get JSON bytes for stock trade");
            return;
        }

        System.out.println("Putting trade: " + trade);
        PutRecordRequest request = PutRecordRequest.builder()
                .partitionKey(trade.getTickerSymbol()) // We use the ticker symbol
as the partition key, explained in
                                                       // the Supplemental
Information section below.
                .streamName(streamName)
                .data(SdkBytes.fromByteArray(bytes))
                .build();

        try {
            kinesisClient.putRecord(request);
        } catch (KinesisException e) {
            System.err.println(e.getMessage());
        }
    }

    private static void validateStream(KinesisClient kinesisClient, String
streamName) {
        try {
            DescribeStreamRequest describeStreamRequest =
DescribeStreamRequest.builder()
                    .streamName(streamName)
                    .build();

            DescribeStreamResponse describeStreamResponse =
kinesisClient.describeStream(describeStreamRequest);
```

```
            if (!
describeStreamResponse.streamDescription().streamStatus().toString().equals("ACTIVE"))
 {
                System.err.println("Stream " + streamName + " is not active. Please
 wait a few moments and try again.");
                System.exit(1);
            }

        } catch (KinesisException e) {
            System.err.println("Error found while describing the stream " +
 streamName);
            System.err.println(e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutRecorda Referência AWS SDK for Java 2.x da API.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
```

```
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;

public class Handler implements RequestHandler<KinesisEvent, Void> {
    @Override
    public Void handleRequest(final KinesisEvent event, final Context context) {
        LambdaLogger logger = context.getLogger();
        if (event.getRecords().isEmpty()) {
            logger.log("Empty Kinesis Event received");
            return null;
        }
        for (KinesisEvent.KinesisEventRecord record : event.getRecords()) {
            try {
                logger.log("Processed Event with EventId: "+record.getEventID());
                String data = new String(record.getKinesis().getData().array());
                logger.log("Data:"+ data);
                // TODO: Do interesting work based on the new data
            }
            catch (Exception ex) {
                logger.log("An error occurred:"+ex.getMessage());
                throw ex;
            }
        }
        logger.log("Successfully processed:"+event.getRecords().size()+" records");
        return null;
    }

}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;
import com.amazonaws.services.lambda.runtime.events.StreamsEventResponse;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.List;

public class ProcessKinesisRecords implements RequestHandler<KinesisEvent,
 StreamsEventResponse> {

    @Override
    public StreamsEventResponse handleRequest(KinesisEvent input, Context context) {

        List<StreamsEventResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<>();
        String curRecordSequenceNumber = "";

        for (KinesisEvent.KinesisEventRecord kinesisEventRecord :
 input.getRecords()) {
            try {
                //Process your record
                KinesisEvent.Record kinesisRecord = kinesisEventRecord.getKinesis();
                curRecordSequenceNumber = kinesisRecord.getSequenceNumber();

            } catch (Exception e) {
                /* Since we are working with streams, we can return the failed item
 immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                batchItemFailures.add(new
 StreamsEventResponse.BatchItemFailure(curRecordSequenceNumber));
```

```
                return new StreamsEventResponse(batchItemFailures);
            }
        }

        return new StreamsEventResponse(batchItemFailures);
    }
}
```

Exemplos do AWS KMS usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma concessão para uma chave

O exemplo de código a seguir mostra como criar uma concessão para uma chave KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateGrantRequest;
import software.amazon.awssdk.services.kms.model.CreateGrantResponse;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateGrant {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId> <granteePrincipal> <operation>\s

                Where:
                    keyId - The unique identifier for the customer master key (CMK)
 that the grant applies to.\s
                    granteePrincipal - The principal that is given permission to
 perform the operations that the grant permits.\s
                    operation - An operation (for example, Encrypt).\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        String granteePrincipal = args[1];
        String operation = args[2];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        String grantId = createGrant(kmsClient, keyId, granteePrincipal, operation);
```

```
        System.out.printf("Successfully created a grant with ID %s%n", grantId);
        kmsClient.close();
    }

    public static String createGrant(KmsClient kmsClient, String keyId, String
 granteePrincipal, String operation) {
        try {
            CreateGrantRequest grantRequest = CreateGrantRequest.builder()
                    .keyId(keyId)
                    .granteePrincipal(granteePrincipal)
                    .operationsWithStrings(operation)
                    .build();

            CreateGrantResponse response = kmsClient.createGrant(grantRequest);
            return response.grantId();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateGrant a Referência AWS SDK for Java 2.x da API.

Criar uma chave

O exemplo de código a seguir mostra como criar uma AWS KMS key.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateKeyRequest;
```

```
import software.amazon.awssdk.services.kms.model.CustomerMasterKeySpec;
import software.amazon.awssdk.services.kms.model.CreateKeyResponse;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateCustomerKey {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        String keyDesc = "Created by the AWS KMS API";
        System.out.println("The key id is " + createKey(kmsClient, keyDesc));
        kmsClient.close();
    }

    public static String createKey(KmsClient kmsClient, String keyDesc) {
        try {
            CreateKeyRequest keyRequest = CreateKeyRequest.builder()
                    .description(keyDesc)
                    .customerMasterKeySpec(CustomerMasterKeySpec.SYMMETRIC_DEFAULT)
                    .keyUsage("ENCRYPT_DECRYPT")
                    .build();

            CreateKeyResponse result = kmsClient.createKey(keyRequest);
            System.out.printf("Created a customer key with id \"%s\"%n",
 result.keyMetadata().arn());
            return result.keyMetadata().keyId();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for Java 2.x da API.

Criar um alias para uma chave

O exemplo de código a seguir mostra como criar um alias para uma chave do KMS Key.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.CreateAliasRequest;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateAlias {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <targetKeyId> <aliasName>\s

                Where:
                    targetKeyId - The key ID or the Amazon Resource Name (ARN) of
 the customer master key (CMK).\s
                    aliasName - An alias name (for example, alias/myAlias).\s
```

```
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String targetKeyId = args[0];
        String aliasName = args[1];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        createCustomAlias(kmsClient, targetKeyId, aliasName);
        kmsClient.close();
    }

    public static void createCustomAlias(KmsClient kmsClient, String targetKeyId,
 String aliasName) {
        try {
            CreateAliasRequest aliasRequest = CreateAliasRequest.builder()
                    .aliasName(aliasName)
                    .targetKeyId(targetKeyId)
                    .build();

            kmsClient.createAlias(aliasRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateAliasa Referência AWS SDK for Java 2.x da API.

Descriptografar texto cifrado

O exemplo de código a seguir mostra como descriptografar texto cifrado que foi criptografado com uma chave KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void decryptData(KmsClient kmsClient, SdkBytes encryptedData,
String keyId) {
       try {
           DecryptRequest decryptRequest = DecryptRequest.builder()
                   .ciphertextBlob(encryptedData)
                   .keyId(keyId)
                   .build();

           DecryptResponse decryptResponse = kmsClient.decrypt(decryptRequest);
           decryptResponse.plaintext();

       } catch (KmsException e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte Decrypt na Referência de API do AWS SDK for Java 2.x.

Descrever uma chave

O exemplo de código a seguir mostra como descrever uma chave do KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.DescribeKeyRequest;
import software.amazon.awssdk.services.kms.model.DescribeKeyResponse;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId -  A key id value to describe (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        describeSpecifcKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void describeSpecifcKey(KmsClient kmsClient, String keyId) {
        try {
```

```
            DescribeKeyRequest keyRequest = DescribeKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            DescribeKeyResponse response = kmsClient.describeKey(keyRequest);
            System.out.println("The key description is " +
 response.keyMetadata().description());
            System.out.println("The key ARN is " + response.keyMetadata().arn());

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeKeya Referência AWS SDK for Java 2.x da API.

Desabilitar uma chave

O exemplo de código a seguir mostra como desativar uma chave KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.DisableKeyRequest;
import software.amazon.awssdk.services.kms.model.KmsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DisableCustomerKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to disable (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        disableKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void disableKey(KmsClient kmsClient, String keyId) {
        try {
            DisableKeyRequest keyRequest = DisableKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            kmsClient.disableKey(keyRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DisableKeya Referência AWS SDK for Java 2.x da API.

Habilitar uma chave

O exemplo de código a seguir mostra como habilitar uma chave do KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.EnableKeyRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class EnableCustomerKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to enable (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        enableKey(kmsClient, keyId);
        kmsClient.close();
    }

    public static void enableKey(KmsClient kmsClient, String keyId) {
        try {
            EnableKeyRequest enableKeyRequest = EnableKeyRequest.builder()
                    .keyId(keyId)
                    .build();

            kmsClient.enableKey(enableKeyRequest);

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte EnableKeya Referência AWS SDK for Java 2.x da API.

Criptografar texto usando uma chave

O exemplo de código a seguir mostra como criptografar texto usando uma chave KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.EncryptRequest;
import software.amazon.awssdk.services.kms.model.EncryptResponse;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.DecryptRequest;
import software.amazon.awssdk.services.kms.model.DecryptResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class EncryptDataKey {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - A key id value to use to encrypt/decrypt the data (for
 example, xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        SdkBytes encryData = encryptData(kmsClient, keyId);
        decryptData(kmsClient, encryData, keyId);
```

```
        System.out.println("Done");
        kmsClient.close();
    }

    public static SdkBytes encryptData(KmsClient kmsClient, String keyId) {
        try {
            SdkBytes myBytes = SdkBytes.fromByteArray(new byte[] { 1, 2, 3, 4, 5, 6,
7, 8, 9, 0 });
            EncryptRequest encryptRequest = EncryptRequest.builder()
                    .keyId(keyId)
                    .plaintext(myBytes)
                    .build();

            EncryptResponse response = kmsClient.encrypt(encryptRequest);
            String algorithm = response.encryptionAlgorithm().toString();
            System.out.println("The encryption algorithm is " + algorithm);

            // Get the encrypted data.
            SdkBytes encryptedData = response.ciphertextBlob();
            return encryptedData;

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return null;
    }

    public static void decryptData(KmsClient kmsClient, SdkBytes encryptedData,
String keyId) {
        try {
            DecryptRequest decryptRequest = DecryptRequest.builder()
                    .ciphertextBlob(encryptedData)
                    .keyId(keyId)
                    .build();

            DecryptResponse decryptResponse = kmsClient.decrypt(decryptRequest);
            decryptResponse.plaintext();

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte Encrypt na Referência de API do AWS SDK for Java 2.x.

Listar apelidos para uma chave

O exemplo de código a seguir mostra como listar aliases para uma chave do KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.AliasListEntry;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.ListAliasesRequest;
import software.amazon.awssdk.services.kms.model.ListAliasesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListAliases {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        listAllAliases(kmsClient);
        kmsClient.close();
```

```
    }

    public static void listAllAliases(KmsClient kmsClient) {
        try {
            ListAliasesRequest aliasesRequest = ListAliasesRequest.builder()
                    .limit(15)
                    .build();

            ListAliasesResponse aliasesResponse =
 kmsClient.listAliases(aliasesRequest);
            List<AliasListEntry> aliases = aliasesResponse.aliases();
            for (AliasListEntry alias : aliases) {
                System.out.println("The alias name is: " + alias.aliasName());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListAliasesa Referência AWS SDK for Java 2.x da API.

Listar concessões para uma chave

O exemplo de código a seguir mostra como listar concessões para uma chave do KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.GrantListEntry;
import software.amazon.awssdk.services.kms.model.KmsException;
import software.amazon.awssdk.services.kms.model.ListGrantsRequest;
```

```
import software.amazon.awssdk.services.kms.model.ListGrantsResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListGrants {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <keyId>\s

                Where:
                    keyId - a key id value to use (for example,
 xxxxxbcd-12ab-34cd-56ef-1234567890ab).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String keyId = args[0];
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        displayGrantIds(kmsClient, keyId);
        kmsClient.close();
    }

    public static void displayGrantIds(KmsClient kmsClient, String keyId) {
        try {
            ListGrantsRequest grantsRequest = ListGrantsRequest.builder()
                    .keyId(keyId)
                    .limit(15)
                    .build();
```

```
            ListGrantsResponse response = kmsClient.listGrants(grantsRequest);
            List<GrantListEntry> grants = response.grants();
            for (GrantListEntry grant : grants) {
                System.out.println("The grant Id is : " + grant.grantId());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListGrantsa Referência AWS SDK for Java 2.x da API.

Listar chaves

O exemplo de código a seguir mostra como listar chaves do KMS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.kms.KmsClient;
import software.amazon.awssdk.services.kms.model.KeyListEntry;
import software.amazon.awssdk.services.kms.model.ListKeysRequest;
import software.amazon.awssdk.services.kms.model.ListKeysResponse;
import software.amazon.awssdk.services.kms.model.KmsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListKeys {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        KmsClient kmsClient = KmsClient.builder()
                .region(region)
                .build();

        listAllKeys(kmsClient);
        kmsClient.close();
    }

    public static void listAllKeys(KmsClient kmsClient) {
        try {
            ListKeysRequest listKeysRequest = ListKeysRequest.builder()
                    .limit(15)
                    .build();

            ListKeysResponse keysResponse = kmsClient.listKeys(listKeysRequest);
            List<KeyListEntry> keyListEntries = keysResponse.keys();
            for (KeyListEntry key : keyListEntries) {
                System.out.println("The key ARN is: " + key.keyArn());
                System.out.println("The key Id is: " + key.keyId());
            }

        } catch (KmsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListKeysa Referência AWS SDK for Java 2.x da API.

Exemplos do Lambda usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Lambda

Os exemplos de código a seguir mostram como começar a usar o Lambda.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.lambda;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.services.lambda.model.LambdaException;
import software.amazon.awssdk.services.lambda.model.ListFunctionsResponse;
import software.amazon.awssdk.services.lambda.model.FunctionConfiguration;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class ListLambdaFunctions {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        listFunctions(awsLambda);
        awsLambda.close();
    }

    public static void listFunctions(LambdaClient awsLambda) {
        try {
            ListFunctionsResponse functionResult = awsLambda.listFunctions();
            List<FunctionConfiguration> list = functionResult.functions();
            for (FunctionConfiguration config : list) {
                System.out.println("The function name is " + config.functionName());
            }

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.services.lambda.model.CreateFunctionRequest;
import software.amazon.awssdk.services.lambda.model.FunctionCode;
import software.amazon.awssdk.services.lambda.model.CreateFunctionResponse;
import software.amazon.awssdk.services.lambda.model.GetFunctionRequest;
import software.amazon.awssdk.services.lambda.model.GetFunctionResponse;
import software.amazon.awssdk.services.lambda.model.LambdaException;
import software.amazon.awssdk.services.lambda.model.Runtime;
import software.amazon.awssdk.services.lambda.waiters.LambdaWaiter;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;

/**
 * This code example requires a ZIP or JAR that represents the code of the
 * Lambda function.
 * If you do not have a ZIP or JAR, please refer to the following document:
 *
 * https://github.com/aws-doc-sdk-examples/tree/master/javav2/usecases/
creating_workflows_stepfunctions
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class CreateFunction {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <functionName> <filePath> <role> <handler>\s

                Where:
                    functionName - The name of the Lambda function.\s
                    filePath - The path to the ZIP or JAR where the code is located.
\s
                    role - The role ARN that has Lambda permissions.\s
                    handler - The fully qualified method name (for example,
 example.Handler::handleRequest). \s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        String filePath = args[1];
        String role = args[2];
        String handler = args[3];
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        createLambdaFunction(awsLambda, functionName, filePath, role, handler);
        awsLambda.close();
    }

    public static void createLambdaFunction(LambdaClient awsLambda,
            String functionName,
            String filePath,
            String role,
            String handler) {

        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);

            FunctionCode code = FunctionCode.builder()
```

```
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest = CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("Created by the Lambda Java API")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA8)
                    .role(role)
                    .build();

            // Create a Lambda function using a waiter.
            CreateFunctionResponse functionResponse =
 awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
 waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("The function ARN is " +
 functionResponse.functionArn());

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Java 2.x da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.lambda.model.DeleteFunctionRequest;
import software.amazon.awssdk.services.lambda.model.LambdaException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteFunction {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName>\s

                Where:
                    functionName - The name of the Lambda function.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        Region region = Region.US_EAST_1;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();
```

```
        deleteLambdaFunction(awsLambda, functionName);
        awsLambda.close();
    }

    public static void deleteLambdaFunction(LambdaClient awsLambda, String
 functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            awsLambda.deleteFunction(request);
            System.out.println("The " + functionName + " function was deleted");

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Java 2.x da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import org.json.JSONObject;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.lambda.LambdaClient;
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.lambda.model.InvokeRequest;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.services.lambda.model.InvokeResponse;
import software.amazon.awssdk.services.lambda.model.LambdaException;

public class LambdaInvoke {

    /*
     * Function names appear as
     * arn:aws:lambda:us-west-2:335556666777:function:HelloFunction
     * you can retrieve the value by looking at the function in the AWS Console
     *
     * Also, set up your development environment, including your credentials.
     *
     * For information, see this documentation topic:
     *
     * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.
     * html
     */

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <functionName>\s

                Where:
                    functionName - The name of the Lambda function\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        invokeFunction(awsLambda, functionName);
        awsLambda.close();
    }
```

```
    public static void invokeFunction(LambdaClient awsLambda, String functionName) {

        InvokeResponse res = null;
        try {
            // Need a SdkBytes instance for the payload.
            JSONObject jsonObj = new JSONObject();
            jsonObj.put("inputValue", "2000");
            String json = jsonObj.toString();
            SdkBytes payload = SdkBytes.fromUtf8String(json);

            // Setup an InvokeRequest.
            InvokeRequest request = InvokeRequest.builder()
                    .functionName(functionName)
                    .payload(payload)
                    .build();

            res = awsLambda.invoke(request);
            String value = res.payload().asUtf8String();
            System.out.println(value);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Java 2.x.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.

- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/*
 *  Lambda function names appear as:
 *
 *  arn:aws:lambda:us-west-2:335556666777:function:HelloFunction
 *
 *  To find this value, look at the function in the AWS Management Console.
 *
 *  Before running this Java code example, set up your development environment,
 including your credentials.
 *
 *  For more information, see this documentation topic:
 *
 *  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 *  This example performs the following tasks:
 *
 * 1. Creates an AWS Lambda function.
 * 2. Gets a specific AWS Lambda function.
 * 3. Lists all Lambda functions.
 * 4. Invokes a Lambda function.
 * 5. Updates the Lambda function code and invokes it again.
 * 6. Updates a Lambda function's configuration value.
 * 7. Deletes a Lambda function.
 */

public class LambdaScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """
```

```
                Usage:
                    <functionName> <filePath> <role> <handler> <bucketName> <key>\s

                Where:
                    functionName - The name of the Lambda function.\s
                    filePath - The path to the .zip or .jar where the code is
located.\s
                    role - The AWS Identity and Access Management (IAM) service role
that has Lambda permissions.\s
                    handler - The fully qualified method name (for example,
example.Handler::handleRequest).\s
                    bucketName - The Amazon Simple Storage Service (Amazon S3)
bucket name that contains the .zip or .jar used to update the Lambda function's
code.\s
                    key - The Amazon S3 key name that represents the .zip or .jar
(for example, LambdaHello-1.0-SNAPSHOT.jar).
                    """;

        if (args.length != 6) {
            System.out.println(usage);
            System.exit(1);
        }

        String functionName = args[0];
        String filePath = args[1];
        String role = args[2];
        String handler = args[3];
        String bucketName = args[4];
        String key = args[5];

        Region region = Region.US_WEST_2;
        LambdaClient awsLambda = LambdaClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Lambda example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an AWS Lambda function.");
        String funArn = createLambdaFunction(awsLambda, functionName, filePath,
role, handler);
```

```
        System.out.println("The AWS Lambda ARN is " + funArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Get the " + functionName + " AWS Lambda function.");
        getFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. List all AWS Lambda functions.");
        listFunctions(awsLambda);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Invoke the Lambda function.");
        System.out.println("*** Sleep for 1 min to get Lambda function ready.");
        Thread.sleep(60000);
        invokeFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Update the Lambda function code and invoke it
again.");
        updateFunctionCode(awsLambda, functionName, bucketName, key);
        System.out.println("*** Sleep for 1 min to get Lambda function ready.");
        Thread.sleep(60000);
        invokeFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Update a Lambda function's configuration value.");
        updateFunctionConfiguration(awsLambda, functionName, handler);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the AWS Lambda function.");
        LambdaScenario.deleteLambdaFunction(awsLambda, functionName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS Lambda scenario completed successfully");
        System.out.println(DASHES);
        awsLambda.close();
    }
```

```
    public static String createLambdaFunction(LambdaClient awsLambda,
            String functionName,
            String filePath,
            String role,
            String handler) {

        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);

            FunctionCode code = FunctionCode.builder()
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest = CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("Created by the Lambda Java API")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA8)
                    .role(role)
                    .build();

            // Create a Lambda function using a waiter
            CreateFunctionResponse functionResponse =
awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            return functionResponse.functionArn();

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void getFunction(LambdaClient awsLambda, String functionName) {
```

```
        try {
            GetFunctionRequest functionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            GetFunctionResponse response = awsLambda.getFunction(functionRequest);
            System.out.println("The runtime of this Lambda function is " +
response.configuration().runtime());

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listFunctions(LambdaClient awsLambda) {
        try {
            ListFunctionsResponse functionResult = awsLambda.listFunctions();
            List<FunctionConfiguration> list = functionResult.functions();
            for (FunctionConfiguration config : list) {
                System.out.println("The function name is " + config.functionName());
            }

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void invokeFunction(LambdaClient awsLambda, String functionName) {

        InvokeResponse res;
        try {
            // Need a SdkBytes instance for the payload.
            JSONObject jsonObj = new JSONObject();
            jsonObj.put("inputValue", "2000");
            String json = jsonObj.toString();
            SdkBytes payload = SdkBytes.fromUtf8String(json);

            InvokeRequest request = InvokeRequest.builder()
                    .functionName(functionName)
                    .payload(payload)
                    .build();
```

```
            res = awsLambda.invoke(request);
            String value = res.payload().asUtf8String();
            System.out.println(value);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateFunctionCode(LambdaClient awsLambda, String
functionName, String bucketName, String key) {
        try {
            LambdaWaiter waiter = awsLambda.waiter();
            UpdateFunctionCodeRequest functionCodeRequest =
UpdateFunctionCodeRequest.builder()
                    .functionName(functionName)
                    .publish(true)
                    .s3Bucket(bucketName)
                    .s3Key(key)
                    .build();

            UpdateFunctionCodeResponse response =
awsLambda.updateFunctionCode(functionCodeRequest);
            GetFunctionConfigurationRequest getFunctionConfigRequest =
GetFunctionConfigurationRequest.builder()
                    .functionName(functionName)
                    .build();

            WaiterResponse<GetFunctionConfigurationResponse> waiterResponse = waiter
                    .waitUntilFunctionUpdated(getFunctionConfigRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("The last modified value is " +
response.lastModified());

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateFunctionConfiguration(LambdaClient awsLambda, String
functionName, String handler) {
        try {
```

```
            UpdateFunctionConfigurationRequest configurationRequest =
 UpdateFunctionConfigurationRequest.builder()
                    .functionName(functionName)
                    .handler(handler)
                    .runtime(Runtime.JAVA11)
                    .build();

            awsLambda.updateFunctionConfiguration(configurationRequest);

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void deleteLambdaFunction(LambdaClient awsLambda, String
 functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            awsLambda.deleteFunction(request);
            System.out.println("The " + functionName + " function was deleted");

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode

- UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;

public class Handler implements RequestHandler<KinesisEvent, Void> {
    @Override
    public Void handleRequest(final KinesisEvent event, final Context context) {
        LambdaLogger logger = context.getLogger();
        if (event.getRecords().isEmpty()) {
            logger.log("Empty Kinesis Event received");
            return null;
        }
        for (KinesisEvent.KinesisEventRecord record : event.getRecords()) {
            try {
                logger.log("Processed Event with EventId: "+record.getEventID());
                String data = new String(record.getKinesis().getData().array());
                logger.log("Data:"+ data);
                // TODO: Do interesting work based on the new data
```

```
            }
            catch (Exception ex) {
                logger.log("An error occurred:"+ex.getMessage());
                throw ex;
            }
        }
        logger.log("Successfully processed:"+event.getRecords().size()+" records");
        return null;
    }

}
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Java.

```
package example;

import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.S3Client;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.S3Event;
import
 com.amazonaws.services.lambda.runtime.events.models.s3.S3EventNotification.S3EventNotificat
```

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Handler implements RequestHandler<S3Event, String> {
    private static final Logger logger = LoggerFactory.getLogger(Handler.class);
    @Override
    public String handleRequest(S3Event s3event, Context context) {
        try {
          S3EventNotificationRecord record = s3event.getRecords().get(0);
          String srcBucket = record.getS3().getBucket().getName();
          String srcKey = record.getS3().getObject().getUrlDecodedKey();

          S3Client s3Client = S3Client.builder().build();
          HeadObjectResponse headObject = getHeadObject(s3Client, srcBucket,
 srcKey);

          logger.info("Successfully retrieved " + srcBucket + "/" + srcKey + " of
 type " + headObject.contentType());

          return "Ok";
        } catch (Exception e) {
          throw new RuntimeException(e);
        }
    }

    private HeadObjectResponse getHeadObject(S3Client s3Client, String bucket,
 String key) {
        HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                .bucket(bucket)
                .key(key)
                .build();
        return s3Client.headObject(headObjectRequest);
    }
}
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SNSEvent;
import com.amazonaws.services.lambda.runtime.events.SNSEvent.SNSRecord;


import java.util.Iterator;
import java.util.List;

public class SNSEventHandler implements RequestHandler<SNSEvent, Boolean> {
    LambdaLogger logger;

    @Override
    public Boolean handleRequest(SNSEvent event, Context context) {
        logger = context.getLogger();
        List<SNSRecord> records = event.getRecords();
        if (!records.isEmpty()) {
            Iterator<SNSRecord> recordsIter = records.iterator();
            while (recordsIter.hasNext()) {
                processRecord(recordsIter.next());
            }
        }
        return Boolean.TRUE;
    }

    public void processRecord(SNSRecord record) {
        try {
            String message = record.getSNS().getMessage();
            logger.log("message: " + message);
        } catch (Exception e) {
```

```
            throw new RuntimeException(e);
        }
    }

}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando JavaScript.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSEvent.SQSMessage;

public class Function implements RequestHandler<SQSEvent, Void> {
    @Override
    public Void handleRequest(SQSEvent sqsEvent, Context context) {
        for (SQSMessage msg : sqsEvent.getRecords()) {
            processMessage(msg, context);
        }
        context.getLogger().log("done");
        return null;
    }
```

```
    private void processMessage(SQSMessage msg, Context context) {
        try {
            context.getLogger().log("Processed message " + msg.getBody());

            // TODO: Do interesting work based on the new message

        } catch (Exception e) {
            context.getLogger().log("An error occurred");
            throw e;
        }

    }
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.KinesisEvent;
import com.amazonaws.services.lambda.runtime.events.StreamsEventResponse;

import java.io.Serializable;
import java.util.ArrayList;
import java.util.List;

public class ProcessKinesisRecords implements RequestHandler<KinesisEvent,
 StreamsEventResponse> {
```

```
    @Override
    public StreamsEventResponse handleRequest(KinesisEvent input, Context context) {

        List<StreamsEventResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<>();
        String curRecordSequenceNumber = "";

        for (KinesisEvent.KinesisEventRecord kinesisEventRecord :
 input.getRecords()) {
            try {
                //Process your record
                KinesisEvent.Record kinesisRecord = kinesisEventRecord.getKinesis();
                curRecordSequenceNumber = kinesisRecord.getSequenceNumber();

            } catch (Exception e) {
                /* Since we are working with streams, we can return the failed item
 immediately.
                   Lambda will immediately begin to retry processing from this
 failed item onwards. */
                batchItemFailures.add(new
 StreamsEventResponse.BatchItemFailure(curRecordSequenceNumber));
                return new StreamsEventResponse(batchItemFailures);
            }
        }

       return new StreamsEventResponse(batchItemFailures);
    }
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSBatchResponse;

import java.util.ArrayList;
import java.util.List;

public class ProcessSQSMessageBatch implements RequestHandler<SQSEvent,
 SQSBatchResponse> {
    @Override
    public SQSBatchResponse handleRequest(SQSEvent sqsEvent, Context context) {

        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<SQSBatchResponse.BatchItemFailure>();
        String messageId = "";
        for (SQSEvent.SQSMessage message : sqsEvent.getRecords()) {
            try {
                //process your message
                messageId = message.getMessageId();
            } catch (Exception e) {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.add(new
 SQSBatchResponse.BatchItemFailure(messageId));
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }
}
```

MediaConvert exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with MediaConvert.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar trabalho de transcodificação

O exemplo de código a seguir mostra como criar um trabalho de transcodificação doAWS Elemental MediaConvert.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.mediaconvert;

import java.net.URI;
import java.util.HashMap;
import java.util.Map;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
```

```
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.Output;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import software.amazon.awssdk.services.mediaconvert.model.OutputGroup;
import software.amazon.awssdk.services.mediaconvert.model.OutputGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.HlsGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.OutputGroupType;
import software.amazon.awssdk.services.mediaconvert.model.HlsDirectoryStructure;
import software.amazon.awssdk.services.mediaconvert.model.HlsManifestDurationFormat;
import software.amazon.awssdk.services.mediaconvert.model.HlsStreamInfResolution;
import software.amazon.awssdk.services.mediaconvert.model.HlsClientCache;
import software.amazon.awssdk.services.mediaconvert.model.HlsCaptionLanguageSetting;
import software.amazon.awssdk.services.mediaconvert.model.HlsManifestCompression;
import software.amazon.awssdk.services.mediaconvert.model.HlsCodecSpecification;
import software.amazon.awssdk.services.mediaconvert.model.HlsOutputSelection;
import software.amazon.awssdk.services.mediaconvert.model.HlsProgramDateTime;
import software.amazon.awssdk.services.mediaconvert.model.HlsTimedMetadataId3Frame;
import software.amazon.awssdk.services.mediaconvert.model.HlsSegmentControl;
import software.amazon.awssdk.services.mediaconvert.model.FileGroupSettings;
import software.amazon.awssdk.services.mediaconvert.model.ContainerSettings;
import software.amazon.awssdk.services.mediaconvert.model.VideoDescription;
import software.amazon.awssdk.services.mediaconvert.model.ContainerType;
import software.amazon.awssdk.services.mediaconvert.model.ScalingBehavior;
import software.amazon.awssdk.services.mediaconvert.model.VideoTimecodeInsertion;
import software.amazon.awssdk.services.mediaconvert.model.ColorMetadata;
import software.amazon.awssdk.services.mediaconvert.model.RespondToAfd;
import software.amazon.awssdk.services.mediaconvert.model.AfdSignaling;
import software.amazon.awssdk.services.mediaconvert.model.DropFrameTimecode;
import software.amazon.awssdk.services.mediaconvert.model.VideoCodecSettings;
import software.amazon.awssdk.services.mediaconvert.model.H264Settings;
import software.amazon.awssdk.services.mediaconvert.model.VideoCodec;
import software.amazon.awssdk.services.mediaconvert.model.CreateJobRequest;
import software.amazon.awssdk.services.mediaconvert.model.H264RateControlMode;
import software.amazon.awssdk.services.mediaconvert.model.H264QualityTuningLevel;
import software.amazon.awssdk.services.mediaconvert.model.H264SceneChangeDetect;
import
 software.amazon.awssdk.services.mediaconvert.model.AacAudioDescriptionBroadcasterMix;
import software.amazon.awssdk.services.mediaconvert.model.H264ParControl;
import software.amazon.awssdk.services.mediaconvert.model.AacRawFormat;
import software.amazon.awssdk.services.mediaconvert.model.H264QvbrSettings;
import
 software.amazon.awssdk.services.mediaconvert.model.H264FramerateConversionAlgorithm;
import software.amazon.awssdk.services.mediaconvert.model.H264CodecLevel;
import software.amazon.awssdk.services.mediaconvert.model.H264FramerateControl;
```

```
import software.amazon.awssdk.services.mediaconvert.model.AacCodingMode;
import software.amazon.awssdk.services.mediaconvert.model.H264Telecine;
import
 software.amazon.awssdk.services.mediaconvert.model.H264FlickerAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.H264GopSizeUnits;
import software.amazon.awssdk.services.mediaconvert.model.H264CodecProfile;
import software.amazon.awssdk.services.mediaconvert.model.H264GopBReference;
import software.amazon.awssdk.services.mediaconvert.model.AudioTypeControl;
import software.amazon.awssdk.services.mediaconvert.model.AntiAlias;
import software.amazon.awssdk.services.mediaconvert.model.H264SlowPal;
import
 software.amazon.awssdk.services.mediaconvert.model.H264SpatialAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.H264Syntax;
import software.amazon.awssdk.services.mediaconvert.model.M3u8Settings;
import software.amazon.awssdk.services.mediaconvert.model.InputDenoiseFilter;
import
 software.amazon.awssdk.services.mediaconvert.model.H264TemporalAdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.CreateJobResponse;
import
 software.amazon.awssdk.services.mediaconvert.model.H264UnregisteredSeiTimecode;
import software.amazon.awssdk.services.mediaconvert.model.H264EntropyEncoding;
import software.amazon.awssdk.services.mediaconvert.model.InputPsiControl;
import software.amazon.awssdk.services.mediaconvert.model.ColorSpace;
import software.amazon.awssdk.services.mediaconvert.model.H264RepeatPps;
import software.amazon.awssdk.services.mediaconvert.model.H264FieldEncoding;
import software.amazon.awssdk.services.mediaconvert.model.M3u8NielsenId3;
import software.amazon.awssdk.services.mediaconvert.model.InputDeblockFilter;
import software.amazon.awssdk.services.mediaconvert.model.InputRotate;
import software.amazon.awssdk.services.mediaconvert.model.H264DynamicSubGop;
import software.amazon.awssdk.services.mediaconvert.model.TimedMetadata;
import software.amazon.awssdk.services.mediaconvert.model.JobSettings;
import software.amazon.awssdk.services.mediaconvert.model.AudioDefaultSelection;
import software.amazon.awssdk.services.mediaconvert.model.VideoSelector;
import software.amazon.awssdk.services.mediaconvert.model.AacSpecification;
import software.amazon.awssdk.services.mediaconvert.model.Input;
import software.amazon.awssdk.services.mediaconvert.model.OutputSettings;
import software.amazon.awssdk.services.mediaconvert.model.H264AdaptiveQuantization;
import software.amazon.awssdk.services.mediaconvert.model.AudioLanguageCodeControl;
import software.amazon.awssdk.services.mediaconvert.model.InputFilterEnable;
import software.amazon.awssdk.services.mediaconvert.model.AudioDescription;
import software.amazon.awssdk.services.mediaconvert.model.H264InterlaceMode;
import software.amazon.awssdk.services.mediaconvert.model.AudioCodecSettings;
import software.amazon.awssdk.services.mediaconvert.model.AacSettings;
import software.amazon.awssdk.services.mediaconvert.model.AudioCodec;
```

```
import software.amazon.awssdk.services.mediaconvert.model.AacRateControlMode;
import software.amazon.awssdk.services.mediaconvert.model.AacCodecProfile;
import software.amazon.awssdk.services.mediaconvert.model.HlsIFrameOnlyManifest;
import software.amazon.awssdk.services.mediaconvert.model.FrameCaptureSettings;
import software.amazon.awssdk.services.mediaconvert.model.AudioSelector;
import software.amazon.awssdk.services.mediaconvert.model.M3u8PcrControl;
import software.amazon.awssdk.services.mediaconvert.model.InputTimecodeSource;
import software.amazon.awssdk.services.mediaconvert.model.HlsSettings;
import software.amazon.awssdk.services.mediaconvert.model.M3u8Scte35Source;

/**
 * Create a MediaConvert job. Must supply MediaConvert access role Amazon
 * Resource Name (ARN), and a
 * valid video input file via Amazon S3 URL.
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 */
public class CreateJob {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                    <mcRoleARN> <fileInput>\s

                                Where:
                                    mcRoleARN - The MediaConvert Role ARN.\s
                                    fileInput -  The URL of an Amazon S3 bucket
 where the input file is located.\s
                                """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String mcRoleARN = args[0];
                String fileInput = args[1];
                Region region = Region.US_WEST_2;
                MediaConvertClient mc = MediaConvertClient.builder()
```

```
                                .region(region)
                                .build();

                String id = createMediaJob(mc, mcRoleARN, fileInput);
                System.out.println("MediaConvert job created. Job Id = " + id);
                mc.close();
        }

        public static String createMediaJob(MediaConvertClient mc, String mcRoleARN,
String fileInput) {

                String s3path = fileInput.substring(0, fileInput.lastIndexOf('/') +
1) + "javasdk/out/";
                String fileOutput = s3path + "index";
                String thumbsOutput = s3path + "thumbs/";
                String mp4Output = s3path + "mp4/";

                try {
                        DescribeEndpointsResponse res = mc

.describeEndpoints(DescribeEndpointsRequest.builder().maxResults(20).build());

                        if (res.endpoints().size() <= 0) {
                                System.out.println("Cannot find MediaConvert service
endpoint URL!");
                                System.exit(1);
                        }
                        String endpointURL = res.endpoints().get(0).url();
                        System.out.println("MediaConvert service URL: " +
endpointURL);
                        System.out.println("MediaConvert role arn: " + mcRoleARN);
                        System.out.println("MediaConvert input file: " + fileInput);
                        System.out.println("MediaConvert output path: " + s3path);

                        MediaConvertClient emc = MediaConvertClient.builder()
                                        .region(Region.US_WEST_2)
                                        .endpointOverride(URI.create(endpointURL))
                                        .build();

                        // output group Preset HLS low profile
                        Output hlsLow = createOutput("hls_low", "_low", "_$dt$",
750000, 7, 1920, 1080, 640);
                        // output group Preset HLS media profile
```

```
                        Output hlsMedium = createOutput("hls_medium", "_medium", "_
$dt$", 1200000, 7, 1920, 1080, 1280);
                        // output group Preset HLS high profole
                        Output hlsHigh = createOutput("hls_high", "_high", "_$dt$",
 3500000, 8, 1920, 1080, 1920);

                        OutputGroup appleHLS = OutputGroup.builder().name("Apple
 HLS").customName("Example")

 .outputGroupSettings(OutputGroupSettings.builder()

 .type(OutputGroupType.HLS_GROUP_SETTINGS)

 .hlsGroupSettings(HlsGroupSettings.builder()

 .directoryStructure(

    HlsDirectoryStructure.SINGLE_DIRECTORY)

 .manifestDurationFormat(

    HlsManifestDurationFormat.INTEGER)

 .streamInfResolution(

    HlsStreamInfResolution.INCLUDE)

 .clientCache(HlsClientCache.ENABLED)

 .captionLanguageSetting(

    HlsCaptionLanguageSetting.OMIT)

 .manifestCompression(

    HlsManifestCompression.NONE)

 .codecSpecification(

    HlsCodecSpecification.RFC_4281)

 .outputSelection(

    HlsOutputSelection.MANIFESTS_AND_SEGMENTS)
```

```
.programDateTime(HlsProgramDateTime.EXCLUDE)

.programDateTimePeriod(600)

.timedMetadataId3Frame(

   HlsTimedMetadataId3Frame.PRIV)

.timedMetadataId3Period(10)

.destination(fileOutput)

.segmentControl(HlsSegmentControl.SEGMENTED_FILES)

.minFinalSegmentLength((double) 0)

.segmentLength(4).minSegmentLength(0).build())
                                                        .build())
                                        .outputs(hlsLow, hlsMedium,
hlsHigh).build();

                       OutputGroup fileMp4 = OutputGroup.builder().name("File
Group").customName("mp4")

.outputGroupSettings(OutputGroupSettings.builder()

.type(OutputGroupType.FILE_GROUP_SETTINGS)

.fileGroupSettings(FileGroupSettings.builder()

.destination(mp4Output).build())
                                                        .build())
                                        .outputs(Output.builder().extension("mp4")

.containerSettings(ContainerSettings.builder()

.container(ContainerType.MP4).build())

.videoDescription(VideoDescription.builder().width(1280)
                                                                        .height(720)

.scalingBehavior(ScalingBehavior.DEFAULT)
```

```
.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

   VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.respondToAfd(RespondToAfd.NONE)

.afdSignaling(AfdSignaling.NONE)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

   .codec(VideoCodec.H_264)

   .h264Settings(H264Settings

                   .builder()

                   .rateControlMode(

                                   H264RateControlMode.QVBR)

                   .parControl(H264ParControl.INITIALIZE_FROM_SOURCE)

                   .qualityTuningLevel(

                                   H264QualityTuningLevel.SINGLE_PASS)

                   .qvbrSettings(

                                   H264QvbrSettings.builder()

                                                   .qvbrQualityLevel(

                                                                   8)

                                                   .build())

                   .codecLevel(H264CodecLevel.AUTO)
```

```
                .codecProfile(H264CodecProfile.MAIN)
                .maxBitrate(2400000)
                .framerateControl(
                        H264FramerateControl.INITIALIZE_FROM_SOURCE)
                .gopSize(2.0)
                .gopSizeUnits(H264GopSizeUnits.SECONDS)
                .numberBFramesBetweenReferenceFrames(
                        2)
                .gopClosedCadence(
                        1)
                .gopBReference(H264GopBReference.DISABLED)
                .slowPal(H264SlowPal.DISABLED)
                .syntax(H264Syntax.DEFAULT)
                .numberReferenceFrames(
                        3)
                .dynamicSubGop(H264DynamicSubGop.STATIC)
                .fieldEncoding(H264FieldEncoding.PAFF)
                .sceneChangeDetect(
                        H264SceneChangeDetect.ENABLED)
                .minIInterval(0)
                .telecine(H264Telecine.NONE)
                .framerateConversionAlgorithm(
```

```
                                H264FramerateConversionAlgorithm.DUPLICATE_DROP)
                    .entropyEncoding(
                                H264EntropyEncoding.CABAC)
                    .slices(1)
                    .unregisteredSeiTimecode(
                                H264UnregisteredSeiTimecode.DISABLED)
                    .repeatPps(H264RepeatPps.DISABLED)
                    .adaptiveQuantization(
                                H264AdaptiveQuantization.HIGH)
                    .spatialAdaptiveQuantization(
                                H264SpatialAdaptiveQuantization.ENABLED)
                    .temporalAdaptiveQuantization(
                                H264TemporalAdaptiveQuantization.ENABLED)
                    .flickerAdaptiveQuantization(
                                H264FlickerAdaptiveQuantization.DISABLED)
                    .softness(0)
                    .interlaceMode(H264InterlaceMode.PROGRESSIVE)
                    .build())
   .build())
                                                                .build())
.audioDescriptions(AudioDescription.builder()
.audioTypeControl(AudioTypeControl.FOLLOW_INPUT)
```

```
.languageCodeControl(

   AudioLanguageCodeControl.FOLLOW_INPUT)

.codecSettings(AudioCodecSettings.builder()

   .codec(AudioCodec.AAC)

   .aacSettings(AacSettings

                    .builder()

                    .codecProfile(AacCodecProfile.LC)

                    .rateControlMode(

                                   AacRateControlMode.CBR)

                    .codingMode(AacCodingMode.CODING_MODE_2_0)

                    .sampleRate(44100)

                    .bitrate(160000)

                    .rawFormat(AacRawFormat.NONE)

                    .specification(AacSpecification.MPEG4)

                    .audioDescriptionBroadcasterMix(

                                   AacAudioDescriptionBroadcasterMix.NORMAL)

                    .build())

   .build())
                                                                        .build())
                                                              .build())
                                          .build();
                       OutputGroup thumbs = OutputGroup.builder().name("File
Group").customName("thumbs")

.outputGroupSettings(OutputGroupSettings.builder()
```

```
.type(OutputGroupType.FILE_GROUP_SETTINGS)

.fileGroupSettings(FileGroupSettings.builder()

.destination(thumbsOutput).build())
                                                                .build())
                                        .outputs(Output.builder().extension("jpg")

.containerSettings(ContainerSettings.builder()

.container(ContainerType.RAW).build())

.videoDescription(VideoDescription.builder()

.scalingBehavior(ScalingBehavior.DEFAULT)

.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

   VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

   .codec(VideoCodec.FRAME_CAPTURE)

   .frameCaptureSettings(

                    FrameCaptureSettings

                                    .builder()

                                    .framerateNumerator(

                                                    1)

                                    .framerateDenominator(

                                                    1)
```

```
                                    .maxCaptures(10000000)

                                    .quality(80)

                                    .build())

   .build())
                                                                        .build())
                                                        .build())
                                        .build();

                        Map<String, AudioSelector> audioSelectors = new HashMap<>();
                        audioSelectors.put("Audio Selector 1",

AudioSelector.builder().defaultSelection(AudioDefaultSelection.DEFAULT)
                                                        .offset(0).build());

                        JobSettings jobSettings =
JobSettings.builder().inputs(Input.builder()
                                        .audioSelectors(audioSelectors)
                                        .videoSelector(

VideoSelector.builder().colorSpace(ColorSpace.FOLLOW)

.rotate(InputRotate.DEGREE_0).build())

.filterEnable(InputFilterEnable.AUTO).filterStrength(0)
                                        .deblockFilter(InputDeblockFilter.DISABLED)

.denoiseFilter(InputDenoiseFilter.DISABLED).psiControl(InputPsiControl.USE_PSI)

.timecodeSource(InputTimecodeSource.EMBEDDED).fileInput(fileInput).build())
                                        .outputGroups(appleHLS, thumbs,
fileMp4).build();

                        CreateJobRequest createJobRequest =
CreateJobRequest.builder().role(mcRoleARN)
                                        .settings(jobSettings)
                                        .build();

                        CreateJobResponse createJobResponse =
emc.createJob(createJobRequest);
                        return createJobResponse.job().id();
```

```
                } catch (MediaConvertException e) {
                        System.out.println(e.toString());
                        System.exit(0);
                }
                return "";
        }

        private final static Output createOutput(String customName,
                        String nameModifier,
                        String segmentModifier,
                        int qvbrMaxBitrate,
                        int qvbrQualityLevel,
                        int originWidth,
                        int originHeight,
                        int targetWidth) {

                int targetHeight = Math.round(originHeight * targetWidth /
originWidth)
                                - (Math.round(originHeight * targetWidth /
originWidth) % 4);
                Output output = null;
                try {
                        output =
Output.builder().nameModifier(nameModifier).outputSettings(OutputSettings.builder()

.hlsSettings(HlsSettings.builder().segmentModifier(segmentModifier)

.audioGroupId("program_audio")

.iFrameOnlyManifest(HlsIFrameOnlyManifest.EXCLUDE).build())
                                        .build())

.containerSettings(ContainerSettings.builder().container(ContainerType.M3_U8)

.m3u8Settings(M3u8Settings.builder().audioFramesPerPes(4)

.pcrControl(M3u8PcrControl.PCR_EVERY_PES_PACKET)

.pmtPid(480).privateMetadataPid(503)

.programNumber(1).patInterval(0).pmtInterval(0)

.scte35Source(M3u8Scte35Source.NONE)
```

```
.scte35Pid(500).nielsenId3(M3u8NielsenId3.NONE)

.timedMetadata(TimedMetadata.NONE)

.timedMetadataPid(502).videoPid(481)

.audioPids(482, 483, 484, 485, 486, 487, 488,

   489, 490, 491, 492)
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
VideoDescription.builder().width(targetWidth)

.height(targetHeight)

.scalingBehavior(ScalingBehavior.DEFAULT)

.sharpness(50).antiAlias(AntiAlias.ENABLED)

.timecodeInsertion(

   VideoTimecodeInsertion.DISABLED)

.colorMetadata(ColorMetadata.INSERT)

.respondToAfd(RespondToAfd.NONE)

.afdSignaling(AfdSignaling.NONE)

.dropFrameTimecode(DropFrameTimecode.ENABLED)

.codecSettings(VideoCodecSettings.builder()

   .codec(VideoCodec.H_264)

   .h264Settings(H264Settings

                    .builder()

                    .rateControlMode(
```

```
                                H264RateControlMode.QVBR)
                        .parControl(H264ParControl.INITIALIZE_FROM_SOURCE)
                        .qualityTuningLevel(
                                H264QualityTuningLevel.SINGLE_PASS)
                        .qvbrSettings(H264QvbrSettings
                                .builder()
                                .qvbrQualityLevel(
                                                qvbrQualityLevel)
                                .build())
                        .codecLevel(H264CodecLevel.AUTO)
                        .codecProfile((targetHeight > 720
                                && targetWidth > 1280)
                                                ? H264CodecProfile.HIGH
                                                : H264CodecProfile.MAIN)
                        .maxBitrate(qvbrMaxBitrate)
                        .framerateControl(
                                H264FramerateControl.INITIALIZE_FROM_SOURCE)
                        .gopSize(2.0)
                        .gopSizeUnits(H264GopSizeUnits.SECONDS)
                        .numberBFramesBetweenReferenceFrames(
                                2)
                        .gopClosedCadence(
```

```
                1)
        .gopBReference(H264GopBReference.DISABLED)
        .slowPal(H264SlowPal.DISABLED)
        .syntax(H264Syntax.DEFAULT)
        .numberReferenceFrames(
                3)
        .dynamicSubGop(H264DynamicSubGop.STATIC)
        .fieldEncoding(H264FieldEncoding.PAFF)
        .sceneChangeDetect(
                H264SceneChangeDetect.ENABLED)
        .minIInterval(0)
        .telecine(H264Telecine.NONE)
        .framerateConversionAlgorithm(
                H264FramerateConversionAlgorithm.DUPLICATE_DROP)
        .entropyEncoding(
                H264EntropyEncoding.CABAC)
        .slices(1)
        .unregisteredSeiTimecode(
                H264UnregisteredSeiTimecode.DISABLED)
        .repeatPps(H264RepeatPps.DISABLED)
        .adaptiveQuantization(
                H264AdaptiveQuantization.HIGH)
```

```
                    .spatialAdaptiveQuantization(
                                    H264SpatialAdaptiveQuantization.ENABLED)
                    .temporalAdaptiveQuantization(
                                    H264TemporalAdaptiveQuantization.ENABLED)
                    .flickerAdaptiveQuantization(
                                    H264FlickerAdaptiveQuantization.DISABLED)
                    .softness(0)
                    .interlaceMode(H264InterlaceMode.PROGRESSIVE)
                    .build())
    .build())
                                                                    .build())
.audioDescriptions(AudioDescription.builder()
.audioTypeControl(AudioTypeControl.FOLLOW_INPUT)
.languageCodeControl(AudioLanguageCodeControl.FOLLOW_INPUT)
.codecSettings(AudioCodecSettings.builder()
.codec(AudioCodec.AAC).aacSettings(AacSettings
    .builder()
    .codecProfile(AacCodecProfile.LC)
    .rateControlMode(
                    AacRateControlMode.CBR)
    .codingMode(AacCodingMode.CODING_MODE_2_0)
    .sampleRate(44100)
```

```
    .bitrate(96000)

    .rawFormat(AacRawFormat.NONE)

    .specification(AacSpecification.MPEG4)

    .audioDescriptionBroadcasterMix(

                    AacAudioDescriptionBroadcasterMix.NORMAL)

    .build())
                                                                    .build())
                                                        .build())
                                        .build();
                } catch (MediaConvertException e) {
                        e.printStackTrace();
                        System.exit(0);
                }
                return output;
        }
}
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for Java 2.x da API.

Obter um trabalho de transcodificação

O exemplo de código a seguir mostra como obter um trabalho de transcodificação do AWS Elemental MediaConvert.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
import software.amazon.awssdk.services.mediaconvert.model.GetJobRequest;
```

```
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.GetJobResponse;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import java.net.URI;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetJob {

    public static void main(String[] args) {

        final String usage = "\n" +
                "  <jobId> \n\n" +
                "Where:\n" +
                "  jobId - The job id value.\n\n";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String jobId = args[0];
        Region region = Region.US_WEST_2;
        MediaConvertClient mc = MediaConvertClient.builder()
                .region(region)
                .build();

        getSpecificJob(mc, jobId);
        mc.close();
    }

    public static void getSpecificJob(MediaConvertClient mc, String jobId) {
        try {
            DescribeEndpointsResponse res =
 mc.describeEndpoints(DescribeEndpointsRequest.builder()
                    .maxResults(20)
                    .build());
```

```
            if (res.endpoints().size() <= 0) {
                System.out.println("Cannot find MediaConvert service endpoint
 URL!");
                System.exit(1);
            }
            String endpointURL = res.endpoints().get(0).url();
            MediaConvertClient emc = MediaConvertClient.builder()
                    .region(Region.US_WEST_2)
                    .endpointOverride(URI.create(endpointURL))
                    .build();

            GetJobRequest jobRequest = GetJobRequest.builder()
                    .id(jobId)
                    .build();

            GetJobResponse response = emc.getJob(jobRequest);
            System.out.println("The ARN of the job is " + response.job().arn());

        } catch (MediaConvertException e) {
            System.out.println(e.toString());
            System.exit(0);
        }
    }
}
```

- Para obter detalhes da API, consulte GetJoba Referência AWS SDK for Java 2.x da API.

Listar trabalhos de transcodificação

O exemplo de código a seguir mostra como listar trabalhos transcodificação AWS Elemental MediaConvert.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.mediaconvert.MediaConvertClient;
import software.amazon.awssdk.services.mediaconvert.model.ListJobsRequest;
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsResponse;
import software.amazon.awssdk.services.mediaconvert.model.DescribeEndpointsRequest;
import software.amazon.awssdk.services.mediaconvert.model.ListJobsResponse;
import software.amazon.awssdk.services.mediaconvert.model.Job;
import software.amazon.awssdk.services.mediaconvert.model.MediaConvertException;
import java.net.URI;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListJobs {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MediaConvertClient mc = MediaConvertClient.builder()
                .region(region)
                .build();

        listCompleteJobs(mc);
        mc.close();
    }

    public static void listCompleteJobs(MediaConvertClient mc) {
        try {
            DescribeEndpointsResponse res =
 mc.describeEndpoints(DescribeEndpointsRequest.builder()
                    .maxResults(20)
                    .build());

            if (res.endpoints().size() <= 0) {
                System.out.println("Cannot find MediaConvert service endpoint
 URL!");
                System.exit(1);
            }
```

```
            String endpointURL = res.endpoints().get(0).url();
            MediaConvertClient emc = MediaConvertClient.builder()
                    .region(Region.US_WEST_2)
                    .endpointOverride(URI.create(endpointURL))
                    .build();

            ListJobsRequest jobsRequest = ListJobsRequest.builder()
                    .maxResults(10)
                    .status("COMPLETE")
                    .build();

            ListJobsResponse jobsResponse = emc.listJobs(jobsRequest);
            List<Job> jobs = jobsResponse.jobs();
            for (Job job : jobs) {
                System.out.println("The JOB ARN is : " + job.arn());
            }

        } catch (MediaConvertException e) {
            System.out.println(e.toString());
            System.exit(0);
        }
    }
}
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Java 2.x da API.

Exemplos do Migration Hub usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Migration Hub.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir stream de progresso

O exemplo de código a seguir mostra como excluir um stream de progresso.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DeleteProgressUpdateStreamRequest;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteProgressStream {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <progressStream>\s

                Where:
                    progressStream - the name of a progress stream to delete.\s
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String progressStream = args[0];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        deleteStream(migrationClient, progressStream);
        migrationClient.close();
    }

    public static void deleteStream(MigrationHubClient migrationClient, String
 streamName) {
        try {
            DeleteProgressUpdateStreamRequest deleteProgressUpdateStreamRequest =
 DeleteProgressUpdateStreamRequest
                    .builder()
                    .progressUpdateStreamName(streamName)
                    .build();


 migrationClient.deleteProgressUpdateStream(deleteProgressUpdateStreamRequest);
            System.out.println(streamName + " is deleted");

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteProgressUpdateStreama Referência AWS SDK for Java 2.x da API.

Descrever status da migração

O exemplo de código a seguir mostra como descrever o status da migração.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeApplicationStateRequest;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeApplicationStateResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeAppState {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    DescribeAppState <appId>\s

                Where:
                    appId -  the application id value.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        Region region = Region.US_WEST_2;
```

```
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        describeApplicationState(migrationClient, appId);
        migrationClient.close();
    }

    public static void describeApplicationState(MigrationHubClient migrationClient,
 String appId) {
        try {
            DescribeApplicationStateRequest applicationStateRequest =
 DescribeApplicationStateRequest.builder()
                    .applicationId(appId)
                    .build();

            DescribeApplicationStateResponse applicationStateResponse =
 migrationClient
                    .describeApplicationState(applicationStateRequest);
            System.out.println("The application status is " +
 applicationStateResponse.applicationStatusAsString());

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeApplicationStatea Referência AWS SDK for Java 2.x da API.

Obter uma lista de atributos associados a uma migração

O exemplo de código a seguir mostra como obter uma lista de atributos associados a uma migração.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeMigrationTaskRequest;
import
 software.amazon.awssdk.services.migrationhub.model.DescribeMigrationTaskResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeMigrationTask {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    DescribeMigrationTask <migrationTask> <progressStream>\s

                Where:
                    migrationTask - the name of a migration task.\s
                    progressStream - the name of a progress stream.\s
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String migrationTask = args[0];
        String progressStream = args[1];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        describeMigTask(migrationClient, migrationTask, progressStream);
        migrationClient.close();
    }

    public static void describeMigTask(MigrationHubClient migrationClient, String
 migrationTask,
            String progressStream) {
        try {
            DescribeMigrationTaskRequest migrationTaskRequestRequest =
 DescribeMigrationTaskRequest.builder()
                    .progressUpdateStream(progressStream)
                    .migrationTaskName(migrationTask)
                    .build();

            DescribeMigrationTaskResponse migrationTaskResponse = migrationClient
                    .describeMigrationTask(migrationTaskRequestRequest);
            System.out.println("The name is " +
 migrationTaskResponse.migrationTask().migrationTaskName());

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeMigrationTaska Referência AWS SDK for Java 2.x da API.

Listar aplicações

O exemplo de código a seguir mostra como listar aplicações.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import software.amazon.awssdk.services.migrationhub.model.ApplicationState;
import
 software.amazon.awssdk.services.migrationhub.model.ListApplicationStatesRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListApplicationStatesResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListApplications {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        listApps(migrationClient);
        migrationClient.close();
    }

    public static void listApps(MigrationHubClient migrationClient) {
        try {
            ListApplicationStatesRequest applicationStatesRequest =
 ListApplicationStatesRequest.builder()
                    .maxResults(10)
```

```
                    .build();

            ListApplicationStatesResponse response =
 migrationClient.listApplicationStates(applicationStatesRequest);
            List<ApplicationState> apps = response.applicationStateList();
            for (ApplicationState appState : apps) {
                System.out.println("App Id is " + appState.applicationId());
                System.out.println("The status is " +
 appState.applicationStatus().toString());
            }

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListApplicationsa Referência AWS SDK for Java 2.x da API.

Listar artefatos criados

O exemplo de código a seguir mostra como listar artefatos criados.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import software.amazon.awssdk.services.migrationhub.model.CreatedArtifact;
import
 software.amazon.awssdk.services.migrationhub.model.ListCreatedArtifactsRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListCreatedArtifactsResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
```

```
import java.util.List;

/**
 * To run this Java V2 code example, ensure that you have setup your development
 * environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListCreatedArtifacts {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        listArtifacts(migrationClient);
        migrationClient.close();
    }

    public static void listArtifacts(MigrationHubClient migrationClient) {
        try {
            ListCreatedArtifactsRequest listCreatedArtifactsRequest =
 ListCreatedArtifactsRequest.builder()
                    .maxResults(10)
                    .migrationTaskName("SampleApp5")
                    .progressUpdateStream("ProgressSteamB")
                    .build();

            ListCreatedArtifactsResponse response =
 migrationClient.listCreatedArtifacts(listCreatedArtifactsRequest);
            List<CreatedArtifact> apps = response.createdArtifactList();
            for (CreatedArtifact artifact : apps) {
                System.out.println("APp Id is " + artifact.description());
                System.out.println("The name is " + artifact.name());
            }

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListCreatedArtifactsa Referência AWS SDK for Java 2.x da API.

Listar tarefas de migração

O exemplo de código a seguir mostra como listar tarefas de migração.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import software.amazon.awssdk.services.migrationhub.model.ListMigrationTasksRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ListMigrationTasksResponse;
import software.amazon.awssdk.services.migrationhub.model.MigrationTaskSummary;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListMigrationTasks {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();
```

```
        listMigrTasks(migrationClient);
        migrationClient.close();
    }

    public static void listMigrTasks(MigrationHubClient migrationClient) {
        try {
            ListMigrationTasksRequest listMigrationTasksRequest =
 ListMigrationTasksRequest.builder()
                    .maxResults(10)
                    .build();

            ListMigrationTasksResponse response =
 migrationClient.listMigrationTasks(listMigrationTasksRequest);
            List<MigrationTaskSummary> migrationList =
 response.migrationTaskSummaryList();
            for (MigrationTaskSummary migration : migrationList) {
                System.out.println("Migration task name is " +
 migration.migrationTaskName());
                System.out.println("The Progress update stream is " +
 migration.progressUpdateStream());
            }

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListMigrationTasksa Referência AWS SDK for Java 2.x da API.

Registrar uma tarefa de migração

O exemplo de código a seguir mostra como registrar uma tarefa de migração.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.migrationhub.MigrationHubClient;
import
 software.amazon.awssdk.services.migrationhub.model.CreateProgressUpdateStreamRequest;
import
 software.amazon.awssdk.services.migrationhub.model.ImportMigrationTaskRequest;
import software.amazon.awssdk.services.migrationhub.model.MigrationHubException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ImportMigrationTask {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <migrationTask> <progressStream>\s

                Where:
                    migrationTask - the name of a migration task.\s
                    progressStream - the name of a progress stream.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String migrationTask = args[0];
```

```
        String progressStream = args[1];
        Region region = Region.US_WEST_2;
        MigrationHubClient migrationClient = MigrationHubClient.builder()
                .region(region)
                .build();

        importMigrTask(migrationClient, migrationTask, progressStream);
        migrationClient.close();
    }

    public static void importMigrTask(MigrationHubClient migrationClient, String
 migrationTask, String progressStream) {
        try {
            CreateProgressUpdateStreamRequest progressUpdateStreamRequest =
 CreateProgressUpdateStreamRequest.builder()
                    .progressUpdateStreamName(progressStream)
                    .dryRun(false)
                    .build();

            migrationClient.createProgressUpdateStream(progressUpdateStreamRequest);
            ImportMigrationTaskRequest migrationTaskRequest =
 ImportMigrationTaskRequest.builder()
                    .migrationTaskName(migrationTask)
                    .progressUpdateStream(progressStream)
                    .dryRun(false)
                    .build();

            migrationClient.importMigrationTask(migrationTaskRequest);

        } catch (MigrationHubException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ImportMigrationTaska Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Personalize usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Personalize.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um trabalho de interface em lote

O exemplo de código a seguir mostra como criar um trabalho de interface em lote do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static String createPersonalizeBatchInferenceJob(PersonalizeClient
personalizeClient,
                        String solutionVersionArn,
                        String jobName,
                        String s3InputDataSourcePath,
                        String s3DataDestinationPath,
                        String roleArn,
                        String explorationWeight,
```

```
                        String explorationItemAgeCutOff) {

                long waitInMilliseconds = 60 * 1000;
                String status;
                String batchInferenceJobArn;

                try {

                        // Set up data input and output parameters.
                        S3DataConfig inputSource = S3DataConfig.builder()
                                        .path(s3InputDataSourcePath)
                                        .build();

                        S3DataConfig outputDestination = S3DataConfig.builder()
                                        .path(s3DataDestinationPath)
                                        .build();

                        BatchInferenceJobInput jobInput =
BatchInferenceJobInput.builder()
                                        .s3DataSource(inputSource)
                                        .build();

                        BatchInferenceJobOutput jobOutputLocation =
BatchInferenceJobOutput.builder()
                                        .s3DataDestination(outputDestination)
                                        .build();

                        // Optional code to build the User-Personalization specific
item exploration
                        // config.
                        HashMap<String, String> explorationConfig = new HashMap<>();

                        explorationConfig.put("explorationWeight",
explorationWeight);
                        explorationConfig.put("explorationItemAgeCutOff",
explorationItemAgeCutOff);

                        BatchInferenceJobConfig jobConfig =
BatchInferenceJobConfig.builder()
                                        .itemExplorationConfig(explorationConfig)
                                        .build();

                        // End optional User-Personalization recipe specific code.
```

```
                        CreateBatchInferenceJobRequest
createBatchInferenceJobRequest = CreateBatchInferenceJobRequest
                                        .builder()
                                        .solutionVersionArn(solutionVersionArn)
                                        .jobInput(jobInput)
                                        .jobOutput(jobOutputLocation)
                                        .jobName(jobName)
                                        .roleArn(roleArn)
                                        .batchInferenceJobConfig(jobConfig) //
Optional
                                        .build();

                        batchInferenceJobArn =
personalizeClient.createBatchInferenceJob(createBatchInferenceJobRequest)
                                        .batchInferenceJobArn();

                        DescribeBatchInferenceJobRequest
describeBatchInferenceJobRequest = DescribeBatchInferenceJobRequest
                                        .builder()
                                        .batchInferenceJobArn(batchInferenceJobArn)
                                        .build();

                        long maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;
                        while (Instant.now().getEpochSecond() < maxTime) {

                                BatchInferenceJob batchInferenceJob =
personalizeClient

.describeBatchInferenceJob(describeBatchInferenceJobRequest)
                                                .batchInferenceJob();

                                status = batchInferenceJob.status();
                                System.out.println("Batch inference job status: " +
status);

                                if (status.equals("ACTIVE") || status.equals("CREATE
FAILED")) {
                                        break;
                                }
                                try {
                                        Thread.sleep(waitInMilliseconds);
                                } catch (InterruptedException e) {
                                        System.out.println(e.getMessage());
                                }
```

```
                        }
                        return batchInferenceJobArn;

                } catch (PersonalizeException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
                }
                return "";
        }
```

- Para obter detalhes da API, consulte CreateBatchInferenceJoba Referência AWS SDK for Java 2.x da API.

Criar uma campanha

O exemplo de código a seguir mostra como criar uma campanha do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalCompaign(PersonalizeClient personalizeClient,
String solutionVersionArn,
           String name) {

       try {
           CreateCampaignRequest createCampaignRequest =
CreateCampaignRequest.builder()
                   .minProvisionedTPS(1)
                   .solutionVersionArn(solutionVersionArn)
                   .name(name)
                   .build();

           CreateCampaignResponse campaignResponse =
personalizeClient.createCampaign(createCampaignRequest);
           System.out.println("The campaign ARN is " +
campaignResponse.campaignArn());
           return campaignResponse.campaignArn();
```

```
        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "" ;
    }
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for Java 2.x da API.

Criar um conjunto de dados

O exemplo de código a seguir mostra como criar um conjunto de dados do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createDataset(PersonalizeClient personalizeClient,
            String datasetName,
            String datasetGroupArn,
            String datasetType,
            String schemaArn) {
        try {
            CreateDatasetRequest request = CreateDatasetRequest.builder()
                    .name(datasetName)
                    .datasetGroupArn(datasetGroupArn)
                    .datasetType(datasetType)
                    .schemaArn(schemaArn)
                    .build();

            String datasetArn = personalizeClient.createDataset(request)
                    .datasetArn();
            System.out.println("Dataset " + datasetName + " created.");
            return datasetArn;
```

```
        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetA Referência AWS SDK for Java 2.x da API.

Criar um trabalho de exportação de conjunto de dados

O exemplo de código a seguir mostra como criar um trabalho de exportação de conjunto de dados do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createDatasetExportJob(PersonalizeClient personalizeClient,
            String jobName,
            String datasetArn,
            IngestionMode ingestionMode,
            String roleArn,
            String s3BucketPath,
            String kmsKeyArn) {

        long waitInMilliseconds = 30 * 1000; // 30 seconds
        String status = null;

        try {

            S3DataConfig exportS3DataConfig =
S3DataConfig.builder().path(s3BucketPath).kmsKeyArn(kmsKeyArn).build();
            DatasetExportJobOutput jobOutput =
DatasetExportJobOutput.builder().s3DataDestination(exportS3DataConfig)
```

```
                    .build();

            CreateDatasetExportJobRequest createRequest =
CreateDatasetExportJobRequest.builder()
                    .jobName(jobName)
                    .datasetArn(datasetArn)
                    .ingestionMode(ingestionMode)
                    .jobOutput(jobOutput)
                    .roleArn(roleArn)
                    .build();

            String datasetExportJobArn =
personalizeClient.createDatasetExportJob(createRequest).datasetExportJobArn();

            DescribeDatasetExportJobRequest describeDatasetExportJobRequest =
DescribeDatasetExportJobRequest.builder()
                    .datasetExportJobArn(datasetExportJobArn)
                    .build();

            long maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            while (Instant.now().getEpochSecond() < maxTime) {

                DatasetExportJob datasetExportJob = personalizeClient
                        .describeDatasetExportJob(describeDatasetExportJobRequest)
                        .datasetExportJob();

                status = datasetExportJob.status();
                System.out.println("Export job status: " + status);

                if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                    return status;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetExportJoba Referência AWS SDK for Java 2.x da API.

Criar um grupo de conjuntos de dados

O exemplo de código a seguir mostra como criar um grupo de conjuntos de dados do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createDatasetGroup(PersonalizeClient personalizeClient,
String datasetGroupName) {

       try {
           CreateDatasetGroupRequest createDatasetGroupRequest =
CreateDatasetGroupRequest.builder()
                   .name(datasetGroupName)
                   .build();
           return
personalizeClient.createDatasetGroup(createDatasetGroupRequest).datasetGroupArn();
       } catch (PersonalizeException e) {
           System.out.println(e.awsErrorDetails().errorMessage());
       }
       return "";
   }
```

Criar um grupo de conjunto de dados de domínio.

```
   public static String createDomainDatasetGroup(PersonalizeClient
personalizeClient,
           String datasetGroupName,
           String domain) {
```

```
        try {
            CreateDatasetGroupRequest createDatasetGroupRequest =
CreateDatasetGroupRequest.builder()
                    .name(datasetGroupName)
                    .domain(domain)
                    .build();
            return
personalizeClient.createDatasetGroup(createDatasetGroupRequest).datasetGroupArn();
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetGroupa Referência AWS SDK for Java 2.x da API.

Criar um trabalho de importação de conjunto de dados

O exemplo de código a seguir mostra como criar um trabalho de importação de conjunto de dados do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createPersonalizeDatasetImportJob(PersonalizeClient
personalizeClient,
            String jobName,
            String datasetArn,
            String s3BucketPath,
            String roleArn) {

        long waitInMilliseconds = 60 * 1000;
        String status;
```

```
        String datasetImportJobArn;

        try {
            DataSource importDataSource = DataSource.builder()
                    .dataLocation(s3BucketPath)
                    .build();

            CreateDatasetImportJobRequest createDatasetImportJobRequest =
CreateDatasetImportJobRequest.builder()
                    .datasetArn(datasetArn)
                    .dataSource(importDataSource)
                    .jobName(jobName)
                    .roleArn(roleArn)
                    .build();

            datasetImportJobArn =
personalizeClient.createDatasetImportJob(createDatasetImportJobRequest)
                    .datasetImportJobArn();
            DescribeDatasetImportJobRequest describeDatasetImportJobRequest =
DescribeDatasetImportJobRequest.builder()
                    .datasetImportJobArn(datasetImportJobArn)
                    .build();

            long maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            while (Instant.now().getEpochSecond() < maxTime) {

                DatasetImportJob datasetImportJob = personalizeClient
                        .describeDatasetImportJob(describeDatasetImportJobRequest)
                        .datasetImportJob();

                status = datasetImportJob.status();
                System.out.println("Dataset import job status: " + status);

                if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return datasetImportJobArn;
```

```
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateDatasetImportJoba Referência AWS SDK for Java 2.x da API.

Criar um esquema de domínio

O exemplo de código a seguir mostra como criar um esquema de domínio do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createDomainSchema(PersonalizeClient personalizeClient,
String schemaName, String domain,
            String filePath) {

        String schema = null;
        try {
            schema = new String(Files.readAllBytes(Paths.get(filePath)));
        } catch (IOException e) {
            System.out.println(e.getMessage());
        }

        try {
            CreateSchemaRequest createSchemaRequest = CreateSchemaRequest.builder()
                    .name(schemaName)
                    .domain(domain)
                    .schema(schema)
                    .build();
```

```
            String schemaArn =
personalizeClient.createSchema(createSchemaRequest).schemaArn();

            System.out.println("Schema arn: " + schemaArn);

            return schemaArn;

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for Java 2.x da API.

Criar um filtro

O exemplo de código a seguir mostra como criar um filtro do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createFilter(PersonalizeClient personalizeClient,
            String filterName,
            String datasetGroupArn,
            String filterExpression) {
        try {
            CreateFilterRequest request = CreateFilterRequest.builder()
                    .name(filterName)
                    .datasetGroupArn(datasetGroupArn)
                    .filterExpression(filterExpression)
                    .build();
```

```
            return personalizeClient.createFilter(request).filterArn();
        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateFiltera Referência AWS SDK for Java 2.x da API.

Criar um recomendador

O exemplo de código a seguir mostra como criar um recomendador do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createRecommender(PersonalizeClient personalizeClient,
            String name,
            String datasetGroupArn,
            String recipeArn) {

        long maxTime = 0;
        long waitInMilliseconds = 30 * 1000; // 30 seconds
        String recommenderStatus = "";

        try {
            CreateRecommenderRequest createRecommenderRequest =
CreateRecommenderRequest.builder()
                    .datasetGroupArn(datasetGroupArn)
                    .name(name)
                    .recipeArn(recipeArn)
                    .build();

            CreateRecommenderResponse recommenderResponse = personalizeClient
                    .createRecommender(createRecommenderRequest);
```

```
            String recommenderArn = recommenderResponse.recommenderArn();
            System.out.println("The recommender ARN is " + recommenderArn);

            DescribeRecommenderRequest describeRecommenderRequest =
DescribeRecommenderRequest.builder()
                    .recommenderArn(recommenderArn)
                    .build();

            maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

            while (Instant.now().getEpochSecond() < maxTime) {

                recommenderStatus =
personalizeClient.describeRecommender(describeRecommenderRequest).recommender()
                        .status();
                System.out.println("Recommender status: " + recommenderStatus);

                if (recommenderStatus.equals("ACTIVE") ||
recommenderStatus.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return recommenderArn;

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateRecommendera Referência AWS SDK for Java 2.x da API.

Criar um esquema

O exemplo de código a seguir mostra como criar um esquema do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createSchema(PersonalizeClient personalizeClient, String
schemaName, String filePath) {

       String schema = null;
       try {
           schema = new String(Files.readAllBytes(Paths.get(filePath)));
       } catch (IOException e) {
           System.out.println(e.getMessage());
       }

       try {
           CreateSchemaRequest createSchemaRequest = CreateSchemaRequest.builder()
                   .name(schemaName)
                   .schema(schema)
                   .build();

           String schemaArn =
personalizeClient.createSchema(createSchemaRequest).schemaArn();

           System.out.println("Schema arn: " + schemaArn);

           return schemaArn;

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateSchemaa Referência AWS SDK for Java 2.x da API.

Criar uma solução

O exemplo de código a seguir mostra como criar uma solução do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalizeSolution(PersonalizeClient
personalizeClient,
           String datasetGroupArn,
           String solutionName,
           String recipeArn) {

       try {
           CreateSolutionRequest solutionRequest = CreateSolutionRequest.builder()
                   .name(solutionName)
                   .datasetGroupArn(datasetGroupArn)
                   .recipeArn(recipeArn)
                   .build();

           CreateSolutionResponse solutionResponse =
personalizeClient.createSolution(solutionRequest);
           return solutionResponse.solutionArn();

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateSolutiona Referência AWS SDK for Java 2.x da API.

Criar uma versão da solução

O exemplo de código a seguir mostra como criar uma solução do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createPersonalizeSolutionVersion(PersonalizeClient
personalizeClient, String solutionArn) {
       long maxTime = 0;
       long waitInMilliseconds = 30 * 1000; // 30 seconds
       String solutionStatus = "";
       String solutionVersionStatus = "";
       String solutionVersionArn = "";

       try {
           DescribeSolutionRequest describeSolutionRequest =
DescribeSolutionRequest.builder()
                   .solutionArn(solutionArn)
                   .build();

           maxTime = Instant.now().getEpochSecond() + 3 * 60 * 60;

           // Wait until solution is active.
           while (Instant.now().getEpochSecond() < maxTime) {

               solutionStatus =
personalizeClient.describeSolution(describeSolutionRequest).solution().status();
               System.out.println("Solution status: " + solutionStatus);

               if (solutionStatus.equals("ACTIVE") || solutionStatus.equals("CREATE
FAILED")) {
                   break;
               }
               try {
                   Thread.sleep(waitInMilliseconds);
               } catch (InterruptedException e) {
                   System.out.println(e.getMessage());
```

```
                }
            }

            if (solutionStatus.equals("ACTIVE")) {

                CreateSolutionVersionRequest createSolutionVersionRequest =
CreateSolutionVersionRequest.builder()
                        .solutionArn(solutionArn)
                        .build();

                CreateSolutionVersionResponse createSolutionVersionResponse =
personalizeClient
                        .createSolutionVersion(createSolutionVersionRequest);
                solutionVersionArn =
createSolutionVersionResponse.solutionVersionArn();

                System.out.println("Solution version ARN: " + solutionVersionArn);

                DescribeSolutionVersionRequest describeSolutionVersionRequest =
DescribeSolutionVersionRequest.builder()
                        .solutionVersionArn(solutionVersionArn)
                        .build();

                while (Instant.now().getEpochSecond() < maxTime) {

                    solutionVersionStatus =
personalizeClient.describeSolutionVersion(describeSolutionVersionRequest)
                            .solutionVersion().status();
                    System.out.println("Solution version status: " +
solutionVersionStatus);

                    if (solutionVersionStatus.equals("ACTIVE") ||
solutionVersionStatus.equals("CREATE FAILED")) {
                        break;
                    }
                    try {
                        Thread.sleep(waitInMilliseconds);
                    } catch (InterruptedException e) {
                        System.out.println(e.getMessage());
                    }
                }
                return solutionVersionArn;
            }
        } catch (PersonalizeException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateSolutionVersiona Referência AWS SDK for Java 2.x da API.

Criar um rastreador de eventos

O exemplo de código a seguir mostra como criar um rastreador de eventos do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createEventTracker(PersonalizeClient personalizeClient,
String eventTrackerName,
            String datasetGroupArn) {

        String eventTrackerId = "";
        String eventTrackerArn;
        long maxTime = 3 * 60 * 60; // 3 hours
        long waitInMilliseconds = 20 * 1000; // 20 seconds
        String status;

        try {

            CreateEventTrackerRequest createEventTrackerRequest =
CreateEventTrackerRequest.builder()
                    .name(eventTrackerName)
                    .datasetGroupArn(datasetGroupArn)
                    .build();

            CreateEventTrackerResponse createEventTrackerResponse =
personalizeClient
```

```
                    .createEventTracker(createEventTrackerRequest);

            eventTrackerArn = createEventTrackerResponse.eventTrackerArn();
            eventTrackerId = createEventTrackerResponse.trackingId();
            System.out.println("Event tracker ARN: " + eventTrackerArn);
            System.out.println("Event tracker ID: " + eventTrackerId);

            maxTime = Instant.now().getEpochSecond() + maxTime;

            DescribeEventTrackerRequest describeRequest =
DescribeEventTrackerRequest.builder()
                    .eventTrackerArn(eventTrackerArn)
                    .build();

            while (Instant.now().getEpochSecond() < maxTime) {

                status =
personalizeClient.describeEventTracker(describeRequest).eventTracker().status();
                System.out.println("EventTracker status: " + status);

                if (status.equals("ACTIVE") || status.equals("CREATE FAILED")) {
                    break;
                }
                try {
                    Thread.sleep(waitInMilliseconds);
                } catch (InterruptedException e) {
                    System.out.println(e.getMessage());
                }
            }
            return eventTrackerId;
        } catch (PersonalizeException e) {
            System.out.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return eventTrackerId;
    }
```

- Para obter detalhes da API, consulte CreateEventTrackera Referência AWS SDK for Java 2.x da API.

Excluir uma campanha

O exemplo de código a seguir mostra como excluir uma campanha no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteSpecificCampaign(PersonalizeClient personalizeClient,
String campaignArn) {

       try {
           DeleteCampaignRequest campaignRequest = DeleteCampaignRequest.builder()
                   .campaignArn(campaignArn)
                   .build();

           personalizeClient.deleteCampaign(campaignRequest);

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteCampaigna Referência AWS SDK for Java 2.x da API.

Excluir uma solução

O exemplo de código a seguir mostra como excluir uma solução no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteGivenSolution(PersonalizeClient personalizeClient,
String solutionArn) {

       try {
           DeleteSolutionRequest solutionRequest = DeleteSolutionRequest.builder()
                   .solutionArn(solutionArn)
                   .build();

           personalizeClient.deleteSolution(solutionRequest);
           System.out.println("Done");

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteSolutiona Referência AWS SDK for Java 2.x da API.

Excluir um rastreador de eventos

O exemplo de código a seguir mostra como excluir um rastreador de eventos no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteEventTracker(PersonalizeClient personalizeClient,
String eventTrackerArn) {
       try {
           DeleteEventTrackerRequest deleteEventTrackerRequest =
DeleteEventTrackerRequest.builder()
                   .eventTrackerArn(eventTrackerArn)
                   .build();

           int status =
personalizeClient.deleteEventTracker(deleteEventTrackerRequest).sdkHttpResponse().statusCod

           System.out.println("Status code:" + status);

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte DeleteEventTrackera Referência AWS SDK for Java 2.x da API.

Descrever uma campanha

O exemplo de código a seguir mostra como descrever uma campanha no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeSpecificCampaign(PersonalizeClient personalizeClient,
String campaignArn) {

       try {
           DescribeCampaignRequest campaignRequest =
DescribeCampaignRequest.builder()
```

```
                    .campaignArn(campaignArn)
                    .build();

            DescribeCampaignResponse campaignResponse =
personalizeClient.describeCampaign(campaignRequest);
            Campaign myCampaign = campaignResponse.campaign();
            System.out.println("The Campaign name is " + myCampaign.name());
            System.out.println("The Campaign status is " + myCampaign.status());

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeCampaigna Referência AWS SDK for Java 2.x da API.

Descrever uma fórmula

O exemplo de código a seguir mostra como descrever uma fórmula no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeSpecificRecipe(PersonalizeClient personalizeClient,
String recipeArn) {

        try {
            DescribeRecipeRequest recipeRequest = DescribeRecipeRequest.builder()
                    .recipeArn(recipeArn)
                    .build();

            DescribeRecipeResponse recipeResponse =
personalizeClient.describeRecipe(recipeRequest);
```

```
            System.out.println("The recipe name is " +
recipeResponse.recipe().name());

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeRecipea Referência AWS SDK for Java 2.x da API.

Descreve uma solução

O exemplo de código a seguir mostra como descrever uma solução no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeSpecificSolution(PersonalizeClient personalizeClient,
String solutionArn) {

        try {
            DescribeSolutionRequest solutionRequest =
DescribeSolutionRequest.builder()
                    .solutionArn(solutionArn)
                    .build();

            DescribeSolutionResponse response =
personalizeClient.describeSolution(solutionRequest);
            System.out.println("The Solution name is " +
response.solution().name());

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeSolutiona Referência AWS SDK for Java 2.x da API.

Listar campanhas

O exemplo de código a seguir mostra como listar campanhas no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listAllCampaigns(PersonalizeClient personalizeClient, String
solutionArn) {

       try {
           ListCampaignsRequest campaignsRequest = ListCampaignsRequest.builder()
                   .maxResults(10)
                   .solutionArn(solutionArn)
                   .build();

           ListCampaignsResponse response =
personalizeClient.listCampaigns(campaignsRequest);
           List<CampaignSummary> campaigns = response.campaigns();
           for (CampaignSummary campaign : campaigns) {
               System.out.println("Campaign name is : " + campaign.name());
               System.out.println("Campaign ARN is : " + campaign.campaignArn());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
    }
```

- Para obter detalhes da API, consulte ListCampaignsa Referência AWS SDK for Java 2.x da API.

Listar grupos de conjunto de dados

O exemplo de código a seguir mostra como listar grupos de conjuntos de dados no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listDSGroups(PersonalizeClient personalizeClient) {

       try {
           ListDatasetGroupsRequest groupsRequest =
ListDatasetGroupsRequest.builder()
                   .maxResults(15)
                   .build();

           ListDatasetGroupsResponse groupsResponse =
personalizeClient.listDatasetGroups(groupsRequest);
           List<DatasetGroupSummary> groups = groupsResponse.datasetGroups();
           for (DatasetGroupSummary group : groups) {
               System.out.println("The DataSet name is : " + group.name());
               System.out.println("The DataSet ARN is : " +
group.datasetGroupArn());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListDatasetGroupsa Referência AWS SDK for Java 2.x da API.

Listar receitas

O exemplo de código a seguir mostra como listar fórmulas no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listAllRecipes(PersonalizeClient personalizeClient) {

        try {
            ListRecipesRequest recipesRequest = ListRecipesRequest.builder()
                    .maxResults(15)
                    .build();

            ListRecipesResponse response =
personalizeClient.listRecipes(recipesRequest);
            List<RecipeSummary> recipes = response.recipes();
            for (RecipeSummary recipe : recipes) {
                System.out.println("The recipe ARN is: " + recipe.recipeArn());
                System.out.println("The recipe name is: " + recipe.name());
            }

        } catch (PersonalizeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListRecipesa Referência AWS SDK for Java 2.x da API.

Listar soluções

O exemplo de código a seguir mostra como listar soluções no Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listAllSolutions(PersonalizeClient personalizeClient, String
datasetGroupArn) {

       try {
           ListSolutionsRequest solutionsRequest = ListSolutionsRequest.builder()
                   .maxResults(10)
                   .datasetGroupArn(datasetGroupArn)
                   .build();

           ListSolutionsResponse response =
personalizeClient.listSolutions(solutionsRequest);
           List<SolutionSummary> solutions = response.solutions();
           for (SolutionSummary solution : solutions) {
               System.out.println("The solution ARN is: " +
solution.solutionArn());
               System.out.println("The solution name is: " + solution.name());
           }

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListSolutionsa Referência AWS SDK for Java 2.x da API.

Atualizar uma campanha

O exemplo de código a seguir mostra como atualizar uma campanha do Amazon Personalize.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String updateCampaign(PersonalizeClient personalizeClient,
           String campaignArn,
           String solutionVersionArn,
           Integer minProvisionedTPS) {

       try {
           // build the updateCampaignRequest
           UpdateCampaignRequest updateCampaignRequest =
UpdateCampaignRequest.builder()
                   .campaignArn(campaignArn)
                   .solutionVersionArn(solutionVersionArn)
                   .minProvisionedTPS(minProvisionedTPS)
                   .build();

           // update the campaign
           personalizeClient.updateCampaign(updateCampaignRequest);

           DescribeCampaignRequest campaignRequest =
DescribeCampaignRequest.builder()
                   .campaignArn(campaignArn)
                   .build();

           DescribeCampaignResponse campaignResponse =
personalizeClient.describeCampaign(campaignRequest);
           Campaign updatedCampaign = campaignResponse.campaign();

           System.out.println("The Campaign status is " +
updatedCampaign.status());
           return updatedCampaign.status();

       } catch (PersonalizeException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
```

```
        return "";
    }
```

- Para obter detalhes da API, consulte UpdateCampaigna Referência AWS SDK for Java 2.x da API.

Exemplos de eventos do Amazon Personalize usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Personalize Events.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Importar dados de eventos de interação em tempo real

O exemplo de código a seguir mostra como importar dados de eventos de interação em tempo real para o Amazon Personalize Events.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static int putItems(PersonalizeEventsClient personalizeEventsClient,
                        String datasetArn,
                        String item1Id,
                        String item1PropertyName,
                        String item1PropertyValue,
                        String item2Id,
                        String item2PropertyName,
                        String item2PropertyValue) {

                int responseCode = 0;
                ArrayList<Item> items = new ArrayList<>();

                try {
                        Item item1 = Item.builder()
                                        .itemId(item1Id)
                                        .properties(String.format("{\"%1$s\": \"%2$s
\"}",
                                                        item1PropertyName,
 item1PropertyValue))
                                        .build();

                        items.add(item1);

                        Item item2 = Item.builder()
                                        .itemId(item2Id)
                                        .properties(String.format("{\"%1$s\": \"%2$s
\"}",
                                                        item2PropertyName,
 item2PropertyValue))
                                        .build();

                        items.add(item2);

                        PutItemsRequest putItemsRequest = PutItemsRequest.builder()
                                        .datasetArn(datasetArn)
                                        .items(items)
                                        .build();

                        responseCode =
 personalizeEventsClient.putItems(putItemsRequest).sdkHttpResponse().statusCode();
                        System.out.println("Response code: " + responseCode);
                        return responseCode;
```

```
                } catch (PersonalizeEventsException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
                }
                return responseCode;
        }
```

- Para obter detalhes da API, consulte PutEventsa Referência AWS SDK for Java 2.x da API.

Importar incrementalmente um usuário

O exemplo de código a seguir mostra como importar incrementalmente um usuário para eventos do Amazon Personalize Events.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        public static int putUsers(PersonalizeEventsClient personalizeEventsClient,
                        String datasetArn,
                        String user1Id,
                        String user1PropertyName,
                        String user1PropertyValue,
                        String user2Id,
                        String user2PropertyName,
                        String user2PropertyValue) {

                int responseCode = 0;
                ArrayList<User> users = new ArrayList<>();

                try {
                        User user1 = User.builder()
                                        .userId(user1Id)
                                        .properties(String.format("{\"%1$s\": \"%2$s
\"}",
                                                        user1PropertyName,
 user1PropertyValue))
```

```
                                        .build();

                        users.add(user1);

                        User user2 = User.builder()
                                        .userId(user2Id)
                                        .properties(String.format("{\"%1$s\": \"%2$s
\"}",
                                                        user2PropertyName,
 user2PropertyValue))
                                        .build();

                        users.add(user2);

                        PutUsersRequest putUsersRequest = PutUsersRequest.builder()
                                        .datasetArn(datasetArn)
                                        .users(users)
                                        .build();

                        responseCode =
 personalizeEventsClient.putUsers(putUsersRequest).sdkHttpResponse().statusCode();
                        System.out.println("Response code: " + responseCode);
                        return responseCode;

                } catch (PersonalizeEventsException e) {
                        System.out.println(e.awsErrorDetails().errorMessage());
                }
                return responseCode;
        }
```

- Para obter detalhes da API, consulte PutUsersa Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Personalize Runtime usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Personalize Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter recomendações (grupo de conjunto de dados personalizados)

O exemplo de código a seguir mostra como obter recomendações de classificação do Amazon Personalize Runtime.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static List<PredictedItem> getRankedRecs(PersonalizeRuntimeClient
personalizeRuntimeClient,
           String campaignArn,
           String userId,
           ArrayList<String> items) {

       try {
           GetPersonalizedRankingRequest rankingRecommendationsRequest =
GetPersonalizedRankingRequest.builder()
                   .campaignArn(campaignArn)
                   .userId(userId)
                   .inputList(items)
                   .build();

           GetPersonalizedRankingResponse recommendationsResponse =
personalizeRuntimeClient
                   .getPersonalizedRanking(rankingRecommendationsRequest);
```

```
            List<PredictedItem> rankedItems =
recommendationsResponse.personalizedRanking();
            int rank = 1;
            for (PredictedItem item : rankedItems) {
                System.out.println("Item ranked at position " + rank + " details");
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
                System.out.println("----------------------------------------------");
                rank++;
            }
            return rankedItems;
        } catch (PersonalizeRuntimeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
```

- Para obter detalhes da API, consulte GetPersonalizedRankinga Referência AWS SDK for Java 2.x da API.

Receber recomendações de um recomendador (grupo de conjunto de dados de domínio)

O exemplo de código a seguir mostra como obter recomendações de runtime do Amazon Personalize Runtime.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter uma lista de itens recomendados.

```
    public static void getRecs(PersonalizeRuntimeClient personalizeRuntimeClient,
String campaignArn, String userId) {

        try {
```

```
            GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                    .campaignArn(campaignArn)
                    .numResults(20)
                    .userId(userId)
                    .build();

            GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
                    .getRecommendations(recommendationsRequest);
            List<PredictedItem> items = recommendationsResponse.itemList();
            for (PredictedItem item : items) {
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
            }

        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Obter uma lista de itens recomendados de um recomendador criado em um grupo de conjuntos de dados de domínio.

```
    public static void getRecs(PersonalizeRuntimeClient personalizeRuntimeClient,
String recommenderArn,
            String userId) {

        try {
            GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                    .recommenderArn(recommenderArn)
                    .numResults(20)
                    .userId(userId)
                    .build();

            GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
                    .getRecommendations(recommendationsRequest);
            List<PredictedItem> items = recommendationsResponse.itemList();
```

```
            for (PredictedItem item : items) {
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
            }
        } catch (AwsServiceException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

Usar um filtro ao solicitar recomendações.

```
    public static void getFilteredRecs(PersonalizeRuntimeClient
personalizeRuntimeClient,
            String campaignArn,
            String userId,
            String filterArn,
            String parameter1Name,
            String parameter1Value1,
            String parameter1Value2,
            String parameter2Name,
            String parameter2Value) {

        try {

            Map<String, String> filterValues = new HashMap<>();

            filterValues.put(parameter1Name, String.format("\"%1$s\",\"%2$s\"",
                    parameter1Value1, parameter1Value2));
            filterValues.put(parameter2Name, String.format("\"%1$s\"",
                    parameter2Value));

            GetRecommendationsRequest recommendationsRequest =
GetRecommendationsRequest.builder()
                    .campaignArn(campaignArn)
                    .numResults(20)
                    .userId(userId)
                    .filterArn(filterArn)
                    .filterValues(filterValues)
                    .build();
```

```
            GetRecommendationsResponse recommendationsResponse =
personalizeRuntimeClient
                    .getRecommendations(recommendationsRequest);
            List<PredictedItem> items = recommendationsResponse.itemList();

            for (PredictedItem item : items) {
                System.out.println("Item Id is : " + item.itemId());
                System.out.println("Item score is : " + item.score());
            }
        } catch (PersonalizeRuntimeException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte GetRecommendationsa Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Pinpoint usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma campanha

O exemplo de código a seguir mostra como criar uma campanha.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma campanha.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CampaignResponse;
import software.amazon.awssdk.services.pinpoint.model.Message;
import software.amazon.awssdk.services.pinpoint.model.Schedule;
import software.amazon.awssdk.services.pinpoint.model.Action;
import software.amazon.awssdk.services.pinpoint.model.MessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.WriteCampaignRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateCampaignResponse;
import software.amazon.awssdk.services.pinpoint.model.CreateCampaignRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateCampaign {
    public static void main(String[] args) {

        final String usage = """

                Usage:   <appId> <segmentId>
```

```
                Where:
                  appId - The ID of the application to create the campaign in.
                  segmentId - The ID of the segment to create the campaign from.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String segmentId = args[1];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createPinCampaign(pinpoint, appId, segmentId);
        pinpoint.close();
    }

    public static void createPinCampaign(PinpointClient pinpoint, String appId,
String segmentId) {
        CampaignResponse result = createCampaign(pinpoint, appId, segmentId);
        System.out.println("Campaign " + result.name() + " created.");
        System.out.println(result.description());
    }

    public static CampaignResponse createCampaign(PinpointClient client, String
appID, String segmentID) {

        try {
            Schedule schedule = Schedule.builder()
                    .startTime("IMMEDIATE")
                    .build();

            Message defaultMessage = Message.builder()
                    .action(Action.OPEN_APP)
                    .body("My message body.")
                    .title("My message title.")
                    .build();

            MessageConfiguration messageConfiguration =
MessageConfiguration.builder()
                    .defaultMessage(defaultMessage)
```

```
                    .build();

            WriteCampaignRequest request = WriteCampaignRequest.builder()
                    .description("My description")
                    .schedule(schedule)
                    .name("MyCampaign")
                    .segmentId(segmentID)
                    .messageConfiguration(messageConfiguration)
                    .build();

            CreateCampaignResponse result =
 client.createCampaign(CreateCampaignRequest.builder()
                    .applicationId(appID)
                    .writeCampaignRequest(request).build());

            System.out.println("Campaign ID: " + result.campaignResponse().id());
            return result.campaignResponse();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return null;
    }
}
```

- Para obter detalhes da API, consulte CreateCampaigna Referência AWS SDK for Java 2.x da API.

Criar um segmento

O exemplo de código a seguir mostra como criar um segmento.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.AttributeDimension;
import software.amazon.awssdk.services.pinpoint.model.SegmentResponse;
import software.amazon.awssdk.services.pinpoint.model.AttributeType;
import software.amazon.awssdk.services.pinpoint.model.RecencyDimension;
import software.amazon.awssdk.services.pinpoint.model.SegmentBehaviors;
import software.amazon.awssdk.services.pinpoint.model.SegmentDemographics;
import software.amazon.awssdk.services.pinpoint.model.SegmentLocation;
import software.amazon.awssdk.services.pinpoint.model.SegmentDimensions;
import software.amazon.awssdk.services.pinpoint.model.WriteSegmentRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateSegmentRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateSegmentResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateSegment {
        public static void main(String[] args) {
                final String usage = """

                                Usage:   <appId>

                                Where:
                                  appId - The application ID to create a segment
 for.

                                """;

                if (args.length != 1) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String appId = args[0];
```

```
                PinpointClient pinpoint = PinpointClient.builder()
                                .region(Region.US_EAST_1)
                                .build();

                SegmentResponse result = createSegment(pinpoint, appId);
                System.out.println("Segment " + result.name() + " created.");
                System.out.println(result.segmentType());
                pinpoint.close();
        }

        public static SegmentResponse createSegment(PinpointClient client, String
appId) {
                try {
                        Map<String, AttributeDimension> segmentAttributes = new
HashMap<>();
                        segmentAttributes.put("Team", AttributeDimension.builder()
                                        .attributeType(AttributeType.INCLUSIVE)
                                        .values("Lakers")
                                        .build());

                        RecencyDimension recencyDimension =
RecencyDimension.builder()
                                        .duration("DAY_30")
                                        .recencyType("ACTIVE")
                                        .build();

                        SegmentBehaviors segmentBehaviors =
SegmentBehaviors.builder()
                                        .recency(recencyDimension)
                                        .build();

                        SegmentDemographics segmentDemographics =
SegmentDemographics
                                        .builder()
                                        .build();

                        SegmentLocation segmentLocation = SegmentLocation
                                        .builder()
                                        .build();

                        SegmentDimensions dimensions = SegmentDimensions
                                        .builder()
                                        .attributes(segmentAttributes)
                                        .behavior(segmentBehaviors)
```

```
                                        .demographic(segmentDemographics)
                                        .location(segmentLocation)
                                        .build();

                        WriteSegmentRequest writeSegmentRequest =
 WriteSegmentRequest.builder()
                                        .name("MySegment")
                                        .dimensions(dimensions)
                                        .build();

                        CreateSegmentRequest createSegmentRequest =
 CreateSegmentRequest.builder()
                                        .applicationId(appId)
                                        .writeSegmentRequest(writeSegmentRequest)
                                        .build();

                        CreateSegmentResponse createSegmentResult =
 client.createSegment(createSegmentRequest);
                        System.out.println("Segment ID: " +
 createSegmentResult.segmentResponse().id());
                        System.out.println("Done");
                        return createSegmentResult.segmentResponse();

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
                return null;
        }
}
```

- Para obter detalhes da API, consulte CreateSegmenta Referência AWS SDK for Java 2.x da API.

Cria uma aplicação

O exemplo de código a seguir mostra como criar uma aplicação.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CreateAppRequest;
import software.amazon.awssdk.services.pinpoint.model.CreateAppResponse;
import software.amazon.awssdk.services.pinpoint.model.CreateApplicationRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateApp {
    public static void main(String[] args) {
        final String usage = """

                 Usage:  <appName>

                 Where:
                  appName - The name of the application to create.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
        String appName = args[0];
        System.out.println("Creating an application with name: " + appName);

        PinpointClient pinpoint = PinpointClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        String appID = createApplication(pinpoint, appName);
        System.out.println("App ID is: " + appID);
        pinpoint.close();
    }

    public static String createApplication(PinpointClient pinpoint, String appName)
 {
        try {
            CreateApplicationRequest appRequest = CreateApplicationRequest.builder()
                    .name(appName)
                    .build();

            CreateAppRequest request = CreateAppRequest.builder()
                    .createApplicationRequest(appRequest)
                    .build();

            CreateAppResponse result = pinpoint.createApp(request);
            return result.applicationResponse().id();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateApp a Referência AWS SDK for Java 2.x da API.

Deleta o aplicativo

O exemplo de código a seguir mostra como excluir uma aplicação.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir uma aplicação.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DeleteAppRequest;
import software.amazon.awssdk.services.pinpoint.model.DeleteAppResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteApp {
    public static void main(String[] args) {
        final String usage = """

                Usage:  <appId>

                Where:
                 appId - The ID of the application to delete.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        System.out.println("Deleting an application with ID: " + appId);
        PinpointClient pinpoint = PinpointClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        deletePinApp(pinpoint, appId);
        System.out.println("Done");
        pinpoint.close();
    }

    public static void deletePinApp(PinpointClient pinpoint, String appId) {
        try {
            DeleteAppRequest appRequest = DeleteAppRequest.builder()
                    .applicationId(appId)
                    .build();

            DeleteAppResponse result = pinpoint.deleteApp(appRequest);
            String appName = result.applicationResponse().name();
            System.out.println("Application " + appName + " has been deleted.");

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteApp a Referência AWS SDK for Java 2.x da API.

Excluir um endpoint

O exemplo de código a seguir mostra como excluir um endpoint.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um endpoint

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DeleteEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.DeleteEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteEndpoint {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appName> <endpointId >

                Where:
                  appId - The id of the application to delete.
                  endpointId - The id of the endpoint to delete.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String endpointId = args[1];
        System.out.println("Deleting an endpoint with id: " + endpointId);
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deletePinEncpoint(pinpoint, appId, endpointId);
        pinpoint.close();
    }

    public static void deletePinEncpoint(PinpointClient pinpoint, String appId,
 String endpointId) {
```

```
        try {
            DeleteEndpointRequest appRequest = DeleteEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .build();

            DeleteEndpointResponse result = pinpoint.deleteEndpoint(appRequest);
            String id = result.endpointResponse().id();
            System.out.println("The deleted endpoint id  " + id);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte DeleteEndpointa Referência AWS SDK for Java 2.x da API.

Exportar um endpoint

Os exemplos a seguir mostram como exportar um endpoint.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exporte um endpoint.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.ExportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.CreateExportJobRequest;
```

```
import software.amazon.awssdk.services.pinpoint.model.CreateExportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.GetExportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.GetExportJobRequest;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Request;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Response;
import software.amazon.awssdk.services.s3.model.S3Object;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;
import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Date;
import java.util.List;
import java.util.concurrent.TimeUnit;
import java.util.stream.Collectors;

/**
 * To run this code example, you need to create an AWS Identity and Access
 * Management (IAM) role with the correct policy as described in this
 * documentation:
 * https://docs.aws.amazon.com/pinpoint/latest/developerguide/audience-data-
export.html
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class ExportEndpoints {
    public static void main(String[] args) {
        final String usage = """

                This program performs the following steps:

                1. Exports the endpoints to an Amazon S3 bucket.
                2. Downloads the exported endpoints files from Amazon S3.
```

```
                3. Parses the endpoints files to obtain the endpoint IDs and prints
them.
                Usage: ExportEndpoints <applicationId> <s3BucketName>
<iamExportRoleArn> <path>

                Where:
                  applicationId - The ID of the Amazon Pinpoint application that has
the endpoint.
                  s3BucketName - The name of the Amazon S3 bucket to export the JSON
file to.\s
                  iamExportRoleArn - The ARN of an IAM role that grants Amazon
Pinpoint write permissions to the S3 bucket.  path - The path where the files
downloaded from the Amazon S3 bucket are written (for example, C:/AWS/).
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String applicationId = args[0];
        String s3BucketName = args[1];
        String iamExportRoleArn = args[2];
        String path = args[3];
        System.out.println("Deleting an application with ID: " + applicationId);

        Region region = Region.US_EAST_1;
        PinpointClient pinpoint = PinpointClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        exportAllEndpoints(pinpoint, s3Client, applicationId, s3BucketName, path,
iamExportRoleArn);
        pinpoint.close();
        s3Client.close();
    }

    public static void exportAllEndpoints(PinpointClient pinpoint,
            S3Client s3Client,
            String applicationId,
```

```
            String s3BucketName,
            String path,
            String iamExportRoleArn) {

        try {
            List<String> objectKeys = exportEndpointsToS3(pinpoint, s3Client,
 s3BucketName, iamExportRoleArn,
                    applicationId);
            List<String> endpointFileKeys = objectKeys.stream().filter(o ->
 o.endsWith(".gz"))
                    .collect(Collectors.toList());
            downloadFromS3(s3Client, path, s3BucketName, endpointFileKeys);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static List<String> exportEndpointsToS3(PinpointClient pinpoint, S3Client
 s3Client, String s3BucketName,
            String iamExportRoleArn, String applicationId) {

        SimpleDateFormat dateFormat = new SimpleDateFormat("yyyy-MM-dd-
HH_mm:ss.SSS_z");
        String endpointsKeyPrefix = "exports/" + applicationId + "_" +
 dateFormat.format(new Date());
        String s3UrlPrefix = "s3://" + s3BucketName + "/" + endpointsKeyPrefix +
 "/";
        List<String> objectKeys = new ArrayList<>();
        String key;

        try {
            // Defines the export job that Amazon Pinpoint runs.
            ExportJobRequest jobRequest = ExportJobRequest.builder()
                    .roleArn(iamExportRoleArn)
                    .s3UrlPrefix(s3UrlPrefix)
                    .build();

            CreateExportJobRequest exportJobRequest =
 CreateExportJobRequest.builder()
                    .applicationId(applicationId)
                    .exportJobRequest(jobRequest)
                    .build();
```

```
            System.out.format("Exporting endpoints from Amazon Pinpoint application
%s to Amazon S3 " +
                    "bucket %s . . .\n", applicationId, s3BucketName);

            CreateExportJobResponse exportResult =
pinpoint.createExportJob(exportJobRequest);
            String jobId = exportResult.exportJobResponse().id();
            System.out.println(jobId);
            printExportJobStatus(pinpoint, applicationId, jobId);

            ListObjectsV2Request v2Request = ListObjectsV2Request.builder()
                    .bucket(s3BucketName)
                    .prefix(endpointsKeyPrefix)
                    .build();

            // Create a list of object keys.
            ListObjectsV2Response v2Response = s3Client.listObjectsV2(v2Request);
            List<S3Object> objects = v2Response.contents();
            for (S3Object object : objects) {
                key = object.key();
                objectKeys.add(key);
            }

            return objectKeys;

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static void printExportJobStatus(PinpointClient pinpointClient,
            String applicationId,
            String jobId) {

        GetExportJobResponse getExportJobResult;
        String status;

        try {
            // Checks the job status until the job completes or fails.
            GetExportJobRequest exportJobRequest = GetExportJobRequest.builder()
                    .jobId(jobId)
```

```
                    .applicationId(applicationId)
                    .build();

            do {
                getExportJobResult = pinpointClient.getExportJob(exportJobRequest);
                status =
getExportJobResult.exportJobResponse().jobStatus().toString().toUpperCase();
                System.out.format("Export job %s . . .\n", status);
                TimeUnit.SECONDS.sleep(3);

            } while (!status.equals("COMPLETED") && !status.equals("FAILED"));

            if (status.equals("COMPLETED")) {
                System.out.println("Finished exporting endpoints.");
            } else {
                System.err.println("Failed to export endpoints.");
                System.exit(1);
            }

        } catch (PinpointException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Download files from an Amazon S3 bucket and write them to the path location.
    public static void downloadFromS3(S3Client s3Client, String path, String
s3BucketName, List<String> objectKeys) {

        String newPath;
        try {
            for (String key : objectKeys) {
                GetObjectRequest objectRequest = GetObjectRequest.builder()
                        .bucket(s3BucketName)
                        .key(key)
                        .build();

                ResponseBytes<GetObjectResponse> objectBytes =
s3Client.getObjectAsBytes(objectRequest);
                byte[] data = objectBytes.asByteArray();

                // Write the data to a local file.
                String fileSuffix = new
SimpleDateFormat("yyyyMMddHHmmss").format(new Date());
```

```
                newPath = path + fileSuffix + ".gz";
                File myFile = new File(newPath);
                OutputStream os = new FileOutputStream(myFile);
                os.write(data);
            }
            System.out.println("Download finished.");

        } catch (S3Exception | NullPointerException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateExportJoba Referência AWS SDK for Java 2.x da API.

Obter endpoints

O exemplo de código a seguir mostra como obter endpoints.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import com.google.gson.FieldNamingPolicy;
import com.google.gson.Gson;
import com.google.gson.GsonBuilder;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointRequest;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class LookUpEndpoint {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId> <endpoint>

                Where:
                  appId - The ID of the application to delete.
                  endpoint - The ID of the endpoint.\s
                  """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String endpoint = args[1];
        System.out.println("Looking up an endpoint point with ID: " + endpoint);
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        lookupPinpointEndpoint(pinpoint, appId, endpoint);
        pinpoint.close();
    }

    public static void lookupPinpointEndpoint(PinpointClient pinpoint, String appId,
 String endpoint) {
        try {
            GetEndpointRequest appRequest = GetEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpoint)
                    .build();

            GetEndpointResponse result = pinpoint.getEndpoint(appRequest);
            EndpointResponse endResponse = result.endpointResponse();
```

```
            // Uses the Google Gson library to pretty print the endpoint JSON.
            Gson gson = new GsonBuilder()
                    .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                    .setPrettyPrinting()
                    .create();

            String endpointJson = gson.toJson(endResponse);
            System.out.println(endpointJson);

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Done");
    }
}
```

- Para obter detalhes da API, consulte GetEndpointa Referência AWS SDK for Java 2.x da API.

Importar um segmento

O exemplo de código a seguir mostra como importar um segmento.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importe um segmento.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.CreateImportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.ImportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.ImportJobRequest;
import software.amazon.awssdk.services.pinpoint.model.Format;
import software.amazon.awssdk.services.pinpoint.model.CreateImportJobResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ImportSegment {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId> <bucket> <key> <roleArn>\s

                Where:
                  appId - The application ID to create a segment for.
                  bucket - The name of the Amazon S3 bucket that contains the
 segment definitons.
                  key - The key of the S3 object.
                  roleArn - ARN of the role that allows Amazon Pinpoint to
 access S3. You need to set trust management for this to work. See https://
docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements_principal.html
                  """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
        String bucket = args[1];
        String key = args[2];
        String roleArn = args[3];

        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        ImportJobResponse response = createImportSegment(pinpoint, appId, bucket,
 key, roleArn);
        System.out.println("Import job for " + bucket + " submitted.");
        System.out.println("See application " + response.applicationId() + " for
 import job status.");
```

```
        System.out.println("See application " + response.jobStatus() + " for import
 job status.");
        pinpoint.close();
    }

    public static ImportJobResponse createImportSegment(PinpointClient client,
            String appId,
            String bucket,
            String key,
            String roleArn) {

        try {
            ImportJobRequest importRequest = ImportJobRequest.builder()
                    .defineSegment(true)
                    .registerEndpoints(true)
                    .roleArn(roleArn)
                    .format(Format.JSON)
                    .s3Url("s3://" + bucket + "/" + key)
                    .build();

            CreateImportJobRequest jobRequest = CreateImportJobRequest.builder()
                    .importJobRequest(importRequest)
                    .applicationId(appId)
                    .build();

            CreateImportJobResponse jobResponse =
 client.createImportJob(jobRequest);
            return jobResponse.importJobResponse();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte CreateImportJoba Referência AWS SDK for Java 2.x da API.

Listar endpoints

O exemplo de código a seguir mostra como listar endpoints.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetUserEndpointsRequest;
import software.amazon.awssdk.services.pinpoint.model.GetUserEndpointsResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListEndpointIds {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <applicationId> <userId>

                Where:
                   applicationId - The ID of the Amazon Pinpoint application that
 has the endpoint.
                   userId - The user id applicable to the endpoints""";

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String applicationId = args[0];
        String userId = args[1];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllEndpoints(pinpoint, applicationId, userId);
        pinpoint.close();
    }

    public static void listAllEndpoints(PinpointClient pinpoint,
            String applicationId,
            String userId) {

        try {
            GetUserEndpointsRequest endpointsRequest =
 GetUserEndpointsRequest.builder()
                    .userId(userId)
                    .applicationId(applicationId)
                    .build();

            GetUserEndpointsResponse response =
 pinpoint.getUserEndpoints(endpointsRequest);
            List<EndpointResponse> endpoints = response.endpointsResponse().item();

            // Display the results.
            for (EndpointResponse endpoint : endpoints) {
                System.out.println("The channel type is: " +
 endpoint.channelType());
                System.out.println("The address is  " + endpoint.address());
            }

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetUserEndpointsa Referência AWS SDK for Java 2.x da API.

Listar segmentos

O exemplo de código a seguir mostra como listar segmentos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste segmentos.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.GetSegmentsRequest;
import software.amazon.awssdk.services.pinpoint.model.GetSegmentsResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.SegmentResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListSegments {
    public static void main(String[] args) {
        final String usage = """

                Usage:   <appId>

                Where:
                  appId - The ID of the application that contains a segment.

                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String appId = args[0];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSegs(pinpoint, appId);
        pinpoint.close();
    }

    public static void listSegs(PinpointClient pinpoint, String appId) {
        try {
            GetSegmentsRequest request = GetSegmentsRequest.builder()
                    .applicationId(appId)
                    .build();

            GetSegmentsResponse response = pinpoint.getSegments(request);
            List<SegmentResponse> segments = response.segmentsResponse().item();
            for (SegmentResponse segment : segments) {
                System.out
                        .println("Segement " + segment.id() + " " + segment.name() +
 " " + segment.lastModifiedDate());
            }

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSegmentsa Referência AWS SDK for Java 2.x da API.

Envie e-mails e mensagens de texto

O exemplo de código a seguir mostra como enviar e-mail e mensagens de texto com o Amazon Pinpoint.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.SimpleEmailPart;
import software.amazon.awssdk.services.pinpoint.model.SimpleEmail;
import software.amazon.awssdk.services.pinpoint.model.EmailMessage;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpointemail.PinpointEmailClient;
import software.amazon.awssdk.services.pinpointemail.model.Body;
import software.amazon.awssdk.services.pinpointemail.model.Content;
import software.amazon.awssdk.services.pinpointemail.model.Destination;
import software.amazon.awssdk.services.pinpointemail.model.EmailContent;
import software.amazon.awssdk.services.pinpointemail.model.Message;
import software.amazon.awssdk.services.pinpointemail.model.SendEmailRequest;

import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SendEmailMessage {

        // The character encoding the you want to use for the subject line and
```

```
        // message body of the email.
        public static String charset = "UTF-8";

    // The body of the email for recipients whose email clients support HTML
content.
    static final String body = """
        Amazon Pinpoint test (AWS SDK for Java 2.x)

        This email was sent through the Amazon Pinpoint Email API using the AWS SDK
for Java 2.x

        """;

        public static void main(String[] args) {
                final String usage = """

                                Usage:    <subject> <appId> <senderAddress>
<toAddress>

            Where:
               subject - The email subject to use.
               senderAddress - The from address. This address has to be verified in
Amazon Pinpoint in the region you're using to send email\s
               toAddress - The to address. This address has to be verified in Amazon
Pinpoint in the region you're using to send email\s
            """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String subject = args[0];
        String senderAddress = args[1];
        String toAddress = args[2];
        System.out.println("Sending a message");
        PinpointEmailClient pinpoint = PinpointEmailClient.builder()
            .region(Region.US_EAST_1)
            .build();

        sendEmail(pinpoint, subject, senderAddress, toAddress);
        System.out.println("Email was sent");
        pinpoint.close();
    }
```

```
    public static void sendEmail(PinpointEmailClient pinpointEmailClient, String
 subject, String senderAddress, String toAddress) {
        try {
            Content content = Content.builder()
                .data(body)
                .build();

            Body messageBody = Body.builder()
                .text(content)
                .build();

            Message message = Message.builder()
                .body(messageBody)
                .subject(Content.builder().data(subject).build())
                .build();

            Destination destination = Destination.builder()
                .toAddresses(toAddress)
                .build();

            EmailContent emailContent = EmailContent.builder()
                .simple(message)
                .build();

            SendEmailRequest sendEmailRequest = SendEmailRequest.builder()
                .fromEmailAddress(senderAddress)
                .destination(destination)
                .content(emailContent)
                .build();

            pinpointEmailClient.sendEmail(sendEmailRequest);
            System.out.println("Message Sent");

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Envie uma mensagem de e-mail com cópia para outros destinatários.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import  software.amazon.awssdk.services.pinpointemail.PinpointEmailClient;
import software.amazon.awssdk.services.pinpointemail.model.Body;
import software.amazon.awssdk.services.pinpointemail.model.Content;
import software.amazon.awssdk.services.pinpointemail.model.Destination;
import software.amazon.awssdk.services.pinpointemail.model.EmailContent;
import software.amazon.awssdk.services.pinpointemail.model.Message;
import software.amazon.awssdk.services.pinpointemail.model.SendEmailRequest;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SendEmailMessageCC {

    // The body of the email.
    static final String body = """
        Amazon Pinpoint test (AWS SDK for Java 2.x)

        This email was sent through the Amazon Pinpoint Email API using the AWS SDK
 for Java 2.x

        """;
    public static void main(String[] args) {
        final String usage = """

            Usage:    <subject> <senderAddress> <toAddress> <ccAddress>

            Where:
               subject - The email subject to use.
               senderAddress - The from address. This address has to be verified in
 Amazon Pinpoint in the region you're using to send email\s
               toAddress - The to address. This address has to be verified in Amazon
 Pinpoint in the region you're using to send email\s
               ccAddress - The CC address.
            """;
```

```
        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String subject = args[0];
        String senderAddress = args[1];
        String toAddress = args[2];
        String ccAddress = args[3];

        System.out.println("Sending a message");
        PinpointEmailClient pinpoint = PinpointEmailClient.builder()
            .region(Region.US_EAST_1)
            .build();

        ArrayList<String> ccList = new ArrayList<>();
        ccList.add(ccAddress);
        sendEmail(pinpoint, subject, senderAddress, toAddress, ccList);
        pinpoint.close();
    }

    public static void sendEmail(PinpointEmailClient pinpointEmailClient, String
subject, String senderAddress, String toAddress, ArrayList<String> ccAddresses) {
        try {
            Content content = Content.builder()
                .data(body)
                .build();

            Body messageBody = Body.builder()
                .text(content)
                .build();

            Message message = Message.builder()
                .body(messageBody)
                .subject(Content.builder().data(subject).build())
                .build();

            Destination destination = Destination.builder()
                .toAddresses(toAddress)
                .ccAddresses(ccAddresses)
                .build();

            EmailContent emailContent = EmailContent.builder()
                .simple(message)
```

```
                .build();

            SendEmailRequest sendEmailRequest = SendEmailRequest.builder()
                .fromEmailAddress(senderAddress)
                .destination(destination)
                .content(emailContent)
                .build();

            pinpointEmailClient.sendEmail(sendEmailRequest);
            System.out.println("Message Sent");

        } catch (PinpointException e) {
            // Handle exception
            e.printStackTrace();
        }
    }
}
```

Envie uma mensagem SMS.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.SMSMessage;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesResponse;
import software.amazon.awssdk.services.pinpoint.model.MessageResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class SendMessage {

        // The type of SMS message that you want to send. If you plan to send
        // time-sensitive content, specify TRANSACTIONAL. If you plan to send
        // marketing-related content, specify PROMOTIONAL.
        public static String messageType = "TRANSACTIONAL";

        // The registered keyword associated with the originating short code.
        public static String registeredKeyword = "myKeyword";

        // The sender ID to use when sending the message. Support for sender ID
        // varies by country or region. For more information, see
        // https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html
        public static String senderId = "MySenderID";

        public static void main(String[] args) {
                final String usage = """

                                Usage:   <message> <appId> <originationNumber>
 <destinationNumber>\s

                                Where:
                                  message - The body of the message to send.
                                  appId - The Amazon Pinpoint project/application ID
 to use when you send this message.
                                  originationNumber - The phone number or short code
 that you specify has to be associated with your Amazon Pinpoint account. For best
 results, specify long codes in E.164 format (for example, +1-555-555-5654).
                                  destinationNumber - The recipient's phone number.
 For best results, you should specify the phone number in E.164 format (for example,
 +1-555-555-5654).\s
                                  """;

                if (args.length != 4) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String message = args[0];
                String appId = args[1];
                String originationNumber = args[2];
                String destinationNumber = args[3];
                System.out.println("Sending a message");
```

```
                PinpointClient pinpoint = PinpointClient.builder()
                                .region(Region.US_EAST_1)
                                .build();

                sendSMSMessage(pinpoint, message, appId, originationNumber,
destinationNumber);
                pinpoint.close();
        }

        public static void sendSMSMessage(PinpointClient pinpoint, String message,
String appId,
                        String originationNumber,
                        String destinationNumber) {
                try {
                        Map<String, AddressConfiguration> addressMap = new
HashMap<String, AddressConfiguration>();
                        AddressConfiguration addConfig =
AddressConfiguration.builder()
                                        .channelType(ChannelType.SMS)
                                        .build();

                        addressMap.put(destinationNumber, addConfig);
                        SMSMessage smsMessage = SMSMessage.builder()
                                        .body(message)
                                        .messageType(messageType)
                                        .originationNumber(originationNumber)
                                        .senderId(senderId)
                                        .keyword(registeredKeyword)
                                        .build();

                        // Create a DirectMessageConfiguration object.
                        DirectMessageConfiguration direct =
DirectMessageConfiguration.builder()
                                        .smsMessage(smsMessage)
                                        .build();

                        MessageRequest msgReq = MessageRequest.builder()
                                        .addresses(addressMap)
                                        .messageConfiguration(direct)
                                        .build();

                        // create a SendMessagesRequest object
                        SendMessagesRequest request = SendMessagesRequest.builder()
                                        .applicationId(appId)
```

```
                                        .messageRequest(msgReq)
                                        .build();

                        SendMessagesResponse response =
 pinpoint.sendMessages(request);
                        MessageResponse msg1 = response.messageResponse();
                        Map map1 = msg1.result();

                        // Write out the result of sendMessage.
                        map1.forEach((k, v) -> System.out.println((k + ":" + v)));

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

Envie mensagens SMS em massa.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.DirectMessageConfiguration;
import software.amazon.awssdk.services.pinpoint.model.SMSMessage;
import software.amazon.awssdk.services.pinpoint.model.AddressConfiguration;
import software.amazon.awssdk.services.pinpoint.model.ChannelType;
import software.amazon.awssdk.services.pinpoint.model.MessageRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesRequest;
import software.amazon.awssdk.services.pinpoint.model.SendMessagesResponse;
import software.amazon.awssdk.services.pinpoint.model.MessageResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class SendMessageBatch {

        // The type of SMS message that you want to send. If you plan to send
        // time-sensitive content, specify TRANSACTIONAL. If you plan to send
        // marketing-related content, specify PROMOTIONAL.
        public static String messageType = "TRANSACTIONAL";

        // The registered keyword associated with the originating short code.
        public static String registeredKeyword = "myKeyword";

        // The sender ID to use when sending the message. Support for sender ID
        // varies by country or region. For more information, see
        // https://docs.aws.amazon.com/pinpoint/latest/userguide/channels-sms-
countries.html
        public static String senderId = "MySenderID";

        public static void main(String[] args) {
                final String usage = """

                                Usage:   <message> <appId> <originationNumber>
 <destinationNumber> <destinationNumber1>\s

                                Where:
                                  message - The body of the message to send.
                                  appId - The Amazon Pinpoint project/application ID
 to use when you send this message.
                                  originationNumber - The phone number or short code
 that you specify has to be associated with your Amazon Pinpoint account. For best
 results, specify long codes in E.164 format (for example, +1-555-555-5654).
                                  destinationNumber - The recipient's phone number.
 For best results, you should specify the phone number in E.164 format (for example,
 +1-555-555-5654).
                                  destinationNumber1 - The second recipient's phone
 number.  For best results, you should specify the phone number in E.164 format (for
 example, +1-555-555-5654).\s
                                  """;

                if (args.length != 5) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String message = args[0];
                String appId = args[1];
```

```
                String originationNumber = args[2];
                String destinationNumber = args[3];
                String destinationNumber1 = args[4];
                System.out.println("Sending a message");
                PinpointClient pinpoint = PinpointClient.builder()
                                .region(Region.US_EAST_1)
                                .build();

                sendSMSMessage(pinpoint, message, appId, originationNumber,
destinationNumber, destinationNumber1);
                pinpoint.close();
        }

        public static void sendSMSMessage(PinpointClient pinpoint, String message,
String appId,
                        String originationNumber,
                        String destinationNumber, String destinationNumber1) {
                try {
                        Map<String, AddressConfiguration> addressMap = new
HashMap<String, AddressConfiguration>();
                        AddressConfiguration addConfig =
AddressConfiguration.builder()
                                        .channelType(ChannelType.SMS)
                                        .build();

                        // Add an entry to the Map object for each number to whom
you want to send a
                        // message.
                        addressMap.put(destinationNumber, addConfig);
                        addressMap.put(destinationNumber1, addConfig);
                        SMSMessage smsMessage = SMSMessage.builder()
                                        .body(message)
                                        .messageType(messageType)
                                        .originationNumber(originationNumber)
                                        .senderId(senderId)
                                        .keyword(registeredKeyword)
                                        .build();

                        // Create a DirectMessageConfiguration object.
                        DirectMessageConfiguration direct =
DirectMessageConfiguration.builder()
                                        .smsMessage(smsMessage)
                                        .build();
```

```
                        MessageRequest msgReq = MessageRequest.builder()
                                        .addresses(addressMap)
                                        .messageConfiguration(direct)
                                        .build();

                        // Create a SendMessagesRequest object.
                        SendMessagesRequest request = SendMessagesRequest.builder()
                                        .applicationId(appId)
                                        .messageRequest(msgReq)
                                        .build();

                        SendMessagesResponse response =
 pinpoint.sendMessages(request);
                        MessageResponse msg1 = response.messageResponse();
                        Map map1 = msg1.result();

                        // Write out the result of sendMessage.
                        map1.forEach((k, v) -> System.out.println((k + ":" + v)));

                } catch (PinpointException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendMessagesa Referência AWS SDK for Java 2.x da API.

Atualizar um endpoint

O exemplo de código a seguir mostra como atualizar um endpoint.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.EndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.EndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointRequest;
import software.amazon.awssdk.services.pinpoint.model.GetEndpointResponse;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.EndpointDemographic;
import software.amazon.awssdk.services.pinpoint.model.EndpointLocation;
import software.amazon.awssdk.services.pinpoint.model.EndpointUser;
import java.text.DateFormat;
import java.text.SimpleDateFormat;
import java.util.List;
import java.util.UUID;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.Map;
import java.util.Date;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateEndpoint {
    public static void main(String[] args) {
        final String usage = """

                Usage:  <appId>

                Where:
                  appId - The ID of the application to create an endpoint for.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        String appId = args[0];
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        EndpointResponse response = createEndpoint(pinpoint, appId);
        System.out.println("Got Endpoint: " + response.id());
        pinpoint.close();
    }

    public static EndpointResponse createEndpoint(PinpointClient client, String
appId) {
        String endpointId = UUID.randomUUID().toString();
        System.out.println("Endpoint ID: " + endpointId);

        try {
            EndpointRequest endpointRequest = createEndpointRequestData();
            UpdateEndpointRequest updateEndpointRequest =
UpdateEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .endpointRequest(endpointRequest)
                    .build();

            UpdateEndpointResponse updateEndpointResponse =
client.updateEndpoint(updateEndpointRequest);
            System.out.println("Update Endpoint Response: " +
updateEndpointResponse.messageBody());

            GetEndpointRequest getEndpointRequest = GetEndpointRequest.builder()
                    .applicationId(appId)
                    .endpointId(endpointId)
                    .build();

            GetEndpointResponse getEndpointResponse =
client.getEndpoint(getEndpointRequest);
            System.out.println(getEndpointResponse.endpointResponse().address());

System.out.println(getEndpointResponse.endpointResponse().channelType());

System.out.println(getEndpointResponse.endpointResponse().applicationId());
```

```
System.out.println(getEndpointResponse.endpointResponse().endpointStatus());
            System.out.println(getEndpointResponse.endpointResponse().requestId());
            System.out.println(getEndpointResponse.endpointResponse().user());

            return getEndpointResponse.endpointResponse();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static EndpointRequest createEndpointRequestData() {
        try {
            List<String> favoriteTeams = new ArrayList<>();
            favoriteTeams.add("Lakers");
            favoriteTeams.add("Warriors");
            HashMap<String, List<String>> customAttributes = new HashMap<>();
            customAttributes.put("team", favoriteTeams);

            EndpointDemographic demographic = EndpointDemographic.builder()
                    .appVersion("1.0")
                    .make("apple")
                    .model("iPhone")
                    .modelVersion("7")
                    .platform("ios")
                    .platformVersion("10.1.1")
                    .timezone("America/Los_Angeles")
                    .build();

            EndpointLocation location = EndpointLocation.builder()
                    .city("Los Angeles")
                    .country("US")
                    .latitude(34.0)
                    .longitude(-118.2)
                    .postalCode("90068")
                    .region("CA")
                    .build();

            Map<String, Double> metrics = new HashMap<>();
            metrics.put("health", 100.00);
            metrics.put("luck", 75.00);
```

```
            EndpointUser user = EndpointUser.builder()
                    .userId(UUID.randomUUID().toString())
                    .build();

            DateFormat df = new SimpleDateFormat("yyyy-MM-dd'T'HH:mm'Z'"); // Quoted
 "Z" to indicate UTC, no timezone
                                                                            // offset
            String nowAsISO = df.format(new Date());

            return EndpointRequest.builder()
                    .address(UUID.randomUUID().toString())
                    .attributes(customAttributes)
                    .channelType("APNS")
                    .demographic(demographic)
                    .effectiveDate(nowAsISO)
                    .location(location)
                    .metrics(metrics)
                    .optOut("NONE")
                    .requestId(UUID.randomUUID().toString())
                    .user(user)
                    .build();

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte UpdateEndpointa Referência AWS SDK for Java 2.x da API.

Atualizar canais

O exemplo de código a seguir mostra como atualizar canais.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpoint.PinpointClient;
import software.amazon.awssdk.services.pinpoint.model.SMSChannelResponse;
import software.amazon.awssdk.services.pinpoint.model.GetSmsChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.PinpointException;
import software.amazon.awssdk.services.pinpoint.model.SMSChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateSmsChannelRequest;
import software.amazon.awssdk.services.pinpoint.model.UpdateSmsChannelResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateChannel {
    public static void main(String[] args) {
        final String usage = """

                Usage: CreateChannel <appId>

                Where:
                  appId - The name of the application whose channel is updated.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String appId = args[0];
```

```
        PinpointClient pinpoint = PinpointClient.builder()
                .region(Region.US_EAST_1)
                .build();

        SMSChannelResponse getResponse = getSMSChannel(pinpoint, appId);
        toggleSmsChannel(pinpoint, appId, getResponse);
        pinpoint.close();
    }

    private static SMSChannelResponse getSMSChannel(PinpointClient client, String
appId) {
        try {
            GetSmsChannelRequest request = GetSmsChannelRequest.builder()
                    .applicationId(appId)
                    .build();

            SMSChannelResponse response =
client.getSmsChannel(request).smsChannelResponse();
            System.out.println("Channel state is " + response.enabled());
            return response;

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    private static void toggleSmsChannel(PinpointClient client, String appId,
SMSChannelResponse getResponse) {
        boolean enabled = !getResponse.enabled();
        try {
            SMSChannelRequest request = SMSChannelRequest.builder()
                    .enabled(enabled)
                    .build();

            UpdateSmsChannelRequest updateRequest =
UpdateSmsChannelRequest.builder()
                    .smsChannelRequest(request)
                    .applicationId(appId)
                    .build();

            UpdateSmsChannelResponse result =
client.updateSmsChannel(updateRequest);
```

```
            System.out.println("Channel state: " +
 result.smsChannelResponse().enabled());

        } catch (PinpointException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSmsChannela Referência AWS SDK for Java 2.x da API.

Exemplos da API SMS and Voice do Amazon Pinpoint usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com a API de voz e SMS do Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar uma mensagem de voz com Amazon Pinpoint SMS e Voice API

O exemplo de código a seguir mostra como enviar uma mensagem de voz com a API SMS and Voice do Amazon Pinpoint.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.client.config.ClientOverrideConfiguration;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.pinpointsmsvoice.PinpointSmsVoiceClient;
import software.amazon.awssdk.services.pinpointsmsvoice.model.SSMLMessageType;
import software.amazon.awssdk.services.pinpointsmsvoice.model.VoiceMessageContent;
import
 software.amazon.awssdk.services.pinpointsmsvoice.model.SendVoiceMessageRequest;
import
 software.amazon.awssdk.services.pinpointsmsvoice.model.PinpointSmsVoiceException;
import java.util.ArrayList;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SendVoiceMessage {

        // The Amazon Polly voice that you want to use to send the message. For a
 list
        // of voices, see https://docs.aws.amazon.com/polly/latest/dg/voicelist.html
        static final String voiceName = "Matthew";

        // The language to use when sending the message. For a list of supported
        // languages, see
        // https://docs.aws.amazon.com/polly/latest/dg/SupportedLanguage.html
        static final String languageCode = "en-US";
```

```
        // The content of the message. This example uses SSML to customize and
control
        // certain aspects of the message, such as by adding pauses and changing
        // phonation. The message can't contain any line breaks.
        static final String ssmlMessage = "<speak>This is a test message sent from "
                        + "<emphasis>Amazon Pinpoint</emphasis> "
                        + "using the <break strength='weak'/>AWS "
                        + "SDK for Java. "
                        + "<amazon:effect phonation='soft'>Thank "
                        + "you for listening.</amazon:effect></speak>";

        public static void main(String[] args) {

                final String usage = """

                                Usage:   <originationNumber> <destinationNumber>\s

                                Where:
                                  originationNumber - The phone number or short code
that you specify has to be associated with your Amazon Pinpoint account. For best
results, specify long codes in E.164 format (for example, +1-555-555-5654).
                                  destinationNumber - The recipient's phone number.
For best results, you should specify the phone number in E.164 format (for example,
+1-555-555-5654).\s
                                  """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String originationNumber = args[0];
                String destinationNumber = args[1];
                System.out.println("Sending a voice message");

                // Set the content type to application/json.
                List<String> listVal = new ArrayList<>();
                listVal.add("application/json");
                Map<String, List<String>> values = new HashMap<>();
                values.put("Content-Type", listVal);

                ClientOverrideConfiguration config2 =
ClientOverrideConfiguration.builder()
                                .headers(values)
```

```
                                .build();

                PinpointSmsVoiceClient client = PinpointSmsVoiceClient.builder()
                                .overrideConfiguration(config2)
                                .region(Region.US_EAST_1)
                                .build();

                sendVoiceMsg(client, originationNumber, destinationNumber);
                client.close();
        }

        public static void sendVoiceMsg(PinpointSmsVoiceClient client, String
 originationNumber,
                        String destinationNumber) {
                try {
                        SSMLMessageType ssmlMessageType = SSMLMessageType.builder()
                                        .languageCode(languageCode)
                                        .text(ssmlMessage)
                                        .voiceId(voiceName)
                                        .build();

                        VoiceMessageContent content = VoiceMessageContent.builder()
                                        .ssmlMessage(ssmlMessageType)
                                        .build();

                        SendVoiceMessageRequest voiceMessageRequest =
 SendVoiceMessageRequest.builder()
                                        .destinationPhoneNumber(destinationNumber)
                                        .originationPhoneNumber(originationNumber)
                                        .content(content)
                                        .build();

                        client.sendVoiceMessage(voiceMessageRequest);
                        System.out.println("The message was sent successfully.");

                } catch (PinpointSmsVoiceException e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendVoiceMessagea Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Polly usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Polly.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter vozes disponíveis para síntese

O exemplo de código a seguir mostra como obter vozes disponíveis para síntese do Amazon Polly.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.DescribeVoicesRequest;
import software.amazon.awssdk.services.polly.model.DescribeVoicesResponse;
import software.amazon.awssdk.services.polly.model.PollyException;
```

```
import software.amazon.awssdk.services.polly.model.Voice;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeVoicesSample {
    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();

        describeVoice(polly);
        polly.close();
    }

    public static void describeVoice(PollyClient polly) {
        try {
            DescribeVoicesRequest voicesRequest = DescribeVoicesRequest.builder()
                    .languageCode("en-US")
                    .build();

            DescribeVoicesResponse enUsVoicesResult =
 polly.describeVoices(voicesRequest);
            List<Voice> voices = enUsVoicesResult.voices();
            for (Voice myVoice : voices) {
                System.out.println("The ID of the voice is " + myVoice.id());
                System.out.println("The gender of the voice is " +
 myVoice.gender());
            }

        } catch (PollyException e) {
            System.err.println("Exception caught: " + e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for Java 2.x da API.

Listar léxicos de pronúncia

O exemplo de código a seguir mostra como listar os léxicos de pronúncia do Amazon Polly.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.ListLexiconsResponse;
import software.amazon.awssdk.services.polly.model.ListLexiconsRequest;
import software.amazon.awssdk.services.polly.model.LexiconDescription;
import software.amazon.awssdk.services.polly.model.PollyException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListLexicons {
    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();

        listLexicons(polly);
        polly.close();
    }

    public static void listLexicons(PollyClient client) {
```

```
        try {
            ListLexiconsRequest listLexiconsRequest = ListLexiconsRequest.builder()
                    .build();

            ListLexiconsResponse listLexiconsResult =
 client.listLexicons(listLexiconsRequest);
            List<LexiconDescription> lexiconDescription =
 listLexiconsResult.lexicons();
            for (LexiconDescription lexDescription : lexiconDescription) {
                System.out.println("The name of the Lexicon is " +
 lexDescription.name());
            }

        } catch (PollyException e) {
            System.err.println("Exception caught: " + e);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for Java 2.x da API.

Sintetizar fala a partir de texto

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import javazoom.jl.decoder.JavaLayerException;
import software.amazon.awssdk.core.ResponseInputStream;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.polly.PollyClient;
import software.amazon.awssdk.services.polly.model.DescribeVoicesRequest;
import software.amazon.awssdk.services.polly.model.Voice;
import software.amazon.awssdk.services.polly.model.DescribeVoicesResponse;
```

```
import software.amazon.awssdk.services.polly.model.OutputFormat;
import software.amazon.awssdk.services.polly.model.PollyException;
import software.amazon.awssdk.services.polly.model.SynthesizeSpeechRequest;
import software.amazon.awssdk.services.polly.model.SynthesizeSpeechResponse;
import java.io.IOException;
import java.io.InputStream;
import javazoom.jl.player.advanced.AdvancedPlayer;
import javazoom.jl.player.advanced.PlaybackEvent;
import javazoom.jl.player.advanced.PlaybackListener;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PollyDemo {
    private static final String SAMPLE = "Congratulations. You have successfully
 built this working demo " +
            " of Amazon Polly in Java Version 2. Have fun building voice enabled
 apps with Amazon Polly (that's me!), and always "
            +
            " look at the AWS website for tips and tricks on using Amazon Polly and
 other great services from AWS";

    public static void main(String args[]) {
        PollyClient polly = PollyClient.builder()
                .region(Region.US_WEST_2)
                .build();

        talkPolly(polly);
        polly.close();
    }

    public static void talkPolly(PollyClient polly) {
        try {
            DescribeVoicesRequest describeVoiceRequest =
 DescribeVoicesRequest.builder()
                    .engine("standard")
                    .build();
```

```
            DescribeVoicesResponse describeVoicesResult =
 polly.describeVoices(describeVoiceRequest);
            Voice voice = describeVoicesResult.voices().stream()
                    .filter(v -> v.name().equals("Joanna"))
                    .findFirst()
                    .orElseThrow(() -> new RuntimeException("Voice not found"));
            InputStream stream = synthesize(polly, SAMPLE, voice, OutputFormat.MP3);
            AdvancedPlayer player = new AdvancedPlayer(stream,

 javazoom.jl.player.FactoryRegistry.systemRegistry().createAudioDevice());
            player.setPlayBackListener(new PlaybackListener() {
                public void playbackStarted(PlaybackEvent evt) {
                    System.out.println("Playback started");
                    System.out.println(SAMPLE);
                }

                public void playbackFinished(PlaybackEvent evt) {
                    System.out.println("Playback finished");
                }
            });

            // play it!
            player.play();

        } catch (PollyException | JavaLayerException | IOException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static InputStream synthesize(PollyClient polly, String text, Voice
 voice, OutputFormat format)
            throws IOException {
        SynthesizeSpeechRequest synthReq = SynthesizeSpeechRequest.builder()
                .text(text)
                .voiceId(voice.id())
                .outputFormat(format)
                .build();

        ResponseInputStream<SynthesizeSpeechResponse> synthRes =
 polly.synthesizeSpeech(synthReq);
        return synthRes;
    }
}
```

- Para obter detalhes da API, consulte SynthesizeSpeecha Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon RDS usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon RDS

O exemplo de código a seguir mostra como começar a usar o Amazon RDS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.RdsException;
import java.util.List;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeDBInstances {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeInstances(rdsClient);
        rdsClient.close();
    }

    public static void describeInstances(RdsClient rdsClient) {
        try {
            DescribeDbInstancesResponse response = rdsClient.describeDBInstances();
            List<DBInstance> instanceList = response.dbInstances();
            for (DBInstance instance : instanceList) {
                System.out.println("Instance ARN is: " + instance.dbInstanceArn());
                System.out.println("The Engine is " + instance.engine());
                System.out.println("Connection endpoint is" +
 instance.endpoint().address());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

O exemplo de código a seguir mostra como criar uma instância do Amazon RDS DB e aguardar até que se torne disponível.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import com.google.gson.Gson;
import
 software.amazon.awssdk.auth.credentials.EnvironmentVariableCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;

import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For more details, see:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 *
 */

public class CreateDBInstance {
    public static long sleepTime = 20;

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <dbName> <secretName>

                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
                    dbName - The database name.\s
                    secretName - The name of the AWS Secrets Manager secret that
 contains the database credentials."
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        String dbName = args[1];
        String secretName = args[2];
        Gson gson = new Gson();
        User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
 User.class);
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();
```

```
        createDatabaseInstance(rdsClient, dbInstanceIdentifier, dbName,
user.getUsername(), user.getPassword());
        waitForInstanceReady(rdsClient, dbInstanceIdentifier);
        rdsClient.close();
    }

    private static SecretsManagerClient getSecretClient() {
        Region region = Region.US_WEST_2;
        return SecretsManagerClient.builder()
                .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
                .build();
    }

    private static String getSecretValues(String secretName) {
        SecretsManagerClient secretClient = getSecretClient();
        GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                .secretId(secretName)
                .build();

        GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
        return valueResponse.secretString();
    }

    public static void createDatabaseInstance(RdsClient rdsClient,
            String dbInstanceIdentifier,
            String dbName,
            String userName,
            String userPassword) {

        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .allocatedStorage(100)
                    .dbName(dbName)
                    .engine("mysql")
                    .dbInstanceClass("db.m4.large")
                    .engineVersion("8.0")
                    .storageType("standard")
                    .masterUsername(userName)
                    .masterUserPassword(userPassword)
```

```
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Waits until the database instance is available.
    public static void waitForInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            // Loop until the cluster is ready.
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
                    if (instanceReadyStr.contains("available"))
                        instanceReady = true;
                    else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database instance is available!");

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
```

```
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for Java 2.x.

Criar um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void createDBParameterGroup(RdsClient rdsClient, String
dbGroupName, String dbParameterGroupFamily) {
       try {
           CreateDbParameterGroupRequest groupRequest =
CreateDbParameterGroupRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .description("Created by using the AWS SDK for Java")
                   .build();

           CreateDbParameterGroupResponse response =
rdsClient.createDBParameterGroup(groupRequest);
           System.out.println("The group name is " +
response.dbParameterGroup().dbParameterGroupName());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte CreateDB ParameterGroup na Referência AWS SDK for Java 2.x da API.

Criar um snapshot de uma instância de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de uma instância do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Create an Amazon RDS snapshot.
   public static void createSnapshot(RdsClient rdsClient, String
dbInstanceIdentifier, String dbSnapshotIdentifier) {
       try {
           CreateDbSnapshotRequest snapshotRequest =
CreateDbSnapshotRequest.builder()
                   .dbInstanceIdentifier(dbInstanceIdentifier)
                   .dbSnapshotIdentifier(dbSnapshotIdentifier)
                   .build();

           CreateDbSnapshotResponse response =
rdsClient.createDBSnapshot(snapshotRequest);
           System.out.println("The Snapshot id is " +
response.dbSnapshot().dbiResourceId());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Java 2.x.

Criar um token de autenticação

O exemplo de código a seguir mostra como criar um token de autenticação para autenticação do IAM.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use a RdsUtilitiesclasse para gerar um token de autenticação.

```
public class GenerateRDSAuthToken {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <masterUsername>

                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
                    masterUsername - The master user name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        String masterUsername = args[1];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        String token = getAuthToken(rdsClient, dbInstanceIdentifier,
 masterUsername);
        System.out.println("The token response is " + token);
    }
```

```
    public static String getAuthToken(RdsClient rdsClient, String
 dbInstanceIdentifier, String masterUsername) {

        RdsUtilities utilities = rdsClient.utilities();
        try {
            GenerateAuthenticationTokenRequest tokenRequest =
 GenerateAuthenticationTokenRequest.builder()
                    .credentialsProvider(ProfileCredentialsProvider.create())
                    .username(masterUsername)
                    .port(3306)
                    .hostname(dbInstanceIdentifier)
                    .build();

            return utilities.generateAuthenticationToken(tokenRequest);

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte GenerateRds AuthToken na Referência AWS SDK for Java 2.x da API.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
```

```
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier>\s

                Where:
                    dbInstanceIdentifier - The database instance identifier\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        rdsClient.close();
    }

    public static void deleteDatabaseInstance(RdsClient rdsClient, String
 dbInstanceIdentifier) {
        try {
            DeleteDbInstanceRequest deleteDbInstanceRequest =
 DeleteDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
```

```
                    .deleteAutomatedBackups(true)
                    .skipFinalSnapshot(true)
                    .build();

            DeleteDbInstanceResponse response =
 rdsClient.deleteDBInstance(deleteDbInstanceRequest);
            System.out.print("The status of the database is " +
 response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for Java 2.x.

Excluir um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Delete the parameter group after database has been deleted.
    // An exception is thrown if you attempt to delete the para group while database
    // exists.
    public static void deleteParaGroup(RdsClient rdsClient, String dbGroupName,
 String dbARN)
            throws InterruptedException {
        try {
            boolean isDataDel = false;
            boolean didFind;
            String instanceARN;
```

```
            // Make sure that the database has been deleted.
            while (!isDataDel) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
                List<DBInstance> instanceList = response.dbInstances();
                int listSize = instanceList.size();
                didFind = false;
                int index = 1;
                for (DBInstance instance : instanceList) {
                    instanceARN = instance.dbInstanceArn();
                    if (instanceARN.compareTo(dbARN) == 0) {
                        System.out.println(dbARN + " still exists");
                        didFind = true;
                    }
                    if ((index == listSize) && (!didFind)) {
                        // Went through the entire list and did not find the
database ARN.
                        isDataDel = true;
                    }
                    Thread.sleep(sleepTime * 1000);
                    index++;
                }
            }

            // Delete the para group.
            DeleteDbParameterGroupRequest parameterGroupRequest =
DeleteDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .build();

            rdsClient.deleteDBParameterGroup(parameterGroupRequest);
            System.out.println(dbGroupName + " was deleted.");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DeleteDB ParameterGroup na AWS SDK for Java 2.x Referência da API.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.RdsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeDBInstances {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        describeInstances(rdsClient);
        rdsClient.close();
    }

    public static void describeInstances(RdsClient rdsClient) {
        try {
            DescribeDbInstancesResponse response = rdsClient.describeDBInstances();
            List<DBInstance> instanceList = response.dbInstances();
```

```
            for (DBInstance instance : instanceList) {
                System.out.println("Instance ARN is: " + instance.dbInstanceArn());
                System.out.println("The Engine is " + instance.engine());
                System.out.println("Connection endpoint is" +
 instance.endpoint().address());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Java 2.x.

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeDbParameterGroups(RdsClient rdsClient, String
 dbGroupName) {
        try {
            DescribeDbParameterGroupsRequest groupsRequest =
 DescribeDbParameterGroupsRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .maxRecords(20)
                    .build();

            DescribeDbParameterGroupsResponse response =
 rdsClient.describeDBParameterGroups(groupsRequest);
            List<DBParameterGroup> groups = response.dbParameterGroups();
```

```
            for (DBParameterGroup group : groups) {
                System.out.println("The group name is " +
group.dbParameterGroupName());
                System.out.println("The group description is " +
group.description());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Java 2.x da API.

Descrever as versões de mecanismo de banco de dados

O exemplo de código a seguir mostra como descrever as versões de mecanismo de banco de dados do Amazon RDS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void describeDBEngines(RdsClient rdsClient) {
        try {
            DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .defaultOnly(true)
                    .engine("mysql")
                    .maxRecords(20)
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
```

```
            List<DBEngineVersion> engines = response.dbEngineVersions();

            // Get all DBEngineVersion objects.
            for (DBEngineVersion engineOb : engines) {
                System.out.println("The name of the DB parameter group family for
the database engine is "
                        + engineOb.dbParameterGroupFamily());
                System.out.println("The name of the database engine " +
engineOb.engine());
                System.out.println("The version number of the database engine " +
engineOb.engineVersion());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions em Referência AWS SDK for Java 2.x da API.

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever opções para instâncias do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Get a list of allowed engine versions.
    public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
        try {
            DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .dbParameterGroupFamily(dbParameterGroupFamily)
```

```
                    .engine("mysql")
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
            List<DBEngineVersion> dbEngines = response.dbEngineVersions();
            for (DBEngineVersion dbEngine : dbEngines) {
                System.out.println("The engine version is " +
dbEngine.engineVersion());
                System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeOrderableDB InstanceOptions em Referência de AWS SDK for Java 2.x API.

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Retrieve parameters in the group.
    public static void describeDbParameters(RdsClient rdsClient, String dbGroupName,
int flag) {
        try {
            DescribeDbParametersRequest dbParameterGroupsRequest;
```

```
            if (flag == 0) {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbParametersResponse response =
rdsClient.describeDBParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") == 0)) {
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Java 2.x.

Modificar uma instância de banco de dados

O exemplo de código a seguir mostra como modificar uma instância do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.ModifyDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.ModifyDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ModifyDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier> <dbSnapshotIdentifier>\s
                Where:
                    dbInstanceIdentifier - The database instance identifier.\s
                    masterUserPassword - The updated password that corresponds to
 the master user name.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String dbInstanceIdentifier = args[0];
        String masterUserPassword = args[1];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        updateIntance(rdsClient, dbInstanceIdentifier, masterUserPassword);
        rdsClient.close();
    }

    public static void updateIntance(RdsClient rdsClient, String
 dbInstanceIdentifier, String masterUserPassword) {
        try {
            // For a demo - modify the DB instance by modifying the master password.
            ModifyDbInstanceRequest modifyDbInstanceRequest =
 ModifyDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .publiclyAccessible(true)
                    .masterUserPassword(masterUserPassword)
                    .build();

            ModifyDbInstanceResponse instanceResponse =
 rdsClient.modifyDBInstance(modifyDbInstanceRequest);
            System.out.print("The ARN of the modified database is: " +
 instanceResponse.dbInstance().dbInstanceArn());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte ModifyDBInstance na Referência da API do AWS SDK for Java 2.x.

Reinicializar uma instância de banco de dados

Os exemplos de código a seguir mostram como reinicializar uma instância de banco de dados do Amazon RDS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.RebootDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.RebootDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.RdsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class RebootDBInstance {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <dbInstanceIdentifier>\s

                Where:
                    dbInstanceIdentifier - The database instance identifier\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbInstanceIdentifier = args[0];
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
```

```
                .build();

        rebootInstance(rdsClient, dbInstanceIdentifier);
        rdsClient.close();
    }

    public static void rebootInstance(RdsClient rdsClient, String
 dbInstanceIdentifier) {
        try {
            RebootDbInstanceRequest rebootDbInstanceRequest =
 RebootDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            RebootDbInstanceResponse instanceResponse =
 rdsClient.rebootDBInstance(rebootDbInstanceRequest);
            System.out.print("The database " +
 instanceResponse.dbInstance().dbInstanceArn() + " was rebooted");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para ter detalhes da API, consulte RebootDBInstance na Referência da API do AWS SDK for Java 2.x.

Recuperar atributos

O exemplo de código a seguir mostra como recuperar atributos que pertencem a uma conta do Amazon RDS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.AccountQuota;
import software.amazon.awssdk.services.rds.model.RdsException;
import software.amazon.awssdk.services.rds.model.DescribeAccountAttributesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeAccountAttributes {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();

        getAccountAttributes(rdsClient);
        rdsClient.close();
    }

    public static void getAccountAttributes(RdsClient rdsClient) {
        try {
            DescribeAccountAttributesResponse response =
 rdsClient.describeAccountAttributes();
            List<AccountQuota> quotasList = response.accountQuotas();
            for (AccountQuota quotas : quotasList) {
                System.out.println("Name is: " + quotas.accountQuotaName());
                System.out.println("Max value is " + quotas.max());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeAccountAttributesa Referência AWS SDK for Java 2.x da API.

Atualizar os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como atualizar os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Modify auto_increment_offset and auto_increment_increment parameters.
    public static void modifyDBParas(RdsClient rdsClient, String dbGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
            paraList.add(parameter1);
            ModifyDbParameterGroupRequest groupRequest =
ModifyDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .parameters(paraList)
                    .build();

            ModifyDbParameterGroupResponse response =
rdsClient.modifyDBParameterGroup(groupRequest);
            System.out.println("The parameter group " +
response.dbParameterGroupName() + " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte ModifyDB ParameterGroup na Referência AWS SDK for Java 2.x da API.

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute várias operações.

```
import com.google.gson.Gson;
import
 software.amazon.awssdk.auth.credentials.EnvironmentVariableCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rds.RdsClient;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.CreateDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.CreateDbParameterGroupResponse;
import software.amazon.awssdk.services.rds.model.CreateDbSnapshotRequest;
import software.amazon.awssdk.services.rds.model.CreateDbSnapshotResponse;
import software.amazon.awssdk.services.rds.model.DBEngineVersion;
```

```
import software.amazon.awssdk.services.rds.model.DBInstance;
import software.amazon.awssdk.services.rds.model.DBParameterGroup;
import software.amazon.awssdk.services.rds.model.DBSnapshot;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbInstanceResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbEngineVersionsRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbEngineVersionsResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbInstancesResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbParameterGroupsResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbParametersResponse;
import software.amazon.awssdk.services.rds.model.DescribeDbSnapshotsRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbSnapshotsResponse;
import
 software.amazon.awssdk.services.rds.model.DescribeOrderableDbInstanceOptionsResponse;
import software.amazon.awssdk.services.rds.model.ModifyDbParameterGroupResponse;
import software.amazon.awssdk.services.rds.model.OrderableDBInstanceOption;
import software.amazon.awssdk.services.rds.model.Parameter;
import software.amazon.awssdk.services.rds.model.RdsException;
import software.amazon.awssdk.services.rds.model.CreateDbParameterGroupRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbParameterGroupsRequest;
import software.amazon.awssdk.services.rds.model.DescribeDbParametersRequest;
import software.amazon.awssdk.services.rds.model.ModifyDbParameterGroupRequest;
import
 software.amazon.awssdk.services.rds.model.DescribeOrderableDbInstanceOptionsRequest;
import software.amazon.awssdk.services.rds.model.DeleteDbParameterGroupRequest;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This example requires an AWS Secrets Manager secret that contains the
 * database credentials. If you do not create a
 * secret, this example will not work. For details, see:
 *
```

```
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html
 *
 * This Java example performs these tasks:
 *
 * 1. Returns a list of the available DB engines.
 * 2. Selects an engine family and create a custom DB parameter group.
 * 3. Gets the parameter groups.
 * 4. Gets parameters in the group.
 * 5. Modifies the auto_increment_offset parameter.
 * 6. Gets and displays the updated parameters.
 * 7. Gets a list of allowed engine versions.
 * 8. Gets a list of micro instance classes available for the selected engine.
 * 9. Creates an RDS database instance that contains a MySql database and uses
 * the parameter group.
 * 10. Waits for the DB instance to be ready and prints out the connection
 * endpoint value.
 * 11. Creates a snapshot of the DB instance.
 * 12. Waits for an RDS DB snapshot to be ready.
 * 13. Deletes the RDS DB instance.
 * 14. Deletes the parameter group.
 */
public class RDSScenario {
    public static long sleepTime = 20;
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws InterruptedException {
        final String usage = """

                Usage:
                    <dbGroupName> <dbParameterGroupFamily> <dbInstanceIdentifier>
 <dbName> <dbSnapshotIdentifier> <secretName>

                Where:
                    dbGroupName - The database group name.\s
                    dbParameterGroupFamily - The database parameter group name (for
 example, mysql8.0).
                    dbInstanceIdentifier - The database instance identifier\s
                    dbName - The database name.\s
                    dbSnapshotIdentifier - The snapshot identifier.\s
                    secretName - The name of the AWS Secrets Manager secret that
 contains the database credentials"
                """;
```

```
        if (args.length != 6) {
            System.out.println(usage);
            System.exit(1);
        }

        String dbGroupName = args[0];
        String dbParameterGroupFamily = args[1];
        String dbInstanceIdentifier = args[2];
        String dbName = args[3];
        String dbSnapshotIdentifier = args[4];
        String secretName = args[5];

        Gson gson = new Gson();
        User user = gson.fromJson(String.valueOf(getSecretValues(secretName)),
User.class);
        String masterUsername = user.getUsername();
        String masterUserPassword = user.getPassword();

        Region region = Region.US_WEST_2;
        RdsClient rdsClient = RdsClient.builder()
                .region(region)
                .build();
        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon RDS example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Return a list of the available DB engines");
        describeDBEngines(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Create a custom parameter group");
        createDBParameterGroup(rdsClient, dbGroupName, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Get the parameter group");
        describeDbParameterGroups(rdsClient, dbGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get the parameters in the group");
        describeDbParameters(rdsClient, dbGroupName, 0);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Modify the auto_increment_offset parameter");
        modifyDBParas(rdsClient, dbGroupName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Display the updated value");
        describeDbParameters(rdsClient, dbGroupName, -1);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Get a list of allowed engine versions");
        getAllowedEngines(rdsClient, dbParameterGroupFamily);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Get a list of micro instance classes available for
the selected engine");
        getMicroInstances(rdsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println(
                "9. Create an RDS database instance that contains a MySql database
and uses the parameter group");
        String dbARN = createDatabaseInstance(rdsClient, dbGroupName,
dbInstanceIdentifier, dbName, masterUsername,
                masterUserPassword);
        System.out.println("The ARN of the new database is " + dbARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Wait for DB instance to be ready");
        waitForInstanceReady(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("11. Create a snapshot of the DB instance");
        createSnapshot(rdsClient, dbInstanceIdentifier, dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        System.out.println("12. Wait for DB snapshot to be ready");
        waitForSnapshotReady(rdsClient, dbInstanceIdentifier, dbSnapshotIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("13. Delete the DB instance");
        deleteDatabaseInstance(rdsClient, dbInstanceIdentifier);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("14. Delete the parameter group");
        deleteParaGroup(rdsClient, dbGroupName, dbARN);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The Scenario has successfully completed.");
        System.out.println(DASHES);

        rdsClient.close();
    }

    private static SecretsManagerClient getSecretClient() {
        Region region = Region.US_WEST_2;
        return SecretsManagerClient.builder()
                .region(region)

.credentialsProvider(EnvironmentVariableCredentialsProvider.create())
                .build();
    }

    public static String getSecretValues(String secretName) {
        SecretsManagerClient secretClient = getSecretClient();
        GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                .secretId(secretName)
                .build();

        GetSecretValueResponse valueResponse =
secretClient.getSecretValue(valueRequest);
        return valueResponse.secretString();
    }

    // Delete the parameter group after database has been deleted.
    // An exception is thrown if you attempt to delete the para group while database
    // exists.
```

```
   public static void deleteParaGroup(RdsClient rdsClient, String dbGroupName,
String dbARN)
           throws InterruptedException {
       try {
           boolean isDataDel = false;
           boolean didFind;
           String instanceARN;

           // Make sure that the database has been deleted.
           while (!isDataDel) {
               DescribeDbInstancesResponse response =
rdsClient.describeDBInstances();
               List<DBInstance> instanceList = response.dbInstances();
               int listSize = instanceList.size();
               didFind = false;
               int index = 1;
               for (DBInstance instance : instanceList) {
                   instanceARN = instance.dbInstanceArn();
                   if (instanceARN.compareTo(dbARN) == 0) {
                       System.out.println(dbARN + " still exists");
                       didFind = true;
                   }
                   if ((index == listSize) && (!didFind)) {
                       // Went through the entire list and did not find the
database ARN.
                       isDataDel = true;
                   }
                   Thread.sleep(sleepTime * 1000);
                   index++;
               }
           }

           // Delete the para group.
           DeleteDbParameterGroupRequest parameterGroupRequest =
DeleteDbParameterGroupRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .build();

           rdsClient.deleteDBParameterGroup(parameterGroupRequest);
           System.out.println(dbGroupName + " was deleted.");

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
```

```
        }
    }

    // Delete the DB instance.
    public static void deleteDatabaseInstance(RdsClient rdsClient, String
dbInstanceIdentifier) {
        try {
            DeleteDbInstanceRequest deleteDbInstanceRequest =
DeleteDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .deleteAutomatedBackups(true)
                    .skipFinalSnapshot(true)
                    .build();

            DeleteDbInstanceResponse response =
rdsClient.deleteDBInstance(deleteDbInstanceRequest);
            System.out.print("The status of the database is " +
response.dbInstance().dbInstanceStatus());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Waits until the snapshot instance is available.
    public static void waitForSnapshotReady(RdsClient rdsClient, String
dbInstanceIdentifier,
            String dbSnapshotIdentifier) {
        try {
            boolean snapshotReady = false;
            String snapshotReadyStr;
            System.out.println("Waiting for the snapshot to become available.");

            DescribeDbSnapshotsRequest snapshotsRequest =
DescribeDbSnapshotsRequest.builder()
                    .dbSnapshotIdentifier(dbSnapshotIdentifier)
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            while (!snapshotReady) {
                DescribeDbSnapshotsResponse response =
rdsClient.describeDBSnapshots(snapshotsRequest);
                List<DBSnapshot> snapshotList = response.dbSnapshots();
```

```
                for (DBSnapshot snapshot : snapshotList) {
                    snapshotReadyStr = snapshot.status();
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }

            System.out.println("The Snapshot is available!");
        } catch (RdsException | InterruptedException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Create an Amazon RDS snapshot.
    public static void createSnapshot(RdsClient rdsClient, String
dbInstanceIdentifier, String dbSnapshotIdentifier) {
        try {
            CreateDbSnapshotRequest snapshotRequest =
CreateDbSnapshotRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .dbSnapshotIdentifier(dbSnapshotIdentifier)
                    .build();

            CreateDbSnapshotResponse response =
rdsClient.createDBSnapshot(snapshotRequest);
            System.out.println("The Snapshot id is " +
response.dbSnapshot().dbiResourceId());

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Waits until the database instance is available.
    public static void waitForInstanceReady(RdsClient rdsClient, String
dbInstanceIdentifier) {
        boolean instanceReady = false;
        String instanceReadyStr;
```

```
        System.out.println("Waiting for instance to become available.");
        try {
            DescribeDbInstancesRequest instanceRequest =
DescribeDbInstancesRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
                    .build();

            String endpoint = "";
            while (!instanceReady) {
                DescribeDbInstancesResponse response =
rdsClient.describeDBInstances(instanceRequest);
                List<DBInstance> instanceList = response.dbInstances();
                for (DBInstance instance : instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus();
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint().address();
                        instanceReady = true;
                    } else {
                        System.out.print(".");
                        Thread.sleep(sleepTime * 1000);
                    }
                }
            }
            System.out.println("Database instance is available! The connection
endpoint is " + endpoint);

        } catch (RdsException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Create a database instance and return the ARN of the database.
    public static String createDatabaseInstance(RdsClient rdsClient,
            String dbGroupName,
            String dbInstanceIdentifier,
            String dbName,
            String masterUsername,
            String masterUserPassword) {

        try {
            CreateDbInstanceRequest instanceRequest =
CreateDbInstanceRequest.builder()
                    .dbInstanceIdentifier(dbInstanceIdentifier)
```

```
                    .allocatedStorage(100)
                    .dbName(dbName)
                    .dbParameterGroupName(dbGroupName)
                    .engine("mysql")
                    .dbInstanceClass("db.m4.large")
                    .engineVersion("8.0")
                    .storageType("standard")
                    .masterUsername(masterUsername)
                    .masterUserPassword(masterUserPassword)
                    .build();

            CreateDbInstanceResponse response =
rdsClient.createDBInstance(instanceRequest);
            System.out.print("The status is " +
response.dbInstance().dbInstanceStatus());
            return response.dbInstance().dbInstanceArn();

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }

        return "";
    }

    // Get a list of micro instances.
    public static void getMicroInstances(RdsClient rdsClient) {
        try {
            DescribeOrderableDbInstanceOptionsRequest dbInstanceOptionsRequest =
DescribeOrderableDbInstanceOptionsRequest
                    .builder()
                    .engine("mysql")
                    .build();

            DescribeOrderableDbInstanceOptionsResponse response = rdsClient
                    .describeOrderableDBInstanceOptions(dbInstanceOptionsRequest);
            List<OrderableDBInstanceOption> orderableDBInstances =
response.orderableDBInstanceOptions();
            for (OrderableDBInstanceOption dbInstanceOption : orderableDBInstances)
{
                System.out.println("The engine version is " +
dbInstanceOption.engineVersion());
                System.out.println("The engine description is " +
dbInstanceOption.engine());
```

```
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Get a list of allowed engine versions.
    public static void getAllowedEngines(RdsClient rdsClient, String
dbParameterGroupFamily) {
        try {
            DescribeDbEngineVersionsRequest versionsRequest =
DescribeDbEngineVersionsRequest.builder()
                    .dbParameterGroupFamily(dbParameterGroupFamily)
                    .engine("mysql")
                    .build();

            DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(versionsRequest);
            List<DBEngineVersion> dbEngines = response.dbEngineVersions();
            for (DBEngineVersion dbEngine : dbEngines) {
                System.out.println("The engine version is " +
dbEngine.engineVersion());
                System.out.println("The engine description is " +
dbEngine.dbEngineDescription());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Modify auto_increment_offset and auto_increment_increment parameters.
    public static void modifyDBParas(RdsClient rdsClient, String dbGroupName) {
        try {
            Parameter parameter1 = Parameter.builder()
                    .parameterName("auto_increment_offset")
                    .applyMethod("immediate")
                    .parameterValue("5")
                    .build();

            List<Parameter> paraList = new ArrayList<>();
```

```
            paraList.add(parameter1);
            ModifyDbParameterGroupRequest groupRequest =
ModifyDbParameterGroupRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .parameters(paraList)
                    .build();

            ModifyDbParameterGroupResponse response =
rdsClient.modifyDBParameterGroup(groupRequest);
            System.out.println("The parameter group " +
response.dbParameterGroupName() + " was successfully modified");

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    // Retrieve parameters in the group.
    public static void describeDbParameters(RdsClient rdsClient, String dbGroupName,
int flag) {
        try {
            DescribeDbParametersRequest dbParameterGroupsRequest;
            if (flag == 0) {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .build();
            } else {
                dbParameterGroupsRequest = DescribeDbParametersRequest.builder()
                        .dbParameterGroupName(dbGroupName)
                        .source("user")
                        .build();
            }

            DescribeDbParametersResponse response =
rdsClient.describeDBParameters(dbParameterGroupsRequest);
            List<Parameter> dbParameters = response.parameters();
            String paraName;
            for (Parameter para : dbParameters) {
                // Only print out information about either auto_increment_offset or
                // auto_increment_increment.
                paraName = para.parameterName();
                if ((paraName.compareTo("auto_increment_offset") == 0)
                        || (paraName.compareTo("auto_increment_increment ") == 0)) {
```

```
                    System.out.println("*** The parameter name is  " + paraName);
                    System.out.println("*** The parameter value is  " +
para.parameterValue());
                    System.out.println("*** The parameter data type is " +
para.dataType());
                    System.out.println("*** The parameter description is " +
para.description());
                    System.out.println("*** The parameter allowed values  is " +
para.allowedValues());
                }
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeDbParameterGroups(RdsClient rdsClient, String
dbGroupName) {
        try {
            DescribeDbParameterGroupsRequest groupsRequest =
DescribeDbParameterGroupsRequest.builder()
                    .dbParameterGroupName(dbGroupName)
                    .maxRecords(20)
                    .build();

            DescribeDbParameterGroupsResponse response =
rdsClient.describeDBParameterGroups(groupsRequest);
            List<DBParameterGroup> groups = response.dbParameterGroups();
            for (DBParameterGroup group : groups) {
                System.out.println("The group name is " +
group.dbParameterGroupName());
                System.out.println("The group description is " +
group.description());
            }

        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

```
   public static void createDBParameterGroup(RdsClient rdsClient, String
dbGroupName, String dbParameterGroupFamily) {
       try {
           CreateDbParameterGroupRequest groupRequest =
CreateDbParameterGroupRequest.builder()
                   .dbParameterGroupName(dbGroupName)
                   .dbParameterGroupFamily(dbParameterGroupFamily)
                   .description("Created by using the AWS SDK for Java")
                   .build();

           CreateDbParameterGroupResponse response =
rdsClient.createDBParameterGroup(groupRequest);
           System.out.println("The group name is " +
response.dbParameterGroup().dbParameterGroupName());

       } catch (RdsException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }

   public static void describeDBEngines(RdsClient rdsClient) {
       try {
           DescribeDbEngineVersionsRequest engineVersionsRequest =
DescribeDbEngineVersionsRequest.builder()
                   .defaultOnly(true)
                   .engine("mysql")
                   .maxRecords(20)
                   .build();

           DescribeDbEngineVersionsResponse response =
rdsClient.describeDBEngineVersions(engineVersionsRequest);
           List<DBEngineVersion> engines = response.dbEngineVersions();

           // Get all DBEngineVersion objects.
           for (DBEngineVersion engineOb : engines) {
               System.out.println("The name of the DB parameter group family for
the database engine is "
                       + engineOb.dbParameterGroupFamily());
               System.out.println("The name of the database engine " +
engineOb.engine());
               System.out.println("The version number of the database engine " +
engineOb.engineVersion());
           }
```

```
        } catch (RdsException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - Descreva o DB EngineVersions
  - DescribeDBInstances
  - Descreva o DB ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

Exemplos do Amazon Redshift usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Redshift.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um cluster

O exemplo de código a seguir mostra como criar um cluster do Amazon Redshift.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cluster.

```
   public static void createCluster(RedshiftClient redshiftClient, String
clusterId, String masterUsername,
           String masterUserPassword) {
       try {
           CreateClusterRequest clusterRequest = CreateClusterRequest.builder()
                   .clusterIdentifier(clusterId)
                   .masterUsername(masterUsername) // set the user name here
                   .masterUserPassword(masterUserPassword) // set the user password
here
                   .nodeType("dc2.large")
                   .publiclyAccessible(true)
                   .numberOfNodes(2)
                   .build();

           CreateClusterResponse clusterResponse =
redshiftClient.createCluster(clusterRequest);
           System.out.println("Created cluster " +
clusterResponse.cluster().clusterIdentifier());

       } catch (RedshiftException e) {
```

```
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CreateClustera Referência AWS SDK for Java 2.x da API.

Excluir um cluster

O exemplo de código a seguir mostra como excluir um cluster do Amazon Redshift.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o cluster.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.redshift.RedshiftClient;
import software.amazon.awssdk.services.redshift.model.DeleteClusterRequest;
import software.amazon.awssdk.services.redshift.model.DeleteClusterResponse;
import software.amazon.awssdk.services.redshift.model.RedshiftException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteCluster {
    public static void main(String[] args) {

        final String usage = """
```

```
                Usage:
                    <clusterId>\s

                Where:
                    clusterId - The id of the cluster to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String clusterId = args[0];
        Region region = Region.US_WEST_2;
        RedshiftClient redshiftClient = RedshiftClient.builder()
                .region(region)
                .build();

        deleteRedshiftCluster(redshiftClient, clusterId);
        redshiftClient.close();
    }

    public static void deleteRedshiftCluster(RedshiftClient redshiftClient, String
 clusterId) {
        try {
            DeleteClusterRequest deleteClusterRequest =
 DeleteClusterRequest.builder()
                    .clusterIdentifier(clusterId)
                    .skipFinalClusterSnapshot(true)
                    .build();

            DeleteClusterResponse response =
 redshiftClient.deleteCluster(deleteClusterRequest);
            System.out.println("The status is " +
 response.cluster().clusterStatus());

        } catch (RedshiftException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteClustera Referência AWS SDK for Java 2.x da API.

Descrever seus clusters

O exemplo de código a seguir mostra como descrever clusters do Amazon Redshift.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Descrever o cluster.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.redshift.RedshiftClient;
import software.amazon.awssdk.services.redshift.model.Cluster;
import software.amazon.awssdk.services.redshift.model.DescribeClustersResponse;
import software.amazon.awssdk.services.redshift.model.RedshiftException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeClusters {

    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        RedshiftClient redshiftClient = RedshiftClient.builder()
                .region(region)
                .build();

        describeRedshiftClusters(redshiftClient);
        redshiftClient.close();
    }
```

```
    public static void describeRedshiftClusters(RedshiftClient redshiftClient) {
        try {
            DescribeClustersResponse clusterResponse =
 redshiftClient.describeClusters();
            List<Cluster> clusterList = clusterResponse.clusters();
            for (Cluster cluster : clusterList) {
                System.out.println("Cluster database name is: " + cluster.dbName());
                System.out.println("Cluster status is: " + cluster.clusterStatus());
            }

        } catch (RedshiftException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeClustersa Referência AWS SDK for Java 2.x da API.

Modificar um cluster

O exemplo de código a seguir mostra como modificar um cluster do Amazon Redshift.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Modifique um cluster.

```
    public static void modifyCluster(RedshiftClient redshiftClient, String
 clusterId) {

        try {
            ModifyClusterRequest modifyClusterRequest =
 ModifyClusterRequest.builder()
```

```
                    .clusterIdentifier(clusterId)
                    .preferredMaintenanceWindow("wed:07:30-wed:08:00")
                    .build();

            ModifyClusterResponse clusterResponse =
redshiftClient.modifyCluster(modifyClusterRequest);
            System.out.println("The modified cluster was successfully modified and
has "
                    + clusterResponse.cluster().preferredMaintenanceWindow() + " as
the maintenance window");

        } catch (RedshiftException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ModifyClustera Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Rekognition usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com Amazon Rekognition.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Comparar faces em uma imagem com uma imagem de referência

O exemplo de código a seguir mostra como comparar faces em uma imagem com uma imagem de referência usando o Amazon Rekognition.

Para obter mais informações, consulte Comparar faces em imagens.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.CompareFacesRequest;
import software.amazon.awssdk.services.rekognition.model.CompareFacesResponse;
import software.amazon.awssdk.services.rekognition.model.CompareFacesMatch;
import software.amazon.awssdk.services.rekognition.model.ComparedFace;
import software.amazon.awssdk.services.rekognition.model.BoundingBox;
import software.amazon.awssdk.core.SdkBytes;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CompareFaces {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:    <pathSource> <pathTarget>

                Where:
                   pathSource - The path to the source image (for example, C:\\AWS\
\pic1.png).\s
                    pathTarget - The path to the target image (for example, C:\\AWS\
\pic2.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        Float similarityThreshold = 70F;
        String sourceImage = args[0];
        String targetImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        compareTwoFaces(rekClient, similarityThreshold, sourceImage, targetImage);
        rekClient.close();
    }

    public static void compareTwoFaces(RekognitionClient rekClient, Float
 similarityThreshold, String sourceImage,
            String targetImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            InputStream tarStream = new FileInputStream(targetImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            SdkBytes targetBytes = SdkBytes.fromInputStream(tarStream);

            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            Image tarImage = Image.builder()
                    .bytes(targetBytes)
                    .build();
```

```
            CompareFacesRequest facesRequest = CompareFacesRequest.builder()
                    .sourceImage(souImage)
                    .targetImage(tarImage)
                    .similarityThreshold(similarityThreshold)
                    .build();

            // Compare the two images.
            CompareFacesResponse compareFacesResult =
 rekClient.compareFaces(facesRequest);
            List<CompareFacesMatch> faceDetails = compareFacesResult.faceMatches();
            for (CompareFacesMatch match : faceDetails) {
                ComparedFace face = match.face();
                BoundingBox position = face.boundingBox();
                System.out.println("Face at " + position.left().toString()
                        + " " + position.top()
                        + " matches with " + face.confidence().toString()
                        + "% confidence.");

            }
            List<ComparedFace> uncompared = compareFacesResult.unmatchedFaces();
            System.out.println("There was " + uncompared.size() + " face(s) that did
 not match");
            System.out.println("Source image rotation: " +
 compareFacesResult.sourceImageOrientationCorrection());
            System.out.println("target image rotation: " +
 compareFacesResult.targetImageOrientationCorrection());

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println("Failed to load source image " + sourceImage);
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CompareFacesa Referência AWS SDK for Java 2.x da API.

Criar uma coleção

O exemplo de código a seguir mostra como criar uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Criar uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.CreateCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.CreateCollectionRequest;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionName>\s

                Where:
                   collectionName - The name of the collection.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
```

```
                .region(region)
                .build();

        System.out.println("Creating collection: " + collectionId);
        createMyCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void createMyCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            CreateCollectionRequest collectionRequest =
 CreateCollectionRequest.builder()
                    .collectionId(collectionId)
                    .build();

            CreateCollectionResponse collectionResponse =
 rekClient.createCollection(collectionRequest);
            System.out.println("CollectionArn: " +
 collectionResponse.collectionArn());
            System.out.println("Status code: " +
 collectionResponse.statusCode().toString());

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateCollectiona Referência AWS SDK for Java 2.x da API.

Excluir uma coleção.

O exemplo de código a seguir mostra como excluir uma coleção do Amazon Rekognition.

Para mais informações, consulte Excluir uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DeleteCollectionRequest;
import software.amazon.awssdk.services.rekognition.model.DeleteCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId>\s

                Where:
                   collectionId - The id of the collection to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();
```

```
        System.out.println("Deleting collection: " + collectionId);
        deleteMyCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void deleteMyCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            DeleteCollectionRequest deleteCollectionRequest =
 DeleteCollectionRequest.builder()
                    .collectionId(collectionId)
                    .build();

            DeleteCollectionResponse deleteCollectionResponse =
 rekClient.deleteCollection(deleteCollectionRequest);
            System.out.println(collectionId + ": " +
 deleteCollectionResponse.statusCode().toString());

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteCollectiona Referência AWS SDK for Java 2.x da API.

Excluir faces de uma coleção

O exemplo de código a seguir mostra como excluir faces de uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir faces de uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DeleteFacesRequest;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteFacesFromCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId> <faceId>\s

                Where:
                   collectionId - The id of the collection from which faces are
 deleted.\s

                   faceId - The id of the face to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String faceId = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Deleting collection: " + collectionId);
        deleteFacesCollection(rekClient, collectionId, faceId);
        rekClient.close();
    }
```

```
    public static void deleteFacesCollection(RekognitionClient rekClient,
            String collectionId,
            String faceId) {

        try {
            DeleteFacesRequest deleteFacesRequest = DeleteFacesRequest.builder()
                    .collectionId(collectionId)
                    .faceIds(faceId)
                    .build();

            rekClient.deleteFaces(deleteFacesRequest);
            System.out.println("The face was deleted from the collection.");

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteFacesa Referência AWS SDK for Java 2.x da API.

Descrever uma coleção

O exemplo de código a seguir mostra como descrever uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Descrever uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DescribeCollectionRequest;
import software.amazon.awssdk.services.rekognition.model.DescribeCollectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionName>

                Where:
                   collectionName - The name of the Amazon Rekognition collection.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionName = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        describeColl(rekClient, collectionName);
        rekClient.close();
    }

    public static void describeColl(RekognitionClient rekClient, String
 collectionName) {
        try {
            DescribeCollectionRequest describeCollectionRequest =
 DescribeCollectionRequest.builder()
                    .collectionId(collectionName)
                    .build();

            DescribeCollectionResponse describeCollectionResponse = rekClient
                    .describeCollection(describeCollectionRequest);
```

```
            System.out.println("Collection Arn : " +
 describeCollectionResponse.collectionARN());
            System.out.println("Created : " +
 describeCollectionResponse.creationTimestamp().toString());

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeCollectiona Referência AWS SDK for Java 2.x da API.

Detectar faces em uma imagem

O exemplo de código a seguir mostra como detectar faces em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar faces em uma imagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.DetectFacesRequest;
import software.amazon.awssdk.services.rekognition.model.DetectFacesResponse;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.Attribute;
import software.amazon.awssdk.services.rekognition.model.FaceDetail;
import software.amazon.awssdk.services.rekognition.model.AgeRange;
import software.amazon.awssdk.core.SdkBytes;
```

```
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectFaces {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectFacesinImage(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectFacesinImage(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
```

```
            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectFacesRequest facesRequest = DetectFacesRequest.builder()
                    .attributes(Attribute.ALL)
                    .image(souImage)
                    .build();

            DetectFacesResponse facesResponse = rekClient.detectFaces(facesRequest);
            List<FaceDetail> faceDetails = facesResponse.faceDetails();
            for (FaceDetail face : faceDetails) {
                AgeRange ageRange = face.ageRange();
                System.out.println("The detected face is estimated to be between "
                        + ageRange.low().toString() + " and " +
 ageRange.high().toString()
                        + " years old.");

                System.out.println("There is a smile : " +
 face.smile().value().toString());
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectFacesa Referência AWS SDK for Java 2.x da API.

Para detectar rótulos em uma imagem

O exemplo de código a seguir mostra como detectar rótulos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar rótulos em uma imagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.DetectLabelsRequest;
import software.amazon.awssdk.services.rekognition.model.DetectLabelsResponse;
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectLabels {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectImageLabels(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectImageLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Create an Image object for the source image.
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectLabelsRequest detectLabelsRequest = DetectLabelsRequest.builder()
                    .image(souImage)
                    .maxLabels(10)
                    .build();

            DetectLabelsResponse labelsResponse =
 rekClient.detectLabels(detectLabelsRequest);
            List<Label> labels = labelsResponse.labels();
            System.out.println("Detected labels for the given photo");
            for (Label label : labels) {
                System.out.println(label.name() + ": " +
 label.confidence().toString());
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectLabelsa Referência AWS SDK for Java 2.x da API.

Detectar rótulos de moderação em uma imagem

O exemplo de código a seguir mostra como detectar rótulos de moderação em uma imagem com o Amazon Rekognition. Os rótulos de moderação identificam o conteúdo que pode ser inadequado para alguns públicos.

Para obter mais informações, consulte Detectar imagens inapropriadas.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import
 software.amazon.awssdk.services.rekognition.model.DetectModerationLabelsRequest;
import
 software.amazon.awssdk.services.rekognition.model.DetectModerationLabelsResponse;
import software.amazon.awssdk.services.rekognition.model.ModerationLabel;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectModerationLabels {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectModLabels(rekClient, sourceImage);
        rekClient.close();
    }

    public static void detectModLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectModerationLabelsRequest moderationLabelsRequest =
 DetectModerationLabelsRequest.builder()
                    .image(souImage)
                    .minConfidence(60F)
                    .build();
```

```
            DetectModerationLabelsResponse moderationLabelsResponse = rekClient
                    .detectModerationLabels(moderationLabelsRequest);
            List<ModerationLabel> labels =
 moderationLabelsResponse.moderationLabels();
            System.out.println("Detected labels for image");
            for (ModerationLabel label : labels) {
                System.out.println("Label: " + label.name()
                        + "\n Confidence: " + label.confidence().toString() + "%"
                        + "\n Parent:" + label.parentName());
            }

        } catch (RekognitionException | FileNotFoundException e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectModerationLabelsa Referência AWS SDK for Java 2.x da API.

Detectar texto em uma imagem

O exemplo de código a seguir mostra como detectar texto em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar texto em uma imagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.DetectTextRequest;
```

```
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.DetectTextResponse;
import software.amazon.awssdk.services.rekognition.model.TextDetection;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectText {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <sourceImage>

                Where:
                   sourceImage - The path to the image that contains text (for
 example, C:\\AWS\\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        detectTextLabels(rekClient, sourceImage);
        rekClient.close();
    }
```

```
    public static void detectTextLabels(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            DetectTextRequest textRequest = DetectTextRequest.builder()
                    .image(souImage)
                    .build();

            DetectTextResponse textResponse = rekClient.detectText(textRequest);
            List<TextDetection> textCollection = textResponse.textDetections();
            System.out.println("Detected lines and words");
            for (TextDetection text : textCollection) {
                System.out.println("Detected: " + text.detectedText());
                System.out.println("Confidence: " + text.confidence().toString());
                System.out.println("Id : " + text.id());
                System.out.println("Parent Id: " + text.parentId());
                System.out.println("Type: " + text.type());
                System.out.println();
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectTexta Referência AWS SDK for Java 2.x da API.

Indexar faces de uma coleção

O exemplo de código a seguir mostra como indexar faces em uma imagem e adicioná-las a uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Adicionar faces a uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.IndexFacesResponse;
import software.amazon.awssdk.services.rekognition.model.IndexFacesRequest;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.QualityFilter;
import software.amazon.awssdk.services.rekognition.model.Attribute;
import software.amazon.awssdk.services.rekognition.model.FaceRecord;
import software.amazon.awssdk.services.rekognition.model.UnindexedFace;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Reason;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class AddFacesToCollection {
    public static void main(String[] args) {

        final String usage = """

                Usage:     <collectionId> <sourceImage>

                Where:
                    collectionName - The name of the collection.
```

```
                    sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String sourceImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        addToCollection(rekClient, collectionId, sourceImage);
        rekClient.close();
    }

    public static void addToCollection(RekognitionClient rekClient, String
 collectionId, String sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            IndexFacesRequest facesRequest = IndexFacesRequest.builder()
                    .collectionId(collectionId)
                    .image(souImage)
                    .maxFaces(1)
                    .qualityFilter(QualityFilter.AUTO)
                    .detectionAttributes(Attribute.DEFAULT)
                    .build();

            IndexFacesResponse facesResponse = rekClient.indexFaces(facesRequest);
            System.out.println("Results for the image");
            System.out.println("\n Faces indexed:");
            List<FaceRecord> faceRecords = facesResponse.faceRecords();
            for (FaceRecord faceRecord : faceRecords) {
                System.out.println("  Face ID: " + faceRecord.face().faceId());
```

```
                System.out.println("  Location:" +
 faceRecord.faceDetail().boundingBox().toString());
            }

            List<UnindexedFace> unindexedFaces = facesResponse.unindexedFaces();
            System.out.println("Faces not indexed:");
            for (UnindexedFace unindexedFace : unindexedFaces) {
                System.out.println("  Location:" +
 unindexedFace.faceDetail().boundingBox().toString());
                System.out.println("  Reasons:");
                for (Reason reason : unindexedFace.reasons()) {
                    System.out.println("Reason:  " + reason);
                }
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte IndexFacesa Referência AWS SDK for Java 2.x da API.

Listar coleções

O exemplo de código a seguir mostra como listar coleções do Amazon Rekognition.

Para obter mais informações, consulte Listar coleções.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.ListCollectionsRequest;
```

```
import software.amazon.awssdk.services.rekognition.model.ListCollectionsResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListCollections {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Listing collections");
        listAllCollections(rekClient);
        rekClient.close();
    }

    public static void listAllCollections(RekognitionClient rekClient) {
        try {
            ListCollectionsRequest listCollectionsRequest =
 ListCollectionsRequest.builder()
                    .maxResults(10)
                    .build();

            ListCollectionsResponse response =
 rekClient.listCollections(listCollectionsRequest);
            List<String> collectionIds = response.collectionIds();
            for (String resultId : collectionIds) {
                System.out.println(resultId);
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListCollectionsa Referência AWS SDK for Java 2.x da API.

Listar faces em uma coleção

O exemplo de código a seguir mostra como lista faces em uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Listar faces em uma coleção.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.Face;
import software.amazon.awssdk.services.rekognition.model.ListFacesRequest;
import software.amazon.awssdk.services.rekognition.model.ListFacesResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListFacesInCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId>

                Where:
```

```
                   collectionId - The name of the collection.\s
                """";

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Faces in collection " + collectionId);
        listFacesCollection(rekClient, collectionId);
        rekClient.close();
    }

    public static void listFacesCollection(RekognitionClient rekClient, String
 collectionId) {
        try {
            ListFacesRequest facesRequest = ListFacesRequest.builder()
                    .collectionId(collectionId)
                    .maxResults(10)
                    .build();

            ListFacesResponse facesResponse = rekClient.listFaces(facesRequest);
            List<Face> faces = facesResponse.faces();
            for (Face face : faces) {
                System.out.println("Confidence level there is a face: " +
 face.confidence());
                System.out.println("The face Id value is " + face.faceId());
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListFacesa Referência AWS SDK for Java 2.x da API.

Reconhecer celebridades em uma imagem

O exemplo de código a seguir mostra como reconhecer celebridades em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Reconhecer celebridades em uma imagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.core.SdkBytes;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;
import
 software.amazon.awssdk.services.rekognition.model.RecognizeCelebritiesRequest;
import
 software.amazon.awssdk.services.rekognition.model.RecognizeCelebritiesResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.Celebrity;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class RecognizeCelebrities {
    public static void main(String[] args) {
        final String usage = """
                Usage:    <sourceImage>
```

```
                Where:
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceImage = args[0];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Locating celebrities in " + sourceImage);
        recognizeAllCelebrities(rekClient, sourceImage);
        rekClient.close();
    }

    public static void recognizeAllCelebrities(RekognitionClient rekClient, String
 sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(sourceImage);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            RecognizeCelebritiesRequest request =
 RecognizeCelebritiesRequest.builder()
                    .image(souImage)
                    .build();

            RecognizeCelebritiesResponse result =
 rekClient.recognizeCelebrities(request);
            List<Celebrity> celebs = result.celebrityFaces();
            System.out.println(celebs.size() + " celebrity(s) were recognized.\n");
            for (Celebrity celebrity : celebs) {
                System.out.println("Celebrity recognized: " + celebrity.name());
                System.out.println("Celebrity ID: " + celebrity.id());

                System.out.println("Further information (if available):");
```

```
                for (String url : celebrity.urls()) {
                    System.out.println(url);
                }
                System.out.println();
            }
            System.out.println(result.unrecognizedFaces().size() + " face(s) were
 unrecognized.");

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte RecognizeCelebritiesa Referência AWS SDK for Java 2.x da API.

Pesquisar faces em uma coleção

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition que correspondam a outra face da coleção.

Para obter mais informações, consulte Pesquisar uma face (Face ID).

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.SearchFacesByImageRequest;
import software.amazon.awssdk.services.rekognition.model.Image;
import software.amazon.awssdk.services.rekognition.model.SearchFacesByImageResponse;
```

```
import software.amazon.awssdk.services.rekognition.model.FaceMatch;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SearchFaceMatchingImageCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId> <sourceImage>

                Where:
                   collectionId - The id of the collection. \s
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s

                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
        String sourceImage = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Searching for a face in a collections");
        searchFaceInCollection(rekClient, collectionId, sourceImage);
        rekClient.close();
    }
```

```
    public static void searchFaceInCollection(RekognitionClient rekClient, String
 collectionId, String sourceImage) {
        try {
            InputStream sourceStream = new FileInputStream(new File(sourceImage));
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);
            Image souImage = Image.builder()
                    .bytes(sourceBytes)
                    .build();

            SearchFacesByImageRequest facesByImageRequest =
 SearchFacesByImageRequest.builder()
                    .image(souImage)
                    .maxFaces(10)
                    .faceMatchThreshold(70F)
                    .collectionId(collectionId)
                    .build();

            SearchFacesByImageResponse imageResponse =
 rekClient.searchFacesByImage(facesByImageRequest);
            System.out.println("Faces matching in the collection");
            List<FaceMatch> faceImageMatches = imageResponse.faceMatches();
            for (FaceMatch face : faceImageMatches) {
                System.out.println("The similarity level is  " + face.similarity());
                System.out.println();
            }

        } catch (RekognitionException | FileNotFoundException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SearchFacesa Referência AWS SDK for Java 2.x da API.

Pesquisar faces em uma coleção em comparação com uma imagem de referência

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition em comparação com uma imagem de referência.

Para obter mais informações, consulte Pesquisar uma face (imagem).

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.SearchFacesRequest;
import software.amazon.awssdk.services.rekognition.model.SearchFacesResponse;
import software.amazon.awssdk.services.rekognition.model.FaceMatch;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SearchFaceMatchingIdCollection {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <collectionId> <sourceImage>

                Where:
                   collectionId - The id of the collection. \s
                   sourceImage - The path to the image (for example, C:\\AWS\
\pic1.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String collectionId = args[0];
```

```
        String faceId = args[1];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        System.out.println("Searching for a face in a collections");
        searchFacebyId(rekClient, collectionId, faceId);
        rekClient.close();
    }

    public static void searchFacebyId(RekognitionClient rekClient, String
 collectionId, String faceId) {
        try {
            SearchFacesRequest searchFacesRequest = SearchFacesRequest.builder()
                    .collectionId(collectionId)
                    .faceId(faceId)
                    .faceMatchThreshold(70F)
                    .maxFaces(2)
                    .build();

            SearchFacesResponse imageResponse =
 rekClient.searchFaces(searchFacesRequest);
            System.out.println("Faces matching in the collection");
            List<FaceMatch> faceImageMatches = imageResponse.faceMatches();
            for (FaceMatch face : faceImageMatches) {
                System.out.println("The similarity level is  " + face.similarity());
                System.out.println();
            }

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SearchFacesByImagea Referência AWS SDK for Java 2.x da API.

Cenários

Detectar informações em vídeos

O código de exemplo a seguir mostra como:

- Inicie trabalhos do Amazon Rekognition para detectar elementos como pessoas, objetos e texto em vídeos.
- Verificar o status do trabalho até que eles terminem.
- Criar uma lista de elementos detectados por cada trabalho.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter resultados de celebridades a partir de um vídeo localizado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartCelebrityRecognitionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.CelebrityRecognitionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.CelebrityRecognition;
import software.amazon.awssdk.services.rekognition.model.CelebrityDetail;
import
 software.amazon.awssdk.services.rekognition.model.StartCelebrityRecognitionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetCelebrityRecognitionRequest;
import
 software.amazon.awssdk.services.rekognition.model.GetCelebrityRecognitionResponse;
import java.util.List;
```

```
/**
 * To run this code example, ensure that you perform the Prerequisites as stated
 * in the Amazon Rekognition Guide:
 * https://docs.aws.amazon.com/rekognition/latest/dg/video-analyzing-with-sqs.html
 *
 * Also, ensure that set up your development environment, including your
 * credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class VideoCelebrityDetection {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management (IAM)
 role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();
```

```
        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startCelebrityDetection(rekClient, channel, bucket, video);
        getCelebrityDetectionResults(rekClient);
        System.out.println("This example is done!");
        rekClient.close();
    }

    public static void startCelebrityDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartCelebrityRecognitionRequest recognitionRequest =
StartCelebrityRecognitionRequest.builder()
                    .jobTag("Celebrities")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();

            StartCelebrityRecognitionResponse startCelebrityRecognitionResult =
rekClient
                    .startCelebrityRecognition(recognitionRequest);
            startJobId = startCelebrityRecognitionResult.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
```

```
    public static void getCelebrityDetectionResults(RekognitionClient rekClient) {

        try {
            String paginationToken = null;
            GetCelebrityRecognitionResponse recognitionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (recognitionResponse != null)
                    paginationToken = recognitionResponse.nextToken();

                GetCelebrityRecognitionRequest recognitionRequest =
GetCelebrityRecognitionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .sortBy(CelebrityRecognitionSortBy.TIMESTAMP)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds
                while (!finished) {
                    recognitionResponse =
rekClient.getCelebrityRecognition(recognitionRequest);
                    status = recognitionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is null.
                VideoMetadata videoMetaData = recognitionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
```

```
                System.out.println("Job");

                List<CelebrityRecognition> celebs =
 recognitionResponse.celebrities();
                for (CelebrityRecognition celeb : celebs) {
                    long seconds = celeb.timestamp() / 1000;
                    System.out.print("Sec: " + seconds + " ");
                    CelebrityDetail details = celeb.celebrity();
                    System.out.println("Name: " + details.name());
                    System.out.println("Id: " + details.id());
                    System.out.println();
                }

            } while (recognitionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar rótulos em um vídeo por meio de uma operação de detecção de rótulos.

```
import com.fasterxml.jackson.core.JsonProcessingException;
import com.fasterxml.jackson.databind.JsonMappingException;
import com.fasterxml.jackson.databind.JsonNode;
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import software.amazon.awssdk.services.rekognition.model.StartLabelDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.GetLabelDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.GetLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.LabelDetectionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.LabelDetection;
```

```
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.Instance;
import software.amazon.awssdk.services.rekognition.model.Parent;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class VideoDetect {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <queueUrl> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of the video (for example, people.mp4).\s
                   queueUrl- The URL of a SQS queue.\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management (IAM)
 role to use.\s
                """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String queueUrl = args[2];
```

```
        String topicArn = args[3];
        String roleArn = args[4];
        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        SqsClient sqs = SqsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();

        startLabels(rekClient, channel, bucket, video);
        getLabelJob(rekClient, sqs, queueUrl);
        System.out.println("This example is done!");
        sqs.close();
        rekClient.close();
    }

    public static void startLabels(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartLabelDetectionRequest labelDetectionRequest =
StartLabelDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .minConfidence(50F)
                    .build();
```

```
            StartLabelDetectionResponse labelDetectionResponse =
rekClient.startLabelDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

            boolean ans = true;
            String status = "";
            int yy = 0;
            while (ans) {

                GetLabelDetectionRequest detectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .maxResults(10)
                        .build();

                GetLabelDetectionResponse result =
rekClient.getLabelDetection(detectionRequest);
                status = result.jobStatusAsString();

                if (status.compareTo("SUCCEEDED") == 0)
                    ans = false;
                else
                    System.out.println(yy + " status is: " + status);

                Thread.sleep(1000);
                yy++;
            }

            System.out.println(startJobId + " status is: " + status);

        } catch (RekognitionException | InterruptedException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getLabelJob(RekognitionClient rekClient, SqsClient sqs,
String queueUrl) {
        List<Message> messages;
        ReceiveMessageRequest messageRequest = ReceiveMessageRequest.builder()
                .queueUrl(queueUrl)
                .build();
```

```
        try {
            messages = sqs.receiveMessage(messageRequest).messages();

            if (!messages.isEmpty()) {
                for (Message message : messages) {
                    String notification = message.body();

                    // Get the status and job id from the notification
                    ObjectMapper mapper = new ObjectMapper();
                    JsonNode jsonMessageTree = mapper.readTree(notification);
                    JsonNode messageBodyText = jsonMessageTree.get("Message");
                    ObjectMapper operationResultMapper = new ObjectMapper();
                    JsonNode jsonResultTree =
operationResultMapper.readTree(messageBodyText.textValue());
                    JsonNode operationJobId = jsonResultTree.get("JobId");
                    JsonNode operationStatus = jsonResultTree.get("Status");
                    System.out.println("Job found in JSON is " + operationJobId);

                    DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                            .queueUrl(queueUrl)
                            .build();

                    String jobId = operationJobId.textValue();
                    if (startJobId.compareTo(jobId) == 0) {
                        System.out.println("Job id: " + operationJobId);
                        System.out.println("Status : " +
operationStatus.toString());

                        if (operationStatus.asText().equals("SUCCEEDED"))
                            getResultsLabels(rekClient);
                        else
                            System.out.println("Video analysis failed");

                        sqs.deleteMessage(deleteMessageRequest);
                    } else {
                        System.out.println("Job received was not job " +
startJobId);
                        sqs.deleteMessage(deleteMessageRequest);
                    }
                }
            }

        } catch (RekognitionException e) {
```

```
            e.getMessage();
            System.exit(1);
        } catch (JsonMappingException e) {
            e.printStackTrace();
        } catch (JsonProcessingException e) {
            e.printStackTrace();
        }
    }

    // Gets the job results by calling GetLabelDetection
    private static void getResultsLabels(RekognitionClient rekClient) {

        int maxResults = 10;
        String paginationToken = null;
        GetLabelDetectionResponse labelDetectionResult = null;

        try {
            do {
                if (labelDetectionResult != null)
                    paginationToken = labelDetectionResult.nextToken();

                GetLabelDetectionRequest labelDetectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .sortBy(LabelDetectionSortBy.TIMESTAMP)
                        .maxResults(maxResults)
                        .nextToken(paginationToken)
                        .build();

                labelDetectionResult =
rekClient.getLabelDetection(labelDetectionRequest);
                VideoMetadata videoMetaData = labelDetectionResult.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());

                List<LabelDetection> detectedLabels = labelDetectionResult.labels();
                for (LabelDetection detectedLabel : detectedLabels) {
                    long seconds = detectedLabel.timestamp();
                    Label label = detectedLabel.label();
                    System.out.println("Millisecond: " + seconds + " ");

                    System.out.println("   Label:" + label.name());
```

```
                    System.out.println("   Confidence:" +
 detectedLabel.label().confidence().toString());

                    List<Instance> instances = label.instances();
                    System.out.println("   Instances of " + label.name());

                    if (instances.isEmpty()) {
                        System.out.println("        " + "None");
                    } else {
                        for (Instance instance : instances) {
                            System.out.println("        Confidence: " +
 instance.confidence().toString());
                            System.out.println("        Bounding box: " +
 instance.boundingBox().toString());
                        }
                    }
                    System.out.println("   Parent labels for " + label.name() +
 ":");
                    List<Parent> parents = label.parents();

                    if (parents.isEmpty()) {
                        System.out.println("        None");
                    } else {
                        for (Parent parent : parents) {
                            System.out.println("   " + parent.name());
                        }
                    }
                    System.out.println();
                }
            } while (labelDetectionResult != null &&
 labelDetectionResult.nextToken() != null);

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }
}
```

Detectar faces em um vídeo armazenado em um bucket do Amazon S3.

```
import com.fasterxml.jackson.core.JsonProcessingException;
```

```
import com.fasterxml.jackson.databind.JsonMappingException;
import com.fasterxml.jackson.databind.JsonNode;
import com.fasterxml.jackson.databind.ObjectMapper;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import
 software.amazon.awssdk.services.rekognition.model.StartLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import software.amazon.awssdk.services.rekognition.model.StartLabelDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.GetLabelDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.GetLabelDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.LabelDetectionSortBy;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.LabelDetection;
import software.amazon.awssdk.services.rekognition.model.Label;
import software.amazon.awssdk.services.rekognition.model.Instance;
import software.amazon.awssdk.services.rekognition.model.Parent;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class VideoDetect {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <queueUrl> <topicArn> <roleArn>

                Where:
```

```
                  bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                  video - The name of the video (for example, people.mp4).\s
                  queueUrl- The URL of a SQS queue.\s
                  topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                  roleArn - The ARN of the AWS Identity and Access Management (IAM)
role to use.\s
               """;

       if (args.length != 5) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucket = args[0];
       String video = args[1];
       String queueUrl = args[2];
       String topicArn = args[3];
       String roleArn = args[4];
       Region region = Region.US_EAST_1;
       RekognitionClient rekClient = RekognitionClient.builder()
               .region(region)
               .build();

       SqsClient sqs = SqsClient.builder()
               .region(Region.US_EAST_1)
               .build();

       NotificationChannel channel = NotificationChannel.builder()
               .snsTopicArn(topicArn)
               .roleArn(roleArn)
               .build();

       startLabels(rekClient, channel, bucket, video);
       getLabelJob(rekClient, sqs, queueUrl);
       System.out.println("This example is done!");
       sqs.close();
       rekClient.close();
   }

   public static void startLabels(RekognitionClient rekClient,
           NotificationChannel channel,
           String bucket,
```

```
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartLabelDetectionRequest labelDetectionRequest =
StartLabelDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .minConfidence(50F)
                    .build();

            StartLabelDetectionResponse labelDetectionResponse =
rekClient.startLabelDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

            boolean ans = true;
            String status = "";
            int yy = 0;
            while (ans) {

                GetLabelDetectionRequest detectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .maxResults(10)
                        .build();

                GetLabelDetectionResponse result =
rekClient.getLabelDetection(detectionRequest);
                status = result.jobStatusAsString();

                if (status.compareTo("SUCCEEDED") == 0)
                    ans = false;
                else
                    System.out.println(yy + " status is: " + status);

                Thread.sleep(1000);
```

```
                yy++;
            }

            System.out.println(startJobId + " status is: " + status);

        } catch (RekognitionException | InterruptedException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getLabelJob(RekognitionClient rekClient, SqsClient sqs,
String queueUrl) {
        List<Message> messages;
        ReceiveMessageRequest messageRequest = ReceiveMessageRequest.builder()
                .queueUrl(queueUrl)
                .build();

        try {
            messages = sqs.receiveMessage(messageRequest).messages();

            if (!messages.isEmpty()) {
                for (Message message : messages) {
                    String notification = message.body();

                    // Get the status and job id from the notification
                    ObjectMapper mapper = new ObjectMapper();
                    JsonNode jsonMessageTree = mapper.readTree(notification);
                    JsonNode messageBodyText = jsonMessageTree.get("Message");
                    ObjectMapper operationResultMapper = new ObjectMapper();
                    JsonNode jsonResultTree =
operationResultMapper.readTree(messageBodyText.textValue());
                    JsonNode operationJobId = jsonResultTree.get("JobId");
                    JsonNode operationStatus = jsonResultTree.get("Status");
                    System.out.println("Job found in JSON is " + operationJobId);

                    DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                            .queueUrl(queueUrl)
                            .build();

                    String jobId = operationJobId.textValue();
                    if (startJobId.compareTo(jobId) == 0) {
                        System.out.println("Job id: " + operationJobId);
```

```
                        System.out.println("Status : " +
operationStatus.toString());

                        if (operationStatus.asText().equals("SUCCEEDED"))
                            getResultsLabels(rekClient);
                        else
                            System.out.println("Video analysis failed");

                        sqs.deleteMessage(deleteMessageRequest);
                    } else {
                        System.out.println("Job received was not job " +
startJobId);
                        sqs.deleteMessage(deleteMessageRequest);
                    }
                }
            }

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        } catch (JsonMappingException e) {
            e.printStackTrace();
        } catch (JsonProcessingException e) {
            e.printStackTrace();
        }
    }

    // Gets the job results by calling GetLabelDetection
    private static void getResultsLabels(RekognitionClient rekClient) {

        int maxResults = 10;
        String paginationToken = null;
        GetLabelDetectionResponse labelDetectionResult = null;

        try {
            do {
                if (labelDetectionResult != null)
                    paginationToken = labelDetectionResult.nextToken();

                GetLabelDetectionRequest labelDetectionRequest =
GetLabelDetectionRequest.builder()
                        .jobId(startJobId)
                        .sortBy(LabelDetectionSortBy.TIMESTAMP)
                        .maxResults(maxResults)
```

```
                        .nextToken(paginationToken)
                        .build();

                labelDetectionResult =
rekClient.getLabelDetection(labelDetectionRequest);
                VideoMetadata videoMetaData = labelDetectionResult.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());

                List<LabelDetection> detectedLabels = labelDetectionResult.labels();
                for (LabelDetection detectedLabel : detectedLabels) {
                    long seconds = detectedLabel.timestamp();
                    Label label = detectedLabel.label();
                    System.out.println("Millisecond: " + seconds + " ");

                    System.out.println("   Label:" + label.name());
                    System.out.println("   Confidence:" +
detectedLabel.label().confidence().toString());

                    List<Instance> instances = label.instances();
                    System.out.println("   Instances of " + label.name());

                    if (instances.isEmpty()) {
                        System.out.println("        " + "None");
                    } else {
                        for (Instance instance : instances) {
                            System.out.println("        Confidence: " +
instance.confidence().toString());
                            System.out.println("        Bounding box: " +
instance.boundingBox().toString());
                        }
                    }
                    System.out.println("   Parent labels for " + label.name() +
":");
                    List<Parent> parents = label.parents();

                    if (parents.isEmpty()) {
                        System.out.println("        None");
                    } else {
                        for (Parent parent : parents) {
                            System.out.println("   " + parent.name());
                        }
```

```
                    }
                    System.out.println();
                }
            } while (labelDetectionResult != null &&
 labelDetectionResult.nextToken() != null);

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }
}
```

Detectar conteúdo inapropriado ou ofensivo em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartContentModerationRequest;
import
 software.amazon.awssdk.services.rekognition.model.StartContentModerationResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetContentModerationResponse;
import
 software.amazon.awssdk.services.rekognition.model.GetContentModerationRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.ContentModerationDetection;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
```

```
public class VideoDetectInappropriate {
    private static String startJobId = "";

    public static void main(String[] args) {

        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management (IAM)
 role to use.\s
                """;

       if (args.length != 4) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucket = args[0];
       String video = args[1];
       String topicArn = args[2];
       String roleArn = args[3];
       Region region = Region.US_EAST_1;
       RekognitionClient rekClient = RekognitionClient.builder()
               .region(region)
               .build();

       NotificationChannel channel = NotificationChannel.builder()
               .snsTopicArn(topicArn)
               .roleArn(roleArn)
               .build();

       startModerationDetection(rekClient, channel, bucket, video);
       getModResults(rekClient);
       System.out.println("This example is done!");
       rekClient.close();
    }
```

```
    public static void startModerationDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {

        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartContentModerationRequest modDetectionRequest =
StartContentModerationRequest.builder()
                    .jobTag("Moderation")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();

            StartContentModerationResponse startModDetectionResult = rekClient
                    .startContentModeration(modDetectionRequest);
            startJobId = startModDetectionResult.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getModResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetContentModerationResponse modDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (modDetectionResponse != null)
                    paginationToken = modDetectionResponse.nextToken();
```

```
                GetContentModerationRequest modRequest =
GetContentModerationRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds.
                while (!finished) {
                    modDetectionResponse =
rekClient.getContentModeration(modRequest);
                    status = modDetectionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is null.
                VideoMetadata videoMetaData = modDetectionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<ContentModerationDetection> mods =
modDetectionResponse.moderationLabels();
                for (ContentModerationDetection mod : mods) {
                    long seconds = mod.timestamp() / 1000;
                    System.out.print("Mod label: " + seconds + " ");
                    System.out.println(mod.moderationLabel().toString());
                    System.out.println();
                }

            } while (modDetectionResponse != null &&
modDetectionResponse.nextToken() != null);
```

```
        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar segmentos de sinal técnico e segmentos de detecção de tomada em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import software.amazon.awssdk.services.rekognition.model.StartShotDetectionFilter;
import
 software.amazon.awssdk.services.rekognition.model.StartTechnicalCueDetectionFilter;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionFilters;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionRequest;
import
 software.amazon.awssdk.services.rekognition.model.StartSegmentDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import
 software.amazon.awssdk.services.rekognition.model.GetSegmentDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.GetSegmentDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.SegmentDetection;
import software.amazon.awssdk.services.rekognition.model.TechnicalCueSegment;
import software.amazon.awssdk.services.rekognition.model.ShotSegment;
import software.amazon.awssdk.services.rekognition.model.SegmentType;
import software.amazon.awssdk.services.sqs.SqsClient;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class VideoDetectSegment {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
 (for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
 (Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management (IAM)
 role to use.\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucket = args[0];
        String video = args[1];
        String topicArn = args[2];
        String roleArn = args[3];

        Region region = Region.US_EAST_1;
        RekognitionClient rekClient = RekognitionClient.builder()
                .region(region)
                .build();

        SqsClient sqs = SqsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        NotificationChannel channel = NotificationChannel.builder()
                .snsTopicArn(topicArn)
                .roleArn(roleArn)
                .build();
```

```
        startSegmentDetection(rekClient, channel, bucket, video);
        getSegmentResults(rekClient);
        System.out.println("This example is done!");
        sqs.close();
        rekClient.close();
    }

    public static void startSegmentDetection(RekognitionClient rekClient,
            NotificationChannel channel,
            String bucket,
            String video) {
        try {
            S3Object s3Obj = S3Object.builder()
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartShotDetectionFilter cueDetectionFilter =
StartShotDetectionFilter.builder()
                    .minSegmentConfidence(60F)
                    .build();

            StartTechnicalCueDetectionFilter technicalCueDetectionFilter =
StartTechnicalCueDetectionFilter.builder()
                    .minSegmentConfidence(60F)
                    .build();

            StartSegmentDetectionFilters filters =
StartSegmentDetectionFilters.builder()
                    .shotFilter(cueDetectionFilter)
                    .technicalCueFilter(technicalCueDetectionFilter)
                    .build();

            StartSegmentDetectionRequest segDetectionRequest =
StartSegmentDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .segmentTypes(SegmentType.TECHNICAL_CUE, SegmentType.SHOT)
                    .video(vidOb)
                    .filters(filters)
```

```
                    .build();

            StartSegmentDetectionResponse segDetectionResponse =
rekClient.startSegmentDetection(segDetectionRequest);
            startJobId = segDetectionResponse.jobId();

        } catch (RekognitionException e) {
            e.getMessage();
            System.exit(1);
        }
    }

    public static void getSegmentResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetSegmentDetectionResponse segDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (segDetectionResponse != null)
                    paginationToken = segDetectionResponse.nextToken();

                GetSegmentDetectionRequest recognitionRequest =
GetSegmentDetectionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds.
                while (!finished) {
                    segDetectionResponse =
rekClient.getSegmentDetection(recognitionRequest);
                    status = segDetectionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
```

```
                }
                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is null.
                List<VideoMetadata> videoMetaData =
segDetectionResponse.videoMetadata();
                for (VideoMetadata metaData : videoMetaData) {
                    System.out.println("Format: " + metaData.format());
                    System.out.println("Codec: " + metaData.codec());
                    System.out.println("Duration: " + metaData.durationMillis());
                    System.out.println("FrameRate: " + metaData.frameRate());
                    System.out.println("Job");
                }

                List<SegmentDetection> detectedSegments =
segDetectionResponse.segments();
                for (SegmentDetection detectedSegment : detectedSegments) {
                    String type = detectedSegment.type().toString();
                    if (type.contains(SegmentType.TECHNICAL_CUE.toString())) {
                        System.out.println("Technical Cue");
                        TechnicalCueSegment segmentCue =
detectedSegment.technicalCueSegment();
                        System.out.println("\tType: " + segmentCue.type());
                        System.out.println("\tConfidence: " +
segmentCue.confidence().toString());
                    }

                    if (type.contains(SegmentType.SHOT.toString())) {
                        System.out.println("Shot");
                        ShotSegment segmentShot = detectedSegment.shotSegment();
                        System.out.println("\tIndex " + segmentShot.index());
                        System.out.println("\tConfidence: " +
segmentShot.confidence().toString());
                    }

                    long seconds = detectedSegment.durationMillis();
                    System.out.println("\tDuration : " + seconds + " milliseconds");
                    System.out.println("\tStart time code: " +
detectedSegment.startTimecodeSMPTE());
                    System.out.println("\tEnd time code: " +
detectedSegment.endTimecodeSMPTE());
                    System.out.println("\tDuration time code: " +
detectedSegment.durationSMPTE());
                    System.out.println();
```

```
                }

            } while (segDetectionResponse != null &&
 segDetectionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar texto em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.Video;
import software.amazon.awssdk.services.rekognition.model.StartTextDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.StartTextDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.GetTextDetectionResponse;
import software.amazon.awssdk.services.rekognition.model.GetTextDetectionRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.TextDetectionResult;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class VideoDetectText {
    private static String startJobId = "";

    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
                   bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                   video - The name of video (for example, people.mp4).\s
                   topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                   roleArn - The ARN of the AWS Identity and Access Management (IAM)
role to use.\s
                """;

       if (args.length != 4) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucket = args[0];
       String video = args[1];
       String topicArn = args[2];
       String roleArn = args[3];

       Region region = Region.US_EAST_1;
       RekognitionClient rekClient = RekognitionClient.builder()
               .region(region)
               .build();

       NotificationChannel channel = NotificationChannel.builder()
               .snsTopicArn(topicArn)
               .roleArn(roleArn)
               .build();

       startTextLabels(rekClient, channel, bucket, video);
       getTextResults(rekClient);
       System.out.println("This example is done!");
       rekClient.close();
   }

   public static void startTextLabels(RekognitionClient rekClient,
           NotificationChannel channel,
           String bucket,
           String video) {
       try {
           S3Object s3Obj = S3Object.builder()
```

```
                    .bucket(bucket)
                    .name(video)
                    .build();

            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartTextDetectionRequest labelDetectionRequest =
StartTextDetectionRequest.builder()
                    .jobTag("DetectingLabels")
                    .notificationChannel(channel)
                    .video(vidOb)
                    .build();

            StartTextDetectionResponse labelDetectionResponse =
rekClient.startTextDetection(labelDetectionRequest);
            startJobId = labelDetectionResponse.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getTextResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetTextDetectionResponse textDetectionResponse = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (textDetectionResponse != null)
                    paginationToken = textDetectionResponse.nextToken();

                GetTextDetectionRequest recognitionRequest =
GetTextDetectionRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();
```

```
                // Wait until the job succeeds.
                while (!finished) {
                    textDetectionResponse =
rekClient.getTextDetection(recognitionRequest);
                    status = textDetectionResponse.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is null.
                VideoMetadata videoMetaData = textDetectionResponse.videoMetadata();
                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<TextDetectionResult> labels =
textDetectionResponse.textDetections();
                for (TextDetectionResult detectedText : labels) {
                    System.out.println("Confidence: " +
detectedText.textDetection().confidence().toString());
                    System.out.println("Id : " + detectedText.textDetection().id());
                    System.out.println("Parent Id: " +
detectedText.textDetection().parentId());
                    System.out.println("Type: " +
detectedText.textDetection().type());
                    System.out.println("Text: " +
detectedText.textDetection().detectedText());
                    System.out.println();
                }

            } while (textDetectionResponse != null &&
textDetectionResponse.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
```

```
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detecte pessoas em um vídeo armazenado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.rekognition.RekognitionClient;
import software.amazon.awssdk.services.rekognition.model.S3Object;
import software.amazon.awssdk.services.rekognition.model.NotificationChannel;
import software.amazon.awssdk.services.rekognition.model.StartPersonTrackingRequest;
import software.amazon.awssdk.services.rekognition.model.Video;
import
 software.amazon.awssdk.services.rekognition.model.StartPersonTrackingResponse;
import software.amazon.awssdk.services.rekognition.model.RekognitionException;
import software.amazon.awssdk.services.rekognition.model.GetPersonTrackingResponse;
import software.amazon.awssdk.services.rekognition.model.GetPersonTrackingRequest;
import software.amazon.awssdk.services.rekognition.model.VideoMetadata;
import software.amazon.awssdk.services.rekognition.model.PersonDetection;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class VideoPersonDetection {
    private static String startJobId = "";

    public static void main(String[] args) {

        final String usage = """

                Usage:    <bucket> <video> <topicArn> <roleArn>

                Where:
```

```
                  bucket - The name of the bucket in which the video is located
(for example, (for example, myBucket).\s
                  video - The name of video (for example, people.mp4).\s
                  topicArn - The ARN of the Amazon Simple Notification Service
(Amazon SNS) topic.\s
                  roleArn - The ARN of the AWS Identity and Access Management (IAM)
role to use.\s
               """;

       if (args.length != 4) {
           System.out.println(usage);
           System.exit(1);
       }

       String bucket = args[0];
       String video = args[1];
       String topicArn = args[2];
       String roleArn = args[3];
       Region region = Region.US_EAST_1;
       RekognitionClient rekClient = RekognitionClient.builder()
               .region(region)
               .build();

       NotificationChannel channel = NotificationChannel.builder()
               .snsTopicArn(topicArn)
               .roleArn(roleArn)
               .build();

       startPersonLabels(rekClient, channel, bucket, video);
       getPersonDetectionResults(rekClient);
       System.out.println("This example is done!");
       rekClient.close();
   }

   public static void startPersonLabels(RekognitionClient rekClient,
           NotificationChannel channel,
           String bucket,
           String video) {
       try {
           S3Object s3Obj = S3Object.builder()
                   .bucket(bucket)
                   .name(video)
                   .build();
```

```
            Video vidOb = Video.builder()
                    .s3Object(s3Obj)
                    .build();

            StartPersonTrackingRequest personTrackingRequest =
StartPersonTrackingRequest.builder()
                    .jobTag("DetectingLabels")
                    .video(vidOb)
                    .notificationChannel(channel)
                    .build();

            StartPersonTrackingResponse labelDetectionResponse =
rekClient.startPersonTracking(personTrackingRequest);
            startJobId = labelDetectionResponse.jobId();

        } catch (RekognitionException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getPersonDetectionResults(RekognitionClient rekClient) {
        try {
            String paginationToken = null;
            GetPersonTrackingResponse personTrackingResult = null;
            boolean finished = false;
            String status;
            int yy = 0;

            do {
                if (personTrackingResult != null)
                    paginationToken = personTrackingResult.nextToken();

                GetPersonTrackingRequest recognitionRequest =
GetPersonTrackingRequest.builder()
                        .jobId(startJobId)
                        .nextToken(paginationToken)
                        .maxResults(10)
                        .build();

                // Wait until the job succeeds
                while (!finished) {
```

```
                    personTrackingResult =
 rekClient.getPersonTracking(recognitionRequest);
                    status = personTrackingResult.jobStatusAsString();

                    if (status.compareTo("SUCCEEDED") == 0)
                        finished = true;
                    else {
                        System.out.println(yy + " status is: " + status);
                        Thread.sleep(1000);
                    }
                    yy++;
                }

                finished = false;

                // Proceed when the job is done - otherwise VideoMetadata is null.
                VideoMetadata videoMetaData = personTrackingResult.videoMetadata();

                System.out.println("Format: " + videoMetaData.format());
                System.out.println("Codec: " + videoMetaData.codec());
                System.out.println("Duration: " + videoMetaData.durationMillis());
                System.out.println("FrameRate: " + videoMetaData.frameRate());
                System.out.println("Job");

                List<PersonDetection> detectedPersons =
 personTrackingResult.persons();
                for (PersonDetection detectedPerson : detectedPersons) {
                    long seconds = detectedPerson.timestamp() / 1000;
                    System.out.print("Sec: " + seconds + " ");
                    System.out.println("Person Identifier: " +
 detectedPerson.person().index());
                    System.out.println();
                }

            } while (personTrackingResult != null &&
 personTrackingResult.nextToken() != null);

        } catch (RekognitionException | InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetCelebrityRecognition
  - GetContentModeration
  - GetLabelDetection
  - GetPersonTracking
  - GetSegmentDetection
  - GetTextDetection
  - StartCelebrityRecognition
  - StartContentModeration
  - StartLabelDetection
  - StartPersonTracking
  - StartSegmentDetection
  - StartTextDetection

Exemplos de registro de domínios do Route 53 usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o registro de domínios do Route 53.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Registro de domínios do Hello Route 53

O exemplo de código a seguir mostra como começar a usar o registro de domínios do Route 53.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.route53domains.Route53DomainsClient;
import software.amazon.awssdk.services.route53.model.Route53Exception;
import software.amazon.awssdk.services.route53domains.model.DomainPrice;
import software.amazon.awssdk.services.route53domains.model.ListPricesRequest;
import software.amazon.awssdk.services.route53domains.model.ListPricesResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java code examples performs the following operation:
 *
 * 1. Invokes ListPrices for at least one domain type, such as the “com” type
 * and displays the prices for Registration and Renewal.
 *
 */
public class HelloRoute53 {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) {
        final String usage = "\n" +
                "Usage:\n" +
                "    <hostedZoneId> \n\n" +
                "Where:\n" +
                "    hostedZoneId - The id value of an existing hosted zone. \n";

        if (args.length != 1) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String domainType = args[0];
        Region region = Region.US_EAST_1;
        Route53DomainsClient route53DomainsClient = Route53DomainsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Invokes ListPrices for at least one domain type.");
        listPrices(route53DomainsClient, domainType);
        System.out.println(DASHES);
    }

    public static void listPrices(Route53DomainsClient route53DomainsClient, String
domainType) {
        try {
            ListPricesRequest pricesRequest = ListPricesRequest.builder()
                    .maxItems(10)
                    .tld(domainType)
                    .build();

            ListPricesResponse response =
route53DomainsClient.listPrices(pricesRequest);
            List<DomainPrice> prices = response.prices();
            for (DomainPrice pr : prices) {
                System.out.println("Name: " + pr.name());
                System.out.println(
                        "Registration: " + pr.registrationPrice().price() + " " +
pr.registrationPrice().currency());
                System.out.println("Renewal: " + pr.renewalPrice().price() + " " +
pr.renewalPrice().currency());
                System.out.println("Transfer: " + pr.transferPrice().price() + " " +
pr.transferPrice().currency());
                System.out.println("Transfer: " + pr.transferPrice().price() + " " +
pr.transferPrice().currency());
                System.out.println("Change Ownership: " +
pr.changeOwnershipPrice().price() + " "
                        + pr.changeOwnershipPrice().currency());
                System.out.println(
                        "Restoration: " + pr.restorationPrice().price() + " " +
pr.restorationPrice().currency());
                System.out.println(" ");
```

```
            }

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Verificar disponibilidade de domínios

O exemplo de código a seguir mostra como verificar a disponibilidade de um domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void checkDomainAvailability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainAvailabilityRequest availabilityRequest =
CheckDomainAvailabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainAvailabilityResponse response = route53DomainsClient
                    .checkDomainAvailability(availabilityRequest);
```

```
            System.out.println(domainSuggestion + " is " +
response.availability().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte CheckDomainAvailabilitya Referência AWS SDK for Java 2.x da API.

Verificar a transferibilidade de um domínio

O exemplo de código a seguir mostra como verificar o potencial para transferência de um domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void checkDomainTransferability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainTransferabilityRequest transferabilityRequest =
CheckDomainTransferabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainTransferabilityResponse response = route53DomainsClient
                    .checkDomainTransferability(transferabilityRequest);
            System.out.println("Transferability: " +
response.transferability().transferable().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
```

```
        }
    }
```

- Para obter detalhes da API, consulte CheckDomainTransferabilitya Referência AWS SDK for Java 2.x da API.

Obter detalhes de um domínio

O exemplo de código a seguir mostra como obter os detalhes de um domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getDomainDetails(Route53DomainsClient route53DomainsClient,
String domainSuggestion) {
       try {
           GetDomainDetailRequest detailRequest = GetDomainDetailRequest.builder()
                   .domainName(domainSuggestion)
                   .build();

           GetDomainDetailResponse response =
route53DomainsClient.getDomainDetail(detailRequest);
           System.out.println("The contact first name is " +
response.registrantContact().firstName());
           System.out.println("The contact last name is " +
response.registrantContact().lastName());
           System.out.println("The contact org name is " +
response.registrantContact().organizationName());

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetDomainDetaila Referência AWS SDK for Java 2.x da API.

Obter detalhes de uma operação

O exemplo de código a seguir mostra como obter os detalhes de uma operação.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void getOperationalDetail(Route53DomainsClient
route53DomainsClient, String operationId) {
       try {
           GetOperationDetailRequest detailRequest =
GetOperationDetailRequest.builder()
                   .operationId(operationId)
                   .build();

           GetOperationDetailResponse response =
route53DomainsClient.getOperationDetail(detailRequest);
           System.out.println("Operation detail message is " + response.message());

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetOperationDetaila Referência AWS SDK for Java 2.x da API.

Obter nomes de domínio sugeridos

O exemplo de código a seguir mostra como obter sugestões de nomes de domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listDomainSuggestions(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
       try {
           GetDomainSuggestionsRequest suggestionsRequest =
GetDomainSuggestionsRequest.builder()
                   .domainName(domainSuggestion)
                   .suggestionCount(5)
                   .onlyAvailable(true)
                   .build();

           GetDomainSuggestionsResponse response =
route53DomainsClient.getDomainSuggestions(suggestionsRequest);
           List<DomainSuggestion> suggestions = response.suggestionsList();
           for (DomainSuggestion suggestion : suggestions) {
               System.out.println("Suggestion Name: " + suggestion.domainName());
               System.out.println("Availability: " + suggestion.availability());
               System.out.println(" ");
           }

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte GetDomainSuggestionsa Referência AWS SDK for Java 2.x da API.

Listar preços de domínios

O exemplo de código a seguir mostra como listar preços de domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listPrices(Route53DomainsClient route53DomainsClient, String
domainType) {
       try {
           ListPricesRequest pricesRequest = ListPricesRequest.builder()
                   .tld(domainType)
                   .build();

           ListPricesIterable listRes =
route53DomainsClient.listPricesPaginator(pricesRequest);
           listRes.stream()
                   .flatMap(r -> r.prices().stream())
                   .forEach(content -> System.out.println(" Name: " +
content.name() +
                           " Registration: " + content.registrationPrice().price()
+ " "
                           + content.registrationPrice().currency() +
                           " Renewal: " + content.renewalPrice().price() + " " +
content.renewalPrice().currency()));

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ListPricesa Referência AWS SDK for Java 2.x da API.

Listar domínios

O exemplo de código a seguir mostra como listar os domínios registrados.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listDomains(Route53DomainsClient route53DomainsClient) {
        try {
            ListDomainsIterable listRes =
route53DomainsClient.listDomainsPaginator();
            listRes.stream()
                    .flatMap(r -> r.domains().stream())
                    .forEach(content -> System.out.println("The domain name is " +
content.domainName()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListDomainsa Referência AWS SDK for Java 2.x da API.

Operações de lista

O exemplo de código a seguir mostra como listar operações.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void listOperations(Route53DomainsClient route53DomainsClient) {
        try {
```

```
            Date currentDate = new Date();
            LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
            ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
            localDateTime = localDateTime.minusYears(1);
            Instant myTime = localDateTime.toInstant(zoneOffset);

            ListOperationsRequest operationsRequest =
ListOperationsRequest.builder()
                    .submittedSince(myTime)
                    .build();

            ListOperationsIterable listRes =
route53DomainsClient.listOperationsPaginator(operationsRequest);
            listRes.stream()
                    .flatMap(r -> r.operations().stream())
                    .forEach(content -> System.out.println(" Operation Id: " +
content.operationId() +
                            " Status: " + content.statusAsString() +
                            " Date: " + content.submittedDate()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListOperationsa Referência AWS SDK for Java 2.x da API.

Registrar um domínio

O exemplo de código a seguir mostra como registrar um domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String requestDomainRegistration(Route53DomainsClient
route53DomainsClient,
           String domainSuggestion,
           String phoneNumber,
           String email,
           String firstName,
           String lastName,
           String city) {

       try {
           ContactDetail contactDetail = ContactDetail.builder()
                   .contactType(ContactType.COMPANY)
                   .state("LA")
                   .countryCode(CountryCode.IN)
                   .email(email)
                   .firstName(firstName)
                   .lastName(lastName)
                   .city(city)
                   .phoneNumber(phoneNumber)
                   .organizationName("My Org")
                   .addressLine1("My Address")
                   .zipCode("123 123")
                   .build();

           RegisterDomainRequest domainRequest = RegisterDomainRequest.builder()
                   .adminContact(contactDetail)
                   .registrantContact(contactDetail)
                   .techContact(contactDetail)
                   .domainName(domainSuggestion)
                   .autoRenew(true)
                   .durationInYears(1)
                   .build();

           RegisterDomainResponse response =
route53DomainsClient.registerDomain(domainRequest);
           System.out.println("Registration requested. Operation Id: " +
response.operationId());
           return response.operationId();

       } catch (Route53Exception e) {
           System.err.println(e.getMessage());
           System.exit(1);
       }
```

```
        return "";
    }
```

- Para obter detalhes da API, consulte RegisterDomaina Referência AWS SDK for Java 2.x da API.

Exibir faturamento

O exemplo de código a seguir mostra como visualizar registros de cobrança.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void listBillingRecords(Route53DomainsClient route53DomainsClient)
{
       try {
           Date currentDate = new Date();
           LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
           ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
           LocalDateTime localDateTime2 = localDateTime.minusYears(1);
           Instant myStartTime = localDateTime2.toInstant(zoneOffset);
           Instant myEndTime = localDateTime.toInstant(zoneOffset);

           ViewBillingRequest viewBillingRequest = ViewBillingRequest.builder()
                   .start(myStartTime)
                   .end(myEndTime)
                   .build();

           ViewBillingIterable listRes =
route53DomainsClient.viewBillingPaginator(viewBillingRequest);
           listRes.stream()
                   .flatMap(r -> r.billingRecords().stream())
                   .forEach(content -> System.out.println(" Bill Date:: " +
content.billDate() +
                           " Operation: " + content.operationAsString() +
```

```
                            " Price: " + content.price()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ViewBillinga Referência AWS SDK for Java 2.x da API.

Cenários

Conceitos básicos de domínios

O código de exemplo a seguir mostra como:

- Liste os domínios atuais e as operações do ano passado.
- Veja o faturamento do ano passado e os preços dos tipos de domínio.
- Receba sugestões de domínio.
- Verifique a disponibilidade e a transferibilidade de um domínio.
- Opcionalmente, solicite o registro de um domínio.
- Obtenha os detalhes de uma operação.
- Opcionalmente, obtenha os detalhes de um domínio.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This example uses pagination methods where applicable. For example, to list
 * domains, the
 * listDomainsPaginator method is used. For more information about pagination,
 * see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/pagination.html
 *
 * This Java code example performs the following operations:
 *
 * 1. List current domains.
 * 2. List operations in the past year.
 * 3. View billing for the account in the past year.
 * 4. View prices for domain types.
 * 5. Get domain suggestions.
 * 6. Check domain availability.
 * 7. Check domain transferability.
 * 8. Request a domain registration.
 * 9. Get operation details.
 * 10. Optionally, get domain details.
 */

public class Route53Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <domainType> <phoneNumber> <email> <domainSuggestion>
 <firstName> <lastName> <city>

                Where:
                    domainType - The domain type (for example, com).\s
                    phoneNumber - The phone number to use (for example,
 +91.9966564xxx)      email - The email address to use.      domainSuggestion - The
 domain suggestion (for example, findmy.accountants).\s
                    firstName - The first name to use to register a domain.\s
                    lastName -  The last name to use to register a domain.\s
                    city - the city to use to register a domain.\s
                    """;
```

```
        if (args.length != 7) {
            System.out.println(usage);
            System.exit(1);
        }

        String domainType = args[0];
        String phoneNumber = args[1];
        String email = args[2];
        String domainSuggestion = args[3];
        String firstName = args[4];
        String lastName = args[5];
        String city = args[6];
        Region region = Region.US_EAST_1;
        Route53DomainsClient route53DomainsClient = Route53DomainsClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon Route 53 domains example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. List current domains.");
        listDomains(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. List operations in the past year.");
        listOperations(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. View billing for the account in the past year.");
        listBillingRecords(route53DomainsClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. View prices for domain types.");
        listPrices(route53DomainsClient, domainType);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Get domain suggestions.");
```

```
        listDomainSuggestions(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Check domain availability.");
        checkDomainAvailability(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Check domain transferability.");
        checkDomainTransferability(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Request a domain registration.");
        String opId = requestDomainRegistration(route53DomainsClient,
domainSuggestion, phoneNumber, email, firstName,
                lastName, city);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Get operation details.");
        getOperationalDetail(route53DomainsClient, opId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get domain details.");
        System.out.println("Note: You must have a registered domain to get
details.");
        System.out.println("Otherwise, an exception is thrown that states ");
        System.out.println("Domain xxxxxxx not found in xxxxxxx account.");
        getDomainDetails(route53DomainsClient, domainSuggestion);
        System.out.println(DASHES);
    }

    public static void getDomainDetails(Route53DomainsClient route53DomainsClient,
String domainSuggestion) {
        try {
            GetDomainDetailRequest detailRequest = GetDomainDetailRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            GetDomainDetailResponse response =
route53DomainsClient.getDomainDetail(detailRequest);
```

```
            System.out.println("The contact first name is " +
 response.registrantContact().firstName());
            System.out.println("The contact last name is " +
 response.registrantContact().lastName());
            System.out.println("The contact org name is " +
 response.registrantContact().organizationName());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void getOperationalDetail(Route53DomainsClient
 route53DomainsClient, String operationId) {
        try {
            GetOperationDetailRequest detailRequest =
 GetOperationDetailRequest.builder()
                    .operationId(operationId)
                    .build();

            GetOperationDetailResponse response =
 route53DomainsClient.getOperationDetail(detailRequest);
            System.out.println("Operation detail message is " + response.message());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static String requestDomainRegistration(Route53DomainsClient
 route53DomainsClient,
            String domainSuggestion,
            String phoneNumber,
            String email,
            String firstName,
            String lastName,
            String city) {

        try {
            ContactDetail contactDetail = ContactDetail.builder()
                    .contactType(ContactType.COMPANY)
                    .state("LA")
```

```
                    .countryCode(CountryCode.IN)
                    .email(email)
                    .firstName(firstName)
                    .lastName(lastName)
                    .city(city)
                    .phoneNumber(phoneNumber)
                    .organizationName("My Org")
                    .addressLine1("My Address")
                    .zipCode("123 123")
                    .build();

            RegisterDomainRequest domainRequest = RegisterDomainRequest.builder()
                    .adminContact(contactDetail)
                    .registrantContact(contactDetail)
                    .techContact(contactDetail)
                    .domainName(domainSuggestion)
                    .autoRenew(true)
                    .durationInYears(1)
                    .build();

            RegisterDomainResponse response =
route53DomainsClient.registerDomain(domainRequest);
            System.out.println("Registration requested. Operation Id: " +
response.operationId());
            return response.operationId();

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }

    public static void checkDomainTransferability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainTransferabilityRequest transferabilityRequest =
CheckDomainTransferabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainTransferabilityResponse response = route53DomainsClient
                    .checkDomainTransferability(transferabilityRequest);
```

```
            System.out.println("Transferability: " +
response.transferability().transferable().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void checkDomainAvailability(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            CheckDomainAvailabilityRequest availabilityRequest =
CheckDomainAvailabilityRequest.builder()
                    .domainName(domainSuggestion)
                    .build();

            CheckDomainAvailabilityResponse response = route53DomainsClient
                    .checkDomainAvailability(availabilityRequest);
            System.out.println(domainSuggestion + " is " +
response.availability().toString());

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listDomainSuggestions(Route53DomainsClient
route53DomainsClient, String domainSuggestion) {
        try {
            GetDomainSuggestionsRequest suggestionsRequest =
GetDomainSuggestionsRequest.builder()
                    .domainName(domainSuggestion)
                    .suggestionCount(5)
                    .onlyAvailable(true)
                    .build();

            GetDomainSuggestionsResponse response =
route53DomainsClient.getDomainSuggestions(suggestionsRequest);
            List<DomainSuggestion> suggestions = response.suggestionsList();
            for (DomainSuggestion suggestion : suggestions) {
                System.out.println("Suggestion Name: " + suggestion.domainName());
                System.out.println("Availability: " + suggestion.availability());
```

```
                System.out.println(" ");
            }

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listPrices(Route53DomainsClient route53DomainsClient, String
domainType) {
        try {
            ListPricesRequest pricesRequest = ListPricesRequest.builder()
                    .tld(domainType)
                    .build();

            ListPricesIterable listRes =
route53DomainsClient.listPricesPaginator(pricesRequest);
            listRes.stream()
                    .flatMap(r -> r.prices().stream())
                    .forEach(content -> System.out.println(" Name: " +
content.name() +
                            " Registration: " + content.registrationPrice().price()
+ " "
                            + content.registrationPrice().currency() +
                            " Renewal: " + content.renewalPrice().price() + " " +
content.renewalPrice().currency()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listBillingRecords(Route53DomainsClient route53DomainsClient)
{
        try {
            Date currentDate = new Date();
            LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
            ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
            LocalDateTime localDateTime2 = localDateTime.minusYears(1);
            Instant myStartTime = localDateTime2.toInstant(zoneOffset);
            Instant myEndTime = localDateTime.toInstant(zoneOffset);
```

```
            ViewBillingRequest viewBillingRequest = ViewBillingRequest.builder()
                    .start(myStartTime)
                    .end(myEndTime)
                    .build();

            ViewBillingIterable listRes =
route53DomainsClient.viewBillingPaginator(viewBillingRequest);
            listRes.stream()
                    .flatMap(r -> r.billingRecords().stream())
                    .forEach(content -> System.out.println(" Bill Date:: " +
content.billDate() +
                            " Operation: " + content.operationAsString() +
                            " Price: " + content.price()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listOperations(Route53DomainsClient route53DomainsClient) {
        try {
            Date currentDate = new Date();
            LocalDateTime localDateTime =
currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime();
            ZoneOffset zoneOffset = ZoneOffset.of("+01:00");
            localDateTime = localDateTime.minusYears(1);
            Instant myTime = localDateTime.toInstant(zoneOffset);

            ListOperationsRequest operationsRequest =
ListOperationsRequest.builder()
                    .submittedSince(myTime)
                    .build();

            ListOperationsIterable listRes =
route53DomainsClient.listOperationsPaginator(operationsRequest);
            listRes.stream()
                    .flatMap(r -> r.operations().stream())
                    .forEach(content -> System.out.println(" Operation Id: " +
content.operationId() +
                            " Status: " + content.statusAsString() +
                            " Date: " + content.submittedDate()));
```

```
        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void listDomains(Route53DomainsClient route53DomainsClient) {
        try {
            ListDomainsIterable listRes =
 route53DomainsClient.listDomainsPaginator();
            listRes.stream()
                    .flatMap(r -> r.domains().stream())
                    .forEach(content -> System.out.println("The domain name is " +
 content.domainName()));

        } catch (Route53Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Exemplos do Amazon S3 usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Java 2.x com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.Bucket;
import software.amazon.awssdk.services.s3.model.ListBucketsResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloS3 {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBuckets(s3);
    }

    public static void listBuckets(S3Client s3) {
        try {
            ListBucketsResponse response = s3.listBuckets();
            List<Bucket> bucketList = response.buckets();
            bucketList.forEach(bucket -> {
                System.out.println("Bucket Name: " + bucket.name());
            });

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Adicionar regras de CORS a um bucket

O exemplo de código a seguir mostra como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import java.util.ArrayList;
import java.util.List;
import software.amazon.awssdk.services.s3.model.GetBucketCorsRequest;
import software.amazon.awssdk.services.s3.model.GetBucketCorsResponse;
import software.amazon.awssdk.services.s3.model.DeleteBucketCorsRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.CORSRule;
import software.amazon.awssdk.services.s3.model.CORSConfiguration;
import software.amazon.awssdk.services.s3.model.PutBucketCorsRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class S3Cors {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <accountId>\s

                Where:
                    bucketName - The Amazon S3 bucket to upload an object into.
                    accountId - The id of the account that owns the Amazon S3
 bucket.
                """;

        if (args.length != 2) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String accountId = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setCorsInformation(s3, bucketName, accountId);
        getBucketCorsInformation(s3, bucketName, accountId);
        deleteBucketCorsInformation(s3, bucketName, accountId);
        s3.close();
    }

    public static void deleteBucketCorsInformation(S3Client s3, String bucketName,
String accountId) {
        try {
            DeleteBucketCorsRequest bucketCorsRequest =
DeleteBucketCorsRequest.builder()
                    .bucket(bucketName)
                    .expectedBucketOwner(accountId)
                    .build();

            s3.deleteBucketCors(bucketCorsRequest);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void getBucketCorsInformation(S3Client s3, String bucketName,
String accountId) {
        try {
            GetBucketCorsRequest bucketCorsRequest = GetBucketCorsRequest.builder()
                    .bucket(bucketName)
                    .expectedBucketOwner(accountId)
                    .build();

            GetBucketCorsResponse corsResponse =
s3.getBucketCors(bucketCorsRequest);
```

```
            List<CORSRule> corsRules = corsResponse.corsRules();
            for (CORSRule rule : corsRules) {
                System.out.println("allowOrigins: " + rule.allowedOrigins());
                System.out.println("AllowedMethod: " + rule.allowedMethods());
            }

        } catch (S3Exception e) {

            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void setCorsInformation(S3Client s3, String bucketName, String
 accountId) {
        List<String> allowMethods = new ArrayList<>();
        allowMethods.add("PUT");
        allowMethods.add("POST");
        allowMethods.add("DELETE");

        List<String> allowOrigins = new ArrayList<>();
        allowOrigins.add("http://example.com");
        try {
            // Define CORS rules.
            CORSRule corsRule = CORSRule.builder()
                    .allowedMethods(allowMethods)
                    .allowedOrigins(allowOrigins)
                    .build();

            List<CORSRule> corsRules = new ArrayList<>();
            corsRules.add(corsRule);
            CORSConfiguration configuration = CORSConfiguration.builder()
                    .corsRules(corsRules)
                    .build();

            PutBucketCorsRequest putBucketCorsRequest =
 PutBucketCorsRequest.builder()
                    .bucket(bucketName)
                    .corsConfiguration(configuration)
                    .expectedBucketOwner(accountId)
                    .build();

            s3.putBucketCors(putBucketCorsRequest);
```

```
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for Java 2.x da API.

Adicionar uma configuração de ciclo de vida a um bucket

O exemplo de código a seguir mostra como adicionar a configuração de ciclo de vida a um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.LifecycleRuleFilter;
import software.amazon.awssdk.services.s3.model.Transition;
import
 software.amazon.awssdk.services.s3.model.GetBucketLifecycleConfigurationRequest;
import
 software.amazon.awssdk.services.s3.model.GetBucketLifecycleConfigurationResponse;
import software.amazon.awssdk.services.s3.model.DeleteBucketLifecycleRequest;
import software.amazon.awssdk.services.s3.model.TransitionStorageClass;
import software.amazon.awssdk.services.s3.model.LifecycleRule;
import software.amazon.awssdk.services.s3.model.ExpirationStatus;
import software.amazon.awssdk.services.s3.model.BucketLifecycleConfiguration;
import
 software.amazon.awssdk.services.s3.model.PutBucketLifecycleConfigurationRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.ArrayList;
```

```
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class LifecycleConfiguration {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                  <bucketName> <accountId>\s

                                Where:
                                  bucketName - The Amazon Simple Storage Service
 (Amazon S3) bucket to upload an object into.
                                  accountId - The id of the account that owns the
 Amazon S3 bucket.
                                """;

                if (args.length != 2) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String bucketName = args[0];
                String accountId = args[1];
                Region region = Region.US_EAST_1;
                S3Client s3 = S3Client.builder()
                                .region(region)
                                .build();

                setLifecycleConfig(s3, bucketName, accountId);
                getLifecycleConfig(s3, bucketName, accountId);
                deleteLifecycleConfig(s3, bucketName, accountId);
                System.out.println("You have successfully created, updated, and
 deleted a Lifecycle configuration");
                s3.close();
        }
```

```
       public static void setLifecycleConfig(S3Client s3, String bucketName, String
accountId) {
               try {
                       // Create a rule to archive objects with the
"glacierobjects/" prefix to Amazon
                       // S3 Glacier.
                       LifecycleRuleFilter ruleFilter =
LifecycleRuleFilter.builder()
                                       .prefix("glacierobjects/")
                                       .build();

                       Transition transition = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                       .days(0)
                                       .build();

                       LifecycleRule rule1 = LifecycleRule.builder()
                                       .id("Archive immediately rule")
                                       .filter(ruleFilter)
                                       .transitions(transition)
                                       .status(ExpirationStatus.ENABLED)
                                       .build();

                       // Create a second rule.
                       Transition transition2 = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                       .days(0)
                                       .build();

                       List<Transition> transitionList = new ArrayList<>();
                       transitionList.add(transition2);

                       LifecycleRuleFilter ruleFilter2 =
LifecycleRuleFilter.builder()
                                       .prefix("glacierobjects/")
                                       .build();

                       LifecycleRule rule2 = LifecycleRule.builder()
                                       .id("Archive and then delete rule")
                                       .filter(ruleFilter2)
                                       .transitions(transitionList)
```

```
                                        .status(ExpirationStatus.ENABLED)
                                        .build();

                        // Add the LifecycleRule objects to an ArrayList.
                        ArrayList<LifecycleRule> ruleList = new ArrayList<>();
                        ruleList.add(rule1);
                        ruleList.add(rule2);

                        BucketLifecycleConfiguration lifecycleConfiguration =
BucketLifecycleConfiguration.builder()
                                        .rules(ruleList)
                                        .build();

                        PutBucketLifecycleConfigurationRequest
putBucketLifecycleConfigurationRequest = PutBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)

.lifecycleConfiguration(lifecycleConfiguration)
                                        .expectedBucketOwner(accountId)
                                        .build();


s3.putBucketLifecycleConfiguration(putBucketLifecycleConfigurationRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }

        // Retrieve the configuration and add a new rule.
        public static void getLifecycleConfig(S3Client s3, String bucketName, String
accountId) {
                try {
                        GetBucketLifecycleConfigurationRequest
getBucketLifecycleConfigurationRequest = GetBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)
                                        .expectedBucketOwner(accountId)
                                        .build();

                        GetBucketLifecycleConfigurationResponse response = s3
```

```
.getBucketLifecycleConfiguration(getBucketLifecycleConfigurationRequest);
                        List<LifecycleRule> newList = new ArrayList<>();
                        List<LifecycleRule> rules = response.rules();
                        for (LifecycleRule rule : rules) {
                                newList.add(rule);
                        }

                        // Add a new rule with both a prefix predicate and a tag
predicate.
                        LifecycleRuleFilter ruleFilter =
LifecycleRuleFilter.builder()
                                        .prefix("YearlyDocuments/")
                                        .build();

                        Transition transition = Transition.builder()

.storageClass(TransitionStorageClass.GLACIER)
                                        .days(3650)
                                        .build();

                        LifecycleRule rule1 = LifecycleRule.builder()
                                        .id("NewRule")
                                        .filter(ruleFilter)
                                        .transitions(transition)
                                        .status(ExpirationStatus.ENABLED)
                                        .build();

                        // Add the new rule to the list.
                        newList.add(rule1);
                        BucketLifecycleConfiguration lifecycleConfiguration =
BucketLifecycleConfiguration.builder()
                                        .rules(newList)
                                        .build();

                        PutBucketLifecycleConfigurationRequest
putBucketLifecycleConfigurationRequest = PutBucketLifecycleConfigurationRequest
                                        .builder()
                                        .bucket(bucketName)

.lifecycleConfiguration(lifecycleConfiguration)
                                        .expectedBucketOwner(accountId)
                                        .build();
```

```
s3.putBucketLifecycleConfiguration(putBucketLifecycleConfigurationRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }

        // Delete the configuration from the Amazon S3 bucket.
        public static void deleteLifecycleConfig(S3Client s3, String bucketName,
String accountId) {
                try {
                        DeleteBucketLifecycleRequest deleteBucketLifecycleRequest =
DeleteBucketLifecycleRequest
                                        .builder()
                                        .bucket(bucketName)
                                        .expectedBucketOwner(accountId)
                                        .build();

                        s3.deleteBucketLifecycle(deleteBucketLifecycleRequest);

                } catch (S3Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte PutBucketLifecycleConfigurationa Referência AWS SDK for Java 2.x da API.

Adicionar uma política a um bucket

O exemplo de código a seguir mostra como adicionar uma política a um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutBucketPolicyRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import java.io.IOException;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.List;
import com.fasterxml.jackson.core.JsonParser;
import com.fasterxml.jackson.databind.ObjectMapper;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SetBucketPolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <polFile>

                Where:
                    bucketName - The Amazon S3 bucket to set the policy on.
                    polFile - A JSON file containing the policy (see the Amazon S3
 Readme for an example).\s
                """;

        if (args.length != 2) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String polFile = args[1];
        String policyText = getBucketPolicyFromFile(polFile);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setPolicy(s3, bucketName, policyText);
        s3.close();
    }

    public static void setPolicy(S3Client s3, String bucketName, String policyText)
{
        System.out.println("Setting policy:");
        System.out.println("----");
        System.out.println(policyText);
        System.out.println("----");
        System.out.format("On Amazon S3 bucket: \"%s\"\n", bucketName);

        try {
            PutBucketPolicyRequest policyReq = PutBucketPolicyRequest.builder()
                    .bucket(bucketName)
                    .policy(policyText)
                    .build();

            s3.putBucketPolicy(policyReq);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        System.out.println("Done!");
    }

    // Loads a JSON-formatted policy from a file
    public static String getBucketPolicyFromFile(String policyFile) {

        StringBuilder fileText = new StringBuilder();
```

```
        try {
            List<String> lines = Files.readAllLines(Paths.get(policyFile),
 StandardCharsets.UTF_8);
            for (String line : lines) {
                fileText.append(line);
            }

        } catch (IOException e) {
            System.out.format("Problem reading file: \"%s\"", policyFile);
            System.out.println(e.getMessage());
        }

        try {
            final JsonParser parser = new
 ObjectMapper().getFactory().createParser(fileText.toString());
            while (parser.nextToken() != null) {
            }

        } catch (IOException jpe) {
            jpe.printStackTrace();
        }
        return fileText.toString();
    }
}
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for Java 2.x da API.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CopyObjectRequest;
import software.amazon.awssdk.services.s3.model.CopyObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class CopyObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <objectKey> <fromBucket> <toBucket>

                Where:
                    objectKey - The name of the object (for example, book.pdf).
                    fromBucket - The S3 bucket name that contains the object (for
 example, bucket1).
                    toBucket - The S3 bucket to copy the object to (for example,
 bucket2).
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String objectKey = args[0];
        String fromBucket = args[1];
        String toBucket = args[2];
        System.out.format("Copying object %s from bucket %s to %s\n", objectKey,
 fromBucket, toBucket);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
```

```
                .build();

        copyBucketObject(s3, fromBucket, objectKey, toBucket);
        s3.close();
    }

    public static String copyBucketObject(S3Client s3, String fromBucket, String
 objectKey, String toBucket) {
        CopyObjectRequest copyReq = CopyObjectRequest.builder()
                .sourceBucket(fromBucket)
                .sourceKey(objectKey)
                .destinationBucket(toBucket)
                .destinationKey(objectKey)
                .build();

        try {
            CopyObjectResponse copyRes = s3.copyObject(copyReq);
            return copyRes.copyObjectResult().toString();

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

Use um S3 TransferManager para copiar um objeto de um bucket para outro. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.model.CopyObjectRequest;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedCopy;
import software.amazon.awssdk.transfer.s3.model.Copy;
import software.amazon.awssdk.transfer.s3.model.CopyRequest;

import java.util.UUID;

    public String copyObject(S3TransferManager transferManager, String bucketName,
```

```
            String key, String destinationBucket, String destinationKey) {
        CopyObjectRequest copyObjectRequest = CopyObjectRequest.builder()
                .sourceBucket(bucketName)
                .sourceKey(key)
                .destinationBucket(destinationBucket)
                .destinationKey(destinationKey)
                .build();

        CopyRequest copyRequest = CopyRequest.builder()
                .copyObjectRequest(copyObjectRequest)
                .build();

        Copy copy = transferManager.copy(copyRequest);

        CompletedCopy completedCopy = copy.completionFuture().join();
        return completedCopy.response().copyObjectResult().eTag();
    }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Java 2.x da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.waiters.WaiterResponse;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CreateBucketRequest;
import software.amazon.awssdk.services.s3.model.HeadBucketRequest;
import software.amazon.awssdk.services.s3.model.HeadBucketResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import java.net.URISyntaxException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class CreateBucket {
    public static void main(String[] args) throws URISyntaxException {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The name of the bucket to create. The bucket name
 must be unique, or an error occurs.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Creating a bucket named %s\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        createBucket(s3, bucketName);
        s3.close();
    }

    public static void createBucket(S3Client s3Client, String bucketName) {
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();
```

```
            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
 s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Java 2.x da API.

Excluir uma política de um bucket

O exemplo de código a seguir mostra como excluir uma política de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.DeleteBucketPolicyRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
```

```
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteBucketPolicy {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                    <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to delete the policy from (for
 example, bucket1).""";

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Deleting policy from bucket: \"%s\"\n\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteS3BucketPolicy(s3, bucketName);
        s3.close();
    }

    // Delete the bucket policy.
    public static void deleteS3BucketPolicy(S3Client s3, String bucketName) {
        DeleteBucketPolicyRequest delReq = DeleteBucketPolicyRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            s3.deleteBucketPolicy(delReq);
            System.out.println("Done!");
```

```
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for Java 2.x da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucket)
                .build();

        s3.deleteBucket(deleteBucketRequest);
        s3.close();
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Java 2.x da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.services.s3.model.Delete;
import software.amazon.awssdk.services.s3.model.DeleteObjectsRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteMultiObjects {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucketName>

                Where:
                   bucketName - the Amazon S3 bucket name.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void deleteBucketObjects(S3Client s3, String bucketName) {
        // Upload three sample objects to the specfied Amazon S3 bucket.
        ArrayList<ObjectIdentifier> keys = new ArrayList<>();
        PutObjectRequest putOb;
        ObjectIdentifier objectId;

        for (int i = 0; i < 3; i++) {
            String keyName = "delete object example " + i;
            objectId = ObjectIdentifier.builder()
                    .key(keyName)
                    .build();

            putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            s3.putObject(putOb, RequestBody.fromString(keyName));
            keys.add(objectId);
        }

        System.out.println(keys.size() + " objects successfully created.");

        // Delete multiple objects in one request.
        Delete del = Delete.builder()
                .objects(keys)
                .build();

        try {
            DeleteObjectsRequest multiObjectDeleteRequest =
DeleteObjectsRequest.builder()
                    .bucket(bucketName)
                    .delete(del)
                    .build();
```

```
            s3.deleteObjects(multiObjectDeleteRequest);
            System.out.println("Multiple objects are deleted!");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Java 2.x da API.

Excluir a configuração de site de um bucket

O exemplo de código a seguir mostra como excluir a configuração de site de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.DeleteBucketWebsiteRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class DeleteWebsiteConfiguration {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:     <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to delete the website
 configuration from.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Deleting website configuration for Amazon S3 bucket: %s
\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        deleteBucketWebsiteConfig(s3, bucketName);
        System.out.println("Done!");
        s3.close();
    }

    public static void deleteBucketWebsiteConfig(S3Client s3, String bucketName) {
        DeleteBucketWebsiteRequest delReq = DeleteBucketWebsiteRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            s3.deleteBucketWebsite(delReq);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.out.println("Failed to delete website configuration!");
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteBucketWebsitea Referência AWS SDK for Java 2.x da API.

Determinar a existência e o tipo de conteúdo de um objeto

O exemplo de código a seguir mostra como determinar a existência e o tipo de conteúdo de um objeto em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determine o tipo de conteúdo de um objeto.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetObjectContentType {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
```

```
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getContentType(s3, bucketName, keyName);
        s3.close();
    }

    public static void getContentType(S3Client s3, String bucketName, String
 keyName) {
        try {
            HeadObjectRequest objectRequest = HeadObjectRequest.builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            HeadObjectResponse objectHead = s3.headObject(objectRequest);
            String type = objectHead.contentType();
            System.out.println("The object content type is " + type);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha o status de restauração de um objeto.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
```

```
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;

public class GetObjectRestoreStatus {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents the object.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        checkStatus(s3, bucketName, keyName);
        s3.close();
    }

    public static void checkStatus(S3Client s3, String bucketName, String keyName) {
        try {
            HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            HeadObjectResponse response = s3.headObject(headObjectRequest);
            System.out.println("The Amazon S3 object restoration status is " +
 response.restore());

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte HeadObjecta Referência AWS SDK for Java 2.x da API.

Fazer download de objetos em um diretório local

O exemplo de código a seguir mostra como fazer download de todos os objetos de um bucket do Amazon Simple Storage Service (Amazon S3) em um diretório local.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use um S3 TransferManager para baixar todos os objetos do S3 no mesmo bucket do S3. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedDirectoryDownload;
import software.amazon.awssdk.transfer.s3.model.DirectoryDownload;
import software.amazon.awssdk.transfer.s3.model.DownloadDirectoryRequest;

import java.io.IOException;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.HashSet;
import java.util.Set;
import java.util.UUID;
import java.util.stream.Collectors;

    public Integer downloadObjectsToDirectory(S3TransferManager transferManager,
```

```
            String destinationPath, String bucketName) {
        DirectoryDownload directoryDownload =
 transferManager.downloadDirectory(DownloadDirectoryRequest.builder()
                .destination(Paths.get(destinationPath))
                .bucket(bucketName)
                .build());
        CompletedDirectoryDownload completedDirectoryDownload =
 directoryDownload.completionFuture().join();

        completedDirectoryDownload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
 fail.toString()));
        return completedDirectoryDownload.failedTransfers().size();
    }
```

- Para obter detalhes da API, consulte DownloadDirectorya Referência AWS SDK for Java 2.x da API.

Habilitar notificações

O exemplo de código a seguir mostra como habilitar notificações para um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.Event;
import software.amazon.awssdk.services.s3.model.NotificationConfiguration;
import
 software.amazon.awssdk.services.s3.model.PutBucketNotificationConfigurationRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.TopicConfiguration;
import java.util.ArrayList;
import java.util.List;
```

```
public class SetBucketEventBridgeNotification {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The Amazon S3 bucket.\s
                    topicArn - The Simple Notification Service topic ARN.\s
                    id - An id value used for the topic configuration. This value is
 displayed in the AWS Management Console.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String topicArn = args[1];
        String id = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        setBucketNotification(s3Client, bucketName, topicArn, id);
        s3Client.close();
    }

    public static void setBucketNotification(S3Client s3Client, String bucketName,
 String topicArn, String id) {
        try {
            List<Event> events = new ArrayList<>();
            events.add(Event.S3_OBJECT_CREATED_PUT);

            TopicConfiguration config = TopicConfiguration.builder()
                    .topicArn(topicArn)
                    .events(events)
                    .id(id)
                    .build();

            List<TopicConfiguration> topics = new ArrayList<>();
```

```
            topics.add(config);

            NotificationConfiguration configuration =
 NotificationConfiguration.builder()
                    .topicConfigurations(topics)
                    .build();

            PutBucketNotificationConfigurationRequest configurationRequest =
 PutBucketNotificationConfigurationRequest
                    .builder()
                    .bucket(bucketName)
                    .notificationConfiguration(configuration)
                    .skipDestinationValidation(true)
                    .build();

            // Set the bucket notification configuration.
            s3Client.putBucketNotificationConfiguration(configurationRequest);
            System.out.println("Added bucket " + bucketName + " with EventBridge
 events enabled.");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketNotificationConfigurationa Referência AWS SDK for Java 2.x da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Leia dados como uma matriz de bytes usando um S3Client.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetObjectData {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <path>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
                    path - The path where the file is written to.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String path = args[2];
        Region region = Region.US_EAST_1;
```

```
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getObjectBytes(s3, bucketName, keyName, path);
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
 keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
 s3.getObjectAsBytes(objectRequest);
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Use um S3 TransferManager para baixar um objeto em um bucket do S3 para um arquivo local. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.sync.RequestBody;
```

```
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedFileDownload;
import software.amazon.awssdk.transfer.s3.model.DownloadFileRequest;
import software.amazon.awssdk.transfer.s3.model.FileDownload;
import software.amazon.awssdk.transfer.s3.progress.LoggingTransferListener;

import java.io.IOException;
import java.net.URL;
import java.nio.file.Files;
import java.nio.file.Paths;
import java.util.UUID;

    public Long downloadFile(S3TransferManager transferManager, String bucketName,
            String key, String downloadedFileWithPath) {
        DownloadFileRequest downloadFileRequest = DownloadFileRequest.builder()
                .getObjectRequest(b -> b.bucket(bucketName).key(key))
                .addTransferListener(LoggingTransferListener.create())
                .destination(Paths.get(downloadedFileWithPath))
                .build();

        FileDownload downloadFile =
 transferManager.downloadFile(downloadFileRequest);

        CompletedFileDownload downloadResult =
 downloadFile.completionFuture().join();
        logger.info("Content length [{}]",
 downloadResult.response().contentLength());
        return downloadResult.response().contentLength();
    }
```

Leia etiquetas que pertencem a um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectTaggingRequest;
import software.amazon.awssdk.services.s3.model.GetObjectTaggingResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.Tag;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetObjectTags {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents the object.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listTags(s3, bucketName, keyName);
        s3.close();
    }

    public static void listTags(S3Client s3, String bucketName, String keyName) {
        try {
            GetObjectTaggingRequest getTaggingRequest = GetObjectTaggingRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            GetObjectTaggingResponse tags = s3.getObjectTagging(getTaggingRequest);
```

```
            List<Tag> tagSet = tags.tagSet();
            for (Tag tag : tagSet) {
                System.out.println(tag.key());
                System.out.println(tag.value());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha um URL para um objeto usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetUrlRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.net.URL;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetObjectUrl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.
                    keyName - A key name that represents the object.\s
                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getURL(s3, bucketName, keyName);
        s3.close();
    }

    public static void getURL(S3Client s3, String bucketName, String keyName) {
        try {
            GetUrlRequest request = GetUrlRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            URL url = s3.utilities().getUrl(request);
            System.out.println("The URL for  " + keyName + " is " + url);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Obtenha um objeto usando o objeto de cliente S3Presigner usando um S3Client.

```
import java.io.IOException;
import java.io.InputStream;
import java.io.OutputStream;
import java.net.HttpURLConnection;
import java.time.Duration;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
```

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.presigner.model.GetObjectPresignRequest;
import software.amazon.awssdk.services.s3.presigner.model.PresignedGetObjectRequest;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import software.amazon.awssdk.utils.IoUtils;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetObjectPresignedUrl {
    public static void main(String[] args) {
        final String USAGE = """

                Usage:
                    <bucketName> <keyName>\s

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - A key name that represents a text file.\s
                """;

        if (args.length != 2) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        Region region = Region.US_EAST_1;
        S3Presigner presigner = S3Presigner.builder()
                .region(region)
                .build();

        getPresignedUrl(presigner, bucketName, keyName);
        presigner.close();
    }

    public static void getPresignedUrl(S3Presigner presigner, String bucketName,
 String keyName) {
```

```
        try {
            GetObjectRequest getObjectRequest = GetObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            GetObjectPresignRequest getObjectPresignRequest =
GetObjectPresignRequest.builder()
                    .signatureDuration(Duration.ofMinutes(60))
                    .getObjectRequest(getObjectRequest)
                    .build();

            PresignedGetObjectRequest presignedGetObjectRequest =
presigner.presignGetObject(getObjectPresignRequest);
            String theUrl = presignedGetObjectRequest.url().toString();
            System.out.println("Presigned URL: " + theUrl);
            HttpURLConnection connection = (HttpURLConnection)
presignedGetObjectRequest.url().openConnection();
            presignedGetObjectRequest.httpRequest().headers().forEach((header,
values) -> {
                values.forEach(value -> {
                    connection.addRequestProperty(header, value);
                });
            });

            // Send any request payload that the service needs (not needed when
            // isBrowserExecutable is true).
            if (presignedGetObjectRequest.signedPayload().isPresent()) {
                connection.setDoOutput(true);

                try (InputStream signedPayload =
presignedGetObjectRequest.signedPayload().get().asInputStream();
                        OutputStream httpOutputStream =
connection.getOutputStream()) {
                    IoUtils.copy(signedPayload, httpOutputStream);
                }
            }

            // Download the result of executing the request.
            try (InputStream content = connection.getInputStream()) {
                System.out.println("Service returned response: ");
                IoUtils.copy(content, System.out);
            }
```

```
        } catch (S3Exception | IOException e) {
            e.getStackTrace();
        }
    }
}
```

Obtenha um objeto usando um ResponseTransformer objeto e o S3Client.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.core.sync.ResponseTransformer;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetDataResponseTransformer {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <path>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name.\s
                    path - The path where the file is written to.\s
                """;
```

```
        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String path = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getObjectBytes(s3, bucketName, keyName, path);
        s3.close();
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
s3.getObject(objectRequest, ResponseTransformer.toBytes());
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Java 2.x da API.

Obter a ACL de um bucket

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectAclRequest;
import software.amazon.awssdk.services.s3.model.GetObjectAclResponse;
import software.amazon.awssdk.services.s3.model.Grant;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetAcl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <bucketName> <objectKey>
```

```
                Where:
                  bucketName - The Amazon S3 bucket to get the access control list
(ACL) for.
                  objectKey - The object to get the ACL for.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String objectKey = args[1];
        System.out.println("Retrieving ACL for object: " + objectKey);
        System.out.println("in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        getBucketACL(s3, objectKey, bucketName);
        s3.close();
        System.out.println("Done!");
    }

    public static String getBucketACL(S3Client s3, String objectKey, String
bucketName) {
        try {
            GetObjectAclRequest aclReq = GetObjectAclRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .build();

            GetObjectAclResponse aclRes = s3.getObjectAcl(aclReq);
            List<Grant> grants = aclRes.grants();
            String grantee = "";
            for (Grant grant : grants) {
                System.out.format("  %s: %s\n", grant.grantee().id(),
grant.permission());
                grantee = grant.grantee().id();
            }

            return grantee;
        } catch (S3Exception e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
}
```

- Para obter detalhes da API, consulte GetBucketAcla Referência AWS SDK for Java 2.x da API.

Obter a política de um bucket

O exemplo de código a seguir mostra como obter a política de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetBucketPolicyRequest;
import software.amazon.awssdk.services.s3.model.GetBucketPolicyResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class GetBucketPolicy {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <bucketName>

                Where:
                    bucketName - The Amazon S3 bucket to get the policy from.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        System.out.format("Getting policy for bucket: \"%s\"\n\n", bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        String polText = getPolicy(s3, bucketName);
        System.out.println("Policy Text: " + polText);
        s3.close();
    }

    public static String getPolicy(S3Client s3, String bucketName) {
        String policyText;
        System.out.format("Getting policy for bucket: \"%s\"\n\n", bucketName);
        GetBucketPolicyRequest policyReq = GetBucketPolicyRequest.builder()
                .bucket(bucketName)
                .build();

        try {
            GetBucketPolicyResponse policyRes = s3.getBucketPolicy(policyReq);
            policyText = policyRes.policy();
            return policyText;

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        return "";
    }
}
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for Java 2.x da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.Bucket;
import software.amazon.awssdk.services.s3.model.ListBucketsResponse;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListBuckets {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
            .region(region)
            .build();

        listAllBuckets(s3);

    }
    public static void listAllBuckets(S3Client s3) {
```

```
        ListBucketsResponse response = s3.listBuckets();
        List<Bucket> bucketList = response.buckets();
        for (Bucket bucket: bucketList) {
            System.out.println("Bucket name "+bucket.name());
        }
    }
}
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Java 2.x da API.

Listar carregamentos fracionados em andamento

O exemplo de código a seguir mostra como listar carregamentos fracionados em andamento em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListMultipartUploadsRequest;
import software.amazon.awssdk.services.s3.model.ListMultipartUploadsResponse;
import software.amazon.awssdk.services.s3.model.MultipartUpload;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class ListMultipartUploads {
```

```
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The name of the Amazon S3 bucket where an in-
progress multipart upload is occurring.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();
        listUploads(s3, bucketName);
        s3.close();
    }

    public static void listUploads(S3Client s3, String bucketName) {
        try {
            ListMultipartUploadsRequest listMultipartUploadsRequest =
 ListMultipartUploadsRequest.builder()
                    .bucket(bucketName)
                    .build();

            ListMultipartUploadsResponse response =
 s3.listMultipartUploads(listMultipartUploadsRequest);
            List<MultipartUpload> uploads = response.uploads();
            for (MultipartUpload upload : uploads) {
                System.out.println("Upload in progress: Key = \"" + upload.key() +
 "\", id = " + upload.uploadId());
            }

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte ListMultipartUploadsa Referência AWS SDK for Java 2.x da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListObjectsRequest;
import software.amazon.awssdk.services.s3.model.ListObjectsResponse;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.S3Object;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class ListObjects {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s
```

```
                Where:
                    bucketName - The Amazon S3 bucket from which objects are read.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsRequest listObjects = ListObjectsRequest
                    .builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.print("\n The name of the key is " + myValue.key());
                System.out.print("\n The object is " + calKb(myValue.size()) + "
KBs");
                System.out.print("\n The owner is " + myValue.owner());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // convert bytes to kbs.
    private static long calKb(Long val) {
```

```
        return val / 1024;
    }
}
```

Liste objetos usando paginação.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ListObjectsV2Request;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.paginators.ListObjectsV2Iterable;

public class ListObjectsPaginated {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName>\s

                Where:
                    bucketName - The Amazon S3 bucket from which objects are read.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        listBucketObjects(s3, bucketName);
        s3.close();
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsV2Request listReq = ListObjectsV2Request.builder()
                    .bucket(bucketName)
```

```
                    .maxKeys(1)
                    .build();

            ListObjectsV2Iterable listRes = s3.listObjectsV2Paginator(listReq);
            listRes.stream()
                    .flatMap(r -> r.contents().stream())
                    .forEach(content -> System.out.println(" Key: " + content.key()
 + " size = " + content.size()));

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Java 2.x da API.

Restaurar uma cópia arquivada de um objeto

O exemplo de código a seguir mostra como restaurar uma cópia arquivada de um objeto em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.RestoreRequest;
import software.amazon.awssdk.services.s3.model.GlacierJobParameters;
import software.amazon.awssdk.services.s3.model.RestoreObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.model.Tier;
```

```
/*
 *  For more information about restoring an object, see "Restoring an archived
 object" at
 *  https://docs.aws.amazon.com/AmazonS3/latest/userguide/restoring-objects.html
 *
 *  Before running this Java V2 code example, set up your development environment,
 including your credentials.
 *
 *  For more information, see the following documentation topic:
 *
 *  https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class RestoreObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <keyName> <expectedBucketOwner>

                Where:
                    bucketName - The Amazon S3 bucket name.\s
                    keyName - The key name of an object with a Storage class value
 of Glacier.\s
                    expectedBucketOwner - The account that owns the bucket (you can
 obtain this value from the AWS Management Console).\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String keyName = args[1];
        String expectedBucketOwner = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        restoreS3Object(s3, bucketName, keyName, expectedBucketOwner);
        s3.close();
    }
```

```
    public static void restoreS3Object(S3Client s3, String bucketName, String
 keyName, String expectedBucketOwner) {
        try {
            RestoreRequest restoreRequest = RestoreRequest.builder()
                    .days(10)

 .glacierJobParameters(GlacierJobParameters.builder().tier(Tier.STANDARD).build())
                    .build();

            RestoreObjectRequest objectRequest = RestoreObjectRequest.builder()
                    .expectedBucketOwner(expectedBucketOwner)
                    .bucket(bucketName)
                    .key(keyName)
                    .restoreRequest(restoreRequest)
                    .build();

            s3.restoreObject(objectRequest);

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte RestoreObjecta Referência AWS SDK for Java 2.x da API.

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import java.util.ArrayList;
```

```
import java.util.List;
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.services.s3.model.Permission;
import software.amazon.awssdk.services.s3.model.Grant;
import software.amazon.awssdk.services.s3.model.AccessControlPolicy;
import software.amazon.awssdk.services.s3.model.Type;
import software.amazon.awssdk.services.s3.model.PutBucketAclRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SetAcl {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <bucketName> <id>\s

                Where:
                  bucketName - The Amazon S3 bucket to grant permissions on.\s
                  id - The ID of the owner of this bucket (you can get this value
 from the AWS Management Console).
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String id = args[1];
        System.out.format("Setting access \n");
        System.out.println(" in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
```

```
                .build();

        setBucketAcl(s3, bucketName, id);
        System.out.println("Done!");
        s3.close();
    }

    public static void setBucketAcl(S3Client s3, String bucketName, String id) {
        try {
            Grant ownerGrant = Grant.builder()
                    .grantee(builder -> builder.id(id)
                            .type(Type.CANONICAL_USER))
                    .permission(Permission.FULL_CONTROL)
                    .build();

            List<Grant> grantList2 = new ArrayList<>();
            grantList2.add(ownerGrant);

            AccessControlPolicy acl = AccessControlPolicy.builder()
                    .owner(builder -> builder.id(id))
                    .grants(grantList2)
                    .build();

            PutBucketAclRequest putAclReq = PutBucketAclRequest.builder()
                    .bucket(bucketName)
                    .accessControlPolicy(acl)
                    .build();

            s3.putBucketAcl(putAclReq);

        } catch (S3Exception e) {
            e.printStackTrace();
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketAcla Referência AWS SDK for Java 2.x da API.

Definir a configuração de site de um bucket

O exemplo de código a seguir mostra como definir a configuração de site de um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.IndexDocument;
import software.amazon.awssdk.services.s3.model.PutBucketWebsiteRequest;
import software.amazon.awssdk.services.s3.model.WebsiteConfiguration;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.regions.Region;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class SetWebsiteConfiguration {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <bucketName> [indexdoc]\s

                Where:
                   bucketName   - The Amazon S3 bucket to set the website
 configuration on.\s
                   indexdoc - The index document, ex. 'index.html'
                              If not specified, 'index.html' will be set.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String bucketName = args[0];
        String indexDoc = "index.html";
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setWebsiteConfig(s3, bucketName, indexDoc);
        s3.close();
    }

    public static void setWebsiteConfig(S3Client s3, String bucketName, String
 indexDoc) {
        try {
            WebsiteConfiguration websiteConfig = WebsiteConfiguration.builder()
                    .indexDocument(IndexDocument.builder().suffix(indexDoc).build())
                    .build();

            PutBucketWebsiteRequest pubWebsiteReq =
 PutBucketWebsiteRequest.builder()
                    .bucket(bucketName)
                    .websiteConfiguration(websiteConfig)
                    .build();

            s3.putBucketWebsite(pubWebsiteReq);
            System.out.println("The call was successful");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for Java 2.x da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça upload de um arquivo em um bucket usando um S3Client.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class PutObject {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                  <bucketName> <objectKey> <objectPath>\s

                Where:
                  bucketName - The Amazon S3 bucket to upload an object into.
                  objectKey - The object to upload (for example, book.pdf).
                  objectPath - The path where the file is located (for example, C:/
AWS/book2.pdf).\s
                """;

        if (args.length != 3) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String objectKey = args[1];
        String objectPath = args[2];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        putS3Object(s3, bucketName, objectKey, objectPath);
        s3.close();
    }

    // This example uses RequestBody.fromFile to avoid loading the whole file into
    // memory.
    public static void putS3Object(S3Client s3, String bucketName, String objectKey,
 String objectPath) {
        try {
            Map<String, String> metadata = new HashMap<>();
            metadata.put("x-amz-meta-myVal", "test");
            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .metadata(metadata)
                    .build();

            s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
            System.out.println("Successfully placed " + objectKey + " into bucket "
 + bucketName);

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Use um S3 TransferManager para fazer upload de um arquivo em um bucket. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedFileUpload;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;
import software.amazon.awssdk.transfer.s3.progress.LoggingTransferListener;

import java.net.URL;
import java.nio.file.Paths;
import java.util.UUID;

    public String uploadFile(S3TransferManager transferManager, String bucketName,
            String key, String filePath) {
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b.bucket(bucketName).key(key))
                .addTransferListener(LoggingTransferListener.create())
                .source(Paths.get(filePath))
                .build();

        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);

        CompletedFileUpload uploadResult = fileUpload.completionFuture().join();
        return uploadResult.response().eTag();
    }
```

Faça upload de um objeto em um bucket e defina etiquetas usando um S3Client.

```
    public static void putS3ObjectTags(S3Client s3, String bucketName, String
 objectKey, String objectPath) {
        try {
            Tag tag1 = Tag.builder()
                    .key("Tag 1")
                    .value("This is tag 1")
                    .build();

            Tag tag2 = Tag.builder()
                    .key("Tag 2")
                    .value("This is tag 2")
                    .build();

            List<Tag> tags = new ArrayList<>();
```

```
            tags.add(tag1);
            tags.add(tag2);

            Tagging allTags = Tagging.builder()
                    .tagSet(tags)
                    .build();

            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .tagging(allTags)
                    .build();

            s3.putObject(putOb, RequestBody.fromBytes(getObjectFile(objectPath)));

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateObjectTags(S3Client s3, String bucketName, String
objectKey) {
        try {
            GetObjectTaggingRequest taggingRequest =
GetObjectTaggingRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .build();

            GetObjectTaggingResponse getTaggingRes =
s3.getObjectTagging(taggingRequest);
            List<Tag> obTags = getTaggingRes.tagSet();
            for (Tag sinTag : obTags) {
                System.out.println("The tag key is: " + sinTag.key());
                System.out.println("The tag value is: " + sinTag.value());
            }

            // Replace the object's tags with two new tags.
            Tag tag3 = Tag.builder()
                    .key("Tag 3")
                    .value("This is tag 3")
                    .build();
```

```
            Tag tag4 = Tag.builder()
                    .key("Tag 4")
                    .value("This is tag 4")
                    .build();

            List<Tag> tags = new ArrayList<>();
            tags.add(tag3);
            tags.add(tag4);

            Tagging updatedTags = Tagging.builder()
                    .tagSet(tags)
                    .build();

            PutObjectTaggingRequest taggingRequest1 =
PutObjectTaggingRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .tagging(updatedTags)
                    .build();

            s3.putObjectTagging(taggingRequest1);
            GetObjectTaggingResponse getTaggingRes2 =
s3.getObjectTagging(taggingRequest);
            List<Tag> modTags = getTaggingRes2.tagSet();
            for (Tag sinTag : modTags) {
                System.out.println("The tag key is: " + sinTag.key());
                System.out.println("The tag value is: " + sinTag.value());
            }

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Return a byte array.
    private static byte[] getObjectFile(String filePath) {
        FileInputStream fileInputStream = null;
        byte[] bytesArray = null;

        try {
            File file = new File(filePath);
            bytesArray = new byte[(int) file.length()];
            fileInputStream = new FileInputStream(file);
```

```
            fileInputStream.read(bytesArray);

        } catch (IOException e) {
            e.printStackTrace();
        } finally {
            if (fileInputStream != null) {
                try {
                    fileInputStream.close();
                } catch (IOException e) {
                    e.printStackTrace();
                }
            }
        }

        return bytesArray;
    }
}
```

Faça upload de um objeto em um bucket e defina metadados usando um S3Client.

```
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.io.File;
import java.util.HashMap;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutObjectMetadata {
    public static void main(String[] args) {
        final String USAGE = """

                Usage:
```

```
                  <bucketName> <objectKey> <objectPath>\s

                Where:
                  bucketName - The Amazon S3 bucket to upload an object into.
                  objectKey - The object to upload (for example, book.pdf).
                  objectPath - The path where the file is located (for example, C:/
AWS/book2.pdf).\s
                """;

        if (args.length != 3) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String bucketName = args[0];
        String objectKey = args[1];
        String objectPath = args[2];
        System.out.println("Putting object " + objectKey + " into bucket " +
 bucketName);
        System.out.println("  in bucket: " + bucketName);
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        putS3Object(s3, bucketName, objectKey, objectPath);
        s3.close();
    }

    // This example uses RequestBody.fromFile to avoid loading the whole file into
    // memory.
    public static void putS3Object(S3Client s3, String bucketName, String objectKey,
 String objectPath) {
        try {
            Map<String, String> metadata = new HashMap<>();
            metadata.put("author", "Mary Doe");
            metadata.put("version", "1.0.0.0");

            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key(objectKey)
                    .metadata(metadata)
                    .build();
```

```
            s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
            System.out.println("Successfully placed " + objectKey + " into bucket "
 + bucketName);

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Faça upload de um objeto em um bucket e defina um valor de retenção de objetos usando um S3Client.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRetentionRequest;
import software.amazon.awssdk.services.s3.model.ObjectLockRetention;
import software.amazon.awssdk.services.s3.model.S3Exception;
import java.time.Instant;
import java.time.LocalDate;
import java.time.LocalDateTime;
import java.time.ZoneOffset;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class PutObjectRetention {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <key> <bucketName>\s

                Where:
                    key - The name of the object (for example, book.pdf).\s
```

```
                    bucketName - The Amazon S3 bucket name that contains the object
(for example, bucket1).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String key = args[0];
        String bucketName = args[1];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        setRentionPeriod(s3, key, bucketName);
        s3.close();
    }

    public static void setRentionPeriod(S3Client s3, String key, String bucket) {
        try {
            LocalDate localDate = LocalDate.parse("2020-07-17");
            LocalDateTime localDateTime = localDate.atStartOfDay();
            Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

            ObjectLockRetention lockRetention = ObjectLockRetention.builder()
                    .mode("COMPLIANCE")
                    .retainUntilDate(instant)
                    .build();

            PutObjectRetentionRequest retentionRequest =
PutObjectRetentionRequest.builder()
                    .bucket(bucket)
                    .key(key)
                    .bypassGovernanceRetention(true)
                    .retention(lockRetention)
                    .build();

            // To set Retention on an object, the Amazon S3 bucket must support
object
            // locking, otherwise an exception is thrown.
            s3.putObjectRetention(retentionRequest);
```

```
            System.out.print("An object retention configuration was successfully
 placed on the object");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Java 2.x da API.

Fazer upload em um bucket

O exemplo de código a seguir mostra como fazer upload recursivo de um diretório local em um bucket do Amazon Simple Storage Service (Amazon S3).

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use um S3 TransferManager para carregar um diretório local. Veja o arquivo completo e teste.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.services.s3.model.ObjectIdentifier;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedDirectoryUpload;
import software.amazon.awssdk.transfer.s3.model.DirectoryUpload;
import software.amazon.awssdk.transfer.s3.model.UploadDirectoryRequest;

import java.net.URL;
import java.nio.file.Paths;
import java.util.UUID;

    public Integer uploadDirectory(S3TransferManager transferManager,
            String sourceDirectory, String bucketName) {
```

```
        DirectoryUpload directoryUpload =
transferManager.uploadDirectory(UploadDirectoryRequest.builder()
                .source(Paths.get(sourceDirectory))
                .bucket(bucketName)
                .build());

        CompletedDirectoryUpload completedDirectoryUpload =
directoryUpload.completionFuture().join();
        completedDirectoryUpload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
fail.toString()));
        return completedDirectoryUpload.failedTransfers().size();
    }
```

- Para obter detalhes da API, consulte UploadDirectorya Referência AWS SDK for Java 2.x da API.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado para um objeto e baixe-o (solicitação GET).

Importações

```
import com.example.s3.util.PresignUrlUtils;
import org.slf4j.Logger;
import software.amazon.awssdk.http.HttpExecuteRequest;
import software.amazon.awssdk.http.HttpExecuteResponse;
```

```
import software.amazon.awssdk.http.SdkHttpClient;
import software.amazon.awssdk.http.SdkHttpMethod;
import software.amazon.awssdk.http.SdkHttpRequest;
import software.amazon.awssdk.http.apache.ApacheHttpClient;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.GetObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import software.amazon.awssdk.services.s3.presigner.model.GetObjectPresignRequest;
import software.amazon.awssdk.services.s3.presigner.model.PresignedGetObjectRequest;
import software.amazon.awssdk.utils.IoUtils;

import java.io.ByteArrayOutputStream;
import java.io.File;
import java.io.IOException;
import java.io.InputStream;
import java.net.HttpURLConnection;
import java.net.URISyntaxException;
import java.net.URL;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.file.Paths;
import java.time.Duration;
import java.util.UUID;
```

Gere o URL.

```
    /* Create a pre-signed URL to download an object in a subsequent GET request. */
    public String createPresignedGetUrl(String bucketName, String keyName) {
        try (S3Presigner presigner = S3Presigner.create()) {

            GetObjectRequest objectRequest = GetObjectRequest.builder()
                    .bucket(bucketName)
                    .key(keyName)
                    .build();

            GetObjectPresignRequest presignRequest =
 GetObjectPresignRequest.builder()
                    .signatureDuration(Duration.ofMinutes(10))  // The URL will
 expire in 10 minutes.
                    .getObjectRequest(objectRequest)
```

```
                    .build();

            PresignedGetObjectRequest presignedRequest =
presigner.presignGetObject(presignRequest);
            logger.info("Presigned URL: [{}]", presignedRequest.url().toString());
            logger.info("HTTP method: [{}]",
presignedRequest.httpRequest().method());

            return presignedRequest.url().toExternalForm();
        }
    }
```

Baixe o objeto usando uma das três abordagens a seguir.

Use a classe `HttpURLConnection` do JDK (desde a v1.1) para baixar.

```
    /* Use the JDK HttpURLConnection (since v1.1) class to do the download. */
    public byte[] useHttpUrlConnectionToGet(String presignedUrlString) {
        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.

        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpURLConnection connection = (HttpURLConnection)
presignedUrl.openConnection();
            connection.setRequestMethod("GET");
            // Download the result of executing the request.
            try (InputStream content = connection.getInputStream()) {
                IoUtils.copy(content, byteArrayOutputStream);
            }
            logger.info("HTTP response code is " + connection.getResponseCode());

        } catch (S3Exception | IOException e) {
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Use a classe `HttpClient` do JDK (desde a v11) para baixar.

```
    /* Use the JDK HttpClient (since v11) class to do the download. */
```

```
    public byte[] useHttpClientToGet(String presignedUrlString) {
        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.

        HttpRequest.Builder requestBuilder = HttpRequest.newBuilder();
        HttpClient httpClient = HttpClient.newHttpClient();
        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpResponse<InputStream> response = httpClient.send(requestBuilder
                            .uri(presignedUrl.toURI())
                            .GET()
                            .build(),
                    HttpResponse.BodyHandlers.ofInputStream());

            IoUtils.copy(response.body(), byteArrayOutputStream);

            logger.info("HTTP response code is " + response.statusCode());

        } catch (URISyntaxException | InterruptedException | IOException e) {
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Use a classe `SdkHttpClient` do SDK da AWS para Java para baixar.

```
    /* Use the AWS SDK for Java SdkHttpClient class to do the download. */
    public byte[] useSdkHttpClientToPut(String presignedUrlString) {

        ByteArrayOutputStream byteArrayOutputStream = new
ByteArrayOutputStream(); // Capture the response body to a byte array.
        try {
            URL presignedUrl = new URL(presignedUrlString);
            SdkHttpRequest request = SdkHttpRequest.builder()
                    .method(SdkHttpMethod.GET)
                    .uri(presignedUrl.toURI())
                    .build();

            HttpExecuteRequest executeRequest = HttpExecuteRequest.builder()
                    .request(request)
                    .build();
```

```
            try (SdkHttpClient sdkHttpClient = ApacheHttpClient.create()) {
                HttpExecuteResponse response =
 sdkHttpClient.prepareRequest(executeRequest).call();
                response.responseBody().ifPresentOrElse(
                        abortableInputStream -> {
                            try {
                                IoUtils.copy(abortableInputStream,
 byteArrayOutputStream);
                            } catch (IOException e) {
                                throw new RuntimeException(e);
                            }
                        },
                        () -> logger.error("No response body."));

                logger.info("HTTP Response code is {}",
 response.httpResponse().statusCode());
            }
        } catch (URISyntaxException | IOException e) {
            logger.error(e.getMessage(), e);
        }
        return byteArrayOutputStream.toByteArray();
    }
```

Gere um URL pré-assinado para um upload e faça upload de um arquivo (solicitação PUT).

Importações

```
import com.example.s3.util.PresignUrlUtils;
import org.slf4j.Logger;
import software.amazon.awssdk.core.internal.sync.FileContentStreamProvider;
import software.amazon.awssdk.http.HttpExecuteRequest;
import software.amazon.awssdk.http.HttpExecuteResponse;
import software.amazon.awssdk.http.SdkHttpClient;
import software.amazon.awssdk.http.SdkHttpMethod;
import software.amazon.awssdk.http.SdkHttpRequest;
import software.amazon.awssdk.http.apache.ApacheHttpClient;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.PutObjectRequest;
import software.amazon.awssdk.services.s3.model.S3Exception;
import software.amazon.awssdk.services.s3.presigner.S3Presigner;
import software.amazon.awssdk.services.s3.presigner.model.PresignedPutObjectRequest;
import software.amazon.awssdk.services.s3.presigner.model.PutObjectPresignRequest;
```

```
import java.io.File;
import java.io.IOException;
import java.io.OutputStream;
import java.io.RandomAccessFile;
import java.net.HttpURLConnection;
import java.net.URISyntaxException;
import java.net.URL;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;
import java.nio.ByteBuffer;
import java.nio.channels.FileChannel;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.time.Duration;
import java.util.Map;
import java.util.UUID;
```

Gere o URL.

```
   /* Create a presigned URL to use in a subsequent PUT request */
   public String createPresignedUrl(String bucketName, String keyName, Map<String,
 String> metadata) {
       try (S3Presigner presigner = S3Presigner.create()) {

           PutObjectRequest objectRequest = PutObjectRequest.builder()
                   .bucket(bucketName)
                   .key(keyName)
                   .metadata(metadata)
                   .build();

           PutObjectPresignRequest presignRequest =
 PutObjectPresignRequest.builder()
                   .signatureDuration(Duration.ofMinutes(10))  // The URL expires
 in 10 minutes.
                   .putObjectRequest(objectRequest)
                   .build();


           PresignedPutObjectRequest presignedRequest =
 presigner.presignPutObject(presignRequest);
           String myURL = presignedRequest.url().toString();
```

```
            logger.info("Presigned URL to upload a file to: [{}]", myURL);
            logger.info("HTTP method: [{}]",
presignedRequest.httpRequest().method());

            return presignedRequest.url().toExternalForm();
        }
    }
```

Faça upload de um objeto de arquivo usando uma das três abordagens a seguir.

Use a classe `HttpURLConnection` do JDK (desde a v1.1) para fazer upload.

```
    /* Use the JDK HttpURLConnection (since v1.1) class to do the upload. */
    public void useHttpUrlConnectionToPut(String presignedUrlString, File fileToPut,
Map<String, String> metadata) {
        logger.info("Begin [{}] upload", fileToPut.toString());
        try {
            URL presignedUrl = new URL(presignedUrlString);
            HttpURLConnection connection = (HttpURLConnection)
presignedUrl.openConnection();
            connection.setDoOutput(true);
            metadata.forEach((k, v) -> connection.setRequestProperty("x-amz-meta-" +
k, v));
            connection.setRequestMethod("PUT");
            OutputStream out = connection.getOutputStream();

            try (RandomAccessFile file = new RandomAccessFile(fileToPut, "r");
                 FileChannel inChannel = file.getChannel()) {
                ByteBuffer buffer = ByteBuffer.allocate(8192); //Buffer size is 8k

                while (inChannel.read(buffer) > 0) {
                    buffer.flip();
                    for (int i = 0; i < buffer.limit(); i++) {
                        out.write(buffer.get());
                    }
                    buffer.clear();
                }
            } catch (IOException e) {
                logger.error(e.getMessage(), e);
            }

            out.close();
            connection.getResponseCode();
```

```
            logger.info("HTTP response code is " + connection.getResponseCode());

        } catch (S3Exception | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

Use a classe `HttpClient` do JDK (desde a v11) para fazer upload.

```
    /* Use the JDK HttpClient (since v11) class to do the upload. */
    public void useHttpClientToPut(String presignedUrlString, File fileToPut,
 Map<String, String> metadata) {
        logger.info("Begin [{}] upload", fileToPut.toString());

        HttpRequest.Builder requestBuilder = HttpRequest.newBuilder();
        metadata.forEach((k, v) -> requestBuilder.header("x-amz-meta-" + k, v));

        HttpClient httpClient = HttpClient.newHttpClient();
        try {
            final HttpResponse<Void> response = httpClient.send(requestBuilder
                            .uri(new URL(presignedUrlString).toURI())

 .PUT(HttpRequest.BodyPublishers.ofFile(Path.of(fileToPut.toURI())))
                            .build(),
                    HttpResponse.BodyHandlers.discarding());

            logger.info("HTTP response code is " + response.statusCode());

        } catch (URISyntaxException | InterruptedException | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

Use a classe `SdkHttpClient` do AWS para Java V2 para fazer upload.

```
    /* Use the AWS SDK for Java V2 SdkHttpClient class to do the upload. */
    public void useSdkHttpClientToPut(String presignedUrlString, File fileToPut,
 Map<String, String> metadata) {
        logger.info("Begin [{}] upload", fileToPut.toString());

        try {
```

```
            URL presignedUrl = new URL(presignedUrlString);

            SdkHttpRequest.Builder requestBuilder = SdkHttpRequest.builder()
                    .method(SdkHttpMethod.PUT)
                    .uri(presignedUrl.toURI());
            // Add headers
            metadata.forEach((k, v) -> requestBuilder.putHeader("x-amz-meta-" + k,
v));
            // Finish building the request.
            SdkHttpRequest request = requestBuilder.build();

            HttpExecuteRequest executeRequest = HttpExecuteRequest.builder()
                    .request(request)
                    .contentStreamProvider(new
FileContentStreamProvider(fileToPut.toPath()))
                    .build();

            try (SdkHttpClient sdkHttpClient = ApacheHttpClient.create()) {
                HttpExecuteResponse response =
sdkHttpClient.prepareRequest(executeRequest).call();
                logger.info("Response code: {}",
response.httpResponse().statusCode());
            }
        } catch (URISyntaxException | IOException e) {
            logger.error(e.getMessage(), e);
        }
    }
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java code example performs the following tasks:
 *
 * 1. Creates an Amazon S3 bucket.
 * 2. Uploads an object to the bucket.
 * 3. Downloads the object to another local file.
 * 4. Uploads an object using multipart upload.
 * 5. List all objects located in the Amazon S3 bucket.
 * 6. Copies the object to another Amazon S3 bucket.
 * 7. Deletes the object from the Amazon S3 bucket.
 * 8. Deletes the Amazon S3 bucket.
 */

public class S3Scenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <bucketName> <key> <objectPath> <savePath> <toBucket>

                Where:
                    bucketName - The Amazon S3 bucket to create.
                    key - The key to use.
                    objectPath - The path where the file is located (for example,
 C:/AWS/book2.pdf).
```

```
                    savePath - The path where the file is saved after it's
downloaded (for example, C:/AWS/book2.pdf).
                    toBucket - An Amazon S3 bucket to where an object is copied to
(for example, C:/AWS/book2.pdf).\s
                    """;

        if (args.length != 5) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String key = args[1];
        String objectPath = args[2];
        String savePath = args[3];
        String toBucket = args[4];
        Region region = Region.US_EAST_1;
        S3Client s3 = S3Client.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon S3 example scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an Amazon S3 bucket.");
        createBucket(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Update a local file to the Amazon S3 bucket.");
        uploadLocalFile(s3, bucketName, key, objectPath);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Download the object to another local file.");
        getObjectBytes(s3, bucketName, key, savePath);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Perform a multipart upload.");
        String multipartKey = "multiPartKey";
        multipartUpload(s3, toBucket, multipartKey);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. List all objects located in the Amazon S3 bucket.");
        listAllObjects(s3, bucketName);
        anotherListExample(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Copy the object to another Amazon S3 bucket.");
        copyBucketObject(s3, bucketName, key, toBucket);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the object from the Amazon S3 bucket.");
        deleteObjectFromBucket(s3, bucketName, key);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Delete the Amazon S3 bucket.");
        deleteBucket(s3, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("All Amazon S3 operations were successfully performed");
        System.out.println(DASHES);
        s3.close();
    }

    // Create a bucket by using a S3Waiter object.
    public static void createBucket(S3Client s3Client, String bucketName) {
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
```

```
            WaiterResponse<HeadBucketResponse> waiterResponse =
s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteBucket(S3Client client, String bucket) {
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucket)
                .build();

        client.deleteBucket(deleteBucketRequest);
        System.out.println(bucket + " was deleted.");
    }

    /**
     * Upload an object in parts.
     */
    public static void multipartUpload(S3Client s3, String bucketName, String key) {
        int mB = 1024 * 1024;
        // First create a multipart upload and get the upload id.
        CreateMultipartUploadRequest createMultipartUploadRequest =
CreateMultipartUploadRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        CreateMultipartUploadResponse response =
s3.createMultipartUpload(createMultipartUploadRequest);
        String uploadId = response.uploadId();
        System.out.println(uploadId);

        // Upload all the different parts of the object.
        UploadPartRequest uploadPartRequest1 = UploadPartRequest.builder()
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)
                .partNumber(1).build();
```

```
        String etag1 = s3.uploadPart(uploadPartRequest1,
RequestBody.fromByteBuffer(getRandomByteBuffer(5 * mB)))
                .eTag();
        CompletedPart part1 =
CompletedPart.builder().partNumber(1).eTag(etag1).build();

        UploadPartRequest uploadPartRequest2 =
UploadPartRequest.builder().bucket(bucketName).key(key)
                .uploadId(uploadId)
                .partNumber(2).build();
        String etag2 = s3.uploadPart(uploadPartRequest2,
RequestBody.fromByteBuffer(getRandomByteBuffer(3 * mB)))
                .eTag();
        CompletedPart part2 =
CompletedPart.builder().partNumber(2).eTag(etag2).build();

        // Call completeMultipartUpload operation to tell S3 to merge all uploaded
        // parts and finish the multipart operation.
        CompletedMultipartUpload completedMultipartUpload =
CompletedMultipartUpload.builder()
                .parts(part1, part2)
                .build();

        CompleteMultipartUploadRequest completeMultipartUploadRequest =
CompleteMultipartUploadRequest.builder()
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)
                .multipartUpload(completedMultipartUpload)
                .build();

        s3.completeMultipartUpload(completeMultipartUploadRequest);
    }

    private static ByteBuffer getRandomByteBuffer(int size) {
        byte[] b = new byte[size];
        new Random().nextBytes(b);
        return ByteBuffer.wrap(b);
    }

    public static void getObjectBytes(S3Client s3, String bucketName, String
keyName, String path) {
        try {
            GetObjectRequest objectRequest = GetObjectRequest
```

```
                    .builder()
                    .key(keyName)
                    .bucket(bucketName)
                    .build();

            ResponseBytes<GetObjectResponse> objectBytes =
s3.getObjectAsBytes(objectRequest);
            byte[] data = objectBytes.asByteArray();

            // Write the data to a local file.
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from an S3 object");
            os.close();

        } catch (IOException ex) {
            ex.printStackTrace();
        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void uploadLocalFile(S3Client s3, String bucketName, String key,
String objectPath) {
        PutObjectRequest objectRequest = PutObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        s3.putObject(objectRequest, RequestBody.fromFile(new File(objectPath)));
    }

    public static void listAllObjects(S3Client s3, String bucketName) {
        ListObjectsV2Request listObjectsReqManual = ListObjectsV2Request.builder()
                .bucket(bucketName)
                .maxKeys(1)
                .build();

        boolean done = false;
        while (!done) {
            ListObjectsV2Response listObjResponse =
s3.listObjectsV2(listObjectsReqManual);
```

```
            for (S3Object content : listObjResponse.contents()) {
                System.out.println(content.key());
            }

            if (listObjResponse.nextContinuationToken() == null) {
                done = true;
            }

            listObjectsReqManual = listObjectsReqManual.toBuilder()
                    .continuationToken(listObjResponse.nextContinuationToken())
                    .build();
        }
    }

    public static void anotherListExample(S3Client s3, String bucketName) {
        ListObjectsV2Request listReq = ListObjectsV2Request.builder()
                .bucket(bucketName)
                .maxKeys(1)
                .build();

        ListObjectsV2Iterable listRes = s3.listObjectsV2Paginator(listReq);

        // Process response pages.
        listRes.stream()
                .flatMap(r -> r.contents().stream())
                .forEach(content -> System.out.println(" Key: " + content.key() + "
size = " + content.size()));

        // Helper method to work with paginated collection of items directly.
        listRes.contents().stream()
                .forEach(content -> System.out.println(" Key: " + content.key() + "
size = " + content.size()));

        for (S3Object content : listRes.contents()) {
            System.out.println(" Key: " + content.key() + " size = " +
content.size());
        }
    }

    public static void deleteObjectFromBucket(S3Client s3, String bucketName, String
key) {
        DeleteObjectRequest deleteObjectRequest = DeleteObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
```

```
                .build();

        s3.deleteObject(deleteObjectRequest);
        System.out.println(key + " was deleted");
    }

    public static String copyBucketObject(S3Client s3, String fromBucket, String
 objectKey, String toBucket) {
        String encodedUrl = null;
        try {
            encodedUrl = URLEncoder.encode(fromBucket + "/" + objectKey,
 StandardCharsets.UTF_8.toString());
        } catch (UnsupportedEncodingException e) {
            System.out.println("URL could not be encoded: " + e.getMessage());
        }
        CopyObjectRequest copyReq = CopyObjectRequest.builder()
                .copySource(encodedUrl)
                .destinationBucket(toBucket)
                .destinationKey(objectKey)
                .build();

        try {
            CopyObjectResponse copyRes = s3.copyObject(copyReq);
            System.out.println("The " + objectKey + " was copied to " + toBucket);
            return copyRes.copyObjectResult().toString();

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects

- GetObject
- ListObjectsV2
- PutObject

Analisar URIs

O exemplo de código a seguir mostra como usar analisar URIs do Amazon S3 para extrair componentes importantes como o nome do bucket e a chave do objeto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Analise um URI do Amazon S3 usando a classe S3Uri.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.S3Uri;
import software.amazon.awssdk.services.s3.S3Utilities;

import java.net.URI;
import java.util.List;
import java.util.Map;

    /**
     *
     * @param s3Client    - An S3Client through which you acquire an S3Uri instance.
     * @param s3ObjectUrl - A complex URL (String) that is used to demonstrate S3Uri
     *                    capabilities.
     */
    public static void parseS3UriExample(S3Client s3Client, String s3ObjectUrl) {
        logger.info(s3ObjectUrl);
        // Console output:
        // 'https://s3.us-west-1.amazonaws.com/myBucket/resources/doc.txt?
versionId=abc123&partNumber=77&partNumber=88'.
```

```
        // Create an S3Utilities object using the configuration of the s3Client.
        S3Utilities s3Utilities = s3Client.utilities();

        // From a String URL create a URI object to pass to the parseUri() method.
        URI uri = URI.create(s3ObjectUrl);
        S3Uri s3Uri = s3Utilities.parseUri(uri);

        // If the URI contains no value for the Region, bucket or key, the SDK
returns
        // an empty Optional.
        // The SDK returns decoded URI values.

        Region region = s3Uri.region().orElse(null);
        log("region", region);
        // Console output: 'region: us-west-1'.

        String bucket = s3Uri.bucket().orElse(null);
        log("bucket", bucket);
        // Console output: 'bucket: myBucket'.

        String key = s3Uri.key().orElse(null);
        log("key", key);
        // Console output: 'key: resources/doc.txt'.

        Boolean isPathStyle = s3Uri.isPathStyle();
        log("isPathStyle", isPathStyle);
        // Console output: 'isPathStyle: true'.

        // If the URI contains no query parameters, the SDK returns an empty map.
        Map<String, List<String>> queryParams = s3Uri.rawQueryParameters();
        log("rawQueryParameters", queryParams);
        // Console output: 'rawQueryParameters: {versionId=[abc123], partNumber=[77,
        // 88]}'.

        // Retrieve the first or all values for a query parameter as shown in the
        // following code.
        String versionId =
s3Uri.firstMatchingRawQueryParameter("versionId").orElse(null);
        log("firstMatchingRawQueryParameter-versionId", versionId);
        // Console output: 'firstMatchingRawQueryParameter-versionId: abc123'.

        String partNumber =
s3Uri.firstMatchingRawQueryParameter("partNumber").orElse(null);
```

```
        log("firstMatchingRawQueryParameter-partNumber", partNumber);
        // Console output: 'firstMatchingRawQueryParameter-partNumber: 77'.

        List<String> partNumbers =
 s3Uri.firstMatchingRawQueryParameters("partNumber");
        log("firstMatchingRawQueryParameter", partNumbers);
        // Console output: 'firstMatchingRawQueryParameter: [77, 88]'.

        /*
         * Object keys and query parameters with reserved or unsafe characters, must
 be
         * URL-encoded.
         * For example replace whitespace " " with "%20".
         * Valid:
         * "https://s3.us-west-1.amazonaws.com/myBucket/object%20key?query=
%5Bbrackets%5D"
         * Invalid:
         * "https://s3.us-west-1.amazonaws.com/myBucket/object key?query=[brackets]"
         *
         * Virtual-hosted-style URIs with bucket names that contain a dot, ".", the
 dot
         * must not be URL-encoded.
         * Valid: "https://my.Bucket.s3.us-west-1.amazonaws.com/key"
         * Invalid: "https://my%2EBucket.s3.us-west-1.amazonaws.com/key"
         */
    }

    private static void log(String s3UriElement, Object element) {
        if (element == null) {
            logger.info("{}: {}", s3UriElement, "null");
        } else {
            logger.info("{}: {}", s3UriElement, element.toString());
        }
    }
```

Realizar um carregamento fracionado

O exemplo de código a seguir mostra como executar um carregamento fracionado de um objeto do Amazon S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos de código usam as importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.CompletedMultipartUpload;
import software.amazon.awssdk.services.s3.model.CompletedPart;
import software.amazon.awssdk.services.s3.model.CreateMultipartUploadResponse;
import software.amazon.awssdk.services.s3.model.UploadPartRequest;
import software.amazon.awssdk.services.s3.model.UploadPartResponse;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;

import java.io.IOException;
import java.io.RandomAccessFile;
import java.net.URISyntaxException;
import java.net.URL;
import java.nio.ByteBuffer;
import java.nio.file.Paths;
import java.util.ArrayList;
import java.util.List;
import java.util.Objects;
import java.util.UUID;
```

Use o Gerenciador de Transferências do S3 na parte superior do cliente do S3 baseado no AWS CRT para realizar de forma transparente um carregamento fracionado quando o tamanho do conteúdo exceder um limite. O limite padrão é 8 MB.

```
    public void multipartUploadWithTransferManager(String filePath) {
```

```
        S3TransferManager transferManager = S3TransferManager.create();
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b
                        .bucket(bucketName)
                        .key(key))
                .source(Paths.get(filePath))
                .build();
        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);
        fileUpload.completionFuture().join();
        transferManager.close();
    }
```

Use a API S3Client ou (API S3AsyncClient) para realizar um upload de várias partes.

```
    public void multipartUploadWithS3Client(String filePath) {

        // Initiate the multipart upload.
        CreateMultipartUploadResponse createMultipartUploadResponse =
s3Client.createMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key));
        String uploadId = createMultipartUploadResponse.uploadId();

        // Upload the parts of the file.
        int partNumber = 1;
        List<CompletedPart> completedParts = new ArrayList<>();
        ByteBuffer bb = ByteBuffer.allocate(1024 * 1024 * 5); // 5 MB byte buffer

        try (RandomAccessFile file = new RandomAccessFile(filePath, "r")) {
            long fileSize = file.length();
            int position = 0;
            while (position < fileSize) {
                file.seek(position);
                int read = file.getChannel().read(bb);

                bb.flip(); // Swap position and limit before reading from the
buffer.
                UploadPartRequest uploadPartRequest = UploadPartRequest.builder()
                        .bucket(bucketName)
                        .key(key)
                        .uploadId(uploadId)
                        .partNumber(partNumber)
```

```
                        .build();

                UploadPartResponse partResponse = s3Client.uploadPart(
                        uploadPartRequest,
                        RequestBody.fromByteBuffer(bb));

                CompletedPart part = CompletedPart.builder()
                        .partNumber(partNumber)
                        .eTag(partResponse.eTag())
                        .build();
                completedParts.add(part);

                bb.clear();
                position += read;
                partNumber++;
            }
        } catch (IOException e) {
            logger.error(e.getMessage());
        }

        // Complete the multipart upload.
        s3Client.completeMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)

.multipartUpload(CompletedMultipartUpload.builder().parts(completedParts).build()));
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - UploadPart

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chame funções que transferem arquivos de e para um bucket do S3 usando o TransferManager S3.

```
   public Integer downloadObjectsToDirectory(S3TransferManager transferManager,
           String destinationPath, String bucketName) {
       DirectoryDownload directoryDownload =
transferManager.downloadDirectory(DownloadDirectoryRequest.builder()
               .destination(Paths.get(destinationPath))
               .bucket(bucketName)
               .build());
       CompletedDirectoryDownload completedDirectoryDownload =
directoryDownload.completionFuture().join();

       completedDirectoryDownload.failedTransfers()
               .forEach(fail -> logger.warn("Object [{}] failed to transfer",
fail.toString()));
       return completedDirectoryDownload.failedTransfers().size();
   }
```

Carregue um diretório local inteiro.

```
   public Integer uploadDirectory(S3TransferManager transferManager,
           String sourceDirectory, String bucketName) {
       DirectoryUpload directoryUpload =
transferManager.uploadDirectory(UploadDirectoryRequest.builder()
               .source(Paths.get(sourceDirectory))
               .bucket(bucketName)
               .build());

       CompletedDirectoryUpload completedDirectoryUpload =
directoryUpload.completionFuture().join();
```

```
        completedDirectoryUpload.failedTransfers()
                .forEach(fail -> logger.warn("Object [{}] failed to transfer",
 fail.toString()));
        return completedDirectoryUpload.failedTransfers().size();
    }
```

Carregue um único arquivo.

```
    public String uploadFile(S3TransferManager transferManager, String bucketName,
            String key, String filePath) {
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b.bucket(bucketName).key(key))
                .addTransferListener(LoggingTransferListener.create())
                .source(Paths.get(filePath))
                .build();

        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);

        CompletedFileUpload uploadResult = fileUpload.completionFuture().join();
        return uploadResult.response().eTag();
    }
```

Upload de fluxo de tamanho desconhecido

O exemplo de código a seguir mostra como fazer upload de um fluxo de tamanho desconhecido em um objeto do Amazon S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use o Cliente do S3 baseado em CRT da AWS.

```
import com.example.s3.util.AsyncExampleUtils;
import org.slf4j.Logger;
```

```
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.async.AsyncRequestBody;
import software.amazon.awssdk.core.async.BlockingInputStreamAsyncRequestBody;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.services.s3.S3AsyncClient;
import software.amazon.awssdk.services.s3.model.PutObjectResponse;

import java.io.ByteArrayInputStream;
import java.util.UUID;
import java.util.concurrent.CompletableFuture;

    /**
     * @param s33CrtAsyncClient - To upload content from a stream of unknown size,
 use the AWS CRT-based S3 client. For more information, see
     *                          https://docs.aws.amazon.com/sdk-for-java/latest/
developer-guide/crt-based-s3-client.html.
     * @param bucketName - The name of the bucket.
     * @param key - The name of the object.
     * @return software.amazon.awssdk.services.s3.model.PutObjectResponse - Returns
 metadata pertaining to the put object operation.
     */
    public PutObjectResponse putObjectFromStream(S3AsyncClient s33CrtAsyncClient,
 String bucketName, String key) {

        BlockingInputStreamAsyncRequestBody body =
                AsyncRequestBody.forBlockingInputStream(null); // 'null' indicates a
 stream will be provided later.

        CompletableFuture<PutObjectResponse> responseFuture =
                s33CrtAsyncClient.putObject(r -> r.bucket(bucketName).key(key),
 body);

        // AsyncExampleUtils.randomString() returns a random string up to 100
 characters.
        String randomString = AsyncExampleUtils.randomString();
        logger.info("random string to upload: {}: length={}", randomString,
 randomString.length());

        // Provide the stream of data to be uploaded.
        body.writeInputStream(new ByteArrayInputStream(randomString.getBytes()));

        PutObjectResponse response = responseFuture.join(); // Wait for the
 response.
        logger.info("Object {} uploaded to bucket {}.", key, bucketName);
```

```
        return response;
    }
}
```

Use o Gerenciador de transferências do Amazon S3.

```
import com.example.s3.util.AsyncExampleUtils;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.async.AsyncRequestBody;
import software.amazon.awssdk.core.async.BlockingInputStreamAsyncRequestBody;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.CompletedUpload;
import software.amazon.awssdk.transfer.s3.model.Upload;

import java.io.ByteArrayInputStream;
import java.util.UUID;

    /**
     * @param transferManager - To upload content from a stream of unknown size, use
 the S3TransferManager based on the AWS CRT-based S3 client.
     *                       For more information, see https://docs.aws.amazon.com/
sdk-for-java/latest/developer-guide/transfer-manager.html.
     * @param bucketName - The name of the bucket.
     * @param key - The name of the object.
     * @return - software.amazon.awssdk.transfer.s3.model.CompletedUpload - The
 result of the completed upload.
     */
    public CompletedUpload uploadStream(S3TransferManager transferManager, String
 bucketName, String key) {

        BlockingInputStreamAsyncRequestBody body =
                AsyncRequestBody.forBlockingInputStream(null); // 'null' indicates a
 stream will be provided later.

        Upload upload = transferManager.upload(builder -> builder
                .requestBody(body)
                .putObjectRequest(req -> req.bucket(bucketName).key(key))
                .build());
```

```
        // AsyncExampleUtils.randomString() returns a random string up to 100
 characters.
        String randomString = AsyncExampleUtils.randomString();
        logger.info("random string to upload: {}: length={}", randomString,
 randomString.length());

        // Provide the stream of data to be uploaded.
        body.writeInputStream(new ByteArrayInputStream(randomString.getBytes()));

        return upload.completionFuture().join();
    }
}
```

Usar somas de verificação

O exemplo de código a seguir mostra como usar somas de verificação para trabalhar com um objeto do Amazon S3.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Os exemplos de código usam um subconjunto das importações a seguir.

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import software.amazon.awssdk.core.exception.SdkException;
import software.amazon.awssdk.core.sync.RequestBody;
import software.amazon.awssdk.services.s3.S3Client;
import software.amazon.awssdk.services.s3.model.ChecksumAlgorithm;
import software.amazon.awssdk.services.s3.model.ChecksumMode;
import software.amazon.awssdk.services.s3.model.CompletedMultipartUpload;
import software.amazon.awssdk.services.s3.model.CompletedPart;
import software.amazon.awssdk.services.s3.model.CreateMultipartUploadResponse;
import software.amazon.awssdk.services.s3.model.GetObjectResponse;
```

```
import software.amazon.awssdk.services.s3.model.UploadPartRequest;
import software.amazon.awssdk.services.s3.model.UploadPartResponse;
import software.amazon.awssdk.services.s3.waiters.S3Waiter;
import software.amazon.awssdk.transfer.s3.S3TransferManager;
import software.amazon.awssdk.transfer.s3.model.FileUpload;
import software.amazon.awssdk.transfer.s3.model.UploadFileRequest;

import java.io.FileInputStream;
import java.io.IOException;
import java.io.RandomAccessFile;
import java.net.URISyntaxException;
import java.net.URL;
import java.nio.ByteBuffer;
import java.nio.file.Paths;
import java.security.DigestInputStream;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
import java.util.ArrayList;
import java.util.Base64;
import java.util.List;
import java.util.Objects;
import java.util.UUID;
```

Especifique um algoritmo de soma de verificação para o método `putObject` ao criar `PutObjectRequest`.

```
    public void putObjectWithChecksum() {
        s3Client.putObject(b -> b
                .bucket(bucketName)
                .key(key)
                .checksumAlgorithm(ChecksumAlgorithm.CRC32),
                RequestBody.fromString("This is a test"));
    }
```

Verifique a soma de verificação do `getObject` método ao criar o. GetObjectRequest

```
    public GetObjectResponse getObjectWithChecksum() {
        return s3Client.getObject(b -> b
                .bucket(bucketName)
                .key(key)
                .checksumMode(ChecksumMode.ENABLED))
```

```
                .response();
    }
```

Calcule previamente uma soma de verificação para o método `putObject` ao criar o `PutObjectRequest`.

```
    public void putObjectWithPrecalculatedChecksum(String filePath) {
        String checksum = calculateChecksum(filePath, "SHA-256");

        s3Client.putObject((b -> b
                .bucket(bucketName)
                .key(key)
                .checksumSHA256(checksum)),
                RequestBody.fromFile(Paths.get(filePath)));
    }
```

Use o Gerenciador de Transferências do S3 na parte superior do cliente do S3 baseado no AWS CRT para realizar de forma transparente um carregamento fracionado quando o tamanho do conteúdo exceder um limite. O limite padrão é 8 MB.

Você pode especificar um algoritmo de soma de verificação para o SDK usar. Por padrão, o SDK usa o algoritmo CRC32.

```
    public void multipartUploadWithChecksumTm(String filePath) {
        S3TransferManager transferManager = S3TransferManager.create();
        UploadFileRequest uploadFileRequest = UploadFileRequest.builder()
                .putObjectRequest(b -> b
                        .bucket(bucketName)
                        .key(key)
                        .checksumAlgorithm(ChecksumAlgorithm.SHA1))
                .source(Paths.get(filePath))
                .build();
        FileUpload fileUpload = transferManager.uploadFile(uploadFileRequest);
        fileUpload.completionFuture().join();
        transferManager.close();
    }
```

Use a API S3Client ou (API S3AsyncClient) para realizar um upload de várias partes. Se você especificar uma soma de verificação adicional, deverá indicar o algoritmo a ser usado no início

do carregamento. Você também deve especificar o algoritmo para a solicitação de cada parte e fornecer a soma de verificação calculada para cada parte após o carregamento.

```
   public void multipartUploadWithChecksumS3Client(String filePath) {
       ChecksumAlgorithm algorithm = ChecksumAlgorithm.CRC32;

       // Initiate the multipart upload.
       CreateMultipartUploadResponse createMultipartUploadResponse =
s3Client.createMultipartUpload(b -> b
               .bucket(bucketName)
               .key(key)
               .checksumAlgorithm(algorithm)); // Checksum specified on initiation.
       String uploadId = createMultipartUploadResponse.uploadId();

       // Upload the parts of the file.
       int partNumber = 1;
       List<CompletedPart> completedParts = new ArrayList<>();
       ByteBuffer bb = ByteBuffer.allocate(1024 * 1024 * 5); // 5 MB byte buffer

       try (RandomAccessFile file = new RandomAccessFile(filePath, "r")) {
           long fileSize = file.length();
           int position = 0;
           while (position < fileSize) {
               file.seek(position);
               int read = file.getChannel().read(bb);

               bb.flip(); // Swap position and limit before reading from the
buffer.
               UploadPartRequest uploadPartRequest = UploadPartRequest.builder()
                       .bucket(bucketName)
                       .key(key)
                       .uploadId(uploadId)
                       .checksumAlgorithm(algorithm) // Checksum specified on each
part.
                       .partNumber(partNumber)
                       .build();

               UploadPartResponse partResponse = s3Client.uploadPart(
                       uploadPartRequest,
                       RequestBody.fromByteBuffer(bb));

               CompletedPart part = CompletedPart.builder()
                       .partNumber(partNumber)
```

```
                        .checksumCRC32(partResponse.checksumCRC32()) // Provide the
calculated checksum.
                        .eTag(partResponse.eTag())
                        .build();
                completedParts.add(part);

                bb.clear();
                position += read;
                partNumber++;
            }
        } catch (IOException e) {
            System.err.println(e.getMessage());
        }

        // Complete the multipart upload.
        s3Client.completeMultipartUpload(b -> b
                .bucket(bucketName)
                .key(key)
                .uploadId(uploadId)

.multipartUpload(CompletedMultipartUpload.builder().parts(completedParts).build()));
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - UploadPart

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Java.

```
package example;

import software.amazon.awssdk.services.s3.model.HeadObjectRequest;
import software.amazon.awssdk.services.s3.model.HeadObjectResponse;
import software.amazon.awssdk.services.s3.S3Client;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.S3Event;
import
 com.amazonaws.services.lambda.runtime.events.models.s3.S3EventNotification.S3EventNotificat

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class Handler implements RequestHandler<S3Event, String> {
    private static final Logger logger = LoggerFactory.getLogger(Handler.class);
    @Override
    public String handleRequest(S3Event s3event, Context context) {
        try {
          S3EventNotificationRecord record = s3event.getRecords().get(0);
          String srcBucket = record.getS3().getBucket().getName();
          String srcKey = record.getS3().getObject().getUrlDecodedKey();

          S3Client s3Client = S3Client.builder().build();
          HeadObjectResponse headObject = getHeadObject(s3Client, srcBucket,
 srcKey);

          logger.info("Successfully retrieved " + srcBucket + "/" + srcKey + " of
 type " + headObject.contentType());

          return "Ok";
        } catch (Exception e) {
```

```
            throw new RuntimeException(e);
        }
    }

    private HeadObjectResponse getHeadObject(S3Client s3Client, String bucket,
 String key) {
        HeadObjectRequest headObjectRequest = HeadObjectRequest.builder()
                .bucket(bucket)
                .key(key)
                .build();
        return s3Client.headObject(headObjectRequest);
    }
}
```

Exemplos do S3 Glacier usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o S3 Glacier.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um vault

O exemplo de código a seguir mostra como criar um vault (cofre) do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.CreateVaultRequest;
import software.amazon.awssdk.services.glacier.model.CreateVaultResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateVault {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <vaultName>

                Where:
                   vaultName - The name of the vault to create.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();
```

```
        createGlacierVault(glacier, vaultName);
        glacier.close();
    }

    public static void createGlacierVault(GlacierClient glacier, String vaultName) {
        try {
            CreateVaultRequest vaultRequest = CreateVaultRequest.builder()
                    .vaultName(vaultName)
                    .build();

            CreateVaultResponse createVaultResult =
 glacier.createVault(vaultRequest);
            System.out.println("The URI of the new vault is " +
 createVaultResult.location());

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateVaulta Referência AWS SDK for Java 2.x da API.

Excluir um cofre

O exemplo de código a seguir mostra como excluir um cofre do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DeleteVaultRequest;
import software.amazon.awssdk.services.glacier.model.GlacierException;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteVault {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <vaultName>

                Where:
                   vaultName - The name of the vault to delete.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteGlacierVault(glacier, vaultName);
        glacier.close();
    }

    public static void deleteGlacierVault(GlacierClient glacier, String vaultName) {
        try {
            DeleteVaultRequest delVaultRequest = DeleteVaultRequest.builder()
                    .vaultName(vaultName)
                    .build();

            glacier.deleteVault(delVaultRequest);
            System.out.println("The vault was deleted!");

        } catch (GlacierException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteVaulta Referência AWS SDK for Java 2.x da API.

Excluir um arquivo

O exemplo de código a seguir mostra como excluir um arquivo do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DeleteArchiveRequest;
import software.amazon.awssdk.services.glacier.model.GlacierException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteArchive {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <vaultName> <accountId> <archiveId>

                Where:
```

```
                    vaultName - The name of the vault that contains the archive to
 delete.
                    accountId - The account ID value.
                    archiveId - The archive ID value.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        String accountId = args[1];
        String archiveId = args[2];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        deleteGlacierArchive(glacier, vaultName, accountId, archiveId);
        glacier.close();
    }

    public static void deleteGlacierArchive(GlacierClient glacier, String vaultName,
 String accountId,
            String archiveId) {
        try {
            DeleteArchiveRequest delArcRequest = DeleteArchiveRequest.builder()
                    .vaultName(vaultName)
                    .accountId(accountId)
                    .archiveId(archiveId)
                    .build();

            glacier.deleteArchive(delArcRequest);
            System.out.println("The archive was deleted.");

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteArchivea Referência AWS SDK for Java 2.x da API.

Liste cofres

O exemplo de código a seguir mostra como listar cofres do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.model.ListVaultsRequest;
import software.amazon.awssdk.services.glacier.model.ListVaultsResponse;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.DescribeVaultOutput;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListVaults {
    public static void main(String[] args) {
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listAllVault(glacier);
        glacier.close();
    }

    public static void listAllVault(GlacierClient glacier) {
        boolean listComplete = false;
        String newMarker = null;
        int totalVaults = 0;
        System.out.println("Your Amazon Glacier vaults:");
```

```
        try {
            while (!listComplete) {
                ListVaultsResponse response = null;
                if (newMarker != null) {
                    ListVaultsRequest request = ListVaultsRequest.builder()
                            .marker(newMarker)
                            .build();

                    response = glacier.listVaults(request);
                } else {
                    ListVaultsRequest request = ListVaultsRequest.builder()
                            .build();
                    response = glacier.listVaults(request);
                }

                List<DescribeVaultOutput> vaultList = response.vaultList();
                for (DescribeVaultOutput v : vaultList) {
                    totalVaults += 1;
                    System.out.println("* " + v.vaultName());
                }

                // Check for further results.
                newMarker = response.marker();
                if (newMarker == null) {
                    listComplete = true;
                }
            }

            if (totalVaults == 0) {
                System.out.println("No vaults found.");
            }

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListVaultsa Referência AWS SDK for Java 2.x da API.

Recuperar um inventário do cofre

O exemplo de código a seguir mostra como recuperar um inventário de cofre do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.ResponseBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.JobParameters;
import software.amazon.awssdk.services.glacier.model.InitiateJobResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import software.amazon.awssdk.services.glacier.model.InitiateJobRequest;
import software.amazon.awssdk.services.glacier.model.DescribeJobRequest;
import software.amazon.awssdk.services.glacier.model.DescribeJobResponse;
import software.amazon.awssdk.services.glacier.model.GetJobOutputRequest;
import software.amazon.awssdk.services.glacier.model.GetJobOutputResponse;
import java.io.File;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.OutputStream;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ArchiveDownload {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <vaultName> <accountId> <path>
```

```
                Where:
                   vaultName - The name of the vault.
                   accountId - The account ID value.
                   path - The path where the file is written to.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String vaultName = args[0];
        String accountId = args[1];
        String path = args[2];
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String jobNum = createJob(glacier, vaultName, accountId);
        checkJob(glacier, jobNum, vaultName, accountId, path);
        glacier.close();
    }

    public static String createJob(GlacierClient glacier, String vaultName, String
accountId) {
        try {
            JobParameters job = JobParameters.builder()
                    .type("inventory-retrieval")
                    .build();

            InitiateJobRequest initJob = InitiateJobRequest.builder()
                    .jobParameters(job)
                    .accountId(accountId)
                    .vaultName(vaultName)
                    .build();

            InitiateJobResponse response = glacier.initiateJob(initJob);
            System.out.println("The job ID is: " + response.jobId());
            System.out.println("The relative URI path of the job is: " +
response.location());
            return response.jobId();

        } catch (GlacierException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
```

```
            System.exit(1);

        }
        return "";
    }

    // Poll S3 Glacier = Polling a Job may take 4-6 hours according to the
    // Documentation.
    public static void checkJob(GlacierClient glacier, String jobId, String name,
String account, String path) {
        try {
            boolean finished = false;
            String jobStatus;
            int yy = 0;

            while (!finished) {
                DescribeJobRequest jobRequest = DescribeJobRequest.builder()
                        .jobId(jobId)
                        .accountId(account)
                        .vaultName(name)
                        .build();

                DescribeJobResponse response = glacier.describeJob(jobRequest);
                jobStatus = response.statusCodeAsString();

                if (jobStatus.compareTo("Succeeded") == 0)
                    finished = true;
                else {
                    System.out.println(yy + " status is: " + jobStatus);
                    Thread.sleep(1000);
                }
                yy++;
            }

            System.out.println("Job has Succeeded");
            GetJobOutputRequest jobOutputRequest = GetJobOutputRequest.builder()
                    .jobId(jobId)
                    .vaultName(name)
                    .accountId(account)
                    .build();

            ResponseBytes<GetJobOutputResponse> objectBytes =
glacier.getJobOutputAsBytes(jobOutputRequest);
            // Write the data to a local file.
```

```
            byte[] data = objectBytes.asByteArray();
            File myFile = new File(path);
            OutputStream os = new FileOutputStream(myFile);
            os.write(data);
            System.out.println("Successfully obtained bytes from a Glacier vault");
            os.close();

        } catch (GlacierException | InterruptedException | IOException e) {
            System.out.println(e.getMessage());
            System.exit(1);

        }
    }
}
```

- Para obter detalhes da API, consulte InitiateJoba Referência AWS SDK for Java 2.x da API.

Baixe um arquivo em um cofre

O exemplo de código a seguir mostra como fazer upload de um arquivo em um cofre do Amazon S3 Glacier.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.glacier.GlacierClient;
import software.amazon.awssdk.services.glacier.model.UploadArchiveRequest;
import software.amazon.awssdk.services.glacier.model.UploadArchiveResponse;
import software.amazon.awssdk.services.glacier.model.GlacierException;
import java.io.File;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.io.FileInputStream;
import java.io.IOException;
import java.security.MessageDigest;
```

```
import java.security.NoSuchAlgorithmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UploadArchive {

    static final int ONE_MB = 1024 * 1024;

    public static void main(String[] args) {
        final String usage = """

                Usage:   <strPath> <vaultName>\s

                Where:
                   strPath - The path to the archive to upload (for example, C:\\AWS
\\test.pdf).
                   vaultName - The name of the vault.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String strPath = args[0];
        String vaultName = args[1];
        File myFile = new File(strPath);
        Path path = Paths.get(strPath);
        GlacierClient glacier = GlacierClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String archiveId = uploadContent(glacier, path, vaultName, myFile);
        System.out.println("The ID of the archived item is " + archiveId);
        glacier.close();
    }
```

```
   public static String uploadContent(GlacierClient glacier, Path path, String
vaultName, File myFile) {
       // Get an SHA-256 tree hash value.
       String checkVal = computeSHA256(myFile);
       try {
           UploadArchiveRequest uploadRequest = UploadArchiveRequest.builder()
                   .vaultName(vaultName)
                   .checksum(checkVal)
                   .build();

           UploadArchiveResponse res = glacier.uploadArchive(uploadRequest, path);
           return res.archiveId();

       } catch (GlacierException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }

   private static String computeSHA256(File inputFile) {
       try {
           byte[] treeHash = computeSHA256TreeHash(inputFile);
           System.out.printf("SHA-256 tree hash = %s\n", toHex(treeHash));
           return toHex(treeHash);

       } catch (IOException ioe) {
           System.err.format("Exception when reading from file %s: %s", inputFile,
ioe.getMessage());
           System.exit(-1);

       } catch (NoSuchAlgorithmException nsae) {
           System.err.format("Cannot locate MessageDigest algorithm for SHA-256:
%s", nsae.getMessage());
           System.exit(-1);
       }
       return "";
   }

   public static byte[] computeSHA256TreeHash(File inputFile) throws IOException,
           NoSuchAlgorithmException {

       byte[][] chunkSHA256Hashes = getChunkSHA256Hashes(inputFile);
       return computeSHA256TreeHash(chunkSHA256Hashes);
```

```
    }

    /**
     * Computes an SHA256 checksum for each 1 MB chunk of the input file. This
     * includes the checksum for the last chunk, even if it's smaller than 1 MB.
     */
    public static byte[][] getChunkSHA256Hashes(File file) throws IOException,
            NoSuchAlgorithmException {

        MessageDigest md = MessageDigest.getInstance("SHA-256");
        long numChunks = file.length() / ONE_MB;
        if (file.length() % ONE_MB > 0) {
            numChunks++;
        }

        if (numChunks == 0) {
            return new byte[][] { md.digest() };
        }

        byte[][] chunkSHA256Hashes = new byte[(int) numChunks][];
        FileInputStream fileStream = null;

        try {
            fileStream = new FileInputStream(file);
            byte[] buff = new byte[ONE_MB];

            int bytesRead;
            int idx = 0;

            while ((bytesRead = fileStream.read(buff, 0, ONE_MB)) > 0) {
                md.reset();
                md.update(buff, 0, bytesRead);
                chunkSHA256Hashes[idx++] = md.digest();
            }

            return chunkSHA256Hashes;

        } finally {
            if (fileStream != null) {
                try {
                    fileStream.close();
                } catch (IOException ioe) {
                    System.err.printf("Exception while closing %s.\n %s",
file.getName(),
```

```
                            ioe.getMessage());
                }
            }
        }
    }

    /**
     * Computes the SHA-256 tree hash for the passed array of 1 MB chunk
     * checksums.
     */
    public static byte[] computeSHA256TreeHash(byte[][] chunkSHA256Hashes)
            throws NoSuchAlgorithmException {

        MessageDigest md = MessageDigest.getInstance("SHA-256");
        byte[][] prevLvlHashes = chunkSHA256Hashes;
        while (prevLvlHashes.length > 1) {
            int len = prevLvlHashes.length / 2;
            if (prevLvlHashes.length % 2 != 0) {
                len++;
            }

            byte[][] currLvlHashes = new byte[len][];
            int j = 0;
            for (int i = 0; i < prevLvlHashes.length; i = i + 2, j++) {

                // If there are at least two elements remaining.
                if (prevLvlHashes.length - i > 1) {

                    // Calculate a digest of the concatenated nodes.
                    md.reset();
                    md.update(prevLvlHashes[i]);
                    md.update(prevLvlHashes[i + 1]);
                    currLvlHashes[j] = md.digest();

                } else { // Take care of the remaining odd chunk
                    currLvlHashes[j] = prevLvlHashes[i];
                }
            }

            prevLvlHashes = currLvlHashes;
        }

        return prevLvlHashes[0];
    }
```

```
    /**
     * Returns the hexadecimal representation of the input byte array
     */
    public static String toHex(byte[] data) {
        StringBuilder sb = new StringBuilder(data.length * 2);
        for (byte datum : data) {
            String hex = Integer.toHexString(datum & 0xFF);

            if (hex.length() == 1) {
                // Append leading zero.
                sb.append("0");
            }
            sb.append(hex);
        }
        return sb.toString().toLowerCase();
    }
}
```

- Para obter detalhes da API, consulte UploadArchivea Referência AWS SDK for Java 2.x da API.

SageMaker exemplos usando o SDK for Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x with SageMaker.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá SageMaker

O exemplo de código a seguir mostra como começar a usar o SageMaker.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloSageMaker {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        SageMakerClient sageMakerClient = SageMakerClient.builder()
                .region(region)
                .build();

        listBooks(sageMakerClient);
        sageMakerClient.close();
    }

    public static void listBooks(SageMakerClient sageMakerClient) {
        try {
            ListNotebookInstancesResponse notebookInstancesResponse =
 sageMakerClient.listNotebookInstances();
            List<NotebookInstanceSummary> items =
 notebookInstancesResponse.notebookInstances();
            for (NotebookInstanceSummary item : items) {
                System.out.println("The notebook name is: " +
 item.notebookInstanceName());
            }

        } catch (SageMakerException e) {
```

```
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListNotebookInstancesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar um pipeline

O exemplo de código a seguir mostra como criar ou atualizar um pipeline em SageMaker.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
   // Create a pipeline from the example pipeline JSON.
   public static void setupPipeline(SageMakerClient sageMakerClient, String
filePath, String roleArn,
           String functionArn, String pipelineName) {
       System.out.println("Setting up the pipeline.");
       JSONParser parser = new JSONParser();

       // Read JSON and get pipeline definition.
       try (FileReader reader = new FileReader(filePath)) {
           Object obj = parser.parse(reader);
           JSONObject jsonObject = (JSONObject) obj;
```

```
            JSONArray stepsArray = (JSONArray) jsonObject.get("Steps");
            for (Object stepObj : stepsArray) {
                JSONObject step = (JSONObject) stepObj;
                if (step.containsKey("FunctionArn")) {
                    step.put("FunctionArn", functionArn);
                }
            }
            System.out.println(jsonObject);

            // Create the pipeline.
            CreatePipelineRequest pipelineRequest = CreatePipelineRequest.builder()
                    .pipelineDescription("Java SDK example pipeline")
                    .roleArn(roleArn)
                    .pipelineName(pipelineName)
                    .pipelineDefinition(jsonObject.toString())
                    .build();

            sageMakerClient.createPipeline(pipelineRequest);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException | ParseException e) {
            throw new RuntimeException(e);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreatePipeline
  - UpdatePipeline

Excluir um pipeline

O exemplo de código a seguir mostra como excluir um pipeline em SageMaker.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Delete a SageMaker pipeline by name.
   public static void deletePipeline(SageMakerClient sageMakerClient, String
pipelineName) {
       DeletePipelineRequest pipelineRequest = DeletePipelineRequest.builder()
               .pipelineName(pipelineName)
               .build();

       sageMakerClient.deletePipeline(pipelineRequest);
       System.out.println("*** Successfully deleted " + pipelineName);
   }
```

- Para obter detalhes da API, consulte DeletePipelinea Referência AWS SDK for Java 2.x da API.

Descrever uma execução de pipeline

O exemplo de código a seguir mostra como descrever a execução de um pipeline em SageMaker.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Check the status of a pipeline execution.
   public static void waitForPipelineExecution(SageMakerClient sageMakerClient,
String executionArn)
           throws InterruptedException {
       String status;
```

```
        int index = 0;
        do {
            DescribePipelineExecutionRequest pipelineExecutionRequest =
 DescribePipelineExecutionRequest.builder()
                    .pipelineExecutionArn(executionArn)
                    .build();

            DescribePipelineExecutionResponse response = sageMakerClient
                    .describePipelineExecution(pipelineExecutionRequest);
            status = response.pipelineExecutionStatusAsString();
            System.out.println(index + ". The Status of the pipeline is " + status);
            TimeUnit.SECONDS.sleep(4);
            index++;
        } while ("Executing".equals(status));
        System.out.println("Pipeline finished with status " + status);
    }
```

- Para obter detalhes da API, consulte DescribePipelineExecutiona Referência AWS SDK for Java 2.x da API.

Executar pipeline

O exemplo de código a seguir mostra como iniciar a execução de um pipeline em SageMaker.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Start a pipeline run with job configurations.
    public static String executePipeline(SageMakerClient sageMakerClient, String
 bucketName, String queueUrl,
            String roleArn, String pipelineName) {
        System.out.println("Starting pipeline execution.");
        String inputBucketLocation = "s3://" + bucketName + "/samplefiles/
latlongtest.csv";
        String output = "s3://" + bucketName + "/outputfiles/";
        Gson gson = new GsonBuilder()
```

```
                .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                .setPrettyPrinting().create();

        // Set up all parameters required to start the pipeline.
        List<Parameter> parameters = new ArrayList<>();
        Parameter para1 = Parameter.builder()
                .name("parameter_execution_role")
                .value(roleArn)
                .build();

        Parameter para2 = Parameter.builder()
                .name("parameter_queue_url")
                .value(queueUrl)
                .build();

        String inputJSON = "{\n" +
                "  \"DataSourceConfig\": {\n" +
                "    \"S3Data\": {\n" +
                "      \"S3Uri\": \"s3://" + bucketName + "/samplefiles/
latlongtest.csv\"\n" +
                "    },\n" +
                "    \"Type\": \"S3_DATA\"\n" +
                "  },\n" +
                "  \"DocumentType\": \"CSV\"\n" +
                "}";

        System.out.println(inputJSON);

        Parameter para3 = Parameter.builder()
                .name("parameter_vej_input_config")
                .value(inputJSON)
                .build();

        // Create an ExportVectorEnrichmentJobOutputConfig object.
        VectorEnrichmentJobS3Data jobS3Data = VectorEnrichmentJobS3Data.builder()
                .s3Uri(output)
                .build();

        ExportVectorEnrichmentJobOutputConfig outputConfig =
 ExportVectorEnrichmentJobOutputConfig.builder()
                .s3Data(jobS3Data)
                .build();

        String gson4 = gson.toJson(outputConfig);
```

```
        Parameter para4 = Parameter.builder()
                .name("parameter_vej_export_config")
                .value(gson4)
                .build();
        System.out.println("parameter_vej_export_config:" +
 gson.toJson(outputConfig));

        // Create a VectorEnrichmentJobConfig object.
        ReverseGeocodingConfig reverseGeocodingConfig =
 ReverseGeocodingConfig.builder()
                .xAttributeName("Longitude")
                .yAttributeName("Latitude")
                .build();

        VectorEnrichmentJobConfig jobConfig = VectorEnrichmentJobConfig.builder()
                .reverseGeocodingConfig(reverseGeocodingConfig)
                .build();

        String para5JSON = "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":
{\"XAttributeName\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}";
        Parameter para5 = Parameter.builder()
                .name("parameter_step_1_vej_config")
                .value(para5JSON)
                .build();

        System.out.println("parameter_step_1_vej_config:" + gson.toJson(jobConfig));
        parameters.add(para1);
        parameters.add(para2);
        parameters.add(para3);
        parameters.add(para4);
        parameters.add(para5);

        StartPipelineExecutionRequest pipelineExecutionRequest =
 StartPipelineExecutionRequest.builder()
                .pipelineExecutionDescription("Created using Java SDK")
                .pipelineExecutionDisplayName(pipelineName + "-example-execution")
                .pipelineParameters(parameters)
                .pipelineName(pipelineName)
                .build();

        StartPipelineExecutionResponse response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest);
        return response.pipelineExecutionArn();
    }
```

- Para obter detalhes da API, consulte StartPipelineExecutiona Referência AWS SDK for Java 2.x da API.

Cenários

Iniciar com trabalhos geoespaciais e pipelines

O código de exemplo a seguir mostra como:

- Configurar recursos para um pipeline.
- Configurar um pipeline que execute um trabalho geoespacial.
- Inicie a execução de um pipeline.
- Monitorar o status da execução.
- Ver saída do pipeline.
- Limpe os recursos.

Para obter mais informações, consulte Criar e executar SageMaker pipelines usando AWS SDKs no Community.aws.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
public class SagemakerWorkflow {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");
    private static String eventSourceMapping = "";

    public static void main(String[] args) throws InterruptedException {
        final String usage = "\n" +
                "Usage:\n" +
```

```
                "    <sageMakerRoleName> <lambdaRoleName> <functionFileLocation>
<functionName> <queueName> <bucketName> <lnglatData> <spatialPipelinePath>
<pipelineName>\n\n"
                +
                "Where:\n" +
                "    sageMakerRoleName - The name of the Amazon SageMaker role.\n\n"
+
                "    lambdaRoleName - The name of the AWS Lambda role.\n\n" +
                "    functionFileLocation - The file location where the JAR file
that represents the AWS Lambda function is located.\n\n"
                +
                "    functionName - The name of the AWS Lambda function (for
example,SageMakerExampleFunction).\n\n" +
                "    queueName - The name of the Amazon Simple Queue Service (Amazon
SQS) queue.\n\n" +
                "    bucketName - The name of the Amazon Simple Storage Service
(Amazon S3) bucket.\n\n" +
                "    lnglatData - The file location of the latlongtest.csv file
required for this use case.\n\n" +
                "    spatialPipelinePath - The file location of the
GeoSpatialPipeline.json file required for this use case.\n\n"
                +
                "    pipelineName - The name of the pipeline to create (for example,
sagemaker-sdk-example-pipeline).\n\n";

        if (args.length != 9) {
            System.out.println(usage);
            System.exit(1);
        }

        String sageMakerRoleName = args[0];
        String lambdaRoleName = args[1];
        String functionFileLocation = args[2];
        String functionName = args[3];
        String queueName = args[4];
        String bucketName = args[5];
        String lnglatData = args[6];
        String spatialPipelinePath = args[7];
        String pipelineName = args[8];
        String handlerName = "org.example.SageMakerLambdaFunction::handleRequest";

        Region region = Region.US_WEST_2;
        SageMakerClient sageMakerClient = SageMakerClient.builder()
                .region(region)
```

```
                .build();

        IamClient iam = IamClient.builder()
                .region(region)
                .build();

        LambdaClient lambdaClient = LambdaClient.builder()
                .region(region)
                .build();

        SqsClient sqsClient = SqsClient.builder()
                .region(region)
                .build();

        S3Client s3Client = S3Client.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the Amazon SageMaker pipeline example
scenario.");
        System.out.println(
                "\nThis example workflow will guide you through setting up and
running an" +
                        "\nAmazon SageMaker pipeline. The pipeline uses an AWS
Lambda function and an" +
                        "\nAmazon SQS Queue. It runs a vector enrichment reverse
geocode job to" +
                        "\nreverse geocode addresses in an input file and store the
results in an export file.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("First, we will set up the roles, functions, and queue
needed by the SageMaker pipeline.");
        String lambdaRoleArn = checkLambdaRole(iam, lambdaRoleName);
        String sageMakerRoleArn = checkSageMakerRole(iam, sageMakerRoleName);

        String functionArn = checkFunction(lambdaClient, functionName,
functionFileLocation, lambdaRoleArn,
                handlerName);
        String queueUrl = checkQueue(sqsClient, lambdaClient, queueName,
functionName);
        System.out.println("The queue URL is " + queueUrl);
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Setting up bucket " + bucketName);
        if (!checkBucket(s3Client, bucketName)) {
            setupBucket(s3Client, bucketName);
            System.out.println("Put " + lnglatData + " into " + bucketName);
            putS3Object(s3Client, bucketName, "latlongtest.csv", lnglatData);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Now we can create and run our pipeline.");
        setupPipeline(sageMakerClient, spatialPipelinePath, sageMakerRoleArn,
 functionArn, pipelineName);
        String pipelineExecutionARN = executePipeline(sageMakerClient, bucketName,
 queueUrl, sageMakerRoleArn,
                pipelineName);
        System.out.println("The pipeline execution ARN value is " +
 pipelineExecutionARN);
        waitForPipelineExecution(sageMakerClient, pipelineExecutionARN);
        System.out.println("Getting output results " + bucketName);
        getOutputResults(s3Client, bucketName);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The pipeline has completed. To view the pipeline and
 runs " +
                "in SageMaker Studio, follow these instructions:" +
                "\nhttps://docs.aws.amazon.com/sagemaker/latest/dg/pipelines-
studio.html");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("Do you want to delete the AWS resources used in this
 Workflow? (y/n)");
        Scanner in = new Scanner(System.in);
        String delResources = in.nextLine();
        if (delResources.compareTo("y") == 0) {
            System.out.println("Lets clean up the AWS resources. Wait 30 seconds");
            TimeUnit.SECONDS.sleep(30);
            deleteEventSourceMapping(lambdaClient);
            deleteSQSQueue(sqsClient, queueName);
            listBucketObjects(s3Client, bucketName);
```

```
            deleteBucket(s3Client, bucketName);
            deleteLambdaFunction(lambdaClient, functionName);
            deleteLambdaRole(iam, lambdaRoleName);
            deleteSagemakerRole(iam, sageMakerRoleName);
            deletePipeline(sageMakerClient, pipelineName);
        } else {
            System.out.println("The AWS Resources were not deleted!");
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("SageMaker pipeline scenario is complete.");
        System.out.println(DASHES);
    }

    private static void readObject(S3Client s3Client, String bucketName, String key)
{
        System.out.println("Output file contents: \n");
        GetObjectRequest objectRequest = GetObjectRequest.builder()
                .bucket(bucketName)
                .key(key)
                .build();

        ResponseBytes<GetObjectResponse> objectBytes =
s3Client.getObjectAsBytes(objectRequest);
        byte[] byteArray = objectBytes.asByteArray();
        String text = new String(byteArray, StandardCharsets.UTF_8);
        System.out.println("Text output: " + text);
    }

    // Display some results from the output directory.
    public static void getOutputResults(S3Client s3Client, String bucketName) {
        System.out.println("Getting output results {bucketName}.");
        ListObjectsRequest listObjectsRequest = ListObjectsRequest.builder()
                .bucket(bucketName)
                .prefix("outputfiles/")
                .build();

        ListObjectsResponse response = s3Client.listObjects(listObjectsRequest);
        List<S3Object> s3Objects = response.contents();
        for (S3Object object : s3Objects) {
            readObject(s3Client, bucketName, object.key());
        }
    }
```

```
   // Check the status of a pipeline execution.
   public static void waitForPipelineExecution(SageMakerClient sageMakerClient,
String executionArn)
           throws InterruptedException {
       String status;
       int index = 0;
       do {
           DescribePipelineExecutionRequest pipelineExecutionRequest =
DescribePipelineExecutionRequest.builder()
                   .pipelineExecutionArn(executionArn)
                   .build();

           DescribePipelineExecutionResponse response = sageMakerClient
                   .describePipelineExecution(pipelineExecutionRequest);
           status = response.pipelineExecutionStatusAsString();
           System.out.println(index + ". The Status of the pipeline is " + status);
           TimeUnit.SECONDS.sleep(4);
           index++;
       } while ("Executing".equals(status));
       System.out.println("Pipeline finished with status " + status);
   }

   // Delete a SageMaker pipeline by name.
   public static void deletePipeline(SageMakerClient sageMakerClient, String
pipelineName) {
       DeletePipelineRequest pipelineRequest = DeletePipelineRequest.builder()
               .pipelineName(pipelineName)
               .build();

       sageMakerClient.deletePipeline(pipelineRequest);
       System.out.println("*** Successfully deleted " + pipelineName);
   }

   // Create a pipeline from the example pipeline JSON.
   public static void setupPipeline(SageMakerClient sageMakerClient, String
filePath, String roleArn,
           String functionArn, String pipelineName) {
       System.out.println("Setting up the pipeline.");
       JSONParser parser = new JSONParser();

       // Read JSON and get pipeline definition.
       try (FileReader reader = new FileReader(filePath)) {
           Object obj = parser.parse(reader);
```

```
            JSONObject jsonObject = (JSONObject) obj;
            JSONArray stepsArray = (JSONArray) jsonObject.get("Steps");
            for (Object stepObj : stepsArray) {
                JSONObject step = (JSONObject) stepObj;
                if (step.containsKey("FunctionArn")) {
                    step.put("FunctionArn", functionArn);
                }
            }
            System.out.println(jsonObject);

            // Create the pipeline.
            CreatePipelineRequest pipelineRequest = CreatePipelineRequest.builder()
                    .pipelineDescription("Java SDK example pipeline")
                    .roleArn(roleArn)
                    .pipelineName(pipelineName)
                    .pipelineDefinition(jsonObject.toString())
                    .build();

            sageMakerClient.createPipeline(pipelineRequest);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (IOException | ParseException e) {
            throw new RuntimeException(e);
        }
    }

    // Start a pipeline run with job configurations.
    public static String executePipeline(SageMakerClient sageMakerClient, String
 bucketName, String queueUrl,
            String roleArn, String pipelineName) {
        System.out.println("Starting pipeline execution.");
        String inputBucketLocation = "s3://" + bucketName + "/samplefiles/
latlongtest.csv";
        String output = "s3://" + bucketName + "/outputfiles/";
        Gson gson = new GsonBuilder()
                .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
                .setPrettyPrinting().create();

        // Set up all parameters required to start the pipeline.
        List<Parameter> parameters = new ArrayList<>();
        Parameter para1 = Parameter.builder()
                .name("parameter_execution_role")
```

```
                .value(roleArn)
                .build();

        Parameter para2 = Parameter.builder()
                .name("parameter_queue_url")
                .value(queueUrl)
                .build();

        String inputJSON = "{\n" +
                "  \"DataSourceConfig\": {\n" +
                "    \"S3Data\": {\n" +
                "      \"S3Uri\": \"s3://" + bucketName + "/samplefiles/
latlongtest.csv\"\n" +
                "    },\n" +
                "    \"Type\": \"S3_DATA\"\n" +
                "  },\n" +
                "  \"DocumentType\": \"CSV\"\n" +
                "}";

        System.out.println(inputJSON);

        Parameter para3 = Parameter.builder()
                .name("parameter_vej_input_config")
                .value(inputJSON)
                .build();

        // Create an ExportVectorEnrichmentJobOutputConfig object.
        VectorEnrichmentJobS3Data jobS3Data = VectorEnrichmentJobS3Data.builder()
                .s3Uri(output)
                .build();

        ExportVectorEnrichmentJobOutputConfig outputConfig =
 ExportVectorEnrichmentJobOutputConfig.builder()
                .s3Data(jobS3Data)
                .build();

        String gson4 = gson.toJson(outputConfig);
        Parameter para4 = Parameter.builder()
                .name("parameter_vej_export_config")
                .value(gson4)
                .build();
        System.out.println("parameter_vej_export_config:" +
 gson.toJson(outputConfig));
```

```
        // Create a VectorEnrichmentJobConfig object.
        ReverseGeocodingConfig reverseGeocodingConfig =
 ReverseGeocodingConfig.builder()
                .xAttributeName("Longitude")
                .yAttributeName("Latitude")
                .build();

        VectorEnrichmentJobConfig jobConfig = VectorEnrichmentJobConfig.builder()
                .reverseGeocodingConfig(reverseGeocodingConfig)
                .build();

        String para5JSON = "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":
{\"XAttributeName\":\"Longitude\",\"YAttributeName\":\"Latitude\"}}";
        Parameter para5 = Parameter.builder()
                .name("parameter_step_1_vej_config")
                .value(para5JSON)
                .build();

        System.out.println("parameter_step_1_vej_config:" + gson.toJson(jobConfig));
        parameters.add(para1);
        parameters.add(para2);
        parameters.add(para3);
        parameters.add(para4);
        parameters.add(para5);

        StartPipelineExecutionRequest pipelineExecutionRequest =
 StartPipelineExecutionRequest.builder()
                .pipelineExecutionDescription("Created using Java SDK")
                .pipelineExecutionDisplayName(pipelineName + "-example-execution")
                .pipelineParameters(parameters)
                .pipelineName(pipelineName)
                .build();

        StartPipelineExecutionResponse response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest);
        return response.pipelineExecutionArn();
    }

    public static void deleteEventSourceMapping(LambdaClient lambdaClient) {
        DeleteEventSourceMappingRequest eventSourceMappingRequest =
 DeleteEventSourceMappingRequest.builder()
                .uuid(eventSourceMapping)
                .build();
```

```
        lambdaClient.deleteEventSourceMapping(eventSourceMappingRequest);
    }

    public static void deleteSagemakerRole(IamClient iam, String roleName) {
        String[] sageMakerRolePolicies = getSageMakerRolePolicies();
        try {
            for (String policy : sageMakerRolePolicies) {
                // First the policy needs to be detached.
                DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
                        .policyArn(policy)
                        .roleName(roleName)
                        .build();

                iam.detachRolePolicy(rolePolicyRequest);
            }

            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteLambdaRole(IamClient iam, String roleName) {
        String[] lambdaRolePolicies = getLambdaRolePolicies();
        try {
            for (String policy : lambdaRolePolicies) {
                // First the policy needs to be detached.
                DetachRolePolicyRequest rolePolicyRequest =
DetachRolePolicyRequest.builder()
                        .policyArn(policy)
                        .roleName(roleName)
                        .build();

                iam.detachRolePolicy(rolePolicyRequest);
            }
```

```
            // Delete the role.
            DeleteRoleRequest roleRequest = DeleteRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            iam.deleteRole(roleRequest);
            System.out.println("*** Successfully deleted " + roleName);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Delete the specific AWS Lambda function.
    public static void deleteLambdaFunction(LambdaClient awsLambda, String
functionName) {
        try {
            DeleteFunctionRequest request = DeleteFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            awsLambda.deleteFunction(request);
            System.out.println("*** " + functionName + " was deleted");

        } catch (LambdaException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Delete the specific S3 bucket.
    public static void deleteBucket(S3Client s3Client, String bucketName) {
        DeleteBucketRequest deleteBucketRequest = DeleteBucketRequest.builder()
                .bucket(bucketName)
                .build();
        s3Client.deleteBucket(deleteBucketRequest);
        System.out.println("*** " + bucketName + " was deleted.");
    }

    public static void listBucketObjects(S3Client s3, String bucketName) {
        try {
            ListObjectsRequest listObjects = ListObjectsRequest
```

```
                    .builder()
                    .bucket(bucketName)
                    .build();

            ListObjectsResponse res = s3.listObjects(listObjects);
            List<S3Object> objects = res.contents();
            for (S3Object myValue : objects) {
                System.out.print("\n The name of the key is " + myValue.key());
                deleteBucketObjects(s3, bucketName, myValue.key());
            }

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteBucketObjects(S3Client s3, String bucketName, String
objectName) {
        ArrayList<ObjectIdentifier> toDelete = new ArrayList<>();
        toDelete.add(ObjectIdentifier.builder()
                .key(objectName)
                .build());
        try {
            DeleteObjectsRequest dor = DeleteObjectsRequest.builder()
                    .bucket(bucketName)
                    .delete(Delete.builder()
                            .objects(toDelete).build())
                    .build();

            s3.deleteObjects(dor);
            System.out.println("*** " + bucketName + " objects were deleted.");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Delete the specific Amazon SQS queue.
    public static void deleteSQSQueue(SqsClient sqsClient, String queueName) {
        try {
            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
```

```
                .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            DeleteQueueRequest deleteQueueRequest = DeleteQueueRequest.builder()
                    .queueUrl(queueUrl)
                    .build();

            sqsClient.deleteQueue(deleteQueueRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void putS3Object(S3Client s3, String bucketName, String objectKey,
String objectPath) {
        try {
            Map<String, String> metadata = new HashMap<>();
            metadata.put("x-amz-meta-myVal", "test");
            PutObjectRequest putOb = PutObjectRequest.builder()
                    .bucket(bucketName)
                    .key("samplefiles/" + objectKey)
                    .metadata(metadata)
                    .build();

            s3.putObject(putOb, RequestBody.fromFile(new File(objectPath)));
            System.out.println("Successfully placed " + objectKey + " into bucket "
+ bucketName);

        } catch (S3Exception e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void setupBucket(S3Client s3Client, String bucketName) {
        try {
            S3Waiter s3Waiter = s3Client.waiter();
            CreateBucketRequest bucketRequest = CreateBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3Client.createBucket(bucketRequest);
```

```
            HeadBucketRequest bucketRequestWait = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            // Wait until the bucket is created and print out the response.
            WaiterResponse<HeadBucketResponse> waiterResponse =
s3Waiter.waitUntilBucketExists(bucketRequestWait);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println(bucketName + " is ready");

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    // Set up the SQS queue to use with the pipeline.
    public static String setupQueue(SqsClient sqsClient, LambdaClient lambdaClient,
String queueName,
            String lambdaName) {
        System.out.println("Setting up queue named " + queueName);
        try {
            Map<QueueAttributeName, String> queueAtt = new HashMap<>();
            queueAtt.put(QueueAttributeName.DELAY_SECONDS, "5");
            queueAtt.put(QueueAttributeName.RECEIVE_MESSAGE_WAIT_TIME_SECONDS, "5");
            queueAtt.put(QueueAttributeName.VISIBILITY_TIMEOUT, "300");
            CreateQueueRequest createQueueRequest = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .attributes(queueAtt)
                    .build();

            sqsClient.createQueue(createQueueRequest);
            System.out.println("\nGet queue url");
            GetQueueUrlResponse getQueueUrlResponse = sqsClient

.getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
            TimeUnit.SECONDS.sleep(15);

            connectLambda(sqsClient, lambdaClient, getQueueUrlResponse.queueUrl(),
lambdaName);
            System.out.println("Queue ready with Url " +
getQueueUrlResponse.queueUrl());
            return getQueueUrlResponse.queueUrl();
```

```
        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    // Connect the queue to the Lambda function as an event source.
    public static void connectLambda(SqsClient sqsClient, LambdaClient lambdaClient,
String queueUrl,
            String lambdaName) {
        System.out.println("Connecting the Lambda function and queue for the
pipeline.");
        String queueArn = "";

        // Specify the attributes to retrieve.
        List<QueueAttributeName> atts = new ArrayList<>();
        atts.add(QueueAttributeName.QUEUE_ARN);
        GetQueueAttributesRequest attributesRequest =
GetQueueAttributesRequest.builder()
                .queueUrl(queueUrl)
                .attributeNames(atts)
                .build();

        GetQueueAttributesResponse response =
sqsClient.getQueueAttributes(attributesRequest);
        Map<String, String> queueAtts = response.attributesAsStrings();
        for (Map.Entry<String, String> queueAtt : queueAtts.entrySet()) {
            System.out.println("Key = " + queueAtt.getKey() + ", Value = " +
queueAtt.getValue());
            queueArn = queueAtt.getValue();
        }

        CreateEventSourceMappingRequest eventSourceMappingRequest =
CreateEventSourceMappingRequest.builder()
                .eventSourceArn(queueArn)
                .functionName(lambdaName)
                .build();

        CreateEventSourceMappingResponse response1 =
lambdaClient.createEventSourceMapping(eventSourceMappingRequest);
        eventSourceMapping = response1.uuid();
```

```
        System.out.println("The mapping between the event source and Lambda function
was successful");
    }

    // Create an AWS Lambda function.
    public static String createLambdaFunction(LambdaClient awsLambda, String
functionName, String filePath, String role,
            String handler) {
        try {
            LambdaWaiter waiter = awsLambda.waiter();
            InputStream is = new FileInputStream(filePath);
            SdkBytes fileToUpload = SdkBytes.fromInputStream(is);
            FunctionCode code = FunctionCode.builder()
                    .zipFile(fileToUpload)
                    .build();

            CreateFunctionRequest functionRequest = CreateFunctionRequest.builder()
                    .functionName(functionName)
                    .description("SageMaker example function.")
                    .code(code)
                    .handler(handler)
                    .runtime(Runtime.JAVA11)
                    .timeout(200)
                    .memorySize(1024)
                    .role(role)
                    .build();

            // Create a Lambda function using a waiter.
            CreateFunctionResponse functionResponse =
awsLambda.createFunction(functionRequest);
            GetFunctionRequest getFunctionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();
            WaiterResponse<GetFunctionResponse> waiterResponse =
waiter.waitUntilFunctionExists(getFunctionRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            System.out.println("The function ARN is " +
functionResponse.functionArn());
            return functionResponse.functionArn();

        } catch (LambdaException | FileNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
        return "";
    }

    public static String createSageMakerRole(IamClient iam, String roleName) {
        String[] sageMakerRolePolicies = getSageMakerRolePolicies();
        System.out.println("Creating a role to use with SageMaker.");
        String assumeRolePolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": [" +
                "\"sagemaker.amazonaws.com\"," +
                "\"sagemaker-geospatial.amazonaws.com\"," +
                "\"lambda.amazonaws.com\"," +
                "\"s3.amazonaws.com\"" +
                "]" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(roleName)
                    .assumeRolePolicyDocument(assumeRolePolicy)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse roleResult = iam.createRole(request);

            // Attach the policies to the role.
            for (String policy : sageMakerRolePolicies) {
                AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                        .roleName(roleName)
                        .policyArn(policy)
                        .build();

                iam.attachRolePolicy(attachRequest);
            }

            // Allow time for the role to be ready.
            TimeUnit.SECONDS.sleep(15);
```

```
            System.out.println("Role ready with ARN " + roleResult.role().arn());
            return roleResult.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    private static String createLambdaRole(IamClient iam, String roleName) {
        String[] lambdaRolePolicies = getLambdaRolePolicies();
        String assumeRolePolicy = "{" +
                "\"Version\": \"2012-10-17\"," +
                "\"Statement\": [{" +
                "\"Effect\": \"Allow\"," +
                "\"Principal\": {" +
                "\"Service\": [" +
                "\"sagemaker.amazonaws.com\"," +
                "\"sagemaker-geospatial.amazonaws.com\"," +
                "\"lambda.amazonaws.com\"," +
                "\"s3.amazonaws.com\"" +
                "]" +
                "}," +
                "\"Action\": \"sts:AssumeRole\"" +
                "}]" +
                "}";

        try {
            CreateRoleRequest request = CreateRoleRequest.builder()
                    .roleName(roleName)
                    .assumeRolePolicyDocument(assumeRolePolicy)
                    .description("Created using the AWS SDK for Java")
                    .build();

            CreateRoleResponse roleResult = iam.createRole(request);

            // Attach the policies to the role.
            for (String policy : lambdaRolePolicies) {
                AttachRolePolicyRequest attachRequest =
AttachRolePolicyRequest.builder()
                        .roleName(roleName)
```

```
                        .policyArn(policy)
                        .build();

                iam.attachRolePolicy(attachRequest);
            }

            // Allow time for the role to be ready.
            TimeUnit.SECONDS.sleep(15);
            System.out.println("Role ready with ARN " + roleResult.role().arn());
            return roleResult.role().arn();

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());

        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }
        return "";
    }

    public static String checkFunction(LambdaClient lambdaClient, String
functionName, String filePath, String role,
            String handler) {
        System.out.println("Create an AWS Lambda function used in this workflow.");
        String functionArn;
        try {
            // Does this function already exist.
            GetFunctionRequest functionRequest = GetFunctionRequest.builder()
                    .functionName(functionName)
                    .build();

            GetFunctionResponse response =
lambdaClient.getFunction(functionRequest);
            functionArn = response.configuration().functionArn();

        } catch (LambdaException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            functionArn = createLambdaFunction(lambdaClient, functionName, filePath,
role, handler);
        }
        return functionArn;
    }

    // Check to see if the specific S3 bucket exists. If the S3 bucket exists, this
```

```
    // method returns true.
    public static boolean checkBucket(S3Client s3, String bucketName) {
        try {
            HeadBucketRequest headBucketRequest = HeadBucketRequest.builder()
                    .bucket(bucketName)
                    .build();

            s3.headBucket(headBucketRequest);
            System.out.println(bucketName + " exists");
            return true;

        } catch (S3Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
        }
        return false;
    }

    // Checks to see if the Amazon SQS queue exists. If not, this method creates a
    // new queue
    // and returns the ARN value.
    public static String checkQueue(SqsClient sqsClient, LambdaClient lambdaClient,
String queueName,
            String lambdaName) {
        System.out.println("Creating a queue for this use case.");
        String queueUrl;
        try {
            GetQueueUrlRequest request = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            GetQueueUrlResponse response = sqsClient.getQueueUrl(request);
            queueUrl = response.queueUrl();
            System.out.println(queueUrl);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            queueUrl = setupQueue(sqsClient, lambdaClient, queueName, lambdaName);
        }
        return queueUrl;
    }

    // Checks to see if the Lambda role exists. If not, this method creates it.
    public static String checkLambdaRole(IamClient iam, String roleName) {
        System.out.println("Creating a role to for AWS Lambda to use.");
```

```
        String roleArn;
        try {
            GetRoleRequest roleRequest = GetRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            GetRoleResponse response = iam.getRole(roleRequest);
            roleArn = response.role().arn();
            System.out.println(roleArn);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            roleArn = createLambdaRole(iam, roleName);
        }
        return roleArn;
    }

    // Checks to see if the SageMaker role exists. If not, this method creates it.
    public static String checkSageMakerRole(IamClient iam, String roleName) {
        System.out.println("Creating a role to for AWS SageMaker to use.");
        String roleArn;
        try {
            GetRoleRequest roleRequest = GetRoleRequest.builder()
                    .roleName(roleName)
                    .build();

            GetRoleResponse response = iam.getRole(roleRequest);
            roleArn = response.role().arn();
            System.out.println(roleArn);

        } catch (IamException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            roleArn = createSageMakerRole(iam, roleName);
        }
        return roleArn;
    }

    private static String[] getSageMakerRolePolicies() {
        String[] sageMakerRolePolicies = new String[3];
        sageMakerRolePolicies[0] = "arn:aws:iam::aws:policy/
AmazonSageMakerFullAccess";
        sageMakerRolePolicies[1] = "arn:aws:iam::aws:policy/" +
 "AmazonSageMakerGeospatialFullAccess";
        sageMakerRolePolicies[2] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess";
```

```
        return sageMakerRolePolicies;
    }

    private static String[] getLambdaRolePolicies() {
        String[] lambdaRolePolicies = new String[5];
        lambdaRolePolicies[0] = "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess";
        lambdaRolePolicies[1] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess";
        lambdaRolePolicies[2] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess";
        lambdaRolePolicies[3] = "arn:aws:iam::aws:policy/service-role/"
                + "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy";
        lambdaRolePolicies[4] = "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole";
        return lambdaRolePolicies;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Exemplos do Secrets Manager usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um segredo

O exemplo de código a seguir mostra como criar um segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.CreateSecretRequest;
import software.amazon.awssdk.services.secretsmanager.model.CreateSecretResponse;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName> <secretValue>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
```

```
                    secretValue - The secret value.\s
                """";

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        String secretARN = createNewSecret(secretsClient, secretName, secretValue);
        System.out.println("The secret ARN is " + secretARN);
        secretsClient.close();
    }

    public static String createNewSecret(SecretsManagerClient secretsClient, String
 secretName, String secretValue) {
        try {
            CreateSecretRequest secretRequest = CreateSecretRequest.builder()
                    .name(secretName)
                    .description("This secret was created by the AWS Secret Manager
 Java API")
                    .secretString(secretValue)
                    .build();

            CreateSecretResponse secretResponse =
 secretsClient.createSecret(secretRequest);
            return secretResponse.arn();

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateSecreta Referência AWS SDK for Java 2.x da API.

Excluir um segredo

O exemplo de código a seguir mostra como excluir um segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.DeleteSecretRequest;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteSecret {
    public static void main(String[] args) {

        final String usage = """

                Usage:
                     <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        deleteSpecificSecret(secretsClient, secretName);
        secretsClient.close();
    }

    public static void deleteSpecificSecret(SecretsManagerClient secretsClient,
 String secretName) {
        try {
            DeleteSecretRequest secretRequest = DeleteSecretRequest.builder()
                    .secretId(secretName)
                    .build();

            secretsClient.deleteSecret(secretRequest);
            System.out.println(secretName + " is deleted.");

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteSecreta Referência AWS SDK for Java 2.x da API.

Descrever um segredo

O exemplo de código a seguir mostra como descrever um segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.DescribeSecretRequest;
import software.amazon.awssdk.services.secretsmanager.model.DescribeSecretResponse;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        describeGivenSecret(secretsClient, secretName);
```

```
        secretsClient.close();
    }

    public static void describeGivenSecret(SecretsManagerClient secretsClient,
 String secretName) {
        try {
            DescribeSecretRequest secretRequest = DescribeSecretRequest.builder()
                    .secretId(secretName)
                    .build();

            DescribeSecretResponse secretResponse =
 secretsClient.describeSecret(secretRequest);
            Instant lastChangedDate = secretResponse.lastChangedDate();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(lastChangedDate);
            System.out.println("The date of the last change to " +
 secretResponse.name() + " is " + lastChangedDate);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeSecreta Referência AWS SDK for Java 2.x da API.

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueRequest;
import software.amazon.awssdk.services.secretsmanager.model.GetSecretValueResponse;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * We recommend that you cache your secret values by using client-side caching.
 *
 * Caching secrets improves speed and reduces your costs. For more information,
 * see the following documentation topic:
 *
 * https://docs.aws.amazon.com/secretsmanager/latest/userguide/retrieving-
secrets.html
 */
public class GetSecretValue {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName>\s

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        getValue(secretsClient, secretName);
        secretsClient.close();
    }

    public static void getValue(SecretsManagerClient secretsClient, String
 secretName) {
        try {
            GetSecretValueRequest valueRequest = GetSecretValueRequest.builder()
                    .secretId(secretName)
                    .build();

            GetSecretValueResponse valueResponse =
 secretsClient.getSecretValue(valueRequest);
            String secret = valueResponse.secretString();
            System.out.println(secret);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetSecretValuea Referência AWS SDK for Java 2.x da API.

listar segredos

O exemplo de código a seguir mostra como listar um segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.ListSecretsResponse;
import software.amazon.awssdk.services.secretsmanager.model.SecretListEntry;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListSecrets {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        listAllSecrets(secretsClient);
        secretsClient.close();
    }

    public static void listAllSecrets(SecretsManagerClient secretsClient) {
        try {
            ListSecretsResponse secretsResponse = secretsClient.listSecrets();
            List<SecretListEntry> secrets = secretsResponse.secretList();
            for (SecretListEntry secret : secrets) {
                System.out.println("The secret name is " + secret.name());
                System.out.println("The secret descreiption is " +
 secret.description());
```

```
            }

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListSecretsa Referência AWS SDK for Java 2.x da API.

Modificar os detalhes de um segredo

O exemplo de código a seguir mostra como modificar o segredo.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;
import software.amazon.awssdk.services.secretsmanager.model.UpdateSecretRequest;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UpdateSecret {
    public static void main(String[] args) {
        final String usage = """
```

```
                Usage:
                    <secretName> <secretValue>

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                    secretValue - The secret value that is updated.\s
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        updateMySecret(secretsClient, secretName, secretValue);
        secretsClient.close();
    }

    public static void updateMySecret(SecretsManagerClient secretsClient, String
 secretName, String secretValue) {
        try {
            UpdateSecretRequest secretRequest = UpdateSecretRequest.builder()
                    .secretId(secretName)
                    .secretString(secretValue)
                    .build();

            secretsClient.updateSecret(secretRequest);

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateSecreta Referência AWS SDK for Java 2.x da API.

Inserir um valor em um segredo

O exemplo de código a seguir mostra como inserir valor em um segredo do Secrets Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.secretsmanager.SecretsManagerClient;
import software.amazon.awssdk.services.secretsmanager.model.PutSecretValueRequest;
import software.amazon.awssdk.services.secretsmanager.model.SecretsManagerException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PutSecret {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <secretName> <secretValue>

                Where:
                    secretName - The name of the secret (for example, tutorials/
MyFirstSecret).\s
                    secretValue - The text to encrypt and store in the new version
 of the secret.\s
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String secretName = args[0];
        String secretValue = args[1];
        Region region = Region.US_EAST_1;
        SecretsManagerClient secretsClient = SecretsManagerClient.builder()
                .region(region)
                .build();

        putSecret(secretsClient, secretName, secretValue);
        secretsClient.close();
    }

    public static void putSecret(SecretsManagerClient secretsClient, String
 secretName, String secretValue) {
        try {
            PutSecretValueRequest secretRequest = PutSecretValueRequest.builder()
                    .secretId(secretName)
                    .secretString(secretValue)
                    .build();

            secretsClient.putSecretValue(secretRequest);
            System.out.println("A new version was created.");

        } catch (SecretsManagerException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutSecretValuea Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon SES usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar modelos de e-mail

O exemplo de código a seguir mostra como lista modelos existentes de e-mail do Amazon SES.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.SesV2Client;
import software.amazon.awssdk.services.sesv2.model.ListEmailTemplatesRequest;
import software.amazon.awssdk.services.sesv2.model.ListEmailTemplatesResponse;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;

public class ListTemplates {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SesV2Client sesv2Client = SesV2Client.builder()
                .region(region)
                .build();

        listAllTemplates(sesv2Client);
    }

    public static void listAllTemplates(SesV2Client sesv2Client) {
```

```
        try {
            ListEmailTemplatesRequest templatesRequest =
 ListEmailTemplatesRequest.builder()
                    .pageSize(1)
                    .build();

            ListEmailTemplatesResponse response =
 sesv2Client.listEmailTemplates(templatesRequest);
            response.templatesMetadata()
                    .forEach(template -> System.out.println("Template name: " +
 template.templateName()));

        } catch (SesV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTemplatesa Referência AWS SDK for Java 2.x da API.

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import software.amazon.awssdk.services.ses.model.ListIdentitiesResponse;
import software.amazon.awssdk.services.ses.model.SesException;
import java.io.IOException;
import java.util.List;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListIdentities {

    public static void main(String[] args) throws IOException {
        Region region = Region.US_WEST_2;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        listSESIdentities(client);
    }

    public static void listSESIdentities(SesClient client) {
        try {
            ListIdentitiesResponse identitiesResponse = client.listIdentities();
            List<String> identities = identitiesResponse.identities();
            for (String identity : identities) {
                System.out.println("The identity is " + identity);
            }

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for Java 2.x da API.

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import software.amazon.awssdk.services.ses.model.Content;
import software.amazon.awssdk.services.ses.model.Destination;
import software.amazon.awssdk.services.ses.model.Message;
import software.amazon.awssdk.services.ses.model.Body;
import software.amazon.awssdk.services.ses.model.SendEmailRequest;
import software.amazon.awssdk.services.ses.model.SesException;

import javax.mail.MessagingException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SendMessageEmailRequest {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <sender> <recipient> <subject>\s

                Where:
                    sender - An email address that represents the sender.\s
                    recipient -  An email address that represents the recipient.\s
                    subject - The  subject line.\s
                """;

        if (args.length != 3) {
            System.out.println(usage);
```

```
            System.exit(1);
        }

        String sender = args[0];
        String recipient = args[1];
        String subject = args[2];

        Region region = Region.US_EAST_1;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        // The HTML body of the email.
        String bodyHTML = "<html>" + "<head></head>" + "<body>" + "<h1>Hello!</h1>"
                + "<p> See the list of customers.</p>" + "</body>" + "</html>";

        try {
            send(client, sender, recipient, subject, bodyHTML);
            client.close();
            System.out.println("Done");

        } catch (MessagingException e) {
            e.getStackTrace();
        }
    }

    public static void send(SesClient client,
            String sender,
            String recipient,
            String subject,
            String bodyHTML) throws MessagingException {

        Destination destination = Destination.builder()
                .toAddresses(recipient)
                .build();

        Content content = Content.builder()
                .data(bodyHTML)
                .build();

        Content sub = Content.builder()
                .data(subject)
                .build();
```

```
        Body body = Body.builder()
                .html(content)
                .build();

        Message msg = Message.builder()
                .subject(sub)
                .body(body)
                .build();

        SendEmailRequest emailRequest = SendEmailRequest.builder()
                .destination(destination)
                .message(msg)
                .source(sender)
                .build();

        try {
            System.out.println("Attempting to send an email through Amazon SES " +
 "using the AWS SDK for Java...");
            client.sendEmail(emailRequest);

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ses.SesClient;
import javax.activation.DataHandler;
import javax.activation.DataSource;
import javax.mail.Message;
import javax.mail.MessagingException;
import javax.mail.Session;
import javax.mail.internet.AddressException;
import javax.mail.internet.InternetAddress;
import javax.mail.internet.MimeMessage;
import javax.mail.internet.MimeMultipart;
import javax.mail.internet.MimeBodyPart;
import javax.mail.util.ByteArrayDataSource;
import java.io.ByteArrayOutputStream;
import java.io.IOException;
import java.nio.ByteBuffer;
import java.nio.file.Files;
```

```
import java.util.Properties;
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.services.ses.model.SendRawEmailRequest;
import software.amazon.awssdk.services.ses.model.RawMessage;
import software.amazon.awssdk.services.ses.model.SesException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class SendMessageAttachment {
    public static void main(String[] args) throws IOException {
        final String usage = """

                Usage:
                    <sender> <recipient> <subject> <fileLocation>\s

                Where:
                    sender - An email address that represents the sender.\s
                    recipient -  An email address that represents the recipient.\s
                    subject - The  subject line.\s
                    fileLocation - The location of a Microsoft Excel file to use as
 an attachment (C:/AWS/customers.xls).\s
                """;

        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        String sender = args[0];
        String recipient = args[1];
        String subject = args[2];
        String fileLocation = args[3];

        // The email body for recipients with non-HTML email clients.
        String bodyText = "Hello,\r\n" + "Please see the attached file for a list "
                + "of customers to contact.";
```

```
        // The HTML body of the email.
        String bodyHTML = "<html>" + "<head></head>" + "<body>" + "<h1>Hello!</h1>"
                + "<p>Please see the attached file for a " + "list of customers to
contact.</p>" + "</body>"
                + "</html>";

        Region region = Region.US_WEST_2;
        SesClient client = SesClient.builder()
                .region(region)
                .build();

        try {
            sendemailAttachment(client, sender, recipient, subject, bodyText,
bodyHTML, fileLocation);
            client.close();
            System.out.println("Done");

        } catch (IOException | MessagingException e) {
            e.getStackTrace();
        }
    }

    public static void sendemailAttachment(SesClient client,
            String sender,
            String recipient,
            String subject,
            String bodyText,
            String bodyHTML,
            String fileLocation) throws AddressException, MessagingException,
IOException {

        java.io.File theFile = new java.io.File(fileLocation);
        byte[] fileContent = Files.readAllBytes(theFile.toPath());

        Session session = Session.getDefaultInstance(new Properties());

        // Create a new MimeMessage object.
        MimeMessage message = new MimeMessage(session);

        // Add subject, from and to lines.
        message.setSubject(subject, "UTF-8");
        message.setFrom(new InternetAddress(sender));
        message.setRecipients(Message.RecipientType.TO,
InternetAddress.parse(recipient));
```

```
        // Create a multipart/alternative child container.
        MimeMultipart msgBody = new MimeMultipart("alternative");

        // Create a wrapper for the HTML and text parts.
        MimeBodyPart wrap = new MimeBodyPart();

        // Define the text part.
        MimeBodyPart textPart = new MimeBodyPart();
        textPart.setContent(bodyText, "text/plain; charset=UTF-8");

        // Define the HTML part.
        MimeBodyPart htmlPart = new MimeBodyPart();
        htmlPart.setContent(bodyHTML, "text/html; charset=UTF-8");

        // Add the text and HTML parts to the child container.
        msgBody.addBodyPart(textPart);
        msgBody.addBodyPart(htmlPart);

        // Add the child container to the wrapper object.
        wrap.setContent(msgBody);

        // Create a multipart/mixed parent container.
        MimeMultipart msg = new MimeMultipart("mixed");

        // Add the parent container to the message.
        message.setContent(msg);
        msg.addBodyPart(wrap);

        // Define the attachment.
        MimeBodyPart att = new MimeBodyPart();
        DataSource fds = new ByteArrayDataSource(fileContent,
                "application/vnd.openxmlformats-
officedocument.spreadsheetml.sheet");
        att.setDataHandler(new DataHandler(fds));

        String reportName = "WorkReport.xls";
        att.setFileName(reportName);

        // Add the attachment to the message.
        msg.addBodyPart(att);

        try {
```

```
            System.out.println("Attempting to send an email through Amazon SES " +
 "using the AWS SDK for Java...");

            ByteArrayOutputStream outputStream = new ByteArrayOutputStream();
            message.writeTo(outputStream);

            ByteBuffer buf = ByteBuffer.wrap(outputStream.toByteArray());

            byte[] arr = new byte[buf.remaining()];
            buf.get(arr);

            SdkBytes data = SdkBytes.fromByteArray(arr);
            RawMessage rawMessage = RawMessage.builder()
                    .data(data)
                    .build();

            SendRawEmailRequest rawEmailRequest = SendRawEmailRequest.builder()
                    .rawMessage(rawMessage)
                    .build();

            client.sendRawEmail(rawEmailRequest);

        } catch (SesException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        System.out.println("Email sent using SesClient with attachment");
    }
}
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Java 2.x da API.

Enviar e-mails com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo com o Amazon SES.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.model.Destination;
import software.amazon.awssdk.services.sesv2.model.EmailContent;
import software.amazon.awssdk.services.sesv2.model.SendEmailRequest;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;
import software.amazon.awssdk.services.sesv2.SesV2Client;
import software.amazon.awssdk.services.sesv2.model.Template;

/**
 * Before running this AWS SDK for Java (v2) example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * Also, make sure that you create a template. See the following documentation
 * topic:
 *
 * https://docs.aws.amazon.com/ses/latest/dg/send-personalized-email-api.html
 */

public class SendEmailTemplate {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <template> <sender> <recipient>\s

                Where:
                    template - The name of the email template.
                    sender - An email address that represents the sender.\s
                    recipient - An email address that represents the recipient.\s
                """;
```

```
        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String templateName = args[0];
        String sender = args[1];
        String recipient = args[2];
        Region region = Region.US_EAST_1;
        SesV2Client sesv2Client = SesV2Client.builder()
                .region(region)
                .build();

        send(sesv2Client, sender, recipient, templateName);
    }

    public static void send(SesV2Client client, String sender, String recipient,
String templateName) {
        Destination destination = Destination.builder()
                .toAddresses(recipient)
                .build();

        /*
         * Specify both name and favorite animal (favoriteanimal) in your code when
         * defining the Template object.
         * If you don't specify all the variables in the template, Amazon SES
doesn't
         * send the email.
         */
        Template myTemplate = Template.builder()
                .templateName(templateName)
                .templateData("{\n" +
                        "  \"name\": \"Jason\"\n," +
                        "  \"favoriteanimal\": \"Cat\"\n" +
                        "}")
                .build();

        EmailContent emailContent = EmailContent.builder()
                .template(myTemplate)
                .build();

        SendEmailRequest emailRequest = SendEmailRequest.builder()
                .destination(destination)
```

```
                .content(emailContent)
                .fromEmailAddress(sender)
                .build();

        try {
            System.out.println("Attempting to send an email based on a template
 using the AWS SDK for Java (v2)...");
            client.sendEmail(emailRequest);
            System.out.println("email based on a template was sent");

        } catch (SesV2Exception e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SendTemplatedEmaila Referência AWS SDK for Java 2.x da API.

Exemplos de API v2 do Amazon SES usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com a API v2 do Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar um e-mail

O exemplo de código a seguir mostra como enviar um e-mail com a API v2 do Amazon SES.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envia uma mensagem.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sesv2.model.Body;
import software.amazon.awssdk.services.sesv2.model.Content;
import software.amazon.awssdk.services.sesv2.model.Destination;
import software.amazon.awssdk.services.sesv2.model.EmailContent;
import software.amazon.awssdk.services.sesv2.model.Message;
import software.amazon.awssdk.services.sesv2.model.SendEmailRequest;
import software.amazon.awssdk.services.sesv2.model.SesV2Exception;
import software.amazon.awssdk.services.sesv2.SesV2Client;

/**
 * Before running this AWS SDK for Java (v2) example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class SendEmail {
        public static void main(String[] args) {
                final String usage = """

                                Usage:
                                    <sender> <recipient> <subject>\s

                                Where:
```

```
                                    sender - An email address that represents the
sender.\s
                                    recipient - An email address that represents the
recipient.\s
                                    subject - The subject line.\s
                                """;

                if (args.length != 3) {
                        System.out.println(usage);
                        System.exit(1);
                }

                String sender = args[0];
                String recipient = args[1];
                String subject = args[2];

                Region region = Region.US_EAST_1;
                SesV2Client sesv2Client = SesV2Client.builder()
                                .region(region)
                                .build();

                // The HTML body of the email.
                String bodyHTML = "<html>" + "<head></head>" + "<body>" +
"<h1>Hello!</h1>"
                                + "<p> See the list of customers.</p>" + "</body>" +
"</html>";

                send(sesv2Client, sender, recipient, subject, bodyHTML);
        }

        public static void send(SesV2Client client,
                        String sender,
                        String recipient,
                        String subject,
                        String bodyHTML) {

                Destination destination = Destination.builder()
                                .toAddresses(recipient)
                                .build();

                Content content = Content.builder()
                                .data(bodyHTML)
                                .build();
```

```
                Content sub = Content.builder()
                                .data(subject)
                                .build();

                Body body = Body.builder()
                                .html(content)
                                .build();

                Message msg = Message.builder()
                                .subject(sub)
                                .body(body)
                                .build();

                EmailContent emailContent = EmailContent.builder()
                                .simple(msg)
                                .build();

                SendEmailRequest emailRequest = SendEmailRequest.builder()
                                .destination(destination)
                                .content(emailContent)
                                .fromEmailAddress(sender)
                                .build();

                try {
                        System.out.println("Attempting to send an email through
 Amazon SES "
                                        + "using the AWS SDK for Java...");
                        client.sendEmail(emailRequest);
                        System.out.println("email was sent");

                } catch (SesV2Exception e) {
                        System.err.println(e.awsErrorDetails().errorMessage());
                        System.exit(1);
                }
        }
}
```

- Para obter detalhes da API, consulte SendEmail a Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon SNS usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.example.sns;

import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.paginators.ListTopicsIterable;

public class HelloSNS {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
```

```
        listSNSTopics(snsClient);
        snsClient.close();
    }

    public static void listSNSTopics(SnsClient snsClient) {
        try {
            ListTopicsIterable listTopics = snsClient.listTopicsPaginator();
            listTopics.stream()
                    .flatMap(r -> r.topics().stream())
                    .forEach(content -> System.out.println(" Topic ARN: " +
 content.topicArn()));

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Adicionar tags a um tópico

O exemplo de código a seguir mostra como adicionar tags a um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.Tag;
import software.amazon.awssdk.services.sns.model.TagResourceRequest;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class AddTags {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic to which tags are added.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        addTopicTags(snsClient, topicArn);
        snsClient.close();
    }

    public static void addTopicTags(SnsClient snsClient, String topicArn) {
        try {
```

```
            Tag tag = Tag.builder()
                    .key("Team")
                    .value("Development")
                    .build();

            Tag tag2 = Tag.builder()
                    .key("Environment")
                    .value("Gamma")
                    .build();

            List<Tag> tagList = new ArrayList<>();
            tagList.add(tag);
            tagList.add(tag2);

            TagResourceRequest tagResourceRequest = TagResourceRequest.builder()
                    .resourceArn(topicArn)
                    .tags(tagList)
                    .build();

            snsClient.tagResource(tagResourceRequest);
            System.out.println("Tags have been added to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte TagResourcea Referência AWS SDK for Java 2.x da API.

Verificar se um número de telefone saiu

O exemplo de código a seguir mostra como verificar se um número de telefone optou por não receber mensagens do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import
 software.amazon.awssdk.services.sns.model.CheckIfPhoneNumberIsOptedOutRequest;
import
 software.amazon.awssdk.services.sns.model.CheckIfPhoneNumberIsOptedOutResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CheckOptOut {
    public static void main(String[] args) {

        final String usage = """

                Usage:    <phoneNumber>

                Where:
                   phoneNumber - The mobile phone number to look up (for example,
 +1XXX5550100).

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }
```

```
        String phoneNumber = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        checkPhone(snsClient, phoneNumber);
        snsClient.close();
    }

    public static void checkPhone(SnsClient snsClient, String phoneNumber) {
        try {
            CheckIfPhoneNumberIsOptedOutRequest request =
 CheckIfPhoneNumberIsOptedOutRequest.builder()
                    .phoneNumber(phoneNumber)
                    .build();

            CheckIfPhoneNumberIsOptedOutResponse result =
 snsClient.checkIfPhoneNumberIsOptedOut(request);
            System.out.println(
                    result.isOptedOut() + "Phone Number " + phoneNumber + " has
 Opted Out of receiving sns messages." +
                            "\n\nStatus was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for Java 2.x da API.

Confirmar que um proprietário de endpoint deseja receber mensagens

O exemplo de código a seguir mostra como confirmar que o proprietário de um endpoint deseja receber mensagens do Amazon SNS validando o token enviado para o endpoint por uma ação Subscribe anterior.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ConfirmSubscriptionRequest;
import software.amazon.awssdk.services.sns.model.ConfirmSubscriptionResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ConfirmSubscription {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <subscriptionToken> <topicArn>

                Where:
                   subscriptionToken - A short-lived token sent to an endpoint
 during the Subscribe action.
                   topicArn - The ARN of the topic.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String subscriptionToken = args[0];
        String topicArn = args[1];
        SnsClient snsClient = SnsClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        confirmSub(snsClient, subscriptionToken, topicArn);
        snsClient.close();
    }

    public static void confirmSub(SnsClient snsClient, String subscriptionToken,
 String topicArn) {
        try {
            ConfirmSubscriptionRequest request =
 ConfirmSubscriptionRequest.builder()
                    .token(subscriptionToken)
                    .topicArn(topicArn)
                    .build();

            ConfirmSubscriptionResponse result =
 snsClient.confirmSubscription(request);
            System.out.println("\n\nStatus was " +
 result.sdkHttpResponse().statusCode() + "\n\nSubscription Arn: \n\n"
                    + result.subscriptionArn());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for Java 2.x da API.

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreateTopicRequest;
import software.amazon.awssdk.services.sns.model.CreateTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicName>

                Where:
                   topicName - The name of the topic to create (for example,
 mytopic).

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicName = args[0];
        System.out.println("Creating a topic with name: " + topicName);
        SnsClient snsClient = SnsClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        String arnVal = createSNSTopic(snsClient, topicName);
        System.out.println("The topic ARN is" + arnVal);
        snsClient.close();
    }

    public static String createSNSTopic(SnsClient snsClient, String topicName) {
        CreateTopicResponse result;
        try {
            CreateTopicRequest request = CreateTopicRequest.builder()
                    .name(topicName)
                    .build();

            result = snsClient.createTopic(request);
            return result.topicArn();

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Java 2.x da API.

Excluir uma assinatura

O exemplo de códigos a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.UnsubscribeRequest;
import software.amazon.awssdk.services.sns.model.UnsubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class Unsubscribe {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <subscriptionArn>

                Where:
                   subscriptionArn - The ARN of the subscription to delete.
                """;

        if (args.length < 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String subscriptionArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        unSub(snsClient, subscriptionArn);
        snsClient.close();
    }

    public static void unSub(SnsClient snsClient, String subscriptionArn) {
        try {
            UnsubscribeRequest request = UnsubscribeRequest.builder()
                    .subscriptionArn(subscriptionArn)
                    .build();

            UnsubscribeResponse result = snsClient.unsubscribe(request);
```

```
            System.out.println("\n\nStatus was " +
 result.sdkHttpResponse().statusCode()
                    + "\n\nSubscription was removed for " +
 request.subscriptionArn());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for Java 2.x.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.DeleteTopicRequest;
import software.amazon.awssdk.services.sns.model.DeleteTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:     <topicArn>

                Where:
                   topicArn - The ARN of the topic to delete.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println("Deleting a topic with name: " + topicArn);
        deleteSNSTopic(snsClient, topicArn);
        snsClient.close();
    }

    public static void deleteSNSTopic(SnsClient snsClient, String topicArn) {
        try {
            DeleteTopicRequest request = DeleteTopicRequest.builder()
                    .topicArn(topicArn)
                    .build();

            DeleteTopicResponse result = snsClient.deleteTopic(request);
            System.out.println("\n\nStatus was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for Java 2.x da API.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.GetTopicAttributesRequest;
import software.amazon.awssdk.services.sns.model.GetTopicAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetTopicAttributes {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic to look up.
                """;

        if (args.length != 1) {
```

```
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        System.out.println("Getting attributes for a topic with name: " + topicArn);
        getSNSTopicAttributes(snsClient, topicArn);
        snsClient.close();
    }

    public static void getSNSTopicAttributes(SnsClient snsClient, String topicArn) {
        try {
            GetTopicAttributesRequest request = GetTopicAttributesRequest.builder()
                    .topicArn(topicArn)
                    .build();

            GetTopicAttributesResponse result =
 snsClient.getTopicAttributes(request);
            System.out.println("\n\nStatus is " +
 result.sdkHttpResponse().statusCode() + "\n\nAttributes: \n\n"
                    + result.attributes());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for Java 2.x da API.

Obter as configurações para enviar mensagens SMS

O exemplo de código a seguir mostra como obter as configurações para enviar mensagens SMS do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.GetSubscriptionAttributesRequest;
import software.amazon.awssdk.services.sns.model.GetSubscriptionAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.Iterator;
import java.util.Map;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetSMSAtrributes {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn>

                Where:
                   topicArn - The ARN of the topic from which to retrieve
 attributes.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        SnsClient snsClient = SnsClient.builder()
```

```
                .region(Region.US_EAST_1)
                .build();

        getSNSAttrutes(snsClient, topicArn);
        snsClient.close();
    }

    public static void getSNSAttrutes(SnsClient snsClient, String topicArn) {
        try {
            GetSubscriptionAttributesRequest request =
 GetSubscriptionAttributesRequest.builder()
                    .subscriptionArn(topicArn)
                    .build();

            // Get the Subscription attributes
            GetSubscriptionAttributesResponse res =
 snsClient.getSubscriptionAttributes(request);
            Map<String, String> map = res.attributes();

            // Iterate through the map
            Iterator iter = map.entrySet().iterator();
            while (iter.hasNext()) {
                Map.Entry entry = (Map.Entry) iter.next();
                System.out.println("[Key] : " + entry.getKey() + " [Value] : " +
 entry.getValue());
            }

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }

        System.out.println("\n\nStatus was good");
    }
}
```

- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for Java 2.x.

Listar números de telefone que saíram

O exemplo de código a seguir mostra como listar números de telefone que optaram por não receber mensagens do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListPhoneNumbersOptedOutRequest;
import software.amazon.awssdk.services.sns.model.ListPhoneNumbersOptedOutResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListOptOut {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listOpts(snsClient);
        snsClient.close();
    }

    public static void listOpts(SnsClient snsClient) {
        try {
            ListPhoneNumbersOptedOutRequest request =
 ListPhoneNumbersOptedOutRequest.builder().build();
```

```
            ListPhoneNumbersOptedOutResponse result =
 snsClient.listPhoneNumbersOptedOut(request);
            System.out.println("Status is " + result.sdkHttpResponse().statusCode()
 + "\n\nPhone Numbers: \n\n"
                    + result.phoneNumbers());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListPhoneNumbersOptedOuta Referência AWS SDK for Java 2.x da API.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListSubscriptionsRequest;
import software.amazon.awssdk.services.sns.model.ListSubscriptionsResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
```

```
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListSubscriptions {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSNSSubscriptions(snsClient);
        snsClient.close();
    }

    public static void listSNSSubscriptions(SnsClient snsClient) {
        try {
            ListSubscriptionsRequest request = ListSubscriptionsRequest.builder()
                    .build();

            ListSubscriptionsResponse result = snsClient.listSubscriptions(request);
            System.out.println(result.subscriptions());

        } catch (SnsException e) {

            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for Java 2.x da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.ListTopicsRequest;
import software.amazon.awssdk.services.sns.model.ListTopicsResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListTopics {
    public static void main(String[] args) {
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        listSNSTopics(snsClient);
        snsClient.close();
    }

    public static void listSNSTopics(SnsClient snsClient) {
        try {
            ListTopicsRequest request = ListTopicsRequest.builder()
                    .build();

            ListTopicsResponse result = snsClient.listTopics(request);
            System.out.println(
                    "Status was " + result.sdkHttpResponse().statusCode() + "\n
\nTopics\n\n" + result.topics());
```

```
        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Java 2.x da API.

Publicar uma mensagem de texto SMS

O exemplo de código a seguir mostra como publicar mensagens SMS usando o Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PublishTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <phoneNumber>
```

```
                Where:
                   message - The message text to send.
                   phoneNumber - The mobile phone number to which a message is sent
 (for example, +1XXX5550100).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTextSMS(snsClient, message, phoneNumber);
        snsClient.close();
    }

    public static void pubTextSMS(SnsClient snsClient, String message, String
 phoneNumber) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .phoneNumber(phoneNumber)
                    .build();

            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Java 2.x.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PublishTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <topicArn>

                Where:
                   message - The message text to send.
                   topicArn - The ARN of the topic to publish.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
```

```
        String topicArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTopic(snsClient, message, topicArn);
        snsClient.close();
    }

    public static void pubTopic(SnsClient snsClient, String message, String
 topicArn) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .topicArn(topicArn)
                    .build();

            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status is " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Java 2.x.

Definir uma política de filtro

O exemplo de código a seguir mostra como definir uma política de filtro do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.ArrayList;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class UseMessageFilterPolicy {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <subscriptionArn>

                Where:
                   subscriptionArn - The ARN of a subscription.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String subscriptionArn = args[0];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        usePolicy(snsClient, subscriptionArn);
        snsClient.close();
    }

    public static void usePolicy(SnsClient snsClient, String subscriptionArn) {
        try {
            SNSMessageFilterPolicy fp = new SNSMessageFilterPolicy();
            // Add a filter policy attribute with a single value
            fp.addAttribute("store", "example_corp");
```

```
            fp.addAttribute("event", "order_placed");

            // Add a prefix attribute
            fp.addAttributePrefix("customer_interests", "bas");

            // Add an anything-but attribute
            fp.addAttributeAnythingBut("customer_interests", "baseball");

            // Add a filter policy attribute with a list of values
            ArrayList<String> attributeValues = new ArrayList<>();
            attributeValues.add("rugby");
            attributeValues.add("soccer");
            attributeValues.add("hockey");
            fp.addAttribute("customer_interests", attributeValues);

            // Add a numeric attribute
            fp.addAttribute("price_usd", "=", 0);

            // Add a numeric attribute with a range
            fp.addAttributeRange("price_usd", ">", 0, "<=", 100);

            // Apply the filter policy attributes to an Amazon SNS subscription
            fp.apply(snsClient, subscriptionArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SetSubscriptionAttributesa Referência AWS SDK for Java 2.x da API.

Definir as configurações padrão para enviar mensagens SMS

O exemplo de código a seguir mostra como definir as configurações padrão para enviar mensagens SMS usando o Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SetSMSAttributes {
    public static void main(String[] args) {
        HashMap<String, String> attributes = new HashMap<>(1);
        attributes.put("DefaultSMSType", "Transactional");
        attributes.put("UsageReportS3Bucket", "janbucket");

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        setSNSAttributes(snsClient, attributes);
        snsClient.close();
    }

    public static void setSNSAttributes(SnsClient snsClient, HashMap<String, String>
 attributes) {
        try {
            SetSmsAttributesRequest request = SetSmsAttributesRequest.builder()
                    .attributes(attributes)
                    .build();
```

```
            SetSmsAttributesResponse result = snsClient.setSMSAttributes(request);
            System.out.println("Set default Attributes to " + attributes + ". Status
 was "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for Java 2.x.

Definir atributos de tópicos

O exemplo de código a seguir mostra como definir atributos para um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetTopicAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetTopicAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
```

```
 */
public class SetTopicAttributes {

    public static void main(String[] args) {
        final String usage = """

                Usage:    <attribute> <topicArn> <value>

                Where:
                   attribute - The attribute action to use. Valid parameters are:
 Policy | DisplayName | DeliveryPolicy .
                   topicArn - The ARN of the topic.\s
                   value - The value for the attribute.
                """;

        if (args.length < 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String attribute = args[0];
        String topicArn = args[1];
        String value = args[2];

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        setTopAttr(snsClient, attribute, topicArn, value);
        snsClient.close();
    }

    public static void setTopAttr(SnsClient snsClient, String attribute, String
 topicArn, String value) {
        try {
            SetTopicAttributesRequest request = SetTopicAttributesRequest.builder()
                    .attributeName(attribute)
                    .attributeValue(value)
                    .topicArn(topicArn)
                    .build();

            SetTopicAttributesResponse result =
 snsClient.setTopicAttributes(request);
            System.out.println(
```

```
                    "\n\nStatus was " + result.sdkHttpResponse().statusCode() + "\n
\nTopic " + request.topicArn()
                            + " updated " + request.attributeName() + " to " +
 request.attributeValue());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for Java 2.x da API.

Inscrever uma função do Lambda em um tópico

O exemplo de código a seguir mostra como inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
```

```
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SubscribeLambda {

    public static void main(String[] args) {

        final String usage = """

                Usage:    <topicArn> <lambdaArn>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   lambdaArn - The ARN of an AWS Lambda function.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String lambdaArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String arnValue = subLambda(snsClient, topicArn, lambdaArn);
        System.out.println("Subscription ARN: " + arnValue);
        snsClient.close();
    }

    public static String subLambda(SnsClient snsClient, String topicArn, String
 lambdaArn) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("lambda")
                    .endpoint(lambdaArn)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            return result.subscriptionArn();
```

```
        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

Inscrever um endpoint HTTP em um tópico

O exemplo de código a seguir mostra como inscrever um endpoint HTTP ou HTTPS para receber notificações de um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SubscribeHTTPS {
    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:    <topicArn> <url>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   url - The HTTPS endpoint that you want to receive notifications.
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String url = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subHTTPS(snsClient, topicArn, url);
        snsClient.close();
    }

    public static void subHTTPS(SnsClient snsClient, String topicArn, String url) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("https")
                    .endpoint(url)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN is " + result.subscriptionArn() +
 "\n\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

Inscrever um endereço de e-mail em um tópico

O exemplo de código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SubscribeEmail {
    public static void main(String[] args) {
        final String usage = """
                Usage:     <topicArn> <email>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   email - The email address to use.
                """;
```

```
        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String email = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subEmail(snsClient, topicArn, email);
        snsClient.close();
    }

    public static void subEmail(SnsClient snsClient, String topicArn, String email)
 {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("email")
                    .endpoint(email)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();

            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN: " + result.subscriptionArn() + "\n
\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Java 2.x.

Cenários

Criar um endpoint de plataforma para notificações por push

O exemplo de código a seguir mostra como criar um endpoint de plataforma para notificações por push do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreatePlatformEndpointRequest;
import software.amazon.awssdk.services.sns.model.CreatePlatformEndpointResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * In addition, create a platform application using the AWS Management Console.
 * See this doc topic:
 *
 * https://docs.aws.amazon.com/sns/latest/dg/mobile-push-send-register.html
 *
 * Without the values created by following the previous link, this code examples
 * does not work.
 */

public class RegistrationExample {
    public static void main(String[] args) {
        final String usage = """

                Usage:     <token> <platformApplicationArn>
```

```
                Where:
                   token - The name of the FIFO topic.\s
                   platformApplicationArn - The ARN value of platform application.
 You can get this value from the AWS Management Console.\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String token = args[0];
        String platformApplicationArn = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        createEndpoint(snsClient, token, platformApplicationArn);
    }

    public static void createEndpoint(SnsClient snsClient, String token, String
 platformApplicationArn) {
        System.out.println("Creating platform endpoint with token " + token);
        try {
            CreatePlatformEndpointRequest endpointRequest =
 CreatePlatformEndpointRequest.builder()
                    .token(token)
                    .platformApplicationArn(platformApplicationArn)
                    .build();

            CreatePlatformEndpointResponse response =
 snsClient.createPlatformEndpoint(endpointRequest);
            System.out.println("The ARN of the endpoint is " +
 response.endpointArn());
        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse exemplo

- cria um tópico FIFO do Amazon SNS, duas filas FIFO do Amazon SQS e uma fila padrão.
- inscreve as filas no tópico e publica a mensagem no tópico.

O teste verifica o recebimento da mensagem em cada fila. O exemplo completo também mostra a adição de políticas de acesso e exclui os recursos no final.

```
public class PriceUpdateExample {
    public final static SnsClient snsClient = SnsClient.create();
    public final static SqsClient sqsClient = SqsClient.create();

    public static void main(String[] args) {

        final String usage = "\n" +
                "Usage: " +
                "    <topicName> <wholesaleQueueFifoName> <retailQueueFifoName>
 <analyticsQueueName>\n\n" +
                "Where:\n" +
                "   fifoTopicName - The name of the FIFO topic that you want to
 create. \n\n" +
                "   wholesaleQueueARN - The name of a SQS FIFO queue that will be
 created for the wholesale consumer. \n\n"
                +
                "   retailQueueARN - The name of a SQS FIFO queue that will created
 for the retail consumer. \n\n" +
                "   analyticsQueueARN - The name of a SQS standard queue that will
 be created for the analytics consumer. \n\n";
        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
```

```
        }

        final String fifoTopicName = args[0];
        final String wholeSaleQueueName = args[1];
        final String retailQueueName = args[2];
        final String analyticsQueueName = args[3];

        // For convenience, the QueueData class holds metadata about a queue: ARN,
URL,
        // name and type.
        List<QueueData> queues = List.of(
                new QueueData(wholeSaleQueueName, QueueType.FIFO),
                new QueueData(retailQueueName, QueueType.FIFO),
                new QueueData(analyticsQueueName, QueueType.Standard));

        // Create queues.
        createQueues(queues);

        // Create a topic.
        String topicARN = createFIFOTopic(fifoTopicName);

        // Subscribe each queue to the topic.
        subscribeQueues(queues, topicARN);

        // Allow the newly created topic to send messages to the queues.
        addAccessPolicyToQueuesFINAL(queues, topicARN);

        // Publish a sample price update message with payload.
        publishPriceUpdate(topicARN, "{\"product\": 214, \"price\": 79.99}",
"Consumables");

        // Clean up resources.
        deleteSubscriptions(queues);
        deleteQueues(queues);
        deleteTopic(topicARN);
    }

    public static String createFIFOTopic(String topicName) {
        try {
            // Create a FIFO topic by using the SNS service client.
            Map<String, String> topicAttributes = Map.of(
                    "FifoTopic", "true",
                    "ContentBasedDeduplication", "false");
```

```
            CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                    .name(topicName)
                    .attributes(topicAttributes)
                    .build();

            CreateTopicResponse response = snsClient.createTopic(topicRequest);
            String topicArn = response.topicArn();
            System.out.println("The topic ARN is" + topicArn);

            return topicArn;

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void subscribeQueues(List<QueueData> queues, String topicARN) {
        queues.forEach(queue -> {
            SubscribeRequest subscribeRequest = SubscribeRequest.builder()
                    .topicArn(topicARN)
                    .endpoint(queue.queueARN)
                    .protocol("sqs")
                    .build();

            // Subscribe to the endpoint by using the SNS service client.
            // Only Amazon SQS queues can receive notifications from an Amazon SNS
FIFO
            // topic.
            SubscribeResponse subscribeResponse =
snsClient.subscribe(subscribeRequest);
            System.out.println("The queue [" + queue.queueARN + "] subscribed to the
topic [" + topicARN + "]");
            queue.subscriptionARN = subscribeResponse.subscriptionArn();
        });
    }

    public static void publishPriceUpdate(String topicArn, String payload, String
groupId) {

        try {
            // Create and publish a message that updates the wholesale price.
            String subject = "Price Update";
```

```
            String dedupId = UUID.randomUUID().toString();
            String attributeName = "business";
            String attributeValue = "wholesale";

            MessageAttributeValue msgAttValue = MessageAttributeValue.builder()
                    .dataType("String")
                    .stringValue(attributeValue)
                    .build();

            Map<String, MessageAttributeValue> attributes = new HashMap<>();
            attributes.put(attributeName, msgAttValue);
            PublishRequest pubRequest = PublishRequest.builder()
                    .topicArn(topicArn)
                    .subject(subject)
                    .message(payload)
                    .messageGroupId(groupId)
                    .messageDeduplicationId(dedupId)
                    .messageAttributes(attributes)
                    .build();

            final PublishResponse response = snsClient.publish(pubRequest);
            System.out.println(response.messageId());
            System.out.println(response.sequenceNumber());
            System.out.println("Message was published to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateTopic
  - Publicar
  - Assinar

Publicar mensagens SMS em um tópico

O código de exemplo a seguir mostra como:

- Crie um tópico do Amazon SNS.
- Inscrever números de telefone no tópico.
- Publicar mensagens SMS no tópico para que todos os números de telefone inscritos recebam a mensagem de uma só vez.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um tópico e retorne seu ARN.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.CreateTopicRequest;
import software.amazon.awssdk.services.sns.model.CreateTopicResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateTopic {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicName>

                Where:
                   topicName - The name of the topic to create (for example,
 mytopic).

                """;
```

```
        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicName = args[0];
        System.out.println("Creating a topic with name: " + topicName);
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        String arnVal = createSNSTopic(snsClient, topicName);
        System.out.println("The topic ARN is" + arnVal);
        snsClient.close();
    }

    public static String createSNSTopic(SnsClient snsClient, String topicName) {
        CreateTopicResponse result;
        try {
            CreateTopicRequest request = CreateTopicRequest.builder()
                    .name(topicName)
                    .build();

            result = snsClient.createTopic(request);
            return result.topicArn();

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

Inscreva um endpoint em um tópico.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SnsException;
import software.amazon.awssdk.services.sns.model.SubscribeRequest;
import software.amazon.awssdk.services.sns.model.SubscribeResponse;
```

```
/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SubscribeTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <topicArn> <phoneNumber>

                Where:
                   topicArn - The ARN of the topic to subscribe.
                   phoneNumber - A mobile phone number that receives notifications
 (for example, +1XXX5550100).
                """;

        if (args.length < 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String topicArn = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();

        subTextSNS(snsClient, topicArn, phoneNumber);
        snsClient.close();
    }

    public static void subTextSNS(SnsClient snsClient, String topicArn, String
 phoneNumber) {
        try {
            SubscribeRequest request = SubscribeRequest.builder()
                    .protocol("sms")
                    .endpoint(phoneNumber)
                    .returnSubscriptionArn(true)
                    .topicArn(topicArn)
                    .build();
```

```
            SubscribeResponse result = snsClient.subscribe(request);
            System.out.println("Subscription ARN: " + result.subscriptionArn() + "\n
\n Status is "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Defina atributos na mensagem, como o ID do remetente, o preço máximo e seu tipo. Os atributos de mensagem são opcionais.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesRequest;
import software.amazon.awssdk.services.sns.model.SetSmsAttributesResponse;
import software.amazon.awssdk.services.sns.model.SnsException;
import java.util.HashMap;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SetSMSAttributes {
    public static void main(String[] args) {
        HashMap<String, String> attributes = new HashMap<>(1);
        attributes.put("DefaultSMSType", "Transactional");
        attributes.put("UsageReportS3Bucket", "janbucket");

        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        setSNSAttributes(snsClient, attributes);
        snsClient.close();
```

```
    }

    public static void setSNSAttributes(SnsClient snsClient, HashMap<String, String>
 attributes) {
        try {
            SetSmsAttributesRequest request = SetSmsAttributesRequest.builder()
                    .attributes(attributes)
                    .build();

            SetSmsAttributesResponse result = snsClient.setSMSAttributes(request);
            System.out.println("Set default Attributes to " + attributes + ". Status
 was "
                    + result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Publique uma mensagem em um tópico. A mensagem é enviada para todos os assinantes.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sns.SnsClient;
import software.amazon.awssdk.services.sns.model.PublishRequest;
import software.amazon.awssdk.services.sns.model.PublishResponse;
import software.amazon.awssdk.services.sns.model.SnsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class PublishTextSMS {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <message> <phoneNumber>
```

```
                Where:
                   message - The message text to send.
                   phoneNumber - The mobile phone number to which a message is sent
 (for example, +1XXX5550100).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String message = args[0];
        String phoneNumber = args[1];
        SnsClient snsClient = SnsClient.builder()
                .region(Region.US_EAST_1)
                .build();
        pubTextSMS(snsClient, message, phoneNumber);
        snsClient.close();
    }

    public static void pubTextSMS(SnsClient snsClient, String message, String
 phoneNumber) {
        try {
            PublishRequest request = PublishRequest.builder()
                    .message(message)
                    .phoneNumber(phoneNumber)
                    .build();

            PublishResponse result = snsClient.publish(request);
            System.out
                    .println(result.messageId() + " Message sent. Status was " +
 result.sdkHttpResponse().statusCode());

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Java.

```
package example;

import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.LambdaLogger;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SNSEvent;
import com.amazonaws.services.lambda.runtime.events.SNSEvent.SNSRecord;


import java.util.Iterator;
import java.util.List;

public class SNSEventHandler implements RequestHandler<SNSEvent, Boolean> {
    LambdaLogger logger;

    @Override
    public Boolean handleRequest(SNSEvent event, Context context) {
        logger = context.getLogger();
        List<SNSRecord> records = event.getRecords();
        if (!records.isEmpty()) {
            Iterator<SNSRecord> recordsIter = records.iterator();
            while (recordsIter.hasNext()) {
                processRecord(recordsIter.next());
            }
```

```
        }
        return Boolean.TRUE;
    }

    public void processRecord(SNSRecord record) {
        try {
            String message = record.getSNS().getMessage();
            logger.log("message: " + message);
        } catch (Exception e) {
            throw new RuntimeException(e);
        }
    }

}
```

Exemplos do Amazon SQS usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.SqsException;
import software.amazon.awssdk.services.sqs.paginators.ListQueuesIterable;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class HelloSQS {
    public static void main(String[] args) {
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        listQueues(sqsClient);
        sqsClient.close();
    }

    public static void listQueues(SqsClient sqsClient) {
        try {
            ListQueuesIterable listQueues = sqsClient.listQueuesPaginator();
            listQueues.stream()
                    .flatMap(r -> r.queueUrls().stream())
                    .forEach(content -> System.out.println(" Queue URL: " +
 content.toLowerCase()));

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.ChangeMessageVisibilityRequest;
import software.amazon.awssdk.services.sqs.model.CreateQueueRequest;
import software.amazon.awssdk.services.sqs.model.DeleteMessageRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlResponse;
import software.amazon.awssdk.services.sqs.model.ListQueuesRequest;
import software.amazon.awssdk.services.sqs.model.ListQueuesResponse;
import software.amazon.awssdk.services.sqs.model.Message;
import software.amazon.awssdk.services.sqs.model.ReceiveMessageRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageBatchRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageBatchRequestEntry;
import software.amazon.awssdk.services.sqs.model.SendMessageRequest;
```

```
import software.amazon.awssdk.services.sqs.model.SqsException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SQSExample {
    public static void main(String[] args) {
        String queueName = "queue" + System.currentTimeMillis();
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        // Perform various tasks on the Amazon SQS queue.
        String queueUrl = createQueue(sqsClient, queueName);
        listQueues(sqsClient);
        listQueuesFilter(sqsClient, queueUrl);
        List<Message> messages = receiveMessages(sqsClient, queueUrl);
        sendBatchMessages(sqsClient, queueUrl);
        changeMessages(sqsClient, queueUrl, messages);
        deleteMessages(sqsClient, queueUrl, messages);
        sqsClient.close();
    }

    public static String createQueue(SqsClient sqsClient, String queueName) {
        try {
            System.out.println("\nCreate Queue");

            CreateQueueRequest createQueueRequest = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .build();

            sqsClient.createQueue(createQueueRequest);

            System.out.println("\nGet queue url");

            GetQueueUrlResponse getQueueUrlResponse = sqsClient

 .getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
```

```
            return getQueueUrlResponse.queueUrl();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static void listQueues(SqsClient sqsClient) {

        System.out.println("\nList Queues");
        String prefix = "que";

        try {
            ListQueuesRequest listQueuesRequest =
ListQueuesRequest.builder().queueNamePrefix(prefix).build();
            ListQueuesResponse listQueuesResponse =
sqsClient.listQueues(listQueuesRequest);
            for (String url : listQueuesResponse.queueUrls()) {
                System.out.println(url);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void listQueuesFilter(SqsClient sqsClient, String queueUrl) {
        // List queues with filters
        String namePrefix = "queue";
        ListQueuesRequest filterListRequest = ListQueuesRequest.builder()
                .queueNamePrefix(namePrefix)
                .build();

        ListQueuesResponse listQueuesFilteredResponse =
sqsClient.listQueues(filterListRequest);
        System.out.println("Queue URLs with prefix: " + namePrefix);
        for (String url : listQueuesFilteredResponse.queueUrls()) {
            System.out.println(url);
        }

        System.out.println("\nSend message");
```

```
        try {
            sqsClient.sendMessage(SendMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .messageBody("Hello world!")
                    .delaySeconds(10)
                    .build());

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void sendBatchMessages(SqsClient sqsClient, String queueUrl) {

        System.out.println("\nSend multiple messages");
        try {
            SendMessageBatchRequest sendMessageBatchRequest =
SendMessageBatchRequest.builder()
                    .queueUrl(queueUrl)

.entries(SendMessageBatchRequestEntry.builder().id("id1").messageBody("Hello from
msg 1").build(),

SendMessageBatchRequestEntry.builder().id("id2").messageBody("msg
2").delaySeconds(10)
                                    .build())
                    .build();
            sqsClient.sendMessageBatch(sendMessageBatchRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static List<Message> receiveMessages(SqsClient sqsClient, String
queueUrl) {

        System.out.println("\nReceive messages");
        try {
            ReceiveMessageRequest receiveMessageRequest =
ReceiveMessageRequest.builder()
                    .queueUrl(queueUrl)
```

```
                    .maxNumberOfMessages(5)
                    .build();
            return sqsClient.receiveMessage(receiveMessageRequest).messages();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
    }

    public static void changeMessages(SqsClient sqsClient, String queueUrl,
List<Message> messages) {

        System.out.println("\nChange Message Visibility");
        try {

            for (Message message : messages) {
                ChangeMessageVisibilityRequest req =
ChangeMessageVisibilityRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .visibilityTimeout(100)
                        .build();
                sqsClient.changeMessageVisibility(req);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void deleteMessages(SqsClient sqsClient, String queueUrl,
List<Message> messages) {
        System.out.println("\nDelete Messages");

        try {
            for (Message message : messages) {
                DeleteMessageRequest deleteMessageRequest =
DeleteMessageRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .build();
```

```
                sqsClient.deleteMessage(deleteMessageRequest);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Java 2.x da API.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        try {
            for (Message message : messages) {
                DeleteMessageRequest deleteMessageRequest =
 DeleteMessageRequest.builder()
                        .queueUrl(queueUrl)
                        .receiptHandle(message.receiptHandle())
                        .build();
                sqsClient.deleteMessage(deleteMessageRequest);
            }
```

- Para obter detalhes da API, consulte DeleteMessagea Referência AWS SDK for Java 2.x da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.DeleteQueueRequest;
import software.amazon.awssdk.services.sqs.model.SqsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DeleteQueue {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <queueName>

                Where:
                   queueName - The name of the Amazon SQS queue to delete.

                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String queueName = args[0];
```

```
        SqsClient sqs = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();

        deleteSQSQueue(sqs, queueName);
        sqs.close();
    }

    public static void deleteSQSQueue(SqsClient sqsClient, String queueName) {
        try {
            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            DeleteQueueRequest deleteQueueRequest = DeleteQueueRequest.builder()
                    .queueUrl(queueUrl)
                    .build();

            sqsClient.deleteQueue(deleteQueueRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Java 2.x da API.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            GetQueueUrlResponse getQueueUrlResponse = sqsClient

.getQueueUrl(GetQueueUrlRequest.builder().queueName(queueName).build());
            return getQueueUrlResponse.queueUrl();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
```

- Para obter detalhes da API, consulte GetQueueUrla Referência AWS SDK for Java 2.x da API.

Listar filas

O exemplo de código a seguir mostra como listar filas do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        String prefix = "que";

        try {
            ListQueuesRequest listQueuesRequest =
ListQueuesRequest.builder().queueNamePrefix(prefix).build();
            ListQueuesResponse listQueuesResponse =
sqsClient.listQueues(listQueuesRequest);
            for (String url : listQueuesResponse.queueUrls()) {
                System.out.println(url);
            }

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Java 2.x da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            ReceiveMessageRequest receiveMessageRequest =
ReceiveMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .maxNumberOfMessages(5)
                    .build();
            return sqsClient.receiveMessage(receiveMessageRequest).messages();

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return null;
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Java 2.x da API.

Para enviar mensagens em lote a uma fila.

O exemplo de código a seguir mostra como enviar um lote de mensagens para uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            SendMessageBatchRequest sendMessageBatchRequest =
SendMessageBatchRequest.builder()
                    .queueUrl(queueUrl)

.entries(SendMessageBatchRequestEntry.builder().id("id1").messageBody("Hello from
msg 1").build(),

SendMessageBatchRequestEntry.builder().id("id2").messageBody("msg
2").delaySeconds(10)
                                    .build())
                    .build();
            sqsClient.sendMessageBatch(sendMessageBatchRequest);
```

- Para obter detalhes da API, consulte SendMessageBatcha Referência AWS SDK for Java 2.x da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.auth.credentials.ProfileCredentialsProvider;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sqs.SqsClient;
```

```
import software.amazon.awssdk.services.sqs.model.CreateQueueRequest;
import software.amazon.awssdk.services.sqs.model.GetQueueUrlRequest;
import software.amazon.awssdk.services.sqs.model.SendMessageRequest;
import software.amazon.awssdk.services.sqs.model.SqsException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class SendMessages {
    public static void main(String[] args) {
        final String usage = """

                Usage:    <queueName> <message>

                Where:
                   queueName - The name of the queue.
                   message - The message to send.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String queueName = args[0];
        String message = args[1];
        SqsClient sqsClient = SqsClient.builder()
                .region(Region.US_WEST_2)
                .build();
        sendMessage(sqsClient, queueName, message);
        sqsClient.close();
    }

    public static void sendMessage(SqsClient sqsClient, String queueName, String
 message) {
        try {
            CreateQueueRequest request = CreateQueueRequest.builder()
                    .queueName(queueName)
                    .build();
```

```
            sqsClient.createQueue(request);

            GetQueueUrlRequest getQueueRequest = GetQueueUrlRequest.builder()
                    .queueName(queueName)
                    .build();

            String queueUrl = sqsClient.getQueueUrl(getQueueRequest).queueUrl();
            SendMessageRequest sendMsgRequest = SendMessageRequest.builder()
                    .queueUrl(queueUrl)
                    .messageBody(message)
                    .delaySeconds(5)
                    .build();

            sqsClient.sendMessage(sendMsgRequest);

        } catch (SqsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for Java 2.x da API.

Cenários

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Esse exemplo

- cria um tópico FIFO do Amazon SNS, duas filas FIFO do Amazon SQS e uma fila padrão.

- inscreve as filas no tópico e publica a mensagem no tópico.

O teste verifica o recebimento da mensagem em cada fila. O exemplo completo também mostra a adição de políticas de acesso e exclui os recursos no final.

```
public class PriceUpdateExample {
    public final static SnsClient snsClient = SnsClient.create();
    public final static SqsClient sqsClient = SqsClient.create();

    public static void main(String[] args) {

        final String usage = "\n" +
                "Usage: " +
                "    <topicName> <wholesaleQueueFifoName> <retailQueueFifoName>
 <analyticsQueueName>\n\n" +
                "Where:\n" +
                "   fifoTopicName - The name of the FIFO topic that you want to
 create. \n\n" +
                "   wholesaleQueueARN - The name of a SQS FIFO queue that will be
 created for the wholesale consumer. \n\n"
                +
                "   retailQueueARN - The name of a SQS FIFO queue that will created
 for the retail consumer. \n\n" +
                "   analyticsQueueARN - The name of a SQS standard queue that will
 be created for the analytics consumer. \n\n";
        if (args.length != 4) {
            System.out.println(usage);
            System.exit(1);
        }

        final String fifoTopicName = args[0];
        final String wholeSaleQueueName = args[1];
        final String retailQueueName = args[2];
        final String analyticsQueueName = args[3];

        // For convenience, the QueueData class holds metadata about a queue: ARN,
 URL,
        // name and type.
        List<QueueData> queues = List.of(
                new QueueData(wholeSaleQueueName, QueueType.FIFO),
                new QueueData(retailQueueName, QueueType.FIFO),
                new QueueData(analyticsQueueName, QueueType.Standard));

        // Create queues.
```

```
        createQueues(queues);

        // Create a topic.
        String topicARN = createFIFOTopic(fifoTopicName);

        // Subscribe each queue to the topic.
        subscribeQueues(queues, topicARN);

        // Allow the newly created topic to send messages to the queues.
        addAccessPolicyToQueuesFINAL(queues, topicARN);

        // Publish a sample price update message with payload.
        publishPriceUpdate(topicARN, "{\"product\": 214, \"price\": 79.99}",
"Consumables");

        // Clean up resources.
        deleteSubscriptions(queues);
        deleteQueues(queues);
        deleteTopic(topicARN);
    }

    public static String createFIFOTopic(String topicName) {
        try {
            // Create a FIFO topic by using the SNS service client.
            Map<String, String> topicAttributes = Map.of(
                    "FifoTopic", "true",
                    "ContentBasedDeduplication", "false");

            CreateTopicRequest topicRequest = CreateTopicRequest.builder()
                    .name(topicName)
                    .attributes(topicAttributes)
                    .build();

            CreateTopicResponse response = snsClient.createTopic(topicRequest);
            String topicArn = response.topicArn();
            System.out.println("The topic ARN is" + topicArn);

            return topicArn;

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
```

```
    }

    public static void subscribeQueues(List<QueueData> queues, String topicARN) {
        queues.forEach(queue -> {
            SubscribeRequest subscribeRequest = SubscribeRequest.builder()
                    .topicArn(topicARN)
                    .endpoint(queue.queueARN)
                    .protocol("sqs")
                    .build();

            // Subscribe to the endpoint by using the SNS service client.
            // Only Amazon SQS queues can receive notifications from an Amazon SNS
FIFO
            // topic.
            SubscribeResponse subscribeResponse =
snsClient.subscribe(subscribeRequest);
            System.out.println("The queue [" + queue.queueARN + "] subscribed to the
topic [" + topicARN + "]");
            queue.subscriptionARN = subscribeResponse.subscriptionArn();
        });
    }

    public static void publishPriceUpdate(String topicArn, String payload, String
groupId) {

        try {
            // Create and publish a message that updates the wholesale price.
            String subject = "Price Update";
            String dedupId = UUID.randomUUID().toString();
            String attributeName = "business";
            String attributeValue = "wholesale";

            MessageAttributeValue msgAttValue = MessageAttributeValue.builder()
                    .dataType("String")
                    .stringValue(attributeValue)
                    .build();

            Map<String, MessageAttributeValue> attributes = new HashMap<>();
            attributes.put(attributeName, msgAttValue);
            PublishRequest pubRequest = PublishRequest.builder()
                    .topicArn(topicArn)
                    .subject(subject)
                    .message(payload)
                    .messageGroupId(groupId)
```

```
                    .messageDeduplicationId(dedupId)
                    .messageAttributes(attributes)
                    .build();

            final PublishResponse response = snsClient.publish(pubRequest);
            System.out.println(response.messageId());
            System.out.println(response.sequenceNumber());
            System.out.println("Message was published to " + topicArn);

        } catch (SnsException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateTopic
  - Publicar
  - Assinar

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando JavaScript.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSEvent.SQSMessage;

public class Function implements RequestHandler<SQSEvent, Void> {
    @Override
    public Void handleRequest(SQSEvent sqsEvent, Context context) {
        for (SQSMessage msg : sqsEvent.getRecords()) {
            processMessage(msg, context);
        }
        context.getLogger().log("done");
        return null;
    }

    private void processMessage(SQSMessage msg, Context context) {
        try {
            context.getLogger().log("Processed message " + msg.getBody());

            // TODO: Do interesting work based on the new message

        } catch (Exception e) {
            context.getLogger().log("An error occurred");
            throw e;
        }

    }
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Java.

```
import com.amazonaws.services.lambda.runtime.Context;
import com.amazonaws.services.lambda.runtime.RequestHandler;
import com.amazonaws.services.lambda.runtime.events.SQSEvent;
import com.amazonaws.services.lambda.runtime.events.SQSBatchResponse;

import java.util.ArrayList;
import java.util.List;

public class ProcessSQSMessageBatch implements RequestHandler<SQSEvent,
 SQSBatchResponse> {
    @Override
    public SQSBatchResponse handleRequest(SQSEvent sqsEvent, Context context) {

        List<SQSBatchResponse.BatchItemFailure> batchItemFailures = new
 ArrayList<SQSBatchResponse.BatchItemFailure>();
        String messageId = "";
        for (SQSEvent.SQSMessage message : sqsEvent.getRecords()) {
            try {
                //process your message
                messageId = message.getMessageId();
            } catch (Exception e) {
                //Add failed message identifier to the batchItemFailures list
                batchItemFailures.add(new
 SQSBatchResponse.BatchItemFailure(messageId));
            }
        }
        return new SQSBatchResponse(batchItemFailures);
    }
}
```

Exemplos do Step Functions usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Step Functions.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Step Functions

Os exemplos de código a seguir mostram como começar a usar o Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Versão Java do Olá.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListStateMachinesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.StateMachineListItem;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
```

```
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListStateMachines {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listMachines(sfnClient);
        sfnClient.close();
    }

    public static void listMachines(SfnClient sfnClient) {
        try {
            ListStateMachinesResponse response = sfnClient.listStateMachines();
            List<StateMachineListItem> machines = response.stateMachines();
            for (StateMachineListItem machine : machines) {
                System.out.println("The name of the state machine is: " +
 machine.name());
                System.out.println("The ARN value is : " +
 machine.stateMachineArn());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Criar uma máquina de estado

O exemplo de código a seguir mostra como criar uma máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createMachine(SfnClient sfnClient, String roleARN, String
stateMachineName, String json) {
       try {
           CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                   .definition(json)
                   .name(stateMachineName)
                   .roleArn(roleARN)
                   .type(StateMachineType.STANDARD)
                   .build();

           CreateStateMachineResponse response =
sfnClient.createStateMachine(machineRequest);
           return response.stateMachineArn();

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte CreateStateMachinea Referência AWS SDK for Java 2.x da API.

Criar uma atividade

O exemplo de código a seguir mostra como criar uma atividade do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createActivity(SfnClient sfnClient, String activityName) {
        try {
            CreateActivityRequest activityRequest = CreateActivityRequest.builder()
                    .name(activityName)
                    .build();

            CreateActivityResponse response =
sfnClient.createActivity(activityRequest);
            return response.activityArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateActivitya Referência AWS SDK for Java 2.x da API.

Excluir uma máquina de estado

O exemplo de código a seguir mostra como excluir uma máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void deleteMachine(SfnClient sfnClient, String stateMachineArn) {
       try {
           DeleteStateMachineRequest deleteStateMachineRequest =
DeleteStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           sfnClient.deleteStateMachine(deleteStateMachineRequest);
           DescribeStateMachineRequest describeStateMachine =
DescribeStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           while (true) {
               DescribeStateMachineResponse response =
sfnClient.describeStateMachine(describeStateMachine);
               System.out.println("The state machine is not deleted yet. The status
is " + response.status());
               Thread.sleep(3000);
           }

       } catch (SfnException | InterruptedException e) {
           System.err.println(e.getMessage());
       }
       System.out.println(stateMachineArn + " was successfully deleted.");
   }
```

- Para obter detalhes da API, consulte DeleteStateMachinea Referência AWS SDK for Java 2.x da API.

Excluir uma atividade.

Os exemplos de código a seguir mostram como excluir uma atividade do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public static void deleteActivity(SfnClient sfnClient, String actArn) {
    try {
        DeleteActivityRequest activityRequest = DeleteActivityRequest.builder()
                .activityArn(actArn)
                .build();

        sfnClient.deleteActivity(activityRequest);
        System.out.println("You have deleted " + actArn);

    } catch (SfnException e) {
        System.err.println(e.awsErrorDetails().errorMessage());
        System.exit(1);
    }
}
```

- Para obter detalhes da API, consulte DeleteActivitya Referência AWS SDK for Java 2.x da API.

Descrever uma máquina de estado

O exemplo de código a seguir mostra como descrever uma máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeStateMachine(SfnClient sfnClient, String
stateMachineArn) {
       try {
           DescribeStateMachineRequest stateMachineRequest =
DescribeStateMachineRequest.builder()
                   .stateMachineArn(stateMachineArn)
                   .build();

           DescribeStateMachineResponse response =
sfnClient.describeStateMachine(stateMachineRequest);
           System.out.println("The name of the State machine is " +
response.name());
           System.out.println("The status of the State machine is " +
response.status());
           System.out.println("The ARN value of the State machine is " +
response.stateMachineArn());
           System.out.println("The role ARN value is " + response.roleArn());

       } catch (SfnException e) {
           System.err.println(e.getMessage());
       }
   }
```

- Para obter detalhes da API, consulte DescribeStateMachinea Referência AWS SDK for Java 2.x da API.

Descrever a execução de uma máquina de estado

O exemplo de código a seguir mostra como descrever uma execução de máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeExe(SfnClient sfnClient, String executionArn) {
```

```
        try {
            DescribeExecutionRequest executionRequest =
DescribeExecutionRequest.builder()
                    .executionArn(executionArn)
                    .build();

            String status = "";
            boolean hasSucceeded = false;
            while (!hasSucceeded) {
                DescribeExecutionResponse response =
sfnClient.describeExecution(executionRequest);
                status = response.statusAsString();
                if (status.compareTo("RUNNING") == 0) {
                    System.out.println("The state machine is still running, let's
wait for it to finish.");
                    Thread.sleep(2000);
                } else if (status.compareTo("SUCCEEDED") == 0) {
                    System.out.println("The Step Function workflow has succeeded");
                    hasSucceeded = true;
                } else {
                    System.out.println("The Status is neither running or
succeeded");
                }
            }
            System.out.println("The Status is " + status);

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeExecutiona Referência AWS SDK for Java 2.x da API.

Obter dados de tarefas para uma atividade

O exemplo de código a seguir mostra como obter dados de tarefa para uma atividade de Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static List<String> getActivityTask(SfnClient sfnClient, String actArn) {
       List<String> myList = new ArrayList<>();
       GetActivityTaskRequest getActivityTaskRequest =
GetActivityTaskRequest.builder()
               .activityArn(actArn)
               .build();

       GetActivityTaskResponse response =
sfnClient.getActivityTask(getActivityTaskRequest);
       myList.add(response.taskToken());
       myList.add(response.input());
       return myList;
   }

   /// <summary>
   /// Stop execution of a Step Functions workflow.
   /// </summary>
   /// <param name="executionArn">The Amazon Resource Name (ARN) of
   /// the Step Functions execution to stop.</param>
   /// <returns>A Boolean value indicating the success of the action.</returns>
   public async Task<bool> StopExecution(string executionArn)
   {
       var response =
           await _amazonStepFunctions.StopExecutionAsync(new StopExecutionRequest
{ ExecutionArn = executionArn });
       return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
   }
```

- Para obter detalhes da API, consulte GetActivityTaska Referência AWS SDK for Java 2.x da API.

Listar atividades

O exemplo de código a seguir mostra como listar atividades do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListActivitiesRequest;
import software.amazon.awssdk.services.sfn.model.ListActivitiesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.ActivityListItem;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListActivities {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listAllActivites(sfnClient);
        sfnClient.close();
    }

    public static void listAllActivites(SfnClient sfnClient) {
        try {
            ListActivitiesRequest activitiesRequest =
 ListActivitiesRequest.builder()
```

```
                    .maxResults(10)
                    .build();

            ListActivitiesResponse response =
 sfnClient.listActivities(activitiesRequest);
            List<ActivityListItem> items = response.activities();
            for (ActivityListItem item : items) {
                System.out.println("The activity ARN is " + item.activityArn());
                System.out.println("The activity name is " + item.name());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListActivitiesa Referência AWS SDK for Java 2.x da API.

Listar execuções de máquinas de estado

O exemplo de código a seguir mostra como listar execuções de máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getExeHistory(SfnClient sfnClient, String exeARN) {
        try {
            GetExecutionHistoryRequest historyRequest =
 GetExecutionHistoryRequest.builder()
                    .executionArn(exeARN)
                    .maxResults(10)
                    .build();
```

```
            GetExecutionHistoryResponse historyResponse =
 sfnClient.getExecutionHistory(historyRequest);
            List<HistoryEvent> events = historyResponse.events();
            for (HistoryEvent event : events) {
                System.out.println("The event type is " + event.type().toString());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte ListExecutionsa Referência AWS SDK for Java 2.x da API.

Listar máquinas de estado

O exemplo de código a seguir mostra como listar estado de máquinas do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sfn.SfnClient;
import software.amazon.awssdk.services.sfn.model.ListStateMachinesResponse;
import software.amazon.awssdk.services.sfn.model.SfnException;
import software.amazon.awssdk.services.sfn.model.StateMachineListItem;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
```

```
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class ListStateMachines {
    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        listMachines(sfnClient);
        sfnClient.close();
    }

    public static void listMachines(SfnClient sfnClient) {
        try {
            ListStateMachinesResponse response = sfnClient.listStateMachines();
            List<StateMachineListItem> machines = response.stateMachines();
            for (StateMachineListItem machine : machines) {
                System.out.println("The name of the state machine is: " +
 machine.name());
                System.out.println("The ARN value is : " +
 machine.stateMachineArn());
            }

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte ListStateMachinesa Referência AWS SDK for Java 2.x da API.

Enviar uma resposta bem-sucedida para uma tarefa

O exemplo de código a seguir mostra como enviar uma resposta de sucesso para uma tarefa de Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void sendTaskSuccess(SfnClient sfnClient, String token, String
json) {
       try {
           SendTaskSuccessRequest successRequest = SendTaskSuccessRequest.builder()
                   .taskToken(token)
                   .output(json)
                   .build();

           sfnClient.sendTaskSuccess(successRequest);

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte SendTaskSuccessa Referência AWS SDK for Java 2.x da API.

Iniciar execução de máquina de estado

O exemplo de código a seguir mostra como iniciar uma execução de máquina de estado do Step Functions.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String startWorkflow(SfnClient sfnClient, String stateMachineArn,
String jsonEx) {
       UUID uuid = UUID.randomUUID();
       String uuidValue = uuid.toString();
       try {
           StartExecutionRequest executionRequest = StartExecutionRequest.builder()
                   .input(jsonEx)
                   .stateMachineArn(stateMachineArn)
                   .name(uuidValue)
                   .build();

           StartExecutionResponse response =
sfnClient.startExecution(executionRequest);
           return response.executionArn();

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte StartExecutiona Referência AWS SDK for Java 2.x da API.

Cenários

Começar a usar máquinas de estado

O código de exemplo a seguir mostra como:

- Criar uma atividade.
- Criar uma máquina de estado a partir de uma definição da Amazon States Language que contenha a atividade criada anteriormente como uma etapa.
- Executar a máquina de estado e responder à atividade com entrada do usuário.
- Obter o status e a saída finais após a conclusão da execução e, em seguida, limpar os recursos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
/**
 * You can obtain the JSON file to create a state machine in the following
 * GitHub location.
 *
 * https://github.com/awsdocs/aws-doc-sdk-examples/tree/main/resources/sample_files
 *
 * To run this code example, place the chat_sfn_state_machine.json file into
 * your project's resources folder.
 *
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * This Java code example performs the following tasks:
 *
 * 1. Creates an activity.
 * 2. Creates a state machine.
 * 3. Describes the state machine.
 * 4. Starts execution of the state machine and interacts with it.
 * 5. Describes the execution.
 * 6. Delete the activity.
 * 7. Deletes the state machine.
 */
public class StepFunctionsScenario {
    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) throws Exception {
        final String usage = """

                Usage:
                    <roleARN> <activityName> <stateMachineName>
```

```
                Where:
                    roleName - The name of the IAM role to create for this state
machine.
                    activityName - The name of an activity to create.
                    stateMachineName - The name of the state machine to create.
                """;

        if (args.length != 3) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleName = args[0];
        String activityName = args[1];
        String stateMachineName = args[2];
        String polJSON = "{\n" +
                "    \"Version\": \"2012-10-17\",\n" +
                "    \"Statement\": [\n" +
                "        {\n" +
                "            \"Sid\": \"\",\n" +
                "            \"Effect\": \"Allow\",\n" +
                "            \"Principal\": {\n" +
                "                \"Service\": \"states.amazonaws.com\"\n" +
                "            },\n" +
                "            \"Action\": \"sts:AssumeRole\"\n" +
                "        }\n" +
                "    ]\n" +
                "}";

        Scanner sc = new Scanner(System.in);
        boolean action = false;

        Region region = Region.US_EAST_1;
        SfnClient sfnClient = SfnClient.builder()
                .region(region)
                .build();

        Region regionGl = Region.AWS_GLOBAL;
        IamClient iam = IamClient.builder()
                .region(regionGl)
                .build();

        System.out.println(DASHES);
        System.out.println("Welcome to the AWS Step Functions example scenario.");
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Create an activity.");
        String activityArn = createActivity(sfnClient, activityName);
        System.out.println("The ARN of the activity is " + activityArn);
        System.out.println(DASHES);

        // Get JSON to use for the state machine and place the activityArn value
into
        // it.
        InputStream input = StepFunctionsScenario.class.getClassLoader()
                .getResourceAsStream("chat_sfn_state_machine.json");
        ObjectMapper mapper = new ObjectMapper();
        JsonNode jsonNode = mapper.readValue(input, JsonNode.class);
        String jsonString = mapper.writeValueAsString(jsonNode);

        // Modify the Resource node.
        ObjectMapper objectMapper = new ObjectMapper();
        JsonNode root = objectMapper.readTree(jsonString);
        ((ObjectNode) root.path("States").path("GetInput")).put("Resource",
activityArn);

        // Convert the modified Java object back to a JSON string.
        String stateDefinition = objectMapper.writeValueAsString(root);
        System.out.println(stateDefinition);

        System.out.println(DASHES);
        System.out.println("2. Create a state machine.");
        String roleARN = createIAMRole(iam, roleName, polJSON);
        String stateMachineArn = createMachine(sfnClient, roleARN, stateMachineName,
stateDefinition);
        System.out.println("The ARN of the state machine is " + stateMachineArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Describe the state machine.");
        describeStateMachine(sfnClient, stateMachineArn);
        System.out.println("What should ChatSFN call you?");
        String userName = sc.nextLine();
        System.out.println("Hello " + userName);
        System.out.println(DASHES);

        System.out.println(DASHES);
```

```
        // The JSON to pass to the StartExecution call.
        String executionJson = "{ \"name\" : \"" + userName + "\" }";
        System.out.println(executionJson);
        System.out.println("4. Start execution of the state machine and interact
with it.");
        String runArn = startWorkflow(sfnClient, stateMachineArn, executionJson);
        System.out.println("The ARN of the state machine execution is " + runArn);
        List<String> myList;
        while (!action) {
            myList = getActivityTask(sfnClient, activityArn);
            System.out.println("ChatSFN: " + myList.get(1));
            System.out.println(userName + " please specify a value.");
            String myAction = sc.nextLine();
            if (myAction.compareTo("done") == 0)
                action = true;

            System.out.println("You have selected " + myAction);
            String taskJson = "{ \"action\" : \"" + myAction + "\" }";
            System.out.println(taskJson);
            sendTaskSuccess(sfnClient, myList.get(0), taskJson);
        }
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Describe the execution.");
        describeExe(sfnClient, runArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Delete the activity.");
        deleteActivity(sfnClient, activityArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. Delete the state machines.");
        deleteMachine(sfnClient, stateMachineArn);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("The AWS Step Functions example scenario is complete.");
        System.out.println(DASHES);
    }
```

```
   public static String createIAMRole(IamClient iam, String rolename, String
polJSON) {
       try {
           CreateRoleRequest request = CreateRoleRequest.builder()
                   .roleName(rolename)
                   .assumeRolePolicyDocument(polJSON)
                   .description("Created using the AWS SDK for Java")
                   .build();

           CreateRoleResponse response = iam.createRole(request);
           return response.role().arn();

       } catch (IamException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }

   public static void describeExe(SfnClient sfnClient, String executionArn) {
       try {
           DescribeExecutionRequest executionRequest =
DescribeExecutionRequest.builder()
                   .executionArn(executionArn)
                   .build();

           String status = "";
           boolean hasSucceeded = false;
           while (!hasSucceeded) {
               DescribeExecutionResponse response =
sfnClient.describeExecution(executionRequest);
               status = response.statusAsString();
               if (status.compareTo("RUNNING") == 0) {
                   System.out.println("The state machine is still running, let's
wait for it to finish.");
                   Thread.sleep(2000);
               } else if (status.compareTo("SUCCEEDED") == 0) {
                   System.out.println("The Step Function workflow has succeeded");
                   hasSucceeded = true;
               } else {
                   System.out.println("The Status is neither running or
succeeded");
               }
           }
```

```
            System.out.println("The Status is " + status);

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void sendTaskSuccess(SfnClient sfnClient, String token, String
 json) {
        try {
            SendTaskSuccessRequest successRequest = SendTaskSuccessRequest.builder()
                    .taskToken(token)
                    .output(json)
                    .build();

            sfnClient.sendTaskSuccess(successRequest);

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static List<String> getActivityTask(SfnClient sfnClient, String actArn) {
        List<String> myList = new ArrayList<>();
        GetActivityTaskRequest getActivityTaskRequest =
 GetActivityTaskRequest.builder()
                .activityArn(actArn)
                .build();

        GetActivityTaskResponse response =
 sfnClient.getActivityTask(getActivityTaskRequest);
        myList.add(response.taskToken());
        myList.add(response.input());
        return myList;
    }

    public static void deleteActivity(SfnClient sfnClient, String actArn) {
        try {
            DeleteActivityRequest activityRequest = DeleteActivityRequest.builder()
                    .activityArn(actArn)
                    .build();
```

```
            sfnClient.deleteActivity(activityRequest);
            System.out.println("You have deleted " + actArn);

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
    }

    public static void describeStateMachine(SfnClient sfnClient, String
stateMachineArn) {
        try {
            DescribeStateMachineRequest stateMachineRequest =
DescribeStateMachineRequest.builder()
                    .stateMachineArn(stateMachineArn)
                    .build();

            DescribeStateMachineResponse response =
sfnClient.describeStateMachine(stateMachineRequest);
            System.out.println("The name of the State machine is " +
response.name());
            System.out.println("The status of the State machine is " +
response.status());
            System.out.println("The ARN value of the State machine is " +
response.stateMachineArn());
            System.out.println("The role ARN value is " + response.roleArn());

        } catch (SfnException e) {
            System.err.println(e.getMessage());
        }
    }

    public static void deleteMachine(SfnClient sfnClient, String stateMachineArn) {
        try {
            DeleteStateMachineRequest deleteStateMachineRequest =
DeleteStateMachineRequest.builder()
                    .stateMachineArn(stateMachineArn)
                    .build();

            sfnClient.deleteStateMachine(deleteStateMachineRequest);
            DescribeStateMachineRequest describeStateMachine =
DescribeStateMachineRequest.builder()
                    .stateMachineArn(stateMachineArn)
                    .build();
```

```
            while (true) {
                DescribeStateMachineResponse response =
sfnClient.describeStateMachine(describeStateMachine);
                System.out.println("The state machine is not deleted yet. The status
is " + response.status());
                Thread.sleep(3000);
            }

        } catch (SfnException | InterruptedException e) {
            System.err.println(e.getMessage());
        }
        System.out.println(stateMachineArn + " was successfully deleted.");
    }

    public static String startWorkflow(SfnClient sfnClient, String stateMachineArn,
String jsonEx) {
        UUID uuid = UUID.randomUUID();
        String uuidValue = uuid.toString();
        try {
            StartExecutionRequest executionRequest = StartExecutionRequest.builder()
                    .input(jsonEx)
                    .stateMachineArn(stateMachineArn)
                    .name(uuidValue)
                    .build();

            StartExecutionResponse response =
sfnClient.startExecution(executionRequest);
            return response.executionArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createMachine(SfnClient sfnClient, String roleARN, String
stateMachineName, String json) {
        try {
            CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                    .definition(json)
                    .name(stateMachineName)
```

```
                    .roleArn(roleARN)
                    .type(StateMachineType.STANDARD)
                    .build();

            CreateStateMachineResponse response =
 sfnClient.createStateMachine(machineRequest);
            return response.stateMachineArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }

    public static String createActivity(SfnClient sfnClient, String activityName) {
        try {
            CreateActivityRequest activityRequest = CreateActivityRequest.builder()
                    .name(activityName)
                    .build();

            CreateActivityResponse response =
 sfnClient.createActivity(activityRequest);
            return response.activityArn();

        } catch (SfnException e) {
            System.err.println(e.awsErrorDetails().errorMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine
  - DescribeExecution

- DescribeStateMachine
- GetActivityTask
- ListActivities
- ListStateMachines
- SendTaskSuccess
- StartExecution
- StopExecution

Exemplos do AWS STS usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.sts.StsClient;
import software.amazon.awssdk.services.sts.model.AssumeRoleRequest;
import software.amazon.awssdk.services.sts.model.StsException;
import software.amazon.awssdk.services.sts.model.AssumeRoleResponse;
import software.amazon.awssdk.services.sts.model.Credentials;
import java.time.Instant;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.time.format.FormatStyle;
import java.util.Locale;

/**
 * To make this code example work, create a Role that you want to assume.
 * Then define a Trust Relationship in the AWS Console. You can use this as an
 * example:
 *
 * {
 * "Version": "2012-10-17",
 * "Statement": [
 * {
 * "Effect": "Allow",
 * "Principal": {
 * "AWS": "<Specify the ARN of your IAM user you are using in this code
 * example>"
 * },
 * "Action": "sts:AssumeRole"
 * }
 * ]
 * }
 *
 * For more information, see "Editing the Trust Relationship for an Existing
 * Role" in the AWS Directory Service guide.
 *
```

```
 * Also, set up your development environment, including your credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class AssumeRole {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <roleArn> <roleSessionName>\s

                Where:
                    roleArn - The Amazon Resource Name (ARN) of the role to assume
 (for example, rn:aws:iam::000008047983:role/s3role).\s
                    roleSessionName - An identifier for the assumed role session
 (for example, mysession).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String roleArn = args[0];
        String roleSessionName = args[1];
        Region region = Region.US_EAST_1;
        StsClient stsClient = StsClient.builder()
                .region(region)
                .build();

        assumeGivenRole(stsClient, roleArn, roleSessionName);
        stsClient.close();
    }

    public static void assumeGivenRole(StsClient stsClient, String roleArn, String
 roleSessionName) {
        try {
            AssumeRoleRequest roleRequest = AssumeRoleRequest.builder()
                    .roleArn(roleArn)
                    .roleSessionName(roleSessionName)
                    .build();
```

```
            AssumeRoleResponse roleResponse = stsClient.assumeRole(roleRequest);
            Credentials myCreds = roleResponse.credentials();

            // Display the time when the temp creds expire.
            Instant exTime = myCreds.expiration();
            String tokenInfo = myCreds.sessionToken();

            // Convert the Instant to readable date.
            DateTimeFormatter formatter =
 DateTimeFormatter.ofLocalizedDateTime(FormatStyle.SHORT)
                    .withLocale(Locale.US)
                    .withZone(ZoneId.systemDefault());

            formatter.format(exTime);
            System.out.println("The token " + tokenInfo + "  expires on " + exTime);

        } catch (StsException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for Java 2.x da API.

Exemplos do AWS Support usando o SDK para Java 2.x

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com AWS Support.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.support.SupportClient;
import software.amazon.awssdk.services.support.model.Category;
import software.amazon.awssdk.services.support.model.DescribeServicesRequest;
import software.amazon.awssdk.services.support.model.DescribeServicesResponse;
import software.amazon.awssdk.services.support.model.Service;
import software.amazon.awssdk.services.support.model.SupportException;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * In addition, you must have the AWS Business Support Plan to use the AWS
 * Support Java API. For more information, see:
 *
 * https://aws.amazon.com/premiumsupport/plans/
 *
 * This Java example performs the following task:
 *
 * 1. Gets and displays available services.
 *
 *
 * NOTE: To see multiple operations, see SupportScenario.
 */
```

```
public class HelloSupport {
    public static void main(String[] args) {
        Region region = Region.US_WEST_2;
        SupportClient supportClient = SupportClient.builder()
                .region(region)
                .build();

        System.out.println("***** Step 1. Get and display available services.");
        displayServices(supportClient);
    }

    // Return a List that contains a Service name and Category name.
    public static void displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
 DescribeServicesRequest.builder()
                    .language("en")
                    .build();

            DescribeServicesResponse response =
 supportClient.describeServices(servicesRequest);
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;

                System.out.println("The Service name is: " + service.name());

                // Display the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                }
                index++;
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for Java 2.x da API.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma comunicação a um caso

O exemplo de código a seguir mostra como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void addAttachSupportCase(SupportClient supportClient, String
caseId, String attachmentSetId) {
       try {
           AddCommunicationToCaseRequest caseRequest =
AddCommunicationToCaseRequest.builder()
                   .caseId(caseId)
                   .attachmentSetId(attachmentSetId)
                   .communicationBody("Please refer to attachment for details.")
                   .build();

           AddCommunicationToCaseResponse response =
supportClient.addCommunicationToCase(caseRequest);
           if (response.result())
               System.out.println("You have successfully added a communication to
an AWS Support case");
```

```
            else
                System.out.println("There was an error adding the communication to
an AWS Support case");

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte AddCommunicationToCasea Referência AWS SDK for Java 2.x da API.

Adicionar um anexo a um conjunto

O exemplo de código a seguir mostra como adicionar um anexo do AWS Support a um conjunto de anexos.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String addAttachment(SupportClient supportClient, String
fileAttachment) {
        try {
            File myFile = new File(fileAttachment);
            InputStream sourceStream = new FileInputStream(myFile);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            Attachment attachment = Attachment.builder()
                    .fileName(myFile.getName())
                    .data(sourceBytes)
                    .build();

            AddAttachmentsToSetRequest setRequest =
AddAttachmentsToSetRequest.builder()
```

```
                    .attachments(attachment)
                    .build();

            AddAttachmentsToSetResponse response =
supportClient.addAttachmentsToSet(setRequest);
            return response.attachmentSetId();

        } catch (SupportException | FileNotFoundException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte AddAttachmentsToSeta Referência AWS SDK for Java 2.x da API.

Criar um caso

O exemplo de código a seguir mostra como criar um novo caso do AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static String createSupportCase(SupportClient supportClient, List<String>
sevCatList, String sevLevel) {
        try {
            String serviceCode = sevCatList.get(0);
            String caseCat = sevCatList.get(1);
            CreateCaseRequest caseRequest = CreateCaseRequest.builder()
                    .categoryCode(caseCat.toLowerCase())
                    .serviceCode(serviceCode.toLowerCase())
                    .severityCode(sevLevel.toLowerCase())
                    .communicationBody("Test issue with " +
serviceCode.toLowerCase())
```

```
                    .subject("Test case, please ignore")
                    .language("en")
                    .issueType("technical")
                    .build();

            CreateCaseResponse response = supportClient.createCase(caseRequest);
            return response.caseId();

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte CreateCasea Referência AWS SDK for Java 2.x da API.

Descrever um anexo

O exemplo de código a seguir mostra como descrever um anexo para um caso do AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void describeAttachment(SupportClient supportClient, String
attachId) {
       try {
           DescribeAttachmentRequest attachmentRequest =
DescribeAttachmentRequest.builder()
                   .attachmentId(attachId)
                   .build();

           DescribeAttachmentResponse response =
supportClient.describeAttachment(attachmentRequest);
           System.out.println("The name of the file is " +
response.attachment().fileName());
```

```
        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeAttachmenta Referência AWS SDK for Java 2.x da API.

Descrever casos

O exemplo de código a seguir mostra como descrever casos do AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public static void getOpenCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);

            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(20)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
```

```
                System.out.println("The case status is " + sinCase.status());
                System.out.println("The case Id is " + sinCase.caseId());
                System.out.println("The case subject is " + sinCase.subject());
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }
```

- Para obter detalhes da API, consulte DescribeCasesa Referência AWS SDK for Java 2.x da API.

Descrever as comunicações

O exemplo de código a seguir mostra como descrever as comunicações do AWS Support para um caso.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String listCommunications(SupportClient supportClient, String
caseId) {
       try {
           String attachId = null;
           DescribeCommunicationsRequest communicationsRequest =
DescribeCommunicationsRequest.builder()
                   .caseId(caseId)
                   .maxResults(10)
                   .build();

           DescribeCommunicationsResponse response =
supportClient.describeCommunications(communicationsRequest);
           List<Communication> communications = response.communications();
```

```
            for (Communication comm : communications) {
                System.out.println("the body is: " + comm.body());

                // Get the attachment id value.
                List<AttachmentDetails> attachments = comm.attachmentSet();
                for (AttachmentDetails detail : attachments) {
                    attachId = detail.attachmentId();
                }
            }
            return attachId;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }
```

- Para obter detalhes da API, consulte DescribeCommunicationsa Referência AWS SDK for Java 2.x da API.

Descrever os serviços

O exemplo de código a seguir mostra como descrever a lista de serviços do AWS.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Return a List that contains a Service name and Category name.
    public static List<String> displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
DescribeServicesRequest.builder()
                    .language("en")
                    .build();
```

```
            DescribeServicesResponse response =
supportClient.describeServices(servicesRequest);
            String serviceCode = null;
            String catName = null;
            List<String> sevCatList = new ArrayList<>();
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;

                System.out.println("The Service name is: " + service.name());
                if (service.name().compareTo("Account") == 0)
                    serviceCode = service.code();

                // Get the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                    if (cat.name().compareTo("Security") == 0)
                        catName = cat.name();
                }
                index++;
            }

            // Push the two values to the list.
            sevCatList.add(serviceCode);
            sevCatList.add(catName);
            return sevCatList;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return null;
    }
```

- Para obter detalhes da API, consulte DescribeServicesa Referência AWS SDK for Java 2.x da API.

Descrever os níveis de gravidade

O exemplo de código a seguir mostra como descrever os níveis de gravidade do AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String displaySevLevels(SupportClient supportClient) {
       try {
           DescribeSeverityLevelsRequest severityLevelsRequest =
DescribeSeverityLevelsRequest.builder()
                   .language("en")
                   .build();

           DescribeSeverityLevelsResponse response =
supportClient.describeSeverityLevels(severityLevelsRequest);
           List<SeverityLevel> severityLevels = response.severityLevels();
           String levelName = null;
           for (SeverityLevel sevLevel : severityLevels) {
               System.out.println("The severity level name is: " +
sevLevel.name());
               if (sevLevel.name().compareTo("High") == 0)
                   levelName = sevLevel.name();
           }
           return levelName;

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte DescribeSeverityLevelsa Referência AWS SDK for Java 2.x da API.

Resolver caso

O exemplo de código a seguir mostra como resolver um caso do AWS Support.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static void resolveSupportCase(SupportClient supportClient, String
caseId) {
       try {
           ResolveCaseRequest caseRequest = ResolveCaseRequest.builder()
                   .caseId(caseId)
                   .build();

           ResolveCaseResponse response = supportClient.resolveCase(caseRequest);
           System.out.println("The status of case " + caseId + " is " +
response.finalCaseStatus());

       } catch (SupportException e) {
           System.out.println(e.getLocalizedMessage());
           System.exit(1);
       }
   }
```

- Para obter detalhes da API, consulte ResolveCasea Referência AWS SDK for Java 2.x da API.

Cenários

Conceitos básicos de casos

O código de exemplo a seguir mostra como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.

- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute várias operações do AWS Support.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.support.SupportClient;
import software.amazon.awssdk.services.support.model.AddAttachmentsToSetResponse;
import software.amazon.awssdk.services.support.model.AddCommunicationToCaseRequest;
import software.amazon.awssdk.services.support.model.AddCommunicationToCaseResponse;
import software.amazon.awssdk.services.support.model.Attachment;
import software.amazon.awssdk.services.support.model.AttachmentDetails;
import software.amazon.awssdk.services.support.model.CaseDetails;
import software.amazon.awssdk.services.support.model.Category;
import software.amazon.awssdk.services.support.model.Communication;
import software.amazon.awssdk.services.support.model.CreateCaseRequest;
import software.amazon.awssdk.services.support.model.CreateCaseResponse;
import software.amazon.awssdk.services.support.model.DescribeAttachmentRequest;
import software.amazon.awssdk.services.support.model.DescribeAttachmentResponse;
import software.amazon.awssdk.services.support.model.DescribeCasesRequest;
import software.amazon.awssdk.services.support.model.DescribeCasesResponse;
import software.amazon.awssdk.services.support.model.DescribeCommunicationsRequest;
import software.amazon.awssdk.services.support.model.DescribeCommunicationsResponse;
import software.amazon.awssdk.services.support.model.DescribeServicesRequest;
import software.amazon.awssdk.services.support.model.DescribeServicesResponse;
import software.amazon.awssdk.services.support.model.DescribeSeverityLevelsRequest;
import software.amazon.awssdk.services.support.model.DescribeSeverityLevelsResponse;
import software.amazon.awssdk.services.support.model.ResolveCaseRequest;
import software.amazon.awssdk.services.support.model.ResolveCaseResponse;
import software.amazon.awssdk.services.support.model.Service;
```

```
import software.amazon.awssdk.services.support.model.SeverityLevel;
import software.amazon.awssdk.services.support.model.SupportException;
import software.amazon.awssdk.services.support.model.AddAttachmentsToSetRequest;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.time.Instant;
import java.time.temporal.ChronoUnit;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java (v2) code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 *
 * In addition, you must have the AWS Business Support Plan to use the AWS
 * Support Java API. For more information, see:
 *
 * https://aws.amazon.com/premiumsupport/plans/
 *
 * This Java example performs the following tasks:
 *
 * 1. Gets and displays available services.
 * 2. Gets and displays severity levels.
 * 3. Creates a support case by using the selected service, category, and
 * severity level.
 * 4. Gets a list of open cases for the current day.
 * 5. Creates an attachment set with a generated file.
 * 6. Adds a communication with the attachment to the support case.
 * 7. Lists the communications of the support case.
 * 8. Describes the attachment set included with the communication.
 * 9. Resolves the support case.
 * 10. Gets a list of resolved cases for the current day.
 */
public class SupportScenario {

    public static final String DASHES = new String(new char[80]).replace("\0", "-");

    public static void main(String[] args) {
```

```
        final String usage = """

                Usage:
                    <fileAttachment>Where:
                    fileAttachment - The file can be a simple saved .txt file to use
as an email attachment.\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String fileAttachment = args[0];
        Region region = Region.US_WEST_2;
        SupportClient supportClient = SupportClient.builder()
                .region(region)
                .build();

        System.out.println(DASHES);
        System.out.println("***** Welcome to the AWS Support case example
scenario.");
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("1. Get and display available services.");
        List<String> sevCatList = displayServices(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("2. Get and display Support severity levels.");
        String sevLevel = displaySevLevels(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("3. Create a support case using the selected service,
category, and severity level.");
        String caseId = createSupportCase(supportClient, sevCatList, sevLevel);
        if (caseId.compareTo("") == 0) {
            System.out.println("A support case was not successfully created!");
            System.exit(1);
        } else
            System.out.println("Support case " + caseId + " was successfully
created!");
```

```
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("4. Get open support cases.");
        getOpenCase(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("5. Create an attachment set with a generated file to add
to the case.");
        String attachmentSetId = addAttachment(supportClient, fileAttachment);
        System.out.println("The Attachment Set id value is" + attachmentSetId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("6. Add communication with the attachment to the support
case.");
        addAttachSupportCase(supportClient, caseId, attachmentSetId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("7. List the communications of the support case.");
        String attachId = listCommunications(supportClient, caseId);
        System.out.println("The Attachment id value is" + attachId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("8. Describe the attachment set included with the
communication.");
        describeAttachment(supportClient, attachId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("9. Resolve the support case.");
        resolveSupportCase(supportClient, caseId);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("10. Get a list of resolved cases for the current day.");
        getResolvedCase(supportClient);
        System.out.println(DASHES);

        System.out.println(DASHES);
        System.out.println("***** This Scenario has successfully completed");
```

```
        System.out.println(DASHES);
    }

    public static void getResolvedCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);

            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(30)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .includeResolvedCases(true)
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
                if (sinCase.status().compareTo("resolved") == 0)
                    System.out.println("The case status is " + sinCase.status());
            }

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void resolveSupportCase(SupportClient supportClient, String
caseId) {
        try {
            ResolveCaseRequest caseRequest = ResolveCaseRequest.builder()
                    .caseId(caseId)
                    .build();

            ResolveCaseResponse response = supportClient.resolveCase(caseRequest);
            System.out.println("The status of case " + caseId + " is " +
response.finalCaseStatus());

        } catch (SupportException e) {
```

```
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static void describeAttachment(SupportClient supportClient, String
attachId) {
        try {
            DescribeAttachmentRequest attachmentRequest =
DescribeAttachmentRequest.builder()
                    .attachmentId(attachId)
                    .build();

            DescribeAttachmentResponse response =
supportClient.describeAttachment(attachmentRequest);
            System.out.println("The name of the file is " +
response.attachment().fileName());

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String listCommunications(SupportClient supportClient, String
caseId) {
        try {
            String attachId = null;
            DescribeCommunicationsRequest communicationsRequest =
DescribeCommunicationsRequest.builder()
                    .caseId(caseId)
                    .maxResults(10)
                    .build();

            DescribeCommunicationsResponse response =
supportClient.describeCommunications(communicationsRequest);
            List<Communication> communications = response.communications();
            for (Communication comm : communications) {
                System.out.println("the body is: " + comm.body());

                // Get the attachment id value.
                List<AttachmentDetails> attachments = comm.attachmentSet();
                for (AttachmentDetails detail : attachments) {
                    attachId = detail.attachmentId();
```

```
                }
            }
            return attachId;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    public static void addAttachSupportCase(SupportClient supportClient, String
caseId, String attachmentSetId) {
        try {
            AddCommunicationToCaseRequest caseRequest =
AddCommunicationToCaseRequest.builder()
                    .caseId(caseId)
                    .attachmentSetId(attachmentSetId)
                    .communicationBody("Please refer to attachment for details.")
                    .build();

            AddCommunicationToCaseResponse response =
supportClient.addCommunicationToCase(caseRequest);
            if (response.result())
                System.out.println("You have successfully added a communication to
an AWS Support case");
            else
                System.out.println("There was an error adding the communication to
an AWS Support case");

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String addAttachment(SupportClient supportClient, String
fileAttachment) {
        try {
            File myFile = new File(fileAttachment);
            InputStream sourceStream = new FileInputStream(myFile);
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            Attachment attachment = Attachment.builder()
```

```
                    .fileName(myFile.getName())
                    .data(sourceBytes)
                    .build();

            AddAttachmentsToSetRequest setRequest =
AddAttachmentsToSetRequest.builder()
                    .attachments(attachment)
                    .build();

            AddAttachmentsToSetResponse response =
supportClient.addAttachmentsToSet(setRequest);
            return response.attachmentSetId();

        } catch (SupportException | FileNotFoundException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    public static void getOpenCase(SupportClient supportClient) {
        try {
            // Specify the start and end time.
            Instant now = Instant.now();
            java.time.LocalDate.now();
            Instant yesterday = now.minus(1, ChronoUnit.DAYS);

            DescribeCasesRequest describeCasesRequest =
DescribeCasesRequest.builder()
                    .maxResults(20)
                    .afterTime(yesterday.toString())
                    .beforeTime(now.toString())
                    .build();

            DescribeCasesResponse response =
supportClient.describeCases(describeCasesRequest);
            List<CaseDetails> cases = response.cases();
            for (CaseDetails sinCase : cases) {
                System.out.println("The case status is " + sinCase.status());
                System.out.println("The case Id is " + sinCase.caseId());
                System.out.println("The case subject is " + sinCase.subject());
            }

        } catch (SupportException e) {
```

```
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
    }

    public static String createSupportCase(SupportClient supportClient, List<String>
sevCatList, String sevLevel) {
        try {
            String serviceCode = sevCatList.get(0);
            String caseCat = sevCatList.get(1);
            CreateCaseRequest caseRequest = CreateCaseRequest.builder()
                    .categoryCode(caseCat.toLowerCase())
                    .serviceCode(serviceCode.toLowerCase())
                    .severityCode(sevLevel.toLowerCase())
                    .communicationBody("Test issue with " +
serviceCode.toLowerCase())
                    .subject("Test case, please ignore")
                    .language("en")
                    .issueType("technical")
                    .build();

            CreateCaseResponse response = supportClient.createCase(caseRequest);
            return response.caseId();

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    public static String displaySevLevels(SupportClient supportClient) {
        try {
            DescribeSeverityLevelsRequest severityLevelsRequest =
DescribeSeverityLevelsRequest.builder()
                    .language("en")
                    .build();

            DescribeSeverityLevelsResponse response =
supportClient.describeSeverityLevels(severityLevelsRequest);
            List<SeverityLevel> severityLevels = response.severityLevels();
            String levelName = null;
            for (SeverityLevel sevLevel : severityLevels) {
```

```
                System.out.println("The severity level name is: " +
sevLevel.name());
                if (sevLevel.name().compareTo("High") == 0)
                    levelName = sevLevel.name();
            }
            return levelName;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return "";
    }

    // Return a List that contains a Service name and Category name.
    public static List<String> displayServices(SupportClient supportClient) {
        try {
            DescribeServicesRequest servicesRequest =
DescribeServicesRequest.builder()
                    .language("en")
                    .build();

            DescribeServicesResponse response =
supportClient.describeServices(servicesRequest);
            String serviceCode = null;
            String catName = null;
            List<String> sevCatList = new ArrayList<>();
            List<Service> services = response.services();

            System.out.println("Get the first 10 services");
            int index = 1;
            for (Service service : services) {
                if (index == 11)
                    break;

                System.out.println("The Service name is: " + service.name());
                if (service.name().compareTo("Account") == 0)
                    serviceCode = service.code();

                // Get the Categories for this service.
                List<Category> categories = service.categories();
                for (Category cat : categories) {
                    System.out.println("The category name is: " + cat.name());
                    if (cat.name().compareTo("Security") == 0)
```

```
                        catName = cat.name();
                }
                index++;
            }

            // Push the two values to the list.
            sevCatList.add(serviceCode);
            sevCatList.add(catName);
            return sevCatList;

        } catch (SupportException e) {
            System.out.println(e.getLocalizedMessage());
            System.exit(1);
        }
        return null;
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Exemplos do Systems Manager usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Systems Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adicionar um parâmetro

O exemplo de código a seguir mostra como adicionar um parâmetro do Systems Manager.

SDK para Java 2.x

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.ParameterType;
import software.amazon.awssdk.services.ssm.model.PutParameterRequest;
import software.amazon.awssdk.services.ssm.model.SsmException;

public class PutParameter {

    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <paraName>
```

```
                Where:
                    paraName - The name of the parameter.
                    paraValue - The value of the parameter.
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String paraName = args[0];
        String paraValue = args[1];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        putParaValue(ssmClient, paraName, paraValue);
        ssmClient.close();
    }

    public static void putParaValue(SsmClient ssmClient, String paraName, String
 value) {
        try {
            PutParameterRequest parameterRequest = PutParameterRequest.builder()
                    .name(paraName)
                    .type(ParameterType.STRING)
                    .value(value)
                    .build();

            ssmClient.putParameter(parameterRequest);
            System.out.println("The parameter was successfully added.");

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte PutParameter a Referência AWS SDK for Java 2.x da API.

Crie um novo OpsItem

O exemplo de código a seguir mostra como criar um novo OpsItem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.CreateOpsItemRequest;
import software.amazon.awssdk.services.ssm.model.CreateOpsItemResponse;
import software.amazon.awssdk.services.ssm.model.SsmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class CreateOpsItem {
    public static void main(String[] args) {

        final String USAGE = """

                Usage:
                    <title> <source> <category> <severity>

                Where:
                    title - The OpsItem title.
                    source - The origin of the OpsItem, such as Amazon EC2 or AWS
 Systems Manager.
                    category - A category to assign to an OpsItem.
                    severity - A severity to assign to an OpsItem.
                """;

        if (args.length != 4) {
```

```
            System.out.println(USAGE);
            System.exit(1);
        }

        String title = args[0];
        String source = args[1];
        String category = args[2];
        String severity = args[3];

        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        System.out
                .println("The Id of the OpsItem is " + createNewOpsItem(ssmClient,
title, source, category, severity));
        ssmClient.close();
    }

    public static String createNewOpsItem(SsmClient ssmClient,
            String title,
            String source,
            String category,
            String severity) {

        try {
            CreateOpsItemRequest opsItemRequest = CreateOpsItemRequest.builder()
                    .description("Created by the SSM Java API")
                    .title(title)
                    .source(source)
                    .category(category)
                    .severity(severity)
                    .build();

            CreateOpsItemResponse itemResponse =
ssmClient.createOpsItem(opsItemRequest);
            return itemResponse.opsItemId();

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        return "";
```

```
    }
}
```

- Para obter detalhes da API, consulte CreateOpsItema Referência AWS SDK for Java 2.x da API.

Descreva um OpsItem

O exemplo de código a seguir mostra como descrever um OpsItem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.DescribeOpsItemsRequest;
import software.amazon.awssdk.services.ssm.model.DescribeOpsItemsResponse;
import software.amazon.awssdk.services.ssm.model.OpsItemSummary;
import software.amazon.awssdk.services.ssm.model.SsmException;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DescribeOpsItems {

    public static void main(String[] args) {
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();
```

```
        describeItems(ssmClient);
        ssmClient.close();
    }

    public static void describeItems(SsmClient ssmClient) {
        try {
            DescribeOpsItemsRequest itemsRequest = DescribeOpsItemsRequest.builder()
                    .maxResults(10)
                    .build();

            DescribeOpsItemsResponse itemsResponse =
 ssmClient.describeOpsItems(itemsRequest);
            List<OpsItemSummary> items = itemsResponse.opsItemSummaries();
            for (OpsItemSummary item : items) {
                System.out.println("The item title is " + item.title());
            }

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeOpsItemsa Referência AWS SDK for Java 2.x da API.

Obter informações de parâmetros

O exemplo de código a seguir mostra como obter informações de parâmetros do Systems Manager.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
```

```
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.GetParameterRequest;
import software.amazon.awssdk.services.ssm.model.GetParameterResponse;
import software.amazon.awssdk.services.ssm.model.SsmException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class GetParameter {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <paraName>

                Where:
                    paraName - The name of the parameter.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String paraName = args[0];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();

        getParaValue(ssmClient, paraName);
        ssmClient.close();
    }

    public static void getParaValue(SsmClient ssmClient, String paraName) {
        try {
            GetParameterRequest parameterRequest = GetParameterRequest.builder()
                    .name(paraName)
                    .build();
```

```
            GetParameterResponse parameterResponse =
 ssmClient.getParameter(parameterRequest);
            System.out.println("The parameter value is " +
 parameterResponse.parameter().value());

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeParametersa Referência AWS SDK for Java 2.x da API.

Atualiza e OpsItem

O exemplo de código a seguir mostra como atualizar um OpsItem.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.ssm.SsmClient;
import software.amazon.awssdk.services.ssm.model.SsmException;
import software.amazon.awssdk.services.ssm.model.UpdateOpsItemRequest;
import software.amazon.awssdk.services.ssm.model.OpsItemStatus;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
```

```
 */
public class ResolveOpsItem {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <opsID>

                Where:
                    opsID - The Ops item ID value.
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String opsID = args[0];
        Region region = Region.US_EAST_1;
        SsmClient ssmClient = SsmClient.builder()
                .region(region)
                .build();
        setOpsItemStatus(ssmClient, opsID);
    }

    public static void setOpsItemStatus(SsmClient ssmClient, String opsID) {
        try {
            UpdateOpsItemRequest opsItemRequest = UpdateOpsItemRequest.builder()
                    .opsItemId(opsID)
                    .status(OpsItemStatus.RESOLVED)
                    .build();

            ssmClient.updateOpsItem(opsItemRequest);

        } catch (SsmException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte UpdateOpsItema Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Textract usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Textract.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Analisar um documento

O exemplo de código a seguir mostra como analisar um documento usando o Amazon Textract.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.AnalyzeDocumentRequest;
import software.amazon.awssdk.services.textract.model.Document;
```

```
import software.amazon.awssdk.services.textract.model.FeatureType;
import software.amazon.awssdk.services.textract.model.AnalyzeDocumentResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.TextractException;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.ArrayList;
import java.util.Iterator;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class AnalyzeDocument {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <sourceDoc>\s

                Where:
                    sourceDoc - The path where the document is located (must be an
 image, for example, C:/AWS/book.png).\s
                """;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String sourceDoc = args[0];
        Region region = Region.US_EAST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        analyzeDoc(textractClient, sourceDoc);
```

```
        textractClient.close();
    }

    public static void analyzeDoc(TextractClient textractClient, String sourceDoc) {
        try {
            InputStream sourceStream = new FileInputStream(new File(sourceDoc));
            SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

            // Get the input Document object as bytes
            Document myDoc = Document.builder()
                    .bytes(sourceBytes)
                    .build();

            List<FeatureType> featureTypes = new ArrayList<FeatureType>();
            featureTypes.add(FeatureType.FORMS);
            featureTypes.add(FeatureType.TABLES);

            AnalyzeDocumentRequest analyzeDocumentRequest =
 AnalyzeDocumentRequest.builder()
                    .featureTypes(featureTypes)
                    .document(myDoc)
                    .build();

            AnalyzeDocumentResponse analyzeDocument =
 textractClient.analyzeDocument(analyzeDocumentRequest);
            List<Block> docInfo = analyzeDocument.blocks();
            Iterator<Block> blockIterator = docInfo.iterator();

            while (blockIterator.hasNext()) {
                Block block = blockIterator.next();
                System.out.println("The block type is " +
 block.blockType().toString());
            }

        } catch (TextractException | FileNotFoundException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte AnalyzeDocumenta Referência AWS SDK for Java 2.x da API.

Detectar texto em um documento

O exemplo de código a seguir mostra como detectar texto em um documento usando o Amazon Textract.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Detectar texto de um documento de entrada.

```
import software.amazon.awssdk.core.SdkBytes;
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.Document;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextRequest;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.DocumentMetadata;
import software.amazon.awssdk.services.textract.model.TextractException;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileNotFoundException;
import java.io.InputStream;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectDocumentText {
```

```
   public static void main(String[] args) {
       final String usage = """

               Usage:
                   <sourceDoc>\s

               Where:
                   sourceDoc - The path where the document is located (must be an
image, for example, C:/AWS/book.png).\s
               """;

       if (args.length != 1) {
           System.out.println(usage);
           System.exit(1);
       }

       String sourceDoc = args[0];
       Region region = Region.US_EAST_2;
       TextractClient textractClient = TextractClient.builder()
               .region(region)
               .build();

       detectDocText(textractClient, sourceDoc);
       textractClient.close();
   }

   public static void detectDocText(TextractClient textractClient, String
sourceDoc) {
       try {
           InputStream sourceStream = new FileInputStream(new File(sourceDoc));
           SdkBytes sourceBytes = SdkBytes.fromInputStream(sourceStream);

           // Get the input Document object as bytes.
           Document myDoc = Document.builder()
                   .bytes(sourceBytes)
                   .build();

           DetectDocumentTextRequest detectDocumentTextRequest =
DetectDocumentTextRequest.builder()
                   .document(myDoc)
                   .build();

           // Invoke the Detect operation.
```

```
            DetectDocumentTextResponse textResponse =
 textractClient.detectDocumentText(detectDocumentTextRequest);
            List<Block> docInfo = textResponse.blocks();
            for (Block block : docInfo) {
                System.out.println("The block type is " +
 block.blockType().toString());
            }

            DocumentMetadata documentMetadata = textResponse.documentMetadata();
            System.out.println("The number of pages in the document is " +
 documentMetadata.pages());

        } catch (TextractException | FileNotFoundException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

Detectar texto de um documento localizado em um bucket do Amazon S3.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.model.S3Object;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.Document;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextRequest;
import software.amazon.awssdk.services.textract.model.DetectDocumentTextResponse;
import software.amazon.awssdk.services.textract.model.Block;
import software.amazon.awssdk.services.textract.model.DocumentMetadata;
import software.amazon.awssdk.services.textract.model.TextractException;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class DetectDocumentTextS3 {
```

```
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <docName>\s

                Where:
                    bucketName - The name of the Amazon S3 bucket that contains the
 document.\s

                    docName - The document name (must be an image, i.e., book.png).
\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String docName = args[1];
        Region region = Region.US_WEST_2;
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        detectDocTextS3(textractClient, bucketName, docName);
        textractClient.close();
    }

    public static void detectDocTextS3(TextractClient textractClient, String
 bucketName, String docName) {
        try {
            S3Object s3Object = S3Object.builder()
                    .bucket(bucketName)
                    .name(docName)
                    .build();

            // Create a Document object and reference the s3Object instance.
            Document myDoc = Document.builder()
                    .s3Object(s3Object)
                    .build();
```

```
            DetectDocumentTextRequest detectDocumentTextRequest =
 DetectDocumentTextRequest.builder()
                    .document(myDoc)
                    .build();

            DetectDocumentTextResponse textResponse =
 textractClient.detectDocumentText(detectDocumentTextRequest);
            for (Block block : textResponse.blocks()) {
                System.out.println("The block type is " +
 block.blockType().toString());
            }

            DocumentMetadata documentMetadata = textResponse.documentMetadata();
            System.out.println("The number of pages in the document is " +
 documentMetadata.pages());

        } catch (TextractException e) {

            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}
```

- Para obter detalhes da API, consulte DetectDocumentTexta Referência AWS SDK for Java 2.x da API.

Iniciar análise assíncrona de um documento

O exemplo de código a seguir mostra como iniciar uma análise assíncrona de um documento usando o Amazon Textract.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import software.amazon.awssdk.regions.Region;
import software.amazon.awssdk.services.textract.model.S3Object;
import software.amazon.awssdk.services.textract.TextractClient;
import software.amazon.awssdk.services.textract.model.StartDocumentAnalysisRequest;
import software.amazon.awssdk.services.textract.model.DocumentLocation;
import software.amazon.awssdk.services.textract.model.TextractException;
import software.amazon.awssdk.services.textract.model.StartDocumentAnalysisResponse;
import software.amazon.awssdk.services.textract.model.GetDocumentAnalysisRequest;
import software.amazon.awssdk.services.textract.model.GetDocumentAnalysisResponse;
import software.amazon.awssdk.services.textract.model.FeatureType;
import java.util.ArrayList;
import java.util.List;

/**
 * Before running this Java V2 code example, set up your development
 * environment, including your credentials.
 *
 * For more information, see the following documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */
public class StartDocumentAnalysis {
    public static void main(String[] args) {
        final String usage = """

                Usage:
                    <bucketName> <docName>\s

                Where:
                    bucketName - The name of the Amazon S3 bucket that contains the
 document.\s
                    docName - The document name (must be an image, for example,
 book.png).\s
                """;

        if (args.length != 2) {
            System.out.println(usage);
            System.exit(1);
        }

        String bucketName = args[0];
        String docName = args[1];
        Region region = Region.US_WEST_2;
```

```
        TextractClient textractClient = TextractClient.builder()
                .region(region)
                .build();

        String jobId = startDocAnalysisS3(textractClient, bucketName, docName);
        System.out.println("Getting results for job " + jobId);
        String status = getJobResults(textractClient, jobId);
        System.out.println("The job status is " + status);
        textractClient.close();
    }

    public static String startDocAnalysisS3(TextractClient textractClient, String
bucketName, String docName) {
        try {
            List<FeatureType> myList = new ArrayList<>();
            myList.add(FeatureType.TABLES);
            myList.add(FeatureType.FORMS);

            S3Object s3Object = S3Object.builder()
                    .bucket(bucketName)
                    .name(docName)
                    .build();

            DocumentLocation location = DocumentLocation.builder()
                    .s3Object(s3Object)
                    .build();

            StartDocumentAnalysisRequest documentAnalysisRequest =
StartDocumentAnalysisRequest.builder()
                    .documentLocation(location)
                    .featureTypes(myList)
                    .build();

            StartDocumentAnalysisResponse response =
textractClient.startDocumentAnalysis(documentAnalysisRequest);

            // Get the job ID
            String jobId = response.jobId();
            return jobId;

        } catch (TextractException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
```

```
        return "";
    }

    private static String getJobResults(TextractClient textractClient, String jobId)
 {
        boolean finished = false;
        int index = 0;
        String status = "";

        try {
            while (!finished) {
                GetDocumentAnalysisRequest analysisRequest =
 GetDocumentAnalysisRequest.builder()
                        .jobId(jobId)
                        .maxResults(1000)
                        .build();

                GetDocumentAnalysisResponse response =
 textractClient.getDocumentAnalysis(analysisRequest);
                status = response.jobStatus().toString();

                if (status.compareTo("SUCCEEDED") == 0)
                    finished = true;
                else {
                    System.out.println(index + " status is: " + status);
                    Thread.sleep(1000);
                }
                index++;
            }

            return status;

        } catch (InterruptedException e) {
            System.out.println(e.getMessage());
            System.exit(1);
        }
        return "";
    }
}
```

- Para obter detalhes da API, consulte StartDocumentAnalysisa Referência AWS SDK for Java 2.x da API.

Exemplos do Amazon Transcribe usando o SDK para Java 2.x

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Java 2.x com o Amazon Transcribe.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Listar trabalhos de transcrição

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class ListTranscriptionJobs {
    public static void main(String[] args) {
        TranscribeClient transcribeClient = TranscribeClient.builder()
            .region(Region.US_EAST_1)
            .build();
```

```
            listTranscriptionJobs(transcribeClient);
        }

        public static void listTranscriptionJobs(TranscribeClient transcribeClient)
{
            ListTranscriptionJobsRequest listJobsRequest =
ListTranscriptionJobsRequest.builder()
                .build();


transcribeClient.listTranscriptionJobsPaginator(listJobsRequest).stream()
                .flatMap(response -> response.transcriptionJobSummaries().stream())
                .forEach(jobSummary -> {
                    System.out.println("Job Name: " +
jobSummary.transcriptionJobName());
                    System.out.println("Job Status: " +
jobSummary.transcriptionJobStatus());
                    System.out.println("Output Location: " +
jobSummary.outputLocationType());
                    // Add more information as needed

                    // Retrieve additional details for the job if necessary
                    GetTranscriptionJobResponse jobDetails =
transcribeClient.getTranscriptionJob(
                        GetTranscriptionJobRequest.builder()
                            .transcriptionJobName(jobSummary.transcriptionJobName())
                            .build());

                    // Display additional details
                    System.out.println("Language Code: " +
jobDetails.transcriptionJob().languageCode());
                    System.out.println("Media Format: " +
jobDetails.transcriptionJob().mediaFormat());
                    // Add more details as needed

                    System.out.println("--------------");
                });
        }
    }
```

- Para obter detalhes da API, consulte ListTranscriptionJobsa Referência AWS SDK for Java 2.x da API.

Iniciar um trabalho de transcrição

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public class TranscribeStreamingDemoApp {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[])
            throws URISyntaxException, ExecutionException, InterruptedException,
 LineUnavailableException {

        client = TranscribeStreamingAsyncClient.builder()
                .credentialsProvider(getCredentials())
                .region(REGION)
                .build();

        CompletableFuture<Void> result =
 client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromMic()),
                getResponseHandler());

        result.get();
        client.close();
    }

    private static InputStream getStreamFromMic() throws LineUnavailableException {

        // Signed PCM AudioFormat with 16kHz, 16 bit sample size, mono
        int sampleRate = 16000;
        AudioFormat format = new AudioFormat(sampleRate, 16, 1, true, false);
        DataLine.Info info = new DataLine.Info(TargetDataLine.class, format);

        if (!AudioSystem.isLineSupported(info)) {
            System.out.println("Line not supported");
```

```
            System.exit(0);
        }

        TargetDataLine line = (TargetDataLine) AudioSystem.getLine(info);
        line.open(format);
        line.start();

        InputStream audioStream = new AudioInputStream(line);
        return audioStream;
    }

    private static AwsCredentialsProvider getCredentials() {
        return DefaultCredentialsProvider.create();
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
 mediaSampleRateHertz) {
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US.toString())
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
                    System.out.println("=== All records stream successfully ===");
                })
                .subscriber(event -> {
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {
```

```
System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private InputStream getStreamFromFile(String audioFileName) {
        try {
            File inputFile = new
File(getClass().getClassLoader().getResource(audioFileName).getFile());
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }

        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
```

```
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);

        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream inputStream)
{
            this.subscriber = s;
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
positive"));
            }

            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
```

```
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];

            int len = 0;
            try {
                len = inputStream.read(audioBytes);

                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

- Para obter detalhes da API, consulte StartTranscriptionJoba Referência AWS SDK for Java 2.x da API.

Cenários

Transcrever áudio e obter dados do trabalho

O código de exemplo a seguir mostra como:

- Inicie um trabalho de transcrição com o Amazon Transcribe.
- Aguarde a conclusão do trabalho .
- Obtenha a URI em que a transcrição está armazenada.

Para obter mais informações, consulte Começar a usar o Amazon Transcribe.

SDK para Java 2.x

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Transcreve um arquivo PCM.

```
/**
 * To run this AWS code example, ensure that you have set up your development
 * environment, including your AWS credentials.
 *
 * For information, see this documentation topic:
 *
 * https://docs.aws.amazon.com/sdk-for-java/latest/developer-guide/get-started.html
 */

public class TranscribeStreamingDemoFile {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[]) throws ExecutionException,
 InterruptedException {

        final String USAGE = "\n" +
                "Usage:\n" +
                "    <file> \n\n" +
                "Where:\n" +
                "    file - the location of a PCM file to transcribe. In this
 example, ensure the PCM file is 16 hertz (Hz). \n";

        if (args.length != 1) {
            System.out.println(USAGE);
            System.exit(1);
        }

        String file = args[0];
        client = TranscribeStreamingAsyncClient.builder()
                .region(REGION)
                .build();
```

```
        CompletableFuture<Void> result =
client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromFile(file)),
                getResponseHandler());

        result.get();
        client.close();
    }

    private static InputStream getStreamFromFile(String file) {
        try {
            File inputFile = new File(file);
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;

        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
mediaSampleRateHertz) {
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US)
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
                    System.out.println("=== All records stream successfully ===");
                })
                .subscriber(event -> {
```

```
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {

 System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }

        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);

        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream inputStream)
 {
            this.subscriber = s;
```

```
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
positive"));
            }

            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];

            int len = 0;
            try {
                len = inputStream.read(audioBytes);
```

```
                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

Transcreve o streaming de áudio do microfone do computador.

```
public class TranscribeStreamingDemoApp {
    private static final Region REGION = Region.US_EAST_1;
    private static TranscribeStreamingAsyncClient client;

    public static void main(String args[])
            throws URISyntaxException, ExecutionException, InterruptedException,
 LineUnavailableException {

        client = TranscribeStreamingAsyncClient.builder()
                .credentialsProvider(getCredentials())
                .region(REGION)
                .build();

        CompletableFuture<Void> result =
 client.startStreamTranscription(getRequest(16_000),
                new AudioStreamPublisher(getStreamFromMic()),
                getResponseHandler());

        result.get();
        client.close();
```

```
    }

    private static InputStream getStreamFromMic() throws LineUnavailableException {

        // Signed PCM AudioFormat with 16kHz, 16 bit sample size, mono
        int sampleRate = 16000;
        AudioFormat format = new AudioFormat(sampleRate, 16, 1, true, false);
        DataLine.Info info = new DataLine.Info(TargetDataLine.class, format);

        if (!AudioSystem.isLineSupported(info)) {
            System.out.println("Line not supported");
            System.exit(0);
        }

        TargetDataLine line = (TargetDataLine) AudioSystem.getLine(info);
        line.open(format);
        line.start();

        InputStream audioStream = new AudioInputStream(line);
        return audioStream;
    }

    private static AwsCredentialsProvider getCredentials() {
        return DefaultCredentialsProvider.create();
    }

    private static StartStreamTranscriptionRequest getRequest(Integer
 mediaSampleRateHertz) {
        return StartStreamTranscriptionRequest.builder()
                .languageCode(LanguageCode.EN_US.toString())
                .mediaEncoding(MediaEncoding.PCM)
                .mediaSampleRateHertz(mediaSampleRateHertz)
                .build();
    }

    private static StartStreamTranscriptionResponseHandler getResponseHandler() {
        return StartStreamTranscriptionResponseHandler.builder()
                .onResponse(r -> {
                    System.out.println("Received Initial response");
                })
                .onError(e -> {
                    System.out.println(e.getMessage());
                    StringWriter sw = new StringWriter();
                    e.printStackTrace(new PrintWriter(sw));
```

```
                    System.out.println("Error Occurred: " + sw.toString());
                })
                .onComplete(() -> {
                    System.out.println("=== All records stream successfully ===");
                })
                .subscriber(event -> {
                    List<Result> results = ((TranscriptEvent)
 event).transcript().results();
                    if (results.size() > 0) {
                        if (!
results.get(0).alternatives().get(0).transcript().isEmpty()) {

 System.out.println(results.get(0).alternatives().get(0).transcript());
                        }
                    }
                })
                .build();
    }

    private InputStream getStreamFromFile(String audioFileName) {
        try {
            File inputFile = new
 File(getClass().getClassLoader().getResource(audioFileName).getFile());
            InputStream audioStream = new FileInputStream(inputFile);
            return audioStream;
        } catch (FileNotFoundException e) {
            throw new RuntimeException(e);
        }
    }

    private static class AudioStreamPublisher implements Publisher<AudioStream> {
        private final InputStream inputStream;
        private static Subscription currentSubscription;

        private AudioStreamPublisher(InputStream inputStream) {
            this.inputStream = inputStream;
        }

        @Override
        public void subscribe(Subscriber<? super AudioStream> s) {

            if (this.currentSubscription == null) {
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            } else {
```

```
                this.currentSubscription.cancel();
                this.currentSubscription = new SubscriptionImpl(s, inputStream);
            }
            s.onSubscribe(currentSubscription);
        }
    }

    public static class SubscriptionImpl implements Subscription {
        private static final int CHUNK_SIZE_IN_BYTES = 1024 * 1;
        private final Subscriber<? super AudioStream> subscriber;
        private final InputStream inputStream;
        private ExecutorService executor = Executors.newFixedThreadPool(1);
        private AtomicLong demand = new AtomicLong(0);

        SubscriptionImpl(Subscriber<? super AudioStream> s, InputStream inputStream)
{
            this.subscriber = s;
            this.inputStream = inputStream;
        }

        @Override
        public void request(long n) {
            if (n <= 0) {
                subscriber.onError(new IllegalArgumentException("Demand must be
positive"));
            }

            demand.getAndAdd(n);

            executor.submit(() -> {
                try {
                    do {
                        ByteBuffer audioBuffer = getNextEvent();
                        if (audioBuffer.remaining() > 0) {
                            AudioEvent audioEvent =
audioEventFromBuffer(audioBuffer);
                            subscriber.onNext(audioEvent);
                        } else {
                            subscriber.onComplete();
                            break;
                        }
                    } while (demand.decrementAndGet() > 0);
                } catch (Exception e) {
                    subscriber.onError(e);
```

```
                }
            });
        }

        @Override
        public void cancel() {
            executor.shutdown();
        }

        private ByteBuffer getNextEvent() {
            ByteBuffer audioBuffer = null;
            byte[] audioBytes = new byte[CHUNK_SIZE_IN_BYTES];

            int len = 0;
            try {
                len = inputStream.read(audioBytes);

                if (len <= 0) {
                    audioBuffer = ByteBuffer.allocate(0);
                } else {
                    audioBuffer = ByteBuffer.wrap(audioBytes, 0, len);
                }
            } catch (IOException e) {
                throw new UncheckedIOException(e);
            }

            return audioBuffer;
        }

        private AudioEvent audioEventFromBuffer(ByteBuffer bb) {
            return AudioEvent.builder()
                    .audioChunk(SdkBytes.fromByteBuffer(bb))
                    .build();
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Java 2.x.
  - GetTranscriptionJob
  - StartTranscriptionJob

Exemplos de serviço cruzado usando o SDK para Java 2.x

Os aplicativos de exemplo a seguir usam o AWS SDK for Java 2.x para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma aplicação para enviar dados para uma tabela do DynamoDB
- Criar um chatbot Amazon Lex para engajar os visitantes do site
- Criar uma aplicação de publicação e assinatura que traduz mensagens
- Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Criar um rastreador de itens do Amazon Redshift
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor
- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio
- Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK
- Usar o API Gateway para invocar uma função do Lambda
- Usar Step Functions para invocar funções do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma aplicação para enviar dados para uma tabela do DynamoDB

SDK para Java 2.x

Mostra como criar uma aplicação Web dinâmica que envia dados usando a API Java do Amazon DynamoDB e envia uma mensagem de texto usando a API Java do Amazon Simple Notification Service.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SNS

Criar um chatbot Amazon Lex para engajar os visitantes do site

SDK para Java 2.x

Mostra como usar a API do Amazon Lex para criar um Chatbot em um aplicativo da web para engajar os visitantes do seu site.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon Lex
- Amazon Translate

Criar uma aplicação de publicação e assinatura que traduz mensagens

SDK para Java 2.x

Mostra como usar a API Java do Amazon Simple Notification Service para criar uma aplicação Web com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para obter o código-fonte completo e instruções sobre como configurar e executar o exemplo que usa a API Java Async, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS

- Amazon Translate

Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS

SDK para Java 2.x

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK para Java 2.x

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3

- Amazon SNS

Criar uma aplicação Web para monitorar dados do DynamoDB

SDK para Java 2.x

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Criar um rastreador de itens do Amazon Redshift

SDK para Java 2.x

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK para Java 2.x

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Para obter o código-fonte completo e instruções sobre como configurar e executar um exemplo que usa a API JDBC, consulte o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

SDK para Java 2.x

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly

- Amazon Textract
- Amazon Translate

Detectar EPI em imagens com o Amazon Rekognition usando um AWS SDK

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda que detecta imagens com equipamento de proteção individual.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

SDK para Java 2.x

Mostra como usar a API Java do Amazon Rekognition a fim de construir uma aplicação para detectar faces e objetos em vídeos localizados em um bucket do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

SDK para Java 2.x

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Usar o API Gateway para invocar uma função do Lambda

SDK para Java 2.x

Mostra como criar uma função do AWS Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma função do Lambda chamada pelo Amazon API Gateway que verifica uma tabela do Amazon DynamoDB em busca de aniversários de trabalho e usa o Amazon Simple Notification Service (Amazon SNS) para enviar uma mensagem de texto aos seus funcionários que os parabeniza em sua data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

Usar Step Functions para invocar funções do Lambda

SDK para Java 2.x

Mostra como criar um AWS fluxo de trabalho sem servidor usando o AWS Step Functions e o AWS SDK for Java 2.x. Cada etapa do fluxo de trabalho é implementada usando uma função do AWS Lambda.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

Usar eventos programados para chamar uma função do Lambda

SDK para Java 2.x

Mostra como criar um evento EventBridge programado pela Amazon que invoca uma AWS Lambda função. Configure EventBridge para usar uma expressão cron para agendar quando a função Lambda é invocada. Neste exemplo, você cria uma função do Lambda usando a API de runtime de Java do Lambda. Este exemplo invoca diferentes serviços da AWS para lidar com um caso de uso específico. Este exemplo demonstra como criar uma aplicação que envia uma mensagem de texto móvel para seus funcionários que os parabeniza na data de aniversário de um ano.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

Exemplos de código para SDK para Kotlin

Os exemplos de código a seguir mostram como usar o AWS SDK para Kotlin com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do Desenvolvedor do SDK para Kotlin : Saiba mais sobre como usar o Kotlin com AWS.

- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Kotlin
- Exemplos de serviços cruzados usando SDK para Kotlin

Ações e cenários usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de Aurora usando o SDK para Kotlin
- Exemplos de Auto Scaling usando o SDK para Kotlin
- Exemplos do Amazon Bedrock usando o SDK para Kotlin
- CloudWatch exemplos usando SDK para Kotlin
- CloudWatch Exemplos de registros usando o SDK para Kotlin
- Exemplos de código do Provedor de Identidade do Amazon Cognito usando SDK para Kotlin
- Exemplos do DynamoDB usando o SDK para Kotlin
- Exemplos do Amazon EC2 usando o SDK para Kotlin
- OpenSearch Exemplos de serviços usando o SDK para Kotlin
- EventBridge exemplos usando SDK para Kotlin
- Exemplos de AWS Glue usando o SDK para Kotlin
- Exemplos de IAM usando SDK para Kotlin

- Exemplos do Amazon Keyspaces usando o SDK para Kotlin
- Exemplos de AWS KMS usando o SDK para Kotlin
- Exemplos de Lambda usando o SDK para Kotlin
- MediaConvert exemplos usando SDK para Kotlin
- Exemplos do Amazon Pinpoint usando o SDK para Kotlin
- Exemplos do Amazon RDS usando o SDK para Kotlin
- Exemplos do Amazon Redshift usando o SDK para Kotlin
- Exemplos do Amazon Rekognition usando o SDK para Kotlin
- Exemplos de registro de domínio Route 53 usando SDKs para Kotlin
- Exemplos do Amazon S3 usando SDK para Kotlin
- SageMaker exemplos usando SDK para Kotlin
- Exemplos de Secrets Manager usando SDK para Kotlin
- Exemplos do Amazon SNS usando SDK para Kotlin
- Exemplos do Amazon SQS usando SDK para Kotlin
- Exemplos do Step Functions usando o SDK para Kotlin
- Exemplos de AWS Support usando o SDK para Kotlin

Exemplos de Aurora usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

- Cenários

Ações

Criar um cluster de banco de dados

Os exemplos de código a seguir mostram como criar um cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBCluster(dbParameterGroupFamilyVal: String?, dbName: String?,
 dbClusterIdentifierVal: String?, userName: String?, password: String?): String? {
    val clusterRequest = CreateDbClusterRequest {
        databaseName = dbName
        dbClusterIdentifier = dbClusterIdentifierVal
        dbClusterParameterGroupName = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
        masterUsername = userName
        masterUserPassword = password
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbCluster(clusterRequest)
        return response.dbCluster?.dbClusterArn
    }
}
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK para Kotlin.

Criar um parameter group de cluster de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBClusterParameterGroup(dbClusterGroupNameVal: String?,
 dbParameterGroupFamilyVal: String?) {
    val groupRequest = CreateDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dbClusterGroupNameVal
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterParameterGroup(groupRequest)
        println("The group name is
 ${response.dbClusterParameterGroup?.dbClusterParameterGroupName}")
    }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na referência da API AWSSDK for Kotlin.

Criar um snapshot de cluster de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBClusterSnapshot(dbInstanceClusterIdentifier: String?,
 dbSnapshotIdentifier: String?) {
    val snapshotRequest = CreateDbClusterSnapshotRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterSnapshot(snapshotRequest)
        println("The Snapshot ARN is
 ${response.dbClusterSnapshot?.dbClusterSnapshotArn}")
    }
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na referência da API AWSSDK for Kotlin.

Criar uma instância de banco de dados em um cluster de banco de dados

Os exemplos de código a seguir mostram como criar uma instância DB em cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDBInstanceCluster(dbInstanceIdentifierVal: String?,
 dbInstanceClusterIdentifierVal: String?, instanceClassVal: String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbClusterIdentifier = dbInstanceClusterIdentifierVal
        engine = "aurora-mysql"
        dbInstanceClass = instanceClassVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
```

```
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Kotlin.

Excluir um cluster de banco de dados

O exemplo de código a seguir mostra como excluir um cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteCluster(dbInstanceClusterIdentifier: String) {
    val deleteDbClusterRequest = DeleteDbClusterRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        rdsClient.deleteDbCluster(deleteDbClusterRequest)
        println("$dbInstanceClusterIdentifier was deleted!")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK para Kotlin.

Excluir um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
@Throws(InterruptedException::class)
suspend fun deleteDBClusterGroup(dbClusterGroupName: String, clusterDBARN: String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
            isDataDel = false
            didFind = false
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(clusterDBARN) == 0) {
                        println("$clusterDBARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database ARN.
                        isDataDel = true
                    }
                    delay(slTime * 1000)
                    index++
```

```
                }
            }
        }
        val clusterParameterGroupRequest = DeleteDbClusterParameterGroupRequest {
            dbClusterParameterGroupName = dbClusterGroupName
        }

        rdsClient.deleteDbClusterParameterGroup(clusterParameterGroupRequest)
        println("$dbClusterGroupName was deleted.")
    }
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup no AWSSDK para referência da API Kotlin.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDBInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Kotlin.

Descrever os grupos de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever grupos de parâmetros de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameterGroups(dbClusterGroupName: String?) {
    val groupsRequest = DescribeDbClusterParameterGroupsRequest {
        dbClusterParameterGroupName = dbClusterGroupName
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbClusterParameterGroups(groupsRequest)
        response.dbClusterParameterGroups?.forEach { group ->
            println("The group name is ${group.dbClusterParameterGroupName}")
            println("The group ARN is ${group.dbClusterParameterGroupArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups na referência da API AWSSDK for Kotlin.

Descrever snapshots de cluster de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitSnapshotReady(dbSnapshotIdentifier: String?,
 dbInstanceClusterIdentifier: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbClusterSnapshotsRequest {
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
        dbClusterIdentifier = dbInstanceClusterIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!snapshotReady) {
            val response = rdsClient.describeDbClusterSnapshots(snapshotsRequest)
            val snapshotList = response.dbClusterSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
                    } else {
                        println(".")
                        delay(slTime * 5000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots na referência da API AWSSDK for Kotlin.

Descrever clusters de banco de dados

Os exemplos de código a seguir mostram como descrever clusters do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
```

```
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK para Kotlin.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitDBAuroraInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")
    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    var endpoint = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            response.dbInstances?.forEach { instance ->
                instanceReadyStr = instance.dbInstanceStatus.toString()
                if (instanceReadyStr.contains("available")) {
                    endpoint = instance.endpoint?.address.toString()
                    instanceReady = true
                } else {
                    print(".")
                    delay(sleepTime * 1000)
                }
            }
```

```
        }
    }
    println("Database instance is available! The connection endpoint is $endpoint")
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Kotlin.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Aurora.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get a list of allowed engine versions.
suspend fun getAllowedClusterEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        response.dbEngineVersions?.forEach { dbEngine ->
            println("The engine version is ${dbEngine.engineVersion}")
            println("The engine description is ${dbEngine.dbEngineDescription}")
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na referência da API AWSSDK for Kotlin.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
```

```
                }
            }
        }
    }
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na referência da API AWSSDK for Kotlin.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Modify the auto_increment_offset parameter.
suspend fun modifyDBClusterParas(dClusterGroupName: String?) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.fromValue("immediate")
        parameterValue = "5"
    }

    val paraList = ArrayList<Parameter>()
    paraList.add(parameter1)
    val groupRequest = ModifyDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dClusterGroupName
        parameters = paraList
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbClusterParameterGroup(groupRequest)
```

```
        println("The parameter group ${response.dbClusterParameterGroupName} was
 successfully modified")
    }
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na referência da API AWSSDK for Kotlin.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
 including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

This example requires an AWS Secrets Manager secret that contains the database
 credentials. If you do not create a
```

```
secret, this example will not work. For more details, see:

https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html

This Kotlin example performs the following tasks:

1. Returns a list of the available DB engines.
2. Creates a custom DB parameter group.
3. Gets the parameter groups.
4. Gets the parameters in the group.
5. Modifies the auto_increment_increment parameter.
6. Displays the updated parameter value.
7. Gets a list of allowed engine versions.
8. Creates an Aurora DB cluster database.
9. Waits for DB instance to be ready.
10. Gets a list of instance classes available for the selected engine.
11. Creates a database instance in the cluster.
12. Waits for the database instance in the cluster to be ready.
13. Creates a snapshot.
14. Waits for DB snapshot to be ready.
15. Deletes the DB instance.
16. Deletes the DB cluster.
17. Deletes the DB cluster group.
 */

var slTime: Long = 20
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <dbClusterGroupName> <dbParameterGroupFamily>
 <dbInstanceClusterIdentifier> <dbName> <dbSnapshotIdentifier> <secretName>
        Where:
            dbClusterGroupName - The database group name.
            dbParameterGroupFamily - The database parameter group name.
            dbInstanceClusterIdentifier - The database instance identifier.
            dbName -  The database name.
            dbSnapshotIdentifier - The snapshot identifier.
            secretName - The name of the AWS Secrets Manager secret that contains
 the database credentials.
    """

    if (args.size != 7) {
        println(usage)
```

```
        exitProcess(1)
    }

    val dbClusterGroupName = args[0]
    val dbParameterGroupFamily = args[1]
    val dbInstanceClusterIdentifier = args[2]
    val dbInstanceIdentifier = args[3]
    val dbName = args[4]
    val dbSnapshotIdentifier = args[5]
    val secretName = args[6]

    val gson = Gson()
    val user = gson.fromJson(getSecretValues(secretName).toString(),
User::class.java)
    val username = user.username
    val userPassword = user.password

    println("1. Return a list of the available DB engines")
    describeAuroraDBEngines()

    println("2. Create a custom parameter group")
    createDBClusterParameterGroup(dbClusterGroupName, dbParameterGroupFamily)

    println("3. Get the parameter group")
    describeDbClusterParameterGroups(dbClusterGroupName)

    println("4. Get the parameters in the group")
    describeDbClusterParameters(dbClusterGroupName, 0)

    println("5. Modify the auto_increment_offset parameter")
    modifyDBClusterParas(dbClusterGroupName)

    println("6. Display the updated parameter value")
    describeDbClusterParameters(dbClusterGroupName, -1)

    println("7. Get a list of allowed engine versions")
    getAllowedClusterEngines(dbParameterGroupFamily)

    println("8. Create an Aurora DB cluster database")
    val arnClusterVal = createDBCluster(dbClusterGroupName, dbName,
dbInstanceClusterIdentifier, username, userPassword)
    println("The ARN of the cluster is $arnClusterVal")

    println("9. Wait for DB instance to be ready")
```

```
    waitForClusterInstanceReady(dbInstanceClusterIdentifier)

    println("10. Get a list of instance classes available for the selected engine")
    val instanceClass = getListInstanceClasses()

    println("11. Create a database instance in the cluster.")
    val clusterDBARN = createDBInstanceCluster(dbInstanceIdentifier,
 dbInstanceClusterIdentifier, instanceClass)
    println("The ARN of the database is $clusterDBARN")

    println("12. Wait for DB instance to be ready")
    waitDBAuroraInstanceReady(dbInstanceIdentifier)

    println("13. Create a snapshot")
    createDBClusterSnapshot(dbInstanceClusterIdentifier, dbSnapshotIdentifier)

    println("14. Wait for DB snapshot to be ready")
    waitSnapshotReady(dbSnapshotIdentifier, dbInstanceClusterIdentifier)

    println("15. Delete the DB instance")
    deleteDBInstance(dbInstanceIdentifier)

    println("16. Delete the DB cluster")
    deleteCluster(dbInstanceClusterIdentifier)

    println("17. Delete the DB cluster group")
    if (clusterDBARN != null) {
        deleteDBClusterGroup(dbClusterGroupName, clusterDBARN)
    }
    println("The Scenario has successfully completed.")
}

@Throws(InterruptedException::class)
suspend fun deleteDBClusterGroup(dbClusterGroupName: String, clusterDBARN: String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
```

```
            isDataDel = false
            didFind = false
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(clusterDBARN) == 0) {
                        println("$clusterDBARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database ARN.
                        isDataDel = true
                    }
                    delay(slTime * 1000)
                    index++
                }
            }
        }
        val clusterParameterGroupRequest = DeleteDbClusterParameterGroupRequest {
            dbClusterParameterGroupName = dbClusterGroupName
        }

        rdsClient.deleteDbClusterParameterGroup(clusterParameterGroupRequest)
        println("$dbClusterGroupName was deleted.")
    }
}

suspend fun deleteCluster(dbInstanceClusterIdentifier: String) {
    val deleteDbClusterRequest = DeleteDbClusterRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        rdsClient.deleteDbCluster(deleteDbClusterRequest)
        println("$dbInstanceClusterIdentifier was deleted!")
    }
}

suspend fun deleteDBInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
```

```
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}

suspend fun waitSnapshotReady(dbSnapshotIdentifier: String?,
 dbInstanceClusterIdentifier: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbClusterSnapshotsRequest {
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
        dbClusterIdentifier = dbInstanceClusterIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!snapshotReady) {
            val response = rdsClient.describeDbClusterSnapshots(snapshotsRequest)
            val snapshotList = response.dbClusterSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
                    } else {
                        println(".")
                        delay(slTime * 5000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}

suspend fun createDBClusterSnapshot(dbInstanceClusterIdentifier: String?,
 dbSnapshotIdentifier: String?) {
```

```
    val snapshotRequest = CreateDbClusterSnapshotRequest {
        dbClusterIdentifier = dbInstanceClusterIdentifier
        dbClusterSnapshotIdentifier = dbSnapshotIdentifier
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterSnapshot(snapshotRequest)
        println("The Snapshot ARN is
 ${response.dbClusterSnapshot?.dbClusterSnapshotArn}")
    }
}

suspend fun waitDBAuroraInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")
    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    var endpoint = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            response.dbInstances?.forEach { instance ->
                instanceReadyStr = instance.dbInstanceStatus.toString()
                if (instanceReadyStr.contains("available")) {
                    endpoint = instance.endpoint?.address.toString()
                    instanceReady = true
                } else {
                    print(".")
                    delay(sleepTime * 1000)
                }
            }
        }
    }
    println("Database instance is available! The connection endpoint is $endpoint")
}

suspend fun createDBInstanceCluster(dbInstanceIdentifierVal: String?,
 dbInstanceClusterIdentifierVal: String?, instanceClassVal: String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbClusterIdentifier = dbInstanceClusterIdentifierVal
```

```
        engine = "aurora-mysql"
        dbInstanceClass = instanceClassVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}

suspend fun getListInstanceClasses(): String {
    val optionsRequest = DescribeOrderableDbInstanceOptionsRequest {
        engine = "aurora-mysql"
        maxRecords = 20
    }
    var instanceClass = ""
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeOrderableDbInstanceOptions(optionsRequest)
        response.orderableDbInstanceOptions?.forEach { instanceOption ->
            instanceClass = instanceOption.dbInstanceClass.toString()
            println("The instance class is ${instanceOption.dbInstanceClass}")
            println("The engine version is ${instanceOption.engineVersion}")
        }
    }
    return instanceClass
}

// Waits until the database instance is available.
suspend fun waitForClusterInstanceReady(dbClusterIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbClustersRequest {
        dbClusterIdentifier = dbClusterIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbClusters(instanceRequest)
            response.dbClusters?.forEach { cluster ->
                instanceReadyStr = cluster.status.toString()
                if (instanceReadyStr.contains("available")) {
```

```
                    instanceReady = true
                } else {
                    print(".")
                    delay(sleepTime * 1000)
                }
            }
        }
    }
    println("Database cluster is available!")
}

suspend fun createDBCluster(dbParameterGroupFamilyVal: String?, dbName: String?,
 dbClusterIdentifierVal: String?, userName: String?, password: String?): String? {
    val clusterRequest = CreateDbClusterRequest {
        databaseName = dbName
        dbClusterIdentifier = dbClusterIdentifierVal
        dbClusterParameterGroupName = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
        masterUsername = userName
        masterUserPassword = password
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbCluster(clusterRequest)
        return response.dbCluster?.dbClusterArn
    }
}

// Get a list of allowed engine versions.
suspend fun getAllowedClusterEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "aurora-mysql"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        response.dbEngineVersions?.forEach { dbEngine ->
            println("The engine version is ${dbEngine.engineVersion}")
            println("The engine description is ${dbEngine.dbEngineDescription}")
        }
    }
}
```

```
// Modify the auto_increment_offset parameter.
suspend fun modifyDBClusterParas(dClusterGroupName: String?) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.fromValue("immediate")
        parameterValue = "5"
    }

    val paraList = ArrayList<Parameter>()
    paraList.add(parameter1)
    val groupRequest = ModifyDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dClusterGroupName
        parameters = paraList
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbClusterParameterGroup(groupRequest)
        println("The parameter group ${response.dbClusterParameterGroupName} was
 successfully modified")
    }
}

suspend fun describeDbClusterParameters(dbCLusterGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbClusterParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
        }
    } else {
        DescribeDbClusterParametersRequest {
            dbClusterParameterGroupName = dbCLusterGroupName
            source = "user"
        }
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeDbClusterParameters(dbParameterGroupsRequest)
        response.parameters?.forEach { para ->
            // Only print out information about either auto_increment_offset or
 auto_increment_increment.
            val paraName = para.parameterName
            if (paraName != null) {
```

```
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    println("*** The parameter value is  ${para.parameterValue}")
                    println("*** The parameter data type is ${para.dataType}")
                    println("*** The parameter description is ${para.description}")
                    println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
        }
    }
}

suspend fun describeDbClusterParameterGroups(dbClusterGroupName: String?) {
    val groupsRequest = DescribeDbClusterParameterGroupsRequest {
        dbClusterParameterGroupName = dbClusterGroupName
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbClusterParameterGroups(groupsRequest)
        response.dbClusterParameterGroups?.forEach { group ->
            println("The group name is ${group.dbClusterParameterGroupName}")
            println("The group ARN is ${group.dbClusterParameterGroupArn}")
        }
    }
}

suspend fun createDBClusterParameterGroup(dbClusterGroupNameVal: String?,
 dbParameterGroupFamilyVal: String?) {
    val groupRequest = CreateDbClusterParameterGroupRequest {
        dbClusterParameterGroupName = dbClusterGroupNameVal
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbClusterParameterGroup(groupRequest)
        println("The group name is
 ${response.dbClusterParameterGroup?.dbClusterParameterGroupName}")
    }
}
```

```
suspend fun describeAuroraDBEngines() {
    val engineVersionsRequest = DescribeDbEngineVersionsRequest {
        engine = "aurora-mysql"
        defaultOnly = true
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(engineVersionsRequest)
        response.dbEngineVersions?.forEach { engineOb ->
            println("The name of the DB parameter group family for the database
 engine is ${engineOb.dbParameterGroupFamily}")
            println("The name of the database engine ${engineOb.engine}")
            println("The version number of the database engine
 ${engineOb.engineVersion}")
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - DB descrito ClusterParameterGroups
  - DB descrito ClusterParameters
  - DB descrito ClusterSnapshots
  - DescribeDBClusters
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions

- Modificar banco de dados ClusterParameterGroup

Exemplos de Auto Scaling usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createAutoScalingGroup(groupName: String, launchTemplateNameVal: String,
 serviceLinkedRoleARNVal: String, vpcZoneIdVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
```

```
    }

    val request = CreateAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        availabilityZones = listOf("us-east-1a")
        launchTemplate = templateSpecification
        maxSize = 1
        minSize = 1
        vpcZoneIdentifier = vpcZoneIdVal
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
    }

    // This object is required for the waiter call.
    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.createAutoScalingGroup(request)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("$groupName was created!")
    }
}
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupreferência da API AWSSDK for Kotlin.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSpecificAutoScalingGroup(groupName: String) {
```

```
    val deleteAutoScalingGroupRequest = DeleteAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        forceDelete = true
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest)
        println("You successfully deleted $groupName")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupreferência da API AWSSDK for Kotlin.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableMetricsCollection(groupName: String) {
    val disableMetricsCollectionRequest = DisableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest)
        println("The disable metrics collection operation was successful")
    }
}
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionreferência da API AWSSDK for Kotlin.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableMetricsCollection(groupName: String?) {
    val collectionRequest = EnableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
        granularity = "1Minute"
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.enableMetricsCollection(collectionRequest)
        println("The enable metrics collection operation was successful")
    }
}
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionreferência da API AWSSDK for Kotlin.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informação sobre grupos do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAutoScalingGroups(groupName: String) {
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")
            group.instances?.forEach { instance ->
                println("The instance id is ${instance.instanceId}")
                println("The lifecycle state is " + instance.lifecycleState)
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWSSDK for Kotlin.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAutoScalingInstance(id: String) {
    val describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest {
        instanceIds = listOf(id)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingInstances(describeAutoScalingInstancesRequest)
        response.autoScalingInstances?.forEach { group ->
            println("The instance lifecycle state is: ${group.lifecycleState}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesreferência da API AWSSDK for Kotlin.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informação sobre atividades do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAutoScalingGroups(groupName: String) {
    val groupsReques = DescribeAutoScalingGroupsRequest {
```

```
        autoScalingGroupNames = listOf(groupName)
        maxRecords = 10
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response = autoScalingClient.describeAutoScalingGroups(groupsReques)
        response.autoScalingGroups?.forEach { group ->
            println("The service to use for the health checks:
 ${group.healthCheckType}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesreferência da API AWSSDK for Kotlin.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo de Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setDesiredCapacity(groupName: String) {
    val capacityRequest = SetDesiredCapacityRequest {
        autoScalingGroupName = groupName
        desiredCapacity = 2
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.setDesiredCapacity(capacityRequest)
        println("You set the DesiredCapacity to 2")
    }
}
```

- Para obter detalhes da API, consulte a SetDesiredCapacityreferência da API AWSSDK for Kotlin.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun terminateInstanceInAutoScalingGroup(instanceIdVal: String) {
    val request = TerminateInstanceInAutoScalingGroupRequest {
        instanceId = instanceIdVal
        shouldDecrementDesiredCapacity = false
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.terminateInstanceInAutoScalingGroup(request)
        println("You have terminated instance $instanceIdVal")
    }
}
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupreferência da API AWSSDK for Kotlin.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo de Auto Scaling.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateAutoScalingGroup(groupName: String, launchTemplateNameVal: String,
 serviceLinkedRoleARNVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val groupRequest = UpdateAutoScalingGroupRequest {
        maxSize = 3
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
        autoScalingGroupName = groupName
        launchTemplate = templateSpecification
    }

    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.updateAutoScalingGroup(groupRequest)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("You successfully updated the Auto Scaling group  $groupName")
    }
}
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupreferência da API AWSSDK for Kotlin.

Cenários

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <groupName> <launchTemplateName> <serviceLinkedRoleARN> <vpcZoneId>

    Where:
        groupName - The name of the Auto Scaling group.
        launchTemplateName - The name of the launch template.
        serviceLinkedRoleARN - The Amazon Resource Name (ARN) of the service-linked
 role that the Auto Scaling group uses.
        vpcZoneId - A subnet Id for a virtual private cloud (VPC) where instances in
 the Auto Scaling group can be created.
    """

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val groupName = args[0]
    val launchTemplateName = args[1]
    val serviceLinkedRoleARN = args[2]
```

```
    val vpcZoneId = args[3]

    println("**** Create an Auto Scaling group named $groupName")
    createAutoScalingGroup(groupName, launchTemplateName, serviceLinkedRoleARN,
vpcZoneId)

    println("Wait 1 min for the resources, including the instance. Otherwise, an
empty instance Id is returned")
    delay(60000)

    val instanceId = getSpecificAutoScaling(groupName)
    if (instanceId.compareTo("") == 0) {
        println("Error - no instance Id value")
        exitProcess(1)
    } else {
        println("The instance Id value is $instanceId")
    }

    println("**** Describe Auto Scaling with the Id value $instanceId")
    describeAutoScalingInstance(instanceId)

    println("**** Enable metrics collection $instanceId")
    enableMetricsCollection(groupName)

    println("**** Update an Auto Scaling group to maximum size of 3")
    updateAutoScalingGroup(groupName, launchTemplateName, serviceLinkedRoleARN)

    println("**** Describe all Auto Scaling groups to show the current state of the
groups")
    describeAutoScalingGroups(groupName)

    println("**** Describe account details")
    describeAccountLimits()

    println("Wait 1 min for the resources, including the instance. Otherwise, an
empty instance Id is returned")
    delay(60000)

    println("**** Set desired capacity to 2")
    setDesiredCapacity(groupName)

    println("**** Get the two instance Id values and state")
    getAutoScalingGroups(groupName)
```

```
    println("**** List the scaling activities that have occurred for the group")
    describeScalingActivities(groupName)

    println("**** Terminate an instance in the Auto Scaling group")
    terminateInstanceInAutoScalingGroup(instanceId)

    println("**** Stop the metrics collection")
    disableMetricsCollection(groupName)

    println("**** Delete the Auto Scaling group")
    deleteSpecificAutoScalingGroup(groupName)
}

suspend fun describeAutoScalingGroups(groupName: String) {
    val groupsReques = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
        maxRecords = 10
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response = autoScalingClient.describeAutoScalingGroups(groupsReques)
        response.autoScalingGroups?.forEach { group ->
            println("The service to use for the health checks:
 ${group.healthCheckType}")
        }
    }
}

suspend fun disableMetricsCollection(groupName: String) {
    val disableMetricsCollectionRequest = DisableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.disableMetricsCollection(disableMetricsCollectionRequest)
        println("The disable metrics collection operation was successful")
    }
}

suspend fun describeScalingActivities(groupName: String?) {
    val scalingActivitiesRequest = DescribeScalingActivitiesRequest {
        autoScalingGroupName = groupName
        maxRecords = 10
```

```
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeScalingActivities(scalingActivitiesRequest)
        response.activities?.forEach { activity ->
            println("The activity Id is ${activity.activityId}")
            println("The activity details are ${activity.details}")
        }
    }
}

suspend fun getAutoScalingGroups(groupName: String) {
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")
            group.instances?.forEach { instance ->
                println("The instance id is ${instance.instanceId}")
                println("The lifecycle state is " + instance.lifecycleState)
            }
        }
    }
}

suspend fun setDesiredCapacity(groupName: String) {
    val capacityRequest = SetDesiredCapacityRequest {
        autoScalingGroupName = groupName
        desiredCapacity = 2
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.setDesiredCapacity(capacityRequest)
        println("You set the DesiredCapacity to 2")
    }
}
```

```
suspend fun updateAutoScalingGroup(groupName: String, launchTemplateNameVal: String,
 serviceLinkedRoleARNVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val groupRequest = UpdateAutoScalingGroupRequest {
        maxSize = 3
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
        autoScalingGroupName = groupName
        launchTemplate = templateSpecification
    }

    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.updateAutoScalingGroup(groupRequest)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("You successfully updated the Auto Scaling group  $groupName")
    }
}

suspend fun createAutoScalingGroup(groupName: String, launchTemplateNameVal: String,
 serviceLinkedRoleARNVal: String, vpcZoneIdVal: String) {
    val templateSpecification = LaunchTemplateSpecification {
        launchTemplateName = launchTemplateNameVal
    }

    val request = CreateAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        availabilityZones = listOf("us-east-1a")
        launchTemplate = templateSpecification
        maxSize = 1
        minSize = 1
        vpcZoneIdentifier = vpcZoneIdVal
        serviceLinkedRoleArn = serviceLinkedRoleARNVal
    }

    // This object is required for the waiter call.
    val groupsRequestWaiter = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }
```

```
    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.createAutoScalingGroup(request)
        autoScalingClient.waitUntilGroupExists(groupsRequestWaiter)
        println("$groupName was created!")
    }
}

suspend fun describeAutoScalingInstance(id: String) {
    val describeAutoScalingInstancesRequest = DescribeAutoScalingInstancesRequest {
        instanceIds = listOf(id)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingInstances(describeAutoScalingInstancesRequest)
        response.autoScalingInstances?.forEach { group ->
            println("The instance lifecycle state is: ${group.lifecycleState}")
        }
    }
}

suspend fun enableMetricsCollection(groupName: String?) {
    val collectionRequest = EnableMetricsCollectionRequest {
        autoScalingGroupName = groupName
        metrics = listOf("GroupMaxSize")
        granularity = "1Minute"
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.enableMetricsCollection(collectionRequest)
        println("The enable metrics collection operation was successful")
    }
}

suspend fun getSpecificAutoScaling(groupName: String): String {
    var instanceId = ""
    val scalingGroupsRequest = DescribeAutoScalingGroupsRequest {
        autoScalingGroupNames = listOf(groupName)
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAutoScalingGroups(scalingGroupsRequest)
```

```
        response.autoScalingGroups?.forEach { group ->
            println("The group name is ${group.autoScalingGroupName}")
            println("The group ARN is ${group.autoScalingGroupArn}")

            group.instances?.forEach { instance ->
                instanceId = instance.instanceId.toString()
            }
        }
    }
    return instanceId
}

suspend fun describeAccountLimits() {
    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        val response =
 autoScalingClient.describeAccountLimits(DescribeAccountLimitsRequest {})
        println("The max number of Auto Scaling groups is
 ${response.maxNumberOfAutoScalingGroups}")
        println("The current number of Auto Scaling groups is
 ${response.numberOfAutoScalingGroups}")
    }
}

suspend fun terminateInstanceInAutoScalingGroup(instanceIdVal: String) {
    val request = TerminateInstanceInAutoScalingGroupRequest {
        instanceId = instanceIdVal
        shouldDecrementDesiredCapacity = false
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.terminateInstanceInAutoScalingGroup(request)
        println("You have terminated instance $instanceIdVal")
    }
}

suspend fun deleteSpecificAutoScalingGroup(groupName: String) {
    val deleteAutoScalingGroupRequest = DeleteAutoScalingGroupRequest {
        autoScalingGroupName = groupName
        forceDelete = true
    }

    AutoScalingClient { region = "us-east-1" }.use { autoScalingClient ->
        autoScalingClient.deleteAutoScalingGroup(deleteAutoScalingGroupRequest)
        println("You successfully deleted $groupName")
```

```
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o SDK da AWS para Kotlin com o Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
suspend fun listFoundationModels(): List<FoundationModelSummary>? {
    BedrockClient { region = "us-east-1" }.use { bedrockClient ->
        val response =
 bedrockClient.listFoundationModels(ListFoundationModelsRequest {})
        response.modelSummaries?.forEach { model ->
            println("==========================================")
            println(" Model ID: ${model.modelId}")
            println("------------------------------------------")
            println(" Name: ${model.modelName}")
            println(" Provider: ${model.providerName}")
            println(" Input modalities: ${model.inputModalities}")
            println(" Output modalities: ${model.outputModalities}")
            println(" Supported customizations: ${model.customizationsSupported}")
            println(" Supported inference types: ${model.inferenceTypesSupported}")
            println("------------------------------------------\n")
        }
        return response.modelSummaries
    }
}
```

- Para obter detalhes da API, consulte a ListFoundationModelsreferência da API AWSSDK for Kotlin.

CloudWatch exemplos usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com. CloudWatch

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá CloudWatch

O exemplo de código a seguir mostra como começar a usar o CloudWatch.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
           <namespace>
```

```
        Where:
           namespace - The namespace to filter against (for example, AWS/EC2).
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val namespace = args[0]
    listAllMets(namespace)
}

suspend fun listAllMets(namespaceVal: String?) {
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listMetricsPaginated(request)
            .transform { it.metrics?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name is ${obj.metricName}")
                println("Namespace is ${obj.namespace}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Criar um painel

O exemplo de código a seguir mostra como criar um CloudWatch painel da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDashboardWithMetrics(dashboardNameVal: String, fileNameVal:
 String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully created.")
        val messages = response.dashboardValidationMessages
        if (messages != null) {
            if (messages.isEmpty()) {
                println("There are no messages in the new Dashboard")
            } else {
                for (message in messages) {
                    println("Message is: ${message.message}")
                }
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a PutDashboardreferência da API AWSSDK for Kotlin.

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putMetricAlarm(alarmNameVal: String, instanceIdVal: String) {

    val dimensionOb = Dimension {
        name = "InstanceId"
        value = instanceIdVal
    }

    val request = PutMetricAlarmRequest {
        alarmName = alarmNameVal
        comparisonOperator = ComparisonOperator.GreaterThanThreshold
        evaluationPeriods = 1
        metricName = "CPUUtilization"
        namespace = "AWS/EC2"
        period = 60
        statistic = Statistic.fromValue("Average")
        threshold = 70.0
        actionsEnabled = false
        alarmDescription = "An Alarm created by the Kotlin SDK when server CPU
 utilization exceeds 70%"
        unit = StandardUnit.fromValue("Seconds")
        dimensions = listOf(dimensionOb)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricAlarm(request)
        println("Successfully created an alarm with name $alarmNameVal")
    }
}
```

- Para obter detalhes da API, consulte a PutMetricAlarmreferência da API AWSSDK for Kotlin.

Criar um detector de anomalias

O exemplo de código a seguir mostra como criar um detector de CloudWatch anomalias da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAnomalyDetector(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val anomalyDetectorRequest = PutAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putAnomalyDetector(anomalyDetectorRequest)
        println("Added anomaly detector for metric $customMetricName.")
    }
}
```

- Para obter detalhes da API, consulte a PutAnomalyDetectorreferência da API AWSSDK for Kotlin.

Excluir alarmes

O exemplo de código a seguir mostra como excluir os CloudWatch alarmes da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteAlarm(alarmNameVal: String) {
    val request = DeleteAlarmsRequest {
        alarmNames = listOf(alarmNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAlarms(request)
        println("Successfully deleted alarm $alarmNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAlarmsreferência da API AWSSDK for Kotlin.

Excluir um detector de anomalias

O exemplo de código a seguir mostra como excluir um detector de CloudWatch anomalias da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteAnomalyDetector(fileName: String) {
```

```
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val request = DeleteAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAnomalyDetector(request)
        println("Successfully deleted the Anomaly Detector.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAnomalyDetectorreferência da API AWSSDK for Kotlin.

Excluir painéis

O exemplo de código a seguir mostra como excluir CloudWatch painéis da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDashboard(dashboardName: String) {
    val dashboardsRequest = DeleteDashboardsRequest {
        dashboardNames = listOf(dashboardName)
    }
```

```
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteDashboards(dashboardsRequest)
        println("$dashboardName was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteDashboardsreferência da API AWSSDK for Kotlin.

Descrever o histórico do alarme

O exemplo de código a seguir mostra como descrever um histórico de CloudWatch alarmes da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAlarmHistory(fileName: String, date: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
    val start = Instant.parse(date)
    val endDateVal = Instant.now()

    val historyRequest = DescribeAlarmHistoryRequest {
        startDate = aws.smithy.kotlin.runtime.time.Instant(start)
        endDate = aws.smithy.kotlin.runtime.time.Instant(endDateVal)
        alarmName = alarmNameVal
        historyItemType = HistoryItemType.Action
    }

    CloudWatchClient { credentialsProvider = EnvironmentCredentialsProvider();
 region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarmHistory(historyRequest)
        val historyItems = response.alarmHistoryItems
        if (historyItems != null) {
```

```
            if (historyItems.isEmpty()) {
                println("No alarm history data found for $alarmNameVal.")
            } else {
                for (item in historyItems) {
                    println("History summary ${item.historySummary}")
                    println("Time stamp: ${item.timestamp}")
                }
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmHistoryreferência da API AWSSDK for Kotlin.

Descrever alarmes

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAlarms() {
    val typeList = ArrayList<AlarmType>()
    typeList.add(AlarmType.MetricAlarm)
    val alarmsRequest = DescribeAlarmsRequest {
        alarmTypes = typeList
        maxRecords = 10
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarms(alarmsRequest)
        response.metricAlarms?.forEach { alarm ->
            println("Alarm name: ${alarm.alarmName}")
            println("Alarm description: ${alarm.alarmDescription}")
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmsreferência da API AWSSDK for Kotlin.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkForMetricAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    var hasAlarm = false
    var retries = 10

    val metricRequest = DescribeAlarmsForMetricRequest {
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        while (!hasAlarm && retries > 0) {
            val response = cwClient.describeAlarmsForMetric(metricRequest)
            if (response.metricAlarms?.count()!! > 0) {
                hasAlarm = true
            }
            retries--
            delay(20000)
            println(".")
        }
```

```
        if (!hasAlarm) println("No Alarm state found for $customMetricName after 10
 retries.") else println("Alarm state found for $customMetricName.")
    }
}
```

- Para obter detalhes da API, consulte a DescribeAlarmsForMetricreferência da API AWSSDK for Kotlin.

Descrever detectores de anomalias

O exemplo de código a seguir mostra como descrever os detectores de CloudWatch anomalias da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAnomalyDetectors(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val detectorsRequest = DescribeAnomalyDetectorsRequest {
        maxResults = 10
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAnomalyDetectors(detectorsRequest)
        response.anomalyDetectors?.forEach { detector ->
            println("Metric name:
 ${detector.singleMetricAnomalyDetector?.metricName}")
            println("State: ${detector.stateValue}")
        }
```

```
    }
}
```

- Para obter detalhes da API, consulte a DescribeAnomalyDetectorsreferência da API AWSSDK for Kotlin.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableActions(alarmName: String) {

    val request = DisableAlarmActionsRequest {
        alarmNames = listOf(alarmName)
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.disableAlarmActions(request)
        println("Successfully disabled actions on alarm $alarmName")
    }
}
```

- Para obter detalhes da API, consulte a DisableAlarmActionsreferência da API AWSSDK for Kotlin.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableActions(alarm: String) {

    val request = EnableAlarmActionsRequest {
        alarmNames = listOf(alarm)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.enableAlarmActions(request)
        println("Successfully enabled actions on alarm $alarm")
    }
}
```

- Para obter detalhes da API, consulte a EnableAlarmActionsreferência da API AWSSDK for Kotlin.

Obter uma imagem de dados de métricas

O exemplo de código a seguir mostra como obter uma imagem de dados CloudWatch métricos da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAndOpenMetricImage(fileName: String) {
    println("Getting Image data for custom metric.")
```

```
    val myJSON = """{
        "title": "Example Metric Graph",
        "view": "timeSeries",
        "stacked ": false,
        "period": 10,
        "width": 1400,
        "height": 600,
        "metrics": [
            [
            "AWS/Billing",
            "EstimatedCharges",
            "Currency",
            "USD"
            ]
        ]
        }"""

    val imageRequest = GetMetricWidgetImageRequest {
        metricWidget = myJSON
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricWidgetImage(imageRequest)
        val bytes = response.metricWidgetImage
        if (bytes != null) {
            File(fileName).writeBytes(bytes)
        }
    }
    println("You have successfully written data to $fileName")
}
```

- Para obter detalhes da API, consulte a GetMetricWidgetImagereferência da API AWSSDK for Kotlin.

Obter dados de métricas

O exemplo de código a seguir mostra como obter dados CloudWatch métricos da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getCustomMetricData(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set the date.
    val nowDate = Instant.now()
    val hours: Long = 1
    val minutes: Long = 30
    val date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(
        minutes,
        ChronoUnit.MINUTES
    )

    val met = Metric {
        metricName = customMetricName
        namespace = customMetricNamespace
    }

    val metStat = MetricStat {
        stat = "Maximum"
        period = 1
        metric = met
    }

    val dataQUery = MetricDataQuery {
        metricStat = metStat
        id = "foo2"
        returnData = true
    }

    val dq = ArrayList<MetricDataQuery>()
```

```
    dq.add(dataQUery)
    val getMetReq = GetMetricDataRequest {
        maxDatapoints = 10
        scanBy = ScanBy.TimestampDescending
        startTime = aws.smithy.kotlin.runtime.time.Instant(nowDate)
        endTime = aws.smithy.kotlin.runtime.time.Instant(date2)
        metricDataQueries = dq
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricData(getMetReq)
        response.metricDataResults?.forEach { item ->
            println("The label is ${item.label}")
            println("The status code is ${item.statusCode}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetMetricDatareferência da API AWSSDK for Kotlin.

Obter estatísticas de métricas

O exemplo de código a seguir mostra como obter estatísticas CloudWatch métricas da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAndDisplayMetricStatistics(nameSpaceVal: String, metVal: String,
 metricOption: String, date: String, myDimension: Dimension) {
    val start = Instant.parse(date)
    val endDate = Instant.now()
    val statisticsRequest = GetMetricStatisticsRequest {
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        dimensions = listOf(myDimension)
        metricName = metVal
```

```
        namespace = nameSpaceVal
        period = 86400
        statistics = listOf(Statistic.fromValue(metricOption))
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data = response.datapoints
        if (data != null) {
            if (data.isNotEmpty()) {
                for (datapoint in data) {
                    println("Timestamp: ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a GetMetricStatisticsreferência da API AWSSDK for Kotlin.

Listar painéis

O exemplo de código a seguir mostra como listar os CloudWatch painéis da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDashboards() {
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listDashboardsPaginated({})
            .transform { it.dashboardEntries?.forEach { obj -> emit(obj) } }
            .collect { obj ->
```

```
                println("Name is ${obj.dashboardName}")
                println("Dashboard ARN is ${obj.dashboardArn}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListDashboardsreferência da API AWSSDK for Kotlin.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listMets(namespaceVal: String?): ArrayList<String>? {
    val metList = ArrayList<String>()
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val reponse = cwClient.listMetrics(request)
        reponse.metrics?.forEach { metrics ->
            val data = metrics.metricName
            if (!metList.contains(data)) {
                metList.add(data!!)
            }
        }
    }
    return metList
}
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWSSDK for Kotlin.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addMetricDataForAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1001.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val datum2 = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1002.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val metricDataList = ArrayList<MetricDatum>()
    metricDataList.add(datum)
    metricDataList.add(datum2)
```

```
    val request = PutMetricDataRequest {
        namespace = customMetricNamespace
        metricData = metricDataList
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric $customMetricName")
    }
}
```

- Para obter detalhes da API, consulte a PutMetricDatareferência da API AWSSDK for Kotlin.

Cenários

Começar a usar métricas, painéis e alarmes

O código de exemplo a seguir mostra como:

- Listar CloudWatch namespaces e métricas.
- Obtenha estatísticas para uma métrica e para faturamento estimado.
- Crie e atualize um painel.
- Crie e adicione dados a uma métrica.
- Crie e acione um alarme e, em seguida, visualize o histórico de alarmes.
- Crie um detector de anomalias.
- Obtenha uma imagem de métrica e, em seguida, limpe os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
```

```
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 To enable billing metrics and statistics for this example, make sure billing alerts
 are enabled for your account:
 https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/
monitor_estimated_charges_with_cloudwatch.html#turning_on_billing_metrics

 This Kotlin code example performs the following tasks:

 1. List available namespaces from Amazon CloudWatch. Select a namespace from the
 list.
 2. List available metrics within the selected namespace.
 3. Get statistics for the selected metric over the last day.
 4. Get CloudWatch estimated billing for the last week.
 5. Create a new CloudWatch dashboard with metrics.
 6. List dashboards using a paginator.
 7. Create a new custom metric by adding data for it.
 8. Add the custom metric to the dashboard.
 9. Create an alarm for the custom metric.
 10. Describe current alarms.
 11. Get current data for the new custom metric.
 12. Push data into the custom metric to trigger the alarm.
 13. Check the alarm state using the action DescribeAlarmsForMetric.
 14. Get alarm history for the new alarm.
 15. Add an anomaly detector for the custom metric.
 16. Describe current anomaly detectors.
 17. Get a metric image for the custom metric.
 18. Clean up the Amazon CloudWatch resources.
 */

val DASHES: String? = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <myDate> <costDateWeek> <dashboardName> <dashboardJson> <dashboardAdd>
 <settings> <metricImage>

        Where:
            myDate - The start date to use to get metric statistics. (For example,
 2023-01-11T18:35:24.00Z.)
```

```
            costDateWeek - The start date to use to get AWS Billing and Cost
Management statistics. (For example, 2023-01-11T18:35:24.00Z.)
            dashboardName - The name of the dashboard to create.
            dashboardJson - The location of a JSON file to use to create a
dashboard. (See Readme file.)
            dashboardAdd - The location of a JSON file to use to update a dashboard.
(See Readme file.)
            settings - The location of a JSON file from which various values are
read. (See Readme file.)
            metricImage - The location of a BMP file that is used to create a
graph.
    """

    if (args.size != 7) {
        println(usage)
        System.exit(1)
    }

    val myDate = args[0]
    val costDateWeek = args[1]
    val dashboardName = args[2]
    val dashboardJson = args[3]
    val dashboardAdd = args[4]
    val settings = args[5]
    var metricImage = args[6]
    val dataPoint = "10.0".toDouble()
    val inOb = Scanner(System.`in`)

    println(DASHES)
    println("Welcome to the Amazon CloudWatch example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. List at least five available unique namespaces from Amazon
CloudWatch. Select a CloudWatch namespace from the list.")
    val list: ArrayList<String> = listNameSpaces()
    for (z in 0..4) {
        println("    ${z + 1}. ${list[z]}")
    }

    var selectedNamespace: String
    var selectedMetrics = ""
    var num = inOb.nextLine().toInt()
    println("You selected $num")
```

```
    if (1 <= num && num <= 5) {
        selectedNamespace = list[num - 1]
    } else {
        println("You did not select a valid option.")
        exitProcess(1)
    }
    println("You selected $selectedNamespace")
    println(DASHES)

    println(DASHES)
    println("2. List available metrics within the selected namespace and select one
from the list.")
    val metList = listMets(selectedNamespace)
    for (z in 0..4) {
        println("    ${ z + 1}. ${metList?.get(z)}")
    }
    num = inOb.nextLine().toInt()
    if (1 <= num && num <= 5) {
        selectedMetrics = metList!![num - 1]
    } else {
        println("You did not select a valid option.")
        System.exit(1)
    }
    println("You selected $selectedMetrics")
    val myDimension = getSpecificMet(selectedNamespace)
    if (myDimension == null) {
        println("Error - Dimension is null")
        exitProcess(1)
    }
    println(DASHES)

    println(DASHES)
    println("3. Get statistics for the selected metric over the last day.")
    val metricOption: String
    val statTypes = ArrayList<String>()
    statTypes.add("SampleCount")
    statTypes.add("Average")
    statTypes.add("Sum")
    statTypes.add("Minimum")
    statTypes.add("Maximum")

    for (t in 0..4) {
        println("    ${t + 1}. ${statTypes[t]}")
```

```
    }
    println("Select a metric statistic by entering a number from the preceding
list:")
    num = inOb.nextLine().toInt()
    if (1 <= num && num <= 5) {
        metricOption = statTypes[num - 1]
    } else {
        println("You did not select a valid option.")
        exitProcess(1)
    }
    println("You selected $metricOption")
    getAndDisplayMetricStatistics(selectedNamespace, selectedMetrics, metricOption,
myDate, myDimension)
    println(DASHES)

    println(DASHES)
    println("4. Get CloudWatch estimated billing for the last week.")
    getMetricStatistics(costDateWeek)
    println(DASHES)

    println(DASHES)
    println("5. Create a new CloudWatch dashboard with metrics.")
    createDashboardWithMetrics(dashboardName, dashboardJson)
    println(DASHES)

    println(DASHES)
    println("6. List dashboards using a paginator.")
    listDashboards()
    println(DASHES)

    println(DASHES)
    println("7. Create a new custom metric by adding data to it.")
    createNewCustomMetric(dataPoint)
    println(DASHES)

    println(DASHES)
    println("8. Add an additional metric to the dashboard.")
    addMetricToDashboard(dashboardAdd, dashboardName)
    println(DASHES)

    println(DASHES)
    println("9. Create an alarm for the custom metric.")
    val alarmName: String = createAlarm(settings)
    println(DASHES)
```

```
    println(DASHES)
    println("10. Describe 10 current alarms.")
    describeAlarms()
    println(DASHES)

    println(DASHES)
    println("11. Get current data for the new custom metric.")
    getCustomMetricData(settings)
    println(DASHES)

    println(DASHES)
    println("12. Push data into the custom metric to trigger the alarm.")
    addMetricDataForAlarm(settings)
    println(DASHES)

    println(DASHES)
    println("13. Check the alarm state using the action DescribeAlarmsForMetric.")
    checkForMetricAlarm(settings)
    println(DASHES)

    println(DASHES)
    println("14. Get alarm history for the new alarm.")
    getAlarmHistory(settings, myDate)
    println(DASHES)

    println(DASHES)
    println("15. Add an anomaly detector for the custom metric.")
    addAnomalyDetector(settings)
    println(DASHES)

    println(DASHES)
    println("16. Describe current anomaly detectors.")
    describeAnomalyDetectors(settings)
    println(DASHES)

    println(DASHES)
    println("17. Get a metric image for the custom metric.")
    getAndOpenMetricImage(metricImage)
    println(DASHES)

    println(DASHES)
    println("18. Clean up the Amazon CloudWatch resources.")
    deleteDashboard(dashboardName)
```

```
    deleteAlarm(alarmName)
    deleteAnomalyDetector(settings)
    println(DASHES)

    println(DASHES)
    println("The Amazon CloudWatch example scenario is complete.")
    println(DASHES)
}

suspend fun deleteAnomalyDetector(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val request = DeleteAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAnomalyDetector(request)
        println("Successfully deleted the Anomaly Detector.")
    }
}

suspend fun deleteAlarm(alarmNameVal: String) {
    val request = DeleteAlarmsRequest {
        alarmNames = listOf(alarmNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteAlarms(request)
        println("Successfully deleted alarm $alarmNameVal")
    }
}

suspend fun deleteDashboard(dashboardName: String) {
```

```
    val dashboardsRequest = DeleteDashboardsRequest {
        dashboardNames = listOf(dashboardName)
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.deleteDashboards(dashboardsRequest)
        println("$dashboardName was successfully deleted.")
    }
}

suspend fun getAndOpenMetricImage(fileName: String) {
    println("Getting Image data for custom metric.")
    val myJSON = """{
        "title": "Example Metric Graph",
        "view": "timeSeries",
        "stacked ": false,
        "period": 10,
        "width": 1400,
        "height": 600,
        "metrics": [
            [
            "AWS/Billing",
            "EstimatedCharges",
            "Currency",
            "USD"
            ]
        ]
        }"""

    val imageRequest = GetMetricWidgetImageRequest {
        metricWidget = myJSON
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricWidgetImage(imageRequest)
        val bytes = response.metricWidgetImage
        if (bytes != null) {
            File(fileName).writeBytes(bytes)
        }
    }
    println("You have successfully written data to $fileName")
}

suspend fun describeAnomalyDetectors(fileName: String) {
    // Read values from the JSON file.
```

```
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val detectorsRequest = DescribeAnomalyDetectorsRequest {
        maxResults = 10
        metricName = customMetricName
        namespace = customMetricNamespace
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAnomalyDetectors(detectorsRequest)
        response.anomalyDetectors?.forEach { detector ->
            println("Metric name:
 ${detector.singleMetricAnomalyDetector?.metricName}")
            println("State: ${detector.stateValue}")
        }
    }
}

suspend fun addAnomalyDetector(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    val singleMetricAnomalyDetectorVal = SingleMetricAnomalyDetector {
        metricName = customMetricName
        namespace = customMetricNamespace
        stat = "Maximum"
    }

    val anomalyDetectorRequest = PutAnomalyDetectorRequest {
        singleMetricAnomalyDetector = singleMetricAnomalyDetectorVal
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putAnomalyDetector(anomalyDetectorRequest)
        println("Added anomaly detector for metric $customMetricName.")
    }
}

suspend fun getAlarmHistory(fileName: String, date: String) {
```

```
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
    val start = Instant.parse(date)
    val endDateVal = Instant.now()

    val historyRequest = DescribeAlarmHistoryRequest {
        startDate = aws.smithy.kotlin.runtime.time.Instant(start)
        endDate = aws.smithy.kotlin.runtime.time.Instant(endDateVal)
        alarmName = alarmNameVal
        historyItemType = HistoryItemType.Action
    }

    CloudWatchClient { credentialsProvider = EnvironmentCredentialsProvider();
 region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarmHistory(historyRequest)
        val historyItems = response.alarmHistoryItems
        if (historyItems != null) {
            if (historyItems.isEmpty()) {
                println("No alarm history data found for $alarmNameVal.")
            } else {
                for (item in historyItems) {
                    println("History summary ${item.historySummary}")
                    println("Time stamp: ${item.timestamp}")
                }
            }
        }
    }
}

suspend fun checkForMetricAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    var hasAlarm = false
    var retries = 10

    val metricRequest = DescribeAlarmsForMetricRequest {
        metricName = customMetricName
        namespace = customMetricNamespace
    }
```

```
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        while (!hasAlarm && retries > 0) {
            val response = cwClient.describeAlarmsForMetric(metricRequest)
            if (response.metricAlarms?.count()!! > 0) {
                hasAlarm = true
            }
            retries--
            delay(20000)
            println(".")
        }
        if (!hasAlarm) println("No Alarm state found for $customMetricName after 10
 retries.") else println("Alarm state found for $customMetricName.")
    }
}

suspend fun addMetricDataForAlarm(fileName: String?) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1001.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val datum2 = MetricDatum {
        metricName = customMetricName
        unit = StandardUnit.None
        value = 1002.00
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
    }

    val metricDataList = ArrayList<MetricDatum>()
    metricDataList.add(datum)
    metricDataList.add(datum2)
```

```
    val request = PutMetricDataRequest {
        namespace = customMetricNamespace
        metricData = metricDataList
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric $customMetricName")
    }
}

suspend fun getCustomMetricData(fileName: String) {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()

    // Set the date.
    val nowDate = Instant.now()
    val hours: Long = 1
    val minutes: Long = 30
    val date2 = nowDate.plus(hours, ChronoUnit.HOURS).plus(
        minutes,
        ChronoUnit.MINUTES
    )

    val met = Metric {
        metricName = customMetricName
        namespace = customMetricNamespace
    }

    val metStat = MetricStat {
        stat = "Maximum"
        period = 1
        metric = met
    }

    val dataQUery = MetricDataQuery {
        metricStat = metStat
        id = "foo2"
        returnData = true
    }
```

```
    val dq = ArrayList<MetricDataQuery>()
    dq.add(dataQUery)
    val getMetReq = GetMetricDataRequest {
        maxDatapoints = 10
        scanBy = ScanBy.TimestampDescending
        startTime = aws.smithy.kotlin.runtime.time.Instant(nowDate)
        endTime = aws.smithy.kotlin.runtime.time.Instant(date2)
        metricDataQueries = dq
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricData(getMetReq)
        response.metricDataResults?.forEach { item ->
            println("The label is ${item.label}")
            println("The status code is ${item.statusCode}")
        }
    }
}

suspend fun describeAlarms() {
    val typeList = ArrayList<AlarmType>()
    typeList.add(AlarmType.MetricAlarm)
    val alarmsRequest = DescribeAlarmsRequest {
        alarmTypes = typeList
        maxRecords = 10
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.describeAlarms(alarmsRequest)
        response.metricAlarms?.forEach { alarm ->
            println("Alarm name: ${alarm.alarmName}")
            println("Alarm description: ${alarm.alarmDescription}")
        }
    }
}

suspend fun createAlarm(fileName: String): String {
    // Read values from the JSON file.
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode: JsonNode = ObjectMapper().readTree(parser)
    val customMetricNamespace = rootNode.findValue("customMetricNamespace").asText()
    val customMetricName = rootNode.findValue("customMetricName").asText()
    val alarmNameVal = rootNode.findValue("exampleAlarmName").asText()
    val emailTopic = rootNode.findValue("emailTopic").asText()
```

```
    val accountId = rootNode.findValue("accountId").asText()
    val region2 = rootNode.findValue("region").asText()

    // Create a List for alarm actions.
    val alarmActionObs: MutableList<String> = ArrayList()
    alarmActionObs.add("arn:aws:sns:$region2:$accountId:$emailTopic")
    val alarmRequest = PutMetricAlarmRequest {
        alarmActions = alarmActionObs
        alarmDescription = "Example metric alarm"
        alarmName = alarmNameVal
        comparisonOperator = ComparisonOperator.GreaterThanOrEqualToThreshold
        threshold = 100.00
        metricName = customMetricName
        namespace = customMetricNamespace
        evaluationPeriods = 1
        period = 10
        statistic = Statistic.Maximum
        datapointsToAlarm = 1
        treatMissingData = "ignore"
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricAlarm(alarmRequest)
        println("$alarmNameVal was successfully created!")
        return alarmNameVal
    }
}

suspend fun addMetricToDashboard(fileNameVal: String, dashboardNameVal: String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully updated.")
    }
}

suspend fun createNewCustomMetric(dataPoint: Double) {
    val dimension = Dimension {
        name = "UNIQUE_PAGES"
        value = "URLS"
```

```
    }

    // Set an Instant object.
    val time =
 ZonedDateTime.now(ZoneOffset.UTC).format(DateTimeFormatter.ISO_INSTANT)
    val instant = Instant.parse(time)
    val datum = MetricDatum {
        metricName = "PAGES_VISITED"
        unit = StandardUnit.None
        value = dataPoint
        timestamp = aws.smithy.kotlin.runtime.time.Instant(instant)
        dimensions = listOf(dimension)
    }

    val request = PutMetricDataRequest {
        namespace = "SITE/TRAFFIC"
        metricData = listOf(datum)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.putMetricData(request)
        println("Added metric values for for metric PAGES_VISITED")
    }
}

suspend fun listDashboards() {
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        cwClient.listDashboardsPaginated({})
            .transform { it.dashboardEntries?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name is ${obj.dashboardName}")
                println("Dashboard ARN is ${obj.dashboardArn}")
            }
    }
}

suspend fun createDashboardWithMetrics(dashboardNameVal: String, fileNameVal:
 String) {
    val dashboardRequest = PutDashboardRequest {
        dashboardName = dashboardNameVal
        dashboardBody = readFileAsString(fileNameVal)
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
```

```
        val response = cwClient.putDashboard(dashboardRequest)
        println("$dashboardNameVal was successfully created.")
        val messages = response.dashboardValidationMessages
        if (messages != null) {
            if (messages.isEmpty()) {
                println("There are no messages in the new Dashboard")
            } else {
                for (message in messages) {
                    println("Message is: ${message.message}")
                }
            }
        }
    }
}

fun readFileAsString(file: String): String {
    return String(Files.readAllBytes(Paths.get(file)))
}

suspend fun getMetricStatistics(costDateWeek: String?) {
    val start = Instant.parse(costDateWeek)
    val endDate = Instant.now()
    val dimension = Dimension {
        name = "Currency"
        value = "USD"
    }

    val dimensionList: MutableList<Dimension> = ArrayList()
    dimensionList.add(dimension)

    val statisticsRequest = GetMetricStatisticsRequest {
        metricName = "EstimatedCharges"
        namespace = "AWS/Billing"
        dimensions = dimensionList
        statistics = listOf(Statistic.Maximum)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        period = 86400
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data: List<Datapoint>? = response.datapoints
        if (data != null) {
            if (!data.isEmpty()) {
```

```
                for (datapoint in data) {
                    println("Timestamp:  ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}

suspend fun getAndDisplayMetricStatistics(nameSpaceVal: String, metVal: String,
 metricOption: String, date: String, myDimension: Dimension) {
    val start = Instant.parse(date)
    val endDate = Instant.now()
    val statisticsRequest = GetMetricStatisticsRequest {
        endTime = aws.smithy.kotlin.runtime.time.Instant(endDate)
        startTime = aws.smithy.kotlin.runtime.time.Instant(start)
        dimensions = listOf(myDimension)
        metricName = metVal
        namespace = nameSpaceVal
        period = 86400
        statistics = listOf(Statistic.fromValue(metricOption))
    }

    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.getMetricStatistics(statisticsRequest)
        val data = response.datapoints
        if (data != null) {
            if (data.isNotEmpty()) {
                for (datapoint in data) {
                    println("Timestamp: ${datapoint.timestamp} Maximum value:
 ${datapoint.maximum}")
                }
            } else {
                println("The returned data list is empty")
            }
        }
    }
}

suspend fun listMets(namespaceVal: String?): ArrayList<String>? {
    val metList = ArrayList<String>()
    val request = ListMetricsRequest {
```

```
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val reponse = cwClient.listMetrics(request)
        reponse.metrics?.forEach { metrics ->
            val data = metrics.metricName
            if (!metList.contains(data)) {
                metList.add(data!!)
            }
        }
    }
    return metList
}

suspend fun getSpecificMet(namespaceVal: String?): Dimension? {
    val request = ListMetricsRequest {
        namespace = namespaceVal
    }
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.listMetrics(request)
        val myList = response.metrics
        if (myList != null) {
            return myList[0].dimensions?.get(0)
        }
    }
    return null
}

suspend fun listNameSpaces(): ArrayList<String> {
    val nameSpaceList = ArrayList<String>()
    CloudWatchClient { region = "us-east-1" }.use { cwClient ->
        val response = cwClient.listMetrics(ListMetricsRequest {})
        response.metrics?.forEach { metrics ->
            val data = metrics.namespace
            if (!nameSpaceList.contains(data)) {
                nameSpaceList.add(data!!)
            }
        }
    }
    return nameSpaceList
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - DeleteAlarms
  - DeleteAnomalyDetector
  - DeleteDashboards
  - DescribeAlarmHistory
  - DescribeAlarms
  - DescribeAlarmsForMetric
  - DescribeAnomalyDetectors
  - GetMetricData
  - GetMetricStatistics
  - GetMetricWidgetImage
  - ListMetrics
  - PutAnomalyDetector
  - PutDashboard
  - PutMetricAlarm
  - PutMetricData

CloudWatch Exemplos de registros usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin with Logs. CloudWatch

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir um filtro de assinatura

O exemplo de código a seguir mostra como excluir um filtro de assinatura do Amazon CloudWatch Logs.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSubFilter(filter: String?, logGroup: String?) {

    val request = DeleteSubscriptionFilterRequest {
        filterName = filter
        logGroupName = logGroup
    }

    CloudWatchLogsClient { region = "us-west-2" }.use { logs ->
        logs.deleteSubscriptionFilter(request)
        println("Successfully deleted CloudWatch logs subscription filter named
 $filter")
    }
}
```

- Para obter detalhes da API, consulte a DeleteSubscriptionFilterreferência da API AWSSDK for Kotlin.

Descreva os filtros de assinatura existentes

O exemplo de código a seguir mostra como descrever os filtros de assinatura existentes do Amazon CloudWatch Logs.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeFilters(logGroup: String) {

    val request = DescribeSubscriptionFiltersRequest {
        logGroupName = logGroup
        limit = 1
    }

    CloudWatchLogsClient { region = "us-west-2" }.use { cwlClient ->
        val response = cwlClient.describeSubscriptionFilters(request)
        response.subscriptionFilters?.forEach { filter ->
            println("Retrieved filter with name  ${filter.filterName} pattern
 ${filter.filterPattern} and destination ${filter.destinationArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSubscriptionFiltersreferência da API AWSSDK for Kotlin.

Iniciar uma sessão Live Tail

O exemplo de código a seguir mostra como iniciar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

SDK for Kotlin

Inclua os arquivos necessários.

```
import aws.sdk.kotlin.services.cloudwatchlogs.CloudWatchLogsClient
import aws.sdk.kotlin.services.cloudwatchlogs.model.StartLiveTailRequest
import aws.sdk.kotlin.services.cloudwatchlogs.model.StartLiveTailResponseStream
import kotlinx.coroutines.flow.takeWhile
```

Inicie a sessão do Live Tail.

```
    val client = CloudWatchLogsClient.fromEnvironment()

    val request = StartLiveTailRequest {
        logGroupIdentifiers = logGroupIdentifiersVal
        logStreamNames = logStreamNamesVal
        logEventFilterPattern = logEventFilterPatternVal
    }

    val startTime = System.currentTimeMillis()

    try {
        client.startLiveTail(request) { response ->
            val stream = response.responseStream
            if (stream != null) {
                /* Set a timeout to unsubcribe from the flow. This will:
                * 1). Close the stream
                * 2). Stop the Live Tail session
                */
                stream.takeWhile { System.currentTimeMillis() - startTime <
10000 }.collect { value ->
                    if (value is StartLiveTailResponseStream.SessionStart) {
                        println(value.asSessionStart())
                    } else if (value is StartLiveTailResponseStream.SessionUpdate) {
                        for (e in value.asSessionUpdate().sessionResults!!) {
                            println(e)
                        }
                    } else {
                        throw IllegalArgumentException("Unknown event type")
                    }
                }
            } else {
                throw IllegalArgumentException("No response stream")
            }
        }
    } catch (e: Exception) {
        println("Exception occurred during StartLiveTail: $e")
        System.exit(1)
    }
```

- Para obter detalhes da API, consulte a StartLiveTailreferência da API AWSSDK for Kotlin.

Exemplos de código do Provedor de Identidade do Amazon Cognito usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun confirmSignUp(clientIdVal: String?, codeVal: String?, userNameVal:
 String?) {
```

```
    val signUpRequest = ConfirmSignUpRequest {
        clientId = clientIdVal
        confirmationCode = codeVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.confirmSignUp(signUpRequest)
        println("$userNameVal  was confirmed")
    }
}
```

- Para obter detalhes da API, consulte a ConfirmSignUpreferência da API AWSSDK for Kotlin.

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSecretForAppMFA(sessionVal: String?): String? {
    val softwareTokenRequest = AssociateSoftwareTokenRequest {
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val tokenResponse =
 identityProviderClient.associateSoftwareToken(softwareTokenRequest)
        val secretCode = tokenResponse.secretCode
        println("Enter this token into Google Authenticator")
        println(secretCode)
```

```
        return tokenResponse.session
    }
}
```

- Para obter detalhes da API, consulte a AssociateSoftwareTokenreferência da API AWSSDK for Kotlin.

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAdminUser(userNameVal: String?, poolIdVal: String?) {
    val userRequest = AdminGetUserRequest {
        username = userNameVal
        userPoolId = poolIdVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminGetUser(userRequest)
        println("User status ${response.userStatus}")
    }
}
```

- Para obter detalhes da API, consulte a AdminGetUserreferência da API AWSSDK for Kotlin.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllUsers(userPoolId: String) {

    val request = ListUsersRequest {
        this.userPoolId = userPoolId
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use { cognitoClient ->
        val response = cognitoClient.listUsers(request)
        response.users?.forEach { user ->
            println("The user name is ${user.username}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWSSDK for Kotlin.

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun resendConfirmationCode(clientIdVal: String?, userNameVal: String?) {
    val codeRequest = ResendConfirmationCodeRequest {
```

```
        clientId = clientIdVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.resendConfirmationCode(codeRequest)
        println("Method of delivery is " +
 (response.codeDeliveryDetails?.deliveryMedium))
    }
}
```

- Para obter detalhes da API, consulte a ResendConfirmationCodereferência da API AWSSDK for Kotlin.

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Respond to an authentication challenge.
suspend fun adminRespondToAuthChallenge(userName: String, clientIdVal: String?,
 mfaCode: String, sessionVal: String?) {
    println("SOFTWARE_TOKEN_MFA challenge is generated")
    val challengeResponsesOb = mutableMapOf<String, String>()
    challengeResponsesOb["USERNAME"] = userName
    challengeResponsesOb["SOFTWARE_TOKEN_MFA_CODE"] = mfaCode

    val adminRespondToAuthChallengeRequest = AdminRespondToAuthChallengeRequest {
        challengeName = ChallengeNameType.SoftwareTokenMfa
        clientId = clientIdVal
        challengeResponses = challengeResponsesOb
```

```
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val respondToAuthChallengeResult =
 identityProviderClient.adminRespondToAuthChallenge(adminRespondToAuthChallengeRequest)
        println("respondToAuthChallengeResult.getAuthenticationResult()
 ${respondToAuthChallengeResult.authenticationResult}")
    }
}
```

- Para obter detalhes da API, consulte a AdminRespondToAuthChallengereferência da API AWSSDK for Kotlin.

Inscrever um usuário

O exemplo de código a seguir mostra como inscrever um usuário no Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun signUp(clientIdVal: String?, userNameVal: String?, passwordVal: String?,
 emailVal: String?) {
    val userAttrs = AttributeType {
        name = "email"
        value = emailVal
    }

    val userAttrsList = mutableListOf<AttributeType>()
    userAttrsList.add(userAttrs)
    val signUpRequest = SignUpRequest {
        userAttributes = userAttrsList
        username = userNameVal
        clientId = clientIdVal
```

```
        password = passwordVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.signUp(signUpRequest)
        println("User has been signed up")
    }
}
```

- Para obter detalhes da API, consulte a SignUpreferência da API AWSSDK for Kotlin.

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkAuthMethod(clientIdVal: String, userNameVal: String, passwordVal:
 String, userPoolIdVal: String): AdminInitiateAuthResponse {
    val authParas = mutableMapOf<String, String>()
    authParas["USERNAME"] = userNameVal
    authParas["PASSWORD"] = passwordVal

    val authRequest = AdminInitiateAuthRequest {
        clientId = clientIdVal
        userPoolId = userPoolIdVal
        authParameters = authParas
        authFlow = AuthFlowType.AdminUserPasswordAuth
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
```

```
        val response = identityProviderClient.adminInitiateAuth(authRequest)
        println("Result Challenge is ${response.challengeName}")
        return response
    }
}
```

- Para obter detalhes da API, consulte a AdminInitiateAuthreferência da API AWSSDK for Kotlin.

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Verify the TOTP and register for MFA.
suspend fun verifyTOTP(sessionVal: String?, codeVal: String?) {
    val tokenRequest = VerifySoftwareTokenRequest {
        userCode = codeVal
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val verifyResponse =
 identityProviderClient.verifySoftwareToken(tokenRequest)
        println("The status of the token is ${verifyResponse.status}")
    }
}
```

- Para obter detalhes da API, consulte a VerifySoftwareTokenreferência da API AWSSDK for Kotlin.

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 TIP: To set up the required user pool, run the AWS Cloud Development
 Kit (AWS CDK) script provided in this GitHub repo at resources/cdk/
cognito_scenario_user_pool_with_mfa.

 This code example performs the following operations:

 1. Invokes the signUp method to sign up a user.
 2. Invokes the adminGetUser method to get the user's confirmation status.
 3. Invokes the ResendConfirmationCode method if the user requested another code.
 4. Invokes the confirmSignUp method.
 5. Invokes the initiateAuth to sign in. This results in being prompted to
 set up TOTP (time-based one-time password). (The response is “ChallengeName”:
 “MFA_SETUP”).
 6. Invokes the AssociateSoftwareToken method to generate a TOTP MFA private key.
 This can be used with Google Authenticator.
 7. Invokes the VerifySoftwareToken method to verify the TOTP and register for MFA.
```

```
 8. Invokes the AdminInitiateAuth to sign in again. This results in being prompted
 to submit a TOTP (Response: “ChallengeName”: “SOFTWARE_TOKEN_MFA”).
 9. Invokes the AdminRespondToAuthChallenge to get back a token.
 */

suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <clientId> <poolId>
        Where:
            clientId - The app client Id value that you can get from the AWS CDK
 script.
            poolId - The pool Id that you can get from the AWS CDK script.
    """

    if (args.size != 2) {
        println(usage)
        exitProcess(1)
    }

    val clientId = args[0]
    val poolId = args[1]

    // Use the console to get data from the user.
    println("*** Enter your use name")
    val inOb = Scanner(System.`in`)
    val userName = inOb.nextLine()
    println(userName)

    println("*** Enter your password")
    val password: String = inOb.nextLine()

    println("*** Enter your email")
    val email = inOb.nextLine()

    println("*** Signing up $userName")
    signUp(clientId, userName, password, email)

    println("*** Getting $userName in the user pool")
    getAdminUser(userName, poolId)

    println("*** Conformation code sent to $userName. Would you like to send a new
 code? (Yes/No)")
    val ans = inOb.nextLine()
```

```
    if (ans.compareTo("Yes") == 0) {
        println("*** Sending a new confirmation code")
        resendConfirmationCode(clientId, userName)
    }
    println("*** Enter the confirmation code that was emailed")
    val code = inOb.nextLine()
    confirmSignUp(clientId, code, userName)

    println("*** Rechecking the status of $userName in the user pool")
    getAdminUser(userName, poolId)

    val authResponse = checkAuthMethod(clientId, userName, password, poolId)
    val mySession = authResponse.session
    val newSession = getSecretForAppMFA(mySession)
    println("*** Enter the 6-digit code displayed in Google Authenticator")
    val myCode = inOb.nextLine()

    // Verify the TOTP and register for MFA.
    verifyTOTP(newSession, myCode)
    println("*** Re-enter a 6-digit code displayed in Google Authenticator")
    val mfaCode: String = inOb.nextLine()
    val authResponse1 = checkAuthMethod(clientId, userName, password, poolId)
    val session2 = authResponse1.session
    adminRespondToAuthChallenge(userName, clientId, mfaCode, session2)
}

suspend fun checkAuthMethod(clientIdVal: String, userNameVal: String, passwordVal:
 String, userPoolIdVal: String): AdminInitiateAuthResponse {
    val authParas = mutableMapOf<String, String>()
    authParas["USERNAME"] = userNameVal
    authParas["PASSWORD"] = passwordVal

    val authRequest = AdminInitiateAuthRequest {
        clientId = clientIdVal
        userPoolId = userPoolIdVal
        authParameters = authParas
        authFlow = AuthFlowType.AdminUserPasswordAuth
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminInitiateAuth(authRequest)
        println("Result Challenge is ${response.challengeName}")
```

```
        return response
    }
}

suspend fun resendConfirmationCode(clientIdVal: String?, userNameVal: String?) {
    val codeRequest = ResendConfirmationCodeRequest {
        clientId = clientIdVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.resendConfirmationCode(codeRequest)
        println("Method of delivery is " +
 (response.codeDeliveryDetails?.deliveryMedium))
    }
}

// Respond to an authentication challenge.
suspend fun adminRespondToAuthChallenge(userName: String, clientIdVal: String?,
 mfaCode: String, sessionVal: String?) {
    println("SOFTWARE_TOKEN_MFA challenge is generated")
    val challengeResponsesOb = mutableMapOf<String, String>()
    challengeResponsesOb["USERNAME"] = userName
    challengeResponsesOb["SOFTWARE_TOKEN_MFA_CODE"] = mfaCode

    val adminRespondToAuthChallengeRequest = AdminRespondToAuthChallengeRequest {
        challengeName = ChallengeNameType.SoftwareTokenMfa
        clientId = clientIdVal
        challengeResponses = challengeResponsesOb
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val respondToAuthChallengeResult =
 identityProviderClient.adminRespondToAuthChallenge(adminRespondToAuthChallengeRequest)
        println("respondToAuthChallengeResult.getAuthenticationResult()
 ${respondToAuthChallengeResult.authenticationResult}")
    }
}

// Verify the TOTP and register for MFA.
suspend fun verifyTOTP(sessionVal: String?, codeVal: String?) {
```

```
    val tokenRequest = VerifySoftwareTokenRequest {
        userCode = codeVal
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val verifyResponse =
 identityProviderClient.verifySoftwareToken(tokenRequest)
        println("The status of the token is ${verifyResponse.status}")
    }
}

suspend fun getSecretForAppMFA(sessionVal: String?): String? {
    val softwareTokenRequest = AssociateSoftwareTokenRequest {
        session = sessionVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val tokenResponse =
 identityProviderClient.associateSoftwareToken(softwareTokenRequest)
        val secretCode = tokenResponse.secretCode
        println("Enter this token into Google Authenticator")
        println(secretCode)
        return tokenResponse.session
    }
}

suspend fun confirmSignUp(clientIdVal: String?, codeVal: String?, userNameVal:
 String?) {
    val signUpRequest = ConfirmSignUpRequest {
        clientId = clientIdVal
        confirmationCode = codeVal
        username = userNameVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.confirmSignUp(signUpRequest)
        println("$userNameVal  was confirmed")
    }
}
```

```
suspend fun getAdminUser(userNameVal: String?, poolIdVal: String?) {
    val userRequest = AdminGetUserRequest {
        username = userNameVal
        userPoolId = poolIdVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        val response = identityProviderClient.adminGetUser(userRequest)
        println("User status ${response.userStatus}")
    }
}

suspend fun signUp(clientIdVal: String?, userNameVal: String?, passwordVal: String?,
 emailVal: String?) {
    val userAttrs = AttributeType {
        name = "email"
        value = emailVal
    }

    val userAttrsList = mutableListOf<AttributeType>()
    userAttrsList.add(userAttrs)
    val signUpRequest = SignUpRequest {
        userAttributes = userAttrsList
        username = userNameVal
        clientId = clientIdVal
        password = passwordVal
    }

    CognitoIdentityProviderClient { region = "us-east-1" }.use
 { identityProviderClient ->
        identityProviderClient.signUp(signUpRequest)
        println("User has been signed up")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge

- AssociateSoftwareToken
- ConfirmDevice
- ConfirmSignUp
- InitiateAuth
- ListUsers
- ResendConfirmationCode
- RespondToAuthChallenge
- SignUp
- VerifySoftwareToken

Exemplos do DynamoDB usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewTable(tableNameVal: String, key: String): String? {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef)
        keySchema = listOf(keySchemaVal)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        var tableArn: String
        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        tableArn = response.tableDescription!!.tableArn.toString()
        println("Table $tableArn is ready")
        return tableArn
    }
```

```
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWSSDK for Kotlin.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDynamoDBTable(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWSSDK for Kotlin.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDynamoDBItem(tableNameVal: String, keyName: String, keyVal:
 String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = DeleteItemRequest {
        tableName = tableNameVal
        key = keyToGet
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteItem(request)
        println("Item with key matching $keyVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWSSDK for Kotlin.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificItem(tableNameVal: String, keyName: String, keyVal: String) {
```

```
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}
```

- Para obter detalhes da API, consulte a GetItemreferência da API AWSSDK for Kotlin.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllTables() {
    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.listTables(ListTablesRequest {})
        response.tableNames?.forEach { tableName ->
            println("Table name is $tableName")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWSSDK for Kotlin.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putItemInTable(
    tableNameVal: String,
    key: String,
    keyVal: String,
    albumTitle: String,
    albumTitleValue: String,
    awards: String,
    awardVal: String,
    songTitle: String,
    songTitleVal: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()

    // Add all content to the table.
    itemValues[key] = AttributeValue.S(keyVal)
    itemValues[songTitle] = AttributeValue.S(songTitleVal)
    itemValues[albumTitle] = AttributeValue.S(albumTitleValue)
    itemValues[awards] = AttributeValue.S(awardVal)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
```

```
        println(" A new item was placed into $tableNameVal.")
    }
}
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWSSDK for Kotlin.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
suspend fun queryDynTable(
    tableNameVal: String,
    partitionKeyName: String,
    partitionKeyVal: String,
    partitionAlias: String
): Int {
    val attrNameAlias = mutableMapOf<String, String>()
    attrNameAlias[partitionAlias] = partitionKeyName

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.S(partitionKeyVal)

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
```

```
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Kotlin.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
suspend fun scanItems(tableNameVal: String) {
    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Kotlin.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateTableItem(
    tableNameVal: String,
    keyName: String,
    keyVal: String,
    name: String,
    updateVal: String
) {
    val itemKey = mutableMapOf<String, AttributeValue>()
    itemKey[keyName] = AttributeValue.S(keyVal)

    val updatedValues = mutableMapOf<String, AttributeValueUpdate>()
    updatedValues[name] = AttributeValueUpdate {
        value = AttributeValue.S(updateVal)
        action = AttributeAction.Put
    }

    val request = UpdateItemRequest {
        tableName = tableNameVal
        key = itemKey
        attributeUpdates = updatedValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.updateItem(request)
        println("Item in $tableNameVal was updated")
    }
}
```

- Para obter detalhes da API, consulte a UpdateItemreferência da API AWSSDK for Kotlin.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela do DynamoDB.

```
suspend fun createScenarioTable(tableNameVal: String, key: String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
```

```
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
 ${response.tableDescription?.tableArn}")
    }
}
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }
```

```
        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
        putMovie(tableName, year, title, info)
        t++
    }
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()
    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}
```

Obtenha um item de uma tabela.

```
suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
```

```
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}
```

Exemplo completo.

```
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
          <fileName>

        Where:
           fileName - The path to the moviedata.json you can download from the
 Amazon DynamoDB Developer Guide.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(1)
    }

    // Get the moviedata.json from the Amazon DynamoDB Developer Guide.
    val tableName = "Movies"
    val fileName = args[0]
    val partitionAlias = "#a"

    println("Creating an Amazon DynamoDB table named Movies with a key named id and
 a sort key named title.")
    createScenarioTable(tableName, "year")
    loadData(tableName, fileName)
    getMovie(tableName, "year", "1933")
    scanMovies(tableName)
    val count = queryMovieTable(tableName, "year", partitionAlias)
```

```
    println("There are $count Movies released in 2013.")
    deletIssuesTable(tableName)
}

suspend fun createScenarioTable(tableNameVal: String, key: String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
```

```
        println("The table was successfully created
 ${response.tableDescription?.tableArn}")
    }
}

// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
        putMovie(tableName, year, title, info)
        t++
    }
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()
    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }
```

```
    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}

suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}

suspend fun deletIssuesTable(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}

suspend fun queryMovieTable(
    tableNameVal: String,
    partitionKeyName: String,
    partitionAlias: String
): Int {
    val attrNameAlias = mutableMapOf<String, String>()
```

```
    attrNameAlias[partitionAlias] = "year"

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.N("2013")

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
    }
}

suspend fun scanMovies(tableNameVal: String) {
    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable

- DescribeTable
- GetItem
- PutItem
- Query
- Scan
- UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main() {
    val ddb = DynamoDbClient { region = "us-east-1" }
    val tableName = "MoviesPartiQBatch"
    println("Creating an Amazon DynamoDB table named $tableName with a key named id
 and a sort key named title.")
    createTablePartiQLBatch(ddb, tableName, "year")
    putRecordBatch(ddb)
    updateTableItemBatchBatch(ddb)
    deleteItemsBatch(ddb)
    deleteTablePartiQLBatch(tableName)
}
```

```
suspend fun createTablePartiQLBatch(ddb: DynamoDbClient, tableNameVal: String, key:
 String) {
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    val response = ddb.createTable(request)
    ddb.waitUntilTableExists { // suspend call
        tableName = tableNameVal
    }
    println("The table was successfully created
 ${response.tableDescription?.tableArn}")
}

suspend fun putRecordBatch(ddb: DynamoDbClient) {
```

```
    val sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE {'year':?, 'title' : ?,
 'info' : ?}"

    // Create three movies to add to the Amazon DynamoDB table.
    val parametersMovie1 = mutableListOf<AttributeValue>()
    parametersMovie1.add(AttributeValue.N("2022"))
    parametersMovie1.add(AttributeValue.S("My Movie 1"))
    parametersMovie1.add(AttributeValue.S("No Information"))

    val statementRequestMovie1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie1
    }

    // Set data for Movie 2.
    val parametersMovie2 = mutableListOf<AttributeValue>()
    parametersMovie2.add(AttributeValue.N("2022"))
    parametersMovie2.add(AttributeValue.S("My Movie 2"))
    parametersMovie2.add(AttributeValue.S("No Information"))

    val statementRequestMovie2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie2
    }

    // Set data for Movie 3.
    val parametersMovie3 = mutableListOf<AttributeValue>()
    parametersMovie3.add(AttributeValue.N("2022"))
    parametersMovie3.add(AttributeValue.S("My Movie 3"))
    parametersMovie3.add(AttributeValue.S("No Information"))

    val statementRequestMovie3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestMovie1)
    myBatchStatementList.add(statementRequestMovie2)
    myBatchStatementList.add(statementRequestMovie3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
```

```
    }
    val response = ddb.batchExecuteStatement(batchRequest)
    println("ExecuteStatement successful: " + response.toString())
    println("Added new movies using a batch command.")
}

suspend fun updateTableItemBatchBatch(ddb: DynamoDbClient) {
    val sqlStatement =
        "UPDATE MoviesPartiQBatch SET info = 'directors\":[\"Merian C. Cooper\",
\"Ernest B. Schoedsack' where year=? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
    parametersRec1.add(AttributeValue.N("2022"))
    parametersRec1.add(AttributeValue.S("My Movie 1"))
    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Update record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Update record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestRec1)
    myBatchStatementList.add(statementRequestRec2)
    myBatchStatementList.add(statementRequestRec3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
```

```
    }

    val response = ddb.batchExecuteStatement(batchRequest)
    println("ExecuteStatement successful: $response")
    println("Updated three movies using a batch command.")
    println("Items were updated!")
}

suspend fun deleteItemsBatch(ddb: DynamoDbClient) {
    // Specify three records to delete.
    val sqlStatement = "DELETE FROM MoviesPartiQBatch WHERE year = ? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
    parametersRec1.add(AttributeValue.N("2022"))
    parametersRec1.add(AttributeValue.S("My Movie 1"))

    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Specify record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Specify record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestRec1)
    myBatchStatementList.add(statementRequestRec2)
    myBatchStatementList.add(statementRequestRec3)
```

```
    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
    }

    ddb.batchExecuteStatement(batchRequest)
    println("Deleted three movies using a batch command.")
}

suspend fun deleteTablePartiQLBatch(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}
```

- Para obter detalhes da API, consulte a BatchExecuteStatementreferência da API AWSSDK for Kotlin.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
          <fileName>

        Where:
           fileName - The path to the moviedata.json you can download from the
 Amazon DynamoDB Developer Guide.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(1)
    }

    val ddb = DynamoDbClient { region = "us-east-1" }
    val tableName = "MoviesPartiQ"

    // Get the moviedata.json from the Amazon DynamoDB Developer Guide.
    val fileName = args[0]
    println("Creating an Amazon DynamoDB table named MoviesPartiQ with a key named
 id and a sort key named title.")
    createTablePartiQL(ddb, tableName, "year")
    loadDataPartiQL(ddb, fileName)

    println("******* Getting data from the MoviesPartiQ table.")
    getMoviePartiQL(ddb)

    println("******* Putting a record into the MoviesPartiQ table.")
    putRecordPartiQL(ddb)

    println("******* Updating a record.")
    updateTableItemPartiQL(ddb)

    println("******* Querying the movies released in 2013.")
    queryTablePartiQL(ddb)

    println("******* Deleting the MoviesPartiQ table.")
    deleteTablePartiQL(tableName)
}

suspend fun createTablePartiQL(ddb: DynamoDbClient, tableNameVal: String, key:
 String) {
```

```
    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    val response = ddb.createTable(request)
    ddb.waitUntilTableExists { // suspend call
        tableName = tableNameVal
    }
    println("The table was successfully created
 ${response.tableDescription?.tableArn}")
}

suspend fun loadDataPartiQL(ddb: DynamoDbClient, fileName: String) {
    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?,
 'info' : ?}"
    val parser = JsonFactory().createParser(File(fileName))
```

```
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode
    var t = 0

    while (iter.hasNext()) {
        if (t == 200) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()

        val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
        parameters.add(AttributeValue.N(year.toString()))
        parameters.add(AttributeValue.S(title))
        parameters.add(AttributeValue.S(info))

        executeStatementPartiQL(ddb, sqlStatement, parameters)
        println("Added Movie $title")
        parameters.clear()
        t++
    }
}

suspend fun getMoviePartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and title=?"
    val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
    parameters.add(AttributeValue.N("2012"))
    parameters.add(AttributeValue.S("The Perks of Being a Wallflower"))
    val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("ExecuteStatement successful: $response")
}

suspend fun putRecordPartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?,
 'info' : ?}"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2020"))
    parameters.add(AttributeValue.S("My Movie"))
    parameters.add(AttributeValue.S("No Info"))
    executeStatementPartiQL(ddb, sqlStatement, parameters)
```

```
    println("Added new movie.")
}

suspend fun updateTableItemPartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\":[\"Merian C.
 Cooper\",\"Ernest B. Schoedsack\' where year=? and title=?"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2013"))
    parameters.add(AttributeValue.S("The East"))
    executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("Item was updated!")
}

// Query the table where the year is 2013.
suspend fun queryTablePartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "SELECT * FROM MoviesPartiQ where year = ?"

    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2013"))
    val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("ExecuteStatement successful: $response")
}

suspend fun deleteTablePartiQL(tableNameVal: String) {
    val request = DeleteTableRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteTable(request)
        println("$tableNameVal was deleted")
    }
}

suspend fun executeStatementPartiQL(
    ddb: DynamoDbClient,
    statementVal: String,
    parametersVal: List<AttributeValue>
): ExecuteStatementResponse {
    val request = ExecuteStatementRequest {
        statement = statementVal
        parameters = parametersVal
    }
```

```
    return ddb.executeStatement(request)
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWSSDK for Kotlin.

Exemplos do Amazon EC2 usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2SecurityGroups(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
```

```
        val response = ec2.describeSecurityGroups(request)
        response.securityGroups?.forEach { group ->
            println("Found Security Group with id ${group.groupId}, vpc id
 ${group.vpcId} and description ${group.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico ao Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAllocateAddress(instanceIdVal: String?): String? {
    val allocateRequest = AllocateAddressRequest {
        domain = DomainType.Vpc
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val allocateResponse = ec2.allocateAddress(allocateRequest)
        val allocationIdVal = allocateResponse.allocationId
```

```
        val request = AssociateAddressRequest {
            instanceId = instanceIdVal
            allocationId = allocationIdVal
        }

        val associateResponse = ec2.associateAddress(request)
        return associateResponse.associationId
    }
}
```

- Para obter detalhes da API, consulte a AllocateAddressreferência da API AWSSDK for Kotlin.

Para associar um endereço IP elástico a uma instância

Os exemplos de código a seguir mostram como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun associateAddressSc(instanceIdVal: String?, allocationIdVal: String?):
 String? {
    val associateRequest = AssociateAddressRequest {
        instanceId = instanceIdVal
        allocationId = allocationIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val associateResponse = ec2.associateAddress(associateRequest)
        return associateResponse.associationId
    }
}
```

- Para obter detalhes da API, consulte a AssociateAddressreferência da API AWSSDK for Kotlin.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2SecurityGroup(groupNameVal: String?, groupDescVal: String?,
 vpcIdVal: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "0.0.0.0/0"
        }

        val ipPerm = IpPermission {
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
```

```
        }
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group $groupNameVal")
        return resp.groupId
    }
}
```

- Para obter detalhes da API, consulte a CreateSecurityGroupreferência da API AWSSDK for Kotlin.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2KeyPair(keyNameVal: String) {
    val request = CreateKeyPairRequest {
        keyName = keyNameVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.createKeyPair(request)
        println("The key ID is ${response.keyPairId}")
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyPairreferência da API AWSSDK for Kotlin.

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2Instance(name: String, amiId: String): String? {
    val request = RunInstancesRequest {
        imageId = amiId
        instanceType = InstanceType.T1Micro
        maxCount = 1
        minCount = 1
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.runInstances(request)
        val instanceId = response.instances?.get(0)?.instanceId
        val tag = Tag {
            key = "Name"
            value = name
        }

        val requestTags = CreateTagsRequest {
            resources = listOf(instanceId.toString())
            tags = listOf(tag)
        }
        ec2.createTags(requestTags)
        println("Successfully started EC2 Instance $instanceId based on AMI $amiId")
        return instanceId
    }
}
```

- Para obter detalhes da API, consulte a RunInstancesreferência da API AWSSDK for Kotlin.

Exclua um grupo de segurança

Os exemplos de código a seguir mostram como excluir um grupo de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteEC2SecGroup(groupIdVal: String) {
    val request = DeleteSecurityGroupRequest {
        groupId = groupIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteSecurityGroup(request)
        println("Successfully deleted Security Group with id $groupIdVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupreferência da API AWSSDK for Kotlin.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKeys(keyPair: String?) {
    val request = DeleteKeyPairRequest {
        keyName = keyPair
    }
```

```
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteKeyPair(request)
        println("Successfully deleted key pair named $keyPair")
    }
}
```

- Para obter detalhes da API, consulte a DeleteKeyPairreferência da API AWSSDK for Kotlin.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2Instances() {
    val request = DescribeInstancesRequest {
        maxResults = 6
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstances(request)
        response.reservations?.forEach { reservation ->
            reservation.instances?.forEach { instance ->
                println("Instance Id is ${instance.instanceId}")
                println("Image id is ${instance.imageId}")
                println("Instance type is ${instance.instanceType}")
                println("Instance state name is ${instance.state?.name}")
                println("monitoring information is ${instance.monitoring?.state}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWSSDK for Kotlin.

Desassociar um endereço IP elástico de uma instância

Os exemplos de código a seguir mostram como desassociar um endereço IP elástico de uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disassociateAddressSc(associationIdVal: String?) {
    val addressRequest = DisassociateAddressRequest {
        associationId = associationIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.disassociateAddress(addressRequest)
        println("You successfully disassociated the address!")
    }
}
```

- Para obter detalhes da API, consulte a DisassociateAddressreferência da API AWSSDK for Kotlin.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2SecurityGroups(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->

        val response = ec2.describeSecurityGroups(request)
        response.securityGroups?.forEach { group ->
            println("Found Security Group with id ${group.groupId}, vpc id
 ${group.vpcId} and description ${group.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWSSDK for Kotlin.

Obter dados sobre tipos de instâncias

O exemplo de código a seguir mostra como obter dados sobre tipos de instâncias do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Get a list of instance types.
```

```
suspend fun getInstanceTypesSc(): String {
    var instanceType = ""
    val filterObs = ArrayList<Filter>()
    val filter = Filter {
        name = "processor-info.supported-architecture"
        values = listOf("arm64")
    }

    filterObs.add(filter)
    val typesRequest = DescribeInstanceTypesRequest {
        filters = filterObs
        maxResults = 10
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstanceTypes(typesRequest)
        response.instanceTypes?.forEach { type ->
            println("The memory information of this type is
 ${type.memoryInfo?.sizeInMib}")
            println("Maximum number of network cards is
 ${type.networkInfo?.maximumNetworkCards}")
            instanceType = type.instanceType.toString()
        }
        return instanceType
    }
}
```

- Para obter detalhes da API, consulte a DescribeInstanceTypesreferência da API AWSSDK for Kotlin.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeEC2Keys() {
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeKeyPairs(DescribeKeyPairsRequest {})
        response.keyPairs?.forEach { keyPair ->
            println("Found key pair with name ${keyPair.keyName} and fingerprint
 ${ keyPair.keyFingerprint}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeKeyPairsreferência da API AWSSDK for Kotlin.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun releaseEC2AddressSc(allocId: String?) {
    val request = ReleaseAddressRequest {
        allocationId = allocId
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.releaseAddress(request)
        println("Successfully released Elastic IP address $allocId")
    }
}
```

- Para obter detalhes da API, consulte a ReleaseAddressreferência da API AWSSDK for Kotlin.

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createEC2SecurityGroupSc(groupNameVal: String?, groupDescVal: String?,
 vpcIdVal: String?, myIpAddress: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "$myIpAddress/0"
        }

        val ipPerm = IpPermission {
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
```

```
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
        }
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group $groupNameVal")
        return resp.groupId
    }
}
```

- Para obter detalhes da API, consulte a AuthorizeSecurityGroupIngressreferência da API AWSSDK for Kotlin.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startInstanceSc(instanceId: String) {
    val request = StartInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.startInstances(request)
        println("Waiting until instance $instanceId starts. This will take a few
 minutes.")
        ec2.waitUntilInstanceRunning { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully started instance $instanceId")
    }
}
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWSSDK for Kotlin.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun stopInstanceSc(instanceId: String) {
    val request = StopInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.stopInstances(request)
        println("Waiting until instance $instanceId stops. This will take a few
 minutes.")
        ec2.waitUntilInstanceStopped { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully stopped instance $instanceId")
    }
}
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWSSDK for Kotlin.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun terminateEC2(instanceID: String) {
    val request = TerminateInstancesRequest {
        instanceIds = listOf(instanceID)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.terminateInstances(request)
        response.terminatingInstances?.forEach { instance ->
            println("The ID of the terminated instance is ${instance.instanceId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a TerminateInstancesreferência da API AWSSDK for Kotlin.

Cenários

Começar a usar instâncias

O código de exemplo a seguir mostra como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.
- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.
- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This Kotlin example performs the following tasks:

 1. Creates an RSA key pair and saves the private key data as a .pem file.
 2. Lists key pairs.
 3. Creates a security group for the default VPC.
 4. Displays security group information.
 5. Gets a list of Amazon Linux 2 AMIs and selects one.
 6. Gets more information about the image.
 7. Gets a list of instance types that are compatible with the selected AMI’s
 architecture.
 8. Creates an instance with the key pair, security group, AMI, and an instance
 type.
 9. Displays information about the instance.
 10. Stops the instance and waits for it to stop.
 11. Starts the instance and waits for it to start.
 12. Allocates an Elastic IP address and associates it with the instance.
 13. Displays SSH connection info for the instance.
 14. Disassociates and deletes the Elastic IP address.
 15. Terminates the instance.
 16. Deletes the security group.
 17. Deletes the key pair.
 */

val DASHES = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
```

```
            <keyName> <fileName> <groupName> <groupDesc> <vpcId> <myIpAddress>

        Where:
            keyName - A key pair name (for example, TestKeyPair).
            fileName - A file name where the key information is written to.
            groupName - The name of the security group.
            groupDesc - The description of the security group.
            vpcId - A VPC ID. You can get this value from the AWS Management
 Console.
            myIpAddress - The IP address of your development machine.

"""

    if (args.size != 6) {
        println(usage)
        exitProcess(0)
    }

    val keyName = args[0]
    val fileName = args[1]
    val groupName = args[2]
    val groupDesc = args[3]
    val vpcId = args[4]
    val myIpAddress = args[5]
    var newInstanceId: String? = ""

    println(DASHES)
    println("Welcome to the Amazon EC2 example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create an RSA key pair and save the private key material as a .pem
 file.")
    createKeyPairSc(keyName, fileName)
    println(DASHES)

    println(DASHES)
    println("2. List key pairs.")
    describeEC2KeysSc()
    println(DASHES)

    println(DASHES)
    println("3. Create a security group.")
    val groupId = createEC2SecurityGroupSc(groupName, groupDesc, vpcId, myIpAddress)
```

```
    println(DASHES)

    println(DASHES)
    println("4. Display security group info for the newly created security group.")
    describeSecurityGroupsSc(groupId.toString())
    println(DASHES)

    println(DASHES)
    println("5. Get a list of Amazon Linux 2 AMIs and select one with amzn2 in the
name.")
    val instanceId = getParaValuesSc()
    if (instanceId == "") {
        println("The instance Id value isn't valid.")
        exitProcess(0)
    }
    println("The instance Id is $instanceId.")
    println(DASHES)

    println(DASHES)
    println("6. Get more information about an amzn2 image and return the AMI
value.")
    val amiValue = instanceId?.let { describeImageSc(it) }
    if (instanceId == "") {
        println("The instance Id value is invalid.")
        exitProcess(0)
    }
    println("The AMI value is $amiValue.")
    println(DASHES)

    println(DASHES)
    println("7. Get a list of instance types.")
    val instanceType = getInstanceTypesSc()
    println(DASHES)

    println(DASHES)
    println("8. Create an instance.")
    if (amiValue != null) {
        newInstanceId = runInstanceSc(instanceType, keyName, groupName, amiValue)
        println("The instance Id is $newInstanceId")
    }
    println(DASHES)

    println(DASHES)
    println("9. Display information about the running instance. ")
```

```
    var ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("10.  Stop the instance.")
    if (newInstanceId != null) {
        stopInstanceSc(newInstanceId)
    }
    println(DASHES)

    println(DASHES)
    println("11.  Start the instance.")
    if (newInstanceId != null) {
        startInstanceSc(newInstanceId)
    }
    ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("12. Allocate an Elastic IP address and associate it with the
 instance.")
    val allocationId = allocateAddressSc()
    println("The allocation Id value is $allocationId")
    val associationId = associateAddressSc(newInstanceId, allocationId)
    println("The associate Id value is $associationId")
    println(DASHES)

    println(DASHES)
    println("13. Describe the instance again.")
    ipAddress = describeEC2InstancesSc(newInstanceId)
    println("You can SSH to the instance using this command:")
    println("ssh -i " + fileName + "ec2-user@" + ipAddress)
    println(DASHES)

    println(DASHES)
    println("14. Disassociate and release the Elastic IP address.")
    disassociateAddressSc(associationId)
    releaseEC2AddressSc(allocationId)
    println(DASHES)
```

```
    println(DASHES)
    println("15. Terminate the instance and use a waiter.")
    if (newInstanceId != null) {
        terminateEC2Sc(newInstanceId)
    }
    println(DASHES)

    println(DASHES)
    println("16. Delete the security group.")
    if (groupId != null) {
        deleteEC2SecGroupSc(groupId)
    }
    println(DASHES)

    println(DASHES)
    println("17. Delete the key pair.")
    deleteKeysSc(keyName)
    println(DASHES)

    println(DASHES)
    println("You successfully completed the Amazon EC2 scenario.")
    println(DASHES)
}

suspend fun deleteKeysSc(keyPair: String) {
    val request = DeleteKeyPairRequest {
        keyName = keyPair
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteKeyPair(request)
        println("Successfully deleted key pair named $keyPair")
    }
}

suspend fun deleteEC2SecGroupSc(groupIdVal: String) {
    val request = DeleteSecurityGroupRequest {
        groupId = groupIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.deleteSecurityGroup(request)
        println("Successfully deleted security group with Id $groupIdVal")
    }
}
```

```
suspend fun terminateEC2Sc(instanceIdVal: String) {
    val ti = TerminateInstancesRequest {
        instanceIds = listOf(instanceIdVal)
    }
    println("Wait for the instance to terminate. This will take a few minutes.")
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.terminateInstances(ti)
        ec2.waitUntilInstanceTerminated { // suspend call
            instanceIds = listOf(instanceIdVal)
        }
        println("$instanceIdVal is terminated!")
    }
}

suspend fun releaseEC2AddressSc(allocId: String?) {
    val request = ReleaseAddressRequest {
        allocationId = allocId
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.releaseAddress(request)
        println("Successfully released Elastic IP address $allocId")
    }
}

suspend fun disassociateAddressSc(associationIdVal: String?) {
    val addressRequest = DisassociateAddressRequest {
        associationId = associationIdVal
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.disassociateAddress(addressRequest)
        println("You successfully disassociated the address!")
    }
}

suspend fun associateAddressSc(instanceIdVal: String?, allocationIdVal: String?):
 String? {
    val associateRequest = AssociateAddressRequest {
        instanceId = instanceIdVal
        allocationId = allocationIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val associateResponse = ec2.associateAddress(associateRequest)
```

```
        return associateResponse.associationId
    }
}

suspend fun allocateAddressSc(): String? {
    val allocateRequest = AllocateAddressRequest {
        domain = DomainType.Vpc
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val allocateResponse = ec2.allocateAddress(allocateRequest)
        return allocateResponse.allocationId
    }
}

suspend fun startInstanceSc(instanceId: String) {
    val request = StartInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.startInstances(request)
        println("Waiting until instance $instanceId starts. This will take a few
 minutes.")
        ec2.waitUntilInstanceRunning { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully started instance $instanceId")
    }
}

suspend fun stopInstanceSc(instanceId: String) {
    val request = StopInstancesRequest {
        instanceIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        ec2.stopInstances(request)
        println("Waiting until instance $instanceId stops. This will take a few
 minutes.")
        ec2.waitUntilInstanceStopped { // suspend call
            instanceIds = listOf(instanceId)
        }
        println("Successfully stopped instance $instanceId")
    }
```

```
}

suspend fun describeEC2InstancesSc(newInstanceId: String?): String {
    var pubAddress = ""
    var isRunning = false
    val request = DescribeInstancesRequest {
        instanceIds = listOf(newInstanceId.toString())
    }

    while (!isRunning) {
        Ec2Client { region = "us-west-2" }.use { ec2 ->
            val response = ec2.describeInstances(request)
            val state =
 response.reservations?.get(0)?.instances?.get(0)?.state?.name?. value
            if (state != null) {
                if (state.compareTo("running") == 0) {
                    println("Image id is
 ${response.reservations!!.get(0).instances?.get(0)?.imageId}")
                    println("Instance type is
 ${response.reservations!!.get(0).instances?.get(0)?.instanceType}")
                    println("Instance state is
 ${response.reservations!!.get(0).instances?.get(0)?.state}")
                    pubAddress =
 response.reservations!!.get(0).instances?.get(0)?.publicIpAddress.toString()
                    println("Instance address is $pubAddress")
                    isRunning = true
                }
            }
        }
    }
    return pubAddress
}

suspend fun runInstanceSc(instanceTypeVal: String, keyNameVal: String, groupNameVal:
 String, amiIdVal: String): String {
    val runRequest = RunInstancesRequest {
        instanceType = InstanceType.fromValue(instanceTypeVal)
        keyName = keyNameVal
        securityGroups = listOf(groupNameVal)
        maxCount = 1
        minCount = 1
        imageId = amiIdVal
    }
```

```
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.runInstances(runRequest)
        val instanceId = response.instances?.get(0)?.instanceId
        println("Successfully started EC2 Instance $instanceId based on AMI
 $amiIdVal")
        return instanceId.toString()
    }
}

// Get a list of instance types.
suspend fun getInstanceTypesSc(): String {
    var instanceType = ""
    val filterObs = ArrayList<Filter>()
    val filter = Filter {
        name = "processor-info.supported-architecture"
        values = listOf("arm64")
    }

    filterObs.add(filter)
    val typesRequest = DescribeInstanceTypesRequest {
        filters = filterObs
        maxResults = 10
    }
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeInstanceTypes(typesRequest)
        response.instanceTypes?.forEach { type ->
            println("The memory information of this type is
 ${type.memoryInfo?.sizeInMib}")
            println("Maximum number of network cards is
 ${type.networkInfo?.maximumNetworkCards}")
            instanceType = type.instanceType.toString()
        }
        return instanceType
    }
}

// Display the Description field that corresponds to the instance Id value.
suspend fun describeImageSc(instanceId: String): String? {
    val imagesRequest = DescribeImagesRequest {
        imageIds = listOf(instanceId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeImages(imagesRequest)
```

```
        println("The description of the first image is
 ${response.images?.get(0)?.description}")
        println("The name of the first image is  ${response.images?.get(0)?.name}")

        // Return the image Id value.
        return response.images?.get(0)?.imageId
    }
}

// Get the Id value of an instance with amzn2 in the name.
suspend fun getParaValuesSc(): String? {
    val parameterRequest = GetParametersByPathRequest {
        path = "/aws/service/ami-amazon-linux-latest"
    }

    SsmClient { region = "us-west-2" }.use { ssmClient ->
        val response = ssmClient.getParametersByPath(parameterRequest)
        response.parameters?.forEach { para ->
            println("The name of the para is: ${para.name}")
            println("The type of the para is: ${para.type}")
            println("")
            if (para.name?.let { filterName(it) } == true) {
                return para.value
            }
        }
    }
    return ""
}

fun filterName(name: String): Boolean {
    val parts = name.split("/").toTypedArray()
    val myValue = parts[4]
    return myValue.contains("amzn2")
}

suspend fun describeSecurityGroupsSc(groupId: String) {
    val request = DescribeSecurityGroupsRequest {
        groupIds = listOf(groupId)
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeSecurityGroups(request)
        for (group in response.securityGroups!!) {
```

```
            println("Found Security Group with id " + group.groupId.toString() + "
 and group VPC " + group.vpcId)
        }
    }
}

suspend fun createEC2SecurityGroupSc(groupNameVal: String?, groupDescVal: String?,
 vpcIdVal: String?, myIpAddress: String?): String? {
    val request = CreateSecurityGroupRequest {
        groupName = groupNameVal
        description = groupDescVal
        vpcId = vpcIdVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val resp = ec2.createSecurityGroup(request)
        val ipRange = IpRange {
            cidrIp = "$myIpAddress/0"
        }

        val ipPerm = IpPermission {
            ipProtocol = "tcp"
            toPort = 80
            fromPort = 80
            ipRanges = listOf(ipRange)
        }

        val ipPerm2 = IpPermission {
            ipProtocol = "tcp"
            toPort = 22
            fromPort = 22
            ipRanges = listOf(ipRange)
        }

        val authRequest = AuthorizeSecurityGroupIngressRequest {
            groupName = groupNameVal
            ipPermissions = listOf(ipPerm, ipPerm2)
        }
        ec2.authorizeSecurityGroupIngress(authRequest)
        println("Successfully added ingress policy to Security Group $groupNameVal")
        return resp.groupId
    }
}
```

```
suspend fun describeEC2KeysSc() {
    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.describeKeyPairs(DescribeKeyPairsRequest {})
        response.keyPairs?.forEach { keyPair ->
            println("Found key pair with name ${keyPair.keyName} and fingerprint
 ${ keyPair.keyFingerprint}")
        }
    }
}

suspend fun createKeyPairSc(keyNameVal: String, fileNameVal: String) {
    val request = CreateKeyPairRequest {
        keyName = keyNameVal
    }

    Ec2Client { region = "us-west-2" }.use { ec2 ->
        val response = ec2.createKeyPair(request)
        val content = response.keyMaterial
        if (content != null) {
            File(fileNameVal).writeText(content)
        }
        println("Successfully created key pair named $keyNameVal")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup
  - DescribeImages
  - DescribeInstanceTypes
  - DescribeInstances
  - DescribeKeyPairs

- DescribeSecurityGroups
- DisassociateAddress
- ReleaseAddress
- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

OpenSearch Exemplos de serviços usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin with Service. OpenSearch

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um domínio

O exemplo de código a seguir mostra como criar um domínio OpenSearch de serviço.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewDomain(domainNameVal: String?) {

    val clusterConfigOb = ClusterConfig {
        dedicatedMasterEnabled = true
        dedicatedMasterCount = 3
        dedicatedMasterType =
 OpenSearchPartitionInstanceType.fromValue("t2.small.search")
        instanceType = OpenSearchPartitionInstanceType.fromValue("t2.small.search")
        instanceCount = 5
    }

    val ebsOptionsOb = EbsOptions {
        ebsEnabled = true
        volumeSize = 10
        volumeType = VolumeType.Gp2
    }

    val encryptionOptionsOb = NodeToNodeEncryptionOptions {
        enabled = true
    }

    val request = CreateDomainRequest {
        domainName = domainNameVal
        engineVersion = "OpenSearch_1.0"
        clusterConfig = clusterConfigOb
        ebsOptions = ebsOptionsOb
        nodeToNodeEncryptionOptions = encryptionOptionsOb
    }

    println("Sending domain creation request...")
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val createResponse = searchClient.createDomain(request)
        println("Domain status is ${createResponse.domainStatus}")
        println("Domain Id is ${createResponse.domainStatus?.domainId}")
```

```
    }
}
```

- Para obter detalhes da API, consulte a CreateDomainreferência da API AWSSDK for Kotlin.

Excluir um domínio

O exemplo de código a seguir mostra como excluir um domínio OpenSearch de serviço.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSpecificDomain(domainNameVal: String) {

    val request = DeleteDomainRequest {
        domainName = domainNameVal
    }
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        searchClient.deleteDomain(request)
        println("$domainNameVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteDomainreferência da API AWSSDK for Kotlin.

Listar domínios

O exemplo de código a seguir mostra como listar domínios OpenSearch de serviço.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllDomains() {

    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val response: ListDomainNamesResponse =
 searchClient.listDomainNames(ListDomainNamesRequest {})
        response.domainNames?.forEach { domain ->
            println("Domain name is " + domain.domainName)
        }
    }
}
```

- Para obter detalhes da API, consulte a ListDomainNamesreferência da API AWSSDK for Kotlin.

Modificar uma configuração de cluster

O exemplo de código a seguir mostra como modificar a configuração de um cluster de um domínio de OpenSearch serviço.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateSpecificDomain(domainNameVal: String?) {

    val clusterConfigOb = ClusterConfig {
        instanceCount = 3
```

```
    }

    val request = UpdateDomainConfigRequest {
        domainName = domainNameVal
        clusterConfig = clusterConfigOb
    }

    println("Sending domain update request...")
    OpenSearchClient { region = "us-east-1" }.use { searchClient ->
        val updateResponse = searchClient.updateDomainConfig(request)
        println("Domain update response from Amazon OpenSearch Service:")
        println(updateResponse.toString())
    }
}
```

- Para obter detalhes da API, consulte a UpdateDomainConfigreferência da API AWSSDK for Kotlin.

EventBridge exemplos usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com. EventBridge

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá EventBridge

O exemplo de código a seguir mostra como começar a usar o EventBridge.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.eventbridge.EventBridgeClient
import aws.sdk.kotlin.services.eventbridge.model.ListEventBusesRequest
import aws.sdk.kotlin.services.eventbridge.model.ListEventBusesResponse

suspend fun main() {
    listBusesHello()
}

suspend fun listBusesHello() {
    val request = ListEventBusesRequest {
        limit = 10
    }

    EventBridgeClient { region = "us-west-2" }.use { eventBrClient ->
        val response: ListEventBusesResponse = eventBrClient.listEventBuses(request)
        response.eventBuses?.forEach { bus ->
            println("The name of the event bus is ${bus.name}")
            println("The ARN of the event bus is ${bus.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListEventBusesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Adicionar destino

O exemplo de código a seguir mostra como adicionar um alvo a um EventBridge evento da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Add a rule that triggers an SNS target when a file is uploaded to an S3 bucket.
suspend fun addSnsEventRule(ruleName: String?, topicArn: String?, topicName: String,
 eventRuleName: String, bucketName: String) {
    val targetID = UUID.randomUUID().toString()
    val myTarget = Target {
        id = targetID
        arn = topicArn
    }

    val targetsOb = mutableListOf<Target>()
    targetsOb.add(myTarget)

    val request = PutTargetsRequest {
        eventBusName = null
        targets = targetsOb
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(request)
        println("Added event rule $eventRuleName with Amazon SNS target $topicName
 for bucket $bucketName.")
    }
}
```

Adicionar um transformador de entrada a um destino para uma regra.

```
suspend fun updateCustomRuleTargetWithTransform(topicArn: String?, ruleName:
 String?) {
    val targetId = UUID.randomUUID().toString()

    val inputTransformerOb = InputTransformer {
        inputTemplate = "\"Notification: sample event was received.\""
    }

    val target = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransformerOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
        targets = listOf(target)
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}
```

- Para obter detalhes da API, consulte a PutTargetsreferência da API AWSSDK for Kotlin.

Criar uma regra

O exemplo de código a seguir mostra como criar uma EventBridge regra da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma regra agendada

```
suspend fun createScRule(ruleName: String?, cronExpression: String?) {
    val ruleRequest = PutRuleRequest {
        name = ruleName
        eventBusName = "default"
        scheduleExpression = cronExpression
        state = RuleState.Enabled
        description = "A test rule that runs on a schedule created by the Kotlin
 API"
    }

    EventBridgeClient { region = "us-west-2" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}
```

Criar uma regra que seja acionada quando um objeto é adicionado a um bucket do Amazon Simple Storage Service.

```
// Create a new event rule that triggers when an Amazon S3 object is created in a
 bucket.
suspend fun addEventRule(roleArnVal: String?, bucketName: String, eventRuleName:
 String?) {
    val pattern = """{
        "source": ["aws.s3"],
        "detail-type": ["Object Created"],
        "detail": {
        "bucket": {
            "name": ["$bucketName"]
            }
        }
    }"""

    val ruleRequest = PutRuleRequest {
        description = "Created by using the AWS SDK for Kotlin"
        name = eventRuleName
        eventPattern = pattern
        roleArn = roleArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
```

```
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}
```

- Para obter detalhes da API, consulte a PutRulereferência da API AWSSDK for Kotlin.

Excluir uma regra

O exemplo de código a seguir mostra como excluir uma EventBridge regra da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteRuleByName(ruleName: String?) {
    val ruleRequest = DeleteRuleRequest {
        name = ruleName
    }
    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.deleteRule(ruleRequest)
        println("Successfully deleted the rule")
    }
}
```

- Para obter detalhes da API, consulte a DeleteRulereferência da API AWSSDK for Kotlin.

Descrever uma regra

O exemplo de código a seguir mostra como descrever uma EventBridge regra da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkRule(eventRuleName: String?) {
    val ruleRequest = DescribeRuleRequest {
        name = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.describeRule(ruleRequest)
        println("The state of the rule is $response")
    }
}
```

- Para obter detalhes da API, consulte a DescribeRulereferência da API AWSSDK for Kotlin.

Desabilitar uma regra

O exemplo de código a seguir mostra como desativar uma EventBridge regra da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
```

```
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}
```

- Para obter detalhes da API, consulte a DisableRulereferência da API AWSSDK for Kotlin.

Habilitar uma regra

O exemplo de código a seguir mostra como habilitar uma EventBridge regra da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
```

```
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}
```

- Para obter detalhes da API, consulte a EnableRulereferência da API AWSSDK for Kotlin.

Listar nomes de regras para um destino

O exemplo de código a seguir mostra como listar nomes de EventBridge regras da Amazon para um alvo.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTargetRules(topicArnVal: String?) {
    val ruleNamesByTargetRequest = ListRuleNamesByTargetRequest {
        targetArn = topicArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest)
        response.ruleNames?.forEach { rule ->
            println("The rule name is $rule")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListRuleNamesByTargetreferência da API AWSSDK for Kotlin.

Listar regras

O exemplo de código a seguir mostra como listar EventBridge as regras da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listRules() {
    val rulesRequest = ListRulesRequest {
        eventBusName = "default"
        limit = 10
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRules(rulesRequest)
        response.rules?.forEach { rule ->
            println("The rule name is ${rule.name}")
            println("The rule ARN is ${rule.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListRulesreferência da API AWSSDK for Kotlin.

Listar destinos para uma regra

O exemplo de código a seguir mostra como listar EventBridge alvos da Amazon para uma regra.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTargets(ruleName: String?) {
    val ruleRequest = ListTargetsByRuleRequest {
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(ruleRequest)
        response.targets?.forEach { target ->
            println("Target ARN: ${target.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListTargetsByRulereferência da API AWSSDK for Kotlin.

Remover destinos de uma regra

O exemplo de código a seguir mostra como remover EventBridge alvos da Amazon de uma regra.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteTargetsFromRule(eventRuleName: String?) {
    // First, get all targets that will be deleted.
    val request = ListTargetsByRuleRequest {
        rule = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(request)
        val allTargets = response.targets

        // Get all targets and delete them.
        if (allTargets != null) {
            for (myTarget in allTargets) {
```

```
                val removeTargetsRequest = RemoveTargetsRequest {
                    rule = eventRuleName
                    ids = listOf(myTarget.id.toString())
                }
                eventBrClient.removeTargets(removeTargetsRequest)
                println("Successfully removed the target")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a RemoveTargetsreferência da API AWSSDK for Kotlin.

Enviar eventos

O exemplo de código a seguir mostra como enviar EventBridge eventos da Amazon.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun triggerCustomRule(email: String) {
    val json = "{" +
        "\"UserEmail\": \"" + email + "\"," +
        "\"Message\": \"This event was generated by example code.\"" +
        "\"UtcTime\": \"Now.\"" +
        "}"

    val entry = PutEventsRequestEntry {
        source = "ExampleSource"
        detail = json
        detailType = "ExampleType"
    }

    val eventsRequest = PutEventsRequest {
        this.entries = listOf(entry)
    }
```

```
    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putEvents(eventsRequest)
    }
}
```

- Para obter detalhes da API, consulte a PutEventsreferência da API AWSSDK for Kotlin.

Cenários

Conceitos básicos de regras e destinos

O código de exemplo a seguir mostra como:

- Criar uma regra e adicione um destino a ela.
- Habilitar e desabilitar regras.
- Listar e atualizar regras e destinos.
- Enviar eventos e limpar os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/*
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This Kotlin example performs the following tasks with Amazon EventBridge:

 1. Creates an AWS Identity and Access Management (IAM) role to use with Amazon
 EventBridge.
```

```
 2. Creates an Amazon Simple Storage Service (Amazon S3) bucket with EventBridge
 events enabled.
 3. Creates a rule that triggers when an object is uploaded to Amazon S3.
 4. Lists rules on the event bus.
 5. Creates a new Amazon Simple Notification Service (Amazon SNS) topic and lets the
 user subscribe to it.
 6. Adds a target to the rule that sends an email to the specified topic.
 7. Creates an EventBridge event that sends an email when an Amazon S3 object is
 created.
 8. Lists targets.
 9. Lists the rules for the same target.
 10. Triggers the rule by uploading a file to the S3 bucket.
 11. Disables a specific rule.
 12. Checks and prints the state of the rule.
 13. Adds a transform to the rule to change the text of the email.
 14. Enables a specific rule.
 15. Triggers the updated rule by uploading a file to the S3 bucket.
 16. Updates the rule to a custom rule pattern.
 17. Sends an event to trigger the rule.
 18. Cleans up resources.
*/
val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <roleName> <bucketName> <topicName> <eventRuleName>

    Where:
        roleName - The name of the role to create.
        bucketName - The Amazon Simple Storage Service (Amazon S3) bucket name to
 create.
        topicName - The name of the Amazon Simple Notification Service (Amazon SNS)
 topic to create.
        eventRuleName - The Amazon EventBridge rule name to create.
    """
    val polJSON = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": \"events.amazonaws.com\"" +
        "}," +
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
```

```
        "}"

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val sc = Scanner(System.`in`)
    val roleName = args[0]
    val bucketName = args[1]
    val topicName = args[2]
    val eventRuleName = args[3]

    println(DASHES)
    println("Welcome to the Amazon EventBridge example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create an AWS Identity and Access Management (IAM) role to use with
 Amazon EventBridge.")
    val roleArn = createIAMRole(roleName, polJSON)
    println(DASHES)

    println(DASHES)
    println("2. Create an S3 bucket with EventBridge events enabled.")
    if (checkBucket(bucketName)) {
        println("$bucketName already exists. Ending this scenario.")
        exitProcess(1)
    }

    createBucket(bucketName)
    delay(3000)
    setBucketNotification(bucketName)
    println(DASHES)

    println(DASHES)
    println("3. Create a rule that triggers when an object is uploaded to Amazon
 S3.")
    delay(10000)
    addEventRule(roleArn, bucketName, eventRuleName)
    println(DASHES)

    println(DASHES)
    println("4. List rules on the event bus.")
```

```
    listRules()
    println(DASHES)

    println(DASHES)
    println("5. Create a new SNS topic for testing and let the user subscribe to the
topic.")
    val topicArn = createSnsTopic(topicName)
    println(DASHES)

    println(DASHES)
    println("6. Add a target to the rule that sends an email to the specified
topic.")
    println("Enter your email to subscribe to the Amazon SNS topic:")
    val email = sc.nextLine()
    subEmail(topicArn, email)
    println("Use the link in the email you received to confirm your subscription.
Then press Enter to continue.")
    sc.nextLine()
    println(DASHES)

    println(DASHES)
    println("7. Create an EventBridge event that sends an email when an Amazon S3
object is created.")
    addSnsEventRule(eventRuleName, topicArn, topicName, eventRuleName, bucketName)
    println(DASHES)

    println(DASHES)
    println("8. List targets.")
    listTargets(eventRuleName)
    println(DASHES)

    println(DASHES)
    println(" 9. List the rules for the same target.")
    listTargetRules(topicArn)
    println(DASHES)

    println(DASHES)
    println("10. Trigger the rule by uploading a file to the S3 bucket.")
    println("Press Enter to continue.")
    sc.nextLine()
    uploadTextFiletoS3(bucketName)
    println(DASHES)

    println(DASHES)
```

```
    println("11. Disable a specific rule.")
    changeRuleState(eventRuleName, false)
    println(DASHES)

    println(DASHES)
    println("12. Check and print the state of the rule.")
    checkRule(eventRuleName)
    println(DASHES)

    println(DASHES)
    println("13. Add a transform to the rule to change the text of the email.")
    updateSnsEventRule(topicArn, eventRuleName)
    println(DASHES)

    println(DASHES)
    println("14. Enable a specific rule.")
    changeRuleState(eventRuleName, true)
    println(DASHES)

    println(DASHES)
    println("15. Trigger the updated rule by uploading a file to the S3 bucket.")
    println("Press Enter to continue.")
    sc.nextLine()
    uploadTextFiletoS3(bucketName)
    println(DASHES)

    println(DASHES)
    println("16. Update the rule to a custom rule pattern.")
    updateToCustomRule(eventRuleName)
    println("Updated event rule $eventRuleName to use a custom pattern.")
    updateCustomRuleTargetWithTransform(topicArn, eventRuleName)
    println("Updated event target $topicArn.")
    println(DASHES)

    println(DASHES)
    println("17. Send an event to trigger the rule. This will trigger a subscription
email.")
    triggerCustomRule(email)
    println("Events have been sent. Press Enter to continue.")
    sc.nextLine()
    println(DASHES)

    println(DASHES)
    println("18. Clean up resources.")
```

```
    println("Do you want to clean up resources (y/n)")
    val ans = sc.nextLine()
    if (ans.compareTo("y") == 0) {
        cleanupResources(topicArn, eventRuleName, bucketName, roleName)
    } else {
        println("The resources will not be cleaned up. ")
    }
    println(DASHES)

    println(DASHES)
    println("The Amazon EventBridge example scenario has successfully completed.")
    println(DASHES)
}

suspend fun cleanupResources(topicArn: String?, eventRuleName: String?, bucketName:
 String?, roleName: String?) {
    println("Removing all targets from the event rule.")
    deleteTargetsFromRule(eventRuleName)
    deleteRuleByName(eventRuleName)
    deleteSNSTopic(topicArn)
    deleteS3Bucket(bucketName)
    deleteRole(roleName)
}

suspend fun deleteRole(roleNameVal: String?) {
    val policyArnVal = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess"
    val policyRequest = DetachRolePolicyRequest {
        policyArn = policyArnVal
        roleName = roleNameVal
    }
    IamClient { region = "us-east-1" }.use { iam ->
        iam.detachRolePolicy(policyRequest)
        println("Successfully detached policy $policyArnVal from role $roleNameVal")

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
            roleName = roleNameVal
        }

        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}
```

```
suspend fun deleteS3Bucket(bucketName: String?) {
    // Remove all the objects from the S3 bucket.
    val listObjects = ListObjectsRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        val res = s3Client.listObjects(listObjects)
        val myObjects = res.contents
        val toDelete = mutableListOf<ObjectIdentifier>()

        if (myObjects != null) {
            for (myValue in myObjects) {
                toDelete.add(
                    ObjectIdentifier {
                        key = myValue.key
                    }
                )
            }
        }

        val delOb = Delete {
            objects = toDelete
        }

        val dor = DeleteObjectsRequest {
            bucket = bucketName
            delete = delOb
        }
        s3Client.deleteObjects(dor)

        // Delete the S3 bucket.
        val deleteBucketRequest = DeleteBucketRequest {
            bucket = bucketName
        }
        s3Client.deleteBucket(deleteBucketRequest)
        println("You have deleted the bucket and the objects")
    }
}

// Delete the SNS topic.
suspend fun deleteSNSTopic(topicArnVal: String?) {
    val request = DeleteTopicRequest {
        topicArn = topicArnVal
    }
```

```
    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.deleteTopic(request)
        println(" $topicArnVal was deleted.")
    }
}

suspend fun deleteRuleByName(ruleName: String?) {
    val ruleRequest = DeleteRuleRequest {
        name = ruleName
    }
    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.deleteRule(ruleRequest)
        println("Successfully deleted the rule")
    }
}

suspend fun deleteTargetsFromRule(eventRuleName: String?) {
    // First, get all targets that will be deleted.
    val request = ListTargetsByRuleRequest {
        rule = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(request)
        val allTargets = response.targets

        // Get all targets and delete them.
        if (allTargets != null) {
            for (myTarget in allTargets) {
                val removeTargetsRequest = RemoveTargetsRequest {
                    rule = eventRuleName
                    ids = listOf(myTarget.id.toString())
                }
                eventBrClient.removeTargets(removeTargetsRequest)
                println("Successfully removed the target")
            }
        }
    }
}

suspend fun triggerCustomRule(email: String) {
    val json = "{" +
        "\"UserEmail\": \"" + email + "\"," +
```

```
        "\"Message\": \"This event was generated by example code.\"" +
        "\"UtcTime\": \"Now.\"" +
        "}"

    val entry = PutEventsRequestEntry {
        source = "ExampleSource"
        detail = json
        detailType = "ExampleType"
    }

    val eventsRequest = PutEventsRequest {
        this.entries = listOf(entry)
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putEvents(eventsRequest)
    }
}

suspend fun updateCustomRuleTargetWithTransform(topicArn: String?, ruleName:
 String?) {
    val targetId = UUID.randomUUID().toString()

    val inputTransformerOb = InputTransformer {
        inputTemplate = "\"Notification: sample event was received.\""
    }

    val target = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransformerOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
        targets = listOf(target)
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}
```

```
suspend fun updateToCustomRule(ruleName: String?) {
    val customEventsPattern = "{" +
        "\"source\": [\"ExampleSource\"]," +
        "\"detail-type\": [\"ExampleType\"]" +
        "}"
    val request = PutRuleRequest {
        name = ruleName
        description = "Custom test rule"
        eventPattern = customEventsPattern
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putRule(request)
    }
}

// Update an Amazon S3 object created rule with a transform on the target.
suspend fun updateSnsEventRule(topicArn: String?, ruleName: String?) {
    val targetId = UUID.randomUUID().toString()
    val myMap = mutableMapOf<String, String>()
    myMap["bucket"] = "$.detail.bucket.name"
    myMap["time"] = "$.time"

    val inputTransOb = InputTransformer {
        inputTemplate = "\"Notification: an object was uploaded to bucket <bucket>
 at <time>.\""
        inputPathsMap = myMap
    }
    val targetOb = Target {
        id = targetId
        arn = topicArn
        inputTransformer = inputTransOb
    }

    val targetsRequest = PutTargetsRequest {
        rule = ruleName
        targets = listOf(targetOb)
        eventBusName = null
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(targetsRequest)
    }
}
```

```
suspend fun checkRule(eventRuleName: String?) {
    val ruleRequest = DescribeRuleRequest {
        name = eventRuleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.describeRule(ruleRequest)
        println("The state of the rule is $response")
    }
}

suspend fun changeRuleState(eventRuleName: String, isEnabled: Boolean?) {
    if (!isEnabled!!) {
        println("Disabling the rule: $eventRuleName")
        val ruleRequest = DisableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.disableRule(ruleRequest)
        }
    } else {
        println("Enabling the rule: $eventRuleName")
        val ruleRequest = EnableRuleRequest {
            name = eventRuleName
        }
        EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
            eventBrClient.enableRule(ruleRequest)
        }
    }
}

// Create and upload a file to an S3 bucket to trigger an event.
@Throws(IOException::class)
suspend fun uploadTextFiletoS3(bucketName: String?) {
    val fileSuffix = SimpleDateFormat("yyyyMMddHHmmss").format(Date())
    val fileName = "TextFile$fileSuffix.txt"
    val myFile = File(fileName)
    val fw = FileWriter(myFile.absoluteFile)
    val bw = BufferedWriter(fw)
    bw.write("This is a sample file for testing uploads.")
    bw.close()

    val putOb = PutObjectRequest {
```

```
        bucket = bucketName
        key = fileName
        body = myFile.asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.putObject(putOb)
    }
}

suspend fun listTargetRules(topicArnVal: String?) {
    val ruleNamesByTargetRequest = ListRuleNamesByTargetRequest {
        targetArn = topicArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRuleNamesByTarget(ruleNamesByTargetRequest)
        response.ruleNames?.forEach { rule ->
            println("The rule name is $rule")
        }
    }
}

suspend fun listTargets(ruleName: String?) {
    val ruleRequest = ListTargetsByRuleRequest {
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listTargetsByRule(ruleRequest)
        response.targets?.forEach { target ->
            println("Target ARN: ${target.arn}")
        }
    }
}

// Add a rule that triggers an SNS target when a file is uploaded to an S3 bucket.
suspend fun addSnsEventRule(ruleName: String?, topicArn: String?, topicName: String,
 eventRuleName: String, bucketName: String) {
    val targetID = UUID.randomUUID().toString()
    val myTarget = Target {
        id = targetID
        arn = topicArn
    }
```

```
    val targetsOb = mutableListOf<Target>()
    targetsOb.add(myTarget)

    val request = PutTargetsRequest {
        eventBusName = null
        targets = targetsOb
        rule = ruleName
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        eventBrClient.putTargets(request)
        println("Added event rule $eventRuleName with Amazon SNS target $topicName
 for bucket $bucketName.")
    }
}

suspend fun subEmail(topicArnVal: String?, email: String?) {
    val request = SubscribeRequest {
        protocol = "email"
        endpoint = email
        returnSubscriptionArn = true
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.subscribe(request)
        println(" Subscription ARN: ${result.subscriptionArn}")
    }
}

suspend fun createSnsTopic(topicName: String): String? {
    val topicPolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Sid\": \"EventBridgePublishTopic\"," +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": \"events.amazonaws.com\"" +
        "}," +
        "\"Resource\": \"*\"," +
        "\"Action\": \"sns:Publish\"" +
        "}]" +
        "}"
```

```
    val topicAttributes = mutableMapOf<String, String>()
    topicAttributes["Policy"] = topicPolicy

    val topicRequest = CreateTopicRequest {
        name = topicName
        attributes = topicAttributes
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.createTopic(topicRequest)
        println("Added topic $topicName for email subscriptions.")
        return response.topicArn
    }
}

suspend fun listRules() {
    val rulesRequest = ListRulesRequest {
        eventBusName = "default"
        limit = 10
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val response = eventBrClient.listRules(rulesRequest)
        response.rules?.forEach { rule ->
            println("The rule name is ${rule.name}")
            println("The rule ARN is ${rule.arn}")
        }
    }
}

// Create a new event rule that triggers when an Amazon S3 object is created in a
 bucket.
suspend fun addEventRule(roleArnVal: String?, bucketName: String, eventRuleName:
 String?) {
    val pattern = """{
        "source": ["aws.s3"],
        "detail-type": ["Object Created"],
        "detail": {
        "bucket": {
            "name": ["$bucketName"]
            }
        }
    }"""
```

```
    val ruleRequest = PutRuleRequest {
        description = "Created by using the AWS SDK for Kotlin"
        name = eventRuleName
        eventPattern = pattern
        roleArn = roleArnVal
    }

    EventBridgeClient { region = "us-east-1" }.use { eventBrClient ->
        val ruleResponse = eventBrClient.putRule(ruleRequest)
        println("The ARN of the new rule is ${ruleResponse.ruleArn}")
    }
}

// Set the Amazon S3 bucket notification configuration.
suspend fun setBucketNotification(bucketName: String) {
    val eventBridgeConfig = EventBridgeConfiguration {
    }

    val configuration = NotificationConfiguration {
        eventBridgeConfiguration = eventBridgeConfig
    }

    val configurationRequest = PutBucketNotificationConfigurationRequest {
        bucket = bucketName
        notificationConfiguration = configuration
        skipDestinationValidation = true
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.putBucketNotificationConfiguration(configurationRequest)
        println("Added bucket $bucketName with EventBridge events enabled.")
    }
}

// Create an S3 bucket using a waiter.
suspend fun createBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        s3.waitUntilBucketExists {
```

```
            bucket = bucketName
        }
        println("$bucketName is ready")
    }
}

suspend fun checkBucket(bucketName: String?): Boolean {
    try {
        // Determine if the S3 bucket exists.
        val headBucketRequest = HeadBucketRequest {
            bucket = bucketName
        }

        S3Client { region = "us-east-1" }.use { s3Client ->
            s3Client.headBucket(headBucketRequest)
            return true
        }
    } catch (e: S3Exception) {
        System.err.println(e.message)
    }
    return false
}

suspend fun createIAMRole(rolenameVal: String?, polJSON: String?): String? {
    val request = CreateRoleRequest {
        roleName = rolenameVal
        assumeRolePolicyDocument = polJSON
        description = "Created using the AWS SDK for Kotlin"
    }

    val rolePolicyRequest = AttachRolePolicyRequest {
        roleName = rolenameVal
        policyArn = "arn:aws:iam::aws:policy/AmazonEventBridgeFullAccess"
    }

    IamClient { region = "us-east-1" }.use { iam ->
        val response = iam.createRole(request)
        iam.attachRolePolicy(rolePolicyRequest)
        return response.role?.arn
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - DeleteRule
  - DescribeRule
  - DisableRule
  - EnableRule
  - ListRuleNamesByTarget
  - ListRules
  - ListTargetsByRule
  - PutEvents
  - PutRule
  - PutTargets

Exemplos de AWS Glue usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

Os exemplos de código a seguir mostram como criar um crawler do AWS Glue.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createGlueCrawler(
    iam: String?,
    s3Path: String?,
    cron: String?,
    dbName: String?,
    crawlerName: String
) {
    val s3Target = S3Target {
        path = s3Path
    }

    // Add the S3Target to a list.
    val targetList = mutableListOf<S3Target>()
    targetList.add(s3Target)

    val targetOb = CrawlerTargets {
        s3Targets = targetList
    }

    val request = CreateCrawlerRequest {
        databaseName = dbName
        name = crawlerName
        description = "Created by the AWS Glue Kotlin API"
        targets = targetOb
        role = iam
        schedule = cron
    }
```

```
    GlueClient { region = "us-west-2" }.use { glueClient ->
        glueClient.createCrawler(request)
        println("$crawlerName was successfully created")
    }
}
```

- Para obter detalhes da API, consulte a CreateCrawlerreferência da API AWSSDK for Kotlin.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawlerr AWS Glue.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificCrawler(crawlerName: String?) {

    val request = GetCrawlerRequest {
        name = crawlerName
    }
    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getCrawler(request)
        val role = response.crawler?.role
        println("The role associated with this crawler is $role")
    }
}
```

- Para obter detalhes da API, consulte a GetCrawlerreferência da API AWSSDK for Kotlin.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificDatabase(databaseName: String?) {

    val request = GetDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getDatabase(request)
        val dbDesc = response.database?.description
        println("The database description is $dbDesc")
    }
}
```

- Para obter detalhes da API, consulte a GetDatabasereferência da API AWSSDK for Kotlin.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startSpecificCrawler(crawlerName: String?) {

    val request = StartCrawlerRequest {
        name = crawlerName
```

```
    }

    GlueClient { region = "us-west-2" }.use { glueClient ->
        glueClient.startCrawler(request)
        println("$crawlerName was successfully started.")
    }
}
```

- Para obter detalhes da API, consulte a StartCrawlerreferência da API AWSSDK for Kotlin.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
```

```
            <iam> <s3Path> <cron> <dbName> <crawlerName> <jobName> <scriptLocation>
<locationUri>

        Where:
            iam - The Amazon Resource Name (ARN) of the AWS Identity and Access
Management (IAM) role that has AWS Glue and Amazon Simple Storage Service (Amazon
S3) permissions.
            s3Path - The Amazon Simple Storage Service (Amazon S3) target that
contains data (for example, CSV data).
            cron - A cron expression used to specify the schedule (for example,
cron(15 12 * * ? *).
            dbName - The database name.
            crawlerName - The name of the crawler.
            jobName - The name you assign to this job definition.
            scriptLocation - Specifies the Amazon S3 path to a script that runs a
job.
            locationUri - Specifies the location of the database
        """

    if (args.size != 8) {
        println(usage)
        exitProcess(1)
    }

    val iam = args[0]
    val s3Path = args[1]
    val cron = args[2]
    val dbName = args[3]
    val crawlerName = args[4]
    val jobName = args[5]
    val scriptLocation = args[6]
    val locationUri = args[7]

    println("About to start the AWS Glue Scenario")
    createDatabase(dbName, locationUri)
    createCrawler(iam, s3Path, cron, dbName, crawlerName)
    getCrawler(crawlerName)
    startCrawler(crawlerName)
    getDatabase(dbName)
    getGlueTables(dbName)
    createJob(jobName, iam, scriptLocation)
    startJob(jobName)
    getJobs()
    getJobRuns(jobName)
```

```
    deleteJob(jobName)
    println("*** Wait for 5 MIN so the $crawlerName is ready to be deleted")
    TimeUnit.MINUTES.sleep(5)
    deleteMyDatabase(dbName)
    deleteCrawler(crawlerName)
}

suspend fun createDatabase(dbName: String?, locationUriVal: String?) {

    val input = DatabaseInput {
        description = "Built with the AWS SDK for Kotlin"
        name = dbName
        locationUri = locationUriVal
    }

    val request = CreateDatabaseRequest {
        databaseInput = input
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createDatabase(request)
        println("The database was successfully created")
    }
}

suspend fun createCrawler(iam: String?, s3Path: String?, cron: String?, dbName:
 String?, crawlerName: String) {

    val s3Target = S3Target {
        path = s3Path
    }

    val targetList = ArrayList<S3Target>()
    targetList.add(s3Target)

    val targetOb = CrawlerTargets {
        s3Targets = targetList
    }

    val crawlerRequest = CreateCrawlerRequest {
        databaseName = dbName
        name = crawlerName
        description = "Created by the AWS Glue Java API"
        targets = targetOb
```

```
        role = iam
        schedule = cron
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createCrawler(crawlerRequest)
        println("$crawlerName was successfully created")
    }
}

suspend fun getCrawler(crawlerName: String?) {

    val request = GetCrawlerRequest {
        name = crawlerName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getCrawler(request)
        val role = response.crawler?.role
        println("The role associated with this crawler is $role")
    }
}

suspend fun startCrawler(crawlerName: String) {

    val crawlerRequest = StartCrawlerRequest {
        name = crawlerName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.startCrawler(crawlerRequest)
        println("$crawlerName was successfully started.")
    }
}

suspend fun getDatabase(databaseName: String?) {

    val request = GetDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getDatabase(request)
        val dbDesc = response.database?.description
```

```
        println("The database description is $dbDesc")
    }
}

suspend fun getGlueTables(dbName: String?) {

    val tableRequest = GetTablesRequest {
        databaseName = dbName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getTables(tableRequest)
        response.tableList?.forEach { tableName ->
            println("Table name is ${tableName.name}")
        }
    }
}

suspend fun startJob(jobNameVal: String?) {

    val runRequest = StartJobRunRequest {
        workerType = WorkerType.G1X
        numberOfWorkers = 10
        jobName = jobNameVal
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.startJobRun(runRequest)
        println("The job run Id is ${response.jobRunId}")
    }
}

suspend fun createJob(jobName: String, iam: String?, scriptLocationVal: String?) {

    val commandOb = JobCommand {
        pythonVersion = "3"
        name = "MyJob1"
        scriptLocation = scriptLocationVal
    }

    val jobRequest = CreateJobRequest {
        description = "A Job created by using the AWS SDK for Java V2"
        glueVersion = "2.0"
        workerType = WorkerType.G1X
```

```
        numberOfWorkers = 10
        name = jobName
        role = iam
        command = commandOb
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.createJob(jobRequest)
        println("$jobName was successfully created.")
    }
}

suspend fun getJobs() {

    val request = GetJobsRequest {
        maxResults = 10
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getJobs(request)
        response.jobs?.forEach { job ->
            println("Job name is ${job.name}")
        }
    }
}

suspend fun getJobRuns(jobNameVal: String?) {

    val request = GetJobRunsRequest {
        jobName = jobNameVal
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        val response = glueClient.getJobRuns(request)
        response.jobRuns?.forEach { job ->
            println("Job name is ${job.jobName}")
        }
    }
}

suspend fun deleteJob(jobNameVal: String) {

    val jobRequest = DeleteJobRequest {
        jobName = jobNameVal
```

```
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteJob(jobRequest)
        println("$jobNameVal was successfully deleted")
    }
}

suspend fun deleteMyDatabase(databaseName: String) {

    val request = DeleteDatabaseRequest {
        name = databaseName
    }

    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteDatabase(request)
        println("$databaseName was successfully deleted")
    }
}

suspend fun deleteCrawler(crawlerName: String) {

    val request = DeleteCrawlerRequest {
        name = crawlerName
    }
    GlueClient { region = "us-east-1" }.use { glueClient ->
        glueClient.deleteCrawler(request)
        println("$crawlerName was deleted")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable

- GetCrawler
- GetDatabase
- GetDatabases
- GetJob
- GetJobRun
- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

Exemplos de IAM usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun attachIAMRolePolicy(roleNameVal: String, policyArnVal: String) {

    val request = ListAttachedRolePoliciesRequest {
        roleName = roleNameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAttachedRolePolicies(request)
        val attachedPolicies = response.attachedPolicies

        // Ensure that the policy is not attached to this role.
        val checkStatus: Int
        if (attachedPolicies != null) {
            checkStatus = checkList(attachedPolicies, policyArnVal)
            if (checkStatus == -1)
                return
        }

        val policyRequest = AttachRolePolicyRequest {
            roleName = roleNameVal
            policyArn = policyArnVal
        }
        iamClient.attachRolePolicy(policyRequest)
        println("Successfully attached policy $policyArnVal to role $roleNameVal")
    }
}

fun checkList(attachedPolicies: List<AttachedPolicy>, policyArnVal: String): Int {

    for (policy in attachedPolicies) {
        val polArn = policy.policyArn.toString()

        if (polArn.compareTo(policyArnVal) == 0) {
            println("The policy is already attached to this role.")
```

```
            return -1
        }
    }
    return 0
}
```

- Para obter detalhes da API, consulte a AttachRolePolicyreferência da API AWSSDK for Kotlin.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMPolicy(policyNameVal: String?): String {

    val policyDocumentVal = "{" +
        "  \"Version\": \"2012-10-17\"," +
        "  \"Statement\": [" +
        "    {" +
        "        \"Effect\": \"Allow\"," +
        "        \"Action\": [" +
        "            \"dynamodb:DeleteItem\"," +
        "            \"dynamodb:GetItem\"," +
        "            \"dynamodb:PutItem\"," +
        "            \"dynamodb:Scan\"," +
        "            \"dynamodb:UpdateItem\"" +
        "        ]," +
        "        \"Resource\": \"*\"" +
        "    }" +
        "   ]" +
        "}"

    val request = CreatePolicyRequest {
        policyName = policyNameVal
```

```
        policyDocument = policyDocumentVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createPolicy(request)
        return response.policy?.arn.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreatePolicyreferência da API AWSSDK for Kotlin.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMUser(usernameVal: String?): String? {

    val request = CreateUserRequest {
        userName = usernameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createUser(request)
        return response.user?.userName
```

```
    }
}
```

- Para obter detalhes da API, consulte a CreateUserreferência da API AWSSDK for Kotlin.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMAccessKey(user: String?): String {

    val request = CreateAccessKeyRequest {
        userName = user
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createAccessKey(request)
        return response.accessKey?.accessKeyId.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateAccessKeyreferência da API AWSSDK for Kotlin.

Criar um alias para uma conta

Os exemplos de código a seguir mostram como criar um alias para uma conta do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createIAMAccountAlias(alias: String) {

    val request = CreateAccountAliasRequest {
        accountAlias = alias
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.createAccountAlias(request)
        println("Successfully created account alias named $alias")
    }
}
```

- Para obter detalhes da API, consulte a CreateAccountAliasreferência da API AWSSDK for Kotlin.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMPolicy(policyARNVal: String?) {

    val request = DeletePolicyRequest {
        policyArn = policyARNVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deletePolicy(request)
        println("Successfully deleted $policyARNVal")
    }
}
```

- Para obter detalhes da API, consulte a DeletePolicyreferência da API AWSSDK for Kotlin.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMUser(userNameVal: String) {

    val request = DeleteUserRequest {
        userName = userNameVal
    }
```

```
    // To delete a user, ensure that the user's access keys are deleted first.
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteUser(request)
        println("Successfully deleted user $userNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeleteUserreferência da API AWSSDK for Kotlin.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKey(userNameVal: String, accessKey: String) {

    val request = DeleteAccessKeyRequest {
        accessKeyId = accessKey
        userName = userNameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteAccessKey(request)
        println("Successfully deleted access key $accessKey from $userNameVal")
```

```
    }
}
```

- Para obter detalhes da API, consulte a DeleteAccessKeyreferência da API AWSSDK for Kotlin.

Excluir um alias de conta

Os exemplos de código a seguir mostram como excluir alias de uma conta do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteIAMAccountAlias(alias: String) {

    val request = DeleteAccountAliasRequest {
        accountAlias = alias
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.deleteAccountAlias(request)
        println("Successfully deleted account alias $alias")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAccountAliasreferência da API AWSSDK for Kotlin.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detachPolicy(roleNameVal: String, policyArnVal: String) {

    val request = DetachRolePolicyRequest {
        roleName = roleNameVal
        policyArn = policyArnVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.detachRolePolicy(request)
        println("Successfully detached policy $policyArnVal from role $roleNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DetachRolePolicyreferência da API AWSSDK for Kotlin.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getIAMPolicy(policyArnVal: String?) {

    val request = GetPolicyRequest {
```

```
        policyArn = policyArnVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.getPolicy(request)
        println("Successfully retrieved policy ${response.policy?.policyName}")
    }
}
```

- Para obter detalhes da API, consulte a GetPolicyreferência da API AWSSDK for Kotlin.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listKeys(userNameVal: String?) {

    val request = ListAccessKeysRequest {
        userName = userNameVal
    }
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAccessKeys(request)
        response.accessKeyMetadata?.forEach { md ->
            println("Retrieved access key ${md.accessKeyId}")
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAccessKeysreferência da API AWSSDK for Kotlin.

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de uma conta do IAM.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAliases() {

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAccountAliases(ListAccountAliasesRequest {})
        response.accountAliases?.forEach { alias ->
            println("Retrieved account alias $alias")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAccountAliasesreferência da API AWSSDK for Kotlin.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllUsers() {

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listUsers(ListUsersRequest { })
        response.users?.forEach { user ->
            println("Retrieved user ${user.userName}")
            val permissionsBoundary = user.permissionsBoundary
            if (permissionsBoundary != null)
                println("Permissions boundary details
 ${permissionsBoundary.permissionsBoundaryType}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWSSDK for Kotlin.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateIAMUser(curName: String?, newName: String?) {

    val request = UpdateUserRequest {
        userName = curName
        newUserName = newName
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        iamClient.updateUser(request)
        println("Successfully updated user to $newName")
    }
}
```

- Para obter detalhes da API, consulte a UpdateUserreferência da API AWSSDK for Kotlin.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
suspend fun main(args: Array<String>) {

    val usage = """
    Usage:
        <username> <policyName> <roleName> <roleSessionName> <fileLocation>
 <bucketName>

    Where:
        username - The name of the IAM user to create.
        policyName - The name of the policy to create.
        roleName - The name of the role to create.
        roleSessionName - The name of the session required for the assumeRole
 operation.
        fileLocation - The file location to the JSON required to create the role
 (see Readme).
        bucketName - The name of the Amazon S3 bucket from which objects are read.
    """
```

```
    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }

    val userName = args[0]
    val policyName = args[1]
    val roleName = args[2]
    val roleSessionName = args[3]
    val fileLocation = args[4]
    val bucketName = args[5]

    createUser(userName)
    println("$userName was successfully created.")

    val polArn = createPolicy(policyName)
    println("The policy $polArn was successfully created.")

    val roleArn = createRole(roleName, fileLocation)
    println("$roleArn was successfully created.")
    attachRolePolicy(roleName, polArn)

    println("*** Wait for 1 MIN so the resource is available.")
    delay(60000)
    assumeGivenRole(roleArn, roleSessionName, bucketName)

    println("*** Getting ready to delete the AWS resources.")
    deleteRole(roleName, polArn)
    deleteUser(userName)
    println("This IAM Scenario has successfully completed.")
}

suspend fun createUser(usernameVal: String?): String? {

    val request = CreateUserRequest {
        userName = usernameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createUser(request)
        return response.user?.userName
    }
}
```

```
suspend fun createPolicy(policyNameVal: String?): String {

    val policyDocumentValue: String = "{" +
        "  \"Version\": \"2012-10-17\"," +
        "  \"Statement\": [" +
        "    {" +
        "        \"Effect\": \"Allow\"," +
        "        \"Action\": [" +
        "            \"s3:*\"" +
        "       ]," +
        "       \"Resource\": \"*\"" +
        "    }" +
        "   ]" +
        "}"

    val request = CreatePolicyRequest {
        policyName = policyNameVal
        policyDocument = policyDocumentValue
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createPolicy(request)
        return response.policy?.arn.toString()
    }
}

suspend fun createRole(rolenameVal: String?, fileLocation: String?): String? {

    val jsonObject = fileLocation?.let { readJsonSimpleDemo(it) } as JSONObject

    val request = CreateRoleRequest {
        roleName = rolenameVal
        assumeRolePolicyDocument = jsonObject.toJSONString()
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createRole(request)
        return response.role?.arn
    }
}

suspend fun attachRolePolicy(roleNameVal: String, policyArnVal: String) {
```

```
    val request = ListAttachedRolePoliciesRequest {
        roleName = roleNameVal
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.listAttachedRolePolicies(request)
        val attachedPolicies = response.attachedPolicies

        // Ensure that the policy is not attached to this role.
        val checkStatus: Int
        if (attachedPolicies != null) {
            checkStatus = checkMyList(attachedPolicies, policyArnVal)
            if (checkStatus == -1)
                return
        }

        val policyRequest = AttachRolePolicyRequest {
            roleName = roleNameVal
            policyArn = policyArnVal
        }
        iamClient.attachRolePolicy(policyRequest)
        println("Successfully attached policy $policyArnVal to role $roleNameVal")
    }
}

fun checkMyList(attachedPolicies: List<AttachedPolicy>, policyArnVal: String): Int {

    for (policy in attachedPolicies) {
        val polArn = policy.policyArn.toString()

        if (polArn.compareTo(policyArnVal) == 0) {
            println("The policy is already attached to this role.")
            return -1
        }
    }
    return 0
}

suspend fun assumeGivenRole(roleArnVal: String?, roleSessionNameVal: String?,
 bucketName: String) {

    val stsClient = StsClient {
        region = "us-east-1"
```

```
    }

    val roleRequest = AssumeRoleRequest {
        roleArn = roleArnVal
        roleSessionName = roleSessionNameVal
    }

    val roleResponse = stsClient.assumeRole(roleRequest)
    val myCreds = roleResponse.credentials
    val key = myCreds?.accessKeyId
    val secKey = myCreds?.secretAccessKey
    val secToken = myCreds?.sessionToken

    val staticCredentials = StaticCredentialsProvider {
        accessKeyId = key
        secretAccessKey = secKey
        sessionToken = secToken
    }

    // List all objects in an Amazon S3 bucket using the temp creds.
    val s3 = S3Client {
        credentialsProvider = staticCredentials
        region = "us-east-1"
    }

    println("Created a S3Client using temp credentials.")
    println("Listing objects in $bucketName")

    val listObjects = ListObjectsRequest {
        bucket = bucketName
    }

    val response = s3.listObjects(listObjects)
    response.contents?.forEach { myObject ->
        println("The name of the key is ${myObject.key}")
        println("The owner is ${myObject.owner}")
    }
}

suspend fun deleteRole(roleNameVal: String, polArn: String) {

    val iam = IamClient { region = "AWS_GLOBAL" }

    // First the policy needs to be detached.
```

```
    val rolePolicyRequest = DetachRolePolicyRequest {
        policyArn = polArn
        roleName = roleNameVal
    }

    iam.detachRolePolicy(rolePolicyRequest)

    // Delete the policy.
    val request = DeletePolicyRequest {
        policyArn = polArn
    }

    iam.deletePolicy(request)
    println("*** Successfully deleted $polArn")

    // Delete the role.
    val roleRequest = DeleteRoleRequest {
        roleName = roleNameVal
    }

    iam.deleteRole(roleRequest)
    println("*** Successfully deleted $roleNameVal")
}

suspend fun deleteUser(userNameVal: String) {
    val iam = IamClient { region = "AWS_GLOBAL" }
    val request = DeleteUserRequest {
        userName = userNameVal
    }

    iam.deleteUser(request)
    println("*** Successfully deleted $userNameVal")
}

@Throws(java.lang.Exception::class)
fun readJsonSimpleDemo(filename: String): Any? {
    val reader = FileReader(filename)
    val jsonParser = JSONParser()
    return jsonParser.parse(reader)
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos do Amazon Keyspaces usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon Keyspaces.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Keyspaces

O exemplo de código a seguir mostra como começar a usar o Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
 including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
*/

suspend fun main() {
    listKeyspaces()
}

suspend fun listKeyspaces() {
    val keyspacesRequest = ListKeyspacesRequest {
        maxResults = 10
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.listKeyspaces(keyspacesRequest)
        response.keyspaces?.forEach { keyspace ->
            println("The name of the keyspace is ${keyspace.keyspaceName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListKeyspacesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Criar um espaço de chaves

Os exemplos de código a seguir mostram como criar um espaço de chave do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createKeySpace(keyspaceNameVal: String) {
    val keyspaceRequest = CreateKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createKeyspace(keyspaceRequest)
        println("The ARN of the KeySpace is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyspacereferência da API AWSSDK for Kotlin.

Criar uma tabela

Os exemplos de código a seguir mostram como criar uma tabela do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createTable(keySpaceVal: String?, tableNameVal: String?) {
```

```
    // Set the columns.
    val defTitle = ColumnDefinition {
        name = "title"
        type = "text"
    }

    val defYear = ColumnDefinition {
        name = "year"
        type = "int"
    }

    val defReleaseDate = ColumnDefinition {
        name = "release_date"
        type = "timestamp"
    }

    val defPlot = ColumnDefinition {
        name = "plot"
        type = "text"
    }

    val colList = ArrayList<ColumnDefinition>()
    colList.add(defTitle)
    colList.add(defYear)
    colList.add(defReleaseDate)
    colList.add(defPlot)

    // Set the keys.
    val yearKey = PartitionKey {
        name = "year"
    }

    val titleKey = PartitionKey {
        name = "title"
    }

    val keyList = ArrayList<PartitionKey>()
    keyList.add(yearKey)
    keyList.add(titleKey)

    val schemaDefinitionOb = SchemaDefinition {
        partitionKeys = keyList
        allColumns = colList
    }
```

```
    val timeRecovery = PointInTimeRecovery {
        status = PointInTimeRecoveryStatus.Enabled
    }

    val tableRequest = CreateTableRequest {
        keyspaceName = keySpaceVal
        tableName = tableNameVal
        schemaDefinition = schemaDefinitionOb
        pointInTimeRecovery = timeRecovery
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createTable(tableRequest)
        println("The table ARN is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWSSDK for Kotlin.

Excluir um keyspace

O exemplo de código a seguir mostra como excluir um espaço de chaves do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteKeyspace(keyspaceNameVal: String?) {
    val deleteKeyspaceRequest = DeleteKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteKeyspace(deleteKeyspaceRequest)
    }
}
```

- Para obter detalhes da API, consulte a DeleteKeyspacereferência da API AWSSDK for Kotlin.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteTable(keyspaceNameVal: String?, tableNameVal: String?) {
    val tableRequest = DeleteTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteTable(tableRequest)
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWSSDK for Kotlin.

Obter dados sobre um keyspace

O exemplo de código a seguir mostra como obter dados sobre um keyspace do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkKeyspaceExistence(keyspaceNameVal: String?) {
    val keyspaceRequest = GetKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response: GetKeyspaceResponse = keyClient.getKeyspace(keyspaceRequest)
        val name = response.keyspaceName
        println("The $name KeySpace is ready")
    }
}
```

- Para obter detalhes da API, consulte a GetKeyspacereferência da API AWSSDK for Kotlin.

Obter dados sobre uma tabela

O exemplo de código a seguir mostra como obter dados sobre uma tabela do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println(". The table status is $status")
            if (status.compareTo("ACTIVE") == 0) {
```

```
                tableStatus = true
            }
            delay(500)
        }
        val cols: List<ColumnDefinition>? = response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a GetTablereferência da API AWSSDK for Kotlin.

Listar espaços de chaves

O exemplo de código a seguir mostra como listar espaços de chaves do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listKeyspacesPaginator() {
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listKeyspacesPaginated(ListKeyspacesRequest {})
            .transform { it.keyspaces?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println("Name: ${obj.keyspaceName}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListKeyspacesreferência da API AWSSDK for Kotlin.

Listar tabelas em um keyspace

O exemplo de código a seguir mostra como listar tabelas do Amazon Keyspaces em um espaço de chave.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listTables(keyspaceNameVal: String?) {
    val tablesRequest = ListTablesRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listTablesPaginated(tablesRequest)
            .transform { it.tables?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(
                    " ARN: " + obj.resourceArn.toString() +
                        " Table name: " + obj.tableName
                )
            }
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWSSDK for Kotlin.

Restaurar uma tabela para um ponto no tempo

O exemplo de código a seguir mostra como restaurar uma tabela do Amazon Keyspaces em um determinado momento.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun restoreTable(keyspaceName: String?, utc: ZonedDateTime) {
    // Create an aws.smithy.kotlin.runtime.time.Instant value.
    val timeStamp = aws.smithy.kotlin.runtime.time.Instant(utc.toInstant())
    val restoreTableRequest = RestoreTableRequest {
        restoreTimestamp = timeStamp
        sourceTableName = "MovieKotlin"
        targetKeyspaceName = keyspaceName
        targetTableName = "MovieRestore"
        sourceKeyspaceName = keyspaceName
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.restoreTable(restoreTableRequest)
        println("The ARN of the restored table is ${response.restoredTableArn}")
    }
}
```

- Para obter detalhes da API, consulte a RestoreTablereferência da API AWSSDK for Kotlin.

Atualizar uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do Amazon Keyspaces.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateTable(keySpace: String?, tableNameVal: String?) {
    val def = ColumnDefinition {
        name = "watched"
        type = "boolean"
    }

    val tableRequest = UpdateTableRequest {
        keyspaceName = keySpace
        tableName = tableNameVal
        addColumns = listOf(def)
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.updateTable(tableRequest)
    }
}
```

- Para obter detalhes da API, consulte a UpdateTablereferência da API AWSSDK for Kotlin.

Cenários

Começar a usar espaços de chaves e tabelas

O código de exemplo a seguir mostra como:

- Criar um keyspace e uma tabela. O esquema da tabela contém dados do filme e tem a point-in-time recuperação ativada.
- Conectar-se ao espaço de chaves usando uma conexão TLS segura com autenticação SigV4.
- Consulte a tabela. Adicionar recuperar e atualizar dados do filme.
- Atualizar tabela. Adicionar uma coluna para rastrear os filmes assistidos.
- Restaurar a tabela ao estado anterior e limpar os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:

 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This example uses a secure file format to hold certificate information for
 Kotlin applications. This is required to make a connection to Amazon Keyspaces.
 For more information, see the following documentation topic:

 https://docs.aws.amazon.com/keyspaces/latest/devguide/using_java_driver.html

 This Kotlin example performs the following tasks:

 1. Create a keyspace.
 2. Check for keyspace existence.
 3. List keyspaces using a paginator.
 4. Create a table with a simple movie data schema and enable point-in-time
 recovery.
 5. Check for the table to be in an Active state.
 6. List all tables in the keyspace.
 7. Use a Cassandra driver to insert some records into the Movie table.
 8. Get all records from the Movie table.
 9. Get a specific Movie.
 10. Get a UTC timestamp for the current time.
 11. Update the table schema to add a ‘watched’ Boolean column.
 12. Update an item as watched.
 13. Query for items with watched = True.
 14. Restore the table back to the previous state using the timestamp.
 15. Check for completion of the restore action.
 16. Delete the table.
 17. Confirm that both tables are deleted.
 18. Delete the keyspace.
 */

/*
   Usage:
     fileName - The name of the JSON file that contains movie data. (Get this file
 from the GitHub repo at resources/sample_file.)
     keyspaceName - The name of the keyspace to create.
  */
```

```
val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main() {
    val fileName = "<Replace with the JSON file that contains movie data>"
    val keyspaceName = "<Replace with the name of the keyspace to create>"
    val titleUpdate = "The Family"
    val yearUpdate = 2013
    val tableName = "MovieKotlin"
    val tableNameRestore = "MovieRestore"

    val loader = DriverConfigLoader.fromClasspath("application.conf")
    val session = CqlSession.builder()
        .withConfigLoader(loader)
        .build()

    println(DASHES)
    println("Welcome to the Amazon Keyspaces example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. Create a keyspace.")
    createKeySpace(keyspaceName)
    println(DASHES)

    println(DASHES)
    delay(5000)
    println("2. Check for keyspace existence.")
    checkKeyspaceExistence(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("3. List keyspaces using a paginator.")
    listKeyspacesPaginator()
    println(DASHES)

    println(DASHES)
    println("4. Create a table with a simple movie data schema and enable point-in-
time recovery.")
    createTable(keyspaceName, tableName)
    println(DASHES)

    println(DASHES)
    println("5. Check for the table to be in an Active state.")
    delay(6000)
    checkTable(keyspaceName, tableName)
```

```
    println(DASHES)

    println(DASHES)
    println("6. List all tables in the keyspace.")
    listTables(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("7. Use a Cassandra driver to insert some records into the Movie
 table.")
    delay(6000)
    loadData(session, fileName, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("8. Get all records from the Movie table.")
    getMovieData(session, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("9. Get a specific Movie.")
    getSpecificMovie(session, keyspaceName)
    println(DASHES)

    println(DASHES)
    println("10. Get a UTC timestamp for the current time.")
    val utc = ZonedDateTime.now(ZoneOffset.UTC)
    println("DATETIME = ${Date.from(utc.toInstant())}")
    println(DASHES)

    println(DASHES)
    println("11. Update the table schema to add a watched Boolean column.")
    updateTable(keyspaceName, tableName)
    println(DASHES)

    println(DASHES)
    println("12. Update an item as watched.")
    delay(10000) // Wait 10 seconds for the update.
    updateRecord(session, keyspaceName, titleUpdate, yearUpdate)
    println(DASHES)

    println(DASHES)
    println("13. Query for items with watched = True.")
    getWatchedData(session, keyspaceName)
```

```
    println(DASHES)

    println(DASHES)
    println("14. Restore the table back to the previous state using the timestamp.")
    println("Note that the restore operation can take up to 20 minutes.")
    restoreTable(keyspaceName, utc)
    println(DASHES)

    println(DASHES)
    println("15. Check for completion of the restore action.")
    delay(5000)
    checkRestoredTable(keyspaceName, "MovieRestore")
    println(DASHES)

    println(DASHES)
    println("16. Delete both tables.")
    deleteTable(keyspaceName, tableName)
    deleteTable(keyspaceName, tableNameRestore)
    println(DASHES)

    println(DASHES)
    println("17. Confirm that both tables are deleted.")
    checkTableDelete(keyspaceName, tableName)
    checkTableDelete(keyspaceName, tableNameRestore)
    println(DASHES)

    println(DASHES)
    println("18. Delete the keyspace.")
    deleteKeyspace(keyspaceName)
    println(DASHES)

    println(DASHES)
    println("The scenario has completed successfully.")
    println(DASHES)
}

suspend fun deleteKeyspace(keyspaceNameVal: String?) {
    val deleteKeyspaceRequest = DeleteKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteKeyspace(deleteKeyspaceRequest)
    }
```

```
}

suspend fun checkTableDelete(keyspaceNameVal: String?, tableNameVal: String?) {
    var status: String
    var response: GetTableResponse
    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    try {
        KeyspacesClient { region = "us-east-1" }.use { keyClient ->
            // Keep looping until the table cannot be found and a
 ResourceNotFoundException is thrown.
            while (true) {
                response = keyClient.getTable(tableRequest)
                status = response.status.toString()
                println(". The table status is $status")
                delay(500)
            }
        }
    } catch (e: ResourceNotFoundException) {
        println(e.message)
    }
    println("The table is deleted")
}

suspend fun deleteTable(keyspaceNameVal: String?, tableNameVal: String?) {
    val tableRequest = DeleteTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.deleteTable(tableRequest)
    }
}

suspend fun checkRestoredTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
```

```
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println("The table status is $status")

            if (status.compareTo("ACTIVE") == 0) {
                tableStatus = true
            }
            delay(500)
        }

        val cols = response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}

suspend fun restoreTable(keyspaceName: String?, utc: ZonedDateTime) {
    // Create an aws.smithy.kotlin.runtime.time.Instant value.
    val timeStamp = aws.smithy.kotlin.runtime.time.Instant(utc.toInstant())
    val restoreTableRequest = RestoreTableRequest {
        restoreTimestamp = timeStamp
        sourceTableName = "MovieKotlin"
        targetKeyspaceName = keyspaceName
        targetTableName = "MovieRestore"
        sourceKeyspaceName = keyspaceName
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.restoreTable(restoreTableRequest)
        println("The ARN of the restored table is ${response.restoredTableArn}")
    }
}

fun getWatchedData(session: CqlSession, keyspaceName: String) {
```

```
    val resultSet = session.execute("SELECT * FROM \"$keyspaceName\".\"MovieKotlin\"
 WHERE watched = true ALLOW FILTERING;")
    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

fun updateRecord(session: CqlSession, keySpace: String, titleUpdate: String?,
 yearUpdate: Int) {
    val sqlStatement =
        "UPDATE \"$keySpace\".\"MovieKotlin\" SET watched=true WHERE title = :k0 AND
 year = :k1;"
    val builder = BatchStatement.builder(DefaultBatchType.UNLOGGED)
    builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM)
    val preparedStatement = session.prepare(sqlStatement)
    builder.addStatement(
        preparedStatement.boundStatementBuilder()
            .setString("k0", titleUpdate)
            .setInt("k1", yearUpdate)
            .build()
    )
    val batchStatement = builder.build()
    session.execute(batchStatement)
}

suspend fun updateTable(keySpace: String?, tableNameVal: String?) {
    val def = ColumnDefinition {
        name = "watched"
        type = "boolean"
    }

    val tableRequest = UpdateTableRequest {
        keyspaceName = keySpace
        tableName = tableNameVal
        addColumns = listOf(def)
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.updateTable(tableRequest)
    }
}
```

```
fun getSpecificMovie(session: CqlSession, keyspaceName: String) {
    val resultSet =
        session.execute("SELECT * FROM \"$keyspaceName\".\"MovieKotlin\" WHERE title
 = 'The Family' ALLOW FILTERING ;")

    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

// Get records from the Movie table.
fun getMovieData(session: CqlSession, keyspaceName: String) {
    val resultSet = session.execute("SELECT * FROM \"$keyspaceName\".\"MovieKotlin
\";")
    resultSet.forEach { item: Row ->
        println("The Movie title is ${item.getString("title")}")
        println("The Movie year is ${item.getInt("year")}")
        println("The plot is ${item.getString("plot")}")
    }
}

// Load data into the table.
fun loadData(session: CqlSession, fileName: String, keySpace: String) {
    val sqlStatement =
        "INSERT INTO \"$keySpace\".\"MovieKotlin\" (title, year, plot) values
 (:k0, :k1, :k2)"
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {
        if (t == 50) {
            break
        }

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
```

```
        // Insert the data into the Amazon Keyspaces table.
        val builder = BatchStatement.builder(DefaultBatchType.UNLOGGED)
        builder.setConsistencyLevel(ConsistencyLevel.LOCAL_QUORUM)
        val preparedStatement: PreparedStatement = session.prepare(sqlStatement)
        builder.addStatement(
            preparedStatement.boundStatementBuilder()
                .setString("k0", title)
                .setInt("k1", year)
                .setString("k2", info)
                .build()
        )

        val batchStatement = builder.build()
        session.execute(batchStatement)
        t++
    }
}

suspend fun listTables(keyspaceNameVal: String?) {
    val tablesRequest = ListTablesRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listTablesPaginated(tablesRequest)
            .transform { it.tables?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(
                    " ARN: " + obj.resourceArn.toString() +
                        " Table name: " + obj.tableName
                )
            }
    }
}

suspend fun checkTable(keyspaceNameVal: String?, tableNameVal: String?) {
    var tableStatus = false
    var status: String
    var response: GetTableResponse? = null

    val tableRequest = GetTableRequest {
        keyspaceName = keyspaceNameVal
        tableName = tableNameVal
    }
```

```
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        while (!tableStatus) {
            response = keyClient.getTable(tableRequest)
            status = response!!.status.toString()
            println(". The table status is $status")
            if (status.compareTo("ACTIVE") == 0) {
                tableStatus = true
            }
            delay(500)
        }
        val cols: List<ColumnDefinition>? = response!!.schemaDefinition?.allColumns
        if (cols != null) {
            for (def in cols) {
                println("The column name is ${def.name}")
                println("The column type is ${def.type}")
            }
        }
    }
}

suspend fun createTable(keySpaceVal: String?, tableNameVal: String?) {
    // Set the columns.
    val defTitle = ColumnDefinition {
        name = "title"
        type = "text"
    }

    val defYear = ColumnDefinition {
        name = "year"
        type = "int"
    }

    val defReleaseDate = ColumnDefinition {
        name = "release_date"
        type = "timestamp"
    }

    val defPlot = ColumnDefinition {
        name = "plot"
        type = "text"
    }

    val colList = ArrayList<ColumnDefinition>()
    colList.add(defTitle)
```

```
    colList.add(defYear)
    colList.add(defReleaseDate)
    colList.add(defPlot)

    // Set the keys.
    val yearKey = PartitionKey {
        name = "year"
    }

    val titleKey = PartitionKey {
        name = "title"
    }

    val keyList = ArrayList<PartitionKey>()
    keyList.add(yearKey)
    keyList.add(titleKey)

    val schemaDefinitionOb = SchemaDefinition {
        partitionKeys = keyList
        allColumns = colList
    }

    val timeRecovery = PointInTimeRecovery {
        status = PointInTimeRecoveryStatus.Enabled
    }

    val tableRequest = CreateTableRequest {
        keyspaceName = keySpaceVal
        tableName = tableNameVal
        schemaDefinition = schemaDefinitionOb
        pointInTimeRecovery = timeRecovery
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createTable(tableRequest)
        println("The table ARN is ${response.resourceArn}")
    }
}

suspend fun listKeyspacesPaginator() {
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        keyClient.listKeyspacesPaginated(ListKeyspacesRequest {})
            .transform { it.keyspaces?.forEach { obj -> emit(obj) } }
            .collect { obj ->
```

```
                println("Name: ${obj.keyspaceName}")
            }
    }
}

suspend fun checkKeyspaceExistence(keyspaceNameVal: String?) {
    val keyspaceRequest = GetKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }
    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response: GetKeyspaceResponse = keyClient.getKeyspace(keyspaceRequest)
        val name = response.keyspaceName
        println("The $name KeySpace is ready")
    }
}

suspend fun createKeySpace(keyspaceNameVal: String) {
    val keyspaceRequest = CreateKeyspaceRequest {
        keyspaceName = keyspaceNameVal
    }

    KeyspacesClient { region = "us-east-1" }.use { keyClient ->
        val response = keyClient.createKeyspace(keyspaceRequest)
        println("The ARN of the KeySpace is ${response.resourceArn}")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable

- UpdateTable

Exemplos de AWS KMS usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma concessão para uma chave

O exemplo de código a seguir mostra como criar uma concessão para uma chave KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewGrant(keyIdVal: String?, granteePrincipalVal: String?,
 operation: String): String? {

    val operationOb = GrantOperation.fromValue(operation)
```

```
    val grantOperationList = ArrayList<GrantOperation>()
    grantOperationList.add(operationOb)

    val request = CreateGrantRequest {
        keyId = keyIdVal
        granteePrincipal = granteePrincipalVal
        operations = grantOperationList
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.createGrant(request)
        return response.grantId
    }
}
```

- Para obter detalhes da API, consulte a CreateGrantreferência da API AWSSDK for Kotlin.

Criar uma chave

O exemplo de código a seguir mostra como criar AWS KMS key.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createKey(keyDesc: String?): String? {

    val request = CreateKeyRequest {
        description = keyDesc
        customerMasterKeySpec = CustomerMasterKeySpec.SymmetricDefault
        keyUsage = KeyUsageType.fromValue("ENCRYPT_DECRYPT")
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val result = kmsClient.createKey(request)
        println("Created a customer key with id " + result.keyMetadata?.arn)
```

```
        return result.keyMetadata?.keyId
    }
}
```

- Para obter detalhes da API, consulte a CreateKeyreferência da API AWSSDK for Kotlin.

Criar um alias para uma chave

O exemplo de código a seguir mostra como criar um alias para uma chave do KMS Key.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createCustomAlias(targetKeyIdVal: String?, aliasNameVal: String?) {

    val request = CreateAliasRequest {
        aliasName = aliasNameVal
        targetKeyId = targetKeyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.createAlias(request)
        println("$aliasNameVal was successfully created")
    }
}
```

- Para obter detalhes da API, consulte a CreateAliasreferência da API AWSSDK for Kotlin.

Descriptografar texto cifrado

O exemplo de código a seguir mostra como descriptografar texto cifrado que foi criptografado com uma chave KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun encryptData(keyIdValue: String): ByteArray? {

    val text = "This is the text to encrypt by using the AWS KMS Service"
    val myBytes: ByteArray = text.toByteArray()

    val encryptRequest = EncryptRequest {
        keyId = keyIdValue
        plaintext = myBytes
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.encrypt(encryptRequest)
        val algorithm: String = response.encryptionAlgorithm.toString()
        println("The encryption algorithm is $algorithm")

        // Return the encrypted data.
        return response.ciphertextBlob
    }
}

suspend fun decryptData(encryptedDataVal: ByteArray?, keyIdVal: String?, path:
 String) {

    val decryptRequest = DecryptRequest {
        ciphertextBlob = encryptedDataVal
        keyId = keyIdVal
    }
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val decryptResponse = kmsClient.decrypt(decryptRequest)
        val myVal = decryptResponse.plaintext

        // Write the decrypted data to a file.
        if (myVal != null) {
            File(path).writeBytes(myVal)
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte Descriptografar na AWS Referência da API SDK para Kotlin.

Descrever uma chave

O exemplo de código a seguir mostra como descrever uma chave do KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeSpecifcKey(keyIdVal: String?) {

    val request = DescribeKeyRequest {
        keyId = keyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.describeKey(request)
        println("The key description is ${response.keyMetadata?.description}")
        println("The key ARN is ${response.keyMetadata?.arn}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeKeyreferência da API AWSSDK for Kotlin.

Desabilitar uma chave

O exemplo de código a seguir mostra como desativar uma chave KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun disableKey(keyIdVal: String?) {

    val request = DisableKeyRequest {
        keyId = keyIdVal
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.disableKey(request)
        println("$keyIdVal was successfully disabled")
    }
}
```

- Para obter detalhes da API, consulte a DisableKeyreferência da API AWSSDK for Kotlin.

Habilitar uma chave

O exemplo de código a seguir mostra como habilitar uma chave do KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun enableKey(keyIdVal: String?) {

    val request = EnableKeyRequest {
        keyId = keyIdVal
    }
```

```
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        kmsClient.enableKey(request)
        println("$keyIdVal was successfully enabled.")
    }
}
```

- Para obter detalhes da API, consulte a EnableKeyreferência da API AWSSDK for Kotlin.

Criptografar texto usando uma chave

O exemplo de código a seguir mostra como criptografar texto usando uma chave KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun encryptData(keyIdValue: String): ByteArray? {

    val text = "This is the text to encrypt by using the AWS KMS Service"
    val myBytes: ByteArray = text.toByteArray()

    val encryptRequest = EncryptRequest {
        keyId = keyIdValue
        plaintext = myBytes
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.encrypt(encryptRequest)
        val algorithm: String = response.encryptionAlgorithm.toString()
        println("The encryption algorithm is $algorithm")

        // Return the encrypted data.
        return response.ciphertextBlob
    }
}
```

```
suspend fun decryptData(encryptedDataVal: ByteArray?, keyIdVal: String?, path:
 String) {

    val decryptRequest = DecryptRequest {
        ciphertextBlob = encryptedDataVal
        keyId = keyIdVal
    }
    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val decryptResponse = kmsClient.decrypt(decryptRequest)
        val myVal = decryptResponse.plaintext

        // Write the decrypted data to a file.
        if (myVal != null) {
            File(path).writeBytes(myVal)
        }
    }
}
```

- Para obter detalhes da API, consulte Criptografar na AWS Referência da API SDK para Kotlin.

Listar aliases para uma chave

Os exemplos de código a seguir mostram como listar aliases para uma chave KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllAliases() {

    val request = ListAliasesRequest {
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listAliases(request)
        response.aliases?.forEach { alias ->
```

```
            println("The alias name is ${alias.aliasName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListAliasesreferência da API AWSSDK for Kotlin.

Listar concessões para uma chave

O exemplo de código a seguir mostra como listar concessões para uma chave do KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun displayGrantIds(keyIdVal: String?) {

    val request = ListGrantsRequest {
        keyId = keyIdVal
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listGrants(request)
        response.grants?.forEach { grant ->
            println("The grant Id is ${grant.grantId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListGrantsreferência da API AWSSDK for Kotlin.

Listar chaves

O exemplo de código a seguir mostra como listar chaves do KMS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllKeys() {

    val request = ListKeysRequest {
        limit = 15
    }

    KmsClient { region = "us-west-2" }.use { kmsClient ->
        val response = kmsClient.listKeys(request)
        response.keys?.forEach { key ->
            println("The key ARN is ${key.keyArn}")
            println("The key Id is ${key.keyId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListKeysreferência da API AWSSDK for Kotlin.

Exemplos de Lambda usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewFunction(
    myFunctionName: String,
    s3BucketName: String,
    myS3Key: String,
    myHandler: String,
    myRole: String
): String? {

    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }

    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java8
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
```

```
        val functionResponse = awsLambda.createFunction(request)
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        return functionResponse.functionArn
    }
}
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWSSDK for Kotlin.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun delLambdaFunction(myFunctionName: String) {

    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWSSDK for Kotlin.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun invokeFunction(functionNameVal: String) {

    val json = """{"inputValue":"1000"}"""
    val byteArray = json.trimIndent().encodeToByteArray()
    val request = InvokeRequest {
        functionName = functionNameVal
        logType = LogType.Tail
        payload = byteArray
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val res = awsLambda.invoke(request)
        println("${res.payload?.toString(Charsets.UTF_8)}")
        println("The log result is ${res.logResult}")
    }
}
```

- Para obter detalhes da API, consulte Invoke na Referência da APIs do AWS SDK para Kotlin.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
            <functionName> <role> <handler> <bucketName> <updatedBucketName> <key>

        Where:
            functionName - The name of the AWS Lambda function.
            role - The AWS Identity and Access Management (IAM) service role that
 has AWS Lambda permissions.
            handler - The fully qualified method name (for example,
 example.Handler::handleRequest).
            bucketName - The Amazon Simple Storage Service (Amazon S3) bucket name
 that contains the ZIP or JAR used for the Lambda function's code.
            updatedBucketName - The Amazon S3 bucket name that contains the .zip
 or .jar used to update the Lambda function's code.
            key - The Amazon S3 key name that represents the .zip or .jar file (for
 example, LambdaHello-1.0-SNAPSHOT.jar).
            """

    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }

    val functionName = args[0]
    val role = args[1]
    val handler = args[2]
    val bucketName = args[3]
    val updatedBucketName = args[4]
    val key = args[5]
```

```
    println("Creating a Lambda function named $functionName.")
    val funArn = createScFunction(functionName, bucketName, key, handler, role)
    println("The AWS Lambda ARN is $funArn")

    // Get a specific Lambda function.
    println("Getting the $functionName AWS Lambda function.")
    getFunction(functionName)

    // List the Lambda functions.
    println("Listing all AWS Lambda functions.")
    listFunctionsSc()

    // Invoke the Lambda function.
    println("*** Invoke the Lambda function.")
    invokeFunctionSc(functionName)

    // Update the AWS Lambda function code.
    println("*** Update the Lambda function code.")
    updateFunctionCode(functionName, updatedBucketName, key)

    // println("*** Invoke the function again after updating the code.")
    invokeFunctionSc(functionName)

    // Update the AWS Lambda function configuration.
    println("Update the run time of the function.")
    UpdateFunctionConfiguration(functionName, handler)

    // Delete the AWS Lambda function.
    println("Delete the AWS Lambda function.")
    delFunction(functionName)
}

suspend fun createScFunction(
    myFunctionName: String,
    s3BucketName: String,
    myS3Key: String,
    myHandler: String,
    myRole: String
): String {

    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }
```

```
    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java8
    }

    // Create a Lambda function using a waiter
    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val functionResponse = awsLambda.createFunction(request)
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        return functionResponse.functionArn.toString()
    }
}

suspend fun getFunction(functionNameVal: String) {

    val functionRequest = GetFunctionRequest {
        functionName = functionNameVal
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.getFunction(functionRequest)
        println("The runtime of this Lambda function is
 ${response.configuration?.runtime}")
    }
}

suspend fun listFunctionsSc() {

    val request = ListFunctionsRequest {
        maxItems = 10
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.listFunctions(request)
        response.functions?.forEach { function ->
            println("The function name is ${function.functionName}")
        }
```

```
    }
}

suspend fun invokeFunctionSc(functionNameVal: String) {

    val json = """{"inputValue":"1000"}"""
    val byteArray = json.trimIndent().encodeToByteArray()
    val request = InvokeRequest {
        functionName = functionNameVal
        payload = byteArray
        logType = LogType.Tail
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val res = awsLambda.invoke(request)
        println("The function payload is ${res.payload?.toString(Charsets.UTF_8)}")
    }
}

suspend fun updateFunctionCode(functionNameVal: String?, bucketName: String?, key:
 String?) {

    val functionCodeRequest = UpdateFunctionCodeRequest {
        functionName = functionNameVal
        publish = true
        s3Bucket = bucketName
        s3Key = key
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val response = awsLambda.updateFunctionCode(functionCodeRequest)
        awsLambda.waitUntilFunctionUpdated {
            functionName = functionNameVal
        }
        println("The last modified value is " + response.lastModified)
    }
}

suspend fun UpdateFunctionConfiguration(functionNameVal: String?, handlerVal:
 String?) {

    val configurationRequest = UpdateFunctionConfigurationRequest {
        functionName = functionNameVal
        handler = handlerVal
```

```
        runtime = Runtime.Java11
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.updateFunctionConfiguration(configurationRequest)
    }
}

suspend fun delFunction(myFunctionName: String) {

    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

MediaConvert exemplos usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com. MediaConvert

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar trabalho de transcodificação

O exemplo de código a seguir mostra como criar um trabalho de transcodificação AWS Elemental MediaConvert.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createMediaJob(mcClient: MediaConvertClient, mcRoleARN: String,
 fileInputVal: String): String? {
    val s3path = fileInputVal.substring(0, fileInputVal.lastIndexOf('/') + 1) +
 "javasdk/out/"
    val fileOutput = s3path + "index"
    val thumbsOutput = s3path + "thumbs/"
    val mp4Output = s3path + "mp4/"

    try {
        val describeEndpoints = DescribeEndpointsRequest {
            maxResults = 20
        }

        val res = mcClient.describeEndpoints(describeEndpoints)
        if (res.endpoints?.size!! <= 0) {
            println("Cannot find MediaConvert service endpoint URL!")
            exitProcess(0)
```

```
        }
        val endpointURL = res.endpoints!!.get(0).url!!
        val mediaConvert = MediaConvertClient.fromEnvironment {
            region = "us-west-2"
            endpointProvider = MediaConvertEndpointProvider {
                Endpoint(endpointURL)
            }
        }

        // output group Preset HLS low profile
        val hlsLow = createOutput("_low", "_\$dt$", 750000, 7, 1920, 1080, 640)

        // output group Preset HLS medium profile
        val hlsMedium = createOutput("_medium", "_\$dt$", 1200000, 7, 1920, 1080,
1280)

        // output group Preset HLS high profole
        val hlsHigh = createOutput("_high", "_\$dt$", 3500000, 8, 1920, 1080, 1920)

        val outputSettings = OutputGroupSettings {
            type = OutputGroupType.HlsGroupSettings
        }

        val OutputObsList: MutableList<Output> = mutableListOf()
        if (hlsLow != null) {
            OutputObsList.add(hlsLow)
        }
        if (hlsMedium != null) {
            OutputObsList.add(hlsMedium)
        }
        if (hlsHigh != null) {
            OutputObsList.add(hlsHigh)
        }

        // Create an OutputGroup object.
        val appleHLS = OutputGroup {
            name = "Apple HLS"
            customName = "Example"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.HlsGroupSettings
                this.hlsGroupSettings = HlsGroupSettings {
                    directoryStructure = HlsDirectoryStructure.SingleDirectory
                    manifestDurationFormat = HlsManifestDurationFormat.Integer
                    streamInfResolution = HlsStreamInfResolution.Include
```

```
                clientCache = HlsClientCache.Enabled
                captionLanguageSetting = HlsCaptionLanguageSetting.Omit
                manifestCompression = HlsManifestCompression.None
                codecSpecification = HlsCodecSpecification.Rfc4281
                outputSelection = HlsOutputSelection.ManifestsAndSegments
                programDateTime = HlsProgramDateTime.Exclude
                programDateTimePeriod = 600
                timedMetadataId3Frame = HlsTimedMetadataId3Frame.Priv
                timedMetadataId3Period = 10
                destination = fileOutput
                segmentControl = HlsSegmentControl.SegmentedFiles
                minFinalSegmentLength = 0.toDouble()
                segmentLength = 4
                minSegmentLength = 1
            }
        }
        outputs = OutputObsList
    }

    val theOutput = Output {
        extension = "mp4"
        containerSettings = ContainerSettings {
            container = ContainerType.fromValue("MP4")
        }

        videoDescription = VideoDescription {
            width = 1280
            height = 720
            scalingBehavior = ScalingBehavior.Default
            sharpness = 50
            antiAlias = AntiAlias.Enabled
            timecodeInsertion = VideoTimecodeInsertion.Disabled
            colorMetadata = ColorMetadata.Insert
            respondToAfd = RespondToAfd.None
            afdSignaling = AfdSignaling.None
            dropFrameTimecode = DropFrameTimecode.Enabled
            codecSettings = VideoCodecSettings {
                codec = VideoCodec.H264
                h264Settings = H264Settings {
                    rateControlMode = H264RateControlMode.Qvbr
                    parControl = H264ParControl.InitializeFromSource
                    qualityTuningLevel = H264QualityTuningLevel.SinglePass
                    qvbrSettings = H264QvbrSettings { qvbrQualityLevel = 8 }
                    codecLevel = H264CodecLevel.Auto
```

```
                        codecProfile = H264CodecProfile.Main
                        maxBitrate = 2400000
                        framerateControl = H264FramerateControl.InitializeFromSource
                        gopSize = 2.0
                        gopSizeUnits = H264GopSizeUnits.Seconds
                        numberBFramesBetweenReferenceFrames = 2
                        gopClosedCadence = 1
                        gopBReference = H264GopBReference.Disabled
                        slowPal = H264SlowPal.Disabled
                        syntax = H264Syntax.Default
                        numberReferenceFrames = 3
                        dynamicSubGop = H264DynamicSubGop.Static
                        fieldEncoding = H264FieldEncoding.Paff
                        sceneChangeDetect = H264SceneChangeDetect.Enabled
                        minIInterval = 0
                        telecine = H264Telecine.None
                        framerateConversionAlgorithm =
H264FramerateConversionAlgorithm.DuplicateDrop
                        entropyEncoding = H264EntropyEncoding.Cabac
                        slices = 1
                        unregisteredSeiTimecode =
H264UnregisteredSeiTimecode.Disabled
                        repeatPps = H264RepeatPps.Disabled
                        adaptiveQuantization = H264AdaptiveQuantization.High
                        spatialAdaptiveQuantization =
H264SpatialAdaptiveQuantization.Enabled
                        temporalAdaptiveQuantization =
H264TemporalAdaptiveQuantization.Enabled
                        flickerAdaptiveQuantization =
H264FlickerAdaptiveQuantization.Disabled
                        softness = 0
                        interlaceMode = H264InterlaceMode.Progressive
                    }
                }
            }

            audioDescriptions = listOf(
                AudioDescription {
                    audioTypeControl = AudioTypeControl.FollowInput
                    languageCodeControl = AudioLanguageCodeControl.FollowInput
                    codecSettings = AudioCodecSettings {
                        codec = AudioCodec.Aac
                        aacSettings = AacSettings {
                            codecProfile = AacCodecProfile.Lc
```

```
                            rateControlMode = AacRateControlMode.Cbr
                            codingMode = AacCodingMode.CodingMode2_0
                            sampleRate = 44100
                            bitrate = 160000
                            rawFormat = AacRawFormat.None
                            specification = AacSpecification.Mpeg4
                            audioDescriptionBroadcasterMix =
AacAudioDescriptionBroadcasterMix.Normal
                        }
                    }
                }
            )
        }

        // Create an OutputGroup
        val fileMp4 = OutputGroup {
            name = "File Group"
            customName = "mp4"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.FileGroupSettings
                fileGroupSettings = FileGroupSettings {
                    destination = mp4Output
                }
            }
            outputs = listOf(theOutput)
        }

        val containerSettings1 = ContainerSettings {
            container = ContainerType.Raw
        }

        val thumbs = OutputGroup {
            name = "File Group"
            customName = "thumbs"
            outputGroupSettings = OutputGroupSettings {
                type = OutputGroupType.FileGroupSettings
                fileGroupSettings = FileGroupSettings {
                    destination = thumbsOutput
                }
            }

            outputs = listOf(
                Output {
                    extension = "jpg"
```

```
                this.containerSettings = containerSettings1
                videoDescription = VideoDescription {
                    scalingBehavior = ScalingBehavior.Default
                    sharpness = 50
                    antiAlias = AntiAlias.Enabled
                    timecodeInsertion = VideoTimecodeInsertion.Disabled
                    colorMetadata = ColorMetadata.Insert
                    dropFrameTimecode = DropFrameTimecode.Enabled
                    codecSettings = VideoCodecSettings {
                        codec = VideoCodec.FrameCapture
                        frameCaptureSettings = FrameCaptureSettings {
                            framerateNumerator = 1
                            framerateDenominator = 1
                            maxCaptures = 10000000
                            quality = 80
                        }
                    }
                }
            }
        )
    }

    val audioSelectors1: MutableMap<String, AudioSelector> = HashMap()
    audioSelectors1["Audio Selector 1"] =
        AudioSelector {
            defaultSelection = AudioDefaultSelection.Default
            offset = 0
        }

    val jobSettings = JobSettings {
        inputs = listOf(
            Input {
                audioSelectors = audioSelectors1
                videoSelector = VideoSelector {
                    colorSpace = ColorSpace.Follow
                    rotate = InputRotate.Degree0
                }
                filterEnable = InputFilterEnable.Auto
                filterStrength = 0
                deblockFilter = InputDeblockFilter.Disabled
                denoiseFilter = InputDenoiseFilter.Disabled
                psiControl = InputPsiControl.UsePsi
                timecodeSource = InputTimecodeSource.Embedded
```

```
                    fileInput = fileInputVal

                    outputGroups = listOf(appleHLS, thumbs, fileMp4)
                }
            )
        }

        val createJobRequest = CreateJobRequest {
            role = mcRoleARN
            settings = jobSettings
        }

        val createJobResponse = mediaConvert.createJob(createJobRequest)
        return createJobResponse.job?.id
    } catch (ex: MediaConvertException) {
        println(ex.message)
        mcClient.close()
        exitProcess(0)
    }
}

fun createOutput(
    nameModifierVal: String,
    segmentModifierVal: String,
    qvbrMaxBitrate: Int,
    qvbrQualityLevelVal: Int,
    originWidth: Int,
    originHeight: Int,
    targetWidth: Int
): Output? {
    val targetHeight = (
        (originHeight * targetWidth / originWidth).toFloat().roundToInt() -
            (originHeight * targetWidth / originWidth).toFloat().roundToInt() % 4
        )

    var output: Output?
    try {
        val audio1 = AudioDescription {
            audioTypeControl = AudioTypeControl.FollowInput
            languageCodeControl = AudioLanguageCodeControl.FollowInput
            codecSettings = AudioCodecSettings {
                codec = AudioCodec.Aac
                aacSettings = AacSettings {
                    codecProfile = AacCodecProfile.Lc
```

```
                    rateControlMode = AacRateControlMode.Cbr
                    codingMode = AacCodingMode.CodingMode2_0
                    sampleRate = 44100
                    bitrate = 96000
                    rawFormat = AacRawFormat.None
                    specification = AacSpecification.Mpeg4
                    audioDescriptionBroadcasterMix =
AacAudioDescriptionBroadcasterMix.Normal
                }
            }
        }

        output = Output {
            nameModifier = nameModifierVal
            outputSettings = OutputSettings {
                hlsSettings = HlsSettings {
                    segmentModifier = segmentModifierVal
                    audioGroupId = "program_audio"
                    iFrameOnlyManifest = HlsIFrameOnlyManifest.Exclude
                }
            }
            containerSettings = ContainerSettings {
                container = ContainerType.M3U8
                this.m3u8Settings = M3u8Settings {
                    audioFramesPerPes = 4
                    pcrControl = M3u8PcrControl.PcrEveryPesPacket
                    pmtPid = 480
                    privateMetadataPid = 503
                    programNumber = 1
                    patInterval = 0
                    pmtInterval = 0
                    scte35Source = M3u8Scte35Source.None
                    scte35Pid = 500
                    nielsenId3 = M3u8NielsenId3.None
                    timedMetadata = TimedMetadata.None
                    timedMetadataPid = 502
                    videoPid = 481
                    audioPids = listOf(482, 483, 484, 485, 486, 487, 488, 489, 490,
491, 492)
                }

                videoDescription = VideoDescription {
                    width = targetWidth
                    height = targetHeight
```

```
                    scalingBehavior = ScalingBehavior.Default
                    sharpness = 50
                    antiAlias = AntiAlias.Enabled
                    timecodeInsertion = VideoTimecodeInsertion.Disabled
                    colorMetadata = ColorMetadata.Insert
                    respondToAfd = RespondToAfd.None
                    afdSignaling = AfdSignaling.None
                    dropFrameTimecode = DropFrameTimecode.Enabled
                    codecSettings = VideoCodecSettings {
                        codec = VideoCodec.H264
                        h264Settings = H264Settings {
                            rateControlMode = H264RateControlMode.Qvbr
                            parControl = H264ParControl.InitializeFromSource
                            qualityTuningLevel = H264QualityTuningLevel.SinglePass
                            qvbrSettings = H264QvbrSettings {
                                qvbrQualityLevel = qvbrQualityLevelVal
                            }
                            codecLevel = H264CodecLevel.Auto
                            codecProfile =
                                if (targetHeight > 720 && targetWidth > 1280)
H264CodecProfile.High else H264CodecProfile.Main
                            maxBitrate = qvbrMaxBitrate
                            framerateControl =
H264FramerateControl.InitializeFromSource
                            gopSize = 2.0
                            gopSizeUnits = H264GopSizeUnits.Seconds
                            numberBFramesBetweenReferenceFrames = 2
                            gopClosedCadence = 1
                            gopBReference = H264GopBReference.Disabled
                            slowPal = H264SlowPal.Disabled
                            syntax = H264Syntax.Default
                            numberReferenceFrames = 3
                            dynamicSubGop = H264DynamicSubGop.Static
                            fieldEncoding = H264FieldEncoding.Paff
                            sceneChangeDetect = H264SceneChangeDetect.Enabled
                            minIInterval = 0
                            telecine = H264Telecine.None
                            framerateConversionAlgorithm =
H264FramerateConversionAlgorithm.DuplicateDrop
                            entropyEncoding = H264EntropyEncoding.Cabac
                            slices = 1
                            unregisteredSeiTimecode =
H264UnregisteredSeiTimecode.Disabled
                            repeatPps = H264RepeatPps.Disabled
```

```
                            adaptiveQuantization = H264AdaptiveQuantization.High
                            spatialAdaptiveQuantization =
 H264SpatialAdaptiveQuantization.Enabled
                            temporalAdaptiveQuantization =
 H264TemporalAdaptiveQuantization.Enabled
                            flickerAdaptiveQuantization =
 H264FlickerAdaptiveQuantization.Disabled
                            softness = 0
                            interlaceMode = H264InterlaceMode.Progressive
                        }
                    }
                    audioDescriptions = listOf(audio1)
                }
            }
        }
    } catch (ex: MediaConvertException) {
        println(ex.toString())
        exitProcess(0)
    }
    return output
}
```

- Para obter detalhes da API, consulte a CreateJobreferência da API AWSSDK for Kotlin.

Obter um trabalho de transcodificação

O exemplo de código a seguir mostra como obter um trabalho de transcodificação AWS Elemental MediaConvert.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSpecificJob(mcClient: MediaConvertClient, jobId: String?) {
    val describeEndpoints = DescribeEndpointsRequest {
        maxResults = 20
```

```
    }

    val res = mcClient.describeEndpoints(describeEndpoints)
    if (res.endpoints?.size!! <= 0) {
        println("Cannot find MediaConvert service endpoint URL!")
        exitProcess(0)
    }

    val endpointURL = res.endpoints!!.get(0).url!!
    val mediaConvert = MediaConvertClient.fromEnvironment {
        region = "us-west-2"
        endpointProvider = MediaConvertEndpointProvider {
            Endpoint(endpointURL)
        }
    }

    val jobRequest = GetJobRequest {
        id = jobId
    }

    val response: GetJobResponse = mediaConvert.getJob(jobRequest)
    println("The ARN of the job is ${response.job?.arn}.")
}
```

- Para obter detalhes da API, consulte a GetJobreferência da API AWSSDK for Kotlin.

Listar trabalhos de transcodificação

O exemplo de código a seguir mostra como listar trabalhos transcodificação AWS Elemental MediaConvert.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listCompleteJobs(mcClient: MediaConvertClient) {
```

```
    val describeEndpoints = DescribeEndpointsRequest {
        maxResults = 20
    }

    val res = mcClient.describeEndpoints(describeEndpoints)
    if (res.endpoints?.size!! <= 0) {
        println("Cannot find MediaConvert service endpoint URL!")
        exitProcess(0)
    }
    val endpointURL = res.endpoints!![0].url!!
    val mediaConvert = MediaConvertClient.fromEnvironment {
        region = "us-west-2"
        endpointProvider = MediaConvertEndpointProvider {
            Endpoint(endpointURL)
        }
    }

    val jobsRequest = ListJobsRequest {
        maxResults = 10
        status = JobStatus.fromValue("COMPLETE")
    }

    val jobsResponse = mediaConvert.listJobs(jobsRequest)
    val jobs = jobsResponse.jobs
    if (jobs != null) {
        for (job in jobs) {
            println("The JOB ARN is ${job.arn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWSSDK for Kotlin.

Exemplos do Amazon Pinpoint usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma campanha

O exemplo de código a seguir mostra como criar uma campanha.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createPinCampaign(appId: String, segmentIdVal: String) {

    val scheduleOb = Schedule {
        startTime = "IMMEDIATE"
    }

    val defaultMessageOb = Message {
        action = Action.OpenApp
        body = "My message body"
        title = "My message title"
    }

    val messageConfigurationOb = MessageConfiguration {
        defaultMessage = defaultMessageOb
    }

    val writeCampaign = WriteCampaignRequest {
        description = "My description"
```

```
        schedule = scheduleOb
        name = "MyCampaign"
        segmentId = segmentIdVal
        messageConfiguration = messageConfigurationOb
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result: CreateCampaignResponse = pinpoint.createCampaign(
            CreateCampaignRequest {
                applicationId = appId
                writeCampaignRequest = writeCampaign
            }
        )
        println("Campaign ID is ${result.campaignResponse?.id}")
    }
}
```

- Para obter detalhes da API, consulte a CreateCampaignreferência da API AWSSDK for Kotlin.

Criar um segmento

O exemplo de código a seguir mostra como criar um segmento.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createPinpointSegment(applicationIdVal: String?): String? {

    val segmentAttributes = mutableMapOf<String, AttributeDimension>()
    val myList = mutableListOf<String>()
    myList.add("Lakers")

    val atts = AttributeDimension {
        attributeType = AttributeType.Inclusive
        values = myList
```

```
    }

    segmentAttributes["Team"] = atts
    val recencyDimension = RecencyDimension {
        duration = Duration.fromValue("DAY_30")
        recencyType = RecencyType.fromValue("ACTIVE")
    }

    val segmentBehaviors = SegmentBehaviors {
        recency = recencyDimension
    }

    val segmentLocation = SegmentLocation {}
    val dimensionsOb = SegmentDimensions {
        attributes = segmentAttributes
        behavior = segmentBehaviors
        demographic = SegmentDemographics {}
        location = segmentLocation
    }

    val writeSegmentRequestOb = WriteSegmentRequest {
        name = "MySegment101"
        dimensions = dimensionsOb
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val createSegmentResult: CreateSegmentResponse = pinpoint.createSegment(
            CreateSegmentRequest {
                applicationId = applicationIdVal
                writeSegmentRequest = writeSegmentRequestOb
            }
        )
        println("Segment ID is ${createSegmentResult.segmentResponse?.id}")
        return createSegmentResult.segmentResponse?.id
    }
}
```

- Para obter detalhes da API, consulte a CreateSegmentreferência da API AWSSDK for Kotlin.

Cria uma aplicação

O exemplo de código a seguir mostra como criar uma aplicação.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createApplication(applicationName: String?): String? {

    val createApplicationRequestOb = CreateApplicationRequest {
        name = applicationName
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.createApp(
            CreateAppRequest {
                createApplicationRequest = createApplicationRequestOb
            }
        )
        return result.applicationResponse?.id
    }
}
```

- Para obter detalhes da API, consulte a CreateAppreferência da API AWSSDK for Kotlin.

Deleta o aplicativo

O exemplo de código a seguir mostra como excluir uma aplicação.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deletePinApp(appId: String?) {
```

```
    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.deleteApp(
            DeleteAppRequest {
                applicationId = appId
            }
        )
        val appName = result.applicationResponse?.name
        println("Application $appName has been deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteAppreferência da API AWSSDK for Kotlin.

Excluir um endpoint

O exemplo de código a seguir mostra como excluir um endpoint.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deletePinEncpoint(appIdVal: String?, endpointIdVal: String?) {

    val deleteEndpointRequest = DeleteEndpointRequest {
        applicationId = appIdVal
        endpointId = endpointIdVal
    }

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.deleteEndpoint(deleteEndpointRequest)
        val id = result.endpointResponse?.id
        println("The deleted endpoint is  $id")
    }
}
```

- Para obter detalhes da API, consulte a DeleteEndpointreferência da API AWSSDK for Kotlin.

Obter endpoints

O exemplo de código a seguir mostra como obter endpoints.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun lookupPinpointEndpoint(appId: String?, endpoint: String?) {

    PinpointClient { region = "us-west-2" }.use { pinpoint ->
        val result = pinpoint.getEndpoint(
            GetEndpointRequest {
                applicationId = appId
                endpointId = endpoint
            }
        )
        val endResponse = result.endpointResponse

        // Uses the Google Gson library to pretty print the endpoint JSON.
        val gson: com.google.gson.Gson = GsonBuilder()
            .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
            .setPrettyPrinting()
            .create()

        val endpointJson: String = gson.toJson(endResponse)
        println(endpointJson)
    }
}
```

- Para obter detalhes da API, consulte a GetEndpointreferência da API AWSSDK for Kotlin.

Listar segmentos

O exemplo de código a seguir mostra como listar segmentos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSegs(appId: String?) {

    PinpointClient { region = "us-west-2" }.use { pinpoint ->

        val response = pinpoint.getSegments(
            GetSegmentsRequest {
                applicationId = appId
            }
        )
        response.segmentsResponse?.item?.forEach { segment ->
            println("Segement id is ${segment.id}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetSegmentsreferência da API AWSSDK for Kotlin.

Envie e-mails e mensagens de texto

O exemplo de código a seguir mostra como enviar email e mensagem de texto com o Amazon Pinpoint.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

val body: String = """
        Amazon Pinpoint test (AWS SDK for Kotlin)

        This email was sent through the Amazon Pinpoint Email API using the AWS SDK
 for Kotlin.

""".trimIndent()

suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <subject> <appId> <senderAddress> <toAddress>

    Where:
        subject - The email subject to use.
        senderAddress - The from address. This address has to be verified in Amazon
 Pinpoint in the region you're using to send email
        toAddress - The to address. This address has to be verified in Amazon
 Pinpoint in the region you're using to send email
    """

    if (args.size != 3) {
        println(usage)
        exitProcess(0)
    }
```

```
    val subject = args[0]
    val senderAddress = args[1]
    val toAddress = args[2]
    sendEmail(subject, senderAddress, toAddress)
}

suspend fun sendEmail(subjectVal: String?, senderAddress: String, toAddressVal:
 String) {
    var content = Content {
        data = body
    }

    val messageBody = Body {
        text = content
    }

    val subContent = Content {
        data = subjectVal
    }

    val message = Message {
        body = messageBody
        subject = subContent
    }

    val destinationOb = Destination {
        toAddresses = listOf(toAddressVal)
    }

    val emailContent = EmailContent {
        simple = message
    }

    val sendEmailRequest = SendEmailRequest {
        fromEmailAddress = senderAddress
        destination = destinationOb
        this.content = emailContent
    }

    PinpointEmailClient { region = "us-east-1" }.use { pinpointemail ->
        pinpointemail.sendEmail(sendEmailRequest)
        println("Message Sent")
    }
}
```

- Para obter detalhes da API, consulte a SendMessagesreferência da API AWSSDK for Kotlin.

Exemplos do Amazon RDS usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

O exemplo de código a seguir mostra como criar uma instância do Amazon RDS DB e aguardar até que se torne disponível.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createDatabaseInstance(
```

```
    dbInstanceIdentifierVal: String?,
    dbNamedbVal: String?,
    masterUsernameVal: String?,
    masterUserPasswordVal: String?
) {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        allocatedStorage = 100
        dbName = dbNamedbVal
        engine = "mysql"
        dbInstanceClass = "db.m4.large"
        engineVersion = "8.0"
        storageType = "standard"
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
    }
}

// Waits until the database instance is available.
suspend fun waitForInstanceReady(dbInstanceIdentifierVal: String?) {
    val sleepTime: Long = 20
    var instanceReady = false
    var instanceReadyStr = ""
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        while (!instanceReady) {
            val response = rdsClient.describeDbInstances(instanceRequest)
            val instanceList = response.dbInstances
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus.toString()
                    if (instanceReadyStr.contains("available")) {
                        instanceReady = true
                    } else {
```

```
                        println("...$instanceReadyStr")
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
        println("Database instance is available!")
    }
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Kotlin.

Excluir uma instância de banco de dados

Os exemplos de código a seguir mostram como excluir uma instância do Amazon RDS DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteDatabaseInstance(dbInstanceIdentifierVal: String?) {

    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Kotlin.

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Amazon RDS DB

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeInstances() {

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbInstances(DescribeDbInstancesRequest {})
        response.dbInstances?.forEach { instance ->
            println("Instance Identifier is ${instance.dbInstanceIdentifier}")
            println("The Engine is ${instance.engine}")
            println("Connection endpoint is ${instance.endpoint?.address}")
        }
    }
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Kotlin.

Modificar uma instância de banco de dados

O exemplo de código a seguir mostra como modificar uma instância do Amazon RDS DB.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateIntance(dbInstanceIdentifierVal: String?, masterUserPasswordVal:
 String?) {

    val request = ModifyDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        publiclyAccessible = true
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val instanceResponse = rdsClient.modifyDbInstance(request)
        println("The ARN of the modified database is
 ${instanceResponse.dbInstance?.dbInstanceArn}")
    }
}
```

- Para ter detalhes da API, consulte ModifyDBInstance na Referência da API do AWS SDK para Kotlin.

Recuperar atributos

O exemplo de código a seguir mostra como recuperar atributos que pertencem a uma conta do Amazon RDS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getAccountAttributes() {

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeAccountAttributes(DescribeAccountAttributesRequest {})
        response.accountQuotas?.forEach { quotas ->
            val response = response.accountQuotas
            println("Name is: ${quotas.accountQuotaName}")
            println("Max value is ${quotas.max}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeAccountAttributesreferência da API AWSSDK for Kotlin.

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
```

```
Before running this code example, set up your development environment, including
 your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

This example requires an AWS Secrets Manager secret that contains the database
 credentials. If you do not create a
secret, this example will not work. For more details, see:

https://docs.aws.amazon.com/secretsmanager/latest/userguide/integrating_how-
services-use-secrets_RS.html

This example performs the following tasks:

1. Returns a list of the available DB engines by invoking the
 DescribeDbEngineVersions method.
2. Selects an engine family and create a custom DB parameter group by invoking the
 createDBParameterGroup method.
3. Gets the parameter groups by invoking the DescribeDbParameterGroups method.
4. Gets parameters in the group by invoking the DescribeDbParameters method.
5. Modifies both the auto_increment_offset and auto_increment_increment parameters
 by invoking the modifyDbParameterGroup method.
6. Gets and displays the updated parameters.
7. Gets a list of allowed engine versions by invoking the describeDbEngineVersions
 method.
8. Gets a list of micro instance classes available for the selected engine.
9. Creates an Amazon Relational Database Service (Amazon RDS) database instance that
 contains a MySQL database and uses the parameter group.
10. Waits for DB instance to be ready and prints out the connection endpoint value.
11. Creates a snapshot of the DB instance.
12. Waits for the DB snapshot to be ready.
13. Deletes the DB instance.
14. Deletes the parameter group.
 */

var sleepTime: Long = 20
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <dbGroupName> <dbParameterGroupFamily> <dbInstanceIdentifier> <dbName>
 <dbSnapshotIdentifier><secretName>
```

```
        Where:
            dbGroupName - The database group name.
            dbParameterGroupFamily - The database parameter group name.
            dbInstanceIdentifier - The database instance identifier.
            dbName -  The database name.
            dbSnapshotIdentifier - The snapshot identifier.
            secretName - The name of the AWS Secrets Manager secret that contains
the database credentials.
    """

    if (args.size != 6) {
        println(usage)
        exitProcess(1)
    }

    val dbGroupName = args[0]
    val dbParameterGroupFamily = args[1]
    val dbInstanceIdentifier = args[2]
    val dbName = args[3]
    val dbSnapshotIdentifier = args[4]
    val secretName = args[5]

    val gson = Gson()
    val user = gson.fromJson(getSecretValues(secretName).toString(),
User::class.java)
    val username = user.username
    val userPassword = user.password

    println("1. Return a list of the available DB engines")
    describeDBEngines()

    println("2. Create a custom parameter group")
    createDBParameterGroup(dbGroupName, dbParameterGroupFamily)

    println("3. Get the parameter groups")
    describeDbParameterGroups(dbGroupName)

    println("4. Get the parameters in the group")
    describeDbParameters(dbGroupName, 0)

    println("5. Modify the auto_increment_offset parameter")
    modifyDBParas(dbGroupName)

    println("6. Display the updated value")
```

```
    describeDbParameters(dbGroupName, -1)

    println("7. Get a list of allowed engine versions")
    getAllowedEngines(dbParameterGroupFamily)

    println("8. Get a list of micro instance classes available for the selected
 engine")
    getMicroInstances()

    println("9. Create an RDS database instance that contains a MySql database and
 uses the parameter group")
    val dbARN = createDatabaseInstance(dbGroupName, dbInstanceIdentifier, dbName,
 username, userPassword)
    println("The ARN of the new database is $dbARN")

    println("10. Wait for DB instance to be ready")
    waitForDbInstanceReady(dbInstanceIdentifier)

    println("11. Create a snapshot of the DB instance")
    createDbSnapshot(dbInstanceIdentifier, dbSnapshotIdentifier)

    println("12. Wait for DB snapshot to be ready")
    waitForSnapshotReady(dbInstanceIdentifier, dbSnapshotIdentifier)

    println("13. Delete the DB instance")
    deleteDbInstance(dbInstanceIdentifier)

    println("14. Delete the parameter group")
    if (dbARN != null) {
        deleteParaGroup(dbGroupName, dbARN)
    }

    println("The Scenario has successfully completed.")
}

suspend fun deleteParaGroup(dbGroupName: String, dbARN: String) {
    var isDataDel = false
    var didFind: Boolean
    var instanceARN: String

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        // Make sure that the database has been deleted.
        while (!isDataDel) {
            val response = rdsClient.describeDbInstances()
```

```
            val instanceList = response.dbInstances
            val listSize = instanceList?.size
            isDataDel = false // Reset this value.
            didFind = false // Reset this value.
            var index = 1
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceARN = instance.dbInstanceArn.toString()
                    if (instanceARN.compareTo(dbARN) == 0) {
                        println("$dbARN still exists")
                        didFind = true
                    }
                    if (index == listSize && !didFind) {
                        // Went through the entire list and did not find the
 database name.
                        isDataDel = true
                    }
                    index++
                }
            }
        }

        // Delete the para group.
        val parameterGroupRequest = DeleteDbParameterGroupRequest {
            dbParameterGroupName = dbGroupName
        }
        rdsClient.deleteDbParameterGroup(parameterGroupRequest)
        println("$dbGroupName was deleted.")
    }
}

suspend fun deleteDbInstance(dbInstanceIdentifierVal: String) {
    val deleteDbInstanceRequest = DeleteDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        deleteAutomatedBackups = true
        skipFinalSnapshot = true
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.deleteDbInstance(deleteDbInstanceRequest)
        print("The status of the database is
 ${response.dbInstance?.dbInstanceStatus}")
    }
}
```

```
// Waits until the snapshot instance is available.
suspend fun waitForSnapshotReady(dbInstanceIdentifierVal: String?,
 dbSnapshotIdentifierVal: String?) {
    var snapshotReady = false
    var snapshotReadyStr: String
    println("Waiting for the snapshot to become available.")

    val snapshotsRequest = DescribeDbSnapshotsRequest {
        dbSnapshotIdentifier = dbSnapshotIdentifierVal
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }

    while (!snapshotReady) {
        RdsClient { region = "us-west-2" }.use { rdsClient ->
            val response = rdsClient.describeDbSnapshots(snapshotsRequest)
            val snapshotList: List<DbSnapshot>? = response.dbSnapshots
            if (snapshotList != null) {
                for (snapshot in snapshotList) {
                    snapshotReadyStr = snapshot.status.toString()
                    if (snapshotReadyStr.contains("available")) {
                        snapshotReady = true
                    } else {
                        print(".")
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
    }
    println("The Snapshot is available!")
}

// Create an Amazon RDS snapshot.
suspend fun createDbSnapshot(dbInstanceIdentifierVal: String?,
 dbSnapshotIdentifierVal: String?) {
    val snapshotRequest = CreateDbSnapshotRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        dbSnapshotIdentifier = dbSnapshotIdentifierVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbSnapshot(snapshotRequest)
        print("The Snapshot id is ${response.dbSnapshot?.dbiResourceId}")
```

```
    }
}

// Waits until the database instance is available.
suspend fun waitForDbInstanceReady(dbInstanceIdentifierVal: String?) {
    var instanceReady = false
    var instanceReadyStr: String
    println("Waiting for instance to become available.")

    val instanceRequest = DescribeDbInstancesRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
    }
    var endpoint = ""
    while (!instanceReady) {
        RdsClient { region = "us-west-2" }.use { rdsClient ->
            val response = rdsClient.describeDbInstances(instanceRequest)
            val instanceList = response.dbInstances
            if (instanceList != null) {
                for (instance in instanceList) {
                    instanceReadyStr = instance.dbInstanceStatus.toString()
                    if (instanceReadyStr.contains("available")) {
                        endpoint = instance.endpoint?.address.toString()
                        instanceReady = true
                    } else {
                        print(".")
                        delay(sleepTime * 1000)
                    }
                }
            }
        }
    }
    println("Database instance is available! The connection endpoint is $endpoint")
}

// Create a database instance and return the ARN of the database.
suspend fun createDatabaseInstance(dbGroupNameVal: String?, dbInstanceIdentifierVal:
 String?, dbNameVal: String?, masterUsernameVal: String?, masterUserPasswordVal:
 String?): String? {
    val instanceRequest = CreateDbInstanceRequest {
        dbInstanceIdentifier = dbInstanceIdentifierVal
        allocatedStorage = 100
        dbName = dbNameVal
        dbParameterGroupName = dbGroupNameVal
        engine = "mysql"
```

```
        dbInstanceClass = "db.m4.large"
        engineVersion = "8.0"
        storageType = "standard"
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbInstance(instanceRequest)
        print("The status is ${response.dbInstance?.dbInstanceStatus}")
        return response.dbInstance?.dbInstanceArn
    }
}

// Get a list of micro instances.
suspend fun getMicroInstances() {
    val dbInstanceOptionsRequest = DescribeOrderableDbInstanceOptionsRequest {
        engine = "mysql"
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response =
 rdsClient.describeOrderableDbInstanceOptions(dbInstanceOptionsRequest)
        val orderableDBInstances = response.orderableDbInstanceOptions
        if (orderableDBInstances != null) {
            for (dbInstanceOption in orderableDBInstances) {
                println("The engine version is ${dbInstanceOption.engineVersion}")
                println("The engine description is ${dbInstanceOption.engine}")
            }
        }
    }
}

// Get a list of allowed engine versions.
suspend fun getAllowedEngines(dbParameterGroupFamilyVal: String?) {
    val versionsRequest = DescribeDbEngineVersionsRequest {
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        engine = "mysql"
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(versionsRequest)
        val dbEngines: List<DbEngineVersion>? = response.dbEngineVersions
        if (dbEngines != null) {
            for (dbEngine in dbEngines) {
                println("The engine version is ${dbEngine.engineVersion}")
```

```
                println("The engine description is ${dbEngine.dbEngineDescription}")
            }
        }
    }
}

// Modify the auto_increment_offset parameter.
suspend fun modifyDBParas(dbGroupName: String) {
    val parameter1 = Parameter {
        parameterName = "auto_increment_offset"
        applyMethod = ApplyMethod.Immediate
        parameterValue = "5"
    }

    val paraList: ArrayList<Parameter> = ArrayList()
    paraList.add(parameter1)
    val groupRequest = ModifyDbParameterGroupRequest {
        dbParameterGroupName = dbGroupName
        parameters = paraList
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.modifyDbParameterGroup(groupRequest)
        println("The parameter group ${response.dbParameterGroupName} was
 successfully modified")
    }
}

// Retrieve parameters in the group.
suspend fun describeDbParameters(dbGroupName: String?, flag: Int) {
    val dbParameterGroupsRequest: DescribeDbParametersRequest
    dbParameterGroupsRequest = if (flag == 0) {
        DescribeDbParametersRequest {
            dbParameterGroupName = dbGroupName
        }
    } else {
        DescribeDbParametersRequest {
            dbParameterGroupName = dbGroupName
            source = "user"
        }
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbParameters(dbParameterGroupsRequest)
        val dbParameters: List<Parameter>? = response.parameters
```

```
        var paraName: String
        if (dbParameters != null) {
            for (para in dbParameters) {
                // Only print out information about either auto_increment_offset or
 auto_increment_increment.
                paraName = para.parameterName.toString()
                if (paraName.compareTo("auto_increment_offset") == 0 ||
 paraName.compareTo("auto_increment_increment ") == 0) {
                    println("*** The parameter name is  $paraName")
                    System.out.println("*** The parameter value is
 ${para.parameterValue}")
                    System.out.println("*** The parameter data type is
 ${para.dataType}")
                    System.out.println("*** The parameter description is
 ${para.description}")
                    System.out.println("*** The parameter allowed values  is
 ${para.allowedValues}")
                }
            }
        }
    }
}

suspend fun describeDbParameterGroups(dbGroupName: String?) {
    val groupsRequest = DescribeDbParameterGroupsRequest {
        dbParameterGroupName = dbGroupName
        maxRecords = 20
    }
    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbParameterGroups(groupsRequest)
        val groups = response.dbParameterGroups
        if (groups != null) {
            for (group in groups) {
                println("The group name is ${group.dbParameterGroupName}")
                println("The group description is ${group.description}")
            }
        }
    }
}

// Create a parameter group.
suspend fun createDBParameterGroup(dbGroupName: String?, dbParameterGroupFamilyVal:
 String?) {
    val groupRequest = CreateDbParameterGroupRequest {
```

```
        dbParameterGroupName = dbGroupName
        dbParameterGroupFamily = dbParameterGroupFamilyVal
        description = "Created by using the AWS SDK for Kotlin"
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.createDbParameterGroup(groupRequest)
        println("The group name is
 ${response.dbParameterGroup?.dbParameterGroupName}")
    }
}

// Returns a list of the available DB engines.
suspend fun describeDBEngines() {
    val engineVersionsRequest = DescribeDbEngineVersionsRequest {
        defaultOnly = true
        engine = "mysql"
        maxRecords = 20
    }

    RdsClient { region = "us-west-2" }.use { rdsClient ->
        val response = rdsClient.describeDbEngineVersions(engineVersionsRequest)
        val engines: List<DbEngineVersion>? = response.dbEngineVersions

        // Get all DbEngineVersion objects.
        if (engines != null) {
            for (engineOb in engines) {
                println("The name of the DB parameter group family for the database
 engine is ${engineOb.dbParameterGroupFamily}.")
                println("The name of the database engine ${engineOb.engine}.")
                println("The version number of the database engine
 ${engineOb.engineVersion}")
            }
        }
    }
}

suspend fun getSecretValues(secretName: String?): String? {
    val valueRequest = GetSecretValueRequest {
        secretId = secretName
    }

    SecretsManagerClient { region = "us-west-2" }.use { secretsClient ->
        val valueResponse = secretsClient.getSecretValue(valueRequest)
```

```
        return valueResponse.secretString
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

Exemplos do Amazon Redshift usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon Redshift.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um cluster

O exemplo de código a seguir mostra como criar um cluster do Amazon Redshift.

SDK for Kotlin

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie o cluster.

```
suspend fun createCluster(clusterId: String?, masterUsernameVal: String?,
 masterUserPasswordVal: String?) {
    val clusterRequest = CreateClusterRequest {
        clusterIdentifier = clusterId
        masterUsername = masterUsernameVal
        masterUserPassword = masterUserPasswordVal
        nodeType = "ds2.xlarge"
        publiclyAccessible = true
        numberOfNodes = 2
    }

    RedshiftClient { region = "us-east-1" }.use { redshiftClient ->
        val clusterResponse = redshiftClient.createCluster(clusterRequest)
        println("Created cluster ${clusterResponse.cluster?.clusterIdentifier}")
    }
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWSSDK for Kotlin.

Excluir um cluster

O exemplo de código a seguir mostra como excluir um cluster do Amazon Redshift.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir o cluster.

```
suspend fun deleteRedshiftCluster(clusterId: String?) {

    val request = DeleteClusterRequest {
        clusterIdentifier = clusterId
        skipFinalClusterSnapshot = true
    }

    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
        val response = redshiftClient.deleteCluster(request)
        println("The status is ${response.cluster?.clusterStatus}")
    }
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWSSDK for Kotlin.

Descrever seus clusters

O exemplo de código a seguir mostra como descrever clusters do Amazon Redshift.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Descrever o cluster.

```
suspend fun describeRedshiftClusters() {
```

```
    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
        val clusterResponse =
 redshiftClient.describeClusters(DescribeClustersRequest {})
        val clusterList = clusterResponse.clusters

        if (clusterList != null) {
            for (cluster in clusterList) {
                println("Cluster database name is ${cluster.dbName}")
                println("Cluster status is ${cluster.clusterStatus}")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeClustersreferência da API AWSSDK for Kotlin.

Modificar um cluster

O exemplo de código a seguir mostra como modificar um cluster do Amazon Redshift.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Modifique um cluster.

```
suspend fun modifyCluster(clusterId: String?) {
    val modifyClusterRequest = ModifyClusterRequest {
        clusterIdentifier = clusterId
        preferredMaintenanceWindow = "wed:07:30-wed:08:00"
    }

    RedshiftClient { region = "us-west-2" }.use { redshiftClient ->
        val clusterResponse = redshiftClient.modifyCluster(modifyClusterRequest)
        println("The modified cluster was successfully modified and has
 ${clusterResponse.cluster?.preferredMaintenanceWindow} as the maintenance window")
```

```
    }
}
```

- Para obter detalhes da API, consulte a ModifyClusterreferência da API AWSSDK for Kotlin.

Exemplos do Amazon Rekognition usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon Rekognition.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Comparar faces em uma imagem com uma imagem de referência

O exemplo de código a seguir mostra como comparar faces em uma imagem com uma imagem de referência usando o Amazon Rekognition.

Para obter mais informações, consulte Comparação de faces em imagens.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun compareTwoFaces(similarityThresholdVal: Float, sourceImageVal: String,
 targetImageVal: String) {

    val sourceBytes = (File(sourceImageVal).readBytes())
    val targetBytes = (File(targetImageVal).readBytes())

    // Create an Image object for the source image.
    val souImage = Image {
        bytes = sourceBytes
    }

    val tarImage = Image {
        bytes = targetBytes
    }

    val facesRequest = CompareFacesRequest {
        sourceImage = souImage
        targetImage = tarImage
        similarityThreshold = similarityThresholdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->

        val compareFacesResult = rekClient.compareFaces(facesRequest)
        val faceDetails = compareFacesResult.faceMatches

        if (faceDetails != null) {
            for (match: CompareFacesMatch in faceDetails) {
                val face = match.face
                val position = face?.boundingBox
                if (position != null)
                    println("Face at ${position.left} ${position.top} matches with
 ${face.confidence} % confidence.")
            }
        }

        val uncompared = compareFacesResult.unmatchedFaces
        if (uncompared != null)
            println("There was ${uncompared.size} face(s) that did not match")

        println("Source image rotation:
 ${compareFacesResult.sourceImageOrientationCorrection}")
```

```
        println("target image rotation:
 ${compareFacesResult.targetImageOrientationCorrection}")
    }
}
```

- Para obter detalhes da API, consulte a CompareFacesreferência da API AWSSDK for Kotlin.

Criar uma coleção

O exemplo de código a seguir mostra como criar uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Criar uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createMyCollection(collectionIdVal: String) {

    val request = CreateCollectionRequest {
        collectionId = collectionIdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.createCollection(request)
        println("Collection ARN is ${response.collectionArn}")
        println("Status code is ${response.statusCode}")
    }
}
```

- Para obter detalhes da API, consulte a CreateCollectionreferência da API AWSSDK for Kotlin.

Excluir uma coleção.

O exemplo de código a seguir mostra como excluir uma coleção do Amazon Rekognition.

Para mais informações, consulte Excluir uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMyCollection(collectionIdVal: String) {

    val request = DeleteCollectionRequest {
        collectionId = collectionIdVal
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.deleteCollection(request)
        println("The collectionId status is ${response.statusCode}")
    }
}
```

- Para obter detalhes da API, consulte a DeleteCollectionreferência da API AWSSDK for Kotlin.

Excluir faces de uma coleção

O exemplo de código a seguir mostra como excluir faces de uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir faces de uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteFacesCollection(collectionIdVal: String?, faceIdVal: String) {
```

```
    val deleteFacesRequest = DeleteFacesRequest {
        collectionId = collectionIdVal
        faceIds = listOf(faceIdVal)
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        rekClient.deleteFaces(deleteFacesRequest)
        println("$faceIdVal was deleted from the collection")
    }
}
```

- Para obter detalhes da API, consulte a DeleteFacesreferência da API AWSSDK for Kotlin.

Descrever uma coleção

O exemplo de código a seguir mostra como descrever uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Descrever uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeColl(collectionName: String) {

    val request = DescribeCollectionRequest {
        collectionId = collectionName
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.describeCollection(request)
        println("The collection Arn is ${response.collectionArn}")
        println("The collection contains this many faces ${response.faceCount}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeCollectionreferência da API AWSSDK for Kotlin.

Detectar faces em uma imagem

O exemplo de código a seguir mostra como detectar faces em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar faces em uma imagem.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectFacesinImage(sourceImage: String?) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = DetectFacesRequest {
        attributes = listOf(Attribute.All)
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectFaces(request)
        response.faceDetails?.forEach { face ->
            val ageRange = face.ageRange
            println("The detected face is estimated to be between ${ageRange?.low}
 and ${ageRange?.high} years old.")
            println("There is a smile ${face.smile?.value}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectFacesreferência da API AWSSDK for Kotlin.

Para detectar rótulos em uma imagem

O exemplo de código a seguir mostra como detectar rótulos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar rótulos em uma imagem.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectImageLabels(sourceImage: String) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }
    val request = DetectLabelsRequest {
        image = souImage
        maxLabels = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectLabels(request)
        response.labels?.forEach { label ->
            println("${label.name} : ${label.confidence}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectLabelsreferência da API AWSSDK for Kotlin.

Detectar rótulos de moderação em uma imagem

O exemplo de código a seguir mostra como detectar rótulos de moderação em uma imagem com o Amazon Rekognition. Os rótulos de moderação identificam o conteúdo que pode ser inadequado para alguns públicos.

Para obter mais informações, consulte Detectar imagens inapropriadas.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectModLabels(sourceImage: String) {

    val myImage = Image {
        this.bytes = (File(sourceImage).readBytes())
    }

    val request = DetectModerationLabelsRequest {
        image = myImage
        minConfidence = 60f
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectModerationLabels(request)
        response.moderationLabels?.forEach { label ->
            println("Label: ${label.name} - Confidence: ${label.confidence} %
 Parent: ${label.parentName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectModerationLabelsreferência da API AWSSDK for Kotlin.

Detectar texto em uma imagem

O exemplo de código a seguir mostra como detectar texto em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar texto em uma imagem.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun detectTextLabels(sourceImage: String?) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = DetectTextRequest {
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.detectText(request)
        response.textDetections?.forEach { text ->
            println("Detected: ${text.detectedText}")
            println("Confidence: ${text.confidence}")
            println("Id: ${text.id}")
            println("Parent Id:  ${text.parentId}")
            println("Type: ${text.type}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DetectTextreferência da API AWSSDK for Kotlin.

Indexar faces de uma coleção

O exemplo de código a seguir mostra como indexar faces em uma imagem e adicioná-las a uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Adicionar faces a uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addToCollection(collectionIdVal: String?, sourceImage: String) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = IndexFacesRequest {
        collectionId = collectionIdVal
        image = souImage
        maxFaces = 1
        qualityFilter = QualityFilter.Auto
        detectionAttributes = listOf(Attribute.Default)
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val facesResponse = rekClient.indexFaces(request)

        // Display the results.
        println("Results for the image")
        println("\n Faces indexed:")
        facesResponse.faceRecords?.forEach { faceRecord ->
            println("Face ID: ${faceRecord.face?.faceId}")
            println("Location: ${faceRecord.faceDetail?.boundingBox}")
        }

        println("Faces not indexed:")
        facesResponse.unindexedFaces?.forEach { unindexedFace ->
```

```
            println("Location: ${unindexedFace.faceDetail?.boundingBox}")
            println("Reasons:")

            unindexedFace.reasons?.forEach { reason ->
                println("Reason:  $reason")
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a IndexFacesreferência da API AWSSDK for Kotlin.

Listar coleções

O exemplo de código a seguir mostra como listar coleções do Amazon Rekognition.

Para obter mais informações, consulte Listar coleções.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllCollections() {

    val request = ListCollectionsRequest {
        maxResults = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.listCollections(request)
        response.collectionIds?.forEach { resultId ->
            println(resultId)
        }
    }
}
```

- Para obter detalhes da API, consulte a ListCollectionsreferência da API AWSSDK for Kotlin.

Listar faces em uma coleção

O exemplo de código a seguir mostra como lista faces em uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Listar faces em uma coleção.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listFacesCollection(collectionIdVal: String?) {

    val request = ListFacesRequest {
        collectionId = collectionIdVal
        maxResults = 10
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.listFaces(request)
        response.faces?.forEach { face ->
            println("Confidence level there is a face: ${face.confidence}")
            println("The face Id value is ${face.faceId}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListFacesreferência da API AWSSDK for Kotlin.

Reconhecer celebridades em uma imagem

O exemplo de código a seguir mostra como reconhecer celebridades em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Reconhecer celebridades em uma imagem.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun recognizeAllCelebrities(sourceImage: String?) {

    val souImage = Image {
        bytes = (File(sourceImage).readBytes())
    }

    val request = RecognizeCelebritiesRequest {
        image = souImage
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val response = rekClient.recognizeCelebrities(request)
        response.celebrityFaces?.forEach { celebrity ->
            println("Celebrity recognized: ${celebrity.name}")
            println("Celebrity ID:${celebrity.id}")
            println("Further information (if available):")
            celebrity.urls?.forEach { url ->
                println(url)
            }
        }
        println("${response.unrecognizedFaces?.size} face(s) were unrecognized.")
    }
}
```

- Para obter detalhes da API, consulte a RecognizeCelebritiesreferência da API AWSSDK for Kotlin.

Cenários

Detectar informações em vídeos

O código de exemplo a seguir mostra como:

- Inicie trabalhos do Amazon Rekognition para detectar elementos como pessoas, objetos e texto em vídeos.
- Verificar o status do trabalho até que eles terminem.
- Visualizar a lista de elementos detectados por cada trabalho.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Detectar faces em um vídeo armazenado em um bucket do Amazon S3.

```
suspend fun startFaceDetection(channelVal: NotificationChannel?, bucketVal: String,
 videoVal: String) {

    val s3Obj = S3Object {
        bucket = bucketVal
        name = videoVal
    }
    val vidOb = Video {
        s3Object = s3Obj
    }

    val request = StartFaceDetectionRequest {
        jobTag = "Faces"
        faceAttributes = FaceAttributes.All
        notificationChannel = channelVal
        video = vidOb
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val startLabelDetectionResult = rekClient.startFaceDetection(request)
        startJobId = startLabelDetectionResult.jobId.toString()
    }
}

suspend fun getFaceResults() {
```

```
    var finished = false
    var status: String
    var yy = 0
    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        var response: GetFaceDetectionResponse? = null

        val recognitionRequest = GetFaceDetectionRequest {
            jobId = startJobId
            maxResults = 10
        }

        // Wait until the job succeeds.
        while (!finished) {
            response = rekClient.getFaceDetection(recognitionRequest)
            status = response.jobStatus.toString()
            if (status.compareTo("SUCCEEDED") == 0)
                finished = true
            else {
                println("$yy status is: $status")
                delay(1000)
            }
            yy++
        }

        // Proceed when the job is done - otherwise VideoMetadata is null.
        val videoMetaData = response?.videoMetadata
        println("Format: ${videoMetaData?.format}")
        println("Codec: ${videoMetaData?.codec}")
        println("Duration: ${videoMetaData?.durationMillis}")
        println("FrameRate: ${videoMetaData?.frameRate}")

        // Show face information.
        response?.faces?.forEach { face ->
            println("Age: ${face.face?.ageRange}")
            println("Face: ${face.face?.beard}")
            println("Eye glasses: ${face?.face?.eyeglasses}")
            println("Mustache: ${face.face?.mustache}")
            println("Smile: ${face.face?.smile}")
        }
    }
}
```

Detectar conteúdo inapropriado ou ofensivo em um vídeo armazenado em um bucket do Amazon S3.

```
suspend fun startModerationDetection(channel: NotificationChannel?, bucketVal:
 String?, videoVal: String?) {

    val s3Obj = S3Object {
        bucket = bucketVal
        name = videoVal
    }
    val vidOb = Video {
        s3Object = s3Obj
    }
    val request = StartContentModerationRequest {
        jobTag = "Moderation"
        notificationChannel = channel
        video = vidOb
    }

    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        val startModDetectionResult = rekClient.startContentModeration(request)
        startJobId = startModDetectionResult.jobId.toString()
    }
}

suspend fun getModResults() {
    var finished = false
    var status: String
    var yy = 0
    RekognitionClient { region = "us-east-1" }.use { rekClient ->
        var modDetectionResponse: GetContentModerationResponse? = null

        val modRequest = GetContentModerationRequest {
            jobId = startJobId
            maxResults = 10
        }

        // Wait until the job succeeds.
        while (!finished) {
            modDetectionResponse = rekClient.getContentModeration(modRequest)
            status = modDetectionResponse.jobStatus.toString()
            if (status.compareTo("SUCCEEDED") == 0)
                finished = true
```

```
            else {
                println("$yy status is: $status")
                delay(1000)
            }
            yy++
        }

        // Proceed when the job is done - otherwise VideoMetadata is null.
        val videoMetaData = modDetectionResponse?.videoMetadata
        println("Format: ${videoMetaData?.format}")
        println("Codec: ${videoMetaData?.codec}")
        println("Duration: ${videoMetaData?.durationMillis}")
        println("FrameRate: ${videoMetaData?.frameRate}")

        modDetectionResponse?.moderationLabels?.forEach { mod ->
            val seconds: Long = mod.timestamp / 1000
            print("Mod label: $seconds ")
            println(mod.moderationLabel)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - GetCelebrityRecognition
  - GetContentModeration
  - GetLabelDetection
  - GetPersonTracking
  - GetSegmentDetection
  - GetTextDetection
  - StartCelebrityRecognition
  - StartContentModeration
  - StartLabelDetection
  - StartPersonTracking
  - StartSegmentDetection
  - StartTextDetection

Exemplos de registro de domínio Route 53 usando SDKs para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o registro de domínio do Route 53.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Registro de domínios do Hello Route 53

O exemplo de código a seguir mostra como começar a usar o registro de domínios do Route 53.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
           <domainType>
```

```
       Where:
           domainType - The domain type (for example, com).
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val domainType = args[0]
    println("Invokes ListPrices using a Paginated method.")
    listPricesPaginated(domainType)
}

suspend fun listPricesPaginated(domainType: String) {
    val pricesRequest = ListPricesRequest {
        maxItems = 10
        tld = domainType
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListPricesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Verificar disponibilidade de domínios

Os exemplos de código a seguir mostram como verificar a disponibilidade de um domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkDomainAvailability(domainSuggestion: String) {
    val availabilityRequest = CheckDomainAvailabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainAvailability(availabilityRequest)
        println("$domainSuggestion is ${response.availability}")
    }
}
```

- Para obter detalhes da API, consulte a CheckDomainAvailabilityreferência da API AWSSDK for Kotlin.

Verificar a transferibilidade de um domínio

Os exemplos de código a seguir mostram como verificar o potencial para transferência de um domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun checkDomainTransferability(domainSuggestion: String?) {
    val transferabilityRequest = CheckDomainTransferabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainTransferability(transferabilityRequest)
        println("Transferability: ${response.transferability?.transferable}")
    }
}
```

- Para obter detalhes da API, consulte a CheckDomainTransferabilityreferência da API AWSSDK for Kotlin.

Obter detalhes de um domínio

Os exemplos de código a seguir mostram como obter os detalhes de um domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getDomainDetails(domainSuggestion: String?) {
    val detailRequest = GetDomainDetailRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainDetail(detailRequest)
        println("The contact first name is
 ${response.registrantContact?.firstName}")
        println("The contact last name is ${response.registrantContact?.lastName}")
        println("The contact org name is
 ${response.registrantContact?.organizationName}")
    }
}
```

- Para obter detalhes da API, consulte a GetDomainDetailreferência da API AWSSDK for Kotlin.

Obter detalhes de uma operação

O exemplo de código a seguir mostra como obter os detalhes de uma operação.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getOperationalDetail(opId: String?) {
    val detailRequest = GetOperationDetailRequest {
        operationId = opId
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getOperationDetail(detailRequest)
        println("Operation detail message is ${response.message}")
    }
}
```

- Para obter detalhes da API, consulte a GetOperationDetailreferência da API AWSSDK for Kotlin.

Obter nomes de domínio sugeridos

O exemplo de código a seguir mostra como obter sugestões de nomes de domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDomainSuggestions(domainSuggestion: String?) {
    val suggestionsRequest = GetDomainSuggestionsRequest {
        domainName = domainSuggestion
        suggestionCount = 5
        onlyAvailable = true
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainSuggestions(suggestionsRequest)
        response.suggestionsList?.forEach { suggestion ->
            println("Suggestion Name: ${suggestion.domainName}")
            println("Availability: ${suggestion.availability}")
            println(" ")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetDomainSuggestionsreferência da API AWSSDK for Kotlin.

Listar preços de domínios

O exemplo de código a seguir mostra como listar preços de domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllPrices(domainType: String?) {
    val pricesRequest = ListPricesRequest {
        tld = domainType
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListPricesreferência da API AWSSDK for Kotlin.

Listar domínios

O exemplo de código a seguir mostra como listar os domínios registrados.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listDomains() {
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listDomainsPaginated(ListDomainsRequest {})
            .transform { it.domains?.forEach { obj -> emit(obj) } }
            .collect { content ->
```

```
                println("The domain name is ${content.domainName}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListDomainsreferência da API AWSSDK for Kotlin.

Operações de lista

O exemplo de código a seguir mostra como listar operações.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listOperations() {
    val currentDate = Date()
    var localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    localDateTime = localDateTime.minusYears(1)
    val myTime: java.time.Instant? = localDateTime.toInstant(zoneOffset)
    val time2: Instant? = myTime?.let { Instant(it) }
    val operationsRequest = ListOperationsRequest {
        submittedSince = time2
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listOperationsPaginated(operationsRequest)
            .transform { it.operations?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("Operation Id: ${content.operationId}")
                println("Status: ${content.status}")
                println("Date: ${content.submittedDate}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListOperationsreferência da API AWSSDK for Kotlin.

Registrar um domínio

O exemplo de código a seguir mostra como registrar um domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun requestDomainRegistration(domainSuggestion: String?, phoneNumberVal:
 String?, emailVal: String?, firstNameVal: String?, lastNameVal: String?, cityVal:
 String?): String? {
    val contactDetail = ContactDetail {
        contactType = ContactType.Company
        state = "LA"
        countryCode = CountryCode.In
        email = emailVal
        firstName = firstNameVal
        lastName = lastNameVal
        city = cityVal
        phoneNumber = phoneNumberVal
        organizationName = "My Org"
        addressLine1 = "My Address"
        zipCode = "123 123"
    }

    val domainRequest = RegisterDomainRequest {
        adminContact = contactDetail
        registrantContact = contactDetail
        techContact = contactDetail
        domainName = domainSuggestion
        autoRenew = true
        durationInYears = 1
    }
```

```
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.registerDomain(domainRequest)
        println("Registration requested. Operation Id: ${response.operationId}")
        return response.operationId
    }
}
```

- Para obter detalhes da API, consulte a RegisterDomainreferência da API AWSSDK for Kotlin.

Exibir faturamento

O exemplo de código a seguir mostra como visualizar registros de cobrança.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBillingRecords() {
    val currentDate = Date()
    val localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    val localDateTime2 = localDateTime.minusYears(1)
    val myStartTime = localDateTime2.toInstant(zoneOffset)
    val myEndTime = localDateTime.toInstant(zoneOffset)
    val timeStart: Instant? = myStartTime?.let { Instant(it) }
    val timeEnd: Instant? = myEndTime?.let { Instant(it) }

    val viewBillingRequest = ViewBillingRequest {
        start = timeStart
        end = timeEnd
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.viewBillingPaginated(viewBillingRequest)
            .transform { it.billingRecords?.forEach { obj -> emit(obj) } }
            .collect { billing ->
```

```
                println("Bill Date: ${billing.billDate}")
                println("Operation: ${billing.operation}")
                println("Price: ${billing.price}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ViewBillingreferência da API AWSSDK for Kotlin.

Cenários

Conceitos básicos de domínios

O código de exemplo a seguir mostra como:

- Liste os domínios atuais e as operações do ano passado.
- Veja o faturamento do ano passado e os preços dos tipos de domínio.
- Receba sugestões de domínio.
- Verifique a disponibilidade e a transferibilidade de um domínio.
- Opcionalmente, solicite o registro de um domínio.
- Obtenha os detalhes de uma operação.
- Opcionalmente, obtenha os detalhes de um domínio.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
```

```
This Kotlin code example performs the following operations:

1. List current domains.
2. List operations in the past year.
3. View billing for the account in the past year.
4. View prices for domain types.
5. Get domain suggestions.
6. Check domain availability.
7. Check domain transferability.
8. Request a domain registration.
9. Get operation details.
10. Optionally, get domain details.
 */

val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
        Usage:
            <domainType> <phoneNumber> <email> <domainSuggestion> <firstName>
 <lastName> <city>
        Where:
           domainType - The domain type (for example, com).
           phoneNumber - The phone number to use (for example, +1.2065550100)
           email - The email address to use.
           domainSuggestion - The domain suggestion (for example, findmy.example).
           firstName - The first name to use to register a domain.
           lastName -  The last name to use to register a domain.
           city - The city to use to register a domain.
    """

    if (args.size != 7) {
        println(usage)
        exitProcess(1)
    }

    val domainType = args[0]
    val phoneNumber = args[1]
    val email = args[2]
    val domainSuggestion = args[3]
    val firstName = args[4]
    val lastName = args[5]
    val city = args[6]
```

```
    println(DASHES)
    println("Welcome to the Amazon Route 53 domains example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. List current domains.")
    listDomains()
    println(DASHES)

    println(DASHES)
    println("2. List operations in the past year.")
    listOperations()
    println(DASHES)

    println(DASHES)
    println("3. View billing for the account in the past year.")
    listBillingRecords()
    println(DASHES)

    println(DASHES)
    println("4. View prices for domain types.")
    listAllPrices(domainType)
    println(DASHES)

    println(DASHES)
    println("5. Get domain suggestions.")
    listDomainSuggestions(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("6. Check domain availability.")
    checkDomainAvailability(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("7. Check domain transferability.")
    checkDomainTransferability(domainSuggestion)
    println(DASHES)

    println(DASHES)
    println("8. Request a domain registration.")
    val opId = requestDomainRegistration(domainSuggestion, phoneNumber, email,
firstName, lastName, city)
    println(DASHES)
```

```
    println(DASHES)
    println("9. Get operation details.")
    getOperationalDetail(opId)
    println(DASHES)

    println(DASHES)
    println("10. Get domain details.")
    println("Note: You must have a registered domain to get details.")
    println("Otherwise an exception is thrown that states ")
    println("Domain xxxxxxx not found in xxxxxxx account.")
    getDomainDetails(domainSuggestion)
    println(DASHES)
}

suspend fun getDomainDetails(domainSuggestion: String?) {
    val detailRequest = GetDomainDetailRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainDetail(detailRequest)
        println("The contact first name is
 ${response.registrantContact?.firstName}")
        println("The contact last name is ${response.registrantContact?.lastName}")
        println("The contact org name is
 ${response.registrantContact?.organizationName}")
    }
}

suspend fun getOperationalDetail(opId: String?) {
    val detailRequest = GetOperationDetailRequest {
        operationId = opId
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getOperationDetail(detailRequest)
        println("Operation detail message is ${response.message}")
    }
}

suspend fun requestDomainRegistration(domainSuggestion: String?, phoneNumberVal:
 String?, emailVal: String?, firstNameVal: String?, lastNameVal: String?, cityVal:
 String?): String? {
    val contactDetail = ContactDetail {
        contactType = ContactType.Company
```

```
        state = "LA"
        countryCode = CountryCode.In
        email = emailVal
        firstName = firstNameVal
        lastName = lastNameVal
        city = cityVal
        phoneNumber = phoneNumberVal
        organizationName = "My Org"
        addressLine1 = "My Address"
        zipCode = "123 123"
    }

    val domainRequest = RegisterDomainRequest {
        adminContact = contactDetail
        registrantContact = contactDetail
        techContact = contactDetail
        domainName = domainSuggestion
        autoRenew = true
        durationInYears = 1
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.registerDomain(domainRequest)
        println("Registration requested. Operation Id: ${response.operationId}")
        return response.operationId
    }
}

suspend fun checkDomainTransferability(domainSuggestion: String?) {
    val transferabilityRequest = CheckDomainTransferabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response =
 route53DomainsClient.checkDomainTransferability(transferabilityRequest)
        println("Transferability: ${response.transferability?.transferable}")
    }
}

suspend fun checkDomainAvailability(domainSuggestion: String) {
    val availabilityRequest = CheckDomainAvailabilityRequest {
        domainName = domainSuggestion
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
```

```
        val response =
 route53DomainsClient.checkDomainAvailability(availabilityRequest)
        println("$domainSuggestion is ${response.availability}")
    }
}

suspend fun listDomainSuggestions(domainSuggestion: String?) {
    val suggestionsRequest = GetDomainSuggestionsRequest {
        domainName = domainSuggestion
        suggestionCount = 5
        onlyAvailable = true
    }
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        val response = route53DomainsClient.getDomainSuggestions(suggestionsRequest)
        response.suggestionsList?.forEach { suggestion ->
            println("Suggestion Name: ${suggestion.domainName}")
            println("Availability: ${suggestion.availability}")
            println(" ")
        }
    }
}

suspend fun listAllPrices(domainType: String?) {
    val pricesRequest = ListPricesRequest {
        tld = domainType
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listPricesPaginated(pricesRequest)
            .transform { it.prices?.forEach { obj -> emit(obj) } }
            .collect { pr ->
                println("Registration: ${pr.registrationPrice}
 ${pr.registrationPrice?.currency}")
                println("Renewal: ${pr.renewalPrice?.price}
 ${pr.renewalPrice?.currency}")
                println("Transfer: ${pr.transferPrice?.price}
 ${pr.transferPrice?.currency}")
                println("Restoration: ${pr.restorationPrice?.price}
 ${pr.restorationPrice?.currency}")
            }
    }
}

suspend fun listBillingRecords() {
```

```
    val currentDate = Date()
    val localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    val localDateTime2 = localDateTime.minusYears(1)
    val myStartTime = localDateTime2.toInstant(zoneOffset)
    val myEndTime = localDateTime.toInstant(zoneOffset)
    val timeStart: Instant? = myStartTime?.let { Instant(it) }
    val timeEnd: Instant? = myEndTime?.let { Instant(it) }

    val viewBillingRequest = ViewBillingRequest {
        start = timeStart
        end = timeEnd
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.viewBillingPaginated(viewBillingRequest)
            .transform { it.billingRecords?.forEach { obj -> emit(obj) } }
            .collect { billing ->
                println("Bill Date: ${billing.billDate}")
                println("Operation: ${billing.operation}")
                println("Price: ${billing.price}")
            }
    }
}

suspend fun listOperations() {
    val currentDate = Date()
    var localDateTime =
 currentDate.toInstant().atZone(ZoneId.systemDefault()).toLocalDateTime()
    val zoneOffset = ZoneOffset.of("+01:00")
    localDateTime = localDateTime.minusYears(1)
    val myTime: java.time.Instant? = localDateTime.toInstant(zoneOffset)
    val time2: Instant? = myTime?.let { Instant(it) }
    val operationsRequest = ListOperationsRequest {
        submittedSince = time2
    }

    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listOperationsPaginated(operationsRequest)
            .transform { it.operations?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("Operation Id: ${content.operationId}")
                println("Status: ${content.status}")
```

```
                println("Date: ${content.submittedDate}")
            }
    }
}

suspend fun listDomains() {
    Route53DomainsClient { region = "us-east-1" }.use { route53DomainsClient ->
        route53DomainsClient.listDomainsPaginated(ListDomainsRequest {})
            .transform { it.domains?.forEach { obj -> emit(obj) } }
            .collect { content ->
                println("The domain name is ${content.domainName}")
            }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CheckDomainAvailability
  - CheckDomainTransferability
  - GetDomainDetail
  - GetDomainSuggestions
  - GetOperationDetail
  - ListDomains
  - ListOperations
  - ListPrices
  - RegisterDomain
  - ViewBilling

Exemplos do Amazon S3 usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun copyBucketObject(
    fromBucket: String,
    objectKey: String,
    toBucket: String
) {
    var encodedUrl = ""
    try {
        encodedUrl = URLEncoder.encode("$fromBucket/$objectKey",
 StandardCharsets.UTF_8.toString())
    } catch (e: UnsupportedEncodingException) {
        println("URL could not be encoded: " + e.message)
    }

    val request = CopyObjectRequest {
        copySource = encodedUrl
        bucket = toBucket
```

```
        key = objectKey
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.copyObject(request)
    }
}
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWSSDK for Kotlin.

Crie um ponto de acesso multirregional

O exemplo de código a seguir mostra como criar um ponto de acesso multirregional Amazon S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure o cliente de controle S3 para enviar a solicitação para a região us-west-2.

```
        suspend fun createS3ControlClient(): S3ControlClient {
            // Configure your S3ControlClient to send requests to US West (Oregon).
            val s3Control = S3ControlClient.fromEnvironment {
                region = "us-west-2"
            }
            return s3Control
        }
```

Crie o ponto de acesso multirregional.

```
    suspend fun createMrap(s3Control: S3ControlClient, accountIdParam: String,
bucketName1: String, bucketName2: String, mrapName: String): String {
        println("Creating MRAP ...")
        val createMrapResponse: CreateMultiRegionAccessPointResponse =
s3Control.createMultiRegionAccessPoint {
            accountId = accountIdParam
```

```
            clientToken = UUID.randomUUID().toString()
            details {
                name = mrapName

                regions = listOf(
                    Region {
                        bucket = bucketName1
                    },
                    Region {
                        bucket = bucketName2
                    }
                )
            }
        }
        val requestToken: String? = createMrapResponse.requestTokenArn

        // Use the request token to check for the status of the
CreateMultiRegionAccessPoint operation.
        if (requestToken != null) {
            waitForSucceededStatus(s3Control, requestToken, accountIdParam)
            println("MRAP created")
        }

        val getMrapResponse = s3Control.getMultiRegionAccessPoint(
            input = GetMultiRegionAccessPointRequest {
                accountId = accountIdParam
                name = mrapName
            }
        )
        val mrapAlias = getMrapResponse.accessPoint?.alias
        return "arn:aws:s3::$accountIdParam:accesspoint/$mrapAlias"
    }
```

Aguarde até que o ponto de acesso multirregional fique disponível.

```
        suspend fun waitForSucceededStatus(s3Control: S3ControlClient, requestToken:
String, accountIdParam: String, timeBetweenChecks: Duration = 1.minutes) {
            var describeResponse: DescribeMultiRegionAccessPointOperationResponse
            describeResponse = s3Control.describeMultiRegionAccessPointOperation(
                input = DescribeMultiRegionAccessPointOperationRequest {
                    accountId = accountIdParam
                    requestTokenArn = requestToken
```

```
                }
            )

            var status: String? = describeResponse.asyncOperation?.requestStatus
            while (status != "SUCCEEDED") {
                delay(timeBetweenChecks)
                describeResponse =
 s3Control.describeMultiRegionAccessPointOperation(
                    input = DescribeMultiRegionAccessPointOperationRequest {
                        accountId = accountIdParam
                        requestTokenArn = requestToken
                    }
                )
                status = describeResponse.asyncOperation?.requestStatus
                println(status)
            }
        }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.
- Para obter detalhes da API, consulte a CreateMultiRegionAccessPointreferência da API AWSSDK for Kotlin.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
```

```
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWSSDK for Kotlin.

Excluir uma política de um bucket

O exemplo de código a seguir mostra como excluir uma política de um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteS3BucketPolicy(bucketName: String?) {
    val request = DeleteBucketPolicyRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucketPolicy(request)
        println("Done!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteBucketPolicyreferência da API AWSSDK for Kotlin.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteBucketObjects(bucketName: String, objectName: String) {
    val objectId = ObjectIdentifier {
        key = objectName
    }

    val delOb = Delete {
        objects = listOf(objectId)
    }

    val request = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteObjects(request)
        println("$objectName was deleted from $bucketName")
    }
}
```

- Para obter detalhes da API, consulte a DeleteObjectsreferência da API AWSSDK for Kotlin.

Obter um objeto de um ponto de acesso multirregional

O exemplo de código a seguir mostra como obter um objeto de um ponto de acesso multirregional.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure o cliente S3 para usar o algoritmo de assinatura assimétrica Sigv4 (SIGv4a).

```
        suspend fun createS3Client(): S3Client {
            // Configure your S3Client to use the Asymmetric Sigv4 (Sigv4a) signing
algorithm.
            val sigV4AScheme = SigV4AsymmetricAuthScheme(CrtAwsSigner)
            val s3 = S3Client.fromEnvironment {
                authSchemes = listOf(sigV4AScheme)
            }
            return s3
        }
```

Use o ARN do ponto de acesso multirregional em vez de um nome de bucket para recuperar o objeto.

```
    suspend fun getObjectFromMrap(s3: S3Client, mrapArn: String, keyName: String):
String? {
        val request = GetObjectRequest {
            bucket = mrapArn // Use the ARN instead of the bucket name for object
operations.
            key = keyName
        }

        var stringObj: String? = null
        s3.getObject(request) { resp ->
            stringObj = resp.body?.decodeToString()
            if (stringObj != null) {
                println("Successfully read $keyName from $mrapArn")
            }
        }
        return stringObj
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.
- Para obter detalhes da API, consulte a GetObjectreferência da API AWSSDK for Kotlin.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK for Kotlin

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getObjectBytes(bucketName: String, keyName: String, path: String) {
    val request = GetObjectRequest {
        key = keyName
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.getObject(request) { resp ->
            val myFile = File(path)
            resp.body?.writeToFile(myFile)
            println("Successfully read $keyName from $bucketName")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWSSDK for Kotlin.

Obter a ACL de um objeto

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um objeto do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getBucketACL(objectKey: String, bucketName: String) {
    val request = GetObjectAclRequest {
        bucket = bucketName
        key = objectKey
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.getObjectAcl(request)
        response.grants?.forEach { grant ->
            println("Grant permission is ${grant.permission}")
        }
    }
}
```

- Para obter detalhes da API, consulte a GetObjectAclreferência da API AWSSDK for Kotlin.

Obter a política de um bucket

O exemplo de código a seguir mostra como obter a política de um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getPolicy(bucketName: String): String? {
    println("Getting policy for bucket $bucketName")
```

```
    val request = GetBucketPolicyRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val policyRes = s3.getBucketPolicy(request)
        return policyRes.policy
    }
}
```

- Para obter detalhes da API, consulte a GetBucketPolicyreferência da API AWSSDK for Kotlin.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBucketObjects(bucketName: String) {
    val request = ListObjectsRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->

        val response = s3.listObjects(request)
        response.contents?.forEach { myObject ->
            println("The name of the key is ${myObject.key}")
            println("The object is ${myObject.size?.let { calKb(it) }} KBs")
            println("The owner is ${myObject.owner}")
        }
    }
}

private fun calKb(intValue: Long): Long {
```

```
    return intValue / 1024
}
```

- Para obter detalhes da API, consulte ListObjectsV2 no AWSSDK para referência da API Kotlin.

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setBucketAcl(bucketName: String, idVal: String) {
    val myGrant = Grantee {
        id = idVal
        type = Type.CanonicalUser
    }

    val ownerGrant = Grant {
        grantee = myGrant
        permission = Permission.FullControl
    }

    val grantList = mutableListOf<Grant>()
    grantList.add(ownerGrant)

    val ownerOb = Owner {
        id = idVal
    }

    val acl = AccessControlPolicy {
        owner = ownerOb
        grants = grantList
    }
```

```
    val request = PutBucketAclRequest {
        bucket = bucketName
        accessControlPolicy = acl
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.putBucketAcl(request)
        println("An ACL was successfully set on $bucketName")
    }
}
```

- Para obter detalhes da API, consulte a PutBucketAclreferência da API AWSSDK for Kotlin.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun putS3Object(bucketName: String, objectKey: String, objectPath: String) {
    val metadataVal = mutableMapOf<String, String>()
    metadataVal["myVal"] = "test"

    val request = PutObjectRequest {
        bucket = bucketName
        key = objectKey
        metadata = metadataVal
        body = File(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.putObject(request)
        println("Tag information is ${response.eTag}")
    }
}
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWSSDK for Kotlin.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma `GetObject` solicitação pré-assinada e usar a URL para baixar um objeto.

```
suspend fun getObjectPresigned(s3: S3Client, bucketName: String, keyName: String):
 String {
    // Create a GetObjectRequest.
    val unsignedRequest = GetObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the GetObject request.
    val presignedRequest = s3.presignGetObject(unsignedRequest, 24.hours)

    // Use the URL from the presigned HttpRequest in a subsequent HTTP GET request
 to retrieve the object.
    val objectContents = URL(presignedRequest.url.toString()).readText()

    return objectContents
}
```

Crie uma solicitação `GetObject` atribuída previamente com opções avançadas.

```
suspend fun getObjectPresignedMoreOptions(s3: S3Client, bucketName: String, keyName:
 String): HttpRequest {
    // Create a GetObjectRequest.
    val unsignedRequest = GetObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the GetObject request.
    val presignedRequest = s3.presignGetObject(unsignedRequest, signer =
 CrtAwsSigner) {
        signingDate = Instant.now() + 12.hours // Presigned request can be used 12
 hours from now.
        algorithm = AwsSigningAlgorithm.SIGV4_ASYMMETRIC
        signatureType = AwsSignatureType.HTTP_REQUEST_VIA_QUERY_PARAMS
        expiresAfter = 8.hours // Presigned request expires 8 hours later.
    }
    return presignedRequest
}
```

Criar uma `PutObject` solicitação pré-assinada e usá-la para carregar um objeto.

```
suspend fun putObjectPresigned(s3: S3Client, bucketName: String, keyName: String,
 content: String) {
    // Create a PutObjectRequest.
    val unsignedRequest = PutObjectRequest {
        bucket = bucketName
        key = keyName
    }

    // Presign the request.
    val presignedRequest = s3.presignPutObject(unsignedRequest, 24.hours)

    // Use the URL and any headers from the presigned HttpRequest in a subsequent
 HTTP PUT request to retrieve the object.
    // Create a PUT request using the OKHttpClient API.
    val putRequest = Request
        .Builder()
        .url(presignedRequest.url.toString())
        .apply {
            presignedRequest.headers.forEach { key, values ->
                header(key, values.joinToString(", "))
```

```
            }
        }
        .put(content.toRequestBody())
        .build()

    val response = OkHttpClient().newCall(putRequest).execute()
    assert(response.isSuccessful)
}
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Kotlin.

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <bucketName> <key> <objectPath> <savePath> <toBucket>

    Where:
        bucketName - The Amazon S3 bucket to create.
        key - The key to use.
```

```
        objectPath - The path where the file is located (for example, C:/AWS/
book2.pdf).
        savePath - The path where the file is saved after it's downloaded (for
 example, C:/AWS/book2.pdf).
        toBucket - An Amazon S3 bucket to where an object is copied to (for example,
 C:/AWS/book2.pdf).
        """

    if (args.size != 4) {
        println(usage)
        exitProcess(1)
    }

    val bucketName = args[0]
    val key = args[1]
    val objectPath = args[2]
    val savePath = args[3]
    val toBucket = args[4]

    // Create an Amazon S3 bucket.
    createBucket(bucketName)

    // Update a local file to the Amazon S3 bucket.
    putObject(bucketName, key, objectPath)

    // Download the object to another local file.
    getObjectFromMrap(bucketName, key, savePath)

    // List all objects located in the Amazon S3 bucket.
    listBucketObs(bucketName)

    // Copy the object to another Amazon S3 bucket
    copyBucketOb(bucketName, key, toBucket)

    // Delete the object from the Amazon S3 bucket.
    deleteBucketObs(bucketName, key)

    // Delete the Amazon S3 bucket.
    deleteBucket(bucketName)
    println("All Amazon S3 operations were successfully performed")
}

suspend fun createBucket(bucketName: String) {
    val request = CreateBucketRequest {
```

```
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}

suspend fun putObject(bucketName: String, objectKey: String, objectPath: String) {
    val metadataVal = mutableMapOf<String, String>()
    metadataVal["myVal"] = "test"

    val request = PutObjectRequest {
        bucket = bucketName
        key = objectKey
        metadata = metadataVal
        this.body = Paths.get(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        val response = s3.putObject(request)
        println("Tag information is ${response.eTag}")
    }
}

suspend fun getObjectFromMrap(bucketName: String, keyName: String, path: String) {
    val request = GetObjectRequest {
        key = keyName
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.getObject(request) { resp ->
            val myFile = File(path)
            resp.body?.writeToFile(myFile)
            println("Successfully read $keyName from $bucketName")
        }
    }
}

suspend fun listBucketObs(bucketName: String) {
    val request = ListObjectsRequest {
        bucket = bucketName
```

```
    }

    S3Client { region = "us-east-1" }.use { s3 ->

        val response = s3.listObjects(request)
        response.contents?.forEach { myObject ->
            println("The name of the key is ${myObject.key}")
            println("The owner is ${myObject.owner}")
        }
    }
}

suspend fun copyBucketOb(fromBucket: String, objectKey: String, toBucket: String) {
    var encodedUrl = ""
    try {
        encodedUrl = URLEncoder.encode("$fromBucket/$objectKey",
 StandardCharsets.UTF_8.toString())
    } catch (e: UnsupportedEncodingException) {
        println("URL could not be encoded: " + e.message)
    }

    val request = CopyObjectRequest {
        copySource = encodedUrl
        bucket = toBucket
        key = objectKey
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.copyObject(request)
    }
}

suspend fun deleteBucketObs(bucketName: String, objectName: String) {
    val objectId = ObjectIdentifier {
        key = objectName
    }

    val delOb = Delete {
        objects = listOf(objectId)
    }

    val request = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }
```

```
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteObjects(request)
        println("$objectName was deleted from $bucketName")
    }
}

suspend fun deleteBucket(bucketName: String?) {
    val request = DeleteBucketRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucket(request)
        println("The $bucketName was successfully deleted!")
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

SageMaker exemplos usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com. SageMaker

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá SageMaker

O exemplo de código a seguir mostra como começar a usar o SageMaker.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listBooks() {

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        val response =
 sageMakerClient.listNotebookInstances(ListNotebookInstancesRequest {})
        response.notebookInstances?.forEach { item ->
            println("The notebook name is: ${item.notebookInstanceName}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Criar um pipeline

O exemplo de código a seguir mostra como criar ou atualizar um pipeline em SageMaker.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Create a pipeline from the example pipeline JSON.
suspend fun setupPipeline(filePath: String?, roleArnVal: String?, functionArnVal:
 String?, pipelineNameVal: String?) {
    println("Setting up the pipeline.")
    val parser = JSONParser()

    // Read JSON and get pipeline definition.
    FileReader(filePath).use { reader ->
        val obj: Any = parser.parse(reader)
        val jsonObject: JSONObject = obj as JSONObject
        val stepsArray: JSONArray = jsonObject.get("Steps") as JSONArray
        for (stepObj in stepsArray) {
            val step: JSONObject = stepObj as JSONObject
            if (step.containsKey("FunctionArn")) {
                step.put("FunctionArn", functionArnVal)
            }
        }
        println(jsonObject)

        // Create the pipeline.
        val pipelineRequest = CreatePipelineRequest {
            pipelineDescription = "Kotlin SDK example pipeline"
            roleArn = roleArnVal
            pipelineName = pipelineNameVal
            pipelineDefinition = jsonObject.toString()
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            sageMakerClient.createPipeline(pipelineRequest)
```

```
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreatePipeline
  - UpdatePipeline

Excluir um pipeline

O exemplo de código a seguir mostra como excluir um pipeline em SageMaker.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Delete a SageMaker pipeline by name.
suspend fun deletePipeline(pipelineNameVal: String) {
    val pipelineRequest = DeletePipelineRequest {
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        sageMakerClient.deletePipeline(pipelineRequest)
        println("*** Successfully deleted $pipelineNameVal")
    }
}
```

- Para obter detalhes da API, consulte a DeletePipelinereferência da API AWSSDK for Kotlin.

Descrever uma execução de pipeline

O exemplo de código a seguir mostra como descrever a execução de um pipeline em SageMaker.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun waitForPipelineExecution(executionArn: String?) {
    var status: String
    var index = 0
    do {
        val pipelineExecutionRequest = DescribePipelineExecutionRequest {
            pipelineExecutionArn = executionArn
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            val response =
 sageMakerClient.describePipelineExecution(pipelineExecutionRequest)
            status = response.pipelineExecutionStatus.toString()
            println("$index. The status of the pipeline is $status")
            TimeUnit.SECONDS.sleep(4)
            index++
        }
    } while ("Executing" == status)
    println("Pipeline finished with status $status")
}
```

- Para obter detalhes da API, consulte a DescribePipelineExecutionreferência da API AWSSDK for Kotlin.

Executar pipeline

O exemplo de código a seguir mostra como iniciar a execução de um pipeline em SageMaker.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Start a pipeline run with job configurations.
suspend fun executePipeline(bucketName: String, queueUrl: String?, roleArn: String?,
 pipelineNameVal: String): String? {
    println("Starting pipeline execution.")
    val inputBucketLocation = "s3://$bucketName/samplefiles/latlongtest.csv"
    val output = "s3://$bucketName/outputfiles/"

    val gson = GsonBuilder()
        .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
        .setPrettyPrinting()
        .create()

    // Set up all parameters required to start the pipeline.
    val parameters: MutableList<Parameter> = java.util.ArrayList<Parameter>()

    val para1 = Parameter {
        name = "parameter_execution_role"
        value = roleArn
    }
    val para2 = Parameter {
        name = "parameter_queue_url"
        value = queueUrl
    }

    val inputJSON = """{
        "DataSourceConfig": {
        "S3Data": {
            "S3Uri": "s3://$bucketName/samplefiles/latlongtest.csv"
        },
        "Type": "S3_DATA"
        },
        "DocumentType": "CSV"
    }"""
    println(inputJSON)
```

```
    val para3 = Parameter {
        name = "parameter_vej_input_config"
        value = inputJSON
    }

    // Create an ExportVectorEnrichmentJobOutputConfig object.
    val jobS3Data = VectorEnrichmentJobS3Data {
        s3Uri = output
    }

    val outputConfig = ExportVectorEnrichmentJobOutputConfig {
        s3Data = jobS3Data
    }

    val gson4: String = gson.toJson(outputConfig)
    val para4: Parameter = Parameter {
        name = "parameter_vej_export_config"
        value = gson4
    }
    println("parameter_vej_export_config:" + gson.toJson(outputConfig))

    val para5JSON =
        "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":{\"XAttributeName\":
\"Longitude\",\"YAttributeName\":\"Latitude\"}}"

    val para5: Parameter = Parameter {
        name = "parameter_step_1_vej_config"
        value = para5JSON
    }

    parameters.add(para1)
    parameters.add(para2)
    parameters.add(para3)
    parameters.add(para4)
    parameters.add(para5)

    val pipelineExecutionRequest = StartPipelineExecutionRequest {
        pipelineExecutionDescription = "Created using Kotlin SDK"
        pipelineExecutionDisplayName = "$pipelineName-example-execution"
        pipelineParameters = parameters
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
```

```
        val response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest)
        return response.pipelineExecutionArn
    }
}
```

- Para obter detalhes da API, consulte a StartPipelineExecutionreferência da API AWSSDK for Kotlin.

Cenários

Iniciar com trabalhos geoespaciais e pipelines

O código de exemplo a seguir mostra como:

- Configurar recursos para um pipeline.
- Configurar um pipeline que execute um trabalho geoespacial.
- Inicie a execução de um pipeline.
- Monitorar o status da execução.
- Ver saída do pipeline.
- Limpe os recursos.

Para obter mais informações, consulte Criar e executar SageMaker pipelines usando AWS SDKs no Community.aws.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
val DASHES = String(CharArray(80)).replace("\u0000", "-")
private var eventSourceMapping = ""

suspend fun main(args: Array<String>) {
```

```
    val usage = """
    Usage:
          <sageMakerRoleName> <lambdaRoleName> <functionName> <functionKey>
 <queueName> <bucketName> <bucketFunction> <lnglatData> <spatialPipelinePath>
 <pipelineName>

    Where:
        sageMakerRoleName - The name of the Amazon SageMaker role.
        lambdaRoleName - The name of the AWS Lambda role.
        functionName - The name of the AWS Lambda function (for
 example,SageMakerExampleFunction).
        functionKey - The name of the Amazon S3 key name that represents the Lambda
 function (for example, SageMakerLambda.zip).
        queueName - The name of the Amazon Simple Queue Service (Amazon SQS) queue.
        bucketName - The name of the Amazon Simple Storage Service (Amazon S3)
 bucket.
        bucketFunction - The name of the Amazon S3 bucket that contains the Lambda
 ZIP file.
        lnglatData - The file location of the latlongtest.csv file required for this
 use case.
        spatialPipelinePath - The file location of the GeoSpatialPipeline.json file
 required for this use case.
        pipelineName - The name of the pipeline to create (for example, sagemaker-
sdk-example-pipeline).
    """

    if (args.size != 10) {
        println(usage)
        exitProcess(1)
    }

    val sageMakerRoleName = args[0]
    val lambdaRoleName = args[1]
    val functionKey = args[2]
    val functionName = args[3]
    val queueName = args[4]
    val bucketName = args[5]
    val bucketFunction = args[6]
    val lnglatData = args[7]
    val spatialPipelinePath = args[8]
    val pipelineName = args[9]
    val handlerName = "org.example.SageMakerLambdaFunction::handleRequest"

    println(DASHES)
```

```
    println("Welcome to the Amazon SageMaker pipeline example scenario.")
    println(
        """
         This example workflow will guide you through setting up and running an
         Amazon SageMaker pipeline. The pipeline uses an AWS Lambda function and an
         Amazon SQS Queue. It runs a vector enrichment reverse geocode job to
         reverse geocode addresses in an input file and store the results in an
export file.
        """.trimIndent()
    )
    println(DASHES)

    println(DASHES)
    println("First, we will set up the roles, functions, and queue needed by the
SageMaker pipeline.")
    val lambdaRoleArn: String = checkLambdaRole(lambdaRoleName)
    val sageMakerRoleArn: String = checkSageMakerRole(sageMakerRoleName)
    val functionArn = checkFunction(functionName, bucketFunction, functionKey,
handlerName, lambdaRoleArn)
    val queueUrl = checkQueue(queueName, functionName)
    println(DASHES)

    println(DASHES)
    println("Setting up bucket $bucketName")
    if (!checkBucket(bucketName)) {
        setupBucket(bucketName)
        println("Put $lnglatData into $bucketName")
        val objectKey = "samplefiles/latlongtest.csv"
        putS3Object(bucketName, objectKey, lnglatData)
    }
    println(DASHES)

    println(DASHES)
    println("Now we can create and run our pipeline.")
    setupPipeline(spatialPipelinePath, sageMakerRoleArn, functionArn, pipelineName)
    val pipelineExecutionARN = executePipeline(bucketName, queueUrl,
sageMakerRoleArn, pipelineName)
    println("The pipeline execution ARN value is $pipelineExecutionARN")
    waitForPipelineExecution(pipelineExecutionARN)
    println("Wait 30 secs to get output results $bucketName")
    TimeUnit.SECONDS.sleep(30)
    getOutputResults(bucketName)
    println(DASHES)
```

```
    println(DASHES)
    println(
        """
            The pipeline has completed. To view the pipeline and runs in SageMaker
 Studio, follow these instructions:
            https://docs.aws.amazon.com/sagemaker/latest/dg/pipelines-studio.html
        """.trimIndent()
    )
    println(DASHES)

    println(DASHES)
    println("Do you want to delete the AWS resources used in this Workflow? (y/n)")
    val `in` = Scanner(System.`in`)
    val delResources = `in`.nextLine()
    if (delResources.compareTo("y") == 0) {
        println("Lets clean up the AWS resources. Wait 30 seconds")
        TimeUnit.SECONDS.sleep(30)
        deleteEventSourceMapping(functionName)
        deleteSQSQueue(queueName)
        listBucketObjects(bucketName)
        deleteBucket(bucketName)
        delLambdaFunction(functionName)
        deleteLambdaRole(lambdaRoleName)
        deleteSagemakerRole(sageMakerRoleName)
        deletePipeline(pipelineName)
    } else {
        println("The AWS Resources were not deleted!")
    }
    println(DASHES)

    println(DASHES)
    println("SageMaker pipeline scenario is complete.")
    println(DASHES)
}

// Delete a SageMaker pipeline by name.
suspend fun deletePipeline(pipelineNameVal: String) {
    val pipelineRequest = DeletePipelineRequest {
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        sageMakerClient.deletePipeline(pipelineRequest)
        println("*** Successfully deleted $pipelineNameVal")
```

```
    }
}

suspend fun deleteSagemakerRole(roleNameVal: String) {
    val sageMakerRolePolicies = getSageMakerRolePolicies()
    IamClient { region = "us-west-2" }.use { iam ->
        for (policy in sageMakerRolePolicies) {
            // First the policy needs to be detached.
            val rolePolicyRequest = DetachRolePolicyRequest {
                policyArn = policy
                roleName = roleNameVal
            }
            iam.detachRolePolicy(rolePolicyRequest)
        }

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
            roleName = roleNameVal
        }
        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}

suspend fun deleteLambdaRole(roleNameVal: String) {
    val lambdaRolePolicies = getLambdaRolePolicies()
    IamClient { region = "us-west-2" }.use { iam ->
        for (policy in lambdaRolePolicies) {
            // First the policy needs to be detached.
            val rolePolicyRequest = DetachRolePolicyRequest {
                policyArn = policy
                roleName = roleNameVal
            }
            iam.detachRolePolicy(rolePolicyRequest)
        }

        // Delete the role.
        val roleRequest = DeleteRoleRequest {
            roleName = roleNameVal
        }
        iam.deleteRole(roleRequest)
        println("*** Successfully deleted $roleNameVal")
    }
}
```

```
suspend fun delLambdaFunction(myFunctionName: String) {
    val request = DeleteFunctionRequest {
        functionName = myFunctionName
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        awsLambda.deleteFunction(request)
        println("$myFunctionName was deleted")
    }
}

suspend fun deleteBucket(bucketName: String?) {
    val request = DeleteBucketRequest {
        bucket = bucketName
    }
    S3Client { region = "us-east-1" }.use { s3 ->
        s3.deleteBucket(request)
        println("The $bucketName was successfully deleted!")
    }
}

suspend fun deleteBucketObjects(bucketName: String, objectName: String?) {
    val toDelete = ArrayList<ObjectIdentifier>()
    val obId = ObjectIdentifier {
        key = objectName
    }
    toDelete.add(obId)
    val delOb = Delete {
        objects = toDelete
    }
    val dor = DeleteObjectsRequest {
        bucket = bucketName
        delete = delOb
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.deleteObjects(dor)
        println("*** $bucketName objects were deleted.")
    }
}

suspend fun listBucketObjects(bucketNameVal: String) {
    val listObjects = ListObjectsRequest {
```

```
        bucket = bucketNameVal
    }

    S3Client { region = "us-east-1" }.use { s3Client ->
        val res = s3Client.listObjects(listObjects)
        val objects = res.contents
        if (objects != null) {
            for (myValue in objects) {
                println("The name of the key is ${myValue.key}")
                deleteBucketObjects(bucketNameVal, myValue.key)
            }
        }
    }
}

// Delete the specific Amazon SQS queue.
suspend fun deleteSQSQueue(queueNameVal: String?) {
    val getQueueRequest = GetQueueUrlRequest {
        queueName = queueNameVal
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        val urlVal = sqsClient.getQueueUrl(getQueueRequest).queueUrl
        val deleteQueueRequest = DeleteQueueRequest {
            queueUrl = urlVal
        }
        sqsClient.deleteQueue(deleteQueueRequest)
    }
}

// Delete the queue event mapping.
suspend fun deleteEventSourceMapping(functionNameVal: String) {
    if (eventSourceMapping.compareTo("") == 0) {
        LambdaClient { region = "us-west-2" }.use { lambdaClient ->
            val request = ListEventSourceMappingsRequest {
                functionName = functionNameVal
            }
            val response = lambdaClient.listEventSourceMappings(request)
            val eventList = response.eventSourceMappings
            if (eventList != null) {
                for (event in eventList) {
                    eventSourceMapping = event.uuid.toString()
                }
            }
```

```
        }
    }

    val eventSourceMappingRequest = DeleteEventSourceMappingRequest {
        uuid = eventSourceMapping
    }
    LambdaClient { region = "us-west-2" }.use { lambdaClient ->
        lambdaClient.deleteEventSourceMapping(eventSourceMappingRequest)
        println("The event mapping is deleted!")
    }
}

// Reads the objects in the S3 bucket and displays the values.
private suspend fun readObject(bucketName: String, keyVal: String?) {
    println("Output file contents: \n")
    val objectRequest = GetObjectRequest {
        bucket = bucketName
        key = keyVal
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        s3Client.getObject(objectRequest) { resp ->
            val byteArray = resp.body?.toByteArray()
            val text = byteArray?.let { String(it, StandardCharsets.UTF_8) }
            println("Text output: $text")
        }
    }
}

// Display the results from the output directory.
suspend fun getOutputResults(bucketName: String?) {
    println("Getting output results $bucketName.")
    val listObjectsRequest = ListObjectsRequest {
        bucket = bucketName
        prefix = "outputfiles/"
    }
    S3Client { region = "us-east-1" }.use { s3Client ->
        val response = s3Client.listObjects(listObjectsRequest)
        val s3Objects: List<Object>? = response.contents
        if (s3Objects != null) {
            for (`object` in s3Objects) {
                if (bucketName != null) {
                    readObject(bucketName, (`object`.key))
                }
            }
```

```
        }
    }
}

suspend fun waitForPipelineExecution(executionArn: String?) {
    var status: String
    var index = 0
    do {
        val pipelineExecutionRequest = DescribePipelineExecutionRequest {
            pipelineExecutionArn = executionArn
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            val response =
 sageMakerClient.describePipelineExecution(pipelineExecutionRequest)
            status = response.pipelineExecutionStatus.toString()
            println("$index. The status of the pipeline is $status")
            TimeUnit.SECONDS.sleep(4)
            index++
        }
    } while ("Executing" == status)
    println("Pipeline finished with status $status")
}

// Start a pipeline run with job configurations.
suspend fun executePipeline(bucketName: String, queueUrl: String?, roleArn: String?,
 pipelineNameVal: String): String? {
    println("Starting pipeline execution.")
    val inputBucketLocation = "s3://$bucketName/samplefiles/latlongtest.csv"
    val output = "s3://$bucketName/outputfiles/"

    val gson = GsonBuilder()
        .setFieldNamingPolicy(FieldNamingPolicy.UPPER_CAMEL_CASE)
        .setPrettyPrinting()
        .create()

    // Set up all parameters required to start the pipeline.
    val parameters: MutableList<Parameter> = java.util.ArrayList<Parameter>()

    val para1 = Parameter {
        name = "parameter_execution_role"
        value = roleArn
    }
    val para2 = Parameter {
```

```
        name = "parameter_queue_url"
        value = queueUrl
    }

    val inputJSON = """{
        "DataSourceConfig": {
        "S3Data": {
            "S3Uri": "s3://$bucketName/samplefiles/latlongtest.csv"
        },
        "Type": "S3_DATA"
        },
        "DocumentType": "CSV"
    }"""
    println(inputJSON)
    val para3 = Parameter {
        name = "parameter_vej_input_config"
        value = inputJSON
    }

    // Create an ExportVectorEnrichmentJobOutputConfig object.
    val jobS3Data = VectorEnrichmentJobS3Data {
        s3Uri = output
    }

    val outputConfig = ExportVectorEnrichmentJobOutputConfig {
        s3Data = jobS3Data
    }

    val gson4: String = gson.toJson(outputConfig)
    val para4: Parameter = Parameter {
        name = "parameter_vej_export_config"
        value = gson4
    }
    println("parameter_vej_export_config:" + gson.toJson(outputConfig))

    val para5JSON =
        "{\"MapMatchingConfig\":null,\"ReverseGeocodingConfig\":{\"XAttributeName\":
\"Longitude\",\"YAttributeName\":\"Latitude\"}}"

    val para5: Parameter = Parameter {
        name = "parameter_step_1_vej_config"
        value = para5JSON
    }
```

```
    parameters.add(para1)
    parameters.add(para2)
    parameters.add(para3)
    parameters.add(para4)
    parameters.add(para5)

    val pipelineExecutionRequest = StartPipelineExecutionRequest {
        pipelineExecutionDescription = "Created using Kotlin SDK"
        pipelineExecutionDisplayName = "$pipelineName-example-execution"
        pipelineParameters = parameters
        pipelineName = pipelineNameVal
    }

    SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
        val response =
 sageMakerClient.startPipelineExecution(pipelineExecutionRequest)
        return response.pipelineExecutionArn
    }
}

// Create a pipeline from the example pipeline JSON.
suspend fun setupPipeline(filePath: String?, roleArnVal: String?, functionArnVal:
 String?, pipelineNameVal: String?) {
    println("Setting up the pipeline.")
    val parser = JSONParser()

    // Read JSON and get pipeline definition.
    FileReader(filePath).use { reader ->
        val obj: Any = parser.parse(reader)
        val jsonObject: JSONObject = obj as JSONObject
        val stepsArray: JSONArray = jsonObject.get("Steps") as JSONArray
        for (stepObj in stepsArray) {
            val step: JSONObject = stepObj as JSONObject
            if (step.containsKey("FunctionArn")) {
                step.put("FunctionArn", functionArnVal)
            }
        }
        println(jsonObject)

        // Create the pipeline.
        val pipelineRequest = CreatePipelineRequest {
            pipelineDescription = "Kotlin SDK example pipeline"
            roleArn = roleArnVal
            pipelineName = pipelineNameVal
```

```
            pipelineDefinition = jsonObject.toString()
        }

        SageMakerClient { region = "us-west-2" }.use { sageMakerClient ->
            sageMakerClient.createPipeline(pipelineRequest)
        }
    }
}

suspend fun putS3Object(bucketName: String, objectKey: String, objectPath: String) {
    val request = PutObjectRequest {
        bucket = bucketName
        key = objectKey
        body = File(objectPath).asByteStream()
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.putObject(request)
        println("Successfully placed $objectKey into bucket $bucketName")
    }
}

suspend fun setupBucket(bucketName: String) {
    val request = CreateBucketRequest {
        bucket = bucketName
    }

    S3Client { region = "us-east-1" }.use { s3 ->
        s3.createBucket(request)
        println("$bucketName is ready")
    }
}

suspend fun checkBucket(bucketName: String): Boolean {
    try {
        val headBucketRequest = HeadBucketRequest {
            bucket = bucketName
        }
        S3Client { region = "us-east-1" }.use { s3Client ->
            s3Client.headBucket(headBucketRequest)
            println("$bucketName exists")
            return true
        }
    } catch (e: S3Exception) {
```

```
        println("Bucket does not exist")
    }
    return false
}

// Connect the queue to the Lambda function as an event source.
suspend fun connectLambda(queueUrlVal: String?, lambdaNameVal: String?) {
    println("Connecting the Lambda function and queue for the pipeline.")
    var queueArn = ""

    // Specify the attributes to retrieve.
    val atts: MutableList<QueueAttributeName> = ArrayList()
    atts.add(QueueAttributeName.QueueArn)
    val attributesRequest = GetQueueAttributesRequest {
        queueUrl = queueUrlVal
        attributeNames = atts
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        val response = sqsClient.getQueueAttributes(attributesRequest)
        val queueAtts = response.attributes
        if (queueAtts != null) {
            for ((key, value) in queueAtts) {
                println("Key = $key, Value = $value")
                queueArn = value
            }
        }
    }
    val eventSourceMappingRequest = CreateEventSourceMappingRequest {
        eventSourceArn = queueArn
        functionName = lambdaNameVal
    }
    LambdaClient { region = "us-west-2" }.use { lambdaClient ->
        val response1 =
 lambdaClient.createEventSourceMapping(eventSourceMappingRequest)
        eventSourceMapping = response1.uuid.toString()
        println("The mapping between the event source and Lambda function was
 successful")
    }
}

// Set up the SQS queue to use with the pipeline.
suspend fun setupQueue(queueNameVal: String, lambdaNameVal: String): String {
    println("Setting up queue named $queueNameVal")
```

```
    val queueAtt: MutableMap<String, String> = HashMap()
    queueAtt.put("DelaySeconds", "5")
    queueAtt.put("ReceiveMessageWaitTimeSeconds", "5")
    queueAtt.put("VisibilityTimeout", "300")

    val createQueueRequest = CreateQueueRequest {
        queueName = queueNameVal
        attributes = queueAtt
    }

    SqsClient { region = "us-west-2" }.use { sqsClient ->
        sqsClient.createQueue(createQueueRequest)
        println("\nGet queue url")
        val getQueueUrlResponse = sqsClient.getQueueUrl(GetQueueUrlRequest
 { queueName = queueNameVal })
        TimeUnit.SECONDS.sleep(15)
        connectLambda(getQueueUrlResponse.queueUrl, lambdaNameVal)
        println("Queue ready with Url " + getQueueUrlResponse.queueUrl)
        return getQueueUrlResponse.queueUrl.toString()
    }
}

// Checks to see if the Amazon SQS queue exists. If not, this method creates a new
 queue
// and returns the ARN value.
suspend fun checkQueue(queueNameVal: String, lambdaNameVal: String): String? {
    println("Checking to see if the queue exists. If not, a new queue will be
 created for use in this workflow.")
    var queueUrl: String
    try {
        val request = GetQueueUrlRequest {
            queueName = queueNameVal
        }

        SqsClient { region = "us-west-2" }.use { sqsClient ->
            val response = sqsClient.getQueueUrl(request)
            queueUrl = response.queueUrl.toString()
            println(queueUrl)
        }
    } catch (e: SqsException) {
        println(e.message + " A new queue will be created")
        queueUrl = setupQueue(queueNameVal, lambdaNameVal)
    }
    return queueUrl
```

```
}

suspend fun createNewFunction(myFunctionName: String, s3BucketName: String, myS3Key:
 String, myHandler: String, myRole: String): String {
    val functionCode = FunctionCode {
        s3Bucket = s3BucketName
        s3Key = myS3Key
    }

    val request = CreateFunctionRequest {
        functionName = myFunctionName
        code = functionCode
        description = "Created by the Lambda Kotlin API"
        handler = myHandler
        role = myRole
        runtime = Runtime.Java11
        memorySize = 1024
        timeout = 200
    }

    LambdaClient { region = "us-west-2" }.use { awsLambda ->
        val functionResponse = awsLambda.createFunction(request)
        awsLambda.waitUntilFunctionActive {
            functionName = myFunctionName
        }
        println("${functionResponse.functionArn} was created")
        return functionResponse.functionArn.toString()
    }
}

suspend fun checkFunction(myFunctionName: String, s3BucketName: String, myS3Key:
 String, myHandler: String, myRole: String): String {
    println("Checking to see if the function exists. If not, a new AWS Lambda
 function will be created for use in this workflow.")
    var functionArn: String
    try {
        // Does this function already exist.
        val functionRequest = GetFunctionRequest {
            functionName = myFunctionName
        }
        LambdaClient { region = "us-west-2" }.use { lambdaClient ->
            val response = lambdaClient.getFunction(functionRequest)
            functionArn = response.configuration?.functionArn.toString()
            println("$functionArn exists")
```

```
        }
    } catch (e: LambdaException) {
        println(e.message + " A new function will be created")
        functionArn = createNewFunction(myFunctionName, s3BucketName, myS3Key,
 myHandler, myRole)
    }
    return functionArn
}

// Checks to see if the SageMaker role exists. If not, this method creates it.
suspend fun checkSageMakerRole(roleNameVal: String): String {
    println("Checking to see if the role exists. If not, a new role will be created
 for AWS SageMaker to use.")
    var roleArn: String
    try {
        val roleRequest = GetRoleRequest {
            roleName = roleNameVal
        }
        IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
            val response = iamClient.getRole(roleRequest)
            roleArn = response.role?.arn.toString()
            println(roleArn)
        }
    } catch (e: IamException) {
        println(e.message + " A new role will be created")
        roleArn = createSageMakerRole(roleNameVal)
    }
    return roleArn
}

suspend fun createSageMakerRole(roleNameVal: String): String {
    val sageMakerRolePolicies = getSageMakerRolePolicies()
    println("Creating a role to use with SageMaker.")
    val assumeRolePolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": [" +
        "\"sagemaker.amazonaws.com\"," +
        "\"sagemaker-geospatial.amazonaws.com\"," +
        "\"lambda.amazonaws.com\"," +
        "\"s3.amazonaws.com\"" +
        "]" +
```

```
        "}," +
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
        "}"

    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = assumeRolePolicy
        description = "Created using the AWS SDK for Kotlin"
    }
    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val roleResult = iamClient.createRole(request)

        // Attach the policies to the role.
        for (policy in sageMakerRolePolicies) {
            val attachRequest = AttachRolePolicyRequest {
                roleName = roleNameVal
                policyArn = policy
            }
            iamClient.attachRolePolicy(attachRequest)
        }

        // Allow time for the role to be ready.
        TimeUnit.SECONDS.sleep(15)
        System.out.println("Role ready with ARN ${roleResult.role?.arn}")
        return roleResult.role?.arn.toString()
    }
}

// Checks to see if the Lambda role exists. If not, this method creates it.
suspend fun checkLambdaRole(roleNameVal: String): String {
    println("Checking to see if the role exists. If not, a new role will be created
 for AWS Lambda to use.")
    var roleArn: String
    val roleRequest = GetRoleRequest {
        roleName = roleNameVal
    }

    try {
        IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
            val response = iamClient.getRole(roleRequest)
            roleArn = response.role?.arn.toString()
            println(roleArn)
        }
```

```
    } catch (e: IamException) {
        println(e.message + " A new role will be created")
        roleArn = createLambdaRole(roleNameVal)
    }

    return roleArn
}

private suspend fun createLambdaRole(roleNameVal: String): String {
    val lambdaRolePolicies = getLambdaRolePolicies()
    val assumeRolePolicy = "{" +
        "\"Version\": \"2012-10-17\"," +
        "\"Statement\": [{" +
        "\"Effect\": \"Allow\"," +
        "\"Principal\": {" +
        "\"Service\": [" +
        "\"sagemaker.amazonaws.com\"," +
        "\"sagemaker-geospatial.amazonaws.com\"," +
        "\"lambda.amazonaws.com\"," +
        "\"s3.amazonaws.com\"" +
        "]" +
        "}," +
        "\"Action\": \"sts:AssumeRole\"" +
        "}]" +
        "}"

    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = assumeRolePolicy
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val roleResult = iamClient.createRole(request)

        // Attach the policies to the role.
        for (policy in lambdaRolePolicies) {
            val attachRequest = AttachRolePolicyRequest {
                roleName = roleNameVal
                policyArn = policy
            }
            iamClient.attachRolePolicy(attachRequest)
        }
```

```
        // Allow time for the role to be ready.
        TimeUnit.SECONDS.sleep(15)
        println("Role ready with ARN " + roleResult.role?.arn)
        return roleResult.role?.arn.toString()
    }
}

fun getLambdaRolePolicies(): Array<String?> {
    val lambdaRolePolicies = arrayOfNulls<String>(5)
    lambdaRolePolicies[0] = "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess"
    lambdaRolePolicies[1] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess"
    lambdaRolePolicies[2] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess"
    lambdaRolePolicies[3] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerServiceCatalogProductsLambdaServiceRolePolicy"
    lambdaRolePolicies[4] = "arn:aws:iam::aws:policy/service-role/" +
 "AWSLambdaSQSQueueExecutionRole"
    return lambdaRolePolicies
}

fun getSageMakerRolePolicies(): Array<String?> {
    val sageMakerRolePolicies = arrayOfNulls<String>(3)
    sageMakerRolePolicies[0] = "arn:aws:iam::aws:policy/AmazonSageMakerFullAccess"
    sageMakerRolePolicies[1] = "arn:aws:iam::aws:policy/service-role/" +
 "AmazonSageMakerGeospatialFullAccess"
    sageMakerRolePolicies[2] = "arn:aws:iam::aws:policy/AmazonSQSFullAccess"
    return sageMakerRolePolicies
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreatePipeline
  - DeletePipeline
  - DescribePipelineExecution
  - StartPipelineExecution
  - UpdatePipeline

Exemplos de Secrets Manager usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um segredo

O exemplo de código a seguir mostra como criar um segredo do Secrets Manager.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createNewSecret(secretName: String?, secretValue: String?): String? {

    val request = CreateSecretRequest {
        name = secretName
        description = "This secret was created by the AWS Secrets Manager Kotlin
 API"
        secretString = secretValue
    }
```

```
    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.createSecret(request)
        return response.arn
    }
}
```

- Para obter detalhes da API, consulte a CreateSecretreferência da API AWSSDK for Kotlin.

Descrever um segredo

O exemplo de código a seguir mostra como descrever um segredo do Secrets Manager.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeGivenSecret(secretName: String?) {

    val secretRequest = DescribeSecretRequest {
        secretId = secretName
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.describeSecret(secretRequest)
        val secArn = response.description
        println("The secret description is $secArn")
    }
}
```

- Para obter detalhes da API, consulte a DescribeSecretreferência da API AWSSDK for Kotlin.

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getValue(secretName: String?) {

    val valueRequest = GetSecretValueRequest {
        secretId = secretName
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        val response = secretsClient.getSecretValue(valueRequest)
        val secret = response.secretString
        println("The secret value is $secret")
    }
}
```

- Para obter detalhes da API, consulte a GetSecretValuereferência da API AWSSDK for Kotlin.

listar segredos

O exemplo de código a seguir mostra como listar um segredo do Secrets Manager.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllSecrets() {

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
```

```
        val response = secretsClient.listSecrets(ListSecretsRequest {})
        response.secretList?.forEach { secret ->
            println("The secret name is ${secret.name}")
            println("The secret description is ${secret.description}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListSecretsreferência da API AWSSDK for Kotlin.

Modificar os detalhes de um segredo

O exemplo de código a seguir mostra como modificar o segredo.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun updateMySecret(secretName: String?, secretValue: String?) {

    val request = UpdateSecretRequest {
        secretId = secretName
        secretString = secretValue
    }

    SecretsManagerClient { region = "us-east-1" }.use { secretsClient ->
        secretsClient.updateSecret(request)
        println("The secret value was updated")
    }
}
```

- Para obter detalhes da API, consulte a UpdateSecretreferência da API AWSSDK for Kotlin.

Exemplos do Amazon SNS usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon SNS

Os exemplos de código a seguir mostram como começar a usar o Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sns.SnsClient
import aws.sdk.kotlin.services.sns.model.ListTopicsRequest
import aws.sdk.kotlin.services.sns.paginators.listTopicsPaginated
import kotlinx.coroutines.flow.transform

/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */
suspend fun main() {
```

```
    listTopicsPag()
}

suspend fun listTopicsPag() {
    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.listTopicsPaginated(ListTopicsRequest { })
            .transform { it.topics?.forEach { topic -> emit(topic) } }
            .collect { topic ->
                println("The topic ARN is ${topic.topicArn}")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWSSDK for Kotlin.

Tópicos

- Ações

Ações

Adicionar tags a um tópico

O exemplo de código a seguir mostra como adicionar tags a um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addTopicTags(topicArn: String) {

    val tag = Tag {
        key = "Team"
        value = "Development"
    }
```

```
    val tag2 = Tag {
        key = "Environment"
        value = "Gamma"
    }

    val tagList = mutableListOf<Tag>()
    tagList.add(tag)
    tagList.add(tag2)

    val request = TagResourceRequest {
        resourceArn = topicArn
        tags = tagList
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.tagResource(request)
        println("Tags have been added to $topicArn")
    }
}
```

- Para obter detalhes da API, consulte a TagResourcereferência da API AWSSDK for Kotlin.

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createSNSTopic(topicName: String): String {

    val request = CreateTopicRequest {
        name = topicName
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
```

```
        val result = snsClient.createTopic(request)
        return result.topicArn.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWSSDK for Kotlin.

Excluir uma assinatura

O exemplo de códigos a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun unSub(subscriptionArnVal: String) {

    val request = UnsubscribeRequest {
        subscriptionArn = subscriptionArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.unsubscribe(request)
        println("Subscription was removed for ${request.subscriptionArn}")
    }
}
```

- Para obter detalhes da API, consulte Unsubscribe (Cancelar assinatura) na Referência da API do AWS SDK para Kotlin.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteSNSTopic(topicArnVal: String) {

    val request = DeleteTopicRequest {
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.deleteTopic(request)
        println("$topicArnVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteTopicreferência da API AWSSDK for Kotlin.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getSNSTopicAttributes(topicArnVal: String) {

    val request = GetTopicAttributesRequest {
        topicArn = topicArnVal
    }
```

```
    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.getTopicAttributes(request)
        println("${result.attributes}")
    }
}
```

- Para obter detalhes da API, consulte a GetTopicAttributesreferência da API AWSSDK for Kotlin.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSNSSubscriptions() {

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.listSubscriptions(ListSubscriptionsRequest {})
        response.subscriptions?.forEach { sub ->
            println("Sub ARN is ${sub.subscriptionArn}")
            println("Sub protocol is ${sub.protocol}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListSubscriptionsreferência da API AWSSDK for Kotlin.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listSNSTopics() {

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val response = snsClient.listTopics(ListTopicsRequest { })
        response.topics?.forEach { topic ->
            println("The topic ARN is ${topic.topicArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWSSDK for Kotlin.

Publicar uma mensagem de texto SMS

O exemplo de código a seguir mostra como publicar mensagens SMS usando o Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun pubTextSMS(messageVal: String?, phoneNumberVal: String?) {

    val request = PublishRequest {
        message = messageVal
        phoneNumber = phoneNumberVal
    }
```

```
    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.publish(request)
        println("${result.messageId} message sent.")
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK para Kotlin.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun pubTopic(topicArnVal: String, messageVal: String) {

    val request = PublishRequest {
        message = messageVal
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.publish(request)
        println("${result.messageId} message sent.")
    }
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK para Kotlin.

Definir atributos de tópicos

Os exemplos de código a seguir mostram como definir atributos para um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun setTopAttr(attribute: String?, topicArnVal: String?, value: String?) {

    val request = SetTopicAttributesRequest {
        attributeName = attribute
        attributeValue = value
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        snsClient.setTopicAttributes(request)
        println("Topic ${request.topicArn} was updated.")
    }
}
```

- Para obter detalhes da API, consulte a SetTopicAttributesreferência da API AWSSDK for Kotlin.

Inscrever uma função do Lambda em um tópico

O exemplo de código a seguir mostra como inscrever uma função do Lambda para receber notificações de um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun subLambda(topicArnVal: String?, lambdaArn: String?) {
```

```
    val request = SubscribeRequest {
        protocol = "lambda"
        endpoint = lambdaArn
        returnSubscriptionArn = true
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.subscribe(request)
        println(" The subscription Arn is ${result.subscriptionArn}")
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Kotlin.

Inscrever um endereço de e-mail em um tópico

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun subEmail(topicArnVal: String, email: String): String {

    val request = SubscribeRequest {
        protocol = "email"
        endpoint = email
        returnSubscriptionArn = true
        topicArn = topicArnVal
    }

    SnsClient { region = "us-east-1" }.use { snsClient ->
        val result = snsClient.subscribe(request)
        return result.subscriptionArn.toString()
```

```
    }
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Kotlin.

Exemplos do Amazon SQS usando SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Kotlin com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon SQS

Os exemplos de código a seguir mostram como começar a usar o Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
package com.kotlin.sqs

import aws.sdk.kotlin.services.sqs.SqsClient
import aws.sdk.kotlin.services.sqs.paginators.listQueuesPaginated
```

```
import kotlinx.coroutines.flow.transform

suspend fun main() {
    listTopicsPag()
}

suspend fun listTopicsPag() {
    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.listQueuesPaginated { }
            .transform { it.queueUrls?.forEach { queue -> emit(queue) } }
            .collect { queue ->
                println("The Queue URL is $queue")
            }
    }
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações

Ações

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createQueue(queueNameVal: String): String {

    println("Create Queue")
    val createQueueRequest = CreateQueueRequest {
```

```
        queueName = queueNameVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.createQueue(createQueueRequest)
        println("Get queue url")

        val getQueueUrlRequest = GetQueueUrlRequest {
            queueName = queueNameVal
        }

        val getQueueUrlResponse = sqsClient.getQueueUrl(getQueueUrlRequest)
        return getQueueUrlResponse.queueUrl.toString()
    }
}
```

- Para obter detalhes da API, consulte a CreateQueuereferência da API AWSSDK for Kotlin.

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMessages(queueUrlVal: String) {
    println("Delete Messages from $queueUrlVal")

    val purgeRequest = PurgeQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.purgeQueue(purgeRequest)
        println("Messages are successfully deleted from $queueUrlVal")
```

```
    }
}

suspend fun deleteQueue(queueUrlVal: String) {

    val request = DeleteQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.deleteQueue(request)
        println("$queueUrlVal was deleted!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteMessagereferência da API AWSSDK for Kotlin.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMessages(queueUrlVal: String) {
    println("Delete Messages from $queueUrlVal")

    val purgeRequest = PurgeQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.purgeQueue(purgeRequest)
        println("Messages are successfully deleted from $queueUrlVal")
    }
}
```

```
suspend fun deleteQueue(queueUrlVal: String) {

    val request = DeleteQueueRequest {
        queueUrl = queueUrlVal
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.deleteQueue(request)
        println("$queueUrlVal was deleted!")
    }
}
```

- Para obter detalhes da API, consulte a DeleteQueuereferência da API AWSSDK for Kotlin.

Listar filas

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listQueues() {
    println("\nList Queues")

    val prefix = "que"
    val listQueuesRequest = ListQueuesRequest {
        queueNamePrefix = prefix
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        val response = sqsClient.listQueues(listQueuesRequest)
        response.queueUrls?.forEach { url ->
            println(url)
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWSSDK for Kotlin.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun receiveMessages(queueUrlVal: String?) {

    println("Retrieving messages from $queueUrlVal")

    val receiveMessageRequest = ReceiveMessageRequest {
        queueUrl = queueUrlVal
        maxNumberOfMessages = 5
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        val response = sqsClient.receiveMessage(receiveMessageRequest)
        response.messages?.forEach { message ->
            println(message.body)
        }
    }
}
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWSSDK for Kotlin.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun sendMessages(queueUrlVal: String, message: String) {
    println("Sending multiple messages")
    println("\nSend message")
    val sendRequest = SendMessageRequest {
        queueUrl = queueUrlVal
        messageBody = message
        delaySeconds = 10
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
        sqsClient.sendMessage(sendRequest)
        println("A single message was successfully sent.")
    }
}

suspend fun sendBatchMessages(queueUrlVal: String?) {
    println("Sending multiple messages")

    val msg1 = SendMessageBatchRequestEntry {
        id = "id1"
        messageBody = "Hello from msg 1"
    }

    val msg2 = SendMessageBatchRequestEntry {
        id = "id2"
        messageBody = "Hello from msg 2"
    }

    val sendMessageBatchRequest = SendMessageBatchRequest {
        queueUrl = queueUrlVal
        entries = listOf(msg1, msg2)
    }

    SqsClient { region = "us-east-1" }.use { sqsClient ->
```

```
        sqsClient.sendMessageBatch(sendMessageBatchRequest)
        println("Batch message were successfully sent.")
    }
}
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWSSDK for Kotlin.

Exemplos do Step Functions usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com Step Functions.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Step Functions

O exemplo de código a seguir mostra como começar a usar o Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest
```

```
/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

suspend fun main() {
    println(DASHES)
    println("Welcome to the AWS Step Functions Hello example.")
    println("Lets list up to ten of your state machines:")
    println(DASHES)

    listMachines()
}

suspend fun listMachines() {
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listStateMachines(ListStateMachinesRequest {})
        response.stateMachines?.forEach { machine ->
            println("The name of the state machine is ${machine.name}")
            println("The ARN value is ${machine.stateMachineArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListStateMachinesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Criar uma máquina de estado

O exemplo de código a seguir mostra como criar uma máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public static String createMachine(SfnClient sfnClient, String roleARN, String
stateMachineName, String json) {
       try {
           CreateStateMachineRequest machineRequest =
CreateStateMachineRequest.builder()
                   .definition(json)
                   .name(stateMachineName)
                   .roleArn(roleARN)
                   .type(StateMachineType.STANDARD)
                   .build();

           CreateStateMachineResponse response =
sfnClient.createStateMachine(machineRequest);
           return response.stateMachineArn();

       } catch (SfnException e) {
           System.err.println(e.awsErrorDetails().errorMessage());
           System.exit(1);
       }
       return "";
   }
```

- Para obter detalhes da API, consulte a CreateStateMachinereferência da API AWSSDK for Kotlin.

Criar uma atividade

O exemplo de código a seguir mostra como criar uma atividade do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createActivity(activityName: String): String? {
    val activityRequest = CreateActivityRequest {
        name = activityName
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createActivity(activityRequest)
        return response.activityArn
    }
}
```

- Para obter detalhes da API, consulte a CreateActivityreferência da API AWSSDK for Kotlin.

Excluir uma máquina de estado

O exemplo de código a seguir mostra como excluir uma máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteMachine(stateMachineArnVal: String?) {
    val deleteStateMachineRequest = DeleteStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }
```

```
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteStateMachine(deleteStateMachineRequest)
        println("$stateMachineArnVal was successfully deleted.")
    }
}
```

- Para obter detalhes da API, consulte a DeleteStateMachinereferência da API AWSSDK for Kotlin.

Excluir uma atividade.

Os exemplos de código a seguir mostram como excluir uma atividade do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun deleteActivity(actArn: String?) {
    val activityRequest = DeleteActivityRequest {
        activityArn = actArn
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteActivity(activityRequest)
        println("You have deleted $actArn")
    }
}
```

- Para obter detalhes da API, consulte a DeleteActivityreferência da API AWSSDK for Kotlin.

Descrever uma máquina de estado

O exemplo de código a seguir mostra como descrever uma máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeStateMachine(stateMachineArnVal: String?) {
    val stateMachineRequest = DescribeStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.describeStateMachine(stateMachineRequest)
        println("The name of the State machine is ${response.name}")
        println("The status of the State machine is ${response.status}")
        println("The ARN value of the State machine is ${response.stateMachineArn}")
        println("The role ARN value is ${response.roleArn}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeStateMachinereferência da API AWSSDK for Kotlin.

Descrever a execução de uma máquina de estado

O exemplo de código a seguir mostra como descrever uma execução de máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeExe(executionArnVal: String?) {
```

```
    val executionRequest = DescribeExecutionRequest {
        executionArn = executionArnVal
    }

    var status = ""
    var hasSucceeded = false
    while (!hasSucceeded) {
        SfnClient { region = "us-east-1" }.use { sfnClient ->
            val response = sfnClient.describeExecution(executionRequest)
            status = response.status.toString()
            if (status.compareTo("RUNNING") == 0) {
                println("The state machine is still running, let's wait for it to
 finish.")
                Thread.sleep(2000)
            } else if (status.compareTo("SUCCEEDED") == 0) {
                println("The Step Function workflow has succeeded")
                hasSucceeded = true
            } else {
                println("The Status is neither running or succeeded")
            }
        }
    }
    println("The Status is $status")
}
```

- Para obter detalhes da API, consulte a DescribeExecutionreferência da API AWSSDK for Kotlin.

Obter dados de tarefas para uma atividade

O exemplo de código a seguir mostra como obter dados de tarefa para uma atividade de Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getActivityTask(actArn: String?): List<String> {
    val myList: MutableList<String> = ArrayList()
    val getActivityTaskRequest = GetActivityTaskRequest {
        activityArn = actArn
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getActivityTask(getActivityTaskRequest)
        myList.add(response.taskToken.toString())
        myList.add(response.input.toString())
        return myList
    }
}
```

- Para obter detalhes da API, consulte a GetActivityTaskreferência da API AWSSDK for Kotlin.

Listar atividades

O exemplo de código a seguir mostra como listar atividades do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listAllActivites() {

    val activitiesRequest = ListActivitiesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listActivities(activitiesRequest)
        response.activities?.forEach { item ->
            println("The activity ARN is ${item.activityArn}")
            println("The activity name is ${item.name}")
        }
    }
```

```
}
```

- Para obter detalhes da API, consulte a ListActivitiesreferência da API AWSSDK for Kotlin.

Listar execuções de máquinas de estado

O exemplo de código a seguir mostra como listar execuções de máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getExeHistory(exeARN: String?) {

    val historyRequest = GetExecutionHistoryRequest {
        executionArn = exeARN
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getExecutionHistory(historyRequest)
        response.events?.forEach { event ->
            println("The event type is ${event.type}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListExecutionsreferência da API AWSSDK for Kotlin.

Listar máquinas de estado

O exemplo de código a seguir mostra como listar estado de máquinas do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest

/**
 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
 */

suspend fun main() {
    println(DASHES)
    println("Welcome to the AWS Step Functions Hello example.")
    println("Lets list up to ten of your state machines:")
    println(DASHES)

    listMachines()
}

suspend fun listMachines() {
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.listStateMachines(ListStateMachinesRequest {})
        response.stateMachines?.forEach { machine ->
            println("The name of the state machine is ${machine.name}")
            println("The ARN value is ${machine.stateMachineArn}")
        }
    }
}
```

- Para obter detalhes da API, consulte a ListStateMachinesreferência da API AWSSDK for Kotlin.

Enviar uma resposta bem-sucedida para uma tarefa

O exemplo de código a seguir mostra como enviar uma resposta de sucesso para uma tarefa de Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun sendTaskSuccess(token: String?, json: String?) {
    val successRequest = SendTaskSuccessRequest {
        taskToken = token
        output = json
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.sendTaskSuccess(successRequest)
    }
}
```

- Para obter detalhes da API, consulte a SendTaskSuccessreferência da API AWSSDK for Kotlin.

Iniciar execução de máquina de estado

O exemplo de código a seguir mostra como iniciar uma execução de máquina de estado do Step Functions.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun startWorkflow(stateMachineArnVal: String?, jsonEx: String?): String? {
```

```
    val uuid = UUID.randomUUID()
    val uuidValue = uuid.toString()
    val executionRequest = StartExecutionRequest {
        input = jsonEx
        stateMachineArn = stateMachineArnVal
        name = uuidValue
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.startExecution(executionRequest)
        return response.executionArn
    }
}
```

- Para obter detalhes da API, consulte a StartExecutionreferência da API AWSSDK for Kotlin.

Cenários

Começar a usar máquinas de estado

O código de exemplo a seguir mostra como:

- Criar uma atividade.
- Criar uma máquina de estado a partir de uma definição da Amazon States Language que contenha a atividade criada anteriormente como uma etapa.
- Executar a máquina de estado e responder à atividade com entrada do usuário.
- Obter o status e a saída finais após a conclusão da execução e, em seguida, limpar os recursos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import aws.sdk.kotlin.services.iam.IamClient
import aws.sdk.kotlin.services.iam.model.CreateRoleRequest
import aws.sdk.kotlin.services.sfn.SfnClient
import aws.sdk.kotlin.services.sfn.model.CreateActivityRequest
```

```
import aws.sdk.kotlin.services.sfn.model.CreateStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.DeleteActivityRequest
import aws.sdk.kotlin.services.sfn.model.DeleteStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.DescribeExecutionRequest
import aws.sdk.kotlin.services.sfn.model.DescribeStateMachineRequest
import aws.sdk.kotlin.services.sfn.model.GetActivityTaskRequest
import aws.sdk.kotlin.services.sfn.model.ListActivitiesRequest
import aws.sdk.kotlin.services.sfn.model.ListStateMachinesRequest
import aws.sdk.kotlin.services.sfn.model.SendTaskSuccessRequest
import aws.sdk.kotlin.services.sfn.model.StartExecutionRequest
import aws.sdk.kotlin.services.sfn.model.StateMachineType
import aws.sdk.kotlin.services.sfn.paginators.listActivitiesPaginated
import aws.sdk.kotlin.services.sfn.paginators.listStateMachinesPaginated
import com.fasterxml.jackson.databind.JsonNode
import com.fasterxml.jackson.databind.ObjectMapper
import com.fasterxml.jackson.databind.node.ObjectNode
import kotlinx.coroutines.flow.transform
import java.util.Scanner
import java.util.UUID
import kotlin.collections.ArrayList
import kotlin.system.exitProcess

/**
 To run this code example, place the chat_sfn_state_machine.json file into your
 project's resources folder.

 You can obtain the JSON file to create a state machine in the following GitHub
 location:

 https://github.com/awsdocs/aws-doc-sdk-examples/tree/main/resources/sample_files

 Before running this Kotlin code example, set up your development environment,
 including your credentials.

 For more information, see the following documentation topic:
 https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

 This Kotlin code example performs the following tasks:

 1. List activities using a paginator.
 2. List state machines using a paginator.
 3. Creates an activity.
 4. Creates a state machine.
 5. Describes the state machine.
```

```
 6. Starts execution of the state machine and interacts with it.
 7. Describes the execution.
 8. Deletes the activity.
 9. Deletes the state machine.
 */

val DASHES: String = String(CharArray(80)).replace("\u0000", "-")
suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <roleARN> <activityName> <stateMachineName>

    Where:
        roleName - The name of the IAM role to create for this state machine.
        activityName - The name of an activity to create.
        stateMachineName - The name of the state machine to create.
    """

    if (args.size != 3) {
        println(usage)
        exitProcess(0)
    }

    val roleName = args[0]
    val activityName = args[1]
    val stateMachineName = args[2]
    val sc = Scanner(System.`in`)
    var action = false

    val polJSON = """{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "",
            "Effect": "Allow",
            "Principal": {
                "Service": "states.amazonaws.com"
            },
            "Action": "sts:AssumeRole"
        }
    ]
    }"""

    println(DASHES)
```

```
    println("Welcome to the AWS Step Functions example scenario.")
    println(DASHES)

    println(DASHES)
    println("1. List activities using a Paginator.")
    listActivitesPagnator()
    println(DASHES)

    println(DASHES)
    println("2. List state machines using a paginator.")
    listStatemachinesPagnator()
    println(DASHES)

    println(DASHES)
    println("3. Create a new activity.")
    val activityArn = createActivity(activityName)
    println("The ARN of the Activity is $activityArn")
    println(DASHES)

    // Get JSON to use for the state machine and place the activityArn value into
it.
    val stream = GetStream()
    val jsonString = stream.getStream()

    // Modify the Resource node.
    val objectMapper = ObjectMapper()
    val root: JsonNode = objectMapper.readTree(jsonString)
    (root.path("States").path("GetInput") as ObjectNode).put("Resource",
activityArn)

    // Convert the modified Java object back to a JSON string.
    val stateDefinition = objectMapper.writeValueAsString(root)
    println(stateDefinition)

    println(DASHES)
    println("4. Create a state machine.")
    val roleARN = createIAMRole(roleName, polJSON)
    val stateMachineArn = createMachine(roleARN, stateMachineName, stateDefinition)
    println("The ARN of the state machine is $stateMachineArn")
    println(DASHES)

    println(DASHES)
    println("5. Describe the state machine.")
    describeStateMachine(stateMachineArn)
```

```
    println("What should ChatSFN call you?")
    val userName = sc.nextLine()
    println("Hello $userName")
    println(DASHES)

    println(DASHES)
    // The JSON to pass to the StartExecution call.
    val executionJson = "{ \"name\" : \"$userName\" }"
    println(executionJson)
    println("6. Start execution of the state machine and interact with it.")
    val runArn = startWorkflow(stateMachineArn, executionJson)
    println("The ARN of the state machine execution is $runArn")
    var myList: List<String>
    while (!action) {
        myList = getActivityTask(activityArn)
        println("ChatSFN: " + myList[1])
        println("$userName please specify a value.")
        val myAction = sc.nextLine()
        if (myAction.compareTo("done") == 0) {
            action = true
        }
        println("You have selected $myAction")
        val taskJson = "{ \"action\" : \"$myAction\" }"
        println(taskJson)
        sendTaskSuccess(myList[0], taskJson)
    }
    println(DASHES)

    println(DASHES)
    println("7. Describe the execution.")
    describeExe(runArn)
    println(DASHES)

    println(DASHES)
    println("8. Delete the activity.")
    deleteActivity(activityArn)
    println(DASHES)

    println(DASHES)
    println("9. Delete the state machines.")
    deleteMachine(stateMachineArn)
    println(DASHES)

    println(DASHES)
```

```
    println("The AWS Step Functions example scenario is complete.")
    println(DASHES)
}

suspend fun listStatemachinesPagnator() {
    val machineRequest = ListStateMachinesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.listStateMachinesPaginated(machineRequest)
            .transform { it.stateMachines?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(" The state machine ARN is ${obj.stateMachineArn}")
            }
    }
}

suspend fun listActivitesPagnator() {
    val activitiesRequest = ListActivitiesRequest {
        maxResults = 10
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.listActivitiesPaginated(activitiesRequest)
            .transform { it.activities?.forEach { obj -> emit(obj) } }
            .collect { obj ->
                println(" The activity ARN is ${obj.activityArn}")
            }
    }
}

suspend fun deleteMachine(stateMachineArnVal: String?) {
    val deleteStateMachineRequest = DeleteStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteStateMachine(deleteStateMachineRequest)
        println("$stateMachineArnVal was successfully deleted.")
    }
}

suspend fun deleteActivity(actArn: String?) {
```

```
    val activityRequest = DeleteActivityRequest {
        activityArn = actArn
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.deleteActivity(activityRequest)
        println("You have deleted $actArn")
    }
}

suspend fun describeExe(executionArnVal: String?) {
    val executionRequest = DescribeExecutionRequest {
        executionArn = executionArnVal
    }

    var status = ""
    var hasSucceeded = false
    while (!hasSucceeded) {
        SfnClient { region = "us-east-1" }.use { sfnClient ->
            val response = sfnClient.describeExecution(executionRequest)
            status = response.status.toString()
            if (status.compareTo("RUNNING") == 0) {
                println("The state machine is still running, let's wait for it to
 finish.")
                Thread.sleep(2000)
            } else if (status.compareTo("SUCCEEDED") == 0) {
                println("The Step Function workflow has succeeded")
                hasSucceeded = true
            } else {
                println("The Status is neither running or succeeded")
            }
        }
    }
    println("The Status is $status")
}

suspend fun sendTaskSuccess(token: String?, json: String?) {
    val successRequest = SendTaskSuccessRequest {
        taskToken = token
        output = json
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        sfnClient.sendTaskSuccess(successRequest)
    }
```

```
}

suspend fun getActivityTask(actArn: String?): List<String> {
    val myList: MutableList<String> = ArrayList()
    val getActivityTaskRequest = GetActivityTaskRequest {
        activityArn = actArn
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.getActivityTask(getActivityTaskRequest)
        myList.add(response.taskToken.toString())
        myList.add(response.input.toString())
        return myList
    }
}

suspend fun startWorkflow(stateMachineArnVal: String?, jsonEx: String?): String? {
    val uuid = UUID.randomUUID()
    val uuidValue = uuid.toString()
    val executionRequest = StartExecutionRequest {
        input = jsonEx
        stateMachineArn = stateMachineArnVal
        name = uuidValue
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.startExecution(executionRequest)
        return response.executionArn
    }
}

suspend fun describeStateMachine(stateMachineArnVal: String?) {
    val stateMachineRequest = DescribeStateMachineRequest {
        stateMachineArn = stateMachineArnVal
    }
    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.describeStateMachine(stateMachineRequest)
        println("The name of the State machine is ${response.name}")
        println("The status of the State machine is ${response.status}")
        println("The ARN value of the State machine is ${response.stateMachineArn}")
        println("The role ARN value is ${response.roleArn}")
    }
}

suspend fun createMachine(roleARNVal: String?, stateMachineName: String?, jsonVal:
 String?): String? {
```

```
    val machineRequest = CreateStateMachineRequest {
        definition = jsonVal
        name = stateMachineName
        roleArn = roleARNVal
        type = StateMachineType.Standard
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createStateMachine(machineRequest)
        return response.stateMachineArn
    }
}

suspend fun createIAMRole(roleNameVal: String?, polJSON: String?): String? {
    val request = CreateRoleRequest {
        roleName = roleNameVal
        assumeRolePolicyDocument = polJSON
        description = "Created using the AWS SDK for Kotlin"
    }

    IamClient { region = "AWS_GLOBAL" }.use { iamClient ->
        val response = iamClient.createRole(request)
        return response.role?.arn
    }
}

suspend fun createActivity(activityName: String): String? {
    val activityRequest = CreateActivityRequest {
        name = activityName
    }

    SfnClient { region = "us-east-1" }.use { sfnClient ->
        val response = sfnClient.createActivity(activityRequest)
        return response.activityArn
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - CreateActivity
  - CreateStateMachine

- DeleteActivity
- DeleteStateMachine
- DescribeExecution
- DescribeStateMachine
- GetActivityTask
- ListActivities
- ListStateMachines
- SendTaskSuccess
- StartExecution
- StopExecution

Exemplos de AWS Support usando o SDK para Kotlin

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Kotlin com AWS Support.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:
https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html

In addition, you must have the AWS Business Support Plan to use the AWS Support Java
 API. For more information, see:

https://aws.amazon.com/premiumsupport/plans/

This Kotlin example performs the following task:

1. Gets and displays available services.
 */

suspend fun main() {
    displaySomeServices()
}

// Return a List that contains a Service name and Category name.
suspend fun displaySomeServices() {
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
```

```
                return@forEach
            }

            println("The Service name is: " + service.name)

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                index++
            }
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeServicesreferência da API AWSSDK for Kotlin.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma comunicação a um caso

O exemplo de código a seguir mostra como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAttachSupportCase(caseIdVal: String?, attachmentSetIdVal: String?) {
    val caseRequest = AddCommunicationToCaseRequest {
```

```
        caseId = caseIdVal
        attachmentSetId = attachmentSetIdVal
        communicationBody = "Please refer to attachment for details."
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addCommunicationToCase(caseRequest)
        if (response.result) {
            println("You have successfully added a communication to an AWS Support
 case")
        } else {
            println("There was an error adding the communication to an AWS Support
 case")
        }
    }
}
```

- Para obter detalhes da API, consulte a AddCommunicationToCasereferência da API AWSSDK for Kotlin.

Adicionar um anexo a um conjunto

O exemplo de código a seguir mostra como adicionar um anexo do AWS Support a um conjunto de anexos.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun addAttachment(fileAttachment: String): String? {
    val myFile = File(fileAttachment)
    val sourceBytes = (File(fileAttachment).readBytes())
    val attachmentVal = Attachment {
        fileName = myFile.name
        data = sourceBytes
    }
```

```
    val setRequest = AddAttachmentsToSetRequest {
        attachments = listOf(attachmentVal)
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addAttachmentsToSet(setRequest)
        return response.attachmentSetId
    }
}
```

- Para obter detalhes da API, consulte a AddAttachmentsToSetreferência da API AWSSDK for Kotlin.

Criar um caso

O exemplo de código a seguir mostra como criar um novo caso do AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun createSupportCase(sevCatListVal: List<String>, sevLevelVal: String):
 String? {
    val serCode = sevCatListVal[0]
    val caseCategory = sevCatListVal[1]
    val caseRequest = CreateCaseRequest {
        categoryCode = caseCategory.lowercase(Locale.getDefault())
        serviceCode = serCode.lowercase(Locale.getDefault())
        severityCode = sevLevelVal.lowercase(Locale.getDefault())
        communicationBody = "Test issue with
 ${serCode.lowercase(Locale.getDefault())}"
        subject = "Test case, please ignore"
        language = "en"
        issueType = "technical"
    }
```

```
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.createCase(caseRequest)
        return response.caseId
    }
}
```

- Para obter detalhes da API, consulte a CreateCasereferência da API AWSSDK for Kotlin.

Descrever um anexo

O exemplo de código a seguir mostra como descrever um anexo para um caso do AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun describeAttachment(attachId: String?) {
    val attachmentRequest = DescribeAttachmentRequest {
        attachmentId = attachId
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeAttachment(attachmentRequest)
        println("The name of the file is ${response.attachment?.fileName}")
    }
}
```

- Para obter detalhes da API, consulte a DescribeAttachmentreferência da API AWSSDK for Kotlin.

Descrever casos

O exemplo de código a seguir mostra como descrever casos do AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun getOpenCase() {
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 20
        afterTime = yesterday.toString()
        beforeTime = now.toString()
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}
```

- Para obter detalhes da API, consulte a DescribeCasesreferência da API AWSSDK for Kotlin.

Descrever as comunicações

O exemplo de código a seguir mostra como descrever as comunicações do AWS Support para um caso.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun listCommunications(caseIdVal: String?): String? {
    val communicationsRequest = DescribeCommunicationsRequest {
        caseId = caseIdVal
        maxResults = 10
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCommunications(communicationsRequest)
        response.communications?.forEach { comm ->
            println("the body is: " + comm.body)
            comm.attachmentSet?.forEach { detail ->
                return detail.attachmentId
            }
        }
    }
    return ""
}
```

- Para obter detalhes da API, consulte a DescribeCommunicationsreferência da API AWSSDK for Kotlin.

Descrever os serviços

O exemplo de código a seguir mostra como descrever a lista de serviços do AWS.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Return a List that contains a Service name and Category name.
suspend fun displayServices(): List<String> {
    var serviceCode = ""
    var catName = ""
    val sevCatList = mutableListOf<String>()
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
                return@forEach
            }

            println("The Service name is ${service.name}")
            if (service.name == "Account") {
                serviceCode = service.code.toString()
            }

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                if (cat.name == "Security") {
                    catName = cat.name!!
                }
            }
            index++
        }
    }

    // Push the two values to the list.
    serviceCode.let { sevCatList.add(it) }
    catName.let { sevCatList.add(it) }
    return sevCatList
}
```

- Para obter detalhes da API, consulte a DescribeServicesreferência da API AWSSDK for Kotlin.

Descrever os níveis de gravidade

O exemplo de código a seguir mostra como descrever os níveis de gravidade do AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun displaySevLevels(): String {
    var levelName = ""
    val severityLevelsRequest = DescribeSeverityLevelsRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeSeverityLevels(severityLevelsRequest)
        response.severityLevels?.forEach { sevLevel ->
            println("The severity level name is: ${sevLevel.name}")
            if (sevLevel.name == "High") {
                levelName = sevLevel.name!!
            }
        }
        return levelName
    }
}
```

- Para obter detalhes da API, consulte a DescribeSeverityLevelsreferência da API AWSSDK for Kotlin.

Resolver caso

O exemplo de código a seguir mostra como resolver um caso do AWS Support.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
suspend fun resolveSupportCase(caseIdVal: String) {
    val caseRequest = ResolveCaseRequest {
        caseId = caseIdVal
    }
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.resolveCase(caseRequest)
        println("The status of case $caseIdVal is ${response.finalCaseStatus}")
    }
}
```

- Para obter detalhes da API, consulte a ResolveCasereferência da API AWSSDK for Kotlin.

Cenários

Conceitos básicos de casos

O código de exemplo a seguir mostra como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.
- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

SDK for Kotlin

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/**
Before running this Kotlin code example, set up your development environment,
including your credentials.

For more information, see the following documentation topic:

https://docs.aws.amazon.com/sdk-for-kotlin/latest/developer-guide/setup.html
In addition, you must have the AWS Business Support Plan to use the AWS Support Java
 API. For more information, see:

https://aws.amazon.com/premiumsupport/plans/

This Kotlin example performs the following tasks:
1. Gets and displays available services.
2. Gets and displays severity levels.
3. Creates a support case by using the selected service, category, and severity
 level.
4. Gets a list of open cases for the current day.
5. Creates an attachment set with a generated file.
6. Adds a communication with the attachment to the support case.
7. Lists the communications of the support case.
8. Describes the attachment set included with the communication.
9. Resolves the support case.
10. Gets a list of resolved cases for the current day.
*/

suspend fun main(args: Array<String>) {
    val usage = """
    Usage:
        <fileAttachment>
    Where:
         fileAttachment - The file can be a simple saved .txt file to use as an
 email attachment.
    """
```

```
    if (args.size != 1) {
        println(usage)
        exitProcess(0)
    }

    val fileAttachment = args[0]
    println("***** Welcome to the AWS Support case example scenario.")
    println("***** Step 1. Get and display available services.")
    val sevCatList = displayServices()

    println("***** Step 2. Get and display Support severity levels.")
    val sevLevel = displaySevLevels()

    println("***** Step 3. Create a support case using the selected service,
category, and severity level.")
    val caseIdVal = createSupportCase(sevCatList, sevLevel)
    if (caseIdVal != null) {
        println("Support case $caseIdVal was successfully created!")
    } else {
        println("A support case was not successfully created!")
        exitProcess(1)
    }

    println("***** Step 4. Get open support cases.")
    getOpenCase()

    println("***** Step 5. Create an attachment set with a generated file to add to
the case.")
    val attachmentSetId = addAttachment(fileAttachment)
    println("The Attachment Set id value is $attachmentSetId")

    println("***** Step 6. Add communication with the attachment to the support
case.")
    addAttachSupportCase(caseIdVal, attachmentSetId)

    println("***** Step 7. List the communications of the support case.")
    val attachId = listCommunications(caseIdVal)
    println("The Attachment id value is $attachId")

    println("***** Step 8. Describe the attachment set included with the
communication.")
    describeAttachment(attachId)
```

```
    println("***** Step 9. Resolve the support case.")
    resolveSupportCase(caseIdVal)

    println("***** Step 10. Get a list of resolved cases for the current day.")
    getResolvedCase()
    println("***** This Scenario has successfully completed")
}

suspend fun getResolvedCase() {
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 30
        afterTime = yesterday.toString()
        beforeTime = now.toString()
        includeResolvedCases = true
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}

suspend fun resolveSupportCase(caseIdVal: String) {
    val caseRequest = ResolveCaseRequest {
        caseId = caseIdVal
    }
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.resolveCase(caseRequest)
        println("The status of case $caseIdVal is ${response.finalCaseStatus}")
    }
}

suspend fun describeAttachment(attachId: String?) {
    val attachmentRequest = DescribeAttachmentRequest {
        attachmentId = attachId
    }
```

```
    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeAttachment(attachmentRequest)
        println("The name of the file is ${response.attachment?.fileName}")
    }
}

suspend fun listCommunications(caseIdVal: String?): String? {
    val communicationsRequest = DescribeCommunicationsRequest {
        caseId = caseIdVal
        maxResults = 10
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCommunications(communicationsRequest)
        response.communications?.forEach { comm ->
            println("the body is: " + comm.body)
            comm.attachmentSet?.forEach { detail ->
                return detail.attachmentId
            }
        }
    }
    return ""
}

suspend fun addAttachSupportCase(caseIdVal: String?, attachmentSetIdVal: String?) {
    val caseRequest = AddCommunicationToCaseRequest {
        caseId = caseIdVal
        attachmentSetId = attachmentSetIdVal
        communicationBody = "Please refer to attachment for details."
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addCommunicationToCase(caseRequest)
        if (response.result) {
            println("You have successfully added a communication to an AWS Support
 case")
        } else {
            println("There was an error adding the communication to an AWS Support
 case")
        }
    }
}
```

```
suspend fun addAttachment(fileAttachment: String): String? {
    val myFile = File(fileAttachment)
    val sourceBytes = (File(fileAttachment).readBytes())
    val attachmentVal = Attachment {
        fileName = myFile.name
        data = sourceBytes
    }

    val setRequest = AddAttachmentsToSetRequest {
        attachments = listOf(attachmentVal)
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.addAttachmentsToSet(setRequest)
        return response.attachmentSetId
    }
}

suspend fun getOpenCase() {
    // Specify the start and end time.
    val now = Instant.now()
    LocalDate.now()
    val yesterday = now.minus(1, ChronoUnit.DAYS)
    val describeCasesRequest = DescribeCasesRequest {
        maxResults = 20
        afterTime = yesterday.toString()
        beforeTime = now.toString()
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeCases(describeCasesRequest)
        response.cases?.forEach { sinCase ->
            println("The case status is ${sinCase.status}")
            println("The case Id is ${sinCase.caseId}")
            println("The case subject is ${sinCase.subject}")
        }
    }
}

suspend fun createSupportCase(sevCatListVal: List<String>, sevLevelVal: String):
 String? {
    val serCode = sevCatListVal[0]
    val caseCategory = sevCatListVal[1]
    val caseRequest = CreateCaseRequest {
```

```
        categoryCode = caseCategory.lowercase(Locale.getDefault())
        serviceCode = serCode.lowercase(Locale.getDefault())
        severityCode = sevLevelVal.lowercase(Locale.getDefault())
        communicationBody = "Test issue with
 ${serCode.lowercase(Locale.getDefault())}"
        subject = "Test case, please ignore"
        language = "en"
        issueType = "technical"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.createCase(caseRequest)
        return response.caseId
    }
}

suspend fun displaySevLevels(): String {
    var levelName = ""
    val severityLevelsRequest = DescribeSeverityLevelsRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
        val response = supportClient.describeSeverityLevels(severityLevelsRequest)
        response.severityLevels?.forEach { sevLevel ->
            println("The severity level name is: ${sevLevel.name}")
            if (sevLevel.name == "High") {
                levelName = sevLevel.name!!
            }
        }
        return levelName
    }
}

// Return a List that contains a Service name and Category name.
suspend fun displayServices(): List<String> {
    var serviceCode = ""
    var catName = ""
    val sevCatList = mutableListOf<String>()
    val servicesRequest = DescribeServicesRequest {
        language = "en"
    }

    SupportClient { region = "us-west-2" }.use { supportClient ->
```

```
        val response = supportClient.describeServices(servicesRequest)
        println("Get the first 10 services")
        var index = 1

        response.services?.forEach { service ->
            if (index == 11) {
                return@forEach
            }

            println("The Service name is ${service.name}")
            if (service.name == "Account") {
                serviceCode = service.code.toString()
            }

            // Get the categories for this service.
            service.categories?.forEach { cat ->
                println("The category name is ${cat.name}")
                if (cat.name == "Security") {
                    catName = cat.name!!
                }
            }
            index++
        }
    }

    // Push the two values to the list.
    serviceCode.let { sevCatList.add(it) }
    catName.let { sevCatList.add(it) }
    return sevCatList
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Kotlin.
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications

- DescribeServices
- DescribeSeverityLevels
- ResolveCase

Exemplos de serviços cruzados usando SDK para Kotlin

Os aplicativos de exemplo a seguir usam o AWS SDK para Kotlin para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicações.

Exemplos

- Criar uma aplicação para enviar dados para uma tabela do DynamoDB
- Criar uma aplicação de publicação e assinatura que traduz mensagens
- Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Criar um rastreador de itens do Amazon Redshift
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

Criar uma aplicação para enviar dados para uma tabela do DynamoDB

SDK for Kotlin

Mostra como criar uma aplicação Android nativa que envia dados usando a API Kotlin do Amazon DynamoDB e envia uma mensagem de texto usando a API Kotlin do Amazon SNS.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB

- Amazon SNS

Criar uma aplicação de publicação e assinatura que traduz mensagens

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon SNS para criar uma aplicação com funcionalidade de assinatura e publicação. Além disso, essa aplicação de exemplo também traduz mensagens.

Para obter o código-fonte completo e instruções sobre como criar um aplicativo web, veja o exemplo completo em GitHub.

Para ver o código-fonte completo e instruções sobre como criar um aplicativo Android nativo, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon Translate

Criar um aplicativo web que envie e recupere mensagens usando o Amazon SQS

SDK for Kotlin

Mostra como usar a API do Amazon SQS para desenvolver uma API REST que envia e recupera mensagens.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon SQS

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK for Kotlin

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Criar uma aplicação Web para monitorar dados do DynamoDB

SDK for Kotlin

Mostra como usar a API do Amazon DynamoDB para construir uma aplicação Web dinâmica que monitora os dados de trabalho do DynamoDB.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Criar um rastreador de itens do Amazon Redshift

SDK for Kotlin

Mostra como criar uma aplicação Web que rastreia e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon Redshift.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Redshift e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon Redshift
- Amazon SES

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK for Kotlin

Mostra como construir uma aplicação Web que monitora e gera relatórios sobre itens de trabalho armazenados em um banco de dados do Amazon RDS.

Para obter o código-fonte completo e instruções sobre como configurar uma API Spring REST que consulta dados do Amazon Aurora Serverless e para uso por um aplicativo React, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

SDK for Kotlin

Mostra como usar a API Kotlin do Amazon Rekognition para construir uma aplicação que usa o Amazon Rekognition para identificar objetos por categoria em imagens localizadas em um bucket

do Amazon Simple Storage Service (Amazon S3). A aplicação envia uma notificação por e-mail ao administrador com os resultados usando o Amazon Simple Email Service (Amazon SES).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Publicação de mensagens do Amazon SNS nas filas do Amazon SQS usando um AWS SDK

SDK for Kotlin

Demonstra mensagens com tópicos e filas usando o Amazon Simple Notification Service (Amazon SNS) e o Amazon Simple Queue Service (Amazon SQS).

Para obter o código-fonte completo e as instruções que demonstram mensagens com tópicos e filas no Amazon SNS e no Amazon SQS, veja o exemplo completo em. GitHub

Serviços utilizados neste exemplo

- Amazon SNS
- Amazon SQS

Exemplos de código para o SDK para PHP.

Os exemplos a seguir mostram como usar o AWS SDK for PHP com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do Desenvolvedor do SDK para PHP : Saiba mais sobre como usar o PHP com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para PHP
- Exemplos para entre serviços usando SDK para PHP

Ações e cenários usando o SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de API Gateway usando SDK for PHP
- Exemplos do Auto Scaling usando o SDK para PHP
- Exemplos do Amazon Bedrock usando o SDK para PHP
- Exemplos do Amazon Bedrock Runtime usando o SDK para PHP
- Exemplos de código do DynamoDB usando SDK para PHP
- Exemplos de AWS Glue usando SDK for PHP
- Exemplos do IAM usando SDK para PHP
- Exemplos do Kinesis usando SDK for PHP
- Exemplos de código do Lambda usando SDK para PHP
- Exemplos do Amazon RDS usando SDK for PHP

- Exemplos de código do Amazon S3 usando SDK para PHP
- Exemplos de código para o Amazon SNS usando SDK para PHP
- Exemplos do Amazon SQS usando SDK for PHP

Exemplos de API Gateway usando SDK for PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com o API Gateway.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter o mapeamento do caminho básico

O exemplo de código a seguir mostra como obter um mapeamento de caminho base do API Gateway.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';
```

```
use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 * Purpose: Gets the base path mapping for a custom domain name in
 * Amazon API Gateway.
 *
 * Prerequisites: A custom domain name in API Gateway. For more information,
 * see "Custom Domain Names" in the Amazon API Gateway Developer Guide.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $basePath: The base path name that callers must provide as part of the
 *   URL after the domain name.
 * - $domainName: The custom domain name for the base path mapping.
 *
 * Returns: The base path mapping, if available; otherwise, the error message.
 * /////////////////////////////////////////////////////////////////////////// */

function getBasePathMapping($apiGatewayClient, $basePath, $domainName)
{
    try {
        $result = $apiGatewayClient->getBasePathMapping([
            'basePath' => $basePath,
            'domainName' => $domainName,
        ]);
        return 'The base path mapping\'s effective URI is: ' .
            $result['@metadata']['effectiveUri'];
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function getsTheBasePathMapping()
{
    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo getBasePathMapping($apiGatewayClient, '(none)', 'example.com');
```

```
}

// Uncomment the following line to run this code in an AWS account.
// getsTheBasePathMapping();
```

- Para obter detalhes da API, consulte GetBasePathMappinga Referência AWS SDK for PHP da API.

Mapeamento do caminho base da lista

O exemplo de código a seguir mostra como ter uma lista de mapeamento de caminho base do API Gateway.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 * Purpose: Lists the base path mapping for a custom domain name in
 * Amazon API Gateway.
 *
 * Prerequisites: A custom domain name in API Gateway. For more information,
 * see "Custom Domain Names" in the Amazon API Gateway Developer Guide.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $domainName: The custom domain name for the base path mappings.
 *
 * Returns: Information about the base path mappings, if available;
```

```
 * otherwise, the error message.
 * ////////////////////////////////////////////////////////////////////// */

function listBasePathMappings($apiGatewayClient, $domainName)
{
    try {
        $result = $apiGatewayClient->getBasePathMappings([
            'domainName' => $domainName
        ]);
        return 'The base path mapping(s) effective URI is: ' .
            $result['@metadata']['effectiveUri'];
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function listTheBasePathMappings()
{
    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo listBasePathMappings($apiGatewayClient, 'example.com');
}

// Uncomment the following line to run this code in an AWS account.
// listTheBasePathMappings();
```

- Para obter detalhes da API, consulte ListBasePathMappingsa Referência AWS SDK for PHP da API.

Atualizar o mapeamento do caminho base

O exemplo de código a seguir mostra como atualizar um mapeamento de caminho base do API Gateway.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\ApiGateway\ApiGatewayClient;
use Aws\Exception\AwsException;


/* ///////////////////////////////////////////////////////////////////////////
 *
 * Purpose: Updates the base path mapping for a custom domain name
 * in Amazon API Gateway.
 *
 * Inputs:
 * - $apiGatewayClient: An initialized AWS SDK for PHP API client for
 *   API Gateway.
 * - $basePath: The base path name that callers must provide as part of the
 *   URL after the domain name.
 * - $domainName: The custom domain name for the base path mapping.
 * - $patchOperations: The base path update operations to apply.
 *
 * Returns: Information about the updated base path mapping, if available;
 * otherwise, the error message.
 * ////////////////////////////////////////////////////////////////////////// */

function updateBasePathMapping(
    $apiGatewayClient,
    $basePath,
    $domainName,
    $patchOperations
) {
    try {
        $result = $apiGatewayClient->updateBasePathMapping([
            'basePath' => $basePath,
            'domainName' => $domainName,
            'patchOperations' => $patchOperations
```

```
        ]);
        return 'The updated base path\'s URI is: ' .
            $result['@metadata']['effectiveUri'];
    } catch (AwsException $e) {
        return 'Error: ' . $e['message'];
    }
}

function updateTheBasePathMapping()
{
    $patchOperations = array([
        'op' => 'replace',
        'path' => '/stage',
        'value' => 'stage2'
    ]);

    $apiGatewayClient = new ApiGatewayClient([
        'profile' => 'default',
        'region' => 'us-east-1',
        'version' => '2015-07-09'
    ]);

    echo updateBasePathMapping(
        $apiGatewayClient,
        '(none)',
        'example.com',
        $patchOperations
    );
}

// Uncomment the following line to run this code in an AWS account.
// updateTheBasePathMapping();
```

- Para obter detalhes da API, consulte UpdateBasePathMappinga Referência AWS SDK for PHP da API.

Exemplos do Auto Scaling usando o SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function helloService()
{
    $autoScalingClient = new AutoScalingClient([
        'region' => 'us-west-2',
        'version' => 'latest',
        'profile' => 'default',
    ]);

    $groups = $autoScalingClient->describeAutoScalingGroups([]);
    var_dump($groups);
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for PHP da API.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function createAutoScalingGroup(
    $autoScalingGroupName,
    $availabilityZones,
    $minSize,
    $maxSize,
    $launchTemplateId
) {
    return $this->autoScalingClient->createAutoScalingGroup([
        'AutoScalingGroupName' => $autoScalingGroupName,
        'AvailabilityZones' => $availabilityZones,
        'MinSize' => $minSize,
        'MaxSize' => $maxSize,
        'LaunchTemplate' => [
            'LaunchTemplateId' => $launchTemplateId,
        ],
    ]);
}
```

- Para obter detalhes da API, consulte CreateAutoScalingGroupa Referência AWS SDK for PHP da API.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function deleteAutoScalingGroup($autoScalingGroupName)
{
    return $this->autoScalingClient->deleteAutoScalingGroup([
        'AutoScalingGroupName' => $autoScalingGroupName,
        'ForceDelete' => true,
    ]);
}
```

- Para obter detalhes da API, consulte DeleteAutoScalingGroupa Referência AWS SDK for PHP da API.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function disableMetricsCollection($autoScalingGroupName)
{
```

```
        return $this->autoScalingClient->disableMetricsCollection([
            'AutoScalingGroupName' => $autoScalingGroupName,
        ]);
    }
```

- Para obter detalhes da API, consulte DisableMetricsCollectiona Referência AWS SDK for PHP da API.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function enableMetricsCollection($autoScalingGroupName, $granularity)
    {
        return $this->autoScalingClient->enableMetricsCollection([
            'AutoScalingGroupName' => $autoScalingGroupName,
            'Granularity' => $granularity,
        ]);
    }
```

- Para obter detalhes da API, consulte EnableMetricsCollectiona Referência AWS SDK for PHP da API.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informações sobre grupos do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function describeAutoScalingGroups($autoScalingGroupNames)
{
    return $this->autoScalingClient->describeAutoScalingGroups([
        'AutoScalingGroupNames' => $autoScalingGroupNames
    ]);
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingGroupsa Referência AWS SDK for PHP da API.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function describeAutoScalingInstances($instanceIds)
{
    return $this->autoScalingClient->describeAutoScalingInstances([
        'InstanceIds' => $instanceIds
    ]);
}
```

- Para obter detalhes da API, consulte DescribeAutoScalingInstancesa Referência AWS SDK for PHP da API.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informações sobre as atividades do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function describeScalingActivities($autoScalingGroupName)
{
    return $this->autoScalingClient->describeScalingActivities([
        'AutoScalingGroupName' => $autoScalingGroupName,
    ]);
}
```

- Para obter detalhes da API, consulte DescribeScalingActivitiesa Referência AWS SDK for PHP da API.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function setDesiredCapacity($autoScalingGroupName, $desiredCapacity)
    {
        return $this->autoScalingClient->setDesiredCapacity([
            'AutoScalingGroupName' => $autoScalingGroupName,
            'DesiredCapacity' => $desiredCapacity,
        ]);
    }
```

- Para obter detalhes da API, consulte SetDesiredCapacitya Referência AWS SDK for PHP da API.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function terminateInstanceInAutoScalingGroup(
        $instanceId,
        $shouldDecrementDesiredCapacity = true,
        $attempts = 0
    ) {
        try {
            return $this->autoScalingClient->terminateInstanceInAutoScalingGroup([
                'InstanceId' => $instanceId,
                'ShouldDecrementDesiredCapacity' => $shouldDecrementDesiredCapacity,
            ]);
        } catch (AutoScalingException $exception) {
            if ($exception->getAwsErrorCode() == "ScalingActivityInProgress" &&
$attempts < 5) {
                error_log("Cannot terminate an instance while it is still pending.
Waiting then trying again.");
                sleep(5 * (1 + $attempts));
                return $this->terminateInstanceInAutoScalingGroup(
```

```
                    $instanceId,
                    $shouldDecrementDesiredCapacity,
                    ++$attempts
                );
            } else {
                throw $exception;
            }
        }
    }
```

- Para obter detalhes da API, consulte TerminateInstanceInAutoScalingGroupa Referência AWS SDK for PHP da API.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo do Auto Scaling.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function updateAutoScalingGroup($autoScalingGroupName, $args)
    {
        if (array_key_exists('MaxSize', $args)) {
            $maxSize = ['MaxSize' => $args['MaxSize']];
        } else {
            $maxSize = [];
        }
        if (array_key_exists('MinSize', $args)) {
            $minSize = ['MinSize' => $args['MinSize']];
        } else {
            $minSize = [];
        }
        $parameters = ['AutoScalingGroupName' => $autoScalingGroupName];
        $parameters = array_merge($parameters, $minSize, $maxSize);
        return $this->autoScalingClient->updateAutoScalingGroup($parameters);
    }
```

- Para obter detalhes da API, consulte UpdateAutoScalingGroupa Referência AWS SDK for PHP da API.

Cenários

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace AutoScaling;

use Aws\AutoScaling\AutoScalingClient;
use Aws\CloudWatch\CloudWatchClient;
use Aws\Ec2\Ec2Client;
use AwsUtilities\AWSServiceClass;
use AwsUtilities\RunnableExample;

class GettingStartedWithAutoScaling implements RunnableExample
{
```

```
    protected Ec2Client $ec2Client;
    protected AutoScalingClient $autoScalingClient;
    protected AutoScalingService $autoScalingService;
    protected CloudWatchClient $cloudWatchClient;
    protected string $templateName;
    protected string $autoScalingGroupName;
    protected array $role;

    public function runExample()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon EC2 Auto Scaling getting started demo using
 PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();

        $this->autoScalingClient = new AutoScalingClient($clientArgs);
        $this->autoScalingService = new AutoScalingService($this-
>autoScalingClient);
        $this->cloudWatchClient = new CloudWatchClient($clientArgs);

        AWSServiceClass::$waitTime = 5;
        AWSServiceClass::$maxWaitAttempts = 20;

        /**
         * Step 0: Create an EC2 launch template that you'll use to create an Auto
 Scaling group.
         */
        $this->ec2Client = new EC2Client($clientArgs);
        $this->templateName = "example_launch_template_$uniqid";
        $instanceType = "t1.micro";
        $amiId = "ami-0ca285d4c2cda3300";
        $launchTemplate = $this->ec2Client->createLaunchTemplate(
            [
            'LaunchTemplateName' => $this->templateName,
            'LaunchTemplateData' => [
                'InstanceType' => $instanceType,
```

```
                'ImageId' => $amiId,
            ]
            ]
        );

        /**
         * Step 1: CreateAutoScalingGroup: pass it the launch template you created
 in step 0.
         */
        $availabilityZones[] = $this->ec2Client->describeAvailabilityZones([])
['AvailabilityZones'][1]['ZoneName'];

        $this->autoScalingGroupName = "demoAutoScalingGroupName_$uniqid";
        $minSize = 1;
        $maxSize = 1;
        $launchTemplateId = $launchTemplate['LaunchTemplate']['LaunchTemplateId'];
        $this->autoScalingService->createAutoScalingGroup(
            $this->autoScalingGroupName,
            $availabilityZones,
            $minSize,
            $maxSize,
            $launchTemplateId
        );

        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        $autoScalingGroup = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);

        /**
         * Step 2: DescribeAutoScalingInstances: show that one instance has
 launched.
         */
        $instanceIds = [$autoScalingGroup['AutoScalingGroups'][0]['Instances'][0]
['InstanceId']];
        $instances = $this->autoScalingService-
>describeAutoScalingInstances($instanceIds);
        echo "The Auto Scaling group {$this->autoScalingGroupName} was created
 successfully.\n";
        echo count($instances['AutoScalingInstances']) . " instances were created
 for the group.\n";
        echo $autoScalingGroup['AutoScalingGroups'][0]['MaxSize'] . " is the max
 number of instances for the group.\n";
```

```
        /**
         * Step 3: EnableMetricsCollection: enable all metrics or a subset.
         */
        $this->autoScalingService->enableMetricsCollection($this-
>autoScalingGroupName, "1Minute");

        /**
         * Step 4: UpdateAutoScalingGroup: update max size to 3.
         */
        echo "Updating the max number of instances to 3.\n";
        $this->autoScalingService->updateAutoScalingGroup($this-
>autoScalingGroupName, ['MaxSize' => 3]);

        /**
         * Step 5: DescribeAutoScalingGroups: show the current state of the group.
         */
        $autoScalingGroup = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
        echo $autoScalingGroup['AutoScalingGroups'][0]['MaxSize'];
        echo " is the updated max number of instances for the group.\n";

        $limits = $this->autoScalingService->describeAccountLimits();
        echo "Here are your account limits:\n";
        echo "MaxNumberOfAutoScalingGroups:
 {$limits['MaxNumberOfAutoScalingGroups']}\n";
        echo "MaxNumberOfLaunchConfigurations:
 {$limits['MaxNumberOfLaunchConfigurations']}\n";
        echo "NumberOfAutoScalingGroups: {$limits['NumberOfAutoScalingGroups']}\n";
        echo "NumberOfLaunchConfigurations:
 {$limits['NumberOfLaunchConfigurations']}\n";

        /**
         * Step 6: SetDesiredCapacity: set desired capacity to 2.
         */
        $this->autoScalingService->setDesiredCapacity($this->autoScalingGroupName,
 2);
        sleep(10); // Wait for the group to start processing the request.
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);

        /**
         * Step 7: DescribeAutoScalingInstances: show that two instances are
 launched.
         */
```

```
        $autoScalingGroups = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
        foreach ($autoScalingGroups['AutoScalingGroups'] as $autoScalingGroup) {
            echo "There is a group named:
 {$autoScalingGroup['AutoScalingGroupName']}";
            echo "with an ARN of {$autoScalingGroup['AutoScalingGroupARN']}.\n";
            foreach ($autoScalingGroup['Instances'] as $instance) {
                echo "{$autoScalingGroup['AutoScalingGroupName']} has an instance
 with id of: ";
                echo "{$instance['InstanceId']} and a lifecycle state of:
 {$instance['LifecycleState']}.\n";
            }
        }

        /**
         * Step 8: TerminateInstanceInAutoScalingGroup: terminate one of the
 instances in the group.
         */
        $this->autoScalingService-
>terminateInstanceInAutoScalingGroup($instance['InstanceId'], false);
        do {
            sleep(10);
            $instances = $this->autoScalingService-
>describeAutoScalingInstances([$instance['InstanceId']]);
        } while (count($instances['AutoScalingInstances']) > 0);
        do {
            sleep(10);
            $autoScalingGroups = $this->autoScalingService-
>describeAutoScalingGroups([$this->autoScalingGroupName]);
            $instances = $autoScalingGroups['AutoScalingGroups'][0]['Instances'];
        } while (count($instances) < 2);
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        foreach ($autoScalingGroups['AutoScalingGroups'] as $autoScalingGroup) {
            echo "There is a group named:
 {$autoScalingGroup['AutoScalingGroupName']}";
            echo "with an ARN of {$autoScalingGroup['AutoScalingGroupARN']}.\n";
            foreach ($autoScalingGroup['Instances'] as $instance) {
                echo "{$autoScalingGroup['AutoScalingGroupName']} has an instance
 with id of: ";
                echo "{$instance['InstanceId']} and a lifecycle state of:
 {$instance['LifecycleState']}.\n";
            }
        }
```

```
        /**
         * Step 9: DescribeScalingActivities: list the scaling activities that have
 occurred for the group so far.
         */
        $activities = $this->autoScalingService-
>describeScalingActivities($autoScalingGroup['AutoScalingGroupName']);
        echo "We found " . count($activities['Activities']) . " activities.\n";
        foreach ($activities['Activities'] as $activity) {
            echo "{$activity['ActivityId']} - {$activity['StartTime']} -
 {$activity['Description']}\n";
        }

        /**
         * Step 10: Use the Amazon CloudWatch API to get and show some metrics
 collected for the group.
         */
        $metricsNamespace = 'AWS/AutoScaling';
        $metricsDimensions = [
            [
                'Name' => 'AutoScalingGroupName',
                'Value' => $autoScalingGroup['AutoScalingGroupName'],
            ],
        ];
        $metrics = $this->cloudWatchClient->listMetrics(
            [
            'Dimensions' => $metricsDimensions,
            'Namespace' => $metricsNamespace,
            ]
        );
        foreach ($metrics['Metrics'] as $metric) {
            $timespan = 5;
            if ($metric['MetricName'] != 'GroupTotalCapacity' &&
 $metric['MetricName'] != 'GroupMaxSize') {
                continue;
            }
            echo "Over the last $timespan minutes, {$metric['MetricName']} recorded:
\n";
            $stats = $this->cloudWatchClient->getMetricStatistics(
                [
                'Dimensions' => $metricsDimensions,
                'EndTime' => time(),
                'StartTime' => time() - (5 * 60),
                'MetricName' => $metric['MetricName'],
```

```
                'Namespace' => $metricsNamespace,
                'Period' => 60,
                'Statistics' => ['Sum'],
                ]
            );
            foreach ($stats['Datapoints'] as $stat) {
                echo "{$stat['Timestamp']}: {$stat['Sum']}\n";
            }
        }

        return $instances;
    }

    public function cleanUp()
    {
        /**
         * Step 11: DisableMetricsCollection: disable all metrics.
         */
        $this->autoScalingService->disableMetricsCollection($this-
>autoScalingGroupName);

        /**
         * Step 12: DeleteAutoScalingGroup: to delete the group you must stop all
 instances.
         * - UpdateAutoScalingGroup with MinSize=0
         * - TerminateInstanceInAutoScalingGroup for each instance,
         *     specify ShouldDecrementDesiredCapacity=True. Wait for instances to
 stop.
         * - Now you can delete the group.
         */
        $this->autoScalingService->updateAutoScalingGroup($this-
>autoScalingGroupName, ['MinSize' => 0]);
        $this->autoScalingService->terminateAllInstancesInAutoScalingGroup($this-
>autoScalingGroupName);
        $this->autoScalingService->waitUntilGroupInService([$this-
>autoScalingGroupName]);
        $this->autoScalingService->deleteAutoScalingGroup($this-
>autoScalingGroupName);

        /**
         * Step 13: Delete launch template.
         */
        $this->ec2Client->deleteLaunchTemplate(
            [
```

```
            'LaunchTemplateName' => $this->templateName,
            ]
        );
    }

    public function helloService()
    {
        $autoScalingClient = new AutoScalingClient([
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ]);

        $groups = $autoScalingClient->describeAutoScalingGroups([]);
        var_dump($groups);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
public function listFoundationModels()
{
    $result = $this->bedrockClient->listFoundationModels();
    return $result;
}
```

- Para obter detalhes da API, consulte ListFoundationModelsa Referência AWS SDK for PHP da API.

Exemplos do Amazon Bedrock Runtime usando o SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Geração de imagens com o Image Generator G1 do Amazon Titan

O exemplo de código a seguir mostra como invocar o modelo Amazon Titan Image Generator no Amazon Bedrock para geração de imagens.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
    public function invokeTitanImage(string $prompt, int $seed)
    {
        # The different model providers have individual request and response
formats.
```

```
        # For the format, ranges, and default values for Titan Image models refer
 to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-image.html

        $base64_image_data = "";

        try {
            $modelId = 'amazon.titan-image-generator-v1';

            $request = json_encode([
                'taskType' => 'TEXT_IMAGE',
                'textToImageParams' => [
                    'text' => $prompt
                ],
                'imageGenerationConfig' => [
                    'numberOfImages' => 1,
                    'quality' => 'standard',
                    'cfgScale' => 8.0,
                    'height' => 512,
                    'width' => 512,
                    'seed' => $seed
                ]
            ]);

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => $request,
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $base64_image_data = $response_body->images[0];
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $base64_image_data;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Geração de imagens com o Stable Diffusion XL da Stability.ai

O exemplo de código a seguir mostra como invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para a geração de imagens.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    public function invokeStableDiffusion(string $prompt, int $seed, string
 $style_preset)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and available style_presets of Stable Diffusion
 models refer to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
stability-diffusion.html

        $base64_image_data = "";

        try {
            $modelId = 'stability.stable-diffusion-xl';

            $body = [
                'text_prompts' => [
                    ['text' => $prompt]
                ],
                'seed' => $seed,
                'cfg_scale' => 10,
                'steps' => 30
            ];

            if ($style_preset) {
                $body['style_preset'] = $style_preset;
            }
```

```
            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $base64_image_data = $response_body->artifacts[0]->base64;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $base64_image_data;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
    public function invokeJurassic2($prompt)
    {
        # The different model providers have individual request and response
formats.
        # For the format, ranges, and default values for AI21 Labs Jurassic-2, refer
to:
```

```
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html

        $completion = "";

        try {
            $modelId = 'ai21.j2-mid-v1';

            $body = [
                'prompt' => $prompt,
                'temperature' => 0.5,
                'maxTokens' => 200,
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->completions[0]->data->text;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
    public function invokeClaude($prompt)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for Anthropic Claude, refer to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html

        $completion = "";

        try {
            $modelId = 'anthropic.claude-v2';

            # Claude requires you to enclose the prompt as follows:
            $prompt = "\n\nHuman: {$prompt}\n\nAssistant:";

            $body = [
                'prompt' => $prompt,
                'max_tokens_to_sample' => 200,
                'temperature' => 0.5,
                'stop_sequences' => ["\n\nHuman:"],
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->completion;
        } catch (Exception $e) {
```

```
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
    public function invokeLlama2($prompt)
    {
        # The different model providers have individual request and response
 formats.
        # For the format, ranges, and default values for Meta Llama 2 Chat, refer
 to:
        # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html

        $completion = "";

        try {
            $modelId = 'meta.llama2-13b-chat-v1';

            $body = [
                'prompt' => $prompt,
                'temperature' => 0.5,
```

```
                'max_gen_len' => 512,
            ];

            $result = $this->bedrockRuntimeClient->invokeModel([
                'contentType' => 'application/json',
                'body' => json_encode($body),
                'modelId' => $modelId,
            ]);

            $response_body = json_decode($result['body']);

            $completion = $response_body->generation;
        } catch (Exception $e) {
            echo "Error: ({$e->getCode()}) - {$e->getMessage()}\n";
        }

        return $completion;
    }
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Cenários

Invocar vários LLMs no Amazon Bedrock

O exemplo de código a seguir mostra como invocar vários large-language-models (LLMs) no Amazon Bedrock.

- Gere texto com Claude da Anthropic.
- Gere texto com o AI21 Labs Jurassic-2.
- Gere texto com o Chat Llama 2 da Meta.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque vários LLMs no Amazon Bedrock.

```
namespace BedrockRuntime;

class GettingStartedWithBedrockRuntime
{
    protected BedrockRuntimeService $bedrockRuntimeService;

    public function runExample()
    {
        echo "\n";
        echo "----------------------------------------------------------------------
\n";
        echo "Welcome to the Amazon Bedrock Runtime getting started demo using PHP!
\n";
        echo "----------------------------------------------------------------------
\n";

        $clientArgs = [
            'region' => 'us-east-1',
            'version' => 'latest',
            'profile' => 'default',
        ];

        $bedrockRuntimeService = new BedrockRuntimeService($clientArgs);

        $prompt = 'In one paragraph, who are you?';

        echo "\nPrompt: " . $prompt;

        echo "\n\nAnthropic Claude:";
        echo $bedrockRuntimeService->invokeClaude($prompt);

        echo "\n\nAI21 Labs Jurassic-2: ";
        echo $bedrockRuntimeService->invokeJurassic2($prompt);

        echo "\n\nMeta Llama 2 Chat: ";
        echo $bedrockRuntimeService->invokeLlama2($prompt);

        echo
 "\n----------------------------------------------------------------------\n";

        $image_prompt = 'stylized picture of a cute old steampunk robot';
```

```
        echo "\nImage prompt: " . $image_prompt;

        echo "\n\nStability.ai Stable Diffusion XL:\n";
        $diffusionSeed = rand(0, 4294967295);
        $style_preset = 'photographic';
        $base64 = $bedrockRuntimeService->invokeStableDiffusion($image_prompt,
 $diffusionSeed, $style_preset);
        $image_path = $this->saveImage($base64, 'stability.stable-diffusion-xl');
        echo "The generated images have been saved to $image_path";

        echo "\n\nAmazon Titan Image Generation:\n";
        $titanSeed = rand(0, 2147483647);
        $base64 = $bedrockRuntimeService->invokeTitanImage($image_prompt,
 $titanSeed);
        $image_path = $this->saveImage($base64, 'amazon.titan-image-generator-v1');
        echo "The generated images have been saved to $image_path";
    }

    private function saveImage($base64_image_data, $model_id): string
    {
        $output_dir = "output";

        if (!file_exists($output_dir)) {
            mkdir($output_dir);
        }

        $i = 1;
        while (file_exists("$output_dir/$model_id" . '_' . "$i.png")) {
            $i++;
        }

        $image_data = base64_decode($base64_image_data);

        $file_path = "$output_dir/$model_id" . '_' . "$i.png";

        $file = fopen($file_path, 'wb');
        fwrite($file, $image_data);
        fclose($file);

        return $file_path;
    }
}
```

- Para obter detalhes da API, consulte InvokeModela Referência AWS SDK for PHP da API.

Exemplos de código do DynamoDB usando SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela.

```
        $tableName = "ddb_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

    public function createTable(string $tableName, array $attributes)
    {
        $keySchema = [];
        $attributeDefinitions = [];
        foreach ($attributes as $attribute) {
            if (is_a($attribute, DynamoDBAttribute::class)) {
                $keySchema[] = ['AttributeName' => $attribute->AttributeName,
'KeyType' => $attribute->KeyType];
                $attributeDefinitions[] =
                    ['AttributeName' => $attribute->AttributeName, 'AttributeType'
=> $attribute->AttributeType];
            }
        }

        $this->dynamoDbClient->createTable([
            'TableName' => $tableName,
            'KeySchema' => $keySchema,
            'AttributeDefinitions' => $attributeDefinitions,
            'ProvisionedThroughput' => ['ReadCapacityUnits' => 10,
'WriteCapacityUnits' => 10],
        ]);
    }
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for PHP da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function deleteTable(string $TableName)
{
    $this->customWaiter(function () use ($TableName) {
        return $this->dynamoDbClient->deleteTable([
            'TableName' => $TableName,
        ]);
    });
}
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for PHP da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    $key = [
        'Item' => [
            'title' => [
                'S' => $movieName,
            ],
            'year' => [
                'N' => $movieYear,
            ],
```

```
            ]
        ];

        $service->deleteItemByKey($tableName, $key);
        echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

    public function deleteItemByKey(string $tableName, array $key)
    {
        $this->dynamoDbClient->deleteItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for PHP da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $movie = $service->getItemByKey($tableName, $key);
        echo "\nThe movie {$movie['Item']['title']['S']} was released in
{$movie['Item']['year']['N']}.\n";

    public function getItemByKey(string $tableName, array $key)
    {
        return $this->dynamoDbClient->getItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for PHP da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function listTables($exclusiveStartTableName = "", $limit = 100)
{
    $this->dynamoDbClient->listTables([
        'ExclusiveStartTableName' => $exclusiveStartTableName,
        'Limit' => $limit,
    ]);
}
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for PHP da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    echo "What's the name of the last movie you watched?\n";
```

```
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }

        $service->putItem([
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
            'TableName' => $tableName,
        ]);

    public function putItem(array $array)
    {
        $this->dynamoDbClient->putItem($array);
    }
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for PHP da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
        $birthKey = [
```

```
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);

    public function query(string $tableName, $key)
    {
        $expressionAttributeValues = [];
        $expressionAttributeNames = [];
        $keyConditionExpression = "";
        $index = 1;
        foreach ($key as $name => $value) {
            $keyConditionExpression .= "#" . array_key_first($value) . " = :v
$index,";
            $expressionAttributeNames["#" . array_key_first($value)] =
 array_key_first($value);
            $hold = array_pop($value);
            $expressionAttributeValues[":v$index"] = [
                array_key_first($hold) => array_pop($hold),
            ];
        }
        $keyConditionExpression = substr($keyConditionExpression, 0, -1);
        $query = [
            'ExpressionAttributeValues' => $expressionAttributeValues,
            'ExpressionAttributeNames' => $expressionAttributeNames,
            'KeyConditionExpression' => $keyConditionExpression,
            'TableName' => $tableName,
        ];
        return $this->dynamoDbClient->query($query);
    }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for PHP.

Executar uma instrução PartiQL

O exemplo de código a seguir mostra como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function insertItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ]);
    }

    public function getItemByPartiQL(string $tableName, array $key): Result
    {
        list($statement, $parameters) = $this->buildStatementAndParameters("SELECT",
$tableName, $key['Item']);

        return $this->dynamoDbClient->executeStatement([
            'Parameters' => $parameters,
            'Statement' => $statement,
        ]);
    }

    public function updateItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }

    public function deleteItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for PHP da API.

Executar lotes de instruções PartiQL

O exemplo de código a seguir mostra como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function getItemByPartiQLBatch(string $tableName, array $keys): Result
    {
        $statements = [];
        foreach ($keys as $key) {
            list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);
            $statements[] = [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ];
        }

        return $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => $statements,
        ]);
    }

    public function insertItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
```

```
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function updateItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function deleteItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for PHP da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
    $yearsKey = [
        'Key' => [
            'year' => [
                'N' => [
                    'minRange' => 1990,
                    'maxRange' => 1999,
                ],
            ],
        ],
    ];
    $filter = "year between 1990 and 1999";
    echo "\nHere's a list of all the movies released in the 90s:\n";
    $result = $service->scan($tableName, $yearsKey, $filter);
    foreach ($result['Items'] as $movie) {
        $movie = $marshal->unmarshalItem($movie);
        echo $movie['title'] . "\n";
    }

public function scan(string $tableName, array $key, string $filters)
{
    $query = [
        'ExpressionAttributeNames' => ['#year' => 'year'],
        'ExpressionAttributeValues' => [
            ":min" => ['N' => '1990'],
            ":max" => ['N' => '1999'],
        ],
        'FilterExpression' => "#year between :min and :max",
        'TableName' => $tableName,
    ];
    return $this->dynamoDbClient->scan($query);
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for PHP.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "What rating would you like to give {$movie['Item']['title']['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
$rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $service->updateItemAttributeByKey($tableName, $key, 'rating', 'N',
$rating);

    public function updateItemAttributeByKey(
        string $tableName,
        array $key,
        string $attributeName,
        string $attributeType,
        string $newValue
    ) {
        $this->dynamoDbClient->updateItem([
            'Key' => $key['Item'],
            'TableName' => $tableName,
            'UpdateExpression' => "set #NV=:NV",
            'ExpressionAttributeNames' => [
                '#NV' => $attributeName,
            ],
            'ExpressionAttributeValues' => [
                ':NV' => [
                    $attributeType => $newValue
                ]
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for PHP da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public function writeBatch(string $TableName, array $Batch, int $depth = 2)
   {
       if (--$depth <= 0) {
           throw new Exception("Max depth exceeded. Please try with fewer batch
items or increase depth.");
       }

       $marshal = new Marshaler();
       $total = 0;
       foreach (array_chunk($Batch, 25) as $Items) {
           foreach ($Items as $Item) {
               $BatchWrite['RequestItems'][$TableName][] = ['PutRequest' => ['Item'
=> $marshal->marshalItem($Item)]];
           }
           try {
               echo "Batching another " . count($Items) . " for a total of " .
($total += count($Items)) . " items!\n";
               $response = $this->dynamoDbClient->batchWriteItem($BatchWrite);
               $BatchWrite = [];
           } catch (Exception $e) {
               echo "uh oh...";
               echo $e->getMessage();
               die();
           }
           if ($total >= 250) {
               echo "250 movies is probably enough. Right? We can stop there.\n";
```

```
                break;
            }
        }
    }
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for PHP da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace DynamoDb\Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;
use DynamoDb\DynamoDBService;

use function AwsUtilities\loadMovieData;
use function AwsUtilities\testable_readline;
```

```
class GettingStartedWithDynamoDB
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $uuid = uniqid();
        $service = new DynamoDBService();

        $tableName = "ddb_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
 $tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }

        $service->putItem([
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
```

```
            ],
            'TableName' => $tableName,
        ]);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
$rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $key = [
            'Item' => [
                'title' => [
                    'S' => $movieName,
                ],
                'year' => [
                    'N' => $movieYear,
                ],
            ]
        ];
        $attributes = ["rating" =>
            [
                'AttributeName' => 'rating',
                'AttributeType' => 'N',
                'Value' => $rating,
            ],
            'plot' => [
                'AttributeName' => 'plot',
                'AttributeType' => 'S',
                'Value' => $plot,
            ]
        ];
        $service->updateItemAttributesByKey($tableName, $key, $attributes);
        echo "Movie added and updated.";

        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);
```

```
        $movie = $service->getItemByKey($tableName, $key);
        echo "\nThe movie {$movie['Item']['title']['S']} was released in
 {$movie['Item']['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Item']['title']['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
 $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $service->updateItemAttributeByKey($tableName, $key, 'rating', 'N',
 $rating);

        $movie = $service->getItemByKey($tableName, $key);
        echo "Ok, you have rated {$movie['Item']['title']['S']} as a {$movie['Item']
['rating']['N']}\n";

        $service->deleteItemByKey($tableName, $key);
        echo "But, bad news, this was a trap. That movie has now been deleted
 because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something lighter,
 in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were born:
\n";
        $oops = "Oops! There were no movies released in that year (that we know of).
\n";
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
```

```
        echo ($display) ?: $oops;

        $yearsKey = [
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;

use function AwsUtilities\loadMovieData;
use function AwsUtilities\testable_readline;

class GettingStartedWithPartiQLBatch
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo using
 PHP!\n");
        echo("--------------------------------------\n");

        $uuid = uniqid();
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_$uuid";
```

```
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
 $tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
        $service->insertItemByPartiQLBatch($statement, $parameters);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
 $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
```

```
            $plot = testable_readline("Plot summary: ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
        ];

        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQLBatch($statement, $parameters);
        echo "Movie added and updated.\n";

        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);

        $movie = $service->getItemByPartiQLBatch($tableName, [$key]);
        echo "\nThe movie {$movie['Responses'][0]['Item']['title']['S']}
        was released in {$movie['Responses'][0]['Item']['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Responses'][0]['Item']
['title']['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
 $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQLBatch($statement, $parameters);

        $movie = $service->getItemByPartiQLBatch($tableName, [$key]);
        echo "Okay, you have rated {$movie['Responses'][0]['Item']['title']['S']}
        as a {$movie['Responses'][0]['Item']['rating']['N']}\n";

        $service->deleteItemByPartiQLBatch($statement, $parameters);
        echo "But, bad news, this was a trap. That movie has now been deleted
 because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something lighter,
 in what year were you born?\n";
```

```
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were born:
\n";
        $oops = "Oops! There were no movies released in that year (that we know of).
\n";
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
        echo ($display) ?: $oops;

        $yearsKey = [
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
```

```
    }
}

    public function insertItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }

    public function getItemByPartiQLBatch(string $tableName, array $keys): Result
    {
        $statements = [];
        foreach ($keys as $key) {
            list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);
            $statements[] = [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ];
        }

        return $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => $statements,
        ]);
    }

    public function updateItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }
```

```
    public function deleteItemByPartiQLBatch(string $statement, array $parameters)
    {
        $this->dynamoDbClient->batchExecuteStatement([
            'Statements' => [
                [
                    'Statement' => "$statement",
                    'Parameters' => $parameters,
                ],
            ],
        ]);
    }
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for PHP da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;
```

```
use function AwsUtilities\testable_readline;
use function AwsUtilities\loadMovieData;

class GettingStartedWithPartiQL
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo using
 PHP!\n");
        echo("--------------------------------------\n");

        $uuid = uniqid();
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
 $tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
```

```
                'title' => [
                    'S' => $movieName,
                ],
            ],
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
        $service->insertItemByPartiQL($statement, $parameters);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
 $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
        ];

        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQL($statement, $parameters);
        echo "Movie added and updated.\n";



        $batch = json_decode(loadMovieData());

        $service->writeBatch($tableName, $batch);

        $movie = $service->getItemByPartiQL($tableName, $key);
        echo "\nThe movie {$movie['Items'][0]['title']['S']} was released in
 {$movie['Items'][0]['year']['N']}.\n";
        echo "What rating would you like to give {$movie['Items'][0]['title']['S']}?
\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
 $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
```

```
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQL($statement, $parameters);

        $movie = $service->getItemByPartiQL($tableName, $key);
        echo "Okay, you have rated {$movie['Items'][0]['title']['S']} as a
 {$movie['Items'][0]['rating']['N']}\n";

        $service->deleteItemByPartiQL($statement, $parameters);
        echo "But, bad news, this was a trap. That movie has now been deleted
 because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something lighter,
 in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
        $birthKey = [
            'Key' => [
                'year' => [
                    'N' => "$birthYear",
                ],
            ],
        ];
        $result = $service->query($tableName, $birthKey);
        $marshal = new Marshaler();
        echo "Here are the movies in our collection released the year you were born:
\n";
        $oops = "Oops! There were no movies released in that year (that we know of).
\n";
        $display = "";
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            $display .= $movie['title'] . "\n";
        }
        echo ($display) ?: $oops;

        $yearsKey = [
```

```
            'Key' => [
                'year' => [
                    'N' => [
                        'minRange' => 1990,
                        'maxRange' => 1999,
                    ],
                ],
            ],
        ];
        $filter = "year between 1990 and 1999";
        echo "\nHere's a list of all the movies released in the 90s:\n";
        $result = $service->scan($tableName, $yearsKey, $filter);
        foreach ($result['Items'] as $movie) {
            $movie = $marshal->unmarshalItem($movie);
            echo $movie['title'] . "\n";
        }

        echo "\nCleaning up this demo by deleting table $tableName...\n";
        $service->deleteTable($tableName);
    }
}

    public function insertItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ]);
    }

    public function getItemByPartiQL(string $tableName, array $key): Result
    {
        list($statement, $parameters) = $this->buildStatementAndParameters("SELECT",
 $tableName, $key['Item']);

        return $this->dynamoDbClient->executeStatement([
            'Parameters' => $parameters,
            'Statement' => $statement,
        ]);
    }

    public function updateItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
```

```
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }

    public function deleteItemByPartiQL(string $statement, array $parameters)
    {
        $this->dynamoDbClient->executeStatement([
            'Statement' => $statement,
            'Parameters' => $parameters,
        ]);
    }
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for PHP da API.

Exemplos de AWS Glue usando SDK for PHP

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

O exemplo de código a seguir mostra como criar um crawler do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $crawlerName = "example-crawler-test-" . $uniqid;

        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $path = 's3://crawler-public-us-east-1/flight/2016/csv';
        $glueService->createCrawler($crawlerName, $role['Role']['Arn'],
$databaseName, $path);

    public function createCrawler($crawlerName, $role, $databaseName, $path): Result
    {
        return $this->customWaiter(function () use ($crawlerName, $role,
$databaseName, $path) {
            return $this->glueClient->createCrawler([
                'Name' => $crawlerName,
                'Role' => $role,
                'DatabaseName' => $databaseName,
                'Targets' => [
                    'S3Targets' =>
                        [[
                            'Path' => $path,
                        ]]
                ],
            ]);
        });
    }
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for PHP da API.

Crie uma definição de trabalho

O exemplo de código a seguir mostra como criar uma definição de trabalho do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $jobName = 'test-job-' . $uniqid;

        $scriptLocation = "s3://$bucketName/run_job.py";
        $job = $glueService->createJob($jobName, $role['Role']['Arn'],
$scriptLocation);

    public function createJob($jobName, $role, $scriptLocation, $pythonVersion =
'3', $glueVersion = '3.0'): Result
    {
        return $this->glueClient->createJob([
            'Name' => $jobName,
            'Role' => $role,
            'Command' => [
                'Name' => 'glueetl',
                'ScriptLocation' => $scriptLocation,
                'PythonVersion' => $pythonVersion,
            ],
            'GlueVersion' => $glueVersion,
        ]);
    }
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for PHP da API.

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the crawler.\n";
        $glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);

    public function deleteCrawler($crawlerName)
    {
        return $this->glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for PHP da API.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the databases.\n";
        $glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);
```

```
    public function deleteDatabase($databaseName)
    {
        return $this->glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for PHP da API.

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the job.\n";
        $glueClient->deleteJob([
            'JobName' => $job['Name'],
        ]);

    public function deleteJob($jobName)
    {
        return $this->glueClient->deleteJob([
            'JobName' => $jobName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for PHP da API.

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela do AWS Glue Data Catalog.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Delete the tables.\n";
        foreach ($tables['TableList'] as $table) {
            $glueService->deleteTable($table['Name'], $databaseName);
        }

    public function deleteTable($tableName, $databaseName)
    {
        return $this->glueClient->deleteTable([
            'DatabaseName' => $databaseName,
            'Name' => $tableName,
        ]);
    }
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for PHP da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        echo "Waiting for crawler";
        do {
            $crawler = $glueService->getCrawler($crawlerName);
```

```
            echo ".";
            sleep(10);
        } while ($crawler['Crawler']['State'] != "READY");
        echo "\n";

    public function getCrawler($crawlerName)
    {
        return $this->customWaiter(function () use ($crawlerName) {
            return $this->glueClient->getCrawler([
                'Name' => $crawlerName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for PHP da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $databaseName = "doc-example-database-$uniqid";

        $database = $glueService->getDatabase($databaseName);
        echo "Found a database named " . $database['Database']['Name'] . "\n";

    public function getDatabase(string $databaseName): Result
    {
        return $this->customWaiter(function () use ($databaseName) {
            return $this->glueClient->getDatabase([
                'Name' => $databaseName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for PHP da API.

Obter uma execução de trabalho

O exemplo de código a seguir mostra como obter uma execução de trabalho do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobName = 'test-job-' . $uniqid;

        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl)['JobRunId'];

        echo "waiting for job";
        do {
            $jobRun = $glueService->getJobRun($jobName, $runId);
            echo ".";
            sleep(10);
        } while (!array_intersect([$jobRun['JobRun']['JobRunState']], ['SUCCEEDED',
'STOPPED', 'FAILED', 'TIMEOUT']));
        echo "\n";

    public function getJobRun($jobName, $runId, $predecessorsIncluded = false):
Result
    {
        return $this->glueClient->getJobRun([
            'JobName' => $jobName,
            'RunId' => $runId,
            'PredecessorsIncluded' => $predecessorsIncluded,
        ]);
    }
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for PHP da API.

Obter execuções de um trabalho

O exemplo de código a seguir mostra como obter execuções de um trabalho do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    $jobName = 'test-job-' . $uniqid;

    $jobRuns = $glueService->getJobRuns($jobName);

public function getJobRuns($jobName, $maxResults = 0, $nextToken = ''): Result
{
    $arguments = ['JobName' => $jobName];
    if ($maxResults) {
        $arguments['MaxResults'] = $maxResults;
    }
    if ($nextToken) {
        $arguments['NextToken'] = $nextToken;
    }
    return $this->glueClient->getJobRuns($arguments);
}
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for PHP da API.

Obter tabelas de um banco de dados

O exemplo de código a seguir mostra como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    $databaseName = "doc-example-database-$uniqid";

    $tables = $glueService->getTables($databaseName);

public function getTables($databaseName): Result
{
    return $this->glueClient->getTables([
        'DatabaseName' => $databaseName,
    ]);
}
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for PHP da API.

Listar definições de trabalho

O exemplo de código a seguir mostra como listas definições de trabalho do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    $jobs = $glueService->listJobs();
    echo "Current jobs:\n";
    foreach ($jobs['JobNames'] as $jobsName) {
        echo "{$jobsName}\n";
    }
```

```
    public function listJobs($maxResults = null, $nextToken = null, $tags = []):
Result
    {
        $arguments = [];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        if (!empty($tags)) {
            $arguments['Tags'] = $tags;
        }
        return $this->glueClient->listJobs($arguments);
    }
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for PHP da API.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $crawlerName = "example-crawler-test-" . $uniqid;

        $databaseName = "doc-example-database-$uniqid";

        $glueService->startCrawler($crawlerName);

    public function startCrawler($crawlerName): Result
    {
        return $this->glueClient->startCrawler([
            'Name' => $crawlerName,
        ]);
```

```
    }
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for PHP da API.

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        $jobName = 'test-job-' . $uniqid;

        $databaseName = "doc-example-database-$uniqid";

        $tables = $glueService->getTables($databaseName);

        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl)['JobRunId'];

   public function startJobRun($jobName, $databaseName, $tables, $outputBucketUrl):
Result
   {
       return $this->glueClient->startJobRun([
           'JobName' => $jobName,
           'Arguments' => [
               'input_database' => $databaseName,
               'input_table' => $tables['TableList'][0]['Name'],
               'output_bucket_url' => $outputBucketUrl,
               '--input_database' => $databaseName,
               '--input_table' => $tables['TableList'][0]['Name'],
               '--output_bucket_url' => $outputBucketUrl,
           ],
       ]);
   }
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for PHP da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Glue;

use Aws\Glue\GlueClient;
use Aws\S3\S3Client;
use AwsUtilities\AWSServiceClass;
use GuzzleHttp\Psr7\Stream;
use Iam\IAMService;

class GettingStartedWithGlue
{
    public function run()
    {
```

```
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the AWS Glue getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();

        $glueClient = new GlueClient($clientArgs);
        $glueService = new GlueService($glueClient);
        $iamService = new IAMService();
        $crawlerName = "example-crawler-test-" . $uniqid;

        AWSServiceClass::$waitTime = 5;
        AWSServiceClass::$maxWaitAttempts = 20;

        $role = $iamService->getRole("AWSGlueServiceRole-DocExample");

        $databaseName = "doc-example-database-$uniqid";
        $path = 's3://crawler-public-us-east-1/flight/2016/csv';
        $glueService->createCrawler($crawlerName, $role['Role']['Arn'],
$databaseName, $path);
        $glueService->startCrawler($crawlerName);

        echo "Waiting for crawler";
        do {
            $crawler = $glueService->getCrawler($crawlerName);
            echo ".";
            sleep(10);
        } while ($crawler['Crawler']['State'] != "READY");
        echo "\n";

        $database = $glueService->getDatabase($databaseName);
        echo "Found a database named " . $database['Database']['Name'] . "\n";

        //Upload job script
        $s3client = new S3Client($clientArgs);
        $bucketName = "test-glue-bucket-" . $uniqid;
        $s3client->createBucket([
            'Bucket' => $bucketName,
```

```
            'CreateBucketConfiguration' => ['LocationConstraint' => 'us-west-2'],
        ]);

        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => 'run_job.py',
            'SourceFile' => __DIR__ . '/flight_etl_job_script.py'
        ]);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => 'setup_scenario_getting_started.yaml',
            'SourceFile' => __DIR__ . '/setup_scenario_getting_started.yaml'
        ]);

        $tables = $glueService->getTables($databaseName);

        $jobName = 'test-job-' . $uniqid;
        $scriptLocation = "s3://$bucketName/run_job.py";
        $job = $glueService->createJob($jobName, $role['Role']['Arn'],
$scriptLocation);

        $outputBucketUrl = "s3://$bucketName";
        $runId = $glueService->startJobRun($jobName, $databaseName, $tables,
$outputBucketUrl)['JobRunId'];

        echo "waiting for job";
        do {
            $jobRun = $glueService->getJobRun($jobName, $runId);
            echo ".";
            sleep(10);
        } while (!array_intersect([$jobRun['JobRun']['JobRunState']], ['SUCCEEDED',
'STOPPED', 'FAILED', 'TIMEOUT']));
        echo "\n";

        $jobRuns = $glueService->getJobRuns($jobName);

        $objects = $s3client->listObjects([
            'Bucket' => $bucketName,
        ])['Contents'];

        foreach ($objects as $object) {
            echo $object['Key'] . "\n";
        }
```

```
        echo "Downloading " . $objects[1]['Key'] . "\n";
        /** @var Stream $downloadObject */
        $downloadObject = $s3client->getObject([
            'Bucket' => $bucketName,
            'Key' => $objects[1]['Key'],
        ])['Body']->getContents();
        echo "Here is the first 1000 characters in the object.";
        echo substr($downloadObject, 0, 1000);

        $jobs = $glueService->listJobs();
        echo "Current jobs:\n";
        foreach ($jobs['JobNames'] as $jobsName) {
            echo "{$jobsName}\n";
        }

        echo "Delete the job.\n";
        $glueClient->deleteJob([
            'JobName' => $job['Name'],
        ]);

        echo "Delete the tables.\n";
        foreach ($tables['TableList'] as $table) {
            $glueService->deleteTable($table['Name'], $databaseName);
        }

        echo "Delete the databases.\n";
        $glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);

        echo "Delete the crawler.\n";
        $glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);

        $deleteObjects = $s3client->listObjectsV2([
            'Bucket' => $bucketName,
        ]);
        echo "Delete all objects in the bucket.\n";
        $deleteObjects = $s3client->deleteObjects([
            'Bucket' => $bucketName,
            'Delete' => [
                'Objects' => $deleteObjects['Contents'],
            ]
```

```
        ]);
        echo "Delete the bucket.\n";
        $s3client->deleteBucket(['Bucket' => $bucketName]);

        echo "This job was brought to you by the number $uniqid\n";
    }
}

namespace Glue;

use Aws\Glue\GlueClient;
use Aws\Result;

use function PHPUnit\Framework\isEmpty;

class GlueService extends \AwsUtilities\AWSServiceClass
{
    protected GlueClient $glueClient;

    public function __construct($glueClient)
    {
        $this->glueClient = $glueClient;
    }

    public function getCrawler($crawlerName)
    {
        return $this->customWaiter(function () use ($crawlerName) {
            return $this->glueClient->getCrawler([
                'Name' => $crawlerName,
            ]);
        });
    }

    public function createCrawler($crawlerName, $role, $databaseName, $path): Result
    {
        return $this->customWaiter(function () use ($crawlerName, $role,
 $databaseName, $path) {
            return $this->glueClient->createCrawler([
                'Name' => $crawlerName,
                'Role' => $role,
                'DatabaseName' => $databaseName,
                'Targets' => [
                    'S3Targets' =>
                        [[
```

```
                            'Path' => $path,
                        ]]
                ],
            ]);
        });
    }

    public function startCrawler($crawlerName): Result
    {
        return $this->glueClient->startCrawler([
            'Name' => $crawlerName,
        ]);
    }

    public function getDatabase(string $databaseName): Result
    {
        return $this->customWaiter(function () use ($databaseName) {
            return $this->glueClient->getDatabase([
                'Name' => $databaseName,
            ]);
        });
    }

    public function getTables($databaseName): Result
    {
        return $this->glueClient->getTables([
            'DatabaseName' => $databaseName,
        ]);
    }

    public function createJob($jobName, $role, $scriptLocation, $pythonVersion =
'3', $glueVersion = '3.0'): Result
    {
        return $this->glueClient->createJob([
            'Name' => $jobName,
            'Role' => $role,
            'Command' => [
                'Name' => 'glueetl',
                'ScriptLocation' => $scriptLocation,
                'PythonVersion' => $pythonVersion,
            ],
            'GlueVersion' => $glueVersion,
        ]);
    }
```

```
    public function startJobRun($jobName, $databaseName, $tables, $outputBucketUrl):
Result
    {
        return $this->glueClient->startJobRun([
            'JobName' => $jobName,
            'Arguments' => [
                'input_database' => $databaseName,
                'input_table' => $tables['TableList'][0]['Name'],
                'output_bucket_url' => $outputBucketUrl,
                '--input_database' => $databaseName,
                '--input_table' => $tables['TableList'][0]['Name'],
                '--output_bucket_url' => $outputBucketUrl,
            ],
        ]);
    }

    public function listJobs($maxResults = null, $nextToken = null, $tags = []):
Result
    {
        $arguments = [];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        if (!empty($tags)) {
            $arguments['Tags'] = $tags;
        }
        return $this->glueClient->listJobs($arguments);
    }

    public function getJobRuns($jobName, $maxResults = 0, $nextToken = ''): Result
    {
        $arguments = ['JobName' => $jobName];
        if ($maxResults) {
            $arguments['MaxResults'] = $maxResults;
        }
        if ($nextToken) {
            $arguments['NextToken'] = $nextToken;
        }
        return $this->glueClient->getJobRuns($arguments);
    }
```

```
    public function getJobRun($jobName, $runId, $predecessorsIncluded = false):
 Result
    {
        return $this->glueClient->getJobRun([
            'JobName' => $jobName,
            'RunId' => $runId,
            'PredecessorsIncluded' => $predecessorsIncluded,
        ]);
    }

    public function deleteJob($jobName)
    {
        return $this->glueClient->deleteJob([
            'JobName' => $jobName,
        ]);
    }

    public function deleteTable($tableName, $databaseName)
    {
        return $this->glueClient->deleteTable([
            'DatabaseName' => $databaseName,
            'Name' => $tableName,
        ]);
    }

    public function deleteDatabase($databaseName)
    {
        return $this->glueClient->deleteDatabase([
            'Name' => $databaseName,
        ]);
    }

    public function deleteCrawler($crawlerName)
    {
        return $this->glueClient->deleteCrawler([
            'Name' => $crawlerName,
        ]);
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

Exemplos do IAM usando SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
echo "Created role: {$assumeRoleRole['RoleName']}\n";

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
```

```
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";

$service->attachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);

    public function attachRolePolicy($roleName, $policyArn)
    {
        return $this->customWaiter(function () use ($roleName, $policyArn) {
            $this->iamClient->attachRolePolicy([
                'PolicyArn' => $policyArn,
                'RoleName' => $roleName,
            ]);
        });
    }
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for PHP da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
```

```
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";

    public function createPolicy(string $policyName, string $policyDocument)
    {
        $result = $this->customWaiter(function () use ($policyName, $policyDocument)
 {
            return $this->iamClient->createPolicy([
                'PolicyName' => $policyName,
                'PolicyDocument' => $policyDocument,
            ]);
        });
        return $result['Policy'];
    }
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for PHP da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
```

```
echo "Created role: {$assumeRoleRole['RoleName']}\n";

    /**
     * @param string $roleName
     * @param string $rolePolicyDocument
     * @return array
     * @throws AwsException
     */
    public function createRole(string $roleName, string $rolePolicyDocument)
    {
        $result = $this->customWaiter(function () use ($roleName,
 $rolePolicyDocument) {
            return $this->iamClient->createRole([
                'AssumeRolePolicyDocument' => $rolePolicyDocument,
                'RoleName' => $roleName,
            ]);
        });
        return $result['Role'];
    }
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for PHP da API.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function createServiceLinkedRole($awsServiceName, $customSuffix = "",
 $description = "")
```

```
    {
        $createServiceLinkedRoleArguments = ['AWSServiceName' => $awsServiceName];
        if ($customSuffix) {
            $createServiceLinkedRoleArguments['CustomSuffix'] = $customSuffix;
        }
        if ($description) {
            $createServiceLinkedRoleArguments['Description'] = $description;
        }
        return $this->iamClient-
>createServiceLinkedRole($createServiceLinkedRoleArguments);
    }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for PHP da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

$user = $service->createUser("iam_demo_user_$uuid");
echo "Created user with the arn: {$user['Arn']}\n";
```

```
    /**
     * @param string $name
     * @return array
     * @throws AwsException
     */
    public function createUser(string $name): array
    {
        $result = $this->iamClient->createUser([
            'UserName' => $name,
        ]);

        return $result['User'];
    }
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for PHP da API.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function getPolicy($policyArn)
    {
        return $this->customWaiter(function () use ($policyArn) {
            return $this->iamClient->getPolicy(['PolicyArn' => $policyArn]);
        });
    }
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for PHP da API.

Obter um perfil

O exemplo de código a seguir mostra como obter um perfil do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function getRole($roleName)
    {
        return $this->customWaiter(function () use ($roleName) {
            return $this->iamClient->getRole(['RoleName' => $roleName]);
        });
    }
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for PHP da API.

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
```

```
$service = new IAMService();

    public function getAccountPasswordPolicy()
    {
        return $this->iamClient->getAccountPasswordPolicy();
    }
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for PHP da API.

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listSAMLProviders()
    {
        return $this->iamClient->listSAMLProviders();
    }
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for PHP.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listGroups($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listGroupsArguments = [];
        if ($pathPrefix) {
            $listGroupsArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listGroupsArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listGroupsArguments["MaxItems"] = $maxItems;
        }

        return $this->iamClient->listGroups($listGroupsArguments);
    }
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for PHP da API.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listRolePolicies($roleName, $marker = "", $maxItems = 0)
    {
        $listRolePoliciesArguments = ['RoleName' => $roleName];
        if ($marker) {
            $listRolePoliciesArguments['Marker'] = $marker;
        }
        if ($maxItems) {
            $listRolePoliciesArguments['MaxItems'] = $maxItems;
        }
        return $this->customWaiter(function () use ($listRolePoliciesArguments) {
            return $this->iamClient->listRolePolicies($listRolePoliciesArguments);
        });
    }
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for PHP da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listPolicies($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listPoliciesArguments = [];
        if ($pathPrefix) {
            $listPoliciesArguments["PathPrefix"] = $pathPrefix;
        }
```

```
        if ($marker) {
            $listPoliciesArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listPoliciesArguments["MaxItems"] = $maxItems;
        }

        return $this->iamClient->listPolicies($listPoliciesArguments);
    }
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for PHP da API.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas do IAM a um perfil do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listAttachedRolePolicies($roleName, $pathPrefix = "", $marker =
 "", $maxItems = 0)
    {
        $listAttachRolePoliciesArguments = ['RoleName' => $roleName];
        if ($pathPrefix) {
            $listAttachRolePoliciesArguments['PathPrefix'] = $pathPrefix;
        }
        if ($marker) {
            $listAttachRolePoliciesArguments['Marker'] = $marker;
        }
        if ($maxItems) {
            $listAttachRolePoliciesArguments['MaxItems'] = $maxItems;
        }
```

```
        return $this->iamClient-
>listAttachedRolePolicies($listAttachRolePoliciesArguments);
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for PHP da API.

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    /**
     * @param string $pathPrefix
     * @param string $marker
     * @param int $maxItems
     * @return Result
     * $roles = $service->listRoles();
     */
    public function listRoles($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listRolesArguments = [];
        if ($pathPrefix) {
            $listRolesArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listRolesArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listRolesArguments["MaxItems"] = $maxItems;
        }
```

```
        return $this->iamClient->listRoles($listRolesArguments);
    }
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for PHP da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para PHP

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$uuid = uniqid();
$service = new IAMService();

    public function listUsers($pathPrefix = "", $marker = "", $maxItems = 0)
    {
        $listUsersArguments = [];
        if ($pathPrefix) {
            $listUsersArguments["PathPrefix"] = $pathPrefix;
        }
        if ($marker) {
            $listUsersArguments["Marker"] = $marker;
        }
        if ($maxItems) {
            $listUsersArguments["MaxItems"] = $maxItems;
        }
```

```
        return $this->iamClient->listUsers($listUsersArguments);
    }
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for PHP da API.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK para PHP

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Iam\Basics;

require 'vendor/autoload.php';

use Aws\Credentials\Credentials;
use Aws\S3\Exception\S3Exception;
use Aws\S3\S3Client;
```

```
use Aws\Sts\StsClient;
use Iam\IAMService;

echo("\n");
echo("--------------------------------------\n");
print("Welcome to the IAM getting started demo using PHP!\n");
echo("--------------------------------------\n");

$uuid = uniqid();
$service = new IAMService();

$user = $service->createUser("iam_demo_user_$uuid");
echo "Created user with the arn: {$user['Arn']}\n";

$key = $service->createAccessKey($user['UserName']);
$assumeRolePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{$user['Arn']}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }";
$assumeRoleRole = $service->createRole("iam_demo_role_$uuid",
 $assumeRolePolicyDocument);
echo "Created role: {$assumeRoleRole['RoleName']}\n";

$listAllBucketsPolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
}";
$listAllBucketsPolicy = $service->createPolicy("iam_demo_policy_$uuid",
 $listAllBucketsPolicyDocument);
echo "Created policy: {$listAllBucketsPolicy['PolicyName']}\n";

$service->attachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);

$inlinePolicyDocument = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
```

```
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"{$assumeRoleRole['Arn']}\"}]
}";
$inlinePolicy = $service->createUserPolicy("iam_demo_inline_policy_$uuid",
 $inlinePolicyDocument, $user['UserName']);
//First, fail to list the buckets with the user
$credentials = new Credentials($key['AccessKeyId'], $key['SecretAccessKey']);
$s3Client = new S3Client(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $credentials]);
try {
    $s3Client->listBuckets([
    ]);
    echo "this should not run";
} catch (S3Exception $exception) {
    echo "successfully failed!\n";
}

$stsClient = new StsClient(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $credentials]);
sleep(10);
$assumedRole = $stsClient->assumeRole([
    'RoleArn' => $assumeRoleRole['Arn'],
    'RoleSessionName' => "DemoAssumeRoleSession_$uuid",
]);
$assumedCredentials = [
    'key' => $assumedRole['Credentials']['AccessKeyId'],
    'secret' => $assumedRole['Credentials']['SecretAccessKey'],
    'token' => $assumedRole['Credentials']['SessionToken'],
];
$s3Client = new S3Client(['region' => 'us-west-2', 'version' => 'latest',
 'credentials' => $assumedCredentials]);
try {
    $s3Client->listBuckets([]);
    echo "this should now run!\n";
} catch (S3Exception $exception) {
    echo "this should now not fail\n";
}

$service->detachRolePolicy($assumeRoleRole['RoleName'],
 $listAllBucketsPolicy['Arn']);
$deletePolicy = $service->deletePolicy($listAllBucketsPolicy['Arn']);
echo "Delete policy: {$listAllBucketsPolicy['PolicyName']}\n";
$deletedRole = $service->deleteRole($assumeRoleRole['Arn']);
```

```
echo "Deleted role: {$assumeRoleRole['RoleName']}\n";
$deletedKey = $service->deleteAccessKey($key['AccessKeyId'], $user['UserName']);
$deletedUser = $service->deleteUser($user['UserName']);
echo "Delete user: {$user['UserName']}\n";
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos do Kinesis usando SDK for PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Kinesis\KinesisHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler extends KinesisHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
```

```
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handleKinesis(KinesisEvent $event, Context $context): void
    {
        $this->logger->info("Processing records");
        $records = $event->getRecords();
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                throw $e;
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando PHP.

```php
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $kinesisEvent = new KinesisEvent($event);
        $this->logger->info("Processing records");
        $records = $kinesisEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getSequenceNumber();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");
```

```
        // change format for the response
        $failures = array_map(
            fn(string $sequenceNumber) => ['itemIdentifier' => $sequenceNumber],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Exemplos de código do Lambda usando SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function createFunction($functionName, $role, $bucketName, $handler)
    {
        //This assumes the Lambda function is in an S3 bucket.
        return $this->customWaiter(function () use ($functionName, $role,
$bucketName, $handler) {
            return $this->lambdaClient->createFunction([
                'Code' => [
                    'S3Bucket' => $bucketName,
                    'S3Key' => $functionName,
                ],
                'FunctionName' => $functionName,
                'Role' => $role['Arn'],
                'Runtime' => 'python3.9',
                'Handler' => "$handler.lambda_handler",
            ]);
        });
    }
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for PHP da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function deleteFunction($functionName)
{
    return $this->lambdaClient->deleteFunction([
        'FunctionName' => $functionName,
    ]);
}
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for PHP da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function getFunction($functionName)
{
    return $this->lambdaClient->getFunction([
        'FunctionName' => $functionName,
    ]);
}
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for PHP da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function invoke($functionName, $params, $logType = 'None')
{
    return $this->lambdaClient->invoke([
        'FunctionName' => $functionName,
        'Payload' => json_encode($params),
        'LogType' => $logType,
    ]);
}
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for PHP.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public function listFunctions($maxItems = 50, $marker = null)
{
    if (is_null($marker)) {
        return $this->lambdaClient->listFunctions([
```

```
                'MaxItems' => $maxItems,
            ]);
        }

        return $this->lambdaClient->listFunctions([
            'Marker' => $marker,
            'MaxItems' => $maxItems,
        ]);
    }
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for PHP da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public function updateFunctionCode($functionName, $s3Bucket, $s3Key)
    {
        return $this->lambdaClient->updateFunctionCode([
            'FunctionName' => $functionName,
            'S3Bucket' => $s3Bucket,
            'S3Key' => $s3Key,
        ]);
    }
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for PHP da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public function updateFunctionConfiguration($functionName, $handler,
$environment = '')
   {
       return $this->lambdaClient->updateFunctionConfiguration([
           'FunctionName' => $functionName,
           'Handler' => "$handler.lambda_handler",
           'Environment' => $environment,
       ]);
   }
```

- Para obter detalhes da API, consulte UpdateFunctionConfiguration a Referência AWS SDK for PHP da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
namespace Lambda;

use Aws\S3\S3Client;
use GuzzleHttp\Psr7\Stream;
use Iam\IAMService;

class GettingStartedWithLambda
{
    public function run()
    {
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the AWS Lambda getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $clientArgs = [
            'region' => 'us-west-2',
            'version' => 'latest',
            'profile' => 'default',
        ];
        $uniqid = uniqid();

        $iamService = new IAMService();
        $s3client = new S3Client($clientArgs);
        $lambdaService = new LambdaService();

        echo "First, let's create a role to run our Lambda code.\n";
        $roleName = "test-lambda-role-$uniqid";
        $rolePolicyDocument = "{
            \"Version\": \"2012-10-17\",
            \"Statement\": [
                {
                    \"Effect\": \"Allow\",
                    \"Principal\": {
```

```
                        \"Service\": \"lambda.amazonaws.com\"
                    },
                    \"Action\": \"sts:AssumeRole\"
                }
            ]
        }";
        $role = $iamService->createRole($roleName, $rolePolicyDocument);
        echo "Created role {$role['RoleName']}.\n";

        $iamService->attachRolePolicy(
            $role['RoleName'],
            "arn:aws:iam::aws:policy/service-role/AWSLambdaBasicExecutionRole"
        );
        echo "Attached the AWSLambdaBasicExecutionRole to {$role['RoleName']}.\n";

        echo "\nNow let's create an S3 bucket and upload our Lambda code there.\n";
        $bucketName = "test-example-bucket-$uniqid";
        $s3client->createBucket([
            'Bucket' => $bucketName,
        ]);
        echo "Created bucket $bucketName.\n";

        $functionName = "doc_example_lambda_$uniqid";
        $codeBasic = __DIR__ . "/lambda_handler_basic.zip";
        $handler = "lambda_handler_basic";
        $file = file_get_contents($codeBasic);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => $functionName,
            'Body' => $file,
        ]);
        echo "Uploaded the Lambda code.\n";

        $createLambdaFunction = $lambdaService->createFunction($functionName, $role,
 $bucketName, $handler);
        // Wait until the function has finished being created.
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
        } while ($getLambdaFunction['Configuration']['State'] == "Pending");
        echo "Created Lambda function {$getLambdaFunction['Configuration']
['FunctionName']}.\n";

        sleep(1);
```

```
        echo "\nOk, let's invoke that Lambda code.\n";
        $basicParams = [
            'action' => 'increment',
            'number' => 3,
        ];
        /** @var Stream $invokeFunction */
        $invokeFunction = $lambdaService->invoke($functionName, $basicParams)
['Payload'];
        $result = json_decode($invokeFunction->getContents())->result;
        echo "After invoking the Lambda code with the input of
 {$basicParams['number']} we received $result.\n";

        echo "\nSince that's working, let's update the Lambda code.\n";
        $codeCalculator = "lambda_handler_calculator.zip";
        $handlerCalculator = "lambda_handler_calculator";
        echo "First, put the new code into the S3 bucket.\n";
        $file = file_get_contents($codeCalculator);
        $s3client->putObject([
            'Bucket' => $bucketName,
            'Key' => $functionName,
            'Body' => $file,
        ]);
        echo "New code uploaded.\n";

        $lambdaService->updateFunctionCode($functionName, $bucketName,
 $functionName);
        // Wait for the Lambda code to finish updating.
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
        } while ($getLambdaFunction['Configuration']['LastUpdateStatus'] !==
 "Successful");
        echo "New Lambda code uploaded.\n";

        $environment = [
            'Variable' => ['Variables' => ['LOG_LEVEL' => 'DEBUG']],
        ];
        $lambdaService->updateFunctionConfiguration($functionName,
 $handlerCalculator, $environment);
        do {
            $getLambdaFunction = $lambdaService-
>getFunction($createLambdaFunction['FunctionName']);
```

```
        } while ($getLambdaFunction['Configuration']['LastUpdateStatus'] !==
"Successful");
        echo "Lambda code updated with new handler and a LOG_LEVEL of DEBUG for more
information.\n";

        echo "Invoke the new code with some new data.\n";
        $calculatorParams = [
            'action' => 'plus',
            'x' => 5,
            'y' => 4,
        ];
        $invokeFunction = $lambdaService->invoke($functionName, $calculatorParams,
"Tail");
        $result = json_decode($invokeFunction['Payload']->getContents())->result;
        echo "Indeed, {$calculatorParams['x']} + {$calculatorParams['y']} does equal
$result.\n";
        echo "Here's the extra debug info: ";
        echo base64_decode($invokeFunction['LogResult']) . "\n";

        echo "\nBut what happens if you try to divide by zero?\n";
        $divZeroParams = [
            'action' => 'divide',
            'x' => 5,
            'y' => 0,
        ];
        $invokeFunction = $lambdaService->invoke($functionName, $divZeroParams,
"Tail");
        $result = json_decode($invokeFunction['Payload']->getContents())->result;
        echo "You get a |$result| result.\n";
        echo "And an error message: ";
        echo base64_decode($invokeFunction['LogResult']) . "\n";

        echo "\nHere's all the Lambda functions you have in this Region:\n";
        $listLambdaFunctions = $lambdaService->listFunctions(5);
        $allLambdaFunctions = $listLambdaFunctions['Functions'];
        $next = $listLambdaFunctions->get('NextMarker');
        while ($next != false) {
            $listLambdaFunctions = $lambdaService->listFunctions(5, $next);
            $next = $listLambdaFunctions->get('NextMarker');
            $allLambdaFunctions = array_merge($allLambdaFunctions,
$listLambdaFunctions['Functions']);
        }
        foreach ($allLambdaFunctions as $function) {
            echo "{$function['FunctionName']}\n";
```

```
        }

        echo "\n\nAnd don't forget to clean up your data!\n";

        $lambdaService->deleteFunction($functionName);
        echo "Deleted Lambda function.\n";
        $iamService->deleteRole($role['RoleName']);
        echo "Deleted Role.\n";
        $deleteObjects = $s3client->listObjectsV2([
            'Bucket' => $bucketName,
        ]);
        $deleteObjects = $s3client->deleteObjects([
            'Bucket' => $bucketName,
            'Delete' => [
                'Objects' => $deleteObjects['Contents'],
            ]
        ]);
        echo "Deleted all objects from the S3 bucket.\n";
        $s3client->deleteBucket(['Bucket' => $bucketName]);
        echo "Deleted the bucket.\n";
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Kinesis\KinesisHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler extends KinesisHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handleKinesis(KinesisEvent $event, Context $context): void
```

```
    {
        $this->logger->info("Processing records");
        $records = $event->getRecords();
        foreach ($records as $record) {
            try {
                $data = $record->getData();
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                throw $e;
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando PHP.

```
<?php

/*
```

```
Since native PHP support for AWS Lambda is not available, we are utilizing Bref's
 PHP functions runtime for AWS Lambda.
For more information on Bref's PHP runtime for Lambda, refer to: https://bref.sh/
docs/runtimes/function

Another approach would be to create a custom runtime.
A practical example can be found here: https://aws.amazon.com/blogs/apn/aws-lambda-
custom-runtime-for-php-a-practical-example/
*/

// Additional composer packages may be required when using Bref or any other PHP
 functions runtime.
// require __DIR__ . '/vendor/autoload.php';

return function ($event, $context) {
    foreach ($event["Records"] as $record) {
        processMessage($record);
    }
    echo "Done!" . PHP_EOL;
};

function processMessage($record)
{
    try {
        $message = $record['Sns']['Message'];
        echo "Processed Message: {$message}" . PHP_EOL;
    } catch (Exception $e) {
        echo "Error occured: {$e->getMessage()}" . PHP_EOL;
        throw $e;
    }
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do Kinesis com o Lambda usando PHP.

```
<?php

# using bref/bref and bref/logger for simplicity

use Bref\Context\Context;
use Bref\Event\Kinesis\KinesisEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $kinesisEvent = new KinesisEvent($event);
        $this->logger->info("Processing records");
        $records = $kinesisEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                $data = $record->getData();
```

```
                $this->logger->info(json_encode($data));
                // TODO: Do interesting work based on the new data
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getSequenceNumber();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords records");

        // change format for the response
        $failures = array_map(
            fn(string $sequenceNumber) => ['itemIdentifier' => $sequenceNumber],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando PHP.

```
<?php

use Bref\Context\Context;
use Bref\Event\Sqs\SqsEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $sqsEvent = new SqsEvent($event);
        $this->logger->info("Processing SQS records");
        $records = $sqsEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                // Assuming the SQS message is in JSON format
                $message = json_decode($record->getBody(), true);
                $this->logger->info(json_encode($message));
                // TODO: Implement your custom processing logic here
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getMessageId();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords SQS records");
```

```
        // Format failures for the response
        $failures = array_map(
            fn(string $messageId) => ['itemIdentifier' => $messageId],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);

?>
```

Exemplos do Amazon RDS usando SDK for PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma instância de banco de dados

O exemplo de código a seguir mostra como criar uma instância do Amazon RDS DB e aguardar até que se torne disponível.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;



$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

$dbIdentifier = '<<{{db-identifier}}>>';
$dbClass = 'db.t2.micro';
$storage = 5;
$engine = 'MySQL';
$username = 'MyUser';
$password = 'MyPassword';

try {
    $result = $rdsClient->createDBInstance([
        'DBInstanceIdentifier' => $dbIdentifier,
        'DBInstanceClass' => $dbClass,
        'AllocatedStorage' => $storage,
        'Engine' => $engine,
        'MasterUsername' => $username,
        'MasterUserPassword' => $password,
    ]);
    var_dump($result);
```

```
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK for PHP.

Criar um snapshot de uma instância de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de uma instância do Amazon RDS DB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;



$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

$dbIdentifier = '<<{{db-identifier}}>>';
$snapshotName = '<<{{backup_2018_12_25}}>>';

try {
    $result = $rdsClient->createDBSnapshot([
        'DBInstanceIdentifier' => $dbIdentifier,
        'DBSnapshotIdentifier' => $snapshotName,
```

```
    ]);
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for PHP.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Amazon RDS DB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;


//Create an RDSClient
$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-1'
]);

$dbIdentifier = '<<{{db-identifier}}>>';

try {
    $result = $rdsClient->deleteDBInstance([
        'DBInstanceIdentifier' => $dbIdentifier,
    ]);
```

```
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK for PHP.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Amazon RDS DB.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require __DIR__ . '/vendor/autoload.php';

use Aws\Exception\AwsException;


//Create an RDSClient
$rdsClient = new Aws\Rds\RdsClient([
    'region' => 'us-east-2'
]);

try {
    $result = $rdsClient->describeDBInstances();
    foreach ($result['DBInstances'] as $instance) {
        print('<p>DB Identifier: ' . $instance['DBInstanceIdentifier']);
        print('<br />Endpoint: ' . $instance['Endpoint']["Address"]
            . ':' . $instance['Endpoint']["Port"]);
        print('<br />Current Status: ' . $instance["DBInstanceStatus"]);
```

```
        print('</p>');
    }
    print(" Raw Result ");
    var_dump($result);
} catch (AwsException $e) {
    echo $e->getMessage();
    echo "\n";
}
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for PHP.

Exemplos de código do Amazon S3 usando SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for PHP com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use Aws\S3\S3Client;

$client = new S3Client(['region' => 'us-west-2']);
$results = $client->listBuckets();
var_dump($results);
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for PHP da API.

Tópicos

- Ações
- Cenários

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cópia simples de um objeto.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $folder = "copied-folder";
            $this->s3client->copyObject([
                'Bucket' => $this->bucketName,
                'CopySource' => "$this->bucketName/$fileName",
                'Key' => "$folder/$fileName-copy",
            ]);
            echo "Copied $fileName to $folder/$fileName-copy.\n";
        } catch (Exception $exception) {
```

```
            echo "Failed to copy $fileName with error: " . $exception->getMessage();
            exit("Please fix error with object copying before continuing.");
        }
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for PHP da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $this->s3client->createBucket([
                'Bucket' => $this->bucketName,
                'CreateBucketConfiguration' => ['LocationConstraint' => $region],
            ]);
            echo "Created bucket named: $this->bucketName \n";
        } catch (Exception $exception) {
            echo "Failed to create bucket $this->bucketName with error: " .
$exception->getMessage();
            exit("Please fix error with bucket creation before continuing.");
        }
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for PHP da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um bucket vazio.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $this->s3client->deleteBucket([
                'Bucket' => $this->bucketName,
            ]);
            echo "Deleted bucket $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $this->bucketName with error: " . $exception-
>getMessage();
            exit("Please fix error with bucket deletion before continuing.");
        }
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for PHP da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um conjunto de objetos de uma lista de chaves.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);
```

```
        try {
            $objects = [];
            foreach ($contents['Contents'] as $content) {
                $objects[] = [
                    'Key' => $content['Key'],
                ];
            }
            $this->s3client->deleteObjects([
                'Bucket' => $this->bucketName,
                'Delete' => [
                    'Objects' => $objects,
                ],
            ]);
            $check = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            if (count($check) <= 0) {
                throw new Exception("Bucket wasn't empty.");
            }
            echo "Deleted all objects and folders from $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $fileName from $this->bucketName with error: " .
$exception->getMessage();
            exit("Please fix error with object deletion before continuing.");
        }
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for PHP da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um objeto.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $file = $this->s3client->getObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
            ]);
            $body = $file->get('Body');
            $body->rewind();
            echo "Downloaded the file and it begins with: {$body->read(26)}.\n";
        } catch (Exception $exception) {
            echo "Failed to download $fileName from $this->bucketName with error:
" . $exception->getMessage();
            exit("Please fix error with file downloading before continuing.");
        }
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for PHP da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste objetos em um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        try {
            $contents = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
```

```
            echo "The contents of your bucket are: \n";
            foreach ($contents['Contents'] as $content) {
                echo $content['Key'] . "\n";
            }
        } catch (Exception $exception) {
            echo "Failed to list objects in $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with listing objects before continuing.");
        }
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for PHP da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um objeto em um bucket.

```
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);

        $fileName = __DIR__ . "/local-file-" . uniqid();
        try {
            $this->s3client->putObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
                'SourceFile' => __DIR__ . '/testfile.txt'
            ]);
            echo "Uploaded $fileName to $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to upload $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with file upload before continuing.");
        }
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for PHP da API.

Cenários

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK para PHP

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
        echo("\n");
        echo("--------------------------------------\n");
        print("Welcome to the Amazon S3 getting started demo using PHP!\n");
        echo("--------------------------------------\n");

        $region = 'us-west-2';

        $this->s3client = new S3Client([
                'region' => $region,
        ]);
        /* Inline declaration example
        $s3client = new Aws\S3\S3Client(['region' => 'us-west-2']);
        */

        $this->bucketName = "doc-example-bucket-" . uniqid();
```

```
        try {
            $this->s3client->createBucket([
                'Bucket' => $this->bucketName,
                'CreateBucketConfiguration' => ['LocationConstraint' => $region],
            ]);
            echo "Created bucket named: $this->bucketName \n";
        } catch (Exception $exception) {
            echo "Failed to create bucket $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with bucket creation before continuing.");
        }

        $fileName = __DIR__ . "/local-file-" . uniqid();
        try {
            $this->s3client->putObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
                'SourceFile' => __DIR__ . '/testfile.txt'
            ]);
            echo "Uploaded $fileName to $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to upload $fileName with error: " . $exception-
>getMessage();
            exit("Please fix error with file upload before continuing.");
        }

        try {
            $file = $this->s3client->getObject([
                'Bucket' => $this->bucketName,
                'Key' => $fileName,
            ]);
            $body = $file->get('Body');
            $body->rewind();
            echo "Downloaded the file and it begins with: {$body->read(26)}.\n";
        } catch (Exception $exception) {
            echo "Failed to download $fileName from $this->bucketName with error:
 " . $exception->getMessage();
            exit("Please fix error with file downloading before continuing.");
        }

        try {
            $folder = "copied-folder";
            $this->s3client->copyObject([
```

```
                'Bucket' => $this->bucketName,
                'CopySource' => "$this->bucketName/$fileName",
                'Key' => "$folder/$fileName-copy",
            ]);
            echo "Copied $fileName to $folder/$fileName-copy.\n";
        } catch (Exception $exception) {
            echo "Failed to copy $fileName with error: " . $exception->getMessage();
            exit("Please fix error with object copying before continuing.");
        }

        try {
            $contents = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            echo "The contents of your bucket are: \n";
            foreach ($contents['Contents'] as $content) {
                echo $content['Key'] . "\n";
            }
        } catch (Exception $exception) {
            echo "Failed to list objects in $this->bucketName with error: " .
$exception->getMessage();
            exit("Please fix error with listing objects before continuing.");
        }

        try {
            $objects = [];
            foreach ($contents['Contents'] as $content) {
                $objects[] = [
                    'Key' => $content['Key'],
                ];
            }
            $this->s3client->deleteObjects([
                'Bucket' => $this->bucketName,
                'Delete' => [
                    'Objects' => $objects,
                ],
            ]);
            $check = $this->s3client->listObjectsV2([
                'Bucket' => $this->bucketName,
            ]);
            if (count($check) <= 0) {
                throw new Exception("Bucket wasn't empty.");
            }
            echo "Deleted all objects and folders from $this->bucketName.\n";
```

```
        } catch (Exception $exception) {
            echo "Failed to delete $fileName from $this->bucketName with error: " .
 $exception->getMessage();
            exit("Please fix error with object deletion before continuing.");
        }

        try {
            $this->s3client->deleteBucket([
                'Bucket' => $this->bucketName,
            ]);
            echo "Deleted bucket $this->bucketName.\n";
        } catch (Exception $exception) {
            echo "Failed to delete $this->bucketName with error: " . $exception-
>getMessage();
            exit("Please fix error with bucket deletion before continuing.");
        }

        echo "Successfully ran the Amazon S3 with PHP demo.\n";
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for PHP.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Exemplos de código para o Amazon SNS usando SDK para PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Verificar se um número de telefone saiu

O exemplo de código a seguir mostra como verificar se um número de telefone cancelou o recebimento de mensagens do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Indicates whether the phone number owner has opted out of receiving SMS messages
 from your AWS SNS account.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
```

```
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$phone = '+1XXX5550100';

try {
    $result = $SnSclient->checkIfPhoneNumberIsOptedOut([
        'phoneNumber' => $phone,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte CheckIfPhoneNumberIsOptedOuta Referência AWS SDK for PHP da API.

Confirmar que um proprietário de endpoint deseja receber mensagens

O exemplo de código a seguir mostra como confirmar que o proprietário de um endpoint deseja receber mensagens do Amazon SNS validando o token enviado para o endpoint por uma ação Subscribe anterior.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
```

```
use Aws\Sns\SnsClient;


/**
 * Verifies an endpoint owner's intent to receive messages by
 * validating the token sent to the endpoint by an earlier Subscribe action.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$subscription_token = 'arn:aws:sns:us-east-1:111122223333:MyTopic:123456-
abcd-12ab-1234-12ba3dc1234a';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->confirmSubscription([
        'Token' => $subscription_token,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ConfirmSubscriptiona Referência AWS SDK for PHP da API.

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Create a Simple Notification Service topics in your AWS account at the requested
 region.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$topicname = 'myTopic';

try {
    $result = $SnSclient->createTopic([
        'Name' => $topicname,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for PHP da API.

Excluir uma assinatura

O exemplo de código a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Deletes a subscription to an Amazon SNS topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$subscription = 'arn:aws:sns:us-east-1:111122223333:MySubscription';

try {
    $result = $SnSclient->unsubscribe([
        'SubscriptionArn' => $subscription,
    ]);
    var_dump($result);
```

```
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for PHP.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Deletes an SNS topic and all its subscriptions.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);
```

```
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->deleteTopic([
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte DeleteTopica Referência AWS SDK for PHP da API.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->getTopicAttributes([
        'TopicArn' => $topic,
    ]);
    var_dump($result);
```

```
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte GetTopicAttributesa Referência AWS SDK for PHP da API.

Obter as configurações para enviar mensagens SMS

O exemplo de código a seguir mostra como obter as configurações para enviar mensagens SMS do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Get the type of SMS Message sent by default from the AWS SNS service.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);
```

```
try {
    $result = $SnSclient->getSMSAttributes([
        'attributes' => ['DefaultSMSType'],
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte GetSMSAttributes na Referência da API do AWS SDK for PHP.

Listar números de telefone que saíram

O exemplo de código a seguir mostra como listar números de telefone que optaram por não receber mensagens do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Returns a list of phone numbers that are opted out of receiving SMS messages from
 your AWS SNS account.
 *
 * This code expects that you have AWS credentials set up per:
```

```
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listPhoneNumbersOptedOut();
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte ListPhoneNumbersOptedOuta Referência AWS SDK for PHP da API.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;
```

```
/**
 * Returns a list of Amazon SNS subscriptions in the requested region.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listSubscriptions();
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for PHP da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;
```

```
/**
 * Returns a list of the requester's topics from your AWS SNS account in the region
 specified.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->listTopics();
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for PHP da API.

Publicar uma mensagem de texto SMS

O exemplo de código a seguir mostra como publicar mensagens SMS usando o Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';
```

```
use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Sends a text message (SMS message) directly to a phone number using Amazon SNS.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$message = 'This message is sent from a Amazon SNS code sample.';
$phone = '+1XXX5550100';

try {
    $result = $SnSclient->publish([
        'Message' => $message,
        'PhoneNumber' => $phone,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for PHP.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Sends a message to an Amazon SNS topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$message = 'This message is sent from a Amazon SNS code sample.';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->publish([
        'Message' => $message,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for PHP.

Definir as configurações padrão para enviar mensagens SMS

O exemplo de código a seguir mostra como definir as configurações padrão para enviar mensagens SMS usando o Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

try {
    $result = $SnSclient->SetSMSAttributes([
        'attributes' => [
            'DefaultSMSType' => 'Transactional',
        ],
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for PHP.
- Para receber detalhes da API, consulte SetSMSAttributes na Referência da API do AWS SDK for PHP.

Definir atributos de tópicos

O exemplo de código a seguir mostra como definir atributos para um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Configure the message delivery status attributes for an Amazon SNS Topic.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);
$attribute = 'Policy | DisplayName | DeliveryPolicy';
$value = 'First Topic';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->setTopicAttributes([
        'AttributeName' => $attribute,
        'AttributeValue' => $value,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
```

```
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for PHP da API.

Inscrever um endpoint HTTP em um tópico

O exemplo de código a seguir mostra como inscrever um endpoint HTTP ou HTTPS para receber notificações de um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Prepares to subscribe an endpoint by sending the endpoint a confirmation message.
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$protocol = 'https';
```

```
$endpoint = 'https://';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->subscribe([
        'Protocol' => $protocol,
        'Endpoint' => $endpoint,
        'ReturnSubscriptionArn' => true,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for PHP.

Inscrever um endereço de e-mail em um tópico

O exemplo do código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require 'vendor/autoload.php';

use Aws\Exception\AwsException;
use Aws\Sns\SnsClient;


/**
 * Prepares to subscribe an endpoint by sending the endpoint a confirmation message.
```

```
 *
 * This code expects that you have AWS credentials set up per:
 * https://docs.aws.amazon.com/sdk-for-php/v3/developer-guide/guide_credentials.html
 */

$SnSclient = new SnsClient([
    'profile' => 'default',
    'region' => 'us-east-1',
    'version' => '2010-03-31'
]);

$protocol = 'email';
$endpoint = 'sample@example.com';
$topic = 'arn:aws:sns:us-east-1:111122223333:MyTopic';

try {
    $result = $SnSclient->subscribe([
        'Protocol' => $protocol,
        'Endpoint' => $endpoint,
        'ReturnSubscriptionArn' => true,
        'TopicArn' => $topic,
    ]);
    var_dump($result);
} catch (AwsException $e) {
    // output error message if fails
    error_log($e->getMessage());
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for PHP.

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando PHP.

```
<?php

/*
Since native PHP support for AWS Lambda is not available, we are utilizing Bref's
 PHP functions runtime for AWS Lambda.
For more information on Bref's PHP runtime for Lambda, refer to: https://bref.sh/
docs/runtimes/function

Another approach would be to create a custom runtime.
A practical example can be found here: https://aws.amazon.com/blogs/apn/aws-lambda-
custom-runtime-for-php-a-practical-example/
*/

// Additional composer packages may be required when using Bref or any other PHP
 functions runtime.
// require __DIR__ . '/vendor/autoload.php';

return function ($event, $context) {
    foreach ($event["Records"] as $record) {
        processMessage($record);
    }
    echo "Done!" . PHP_EOL;
};

function processMessage($record)
{
    try {
        $message = $record['Sns']['Message'];
        echo "Processed Message: {$message}" . PHP_EOL;
    } catch (Exception $e) {
        echo "Error occured: {$e->getMessage()}" . PHP_EOL;
        throw $e;
    }
```

```
}
```

Exemplos do Amazon SQS usando SDK for PHP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for PHP com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Exemplos sem servidor

Exemplos sem servidor

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para PHP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatando falhas de itens em lote do SQS com o Lambda usando PHP.

```
<?php
```

```
use Bref\Context\Context;
use Bref\Event\Sqs\SqsEvent;
use Bref\Event\Handler as StdHandler;
use Bref\Logger\StderrLogger;

require __DIR__ . '/vendor/autoload.php';

class Handler implements StdHandler
{
    private StderrLogger $logger;
    public function __construct(StderrLogger $logger)
    {
        $this->logger = $logger;
    }

    /**
     * @throws JsonException
     * @throws \Bref\Event\InvalidLambdaEvent
     */
    public function handle(mixed $event, Context $context): array
    {
        $sqsEvent = new SqsEvent($event);
        $this->logger->info("Processing SQS records");
        $records = $sqsEvent->getRecords();

        $failedRecords = [];
        foreach ($records as $record) {
            try {
                // Assuming the SQS message is in JSON format
                $message = json_decode($record->getBody(), true);
                $this->logger->info(json_encode($message));
                // TODO: Implement your custom processing logic here
            } catch (Exception $e) {
                $this->logger->error($e->getMessage());
                // failed processing the record
                $failedRecords[] = $record->getMessageId();
            }
        }
        $totalRecords = count($records);
        $this->logger->info("Successfully processed $totalRecords SQS records");

        // Format failures for the response
        $failures = array_map(
```

```
            fn(string $messageId) => ['itemIdentifier' => $messageId],
            $failedRecords
        );

        return [
            'batchItemFailures' => $failures
        ];
    }
}

$logger = new StderrLogger();
return new Handler($logger);

?>
```

Exemplos para entre serviços usando SDK para PHP

Os aplicativos de exemplo a seguir usam o AWS SDK for PHP para trabalhar em vários Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK para PHP

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK para PHP

Mostra como usar o AWS SDK for PHP para construir uma aplicação Web que monitora itens de trabalho no banco de dados do Amazon RDS e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa um front-end construído com React.js para interagir com um back-end PHP RESTful.

- Integre uma aplicação Web React.js com os serviços da AWS.
- Liste, adicione, atualize e exclua itens em uma tabela do Amazon RDS.
- Envie um relatório por e-mail dos itens de trabalho filtrados usando o Amazon SES.
- Implante e gerencie recursos de exemplo com o script do AWS CloudFormation incluído.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Exemplos de código para o SDK para Python (Boto3)

Os exemplos a seguir mostram como usar o AWS SDK for Python (Boto3) com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para Python (Boto3) : Saiba mais sobre como usar o Python com o AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Python (Boto3)
- Exemplos de serviços cruzados usando o SDK para Python (Boto3)

Ações e cenários usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK for Python (Boto3) com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de ACM usando o SDK para Python (Boto3)
- Exemplos de API Gateway usando o SDK para Python (Boto3)
- Exemplos do Application Recovery Controller usando o SDK para Python (Boto3)
- Exemplos do Audit Manager usando o SDK para Python (Boto3)
- Exemplos de Aurora usando o SDK para Python (Boto3)
- Exemplos de Auto Scaling usando o SDK para Python (Boto3)
- Exemplos do Amazon Bedrock usando o SDK para Python (Boto3)
- Exemplos do Amazon Bedrock Runtime usando o SDK para Python (Boto3)
- Exemplos de agentes para Amazon Bedrock usando SDK para Python (Boto3)
- Exemplos de agentes para Amazon Bedrock Runtime usando SDK para Python (Boto3)
- CloudFront exemplos usando SDK para Python (Boto3)
- CloudWatch exemplos usando SDK para Python (Boto3)
- CloudWatch Exemplos de registros usando o SDK para Python (Boto3)
- Exemplos de código do Provedor de Identidades Amazon Cognito usando SDK para Python (Boto3)
- Exemplos do Amazon Comprehend usando o SDK para Python (Boto3)
- Exemplos de AWS Config usando o SDK para Python (Boto3)
- Exemplos de Device Farm usando o SDK para Python (Boto3)
- Exemplos de DynamoDB usando o SDK para Python (Boto3)
- Exemplos do Amazon EC2 usando o SDK para Python (Boto3)
- Exemplos de Elastic Load Balancing usando o SDK para Python (Boto3)
- Exemplos do Amazon EMR usando o SDK para Python (Boto3)
- Exemplos de AWS Glue usando o SDK para Python (Boto3)
- HealthImaging exemplos usando SDK para Python (Boto3)
- Exemplos de IAM usando o SDK para Python (Boto3)
- Exemplos do Amazon Keyspaces usando o SDK para Python (Boto3)
- Exemplos do Kinesis usando o SDK para Python (Boto3)
- Exemplos de AWS KMS usando o SDK para Python (Boto3)
- Exemplos de Lambda usando o SDK para Python (Boto3)
- Exemplos do Lookout for Vision usando o SDK para Python (Boto3)

- Exemplos de Serviço gerenciado para Apache Flink usando SDK para Python (Boto3)
- Exemplos de Organizações usando o SDK para Python (Boto3)
- Exemplos do Amazon Pinpoint usando o SDK para Python (Boto3)
- Exemplos do Amazon Pinpoint SMS e API de voz usando o SDK para Python (Boto3)
- Exemplos do Amazon Polly usando o SDK para Python (Boto3)
- Exemplos do Amazon RDS usando o SDK para Python (Boto3)
- Exemplos do Amazon Rekognition usando o SDK para Python (Boto3)
- Exemplos do Amazon S3 usando o SDK para Python (Boto3)
- Exemplos do S3 Glacier usando o SDK para Python (Boto3).
- Exemplos do Secrets Manager usando o SDK para Python (Boto3)
- Exemplos do Amazon SES usando o SDK para Python (Boto3)
- Exemplos do Amazon SNS usando o SDK para Python (Boto3)
- Exemplos do Amazon SQS usando o SDK para Python (Boto3)
- Exemplos do Step Functions usando o SDK para Python (Boto3)
- Exemplos de AWS STS usando o SDK para Python (Boto3)
- Exemplos de AWS Support usando o SDK para Python (Boto3)
- Exemplos do Amazon Textract usando o SDK para Python (Boto3)
- Exemplos do Amazon Transcribe usando o SDK para Python (Boto3)

Exemplos de ACM usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o ACM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar tags a um certificado

O exemplo de código a seguir mostra como adicionar tags aos certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def add_tags(self, certificate_arn, tags):
        """
        Adds tags to a certificate. Tags are key-value pairs that contain custom
        metadata.

        :param certificate_arn: The ARN of the certificate.
        :param tags: A dictionary of key-value tags to add to the certificate.
        """
        try:
            self.acm_client.add_tags_to_certificate(
                CertificateArn=certificate_arn,
                Tags=[{"Key": key, "Value": value} for key, value in tags.items()],
```

```
            )
            logger.info("Added %s tags to certificate %s.", len(tags),
 certificate_arn)
        except ClientError:
            logger.exception("Couldn't add tags to certificate %s.",
 certificate_arn)
            raise
```

- Para obter detalhes da API, consulte a AddTagsToCertificateReferência da API AWSSDK for Python (Boto3).

Excluir um certificado

O exemplo de código a seguir mostra como excluir certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def remove(self, certificate_arn):
        """
        Removes a certificate.

        :param certificate_arn: The ARN of the certificate to remove.
```

```
        """
        try:
            self.acm_client.delete_certificate(CertificateArn=certificate_arn)
            logger.info("Removed certificate %s.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't remove certificate %s.", certificate_arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteCertificateReferência da API AWSSDK for Python (Boto3).

Descrever um certificado

Os exemplos de código a seguir mostram como descrever certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def describe(self, certificate_arn):
        """
        Gets certificate metadata.

        :param certificate_arn: The Amazon Resource Name (ARN) of the certificate.
```

```
        :return: Metadata about the certificate.
        """
        try:
            response = self.acm_client.describe_certificate(
                CertificateArn=certificate_arn
            )
            certificate = response["Certificate"]
            logger.info(
                "Got metadata for certificate for domain %s.",
certificate["DomainName"]
            )
        except ClientError:
            logger.exception("Couldn't get data for certificate %s.",
certificate_arn)
            raise
        else:
            return certificate
```

- Para obter detalhes da API, consulte a DescribeCertificateReferência da API AWSSDK for Python (Boto3).

Obter um certificado

O exemplo de código a seguir mostra como obter certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
```

```
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def get(self, certificate_arn):
        """
        Gets the body and certificate chain of a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The body and chain of a certificate.
        """
        try:
            response =
self.acm_client.get_certificate(CertificateArn=certificate_arn)
            logger.info("Got certificate %s and its chain.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't get certificate %s.", certificate_arn)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetCertificateReferência da API AWSSDK for Python (Boto3).

Importar certificados

O exemplo de código a seguir mostra como importar certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
```

```
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def import_certificate(self, certificate_body, private_key):
        """
        Imports a self-signed certificate to ACM.

        :param certificate_body: The body of the certificate, in PEM format.
        :param private_key: The unencrypted private key of the certificate, in PEM
                            format.
        :return: The ARN of the imported certificate.
        """
        try:
            response = self.acm_client.import_certificate(
                Certificate=certificate_body, PrivateKey=private_key
            )
            certificate_arn = response["CertificateArn"]
            logger.info("Imported certificate.")
        except ClientError:
            logger.exception("Couldn't import certificate.")
            raise
        else:
            return certificate_arn
```

- Para obter detalhes da API, consulte a ImportCertificateReferência da API AWSSDK for Python (Boto3).

Listar certificados

O exemplo de código a seguir mostra como listar certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def list(
        self,
        max_items,
        statuses=None,
        key_usage=None,
        extended_key_usage=None,
        key_types=None,
    ):
        """
        Lists the certificates for the current account.

        :param max_items: The maximum number of certificates to list.
        :param statuses: Filters the results to the specified statuses. If None, all
                         certificates are included.
        :param key_usage: Filters the results to the specified key usages. If None,
                          all key usages are included.
        :param extended_key_usage: Filters the results to the specified extended key
                                   usages. If None, all extended key usages are
                                   included.
        :param key_types: Filters the results to the specified key types. If None,
 all
                          key types are included.
```

```
        :return: The list of certificates.
        """
        try:
            kwargs = {"MaxItems": max_items}
            if statuses is not None:
                kwargs["CertificateStatuses"] = statuses
            includes = {}
            if key_usage is not None:
                includes["keyUsage"] = key_usage
            if extended_key_usage is not None:
                includes["extendedKeyUsage"] = extended_key_usage
            if key_types is not None:
                includes["keyTypes"] = key_types
            if includes:
                kwargs["Includes"] = includes
            response = self.acm_client.list_certificates(**kwargs)
            certificates = response["CertificateSummaryList"]
            logger.info("Got %s certificates.", len(certificates))
        except ClientError:
            logger.exception("Couldn't get certificates.")
            raise
        else:
            return certificates
```

- Para obter detalhes da API, consulte a ListCertificatesReferência da API AWSSDK for Python (Boto3).

Listar tags para um certificado

O exemplo de código a seguir mostra como listar tags para certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
```

```
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def list_tags(self, certificate_arn):
        """
        Lists the tags attached to a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The dictionary of certificate tags.
        """
        try:
            response = self.acm_client.list_tags_for_certificate(
                CertificateArn=certificate_arn
            )
            tags = {tag["Key"]: tag["Value"] for tag in response["Tags"]}
            logger.info("Got %s tags for certificates %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't get tags for certificate %s.",
certificate_arn)
            raise
        else:
            return tags
```

- Para obter detalhes da API, consulte a ListTagsForCertificateReferência da API AWSSDK for Python (Boto3).

Remover tags de um certificado

O exemplo de código a seguir mostra como remover tags de certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def remove_tags(self, certificate_arn, tags):
        """
        Removes tags from a certificate. If the value of a tag is specified, the tag
 is
        removed only when the value matches the value of the certificate's tag.
        Otherwise, the tag is removed regardless of its value.

        :param certificate_arn: The ARN of the certificate.
        :param tags: The dictionary of tags to remove.
        """
        try:
            cert_tags = []
            for key, value in tags.items():
                tag = {"Key": key}
                if value is not None:
                    tag["Value"] = value
                cert_tags.append(tag)
            self.acm_client.remove_tags_from_certificate(
                CertificateArn=certificate_arn, Tags=cert_tags
            )
            logger.info(
                "Removed %s tags from certificate %s.", len(tags), certificate_arn
```

```
            )
        except ClientError:
            logger.exception(
                "Couldn't remove tags from certificate %s.", certificate_arn
            )
            raise
```

- Para obter detalhes da API, consulte a RemoveTagsFromCertificateReferência da API AWSSDK for Python (Boto3).

Solicitar validação de um certificado

O exemplo de código a seguir mostra como solicitar a validação de certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def request_validation(
        self, domain, alternate_domains, method, validation_domains=None
    ):
        """
        Starts a validation request that results in a new certificate being issued
        by ACM. DNS validation requires that you add CNAME records to your DNS
```

```
        provider. Email validation sends email to a list of email addresses that
        are associated with the domain.

        For more information, see _Issuing and managing certificates_ in the ACM
        user guide.
            https://docs.aws.amazon.com/acm/latest/userguide/gs.html

        :param domain: The primary domain to associate with the certificate.
        :param alternate_domains: Subject Alternate Names (SANs) for the
certificate.
        :param method: The validation method, either DNS or EMAIL.
        :param validation_domains: Alternate domains to use for email validation,
when
                                   the email domain differs from the primary domain
of
                                   the certificate.
        :return: The ARN of the requested certificate.
        """
        try:
            kwargs = {
                "DomainName": domain,
                "ValidationMethod": method,
                "SubjectAlternativeNames": alternate_domains,
            }
            if validation_domains is not None:
                kwargs["DomainValidationOptions"] = [
                    {"DomainName": key, "ValidationDomain": value}
                    for key, value in validation_domains.items()
                ]
            response = self.acm_client.request_certificate(**kwargs)
            certificate_arn = response["CertificateArn"]
            logger.info(
                "Requested %s validation for domain %s. Certificate ARN is %s.",
                method,
                domain,
                certificate_arn,
            )
        except ClientError:
            logger.exception(
                "Request for %s validation of domain %s failed.", method, domain
            )
            raise
        else:
            return certificate_arn
```

- Para obter detalhes da API, consulte a RequestCertificateReferência da API AWSSDK for Python (Boto3).

Reenviar e-mail de validação para um certificado

O exemplo de código a seguir mostra como reenviar e-mail de validação de certificados ACM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def resend_validation_email(self, certificate_arn, domain, validation_domain):
        """
        Request that validation email is sent again, for a certificate that was
        previously requested with email validation.

        :param certificate_arn: The ARN of the certificate.
        :param domain: The primary domain of the certificate.
        :param validation_domain: Alternate domain to use for determining email
                                  addresses to use for validation.
        """
        try:
            self.acm_client.resend_validation_email(
```

```
                CertificateArn=certificate_arn,
                Domain=domain,
                ValidationDomain=validation_domain,
            )
            logger.info(
                "Validation email resent to validation domain %s.",
validation_domain
            )
        except ClientError:
            logger.exception(
                "Couldn't resend validation email to %s.", validation_domain
            )
            raise
```

- Para obter detalhes da API, consulte a ResendValidationEmailReferência da API AWSSDK for Python (Boto3).

Cenários

Gerenciar certificados

O código de exemplo a seguir mostra como:

- Solicitar um certificado do ACM.
- Importar um certificado auto-assinado.
- Listar e descrever certificados.
- Remover certificados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as operações do ACM.

```
import logging
from pprint import pprint

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class AcmCertificate:
    """
    Encapsulates ACM functions.
    """

    def __init__(self, acm_client):
        """
        :param acm_client: A Boto3 ACM client.
        """
        self.acm_client = acm_client


    def request_validation(
        self, domain, alternate_domains, method, validation_domains=None
    ):
        """
        Starts a validation request that results in a new certificate being issued
        by ACM. DNS validation requires that you add CNAME records to your DNS
        provider. Email validation sends email to a list of email addresses that
        are associated with the domain.

        For more information, see _Issuing and managing certificates_ in the ACM
        user guide.
            https://docs.aws.amazon.com/acm/latest/userguide/gs.html

        :param domain: The primary domain to associate with the certificate.
        :param alternate_domains: Subject Alternate Names (SANs) for the
certificate.
        :param method: The validation method, either DNS or EMAIL.
        :param validation_domains: Alternate domains to use for email validation,
when
                                   the email domain differs from the primary domain
of
                                   the certificate.
```

```
        :return: The ARN of the requested certificate.
        """
        try:
            kwargs = {
                "DomainName": domain,
                "ValidationMethod": method,
                "SubjectAlternativeNames": alternate_domains,
            }
            if validation_domains is not None:
                kwargs["DomainValidationOptions"] = [
                    {"DomainName": key, "ValidationDomain": value}
                    for key, value in validation_domains.items()
                ]
            response = self.acm_client.request_certificate(**kwargs)
            certificate_arn = response["CertificateArn"]
            logger.info(
                "Requested %s validation for domain %s. Certificate ARN is %s.",
                method,
                domain,
                certificate_arn,
            )
        except ClientError:
            logger.exception(
                "Request for %s validation of domain %s failed.", method, domain
            )
            raise
        else:
            return certificate_arn


    def import_certificate(self, certificate_body, private_key):
        """
        Imports a self-signed certificate to ACM.

        :param certificate_body: The body of the certificate, in PEM format.
        :param private_key: The unencrypted private key of the certificate, in PEM
                            format.
        :return: The ARN of the imported certificate.
        """
        try:
            response = self.acm_client.import_certificate(
                Certificate=certificate_body, PrivateKey=private_key
            )
            certificate_arn = response["CertificateArn"]
```

```
            logger.info("Imported certificate.")
        except ClientError:
            logger.exception("Couldn't import certificate.")
            raise
        else:
            return certificate_arn


    def list(
        self,
        max_items,
        statuses=None,
        key_usage=None,
        extended_key_usage=None,
        key_types=None,
    ):
        """
        Lists the certificates for the current account.

        :param max_items: The maximum number of certificates to list.
        :param statuses: Filters the results to the specified statuses. If None, all
                         certificates are included.
        :param key_usage: Filters the results to the specified key usages. If None,
                          all key usages are included.
        :param extended_key_usage: Filters the results to the specified extended key
                                   usages. If None, all extended key usages are
                                   included.
        :param key_types: Filters the results to the specified key types. If None,
all
                          key types are included.
        :return: The list of certificates.
        """
        try:
            kwargs = {"MaxItems": max_items}
            if statuses is not None:
                kwargs["CertificateStatuses"] = statuses
            includes = {}
            if key_usage is not None:
                includes["keyUsage"] = key_usage
            if extended_key_usage is not None:
                includes["extendedKeyUsage"] = extended_key_usage
            if key_types is not None:
                includes["keyTypes"] = key_types
            if includes:
```

```
                kwargs["Includes"] = includes
            response = self.acm_client.list_certificates(**kwargs)
            certificates = response["CertificateSummaryList"]
            logger.info("Got %s certificates.", len(certificates))
        except ClientError:
            logger.exception("Couldn't get certificates.")
            raise
        else:
            return certificates


    def describe(self, certificate_arn):
        """
        Gets certificate metadata.

        :param certificate_arn: The Amazon Resource Name (ARN) of the certificate.
        :return: Metadata about the certificate.
        """
        try:
            response = self.acm_client.describe_certificate(
                CertificateArn=certificate_arn
            )
            certificate = response["Certificate"]
            logger.info(
                "Got metadata for certificate for domain %s.",
certificate["DomainName"]
            )
        except ClientError:
            logger.exception("Couldn't get data for certificate %s.",
certificate_arn)
            raise
        else:
            return certificate


    def get(self, certificate_arn):
        """
        Gets the body and certificate chain of a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The body and chain of a certificate.
        """
        try:
```

```
            response =
self.acm_client.get_certificate(CertificateArn=certificate_arn)
            logger.info("Got certificate %s and its chain.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't get certificate %s.", certificate_arn)
            raise
        else:
            return response


    def add_tags(self, certificate_arn, tags):
        """
        Adds tags to a certificate. Tags are key-value pairs that contain custom
        metadata.

        :param certificate_arn: The ARN of the certificate.
        :param tags: A dictionary of key-value tags to add to the certificate.
        """
        try:
            self.acm_client.add_tags_to_certificate(
                CertificateArn=certificate_arn,
                Tags=[{"Key": key, "Value": value} for key, value in tags.items()],
            )
            logger.info("Added %s tags to certificate %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't add tags to certificate %s.",
certificate_arn)
            raise


    def list_tags(self, certificate_arn):
        """
        Lists the tags attached to a certificate.

        :param certificate_arn: The ARN of the certificate.
        :return: The dictionary of certificate tags.
        """
        try:
            response = self.acm_client.list_tags_for_certificate(
                CertificateArn=certificate_arn
            )
            tags = {tag["Key"]: tag["Value"] for tag in response["Tags"]}
```

```
            logger.info("Got %s tags for certificates %s.", len(tags),
certificate_arn)
        except ClientError:
            logger.exception("Couldn't get tags for certificate %s.",
certificate_arn)
            raise
        else:
            return tags


    def remove_tags(self, certificate_arn, tags):
        """
        Removes tags from a certificate. If the value of a tag is specified, the tag
is
        removed only when the value matches the value of the certificate's tag.
        Otherwise, the tag is removed regardless of its value.

        :param certificate_arn: The ARN of the certificate.
        :param tags: The dictionary of tags to remove.
        """
        try:
            cert_tags = []
            for key, value in tags.items():
                tag = {"Key": key}
                if value is not None:
                    tag["Value"] = value
                cert_tags.append(tag)
            self.acm_client.remove_tags_from_certificate(
                CertificateArn=certificate_arn, Tags=cert_tags
            )
            logger.info(
                "Removed %s tags from certificate %s.", len(tags), certificate_arn
            )
        except ClientError:
            logger.exception(
                "Couldn't remove tags from certificate %s.", certificate_arn
            )
            raise


    def remove(self, certificate_arn):
        """
        Removes a certificate.
```

```
        :param certificate_arn: The ARN of the certificate to remove.
        """
        try:
            self.acm_client.delete_certificate(CertificateArn=certificate_arn)
            logger.info("Removed certificate %s.", certificate_arn)
        except ClientError:
            logger.exception("Couldn't remove certificate %s.", certificate_arn)
            raise
```

Usar a classe wrapper para gerenciar certificados para uma conta.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the AWS Certificate Manager (ACM) demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    acm_certificate = AcmCertificate(boto3.client("acm"))
    domain = "example.com"
    sub_domains = [f"{sub}.{domain}" for sub in ["test", "dev"]]
    print(f"Request a certificate for {domain}.")
    certificate_arn = acm_certificate.request_validation(domain, sub_domains, "DNS")
    print(f"Started validation, got certificate ARN: {certificate_arn}.")

    import_cert_arn = None
    cert_file_name = input(
        "Enter the file name for a self-signed certificate in PEM format. "
        "This certificate will be imported to ACM. Press Enter to skip: "
    )
    if cert_file_name:
        pk_file_name = input(
            "Enter the file name for the unencrypted private key of the certificate.
 "
            "This file must also be in PEM format: "
        )
        if pk_file_name:
            with open(cert_file_name, "rb") as cert_file:
                import_cert = cert_file.read()
            with open(pk_file_name, "rb") as pk_file:
                import_pk = pk_file.read()
```

```
            import_cert_arn = acm_certificate.import_certificate(import_cert,
import_pk)
            print(f"Certificate imported, got ARN: {import_cert_arn}")
        else:
            print("No private key file entered. Skipping certificate import.")
    else:
        print("Skipping self-signed certificate import.")

    print("Getting the first 10 issued certificates.")
    certificates = acm_certificate.list(10, statuses=["ISSUED"])
    print(f"Found {len(certificates)} issued certificates.")

    print(f"Getting metadata for certificate {certificate_arn}")
    cert_metadata = acm_certificate.describe(certificate_arn)
    pprint(cert_metadata)

    if import_cert_arn is not None:
        print(f"Getting certificate for imported certificate {import_cert_arn}")
        import_cert_data = acm_certificate.get(import_cert_arn)
        pprint(import_cert_data)

    print(f"Adding tags to certificate {certificate_arn}.")
    acm_certificate.add_tags(certificate_arn, {"purpose": "acm demo", "color":
"green"})
    tags = acm_certificate.list_tags(certificate_arn)
    print(f"Found tags: {tags}")
    acm_certificate.remove_tags(certificate_arn, {key: None for key in tags})
    print("Removed tags.")

    print("Removing certificates added during the demo.")
    acm_certificate.remove(certificate_arn)
    if import_cert_arn is not None:
        acm_certificate.remove(import_cert_arn)

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AddTagsToCertificate

- DeleteCertificate
- DescribeCertificate
- GetCertificate
- ImportCertificate
- ListCertificates
- ListTagsForCertificate
- RemoveTagsFromCertificate
- RequestCertificate
- ResendValidationEmail

Exemplos de API Gateway usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com o API Gateway.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma resposta de um serviço AWS integrado a um método

O exemplo de código a seguir mostra como adicionar uma resposta de um serviço AWS integrado a um método API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
```

```
        :param service_endpoint_prefix: The service endpoint that is integrated with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate REST
                                 elements, such as query parameters, to the request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
```

```
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json": json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutIntegrationResponseReferência da API AWSSDK for Python (Boto3).

Adicionar um método HTTP a um recurso REST

O exemplo de código a seguir mostra como adicionar um método HTTP a um recurso REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
```

```
        :param service_endpoint_prefix: The service endpoint that is integrated with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate REST
                                 elements, such as query parameters, to the request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
```

```
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json": json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutMethodReferência da API AWSSDK for Python (Boto3).

Adicionar uma resposta HTTP a um recurso REST

O exemplo de código a seguir mostra como adicionar uma resposta HTTP a um recurso REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
```

```
        :param service_endpoint_prefix: The service endpoint that is integrated with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate REST
                                 elements, such as query parameters, to the request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
```

```
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json": json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutMethodResponseReferência da API AWSSDK for Python (Boto3).

Criar uma API REST

O exemplo de código a seguir mostra como criar uma API REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
            raise
```

```
        try:
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
            raise ValueError from err

        return self.api_id
```

- Para obter detalhes da API, consulte a CreateRestApiReferência da API AWSSDK for Python (Boto3).

Criar um recurso REST

O exemplo de código a seguir mostra como criar um recurso REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
```

```
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_rest_resource(self, parent_id, resource_path):
        """
        Adds a resource to a REST API.

        :param parent_id: The ID of the parent resource.
        :param resource_path: The path of the new resource, relative to the parent.
        :return: The ID of the new resource.
        """
        try:
            result = self.apig_client.create_resource(
                restApiId=self.api_id, parentId=parent_id, pathPart=resource_path
            )
            resource_id = result["id"]
            logger.info("Created resource %s.", resource_path)
        except ClientError:
            logger.exception("Couldn't create resource %s.", resource_path)
            raise
        else:
            return resource_id
```

- Para obter detalhes da API, consulte a CreateResourceReferência da API AWSSDK for Python (Boto3).

Excluir uma API REST

O exemplo de código a seguir mostra como excluir uma API REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def delete_rest_api(self):
        """
        Deletes a REST API, including all of its resources and configuration.
        """
        try:
            self.apig_client.delete_rest_api(restApiId=self.api_id)
            logger.info("Deleted REST API %s.", self.api_id)
            self.api_id = None
        except ClientError:
            logger.exception("Couldn't delete REST API %s.", self.api_id)
            raise
```

- Para obter detalhes da API, consulte a DeleteRestApiReferência da API AWSSDK for Python (Boto3).

Implantar uma API REST

O exemplo de código a seguir mostra como implantar uma API REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def deploy_api(self, stage_name):
        """
        Deploys a REST API. After a REST API is deployed, it can be called from any
        REST client, such as the Python Requests package or Postman.

        :param stage_name: The stage of the API to deploy, such as 'test'.
        :return: The base URL of the deployed REST API.
        """
        try:
            self.apig_client.create_deployment(
                restApiId=self.api_id, stageName=stage_name
            )
            self.stage = stage_name
            logger.info("Deployed stage %s.", stage_name)
        except ClientError:
            logger.exception("Couldn't deploy stage %s.", stage_name)
            raise
```

```
        else:
            return self.api_url()



    def api_url(self, resource=None):
        """
        Builds the REST API URL from its parts.

        :param resource: The resource path to append to the base URL.
        :return: The REST URL to the specified resource.
        """
        url = (
            f"https://{self.api_id}.execute-api.{self.apig_client.meta.region_name}"
            f".amazonaws.com/{self.stage}"
        )
        if resource is not None:
            url = f"{url}/{resource}"
        return url
```

- Para obter detalhes da API, consulte a CreateDeploymentReferência da API AWSSDK for Python (Boto3).

Obter recursos REST

O exemplo de código a seguir mostra como obter recursos REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
```

```
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
            raise

        try:
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
            raise ValueError from err

        return self.api_id
```

- Para obter detalhes da API, consulte a GetResourcesReferência da API AWSSDK for Python (Boto3).

Integrar um método a um serviço AWS

O exemplo de código a seguir mostra como integrar um método API Gateway com um serviço do AWS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
```

```
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate REST
                                 elements, such as query parameters, to the request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
```

```
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json": json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise
```

- Para obter detalhes da API, consulte a PutIntegrationReferência da API AWSSDK for Python (Boto3).

Listar APIs REST

O exemplo de código a seguir mostra como listar uma APIs REST do API Gateway.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def get_rest_api_id(self, api_name):
        """
        Gets the ID of a REST API from its name by searching the list of REST APIs
        for the current account. Because names need not be unique, this returns only
        the first API with the specified name.

        :param api_name: The name of the API to look up.
        :return: The ID of the specified API.
        """
        try:
            rest_api = None
            paginator = self.apig_client.get_paginator("get_rest_apis")
            for page in paginator.paginate():
                rest_api = next(
```

```
                    (item for item in page["items"] if item["name"] == api_name),
None
                )
                if rest_api is not None:
                    break
            self.api_id = rest_api["id"]
            logger.info("Found ID %s for API %s.", rest_api["id"], api_name)
        except ClientError:
            logger.exception("Couldn't find ID for API %s.", api_name)
            raise
        else:
            return rest_api["id"]
```

- Para obter detalhes da API, consulte a GetRestApisReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e implantar uma API REST

O código de exemplo a seguir mostra como:

- Criar uma API REST atendida pelo API Gateway.
- Adicionar recursos à API REST para representar um perfil de usuário.
- Adicione métodos de integração para que a API REST use uma tabela do DynamoDB para armazenar dados de perfil de usuário.
- Envie solicitações HTTP para a API REST para adicionar e recuperar perfis de usuário.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as operações do API Gateway.

```
import argparse
import json
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError
import requests

logger = logging.getLogger(__name__)


class ApiGatewayToService:
    """
    Encapsulates Amazon API Gateway functions that are used to create a REST API
 that
    integrates with another AWS service.
    """

    def __init__(self, apig_client):
        """
        :param apig_client: A Boto3 API Gateway client.
        """
        self.apig_client = apig_client
        self.api_id = None
        self.root_id = None
        self.stage = None


    def create_rest_api(self, api_name):
        """
        Creates a REST API on API Gateway. The default API has only a root resource
        and no HTTP methods.

        :param api_name: The name of the API. This descriptive name is not used in
                         the API path.
        :return: The ID of the newly created API.
        """
        try:
            result = self.apig_client.create_rest_api(name=api_name)
            self.api_id = result["id"]
            logger.info("Created REST API %s with ID %s.", api_name, self.api_id)
        except ClientError:
            logger.exception("Couldn't create REST API %s.", api_name)
```

```
            raise

        try:
            result = self.apig_client.get_resources(restApiId=self.api_id)
            self.root_id = next(
                item for item in result["items"] if item["path"] == "/"
            )["id"]
        except ClientError:
            logger.exception("Couldn't get resources for API %s.", self.api_id)
            raise
        except StopIteration as err:
            logger.exception("No root resource found in API %s.", self.api_id)
            raise ValueError from err

        return self.api_id


    def add_rest_resource(self, parent_id, resource_path):
        """
        Adds a resource to a REST API.

        :param parent_id: The ID of the parent resource.
        :param resource_path: The path of the new resource, relative to the parent.
        :return: The ID of the new resource.
        """
        try:
            result = self.apig_client.create_resource(
                restApiId=self.api_id, parentId=parent_id, pathPart=resource_path
            )
            resource_id = result["id"]
            logger.info("Created resource %s.", resource_path)
        except ClientError:
            logger.exception("Couldn't create resource %s.", resource_path)
            raise
        else:
            return resource_id


    def add_integration_method(
        self,
        resource_id,
        rest_method,
        service_endpoint_prefix,
        service_action,
```

```
        service_method,
        role_arn,
        mapping_template,
    ):
        """
        Adds an integration method to a REST API. An integration method is a REST
        resource, such as '/users', and an HTTP verb, such as GET. The integration
        method is backed by an AWS service, such as Amazon DynamoDB.

        :param resource_id: The ID of the REST resource.
        :param rest_method: The HTTP verb used with the REST resource.
        :param service_endpoint_prefix: The service endpoint that is integrated with
                                        this method, such as 'dynamodb'.
        :param service_action: The action that is called on the service, such as
                               'GetItem'.
        :param service_method: The HTTP method of the service request, such as POST.
        :param role_arn: The Amazon Resource Name (ARN) of a role that grants API
                         Gateway permission to use the specified action with the
                         service.
        :param mapping_template: A mapping template that is used to translate REST
                                 elements, such as query parameters, to the request
                                 body format required by the service.
        """
        service_uri = (
            f"arn:aws:apigateway:{self.apig_client.meta.region_name}"
            f":{service_endpoint_prefix}:action/{service_action}"
        )
        try:
            self.apig_client.put_method(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                authorizationType="NONE",
            )
            self.apig_client.put_method_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseModels={"application/json": "Empty"},
            )
            logger.info("Created %s method for resource %s.", rest_method,
resource_id)
        except ClientError:
```

```
            logger.exception(
                "Couldn't create %s method for resource %s.", rest_method,
resource_id
            )
            raise

        try:
            self.apig_client.put_integration(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                type="AWS",
                integrationHttpMethod=service_method,
                credentials=role_arn,
                requestTemplates={"application/json": json.dumps(mapping_template)},
                uri=service_uri,
                passthroughBehavior="WHEN_NO_TEMPLATES",
            )
            self.apig_client.put_integration_response(
                restApiId=self.api_id,
                resourceId=resource_id,
                httpMethod=rest_method,
                statusCode="200",
                responseTemplates={"application/json": ""},
            )
            logger.info(
                "Created integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
        except ClientError:
            logger.exception(
                "Couldn't create integration for resource %s to service URI %s.",
                resource_id,
                service_uri,
            )
            raise


    def deploy_api(self, stage_name):
        """
        Deploys a REST API. After a REST API is deployed, it can be called from any
        REST client, such as the Python Requests package or Postman.
```

```
        :param stage_name: The stage of the API to deploy, such as 'test'.
        :return: The base URL of the deployed REST API.
        """
        try:
            self.apig_client.create_deployment(
                restApiId=self.api_id, stageName=stage_name
            )
            self.stage = stage_name
            logger.info("Deployed stage %s.", stage_name)
        except ClientError:
            logger.exception("Couldn't deploy stage %s.", stage_name)
            raise
        else:
            return self.api_url()



    def api_url(self, resource=None):
        """
        Builds the REST API URL from its parts.

        :param resource: The resource path to append to the base URL.
        :return: The REST URL to the specified resource.
        """
        url = (
            f"https://{self.api_id}.execute-api.{self.apig_client.meta.region_name}"
            f".amazonaws.com/{self.stage}"
        )
        if resource is not None:
            url = f"{url}/{resource}"
        return url
```

Implantar uma API REST e chamá–la com o pacote Requests.

```
def usage_demo(table_name, role_name, rest_api_name):
    """
    Demonstrates how to used API Gateway to create and deploy a REST API, and how
    to use the Requests package to call it.

    :param table_name: The name of the demo DynamoDB table.
```

```
    :param role_name: The name of the demo role that grants API Gateway permission
to
                      call DynamoDB.
    :param rest_api_name: The name of the demo REST API created by the demo.
    """
    gateway = ApiGatewayToService(boto3.client("apigateway"))
    role = boto3.resource("iam").Role(role_name)

    print("Creating REST API in API Gateway.")
    gateway.create_rest_api(rest_api_name)

    print("Adding resources to the REST API.")
    profiles_id = gateway.add_rest_resource(gateway.root_id, "profiles")
    username_id = gateway.add_rest_resource(profiles_id, "{username}")

    # The DynamoDB service requires that all integration requests use POST.
    print("Adding integration methods to read and write profiles in Amazon
DynamoDB.")
    gateway.add_integration_method(
        profiles_id,
        "GET",
        "dynamodb",
        "Scan",
        "POST",
        role.arn,
        {"TableName": table_name},
    )
    gateway.add_integration_method(
        profiles_id,
        "POST",
        "dynamodb",
        "PutItem",
        "POST",
        role.arn,
        {
            "TableName": table_name,
            "Item": {
                "username": {"S": "$input.path('$.username')"},
                "name": {"S": "$input.path('$.name')"},
                "title": {"S": "$input.path('$.title')"},
            },
        },
    )
    gateway.add_integration_method(
```

```
        username_id,
        "GET",
        "dynamodb",
        "GetItem",
        "POST",
        role.arn,
        {
            "TableName": table_name,
            "Key": {"username": {"S": "$method.request.path.username"}},
        },
    )

    stage = "test"
    print(f"Deploying the {stage} stage.")
    gateway.deploy_api(stage)

    profiles_url = gateway.api_url("profiles")
    print(
        f"Using the Requests package to post some people to the profiles REST API at
 "
        f"{profiles_url}."
    )
    requests.post(
        profiles_url,
        json={"username": "will", "name": "William Shakespeare", "title":
 "playwright"},
    )
    requests.post(
        profiles_url,
        json={
            "username": "ludwig",
            "name": "Ludwig van Beethoven",
            "title": "composer",
        },
    )
    requests.post(
        profiles_url,
        json={"username": "jane", "name": "Jane Austen", "title": "author"},
    )
    print("Getting the list of profiles from the REST API.")
    profiles = requests.get(profiles_url).json()
    pprint(profiles)
    print(f"Getting just the profile for username 'jane' (URL: {profiles_url}/
jane).")
```

```
    jane = requests.get(f"{profiles_url}/jane").json()
    pprint(jane)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDeployment
  - CreateResource
  - CreateRestApi
  - DeleteRestApi
  - GetResources
  - GetRestApis
  - PutIntegration
  - PutIntegrationResponse
  - PutMethod
  - PutMethodResponse

Exemplos do Application Recovery Controller usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Application Recovery Controller.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter o estado de um controle de roteamento

O exemplo de código a seguir mostra como obter o estado do controle de roteamento do Application Recovery Controller.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def create_recovery_client(cluster_endpoint):
    """
    Creates a Boto3 Route 53 Application Recovery Controller client for the
 specified
    cluster endpoint URL and AWS Region.

    :param cluster_endpoint: The cluster endpoint URL and Region.
    :return: The Boto3 client.
    """
    return boto3.client(
        "route53-recovery-cluster",
        endpoint_url=cluster_endpoint["Endpoint"],
        region_name=cluster_endpoint["Region"],
    )



def get_routing_control_state(routing_control_arn, cluster_endpoints):
    """
    Gets the state of a routing control. Cluster endpoints are tried in
    sequence until the first successful response is received.

    :param routing_control_arn: The ARN of the routing control to look up.
    :param cluster_endpoints: The list of cluster endpoints to query.
    :return: The routing control state response.
```

```
    """

    # As a best practice, we recommend choosing a random cluster endpoint to get or
 set routing control states.
    # For more information, see https://docs.aws.amazon.com/r53recovery/latest/dg/
route53-arc-best-practices.html#route53-arc-best-practices.regional
    random.shuffle(cluster_endpoints)
    for cluster_endpoint in cluster_endpoints:
        try:
            recovery_client = create_recovery_client(cluster_endpoint)
            response = recovery_client.get_routing_control_state(
                RoutingControlArn=routing_control_arn
            )
            return response
        except Exception as error:
            print(error)
            raise error
```

- Para obter detalhes da API, consulte a GetRoutingControlStateReferência da API AWSSDK for Python (Boto3).

Atualizar o estado de um controle de roteamento

O exemplo de código a seguir mostra como atualizar o estado de um controle de roteamento do Application Recovery Controller.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def create_recovery_client(cluster_endpoint):
```

```
    """
    Creates a Boto3 Route 53 Application Recovery Controller client for the
 specified
    cluster endpoint URL and AWS Region.

    :param cluster_endpoint: The cluster endpoint URL and Region.
    :return: The Boto3 client.
    """
    return boto3.client(
        "route53-recovery-cluster",
        endpoint_url=cluster_endpoint["Endpoint"],
        region_name=cluster_endpoint["Region"],
    )



def update_routing_control_state(
    routing_control_arn, cluster_endpoints, routing_control_state
):
    """
    Updates the state of a routing control. Cluster endpoints are tried in
    sequence until the first successful response is received.

    :param routing_control_arn: The ARN of the routing control to update the state
 for.
    :param cluster_endpoints: The list of cluster endpoints to try.
    :param routing_control_state: The new routing control state.
    :return: The routing control update response.
    """

    # As a best practice, we recommend choosing a random cluster endpoint to get or
 set routing control states.
    # For more information, see https://docs.aws.amazon.com/r53recovery/latest/dg/
route53-arc-best-practices.html#route53-arc-best-practices.regional
    random.shuffle(cluster_endpoints)
    for cluster_endpoint in cluster_endpoints:
        try:
            recovery_client = create_recovery_client(cluster_endpoint)
            response = recovery_client.update_routing_control_state(
                RoutingControlArn=routing_control_arn,
                RoutingControlState=routing_control_state,
            )
            return response
        except Exception as error:
```

```
            print(error)
```

- Para obter detalhes da API, consulte a UpdateRoutingControlStateReferência da API AWSSDK for Python (Boto3).

Exemplos do Audit Manager usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Audit Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Cenários

Cenários

Criar uma estrutura personalizada a partir de um AWS Config pacote de conformidade

O código de exemplo a seguir mostra como:

- Obter uma lista de pacotes de conformidade do AWS Config.
- Criar um controle personalizado do Audit Manager para cada regra gerenciada em um pacote de conformidade.
- Criar uma estrutura personalizada do Audit Manager que contenha os controles.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class ConformancePack:
    def __init__(self, config_client, auditmanager_client):
        self.config_client = config_client
        self.auditmanager_client = auditmanager_client

    def get_conformance_pack(self):
        """
        Return a selected conformance pack from the list of conformance packs.

        :return: selected conformance pack
        """
        try:
            conformance_packs = self.config_client.describe_conformance_packs()
            print(
                "Number of conformance packs fetched: ",
                len(conformance_packs.get("ConformancePackDetails")),
            )
            print("Fetched the following conformance packs: ")
            all_cpack_names = {
                cp["ConformancePackName"]
                for cp in conformance_packs.get("ConformancePackDetails")
            }
            for pack in all_cpack_names:
                print(f"\t{pack}")
            cpack_name = input(
                "Provide ConformancePackName that you want to create a custom "
                "framework for: "
```

```
            )
            if cpack_name not in all_cpack_names:
                print(f"{cpack_name} is not in the list of conformance packs!")
                print(
                    "Provide a conformance pack name from the available list of "
                    "conformance packs."
                )
                raise Exception("Invalid conformance pack")
            print("-" * 88)
        except ClientError:
            logger.exception("Couldn't select conformance pack.")
            raise
        else:
            return cpack_name

    def create_custom_controls(self, cpack_name):
        """
        Create custom controls for all managed AWS Config rules in a conformance
pack.

        :param cpack_name: The name of the conformance pack to create controls for.
        :return: The list of custom control IDs.
        """
        try:
            rules_in_pack = self.config_client.describe_conformance_pack_compliance(
                ConformancePackName=cpack_name
            )
            print(
                "Number of rules in the conformance pack: ",
                len(rules_in_pack.get("ConformancePackRuleComplianceList")),
            )
            for rule in rules_in_pack.get("ConformancePackRuleComplianceList"):
                print(f"\t{rule.get('ConfigRuleName')}")
            print("-" * 88)
            print(
                "Creating a custom control for each rule and a custom framework "
                "consisting of these rules in Audit Manager."
            )
            am_controls = []
            for rule in rules_in_pack.get("ConformancePackRuleComplianceList"):
                config_rule = self.config_client.describe_config_rules(
                    ConfigRuleNames=[rule.get("ConfigRuleName")]
                )
                source_id = (
```

```
                    config_rule.get("ConfigRules")[0]
                    .get("Source", {})
                    .get("SourceIdentifier")
                )
                custom_control = self.auditmanager_client.create_control(
                    name="Config-" + rule.get("ConfigRuleName"),
                    controlMappingSources=[
                        {
                            "sourceName": "ConfigRule",
                            "sourceSetUpOption": "System_Controls_Mapping",
                            "sourceType": "AWS_Config",
                            "sourceKeyword": {
                                "keywordInputType": "SELECT_FROM_LIST",
                                "keywordValue": source_id,
                            },
                        }
                    ],
                ).get("control", {})
                am_controls.append({"id": custom_control.get("id")})
            print("Successfully created a control for each config rule.")
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom controls.")
            raise
        else:
            return am_controls

    def create_custom_framework(self, cpack_name, am_control_ids):
        """
        Create a custom Audit Manager framework from a selected AWS Config
conformance
        pack.

        :param cpack_name: The name of the conformance pack to create a framework
from.
        :param am_control_ids: The IDs of the custom controls created from the
                               conformance pack.
        """
        try:
            print("Creating custom framework...")
            custom_framework = self.auditmanager_client.create_assessment_framework(
                name="Config-Conformance-pack-" + cpack_name,
                controlSets=[{"name": cpack_name, "controls": am_control_ids}],
            )
```

```
            print(
                f"Successfully created the custom framework: ",
                f"{custom_framework.get('framework').get('name')}: ",
                f"{custom_framework.get('framework').get('id')}",
            )
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom framework.")
            raise


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager custom framework demo!")
    print("-" * 88)
    print(
        "You can use this sample to select a conformance pack from AWS Config and "
        "use AWS Audit Manager to create a custom control for all the managed "
        "rules under the conformance pack. A custom framework is also created "
        "with these controls."
    )
    print("-" * 88)
    conf_pack = ConformancePack(boto3.client("config"),
 boto3.client("auditmanager"))
    cpack_name = conf_pack.get_conformance_pack()
    am_controls = conf_pack.create_custom_controls(cpack_name)
    conf_pack.create_custom_framework(cpack_name, am_controls)


if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAssessmentFramework
  - CreateControl

Criar uma estrutura personalizada que contenha controles do Security Hub

O código de exemplo a seguir mostra como:

- Obter uma lista de todos os controles padrão que têm o Security Hub como fonte de dados.
- Criar uma estrutura personalizada do Audit Manager que contenha os controles.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class SecurityHub:
    def __init__(self, auditmanager_client):
        self.auditmanager_client = auditmanager_client

    def get_sechub_controls(self):
        """
        Gets the list of controls that use Security Hub as their data source.

        :return: The list of Security Hub controls.
        """
        print("-" * 88)
        next_token = None
        page = 1
        sechub_control_list = []
        while True:
            print("Page [" + str(page) + "]")
            if next_token is None:
                control_list = self.auditmanager_client.list_controls(
                    controlType="Standard", maxResults=100
                )
            else:
                control_list = self.auditmanager_client.list_controls(
                    controlType="Standard", nextToken=next_token, maxResults=100
```

```
                )
            print("Total controls found:",
 len(control_list.get("controlMetadataList")))
            for control in control_list.get("controlMetadataList"):
                control_details = self.auditmanager_client.get_control(
                    controlId=control.get("id")
                ).get("control", {})
                if "AWS Security Hub" in control_details.get("controlSources"):
                    sechub_control_list.append({"id": control_details.get("id")})
            next_token = control_list.get("nextToken")
            if not next_token:
                break
            page += 1
        print("Number of Security Hub controls found: ", len(sechub_control_list))
        return sechub_control_list

    def create_custom_framework(self, am_controls):
        """
        Create a custom framework with a list of controls.

        :param am_controls: The list of controls to include in the framework.
        """
        try:
            print("Creating custom framework...")
            custom_framework = self.auditmanager_client.create_assessment_framework(
                name="All Security Hub Controls Framework",
                controlSets=[{"name": "Security-Hub", "controls": am_controls}],
            )
            print(
                f"Successfully created the custom framework: "
                f"{custom_framework.get('framework').get('name')}: "
                f"{custom_framework.get('framework').get('id')}"
            )
            print("-" * 88)
        except ClientError:
            logger.exception("Failed to create custom framework.")
            raise


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager Security Hub demo!")
    print("-" * 88)
    print(" This script creates a custom framework with all Security Hub controls.")
```

```
    print("-" * 88)
    sechub = SecurityHub(boto3.client("auditmanager"))
    am_controls = sechub.get_sechub_controls()
    sechub.create_custom_framework(am_controls)


if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAssessmentFramework
  - GetControl
  - ListControls

Criar um relatório de avaliação

O exemplo de código a seguir mostra como criar um relatório de avaliação do Audit Manager que contém um dia de evidência.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import dateutil.parser
import logging
import time
import urllib.request
import uuid
import boto3
from botocore.exceptions import ClientError


logger = logging.getLogger(__name__)
```

```
class AuditReport:
    def __init__(self, auditmanager_client):
        self.auditmanager_client = auditmanager_client

    def get_input(self):
        print("-" * 40)
        try:
            assessment_id = input("Provide assessment id [uuid]: ").lower()
            try:
                assessment_uuid = uuid.UUID(assessment_id)
            except ValueError:
                logger.error("Assessment Id is not a valid UUID: %s", assessment_id)
                raise
            evidence_folder = input("Provide evidence date [yyyy-mm-dd]: ")
            try:
                evidence_date = dateutil.parser.parse(evidence_folder).date()
            except ValueError:
                logger.error("Invalid date : %s", evidence_folder)
                raise
            try:
                self.auditmanager_client.get_assessment(
                    assessmentId=str(assessment_uuid)
                )
            except ClientError:
                logger.exception("Couldn't get assessment %s.", assessment_uuid)
                raise
        except (ValueError, ClientError):
            return None, None
        else:
            return assessment_uuid, evidence_date

    def clear_staging(self, assessment_uuid, evidence_date):
        """
        Find all the evidence in the report and clear it.
        """
        next_token = None
        page = 1
        interested_folder_id_list = []
        while True:
            print(f"Page [{page}]")
            if next_token is None:
                folder_list = (
                    self.auditmanager_client.get_evidence_folders_by_assessment(
```

```
                        assessmentId=str(assessment_uuid), maxResults=1000
                    )
                )
            else:
                folder_list = (
                    self.auditmanager_client.get_evidence_folders_by_assessment(
                        assessmentId=str(assessment_uuid),
                        nextToken=next_token,
                        maxResults=1000,
                    )
                )
            folders = folder_list.get("evidenceFolders")
            print(f"Got {len(folders)} folders.")
            for folder in folders:
                folder_id = folder.get("id")
                if folder.get("name") == str(evidence_date):
                    interested_folder_id_list.append(folder_id)
                if folder.get("assessmentReportSelectionCount") == folder.get(
                    "totalEvidence"
                ):
                    print(
                        f"Removing folder from report selection :
{folder.get('name')} "
                        f"{folder_id} {folder.get('controlId')}"
                    )

self.auditmanager_client.disassociate_assessment_report_evidence_folder(
                        assessmentId=str(assessment_uuid),
evidenceFolderId=folder_id
                    )
                elif folder.get("assessmentReportSelectionCount") > 0:
                    # Get all evidence in the folder and
                    # add selected evidence in the selected_evidence_list.
                    evidence_list = (
                        self.auditmanager_client.get_evidence_by_evidence_folder(
                            assessmentId=str(assessment_uuid),
                            controlSetId=folder_id,
                            evidenceFolderId=folder_id,
                            maxResults=1000,
                        )
                    )
                    selected_evidence_list = []
                    for evidence in evidence_list.get("evidence"):
                        if evidence.get("assessmentReportSelection") == "Yes":
```

```
                            selected_evidence_list.append(evidence.get("id"))
                    print(
                        f"Removing evidence report selection : {folder.get('name')}
"
                        f"{len(selected_evidence_list)}"
                    )

self.auditmanager_client.batch_disassociate_assessment_report_evidence(
                        assessmentId=str(assessment_uuid),
                        evidenceFolderId=folder_id,
                        evidenceIds=selected_evidence_list,
                    )
            next_token = folder_list.get("nextToken")
            if not next_token:
                break
            page += 1
        return interested_folder_id_list

    def add_folder_to_staging(self, assessment_uuid, folder_id_list):
        print(f"Adding folders to report : {folder_id_list}")
        for folder in folder_id_list:
            self.auditmanager_client.associate_assessment_report_evidence_folder(
                assessmentId=str(assessment_uuid), evidenceFolderId=folder
            )

    def get_report(self, assessment_uuid):
        report = self.auditmanager_client.create_assessment_report(
            name="ReportViaScript",
            description="testing",
            assessmentId=str(assessment_uuid),
        )
        if self._is_report_generated(report.get("assessmentReport").get("id")):
            report_url = self.auditmanager_client.get_assessment_report_url(
                assessmentReportId=report.get("assessmentReport").get("id"),
                assessmentId=str(assessment_uuid),
            )
            print(report_url.get("preSignedUrl"))
            urllib.request.urlretrieve(
                report_url.get("preSignedUrl").get("link"),
                report_url.get("preSignedUrl").get("hyperlinkName"),
            )
            print(
                f"Report saved as
{report_url.get('preSignedUrl').get('hyperlinkName')}."
```

```
            )
        else:
            print("Report generation did not finish in 15 minutes.")
            print(
                "Failed to download report. Go to the console and manually download
 "
                "the report."
            )

    def _is_report_generated(self, assessment_report_id):
        max_wait_time = 0
        while max_wait_time < 900:
            print(f"Checking status of the report {assessment_report_id}")
            report_list =
 self.auditmanager_client.list_assessment_reports(maxResults=1)
            if (
                report_list.get("assessmentReports")[0].get("id")
                == assessment_report_id
                and report_list.get("assessmentReports")[0].get("status") ==
 "COMPLETE"
            ):
                return True
            print("Sleeping for 5 seconds...")
            time.sleep(5)
            max_wait_time += 5


def run_demo():
    print("-" * 88)
    print("Welcome to the AWS Audit Manager samples demo!")
    print("-" * 88)
    print(
        "This script creates an assessment report for an assessment with all the "
        "evidence collected on the provided date."
    )
    print("-" * 88)

    report = AuditReport(boto3.client("auditmanager"))
    assessment_uuid, evidence_date = report.get_input()
    if assessment_uuid is not None and evidence_date is not None:
        folder_id_list = report.clear_staging(assessment_uuid, evidence_date)
        report.add_folder_to_staging(assessment_uuid, folder_id_list)
        report.get_report(assessment_uuid)
```

```
if __name__ == "__main__":
    run_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AssociateAssessmentReportEvidenceFolder
  - BatchDisassociateAssessmentReportEvidence
  - CreateAssessmentReport
  - DisassociateAssessmentReportEvidenceFolder
  - GetAssessment
  - GetAssessmentReportUrl
  - GetEvidenceByEvidenceFolder
  - GetEvidenceFoldersByAssessment
  - ListAssessmentReports

Exemplos de Aurora usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

Os exemplos de código a seguir mostram como criar um cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_db_cluster(
        self,
        cluster_name,
        parameter_group_name,
        db_name,
        db_engine,
        db_engine_version,
        admin_name,
        admin_password,
    ):
```

```
        """
        Creates a DB cluster that is configured to use the specified parameter
group.
        The newly created DB cluster contains a database that uses the specified
engine and
        engine version.

        :param cluster_name: The name of the DB cluster to create.
        :param parameter_group_name: The name of the parameter group to associate
with
                                     the DB cluster.
        :param db_name: The name of the database to create.
        :param db_engine: The database engine of the database that is created, such
as MySql.
        :param db_engine_version: The version of the database engine.
        :param admin_name: The user name of the database administrator.
        :param admin_password: The password of the database administrator.
        :return: The newly created DB cluster.
        """
        try:
            response = self.rds_client.create_db_cluster(
                DatabaseName=db_name,
                DBClusterIdentifier=cluster_name,
                DBClusterParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            cluster = response["DBCluster"]
        except ClientError as err:
            logger.error(
                "Couldn't create database %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return cluster
```

- Para obter detalhes da API, consulte CreateDBCluster na Referência da API do AWS SDK para Python (Boto3).

Criar um parameter group de cluster de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB cluster parameter group that is based on the specified
 parameter group
        family.
```

```
        :param parameter_group_name: The name of the newly created parameter group.
        :param parameter_group_family: The family that is used as the basis of the
new
                                    parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API CreateDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Criar um snapshot de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
```

```
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_cluster_snapshot(self, snapshot_id, cluster_id):
        """
        Creates a snapshot of a DB cluster.

        :param snapshot_id: The ID to give the created snapshot.
        :param cluster_id: The DB cluster to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_cluster_snapshot(
                DBClusterSnapshotIdentifier=snapshot_id,
DBClusterIdentifier=cluster_id
            )
            snapshot = response["DBClusterSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                cluster_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte Referência da API CreateDB ClusterSnapshot no AWSSDK for Python (Boto3).

Criar uma instância de banco de dados em um cluster de banco de dados

Os exemplos de código a seguir mostram como criar uma instância DB em um cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_instance_in_cluster(
        self, instance_id, cluster_id, db_engine, instance_class
    ):
        """
        Creates a database instance in an existing DB cluster. The first database
 that is
```

```
        created defaults to a read-write DB instance.

        :param instance_id: The ID to give the newly created DB instance.
        :param cluster_id: The ID of the DB cluster where the DB instance is
created.
        :param db_engine: The database engine of a database to create in the DB
instance.
                          This must be compatible with the configured parameter
group
                          of the DB cluster.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBInstanceIdentifier=instance_id,
                DBClusterIdentifier=cluster_id,
                Engine=db_engine,
                DBInstanceClass=instance_class,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Python (Boto3).

Excluir um cluster de banco de dados

O exemplo de código a seguir mostra como excluir um cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_cluster(self, cluster_name):
        """
        Deletes a DB cluster.

        :param cluster_name: The name of the DB cluster to delete.
        """
        try:
            self.rds_client.delete_db_cluster(
                DBClusterIdentifier=cluster_name, SkipFinalSnapshot=True
            )
            logger.info("Deleted DB cluster %s.", cluster_name)
        except ClientError:
            logger.exception("Couldn't delete DB cluster %s.", cluster_name)
            raise
```

- Para ter detalhes da API, consulte DeleteDBCluster na Referência da API do AWS SDK para Python (Boto3).

Excluir um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB cluster parameter group.
```

```
        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            response = self.rds_client.delete_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API DeleteDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
```

```
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Python (Boto3).

Descrever os grupos de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever grupos de parâmetros de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The requested parameter group.
        """
        try:
            response = self.rds_client.describe_db_cluster_parameter_groups(
                DBClusterParameterGroupName=parameter_group_name
```

```
            )
            parameter_group = response["DBClusterParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
 parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameterGroups na Referência da API AWSSDK for Python (Boto3).

Descrever snapshots de cluster de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
```

```
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_cluster_snapshot(self, snapshot_id):
        """
        Gets a DB cluster snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_cluster_snapshots(
                DBClusterSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBClusterSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get DB cluster snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte DescribeDB ClusterSnapshots na Referência da API AWSSDK for Python (Boto3).

Descrever clusters de banco de dados

Os exemplos de código a seguir mostram como descrever clusters do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_cluster(self, cluster_name):
        """
        Gets data about an Aurora DB cluster.

        :param cluster_name: The name of the DB cluster to retrieve.
        :return: The retrieved DB cluster.
        """
        try:
            response = self.rds_client.describe_db_clusters(
                DBClusterIdentifier=cluster_name
            )
            cluster = response["DBClusters"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBClusterNotFoundFault":
                logger.info("Cluster %s does not exist.", cluster_name)
```

```
            else:
                logger.error(
                    "Couldn't verify the existence of DB cluster %s. Here's why: %s: 
%s",
                    cluster_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return cluster
```

- Para ter detalhes da API, consulte DescribeDBClusters na Referência da API do AWS SDK para Python (Boto3).

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS) 
client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
```

```
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Python (Boto3).

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Aurora.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned list
 of
                                       engine versions to those that are compatible
 with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
```

```
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na Referência da API AWSSDK for Python (Boto3).

Descrever as opções de instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever as opções de instâncias do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client
```

```
    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by the
DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts
```

- Para obter detalhes da API, consulte DescribeOrderableReferência da API DB InstanceOptions in AWSSDK for Python (Boto3).

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to query.
```

```
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBClusterParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator =
self.rds_client.get_paginator("describe_db_cluster_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na Referência da API AWSSDK for Python (Boto3).

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                Parameters=update_parameters,
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API ModifyDB ClusterParameterGroup no AWSSDK for Python (Boto3).

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class AuroraClusterScenario:
    """Runs a scenario that shows how to get started using Aurora DB clusters."""

    def __init__(self, aurora_wrapper):
```

```
        """
        :param aurora_wrapper: An object that wraps Aurora DB cluster actions.
        """
        self.aurora_wrapper = aurora_wrapper

    def create_parameter_group(self, db_engine, parameter_group_name):
        """
        Shows how to get available engine versions for a specified database engine
and
        create a DB cluster parameter group that is compatible with a selected
engine family.

        :param db_engine: The database engine to use as a basis.
        :param parameter_group_name: The name given to the newly created parameter
group.
        :return: The newly created parameter group.
        """
        print(
            f"Checking for an existing DB cluster parameter group named
{parameter_group_name}."
        )
        parameter_group =
self.aurora_wrapper.get_parameter_group(parameter_group_name)
        if parameter_group is None:
            print(f"Getting available database engine versions for {db_engine}.")
            engine_versions = self.aurora_wrapper.get_engine_versions(db_engine)
            families = list({ver["DBParameterGroupFamily"] for ver in
engine_versions})
            family_index = q.choose("Which family do you want to use? ", families)
            print(f"Creating a DB cluster parameter group.")
            self.aurora_wrapper.create_parameter_group(
                parameter_group_name, families[family_index], "Example parameter
group."
            )
            parameter_group = self.aurora_wrapper.get_parameter_group(
                parameter_group_name
            )
        print(f"Parameter group {parameter_group['DBClusterParameterGroupName']}:")
        pp(parameter_group)
        print("-" * 88)
        return parameter_group

    def set_user_parameters(self, parameter_group_name):
        """
```

```
        Shows how to get the parameters contained in a custom parameter group and
        update some of the parameter values in the group.

        :param parameter_group_name: The name of the parameter group to query and
modify.
        """
        print("Let's set some parameter values in your parameter group.")
        auto_inc_parameters = self.aurora_wrapper.get_parameters(
            parameter_group_name, name_prefix="auto_increment"
        )
        update_params = []
        for auto_inc in auto_inc_parameters:
            if auto_inc["IsModifiable"] and auto_inc["DataType"] == "integer":
                print(f"The {auto_inc['ParameterName']} parameter is described as:")
                print(f"\t{auto_inc['Description']}")
                param_range = auto_inc["AllowedValues"].split("-")
                auto_inc["ParameterValue"] = str(
                    q.ask(
                        f"Enter a value between {param_range[0]} and
{param_range[1]}: ",
                        q.is_int,
                        q.in_range(int(param_range[0]), int(param_range[1])),
                    )
                )
                update_params.append(auto_inc)
        self.aurora_wrapper.update_parameters(parameter_group_name, update_params)
        print(
            "You can get a list of parameters you've set by specifying a source of
'user'."
        )
        user_parameters = self.aurora_wrapper.get_parameters(
            parameter_group_name, source="user"
        )
        pp(user_parameters)
        print("-" * 88)

    def create_cluster(self, cluster_name, db_engine, db_name, parameter_group):
        """
        Shows how to create an Aurora DB cluster that contains a database of a
specified
        type. The database is also configured to use a custom DB cluster parameter
group.

        :param cluster_name: The name given to the newly created DB cluster.
```

```
        :param db_engine: The engine of the created database.
        :param db_name: The name given to the created database.
        :param parameter_group: The parameter group that is associated with the DB
cluster.
        :return: The newly created DB cluster.
        """
        print("Checking for an existing DB cluster.")
        cluster = self.aurora_wrapper.get_db_cluster(cluster_name)
        if cluster is None:
            admin_username = q.ask(
                "Enter an administrator user name for the database: ", q.non_empty
            )
            admin_password = q.ask(
                "Enter a password for the administrator (at least 8 characters): ",
                q.non_empty,
            )
            engine_versions = self.aurora_wrapper.get_engine_versions(
                db_engine, parameter_group["DBParameterGroupFamily"]
            )
            engine_choices = [ver["EngineVersion"] for ver in engine_versions]
            print("The available engines for your parameter group are:")
            engine_index = q.choose("Which engine do you want to use? ",
engine_choices)
            print(
                f"Creating DB cluster {cluster_name} and database {db_name}.\n"
                f"The DB cluster is configured to use\n"
                f"your custom parameter group
{parameter_group['DBClusterParameterGroupName']}\n"
                f"and selected engine {engine_choices[engine_index]}.\n"
                f"This typically takes several minutes."
            )
            cluster = self.aurora_wrapper.create_db_cluster(
                cluster_name,
                parameter_group["DBClusterParameterGroupName"],
                db_name,
                db_engine,
                engine_choices[engine_index],
                admin_username,
                admin_password,
            )
            while cluster.get("Status") != "available":
                wait(30)
                cluster = self.aurora_wrapper.get_db_cluster(cluster_name)
            print("Cluster created and available.\n")
```

```
        print("Cluster data:")
        pp(cluster)
        print("-" * 88)
        return cluster

    def create_instance(self, cluster):
        """
        Shows how to create a DB instance in an existing Aurora DB cluster. A new DB
cluster
        contains no DB instances, so you must add one. The first DB instance that is
added
        to a DB cluster defaults to a read-write DB instance.

        :param cluster: The DB cluster where the DB instance is added.
        :return: The newly created DB instance.
        """
        print("Checking for an existing database instance.")
        cluster_name = cluster["DBClusterIdentifier"]
        db_inst = self.aurora_wrapper.get_db_instance(cluster_name)
        if db_inst is None:
            print("Let's create a database instance in your DB cluster.")
            print("First, choose a DB instance type:")
            inst_opts = self.aurora_wrapper.get_orderable_instances(
                cluster["Engine"], cluster["EngineVersion"]
            )
            inst_choices = list({opt["DBInstanceClass"] for opt in inst_opts})
            inst_index = q.choose(
                "Which DB instance class do you want to use? ", inst_choices
            )
            print(
                f"Creating a database instance. This typically takes several
minutes."
            )
            db_inst = self.aurora_wrapper.create_instance_in_cluster(
                cluster_name, cluster_name, cluster["Engine"],
inst_choices[inst_index]
            )
            while db_inst.get("DBInstanceStatus") != "available":
                wait(30)
                db_inst = self.aurora_wrapper.get_db_instance(cluster_name)
        print("Instance data:")
        pp(db_inst)
        print("-" * 88)
        return db_inst
```

```
    @staticmethod
    def display_connection(cluster):
        """
        Displays connection information about an Aurora DB cluster and tips on how
 to
        connect to it.

        :param cluster: The DB cluster to display.
        """
        print(
            "You can now connect to your database using your favorite MySql client.
\n"
            "One way to connect is by using the 'mysql' shell on an Amazon EC2
 instance\n"
            "that is running in the same VPC as your database cluster. Pass the
 endpoint,\n"
            "port, and administrator user name to 'mysql' and enter your password\n"
            "when prompted:\n"
        )
        print(
            f"\n\tmysql -h {cluster['Endpoint']} -P {cluster['Port']} -u
 {cluster['MasterUsername']} -p\n"
        )
        print(
            "For more information, see the User Guide for Aurora:\n"
            "\thttps://docs.aws.amazon.com/AmazonRDS/latest/AuroraUserGuide/
CHAP_GettingStartedAurora.CreatingConnecting.Aurora.html#CHAP_GettingStartedAurora.Aurora.Co
        )
        print("-" * 88)

    def create_snapshot(self, cluster_name):
        """
        Shows how to create a DB cluster snapshot and wait until it's available.

        :param cluster_name: The name of a DB cluster to snapshot.
        """
        if q.ask(
            "Do you want to create a snapshot of your DB cluster (y/n)? ",
 q.is_yesno
        ):
            snapshot_id = f"{cluster_name}-{uuid.uuid4()}"
            print(
```

```
                f"Creating a snapshot named {snapshot_id}. This typically takes a
few minutes."
            )
            snapshot = self.aurora_wrapper.create_cluster_snapshot(
                snapshot_id, cluster_name
            )
            while snapshot.get("Status") != "available":
                wait(30)
                snapshot = self.aurora_wrapper.get_cluster_snapshot(snapshot_id)
            pp(snapshot)
            print("-" * 88)

    def cleanup(self, db_inst, cluster, parameter_group):
        """
        Shows how to clean up a DB instance, DB cluster, and DB cluster parameter
group.
        Before the DB cluster parameter group can be deleted, all associated DB
instances and
        DB clusters must first be deleted.

        :param db_inst: The DB instance to delete.
        :param cluster: The DB cluster to delete.
        :param parameter_group: The DB cluster parameter group to delete.
        """
        cluster_name = cluster["DBClusterIdentifier"]
        parameter_group_name = parameter_group["DBClusterParameterGroupName"]
        if q.ask(
            "\nDo you want to delete the database instance, DB cluster, and
parameter "
            "group (y/n)? ",
            q.is_yesno,
        ):
            print(f"Deleting database instance {db_inst['DBInstanceIdentifier']}.")
            self.aurora_wrapper.delete_db_instance(db_inst["DBInstanceIdentifier"])
            print(f"Deleting database cluster {cluster_name}.")
            self.aurora_wrapper.delete_db_cluster(cluster_name)
            print(
                "Waiting for the DB instance and DB cluster to delete.\n"
                "This typically takes several minutes."
            )
            while db_inst is not None or cluster is not None:
                wait(30)
                if db_inst is not None:
                    db_inst = self.aurora_wrapper.get_db_instance(
```

```
                        db_inst["DBInstanceIdentifier"]
                    )
                if cluster is not None:
                    cluster = self.aurora_wrapper.get_db_cluster(
                        cluster["DBClusterIdentifier"]
                    )
            print(f"Deleting parameter group {parameter_group_name}.")
            self.aurora_wrapper.delete_parameter_group(parameter_group_name)

    def run_scenario(self, db_engine, parameter_group_name, cluster_name, db_name):
        print("-" * 88)
        print(
            "Welcome to the Amazon Relational Database Service (Amazon RDS) get
 started\n"
            "with Aurora DB clusters demo."
        )
        print("-" * 88)

        parameter_group = self.create_parameter_group(db_engine,
 parameter_group_name)
        self.set_user_parameters(parameter_group_name)
        cluster = self.create_cluster(cluster_name, db_engine, db_name,
 parameter_group)
        wait(5)
        db_inst = self.create_instance(cluster)
        self.display_connection(cluster)
        self.create_snapshot(cluster_name)
        self.cleanup(db_inst, cluster, parameter_group)

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    try:
        scenario = AuroraClusterScenario(AuroraWrapper.from_client())
        scenario.run_scenario(
            "aurora-mysql",
            "doc-example-cluster-parameter-group",
            "doc-example-aurora",
            "docexampledb",
        )
    except Exception:
```

```
        logging.exception("Something went wrong with the demo.")
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Aurora.

```
class AuroraWrapper:
    """Encapsulates Aurora DB cluster actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon Relational Database Service (Amazon RDS)
 client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The requested parameter group.
        """
        try:
            response = self.rds_client.describe_db_cluster_parameter_groups(
                DBClusterParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBClusterParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
 parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
```

```
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB cluster parameter group that is based on the specified
parameter group
        family.

        :param parameter_group_name: The name of the newly created parameter group.
        :param parameter_group_family: The family that is used as the basis of the
new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def delete_parameter_group(self, parameter_group_name):
        """
```

```
        Deletes a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            response = self.rds_client.delete_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBClusterParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator =
self.rds_client.get_paginator("describe_db_cluster_parameters")
            for page in paginator.paginate(**kwargs):
```

```
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB cluster parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_cluster_parameter_group(
                DBClusterParameterGroupName=parameter_group_name,
                Parameters=update_parameters,
            )
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def get_db_cluster(self, cluster_name):
        """
```

```
        Gets data about an Aurora DB cluster.

        :param cluster_name: The name of the DB cluster to retrieve.
        :return: The retrieved DB cluster.
        """
        try:
            response = self.rds_client.describe_db_clusters(
                DBClusterIdentifier=cluster_name
            )
            cluster = response["DBClusters"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBClusterNotFoundFault":
                logger.info("Cluster %s does not exist.", cluster_name)
            else:
                logger.error(
                    "Couldn't verify the existence of DB cluster %s. Here's why: %s:
%s",
                    cluster_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return cluster


    def create_db_cluster(
        self,
        cluster_name,
        parameter_group_name,
        db_name,
        db_engine,
        db_engine_version,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB cluster that is configured to use the specified parameter
group.
        The newly created DB cluster contains a database that uses the specified
engine and
        engine version.

        :param cluster_name: The name of the DB cluster to create.
```

```
        :param parameter_group_name: The name of the parameter group to associate
with
                                     the DB cluster.
        :param db_name: The name of the database to create.
        :param db_engine: The database engine of the database that is created, such
as MySql.
        :param db_engine_version: The version of the database engine.
        :param admin_name: The user name of the database administrator.
        :param admin_password: The password of the database administrator.
        :return: The newly created DB cluster.
        """
        try:
            response = self.rds_client.create_db_cluster(
                DatabaseName=db_name,
                DBClusterIdentifier=cluster_name,
                DBClusterParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            cluster = response["DBCluster"]
        except ClientError as err:
            logger.error(
                "Couldn't create database %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return cluster


    def delete_db_cluster(self, cluster_name):
        """
        Deletes a DB cluster.

        :param cluster_name: The name of the DB cluster to delete.
        """
        try:
            self.rds_client.delete_db_cluster(
                DBClusterIdentifier=cluster_name, SkipFinalSnapshot=True
            )
```

```
            logger.info("Deleted DB cluster %s.", cluster_name)
        except ClientError:
            logger.exception("Couldn't delete DB cluster %s.", cluster_name)
            raise


    def create_cluster_snapshot(self, snapshot_id, cluster_id):
        """
        Creates a snapshot of a DB cluster.

        :param snapshot_id: The ID to give the created snapshot.
        :param cluster_id: The DB cluster to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_cluster_snapshot(
                DBClusterSnapshotIdentifier=snapshot_id,
DBClusterIdentifier=cluster_id
            )
            snapshot = response["DBClusterSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                cluster_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def get_cluster_snapshot(self, snapshot_id):
        """
        Gets a DB cluster snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_cluster_snapshots(
                DBClusterSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBClusterSnapshots"][0]
```

```
        except ClientError as err:
            logger.error(
                "Couldn't get DB cluster snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def create_instance_in_cluster(
        self, instance_id, cluster_id, db_engine, instance_class
    ):
        """
        Creates a database instance in an existing DB cluster. The first database
that is
        created defaults to a read-write DB instance.

        :param instance_id: The ID to give the newly created DB instance.
        :param cluster_id: The ID of the DB cluster where the DB instance is
created.
        :param db_engine: The database engine of a database to create in the DB
instance.
                          This must be compatible with the configured parameter
group
                          of the DB cluster.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBInstanceIdentifier=instance_id,
                DBClusterIdentifier=cluster_id,
                Engine=db_engine,
                DBInstanceClass=instance_class,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned list
of
                                       engine versions to those that are compatible
with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.
```

```
        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by the
DB instance.
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
```

```
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDBCluster

- Criado B ClusterParameterGroup
- Criado B ClusterSnapshot
- CreateDBInstance
- DeleteDBCluster
- Banco de dados excluído ClusterParameterGroup
- DeleteDBInstance
- DB descrito ClusterParameterGroups
- DB descrito ClusterParameters
- DB descrito ClusterSnapshots
- DescribeDBClusters
- DB descrito EngineVersions
- DescribeDBInstances
- DescribeOrderableDB InstanceOptions
- Modificar banco de dados ClusterParameterGroup

Exemplos de Auto Scaling usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_autoscaling(autoscaling_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon EC2 Auto Scaling client
 and list
    some of the Auto Scaling groups in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param auto-scaling_client: A Boto3 Amazon EC2 Auto Scaling client object.
    """
    print(
        "Hello, Amazon EC2 Auto Scaling! Let's list up to ten of you Auto Scaling
 groups:"
    )
    response = autoscaling_client.describe_auto_scaling_groups()
    groups = response.get("AutoScalingGroups", [])
    if groups:
        for group in groups:
            print(f"\t{group['AutoScalingGroupName']}:
 {group['AvailabilityZones']}")
    else:
        print("There are no Auto Scaling groups in your account.")


if __name__ == "__main__":
    hello_autoscaling(boto3.client("autoscaling"))
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Anexar um grupo de destino ELB ao grupo do Auto Scaling

O exemplo de código a seguir mostra como anexar um grupo destino ELB a um grupo Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
```

```
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group %s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )
```

- Para obter detalhes da API, consulte a AttachLoadBalancerTargetGroupsReferência da API AWSSDK for Python (Boto3).

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def create_group(
        self, group_name, group_zones, launch_template_name, min_size, max_size
    ):
        """
        Creates an Auto Scaling group.

        :param group_name: The name to give to the group.
        :param group_zones: The Availability Zones in which instances can be
created.
```

```
        :param launch_template_name: The name of an existing Amazon EC2 launch
template.
                                     The launch template specifies the configuration
of
                                     instances that are created by auto scaling
activities.
        :param min_size: The minimum number of active instances in the group.
        :param max_size: The maximum number of active instances in the group.
        """
        try:
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=group_name,
                AvailabilityZones=group_zones,
                LaunchTemplate={
                    "LaunchTemplateName": launch_template_name,
                    "Version": "$Default",
                },
                MinSize=min_size,
                MaxSize=max_size,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar o tamanho mínimo de um grupo do Auto Scaling para zero, encerrar todas as instâncias no grupo e excluir o grupo.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
```

```
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
```

```
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] == "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def disable_metrics(self, group_name):
        """
        Stops CloudWatch metric collection for the Auto Scaling group.

        :param group_name: The name of the group.
        """
        try:
            self.autoscaling_client.disable_metrics_collection(
                AutoScalingGroupName=group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't disable metrics %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionReferência da API AWSSDK for Python (Boto3).

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def enable_metrics(self, group_name, metrics):
        """
        Enables CloudWatch metric collection for Amazon EC2 Auto Scaling activities.

        :param group_name: The name of the group to enable.
        :param metrics: A list of metrics to collect.
        """
        try:
            self.autoscaling_client.enable_metrics_collection(
```

```
                AutoScalingGroupName=group_name, Metrics=metrics,
 Granularity="1Minute"
            )
        except ClientError as err:
            logger.error(
                "Couldn't enable metrics on %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionReferência da API AWSSDK for Python (Boto3).

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informação sobre grupos do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def describe_group(self, group_name):
        """
```

```
        Gets information about an Auto Scaling group.

        :param group_name: The name of the group to look up.
        :return: Information about the group, if found.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[group_name]
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            groups = response.get("AutoScalingGroups", [])
            return groups[0] if len(groups) > 0 else None
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsReferência da API AWSSDK for Python (Boto3).

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""
```

```
    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def describe_instances(self, instance_ids):
        """
        Gets information about instances.

        :param instance_ids: A list of instance IDs to look up.
        :return: Information about instances, or an empty list if none are found.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_instances(
                InstanceIds=instance_ids
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe instances %s. Here's why: %s: %s",
                instance_ids,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["AutoScalingInstances"]
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesReferência da API AWSSDK for Python (Boto3).

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informação sobre atividades do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def describe_scaling_activities(self, group_name):
        """
        Gets information about scaling activities for the group. Scaling activities
        are things like instances stopping or starting in response to user requests
        or capacity changes.

        :param group_name: The name of the group to look up.
        :return: The list of scaling activities for the group, ordered with the most
                 recent activity first.
        """
        try:
            response = self.autoscaling_client.describe_scaling_activities(
                AutoScalingGroupName=group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe scaling activities %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Activities"]
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesReferência da API AWSSDK for Python (Boto3).

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo de Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def set_desired_capacity(self, group_name, capacity):
        """
        Sets the desired capacity of the group. Amazon EC2 Auto Scaling tries to
 keep the
        number of running instances equal to the desired capacity.

        :param group_name: The name of the group to update.
        :param capacity: The desired number of running instances.
        """
        try:
            self.autoscaling_client.set_desired_capacity(
                AutoScalingGroupName=group_name,
```

```
                DesiredCapacity=capacity,
                HonorCooldown=False,
            )
        except ClientError as err:
            logger.error(
                "Couldn't set desired capacity %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a SetDesiredCapacityReferência da API AWSSDK for Python (Boto3).

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def terminate_instance(self, instance_id, decrease_capacity):
        """
```

```
        Stops an instance.

        :param instance_id: The ID of the instance to stop.
        :param decrease_capacity: Specifies whether to decrease the desired capacity
                                  of the group. When passing True for this
parameter,
                                  you can stop an instance without having a
replacement
                                  instance start when the desired capacity threshold
is
                                  crossed.
        :return: The scaling activity that occurs in response to this action.
        """
        try:
            response =
self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id,
ShouldDecrementDesiredCapacity=decrease_capacity
            )
        except ClientError as err:
            logger.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Activity"]
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo de Auto Scaling.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScalingWrapper:
    """Encapsulates Amazon EC2 Auto Scaling actions."""

    def __init__(self, autoscaling_client):
        """
        :param autoscaling_client: A Boto3 Amazon EC2 Auto Scaling client.
        """
        self.autoscaling_client = autoscaling_client


    def update_group(self, group_name, **kwargs):
        """
        Updates an Auto Scaling group.

        :param group_name: The name of the group to update.
        :param kwargs: Keyword arguments to pass through to the service.
        """
        try:
            self.autoscaling_client.update_auto_scaling_group(
                AutoScalingGroupName=group_name, **kwargs
            )
        except ClientError as err:
            logger.error(
                "Couldn't update group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer, param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
```

```
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways to
make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide book,
movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each contain
a Python web server."
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
'{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)
```

```
        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when an
 instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
 script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
 and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In production,
 the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged credentials.
\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
 assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
 Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
            f"Creating an EC2 Auto Scaling group that maintains three EC2 instances,
 each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
 starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or continue
 with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
 The target group\n"
```

```
            "defines how the load balancer connects to instances. The load balancer
provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port is
open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for your
default VPC must\n"
                    "allows access from this computer. You can either add it
automatically from this\n"
                    "example or add it yourself using the AWS Management Console.\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
{sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
```

```
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging from
 your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
                "Couldn't get a successful response from the load balancer endpoint.
 Troubleshoot by\n"
                "manually verifying that your VPC and security group are configured
 correctly and that\n"
                "you can successfully make a GET request to the load balancer
 endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
```

```
                "\nSee the current state of the service by selecting one of the
following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health check
to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
```

```
            "\nThis part of the demonstration shows how to toggle different parts of
the system\n"
            "to create situations where the web service fails, and shows how using a
resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations by
querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't check
for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with a
somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns a
static response.\n"
            f"The service still reports as healthy because health checks are still
shallow.\n"
```

```
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in the
target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a profile
that contains\n"
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
```

```
            "the deep health check is only for ELB routing and not for Auto Scaling
instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling group
when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect when
one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
            "\nBecause the instances in this demo are controlled by an auto scaler,
the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
starting, sending a GET\n"
            "request to the web service continues to get a successful recommendation
response because\n"
            "the load balancer routes requests to the healthy instances. After the
replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
running and healthy.\n"
```

```
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean all
 instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient service.
\n"
            "To keep things tidy and to avoid unwanted charges on your account, we
 can clean up all AWS resources\n"
            "that were created for this demo."
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ", q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            )
```

```
def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM policies
 and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer, param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
```

```
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
```

```
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        """
        as_client = boto3.client("autoscaling")
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
```

```
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is assumed
by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as AmazonSSMManagedInstanceCore
to grant
                                     use of Systems Manager to send commands to the
instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
role_name)
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
 profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to role
\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response = self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
 {instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the profile
 is
```

```
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
```

```
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
```

```
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.

        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.", self.key_pair_name
            )
        except Exception as err:
```

```
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a permissions
policy
                                     to create and attach to the instance profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
```

```
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template {self.launch_template_name}:
{err}."
                )
        return template


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
```

```
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template {self.launch_template_name}:
{err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones


    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
```

```
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group {self.group_name}:
{err}"
            )
        else:
```

```
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.

        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group %s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
```

```
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] == "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
stop..."
                    )
```

```
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
                log.info("No groups found named %s, nothing to do.",
 self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
 {err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
```

```
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress from
this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
```

```
                        log.info(
                            "The inbound rule does not appear to be open to either
this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or to a
prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
```

```
                f"Couldn't authorize ingress to {sec_group_id} on port {port} from
{ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
load balancer.
        :param load_balancer_name: The name of the load balancer.
```

```
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by this
class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group specifies
how
```

```
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened times
and
        lower thresholds. In production, you might want to decrease the sensitivity
of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
```

```
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
```

```
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
```

```
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint, retrying..."
                )
                retries -= 1
```

```
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets: {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books, movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client
```

```
    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended, such
as
        Book or Movie, and a range key named 'ItemId' that, combined with the
MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5, "WriteCapacityUnits":
5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
```

```
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name, data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}: {err}"
            )

    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters to
 drive
    the demonstration of resilient architecture, such as failure of a dependency or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                            service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
```

```
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile
  - CreateLaunchTemplate
  - CreateListener
  - CreateLoadBalancer
  - CreateTargetGroup
  - DeleteAutoScalingGroup
  - DeleteInstanceProfile
  - DeleteLaunchTemplate
  - DeleteLoadBalancer
  - DeleteTargetGroup
  - DescribeAutoScalingGroups
  - DescribeAvailabilityZones
  - DescribeIamInstanceProfileAssociations
  - DescribeInstances

- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
def run_scenario(as_wrapper, svc_helper):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
```

```
    print("-" * 88)
    print(
        "Welcome to the Amazon EC2 Auto Scaling demo for managing groups and
instances."
    )
    print("-" * 88)

    print(
        "This example requires a launch template that specifies how to create\n"
        "EC2 instances. You can use an existing template or create a new one."
    )
    template_name = q.ask(
        "Enter the name of an existing launch template or press Enter to create a
new one: "
    )
    template = None
    if template_name:
        template = svc_helper.get_template(template_name)
    if template is None:
        inst_type = "t1.micro"
        ami_id = "ami-0ca285d4c2cda3300"
        print("Let's create a launch template with the following specifications:")
        print(f"\tInstanceType: {inst_type}")
        print(f"\tAMI ID: {ami_id}")
        template_name = q.ask("Enter a name for the template: ", q.non_empty)
        template = svc_helper.create_template(template_name, inst_type, ami_id)
    print("-" * 88)

    print("Let's create an Auto Scaling group.")
    group_name = q.ask("Enter a name for the group: ", q.non_empty)
    zones = svc_helper.get_availability_zones()
    print("EC2 instances can be created in the following Availability Zones:")
    for index, zone in enumerate(zones):
        print(f"\t{index+1}. {zone}")
    print(f"\t{len(zones)+1}. All zones")
    zone_sel = q.ask(
        "Which zone do you want to use? ", q.is_int, q.in_range(1, len(zones) + 1)
    )
    group_zones = [zones[zone_sel - 1]] if zone_sel <= len(zones) else zones
    print(f"Creating group {group_name}...")
    as_wrapper.create_group(group_name, group_zones, template_name, 1, 1)
    wait(10)
    group = as_wrapper.describe_group(group_name)
```

```
    print("Created group:")
    pp(group)
    print("Waiting for instance to start...")
    wait_for_group(group_name, as_wrapper)
    print("-" * 88)

    use_metrics = q.ask(
        "Do you want to collect metrics about Amazon EC2 Auto Scaling during this
demo (y/n)? ",
        q.is_yesno,
    )
    if use_metrics:
        as_wrapper.enable_metrics(
            group_name,
            [
                "GroupMinSize",
                "GroupMaxSize",
                "GroupDesiredCapacity",
                "GroupInServiceInstances",
                "GroupTotalInstances",
            ],
        )
        print(f"Metrics enabled for {group_name}.")
    print("-" * 88)

    print(f"Let's update the maximum number of instances in {group_name} from 1 to
3.")
    q.ask("Press Enter when you're ready.")
    as_wrapper.update_group(group_name, MaxSize=3)
    group = as_wrapper.describe_group(group_name)
    print("The group still has one running instance, but can have up to three:")
    print_simplified_group(group)
    print("-" * 88)

    print(f"Let's update the desired capacity of {group_name} from 1 to 2.")
    q.ask("Press Enter when you're ready.")
    as_wrapper.set_desired_capacity(group_name, 2)
    wait(10)
    group = as_wrapper.describe_group(group_name)
    print("Here's the current state of the group:")
    print_simplified_group(group)
    print("-" * 88)
    print("Waiting for the new instance to start...")
    instance_ids = wait_for_group(group_name, as_wrapper)
```

```
    print("-" * 88)

    print(f"Let's terminate one of the instances in {group_name}.")
    print("Because the desired capacity is 2, another instance will start.")
    print("The currently running instances are:")
    for index, inst_id in enumerate(instance_ids):
        print(f"\t{index+1}. {inst_id}")
    inst_sel = q.ask(
        "Which instance do you want to stop? ",
        q.is_int,
        q.in_range(1, len(instance_ids) + 1),
    )
    print(f"Stopping {instance_ids[inst_sel-1]}...")
    as_wrapper.terminate_instance(instance_ids[inst_sel - 1], False)
    wait(10)
    group = as_wrapper.describe_group(group_name)
    print(f"Here's the state of {group_name}:")
    print_simplified_group(group)
    print("Waiting for the scaling activities to complete...")
    wait_for_group(group_name, as_wrapper)
    print("-" * 88)

    print(f"Let's get a report of scaling activities for {group_name}.")
    q.ask("Press Enter when you're ready.")
    activities = as_wrapper.describe_scaling_activities(group_name)
    print(
        f"Found {len(activities)} activities.\n"
        f"Activities are ordered with the most recent one first:"
    )
    for act in activities:
        pp(act)
    print("-" * 88)

    if use_metrics:
        print("Let's look at CloudWatch metrics.")
        metric_namespace = "AWS/AutoScaling"
        metric_dimensions = [{"Name": "AutoScalingGroupName", "Value": group_name}]
        print(f"The following metrics are enabled for {group_name}:")
        done = False
        while not done:
            metrics = svc_helper.get_metrics(metric_namespace, metric_dimensions)
            for index, metric in enumerate(metrics):
                print(f"\t{index+1}. {metric.name}")
            print(f"\t{len(metrics)+1}. None")
```

```
            metric_sel = q.ask(
                "Which metric do you want to see? ",
                q.is_int,
                q.in_range(1, len(metrics) + 1),
            )
            if metric_sel < len(metrics) + 1:
                span = 5
                metric = metrics[metric_sel - 1]
                print(f"Over the last {span} minutes, {metric.name} recorded:")
                # CloudWatch metric times are in the UTC+0 time zone.
                now = datetime.now(timezone.utc)
                metric_data = svc_helper.get_metric_statistics(
                    metric_dimensions, metric, now - timedelta(minutes=span), now
                )
                pp(metric_data)
                if not q.ask("Do you want to see another metric (y/n)? ",
q.is_yesno):
                    done = True
            else:
                done = True

    print(f"Let's clean up.")
    q.ask("Press Enter when you're ready.")
    if use_metrics:
        print(f"Stopping metrics collection for {group_name}.")
        as_wrapper.disable_metrics(group_name)

    print(
        "You must terminate all instances in the group before you can delete the
group."
    )
    print("Set minimum size to 0.")
    as_wrapper.update_group(group_name, MinSize=0)
    group = as_wrapper.describe_group(group_name)
    instance_ids = [inst["InstanceId"] for inst in group["Instances"]]
    for inst_id in instance_ids:
        print(f"Stopping {inst_id}.")
        as_wrapper.terminate_instance(inst_id, True)
    print("Waiting for instances to stop...")
    wait_for_instances(instance_ids, as_wrapper)
    print(f"Deleting {group_name}.")
    as_wrapper.delete_group(group_name)
    print("-" * 88)
```

```
    if template is not None:
        if q.ask(
            f"Do you want to delete launch template {template_name} used in this
 demo (y/n)? "
        ):
            svc_helper.delete_template(template_name)
            print("Template deleted.")

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        wrapper = AutoScalingWrapper(boto3.client("autoscaling"))
        helper = ServiceHelper(boto3.client("ec2"), boto3.resource("cloudwatch"))
        run_scenario(wrapper, helper)
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

Definir as funções que são chamadas pelo cenário para gerenciar modelos e métricas de lançamento. Essas funções envolvem o Amazon EC2 e CloudWatch as ações.

```
class ServiceHelper:
    """Encapsulates Amazon EC2 and CloudWatch actions for the example."""

    def __init__(self, ec2_client, cloudwatch_resource):
        """
        :param ec2_client: A Boto3 Amazon EC2 client.
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.ec2_client = ec2_client
        self.cloudwatch_resource = cloudwatch_resource

    def get_template(self, template_name):
        """
        Gets a launch template. Launch templates specify configuration for instances
        that are launched by Amazon EC2 Auto Scaling.

        :param template_name: The name of the template to look up.
        :return: The template, if it exists.
        """
```

```
        try:
            response = self.ec2_client.describe_launch_templates(
                LaunchTemplateNames=[template_name]
            )
            template = response["LaunchTemplates"][0]
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                logger.warning("Launch template %s does not exist.", template_name)
            else:
                logger.error(
                    "Couldn't verify launch template %s. Here's why: %s: %s",
                    template_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return template

    def create_template(self, template_name, inst_type, ami_id):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.

        :param template_name: The name to give to the template.
        :param inst_type: The type of the instance, such as t1.micro.
        :param ami_id: The ID of the Amazon Machine Image (AMI) to use when creating
                       an instance.
        :return: Information about the newly created template.
        """
        try:
            response = self.ec2_client.create_launch_template(
                LaunchTemplateName=template_name,
                LaunchTemplateData={"InstanceType": inst_type, "ImageId": ami_id},
            )
            template = response["LaunchTemplate"]
        except ClientError as err:
            logger.error(
                "Couldn't create launch template %s. Here's why: %s: %s",
                template_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return template

    def delete_template(self, template_name):
        """
        Deletes a launch template.

        :param template_name: The name of the template to delete.
        """
        try:
            self.ec2_client.delete_launch_template(LaunchTemplateName=template_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete launch template %s. Here's why: %s: %s",
                template_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            logger.error(
                "Couldn't get availability zones. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return zones

    def get_metrics(self, namespace, dimensions):
        """
```

```
        Gets a list of CloudWatch metrics filtered by namespace and dimensions.

        :param namespace: The namespace of the metrics to look up.
        :param dimensions: The dimensions of the metrics to look up.
        :return: The list of metrics.
        """
        try:
            metrics = list(
                self.cloudwatch_resource.metrics.filter(
                    Namespace=namespace, Dimensions=dimensions
                )
            )
        except ClientError as err:
            logger.error(
                "Couldn't get metrics for %s, %s. Here's why: %s: %s",
                namespace,
                dimensions,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return metrics

    @staticmethod
    def get_metric_statistics(dimensions, metric, start, end):
        """
        Gets statistics for a CloudWatch metric within a specified time span.

        :param dimensions: The dimensions of the metric.
        :param metric: The metric to look up.
        :param start: The start of the time span for retrieved metrics.
        :param end: The end of the time span for retrieved metrics.
        :return: The list of data points found for the specified metric.
        """
        try:
            response = metric.get_statistics(
                Dimensions=dimensions,
                StartTime=start,
                EndTime=end,
                Period=60,
                Statistics=["Sum"],
            )
            data = response["Datapoints"]
```

```
        except ClientError as err:
            logger.error(
                "Couldn't get statistics for metric %s. Here's why: %s: %s",
                metric.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return data


def print_simplified_group(group):
    """
    Prints a subset of data for an Auto Scaling group.
    """
    print(group["AutoScalingGroupName"])
    print(f"\tLaunch template: {group['LaunchTemplate']['LaunchTemplateName']}")
    print(
        f"\tMin: {group['MinSize']}, Max: {group['MaxSize']}, Desired:
 {group['DesiredCapacity']}"
    )
    if group["Instances"]:
        print(f"\tInstances:")
        for inst in group["Instances"]:
            print(f"\t\t{inst['InstanceId']}: {inst['LifecycleState']}")


def wait_for_group(group_name, as_wrapper):
    """
    Waits for instances to start or stop in an Auto Scaling group.
    Prints the data for each instance after scaling activities are complete.
    """
    group = as_wrapper.describe_group(group_name)
    instance_ids = [i["InstanceId"] for i in group["Instances"]]
    return wait_for_instances(instance_ids, as_wrapper)


def wait_for_instances(instance_ids, as_wrapper):
    """
    Waits for instances to start or stop in an Auto Scaling group.
    Prints the data for each instance after scaling activities are complete.
    """
    ready = False
```

```
    instances = []
    while not ready:
        instances = as_wrapper.describe_instances(instance_ids) if instance_ids else
[]
        if all([x["LifecycleState"] in ["Terminated", "InService"] for x in
instances]):
            ready = True
        else:
            wait(10)
    if instances:
        print(
            f"Here are the details of the instance{'s' if len(instances) > 1 else
''}:"
        )
        for instance in instances:
            pp(instance)
    return instance_ids
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity
  - TerminateInstanceInAutoScalingGroup
  - UpdateAutoScalingGroup

Exemplos do Amazon Bedrock usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Listar modelos de base Amazon Bedrock disponíveis

O exemplo de código a seguir mostra como listar modelos de base disponíveis do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os modelos de base disponíveis do Amazon Bedrock.

```
    def list_foundation_models(self):
        """
        List the available Amazon Bedrock foundation models.

        :return: The list of available bedrock foundation models.
        """

        try:
            response = self.bedrock_client.list_foundation_models()
            models = response["modelSummaries"]
```

```
            logger.info("Got %s foundation models.", len(models))
        except ClientError:
            logger.error("Couldn't list foundation models.")
            raise
        else:
            return models
```

- Para obter detalhes da API, consulte a ListFoundationModelsReferência da API AWSSDK for Python (Boto3).

Cenários

Organize aplicativos generativos de IA com Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.

- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos do Amazon Bedrock Runtime usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Geração de imagens com o Image Generator G1 do Amazon Titan

O exemplo de código a seguir mostra como invocar o modelo Amazon Titan Image Generator G1 no Amazon Bedrock para geração de imagens.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Amazon Titan Image Generator G1 para gerar imagens.

```
    def invoke_titan_image(self, prompt, seed):
        """
        Invokes the Titan Image model to create an image using the input provided in
 the request body.

        :param prompt: The prompt that you want Amazon Titan to use for image
 generation.
        :param seed: Random noise seed (range: 0 to 2147483647)
        :return: Base64-encoded inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Titan Image models
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
titan-image.html

            request = json.dumps(
                {
                    "taskType": "TEXT_IMAGE",
                    "textToImageParams": {"text": prompt},
                    "imageGenerationConfig": {
                        "numberOfImages": 1,
                        "quality": "standard",
                        "cfgScale": 8.0,
                        "height": 512,
                        "width": 512,
                        "seed": seed,
                    },
                }
            )
```

```
            response = self.bedrock_runtime_client.invoke_model(
                modelId="amazon.titan-image-generator-v1", body=request
            )

            response_body = json.loads(response["body"].read())
            base64_image_data = response_body["images"][0]

            return base64_image_data

        except ClientError:
            logger.error("Couldn't invoke Titan Image generator")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Geração de imagens com o Stable Diffusion XL da Stability.ai

O exemplo de código a seguir mostra como invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para a geração de imagens.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    def invoke_stable_diffusion(self, prompt, seed, style_preset=None):
        """
        Invokes the Stability.ai Stable Diffusion XL model to create an image using
        the input provided in the request body.

        :param prompt: The prompt that you want Stable Diffusion  to use for image
generation.
```

```
        :param seed: Random noise seed (omit this option or use 0 for a random seed)
        :param style_preset: Pass in a style preset to guide the image model towards
                             a particular style.
        :return: Base64-encoded inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and available style_presets of Stable
 Diffusion models refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
stability-diffusion.html

            body = {
                "text_prompts": [{"text": prompt}],
                "seed": seed,
                "cfg_scale": 10,
                "steps": 30,
            }

            if style_preset:
                body["style_preset"] = style_preset

            response = self.bedrock_runtime_client.invoke_model(
                modelId="stability.stable-diffusion-xl", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            base64_image_data = response_body["artifacts"][0]["base64"]

            return base64_image_data

        except ClientError:
            logger.error("Couldn't invoke Stable Diffusion XL")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Geração de texto com o Jurassic-2 da AI21 Labs

O exemplo de código a seguir mostra como invocar o modelo AI21 Labs Jurassic-2 no Amazon Bedrock para geração de texto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Jurassic-2 da AI21 Labs para gerar texto.

```
    def invoke_jurassic2(self, prompt):
        """
        Invokes the AI21 Labs Jurassic-2 large-language model to run an inference
        using the input provided in the request body.

        :param prompt: The prompt that you want Jurassic-2 to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for AI21 Labs Jurassic-2,
 refer to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
jurassic2.html

            body = {
                "prompt": prompt,
                "temperature": 0.5,
                "maxTokens": 200,
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="ai21.j2-mid-v1", body=json.dumps(body)
            )
```

```
            response_body = json.loads(response["body"].read())
            completion = response_body["completions"][0]["data"]["text"]

            return completion

        except ClientError:
            logger.error("Couldn't invoke Jurassic-2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto.

```
    def invoke_claude(self, prompt):
        """
        Invokes the Anthropic Claude 2 model to run an inference using the input
        provided in the request body.

        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
formats.
```

```
            # For the format, ranges, and default values for Anthropic Claude, refer
 to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html

            # Claude requires you to enclose the prompt as follows:
            enclosed_prompt = "Human: " + prompt + "\n\nAssistant:"

            body = {
                "prompt": enclosed_prompt,
                "max_tokens_to_sample": 200,
                "temperature": 0.5,
                "stop_sequences": ["\n\nHuman:"],
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="anthropic.claude-v2", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            completion = response_body["completion"]

            return completion

        except ClientError:
            logger.error("Couldn't invoke Anthropic Claude")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Geração de texto com Claude 2 da Anthropic com fluxo de resposta

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto com fluxo de resposta.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo Claude 2 da Anthropic e processe o fluxo de resposta.

```
    async def invoke_model_with_response_stream(self, prompt):
        """
        Invokes the Anthropic Claude 2 model to run an inference and process the
 response stream.

        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
 formats.
            # For the format, ranges, and default values for Anthropic Claude, refer
 to:
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
claude.html

            # Claude requires you to enclose the prompt as follows:
            enclosed_prompt = "Human: " + prompt + "\n\nAssistant:"

            body = {
                "prompt": enclosed_prompt,
                "max_tokens_to_sample": 1024,
                "temperature": 0.5,
                "stop_sequences": ["\n\nHuman:"],
            }

            response =
 self.bedrock_runtime_client.invoke_model_with_response_stream(
                modelId="anthropic.claude-v2", body=json.dumps(body)
            )

            for event in response.get("body"):
```

```
                chunk = json.loads(event["chunk"]["bytes"])["completion"]
                yield chunk

        except ClientError:
            logger.error("Couldn't invoke Anthropic Claude v2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelWithResponseStreamReferência da API AWSSDK for Python (Boto3).

Geração de texto com o Chat Llama 2 da Meta

O exemplo de código a seguir mostra como invocar o modelo Chat Llama 2 da Meta no Amazon Bedrock para geração de texto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo base do Chat Llama 2 da Meta para gerar texto.

```
    def invoke_llama2(self, prompt):
        """
        Invokes the Meta Llama 2 large-language model to run an inference
        using the input provided in the request body.

        :param prompt: The prompt that you want Llama 2 to complete.
        :return: Inference response from the model.
        """

        try:
            # The different model providers have individual request and response
formats.
            # For the format, ranges, and default values for Meta Llama 2 Chat,
refer to:
```

```
            # https://docs.aws.amazon.com/bedrock/latest/userguide/model-parameters-
meta.html

            body = {
                "prompt": prompt,
                "temperature": 0.5,
                "top_p": 0.9,
                "max_gen_len": 512,
            }

            response = self.bedrock_runtime_client.invoke_model(
                modelId="meta.llama2-13b-chat-v1", body=json.dumps(body)
            )

            response_body = json.loads(response["body"].read())
            completion = response_body["generation"]

            return completion

        except ClientError:
            logger.error("Couldn't invoke Llama 2")
            raise
```

- Para obter detalhes da API, consulte a InvokeModelReferência da API AWSSDK for Python (Boto3).

Cenários

Criar uma aplicação de playground para interagir com os modelos de base do Amazon Bedrock

O exemplo de código a seguir mostra como criar playgrounds para interagir com os modelos de base da Amazon Bedrock por meio de diferentes modalidades.

SDK para Python (Boto3)

O modelo de base (FM) Python Playground é um aplicativo de amostra em Python/FastAPI que mostra como usar o Amazon Bedrock com Python. Este exemplo mostra como os desenvolvedores Python podem usar o Amazon Bedrock para criar aplicativos habilitados para IA generativa. Você pode testar e interagir com os modelos de base do Amazon Bedrock usando os três playgrounds a seguir:

- Um playground de texto.
- Um playground de conversa.
- Um playground de imagens.

O exemplo também lista e exibe os modelos de base aos quais tem-se acesso, junto com suas características. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock Runtime

Organize aplicativos generativos de IA com Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.

- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de agentes para Amazon Bedrock usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with Agents for Amazon Bedrock.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Crie um agente do

O exemplo de código a seguir mostra como criar um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um agente do .

```
    def create_agent(self, agent_name, foundation_model, role_arn, instruction):
        """
        Creates an agent that orchestrates interactions between foundation models,
        data sources, software applications, user conversations, and APIs to carry
        out tasks to help customers.

        :param agent_name: A name for the agent.
        :param foundation_model: The foundation model to be used for orchestration
by the agent.
        :param role_arn: The ARN of the IAM role with permissions needed by the
agent.
        :param instruction: Instructions that tell the agent what it should do and
how it should
                            interact with users.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """
        try:
            response = self.client.create_agent(
                agentName=agent_name,
                foundationModel=foundation_model,
                agentResourceRoleArn=role_arn,
                instruction=instruction,
            )
        except ClientError as e:
            logger.error(f"Error: Couldn't create agent. Here's why: {e}")
            raise
        else:
            return response["agent"]
```

- Para obter detalhes da API, consulte a CreateAgentReferência da API AWSSDK for Python (Boto3).

Criar um grupo de ações do agente

O exemplo de código a seguir mostra como criar um grupo de ações do agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um grupo de ação do agente.

```
    def create_agent_action_group(
        self, name, description, agent_id, agent_version, function_arn, api_schema
    ):
        """
        Creates an action group for an agent. An action group defines a set of
actions that an
        agent should carry out for the customer.

        :param name: The name to give the action group.
        :param description: The description of the action group.
        :param agent_id: The unique identifier of the agent for which to create the
action group.
        :param agent_version: The version of the agent for which to create the
action group.
        :param function_arn: The ARN of the Lambda function containing the business
logic that is
                             carried out upon invoking the action.
        :param api_schema: Contains the OpenAPI schema for the action group.
        :return: Details about the action group that was created.
        """
        try:
            response = self.client.create_agent_action_group(
                actionGroupName=name,
                description=description,
                agentId=agent_id,
```

```
                agentVersion=agent_version,
                actionGroupExecutor={"lambda": function_arn},
                apiSchema={"payload": api_schema},
            )
            agent_action_group = response["agentActionGroup"]
        except ClientError as e:
            logger.error(f"Error: Couldn't create agent action group. Here's why:
{e}")
            raise
        else:
            return agent_action_group
```

- Para obter detalhes da API, consulte a CreateAgentActionGroupReferência da API AWSSDK for Python (Boto3).

Criar um alias de agente

O exemplo de código a seguir mostra como criar um alias de agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um alias de agente.

```
    def create_agent_alias(self, name, agent_id):
        """
        Creates an alias of an agent that can be used to deploy the agent.

        :param name: The name of the alias.
        :param agent_id: The unique identifier of the agent.
        :return: Details about the alias that was created.
        """
        try:
            response = self.client.create_agent_alias(
                agentAliasName=name, agentId=agent_id
```

```
            )
            agent_alias = response["agentAlias"]
        except ClientError as e:
            logger.error(f"Couldn't create agent alias. {e}")
            raise
        else:
            return agent_alias
```

- Para obter detalhes da API, consulte a CreateAgentAliasReferência da API AWSSDK for Python (Boto3).

Excluir um agente

O exemplo de código a seguir mostra como excluir um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um agente.

```
    def delete_agent(self, agent_id):
        """
        Deletes an Amazon Bedrock agent.

        :param agent_id: The unique identifier of the agent to delete.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """

        try:
            response = self.client.delete_agent(
                agentId=agent_id, skipResourceInUseCheck=False
            )
        except ClientError as e:
            logger.error(f"Couldn't delete agent. {e}")
```

```
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteAgentReferência da API AWSSDK for Python (Boto3).

Excluir um alias de agente

O exemplo de código a seguir mostra como excluir um alias de agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um alias de agente.

```
    def delete_agent_alias(self, agent_id, agent_alias_id):
        """
        Deletes an alias of an Amazon Bedrock agent.

        :param agent_id: The unique identifier of the agent that the alias belongs
to.
        :param agent_alias_id: The unique identifier of the alias to delete.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """

        try:
            response = self.client.delete_agent_alias(
                agentId=agent_id, agentAliasId=agent_alias_id
            )
        except ClientError as e:
            logger.error(f"Couldn't delete agent alias. {e}")
            raise
        else:
```

```
            return response
```

- Para obter detalhes da API, consulte a DeleteAgentAliasReferência da API AWSSDK for Python (Boto3).

Obter informações sobre um agente

O exemplo de código a seguir mostra como obter informações sobre um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um agente.

```
    def get_agent(self, agent_id, log_error=True):
        """
        Gets information about an agent.

        :param agent_id: The unique identifier of the agent.
        :param log_error: Whether to log any errors that occur when getting the
agent.
                          If True, errors will be logged to the logger. If False,
errors
                          will still be raised, but not logged.
        :return: The information about the requested agent.
        """

        try:
            response = self.client.get_agent(agentId=agent_id)
            agent = response["agent"]
        except ClientError as e:
            if log_error:
                logger.error(f"Couldn't get agent {agent_id}. {e}")
            raise
        else:
```

```
        return agent
```

- Para obter detalhes da API, consulte a GetAgentReferência da API AWSSDK for Python (Boto3).

Listar os grupos de ação de um agente

O exemplo de código a seguir mostra como listar os grupos de ação de um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os grupos de ação de um agente.

```
    def list_agent_action_groups(self, agent_id, agent_version):
        """
        List the action groups for a version of an Amazon Bedrock Agent.

        :param agent_id: The unique identifier of the agent.
        :param agent_version: The version of the agent.
        :return: The list of action group summaries for the version of the agent.
        """

        try:
            action_groups = []

            paginator = self.client.get_paginator("list_agent_action_groups")
            for page in paginator.paginate(
                agentId=agent_id,
                agentVersion=agent_version,
                PaginationConfig={"PageSize": 10},
            ):
                action_groups.extend(page["actionGroupSummaries"])
```

```
        except ClientError as e:
            logger.error(f"Couldn't list action groups. {e}")
            raise
        else:
            return action_groups
```

- Para obter detalhes da API, consulte a ListAgentActionGroupsReferência da API AWSSDK for Python (Boto3).

Listar os agentes

O exemplo de código a seguir mostra como listar os agentes do Amazon Bedrock que pertencem a uma conta.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste os agentes que pertencem a uma conta.

```
    def list_agents(self):
        """
        List the available Amazon Bedrock Agents.

        :return: The list of available bedrock agents.
        """

        try:
            all_agents = []

            paginator = self.client.get_paginator("list_agents")
            for page in paginator.paginate(PaginationConfig={"PageSize": 10}):
                all_agents.extend(page["agentSummaries"])

        except ClientError as e:
```

```
            logger.error(f"Couldn't list agents. {e}")
            raise
        else:
            return all_agents
```

- Para obter detalhes da API, consulte a ListAgentsReferência da API AWSSDK for Python (Boto3).

Listar as bases de conhecimento associadas a um agente

O exemplo de código a seguir mostra como listar as bases de conhecimento associadas a um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste as bases de conhecimento associadas a um agente.

```
    def list_agent_knowledge_bases(self, agent_id, agent_version):
        """
        List the knowledge bases associated with a version of an Amazon Bedrock
Agent.

        :param agent_id: The unique identifier of the agent.
        :param agent_version: The version of the agent.
        :return: The list of knowledge base summaries for the version of the agent.
        """

        try:
            knowledge_bases = []

            paginator = self.client.get_paginator("list_agent_knowledge_bases")
            for page in paginator.paginate(
                agentId=agent_id,
                agentVersion=agent_version,
```

```
                PaginationConfig={"PageSize": 10},
            ):
                knowledge_bases.extend(page["agentKnowledgeBaseSummaries"])

        except ClientError as e:
            logger.error(f"Couldn't list knowledge bases. {e}")
            raise
        else:
            return knowledge_bases
```

- Para obter detalhes da API, consulte a ListAgentKnowledgeBasesReferência da API AWSSDK for Python (Boto3).

Preparar um agente

O exemplo de código a seguir mostra como preparar um agente do Amazon Bedrock para testes internos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Prepare um agente para testes internos.

```
    def prepare_agent(self, agent_id):
        """
        Creates a DRAFT version of the agent that can be used for internal testing.

        :param agent_id: The unique identifier of the agent to prepare.
        :return: The response from Agents for Bedrock if successful, otherwise
raises an exception.
        """
        try:
            prepared_agent_details = self.client.prepare_agent(agentId=agent_id)
        except ClientError as e:
            logger.error(f"Couldn't prepare agent. {e}")
```

```
            raise
        else:
            return prepared_agent_details
```

- Para obter detalhes da API, consulte a PrepareAgentReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e invocar um agente

O código de exemplo a seguir mostra como:

- Crie um perfil de execução para o agente.
- Crie o agente e implante uma versão de RASCUNHO.
- Crie uma função do Lambda que implante os recursos do agente.
- Crie um grupo de ação que conecte o agente à função do Lambda.
- Implante o agente totalmente configurado.
- Invoque o agente com prompts fornecidos pelo usuário.
- Exclua todos os recursos criados.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e invoque um agente.

```
REGION = "us-east-1"
ROLE_POLICY_NAME = "agent_permissions"


class BedrockAgentScenarioWrapper:
```

```
    """Runs a scenario that shows how to get started using Agents for Amazon
Bedrock."""

    def __init__(
        self, bedrock_agent_client, runtime_client, lambda_client, iam_resource,
postfix
    ):
        self.iam_resource = iam_resource
        self.lambda_client = lambda_client
        self.bedrock_agent_runtime_client = runtime_client
        self.postfix = postfix

        self.bedrock_wrapper = BedrockAgentWrapper(bedrock_agent_client)

        self.agent = None
        self.agent_alias = None
        self.agent_role = None
        self.prepared_agent_details = None
        self.lambda_role = None
        self.lambda_function = None

    def run_scenario(self):
        print("=" * 88)
        print("Welcome to the Amazon Bedrock Agents demo.")
        print("=" * 88)

        # Query input from user
        print("Let's start with creating an agent:")
        print("-" * 40)
        name, foundation_model = self._request_name_and_model_from_user()
        print("-" * 40)

        # Create an execution role for the agent
        self.agent_role = self._create_agent_role(foundation_model)

        # Create the agent
        self.agent = self._create_agent(name, foundation_model)

        # Prepare a DRAFT version of the agent
        self.prepared_agent_details = self._prepare_agent()

        # Create the agent's Lambda function
        self.lambda_function = self._create_lambda_function()
```

```
        # Configure permissions for the agent to invoke the Lambda function
        self._allow_agent_to_invoke_function()
        self._let_function_accept_invocations_from_agent()

        # Create an action group to connect the agent with the Lambda function
        self._create_agent_action_group()

        # If the agent has been modified or any components have been added, prepare
the agent again
        components = [self._get_agent()]
        components += self._get_agent_action_groups()
        components += self._get_agent_knowledge_bases()

        latest_update = max(component["updatedAt"] for component in components)
        if latest_update > self.prepared_agent_details["preparedAt"]:
            self.prepared_agent_details = self._prepare_agent()

        # Create an agent alias
        self.agent_alias = self._create_agent_alias()

        # Test the agent
        self._chat_with_agent(self.agent_alias)

        print("=" * 88)
        print("Thanks for running the demo!\n")

        if q.ask("Do you want to delete the created resources? [y/N] ", q.is_yesno):
            self._delete_resources()
            print("=" * 88)
            print(
                "All demo resources have been deleted. Thanks again for running the
demo!"
            )
        else:
            self._list_resources()
            print("=" * 88)
            print("Thanks again for running the demo!")

    def _request_name_and_model_from_user(self):
        existing_agent_names = [
            agent["agentName"] for agent in self.bedrock_wrapper.list_agents()
        ]

        while True:
```

```
            name = q.ask("Enter an agent name: ", self.is_valid_agent_name)
            if name.lower() not in [n.lower() for n in existing_agent_names]:
                break
            print(
                f"Agent {name} conflicts with an existing agent. Please use a
different name."
            )

        models = ["anthropic.claude-instant-v1", "anthropic.claude-v2"]
        model_id = models[
            q.choose("Which foundation model would you like to use? ", models)
        ]

        return name, model_id

    def _create_agent_role(self, model_id):
        role_name = f"AmazonBedrockExecutionRoleForAgents_{self.postfix}"
        model_arn = f"arn:aws:bedrock:{REGION}::foundation-model/{model_id}*"

        print("Creating an an execution role for the agent...")

        try:
            role = self.iam_resource.create_role(
                RoleName=role_name,
                AssumeRolePolicyDocument=json.dumps(
                    {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
                                "Principal": {"Service": "bedrock.amazonaws.com"},
                                "Action": "sts:AssumeRole",
                            }
                        ],
                    }
                ),
            )

            role.Policy(ROLE_POLICY_NAME).put(
                PolicyDocument=json.dumps(
                    {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
```

```
                                "Effect": "Allow",
                                "Action": "bedrock:InvokeModel",
                                "Resource": model_arn,
                            }
                        ],
                    }
                )
            )
        except ClientError as e:
            logger.error(f"Couldn't create role {role_name}. Here's why: {e}")
            raise

        return role

    def _create_agent(self, name, model_id):
        print("Creating the agent...")

        instruction = """
            You are a friendly chat bot. You have access to a function called that
returns
            information about the current date and time. When responding with date
or time,
            please make sure to add the timezone UTC.
            """
        agent = self.bedrock_wrapper.create_agent(
            agent_name=name,
            foundation_model=model_id,
            instruction=instruction,
            role_arn=self.agent_role.arn,
        )
        self._wait_for_agent_status(agent["agentId"], "NOT_PREPARED")

        return agent

    def _prepare_agent(self):
        print("Preparing the agent...")

        agent_id = self.agent["agentId"]
        prepared_agent_details = self.bedrock_wrapper.prepare_agent(agent_id)
        self._wait_for_agent_status(agent_id, "PREPARED")

        return prepared_agent_details

    def _create_lambda_function(self):
```

```
        print("Creating the Lambda function...")

        function_name = f"AmazonBedrockExampleFunction_{self.postfix}"

        self.lambda_role = self._create_lambda_role()

        try:
            deployment_package = self._create_deployment_package(function_name)

            lambda_function = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="Lambda function for Amazon Bedrock example",
                Runtime="python3.11",
                Role=self.lambda_role.arn,
                Handler=f"{function_name}.lambda_handler",
                Code={"ZipFile": deployment_package},
                Publish=True,
            )

            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)

        except ClientError as e:
            logger.error(
                f"Couldn't create Lambda function {function_name}. Here's why: {e}"
            )
            raise

        return lambda_function

    def _create_lambda_role(self):
        print("Creating an execution role for the Lambda function...")

        role_name = f"AmazonBedrockExecutionRoleForLambda_{self.postfix}"

        try:
            role = self.iam_resource.create_role(
                RoleName=role_name,
                AssumeRolePolicyDocument=json.dumps(
                    {
                        "Version": "2012-10-17",
                        "Statement": [
                            {
                                "Effect": "Allow",
```

```
                                "Principal": {"Service": "lambda.amazonaws.com"},
                                "Action": "sts:AssumeRole",
                            }
                        ],
                    }
                ),
            )
            role.attach_policy(
                PolicyArn="arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole"
            )
            print(f"Created role {role_name}")
        except ClientError as e:
            logger.error(f"Couldn't create role {role_name}. Here's why: {e}")
            raise

        print("Waiting for the execution role to be fully propagated...")
        wait(10)

        return role

    def _allow_agent_to_invoke_function(self):
        policy = self.iam_resource.RolePolicy(
            self.agent_role.role_name, ROLE_POLICY_NAME
        )
        doc = policy.policy_document
        doc["Statement"].append(
            {
                "Effect": "Allow",
                "Action": "lambda:InvokeFunction",
                "Resource": self.lambda_function["FunctionArn"],
            }
        )
        self.agent_role.Policy(ROLE_POLICY_NAME).put(PolicyDocument=json.dumps(doc))

    def _let_function_accept_invocations_from_agent(self):
        try:
            self.lambda_client.add_permission(
                FunctionName=self.lambda_function["FunctionName"],
                SourceArn=self.agent["agentArn"],
                StatementId="BedrockAccess",
                Action="lambda:InvokeFunction",
                Principal="bedrock.amazonaws.com",
            )
```

```
        except ClientError as e:
            logger.error(
                f"Couldn't grant Bedrock permission to invoke the Lambda function.
Here's why: {e}"
            )
            raise

    def _create_agent_action_group(self):
        print("Creating an action group for the agent...")

        try:
            with open("./scenario_resources/api_schema.yaml") as file:
                self.bedrock_wrapper.create_agent_action_group(
                    name="current_date_and_time",
                    description="Gets the current date and time.",
                    agent_id=self.agent["agentId"],
                    agent_version=self.prepared_agent_details["agentVersion"],
                    function_arn=self.lambda_function["FunctionArn"],
                    api_schema=json.dumps(yaml.safe_load(file)),
                )
        except ClientError as e:
            logger.error(f"Couldn't create agent action group. Here's why: {e}")
            raise

    def _get_agent(self):
        return self.bedrock_wrapper.get_agent(self.agent["agentId"])

    def _get_agent_action_groups(self):
        return self.bedrock_wrapper.list_agent_action_groups(
            self.agent["agentId"], self.prepared_agent_details["agentVersion"]
        )

    def _get_agent_knowledge_bases(self):
        return self.bedrock_wrapper.list_agent_knowledge_bases(
            self.agent["agentId"], self.prepared_agent_details["agentVersion"]
        )

    def _create_agent_alias(self):
        print("Creating an agent alias...")

        agent_alias_name = "test_agent_alias"
        agent_alias = self.bedrock_wrapper.create_agent_alias(
            agent_alias_name, self.agent["agentId"]
        )
```

```
        self._wait_for_agent_status(self.agent["agentId"], "PREPARED")

        return agent_alias

    def _wait_for_agent_status(self, agent_id, status):
        while self.bedrock_wrapper.get_agent(agent_id)["agentStatus"] != status:
            wait(2)

    def _chat_with_agent(self, agent_alias):
        print("-" * 88)
        print("The agent is ready to chat.")
        print("Try asking for the date or time. Type 'exit' to quit.")

        # Create a unique session ID for the conversation
        session_id = uuid.uuid4().hex

        while True:
            prompt = q.ask("Prompt: ", q.non_empty)

            if prompt == "exit":
                break

            response = asyncio.run(self._invoke_agent(agent_alias, prompt,
session_id))

            print(f"Agent: {response}")

    async def _invoke_agent(self, agent_alias, prompt, session_id):
        response = self.bedrock_agent_runtime_client.invoke_agent(
            agentId=self.agent["agentId"],
            agentAliasId=agent_alias["agentAliasId"],
            sessionId=session_id,
            inputText=prompt,
        )

        completion = ""

        for event in response.get("completion"):
            chunk = event["chunk"]
            completion += chunk["bytes"].decode()

        return completion
```

```
    def _delete_resources(self):
        if self.agent:
            agent_id = self.agent["agentId"]

            if self.agent_alias:
                agent_alias_id = self.agent_alias["agentAliasId"]
                print("Deleting agent alias...")
                self.bedrock_wrapper.delete_agent_alias(agent_id, agent_alias_id)

            print("Deleting agent...")
            agent_status = self.bedrock_wrapper.delete_agent(agent_id)
["agentStatus"]
            while agent_status == "DELETING":
                wait(5)
                try:
                    agent_status = self.bedrock_wrapper.get_agent(
                        agent_id, log_error=False
                    )["agentStatus"]
                except ClientError as err:
                    if err.response["Error"]["Code"] == "ResourceNotFoundException":
                        agent_status = "DELETED"

        if self.lambda_function:
            name = self.lambda_function["FunctionName"]
            print(f"Deleting function '{name}'...")
            self.lambda_client.delete_function(FunctionName=name)

        if self.agent_role:
            print(f"Deleting role '{self.agent_role.role_name}'...")
            self.agent_role.Policy(ROLE_POLICY_NAME).delete()
            self.agent_role.delete()

        if self.lambda_role:
            print(f"Deleting role '{self.lambda_role.role_name}'...")
            for policy in self.lambda_role.attached_policies.all():
                policy.detach_role(RoleName=self.lambda_role.role_name)
            self.lambda_role.delete()

    def _list_resources(self):
        print("-" * 40)
        print(f"Here is the list of created resources in '{REGION}'.")
        print("Make sure you delete them once you're done to avoid unnecessary
 costs.")
        if self.agent:
```

```
            print(f"Bedrock Agent:   {self.agent['agentName']}")
        if self.lambda_function:
            print(f"Lambda function: {self.lambda_function['FunctionName']}")
        if self.agent_role:
            print(f"IAM role:        {self.agent_role.role_name}")
        if self.lambda_role:
            print(f"IAM role:        {self.lambda_role.role_name}")

    @staticmethod
    def is_valid_agent_name(answer):
        valid_regex = r"^[a-zA-Z0-9_-]{1,100}$"
        return (
            answer
            if answer and len(answer) <= 100 and re.match(valid_regex, answer)
            else None,
            "I need a name for the agent, please. Valid characters are a-z, A-Z,
 0-9, _ (underscore) and - (hyphen).",
        )

    @staticmethod
    def _create_deployment_package(function_name):
        buffer = io.BytesIO()
        with zipfile.ZipFile(buffer, "w") as zipped:
            zipped.write(
                "./scenario_resources/lambda_function.py", f"{function_name}.py"
            )
        buffer.seek(0)
        return buffer.read()


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    postfix = "".join(
        random.choice(string.ascii_lowercase + "0123456789") for _ in range(8)
    )
    scenario = BedrockAgentScenarioWrapper(
        bedrock_agent_client=boto3.client(
            service_name="bedrock-agent", region_name=REGION
        ),
        runtime_client=boto3.client(
            service_name="bedrock-agent-runtime", region_name=REGION
        ),
        lambda_client=boto3.client(service_name="lambda", region_name=REGION),
```

```
        iam_resource=boto3.resource("iam"),
        postfix=postfix,
    )
    try:
        scenario.run_scenario()
    except Exception as e:
        logging.exception(f"Something went wrong with the demo. Here's what: {e}")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAgent
  - CreateAgentActionGroup
  - CreateAgentAlias
  - DeleteAgent
  - DeleteAgentAlias
  - GetAgent
  - ListAgentActionGroups
  - ListAgentKnowledgeBases
  - ListAgents
  - PrepareAgent

Organize aplicativos generativos de IA com Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.

- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de agentes para Amazon Bedrock Runtime usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with Agents for Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Invocar um agente

O exemplo de código a seguir mostra como invocar um agente do Amazon Bedrock.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque um agente.

```
    def invoke_agent(self, agent_id, agent_alias_id, session_id, prompt):
        """
        Sends a prompt for the agent to process and respond to.

        :param agent_id: The unique identifier of the agent to use.
        :param agent_alias_id: The alias of the agent to use.
        :param session_id: The unique identifier of the session. Use the same value
across requests
                           to continue the same conversation.
        :param prompt: The prompt that you want Claude to complete.
        :return: Inference response from the model.
        """

        try:
            response = self.agents_runtime_client.invoke_agent(
                agentId=agent_id,
                agentAliasId=agent_alias_id,
```

```
            sessionId=session_id,
            inputText=prompt,
        )

        completion = ""

        for event in response.get("completion"):
            chunk = event["chunk"]
            completion = completion + chunk["bytes"].decode()

    except ClientError as e:
        logger.error(f"Couldn't invoke agent. {e}")
        raise

    return completion
```

- Para obter detalhes da API, consulte a InvokeAgentReferência da API AWSSDK for Python (Boto3).

Cenários

Organize aplicativos generativos de IA com Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.

- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

CloudFront exemplos usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with CloudFront.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter a configuração de distribuição.

O exemplo de código a seguir mostra como obter a configuração de CloudFront distribuição da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""

    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client


    def update_distribution(self):
        distribution_id = input(
            "This script updates the comment for a CloudFront distribution.\n"
            "Enter a CloudFront distribution ID: "
        )

        distribution_config_response =
 self.cloudfront_client.get_distribution_config(
            Id=distribution_id
        )
        distribution_config = distribution_config_response["DistributionConfig"]
        distribution_etag = distribution_config_response["ETag"]

        distribution_config["Comment"] = input(
            f"\nThe current comment for distribution {distribution_id} is "
            f"'{distribution_config['Comment']}'.\n"
            f"Enter a new comment: "
        )
```

```
        self.cloudfront_client.update_distribution(
            DistributionConfig=distribution_config,
            Id=distribution_id,
            IfMatch=distribution_etag,
        )
        print("Done!")
```

- Para obter detalhes da API, consulte a GetDistributionConfigReferência da API AWSSDK for Python (Boto3).

Listar distribuições

O exemplo de código a seguir mostra como listar as CloudFront distribuições da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""

    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client


    def list_distributions(self):
        print("CloudFront distributions:\n")
        distributions = self.cloudfront_client.list_distributions()
        if distributions["DistributionList"]["Quantity"] > 0:
            for distribution in distributions["DistributionList"]["Items"]:
                print(f"Domain: {distribution['DomainName']}")
```

```
                print(f"Distribution Id: {distribution['Id']}")
                print(
                    f"Certificate Source: "
                    f"{distribution['ViewerCertificate']['CertificateSource']}"
                )
                if distribution["ViewerCertificate"]["CertificateSource"] == "acm":
                    print(
                        f"Certificate: {distribution['ViewerCertificate']
['Certificate']}"
                    )
                print("")
        else:
            print("No CloudFront distributions detected.")
```

- Para obter detalhes da API, consulte a ListDistributionsReferência da API AWSSDK for Python (Boto3).

Atualizar uma distribuição

O exemplo de código a seguir mostra como atualizar uma CloudFront distribuição da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudFrontWrapper:
    """Encapsulates Amazon CloudFront operations."""

    def __init__(self, cloudfront_client):
        """
        :param cloudfront_client: A Boto3 CloudFront client
        """
        self.cloudfront_client = cloudfront_client
```

```
    def update_distribution(self):
        distribution_id = input(
            "This script updates the comment for a CloudFront distribution.\n"
            "Enter a CloudFront distribution ID: "
        )

        distribution_config_response =
self.cloudfront_client.get_distribution_config(
            Id=distribution_id
        )
        distribution_config = distribution_config_response["DistributionConfig"]
        distribution_etag = distribution_config_response["ETag"]

        distribution_config["Comment"] = input(
            f"\nThe current comment for distribution {distribution_id} is "
            f"'{distribution_config['Comment']}'.\n"
            f"Enter a new comment: "
        )
        self.cloudfront_client.update_distribution(
            DistributionConfig=distribution_config,
            Id=distribution_id,
            IfMatch=distribution_etag,
        )
        print("Done!")
```

- Para obter detalhes da API, consulte a UpdateDistributionReferência da API AWSSDK for Python (Boto3).

CloudWatch exemplos usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def create_metric_alarm(
        self,
        metric_namespace,
        metric_name,
        alarm_name,
        stat_type,
        period,
```

```
        eval_periods,
        threshold,
        comparison_op,
    ):
        """
        Creates an alarm that watches a metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :param alarm_name: The name of the alarm.
        :param stat_type: The type of statistic the alarm watches.
        :param period: The period in which metric data are grouped to calculate
                       statistics.
        :param eval_periods: The number of periods that the metric must be over the
                             alarm threshold before the alarm is set into an alarmed
                             state.
        :param threshold: The threshold value to compare against the metric
statistic.
        :param comparison_op: The comparison operation used to compare the threshold
                              against the metric.
        :return: The newly created alarm.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
            alarm = metric.put_alarm(
                AlarmName=alarm_name,
                Statistic=stat_type,
                Period=period,
                EvaluationPeriods=eval_periods,
                Threshold=threshold,
                ComparisonOperator=comparison_op,
            )
            logger.info(
                "Added alarm %s to track metric %s.%s.",
                alarm_name,
                metric_namespace,
                metric_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't add alarm %s to metric %s.%s",
                alarm_name,
                metric_namespace,
                metric_name,
```

```
            )
            raise
        else:
            return alarm
```

- Para obter detalhes da API, consulte a PutMetricAlarmReferência da API AWSSDK for Python (Boto3).

Excluir alarmes

O exemplo de código a seguir mostra como excluir os CloudWatch alarmes da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def delete_metric_alarms(self, metric_namespace, metric_name):
        """
        Deletes all of the alarms that are currently watching the specified metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
            metric.alarms.delete()
```

```
            logger.info(
                "Deleted alarms for metric %s.%s.", metric_namespace, metric_name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete alarms for metric %s.%s.",
                metric_namespace,
                metric_name,
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteAlarmsReferência da API AWSSDK for Python (Boto3).

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def get_metric_alarms(self, metric_namespace, metric_name):
```

```
        """
        Gets the alarms that are currently watching the specified metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :returns: An iterator that yields the alarms.
        """
        metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
        alarm_iter = metric.alarms.all()
        logger.info("Got alarms for metric %s.%s.", metric_namespace, metric_name)
        return alarm_iter
```

- Para obter detalhes da API, consulte a DescribeAlarmsForMetricReferência da API AWSSDK for Python (Boto3).

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def enable_alarm_actions(self, alarm_name, enable):
        """
        Enables or disables actions on the specified alarm. Alarm actions can be
```

```
        used to send notifications or automate responses when an alarm enters a
        particular state.

        :param alarm_name: The name of the alarm.
        :param enable: When True, actions are enabled for the alarm. Otherwise, they
                       disabled.
        """
        try:
            alarm = self.cloudwatch_resource.Alarm(alarm_name)
            if enable:
                alarm.enable_actions()
            else:
                alarm.disable_actions()
            logger.info(
                "%s actions for alarm %s.",
                "Enabled" if enable else "Disabled",
                alarm_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't %s actions alarm %s.",
                "enable" if enable else "disable",
                alarm_name,
            )
            raise
```

- Para obter detalhes da API, consulte a DisableAlarmActionsReferência da API AWSSDK for Python (Boto3).

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def enable_alarm_actions(self, alarm_name, enable):
        """
        Enables or disables actions on the specified alarm. Alarm actions can be
        used to send notifications or automate responses when an alarm enters a
        particular state.

        :param alarm_name: The name of the alarm.
        :param enable: When True, actions are enabled for the alarm. Otherwise, they
                       disabled.
        """
        try:
            alarm = self.cloudwatch_resource.Alarm(alarm_name)
            if enable:
                alarm.enable_actions()
            else:
                alarm.disable_actions()
            logger.info(
                "%s actions for alarm %s.",
                "Enabled" if enable else "Disabled",
                alarm_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't %s actions alarm %s.",
                "enable" if enable else "disable",
                alarm_name,
            )
            raise
```

- Para obter detalhes da API, consulte a EnableAlarmActionsReferência da API AWSSDK for Python (Boto3).

Obter estatísticas de métricas

O exemplo de código a seguir mostra como obter estatísticas CloudWatch métricas da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def get_metric_statistics(self, namespace, name, start, end, period,
 stat_types):
        """
        Gets statistics for a metric within a specified time span. Metrics are
 grouped
        into the specified period.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param start: The UTC start time of the time span to retrieve.
        :param end: The UTC end time of the time span to retrieve.
        :param period: The period, in seconds, in which to group metrics. The period
                       must match the granularity of the metric, which depends on
                       the metric's age. For example, metrics that are older than
                       three hours have a one-minute granularity, so the period must
                       be at least 60 and must be a multiple of 60.
        :param stat_types: The type of statistics to retrieve, such as average value
                           or maximum value.
        :return: The retrieved statistics for the metric.
        """
        try:
```

```
            metric = self.cloudwatch_resource.Metric(namespace, name)
            stats = metric.get_statistics(
                StartTime=start, EndTime=end, Period=period, Statistics=stat_types
            )
            logger.info(
                "Got %s statistics for %s.", len(stats["Datapoints"]),
 stats["Label"]
            )
        except ClientError:
            logger.exception("Couldn't get statistics for %s.%s.", namespace, name)
            raise
        else:
            return stats
```

- Para obter detalhes da API, consulte a GetMetricStatisticsReferência da API AWSSDK for Python (Boto3).

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource
```

```
    def list_metrics(self, namespace, name, recent=False):
        """
        Gets the metrics within a namespace that have the specified name.
        If the metric has no dimensions, a single metric is returned.
        Otherwise, metrics for all dimensions are returned.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param recent: When True, only metrics that have been active in the last
                       three hours are returned.
        :return: An iterator that yields the retrieved metrics.
        """
        try:
            kwargs = {"Namespace": namespace, "MetricName": name}
            if recent:
                kwargs["RecentlyActive"] = "PT3H"  # List past 3 hours only
            metric_iter = self.cloudwatch_resource.metrics.filter(**kwargs)
            logger.info("Got metrics for %s.%s.", namespace, name)
        except ClientError:
            logger.exception("Couldn't get metrics for %s.%s.", namespace, name)
            raise
        else:
            return metric_iter
```

- Para obter detalhes da API, consulte a ListMetricsReferência da API AWSSDK for Python (Boto3).

Inserir um conjunto de dados em uma métrica

O exemplo de código a seguir mostra como colocar um conjunto de dados em uma CloudWatch métrica da Amazon.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data_set(self, namespace, name, timestamp, unit, data_set):
        """
        Sends a set of data to CloudWatch for a metric. All of the data in the set
        have the same timestamp and unit.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param timestamp: The UTC timestamp for the metric.
        :param unit: The unit of the metric.
        :param data_set: The set of data to send. This set is a dictionary that
                         contains a list of values and a list of corresponding
 counts.
                         The value and count lists must be the same length.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[
                    {
                        "MetricName": name,
                        "Timestamp": timestamp,
                        "Values": data_set["values"],
                        "Counts": data_set["counts"],
                        "Unit": unit,
                    }
                ],
            )
            logger.info("Put data set for metric %s.%s.", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data set for metric %s.%s.", namespace,
 name)
            raise
```

- Para obter detalhes da API, consulte a PutMetricDataReferência da API AWSSDK for Python (Boto3).

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data(self, namespace, name, value, unit):
        """
        Sends a single data value to CloudWatch for a metric. This metric is given
        a timestamp of the current UTC time.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param value: The value of the metric.
        :param unit: The unit of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
```

```
            metric.put_data(
                Namespace=namespace,
                MetricData=[{"MetricName": name, "Value": value, "Unit": unit}],
            )
            logger.info("Put data for metric %s.%s", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data for metric %s.%s", namespace, name)
            raise
```

- Para obter detalhes da API, consulte a PutMetricDataReferência da API AWSSDK for Python (Boto3).

Cenários

Gerencie métricas e alarmes

O código de exemplo a seguir mostra como:

- Crie um alarme para observar uma CloudWatch métrica.
- Inserir dados em uma métrica e acionar o alarme.
- Obtenha dados do alarme.
- Exclua o alarme.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as CloudWatch operações.

```
from datetime import datetime, timedelta
import logging
from pprint import pprint
import random
import time
```

```
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class CloudWatchWrapper:
    """Encapsulates Amazon CloudWatch functions."""

    def __init__(self, cloudwatch_resource):
        """
        :param cloudwatch_resource: A Boto3 CloudWatch resource.
        """
        self.cloudwatch_resource = cloudwatch_resource


    def put_metric_data_set(self, namespace, name, timestamp, unit, data_set):
        """
        Sends a set of data to CloudWatch for a metric. All of the data in the set
        have the same timestamp and unit.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param timestamp: The UTC timestamp for the metric.
        :param unit: The unit of the metric.
        :param data_set: The set of data to send. This set is a dictionary that
                         contains a list of values and a list of corresponding
 counts.
                         The value and count lists must be the same length.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[
                    {
                        "MetricName": name,
                        "Timestamp": timestamp,
                        "Values": data_set["values"],
                        "Counts": data_set["counts"],
                        "Unit": unit,
                    }
                ],
            )
```

```
            logger.info("Put data set for metric %s.%s.", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data set for metric %s.%s.", namespace,
name)
            raise


    def create_metric_alarm(
        self,
        metric_namespace,
        metric_name,
        alarm_name,
        stat_type,
        period,
        eval_periods,
        threshold,
        comparison_op,
    ):
        """
        Creates an alarm that watches a metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :param alarm_name: The name of the alarm.
        :param stat_type: The type of statistic the alarm watches.
        :param period: The period in which metric data are grouped to calculate
                       statistics.
        :param eval_periods: The number of periods that the metric must be over the
                             alarm threshold before the alarm is set into an alarmed
                             state.
        :param threshold: The threshold value to compare against the metric
statistic.
        :param comparison_op: The comparison operation used to compare the threshold
                              against the metric.
        :return: The newly created alarm.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
            alarm = metric.put_alarm(
                AlarmName=alarm_name,
                Statistic=stat_type,
                Period=period,
                EvaluationPeriods=eval_periods,
                Threshold=threshold,
```

```
                ComparisonOperator=comparison_op,
            )
            logger.info(
                "Added alarm %s to track metric %s.%s.",
                alarm_name,
                metric_namespace,
                metric_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't add alarm %s to metric %s.%s",
                alarm_name,
                metric_namespace,
                metric_name,
            )
            raise
        else:
            return alarm


    def put_metric_data(self, namespace, name, value, unit):
        """
        Sends a single data value to CloudWatch for a metric. This metric is given
        a timestamp of the current UTC time.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param value: The value of the metric.
        :param unit: The unit of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            metric.put_data(
                Namespace=namespace,
                MetricData=[{"MetricName": name, "Value": value, "Unit": unit}],
            )
            logger.info("Put data for metric %s.%s", namespace, name)
        except ClientError:
            logger.exception("Couldn't put data for metric %s.%s", namespace, name)
            raise


    def get_metric_statistics(self, namespace, name, start, end, period,
stat_types):
```

```
        """
        Gets statistics for a metric within a specified time span. Metrics are
grouped
        into the specified period.

        :param namespace: The namespace of the metric.
        :param name: The name of the metric.
        :param start: The UTC start time of the time span to retrieve.
        :param end: The UTC end time of the time span to retrieve.
        :param period: The period, in seconds, in which to group metrics. The period
                       must match the granularity of the metric, which depends on
                       the metric's age. For example, metrics that are older than
                       three hours have a one-minute granularity, so the period must
                       be at least 60 and must be a multiple of 60.
        :param stat_types: The type of statistics to retrieve, such as average value
                           or maximum value.
        :return: The retrieved statistics for the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(namespace, name)
            stats = metric.get_statistics(
                StartTime=start, EndTime=end, Period=period, Statistics=stat_types
            )
            logger.info(
                "Got %s statistics for %s.", len(stats["Datapoints"]),
stats["Label"]
            )
        except ClientError:
            logger.exception("Couldn't get statistics for %s.%s.", namespace, name)
            raise
        else:
            return stats


    def get_metric_alarms(self, metric_namespace, metric_name):
        """
        Gets the alarms that are currently watching the specified metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        :returns: An iterator that yields the alarms.
        """
        metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
        alarm_iter = metric.alarms.all()
```

```
        logger.info("Got alarms for metric %s.%s.", metric_namespace, metric_name)
        return alarm_iter


    def delete_metric_alarms(self, metric_namespace, metric_name):
        """
        Deletes all of the alarms that are currently watching the specified metric.

        :param metric_namespace: The namespace of the metric.
        :param metric_name: The name of the metric.
        """
        try:
            metric = self.cloudwatch_resource.Metric(metric_namespace, metric_name)
            metric.alarms.delete()
            logger.info(
                "Deleted alarms for metric %s.%s.", metric_namespace, metric_name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete alarms for metric %s.%s.",
                metric_namespace,
                metric_name,
            )
            raise
```

Use a classe criada para colocar dados em uma métrica, acionar um alarme que observa a métrica e obter dados do alarme.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon CloudWatch metrics and alarms demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    cw_wrapper = CloudWatchWrapper(boto3.resource("cloudwatch"))

    minutes = 20
    metric_namespace = "doc-example-metric"
    metric_name = "page_views"
```

```
    start = datetime.utcnow() - timedelta(minutes=minutes)
    print(
        f"Putting data into metric {metric_namespace}.{metric_name} spanning the "
        f"last {minutes} minutes."
    )
    for offset in range(0, minutes):
        stamp = start + timedelta(minutes=offset)
        cw_wrapper.put_metric_data_set(
            metric_namespace,
            metric_name,
            stamp,
            "Count",
            {
                "values": [
                    random.randint(bound, bound * 2)
                    for bound in range(offset + 1, offset + 11)
                ],
                "counts": [random.randint(1, offset + 1) for _ in range(10)],
            },
        )

    alarm_name = "high_page_views"
    period = 60
    eval_periods = 2
    print(f"Creating alarm {alarm_name} for metric {metric_name}.")
    alarm = cw_wrapper.create_metric_alarm(
        metric_namespace,
        metric_name,
        alarm_name,
        "Maximum",
        period,
        eval_periods,
        100,
        "GreaterThanThreshold",
    )
    print(f"Alarm ARN is {alarm.alarm_arn}.")
    print(f"Current alarm state is: {alarm.state_value}.")

    print(
        f"Sending data to trigger the alarm. This requires data over the threshold "
        f"for {eval_periods} periods of {period} seconds each."
    )
    while alarm.state_value == "INSUFFICIENT_DATA":
        print("Sending data for the metric.")
```

```
        cw_wrapper.put_metric_data(
            metric_namespace, metric_name, random.randint(100, 200), "Count"
        )
        alarm.load()
        print(f"Current alarm state is: {alarm.state_value}.")
        if alarm.state_value == "INSUFFICIENT_DATA":
            print(f"Waiting for {period} seconds...")
            time.sleep(period)
        else:
            print("Wait for a minute for eventual consistency of metric data.")
            time.sleep(period)
            if alarm.state_value == "OK":
                alarm.load()
                print(f"Current alarm state is: {alarm.state_value}.")

    print(
        f"Getting data for metric {metric_namespace}.{metric_name} during timespan "
        f"of {start} to {datetime.utcnow()} (times are UTC)."
    )
    stats = cw_wrapper.get_metric_statistics(
        metric_namespace,
        metric_name,
        start,
        datetime.utcnow(),
        60,
        ["Average", "Minimum", "Maximum"],
    )
    print(
        f"Got {len(stats['Datapoints'])} data points for metric "
        f"{metric_namespace}.{metric_name}."
    )
    pprint(sorted(stats["Datapoints"], key=lambda x: x["Timestamp"]))

    print(f"Getting alarms for metric {metric_name}.")
    alarms = cw_wrapper.get_metric_alarms(metric_namespace, metric_name)
    for alarm in alarms:
        print(f"Alarm {alarm.name} is currently in state {alarm.state_value}.")

    print(f"Deleting alarms for metric {metric_name}.")
    cw_wrapper.delete_metric_alarms(metric_namespace, metric_name)

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeleteAlarms
  - DescribeAlarmsForMetric
  - DisableAlarmActions
  - EnableAlarmActions
  - GetMetricStatistics
  - ListMetrics
  - PutMetricAlarm
  - PutMetricData

CloudWatch Exemplos de registros usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with CloudWatch Logs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Iniciar uma sessão Live Tail

O exemplo de código a seguir mostra como iniciar uma sessão do Live Tail para um grupo de logs/fluxo de logs existente.

SDK para Python (Boto3)

Inclua os arquivos necessários.

```
import boto3
import time
from datetime import datetime
```

Inicie a sessão do Live Tail.

```
    # Initialize the client
    client = boto3.client('logs')

    start_time = time.time()

    try:
        response = client.start_live_tail(
            logGroupIdentifiers=log_group_identifiers,
            logStreamNames=log_streams,
            logEventFilterPattern=filter_pattern
        )
        event_stream = response['responseStream']
        # Handle the events streamed back in the response
        for event in event_stream:
            # Set a timeout to close the stream.
            # This will end the Live Tail session.
            if (time.time() - start_time >= 10):
                event_stream.close()
                break
            # Handle when session is started
            if 'sessionStart' in event:
                session_start_event = event['sessionStart']
                print(session_start_event)
            # Handle when log event is given in a session update
            elif 'sessionUpdate' in event:
```

```
                log_events = event['sessionUpdate']['sessionResults']
                for log_event in log_events:
                    print('[{date}]
{log}'.format(date=datetime.fromtimestamp(log_event['timestamp']/1000),log=log_event['messa
            else:
                # On-stream exceptions are captured here
                raise RuntimeError(str(event))
    except Exception as e:
        print(e)
```

- Para obter detalhes da API, consulte a StartLiveTailReferência da API AWSSDK for Python (Boto3).

Exemplos de código do Provedor de Identidades Amazon Cognito usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Confirmar um usuário

O exemplo de código a seguir mostra como confirmar um usuário do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def confirm_user_sign_up(self, user_name, confirmation_code):
        """
        Confirms a previously created user. A user must be confirmed before they
        can sign in to Amazon Cognito.

        :param user_name: The name of the user to confirm.
        :param confirmation_code: The confirmation code sent to the user's
 registered
                                  email address.
        :return: True when the confirmation succeeds.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "ConfirmationCode": confirmation_code,
```

```
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            self.cognito_idp_client.confirm_sign_up(**kwargs)
        except ClientError as err:
            logger.error(
                "Couldn't confirm sign up for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return True
```

- Para obter detalhes da API, consulte a ConfirmSignUpReferência da API AWSSDK for Python (Boto3).

Confirme um dispositivo MFA para rastreamento

O exemplo de código a seguir mostra como confirmar um dispositivo de MFA para rastreamento pelo Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
```

```
        :param client_id: The ID of a client application registered with the user
pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def confirm_mfa_device(
        self,
        user_name,
        device_key,
        device_group_key,
        device_password,
        access_token,
        aws_srp,
    ):
        """
        Confirms an MFA device to be tracked by Amazon Cognito. When a device is
        tracked, its key and password can be used to sign in without requiring a new
        MFA code from the MFA application.

        :param user_name: The user that is associated with the device.
        :param device_key: The key of the device, returned by Amazon Cognito.
        :param device_group_key: The group key of the device, returned by Amazon
Cognito.
        :param device_password: The password that is associated with the device.
        :param access_token: The user's access token.
        :param aws_srp: A class that helps with Secure Remote Password (SRP)
                        calculations. The scenario associated with this example uses
                        the warrant package.
        :return: True when the user must confirm the device. Otherwise, False. When
                 False, the device is automatically confirmed and tracked.
        """
        srp_helper = aws_srp.AWSSRP(
            username=user_name,
            password=device_password,
            pool_id="_",
            client_id=self.client_id,
            client_secret=None,
            client=self.cognito_idp_client,
        )
```

```
        device_and_pw = f"{device_group_key}{device_key}:{device_password}"
        device_and_pw_hash = aws_srp.hash_sha256(device_and_pw.encode("utf-8"))
        salt = aws_srp.pad_hex(aws_srp.get_random(16))
        x_value = aws_srp.hex_to_long(aws_srp.hex_hash(salt + device_and_pw_hash))
        verifier = aws_srp.pad_hex(pow(srp_helper.val_g, x_value, srp_helper.big_n))
        device_secret_verifier_config = {
            "PasswordVerifier": base64.standard_b64encode(
                bytearray.fromhex(verifier)
            ).decode("utf-8"),
            "Salt":
base64.standard_b64encode(bytearray.fromhex(salt)).decode("utf-8"),
        }
        try:
            response = self.cognito_idp_client.confirm_device(
                AccessToken=access_token,
                DeviceKey=device_key,
                DeviceSecretVerifierConfig=device_secret_verifier_config,
            )
            user_confirm = response["UserConfirmationNecessary"]
        except ClientError as err:
            logger.error(
                "Couldn't confirm mfa device %s. Here's why: %s: %s",
                device_key,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return user_confirm
```

- Para obter detalhes da API, consulte a ConfirmDeviceReferência da API AWSSDK for Python (Boto3).

Obter um token para associar uma aplicação de MFA a um usuário

O exemplo de código a seguir mostra como obter um token para associar uma aplicação de MFA a um usuário do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def get_mfa_secret(self, session):
        """
        Gets a token that can be used to associate an MFA application with the user.

        :param session: Session information returned from a previous call to
 initiate
                        authentication.
        :return: An MFA token that can be used to set up an MFA application.
        """
        try:
            response =
 self.cognito_idp_client.associate_software_token(Session=session)
        except ClientError as err:
            logger.error(
                "Couldn't get MFA secret. Here's why: %s: %s",
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response
```

- Para obter detalhes da API, consulte a AssociateSoftwareTokenReferência da API AWSSDK for Python (Boto3).

Ter informações sobre um usuário

O exemplo de código a seguir mostra como obter informações sobre um usuário do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret
```

```
    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon Cognito
        to send an email to the specified email address. The email contains a code
that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
whether
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
        :param password: The password for the new user.
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name, response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
```

```
                raise
        return confirmed
```

- Para obter detalhes da API, consulte a AdminGetUserReferência da API AWSSDK for Python (Boto3).

Listar usuários

O exemplo de código a seguir mostra como listar usuários do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def list_users(self):
        """
        Returns a list of the users in the current user pool.
```

```
        :return: The list of users.
        """
        try:
            response =
 self.cognito_idp_client.list_users(UserPoolId=self.user_pool_id)
            users = response["Users"]
        except ClientError as err:
            logger.error(
                "Couldn't list users for %s. Here's why: %s: %s",
                self.user_pool_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return users
```

- Para obter detalhes da API, consulte a ListUsersReferência da API AWSSDK for Python (Boto3).

Reenviar um código de confirmação

O exemplo de código a seguir mostra como reenviar um código de confirmação do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
```

```
        :param client_id: The ID of a client application registered with the user
pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def resend_confirmation(self, user_name):
        """
        Prompts Amazon Cognito to resend an email with a new confirmation code.

        :param user_name: The name of the user who will receive the email.
        :return: Delivery information about where the email is sent.
        """
        try:
            kwargs = {"ClientId": self.client_id, "Username": user_name}
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.resend_confirmation_code(**kwargs)
            delivery = response["CodeDeliveryDetails"]
        except ClientError as err:
            logger.error(
                "Couldn't resend confirmation to %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return delivery
```

- Para obter detalhes da API, consulte a ResendConfirmationCodeReferência da API AWSSDK for Python (Boto3).

Responder aos desafios de autenticação SRP

Os exemplos de código a seguir mostram como responder aos desafios de autenticação SRP do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Faça login com um dispositivo rastreado. Para concluir o login, o cliente deve responder corretamente aos desafios de Secure Remote Password (SRP).

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
        """
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
        with a tracked device lets a user sign in without entering a new MFA code.
```

```
        Signing in with a tracked device requires that the client respond to the SRP
        protocol. The scenario associated with this example uses the warrant package
        to help with SRP calculations.

        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
 {response_init['ChallengeName']}."
                )

            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
```

```
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

- Para obter detalhes da API, consulte a RespondToAuthChallengeReferência da API AWSSDK for Python (Boto3).

Responder a um desafio de autenticação

O exemplo de código a seguir mostra como responder a um desafio de autenticação do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Responda a um desafio de MFA fornecendo um código gerado por uma aplicação de MFA associada.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def respond_to_mfa_challenge(self, user_name, session, mfa_code):
        """
        Responds to a challenge for an MFA code. This completes the second step of
        a two-factor sign-in. When sign-in is successful, it returns an access token
        that can be used to get AWS credentials from Amazon Cognito.

        :param user_name: The name of the user who is signing in.
        :param session: Session information returned from a previous call to
 initiate
                        authentication.
        :param mfa_code: A code generated by the associated MFA application.
        :return: The result of the authentication. When successful, this contains an
                 access token for the user.
```

```
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "ChallengeName": "SOFTWARE_TOKEN_MFA",
                "Session": session,
                "ChallengeResponses": {
                    "USERNAME": user_name,
                    "SOFTWARE_TOKEN_MFA_CODE": mfa_code,
                },
            }
            if self.client_secret is not None:
                kwargs["ChallengeResponses"]["SECRET_HASH"] = self._secret_hash(
                    user_name
                )
            response =
self.cognito_idp_client.admin_respond_to_auth_challenge(**kwargs)
            auth_result = response["AuthenticationResult"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "ExpiredCodeException":
                logger.warning(
                    "Your MFA code has expired or has been used already. You might
have "
                    "to wait a few seconds until your app shows you a new code."
                )
            else:
                logger.error(
                    "Couldn't respond to mfa challenge for %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return auth_result
```

- Para obter detalhes da API, consulte a AdminRespondToAuthChallengeReferência da API AWSSDK for Python (Boto3).

Inscrever um usuário

O exemplo de código a seguir mostra como inscrever um usuário no Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon Cognito
        to send an email to the specified email address. The email contains a code
 that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
 whether
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
        :param password: The password for the new user.
```

```
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name, response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return confirmed
```

- Para obter detalhes da API, consulte a SignUpReferência da API AWSSDK for Python (Boto3).

Iniciar a autenticação

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo mostra como iniciar a autenticação com um dispositivo rastreado. Para concluir o login, o cliente deve responder corretamente aos desafios de Secure Remote Password (SRP).

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
        """
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
        with a tracked device lets a user sign in without entering a new MFA code.
```

```
        Signing in with a tracked device requires that the client respond to the SRP
        protocol. The scenario associated with this example uses the warrant package
        to help with SRP calculations.

        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
 {response_init['ChallengeName']}."
                )

            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
```

```
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

- Para obter detalhes da API, consulte a InitiateAuthReferência da API AWSSDK for Python (Boto3).

Iniciar a autenticação com credenciais de administrador

O exemplo de código a seguir mostra como iniciar a autenticação com o Amazon Cognito e credenciais de administrador.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def start_sign_in(self, user_name, password):
        """
        Starts the sign-in process for a user by using administrator credentials.
        This method of signing in is appropriate for code running on a secure
 server.

        If the user pool is configured to require MFA and this is the first sign-in
        for the user, Amazon Cognito returns a challenge response to set up an
        MFA application. When this occurs, this function gets an MFA secret from
        Amazon Cognito and returns it to the caller.

        :param user_name: The name of the user to sign in.
        :param password: The user's password.
        :return: The result of the sign-in attempt. When sign-in is successful, this
                 returns an access token that can be used to get AWS credentials.
 Otherwise,
```

```
                 Amazon Cognito returns a challenge to set up an MFA application,
                 or a challenge to enter an MFA code from a registered MFA
application.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "AuthFlow": "ADMIN_USER_PASSWORD_AUTH",
                "AuthParameters": {"USERNAME": user_name, "PASSWORD": password},
            }
            if self.client_secret is not None:
                kwargs["AuthParameters"]["SECRET_HASH"] =
self._secret_hash(user_name)
            response = self.cognito_idp_client.admin_initiate_auth(**kwargs)
            challenge_name = response.get("ChallengeName", None)
            if challenge_name == "MFA_SETUP":
                if (
                    "SOFTWARE_TOKEN_MFA"
                    in response["ChallengeParameters"]["MFAS_CAN_SETUP"]
                ):
                    response.update(self.get_mfa_secret(response["Session"]))
                else:
                    raise RuntimeError(
                        "The user pool requires MFA setup, but the user pool is not
"
                        "configured for TOTP MFA. This example requires TOTP MFA."
                    )
        except ClientError as err:
            logger.error(
                "Couldn't start sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response
```

- Para obter detalhes da API, consulte a AdminInitiateAuthReferência da API AWSSDK for Python (Boto3).

Verificar uma aplicação de MFA com um usuário

O exemplo de código a seguir mostra como verificar uma aplicação de MFA com um usuário do Amazon Cognito.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def verify_mfa(self, session, user_code):
        """
        Verify a new MFA application that is associated with a user.

        :param session: Session information returned from a previous call to
 initiate
                        authentication.
```

```
        :param user_code: A code generated by the associated MFA application.
        :return: Status that indicates whether the MFA application is verified.
        """
        try:
            response = self.cognito_idp_client.verify_software_token(
                Session=session, UserCode=user_code
            )
        except ClientError as err:
            logger.error(
                "Couldn't verify MFA. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response
```

- Para obter detalhes da API, consulte a VerifySoftwareTokenReferência da API AWSSDK for Python (Boto3).

Cenários

Inscrever um usuário em um grupo de usuários que exija MFA

O código de exemplo a seguir mostra como:

- Inscreva e confirme um usuário com nome de usuário, senha e endereço de e-mail.
- Configure a autenticação multifator associando uma aplicação de MFA ao usuário.
- Faça login usando uma senha e um código de MFA.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do Amazon Cognito usadas no cenário.

```
class CognitoIdentityProviderWrapper:
    """Encapsulates Amazon Cognito actions"""

    def __init__(self, cognito_idp_client, user_pool_id, client_id,
 client_secret=None):
        """
        :param cognito_idp_client: A Boto3 Amazon Cognito Identity Provider client.
        :param user_pool_id: The ID of an existing Amazon Cognito user pool.
        :param client_id: The ID of a client application registered with the user
 pool.
        :param client_secret: The client secret, if the client has a secret.
        """
        self.cognito_idp_client = cognito_idp_client
        self.user_pool_id = user_pool_id
        self.client_id = client_id
        self.client_secret = client_secret


    def _secret_hash(self, user_name):
        """
        Calculates a secret hash from a user name and a client secret.

        :param user_name: The user name to use when calculating the hash.
        :return: The secret hash.
        """
        key = self.client_secret.encode()
        msg = bytes(user_name + self.client_id, "utf-8")
        secret_hash = base64.b64encode(
            hmac.new(key, msg, digestmod=hashlib.sha256).digest()
        ).decode()
        logger.info("Made secret hash for %s: %s.", user_name, secret_hash)
        return secret_hash

    def sign_up_user(self, user_name, password, user_email):
        """
        Signs up a new user with Amazon Cognito. This action prompts Amazon Cognito
        to send an email to the specified email address. The email contains a code
 that
        can be used to confirm the user.

        When the user already exists, the user status is checked to determine
 whether
```

```
        the user has been confirmed.

        :param user_name: The user name that identifies the new user.
        :param password: The password for the new user.
        :param user_email: The email address for the new user.
        :return: True when the user is already confirmed with Amazon Cognito.
                 Otherwise, false.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "Password": password,
                "UserAttributes": [{"Name": "email", "Value": user_email}],
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.sign_up(**kwargs)
            confirmed = response["UserConfirmed"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "UsernameExistsException":
                response = self.cognito_idp_client.admin_get_user(
                    UserPoolId=self.user_pool_id, Username=user_name
                )
                logger.warning(
                    "User %s exists and is %s.", user_name, response["UserStatus"]
                )
                confirmed = response["UserStatus"] == "CONFIRMED"
            else:
                logger.error(
                    "Couldn't sign up %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return confirmed


    def resend_confirmation(self, user_name):
        """
        Prompts Amazon Cognito to resend an email with a new confirmation code.

        :param user_name: The name of the user who will receive the email.
```

```
        :return: Delivery information about where the email is sent.
        """
        try:
            kwargs = {"ClientId": self.client_id, "Username": user_name}
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            response = self.cognito_idp_client.resend_confirmation_code(**kwargs)
            delivery = response["CodeDeliveryDetails"]
        except ClientError as err:
            logger.error(
                "Couldn't resend confirmation to %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return delivery


    def confirm_user_sign_up(self, user_name, confirmation_code):
        """
        Confirms a previously created user. A user must be confirmed before they
        can sign in to Amazon Cognito.

        :param user_name: The name of the user to confirm.
        :param confirmation_code: The confirmation code sent to the user's
registered
                                  email address.
        :return: True when the confirmation succeeds.
        """
        try:
            kwargs = {
                "ClientId": self.client_id,
                "Username": user_name,
                "ConfirmationCode": confirmation_code,
            }
            if self.client_secret is not None:
                kwargs["SecretHash"] = self._secret_hash(user_name)
            self.cognito_idp_client.confirm_sign_up(**kwargs)
        except ClientError as err:
            logger.error(
                "Couldn't confirm sign up for %s. Here's why: %s: %s",
                user_name,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return True


    def list_users(self):
        """
        Returns a list of the users in the current user pool.

        :return: The list of users.
        """
        try:
            response =
self.cognito_idp_client.list_users(UserPoolId=self.user_pool_id)
            users = response["Users"]
        except ClientError as err:
            logger.error(
                "Couldn't list users for %s. Here's why: %s: %s",
                self.user_pool_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return users


    def start_sign_in(self, user_name, password):
        """
        Starts the sign-in process for a user by using administrator credentials.
        This method of signing in is appropriate for code running on a secure
server.

        If the user pool is configured to require MFA and this is the first sign-in
        for the user, Amazon Cognito returns a challenge response to set up an
        MFA application. When this occurs, this function gets an MFA secret from
        Amazon Cognito and returns it to the caller.

        :param user_name: The name of the user to sign in.
        :param password: The user's password.
        :return: The result of the sign-in attempt. When sign-in is successful, this
```

```
                returns an access token that can be used to get AWS credentials.
Otherwise,
                Amazon Cognito returns a challenge to set up an MFA application,
                or a challenge to enter an MFA code from a registered MFA
application.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "AuthFlow": "ADMIN_USER_PASSWORD_AUTH",
                "AuthParameters": {"USERNAME": user_name, "PASSWORD": password},
            }
            if self.client_secret is not None:
                kwargs["AuthParameters"]["SECRET_HASH"] =
self._secret_hash(user_name)
            response = self.cognito_idp_client.admin_initiate_auth(**kwargs)
            challenge_name = response.get("ChallengeName", None)
            if challenge_name == "MFA_SETUP":
                if (
                    "SOFTWARE_TOKEN_MFA"
                    in response["ChallengeParameters"]["MFAS_CAN_SETUP"]
                ):
                    response.update(self.get_mfa_secret(response["Session"]))
                else:
                    raise RuntimeError(
                        "The user pool requires MFA setup, but the user pool is not
"
                        "configured for TOTP MFA. This example requires TOTP MFA."
                    )
        except ClientError as err:
            logger.error(
                "Couldn't start sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response


    def get_mfa_secret(self, session):
```

```
        """
        Gets a token that can be used to associate an MFA application with the user.

        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :return: An MFA token that can be used to set up an MFA application.
        """
        try:
            response =
self.cognito_idp_client.associate_software_token(Session=session)
        except ClientError as err:
            logger.error(
                "Couldn't get MFA secret. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            response.pop("ResponseMetadata", None)
            return response


    def verify_mfa(self, session, user_code):
        """
        Verify a new MFA application that is associated with a user.

        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :param user_code: A code generated by the associated MFA application.
        :return: Status that indicates whether the MFA application is verified.
        """
        try:
            response = self.cognito_idp_client.verify_software_token(
                Session=session, UserCode=user_code
            )
        except ClientError as err:
            logger.error(
                "Couldn't verify MFA. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            response.pop("ResponseMetadata", None)
            return response


    def respond_to_mfa_challenge(self, user_name, session, mfa_code):
        """
        Responds to a challenge for an MFA code. This completes the second step of
        a two-factor sign-in. When sign-in is successful, it returns an access token
        that can be used to get AWS credentials from Amazon Cognito.

        :param user_name: The name of the user who is signing in.
        :param session: Session information returned from a previous call to
initiate
                        authentication.
        :param mfa_code: A code generated by the associated MFA application.
        :return: The result of the authentication. When successful, this contains an
                 access token for the user.
        """
        try:
            kwargs = {
                "UserPoolId": self.user_pool_id,
                "ClientId": self.client_id,
                "ChallengeName": "SOFTWARE_TOKEN_MFA",
                "Session": session,
                "ChallengeResponses": {
                    "USERNAME": user_name,
                    "SOFTWARE_TOKEN_MFA_CODE": mfa_code,
                },
            }
            if self.client_secret is not None:
                kwargs["ChallengeResponses"]["SECRET_HASH"] = self._secret_hash(
                    user_name
                )
            response =
self.cognito_idp_client.admin_respond_to_auth_challenge(**kwargs)
            auth_result = response["AuthenticationResult"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "ExpiredCodeException":
                logger.warning(
                    "Your MFA code has expired or has been used already. You might
have "
                    "to wait a few seconds until your app shows you a new code."
                )
```

```
            else:
                logger.error(
                    "Couldn't respond to mfa challenge for %s. Here's why: %s: %s",
                    user_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return auth_result


    def confirm_mfa_device(
        self,
        user_name,
        device_key,
        device_group_key,
        device_password,
        access_token,
        aws_srp,
    ):
        """
        Confirms an MFA device to be tracked by Amazon Cognito. When a device is
        tracked, its key and password can be used to sign in without requiring a new
        MFA code from the MFA application.

        :param user_name: The user that is associated with the device.
        :param device_key: The key of the device, returned by Amazon Cognito.
        :param device_group_key: The group key of the device, returned by Amazon
 Cognito.
        :param device_password: The password that is associated with the device.
        :param access_token: The user's access token.
        :param aws_srp: A class that helps with Secure Remote Password (SRP)
                        calculations. The scenario associated with this example uses
                        the warrant package.
        :return: True when the user must confirm the device. Otherwise, False. When
                 False, the device is automatically confirmed and tracked.
        """
        srp_helper = aws_srp.AWSSRP(
            username=user_name,
            password=device_password,
            pool_id="_",
            client_id=self.client_id,
            client_secret=None,
```

```
            client=self.cognito_idp_client,
        )
        device_and_pw = f"{device_group_key}{device_key}:{device_password}"
        device_and_pw_hash = aws_srp.hash_sha256(device_and_pw.encode("utf-8"))
        salt = aws_srp.pad_hex(aws_srp.get_random(16))
        x_value = aws_srp.hex_to_long(aws_srp.hex_hash(salt + device_and_pw_hash))
        verifier = aws_srp.pad_hex(pow(srp_helper.val_g, x_value, srp_helper.big_n))
        device_secret_verifier_config = {
            "PasswordVerifier": base64.standard_b64encode(
                bytearray.fromhex(verifier)
            ).decode("utf-8"),
            "Salt":
base64.standard_b64encode(bytearray.fromhex(salt)).decode("utf-8"),
        }
        try:
            response = self.cognito_idp_client.confirm_device(
                AccessToken=access_token,
                DeviceKey=device_key,
                DeviceSecretVerifierConfig=device_secret_verifier_config,
            )
            user_confirm = response["UserConfirmationNecessary"]
        except ClientError as err:
            logger.error(
                "Couldn't confirm mfa device %s. Here's why: %s: %s",
                device_key,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return user_confirm


    def sign_in_with_tracked_device(
        self,
        user_name,
        password,
        device_key,
        device_group_key,
        device_password,
        aws_srp,
    ):
        """
        Signs in to Amazon Cognito as a user who has a tracked device. Signing in
```

```
        with a tracked device lets a user sign in without entering a new MFA code.

        Signing in with a tracked device requires that the client respond to the SRP
        protocol. The scenario associated with this example uses the warrant package
        to help with SRP calculations.

        For more information on SRP, see https://en.wikipedia.org/wiki/
Secure_Remote_Password_protocol.

        :param user_name: The user that is associated with the device.
        :param password: The user's password.
        :param device_key: The key of a tracked device.
        :param device_group_key: The group key of a tracked device.
        :param device_password: The password that is associated with the device.
        :param aws_srp: A class that helps with SRP calculations. The scenario
                        associated with this example uses the warrant package.
        :return: The result of the authentication. When successful, this contains an
                 access token for the user.
        """
        try:
            srp_helper = aws_srp.AWSSRP(
                username=user_name,
                password=device_password,
                pool_id="_",
                client_id=self.client_id,
                client_secret=None,
                client=self.cognito_idp_client,
            )

            response_init = self.cognito_idp_client.initiate_auth(
                ClientId=self.client_id,
                AuthFlow="USER_PASSWORD_AUTH",
                AuthParameters={
                    "USERNAME": user_name,
                    "PASSWORD": password,
                    "DEVICE_KEY": device_key,
                },
            )
            if response_init["ChallengeName"] != "DEVICE_SRP_AUTH":
                raise RuntimeError(
                    f"Expected DEVICE_SRP_AUTH challenge but got
 {response_init['ChallengeName']}."
                )
```

```
            auth_params = srp_helper.get_auth_params()
            auth_params["DEVICE_KEY"] = device_key
            response_auth = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_SRP_AUTH",
                ChallengeResponses=auth_params,
            )
            if response_auth["ChallengeName"] != "DEVICE_PASSWORD_VERIFIER":
                raise RuntimeError(
                    f"Expected DEVICE_PASSWORD_VERIFIER challenge but got "
                    f"{response_init['ChallengeName']}."
                )

            challenge_params = response_auth["ChallengeParameters"]
            challenge_params["USER_ID_FOR_SRP"] = device_group_key + device_key
            cr = srp_helper.process_challenge(challenge_params, {"USERNAME":
user_name})
            cr["USERNAME"] = user_name
            cr["DEVICE_KEY"] = device_key
            response_verifier = self.cognito_idp_client.respond_to_auth_challenge(
                ClientId=self.client_id,
                ChallengeName="DEVICE_PASSWORD_VERIFIER",
                ChallengeResponses=cr,
            )
            auth_tokens = response_verifier["AuthenticationResult"]
        except ClientError as err:
            logger.error(
                "Couldn't start client sign in for %s. Here's why: %s: %s",
                user_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return auth_tokens
```

Crie uma classe que execute o cenário. Este exemplo também registra um dispositivo de MFA a ser rastreado pelo Amazon Cognito e mostra como fazer login com uma senha e informações do dispositivo rastreado. Isso evita a necessidade de inserir um novo código de MFA.

```
def run_scenario(cognito_idp_client, user_pool_id, client_id):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon Cognito user signup with MFA demo.")
    print("-" * 88)

    cog_wrapper = CognitoIdentityProviderWrapper(
        cognito_idp_client, user_pool_id, client_id
    )

    user_name = q.ask("Let's sign up a new user. Enter a user name: ", q.non_empty)
    password = q.ask("Enter a password for the user: ", q.non_empty)
    email = q.ask("Enter a valid email address that you own: ", q.non_empty)
    confirmed = cog_wrapper.sign_up_user(user_name, password, email)
    while not confirmed:
        print(
            f"User {user_name} requires confirmation. Check {email} for "
            f"a verification code."
        )
        confirmation_code = q.ask("Enter the confirmation code from the email: ")
        if not confirmation_code:
            if q.ask("Do you need another confirmation code (y/n)? ", q.is_yesno):
                delivery = cog_wrapper.resend_confirmation(user_name)
                print(
                    f"Confirmation code sent by {delivery['DeliveryMedium']} "
                    f"to {delivery['Destination']}."
                )
        else:
            confirmed = cog_wrapper.confirm_user_sign_up(user_name,
 confirmation_code)
    print(f"User {user_name} is confirmed and ready to use.")
    print("-" * 88)

    print("Let's get a list of users in the user pool.")
    q.ask("Press Enter when you're ready.")
    users = cog_wrapper.list_users()
    if users:
        print(f"Found {len(users)} users:")
        pp(users)
    else:
        print("No users found.")
    print("-" * 88)
```

```
    print("Let's sign in and get an access token.")
    auth_tokens = None
    challenge = "ADMIN_USER_PASSWORD_AUTH"
    response = {}
    while challenge is not None:
        if challenge == "ADMIN_USER_PASSWORD_AUTH":
            response = cog_wrapper.start_sign_in(user_name, password)
            challenge = response["ChallengeName"]
        elif response["ChallengeName"] == "MFA_SETUP":
            print("First, we need to set up an MFA application.")
            qr_img = qrcode.make(
                f"otpauth://totp/{user_name}?secret={response['SecretCode']}"
            )
            qr_img.save("qr.png")
            q.ask(
                "Press Enter to see a QR code on your screen. Scan it into an MFA "
                "application, such as Google Authenticator."
            )
            webbrowser.open("qr.png")
            mfa_code = q.ask(
                "Enter the verification code from your MFA application: ",
q.non_empty
            )
            response = cog_wrapper.verify_mfa(response["Session"], mfa_code)
            print(f"MFA device setup {response['Status']}")
            print("Now that an MFA application is set up, let's sign in again.")
            print(
                "You might have to wait a few seconds for a new MFA code to appear
in "
                "your MFA application."
            )
            challenge = "ADMIN_USER_PASSWORD_AUTH"
        elif response["ChallengeName"] == "SOFTWARE_TOKEN_MFA":
            auth_tokens = None
            while auth_tokens is None:
                mfa_code = q.ask(
                    "Enter a verification code from your MFA application: ",
q.non_empty
                )
                auth_tokens = cog_wrapper.respond_to_mfa_challenge(
                    user_name, response["Session"], mfa_code
                )
            print(f"You're signed in as {user_name}.")
```

```
            print("Here's your access token:")
            pp(auth_tokens["AccessToken"])
            print("And your device information:")
            pp(auth_tokens["NewDeviceMetadata"])
            challenge = None
        else:
            raise Exception(f"Got unexpected challenge {response['ChallengeName']}")
    print("-" * 88)

    device_group_key = auth_tokens["NewDeviceMetadata"]["DeviceGroupKey"]
    device_key = auth_tokens["NewDeviceMetadata"]["DeviceKey"]
    device_password = base64.standard_b64encode(os.urandom(40)).decode("utf-8")

    print("Let's confirm your MFA device so you don't have re-enter MFA tokens for
 it.")
    q.ask("Press Enter when you're ready.")
    cog_wrapper.confirm_mfa_device(
        user_name,
        device_key,
        device_group_key,
        device_password,
        auth_tokens["AccessToken"],
        aws_srp,
    )
    print(f"Your device {device_key} is confirmed.")
    print("-" * 88)

    print(
        f"Now let's sign in as {user_name} from your confirmed device {device_key}.
\n"
        f"Because this device is tracked by Amazon Cognito, you won't have to re-
enter an MFA code."
    )
    q.ask("Press Enter when ready.")
    auth_tokens = cog_wrapper.sign_in_with_tracked_device(
        user_name, password, device_key, device_group_key, device_password, aws_srp
    )
    print("You're signed in. Your access token is:")
    pp(auth_tokens["AccessToken"])
    print("-" * 88)

    print("Don't forget to delete your user pool when you're done with this
 example.")
    print("\nThanks for watching!")
```

```
    print("-" * 88)


def main():
    parser = argparse.ArgumentParser(
        description="Shows how to sign up a new user with Amazon Cognito and
 associate "
        "the user with an MFA application for multi-factor authentication."
    )
    parser.add_argument(
        "user_pool_id", help="The ID of the user pool to use for the example."
    )
    parser.add_argument(
        "client_id", help="The ID of the client application to use for the example."
    )
    args = parser.parse_args()
    try:
        run_scenario(boto3.client("cognito-idp"), args.user_pool_id, args.client_id)
    except Exception:
        logging.exception("Something went wrong with the demo.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp

- VerifySoftwareToken

Exemplos do Amazon Comprehend usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Comprehend.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um classificador de documentos

O exemplo de código a seguir mostra como criar um classificador de documentos do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""
```

```
    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def create(
        self,
        name,
        language_code,
        training_bucket,
        training_key,
        data_access_role_arn,
        mode,
    ):
        """
        Creates a custom classifier. After the classifier is created, it immediately
        starts training on the data found in the specified Amazon S3 bucket.
Training
        can take 30 minutes or longer. The `describe_document_classifier` function
        can be used to get training status and returns a status of TRAINED when the
        classifier is ready to use.

        :param name: The name of the classifier.
        :param language_code: The language the classifier can operate on.
        :param training_bucket: The Amazon S3 bucket that contains the training
data.
        :param training_key: The prefix used to find training data in the training
                             bucket. If multiple objects have the same prefix, all
                             of them are used.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     training bucket.
        :return: The ARN of the newly created classifier.
        """
        try:
            response = self.comprehend_client.create_document_classifier(
                DocumentClassifierName=name,
                LanguageCode=language_code,
                InputDataConfig={"S3Uri": f"s3://{training_bucket}/{training_key}"},
                DataAccessRoleArn=data_access_role_arn,
                Mode=mode.value,
```

```
            )
            self.classifier_arn = response["DocumentClassifierArn"]
            logger.info("Started classifier creation. Arn is: %s.",
self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't create classifier %s.", name)
            raise
        else:
            return self.classifier_arn
```

- Para obter detalhes da API, consulte a CreateDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Excluir um classificador de documentos

O exemplo de código a seguir mostra como excluir um classificador de documentos do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def delete(self):
        """
```

```
        Deletes the classifier.
        """
        try:
            self.comprehend_client.delete_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            logger.info("Deleted classifier %s.", self.classifier_arn)
            self.classifier_arn = None
        except ClientError:
            logger.exception("Couldn't deleted classifier %s.", self.classifier_arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Descrever um trabalho de classificação de documentos

O exemplo de código a seguir mostra como descrever uma trabalho de classificação de documentos do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None
```

```
    def describe_job(self, job_id):
        """
        Gets metadata about a classification job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_document_classification_job(
                JobId=job_id
            )
            job = response["DocumentClassificationJobProperties"]
            logger.info("Got classification job %s.", job["JobName"])
        except ClientError:
            logger.exception("Couldn't get classification job %s.", job_id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a DescribeDocumentClassificationJobReferência da API AWSSDK for Python (Boto3).

Descrever um classificador de documentos

O exemplo de código a seguir mostra como descrever um classificador de documento do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
```

```
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def describe(self, classifier_arn=None):
        """
        Gets metadata about a custom classifier, including its current status.

        :param classifier_arn: The ARN of the classifier to look up.
        :return: Metadata about the classifier.
        """
        if classifier_arn is not None:
            self.classifier_arn = classifier_arn
        try:
            response = self.comprehend_client.describe_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            classifier = response["DocumentClassifierProperties"]
            logger.info("Got classifier %s.", self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't get classifier %s.", self.classifier_arn)
            raise
        else:
            return classifier
```

- Para obter detalhes da API, consulte a DescribeDocumentClassifierReferência da API AWSSDK for Python (Boto3).

Descrever um trabalho de modelagem de tópico

O exemplo de código a seguir mostra como descrever um trabalho de modelagem de tópico do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def describe_job(self, job_id):
        """
        Gets metadata about a topic modeling job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_topics_detection_job(
                JobId=job_id
            )
            job = response["TopicsDetectionJobProperties"]
            logger.info("Got topic detection job %s.", job_id)
        except ClientError:
            logger.exception("Couldn't get topic detection job %s.", job_id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a DescribeTopicsDetectionJobReferência da API AWSSDK for Python (Boto3).

Detectar entidades em um documento

O exemplo de código a seguir mostra como detectar entidades em um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_entities(self, text, language_code):
        """
        Detects entities in a document. Entities can be things like people and
 places
        or other common terms.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
            logger.info("Detected %s entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect entities.")
            raise
```

```
        else:
            return entities
```

- Para obter detalhes da API, consulte a DetectEntitiesReferência da API AWSSDK for Python (Boto3).

Detectar frases-chave em um documento

O exemplo de código a seguir mostra como detectar frases-chave em um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_key_phrases(self, text, language_code):
        """
        Detects key phrases in a document. A key phrase is typically a noun and its
        modifiers.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of key phrases along with their confidence scores.
        """
        try:
```

```
            response = self.comprehend_client.detect_key_phrases(
                Text=text, LanguageCode=language_code
            )
            phrases = response["KeyPhrases"]
            logger.info("Detected %s phrases.", len(phrases))
        except ClientError:
            logger.exception("Couldn't detect phrases.")
            raise
        else:
            return phrases
```

- Para obter detalhes da API, consulte a DetectKeyPhrasesReferência da API AWSSDK for Python (Boto3).

Detectar informações de identificação pessoal em um documento

O exemplo de código a seguir mostra como detectar informações de identificação pessoal (PII) em um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_pii(self, text, language_code):
        """
```

```
        Detects personally identifiable information (PII) in a document. PII can be
        things like names, account numbers, or addresses.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of PII entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_pii_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
            logger.info("Detected %s PII entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect PII entities.")
            raise
        else:
            return entities
```

- Para obter detalhes da API, consulte a DetectPiiEntitiesReferência da API AWSSDK for Python (Boto3).

Detectar elementos sintáticos de um documento

O exemplo de código a seguir mostra como detectar elementos sintáticos de um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
```

```
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_syntax(self, text, language_code):
        """
        Detects syntactical elements of a document. Syntax tokens are portions of
        text along with their use as parts of speech, such as nouns, verbs, and
        interjections.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of syntax tokens along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_syntax(
                Text=text, LanguageCode=language_code
            )
            tokens = response["SyntaxTokens"]
            logger.info("Detected %s syntax tokens.", len(tokens))
        except ClientError:
            logger.exception("Couldn't detect syntax.")
            raise
        else:
            return tokens
```

- Para obter detalhes da API, consulte a DetectSyntaxReferência da API AWSSDK for Python (Boto3).

Detectar o idioma dominante em um documento

O exemplo de código a seguir mostra como detectar a linguagem dominante em um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_languages(self, text):
        """
        Detects languages used in a document.

        :param text: The document to inspect.
        :return: The list of languages along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_dominant_language(Text=text)
            languages = response["Languages"]
            logger.info("Detected %s languages.", len(languages))
        except ClientError:
            logger.exception("Couldn't detect languages.")
            raise
        else:
            return languages
```

- Para obter detalhes da API, consulte a DetectDominantLanguageReferência da API AWSSDK for Python (Boto3).

Detectar o sentimento de um documento

O exemplo de código a seguir mostra como detectar o sentimento em um documento com o Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_sentiment(self, text, language_code):
        """
        Detects the overall sentiment expressed in a document. Sentiment can
        be positive, negative, neutral, or a mixture.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The sentiments along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_sentiment(
                Text=text, LanguageCode=language_code
            )
            logger.info("Detected primary sentiment %s.", response["Sentiment"])
        except ClientError:
            logger.exception("Couldn't detect sentiment.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DetectSentimentReferência da API AWSSDK for Python (Boto3).

Listar trabalhos de classificação de documento

O exemplo de código a seguir mostra como listar tarefas de classificação de documento do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def list_jobs(self):
        """
        Lists the classification jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_document_classification_jobs()
            jobs = response["DocumentClassificationJobPropertiesList"]
            logger.info("Got %s document classification jobs.", len(jobs))
        except ClientError:
```

```
            logger.exception(
                "Couldn't get document classification jobs.",
            )
            raise
        else:
            return jobs
```

- Para obter detalhes da API, consulte a ListDocumentClassificationJobsReferência da API AWSSDK for Python (Boto3).

Listar classificadores de documento

O exemplo de código a seguir mostra como listar os classificadores de documento do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def list(self):
        """
        Lists custom classifiers for the current account.
```

```
        :return: The list of classifiers.
        """
        try:
            response = self.comprehend_client.list_document_classifiers()
            classifiers = response["DocumentClassifierPropertiesList"]
            logger.info("Got %s classifiers.", len(classifiers))
        except ClientError:
            logger.exception(
                "Couldn't get classifiers.",
            )
            raise
        else:
            return classifiers
```

- Para obter detalhes da API, consulte a ListDocumentClassifiersReferência da API AWSSDK for Python (Boto3).

Listar trabalhos de modelagem de tópicos

O exemplo de código a seguir mostra como listar trabalhos de modelagem de tópico do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
```

```
    def list_jobs(self):
        """
        Lists topic modeling jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_topics_detection_jobs()
            jobs = response["TopicsDetectionJobPropertiesList"]
            logger.info("Got %s topic detection jobs.", len(jobs))
        except ClientError:
            logger.exception("Couldn't get topic detection jobs.")
            raise
        else:
            return jobs
```

- Para obter detalhes da API, consulte a ListTopicsDetectionJobsReferência da API AWSSDK for Python (Boto3).

Iniciar um trabalho de classificação de documento

O exemplo de código a seguir mostra como iniciar uma tarefa de classificação de documento do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
```

```
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a classification job. The classifier must be trained or the job
        will fail. Input is read from the specified Amazon S3 input bucket and
        written to the specified output bucket. Output data is stored in a tar
        archive compressed in gzip format. The job runs asynchronously, so you can
        call `describe_document_classification_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: The Amazon S3 bucket that contains input data.
        :param input_key: The prefix used to find input data in the input
                          bucket. If multiple objects have the same prefix, all
                          of them are used.
        :param input_format: The format of the input data, either one document per
                             file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_document_classification_job(
                DocumentClassifierArn=self.classifier_arn,
                JobName=job_name,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
```

```
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
                DataAccessRoleArn=data_access_role_arn,
            )
            logger.info(
                "Document classification job %s is %s.", job_name,
response["JobStatus"]
            )
        except ClientError:
            logger.exception("Couldn't start classification job %s.", job_name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartDocumentClassificationJobReferência da API AWSSDK for Python (Boto3).

Iniciar um trabalho de modelagem de tópico

O exemplo de código a seguir mostra como iniciar um trabalho de modelagem de tópico do Amazon Comprehend.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client
```

```
    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a topic modeling job. Input is read from the specified Amazon S3
        input bucket and written to the specified output bucket. Output data is
stored
        in a tar archive compressed in gzip format. The job runs asynchronously, so
you
        can call `describe_topics_detection_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: An Amazon S3 bucket that contains job input.
        :param input_key: The prefix used to find input data in the input
                            bucket. If multiple objects have the same prefix, all
                            of them are used.
        :param input_format: The format of the input data, either one document per
                            file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_topics_detection_job(
                JobName=job_name,
                DataAccessRoleArn=data_access_role_arn,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
```

```
            )
            logger.info("Started topic modeling job %s.", response["JobId"])
        except ClientError:
            logger.exception("Couldn't start topic modeling job.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartTopicsDetectionJobReferência da API AWSSDK for Python (Boto3).

Cenários

Detectar elementos do documento

O código de exemplo a seguir mostra como:

- Detectar idiomas, entidades e frases-chave em um documento.
- Detectar informações de identificação pessoal (PII) em um documento.
- Detectar o sentimento em um documento.
- Detectar elementos de sintaxe em um documento.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe que envolva as ações do Amazon Comprehend.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
```

```
class ComprehendDetect:
    """Encapsulates Comprehend detection functions."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def detect_languages(self, text):
        """
        Detects languages used in a document.

        :param text: The document to inspect.
        :return: The list of languages along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_dominant_language(Text=text)
            languages = response["Languages"]
            logger.info("Detected %s languages.", len(languages))
        except ClientError:
            logger.exception("Couldn't detect languages.")
            raise
        else:
            return languages


    def detect_entities(self, text, language_code):
        """
        Detects entities in a document. Entities can be things like people and
 places
        or other common terms.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
```

```
            logger.info("Detected %s entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect entities.")
            raise
        else:
            return entities


    def detect_key_phrases(self, text, language_code):
        """
        Detects key phrases in a document. A key phrase is typically a noun and its
        modifiers.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of key phrases along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_key_phrases(
                Text=text, LanguageCode=language_code
            )
            phrases = response["KeyPhrases"]
            logger.info("Detected %s phrases.", len(phrases))
        except ClientError:
            logger.exception("Couldn't detect phrases.")
            raise
        else:
            return phrases


    def detect_pii(self, text, language_code):
        """
        Detects personally identifiable information (PII) in a document. PII can be
        things like names, account numbers, or addresses.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of PII entities along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_pii_entities(
                Text=text, LanguageCode=language_code
            )
            entities = response["Entities"]
```

```
            logger.info("Detected %s PII entities.", len(entities))
        except ClientError:
            logger.exception("Couldn't detect PII entities.")
            raise
        else:
            return entities


    def detect_sentiment(self, text, language_code):
        """
        Detects the overall sentiment expressed in a document. Sentiment can
        be positive, negative, neutral, or a mixture.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The sentiments along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_sentiment(
                Text=text, LanguageCode=language_code
            )
            logger.info("Detected primary sentiment %s.", response["Sentiment"])
        except ClientError:
            logger.exception("Couldn't detect sentiment.")
            raise
        else:
            return response


    def detect_syntax(self, text, language_code):
        """
        Detects syntactical elements of a document. Syntax tokens are portions of
        text along with their use as parts of speech, such as nouns, verbs, and
        interjections.

        :param text: The document to inspect.
        :param language_code: The language of the document.
        :return: The list of syntax tokens along with their confidence scores.
        """
        try:
            response = self.comprehend_client.detect_syntax(
                Text=text, LanguageCode=language_code
            )
            tokens = response["SyntaxTokens"]
```

```
            logger.info("Detected %s syntax tokens.", len(tokens))
        except ClientError:
            logger.exception("Couldn't detect syntax.")
            raise
        else:
            return tokens
```

Chamar funções na classe wrapper para detectar entidades, frases e mais em um documento.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend detection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    comp_detect = ComprehendDetect(boto3.client("comprehend"))
    with open("detect_sample.txt") as sample_file:
        sample_text = sample_file.read()

    demo_size = 3

    print("Sample text used for this demo:")
    print("-" * 88)
    print(sample_text)
    print("-" * 88)

    print("Detecting languages.")
    languages = comp_detect.detect_languages(sample_text)
    pprint(languages)
    lang_code = languages[0]["LanguageCode"]

    print("Detecting entities.")
    entities = comp_detect.detect_entities(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(entities[:demo_size])

    print("Detecting key phrases.")
    phrases = comp_detect.detect_key_phrases(sample_text, lang_code)
    print(f"The first {demo_size} are:")
```

```
    pprint(phrases[:demo_size])

    print("Detecting personally identifiable information (PII).")
    pii_entities = comp_detect.detect_pii(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(pii_entities[:demo_size])

    print("Detecting sentiment.")
    sentiment = comp_detect.detect_sentiment(sample_text, lang_code)
    print(f"Sentiment: {sentiment['Sentiment']}")
    print("SentimentScore:")
    pprint(sentiment["SentimentScore"])

    print("Detecting syntax elements.")
    syntax_tokens = comp_detect.detect_syntax(sample_text, lang_code)
    print(f"The first {demo_size} are:")
    pprint(syntax_tokens[:demo_size])

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DetectDominantLanguage
  - DetectEntities
  - DetectKeyPhrases
  - DetectPiiEntities
  - DetectSentiment
  - DetectSyntax

Executar um trabalho de modelagem de tópico em dados de amostra

O código de exemplo a seguir mostra como:

- Executar um trabalho de modelagem de tópico do Amazon Comprehend em dados de amostra.
- Obter informações sobre o trabalho.

- Extrair dados de saída do trabalho no Amazon S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe wrapper para chamar as ações de modelagem de tópico do Amazon Comprehend.

```
class ComprehendTopicModeler:
    """Encapsulates a Comprehend topic modeler."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
        """
        self.comprehend_client = comprehend_client


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a topic modeling job. Input is read from the specified Amazon S3
        input bucket and written to the specified output bucket. Output data is
 stored
        in a tar archive compressed in gzip format. The job runs asynchronously, so
 you
        can call `describe_topics_detection_job` to get job status until it
        returns a status of SUCCEEDED.
```

```
        :param job_name: The name of the job.
        :param input_bucket: An Amazon S3 bucket that contains job input.
        :param input_key: The prefix used to find input data in the input
                           bucket. If multiple objects have the same prefix, all
                           of them are used.
        :param input_format: The format of the input data, either one document per
                           file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_topics_detection_job(
                JobName=job_name,
                DataAccessRoleArn=data_access_role_arn,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
            )
            logger.info("Started topic modeling job %s.", response["JobId"])
        except ClientError:
            logger.exception("Couldn't start topic modeling job.")
            raise
        else:
            return response


    def describe_job(self, job_id):
        """
        Gets metadata about a topic modeling job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_topics_detection_job(
                JobId=job_id
            )
            job = response["TopicsDetectionJobProperties"]
```

```
            logger.info("Got topic detection job %s.", job_id)
        except ClientError:
            logger.exception("Couldn't get topic detection job %s.", job_id)
            raise
        else:
            return job


    def list_jobs(self):
        """
        Lists topic modeling jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_topics_detection_jobs()
            jobs = response["TopicsDetectionJobPropertiesList"]
            logger.info("Got %s topic detection jobs.", len(jobs))
        except ClientError:
            logger.exception("Couldn't get topic detection jobs.")
            raise
        else:
            return jobs
```

Usar a classe wrapper para executar um trabalho de modelagem de tópico e obter dados dela.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend topic modeling demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    input_prefix = "input/"
    output_prefix = "output/"
    demo_resources = ComprehendDemoResources(
        boto3.resource("s3"), boto3.resource("iam")
    )
    topic_modeler = ComprehendTopicModeler(boto3.client("comprehend"))
```

```
    print("Setting up storage and security resources needed for the demo.")
    demo_resources.setup("comprehend-topic-modeler-demo")
    print("Copying sample data from public bucket into input bucket.")
    demo_resources.bucket.copy(
        {"Bucket": "public-sample-us-west-2", "Key": "TopicModeling/Sample.txt"},
        f"{input_prefix}sample.txt",
    )

    print("Starting topic modeling job on sample data.")
    job_info = topic_modeler.start_job(
        "demo-topic-modeling-job",
        demo_resources.bucket.name,
        input_prefix,
        JobInputFormat.per_line,
        demo_resources.bucket.name,
        output_prefix,
        demo_resources.data_access_role.arn,
    )

    print(
        f"Waiting for job {job_info['JobId']} to complete. This typically takes "
        f"20 - 30 minutes."
    )
    job_waiter = JobCompleteWaiter(topic_modeler.comprehend_client)
    job_waiter.wait(job_info["JobId"])

    job = topic_modeler.describe_job(job_info["JobId"])
    print(f"Job {job['JobId']} complete:")
    pprint(job)

    print(
        f"Getting job output data from the output Amazon S3 bucket: "
        f"{job['OutputDataConfig']['S3Uri']}."
    )
    job_output = demo_resources.extract_job_output(job)
    lines = 10
    print(f"First {lines} lines of document topics output:")
    pprint(job_output["doc-topics.csv"]["data"][:lines])
    print(f"First {lines} lines of terms output:")
    pprint(job_output["topic-terms.csv"]["data"][:lines])

    print("Cleaning up resources created for the demo.")
    demo_resources.cleanup()
```

```
    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DescribeTopicsDetectionJob
  - ListTopicsDetectionJobs
  - StartTopicsDetectionJob

Treinar um classificador personalizado e classificar documentos

O código de exemplo a seguir mostra como:

- Criar um classificador de múltiplos rótulos do Amazon Comprehend.
- Treinar o classificador em dados de amostra.
- Executar um trabalho de classificação em um segundo conjunto de dados.
- Extrair dados de saída da tarefa do Amazon S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar uma classe wrapper para chamar as ações do classificador de documento Amazon Comprehend.

```
class ComprehendClassifier:
    """Encapsulates an Amazon Comprehend custom classifier."""

    def __init__(self, comprehend_client):
        """
        :param comprehend_client: A Boto3 Comprehend client.
```

```
        """
        self.comprehend_client = comprehend_client
        self.classifier_arn = None


    def create(
        self,
        name,
        language_code,
        training_bucket,
        training_key,
        data_access_role_arn,
        mode,
    ):
        """
        Creates a custom classifier. After the classifier is created, it immediately
        starts training on the data found in the specified Amazon S3 bucket.
Training
        can take 30 minutes or longer. The `describe_document_classifier` function
        can be used to get training status and returns a status of TRAINED when the
        classifier is ready to use.

        :param name: The name of the classifier.
        :param language_code: The language the classifier can operate on.
        :param training_bucket: The Amazon S3 bucket that contains the training
data.
        :param training_key: The prefix used to find training data in the training
                             bucket. If multiple objects have the same prefix, all
                             of them are used.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     training bucket.
        :return: The ARN of the newly created classifier.
        """
        try:
            response = self.comprehend_client.create_document_classifier(
                DocumentClassifierName=name,
                LanguageCode=language_code,
                InputDataConfig={"S3Uri": f"s3://{training_bucket}/{training_key}"},
                DataAccessRoleArn=data_access_role_arn,
                Mode=mode.value,
            )
            self.classifier_arn = response["DocumentClassifierArn"]
```

```
            logger.info("Started classifier creation. Arn is: %s.",
self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't create classifier %s.", name)
            raise
        else:
            return self.classifier_arn


    def describe(self, classifier_arn=None):
        """
        Gets metadata about a custom classifier, including its current status.

        :param classifier_arn: The ARN of the classifier to look up.
        :return: Metadata about the classifier.
        """
        if classifier_arn is not None:
            self.classifier_arn = classifier_arn
        try:
            response = self.comprehend_client.describe_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            classifier = response["DocumentClassifierProperties"]
            logger.info("Got classifier %s.", self.classifier_arn)
        except ClientError:
            logger.exception("Couldn't get classifier %s.", self.classifier_arn)
            raise
        else:
            return classifier


    def list(self):
        """
        Lists custom classifiers for the current account.

        :return: The list of classifiers.
        """
        try:
            response = self.comprehend_client.list_document_classifiers()
            classifiers = response["DocumentClassifierPropertiesList"]
            logger.info("Got %s classifiers.", len(classifiers))
        except ClientError:
            logger.exception(
                "Couldn't get classifiers.",
```

```
            )
            raise
        else:
            return classifiers


    def delete(self):
        """
        Deletes the classifier.
        """
        try:
            self.comprehend_client.delete_document_classifier(
                DocumentClassifierArn=self.classifier_arn
            )
            logger.info("Deleted classifier %s.", self.classifier_arn)
            self.classifier_arn = None
        except ClientError:
            logger.exception("Couldn't deleted classifier %s.", self.classifier_arn)
            raise


    def start_job(
        self,
        job_name,
        input_bucket,
        input_key,
        input_format,
        output_bucket,
        output_key,
        data_access_role_arn,
    ):
        """
        Starts a classification job. The classifier must be trained or the job
        will fail. Input is read from the specified Amazon S3 input bucket and
        written to the specified output bucket. Output data is stored in a tar
        archive compressed in gzip format. The job runs asynchronously, so you can
        call `describe_document_classification_job` to get job status until it
        returns a status of SUCCEEDED.

        :param job_name: The name of the job.
        :param input_bucket: The Amazon S3 bucket that contains input data.
        :param input_key: The prefix used to find input data in the input
                          bucket. If multiple objects have the same prefix, all
                          of them are used.
```

```
        :param input_format: The format of the input data, either one document per
                             file or one document per line.
        :param output_bucket: The Amazon S3 bucket where output data is written.
        :param output_key: The prefix prepended to the output data.
        :param data_access_role_arn: The Amazon Resource Name (ARN) of a role that
                                     grants Comprehend permission to read from the
                                     input bucket and write to the output bucket.
        :return: Information about the job, including the job ID.
        """
        try:
            response = self.comprehend_client.start_document_classification_job(
                DocumentClassifierArn=self.classifier_arn,
                JobName=job_name,
                InputDataConfig={
                    "S3Uri": f"s3://{input_bucket}/{input_key}",
                    "InputFormat": input_format.value,
                },
                OutputDataConfig={"S3Uri": f"s3://{output_bucket}/{output_key}"},
                DataAccessRoleArn=data_access_role_arn,
            )
            logger.info(
                "Document classification job %s is %s.", job_name,
response["JobStatus"]
            )
        except ClientError:
            logger.exception("Couldn't start classification job %s.", job_name)
            raise
        else:
            return response


    def describe_job(self, job_id):
        """
        Gets metadata about a classification job.

        :param job_id: The ID of the job to look up.
        :return: Metadata about the job.
        """
        try:
            response = self.comprehend_client.describe_document_classification_job(
                JobId=job_id
            )
            job = response["DocumentClassificationJobProperties"]
            logger.info("Got classification job %s.", job["JobName"])
```

```
        except ClientError:
            logger.exception("Couldn't get classification job %s.", job_id)
            raise
        else:
            return job


    def list_jobs(self):
        """
        Lists the classification jobs for the current account.

        :return: The list of jobs.
        """
        try:
            response = self.comprehend_client.list_document_classification_jobs()
            jobs = response["DocumentClassificationJobPropertiesList"]
            logger.info("Got %s document classification jobs.", len(jobs))
        except ClientError:
            logger.exception(
                "Couldn't get document classification jobs.",
            )
            raise
        else:
            return jobs
```

Criar uma classe que execute o cenário.

```
class ClassifierDemo:
    """
    Encapsulates functions used to run the demonstration.
    """

    def __init__(self, demo_resources):
        """
        :param demo_resources: A ComprehendDemoResources class that manages
 resources
                               for the demonstration.
        """
        self.demo_resources = demo_resources
        self.training_prefix = "training/"
```

```
        self.input_prefix = "input/"
        self.input_format = JobInputFormat.per_line
        self.output_prefix = "output/"

    def setup(self):
        """Creates AWS resources used by the demo."""
        self.demo_resources.setup("comprehend-classifier-demo")

    def cleanup(self):
        """Deletes AWS resources used by the demo."""
        self.demo_resources.cleanup()

    @staticmethod
    def _sanitize_text(text):
        """Removes characters that cause errors for the document parser."""
        return text.replace("\r", " ").replace("\n", " ").replace(",", ";")

    @staticmethod
    def _get_issues(query, issue_count):
        """
        Gets issues from GitHub using the specified query parameters.

        :param query: The query string used to request issues from the GitHub API.
        :param issue_count: The number of issues to retrieve.
        :return: The list of issues retrieved from GitHub.
        """
        issues = []
        logger.info("Requesting issues from %s?%s.", GITHUB_SEARCH_URL, query)
        response = requests.get(f"{GITHUB_SEARCH_URL}?
{query}&per_page={issue_count}")
        if response.status_code == 200:
            issue_page = response.json()["items"]
            logger.info("Got %s issues.", len(issue_page))
            issues = [
                {
                    "title": ClassifierDemo._sanitize_text(issue["title"]),
                    "body": ClassifierDemo._sanitize_text(issue["body"]),
                    "labels": {label["name"] for label in issue["labels"]},
                }
                for issue in issue_page
            ]
        else:
            logger.error(
                "GitHub returned error code %s with message %s.",
```

```
                response.status_code,
                response.json(),
            )
        logger.info("Found %s issues.", len(issues))
        return issues

    def get_training_issues(self, training_labels):
        """
        Gets issues used for training the custom classifier. Training issues are
        closed issues from the Boto3 repo that have known labels. Comprehend
        requires a minimum of ten training issues per label.

        :param training_labels: The issue labels to use for training.
        :return: The set of issues used for training.
        """
        issues = []
        per_label_count = 15
        for label in training_labels:
            issues += self._get_issues(
                f"q=type:issue+repo:boto/boto3+state:closed+label:{label}",
                per_label_count,
            )
            for issue in issues:
                issue["labels"] = issue["labels"].intersection(training_labels)
        return issues

    def get_input_issues(self, training_labels):
        """
        Gets input issues from GitHub. For demonstration purposes, input issues
        are open issues from the Boto3 repo with known labels, though in practice
        any issue could be submitted to the classifier for labeling.

        :param training_labels: The set of labels to query for.
        :return: The set of issues used for input.
        """
        issues = []
        per_label_count = 5
        for label in training_labels:
            issues += self._get_issues(
                f"q=type:issue+repo:boto/boto3+state:open+label:{label}",
                per_label_count,
            )
        return issues
```

```
    def upload_issue_data(self, issues, training=False):
        """
        Uploads issue data to an Amazon S3 bucket, either for training or for input.
        The data is first put into the format expected by Comprehend. For training,
        the set of pipe-delimited labels is prepended to each document. For
        input, labels are not sent.

        :param issues: The set of issues to upload to Amazon S3.
        :param training: Indicates whether the issue data is used for training or
                         input.
        """
        try:
            obj_key = (
                self.training_prefix if training else self.input_prefix
            ) + "issues.txt"
            if training:
                issue_strings = [
                    f"{'|'.join(issue['labels'])},{issue['title']} {issue['body']}"
                    for issue in issues
                ]
            else:
                issue_strings = [
                    f"{issue['title']} {issue['body']}" for issue in issues
                ]
            issue_bytes = BytesIO("\n".join(issue_strings).encode("utf-8"))
            self.demo_resources.bucket.upload_fileobj(issue_bytes, obj_key)
            logger.info(
                "Uploaded data as %s to bucket %s.",
                obj_key,
                self.demo_resources.bucket.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload data to bucket %s.",
self.demo_resources.bucket.name
            )
            raise

    def extract_job_output(self, job):
        """Extracts job output from Amazon S3."""
        return self.demo_resources.extract_job_output(job)

    @staticmethod
    def reconcile_job_output(input_issues, output_dict):
```

```
        """
        Reconciles job output with the list of input issues. Because the input
 issues
        have known labels, these can be compared with the labels added by the
        classifier to judge the accuracy of the output.

        :param input_issues: The list of issues used as input.
        :param output_dict: The dictionary of data that is output by the classifier.
        :return: The list of reconciled input and output data.
        """
        reconciled = []
        for archive in output_dict.values():
            for line in archive["data"]:
                in_line = int(line["Line"])
                in_labels = input_issues[in_line]["labels"]
                out_labels = {
                    label["Name"]
                    for label in line["Labels"]
                    if float(label["Score"]) > 0.3
                }
                reconciled.append(
                    f"{line['File']}, line {in_line} has labels {in_labels}.\n"
                    f"\tClassifier assigned {out_labels}."
                )
        logger.info("Reconciled input and output labels.")
        return reconciled
```

Treine um classificador em um conjunto de GitHub problemas com rótulos conhecidos e, em seguida, envie um segundo conjunto de GitHub problemas ao classificador para que eles possam ser rotulados.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Comprehend custom document classifier demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    comp_demo = ClassifierDemo(
        ComprehendDemoResources(boto3.resource("s3"), boto3.resource("iam"))
```

```
    )
    comp_classifier = ComprehendClassifier(boto3.client("comprehend"))
    classifier_trained_waiter = ClassifierTrainedWaiter(
        comp_classifier.comprehend_client
    )
    training_labels = {"bug", "feature-request", "dynamodb", "s3"}

    print("Setting up storage and security resources needed for the demo.")
    comp_demo.setup()

    print("Getting training data from GitHub and uploading it to Amazon S3.")
    training_issues = comp_demo.get_training_issues(training_labels)
    comp_demo.upload_issue_data(training_issues, True)

    classifier_name = "doc-example-classifier"
    print(f"Creating document classifier {classifier_name}.")
    comp_classifier.create(
        classifier_name,
        "en",
        comp_demo.demo_resources.bucket.name,
        comp_demo.training_prefix,
        comp_demo.demo_resources.data_access_role.arn,
        ClassifierMode.multi_label,
    )
    print(
        f"Waiting until {classifier_name} is trained. This typically takes "
        f"30-40 minutes."
    )
    classifier_trained_waiter.wait(comp_classifier.classifier_arn)

    print(f"Classifier {classifier_name} is trained:")
    pprint(comp_classifier.describe())

    print("Getting input data from GitHub and uploading it to Amazon S3.")
    input_issues = comp_demo.get_input_issues(training_labels)
    comp_demo.upload_issue_data(input_issues)

    print("Starting classification job on input data.")
    job_info = comp_classifier.start_job(
        "issue_classification_job",
        comp_demo.demo_resources.bucket.name,
        comp_demo.input_prefix,
        comp_demo.input_format,
        comp_demo.demo_resources.bucket.name,
```

```
        comp_demo.output_prefix,
        comp_demo.demo_resources.data_access_role.arn,
    )
    print(f"Waiting for job {job_info['JobId']} to complete.")
    job_waiter = JobCompleteWaiter(comp_classifier.comprehend_client)
    job_waiter.wait(job_info["JobId"])

    job = comp_classifier.describe_job(job_info["JobId"])
    print(f"Job {job['JobId']} complete:")
    pprint(job)

    print(
        f"Getting job output data from Amazon S3: "
        f"{job['OutputDataConfig']['S3Uri']}."
    )
    job_output = comp_demo.extract_job_output(job)
    print("Job output:")
    pprint(job_output)

    print("Reconciling job output with labels from GitHub:")
    reconciled_output = comp_demo.reconcile_job_output(input_issues, job_output)
    print(*reconciled_output, sep="\n")

    answer = input(f"Do you want to delete the classifier {classifier_name} (y/n)?
")
    if answer.lower() == "y":
        print(f"Deleting {classifier_name}.")
        comp_classifier.delete()

    print("Cleaning up resources created for the demo.")
    comp_demo.cleanup()

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDocumentClassifier
  - DeleteDocumentClassifier

- DescribeDocumentClassificationJob
- DescribeDocumentClassifier
- ListDocumentClassificationJobs
- ListDocumentClassifiers
- StartDocumentClassificationJob

Exemplos de AWS Config usando o SDK para Python (Boto3)

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com AWS Config.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir uma regra

O exemplo de código a seguir mostra como excluir uma regra do AWS Config.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def delete_config_rule(self, rule_name):
        """
        Delete the specified rule.

        :param rule_name: The name of the rule to delete.
        """
        try:
            self.config_client.delete_config_rule(ConfigRuleName=rule_name)
            logger.info("Deleted rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't delete rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteConfigRuleReferência da API AWSSDK for Python (Boto3).

Descrever regras

Os exemplos de código a seguir mostram como descrever regras do AWS Config.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def describe_config_rule(self, rule_name):
        """
        Gets data for the specified rule.

        :param rule_name: The name of the rule to retrieve.
        :return: The rule data.
        """
        try:
            response = self.config_client.describe_config_rules(
                ConfigRuleNames=[rule_name]
            )
            rule = response["ConfigRules"]
            logger.info("Got data for rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't get data for rule %s.", rule_name)
            raise
        else:
            return rule
```

- Para obter detalhes da API, consulte a DescribeConfigRulesReferência da API AWSSDK for Python (Boto3).

Inserir uma regra

O exemplo de código a seguir mostra como inserir uma regra do AWS Config.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ConfigWrapper:
    """
    Encapsulates AWS Config functions.
    """

    def __init__(self, config_client):
        """
        :param config_client: A Boto3 AWS Config client.
        """
        self.config_client = config_client


    def put_config_rule(self, rule_name):
        """
        Sets a configuration rule that prohibits making Amazon S3 buckets publicly
        readable.

        :param rule_name: The name to give the rule.
        """
        try:
            self.config_client.put_config_rule(
                ConfigRule={
                    "ConfigRuleName": rule_name,
                    "Description": "S3 Public Read Prohibited Bucket Rule",
                    "Scope": {
                        "ComplianceResourceTypes": [
                            "AWS::S3::Bucket",
                        ],
                    },
                    "Source": {
                        "Owner": "AWS",
                        "SourceIdentifier": "S3_BUCKET_PUBLIC_READ_PROHIBITED",
                    },
                    "InputParameters": "{}",
```

```
                    "ConfigRuleState": "ACTIVE",
                }
            )
            logger.info("Created configuration rule %s.", rule_name)
        except ClientError:
            logger.exception("Couldn't create configuration rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a PutConfigRuleReferência da API AWSSDK for Python (Boto3).

Exemplos de Device Farm usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Device Farm.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Cenários

Cenários

Executar testes de navegador e capturar tela

O exemplo de código a seguir mostra como executar testes de navegador com o Device Farm e fazer capturas de tela.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Use o PyTest Selenium para navegar até sites específicos, fazer capturas de tela e comparar o conteúdo real do site com o conteúdo esperado.

```
import datetime
import os
import subprocess
import boto3
import pytest
from selenium import webdriver
from selenium.webdriver import DesiredCapabilities
from selenium.webdriver.common.by import By
from selenium.webdriver.common.keys import Keys
from selenium.webdriver.support import expected_conditions
from selenium.webdriver.support.wait import WebDriverWait


def get_git_hash():
    """
    Get the short Git hash of the current commit of the repository
    """
    try:
        return (
            subprocess.check_output(["git", "rev-parse", "--short", "HEAD"])
            .decode("utf-8")
            .strip()
        )
    except:
        return "norepo"


class TestHelloSuite:
    """
    Our test suite.
```

```
    This style of test suite allows us to use setup_method and teardown_method.

    """

    def save_screenshot(self, name):
        self.driver.save_screenshot(os.path.join(self.screenshot_path, name))

    def setup_method(self, method):
        """
        Set up a test.

        This makes sure that the session for an individual test is ready.

        The AWS credentials are read from the default ~/.aws/credentials or from the
        command line by setting the AWS_ACCESS_KEY_ID and AWS_SECRET_KEY environment
        variables.

        The project Amazon Resource Name (ARN) is determined by the PROJECT_ARN
        environment variable.
        """
        devicefarm_client = boto3.client("devicefarm")
        project_arn = os.environ.get("PROJECT_ARN", None)
        if project_arn is None:
            raise ValueError("Must set PROJECT_ARN")
        # Request a driver hub URL for the Selenium client
        testgrid_url_response = devicefarm_client.create_test_grid_url(
            projectArn=project_arn, expiresInSeconds=300
        )

        # We want a directory to save our files into. We're going to make a
directory
        # in the current directory that holds our results.
        self.screenshot_path = os.path.join(
            ".", "results", get_git_hash() + "-" +
(datetime.date.today().isoformat())
        )
        if not os.path.exists(self.screenshot_path):
            os.makedirs(self.screenshot_path, exist_ok=True)

        # We want a Firefox instance on Windows
        desired_cap = DesiredCapabilities.FIREFOX
        desired_cap["platform"] = "windows"
        desired_cap["BrowserVersion"] = "latest"
```

```
        # Configure the webdriver with the appropriate remote endpoint.
        self.driver = webdriver.Remote(testgrid_url_response["url"], desired_cap)

        #
        # Auto-Tagging
        #

        # In order to get the Session ARN, we need to look up the session by the
        # Project ARN and session ID (from the driver).
        testgrid_session_arn_response = devicefarm_client.get_test_grid_session(
            projectArn=project_arn, sessionId=self.driver.session_id
        )

        # Save the session's ARN so we can tag the session.
        self.session_arn = testgrid_session_arn_response["testGridSession"]["arn"]

        # In order to tag it, we're going to use the resourcegroupstaggingapi client
to
        # add a tag to the session ARN that we just got.
        tag_client = boto3.client("resourcegroupstaggingapi")
        tag_client.tag_resources(
            ResourceARNList=[self.session_arn],
            Tags={"TestSuite": f"testsuite {method.__name__}", "GitId":
get_git_hash()},
        )

    def teardown_method(self, method):
        """
        Clean up resources used by each method.
        """
        # End the Selenium session so we're off the clock.
        self.driver.quit()

    @pytest.mark.parametrize(
        "query,leading",
        [
            pytest.param(
                "Seattle",
                "Seattle (/si#ætəl/ (listen) see-AT-əl) is a seaport city on the
West Coast of the United States.",
            ),
            pytest.param(
                "Selenium",
```

```
                "Selenium is a chemical element with the symbol Se and atomic number
34.",
            ),
            pytest.param(
                "Amazon Locker",
                "Amazon Locker is a self-service package delivery service offered by
online retailer Amazon.",
            ),
            pytest.param(
                "Kootenai Falls",
                "Kootenai Falls is a waterfall on the Kootenay River located in
Lincoln County, Montana, just off U.S. Route 2.",
            ),
            pytest.param(
                "Dorayaki",
                "Dorayaki (####, ####, ####, ####) is a type of Japanese
confection.",
            ),
            pytest.param("Robot Face", "<|°_°|> (also known as Robot Face or
Robot)"),
        ],
    )
    def test_first_paragraph_text(self, query, leading):
        """
        This test looks at the first paragraph of a page on Wikipedia, comparing it
to
        a known leading sentence.

        If the leading sentence matches, the test passes. A screenshot is taken
before
        the final assertion is made, letting us debug if something isn't right.
        """
        # Open the main page of Wikipedia
        self.driver.get("https://en.wikipedia.org/wiki/Main_Page")
        # Find the search box, enter a query, and press enter
        search_input = self.driver.find_element(By.ID, "searchInput")
        search_input.click()
        search_input.send_keys(query)
        search_input.send_keys(Keys.ENTER)
        # Wait for the search box to go stale -- This means we've navigated fully.
        WebDriverWait(self.driver, 5).until(
            expected_conditions.staleness_of(search_input)
        )
        # Get the leading paragraph of the article.
```

```
        lead = leading.lower()
        # Find the element...
        lead_para = self.driver.find_element(
            By.XPATH, "//div[@class='mw-parser-output']//p[not(@class)]"
        )
        # ... and copy out its text.
        our_text = lead_para.text.lower()
        our_text = our_text[: len(lead)]
        # Take a screenshot and compare the strings.
        self.save_screenshot(f"leadingpara_{query}.png")
        assert our_text.startswith(lead)

    @pytest.mark.parametrize(
        "query,expected",
        [
            pytest.param("Automation Testing", "Test Automation"),
            pytest.param("DevOps", "DevOps"),
            pytest.param("Jackdaws Love My Big Sphinx Of Quartz", "Pangram"),
            pytest.param("EarthBound", "EarthBound"),
            pytest.param("Covered Bridges Today", "Covered Bridges Today"),
            pytest.param("Kurt Godel", "Kurt Gödel"),
            pytest.param("N//ng language", "N#ng language"),
            pytest.param(
                "Who the Frick Is Jackson Pollock?", "Who the $&% Is Jackson
Pollock?"
            ),
        ],
    )
    def test_redirect_titles(self, query, expected):
        """
        A test comparing pages we expect to (or not to) redirect on Wikipedia.

        This test checks to see that the page ("query") redirects (or doesn't) to
the
        "expected" page title. Several of these are common synonyms ("Jackdaws...")
        while others are because of characters untypable by most keyboards ("N#ng
language")

        A screenshot is taken just before the final assertion is made to aid in
        debugging and verification.
        """
        # Open the main page of Wikipedia
        self.driver.get("https://en.wikipedia.org/wiki/Main_Page")
        # Find the search box, enter some text into it, and send an enter key.
```

```
        search_input = self.driver.find_element(By.ID, "searchInput")
        search_input.click()
        search_input.send_keys(query)
        search_input.send_keys(Keys.ENTER)
        # wait until the page has rolled over -- once the search input handle is
stale,
        # the browser has navigated.
        WebDriverWait(self.driver, 5).until(
            expected_conditions.staleness_of(search_input)
        )
        # Get the first heading & take a screenshot
        our_text = self.driver.find_element(By.ID, "firstHeading").text.lower()
        self.save_screenshot(f"redirect_{query}.png")
        # did it match?
        assert our_text == expected.lower()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTestGridUrl
  - GetTestGridSession

Carregar e testar pacotes de dispositivos

O exemplo de código a seguir mostra como fazer upload e testar pacotes de dispositivos móveis com o Device Farm.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Fazer upload de aplicativos Android compilados e pacotes de teste para o Device Farm, iniciar um teste, aguardar a conclusão do teste e relatar os resultados.

```
import boto3
import os
import requests
import string
import random
import datetime
import time

# Update this dict with your own values before you run the example:
config = {
    # This is our app under test.
    "appFilePath": "app-debug.apk",
    "projectArn": "arn:aws:devicefarm:us-west-2:111222333444:project:581f5703-
e040-4ac9-b7ae-0ba007bfb8e6",
    # Since we care about the most popular devices, we'll use a curated pool.
    "testSpecArn": "arn:aws:devicefarm:us-west-2::upload:20fcf771-eae3-4137-
aa76-92e17fb3131b",
    "poolArn": "arn:aws:devicefarm:us-
west-2::devicepool:4a869d91-6f17-491f-9a95-0a601aee2406",
    "namePrefix": "MyAppTest",
    # This is our test package. This tutorial won't go into how to make these.
    "testPackage": "tests.zip",
}

client = boto3.client("devicefarm")

unique = (
    config["namePrefix"]
    + "-"
    + (datetime.date.today().isoformat())
    + ("".join(random.sample(string.ascii_letters, 8)))
)

print(
    f"The unique identifier for this run is '{unique}'. All uploads will be prefixed
 "
    f"with this."
)


def upload_df_file(filename, type_, mime="application/octet-stream"):
    upload_response = client.create_upload(
        projectArn=config["projectArn"],
```

```
        name=unique + "_" + os.path.basename(filename),
        type=type_,
        contentType=mime,
    )
    upload_arn = upload_response["upload"]["arn"]
    # Extract the URL of the upload and use Requests to upload it.
    upload_url = upload_response["upload"]["url"]
    with open(filename, "rb") as file_stream:
        print(
            f"Uploading {filename} to Device Farm as "
            f"{upload_response['upload']['name']}... ",
            end="",
        )
        put_req = requests.put(
            upload_url, data=file_stream, headers={"content-type": mime}
        )
        print(" done")
        if not put_req.ok:
            raise Exception(f"Couldn't upload. Requests says: {put_req.reason}")
    started = datetime.datetime.now()
    while True:
        print(
            f"Upload of {filename} in state {upload_response['upload']['status']} "
            f"after " + str(datetime.datetime.now() - started)
        )
        if upload_response["upload"]["status"] == "FAILED":
            raise Exception(
                f"The upload failed processing. Device Farm says the reason is: \n"
                f"{+upload_response['upload']['message']}"
            )
        if upload_response["upload"]["status"] == "SUCCEEDED":
            break
        time.sleep(5)
        upload_response = client.get_upload(arn=upload_arn)
    print("")
    return upload_arn


our_upload_arn = upload_df_file(config["appFilePath"], "ANDROID_APP")
our_test_package_arn = upload_df_file(
    config["testPackage"], "APPIUM_PYTHON_TEST_PACKAGE"
)
print(our_upload_arn, our_test_package_arn)
```

```
response = client.schedule_run(
    projectArn=config["projectArn"],
    appArn=our_upload_arn,
    devicePoolArn=config["poolArn"],
    name=unique,
    test={
        "type": "APPIUM_PYTHON",
        "testSpecArn": config["testSpecArn"],
        "testPackageArn": our_test_package_arn,
    },
)
run_arn = response["run"]["arn"]
start_time = datetime.datetime.now()
print(f"Run {unique} is scheduled as arn {run_arn} ")

state = "UNKNOWN"
try:
    while True:
        response = client.get_run(arn=run_arn)
        state = response["run"]["status"]
        if state == "COMPLETED" or state == "ERRORED":
            break
        else:
            print(
                f" Run {unique} in state {state}, total "
                f"time {datetime.datetime.now() - start_time}"
            )
            time.sleep(10)
except:
    client.stop_run(arn=run_arn)
    exit(1)

print(f"Tests finished in state {state} after {datetime.datetime.now() -
 start_time}")
# Pull all the logs.
jobs_response = client.list_jobs(arn=run_arn)
# Save the output somewhere, using the unique value.
save_path = os.path.join(os.getcwd(), "results", unique)
os.mkdir(save_path)
# Save the last run information.
for job in jobs_response["jobs"]:
    job_name = job["name"]
    os.makedirs(os.path.join(save_path, job_name), exist_ok=True)
    # Get each suite within the job.
```

```
    suites = client.list_suites(arn=job["arn"])["suites"]
    for suite in suites:
        for test in client.list_tests(arn=suite["arn"])["tests"]:
            # Get the artifacts.
            for artifact_type in ["FILE", "SCREENSHOT", "LOG"]:
                artifacts = client.list_artifacts(type=artifact_type,
 arn=test["arn"])[
                    "artifacts"
                ]
                for artifact in artifacts:
                    # Replace `:` because it has a special meaning in Windows &
 macOS.
                    path_to = os.path.join(
                        save_path,
                        job_name,
                        suite["name"],
                        test["name"].replace(":", "_"),
                    )
                    os.makedirs(path_to, exist_ok=True)
                    filename = (
                        artifact["type"]
                        + "_"
                        + artifact["name"]
                        + "."
                        + artifact["extension"]
                    )
                    artifact_save_path = os.path.join(path_to, filename)
                    print(f"Downloading {artifact_save_path}")
                    with open(artifact_save_path, "wb") as fn:
                        with requests.get(
                            artifact["url"], allow_redirects=True
                        ) as request:
                            fn.write(request.content)
print("Finished")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateUpload
  - GetRun
  - GetUpload
  - ListArtifacts

- ListJobs
- ListSuites
- ListTests
- ScheduleRun
- StopRun

Exemplos de DynamoDB usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela para armazenar dados de filmes.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.

        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {"AttributeName": "year", "KeyType": "HASH"},  # Partition key
                    {"AttributeName": "title", "KeyType": "RANGE"},  # Sort key
                ],
                AttributeDefinitions=[
                    {"AttributeName": "year", "AttributeType": "N"},
                    {"AttributeName": "title", "AttributeType": "S"},
                ],
                ProvisionedThroughput={
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 10,
                },
            )
            self.table.wait_until_exists()
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
```

```
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.table
```

- Para obter detalhes da API, consulte a CreateTableReferência da API AWSSDK for Python (Boto3).

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def delete_table(self):
        """
        Deletes the table.
```

```
        """
        try:
            self.table.delete()
            self.table = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None
```

```
    def delete_movie(self, title, year):
        """
        Deletes a movie from the table.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        """
        try:
            self.table.delete_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s",
                title,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

É possível especificar uma condição para que um item seja excluído somente quando ele atender a determinados critérios.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def delete_underrated_movie(self, title, year, rating):
        """
        Deletes a movie only if it is rated below a specified value. By using a
        condition expression in a delete operation, you can specify that an item is
        deleted only when it meets certain criteria.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        :param rating: The rating threshold to check before deleting the movie.
        """
        try:
            self.table.delete_item(
                Key={"year": year, "title": title},
                ConditionExpression="info.rating <= :val",
```

```
                ExpressionAttributeValues={":val": Decimal(str(rating))},
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ConditionalCheckFailedException":
                logger.warning(
                    "Didn't delete %s because its rating is greater than %s.",
                    title,
                    rating,
                )
            else:
                logger.error(
                    "Couldn't delete movie %s. Here's why: %s: %s",
                    title,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
```

- Para obter detalhes da API, consulte a DeleteItemReferência da API AWSSDK for Python (Boto3).

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import decimal
import json
import logging
import os
import pprint
import time
import boto3
```

```
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
dynamodb = boto3.resource("dynamodb")

MAX_GET_SIZE = 100  # Amazon DynamoDB rejects a get batch larger than 100 items.


def do_batch_get(batch_keys):
    """
    Gets a batch of items from Amazon DynamoDB. Batches can contain keys from
    more than one table.

    When Amazon DynamoDB cannot process all items in a batch, a set of unprocessed
    keys is returned. This function uses an exponential backoff algorithm to retry
    getting the unprocessed keys until all are retrieved or the specified
    number of tries is reached.

    :param batch_keys: The set of keys to retrieve. A batch can contain at most 100
                       keys. Otherwise, Amazon DynamoDB returns an error.
    :return: The dictionary of retrieved items grouped under their respective
             table names.
    """
    tries = 0
    max_tries = 5
    sleepy_time = 1  # Start with 1 second of sleep, then exponentially increase.
    retrieved = {key: [] for key in batch_keys}
    while tries < max_tries:
        response = dynamodb.batch_get_item(RequestItems=batch_keys)
        # Collect any retrieved items and retry unprocessed keys.
        for key in response.get("Responses", []):
            retrieved[key] += response["Responses"][key]
        unprocessed = response["UnprocessedKeys"]
        if len(unprocessed) > 0:
            batch_keys = unprocessed
            unprocessed_count = sum(
                [len(batch_key["Keys"]) for batch_key in batch_keys.values()]
            )
            logger.info(
                "%s unprocessed keys returned. Sleep, then retry.",
 unprocessed_count
            )
            tries += 1
            if tries < max_tries:
```

```
                logger.info("Sleeping for %s seconds.", sleepy_time)
                time.sleep(sleepy_time)
                sleepy_time = min(sleepy_time * 2, 32)
        else:
            break

    return retrieved
```

- Para obter detalhes da API, consulte a BatchGetItemReferência da API AWSSDK for Python (Boto3).

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def get_movie(self, title, year):
        """
```

```
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Item"]
```

- Para obter detalhes da API, consulte a GetItemReferência da API AWSSDK for Python (Boto3).

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
```

```
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                exists = False
            else:
                logger.error(
                    "Couldn't check for existence of %s. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            self.table = table
        return exists
```

- Para obter detalhes da API, consulte a DescribeTableReferência da API AWSSDK for Python (Boto3).

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def list_tables(self):
        """
        Lists the Amazon DynamoDB tables for the current account.

        :return: The list of tables.
        """
        try:
            tables = []
            for table in self.dyn_resource.tables.all():
                print(table.name)
                tables.append(table)
        except ClientError as err:
            logger.error(
                "Couldn't list tables. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tables
```

- Para obter detalhes da API, consulte a ListTablesReferência da API AWSSDK for Python (Boto3).

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
```

```
                Item={
                    "year": year,
                    "title": title,
                    "info": {"plot": plot, "rating": Decimal(str(rating))},
                }
            )
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a PutItemReferência da API AWSSDK for Python (Boto3).

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Consulte itens usando uma expressão de condição de chave.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
```

```
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def query_movies(self, year):
        """
        Queries for movies that were released in the specified year.

        :param year: The year to query.
        :return: The list of movies that were released in the specified year.
        """
        try:
            response = self.table.query(KeyConditionExpression=Key("year").eq(year))
        except ClientError as err:
            logger.error(
                "Couldn't query for movies released in %s. Here's why: %s: %s",
                year,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Items"]
```

Consulte itens e projete-os para retornar um subconjunto de dados.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def query_and_project_movies(self, year, title_bounds):
        """
        Query for movies that were released in a specified year and that have titles
        that start within a range of letters. A projection expression is used
        to return a subset of data for each movie.

        :param year: The release year to query.
        :param title_bounds: The range of starting letters to query.
        :return: The list of movies.
```

```
        """
        try:
            response = self.table.query(
                ProjectionExpression="#yr, title, info.genres, info.actors[0]",
                ExpressionAttributeNames={"#yr": "year"},
                KeyConditionExpression=(
                    Key("year").eq(year)
                    & Key("title").between(
                        title_bounds["first"], title_bounds["second"]
                    )
                ),
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ValidationException":
                logger.warning(
                    "There's a validation error. Here's the message: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            else:
                logger.error(
                    "Couldn't query for movies. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return response["Items"]
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Python (Boto3).

Executar uma instrução PartiQL

Os exemplos de código a seguir mostram como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PartiQLWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statement, params):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
 to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statement: The PartiQL statement.
        :param params: The list of PartiQL parameters. These are applied to the
                       statement in the order they are listed.
        :return: The items returned from the statement, if any.
        """
        try:
            output = self.dyn_resource.meta.client.execute_statement(
                Statement=statement, Parameters=params
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
```

```
                    "Couldn't execute PartiQL '%s' because the table does not
 exist.",
                    statement,
                )
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s",
                    statement,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

- Para obter detalhes da API, consulte a ExecuteStatementReferência da API AWSSDK for Python (Boto3).

Executar lotes de instruções PartiQL

O exemplo de código a seguir mostra como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
```

```
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statements, param_list):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statements: The batch of PartiQL statements.
        :param param_list: The batch of PartiQL parameters that are associated with
                           each statement. This list must be in the same order as
the
                           statements.
        :return: The responses returned from running the statements, if any.
        """
        try:
            output = self.dyn_resource.meta.client.batch_execute_statement(
                Statements=[
                    {"Statement": statement, "Parameters": params}
                    for statement, params in zip(statements, param_list)
                ]
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute batch of PartiQL statements because the table
"
                    "does not exist."
                )
            else:
                logger.error(
                    "Couldn't execute batch of PartiQL statements. Here's why: %s:
%s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
```

```
            return output
```

- Para obter detalhes da API, consulte a BatchExecuteStatementReferência da API AWSSDK for Python (Boto3).

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def scan_movies(self, year_range):
        """
        Scans for movies that were released in a range of years.
        Uses a projection expression to return a subset of data for each movie.

        :param year_range: The range of years to retrieve.
        :return: The list of movies released in the specified years.
        """
        movies = []
        scan_kwargs = {
```

```
            "FilterExpression": Key("year").between(
                year_range["first"], year_range["second"]
            ),
            "ProjectionExpression": "#yr, title, info.rating",
            "ExpressionAttributeNames": {"#yr": "year"},
        }
        try:
            done = False
            start_key = None
            while not done:
                if start_key:
                    scan_kwargs["ExclusiveStartKey"] = start_key
                response = self.table.scan(**scan_kwargs)
                movies.extend(response.get("Items", []))
                start_key = response.get("LastEvaluatedKey", None)
                done = start_key is None
        except ClientError as err:
            logger.error(
                "Couldn't scan for movies. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

        return movies
```

- Para ver os detalhes da API, consulte Scan na Referência da API do AWS SDK para Python (Boto3).

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Atualize um item usando uma expressão de atualização.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to the give the movie.
        :param plot: The updated plot summary to give the movie.
        :return: The fields that were updated, with their new values.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
                ExpressionAttributeValues={":r": Decimal(str(rating)), ":p": plot},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]
```

Atualize um item usando uma expressão de atualização que inclui uma operação aritmética.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def update_rating(self, title, year, rating_change):
        """
        Updates the quality rating of a movie in the table by using an arithmetic
        operation in the update expression. By specifying an arithmetic operation,
        you can adjust a value in a single request, rather than first getting its
        value and then setting its new value.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating_change: The amount to add to the current rating for the movie.
        :return: The updated rating.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating = info.rating + :val",
                ExpressionAttributeValues={":val": Decimal(str(rating_change))},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]
```

Atualize um item somente quando ele atender a determinadas condições.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table


    def remove_actors(self, title, year, actor_threshold):
        """
        Removes an actor from a movie, but only when the number of actors is greater
        than a specified threshold. If the movie does not list more than the
 threshold,
        no actors are removed.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param actor_threshold: The threshold of actors to check.
        :return: The movie data after the update.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="remove info.actors[0]",
                ConditionExpression="size(info.actors) > :num",
                ExpressionAttributeValues={":num": actor_threshold},
                ReturnValues="ALL_NEW",
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ConditionalCheckFailedException":
                logger.warning(
                    "Didn't update %s because it has fewer than %s actors.",
                    title,
                    actor_threshold + 1,
                )
            else:
                logger.error(
                    "Couldn't update movie %s. Here's why: %s: %s",
                    title,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return response["Attributes"]
```

- Para obter detalhes da API, consulte a UpdateItemReferência da API AWSSDK for Python (Boto3).

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None


    def write_batch(self, movies):
        """
        Fills an Amazon DynamoDB table with the specified data, using the Boto3
        Table.batch_writer() function to put the items in the table.
        Inside the context manager, Table.batch_writer builds a list of
        requests. On exiting the context manager, Table.batch_writer starts sending
        batches of write requests to Amazon DynamoDB and automatically
        handles chunking, buffering, and retrying.

        :param movies: The data to put in the table. Each item must contain at least
                       the keys required by the schema that was specified when the
```

```
                        table was created.
        """
        try:
            with self.table.batch_writer() as writer:
                for movie in movies:
                    writer.put_item(Item=movie)
        except ClientError as err:
            logger.error(
                "Couldn't load data into table %s. Here's why: %s: %s",
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a BatchWriteItemReferência da API AWSSDK for Python (Boto3).

Cenários

Acelerar leituras com o DAX

O código de exemplo a seguir mostra como:

- Criar e gravar dados em uma tabela com os clientes DAX e SDK.
- Obter, consultar e verificar a tabela com ambos os clientes e comparar a respectiva performance.

Para obter mais informações, consulte Desenvolver com o cliente do DynamoDB Accelerator.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma tabela com o cliente do DAX ou Boto3.

```
import boto3


def create_dax_table(dyn_resource=None):
    """
    Creates a DynamoDB table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The newly created table.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table_name = "TryDaxTable"
    params = {
        "TableName": table_name,
        "KeySchema": [
            {"AttributeName": "partition_key", "KeyType": "HASH"},
            {"AttributeName": "sort_key", "KeyType": "RANGE"},
        ],
        "AttributeDefinitions": [
            {"AttributeName": "partition_key", "AttributeType": "N"},
            {"AttributeName": "sort_key", "AttributeType": "N"},
        ],
        "ProvisionedThroughput": {"ReadCapacityUnits": 10, "WriteCapacityUnits":
 10},
    }
    table = dyn_resource.create_table(**params)
    print(f"Creating {table_name}...")
    table.wait_until_exists()
    return table


if __name__ == "__main__":
    dax_table = create_dax_table()
    print(f"Created table.")
```

Grave dados de teste na tabela.

```
import boto3
```

```
def write_data_to_dax_table(key_count, item_size, dyn_resource=None):
    """
    Writes test data to the demonstration table.

    :param key_count: The number of partition and sort keys to use to populate the
                      table. The total number of items is key_count * key_count.
    :param item_size: The size of non-key data for each test item.
    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    some_data = "X" * item_size

    for partition_key in range(1, key_count + 1):
        for sort_key in range(1, key_count + 1):
            table.put_item(
                Item={
                    "partition_key": partition_key,
                    "sort_key": sort_key,
                    "some_data": some_data,
                }
            )
            print(f"Put item ({partition_key}, {sort_key}) succeeded.")


if __name__ == "__main__":
    write_key_count = 10
    write_item_size = 1000
    print(
        f"Writing {write_key_count*write_key_count} items to the table. "
        f"Each item is {write_item_size} characters."
    )
    write_data_to_dax_table(write_key_count, write_item_size)
```

Obtenha itens para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import sys
import time
```

```
import amazondax
import boto3


def get_item_test(key_count, iterations, dyn_resource=None):
    """
    Gets items from the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param key_count: The number of items to get from the table in each iteration.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    start = time.perf_counter()
    for _ in range(iterations):
        for partition_key in range(1, key_count + 1):
            for sort_key in range(1, key_count + 1):
                table.get_item(
                    Key={"partition_key": partition_key, "sort_key": sort_key}
                )
                print(".", end="")
                sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()
```

```
    test_key_count = 10
    test_iterations = 50
    if args.endpoint_url:
        print(
            f"Getting each item from the table {test_iterations} times, "
            f"using the DAX client."
        )
        # Use a with statement so the DAX client closes the cluster after
 completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as
 dax:
            test_start, test_end = get_item_test(
                test_key_count, test_iterations, dyn_resource=dax
            )
    else:
        print(
            f"Getting each item from the table {test_iterations} times, "
            f"using the Boto3 client."
        )
        test_start, test_end = get_item_test(test_key_count, test_iterations)
    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
        f"{(test_end - test_start)/ test_iterations}."
    )
```

Consulte a tabela para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import time
import sys
import amazondax
import boto3
from boto3.dynamodb.conditions import Key


def query_test(partition_key, sort_keys, iterations, dyn_resource=None):
    """
    Queries the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.
```

```
    :param partition_key: The partition key value to use in the query. The query
                          returns items that have partition keys equal to this
 value.
    :param sort_keys: The range of sort key values for the query. The query returns
                      items that have sort key values between these two values.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    key_condition_expression = Key("partition_key").eq(partition_key) & Key(
        "sort_key"
    ).between(*sort_keys)

    start = time.perf_counter()
    for _ in range(iterations):
        table.query(KeyConditionExpression=key_condition_expression)
        print(".", end="")
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()

    test_partition_key = 5
    test_sort_keys = (2, 9)
    test_iterations = 100
    if args.endpoint_url:
        print(f"Querying the table {test_iterations} times, using the DAX client.")
```

```
        # Use a with statement so the DAX client closes the cluster after
completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as
dax:
            test_start, test_end = query_test(
                test_partition_key, test_sort_keys, test_iterations,
dyn_resource=dax
            )
    else:
        print(f"Querying the table {test_iterations} times, using the Boto3
client.")
        test_start, test_end = query_test(
            test_partition_key, test_sort_keys, test_iterations
        )

    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
        f"{(test_end - test_start)/test_iterations}."
    )
```

Verifique a tabela para várias iterações associadas ao cliente do DAX e ao cliente do Boto3 e relate o tempo gasto para cada um.

```
import argparse
import time
import sys
import amazondax
import boto3


def scan_test(iterations, dyn_resource=None):
    """
    Scans the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")
```

```
    table = dyn_resource.Table("TryDaxTable")
    start = time.perf_counter()
    for _ in range(iterations):
        table.scan()
        print(".", end="")
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == "__main__":
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "endpoint_url",
        nargs="?",
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not
 used.",
    )
    args = parser.parse_args()

    test_iterations = 100
    if args.endpoint_url:
        print(f"Scanning the table {test_iterations} times, using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after
 completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as
 dax:
            test_start, test_end = scan_test(test_iterations, dyn_resource=dax)
    else:
        print(f"Scanning the table {test_iterations} times, using the Boto3
 client.")
        test_start, test_end = scan_test(test_iterations)
    print(
        f"Total time: {test_end - test_start:.4f} sec. Average time: "
        f"{(test_end - test_start)/test_iterations}."
    )
```

Exclua a tabela.

```
import boto3


def delete_dax_table(dyn_resource=None):
    """
    Deletes the demonstration table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource("dynamodb")

    table = dyn_resource.Table("TryDaxTable")
    table.delete()

    print(f"Deleting {table.name}...")
    table.wait_until_not_exists()


if __name__ == "__main__":
    delete_dax_table()
    print("Table deleted!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTable
  - DeleteTable
  - GetItem
  - PutItem
  - Query
  - Scan

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.

- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que encapsule uma tabela do DynamoDB.

```
from decimal import Decimal
from io import BytesIO
import json
import logging
import os
from pprint import pprint
import requests
from zipfile import ZipFile
import boto3
from boto3.dynamodb.conditions import Key
from botocore.exceptions import ClientError
from question import Question

logger = logging.getLogger(__name__)

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        # The table variable is set during the scenario in the call to
        # 'exists' if the table exists. Otherwise, it is set by 'create_table'.
        self.table = None
```

```
    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                exists = False
            else:
                logger.error(
                    "Couldn't check for existence of %s. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            self.table = table
        return exists


    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.

        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {"AttributeName": "year", "KeyType": "HASH"},  # Partition key
```

```
                    {"AttributeName": "title", "KeyType": "RANGE"},  # Sort key
                ],
                AttributeDefinitions=[
                    {"AttributeName": "year", "AttributeType": "N"},
                    {"AttributeName": "title", "AttributeType": "S"},
                ],
                ProvisionedThroughput={
                    "ReadCapacityUnits": 10,
                    "WriteCapacityUnits": 10,
                },
            )
            self.table.wait_until_exists()
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.table


    def list_tables(self):
        """
        Lists the Amazon DynamoDB tables for the current account.

        :return: The list of tables.
        """
        try:
            tables = []
            for table in self.dyn_resource.tables.all():
                print(table.name)
                tables.append(table)
        except ClientError as err:
            logger.error(
                "Couldn't list tables. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tables
```

```
    def write_batch(self, movies):
        """
        Fills an Amazon DynamoDB table with the specified data, using the Boto3
        Table.batch_writer() function to put the items in the table.
        Inside the context manager, Table.batch_writer builds a list of
        requests. On exiting the context manager, Table.batch_writer starts sending
        batches of write requests to Amazon DynamoDB and automatically
        handles chunking, buffering, and retrying.

        :param movies: The data to put in the table. Each item must contain at least
                       the keys required by the schema that was specified when the
                       table was created.
        """
        try:
            with self.table.batch_writer() as writer:
                for movie in movies:
                    writer.put_item(Item=movie)
        except ClientError as err:
            logger.error(
                "Couldn't load data into table %s. Here's why: %s: %s",
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    "year": year,
                    "title": title,
                    "info": {"plot": plot, "rating": Decimal(str(rating))},
```

```
                }
            )
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Item"]


    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to the give the movie.
        :param plot: The updated plot summary to give the movie.
```

```
        :return: The fields that were updated, with their new values.
        """
        try:
            response = self.table.update_item(
                Key={"year": year, "title": title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
                ExpressionAttributeValues={":r": Decimal(str(rating)), ":p": plot},
                ReturnValues="UPDATED_NEW",
            )
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title,
                self.table.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Attributes"]


    def query_movies(self, year):
        """
        Queries for movies that were released in the specified year.

        :param year: The year to query.
        :return: The list of movies that were released in the specified year.
        """
        try:
            response = self.table.query(KeyConditionExpression=Key("year").eq(year))
        except ClientError as err:
            logger.error(
                "Couldn't query for movies released in %s. Here's why: %s: %s",
                year,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Items"]


    def scan_movies(self, year_range):
```

```
        """
        Scans for movies that were released in a range of years.
        Uses a projection expression to return a subset of data for each movie.

        :param year_range: The range of years to retrieve.
        :return: The list of movies released in the specified years.
        """
        movies = []
        scan_kwargs = {
            "FilterExpression": Key("year").between(
                year_range["first"], year_range["second"]
            ),
            "ProjectionExpression": "#yr, title, info.rating",
            "ExpressionAttributeNames": {"#yr": "year"},
        }
        try:
            done = False
            start_key = None
            while not done:
                if start_key:
                    scan_kwargs["ExclusiveStartKey"] = start_key
                response = self.table.scan(**scan_kwargs)
                movies.extend(response.get("Items", []))
                start_key = response.get("LastEvaluatedKey", None)
                done = start_key is None
        except ClientError as err:
            logger.error(
                "Couldn't scan for movies. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise

        return movies


    def delete_movie(self, title, year):
        """
        Deletes a movie from the table.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        """
        try:
```

```
            self.table.delete_item(Key={"year": year, "title": title})
        except ClientError as err:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s",
                title,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_table(self):
        """
        Deletes the table.
        """
        try:
            self.table.delete()
            self.table = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
def get_sample_movie_data(movie_file_name):
    """
    Gets sample movie data, either from a local file or by first downloading it from
    the Amazon DynamoDB developer guide.

    :param movie_file_name: The local file name where the movie data is stored in
 JSON format.
    :return: The movie data as a dict.
    """
    if not os.path.isfile(movie_file_name):
        print(f"Downloading {movie_file_name}...")
```

```
        movie_content = requests.get(
            "https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
samples/moviedata.zip"
        )
        movie_zip = ZipFile(BytesIO(movie_content.content))
        movie_zip.extractall()

    try:
        with open(movie_file_name) as movie_file:
            movie_data = json.load(movie_file, parse_float=Decimal)
    except FileNotFoundError:
        print(
            f"File {movie_file_name} not found. You must first download the file to
 "
            "run this demo. See the README for instructions."
        )
        raise
    else:
        # The sample file lists over 4000 movies, return only the first 250.
        return movie_data[:250]
```

Execute um cenário interativo para criar a tabela e executar ações nela.

```
def run_scenario(table_name, movie_file_name, dyn_resource):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB getting started demo.")
    print("-" * 88)

    movies = Movies(dyn_resource)
    movies_exists = movies.exists(table_name)
    if not movies_exists:
        print(f"\nCreating table {table_name}...")
        movies.create_table(table_name)
        print(f"\nCreated table {movies.table.name}.")

    my_movie = Question.ask_questions(
        [
            Question(
```

```
                "title", "Enter the title of a movie you want to add to the table: "
            ),
            Question("year", "What year was it released? ", Question.is_int),
            Question(
                "rating",
                "On a scale of 1 - 10, how do you rate it? ",
                Question.is_float,
                Question.in_range(1, 10),
            ),
            Question("plot", "Summarize the plot for me: "),
        ]
    )
    movies.add_movie(**my_movie)
    print(f"\nAdded '{my_movie['title']}' to '{movies.table.name}'.")
    print("-" * 88)

    movie_update = Question.ask_questions(
        [
            Question(
                "rating",
                f"\nLet's update your movie.\nYou rated it {my_movie['rating']},
what new "
                f"rating would you give it? ",
                Question.is_float,
                Question.in_range(1, 10),
            ),
            Question(
                "plot",
                f"You summarized the plot as '{my_movie['plot']}'.\nWhat would you
say now? ",
            ),
        ]
    )
    my_movie.update(movie_update)
    updated = movies.update_movie(**my_movie)
    print(f"\nUpdated '{my_movie['title']}' with new attributes:")
    pprint(updated)
    print("-" * 88)

    if not movies_exists:
        movie_data = get_sample_movie_data(movie_file_name)
        print(f"\nReading data from '{movie_file_name}' into your table.")
        movies.write_batch(movie_data)
        print(f"\nWrote {len(movie_data)} movies into {movies.table.name}.")
```

```
    print("-" * 88)

    title = "The Lord of the Rings: The Fellowship of the Ring"
    if Question.ask_question(
        f"Let's move on...do you want to get info about '{title}'? (y/n) ",
        Question.is_yesno,
    ):
        movie = movies.get_movie(title, 2001)
        print("\nHere's what I found:")
        pprint(movie)
    print("-" * 88)

    ask_for_year = True
    while ask_for_year:
        release_year = Question.ask_question(
            f"\nLet's get a list of movies released in a given year. Enter a year
between "
            f"1972 and 2018: ",
            Question.is_int,
            Question.in_range(1972, 2018),
        )
        releases = movies.query_movies(release_year)
        if releases:
            print(f"There were {len(releases)} movies released in {release_year}:")
            for release in releases:
                print(f"\t{release['title']}")
            ask_for_year = False
        else:
            print(f"I don't know about any movies released in {release_year}!")
            ask_for_year = Question.ask_question(
                "Try another year? (y/n) ", Question.is_yesno
            )
    print("-" * 88)

    years = Question.ask_questions(
        [
            Question(
                "first",
                f"\nNow let's scan for movies released in a range of years. Enter a
year: ",
                Question.is_int,
                Question.in_range(1972, 2018),
            ),
            Question(
```

```
                "second",
                "Now enter another year: ",
                Question.is_int,
                Question.in_range(1972, 2018),
            ),
        ]
    )
    releases = movies.scan_movies(years)
    if releases:
        count = Question.ask_question(
            f"\nFound {len(releases)} movies. How many do you want to see? ",
            Question.is_int,
            Question.in_range(1, len(releases)),
        )
        print(f"\nHere are your {count} movies:\n")
        pprint(releases[:count])
    else:
        print(
            f"I don't know about any movies released between {years['first']} "
            f"and {years['second']}."
        )
    print("-" * 88)

    if Question.ask_question(
        f"\nLet's remove your movie from the table. Do you want to remove "
        f"'{my_movie['title']}'? (y/n)",
        Question.is_yesno,
    ):
        movies.delete_movie(my_movie["title"], my_movie["year"])
        print(f"\nRemoved '{my_movie['title']}' from the table.")
    print("-" * 88)

    if Question.ask_question(f"\nDelete the table? (y/n) ", Question.is_yesno):
        movies.delete_table()
        print(f"Deleted {table_name}.")
    else:
        print(
            "Don't forget to delete the table when you're done or you might incur "
            "charges on your account."
        )

    print("\nThanks for watching!")
    print("-" * 88)
```

```
if __name__ == "__main__":
    try:
        run_scenario(
            "doc-example-table-movies", "moviedata.json", boto3.resource("dynamodb")
        )
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

Esse cenário usa a classe auxiliar a seguir para fazer perguntas em um prompt de comando.

```
class Question:
    """
    A helper class to ask questions at a command prompt and validate and convert
    the answers.
    """

    def __init__(self, key, question, *validators):
        """
        :param key: The key that is used for storing the answer in a dict, when
                    multiple questions are asked in a set.
        :param question: The question to ask.
        :param validators: The answer is passed through the list of validators until
                           one fails or they all pass. Validators may also convert
 the
                           answer to another form, such as from a str to an int.
        """
        self.key = key
        self.question = question
        self.validators = Question.non_empty, *validators

    @staticmethod
    def ask_questions(questions):
        """
        Asks a set of questions and stores the answers in a dict.

        :param questions: The list of questions to ask.
        :return: A dict of answers.
        """
        answers = {}
        for question in questions:
            answers[question.key] = Question.ask_question(
```

```
                question.question, *question.validators
            )
        return answers

    @staticmethod
    def ask_question(question, *validators):
        """
        Asks a single question and validates it against a list of validators.
        When an answer fails validation, the complaint is printed and the question
        is asked again.

        :param question: The question to ask.
        :param validators: The list of validators that the answer must pass.
        :return: The answer, converted to its final form by the validators.
        """
        answer = None
        while answer is None:
            answer = input(question)
            for validator in validators:
                answer, complaint = validator(answer)
                if answer is None:
                    print(complaint)
                    break
        return answer

    @staticmethod
    def non_empty(answer):
        """
        Validates that the answer is not empty.
        :return: The non-empty answer, or None.
        """
        return answer if answer != "" else None, "I need an answer. Please?"

    @staticmethod
    def is_yesno(answer):
        """
        Validates a yes/no answer.
        :return: True when the answer is 'y'; otherwise, False.
        """
        return answer.lower() == "y", ""

    @staticmethod
    def is_int(answer):
        """
```

```
        Validates that the answer can be converted to an int.
        :return: The int answer; otherwise, None.
        """
        try:
            int_answer = int(answer)
        except ValueError:
            int_answer = None
        return int_answer, f"{answer} must be a valid integer."

    @staticmethod
    def is_letter(answer):
        """
        Validates that the answer is a letter.
        :return The letter answer, converted to uppercase; otherwise, None.
        """
        return (
            answer.upper() if answer.isalpha() else None,
            f"{answer} must be a single letter.",
        )

    @staticmethod
    def is_float(answer):
        """
        Validate that the answer can be converted to a float.
        :return The float answer; otherwise, None.
        """
        try:
            float_answer = float(answer)
        except ValueError:
            float_answer = None
        return float_answer, f"{answer} must be a valid float."

    @staticmethod
    def in_range(lower, upper):
        """
        Validate that the answer is within a range. The answer must be of a type
that can
        be compared to the lower and upper bounds.
        :return: The answer, if it is within the range; otherwise, None.
        """

        def _validate(answer):
            return (
                answer if lower <= answer <= upper else None,
```

```
                f"{answer} must be between {lower} and {upper}.",
            )

        return _validate
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que possa executar lotes de instruções PartiQL.

```
from datetime import datetime
from decimal import Decimal
import logging
from pprint import pprint

import boto3
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statements, param_list):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
 to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.
```

```
        :param statements: The batch of PartiQL statements.
        :param param_list: The batch of PartiQL parameters that are associated with
                           each statement. This list must be in the same order as
the
                           statements.
        :return: The responses returned from running the statements, if any.
        """
        try:
            output = self.dyn_resource.meta.client.batch_execute_statement(
                Statements=[
                    {"Statement": statement, "Parameters": params}
                    for statement, params in zip(statements, param_list)
                ]
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute batch of PartiQL statements because the table
"
                    "does not exist."
                )
            else:
                logger.error(
                    "Couldn't execute batch of PartiQL statements. Here's why: %s:
%s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

Execute um cenário que crie uma tabela e execute consultas do PartiQL em lotes.

```
def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB PartiQL batch statement demo.")
```

```
    print("-" * 88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print("-" * 88)

    movie_data = [
        {
            "title": f"House PartiQL",
            "year": datetime.now().year - 5,
            "info": {
                "plot": "Wacky high jinks result from querying a mysterious
database.",
                "rating": Decimal("8.5"),
            },
        },
        {
            "title": f"House PartiQL 2",
            "year": datetime.now().year - 3,
            "info": {
                "plot": "Moderate high jinks result from querying another mysterious
database.",
                "rating": Decimal("6.5"),
            },
        },
        {
            "title": f"House PartiQL 3",
            "year": datetime.now().year - 1,
            "info": {
                "plot": "Tepid high jinks result from querying yet another
mysterious database.",
                "rating": Decimal("2.5"),
            },
        },
    ]

    print(f"Inserting a batch of movies into table '{table_name}.")
    statements = [
        f'INSERT INTO "{table_name}" ' f"VALUE {{'title': ?, 'year': ?, 'info': ?}}"
    ] * len(movie_data)
    params = [list(movie.values()) for movie in movie_data]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)
```

```
    print(f"Getting data for a batch of movies.")
    statements = [f'SELECT * FROM "{table_name}" WHERE title=? AND year=?'] * len(
        movie_data
    )
    params = [[movie["title"], movie["year"]] for movie in movie_data]
    output = wrapper.run_partiql(statements, params)
    for item in output["Responses"]:
        print(f"\n{item['Item']['title']}, {item['Item']['year']}")
        pprint(item["Item"])
    print("-" * 88)

    ratings = [Decimal("7.7"), Decimal("5.5"), Decimal("1.3")]
    print(f"Updating a batch of movies with new ratings.")
    statements = [
        f'UPDATE "{table_name}" SET info.rating=? ' f"WHERE title=? AND year=?"
    ] * len(movie_data)
    params = [
        [rating, movie["title"], movie["year"]]
        for rating, movie in zip(ratings, movie_data)
    ]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)

    print(f"Getting projected data from the table to verify our update.")
    output = wrapper.dyn_resource.meta.client.execute_statement(
        Statement=f'SELECT title, info.rating FROM "{table_name}"'
    )
    pprint(output["Items"])
    print("-" * 88)

    print(f"Deleting a batch of movies from the table.")
    statements = [f'DELETE FROM "{table_name}" WHERE title=? AND year=?'] * len(
        movie_data
    )
    params = [[movie["title"], movie["year"]] for movie in movie_data]
    wrapper.run_partiql(statements, params)
    print("Success!")
    print("-" * 88)

    print(f"Deleting table '{table_name}'...")
    scaffold.delete_table()
    print("-" * 88)
```

```
    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        dyn_res = boto3.resource("dynamodb")
        scaffold = Scaffold(dyn_res)
        movies = PartiQLBatchWrapper(dyn_res)
        run_scenario(scaffold, movies, "doc-example-table-partiql-movies")
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

- Para obter detalhes da API, consulte a BatchExecuteStatementReferência da API AWSSDK for Python (Boto3).

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que possa executar instruções PartiQL.

```
from datetime import datetime
from decimal import Decimal
import logging
```

```
from pprint import pprint

import boto3
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """

    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource


    def run_partiql(self, statement, params):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
 to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statement: The PartiQL statement.
        :param params: The list of PartiQL parameters. These are applied to the
                       statement in the order they are listed.
        :return: The items returned from the statement, if any.
        """
        try:
            output = self.dyn_resource.meta.client.execute_statement(
                Statement=statement, Parameters=params
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.error(
                    "Couldn't execute PartiQL '%s' because the table does not
 exist.",
```

```
                    statement,
                )
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s",
                    statement,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
            raise
        else:
            return output
```

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon DynamoDB PartiQL single statement demo.")
    print("-" * 88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print("-" * 88)

    title = "24 Hour PartiQL People"
    year = datetime.now().year
    plot = "A group of data developers discover a new query language they can't stop
 using."
    rating = Decimal("9.9")

    print(f"Inserting movie '{title}' released in {year}.")
    wrapper.run_partiql(
        f"INSERT INTO \"{table_name}\" VALUE {{'title': ?, 'year': ?, 'info': ?}}",
        [title, year, {"plot": plot, "rating": rating}],
    )
    print("Success!")
    print("-" * 88)
```

```
    print(f"Getting data for movie '{title}' released in {year}.")
    output = wrapper.run_partiql(
        f'SELECT * FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    for item in output["Items"]:
        print(f"\n{item['title']}, {item['year']}")
        pprint(output["Items"])
    print("-" * 88)

    rating = Decimal("2.4")
    print(f"Updating movie '{title}' with a rating of {float(rating)}.")
    wrapper.run_partiql(
        f'UPDATE "{table_name}" SET info.rating=? WHERE title=? AND year=?',
        [rating, title, year],
    )
    print("Success!")
    print("-" * 88)

    print(f"Getting data again to verify our update.")
    output = wrapper.run_partiql(
        f'SELECT * FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    for item in output["Items"]:
        print(f"\n{item['title']}, {item['year']}")
        pprint(output["Items"])
    print("-" * 88)

    print(f"Deleting movie '{title}' released in {year}.")
    wrapper.run_partiql(
        f'DELETE FROM "{table_name}" WHERE title=? AND year=?', [title, year]
    )
    print("Success!")
    print("-" * 88)

    print(f"Deleting table '{table_name}'...")
    scaffold.delete_table()
    print("-" * 88)

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
```

```
        dyn_res = boto3.resource("dynamodb")
        scaffold = Scaffold(dyn_res)
        movies = PartiQLWrapper(dyn_res)
        run_scenario(scaffold, movies, "doc-example-table-partiql-movies")
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")
```

- Para obter detalhes da API, consulte a ExecuteStatementReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon EC2 usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon EC2

Os exemplos de código a seguir mostram como começar a usar o Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3
```

```
def hello_ec2(ec2_resource):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Elastic Compute Cloud
    (Amazon EC2) resource and list the security groups in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param ec2_resource: A Boto3 EC2 ServiceResource object. This object is a high-
level
                         resource that wraps the low-level EC2 service API.
    """
    print("Hello, Amazon EC2! Let's list up to 10 of your security groups:")
    for sg in ec2_resource.security_groups.limit(10):
        print(f"\t{sg.id}: {sg.group_name}")


if __name__ == "__main__":
    hello_ec2(boto3.resource("ec2"))
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico ao Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def allocate(self):
        """
        Allocates an Elastic IP address that can be associated with an Amazon EC2
        instance. By using an Elastic IP address, you can keep the public IP address
        constant even when you restart the associated instance.

        :return: The newly created Elastic IP object. By default, the address is not
                 associated with any instance.
        """
        try:
            response = self.ec2_resource.meta.client.allocate_address(Domain="vpc")
            self.elastic_ip = self.ec2_resource.VpcAddress(response["AllocationId"])
```

```
        except ClientError as err:
            logger.error(
                "Couldn't allocate Elastic IP. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.elastic_ip
```

- Para obter detalhes da API, consulte a AllocateAddressReferência da API AWSSDK for Python (Boto3).

Para associar um endereço IP elástico a uma instância

Os exemplos de código a seguir mostram como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
```

```
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def associate(self, instance):
        """
        Associates an Elastic IP address with an instance. When this association is
        created, the Elastic IP's public IP address is immediately used as the
public
        IP address of the associated instance.

        :param instance: A Boto3 Instance object. This is a high-level object that
wraps
                         Amazon EC2 instance actions.
        :return: A response that contains the ID of the association.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to associate.")
            return

        try:
            response = self.elastic_ip.associate(InstanceId=instance.id)
        except ClientError as err:
            logger.error(
                "Couldn't associate Elastic IP %s with instance %s. Here's why: %s:
%s",
                self.elastic_ip.allocation_id,
                instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        return response
```

- Para obter detalhes da API, consulte a AssociateAddressReferência da API AWSSDK for Python (Boto3).

Criar um modelo de inicialização

O exemplo de código a seguir mostra como criar um modelo de execução de sub-rede do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo cria um modelo de execução que inclui um perfil de instância que concede permissões específicas à instância e um script Bash de dados do usuário que é executado na instância após sua inicialização.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
```

```
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a permissions
policy
                                     to create and attach to the instance profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
```

```
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template {self.launch_template_name}:
{err}."
                )
        return template
```

- Para obter detalhes da API, consulte a CreateLaunchTemplateReferência da API AWSSDK for Python (Boto3).

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, group_name, group_description):
        """
        Creates a security group in the default virtual private cloud (VPC) of the
        current account.
```

```
        :param group_name: The name of the security group to create.
        :param group_description: The description of the security group to create.
        :return: A Boto3 SecurityGroup object that represents the newly created
 security group.
        """
        try:
            self.security_group = self.ec2_resource.create_security_group(
                GroupName=group_name, Description=group_description
            )
        except ClientError as err:
            logger.error(
                "Couldn't create security group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.security_group
```

- Para obter detalhes da API, consulte a CreateSecurityGroupReferência da API AWSSDK for Python (Boto3).

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
```

```
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def create(self, key_name):
        """
        Creates a key pair that can be used to securely connect to an EC2 instance.
        The returned key pair contains private key information that cannot be
retrieved
        again. The private key data is stored as a .pem file.

        :param key_name: The name of the key pair to create.
        :return: A Boto3 KeyPair object that represents the newly created key pair.
        """
        try:
            self.key_pair = self.ec2_resource.create_key_pair(KeyName=key_name)
            self.key_file_path = os.path.join(
                self.key_file_dir.name, f"{self.key_pair.name}.pem"
            )
            with open(self.key_file_path, "w") as key_file:
                key_file.write(self.key_pair.key_material)
        except ClientError as err:
            logger.error(
                "Couldn't create key %s. Here's why: %s: %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return self.key_pair
```

- Para obter detalhes da API, consulte a CreateKeyPairReferência da API AWSSDK for Python (Boto3).

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, image, instance_type, key_pair, security_groups=None):
        """
```

```
        Creates a new EC2 instance. The instance starts immediately after
        it is created.

        The instance is created in the default VPC of the current account.

        :param image: A Boto3 Image object that represents an Amazon Machine Image
(AMI)
                      that defines attributes of the instance that is created. The
AMI
                      defines things like the kind of operating system and the type
of
                      storage used by the instance.
        :param instance_type: The type of instance to create, such as 't2.micro'.
                              The instance type defines things like the number of
CPUs and
                              the amount of memory.
        :param key_pair: A Boto3 KeyPair or KeyPairInfo object that represents the
key
                         pair that is used to secure connections to the instance.
        :param security_groups: A list of Boto3 SecurityGroup objects that
represents the
                                security groups that are used to grant access to the
                                instance. When no security groups are specified, the
                                default security group of the VPC is used.
        :return: A Boto3 Instance object that represents the newly created instance.
        """
        try:
            instance_params = {
                "ImageId": image.id,
                "InstanceType": instance_type,
                "KeyName": key_pair.name,
            }
            if security_groups is not None:
                instance_params["SecurityGroupIds"] = [sg.id for sg in
security_groups]
            self.instance = self.ec2_resource.create_instances(
                **instance_params, MinCount=1, MaxCount=1
            )[0]
            self.instance.wait_until_running()
        except ClientError as err:
            logging.error(
                "Couldn't create instance with image %s, instance type %s, and key
%s. "
                "Here's why: %s: %s",
```

```
                image.id,
                instance_type,
                key_pair.name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.instance
```

- Para obter detalhes da API, consulte a RunInstancesReferência da API AWSSDK for Python (Boto3).

Excluir um modelo de execução

O exemplo de código a seguir mostra como excluir um modelo de execução de sub-rede do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
```

```
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
```

```
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template {self.launch_template_name}:
 {err}."
                )
```

- Para obter detalhes da API, consulte a DeleteLaunchTemplateReferência da API AWSSDK for Python (Boto3).

Exclua um grupo de segurança

Os exemplos de código a seguir mostram como excluir um grupo de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
```

```
                                that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def delete(self):
        """
        Deletes the security group.
        """
        if self.security_group is None:
            logger.info("No security group to delete.")
            return

        group_id = self.security_group.id
        try:
            self.security_group.delete()
        except ClientError as err:
            logger.error(
                "Couldn't delete security group %s. Here's why: %s: %s",
                group_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupReferência da API AWSSDK for Python (Boto3).

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def delete(self):
        """
        Deletes a key pair.
        """
        if self.key_pair is None:
            logger.info("No key pair to delete.")
            return

        key_name = self.key_pair.name
        try:
```

```
            self.key_pair.delete()
            self.key_pair = None
        except ClientError as err:
            logger.error(
                "Couldn't delete key %s. Here's why: %s : %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteKeyPairReferência da API AWSSDK for Python (Boto3).

Descrever as zonas de disponibilidade

Os exemplos de código a seguir mostram como descrever as zonas de disponibilidade do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
```

```
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
```

```
        else:
            return zones
```

- Para obter detalhes da API, consulte a DescribeAvailabilityZonesReferência da API AWSSDK for Python (Boto3).

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def display(self, indent=1):
```

```
        """
        Displays information about an instance.

        :param indent: The visual indent to apply to the output.
        """
        if self.instance is None:
            logger.info("No instance to display.")
            return

        try:
            self.instance.load()
            ind = "\t" * indent
            print(f"{ind}ID: {self.instance.id}")
            print(f"{ind}Image ID: {self.instance.image_id}")
            print(f"{ind}Instance type: {self.instance.instance_type}")
            print(f"{ind}Key name: {self.instance.key_name}")
            print(f"{ind}VPC ID: {self.instance.vpc_id}")
            print(f"{ind}Public IP: {self.instance.public_ip_address}")
            print(f"{ind}State: {self.instance.state['Name']}")
        except ClientError as err:
            logger.error(
                "Couldn't display your instance. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DescribeInstancesReferência da API AWSSDK for Python (Boto3).

Desassociar um endereço IP elástico de uma instância

Os exemplos de código a seguir mostram como desassociar um endereço IP elástico de uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def disassociate(self):
        """
        Removes an association between an Elastic IP address and an instance. When
 the
        association is removed, the instance is assigned a new public IP address.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to disassociate.")
            return

        try:
            self.elastic_ip.association.delete()
```

```
        except ClientError as err:
            logger.error(
                "Couldn't disassociate Elastic IP %s from its instance. Here's why:
%s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DisassociateAddressReferência da API AWSSDK for Python (Boto3).

Obter dados sobre imagens de máquina da Amazon

Os exemplos de código a seguir mostram como obter dados sobre imagens de máquina da Amazon (AMIs).

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance
```

```
    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def get_images(self, image_ids):
        """
        Gets information about Amazon Machine Images (AMIs) from a list of AMI IDs.

        :param image_ids: The list of AMIs to look up.
        :return: A list of Boto3 Image objects that represent the requested AMIs.
        """
        try:
            images = list(self.ec2_resource.images.filter(ImageIds=image_ids))
        except ClientError as err:
            logger.error(
                "Couldn't get images. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return images
```

- Para obter detalhes da API, consulte a DescribeImagesReferência da API AWSSDK for Python (Boto3).

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def describe(self):
        """
        Displays information about the security group.
        """
        if self.security_group is None:
            logger.info("No security group to describe.")
            return

        try:
            print(f"Security group: {self.security_group.group_name}")
            print(f"\tID: {self.security_group.id}")
            print(f"\tVPC: {self.security_group.vpc_id}")
```

```
            if self.security_group.ip_permissions:
                print(f"Inbound permissions:")
                pp(self.security_group.ip_permissions)
        except ClientError as err:
            logger.error(
                "Couldn't get data for security group %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsReferência da API AWSSDK for Python (Boto3).

Obter dados sobre tipos de instâncias

O exemplo de código a seguir mostra como obter dados sobre tipos de instâncias do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance
```

```
    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def get_instance_types(self, architecture):
        """
        Gets instance types that support the specified architecture and are
designated
        as either 'micro' or 'small'. When an instance is created, the instance type
        you specify must support the architecture of the AMI you use.

        :param architecture: The kind of architecture the instance types must
support,
                             such as 'x86_64'.
        :return: A list of instance types that support the specified architecture
                 and are either 'micro' or 'small'.
        """
        try:
            inst_types = []
            it_paginator = self.ec2_resource.meta.client.get_paginator(
                "describe_instance_types"
            )
            for page in it_paginator.paginate(
                Filters=[
                    {
                        "Name": "processor-info.supported-architecture",
                        "Values": [architecture],
                    },
                    {"Name": "instance-type", "Values": ["*.micro", "*.small"]},
                ]
            ):
                inst_types += page["InstanceTypes"]
        except ClientError as err:
            logger.error(
                "Couldn't get instance types. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_types
```

- Para obter detalhes da API, consulte a DescribeInstanceTypesReferência da API AWSSDK for Python (Boto3).

Obtenha dados sobre o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como obter dados sobre o perfil de instância associado a uma instância Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
```

```
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
            response = self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]
```

- Para obter detalhes da API, consulte a DescribeIamInstanceProfileAssociationsReferência da API AWSSDK for Python (Boto3).

Obtenha a VPC padrão

O exemplo de código a seguir mostra como obter o VPC padrão da conta atual.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
```

```
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]
```

- Para obter detalhes da API, consulte a DescribeVpcsReferência da API AWSSDK for Python (Boto3).

Obtenha sub-redes padrão para uma VPC

O exemplo de código a seguir mostra como obter as sub-redes padrão para uma VPC.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
 is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
```

```
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
 Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

- Para obter detalhes da API, consulte a DescribeSubnetsReferência da API AWSSDK for Python (Boto3).

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is stored.
                             This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def list(self, limit):
        """
        Displays a list of key pairs for the current account.

        :param limit: The maximum number of key pairs to list.
        """
        try:
            for kp in self.ec2_resource.key_pairs.limit(limit):
                print(f"Found {kp.key_type} key {kp.name} with fingerprint:")
                print(f"\t{kp.key_fingerprint}")
```

```
        except ClientError as err:
            logger.error(
                "Couldn't list key pairs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DescribeKeyPairsReferência da API AWSSDK for Python (Boto3).

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
```

```
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the profile
is
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
```

```
        :param profile_association_id: The ID of the existing profile association
for the
                                        instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )
```

- Para obter detalhes da API, consulte a RebootInstancesReferência da API AWSSDK for Python (Boto3).

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
 that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def release(self):
        """
        Releases an Elastic IP address. After the Elastic IP address is released,
        it can no longer be used.
        """
```

```
        if self.elastic_ip is None:
            logger.info("No Elastic IP to release.")
            return

        try:
            self.elastic_ip.release()
        except ClientError as err:
            logger.error(
                "Couldn't release Elastic IP address %s. Here's why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ReleaseAddressReferência da API AWSSDK for Python (Boto3).

Subtitua o perfil de instância associado a uma instância

O exemplo de código a seguir mostra como substituir o perfil de instância associado a uma instância Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo substitui o perfil de instância de uma instância em execução, reinicia a instância e envia um comando para a instância após ela iniciar.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """
```

```
    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
```

```
        Replaces the profile associated with a running instance. After the profile
is
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
```

```
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )
```

- Para obter detalhes da API, consulte a ReplaceIamInstanceProfileAssociationReferência da API AWSSDK for Python (Boto3).

Definir regras de entrada para um grupo de segurança

O exemplo de código a seguir mostra como definir regras de entrada para um grupo de segurança do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
```

```
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def authorize_ingress(self, ssh_ingress_ip):
        """
        Adds a rule to the security group to allow access to SSH.

        :param ssh_ingress_ip: The IP address that is granted inbound access to
connect
                               to port 22 over TCP, used for SSH.
        :return: The response to the authorization request. The 'Return' field of
the
                 response indicates whether the request succeeded or failed.
        """
        if self.security_group is None:
            logger.info("No security group to update.")
            return

        try:
            ip_permissions = [
                {
                    # SSH ingress open to only the specified IP address.
                    "IpProtocol": "tcp",
                    "FromPort": 22,
                    "ToPort": 22,
                    "IpRanges": [{"CidrIp": f"{ssh_ingress_ip}/32"}],
                }
            ]
            response = self.security_group.authorize_ingress(
                IpPermissions=ip_permissions
            )
        except ClientError as err:
            logger.error(
                "Couldn't authorize inbound rules for %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return response
```

- Para obter detalhes da API, consulte a AuthorizeSecurityGroupIngressReferência da API AWSSDK for Python (Boto3).

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def start(self):
        """
```

```
        Starts an instance and waits for it to be in a running state.

        :return: The response to the start request.
        """
        if self.instance is None:
            logger.info("No instance to start.")
            return

        try:
            response = self.instance.start()
            self.instance.wait_until_running()
        except ClientError as err:
            logger.error(
                "Couldn't start instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StartInstancesReferência da API AWSSDK for Python (Boto3).

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""
```

```
    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def stop(self):
        """
        Stops an instance and waits for it to be in a stopped state.

        :return: The response to the stop request.
        """
        if self.instance is None:
            logger.info("No instance to stop.")
            return

        try:
            response = self.instance.stop()
            self.instance.wait_until_stopped()
        except ClientError as err:
            logger.error(
                "Couldn't stop instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a StopInstancesReferência da API AWSSDK for Python (Boto3).

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                         wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def terminate(self):
        """
        Terminates an instance and waits for it to be in a terminated state.
        """
        if self.instance is None:
            logger.info("No instance to terminate.")
            return
```

```
        instance_id = self.instance.id
        try:
            self.instance.terminate()
            self.instance.wait_until_terminated()
            self.instance = None
        except ClientError as err:
            logging.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a TerminateInstancesReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer, param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
 several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways to
 make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide book,
 movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each contain
 a Python web server."
```

```
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
 Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
 Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
 '{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when an
 instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
 script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
 and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In production,
 the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged credentials.
\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
 assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
 Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
```

```
            f"Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or continue
with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load balancer
provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port is
open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
```

```
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for your
 default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging from
 your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
```

```
                "Couldn't get a successful response from the load balancer endpoint.
Troubleshoot by\n"
                "manually verifying that your VPC and security group are configured
correctly and that\n"
                "you can successfully make a GET request to the load balancer
endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
```

```
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health check
to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts of
the system\n"
            "to create situations where the web service fails, and shows how using a
resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations by
querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
```

```
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't check
for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with a
somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns a
static response.\n"
            f"The service still reports as healthy because health checks are still
shallow.\n"
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in the
target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a profile
that contains\n"
```

```
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto Scaling
instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling group
when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect when
one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
```

```
            "\nBecause the instances in this demo are controlled by an auto scaler,
 the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
 instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
 starting, sending a GET\n"
            "request to the web service continues to get a successful recommendation
 response because\n"
            "the load balancer routes requests to the healthy instances. After the
 replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
 rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
 several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
 running and healthy.\n"
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean all
 instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient service.
\n"
            "To keep things tidy and to avoid unwanted charges on your account, we
 can clean up all AWS resources\n"
            "that were created for this demo."
```

```
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ", q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM policies
 and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
```

```
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer, param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
```

```
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        """
        as_client = boto3.client("autoscaling")
```

```
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is assumed
by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as AmazonSSMManagedInstanceCore
to grant
                                     use of Systems Manager to send commands to the
instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
```

```
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
 role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
 profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to role
\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
```

```
            response = self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the profile
is
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
```

```
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
```

```
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.
```

```
        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.", self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a permissions
policy
                                     to create and attach to the instance profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
```

```
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template {self.launch_template_name}:
{err}."
                )
        return template
```

```
    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template {self.launch_template_name}:
{err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones
```

```
    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
```

```
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group {self.group_name}:
{err}"
            )
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.
```

```
        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group %s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
```

```
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] == "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
```

```
                log.info("No groups found named %s, nothing to do.",
self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
{err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress from
this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
```

```
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to either
this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or to a
prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
```

```
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port} from
{ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
```

```
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by this
 class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
```

```
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group specifies
how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened times
and
        lower thresholds. In production, you might want to decrease the sensitivity
of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
```

```
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
```

```
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
```

```
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
```

```
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint, retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets: {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books, movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended, such
 as
        Book or Movie, and a range key named 'ItemId' that, combined with the
 MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
```

```
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5, "WriteCapacityUnits":
5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name, data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}: {err}"
            )
```

```
    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters to
 drive
    the demonstration of resilient architecture, such as failure of a dependency or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
```

```
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile

- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Começar a usar instâncias

O código de exemplo a seguir mostra como:

- Criar um par de chaves e um grupo de segurança.
- Selecionar uma imagem de máquina da Amazon (AMI) e um tipo de instância compatível e, em seguida, criar uma instância.
- Interromper e reiniciar a instância.
- Associe um endereço IP elástico à sua instância.

- Conecte-se à sua instância via SSH e, em seguida, limpe os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class Ec2InstanceScenario:
    """Runs an interactive scenario that shows how to get started using EC2
 instances."""

    def __init__(self, inst_wrapper, key_wrapper, sg_wrapper, eip_wrapper,
 ssm_client):
        """
        :param inst_wrapper: An object that wraps instance actions.
        :param key_wrapper: An object that wraps key pair actions.
        :param sg_wrapper: An object that wraps security group actions.
        :param eip_wrapper: An object that wraps Elastic IP actions.
        :param ssm_client: A Boto3 AWS Systems Manager client.
        """
        self.inst_wrapper = inst_wrapper
        self.key_wrapper = key_wrapper
        self.sg_wrapper = sg_wrapper
        self.eip_wrapper = eip_wrapper
        self.ssm_client = ssm_client

    @demo_func
    def create_and_list_key_pairs(self):
        """
        1. Creates an RSA key pair and saves its private key data as a .pem file in
 secure
           temporary storage. The private key data is deleted after the example
 completes.
        2. Lists the first five key pairs for the current account.
        """
        print(
```

```
            "Let's create an RSA key pair that you can be use to securely connect to
"
            "your EC2 instance."
        )
        key_name = q.ask("Enter a unique name for your key: ", q.non_empty)
        self.key_wrapper.create(key_name)
        print(
            f"Created a key pair {self.key_wrapper.key_pair.key_name} and saved the
"
            f"private key to {self.key_wrapper.key_file_path}.\n"
        )
        if q.ask("Do you want to list some of your key pairs? (y/n) ", q.is_yesno):
            self.key_wrapper.list(5)

    @demo_func
    def create_security_group(self):
        """
        1. Creates a security group for the default VPC.
        2. Adds an inbound rule to allow SSH. The SSH rule allows only
           inbound traffic from the current computer’s public IPv4 address.
        3. Displays information about the security group.

        This function uses 'http://checkip.amazonaws.com' to get the current public
IP
        address of the computer that is running the example. This method works in
most
        cases. However, depending on how your computer connects to the internet, you
        might have to manually add your public IP address to the security group by
using
        the AWS Management Console.
        """
        print("Let's create a security group to manage access to your instance.")
        sg_name = q.ask("Enter a unique name for your security group: ",
q.non_empty)
        security_group = self.sg_wrapper.create(
            sg_name, "Security group for example: get started with instances."
        )
        print(
            f"Created security group {security_group.group_name} in your default "
            f"VPC {security_group.vpc_id}.\n"
        )

        ip_response = urllib.request.urlopen("http://checkip.amazonaws.com")
        current_ip_address = ip_response.read().decode("utf-8").strip()
```

```
        print("Let's add a rule to allow SSH only from your current IP address.")
        print(f"Your public IP address is {current_ip_address}.")
        q.ask("Press Enter to add this rule to your security group.")
        response = self.sg_wrapper.authorize_ingress(current_ip_address)
        if response["Return"]:
            print("Security group rules updated.")
        else:
            print("Couldn't update security group rules.")
        self.sg_wrapper.describe()

    @demo_func
    def create_instance(self):
        """
        1. Gets a list of Amazon Linux 2 AMIs from AWS Systems Manager. Specifying
 the
           '/aws/service/ami-amazon-linux-latest' path returns only the latest AMIs.
        2. Gets and displays information about the available AMIs and lets you
 select one.
        3. Gets a list of instance types that are compatible with the selected AMI
 and
           lets you select one.
        4. Creates an instance with the previously created key pair and security
 group,
           and the selected AMI and instance type.
        5. Waits for the instance to be running and then displays its information.
        """
        ami_paginator = self.ssm_client.get_paginator("get_parameters_by_path")
        ami_options = []
        for page in ami_paginator.paginate(Path="/aws/service/ami-amazon-linux-
latest"):
            ami_options += page["Parameters"]
        amzn2_images = self.inst_wrapper.get_images(
            [opt["Value"] for opt in ami_options if "amzn2" in opt["Name"]]
        )
        print(
            "Let's create an instance from an Amazon Linux 2 AMI. Here are some
 options:"
        )
        image_choice = q.choose(
            "Which one do you want to use? ", [opt.description for opt in
 amzn2_images]
        )
        print("Great choice!\n")
```

```
        print(
            f"Here are some instance types that support the "
            f"{amzn2_images[image_choice].architecture} architecture of the image:"
        )
        inst_types = self.inst_wrapper.get_instance_types(
            amzn2_images[image_choice].architecture
        )
        inst_type_choice = q.choose(
            "Which one do you want to use? ", [it["InstanceType"] for it in
inst_types]
        )
        print("Another great choice.\n")

        print("Creating your instance and waiting for it to start...")
        self.inst_wrapper.create(
            amzn2_images[image_choice],
            inst_types[inst_type_choice]["InstanceType"],
            self.key_wrapper.key_pair,
            [self.sg_wrapper.security_group],
        )
        print(f"Your instance is ready:\n")
        self.inst_wrapper.display()

        print("You can use SSH to connect to your instance.")
        print(
            "If the connection attempt times out, you might have to manually update
"
            "the SSH ingress rule for your IP address in the AWS Management
Console."
        )
        self._display_ssh_info()

    def _display_ssh_info(self):
        """
        Displays an SSH connection string that can be used to connect to a running
        instance.
        """
        print("To connect, open another command prompt and run the following
command:")
        if self.eip_wrapper.elastic_ip is None:
            print(
                f"\tssh -i {self.key_wrapper.key_file_path} "
                f"ec2-user@{self.inst_wrapper.instance.public_ip_address}"
            )
```

```
        else:
            print(
                f"\tssh -i {self.key_wrapper.key_file_path} "
                f"ec2-user@{self.eip_wrapper.elastic_ip.public_ip}"
            )
        q.ask("Press Enter when you're ready to continue the demo.")

    @demo_func
    def associate_elastic_ip(self):
        """
        1. Allocates an Elastic IP address and associates it with the instance.
        2. Displays an SSH connection string that uses the Elastic IP address.
        """
        print(
            "You can allocate an Elastic IP address and associate it with your
instance\n"
            "to keep a consistent IP address even when your instance restarts."
        )
        elastic_ip = self.eip_wrapper.allocate()
        print(f"Allocated static Elastic IP address: {elastic_ip.public_ip}.")
        self.eip_wrapper.associate(self.inst_wrapper.instance)
        print(f"Associated your Elastic IP with your instance.")
        print(
            "You can now use SSH to connect to your instance by using the Elastic
IP."
        )
        self._display_ssh_info()

    @demo_func
    def stop_and_start_instance(self):
        """
        1. Stops the instance and waits for it to stop.
        2. Starts the instance and waits for it to start.
        3. Displays information about the instance.
        4. Displays an SSH connection string. When an Elastic IP address is
associated
           with the instance, the IP address stays consistent when the instance
stops
           and starts.
        """
        print("Let's stop and start your instance to see what changes.")
        print("Stopping your instance and waiting until it's stopped...")
        self.inst_wrapper.stop()
        print("Your instance is stopped. Restarting...")
```

```
        self.inst_wrapper.start()
        print("Your instance is running.")
        self.inst_wrapper.display()
        if self.eip_wrapper.elastic_ip is None:
            print(
                "Every time your instance is restarted, its public IP address
changes."
            )
        else:
            print(
                "Because you have associated an Elastic IP with your instance, you
can \n"
                "connect by using a consistent IP address after the instance
restarts."
            )
        self._display_ssh_info()

    @demo_func
    def cleanup(self):
        """
        1. Disassociate and delete the previously created Elastic IP.
        2. Terminate the previously created instance.
        3. Delete the previously created security group.
        4. Delete the previously created key pair.
        """
        print("Let's clean everything up. This example created these resources:")
        print(f"\tElastic IP: {self.eip_wrapper.elastic_ip.allocation_id}")
        print(f"\tInstance: {self.inst_wrapper.instance.id}")
        print(f"\tSecurity group: {self.sg_wrapper.security_group.id}")
        print(f"\tKey pair: {self.key_wrapper.key_pair.name}")
        if q.ask("Ready to delete these resources? (y/n) ", q.is_yesno):
            self.eip_wrapper.disassociate()
            print("Disassociated the Elastic IP from the instance.")
            self.eip_wrapper.release()
            print("Released the Elastic IP.")
            print("Terminating the instance and waiting for it to terminate...")
            self.inst_wrapper.terminate()
            print("Instance terminated.")
            self.sg_wrapper.delete()
            print("Deleted security group.")
            self.key_wrapper.delete()
            print("Deleted key pair.")

    def run_scenario(self):
```

```
        logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

        print("-" * 88)
        print(
            "Welcome to the Amazon Elastic Compute Cloud (Amazon EC2) get started
 with instances demo."
        )
        print("-" * 88)

        self.create_and_list_key_pairs()
        self.create_security_group()
        self.create_instance()
        self.stop_and_start_instance()
        self.associate_elastic_ip()
        self.stop_and_start_instance()
        self.cleanup()

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = Ec2InstanceScenario(
            InstanceWrapper.from_resource(),
            KeyPairWrapper.from_resource(),
            SecurityGroupWrapper.from_resource(),
            ElasticIpWrapper.from_resource(),
            boto3.client("ssm"),
        )
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina uma classe que envolva as ações de pares de chaves.

```
class KeyPairWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) key pair actions."""

    def __init__(self, ec2_resource, key_file_dir, key_pair=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
```

```
                                is used to create additional high-level objects
                                that wrap low-level Amazon EC2 service actions.
        :param key_file_dir: The folder where the private key information is stored.
                                This should be a secure folder.
        :param key_pair: A Boto3 KeyPair object. This is a high-level object that
                         wraps key pair actions.
        """
        self.ec2_resource = ec2_resource
        self.key_pair = key_pair
        self.key_file_path = None
        self.key_file_dir = key_file_dir

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource, tempfile.TemporaryDirectory())


    def create(self, key_name):
        """
        Creates a key pair that can be used to securely connect to an EC2 instance.
        The returned key pair contains private key information that cannot be
retrieved
        again. The private key data is stored as a .pem file.

        :param key_name: The name of the key pair to create.
        :return: A Boto3 KeyPair object that represents the newly created key pair.
        """
        try:
            self.key_pair = self.ec2_resource.create_key_pair(KeyName=key_name)
            self.key_file_path = os.path.join(
                self.key_file_dir.name, f"{self.key_pair.name}.pem"
            )
            with open(self.key_file_path, "w") as key_file:
                key_file.write(self.key_pair.key_material)
        except ClientError as err:
            logger.error(
                "Couldn't create key %s. Here's why: %s: %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
```

```
        return self.key_pair


    def list(self, limit):
        """
        Displays a list of key pairs for the current account.

        :param limit: The maximum number of key pairs to list.
        """
        try:
            for kp in self.ec2_resource.key_pairs.limit(limit):
                print(f"Found {kp.key_type} key {kp.name} with fingerprint:")
                print(f"\t{kp.key_fingerprint}")
        except ClientError as err:
            logger.error(
                "Couldn't list key pairs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self):
        """
        Deletes a key pair.
        """
        if self.key_pair is None:
            logger.info("No key pair to delete.")
            return

        key_name = self.key_pair.name
        try:
            self.key_pair.delete()
            self.key_pair = None
        except ClientError as err:
            logger.error(
                "Couldn't delete key %s. Here's why: %s : %s",
                key_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que envolva as ações de grupos de segurança.

```
class SecurityGroupWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) security group
 actions."""

    def __init__(self, ec2_resource, security_group=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param security_group: A Boto3 SecurityGroup object. This is a high-level
 object
                               that wraps security group actions.
        """
        self.ec2_resource = ec2_resource
        self.security_group = security_group

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, group_name, group_description):
        """
        Creates a security group in the default virtual private cloud (VPC) of the
        current account.

        :param group_name: The name of the security group to create.
        :param group_description: The description of the security group to create.
        :return: A Boto3 SecurityGroup object that represents the newly created
 security group.
        """
        try:
            self.security_group = self.ec2_resource.create_security_group(
                GroupName=group_name, Description=group_description
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't create security group %s. Here's why: %s: %s",
                group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.security_group


    def authorize_ingress(self, ssh_ingress_ip):
        """
        Adds a rule to the security group to allow access to SSH.

        :param ssh_ingress_ip: The IP address that is granted inbound access to
connect
                               to port 22 over TCP, used for SSH.
        :return: The response to the authorization request. The 'Return' field of
the
                 response indicates whether the request succeeded or failed.
        """
        if self.security_group is None:
            logger.info("No security group to update.")
            return

        try:
            ip_permissions = [
                {
                    # SSH ingress open to only the specified IP address.
                    "IpProtocol": "tcp",
                    "FromPort": 22,
                    "ToPort": 22,
                    "IpRanges": [{"CidrIp": f"{ssh_ingress_ip}/32"}],
                }
            ]
            response = self.security_group.authorize_ingress(
                IpPermissions=ip_permissions
            )
        except ClientError as err:
            logger.error(
                "Couldn't authorize inbound rules for %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return response


    def describe(self):
        """
        Displays information about the security group.
        """
        if self.security_group is None:
            logger.info("No security group to describe.")
            return

        try:
            print(f"Security group: {self.security_group.group_name}")
            print(f"\tID: {self.security_group.id}")
            print(f"\tVPC: {self.security_group.vpc_id}")
            if self.security_group.ip_permissions:
                print(f"Inbound permissions:")
                pp(self.security_group.ip_permissions)
        except ClientError as err:
            logger.error(
                "Couldn't get data for security group %s. Here's why: %s: %s",
                self.security_group.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self):
        """
        Deletes the security group.
        """
        if self.security_group is None:
            logger.info("No security group to delete.")
            return

        group_id = self.security_group.id
        try:
            self.security_group.delete()
        except ClientError as err:
            logger.error(
```

```
                "Couldn't delete security group %s. Here's why: %s: %s",
                group_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que envolva as ações de instâncias.

```
class InstanceWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) instance actions."""

    def __init__(self, ec2_resource, instance=None):
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param instance: A Boto3 Instance object. This is a high-level object that
                            wraps instance actions.
        """
        self.ec2_resource = ec2_resource
        self.instance = instance

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def create(self, image, instance_type, key_pair, security_groups=None):
        """
        Creates a new EC2 instance. The instance starts immediately after
        it is created.

        The instance is created in the default VPC of the current account.

        :param image: A Boto3 Image object that represents an Amazon Machine Image
 (AMI)
```

```
                     that defines attributes of the instance that is created. The
AMI
                     defines things like the kind of operating system and the type
of
                     storage used by the instance.
       :param instance_type: The type of instance to create, such as 't2.micro'.
                             The instance type defines things like the number of
CPUs and
                             the amount of memory.
       :param key_pair: A Boto3 KeyPair or KeyPairInfo object that represents the
key
                        pair that is used to secure connections to the instance.
       :param security_groups: A list of Boto3 SecurityGroup objects that
represents the
                               security groups that are used to grant access to the
                               instance. When no security groups are specified, the
                               default security group of the VPC is used.
       :return: A Boto3 Instance object that represents the newly created instance.
       """
       try:
           instance_params = {
               "ImageId": image.id,
               "InstanceType": instance_type,
               "KeyName": key_pair.name,
           }
           if security_groups is not None:
               instance_params["SecurityGroupIds"] = [sg.id for sg in
security_groups]
           self.instance = self.ec2_resource.create_instances(
               **instance_params, MinCount=1, MaxCount=1
           )[0]
           self.instance.wait_until_running()
       except ClientError as err:
           logging.error(
               "Couldn't create instance with image %s, instance type %s, and key
%s. "
               "Here's why: %s: %s",
               image.id,
               instance_type,
               key_pair.name,
               err.response["Error"]["Code"],
               err.response["Error"]["Message"],
           )
           raise
```

```
        else:
            return self.instance


    def display(self, indent=1):
        """
        Displays information about an instance.

        :param indent: The visual indent to apply to the output.
        """
        if self.instance is None:
            logger.info("No instance to display.")
            return

        try:
            self.instance.load()
            ind = "\t" * indent
            print(f"{ind}ID: {self.instance.id}")
            print(f"{ind}Image ID: {self.instance.image_id}")
            print(f"{ind}Instance type: {self.instance.instance_type}")
            print(f"{ind}Key name: {self.instance.key_name}")
            print(f"{ind}VPC ID: {self.instance.vpc_id}")
            print(f"{ind}Public IP: {self.instance.public_ip_address}")
            print(f"{ind}State: {self.instance.state['Name']}")
        except ClientError as err:
            logger.error(
                "Couldn't display your instance. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def terminate(self):
        """
        Terminates an instance and waits for it to be in a terminated state.
        """
        if self.instance is None:
            logger.info("No instance to terminate.")
            return

        instance_id = self.instance.id
        try:
            self.instance.terminate()
```

```
            self.instance.wait_until_terminated()
            self.instance = None
        except ClientError as err:
            logging.error(
                "Couldn't terminate instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def start(self):
        """
        Starts an instance and waits for it to be in a running state.

        :return: The response to the start request.
        """
        if self.instance is None:
            logger.info("No instance to start.")
            return

        try:
            response = self.instance.start()
            self.instance.wait_until_running()
        except ClientError as err:
            logger.error(
                "Couldn't start instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def stop(self):
        """
        Stops an instance and waits for it to be in a stopped state.

        :return: The response to the stop request.
        """
        if self.instance is None:
```

```
            logger.info("No instance to stop.")
            return

        try:
            response = self.instance.stop()
            self.instance.wait_until_stopped()
        except ClientError as err:
            logger.error(
                "Couldn't stop instance %s. Here's why: %s: %s",
                self.instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def get_images(self, image_ids):
        """
        Gets information about Amazon Machine Images (AMIs) from a list of AMI IDs.

        :param image_ids: The list of AMIs to look up.
        :return: A list of Boto3 Image objects that represent the requested AMIs.
        """
        try:
            images = list(self.ec2_resource.images.filter(ImageIds=image_ids))
        except ClientError as err:
            logger.error(
                "Couldn't get images. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return images


    def get_instance_types(self, architecture):
        """
        Gets instance types that support the specified architecture and are
designated
        as either 'micro' or 'small'. When an instance is created, the instance type
        you specify must support the architecture of the AMI you use.
```

```
        :param architecture: The kind of architecture the instance types must
 support,
                             such as 'x86_64'.
        :return: A list of instance types that support the specified architecture
                 and are either 'micro' or 'small'.
        """
        try:
            inst_types = []
            it_paginator = self.ec2_resource.meta.client.get_paginator(
                "describe_instance_types"
            )
            for page in it_paginator.paginate(
                Filters=[
                    {
                        "Name": "processor-info.supported-architecture",
                        "Values": [architecture],
                    },
                    {"Name": "instance-type", "Values": ["*.micro", "*.small"]},
                ]
            ):
                inst_types += page["InstanceTypes"]
        except ClientError as err:
            logger.error(
                "Couldn't get instance types. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_types
```

Defina uma classe que envolva as ações de IP elástico.

```
class ElasticIpWrapper:
    """Encapsulates Amazon Elastic Compute Cloud (Amazon EC2) Elastic IP address
 actions."""

    def __init__(self, ec2_resource, elastic_ip=None):
```

```
        """
        :param ec2_resource: A Boto3 Amazon EC2 resource. This high-level resource
                             is used to create additional high-level objects
                             that wrap low-level Amazon EC2 service actions.
        :param elastic_ip: A Boto3 VpcAddress object. This is a high-level object
that
                           wraps Elastic IP actions.
        """
        self.ec2_resource = ec2_resource
        self.elastic_ip = elastic_ip

    @classmethod
    def from_resource(cls):
        ec2_resource = boto3.resource("ec2")
        return cls(ec2_resource)


    def allocate(self):
        """
        Allocates an Elastic IP address that can be associated with an Amazon EC2
        instance. By using an Elastic IP address, you can keep the public IP address
        constant even when you restart the associated instance.

        :return: The newly created Elastic IP object. By default, the address is not
                 associated with any instance.
        """
        try:
            response = self.ec2_resource.meta.client.allocate_address(Domain="vpc")
            self.elastic_ip = self.ec2_resource.VpcAddress(response["AllocationId"])
        except ClientError as err:
            logger.error(
                "Couldn't allocate Elastic IP. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.elastic_ip


    def associate(self, instance):
        """
        Associates an Elastic IP address with an instance. When this association is
```

```
        created, the Elastic IP's public IP address is immediately used as the
public
        IP address of the associated instance.

        :param instance: A Boto3 Instance object. This is a high-level object that
wraps
                         Amazon EC2 instance actions.
        :return: A response that contains the ID of the association.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to associate.")
            return

        try:
            response = self.elastic_ip.associate(InstanceId=instance.id)
        except ClientError as err:
            logger.error(
                "Couldn't associate Elastic IP %s with instance %s. Here's why: %s:
%s",
                self.elastic_ip.allocation_id,
                instance.id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        return response


    def disassociate(self):
        """
        Removes an association between an Elastic IP address and an instance. When
the
        association is removed, the instance is assigned a new public IP address.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to disassociate.")
            return

        try:
            self.elastic_ip.association.delete()
        except ClientError as err:
            logger.error(
                "Couldn't disassociate Elastic IP %s from its instance. Here's why:
%s: %s",
```

```
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def release(self):
        """
        Releases an Elastic IP address. After the Elastic IP address is released,
        it can no longer be used.
        """
        if self.elastic_ip is None:
            logger.info("No Elastic IP to release.")
            return

        try:
            self.elastic_ip.release()
        except ClientError as err:
            logger.error(
                "Couldn't release Elastic IP address %s. Here's why: %s: %s",
                self.elastic_ip.allocation_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AllocateAddress
  - AssociateAddress
  - AuthorizeSecurityGroupIngress
  - CreateKeyPair
  - CreateSecurityGroup
  - DeleteKeyPair
  - DeleteSecurityGroup

- DescribeImages
- DescribeInstanceTypes
- DescribeInstances
- DescribeKeyPairs
- DescribeSecurityGroups
- DisassociateAddress
- ReleaseAddress
- RunInstances
- StartInstances
- StopInstances
- TerminateInstances
- UnmonitorInstances

Exemplos de Elastic Load Balancing usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Elastic Load Balancing.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Elastic Load Balancing

O exemplo de código a seguir mostra como começar a usar o Elastic Load Balancing.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_elbv2(elbv2_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Elastic Load Balancing V2 client
 and list
    up to ten of the load balancers for your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param elbv2_client: A Boto3 Elastic Load Balancing V2 client object.
    """
    print("Hello, Elastic Load Balancing! Let's list some of your load balancers:")
    load_balancers = elbv2_client.describe_load_balancers(PageSize=10).get(
        "LoadBalancers", []
    )
    if load_balancers:
        for lb in load_balancers:
            print(f"\t{lb['LoadBalancerName']}: {lb['DNSName']}")
    else:
        print("Your account doesn't have any load balancers.")


if __name__ == "__main__":
    hello_elbv2(boto3.client("elbv2"))
```

- Para obter detalhes da API, consulte a DescribeLoadBalancersReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações

- Cenários

Ações

Criar um receptor para o balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como criar um receptor que encaminha solicitações de um balanceador de carga do ELB para um grupo de destino.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
 subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
 the
```

```
                            load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer
```

- Para obter detalhes da API, consulte a CreateListenerReferência da API AWSSDK for Python (Boto3).

Criar um grupo de destino

O exemplo de código a seguir mostra como criar um grupo de destino do ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group specifies
 how
        the load balancer forward requests to instances in the group and how
 instance
        health is checked.

        To speed up this demo, the health check is configured with shortened times
 and
```

```
        lower thresholds. In production, you might want to decrease the sensitivity
of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group
```

- Para obter detalhes da API, consulte a CreateTargetGroupReferência da API AWSSDK for Python (Boto3).

Criar um Application Load Balancer

O exemplo de código a seguir mostra como criar um balanceador de carga de aplicações do ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
 subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
 the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
```

```
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer
```

- Para obter detalhes da API, consulte a CreateLoadBalancerReferência da API AWSSDK for Python (Boto3).

Excluir um balanceador de carga

O exemplo de código a seguir mostra como excluir um balanceador de carga do ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
```

```
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
 {err}"
                )
```

- Para obter detalhes da API, consulte a DeleteLoadBalancerReferência da API AWSSDK for Python (Boto3).

Excluir um grupo de destino

O exemplo de código a seguir mostra como excluir um grupo de destino do ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def delete_target_group(self):
```

```
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )
```

- Para obter detalhes da API, consulte a DeleteTargetGroupReferência da API AWSSDK for Python (Boto3).

Obter o endpoint de um balanceador de carga (Load Balancer)

O exemplo de código a seguir mostra como obter um endpoint de um balanceador de carga ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
 {self.load_balancer_name}: {err}"
                )
        return self._endpoint
```

- Para obter detalhes da API, consulte a DescribeLoadBalancersReferência da API AWSSDK for Python (Boto3).

Obter a integridade de um grupo de destino

O exemplo de código a seguir mostra como obter a integridade de instâncias em um grupo de destino do ELB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
```

```
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets: {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

- Para obter detalhes da API, consulte a DescribeTargetHealthReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer, param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
 several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways to
 make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide book,
 movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each contain
 a Python web server."
```

```
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
 Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
 Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
 '{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when an
 instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
 script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
 and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In production,
 the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged credentials.
\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
 assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
 Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
```

```
            f"Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or continue
with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load balancer
provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port is
open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
```

```
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for your
 default VPC must\n"
                    "allows access from this computer. You can either add it
 automatically from this\n"
                    "example or add it yourself using the AWS Management Console.\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
 address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
 {sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging from
 your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
```

```
                "Couldn't get a successful response from the load balancer endpoint.
Troubleshoot by\n"
                "manually verifying that your VPC and security group are configured
correctly and that\n"
                "you can successfully make a GET request to the load balancer
endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
```

```
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health check
to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts of
the system\n"
            "to create situations where the web service fails, and shows how using a
resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations by
querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
```

```
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't check
for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with a
somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns a
static response.\n"
            f"The service still reports as healthy because health checks are still
shallow.\n"
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in the
target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a profile
that contains\n"
```

```
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto Scaling
instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling group
when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect when
one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
```

```
            "\nBecause the instances in this demo are controlled by an auto scaler,
 the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
 instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
 starting, sending a GET\n"
            "request to the web service continues to get a successful recommendation
 response because\n"
            "the load balancer routes requests to the healthy instances. After the
 replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
 rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
 several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
 running and healthy.\n"
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean all
 instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient service.
\n"
            "To keep things tidy and to avoid unwanted charges on your account, we
 can clean up all AWS resources\n"
            "that were created for this demo."
```

```
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ", q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM policies
 and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
```

```
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer, param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
```

```
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        """
        as_client = boto3.client("autoscaling")
```

```
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is assumed
by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as AmazonSSMManagedInstanceCore
to grant
                                     use of Systems Manager to send commands to the
instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
```

```
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
 role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
 profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to role
\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
```

```
            response = self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the profile
is
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
```

```
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
```

```
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.
```

```
        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.", self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a permissions
policy
                                     to create and attach to the instance profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
```

```
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template {self.launch_template_name}:
{err}."
                )
        return template
```

```
    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template {self.launch_template_name}:
{err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones
```

```
    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
```

```
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group {self.group_name}:
{err}"
            )
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.
```

```
        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group %s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
```

```
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] == "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
```

```
                log.info("No groups found named %s, nothing to do.",
self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
{err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress from
this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
```

```
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to either
this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or to a
prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
```

```
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port} from
{ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
```

```
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by this
 class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
```

```
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group specifies
how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened times
and
        lower thresholds. In production, you might want to decrease the sensitivity
of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
```

```
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
```

```
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
```

```
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
```

```
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint, retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets: {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books, movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended, such
 as
        Book or Movie, and a range key named 'ItemId' that, combined with the
 MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
```

```
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5, "WriteCapacityUnits":
5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name, data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}: {err}"
            )
```

```
    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters to
 drive
    the demonstration of resilient architecture, such as failure of a dependency or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
```

```
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile

- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Exemplos do Amazon EMR usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon EMR.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar etapas a um fluxo de trabalho

O exemplo de código a seguir mostra como adicionar etapas a fluxo de trabalho do Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Adicionar uma etapa do Spark, que é executada pelo cluster assim que é adicionada.

```
def add_step(cluster_id, name, script_uri, script_args, emr_client):
    """
    Adds a job step to the specified cluster. This example adds a Spark
    step, which is run by the cluster as soon as it is added.

    :param cluster_id: The ID of the cluster.
    :param name: The name of the step.
    :param script_uri: The URI where the Python script is stored.
    :param script_args: Arguments to pass to the Python script.
    :param emr_client: The Boto3 EMR client object.
    :return: The ID of the newly added step.
    """
    try:
        response = emr_client.add_job_flow_steps(
            JobFlowId=cluster_id,
```

```
            Steps=[
                {
                    "Name": name,
                    "ActionOnFailure": "CONTINUE",
                    "HadoopJarStep": {
                        "Jar": "command-runner.jar",
                        "Args": [
                            "spark-submit",
                            "--deploy-mode",
                            "cluster",
                            script_uri,
                            *script_args,
                        ],
                    },
                }
            ],
        )
        step_id = response["StepIds"][0]
        logger.info("Started step with ID %s", step_id)
    except ClientError:
        logger.exception("Couldn't start step %s with URI %s.", name, script_uri)
        raise
    else:
        return step_id
```

Executar um comando do Amazon EMR File System (EMRFS) como uma etapa de trabalho em um cluster. Isso pode ser usado para automatizar comandos do EMRFS em um cluster em vez de executar comandos manualmente por meio de uma conexão SSH.

```
import boto3
from botocore.exceptions import ClientError


def add_emrfs_step(command, bucket_url, cluster_id, emr_client):
    """
    Add an EMRFS command as a job flow step to an existing cluster.

    :param command: The EMRFS command to run.
    :param bucket_url: The URL of a bucket that contains tracking metadata.
    :param cluster_id: The ID of the cluster to update.
```

```
    :param emr_client: The Boto3 Amazon EMR client object.
    :return: The ID of the added job flow step. Status can be tracked by calling
             the emr_client.describe_step() function.
    """
    job_flow_step = {
        "Name": "Example EMRFS Command Step",
        "ActionOnFailure": "CONTINUE",
        "HadoopJarStep": {
            "Jar": "command-runner.jar",
            "Args": ["/usr/bin/emrfs", command, bucket_url],
        },
    }

    try:
        response = emr_client.add_job_flow_steps(
            JobFlowId=cluster_id, Steps=[job_flow_step]
        )
        step_id = response["StepIds"][0]
        print(f"Added step {step_id} to cluster {cluster_id}.")
    except ClientError:
        print(f"Couldn't add a step to cluster {cluster_id}.")
        raise
    else:
        return step_id


def usage_demo():
    emr_client = boto3.client("emr")
    # Assumes the first waiting cluster has EMRFS enabled and has created metadata
    # with the default name of 'EmrFSMetadata'.
    cluster = emr_client.list_clusters(ClusterStates=["WAITING"])["Clusters"][0]
    add_emrfs_step(
        "sync", "s3://elasticmapreduce/samples/cloudfront", cluster["Id"],
 emr_client
    )


if __name__ == "__main__":
    usage_demo()
```

- Para obter detalhes da API, consulte a AddJobFlowStepsReferência da API AWSSDK for Python (Boto3).

Descrever um cluster

O exemplo de código a seguir mostra como descrever um cluster do Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_cluster(cluster_id, emr_client):
    """
    Gets detailed information about a cluster.

    :param cluster_id: The ID of the cluster to describe.
    :param emr_client: The Boto3 EMR client object.
    :return: The retrieved cluster information.
    """
    try:
        response = emr_client.describe_cluster(ClusterId=cluster_id)
        cluster = response["Cluster"]
        logger.info("Got data for cluster %s.", cluster["Name"])
    except ClientError:
        logger.exception("Couldn't get data for cluster %s.", cluster_id)
        raise
    else:
        return cluster
```

- Para obter detalhes da API, consulte a DescribeClusterReferência da API AWSSDK for Python (Boto3).

Descrever uma etapa

O exemplo de código a seguir mostra como descrever uma etapa no cluster Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_step(cluster_id, step_id, emr_client):
    """
    Gets detailed information about the specified step, including the current state
 of
    the step.

    :param cluster_id: The ID of the cluster.
    :param step_id: The ID of the step.
    :param emr_client: The Boto3 EMR client object.
    :return: The retrieved information about the specified step.
    """
    try:
        response = emr_client.describe_step(ClusterId=cluster_id, StepId=step_id)
        step = response["Step"]
        logger.info("Got data for step %s.", step_id)
    except ClientError:
        logger.exception("Couldn't get data for step %s.", step_id)
        raise
    else:
        return step
```

- Para obter detalhes da API, consulte a DescribeStepReferência da API AWSSDK for Python (Boto3).

Listar etapas para um cluster

O exemplo de código a seguir mostra como descrever etapas em cluster do Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_steps(cluster_id, emr_client):
    """
    Gets a list of steps for the specified cluster. In this example, all steps are
    returned, including completed and failed steps.

    :param cluster_id: The ID of the cluster.
    :param emr_client: The Boto3 EMR client object.
    :return: The list of steps for the specified cluster.
    """
    try:
        response = emr_client.list_steps(ClusterId=cluster_id)
        steps = response["Steps"]
        logger.info("Got %s steps for cluster %s.", len(steps), cluster_id)
    except ClientError:
        logger.exception("Couldn't get steps for cluster %s.", cluster_id)
        raise
    else:
        return steps
```

- Para obter detalhes da API, consulte a ListStepsReferência da API AWSSDK for Python (Boto3).

Executar um fluxo de trabalho

O exemplo de código a seguir mostra como executar um fluxo de trabalho do Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def run_job_flow(
    name,
    log_uri,
    keep_alive,
    applications,
    job_flow_role,
    service_role,
    security_groups,
    steps,
    emr_client,
):
    """
    Runs a job flow with the specified steps. A job flow creates a cluster of
    instances and adds steps to be run on the cluster. Steps added to the cluster
    are run as soon as the cluster is ready.

    This example uses the 'emr-5.30.1' release. A list of recent releases can be
    found here:
        https://docs.aws.amazon.com/emr/latest/ReleaseGuide/emr-release-
components.html.

    :param name: The name of the cluster.
    :param log_uri: The URI where logs are stored. This can be an Amazon S3 bucket
 URL,
                    such as 's3://my-log-bucket'.
    :param keep_alive: When True, the cluster is put into a Waiting state after all
                       steps are run. When False, the cluster terminates itself when
                       the step queue is empty.
    :param applications: The applications to install on each instance in the
 cluster,
                         such as Hive or Spark.
    :param job_flow_role: The IAM role assumed by the cluster.
    :param service_role: The IAM role assumed by the service.
    :param security_groups: The security groups to assign to the cluster instances.
```

```
                            Amazon EMR adds all needed rules to these groups, so
                            they can be empty if you require only the default rules.
    :param steps: The job flow steps to add to the cluster. These are run in order
                  when the cluster is ready.
    :param emr_client: The Boto3 EMR client object.
    :return: The ID of the newly created cluster.
    """
    try:
        response = emr_client.run_job_flow(
            Name=name,
            LogUri=log_uri,
            ReleaseLabel="emr-5.30.1",
            Instances={
                "MasterInstanceType": "m5.xlarge",
                "SlaveInstanceType": "m5.xlarge",
                "InstanceCount": 3,
                "KeepJobFlowAliveWhenNoSteps": keep_alive,
                "EmrManagedMasterSecurityGroup": security_groups["manager"].id,
                "EmrManagedSlaveSecurityGroup": security_groups["worker"].id,
            },
            Steps=[
                {
                    "Name": step["name"],
                    "ActionOnFailure": "CONTINUE",
                    "HadoopJarStep": {
                        "Jar": "command-runner.jar",
                        "Args": [
                            "spark-submit",
                            "--deploy-mode",
                            "cluster",
                            step["script_uri"],
                            *step["script_args"],
                        ],
                    },
                }
                for step in steps
            ],
            Applications=[{"Name": app} for app in applications],
            JobFlowRole=job_flow_role.name,
            ServiceRole=service_role.name,
            EbsRootVolumeSize=10,
            VisibleToAllUsers=True,
        )
        cluster_id = response["JobFlowId"]
```

```
        logger.info("Created cluster %s.", cluster_id)
    except ClientError:
        logger.exception("Couldn't create cluster.")
        raise
    else:
        return cluster_id
```

- Para obter detalhes da API, consulte a RunJobFlowReferência da API AWSSDK for Python (Boto3).

Encerrar fluxos de trabalho

O exemplo de código a seguir mostra como encerrar fluxos de trabalho do Amazon EMR.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def terminate_cluster(cluster_id, emr_client):
    """
    Terminates a cluster. This terminates all instances in the cluster and cannot
    be undone. Any data not saved elsewhere, such as in an Amazon S3 bucket, is
 lost.

    :param cluster_id: The ID of the cluster to terminate.
    :param emr_client: The Boto3 EMR client object.
    """
    try:
        emr_client.terminate_job_flows(JobFlowIds=[cluster_id])
        logger.info("Terminated cluster %s.", cluster_id)
    except ClientError:
        logger.exception("Couldn't terminate cluster %s.", cluster_id)
        raise
```

- Para obter detalhes da API, consulte a TerminateJobFlowsReferência da API AWSSDK for Python (Boto3).

Cenários

Criar um cluster do Amazon EMR de curta duração e executar uma etapa usando

O exemplo de código a seguir mostra como criar um cluster do Amazon EMR de curta duração que executa uma etapa e termina automaticamente após a conclusão dessa etapa.

SDK para Python (Boto3)

Crie um cluster do Amazon EMR de curta duração que estime o valor de pi usando o Apache Spark para paralelizar um grande número de cálculos. O trabalho grava a saída em logs do Amazon EMR e em um bucket do Amazon Simple Storage Service (Amazon S3). O cluster é encerrado automaticamente após a conclusão do trabalho.

- Crie um bucket do Amazon S3 e carregue um script de trabalho.
- Crie perfis do AWS Identity and Access Management (IAM).
- Crie grupos de segurança do Amazon Elastic Compute Cloud (Amazon EC2).
- Criar um cluster de curta duração e executar uma única etapa do trabalho.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon EMR

Executar um script shell para instalar bibliotecas

O exemplo de código a seguir mostra como usar AWS Systems Manager para executar um script de shell em instâncias do Amazon EMR que instalam bibliotecas adicionais. Dessa forma, é possível automatizar o gerenciamento de instâncias em vez de executar comandos manualmente por meio de uma conexão SSH.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import argparse
import time
import boto3


def install_libraries_on_core_nodes(cluster_id, script_path, emr_client,
 ssm_client):
    """
    Copies and runs a shell script on the core nodes in the cluster.

    :param cluster_id: The ID of the cluster.
    :param script_path: The path to the script, typically an Amazon S3 object URL.
    :param emr_client: The Boto3 Amazon EMR client.
    :param ssm_client: The Boto3 AWS Systems Manager client.
    """
    core_nodes = emr_client.list_instances(
        ClusterId=cluster_id, InstanceGroupTypes=["CORE"]
    )["Instances"]
    core_instance_ids = [node["Ec2InstanceId"] for node in core_nodes]
    print(f"Found core instances: {core_instance_ids}.")

    commands = [
        # Copy the shell script from Amazon S3 to each node instance.
        f"aws s3 cp {script_path} /home/hadoop",
        # Run the shell script to install libraries on each node instance.
        "bash /home/hadoop/install_libraries.sh",
    ]
    for command in commands:
        print(f"Sending '{command}' to core instances...")
        command_id = ssm_client.send_command(
            InstanceIds=core_instance_ids,
            DocumentName="AWS-RunShellScript",
            Parameters={"commands": [command]},
            TimeoutSeconds=3600,
```

```
        )["Command"]["CommandId"]
        while True:
            # Verify the previous step succeeded before running the next step.
            cmd_result = ssm_client.list_commands(CommandId=command_id)["Commands"]
[0]
            if cmd_result["StatusDetails"] == "Success":
                print(f"Command succeeded.")
                break
            elif cmd_result["StatusDetails"] in ["Pending", "InProgress"]:
                print(f"Command status is {cmd_result['StatusDetails']},
 waiting...")
                time.sleep(10)
            else:
                print(f"Command status is {cmd_result['StatusDetails']}, quitting.")
                raise RuntimeError(
                    f"Command {command} failed to run. "
                    f"Details: {cmd_result['StatusDetails']}"
                )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument("cluster_id", help="The ID of the cluster.")
    parser.add_argument("script_path", help="The path to the script in Amazon S3.")
    args = parser.parse_args()

    emr_client = boto3.client("emr")
    ssm_client = boto3.client("ssm")

    install_libraries_on_core_nodes(
        args.cluster_id, args.script_path, emr_client, ssm_client
    )


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a ListInstancesReferência da API AWSSDK for Python (Boto3).

Exemplos de AWS Glue usando o SDK para Python (Boto3)

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

Os exemplos de código a seguir mostram como criar um crawler do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
```

```
        """
        self.glue_client = glue_client


    def create_crawler(self, name, role_arn, db_name, db_prefix, s3_target):
        """
        Creates a crawler that can crawl the specified target and populate a
        database in your AWS Glue Data Catalog with metadata that describes the data
        in the target.

        :param name: The name of the crawler.
        :param role_arn: The Amazon Resource Name (ARN) of an AWS Identity and
Access
                         Management (IAM) role that grants permission to let AWS
Glue
                         access the resources it needs.
        :param db_name: The name to give the database that is created by the
crawler.
        :param db_prefix: The prefix to give any database tables that are created by
                          the crawler.
        :param s3_target: The URL to an S3 bucket that contains data that is
                          the target of the crawler.
        """
        try:
            self.glue_client.create_crawler(
                Name=name,
                Role=role_arn,
                DatabaseName=db_name,
                TablePrefix=db_prefix,
                Targets={"S3Targets": [{"Path": s3_target}]},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create crawler. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateCrawlerReferência da API AWSSDK for Python (Boto3).

Crie uma definição de trabalho

Os exemplos de código a seguir mostram como criar uma definição de trabalho do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def create_job(self, name, description, role_arn, script_location):
        """
        Creates a job definition for an extract, transform, and load (ETL) job that
 can
        be run by AWS Glue.

        :param name: The name of the job definition.
        :param description: The description of the job definition.
        :param role_arn: The ARN of an IAM role that grants AWS Glue the permissions
                         it requires to run the job.
        :param script_location: The Amazon S3 URL of a Python ETL script that is run
 as
                                part of the job. The script defines how the data is
                                transformed.
        """
        try:
            self.glue_client.create_job(
                Name=name,
                Description=description,
                Role=role_arn,
                Command={
```

```
                    "Name": "glueetl",
                    "ScriptLocation": script_location,
                    "PythonVersion": "3",
                },
                GlueVersion="3.0",
            )
        except ClientError as err:
            logger.error(
                "Couldn't create job %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a CreateJobReferência da API AWSSDK for Python (Boto3).

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client
```

```
    def delete_crawler(self, name):
        """
        Deletes a crawler.

        :param name: The name of the crawler to delete.
        """
        try:
            self.glue_client.delete_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteCrawlerReferência da API AWSSDK for Python (Boto3).

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
```

```
        self.glue_client = glue_client


    def delete_database(self, name):
        """
        Deletes a metadata database from your Data Catalog.

        :param name: The name of the database to delete.
        """
        try:
            self.glue_client.delete_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteDatabaseReferência da API AWSSDK for Python (Boto3).

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""
```

```
    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_job(self, job_name):
        """
        Deletes a job definition. This also deletes data about all runs that are
        associated with this job definition.

        :param job_name: The name of the job definition to delete.
        """
        try:
            self.glue_client.delete_job(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete job %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteJobReferência da API AWSSDK for Python (Boto3).

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela de um banco de dados do AWS Glue Data Catalog.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def delete_table(self, db_name, table_name):
        """
        Deletes a table from a metadata database.

        :param db_name: The name of the database that contains the table.
        :param table_name: The name of the table to delete.
        """
        try:
            self.glue_client.delete_table(DatabaseName=db_name, Name=table_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_crawler(self, name):
        """
        Gets information about a crawler.

        :param name: The name of the crawler to look up.
        :return: Data about the crawler.
        """
        crawler = None
        try:
            response = self.glue_client.get_crawler(Name=name)
            crawler = response["Crawler"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityNotFoundException":
                logger.info("Crawler %s doesn't exist.", name)
            else:
                logger.error(
                    "Couldn't get crawler %s. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return crawler
```

- Para obter detalhes da API, consulte a GetCrawlerReferência da API AWSSDK for Python (Boto3).

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_database(self, name):
        """
        Gets information about a database in your Data Catalog.

        :param name: The name of the database to look up.
        :return: Information about the database.
        """
        try:
            response = self.glue_client.get_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't get database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return response["Database"]
```

- Para obter detalhes da API, consulte a GetDatabaseReferência da API AWSSDK for Python (Boto3).

Obter uma execução de trabalho

Os exemplos de código a seguir mostram como obter uma execução de trabalho do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_job_run(self, name, run_id):
        """
        Gets information about a single job run.

        :param name: The name of the job definition for the run.
        :param run_id: The ID of the run.
        :return: Information about the run.
        """
        try:
            response = self.glue_client.get_job_run(JobName=name, RunId=run_id)
```

```
        except ClientError as err:
            logger.error(
                "Couldn't get job run %s/%s. Here's why: %s: %s",
                name,
                run_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRun"]
```

- Para obter detalhes da API, consulte a GetJobRunReferência da API AWSSDK for Python (Boto3).

Obter execuções de um trabalho

O exemplo de código a seguir mostra como obter execuções de um trabalho do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_job_runs(self, job_name):
        """
        Gets information about runs that have been performed for a specific job
```

```
        definition.

        :param job_name: The name of the job definition to look up.
        :return: The list of job runs.
        """
        try:
            response = self.glue_client.get_job_runs(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't get job runs for %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRuns"]
```

- Para obter detalhes da API, consulte a GetJobRunsReferência da API AWSSDK for Python (Boto3).

Obter tabelas de um banco de dados

Os exemplos de código a seguir mostram como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
```

```
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_tables(self, db_name):
        """
        Gets a list of tables in a Data Catalog database.

        :param db_name: The name of the database to query.
        :return: The list of tables in the database.
        """
        try:
            response = self.glue_client.get_tables(DatabaseName=db_name)
        except ClientError as err:
            logger.error(
                "Couldn't get tables %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["TableList"]
```

- Para obter detalhes da API, consulte a GetTablesReferência da API AWSSDK for Python (Boto3).

Listar definições de trabalho

Os exemplos de código a seguir mostram como listar definições de trabalho do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def list_jobs(self):
        """
        Lists the names of job definitions in your account.

        :return: The list of job definition names.
        """
        try:
            response = self.glue_client.list_jobs()
        except ClientError as err:
            logger.error(
                "Couldn't list jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobNames"]
```

- Para obter detalhes da API, consulte a ListJobsReferência da API AWSSDK for Python (Boto3).

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def start_crawler(self, name):
        """
        Starts a crawler. The crawler crawls its configured target and creates
        metadata that describes the data it finds in the target data source.

        :param name: The name of the crawler to start.
        """
        try:
            self.glue_client.start_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't start crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a StartCrawlerReferência da API AWSSDK for Python (Boto3).

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def start_job_run(self, name, input_database, input_table, output_bucket_name):
        """
        Starts a job run. A job run extracts data from the source, transforms it,
        and loads it to the output bucket.

        :param name: The name of the job definition.
        :param input_database: The name of the metadata database that contains
 tables
                               that describe the source data. This is typically
 created
                               by a crawler.
        :param input_table: The name of the table in the metadata database that
                            describes the source data.
        :param output_bucket_name: The S3 bucket where the output is written.
        :return: The ID of the job run.
        """
        try:
            # The custom Arguments that are passed to this function are used by the
            # Python ETL script to determine the location of input and output data.
            response = self.glue_client.start_job_run(
                JobName=name,
```

```
                Arguments={
                    "--input_database": input_database,
                    "--input_table": input_table,
                    "--output_bucket_url": f"s3://{output_bucket_name}/",
                },
            )
        except ClientError as err:
            logger.error(
                "Couldn't start job run %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRunId"]
```

- Para obter detalhes da API, consulte a StartJobRunReferência da API AWSSDK for Python (Boto3).

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do AWS Glue usadas no cenário.

```
class GlueWrapper:
    """Encapsulates AWS Glue actions."""

    def __init__(self, glue_client):
        """
        :param glue_client: A Boto3 Glue client.
        """
        self.glue_client = glue_client


    def get_crawler(self, name):
        """
        Gets information about a crawler.

        :param name: The name of the crawler to look up.
        :return: Data about the crawler.
        """
        crawler = None
        try:
            response = self.glue_client.get_crawler(Name=name)
            crawler = response["Crawler"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityNotFoundException":
                logger.info("Crawler %s doesn't exist.", name)
            else:
                logger.error(
                    "Couldn't get crawler %s. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return crawler
```

```
    def create_crawler(self, name, role_arn, db_name, db_prefix, s3_target):
        """
        Creates a crawler that can crawl the specified target and populate a
        database in your AWS Glue Data Catalog with metadata that describes the data
        in the target.

        :param name: The name of the crawler.
        :param role_arn: The Amazon Resource Name (ARN) of an AWS Identity and
Access
                         Management (IAM) role that grants permission to let AWS
Glue
                         access the resources it needs.
        :param db_name: The name to give the database that is created by the
crawler.
        :param db_prefix: The prefix to give any database tables that are created by
                          the crawler.
        :param s3_target: The URL to an S3 bucket that contains data that is
                          the target of the crawler.
        """
        try:
            self.glue_client.create_crawler(
                Name=name,
                Role=role_arn,
                DatabaseName=db_name,
                TablePrefix=db_prefix,
                Targets={"S3Targets": [{"Path": s3_target}]},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create crawler. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def start_crawler(self, name):
        """
        Starts a crawler. The crawler crawls its configured target and creates
        metadata that describes the data it finds in the target data source.

        :param name: The name of the crawler to start.
```

```
        """
        try:
            self.glue_client.start_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't start crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_database(self, name):
        """
        Gets information about a database in your Data Catalog.

        :param name: The name of the database to look up.
        :return: Information about the database.
        """
        try:
            response = self.glue_client.get_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't get database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["Database"]


    def get_tables(self, db_name):
        """
        Gets a list of tables in a Data Catalog database.

        :param db_name: The name of the database to query.
        :return: The list of tables in the database.
        """
        try:
            response = self.glue_client.get_tables(DatabaseName=db_name)
        except ClientError as err:
```

```
            logger.error(
                "Couldn't get tables %s. Here's why: %s: %s",
                db_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["TableList"]


    def create_job(self, name, description, role_arn, script_location):
        """
        Creates a job definition for an extract, transform, and load (ETL) job that
can
        be run by AWS Glue.

        :param name: The name of the job definition.
        :param description: The description of the job definition.
        :param role_arn: The ARN of an IAM role that grants AWS Glue the permissions
                         it requires to run the job.
        :param script_location: The Amazon S3 URL of a Python ETL script that is run
as
                                part of the job. The script defines how the data is
                                transformed.
        """
        try:
            self.glue_client.create_job(
                Name=name,
                Description=description,
                Role=role_arn,
                Command={
                    "Name": "glueetl",
                    "ScriptLocation": script_location,
                    "PythonVersion": "3",
                },
                GlueVersion="3.0",
            )
        except ClientError as err:
            logger.error(
                "Couldn't create job %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise


    def start_job_run(self, name, input_database, input_table, output_bucket_name):
        """
        Starts a job run. A job run extracts data from the source, transforms it,
        and loads it to the output bucket.

        :param name: The name of the job definition.
        :param input_database: The name of the metadata database that contains
tables
                               that describe the source data. This is typically
created
                               by a crawler.
        :param input_table: The name of the table in the metadata database that
                            describes the source data.
        :param output_bucket_name: The S3 bucket where the output is written.
        :return: The ID of the job run.
        """
        try:
            # The custom Arguments that are passed to this function are used by the
            # Python ETL script to determine the location of input and output data.
            response = self.glue_client.start_job_run(
                JobName=name,
                Arguments={
                    "--input_database": input_database,
                    "--input_table": input_table,
                    "--output_bucket_url": f"s3://{output_bucket_name}/",
                },
            )
        except ClientError as err:
            logger.error(
                "Couldn't start job run %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRunId"]


    def list_jobs(self):
```

```
        """
        Lists the names of job definitions in your account.

        :return: The list of job definition names.
        """
        try:
            response = self.glue_client.list_jobs()
        except ClientError as err:
            logger.error(
                "Couldn't list jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobNames"]


    def get_job_runs(self, job_name):
        """
        Gets information about runs that have been performed for a specific job
        definition.

        :param job_name: The name of the job definition to look up.
        :return: The list of job runs.
        """
        try:
            response = self.glue_client.get_job_runs(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't get job runs for %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRuns"]


    def get_job_run(self, name, run_id):
        """
        Gets information about a single job run.
```

```
        :param name: The name of the job definition for the run.
        :param run_id: The ID of the run.
        :return: Information about the run.
        """
        try:
            response = self.glue_client.get_job_run(JobName=name, RunId=run_id)
        except ClientError as err:
            logger.error(
                "Couldn't get job run %s/%s. Here's why: %s: %s",
                name,
                run_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["JobRun"]


    def delete_job(self, job_name):
        """
        Deletes a job definition. This also deletes data about all runs that are
        associated with this job definition.

        :param job_name: The name of the job definition to delete.
        """
        try:
            self.glue_client.delete_job(JobName=job_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete job %s. Here's why: %s: %s",
                job_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_table(self, db_name, table_name):
        """
        Deletes a table from a metadata database.

        :param db_name: The name of the database that contains the table.
        :param table_name: The name of the table to delete.
```

```
        """
        try:
            self.glue_client.delete_table(DatabaseName=db_name, Name=table_name)
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_database(self, name):
        """
        Deletes a metadata database from your Data Catalog.

        :param name: The name of the database to delete.
        """
        try:
            self.glue_client.delete_database(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete database %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_crawler(self, name):
        """
        Deletes a crawler.

        :param name: The name of the crawler to delete.
        """
        try:
            self.glue_client.delete_crawler(Name=name)
        except ClientError as err:
            logger.error(
                "Couldn't delete crawler %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma classe que execute o cenário.

```
class GlueCrawlerJobScenario:
    """
    Encapsulates a scenario that shows how to create an AWS Glue crawler and job and
 use
    them to transform data from CSV to JSON format.
    """

    def __init__(self, glue_client, glue_service_role, glue_bucket):
        """
        :param glue_client: A Boto3 AWS Glue client.
        :param glue_service_role: An AWS Identity and Access Management (IAM) role
                                  that AWS Glue can assume to gain access to the
                                  resources it requires.
        :param glue_bucket: An S3 bucket that can hold a job script and output data
                            from AWS Glue job runs.
        """
        self.glue_client = glue_client
        self.glue_service_role = glue_service_role
        self.glue_bucket = glue_bucket

    @staticmethod
    def wait(seconds, tick=12):
        """
        Waits for a specified number of seconds, while also displaying an animated
        spinner.

        :param seconds: The number of seconds to wait.
        :param tick: The number of frames per second used to animate the spinner.
        """
        progress = "|/-\\"
        waited = 0
        while waited < seconds:
            for frame in range(tick):
```

```
                sys.stdout.write(f"\r{progress[frame % len(progress)]}")
                sys.stdout.flush()
                time.sleep(1 / tick)
            waited += 1

    def upload_job_script(self, job_script):
        """
        Uploads a Python ETL script to an S3 bucket. The script is used by the AWS
Glue
        job to transform data.

        :param job_script: The relative path to the job script.
        """
        try:
            self.glue_bucket.upload_file(Filename=job_script, Key=job_script)
            print(f"Uploaded job script '{job_script}' to the example bucket.")
        except S3UploadFailedError as err:
            logger.error("Couldn't upload job script. Here's why: %s", err)
            raise

    def run(self, crawler_name, db_name, db_prefix, data_source, job_script,
job_name):
        """
        Runs the scenario. This is an interactive experience that runs at a command
        prompt and asks you for input throughout.

        :param crawler_name: The name of the crawler used in the scenario. If the
                             crawler does not exist, it is created.
        :param db_name: The name to give the metadata database created by the
crawler.
        :param db_prefix: The prefix to give tables added to the database by the
                          crawler.
        :param data_source: The location of the data source that is targeted by the
                            crawler and extracted during job runs.
        :param job_script: The job script that is used to transform data during job
                           runs.
        :param job_name: The name to give the job definition that is created during
the
                         scenario.
        """
        wrapper = GlueWrapper(self.glue_client)
        print(f"Checking for crawler {crawler_name}.")
        crawler = wrapper.get_crawler(crawler_name)
        if crawler is None:
```

```
            print(f"Creating crawler {crawler_name}.")
            wrapper.create_crawler(
                crawler_name,
                self.glue_service_role.arn,
                db_name,
                db_prefix,
                data_source,
            )
            print(f"Created crawler {crawler_name}.")
            crawler = wrapper.get_crawler(crawler_name)
        pprint(crawler)
        print("-" * 88)

        print(
            f"When you run the crawler, it crawls data stored in {data_source} and "
            f"creates a metadata database in the AWS Glue Data Catalog that
describes "
            f"the data in the data source."
        )
        print("In this example, the source data is in CSV format.")
        ready = False
        while not ready:
            ready = Question.ask_question(
                "Ready to start the crawler? (y/n) ", Question.is_yesno
            )
        wrapper.start_crawler(crawler_name)
        print("Let's wait for the crawler to run. This typically takes a few
minutes.")
        crawler_state = None
        while crawler_state != "READY":
            self.wait(10)
            crawler = wrapper.get_crawler(crawler_name)
            crawler_state = crawler["State"]
            print(f"Crawler is {crawler['State']}.")
        print("-" * 88)

        database = wrapper.get_database(db_name)
        print(f"The crawler created database {db_name}:")
        pprint(database)
        print(f"The database contains these tables:")
        tables = wrapper.get_tables(db_name)
        for index, table in enumerate(tables):
            print(f"\t{index + 1}. {table['Name']}")
        table_index = Question.ask_question(
```

```
            f"Enter the number of a table to see more detail: ",
            Question.is_int,
            Question.in_range(1, len(tables)),
        )
        pprint(tables[table_index - 1])
        print("-" * 88)

        print(f"Creating job definition {job_name}.")
        wrapper.create_job(
            job_name,
            "Getting started example job.",
            self.glue_service_role.arn,
            f"s3://{self.glue_bucket.name}/{job_script}",
        )
        print("Created job definition.")
        print(
            f"When you run the job, it extracts data from {data_source}, transforms
it "
            f"by using the {job_script} script, and loads the output into "
            f"S3 bucket {self.glue_bucket.name}."
        )
        print(
            "In this example, the data is transformed from CSV to JSON, and only a
few "
            "fields are included in the output."
        )
        job_run_status = None
        if Question.ask_question(f"Ready to run? (y/n) ", Question.is_yesno):
            job_run_id = wrapper.start_job_run(
                job_name, db_name, tables[0]["Name"], self.glue_bucket.name
            )
            print(f"Job {job_name} started. Let's wait for it to run.")
            while job_run_status not in ["SUCCEEDED", "STOPPED", "FAILED",
"TIMEOUT"]:
                self.wait(10)
                job_run = wrapper.get_job_run(job_name, job_run_id)
                job_run_status = job_run["JobRunState"]
                print(f"Job {job_name}/{job_run_id} is {job_run_status}.")
        print("-" * 88)

        if job_run_status == "SUCCEEDED":
            print(
                f"Data from your job run is stored in your S3 bucket
'{self.glue_bucket.name}':"
```

```
            )
            try:
                keys = [
                    obj.key for obj in
self.glue_bucket.objects.filter(Prefix="run-")
                ]
                for index, key in enumerate(keys):
                    print(f"\t{index + 1}: {key}")
                lines = 4
                key_index = Question.ask_question(
                    f"Enter the number of a block to download it and see the first
{lines} "
                    f"lines of JSON output in the block: ",
                    Question.is_int,
                    Question.in_range(1, len(keys)),
                )
                job_data = io.BytesIO()
                self.glue_bucket.download_fileobj(keys[key_index - 1], job_data)
                job_data.seek(0)
                for _ in range(lines):
                    print(job_data.readline().decode("utf-8"))
            except ClientError as err:
                logger.error(
                    "Couldn't get job run data. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
            print("-" * 88)

        job_names = wrapper.list_jobs()
        if job_names:
            print(f"Your account has {len(job_names)} jobs defined:")
            for index, job_name in enumerate(job_names):
                print(f"\t{index + 1}. {job_name}")
            job_index = Question.ask_question(
                f"Enter a number between 1 and {len(job_names)} to see the list of
runs for "
                f"a job: ",
                Question.is_int,
                Question.in_range(1, len(job_names)),
            )
            job_runs = wrapper.get_job_runs(job_names[job_index - 1])
            if job_runs:
```

```
                print(f"Found {len(job_runs)} runs for job {job_names[job_index -
1]}:")
                for index, job_run in enumerate(job_runs):
                    print(
                        f"\t{index + 1}. {job_run['JobRunState']} on "
                        f"{job_run['CompletedOn']:%Y-%m-%d %H:%M:%S}"
                    )
                run_index = Question.ask_question(
                    f"Enter a number between 1 and {len(job_runs)} to see details
for a run: ",
                    Question.is_int,
                    Question.in_range(1, len(job_runs)),
                )
                pprint(job_runs[run_index - 1])
            else:
                print(f"No runs found for job {job_names[job_index - 1]}")
        else:
            print("Your account doesn't have any jobs defined.")
        print("-" * 88)

        print(
            f"Let's clean up. During this example we created job definition
'{job_name}'."
        )
        if Question.ask_question(
            "Do you want to delete the definition and all runs? (y/n) ",
            Question.is_yesno,
        ):
            wrapper.delete_job(job_name)
            print(f"Job definition '{job_name}' deleted.")
        tables = wrapper.get_tables(db_name)
        print(f"We also created database '{db_name}' that contains these tables:")
        for table in tables:
            print(f"\t{table['Name']}")
        if Question.ask_question(
            "Do you want to delete the tables and the database? (y/n) ",
            Question.is_yesno,
        ):
            for table in tables:
                wrapper.delete_table(db_name, table["Name"])
                print(f"Deleted table {table['Name']}.")
            wrapper.delete_database(db_name)
            print(f"Deleted database {db_name}.")
        print(f"We also created crawler '{crawler_name}'.")
```

```
        if Question.ask_question(
            "Do you want to delete the crawler? (y/n) ", Question.is_yesno
        ):
            wrapper.delete_crawler(crawler_name)
            print(f"Deleted crawler {crawler_name}.")
        print("-" * 88)


def parse_args(args):
    """
    Parse command line arguments.

    :param args: The command line arguments.
    :return: The parsed arguments.
    """
    parser = argparse.ArgumentParser(
        description="Runs the AWS Glue getting started with crawlers and jobs
 scenario. "
        "Before you run this scenario, set up scaffold resources by running "
        "'python scaffold.py deploy'."
    )
    parser.add_argument(
        "role_name",
        help="The name of an IAM role that AWS Glue can assume. This role must grant
 access "
        "to Amazon S3 and to the permissions granted by the AWSGlueServiceRole "
        "managed policy.",
    )
    parser.add_argument(
        "bucket_name",
        help="The name of an S3 bucket that AWS Glue can access to get the job
 script and "
        "put job results.",
    )
    parser.add_argument(
        "--job_script",
        default="flight_etl_job_script.py",
        help="The name of the job script file that is used in the scenario.",
    )
    return parser.parse_args(args)


def main():
    args = parse_args(sys.argv[1:])
```

```
    try:
        print("-" * 88)
        print(
            "Welcome to the AWS Glue getting started with crawlers and jobs
 scenario."
        )
        print("-" * 88)
        scenario = GlueCrawlerJobScenario(
            boto3.client("glue"),
            boto3.resource("iam").Role(args.role_name),
            boto3.resource("s3").Bucket(args.bucket_name),
        )
        scenario.upload_job_script(args.job_script)
        scenario.run(
            "doc-example-crawler",
            "doc-example-database",
            "doc-example-",
            "s3://crawler-public-us-east-1/flight/2016/csv",
            args.job_script,
            "doc-example-job",
        )
        print("-" * 88)
        print(
            "To destroy scaffold resources, including the IAM role and S3 bucket "
            "used in this scenario, run 'python scaffold.py destroy'."
        )
        print("\nThanks for watching!")
        print("-" * 88)
    except Exception:
        logging.exception("Something went wrong with the example.")
```

Crie um script de ETL usado pelo AWS Glue para extrair, transformar e carregar dados durante execuções de trabalhos.

```
import sys
from awsglue.transforms import *
from awsglue.utils import getResolvedOptions
from pyspark.context import SparkContext
from awsglue.context import GlueContext
from awsglue.job import Job
```

```
"""
These custom arguments must be passed as Arguments to the StartJobRun request.
    --input_database    The name of a metadata database that is contained in your
                        AWS Glue Data Catalog and that contains tables that
 describe
                        the data to be processed.
    --input_table       The name of a table in the database that describes the data
 to
                        be processed.
    --output_bucket_url An S3 bucket that receives the transformed output data.
"""
args = getResolvedOptions(
    sys.argv, ["JOB_NAME", "input_database", "input_table", "output_bucket_url"]
)
sc = SparkContext()
glueContext = GlueContext(sc)
spark = glueContext.spark_session
job = Job(glueContext)
job.init(args["JOB_NAME"], args)

# Script generated for node S3 Flight Data.
S3FlightData_node1 = glueContext.create_dynamic_frame.from_catalog(
    database=args["input_database"],
    table_name=args["input_table"],
    transformation_ctx="S3FlightData_node1",
)

# This mapping performs two main functions:
# 1. It simplifies the output by removing most of the fields from the data.
# 2. It renames some fields. For example, `fl_date` is renamed to `flight_date`.
ApplyMapping_node2 = ApplyMapping.apply(
    frame=S3FlightData_node1,
    mappings=[
        ("year", "long", "year", "long"),
        ("month", "long", "month", "tinyint"),
        ("day_of_month", "long", "day", "tinyint"),
        ("fl_date", "string", "flight_date", "string"),
        ("carrier", "string", "carrier", "string"),
        ("fl_num", "long", "flight_num", "long"),
        ("origin_city_name", "string", "origin_city_name", "string"),
        ("origin_state_abr", "string", "origin_state_abr", "string"),
        ("dest_city_name", "string", "dest_city_name", "string"),
        ("dest_state_abr", "string", "dest_state_abr", "string"),
```

```
        ("dep_time", "long", "departure_time", "long"),
        ("wheels_off", "long", "wheels_off", "long"),
        ("wheels_on", "long", "wheels_on", "long"),
        ("arr_time", "long", "arrival_time", "long"),
        ("mon", "string", "mon", "string"),
    ],
    transformation_ctx="ApplyMapping_node2",
)

# Script generated for node Revised Flight Data.
RevisedFlightData_node3 = glueContext.write_dynamic_frame.from_options(
    frame=ApplyMapping_node2,
    connection_type="s3",
    format="json",
    connection_options={"path": args["output_bucket_url"], "partitionKeys": []},
    transformation_ctx="RevisedFlightData_node3",
)

job.commit()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs

- StartCrawler
- StartJobRun

HealthImaging exemplos usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) with HealthImaging.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar uma tag a um recurso

O exemplo de código a seguir mostra como adicionar uma tag a um HealthImaging recurso.

SDK para Python (Boto3)

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
tags=tags)
```

```
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a TagResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copiar um conjunto de imagens

O exemplo de código a seguir mostra como copiar um conjunto de HealthImaging imagens.

SDK para Python (Boto3)

Função de utilitário para copiar um conjunto de imagens.

```
    def copy_image_set(
        self,
        datastore_id,
        image_set_id,
        version_id,
        destination_image_set_id=None,
        destination_version_id=None,
    ):
        """
        Copy an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The ID of the image set version.
        :param destination_image_set_id: The ID of the optional destination image
set.
```

```
        :param destination_version_id: The ID of the optional destination image set
version.
        :return: The copied image set ID.
        """
        try:
            copy_image_set_information = {
                "sourceImageSet": {"latestVersionId": version_id}
            }
            if destination_image_set_id and destination_version_id:
                copy_image_set_information["destinationImageSet"] = {
                    "imageSetId": destination_image_set_id,
                    "latestVersionId": destination_version_id,
                }
            copy_results = self.health_imaging_client.copy_image_set(
                datastoreId=datastore_id,
                sourceImageSetId=image_set_id,
                copyImageSetInformation=copy_image_set_information,
            )
        except ClientError as err:
            logger.error(
                "Couldn't copy image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return copy_results["destinationImageSetProperties"]["imageSetId"]
```

Copie um conjunto de imagens sem um destino.

```
            copy_image_set_information = {
                "sourceImageSet": {"latestVersionId": version_id}
            }

            copy_results = self.health_imaging_client.copy_image_set(
                datastoreId=datastore_id,
                sourceImageSetId=image_set_id,
                copyImageSetInformation=copy_image_set_information,
            )
```

Copie um conjunto de imagens com um destino.

```
        copy_image_set_information = {
            "sourceImageSet": {"latestVersionId": version_id}
        }

        if destination_image_set_id and destination_version_id:
            copy_image_set_information["destinationImageSet"] = {
                "imageSetId": destination_image_set_id,
                "latestVersionId": destination_version_id,
            }

        copy_results = self.health_imaging_client.copy_image_set(
            datastoreId=datastore_id,
            sourceImageSetId=image_set_id,
            copyImageSetInformation=copy_image_set_information,
        )
```

- Para obter detalhes da API, consulte a CopyImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar um datastore

O exemplo de código a seguir mostra como criar um armazenamento HealthImaging de dados.

SDK para Python (Boto3)

```
    def create_datastore(self, name):
        """
        Create a data store.

        :param name: The name of the data store to create.
        :return: The data store ID.
        """
        try:
```

```
            data_store =
self.health_imaging_client.create_datastore(datastoreName=name)
        except ClientError as err:
            logger.error(
                "Couldn't create data store %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return data_store["datastoreId"]
```

- Para obter detalhes da API, consulte a CreateDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um datastore

O exemplo de código a seguir mostra como excluir um armazenamento HealthImaging de dados.

SDK para Python (Boto3)

```
    def delete_datastore(self, datastore_id):
        """
        Delete a data store.

        :param datastore_id: The ID of the data store.
        """
        try:
            self.health_imaging_client.delete_datastore(datastoreId=datastore_id)
        except ClientError as err:
            logger.error(
                "Couldn't delete data store %s. Here's why: %s: %s",
                datastore_id,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Excluir um conjunto de imagens

O exemplo de código a seguir mostra como excluir um conjunto de HealthImaging imagens.

SDK para Python (Boto3)

```
    def delete_image_set(self, datastore_id, image_set_id):
        """
        Delete an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :return: The delete results.
        """
        try:
            delete_results = self.health_imaging_client.delete_image_set(
                imageSetId=image_set_id, datastoreId=datastore_id
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
```

```
            return delete_results
```

- Para obter detalhes da API, consulte a DeleteImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter um quadro de imagem

O exemplo de código a seguir mostra como obter um frame de imagem.

SDK para Python (Boto3)

```
    def get_pixel_data(
        self, file_path_to_write, datastore_id, image_set_id, image_frame_id
    ):
        """
        Get an image frame's pixel data.

        :param file_path_to_write: The path to write the image frame's HTJ2K encoded
pixel data.
        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param image_frame_id: The ID of the image frame.
        """
        try:
            image_frame = self.health_imaging_client.get_image_frame(
                datastoreId=datastore_id,
                imageSetId=image_set_id,
                imageFrameInformation={"imageFrameId": image_frame_id},
            )
            with open(file_path_to_write, "wb") as f:
                for chunk in image_frame["imageFrameBlob"].iter_chunks():
                    if chunk:
                        f.write(chunk)
        except ClientError as err:
```

```
            logger.error(
                "Couldn't get image frame. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a GetImageFrameReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do datastore

O exemplo de código a seguir mostra como obter propriedades do armazenamento de HealthImaging dados.

SDK para Python (Boto3)

```
    def get_datastore_properties(self, datastore_id):
        """
        Get the properties of a data store.

        :param datastore_id: The ID of the data store.
        :return: The data store properties.
        """
        try:
            data_store = self.health_imaging_client.get_datastore(
                datastoreId=datastore_id
            )
        except ClientError as err:
            logger.error(
                "Couldn't get data store %s. Here's why: %s: %s",
                id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
        else:
            return data_store["datastoreProperties"]
```

- Para obter detalhes da API, consulte a GetDatastoreReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do conjunto de imagens

O exemplo de código a seguir mostra como obter as propriedades do conjunto de HealthImaging imagens.

SDK para Python (Boto3)

```
    def get_image_set(self, datastore_id, image_set_id, version_id=None):
        """
        Get the properties of an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The optional version of the image set.
        :return: The image set properties.
        """
        try:
            if version_id:
                image_set = self.health_imaging_client.get_image_set(
                    imageSetId=image_set_id,
                    datastoreId=datastore_id,
                    versionId=version_id,
                )
            else:
                image_set = self.health_imaging_client.get_image_set(
                    imageSetId=image_set_id, datastoreId=datastore_id
```

```
            )
        except ClientError as err:
            logger.error(
                "Couldn't get image set. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return image_set
```

- Para obter detalhes da API, consulte a GetImageSetReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter propriedades do trabalho de importação

O exemplo de código a seguir mostra como obter as propriedades do trabalho de importação.

SDK para Python (Boto3)

```
    def get_dicom_import_job(self, datastore_id, job_id):
        """
        Get the properties of a DICOM import job.

        :param datastore_id: The ID of the data store.
        :param job_id: The ID of the job.
        :return: The job properties.
        """
        try:
            job = self.health_imaging_client.get_dicom_import_job(
                jobId=job_id, datastoreId=datastore_id
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't get DICOM import job. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return job["jobProperties"]
```

- Para obter detalhes da API, consulte GetDICOM ImportJob na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obter metadados para um conjunto de imagem

O exemplo de código a seguir mostra como obter metadados para um conjunto de HealthImaging imagens.

SDK para Python (Boto3)

Função de utilitário para obter metadados do conjunto de imagens.

```
    def get_image_set_metadata(
        self, metadata_file, datastore_id, image_set_id, version_id=None
    ):
        """
        Get the metadata of an image set.

        :param metadata_file: The file to store the JSON gzipped metadata.
        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The version of the image set.
        """
        try:
            if version_id:
```

```
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id,
                    datastoreId=datastore_id,
                    versionId=version_id,
                )
            else:

                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id, datastoreId=datastore_id
                )
            print(image_set_metadata)
            with open(metadata_file, "wb") as f:
                for chunk in
image_set_metadata["imageSetMetadataBlob"].iter_chunks():
                    if chunk:
                        f.write(chunk)

        except ClientError as err:
            logger.error(
                "Couldn't get image metadata. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Obtenha metadados do conjunto de imagens sem versão.

```
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id, datastoreId=datastore_id
                )
```

Obtenha metadados do conjunto de imagens com versão.

```
                image_set_metadata =
self.health_imaging_client.get_image_set_metadata(
                    imageSetId=image_set_id,
```

```
                datastoreId=datastore_id,
                versionId=version_id,
            )
```

- Para obter detalhes da API, consulte a GetImageSetMetadataReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Importar dados em massa para um datastore

O exemplo de código a seguir mostra como importar dados em massa para um armazenamento HealthImaging de dados.

SDK para Python (Boto3)

```
    def start_dicom_import_job(
        self, job_name, datastore_id, role_arn, input_s3_uri, output_s3_uri
    ):
        """
        Start a DICOM import job.

        :param job_name: The name of the job.
        :param datastore_id: The ID of the data store.
        :param role_arn: The Amazon Resource Name (ARN) of the role to use for the
job.
        :param input_s3_uri: The S3 bucket input prefix path containing the DICOM
files.
        :param output_s3_uri: The S3 bucket output prefix path for the result.
        :return: The job ID.
        """
        try:
            job = self.health_imaging_client.start_dicom_import_job(
                jobName=job_name,
                datastoreId=datastore_id,
                dataAccessRoleArn=role_arn,
                inputS3Uri=input_s3_uri,
```

```
                outputS3Uri=output_s3_uri,
            )
        except ClientError as err:
            logger.error(
                "Couldn't start DICOM import job. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return job["jobId"]
```

- Para obter detalhes da API, consulte StartDICOM ImportJob na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar datastores

O exemplo de código a seguir mostra como listar armazenamentos HealthImaging de dados.

SDK para Python (Boto3)

```
    def list_datastores(self):
        """
        List the data stores.

        :return: The list of data stores.
        """
        try:
            paginator = self.health_imaging_client.get_paginator("list_datastores")
            page_iterator = paginator.paginate()
            datastore_summaries = []
            for page in page_iterator:
                datastore_summaries.extend(page["datastoreSummaries"])
        except ClientError as err:
```

```
            logger.error(
                "Couldn't list data stores. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return datastore_summaries
```

- Para obter detalhes da API, consulte a ListDatastoresReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar versões do conjunto de imagens

O exemplo de código a seguir mostra como listar as versões do conjunto de HealthImaging imagens.

SDK para Python (Boto3)

```
    def list_image_set_versions(self, datastore_id, image_set_id):
        """
        List the image set versions.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :return: The list of image set versions.
        """
        try:
            paginator = self.health_imaging_client.get_paginator(
                "list_image_set_versions"
            )
            page_iterator = paginator.paginate(
                imageSetId=image_set_id, datastoreId=datastore_id
            )
            image_set_properties_list = []
```

```
            for page in page_iterator:
                image_set_properties_list.extend(page["imageSetPropertiesList"])
        except ClientError as err:
            logger.error(
                "Couldn't list image set versions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return image_set_properties_list
```

- Para obter detalhes da API, consulte a ListImageSetVersionsReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar trabalhos de importação para um datastore

O exemplo de código a seguir mostra como listar trabalhos de importação para um armazenamento HealthImaging de dados.

SDK para Python (Boto3)

```
    def list_dicom_import_jobs(self, datastore_id):
        """
        List the DICOM import jobs.

        :param datastore_id: The ID of the data store.
        :return: The list of jobs.
        """
        try:
            paginator = self.health_imaging_client.get_paginator(
                "list_dicom_import_jobs"
            )
            page_iterator = paginator.paginate(datastoreId=datastore_id)
```

```
            job_summaries = []
            for page in page_iterator:
                job_summaries.extend(page["jobSummaries"])
        except ClientError as err:
            logger.error(
                "Couldn't list DICOM import jobs. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return job_summaries
```

- Para obter detalhes da API, consulte ListDicom ImportJobs na Referência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar as tags para um recurso

O exemplo de código a seguir mostra como listar as tags de um HealthImaging recurso.

SDK para Python (Boto3)

```
    def list_tags_for_resource(self, resource_arn):
        """
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
```

```
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

- Para obter detalhes da API, consulte a ListTagsForResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Remover tag de um recurso

O exemplo de código a seguir mostra como remover uma tag de um HealthImaging recurso.

SDK para Python (Boto3)

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
```

- Para obter detalhes da API, consulte a UntagResourceReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Pesquisar conjuntos de imagens

O exemplo de código a seguir mostra como pesquisar conjuntos de HealthImaging imagens.

SDK para Python (Boto3)

A função de utilitário para pesquisar conjuntos de imagens.

```
    def search_image_sets(self, datastore_id, search_filter):
        """
        Search for image sets.

        :param datastore_id: The ID of the data store.
        :param search_filter: The search filter.
            For example: {"filters" : [{ "operator": "EQUAL", "values":
[{"DICOMPatientId": "3524578"}]}]}.
        :return: The list of image sets.
        """
        try:
            paginator =
self.health_imaging_client.get_paginator("search_image_sets")
            page_iterator = paginator.paginate(
                datastoreId=datastore_id, searchCriteria=search_filter
            )
            metadata_summaries = []
            for page in page_iterator:
                metadata_summaries.extend(page["imageSetsMetadataSummaries"])
        except ClientError as err:
```

```
            logger.error(
                "Couldn't search image sets. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return metadata_summaries
```

Caso de uso nº 1: operador EQUAL.

```
        filter = {
            "filters": [
                {"operator": "EQUAL", "values": [{"DICOMPatientId": "3524578"}]}
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

Caso de uso #2: BETWEEN operador usando DICOM StudyDate e StudyTime DICOM.

```
        filter = {
            "filters": [
                {
                    "operator": "BETWEEN",
                    "values": [
                        {
                            "DICOMStudyDateAndTime": {
                                "DICOMStudyDate": "19900101",
                                "DICOMStudyTime": "000000",
                            }
                        },
                        {
                            "DICOMStudyDateAndTime": {
                                "DICOMStudyDate": "20230101",
                                "DICOMStudyTime": "000000",
                            }
                        },
                    ],
                }
```

```
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

Caso de uso nº 3: operador BETWEEN usando createdAt. Os estudos de tempo foram previamente persistidos.

```
        filter = {
            "filters": [
                {
                    "values": [
                        {
                            "createdAt": datetime.datetime(
                                2021, 8, 4, 14, 49, 54, 429000
                            )
                        },
                        {
                            "createdAt": datetime.datetime.now()
                            + datetime.timedelta(days=1)
                        },
                    ],
                    "operator": "BETWEEN",
                }
            ]
        }

        image_sets = self.search_image_sets(data_store_id, filter)
```

- Para obter detalhes da API, consulte a SearchImageSetsReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Atualizar metadados do conjunto de imagens

O exemplo de código a seguir mostra como atualizar os metadados do conjunto de HealthImaging imagens.

SDK para Python (Boto3)

```
    def update_image_set_metadata(
        self, datastore_id, image_set_id, version_id, metadata
    ):
        """
        Update the metadata of an image set.

        :param datastore_id: The ID of the data store.
        :param image_set_id: The ID of the image set.
        :param version_id: The ID of the image set version.
        :param metadata: The image set metadata as a dictionary.
            For example {"DICOMUpdates": {"updatableAttributes":
            "{\"SchemaVersion\":1.1,\"Patient\":{\"DICOM\":{\"PatientName\":
\"Garcia^Gloria\"}}}"}}
        :return: The updated image set metadata.
        """
        try:
            updated_metadata = self.health_imaging_client.update_image_set_metadata(
                imageSetId=image_set_id,
                datastoreId=datastore_id,
                latestVersionId=version_id,
                updateImageSetMetadataUpdates=metadata,
            )
        except ClientError as err:
            logger.error(
                "Couldn't update image set metadata. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return updated_metadata
```

- Para obter detalhes da API, consulte a UpdateImageSetMetadataReferência da API AWSSDK for Python (Boto3).

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cenários

Marcar um datastore

O exemplo de código a seguir mostra como marcar um armazenamento HealthImaging de dados.

SDK para Python (Boto3)

Para marcar um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.tag_resource(data_store_arn, {"Deployment":
 "Development"})
```

A função utilitária para marcar um recurso.

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
 tags=tags)
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Para listar tags para um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.list_tags_for_resource(data_store_arn)
```

A função utilitária para listar as tags de um recurso.

```
    def list_tags_for_resource(self, resource_arn):
        """
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

Para desmarcar um armazenamento de dados

```
    a_data_store_arn = "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012"

    medical_imaging_wrapper.untag_resource(data_store_arn, ["Deployment"])
```

A função de utilitário para desmarcar um recurso.

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Marcar um conjunto de imagens

O exemplo de código a seguir mostra como marcar um conjunto de HealthImaging imagens.

SDK para Python (Boto3)

Para marcar um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
    )

    medical_imaging_wrapper.tag_resource(image_set_arn, {"Deployment":
 "Development"})
```

A função utilitária para marcar um recurso.

```
    def tag_resource(self, resource_arn, tags):
        """
        Tag a resource.

        :param resource_arn: The ARN of the resource.
        :param tags: The tags to apply.
        """
        try:
            self.health_imaging_client.tag_resource(resourceArn=resource_arn,
 tags=tags)
        except ClientError as err:
            logger.error(
                "Couldn't tag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Para listar tags para um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
```

```
    )

    medical_imaging_wrapper.list_tags_for_resource(image_set_arn)
```

A função utilitária para listar as tags de um recurso.

```
    def list_tags_for_resource(self, resource_arn):
        """
        List the tags for a resource.

        :param resource_arn: The ARN of the resource.
        :return: The list of tags.
        """
        try:
            tags = self.health_imaging_client.list_tags_for_resource(
                resourceArn=resource_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't list tags for resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return tags["tags"]
```

Para desmarcar um conjunto de imagens

```
    an_image_set_arn = (
        "arn:aws:medical-imaging:us-
east-1:123456789012:datastore/12345678901234567890123456789012/"
        "imageset/12345678901234567890123456789012"
    )

    medical_imaging_wrapper.untag_resource(image_set_arn, ["Deployment"])
```

A função de utilitário para desmarcar um recurso.

```
    def untag_resource(self, resource_arn, tag_keys):
        """
        Untag a resource.

        :param resource_arn: The ARN of the resource.
        :param tag_keys: The tag keys to remove.
        """
        try:
            self.health_imaging_client.untag_resource(
                resourceArn=resource_arn, tagKeys=tag_keys
            )
        except ClientError as err:
            logger.error(
                "Couldn't untag resource. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListTagsForResource
  - TagResource
  - UntagResource

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exemplos de IAM usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Anexar uma política a uma função usando o objeto Policy do Boto3.

```
def attach_to_role(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Policy(policy_arn).attach_role(RoleName=role_name)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
```

```
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise
```

Anexar uma política a uma função usando o objeto Role do Boto3.

```
def attach_policy(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise
```

- Para obter detalhes da API, consulte a AttachRolePolicyReferência da API AWSSDK for Python (Boto3).

Anexar uma política a um usuário

Os exemplos de código a seguir mostram como anexar uma política do IAM a um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def attach_policy(user_name, policy_arn):
    """
    Attaches a policy to a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to user %s.", policy_arn, user_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to user %s.", policy_arn,
 user_name)
        raise
```

- Para obter detalhes da API, consulte a AttachUserPolicyReferência da API AWSSDK for Python (Boto3).

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy(name, description, actions, resource_arn):
    """
    Creates a policy that contains a single statement.

    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a CreatePolicyReferência da API AWSSDK for Python (Boto3).

Criar uma versão de política

O exemplo de código a seguir mostra como criar uma versão de política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy_version(policy_arn, actions, resource_arn, set_as_default):
    """
    Creates a policy version. Policies can have up to five versions. The default
    version is the one that is used for all resources that reference the policy.

    :param policy_arn: The ARN of the policy.
    :param actions: The actions to allow in the policy version.
    :param resource_arn: The ARN of the resource this policy version applies to.
    :param set_as_default: When True, this policy version is set as the default
                           version for the policy. Otherwise, the default
                           is not changed.
    :return: The newly created policy version.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.Policy(policy_arn)
        policy_version = policy.create_version(
            PolicyDocument=json.dumps(policy_doc), SetAsDefault=set_as_default
        )
        logger.info(
            "Created policy version %s for policy %s.",
            policy_version.version_id,
            policy_version.arn,
        )
    except ClientError:
        logger.exception("Couldn't create a policy version for %s.", policy_arn)
        raise
    else:
        return policy_version
```

- Para obter detalhes da API, consulte a CreatePolicyVersionReferência da API AWSSDK for Python (Boto3).

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_role(role_name, allowed_services):
    """
    Creates a role that lets a list of specified services assume the role.

    :param role_name: The name of the role.
    :param allowed_services: The services that can assume the role.
    :return: The newly created role.
    """
    trust_policy = {
        "Version": "2012-10-17",
        "Statement": [
            {
                "Effect": "Allow",
                "Principal": {"Service": service},
                "Action": "sts:AssumeRole",
            }
            for service in allowed_services
        ],
    }

    try:
        role = iam.create_role(
            RoleName=role_name, AssumeRolePolicyDocument=json.dumps(trust_policy)
        )
```

```
        logger.info("Created role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create role %s.", role_name)
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a CreateRoleReferência da API AWSSDK for Python (Boto3).

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_service_linked_role(service_name, description):
    """
    Creates a service-linked role.

    :param service_name: The name of the service that owns the role.
    :param description: A description to give the role.
    :return: The newly created role.
    """
    try:
        response = iam.meta.client.create_service_linked_role(
            AWSServiceName=service_name, Description=description
        )
        role = iam.Role(response["Role"]["RoleName"])
        logger.info("Created service-linked role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create service-linked role for %s.",
 service_name)
```

```
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a CreateServiceLinkedRoleReferência da API AWSSDK for Python (Boto3).

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_user(user_name):
    """
    Creates a user. By default, a user has no permissions or access keys.

    :param user_name: The name of the user.
    :return: The newly created user.
    """
    try:
        user = iam.create_user(UserName=user_name)
        logger.info("Created user %s.", user.name)
    except ClientError:
```

```
        logger.exception("Couldn't create user %s.", user_name)
        raise
    else:
        return user
```

- Para obter detalhes da API, consulte a CreateUserReferência da API AWSSDK for Python (Boto3).

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.

    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
```

```
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair
```

- Para obter detalhes da API, consulte a CreateAccessKeyReferência da API AWSSDK for Python (Boto3).

Criar um alias para uma conta

Os exemplos de código a seguir mostram como criar um alias para uma conta do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_alias(alias):
    """
    Creates an alias for the current account. The alias can be used in place of the
    account ID in the sign-in URL. An account can have only one alias. When a new
    alias is created, it replaces any existing alias.

    :param alias: The alias to assign to the account.
    """

    try:
        iam.create_account_alias(AccountAlias=alias)
        logger.info("Created an alias '%s' for your account.", alias)
    except ClientError:
```

```
        logger.exception("Couldn't create alias '%s' for your account.", alias)
        raise
```

- Para obter detalhes da API, consulte a CreateAccountAliasReferência da API AWSSDK for Python (Boto3).

criar um perfil de instância

O exemplo de código a seguir mostra como criar um perfil de instância do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo cria uma política, um perfil e um perfil de instância e vincula uns aos outros.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
 by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
```

```
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is assumed
by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
```

```
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as AmazonSSMManagedInstanceCore
to grant
                                     use of Systems Manager to send commands to the
instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
```

```
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
 PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
 policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
 role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
 profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to role
 \n"
                    f"{role_name}: {err}"
```

```
                )
        return profile_arn
```

- Para obter detalhes da API, consulte a CreateInstanceProfileReferência da API AWSSDK for Python (Boto3).

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
        raise
```

- Para obter detalhes da API, consulte a DeletePolicyReferência da API AWSSDK for Python (Boto3).

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_role(role_name):
    """
    Deletes a role.

    :param role_name: The name of the role to delete.
    """
    try:
        iam.Role(role_name).delete()
        logger.info("Deleted role %s.", role_name)
    except ClientError:
        logger.exception("Couldn't delete role %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteRoleReferência da API AWSSDK for Python (Boto3).

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_user(user_name):
    """
    Deletes a user. Before a user can be deleted, all associated resources,
    such as access keys and policies, must be deleted or detached.

    :param user_name: The name of the user.
    """
    try:
        iam.User(user_name).delete()
        logger.info("Deleted user %s.", user_name)
    except ClientError:
        logger.exception("Couldn't delete user %s.", user_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteUserReferência da API AWSSDK for Python (Boto3).

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteAccessKeyReferência da API AWSSDK for Python (Boto3).

Excluir um alias de conta

Os exemplos de código a seguir mostram como excluir alias de uma conta do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_alias(alias):
    """
    Removes the alias from the current account.

    :param alias: The alias to remove.
    """
    try:
        iam.meta.client.delete_account_alias(AccountAlias=alias)
        logger.info("Removed alias '%s' from your account.", alias)
    except ClientError:
        logger.exception("Couldn't remove alias '%s' from your account.", alias)
        raise
```

- Para obter detalhes da API, consulte a DeleteAccountAliasReferência da API AWSSDK for Python (Boto3).

Excluir um perfil de instância

O exemplo de código a seguir mostra como excluir um perfil de instância do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo remove o perfil do perfil de instância, separa todas as políticas anexadas ao perfil e exclui todos os recursos.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
```

```
        resource_prefix,
        inst_type,
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
```

```
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )
```

- Para obter detalhes da API, consulte a DeleteInstanceProfileReferência da API AWSSDK for Python (Boto3).

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Desanexar uma política de uma função usando o objeto Policy do Boto3.

```
def detach_from_role(role_name, policy_arn):
    """
    Detaches a policy from a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Policy(policy_arn).detach_role(RoleName=role_name)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise
```

Desanexar uma política de uma função usando o objeto Role do Boto3.

```
def detach_policy(role_name, policy_arn):
    """
    Detaches a policy from a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
```

```
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise
```

- Para obter detalhes da API, consulte a DetachRolePolicyReferência da API AWSSDK for Python (Boto3).

Desanexar uma política de um usuário

Os exemplos de código a seguir mostram como desanexar uma política do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def detach_policy(user_name, policy_arn):
    """
    Detaches a policy from a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from user %s.", policy_arn, user_name)
```

```
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from user %s.", policy_arn, user_name
        )
        raise
```

- Para obter detalhes da API, consulte a DetachUserPolicyReferência da API AWSSDK for Python (Boto3).

Para gerar um relatório de credenciais

O exemplo de código a seguir mostra como gerar um relatório de credenciais do IAM para a conta atual. Depois que o relatório for gerado, obtenha-o usando a GetCredentialReport ação.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def generate_credential_report():
    """
    Starts generation of a credentials report about the current account. After
    calling this function to generate the report, call get_credential_report
    to get the latest report. A new report can be generated a minimum of four hours
    after the last one was generated.
    """
    try:
        response = iam.meta.client.generate_credential_report()
        logger.info(
            "Generating credentials report for your account. " "Current state is
 %s.",
            response["State"],
        )
    except ClientError:
        logger.exception("Couldn't generate a credentials report for your account.")
```

```
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a GenerateCredentialReportReferência da API AWSSDK for Python (Boto3).

Obter um relatório de credenciais

O exemplo de código a seguir mostra como obter o relatório de credenciais gerado mais recentemente no IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_credential_report():
    """
    Gets the most recently generated credentials report about the current account.

    :return: The credentials report.
    """
    try:
        response = iam.meta.client.get_credential_report()
        logger.debug(response["Content"])
    except ClientError:
        logger.exception("Couldn't get credentials report.")
        raise
    else:
        return response["Content"]
```

- Para obter detalhes da API, consulte a GetCredentialReportReferência da API AWSSDK for Python (Boto3).

Obter um relatório de autorização detalhado para a conta

O exemplo de código a seguir mostra como obter um relatório detalhado de autorização do IAM para a conta.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_authorization_details(response_filter):
    """
    Gets an authorization detail report for the current account.

    :param response_filter: A list of resource types to include in the report, such
                            as users or roles. When not specified, all resources
                            are included.
    :return: The authorization detail report.
    """
    try:
        account_details = iam.meta.client.get_account_authorization_details(
            Filter=response_filter
        )
        logger.debug(account_details)
    except ClientError:
        logger.exception("Couldn't get details for your account.")
        raise
    else:
        return account_details
```

- Para obter detalhes da API, consulte a GetAccountAuthorizationDetailsReferência da API AWSSDK for Python (Boto3).

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement
```

- Para obter detalhes da API, consulte a GetPolicyReferência da API AWSSDK for Python (Boto3).

Obter uma versão de política

O código de exemplo a seguir mostra como obter uma versão de política do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement
```

- Para obter detalhes da API, consulte a GetPolicyVersionReferência da API AWSSDK for Python (Boto3).

Obter um perfil

Os exemplos de código a seguir mostram como obter um perfil do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_role(role_name):
    """
    Gets a role by name.

    :param role_name: The name of the role to retrieve.
    :return: The specified role.
    """
    try:
        role = iam.Role(role_name)
        role.load()  # calls GetRole to load attributes
        logger.info("Got role with arn %s.", role.arn)
    except ClientError:
        logger.exception("Couldn't get role named %s.", role_name)
        raise
    else:
        return role
```

- Para obter detalhes da API, consulte a GetRoleReferência da API AWSSDK for Python (Boto3).

Obter um resumo da utilização da conta

O exemplo de código a seguir mostra como obter um resumo da utilização da conta no IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_summary():
    """
    Gets a summary of account usage.

    :return: The summary of account usage.
    """
    try:
        summary = iam.AccountSummary()
        logger.debug(summary.summary_map)
    except ClientError:
        logger.exception("Couldn't get a summary for your account.")
        raise
    else:
        return summary.summary_map
```

- Para obter detalhes da API, consulte a GetAccountSummaryReferência da API AWSSDK for Python (Boto3).

Obter dados sobre a última utilização de uma chave de acesso

O exemplo de código a seguir mostra como obter dados sobre a última utilização de uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_last_use(key_id):
    """
    Gets information about when and how a key was last used.

    :param key_id: The ID of the key to look up.
    :return: Information about the key's last use.
    """
    try:
        response = iam.meta.client.get_access_key_last_used(AccessKeyId=key_id)
        last_used_date = response["AccessKeyLastUsed"].get("LastUsedDate", None)
        last_service = response["AccessKeyLastUsed"].get("ServiceName", None)
        logger.info(
            "Key %s was last used by %s on %s to access %s.",
            key_id,
            response["UserName"],
            last_used_date,
            last_service,
        )
    except ClientError:
        logger.exception("Couldn't get last use of key %s.", key_id)
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a GetAccessKeyLastUsedReferência da API AWSSDK for Python (Boto3).

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def print_password_policy():
    """
    Prints the password policy for the account.
    """
    try:
        pw_policy = iam.AccountPasswordPolicy()
        print("Current account password policy:")
        print(
            f"\tallow_users_to_change_password:
 {pw_policy.allow_users_to_change_password}"
        )
        print(f"\texpire_passwords: {pw_policy.expire_passwords}")
        print(f"\thard_expiry: {pw_policy.hard_expiry}")
        print(f"\tmax_password_age: {pw_policy.max_password_age}")
        print(f"\tminimum_password_length: {pw_policy.minimum_password_length}")
        print(f"\tpassword_reuse_prevention: {pw_policy.password_reuse_prevention}")
        print(
            f"\trequire_lowercase_characters:
 {pw_policy.require_lowercase_characters}"
        )
        print(f"\trequire_numbers: {pw_policy.require_numbers}")
        print(f"\trequire_symbols: {pw_policy.require_symbols}")
        print(
            f"\trequire_uppercase_characters:
 {pw_policy.require_uppercase_characters}"
        )
        printed = True
    except ClientError as error:
        if error.response["Error"]["Code"] == "NoSuchEntity":
            print("The account does not have a password policy set.")
        else:
            logger.exception("Couldn't get account password policy.")
            raise
    else:
```

```
        return printed
```

- Para obter detalhes da API, consulte a GetAccountPasswordPolicyReferência da API AWSSDK for Python (Boto3).

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
def list_saml_providers(count):
    """
    Lists the SAML providers for the account.

    :param count: The maximum number of providers to list.
    """
    try:
        found = 0
        for provider in iam.saml_providers.limit(count):
            logger.info("Got SAML provider %s.", provider.arn)
            found += 1
        if found == 0:
            logger.info("Your account has no SAML providers.")
    except ClientError:
        logger.exception("Couldn't list SAML providers.")
        raise
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Python (Boto3).

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_keys(user_name):
    """
    Lists the keys owned by the specified user.

    :param user_name: The name of the user.
    :return: The list of keys owned by the user.
    """
    try:
        keys = list(iam.User(user_name).access_keys.all())
        logger.info("Got %s access keys for %s.", len(keys), user_name)
    except ClientError:
        logger.exception("Couldn't get access keys for %s.", user_name)
        raise
    else:
        return keys
```

- Para obter detalhes da API, consulte a ListAccessKeysReferência da API AWSSDK for Python (Boto3).

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de uma conta do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_aliases():
    """
    Gets the list of aliases for the current account. An account has at most one
 alias.

    :return: The list of aliases for the account.
    """
    try:
        response = iam.meta.client.list_account_aliases()
        aliases = response["AccountAliases"]
        if len(aliases) > 0:
            logger.info("Got aliases for your account: %s.", ",".join(aliases))
        else:
            logger.info("Got no aliases for your account.")
    except ClientError:
        logger.exception("Couldn't list aliases for your account.")
        raise
    else:
        return response["AccountAliases"]
```

- Para obter detalhes da API, consulte a ListAccountAliasesReferência da API AWSSDK for Python (Boto3).

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_groups(count):
    """
    Lists the specified number of groups for the account.

    :param count: The number of groups to list.
    """
    try:
        for group in iam.groups.limit(count):
            logger.info("Group: %s", group.name)
    except ClientError:
        logger.exception("Couldn't list groups for the account.")
        raise
```

- Para obter detalhes da API, consulte a ListGroupsReferência da API AWSSDK for Python (Boto3).

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(role_name):
    """
    Lists inline policies for a role.

    :param role_name: The name of the role to query.
    """
    try:
        role = iam.Role(role_name)
        for policy in role.policies.all():
            logger.info("Got inline policy %s.", policy.name)
    except ClientError:
        logger.exception("Couldn't list inline policies for %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a ListRolePoliciesReferência da API AWSSDK for Python (Boto3).

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(scope):
    """
    Lists the policies in the current account.

    :param scope: Limits the kinds of policies that are returned. For example,
                  'Local' specifies that only locally managed policies are returned.
    :return: The list of policies.
    """
    try:
        policies = list(iam.policies.filter(Scope=scope))
        logger.info("Got %s policies in scope '%s'.", len(policies), scope)
    except ClientError:
        logger.exception("Couldn't get policies for scope '%s'.", scope)
        raise
    else:
        return policies
```

- Para obter detalhes da API, consulte a ListPoliciesReferência da API AWSSDK for Python (Boto3).

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas anexadas a um perfil do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_attached_policies(role_name):
    """
    Lists policies attached to a role.

    :param role_name: The name of the role to query.
    """
```

```
    try:
        role = iam.Role(role_name)
        for policy in role.attached_policies.all():
            logger.info("Got policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't list attached policies for %s.", role_name)
        raise
```

- Para obter detalhes da API, consulte a ListAttachedRolePoliciesReferência da API AWSSDK for Python (Boto3).

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_roles(count):
    """
    Lists the specified number of roles for the account.

    :param count: The number of roles to list.
    """
    try:
        roles = list(iam.roles.limit(count=count))
        for role in roles:
            logger.info("Role: %s", role.name)
    except ClientError:
        logger.exception("Couldn't list roles for the account.")
        raise
    else:
        return roles
```

- Para obter detalhes da API, consulte a ListRolesReferência da API AWSSDK for Python (Boto3).

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_users():
    """
    Lists the users in the current account.

    :return: The list of users.
    """
    try:
        users = list(iam.users.all())
        logger.info("Got %s users.", len(users))
    except ClientError:
        logger.exception("Couldn't get users.")
        raise
    else:
        return users
```

- Para obter detalhes da API, consulte a ListUsersReferência da API AWSSDK for Python (Boto3).

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_user(user_name, new_user_name):
    """
    Updates a user's name.

    :param user_name: The current name of the user to update.
    :param new_user_name: The new name to assign to the user.
    :return: The updated user.
    """
    try:
        user = iam.User(user_name)
        user.update(NewUserName=new_user_name)
        logger.info("Renamed %s to %s.", user_name, new_user_name)
    except ClientError:
        logger.exception("Couldn't update name for user %s.", user_name)
```

```
        raise
    return user
```

- Para obter detalhes da API, consulte a UpdateUserReferência da API AWSSDK for Python (Boto3).

Atualizar uma chave de acesso

O exemplo de código a seguir mostra como atualizar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_key(user_name, key_id, activate):
    """
    Updates the status of a key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to update.
    :param activate: When True, the key is activated. Otherwise, the key is
 deactivated.
    """

    try:
        key = iam.User(user_name).AccessKey(key_id)
```

```
        if activate:
            key.activate()
        else:
            key.deactivate()
        logger.info("%s key %s.", "Activated" if activate else "Deactivated",
key_id)
    except ClientError:
        logger.exception(
            "Couldn't %s key %s.", "Activate" if activate else "Deactivate", key_id
        )
        raise
```

- Para obter detalhes da API, consulte a UpdateAccessKeyReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e gerenciar um serviço resiliente

O exemplo de código a seguir mostra como criar um serviço web com balanceamento de carga que retorna recomendações de livros, filmes e músicas. O exemplo mostra como o serviço responde a falhas e como é possível reestruturá-lo para gerar mais resiliência em caso de falhas.

- Use um grupo do Amazon EC2 Auto Scaling para criar instâncias do Amazon Elastic Compute Cloud (Amazon EC2) com base em um modelo de execução e para manter o número de instâncias em um intervalo especificado.
- Gerencie e distribua solicitações HTTP com o Elastic Load Balancing.
- Monitore a integridade das instâncias em um grupo do Auto Scaling e encaminhe solicitações somente para instâncias íntegras.
- Execute um servidor Web Python em cada instância do EC2 para lidar com solicitações HTTP. O servidor Web responde com recomendações e verificações de integridade.
- Simule um serviço de recomendação com uma tabela do Amazon DynamoDB.
- Controle a resposta do servidor Web às solicitações e verificações de integridade atualizando os parâmetros do AWS Systems Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute o cenário interativo em um prompt de comando.

```
class Runner:
    def __init__(
        self, resource_path, recommendation, autoscaler, loadbalancer, param_helper
    ):
        self.resource_path = resource_path
        self.recommendation = recommendation
        self.autoscaler = autoscaler
        self.loadbalancer = loadbalancer
        self.param_helper = param_helper
        self.protocol = "HTTP"
        self.port = 80
        self.ssh_port = 22

    def deploy(self):
        recommendations_path = f"{self.resource_path}/recommendations.json"
        startup_script = f"{self.resource_path}/server_startup_script.sh"
        instance_policy = f"{self.resource_path}/instance_policy.json"

        print(
            "\nFor this demo, we'll use the AWS SDK for Python (Boto3) to create
 several AWS resources\n"
            "to set up a load-balanced web service endpoint and explore some ways to
 make it resilient\n"
            "against various kinds of failures.\n\n"
            "Some of the resources create by this demo are:\n"
        )
        print(
            "\t* A DynamoDB table that the web service depends on to provide book,
 movie, and song recommendations."
        )
        print(
            "\t* An EC2 launch template that defines EC2 instances that each contain
 a Python web server."
```

```
        )
        print(
            "\t* An EC2 Auto Scaling group that manages EC2 instances across several
 Availability Zones."
        )
        print(
            "\t* An Elastic Load Balancing (ELB) load balancer that targets the Auto
 Scaling group to distribute requests."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to start deploying resources.")

        print(
            f"Creating and populating a DynamoDB table named
 '{self.recommendation.table_name}'."
        )
        self.recommendation.create()
        self.recommendation.populate(recommendations_path)
        print("-" * 88)

        print(
            f"Creating an EC2 launch template that runs '{startup_script}' when an
 instance starts.\n"
            f"This script starts a Python web server defined in the `server.py`
 script. The web server\n"
            f"listens to HTTP requests on port 80 and responds to requests to '/'
 and to '/healthcheck'.\n"
            f"For demo purposes, this server is run as the root user. In production,
 the best practice is to\n"
            f"run a web server, such as Apache, with least-privileged credentials.
\n"
        )
        print(
            f"The template also defines an IAM policy that each instance uses to
 assume a role that grants\n"
            f"permissions to access the DynamoDB recommendation table and Systems
 Manager parameters\n"
            f"that control the flow of the demo.\n"
        )
        self.autoscaler.create_template(startup_script, instance_policy)
        print("-" * 88)

        print(
```

```
            f"Creating an EC2 Auto Scaling group that maintains three EC2 instances,
each in a different\n"
            f"Availability Zone."
        )
        zones = self.autoscaler.create_group(3)
        print("-" * 88)
        print(
            "At this point, you have EC2 instances created. Once each instance
starts, it listens for\n"
            "HTTP requests. You can see these instances in the console or continue
with the demo."
        )
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue.")

        print(f"Creating variables that control the flow of the demo.\n")
        self.param_helper.reset()

        print(
            "\nCreating an Elastic Load Balancing target group and load balancer.
The target group\n"
            "defines how the load balancer connects to instances. The load balancer
provides a\n"
            "single endpoint where clients connect and dispatches requests to
instances in the group.\n"
        )
        vpc = self.autoscaler.get_default_vpc()
        subnets = self.autoscaler.get_subnets(vpc["VpcId"], zones)
        target_group = self.loadbalancer.create_target_group(
            self.protocol, self.port, vpc["VpcId"]
        )
        self.loadbalancer.create_load_balancer(
            [subnet["SubnetId"] for subnet in subnets], target_group
        )
        self.autoscaler.attach_load_balancer_target_group(target_group)
        print(f"Verifying access to the load balancer endpoint...")
        lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if not lb_success:
            print(
                "Couldn't connect to the load balancer, verifying that the port is
open..."
            )
            current_ip_address = requests.get(
                "http://checkip.amazonaws.com"
```

```
            ).text.strip()
            sec_group, port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.port, current_ip_address
            )
            sec_group, ssh_port_is_open = self.autoscaler.verify_inbound_port(
                vpc, self.ssh_port, current_ip_address
            )
            if not port_is_open:
                print(
                    "For this example to work, the default security group for your
default VPC must\n"
                    "allows access from this computer. You can either add it
automatically from this\n"
                    "example or add it yourself using the AWS Management Console.\n"
                )
                if q.ask(
                    f"Do you want to add a rule to security group
{sec_group['GroupId']} to allow\n"
                    f"inbound traffic on port {self.port} from your computer's IP
address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.port, current_ip_address
                    )
            if not ssh_port_is_open:
                if q.ask(
                    f"Do you want to add a rule to security group
{sec_group['GroupId']} to allow\n"
                    f"inbound SSH traffic on port {self.ssh_port} for debugging from
your computer's IP address of {current_ip_address}? (y/n) ",
                    q.is_yesno,
                ):
                    self.autoscaler.open_inbound_port(
                        sec_group["GroupId"], self.ssh_port, current_ip_address
                    )
            lb_success = self.loadbalancer.verify_load_balancer_endpoint()
        if lb_success:
            print("Your load balancer is ready. You can access it by browsing to:
\n")
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        else:
            print(
```

```
                "Couldn't get a successful response from the load balancer endpoint.
Troubleshoot by\n"
                "manually verifying that your VPC and security group are configured
correctly and that\n"
                "you can successfully make a GET request to the load balancer
endpoint:\n"
            )
            print(f"\thttp://{self.loadbalancer.endpoint()}\n")
        print("-" * 88)
        q.ask("Press Enter when you're ready to continue with the demo.")

    def demo_choices(self):
        actions = [
            "Send a GET request to the load balancer endpoint.",
            "Check the health of load balancer targets.",
            "Go to the next part of the demo.",
        ]
        choice = 0
        while choice != 2:
            print("-" * 88)
            print(
                "\nSee the current state of the service by selecting one of the
following choices:\n"
            )
            choice = q.choose("\nWhich action would you like to take? ", actions)
            print("-" * 88)
            if choice == 0:
                print("Request:\n")
                print(f"GET http://{self.loadbalancer.endpoint()}")
                response = requests.get(f"http://{self.loadbalancer.endpoint()}")
                print("\nResponse:\n")
                print(f"{response.status_code}")
                if response.headers.get("content-type") == "application/json":
                    pp(response.json())
            elif choice == 1:
                print("\nChecking the health of load balancer targets:\n")
                health = self.loadbalancer.check_target_health()
                for target in health:
                    state = target["TargetHealth"]["State"]
                    print(
                        f"\tTarget {target['Target']['Id']} on port
{target['Target']['Port']} is {state}"
                    )
                    if state != "healthy":
```

```
                        print(
                            f"\t\t{target['TargetHealth']['Reason']}:
{target['TargetHealth']['Description']}\n"
                        )
                print(
                    f"\nNote that it can take a minute or two for the health check
to update\n"
                    f"after changes are made.\n"
                )
            elif choice == 2:
                print("\nOkay, let's move on.")
                print("-" * 88)

    def demo(self):
        ssm_only_policy = f"{self.resource_path}/ssm_only_policy.json"

        print("\nResetting parameters to starting values for demo.\n")
        self.param_helper.reset()

        print(
            "\nThis part of the demonstration shows how to toggle different parts of
the system\n"
            "to create situations where the web service fails, and shows how using a
resilient\n"
            "architecture can keep the web service running in spite of these
failures."
        )
        print("-" * 88)

        print(
            "At the start, the load balancer endpoint returns recommendations and
reports that all targets are healthy."
        )
        self.demo_choices()

        print(
            f"The web service running on the EC2 instances gets recommendations by
querying a DynamoDB table.\n"
            f"The table name is contained in a Systems Manager parameter named
'{self.param_helper.table}'.\n"
            f"To simulate a failure of the recommendation service, let's set this
parameter to name a non-existent table.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
```

```
        print(
            "\nNow, sending a GET request to the load balancer endpoint returns a
failure code. But, the service reports as\n"
            "healthy to the load balancer because shallow health checks don't check
for failure of the recommendation service."
        )
        self.demo_choices()

        print(
            f"Instead of failing when the recommendation service fails, the web
service can return a static response.\n"
            f"While this is not a perfect solution, it presents the customer with a
somewhat better experience than failure.\n"
        )
        self.param_helper.put(self.param_helper.failure_response, "static")
        print(
            f"\nNow, sending a GET request to the load balancer endpoint returns a
static response.\n"
            f"The service still reports as healthy because health checks are still
shallow.\n"
        )
        self.demo_choices()

        print("Let's reinstate the recommendation service.\n")
        self.param_helper.put(self.param_helper.table,
self.recommendation.table_name)
        print(
            "\nLet's also substitute bad credentials for one of the instances in the
target group so that it can't\n"
            "access the DynamoDB recommendation table.\n"
        )
        self.autoscaler.create_instance_profile(
            ssm_only_policy,
            self.autoscaler.bad_creds_policy_name,
            self.autoscaler.bad_creds_role_name,
            self.autoscaler.bad_creds_profile_name,
            ["AmazonSSMManagedInstanceCore"],
        )
        instances = self.autoscaler.get_instances()
        bad_instance_id = instances[0]
        instance_profile = self.autoscaler.get_instance_profile(bad_instance_id)
        print(
            f"\nReplacing the profile for instance {bad_instance_id} with a profile
that contains\n"
```

```
            f"bad credentials...\n"
        )
        self.autoscaler.replace_instance_profile(
            bad_instance_id,
            self.autoscaler.bad_creds_profile_name,
            instance_profile["AssociationId"],
        )
        print(
            "Now, sending a GET request to the load balancer endpoint returns either
a recommendation or a static response,\n"
            "depending on which instance is selected by the load balancer.\n"
        )
        self.demo_choices()

        print(
            "\nLet's implement a deep health check. For this demo, a deep health
check tests whether\n"
            "the web service can access the DynamoDB table that it depends on for
recommendations. Note that\n"
            "the deep health check is only for ELB routing and not for Auto Scaling
instance health.\n"
            "This kind of deep health check is not recommended for Auto Scaling
instance health, because it\n"
            "risks accidental termination of all instances in the Auto Scaling group
when a dependent service fails.\n"
        )
        print(
            "By implementing deep health checks, the load balancer can detect when
one of the instances is failing\n"
            "and take that instance out of rotation.\n"
        )
        self.param_helper.put(self.param_helper.health_check, "deep")
        print(
            f"\nNow, checking target health indicates that the instance with bad
credentials ({bad_instance_id})\n"
            f"is unhealthy. Note that it might take a minute or two for the load
balancer to detect the unhealthy \n"
            f"instance. Sending a GET request to the load balancer endpoint always
returns a recommendation, because\n"
            "the load balancer takes unhealthy instances out of its rotation.\n"
        )
        self.demo_choices()

        print(
```

```
            "\nBecause the instances in this demo are controlled by an auto scaler,
 the simplest way to fix an unhealthy\n"
            "instance is to terminate it and let the auto scaler start a new
 instance to replace it.\n"
        )
        self.autoscaler.terminate_instance(bad_instance_id)
        print(
            "\nEven while the instance is terminating and the new instance is
 starting, sending a GET\n"
            "request to the web service continues to get a successful recommendation
 response because\n"
            "the load balancer routes requests to the healthy instances. After the
 replacement instance\n"
            "starts and reports as healthy, it is included in the load balancing
 rotation.\n"
            "\nNote that terminating and replacing an instance typically takes
 several minutes, during which time you\n"
            "can see the changing health check status until the new instance is
 running and healthy.\n"
        )
        self.demo_choices()

        print(
            "\nIf the recommendation service fails now, deep health checks mean all
 instances report as unhealthy.\n"
        )
        self.param_helper.put(self.param_helper.table, "this-is-not-a-table")
        print(
            "\nWhen all instances are unhealthy, the load balancer continues to
 route requests even to\n"
            "unhealthy instances, allowing them to fail open and return a static
 response rather than fail\n"
            "closed and report failure to the customer."
        )
        self.demo_choices()
        self.param_helper.reset()

    def destroy(self):
        print(
            "This concludes the demo of how to build and manage a resilient service.
\n"
            "To keep things tidy and to avoid unwanted charges on your account, we
 can clean up all AWS resources\n"
            "that were created for this demo."
```

```
        )
        if q.ask("Do you want to clean up all demo resources? (y/n) ", q.is_yesno):
            self.loadbalancer.delete_load_balancer()
            self.loadbalancer.delete_target_group()
            self.autoscaler.delete_group()
            self.autoscaler.delete_key_pair()
            self.autoscaler.delete_template()
            self.autoscaler.delete_instance_profile(
                self.autoscaler.bad_creds_profile_name,
                self.autoscaler.bad_creds_role_name,
            )
            self.recommendation.destroy()
        else:
            print(
                "Okay, we'll leave the resources intact.\n"
                "Don't forget to delete them when you're done with them or you might
 incur unexpected charges."
            )


def main():
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--action",
        required=True,
        choices=["all", "deploy", "demo", "destroy"],
        help="The action to take for the demo. When 'all' is specified, resources
 are\n"
        "deployed, the demo is run, and resources are destroyed.",
    )
    parser.add_argument(
        "--resource_path",
        default="../../../workflows/resilient_service/resources",
        help="The path to resource files used by this example, such as IAM policies
 and\n"
        "instance scripts.",
    )
    args = parser.parse_args()

    print("-" * 88)
    print(
        "Welcome to the demonstration of How to Build and Manage a Resilient
 Service!"
    )
```

```
    print("-" * 88)

    prefix = "doc-example-resilience"
    recommendation = RecommendationService.from_client(
        "doc-example-recommendation-service"
    )
    autoscaler = AutoScaler.from_client(prefix)
    loadbalancer = LoadBalancer.from_client(prefix)
    param_helper = ParameterHelper.from_client(recommendation.table_name)
    runner = Runner(
        args.resource_path, recommendation, autoscaler, loadbalancer, param_helper
    )
    actions = [args.action] if args.action != "all" else ["deploy", "demo",
 "destroy"]
    for action in actions:
        if action == "deploy":
            runner.deploy()
        elif action == "demo":
            runner.demo()
        elif action == "destroy":
            runner.destroy()

    print("-" * 88)
    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    main()
```

Crie uma classe que envolva as ações do Auto Scaling e do Amazon EC2.

```
class AutoScaler:
    """
    Encapsulates Amazon EC2 Auto Scaling and EC2 management actions.
    """

    def __init__(
        self,
        resource_prefix,
        inst_type,
```

```
        ami_param,
        autoscaling_client,
        ec2_client,
        ssm_client,
        iam_client,
    ):
        """
        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        :param inst_type: The type of EC2 instance to create, such as t3.micro.
        :param ami_param: The Systems Manager parameter used to look up the AMI that
is
                          created.
        :param autoscaling_client: A Boto3 EC2 Auto Scaling client.
        :param ec2_client: A Boto3 EC2 client.
        :param ssm_client: A Boto3 Systems Manager client.
        :param iam_client: A Boto3 IAM client.
        """
        self.inst_type = inst_type
        self.ami_param = ami_param
        self.autoscaling_client = autoscaling_client
        self.ec2_client = ec2_client
        self.ssm_client = ssm_client
        self.iam_client = iam_client
        self.launch_template_name = f"{resource_prefix}-template"
        self.group_name = f"{resource_prefix}-group"
        self.instance_policy_name = f"{resource_prefix}-pol"
        self.instance_role_name = f"{resource_prefix}-role"
        self.instance_profile_name = f"{resource_prefix}-prof"
        self.bad_creds_policy_name = f"{resource_prefix}-bc-pol"
        self.bad_creds_role_name = f"{resource_prefix}-bc-role"
        self.bad_creds_profile_name = f"{resource_prefix}-bc-prof"
        self.key_pair_name = f"{resource_prefix}-key-pair"


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from Boto3 clients.

        :param resource_prefix: The prefix for naming AWS resources that are created
by this class.
        """
        as_client = boto3.client("autoscaling")
```

```
        ec2_client = boto3.client("ec2")
        ssm_client = boto3.client("ssm")
        iam_client = boto3.client("iam")
        return cls(
            resource_prefix,
            "t3.micro",
            "/aws/service/ami-amazon-linux-latest/amzn2-ami-hvm-x86_64-gp2",
            as_client,
            ec2_client,
            ssm_client,
            iam_client,
        )

    def create_instance_profile(
        self, policy_file, policy_name, role_name, profile_name,
aws_managed_policies=()
    ):
        """
        Creates a policy, role, and profile that is associated with instances
created by
        this class. An instance's associated profile defines a role that is assumed
by the
        instance. The role has attached policies that specify the AWS permissions
granted to
        clients that run on the instance.

        :param policy_file: The name of a JSON file that contains the policy
definition to
                            create and attach to the role.
        :param policy_name: The name to give the created policy.
        :param role_name: The name to give the created role.
        :param profile_name: The name to the created profile.
        :param aws_managed_policies: Additional AWS-managed policies that are
attached to
                                     the role, such as AmazonSSMManagedInstanceCore
to grant
                                     use of Systems Manager to send commands to the
instance.
        :return: The ARN of the profile that is created.
        """
        assume_role_doc = {
            "Version": "2012-10-17",
            "Statement": [
                {
```

```
                    "Effect": "Allow",
                    "Principal": {"Service": "ec2.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        with open(policy_file) as file:
            instance_policy_doc = file.read()

        policy_arn = None
        try:
            pol_response = self.iam_client.create_policy(
                PolicyName=policy_name, PolicyDocument=instance_policy_doc
            )
            policy_arn = pol_response["Policy"]["Arn"]
            log.info("Created policy with ARN %s.", policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                log.info("Policy %s already exists, nothing to do.", policy_name)
                list_pol_response = self.iam_client.list_policies(Scope="Local")
                for pol in list_pol_response["Policies"]:
                    if pol["PolicyName"] == policy_name:
                        policy_arn = pol["Arn"]
                        break
            if policy_arn is None:
                raise AutoScalerError(f"Couldn't create policy {policy_name}:
{err}")

        try:
            self.iam_client.create_role(
                RoleName=role_name,
AssumeRolePolicyDocument=json.dumps(assume_role_doc)
            )
            self.iam_client.attach_role_policy(RoleName=role_name,
PolicyArn=policy_arn)
            for aws_policy in aws_managed_policies:
                self.iam_client.attach_role_policy(
                    RoleName=role_name,
                    PolicyArn=f"arn:aws:iam::aws:policy/{aws_policy}",
                )
            log.info("Created role %s and attached policy %s.", role_name,
policy_arn)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                log.info("Role %s already exists, nothing to do.", role_name)
            else:
                raise AutoScalerError(f"Couldn't create role {role_name}: {err}")

        try:
            profile_response = self.iam_client.create_instance_profile(
                InstanceProfileName=profile_name
            )
            waiter = self.iam_client.get_waiter("instance_profile_exists")
            waiter.wait(InstanceProfileName=profile_name)
            time.sleep(10)  # wait a little longer
            profile_arn = profile_response["InstanceProfile"]["Arn"]
            self.iam_client.add_role_to_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )
            log.info("Created profile %s and added role %s.", profile_name,
 role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "EntityAlreadyExists":
                prof_response = self.iam_client.get_instance_profile(
                    InstanceProfileName=profile_name
                )
                profile_arn = prof_response["InstanceProfile"]["Arn"]
                log.info(
                    "Instance profile %s already exists, nothing to do.",
 profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create profile {profile_name} and attach it to role
\n"
                    f"{role_name}: {err}"
                )
        return profile_arn


    def get_instance_profile(self, instance_id):
        """
        Gets data about the profile associated with an instance.

        :param instance_id: The ID of the instance to look up.
        :return: The profile data.
        """
        try:
```

```
            response = self.ec2_client.describe_iam_instance_profile_associations(
                Filters=[{"Name": "instance-id", "Values": [instance_id]}]
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instance profile association for instance
{instance_id}: {err}"
            )
        else:
            return response["IamInstanceProfileAssociations"][0]


    def replace_instance_profile(
        self, instance_id, new_instance_profile_name, profile_association_id
    ):
        """
        Replaces the profile associated with a running instance. After the profile
is
        replaced, the instance is rebooted to ensure that it uses the new profile.
When
        the instance is ready, Systems Manager is used to restart the Python web
server.

        :param instance_id: The ID of the instance to update.
        :param new_instance_profile_name: The name of the new profile to associate
with
                                          the specified instance.
        :param profile_association_id: The ID of the existing profile association
for the
                                       instance.
        """
        try:
            self.ec2_client.replace_iam_instance_profile_association(
                IamInstanceProfile={"Name": new_instance_profile_name},
                AssociationId=profile_association_id,
            )
            log.info(
                "Replaced instance profile for association %s with profile %s.",
                profile_association_id,
                new_instance_profile_name,
            )
            time.sleep(5)
            inst_ready = False
            tries = 0
```

```
            while not inst_ready:
                if tries % 6 == 0:
                    self.ec2_client.reboot_instances(InstanceIds=[instance_id])
                    log.info(
                        "Rebooting instance %s and waiting for it to to be ready.",
                        instance_id,
                    )
                tries += 1
                time.sleep(10)
                response = self.ssm_client.describe_instance_information()
                for info in response["InstanceInformationList"]:
                    if info["InstanceId"] == instance_id:
                        inst_ready = True
            self.ssm_client.send_command(
                InstanceIds=[instance_id],
                DocumentName="AWS-RunShellScript",
                Parameters={"commands": ["cd / && sudo python3 server.py 80"]},
            )
            log.info("Restarted the Python web server on instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't replace instance profile for association
{profile_association_id}: {err}"
            )


    def delete_instance_profile(self, profile_name, role_name):
        """
        Detaches a role from an instance profile, detaches policies from the role,
        and deletes all the resources.

        :param profile_name: The name of the profile to delete.
        :param role_name: The name of the role to delete.
        """
        try:
            self.iam_client.remove_role_from_instance_profile(
                InstanceProfileName=profile_name, RoleName=role_name
            )

self.iam_client.delete_instance_profile(InstanceProfileName=profile_name)
            log.info("Deleted instance profile %s.", profile_name)
            attached_policies = self.iam_client.list_attached_role_policies(
                RoleName=role_name
            )
```

```
            for pol in attached_policies["AttachedPolicies"]:
                self.iam_client.detach_role_policy(
                    RoleName=role_name, PolicyArn=pol["PolicyArn"]
                )
                if not pol["PolicyArn"].startswith("arn:aws:iam::aws"):
                    self.iam_client.delete_policy(PolicyArn=pol["PolicyArn"])
                log.info("Detached and deleted policy %s.", pol["PolicyName"])
            self.iam_client.delete_role(RoleName=role_name)
            log.info("Deleted role %s.", role_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                log.info(
                    "Instance profile %s doesn't exist, nothing to do.",
profile_name
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete instance profile {profile_name} or detach "
                    f"policies and delete role {role_name}: {err}"
                )


    def create_key_pair(self, key_pair_name):
        """
        Creates a new key pair.

        :param key_pair_name: The name of the key pair to create.
        :return: The newly created key pair.
        """
        try:
            response = self.ec2_client.create_key_pair(KeyName=key_pair_name)
            with open(f"{key_pair_name}.pem", "w") as file:
                file.write(response["KeyMaterial"])
            chmod(f"{key_pair_name}.pem", 0o600)
            log.info("Created key pair %s.", key_pair_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't create key pair {key_pair_name}:
{err}")


    def delete_key_pair(self):
        """
        Deletes a key pair.
```

```
        :param key_pair_name: The name of the key pair to delete.
        """
        try:
            self.ec2_client.delete_key_pair(KeyName=self.key_pair_name)
            remove(f"{self.key_pair_name}.pem")
            log.info("Deleted key pair %s.", self.key_pair_name)
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )
        except FileNotFoundError:
            log.info("Key pair %s doesn't exist, nothing to do.",
self.key_pair_name)
        except PermissionError:
            log.info(
                "Inadequate permissions to delete key pair %s.", self.key_pair_name
            )
        except Exception as err:
            raise AutoScalerError(
                f"Couldn't delete key pair {self.key_pair_name}: {err}"
            )


    def create_template(self, server_startup_script_file, instance_policy_file):
        """
        Creates an Amazon EC2 launch template to use with Amazon EC2 Auto Scaling.
The
        launch template specifies a Bash script in its user data field that runs
after
        the instance is started. This script installs Python packages and starts a
        Python web server on the instance.

        :param server_startup_script_file: The path to a Bash script file that is
run
                                           when an instance starts.
        :param instance_policy_file: The path to a file that defines a permissions
policy
                                     to create and attach to the instance profile.
        :return: Information about the newly created template.
        """
        template = {}
        try:
            self.create_key_pair(self.key_pair_name)
            self.create_instance_profile(
```

```
                instance_policy_file,
                self.instance_policy_name,
                self.instance_role_name,
                self.instance_profile_name,
            )
            with open(server_startup_script_file) as file:
                start_server_script = file.read()
            ami_latest = self.ssm_client.get_parameter(Name=self.ami_param)
            ami_id = ami_latest["Parameter"]["Value"]
            lt_response = self.ec2_client.create_launch_template(
                LaunchTemplateName=self.launch_template_name,
                LaunchTemplateData={
                    "InstanceType": self.inst_type,
                    "ImageId": ami_id,
                    "IamInstanceProfile": {"Name": self.instance_profile_name},
                    "UserData": base64.b64encode(
                        start_server_script.encode(encoding="utf-8")
                    ).decode(encoding="utf-8"),
                    "KeyName": self.key_pair_name,
                },
            )
            template = lt_response["LaunchTemplate"]
            log.info(
                "Created launch template %s for AMI %s on %s.",
                self.launch_template_name,
                ami_id,
                self.inst_type,
            )
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.AlreadyExistsException"
            ):
                log.info(
                    "Launch template %s already exists, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create launch template {self.launch_template_name}:
{err}."
                )
        return template
```

```
    def delete_template(self):
        """
        Deletes a launch template.
        """
        try:
            self.ec2_client.delete_launch_template(
                LaunchTemplateName=self.launch_template_name
            )
            self.delete_instance_profile(
                self.instance_profile_name, self.instance_role_name
            )
            log.info("Launch template %s deleted.", self.launch_template_name)
        except ClientError as err:
            if (
                err.response["Error"]["Code"]
                == "InvalidLaunchTemplateName.NotFoundException"
            ):
                log.info(
                    "Launch template %s does not exist, nothing to do.",
                    self.launch_template_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't delete launch template {self.launch_template_name}:
{err}."
                )


    def get_availability_zones(self):
        """
        Gets a list of Availability Zones in the AWS Region of the Amazon EC2
client.

        :return: The list of Availability Zones for the client Region.
        """
        try:
            response = self.ec2_client.describe_availability_zones()
            zones = [zone["ZoneName"] for zone in response["AvailabilityZones"]]
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get availability zones: {err}.")
        else:
            return zones
```

```
    def create_group(self, group_size):
        """
        Creates an EC2 Auto Scaling group with the specified size.

        :param group_size: The number of instances to set for the minimum and
maximum in
                           the group.
        :return: The list of Availability Zones specified for the group.
        """
        zones = []
        try:
            zones = self.get_availability_zones()
            self.autoscaling_client.create_auto_scaling_group(
                AutoScalingGroupName=self.group_name,
                AvailabilityZones=zones,
                LaunchTemplate={
                    "LaunchTemplateName": self.launch_template_name,
                    "Version": "$Default",
                },
                MinSize=group_size,
                MaxSize=group_size,
            )
            log.info(
                "Created EC2 Auto Scaling group %s with availability zones %s.",
                self.launch_template_name,
                zones,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "AlreadyExists":
                log.info(
                    "EC2 Auto Scaling group %s already exists, nothing to do.",
                    self.group_name,
                )
            else:
                raise AutoScalerError(
                    f"Couldn't create EC2 Auto Scaling group {self.group_name}:
{err}"
                )
        return zones


    def get_instances(self):
        """
```

```
        Gets data about the instances in the EC2 Auto Scaling group.

        :return: Data about the instances.
        """
        try:
            as_response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            instance_ids = [
                i["InstanceId"]
                for i in as_response["AutoScalingGroups"][0]["Instances"]
            ]
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't get instances for Auto Scaling group {self.group_name}:
{err}"
            )
        else:
            return instance_ids


    def terminate_instance(self, instance_id):
        """
        Terminates and instances in an EC2 Auto Scaling group. After an instance is
        terminated, it can no longer be accessed.

        :param instance_id: The ID of the instance to terminate.
        """
        try:
            self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                InstanceId=instance_id, ShouldDecrementDesiredCapacity=False
            )
            log.info("Terminated instance %s.", instance_id)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't terminate instance {instance_id}:
{err}")

    def attach_load_balancer_target_group(self, lb_target_group):
        """
        Attaches an Elastic Load Balancing (ELB) target group to this EC2 Auto
Scaling group.
        The target group specifies how the load balancer forward requests to the
instances
        in the group.
```

```
        :param lb_target_group: Data about the ELB target group to attach.
        """
        try:
            self.autoscaling_client.attach_load_balancer_target_groups(
                AutoScalingGroupName=self.group_name,
                TargetGroupARNs=[lb_target_group["TargetGroupArn"]],
            )
            log.info(
                "Attached load balancer target group %s to auto scaling group %s.",
                lb_target_group["TargetGroupName"],
                self.group_name,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't attach load balancer target group
{lb_target_group['TargetGroupName']}\n"
                f"to auto scaling group {self.group_name}"
            )


    def _try_terminate_instance(self, inst_id):
        stopping = False
        log.info(f"Stopping {inst_id}.")
        while not stopping:
            try:
                self.autoscaling_client.terminate_instance_in_auto_scaling_group(
                    InstanceId=inst_id, ShouldDecrementDesiredCapacity=True
                )
                stopping = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "ScalingActivityInProgress":
                    log.info("Scaling activity in progress for %s. Waiting...",
inst_id)
                    time.sleep(10)
                else:
                    raise AutoScalerError(f"Couldn't stop instance {inst_id}:
{err}.")

    def _try_delete_group(self):
        """
        Tries to delete the EC2 Auto Scaling group. If the group is in use or in
progress,
        the function waits and retries until the group is successfully deleted.
```

```
        """
        stopped = False
        while not stopped:
            try:
                self.autoscaling_client.delete_auto_scaling_group(
                    AutoScalingGroupName=self.group_name
                )
                stopped = True
                log.info("Deleted EC2 Auto Scaling group %s.", self.group_name)
            except ClientError as err:
                if (
                    err.response["Error"]["Code"] == "ResourceInUse"
                    or err.response["Error"]["Code"] == "ScalingActivityInProgress"
                ):
                    log.info(
                        "Some instances are still running. Waiting for them to
 stop..."
                    )
                    time.sleep(10)
                else:
                    raise AutoScalerError(
                        f"Couldn't delete group {self.group_name}: {err}."
                    )

    def delete_group(self):
        """
        Terminates all instances in the group, deletes the EC2 Auto Scaling group.
        """
        try:
            response = self.autoscaling_client.describe_auto_scaling_groups(
                AutoScalingGroupNames=[self.group_name]
            )
            groups = response.get("AutoScalingGroups", [])
            if len(groups) > 0:
                self.autoscaling_client.update_auto_scaling_group(
                    AutoScalingGroupName=self.group_name, MinSize=0
                )
                instance_ids = [inst["InstanceId"] for inst in groups[0]
["Instances"]]
                for inst_id in instance_ids:
                    self._try_terminate_instance(inst_id)
                self._try_delete_group()
            else:
```

```
                log.info("No groups found named %s, nothing to do.",
self.group_name)
        except ClientError as err:
            raise AutoScalerError(f"Couldn't delete group {self.group_name}:
{err}.")


    def get_default_vpc(self):
        """
        Gets the default VPC for the account.

        :return: Data about the default VPC.
        """
        try:
            response = self.ec2_client.describe_vpcs(
                Filters=[{"Name": "is-default", "Values": ["true"]}]
            )
        except ClientError as err:
            raise AutoScalerError(f"Couldn't get default VPC: {err}")
        else:
            return response["Vpcs"][0]


    def verify_inbound_port(self, vpc, port, ip_address):
        """
        Verify the default security group of the specified VPC allows ingress from
this
        computer. This can be done by allowing ingress from this computer's IP
        address. In some situations, such as connecting from a corporate network,
you
        must instead specify a prefix list ID. You can also temporarily open the
port to
        any IP address while running this example. If you do, be sure to remove
public
        access when you're done.

        :param vpc: The VPC used by this example.
        :param port: The port to verify.
        :param ip_address: This computer's IP address.
        :return: The default security group of the specific VPC, and a value that
indicates
                 whether the specified port is open.
        """
        try:
```

```
            response = self.ec2_client.describe_security_groups(
                Filters=[
                    {"Name": "group-name", "Values": ["default"]},
                    {"Name": "vpc-id", "Values": [vpc["VpcId"]]},
                ]
            )
            sec_group = response["SecurityGroups"][0]
            port_is_open = False
            log.info("Found default security group %s.", sec_group["GroupId"])
            for ip_perm in sec_group["IpPermissions"]:
                if ip_perm.get("FromPort", 0) == port:
                    log.info("Found inbound rule: %s", ip_perm)
                    for ip_range in ip_perm["IpRanges"]:
                        cidr = ip_range.get("CidrIp", "")
                        if cidr.startswith(ip_address) or cidr == "0.0.0.0/0":
                            port_is_open = True
                    if ip_perm["PrefixListIds"]:
                        port_is_open = True
                    if not port_is_open:
                        log.info(
                            "The inbound rule does not appear to be open to either
this computer's IP\n"
                            "address of %s, to all IP addresses (0.0.0.0/0), or to a
prefix list ID.",
                            ip_address,
                        )
                    else:
                        break
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't verify inbound rule for port {port} for VPC
{vpc['VpcId']}: {err}"
            )
        else:
            return sec_group, port_is_open


    def open_inbound_port(self, sec_group_id, port, ip_address):
        """
        Add an ingress rule to the specified security group that allows access on
the
        specified port from the specified IP address.

        :param sec_group_id: The ID of the security group to modify.
```

```
        :param port: The port to open.
        :param ip_address: The IP address that is granted access.
        """
        try:
            self.ec2_client.authorize_security_group_ingress(
                GroupId=sec_group_id,
                CidrIp=f"{ip_address}/32",
                FromPort=port,
                ToPort=port,
                IpProtocol="tcp",
            )
            log.info(
                "Authorized ingress to %s on port %s from %s.",
                sec_group_id,
                port,
                ip_address,
            )
        except ClientError as err:
            raise AutoScalerError(
                f"Couldn't authorize ingress to {sec_group_id} on port {port} from
{ip_address}: {err}"
            )


    def get_subnets(self, vpc_id, zones):
        """
        Gets the default subnets in a VPC for a specified list of Availability
Zones.

        :param vpc_id: The ID of the VPC to look up.
        :param zones: The list of Availability Zones to look up.
        :return: The list of subnets found.
        """
        try:
            response = self.ec2_client.describe_subnets(
                Filters=[
                    {"Name": "vpc-id", "Values": [vpc_id]},
                    {"Name": "availability-zone", "Values": zones},
                    {"Name": "default-for-az", "Values": ["true"]},
                ]
            )
            subnets = response["Subnets"]
            log.info("Found %s subnets for the specified zones.", len(subnets))
        except ClientError as err:
```

```
            raise AutoScalerError(f"Couldn't get subnets: {err}")
        else:
            return subnets
```

Crie uma classe que envolva as ações do Elastic Load Balancing.

```
class LoadBalancer:
    """Encapsulates Elastic Load Balancing (ELB) actions."""

    def __init__(self, target_group_name, load_balancer_name, elb_client):
        """
        :param target_group_name: The name of the target group associated with the
 load balancer.
        :param load_balancer_name: The name of the load balancer.
        :param elb_client: A Boto3 Elastic Load Balancing client.
        """
        self.target_group_name = target_group_name
        self.load_balancer_name = load_balancer_name
        self.elb_client = elb_client
        self._endpoint = None


    @classmethod
    def from_client(cls, resource_prefix):
        """
        Creates this class from a Boto3 client.

        :param resource_prefix: The prefix to give to AWS resources created by this
 class.
        """
        elb_client = boto3.client("elbv2")
        return cls(f"{resource_prefix}-tg", f"{resource_prefix}-lb", elb_client)

    def endpoint(self):
        """
        Gets the HTTP endpoint of the load balancer.

        :return: The endpoint.
        """
```

```
        if self._endpoint is None:
            try:
                response = self.elb_client.describe_load_balancers(
                    Names=[self.load_balancer_name]
                )
                self._endpoint = response["LoadBalancers"][0]["DNSName"]
            except ClientError as err:
                raise LoadBalancerError(
                    f"Couldn't get the endpoint for load balancer
{self.load_balancer_name}: {err}"
                )
        return self._endpoint


    def create_target_group(self, protocol, port, vpc_id):
        """
        Creates an Elastic Load Balancing target group. The target group specifies
how
        the load balancer forward requests to instances in the group and how
instance
        health is checked.

        To speed up this demo, the health check is configured with shortened times
and
        lower thresholds. In production, you might want to decrease the sensitivity
of
        your health checks to avoid unwanted failures.

        :param protocol: The protocol to use to forward requests, such as 'HTTP'.
        :param port: The port to use to forward requests, such as 80.
        :param vpc_id: The ID of the VPC in which the load balancer exists.
        :return: Data about the newly created target group.
        """
        try:
            response = self.elb_client.create_target_group(
                Name=self.target_group_name,
                Protocol=protocol,
                Port=port,
                HealthCheckPath="/healthcheck",
                HealthCheckIntervalSeconds=10,
                HealthCheckTimeoutSeconds=5,
                HealthyThresholdCount=2,
                UnhealthyThresholdCount=2,
                VpcId=vpc_id,
```

```
            )
            target_group = response["TargetGroups"][0]
            log.info("Created load balancing target group %s.",
self.target_group_name)
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't create load balancing target group
{self.target_group_name}: {err}"
            )
        else:
            return target_group


    def delete_target_group(self):
        """
        Deletes the target group.
        """
        done = False
        while not done:
            try:
                response = self.elb_client.describe_target_groups(
                    Names=[self.target_group_name]
                )
                tg_arn = response["TargetGroups"][0]["TargetGroupArn"]
                self.elb_client.delete_target_group(TargetGroupArn=tg_arn)
                log.info(
                    "Deleted load balancing target group %s.",
self.target_group_name
                )
                done = True
            except ClientError as err:
                if err.response["Error"]["Code"] == "TargetGroupNotFound":
                    log.info(
                        "Load balancer target group %s not found, nothing to do.",
                        self.target_group_name,
                    )
                    done = True
                elif err.response["Error"]["Code"] == "ResourceInUse":
                    log.info(
                        "Target group not yet released from load balancer,
waiting..."
                    )
                    time.sleep(10)
                else:
```

```
                    raise LoadBalancerError(
                        f"Couldn't delete load balancing target group
{self.target_group_name}: {err}"
                    )


    def create_load_balancer(self, subnet_ids, target_group):
        """
        Creates an Elastic Load Balancing load balancer that uses the specified
subnets
        and forwards requests to the specified target group.

        :param subnet_ids: A list of subnets to associate with the load balancer.
        :param target_group: An existing target group that is added as a listener to
the
                             load balancer.
        :return: Data about the newly created load balancer.
        """
        try:
            response = self.elb_client.create_load_balancer(
                Name=self.load_balancer_name, Subnets=subnet_ids
            )
            load_balancer = response["LoadBalancers"][0]
            log.info("Created load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancer_available")
            log.info("Waiting for load balancer to be available...")
            waiter.wait(Names=[self.load_balancer_name])
            log.info("Load balancer is available!")
            self.elb_client.create_listener(
                LoadBalancerArn=load_balancer["LoadBalancerArn"],
                Protocol=target_group["Protocol"],
                Port=target_group["Port"],
                DefaultActions=[
                    {
                        "Type": "forward",
                        "TargetGroupArn": target_group["TargetGroupArn"],
                    }
                ],
            )
            log.info(
                "Created listener to forward traffic from load balancer %s to target
group %s.",
                self.load_balancer_name,
                target_group["TargetGroupName"],
```

```
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Failed to create load balancer {self.load_balancer_name}"
                f"and add a listener for target group
{target_group['TargetGroupName']}: {err}"
            )
        else:
            self._endpoint = load_balancer["DNSName"]
            return load_balancer


    def delete_load_balancer(self):
        """
        Deletes a load balancer.
        """
        try:
            response = self.elb_client.describe_load_balancers(
                Names=[self.load_balancer_name]
            )
            lb_arn = response["LoadBalancers"][0]["LoadBalancerArn"]
            self.elb_client.delete_load_balancer(LoadBalancerArn=lb_arn)
            log.info("Deleted load balancer %s.", self.load_balancer_name)
            waiter = self.elb_client.get_waiter("load_balancers_deleted")
            log.info("Waiting for load balancer to be deleted...")
            waiter.wait(Names=[self.load_balancer_name])
        except ClientError as err:
            if err.response["Error"]["Code"] == "LoadBalancerNotFound":
                log.info(
                    "Load balancer %s does not exist, nothing to do.",
                    self.load_balancer_name,
                )
            else:
                raise LoadBalancerError(
                    f"Couldn't delete load balancer {self.load_balancer_name}:
{err}"
                )


    def verify_load_balancer_endpoint(self):
        """
        Verify this computer can successfully send a GET request to the load
balancer endpoint.
        """
```

```
        success = False
        retries = 3
        while not success and retries > 0:
            try:
                lb_response = requests.get(f"http://{self.endpoint()}")
                log.info(
                    "Got response %s from load balancer endpoint.",
                    lb_response.status_code,
                )
                if lb_response.status_code == 200:
                    success = True
                else:
                    retries = 0
            except requests.exceptions.ConnectionError:
                log.info(
                    "Got connection error from load balancer endpoint, retrying..."
                )
                retries -= 1
                time.sleep(10)
        return success

    def check_target_health(self):
        """
        Checks the health of the instances in the target group.

        :return: The health status of the target group.
        """
        try:
            tg_response = self.elb_client.describe_target_groups(
                Names=[self.target_group_name]
            )
            health_response = self.elb_client.describe_target_health(
                TargetGroupArn=tg_response["TargetGroups"][0]["TargetGroupArn"]
            )
        except ClientError as err:
            raise LoadBalancerError(
                f"Couldn't check health of {self.target_group_name} targets: {err}"
            )
        else:
            return health_response["TargetHealthDescriptions"]
```

Crie uma classe que use o DynamoDB para simular um serviço de recomendação.

```
class RecommendationService:
    """
    Encapsulates a DynamoDB table to use as a service that recommends books, movies,
    and songs.
    """

    def __init__(self, table_name, dynamodb_client):
        """
        :param table_name: The name of the DynamoDB recommendations table.
        :param dynamodb_client: A Boto3 DynamoDB client.
        """
        self.table_name = table_name
        self.dynamodb_client = dynamodb_client

    @classmethod
    def from_client(cls, table_name):
        """
        Creates this class from a Boto3 client.

        :param table_name: The name of the DynamoDB recommendations table.
        """
        ddb_client = boto3.client("dynamodb")
        return cls(table_name, ddb_client)

    def create(self):
        """
        Creates a DynamoDB table to use a recommendation service. The table has a
        hash key named 'MediaType' that defines the type of media recommended, such
 as
        Book or Movie, and a range key named 'ItemId' that, combined with the
 MediaType,
        forms a unique identifier for the recommended item.

        :return: Data about the newly created table.
        """
        try:
            response = self.dynamodb_client.create_table(
                TableName=self.table_name,
                AttributeDefinitions=[
```

```
                    {"AttributeName": "MediaType", "AttributeType": "S"},
                    {"AttributeName": "ItemId", "AttributeType": "N"},
                ],
                KeySchema=[
                    {"AttributeName": "MediaType", "KeyType": "HASH"},
                    {"AttributeName": "ItemId", "KeyType": "RANGE"},
                ],
                ProvisionedThroughput={"ReadCapacityUnits": 5, "WriteCapacityUnits":
5},
            )
            log.info("Creating table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s created.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceInUseException":
                log.info("Table %s exists, nothing to be do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when creating table: {err}."
                )
        else:
            return response

    def populate(self, data_file):
        """
        Populates the recommendations table from a JSON file.

        :param data_file: The path to the data file.
        """
        try:
            with open(data_file) as data:
                items = json.load(data)
            batch = [{"PutRequest": {"Item": item}} for item in items]
            self.dynamodb_client.batch_write_item(RequestItems={self.table_name:
batch})
            log.info(
                "Populated table %s with items from %s.", self.table_name, data_file
            )
        except ClientError as err:
            raise RecommendationServiceError(
                self.table_name, f"Couldn't populate table from {data_file}: {err}"
            )
```

```
    def destroy(self):
        """
        Deletes the recommendations table.
        """
        try:
            self.dynamodb_client.delete_table(TableName=self.table_name)
            log.info("Deleting table %s...", self.table_name)
            waiter = self.dynamodb_client.get_waiter("table_not_exists")
            waiter.wait(TableName=self.table_name)
            log.info("Table %s deleted.", self.table_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                log.info("Table %s does not exist, nothing to do.", self.table_name)
            else:
                raise RecommendationServiceError(
                    self.table_name, f"ClientError when deleting table: {err}."
                )
```

Crie uma classe que envolva as ações do Systems Manager.

```
class ParameterHelper:
    """
    Encapsulates Systems Manager parameters. This example uses these parameters to
 drive
    the demonstration of resilient architecture, such as failure of a dependency or
    how the service responds to a health check.
    """

    table = "doc-example-resilient-architecture-table"
    failure_response = "doc-example-resilient-architecture-failure-response"
    health_check = "doc-example-resilient-architecture-health-check"

    def __init__(self, table_name, ssm_client):
        """
        :param table_name: The name of the DynamoDB table that is used as a
 recommendation
                           service.
        :param ssm_client: A Boto3 Systems Manager client.
        """
        self.ssm_client = ssm_client
```

```
        self.table_name = table_name

    @classmethod
    def from_client(cls, table_name):
        ssm_client = boto3.client("ssm")
        return cls(table_name, ssm_client)

    def reset(self):
        """
        Resets the Systems Manager parameters to starting values for the demo.
        These are the name of the DynamoDB recommendation table, no response when a
        dependency fails, and shallow health checks.
        """
        self.put(self.table, self.table_name)
        self.put(self.failure_response, "none")
        self.put(self.health_check, "shallow")

    def put(self, name, value):
        """
        Sets the value of a named Systems Manager parameter.

        :param name: The name of the parameter.
        :param value: The new value of the parameter.
        """
        try:
            self.ssm_client.put_parameter(
                Name=name, Value=value, Overwrite=True, Type="String"
            )
            log.info("Setting demo parameter %s to '%s'.", name, value)
        except ClientError as err:
            raise ParameterHelperError(
                f"Couldn't set parameter {name} to {value}: {err}"
            )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachLoadBalancerTargetGroups
  - CreateAutoScalingGroup
  - CreateInstanceProfile

- CreateLaunchTemplate
- CreateListener
- CreateLoadBalancer
- CreateTargetGroup
- DeleteAutoScalingGroup
- DeleteInstanceProfile
- DeleteLaunchTemplate
- DeleteLoadBalancer
- DeleteTargetGroup
- DescribeAutoScalingGroups
- DescribeAvailabilityZones
- DescribeIamInstanceProfileAssociations
- DescribeInstances
- DescribeLoadBalancers
- DescribeSubnets
- DescribeTargetGroups
- DescribeTargetHealth
- DescribeVpcs
- RebootInstances
- ReplaceIamInstanceProfileAssociation
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
import json
import sys
import time
from uuid import uuid4

import boto3
from botocore.exceptions import ClientError


def progress_bar(seconds):
    """Shows a simple progress bar in the command window."""
    for _ in range(seconds):
        time.sleep(1)
        print(".", end="")
        sys.stdout.flush()
    print()


def setup(iam_resource):
    """
    Creates a new user with no permissions.
    Creates an access key pair for the user.
    Creates a role with a policy that lets the user assume the role.
```

```
    Creates a policy that allows listing Amazon S3 buckets.
    Attaches the policy to the role.
    Creates an inline policy for the user that lets the user assume the role.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM) resource
                         that has permissions to create users, roles, and policies
                         in the account.
    :return: The newly created user, user key, and role.
    """
    try:
        user = iam_resource.create_user(UserName=f"demo-user-{uuid4()}")
        print(f"Created user {user.name}.")
    except ClientError as error:
        print(
            f"Couldn't create a user for the demo. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        user_key = user.create_access_key_pair()
        print(f"Created access key pair for user.")
    except ClientError as error:
        print(
            f"Couldn't create access keys for user {user.name}. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    try:
        role = iam_resource.create_role(
            RoleName=f"demo-role-{uuid4()}",
            AssumeRolePolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Principal": {"AWS": user.arn},
                            "Action": "sts:AssumeRole",
                        }
```

```
                    ],
                }
            ),
        )
        print(f"Created role {role.name}.")
    except ClientError as error:
        print(
            f"Couldn't create a role for the demo. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        policy = iam_resource.create_policy(
            PolicyName=f"demo-policy-{uuid4()}",
            PolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Action": "s3:ListAllMyBuckets",
                            "Resource": "arn:aws:s3:::*",
                        }
                    ],
                }
            ),
        )
        role.attach_policy(PolicyArn=policy.arn)
        print(f"Created policy {policy.policy_name} and attached it to the role.")
    except ClientError as error:
        print(
            f"Couldn't create a policy and attach it to role {role.name}. Here's
why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        user.create_policy(
            PolicyName=f"demo-user-policy-{uuid4()}",
            PolicyDocument=json.dumps(
                {
                    "Version": "2012-10-17",
```

```
                    "Statement": [
                        {
                            "Effect": "Allow",
                            "Action": "sts:AssumeRole",
                            "Resource": role.arn,
                        }
                    ],
                }
            ),
        )
        print(
            f"Created an inline policy for {user.name} that lets the user assume "
            f"the role."
        )
    except ClientError as error:
        print(
            f"Couldn't create an inline policy for user {user.name}. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    print("Give AWS time to propagate these new resources and connections.", end="")
    progress_bar(10)

    return user, user_key, role


def show_access_denied_without_role(user_key):
    """
    Shows that listing buckets without first assuming the role is not allowed.

    :param user_key: The key of the user created during setup. This user does not
                     have permission to list buckets in the account.
    """
    print(f"Try to list buckets without first assuming the role.")
    s3_denied_resource = boto3.resource(
        "s3", aws_access_key_id=user_key.id, aws_secret_access_key=user_key.secret
    )
    try:
        for bucket in s3_denied_resource.buckets.all():
            print(bucket.name)
        raise RuntimeError("Expected to get AccessDenied error when listing
 buckets!")
    except ClientError as error:
```

```
        if error.response["Error"]["Code"] == "AccessDenied":
            print("Attempt to list buckets with no permissions: AccessDenied.")
        else:
            raise


def list_buckets_from_assumed_role(user_key, assume_role_arn, session_name):
    """
    Assumes a role that grants permission to list the Amazon S3 buckets in the
 account.
    Uses the temporary credentials from the role to list the buckets that are owned
    by the assumed role's account.

    :param user_key: The access key of a user that has permission to assume the
 role.
    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    """
    sts_client = boto3.client(
        "sts", aws_access_key_id=user_key.id, aws_secret_access_key=user_key.secret
    )
    try:
        response = sts_client.assume_role(
            RoleArn=assume_role_arn, RoleSessionName=session_name
        )
        temp_credentials = response["Credentials"]
        print(f"Assumed role {assume_role_arn} and got temporary credentials.")
    except ClientError as error:
        print(
            f"Couldn't assume role {assume_role_arn}. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    # Create an S3 resource that can access the account with the temporary
 credentials.
    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )
    print(f"Listing buckets for the assumed role's account:")
```

```
    try:
        for bucket in s3_resource.buckets.all():
            print(bucket.name)
    except ClientError as error:
        print(
            f"Couldn't list buckets for the account. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise




def teardown(user, role):
    """
    Removes all resources created during setup.

    :param user: The demo user.
    :param role: The demo role.
    """
    try:
        for attached in role.attached_policies.all():
            policy_name = attached.policy_name
            role.detach_policy(PolicyArn=attached.arn)
            attached.delete()
            print(f"Detached and deleted {policy_name}.")
        role.delete()
        print(f"Deleted {role.name}.")
    except ClientError as error:
        print(
            "Couldn't detach policy, delete policy, or delete role. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

    try:
        for user_pol in user.policies.all():
            user_pol.delete()
            print("Deleted inline user policy.")
        for key in user.access_keys.all():
            key.delete()
            print("Deleted user's access key.")
        user.delete()
        print(f"Deleted {user.name}.")
```

```
    except ClientError as error:
        print(
            "Couldn't delete user policy or delete user. Here's why: "
            f"{error.response['Error']['Message']}"
        )


def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(f"Welcome to the IAM create user and assume role demo.")
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    user = None
    role = None
    try:
        user, user_key, role = setup(iam_resource)
        print(f"Created {user.name} and {role.name}.")
        show_access_denied_without_role(user_key)
        list_buckets_from_assumed_role(user_key, role.arn, "AssumeRoleDemoSession")
    except Exception:
        print("Something went wrong!")
    finally:
        if user is not None and role is not None:
            teardown(user, role)
        print("Thanks for watching!")


if __name__ == "__main__":
    usage_demo()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey

- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Criar usuários somente leitura e leitura/gravação usando

Os exemplos de código a seguir mostram como criar usuários e anexar políticas a eles.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar dois usuários IAM.
- Anexe uma política para um usuário obter e colocar objetos em um bucket do Amazon S3.
- Anexar uma política para o segundo usuário para obter objetos do bucket.
- Obter outras permissões para o bucket com base nas credenciais do usuário.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie a funções que envolvam ações do usuário do IAM.

```
import logging
import time
```

```
import boto3
from botocore.exceptions import ClientError

import access_key_wrapper
import policy_wrapper

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_user(user_name):
    """
    Creates a user. By default, a user has no permissions or access keys.

    :param user_name: The name of the user.
    :return: The newly created user.
    """
    try:
        user = iam.create_user(UserName=user_name)
        logger.info("Created user %s.", user.name)
    except ClientError:
        logger.exception("Couldn't create user %s.", user_name)
        raise
    else:
        return user



def update_user(user_name, new_user_name):
    """
    Updates a user's name.

    :param user_name: The current name of the user to update.
    :param new_user_name: The new name to assign to the user.
    :return: The updated user.
    """
    try:
        user = iam.User(user_name)
        user.update(NewUserName=new_user_name)
        logger.info("Renamed %s to %s.", user_name, new_user_name)
    except ClientError:
        logger.exception("Couldn't update name for user %s.", user_name)
        raise
    return user
```

```
def list_users():
    """
    Lists the users in the current account.

    :return: The list of users.
    """
    try:
        users = list(iam.users.all())
        logger.info("Got %s users.", len(users))
    except ClientError:
        logger.exception("Couldn't get users.")
        raise
    else:
        return users



def delete_user(user_name):
    """
    Deletes a user. Before a user can be deleted, all associated resources,
    such as access keys and policies, must be deleted or detached.

    :param user_name: The name of the user.
    """
    try:
        iam.User(user_name).delete()
        logger.info("Deleted user %s.", user_name)
    except ClientError:
        logger.exception("Couldn't delete user %s.", user_name)
        raise



def attach_policy(user_name, policy_arn):
    """
    Attaches a policy to a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).attach_policy(PolicyArn=policy_arn)
```

```
        logger.info("Attached policy %s to user %s.", policy_arn, user_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to user %s.", policy_arn,
 user_name)
        raise



def detach_policy(user_name, policy_arn):
    """
    Detaches a policy from a user.

    :param user_name: The name of the user.
    :param policy_arn: The Amazon Resource Name (ARN) of the policy.
    """
    try:
        iam.User(user_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from user %s.", policy_arn, user_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from user %s.", policy_arn, user_name
        )
        raise
```

Crie a funções que envolvam ações de política do IAM.

```
import json
import logging
import operator
import pprint
import time

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_policy(name, description, actions, resource_arn):
    """
```

```
    Creates a policy that contains a single statement.

    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy



def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
        raise
```

Crie funções que envolvam ações de chave de acesso do IAM.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)

iam = boto3.resource("iam")

def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.

    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair



def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
```

```
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

Use as funções de wrapper para criar usuários com políticas diferentes e use as credenciais deles para acessar um bucket do Amazon S3.

```
def usage_demo():
    """
    Shows how to manage users, keys, and policies.
    This demonstration creates two users: one user who can put and get objects in an
    Amazon S3 bucket, and another user who can only get objects from the bucket.
    The demo then shows how the users can perform only the actions they are
 permitted
    to perform.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management user demo.")
    print("-" * 88)
    print(
        "Users can have policies and roles attached to grant them specific "
        "permissions."
    )
    s3 = boto3.resource("s3")
    bucket = s3.create_bucket(
        Bucket=f"demo-iam-bucket-{time.time_ns()}",
        CreateBucketConfiguration={
            "LocationConstraint": s3.meta.client.meta.region_name
        },
    )
    print(f"Created an Amazon S3 bucket named {bucket.name}.")
    user_read_writer = create_user("demo-iam-read-writer")
    user_reader = create_user("demo-iam-reader")
```

```
    print(f"Created two IAM users: {user_read_writer.name} and {user_reader.name}")
    update_user(user_read_writer.name, "demo-iam-creator")
    update_user(user_reader.name, "demo-iam-getter")
    users = list_users()
    user_read_writer = next(
        user for user in users if user.user_id == user_read_writer.user_id
    )
    user_reader = next(user for user in users if user.user_id ==
user_reader.user_id)
    print(
        f"Changed the names of the users to {user_read_writer.name} "
        f"and {user_reader.name}."
    )

    read_write_policy = policy_wrapper.create_policy(
        "demo-iam-read-write-policy",
        "Grants rights to create and get an object in the demo bucket.",
        ["s3:PutObject", "s3:GetObject"],
        f"arn:aws:s3:::{bucket.name}/*",
    )
    print(
        f"Created policy {read_write_policy.policy_name} with ARN:
{read_write_policy.arn}"
    )
    print(read_write_policy.description)
    read_policy = policy_wrapper.create_policy(
        "demo-iam-read-policy",
        "Grants rights to get an object from the demo bucket.",
        "s3:GetObject",
        f"arn:aws:s3:::{bucket.name}/*",
    )
    print(f"Created policy {read_policy.policy_name} with ARN: {read_policy.arn}")
    print(read_policy.description)
    attach_policy(user_read_writer.name, read_write_policy.arn)
    print(f"Attached {read_write_policy.policy_name} to {user_read_writer.name}.")
    attach_policy(user_reader.name, read_policy.arn)
    print(f"Attached {read_policy.policy_name} to {user_reader.name}.")

    user_read_writer_key = access_key_wrapper.create_key(user_read_writer.name)
    print(f"Created access key pair for {user_read_writer.name}.")
    user_reader_key = access_key_wrapper.create_key(user_reader.name)
    print(f"Created access key pair for {user_reader.name}.")

    s3_read_writer_resource = boto3.resource(
```

```
        "s3",
        aws_access_key_id=user_read_writer_key.id,
        aws_secret_access_key=user_read_writer_key.secret,
    )
    demo_object_key = f"object-{time.time_ns()}"
    demo_object = None
    while demo_object is None:
        try:
            demo_object = s3_read_writer_resource.Bucket(bucket.name).put_object(
                Key=demo_object_key, Body=b"AWS IAM demo object content!"
            )
        except ClientError as error:
            if error.response["Error"]["Code"] == "InvalidAccessKeyId":
                print("Access key not yet available. Waiting...")
                time.sleep(1)
            else:
                raise
    print(
        f"Put {demo_object_key} into {bucket.name} using "
        f"{user_read_writer.name}'s credentials."
    )

    read_writer_object = s3_read_writer_resource.Bucket(bucket.name).Object(
        demo_object_key
    )
    read_writer_content = read_writer_object.get()["Body"].read()
    print(f"Got object {read_writer_object.key} using read-writer user's
credentials.")
    print(f"Object content: {read_writer_content}")

    s3_reader_resource = boto3.resource(
        "s3",
        aws_access_key_id=user_reader_key.id,
        aws_secret_access_key=user_reader_key.secret,
    )
    demo_content = None
    while demo_content is None:
        try:
            demo_object =
s3_reader_resource.Bucket(bucket.name).Object(demo_object_key)
            demo_content = demo_object.get()["Body"].read()
            print(f"Got object {demo_object.key} using reader user's credentials.")
            print(f"Object content: {demo_content}")
        except ClientError as error:
```

```
            if error.response["Error"]["Code"] == "InvalidAccessKeyId":
                print("Access key not yet available. Waiting...")
                time.sleep(1)
            else:
                raise

    try:
        demo_object.delete()
    except ClientError as error:
        if error.response["Error"]["Code"] == "AccessDenied":
            print("-" * 88)
            print(
                "Tried to delete the object using the reader user's credentials. "
                "Got expected AccessDenied error because the reader is not "
                "allowed to delete objects."
            )
            print("-" * 88)

    access_key_wrapper.delete_key(user_reader.name, user_reader_key.id)
    detach_policy(user_reader.name, read_policy.arn)
    policy_wrapper.delete_policy(read_policy.arn)
    delete_user(user_reader.name)
    print(f"Deleted keys, detached and deleted policy, and deleted
{user_reader.name}.")

    access_key_wrapper.delete_key(user_read_writer.name, user_read_writer_key.id)
    detach_policy(user_read_writer.name, read_write_policy.arn)
    policy_wrapper.delete_policy(read_write_policy.arn)
    delete_user(user_read_writer.name)
    print(
        f"Deleted keys, detached and deleted policy, and deleted
{user_read_writer.name}."
    )

    bucket.objects.delete()
    bucket.delete()
    print(f"Emptied and deleted {bucket.name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachUserPolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteUser
  - DetachUserPolicy
  - ListUsers
  - UpdateUser

Gerenciar chaves de acesso

O exemplo de código a seguir mostra como gerenciar chaves de acesso.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar e listar chaves de acesso.
- Descobrir quando e como a chave de acesso foi usada pela última vez.
- Atualizar e excluir chaves de acesso.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a funções que envolvam ações de chave de acesso do IAM.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)

iam = boto3.resource("iam")

def list_keys(user_name):
    """
    Lists the keys owned by the specified user.

    :param user_name: The name of the user.
    :return: The list of keys owned by the user.
    """
    try:
        keys = list(iam.User(user_name).access_keys.all())
        logger.info("Got %s access keys for %s.", len(keys), user_name)
    except ClientError:
        logger.exception("Couldn't get access keys for %s.", user_name)
        raise
    else:
        return keys



def create_key(user_name):
    """
    Creates an access key for the specified user. Each user can have a
    maximum of two keys.

    :param user_name: The name of the user.
    :return: The created access key.
    """
    try:
        key_pair = iam.User(user_name).create_access_key_pair()
        logger.info(
            "Created access key pair for %s. Key ID is %s.",
            key_pair.user_name,
            key_pair.id,
        )
    except ClientError:
```

```
        logger.exception("Couldn't create access key pair for %s.", user_name)
        raise
    else:
        return key_pair



def get_last_use(key_id):
    """
    Gets information about when and how a key was last used.

    :param key_id: The ID of the key to look up.
    :return: Information about the key's last use.
    """
    try:
        response = iam.meta.client.get_access_key_last_used(AccessKeyId=key_id)
        last_used_date = response["AccessKeyLastUsed"].get("LastUsedDate", None)
        last_service = response["AccessKeyLastUsed"].get("ServiceName", None)
        logger.info(
            "Key %s was last used by %s on %s to access %s.",
            key_id,
            response["UserName"],
            last_used_date,
            last_service,
        )
    except ClientError:
        logger.exception("Couldn't get last use of key %s.", key_id)
        raise
    else:
        return response



def update_key(user_name, key_id, activate):
    """
    Updates the status of a key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to update.
    :param activate: When True, the key is activated. Otherwise, the key is
 deactivated.
    """

    try:
```

```
        key = iam.User(user_name).AccessKey(key_id)
        if activate:
            key.activate()
        else:
            key.deactivate()
        logger.info("%s key %s.", "Activated" if activate else "Deactivated",
 key_id)
    except ClientError:
        logger.exception(
            "Couldn't %s key %s.", "Activate" if activate else "Deactivate", key_id
        )
        raise



def delete_key(user_name, key_id):
    """
    Deletes a user's access key.

    :param user_name: The user that owns the key.
    :param key_id: The ID of the key to delete.
    """

    try:
        key = iam.AccessKey(user_name, key_id)
        key.delete()
        logger.info("Deleted access key %s for %s.", key.id, key.user_name)
    except ClientError:
        logger.exception("Couldn't delete key %s for %s", key_id, user_name)
        raise
```

Use a funções de wrapper para executar ações de chave de acesso para o usuário atual.

```
def usage_demo():
    """Shows how to create and manage access keys."""

    def print_keys():
        """Gets and prints the current keys for a user."""
        current_keys = list_keys(current_user_name)
        print("The current user's keys are now:")
```

```
        print(*[f"{key.id}: {key.status}" for key in current_keys], sep="\n")

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management access key demo.")
    print("-" * 88)
    current_user_name = iam.CurrentUser().user_name
    print(
        f"This demo creates an access key for the current user "
        f"({current_user_name}), manipulates the key in a few ways, and then "
        f"deletes it."
    )
    all_keys = list_keys(current_user_name)
    if len(all_keys) == 2:
        print(
            "The current user already has the maximum of 2 access keys. To run "
            "this demo, either delete one of the access keys or use a user "
            "that has only 1 access key."
        )
    else:
        new_key = create_key(current_user_name)
        print(f"Created a new key with id {new_key.id} and secret
{new_key.secret}.")
        print_keys()
        existing_key = next(key for key in all_keys if key != new_key)
        last_use = get_last_use(existing_key.id)["AccessKeyLastUsed"]
        print(
            f"Key {all_keys[0].id} was last used to access {last_use['ServiceName']}
"
            f"on {last_use['LastUsedDate']}"
        )
        update_key(current_user_name, new_key.id, False)
        print(f"Key {new_key.id} is now deactivated.")
        print_keys()
        delete_key(current_user_name, new_key.id)
        print_keys()
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).

- CreateAccessKey
- DeleteAccessKey
- GetAccessKeyLastUsed
- ListAccessKeys
- UpdateAccessKey

Políticas gerenciadas

O código de exemplo a seguir mostra como:

- Criar e listar políticas.
- Criar e obter versões de políticas.
- Reverter uma política para uma versão anterior.
- Excluir políticas.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie a funções que envolvam ações de política do IAM.

```
import json
import logging
import operator
import pprint
import time

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_policy(name, description, actions, resource_arn):
```

```
    """
    Creates a policy that contains a single statement.

    :param name: The name of the policy to create.
    :param description: The description of the policy.
    :param actions: The actions allowed by the policy. These typically take the
                    form of service:action, such as s3:PutObject.
    :param resource_arn: The Amazon Resource Name (ARN) of the resource this policy
                         applies to. This ARN can contain wildcards, such as
                         'arn:aws:s3:::my-bucket/*' to allow actions on all objects
                         in the bucket named 'my-bucket'.
    :return: The newly created policy.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.create_policy(
            PolicyName=name,
            Description=description,
            PolicyDocument=json.dumps(policy_doc),
        )
        logger.info("Created policy %s.", policy.arn)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy



def list_policies(scope):
    """
    Lists the policies in the current account.

    :param scope: Limits the kinds of policies that are returned. For example,
                  'Local' specifies that only locally managed policies are returned.
    :return: The list of policies.
    """
    try:
        policies = list(iam.policies.filter(Scope=scope))
        logger.info("Got %s policies in scope '%s'.", len(policies), scope)
```

```
    except ClientError:
        logger.exception("Couldn't get policies for scope '%s'.", scope)
        raise
    else:
        return policies



def create_policy_version(policy_arn, actions, resource_arn, set_as_default):
    """
    Creates a policy version. Policies can have up to five versions. The default
    version is the one that is used for all resources that reference the policy.

    :param policy_arn: The ARN of the policy.
    :param actions: The actions to allow in the policy version.
    :param resource_arn: The ARN of the resource this policy version applies to.
    :param set_as_default: When True, this policy version is set as the default
                           version for the policy. Otherwise, the default
                           is not changed.
    :return: The newly created policy version.
    """
    policy_doc = {
        "Version": "2012-10-17",
        "Statement": [{"Effect": "Allow", "Action": actions, "Resource":
 resource_arn}],
    }
    try:
        policy = iam.Policy(policy_arn)
        policy_version = policy.create_version(
            PolicyDocument=json.dumps(policy_doc), SetAsDefault=set_as_default
        )
        logger.info(
            "Created policy version %s for policy %s.",
            policy_version.version_id,
            policy_version.arn,
        )
    except ClientError:
        logger.exception("Couldn't create a policy version for %s.", policy_arn)
        raise
    else:
        return policy_version
```

```
def get_default_policy_statement(policy_arn):
    """
    Gets the statement of the default version of the specified policy.

    :param policy_arn: The ARN of the policy to look up.
    :return: The statement of the default policy version.
    """
    try:
        policy = iam.Policy(policy_arn)
        # To get an attribute of a policy, the SDK first calls get_policy.
        policy_doc = policy.default_version.document
        policy_statement = policy_doc.get("Statement", None)
        logger.info("Got default policy doc for %s.", policy.policy_name)
        logger.info(policy_doc)
    except ClientError:
        logger.exception("Couldn't get default policy statement for %s.",
 policy_arn)
        raise
    else:
        return policy_statement



def rollback_policy_version(policy_arn):
    """
    Rolls back to the previous default policy, if it exists.

    1. Gets the list of policy versions in order by date.
    2. Finds the default.
    3. Makes the previous policy the default.
    4. Deletes the old default version.

    :param policy_arn: The ARN of the policy to roll back.
    :return: The default version of the policy after the rollback.
    """
    try:
        policy_versions = sorted(
            iam.Policy(policy_arn).versions.all(),
            key=operator.attrgetter("create_date"),
        )
        logger.info("Got %s versions for %s.", len(policy_versions), policy_arn)
    except ClientError:
        logger.exception("Couldn't get versions for %s.", policy_arn)
        raise
```

```
    default_version = None
    rollback_version = None
    try:
        while default_version is None:
            ver = policy_versions.pop()
            if ver.is_default_version:
                default_version = ver
        rollback_version = policy_versions.pop()
        rollback_version.set_as_default()
        logger.info("Set %s as the default version.", rollback_version.version_id)
        default_version.delete()
        logger.info("Deleted original default version %s.",
 default_version.version_id)
    except IndexError:
        if default_version is None:
            logger.warning("No default version found for %s.", policy_arn)
        elif rollback_version is None:
            logger.warning(
                "Default version %s found for %s, but no previous version exists, so
 "
                "nothing to roll back to.",
                default_version.version_id,
                policy_arn,
            )
    except ClientError:
        logger.exception("Couldn't roll back version for %s.", policy_arn)
        raise
    else:
        return rollback_version



def delete_policy(policy_arn):
    """
    Deletes a policy.

    :param policy_arn: The ARN of the policy to delete.
    """
    try:
        iam.Policy(policy_arn).delete()
        logger.info("Deleted policy %s.", policy_arn)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_arn)
```

```
        raise
```

Use a funções de wrapper para criar políticas, atualizar versões e obter informações sobre elas.

```
def usage_demo():
    """Shows how to use the policy functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management policy demo.")
    print("-" * 88)
    print(
        "Policies let you define sets of permissions that can be attached to "
        "other IAM resources, like users and roles."
    )
    bucket_arn = f"arn:aws:s3:::made-up-bucket-name"
    policy = create_policy(
        "demo-iam-policy",
        "Policy for IAM demonstration.",
        ["s3:ListObjects"],
        bucket_arn,
    )
    print(f"Created policy {policy.policy_name}.")
    policies = list_policies("Local")
    print(f"Your account has {len(policies)} managed policies:")
    print(*[pol.policy_name for pol in policies], sep=", ")
    time.sleep(1)
    policy_version = create_policy_version(
        policy.arn, ["s3:PutObject"], bucket_arn, True
    )
    print(
        f"Added policy version {policy_version.version_id} to policy "
        f"{policy.policy_name}."
    )
    default_statement = get_default_policy_statement(policy.arn)
    print(f"The default policy statement for {policy.policy_name} is:")
    pprint.pprint(default_statement)
    rollback_version = rollback_policy_version(policy.arn)
    print(
        f"Rolled back to version {rollback_version.version_id} for "
        f"{policy.policy_name}."
```

```
    )
    default_statement = get_default_policy_statement(policy.arn)
    print(f"The default policy statement for {policy.policy_name} is now:")
    pprint.pprint(default_statement)
    delete_policy(policy.arn)
    print(f"Deleted policy {policy.policy_name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreatePolicy
  - CreatePolicyVersion
  - DeletePolicy
  - DeletePolicyVersion
  - GetPolicyVersion
  - ListPolicies
  - ListPolicyVersions
  - SetDefaultPolicyVersion

Gerenciar funções

O código de exemplo a seguir mostra como:

- Criar um perfil do IAM.
- Anexar e separar políticas para um perfil.
- Excluir um perfil.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar perfis que envolvam ações de perfil do IAM.

```
import json
import logging
import pprint

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def create_role(role_name, allowed_services):
    """
    Creates a role that lets a list of specified services assume the role.

    :param role_name: The name of the role.
    :param allowed_services: The services that can assume the role.
    :return: The newly created role.
    """
    trust_policy = {
        "Version": "2012-10-17",
        "Statement": [
            {
                "Effect": "Allow",
                "Principal": {"Service": service},
                "Action": "sts:AssumeRole",
            }
            for service in allowed_services
        ],
    }

    try:
        role = iam.create_role(
            RoleName=role_name, AssumeRolePolicyDocument=json.dumps(trust_policy)
        )
        logger.info("Created role %s.", role.name)
    except ClientError:
        logger.exception("Couldn't create role %s.", role_name)
        raise
    else:
        return role
```

```
def attach_policy(role_name, policy_arn):
    """
    Attaches a policy to a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).attach_policy(PolicyArn=policy_arn)
        logger.info("Attached policy %s to role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception("Couldn't attach policy %s to role %s.", policy_arn,
 role_name)
        raise



def detach_policy(role_name, policy_arn):
    """
    Detaches a policy from a role.

    :param role_name: The name of the role. **Note** this is the name, not the ARN.
    :param policy_arn: The ARN of the policy.
    """
    try:
        iam.Role(role_name).detach_policy(PolicyArn=policy_arn)
        logger.info("Detached policy %s from role %s.", policy_arn, role_name)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from role %s.", policy_arn, role_name
        )
        raise



def delete_role(role_name):
    """
    Deletes a role.

    :param role_name: The name of the role to delete.
    """
    try:
        iam.Role(role_name).delete()
```

```
        logger.info("Deleted role %s.", role_name)
    except ClientError:
        logger.exception("Couldn't delete role %s.", role_name)
        raise
```

Use a funções de wrapper para criar uma função, depois, anexe e desanexe uma política.

```
def usage_demo():
    """Shows how to use the role functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management role demo.")
    print("-" * 88)
    print(
        "Roles let you define sets of permissions and can be assumed by "
        "other entities, like users and services."
    )
    print("The first 10 roles currently in your account are:")
    roles = list_roles(10)
    print(f"The inline policies for role {roles[0].name} are:")
    list_policies(roles[0].name)
    role = create_role(
        "demo-iam-role", ["lambda.amazonaws.com",
 "batchoperations.s3.amazonaws.com"]
    )
    print(f"Created role {role.name}, with trust policy:")
    pprint.pprint(role.assume_role_policy_document)
    policy_arn = "arn:aws:iam::aws:policy/AmazonS3ReadOnlyAccess"
    attach_policy(role.name, policy_arn)
    print(f"Attached policy {policy_arn} to {role.name}.")
    print(f"Policies attached to role {role.name} are:")
    list_attached_policies(role.name)
    detach_policy(role.name, policy_arn)
    print(f"Detached policy {policy_arn} from {role.name}.")
    delete_role(role.name)
    print(f"Deleted {role.name}.")
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AttachRolePolicy
  - CreateRole
  - DeleteRole
  - DetachRolePolicy

Gerenciar sua conta

O código de exemplo a seguir mostra como:

- Obtenha e atualize o alias da conta.
- Gere um relatório de usuários e credenciais.
- Obter um resumo da utilização da conta.
- Obtenha detalhes de todos os usuários, grupos, perfis e políticas em sua conta, incluindo as relações uns com os outros.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações de conta do IAM.

```
import logging
import pprint
import sys
import time
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
iam = boto3.resource("iam")

def list_aliases():
```

```
    """
    Gets the list of aliases for the current account. An account has at most one
 alias.

    :return: The list of aliases for the account.
    """
    try:
        response = iam.meta.client.list_account_aliases()
        aliases = response["AccountAliases"]
        if len(aliases) > 0:
            logger.info("Got aliases for your account: %s.", ",".join(aliases))
        else:
            logger.info("Got no aliases for your account.")
    except ClientError:
        logger.exception("Couldn't list aliases for your account.")
        raise
    else:
        return response["AccountAliases"]



def create_alias(alias):
    """
    Creates an alias for the current account. The alias can be used in place of the
    account ID in the sign-in URL. An account can have only one alias. When a new
    alias is created, it replaces any existing alias.

    :param alias: The alias to assign to the account.
    """

    try:
        iam.create_account_alias(AccountAlias=alias)
        logger.info("Created an alias '%s' for your account.", alias)
    except ClientError:
        logger.exception("Couldn't create alias '%s' for your account.", alias)
        raise



def delete_alias(alias):
    """
    Removes the alias from the current account.

    :param alias: The alias to remove.
```

```
    """
    try:
        iam.meta.client.delete_account_alias(AccountAlias=alias)
        logger.info("Removed alias '%s' from your account.", alias)
    except ClientError:
        logger.exception("Couldn't remove alias '%s' from your account.", alias)
        raise



def generate_credential_report():
    """
    Starts generation of a credentials report about the current account. After
    calling this function to generate the report, call get_credential_report
    to get the latest report. A new report can be generated a minimum of four hours
    after the last one was generated.
    """
    try:
        response = iam.meta.client.generate_credential_report()
        logger.info(
            "Generating credentials report for your account. " "Current state is
 %s.",
            response["State"],
        )
    except ClientError:
        logger.exception("Couldn't generate a credentials report for your account.")
        raise
    else:
        return response



def get_credential_report():
    """
    Gets the most recently generated credentials report about the current account.

    :return: The credentials report.
    """
    try:
        response = iam.meta.client.get_credential_report()
        logger.debug(response["Content"])
    except ClientError:
        logger.exception("Couldn't get credentials report.")
        raise
```

```
    else:
        return response["Content"]



def get_summary():
    """
    Gets a summary of account usage.

    :return: The summary of account usage.
    """
    try:
        summary = iam.AccountSummary()
        logger.debug(summary.summary_map)
    except ClientError:
        logger.exception("Couldn't get a summary for your account.")
        raise
    else:
        return summary.summary_map



def get_authorization_details(response_filter):
    """
    Gets an authorization detail report for the current account.

    :param response_filter: A list of resource types to include in the report, such
                            as users or roles. When not specified, all resources
                            are included.
    :return: The authorization detail report.
    """
    try:
        account_details = iam.meta.client.get_account_authorization_details(
            Filter=response_filter
        )
        logger.debug(account_details)
    except ClientError:
        logger.exception("Couldn't get details for your account.")
        raise
    else:
        return account_details
```

Chame funções de wrapper para alterar o alias da conta e obter relatórios sobre a conta.

```
def usage_demo():
    """Shows how to use the account functions."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    print("-" * 88)
    print("Welcome to the AWS Identity and Account Management account demo.")
    print("-" * 88)
    print(
        "Setting an account alias lets you use the alias in your sign-in URL "
        "instead of your account number."
    )
    old_aliases = list_aliases()
    if len(old_aliases) > 0:
        print(f"Your account currently uses '{old_aliases[0]}' as its alias.")
    else:
        print("Your account currently has no alias.")
    for index in range(1, 3):
        new_alias = f"alias-{index}-{time.time_ns()}"
        print(f"Setting your account alias to {new_alias}")
        create_alias(new_alias)
    current_aliases = list_aliases()
    print(f"Your account alias is now {current_aliases}.")
    delete_alias(current_aliases[0])
    print(f"Your account now has no alias.")
    if len(old_aliases) > 0:
        print(f"Restoring your original alias back to {old_aliases[0]}...")
        create_alias(old_aliases[0])

    print("-" * 88)
    print("You can get various reports about your account.")
    print("Let's generate a credentials report...")
    report_state = None
    while report_state != "COMPLETE":
        cred_report_response = generate_credential_report()
        old_report_state = report_state
        report_state = cred_report_response["State"]
        if report_state != old_report_state:
            print(report_state, sep="")
        else:
            print(".", sep="")
```

```
        sys.stdout.flush()
        time.sleep(1)
    print()
    cred_report = get_credential_report()
    col_count = 3
    print(f"Got credentials report. Showing only the first {col_count} columns.")
    cred_lines = [
        line.split(",")[:col_count] for line in
 cred_report.decode("utf-8").split("\n")
    ]
    col_width = max([len(item) for line in cred_lines for item in line]) + 2
    for line in cred_report.decode("utf-8").split("\n"):
        print(
            "".join(element.ljust(col_width) for element in line.split(",")
[:col_count])
        )

    print("-" * 88)
    print("Let's get an account summary.")
    summary = get_summary()
    print("Here's your summary:")
    pprint.pprint(summary)

    print("-" * 88)
    print("Let's get authorization details!")
    details = get_authorization_details([])
    see_details = input("These are pretty long, do you want to see them (y/n)? ")
    if see_details.lower() == "y":
        pprint.pprint(details)

    print("-" * 88)
    pw_policy_created = None
    see_pw_policy = input("Want to see the password policy for the account (y/n)? ")
    if see_pw_policy.lower() == "y":
        while True:
            if print_password_policy():
                break
            else:
                answer = input(
                    "Do you want to create a default password policy (y/n)? "
                )
                if answer.lower() == "y":
                    pw_policy_created = iam.create_account_password_policy()
                else:
```

```
                    break
    if pw_policy_created is not None:
        answer = input("Do you want to delete the password policy (y/n)? ")
        if answer.lower() == "y":
            pw_policy_created.delete()
            print("Password policy deleted.")

    print("The SAML providers for your account are:")
    list_saml_providers(10)

    print("-" * 88)
    print("Thanks for watching.")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateAccountAlias
  - DeleteAccountAlias
  - GenerateCredentialReport
  - GetAccountAuthorizationDetails
  - GetAccountSummary
  - GetCredentialReport
  - ListAccountAliases

Reverter uma versão de política

O código de exemplo a seguir mostra como:

- Obter a lista de versões da política em ordem por data.
- Encontrar a versão da política padrão.
- Tornar a versão da política anterior a padrão.
- Excluir a versão padrão antiga.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def rollback_policy_version(policy_arn):
    """
    Rolls back to the previous default policy, if it exists.

    1. Gets the list of policy versions in order by date.
    2. Finds the default.
    3. Makes the previous policy the default.
    4. Deletes the old default version.

    :param policy_arn: The ARN of the policy to roll back.
    :return: The default version of the policy after the rollback.
    """
    try:
        policy_versions = sorted(
            iam.Policy(policy_arn).versions.all(),
            key=operator.attrgetter("create_date"),
        )
        logger.info("Got %s versions for %s.", len(policy_versions), policy_arn)
    except ClientError:
        logger.exception("Couldn't get versions for %s.", policy_arn)
        raise

    default_version = None
    rollback_version = None
    try:
        while default_version is None:
            ver = policy_versions.pop()
            if ver.is_default_version:
                default_version = ver
        rollback_version = policy_versions.pop()
        rollback_version.set_as_default()
        logger.info("Set %s as the default version.", rollback_version.version_id)
        default_version.delete()
```

```
        logger.info("Deleted original default version %s.",
default_version.version_id)
    except IndexError:
        if default_version is None:
            logger.warning("No default version found for %s.", policy_arn)
        elif rollback_version is None:
            logger.warning(
                "Default version %s found for %s, but no previous version exists, so
"
                "nothing to roll back to.",
                default_version.version_id,
                policy_arn,
            )
    except ClientError:
        logger.exception("Couldn't roll back version for %s.", policy_arn)
        raise
    else:
        return rollback_version
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeletePolicyVersion
  - ListPolicyVersions
  - SetDefaultPolicyVersion

Exemplos do Amazon Keyspaces usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Keyspaces.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Amazon Keyspaces

O exemplo de código a seguir mostra como começar a usar o Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_keyspaces(keyspaces_client):
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Keyspaces (for Apache
 Cassandra)
    client and list the keyspaces in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param keyspaces_client: A Boto3 Amazon Keyspaces Client object. This object
 wraps
                             the low-level Amazon Keyspaces service API.
    """
    print("Hello, Amazon Keyspaces! Let's list some of your keyspaces:\n")
    for ks in keyspaces_client.list_keyspaces(maxResults=5).get("keyspaces", []):
        print(ks["keyspaceName"])
        print(f"\t{ks['resourceArn']}")


if __name__ == "__main__":
    hello_keyspaces(boto3.client("keyspaces"))
```

- Para obter detalhes da API, consulte a ListKeyspacesReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Criar um espaço de chaves

Os exemplos de código a seguir mostram como criar um espaço de chave do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)
```

```
    def create_keyspace(self, name):
        """
        Creates a keyspace.

        :param name: The name to give the keyspace.
        :return: The Amazon Resource Name (ARN) of the new keyspace.
        """
        try:
            response = self.keyspaces_client.create_keyspace(keyspaceName=name)
            self.ks_name = name
            self.ks_arn = response["resourceArn"]
        except ClientError as err:
            logger.error(
                "Couldn't create %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.ks_arn
```

- Para obter detalhes da API, consulte a CreateKeyspaceReferência da API AWSSDK for Python (Boto3).

Criar uma tabela

Os exemplos de código a seguir mostram como criar uma tabela do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""
```

```
    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def create_table(self, table_name):
        """
        Creates a table in the  keyspace.
        The table is created with a schema for storing movie data
        and has point-in-time recovery enabled.

        :param table_name: The name to give the table.
        :return: The ARN of the new table.
        """
        try:
            response = self.keyspaces_client.create_table(
                keyspaceName=self.ks_name,
                tableName=table_name,
                schemaDefinition={
                    "allColumns": [
                        {"name": "title", "type": "text"},
                        {"name": "year", "type": "int"},
                        {"name": "release_date", "type": "timestamp"},
                        {"name": "plot", "type": "text"},
                    ],
                    "partitionKeys": [{"name": "year"}, {"name": "title"}],
                },
                pointInTimeRecovery={"status": "ENABLED"},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["resourceArn"]
```

- Para obter detalhes da API, consulte a CreateTableReferência da API AWSSDK for Python (Boto3).

Excluir um keyspace

O exemplo de código a seguir mostra como excluir um espaço de chaves do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)
```

```
    def delete_keyspace(self):
        """
        Deletes the keyspace.
        """
        try:
            self.keyspaces_client.delete_keyspace(keyspaceName=self.ks_name)
            self.ks_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteKeyspaceReferência da API AWSSDK for Python (Boto3).

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
```

```
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def delete_table(self):
        """
        Deletes the table from the keyspace.
        """
        try:
            self.keyspaces_client.delete_table(
                keyspaceName=self.ks_name, tableName=self.table_name
            )
            self.table_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTableReferência da API AWSSDK for Python (Boto3).

Obter dados sobre um keyspace

O exemplo de código a seguir mostra como obter dados sobre um keyspace do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def exists_keyspace(self, name):
        """
        Checks whether a keyspace exists.

        :param name: The name of the keyspace to look up.
        :return: True when the keyspace exists. Otherwise, False.
        """
        try:
            response = self.keyspaces_client.get_keyspace(keyspaceName=name)
            self.ks_name = response["keyspaceName"]
            self.ks_arn = response["resourceArn"]
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Keyspace %s does not exist.", name)
```

```
                exists = False
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return exists
```

- Para obter detalhes da API, consulte a GetKeyspaceReferência da API AWSSDK for Python (Boto3).

Obter dados sobre uma tabela

O exemplo de código a seguir mostra como obter dados sobre uma tabela do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None
```

```
    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def get_table(self, table_name):
        """
        Gets data about a table in the keyspace.

        :param table_name: The name of the table to look up.
        :return: Data about the table.
        """
        try:
            response = self.keyspaces_client.get_table(
                keyspaceName=self.ks_name, tableName=table_name
            )
            self.table_name = table_name
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Table %s does not exist.", table_name)
                self.table_name = None
                response = None
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response
```

- Para obter detalhes da API, consulte a GetTableReferência da API AWSSDK for Python (Boto3).

Listar espaços de chaves

O exemplo de código a seguir mostra como listar espaços de chaves do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def list_keyspaces(self, limit):
        """
        Lists the keyspaces in your account.

        :param limit: The maximum number of keyspaces to list.
        """
        try:
            ks_paginator = self.keyspaces_client.get_paginator("list_keyspaces")
            for page in ks_paginator.paginate(PaginationConfig={"MaxItems": limit}):
                for ks in page["keyspaces"]:
                    print(ks["keyspaceName"])
                    print(f"\t{ks['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list keyspaces. Here's why: %s: %s",
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListKeyspacesReferência da API AWSSDK for Python (Boto3).

Listar tabelas em um keyspace

O exemplo de código a seguir mostra como listar tabelas do Amazon Keyspaces em um espaço de chave.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)
```

```
    def list_tables(self):
        """
        Lists the tables in the keyspace.
        """
        try:
            table_paginator = self.keyspaces_client.get_paginator("list_tables")
            for page in table_paginator.paginate(keyspaceName=self.ks_name):
                for table in page["tables"]:
                    print(table["tableName"])
                    print(f"\t{table['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list tables in keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListTablesReferência da API AWSSDK for Python (Boto3).

Restaurar uma tabela para um ponto no tempo

O exemplo de código a seguir mostra como restaurar uma tabela do Amazon Keyspaces em um determinado momento.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""
```

```
    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def restore_table(self, restore_timestamp):
        """
        Restores the table to a previous point in time. The table is restored
        to a new table in the same keyspace.

        :param restore_timestamp: The point in time to restore the table. This time
                                  must be in UTC format.
        :return: The name of the restored table.
        """
        try:
            restored_table_name = f"{self.table_name}_restored"
            self.keyspaces_client.restore_table(
                sourceKeyspaceName=self.ks_name,
                sourceTableName=self.table_name,
                targetKeyspaceName=self.ks_name,
                targetTableName=restored_table_name,
                restoreTimestamp=restore_timestamp,
            )
        except ClientError as err:
            logger.error(
                "Couldn't restore table %s. Here's why: %s: %s",
                restore_timestamp,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return restored_table_name
```

- Para obter detalhes da API, consulte a RestoreTableReferência da API AWSSDK for Python (Boto3).

Atualizar uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do Amazon Keyspaces.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None

    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def update_table(self):
        """
        Updates the schema of the table.
```

```
        This example updates a table of movie data by adding a new column
        that tracks whether the movie has been watched.
        """
        try:
            self.keyspaces_client.update_table(
                keyspaceName=self.ks_name,
                tableName=self.table_name,
                addColumns=[{"name": "watched", "type": "boolean"}],
            )
        except ClientError as err:
            logger.error(
                "Couldn't update table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a UpdateTableReferência da API AWSSDK for Python (Boto3).

Cenários

Começar a usar espaços de chaves e tabelas

O código de exemplo a seguir mostra como:

- Criar um keyspace e uma tabela. O esquema da tabela contém dados do filme e tem a point-in-time recuperação ativada.
- Conectar-se ao espaço de chaves usando uma conexão TLS segura com autenticação SigV4.
- Consulte a tabela. Adicionar recuperar e atualizar dados do filme.
- Atualizar tabela. Adicionar uma coluna para rastrear os filmes assistidos.
- Restaurar a tabela ao estado anterior e limpar os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class KeyspaceScenario:
    """Runs an interactive scenario that shows how to get started using Amazon
 Keyspaces."""

    def __init__(self, ks_wrapper):
        """
        :param ks_wrapper: An object that wraps Amazon Keyspace actions.
        """
        self.ks_wrapper = ks_wrapper

    @demo_func
    def create_keyspace(self):
        """
        1. Creates a keyspace.
        2. Lists up to 10 keyspaces in your account.
        """
        print("Let's create a keyspace.")
        ks_name = q.ask(
            "Enter a name for your new keyspace.\nThe name can contain only letters,
 "
            "numbers and underscores: ",
            q.non_empty,
        )
        if self.ks_wrapper.exists_keyspace(ks_name):
            print(f"A keyspace named {ks_name} exists.")
        else:
            ks_arn = self.ks_wrapper.create_keyspace(ks_name)
            ks_exists = False
            while not ks_exists:
                wait(3)
                ks_exists = self.ks_wrapper.exists_keyspace(ks_name)
            print(f"Created a new keyspace.\n\t{ks_arn}.")
        print("The first 10 keyspaces in your account are:\n")
```

```
        self.ks_wrapper.list_keyspaces(10)

    @demo_func
    def create_table(self):
        """
        1. Creates a table in the keyspace. The table is configured with a schema to
hold
           movie data and has point-in-time recovery enabled.
        2. Waits for the table to be in an active state.
        3. Displays schema information for the table.
        4. Lists tables in the keyspace.
        """
        print("Let's create a table for movies in your keyspace.")
        table_name = q.ask("Enter a name for your table: ", q.non_empty)
        table = self.ks_wrapper.get_table(table_name)
        if table is not None:
            print(
                f"A table named {table_name} already exists in keyspace "
                f"{self.ks_wrapper.ks_name}."
            )
        else:
            table_arn = self.ks_wrapper.create_table(table_name)
            print(f"Created table {table_name}:\n\t{table_arn}")
            table = {"status": None}
            print("Waiting for your table to be ready...")
            while table["status"] != "ACTIVE":
                wait(5)
                table = self.ks_wrapper.get_table(table_name)
        print(f"Your table is {table['status']}. Its schema is:")
        pp(table["schemaDefinition"])
        print("\nThe tables in your keyspace are:\n")
        self.ks_wrapper.list_tables()

    @demo_func
    def ensure_tls_cert(self):
        """
        Ensures you have a TLS certificate available to use to secure the connection
        to the keyspace. This function downloads a default certificate or lets you
        specify your own.
        """
        print("To connect to your keyspace, you must have a TLS certificate.")
        print("Checking for TLS certificate...")
        cert_path = os.path.join(
            os.path.dirname(__file__), QueryManager.DEFAULT_CERT_FILE
```

```
        )
        if not os.path.exists(cert_path):
            cert_choice = q.ask(
                f"Press enter to download a certificate from {QueryManager.CERT_URL}
"
                f"or enter the full path to the certificate you want to use: "
            )
            if cert_choice:
                cert_path = cert_choice
            else:
                cert = requests.get(QueryManager.CERT_URL).text
                with open(cert_path, "w") as cert_file:
                    cert_file.write(cert)
        else:
            q.ask(f"Certificate {cert_path} found. Press Enter to continue.")
        print(
            f"Certificate {cert_path} will be used to secure the connection to your
keyspace."
        )
        return cert_path

    @demo_func
    def query_table(self, qm, movie_file):
        """
        1. Adds movies to the table from a sample movie data file.
        2. Gets a list of movies from the table and lets you select one.
        3. Displays more information about the selected movie.
        """
        qm.add_movies(self.ks_wrapper.table_name, movie_file)
        movies = qm.get_movies(self.ks_wrapper.table_name)
        print(f"Added {len(movies)} movies to the table:")
        sel = q.choose("Pick one to learn more about it: ", [m.title for m in
movies])
        movie_choice = qm.get_movie(
            self.ks_wrapper.table_name, movies[sel].title, movies[sel].year
        )
        print(movie_choice.title)
        print(f"\tReleased: {movie_choice.release_date}")
        print(f"\tPlot: {movie_choice.plot}")

    @demo_func
    def update_and_restore_table(self, qm):
        """
        1. Updates the table by adding a column to track watched movies.
```

```
        2. Marks some of the movies as watched.
        3. Gets the list of watched movies from the table.
        4. Restores to a movies_restored table at a previous point in time.
        5. Gets the list of movies from the restored table.
        """
        print("Let's add a column to record which movies you've watched.")
        pre_update_timestamp = datetime.utcnow()
        print(
            f"Recorded the current UTC time of {pre_update_timestamp} so we can
 restore the table later."
        )
        self.ks_wrapper.update_table()
        print("Waiting for your table to update...")
        table = {"status": "UPDATING"}
        while table["status"] != "ACTIVE":
            wait(5)
            table = self.ks_wrapper.get_table(self.ks_wrapper.table_name)
        print("Column 'watched' added to table.")
        q.ask(
            "Let's mark some of the movies as watched. Press Enter when you're
 ready.\n"
        )
        movies = qm.get_movies(self.ks_wrapper.table_name)
        for movie in movies[:10]:
            qm.watched_movie(self.ks_wrapper.table_name, movie.title, movie.year)
            print(f"Marked {movie.title} as watched.")
        movies = qm.get_movies(self.ks_wrapper.table_name, watched=True)
        print("-" * 88)
        print("The watched movies in our table are:\n")
        for movie in movies:
            print(movie.title)
        print("-" * 88)
        if q.ask(
            "Do you want to restore the table to the way it was before all of these
\n"
            "updates? Keep in mind, this can take up to 20 minutes. (y/n) ",
            q.is_yesno,
        ):
            starting_table_name = self.ks_wrapper.table_name
            table_name_restored =
 self.ks_wrapper.restore_table(pre_update_timestamp)
            table = {"status": "RESTORING"}
            while table["status"] != "ACTIVE":
                wait(10)
```

```
                table = self.ks_wrapper.get_table(table_name_restored)
            print(
                f"Restored {starting_table_name} to {table_name_restored} "
                f"at a point in time of {pre_update_timestamp}."
            )
            movies = qm.get_movies(table_name_restored)
            print("Now the movies in our table are:")
            for movie in movies:
                print(movie.title)

    def cleanup(self, cert_path):
        """
        1. Deletes the table and waits for it to be removed.
        2. Deletes the keyspace.

        :param cert_path: The path of the TLS certificate used in the demo. If the
                          certificate was downloaded during the demo, it is removed.
        """
        if q.ask(
            f"Do you want to delete your {self.ks_wrapper.table_name} table and "
            f"{self.ks_wrapper.ks_name} keyspace? (y/n) ",
            q.is_yesno,
        ):
            table_name = self.ks_wrapper.table_name
            self.ks_wrapper.delete_table()
            table = self.ks_wrapper.get_table(table_name)
            print("Waiting for the table to be deleted.")
            while table is not None:
                wait(5)
                table = self.ks_wrapper.get_table(table_name)
            print("Table deleted.")
            self.ks_wrapper.delete_keyspace()
            print(
                "Keyspace deleted. If you chose to restore your table during the "
                "demo, the original table is also deleted."
            )
            if cert_path == os.path.join(
                os.path.dirname(__file__), QueryManager.DEFAULT_CERT_FILE
            ) and os.path.exists(cert_path):
                os.remove(cert_path)
                print("Removed certificate that was downloaded for this demo.")

    def run_scenario(self):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
```

```
        print("-" * 88)
        print("Welcome to the Amazon Keyspaces (for Apache Cassandra) demo.")
        print("-" * 88)

        self.create_keyspace()
        self.create_table()
        cert_file_path = self.ensure_tls_cert()
        # Use a context manager to ensure the connection to the keyspace is closed.
        with QueryManager(
            cert_file_path, boto3.DEFAULT_SESSION, self.ks_wrapper.ks_name
        ) as qm:
            self.query_table(qm, "../../../resources/sample_files/movies.json")
            self.update_and_restore_table(qm)
        self.cleanup(cert_file_path)

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = KeyspaceScenario(KeyspaceWrapper.from_client())
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina uma classe que envolva as ações de tabelas e de espaço de chaves.

```
class KeyspaceWrapper:
    """Encapsulates Amazon Keyspaces (for Apache Cassandra) keyspace and table
 actions."""

    def __init__(self, keyspaces_client):
        """
        :param keyspaces_client: A Boto3 Amazon Keyspaces client.
        """
        self.keyspaces_client = keyspaces_client
        self.ks_name = None
        self.ks_arn = None
        self.table_name = None
```

```
    @classmethod
    def from_client(cls):
        keyspaces_client = boto3.client("keyspaces")
        return cls(keyspaces_client)


    def create_keyspace(self, name):
        """
        Creates a keyspace.

        :param name: The name to give the keyspace.
        :return: The Amazon Resource Name (ARN) of the new keyspace.
        """
        try:
            response = self.keyspaces_client.create_keyspace(keyspaceName=name)
            self.ks_name = name
            self.ks_arn = response["resourceArn"]
        except ClientError as err:
            logger.error(
                "Couldn't create %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return self.ks_arn


    def exists_keyspace(self, name):
        """
        Checks whether a keyspace exists.

        :param name: The name of the keyspace to look up.
        :return: True when the keyspace exists. Otherwise, False.
        """
        try:
            response = self.keyspaces_client.get_keyspace(keyspaceName=name)
            self.ks_name = response["keyspaceName"]
            self.ks_arn = response["resourceArn"]
            exists = True
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Keyspace %s does not exist.", name)
```

```
                exists = False
            else:
                logger.error(
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return exists


    def list_keyspaces(self, limit):
        """
        Lists the keyspaces in your account.

        :param limit: The maximum number of keyspaces to list.
        """
        try:
            ks_paginator = self.keyspaces_client.get_paginator("list_keyspaces")
            for page in ks_paginator.paginate(PaginationConfig={"MaxItems": limit}):
                for ks in page["keyspaces"]:
                    print(ks["keyspaceName"])
                    print(f"\t{ks['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list keyspaces. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Message"],
            )
            raise


    def create_table(self, table_name):
        """
        Creates a table in the  keyspace.
        The table is created with a schema for storing movie data
        and has point-in-time recovery enabled.

        :param table_name: The name to give the table.
        :return: The ARN of the new table.
        """
        try:
            response = self.keyspaces_client.create_table(
```

```
                keyspaceName=self.ks_name,
                tableName=table_name,
                schemaDefinition={
                    "allColumns": [
                        {"name": "title", "type": "text"},
                        {"name": "year", "type": "int"},
                        {"name": "release_date", "type": "timestamp"},
                        {"name": "plot", "type": "text"},
                    ],
                    "partitionKeys": [{"name": "year"}, {"name": "title"}],
                },
                pointInTimeRecovery={"status": "ENABLED"},
            )
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["resourceArn"]


    def get_table(self, table_name):
        """
        Gets data about a table in the keyspace.

        :param table_name: The name of the table to look up.
        :return: Data about the table.
        """
        try:
            response = self.keyspaces_client.get_table(
                keyspaceName=self.ks_name, tableName=table_name
            )
            self.table_name = table_name
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Table %s does not exist.", table_name)
                self.table_name = None
                response = None
            else:
                logger.error(
```

```
                    "Couldn't verify %s exists. Here's why: %s: %s",
                    table_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response


    def list_tables(self):
        """
        Lists the tables in the keyspace.
        """
        try:
            table_paginator = self.keyspaces_client.get_paginator("list_tables")
            for page in table_paginator.paginate(keyspaceName=self.ks_name):
                for table in page["tables"]:
                    print(table["tableName"])
                    print(f"\t{table['resourceArn']}")
        except ClientError as err:
            logger.error(
                "Couldn't list tables in keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def update_table(self):
        """
        Updates the schema of the table.

        This example updates a table of movie data by adding a new column
        that tracks whether the movie has been watched.
        """
        try:
            self.keyspaces_client.update_table(
                keyspaceName=self.ks_name,
                tableName=self.table_name,
                addColumns=[{"name": "watched", "type": "boolean"}],
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't update table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def restore_table(self, restore_timestamp):
        """
        Restores the table to a previous point in time. The table is restored
        to a new table in the same keyspace.

        :param restore_timestamp: The point in time to restore the table. This time
                                  must be in UTC format.
        :return: The name of the restored table.
        """
        try:
            restored_table_name = f"{self.table_name}_restored"
            self.keyspaces_client.restore_table(
                sourceKeyspaceName=self.ks_name,
                sourceTableName=self.table_name,
                targetKeyspaceName=self.ks_name,
                targetTableName=restored_table_name,
                restoreTimestamp=restore_timestamp,
            )
        except ClientError as err:
            logger.error(
                "Couldn't restore table %s. Here's why: %s: %s",
                restore_timestamp,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return restored_table_name


    def delete_table(self):
        """
        Deletes the table from the keyspace.
        """
        try:
            self.keyspaces_client.delete_table(
```

```
                keyspaceName=self.ks_name, tableName=self.table_name
            )
            self.table_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete table %s. Here's why: %s: %s",
                self.table_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete_keyspace(self):
        """
        Deletes the keyspace.
        """
        try:
            self.keyspaces_client.delete_keyspace(keyspaceName=self.ks_name)
            self.ks_name = None
        except ClientError as err:
            logger.error(
                "Couldn't delete keyspace %s. Here's why: %s: %s",
                self.ks_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Defina uma classe que crie uma conexão TLS com um espaço de chaves, autentique com SigV4 e envie consultas CQL para uma tabela no espaço de chaves.

```
class QueryManager:
    """
    Manages queries to an Amazon Keyspaces (for Apache Cassandra) keyspace.
    Queries are secured by TLS and authenticated by using the Signature V4 (SigV4)
    AWS signing protocol. This is more secure than sending username and password
    with a plain-text authentication provider.
```

```
    This example downloads a default certificate to secure TLS, or lets you specify
    your own.

    This example uses a table of movie data to demonstrate basic queries.
    """

    DEFAULT_CERT_FILE = "sf-class2-root.crt"
    CERT_URL = f"https://certs.secureserver.net/repository/sf-class2-root.crt"

    def __init__(self, cert_file_path, boto_session, keyspace_name):
        """
        :param cert_file_path: The path and file name of the certificate used for
TLS.
        :param boto_session: A Boto3 session. This is used to acquire your AWS
credentials.
        :param keyspace_name: The name of the keyspace to connect.
        """
        self.cert_file_path = cert_file_path
        self.boto_session = boto_session
        self.ks_name = keyspace_name
        self.cluster = None
        self.session = None

    def __enter__(self):
        """
        Creates a session connection to the keyspace that is secured by TLS and
        authenticated by SigV4.
        """
        ssl_context = SSLContext(PROTOCOL_TLSv1_2)
        ssl_context.load_verify_locations(self.cert_file_path)
        ssl_context.verify_mode = CERT_REQUIRED
        auth_provider = SigV4AuthProvider(self.boto_session)
        contact_point = f"cassandra.{self.boto_session.region_name}.amazonaws.com"
        exec_profile = ExecutionProfile(
            consistency_level=ConsistencyLevel.LOCAL_QUORUM,
            load_balancing_policy=DCAwareRoundRobinPolicy(),
        )
        self.cluster = Cluster(
            [contact_point],
            ssl_context=ssl_context,
            auth_provider=auth_provider,
            port=9142,
            execution_profiles={EXEC_PROFILE_DEFAULT: exec_profile},
            protocol_version=4,
```

```
        )
        self.cluster.__enter__()
        self.session = self.cluster.connect(self.ks_name)
        return self

    def __exit__(self, *args):
        """
        Exits the cluster. This shuts down all existing session connections.
        """
        self.cluster.__exit__(*args)

    def add_movies(self, table_name, movie_file_path):
        """
        Gets movies from a JSON file and adds them to a table in the keyspace.

        :param table_name: The name of the table.
        :param movie_file_path: The path and file name of a JSON file that contains
 movie data.
        """
        with open(movie_file_path, "r") as movie_file:
            movies = json.loads(movie_file.read())
        stmt = self.session.prepare(
            f"INSERT INTO {table_name} (year, title, release_date, plot) VALUES
 (?, ?, ?, ?);"
        )
        for movie in movies[:20]:
            self.session.execute(
                stmt,
                parameters=[
                    movie["year"],
                    movie["title"],
                    date.fromisoformat(movie["info"]["release_date"].partition("T")
[0]),
                    movie["info"]["plot"],
                ],
            )

    def get_movies(self, table_name, watched=None):
        """
        Gets the title and year of the full list of movies from the table.

        :param table_name: The name of the movie table.
        :param watched: When specified, the returned list of movies is filtered to
                        either movies that have been watched or movies that have not
```

```
                        been watched. Otherwise, all movies are returned.
        :return: A list of movies in the table.
        """
        if watched is None:
            stmt = SimpleStatement(f"SELECT title, year from {table_name}")
            params = None
        else:
            stmt = SimpleStatement(
                f"SELECT title, year from {table_name} WHERE watched = %s ALLOW
FILTERING"
            )
            params = [watched]
        return self.session.execute(stmt, parameters=params).all()

    def get_movie(self, table_name, title, year):
        """
        Gets a single movie from the table, by title and year.

        :param table_name: The name of the movie table.
        :param title: The title of the movie.
        :param year: The year of the movie's release.
        :return: The requested movie.
        """
        return self.session.execute(
            SimpleStatement(
                f"SELECT * from {table_name} WHERE title = %s AND year = %s"
            ),
            parameters=[title, year],
        ).one()

    def watched_movie(self, table_name, title, year):
        """
        Updates a movie as having been watched.

        :param table_name: The name of the movie table.
        :param title: The title of the movie.
        :param year: The year of the movie's release.
        """
        self.session.execute(
            SimpleStatement(
                f"UPDATE {table_name} SET watched=true WHERE title = %s AND year =
%s"
            ),
            parameters=[title, year],
```

```
        )
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateKeyspace
  - CreateTable
  - DeleteKeyspace
  - DeleteTable
  - GetKeyspace
  - GetTable
  - ListKeyspaces
  - ListTables
  - RestoreTable
  - UpdateTable

Exemplos do Kinesis usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Criar um stream

O exemplo de código a seguir mostra como criar um stream do Kinesis.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def create(self, name, wait_until_exists=True):
        """
        Creates a stream.

        :param name: The name of the stream.
        :param wait_until_exists: When True, waits until the service reports that
                                  the stream exists, then queries for its metadata.
        """
        try:
            self.kinesis_client.create_stream(StreamName=name, ShardCount=1)
            self.name = name
            logger.info("Created stream %s.", name)
            if wait_until_exists:
                logger.info("Waiting until exists.")
                self.stream_exists_waiter.wait(StreamName=name)
                self.describe(name)
```

```
        except ClientError:
            logger.exception("Couldn't create stream %s.", name)
            raise
```

- Para obter detalhes da API, consulte a CreateStreamReferência da API AWSSDK for Python (Boto3).

Excluir um stream

O exemplo de código a seguir mostra como excluir um stream do Kinesis.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def delete(self):
        """
        Deletes a stream.
        """
        try:
            self.kinesis_client.delete_stream(StreamName=self.name)
            self._clear()
            logger.info("Deleted stream %s.", self.name)
```

```
        except ClientError:
            logger.exception("Couldn't delete stream %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteStreamReferência da API AWSSDK for Python (Boto3).

Descrever um stream

O exemplo de código a seguir mostra como descrever um stream do Kinesis.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def describe(self, name):
        """
        Gets metadata about a stream.

        :param name: The name of the stream.
        :return: Metadata about the stream.
        """
```

```
        try:
            response = self.kinesis_client.describe_stream(StreamName=name)
            self.name = name
            self.details = response["StreamDescription"]
            logger.info("Got stream %s.", name)
        except ClientError:
            logger.exception("Couldn't get %s.", name)
            raise
        else:
            return self.details
```

- Para obter detalhes da API, consulte a DescribeStreamReferência da API AWSSDK for Python (Boto3).

Obter dados em lotes de um stream

O exemplo de código a seguir mostra como obter dados em lotes de um stream do Kinesis.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")
```

```
    def get_records(self, max_records):
        """
        Gets records from the stream. This function is a generator that first gets
        a shard iterator for the stream, then uses the shard iterator to get records
        in batches from the stream. Each batch of records is yielded back to the
        caller until the specified maximum number of records has been retrieved.

        :param max_records: The maximum number of records to retrieve.
        :return: Yields the current batch of retrieved records.
        """
        try:
            response = self.kinesis_client.get_shard_iterator(
                StreamName=self.name,
                ShardId=self.details["Shards"][0]["ShardId"],
                ShardIteratorType="LATEST",
            )
            shard_iter = response["ShardIterator"]
            record_count = 0
            while record_count < max_records:
                response = self.kinesis_client.get_records(
                    ShardIterator=shard_iter, Limit=10
                )
                shard_iter = response["NextShardIterator"]
                records = response["Records"]
                logger.info("Got %s records.", len(records))
                record_count += len(records)
                yield records
        except ClientError:
            logger.exception("Couldn't get records from stream %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - GetRecords
  - GetShardIterator

Inserir dados em um stream

O exemplo de código a seguir mostra como inserir dados em um stream do Kinesis.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisStream:
    """Encapsulates a Kinesis stream."""

    def __init__(self, kinesis_client):
        """
        :param kinesis_client: A Boto3 Kinesis client.
        """
        self.kinesis_client = kinesis_client
        self.name = None
        self.details = None
        self.stream_exists_waiter = kinesis_client.get_waiter("stream_exists")


    def put_record(self, data, partition_key):
        """
        Puts data into the stream. The data is formatted as JSON before it is passed
        to the stream.

        :param data: The data to put in the stream.
        :param partition_key: The partition key to use for the data.
        :return: Metadata about the record, including its shard ID and sequence
 number.
        """
        try:
            response = self.kinesis_client.put_record(
                StreamName=self.name, Data=json.dumps(data),
 PartitionKey=partition_key
            )
            logger.info("Put record in stream %s.", self.name)
        except ClientError:
            logger.exception("Couldn't put record in stream %s.", self.name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a PutRecordReferência da API AWSSDK for Python (Boto3).

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Python.

```
import base64
def lambda_handler(event, context):

    for record in event['Records']:
        try:
            print(f"Processed Kinesis Event - EventID: {record['eventID']}")
            record_data = base64.b64decode(record['kinesis']
['data']).decode('utf-8')
            print(f"Record Data: {record_data}")
            # TODO: Do interesting work based on the new data
        except Exception as e:
            print(f"An error occurred {e}")
            raise e
    print(f"Successfully processed {len(event['Records'])} records.")
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Python.

```
def handler(event, context):
    records = event.get("Records")
    curRecordSequenceNumber = ""

    for record in records:
        try:
            # Process your record
            curRecordSequenceNumber = record["kinesis"]["sequenceNumber"]
        except Exception as e:
            # Return failed record's sequence number
            return {"batchItemFailures":[{"itemIdentifier":
 curRecordSequenceNumber}]}

    return {"batchItemFailures":[]}
```

Exemplos de AWS KMS usando o SDK para Python (Boto3)

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma concessão para uma chave

O exemplo de código a seguir mostra como criar uma concessão para uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def create_grant(self, key_id):
        """
        Creates a grant for a key that lets a principal generate a symmetric data
        encryption key.

        :param key_id: The ARN or ID of the key.
        :return: The grant that is created.
        """
        principal = input(
            f"Enter the ARN of a principal, such as an IAM role, to grant that role
 "
            f"GenerateDataKey permissions on key {key_id}: "
```

```
        )
        if principal != "":
            try:
                grant = self.kms_client.create_grant(
                    KeyId=key_id,
                    GranteePrincipal=principal,
                    Operations=["GenerateDataKey"],
                )
            except ClientError as err:
                logger.error(
                    "Couldn't create a grant on key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Grant created on key {key_id}.")
                return grant
        else:
            print("Skipping grant creation.")
```

- Para obter detalhes da API, consulte a CreateGrantReferência da API AWSSDK for Python (Boto3).

Criar uma chave

O exemplo de código a seguir mostra como criar AWS KMS key.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []
```

```
    def create_key(self):
        """
        Creates a key (or multiple keys) with a user-provided description.
        """
        answer = "y"
        while answer.lower() == "y":
            key_desc = input("\nLet's create a key. Describe it for me: ")
            if not key_desc:
                key_desc = "Key management demo key"
            try:
                key = self.kms_client.create_key(Description=key_desc)
["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't create your key. Here's why: %s",
                    err.response["Error"]["Message"],
                )
                raise
            else:
                print("Key created:")
                pprint(key)
                self.created_keys.append(key)
                answer = input("Create another (y/n)? ")
```

- Para obter detalhes da API, consulte a CreateKeyReferência da API AWSSDK for Python (Boto3).

Criar um alias para uma chave

O exemplo de código a seguir mostra como criar um alias para uma chave do KMS Key.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def create_alias(self, key_id):
        """
        Creates an alias for the specified key.

        :param key_id: The ARN or ID of a key to give an alias.
        :return: The alias given to the key.
        """
        alias = ""
        while alias == "":
            alias = input(f"What alias would you like to give to key {key_id}? ")
        try:
            self.kms_client.create_alias(AliasName=alias, TargetKeyId=key_id)
        except ClientError as err:
            logger.error(
                "Couldn't create alias %s. Here's why: %s",
                alias,
                err.response["Error"]["Message"],
            )
        else:
            print(f"Created alias {alias} for key {key_id}.")
            return alias
```

- Para obter detalhes da API, consulte a CreateAliasReferência da API AWSSDK for Python (Boto3).

Descriptografar texto cifrado

O exemplo de código a seguir mostra como descriptografar texto cifrado que foi criptografado com uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def decrypt(self, key_id, cipher_text):
        """
        Decrypts text previously encrypted with a key.

        :param key_id: The ARN or ID of the key used to decrypt the data.
        :param cipher_text: The encrypted text to decrypt.
        """
        answer = input("Ready to decrypt your ciphertext (y/n)? ")
        if answer.lower() == "y":
            try:
                text = self.kms_client.decrypt(
                    KeyId=key_id, CiphertextBlob=cipher_text
                )["Plaintext"]
            except ClientError as err:
                logger.error(
                    "Couldn't decrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Your plaintext is {text.decode()}")
        else:
            print("Skipping decryption demo.")
```

- Para obter detalhes da API, consulte Descriptografar na AWS Referência da API SDK para Python (Boto3).

Excluir um alias

O exemplo de código a seguir mostra como excluir um alias do AWS KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def delete_alias(self):
        """
        Deletes an alias.
        """
        alias = input(f"Enter an alias that you'd like to delete: ")
        if alias != "":
            try:
                self.kms_client.delete_alias(AliasName=alias)
            except ClientError as err:
                logger.error(
                    "Couldn't delete alias %s. Here's why: %s",
                    alias,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Deleted alias {alias}.")
        else:
            print("Skipping alias deletion.")
```

- Para obter detalhes da API, consulte a DeleteAliasReferência da API AWSSDK for Python (Boto3).

Descrever uma chave

O exemplo de código a seguir mostra como descrever uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def describe_key(self):
        """
        Describes a key.
        """
        key_id = input("Enter a key ID or ARN here to get information about the key:
 ")
        if key_id:
            try:
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't get key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Got key {key_id}:")
                pprint(key)
        return key_id
```

- Para obter detalhes da API, consulte a DescribeKeyReferência da API AWSSDK for Python (Boto3).

Desabilitar uma chave

O exemplo de código a seguir mostra como desativar uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")

            try:
                self.kms_client.enable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't enable key '%s'. Here's why: %s",
                    key_id,
```

```
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")
```

- Para obter detalhes da API, consulte a DisableKeyReferência da API AWSSDK for Python (Boto3).

Habilitar uma chave

O exemplo de código a seguir mostra como habilitar uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
```

```
            )
        else:
            print(f"AWS KMS says your key state is: {key['KeyState']}.")

        try:
            self.kms_client.enable_key(KeyId=key_id)
            key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
        except ClientError as err:
            logging.error(
                "Couldn't enable key '%s'. Here's why: %s",
                key_id,
                err.response["Error"]["Message"],
            )
        else:
            print(f"AWS KMS says your key state is: {key['KeyState']}.")
```

- Para obter detalhes da API, consulte a EnableKeyReferência da API AWSSDK for Python (Boto3).

Criptografar texto usando uma chave

O exemplo de código a seguir mostra como criptografar texto usando uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def encrypt(self, key_id):
        """
        Encrypts text by using the specified key.
```

```
        :param key_id: The ARN or ID of the key to use for encryption.
        :return: The encrypted version of the text.
        """
        text = input("Enter some text to encrypt: ")
        try:
            cipher_text = self.kms_client.encrypt(
                KeyId=key_id, Plaintext=text.encode()
            )["CiphertextBlob"]
        except ClientError as err:
            logger.error(
                "Couldn't encrypt text. Here's why: %s",
                err.response["Error"]["Message"],
            )
        else:
            print(f"Your ciphertext is: {cipher_text}")
            return cipher_text
```

- Para obter detalhes da API, consulte Criptografar na AWS Referência da API SDK para Python (Boto3).

Gerar uma chave de dados em texto sem formatação para criptografia do lado do cliente

O exemplo de código a seguir mostra como gerar uma chave de dados simétrica exclusiva para criptografia do lado do cliente a partir de um AWS KMS key. A chave contém versões em texto simples e em texto cifrado.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []
```

```
    def generate_data_key(self, key_id):
        """
        Generates a symmetric data key that can be used for client-side encryption.
        """
        answer = input(
            f"Do you want to generate a symmetric data key from key {key_id} (y/n)?
"
        )
        if answer.lower() == "y":
            try:
                data_key = self.kms_client.generate_data_key(
                    KeyId=key_id, KeySpec="AES_256"
                )
            except ClientError as err:
                logger.error(
                    "Couldn't generate a data key for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(data_key)
```

- Para obter detalhes da API, consulte a GenerateDataKeyReferência da API AWSSDK for Python (Boto3).

Obter uma política para uma chave

O exemplo de código a seguir mostra como obter uma política pelo nome para uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
```

```
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def get_policy(self, key_id):
        """
        Gets the policy of a key.

        :param key_id: The ARN or ID of the key to query.
        :return: The key policy as a dict.
        """
        if key_id != "":
            try:
                response = self.kms_client.get_key_policy(
                    KeyId=key_id, PolicyName="default"
                )
                policy = json.loads(response["Policy"])
            except ClientError as err:
                logger.error(
                    "Couldn't get policy for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(policy)
                return policy
        else:
            print("Skipping get policy demo.")
```

- Para obter detalhes da API, consulte a GetKeyPolicyReferência da API AWSSDK for Python (Boto3).

Listar apelidos para uma chave

Os exemplos de código a seguir mostram como listar aliases para uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None


    def list_aliases(self):
        """
        Lists aliases for the current account.
        """
        answer = input("\nLet's list your key aliases. Ready (y/n)? ")
        if answer.lower() == "y":
            try:
                page_size = 10

                alias_paginator = self.kms_client.get_paginator("list_aliases")
                for alias_page in alias_paginator.paginate(
                    PaginationConfig={"PageSize": 10}
                ):
                    print(f"Here are {page_size} aliases:")
                    pprint(alias_page["Aliases"])
                    if alias_page["Truncated"]:
                        answer = input(
                            f"Do you want to see the next {page_size} aliases (y/n)?
 "
                        )
                        if answer.lower() != "y":
                            break
                    else:
                        print("That's all your aliases!")
            except ClientError as err:
                logging.error(
                    "Couldn't list your aliases. Here's why: %s",
                    err.response["Error"]["Message"],
```

```
                )
```

- Para obter detalhes da API, consulte a ListAliasesReferência da API AWSSDK for Python (Boto3).

Listar concessões para uma chave

O exemplo de código a seguir mostra como listar concessões para uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def list_grants(self, key_id):
        """
        Lists grants for a key.

        :param key_id: The ARN or ID of the key to query.
        :return: The grants for the key.
        """
        answer = input(f"Ready to list grants on key {key_id} (y/n)? ")
        if answer.lower() == "y":
            try:
                grants = self.kms_client.list_grants(KeyId=key_id)["Grants"]
            except ClientError as err:
                logger.error(
                    "Couldn't list grants for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
```

```
                print(f"Grants for key {key_id}:")
                pprint(grants)
                return grants
```

- Para obter detalhes da API, consulte a ListGrantsReferência da API AWSSDK for Python (Boto3).

Listar chaves

O exemplo de código a seguir mostra como listar chaves do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_keys = []


    def list_keys(self):
        """
        Lists the keys for the current account by using a paginator.
        """
        try:
            page_size = 10
            print("\nLet's list your keys.")
            key_paginator = self.kms_client.get_paginator("list_keys")
            for key_page in key_paginator.paginate(PaginationConfig={"PageSize":
 10}):
                print(f"Here are {len(key_page['Keys'])} keys:")
                pprint(key_page["Keys"])
                if key_page["Truncated"]:
                    answer = input(
                        f"Do you want to see the next {page_size} keys (y/n)? "
```

```
                    )
                    if answer.lower() != "y":
                        break
                else:
                    print("That's all your keys!")
        except ClientError as err:
            logging.error(
                "Couldn't list your keys. Here's why: %s",
                err.response["Error"]["Message"],
            )
```

- Para obter detalhes da API, consulte a ListKeysReferência da API AWSSDK for Python (Boto3).

Listar políticas para uma chave

O exemplo de código a seguir mostra como listar políticas para uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def list_policies(self, key_id):
        """
        Lists the names of the policies for a key.

        :param key_id: The ARN or ID of the key to query.
        """
        try:
            policy_names = self.kms_client.list_key_policies(KeyId=key_id)[
                "PolicyNames"
```

```
            ]
        except ClientError as err:
            logging.error(
                "Couldn't list your policies. Here's why: %s",
                err.response["Error"]["Message"],
            )
        else:
            print(f"The policies for key {key_id} are:")
            pprint(policy_names)
```

- Para obter detalhes da API, consulte a ListKeyPoliciesReferência da API AWSSDK for Python (Boto3).

Criptografar novamente o texto cifrado de uma chave para outra

O exemplo de código a seguir mostra como criptografar novamente um texto cifrado de uma chave do KMS para outra.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def re_encrypt(self, source_key_id, cipher_text):
        """
        Takes ciphertext previously encrypted with one key and reencrypt it by using
        another key.

        :param source_key_id: The ARN or ID of the original key used to encrypt the
                              ciphertext.
        :param cipher_text: The encrypted ciphertext.
```

```
        :return: The ciphertext encrypted by the second key.
        """
        destination_key_id = input(
            f"Your ciphertext is currently encrypted with key {source_key_id}. "
            f"Enter another key ID or ARN to reencrypt it: "
        )
        if destination_key_id != "":
            try:
                cipher_text = self.kms_client.re_encrypt(
                    SourceKeyId=source_key_id,
                    DestinationKeyId=destination_key_id,
                    CiphertextBlob=cipher_text,
                )["CiphertextBlob"]
            except ClientError as err:
                logger.error(
                    "Couldn't reencrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Reencrypted your ciphertext as: {cipher_text}")
                return cipher_text
        else:
            print("Skipping reencryption demo.")
```

- Para obter detalhes da API, consulte a ReEncryptReferência da API AWSSDK for Python (Boto3).

Retirar uma concessão para uma chave

O exemplo de código a seguir mostra como retirar uma concessão para uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def retire_grant(self, grant):
        """
        Retires a grant so that it can no longer be used.

        :param grant: The grant to retire.
        """
        try:
            self.kms_client.retire_grant(GrantToken=grant["GrantToken"])
        except ClientError as err:
            logger.error(
                "Couldn't retire grant %s. Here's why: %s",
                grant["GrantId"],
                err.response["Error"]["Message"],
            )
        else:
            print(f"Grant {grant['GrantId']} retired.")
```

- Para obter detalhes da API, consulte a RetireGrantReferência da API AWSSDK for Python (Boto3).

Revogar uma concessão para uma chave

O exemplo de código a seguir mostra como revogar uma concessão para uma chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GrantManager:
    def __init__(self, kms_client):
```

```
        self.kms_client = kms_client


    def revoke_grant(self, key_id, grant):
        """
        Revokes a grant so that it can no longer be used.

        :param key_id: The ARN or ID of the key associated with the grant.
        :param grant: The grant to revoke.
        """
        try:
            self.kms_client.revoke_grant(KeyId=key_id, GrantId=grant["GrantId"])
        except ClientError as err:
            logger.error(
                "Couldn't revoke grant %s. Here's why: %s",
                grant["GrantId"],
                err.response["Error"]["Message"],
            )
        else:
            print(f"Grant {grant['GrantId']} revoked.")
```

- Para obter detalhes da API, consulte a RevokeGrantReferência da API AWSSDK for Python (Boto3).

Programar a exclusão de uma chave

O exemplo de código a seguir mostra como programar a exclusão de uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyManager:
    def __init__(self, kms_client):
```

```
        self.kms_client = kms_client
        self.created_keys = []


    def delete_keys(self, keys):
        """
        Deletes a list of keys.

        :param keys: The list of keys to delete.
        """
        answer = input("Do you want to delete these keys (y/n)? ")
        if answer.lower() == "y":
            window = 7
            for key in keys:
                try:
                    self.kms_client.schedule_key_deletion(
                        KeyId=key["KeyId"], PendingWindowInDays=window
                    )
                except ClientError as err:
                    logging.error(
                        "Couldn't delete key %s. Here's why: %s",
                        key["KeyId"],
                        err.response["Error"]["Message"],
                    )
                else:
                    print(
                        f"Key {key['KeyId']} scheduled for deletion in {window}
days."
                    )
```

- Para obter detalhes da API, consulte a ScheduleKeyDeletionReferência da API AWSSDK for Python (Boto3).

Definir a política para uma chave

O exemplo de código a seguir mostra como definir política para uma chave do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KeyPolicy:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def set_policy(self, key_id, policy):
        """
        Sets the policy of a key. Setting a policy entirely overwrites the existing
        policy, so care is taken to add a statement to the existing list of
 statements
        rather than simply writing a new policy.

        :param key_id: The ARN or ID of the key to set the policy to.
        :param policy: The existing policy of the key.
        """
        principal = input(
            "Enter the ARN of an IAM role to set as the principal on the policy: "
        )
        if key_id != "" and principal != "":
            # The updated policy replaces the existing policy. Add a new statement
 to
            # the list along with the original policy statements.
            policy["Statement"].append(
                {
                    "Sid": "Allow access for ExampleRole",
                    "Effect": "Allow",
                    "Principal": {"AWS": principal},
                    "Action": [
                        "kms:Encrypt",
                        "kms:GenerateDataKey*",
                        "kms:Decrypt",
                        "kms:DescribeKey",
                        "kms:ReEncrypt*",
                    ],
```

```
                    "Resource": "*",
                }
            )
            try:
                self.kms_client.put_key_policy(
                    KeyId=key_id, PolicyName="default", Policy=json.dumps(policy)
                )
            except ClientError as err:
                logger.error(
                    "Couldn't set policy for key %s. Here's why %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Set policy for key {key_id}.")
        else:
            print("Skipping set policy demo.")
```

- Para obter detalhes da API, consulte a PutKeyPolicyReferência da API AWSSDK for Python (Boto3).

Atualizar a chave referida por um alias

O exemplo de código a seguir mostra como atualizar a chave do KMS referida por um alias.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class AliasManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
        self.created_key = None
```

```
    def update_alias(self, alias, current_key_id):
        """
        Updates an alias by assigning it to another key.

        :param alias: The alias to reassign.
        :param current_key_id: The ARN or ID of the key currently associated with
the alias.
        """
        new_key_id = input(
            f"Alias {alias} is currently associated with {current_key_id}. "
            f"Enter another key ID or ARN that you want to associate with {alias}: "
        )
        if new_key_id != "":
            try:
                self.kms_client.update_alias(AliasName=alias,
TargetKeyId=new_key_id)
            except ClientError as err:
                logger.error(
                    "Couldn't associate alias %s with key %s. Here's why: %s",
                    alias,
                    new_key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Alias {alias} is now associated with key {new_key_id}.")
        else:
            print("Skipping alias update.")
```

- Para obter detalhes da API, consulte a UpdateAliasReferência da API AWSSDK for Python (Boto3).

Cenários

Criptografar e descriptografar texto

O código de exemplo a seguir mostra como:

- Criptografr texto sem formatação usando uma chave KMS.
- Decriptografar o texto cifrado usando uma chave KMS.
- Recriptografar texto cifrado usando uma segunda chave KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class KeyEncrypt:
    def __init__(self, kms_client):
        self.kms_client = kms_client


    def encrypt(self, key_id):
        """
        Encrypts text by using the specified key.

        :param key_id: The ARN or ID of the key to use for encryption.
        :return: The encrypted version of the text.
        """
        text = input("Enter some text to encrypt: ")
        try:
            cipher_text = self.kms_client.encrypt(
                KeyId=key_id, Plaintext=text.encode()
            )["CiphertextBlob"]
        except ClientError as err:
            logger.error(
                "Couldn't encrypt text. Here's why: %s",
                err.response["Error"]["Message"],
            )
        else:
            print(f"Your ciphertext is: {cipher_text}")
            return cipher_text
```

```
    def decrypt(self, key_id, cipher_text):
        """
        Decrypts text previously encrypted with a key.

        :param key_id: The ARN or ID of the key used to decrypt the data.
        :param cipher_text: The encrypted text to decrypt.
        """
        answer = input("Ready to decrypt your ciphertext (y/n)? ")
        if answer.lower() == "y":
            try:
                text = self.kms_client.decrypt(
                    KeyId=key_id, CiphertextBlob=cipher_text
                )["Plaintext"]
            except ClientError as err:
                logger.error(
                    "Couldn't decrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Your plaintext is {text.decode()}")
        else:
            print("Skipping decryption demo.")


    def re_encrypt(self, source_key_id, cipher_text):
        """
        Takes ciphertext previously encrypted with one key and reencrypt it by using
        another key.

        :param source_key_id: The ARN or ID of the original key used to encrypt the
                              ciphertext.
        :param cipher_text: The encrypted ciphertext.
        :return: The ciphertext encrypted by the second key.
        """
        destination_key_id = input(
            f"Your ciphertext is currently encrypted with key {source_key_id}. "
            f"Enter another key ID or ARN to reencrypt it: "
        )
        if destination_key_id != "":
            try:
                cipher_text = self.kms_client.re_encrypt(
                    SourceKeyId=source_key_id,
                    DestinationKeyId=destination_key_id,
                    CiphertextBlob=cipher_text,
```

```
                )["CiphertextBlob"]
            except ClientError as err:
                logger.error(
                    "Couldn't reencrypt your ciphertext. Here's why: %s",
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Reencrypted your ciphertext as: {cipher_text}")
                return cipher_text
        else:
            print("Skipping reencryption demo.")




def key_encryption(kms_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the AWS Key Management Service (AWS KMS) key encryption
 demo.")
    print("-" * 88)

    key_id = input("Enter a key ID or ARN to start the demo: ")
    if key_id == "":
        print("A key is required to run this demo.")
        return

    key_encrypt = KeyEncrypt(kms_client)
    cipher_text = key_encrypt.encrypt(key_id)
    print("-" * 88)
    if cipher_text is not None:
        key_encrypt.decrypt(key_id, cipher_text)
        print("-" * 88)
        key_encrypt.re_encrypt(key_id, cipher_text)

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        key_encryption(boto3.client("kms"))
    except Exception:
```

```
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - Decrypt
  - Encrypt
  - ReEncrypt

Gerenciar chaves do

O código de exemplo a seguir mostra como:

- Crie uma chave do KMS.
- Listar chaves KMS para uma conta e obter detalhes sobre elas.
- Habilitar e desabilitar chaves do KMS.
- Gerar uma chave de dados simétrica que possa ser usada para criptografia do lado do cliente.
- Excluir chaves do KMS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class KeyManager:
    def __init__(self, kms_client):
        self.kms_client = kms_client
```

```
        self.created_keys = []


    def create_key(self):
        """
        Creates a key (or multiple keys) with a user-provided description.
        """
        answer = "y"
        while answer.lower() == "y":
            key_desc = input("\nLet's create a key. Describe it for me: ")
            if not key_desc:
                key_desc = "Key management demo key"
            try:
                key = self.kms_client.create_key(Description=key_desc)
["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't create your key. Here's why: %s",
                    err.response["Error"]["Message"],
                )
                raise
            else:
                print("Key created:")
                pprint(key)
                self.created_keys.append(key)
                answer = input("Create another (y/n)? ")


    def list_keys(self):
        """
        Lists the keys for the current account by using a paginator.
        """
        try:
            page_size = 10
            print("\nLet's list your keys.")
            key_paginator = self.kms_client.get_paginator("list_keys")
            for key_page in key_paginator.paginate(PaginationConfig={"PageSize":
 10}):
                print(f"Here are {len(key_page['Keys'])} keys:")
                pprint(key_page["Keys"])
                if key_page["Truncated"]:
                    answer = input(
                        f"Do you want to see the next {page_size} keys (y/n)? "
                    )
```

```
                    if answer.lower() != "y":
                        break
                else:
                    print("That's all your keys!")
        except ClientError as err:
            logging.error(
                "Couldn't list your keys. Here's why: %s",
                err.response["Error"]["Message"],
            )


    def describe_key(self):
        """
        Describes a key.
        """
        key_id = input("Enter a key ID or ARN here to get information about the key:
")
        if key_id:
            try:
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't get key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"Got key {key_id}:")
                pprint(key)
        return key_id


    def generate_data_key(self, key_id):
        """
        Generates a symmetric data key that can be used for client-side encryption.
        """
        answer = input(
            f"Do you want to generate a symmetric data key from key {key_id} (y/n)?
"
        )
        if answer.lower() == "y":
            try:
                data_key = self.kms_client.generate_data_key(
                    KeyId=key_id, KeySpec="AES_256"
```

```
                )
            except ClientError as err:
                logger.error(
                    "Couldn't generate a data key for key %s. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                pprint(data_key)


    def enable_disable_key(self, key_id):
        """
        Disables and then enables a key. Gets the key state after each state change.
        """
        answer = input("Do you want to disable and then enable that key (y/n)? ")
        if answer.lower() == "y":
            try:
                self.kms_client.disable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't disable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")

            try:
                self.kms_client.enable_key(KeyId=key_id)
                key = self.kms_client.describe_key(KeyId=key_id)["KeyMetadata"]
            except ClientError as err:
                logging.error(
                    "Couldn't enable key '%s'. Here's why: %s",
                    key_id,
                    err.response["Error"]["Message"],
                )
            else:
                print(f"AWS KMS says your key state is: {key['KeyState']}.")


    def delete_keys(self, keys):
        """
```

```
        Deletes a list of keys.

        :param keys: The list of keys to delete.
        """
        answer = input("Do you want to delete these keys (y/n)? ")
        if answer.lower() == "y":
            window = 7
            for key in keys:
                try:
                    self.kms_client.schedule_key_deletion(
                        KeyId=key["KeyId"], PendingWindowInDays=window
                    )
                except ClientError as err:
                    logging.error(
                        "Couldn't delete key %s. Here's why: %s",
                        key["KeyId"],
                        err.response["Error"]["Message"],
                    )
                else:
                    print(
                        f"Key {key['KeyId']} scheduled for deletion in {window}
 days."
                    )




def key_management(kms_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the AWS Key Management Service (AWS KMS) key management
 demo.")
    print("-" * 88)

    key_manager = KeyManager(kms_client)
    key_manager.create_key()
    print("-" * 88)
    key_manager.list_keys()
    print("-" * 88)
    key_id = key_manager.describe_key()
    if key_id:
        key_manager.enable_disable_key(key_id)
        print("-" * 88)
```

```
        key_manager.generate_data_key(key_id)
    print("-" * 88)
    print("For this demo, we created these keys:")
    for key in key_manager.created_keys:
        print(f"\tKeyId: {key['KeyId']}")
        print(f"\tDescription: {key['Description']}")
        print("-" * 66)
    key_manager.delete_keys(key_manager.created_keys)
    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        key_management(boto3.client("kms"))
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateKey
  - DescribeKey
  - DisableKey
  - EnableKey
  - GenerateDataKey
  - ListKeys
  - ScheduleKeyDeletion

Exemplos de Lambda usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def create_function(
        self, function_name, handler_name, iam_role, deployment_package
    ):
        """
        Deploys a Lambda function.

        :param function_name: The name of the Lambda function.
        :param handler_name: The fully qualified name of the handler function. This
                             must include the file name and the function name.
```

```
        :param iam_role: The IAM role to use for the function.
        :param deployment_package: The deployment package that contains the function
                                   code in .zip format.
        :return: The Amazon Resource Name (ARN) of the newly created function.
        """
        try:
            response = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="AWS Lambda doc example",
                Runtime="python3.8",
                Role=iam_role.arn,
                Handler=handler_name,
                Code={"ZipFile": deployment_package},
                Publish=True,
            )
            function_arn = response["FunctionArn"]
            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)
            logger.info(
                "Created function '%s' with ARN: '%s'.",
                function_name,
                response["FunctionArn"],
            )
        except ClientError:
            logger.error("Couldn't create function %s.", function_name)
            raise
        else:
            return function_arn
```

- Para obter detalhes da API, consulte a CreateFunctionReferência da API AWSSDK for Python (Boto3).

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def delete_function(self, function_name):
        """
        Deletes a Lambda function.

        :param function_name: The name of the function to delete.
        """
        try:
            self.lambda_client.delete_function(FunctionName=function_name)
        except ClientError:
            logger.exception("Couldn't delete function %s.", function_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteFunctionReferência da API AWSSDK for Python (Boto3).

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def get_function(self, function_name):
        """
        Gets data about a Lambda function.

        :param function_name: The name of the function.
        :return: The function data.
        """
        response = None
        try:
            response = self.lambda_client.get_function(FunctionName=function_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Function %s does not exist.", function_name)
            else:
                logger.error(
                    "Couldn't get function %s. Here's why: %s: %s",
                    function_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response
```

- Para obter detalhes da API, consulte a GetFunctionReferência da API AWSSDK for Python (Boto3).

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def invoke_function(self, function_name, function_params, get_log=False):
        """
        Invokes a Lambda function.

        :param function_name: The name of the function to invoke.
        :param function_params: The parameters of the function as a dict. This dict
                                is serialized to JSON before it is sent to Lambda.
        :param get_log: When true, the last 4 KB of the execution log are included
 in
                        the response.
        :return: The response from the function invocation.
        """
        try:
            response = self.lambda_client.invoke(
                FunctionName=function_name,
                Payload=json.dumps(function_params),
                LogType="Tail" if get_log else "None",
            )
            logger.info("Invoked function %s.", function_name)
        except ClientError:
            logger.exception("Couldn't invoke function %s.", function_name)
            raise
        return response
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK para Python (Boto3).

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def list_functions(self):
        """
        Lists the Lambda functions for the current account.
        """
        try:
            func_paginator = self.lambda_client.get_paginator("list_functions")
            for func_page in func_paginator.paginate():
                for func in func_page["Functions"]:
                    print(func["FunctionName"])
                    desc = func.get("Description")
                    if desc:
                        print(f"\t{desc}")
                    print(f"\t{func['Runtime']}: {func['Handler']}")
        except ClientError as err:
            logger.error(
                "Couldn't list functions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
```

```
            )
            raise
```

- Para obter detalhes da API, consulte a ListFunctionsReferência da API AWSSDK for Python (Boto3).

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def update_function_code(self, function_name, deployment_package):
        """
        Updates the code for a Lambda function by submitting a .zip archive that
 contains
        the code for the function.

        :param function_name: The name of the function to update.
        :param deployment_package: The function code to update, packaged as bytes in
                                   .zip format.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_code(
                FunctionName=function_name, ZipFile=deployment_package
            )
        except ClientError as err:
```

```
            logger.error(
                "Couldn't update function %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a UpdateFunctionCodeReferência da API AWSSDK for Python (Boto3).

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    def update_function_configuration(self, function_name, env_vars):
        """
        Updates the environment variables for a Lambda function.

        :param function_name: The name of the function to update.
        :param env_vars: A dict of environment variables to update.
        :return: Data about the update, including the status.
        """
        try:
```

```
            response = self.lambda_client.update_function_configuration(
                FunctionName=function_name, Environment={"Variables": env_vars}
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function configuration %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationReferência da API AWSSDK for Python (Boto3).

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Defina um manipulador do Lambda que aumente um número.

```
import logging

logger = logging.getLogger()
logger.setLevel(logging.INFO)


def lambda_handler(event, context):
    """
    Accepts an action and a single number, performs the specified action on the
 number,
    and returns the result. The only allowable action is 'increment'.

    :param event: The event dict that contains the parameters sent when the function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the action.
    """
    result = None
    action = event.get("action")
    if action == "increment":
        result = event.get("number", 0) + 1
        logger.info("Calculated result of %s", result)
    else:
        logger.error("%s is not a valid action.", action)

    response = {"result": result}
    return response
```

Defina um segundo manipulador do Lambda que faça operações aritméticas.

```
import logging
import os


logger = logging.getLogger()

# Define a list of Python lambda functions that are called by this AWS Lambda
 function.
```

```
ACTIONS = {
    "plus": lambda x, y: x + y,
    "minus": lambda x, y: x - y,
    "times": lambda x, y: x * y,
    "divided-by": lambda x, y: x / y,
}


def lambda_handler(event, context):
    """
    Accepts an action and two numbers, performs the specified action on the numbers,
    and returns the result.

    :param event: The event dict that contains the parameters sent when the function
                  is invoked.
    :param context: The context in which the function is called.
    :return: The result of the specified action.
    """
    # Set the log level based on a variable configured in the Lambda environment.
    logger.setLevel(os.environ.get("LOG_LEVEL", logging.INFO))
    logger.debug("Event: %s", event)

    action = event.get("action")
    func = ACTIONS.get(action)
    x = event.get("x")
    y = event.get("y")
    result = None
    try:
        if func is not None and x is not None and y is not None:
            result = func(x, y)
            logger.info("%s %s %s is %s", x, action, y, result)
        else:
            logger.error("I can't calculate %s %s %s.", x, action, y)
    except ZeroDivisionError:
        logger.warning("I can't divide %s by 0!", x)

    response = {"result": result}
    return response
```

Crie funções que envolvam ações do Lambda.

```
class LambdaWrapper:
    def __init__(self, lambda_client, iam_resource):
        self.lambda_client = lambda_client
        self.iam_resource = iam_resource


    @staticmethod
    def create_deployment_package(source_file, destination_file):
        """
        Creates a Lambda deployment package in .zip format in an in-memory buffer.
 This
        buffer can be passed directly to Lambda when creating the function.

        :param source_file: The name of the file that contains the Lambda handler
                            function.
        :param destination_file: The name to give the file when it's deployed to
 Lambda.
        :return: The deployment package.
        """
        buffer = io.BytesIO()
        with zipfile.ZipFile(buffer, "w") as zipped:
            zipped.write(source_file, destination_file)
        buffer.seek(0)
        return buffer.read()

    def get_iam_role(self, iam_role_name):
        """
        Get an AWS Identity and Access Management (IAM) role.

        :param iam_role_name: The name of the role to retrieve.
        :return: The IAM role.
        """
        role = None
        try:
            temp_role = self.iam_resource.Role(iam_role_name)
            temp_role.load()
            role = temp_role
            logger.info("Got IAM role %s", role.name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
                logger.info("IAM role %s does not exist.", iam_role_name)
            else:
                logger.error(
```

```
                    "Couldn't get IAM role %s. Here's why: %s: %s",
                    iam_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return role

    def create_iam_role_for_lambda(self, iam_role_name):
        """
        Creates an IAM role that grants the Lambda function basic permissions. If a
        role with the specified name already exists, it is used for the demo.

        :param iam_role_name: The name of the role to create.
        :return: The role and a value that indicates whether the role is newly
 created.
        """
        role = self.get_iam_role(iam_role_name)
        if role is not None:
            return role, False

        lambda_assume_role_policy = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Effect": "Allow",
                    "Principal": {"Service": "lambda.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        policy_arn = "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole"

        try:
            role = self.iam_resource.create_role(
                RoleName=iam_role_name,
                AssumeRolePolicyDocument=json.dumps(lambda_assume_role_policy),
            )
            logger.info("Created role %s.", role.name)
            role.attach_policy(PolicyArn=policy_arn)
            logger.info("Attached basic execution policy to role %s.", role.name)
        except ClientError as error:
            if error.response["Error"]["Code"] == "EntityAlreadyExists":
```

```
                role = self.iam_resource.Role(iam_role_name)
                logger.warning("The role %s already exists. Using it.",
iam_role_name)
            else:
                logger.exception(
                    "Couldn't create role %s or attach policy %s.",
                    iam_role_name,
                    policy_arn,
                )
                raise

        return role, True

    def get_function(self, function_name):
        """
        Gets data about a Lambda function.

        :param function_name: The name of the function.
        :return: The function data.
        """
        response = None
        try:
            response = self.lambda_client.get_function(FunctionName=function_name)
        except ClientError as err:
            if err.response["Error"]["Code"] == "ResourceNotFoundException":
                logger.info("Function %s does not exist.", function_name)
            else:
                logger.error(
                    "Couldn't get function %s. Here's why: %s: %s",
                    function_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        return response


    def create_function(
        self, function_name, handler_name, iam_role, deployment_package
    ):
        """
        Deploys a Lambda function.

        :param function_name: The name of the Lambda function.
```

```
        :param handler_name: The fully qualified name of the handler function. This
                             must include the file name and the function name.
        :param iam_role: The IAM role to use for the function.
        :param deployment_package: The deployment package that contains the function
                                   code in .zip format.
        :return: The Amazon Resource Name (ARN) of the newly created function.
        """
        try:
            response = self.lambda_client.create_function(
                FunctionName=function_name,
                Description="AWS Lambda doc example",
                Runtime="python3.8",
                Role=iam_role.arn,
                Handler=handler_name,
                Code={"ZipFile": deployment_package},
                Publish=True,
            )
            function_arn = response["FunctionArn"]
            waiter = self.lambda_client.get_waiter("function_active_v2")
            waiter.wait(FunctionName=function_name)
            logger.info(
                "Created function '%s' with ARN: '%s'.",
                function_name,
                response["FunctionArn"],
            )
        except ClientError:
            logger.error("Couldn't create function %s.", function_name)
            raise
        else:
            return function_arn


    def delete_function(self, function_name):
        """
        Deletes a Lambda function.

        :param function_name: The name of the function to delete.
        """
        try:
            self.lambda_client.delete_function(FunctionName=function_name)
        except ClientError:
            logger.exception("Couldn't delete function %s.", function_name)
            raise
```

```
    def invoke_function(self, function_name, function_params, get_log=False):
        """
        Invokes a Lambda function.

        :param function_name: The name of the function to invoke.
        :param function_params: The parameters of the function as a dict. This dict
                                is serialized to JSON before it is sent to Lambda.
        :param get_log: When true, the last 4 KB of the execution log are included
in
                        the response.
        :return: The response from the function invocation.
        """
        try:
            response = self.lambda_client.invoke(
                FunctionName=function_name,
                Payload=json.dumps(function_params),
                LogType="Tail" if get_log else "None",
            )
            logger.info("Invoked function %s.", function_name)
        except ClientError:
            logger.exception("Couldn't invoke function %s.", function_name)
            raise
        return response


    def update_function_code(self, function_name, deployment_package):
        """
        Updates the code for a Lambda function by submitting a .zip archive that
contains
        the code for the function.

        :param function_name: The name of the function to update.
        :param deployment_package: The function code to update, packaged as bytes in
                                   .zip format.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_code(
                FunctionName=function_name, ZipFile=deployment_package
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function %s. Here's why: %s: %s",
```

```
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def update_function_configuration(self, function_name, env_vars):
        """
        Updates the environment variables for a Lambda function.

        :param function_name: The name of the function to update.
        :param env_vars: A dict of environment variables to update.
        :return: Data about the update, including the status.
        """
        try:
            response = self.lambda_client.update_function_configuration(
                FunctionName=function_name, Environment={"Variables": env_vars}
            )
        except ClientError as err:
            logger.error(
                "Couldn't update function configuration %s. Here's why: %s: %s",
                function_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def list_functions(self):
        """
        Lists the Lambda functions for the current account.
        """
        try:
            func_paginator = self.lambda_client.get_paginator("list_functions")
            for func_page in func_paginator.paginate():
                for func in func_page["Functions"]:
                    print(func["FunctionName"])
                    desc = func.get("Description")
                    if desc:
```

```
                        print(f"\t{desc}")
                    print(f"\t{func['Runtime']}: {func['Handler']}")
        except ClientError as err:
            logger.error(
                "Couldn't list functions. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

Crie uma função que execute o cenário.

```
class UpdateFunctionWaiter(CustomWaiter):
    """A custom waiter that waits until a function is successfully updated."""

    def __init__(self, client):
        super().__init__(
            "UpdateSuccess",
            "GetFunction",
            "Configuration.LastUpdateStatus",
            {"Successful": WaitState.SUCCESS, "Failed": WaitState.FAILURE},
            client,
        )

    def wait(self, function_name):
        self._wait(FunctionName=function_name)


def run_scenario(lambda_client, iam_resource, basic_file, calculator_file,
 lambda_name):
    """
    Runs the scenario.

    :param lambda_client: A Boto3 Lambda client.
    :param iam_resource: A Boto3 IAM resource.
    :param basic_file: The name of the file that contains the basic Lambda handler.
    :param calculator_file: The name of the file that contains the calculator Lambda
 handler.
```

```
    :param lambda_name: The name to give resources created for the scenario, such as
the
                        IAM role and the Lambda function.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the AWS Lambda getting started with functions demo.")
    print("-" * 88)

    wrapper = LambdaWrapper(lambda_client, iam_resource)

    print("Checking for IAM role for Lambda...")
    iam_role, should_wait = wrapper.create_iam_role_for_lambda(lambda_name)
    if should_wait:
        logger.info("Giving AWS time to create resources...")
        wait(10)

    print(f"Looking for function {lambda_name}...")
    function = wrapper.get_function(lambda_name)
    if function is None:
        print("Zipping the Python script into a deployment package...")
        deployment_package = wrapper.create_deployment_package(
            basic_file, f"{lambda_name}.py"
        )
        print(f"...and creating the {lambda_name} Lambda function.")
        wrapper.create_function(
            lambda_name, f"{lambda_name}.lambda_handler", iam_role,
deployment_package
        )
    else:
        print(f"Function {lambda_name} already exists.")
    print("-" * 88)

    print(f"Let's invoke {lambda_name}. This function increments a number.")
    action_params = {
        "action": "increment",
        "number": q.ask("Give me a number to increment: ", q.is_int),
    }
    print(f"Invoking {lambda_name}...")
    response = wrapper.invoke_function(lambda_name, action_params)
    print(
        f"Incrementing {action_params['number']} resulted in "
        f"{json.load(response['Payload'])}"
```

```
    )
    print("-" * 88)

    print(f"Let's update the function to an arithmetic calculator.")
    q.ask("Press Enter when you're ready.")
    print("Creating a new deployment package...")
    deployment_package = wrapper.create_deployment_package(
        calculator_file, f"{lambda_name}.py"
    )
    print(f"...and updating the {lambda_name} Lambda function.")
    update_waiter = UpdateFunctionWaiter(lambda_client)
    wrapper.update_function_code(lambda_name, deployment_package)
    update_waiter.wait(lambda_name)
    print(f"This function uses an environment variable to control logging level.")
    print(f"Let's set it to DEBUG to get the most logging.")
    wrapper.update_function_configuration(
        lambda_name, {"LOG_LEVEL": logging.getLevelName(logging.DEBUG)}
    )

    actions = ["plus", "minus", "times", "divided-by"]
    want_invoke = True
    while want_invoke:
        print(f"Let's invoke {lambda_name}. You can invoke these actions:")
        for index, action in enumerate(actions):
            print(f"{index + 1}: {action}")
        action_params = {}
        action_index = q.ask(
            "Enter the number of the action you want to take: ",
            q.is_int,
            q.in_range(1, len(actions)),
        )
        action_params["action"] = actions[action_index - 1]
        print(f"You've chosen to invoke 'x {action_params['action']} y'.")
        action_params["x"] = q.ask("Enter a value for x: ", q.is_int)
        action_params["y"] = q.ask("Enter a value for y: ", q.is_int)
        print(f"Invoking {lambda_name}...")
        response = wrapper.invoke_function(lambda_name, action_params, True)
        print(
            f"Calculating {action_params['x']} {action_params['action']}
{action_params['y']} "
            f"resulted in {json.load(response['Payload'])}"
        )
        q.ask("Press Enter to see the logs from the call.")
        print(base64.b64decode(response["LogResult"]).decode())
```

```
        want_invoke = q.ask("That was fun. Shall we do it again? (y/n) ",
 q.is_yesno)
    print("-" * 88)

    if q.ask(
        "Do you want to list all of the functions in your account? (y/n) ",
 q.is_yesno
    ):
        wrapper.list_functions()
    print("-" * 88)

    if q.ask("Ready to delete the function and role? (y/n) ", q.is_yesno):
        for policy in iam_role.attached_policies.all():
            policy.detach_role(RoleName=iam_role.name)
        iam_role.delete()
        print(f"Deleted role {lambda_name}.")
        wrapper.delete_function(lambda_name)
        print(f"Deleted function {lambda_name}.")

    print("\nThanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    try:
        run_scenario(
            boto3.client("lambda"),
            boto3.resource("iam"),
            "lambda_handler_basic.py",
            "lambda_handler_calculator.py",
            "doc_example_lambda_calculator",
        )
    except Exception:
        logging.exception("Something went wrong with the demo!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke

- ListFunctions
- UpdateFunctionCode
- UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do Kinesis com o Lambda usando Python.

```
import base64
def lambda_handler(event, context):

    for record in event['Records']:
        try:
            print(f"Processed Kinesis Event - EventID: {record['eventID']}")
            record_data = base64.b64decode(record['kinesis']
['data']).decode('utf-8')
            print(f"Record Data: {record_data}")
            # TODO: Do interesting work based on the new data
        except Exception as e:
            print(f"An error occurred {e}")
            raise e
    print(f"Successfully processed {len(event['Records'])} records.")
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Python.

```
import json
import urllib.parse
import boto3

print('Loading function')

s3 = boto3.client('s3')


def lambda_handler(event, context):
    #print("Received event: " + json.dumps(event, indent=2))

    # Get the object from the event and show its content type
    bucket = event['Records'][0]['s3']['bucket']['name']
    key = urllib.parse.unquote_plus(event['Records'][0]['s3']['object']['key'],
 encoding='utf-8')
    try:
        response = s3.get_object(Bucket=bucket, Key=key)
        print("CONTENT TYPE: " + response['ContentType'])
        return response['ContentType']
    except Exception as e:
        print(e)
        print('Error getting object {} from bucket {}. Make sure they exist and your
 bucket is in the same region as this function.'.format(key, bucket))
        raise e
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for record in event['Records']:
        process_message(record)
    print("done")

def process_message(record):
    try:
        message = record['Sns']['Message']
        print(f"Processed message {message}")
        # TODO; Process your record here

    except Exception as e:
        print("An error occurred")
        raise e
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for message in event['Records']:
        process_message(message)
    print("done")

def process_message(message):
    try:
        print(f"Processed message {message['body']}")
        # TODO: Do interesting work based on the new message
    except Exception as err:
        print("An error occurred")
        raise err
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do Kinesis com o Lambda usando Python.

```
def handler(event, context):
    records = event.get("Records")
    curRecordSequenceNumber = ""

    for record in records:
        try:
            # Process your record
            curRecordSequenceNumber = record["kinesis"]["sequenceNumber"]
        except Exception as e:
            # Return failed record's sequence number
            return {"batchItemFailures":[{"itemIdentifier":
 curRecordSequenceNumber}]}

    return {"batchItemFailures":[]}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Python.

```
import json
def lambda_handler(event, context):
    if event:
        batch_item_failures = []
        sqs_batch_response = {}

        for record in event["Records"]:
            try:
                # process message
```

```
            except Exception as e:
                batch_item_failures.append({"itemIdentifier": record['messageId']})

        sqs_batch_response["batchItemFailures"] = batch_item_failures
        return sqs_batch_response
```

Exemplos do Lookout for Vision usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK for Python (Boto3) com Lookout for Vision.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Lookout for Vision

O exemplo de código a seguir mostra como começar a usar o Lookout for Vision.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"""
This example shows how to list your Amazon Lookout for Vision projects.
If you haven't previously created a project in the current AWS Region,
the response is an empty list, however it confirms that you can call the
```

```
Lookout for Vision API.
"""
from botocore.exceptions import ClientError
import boto3


class Hello:
    """Hello class for Amazon Lookout for Vision"""

    @staticmethod
    def list_projects(lookoutvision_client):
        """
        Lists information about the projects that are in your AWS account
        and in the current AWS Region.

        : param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            for project in response["Projects"]:
                print("Project: " + project["ProjectName"])
                print("ARN: " + project["ProjectArn"])
                print()
            print("Done!")
        except ClientError as err:
            print(f"Couldn't list projects. \n{err}")
            raise


def main():
    session = boto3.Session(profile_name="lookoutvision-access")
    lookoutvision_client = session.client("lookoutvision")

    Hello.list_projects(lookoutvision_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a ListProjectsReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Criar um conjunto de dados

O exemplo de código a seguir mostra como criar um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Criar Conjunto Dados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def create_dataset(lookoutvision_client, project_name, manifest_file,
 dataset_type):
        """
        Creates a new Lookout for Vision dataset

        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        :param project_name: The name of the project in which you want to
                             create a dataset.
        :param bucket: The bucket that contains the manifest file.
        :param manifest_file: The path and name of the manifest file.
        :param dataset_type: The type of the dataset (train or test).
        """
        try:
            bucket, key = manifest_file.replace("s3://", "").split("/", 1)
            logger.info("Creating %s dataset type...", dataset_type)
            dataset = {
                "GroundTruthManifest": {"S3Object": {"Bucket": bucket, "Key": key}}
            }
```

```
            response = lookoutvision_client.create_dataset(
                ProjectName=project_name,
                DatasetType=dataset_type,
                DatasetSource=dataset,
            )
            logger.info("Dataset Status: %s", response["DatasetMetadata"]["Status"])
            logger.info(
                "Dataset Status Message: %s",
                response["DatasetMetadata"]["StatusMessage"],
            )
            logger.info("Dataset Type: %s", response["DatasetMetadata"]
["DatasetType"])

            # Wait until either created or failed.
            finished = False
            status = ""
            dataset_description = {}
            while finished is False:
                dataset_description = lookoutvision_client.describe_dataset(
                    ProjectName=project_name, DatasetType=dataset_type
                )
                status = dataset_description["DatasetDescription"]["Status"]

                if status == "CREATE_IN_PROGRESS":
                    logger.info("Dataset creation in progress...")
                    time.sleep(2)
                elif status == "CREATE_COMPLETE":
                    logger.info("Dataset created.")
                    finished = True
                else:
                    logger.info(
                        "Dataset creation failed: %s",
                        dataset_description["DatasetDescription"]["StatusMessage"],
                    )
                    finished = True

            if status != "CREATE_COMPLETE":
                message = dataset_description["DatasetDescription"]["StatusMessage"]
                logger.exception("Couldn't create dataset: %s", message)
                raise Exception(f"Couldn't create dataset: {message}")

        except ClientError:
            logger.exception("Service error: Couldn't create dataset.")
            raise
```

- Para obter detalhes da API, consulte a CreateDatasetReferência da API AWSSDK for Python (Boto3).

Criar um modelo

O exemplo de código a seguir mostra como criar um modelo do Lookout for Vision.

Para obter mais informações, consulte TreinandoModelo.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def create_model(
        lookoutvision_client,
        project_name,
        training_results,
        tag_key=None,
        tag_key_value=None,
    ):
        """
        Creates a version of a Lookout for Vision model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project in which you want to create a
                             model.
        :param training_results: The Amazon S3 location where training results are
 stored.
        :param tag_key: The key for a tag to add to the model.
        :param tag_key_value - A value associated with the tag_key.
        return: The model status and version.
        """
```

```
        try:
            logger.info("Training model...")
            output_bucket, output_folder = training_results.replace("s3://",
"").split(
                "/", 1
            )
            output_config = {
                "S3Location": {"Bucket": output_bucket, "Prefix": output_folder}
            }
            tags = []
            if tag_key is not None:
                tags = [{"Key": tag_key, "Value": tag_key_value}]

            response = lookoutvision_client.create_model(
                ProjectName=project_name, OutputConfig=output_config, Tags=tags
            )

            logger.info("ARN: %s", response["ModelMetadata"]["ModelArn"])
            logger.info("Version: %s", response["ModelMetadata"]["ModelVersion"])
            logger.info("Started training...")

            print("Training started. Training might take several hours to
complete.")

            # Wait until training completes.
            finished = False
            status = "UNKNOWN"
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name,
                    ModelVersion=response["ModelMetadata"]["ModelVersion"],
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "TRAINING":
                    logger.info("Model training in progress...")
                    time.sleep(600)
                    continue

                if status == "TRAINED":
                    logger.info("Model was successfully trained.")
                else:
                    logger.info(
                        "Model training failed: %s ",
```

```
                        model_description["ModelDescription"]["StatusMessage"],
                    )
                finished = True
        except ClientError:
            logger.exception("Couldn't train model.")
            raise
        else:
            return status, response["ModelMetadata"]["ModelVersion"]
```

- Para obter detalhes da API, consulte a CreateModelReferência da API AWSSDK for Python (Boto3).

Criar um projeto

O exemplo de código a seguir mostra como criar um projeto Lookout for Vision.

Para obter mais informações, consulte CriandoProjeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def create_project(lookoutvision_client, project_name):
        """
        Creates a new Lookout for Vision project.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param  project_name: The name for the new project.
        :return project_arn: The ARN of the new project.
        """
        try:
            logger.info("Creating project: %s", project_name)
```

```
            response = lookoutvision_client.create_project(ProjectName=project_name)
            project_arn = response["ProjectMetadata"]["ProjectArn"]
            logger.info("project ARN: %s", project_arn)
        except ClientError:
            logger.exception("Couldn't create project %s.", project_name)
            raise
        else:
            return project_arn
```

- Para obter detalhes da API, consulte a CreateProjectReferência da API AWSSDK for Python (Boto3).

Excluir um conjunto de dados

O exemplo de código a seguir mostra como excluir um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Excluindo um conjunto de dados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def delete_dataset(lookoutvision_client, project_name, dataset_type):
        """
        Deletes a Lookout for Vision dataset

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the dataset that
                             you want to delete.
        :param dataset_type: The type (train or test) of the dataset that you
                             want to delete.
        """
        try:
```

```
            logger.info(
                "Deleting the %s dataset for project %s.", dataset_type,
 project_name
            )
            lookoutvision_client.delete_dataset(
                ProjectName=project_name, DatasetType=dataset_type
            )
            logger.info("Dataset deleted.")
        except ClientError:
            logger.exception("Service error: Couldn't delete dataset.")
            raise
```

- Para obter detalhes da API, consulte a DeleteDatasetReferência da API AWSSDK for Python (Boto3).

Excluir um modelo

O exemplo de código a seguir mostra como excluir um modelo do Lookout for Vision.

Para obter mais informações, consulte Excluindo um modelo.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def delete_model(lookoutvision_client, project_name, model_version):
        """
        Deletes a Lookout for Vision model. The model must first be stopped and
 can't
        be in training.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
```

```
        :param project_name: The name of the project that contains the desired
model.
        :param model_version: The version of the model that you want to delete.
        """
        try:
            logger.info("Deleting model: %s", model_version)
            lookoutvision_client.delete_model(
                ProjectName=project_name, ModelVersion=model_version
            )

            model_exists = True
            while model_exists:
                response =
lookoutvision_client.list_models(ProjectName=project_name)

                model_exists = False
                for model in response["Models"]:
                    if model["ModelVersion"] == model_version:
                        model_exists = True

                if model_exists is False:
                    logger.info("Model deleted")
                else:
                    logger.info("Model is being deleted...")
                    time.sleep(2)

            logger.info("Deleted Model: %s", model_version)
        except ClientError:
            logger.exception("Couldn't delete model.")
            raise
```

- Para obter detalhes da API, consulte a DeleteModelReferência da API AWSSDK for Python (Boto3).

Excluir um projeto

O exemplo de código a seguir mostra como excluir um projeto Lookout for Vision.

Para obter mais informações, consulte Excluindo um projeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def delete_project(lookoutvision_client, project_name):
        """
        Deletes a Lookout for Vision Model

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that you want to delete.
        """
        try:
            logger.info("Deleting project: %s", project_name)
            response = lookoutvision_client.delete_project(ProjectName=project_name)
            logger.info("Deleted project ARN: %s ", response["ProjectArn"])
        except ClientError as err:
            logger.exception("Couldn't delete project %s.", project_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteProjectReferência da API AWSSDK for Python (Boto3).

Descrever um conjunto de dados

O exemplo de código a seguir mostra como descrever um conjunto de dados do Lookout for Vision.

Para obter mais informações, consulte Visualizar conjunto de dados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def describe_dataset(lookoutvision_client, project_name, dataset_type):
        """
        Gets information about a Lookout for Vision dataset.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the dataset that
                             you want to describe.
        :param dataset_type: The type (train or test) of the dataset that you want
                             to describe.
        """
        try:
            response = lookoutvision_client.describe_dataset(
                ProjectName=project_name, DatasetType=dataset_type
            )
            print(f"Name: {response['DatasetDescription']['ProjectName']}")
            print(f"Type: {response['DatasetDescription']['DatasetType']}")
            print(f"Status: {response['DatasetDescription']['Status']}")
            print(f"Message: {response['DatasetDescription']['StatusMessage']}")
            print(f"Images: {response['DatasetDescription']['ImageStats']
['Total']}")
            print(f"Labeled: {response['DatasetDescription']['ImageStats']
['Labeled']}")
            print(f"Normal: {response['DatasetDescription']['ImageStats']
['Normal']}")
            print(f"Anomaly: {response['DatasetDescription']['ImageStats']
['Anomaly']}")
        except ClientError:
            logger.exception("Service error: problem listing datasets.")
            raise
        print("Done.")
```

- Para obter detalhes da API, consulte a DescribeDatasetReferência da API AWSSDK for Python (Boto3).

Descrever um modelo

O exemplo de código a seguir mostra como descrever um modelo do Lookout for Vision.

Para obter mais informações, consulte Visualizar modelos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def describe_model(lookoutvision_client, project_name, model_version):
        """
        Shows the performance metrics for a trained model.

        :param lookoutvision_client: A Boto3 Amazon Lookout for Vision client.
        :param project_name: The name of the project that contains the desired
 model.
        :param model_version: The version of the model.
        """
        response = lookoutvision_client.describe_model(
            ProjectName=project_name, ModelVersion=model_version
        )
        model_description = response["ModelDescription"]
        print(f"\tModel version: {model_description['ModelVersion']}")
        print(f"\tARN: {model_description['ModelArn']}")
        if "Description" in model_description:
            print(f"\tDescription: {model_description['Description']}")
        print(f"\tStatus: {model_description['Status']}")
        print(f"\tMessage: {model_description['StatusMessage']}")
        print(f"\tCreated: {str(model_description['CreationTimestamp'])}")
```

```
        if model_description["Status"] in ("TRAINED", "HOSTED"):
            training_start = model_description["CreationTimestamp"]
            training_end = model_description["EvaluationEndTimestamp"]
            duration = training_end - training_start
            print(f"\tTraining duration: {duration}")

            print("\n\tPerformance metrics\n\t-------------------")
            print(f"\tRecall: {model_description['Performance']['Recall']}")
            print(f"\tPrecision: {model_description['Performance']['Precision']}")
            print(f"\tF1: {model_description['Performance']['F1Score']}")

            training_output_bucket = model_description["OutputConfig"]["S3Location"]
[
                "Bucket"
            ]
            prefix = model_description["OutputConfig"]["S3Location"]["Prefix"]
            print(f"\tTraining output: s3://{training_output_bucket}/{prefix}")
```

- Para obter detalhes da API, consulte a DescribeModelReferência da API AWSSDK for Python (Boto3).

Detectar anomalias em uma imagem com um modelo treinado

O exemplo de código a seguir mostra como detectar anomalias em uma imagem com um modelo treinado do Lookout for Vision.

Para obter mais informações, consulte Detectar anomalias em uma imagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Inference:
    """
```

```
    Shows how to detect anomalies in an image using a trained Lookout for Vision
model.
    """

    @staticmethod
    def detect_anomalies(lookoutvision_client, project_name, model_version, photo):
        """
        Calls DetectAnomalies using the supplied project, model version, and image.
        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        :param project: The project that contains the model that you want to use.
        :param model_version: The version of the model that you want to use.
        :param photo: The photo that you want to analyze.
        :return: The DetectAnomalyResult object that contains the analysis results.
        """

        image_type = imghdr.what(photo)
        if image_type == "jpeg":
            content_type = "image/jpeg"
        elif image_type == "png":
            content_type = "image/png"
        else:
            logger.info("Image type not valid for %s", photo)
            raise ValueError(
                f"File format not valid. Supply a jpeg or png format file: {photo}"
            )

        # Get images bytes for call to detect_anomalies.
        with open(photo, "rb") as image:
            response = lookoutvision_client.detect_anomalies(
                ProjectName=project_name,
                ContentType=content_type,
                Body=image.read(),
                ModelVersion=model_version,
            )

        return response["DetectAnomalyResult"]

    @staticmethod
    def download_from_s3(s3_resource, photo):
        """
        Downloads an image from an S3 bucket.

        :param s3_resource: A Boto3 Amazon S3 resource.
        :param photo: The Amazon S3 path of a photo to download.
```

```
        return: The local path to the downloaded file.
        """
        try:
            bucket, key = photo.replace("s3://", "").split("/", 1)
            local_file = os.path.basename(photo)
        except ValueError:
            logger.exception("Couldn't get S3 info for %s", photo)
            raise

        try:
            logger.info("Downloading %s", photo)
            s3_resource.Bucket(bucket).download_file(key, local_file)
        except ClientError:
            logger.exception("Couldn't download %s from S3.", photo)
            raise

        return local_file

    @staticmethod
    def reject_on_classification(image, prediction, confidence_limit):
        """
        Returns True if the anomaly confidence is greater than or equal to
        the supplied confidence limit.
        :param image: The name of the image file that was analyzed.
        :param prediction: The DetectAnomalyResult object returned from
DetectAnomalies.
        :param confidence_limit: The minimum acceptable confidence (float 0 - 1).
        :return: True if the error condition indicates an anomaly, otherwise False.
        """

        reject = False

        logger.info("Checking classification for %s", image)

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
confidence_limit:
            reject = True
            reject_info = (
                f"Rejected: Anomaly confidence ({prediction['Confidence']:.2%}) is
greater"
                f" than limit ({confidence_limit:.2%})"
            )
            logger.info("%s", reject_info)
```

```
        if not reject:
            logger.info("No anomalies found.")
        return reject

    @staticmethod
    def reject_on_anomaly_types(
        image, prediction, confidence_limit, anomaly_types_limit
    ):
        """
        Checks if the number of anomaly types is greater than the anomaly types
        limit and if the prediction confidence is greater than the confidence limit.
        :param image: The name of the image file that was analyzed.
        :param prediction: The DetectAnomalyResult object returned from
DetectAnomalies.
        :param confidence: The minimum acceptable confidence (float 0 - 1).
        :param anomaly_types_limit: The maximum number of allowable anomaly types
(int).
        :return: True if the error condition indicates an anomaly, otherwise False.
        """

        logger.info("Checking number of anomaly types for %s", image)

        reject = False

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
confidence_limit:
            anomaly_types = {
                anomaly["Name"]
                for anomaly in prediction["Anomalies"]
                if anomaly["Name"] != "background"
            }

            if len(anomaly_types) > anomaly_types_limit:
                reject = True
                reject_info = (
                    f"Rejected: Anomaly confidence ({prediction['Confidence']:.2%})
"
                    f"is greater than limit ({confidence_limit:.2%}) and "
                    f"the number of anomaly types ({len(anomaly_types)-1}) is "
                    f"greater than the limit ({anomaly_types_limit})"
                )

                logger.info("%s", reject_info)
```

```
        if not reject:
            logger.info("No anomalies found.")
        return reject

    @staticmethod
    def reject_on_coverage(
        image, prediction, confidence_limit, anomaly_label, coverage_limit
    ):
        """
        Checks if the coverage area of an anomaly is greater than the coverage limit
 and if
        the prediction confidence is greater than the confidence limit.
        :param image: The name of the image file that was analyzed.
        :param prediction: The DetectAnomalyResult object returned from
 DetectAnomalies.
        :param confidence_limit: The minimum acceptable confidence (float 0-1).
        :anomaly_label: The anomaly label for the type of anomaly that you want to
 check.
        :coverage_limit: The maximum acceptable percentage coverage of an anomaly
 (float 0-1).
        :return: True if the error condition indicates an anomaly, otherwise False.
        """

        reject = False

        logger.info("Checking coverage for %s", image)

        if prediction["IsAnomalous"] and prediction["Confidence"] >=
 confidence_limit:
            for anomaly in prediction["Anomalies"]:
                if anomaly["Name"] == anomaly_label and anomaly["PixelAnomaly"][
                    "TotalPercentageArea"
                ] > (coverage_limit):
                    reject = True
                    reject_info = (
                        f"Rejected: Anomaly confidence
 ({prediction['Confidence']:.2%}) "
                        f"is greater than limit ({confidence_limit:.2%}) and
 {anomaly['Name']} "
                        f"coverage ({anomaly['PixelAnomaly']
['TotalPercentageArea']:.2%}) "
                        f"is greater than limit ({coverage_limit:.2%})"
                    )
```

```
                    logger.info("%s", reject_info)

        if not reject:
            logger.info("No anomalies found.")

        return reject

    @staticmethod
    def analyze_image(lookoutvision_client, image, config):
        """
        Analyzes an image with an Amazon Lookout for Vision model. Also
        runs a series of checks to determine if the contents of an image
        should be rejected.
        :param lookoutvision_client: A Lookout for Vision Boto3 client.
        param image: A local image that you want to analyze.
        param config: Configuration information for the model and reject
        limits.
        """

        project = config["project"]
        model_version = config["model_version"]
        confidence_limit = config["confidence_limit"]
        coverage_limit = config["coverage_limit"]
        anomaly_types_limit = config["anomaly_types_limit"]
        anomaly_label = config["anomaly_label"]

        # Get analysis results.
        print(f"Analyzing {image}.")

        prediction = Inference.detect_anomalies(
            lookoutvision_client, project, model_version, image
        )

        anomalies = []

        reject = Inference.reject_on_classification(image, prediction,
confidence_limit)

        if reject:
            anomalies.append("Classification: An anomaly was found.")

        reject = Inference.reject_on_coverage(
            image, prediction, confidence_limit, anomaly_label, coverage_limit
        )
```

```
        if reject:
            anomalies.append("Coverage: Anomaly coverage too high.")

        reject = Inference.reject_on_anomaly_types(
            image, prediction, confidence_limit, anomaly_types_limit
        )

        if reject:
            anomalies.append("Anomaly type count: Too many anomaly types found.")
            print()

        if len(anomalies) > 0:
            print(f"Anomalies found in {image}")
            for anomaly in anomalies:
                print(f"{anomaly}")
        else:
            print(f"No anomalies found in {image}")


def main():
    """
    Detects anomalies in an image file.
    """
    try:
        logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

        parser = argparse.ArgumentParser(
            description="Find anomalies with Amazon Lookout for Vision."
        )
        parser.add_argument(
            "image",
            help="The file that you want to analyze. Supply a local file path or a "
            "path to an S3 object.",
        )
        parser.add_argument(
            "config",
            help=(
                "The configuration JSON file to use. "
                "See https://github.com/awsdocs/aws-doc-sdk-examples/blob/main/"
                "python/example_code/lookoutvision/README.md"
            ),
        )
```

```
        args = parser.parse_args()

        session = boto3.Session(profile_name="lookoutvision-access")

        lookoutvision_client = session.client("lookoutvision")
        s3_resource = session.resource("s3")

        # Get configuration information.
        with open(args.config, encoding="utf-8") as config_file:
            config = json.load(config_file)

        # Download image if located in S3 bucket.
        if args.image.startswith("s3://"):
            image = Inference.download_from_s3(s3_resource, args.image)
        else:
            image = args.image

        Inference.analyze_image(lookoutvision_client, image, config)

        # Delete image, if downloaded from S3 bucket.
        if args.image.startswith("s3://"):
            os.remove(image)

    except ClientError as err:
        print(f"Service error: {err.response['Error']['Message']}")
    except FileNotFoundError as err:
        print(f"The supplied file couldn't be found: {err.filename}.")
    except ValueError as err:
        print(f"A value error occurred: {err}.")
    else:
        print("\nSuccessfully completed analysis.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a DetectAnomaliesReferência da API AWSSDK for Python (Boto3).

Listar modelos

O exemplo de código a seguir mostra como listar modelos do Lookout for Vision.

Para obter mais informações, consulte Visualizar modelos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Models:

    @staticmethod
    def describe_models(lookoutvision_client, project_name):
        """
        Gets information about all models in a Lookout for Vision project.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that you want to use.
        """
        try:
            response = lookoutvision_client.list_models(ProjectName=project_name)
            print("Project: " + project_name)
            for model in response["Models"]:
                Models.describe_model(
                    lookoutvision_client, project_name, model["ModelVersion"]
                )
                print()
            print("Done...")
        except ClientError:
            logger.exception("Couldn't list models.")
            raise
```

- Para obter detalhes da API, consulte a ListModelsReferência da API AWSSDK for Python (Boto3).

Listar projetos

O exemplo de código a seguir mostra como listar projetos do Lookout for Vision.

Para obter mais informações, consulte Visualizar projetos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Projects:

    @staticmethod
    def list_projects(lookoutvision_client):
        """
        Lists information about the projects that are in in your AWS account
        and in the current AWS Region.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            for project in response["Projects"]:
                print("Project: " + project["ProjectName"])
                print("\tARN: " + project["ProjectArn"])
                print("\tCreated: " + str(["CreationTimestamp"]))
                print("Datasets")
                project_description = lookoutvision_client.describe_project(
                    ProjectName=project["ProjectName"]
                )
                if not project_description["ProjectDescription"]["Datasets"]:
                    print("\tNo datasets")
                else:
                    for dataset in project_description["ProjectDescription"][
                        "Datasets"
                    ]:
                        print(f"\ttype: {dataset['DatasetType']}")
                        print(f"\tStatus: {dataset['StatusMessage']}")

                print("Models")
                response_models = lookoutvision_client.list_models(
                    ProjectName=project["ProjectName"]
```

```
                )
                if not response_models["Models"]:
                    print("\tNo models")
                else:
                    for model in response_models["Models"]:
                        Models.describe_model(
                            lookoutvision_client,
                            project["ProjectName"],
                            model["ModelVersion"],
                        )

                print("------------------------------------------------------------
\n")
            print("Done!")
        except ClientError:
            logger.exception("Problem listing projects.")
            raise
```

- Para obter detalhes da API, consulte a ListProjectsReferência da API AWSSDK for Python (Boto3).

Iniciar um modelo

O exemplo de código a seguir mostra como iniciar um modelo do Lookout for Vision.

Para obter mais informações, consulte Iniciando modelo.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
    def start_model(
```

```
        lookoutvision_client, project_name, model_version, min_inference_units
    ):
        """
        Starts the hosting of a Lookout for Vision model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name:  The name of the project that contains the version of
the
                              model that you want to start hosting.
        :param model_version: The version of the model that you want to start
hosting.
        :param min_inference_units: The number of inference units to use for
hosting.
        """
        try:
            logger.info(
                "Starting model version %s for project %s", model_version,
project_name
            )
            lookoutvision_client.start_model(
                ProjectName=project_name,
                ModelVersion=model_version,
                MinInferenceUnits=min_inference_units,
            )
            print("Starting hosting...")

            status = ""
            finished = False

            # Wait until hosted or failed.
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name, ModelVersion=model_version
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "STARTING_HOSTING":
                    logger.info("Host starting in progress...")
                    time.sleep(10)
                    continue

                if status == "HOSTED":
                    logger.info("Model is hosted and ready for use.")
                    finished = True
```

```
                    continue

                logger.info("Model hosting failed and the model can't be used.")
                finished = True

            if status != "HOSTED":
                logger.error("Error hosting model: %s", status)
                raise Exception(f"Error hosting model: {status}")
        except ClientError:
            logger.exception("Couldn't host model.")
            raise
```

- Para obter detalhes da API, consulte a StartModelReferência da API AWSSDK for Python (Boto3).

Interromper um modelo

O exemplo de código a seguir mostra como interromper um modelo do Lookout for Vision.

Para obter mais informações, consulte Interrompendo modelo.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
    def stop_model(lookoutvision_client, project_name, model_version):
        """
        Stops a running Lookout for Vision Model.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        :param project_name: The name of the project that contains the version of
                             the model that you want to stop hosting.
```

```
        :param model_version:  The version of the model that you want to stop
hosting.
        """
        try:
            logger.info("Stopping model version %s for %s", model_version,
project_name)
            response = lookoutvision_client.stop_model(
                ProjectName=project_name, ModelVersion=model_version
            )
            logger.info("Stopping hosting...")

            status = response["Status"]
            finished = False

            # Wait until stopped or failed.
            while finished is False:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project_name, ModelVersion=model_version
                )
                status = model_description["ModelDescription"]["Status"]

                if status == "STOPPING_HOSTING":
                    logger.info("Host stopping in progress...")
                    time.sleep(10)
                    continue

                if status == "TRAINED":
                    logger.info("Model is no longer hosted.")
                    finished = True
                    continue

                logger.info("Failed to stop model: %s ", status)
                finished = True

            if status != "TRAINED":
                logger.error("Error stopping model: %s", status)
                raise Exception(f"Error stopping model: {status}")
        except ClientError:
            logger.exception("Couldn't stop hosting model.")
            raise
```

- Para obter detalhes da API, consulte a StopModelReferência da API AWSSDK for Python (Boto3).

Cenários

Criar um arquivo de manifesto

O exemplo de código a seguir mostra como criar um arquivo de manifesto do Lookout for Vision e carregá-lo para o Amazon S3.

Para obter mais informações, consulte Criando um arquivo de manifesto.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Datasets:

    @staticmethod
    def create_manifest_file_s3(s3_resource, image_s3_path, manifest_s3_path):
        """
        Creates a manifest file and uploads to Amazon S3.

        :param s3_resource: A Boto3 Amazon S3 resource.
        :param image_s3_path: The Amazon S3 path to the images referenced by the
                              manifest file. The images must be in an Amazon S3
 bucket
                              with the following folder structure.
                                s3://doc-example-bucket/<train or test>/
                                    normal/
                                    anomaly/
                              Place normal images in the normal folder and anomalous
                              images in the anomaly folder.
        :param manifest_s3_path: The Amazon S3 location in which to store the
 created
                                 manifest file.
        """
        output_manifest_file = "temp.manifest"
```

```
        try:
            # Current date and time in manifest file format.
            dttm = datetime.now().strftime("%Y-%m-%dT%H:%M:%S.%f")

            # Get bucket and folder from image and manifest file paths.
            bucket, prefix = image_s3_path.replace("s3://", "").split("/", 1)
            if prefix[-1] != "/":
                prefix += "/"
            manifest_bucket, manifest_prefix = manifest_s3_path.replace(
                "s3://", ""
            ).split("/", 1)

            with open(output_manifest_file, "w") as mfile:
                logger.info("Creating manifest file")
                src_bucket = s3_resource.Bucket(bucket)

                # Create JSON lines for anomalous images.
                for obj in src_bucket.objects.filter(
                    Prefix=prefix + "anomaly/", Delimiter="/"
                ):
                    image_path = f"s3://{src_bucket.name}/{obj.key}"
                    manifest = Datasets.create_json_line(image_path, "anomaly",
dttm)
                    mfile.write(json.dumps(manifest) + "\n")

                # Create json lines for normal images.
                for obj in src_bucket.objects.filter(
                    Prefix=prefix + "normal/", Delimiter="/"
                ):
                    image_path = f"s3://{src_bucket.name}/{obj.key}"
                    manifest = Datasets.create_json_line(image_path, "normal", dttm)
                    mfile.write(json.dumps(manifest) + "\n")

            logger.info("Uploading manifest file to %s", manifest_s3_path)
            s3_resource.Bucket(manifest_bucket).upload_file(
                output_manifest_file, manifest_prefix
            )
        except ClientError:
            logger.exception("Error uploading manifest.")
            raise
        except Exception:
            logger.exception("Error uploading manifest.")
            raise
        else:
```

```
            logger.info("Completed manifest file creation and upload.")
        finally:
            try:
                os.remove(output_manifest_file)
            except FileNotFoundError:
                pass

    @staticmethod
    def create_json_line(image, class_name, dttm):
        """
        Creates a single JSON line for an image.

        :param image: The S3 location for the image.
        :param class_name: The class of the image (normal or anomaly)
        :param dttm: The date and time that the JSON is created.
        """

        label = 0
        if class_name == "normal":
            label = 0
        elif class_name == "anomaly":
            label = 1
        else:
            logger.error("Unexpected label value: %s for %s", label, image)
            raise Exception(f"Unexpected label value: {label} for {image}")

        manifest = {
            "source-ref": image,
            "anomaly-label": label,
            "anomaly-label-metadata": {
                "confidence": 1,
                "job-name": "labeling-job/anomaly-label",
                "class-name": class_name,
                "human-annotated": "yes",
                "creation-date": dttm,
                "type": "groundtruth/image-classification",
            },
        }
        return manifest
```

Criar, treinar e iniciar um modelo

O exemplo de código a seguir mostra como criar, treinar e iniciar um modelo do Lookout for Vision.

SDK para Python (Boto3)

Criar e, opcionalmente, iniciar um modelo Amazon Lookout for Vision usando argumentos de linha de comando. O código de exemplo cria um novo projeto, treinando um conjunto de dados, teste opcional em conjunto de dados, e modelo. Depois que o treinamento do modelo for concluído, um script fornecido poderá ser usado para testar o modelo com uma imagem.

Este exemplo requer um conjunto de imagens para treinar o modelo. Você pode encontrar exemplos de imagens de placas de circuito GitHub que você pode usar para treinamento e teste. Para obter detalhes sobre como copiar essas imagens em um bucket do Amazon Simple Storage Service (Amazon S3), consulte Preparar imagens de exemplo.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Lookout for Vision

Exportar os conjuntos de dados de um projeto

O exemplo de código a seguir mostra como exportar o conjunto de dados de um projeto Lookout for Vision.

Para obter mais informações, consulte Exportando conjuntos de dados de um projeto (SDK).

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"""
Purpose
```

```
Shows how to export the datasets (manifest files and images)
from an Amazon Lookout for Vision project to a new Amazon
S3 location.
"""

import argparse
import json
import logging

import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def copy_file(s3_resource, source_file, destination_file):
    """
    Copies a file from a source Amazon S3 folder to a destination
    Amazon S3 folder.
    The destination can be in a different S3 bucket.
    :param s3: An Amazon S3 Boto3 resource.
    :param source_file: The Amazon S3 path to the source file.
    :param destination_file: The destination Amazon S3 path for
    the copy operation.
    """

    source_bucket, source_key = source_file.replace("s3://", "").split("/", 1)
    destination_bucket, destination_key = destination_file.replace("s3://",
 "").split(
        "/", 1
    )

    try:
        bucket = s3_resource.Bucket(destination_bucket)
        dest_object = bucket.Object(destination_key)
        dest_object.copy_from(CopySource={"Bucket": source_bucket, "Key":
 source_key})
        dest_object.wait_until_exists()
        logger.info("Copied %s to %s", source_file, destination_file)
    except ClientError as error:
        if error.response["Error"]["Code"] == "404":
            error_message = (
                f"Failed to copy {source_file} to "
                f"{destination_file}. : {error.response['Error']['Message']}"
```

```
            )
            logger.warning(error_message)
            error.response["Error"]["Message"] = error_message
        raise


def upload_manifest_file(s3_resource, manifest_file, destination):
    """
    Uploads a manifest file to a destination Amazon S3 folder.
    :param s3: An Amazon S3 Boto3 resource.
    :param manifest_file: The manifest file that you want to upload.
    :destination: The Amazon S3 folder location to upload the manifest
    file to.
    """

    destination_bucket, destination_key = destination.replace("s3://",
 "").split("/", 1)

    bucket = s3_resource.Bucket(destination_bucket)

    put_data = open(manifest_file, "rb")
    obj = bucket.Object(destination_key + manifest_file)

    try:
        obj.put(Body=put_data)
        obj.wait_until_exists()
        logger.info("Put manifest file '%s' to bucket '%s'.", obj.key,
 obj.bucket_name)
    except ClientError:
        logger.exception(
            "Couldn't put manifest file '%s' to bucket '%s'.", obj.key,
 obj.bucket_name
        )
        raise
    finally:
        if getattr(put_data, "close", None):
            put_data.close()


def get_dataset_types(lookoutvision_client, project):
    """
    Determines the types of the datasets (train or test) in an
    Amazon Lookout for Vision project.
    :param lookoutvision_client: A Lookout for Vision Boto3 client.
```

```
    :param project: The Lookout for Vision project that you want to check.
    :return: The dataset types in the project.
    """

    try:
        response = lookoutvision_client.describe_project(ProjectName=project)

        datasets = []

        for dataset in response["ProjectDescription"]["Datasets"]:
            if dataset["Status"] in ("CREATE_COMPLETE", "UPDATE_COMPLETE"):
                datasets.append(dataset["DatasetType"])
        return datasets

    except lookoutvision_client.exceptions.ResourceNotFoundException:
        logger.exception("Project %s not found.", project)
        raise


def process_json_line(s3_resource, entry, dataset_type, destination):
    """
    Creates a JSON line for a new manifest file, copies image and mask to
    destination.
    :param s3_resource: An Amazon S3 Boto3 resource.
    :param entry: A JSON line from the manifest file.
    :param dataset_type: The type (train or test) of the dataset that
    you want to create the manifest file for.
    :param destination: The destination Amazon S3 folder for the manifest
    file and dataset images.
    :return: A JSON line with details for the destination location.
    """
    entry_json = json.loads(entry)

    print(f"source: {entry_json['source-ref']}")

    # Use existing folder paths to ensure console added image names don't clash.
    bucket, key = entry_json["source-ref"].replace("s3://", "").split("/", 1)
    logger.info("Source location: %s/%s", bucket, key)

    destination_image_location = destination + dataset_type + "/images/" + key

    copy_file(s3_resource, entry_json["source-ref"], destination_image_location)

    # Update JSON for writing.
```

```
    entry_json["source-ref"] = destination_image_location

    if "anomaly-mask-ref" in entry_json:
        source_anomaly_ref = entry_json["anomaly-mask-ref"]
        mask_bucket, mask_key = source_anomaly_ref.replace("s3://", "").split("/",
 1)

        destination_mask_location = destination + dataset_type + "/masks/" +
 mask_key
        entry_json["anomaly-mask-ref"] = destination_mask_location

        copy_file(s3_resource, source_anomaly_ref, entry_json["anomaly-mask-ref"])

    return entry_json


def write_manifest_file(
    lookoutvision_client, s3_resource, project, dataset_type, destination
):
    """
    Creates a manifest file for a dataset. Copies the manifest file and
    dataset images (and masks, if present) to the specified Amazon S3 destination.
    :param lookoutvision_client: A Lookout for Vision Boto3 client.
    :param project: The Lookout for Vision project that you want to use.
    :param dataset_type: The type (train or test) of the dataset that
    you want to create the manifest file for.
    :param destination: The destination Amazon S3 folder for the manifest file
    and dataset images.
    """

    try:
        # Create a reusable Paginator
        paginator = lookoutvision_client.get_paginator("list_dataset_entries")

        # Create a PageIterator from the Paginator
        page_iterator = paginator.paginate(
            ProjectName=project,
            DatasetType=dataset_type,
            PaginationConfig={"PageSize": 100},
        )

        output_manifest_file = dataset_type + ".manifest"

        # Create manifest file then upload to Amazon S3 with images.
```

```
        with open(output_manifest_file, "w", encoding="utf-8") as manifest_file:
            for page in page_iterator:
                for entry in page["DatasetEntries"]:
                    try:
                        entry_json = process_json_line(
                            s3_resource, entry, dataset_type, destination
                        )

                        manifest_file.write(json.dumps(entry_json) + "\n")

                    except ClientError as error:
                        if error.response["Error"]["Code"] == "404":
                            print(error.response["Error"]["Message"])
                            print(f"Excluded JSON line: {entry}")
                        else:
                            raise
        upload_manifest_file(
            s3_resource, output_manifest_file, destination + "datasets/"
        )

    except ClientError:
        logger.exception("Problem getting dataset_entries")
        raise


def export_datasets(lookoutvision_client, s3_resource, project, destination):
    """
    Exports the datasets from an Amazon Lookout for Vision project to a specified
    Amazon S3 destination.
    :param project: The Lookout for Vision project that you want to use.
    :param destination: The destination Amazon S3 folder for the exported datasets.
    """
    # Add trailing backslash, if missing.
    destination = destination if destination[-1] == "/" else destination + "/"

    print(f"Exporting project {project} datasets to {destination}.")

    # Get each dataset and export to destination.

    dataset_types = get_dataset_types(lookoutvision_client, project)
    for dataset in dataset_types:
        logger.info("Copying %s dataset to %s.", dataset, destination)

        write_manifest_file(
```

```
            lookoutvision_client, s3_resource, project, dataset, destination
        )

    print("Exported dataset locations")
    for dataset in dataset_types:
        print(f"   {dataset}: {destination}datasets/{dataset}.manifest")

    print("Done.")


def add_arguments(parser):
    """
    Adds command line arguments to the parser.
    :param parser: The command line parser.
    """

    parser.add_argument("project", help="The project that contains the dataset.")
    parser.add_argument("destination", help="The destination Amazon S3 folder.")


def main():
    """
    Exports the datasets from an Amazon Lookout for Vision project to a
    destination Amazon S3 location.
    """
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    parser = argparse.ArgumentParser(usage=argparse.SUPPRESS)
    add_arguments(parser)

    args = parser.parse_args()

    try:
        session = boto3.Session(profile_name="lookoutvision-access")
        lookoutvision_client = session.client("lookoutvision")
        s3_resource = session.resource("s3")

        export_datasets(
            lookoutvision_client, s3_resource, args.project, args.destination
        )
    except ClientError as err:
        logger.exception(err)
        print(f"Failed: {format(err)}")
```

```
if __name__ == "__main__":
    main()
```

Encontrar um projeto com uma tag específica

O exemplo de código a seguir mostra como encontrar um projeto Lookout for Vision com uma tag específica.

Para obter mais informações, consulte Marcando modelos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import argparse
import boto3

from botocore.exceptions import ClientError


logger = logging.getLogger(__name__)


def find_tag(tags, key, value):
    """
    Finds a tag in the supplied list of tags.

    :param tags: A list of tags associated with a Lookout for Vision model.
    :param key: The tag to search for.
    :param value: The tag key value to search for.
    :return: True if the tag value exists, otherwise False.
    """

    found = False
```

```
    for tag in tags:
        if key == tag["Key"]:
            logger.info("\t\tMatch found for tag: %s value: %s.", key, value)
            found = True
            break
    return found


def find_tag_in_projects(lookoutvision_client, key, value):
    """
    Finds Lookout for Vision models tagged with the supplied key and value.

    :param lookoutvision_client: A Boto3 Lookout for Vision client.
    :param key: The tag key to find.
    :param value: The value of the tag that you want to find.
    return: A list of matching model versions (and model projects) that were found.
    """
    try:
        found_tags = []
        found = False
        projects = lookoutvision_client.list_projects()
        # Iterate through each project and models within a project.
        for project in projects["Projects"]:
            logger.info("Searching project: %s ...", project["ProjectName"])

            response_models = lookoutvision_client.list_models(
                ProjectName=project["ProjectName"]
            )
            for model in response_models["Models"]:
                model_description = lookoutvision_client.describe_model(
                    ProjectName=project["ProjectName"],
                    ModelVersion=model["ModelVersion"],
                )
                tags = lookoutvision_client.list_tags_for_resource(
                    ResourceArn=model_description["ModelDescription"]["ModelArn"]
                )

                logger.info(
                    "\tSearching model: %s for tag: %s value: %s.",
                    model_description["ModelDescription"]["ModelArn"],
                    key,
                    value,
                )
                if find_tag(tags["Tags"], key, value) is True:
```

```
                    found = True
                    logger.info(
                        "\t\tMATCH: Project: %s: model version %s",
                        project["ProjectName"],
                        model_description["ModelDescription"]["ModelVersion"],
                    )
                    found_tags.append(
                        {
                            "Project": project["ProjectName"],
                            "ModelVersion": model_description["ModelDescription"][
                                "ModelVersion"
                            ],
                        }
                    )
        if found is False:
            logger.info("No match for tag %s with value %s.", key, value)
    except ClientError:
        logger.exception("Problem finding tags.")
        raise
    else:
        return found_tags


def main():
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    parser = argparse.ArgumentParser(usage=argparse.SUPPRESS)
    parser.add_argument("tag", help="The tag that you want to find.")
    parser.add_argument("value", help="The tag value that you want to find.")
    args = parser.parse_args()
    key = args.tag
    value = args.value

    session = boto3.Session(profile_name="lookoutvision-access")

    lookoutvision_client = session.client("lookoutvision")

    print(f"Searching your models for tag: {key} with value: {value}.")
    tagged_models = find_tag_in_projects(lookoutvision_client, key, value)

    print("Matched models\n--------------")
    if len(tagged_models) > 0:
        for model in tagged_models:
            print(f"Project: {model['Project']}. model version:
{model['ModelVersion']}")
```

```
    else:
        print("No matches found.")


if __name__ == "__main__":
    main()
```

Listar modelos que estão atualmente hospedados

O exemplo de código a seguir mostra como listar modelos do Lookout for Vision que estão hospedados atualmente.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Hosting:

    @staticmethod
    def list_hosted(lookoutvision_client):
        """
        Displays a list of models in your account that are currently hosted.

        :param lookoutvision_client: A Boto3 Lookout for Vision client.
        """
        try:
            response = lookoutvision_client.list_projects()
            hosted = 0
            print("Hosted models\n-------------")

            for project in response["Projects"]:
                response_models = lookoutvision_client.list_models(
                    ProjectName=project["ProjectName"]
                )

                for model in response_models["Models"]:
```

```
                    model_description = lookoutvision_client.describe_model(
                        ProjectName=project["ProjectName"],
                        ModelVersion=model["ModelVersion"],
                    )

                    if model_description["ModelDescription"]["Status"] == "HOSTED":
                        print(
                            f"Project: {project['ProjectName']} Model version: "
                            f"{model['ModelVersion']}"
                        )
                        hosted += 1
            print(f"{hosted} model(s) hosted")
        except ClientError:
            logger.exception("Problem listing hosted models.")
            raise
```

Exemplos de Serviço gerenciado para Apache Flink usando SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com Serviço Gerenciado para Apache Flink.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Gerador de dados

Ações

Adicionar um stream de entrada a uma aplicação.

O exemplo de código a seguir mostra como adicionar um stream de entrada a uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def add_input(self, input_prefix, stream_arn, input_schema):
        """
        Adds an input stream to the application. The input stream data is mapped
        to an in-application stream that can be processed by your code running in
        Kinesis Data Analytics.

        :param input_prefix: The prefix prepended to in-application input stream
 names.
        :param stream_arn: The ARN of the input stream.
        :param input_schema: A schema that maps the data in the input stream to the
                             runtime environment. This can be automatically
 generated
                             by using `discover_input_schema` or you can create it
```

```
                                yourself.
        :return: Metadata about the newly added input.
        """
        try:
            response = self.analytics_client.add_application_input(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                Input={
                    "NamePrefix": input_prefix,
                    "KinesisStreamsInput": {"ResourceARN": stream_arn},
                    "InputSchema": input_schema,
                },
            )
            self.version_id = response["ApplicationVersionId"]
            logger.info("Add input stream %s to application %s.", stream_arn,
self.name)
        except ClientError:
            logger.exception(
                "Couldn't add input stream %s to application %s.", stream_arn,
self.name
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a AddApplicationInputReferência da API AWSSDK for Python (Boto3).

Adicionar um stream de saída a uma aplicação.

O exemplo de código a seguir mostra como adicionar um stream de saída a uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def add_output(self, in_app_stream_name, output_arn):
        """
        Adds an output stream to the application. Kinesis Data Analytics maps data
        from the specified in-application stream to the output stream.

        :param in_app_stream_name: The name of the in-application stream to map
                                   to the output stream.
        :param output_arn: The ARN of the output stream.
        :return: A list of metadata about the output resources currently assigned
                 to the application.
        """
        try:
            response = self.analytics_client.add_application_output(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                Output={
                    "Name": in_app_stream_name,
                    "KinesisStreamsOutput": {"ResourceARN": output_arn},
                    "DestinationSchema": {"RecordFormatType": "JSON"},
                },
            )
            outputs = response["OutputDescriptions"]
            self.version_id = response["ApplicationVersionId"]
            logging.info(
                "Added output %s to %s, which now has %s outputs.",
                output_arn,
                self.name,
                len(outputs),
            )
```

```
        except ClientError:
            logger.exception("Couldn't add output %s to %s.", output_arn, self.name)
            raise
        else:
            return outputs
```

- Para obter detalhes da API, consulte a AddApplicationOutputReferência da API AWSSDK for Python (Boto3).

Cria uma aplicação

O exemplo de código a seguir mostra como criar uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def create(self, app_name, role_arn, env="SQL-1_0"):
        """
        Creates a Kinesis Data Analytics application.
```

```
        :param app_name: The name of the application.
        :param role_arn: The ARN of a role that can be assumed by Kinesis Data
                         Analytics and grants needed permissions.
        :param env: The runtime environment of the application, such as SQL. Code
                    uploaded to the application runs in this environment.
        :return: Metadata about the newly created application.
        """
        try:
            response = self.analytics_client.create_application(
                ApplicationName=app_name,
                RuntimeEnvironment=env,
                ServiceExecutionRole=role_arn,
            )
            details = response["ApplicationDetail"]
            self._update_details(details)
            logger.info("Application %s created.", app_name)
        except ClientError:
            logger.exception("Couldn't create application %s.", app_name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a CreateApplicationReferência da API AWSSDK for Python (Boto3).

Deleta o aplicativo

O exemplo de código a seguir mostra como excluir uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def delete(self):
        """
        Deletes an application.
        """
        try:
            self.analytics_client.delete_application(
                ApplicationName=self.name, CreateTimestamp=self.create_timestamp
            )
            logger.info("Deleted application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't delete application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteApplicationReferência da API AWSSDK for Python (Boto3).

Descrever uma aplicação

O exemplo de código a seguir mostra como descrever uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def describe(self, name):
        """
        Gets metadata about an application.

        :param name: The name of the application to look up.
        :return: Metadata about the application.
        """
        try:
            response =
 self.analytics_client.describe_application(ApplicationName=name)
            details = response["ApplicationDetail"]
            self._update_details(details)
            logger.info("Got metadata for application %s.", name)
        except ClientError:
            logger.exception("Couldn't get metadata for application %s.", name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a DescribeApplicationReferência da API AWSSDK for Python (Boto3).

Descrever um snapshot de aplicação

O exemplo de código a seguir mostra como descrever uma aplicação do Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def describe_snapshot(self, application_name, snapshot_name):
        """
        Gets metadata about a previously saved application snapshot.

        :param application_name: The name of the application.
        :param snapshot_name: The name of the snapshot.
        :return: Metadata about the snapshot.
        """
        try:
            response = self.analytics_client.describe_application_snapshot(
                ApplicationName=application_name, SnapshotName=snapshot_name
```

```
            )
            snapshot = response["SnapshotDetails"]
            logger.info(
                "Got metadata for snapshot %s of application %s.",
                snapshot_name,
                application_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't get metadata for snapshot %s of application %s.",
                snapshot_name,
                application_name,
            )
            raise
        else:
            return snapshot
```

- Para obter detalhes da API, consulte a DescribeApplicationSnapshotReferência da API AWSSDK for Python (Boto3).

Descobrir um formato de dados para um stream

O exemplo de código a seguir mostra como descobrir um formato de dados para um fluxo de Serviço Gerenciado para Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
```

```
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def discover_input_schema(self, stream_arn, role_arn):
        """
        Discovers a schema that maps data in a stream to a format that is usable by
        an application's runtime environment. The stream must be active and have
        enough data moving through it for the service to sample. The returned schema
        can be used when you add the stream as an input to the application or you
can
        write your own schema.

        :param stream_arn: The ARN of the stream to map.
        :param role_arn: A role that lets Kinesis Data Analytics read from the
stream.
        :return: The discovered schema of the data in the input stream.
        """
        try:
            response = self.analytics_client.discover_input_schema(
                ResourceARN=stream_arn,
                ServiceExecutionRole=role_arn,
                InputStartingPositionConfiguration={"InputStartingPosition": "NOW"},
            )
            schema = response["InputSchema"]
            logger.info("Discovered input schema for stream %s.", stream_arn)
        except ClientError:
            logger.exception(
                "Couldn't discover input schema for stream %s.", stream_arn
            )
            raise
        else:
            return schema
```

- Para obter detalhes da API, consulte a DiscoverInputSchemaReferência da API AWSSDK for Python (Boto3).

Iniciar a aplicação

O exemplo de código a seguir mostra como iniciar um Serviço Gerenciado para a aplicação Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def start(self, input_id):
        """
        Starts an application. After the application is running, it reads from the
        specified input stream and runs the application code on the incoming data.

        :param input_id: The ID of the input to read.
        """
        try:
            self.analytics_client.start_application(
                ApplicationName=self.name,
                RunConfiguration={
                    "SqlRunConfigurations": [
                        {
                            "InputId": input_id,
                            "InputStartingPositionConfiguration": {
```

```
                                "InputStartingPosition": "NOW"
                            },
                        }
                    ]
                },
            )
            logger.info("Started application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't start application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a StartApplicationReferência da API AWSSDK for Python (Boto3).

Interromper a aplicação

O exemplo de código a seguir mostra como interromper uma aplicação do Serviço Gerenciado para o Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None
```

```
    def stop(self):
        """
        Stops an application. This stops the application from processing data but
        does not delete any resources.
        """
        try:
            self.analytics_client.stop_application(ApplicationName=self.name)
            logger.info("Stopping application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't stop application %s.", self.name)
            raise
```

- Para obter detalhes da API, consulte a StopApplicationReferência da API AWSSDK for Python (Boto3).

Atualizar uma aplicação

O exemplo de código a seguir mostra como atualizar uma aplicação do Serviço Gerenciado para o Apache Flink.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este exemplo atualiza o código que é executado em uma aplicação existente.

```
class KinesisAnalyticsApplicationV2:
    """Encapsulates Kinesis Data Analytics application functions."""

    def __init__(self, analytics_client):
        """
        :param analytics_client: A Boto3 Kinesis Data Analytics v2 client.
```

```
        """
        self.analytics_client = analytics_client
        self.name = None
        self.arn = None
        self.version_id = None
        self.create_timestamp = None


    def update_code(self, code):
        """
        Updates the code that runs in the application. The code must run in the
        runtime environment of the application, such as SQL. Application code
        typically reads data from in-application streams and transforms it in some
way.

        :param code: The code to upload. This completely replaces any existing code
                     in the application.
        :return: Metadata about the application.
        """
        try:
            response = self.analytics_client.update_application(
                ApplicationName=self.name,
                CurrentApplicationVersionId=self.version_id,
                ApplicationConfigurationUpdate={
                    "ApplicationCodeConfigurationUpdate": {
                        "CodeContentTypeUpdate": "PLAINTEXT",
                        "CodeContentUpdate": {"TextContentUpdate": code},
                    }
                },
            )
            details = response["ApplicationDetail"]
            self.version_id = details["ApplicationVersionId"]
            logger.info("Update code for application %s.", self.name)
        except ClientError:
            logger.exception("Couldn't update code for application %s.", self.name)
            raise
        else:
            return details
```

- Para obter detalhes da API, consulte a UpdateApplicationReferência da API AWSSDK for Python (Boto3).

Gerador de dados

Gerar um stream com um referenciador

O exemplo de código a seguir mostra como gerar um stream do Kinesis com um referenciador.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {"REFERRER": "http://www.amazon.com"}


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com anomalias da pressão arterial

O exemplo de código a seguir mostra como gerar um stream do Kinesis com anomalias de pressão arterial.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
from enum import Enum
import json
import random
import boto3

STREAM_NAME = "ExampleInputStream"


class PressureType(Enum):
    low = "LOW"
    normal = "NORMAL"
    high = "HIGH"


def get_blood_pressure(pressure_type):
    pressure = {"BloodPressureLevel": pressure_type.value}
    if pressure_type == PressureType.low:
        pressure["Systolic"] = random.randint(50, 80)
        pressure["Diastolic"] = random.randint(30, 50)
    elif pressure_type == PressureType.normal:
        pressure["Systolic"] = random.randint(90, 120)
        pressure["Diastolic"] = random.randint(60, 80)
    elif pressure_type == PressureType.high:
        pressure["Systolic"] = random.randint(130, 200)
        pressure["Diastolic"] = random.randint(90, 150)
    else:
        raise TypeError
    return pressure
```

```
def generate(stream_name, kinesis_client):
    while True:
        rnd = random.random()
        pressure_type = (
            PressureType.low
            if rnd < 0.005
            else PressureType.high
            if rnd > 0.995
            else PressureType.normal
        )
        blood_pressure = get_blood_pressure(pressure_type)
        print(blood_pressure)
        kinesis_client.put_record(
            StreamName=stream_name,
            Data=json.dumps(blood_pressure),
            PartitionKey="partitionkey",
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com dados em colunas

O exemplo de código a seguir mostra como gerar um stream do Kinesis com dados em colunas.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3
```

```
STREAM_NAME = "ExampleInputStream"


def get_data():
    return {"Col_A": "a", "Col_B": "b", "Col_C": "c", "Col_E_Unstructured": "x,y,z"}


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com anomalias da frequência cardíaca

O exemplo de código a seguir mostra como gerar um stream do Kinesis com anomalias da frequência cardíaca.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
from enum import Enum
import json
import random
import boto3

STREAM_NAME = "ExampleInputStream"
```

```
class RateType(Enum):
    normal = "NORMAL"
    high = "HIGH"


def get_heart_rate(rate_type):
    if rate_type == RateType.normal:
        rate = random.randint(60, 100)
    elif rate_type == RateType.high:
        rate = random.randint(150, 200)
    else:
        raise TypeError
    return {"heartRate": rate, "rateType": rate_type.value}


def generate(stream_name, kinesis_client, output=True):
    while True:
        rnd = random.random()
        rate_type = RateType.high if rnd < 0.01 else RateType.normal
        heart_rate = get_heart_rate(rate_type)
        if output:
            print(heart_rate)
        kinesis_client.put_record(
            StreamName=stream_name,
            Data=json.dumps(heart_rate),
            PartitionKey="partitionkey",
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com pontos de acesso

O exemplo de código a seguir mostra como gerar um stream do Kinesis com pontos de acesso.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
from pprint import pprint
import random
import time
import boto3

STREAM_NAME = "ExampleInputStream"


def get_hotspot(field, spot_size):
    hotspot = {
        "left": field["left"] + random.random() * (field["width"] - spot_size),
        "width": spot_size,
        "top": field["top"] + random.random() * (field["height"] - spot_size),
        "height": spot_size,
    }
    return hotspot


def get_record(field, hotspot, hotspot_weight):
    rectangle = hotspot if random.random() < hotspot_weight else field
    point = {
        "x": rectangle["left"] + random.random() * rectangle["width"],
        "y": rectangle["top"] + random.random() * rectangle["height"],
        "is_hot": "Y" if rectangle is hotspot else "N",
    }
    return {"Data": json.dumps(point), "PartitionKey": "partition_key"}


def generate(
    stream_name, field, hotspot_size, hotspot_weight, batch_size, kinesis_client
):
    """
```

```
    Generates points used as input to a hotspot detection algorithm.
    With probability hotspot_weight (20%), a point is drawn from the hotspot;
    otherwise, it is drawn from the base field. The location of the hotspot
    changes for every 1000 points generated.
    """
    points_generated = 0
    hotspot = None
    while True:
        if points_generated % 1000 == 0:
            hotspot = get_hotspot(field, hotspot_size)
        records = [
            get_record(field, hotspot, hotspot_weight) for _ in range(batch_size)
        ]
        points_generated += len(records)
        pprint(records)
        kinesis_client.put_records(StreamName=stream_name, Records=records)

        time.sleep(0.1)


if __name__ == "__main__":
    generate(
        stream_name=STREAM_NAME,
        field={"left": 0, "width": 10, "top": 0, "height": 10},
        hotspot_size=1,
        hotspot_weight=0.2,
        batch_size=10,
        kinesis_client=boto3.client("kinesis"),
    )
```

Gerar um stream com entradas de registro (log)

O exemplo de código a seguir mostra como gerar um stream do Kinesis com entradas de registro (log).

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {
        "LOGENTRY": "203.0.113.24 - - [25/Mar/2018:15:25:37 -0700] "
        '"GET /index.php HTTP/1.1" 200 125 "-" '
        '"Mozilla/5.0 [en] Gecko/20100101 Firefox/52.0"'
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com dados escalonados

O exemplo de código a seguir mostra como gerar um stream do Kinesis com dados escalonados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import datetime
import json
import random
import time
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    event_time = datetime.datetime.utcnow() - datetime.timedelta(seconds=10)
    return {
        "EVENT_TIME": event_time.isoformat(),
        "TICKER": random.choice(["AAPL", "AMZN", "MSFT", "INTC", "TBV"]),
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        # Send six records, ten seconds apart, with the same event time and ticker
        for _ in range(6):
            print(data)
            kinesis_client.put_record(
                StreamName=stream_name,
                Data=json.dumps(data),
                PartitionKey="partitionkey",
            )
            time.sleep(10)


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com dados de cotação da bolsa

O exemplo de código a seguir mostra como gerar um stream do Kinesis com dados da bolsa.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import datetime
import json
import random
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {
        "EVENT_TIME": datetime.datetime.now().isoformat(),
        "TICKER": random.choice(["AAPL", "AMZN", "MSFT", "INTC", "TBV"]),
        "PRICE": round(random.random() * 100, 2),
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )
```

```
if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com dois tipos de dados

O exemplo de código a seguir mostra como gerar um stream do Kinesis com dois tipos de dados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import random
import boto3

STREAM_NAME = "OrdersAndTradesStream"
PARTITION_KEY = "partition_key"


def get_order(order_id, ticker):
    return {
        "RecordType": "Order",
        "Oid": order_id,
        "Oticker": ticker,
        "Oprice": random.randint(500, 10000),
        "Otype": "Sell",
    }


def get_trade(order_id, trade_id, ticker):
    return {
        "RecordType": "Trade",
        "Tid": trade_id,
        "Toid": order_id,
        "Tticker": ticker,
```

```
        "Tprice": random.randint(0, 3000),
    }


def generate(stream_name, kinesis_client):
    order_id = 1
    while True:
        ticker = random.choice(["AAAA", "BBBB", "CCCC"])
        order = get_order(order_id, ticker)
        print(order)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(order),
 PartitionKey=PARTITION_KEY
        )
        for trade_id in range(1, random.randint(0, 6)):
            trade = get_trade(order_id, trade_id, ticker)
            print(trade)
            kinesis_client.put_record(
                StreamName=stream_name,
                Data=json.dumps(trade),
                PartitionKey=PARTITION_KEY,
            )
        order_id += 1


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Gerar um stream com dados de registro (log) web

O exemplo de código a seguir mostra como gerar um stream do Kinesis com dados de registros (log) web.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import json
import boto3

STREAM_NAME = "ExampleInputStream"


def get_data():
    return {
        "log": "192.168.254.30 - John [24/May/2004:22:01:02 -0700] "
        '"GET /icons/apache_pb.gif HTTP/1.1" 304 0'
    }


def generate(stream_name, kinesis_client):
    while True:
        data = get_data()
        print(data)
        kinesis_client.put_record(
            StreamName=stream_name, Data=json.dumps(data),
 PartitionKey="partitionkey"
        )


if __name__ == "__main__":
    generate(STREAM_NAME, boto3.client("kinesis"))
```

Exemplos de Organizações usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Organizations.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Anexar uma política a uma meta

O exemplo de código a seguir mostra como anexar uma política de Organizações a um destino.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def attach_policy(policy_id, target_id, orgs_client):
    """
    Attaches a policy to a target. The target is an organization root, account, or
    organizational unit.

    :param policy_id: The ID of the policy to attach.
    :param target_id: The ID of the resources to attach the policy to.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.attach_policy(PolicyId=policy_id, TargetId=target_id)
        logger.info("Attached policy %s to target %s.", policy_id, target_id)
    except ClientError:
        logger.exception(
            "Couldn't attach policy %s to target %s.", policy_id, target_id
        )
        raise
```

- Para obter detalhes da API, consulte a AttachPolicyReferência da API AWSSDK for Python (Boto3).

Criar uma política

O exemplo de código a seguir mostra como criar uma política do Organizações.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_policy(name, description, content, policy_type, orgs_client):
    """
    Creates a policy.

    :param name: The name of the policy.
    :param description: The description of the policy.
    :param content: The policy content as a dict. This is converted to JSON before
                    it is sent to AWS. The specific format depends on the policy
 type.
    :param policy_type: The type of the policy.
    :param orgs_client: The Boto3 Organizations client.
    :return: The newly created policy.
    """
    try:
        response = orgs_client.create_policy(
            Name=name,
            Description=description,
            Content=json.dumps(content),
            Type=policy_type,
        )
        policy = response["Policy"]
        logger.info("Created policy %s.", name)
    except ClientError:
        logger.exception("Couldn't create policy %s.", name)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a CreatePolicyReferência da API AWSSDK for Python (Boto3).

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do Organizações.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_policy(policy_id, orgs_client):
    """
    Deletes a policy.

    :param policy_id: The ID of the policy to delete.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.delete_policy(PolicyId=policy_id)
        logger.info("Deleted policy %s.", policy_id)
    except ClientError:
        logger.exception("Couldn't delete policy %s.", policy_id)
        raise
```

- Para obter detalhes da API, consulte a DeletePolicyReferência da API AWSSDK for Python (Boto3).

Descrever uma política

O exemplo de código a seguir mostra como descrever uma política do Organizações.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def describe_policy(policy_id, orgs_client):
    """
    Describes a policy.

    :param policy_id: The ID of the policy to describe.
    :param orgs_client: The Boto3 Organizations client.
    :return: The description of the policy.
    """
    try:
        response = orgs_client.describe_policy(PolicyId=policy_id)
        policy = response["Policy"]
        logger.info("Got policy %s.", policy_id)
    except ClientError:
        logger.exception("Couldn't get policy %s.", policy_id)
        raise
    else:
        return policy
```

- Para obter detalhes da API, consulte a DescribePolicyReferência da API AWSSDK for Python (Boto3).

Desanexar uma política de uma meta

O exemplo de código a seguir mostra como desanexar uma política do Organizações de um destino.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def detach_policy(policy_id, target_id, orgs_client):
    """
    Detaches a policy from a target.

    :param policy_id: The ID of the policy to detach.
    :param target_id: The ID of the resource where the policy is currently attached.
    :param orgs_client: The Boto3 Organizations client.
    """
    try:
        orgs_client.detach_policy(PolicyId=policy_id, TargetId=target_id)
        logger.info("Detached policy %s from target %s.", policy_id, target_id)
    except ClientError:
        logger.exception(
            "Couldn't detach policy %s from target %s.", policy_id, target_id
        )
        raise
```

- Para obter detalhes da API, consulte a DetachPolicyReferência da API AWSSDK for Python (Boto3).

Listar políticas

O exemplo de código a seguir mostra como listar políticas do Organizações.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_policies(policy_filter, orgs_client):
    """
    Lists the policies for the account, limited to the specified filter.

    :param policy_filter: The kind of policies to return.
    :param orgs_client: The Boto3 Organizations client.
    :return: The list of policies found.
    """
    try:
        response = orgs_client.list_policies(Filter=policy_filter)
        policies = response["Policies"]
        logger.info("Found %s %s policies.", len(policies), policy_filter)
    except ClientError:
        logger.exception("Couldn't get %s policies.", policy_filter)
        raise
    else:
        return policies
```

- Para obter detalhes da API, consulte a ListPoliciesReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon Pinpoint usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar e-mails e mensagens de texto

O exemplo de código a seguir mostra como enviar e-mail e mensagens de texto com o Amazon Pinpoint.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_email_message(
    pinpoint_client,
    app_id,
    sender,
    to_addresses,
    char_set,
    subject,
```

```
    html_message,
    text_message,
):
    """
    Sends an email message with HTML and plain text versions.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param app_id: The Amazon Pinpoint project ID to use when you send this message.
    :param sender: The "From" address. This address must be verified in
                   Amazon Pinpoint in the AWS Region you're using to send email.
    :param to_addresses: The addresses on the "To" line. If your Amazon Pinpoint
 account
                         is in the sandbox, these addresses must be verified.
    :param char_set: The character encoding to use for the subject line and message
                     body of the email.
    :param subject: The subject line of the email.
    :param html_message: The body of the email for recipients whose email clients
 can
                         display HTML content.
    :param text_message: The body of the email for recipients whose email clients
                         don't support HTML content.
    :return: A dict of to_addresses and their message IDs.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=app_id,
            MessageRequest={
                "Addresses": {
                    to_address: {"ChannelType": "EMAIL"} for to_address in
 to_addresses
                },
                "MessageConfiguration": {
                    "EmailMessage": {
                        "FromAddress": sender,
                        "SimpleEmail": {
                            "Subject": {"Charset": char_set, "Data": subject},
                            "HtmlPart": {"Charset": char_set, "Data": html_message},
                            "TextPart": {"Charset": char_set, "Data": text_message},
                        },
                    }
                },
            },
        )
    except ClientError:
```

```
        logger.exception("Couldn't send email.")
        raise
    else:
        return {
            to_address: message["MessageId"]
            for to_address, message in response["MessageResponse"]["Result"].items()
        }


def main():
    app_id = "ce796be37f32f178af652b26eexample"
    sender = "sender@example.com"
    to_address = "recipient@example.com"
    char_set = "UTF-8"
    subject = "Amazon Pinpoint Test (SDK for Python (Boto3))"
    text_message = """Amazon Pinpoint Test (SDK for Python)
    -------------------------------------
    This email was sent with Amazon Pinpoint using the AWS SDK for Python (Boto3).
    For more information, see https://aws.amazon.com/sdk-for-python/
                """
    html_message = """<html>
    <head></head>
    <body>
      <h1>Amazon Pinpoint Test (SDK for Python (Boto3)</h1>
      <p>This email was sent with
        <a href='https://aws.amazon.com/pinpoint/'>Amazon Pinpoint</a> using the
        <a href='https://aws.amazon.com/sdk-for-python/'>
          AWS SDK for Python (Boto3)</a>.</p>
    </body>
    </html>
                """

    print("Sending email.")
    message_ids = send_email_message(
        boto3.client("pinpoint"),
        app_id,
        sender,
        [to_address],
        char_set,
        subject,
        html_message,
        text_message,
    )
    print(f"Message sent! Message IDs: {message_ids}")
```

```
if __name__ == "__main__":
    main()
```

Envie uma mensagem SMS.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_sms_message(
    pinpoint_client,
    app_id,
    origination_number,
    destination_number,
    message,
    message_type,
):
    """
    Sends an SMS message with Amazon Pinpoint.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param app_id: The Amazon Pinpoint project/application ID to use when you send
                   this message. The SMS channel must be enabled for the project or
                   application.
    :param destination_number: The recipient's phone number in E.164 format.
    :param origination_number: The phone number to send the message from. This phone
                               number must be associated with your Amazon Pinpoint
                               account and be in E.164 format.
    :param message: The content of the SMS message.
    :param message_type: The type of SMS message that you want to send. If you send
                         time-sensitive content, specify TRANSACTIONAL. If you send
                         marketing-related content, specify PROMOTIONAL.
    :return: The ID of the message.
    """
    try:
        response = pinpoint_client.send_messages(
```

```
            ApplicationId=app_id,
            MessageRequest={
                "Addresses": {destination_number: {"ChannelType": "SMS"}},
                "MessageConfiguration": {
                    "SMSMessage": {
                        "Body": message,
                        "MessageType": message_type,
                        "OriginationNumber": origination_number,
                    }
                },
            },
        )
    except ClientError:
        logger.exception("Couldn't send message.")
        raise
    else:
        return response["MessageResponse"]["Result"][destination_number]
["MessageId"]


def main():
    app_id = "ce796be37f32f178af652b26eexample"
    origination_number = "+12065550199"
    destination_number = "+14255550142"
    message = (
        "This is a sample message sent from Amazon Pinpoint by using the AWS SDK for
 "
        "Python (Boto 3)."
    )
    message_type = "TRANSACTIONAL"

    print("Sending SMS message.")
    message_id = send_sms_message(
        boto3.client("pinpoint"),
        app_id,
        origination_number,
        destination_number,
        message,
        message_type,
    )
    print(f"Message sent! Message ID: {message_id}.")


if __name__ == "__main__":
```

```
    main()
```

- Para obter detalhes da API, consulte a SendMessagesReferência da API AWSSDK for Python (Boto3).

Enviar mensagens de e-mails e de texto modeladas

O exemplo de código a seguir mostra como enviar e-mails e mensagens de texto modeladas com o Amazon Pinpoint.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envie uma mensagem de e-mail com um modelo de e-mail existente.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_templated_email_message(
    pinpoint_client, project_id, sender, to_addresses, template_name,
 template_version
):
    """
    Sends an email message with HTML and plain text versions.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param project_id: The Amazon Pinpoint project ID to use when you send this
 message.
    :param sender: The "From" address. This address must be verified in
                   Amazon Pinpoint in the AWS Region you're using to send email.
    :param to_addresses: The addresses on the "To" line. If your Amazon Pinpoint
```

```
                        account is in the sandbox, these addresses must be
 verified.
    :param template_name: The name of the email template to use when sending the
 message.
    :param template_version: The version number of the message template.

    :return: A dict of to_addresses and their message IDs.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=project_id,
            MessageRequest={
                "Addresses": {
                    to_address: {"ChannelType": "EMAIL"} for to_address in
 to_addresses
                },
                "MessageConfiguration": {"EmailMessage": {"FromAddress": sender}},
                "TemplateConfiguration": {
                    "EmailTemplate": {
                        "Name": template_name,
                        "Version": template_version,
                    }
                },
            },
        )
    except ClientError:
        logger.exception("Couldn't send email.")
        raise
    else:
        return {
            to_address: message["MessageId"]
            for to_address, message in response["MessageResponse"]["Result"].items()
        }


def main():
    project_id = "296b04b342374fceb661bf494example"
    sender = "sender@example.com"
    to_addresses = ["recipient@example.com"]
    template_name = "My_Email_Template"
    template_version = "1"

    print("Sending email.")
    message_ids = send_templated_email_message(
```

```
        boto3.client("pinpoint"),
        project_id,
        sender,
        to_addresses,
        template_name,
        template_version,
    )
    print(f"Message sent! Message IDs: {message_ids}")


if __name__ == "__main__":
    main()
```

Envie uma mensagem de texto com um modelo de SMS existente.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_templated_sms_message(
    pinpoint_client,
    project_id,
    destination_number,
    message_type,
    origination_number,
    template_name,
    template_version,
):
    """
    Sends an SMS message to a specific phone number using a pre-defined template.

    :param pinpoint_client: A Boto3 Pinpoint client.
    :param project_id: An Amazon Pinpoint project (application) ID.
    :param destination_number: The phone number to send the message to.
    :param message_type: The type of SMS message (promotional or transactional).
    :param origination_number: The phone number that the message is sent from.
    :param template_name: The name of the SMS template to use when sending the
 message.
    :param template_version: The version number of the message template.
```

```
    :return The ID of the message.
    """
    try:
        response = pinpoint_client.send_messages(
            ApplicationId=project_id,
            MessageRequest={
                "Addresses": {destination_number: {"ChannelType": "SMS"}},
                "MessageConfiguration": {
                    "SMSMessage": {
                        "MessageType": message_type,
                        "OriginationNumber": origination_number,
                    }
                },
                "TemplateConfiguration": {
                    "SMSTemplate": {"Name": template_name, "Version":
 template_version}
                },
            },
        )

    except ClientError:
        logger.exception("Couldn't send message.")
        raise
    else:
        return response["MessageResponse"]["Result"][destination_number]
["MessageId"]


def main():
    region = "us-east-1"
    origination_number = "+18555550001"
    destination_number = "+14255550142"
    project_id = "7353f53e6885409fa32d07cedexample"
    message_type = "TRANSACTIONAL"
    template_name = "My_SMS_Template"
    template_version = "1"
    message_id = send_templated_sms_message(
        boto3.client("pinpoint", region_name=region),
        project_id,
        destination_number,
        message_type,
        origination_number,
        template_name,
```

```
        template_version,
    )
    print(f"Message sent! Message ID: {message_id}.")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a SendMessagesReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon Pinpoint SMS e API de voz usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com a API de voz e SMS do Amazon Pinpoint.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar uma mensagem de voz com Amazon Pinpoint SMS e Voice API

O exemplo de código a seguir mostra como enviar uma mensagem de voz com Amazon Pinpoint SMS e Voice API.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def send_voice_message(
    sms_voice_client,
    origination_number,
    caller_id,
    destination_number,
    language_code,
    voice_id,
    ssml_message,
):
    """
    Sends a voice message using speech synthesis provided by Amazon Polly.

    :param sms_voice_client: A Boto3 PinpointSMSVoice client.
    :param origination_number: The phone number that the message is sent from.
                               The phone number must be associated with your Amazon
                               Pinpoint account and be in E.164 format.
    :param caller_id: The phone number that you want to appear on the recipient's
                      device. The phone number must be associated with your Amazon
                      Pinpoint account and be in E.164 format.
    :param destination_number: The recipient's phone number. Specify the phone
                               number in E.164 format.
    :param language_code: The language to use when sending the message.
    :param voice_id: The Amazon Polly voice that you want to use to send the
 message.
    :param ssml_message: The content of the message. This example uses SSML to
 control
```

```
                        certain aspects of the message, such as the volume and the
                        speech rate. The message must not contain line breaks.
    :return: The ID of the message.
    """
    try:
        response = sms_voice_client.send_voice_message(
            DestinationPhoneNumber=destination_number,
            OriginationPhoneNumber=origination_number,
            CallerId=caller_id,
            Content={
                "SSMLMessage": {
                    "LanguageCode": language_code,
                    "VoiceId": voice_id,
                    "Text": ssml_message,
                }
            },
        )
    except ClientError:
        logger.exception(
            "Couldn't send message from %s to %s.",
            origination_number,
            destination_number,
        )
        raise
    else:
        return response["MessageId"]


def main():
    origination_number = "+12065550110"
    caller_id = "+12065550199"
    destination_number = "+12065550142"
    language_code = "en-US"
    voice_id = "Matthew"
    ssml_message = (
        "<speak>"
        "This is a test message sent from <emphasis>Amazon Pinpoint</emphasis> "
        "using the <break strength='weak'/>AWS SDK for Python (Boto3). "
        "<amazon:effect phonation='soft'>Thank you for listening."
        "</amazon:effect>"
        "</speak>"
    )
    print(f"Sending voice message from {origination_number} to
 {destination_number}.")
```

```
    message_id = send_voice_message(
        boto3.client("pinpoint-sms-voice"),
        origination_number,
        caller_id,
        destination_number,
        language_code,
        voice_id,
        ssml_message,
    )
    print(f"Message sent!\nMessage ID: {message_id}")


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte a SendVoiceMessageReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon Polly usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Polly.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Obter um léxico

O exemplo de código a seguir mostra como obter um léxico do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def get_lexicon(self, name):
        """
        Gets metadata and contents of an existing lexicon.

        :param name: The name of the lexicon to retrieve.
        :return: The retrieved lexicon.
        """
        try:
            response = self.polly_client.get_lexicon(Name=name)
            logger.info("Got lexicon %s.", name)
        except ClientError:
            logger.exception("Couldn't get lexicon %s.", name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetLexiconReferência da API AWSSDK for Python (Boto3).

Obter dados sobre uma tarefa de síntese de fala

O exemplo de código a seguir mostra como obter dados sobre uma tarefa de síntese de fala assíncrona existente do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def get_speech_synthesis_task(self, task_id):
        """
        Gets metadata about an asynchronous speech synthesis task, such as its
 status.

        :param task_id: The ID of the task to retrieve.
        :return: Metadata about the task.
        """
```

```
        try:
            response = self.polly_client.get_speech_synthesis_task(TaskId=task_id)
            task = response["SynthesisTask"]
            logger.info("Got synthesis task. Status is %s.", task["TaskStatus"])
        except ClientError:
            logger.exception("Couldn't get synthesis task %s.", task_id)
            raise
        else:
            return task
```

- Para obter detalhes da API, consulte a GetSpeechSynthesisTaskReferência da API AWSSDK for Python (Boto3).

Obter vozes disponíveis para síntese

O exemplo de código a seguir mostra como obter vozes disponíveis para síntese do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def describe_voices(self):
```

```
        """
        Gets metadata about available voices.

        :return: The list of voice metadata.
        """
        try:
            response = self.polly_client.describe_voices()
            self.voice_metadata = response["Voices"]
            logger.info("Got metadata about %s voices.", len(self.voice_metadata))
        except ClientError:
            logger.exception("Couldn't get voice metadata.")
            raise
        else:
            return self.voice_metadata
```

- Para obter detalhes da API, consulte a DescribeVoicesReferência da API AWSSDK for Python (Boto3).

Listar léxicos de pronúncia

O exemplo de código a seguir mostra como listar os léxicos de pronúncia do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
```

```
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def list_lexicons(self):
        """
        Lists lexicons in the current account.

        :return: The list of lexicons.
        """
        try:
            response = self.polly_client.list_lexicons()
            lexicons = response["Lexicons"]
            logger.info("Got %s lexicons.", len(lexicons))
        except ClientError:
            logger.exception(
                "Couldn't get  %s.",
            )
            raise
        else:
            return lexicons
```

- Para obter detalhes da API, consulte a ListLexiconsReferência da API AWSSDK for Python (Boto3).

Iniciar uma tarefa de síntese de fala

O exemplo de código a seguir mostra como iniciar uma tarefa de síntese de fala assíncrona do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
```

```
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def do_synthesis_task(
        self,
        text,
        engine,
        voice,
        audio_format,
        s3_bucket,
        lang_code=None,
        include_visemes=False,
        wait_callback=None,
    ):
        """
        Start an asynchronous task to synthesize speech or speech marks, wait for
        the task to complete, retrieve the output from Amazon S3, and return the
        data.

        An asynchronous task is required when the text is too long for near-real
time
        synthesis.

        :param text: The text to synthesize.
        :param engine: The kind of engine used. Can be standard or neural.
        :param voice: The ID of the voice to use.
        :param audio_format: The audio format to return for synthesized speech. When
                             speech marks are synthesized, the output format is
JSON.
        :param s3_bucket: The name of an existing Amazon S3 bucket that you have
                          write access to. Synthesis output is written to this
bucket.
        :param lang_code: The language code of the voice to use. This has an effect
                          only when a bilingual voice is selected.
```

```
        :param include_visemes: When True, a second request is made to Amazon Polly
                                to synthesize a list of visemes, using the specified
                                text and voice. A viseme represents the visual
position
                                of the face and mouth when saying part of a word.
        :param wait_callback: A callback function that is called periodically during
                              task processing, to give the caller an opportunity to
                              take action, such as to display status.
        :return: The audio stream that contains the synthesized speech and a list
                 of visemes that are associated with the speech audio.
        """
        try:
            kwargs = {
                "Engine": engine,
                "OutputFormat": audio_format,
                "OutputS3BucketName": s3_bucket,
                "Text": text,
                "VoiceId": voice,
            }
            if lang_code is not None:
                kwargs["LanguageCode"] = lang_code
            response = self.polly_client.start_speech_synthesis_task(**kwargs)
            speech_task = response["SynthesisTask"]
            logger.info("Started speech synthesis task %s.", speech_task["TaskId"])

            viseme_task = None
            if include_visemes:
                kwargs["OutputFormat"] = "json"
                kwargs["SpeechMarkTypes"] = ["viseme"]
                response = self.polly_client.start_speech_synthesis_task(**kwargs)
                viseme_task = response["SynthesisTask"]
                logger.info("Started viseme synthesis task %s.",
viseme_task["TaskId"])
        except ClientError:
            logger.exception("Couldn't start synthesis task.")
            raise
        else:
            bucket = self.s3_resource.Bucket(s3_bucket)
            audio_stream = self._wait_for_task(
                10, speech_task["TaskId"], "speech", wait_callback, bucket
            )

            visemes = None
            if include_visemes:
```

```
                viseme_data = self._wait_for_task(
                    10, viseme_task["TaskId"], "viseme", wait_callback, bucket
                )
                visemes = [
                    json.loads(v) for v in viseme_data.read().decode().split() if v
                ]

            return audio_stream, visemes
```

- Para obter detalhes da API, consulte a StartSpeechSynthesisTaskReferência da API AWSSDK for Python (Boto3).

Armazenar léxicos de pronúncia

O exemplo de código a seguir mostra como armazenar um léxico de pronúncia do Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None


    def create_lexicon(self, name, content):
        """
```

```
        Creates a lexicon with the specified content. A lexicon contains custom
        pronunciations.

        :param name: The name of the lexicon.
        :param content: The content of the lexicon.
        """
        try:
            self.polly_client.put_lexicon(Name=name, Content=content)
            logger.info("Created lexicon %s.", name)
        except ClientError:
            logger.exception("Couldn't create lexicon %s.")
            raise
```

- Para obter detalhes da API, consulte a PutLexiconReferência da API AWSSDK for Python (Boto3).

Sintetizar fala a partir de texto

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class PollyWrapper:
    """Encapsulates Amazon Polly functions."""

    def __init__(self, polly_client, s3_resource):
        """
        :param polly_client: A Boto3 Amazon Polly client.
        :param s3_resource: A Boto3 Amazon Simple Storage Service (Amazon S3)
 resource.
        """
        self.polly_client = polly_client
        self.s3_resource = s3_resource
        self.voice_metadata = None
```

```
    def synthesize(
        self, text, engine, voice, audio_format, lang_code=None,
include_visemes=False
    ):
        """
        Synthesizes speech or speech marks from text, using the specified voice.

        :param text: The text to synthesize.
        :param engine: The kind of engine used. Can be standard or neural.
        :param voice: The ID of the voice to use.
        :param audio_format: The audio format to return for synthesized speech. When
                             speech marks are synthesized, the output format is
JSON.
        :param lang_code: The language code of the voice to use. This has an effect
                          only when a bilingual voice is selected.
        :param include_visemes: When True, a second request is made to Amazon Polly
                                to synthesize a list of visemes, using the specified
                                text and voice. A viseme represents the visual
position
                                of the face and mouth when saying part of a word.
        :return: The audio stream that contains the synthesized speech and a list
                 of visemes that are associated with the speech audio.
        """
        try:
            kwargs = {
                "Engine": engine,
                "OutputFormat": audio_format,
                "Text": text,
                "VoiceId": voice,
            }
            if lang_code is not None:
                kwargs["LanguageCode"] = lang_code
            response = self.polly_client.synthesize_speech(**kwargs)
            audio_stream = response["AudioStream"]
            logger.info("Got audio stream spoken by %s.", voice)
            visemes = None
            if include_visemes:
                kwargs["OutputFormat"] = "json"
                kwargs["SpeechMarkTypes"] = ["viseme"]
                response = self.polly_client.synthesize_speech(**kwargs)
                visemes = [
                    json.loads(v)
```

```
                    for v in response["AudioStream"].read().decode().split()
                    if v
                ]
                logger.info("Got %s visemes.", len(visemes))
        except ClientError:
            logger.exception("Couldn't get audio stream.")
            raise
        else:
            return audio_stream, visemes
```

- Para obter detalhes da API, consulte a SynthesizeSpeechReferência da API AWSSDK for Python (Boto3).

Cenários

Criar um aplicativo de sincronização labial

O exemplo de código a seguir mostra como criar uma aplicação de sincronização de lábios com o Amazon Polly.

SDK para Python (Boto3)

Mostra como usar o Amazon Polly e o Tkinter para criar um aplicativo de sincronização labial que exibe um rosto animado falando junto com a fala sintetizada pelo Amazon Polly. A sincronização labial é realizada solicitando uma lista de fonemas do Amazon Polly que correspondam à fala sintetizada.

- Obter metadados de voz do Amazon Polly e exibir os mesmos em uma aplicação Tkinter.
- Obter áudio de fala sintetizado e marcas de fala de fonema correspondentes do Amazon Polly.
- Reproduzir o áudio com movimentos sincronizados da boca em um rosto animado.
- Enviar tarefas de síntese assíncrona para textos longos e recuperar a saída de um bucket do Amazon Simple Storage Service (Amazon S3).

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly

Exemplos do Amazon RDS usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma instância de banco de dados

O exemplo de código a seguir mostra como criar uma instância do Amazon RDS DB e aguardar até que se torne disponível.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
```

```
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_db_instance(
        self,
        db_name,
        instance_id,
        parameter_group_name,
        db_engine,
        db_engine_version,
        instance_class,
        storage_type,
        allocated_storage,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB instance.

        :param db_name: The name of the database that is created in the DB instance.
        :param instance_id: The ID to give the newly created DB instance.
        :param parameter_group_name: A parameter group to associate with the DB
instance.
        :param db_engine: The database engine of a database to create in the DB
instance.
        :param db_engine_version: The engine version for the created database.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :param storage_type: The storage type of the DB instance.
        :param allocated_storage: The amount of storage allocated on the DB
instance, in GiBs.
        :param admin_name: The name of the admin user for the created database.
        :param admin_password: The admin password for the created database.
        :return: Data about the newly created DB instance.
        """
```

```
        try:
            response = self.rds_client.create_db_instance(
                DBName=db_name,
                DBInstanceIdentifier=instance_id,
                DBParameterGroupName=parameter_group_name,
                Engine=db_engine,
                EngineVersion=db_engine_version,
                DBInstanceClass=instance_class,
                StorageType=storage_type,
                AllocatedStorage=allocated_storage,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte CreateDBInstance na Referência da API do AWS SDK para Python (Boto3).

Criar um grupo de parâmetros de banco de dados

Os exemplos de código a seguir mostram como criar um grupo de parâmetros do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB parameter group that is based on the specified parameter group
        family.

        :param parameter_group_name: The name of the newly created parameter group.
        :param parameter_group_family: The family that is used as the basis of the
 new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
```

```
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API CreateDB ParameterGroup no AWSSDK for Python (Boto3).

Criar um snapshot de uma instância de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de uma instância do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)
```

```
    def create_snapshot(self, snapshot_id, instance_id):
        """
        Creates a snapshot of a DB instance.

        :param snapshot_id: The ID to give the created snapshot.
        :param instance_id: The ID of the DB instance to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_snapshot(
                DBSnapshotIdentifier=snapshot_id, DBInstanceIdentifier=instance_id
            )
            snapshot = response["DBSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK para Python (Boto3).

Excluir uma instância de banco de dados

Os exemplos de código a seguir mostram como excluir uma instância do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DeleteDBInstance na Referência da API do AWS SDK para Python (Boto3).

Excluir um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como excluir um grupo de parâmetros do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
```

```
        """
        try:
            self.rds_client.delete_db_parameter_group(
                DBParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte Referência da API DeleteDB ParameterGroup no AWSSDK for Python (Boto3).

Descrever instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever instâncias do Amazon RDS DB

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
```

```
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return db_inst
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK para Python (Boto3).

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros de do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The parameter group.
        """
        try:
            response = self.rds_client.describe_db_parameter_groups(
                DBParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
                logger.info("Parameter group %s does not exist.",
 parameter_group_name)
```

```
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups na Referência da API AWSSDK for Python (Boto3).

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as vesões de mecanismo de banco de dados do Amazon RDS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
```

```
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned list
of
                                       engine versions to those that are compatible
with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na Referência da API AWSSDK for Python (Boto3).

Descrever as opções de instâncias de banco de dados

O exemplo de código a seguir mostra como descrever opções para instâncias do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
 instance.
        :param db_engine_version: The engine version that must be supported by the
 DB instance.
        :return: The list of DB instance options that can be used to create a
 compatible DB instance.
        """
        try:
```

```
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts
```

- Para obter detalhes da API, consulte DescribeOrderableReferência da API DB InstanceOptions in AWSSDK for Python (Boto3).

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
```

```
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator = self.rds_client.get_paginator("describe_db_parameters")
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK para Python (Boto3).

Descrever os snapshots das instâncias de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de instâncias do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)
```

```
    def get_snapshot(self, snapshot_id):
        """
        Gets a DB instance snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_snapshots(
                DBSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na referência da API do AWS SDK para Python (Boto3).

Atualizar os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como atualizar os parâmetros em um grupo de parâmetros do Amazon RDS DB.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
 Parameters=update_parameters
            )
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte Referência da API ModifyDB ParameterGroup no AWSSDK for Python (Boto3).

Cenários

Começar a usar instâncias de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de banco de dados e defina os valores dos parâmetros.
- Crie uma instância de banco de dados configurada para usar o grupo de parâmetros. A instância de banco de dados também contém um banco de dados.
- Crie um snapshot da instância.
- Exclua a instância e o grupo de parâmetros.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class RdsInstanceScenario:
    """Runs a scenario that shows how to get started using Amazon RDS DB
 instances."""

    def __init__(self, instance_wrapper):
        """
        :param instance_wrapper: An object that wraps Amazon RDS DB instance
 actions.
        """
        self.instance_wrapper = instance_wrapper

    def create_parameter_group(self, parameter_group_name, db_engine):
        """
        Shows how to get available engine versions for a specified database engine
 and
```

```
        create a DB parameter group that is compatible with a selected engine
family.

        :param parameter_group_name: The name given to the newly created parameter
group.
        :param db_engine: The database engine to use as a basis.
        :return: The newly created parameter group.
        """
        print(
            f"Checking for an existing DB instance parameter group named
{parameter_group_name}."
        )
        parameter_group = self.instance_wrapper.get_parameter_group(
            parameter_group_name
        )
        if parameter_group is None:
            print(f"Getting available database engine versions for {db_engine}.")
            engine_versions = self.instance_wrapper.get_engine_versions(db_engine)
            families = list({ver["DBParameterGroupFamily"] for ver in
engine_versions})
            family_index = q.choose("Which family do you want to use? ", families)
            print(f"Creating a parameter group.")
            self.instance_wrapper.create_parameter_group(
                parameter_group_name, families[family_index], "Example parameter
group."
            )
            parameter_group = self.instance_wrapper.get_parameter_group(
                parameter_group_name
            )
        print(f"Parameter group {parameter_group['DBParameterGroupName']}:")
        pp(parameter_group)
        print("-" * 88)
        return parameter_group

    def update_parameters(self, parameter_group_name):
        """
        Shows how to get the parameters contained in a custom parameter group and
        update some of the parameter values in the group.

        :param parameter_group_name: The name of the parameter group to query and
modify.
        """
        print("Let's set some parameter values in your parameter group.")
        auto_inc_parameters = self.instance_wrapper.get_parameters(
```

```
            parameter_group_name, name_prefix="auto_increment"
        )
        update_params = []
        for auto_inc in auto_inc_parameters:
            if auto_inc["IsModifiable"] and auto_inc["DataType"] == "integer":
                print(f"The {auto_inc['ParameterName']} parameter is described as:")
                print(f"\t{auto_inc['Description']}")
                param_range = auto_inc["AllowedValues"].split("-")
                auto_inc["ParameterValue"] = str(
                    q.ask(
                        f"Enter a value between {param_range[0]} and
{param_range[1]}: ",
                        q.is_int,
                        q.in_range(int(param_range[0]), int(param_range[1])),
                    )
                )
                update_params.append(auto_inc)
        self.instance_wrapper.update_parameters(parameter_group_name, update_params)
        print(
            "You can get a list of parameters you've set by specifying a source of
'user'."
        )
        user_parameters = self.instance_wrapper.get_parameters(
            parameter_group_name, source="user"
        )
        pp(user_parameters)
        print("-" * 88)

    def create_instance(self, instance_name, db_name, db_engine, parameter_group):
        """
        Shows how to create a DB instance that contains a database of a specified
        type and is configured to use a custom DB parameter group.

        :param instance_name: The name given to the newly created DB instance.
        :param db_name: The name given to the created database.
        :param db_engine: The engine of the created database.
        :param parameter_group: The parameter group that is associated with the DB
instance.
        :return: The newly created DB instance.
        """
        print("Checking for an existing DB instance.")
        db_inst = self.instance_wrapper.get_db_instance(instance_name)
        if db_inst is None:
            print("Let's create a DB instance.")
```

```
            admin_username = q.ask(
                "Enter an administrator user name for the database: ", q.non_empty
            )
            admin_password = q.ask(
                "Enter a password for the administrator (at least 8 characters): ",
                q.non_empty,
            )
            engine_versions = self.instance_wrapper.get_engine_versions(
                db_engine, parameter_group["DBParameterGroupFamily"]
            )
            engine_choices = [ver["EngineVersion"] for ver in engine_versions]
            print("The available engines for your parameter group are:")
            engine_index = q.choose("Which engine do you want to use? ",
engine_choices)
            engine_selection = engine_versions[engine_index]
            print(
                "The available micro DB instance classes for your database engine
are:"
            )
            inst_opts = self.instance_wrapper.get_orderable_instances(
                engine_selection["Engine"], engine_selection["EngineVersion"]
            )
            inst_choices = list(
                {
                    opt["DBInstanceClass"]
                    for opt in inst_opts
                    if "micro" in opt["DBInstanceClass"]
                }
            )
            inst_index = q.choose(
                "Which micro DB instance class do you want to use? ", inst_choices
            )
            group_name = parameter_group["DBParameterGroupName"]
            storage_type = "standard"
            allocated_storage = 5
            print(
                f"Creating a DB instance named {instance_name} and database
{db_name}.\n"
                f"The DB instance is configured to use your custom parameter group
{group_name},\n"
                f"selected engine {engine_selection['EngineVersion']},\n"
                f"selected DB instance class {inst_choices[inst_index]},"
                f"and {allocated_storage} GiB of {storage_type} storage.\n"
                f"This typically takes several minutes."
```

```
            )
            db_inst = self.instance_wrapper.create_db_instance(
                db_name,
                instance_name,
                group_name,
                engine_selection["Engine"],
                engine_selection["EngineVersion"],
                inst_choices[inst_index],
                storage_type,
                allocated_storage,
                admin_username,
                admin_password,
            )
            while db_inst.get("DBInstanceStatus") != "available":
                wait(10)
                db_inst = self.instance_wrapper.get_db_instance(instance_name)
        print("Instance data:")
        pp(db_inst)
        print("-" * 88)
        return db_inst

    @staticmethod
    def display_connection(db_inst):
        """
        Displays connection information about a DB instance and tips on how to
        connect to it.

        :param db_inst: The DB instance to display.
        """
        print(
            "You can now connect to your database using your favorite MySql client.
\n"
            "One way to connect is by using the 'mysql' shell on an Amazon EC2
 instance\n"
            "that is running in the same VPC as your DB instance. Pass the endpoint,
\n"
            "port, and administrator user name to 'mysql' and enter your password\n"
            "when prompted:\n"
        )
        print(
            f"\n\tmysql -h {db_inst['Endpoint']['Address']} -P {db_inst['Endpoint']
['Port']} "
            f"-u {db_inst['MasterUsername']} -p\n"
        )
```

```
        print(
            "For more information, see the User Guide for Amazon RDS:\n"
            "\thttps://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/
CHAP_GettingStarted.CreatingConnecting.MySQL.html#CHAP_GettingStarted.Connecting.MySQL"
        )
        print("-" * 88)

    def create_snapshot(self, instance_name):
        """
        Shows how to create a DB instance snapshot and wait until it's available.

        :param instance_name: The name of a DB instance to snapshot.
        """
        if q.ask(
            "Do you want to create a snapshot of your DB instance (y/n)? ",
 q.is_yesno
        ):
            snapshot_id = f"{instance_name}-{uuid.uuid4()}"
            print(
                f"Creating a snapshot named {snapshot_id}. This typically takes a
 few minutes."
            )
            snapshot = self.instance_wrapper.create_snapshot(snapshot_id,
 instance_name)
            while snapshot.get("Status") != "available":
                wait(10)
                snapshot = self.instance_wrapper.get_snapshot(snapshot_id)
            pp(snapshot)
            print("-" * 88)

    def cleanup(self, db_inst, parameter_group_name):
        """
        Shows how to clean up a DB instance and parameter group.
        Before the parameter group can be deleted, all associated DB instances must
 first
        be deleted.

        :param db_inst: The DB instance to delete.
        :param parameter_group_name: The DB parameter group to delete.
        """
        if q.ask(
            "\nDo you want to delete the DB instance and parameter group (y/n)? ",
            q.is_yesno,
        ):
```

```
            print(f"Deleting DB instance {db_inst['DBInstanceIdentifier']}.")

 self.instance_wrapper.delete_db_instance(db_inst["DBInstanceIdentifier"])
            print(
                "Waiting for the DB instance to delete. This typically takes several
 minutes."
            )
            while db_inst is not None:
                wait(10)
                db_inst = self.instance_wrapper.get_db_instance(
                    db_inst["DBInstanceIdentifier"]
                )
            print(f"Deleting parameter group {parameter_group_name}.")
            self.instance_wrapper.delete_parameter_group(parameter_group_name)

    def run_scenario(self, db_engine, parameter_group_name, instance_name, db_name):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

        print("-" * 88)
        print(
            "Welcome to the Amazon Relational Database Service (Amazon RDS)\n"
            "get started with DB instances demo."
        )
        print("-" * 88)

        parameter_group = self.create_parameter_group(parameter_group_name,
 db_engine)
        self.update_parameters(parameter_group_name)
        db_inst = self.create_instance(
            instance_name, db_name, db_engine, parameter_group
        )
        self.display_connection(db_inst)
        self.create_snapshot(instance_name)
        self.cleanup(db_inst, parameter_group_name)

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = RdsInstanceScenario(InstanceWrapper.from_client())
        scenario.run_scenario(
            "mysql",
```

```
            "doc-example-parameter-group",
            "doc-example-instance",
            "docexampledb",
        )
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Defina as funções que são chamadas pelo cenário para gerenciar as ações do Amazon RDS.

```
class InstanceWrapper:
    """Encapsulates Amazon RDS DB instance actions."""

    def __init__(self, rds_client):
        """
        :param rds_client: A Boto3 Amazon RDS client.
        """
        self.rds_client = rds_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        rds_client = boto3.client("rds")
        return cls(rds_client)


    def get_parameter_group(self, parameter_group_name):
        """
        Gets a DB parameter group.

        :param parameter_group_name: The name of the parameter group to retrieve.
        :return: The parameter group.
        """
        try:
            response = self.rds_client.describe_db_parameter_groups(
                DBParameterGroupName=parameter_group_name
            )
            parameter_group = response["DBParameterGroups"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBParameterGroupNotFound":
```

```
                logger.info("Parameter group %s does not exist.",
parameter_group_name)
            else:
                logger.error(
                    "Couldn't get parameter group %s. Here's why: %s: %s",
                    parameter_group_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return parameter_group


    def create_parameter_group(
        self, parameter_group_name, parameter_group_family, description
    ):
        """
        Creates a DB parameter group that is based on the specified parameter group
        family.

        :param parameter_group_name: The name of the newly created parameter group.
        :param parameter_group_family: The family that is used as the basis of the
new
                                       parameter group.
        :param description: A description given to the parameter group.
        :return: Data about the newly created parameter group.
        """
        try:
            response = self.rds_client.create_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
                DBParameterGroupFamily=parameter_group_family,
                Description=description,
            )
        except ClientError as err:
            logger.error(
                "Couldn't create parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

```
    def delete_parameter_group(self, parameter_group_name):
        """
        Deletes a DB parameter group.

        :param parameter_group_name: The name of the parameter group to delete.
        :return: Data about the parameter group.
        """
        try:
            self.rds_client.delete_db_parameter_group(
                DBParameterGroupName=parameter_group_name
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete parameter group %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def get_parameters(self, parameter_group_name, name_prefix="", source=None):
        """
        Gets the parameters that are contained in a DB parameter group.

        :param parameter_group_name: The name of the parameter group to query.
        :param name_prefix: When specified, the retrieved list of parameters is
filtered
                            to contain only parameters that start with this prefix.
        :param source: When specified, only parameters from this source are
retrieved.
                       For example, a source of 'user' retrieves only parameters
that
                       were set by a user.
        :return: The list of requested parameters.
        """
        try:
            kwargs = {"DBParameterGroupName": parameter_group_name}
            if source is not None:
                kwargs["Source"] = source
            parameters = []
            paginator = self.rds_client.get_paginator("describe_db_parameters")
```

```
            for page in paginator.paginate(**kwargs):
                parameters += [
                    p
                    for p in page["Parameters"]
                    if p["ParameterName"].startswith(name_prefix)
                ]
        except ClientError as err:
            logger.error(
                "Couldn't get parameters for %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return parameters


    def update_parameters(self, parameter_group_name, update_parameters):
        """
        Updates parameters in a custom DB parameter group.

        :param parameter_group_name: The name of the parameter group to update.
        :param update_parameters: The parameters to update in the group.
        :return: Data about the modified parameter group.
        """
        try:
            response = self.rds_client.modify_db_parameter_group(
                DBParameterGroupName=parameter_group_name,
Parameters=update_parameters
            )
        except ClientError as err:
            logger.error(
                "Couldn't update parameters in %s. Here's why: %s: %s",
                parameter_group_name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def create_snapshot(self, snapshot_id, instance_id):
```

```
        """
        Creates a snapshot of a DB instance.

        :param snapshot_id: The ID to give the created snapshot.
        :param instance_id: The ID of the DB instance to snapshot.
        :return: Data about the newly created snapshot.
        """
        try:
            response = self.rds_client.create_db_snapshot(
                DBSnapshotIdentifier=snapshot_id, DBInstanceIdentifier=instance_id
            )
            snapshot = response["DBSnapshot"]
        except ClientError as err:
            logger.error(
                "Couldn't create snapshot of %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return snapshot


    def get_snapshot(self, snapshot_id):
        """
        Gets a DB instance snapshot.

        :param snapshot_id: The ID of the snapshot to retrieve.
        :return: The retrieved snapshot.
        """
        try:
            response = self.rds_client.describe_db_snapshots(
                DBSnapshotIdentifier=snapshot_id
            )
            snapshot = response["DBSnapshots"][0]
        except ClientError as err:
            logger.error(
                "Couldn't get snapshot %s. Here's why: %s: %s",
                snapshot_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

```
        else:
            return snapshot


    def get_engine_versions(self, engine, parameter_group_family=None):
        """
        Gets database engine versions that are available for the specified engine
        and parameter group family.

        :param engine: The database engine to look up.
        :param parameter_group_family: When specified, restricts the returned list
of
                                       engine versions to those that are compatible
with
                                       this parameter group family.
        :return: The list of database engine versions.
        """
        try:
            kwargs = {"Engine": engine}
            if parameter_group_family is not None:
                kwargs["DBParameterGroupFamily"] = parameter_group_family
            response = self.rds_client.describe_db_engine_versions(**kwargs)
            versions = response["DBEngineVersions"]
        except ClientError as err:
            logger.error(
                "Couldn't get engine versions for %s. Here's why: %s: %s",
                engine,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return versions


    def get_orderable_instances(self, db_engine, db_engine_version):
        """
        Gets DB instance options that can be used to create DB instances that are
        compatible with a set of specifications.

        :param db_engine: The database engine that must be supported by the DB
instance.
        :param db_engine_version: The engine version that must be supported by the
DB instance.
```

```
        :return: The list of DB instance options that can be used to create a
compatible DB instance.
        """
        try:
            inst_opts = []
            paginator = self.rds_client.get_paginator(
                "describe_orderable_db_instance_options"
            )
            for page in paginator.paginate(
                Engine=db_engine, EngineVersion=db_engine_version
            ):
                inst_opts += page["OrderableDBInstanceOptions"]
        except ClientError as err:
            logger.error(
                "Couldn't get orderable DB instances. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return inst_opts


    def get_db_instance(self, instance_id):
        """
        Gets data about a DB instance.

        :param instance_id: The ID of the DB instance to retrieve.
        :return: The retrieved DB instance.
        """
        try:
            response = self.rds_client.describe_db_instances(
                DBInstanceIdentifier=instance_id
            )
            db_inst = response["DBInstances"][0]
        except ClientError as err:
            if err.response["Error"]["Code"] == "DBInstanceNotFound":
                logger.info("Instance %s does not exist.", instance_id)
            else:
                logger.error(
                    "Couldn't get DB instance %s. Here's why: %s: %s",
                    instance_id,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
```

```
                )
                raise
        else:
            return db_inst


    def create_db_instance(
        self,
        db_name,
        instance_id,
        parameter_group_name,
        db_engine,
        db_engine_version,
        instance_class,
        storage_type,
        allocated_storage,
        admin_name,
        admin_password,
    ):
        """
        Creates a DB instance.

        :param db_name: The name of the database that is created in the DB instance.
        :param instance_id: The ID to give the newly created DB instance.
        :param parameter_group_name: A parameter group to associate with the DB
instance.
        :param db_engine: The database engine of a database to create in the DB
instance.
        :param db_engine_version: The engine version for the created database.
        :param instance_class: The DB instance class for the newly created DB
instance.
        :param storage_type: The storage type of the DB instance.
        :param allocated_storage: The amount of storage allocated on the DB
instance, in GiBs.
        :param admin_name: The name of the admin user for the created database.
        :param admin_password: The admin password for the created database.
        :return: Data about the newly created DB instance.
        """
        try:
            response = self.rds_client.create_db_instance(
                DBName=db_name,
                DBInstanceIdentifier=instance_id,
                DBParameterGroupName=parameter_group_name,
                Engine=db_engine,
```

```
                EngineVersion=db_engine_version,
                DBInstanceClass=instance_class,
                StorageType=storage_type,
                AllocatedStorage=allocated_storage,
                MasterUsername=admin_name,
                MasterUserPassword=admin_password,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't create DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst


    def delete_db_instance(self, instance_id):
        """
        Deletes a DB instance.

        :param instance_id: The ID of the DB instance to delete.
        :return: Data about the deleted DB instance.
        """
        try:
            response = self.rds_client.delete_db_instance(
                DBInstanceIdentifier=instance_id,
                SkipFinalSnapshot=True,
                DeleteAutomatedBackups=True,
            )
            db_inst = response["DBInstance"]
        except ClientError as err:
            logger.error(
                "Couldn't delete DB instance %s. Here's why: %s: %s",
                instance_id,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return db_inst
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateDBInstance
  - Criado B ParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - Banco de dados excluído ParameterGroup
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DB descrito ParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDB InstanceOptions
  - Modificar banco de dados ParameterGroup

Exemplos do Amazon Rekognition usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com Amazon Rekognition.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Comparar faces em uma imagem com uma imagem de referência

O exemplo de código a seguir mostra como comparar faces em uma imagem com uma imagem de referência usando o Amazon Rekognition.

Para obter mais informações, consulte Comparação de faces em imagens.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def compare_faces(self, target_image, similarity):
```

```
        """
        Compares faces in the image with the largest face in the target image.

        :param target_image: The target image to compare against.
        :param similarity: Faces in the image must have a similarity value greater
                           than this value to be included in the results.
        :return: A tuple. The first element is the list of faces that match the
                 reference image. The second element is the list of faces that have
                 a similarity value below the specified threshold.
        """
        try:
            response = self.rekognition_client.compare_faces(
                SourceImage=self.image,
                TargetImage=target_image.image,
                SimilarityThreshold=similarity,
            )
            matches = [
                RekognitionFace(match["Face"]) for match in response["FaceMatches"]
            ]
            unmatches = [RekognitionFace(face) for face in
response["UnmatchedFaces"]]
            logger.info(
                "Found %s matched faces and %s unmatched faces.",
                len(matches),
                len(unmatches),
            )
        except ClientError:
            logger.exception(
                "Couldn't match faces from %s to %s.",
                self.image_name,
                target_image.image_name,
            )
            raise
        else:
            return matches, unmatches
```

- Para obter detalhes da API, consulte a CompareFacesReferência da API AWSSDK for Python (Boto3).

Criar uma coleção

O exemplo de código a seguir mostra como criar uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Criar uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollectionManager:
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def create_collection(self, collection_id):
        """
        Creates an empty collection.

        :param collection_id: Text that identifies the collection.
        :return: The newly created collection.
        """
        try:
            response = self.rekognition_client.create_collection(
                CollectionId=collection_id
            )
            response["CollectionId"] = collection_id
            collection = RekognitionCollection(response, self.rekognition_client)
            logger.info("Created collection %s.", collection_id)
```

```
        except ClientError:
            logger.exception("Couldn't create collection %s.", collection_id)
            raise
        else:
            return collection
```

- Para obter detalhes da API, consulte a CreateCollectionReferência da API AWSSDK for Python (Boto3).

Excluir uma coleção.

O exemplo de código a seguir mostra como excluir uma coleção do Amazon Rekognition.

Para mais informações, consulte Excluir uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
```

```
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def delete_collection(self):
        """
        Deletes the collection.
        """
        try:

self.rekognition_client.delete_collection(CollectionId=self.collection_id)
            logger.info("Deleted collection %s.", self.collection_id)
            self.collection_id = None
        except ClientError:
            logger.exception("Couldn't delete collection %s.", self.collection_id)
            raise
```

- Para obter detalhes da API, consulte a DeleteCollectionReferência da API AWSSDK for Python (Boto3).

Excluir faces de uma coleção

O exemplo de código a seguir mostra como excluir faces de uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Excluir faces de uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
```

```
        )


    def delete_faces(self, face_ids):
        """
        Deletes faces from the collection.

        :param face_ids: The list of IDs of faces to delete.
        :return: The list of IDs of faces that were deleted.
        """
        try:
            response = self.rekognition_client.delete_faces(
                CollectionId=self.collection_id, FaceIds=face_ids
            )
            deleted_ids = response["DeletedFaces"]
            logger.info(
                "Deleted %s faces from %s.", len(deleted_ids), self.collection_id
            )
        except ClientError:
            logger.exception("Couldn't delete faces from %s.", self.collection_id)
            raise
        else:
            return deleted_ids
```

- Para obter detalhes da API, consulte a DeleteFacesReferência da API AWSSDK for Python (Boto3).

Descrever uma coleção

O exemplo de código a seguir mostra como descrever uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Descrever uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def describe_collection(self):
        """
        Gets data about the collection from the Amazon Rekognition service.

        :return: The collection rendered as a dict.
        """
```

```
        try:
            response = self.rekognition_client.describe_collection(
                CollectionId=self.collection_id
            )
            # Work around capitalization of Arn vs. ARN
            response["CollectionArn"] = response.get("CollectionARN")
            (
                self.collection_arn,
                self.face_count,
                self.created,
            ) = self._unpack_collection(response)
            logger.info("Got data for collection %s.", self.collection_id)
        except ClientError:
            logger.exception("Couldn't get data for collection %s.",
self.collection_id)
            raise
        else:
            return self.to_dict()
```

- Para obter detalhes da API, consulte a DescribeCollectionReferência da API AWSSDK for Python (Boto3).

Detectar faces em uma imagem

O exemplo de código a seguir mostra como detectar faces em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar faces em uma imagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
```

```
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_faces(self):
        """
        Detects faces in the image.

        :return: The list of faces found in the image.
        """
        try:
            response = self.rekognition_client.detect_faces(
                Image=self.image, Attributes=["ALL"]
            )
            faces = [RekognitionFace(face) for face in response["FaceDetails"]]
            logger.info("Detected %s faces.", len(faces))
        except ClientError:
            logger.exception("Couldn't detect faces in %s.", self.image_name)
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a DetectFacesReferência da API AWSSDK for Python (Boto3).

Para detectar rótulos em uma imagem

O exemplo de código a seguir mostra como detectar rótulos em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar rótulos em uma imagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_labels(self, max_labels):
        """
        Detects labels in the image. Labels are objects and people.

        :param max_labels: The maximum number of labels to return.
        :return: The list of labels detected in the image.
        """
```

```
        try:
            response = self.rekognition_client.detect_labels(
                Image=self.image, MaxLabels=max_labels
            )
            labels = [RekognitionLabel(label) for label in response["Labels"]]
            logger.info("Found %s labels in %s.", len(labels), self.image_name)
        except ClientError:
            logger.info("Couldn't detect labels in %s.", self.image_name)
            raise
        else:
            return labels
```

- Para obter detalhes da API, consulte a DetectLabelsReferência da API AWSSDK for Python (Boto3).

Detectar rótulos de moderação em uma imagem

O exemplo de código a seguir mostra como detectar rótulos de moderação em uma imagem com o Amazon Rekognition. Os rótulos de moderação identificam o conteúdo que pode ser inadequado para alguns públicos.

Para obter mais informações, consulte Detectar imagens inapropriadas.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
```

```
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_moderation_labels(self):
        """
        Detects moderation labels in the image. Moderation labels identify content
        that may be inappropriate for some audiences.

        :return: The list of moderation labels found in the image.
        """
        try:
            response = self.rekognition_client.detect_moderation_labels(
                Image=self.image
            )
            labels = [
                RekognitionModerationLabel(label)
                for label in response["ModerationLabels"]
            ]
            logger.info(
                "Found %s moderation labels in %s.", len(labels), self.image_name
            )
        except ClientError:
            logger.exception(
                "Couldn't detect moderation labels in %s.", self.image_name
            )
            raise
        else:
            return labels
```

- Para obter detalhes da API, consulte a DetectModerationLabelsReferência da API AWSSDK for Python (Boto3).

Detectar texto em uma imagem

O exemplo de código a seguir mostra como detectar texto em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Detectar texto em uma imagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def detect_text(self):
        """
        Detects text in the image.

        :return The list of text elements found in the image.
        """
        try:
            response = self.rekognition_client.detect_text(Image=self.image)
```

```
            texts = [RekognitionText(text) for text in response["TextDetections"]]
            logger.info("Found %s texts in %s.", len(texts), self.image_name)
        except ClientError:
            logger.exception("Couldn't detect text in %s.", self.image_name)
            raise
        else:
            return texts
```

- Para obter detalhes da API, consulte a DetectTextReferência da API AWSSDK for Python (Boto3).

Indexar faces de uma coleção

O exemplo de código a seguir mostra como indexar faces em uma imagem e adicioná-las a uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Adicionar faces a uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
```

```
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def index_faces(self, image, max_faces):
        """
        Finds faces in the specified image, indexes them, and stores them in the
        collection.

        :param image: The image to index.
        :param max_faces: The maximum number of faces to index.
        :return: A tuple. The first element is a list of indexed faces.
                 The second element is a list of faces that couldn't be indexed.
        """
        try:
            response = self.rekognition_client.index_faces(
                CollectionId=self.collection_id,
                Image=image.image,
                ExternalImageId=image.image_name,
                MaxFaces=max_faces,
                DetectionAttributes=["ALL"],
            )
            indexed_faces = [
                RekognitionFace({**face["Face"], **face["FaceDetail"]})
```

```
                for face in response["FaceRecords"]
            ]
            unindexed_faces = [
                RekognitionFace(face["FaceDetail"])
                for face in response["UnindexedFaces"]
            ]
            logger.info(
                "Indexed %s faces in %s. Could not index %s faces.",
                len(indexed_faces),
                image.image_name,
                len(unindexed_faces),
            )
        except ClientError:
            logger.exception("Couldn't index faces in image %s.", image.image_name)
            raise
        else:
            return indexed_faces, unindexed_faces
```

- Para obter detalhes da API, consulte a IndexFacesReferência da API AWSSDK for Python (Boto3).

Listar coleções

O exemplo de código a seguir mostra como listar coleções do Amazon Rekognition.

Para obter mais informações, consulte Listar coleções.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollectionManager:
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition API.
```

```
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def list_collections(self, max_results):
        """
        Lists collections for the current account.

        :param max_results: The maximum number of collections to return.
        :return: The list of collections for the current account.
        """
        try:
            response =
self.rekognition_client.list_collections(MaxResults=max_results)
            collections = [
                RekognitionCollection({"CollectionId": col_id},
self.rekognition_client)
                for col_id in response["CollectionIds"]
            ]
        except ClientError:
            logger.exception("Couldn't list collections.")
            raise
        else:
            return collections
```

- Para obter detalhes da API, consulte a ListCollectionsReferência da API AWSSDK for Python (Boto3).

Listar faces em uma coleção

O exemplo de código a seguir mostra como lista faces em uma coleção do Amazon Rekognition.

Para obter mais informações, consulte Listar faces em uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
```

```
        )


    def list_faces(self, max_results):
        """
        Lists the faces currently indexed in the collection.

        :param max_results: The maximum number of faces to return.
        :return: The list of faces in the collection.
        """
        try:
            response = self.rekognition_client.list_faces(
                CollectionId=self.collection_id, MaxResults=max_results
            )
            faces = [RekognitionFace(face) for face in response["Faces"]]
            logger.info(
                "Found %s faces in collection %s.", len(faces), self.collection_id
            )
        except ClientError:
            logger.exception(
                "Couldn't list faces in collection %s.", self.collection_id
            )
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a ListFacesReferência da API AWSSDK for Python (Boto3).

Reconhecer celebridades em uma imagem

O exemplo de código a seguir mostra como reconhecer celebridades em uma imagem com o Amazon Rekognition.

Para obter mais informações, consulte Reconhecer celebridades em uma imagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    def recognize_celebrities(self):
        """
        Detects celebrities in the image.

        :return: A tuple. The first element is the list of celebrities found in
                 the image. The second element is the list of faces that were
                 detected but did not match any known celebrities.
        """
        try:
            response =
 self.rekognition_client.recognize_celebrities(Image=self.image)
            celebrities = [
                RekognitionCelebrity(celeb) for celeb in response["CelebrityFaces"]
            ]
```

```
            other_faces = [
                RekognitionFace(face) for face in response["UnrecognizedFaces"]
            ]
            logger.info(
                "Found %s celebrities and %s other faces in %s.",
                len(celebrities),
                len(other_faces),
                self.image_name,
            )
        except ClientError:
            logger.exception("Couldn't detect celebrities in %s.", self.image_name)
            raise
        else:
            return celebrities, other_faces
```

- Para obter detalhes da API, consulte a RecognizeCelebritiesReferência da API AWSSDK for Python (Boto3).

Pesquisar faces em uma coleção

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition que correspondam a outra face da coleção.

Para obter mais informações, consulte Pesquisar face (ID de face).

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """
```

```
    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def search_faces(self, face_id, threshold, max_faces):
        """
        Searches for faces in the collection that match another face from the
        collection.

        :param face_id: The ID of the face in the collection to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: The list of matching faces found in the collection. This list does
                 not contain the face specified by `face_id`.
        """
```

```
        try:
            response = self.rekognition_client.search_faces(
                CollectionId=self.collection_id,
                FaceId=face_id,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            faces = [RekognitionFace(face["Face"]) for face in
response["FaceMatches"]]
            logger.info(
                "Found %s faces in %s that match %s.",
                len(faces),
                self.collection_id,
                face_id,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                face_id,
            )
            raise
        else:
            return faces
```

- Para obter detalhes da API, consulte a SearchFacesReferência da API AWSSDK for Python (Boto3).

Pesquisar faces em uma coleção em comparação com uma imagem de referência

O exemplo de código a seguir mostra como pesquisar faces em uma coleção do Amazon Rekognition em comparação com uma imagem de referência.

Para obter mais informações, consulte Pesquisar uma face (imagem).

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
```

```
        )


    def search_faces_by_image(self, image, threshold, max_faces):
        """
        Searches for faces in the collection that match the largest face in the
        reference image.

        :param image: The image that contains the reference face to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: A tuple. The first element is the face found in the reference
image.
                 The second element is the list of matching faces found in the
                 collection.
        """
        try:
            response = self.rekognition_client.search_faces_by_image(
                CollectionId=self.collection_id,
                Image=image.image,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            image_face = RekognitionFace(
                {
                    "BoundingBox": response["SearchedFaceBoundingBox"],
                    "Confidence": response["SearchedFaceConfidence"],
                }
            )
            collection_faces = [
                RekognitionFace(face["Face"]) for face in response["FaceMatches"]
            ]
            logger.info(
                "Found %s faces in the collection that match the largest "
                "face in %s.",
                len(collection_faces),
                image.image_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                image.image_name,
```

```
            )
            raise
        else:
            return image_face, collection_faces
```

- Para obter detalhes da API, consulte a SearchFacesByImageReferência da API AWSSDK for Python (Boto3).

Cenários

Criar uma coleção e encontrar faces nela

O código de exemplo a seguir mostra como:

- Crie uma coleção do Amazon Rekognition.
- Adicione imagens à coleção e detectar faces nela.
- Pesquise na coleção as faces que correspondem a uma imagem de referência.
- Excluir uma coleção.

Para obter mais informações, consulte Pesquisar faces em uma coleção.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar classes que agrupem as funções do Amazon Rekognition.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError
from rekognition_objects import RekognitionFace
from rekognition_image_detection import RekognitionImage
```

```
logger = logging.getLogger(__name__)


class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    @classmethod
    def from_file(cls, image_file_name, rekognition_client, image_name=None):
        """
        Creates a RekognitionImage object from a local file.

        :param image_file_name: The file name of the image. The file is opened and
 its
                                bytes are read.
        :param rekognition_client: A Boto3 Rekognition client.
        :param image_name: The name of the image. If this is not specified, the
                           file name is used as the image name.
        :return: The RekognitionImage object, initialized with image bytes from the
                 file.
        """
        with open(image_file_name, "rb") as img_file:
            image = {"Bytes": img_file.read()}
        name = image_file_name if image_name is None else image_name
        return cls(image, name, rekognition_client)


class RekognitionCollectionManager:
```

```
    """
    Encapsulates Amazon Rekognition collection management functions.
    This class is a thin wrapper around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, rekognition_client):
        """
        Initializes the collection manager object.

        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.rekognition_client = rekognition_client


    def create_collection(self, collection_id):
        """
        Creates an empty collection.

        :param collection_id: Text that identifies the collection.
        :return: The newly created collection.
        """
        try:
            response = self.rekognition_client.create_collection(
                CollectionId=collection_id
            )
            response["CollectionId"] = collection_id
            collection = RekognitionCollection(response, self.rekognition_client)
            logger.info("Created collection %s.", collection_id)
        except ClientError:
            logger.exception("Couldn't create collection %s.", collection_id)
            raise
        else:
            return collection


    def list_collections(self, max_results):
        """
        Lists collections for the current account.

        :param max_results: The maximum number of collections to return.
        :return: The list of collections for the current account.
        """
        try:
```

```
            response =
 self.rekognition_client.list_collections(MaxResults=max_results)
            collections = [
                RekognitionCollection({"CollectionId": col_id},
 self.rekognition_client)
                for col_id in response["CollectionIds"]
            ]
        except ClientError:
            logger.exception("Couldn't list collections.")
            raise
        else:
            return collections



class RekognitionCollection:
    """
    Encapsulates an Amazon Rekognition collection. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, collection, rekognition_client):
        """
        Initializes a collection object.

        :param collection: Collection data in the format returned by a call to
                           create_collection.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.collection_id = collection["CollectionId"]
        self.collection_arn, self.face_count, self.created =
 self._unpack_collection(
            collection
        )
        self.rekognition_client = rekognition_client

    @staticmethod
    def _unpack_collection(collection):
        """
        Unpacks optional parts of a collection that can be returned by
        describe_collection.

        :param collection: The collection data.
        :return: A tuple of the data in the collection.
```

```
        """
        return (
            collection.get("CollectionArn"),
            collection.get("FaceCount", 0),
            collection.get("CreationTimestamp"),
        )


    def to_dict(self):
        """
        Renders parts of the collection data to a dict.

        :return: The collection data as a dict.
        """
        rendering = {
            "collection_id": self.collection_id,
            "collection_arn": self.collection_arn,
            "face_count": self.face_count,
            "created": self.created,
        }
        return rendering


    def describe_collection(self):
        """
        Gets data about the collection from the Amazon Rekognition service.

        :return: The collection rendered as a dict.
        """
        try:
            response = self.rekognition_client.describe_collection(
                CollectionId=self.collection_id
            )
            # Work around capitalization of Arn vs. ARN
            response["CollectionArn"] = response.get("CollectionARN")
            (
                self.collection_arn,
                self.face_count,
                self.created,
            ) = self._unpack_collection(response)
            logger.info("Got data for collection %s.", self.collection_id)
        except ClientError:
            logger.exception("Couldn't get data for collection %s.",
self.collection_id)
```

```
            raise
        else:
            return self.to_dict()


    def delete_collection(self):
        """
        Deletes the collection.
        """
        try:

self.rekognition_client.delete_collection(CollectionId=self.collection_id)
            logger.info("Deleted collection %s.", self.collection_id)
            self.collection_id = None
        except ClientError:
            logger.exception("Couldn't delete collection %s.", self.collection_id)
            raise


    def index_faces(self, image, max_faces):
        """
        Finds faces in the specified image, indexes them, and stores them in the
        collection.

        :param image: The image to index.
        :param max_faces: The maximum number of faces to index.
        :return: A tuple. The first element is a list of indexed faces.
                 The second element is a list of faces that couldn't be indexed.
        """
        try:
            response = self.rekognition_client.index_faces(
                CollectionId=self.collection_id,
                Image=image.image,
                ExternalImageId=image.image_name,
                MaxFaces=max_faces,
                DetectionAttributes=["ALL"],
            )
            indexed_faces = [
                RekognitionFace({**face["Face"], **face["FaceDetail"]})
                for face in response["FaceRecords"]
            ]
            unindexed_faces = [
                RekognitionFace(face["FaceDetail"])
                for face in response["UnindexedFaces"]
```

```
            ]
            logger.info(
                "Indexed %s faces in %s. Could not index %s faces.",
                len(indexed_faces),
                image.image_name,
                len(unindexed_faces),
            )
        except ClientError:
            logger.exception("Couldn't index faces in image %s.", image.image_name)
            raise
        else:
            return indexed_faces, unindexed_faces


    def list_faces(self, max_results):
        """
        Lists the faces currently indexed in the collection.

        :param max_results: The maximum number of faces to return.
        :return: The list of faces in the collection.
        """
        try:
            response = self.rekognition_client.list_faces(
                CollectionId=self.collection_id, MaxResults=max_results
            )
            faces = [RekognitionFace(face) for face in response["Faces"]]
            logger.info(
                "Found %s faces in collection %s.", len(faces), self.collection_id
            )
        except ClientError:
            logger.exception(
                "Couldn't list faces in collection %s.", self.collection_id
            )
            raise
        else:
            return faces


    def search_faces(self, face_id, threshold, max_faces):
        """
        Searches for faces in the collection that match another face from the
        collection.

        :param face_id: The ID of the face in the collection to search for.
```

```
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: The list of matching faces found in the collection. This list does
                 not contain the face specified by `face_id`.
        """
        try:
            response = self.rekognition_client.search_faces(
                CollectionId=self.collection_id,
                FaceId=face_id,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            faces = [RekognitionFace(face["Face"]) for face in
response["FaceMatches"]]
            logger.info(
                "Found %s faces in %s that match %s.",
                len(faces),
                self.collection_id,
                face_id,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                face_id,
            )
            raise
        else:
            return faces


    def search_faces_by_image(self, image, threshold, max_faces):
        """
        Searches for faces in the collection that match the largest face in the
        reference image.

        :param image: The image that contains the reference face to search for.
        :param threshold: The match confidence must be greater than this value
                          for a face to be included in the results.
        :param max_faces: The maximum number of faces to return.
        :return: A tuple. The first element is the face found in the reference
image.
                 The second element is the list of matching faces found in the
```

```
                 collection.
        """
        try:
            response = self.rekognition_client.search_faces_by_image(
                CollectionId=self.collection_id,
                Image=image.image,
                FaceMatchThreshold=threshold,
                MaxFaces=max_faces,
            )
            image_face = RekognitionFace(
                {
                    "BoundingBox": response["SearchedFaceBoundingBox"],
                    "Confidence": response["SearchedFaceConfidence"],
                }
            )
            collection_faces = [
                RekognitionFace(face["Face"]) for face in response["FaceMatches"]
            ]
            logger.info(
                "Found %s faces in the collection that match the largest "
                "face in %s.",
                len(collection_faces),
                image.image_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't search for faces in %s that match %s.",
                self.collection_id,
                image.image_name,
            )
            raise
        else:
            return image_face, collection_faces


class RekognitionFace:
    """Encapsulates an Amazon Rekognition face."""

    def __init__(self, face, timestamp=None):
        """
        Initializes the face object.

        :param face: Face data, in the format returned by Amazon Rekognition
                     functions.
```

```
        :param timestamp: The time when the face was detected, if the face was
                          detected in a video.
        """
        self.bounding_box = face.get("BoundingBox")
        self.confidence = face.get("Confidence")
        self.landmarks = face.get("Landmarks")
        self.pose = face.get("Pose")
        self.quality = face.get("Quality")
        age_range = face.get("AgeRange")
        if age_range is not None:
            self.age_range = (age_range.get("Low"), age_range.get("High"))
        else:
            self.age_range = None
        self.smile = face.get("Smile", {}).get("Value")
        self.eyeglasses = face.get("Eyeglasses", {}).get("Value")
        self.sunglasses = face.get("Sunglasses", {}).get("Value")
        self.gender = face.get("Gender", {}).get("Value", None)
        self.beard = face.get("Beard", {}).get("Value")
        self.mustache = face.get("Mustache", {}).get("Value")
        self.eyes_open = face.get("EyesOpen", {}).get("Value")
        self.mouth_open = face.get("MouthOpen", {}).get("Value")
        self.emotions = [
            emo.get("Type")
            for emo in face.get("Emotions", [])
            if emo.get("Confidence", 0) > 50
        ]
        self.face_id = face.get("FaceId")
        self.image_id = face.get("ImageId")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the face data to a dict.

        :return: A dict that contains the face data.
        """
        rendering = {}
        if self.bounding_box is not None:
            rendering["bounding_box"] = self.bounding_box
        if self.age_range is not None:
            rendering["age"] = f"{self.age_range[0]} - {self.age_range[1]}"
        if self.gender is not None:
            rendering["gender"] = self.gender
        if self.emotions:
```

```
            rendering["emotions"] = self.emotions
        if self.face_id is not None:
            rendering["face_id"] = self.face_id
        if self.image_id is not None:
            rendering["image_id"] = self.image_id
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        has = []
        if self.smile:
            has.append("smile")
        if self.eyeglasses:
            has.append("eyeglasses")
        if self.sunglasses:
            has.append("sunglasses")
        if self.beard:
            has.append("beard")
        if self.mustache:
            has.append("mustache")
        if self.eyes_open:
            has.append("open eyes")
        if self.mouth_open:
            has.append("open mouth")
        if has:
            rendering["has"] = has
        return rendering
```

Usar as classes wrapper para criar uma coleção de faces a partir de um conjunto de imagens e, em seguida, pesquisar faces na coleção.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Rekognition face collection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    rekognition_client = boto3.client("rekognition")
    images = [
        RekognitionImage.from_file(
            ".media/pexels-agung-pandit-wiguna-1128316.jpg",
```

```
            rekognition_client,
            image_name="sitting",
        ),
        RekognitionImage.from_file(
            ".media/pexels-agung-pandit-wiguna-1128317.jpg",
            rekognition_client,
            image_name="hopping",
        ),
        RekognitionImage.from_file(
            ".media/pexels-agung-pandit-wiguna-1128318.jpg",
            rekognition_client,
            image_name="biking",
        ),
    ]

    collection_mgr = RekognitionCollectionManager(rekognition_client)
    collection = collection_mgr.create_collection("doc-example-collection-demo")
    print(f"Created collection {collection.collection_id}:")
    pprint(collection.describe_collection())

    print("Indexing faces from three images:")
    for image in images:
        collection.index_faces(image, 10)
    print("Listing faces in collection:")
    faces = collection.list_faces(10)
    for face in faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    print(
        f"Searching for faces in the collection that match the first face in the "
        f"list (Face ID: {faces[0].face_id}."
    )
    found_faces = collection.search_faces(faces[0].face_id, 80, 10)
    print(f"Found {len(found_faces)} matching faces.")
    for face in found_faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    print(
        f"Searching for faces in the collection that match the largest face in "
        f"{images[0].image_name}."
    )
    image_face, match_faces = collection.search_faces_by_image(images[0], 80, 10)
```

```
    print(f"The largest face in {images[0].image_name} is:")
    pprint(image_face.to_dict())
    print(f"Found {len(match_faces)} matching faces.")
    for face in match_faces:
        pprint(face.to_dict())
    input("Press Enter to continue.")

    collection.delete_collection()
    print("Thanks for watching!")
    print("-" * 88)
```

Detectar e exibir elementos em imagens

O código de exemplo a seguir mostra como:

- Detectar elementos em imagens usando o Amazon Rekognition.
- Exibir imagens e desenhar caixas delimitadoras ao redor dos elementos detectados.

Para obter mais informações, consulte Exibindo caixas delimitadoras.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar classes para agrupar as funções do Amazon Rekognition.

```
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError
import requests

from rekognition_objects import (
```

```
    RekognitionFace,
    RekognitionCelebrity,
    RekognitionLabel,
    RekognitionModerationLabel,
    RekognitionText,
    show_bounding_boxes,
    show_polygons,
)

logger = logging.getLogger(__name__)


class RekognitionImage:
    """
    Encapsulates an Amazon Rekognition image. This class is a thin wrapper
    around parts of the Boto3 Amazon Rekognition API.
    """

    def __init__(self, image, image_name, rekognition_client):
        """
        Initializes the image object.

        :param image: Data that defines the image, either the image bytes or
                      an Amazon S3 bucket and object key.
        :param image_name: The name of the image.
        :param rekognition_client: A Boto3 Rekognition client.
        """
        self.image = image
        self.image_name = image_name
        self.rekognition_client = rekognition_client


    @classmethod
    def from_file(cls, image_file_name, rekognition_client, image_name=None):
        """
        Creates a RekognitionImage object from a local file.

        :param image_file_name: The file name of the image. The file is opened and
 its
                                bytes are read.
        :param rekognition_client: A Boto3 Rekognition client.
        :param image_name: The name of the image. If this is not specified, the
                           file name is used as the image name.
        :return: The RekognitionImage object, initialized with image bytes from the
```

```
                 file.
        """
        with open(image_file_name, "rb") as img_file:
            image = {"Bytes": img_file.read()}
        name = image_file_name if image_name is None else image_name
        return cls(image, name, rekognition_client)


    @classmethod
    def from_bucket(cls, s3_object, rekognition_client):
        """
        Creates a RekognitionImage object from an Amazon S3 object.

        :param s3_object: An Amazon S3 object that identifies the image. The image
                          is not retrieved until needed for a later call.
        :param rekognition_client: A Boto3 Rekognition client.
        :return: The RekognitionImage object, initialized with Amazon S3 object
data.
        """
        image = {"S3Object": {"Bucket": s3_object.bucket_name, "Name":
s3_object.key}}
        return cls(image, s3_object.key, rekognition_client)


    def detect_faces(self):
        """
        Detects faces in the image.

        :return: The list of faces found in the image.
        """
        try:
            response = self.rekognition_client.detect_faces(
                Image=self.image, Attributes=["ALL"]
            )
            faces = [RekognitionFace(face) for face in response["FaceDetails"]]
            logger.info("Detected %s faces.", len(faces))
        except ClientError:
            logger.exception("Couldn't detect faces in %s.", self.image_name)
            raise
        else:
            return faces


    def detect_labels(self, max_labels):
```

```
        """
        Detects labels in the image. Labels are objects and people.

        :param max_labels: The maximum number of labels to return.
        :return: The list of labels detected in the image.
        """
        try:
            response = self.rekognition_client.detect_labels(
                Image=self.image, MaxLabels=max_labels
            )
            labels = [RekognitionLabel(label) for label in response["Labels"]]
            logger.info("Found %s labels in %s.", len(labels), self.image_name)
        except ClientError:
            logger.info("Couldn't detect labels in %s.", self.image_name)
            raise
        else:
            return labels


    def recognize_celebrities(self):
        """
        Detects celebrities in the image.

        :return: A tuple. The first element is the list of celebrities found in
                 the image. The second element is the list of faces that were
                 detected but did not match any known celebrities.
        """
        try:
            response =
self.rekognition_client.recognize_celebrities(Image=self.image)
            celebrities = [
                RekognitionCelebrity(celeb) for celeb in response["CelebrityFaces"]
            ]
            other_faces = [
                RekognitionFace(face) for face in response["UnrecognizedFaces"]
            ]
            logger.info(
                "Found %s celebrities and %s other faces in %s.",
                len(celebrities),
                len(other_faces),
                self.image_name,
            )
        except ClientError:
            logger.exception("Couldn't detect celebrities in %s.", self.image_name)
```

```
            raise
        else:
            return celebrities, other_faces



    def compare_faces(self, target_image, similarity):
        """
        Compares faces in the image with the largest face in the target image.

        :param target_image: The target image to compare against.
        :param similarity: Faces in the image must have a similarity value greater
                           than this value to be included in the results.
        :return: A tuple. The first element is the list of faces that match the
                 reference image. The second element is the list of faces that have
                 a similarity value below the specified threshold.
        """
        try:
            response = self.rekognition_client.compare_faces(
                SourceImage=self.image,
                TargetImage=target_image.image,
                SimilarityThreshold=similarity,
            )
            matches = [
                RekognitionFace(match["Face"]) for match in response["FaceMatches"]
            ]
            unmatches = [RekognitionFace(face) for face in
response["UnmatchedFaces"]]
            logger.info(
                "Found %s matched faces and %s unmatched faces.",
                len(matches),
                len(unmatches),
            )
        except ClientError:
            logger.exception(
                "Couldn't match faces from %s to %s.",
                self.image_name,
                target_image.image_name,
            )
            raise
        else:
            return matches, unmatches
```

```
    def detect_moderation_labels(self):
        """
        Detects moderation labels in the image. Moderation labels identify content
        that may be inappropriate for some audiences.

        :return: The list of moderation labels found in the image.
        """
        try:
            response = self.rekognition_client.detect_moderation_labels(
                Image=self.image
            )
            labels = [
                RekognitionModerationLabel(label)
                for label in response["ModerationLabels"]
            ]
            logger.info(
                "Found %s moderation labels in %s.", len(labels), self.image_name
            )
        except ClientError:
            logger.exception(
                "Couldn't detect moderation labels in %s.", self.image_name
            )
            raise
        else:
            return labels


    def detect_text(self):
        """
        Detects text in the image.

        :return The list of text elements found in the image.
        """
        try:
            response = self.rekognition_client.detect_text(Image=self.image)
            texts = [RekognitionText(text) for text in response["TextDetections"]]
            logger.info("Found %s texts in %s.", len(texts), self.image_name)
        except ClientError:
            logger.exception("Couldn't detect text in %s.", self.image_name)
            raise
        else:
            return texts
```

Criar funções auxiliares para desenhar caixas delimitadoras e polígonos.

```
import io
import logging
from PIL import Image, ImageDraw

logger = logging.getLogger(__name__)


def show_bounding_boxes(image_bytes, box_sets, colors):
    """
    Draws bounding boxes on an image and shows it with the default image viewer.

    :param image_bytes: The image to draw, as bytes.
    :param box_sets: A list of lists of bounding boxes to draw on the image.
    :param colors: A list of colors to use to draw the bounding boxes.
    """
    image = Image.open(io.BytesIO(image_bytes))
    draw = ImageDraw.Draw(image)
    for boxes, color in zip(box_sets, colors):
        for box in boxes:
            left = image.width * box["Left"]
            top = image.height * box["Top"]
            right = (image.width * box["Width"]) + left
            bottom = (image.height * box["Height"]) + top
            draw.rectangle([left, top, right, bottom], outline=color, width=3)
    image.show()



def show_polygons(image_bytes, polygons, color):
    """
    Draws polygons on an image and shows it with the default image viewer.

    :param image_bytes: The image to draw, as bytes.
    :param polygons: The list of polygons to draw on the image.
    :param color: The color to use to draw the polygons.
    """
    image = Image.open(io.BytesIO(image_bytes))
    draw = ImageDraw.Draw(image)
    for polygon in polygons:
```

```
        draw.polygon(
            [
                (image.width * point["X"], image.height * point["Y"])
                for point in polygon
            ],
            outline=color,
        )
    image.show()
```

Criar classes para analisar objetos retornados pelo Amazon Rekognition.

```
class RekognitionFace:
    """Encapsulates an Amazon Rekognition face."""

    def __init__(self, face, timestamp=None):
        """
        Initializes the face object.

        :param face: Face data, in the format returned by Amazon Rekognition
                     functions.
        :param timestamp: The time when the face was detected, if the face was
                          detected in a video.
        """
        self.bounding_box = face.get("BoundingBox")
        self.confidence = face.get("Confidence")
        self.landmarks = face.get("Landmarks")
        self.pose = face.get("Pose")
        self.quality = face.get("Quality")
        age_range = face.get("AgeRange")
        if age_range is not None:
            self.age_range = (age_range.get("Low"), age_range.get("High"))
        else:
            self.age_range = None
        self.smile = face.get("Smile", {}).get("Value")
        self.eyeglasses = face.get("Eyeglasses", {}).get("Value")
        self.sunglasses = face.get("Sunglasses", {}).get("Value")
        self.gender = face.get("Gender", {}).get("Value", None)
        self.beard = face.get("Beard", {}).get("Value")
        self.mustache = face.get("Mustache", {}).get("Value")
        self.eyes_open = face.get("EyesOpen", {}).get("Value")
```

```
        self.mouth_open = face.get("MouthOpen", {}).get("Value")
        self.emotions = [
            emo.get("Type")
            for emo in face.get("Emotions", [])
            if emo.get("Confidence", 0) > 50
        ]
        self.face_id = face.get("FaceId")
        self.image_id = face.get("ImageId")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the face data to a dict.

        :return: A dict that contains the face data.
        """
        rendering = {}
        if self.bounding_box is not None:
            rendering["bounding_box"] = self.bounding_box
        if self.age_range is not None:
            rendering["age"] = f"{self.age_range[0]} - {self.age_range[1]}"
        if self.gender is not None:
            rendering["gender"] = self.gender
        if self.emotions:
            rendering["emotions"] = self.emotions
        if self.face_id is not None:
            rendering["face_id"] = self.face_id
        if self.image_id is not None:
            rendering["image_id"] = self.image_id
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        has = []
        if self.smile:
            has.append("smile")
        if self.eyeglasses:
            has.append("eyeglasses")
        if self.sunglasses:
            has.append("sunglasses")
        if self.beard:
            has.append("beard")
        if self.mustache:
            has.append("mustache")
        if self.eyes_open:
            has.append("open eyes")
```

```
        if self.mouth_open:
            has.append("open mouth")
        if has:
            rendering["has"] = has
        return rendering



class RekognitionCelebrity:
    """Encapsulates an Amazon Rekognition celebrity."""

    def __init__(self, celebrity, timestamp=None):
        """
        Initializes the celebrity object.

        :param celebrity: Celebrity data, in the format returned by Amazon
 Rekognition
                          functions.
        :param timestamp: The time when the celebrity was detected, if the celebrity
                          was detected in a video.
        """
        self.info_urls = celebrity.get("Urls")
        self.name = celebrity.get("Name")
        self.id = celebrity.get("Id")
        self.face = RekognitionFace(celebrity.get("Face"))
        self.confidence = celebrity.get("MatchConfidence")
        self.bounding_box = celebrity.get("BoundingBox")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the celebrity data to a dict.

        :return: A dict that contains the celebrity data.
        """
        rendering = self.face.to_dict()
        if self.name is not None:
            rendering["name"] = self.name
        if self.info_urls:
            rendering["info URLs"] = self.info_urls
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering
```

```
class RekognitionPerson:
    """Encapsulates an Amazon Rekognition person."""

    def __init__(self, person, timestamp=None):
        """
        Initializes the person object.

        :param person: Person data, in the format returned by Amazon Rekognition
                       functions.
        :param timestamp: The time when the person was detected, if the person
                          was detected in a video.
        """
        self.index = person.get("Index")
        self.bounding_box = person.get("BoundingBox")
        face = person.get("Face")
        self.face = RekognitionFace(face) if face is not None else None
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the person data to a dict.

        :return: A dict that contains the person data.
        """
        rendering = self.face.to_dict() if self.face is not None else {}
        if self.index is not None:
            rendering["index"] = self.index
        if self.bounding_box is not None:
            rendering["bounding_box"] = self.bounding_box
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionLabel:
    """Encapsulates an Amazon Rekognition label."""

    def __init__(self, label, timestamp=None):
        """
        Initializes the label object.
```

```
        :param label: Label data, in the format returned by Amazon Rekognition
                      functions.
        :param timestamp: The time when the label was detected, if the label
                          was detected in a video.
        """
        self.name = label.get("Name")
        self.confidence = label.get("Confidence")
        self.instances = label.get("Instances")
        self.parents = label.get("Parents")
        self.timestamp = timestamp

    def to_dict(self):
        """
        Renders some of the label data to a dict.

        :return: A dict that contains the label data.
        """
        rendering = {}
        if self.name is not None:
            rendering["name"] = self.name
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionModerationLabel:
    """Encapsulates an Amazon Rekognition moderation label."""

    def __init__(self, label, timestamp=None):
        """
        Initializes the moderation label object.

        :param label: Label data, in the format returned by Amazon Rekognition
                      functions.
        :param timestamp: The time when the moderation label was detected, if the
                          label was detected in a video.
        """
        self.name = label.get("Name")
        self.confidence = label.get("Confidence")
        self.parent_name = label.get("ParentName")
        self.timestamp = timestamp

    def to_dict(self):
```

```
        """
        Renders some of the moderation label data to a dict.

        :return: A dict that contains the moderation label data.
        """
        rendering = {}
        if self.name is not None:
            rendering["name"] = self.name
        if self.parent_name is not None:
            rendering["parent_name"] = self.parent_name
        if self.timestamp is not None:
            rendering["timestamp"] = self.timestamp
        return rendering



class RekognitionText:
    """Encapsulates an Amazon Rekognition text element."""

    def __init__(self, text_data):
        """
        Initializes the text object.

        :param text_data: Text data, in the format returned by Amazon Rekognition
                          functions.
        """
        self.text = text_data.get("DetectedText")
        self.kind = text_data.get("Type")
        self.id = text_data.get("Id")
        self.parent_id = text_data.get("ParentId")
        self.confidence = text_data.get("Confidence")
        self.geometry = text_data.get("Geometry")

    def to_dict(self):
        """
        Renders some of the text data to a dict.

        :return: A dict that contains the text data.
        """
        rendering = {}
        if self.text is not None:
            rendering["text"] = self.text
        if self.kind is not None:
            rendering["kind"] = self.kind
```

```
        if self.geometry is not None:
            rendering["polygon"] = self.geometry.get("Polygon")
        return rendering
```

Usar as classes wrapper para detectar elementos em imagens e exibir suas caixas delimitadoras. As imagens usadas neste exemplo podem ser encontradas GitHub junto com instruções e mais códigos.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Rekognition image detection demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    rekognition_client = boto3.client("rekognition")
    street_scene_file_name = ".media/pexels-kaique-rocha-109919.jpg"
    celebrity_file_name = ".media/pexels-pixabay-53370.jpg"
    one_girl_url = "https://dhei5unw3vrsx.cloudfront.net/images/source3_resized.jpg"
    three_girls_url = "https://dhei5unw3vrsx.cloudfront.net/images/
target3_resized.jpg"
    swimwear_object = boto3.resource("s3").Object(
        "console-sample-images-pdx", "yoga_swimwear.jpg"
    )
    book_file_name = ".media/pexels-christina-morillo-1181671.jpg"

    street_scene_image = RekognitionImage.from_file(
        street_scene_file_name, rekognition_client
    )
    print(f"Detecting faces in {street_scene_image.image_name}...")
    faces = street_scene_image.detect_faces()
    print(f"Found {len(faces)} faces, here are the first three.")
    for face in faces[:3]:
        pprint(face.to_dict())
    show_bounding_boxes(
        street_scene_image.image["Bytes"],
        [[face.bounding_box for face in faces]],
        ["aqua"],
    )
    input("Press Enter to continue.")
```

```
    print(f"Detecting labels in {street_scene_image.image_name}...")
    labels = street_scene_image.detect_labels(100)
    print(f"Found {len(labels)} labels.")
    for label in labels:
        pprint(label.to_dict())
    names = []
    box_sets = []
    colors = ["aqua", "red", "white", "blue", "yellow", "green"]
    for label in labels:
        if label.instances:
            names.append(label.name)
            box_sets.append([inst["BoundingBox"] for inst in label.instances])
    print(f"Showing bounding boxes for {names} in {colors[:len(names)]}.")
    show_bounding_boxes(
        street_scene_image.image["Bytes"], box_sets, colors[: len(names)]
    )
    input("Press Enter to continue.")

    celebrity_image = RekognitionImage.from_file(
        celebrity_file_name, rekognition_client
    )
    print(f"Detecting celebrities in {celebrity_image.image_name}...")
    celebs, others = celebrity_image.recognize_celebrities()
    print(f"Found {len(celebs)} celebrities.")
    for celeb in celebs:
        pprint(celeb.to_dict())
    show_bounding_boxes(
        celebrity_image.image["Bytes"],
        [[celeb.face.bounding_box for celeb in celebs]],
        ["aqua"],
    )
    input("Press Enter to continue.")

    girl_image_response = requests.get(one_girl_url)
    girl_image = RekognitionImage(
        {"Bytes": girl_image_response.content}, "one-girl", rekognition_client
    )
    group_image_response = requests.get(three_girls_url)
    group_image = RekognitionImage(
        {"Bytes": group_image_response.content}, "three-girls", rekognition_client
    )
    print("Comparing reference face to group of faces...")
    matches, unmatches = girl_image.compare_faces(group_image, 80)
    print(f"Found {len(matches)} face matching the reference face.")
```

```
    show_bounding_boxes(
        group_image.image["Bytes"],
        [[match.bounding_box for match in matches]],
        ["aqua"],
    )
    input("Press Enter to continue.")

    swimwear_image = RekognitionImage.from_bucket(swimwear_object,
rekognition_client)
    print(f"Detecting suggestive content in {swimwear_object.key}...")
    labels = swimwear_image.detect_moderation_labels()
    print(f"Found {len(labels)} moderation labels.")
    for label in labels:
        pprint(label.to_dict())
    input("Press Enter to continue.")

    book_image = RekognitionImage.from_file(book_file_name, rekognition_client)
    print(f"Detecting text in {book_image.image_name}...")
    texts = book_image.detect_text()
    print(f"Found {len(texts)} text instances. Here are the first seven:")
    for text in texts[:7]:
        pprint(text.to_dict())
    show_polygons(
        book_image.image["Bytes"], [text.geometry["Polygon"] for text in texts],
"aqua"
    )

    print("Thanks for watching!")
    print("-" * 88)
```

Exemplos do Amazon S3 usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Python (Boto3) com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Amazon S3

O exemplo de código a seguir mostra como começar a usar o Amazon S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_s3():
    """
    Use the AWS SDK for Python (Boto3) to create an Amazon Simple Storage Service
    (Amazon S3) resource and list the buckets in your account.
    This example uses the default settings specified in your shared credentials
    and config files.
    """
    s3_resource = boto3.resource("s3")
    print("Hello, Amazon S3! Let's list your buckets:")
    for bucket in s3_resource.buckets.all():
        print(f"\t{bucket.name}")


if __name__ == "__main__":
    hello_s3()
```

- Para obter detalhes da API, consulte a ListBucketsReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Adicionar regras de CORS a um bucket

O exemplo de código a seguir mostra como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def put_cors(self, cors_rules):
        """
        Apply CORS rules to the bucket. CORS rules specify the HTTP actions that are
        allowed from other domains.

        :param cors_rules: The CORS rules to apply.
        """
```

```
        try:
            self.bucket.Cors().put(CORSConfiguration={"CORSRules": cors_rules})
            logger.info(
                "Put CORS rules %s for bucket '%s'.", cors_rules, self.bucket.name
            )
        except ClientError:
            logger.exception("Couldn't put CORS rules for bucket %s.",
self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketCorsReferência da API AWSSDK for Python (Boto3).

Adicionar uma configuração de ciclo de vida a um bucket

O exemplo de código a seguir mostra como adicionar a configuração de ciclo de vida a um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name
```

```
    def put_lifecycle_configuration(self, lifecycle_rules):
        """
        Apply a lifecycle configuration to the bucket. The lifecycle configuration
can
        be used to archive or delete the objects in the bucket according to
specified
        parameters, such as a number of days.

        :param lifecycle_rules: The lifecycle rules to apply.
        """
        try:
            self.bucket.LifecycleConfiguration().put(
                LifecycleConfiguration={"Rules": lifecycle_rules}
            )
            logger.info(
                "Put lifecycle rules %s for bucket '%s'.",
                lifecycle_rules,
                self.bucket.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't put lifecycle rules for bucket '%s'.", self.bucket.name
            )
            raise
```

- Para obter detalhes da API, consulte a PutBucketLifecycleConfigurationReferência da API AWSSDK for Python (Boto3).

Adicionar uma política a um bucket

O exemplo de código a seguir mostra como adicionar uma política a um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def put_policy(self, policy):
        """
        Apply a security policy to the bucket. Policies control users' ability
        to perform specific actions, such as listing the objects in the bucket.

        :param policy: The policy to apply to the bucket.
        """
        try:
            self.bucket.Policy().put(Policy=json.dumps(policy))
            logger.info("Put policy %s for bucket '%s'.", policy, self.bucket.name)
        except ClientError:
            logger.exception("Couldn't apply policy to bucket '%s'.",
 self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketPolicyReferência da API AWSSDK for Python (Boto3).

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                            that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def copy(self, dest_object):
        """
        Copies the object to another bucket.

        :param dest_object: The destination object initialized with a bucket and
 key.
                              This is a Boto3 Object resource.
        """
        try:
            dest_object.copy_from(
                CopySource={"Bucket": self.object.bucket_name, "Key":
 self.object.key}
            )
            dest_object.wait_until_exists()
            logger.info(
                "Copied object from %s:%s to %s:%s.",
                self.object.bucket_name,
                self.object.key,
                dest_object.bucket_name,
                dest_object.key,
            )
```

```
        except ClientError:
            logger.exception(
                "Couldn't copy object from %s/%s to %s/%s.",
                self.object.bucket_name,
                self.object.key,
                dest_object.bucket_name,
                dest_object.key,
            )
            raise
```

- Para obter detalhes da API, consulte a CopyObjectReferência da API AWSSDK for Python (Boto3).

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um bucket com as configurações padrão.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name
```

```
    def create(self, region_override=None):
        """
        Create an Amazon S3 bucket in the default Region for the account or in the
        specified Region.

        :param region_override: The Region in which to create the bucket. If this is
                                not specified, the Region configured in your shared
                                credentials is used.
        """
        if region_override is not None:
            region = region_override
        else:
            region = self.bucket.meta.client.meta.region_name
        try:
            self.bucket.create(CreateBucketConfiguration={"LocationConstraint":
 region})

            self.bucket.wait_until_exists()
            logger.info("Created bucket '%s' in region=%s", self.bucket.name,
 region)
        except ClientError as error:
            logger.exception(
                "Couldn't create bucket named '%s' in region=%s.",
                self.bucket.name,
                region,
            )
            raise error
```

Crie um bucket versionado com uma configuração de ciclo de vida.

```
def create_versioned_bucket(bucket_name, prefix):
    """
    Creates an Amazon S3 bucket, enables it for versioning, and configures a
 lifecycle
    that expires noncurrent object versions after 7 days.

    Adding a lifecycle configuration to a versioned bucket is a best practice.
    It helps prevent objects in the bucket from accumulating a large number of
    noncurrent versions, which can slow down request performance.
```

```
    Usage is shown in the usage_demo_single_object function at the end of this
module.

    :param bucket_name: The name of the bucket to create.
    :param prefix: Identifies which objects are automatically expired under the
                   configured lifecycle rules.
    :return: The newly created bucket.
    """
    try:
        bucket = s3.create_bucket(
            Bucket=bucket_name,
            CreateBucketConfiguration={
                "LocationConstraint": s3.meta.client.meta.region_name
            },
        )
        logger.info("Created bucket %s.", bucket.name)
    except ClientError as error:
        if error.response["Error"]["Code"] == "BucketAlreadyOwnedByYou":
            logger.warning("Bucket %s already exists! Using it.", bucket_name)
            bucket = s3.Bucket(bucket_name)
        else:
            logger.exception("Couldn't create bucket %s.", bucket_name)
            raise

    try:
        bucket.Versioning().enable()
        logger.info("Enabled versioning on bucket %s.", bucket.name)
    except ClientError:
        logger.exception("Couldn't enable versioning on bucket %s.", bucket.name)
        raise

    try:
        expiration = 7
        bucket.LifecycleConfiguration().put(
            LifecycleConfiguration={
                "Rules": [
                    {
                        "Status": "Enabled",
                        "Prefix": prefix,
                        "NoncurrentVersionExpiration": {"NoncurrentDays":
expiration},
                    }
                ]
            }
```

```
        )
        logger.info(
            "Configured lifecycle to expire noncurrent versions after %s days "
            "on bucket %s.",
            expiration,
            bucket.name,
        )
    except ClientError as error:
        logger.warning(
            "Couldn't configure lifecycle on bucket %s because %s. "
            "Continuing anyway.",
            bucket.name,
            error,
        )

    return bucket
```

- Para obter detalhes da API, consulte a CreateBucketReferência da API AWSSDK for Python (Boto3).

Excluir regras de CORS de um bucket

Os exemplos de código a seguir mostram como excluir regras de CORS de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
```

```
                        that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete_cors(self):
        """
        Delete the CORS rules from the bucket.

        :param bucket_name: The name of the bucket to update.
        """
        try:
            self.bucket.Cors().delete()
            logger.info("Deleted CORS from bucket '%s'.", self.bucket.name)
        except ClientError:
            logger.exception("Couldn't delete CORS from bucket '%s'.",
self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketCorsReferência da API AWSSDK for Python (Boto3).

Excluir uma política de um bucket

O exemplo de código a seguir mostra como excluir uma política de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
```

```
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete_policy(self):
        """
        Delete the security policy from the bucket.
        """
        try:
            self.bucket.Policy().delete()
            logger.info("Deleted policy for bucket '%s'.", self.bucket.name)
        except ClientError:
            logger.exception(
                "Couldn't delete policy for bucket '%s'.", self.bucket.name
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketPolicyReferência da API AWSSDK for Python (Boto3).

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""
```

```
    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete(self):
        """
        Delete the bucket. The bucket must be empty or an error is raised.
        """
        try:
            self.bucket.delete()
            self.bucket.wait_until_not_exists()
            logger.info("Bucket %s successfully deleted.", self.bucket.name)
        except ClientError:
            logger.exception("Couldn't delete bucket %s.", self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketReferência da API AWSSDK for Python (Boto3).

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um objeto.

```
class ObjectWrapper:
```

```
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def delete(self):
        """
        Deletes the object.
        """
        try:
            self.object.delete()
            self.object.wait_until_not_exists()
            logger.info(
                "Deleted object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't delete object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
```

Reverta um objeto para uma versão anterior excluindo versões posteriores do objeto.

```
def rollback_object(bucket, object_key, version_id):
    """
    Rolls back an object to an earlier version by deleting all versions that
    occurred after the specified rollback version.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.
```

```
    :param bucket: The bucket that holds the object to roll back.
    :param object_key: The object to roll back.
    :param version_id: The version ID to roll back to.
    """
    # Versions must be sorted by last_modified date because delete markers are
    # at the end of the list even when they are interspersed in time.
    versions = sorted(
        bucket.object_versions.filter(Prefix=object_key),
        key=attrgetter("last_modified"),
        reverse=True,
    )

    logger.debug(
        "Got versions:\n%s",
        "\n".join(
            [
                f"\t{version.version_id}, last modified {version.last_modified}"
                for version in versions
            ]
        ),
    )

    if version_id in [ver.version_id for ver in versions]:
        print(f"Rolling back to version {version_id}")
        for version in versions:
            if version.version_id != version_id:
                version.delete()
                print(f"Deleted version {version.version_id}")
            else:
                break

        print(f"Active version is now {bucket.Object(object_key).version_id}")
    else:
        raise KeyError(
            f"{version_id} was not found in the list of versions for "
f"{object_key}."
        )
```

Restaure um objeto excluído removendo o marcador de exclusão ativo do objeto.

```
def revive_object(bucket, object_key):
    """
    Revives a versioned object that was deleted by removing the object's active
    delete marker.
    A versioned object presents as deleted when its latest version is a delete
 marker.
    By removing the delete marker, we make the previous version the latest version
    and the object then presents as *not* deleted.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to revive.
    """
    # Get the latest version for the object.
    response = s3.meta.client.list_object_versions(
        Bucket=bucket.name, Prefix=object_key, MaxKeys=1
    )

    if "DeleteMarkers" in response:
        latest_version = response["DeleteMarkers"][0]
        if latest_version["IsLatest"]:
            logger.info(
                "Object %s was indeed deleted on %s. Let's revive it.",
                object_key,
                latest_version["LastModified"],
            )
            obj = bucket.Object(object_key)
            obj.Version(latest_version["VersionId"]).delete()
            logger.info(
                "Revived %s, active version is now %s  with body '%s'",
                object_key,
                obj.version_id,
                obj.get()["Body"].read(),
            )
        else:
            logger.warning(
                "Delete marker is not the latest version for %s!", object_key
            )
    elif "Versions" in response:
        logger.warning("Got an active version for %s, nothing to do.", object_key)
    else:
```

```
        logger.error("Couldn't get any version info for %s.", object_key)
```

Crie um manipulador do Lambda que remova um marcador de exclusão de um objeto do S3. Esse manipulador pode ser usado para limpar com eficiência marcadores de exclusão estranhos em um bucket versionado.

```
import logging
from urllib import parse
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
logger.setLevel("INFO")

s3 = boto3.client("s3")


def lambda_handler(event, context):
    """
    Removes a delete marker from the specified versioned object.

    :param event: The S3 batch event that contains the ID of the delete marker
                  to remove.
    :param context: Context about the event.
    :return: A result structure that Amazon S3 uses to interpret the result of the
             operation. When the result code is TemporaryFailure, S3 retries the
             operation.
    """
    # Parse job parameters from Amazon S3 batch operations
    invocation_id = event["invocationId"]
    invocation_schema_version = event["invocationSchemaVersion"]

    results = []
    result_code = None
    result_string = None

    task = event["tasks"][0]
    task_id = task["taskId"]

    try:
```

```
        obj_key = parse.unquote(task["s3Key"], encoding="utf-8")
        obj_version_id = task["s3VersionId"]
        bucket_name = task["s3BucketArn"].split(":")[-1]

        logger.info(
            "Got task: remove delete marker %s from object %s.", obj_version_id,
obj_key
        )

        try:
            # If this call does not raise an error, the object version is not a
delete
            # marker and should not be deleted.
            response = s3.head_object(
                Bucket=bucket_name, Key=obj_key, VersionId=obj_version_id
            )
            result_code = "PermanentFailure"
            result_string = (
                f"Object {obj_key}, ID {obj_version_id} is not " f"a delete marker."
            )

            logger.debug(response)
            logger.warning(result_string)
        except ClientError as error:
            delete_marker = error.response["ResponseMetadata"]["HTTPHeaders"].get(
                "x-amz-delete-marker", "false"
            )
            if delete_marker == "true":
                logger.info(
                    "Object %s, version %s is a delete marker.", obj_key,
obj_version_id
                )
                try:
                    s3.delete_object(
                        Bucket=bucket_name, Key=obj_key, VersionId=obj_version_id
                    )
                    result_code = "Succeeded"
                    result_string = (
                        f"Successfully removed delete marker "
                        f"{obj_version_id} from object {obj_key}."
                    )
                    logger.info(result_string)
                except ClientError as error:
```

```
                    # Mark request timeout as a temporary failure so it will be
retried.
                    if error.response["Error"]["Code"] == "RequestTimeout":
                        result_code = "TemporaryFailure"
                        result_string = (
                            f"Attempt to remove delete marker from  "
                            f"object {obj_key} timed out."
                        )
                        logger.info(result_string)
                    else:
                        raise
            else:
                raise ValueError(
                    f"The x-amz-delete-marker header is either not "
                    f"present or is not 'true'."
                )
    except Exception as error:
        # Mark all other exceptions as permanent failures.
        result_code = "PermanentFailure"
        result_string = str(error)
        logger.exception(error)
    finally:
        results.append(
            {
                "taskId": task_id,
                "resultCode": result_code,
                "resultString": result_string,
            }
        )
    return {
        "invocationSchemaVersion": invocation_schema_version,
        "treatMissingKeysAs": "PermanentFailure",
        "invocationId": invocation_id,
        "results": results,
    }
```

- Para obter detalhes da API, consulte a DeleteObjectReferência da API AWSSDK for Python (Boto3).

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua um conjunto de objetos de uma lista de chaves.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                           that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def delete_objects(bucket, object_keys):
        """
        Removes a list of objects from a bucket.
        This operation is done as a batch in a single request.

        :param bucket: The bucket that contains the objects. This is a Boto3 Bucket
                       resource.
        :param object_keys: The list of keys that identify the objects to remove.
        :return: The response that contains data about which objects were deleted
                 and any that could not be deleted.
        """
        try:
            response = bucket.delete_objects(
                Delete={"Objects": [{"Key": key} for key in object_keys]}
            )
```

```
            if "Deleted" in response:
                logger.info(
                    "Deleted objects '%s' from bucket '%s'.",
                    [del_obj["Key"] for del_obj in response["Deleted"]],
                    bucket.name,
                )
            if "Errors" in response:
                logger.warning(
                    "Could not delete objects '%s' from bucket '%s'.",
                    [
                        f"{del_obj['Key']}: {del_obj['Code']}"
                        for del_obj in response["Errors"]
                    ],
                    bucket.name,
                )
        except ClientError:
            logger.exception("Couldn't delete any objects from bucket %s.",
 bucket.name)
            raise
        else:
            return response
```

Exclua todos os objetos em um bucket.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def empty_bucket(bucket):
        """
        Remove all objects from a bucket.
```

```
        :param bucket: The bucket to empty. This is a Boto3 Bucket resource.
        """
        try:
            bucket.objects.delete()
            logger.info("Emptied bucket '%s'.", bucket.name)
        except ClientError:
            logger.exception("Couldn't empty bucket '%s'.", bucket.name)
            raise
```

Exclua permanentemente um objeto versionado excluindo todas as suas versões.

```
def permanently_delete_object(bucket, object_key):
    """
    Permanently deletes a versioned object by deleting all of its versions.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to delete.
    """
    try:
        bucket.object_versions.filter(Prefix=object_key).delete()
        logger.info("Permanently deleted all versions of object %s.", object_key)
    except ClientError:
        logger.exception("Couldn't delete all versions of %s.", object_key)
        raise
```

- Para obter detalhes da API, consulte a DeleteObjectsReferência da API AWSSDK for Python (Boto3).

Excluir a configuração de ciclo de vida de um bucket

O exemplo de código a seguir mostra como excluir a configuração de ciclo de vida de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def delete_lifecycle_configuration(self):
        """
        Remove the lifecycle configuration from the specified bucket.
        """
        try:
            self.bucket.LifecycleConfiguration().delete()
            logger.info(
                "Deleted lifecycle configuration for bucket '%s'.", self.bucket.name
            )
        except ClientError:
            logger.exception(
                "Couldn't delete lifecycle configuration for bucket '%s'.",
                self.bucket.name,
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteBucketLifecycleReferência da API AWSSDK for Python (Boto3).

Determinar a existência de um bucket

O exemplo de código a seguir mostra como determinar a existência de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def exists(self):
        """
        Determine whether the bucket exists and you have access to it.

        :return: True when the bucket exists; otherwise, False.
        """
        try:
            self.bucket.meta.client.head_bucket(Bucket=self.bucket.name)
            logger.info("Bucket %s exists.", self.bucket.name)
            exists = True
        except ClientError:
            logger.warning(
                "Bucket %s doesn't exist or you don't have access to it.",
                self.bucket.name,
            )
            exists = False
        return exists
```

- Para obter detalhes da API, consulte a HeadBucketReferência da API AWSSDK for Python (Boto3).

Obter regras de CORS para um bucket

O exemplos de código a seguir mostra como obter regras de compartilhamento de recursos de origem cruzada (CORS) para um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_cors(self):
        """
        Get the CORS rules for the bucket.

        :return The CORS rules for the specified bucket.
        """
        try:
            cors = self.bucket.Cors()
            logger.info(
```

```
                "Got CORS rules %s for bucket '%s'.", cors.cors_rules,
self.bucket.name
            )
        except ClientError:
            logger.exception(("Couldn't get CORS for bucket %s.", self.bucket.name))
            raise
        else:
            return cors
```

- Para obter detalhes da API, consulte a GetBucketCorsReferência da API AWSSDK for Python (Boto3).

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def get(self):
        """
        Gets the object.
```

```
        :return: The object data in bytes.
        """
        try:
            body = self.object.get()["Body"].read()
            logger.info(
                "Got object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't get object '%s' from bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
        else:
            return body
```

- Para obter detalhes da API, consulte a GetObjectReferência da API AWSSDK for Python (Boto3).

Obter a ACL de um bucket

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""
```

```
    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_acl(self):
        """
        Get the ACL of the bucket.

        :return: The ACL of the bucket.
        """
        try:
            acl = self.bucket.Acl()
            logger.info(
                "Got ACL for bucket %s. Owner is %s.", self.bucket.name, acl.owner
            )
        except ClientError:
            logger.exception("Couldn't get ACL for bucket %s.", self.bucket.name)
            raise
        else:
            return acl
```

- Para obter detalhes da API, consulte a GetBucketAclReferência da API AWSSDK for Python (Boto3).

Obter a ACL de um objeto

O exemplo de código a seguir mostra como obter a lista de controle de acesso (ACL) de um objeto do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                           that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def get_acl(self):
        """
        Gets the ACL of the object.

        :return: The ACL of the object.
        """
        try:
            acl = self.object.Acl()
            logger.info(
                "Got ACL for object %s owned by %s.",
                self.object.key,
                acl.owner["DisplayName"],
            )
        except ClientError:
            logger.exception("Couldn't get ACL for object %s.", self.object.key)
            raise
        else:
            return acl
```

- Para obter detalhes da API, consulte a GetObjectAclReferência da API AWSSDK for Python (Boto3).

Obter a configuração de ciclo de vida de um bucket

O exemplo de código a seguir mostra como obter a configuração de ciclo de vida de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_lifecycle_configuration(self):
        """
        Get the lifecycle configuration of the bucket.

        :return: The lifecycle rules of the specified bucket.
        """
        try:
            config = self.bucket.LifecycleConfiguration()
            logger.info(
                "Got lifecycle rules %s for bucket '%s'.",
                config.rules,
                self.bucket.name,
```

```
            )
        except:
            logger.exception(
                "Couldn't get lifecycle rules for bucket '%s'.", self.bucket.name
            )
            raise
        else:
            return config.rules
```

- Para obter detalhes da API, consulte a GetBucketLifecycleConfigurationReferência da API AWSSDK for Python (Boto3).

Obter a política de um bucket

O exemplo de código a seguir mostra como obter a política de um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def get_policy(self):
        """
        Get the security policy of the bucket.
```

```
        :return: The security policy of the specified bucket, in JSON format.
        """
        try:
            policy = self.bucket.Policy()
            logger.info(
                "Got policy %s for bucket '%s'.", policy.policy, self.bucket.name
            )
        except ClientError:
            logger.exception("Couldn't get policy for bucket '%s'.",
self.bucket.name)
            raise
        else:
            return json.loads(policy.policy)
```

- Para obter detalhes da API, consulte a GetBucketPolicyReferência da API AWSSDK for Python (Boto3).

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
```

```
        self.name = bucket.name


    @staticmethod
    def list(s3_resource):
        """
        Get the buckets in all Regions for the current account.

        :param s3_resource: A Boto3 S3 resource. This is a high-level resource in
Boto3
                            that contains collections and factory methods to create
                            other high-level S3 sub-resources.
        :return: The list of buckets.
        """
        try:
            buckets = list(s3_resource.buckets.all())
            logger.info("Got buckets: %s.", buckets)
        except ClientError:
            logger.exception("Couldn't get buckets.")
            raise
        else:
            return buckets
```

- Para obter detalhes da API, consulte a ListBucketsReferência da API AWSSDK for Python (Boto3).

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
```

```
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    @staticmethod
    def list(bucket, prefix=None):
        """
        Lists the objects in a bucket, optionally filtered by a prefix.

        :param bucket: The bucket to query. This is a Boto3 Bucket resource.
        :param prefix: When specified, only objects that start with this prefix are
listed.
        :return: The list of objects.
        """
        try:
            if not prefix:
                objects = list(bucket.objects.all())
            else:
                objects = list(bucket.objects.filter(Prefix=prefix))
            logger.info(
                "Got objects %s from bucket '%s'", [o.key for o in objects],
bucket.name
            )
        except ClientError:
            logger.exception("Couldn't get objects for bucket '%s'.", bucket.name)
            raise
        else:
            return objects
```

- Para obter detalhes da API, consulte Referência da API ListObjectsV2 no AWSSDK for Python (Boto3).

Definir uma nova ACL para um bucket

O exemplo de código a seguir mostra como definir uma nova lista de controle de acesso (ACL) para um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BucketWrapper:
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
 Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def grant_log_delivery_access(self):
        """
        Grant the AWS Log Delivery group write access to the bucket so that
        Amazon S3 can deliver access logs to the bucket. This is the only
 recommended
        use of an S3 bucket ACL.
        """
        try:
            acl = self.bucket.Acl()
            # Putting an ACL overwrites the existing ACL. If you want to preserve
            # existing grants, append new grants to the list of existing grants.
            grants = acl.grants if acl.grants else []
            grants.append(
                {
                    "Grantee": {
                        "Type": "Group",
```

```
                        "URI": "http://acs.amazonaws.com/groups/s3/LogDelivery",
                    },
                    "Permission": "WRITE",
                }
            )
            acl.put(AccessControlPolicy={"Grants": grants, "Owner": acl.owner})
            logger.info("Granted log delivery access to bucket '%s'",
 self.bucket.name)
        except ClientError:
            logger.exception("Couldn't add ACL to bucket '%s'.", self.bucket.name)
            raise
```

- Para obter detalhes da API, consulte a PutBucketAclReferência da API AWSSDK for Python (Boto3).

Definir a ACL de um objeto

O exemplo de código a seguir mostra como definir a lista de controle de acesso (ACL) de um objeto do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                          that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key
```

```
    def put_acl(self, email):
        """
        Applies an ACL to the object that grants read access to an AWS user
identified
        by email address.

        :param email: The email address of the user to grant access.
        """
        try:
            acl = self.object.Acl()
            # Putting an ACL overwrites the existing ACL, so append new grants
            # if you want to preserve existing grants.
            grants = acl.grants if acl.grants else []
            grants.append(
                {
                    "Grantee": {"Type": "AmazonCustomerByEmail", "EmailAddress":
email},
                    "Permission": "READ",
                }
            )
            acl.put(AccessControlPolicy={"Grants": grants, "Owner": acl.owner})
            logger.info("Granted read access to %s.", email)
        except ClientError:
            logger.exception("Couldn't add ACL to object '%s'.", self.object.key)
            raise
```

- Para obter detalhes da API, consulte a PutObjectAclReferência da API AWSSDK for Python (Boto3).

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class ObjectWrapper:
    """Encapsulates S3 object actions."""

    def __init__(self, s3_object):
        """
        :param s3_object: A Boto3 Object resource. This is a high-level resource in
 Boto3
                            that wraps object actions in a class-like structure.
        """
        self.object = s3_object
        self.key = self.object.key


    def put(self, data):
        """
        Upload data to the object.

        :param data: The data to upload. This can either be bytes or a string. When
 this
                     argument is a string, it is interpreted as a file name, which
 is
                     opened in read bytes mode.
        """
        put_data = data
        if isinstance(data, str):
            try:
                put_data = open(data, "rb")
            except IOError:
                logger.exception("Expected file name or binary data, got '%s'.",
 data)
                raise

        try:
            self.object.put(Body=put_data)
```

```
            self.object.wait_until_exists()
            logger.info(
                "Put object '%s' to bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't put object '%s' to bucket '%s'.",
                self.object.key,
                self.object.bucket_name,
            )
            raise
        finally:
            if getattr(put_data, "close", None):
                put_data.close()
```

- Para obter detalhes da API, consulte a PutObjectReferência da API AWSSDK for Python (Boto3).

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Gere um URL pré-assinado que possa realizar uma ação do S3 por tempo limitado. Use o pacote Requests (Solicitações) para fazer uma solicitação com o URL.

```
import argparse
import logging
```

```
import boto3
from botocore.exceptions import ClientError
import requests

logger = logging.getLogger(__name__)


def generate_presigned_url(s3_client, client_method, method_parameters, expires_in):
    """
    Generate a presigned Amazon S3 URL that can be used to perform an action.

    :param s3_client: A Boto3 Amazon S3 client.
    :param client_method: The name of the client method that the URL performs.
    :param method_parameters: The parameters of the specified client method.
    :param expires_in: The number of seconds the presigned URL is valid for.
    :return: The presigned URL.
    """
    try:
        url = s3_client.generate_presigned_url(
            ClientMethod=client_method, Params=method_parameters,
 ExpiresIn=expires_in
        )
        logger.info("Got presigned URL: %s", url)
    except ClientError:
        logger.exception(
            "Couldn't get a presigned URL for client method '%s'.", client_method
        )
        raise
    return url


def usage_demo():
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print("Welcome to the Amazon S3 presigned URL demo.")
    print("-" * 88)

    parser = argparse.ArgumentParser()
    parser.add_argument("bucket", help="The name of the bucket.")
    parser.add_argument(
        "key",
        help="For a GET operation, the key of the object in Amazon S3. For a "
        "PUT operation, the name of a file to upload.",
```

```
    )
    parser.add_argument("action", choices=("get", "put"), help="The action to
 perform.")
    args = parser.parse_args()

    s3_client = boto3.client("s3")
    client_action = "get_object" if args.action == "get" else "put_object"
    url = generate_presigned_url(
        s3_client, client_action, {"Bucket": args.bucket, "Key": args.key}, 1000
    )

    print("Using the Requests package to send a request to the URL.")
    response = None
    if args.action == "get":
        response = requests.get(url)
    elif args.action == "put":
        print("Putting data to the URL.")
        try:
            with open(args.key, "r") as object_file:
                object_text = object_file.read()
            response = requests.put(url, data=object_text)
        except FileNotFoundError:
            print(
                f"Couldn't find {args.key}. For a PUT operation, the key must be the
 "
                f"name of a file that exists on your computer."
            )

    if response is not None:
        print("Got response:")
        print(f"Status: {response.status_code}")
        print(response.text)

    print("-" * 88)


if __name__ == "__main__":
    usage_demo()
```

Gere uma solicitação POST pré-assinada para carregar um arquivo.

```
class BucketWrapper:
```

```
    """Encapsulates S3 bucket actions."""

    def __init__(self, bucket):
        """
        :param bucket: A Boto3 Bucket resource. This is a high-level resource in
Boto3
                       that wraps bucket actions in a class-like structure.
        """
        self.bucket = bucket
        self.name = bucket.name


    def generate_presigned_post(self, object_key, expires_in):
        """
        Generate a presigned Amazon S3 POST request to upload a file.
        A presigned POST can be used for a limited time to let someone without an
AWS
        account upload a file to a bucket.

        :param object_key: The object key to identify the uploaded object.
        :param expires_in: The number of seconds the presigned POST is valid.
        :return: A dictionary that contains the URL and form fields that contain
                 required access data.
        """
        try:
            response = self.bucket.meta.client.generate_presigned_post(
                Bucket=self.bucket.name, Key=object_key, ExpiresIn=expires_in
            )
            logger.info("Got presigned POST URL: %s", response["url"])
        except ClientError:
            logger.exception(
                "Couldn't get a presigned POST URL for bucket '%s' and object '%s'",
                self.bucket.name,
                object_key,
            )
            raise
        return response
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import io
import os
import uuid

import boto3
from boto3.s3.transfer import S3UploadFailedError
from botocore.exceptions import ClientError


def do_scenario(s3_resource):
    print("-" * 88)
    print("Welcome to the Amazon S3 getting started demo!")
    print("-" * 88)

    bucket_name = f"doc-example-bucket-{uuid.uuid4()}"
    bucket = s3_resource.Bucket(bucket_name)
    try:
        bucket.create(
            CreateBucketConfiguration={
                "LocationConstraint": s3_resource.meta.client.meta.region_name
            }
        )
```

```
        print(f"Created demo bucket named {bucket.name}.")
    except ClientError as err:
        print(f"Tried and failed to create demo bucket {bucket_name}.")
        print(f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}")
        print(f"\nCan't continue the demo without a bucket!")
        return

    file_name = None
    while file_name is None:
        file_name = input("\nEnter a file you want to upload to your bucket: ")
        if not os.path.exists(file_name):
            print(f"Couldn't find file {file_name}. Are you sure it exists?")
            file_name = None

    obj = bucket.Object(os.path.basename(file_name))
    try:
        obj.upload_file(file_name)
        print(
            f"Uploaded file {file_name} into bucket {bucket.name} with key
 {obj.key}."
        )
    except S3UploadFailedError as err:
        print(f"Couldn't upload file {file_name} to {bucket.name}.")
        print(f"\t{err}")

    answer = input(f"\nDo you want to download {obj.key} into memory (y/n)? ")
    if answer.lower() == "y":
        data = io.BytesIO()
        try:
            obj.download_fileobj(data)
            data.seek(0)
            print(f"Got your object. Here are the first 20 bytes:\n")
            print(f"\t{data.read(20)}")
        except ClientError as err:
            print(f"Couldn't download {obj.key}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    answer = input(
        f"\nDo you want to copy {obj.key} to a subfolder in your bucket (y/n)? "
    )
```

```
    if answer.lower() == "y":
        dest_obj = bucket.Object(f"demo-folder/{obj.key}")
        try:
            dest_obj.copy({"Bucket": bucket.name, "Key": obj.key})
            print(f"Copied {obj.key} to {dest_obj.key}.")
        except ClientError as err:
            print(f"Couldn't copy {obj.key} to {dest_obj.key}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    print("\nYour bucket contains the following objects:")
    try:
        for o in bucket.objects.all():
            print(f"\t{o.key}")
    except ClientError as err:
        print(f"Couldn't list the objects in bucket {bucket.name}.")
        print(f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}")

    answer = input(
        "\nDo you want to delete all of the objects as well as the bucket (y/n)? "
    )
    if answer.lower() == "y":
        try:
            bucket.objects.delete()
            bucket.delete()
            print(f"Emptied and deleted bucket {bucket.name}.\n")
        except ClientError as err:
            print(f"Couldn't empty and delete bucket {bucket.name}.")
            print(
                f"\t{err.response['Error']['Code']}:{err.response['Error']
['Message']}"
            )

    print("Thanks for watching!")
    print("-" * 88)


if __name__ == "__main__":
    do_scenario(boto3.resource("s3"))
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Gerenciar objetos versionados em lotes com uma função do Lambda

O exemplo de código a seguir mostra como gerenciar objetos do S3 versionados em lotes com uma função do Lambda.

SDK para Python (Boto3)

Mostra como manipular objetos do Amazon Simple Storage Service (Amazon S3) versionados em lotes criando trabalhos que chamam funções do AWS Lambda para executar o processamento. Este exemplo cria um bucket habilitado para versão, carrega as estrofes do poema Você é velho, padre William, de Lewis Carroll, e usa trabalhos em lote do Amazon S3 para distorcer o poema de várias maneiras.

Aprenda como:

- Criar funções do Lambda que operam em objetos versionados.
- Criar um manifesto de objetos para atualizar.
- Cria trabalhos em lote que invocam funções do Lambda para atualizar objetos.
- Excluir funções do Lambda
- Esvaziar e excluir um bucket versionado.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que transfiram arquivos usando várias configurações do gerenciador de transferências disponíveis. Use uma classe de retorno de chamada para gravar o andamento do retorno de chamada durante a transferência de arquivos.

```
import sys
import threading

import boto3
from boto3.s3.transfer import TransferConfig


MB = 1024 * 1024
s3 = boto3.resource("s3")


class TransferCallback:
    """
    Handle callbacks from the transfer manager.

    The transfer manager periodically calls the __call__ method throughout
    the upload and download process so that it can take action, such as
    displaying progress to the user and collecting data about the transfer.
    """

    def __init__(self, target_size):
        self._target_size = target_size
        self._total_transferred = 0
```

```
        self._lock = threading.Lock()
        self.thread_info = {}

    def __call__(self, bytes_transferred):
        """
        The callback method that is called by the transfer manager.

        Display progress during file transfer and collect per-thread transfer
        data. This method can be called by multiple threads, so shared instance
        data is protected by a thread lock.
        """
        thread = threading.current_thread()
        with self._lock:
            self._total_transferred += bytes_transferred
            if thread.ident not in self.thread_info.keys():
                self.thread_info[thread.ident] = bytes_transferred
            else:
                self.thread_info[thread.ident] += bytes_transferred

            target = self._target_size * MB
            sys.stdout.write(
                f"\r{self._total_transferred} of {target} transferred "
                f"({(self._total_transferred / target) * 100:.2f}%)."
            )
            sys.stdout.flush()


def upload_with_default_configuration(
    local_file_path, bucket_name, object_key, file_size_mb
):
    """
    Upload a file from a local folder to an Amazon S3 bucket, using the default
    configuration.
    """
    transfer_callback = TransferCallback(file_size_mb)
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def upload_with_chunksize_and_meta(
    local_file_path, bucket_name, object_key, file_size_mb, metadata=None
):
```

```
    """
    Upload a file from a local folder to an Amazon S3 bucket, setting a
    multipart chunk size and adding metadata to the Amazon S3 object.

    The multipart chunk size controls the size of the chunks of data that are
    sent in the request. A smaller chunk size typically results in the transfer
    manager using more threads for the upload.

    The metadata is a set of key-value pairs that are stored with the object
    in Amazon S3.
    """
    transfer_callback = TransferCallback(file_size_mb)

    config = TransferConfig(multipart_chunksize=1 * MB)
    extra_args = {"Metadata": metadata} if metadata else None
    s3.Bucket(bucket_name).upload_file(
        local_file_path,
        object_key,
        Config=config,
        ExtraArgs=extra_args,
        Callback=transfer_callback,
    )
    return transfer_callback.thread_info


def upload_with_high_threshold(local_file_path, bucket_name, object_key,
 file_size_mb):
    """
    Upload a file from a local folder to an Amazon S3 bucket, setting a
    multipart threshold larger than the size of the file.

    Setting a multipart threshold larger than the size of the file results
    in the transfer manager sending the file as a standard upload instead of
    a multipart upload.
    """
    transfer_callback = TransferCallback(file_size_mb)
    config = TransferConfig(multipart_threshold=file_size_mb * 2 * MB)
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, Config=config, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def upload_with_sse(
```

```
    local_file_path, bucket_name, object_key, file_size_mb, sse_key=None
):
    """
    Upload a file from a local folder to an Amazon S3 bucket, adding server-side
    encryption with customer-provided encryption keys to the object.

    When this kind of encryption is specified, Amazon S3 encrypts the object
    at rest and allows downloads only when the expected encryption key is
    provided in the download request.
    """
    transfer_callback = TransferCallback(file_size_mb)
    if sse_key:
        extra_args = {"SSECustomerAlgorithm": "AES256", "SSECustomerKey": sse_key}
    else:
        extra_args = None
    s3.Bucket(bucket_name).upload_file(
        local_file_path, object_key, ExtraArgs=extra_args,
 Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_default_configuration(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, using the
    default configuration.
    """
    transfer_callback = TransferCallback(file_size_mb)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_single_thread(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, using a
    single thread.
    """
    transfer_callback = TransferCallback(file_size_mb)
```

```
    config = TransferConfig(use_threads=False)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Config=config, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_high_threshold(
    bucket_name, object_key, download_file_path, file_size_mb
):
    """
    Download a file from an Amazon S3 bucket to a local folder, setting a
    multipart threshold larger than the size of the file.

    Setting a multipart threshold larger than the size of the file results
    in the transfer manager sending the file as a standard download instead
    of a multipart download.
    """
    transfer_callback = TransferCallback(file_size_mb)
    config = TransferConfig(multipart_threshold=file_size_mb * 2 * MB)
    s3.Bucket(bucket_name).Object(object_key).download_file(
        download_file_path, Config=config, Callback=transfer_callback
    )
    return transfer_callback.thread_info


def download_with_sse(
    bucket_name, object_key, download_file_path, file_size_mb, sse_key
):
    """
    Download a file from an Amazon S3 bucket to a local folder, adding a
    customer-provided encryption key to the request.

    When this kind of encryption is specified, Amazon S3 encrypts the object
    at rest and allows downloads only when the expected encryption key is
    provided in the download request.
    """
    transfer_callback = TransferCallback(file_size_mb)

    if sse_key:
        extra_args = {"SSECustomerAlgorithm": "AES256", "SSECustomerKey": sse_key}
    else:
        extra_args = None
    s3.Bucket(bucket_name).Object(object_key).download_file(
```

```
        download_file_path, ExtraArgs=extra_args, Callback=transfer_callback
    )
    return transfer_callback.thread_info
```

Demonstre as funções do gerenciador de transferências e relate resultados.

```
import hashlib
import os
import platform
import shutil
import time

import boto3
from boto3.s3.transfer import TransferConfig
from botocore.exceptions import ClientError
from botocore.exceptions import ParamValidationError
from botocore.exceptions import NoCredentialsError

import file_transfer

MB = 1024 * 1024
# These configuration attributes affect both uploads and downloads.
CONFIG_ATTRS = (
    "multipart_threshold",
    "multipart_chunksize",
    "max_concurrency",
    "use_threads",
)
# These configuration attributes affect only downloads.
DOWNLOAD_CONFIG_ATTRS = ("max_io_queue", "io_chunksize", "num_download_attempts")


class TransferDemoManager:
    """
    Manages the demonstration. Collects user input from a command line, reports
    transfer results, maintains a list of artifacts created during the
    demonstration, and cleans them up after the demonstration is completed.
    """

    def __init__(self):
```

```
        self._s3 = boto3.resource("s3")
        self._chore_list = []
        self._create_file_cmd = None
        self._size_multiplier = 0
        self.file_size_mb = 30
        self.demo_folder = None
        self.demo_bucket = None
        self._setup_platform_specific()
        self._terminal_width = shutil.get_terminal_size(fallback=(80, 80))[0]

    def collect_user_info(self):
        """
        Collect local folder and Amazon S3 bucket name from the user. These
        locations are used to store files during the demonstration.
        """
        while not self.demo_folder:
            self.demo_folder = input(
                "Which file folder do you want to use to store " "demonstration
files? "
            )
            if not os.path.isdir(self.demo_folder):
                print(f"{self.demo_folder} isn't a folder!")
                self.demo_folder = None

        while not self.demo_bucket:
            self.demo_bucket = input(
                "Which Amazon S3 bucket do you want to use to store "
                "demonstration files? "
            )
            try:
                self._s3.meta.client.head_bucket(Bucket=self.demo_bucket)
            except ParamValidationError as err:
                print(err)
                self.demo_bucket = None
            except ClientError as err:
                print(err)
                print(
                    f"Either {self.demo_bucket} doesn't exist or you don't "
                    f"have access to it."
                )
                self.demo_bucket = None

    def demo(
```

```
        self, question, upload_func, download_func, upload_args=None,
download_args=None
    ):
        """Run a demonstration.

        Ask the user if they want to run this specific demonstration.
        If they say yes, create a file on the local path, upload it
        using the specified upload function, then download it using the
        specified download function.
        """
        if download_args is None:
            download_args = {}
        if upload_args is None:
            upload_args = {}
        question = question.format(self.file_size_mb)
        answer = input(f"{question} (y/n)")
        if answer.lower() == "y":
            local_file_path, object_key, download_file_path =
self._create_demo_file()

            file_transfer.TransferConfig = self._config_wrapper(
                TransferConfig, CONFIG_ATTRS
            )
            self._report_transfer_params(
                "Uploading", local_file_path, object_key, **upload_args
            )
            start_time = time.perf_counter()
            thread_info = upload_func(
                local_file_path,
                self.demo_bucket,
                object_key,
                self.file_size_mb,
                **upload_args,
            )
            end_time = time.perf_counter()
            self._report_transfer_result(thread_info, end_time - start_time)

            file_transfer.TransferConfig = self._config_wrapper(
                TransferConfig, CONFIG_ATTRS + DOWNLOAD_CONFIG_ATTRS
            )
            self._report_transfer_params(
                "Downloading", object_key, download_file_path, **download_args
            )
            start_time = time.perf_counter()
```

```
            thread_info = download_func(
                self.demo_bucket,
                object_key,
                download_file_path,
                self.file_size_mb,
                **download_args,
            )
            end_time = time.perf_counter()
            self._report_transfer_result(thread_info, end_time - start_time)

    def last_name_set(self):
        """Get the name set used for the last demo."""
        return self._chore_list[-1]

    def cleanup(self):
        """
        Remove files from the demo folder, and uploaded objects from the
        Amazon S3 bucket.
        """
        print("-" * self._terminal_width)
        for local_file_path, s3_object_key, downloaded_file_path in
self._chore_list:
            print(f"Removing {local_file_path}")
            try:
                os.remove(local_file_path)
            except FileNotFoundError as err:
                print(err)

            print(f"Removing {downloaded_file_path}")
            try:
                os.remove(downloaded_file_path)
            except FileNotFoundError as err:
                print(err)

            if self.demo_bucket:
                print(f"Removing {self.demo_bucket}:{s3_object_key}")
                try:
                    self._s3.Bucket(self.demo_bucket).Object(s3_object_key).delete()
                except ClientError as err:
                    print(err)

    def _setup_platform_specific(self):
        """Set up platform-specific command used to create a large file."""
        if platform.system() == "Windows":
```

```
            self._create_file_cmd = "fsutil file createnew {} {}"
            self._size_multiplier = MB
        elif platform.system() == "Linux" or platform.system() == "Darwin":
            self._create_file_cmd = f"dd if=/dev/urandom of={{}} " f"bs={MB}
count={{}}"
            self._size_multiplier = 1
        else:
            raise EnvironmentError(
                f"Demo of platform {platform.system()} isn't supported."
            )

    def _create_demo_file(self):
        """
        Create a file in the demo folder specified by the user. Store the local
        path, object name, and download path for later cleanup.

        Only the local file is created by this method. The Amazon S3 object and
        download file are created later during the demonstration.

        Returns:
        A tuple that contains the local file path, object name, and download
        file path.
        """
        file_name_template = "TestFile{}-{}.demo"
        local_suffix = "local"
        object_suffix = "s3object"
        download_suffix = "downloaded"
        file_tag = len(self._chore_list) + 1

        local_file_path = os.path.join(
            self.demo_folder, file_name_template.format(file_tag, local_suffix)
        )

        s3_object_key = file_name_template.format(file_tag, object_suffix)

        downloaded_file_path = os.path.join(
            self.demo_folder, file_name_template.format(file_tag, download_suffix)
        )

        filled_cmd = self._create_file_cmd.format(
            local_file_path, self.file_size_mb * self._size_multiplier
        )

        print(
```

```
            f"Creating file of size {self.file_size_mb} MB "
            f"in {self.demo_folder} by running:"
        )
        print(f"{'':4}{filled_cmd}")
        os.system(filled_cmd)

        chore = (local_file_path, s3_object_key, downloaded_file_path)
        self._chore_list.append(chore)
        return chore

    def _report_transfer_params(self, verb, source_name, dest_name, **kwargs):
        """Report configuration and extra arguments used for a file transfer."""
        print("-" * self._terminal_width)
        print(f"{verb} {source_name} ({self.file_size_mb} MB) to {dest_name}")
        if kwargs:
            print("With extra args:")
            for arg, value in kwargs.items():
                print(f'{"":4}{arg:<20}: {value}')

    @staticmethod
    def ask_user(question):
        """
        Ask the user a yes or no question.

        Returns:
        True when the user answers 'y' or 'Y'; otherwise, False.
        """
        answer = input(f"{question} (y/n) ")
        return answer.lower() == "y"

    @staticmethod
    def _config_wrapper(func, config_attrs):
        def wrapper(*args, **kwargs):
            config = func(*args, **kwargs)
            print("With configuration:")
            for attr in config_attrs:
                print(f'{"":4}{attr:<20}: {getattr(config, attr)}')
            return config

        return wrapper

    @staticmethod
    def _report_transfer_result(thread_info, elapsed):
        """Report the result of a transfer, including per-thread data."""
```

```
        print(f"\nUsed {len(thread_info)} threads.")
        for ident, byte_count in thread_info.items():
            print(f"{'':4}Thread {ident} copied {byte_count} bytes.")
        print(f"Your transfer took {elapsed:.2f} seconds.")


def main():
    """
    Run the demonstration script for s3_file_transfer.
    """
    demo_manager = TransferDemoManager()
    demo_manager.collect_user_info()

    # Upload and download with default configuration. Because the file is 30 MB
    # and the default multipart_threshold is 8 MB, both upload and download are
    # multipart transfers.
    demo_manager.demo(
        "Do you want to upload and download a {} MB file "
        "using the default configuration?",
        file_transfer.upload_with_default_configuration,
        file_transfer.download_with_default_configuration,
    )

    # Upload and download with multipart_threshold set higher than the size of
    # the file. This causes the transfer manager to use standard transfers
    # instead of multipart transfers.
    demo_manager.demo(
        "Do you want to upload and download a {} MB file "
        "as a standard (not multipart) transfer?",
        file_transfer.upload_with_high_threshold,
        file_transfer.download_with_high_threshold,
    )

    # Upload with specific chunk size and additional metadata.
    # Download with a single thread.
    demo_manager.demo(
        "Do you want to upload a {} MB file with a smaller chunk size and "
        "then download the same file using a single thread?",
        file_transfer.upload_with_chunksize_and_meta,
        file_transfer.download_with_single_thread,
        upload_args={
            "metadata": {
                "upload_type": "chunky",
                "favorite_color": "aqua",
```

```
                "size": "medium",
            }
        },
    )

    # Upload using server-side encryption with customer-provided
    # encryption keys.
    # Generate a 256-bit key from a passphrase.
    sse_key = hashlib.sha256("demo_passphrase".encode("utf-8")).digest()
    demo_manager.demo(
        "Do you want to upload and download a {} MB file using "
        "server-side encryption?",
        file_transfer.upload_with_sse,
        file_transfer.download_with_sse,
        upload_args={"sse_key": sse_key},
        download_args={"sse_key": sse_key},
    )

    # Download without specifying an encryption key to show that the
    # encryption key must be included to download an encrypted object.
    if demo_manager.ask_user(
        "Do you want to try to download the encrypted "
        "object without sending the required key?"
    ):
        try:
            _, object_key, download_file_path = demo_manager.last_name_set()
            file_transfer.download_with_default_configuration(
                demo_manager.demo_bucket,
                object_key,
                download_file_path,
                demo_manager.file_size_mb,
            )
        except ClientError as err:
            print(
                "Got expected error when trying to download an encrypted "
                "object without specifying encryption info:"
            )
            print(f"{'':4}{err}")

    # Remove all created and downloaded files, remove all objects from
    # S3 storage.
    if demo_manager.ask_user(
        "Demonstration complete. Do you want to remove local files " "and S3
objects?"
```

```
    ):
        demo_manager.cleanup()


if __name__ == "__main__":
    try:
        main()
    except NoCredentialsError as error:
        print(error)
        print(
            "To run this example, you must have valid credentials in "
            "a shared credential file or set in environment variables."
        )
```

Trabalhar com objetos versionados

O código de exemplo a seguir mostra como:

- Crie um bucket do S3 versionado.
- Obtenha todas as versões de um objeto.
- Reverta um objeto para uma versão anterior.
- Exclua e restaure um objeto versionado.
- Exclua, permanentemente, todas as versões de um objeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie funções que envolvam ações do S3.

```
def create_versioned_bucket(bucket_name, prefix):
    """
    Creates an Amazon S3 bucket, enables it for versioning, and configures a
 lifecycle
```

```
    that expires noncurrent object versions after 7 days.

    Adding a lifecycle configuration to a versioned bucket is a best practice.
    It helps prevent objects in the bucket from accumulating a large number of
    noncurrent versions, which can slow down request performance.

    Usage is shown in the usage_demo_single_object function at the end of this
module.

    :param bucket_name: The name of the bucket to create.
    :param prefix: Identifies which objects are automatically expired under the
                   configured lifecycle rules.
    :return: The newly created bucket.
    """
    try:
        bucket = s3.create_bucket(
            Bucket=bucket_name,
            CreateBucketConfiguration={
                "LocationConstraint": s3.meta.client.meta.region_name
            },
        )
        logger.info("Created bucket %s.", bucket.name)
    except ClientError as error:
        if error.response["Error"]["Code"] == "BucketAlreadyOwnedByYou":
            logger.warning("Bucket %s already exists! Using it.", bucket_name)
            bucket = s3.Bucket(bucket_name)
        else:
            logger.exception("Couldn't create bucket %s.", bucket_name)
            raise

    try:
        bucket.Versioning().enable()
        logger.info("Enabled versioning on bucket %s.", bucket.name)
    except ClientError:
        logger.exception("Couldn't enable versioning on bucket %s.", bucket.name)
        raise

    try:
        expiration = 7
        bucket.LifecycleConfiguration().put(
            LifecycleConfiguration={
                "Rules": [
                    {
                        "Status": "Enabled",
```

```
                        "Prefix": prefix,
                        "NoncurrentVersionExpiration": {"NoncurrentDays":
 expiration},
                    }
                ]
            }
        )
        logger.info(
            "Configured lifecycle to expire noncurrent versions after %s days "
            "on bucket %s.",
            expiration,
            bucket.name,
        )
    except ClientError as error:
        logger.warning(
            "Couldn't configure lifecycle on bucket %s because %s. "
            "Continuing anyway.",
            bucket.name,
            error,
        )

    return bucket



def rollback_object(bucket, object_key, version_id):
    """
    Rolls back an object to an earlier version by deleting all versions that
    occurred after the specified rollback version.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that holds the object to roll back.
    :param object_key: The object to roll back.
    :param version_id: The version ID to roll back to.
    """
    # Versions must be sorted by last_modified date because delete markers are
    # at the end of the list even when they are interspersed in time.
    versions = sorted(
        bucket.object_versions.filter(Prefix=object_key),
        key=attrgetter("last_modified"),
        reverse=True,
    )
```

```
    logger.debug(
        "Got versions:\n%s",
        "\n".join(
            [
                f"\t{version.version_id}, last modified {version.last_modified}"
                for version in versions
            ]
        ),
    )

    if version_id in [ver.version_id for ver in versions]:
        print(f"Rolling back to version {version_id}")
        for version in versions:
            if version.version_id != version_id:
                version.delete()
                print(f"Deleted version {version.version_id}")
            else:
                break

        print(f"Active version is now {bucket.Object(object_key).version_id}")
    else:
        raise KeyError(
            f"{version_id} was not found in the list of versions for "
 f"{object_key}."
        )



def revive_object(bucket, object_key):
    """
    Revives a versioned object that was deleted by removing the object's active
    delete marker.
    A versioned object presents as deleted when its latest version is a delete
 marker.
    By removing the delete marker, we make the previous version the latest version
    and the object then presents as *not* deleted.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to revive.
    """
```

```
    # Get the latest version for the object.
    response = s3.meta.client.list_object_versions(
        Bucket=bucket.name, Prefix=object_key, MaxKeys=1
    )

    if "DeleteMarkers" in response:
        latest_version = response["DeleteMarkers"][0]
        if latest_version["IsLatest"]:
            logger.info(
                "Object %s was indeed deleted on %s. Let's revive it.",
                object_key,
                latest_version["LastModified"],
            )
            obj = bucket.Object(object_key)
            obj.Version(latest_version["VersionId"]).delete()
            logger.info(
                "Revived %s, active version is now %s  with body '%s'",
                object_key,
                obj.version_id,
                obj.get()["Body"].read(),
            )
        else:
            logger.warning(
                "Delete marker is not the latest version for %s!", object_key
            )
    elif "Versions" in response:
        logger.warning("Got an active version for %s, nothing to do.", object_key)
    else:
        logger.error("Couldn't get any version info for %s.", object_key)



def permanently_delete_object(bucket, object_key):
    """
    Permanently deletes a versioned object by deleting all of its versions.

    Usage is shown in the usage_demo_single_object function at the end of this
 module.

    :param bucket: The bucket that contains the object.
    :param object_key: The object to delete.
    """
    try:
        bucket.object_versions.filter(Prefix=object_key).delete()
```

```
        logger.info("Permanently deleted all versions of object %s.", object_key)
    except ClientError:
        logger.exception("Couldn't delete all versions of %s.", object_key)
        raise
```

Carregue uma estrofe de poema para um objeto versionado e realize uma série de ações nela.

```
def usage_demo_single_object(obj_prefix="demo-versioning/"):
    """
    Demonstrates usage of versioned object functions. This demo uploads a stanza
    of a poem and performs a series of revisions, deletions, and revivals on it.

    :param obj_prefix: The prefix to assign to objects created by this demo.
    """
    with open("father_william.txt") as file:
        stanzas = file.read().split("\n\n")

    width = get_terminal_size((80, 20))[0]
    print("-" * width)
    print("Welcome to the usage demonstration of Amazon S3 versioning.")
    print(
        "This demonstration uploads a single stanza of a poem to an Amazon "
        "S3 bucket and then applies various revisions to it."
    )
    print("-" * width)
    print("Creating a version-enabled bucket for the demo...")
    bucket = create_versioned_bucket("bucket-" + str(uuid.uuid1()), obj_prefix)

    print("\nThe initial version of our stanza:")
    print(stanzas[0])

    # Add the first stanza and revise it a few times.
    print("\nApplying some revisions to the stanza...")
    obj_stanza_1 = bucket.Object(f"{obj_prefix}stanza-1")
    obj_stanza_1.put(Body=bytes(stanzas[0], "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0].upper(), "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0].lower(), "utf-8"))
    obj_stanza_1.put(Body=bytes(stanzas[0][::-1], "utf-8"))
    print(
        "The latest version of the stanza is now:",
```

```
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
    )

    # Versions are returned in order, most recent first.
    obj_stanza_1_versions = bucket.object_versions.filter(Prefix=obj_stanza_1.key)
    print(
        "The version data of the stanza revisions:",
        *[
            f"    {version.version_id}, last modified {version.last_modified}"
            for version in obj_stanza_1_versions
        ],
        sep="\n",
    )

    # Rollback two versions.
    print("\nRolling back two versions...")
    rollback_object(bucket, obj_stanza_1.key, list(obj_stanza_1_versions)
[2].version_id)
    print(
        "The latest version of the stanza:",
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
    )

    # Delete the stanza
    print("\nDeleting the stanza...")
    obj_stanza_1.delete()
    try:
        obj_stanza_1.get()
    except ClientError as error:
        if error.response["Error"]["Code"] == "NoSuchKey":
            print("The stanza is now deleted (as expected).")
        else:
            raise

    # Revive the stanza
    print("\nRestoring the stanza...")
    revive_object(bucket, obj_stanza_1.key)
    print(
        "The stanza is restored! The latest version is again:",
        obj_stanza_1.get()["Body"].read().decode("utf-8"),
        sep="\n",
    )
```

```
# Permanently delete all versions of the object. This cannot be undone!
print("\nPermanently deleting all versions of the stanza...")
permanently_delete_object(bucket, obj_stanza_1.key)
obj_stanza_1_versions = bucket.object_versions.filter(Prefix=obj_stanza_1.key)
if len(list(obj_stanza_1_versions)) == 0:
    print("The stanza has been permanently deleted and now has no versions.")
else:
    print("Something went wrong. The stanza still exists!")

print(f"\nRemoving {bucket.name}...")
bucket.delete()
print(f"{bucket.name} deleted.")
print("Demo done!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateBucket
  - DeleteObject
  - ListObjectVersions
  - PutBucketLifecycleConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Python.

```
import json
import urllib.parse
import boto3

print('Loading function')

s3 = boto3.client('s3')


def lambda_handler(event, context):
    #print("Received event: " + json.dumps(event, indent=2))

    # Get the object from the event and show its content type
    bucket = event['Records'][0]['s3']['bucket']['name']
    key = urllib.parse.unquote_plus(event['Records'][0]['s3']['object']['key'],
 encoding='utf-8')
    try:
        response = s3.get_object(Bucket=bucket, Key=key)
        print("CONTENT TYPE: " + response['ContentType'])
        return response['ContentType']
    except Exception as e:
        print(e)
        print('Error getting object {} from bucket {}. Make sure they exist and your
 bucket is in the same region as this function.'.format(key, bucket))
        raise e
```

Exemplos do S3 Glacier usando o SDK para Python (Boto3).

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o S3 Glacier.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um vault

Os exemplos de código a seguir mostram como criar um cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def create_vault(self, vault_name):
        """
        Creates a vault.
```

```
        :param vault_name: The name to give the vault.
        :return: The newly created vault.
        """
        try:
            vault = self.glacier_resource.create_vault(vaultName=vault_name)
            logger.info("Created vault %s.", vault_name)
        except ClientError:
            logger.exception("Couldn't create vault %s.", vault_name)
            raise
        else:
            return vault
```

- Para obter detalhes da API, consulte a CreateVaultReferência da API AWSSDK for Python (Boto3).

Excluir um cofre

O exemplo de código a seguir mostra como excluir um cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def delete_vault(vault):
```

```
        """
        Deletes a vault.

        :param vault: The vault to delete.
        """
        try:
            vault.delete()
            logger.info("Deleted vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't delete vault %s.", vault.name)
            raise
```

- Para obter detalhes da API, consulte a DeleteVaultReferência da API AWSSDK for Python (Boto3).

Excluir um arquivo

Os exemplos de código a seguir mostram como excluir um arquivo do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def delete_archive(archive):
```

```
        """
        Deletes an archive from a vault.

        :param archive: The archive to delete.
        """
        try:
            archive.delete()
            logger.info(
                "Deleted archive %s from vault %s.", archive.id, archive.vault_name
            )
        except ClientError:
            logger.exception("Couldn't delete archive %s.", archive.id)
            raise
```

- Para obter detalhes da API, consulte a DeleteArchiveReferência da API AWSSDK for Python (Boto3).

Excluir notificações do cofre

O exemplo de código a seguir mostra como excluir notificações do cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    @staticmethod
    def stop_notifications(notification):
        """
        Stops notifications to the configured Amazon SNS topic.

        :param notification: The notification configuration to remove.
        """
        try:
            notification.delete()
            logger.info("Notifications stopped.")
        except ClientError:
            logger.exception("Couldn't stop notifications.")
            raise
```

- Para obter detalhes da API, consulte a DeleteVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Descrever um trabalho

O exemplo de código a seguir mostra como descrever um trabalho do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    @staticmethod
    def get_job_status(job):
        """
        Gets the status of a job.

        :param job: The job to query.
        :return: The current status of the job.
        """
        try:
            job.load()
            logger.info(
                "Job %s is performing action %s and has status %s.",
                job.id,
                job.action,
                job.status_code,
            )
        except ClientError:
            logger.exception("Couldn't get status for job %s.", job.id)
            raise
        else:
            return job.status_code
```

- Para obter detalhes da API, consulte a DescribeJobReferência da API AWSSDK for Python (Boto3).

Obter saída de trabalho

O exemplo de código a seguir mostra como obter uma saída de trabalho do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
```

```
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def get_job_output(job):
        """
        Gets the output of a job, such as a vault inventory or the contents of an
        archive.

        :param job: The job to get output from.
        :return: The job output, in bytes.
        """
        try:
            response = job.get_output()
            out_bytes = response["body"].read()
            logger.info("Read %s bytes from job %s.", len(out_bytes), job.id)
            if "archiveDescription" in response:
                logger.info(
                    "These bytes are described as '%s'",
response["archiveDescription"]
                )
        except ClientError:
            logger.exception("Couldn't get output for job %s.", job.id)
            raise
        else:
            return out_bytes
```

- Para obter detalhes da API, consulte a GetJobOutputReferência da API AWSSDK for Python (Boto3).

Obter configuração de notificação do cofre

O exemplo de código a seguir mostra como obter a configuração de notificação do cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def get_notification(vault):
        """
        Gets the currently notification configuration for a vault.

        :param vault: The vault to query.
        :return: The notification configuration for the specified vault.
        """
        try:
            notification = vault.Notification()
            logger.info(
                "Vault %s notifies %s on %s events.",
                vault.name,
                notification.sns_topic,
                notification.events,
            )
        except ClientError:
            logger.exception("Couldn't get notification data for %s.", vault.name)
            raise
        else:
            return notification
```

- Para obter detalhes da API, consulte a GetVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Listar trabalhos

O exemplo de código a seguir mostra como listar trabalhos do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
```

```
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type, vault.name)
            raise
        else:
            return job_list
```

- Para obter detalhes da API, consulte a ListJobsReferência da API AWSSDK for Python (Boto3).

Liste cofres

O exemplo de código a seguir mostra como listar cofres do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    def list_vaults(self):
        """
        Lists vaults for the current account.
        """
        try:
            for vault in self.glacier_resource.vaults.all():
                logger.info("Got vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't list vaults.")
            raise
```

- Para obter detalhes da API, consulte a ListVaultsReferência da API AWSSDK for Python (Boto3).

Recuperar um inventário do cofre

O exemplo de código a seguir mostra como recuperar um inventário de cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def initiate_inventory_retrieval(vault):
        """
        Initiates an inventory retrieval job. The inventory describes the contents
```

```
        of the vault. Standard retrievals typically complete within 3–5 hours.
        When the job completes, you can get the inventory by calling get_output().

        :param vault: The vault to inventory.
        :return: The inventory retrieval job.
        """
        try:
            job = vault.initiate_inventory_retrieval()
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
            logger.exception("Couldn't start job on vault %s.", vault.name)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a InitiateJobReferência da API AWSSDK for Python (Boto3).

Recuperar um arquivo de um cofre

O exemplo de código a seguir mostra como recuperar um arquivo de um cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource
```

```
    @staticmethod
    def initiate_archive_retrieval(archive):
        """
        Initiates an archive retrieval job. Standard retrievals typically complete
        within 3–5 hours. When the job completes, you can get the archive contents
        by calling get_output().

        :param archive: The archive to retrieve.
        :return: The archive retrieval job.
        """
        try:
            job = archive.initiate_archive_retrieval()
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
            logger.exception("Couldn't start job on archive %s.", archive.id)
            raise
        else:
            return job
```

- Para obter detalhes da API, consulte a InitiateJobReferência da API AWSSDK for Python (Boto3).

Configurar notificações do cofre

O exemplo de código a seguir mostra como definir notificações do cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
```

```
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def set_notifications(self, vault, sns_topic_arn):
        """
        Sets an Amazon Simple Notification Service (Amazon SNS) topic as a target
        for notifications. Amazon S3 Glacier publishes messages to this topic for
        the configured list of events.

        :param vault: The vault to set up to publish notifications.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of the topic that
                              receives notifications.
        :return: Data about the new notification configuration.
        """
        try:
            notification = self.glacier_resource.Notification("-", vault.name)
            notification.set(
                vaultNotificationConfig={
                    "SNSTopic": sns_topic_arn,
                    "Events": [
                        "ArchiveRetrievalCompleted",
                        "InventoryRetrievalCompleted",
                    ],
                }
            )
            logger.info(
                "Notifications will be sent to %s for events %s from %s.",
                notification.sns_topic,
                notification.events,
                notification.vault_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't set notifications to %s on %s.", sns_topic_arn, vault.name
            )
            raise
        else:
            return notification
```

- Para obter detalhes da API, consulte a SetVaultNotificationsReferência da API AWSSDK for Python (Boto3).

Baixe um arquivo em um cofre

O exemplo de código a seguir mostra como fazer upload de um arquivo em um cofre do Amazon S3 Glacier.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def upload_archive(vault, archive_description, archive_file):
        """
        Uploads an archive to a vault.

        :param vault: The vault where the archive is put.
        :param archive_description: A description of the archive.
        :param archive_file: The archive file to put in the vault.
        :return: The uploaded archive.
        """
        try:
            archive = vault.upload_archive(
                archiveDescription=archive_description, body=archive_file
            )
            logger.info(
```

```
                "Uploaded %s with ID %s to vault %s.",
                archive_description,
                archive.id,
                vault.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload %s to %s.", archive_description, vault.name
            )
            raise
        else:
            return archive
```

- Para obter detalhes da API, consulte a UploadArchiveReferência da API AWSSDK for Python (Boto3).

Cenários

Guardar um arquivo, receber notificações e iniciar um trabalho

O código de exemplo a seguir mostra como:

- Criar um cofre do Amazon S3 Glacier.
- Configurar o cofre para publicar notificações em um tópico do Amazon SNS.
- Carregar um arquivo no cofre.
- Inicie um trabalho de recuperação de arquivo.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as operações do S3 Glacier.

```
import argparse
```

```
import logging
import os
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    def create_vault(self, vault_name):
        """
        Creates a vault.

        :param vault_name: The name to give the vault.
        :return: The newly created vault.
        """
        try:
            vault = self.glacier_resource.create_vault(vaultName=vault_name)
            logger.info("Created vault %s.", vault_name)
        except ClientError:
            logger.exception("Couldn't create vault %s.", vault_name)
            raise
        else:
            return vault


    def list_vaults(self):
        """
        Lists vaults for the current account.
        """
        try:
            for vault in self.glacier_resource.vaults.all():
                logger.info("Got vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't list vaults.")
```

```
            raise


    @staticmethod
    def upload_archive(vault, archive_description, archive_file):
        """
        Uploads an archive to a vault.

        :param vault: The vault where the archive is put.
        :param archive_description: A description of the archive.
        :param archive_file: The archive file to put in the vault.
        :return: The uploaded archive.
        """
        try:
            archive = vault.upload_archive(
                archiveDescription=archive_description, body=archive_file
            )
            logger.info(
                "Uploaded %s with ID %s to vault %s.",
                archive_description,
                archive.id,
                vault.name,
            )
        except ClientError:
            logger.exception(
                "Couldn't upload %s to %s.", archive_description, vault.name
            )
            raise
        else:
            return archive


    @staticmethod
    def initiate_archive_retrieval(archive):
        """
        Initiates an archive retrieval job. Standard retrievals typically complete
        within 3-5 hours. When the job completes, you can get the archive contents
        by calling get_output().

        :param archive: The archive to retrieve.
        :return: The archive retrieval job.
        """
        try:
            job = archive.initiate_archive_retrieval()
```

```
            logger.info("Started %s job with ID %s.", job.action, job.id)
        except ClientError:
            logger.exception("Couldn't start job on archive %s.", archive.id)
            raise
        else:
            return job


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type, vault.name)
            raise
        else:
            return job_list


    def set_notifications(self, vault, sns_topic_arn):
        """
```

```
        Sets an Amazon Simple Notification Service (Amazon SNS) topic as a target
        for notifications. Amazon S3 Glacier publishes messages to this topic for
        the configured list of events.

        :param vault: The vault to set up to publish notifications.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of the topic that
                              receives notifications.
        :return: Data about the new notification configuration.
        """
        try:
            notification = self.glacier_resource.Notification("-", vault.name)
            notification.set(
                vaultNotificationConfig={
                    "SNSTopic": sns_topic_arn,
                    "Events": [
                        "ArchiveRetrievalCompleted",
                        "InventoryRetrievalCompleted",
                    ],
                }
            )
            logger.info(
                "Notifications will be sent to %s for events %s from %s.",
                notification.sns_topic,
                notification.events,
                notification.vault_name,
            )
        except ClientError:
            logger.exception(
                "Couldn't set notifications to %s on %s.", sns_topic_arn, vault.name
            )
            raise
        else:
            return notification
```

Chame funções na classe wrapper para criar um cofre e carregar um arquivo, depois configure o cofre para publicar notificações e iniciar um trabalho para recuperar o arquivo.

```
def upload_demo(glacier, vault_name, topic_arn):
    """
    Shows how to:
    * Create a vault.
```

```
    * Configure the vault to publish notifications to an Amazon SNS topic.
    * Upload an archive.
    * Start a job to retrieve the archive.

    :param glacier: A Boto3 Amazon S3 Glacier resource.
    :param vault_name: The name of the vault to create.
    :param topic_arn: The ARN of an Amazon SNS topic that receives notification of
                      Amazon S3 Glacier events.
    """
    print(f"\nCreating vault {vault_name}.")
    vault = glacier.create_vault(vault_name)
    print("\nList of vaults in your account:")
    glacier.list_vaults()
    print(f"\nUploading glacier_basics.py to {vault.name}.")
    with open("glacier_basics.py", "rb") as upload_file:
        archive = glacier.upload_archive(vault, "glacier_basics.py", upload_file)
    print(
        "\nStarting an archive retrieval request to get the file back from the "
        "vault."
    )
    glacier.initiate_archive_retrieval(archive)
    print("\nListing in progress jobs:")
    glacier.list_jobs(vault, "in_progress")
    print(
        "\nBecause Amazon S3 Glacier is intended for infrequent retrieval, an "
        "archive request with Standard retrieval typically completes within 3-5 "
        "hours."
    )
    if topic_arn:
        notification = glacier.set_notifications(vault, topic_arn)
        print(
            f"\nVault {vault.name} is configured to notify the "
            f"{notification.sns_topic} topic when {notification.events} "
            f"events occur. You can subscribe to this topic to receive "
            f"a message when the archive retrieval completes.\n"
        )
    else:
        print(
            f"\nVault {vault.name} is not configured to notify an Amazon SNS topic "
            f"when the archive retrieval completes so wait a few hours."
        )
    print("\nRetrieve your job output by running this script with the --retrieve
flag.")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateVault
  - InitiateJob
  - ListJobs
  - ListVaults
  - SetVaultNotifications
  - UploadArchive

Obtenha o conteúdo do arquivo e exclua o arquivo

O código de exemplo a seguir mostra como:

- Liste trabalhos para um cofre do Amazon S3 Glacier e obtenha o status do trabalho.
- Obtenha a saída de um trabalho de recuperação de arquivo concluído.
- Exclua um arquivo.
- Excluir um cofre.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que envolva as operações do S3 Glacier.

```
import argparse
import logging
import os
import boto3
from botocore.exceptions import ClientError
```

```
logger = logging.getLogger(__name__)


class GlacierWrapper:
    """Encapsulates Amazon S3 Glacier API operations."""

    def __init__(self, glacier_resource):
        """
        :param glacier_resource: A Boto3 Amazon S3 Glacier resource.
        """
        self.glacier_resource = glacier_resource


    @staticmethod
    def list_jobs(vault, job_type):
        """
        Lists jobs by type for the specified vault.

        :param vault: The vault to query.
        :param job_type: The type of job to list.
        :return: The list of jobs of the requested type.
        """
        job_list = []
        try:
            if job_type == "all":
                jobs = vault.jobs.all()
            elif job_type == "in_progress":
                jobs = vault.jobs_in_progress.all()
            elif job_type == "completed":
                jobs = vault.completed_jobs.all()
            elif job_type == "succeeded":
                jobs = vault.succeeded_jobs.all()
            elif job_type == "failed":
                jobs = vault.failed_jobs.all()
            else:
                jobs = []
                logger.warning("%s isn't a type of job I can get.", job_type)
            for job in jobs:
                job_list.append(job)
                logger.info("Got %s %s job %s.", job_type, job.action, job.id)
        except ClientError:
            logger.exception("Couldn't get %s jobs from %s.", job_type, vault.name)
            raise
        else:
```

```
            return job_list


    @staticmethod
    def get_job_output(job):
        """
        Gets the output of a job, such as a vault inventory or the contents of an
        archive.

        :param job: The job to get output from.
        :return: The job output, in bytes.
        """
        try:
            response = job.get_output()
            out_bytes = response["body"].read()
            logger.info("Read %s bytes from job %s.", len(out_bytes), job.id)
            if "archiveDescription" in response:
                logger.info(
                    "These bytes are described as '%s'",
response["archiveDescription"]
                )
        except ClientError:
            logger.exception("Couldn't get output for job %s.", job.id)
            raise
        else:
            return out_bytes


    @staticmethod
    def delete_archive(archive):
        """
        Deletes an archive from a vault.

        :param archive: The archive to delete.
        """
        try:
            archive.delete()
            logger.info(
                "Deleted archive %s from vault %s.", archive.id, archive.vault_name
            )
        except ClientError:
            logger.exception("Couldn't delete archive %s.", archive.id)
            raise
```

```
    @staticmethod
    def delete_vault(vault):
        """
        Deletes a vault.

        :param vault: The vault to delete.
        """
        try:
            vault.delete()
            logger.info("Deleted vault %s.", vault.name)
        except ClientError:
            logger.exception("Couldn't delete vault %s.", vault.name)
            raise
```

Chame funções na classe wrapper para obter o conteúdo de arquivo de um trabalho concluído e, em seguida, exclua o arquivo.

```
def retrieve_demo(glacier, vault_name):
    """
    Shows how to:
    * List jobs for a vault and get job status.
    * Get the output of a completed archive retrieval job.
    * Delete an archive.
    * Delete a vault.

    :param glacier: A Boto3 Amazon S3 Glacier resource.
    :param vault_name: The name of the vault to query for jobs.
    """
    vault = glacier.glacier_resource.Vault("-", vault_name)
    try:
        vault.load()
    except ClientError as err:
        if err.response["Error"]["Code"] == "ResourceNotFoundException":
            print(
                f"\nVault {vault_name} doesn't exist. You must first run this script
 "
                f"with the --upload flag to create the vault."
            )
            return
        else:
```

```
            raise

    print(f"\nGetting completed jobs for {vault.name}.")
    jobs = glacier.list_jobs(vault, "completed")
    if not jobs:
        print("\nNo completed jobs found. Give it some time and try again later.")
        return

    retrieval_job = None
    for job in jobs:
        if job.action == "ArchiveRetrieval" and job.status_code == "Succeeded":
            retrieval_job = job
            break
    if retrieval_job is None:
        print(
            "\nNo ArchiveRetrieval jobs found. Give it some time and try again "
            "later."
        )
        return

    print(f"\nGetting output from job {retrieval_job.id}.")
    archive_bytes = glacier.get_job_output(retrieval_job)
    archive_str = archive_bytes.decode("utf-8")
    print("\nGot archive data. Printing the first 10 lines.")
    print(os.linesep.join(archive_str.split(os.linesep)[:10]))

    print(f"\nDeleting the archive from {vault.name}.")
    archive = glacier.glacier_resource.Archive(
        "-", vault.name, retrieval_job.archive_id
    )
    glacier.delete_archive(archive)

    print(f"\nDeleting {vault.name}.")
    glacier.delete_vault(vault)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - DeleteArchive
  - DeleteVault

- GetJobOutput
- ListJobs

Exemplos do Secrets Manager usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter um lote de valores de segredo

O exemplo de código a seguir mostra como obter um lote de valores de segredo do Secrets Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class BatchGetSecretsWrapper:
    def __init__(self, secretsmanager_client):
```

```
        self.client = secretsmanager_client


    def batch_get_secrets(self, filter_name):
        """
        Retrieve multiple secrets from AWS Secrets Manager using the
batch_get_secret_value API.
        This function assumes the stack mentioned in the source code README has been
successfully deployed.
        This stack includes 7 secrets, all of which have names beginning with
"mySecret".

        :param filter_name: The full or partial name of secrets to be fetched.
        :type filter_name: str
        """
        try:
            secrets = []
            response = self.client.batch_get_secret_value(
                Filters=[{"Key": "name", "Values": [f"{filter_name}"]}]
            )
            for secret in response["SecretValues"]:
                secrets.append(json.loads(secret["SecretString"]))
            if secrets:
                logger.info("Secrets retrieved successfully.")
            else:
                logger.info("Zero secrets returned without error.")
            return secrets
        except self.client.exceptions.ResourceNotFoundException:
            msg = f"One or more requested secrets were not found with filter:
{filter_name}"
            logger.info(msg)
            return msg
        except Exception as e:
            logger.error(f"An unknown error occurred:\n{str(e)}.")
            raise
```

- Para obter detalhes da API, consulte a BatchGetSecretValueReferência da API AWSSDK for Python (Boto3).

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class GetSecretWrapper:
    def __init__(self, secretsmanager_client):
        self.client = secretsmanager_client


    def get_secret(self, secret_name):
        """
        Retrieve individual secrets from AWS Secrets Manager using the
 get_secret_value API.
        This function assumes the stack mentioned in the source code README has been
 successfully deployed.
        This stack includes 7 secrets, all of which have names beginning with
 "mySecret".

        :param secret_name: The name of the secret fetched.
        :type secret_name: str
        """
        try:
            get_secret_value_response = self.client.get_secret_value(
                SecretId=secret_name
            )
            logging.info("Secret retrieved successfully.")
            return get_secret_value_response["SecretString"]
        except self.client.exceptions.ResourceNotFoundException:
            msg = f"The requested secret {secret_name} was not found."
            logger.info(msg)
            return msg
        except Exception as e:
            logger.error(f"An unknown error occurred: {str(e)}.")
            raise
```

- Para obter detalhes da API, consulte a GetSecretValueReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon SES usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um filtro de recebimento

O exemplo de código a seguir mostra como criar um filtro de recebimento do Amazon SES que bloqueia e-mails recebidos de um endereço IP ou de um intervalo de endereços IP.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_receipt_filter(self, filter_name, ip_address_or_range, allow):
        """
        Creates a filter that allows or blocks incoming mail from an IP address or
        range.

        :param filter_name: The name to give the filter.
        :param ip_address_or_range: The IP address or range to block or allow.
        :param allow: When True, incoming mail is allowed from the specified IP
                      address or range; otherwise, it is blocked.
        """
        try:
            policy = "Allow" if allow else "Block"
            self.ses_client.create_receipt_filter(
                Filter={
                    "Name": filter_name,
                    "IpFilter": {"Cidr": ip_address_or_range, "Policy": policy},
                }
            )
            logger.info(
                "Created receipt filter %s to %s IP of %s.",
                filter_name,
                policy,
                ip_address_or_range,
            )
        except ClientError:
            logger.exception("Couldn't create receipt filter %s.", filter_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptFilterReferência da API AWSSDK for Python (Boto3).

Criar uma regra de recebimento

O exemplo de código a seguir mostra como criar uma regra de recebimento do Amazon SES.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um bucket do Amazon S3 no qual o Amazon SES possa colocar cópias de e-mails recebidos e crie uma regra que copia para o bucket os e-mails recebidos de uma lista específica de destinatários.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_bucket_for_copy(self, bucket_name):
        """
        Creates a bucket that can receive copies of emails from Amazon SES. This
        includes adding a policy to the bucket that grants Amazon SES permission
        to put objects in the bucket.

        :param bucket_name: The name of the bucket to create.
        :return: The newly created bucket.
        """
        allow_ses_put_policy = {
```

```
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Sid": "AllowSESPut",
                    "Effect": "Allow",
                    "Principal": {"Service": "ses.amazonaws.com"},
                    "Action": "s3:PutObject",
                    "Resource": f"arn:aws:s3:::{bucket_name}/*",
                }
            ],
        }
        bucket = None
        try:
            bucket = self.s3_resource.create_bucket(
                Bucket=bucket_name,
                CreateBucketConfiguration={
                    "LocationConstraint":
self.s3_resource.meta.client.meta.region_name
                },
            )
            bucket.wait_until_exists()
            bucket.Policy().put(Policy=json.dumps(allow_ses_put_policy))
            logger.info("Created bucket %s to receive copies of emails.",
bucket_name)
        except ClientError:
            logger.exception("Couldn't create bucket to receive copies of emails.")
            if bucket is not None:
                bucket.delete()
            raise
        else:
            return bucket


    def create_s3_copy_rule(
        self, rule_set_name, rule_name, recipients, bucket_name, prefix
    ):
        """
        Creates a rule so that all emails received by the specified recipients are
        copied to an Amazon S3 bucket.

        :param rule_set_name: The name of a previously created rule set to contain
                              this rule.
        :param rule_name: The name to give the rule.
        :param recipients: When an email is received by one of these recipients, it
```

```
                        is copied to the Amazon S3 bucket.
        :param bucket_name: The name of the bucket to receive email copies. This
                            bucket must allow Amazon SES to put objects into it.
        :param prefix: An object key prefix to give the emails copied to the bucket.
        """
        try:
            self.ses_client.create_receipt_rule(
                RuleSetName=rule_set_name,
                Rule={
                    "Name": rule_name,
                    "Enabled": True,
                    "Recipients": recipients,
                    "Actions": [
                        {
                            "S3Action": {
                                "BucketName": bucket_name,
                                "ObjectKeyPrefix": prefix,
                            }
                        }
                    ],
                },
            )
            logger.info(
                "Created rule %s to copy mail received by %s to bucket %s.",
                rule_name,
                recipients,
                bucket_name,
            )
        except ClientError:
            logger.exception("Couldn't create rule %s.", rule_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptRuleReferência da API AWSSDK for Python (Boto3).

Criar um conjunto de regras de recebimento

O exemplo de código a seguir mostra como criar um conjunto de regras de recebimento do Amazon SES para organizar as regras aplicadas aos e-mails recebidos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def create_receipt_rule_set(self, rule_set_name):
        """
        Creates an empty rule set. Rule sets contain individual rules and can be
        used to organize rules.

        :param rule_set_name: The name to give the rule set.
        """
        try:
            self.ses_client.create_receipt_rule_set(RuleSetName=rule_set_name)
            logger.info("Created receipt rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't create receipt rule set %s.", rule_set_name)
            raise
```

- Para obter detalhes da API, consulte a CreateReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Criar um modelo de e-mail

O exemplo de código a seguir mostra como criar um modelo de e-mail do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def create_template(self, name, subject, text, html):
        """
        Creates an email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
```

```
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.create_template(Template=template)
            logger.info("Created template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't create template %s.", name)
            raise
```

- Para obter detalhes da API, consulte a CreateTemplateReferência da API AWSSDK for Python (Boto3).

Excluir um filtro de recebimento

O exemplo de código a seguir mostra como excluir um filtro de recebimento do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
```

```
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_filter(self, filter_name):
        """
        Deletes a receipt filter.

        :param filter_name: The name of the filter to delete.
        """
        try:
            self.ses_client.delete_receipt_filter(FilterName=filter_name)
            logger.info("Deleted receipt filter %s.", filter_name)
        except ClientError:
            logger.exception("Couldn't delete receipt filter %s.", filter_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptFilterReferência da API AWSSDK for Python (Boto3).

Excluir uma regra de recebimento

O exemplo de código a seguir mostra como excluir uma regra de recebimento do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
```

```
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_rule(self, rule_set_name, rule_name):
        """
        Deletes a rule.

        :param rule_set_name: The rule set that contains the rule to delete.
        :param rule_name: The rule to delete.
        """
        try:
            self.ses_client.delete_receipt_rule(
                RuleSetName=rule_set_name, RuleName=rule_name
            )
            logger.info("Removed rule %s from rule set %s.", rule_name,
rule_set_name)
        except ClientError:
            logger.exception(
                "Couldn't remove rule %s from rule set %s.", rule_name,
rule_set_name
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptRuleReferência da API AWSSDK for Python (Boto3).

Excluir um conjunto de regras

O exemplo de código a seguir mostra como excluir um conjunto de regras do Amazon SES e todas as regras contidas nesse conjunto.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def delete_receipt_rule_set(self, rule_set_name):
        """
        Deletes a rule set. When a rule set is deleted, all of the rules it contains
        are also deleted.

        :param rule_set_name: The name of the rule set to delete.
        """
        try:
            self.ses_client.delete_receipt_rule_set(RuleSetName=rule_set_name)
            logger.info("Deleted rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't delete rule set %s.", rule_set_name)
            raise
```

- Para obter detalhes da API, consulte a DeleteReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Excluir um modelo de e-mail

O exemplo de código a seguir mostra como excluir um modelo de e-mail do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def delete_template(self):
        """
        Deletes an email template.
        """
        try:

 self.ses_client.delete_template(TemplateName=self.template["TemplateName"])
            logger.info("Deleted template %s.", self.template["TemplateName"])
            self.template = None
            self.template_tags = None
        except ClientError:
```

```
            logger.exception(
                "Couldn't delete template %s.", self.template["TemplateName"]
            )
            raise
```

- Para obter detalhes da API, consulte a DeleteTemplateReferência da API AWSSDK for Python (Boto3).

Excluir uma identidade

O exemplo de código a seguir mostra como excluir uma identidade do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def delete_identity(self, identity):
        """
        Deletes an identity.

        :param identity: The identity to remove.
        """
        try:
            self.ses_client.delete_identity(Identity=identity)
            logger.info("Deleted identity %s.", identity)
```

```
        except ClientError:
            logger.exception("Couldn't delete identity %s.", identity)
            raise
```

- Para obter detalhes da API, consulte a DeleteIdentityReferência da API AWSSDK for Python (Boto3).

Descrever um conjunto de regras de recebimento

O exemplo de código a seguir mostra como descrever um conjunto de regras de recebimento do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def describe_receipt_rule_set(self, rule_set_name):
        """
        Gets data about a rule set.

        :param rule_set_name: The name of the rule set to retrieve.
        :return: Data about the rule set.
        """
```

```
        try:
            response = self.ses_client.describe_receipt_rule_set(
                RuleSetName=rule_set_name
            )
            logger.info("Got data for rule set %s.", rule_set_name)
        except ClientError:
            logger.exception("Couldn't get data for rule set %s.", rule_set_name)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeReceiptRuleSetReferência da API AWSSDK for Python (Boto3).

Obter um modelo existente de e-mail

O exemplo de código a seguir mostra como obter um modelo existente de e-mail do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
```

```
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def get_template(self, name):
        """
        Gets a previously created email template.

        :param name: The name of the template to retrieve.
        :return: The retrieved email template.
        """
        try:
            response = self.ses_client.get_template(TemplateName=name)
            self.template = response["Template"]
            logger.info("Got template %s.", name)
            self._extract_tags(
                self.template["SubjectPart"],
                self.template["TextPart"],
                self.template["HtmlPart"],
            )
        except ClientError:
            logger.exception("Couldn't get template %s.", name)
            raise
        else:
            return self.template
```

- Para obter detalhes da API, consulte a GetTemplateReferência da API AWSSDK for Python (Boto3).

Obter o status de uma identidade

O exemplo de código a seguir mostra como excluir o status de uma identidade do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def get_identity_status(self, identity):
        """
        Gets the status of an identity. This can be used to discover whether
        an identity has been successfully verified.

        :param identity: The identity to query.
        :return: The status of the identity.
        """
        try:
            response = self.ses_client.get_identity_verification_attributes(
                Identities=[identity]
            )
            status = response["VerificationAttributes"].get(
                identity, {"VerificationStatus": "NotFound"}
            )["VerificationStatus"]
            logger.info("Got status of %s for %s.", status, identity)
        except ClientError:
            logger.exception("Couldn't get status for %s.", identity)
            raise
        else:
            return status
```

- Para obter detalhes da API, consulte a GetIdentityVerificationAttributesReferência da API AWSSDK for Python (Boto3).

Listar modelos de e-mail

O exemplo de código a seguir mostra como lista modelos existentes de e-mail do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def list_templates(self):
        """
        Gets a list of all email templates for the current account.
```

```
        :return: The list of retrieved email templates.
        """
        try:
            response = self.ses_client.list_templates()
            templates = response["TemplatesMetadata"]
            logger.info("Got %s templates.", len(templates))
        except ClientError:
            logger.exception("Couldn't get templates.")
            raise
        else:
            return templates
```

- Para obter detalhes da API, consulte a ListTemplatesReferência da API AWSSDK for Python (Boto3).

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def list_identities(self, identity_type, max_items):
        """
        Gets the identities of the specified type for the current account.
```

```
        :param identity_type: The type of identity to retrieve, such as
EmailAddress.
        :param max_items: The maximum number of identities to retrieve.
        :return: The list of retrieved identities.
        """
        try:
            response = self.ses_client.list_identities(
                IdentityType=identity_type, MaxItems=max_items
            )
            identities = response["Identities"]
            logger.info("Got %s identities for the current account.",
len(identities))
        except ClientError:
            logger.exception("Couldn't list identities for the current account.")
            raise
        else:
            return identities
```

- Para obter detalhes da API, consulte a ListIdentitiesReferência da API AWSSDK for Python (Boto3).

Listar filtros de recebimento

O exemplo de código a seguir mostra como listar filtros de recebimento do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesReceiptHandler:
    """Encapsulates Amazon SES receipt handling functions."""

    def __init__(self, ses_client, s3_resource):
        """
```

```
        :param ses_client: A Boto3 Amazon SES client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        """
        self.ses_client = ses_client
        self.s3_resource = s3_resource


    def list_receipt_filters(self):
        """
        Gets the list of receipt filters for the current account.

        :return: The list of receipt filters.
        """
        try:
            response = self.ses_client.list_receipt_filters()
            filters = response["Filters"]
            logger.info("Got %s receipt filters.", len(filters))
        except ClientError:
            logger.exception("Couldn't get receipt filters.")
            raise
        else:
            return filters
```

- Para obter detalhes da API, consulte a ListReceiptFiltersReferência da API AWSSDK for Python (Boto3).

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""
```

```
    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_email(self, source, destination, subject, text, html, reply_tos=None):
        """
        Sends an email.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param subject: The subject of the email.
        :param text: The plain text version of the body of the email.
        :param html: The HTML version of the body of the email.
        :param reply_tos: Email accounts that will receive a reply if the recipient
                          replies to the message.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Message": {
                "Subject": {"Data": subject},
                "Body": {"Text": {"Data": text}, "Html": {"Data": html}},
            },
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent mail %s from %s to %s.", message_id, source, destination.tos
            )
        except ClientError:
            logger.exception(
                "Couldn't send mail from %s to %s.", source, destination.tos
            )
```

```
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte a SendEmailReferência da API AWSSDK for Python (Boto3).

Enviar e-mails com base em modelo

O exemplo de código a seguir mostra como enviar e-mails com base em modelo com o Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_templated_email(
        self, source, destination, template_name, template_data, reply_tos=None
    ):
        """
        Sends an email based on a template. A template contains replaceable tags
        each enclosed in two curly braces, such as {{name}}. The template data
 passed
        in this function contains key-value pairs that define the values to insert
        in place of the template tags.
```

```
        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param template_name: The name of a previously created template.
        :param template_data: JSON-formatted key-value pairs of replacement values
                              that are inserted in the template before it is sent.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Template": template_name,
            "TemplateData": json.dumps(template_data),
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_templated_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent templated mail %s from %s to %s.",
                message_id,
                source,
                destination.tos,
            )
        except ClientError:
            logger.exception(
                "Couldn't send templated mail from %s to %s.", source,
destination.tos
            )
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte a SendTemplatedEmailReferência da API AWSSDK for Python (Boto3).

Atualizar um modelo de e-mail

O exemplo de código a seguir mostra como atualizar um modelo de e-mail do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def update_template(self, name, subject, text, html):
        """
        Updates a previously created email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
```

```
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.update_template(Template=template)
            logger.info("Updated template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't update template %s.", name)
            raise
```

- Para obter detalhes da API, consulte a UpdateTemplateReferência da API AWSSDK for Python (Boto3).

Verificar uma identidade de domínio

O exemplo de código a seguir mostra como verificar uma identidade de domínio com o Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
```

```
        self.ses_client = ses_client


    def verify_domain_identity(self, domain_name):
        """
        Starts verification of a domain identity. To complete verification, you must
        create a TXT record with a specific format through your DNS provider.

        For more information, see *Verifying a domain with Amazon SES* in the
        Amazon SES documentation:
            https://docs.aws.amazon.com/ses/latest/DeveloperGuide/verify-domain-
procedure.html

        :param domain_name: The name of the domain to verify.
        :return: The token to include in the TXT record with your DNS provider.
        """
        try:
            response = self.ses_client.verify_domain_identity(Domain=domain_name)
            token = response["VerificationToken"]
            logger.info("Got domain verification token for %s.", domain_name)
        except ClientError:
            logger.exception("Couldn't verify domain %s.", domain_name)
            raise
        else:
            return token
```

- Para obter detalhes da API, consulte a VerifyDomainIdentityReferência da API AWSSDK for Python (Boto3).

Verificar uma identidade de e-mail

O exemplo de código a seguir mostra como verificar uma identidade de e-mail com o Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def verify_email_identity(self, email_address):
        """
        Starts verification of an email identity. This function causes an email
        to be sent to the specified email address from Amazon SES. To complete
        verification, follow the instructions in the email.

        :param email_address: The email address to verify.
        """
        try:
            self.ses_client.verify_email_identity(EmailAddress=email_address)
            logger.info("Started verification of %s.", email_address)
        except ClientError:
            logger.exception("Couldn't start verification of %s.", email_address)
            raise
```

- Para obter detalhes da API, consulte a VerifyEmailIdentityReferência da API AWSSDK for Python (Boto3).

Cenários

Copiar identidades de domínio e e-mail entre regiões

O exemplo de código a seguir mostra como copiar as identidades de domínio e e-mail do Amazon SES de uma região da AWS para outra. Quando as identidades de domínio são gerenciadas pelo Route 53, os registros de verificação são copiados para o domínio da região de destino.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import argparse
import json
import logging
from pprint import pprint
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def get_identities(ses_client):
    """
    Gets the identities for the current Region. The Region is specified in the
    Boto3 Amazon SES client object.

    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of email identities and the list of domain identities.
    """
    email_identities = []
    domain_identities = []
    try:
        identity_paginator = ses_client.get_paginator("list_identities")
        identity_iterator = identity_paginator.paginate(
            PaginationConfig={"PageSize": 20}
        )
        for identity_page in identity_iterator:
            for identity in identity_page["Identities"]:
                if "@" in identity:
                    email_identities.append(identity)
                else:
                    domain_identities.append(identity)
        logger.info(
            "Found %s email and %s domain identities.",
            len(email_identities),
```

```
            len(domain_identities),
        )
    except ClientError:
        logger.exception("Couldn't get identities.")
        raise
    else:
        return email_identities, domain_identities


def verify_emails(email_list, ses_client):
    """
    Starts verification of a list of email addresses. Verification causes an email
    to be sent to each address. To complete verification, the recipient must follow
    the instructions in the email.

    :param email_list: The list of email addresses to verify.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of emails that were successfully submitted for verification.
    """
    verified_emails = []
    for email in email_list:
        try:
            ses_client.verify_email_identity(EmailAddress=email)
            verified_emails.append(email)
            logger.info("Started verification of %s.", email)
        except ClientError:
            logger.warning("Couldn't start verification of %s.", email)
    return verified_emails


def verify_domains(domain_list, ses_client):
    """
    Starts verification for a list of domain identities. This returns a token for
    each domain, which must be registered as a TXT record with the DNS provider for
    the domain.

    :param domain_list: The list of domains to verify.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The generated domain tokens to use to completed verification.
    """
    domain_tokens = {}
    for domain in domain_list:
        try:
            response = ses_client.verify_domain_identity(Domain=domain)
```

```
            token = response["VerificationToken"]
            domain_tokens[domain] = token
            logger.info("Got verification token %s for domain %s.", token, domain)
        except ClientError:
            logger.warning("Couldn't get verification token for domain %s.", domain)
    return domain_tokens


def get_hosted_zones(route53_client):
    """
    Gets the Amazon Route 53 hosted zones for the current account.

    :param route53_client: A Boto3 Route 53 client.
    :return: The list of hosted zones.
    """
    zones = []
    try:
        zone_paginator = route53_client.get_paginator("list_hosted_zones")
        zone_iterator = zone_paginator.paginate(PaginationConfig={"PageSize": 20})
        zones = [
            zone for zone_page in zone_iterator for zone in zone_page["HostedZones"]
        ]
        logger.info("Found %s hosted zones.", len(zones))
    except ClientError:
        logger.warning("Couldn't get hosted zones.")
    return zones


def find_domain_zone_matches(domains, zones):
    """
    Finds matches between Amazon SES verified domains and Route 53 hosted zones.
    Subdomain matches are taken when found, otherwise root domain matches are taken.

    :param domains: The list of domains to match.
    :param zones: The list of hosted zones to match.
    :return: The set of matched domain-zone pairs. When a match is not found, the
             domain is included in the set with a zone value of None.
    """
    domain_zones = {}
    for domain in domains:
        domain_zones[domain] = None
        # Start at the most specific sub-domain and walk up to the root domain until
 a
        # zone match is found.
```

```
        domain_split = domain.split(".")
        for index in range(0, len(domain_split) - 1):
            sub_domain = ".".join(domain_split[index:])
            for zone in zones:
                # Normalize the zone name from Route 53 by removing the trailing
 '.'.
                zone_name = zone["Name"][:-1]
                if sub_domain == zone_name:
                    domain_zones[domain] = zone
                    break
            if domain_zones[domain] is not None:
                break
    return domain_zones


def add_route53_verification_record(domain, token, zone, route53_client):
    """
    Adds a domain verification TXT record to the specified Route 53 hosted zone.
    When a TXT record already exists in the hosted zone for the specified domain,
    the existing values are preserved and the new token is added to the list.

    :param domain: The domain to add.
    :param token: The verification token for the domain.
    :param zone: The hosted zone where the domain verification record is added.
    :param route53_client: A Boto3 Route 53 client.
    """
    domain_token_record_set_name = f"_amazonses.{domain}"
    record_set_paginator = route53_client.get_paginator("list_resource_record_sets")
    record_set_iterator = record_set_paginator.paginate(
        HostedZoneId=zone["Id"], PaginationConfig={"PageSize": 20}
    )
    records = []
    for record_set_page in record_set_iterator:
        try:
            txt_record_set = next(
                record_set
                for record_set in record_set_page["ResourceRecordSets"]
                if record_set["Name"][:-1] == domain_token_record_set_name
                and record_set["Type"] == "TXT"
            )
            records = txt_record_set["ResourceRecords"]
            logger.info(
                "Existing TXT record found in set %s for zone %s.",
                domain_token_record_set_name,
```

```
                zone["Name"],
            )
            break
        except StopIteration:
            pass
    records.append({"Value": json.dumps(token)})
    changes = [
        {
            "Action": "UPSERT",
            "ResourceRecordSet": {
                "Name": domain_token_record_set_name,
                "Type": "TXT",
                "TTL": 1800,
                "ResourceRecords": records,
            },
        }
    ]
    try:
        route53_client.change_resource_record_sets(
            HostedZoneId=zone["Id"], ChangeBatch={"Changes": changes}
        )
        logger.info(
            "Created or updated the TXT record in set %s for zone %s.",
            domain_token_record_set_name,
            zone["Name"],
        )
    except ClientError as err:
        logger.warning(
            "Got error %s. Couldn't create or update the TXT record for zone %s.",
            err.response["Error"]["Code"],
            zone["Name"],
        )


def generate_dkim_tokens(domain, ses_client):
    """
    Generates DKIM tokens for a domain. These must be added as CNAME records to the
    DNS provider for the domain.

    :param domain: The domain to generate tokens for.
    :param ses_client: A Boto3 Amazon SES client.
    :return: The list of generated DKIM tokens.
    """
    dkim_tokens = []
```

```
    try:
        dkim_tokens = ses_client.verify_domain_dkim(Domain=domain)["DkimTokens"]
        logger.info("Generated %s DKIM tokens for domain %s.", len(dkim_tokens),
 domain)
    except ClientError:
        logger.warning("Couldn't generate DKIM tokens for domain %s.", domain)
    return dkim_tokens


def add_dkim_domain_tokens(hosted_zone, domain, tokens, route53_client):
    """
    Adds DKIM domain token CNAME records to a Route 53 hosted zone.

    :param hosted_zone: The hosted zone where the records are added.
    :param domain: The domain to add.
    :param tokens: The DKIM tokens for the domain to add.
    :param route53_client: A Boto3 Route 53 client.
    """
    try:
        changes = [
            {
                "Action": "UPSERT",
                "ResourceRecordSet": {
                    "Name": f"{token}._domainkey.{domain}",
                    "Type": "CNAME",
                    "TTL": 1800,
                    "ResourceRecords": [{"Value": f"{token}.dkim.amazonses.com"}],
                },
            }
            for token in tokens
        ]
        route53_client.change_resource_record_sets(
            HostedZoneId=hosted_zone["Id"], ChangeBatch={"Changes": changes}
        )
        logger.info(
            "Added %s DKIM CNAME records to %s in zone %s.",
            len(tokens),
            domain,
            hosted_zone["Name"],
        )
    except ClientError:
        logger.warning(
            "Couldn't add DKIM CNAME records for %s to zone %s.",
            domain,
```

```
            hosted_zone["Name"],
        )


def configure_sns_topics(identity, topics, ses_client):
    """
    Configures Amazon Simple Notification Service (Amazon SNS) notifications for
    an identity. The Amazon SNS topics must already exist.

    :param identity: The identity to configure.
    :param topics: The list of topics to configure. The choices are Bounce,
 Delivery,
                   or Complaint.
    :param ses_client: A Boto3 Amazon SES client.
    """
    for topic in topics:
        topic_arn = input(
            f"Enter the Amazon Resource Name (ARN) of the {topic} topic or press "
            f"Enter to skip: "
        )
        if topic_arn != "":
            try:
                ses_client.set_identity_notification_topic(
                    Identity=identity, NotificationType=topic, SnsTopic=topic_arn
                )
                logger.info("Configured %s for %s notifications.", identity, topic)
            except ClientError:
                logger.warning(
                    "Couldn't configure %s for %s notifications.", identity, topic
                )


def replicate(source_client, destination_client, route53_client):
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    print("-" * 88)
    print(
        f"Replicating Amazon SES identities and other configuration from "
        f"{source_client.meta.region_name} to
 {destination_client.meta.region_name}."
    )
    print("-" * 88)

    print(f"Retrieving identities from {source_client.meta.region_name}.")
```

```
    source_emails, source_domains = get_identities(source_client)
    print("Email addresses found:")
    print(*source_emails)
    print("Domains found:")
    print(*source_domains)

    print("Starting verification for email identities.")
    dest_emails = verify_emails(source_emails, destination_client)
    print("Getting domain tokens for domain identities.")
    dest_domain_tokens = verify_domains(source_domains, destination_client)

    # Get Route 53 hosted zones and match them with Amazon SES domains.
    answer = input(
        "Is the DNS configuration for your domains managed by Amazon Route 53 (y/n)?
"
    )
    use_route53 = answer.lower() == "y"
    hosted_zones = get_hosted_zones(route53_client) if use_route53 else []
    if use_route53:
        print("Adding or updating Route 53 TXT records for your domains.")
        domain_zones = find_domain_zone_matches(dest_domain_tokens.keys(),
hosted_zones)
        for domain in domain_zones:
            add_route53_verification_record(
                domain, dest_domain_tokens[domain], domain_zones[domain],
route53_client
            )
    else:
        print(
            "Use these verification tokens to create TXT records through your DNS "
            "provider:"
        )
        pprint(dest_domain_tokens)

    answer = input("Do you want to configure DKIM signing for your identities (y/n)?
")
    if answer.lower() == "y":
        # Build a set of unique domains from email and domain identities.
        domains = {email.split("@")[1] for email in dest_emails}
        domains.update(dest_domain_tokens)
        domain_zones = find_domain_zone_matches(domains, hosted_zones)
        for domain, zone in domain_zones.items():
            answer = input(
                f"Do you want to configure DKIM signing for {domain} (y/n)? "
```

```
            )
            if answer.lower() == "y":
                dkim_tokens = generate_dkim_tokens(domain, destination_client)
                if use_route53 and zone is not None:
                    add_dkim_domain_tokens(zone, domain, dkim_tokens,
 route53_client)
                else:
                    print(
                        "Add the following DKIM tokens as CNAME records through your
 "
                        "DNS provider:"
                    )
                    print(*dkim_tokens, sep="\n")

    answer = input(
        "Do you want to configure Amazon SNS notifications for your identities (y/
n)? "
    )
    if answer.lower() == "y":
        for identity in dest_emails + list(dest_domain_tokens.keys()):
            answer = input(
                f"Do you want to configure Amazon SNS topics for {identity} (y/n)? "
            )
            if answer.lower() == "y":
                configure_sns_topics(
                    identity, ["Bounce", "Delivery", "Complaint"],
 destination_client
                )

    print(f"Replication complete for {destination_client.meta.region_name}.")
    print("-" * 88)


def main():
    boto3_session = boto3.Session()
    ses_regions = boto3_session.get_available_regions("ses")
    parser = argparse.ArgumentParser(
        description="Copies email address and domain identities from one AWS Region
 to "
        "another. Optionally adds records for domain verification and DKIM "
        "signing to domains that are managed by Amazon Route 53, "
        "and sets up Amazon SNS notifications for events of interest."
    )
    parser.add_argument(
```

```
        "source_region", choices=ses_regions, help="The region to copy from."
    )
    parser.add_argument(
        "destination_region", choices=ses_regions, help="The region to copy to."
    )
    args = parser.parse_args()
    source_client = boto3.client("ses", region_name=args.source_region)
    destination_client = boto3.client("ses", region_name=args.destination_region)
    route53_client = boto3.client("route53")
    replicate(source_client, destination_client, route53_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - ListIdentities
  - SetIdentityNotificationTopic
  - VerifyDomainDkim
  - VerifyDomainIdentity
  - VerifyEmailIdentity

Gerar credenciais para estabelecer conexão com um endpoint SMTP

O exemplo de código a seguir mostra como gerar credenciais para estabelecer conexão com um endpoint SMTP do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
#!/usr/bin/env python3
```

```
import hmac
import hashlib
import base64
import argparse

SMTP_REGIONS = [
    "us-east-2",  # US East (Ohio)
    "us-east-1",  # US East (N. Virginia)
    "us-west-2",  # US West (Oregon)
    "ap-south-1",  # Asia Pacific (Mumbai)
    "ap-northeast-2",  # Asia Pacific (Seoul)
    "ap-southeast-1",  # Asia Pacific (Singapore)
    "ap-southeast-2",  # Asia Pacific (Sydney)
    "ap-northeast-1",  # Asia Pacific (Tokyo)
    "ca-central-1",  # Canada (Central)
    "eu-central-1",  # Europe (Frankfurt)
    "eu-west-1",  # Europe (Ireland)
    "eu-west-2",  # Europe (London)
    "eu-south-1",  # Europe (Milan)
    "eu-north-1",  # Europe (Stockholm)
    "sa-east-1",  # South America (Sao Paulo)
    "us-gov-west-1",  # AWS GovCloud (US)
]

# These values are required to calculate the signature. Do not change them.
DATE = "11111111"
SERVICE = "ses"
MESSAGE = "SendRawEmail"
TERMINAL = "aws4_request"
VERSION = 0x04


def sign(key, msg):
    return hmac.new(key, msg.encode("utf-8"), hashlib.sha256).digest()


def calculate_key(secret_access_key, region):
    if region not in SMTP_REGIONS:
        raise ValueError(f"The {region} Region doesn't have an SMTP endpoint.")

    signature = sign(("AWS4" + secret_access_key).encode("utf-8"), DATE)
    signature = sign(signature, region)
    signature = sign(signature, SERVICE)
    signature = sign(signature, TERMINAL)
```

```
    signature = sign(signature, MESSAGE)
    signature_and_version = bytes([VERSION]) + signature
    smtp_password = base64.b64encode(signature_and_version)
    return smtp_password.decode("utf-8")


def main():
    parser = argparse.ArgumentParser(
        description="Convert a Secret Access Key to an SMTP password."
    )
    parser.add_argument("secret", help="The Secret Access Key to convert.")
    parser.add_argument(
        "region",
        help="The AWS Region where the SMTP password will be used.",
        choices=SMTP_REGIONS,
    )
    args = parser.parse_args()
    print(calculate_key(args.secret, args.region))


if __name__ == "__main__":
    main()
```

Verificar uma identidade de e-mail e enviar mensagens

O código de exemplo a seguir mostra como:

- Adicione e verifique um endereço de e-mail com o Amazon SES.
- Envie uma mensagem de e-mail padrão.
- Crie um modelo e envie uma mensagem de e-mail com modelo.
- Envie uma mensagem usando um servidor SMTP do Amazon SES.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Verifique um endereço de e-mail com o Amazon SES e envie mensagens.

```
def usage_demo():
    print("-" * 88)
    print("Welcome to the Amazon Simple Email Service (Amazon SES) email demo!")
    print("-" * 88)

    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    ses_client = boto3.client("ses")
    ses_identity = SesIdentity(ses_client)
    ses_mail_sender = SesMailSender(ses_client)
    ses_template = SesTemplate(ses_client)
    email = input("Enter an email address to send mail with Amazon SES: ")
    status = ses_identity.get_identity_status(email)
    verified = status == "Success"
    if not verified:
        answer = input(
            f"The address '{email}' is not verified with Amazon SES. Unless your "
            f"Amazon SES account is out of sandbox, you can send mail only from "
            f"and to verified accounts. Do you want to verify this account for use "
            f"with Amazon SES? If yes, the address will receive a verification "
            f"email (y/n): "
        )
        if answer.lower() == "y":
            ses_identity.verify_email_identity(email)
            print(f"Follow the steps in the email to {email} to complete
 verification.")
            print("Waiting for verification...")
            try:
                ses_identity.wait_until_identity_exists(email)
                print(f"Identity verified for {email}.")
                verified = True
            except WaiterError:
                print(
                    f"Verification timeout exceeded. You must complete the "
                    f"steps in the email sent to {email} to verify the address."
                )

    if verified:
        test_message_text = "Hello from the Amazon SES mail demo!"
        test_message_html = "<p>Hello!</p><p>From the <b>Amazon SES</b> mail demo!</
p>"
```

```
        print(f"Sending mail from {email} to {email}.")
        ses_mail_sender.send_email(
            email,
            SesDestination([email]),
            "Amazon SES demo",
            test_message_text,
            test_message_html,
        )
        input("Mail sent. Check your inbox and press Enter to continue.")

        template = {
            "name": "doc-example-template",
            "subject": "Example of an email template.",
            "text": "This is what {{name}} will {{action}} if {{name}} can't display
 "
            "HTML.",
            "html": "<p><i>This</i> is what {{name}} will {{action}} if {{name}} "
            "<b>can</b> display HTML.</p>",
        }
        print("Creating a template and sending a templated email.")
        ses_template.create_template(**template)
        template_data = {"name": email.split("@")[0], "action": "read"}
        if ses_template.verify_tags(template_data):
            ses_mail_sender.send_templated_email(
                email, SesDestination([email]), ses_template.name(), template_data
            )
            input("Mail sent. Check your inbox and press Enter to continue.")

        print("Sending mail through the Amazon SES SMTP server.")
        boto3_session = boto3.Session()
        region = boto3_session.region_name
        credentials = boto3_session.get_credentials()
        port = 587
        smtp_server = f"email-smtp.{region}.amazonaws.com"
        password = calculate_key(credentials.secret_key, region)
        message = """
Subject: Hi there

This message is sent from the Amazon SES SMTP mail demo."""
        context = ssl.create_default_context()
        with smtplib.SMTP(smtp_server, port) as server:
            server.starttls(context=context)
            server.login(credentials.access_key, password)
            server.sendmail(email, email, message)
```

```
        print("Mail sent. Check your inbox!")

    if ses_template.template is not None:
        print("Deleting demo template.")
        ses_template.delete_template()
    if verified:
        answer = input(f"Do you want to remove {email} from Amazon SES (y/n)? ")
        if answer.lower() == "y":
            ses_identity.delete_identity(email)
    print("Thanks for watching!")
    print("-" * 88)
```

Crie funções para encapsular ações de identidade do Amazon SES.

```
class SesIdentity:
    """Encapsulates Amazon SES identity functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def verify_domain_identity(self, domain_name):
        """
        Starts verification of a domain identity. To complete verification, you must
        create a TXT record with a specific format through your DNS provider.

        For more information, see *Verifying a domain with Amazon SES* in the
        Amazon SES documentation:
            https://docs.aws.amazon.com/ses/latest/DeveloperGuide/verify-domain-
procedure.html

        :param domain_name: The name of the domain to verify.
        :return: The token to include in the TXT record with your DNS provider.
        """
        try:
            response = self.ses_client.verify_domain_identity(Domain=domain_name)
            token = response["VerificationToken"]
```

```
            logger.info("Got domain verification token for %s.", domain_name)
        except ClientError:
            logger.exception("Couldn't verify domain %s.", domain_name)
            raise
        else:
            return token


    def verify_email_identity(self, email_address):
        """
        Starts verification of an email identity. This function causes an email
        to be sent to the specified email address from Amazon SES. To complete
        verification, follow the instructions in the email.

        :param email_address: The email address to verify.
        """
        try:
            self.ses_client.verify_email_identity(EmailAddress=email_address)
            logger.info("Started verification of %s.", email_address)
        except ClientError:
            logger.exception("Couldn't start verification of %s.", email_address)
            raise


    def wait_until_identity_exists(self, identity):
        """
        Waits until an identity exists. The waiter polls Amazon SES until the
        identity has been successfully verified or until it exceeds its maximum
time.

        :param identity: The identity to wait for.
        """
        try:
            waiter = self.ses_client.get_waiter("identity_exists")
            logger.info("Waiting until %s exists.", identity)
            waiter.wait(Identities=[identity])
        except WaiterError:
            logger.error("Waiting for identity %s failed or timed out.", identity)
            raise


    def get_identity_status(self, identity):
        """
        Gets the status of an identity. This can be used to discover whether
```

```
        an identity has been successfully verified.

        :param identity: The identity to query.
        :return: The status of the identity.
        """
        try:
            response = self.ses_client.get_identity_verification_attributes(
                Identities=[identity]
            )
            status = response["VerificationAttributes"].get(
                identity, {"VerificationStatus": "NotFound"}
            )["VerificationStatus"]
            logger.info("Got status of %s for %s.", status, identity)
        except ClientError:
            logger.exception("Couldn't get status for %s.", identity)
            raise
        else:
            return status


    def delete_identity(self, identity):
        """
        Deletes an identity.

        :param identity: The identity to remove.
        """
        try:
            self.ses_client.delete_identity(Identity=identity)
            logger.info("Deleted identity %s.", identity)
        except ClientError:
            logger.exception("Couldn't delete identity %s.", identity)
            raise


    def list_identities(self, identity_type, max_items):
        """
        Gets the identities of the specified type for the current account.

        :param identity_type: The type of identity to retrieve, such as
EmailAddress.
        :param max_items: The maximum number of identities to retrieve.
        :return: The list of retrieved identities.
        """
        try:
```

```
            response = self.ses_client.list_identities(
                IdentityType=identity_type, MaxItems=max_items
            )
            identities = response["Identities"]
            logger.info("Got %s identities for the current account.",
len(identities))
        except ClientError:
            logger.exception("Couldn't list identities for the current account.")
            raise
        else:
            return identities
```

Crie funções para encapsular ações com modelo do Amazon SES.

```
class SesTemplate:
    """Encapsulates Amazon SES template functions."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client
        self.template = None
        self.template_tags = set()

    def _extract_tags(self, subject, text, html):
        """
        Extracts tags from a template as a set of unique values.

        :param subject: The subject of the email.
        :param text: The text version of the email.
        :param html: The html version of the email.
        """
        self.template_tags = set(re.findall(TEMPLATE_REGEX, subject + text + html))
        logger.info("Extracted template tags: %s", self.template_tags)


    def create_template(self, name, subject, text, html):
        """
        Creates an email template.
```

```
        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
        """
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.create_template(Template=template)
            logger.info("Created template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't create template %s.", name)
            raise


    def delete_template(self):
        """
        Deletes an email template.
        """
        try:

self.ses_client.delete_template(TemplateName=self.template["TemplateName"])
            logger.info("Deleted template %s.", self.template["TemplateName"])
            self.template = None
            self.template_tags = None
        except ClientError:
            logger.exception(
                "Couldn't delete template %s.", self.template["TemplateName"]
            )
            raise


    def get_template(self, name):
        """
        Gets a previously created email template.

        :param name: The name of the template to retrieve.
```

```
        :return: The retrieved email template.
        """
        try:
            response = self.ses_client.get_template(TemplateName=name)
            self.template = response["Template"]
            logger.info("Got template %s.", name)
            self._extract_tags(
                self.template["SubjectPart"],
                self.template["TextPart"],
                self.template["HtmlPart"],
            )
        except ClientError:
            logger.exception("Couldn't get template %s.", name)
            raise
        else:
            return self.template


    def list_templates(self):
        """
        Gets a list of all email templates for the current account.

        :return: The list of retrieved email templates.
        """
        try:
            response = self.ses_client.list_templates()
            templates = response["TemplatesMetadata"]
            logger.info("Got %s templates.", len(templates))
        except ClientError:
            logger.exception("Couldn't get templates.")
            raise
        else:
            return templates


    def update_template(self, name, subject, text, html):
        """
        Updates a previously created email template.

        :param name: The name of the template.
        :param subject: The subject of the email.
        :param text: The plain text version of the email.
        :param html: The HTML version of the email.
        """
```

```
        try:
            template = {
                "TemplateName": name,
                "SubjectPart": subject,
                "TextPart": text,
                "HtmlPart": html,
            }
            self.ses_client.update_template(Template=template)
            logger.info("Updated template %s.", name)
            self.template = template
            self._extract_tags(subject, text, html)
        except ClientError:
            logger.exception("Couldn't update template %s.", name)
            raise
```

Crie funções para encapsular ações de e-mail do Amazon SES.

```
class SesDestination:
    """Contains data about an email destination."""

    def __init__(self, tos, ccs=None, bccs=None):
        """
        :param tos: The list of recipients on the 'To:' line.
        :param ccs: The list of recipients on the 'CC:' line.
        :param bccs: The list of recipients on the 'BCC:' line.
        """
        self.tos = tos
        self.ccs = ccs
        self.bccs = bccs

    def to_service_format(self):
        """
        :return: The destination data in the format expected by Amazon SES.
        """
        svc_format = {"ToAddresses": self.tos}
        if self.ccs is not None:
            svc_format["CcAddresses"] = self.ccs
        if self.bccs is not None:
            svc_format["BccAddresses"] = self.bccs
        return svc_format
```

```
class SesMailSender:
    """Encapsulates functions to send emails with Amazon SES."""

    def __init__(self, ses_client):
        """
        :param ses_client: A Boto3 Amazon SES client.
        """
        self.ses_client = ses_client


    def send_email(self, source, destination, subject, text, html, reply_tos=None):
        """
        Sends an email.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param subject: The subject of the email.
        :param text: The plain text version of the body of the email.
        :param html: The HTML version of the body of the email.
        :param reply_tos: Email accounts that will receive a reply if the recipient
                          replies to the message.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Message": {
                "Subject": {"Data": subject},
                "Body": {"Text": {"Data": text}, "Html": {"Data": html}},
            },
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent mail %s from %s to %s.", message_id, source, destination.tos
```

```
            )
        except ClientError:
            logger.exception(
                "Couldn't send mail from %s to %s.", source, destination.tos
            )
            raise
        else:
            return message_id


    def send_templated_email(
        self, source, destination, template_name, template_data, reply_tos=None
    ):
        """
        Sends an email based on a template. A template contains replaceable tags
        each enclosed in two curly braces, such as {{name}}. The template data
passed
        in this function contains key-value pairs that define the values to insert
        in place of the template tags.

        Note: If your account is in the Amazon SES  sandbox, the source and
        destination email accounts must both be verified.

        :param source: The source email account.
        :param destination: The destination email account.
        :param template_name: The name of a previously created template.
        :param template_data: JSON-formatted key-value pairs of replacement values
                              that are inserted in the template before it is sent.
        :return: The ID of the message, assigned by Amazon SES.
        """
        send_args = {
            "Source": source,
            "Destination": destination.to_service_format(),
            "Template": template_name,
            "TemplateData": json.dumps(template_data),
        }
        if reply_tos is not None:
            send_args["ReplyToAddresses"] = reply_tos
        try:
            response = self.ses_client.send_templated_email(**send_args)
            message_id = response["MessageId"]
            logger.info(
                "Sent templated mail %s from %s to %s.",
                message_id,
```

```
                source,
                destination.tos,
            )
        except ClientError:
            logger.exception(
                "Couldn't send templated mail from %s to %s.", source,
destination.tos
            )
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTemplate
  - DeleteIdentity
  - DeleteTemplate
  - GetIdentityVerificationAttributes
  - GetTemplate
  - ListIdentities
  - ListTemplates
  - SendEmail
  - SendTemplatedEmail
  - UpdateTemplate
  - VerifyDomainIdentity
  - VerifyEmailIdentity

Exemplos do Amazon SNS usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    def create_topic(self, name):
        """
        Creates a notification topic.

        :param name: The name of the topic to create.
        :return: The newly created topic.
        """
        try:
            topic = self.sns_resource.create_topic(Name=name)
            logger.info("Created topic %s with ARN %s.", name, topic.arn)
        except ClientError:
            logger.exception("Couldn't create topic %s.", name)
            raise
        else:
            return topic
```

- Para obter detalhes da API, consulte a CreateTopicReferência da API AWSSDK for Python (Boto3).

Excluir uma assinatura

O exemplo de códigos a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    @staticmethod
    def delete_subscription(subscription):
        """
        Unsubscribes and deletes a subscription.
        """
        try:
            subscription.delete()
            logger.info("Deleted subscription %s.", subscription.arn)
        except ClientError:
            logger.exception("Couldn't delete subscription %s.", subscription.arn)
            raise
```

- Para obter detalhes da API, consulte Unsubscribe na Referência da API do AWS SDK for Python (Boto3).

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas desse tópico.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    @staticmethod
    def delete_topic(topic):
        """
        Deletes a topic. All subscriptions to the topic are also deleted.
        """
        try:
            topic.delete()
            logger.info("Deleted topic %s.", topic.arn)
        except ClientError:
            logger.exception("Couldn't delete topic %s.", topic.arn)
            raise
```

- Para obter detalhes da API, consulte a DeleteTopicReferência da API AWSSDK for Python (Boto3).

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource
```

```
    def list_subscriptions(self, topic=None):
        """
        Lists subscriptions for the current account, optionally limited to a
        specific topic.

        :param topic: When specified, only subscriptions to this topic are returned.
        :return: An iterator that yields the subscriptions.
        """
        try:
            if topic is None:
                subs_iter = self.sns_resource.subscriptions.all()
            else:
                subs_iter = topic.subscriptions.all()
            logger.info("Got subscriptions.")
        except ClientError:
            logger.exception("Couldn't get subscriptions.")
            raise
        else:
            return subs_iter
```

- Para obter detalhes da API, consulte a ListSubscriptionsReferência da API AWSSDK for Python (Boto3).

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
```

```
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    def list_topics(self):
        """
        Lists topics for the current account.

        :return: An iterator that yields the topics.
        """
        try:
            topics_iter = self.sns_resource.topics.all()
            logger.info("Got topics.")
        except ClientError:
            logger.exception("Couldn't get topics.")
            raise
        else:
            return topics_iter
```

- Para obter detalhes da API, consulte a ListTopicsReferência da API AWSSDK for Python (Boto3).

Publicar uma mensagem de texto SMS

O exemplo de código a seguir mostra como publicar mensagens SMS usando o Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""
```

```
    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    def publish_text_message(self, phone_number, message):
        """
        Publishes a text message directly to a phone number without need for a
        subscription.

        :param phone_number: The phone number that receives the message. This must
be
                             in E.164 format. For example, a United States phone
                             number might be +12065550101.
        :param message: The message to send.
        :return: The ID of the message.
        """
        try:
            response = self.sns_resource.meta.client.publish(
                PhoneNumber=phone_number, Message=message
            )
            message_id = response["MessageId"]
            logger.info("Published message to %s.", phone_number)
        except ClientError:
            logger.exception("Couldn't publish message to %s.", phone_number)
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Python (Boto3).

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Publique uma mensagem com atributos para que uma assinatura possa filtrar com base em atributos.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def publish_message(topic, message, attributes):
        """
        Publishes a message, with attributes, to a topic. Subscriptions can be
 filtered
        based on message attributes so that a subscription receives messages only
        when specified attributes are present.

        :param topic: The topic to publish to.
        :param message: The message to publish.
        :param attributes: The key-value attributes to attach to the message. Values
                           must be either `str` or `bytes`.
        :return: The ID of the message.
        """
        try:
            att_dict = {}
            for key, value in attributes.items():
                if isinstance(value, str):
                    att_dict[key] = {"DataType": "String", "StringValue": value}
                elif isinstance(value, bytes):
                    att_dict[key] = {"DataType": "Binary", "BinaryValue": value}
```

```
            response = topic.publish(Message=message, MessageAttributes=att_dict)
            message_id = response["MessageId"]
            logger.info(
                "Published message with attributes %s to topic %s.",
                attributes,
                topic.arn,
            )
        except ClientError:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise
        else:
            return message_id
```

Publique uma mensagem que assume diferentes formas com base no protocolo do assinante.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def publish_multi_message(
        topic, subject, default_message, sms_message, email_message
    ):
        """
        Publishes a multi-format message to a topic. A multi-format message takes
        different forms based on the protocol of the subscriber. For example,
        an SMS subscriber might receive a short version of the message
        while an email subscriber could receive a longer version.

        :param topic: The topic to publish to.
        :param subject: The subject of the message.
        :param default_message: The default version of the message. This version is
                                sent to subscribers that have protocols that are not
                                otherwise specified in the structured message.
        :param sms_message: The version of the message sent to SMS subscribers.
```

```
        :param email_message: The version of the message sent to email subscribers.
        :return: The ID of the message.
        """
        try:
            message = {
                "default": default_message,
                "sms": sms_message,
                "email": email_message,
            }
            response = topic.publish(
                Message=json.dumps(message), Subject=subject,
MessageStructure="json"
            )
            message_id = response["MessageId"]
            logger.info("Published multi-format message to topic %s.", topic.arn)
        except ClientError:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise
        else:
            return message_id
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Python (Boto3).

Definir uma política de filtro

O exemplo de código a seguir mostra como definir uma política de filtro do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""
```

```
    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def add_subscription_filter(subscription, attributes):
        """
        Adds a filter policy to a subscription. A filter policy is a key and a
        list of values that are allowed. When a message is published, it must have
an
        attribute that passes the filter or it will not be sent to the subscription.

        :param subscription: The subscription the filter policy is attached to.
        :param attributes: A dictionary of key-value pairs that define the filter.
        """
        try:
            att_policy = {key: [value] for key, value in attributes.items()}
            subscription.set_attributes(
                AttributeName="FilterPolicy", AttributeValue=json.dumps(att_policy)
            )
            logger.info("Added filter to subscription %s.", subscription.arn)
        except ClientError:
            logger.exception(
                "Couldn't add filter to subscription %s.", subscription.arn
            )
            raise
```

- Para obter detalhes da API, consulte a SetSubscriptionAttributesReferência da API AWSSDK for Python (Boto3).

Inscrever um endereço de e-mail em um tópico

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SnsWrapper:
    """Encapsulates Amazon SNS topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource


    @staticmethod
    def subscribe(topic, protocol, endpoint):
        """
        Subscribes an endpoint to the topic. Some endpoint types, such as email,
        must be confirmed before their subscriptions are active. When a subscription
        is not confirmed, its Amazon Resource Number (ARN) is set to
        'PendingConfirmation'.

        :param topic: The topic to subscribe to.
        :param protocol: The protocol of the endpoint, such as 'sms' or 'email'.
        :param endpoint: The endpoint that receives messages, such as a phone number
                         (in E.164 format) for SMS messages, or an email address for
                         email messages.
        :return: The newly added subscription.
        """
        try:
            subscription = topic.subscribe(
                Protocol=protocol, Endpoint=endpoint, ReturnSubscriptionArn=True
            )
            logger.info("Subscribed %s %s to topic %s.", protocol, endpoint,
 topic.arn)
        except ClientError:
            logger.exception(
```

```
                "Couldn't subscribe %s %s to topic %s.", protocol, endpoint,
topic.arn
            )
            raise
        else:
            return subscription
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Python (Boto3).

Cenários

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO do Amazon SNS, inscreva filas padrão e FIFO do Amazon SQS no tópico e publique uma mensagem no tópico.

```
def usage_demo():
    """Shows how to subscribe queues to a FIFO topic."""
    print("-" * 88)
    print("Welcome to the `Subscribe queues to a FIFO topic` demo!")
    print("-" * 88)

    sns = boto3.resource("sns")
    sqs = boto3.resource("sqs")
    fifo_topic_wrapper = FifoTopicWrapper(sns)
    sns_wrapper = SnsWrapper(sns)

    prefix = "sqs-subscribe-demo-"
    queues = set()
```

```
    subscriptions = set()

    wholesale_queue = sqs.create_queue(
        QueueName=prefix + "wholesale.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(wholesale_queue)
    print(f"Created FIFO queue with URL: {wholesale_queue.url}.")

    retail_queue = sqs.create_queue(
        QueueName=prefix + "retail.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(retail_queue)
    print(f"Created FIFO queue with URL: {retail_queue.url}.")

    analytics_queue = sqs.create_queue(QueueName=prefix + "analytics",
Attributes={})
    queues.add(analytics_queue)
    print(f"Created standard queue with URL: {analytics_queue.url}.")

    topic = fifo_topic_wrapper.create_fifo_topic("price-updates-topic.fifo")
    print(f"Created FIFO topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        fifo_topic_wrapper.add_access_policy(q, topic.attributes["TopicArn"])

    print(f"Added access policies for topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        sub = fifo_topic_wrapper.subscribe_queue_to_topic(
            topic, q.attributes["QueueArn"]
```

```
        )
        subscriptions.add(sub)

    print(f"Subscribed queues to topic: {topic.attributes['TopicArn']}.")

    input("Press Enter to publish a message to the topic.")

    message_id = fifo_topic_wrapper.publish_price_update(
        topic, '{"product": 214, "price": 79.99}', "Consumables"
    )

    print(f"Published price update with message ID: {message_id}.")

    # Clean up the subscriptions, queues, and topic.
    input("Press Enter to clean up resources.")
    for s in subscriptions:
        sns_wrapper.delete_subscription(s)

    sns_wrapper.delete_topic(topic)

    for q in queues:
        fifo_topic_wrapper.delete_queue(q)

    print(f"Deleted subscriptions, queues, and topic.")

    print("Thanks for watching!")
    print("-" * 88)



class FifoTopicWrapper:
    """Encapsulates Amazon SNS FIFO topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource

    def create_fifo_topic(self, topic_name):
        """
        Create a FIFO topic.
        Topic names must be made up of only uppercase and lowercase ASCII letters,
```

```
        numbers, underscores, and hyphens, and must be between 1 and 256 characters
long.
        For a FIFO topic, the name must end with the .fifo suffix.

        :param topic_name: The name for the topic.
        :return: The new topic.
        """
        try:
            topic = self.sns_resource.create_topic(
                Name=topic_name,
                Attributes={
                    "FifoTopic": str(True),
                    "ContentBasedDeduplication": str(False),
                },
            )
            logger.info("Created FIFO topic with name=%s.", topic_name)
            return topic
        except ClientError as error:
            logger.exception("Couldn't create topic with name=%s!", topic_name)
            raise error


    @staticmethod
    def add_access_policy(queue, topic_arn):
        """
        Add the necessary access policy to a queue, so
        it can receive messages from a topic.

        :param queue: The queue resource.
        :param topic_arn: The ARN of the topic.
        :return: None.
        """
        try:
            queue.set_attributes(
                Attributes={
                    "Policy": json.dumps(
                        {
                            "Version": "2012-10-17",
                            "Statement": [
                                {
                                    "Sid": "test-sid",
                                    "Effect": "Allow",
                                    "Principal": {"AWS": "*"},
                                    "Action": "SQS:SendMessage",
```

```
                                    "Resource": queue.attributes["QueueArn"],
                                    "Condition": {
                                        "ArnLike": {"aws:SourceArn": topic_arn}
                                    },
                                }
                            ],
                        }
                    )
                }
            )
            logger.info("Added trust policy to the queue.")
        except ClientError as error:
            logger.exception("Couldn't add trust policy to the queue!")
            raise error


    @staticmethod
    def subscribe_queue_to_topic(topic, queue_arn):
        """
        Subscribe a queue to a topic.

        :param topic: The topic resource.
        :param queue_arn: The ARN of the queue.
        :return: The subscription resource.
        """
        try:
            subscription = topic.subscribe(
                Protocol="sqs",
                Endpoint=queue_arn,
            )
            logger.info("The queue is subscribed to the topic.")
            return subscription
        except ClientError as error:
            logger.exception("Couldn't subscribe queue to topic!")
            raise error


    @staticmethod
    def publish_price_update(topic, payload, group_id):
        """
        Compose and publish a message that updates the wholesale price.

        :param topic: The topic to publish to.
        :param payload: The message to publish.
```

```
        :param group_id: The group ID for the message.
        :return: The ID of the message.
        """
        try:
            att_dict = {"business": {"DataType": "String", "StringValue":
"wholesale"}}
            dedup_id = uuid.uuid4()
            response = topic.publish(
                Subject="Price Update",
                Message=payload,
                MessageAttributes=att_dict,
                MessageGroupId=group_id,
                MessageDeduplicationId=str(dedup_id),
            )
            message_id = response["MessageId"]
            logger.info("Published message to topic %s.", topic.arn)
        except ClientError as error:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise error
        return message_id


    @staticmethod
    def delete_queue(queue):
        """
        Removes an SQS queue. When run against an AWS account, it can take up to
        60 seconds before the queue is actually deleted.

        :param queue: The queue to delete.
        :return: None
        """
        try:
            queue.delete()
            logger.info("Deleted queue with URL=%s.", queue.url)
        except ClientError as error:
            logger.exception("Couldn't delete queue with URL=%s!", queue.url)
            raise error
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTopic
  - Publicar
  - Assinar

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for record in event['Records']:
        process_message(record)
    print("done")

def process_message(record):
    try:
        message = record['Sns']['Message']
        print(f"Processed message {message}")
        # TODO; Process your record here

    except Exception as e:
        print("An error occurred")
        raise e
```

Exemplos do Amazon SQS usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_queue(name, attributes=None):
    """
    Creates an Amazon SQS queue.

    :param name: The name of the queue. This is part of the URL assigned to the
 queue.
```

```
    :param attributes: The attributes of the queue, such as maximum message size or
                       whether it's a FIFO queue.
    :return: A Queue object that contains metadata about the queue and that can be
 used
             to perform queue operations like sending and receiving messages.
    """
    if not attributes:
        attributes = {}

    try:
        queue = sqs.create_queue(QueueName=name, Attributes=attributes)
        logger.info("Created queue '%s' with URL=%s", name, queue.url)
    except ClientError as error:
        logger.exception("Couldn't create queue named '%s'.", name)
        raise error
    else:
        return queue
```

- Para obter detalhes da API, consulte a CreateQueueReferência da API AWSSDK for Python (Boto3).

Excluir um lote de mensagens de uma fila

O exemplo de código a seguir mostra como excluir um lote de mensagens de uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_messages(queue, messages):
    """
    Delete a batch of messages from a queue in a single request.
```

```
    :param queue: The queue from which to delete the messages.
    :param messages: The list of messages to delete.
    :return: The response from SQS that contains the list of successful and failed
             message deletions.
    """
    try:
        entries = [
            {"Id": str(ind), "ReceiptHandle": msg.receipt_handle}
            for ind, msg in enumerate(messages)
        ]
        response = queue.delete_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info("Deleted %s",
messages[int(msg_meta["Id"])].receipt_handle)
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Could not delete %s",
messages[int(msg_meta["Id"])].receipt_handle
                )
    except ClientError:
        logger.exception("Couldn't delete messages from queue %s", queue)
    else:
        return response
```

- Para obter detalhes da API, consulte a DeleteMessageBatchReferência da API AWSSDK for Python (Boto3).

Excluir uma mensagem de uma fila

O exemplo de código a seguir mostra como excluir uma mensagem de uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_message(message):
    """
    Delete a message from a queue. Clients must delete messages after they
    are received and processed to remove them from the queue.

    :param message: The message to delete. The message's queue URL is contained in
                    the message's metadata.
    :return: None
    """
    try:
        message.delete()
        logger.info("Deleted message: %s", message.message_id)
    except ClientError as error:
        logger.exception("Couldn't delete message: %s", message.message_id)
        raise error
```

- Para obter detalhes da API, consulte a DeleteMessageReferência da API AWSSDK for Python (Boto3).

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def remove_queue(queue):
    """
    Removes an SQS queue. When run against an AWS account, it can take up to
    60 seconds before the queue is actually deleted.

    :param queue: The queue to delete.
    :return: None
    """
    try:
        queue.delete()
        logger.info("Deleted queue with URL=%s.", queue.url)
    except ClientError as error:
        logger.exception("Couldn't delete queue with URL=%s!", queue.url)
        raise error
```

- Para obter detalhes da API, consulte a DeleteQueueReferência da API AWSSDK for Python (Boto3).

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_queue(name):
    """
    Gets an SQS queue by name.

    :param name: The name that was used to create the queue.
    :return: A Queue object.
    """
    try:
```

```
        queue = sqs.get_queue_by_name(QueueName=name)
        logger.info("Got queue '%s' with URL=%s", name, queue.url)
    except ClientError as error:
        logger.exception("Couldn't get queue named %s.", name)
        raise error
    else:
        return queue
```

- Para obter detalhes da API, consulte a GetQueueUrlReferência da API AWSSDK for Python (Boto3).

Listar filas

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_queues(prefix=None):
    """
    Gets a list of SQS queues. When a prefix is specified, only queues with names
    that start with the prefix are returned.

    :param prefix: The prefix used to restrict the list of returned queues.
    :return: A list of Queue objects.
    """
    if prefix:
        queue_iter = sqs.queues.filter(QueueNamePrefix=prefix)
    else:
        queue_iter = sqs.queues.all()
    queues = list(queue_iter)
    if queues:
        logger.info("Got queues: %s", ", ".join([q.url for q in queues]))
    else:
```

```
        logger.warning("No queues found.")
    return queues
```

- Para obter detalhes da API, consulte a ListQueuesReferência da API AWSSDK for Python (Boto3).

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def receive_messages(queue, max_number, wait_time):
    """
    Receive a batch of messages in a single request from an SQS queue.

    :param queue: The queue from which to receive messages.
    :param max_number: The maximum number of messages to receive. The actual number
                       of messages received might be less.
    :param wait_time: The maximum time to wait (in seconds) before returning. When
                      this number is greater than zero, long polling is used. This
                      can result in reduced costs and fewer false empty responses.
    :return: The list of Message objects received. These each contain the body
             of the message and metadata and custom attributes.
    """
    try:
        messages = queue.receive_messages(
            MessageAttributeNames=["All"],
            MaxNumberOfMessages=max_number,
            WaitTimeSeconds=wait_time,
        )
        for msg in messages:
            logger.info("Received message: %s: %s", msg.message_id, msg.body)
```

```
    except ClientError as error:
        logger.exception("Couldn't receive messages from queue: %s", queue)
        raise error
    else:
        return messages
```

- Para obter detalhes da API, consulte a ReceiveMessageReferência da API AWSSDK for Python (Boto3).

Para enviar mensagens em lote a uma fila.

O exemplo de código a seguir mostra como enviar um lote de mensagens para uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def send_messages(queue, messages):
    """
    Send a batch of messages in a single request to an SQS queue.
    This request may return overall success even when some messages were not sent.
    The caller must inspect the Successful and Failed lists in the response and
    resend any failed messages.

    :param queue: The queue to receive the messages.
    :param messages: The messages to send to the queue. These are simplified to
                     contain only the message body and attributes.
    :return: The response from SQS that contains the list of successful and failed
             messages.
    """
    try:
        entries = [
            {
```

```
                "Id": str(ind),
                "MessageBody": msg["body"],
                "MessageAttributes": msg["attributes"],
            }
            for ind, msg in enumerate(messages)
        ]
        response = queue.send_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info(
                    "Message sent: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Failed to send: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
    except ClientError as error:
        logger.exception("Send messages failed to queue: %s", queue)
        raise error
    else:
        return response
```

- Para obter detalhes da API, consulte a SendMessageBatchReferência da API AWSSDK for Python (Boto3).

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def send_message(queue, message_body, message_attributes=None):
    """
    Send a message to an Amazon SQS queue.

    :param queue: The queue that receives the message.
    :param message_body: The body text of the message.
    :param message_attributes: Custom attributes of the message. These are key-value
                               pairs that can be whatever you want.
    :return: The response from SQS that contains the assigned message ID.
    """
    if not message_attributes:
        message_attributes = {}

    try:
        response = queue.send_message(
            MessageBody=message_body, MessageAttributes=message_attributes
        )
    except ClientError as error:
        logger.exception("Send message failed: %s", message_body)
        raise error
    else:
        return response
```

- Para obter detalhes da API, consulte a SendMessageReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO do Amazon SNS, inscreva filas padrão e FIFO do Amazon SQS no tópico e publique uma mensagem no tópico.

```
def usage_demo():
    """Shows how to subscribe queues to a FIFO topic."""
    print("-" * 88)
    print("Welcome to the `Subscribe queues to a FIFO topic` demo!")
    print("-" * 88)

    sns = boto3.resource("sns")
    sqs = boto3.resource("sqs")
    fifo_topic_wrapper = FifoTopicWrapper(sns)
    sns_wrapper = SnsWrapper(sns)

    prefix = "sqs-subscribe-demo-"
    queues = set()
    subscriptions = set()

    wholesale_queue = sqs.create_queue(
        QueueName=prefix + "wholesale.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(wholesale_queue)
```

```
    print(f"Created FIFO queue with URL: {wholesale_queue.url}.")

    retail_queue = sqs.create_queue(
        QueueName=prefix + "retail.fifo",
        Attributes={
            "MaximumMessageSize": str(4096),
            "ReceiveMessageWaitTimeSeconds": str(10),
            "VisibilityTimeout": str(300),
            "FifoQueue": str(True),
            "ContentBasedDeduplication": str(True),
        },
    )
    queues.add(retail_queue)
    print(f"Created FIFO queue with URL: {retail_queue.url}.")

    analytics_queue = sqs.create_queue(QueueName=prefix + "analytics",
Attributes={})
    queues.add(analytics_queue)
    print(f"Created standard queue with URL: {analytics_queue.url}.")

    topic = fifo_topic_wrapper.create_fifo_topic("price-updates-topic.fifo")
    print(f"Created FIFO topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        fifo_topic_wrapper.add_access_policy(q, topic.attributes["TopicArn"])

    print(f"Added access policies for topic: {topic.attributes['TopicArn']}.")

    for q in queues:
        sub = fifo_topic_wrapper.subscribe_queue_to_topic(
            topic, q.attributes["QueueArn"]
        )
        subscriptions.add(sub)

    print(f"Subscribed queues to topic: {topic.attributes['TopicArn']}.")

    input("Press Enter to publish a message to the topic.")

    message_id = fifo_topic_wrapper.publish_price_update(
        topic, '{"product": 214, "price": 79.99}', "Consumables"
    )

    print(f"Published price update with message ID: {message_id}.")
```

```
    # Clean up the subscriptions, queues, and topic.
    input("Press Enter to clean up resources.")
    for s in subscriptions:
        sns_wrapper.delete_subscription(s)

    sns_wrapper.delete_topic(topic)

    for q in queues:
        fifo_topic_wrapper.delete_queue(q)

    print(f"Deleted subscriptions, queues, and topic.")

    print("Thanks for watching!")
    print("-" * 88)



class FifoTopicWrapper:
    """Encapsulates Amazon SNS FIFO topic and subscription functions."""

    def __init__(self, sns_resource):
        """
        :param sns_resource: A Boto3 Amazon SNS resource.
        """
        self.sns_resource = sns_resource

    def create_fifo_topic(self, topic_name):
        """
        Create a FIFO topic.
        Topic names must be made up of only uppercase and lowercase ASCII letters,
        numbers, underscores, and hyphens, and must be between 1 and 256 characters
 long.
        For a FIFO topic, the name must end with the .fifo suffix.

        :param topic_name: The name for the topic.
        :return: The new topic.
        """
        try:
            topic = self.sns_resource.create_topic(
                Name=topic_name,
                Attributes={
                    "FifoTopic": str(True),
                    "ContentBasedDeduplication": str(False),
                },
```

```
            )
            logger.info("Created FIFO topic with name=%s.", topic_name)
            return topic
        except ClientError as error:
            logger.exception("Couldn't create topic with name=%s!", topic_name)
            raise error


    @staticmethod
    def add_access_policy(queue, topic_arn):
        """
        Add the necessary access policy to a queue, so
        it can receive messages from a topic.

        :param queue: The queue resource.
        :param topic_arn: The ARN of the topic.
        :return: None.
        """
        try:
            queue.set_attributes(
                Attributes={
                    "Policy": json.dumps(
                        {
                            "Version": "2012-10-17",
                            "Statement": [
                                {
                                    "Sid": "test-sid",
                                    "Effect": "Allow",
                                    "Principal": {"AWS": "*"},
                                    "Action": "SQS:SendMessage",
                                    "Resource": queue.attributes["QueueArn"],
                                    "Condition": {
                                        "ArnLike": {"aws:SourceArn": topic_arn}
                                    },
                                }
                            ],
                        }
                    )
                }
            )
            logger.info("Added trust policy to the queue.")
        except ClientError as error:
            logger.exception("Couldn't add trust policy to the queue!")
            raise error
```

```
    @staticmethod
    def subscribe_queue_to_topic(topic, queue_arn):
        """
        Subscribe a queue to a topic.

        :param topic: The topic resource.
        :param queue_arn: The ARN of the queue.
        :return: The subscription resource.
        """
        try:
            subscription = topic.subscribe(
                Protocol="sqs",
                Endpoint=queue_arn,
            )
            logger.info("The queue is subscribed to the topic.")
            return subscription
        except ClientError as error:
            logger.exception("Couldn't subscribe queue to topic!")
            raise error


    @staticmethod
    def publish_price_update(topic, payload, group_id):
        """
        Compose and publish a message that updates the wholesale price.

        :param topic: The topic to publish to.
        :param payload: The message to publish.
        :param group_id: The group ID for the message.
        :return: The ID of the message.
        """
        try:
            att_dict = {"business": {"DataType": "String", "StringValue":
 "wholesale"}}
            dedup_id = uuid.uuid4()
            response = topic.publish(
                Subject="Price Update",
                Message=payload,
                MessageAttributes=att_dict,
                MessageGroupId=group_id,
                MessageDeduplicationId=str(dedup_id),
            )
```

```
            message_id = response["MessageId"]
            logger.info("Published message to topic %s.", topic.arn)
        except ClientError as error:
            logger.exception("Couldn't publish message to topic %s.", topic.arn)
            raise error
        return message_id


    @staticmethod
    def delete_queue(queue):
        """
        Removes an SQS queue. When run against an AWS account, it can take up to
        60 seconds before the queue is actually deleted.

        :param queue: The queue to delete.
        :return: None
        """
        try:
            queue.delete()
            logger.info("Deleted queue with URL=%s.", queue.url)
        except ClientError as error:
            logger.exception("Couldn't delete queue with URL=%s!", queue.url)
            raise error
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateTopic
  - Publicar
  - Assinar

Enviar e receber lotes de mensagens

O código de exemplo a seguir mostra como:

- Como criar uma fila do Amazon SQS.
- Enviar lotes de mensagens a uma fila.
- Receber lotes de mensagens de uma fila.

- Excluir lotes de mensagens de uma fila.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Criar funções para encapsular funções de mensagem do Amazon SQS.

```
import logging
import sys

import boto3
from botocore.exceptions import ClientError

import queue_wrapper

logger = logging.getLogger(__name__)
sqs = boto3.resource("sqs")

def send_messages(queue, messages):
    """
    Send a batch of messages in a single request to an SQS queue.
    This request may return overall success even when some messages were not sent.
    The caller must inspect the Successful and Failed lists in the response and
    resend any failed messages.

    :param queue: The queue to receive the messages.
    :param messages: The messages to send to the queue. These are simplified to
                     contain only the message body and attributes.
    :return: The response from SQS that contains the list of successful and failed
             messages.
    """
    try:
        entries = [
            {
                "Id": str(ind),
                "MessageBody": msg["body"],
                "MessageAttributes": msg["attributes"],
```

```
            }
            for ind, msg in enumerate(messages)
        ]
        response = queue.send_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info(
                    "Message sent: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Failed to send: %s: %s",
                    msg_meta["MessageId"],
                    messages[int(msg_meta["Id"])]["body"],
                )
    except ClientError as error:
        logger.exception("Send messages failed to queue: %s", queue)
        raise error
    else:
        return response



def receive_messages(queue, max_number, wait_time):
    """
    Receive a batch of messages in a single request from an SQS queue.

    :param queue: The queue from which to receive messages.
    :param max_number: The maximum number of messages to receive. The actual number
                       of messages received might be less.
    :param wait_time: The maximum time to wait (in seconds) before returning. When
                      this number is greater than zero, long polling is used. This
                      can result in reduced costs and fewer false empty responses.
    :return: The list of Message objects received. These each contain the body
             of the message and metadata and custom attributes.
    """
    try:
        messages = queue.receive_messages(
            MessageAttributeNames=["All"],
            MaxNumberOfMessages=max_number,
            WaitTimeSeconds=wait_time,
```

```
        )
        for msg in messages:
            logger.info("Received message: %s: %s", msg.message_id, msg.body)
    except ClientError as error:
        logger.exception("Couldn't receive messages from queue: %s", queue)
        raise error
    else:
        return messages



def delete_messages(queue, messages):
    """
    Delete a batch of messages from a queue in a single request.

    :param queue: The queue from which to delete the messages.
    :param messages: The list of messages to delete.
    :return: The response from SQS that contains the list of successful and failed
             message deletions.
    """
    try:
        entries = [
            {"Id": str(ind), "ReceiptHandle": msg.receipt_handle}
            for ind, msg in enumerate(messages)
        ]
        response = queue.delete_messages(Entries=entries)
        if "Successful" in response:
            for msg_meta in response["Successful"]:
                logger.info("Deleted %s",
 messages[int(msg_meta["Id"])].receipt_handle)
        if "Failed" in response:
            for msg_meta in response["Failed"]:
                logger.warning(
                    "Could not delete %s",
 messages[int(msg_meta["Id"])].receipt_handle
                )
    except ClientError:
        logger.exception("Couldn't delete messages from queue %s", queue)
    else:
        return response
```

Usar as funções de wrapper para enviar e receber mensagens em lotes.

```
def usage_demo():
    """
    Shows how to:
    * Read the lines from this Python file and send the lines in
      batches of 10 as messages to a queue.
    * Receive the messages in batches until the queue is empty.
    * Reassemble the lines of the file and verify they match the original file.
    """

    def pack_message(msg_path, msg_body, msg_line):
        return {
            "body": msg_body,
            "attributes": {
                "path": {"StringValue": msg_path, "DataType": "String"},
                "line": {"StringValue": str(msg_line), "DataType": "String"},
            },
        }

    def unpack_message(msg):
        return (
            msg.message_attributes["path"]["StringValue"],
            msg.body,
            int(msg.message_attributes["line"]["StringValue"]),
        )

    print("-" * 88)
    print("Welcome to the Amazon Simple Queue Service (Amazon SQS) demo!")
    print("-" * 88)

    queue = queue_wrapper.create_queue("sqs-usage-demo-message-wrapper")

    with open(__file__) as file:
        lines = file.readlines()

    line = 0
    batch_size = 10
    received_lines = [None] * len(lines)
    print(f"Sending file lines in batches of {batch_size} as messages.")
    while line < len(lines):
        messages = [
            pack_message(__file__, lines[index], index)
            for index in range(line, min(line + batch_size, len(lines)))
```

```
        ]
        line = line + batch_size
        send_messages(queue, messages)
        print(".", end="")
        sys.stdout.flush()
    print(f"Done. Sent {len(lines) - 1} messages.")

    print(f"Receiving, handling, and deleting messages in batches of {batch_size}.")
    more_messages = True
    while more_messages:
        received_messages = receive_messages(queue, batch_size, 2)
        print(".", end="")
        sys.stdout.flush()
        for message in received_messages:
            path, body, line = unpack_message(message)
            received_lines[line] = body
        if received_messages:
            delete_messages(queue, received_messages)
        else:
            more_messages = False
    print("Done.")

    if all([lines[index] == received_lines[index] for index in range(len(lines))]):
        print(f"Successfully reassembled all file lines!")
    else:
        print(f"Uh oh, some lines were missed!")

    queue.delete()

    print("Thanks for watching!")
    print("-" * 88)
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateQueue
  - DeleteMessageBatch
  - DeleteQueue
  - ReceiveMessage

- SendMessageBatch

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Python.

```
def lambda_handler(event, context):
    for message in event['Records']:
        process_message(message)
    print("done")

def process_message(message):
    try:
        print(f"Processed message {message['body']}")
        # TODO: Do interesting work based on the new message
    except Exception as err:
        print("An error occurred")
        raise err
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Python.

```
import json
def lambda_handler(event, context):
    if event:
        batch_item_failures = []
        sqs_batch_response = {}

        for record in event["Records"]:
            try:
                # process message
            except Exception as e:
                batch_item_failures.append({"itemIdentifier": record['messageId']})

        sqs_batch_response["batchItemFailures"] = batch_item_failures
        return sqs_batch_response
```

Exemplos do Step Functions usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Step Functions.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, Step Functions

O exemplo de código a seguir mostra como começar a usar o Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import boto3


def hello_stepfunctions(stepfunctions_client):
    """
    Use the AWS SDK for Python (Boto3) to create an AWS Step Functions client and
 list
    the state machines in your account. This list might be empty if you haven't
 created
    any state machines.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param stepfunctions_client: A Boto3 Step Functions Client object.
    """
    print("Hello, Step Functions! Let's list up to 10 of your state machines:")
    state_machines = stepfunctions_client.list_state_machines(maxResults=10)
    for sm in state_machines["stateMachines"]:
        print(f"\t{sm['name']}: {sm['stateMachineArn']}")


if __name__ == "__main__":
    hello_stepfunctions(boto3.client("stepfunctions"))
```

- Para obter detalhes da API, consulte a ListStateMachinesReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Criar uma máquina de estado

O exemplo de código a seguir mostra como criar uma máquina de estado do Step Functions.

SDK para Python (Boto3)

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name, definition, role_arn):
        """
        Creates a state machine with the specific definition. The state machine
 assumes
        the provided role before it starts a run.

        :param name: The name to give the state machine.
        :param definition: The Amazon States Language definition of the steps in the
                           the state machine.
        :param role_arn: The Amazon Resource Name (ARN) of the role that is assumed
 by
                         Step Functions when the state machine is run.
        :return: The ARN of the newly created state machine.
        """
```

```
        try:
            response = self.stepfunctions_client.create_state_machine(
                name=name, definition=definition, roleArn=role_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't create state machine %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["stateMachineArn"]
```

- Para obter detalhes da API, consulte a CreateStateMachineReferência da API AWSSDK for Python (Boto3).

Criar uma atividade

O exemplo de código a seguir mostra como criar uma atividade do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client
```

```
    def create(self, name):
        """
        Create an activity.

        :param name: The name of the activity to create.
        :return: The Amazon Resource Name (ARN) of the newly created activity.
        """
        try:
            response = self.stepfunctions_client.create_activity(name=name)
        except ClientError as err:
            logger.error(
                "Couldn't create activity %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["activityArn"]
```

- Para obter detalhes da API, consulte a CreateActivityReferência da API AWSSDK for Python (Boto3).

Excluir uma máquina de estado

O exemplo de código a seguir mostra como excluir uma máquina de estado do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
```

```
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def delete(self, state_machine_arn):
        """
        Delete a state machine and all of its run data.

        :param state_machine_arn: The ARN of the state machine to delete.
        """
        try:
            response = self.stepfunctions_client.delete_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteStateMachineReferência da API AWSSDK for Python (Boto3).

Excluir uma atividade.

Os exemplos de código a seguir mostram como excluir uma atividade do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def delete(self, activity_arn):
        """
        Delete an activity.

        :param activity_arn: The ARN of the activity to delete.
        """
        try:
            response = self.stepfunctions_client.delete_activity(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DeleteActivityReferência da API AWSSDK for Python (Boto3).

Descrever uma máquina de estado

O exemplo de código a seguir mostra como descrever uma máquina de estado do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def describe(self, state_machine_arn):
        """
        Get data about a state machine.

        :param state_machine_arn: The ARN of the state machine to look up.
        :return: The retrieved state machine data.
        """
        try:
            response = self.stepfunctions_client.describe_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeStateMachineReferência da API AWSSDK for Python (Boto3).

Descrever a execução de uma máquina de estado

O exemplo de código a seguir mostra como descrever uma execução de máquina de estado do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    def describe_run(self, run_arn):
        """
        Get data about a state machine run, such as its current status or final
output.

        :param run_arn: The ARN of the run to look up.
        :return: The retrieved run data.
        """
        try:
            response = self.stepfunctions_client.describe_execution(
                executionArn=run_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe run %s. Here's why: %s: %s",
                run_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DescribeExecutionReferência da API AWSSDK for Python (Boto3).

Obter dados de tarefas para uma atividade

O exemplo de código a seguir mostra como obter dados de tarefa para uma atividade de Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def get_task(self, activity_arn):
        """
        Gets task data for an activity. When a state machine is waiting for the
        specified activity, a response is returned with data from the state machine.
        When a state machine is not waiting, this call blocks for 60 seconds.

        :param activity_arn: The ARN of the activity to get task data for.
        :return: The task data for the activity.
        """
        try:
            response = self.stepfunctions_client.get_activity_task(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
```

```
                "Couldn't get a task for activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetActivityTaskReferência da API AWSSDK for Python (Boto3).

Listar atividades

O exemplo de código a seguir mostra como listar atividades do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def find(self, name):
        """
        Find an activity by name. This requires listing activities until one is
 found
        with a matching name.
```

```
        :param name: The name of the activity to search for.
        :return: If found, the ARN of the activity; otherwise, None.
        """
        try:
            paginator = self.stepfunctions_client.get_paginator("list_activities")
            for page in paginator.paginate():
                for activity in page.get("activities", []):
                    if activity["name"] == name:
                        return activity["activityArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list activities. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListActivitiesReferência da API AWSSDK for Python (Boto3).

Listar máquinas de estado

O exemplo de código a seguir mostra como listar estado de máquinas do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Encontrar uma máquina de estado pelo nome pesquisando a lista de máquinas de estado da conta.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""
```

```
    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def find(self, name):
        """
        Find a state machine by name. This requires listing the state machines until
        one is found with a matching name.

        :param name: The name of the state machine to search for.
        :return: The ARN of the state machine if found; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_state_machines")
            for page in paginator.paginate():
                for state_machine in page.get("stateMachines", []):
                    if state_machine["name"] == name:
                        return state_machine["stateMachineArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list state machines. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a ListStateMachinesReferência da API AWSSDK for Python (Boto3).

Enviar uma resposta bem-sucedida para uma tarefa

O exemplo de código a seguir mostra como enviar uma resposta de sucesso para uma tarefa de Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def send_task_success(self, task_token, task_response):
        """
        Sends a success response to a waiting activity step. A state machine with an
        activity step waits for the activity to get task data and then respond with
        either success or failure before it resumes processing.

        :param task_token: The token associated with the task. This is included in
 the
                           response to the get_activity_task action and must be sent
                           without modification.
        :param task_response: The response data from the activity. This data is
                              received and processed by the state machine.
        """
        try:
            self.stepfunctions_client.send_task_success(
                taskToken=task_token, output=task_response
            )
        except ClientError as err:
            logger.error(
                "Couldn't send task success. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
```

- Para obter detalhes da API, consulte a SendTaskSuccessReferência da API AWSSDK for Python (Boto3).

Iniciar execução de máquina de estado

O exemplo de código a seguir mostra como iniciar uma execução de máquina de estado do Step Functions.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def start(self, state_machine_arn, run_input):
        """
        Start a run of a state machine with a specified input. A run is also known
        as an "execution" in Step Functions.

        :param state_machine_arn: The ARN of the state machine to run.
        :param run_input: The input to the state machine, in JSON format.
        :return: The ARN of the run. This can be used to get information about the
 run,
                 including its current status and final output.
        """
        try:
```

```
            response = self.stepfunctions_client.start_execution(
                stateMachineArn=state_machine_arn, input=run_input
            )
        except ClientError as err:
            logger.error(
                "Couldn't start state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["executionArn"]
```

- Para obter detalhes da API, consulte a StartExecutionReferência da API AWSSDK for Python (Boto3).

Cenários

Começar a usar máquinas de estado

O código de exemplo a seguir mostra como:

- Criar uma atividade.
- Criar uma máquina de estado a partir de uma definição da Amazon States Language que contenha a atividade criada anteriormente como uma etapa.
- Executar a máquina de estado e responder à atividade com entrada do usuário.
- Obter o status e a saída finais após a conclusão da execução e, em seguida, limpar os recursos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class StateMachineScenario:
    """Runs an interactive scenario that shows how to get started using Step
 Functions."""

    def __init__(self, activity, state_machine, iam_client):
        """
        :param activity: An object that wraps activity actions.
        :param state_machine: An object that wraps state machine actions.
        :param iam_client: A Boto3 AWS Identity and Access Management (IAM) client.
        """
        self.activity = activity
        self.state_machine = state_machine
        self.iam_client = iam_client
        self.state_machine_role = None

    def prerequisites(self, state_machine_role_name):
        """
        Finds or creates an IAM role that can be assumed by Step Functions.
        A role of this kind is required to create a state machine.
        The state machine used in this example does not call any additional
 services,
        so it needs no additional permissions.

        :param state_machine_role_name: The name of the role.
        :return: Data about the role.
        """
        trust_policy = {
            "Version": "2012-10-17",
            "Statement": [
                {
                    "Sid": "",
                    "Effect": "Allow",
                    "Principal": {"Service": "states.amazonaws.com"},
                    "Action": "sts:AssumeRole",
                }
            ],
        }
        try:
            role = self.iam_client.get_role(RoleName=state_machine_role_name)
            print(f"Prerequisite IAM role {state_machine_role_name} already
 exists.")
        except ClientError as err:
            if err.response["Error"]["Code"] == "NoSuchEntity":
```

```
                role = None
            else:
                logger.error(
                    "Couldn't get prerequisite IAM role %s. Here's why: %s: %s",
                    state_machine_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        if role is None:
            try:
                role = self.iam_client.create_role(
                    RoleName=state_machine_role_name,
                    AssumeRolePolicyDocument=json.dumps(trust_policy),
                )
            except ClientError as err:
                logger.error(
                    "Couldn't create prerequisite IAM role %s. Here's why: %s: %s",
                    state_machine_role_name,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        self.state_machine_role = role["Role"]

    def find_or_create_activity(self, activity_name):
        """
        Finds or creates a Step Functions activity.

        :param activity_name: The name of the activity.
        :return: The Amazon Resource Name (ARN) of the activity.
        """
        print("First, let's set up an activity and state machine.")
        activity_arn = self.activity.find(activity_name)
        if activity_arn is None:
            activity_arn = self.activity.create(activity_name)
            print(
                f"Activity {activity_name} created. Its Amazon Resource Name (ARN)
is "
                f"{activity_arn}."
            )
        else:
            print(f"Activity {activity_name} already exists.")
        return activity_arn
```

```
    def find_or_create_state_machine(
        self, state_machine_name, activity_arn, state_machine_file
    ):
        """
        Finds or creates a Step Functions state machine.

        :param state_machine_name: The name of the state machine.
        :param activity_arn: The ARN of an activity that is used as a step in the
state
                             machine. This ARN is injected into the state machine
                             definition that's used to create the state machine.
        :param state_machine_file: The path to a file containing the state machine
                                   definition.
        :return: The ARN of the state machine.
        """
        state_machine_arn = self.state_machine.find(state_machine_name)
        if state_machine_arn is None:
            with open(state_machine_file) as state_machine_file:
                state_machine_def = state_machine_file.read().replace(
                    "{{DOC_EXAMPLE_ACTIVITY_ARN}}", activity_arn
                )
                state_machine_arn = self.state_machine.create(
                    state_machine_name,
                    state_machine_def,
                    self.state_machine_role["Arn"],
                )
            print(f"State machine {state_machine_name} created.")
        else:
            print(f"State machine {state_machine_name} already exists.")
        print("-" * 88)
        print(f"Here's some information about state machine {state_machine_name}:")
        state_machine_info = self.state_machine.describe(state_machine_arn)
        for field in ["name", "status", "stateMachineArn", "roleArn"]:
            print(f"\t{field}: {state_machine_info[field]}")
        return state_machine_arn

    def run_state_machine(self, state_machine_arn, activity_arn):
        """
        Run the state machine. The state machine used in this example is a simple
        chat simulation. It contains an activity step in a loop that is used for
user
        interaction. When the state machine gets to the activity step, it waits for
```

```
        an external application to get task data and submit a response. This
function
        acts as the activity application by getting task input and responding with
        user input.

        :param state_machine_arn: The ARN of the state machine.
        :param activity_arn: The ARN of the activity used as a step in the state
machine.
        :return: The ARN of the run.
        """
        print(
            f"Let's run the state machine. It's a simplistic, non-AI chat simulator
"
            f"we'll call ChatSFN."
        )
        user_name = q.ask("What should ChatSFN call you? ", q.non_empty)
        run_input = {"name": user_name}
        print("Starting state machine...")
        run_arn = self.state_machine.start(state_machine_arn, json.dumps(run_input))
        action = None
        while action != "done":
            activity_task = self.activity.get_task(activity_arn)
            task_input = json.loads(activity_task["input"])
            print(f"ChatSFN: {task_input['message']}")
            action = task_input["actions"][
                q.choose("What now? ", task_input["actions"])
            ]
            task_response = {"action": action}
            self.activity.send_task_success(
                activity_task["taskToken"], json.dumps(task_response)
            )
        return run_arn

    def finish_state_machine_run(self, run_arn):
        """
        Wait for the state machine run to finish, then print final status and
output.

        :param run_arn: The ARN of the run to retrieve.
        """
        print(f"Let's get the final output from the state machine:")
        status = "RUNNING"
        while status == "RUNNING":
            run_output = self.state_machine.describe_run(run_arn)
```

```
            status = run_output["status"]
            if status == "RUNNING":
                print(
                    "The state machine is still running, let's wait for it to
finish."
                )
                wait(1)
            elif status == "SUCCEEDED":
                print(f"ChatSFN: {json.loads(run_output['output'])['message']}")
            else:
                print(f"Run status: {status}.")

    def cleanup(
        self,
        state_machine_name,
        state_machine_arn,
        activity_name,
        activity_arn,
        state_machine_role_name,
    ):
        """
        Clean up resources created by this example.

        :param state_machine_name: The name of the state machine.
        :param state_machine_arn: The ARN of the state machine.
        :param activity_name: The name of the activity.
        :param activity_arn: The ARN of the activity.
        :param state_machine_role_name: The name of the role used by the state
machine.
        """
        if q.ask(
            "Do you want to delete the state machine, activity, and role created for
this "
            "example? (y/n) ",
            q.is_yesno,
        ):
            self.state_machine.delete(state_machine_arn)
            print(f"Deleted state machine {state_machine_name}.")
            self.activity.delete(activity_arn)
            print(f"Deleted activity {activity_name}.")
            self.iam_client.delete_role(RoleName=state_machine_role_name)
            print(f"Deleted role {state_machine_role_name}.")

    def run_scenario(self, activity_name, state_machine_name):
```

```
        print("-" * 88)
        print("Welcome to the AWS Step Functions state machines demo.")
        print("-" * 88)

        activity_arn = self.find_or_create_activity(activity_name)
        state_machine_arn = self.find_or_create_state_machine(
            state_machine_name,
            activity_arn,
            "../../../resources/sample_files/chat_sfn_state_machine.json",
        )
        print("-" * 88)
        run_arn = self.run_state_machine(state_machine_arn, activity_arn)
        print("-" * 88)
        self.finish_state_machine_run(run_arn)
        print("-" * 88)
        self.cleanup(
            state_machine_name,
            state_machine_arn,
            activity_name,
            activity_arn,
            self.state_machine_role["RoleName"],
        )

        print("-" * 88)
        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")
    try:
        stepfunctions_client = boto3.client("stepfunctions")
        iam_client = boto3.client("iam")
        scenario = StateMachineScenario(
            Activity(stepfunctions_client),
            StateMachine(stepfunctions_client),
            iam_client,
        )
        scenario.prerequisites("doc-example-state-machine-chat")
        scenario.run_scenario("doc-example-activity", "doc-example-state-machine")
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Definir uma classe que envolva as ações de máquina de estado.

```
class StateMachine:
    """Encapsulates Step Functions state machine actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client


    def create(self, name, definition, role_arn):
        """
        Creates a state machine with the specific definition. The state machine
 assumes
        the provided role before it starts a run.

        :param name: The name to give the state machine.
        :param definition: The Amazon States Language definition of the steps in the
                           the state machine.
        :param role_arn: The Amazon Resource Name (ARN) of the role that is assumed
 by
                         Step Functions when the state machine is run.
        :return: The ARN of the newly created state machine.
        """
        try:
            response = self.stepfunctions_client.create_state_machine(
                name=name, definition=definition, roleArn=role_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't create state machine %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["stateMachineArn"]


    def find(self, name):
        """
```

```
        Find a state machine by name. This requires listing the state machines until
        one is found with a matching name.

        :param name: The name of the state machine to search for.
        :return: The ARN of the state machine if found; otherwise, None.
        """
        try:
            paginator =
self.stepfunctions_client.get_paginator("list_state_machines")
            for page in paginator.paginate():
                for state_machine in page.get("stateMachines", []):
                    if state_machine["name"] == name:
                        return state_machine["stateMachineArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list state machines. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def describe(self, state_machine_arn):
        """
        Get data about a state machine.

        :param state_machine_arn: The ARN of the state machine to look up.
        :return: The retrieved state machine data.
        """
        try:
            response = self.stepfunctions_client.describe_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

```
    def start(self, state_machine_arn, run_input):
        """
        Start a run of a state machine with a specified input. A run is also known
        as an "execution" in Step Functions.

        :param state_machine_arn: The ARN of the state machine to run.
        :param run_input: The input to the state machine, in JSON format.
        :return: The ARN of the run. This can be used to get information about the
run,
                 including its current status and final output.
        """
        try:
            response = self.stepfunctions_client.start_execution(
                stateMachineArn=state_machine_arn, input=run_input
            )
        except ClientError as err:
            logger.error(
                "Couldn't start state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["executionArn"]


    def describe_run(self, run_arn):
        """
        Get data about a state machine run, such as its current status or final
output.

        :param run_arn: The ARN of the run to look up.
        :return: The retrieved run data.
        """
        try:
            response = self.stepfunctions_client.describe_execution(
                executionArn=run_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't describe run %s. Here's why: %s: %s",
                run_arn,
```

```
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def delete(self, state_machine_arn):
        """
        Delete a state machine and all of its run data.

        :param state_machine_arn: The ARN of the state machine to delete.
        """
        try:
            response = self.stepfunctions_client.delete_state_machine(
                stateMachineArn=state_machine_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete state machine %s. Here's why: %s: %s",
                state_machine_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

Definir uma classe que envolva as ações de atividade.

```
class Activity:
    """Encapsulates Step Function activity actions."""

    def __init__(self, stepfunctions_client):
        """
        :param stepfunctions_client: A Boto3 Step Functions client.
        """
        self.stepfunctions_client = stepfunctions_client
```

```
    def create(self, name):
        """
        Create an activity.

        :param name: The name of the activity to create.
        :return: The Amazon Resource Name (ARN) of the newly created activity.
        """
        try:
            response = self.stepfunctions_client.create_activity(name=name)
        except ClientError as err:
            logger.error(
                "Couldn't create activity %s. Here's why: %s: %s",
                name,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response["activityArn"]


    def find(self, name):
        """
        Find an activity by name. This requires listing activities until one is
found
        with a matching name.

        :param name: The name of the activity to search for.
        :return: If found, the ARN of the activity; otherwise, None.
        """
        try:
            paginator = self.stepfunctions_client.get_paginator("list_activities")
            for page in paginator.paginate():
                for activity in page.get("activities", []):
                    if activity["name"] == name:
                        return activity["activityArn"]
        except ClientError as err:
            logger.error(
                "Couldn't list activities. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
```

```
            raise


    def get_task(self, activity_arn):
        """
        Gets task data for an activity. When a state machine is waiting for the
        specified activity, a response is returned with data from the state machine.
        When a state machine is not waiting, this call blocks for 60 seconds.

        :param activity_arn: The ARN of the activity to get task data for.
        :return: The task data for the activity.
        """
        try:
            response = self.stepfunctions_client.get_activity_task(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't get a task for activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response


    def send_task_success(self, task_token, task_response):
        """
        Sends a success response to a waiting activity step. A state machine with an
        activity step waits for the activity to get task data and then respond with
        either success or failure before it resumes processing.

        :param task_token: The token associated with the task. This is included in
the
                           response to the get_activity_task action and must be sent
                           without modification.
        :param task_response: The response data from the activity. This data is
                              received and processed by the state machine.
        """
        try:
            self.stepfunctions_client.send_task_success(
                taskToken=task_token, output=task_response
```

```
            )
        except ClientError as err:
            logger.error(
                "Couldn't send task success. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


    def delete(self, activity_arn):
        """
        Delete an activity.

        :param activity_arn: The ARN of the activity to delete.
        """
        try:
            response = self.stepfunctions_client.delete_activity(
                activityArn=activity_arn
            )
        except ClientError as err:
            logger.error(
                "Couldn't delete activity %s. Here's why: %s: %s",
                activity_arn,
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateActivity
  - CreateStateMachine
  - DeleteActivity
  - DeleteStateMachine

- DescribeExecution
- DescribeStateMachine
- GetActivityTask
- ListActivities
- ListStateMachines
- SendTaskSuccess
- StartExecution
- StopExecution

Organize aplicativos generativos de IA com Step Functions

O exemplo de código a seguir mostra como criar e orquestrar aplicativos generativos de IA com o Amazon Bedrock e o Step Functions.

SDK para Python (Boto3)

O cenário Amazon Bedrock Serverless Prompt Chaining demonstra como AWS Step Functionso Amazon Bedrock e os Agents for Amazon Bedrock podem ser usados para criar e orquestrar aplicativos de IA generativa complexos, sem servidor e altamente escaláveis. Ele contém os seguintes exemplos de trabalho:

- Escreva uma análise de um determinado romance para um blog de literatura. Este exemplo ilustra uma cadeia de solicitações simples e sequencial.
- Gere uma história curta sobre um determinado tópico. Este exemplo ilustra como a IA pode processar iterativamente uma lista de itens que ela gerou anteriormente.
- Crie um itinerário para férias de fim de semana em um determinado destino. Este exemplo ilustra como paralelizar vários prompts distintos.
- Apresente ideias de filmes para um usuário humano atuando como produtor de filmes. Este exemplo ilustra como paralelizar o mesmo prompt com diferentes parâmetros de inferência, como voltar a uma etapa anterior na cadeia e como incluir a entrada humana como parte do fluxo de trabalho.
- Planeje uma refeição com base nos ingredientes que o usuário tem em mãos. Este exemplo ilustra como cadeias imediatas podem incorporar duas conversas distintas de IA, com duas personas de IA participando de um debate entre si para melhorar o resultado final.
- Encontre e resuma o repositório mais popular GitHub da atualidade. Este exemplo ilustra o encadeamento de vários agentes de IA que interagem com APIs externas.

Para obter o código-fonte completo e as instruções de configuração e execução, consulte o projeto completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Bedrock
- Amazon Bedrock Runtime
- Agentes do Amazon Bedrock
- Agentes do Amazon Bedrock Runtime
- Step Functions

Exemplos de AWS STS usando o SDK para Python (Boto3)

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Assuma um perfil do IAM que exija um token de MFA e use credenciais temporárias para listar buckets do Amazon S3 para a conta.

```
def list_buckets_from_assumed_role_with_mfa(
    assume_role_arn, session_name, mfa_serial_number, mfa_totp, sts_client
):
    """
    Assumes a role from another account and uses the temporary credentials from
    that role to list the Amazon S3 buckets that are owned by the other account.
    Requires an MFA device serial number and token.

    The assumed role must grant permission to list the buckets in the other account.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    :param mfa_serial_number: The serial number of the MFA device. For a virtual MFA
                              device, this is an ARN.
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the role.
    """
    response = sts_client.assume_role(
        RoleArn=assume_role_arn,
        RoleSessionName=session_name,
        SerialNumber=mfa_serial_number,
        TokenCode=mfa_totp,
    )
    temp_credentials = response["Credentials"]
    print(f"Assumed role {assume_role_arn} and got temporary credentials.")

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
```

```
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Listing buckets for the assumed role's account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Obter um token de sessão

O exemplo de código a seguir mostra como obter um token de sessão com o AWS STS e usá-lo para realizar uma ação de serviço que exija um token de MFA.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Obtenha um token de sessão passando um token de MFA e use-o para listar buckets do Amazon S3 para a conta.

```
def list_buckets_with_session_token_with_mfa(mfa_serial_number, mfa_totp,
 sts_client):
    """
    Gets a session token with MFA credentials and uses the temporary session
    credentials to list Amazon S3 buckets.

    Requires an MFA device serial number and token.

    :param mfa_serial_number: The serial number of the MFA device. For a virtual MFA
                              device, this is an Amazon Resource Name (ARN).
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the role.
```

```
    """
    if mfa_serial_number is not None:
        response = sts_client.get_session_token(
            SerialNumber=mfa_serial_number, TokenCode=mfa_totp
        )
    else:
        response = sts_client.get_session_token()
    temp_credentials = response["Credentials"]

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Buckets for the account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

- Para obter detalhes da API, consulte a GetSessionTokenReferência da API AWSSDK for Python (Boto3).

Cenários

Assumir um perfil do IAM que exija um token de MFA

O exemplo de código a seguir mostra como assumir um perfil que exige um token de MFA.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar um perfil do IAM que conceda permissão para listar os buckets do Amazon S3.

- Criar um usuário do IAM que tenha permissão para assumir o perfil somente quando as credenciais de MFA forem fornecidas.
- Registrar um dispositivo MFA para o usuário.
- Assumir o perfil e usar credenciais temporárias para listar buckets do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um usuário do IAM, registre um dispositivo de MFA e crie um perfil que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função.

```
def setup(iam_resource):
    """
    Creates a new user with no permissions.
    Creates a new virtual MFA device.
    Displays the QR code to seed the device.
    Asks for two codes from the MFA device.
    Registers the MFA device for the user.
    Creates an access key pair for the user.
    Creates a role with a policy that lets the user assume the role and requires
 MFA.
    Creates a policy that allows listing Amazon S3 buckets.
    Attaches the policy to the role.
    Creates an inline policy for the user that lets the user assume the role.

    For demonstration purposes, the user is created in the same account as the role,
    but in practice the user would likely be from another account.

    Any MFA device that can scan a QR code will work with this demonstration.
    Common choices are mobile apps like LastPass Authenticator,
    Microsoft Authenticator, or Google Authenticator.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM) resource
                         that has permissions to create users, roles, and policies
                         in the account.
    :return: The newly created user, user key, virtual MFA device, and role.
```

```
    """
    user = iam_resource.create_user(UserName=unique_name("user"))
    print(f"Created user {user.name}.")

    virtual_mfa_device = iam_resource.create_virtual_mfa_device(
        VirtualMFADeviceName=unique_name("mfa")
    )
    print(f"Created virtual MFA device {virtual_mfa_device.serial_number}")

    print(
        f"Showing the QR code for the device. Scan this in the MFA app of your "
        f"choice."
    )
    with open("qr.png", "wb") as qr_file:
        qr_file.write(virtual_mfa_device.qr_code_png)
    webbrowser.open(qr_file.name)

    print(f"Enter two consecutive code from your MFA device.")
    mfa_code_1 = input("Enter the first code: ")
    mfa_code_2 = input("Enter the second code: ")
    user.enable_mfa(
        SerialNumber=virtual_mfa_device.serial_number,
        AuthenticationCode1=mfa_code_1,
        AuthenticationCode2=mfa_code_2,
    )
    os.remove(qr_file.name)
    print(f"MFA device is registered with the user.")

    user_key = user.create_access_key_pair()
    print(f"Created access key pair for user.")

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    role = iam_resource.create_role(
        RoleName=unique_name("role"),
        AssumeRolePolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Principal": {"AWS": user.arn},
                        "Action": "sts:AssumeRole",
```

```
                        "Condition": {"Bool": {"aws:MultiFactorAuthPresent": True}},
                    }
                ],
            }
        ),
    )
    print(f"Created role {role.name} that requires MFA.")

    policy = iam_resource.create_policy(
        PolicyName=unique_name("policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Action": "s3:ListAllMyBuckets",
                        "Resource": "arn:aws:s3:::*",
                    }
                ],
            }
        ),
    )
    role.attach_policy(PolicyArn=policy.arn)
    print(f"Created policy {policy.policy_name} and attached it to the role.")

    user.create_policy(
        PolicyName=unique_name("user-policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Action": "sts:AssumeRole",
                        "Resource": role.arn,
                    }
                ],
            }
        ),
    )
    print(
        f"Created an inline policy for {user.name} that lets the user assume "
        f"the role."
```

```
    )

    print("Give AWS time to propagate these new resources and connections.", end="")
    progress_bar(10)

    return user, user_key, virtual_mfa_device, role
```

Mostre que não é permitido assumir uma função sem um token de MFA.

```
def try_to_assume_role_without_mfa(assume_role_arn, session_name, sts_client):
    """
    Shows that attempting to assume the role without sending MFA credentials results
    in an AccessDenied error.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role to assume.
    :param session_name: The name of the STS session.
    :param sts_client: A Boto3 STS instance that has permission to assume the role.
    """
    print(f"Trying to assume the role without sending MFA credentials...")
    try:
        sts_client.assume_role(RoleArn=assume_role_arn,
 RoleSessionName=session_name)
        raise RuntimeError("Expected AccessDenied error.")
    except ClientError as error:
        if error.response["Error"]["Code"] == "AccessDenied":
            print("Got AccessDenied.")
        else:
            raise
```

Assuma o perfil que concede permissão para listar buckets do S3 passando o token de MFA necessário e mostre que os buckets podem ser listados.

```
def list_buckets_from_assumed_role_with_mfa(
    assume_role_arn, session_name, mfa_serial_number, mfa_totp, sts_client
):
    """
    Assumes a role from another account and uses the temporary credentials from
```

```
    that role to list the Amazon S3 buckets that are owned by the other account.
    Requires an MFA device serial number and token.

    The assumed role must grant permission to list the buckets in the other account.

    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                            grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    :param mfa_serial_number: The serial number of the MFA device. For a virtual MFA
                              device, this is an ARN.
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the role.
    """
    response = sts_client.assume_role(
        RoleArn=assume_role_arn,
        RoleSessionName=session_name,
        SerialNumber=mfa_serial_number,
        TokenCode=mfa_totp,
    )
    temp_credentials = response["Credentials"]
    print(f"Assumed role {assume_role_arn} and got temporary credentials.")

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )

    print(f"Listing buckets for the assumed role's account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

Destrua os recursos criados para a demonstração.

```
def teardown(user, virtual_mfa_device, role):
    """
    Removes all resources created during setup.

    :param user: The demo user.
```

```
    :param role: The demo role.
    """
    for attached in role.attached_policies.all():
        policy_name = attached.policy_name
        role.detach_policy(PolicyArn=attached.arn)
        attached.delete()
        print(f"Detached and deleted {policy_name}.")
    role.delete()
    print(f"Deleted {role.name}.")
    for user_pol in user.policies.all():
        user_pol.delete()
        print("Deleted inline user policy.")
    for key in user.access_keys.all():
        key.delete()
        print("Deleted user's access key.")
    for mfa in user.mfa_devices.all():
        mfa.disassociate()
    virtual_mfa_device.delete()
    user.delete()
    print(f"Deleted {user.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(
        f"Welcome to the AWS Security Token Service assume role demo, "
        f"starring multi-factor authentication (MFA)!"
    )
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    user, user_key, virtual_mfa_device, role = setup(iam_resource)
    print(f"Created {user.name} and {role.name}.")
    try:
        sts_client = boto3.client(
            "sts", aws_access_key_id=user_key.id,
 aws_secret_access_key=user_key.secret
        )
        try_to_assume_role_without_mfa(role.arn, "demo-sts-session", sts_client)
```

```
        mfa_totp = input("Enter the code from your registered MFA device: ")
        list_buckets_from_assumed_role_with_mfa(
            role.arn,
            "demo-sts-session",
            virtual_mfa_device.serial_number,
            mfa_totp,
            sts_client,
        )
    finally:
        teardown(user, virtual_mfa_device, role)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Criar um URL para usuários federados usando

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM que conceda acesso somente leitura aos recursos do Amazon S3 da conta atual.
- Obtenha um token de segurança do endpoint de federação da AWS.
- Crie um URL que possa ser usado para acessar o console com credenciais federadas.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um perfil que conceda acesso somente leitura aos recursos do S3 da conta atual.

```
def setup(iam_resource):
    """
    Creates a role that can be assumed by the current user.
```

```
    Attaches a policy that allows only Amazon S3 read-only access.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM) instance
                         that has the permission to create a role.
    :return: The newly created role.
    """
    role = iam_resource.create_role(
        RoleName=unique_name("role"),
        AssumeRolePolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Principal": {"AWS": iam_resource.CurrentUser().arn},
                        "Action": "sts:AssumeRole",
                    }
                ],
            }
        ),
    )
    role.attach_policy(PolicyArn="arn:aws:iam::aws:policy/AmazonS3ReadOnlyAccess")
    print(f"Created role {role.name}.")

    print("Give AWS time to propagate these new resources and connections.", end="")
    progress_bar(10)

    return role
```

Obtenha um token de segurança do endpoint de federação da AWS e crie um URL que possa ser usado para acessar o console com credenciais federadas.

```
def construct_federated_url(assume_role_arn, session_name, issuer, sts_client):
    """
    Constructs a URL that gives federated users direct access to the AWS Management
    Console.

    1. Acquires temporary credentials from AWS Security Token Service (AWS STS) that
       can be used to assume a role with limited permissions.
    2. Uses the temporary credentials to request a sign-in token from the
```

```
      AWS federation endpoint.
   3. Builds a URL that can be used in a browser to navigate to the AWS federation
      endpoint, includes the sign-in token for authentication, and redirects to
      the AWS Management Console with permissions defined by the role that was
      specified in step 1.

   :param assume_role_arn: The role that specifies the permissions that are
granted.
                           The current user must have permission to assume the
role.
   :param session_name: The name for the STS session.
   :param issuer: The organization that issues the URL.
   :param sts_client: A Boto3 STS instance that can assume the role.
   :return: The federated URL.
   """
   response = sts_client.assume_role(
       RoleArn=assume_role_arn, RoleSessionName=session_name
   )
   temp_credentials = response["Credentials"]
   print(f"Assumed role {assume_role_arn} and got temporary credentials.")

   session_data = {
       "sessionId": temp_credentials["AccessKeyId"],
       "sessionKey": temp_credentials["SecretAccessKey"],
       "sessionToken": temp_credentials["SessionToken"],
   }
   aws_federated_signin_endpoint = "https://signin.aws.amazon.com/federation"

   # Make a request to the AWS federation endpoint to get a sign-in token.
   # The requests.get function URL-encodes the parameters and builds the query
string
   # before making the request.
   response = requests.get(
       aws_federated_signin_endpoint,
       params={
           "Action": "getSigninToken",
           "SessionDuration": str(datetime.timedelta(hours=12).seconds),
           "Session": json.dumps(session_data),
       },
   )
   signin_token = json.loads(response.text)
   print(f"Got a sign-in token from the AWS sign-in federation endpoint.")

   # Make a federated URL that can be used to sign into the AWS Management Console.
```

```
    query_string = urllib.parse.urlencode(
        {
            "Action": "login",
            "Issuer": issuer,
            "Destination": "https://console.aws.amazon.com/",
            "SigninToken": signin_token["SigninToken"],
        }
    )
    federated_url = f"{aws_federated_signin_endpoint}?{query_string}"
    return federated_url
```

Destrua os recursos criados para a demonstração.

```
def teardown(role):
    """
    Removes all resources created during setup.

    :param role: The demo role.
    """
    for attached in role.attached_policies.all():
        role.detach_policy(PolicyArn=attached.arn)
        print(f"Detached {attached.policy_name}.")
    role.delete()
    print(f"Deleted {role.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(f"Welcome to the AWS Security Token Service federated URL demo.")
    print("-" * 88)
    iam_resource = boto3.resource("iam")
    role = setup(iam_resource)
    sts_client = boto3.client("sts")
    try:
        federated_url = construct_federated_url(
```

```
            role.arn, "AssumeRoleDemoSession", "example.org", sts_client
        )
        print(
            "Constructed a federated URL that can be used to connect to the "
            "AWS Management Console with role-defined permissions:"
        )
        print("-" * 88)
        print(federated_url)
        print("-" * 88)
        _ = input(
            "Copy and paste the above URL into a browser to open the AWS "
            "Management Console with limited permissions. When done, press "
            "Enter to clean up and complete this demo."
        )
    finally:
        teardown(role)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a AssumeRoleReferência da API AWSSDK for Python (Boto3).

Obtenha um token de sessão que requeira um token de MFA

O exemplo de código a seguir mostra como obter um token de sessão que exige um token de MFA.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Criar um perfil do IAM que conceda permissão para listar os buckets do Amazon S3.
- Criar um usuário do IAM que tenha permissão para assumir o perfil somente quando as credenciais de MFA forem fornecidas.
- Registrar um dispositivo MFA para o usuário.

- Forneça credenciais de MFA para obter um token de sessão e use credenciais temporárias para listar buckets do S3.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário do IAM, registre um dispositivo de MFA e crie um perfil que conceda permissão para deixar o usuário listar os buckets do S3 somente quando credenciais de MFA forem usadas.

```
def setup(iam_resource):
    """
    Creates a new user with no permissions.
    Creates a new virtual multi-factor authentication (MFA) device.
    Displays the QR code to seed the device.
    Asks for two codes from the MFA device.
    Registers the MFA device for the user.
    Creates an access key pair for the user.
    Creates an inline policy for the user that lets the user list Amazon S3 buckets,
    but only when MFA credentials are used.

    Any MFA device that can scan a QR code will work with this demonstration.
    Common choices are mobile apps like LastPass Authenticator,
    Microsoft Authenticator, or Google Authenticator.

    :param iam_resource: A Boto3 AWS Identity and Access Management (IAM) resource
                         that has permissions to create users, MFA devices, and
                         policies in the account.
    :return: The newly created user, user key, and virtual MFA device.
    """
    user = iam_resource.create_user(UserName=unique_name("user"))
    print(f"Created user {user.name}.")

    virtual_mfa_device = iam_resource.create_virtual_mfa_device(
        VirtualMFADeviceName=unique_name("mfa")
    )
    print(f"Created virtual MFA device {virtual_mfa_device.serial_number}")
```

```
    print(
        f"Showing the QR code for the device. Scan this in the MFA app of your "
        f"choice."
    )
    with open("qr.png", "wb") as qr_file:
        qr_file.write(virtual_mfa_device.qr_code_png)
    webbrowser.open(qr_file.name)

    print(f"Enter two consecutive code from your MFA device.")
    mfa_code_1 = input("Enter the first code: ")
    mfa_code_2 = input("Enter the second code: ")
    user.enable_mfa(
        SerialNumber=virtual_mfa_device.serial_number,
        AuthenticationCode1=mfa_code_1,
        AuthenticationCode2=mfa_code_2,
    )
    os.remove(qr_file.name)
    print(f"MFA device is registered with the user.")

    user_key = user.create_access_key_pair()
    print(f"Created access key pair for user.")

    print(f"Wait for user to be ready.", end="")
    progress_bar(10)

    user.create_policy(
        PolicyName=unique_name("user-policy"),
        PolicyDocument=json.dumps(
            {
                "Version": "2012-10-17",
                "Statement": [
                    {
                        "Effect": "Allow",
                        "Action": "s3:ListAllMyBuckets",
                        "Resource": "arn:aws:s3:::*",
                        "Condition": {"Bool": {"aws:MultiFactorAuthPresent": True}},
                    }
                ],
            }
        ),
    )
    print(
```

```
        f"Created an inline policy for {user.name} that lets the user list buckets,
 "
        f"but only when MFA credentials are present."
    )

    print("Give AWS time to propagate these new resources and connections.", end="")
    progress_bar(10)

    return user, user_key, virtual_mfa_device
```

Obtenha credenciais de sessão temporárias passando um token de MFA e use-as para listar buckets do S3 para a conta.

```
def list_buckets_with_session_token_with_mfa(mfa_serial_number, mfa_totp,
 sts_client):
    """
    Gets a session token with MFA credentials and uses the temporary session
    credentials to list Amazon S3 buckets.

    Requires an MFA device serial number and token.

    :param mfa_serial_number: The serial number of the MFA device. For a virtual MFA
                              device, this is an Amazon Resource Name (ARN).
    :param mfa_totp: A time-based, one-time password issued by the MFA device.
    :param sts_client: A Boto3 STS instance that has permission to assume the role.
    """
    if mfa_serial_number is not None:
        response = sts_client.get_session_token(
            SerialNumber=mfa_serial_number, TokenCode=mfa_totp
        )
    else:
        response = sts_client.get_session_token()
    temp_credentials = response["Credentials"]

    s3_resource = boto3.resource(
        "s3",
        aws_access_key_id=temp_credentials["AccessKeyId"],
        aws_secret_access_key=temp_credentials["SecretAccessKey"],
        aws_session_token=temp_credentials["SessionToken"],
    )
```

```
    print(f"Buckets for the account:")
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
```

Destrua os recursos criados para a demonstração.

```
def teardown(user, virtual_mfa_device):
    """
    Removes all resources created during setup.

    :param user: The demo user.
    :param role: The demo MFA device.
    """
    for user_pol in user.policies.all():
        user_pol.delete()
        print("Deleted inline user policy.")
    for key in user.access_keys.all():
        key.delete()
        print("Deleted user's access key.")
    for mfa in user.mfa_devices.all():
        mfa.disassociate()
    virtual_mfa_device.delete()
    user.delete()
    print(f"Deleted {user.name}.")
```

Execute esse cenário usando a funções definidas anteriormente.

```
def usage_demo():
    """Drives the demonstration."""
    print("-" * 88)
    print(
        f"Welcome to the AWS Security Token Service assume role demo, "
        f"starring multi-factor authentication (MFA)!"
    )
    print("-" * 88)
    iam_resource = boto3.resource("iam")
```

```
    user, user_key, virtual_mfa_device = setup(iam_resource)
    try:
        sts_client = boto3.client(
            "sts", aws_access_key_id=user_key.id,
aws_secret_access_key=user_key.secret
        )
        try:
            print("Listing buckets without specifying MFA credentials.")
            list_buckets_with_session_token_with_mfa(None, None, sts_client)
        except ClientError as error:
            if error.response["Error"]["Code"] == "AccessDenied":
                print("Got expected AccessDenied error.")
        mfa_totp = input("Enter the code from your registered MFA device: ")
        list_buckets_with_session_token_with_mfa(
            virtual_mfa_device.serial_number, mfa_totp, sts_client
        )
    finally:
        teardown(user, virtual_mfa_device)
        print("Thanks for watching!")
```

- Para obter detalhes da API, consulte a GetSessionTokenReferência da API AWSSDK for Python (Boto3).

Exemplos de AWS Support usando o SDK para Python (Boto3)

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com AWS Support.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Support

O exemplo de código a seguir mostra como começar a usar o AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import logging
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)


def hello_support(support_client):
    """
    Use the AWS SDK for Python (Boto3) to create an AWS Support client and count
    the available services in your account.
    This example uses the default settings specified in your shared credentials
    and config files.

    :param support_client: A Boto3 Support Client object.
    """
    try:
        print("Hello, AWS Support! Let's count the available Support services:")
        response = support_client.describe_services()
        print(f"There are {len(response['services'])} services available.")
    except ClientError as err:
        if err.response["Error"]["Code"] == "SubscriptionRequiredException":
            logger.info(
                "You must have a Business, Enterprise On-Ramp, or Enterprise Support
 "
                "plan to use the AWS Support API. \n\tPlease upgrade your
 subscription to run these "
                "examples."
            )
        else:
            logger.error(
```

```
                "Couldn't count services. Here's why: %s: %s",
                err.response["Error"]["Code"],
                err.response["Error"]["Message"],
            )
            raise


if __name__ == "__main__":
    hello_support(boto3.client("support"))
```

- Para obter detalhes da API, consulte a DescribeServicesReferência da API AWSSDK for Python (Boto3).

Tópicos

- Ações
- Cenários

Ações

Adicionar uma comunicação a um caso

O exemplo de código a seguir mostra como adicionar uma comunicação do AWS Support com um anexo a um caso de suporte.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
```

```
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def add_communication_to_case(self, attachment_set_id, case_id):
        """
        Add a communication and an attachment set to a case.

        :param attachment_set_id: The ID of an existing attachment set.
        :param case_id: The ID of the case.
        """
        try:
            self.support_client.add_communication_to_case(
                caseId=case_id,
                communicationBody="This is an example communication added to a
support case.",
                attachmentSetId=attachment_set_id,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add communication. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
```

- Para obter detalhes da API, consulte a AddCommunicationToCaseReferência da API AWSSDK for Python (Boto3).

Adicionar um anexo a um conjunto

O exemplo de código a seguir mostra como adicionar um anexo do AWS Support a um conjunto de anexos.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def add_attachment_to_set(self):
        """
        Add an attachment to a set, or create a new attachment set if one does not
 exist.

        :return: The attachment set ID.
        """
```

```
        try:
            response = self.support_client.add_attachments_to_set(
                attachments=[
                    {
                        "fileName": "attachment_file.txt",
                        "data": b"This is a sample file for attachment to a support
case.",
                    }
                ]
            )
            new_set_id = response["attachmentSetId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add attachment. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return new_set_id
```

- Para obter detalhes da API, consulte a AddAttachmentsToSetReferência da API AWSSDK for Python (Boto3).

Criar um caso

O exemplo de código a seguir mostra como criar um novo caso do AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def create_case(self, service, category, severity):
        """
        Create a new support case.

        :param service: The service to use for the new case.
        :param category: The category to use for the new case.
        :param severity: The severity to use for the new case.
        :return: The caseId of the new case.
        """
        try:
            response = self.support_client.create_case(
                subject="Example case for testing, ignore.",
                serviceCode=service["code"],
                severityCode=severity["code"],
                categoryCode=category["code"],
                communicationBody="Example support case body.",
```

```
                language="en",
                issueType="customer-service",
            )
            case_id = response["caseId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
 Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
 subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't create case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return case_id
```

- Para obter detalhes da API, consulte a CreateCaseReferência da API AWSSDK for Python (Boto3).

Descrever um anexo

O exemplo de código a seguir mostra como descrever um anexo para um caso do AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""
```

```
    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_attachment(self, attachment_id):
        """
        Get information about an attachment by its attachmentID.

        :param attachment_id: The ID of the attachment.
        :return: The name of the attached file.
        """
        try:
            response = self.support_client.describe_attachment(
                attachmentId=attachment_id
            )
            attached_file = response["attachment"]["fileName"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get attachment description. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
```

```
        else:
            return attached_file
```

- Para obter detalhes da API, consulte a DescribeAttachmentReferência da API AWSSDK for Python (Boto3).

Descrever casos

O exemplo de código a seguir mostra como descrever casos do AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_cases(self, after_time, before_time, resolved):
        """
        Describe support cases over a period of time, optionally filtering
```

```
        by status.

        :param after_time: The start time to include for cases.
        :param before_time: The end time to include for cases.
        :param resolved: True to include resolved cases in the results,
            otherwise results are open cases.
        :return: The final status of the case.
        """
        try:
            cases = []
            paginator = self.support_client.get_paginator("describe_cases")
            for page in paginator.paginate(
                afterTime=after_time,
                beforeTime=before_time,
                includeResolvedCases=resolved,
                language="en",
            ):
                cases += page["cases"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe cases. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            if resolved:
                cases = filter(lambda case: case["status"] == "resolved", cases)
            return cases
```

- Para obter detalhes da API, consulte a DescribeCasesReferência da API AWSSDK for Python (Boto3).

Descrever as comunicações

O exemplo de código a seguir mostra como descrever as comunicações do AWS Support para um caso.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_all_case_communications(self, case_id):
        """
        Describe all the communications for a case using a paginator.

        :param case_id: The ID of the case.
        :return: The communications for the case.
        """
        try:
            communications = []
            paginator = self.support_client.get_paginator("describe_communications")
            for page in paginator.paginate(caseId=case_id):
```

```
                communications += page["communications"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
 Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
 subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe communications. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return communications
```

- Para obter detalhes da API, consulte a DescribeCommunicationsReferência da API AWSSDK for Python (Boto3).

Descrever os serviços

O exemplo de código a seguir mostra como descrever a lista de serviços do AWS.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
```

```
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_services(self, language):
        """
        Get the descriptions of AWS services available for support for a language.

        :param language: The language for support services.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of AWS service descriptions.
        """
        try:
            response = self.support_client.describe_services(language=language)
            services = response["services"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get Support services for language %s. Here's why: %s:
%s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return services
```

- Para obter detalhes da API, consulte a DescribeServicesReferência da API AWSSDK for Python (Boto3).

Descrever os níveis de gravidade

O exemplo de código a seguir mostra como descrever os níveis de gravidade do AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_severity_levels(self, language):
        """
        Get the descriptions of available severity levels for support cases for a
 language.
```

```
        :param language: The language for support severity levels.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of severity levels.
        """
        try:
            response =
self.support_client.describe_severity_levels(language=language)
            severity_levels = response["severityLevels"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get severity levels for language %s. Here's why: %s:
%s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return severity_levels
```

- Para obter detalhes da API, consulte a DescribeSeverityLevelsReferência da API AWSSDK for Python (Boto3).

Resolver caso

O exemplo de código a seguir mostra como resolver um caso do AWS Support.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def resolve_case(self, case_id):
        """
        Resolve a support case by its caseId.

        :param case_id: The ID of the case to resolve.
        :return: The final status of the case.
        """
        try:
            response = self.support_client.resolve_case(caseId=case_id)
            final_status = response["finalCaseStatus"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
 Support "
```

```
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't resolve case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return final_status
```

- Para obter detalhes da API, consulte a ResolveCaseReferência da API AWSSDK for Python (Boto3).

Cenários

Conceitos básicos de casos

O código de exemplo a seguir mostra como:

- Obtenha e exiba os serviços disponíveis e os níveis de gravidade dos casos.
- Crie um caso de suporte usando um serviço, uma categoria e um nível de gravidade selecionados.
- Obtenha e exiba uma lista de casos em aberto para o dia atual.
- Adicione um conjunto de anexos e uma comunicação ao novo caso.
- Descreva o novo anexo e a comunicação para o caso.
- Resolva o caso.
- Obtenha e exiba uma lista de casos resolvidos para o dia atual.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário interativo em um prompt de comando.

```
class SupportCasesScenario:
    """Runs an interactive scenario that shows how to get started using AWS
 Support."""

    def __init__(self, support_wrapper):
        """
        :param support_wrapper: An object that wraps AWS Support actions.
        """
        self.support_wrapper = support_wrapper

    def display_and_select_service(self):
        """
        Lists support services and prompts the user to select one.

        :return: The support service selected by the user.
        """
        print("-" * 88)
        services_list = self.support_wrapper.describe_services("en")
        print(f"AWS Support client returned {len(services_list)} services.")
        print("Displaying first 10 services:")

        service_choices = [svc["name"] for svc in services_list[:10]]
        selected_index = q.choose(
            "Select an example support service by entering a number from the
 preceding list:",
            service_choices,
        )
        selected_service = services_list[selected_index]
        print("-" * 88)
        return selected_service

    def display_and_select_category(self, service):
        """
```

```
        Lists categories for a support service and prompts the user to select one.

        :param service: The service of the categories.
        :return: The selected category.
        """
        print("-" * 88)
        print(
            f"Available support categories for Service {service['name']}
{len(service['categories'])}:"
        )
        categories_choices = [category["name"] for category in
service["categories"]]
        selected_index = q.choose(
            "Select an example support category by entering a number from the
preceding list:",
            categories_choices,
        )
        selected_category = service["categories"][selected_index]
        print("-" * 88)
        return selected_category

    def display_and_select_severity(self):
        """
        Lists available severity levels and prompts the user to select one.

        :return: The selected severity level.
        """
        print("-" * 88)
        severity_levels_list = self.support_wrapper.describe_severity_levels("en")
        print(f"Available severity levels:")
        severity_choices = [level["name"] for level in severity_levels_list]
        selected_index = q.choose(
            "Select an example severity level by entering a number from the
preceding list:",
            severity_choices,
        )
        selected_severity = severity_levels_list[selected_index]
        print("-" * 88)
        return selected_severity

    def create_example_case(self, service, category, severity_level):
        """
        Creates an example support case with the user's selections.
```

```
        :param service: The service for the new case.
        :param category: The category for the new case.
        :param severity_level: The severity level for the new case.
        :return: The caseId of the new support case.
        """
        print("-" * 88)
        print(f"Creating new case for service {service['name']}.")
        case_id = self.support_wrapper.create_case(service, category,
severity_level)
        print(f"\tNew case created with ID {case_id}.")
        print("-" * 88)
        return case_id

    def list_open_cases(self):
        """
        List the open cases for the current day.
        """
        print("-" * 88)
        print("Let's list the open cases for the current day.")
        start_time = str(datetime.utcnow().date())
        end_time = str(datetime.utcnow().date() + timedelta(days=1))
        open_cases = self.support_wrapper.describe_cases(start_time, end_time,
False)
        for case in open_cases:
            print(f"\tCase: {case['caseId']}: status {case['status']}.")
        print("-" * 88)

    def create_attachment_set(self):
        """
        Create an attachment set with a sample file.

        :return: The attachment set ID of the new attachment set.
        """
        print("-" * 88)
        print("Creating attachment set with a sample file.")
        attachment_set_id = self.support_wrapper.add_attachment_to_set()
        print(f"\tNew attachment set created with ID {attachment_set_id}.")
        print("-" * 88)
        return attachment_set_id

    def add_communication(self, case_id, attachment_set_id):
        """
        Add a communication with an attachment set to the case.
```

```
        :param case_id: The ID of the case for the communication.
        :param attachment_set_id: The ID of the attachment set to
        add to the communication.
        """
        print("-" * 88)
        print(f"Adding a communication and attachment set to the case.")
        self.support_wrapper.add_communication_to_case(attachment_set_id, case_id)
        print(
            f"Added a communication and attachment set {attachment_set_id} to the
case {case_id}."
        )
        print("-" * 88)

    def list_communications(self, case_id):
        """
        List the communications associated with a case.

        :param case_id: The ID of the case.
        :return: The attachment ID of an attachment.
        """
        print("-" * 88)
        print("Let's list the communications for our case.")
        attachment_id = ""
        communications =
self.support_wrapper.describe_all_case_communications(case_id)
        for communication in communications:
            print(
                f"\tCommunication created on {communication['timeCreated']} "
                f"has {len(communication['attachmentSet'])} attachments."
            )
            if len(communication["attachmentSet"]) > 0:
                attachment_id = communication["attachmentSet"][0]["attachmentId"]
        print("-" * 88)
        return attachment_id

    def describe_case_attachment(self, attachment_id):
        """
        Describe an attachment associated with a case.

        :param attachment_id: The ID of the attachment.
        """
        print("-" * 88)
        print("Let's list the communications for our case.")
        attached_file = self.support_wrapper.describe_attachment(attachment_id)
```

```
        print(f"\tAttachment includes file {attached_file}.")
        print("-" * 88)

    def resolve_case(self, case_id):
        """
        Shows how to resolve an AWS Support case by its ID.

        :param case_id: The ID of the case to resolve.
        """
        print("-" * 88)
        print(f"Resolving case with ID {case_id}.")
        case_status = self.support_wrapper.resolve_case(case_id)
        print(f"\tFinal case status is {case_status}.")
        print("-" * 88)

    def list_resolved_cases(self):
        """
        List the resolved cases for the current day.
        """
        print("-" * 88)
        print("Let's list the resolved cases for the current day.")
        start_time = str(datetime.utcnow().date())
        end_time = str(datetime.utcnow().date() + timedelta(days=1))
        resolved_cases = self.support_wrapper.describe_cases(start_time, end_time,
True)
        for case in resolved_cases:
            print(f"\tCase: {case['caseId']}: status {case['status']}.")
        print("-" * 88)

    def run_scenario(self):
        logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

        print("-" * 88)
        print("Welcome to the AWS Support get started with support cases demo.")
        print("-" * 88)

        selected_service = self.display_and_select_service()
        selected_category = self.display_and_select_category(selected_service)
        selected_severity = self.display_and_select_severity()
        new_case_id = self.create_example_case(
            selected_service, selected_category, selected_severity
        )
        wait(10)
        self.list_open_cases()
```

```
        new_attachment_set_id = self.create_attachment_set()
        self.add_communication(new_case_id, new_attachment_set_id)
        new_attachment_id = self.list_communications(new_case_id)
        self.describe_case_attachment(new_attachment_id)
        self.resolve_case(new_case_id)
        wait(10)
        self.list_resolved_cases()

        print("\nThanks for watching!")
        print("-" * 88)


if __name__ == "__main__":
    try:
        scenario = SupportCasesScenario(SupportWrapper.from_client())
        scenario.run_scenario()
    except Exception:
        logging.exception("Something went wrong with the demo.")
```

Definir uma classe que envolva ações de suporte ao cliente.

```
class SupportWrapper:
    """Encapsulates Support actions."""

    def __init__(self, support_client):
        """
        :param support_client: A Boto3 Support client.
        """
        self.support_client = support_client

    @classmethod
    def from_client(cls):
        """
        Instantiates this class from a Boto3 client.
        """
        support_client = boto3.client("support")
        return cls(support_client)


    def describe_services(self, language):
        """
        Get the descriptions of AWS services available for support for a language.
```

```
        :param language: The language for support services.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of AWS service descriptions.
        """
        try:
            response = self.support_client.describe_services(language=language)
            services = response["services"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get Support services for language %s. Here's why: %s:
%s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return services


    def describe_severity_levels(self, language):
        """
        Get the descriptions of available severity levels for support cases for a
language.

        :param language: The language for support severity levels.
        Currently, only "en" (English) and "ja" (Japanese) are supported.
        :return: The list of severity levels.
        """
        try:
            response =
self.support_client.describe_severity_levels(language=language)
            severity_levels = response["severityLevels"]
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get severity levels for language %s. Here's why: %s:
%s",
                    language,
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return severity_levels


    def create_case(self, service, category, severity):
        """
        Create a new support case.

        :param service: The service to use for the new case.
        :param category: The category to use for the new case.
        :param severity: The severity to use for the new case.
        :return: The caseId of the new case.
        """
        try:
            response = self.support_client.create_case(
                subject="Example case for testing, ignore.",
                serviceCode=service["code"],
                severityCode=severity["code"],
                categoryCode=category["code"],
                communicationBody="Example support case body.",
                language="en",
                issueType="customer-service",
            )
            case_id = response["caseId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
```

```
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't create case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return case_id


    def add_attachment_to_set(self):
        """
        Add an attachment to a set, or create a new attachment set if one does not
exist.

        :return: The attachment set ID.
        """
        try:
            response = self.support_client.add_attachments_to_set(
                attachments=[
                    {
                        "fileName": "attachment_file.txt",
                        "data": b"This is a sample file for attachment to a support
case.",
                    }
                ]
            )
            new_set_id = response["attachmentSetId"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
```

```
            else:
                logger.error(
                    "Couldn't add attachment. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return new_set_id


    def add_communication_to_case(self, attachment_set_id, case_id):
        """
        Add a communication and an attachment set to a case.

        :param attachment_set_id: The ID of an existing attachment set.
        :param case_id: The ID of the case.
        """
        try:
            self.support_client.add_communication_to_case(
                caseId=case_id,
                communicationBody="This is an example communication added to a
support case.",
                attachmentSetId=attachment_set_id,
            )
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't add communication. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise


    def describe_all_case_communications(self, case_id):
```

```
        """
        Describe all the communications for a case using a paginator.

        :param case_id: The ID of the case.
        :return: The communications for the case.
        """
        try:
            communications = []
            paginator = self.support_client.get_paginator("describe_communications")
            for page in paginator.paginate(caseId=case_id):
                communications += page["communications"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe communications. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return communications


    def describe_attachment(self, attachment_id):
        """
        Get information about an attachment by its attachmentID.

        :param attachment_id: The ID of the attachment.
        :return: The name of the attached file.
        """
        try:
            response = self.support_client.describe_attachment(
                attachmentId=attachment_id
            )
            attached_file = response["attachment"]["fileName"]
        except ClientError as err:
```

```
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't get attachment description. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            return attached_file


    def resolve_case(self, case_id):
        """
        Resolve a support case by its caseId.

        :param case_id: The ID of the case to resolve.
        :return: The final status of the case.
        """
        try:
            response = self.support_client.resolve_case(caseId=case_id)
            final_status = response["finalCaseStatus"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't resolve case. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
```

```
                raise
        else:
            return final_status


    def describe_cases(self, after_time, before_time, resolved):
        """
        Describe support cases over a period of time, optionally filtering
        by status.

        :param after_time: The start time to include for cases.
        :param before_time: The end time to include for cases.
        :param resolved: True to include resolved cases in the results,
            otherwise results are open cases.
        :return: The final status of the case.
        """
        try:
            cases = []
            paginator = self.support_client.get_paginator("describe_cases")
            for page in paginator.paginate(
                afterTime=after_time,
                beforeTime=before_time,
                includeResolvedCases=resolved,
                language="en",
            ):
                cases += page["cases"]
        except ClientError as err:
            if err.response["Error"]["Code"] == "SubscriptionRequiredException":
                logger.info(
                    "You must have a Business, Enterprise On-Ramp, or Enterprise
Support "
                    "plan to use the AWS Support API. \n\tPlease upgrade your
subscription to run these "
                    "examples."
                )
            else:
                logger.error(
                    "Couldn't describe cases. Here's why: %s: %s",
                    err.response["Error"]["Code"],
                    err.response["Error"]["Message"],
                )
                raise
        else:
            if resolved:
```

```
            cases = filter(lambda case: case["status"] == "resolved", cases)
        return cases
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - AddAttachmentsToSet
  - AddCommunicationToCase
  - CreateCase
  - DescribeAttachment
  - DescribeCases
  - DescribeCommunications
  - DescribeServices
  - DescribeSeverityLevels
  - ResolveCase

Exemplos do Amazon Textract usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Textract.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Analisar um documento

O exemplo de código a seguir mostra como analisar um documento usando o Amazon Textract.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def analyze_file(
        self, feature_types, *, document_file_name=None, document_bytes=None
    ):
        """
        Detects text and additional elements, such as forms or tables, in a local
 image
        file or from in-memory byte data.
        The image must be in PNG or JPG format.

        :param feature_types: The types of additional document features to detect.
        :param document_file_name: The name of a document image file.
        :param document_bytes: In-memory byte data of a document image.
        :return: The response from Amazon Textract, including a list of blocks
                 that describe elements detected in the image.
        """
```

```
        if document_file_name is not None:
            with open(document_file_name, "rb") as document_file:
                document_bytes = document_file.read()
        try:
            response = self.textract_client.analyze_document(
                Document={"Bytes": document_bytes}, FeatureTypes=feature_types
            )
            logger.info("Detected %s blocks.", len(response["Blocks"]))
        except ClientError:
            logger.exception("Couldn't detect text.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a AnalyzeDocumentReferência da API AWSSDK for Python (Boto3).

Detectar texto em um documento

O exemplo de código a seguir mostra como detectar texto em um documento usando o Amazon Textract.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
```

```
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def detect_file_text(self, *, document_file_name=None, document_bytes=None):
        """
        Detects text elements in a local image file or from in-memory byte data.
        The image must be in PNG or JPG format.

        :param document_file_name: The name of a document image file.
        :param document_bytes: In-memory byte data of a document image.
        :return: The response from Amazon Textract, including a list of blocks
                 that describe elements detected in the image.
        """
        if document_file_name is not None:
            with open(document_file_name, "rb") as document_file:
                document_bytes = document_file.read()
        try:
            response = self.textract_client.detect_document_text(
                Document={"Bytes": document_bytes}
            )
            logger.info("Detected %s blocks.", len(response["Blocks"]))
        except ClientError:
            logger.exception("Couldn't detect text.")
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a DetectDocumentTextReferência da API AWSSDK for Python (Boto3).

Obter dados sobre um trabalho de análise de documento

O exemplo de código a seguir mostra como obter dados sobre um trabalho de análise de documento do Amazon Textract.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def get_analysis_job(self, job_id):
        """
        Gets data for a previously started detection job that includes additional
        elements.

        :param job_id: The ID of the job to retrieve.
        :return: The job data, including a list of blocks that describe elements
                 detected in the image.
        """
        try:
            response = self.textract_client.get_document_analysis(JobId=job_id)
            job_status = response["JobStatus"]
            logger.info("Job %s status is %s.", job_id, job_status)
        except ClientError:
            logger.exception("Couldn't get data for job %s.", job_id)
            raise
        else:
            return response
```

- Para obter detalhes da API, consulte a GetDocumentAnalysisReferência da API AWSSDK for Python (Boto3).

Iniciar análise assíncrona de um documento

O exemplo de código a seguir mostra como iniciar uma análise assíncrona de um documento usando o Amazon Textract.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Iniciar um trabalho assíncrono para analisar um documento.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def start_analysis_job(
        self,
        bucket_name,
        document_file_name,
        feature_types,
        sns_topic_arn,
        sns_role_arn,
    ):
```

```
        """
        Starts an asynchronous job to detect text and additional elements, such as
        forms or tables, in an image stored in an Amazon S3 bucket. Textract
publishes
        a notification to the specified Amazon SNS topic when the job completes.
        The image must be in PNG, JPG, or PDF format.

        :param bucket_name: The name of the Amazon S3 bucket that contains the
image.
        :param document_file_name: The name of the document image stored in Amazon
S3.
        :param feature_types: The types of additional document features to detect.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of an Amazon SNS topic
                              where job completion notification is published.
        :param sns_role_arn: The ARN of an AWS Identity and Access Management (IAM)
                             role that can be assumed by Textract and grants
permission
                             to publish to the Amazon SNS topic.
        :return: The ID of the job.
        """
        try:
            response = self.textract_client.start_document_analysis(
                DocumentLocation={
                    "S3Object": {"Bucket": bucket_name, "Name": document_file_name}
                },
                NotificationChannel={
                    "SNSTopicArn": sns_topic_arn,
                    "RoleArn": sns_role_arn,
                },
                FeatureTypes=feature_types,
            )
            job_id = response["JobId"]
            logger.info(
                "Started text analysis job %s on %s.", job_id, document_file_name
            )
        except ClientError:
            logger.exception("Couldn't analyze text in %s.", document_file_name)
            raise
        else:
            return job_id
```

- Para obter detalhes da API, consulte a StartDocumentAnalysisReferência da API AWSSDK for Python (Boto3).

Iniciar a detecção assíncrona de texto

O exemplo de código a seguir mostra como detectar texto em um documento usando o Amazon Textract.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Iniciar um trabalho assíncrono para detectar texto em um documento.

```
class TextractWrapper:
    """Encapsulates Textract functions."""

    def __init__(self, textract_client, s3_resource, sqs_resource):
        """
        :param textract_client: A Boto3 Textract client.
        :param s3_resource: A Boto3 Amazon S3 resource.
        :param sqs_resource: A Boto3 Amazon SQS resource.
        """
        self.textract_client = textract_client
        self.s3_resource = s3_resource
        self.sqs_resource = sqs_resource


    def start_detection_job(
        self, bucket_name, document_file_name, sns_topic_arn, sns_role_arn
    ):
        """
        Starts an asynchronous job to detect text elements in an image stored in an
        Amazon S3 bucket. Textract publishes a notification to the specified Amazon
 SNS
        topic when the job completes.
        The image must be in PNG, JPG, or PDF format.
```

```
        :param bucket_name: The name of the Amazon S3 bucket that contains the
image.
        :param document_file_name: The name of the document image stored in Amazon
S3.
        :param sns_topic_arn: The Amazon Resource Name (ARN) of an Amazon SNS topic
                              where the job completion notification is published.
        :param sns_role_arn: The ARN of an AWS Identity and Access Management (IAM)
                             role that can be assumed by Textract and grants
permission
                             to publish to the Amazon SNS topic.
        :return: The ID of the job.
        """
        try:
            response = self.textract_client.start_document_text_detection(
                DocumentLocation={
                    "S3Object": {"Bucket": bucket_name, "Name": document_file_name}
                },
                NotificationChannel={
                    "SNSTopicArn": sns_topic_arn,
                    "RoleArn": sns_role_arn,
                },
            )
            job_id = response["JobId"]
            logger.info(
                "Started text detection job %s on %s.", job_id, document_file_name
            )
        except ClientError:
            logger.exception("Couldn't detect text in %s.", document_file_name)
            raise
        else:
            return job_id
```

- Para obter detalhes da API, consulte a StartDocumentTextDetectionReferência da API AWSSDK for Python (Boto3).

Exemplos do Amazon Transcribe usando o SDK para Python (Boto3)

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Python (Boto3) com o Amazon Transcribe.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um vocabulário personalizado

O exemplo de código a seguir mostra como criar um vocabulário personalizado do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def create_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None, table_uri=None
):
    """
    Creates a custom vocabulary that can be used to improve the accuracy of
    transcription jobs. This function returns as soon as the vocabulary processing
    is started. Call get_vocabulary to get the current status of the vocabulary.
    The vocabulary is ready to use when its status is 'READY'.

    :param vocabulary_name: The name of the custom vocabulary.
```

```
    :param language_code: The language code of the vocabulary.
                          For example, en-US or nl-NL.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in the
                      vocabulary.
    :return: Information about the newly created vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.create_vocabulary(**vocab_args)
        logger.info("Created custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't create custom vocabulary %s.", vocabulary_name)
        raise
    else:
        return response
```

- Para obter detalhes da API, consulte a CreateVocabularyReferência da API AWSSDK for Python (Boto3).

Excluir um vocabulário personalizado

O exemplo de código a seguir mostra como excluir um vocabulário personalizado do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_vocabulary(vocabulary_name, transcribe_client):
    """
    Deletes a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Deleted vocabulary %s.", vocabulary_name)
    except ClientError:
        logger.exception("Couldn't delete vocabulary %s.", vocabulary_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteVocabularyReferência da API AWSSDK for Python (Boto3).

Criar um trabalho de transcrição

O exemplo de código a seguir mostra como excluir um trabalho de transcrição do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def delete_job(job_name, transcribe_client):
    """
    Deletes a transcription job. This also deletes the transcript associated with
    the job.

    :param job_name: The name of the job to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
```

```
    try:
        transcribe_client.delete_transcription_job(TranscriptionJobName=job_name)
        logger.info("Deleted job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't delete job %s.", job_name)
        raise
```

- Para obter detalhes da API, consulte a DeleteTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Obter um vocabulário personalizado

O exemplo de código a seguir mostra como obter um vocabulário personalizado do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_vocabulary(vocabulary_name, transcribe_client):
    """
    Gets information about a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: Information about the vocabulary.
    """
    try:
        response = transcribe_client.get_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Got vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't get vocabulary %s.", vocabulary_name)
        raise
    else:
```

```
        return response
```

- Para obter detalhes da API, consulte a GetVocabularyReferência da API AWSSDK for Python (Boto3).

Obter trabalho de transcrição

O exemplo de código a seguir mostra como obter um trabalho de transcrição do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def get_job(job_name, transcribe_client):
    """
    Gets details about a transcription job.

    :param job_name: The name of the job to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The retrieved transcription job.
    """
    try:
        response = transcribe_client.get_transcription_job(
            TranscriptionJobName=job_name
        )
        job = response["TranscriptionJob"]
        logger.info("Got job %s.", job["TranscriptionJobName"])
    except ClientError:
        logger.exception("Couldn't get job %s.", job_name)
        raise
    else:
        return job
```

- Para obter detalhes da API, consulte a GetTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Listar vocabulários personalizados

O exemplo de código a seguir mostra como listar vocabulários personalizados do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_vocabularies(vocabulary_filter, transcribe_client):
    """
    Lists the custom vocabularies created for this AWS account.

    :param vocabulary_filter: The returned vocabularies must contain this string in
                              their names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved vocabularies.
    """
    try:
        response =
 transcribe_client.list_vocabularies(NameContains=vocabulary_filter)
        vocabs = response["Vocabularies"]
        next_token = response.get("NextToken")
        while next_token is not None:
            response = transcribe_client.list_vocabularies(
                NameContains=vocabulary_filter, NextToken=next_token
            )
            vocabs += response["Vocabularies"]
            next_token = response.get("NextToken")
        logger.info(
            "Got %s vocabularies with filter %s.", len(vocabs), vocabulary_filter
        )
```

```
    except ClientError:
        logger.exception(
            "Couldn't list vocabularies with filter %s.", vocabulary_filter
        )
        raise
    else:
        return vocabs
```

- Para obter detalhes da API, consulte a ListVocabularies Referência da API AWSSDK for Python (Boto3).

Listar trabalhos de transcrição

O exemplo de código a seguir mostra como listar trabalhos de transcrição do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def list_jobs(job_filter, transcribe_client):
    """
    Lists summaries of the transcription jobs for the current AWS account.

    :param job_filter: The list of returned jobs must contain this string in their
                       names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved transcription job summaries.
    """
    try:
        response =
 transcribe_client.list_transcription_jobs(JobNameContains=job_filter)
        jobs = response["TranscriptionJobSummaries"]
        next_token = response.get("NextToken")
        while next_token is not None:
```

```
            response = transcribe_client.list_transcription_jobs(
                JobNameContains=job_filter, NextToken=next_token
            )
            jobs += response["TranscriptionJobSummaries"]
            next_token = response.get("NextToken")
        logger.info("Got %s jobs with filter %s.", len(jobs), job_filter)
    except ClientError:
        logger.exception("Couldn't get jobs with filter %s.", job_filter)
        raise
    else:
        return jobs
```

- Para obter detalhes da API, consulte a ListTranscriptionJobsReferência da API AWSSDK for Python (Boto3).

Iniciar um trabalho de transcrição

O exemplo de código a seguir mostra como iniciar um trabalho de transcrição do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def start_job(
    job_name,
    media_uri,
    media_format,
    language_code,
    transcribe_client,
    vocabulary_name=None,
):
    """
    Starts a transcription job. This function returns as soon as the job is started.
    To get the current status of the job, call get_transcription_job. The job is
```

```
    successfully completed when the job status is 'COMPLETED'.

    :param job_name: The name of the transcription job. This must be unique for
                     your AWS account.
    :param media_uri: The URI where the audio file is stored. This is typically
                      in an Amazon S3 bucket.
    :param media_format: The format of the audio file. For example, mp3 or wav.
    :param language_code: The language code of the audio file.
                          For example, en-US or ja-JP
    :param transcribe_client: The Boto3 Transcribe client.
    :param vocabulary_name: The name of a custom vocabulary to use when transcribing
                            the audio file.
    :return: Data about the job.
    """
    try:
        job_args = {
            "TranscriptionJobName": job_name,
            "Media": {"MediaFileUri": media_uri},
            "MediaFormat": media_format,
            "LanguageCode": language_code,
        }
        if vocabulary_name is not None:
            job_args["Settings"] = {"VocabularyName": vocabulary_name}
        response = transcribe_client.start_transcription_job(**job_args)
        job = response["TranscriptionJob"]
        logger.info("Started transcription job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't start transcription job %s.", job_name)
        raise
    else:
        return job
```

- Para obter detalhes da API, consulte a StartTranscriptionJobReferência da API AWSSDK for Python (Boto3).

Atualizar um vocabulário personalizado

O exemplo de código a seguir mostra como atualizar um vocabulário personalizado do Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
def update_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None, table_uri=None
):
    """
    Updates an existing custom vocabulary. The entire vocabulary is replaced with
    the contents of the update.

    :param vocabulary_name: The name of the vocabulary to update.
    :param language_code: The language code of the vocabulary.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in the
                      vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.update_vocabulary(**vocab_args)
        logger.info("Updated custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't update custom vocabulary %s.", vocabulary_name)
        raise
```

- Para obter detalhes da API, consulte a UpdateVocabularyReferência da API AWSSDK for Python (Boto3).

Cenários

Criar e refinar um vocabulário personalizado

O código de exemplo a seguir mostra como:

- Fazer upload do arquivo de áudio para o Amazon S3.
- Execute um trabalho do Amazon Transcribe para transcrever o arquivo e obter os resultados.
- Crie e refine um vocabulário personalizado para melhorar a precisão da transcrição.
- Execute trabalhos com vocabulários personalizados e obtenha os resultados.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Transcreva um arquivo de áudio que contenha uma leitura de Jabberwocky de Lewis Carroll. Comece criando funções que envolvam as ações do Amazon Transcribe.

```
def start_job(
    job_name,
    media_uri,
    media_format,
    language_code,
    transcribe_client,
    vocabulary_name=None,
):
    """
    Starts a transcription job. This function returns as soon as the job is started.
    To get the current status of the job, call get_transcription_job. The job is
    successfully completed when the job status is 'COMPLETED'.

    :param job_name: The name of the transcription job. This must be unique for
                     your AWS account.
    :param media_uri: The URI where the audio file is stored. This is typically
                      in an Amazon S3 bucket.
    :param media_format: The format of the audio file. For example, mp3 or wav.
    :param language_code: The language code of the audio file.
```

```
                            For example, en-US or ja-JP
    :param transcribe_client: The Boto3 Transcribe client.
    :param vocabulary_name: The name of a custom vocabulary to use when transcribing
                            the audio file.
    :return: Data about the job.
    """
    try:
        job_args = {
            "TranscriptionJobName": job_name,
            "Media": {"MediaFileUri": media_uri},
            "MediaFormat": media_format,
            "LanguageCode": language_code,
        }
        if vocabulary_name is not None:
            job_args["Settings"] = {"VocabularyName": vocabulary_name}
        response = transcribe_client.start_transcription_job(**job_args)
        job = response["TranscriptionJob"]
        logger.info("Started transcription job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't start transcription job %s.", job_name)
        raise
    else:
        return job



def get_job(job_name, transcribe_client):
    """
    Gets details about a transcription job.

    :param job_name: The name of the job to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The retrieved transcription job.
    """
    try:
        response = transcribe_client.get_transcription_job(
            TranscriptionJobName=job_name
        )
        job = response["TranscriptionJob"]
        logger.info("Got job %s.", job["TranscriptionJobName"])
    except ClientError:
        logger.exception("Couldn't get job %s.", job_name)
        raise
    else:
```

```
        return job



def delete_job(job_name, transcribe_client):
    """
    Deletes a transcription job. This also deletes the transcript associated with
    the job.

    :param job_name: The name of the job to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_transcription_job(TranscriptionJobName=job_name)
        logger.info("Deleted job %s.", job_name)
    except ClientError:
        logger.exception("Couldn't delete job %s.", job_name)
        raise



def create_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None, table_uri=None
):
    """
    Creates a custom vocabulary that can be used to improve the accuracy of
    transcription jobs. This function returns as soon as the vocabulary processing
    is started. Call get_vocabulary to get the current status of the vocabulary.
    The vocabulary is ready to use when its status is 'READY'.

    :param vocabulary_name: The name of the custom vocabulary.
    :param language_code: The language code of the vocabulary.
                          For example, en-US or nl-NL.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in the
                      vocabulary.
    :return: Information about the newly created vocabulary.
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
```

```
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.create_vocabulary(**vocab_args)
        logger.info("Created custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't create custom vocabulary %s.", vocabulary_name)
        raise
    else:
        return response



def get_vocabulary(vocabulary_name, transcribe_client):
    """
    Gets information about a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to retrieve.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: Information about the vocabulary.
    """
    try:
        response = transcribe_client.get_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Got vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't get vocabulary %s.", vocabulary_name)
        raise
    else:
        return response



def update_vocabulary(
    vocabulary_name, language_code, transcribe_client, phrases=None, table_uri=None
):
    """
    Updates an existing custom vocabulary. The entire vocabulary is replaced with
    the contents of the update.

    :param vocabulary_name: The name of the vocabulary to update.
    :param language_code: The language code of the vocabulary.
    :param transcribe_client: The Boto3 Transcribe client.
    :param phrases: A list of comma-separated phrases to include in the vocabulary.
    :param table_uri: A table of phrases and pronunciation hints to include in the
                      vocabulary.
```

```
    """
    try:
        vocab_args = {"VocabularyName": vocabulary_name, "LanguageCode":
 language_code}
        if phrases is not None:
            vocab_args["Phrases"] = phrases
        elif table_uri is not None:
            vocab_args["VocabularyFileUri"] = table_uri
        response = transcribe_client.update_vocabulary(**vocab_args)
        logger.info("Updated custom vocabulary %s.", response["VocabularyName"])
    except ClientError:
        logger.exception("Couldn't update custom vocabulary %s.", vocabulary_name)
        raise



def list_vocabularies(vocabulary_filter, transcribe_client):
    """
    Lists the custom vocabularies created for this AWS account.

    :param vocabulary_filter: The returned vocabularies must contain this string in
                              their names.
    :param transcribe_client: The Boto3 Transcribe client.
    :return: The list of retrieved vocabularies.
    """
    try:
        response =
 transcribe_client.list_vocabularies(NameContains=vocabulary_filter)
        vocabs = response["Vocabularies"]
        next_token = response.get("NextToken")
        while next_token is not None:
            response = transcribe_client.list_vocabularies(
                NameContains=vocabulary_filter, NextToken=next_token
            )
            vocabs += response["Vocabularies"]
            next_token = response.get("NextToken")
        logger.info(
            "Got %s vocabularies with filter %s.", len(vocabs), vocabulary_filter
        )
    except ClientError:
        logger.exception(
            "Couldn't list vocabularies with filter %s.", vocabulary_filter
        )
        raise
```

```
    else:
        return vocabs



def delete_vocabulary(vocabulary_name, transcribe_client):
    """
    Deletes a custom vocabulary.

    :param vocabulary_name: The name of the vocabulary to delete.
    :param transcribe_client: The Boto3 Transcribe client.
    """
    try:
        transcribe_client.delete_vocabulary(VocabularyName=vocabulary_name)
        logger.info("Deleted vocabulary %s.", vocabulary_name)
    except ClientError:
        logger.exception("Couldn't delete vocabulary %s.", vocabulary_name)
        raise
```

Chame as funções do wrapper para transcrever áudio sem um vocabulário personalizado e, em seguida, com diferentes versões de um vocabulário personalizado para ver os melhores resultados.

```
def usage_demo():
    """Shows how to use the Amazon Transcribe service."""
    logging.basicConfig(level=logging.INFO, format="%(levelname)s: %(message)s")

    s3_resource = boto3.resource("s3")
    transcribe_client = boto3.client("transcribe")

    print("-" * 88)
    print("Welcome to the Amazon Transcribe demo!")
    print("-" * 88)

    bucket_name = f"jabber-bucket-{time.time_ns()}"
    print(f"Creating bucket {bucket_name}.")
    bucket = s3_resource.create_bucket(
        Bucket=bucket_name,
        CreateBucketConfiguration={
            "LocationConstraint": transcribe_client.meta.region_name
```

```
        },
    )
    media_file_name = ".media/Jabberwocky.mp3"
    media_object_key = "Jabberwocky.mp3"
    print(f"Uploading media file {media_file_name}.")
    bucket.upload_file(media_file_name, media_object_key)
    media_uri = f"s3://{bucket.name}/{media_object_key}"

    job_name_simple = f"Jabber-{time.time_ns()}"
    print(f"Starting transcription job {job_name_simple}.")
    start_job(
        job_name_simple,
        f"s3://{bucket_name}/{media_object_key}",
        "mp3",
        "en-US",
        transcribe_client,
    )
    transcribe_waiter = TranscribeCompleteWaiter(transcribe_client)
    transcribe_waiter.wait(job_name_simple)
    job_simple = get_job(job_name_simple, transcribe_client)
    transcript_simple = requests.get(
        job_simple["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_simple['jobName']}:")
    print(transcript_simple["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print(
        "Creating a custom vocabulary that lists the nonsense words to try to "
        "improve the transcription."
    )
    vocabulary_name = f"Jabber-vocabulary-{time.time_ns()}"
    create_vocabulary(
        vocabulary_name,
        "en-US",
        transcribe_client,
        phrases=[
            "brillig",
            "slithy",
            "borogoves",
            "mome",
            "raths",
            "Jub-Jub",
            "frumious",
```

```
            "manxome",
            "Tumtum",
            "uffish",
            "whiffling",
            "tulgey",
            "thou",
            "frabjous",
            "callooh",
            "callay",
            "chortled",
        ],
    )
    vocabulary_ready_waiter = VocabularyReadyWaiter(transcribe_client)
    vocabulary_ready_waiter.wait(vocabulary_name)

    job_name_vocabulary_list = f"Jabber-vocabulary-list-{time.time_ns()}"
    print(f"Starting transcription job {job_name_vocabulary_list}.")
    start_job(
        job_name_vocabulary_list,
        media_uri,
        "mp3",
        "en-US",
        transcribe_client,
        vocabulary_name,
    )
    transcribe_waiter.wait(job_name_vocabulary_list)
    job_vocabulary_list = get_job(job_name_vocabulary_list, transcribe_client)
    transcript_vocabulary_list = requests.get(
        job_vocabulary_list["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_vocabulary_list['jobName']}:")
    print(transcript_vocabulary_list["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print(
        "Updating the custom vocabulary with table data that provides additional "
        "pronunciation hints."
    )
    table_vocab_file = "jabber-vocabulary-table.txt"
    bucket.upload_file(table_vocab_file, table_vocab_file)
    update_vocabulary(
        vocabulary_name,
        "en-US",
        transcribe_client,
```

```
        table_uri=f"s3://{bucket.name}/{table_vocab_file}",
    )
    vocabulary_ready_waiter.wait(vocabulary_name)

    job_name_vocab_table = f"Jabber-vocab-table-{time.time_ns()}"
    print(f"Starting transcription job {job_name_vocab_table}.")
    start_job(
        job_name_vocab_table,
        media_uri,
        "mp3",
        "en-US",
        transcribe_client,
        vocabulary_name=vocabulary_name,
    )
    transcribe_waiter.wait(job_name_vocab_table)
    job_vocab_table = get_job(job_name_vocab_table, transcribe_client)
    transcript_vocab_table = requests.get(
        job_vocab_table["Transcript"]["TranscriptFileUri"]
    ).json()
    print(f"Transcript for job {transcript_vocab_table['jobName']}:")
    print(transcript_vocab_table["results"]["transcripts"][0]["transcript"])

    print("-" * 88)
    print("Getting data for jobs and vocabularies.")
    jabber_jobs = list_jobs("Jabber", transcribe_client)
    print(f"Found {len(jabber_jobs)} jobs:")
    for job_sum in jabber_jobs:
        job = get_job(job_sum["TranscriptionJobName"], transcribe_client)
        print(
            f"\t{job['TranscriptionJobName']}, {job['Media']['MediaFileUri']}, "
            f"{job['Settings'].get('VocabularyName')}"
        )

    jabber_vocabs = list_vocabularies("Jabber", transcribe_client)
    print(f"Found {len(jabber_vocabs)} vocabularies:")
    for vocab_sum in jabber_vocabs:
        vocab = get_vocabulary(vocab_sum["VocabularyName"], transcribe_client)
        vocab_content = requests.get(vocab["DownloadUri"]).text
        print(f"\t{vocab['VocabularyName']} contents:")
        print(vocab_content)

    print("-" * 88)
    print("Deleting demo jobs.")
```

```
    for job_name in [job_name_simple, job_name_vocabulary_list,
job_name_vocab_table]:
        delete_job(job_name, transcribe_client)
    print("Deleting demo vocabulary.")
    delete_vocabulary(vocabulary_name, transcribe_client)
    print("Deleting demo bucket.")
    bucket.objects.delete()
    bucket.delete()
    print("Thanks for watching!")
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - CreateVocabulary
  - DeleteTranscriptionJob
  - DeleteVocabulary
  - GetTranscriptionJob
  - GetVocabulary
  - ListVocabularies
  - StartTranscriptionJob
  - UpdateVocabulary

Transcrever áudio e obter dados do trabalho

O código de exemplo a seguir mostra como:

- Inicie um trabalho de transcrição com o Amazon Transcribe.
- Aguarde a conclusão do trabalho .
- Obtenha a URI em que a transcrição está armazenada.

Para obter mais informações, consulte Começar a usar o Amazon Transcribe.

SDK para Python (Boto3)

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
import time
import boto3


def transcribe_file(job_name, file_uri, transcribe_client):
    transcribe_client.start_transcription_job(
        TranscriptionJobName=job_name,
        Media={"MediaFileUri": file_uri},
        MediaFormat="wav",
        LanguageCode="en-US",
    )

    max_tries = 60
    while max_tries > 0:
        max_tries -= 1
        job = transcribe_client.get_transcription_job(TranscriptionJobName=job_name)
        job_status = job["TranscriptionJob"]["TranscriptionJobStatus"]
        if job_status in ["COMPLETED", "FAILED"]:
            print(f"Job {job_name} is {job_status}.")
            if job_status == "COMPLETED":
                print(
                    f"Download the transcript from\n"
                    f"\t{job['TranscriptionJob']['Transcript']
['TranscriptFileUri']}."
                )
            break
        else:
            print(f"Waiting for {job_name}. Current status is {job_status}.")
        time.sleep(10)


def main():
    transcribe_client = boto3.client("transcribe")
    file_uri = "s3://test-transcribe/answer2.wav"
```

```
    transcribe_file("Example-job", file_uri, transcribe_client)


if __name__ == "__main__":
    main()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Python (Boto3).
  - GetTranscriptionJob
  - StartTranscriptionJob

Exemplos de serviços cruzados usando o SDK para Python (Boto3)

Os aplicativos de exemplo a seguir usam o AWS SDK for Python (Boto3) para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma API REST do API Gateway para monitorar dados da COVID-19
- Criar uma API REST de biblioteca de empréstimos
- Criar uma aplicação de mensageiro com o Step Functions
- Criar uma aplicação Web para monitorar dados do DynamoDB
- Criar uma aplicação de chat websocket com o API Gateway
- Crie um rastreador de itens de trabalho do Aurora Sem Servidor
- Criar uma aplicação de exploração do Amazon Textract
- Detectar entidades em texto extraído de uma imagem usando um AWS SDK
- Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK
- Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK
- Usar o API Gateway para invocar uma função do Lambda
- Usar eventos programados para chamar uma função do Lambda

Criar uma API REST do API Gateway para monitorar dados da COVID-19

SDK para Python (Boto3)

Mostra como usar o AWS Chalice com o AWS SDK for Python (Boto3) para criar uma API REST sem servidor que usa o Amazon API Gateway, o AWS Lambda e o Amazon DynamoDB. O exemplo de código a seguir simula um sistema que monitora casos diários de COVID-19 nos Estados Unidos, usando dados fictícios. Aprenda como:

- Usar o AWS Chalice para definir rotas nas funções do Lambda que são chamadas para lidar com solicitações REST provenientes do API Gateway.
- Usar as funções do Lambda para recuperar e armazenar dados em uma tabela do DynamoDB para atender a solicitações REST.
- Definir recursos de função de segurança e estrutura de tabela em um modelo do AWS CloudFormation.
- Use AWS Chalice e CloudFormation para empacotar e implantar todos os recursos necessários.
- Use CloudFormation para limpar todos os recursos criados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- AWS CloudFormation
- DynamoDB
- Lambda

Criar uma API REST de biblioteca de empréstimos

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com a API do Amazon Relational Database Service (Amazon RDS) e o AWS Chalice a fim de criar uma API REST com suporte por um banco de dados do Amazon Aurora. O serviço da Web é uma tecnologia sem servidor e representa uma biblioteca de empréstimos simples, na qual os clientes podem pegar e devolver livros emprestados. Aprenda como:

- Crie e gerencie um cluster de banco de dados Aurora com tecnologia sem servidor.
- Utilize o AWS Secrets Manager para gerenciar credenciais de bancos de dados.
- Implemente uma camada de armazenamento de dados que use o Amazon RDS para mover dados para dentro e fora do banco de dados.
- Use o AWS Chalice para implantar uma API REST com tecnologia sem servidor no Amazon API Gateway e no AWS Lambda.
- Use o pacote Requests para enviar solicitações ao serviço Web.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Aurora
- Lambda
- Secrets Manager

Criar uma aplicação de mensageiro com o Step Functions

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o AWS Step Functions para criar uma aplicação de mensageiro que recupere registros de mensagens de uma tabela do Amazon DynamoDB e os envia com o Amazon Simple Queue Service (Amazon SQS). A máquina de estado se integra a uma função do AWS Lambda para verificar o banco de dados em busca de mensagens não enviadas.

- Crie uma máquina de estado que recupere e atualize registros de mensagens de uma tabela do Amazon DynamoDB.
- Atualize a definição de máquina de estado para enviar mensagens ao Amazon Simple Queue Service (Amazon SQS).
- Inicie e interrompa execuções da máquina de estado.
- Conecte-se ao Lambda, ao DynamoDB e ao Amazon SQS por meio de uma máquina de estado usando integrações de serviço.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

Criar uma aplicação Web para monitorar dados do DynamoDB

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para construir um serviço REST que monitora itens de trabalho no Amazon DynamoDB e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa a estrutura web Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST de Flask que se integre com Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em uma tabela do DynamoDB.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo no Repositório de exemplos de AWS código em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon SES

Criar uma aplicação de chat websocket com o API Gateway

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon API Gateway V2 para criar uma API de Websocket que se integra ao AWS Lambda e ao Amazon DynamoDB.

- Crie uma API de Websocket atendida pelo API Gateway.
- Defina um manipulador do Lambda que armazena conexões no DynamoDB e publica mensagens para outros participantes do chat.

- Conecte-se à aplicação de chat websocket e envie mensagens com o pacote Websockets.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda

Crie um rastreador de itens de trabalho do Aurora Sem Servidor

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar um serviço REST que rastreia itens de trabalho no banco de dados do Amazon Aurora Sem Servidor e envia relatórios por e-mail usando o Amazon Simple Email Service (Amazon SES). Este exemplo usa o framework da Web do Flask para lidar com o roteamento HTTP e se integra a uma página da Web do React para apresentar uma aplicação Web totalmente funcional.

- Crie um serviço REST do Flask que se integre a Serviços da AWS.
- Leia, grave e atualize itens de trabalho armazenados em um banco de dados do Aurora Sem Servidor.
- Crie um segredo do AWS Secrets Manager que contenha credenciais do banco de dados e use-o a fim de autenticar chamadas para o banco de dados.
- Use o Amazon SES para enviar relatórios por e-mail de itens de trabalho.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Aurora
- Amazon RDS
- Serviços de dados do Amazon RDS
- Amazon SES

Criar uma aplicação de exploração do Amazon Textract

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) com o Amazon Textract para detectar elementos de texto, formulários e tabelas em uma imagem de documento. A imagem de entrada e a saída do Amazon Textract são mostradas em uma aplicaçãoTkinter que permite explorar os elementos detectados.

- Envie uma imagem de documento para o Amazon Textract e explore a saída dos elementos detectados.
- Envie imagens diretamente para o Amazon Textract ou por meio de um bucket do Amazon Simple Storage Service (Amazon S3).
- Use APIs assíncronas para iniciar um trabalho que publica uma notificação em um tópico do Amazon Simple Notification Service (Amazon SNS) quando o trabalho for concluído.
- Faça uma pesquisa em uma fila do Amazon Simple Queue Service (Amazon SQS) para obter uma mensagem de conclusão do trabalho e exiba os resultados.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon S3
- Amazon SNS
- Amazon SQS
- Amazon Textract

Detectar entidades em texto extraído de uma imagem usando um AWS SDK

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) em um bloco de anotações Jupyter para detectar entidades em texto extraído de uma imagem. Este exemplo usa o Amazon Textract para extrair texto de uma imagem armazenada no Amazon Simple Storage Service (Amazon S3) e no Amazon Comprehend para detectar entidades no texto extraído.

Este exemplo é um bloco de anotações Jupyter e deve ser executado em um ambiente que possa hospedar blocos de anotações. Para obter instruções sobre como executar o exemplo usando a Amazon SageMaker, consulte as instruções em TextractAndComprehendNotebook.ipynb.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Amazon S3
- Amazon Textract

Detectar objetos em imagens com o Amazon Rekognition usando um AWS SDK

SDK para Python (Boto3)

Mostra como usar o AWS SDK for Python (Boto3) para criar uma aplicação Web que permite a você fazer o seguinte:

- Carregar fotos em um bucket do Amazon Simple Storage Service (Amazon S3).
- Usar o Amazon Rekognition para analisar e rotular as fotos.
- Usar o Amazon Simple Email Service (Amazon SES) para enviar relatórios de análise da imagem por e-mail.

Este exemplo contém dois componentes principais: uma página da Web criada com React e um serviço REST escrito em Python criado com Flask-RESTful. JavaScript

Você pode usar a página da Web do React para:

- Exibir uma lista de imagens que estão armazenadas no bucket do S3.
- Carregar imagens do computador para o bucket do S3.
- Exibir imagens e rótulos que identificam os itens detectados na imagem.
- Obter um relatório de todas as imagens no bucket do S3 e enviar um relatório por e-mail.

A página da Web chama o serviço REST. O serviço envia solicitações à AWS para realizar as seguintes ações:

- Obter e filtrar a lista de imagens no bucket do S3.
- Carregar fotos no bucket do S3.

- Usar o Amazon Rekognition para analisar fotos individuais e obter uma lista dos rótulos que identifiquem os itens detectados nas fotos.
- Analisar todas as fotos no bucket do S3 e usar o Amazon SES para enviar um relatório por e-mail.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3
- Amazon SES

Detectar pessoas e objetos em um vídeo com o Amazon Rekognition usando um AWS SDK

SDK para Python (Boto3)

Use o Amazon Rekognition para detectar rostos, objetos e pessoas em vídeos iniciando trabalhos de detecção assíncrona. Este exemplo também configura o Amazon Rekognition para notificar um tópico do Amazon Simple Notification Service (Amazon SNS) quando os trabalhos são concluídos e inscreve uma fila do Amazon Simple Queue Service (Amazon SQS) no tópico. Quando a fila recebe uma mensagem sobre um trabalho, o trabalho é recuperado e os resultados são apresentados.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon SNS
- Amazon SQS

Usar o API Gateway para invocar uma função do Lambda

SDK para Python (Boto3)

Este exemplo mostra como criar e usar uma API REST do Amazon API Gateway cujo alvo é uma função do AWS Lambda. O manipulador do Lambda mostra como rotear com base em métodos HTTP; como obter dados da string de consulta, do cabeçalho e do corpo e como retornar uma resposta JSON.

- Implante uma função do Lambda.
- Crie uma API REST do API Gateway.
- Crie um recurso REST cujo alvo seja a função do Lambda.
- Conceda permissão para que o API Gateway possa invocar a função do Lambda.
- Use o pacote Requests para enviar solicitações à API REST.
- Limpe todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- API Gateway
- Lambda

Usar eventos programados para chamar uma função do Lambda

SDK para Python (Boto3)

Este exemplo mostra como registrar uma AWS Lambda função como alvo de um EventBridge evento programado da Amazon. O manipulador do Lambda grava uma mensagem amigável e os dados completos do evento no Amazon CloudWatch Logs para recuperação posterior.

- Implanta uma função do Lambda
- Cria um evento EventBridge agendado e torna a função Lambda o alvo.
- Concede permissão para permitir a EventBridge invocação da função Lambda.
- Imprime os dados mais recentes do CloudWatch Logs para mostrar o resultado das invocações programadas.
- Limpa todos os recursos criados durante a demonstração.

Este exemplo é melhor visualizado em GitHub. Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- CloudWatch Registros
- EventBridge
- Lambda

Exemplos de código do SDK para Ruby

Os exemplos a seguir mostram como usar o AWS SDK for Ruby com o AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para Ruby : Saiba mais sobre como usar o Ruby com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Ruby
- Exemplos entre serviços usando o SDK para Ruby

Ações e cenários usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com a Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- CloudTrail exemplos usando o SDK for Ruby
- CloudWatch exemplos usando o SDK for Ruby
- Exemplos do DynamoDB usando o SDK para Ruby
- Exemplos do Amazon EC2 usando o SDK para Ruby
- Exemplos do Elastic Beanstalk usando o SDK for Ruby
- EventBridge exemplos usando o SDK for Ruby
- Exemplos de AWS Glue usando o SDK para Ruby
- Exemplos do IAM usando o SDK para Ruby
- Exemplos de AWS KMS usando o SDK para Ruby
- Exemplos de Lambda usando o SDK para Ruby
- Exemplos do Amazon Polly usando o SDK for Ruby
- Exemplos do Amazon RDS usando o SDK para Ruby
- Exemplos do Amazon S3 usando o SDK para Ruby
- Exemplos do Amazon SES usando o SDK for Ruby
- Exemplos da API v2 do Amazon SES usando o SDK for Ruby
- Exemplos do Amazon SNS usando o SDK para Ruby
- Exemplos do Amazon SQS usando o SDK para Ruby
- Exemplos de AWS STS usando o SDK para Ruby
- WorkDocs Exemplos da Amazon usando o SDK for Ruby

CloudTrail exemplos usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby with CloudTrail.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Crie trilhas

O exemplo de código a seguir mostra como criar uma AWS CloudTrail trilha.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail" # v2: require 'aws-sdk'
require "aws-sdk-s3"
require "aws-sdk-sts"

def create_trail_example(s3_client, sts_client, cloudtrail_client, trail_name,
 bucket_name)

  resp = sts_client.get_caller_identity({})
  account_id = resp.account

  # Attach policy to an Amazon Simple Storage Service (S3) bucket.
  s3_client.create_bucket(bucket: bucket_name)
  begin
    policy = {
```

```
      "Version" => "2012-10-17",
      "Statement" => [
        {
          "Sid" => "AWSCloudTrailAclCheck20150319",
          "Effect" => "Allow",
          "Principal" => {
            "Service" => "cloudtrail.amazonaws.com"
          },
          "Action" => "s3:GetBucketAcl",
          "Resource" => "arn:aws:s3:::#{bucket_name}"
        },
        {
          "Sid" => "AWSCloudTrailWrite20150319",
          "Effect" => "Allow",
          "Principal" => {
            "Service" => "cloudtrail.amazonaws.com"
          },
          "Action" => "s3:PutObject",
          "Resource" => "arn:aws:s3:::#{bucket_name}/AWSLogs/#{account_id}/*",
          "Condition" => {
            "StringEquals" => {
              "s3:x-amz-acl" => "bucket-owner-full-control"
            }
          }
        }
      ]
    }.to_json

    s3_client.put_bucket_policy(
      bucket: bucket_name,
      policy: policy
    )
    puts "Successfully added policy to bucket #{bucket_name}"
  end

  begin
    cloudtrail_client.create_trail({
                                      name: trail_name, # required
                                      s3_bucket_name: bucket_name # required
                                    })

    puts "Successfully created trail: #{trail_name}."
  rescue StandardError => e
    puts "Got error trying to create trail #{trail_name}:\n #{e}"
```

```
    puts e
    exit 1
  end
```

- Para obter detalhes da API, consulte CreateTrail a Referência AWS SDK for Ruby da API.

Excluir trilha

O exemplo de código a seguir mostra como excluir uma AWS CloudTrail trilha.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  client.delete_trail({
                        name: trail_name # required
                      })
  puts "Successfully deleted trail: " + trail_name
rescue StandardError => err
  puts "Got error trying to delete trail: " + trail_name + ":"
  puts err
  exit 1
end
```

- Para obter detalhes da API, consulte DeleteTrail a Referência AWS SDK for Ruby da API.

Listar eventos de trilhas

O exemplo de código a seguir mostra como listar eventos de AWS CloudTrail trilha.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail" # v2: require 'aws-sdk'

# @param [Object] client
def lookup_events_example(client)
  resp = client.lookup_events
  puts "Found #{resp.events.count} events:"
  resp.events.each do |e|
    puts "Event name:   #{e.event_name}"
    puts "Event ID:     #{e.event_id}"
    puts "Event time:   #{e.event_time}"
    puts "Resources:"

    e.resources.each do |r|
      puts "  Name:       #{r.resource_name}"
      puts "  Type:       #{r.resource_type}"
      puts ""
    end
  end
end
```

- Para obter detalhes da API, consulte LookupEventsa Referência AWS SDK for Ruby da API.

Listar trilhas

O exemplo de código a seguir mostra como listar AWS CloudTrail trilhas.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudtrail"  # v2: require 'aws-sdk'

def describe_trails_example(client)
  resp = client.describe_trails({})
  puts "Found #{resp.trail_list.count} trail(s)."

  resp.trail_list.each do |trail|
    puts "Name:           " + trail.name
    puts "S3 bucket name: " + trail.s3_bucket_name
    puts
  end
```

- Para obter detalhes da API, consulte ListTrailsa Referência AWS SDK for Ruby da API.

CloudWatch exemplos usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby with CloudWatch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates or updates an alarm in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param alarm_name [String] The name of the alarm.
# @param alarm_description [String] A description about the alarm.
# @param metric_name [String] The name of the metric associated with the alarm.
# @param alarm_actions [Array] A list of Strings representing the
#   Amazon Resource Names (ARNs) to execute when the alarm transitions to the
#   ALARM state.
# @param namespace [String] The namespace for the metric to alarm on.
# @param statistic [String] The statistic for the metric.
# @param dimensions [Array] A list of dimensions for the metric, specified as
#   Aws::CloudWatch::Types::Dimension.
# @param period [Integer] The number of seconds before re-evaluating the metric.
# @param unit [String] The unit of measure for the statistic.
# @param evaluation_periods [Integer] The number of periods over which data is
#   compared to the specified threshold.
# @param theshold [Float] The value against which the specified statistic is
 compared.
# @param comparison_operator [String] The arithmetic operation to use when
#   comparing the specified statistic and threshold.
# @return [Boolean] true if the alarm was created or updated; otherwise, false.
# @example
#   exit 1 unless alarm_created_or_updated?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
```

```
#     'ObjectsInBucket',
#     'Objects exist in this bucket for more than 1 day.',
#     'NumberOfObjects',
#     ['arn:aws:sns:us-east-1:111111111111:Default_CloudWatch_Alarms_Topic'],
#     'AWS/S3',
#     'Average',
#     [
#       {
#         name: 'BucketName',
#         value: 'doc-example-bucket'
#       },
#       {
#         name: 'StorageType',
#         value: 'AllStorageTypes'
#       }
#     ],
#     86_400,
#     'Count',
#     1,
#     1,
#     'GreaterThanThreshold'
#   )
def alarm_created_or_updated?(
  cloudwatch_client,
  alarm_name,
  alarm_description,
  metric_name,
  alarm_actions,
  namespace,
  statistic,
  dimensions,
  period,
  unit,
  evaluation_periods,
  threshold,
  comparison_operator
)
  cloudwatch_client.put_metric_alarm(
    alarm_name: alarm_name,
    alarm_description: alarm_description,
    metric_name: metric_name,
    alarm_actions: alarm_actions,
    namespace: namespace,
    statistic: statistic,
```

```
    dimensions: dimensions,
    period: period,
    unit: unit,
    evaluation_periods: evaluation_periods,
    threshold: threshold,
    comparison_operator: comparison_operator
  )
  return true
rescue StandardError => e
  puts "Error creating alarm: #{e.message}"
  return false
end
```

- Para obter detalhes da API, consulte PutMetricAlarma Referência AWS SDK for Ruby da API.

Descrever alarmes

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudwatch"

# Lists the names of available Amazon CloudWatch alarms.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @example
#   list_alarms(Aws::CloudWatch::Client.new(region: 'us-east-1'))
def list_alarms(cloudwatch_client)
  response = cloudwatch_client.describe_alarms
  if response.metric_alarms.count.positive?
    response.metric_alarms.each do |alarm|
      puts alarm.alarm_name
    end
```

```
  else
    puts "No alarms found."
  end
rescue StandardError => e
  puts "Error getting information about alarms: #{e.message}"
end
```

- Para obter detalhes da API, consulte DescribeAlarmsa Referência AWS SDK for Ruby da API.

Descrever alarmes para uma métrica

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon para uma métrica.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @example
#   describe_metric_alarms(Aws::CloudWatch::Client.new(region: 'us-east-1'))
def describe_metric_alarms(cloudwatch_client)
  response = cloudwatch_client.describe_alarms

  if response.metric_alarms.count.positive?
    response.metric_alarms.each do |alarm|
      puts "-" * 16
      puts "Name:           " + alarm.alarm_name
      puts "State value:    " + alarm.state_value
      puts "State reason:   " + alarm.state_reason
      puts "Metric:         " + alarm.metric_name
      puts "Namespace:      " + alarm.namespace
      puts "Statistic:      " + alarm.statistic
      puts "Period:         " + alarm.period.to_s
```

```
      puts "Unit:           " + alarm.unit.to_s
      puts "Eval. periods:  " + alarm.evaluation_periods.to_s
      puts "Threshold:      " + alarm.threshold.to_s
      puts "Comp. operator: " + alarm.comparison_operator

      if alarm.key?(:ok_actions) && alarm.ok_actions.count.positive?
        puts "OK actions:"
        alarm.ok_actions.each do |a|
          puts "  " + a
        end
      end

      if alarm.key?(:alarm_actions) && alarm.alarm_actions.count.positive?
        puts "Alarm actions:"
        alarm.alarm_actions.each do |a|
          puts "  " + a
        end
      end

      if alarm.key?(:insufficient_data_actions) &&
          alarm.insufficient_data_actions.count.positive?
        puts "Insufficient data actions:"
        alarm.insufficient_data_actions.each do |a|
          puts "  " + a
        end
      end

      puts "Dimensions:"
      if alarm.key?(:dimensions) && alarm.dimensions.count.positive?
        alarm.dimensions.each do |d|
          puts "  Name: " + d.name + ", Value: " + d.value
        end
      else
        puts "  None for this alarm."
      end
    end
  else
    puts "No alarms found."
  end
rescue StandardError => e
  puts "Error getting information about alarms: #{e.message}"
end

# Example usage:
```

```
def run_me
  region = ""

  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby cw-ruby-example-show-alarms.rb REGION"
    puts "Example: ruby cw-ruby-example-show-alarms.rb us-east-1"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    region = "us-east-1"
  # Otherwise, use the values as specified at the command prompt.
  else
    region = ARGV[0]
  end

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)
  puts "Available alarms:"
  describe_metric_alarms(cloudwatch_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeAlarmsForMetrica Referência AWS SDK for Ruby da API.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Disables an alarm in Amazon CloudWatch.
#
```

```
# Prerequisites.
#
# - The alarm to disable.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param alarm_name [String] The name of the alarm to disable.
# @return [Boolean] true if the alarm was disabled; otherwise, false.
# @example
#   exit 1 unless alarm_actions_disabled?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'ObjectsInBucket'
#   )
def alarm_actions_disabled?(cloudwatch_client, alarm_name)
  cloudwatch_client.disable_alarm_actions(alarm_names: [alarm_name])
  return true
rescue StandardError => e
  puts "Error disabling alarm actions: #{e.message}"
  return false
end

# Example usage:
def run_me
  alarm_name = "ObjectsInBucket"
  alarm_description = "Objects exist in this bucket for more than 1 day."
  metric_name = "NumberOfObjects"
  # Notify this Amazon Simple Notification Service (Amazon SNS) topic when
  # the alarm transitions to the ALARM state.
  alarm_actions = ["arn:aws:sns:us-
east-1:111111111111:Default_CloudWatch_Alarms_Topic"]
  namespace = "AWS/S3"
  statistic = "Average"
  dimensions = [
    {
      name: "BucketName",
      value: "doc-example-bucket"
    },
    {
      name: "StorageType",
      value: "AllStorageTypes"
    }
  ]
  period = 86_400 # Daily (24 hours * 60 minutes * 60 seconds = 86400 seconds).
  unit = "Count"
```

```
  evaluation_periods = 1 # More than one day.
  threshold = 1 # One object.
  comparison_operator = "GreaterThanThreshold" # More than one object.
  # Replace us-west-2 with the AWS Region you're using for Amazon CloudWatch.
  region = "us-east-1"

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)

  if alarm_created_or_updated?(
    cloudwatch_client,
    alarm_name,
    alarm_description,
    metric_name,
    alarm_actions,
    namespace,
    statistic,
    dimensions,
    period,
    unit,
    evaluation_periods,
    threshold,
    comparison_operator
  )
    puts "Alarm '#{alarm_name}' created or updated."
  else
    puts "Could not create or update alarm '#{alarm_name}'."
  end

  if alarm_actions_disabled?(cloudwatch_client, alarm_name)
    puts "Alarm '#{alarm_name}' disabled."
  else
    puts "Could not disable alarm '#{alarm_name}'."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DisableAlarmActionsa Referência AWS SDK for Ruby da API.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists available metrics for a metric namespace in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param metric_namespace [String] The namespace of the metric.
# @example
#   list_metrics_for_namespace(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'SITE/TRAFFIC'
#   )
def list_metrics_for_namespace(cloudwatch_client, metric_namespace)
  response = cloudwatch_client.list_metrics(namespace: metric_namespace)

  if response.metrics.count.positive?
    response.metrics.each do |metric|
      puts "  Metric name: #{metric.metric_name}"
      if metric.dimensions.count.positive?
        puts "    Dimensions:"
        metric.dimensions.each do |dimension|
          puts "      Name: #{dimension.name}, Value: #{dimension.value}"
        end
      else
        puts "No dimensions found."
      end
    end
  else
    puts "No metrics found for namespace '#{metric_namespace}'. " \
      "Note that it could take up to 15 minutes for recently-added metrics " \
      "to become available."
```

```
  end
end

# Example usage:
def run_me
  metric_namespace = "SITE/TRAFFIC"
  # Replace us-west-2 with the AWS Region you're using for Amazon CloudWatch.
  region = "us-east-1"

  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)

  # Add three datapoints.
  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
    "UniqueVisitors",
    "SiteName",
    "example.com",
    5_885.0,
    "Count"
  )

  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
    "UniqueVisits",
    "SiteName",
    "example.com",
    8_628.0,
    "Count"
  )

  puts "Continuing..." unless datapoint_added_to_metric?(
    cloudwatch_client,
    metric_namespace,
    "PageViews",
    "PageURL",
    "example.html",
    18_057.0,
    "Count"
  )

  puts "Metrics for namespace '#{metric_namespace}':"
  list_metrics_for_namespace(cloudwatch_client, metric_namespace)
```

```
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListMetricsa Referência AWS SDK for Ruby da API.

Inserir dados em uma métrica

O exemplo de código a seguir mostra como publicar pontos de dados métricos na Amazon CloudWatch.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-cloudwatch"

# Adds a datapoint to a metric in Amazon CloudWatch.
#
# @param cloudwatch_client [Aws::CloudWatch::Client]
#   An initialized CloudWatch client.
# @param metric_namespace [String] The namespace of the metric to add the
#   datapoint to.
# @param metric_name [String] The name of the metric to add the datapoint to.
# @param dimension_name [String] The name of the dimension to add the
#   datapoint to.
# @param dimension_value [String] The value of the dimension to add the
#   datapoint to.
# @param metric_value [Float] The value of the datapoint.
# @param metric_unit [String] The unit of measurement for the datapoint.
# @return [Boolean]
# @example
#   exit 1 unless datapoint_added_to_metric?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'SITE/TRAFFIC',
#     'UniqueVisitors',
```

```
#     'SiteName',
#     'example.com',
#     5_885.0,
#     'Count'
#   )
def datapoint_added_to_metric?(
  cloudwatch_client,
  metric_namespace,
  metric_name,
  dimension_name,
  dimension_value,
  metric_value,
  metric_unit
)
  cloudwatch_client.put_metric_data(
    namespace: metric_namespace,
    metric_data: [
      {
        metric_name: metric_name,
        dimensions: [
          {
            name: dimension_name,
            value: dimension_value
          }
        ],
        value: metric_value,
        unit: metric_unit
      }
    ]
  )
  puts "Added data about '#{metric_name}' to namespace " \
    "'#{metric_namespace}'."
  return true
rescue StandardError => e
  puts "Error adding data about '#{metric_name}' to namespace " \
    "'#{metric_namespace}': #{e.message}"
  return false
end
```

- Para obter detalhes da API, consulte PutMetricDataa Referência AWS SDK for Ruby da API.

Exemplos do DynamoDB usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Ruby com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table
```

```
  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Creates an Amazon DynamoDB table that can be used to store movie data.
  # The table uses the release year of the movie as the partition key and the
  # title as the sort key.
  #
  # @param table_name [String] The name of the table to create.
  # @return [Aws::DynamoDB::Table] The newly created table.
  def create_table(table_name)
    @table = @dynamo_resource.create_table(
      table_name: table_name,
      key_schema: [
        {attribute_name: "year", key_type: "HASH"},  # Partition key
        {attribute_name: "title", key_type: "RANGE"}  # Sort key
      ],
      attribute_definitions: [
        {attribute_name: "year", attribute_type: "N"},
        {attribute_name: "title", attribute_type: "S"}
      ],
      provisioned_throughput: {read_capacity_units: 10, write_capacity_units: 10})
    @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
    @table
  rescue Aws::DynamoDB::Errors::ServiceError => e
    @logger.error("Failed create table #{table_name}:\n#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateTablea Referência AWS SDK for Ruby da API.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Deletes the table.
  def delete_table
    @table.delete
    @table = nil
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't delete table. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Ruby da API.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Deletes a movie from the table.
  #
  # @param title [String] The title of the movie to delete.
  # @param year [Integer] The release year of the movie to delete.
  def delete_item(title, year)
    @table.delete_item(key: {"year" => year, "title" => title})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't delete movie #{title}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteItema Referência AWS SDK for Ruby da API.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Gets movie data from the table for a specific movie.
  #
  # @param title [String] The title of the movie.
  # @param year [Integer] The release year of the movie.
  # @return [Hash] The data about the requested movie.
  def get_item(title, year)
    @table.get_item(key: {"year" => year, "title" => title})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't get movie #{title} (#{year}) from table #{@table.name}:\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetItema Referência AWS SDK for Ruby da API.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Determines whether a table exists. As a side effect, stores the table in
  # a member variable.
  #
  # @param table_name [String] The name of the table to check.
  # @return [Boolean] True when the table exists; otherwise, False.
  def exists?(table_name)
    @dynamo_resource.client.describe_table(table_name: table_name)
    @logger.debug("Table #{table_name} exists")
  rescue Aws::DynamoDB::Errors::ResourceNotFoundException
    @logger.debug("Table #{table_name} doesn't exist")
    false
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't check for existence of #{table_name}:\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DescribeTablea Referência AWS SDK for Ruby da API.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determine se uma tabela existe.

```
# Encapsulates an Amazon DynamoDB table of movie data.
class Scaffold
  attr_reader :dynamo_resource
  attr_reader :table_name
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table_name = table_name
    @table = nil
    @logger = Logger.new($stdout)
    @logger.level = Logger::DEBUG
  end

  # Determines whether a table exists. As a side effect, stores the table in
  # a member variable.
  #
  # @param table_name [String] The name of the table to check.
  # @return [Boolean] True when the table exists; otherwise, False.
  def exists?(table_name)
    @dynamo_resource.client.describe_table(table_name: table_name)
    @logger.debug("Table #{table_name} exists")
  rescue Aws::DynamoDB::Errors::ResourceNotFoundException
    @logger.debug("Table #{table_name} doesn't exist")
    false
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't check for existence of #{table_name}:\n")
    puts("\t#{e.code}: #{e.message}")
```

```
    raise
  end
```

- Para obter detalhes da API, consulte ListTablesa Referência AWS SDK for Ruby da API.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Adds a movie to the table.
  #
  # @param movie [Hash] The title, year, plot, and rating of the movie.
  def add_item(movie)
    @table.put_item(
      item: {
        "year" => movie[:year],
        "title" => movie[:title],
        "info" => {"plot" => movie[:plot], "rating" => movie[:rating]}})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't add movie #{title} to table #{@table.name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte PutItema Referência AWS SDK for Ruby da API.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Queries for movies that were released in the specified year.
  #
  # @param year [Integer] The year to query.
  # @return [Array] The list of movies that were released in the specified year.
  def query_items(year)
    response = @table.query(
      key_condition_expression: "#yr = :year",
      expression_attribute_names: {"#yr" => "year"},
      expression_attribute_values: {":year" => year})
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't query for movies released in #{year}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    response.items
  end
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK for Ruby.

Executar uma instrução PartiQL

O exemplo de código a seguir mostra como executar uma instrução PartiQL em uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Selecione um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Gets a single record from a table using PartiQL.
  # Note: To perform more fine-grained selects,
  # use the Client.query instance method instead.
  #
  # @param title [String] The title of the movie to search.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def select_item_by_title(title)
    request = {
      statement: "SELECT * FROM \"#{@table.name}\" WHERE title=?",
      parameters: [title]
    }
    @dynamodb.client.execute_statement(request)
```

```
  end
```

Atualize um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Updates a single record from a table using PartiQL.
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @param rating [Float] The new rating to assign the title.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def update_rating_by_title(title, year, rating)
    request = {
      statement: "UPDATE \"#{@table.name}\" SET info.rating=? WHERE title=? and
 year=?",
      parameters: [{ "N": rating }, title, year]
    }
    @dynamodb.client.execute_statement(request)
  end
```

Adicione um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
```

```
  end

  # Adds a single record to a table using PartiQL.
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @param plot [String] The plot of the movie.
  # @param rating [Float] The new rating to assign the title.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def insert_item(title, year, plot, rating)
    request = {
      statement: "INSERT INTO \"#{@table.name}\" VALUE {'title': ?, 'year': ?,
 'info': ?}",
      parameters: [title, year, {'plot': plot, 'rating': rating}]
    }
    @dynamodb.client.execute_statement(request)
  end
```

Exclua um único item usando o PartiQL.

```
class DynamoDBPartiQLSingle

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Deletes a single record from a table using PartiQL.
  #
  # @param title [String] The title of the movie to update.
  # @param year [Integer] The year the movie was released.
  # @return [Aws::DynamoDB::Types::ExecuteStatementOutput]
  def delete_item_by_title(title, year)
    request = {
      statement: "DELETE FROM \"#{@table.name}\" WHERE title=? and year=?",
      parameters: [title, year]
    }
    @dynamodb.client.execute_statement(request)
```

```
  end
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Ruby da API.

Executar lotes de instruções PartiQL

O exemplo de código a seguir mostra como executar lotes de instruções PartiQL em uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Leia um lote de itens usando o PartiQL.

```
class DynamoDBPartiQLBatch

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Selects a batch of items from a table using PartiQL
  #
  # @param batch_titles [Array] Collection of movie titles
  # @return [Aws::DynamoDB::Types::BatchExecuteStatementOutput]
  def batch_execute_select(batch_titles)
    request_items = batch_titles.map do |title, year|
      {
        statement: "SELECT * FROM \"#{@table.name}\" WHERE title=? and year=?",
        parameters: [title, year]
```

```
      }
    end
    @dynamodb.client.batch_execute_statement({statements: request_items})
  end
```

Exclua um lote de itens usando o PartiQL.

```
class DynamoDBPartiQLBatch

  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamodb = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamodb.table(table_name)
  end

  # Deletes a batch of items from a table using PartiQL
  #
  # @param batch_titles [Array] Collection of movie titles
  # @return [Aws::DynamoDB::Types::BatchExecuteStatementOutput]
  def batch_execute_write(batch_titles)
    request_items = batch_titles.map do |title, year|
      {
        statement: "DELETE FROM \"#{@table.name}\" WHERE title=? and year=?",
        parameters: [title, year]
      }
    end
    @dynamodb.client.batch_execute_statement({statements: request_items})
  end
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Ruby da API.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWSCode Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Scans for movies that were released in a range of years.
  # Uses a projection expression to return a subset of data for each movie.
  #
  # @param year_range [Hash] The range of years to retrieve.
  # @return [Array] The list of movies released in the specified years.
  def scan_items(year_range)
    movies = []
    scan_hash = {
      filter_expression: "#yr between :start_yr and :end_yr",
      projection_expression: "#yr, title, info.rating",
      expression_attribute_names: {"#yr" => "year"},
      expression_attribute_values: {
        ":start_yr" => year_range[:start], ":end_yr" => year_range[:end]}
    }
    done = false
    start_key = nil
    until done
      scan_hash[:exclusive_start_key] = start_key unless start_key.nil?
      response = @table.scan(scan_hash)
      movies.concat(response.items) unless response.items.empty?
      start_key = response.last_evaluated_key
      done = start_key.nil?
    end
  rescue Aws::DynamoDB::Errors::ServiceError => e
```

```
    puts("Couldn't scan for movies. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    movies
  end
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK for Ruby.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Updates rating and plot data for a movie in the table.
  #
  # @param movie [Hash] The title, year, plot, rating of the movie.
  def update_item(movie)

    response = @table.update_item(
      key: {"year" => movie[:year], "title" => movie[:title]},
      update_expression: "set info.rating=:r",
      expression_attribute_values: { ":r" => movie[:rating] },
      return_values: "UPDATED_NEW")
```

```
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts("Couldn't update movie #{movie[:title]} (#{movie[:year]}) in table
 #{@table.name}\n")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    response.attributes
  end
```

- Para obter detalhes da API, consulte UpdateItema Referência AWS SDK for Ruby da API.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class DynamoDBBasics
  attr_reader :dynamo_resource
  attr_reader :table

  def initialize(table_name)
    client = Aws::DynamoDB::Client.new(region: "us-east-1")
    @dynamo_resource = Aws::DynamoDB::Resource.new(client: client)
    @table = @dynamo_resource.table(table_name)
  end

  # Fills an Amazon DynamoDB table with the specified data. Items are sent in
  # batches of 25 until all items are written.
  #
  # @param movies [Enumerable] The data to put in the table. Each item must contain
 at least
  #                            the keys required by the schema that was specified
 when the
```

```
  #                             table was created.
  def write_batch(movies)
    index = 0
    slice_size = 25
    while index < movies.length
      movie_items = []
      movies[index, slice_size].each do |movie|
        movie_items.append({put_request: { item: movie }})
      end
      @dynamo_resource.client.batch_write_item({request_items: { @table.name =>
movie_items }})
      index += slice_size
    end
  rescue Aws::DynamoDB::Errors::ServiceError => e
    puts(
      "Couldn't load data into table #{@table.name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte BatchWriteItema Referência AWS SDK for Ruby da API.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Crie uma classe que encapsule uma tabela do DynamoDB.

```
# Creates an Amazon DynamoDB table that can be used to store movie data.
# The table uses the release year of the movie as the partition key and the
# title as the sort key.
#
# @param table_name [String] The name of the table to create.
# @return [Aws::DynamoDB::Table] The newly created table.
def create_table(table_name)
  @table = @dynamo_resource.create_table(
    table_name: table_name,
    key_schema: [
      {attribute_name: "year", key_type: "HASH"},  # Partition key
      {attribute_name: "title", key_type: "RANGE"}  # Sort key
    ],
    attribute_definitions: [
      {attribute_name: "year", attribute_type: "N"},
      {attribute_name: "title", attribute_type: "S"}
    ],
    provisioned_throughput: {read_capacity_units: 10, write_capacity_units: 10})
  @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
  @table
rescue Aws::DynamoDB::Errors::ServiceError => e
  @logger.error("Failed create table #{table_name}:\n#{e.code}: #{e.message}")
  raise
end
```

Crie uma função auxiliar para baixar e extrair o arquivo JSON de exemplo.

```
# Gets sample movie data, either from a local file or by first downloading it from
# the Amazon DynamoDB Developer Guide.
#
```

```
  # @param movie_file_name [String] The local file name where the movie data is
 stored in JSON format.
  # @return [Hash] The movie data as a Hash.
  def fetch_movie_data(movie_file_name)
    if !File.file?(movie_file_name)
      @logger.debug("Downloading #{movie_file_name}...")
      movie_content = URI.open(
        "https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/
moviedata.zip"
      )
      movie_json = ""
      Zip::File.open_buffer(movie_content) do |zip|
        zip.each do |entry|
          movie_json = entry.get_input_stream.read
        end
      end
    else
      movie_json = File.read(movie_file_name)
    end
    movie_data = JSON.parse(movie_json)
    # The sample file lists over 4000 movies. This returns only the first 250.
    movie_data.slice(0, 250)
  rescue StandardError => e
    puts("Failure downloading movie data:\n#{e}")
    raise
  end
```

Execute um cenário interativo para criar a tabela e executar ações nela.

```
  table_name = "doc-example-table-movies-#{rand(10**4)}"
  scaffold = Scaffold.new(table_name)
  dynamodb_wrapper = DynamoDBBasics.new(table_name)

  new_step(1, "Create a new DynamoDB table if none already exists.")
  unless scaffold.exists?(table_name)
    puts("\nNo such table: #{table_name}. Creating it...")
    scaffold.create_table(table_name)
    print "Done!\n".green
  end

  new_step(2, "Add a new record to the DynamoDB table.")
  my_movie = {}
```

```
 my_movie[:title] = CLI::UI::Prompt.ask("Enter the title of a movie to add to the
table. E.g. The Matrix")
 my_movie[:year] = CLI::UI::Prompt.ask("What year was it released? E.g. 1989").to_i
 my_movie[:rating] = CLI::UI::Prompt.ask("On a scale of 1 - 10, how do you rate it?
E.g. 7").to_i
 my_movie[:plot] = CLI::UI::Prompt.ask("Enter a brief summary of the plot. E.g. A
man awakens to a new reality.")
 dynamodb_wrapper.add_item(my_movie)
 puts("\nNew record added:")
 puts JSON.pretty_generate(my_movie).green
 print "Done!\n".green

 new_step(3, "Update a record in the DynamoDB table.")
 my_movie[:rating] = CLI::UI::Prompt.ask("Let's update the movie you added with a
new rating, e.g. 3:").to_i
 response = dynamodb_wrapper.update_item(my_movie)
 puts("Updated '#{my_movie[:title]}' with new attributes:")
 puts JSON.pretty_generate(response).green
 print "Done!\n".green

 new_step(4, "Get a record from the DynamoDB table.")
 puts("Searching for #{my_movie[:title]} (#{my_movie[:year]})...")
 response = dynamodb_wrapper.get_item(my_movie[:title], my_movie[:year])
 puts JSON.pretty_generate(response).green
 print "Done!\n".green

 new_step(5, "Write a batch of items into the DynamoDB table.")
 download_file = "moviedata.json"
 puts("Downloading movie database to #{download_file}...")
 movie_data = scaffold.fetch_movie_data(download_file)
 puts("Writing movie data from #{download_file} into your table...")
 scaffold.write_batch(movie_data)
 puts("Records added: #{movie_data.length}.")
 print "Done!\n".green

 new_step(5, "Query for a batch of items by key.")
 loop do
   release_year = CLI::UI::Prompt.ask("Enter a year between 1972 and 2018, e.g.
1999:").to_i
   results = dynamodb_wrapper.query_items(release_year)
   if results.any?
     puts("There were #{results.length} movies released in #{release_year}:")
     results.each do |movie|
       print "\t #{movie["title"]}".green
```

```
      end
      break
    else
      continue = CLI::UI::Prompt.ask("Found no movies released in #{release_year}!
Try another year? (y/n)")
      break if !continue.eql?("y")
    end
  end
  print "\nDone!\n".green

  new_step(6, "Scan for a batch of items using a filter expression.")
  years = {}
  years[:start] = CLI::UI::Prompt.ask("Enter a starting year between 1972 and
2018:")
  years[:end] = CLI::UI::Prompt.ask("Enter an ending year between 1972 and 2018:")
  releases = dynamodb_wrapper.scan_items(years)
  if !releases.empty?
    puts("Found #{releases.length} movies.")
    count = Question.ask(
      "How many do you want to see? ", method(:is_int), in_range(1,
releases.length))
    puts("Here are your #{count} movies:")
    releases.take(count).each do |release|
      puts("\t#{release["title"]}")
    end
  else
    puts("I don't know about any movies released between #{years[:start]} "\
         "and #{years[:end]}.")
  end
  print "\nDone!\n".green

  new_step(7, "Delete an item from the DynamoDB table.")
  answer = CLI::UI::Prompt.ask("Do you want to remove '#{my_movie[:title]}'? (y/n)
")
  if answer.eql?("y")
    dynamodb_wrapper.delete_item(my_movie[:title], my_movie[:year])
    puts("Removed '#{my_movie[:title]}' from the table.")
    print "\nDone!\n".green
  end

  new_step(8, "Delete the DynamoDB table.")
  answer = CLI::UI::Prompt.ask("Delete the table? (y/n)")
  if answer.eql?("y")
    scaffold.delete_table
```

```
    puts("Deleted #{table_name}.")
  else
    puts("Don't forget to delete the table when you're done!")
  end
  print "\nThanks for watching!\n".green
rescue Aws::Errors::ServiceError
  puts("Something went wrong with the demo.")
rescue Errno::ENOENT
  true
end
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Consultar uma tabela usando lotes de instruções PartiQL

O código de exemplo a seguir mostra como:

- Obter um lote de itens executando várias instruções SELECT.
- Adicionar um lote de itens executando várias instruções INSERT.
- Atualizar um lote de itens executando várias instruções UPDATE.
- Excluir um lote de itens executando várias instruções DELETE.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL em lotes.

```
table_name = "doc-example-table-movies-partiql-#{rand(10**4)}"
scaffold = Scaffold.new(table_name)
sdk = DynamoDBPartiQLBatch.new(table_name)

new_step(1, "Create a new DynamoDB table if none already exists.")
unless scaffold.exists?(table_name)
  puts("\nNo such table: #{table_name}. Creating it...")
  scaffold.create_table(table_name)
  print "Done!\n".green
end

new_step(2, "Populate DynamoDB table with movie data.")
download_file = "moviedata.json"
puts("Downloading movie database to #{download_file}...")
movie_data = scaffold.fetch_movie_data(download_file)
puts("Writing movie data from #{download_file} into your table...")
scaffold.write_batch(movie_data)
puts("Records added: #{movie_data.length}.")
print "Done!\n".green

new_step(3, "Select a batch of items from the movies table.")
puts "Let's select some popular movies for side-by-side comparison."
response = sdk.batch_execute_select([["Mean Girls", 2004], ["Goodfellas", 1977],
["The Prancing of the Lambs", 2005]])
puts("Items selected: #{response['responses'].length}\n")
print "\nDone!\n".green

new_step(4, "Delete a batch of items from the movies table.")
sdk.batch_execute_write([["Mean Girls", 2004], ["Goodfellas", 1977], ["The
Prancing of the Lambs", 2005]])
print "\nDone!\n".green

new_step(5, "Delete the table.")
```

```
  if scaffold.exists?(table_name)
    scaffold.delete_table
  end
end
```

- Para obter detalhes da API, consulte BatchExecuteStatementa Referência AWS SDK for Ruby da API.

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Execute um cenário que crie uma tabela e execute consultas do PartiQL.

```
table_name = "doc-example-table-movies-partiql-#{rand(10**8)}"
scaffold = Scaffold.new(table_name)
sdk = DynamoDBPartiQLSingle.new(table_name)

new_step(1, "Create a new DynamoDB table if none already exists.")
unless scaffold.exists?(table_name)
  puts("\nNo such table: #{table_name}. Creating it...")
  scaffold.create_table(table_name)
  print "Done!\n".green
end
```

```
  new_step(2, "Populate DynamoDB table with movie data.")
  download_file = "moviedata.json"
  puts("Downloading movie database to #{download_file}...")
  movie_data = scaffold.fetch_movie_data(download_file)
  puts("Writing movie data from #{download_file} into your table...")
  scaffold.write_batch(movie_data)
  puts("Records added: #{movie_data.length}.")
  print "Done!\n".green

  new_step(3, "Select a single item from the movies table.")
  response = sdk.select_item_by_title("Star Wars")
  puts("Items selected for title 'Star Wars': #{response.items.length}\n")
  print "#{response.items.first}".yellow
  print "\n\nDone!\n".green

  new_step(4, "Update a single item from the movies table.")
  puts "Let's correct the rating on The Big Lebowski to 10.0."
  sdk.update_rating_by_title("The Big Lebowski", 1998, 10.0)
  print "\nDone!\n".green

  new_step(5, "Delete a single item from the movies table.")
  puts "Let's delete The Silence of the Lambs because it's just too scary."
  sdk.delete_item_by_title("The Silence of the Lambs", 1991)
  print "\nDone!\n".green

  new_step(6, "Insert a new item into the movies table.")
  puts "Let's create a less-scary movie called The Prancing of the Lambs."
  sdk.insert_item("The Prancing of the Lambs", 2005, "A movie about happy
 livestock.", 5.0)
  print "\nDone!\n".green

  new_step(7, "Delete the table.")
  if scaffold.exists?(table_name)
    scaffold.delete_table
  end
end
```

- Para obter detalhes da API, consulte ExecuteStatementa Referência AWS SDK for Ruby da API.

Exemplos do Amazon EC2 usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico para o Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates an Elastic IP address in Amazon Virtual Private Cloud (Amazon VPC).
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @return [String] The allocation ID corresponding to the Elastic IP address.
# @example
#   puts allocate_elastic_ip_address(Aws::EC2::Client.new(region: 'us-west-2'))
def allocate_elastic_ip_address(ec2_client)
  response = ec2_client.allocate_address(domain: "vpc")
  return response.allocation_id
```

```
rescue StandardError => e
  puts "Error allocating Elastic IP address: #{e.message}"
  return "Error"
end
```

- Para obter detalhes da API, consulte AllocateAddressa Referência AWS SDK for Ruby da API.

Para associar um endereço IP elástico a uma instância

O exemplo de código a seguir mostra como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Associates an Elastic IP address with an Amazon Elastic Compute Cloud
# (Amazon EC2) instance.
#
# Prerequisites:
#
# - The allocation ID corresponding to the Elastic IP address.
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param allocation_id [String] The ID of the allocation corresponding to
#   the Elastic IP address.
# @param instance_id [String] The ID of the instance.
# @return [String] The assocation ID corresponding to the association of the
#   Elastic IP address to the instance.
# @example
#   puts allocate_elastic_ip_address(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'eipalloc-04452e528a66279EX',
#     'i-033c48ef067af3dEX')
def associate_elastic_ip_address_with_instance(
  ec2_client,
```

```
  allocation_id,
  instance_id
)
  response = ec2_client.associate_address(
    allocation_id: allocation_id,
    instance_id: instance_id,
  )
  return response.association_id
rescue StandardError => e
  puts "Error associating Elastic IP address with instance: #{e.message}"
  return "Error"
end
```

- Para obter detalhes da API, consulte AssociateAddressa Referência AWS SDK for Ruby da API.

Criar uma Amazon Virtual Private Cloud (Amazon VPC)

O exemplo de código a seguir mostra como criar uma Amazon Virtual Private Cloud (Amazon VPC).

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Creates a virtual private cloud (VPC) in
# Amazon Virtual Private Cloud (Amazon VPC) and then tags
# the VPC.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
# @param cidr_block [String] The IPv4 CIDR block for the subnet.
# @param tag_key [String] The key portion of the tag for the VPC.
# @param tag_value [String] The value portion of the tag for the VPC.
# @return [Boolean] true if the VPC was created and tagged;
```

```
#   otherwise, false.
# @example
#   exit 1 unless vpc_created_and_tagged?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     '10.0.0.0/24',
#     'my-key',
#     'my-value'
#   )
def vpc_created_and_tagged?(
  ec2_resource,
  cidr_block,
  tag_key,
  tag_value
)
  vpc = ec2_resource.create_vpc(cidr_block: cidr_block)

  # Create a public DNS by enabling DNS support and DNS hostnames.
  vpc.modify_attribute(enable_dns_support: { value: true })
  vpc.modify_attribute(enable_dns_hostnames: { value: true })

  vpc.create_tags(tags: [{ key: tag_key, value: tag_value }])

  puts "Created VPC with ID '#{vpc.id}' and tagged with key " \
    "'#{tag_key}' and value '#{tag_value}'."
  return true
rescue StandardError => e
  puts "#{e.message}"
  return false
end

# Example usage:
def run_me
  cidr_block = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-create-vpc.rb " \
      "CIDR_BLOCK TAG_KEY TAG_VALUE REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-create-vpc.rb " \
      "10.0.0.0/24 my-key my-value us-west-2"
    exit 1
```

```
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    cidr_block = "10.0.0.0/24"
    tag_key = "my-key"
    tag_value = "my-value"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    cidr_block = ARGV[0]
    tag_key = ARGV[1]
    tag_value = ARGV[2]
    region = ARGV[3]
  end

  ec2_resource = Aws::EC2::Resource.new(region: region)

  if vpc_created_and_tagged?(
    ec2_resource,
    cidr_block,
    tag_key,
    tag_value
  )
    puts "VPC created and tagged."
  else
    puts "VPC not created or not tagged."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateVpca Referência AWS SDK for Ruby da API.

Crie uma tabela de rotas

O exemplo de código a seguir mostra como criar uma tabela de rotas e associá-la à sub-rede do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - A VPC in Amazon VPC.
# - A subnet in that VPC.
# - A gateway attached to that subnet.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
# @param vpc_id [String] The ID of the VPC for the route table.
# @param subnet_id [String] The ID of the subnet for the route table.
# @param gateway_id [String] The ID of the gateway for the route.
# @param destination_cidr_block [String] The destination CIDR block
#   for the route.
# @param tag_key [String] The key portion of the tag for the route table.
# @param tag_value [String] The value portion of the tag for the route table.
# @return [Boolean] true if the route table was created and associated;
#   otherwise, false.
# @example
#   exit 1 unless route_table_created_and_associated?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     'vpc-0b6f769731EXAMPLE',
#     'subnet-03d9303b57EXAMPLE',
#     'igw-06ca90c011EXAMPLE',
#     '0.0.0.0/0',
#     'my-key',
#     'my-value'
#   )
def route_table_created_and_associated?(
  ec2_resource,
  vpc_id,
  subnet_id,
  gateway_id,
```

```
  destination_cidr_block,
  tag_key,
  tag_value
)
  route_table = ec2_resource.create_route_table(vpc_id: vpc_id)
  puts "Created route table with ID '#{route_table.id}'."
  route_table.create_tags(
    tags: [
      {
        key: tag_key,
        value: tag_value
      }
    ]
  )
  puts "Added tags to route table."
  route_table.create_route(
    destination_cidr_block: destination_cidr_block,
    gateway_id: gateway_id
  )
  puts "Created route with destination CIDR block " \
    "'#{destination_cidr_block}' and associated with gateway " \
    "with ID '#{gateway_id}'."
  route_table.associate_with_subnet(subnet_id: subnet_id)
  puts "Associated route table with subnet with ID '#{subnet_id}'."
  return true
rescue StandardError => e
  puts "Error creating or associating route table: #{e.message}"
  puts "If the route table was created but not associated, you should " \
    "clean up by deleting the route table."
  return false
end

# Example usage:
def run_me
  vpc_id = ""
  subnet_id = ""
  gateway_id = ""
  destination_cidr_block = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage: ruby ec2-ruby-example-create-route-table.rb " \
```

```
      "VPC_ID SUBNET_ID GATEWAY_ID DESTINATION_CIDR_BLOCK " \
      "TAG_KEY TAG_VALUE REGION"
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-create-route-table.rb " \
      "vpc-0b6f769731EXAMPLE subnet-03d9303b57EXAMPLE igw-06ca90c011EXAMPLE " \
      "'0.0.0.0/0' my-key my-value us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    vpc_id = "vpc-0b6f769731EXAMPLE"
    subnet_id = "subnet-03d9303b57EXAMPLE"
    gateway_id = "igw-06ca90c011EXAMPLE"
    destination_cidr_block = "0.0.0.0/0"
    tag_key = "my-key"
    tag_value = "my-value"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    vpc_id = ARGV[0]
    subnet_id = ARGV[1]
    gateway_id = ARGV[2]
    destination_cidr_block = ARGV[3]
    tag_key = ARGV[4]
    tag_value = ARGV[5]
    region = ARGV[6]
  end

  ec2_resource = Aws::EC2::Resource.new(region: region)

  if route_table_created_and_associated?(
    ec2_resource,
    vpc_id,
    subnet_id,
    gateway_id,
    destination_cidr_block,
    tag_key,
    tag_value
  )
    puts "Route table created and associated."
  else
    puts "Route table not created or not associated."
  end
end
```

```
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateRouteTablea Referência AWS SDK for Ruby da API.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example does the following:
# 1. Creates an Amazon Elastic Compute Cloud (Amazon EC2) security group.
# 2. Adds inbound rules to the security group.
# 3. Displays information about available security groups.
# 4. Deletes the security group.

require "aws-sdk-ec2"

# Creates an Amazon Elastic Compute Cloud (Amazon EC2) security group.
#
# Prerequisites:
#
# - A VPC in Amazon Virtual Private Cloud (Amazon VPC).
#
# @param ec2_client [Aws::EC2::Client] An initialized
#   Amazon EC2 client.
# @param group_name [String] A name for the security group.
# @param description [String] A description for the security group.
# @param vpc_id [String] The ID of the VPC for the security group.
# @return [String] The ID of security group that was created.
# @example
```

```
#   puts create_security_group(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-security-group',
#     'This is my security group.',
#     'vpc-6713dfEX'
#   )
def create_security_group(
  ec2_client,
  group_name,
  description,
  vpc_id
)
  security_group = ec2_client.create_security_group(
    group_name: group_name,
    description: description,
    vpc_id: vpc_id
  )
  puts "Created security group '#{group_name}' with ID " \
    "'#{security_group.group_id}' in VPC with ID '#{vpc_id}'."
  return security_group.group_id
rescue StandardError => e
  puts "Error creating security group: #{e.message}"
  return "Error"
end

# Adds an inbound rule to an Amazon Elastic Compute Cloud (Amazon EC2)
# security group.
#
# Prerequisites:
#
# - The security group.
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @param security_group_id [String] The ID of the security group.
# @param ip_protocol [String] The network protocol for the inbound rule.
# @param from_port [String] The originating port for the inbound rule.
# @param to_port [String] The destination port for the inbound rule.
# @param cidr_ip_range [String] The CIDR IP range for the inbound rule.
# @return
# @example
#   exit 1 unless security_group_ingress_authorized?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'sg-030a858e078f1b9EX',
#     'tcp',
```

```
#     '80',
#     '80',
#     '0.0.0.0/0'
#   )
def security_group_ingress_authorized?(
  ec2_client,
  security_group_id,
  ip_protocol,
  from_port,
  to_port,
  cidr_ip_range
)
  ec2_client.authorize_security_group_ingress(
    group_id: security_group_id,
    ip_permissions: [
      {
        ip_protocol: ip_protocol,
        from_port: from_port,
        to_port: to_port,
        ip_ranges: [
          {
            cidr_ip: cidr_ip_range
          }
        ]
      }
    ]
  )
  puts "Added inbound rule to security group '#{security_group_id}' for protocol " \
    "'#{ip_protocol}' from port '#{from_port}' to port '#{to_port}' " \
    "with CIDR IP range '#{cidr_ip_range}'."
  return true
rescue StandardError => e
  puts "Error adding inbound rule to security group: #{e.message}"
  return false
end

# Displays information about a security group's IP permissions set in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# Prerequisites:
#
# - A security group with inbound rules, outbound rules, or both.
#
# @param p [Aws::EC2::Types::IpPermission] The IP permissions set.
```

```
# @example
#   ec2_client = Aws::EC2::Client.new(region: 'us-west-2')
#   response = ec2_client.describe_security_groups
#   unless sg.ip_permissions.empty?
#     describe_security_group_permissions(
#       response.security_groups[0].ip_permissions[0]
#     )
#   end
def describe_security_group_permissions(perm)
  print "  Protocol: #{perm.ip_protocol == '-1' ? 'All' : perm.ip_protocol}"

  unless perm.from_port.nil?
    if perm.from_port == "-1" || perm.from_port == -1
      print ", From: All"
    else
      print ", From: #{perm.from_port}"
    end
  end

  unless perm.to_port.nil?
    if perm.to_port == "-1" || perm.to_port == -1
      print ", To: All"
    else
      print ", To: #{perm.to_port}"
    end
  end

  if perm.key?(:ipv_6_ranges) && perm.ipv_6_ranges.count.positive?
    print ", CIDR IPv6: #{perm.ipv_6_ranges[0].cidr_ipv_6}"
  end

  if perm.key?(:ip_ranges) && perm.ip_ranges.count.positive?
    print ", CIDR IPv4: #{perm.ip_ranges[0].cidr_ip}"
  end

  print "\n"
end

# Displays information about available security groups in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @example
#   describe_security_groups(Aws::EC2::Client.new(region: 'us-west-2'))
```

```
def describe_security_groups(ec2_client)
  response = ec2_client.describe_security_groups

  if response.security_groups.count.positive?
    response.security_groups.each do |sg|
      puts "-" * (sg.group_name.length + 13)
      puts "Name:        #{sg.group_name}"
      puts "Description: #{sg.description}"
      puts "Group ID:    #{sg.group_id}"
      puts "Owner ID:    #{sg.owner_id}"
      puts "VPC ID:      #{sg.vpc_id}"

      if sg.tags.count.positive?
        puts "Tags:"
        sg.tags.each do |tag|
          puts "  Key: #{tag.key}, Value: #{tag.value}"
        end
      end

      unless sg.ip_permissions.empty?
        puts "Inbound rules:" if sg.ip_permissions.count.positive?
        sg.ip_permissions.each do |p|
          describe_security_group_permissions(p)
        end
      end

      unless sg.ip_permissions_egress.empty?
        puts "Outbound rules:" if sg.ip_permissions.count.positive?
        sg.ip_permissions_egress.each do |p|
          describe_security_group_permissions(p)
        end
      end
    end
  else
    puts "No security groups found."
  end
rescue StandardError => e
  puts "Error getting information about security groups: #{e.message}"
end

# Deletes an Amazon Elastic Compute Cloud (Amazon EC2)
# security group.
#
# Prerequisites:
```

```
#
# - The security group.
#
# @param ec2_client [Aws::EC2::Client] An initialized
#   Amazon EC2 client.
# @param security_group_id [String] The ID of the security group to delete.
# @return [Boolean] true if the security group was deleted; otherwise, false.
# @example
#   exit 1 unless security_group_deleted?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'sg-030a858e078f1b9EX'
#   )
def security_group_deleted?(ec2_client, security_group_id)
  ec2_client.delete_security_group(group_id: security_group_id)
  puts "Deleted security group '#{security_group_id}'."
  return true
rescue StandardError => e
  puts "Error deleting security group: #{e.message}"
  return false
end

# Example usage:
def run_me
  group_name = ""
  description = ""
  vpc_id = ""
  ip_protocol_http = ""
  from_port_http = ""
  to_port_http = ""
  cidr_ip_range_http = ""
  ip_protocol_ssh = ""
  from_port_ssh = ""
  to_port_ssh = ""
  cidr_ip_range_ssh = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-security-group.rb " \
      "GROUP_NAME DESCRIPTION VPC_ID IP_PROTOCOL_1 FROM_PORT_1 TO_PORT_1 " \
      "CIDR_IP_RANGE_1 IP_PROTOCOL_2 FROM_PORT_2 TO_PORT_2 " \
      "CIDR_IP_RANGE_2 REGION"
    puts "Example: ruby ec2-ruby-example-security-group.rb " \
      "my-security-group 'This is my security group.' vpc-6713dfEX " \
      "tcp 80 80 '0.0.0.0/0' tcp 22 22 '0.0.0.0/0' us-west-2"
```

```
  exit 1
# If no values are specified at the command prompt, use these default values.
elsif ARGV.count.zero?
  group_name = "my-security-group"
  description = "This is my security group."
  vpc_id = "vpc-6713dfEX"
  ip_protocol_http = "tcp"
  from_port_http = "80"
  to_port_http = "80"
  cidr_ip_range_http = "0.0.0.0/0"
  ip_protocol_ssh = "tcp"
  from_port_ssh = "22"
  to_port_ssh = "22"
  cidr_ip_range_ssh = "0.0.0.0/0"
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  region = "us-west-2"
# Otherwise, use the values as specified at the command prompt.
else
  group_name = ARGV[0]
  description = ARGV[1]
  vpc_id = ARGV[2]
  ip_protocol_http = ARGV[3]
  from_port_http = ARGV[4]
  to_port_http = ARGV[5]
  cidr_ip_range_http = ARGV[6]
  ip_protocol_ssh = ARGV[7]
  from_port_ssh = ARGV[8]
  to_port_ssh = ARGV[9]
  cidr_ip_range_ssh = ARGV[10]
  region = ARGV[11]
end

security_group_id = ""
security_group_exists = false
ec2_client = Aws::EC2::Client.new(region: region)

puts "Attempting to create security group..."
security_group_id = create_security_group(
  ec2_client,
  group_name,
  description,
  vpc_id
)
if security_group_id == "Error"
```

```
    puts "Could not create security group. Skipping this step."
  else
    security_group_exists = true
  end

  if security_group_exists
    puts "Attempting to add inbound rules to security group..."
    unless security_group_ingress_authorized?(
      ec2_client,
      security_group_id,
      ip_protocol_http,
      from_port_http,
      to_port_http,
      cidr_ip_range_http
    )
      puts "Could not add inbound HTTP rule to security group. " \
        "Skipping this step."
    end

    unless security_group_ingress_authorized?(
      ec2_client,
      security_group_id,
      ip_protocol_ssh,
      from_port_ssh,
      to_port_ssh,
      cidr_ip_range_ssh
    )
      puts "Could not add inbound SSH rule to security group. " \
        "Skipping this step."
    end
  end

  puts "\nInformation about available security groups:"
  describe_security_groups(ec2_client)

  if security_group_exists
    puts "\nAttempting to delete security group..."
    unless security_group_deleted?(ec2_client, security_group_id)
      puts "Could not delete security group. You must delete it yourself."
    end
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateSecurityGroupa Referência AWS SDK for Ruby da API.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example does the following:
# 1. Creates a key pair in Amazon Elastic Compute Cloud (Amazon EC2).
# 2. Displays information about available key pairs.
# 3. Deletes the key pair.

require "aws-sdk-ec2"

# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param key_pair_name [String] The name for the key pair and private
#   key file.
# @return [Boolean] true if the key pair and private key file were
#   created; otherwise, false.
# @example
#   exit 1 unless key_pair_created?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-key-pair'
#   )
def key_pair_created?(ec2_client, key_pair_name)
  key_pair = ec2_client.create_key_pair(key_name: key_pair_name)
  puts "Created key pair '#{key_pair.key_name}' with fingerprint " \
    "'#{key_pair.key_fingerprint}' and ID '#{key_pair.key_pair_id}'."
  filename = File.join(Dir.home, key_pair_name + ".pem")
  File.open(filename, "w") { |file| file.write(key_pair.key_material) }
  puts "Private key file saved locally as '#{filename}'."
```

```
  return true
rescue Aws::EC2::Errors::InvalidKeyPairDuplicate
  puts "Error creating key pair: a key pair named '#{key_pair_name}' " \
    "already exists."
  return false
rescue StandardError => e
  puts "Error creating key pair or saving private key file: #{e.message}"
  return false
end

# Displays information about available key pairs in
# Amazon Elastic Compute Cloud (Amazon EC2).
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   describe_key_pairs(Aws::EC2::Client.new(region: 'us-west-2'))
def describe_key_pairs(ec2_client)
  result = ec2_client.describe_key_pairs
  if result.key_pairs.count.zero?
    puts "No key pairs found."
  else
    puts "Key pair names:"
    result.key_pairs.each do |key_pair|
      puts key_pair.key_name
    end
  end
rescue StandardError => e
  puts "Error getting information about key pairs: #{e.message}"
end

# Deletes a key pair in Amazon Elastic Compute Cloud (Amazon EC2).
#
# Prerequisites:
#
# - The key pair to delete.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param key_pair_name [String] The name of the key pair to delete.
# @return [Boolean] true if the key pair was deleted; otherwise, false.
# @example
#   exit 1 unless key_pair_deleted?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'my-key-pair'
#   )
```

```
def key_pair_deleted?(ec2_client, key_pair_name)
  ec2_client.delete_key_pair(key_name: key_pair_name)
  return true
rescue StandardError => e
  puts "Error deleting key pair: #{e.message}"
  return false
end

# Example usage:
def run_me
  key_pair_name = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-key-pairs.rb KEY_PAIR_NAME REGION"
    puts "Example: ruby ec2-ruby-example-key-pairs.rb my-key-pair us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    key_pair_name = "my-key-pair"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    key_pair_name = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Displaying existing key pair names before creating this key pair..."
  describe_key_pairs(ec2_client)

  puts "-" * 10
  puts "Creating key pair..."
  unless key_pair_created?(ec2_client, key_pair_name)
    puts "Stopping program."
    exit 1
  end

  puts "-" * 10
  puts "Displaying existing key pair names after creating this key pair..."
  describe_key_pairs(ec2_client)
```

```
  puts "-" * 10
  puts "Deleting key pair..."
  unless key_pair_deleted?(ec2_client, key_pair_name)
    puts "Stopping program. You must delete the key pair yourself."
    exit 1
  end
  puts "Key pair deleted."

  puts "-" * 10
  puts "Now that the key pair is deleted, " \
    "also deleting the related private key pair file..."
  filename = File.join(Dir.home, key_pair_name + ".pem")
  File.delete(filename)
  if File.exist?(filename)
    puts "Could not delete file at '#{filename}'. You must delete it yourself."
  else
    puts "File deleted."
  end

  puts "-" * 10
  puts "Displaying existing key pair names after deleting this key pair..."
  describe_key_pairs(ec2_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateKeyPaira Referência AWS SDK for Ruby da API.

Criar uma sub-rede

Os exemplos de código a seguir mostram como criar uma sub-rede do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Creates a subnet within a virtual private cloud (VPC) in
# Amazon Virtual Private Cloud (Amazon VPC) and then tags
# the subnet.
#
# Prerequisites:
#
# - A VPC in Amazon VPC.
#
# @param ec2_resource [Aws::EC2::Resource] An initialized
#   Amazon Elastic Compute Cloud (Amazon EC2) resource object.
# @param vpc_id [String] The ID of the VPC for the subnet.
# @param cidr_block [String] The IPv4 CIDR block for the subnet.
# @param availability_zone [String] The ID of the Availability Zone
#   for the subnet.
# @param tag_key [String] The key portion of the tag for the subnet.
# @param tag_vlue [String] The value portion of the tag for the subnet.
# @return [Boolean] true if the subnet was created and tagged;
#   otherwise, false.
# @example
#   exit 1 unless subnet_created_and_tagged?(
#     Aws::EC2::Resource.new(region: 'us-west-2'),
#     'vpc-6713dfEX',
#     '10.0.0.0/24',
#     'us-west-2a',
#     'my-key',
#     'my-value'
#   )
def subnet_created_and_tagged?(
  ec2_resource,
  vpc_id,
  cidr_block,
  availability_zone,
  tag_key,
  tag_value
)
  subnet = ec2_resource.create_subnet(
    vpc_id: vpc_id,
    cidr_block: cidr_block,
    availability_zone: availability_zone
  )
  subnet.create_tags(
    tags: [
```

```
      {
        key: tag_key,
        value: tag_value
      }
    ]
  )
  puts "Subnet created with ID '#{subnet.id}' in VPC with ID '#{vpc_id}' " \
    "and CIDR block '#{cidr_block}' in availability zone " \
    "'#{availability_zone}' and tagged with key '#{tag_key}' and " \
    "value '#{tag_value}'."
  return true
rescue StandardError => e
  puts "Error creating or tagging subnet: #{e.message}"
  return false
end

# Example usage:
def run_me
  vpc_id = ""
  cidr_block = ""
  availability_zone = ""
  tag_key = ""
  tag_value = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-create-subnet.rb " \
      "VPC_ID CIDR_BLOCK AVAILABILITY_ZONE TAG_KEY TAG_VALUE REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-create-subnet.rb " \
      "vpc-6713dfEX 10.0.0.0/24 us-west-2a my-key my-value us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  elsif ARGV.count.zero?
    vpc_id = "vpc-6713dfEX"
    cidr_block = "10.0.0.0/24"
    availability_zone = "us-west-2a"
    tag_key = "my-key"
    tag_value = "my-value"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    vpc_id = ARGV[0]
```

```
    cidr_block = ARGV[1]
    availability_zone = ARGV[2]
    tag_key = ARGV[3]
    tag_value = ARGV[4]
    region = ARGV[5]
  end

  ec2_resource = Aws::EC2::Resource.new(region: region)

  if subnet_created_and_tagged?(
    ec2_resource,
    vpc_id,
    cidr_block,
    availability_zone,
    tag_key,
    tag_value
  )
    puts "Subnet created and tagged."
  else
    puts "Subnet not created or not tagged."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateSubneta Referência AWS SDK for Ruby da API.

Descrever regiões

O exemplo de código a seguir mostra como descrever as regiões do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"
```

```
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   list_regions_endpoints(Aws::EC2::Client.new(region: 'us-west-2'))
def list_regions_endpoints(ec2_client)
  result = ec2_client.describe_regions
  # Enable pretty printing.
  max_region_string_length = 16
  max_endpoint_string_length = 33
  # Print header.
  print "Region"
  print " " * (max_region_string_length - "Region".length)
  print "  Endpoint\n"
  print "-" * max_region_string_length
  print "  "
  print "-" * max_endpoint_string_length
  print "\n"
  # Print Regions and their endpoints.
  result.regions.each do |region|
    print region.region_name
    print " " * (max_region_string_length - region.region_name.length)
    print "  "
    print region.endpoint
    print "\n"
  end
end

# Displays a list of Amazon Elastic Compute Cloud (Amazon EC2)
# Availability Zones available to you depending on the AWS Region
# of the Amazon EC2 client.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @example
#   list_availability_zones(Aws::EC2::Client.new(region: 'us-west-2'))
def list_availability_zones(ec2_client)
  result = ec2_client.describe_availability_zones
  # Enable pretty printing.
  max_region_string_length = 16
  max_zone_string_length = 18
  max_state_string_length = 9
  # Print header.
  print "Region"
  print " " * (max_region_string_length - "Region".length)
  print "  Zone"
```

```
  print " " * (max_zone_string_length - "Zone".length)
  print "  State\n"
  print "-" * max_region_string_length
  print "  "
  print "-" * max_zone_string_length
  print "  "
  print "-" * max_state_string_length
  print "\n"
  # Print Regions, Availability Zones, and their states.
  result.availability_zones.each do |zone|
    print zone.region_name
    print " " * (max_region_string_length - zone.region_name.length)
    print "  "
    print zone.zone_name
    print " " * (max_zone_string_length - zone.zone_name.length)
    print "  "
    print zone.state
    # Print any messages for this Availability Zone.
    if zone.messages.count.positive?
      print "\n"
      puts "  Messages for this zone:"
      zone.messages.each do |message|
        print "    #{message.message}\n"
      end
    end
    print "\n"
  end
end

# Example usage:
def run_me
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-regions-availability-zones.rb REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-regions-availability-zones.rb us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
```

```
    region = ARGV[0]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "AWS Regions for Amazon EC2 that are available to you:"
  list_regions_endpoints(ec2_client)
  puts "\n\nAmazon EC2 Availability Zones that are available to you for AWS Region
 '#{region}':"
  list_availability_zones(ec2_client)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeRegionsa Referência AWS SDK for Ruby da API.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# @param ec2_resource [Aws::EC2::Resource] An initialized EC2 resource object.
# @example
#   list_instance_ids_states(Aws::EC2::Resource.new(region: 'us-west-2'))
def list_instance_ids_states(ec2_resource)
  response = ec2_resource.instances
  if response.count.zero?
    puts "No instances found."
  else
    puts "Instances -- ID, state:"
```

```
    response.each do |instance|
      puts "#{instance.id}, #{instance.state.name}"
    end
  end
rescue StandardError => e
  puts "Error getting information about instances: #{e.message}"
end

# Example usage:
def run_me
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-get-all-instance-info.rb REGION"
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-get-all-instance-info.rb us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    region = ARGV[0]
  end
  ec2_resource = Aws::EC2::Resource.new(region: region)
  list_instance_ids_states(ec2_resource)
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte DescribeInstancesa Referência AWS SDK for Ruby da API.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Releases an Elastic IP address from an
# Amazon Elastic Compute Cloud (Amazon EC2) instance.
#
# Prerequisites:
#
# - An Amazon EC2 instance with an associated Elastic IP address.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param allocation_id [String] The ID of the allocation corresponding to
#   the Elastic IP address.
# @return [Boolean] true if the Elastic IP address was released;
#   otherwise, false.
# @example
#   exit 1 unless elastic_ip_address_released?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'eipalloc-04452e528a66279EX'
#   )
def elastic_ip_address_released?(ec2_client, allocation_id)
  ec2_client.release_address(allocation_id: allocation_id)
  return true
rescue StandardError => e
  puts("Error releasing Elastic IP address: #{e.message}")
  return false
end
```

- Para obter detalhes da API, consulte ReleaseAddressa Referência AWS SDK for Ruby da API.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Attempts to start an Amazon Elastic Compute Cloud (Amazon EC2) instance.
#
# Prerequisites:
#
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was started; otherwise, false.
# @example
#   exit 1 unless instance_started?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_started?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive?
    state = response.instance_statuses[0].instance_state.name
    case state
    when "pending"
      puts "Error starting instance: the instance is pending. Try again later."
      return false
    when "running"
      puts "The instance is already running."
      return true
    when "terminated"
      puts "Error starting instance: " \
        "the instance is terminated, so you cannot start it."
      return false
    end
```

```
  end

  ec2_client.start_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_running, instance_ids: [instance_id])
  puts "Instance started."
  return true
rescue StandardError => e
  puts "Error starting instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "INSTANCE_ID REGION "
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to start instance '#{instance_id}' " \
    "(this might take a few minutes)..."
  unless instance_started?(ec2_client, instance_id)
    puts "Could not start instance."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte StartInstancesa Referência AWS SDK for Ruby da API.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was stopped; otherwise, false.
# @example
#   exit 1 unless instance_stopped?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_stopped?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive?
    state = response.instance_statuses[0].instance_state.name
    case state
    when "stopping"
      puts "The instance is already stopping."
      return true
    when "stopped"
      puts "The instance is already stopped."
```

```
      return true
    when "terminated"
      puts "Error stopping instance: " \
        "the instance is terminated, so you cannot stop it."
      return false
    end
  end

  ec2_client.stop_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_stopped, instance_ids: [instance_id])
  puts "Instance stopped."
  return true
rescue StandardError => e
  puts "Error stopping instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-stop-instance-i-123abc.rb " \
      "INSTANCE_ID REGION "
    # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-start-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to stop instance '#{instance_id}' " \
    "(this might take a few minutes)..."
```

```
  unless instance_stopped?(ec2_client, instance_id)
    puts "Could not stop instance."
  end
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte StopInstancesa Referência AWS SDK for Ruby da API.

Como encerrar uma instância

O exemplo de código a seguir mostra como encerrar uma instância do Amazon EC2.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ec2"

# Prerequisites:
#
# - The Amazon EC2 instance.
#
# @param ec2_client [Aws::EC2::Client] An initialized EC2 client.
# @param instance_id [String] The ID of the instance.
# @return [Boolean] true if the instance was terminated; otherwise, false.
# @example
#   exit 1 unless instance_terminated?(
#     Aws::EC2::Client.new(region: 'us-west-2'),
#     'i-123abc'
#   )
def instance_terminated?(ec2_client, instance_id)
  response = ec2_client.describe_instance_status(instance_ids: [instance_id])

  if response.instance_statuses.count.positive? &&
    response.instance_statuses[0].instance_state.name == "terminated"
```

```
    puts "The instance is already terminated."
    return true
  end

  ec2_client.terminate_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_terminated, instance_ids: [instance_id])
  puts "Instance terminated."
  return true
rescue StandardError => e
  puts "Error terminating instance: #{e.message}"
  return false
end

# Example usage:
def run_me
  instance_id = ""
  region = ""
  # Print usage information and then stop.
  if ARGV[0] == "--help" || ARGV[0] == "-h"
    puts "Usage:   ruby ec2-ruby-example-terminate-instance-i-123abc.rb " \
      "INSTANCE_ID REGION "
   # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
    puts "Example: ruby ec2-ruby-example-terminate-instance-i-123abc.rb " \
      "i-123abc us-west-2"
    exit 1
  # If no values are specified at the command prompt, use these default values.
  # Replace us-west-2 with the AWS Region you're using for Amazon EC2.
  elsif ARGV.count.zero?
    instance_id = "i-123abc"
    region = "us-west-2"
  # Otherwise, use the values as specified at the command prompt.
  else
    instance_id = ARGV[0]
    region = ARGV[1]
  end

  ec2_client = Aws::EC2::Client.new(region: region)

  puts "Attempting to terminate instance '#{instance_id}' " \
    "(this might take a few minutes)..."
  unless instance_terminated?(ec2_client, instance_id)
    puts "Could not terminate instance."
  end
```

```
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte TerminateInstancesa Referência AWS SDK for Ruby da API.

Exemplos do Elastic Beanstalk usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Elastic Beanstalk.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descreva o aplicativo

O exemplo de código a seguir mostra como descrever um AWS Elastic Beanstalk aplicativo.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Class to manage Elastic Beanstalk applications
class ElasticBeanstalkManager
  def initialize(eb_client, logger: Logger.new($stdout))
    @eb_client = eb_client
    @logger = logger
  end

  # Lists applications and their environments
  def list_applications
    @eb_client.describe_applications.applications.each do |application|
      log_application_details(application)
      list_environments(application.application_name)
    end
  rescue Aws::ElasticBeanstalk::Errors::ServiceError => e
    @logger.error("Elastic Beanstalk Service Error: #{e.message}")
  end

  private

  # Logs application details
  def log_application_details(application)
    @logger.info("Name:        #{application.application_name}")
    @logger.info("Description: #{application.description}")
  end

  # Lists and logs details of environments for a given application
  def list_environments(application_name)
    @eb_client.describe_environments(application_name:
 application_name).environments.each do |env|
      @logger.info("  Environment:  #{env.environment_name}")
      @logger.info("    URL:        #{env.cname}")
      @logger.info("    Health:     #{env.health}")
    end
  rescue Aws::ElasticBeanstalk::Errors::ServiceError => e
    @logger.error("Error listing environments for application #{application_name}:
 #{e.message}")
  end
end
```

- Para obter detalhes da API, consulte DescribeApplicationsa Referência AWS SDK for Ruby da API.

Listar pilhas

O exemplo de código a seguir mostra como listar AWS Elastic Beanstalk pilhas.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Manages listing of AWS Elastic Beanstalk solution stacks
# @param [Aws::ElasticBeanstalk::Client] eb_client
# @param [String] filter - Returns subset of results based on match
# @param [Logger] logger
class StackLister
  # Initialize with AWS Elastic Beanstalk client
  def initialize(eb_client, filter, logger: Logger.new($stdout))
    @eb_client = eb_client
    @filter = filter.downcase
    @logger = logger
  end

  # Lists and logs Elastic Beanstalk solution stacks
  def list_stacks
    stacks = @eb_client.list_available_solution_stacks.solution_stacks
    orig_length = stacks.length
    filtered_length = 0

    stacks.each do |stack|
      if @filter.empty? || stack.downcase.include?(@filter)
        @logger.info(stack)
        filtered_length += 1
      end
    end

    log_summary(filtered_length, orig_length)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Error listing solution stacks: #{e.message}")
  end

  private
```

```
  # Logs summary of listed stacks
  def log_summary(filtered_length, orig_length)
    if @filter.empty?
      @logger.info("Showed #{orig_length} stack(s)")
    else
      @logger.info("Showed #{filtered_length} stack(s) of #{orig_length}")
    end
  end
end
```

- Para obter detalhes da API, consulte ListAvailableSolutionStacksa Referência AWS SDK for Ruby da API.

Atualizar aplicativo

O exemplo de código a seguir mostra como atualizar um AWS Elastic Beanstalk aplicativo.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Manages deployment of Rails applications to AWS Elastic Beanstalk
class RailsAppDeployer
  def initialize(eb_client, s3_client, app_name, logger: Logger.new($stdout))
    @eb_client = eb_client
    @s3_client = s3_client
    @app_name = app_name
    @logger = logger
  end

  # Deploys the latest application version to Elastic Beanstalk
  def deploy
    create_storage_location
    zip_file_name = create_zip_file
    upload_zip_to_s3(zip_file_name)
    create_and_deploy_new_application_version(zip_file_name)
```

```
  end

  private

  # Creates a new S3 storage location for the application
  def create_storage_location
    resp = @eb_client.create_storage_location
    @logger.info("Created storage location in bucket #{resp.s3_bucket}")
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to create storage location: #{e.message}")
  end

  # Creates a ZIP file of the application using git
  def create_zip_file
    zip_file_basename = SecureRandom.urlsafe_base64
    zip_file_name = "#{zip_file_basename}.zip"
    `git archive --format=zip -o #{zip_file_name} HEAD`
    zip_file_name
  end

  # Uploads the ZIP file to the S3 bucket
  def upload_zip_to_s3(zip_file_name)
    zip_contents = File.read(zip_file_name)
    key = "#{@app_name}/#{zip_file_name}"
    @s3_client.put_object(body: zip_contents, bucket: fetch_bucket_name, key: key)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to upload ZIP file to S3: #{e.message}")
  end

  # Fetches the S3 bucket name from Elastic Beanstalk application versions
  def fetch_bucket_name
    app_versions = @eb_client.describe_application_versions(application_name:
@app_name)
    av = app_versions.application_versions.first
    av.source_bundle.s3_bucket
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to fetch bucket name: #{e.message}")
    raise
  end

  # Creates a new application version and deploys it
  def create_and_deploy_new_application_version(zip_file_name)
    version_label = File.basename(zip_file_name, ".zip")
    @eb_client.create_application_version(
```

```
      process: false,
      application_name: @app_name,
      version_label: version_label,
      source_bundle: {
        s3_bucket: fetch_bucket_name,
        s3_key: "#{@app_name}/#{zip_file_name}"
      },
      description: "Updated #{Time.now.strftime('%d/%m/%Y')}"
    )
    update_environment(version_label)
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to create or deploy application version: #{e.message}")
  end

  # Updates the environment to the new application version
  def update_environment(version_label)
    env_name = fetch_environment_name
    @eb_client.update_environment(
      environment_name: env_name,
      version_label: version_label
    )
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to update environment: #{e.message}")
  end

  # Fetches the environment name of the application
  def fetch_environment_name
    envs = @eb_client.describe_environments(application_name: @app_name)
    envs.environments.first.environment_name
  rescue Aws::Errors::ServiceError => e
    @logger.error("Failed to fetch environment name: #{e.message}")
    raise
  end
end
```

- Para obter detalhes da API, consulte UpdateApplicationa Referência AWS SDK for Ruby da API.

EventBridge exemplos usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby with EventBridge.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Cenários

Cenários

Criar e acionar uma regra

O exemplo de código a seguir mostra como criar e acionar uma regra na Amazon EventBridge.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Chamar as funções na ordem correta.

```
require "aws-sdk-sns"
require "aws-sdk-iam"
require "aws-sdk-cloudwatchevents"
require "aws-sdk-ec2"
require "aws-sdk-cloudwatch"
require "aws-sdk-cloudwatchlogs"
```

```
require "securerandom"
```

Verifica se o tópico do Amazon Simple Notification Service (Amazon SNS) existe dentre aqueles fornecidos para essa função.

```
# Checks whether the specified Amazon SNS
# topic exists among those provided to this function.
# This is a helper function that is called by the topic_exists? function.
#
# @param topics [Array] An array of Aws::SNS::Types::Topic objects.
# @param topic_arn [String] The ARN of the topic to find.
# @return [Boolean] true if the topic ARN was found; otherwise, false.
# @example
#   sns_client = Aws::SNS::Client.new(region: 'us-east-1')
#   response = sns_client.list_topics
#   if topic_found?(
#     response.topics,
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
#   )
#     puts 'Topic found.'
#   end

def topic_found?(topics, topic_arn)
  topics.each do |topic|
    return true if topic.topic_arn == topic_arn
  end
  return false
end
```

Verifica se o tópico especificado existe dentre aqueles disponíveis para o chamador no Amazon SNS.

```
# Checks whether the specified topic exists among those available to the
# caller in Amazon SNS.
#
# @param sns_client [Aws::SNS::Client] An initialized Amazon SNS client.
# @param topic_arn [String] The ARN of the topic to find.
# @return [Boolean] true if the topic ARN was found; otherwise, false.
# @example
#   exit 1 unless topic_exists?(
```

```
#     Aws::SNS::Client.new(region: 'us-east-1'),
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
#   )
def topic_exists?(sns_client, topic_arn)
  puts "Searching for topic with ARN '#{topic_arn}'..."
  response = sns_client.list_topics
  if response.topics.count.positive?
    if topic_found?(response.topics, topic_arn)
      puts "Topic found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.topics.count.positive?
        if topic_found?(response.topics, topic_arn)
          puts "Topic found."
          return true
        end
      end
    end
  end
  puts "Topic not found."
  return false
rescue StandardError => e
  puts "Topic not found: #{e.message}"
  return false
end
```

Crie um tópico no Amazon SNS e, em seguida, assine um endereço de e-mail para receber notificações sobre esse tópico.

```
# Creates a topic in Amazon SNS
# and then subscribes an email address to receive notifications to that topic.
#
# @param sns_client [Aws::SNS::Client] An initialized Amazon SNS client.
# @param topic_name [String] The name of the topic to create.
# @param email_address [String] The email address of the recipient to notify.
# @return [String] The ARN of the topic that was created.
# @example
#   puts create_topic(
#     Aws::SNS::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-topic',
```

```
#     'mary@example.com'
#   )
def create_topic(sns_client, topic_name, email_address)
  puts "Creating the topic named '#{topic_name}'..."
  topic_response = sns_client.create_topic(name: topic_name)
  puts "Topic created with ARN '#{topic_response.topic_arn}'."
  subscription_response = sns_client.subscribe(
    topic_arn: topic_response.topic_arn,
    protocol: "email",
    endpoint: email_address,
    return_subscription_arn: true
  )
  puts "Subscription created with ARN " \
    "'#{subscription_response.subscription_arn}'. Have the owner of the " \
    "email address '#{email_address}' check their inbox in a few minutes " \
    "and confirm the subscription to start receiving notification emails."
  return topic_response.topic_arn
rescue StandardError => e
  puts "Error creating or subscribing to topic: #{e.message}"
  return "Error"
end
```

Verifique se a função AWS Identity and Access Management (IAM) especificada existe dentre aquelas fornecidas para essa função.

```
# Checks whether the specified AWS Identity and Access Management (IAM)
# role exists among those provided to this function.
# This is a helper function that is called by the role_exists? function.
#
# @param roles [Array] An array of Aws::IAM::Role objects.
# @param role_arn [String] The ARN of the role to find.
# @return [Boolean] true if the role ARN was found; otherwise, false.
# @example
#   iam_client = Aws::IAM::Client.new(region: 'us-east-1')
#   response = iam_client.list_roles
#   if role_found?(
#     response.roles,
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change'
#   )
#     puts 'Role found.'
#   end
def role_found?(roles, role_arn)
```

```
  roles.each do |role|
    return true if role.arn == role_arn
  end
  return false
end
```

Verifique se a função especificada existe dentre aquelas disponíveis para o chamador no IAM.

```
# Checks whether the specified role exists among those available to the
# caller in AWS Identity and Access Management (IAM).
#
# @param iam_client [Aws::IAM::Client] An initialized IAM client.
# @param role_arn [String] The ARN of the role to find.
# @return [Boolean] true if the role ARN was found; otherwise, false.
# @example
#   exit 1 unless role_exists?(
#     Aws::IAM::Client.new(region: 'us-east-1'),
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change'
#   )
def role_exists?(iam_client, role_arn)
  puts "Searching for role with ARN '#{role_arn}'..."
  response = iam_client.list_roles
  if response.roles.count.positive?
    if role_found?(response.roles, role_arn)
      puts "Role found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.roles.count.positive?
        if role_found?(response.roles, role_arn)
          puts "Role found."
          return true
        end
      end
    end
  end
  puts "Role not found."
  return false
rescue StandardError => e
  puts "Role not found: #{e.message}"
  return false
```

```
end
```

Criar uma função no IAM.

```
# Creates a role in AWS Identity and Access Management (IAM).
# This role is used by a rule in Amazon EventBridge to allow
# that rule to operate within the caller's account.
# This role is designed to be used specifically by this code example.
#
# @param iam_client [Aws::IAM::Client] An initialized IAM client.
# @param role_name [String] The name of the role to create.
# @return [String] The ARN of the role that was created.
# @example
#   puts create_role(
#     Aws::IAM::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change'
#   )
def create_role(iam_client, role_name)
  puts "Creating the role named '#{role_name}'..."
  response = iam_client.create_role(
    assume_role_policy_document: {
      'Version': "2012-10-17",
      'Statement': [
        {
          'Sid': "",
          'Effect': "Allow",
          'Principal': {
            'Service': "events.amazonaws.com"
          },
          'Action': "sts:AssumeRole"
        }
      ]
    }.to_json,
    path: "/",
    role_name: role_name
  )
  puts "Role created with ARN '#{response.role.arn}'."
  puts "Adding access policy to role..."
  iam_client.put_role_policy(
    policy_document: {
      'Version': "2012-10-17",
      'Statement': [
```

```
        {
          'Sid': "CloudWatchEventsFullAccess",
          'Effect': "Allow",
          'Resource': "*",
          'Action': "events:*"
        },
        {
          'Sid': "IAMPassRoleForCloudWatchEvents",
          'Effect': "Allow",
          'Resource': "arn:aws:iam::*:role/AWS_Events_Invoke_Targets",
          'Action': "iam:PassRole"
        }
      ]
    }.to_json,
    policy_name: "CloudWatchEventsPolicy",
    role_name: role_name
  )
  puts "Access policy added to role."
  return response.role.arn
rescue StandardError => e
  puts "Error creating role or adding policy to it: #{e.message}"
  puts "If the role was created, you must add the access policy " \
    "to the role yourself, or delete the role yourself and try again."
  return "Error"
end
```

Verifica se a EventBridge regra especificada existe entre as fornecidas para essa função.

```
# Checks whether the specified Amazon EventBridge rule exists among
# those provided to this function.
# This is a helper function that is called by the rule_exists? function.
#
# @param rules [Array] An array of Aws::CloudWatchEvents::Types::Rule objects.
# @param rule_arn [String] The name of the rule to find.
# @return [Boolean] true if the name of the rule was found; otherwise, false.
# @example
#   cloudwatchevents_client = Aws::CloudWatch::Client.new(region: 'us-east-1')
#   response = cloudwatchevents_client.list_rules
#   if rule_found?(response.rules, 'aws-doc-sdk-examples-ec2-state-change')
#     puts 'Rule found.'
#   end
def rule_found?(rules, rule_name)
```

```
  rules.each do |rule|
    return true if rule.name == rule_name
  end
  return false
end
```

Verifica se a regra especificada existe entre as disponíveis para o chamador. EventBridge

```
# Checks whether the specified rule exists among those available to the
# caller in Amazon EventBridge.
#
# @param cloudwatchevents_client [Aws::CloudWatchEvents::Client]
#   An initialized Amazon EventBridge client.
# @param rule_name [String] The name of the rule to find.
# @return [Boolean] true if the rule name was found; otherwise, false.
# @example
#   exit 1 unless rule_exists?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1')
#     'aws-doc-sdk-examples-ec2-state-change'
#   )
def rule_exists?(cloudwatchevents_client, rule_name)
  puts "Searching for rule with name '#{rule_name}'..."
  response = cloudwatchevents_client.list_rules
  if response.rules.count.positive?
    if rule_found?(response.rules, rule_name)
      puts "Rule found."
      return true
    end
    while response.next_page? do
      response = response.next_page
      if response.rules.count.positive?
        if rule_found?(response.rules, rule_name)
          puts "Rule found."
          return true
        end
      end
    end
  end
  puts "Rule not found."
  return false
rescue StandardError => e
  puts "Rule not found: #{e.message}"
```

```
  return false
end
```

Crie uma regra em EventBridge.

```
# Creates a rule in Amazon EventBridge.
# This rule is triggered whenever an available instance in
# Amazon EC2 changes to the specified state.
# This rule is designed to be used specifically by this code example.
#
# Prerequisites:
#
# - A role in AWS Identity and Access Management (IAM) that is designed
#   to be used specifically by this code example.
# - A topic in Amazon SNS.
#
# @param cloudwatchevents_client [Aws::CloudWatchEvents::Client]
#   An initialized Amazon EventBridge client.
# @param rule_name [String] The name of the rule to create.
# @param rule_description [String] Some description for this rule.
# @param instance_state [String] The state that available instances in
#   Amazon EC2 must change to, to
#   trigger this rule.
# @param role_arn [String] The Amazon Resource Name (ARN) of the IAM role.
# @param target_id [String] Some identifying string for the rule's target.
# @param topic_arn [String] The ARN of the Amazon SNS topic.
# @return [Boolean] true if the rule was created; otherwise, false.
# @example
#   exit 1 unless rule_created?(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change',
#     'Triggers when any available EC2 instance starts.',
#     'running',
#     'arn:aws:iam::111111111111:role/aws-doc-sdk-examples-ec2-state-change',
#     'sns-topic',
#     'arn:aws:sns:us-east-1:111111111111:aws-doc-sdk-examples-topic'
#   )
def rule_created?(
  cloudwatchevents_client,
  rule_name,
  rule_description,
  instance_state,
```

```
  role_arn,
  target_id,
  topic_arn
)
  puts "Creating rule with name '#{rule_name}'..."
  put_rule_response = cloudwatchevents_client.put_rule(
    name: rule_name,
    description: rule_description,
    event_pattern: {
      'source': [
        "aws.ec2"
      ],
      'detail-type': [
        "EC2 Instance State-change Notification"
      ],
      'detail': {
        'state': [
          instance_state
        ]
      }
    }.to_json,
    state: "ENABLED",
    role_arn: role_arn
  )
  puts "Rule created with ARN '#{put_rule_response.rule_arn}'."

  put_targets_response = cloudwatchevents_client.put_targets(
    rule: rule_name,
    targets: [
      {
        id: target_id,
        arn: topic_arn
      }
    ]
  )
  if put_targets_response.key?(:failed_entry_count) &&
      put_targets_response.failed_entry_count > 0
    puts "Error(s) adding target to rule:"
    put_targets_response.failed_entries.each do |failure|
      puts failure.error_message
    end
    return false
  else
    return true
```

```
  end
rescue StandardError => e
  puts "Error creating rule or adding target to rule: #{e.message}"
  puts "If the rule was created, you must add the target " \
    "to the rule yourself, or delete the rule yourself and try again."
  return false
end
```

Verifique se o grupo de registros especificado existe entre aqueles disponíveis para o chamador no Amazon CloudWatch Logs.

```
# Checks to see whether the specified log group exists among those available
# to the caller in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group to find.
# @return [Boolean] true if the log group name was found; otherwise, false.
# @example
#   exit 1 unless log_group_exists?(
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def log_group_exists?(cloudwatchlogs_client, log_group_name)
  puts "Searching for log group with name '#{log_group_name}'..."
  response = cloudwatchlogs_client.describe_log_groups(
    log_group_name_prefix: log_group_name
  )
  if response.log_groups.count.positive?
    response.log_groups.each do |log_group|
      if log_group.log_group_name == log_group_name
        puts "Log group found."
        return true
      end
    end
  end
  puts "Log group not found."
  return false
rescue StandardError => e
  puts "Log group not found: #{e.message}"
  return false
end
```

Crie um grupo de CloudWatch registros em Registros.

```
# Creates a log group in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group to create.
# @return [Boolean] true if the log group name was created; otherwise, false.
# @example
#   exit 1 unless log_group_created?(
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def log_group_created?(cloudwatchlogs_client, log_group_name)
  puts "Attempting to create log group with the name '#{log_group_name}'..."
  cloudwatchlogs_client.create_log_group(log_group_name: log_group_name)
  puts "Log group created."
  return true
rescue StandardError => e
  puts "Error creating log group: #{e.message}"
  return false
end
```

Grave um evento em um stream de CloudWatch registros em Logs.

```
# Writes an event to a log stream in Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - A log group in Amazon CloudWatch Logs.
# - A log stream within the log group.
#
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group.
# @param log_stream_name [String] The name of the log stream within
#   the log group.
# @param message [String] The message to write to the log stream.
# @param sequence_token [String] If available, the sequence token from the
#   message that was written immediately before this message. This sequence
```

```
#   token is returned by Amazon CloudWatch Logs whenever you programmatically
#   write a message to the log stream.
# @return [String] The sequence token that is returned by
#   Amazon CloudWatch Logs after successfully writing the message to the
#   log stream.
# @example
#   puts log_event(
#     Aws::EC2::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#     '2020/11/19/53f985be-199f-408e-9a45-fc242df41fEX',
#     "Instance 'i-033c48ef067af3dEX' restarted.",
#     '49542672486831074009579604567656788214806863282469607 3EX'
#   )
def log_event(
  cloudwatchlogs_client,
  log_group_name,
  log_stream_name,
  message,
  sequence_token
)
  puts "Attempting to log '#{message}' to log stream '#{log_stream_name}'..."
  event = {
    log_group_name: log_group_name,
    log_stream_name: log_stream_name,
    log_events: [
      {
        timestamp: (Time.now.utc.to_f.round(3) * 1_000).to_i,
        message: message
      }
    ]
  }
  unless sequence_token.empty?
    event[:sequence_token] = sequence_token
  end

  response = cloudwatchlogs_client.put_log_events(event)
  puts "Message logged."
  return response.next_sequence_token
rescue StandardError => e
  puts "Message not logged: #{e.message}"
end
```

Reinicie uma instância do Amazon Elastic Compute Cloud (Amazon EC2) e adicione informações sobre a atividade relacionada a um stream de log no Logs. CloudWatch

```
# Restarts an Amazon EC2 instance
# and adds information about the related activity to a log stream
# in Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - The Amazon EC2 instance to restart.
# - The log group in Amazon CloudWatch Logs to add related activity
#   information to.
#
# @param ec2_client [Aws::EC2::Client] An initialized Amazon EC2 client.
# @param cloudwatchlogs_client [Aws::CloudWatchLogs::Client]
#   An initialized Amazon CloudWatch Logs client.
# @param instance_id [String] The ID of the instance.
# @param log_group_name [String] The name of the log group.
# @return [Boolean] true if the instance was restarted and the information
#   was written to the log stream; otherwise, false.
# @example
#   exit 1 unless instance_restarted?(
#     Aws::EC2::Client.new(region: 'us-east-1'),
#     Aws::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'i-033c48ef067af3dEX',
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def instance_restarted?(
  ec2_client,
  cloudwatchlogs_client,
  instance_id,
  log_group_name
)
  log_stream_name = "#{Time.now.year}/#{Time.now.month}/#{Time.now.day}/" \
    "#{SecureRandom.uuid}"
  cloudwatchlogs_client.create_log_stream(
    log_group_name: log_group_name,
    log_stream_name: log_stream_name
  )
  sequence_token = ""

  puts "Attempting to stop the instance with the ID '#{instance_id}'. " \
```

```
    "This might take a few minutes..."
  ec2_client.stop_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_stopped, instance_ids: [instance_id])
  puts "Instance stopped."
  sequence_token = log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Instance '#{instance_id}' stopped.",
    sequence_token
  )

  puts "Attempting to restart the instance. This might take a few minutes..."
  ec2_client.start_instances(instance_ids: [instance_id])
  ec2_client.wait_until(:instance_running, instance_ids: [instance_id])
  puts "Instance restarted."
  sequence_token = log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Instance '#{instance_id}' restarted.",
    sequence_token
  )

  return true
rescue StandardError => e
  puts "Error creating log stream or stopping or restarting the instance: " \
    "#{e.message}"
  log_event(
    cloudwatchlogs_client,
    log_group_name,
    log_stream_name,
    "Error stopping or starting instance '#{instance_id}': #{e.message}",
    sequence_token
  )
  return false
end
```

Exibir informações sobre a atividade de uma regra em EventBridge.

```
# Displays information about activity for a rule in Amazon EventBridge.
#
```

```
# Prerequisites:
#
# - A rule in Amazon EventBridge.
#
# @param cloudwatch_client [Amazon::CloudWatch::Client] An initialized
#   Amazon CloudWatch client.
# @param rule_name [String] The name of the rule.
# @param start_time [Time] The timestamp that determines the first datapoint
#   to return. Can also be expressed as DateTime, Date, Integer, or String.
# @param end_time [Time] The timestamp that determines the last datapoint
#   to return. Can also be expressed as DateTime, Date, Integer, or String.
# @param period [Integer] The interval, in seconds, to check for activity.
# @example
#   display_rule_activity(
#     Aws::CloudWatch::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-ec2-state-change',
#     Time.now - 600, # Start checking from 10 minutes ago.
#     Time.now, # Check up until now.
#     60 # Check every minute during those 10 minutes.
#   )
def display_rule_activity(
  cloudwatch_client,
  rule_name,
  start_time,
  end_time,
  period
)
  puts "Attempting to display rule activity..."
  response = cloudwatch_client.get_metric_statistics(
    namespace: "AWS/Events",
    metric_name: "Invocations",
    dimensions: [
      {
        name: "RuleName",
        value: rule_name
      }
    ],
    start_time: start_time,
    end_time: end_time,
    period: period,
    statistics: ["Sum"],
    unit: "Count"
  )
```

```
  if response.key?(:datapoints) && response.datapoints.count.positive?
    puts "The event rule '#{rule_name}' was triggered:"
    response.datapoints.each do |datapoint|
      puts "  #{datapoint.sum} time(s) at #{datapoint.timestamp}"
    end
  else
    puts "The event rule '#{rule_name}' was not triggered during the " \
      "specified time period."
  end
rescue StandardError => e
  puts "Error getting information about event rule activity: #{e.message}"
end
```

Exibir informações de registro de todos os fluxos de registros em um grupo de CloudWatch registros de registros.

```
# Displays log information for all of the log streams in a log group in
# Amazon CloudWatch Logs.
#
# Prerequisites:
#
# - A log group in Amazon CloudWatch Logs.
#
# @param cloudwatchlogs_client [Amazon::CloudWatchLogs::Client] An initialized
#   Amazon CloudWatch Logs client.
# @param log_group_name [String] The name of the log group.
# @example
#   display_log_data(
#     Amazon::CloudWatchLogs::Client.new(region: 'us-east-1'),
#     'aws-doc-sdk-examples-cloudwatch-log'
#   )
def display_log_data(cloudwatchlogs_client, log_group_name)
  puts "Attempting to display log stream data for the log group " \
    "named '#{log_group_name}'..."
  describe_log_streams_response = cloudwatchlogs_client.describe_log_streams(
    log_group_name: log_group_name,
    order_by: "LastEventTime",
    descending: true
  )
  if describe_log_streams_response.key?(:log_streams) &&
      describe_log_streams_response.log_streams.count.positive?
    describe_log_streams_response.log_streams.each do |log_stream|
```

```
      get_log_events_response = cloudwatchlogs_client.get_log_events(
        log_group_name: log_group_name,
        log_stream_name: log_stream.log_stream_name
      )
      puts "\nLog messages for '#{log_stream.log_stream_name}':"
      puts "-" * (log_stream.log_stream_name.length + 20)
      if get_log_events_response.key?(:events) &&
          get_log_events_response.events.count.positive?
        get_log_events_response.events.each do |event|
          puts event.message
        end
      else
        puts "No log messages for this log stream."
      end
    end
  end
rescue StandardError => e
  puts "Error getting information about the log streams or their messages: " \
    "#{e.message}"
end
```

Exibir um lembrete para o chamador limpar manualmente todos os recursos AWS associados dos quais ele não precisa mais.

```
# Displays a reminder to the caller to manually clean up any associated
# AWS resources that they no longer need.
#
# @param topic_name [String] The name of the Amazon SNS topic.
# @param role_name [String] The name of the IAM role.
# @param rule_name [String] The name of the Amazon EventBridge rule.
# @param log_group_name [String] The name of the Amazon CloudWatch Logs log group.
# @param instance_id [String] The ID of the Amazon EC2 instance.
# @example
#   manual_cleanup_notice(
#     'aws-doc-sdk-examples-topic',
#     'aws-doc-sdk-examples-cloudwatch-events-rule-role',
#     'aws-doc-sdk-examples-ec2-state-change',
#     'aws-doc-sdk-examples-cloudwatch-log',
#     'i-033c48ef067af3dEX'
#   )
def manual_cleanup_notice(
```

```
  topic_name, role_name, rule_name, log_group_name, instance_id
)
  puts "-" * 10
  puts "Some of the following AWS resources might still exist in your account."
  puts "If you no longer want to use this code example, then to clean up"
  puts "your AWS account and avoid unexpected costs, you might want to"
  puts "manually delete any of the following resources if they exist:"
  puts "- The Amazon SNS topic named '#{topic_name}'."
  puts "- The IAM role named '#{role_name}'."
  puts "- The Amazon EventBridge rule named '#{rule_name}'."
  puts "- The Amazon CloudWatch Logs log group named '#{log_group_name}'."
  puts "- The Amazon EC2 instance with the ID '#{instance_id}'."
end

# Example usage:
def run_me
  # Properties for the Amazon SNS topic.
  topic_name = "aws-doc-sdk-examples-topic"
  email_address = "mary@example.com"
  # Properties for the IAM role.
  role_name = "aws-doc-sdk-examples-cloudwatch-events-rule-role"
  # Properties for the Amazon EventBridge rule.
  rule_name = "aws-doc-sdk-examples-ec2-state-change"
  rule_description = "Triggers when any available EC2 instance starts."
  instance_state = "running"
  target_id = "sns-topic"
  # Properties for the Amazon EC2 instance.
  instance_id = "i-033c48ef067af3dEX"
  # Properties for displaying the event rule's activity.
  start_time = Time.now - 600 # Go back over the past 10 minutes
                              # (10 minutes * 60 seconds = 600 seconds).
  end_time = Time.now
  period = 60 # Look back every 60 seconds over the past 10 minutes.
  # Properties for the Amazon CloudWatch Logs log group.
  log_group_name = "aws-doc-sdk-examples-cloudwatch-log"
  # AWS service clients for this code example.
  region = "us-east-1"
  sts_client = Aws::STS::Client.new(region: region)
  sns_client = Aws::SNS::Client.new(region: region)
  iam_client = Aws::IAM::Client.new(region: region)
  cloudwatchevents_client = Aws::CloudWatchEvents::Client.new(region: region)
  ec2_client = Aws::EC2::Client.new(region: region)
  cloudwatch_client = Aws::CloudWatch::Client.new(region: region)
  cloudwatchlogs_client = Aws::CloudWatchLogs::Client.new(region: region)
```

```
# Get the caller's account ID for use in forming
# Amazon Resource Names (ARNs) that this code relies on later.
account_id = sts_client.get_caller_identity.account

# If the Amazon SNS topic doesn't exist, create it.
topic_arn = "arn:aws:sns:#{region}:#{account_id}:#{topic_name}"
unless topic_exists?(sns_client, topic_arn)
  topic_arn = create_topic(sns_client, topic_name, email_address)
  if topic_arn == "Error"
    puts "Could not create the Amazon SNS topic correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
    exit 1
  end
end

# If the IAM role doesn't exist, create it.
role_arn = "arn:aws:iam::#{account_id}:role/#{role_name}"
unless role_exists?(iam_client, role_arn)
  role_arn = create_role(iam_client, role_name)
  if role_arn == "Error"
    puts "Could not create the IAM role correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# If the Amazon EventBridge rule doesn't exist, create it.
unless rule_exists?(cloudwatchevents_client, rule_name)
  unless rule_created?(
    cloudwatchevents_client,
    rule_name,
    rule_description,
    instance_state,
    role_arn,
    target_id,
    topic_arn
  )
    puts "Could not create the Amazon EventBridge rule correctly. " \
      "Program stopped."
    manual_cleanup_notice(
```

```
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# If the Amazon CloudWatch Logs log group doesn't exist, create it.
unless log_group_exists?(cloudwatchlogs_client, log_group_name)
  unless log_group_created?(cloudwatchlogs_client, log_group_name)
    puts "Could not create the Amazon CloudWatch Logs log group " \
    "correctly. Program stopped."
    manual_cleanup_notice(
      topic_name, role_name, rule_name, log_group_name, instance_id
    )
  end
end

# Restart the Amazon EC2 instance, which triggers the rule.
unless instance_restarted?(
  ec2_client,
  cloudwatchlogs_client,
  instance_id,
  log_group_name
)
  puts "Could not restart the instance to trigger the rule. " \
    "Continuing anyway to show information about the rule and logs..."
end

# Display how many times the rule was triggered over the past 10 minutes.
display_rule_activity(
  cloudwatch_client,
  rule_name,
  start_time,
  end_time,
  period
)

# Display related log data in Amazon CloudWatch Logs.
display_log_data(cloudwatchlogs_client, log_group_name)

# Reminder the caller to clean up any AWS resources that are used
# by this code example and are no longer needed.
manual_cleanup_notice(
  topic_name, role_name, rule_name, log_group_name, instance_id
)
```

```
end

run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - PutEvents
  - PutRule

Exemplos de AWS Glue usando o SDK para Ruby

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

O exemplo de código a seguir mostra como criar um crawler do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Creates a new crawler with the specified configuration.
  #
  # @param name [String] The name of the crawler.
  # @param role_arn [String] The ARN of the IAM role to be used by the crawler.
  # @param db_name [String] The name of the database where the crawler stores its
 metadata.
  # @param db_prefix [String] The prefix to be added to the names of tables that the
 crawler creates.
  # @param s3_target [String] The S3 path that the crawler will crawl.
  # @return [void]
  def create_crawler(name, role_arn, db_name, db_prefix, s3_target)
    @glue_client.create_crawler(
      name: name,
      role: role_arn,
      database_name: db_name,
      targets: {
        s3_targets: [
          {
            path: s3_target
          }
        ]
```

```
      }
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create crawler: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateCrawlera Referência AWS SDK for Ruby da API.

Crie uma definição de trabalho

O exemplo de código a seguir mostra como criar uma definição de trabalho do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Creates a new job with the specified configuration.
  #
  # @param name [String] The name of the job.
  # @param description [String] The description of the job.
  # @param role_arn [String] The ARN of the IAM role to be used by the job.
  # @param script_location [String] The location of the ETL script for the job.
```

```
  # @return [void]
  def create_job(name, description, role_arn, script_location)
    @glue_client.create_job(
      name: name,
      description: description,
      role: role_arn,
      command: {
        name: "glueetl",
        script_location: script_location,
        python_version: "3"
      },
      glue_version: "3.0"
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create job #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateJoba Referência AWS SDK for Ruby da API.

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
```

```
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Deletes a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to delete.
  # @return [void]
  def delete_crawler(name)
    @glue_client.delete_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteCrawlera Referência AWS SDK for Ruby da API.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
```

```
    @logger = logger
  end

  # Removes a specified database from a Data Catalog.
  #
  # @param database_name [String] The name of the database to delete.
  # @return [void]
  def delete_database(database_name)
    @glue_client.delete_database(name: database_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete database: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteDatabasea Referência AWS SDK for Ruby da API.

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end
```

```
  # Deletes a job with the specified name.
  #
  # @param job_name [String] The name of the job to delete.
  # @return [void]
  def delete_job(job_name)
    @glue_client.delete_job(job_name: job_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteJoba Referência AWS SDK for Ruby da API.

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela de um banco de dados do AWS Glue Data Catalog.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Deletes a table with the specified name.
```

```
  #
  # @param database_name [String] The name of the catalog database in which the
 table resides.
  # @param table_name [String] The name of the table to be deleted.
  # @return [void]
  def delete_table(database_name, table_name)
    @glue_client.delete_table(database_name: database_name, name: table_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteTablea Referência AWS SDK for Ruby da API.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific crawler.
  #
```

```
  # @param name [String] The name of the crawler to retrieve information about.
  # @return [Aws::Glue::Types::Crawler, nil] The crawler object if found, or nil if
 not found.
  def get_crawler(name)
    @glue_client.get_crawler(name: name)
  rescue Aws::Glue::Errors::EntityNotFoundException
    @logger.info("Crawler #{name} doesn't exist.")
    false
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetCrawlera Referência AWS SDK for Ruby da API.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific database.
```

```
  #
  # @param name [String] The name of the database to retrieve information about.
  # @return [Aws::Glue::Types::Database, nil] The database object if found, or nil
 if not found.
  def get_database(name)
    response = @glue_client.get_database(name: name)
    response.database
rescue Aws::Glue::Errors::GlueException => e
  @logger.error("Glue could not get database #{name}: \n#{e.message}")
  raise
  end
```

- Para obter detalhes da API, consulte GetDatabasea Referência AWS SDK for Ruby da API.

Obter uma execução de trabalho

O exemplo de código a seguir mostra como obter uma execução de trabalho do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves data for a specific job run.
  #
```

```
  # @param job_name [String] The name of the job run to retrieve data for.
  # @return [Glue::Types::GetJobRunResponse]
  def get_job_run(job_name, run_id)
    @glue_client.get_job_run(job_name: job_name, run_id: run_id)
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte GetJobRuna Referência AWS SDK for Ruby da API.

Obter execuções de um trabalho

O exemplo de código a seguir mostra como obter execuções de um trabalho do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of job runs for the specified job.
  #
  # @param job_name [String] The name of the job to retrieve job runs for.
  # @return [Array<Aws::Glue::Types::JobRun>]
  def get_job_runs(job_name)
    response = @glue_client.get_job_runs(job_name: job_name)
```

```
    response.job_runs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end
```

- Para obter detalhes da API, consulte GetJobRunsa Referência AWS SDK for Ruby da API.

Obter tabelas de um banco de dados

O exemplo de código a seguir mostra como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of tables in the specified database.
  #
  # @param db_name [String] The name of the database to retrieve tables from.
  # @return [Array<Aws::Glue::Types::Table>]
  def get_tables(db_name)
    response = @glue_client.get_tables(database_name: db_name)
    response.table_list
```

```
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get tables #{db_name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetTablesa Referência AWS SDK for Ruby da API.

Listar definições de trabalho

O exemplo de código a seguir mostra como listas definições de trabalho do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves a list of jobs in AWS Glue.
  #
  # @return [Aws::Glue::Types::ListJobsResponse]
  def list_jobs
    @glue_client.list_jobs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not list jobs: \n#{e.message}")
    raise
```

```
  end
```

- Para obter detalhes da API, consulte ListJobsa Referência AWS SDK for Ruby da API.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Starts a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to start.
  # @return [void]
  def start_crawler(name)
    @glue_client.start_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not start crawler #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte StartCrawlera Referência AWS SDK for Ruby da API.

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Starts a job run for the specified job.
  #
  # @param name [String] The name of the job to start the run for.
  # @param input_database [String] The name of the input database for the job.
  # @param input_table [String] The name of the input table for the job.
  # @param output_bucket_name [String] The name of the output S3 bucket for the job.
  # @return [String] The ID of the started job run.
  def start_job_run(name, input_database, input_table, output_bucket_name)
    response = @glue_client.start_job_run(
      job_name: name,
      arguments: {
        '--input_database': input_database,
        '--input_table': input_table,
        '--output_bucket_url': "s3://#{output_bucket_name}/"
      }
```

```
    )
    response.job_run_id
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not start job run #{name}: \n#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte StartJobRuna Referência AWS SDK for Ruby da API.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma classe que englobe as funções do AWS Glue usadas no cenário.

```
# The `GlueWrapper` class serves as a wrapper around the AWS Glue API, providing a
 simplified interface for common operations.
# It encapsulates the functionality of the AWS SDK for Glue and provides methods for
 interacting with Glue crawlers, databases, tables, jobs, and S3 resources.
```

```
# The class initializes with a Glue client and a logger, allowing it to make API
 calls and log any errors or informational messages.
class GlueWrapper
  def initialize(glue_client, logger)
    @glue_client = glue_client
    @logger = logger
  end

  # Retrieves information about a specific crawler.
  #
  # @param name [String] The name of the crawler to retrieve information about.
  # @return [Aws::Glue::Types::Crawler, nil] The crawler object if found, or nil if
 not found.
  def get_crawler(name)
    @glue_client.get_crawler(name: name)
  rescue Aws::Glue::Errors::EntityNotFoundException
    @logger.info("Crawler #{name} doesn't exist.")
    false
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get crawler #{name}: \n#{e.message}")
    raise
  end

  # Creates a new crawler with the specified configuration.
  #
  # @param name [String] The name of the crawler.
  # @param role_arn [String] The ARN of the IAM role to be used by the crawler.
  # @param db_name [String] The name of the database where the crawler stores its
 metadata.
  # @param db_prefix [String] The prefix to be added to the names of tables that the
 crawler creates.
  # @param s3_target [String] The S3 path that the crawler will crawl.
  # @return [void]
  def create_crawler(name, role_arn, db_name, db_prefix, s3_target)
    @glue_client.create_crawler(
      name: name,
      role: role_arn,
      database_name: db_name,
      targets: {
        s3_targets: [
          {
            path: s3_target
          }
        ]
```

```
      }
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create crawler: \n#{e.message}")
    raise
  end

  # Starts a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to start.
  # @return [void]
  def start_crawler(name)
    @glue_client.start_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not start crawler #{name}: \n#{e.message}")
    raise
  end

  # Deletes a crawler with the specified name.
  #
  # @param name [String] The name of the crawler to delete.
  # @return [void]
  def delete_crawler(name)
    @glue_client.delete_crawler(name: name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete crawler #{name}: \n#{e.message}")
    raise
  end

  # Retrieves information about a specific database.
  #
  # @param name [String] The name of the database to retrieve information about.
  # @return [Aws::Glue::Types::Database, nil] The database object if found, or nil
 if not found.
  def get_database(name)
    response = @glue_client.get_database(name: name)
    response.database
rescue Aws::Glue::Errors::GlueException => e
  @logger.error("Glue could not get database #{name}: \n#{e.message}")
  raise
  end

  # Retrieves a list of tables in the specified database.
  #
```

```
  # @param db_name [String] The name of the database to retrieve tables from.
  # @return [Array<Aws::Glue::Types::Table>]
  def get_tables(db_name)
    response = @glue_client.get_tables(database_name: db_name)
    response.table_list
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get tables #{db_name}: \n#{e.message}")
    raise
  end

  # Creates a new job with the specified configuration.
  #
  # @param name [String] The name of the job.
  # @param description [String] The description of the job.
  # @param role_arn [String] The ARN of the IAM role to be used by the job.
  # @param script_location [String] The location of the ETL script for the job.
  # @return [void]
  def create_job(name, description, role_arn, script_location)
    @glue_client.create_job(
      name: name,
      description: description,
      role: role_arn,
      command: {
        name: "glueetl",
        script_location: script_location,
        python_version: "3"
      },
      glue_version: "3.0"
    )
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not create job #{name}: \n#{e.message}")
    raise
  end

  # Starts a job run for the specified job.
  #
  # @param name [String] The name of the job to start the run for.
  # @param input_database [String] The name of the input database for the job.
  # @param input_table [String] The name of the input table for the job.
  # @param output_bucket_name [String] The name of the output S3 bucket for the job.
  # @return [String] The ID of the started job run.
  def start_job_run(name, input_database, input_table, output_bucket_name)
    response = @glue_client.start_job_run(
      job_name: name,
```

```
      arguments: {
        '--input_database': input_database,
        '--input_table': input_table,
        '--output_bucket_url': "s3://#{output_bucket_name}/"
      }
    )
    response.job_run_id
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not start job run #{name}: \n#{e.message}")
    raise
  end

  # Retrieves a list of jobs in AWS Glue.
  #
  # @return [Aws::Glue::Types::ListJobsResponse]
  def list_jobs
    @glue_client.list_jobs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not list jobs: \n#{e.message}")
    raise
  end

  # Retrieves a list of job runs for the specified job.
  #
  # @param job_name [String] The name of the job to retrieve job runs for.
  # @return [Array<Aws::Glue::Types::JobRun>]
  def get_job_runs(job_name)
    response = @glue_client.get_job_runs(job_name: job_name)
    response.job_runs
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end

  # Retrieves data for a specific job run.
  #
  # @param job_name [String] The name of the job run to retrieve data for.
  # @return [Glue::Types::GetJobRunResponse]
  def get_job_run(job_name, run_id)
    @glue_client.get_job_run(job_name: job_name, run_id: run_id)
  rescue Aws::Glue::Errors::GlueException => e
    @logger.error("Glue could not get job runs: \n#{e.message}")
  end

  # Deletes a job with the specified name.
```

```
  #
  # @param job_name [String] The name of the job to delete.
  # @return [void]
  def delete_job(job_name)
    @glue_client.delete_job(job_name: job_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end

  # Deletes a table with the specified name.
  #
  # @param database_name [String] The name of the catalog database in which the
table resides.
  # @param table_name [String] The name of the table to be deleted.
  # @return [void]
  def delete_table(database_name, table_name)
    @glue_client.delete_table(database_name: database_name, name: table_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete job: \n#{e.message}")
  end

  # Removes a specified database from a Data Catalog.
  #
  # @param database_name [String] The name of the database to delete.
  # @return [void]
  def delete_database(database_name)
    @glue_client.delete_database(name: database_name)
  rescue Aws::Glue::Errors::ServiceError => e
    @logger.error("Glue could not delete database: \n#{e.message}")
  end

  # Uploads a job script file to an S3 bucket.
  #
  # @param file_path [String] The local path of the job script file.
  # @param bucket_resource [Aws::S3::Bucket] The S3 bucket resource to upload the
file to.
  # @return [void]
  def upload_job_script(file_path, bucket_resource)
    File.open(file_path) do |file|
      bucket_resource.client.put_object({
       body: file,
       bucket: bucket_resource.name,
       key: file_path
     })
```

```
    end
  rescue Aws::S3::Errors::S3UploadFailedError => e
    @logger.error("S3 could not upload job script: \n#{e.message}")
    raise
  end

end
```

Crie uma classe que execute o cenário.

```
class GlueCrawlerJobScenario
  def initialize(glue_client, glue_service_role, glue_bucket, logger)
    @glue_client = glue_client
    @glue_service_role = glue_service_role
    @glue_bucket = glue_bucket
    @logger = logger
  end

  def run(crawler_name, db_name, db_prefix, data_source, job_script, job_name)
    wrapper = GlueWrapper.new(@glue_client, @logger)

    new_step(1, "Create a crawler")
    puts "Checking for crawler #{crawler_name}."
    crawler = wrapper.get_crawler(crawler_name)
    if crawler == false
      puts "Creating crawler #{crawler_name}."
      wrapper.create_crawler(crawler_name, @glue_service_role.arn, db_name,
 db_prefix, data_source)
      puts "Successfully created #{crawler_name}:"
      crawler = wrapper.get_crawler(crawler_name)
      puts JSON.pretty_generate(crawler).yellow
    end
    print "\nDone!\n".green

    new_step(2, "Run a crawler to output a database.")
    puts "Location of input data analyzed by crawler: #{data_source}"
    puts "Outputs: a Data Catalog database in CSV format containing metadata on
 input."
    wrapper.start_crawler(crawler_name)
    puts "Starting crawler... (this typically takes a few minutes)"
    crawler_state = nil
    while crawler_state != "READY"
```

```
      custom_wait(15)
      crawler = wrapper.get_crawler(crawler_name)
      crawler_state = crawler[0]["state"]
      print "Status check: #{crawler_state}.".yellow
    end
    print "\nDone!\n".green

    new_step(3, "Query the database.")
    database = wrapper.get_database(db_name)
    puts "The crawler created database #{db_name}:"
    print "#{database}".yellow
    puts "\nThe database contains these tables:"
    tables = wrapper.get_tables(db_name)
    tables.each_with_index do |table, index|
      print "\t#{index + 1}. #{table['name']}".yellow
    end
    print "\nDone!\n".green

    new_step(4, "Create a job definition that runs an ETL script.")
    puts "Uploading Python ETL script to S3..."
    wrapper.upload_job_script(job_script, @glue_bucket)
    puts "Creating job definition #{job_name}:\n"
    response = wrapper.create_job(job_name, "Getting started example job.",
@glue_service_role.arn, "s3://#{@glue_bucket.name}/#{job_script}")
    puts JSON.pretty_generate(response).yellow
    print "\nDone!\n".green

    new_step(5, "Start a new job")
    job_run_status = nil
    job_run_id = wrapper.start_job_run(
      job_name,
      db_name,
      tables[0]["name"],
      @glue_bucket.name
    )
    puts "Job #{job_name} started. Let's wait for it to run."
    until ["SUCCEEDED", "STOPPED", "FAILED", "TIMEOUT"].include?(job_run_status)
      custom_wait(10)
      job_run = wrapper.get_job_runs(job_name)
      job_run_status = job_run[0]["job_run_state"]
      print "Status check: #{job_name}/#{job_run_id} - #{job_run_status}.".yellow
    end
    print "\nDone!\n".green
```

```
    new_step(6, "View results from a successful job run.")
    if job_run_status == "SUCCEEDED"
      puts "Data from your job run is stored in your S3 bucket
'#{@glue_bucket.name}'. Files include:"
      begin

        # Print the key name of each object in the bucket.
        @glue_bucket.objects.each do |object_summary|
          if object_summary.key.include?("run-")
            print "#{object_summary.key}".yellow
          end
        end

        # Print the first 256 bytes of a run file
        desired_sample_objects = 1
        @glue_bucket.objects.each do |object_summary|
          if object_summary.key.include?("run-")
            if desired_sample_objects > 0
              sample_object = @glue_bucket.object(object_summary.key)
              sample = sample_object.get(range: "bytes=0-255").body.read
              puts "\nSample run file contents:"
              print "#{sample}".yellow
              desired_sample_objects -= 1
            end
          end
        end
      rescue Aws::S3::Errors::ServiceError => e
        logger.error(
          "Couldn't get job run data. Here's why: %s: %s",
          e.response.error.code, e.response.error.message
        )
        raise
      end
    end
    print "\nDone!\n".green

    new_step(7, "Delete job definition and crawler.")
    wrapper.delete_job(job_name)
    puts "Job deleted: #{job_name}."
    wrapper.delete_crawler(crawler_name)
    puts "Crawler deleted: #{crawler_name}."
    wrapper.delete_table(db_name, tables[0]["name"])
    puts "Table deleted: #{tables[0]["name"]} in #{db_name}."
    wrapper.delete_database(db_name)
```

```
    puts "Database deleted: #{db_name}."
    print "\nDone!\n".green
  end
end

def main

  banner("../../helpers/banner.txt")
  puts
 "#################################################################################
  puts "#
                         #".yellow
  puts "#                                          EXAMPLE CODE DEMO:
                         #".yellow
  puts "#                                              AWS Glue
                         #".yellow
  puts "#
                         #".yellow
  puts
 "#################################################################################
  puts ""
  puts "You have launched a demo of AWS Glue using the AWS for Ruby v3 SDK. Over the
 next 60 seconds, it will"
  puts "do the following:"
  puts "    1. Create a crawler."
  puts "    2. Run a crawler to output a database."
  puts "    3. Query the database."
  puts "    4. Create a job definition that runs an ETL script."
  puts "    5. Start a new job."
  puts "    6. View results from a successful job run."
  puts "    7. Delete job definition and crawler."
  puts ""

  confirm_begin
  billing
  security
  puts "\e[H\e[2J"

  # Set input file names
  job_script_filepath = "job_script.py"
  resource_names = YAML.load_file("resource_names.yaml")

  # Instantiate existing IAM role.
  iam = Aws::IAM::Resource.new(region: "us-east-1")
```

```
  iam_role_name = resource_names["glue_service_role"]
  iam_role = iam.role(iam_role_name)

  # Instantiate existing S3 bucket.
  s3 = Aws::S3::Resource.new(region: "us-east-1")
  s3_bucket_name = resource_names["glue_bucket"]
  s3_bucket = s3.bucket(s3_bucket_name)

  scenario = GlueCrawlerJobScenario.new(
    Aws::Glue::Client.new(region: "us-east-1"),
    iam_role,
    s3_bucket,
    @logger
  )

  random_int = rand(10 ** 4)
  scenario.run(
    "doc-example-crawler-#{random_int}",
    "doc-example-database-#{random_int}",
    "doc-example-#{random_int}-",
    "s3://crawler-public-us-east-1/flight/2016/csv",
    job_script_filepath,
    "doc-example-job-#{random_int}"
  )

  puts "-" * 88
  puts "You have reached the end of this tour of AWS Glue."
  puts "To destroy CDK-created resources, run:\n       cdk destroy"
  puts "-" * 88

end
```

Crie um script de ETL usado pelo AWS Glue para extrair, transformar e carregar dados durante execuções de trabalhos.

```
import sys
from awsglue.transforms import *
from awsglue.utils import getResolvedOptions
from pyspark.context import SparkContext
from awsglue.context import GlueContext
from awsglue.job import Job
```

```
"""
These custom arguments must be passed as Arguments to the StartJobRun request.
    --input_database    The name of a metadata database that is contained in your
                        AWS Glue Data Catalog and that contains tables that
 describe
                        the data to be processed.
    --input_table       The name of a table in the database that describes the data
 to
                        be processed.
    --output_bucket_url An S3 bucket that receives the transformed output data.
"""
args = getResolvedOptions(
    sys.argv, ["JOB_NAME", "input_database", "input_table", "output_bucket_url"]
)
sc = SparkContext()
glueContext = GlueContext(sc)
spark = glueContext.spark_session
job = Job(glueContext)
job.init(args["JOB_NAME"], args)

# Script generated for node S3 Flight Data.
S3FlightData_node1 = glueContext.create_dynamic_frame.from_catalog(
    database=args["input_database"],
    table_name=args["input_table"],
    transformation_ctx="S3FlightData_node1",
)

# This mapping performs two main functions:
# 1. It simplifies the output by removing most of the fields from the data.
# 2. It renames some fields. For example, `fl_date` is renamed to `flight_date`.
ApplyMapping_node2 = ApplyMapping.apply(
    frame=S3FlightData_node1,
    mappings=[
        ("year", "long", "year", "long"),
        ("month", "long", "month", "tinyint"),
        ("day_of_month", "long", "day", "tinyint"),
        ("fl_date", "string", "flight_date", "string"),
        ("carrier", "string", "carrier", "string"),
        ("fl_num", "long", "flight_num", "long"),
        ("origin_city_name", "string", "origin_city_name", "string"),
        ("origin_state_abr", "string", "origin_state_abr", "string"),
        ("dest_city_name", "string", "dest_city_name", "string"),
        ("dest_state_abr", "string", "dest_state_abr", "string"),
        ("dep_time", "long", "departure_time", "long"),
```

```
        ("wheels_off", "long", "wheels_off", "long"),
        ("wheels_on", "long", "wheels_on", "long"),
        ("arr_time", "long", "arrival_time", "long"),
        ("mon", "string", "mon", "string"),
    ],
    transformation_ctx="ApplyMapping_node2",
)

# Script generated for node Revised Flight Data.
RevisedFlightData_node3 = glueContext.write_dynamic_frame.from_options(
    frame=ApplyMapping_node2,
    connection_type="s3",
    format="json",
    connection_options={"path": args["output_bucket_url"], "partitionKeys": []},
    transformation_ctx="RevisedFlightData_node3",
)

job.commit()
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler

- StartJobRun

Exemplos do IAM usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Ruby com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
```

```
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
```

```
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte AttachRolePolicya Referência AWS SDK for Ruby da API.

Anexar uma política a um usuário

Os exemplos de código a seguir mostram como anexar uma política do IAM a um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Attaches a policy to a user
#
# @param user_name [String] The name of the user
# @param policy_arn [String] The Amazon Resource Name (ARN) of the policy
# @return [Boolean] true if successful, false otherwise
def attach_policy_to_user(user_name, policy_arn)
  @iam_client.attach_user_policy(
    user_name: user_name,
    policy_arn: policy_arn
  )
  true
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error attaching policy to user: #{e.message}")
  false
end
```

- Para obter detalhes da API, consulte AttachUserPolicya Referência AWS SDK for Ruby da API.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
```

```
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end
```

```
  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte CreatePolicya Referência AWS SDK for Ruby da API.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Creates a role and attaches policies to it.
  #
  # @param role_name [String] The name of the role.
  # @param assume_role_policy_document [Hash] The trust relationship policy
 document.
  # @param policy_arns [Array<String>] The ARNs of the policies to attach.
  # @return [String, nil] The ARN of the new role if successful, or nil if an error
 occurred.
  def create_role(role_name, assume_role_policy_document, policy_arns)
```

```
    response = @iam_client.create_role(
      role_name: role_name,
      assume_role_policy_document: assume_role_policy_document.to_json
    )
    role_arn = response.role.arn

    policy_arns.each do |policy_arn|
      @iam_client.attach_role_policy(
        role_name: role_name,
        policy_arn: policy_arn
      )
    end

    role_arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating role: #{e.message}")
    nil
  end
```

- Para obter detalhes da API, consulte CreateRolea Referência AWS SDK for Ruby da API.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar uma função vinculada ao serviço do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Creates a service-linked role
  #
  # @param service_name [String] The service name to create the role for.
  # @param description [String] The description of the service-linked role.
  # @param suffix [String] Suffix for customizing role name.
  # @return [String] The name of the created role
  def create_service_linked_role(service_name, description, suffix)
    response = @iam_client.create_service_linked_role(
```

```
      aws_service_name: service_name, description: description, custom_suffix:
suffix,)
    role_name = response.role.role_name
    @logger.info("Created service-linked role #{role_name}.")
    role_name
  rescue Aws::Errors::ServiceError => e
    @logger.error("Couldn't create service-linked role for #{service_name}. Here's
why:")
    @logger.error("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea Referência AWS SDK for Ruby da API.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Creates a user and their login profile
#
# @param user_name [String] The name of the user
# @param initial_password [String] The initial password for the user
# @return [String, nil] The ID of the user if created, or nil if an error occurred
```

```
def create_user(user_name, initial_password)
  response = @iam_client.create_user(user_name: user_name)
  @iam_client.wait_until(:user_exists, user_name: user_name)
  @iam_client.create_login_profile(
    user_name: user_name,
    password: initial_password,
    password_reset_required: true
  )
  @logger.info("User '#{user_name}' created successfully.")
  response.user.user_id
rescue Aws::IAM::Errors::EntityAlreadyExists
  @logger.error("Error creating user '#{user_name}': user already exists.")
  nil
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error creating user '#{user_name}': #{e.message}")
  nil
end
```

- Para obter detalhes da API, consulte CreateUsera Referência AWS SDK for Ruby da API.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
  end

  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
 #{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end
```

```
  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end

  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte CreateAccessKeya Referência AWS SDK for Ruby da API.

Criar um alias para uma conta

O exemplo de código a seguir mostra como criar um alias para uma conta do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists available AWS account aliases.
  def list_aliases
    response = @iam_client.list_account_aliases

    if response.account_aliases.count.positive?
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
```

```
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte CreateAccountAliasa Referência AWS SDK for Ruby da API.

Para criar uma política em linha para um usuário

O exemplo de código a seguir mostra como criar uma política em linha do IAM para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Creates an inline policy for a specified user.
```

```
  # @param username [String] The name of the IAM user.
  # @param policy_name [String] The name of the policy to create.
  # @param policy_document [String] The JSON policy document.
  # @return [Boolean]
  def create_user_policy(username, policy_name, policy_document)
    @iam_client.put_user_policy({
      user_name: username,
      policy_name: policy_name,
      policy_document: policy_document
    })
    @logger.info("Policy #{policy_name} created for user #{username}.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't create policy #{policy_name} for user #{username}.
 Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
    false
  end
```

- Para obter detalhes da API, consulte PutUserPolicya Referência AWS SDK for Ruby da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Deletes a role and its attached policies.
  #
  # @param role_name [String] The name of the role to delete.
  def delete_role(role_name)
    begin
      # Detach and delete attached policies
      @iam_client.list_attached_role_policies(role_name: role_name).each do |
response|
```

```
        response.attached_policies.each do |policy|
          @iam_client.detach_role_policy({
                                  role_name: role_name,
                                  policy_arn: policy.policy_arn
                                })
          # Check if the policy is a customer managed policy (not AWS managed)
          unless policy.policy_arn.include?("aws:policy/")
            @iam_client.delete_policy({ policy_arn: policy.policy_arn })
            @logger.info("Deleted customer managed policy #{policy.policy_name}.")
          end
        end
      end

      # Delete the role
      @iam_client.delete_role({ role_name: role_name })
      @logger.info("Deleted role #{role_name}.")
    rescue Aws::IAM::Errors::ServiceError => e
      @logger.error("Couldn't detach policies and delete role #{role_name}. Here's
why:")
      @logger.error("\t#{e.code}: #{e.message}")
      raise
    end
  end
```

- Para obter detalhes da API, consulte DeleteRolea Referência AWS SDK for Ruby da API.

Excluir um certificado do servidor

Os exemplos de código a seguir mostram como excluir certificado de servidor do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
```

```
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates

    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
#{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
```

```
      new_server_certificate_name: new_name
    )
    @logger.info("Server certificate name updated from '#{current_name}' to
 '#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteServerCertificatea Referência AWS SDK for Ruby da API.

Excluir um perfil vinculado ao serviço

O exemplo de código a seguir mostra como excluir um perfil vinculado ao serviço do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Deletes a service-linked role.
  #
  # @param role_name [String] The name of the role to delete.
  def delete_service_linked_role(role_name)
```

```
    response = @iam_client.delete_service_linked_role(role_name: role_name)
    task_id = response.deletion_task_id
    check_deletion_status(role_name, task_id)
  rescue Aws::Errors::ServiceError => e
    handle_deletion_error(e, role_name)
  end

  private

  # Checks the deletion status of a service-linked role
  #
  # @param role_name [String] The name of the role being deleted
  # @param task_id [String] The task ID for the deletion process
  def check_deletion_status(role_name, task_id)
    loop do
      response = @iam_client.get_service_linked_role_deletion_status(
        deletion_task_id: task_id)
      status = response.status
      @logger.info("Deletion of #{role_name} #{status}.")
      break if %w[SUCCEEDED FAILED].include?(status)
      sleep(3)
    end
  end

  # Handles deletion error
  #
  # @param e [Aws::Errors::ServiceError] The error encountered during deletion
  # @param role_name [String] The name of the role attempted to delete
  def handle_deletion_error(e, role_name)
    unless e.code == "NoSuchEntity"
      @logger.error("Couldn't delete #{role_name}. Here's why:")
      @logger.error("\t#{e.code}: #{e.message}")
      raise
    end
  end
```

- Para obter detalhes da API, consulte DeleteServiceLinkedRolea Referência AWS SDK for Ruby da API.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes a user and their associated resources
#
# @param user_name [String] The name of the user to delete
def delete_user(user_name)
  user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
  user.each do |key|
    @iam_client.delete_access_key({ access_key_id: key.access_key_id, user_name:
user_name })
    @logger.info("Deleted access key #{key.access_key_id} for user
'#{user_name}'.")
  end

  @iam_client.delete_user(user_name: user_name)
  @logger.info("Deleted user '#{user_name}'.")
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error deleting user '#{user_name}': #{e.message}")
end
```

- Para obter detalhes da API, consulte DeleteUsera Referência AWS SDK for Ruby da API.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
```

```
  end

  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
#{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end

  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end

  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
```

```
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteAccessKeya Referência AWS SDK for Ruby da API.

Excluir um alias de conta

O exemplo de código a seguir mostra como excluir um alias da conta do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists available AWS account aliases.
  def list_aliases
    response = @iam_client.list_account_aliases
```

```
    if response.account_aliases.count.positive?
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DeleteAccountAliasa Referência AWS SDK for Ruby da API.

Excluir uma política em linha de um usuário

O exemplo de código a seguir mostra como excluir uma política em linha do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes a user and their associated resources
#
# @param user_name [String] The name of the user to delete
def delete_user(user_name)
  user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
  user.each do |key|
    @iam_client.delete_access_key({ access_key_id: key.access_key_id, user_name:
user_name })
    @logger.info("Deleted access key #{key.access_key_id} for user
'#{user_name}'.")
  end

  @iam_client.delete_user(user_name: user_name)
  @logger.info("Deleted user '#{user_name}'.")
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error deleting user '#{user_name}': #{e.message}")
end
```

- Para obter detalhes da API, consulte DeleteUserPolicya Referência AWS SDK for Ruby da API.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
```

```
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
```

```
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte DetachRolePolicya Referência AWS SDK for Ruby da API.

Desanexar uma política de um usuário

Os exemplos de código a seguir mostram como desanexar uma política do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Detaches a policy from a user
  #
  # @param user_name [String] The name of the user
  # @param policy_arn [String] The ARN of the policy to detach
```

```
  # @return [Boolean] true if the policy was successfully detached, false otherwise
  def detach_user_policy(user_name, policy_arn)
    @iam_client.detach_user_policy(
      user_name: user_name,
      policy_arn: policy_arn
    )
    @logger.info("Policy '#{policy_arn}' detached from user '#{user_name}'
successfully.")
    true
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Error detaching policy: Policy or user does not exist.")
    false
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from user '#{user_name}': #{e.message}")
    false
  end
```

- Para obter detalhes da API, consulte DetachUserPolicya Referência AWS SDK for Ruby da API.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
```

```
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte GetPolicya Referência AWS SDK for Ruby da API.

Obter um perfil

O exemplo de código a seguir mostra como obter uma função do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Gets data about a role.
  #
  # @param name [String] The name of the role to look up.
  # @return [Aws::IAM::Role] The retrieved role.
  def get_role(name)
    role = @iam_client.get_role({
                                  role_name: name,
                                }).role
    puts("Got data for role '#{role.role_name}'. Its ARN is '#{role.arn}'.")
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't get data for role '#{name}' Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    role
  end
```

- Para obter detalhes da API, consulte GetRolea Referência AWS SDK for Ruby da API.

Obter um usuário

O exemplo de código a seguir mostra como obter um usuário do IAM.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Retrieves a user's details
 #
 # @param user_name [String] The name of the user to retrieve
 # @return [Aws::IAM::Types::User, nil] The user object if found, or nil if an
error occurred
 def get_user(user_name)
   response = @iam_client.get_user(user_name: user_name)
   response.user
 rescue Aws::IAM::Errors::NoSuchEntity
   @logger.error("User '#{user_name}' not found.")
   nil
 rescue Aws::IAM::Errors::ServiceError => e
   @logger.error("Error retrieving user '#{user_name}': #{e.message}")
   nil
 end
```

- Para obter detalhes da API, consulte GetUsera Referência AWS SDK for Ruby da API.

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Class to manage IAM account password policies
class PasswordPolicyManager
  attr_accessor :iam_client, :logger

  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "IAMPolicyManager"
  end

  # Retrieves and logs the account password policy
  def print_account_password_policy
    begin
      response = @iam_client.get_account_password_policy
      @logger.info("The account password policy is:
 #{response.password_policy.to_h}")
    rescue Aws::IAM::Errors::NoSuchEntity
      @logger.info("The account does not have a password policy.")
    rescue Aws::Errors::ServiceError => e
      @logger.error("Couldn't print the account password policy. Error: #{e.code} -
 #{e.message}")
      raise
    end
  end
end
```

- Para obter detalhes da API, consulte GetAccountPasswordPolicya Referência AWS SDK for Ruby da API.

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no AWSCode Examples Repository.

```
class SamlProviderLister
  # Initializes the SamlProviderLister with IAM client and a logger.
  # @param iam_client [Aws::IAM::Client] The IAM client object.
  # @param logger [Logger] The logger object for logging output.
  def initialize(iam_client, logger = Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists up to a specified number of SAML providers for the account.
  # @param count [Integer] The maximum number of providers to list.
  # @return [Aws::IAM::Client::Response]
  def list_saml_providers(count)
    response = @iam_client.list_saml_providers
    response.saml_provider_list.take(count).each do |provider|
      @logger.info("\t#{provider.arn}")
    end
    response
  rescue Aws::Errors::ServiceError => e
    @logger.error("Couldn't list SAML providers. Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
    raise
  end
end
```

- Para obter detalhes da API, consulte ListSAMLProvider na Referência da API do AWS SDK for Ruby.

Listar as chaves de acesso de um usuário

O exemplo de código a seguir mostra como listar as chaves de acesso do IAM de um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, desativa e exclui chaves de acesso.

```
# Manages access keys for IAM users
class AccessKeyManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "AccessKeyManager"
  end

  # Lists access keys for a user
  #
  # @param user_name [String] The name of the user.
  def list_access_keys(user_name)
    response = @iam_client.list_access_keys(user_name: user_name)
    if response.access_key_metadata.empty?
      @logger.info("No access keys found for user '#{user_name}'.")
    else
      response.access_key_metadata.map(&:access_key_id)
```

```
    end
  rescue Aws::IAM::Errors::NoSuchEntity => e
    @logger.error("Error listing access keys: cannot find user '#{user_name}'.")
    []
  rescue StandardError => e
    @logger.error("Error listing access keys: #{e.message}")
    []
  end

  # Creates an access key for a user
  #
  # @param user_name [String] The name of the user.
  # @return [Boolean]
  def create_access_key(user_name)
    response = @iam_client.create_access_key(user_name: user_name)
    access_key = response.access_key
    @logger.info("Access key created for user '#{user_name}':
#{access_key.access_key_id}")
    access_key
  rescue Aws::IAM::Errors::LimitExceeded => e
    @logger.error("Error creating access key: limit exceeded. Cannot create more.")
    nil
  rescue StandardError => e
    @logger.error("Error creating access key: #{e.message}")
    nil
  end

  # Deactivates an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def deactivate_access_key(user_name, access_key_id)
    @iam_client.update_access_key(
      user_name: user_name,
      access_key_id: access_key_id,
      status: "Inactive"
    )
    true
  rescue StandardError => e
    @logger.error("Error deactivating access key: #{e.message}")
    false
  end
```

```
  # Deletes an access key
  #
  # @param user_name [String] The name of the user.
  # @param access_key_id [String] The ID for the access key.
  # @return [Boolean]
  def delete_access_key(user_name, access_key_id)
    @iam_client.delete_access_key(
      user_name: user_name,
      access_key_id: access_key_id
    )
    true
  rescue StandardError => e
    @logger.error("Error deleting access key: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAccessKeysa Referência AWS SDK for Ruby da API.

Listar aliases de conta

O exemplo de código a seguir mostra como listar aliases de conta do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, crie e exclua aliases de contas.

```
class IAMAliasManager
  # Initializes the IAM client and logger
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end
```

```
  # Lists available AWS account aliases.
  def list_aliases
    response = @iam_client.list_account_aliases

    if response.account_aliases.count.positive?
      @logger.info("Account aliases are:")
      response.account_aliases.each { |account_alias| @logger.info("
 #{account_alias}") }
    else
      @logger.info("No account aliases found.")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing account aliases: #{e.message}")
  end

  # Creates an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to create.
  # @return [Boolean] true if the account alias was created; otherwise, false.
  def create_account_alias(account_alias)
    @iam_client.create_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating account alias: #{e.message}")
    false
  end

  # Deletes an AWS account alias.
  #
  # @param account_alias [String] The name of the account alias to delete.
  # @return [Boolean] true if the account alias was deleted; otherwise, false.
  def delete_account_alias(account_alias)
    @iam_client.delete_account_alias(account_alias: account_alias)
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting account alias: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAccountAliasesa Referência AWS SDK for Ruby da API.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# A class to manage IAM operations via the AWS SDK client
class IamGroupManager
  # Initializes the IamGroupManager class
  # @param iam_client [Aws::IAM::Client] An instance of the IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Lists up to a specified number of groups for the account.
  # @param count [Integer] The maximum number of groups to list.
  # @return [Aws::IAM::Client::Response]
  def list_groups(count)
    response = @iam_client.list_groups(max_items: count)
    response.groups.each do |group|
      @logger.info("\t#{group.group_name}")
    end
    response
  rescue Aws::Errors::ServiceError => e
    @logger.error("Couldn't list groups for the account. Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
    raise
  end
end
```

- Para obter detalhes da API, consulte ListGroupsa Referência AWS SDK for Ruby da API.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists policy ARNs attached to a role
#
# @param role_name [String] The name of the role
# @return [Array<String>] List of policy ARNs
def list_attached_policy_arns(role_name)
  response = @iam_client.list_attached_role_policies(role_name: role_name)
  response.attached_policies.map(&:policy_arn)
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error listing policies attached to role: #{e.message}")
  []
end
```

- Para obter detalhes da API, consulte ListRolePoliciesa Referência AWS SDK for Ruby da API.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
 #{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
 #{e.message}")
```

```
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
```

```
    false
  end
end
```

- Para obter detalhes da API, consulte ListPoliciesa Referência AWS SDK for Ruby da API.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas anexadas a uma função do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Este módulo de exemplo lista, cria, anexa e separa políticas de função.

```
# Manages policies in AWS Identity and Access Management (IAM)
class RolePolicyManager
  # Initialize with an AWS IAM client
  #
  # @param iam_client [Aws::IAM::Client] An initialized IAM client
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "PolicyManager"
  end

  # Creates a policy
  #
  # @param policy_name [String] The name of the policy
  # @param policy_document [Hash] The policy document
  # @return [String] The policy ARN if successful, otherwise nil
  def create_policy(policy_name, policy_document)
    response = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document.to_json
    )
```

```
    response.policy.arn
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error creating policy: #{e.message}")
    nil
  end

  # Fetches an IAM policy by its ARN
  # @param policy_arn [String] the ARN of the IAM policy to retrieve
  # @return [Aws::IAM::Types::GetPolicyResponse] the policy object if found
  def get_policy(policy_arn)
    response = @iam_client.get_policy(policy_arn: policy_arn)
    policy = response.policy
    @logger.info("Got policy '#{policy.policy_name}'. Its ID is:
#{policy.policy_id}.")
    policy
  rescue Aws::IAM::Errors::NoSuchEntity
    @logger.error("Couldn't get policy '#{policy_arn}'. The policy does not exist.")
    raise
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't get policy '#{policy_arn}'. Here's why: #{e.code}:
#{e.message}")
    raise
  end

  # Attaches a policy to a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def attach_policy_to_role(role_name, policy_arn)
    @iam_client.attach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error attaching policy to role: #{e.message}")
    false
  end

  # Lists policy ARNs attached to a role
  #
  # @param role_name [String] The name of the role
  # @return [Array<String>] List of policy ARNs
```

```
  def list_attached_policy_arns(role_name)
    response = @iam_client.list_attached_role_policies(role_name: role_name)
    response.attached_policies.map(&:policy_arn)
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing policies attached to role: #{e.message}")
    []
  end

  # Detaches a policy from a role
  #
  # @param role_name [String] The name of the role
  # @param policy_arn [String] The policy ARN
  # @return [Boolean] true if successful, false otherwise
  def detach_policy_from_role(role_name, policy_arn)
    @iam_client.detach_role_policy(
      role_name: role_name,
      policy_arn: policy_arn
    )
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error detaching policy from role: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa Referência AWS SDK for Ruby da API.

Listar a funções

O exemplo de código a seguir mostra como listar funções do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Lists IAM roles up to a specified count.
```

```
  # @param count [Integer] the maximum number of roles to list.
  # @return [Array<String>] the names of the roles.
  def list_roles(count)
    role_names = []
    roles_counted = 0

    @iam_client.list_roles.each_page do |page|
      page.roles.each do |role|
        break if roles_counted >= count
        @logger.info("\t#{roles_counted + 1}: #{role.role_name}")
        role_names << role.role_name
        roles_counted += 1
      end
      break if roles_counted >= count
    end

    role_names
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Couldn't list roles for the account. Here's why:")
    @logger.error("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte ListRolesa Referência AWS SDK for Ruby da API.

Listar certificados do servidor

Os exemplos de código a seguir mostram como listar certificados de servidor do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
  def initialize(iam_client, logger: Logger.new($stdout))
```

```
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates

    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
#{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
      new_server_certificate_name: new_name
```

```
    )
    @logger.info("Server certificate name updated from '#{current_name}' to
 '#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte ListServerCertificatesa Referência AWS SDK for Ruby da API.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Lists all users in the AWS account
#
# @return [Array<Aws::IAM::Types::User>] An array of user objects
def list_users
  users = []
  @iam_client.list_users.each_page do |page|
    page.users.each do |user|
      users << user
    end
  end
  users
rescue Aws::IAM::Errors::ServiceError => e
  @logger.error("Error listing users: #{e.message}")
  []
end
```

- Para obter detalhes da API, consulte ListUsersa Referência AWS SDK for Ruby da API.

Atualizar um certificado do servidor

O exemplo de código a seguir mostra como atualizar um certificado de servidor do IAM.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste, atualize e exclua certificados do servidor.

```
class ServerCertificateManager
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
    @logger.progname = "ServerCertificateManager"
  end

  # Creates a new server certificate.
  # @param name [String] the name of the server certificate
  # @param certificate_body [String] the contents of the certificate
  # @param private_key [String] the private key contents
  # @return [Boolean] returns true if the certificate was successfully created
  def create_server_certificate(name, certificate_body, private_key)
    @iam_client.upload_server_certificate({
                                            server_certificate_name: name,
                                            certificate_body: certificate_body,
                                            private_key: private_key,
                                          })
    true
  rescue Aws::IAM::Errors::ServiceError => e
    puts "Failed to create server certificate: #{e.message}"
    false
  end

  # Lists available server certificate names.
  def list_server_certificate_names
    response = @iam_client.list_server_certificates

    if response.server_certificate_metadata_list.empty?
      @logger.info("No server certificates found.")
      return
    end

    response.server_certificate_metadata_list.each do |certificate_metadata|
      @logger.info("Certificate Name:
 #{certificate_metadata.server_certificate_name}")
    end
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error listing server certificates: #{e.message}")
  end

  # Updates the name of a server certificate.
  def update_server_certificate_name(current_name, new_name)
```

```
    @iam_client.update_server_certificate(
      server_certificate_name: current_name,
      new_server_certificate_name: new_name
    )
    @logger.info("Server certificate name updated from '#{current_name}' to
 '#{new_name}'.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error updating server certificate name: #{e.message}")
    false
  end

  # Deletes a server certificate.
  def delete_server_certificate(name)
    @iam_client.delete_server_certificate(server_certificate_name: name)
    @logger.info("Server certificate '#{name}' deleted.")
    true
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting server certificate: #{e.message}")
    false
  end
end
```

- Para obter detalhes da API, consulte UpdateServerCertificatea Referência AWS SDK for Ruby da API.

Atualizar um usuário

O exemplo de código a seguir mostra como atualizar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Updates an IAM user's name
#
# @param current_name [String] The current name of the user
# @param new_name [String] The new name of the user
def update_user_name(current_name, new_name)
  @iam_client.update_user(user_name: current_name, new_user_name: new_name)
  true
rescue StandardError => e
  @logger.error("Error updating user name from '#{current_name}' to '#{new_name}':
#{e.message}")
  false
end
```

- Para obter detalhes da API, consulte UpdateUsera Referência AWS SDK for Ruby da API.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.

- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

Crie um usuário e um perfil do IAM que conceda permissão para listar os buckets do Amazon S3. O usuário só tem direitos para assumir a função. Após assumir a função, use credenciais temporárias para listar intervalos para a conta.

```
# Wraps the scenario actions.
class ScenarioCreateUserAssumeRole
  attr_reader :iam_client

  # @param [Aws::IAM::Client] iam_client: The AWS IAM client.
  def initialize(iam_client, logger: Logger.new($stdout))
    @iam_client = iam_client
    @logger = logger
  end

  # Waits for the specified number of seconds.
  #
  # @param duration [Integer] The number of seconds to wait.
  def wait(duration)
    puts("Give AWS time to propagate resources...")
    sleep(duration)
  end

  # Creates a user.
  #
  # @param user_name [String] The name to give the user.
  # @return [Aws::IAM::User] The newly created user.
  def create_user(user_name)
    user = @iam_client.create_user(user_name: user_name).user
    @logger.info("Created demo user named #{user.user_name}.")
  rescue Aws::Errors::ServiceError => e
```

```
    @logger.info("Tried and failed to create demo user.")
    @logger.info("\t#{e.code}: #{e.message}")
    @logger.info("\nCan't continue the demo without a user!")
    raise
  else
    user
  end

  # Creates an access key for a user.
  #
  # @param user [Aws::IAM::User] The user that owns the key.
  # @return [Aws::IAM::AccessKeyPair] The newly created access key.
  def create_access_key_pair(user)
    user_key = @iam_client.create_access_key(user_name: user.user_name).access_key
    @logger.info("Created accesskey pair for user #{user.user_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't create access keys for user #{user.user_name}.")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  else
    user_key
  end

  # Creates a role that can be assumed by a user.
  #
  # @param role_name [String] The name to give the role.
  # @param user [Aws::IAM::User] The user who is granted permission to assume the
role.
  # @return [Aws::IAM::Role] The newly created role.
  def create_role(role_name, user)
    trust_policy = {
      Version: "2012-10-17",
      Statement: [{
                    Effect: "Allow",
                    Principal: {'AWS': user.arn},
                    Action: "sts:AssumeRole"
                  }]
    }.to_json
    role = @iam_client.create_role(
      role_name: role_name,
      assume_role_policy_document: trust_policy
    ).role
    @logger.info("Created role #{role.role_name}.")
  rescue Aws::Errors::ServiceError => e
```

```
    @logger.info("Couldn't create a role for the demo. Here's why: ")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  else
    role
  end

  # Creates a policy that grants permission to list S3 buckets in the account, and
  # then attaches the policy to a role.
  #
  # @param policy_name [String] The name to give the policy.
  # @param role [Aws::IAM::Role] The role that the policy is attached to.
  # @return [Aws::IAM::Policy] The newly created policy.
  def create_and_attach_role_policy(policy_name, role)
    policy_document = {
      Version: "2012-10-17",
      Statement: [{
                    Effect: "Allow",
                    Action: "s3:ListAllMyBuckets",
                    Resource: "arn:aws:s3:::*"
                  }]
    }.to_json
    policy = @iam_client.create_policy(
      policy_name: policy_name,
      policy_document: policy_document
    ).policy
    @iam_client.attach_role_policy(
      role_name: role.role_name,
      policy_arn: policy.arn
    )
    @logger.info("Created policy #{policy.policy_name} and attached it to role
#{role.role_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't create a policy and attach it to role #{role.role_name}.
Here's why: ")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  end

  # Creates an inline policy for a user that lets the user assume a role.
  #
  # @param policy_name [String] The name to give the policy.
  # @param user [Aws::IAM::User] The user that owns the policy.
  # @param role [Aws::IAM::Role] The role that can be assumed.
```

```
 # @return [Aws::IAM::UserPolicy] The newly created policy.
 def create_user_policy(policy_name, user, role)
   policy_document = {
     Version: "2012-10-17",
     Statement: [{
                   Effect: "Allow",
                   Action: "sts:AssumeRole",
                   Resource: role.arn
                 }]
   }.to_json
   @iam_client.put_user_policy(
     user_name: user.user_name,
     policy_name: policy_name,
     policy_document: policy_document
   )
   puts("Created an inline policy for #{user.user_name} that lets the user assume
role #{role.role_name}.")
 rescue Aws::Errors::ServiceError => e
   @logger.info("Couldn't create an inline policy for user #{user.user_name}.
Here's why: ")
   @logger.info("\t#{e.code}: #{e.message}")
   raise
 end

 # Creates an Amazon S3 resource with specified credentials. This is separated into
a
 # factory function so that it can be mocked for unit testing.
 #
 # @param credentials [Aws::Credentials] The credentials used by the Amazon S3
resource.
 def create_s3_resource(credentials)
   Aws::S3::Resource.new(client: Aws::S3::Client.new(credentials: credentials))
 end

 # Lists the S3 buckets for the account, using the specified Amazon S3 resource.
 # Because the resource uses credentials with limited access, it may not be able to
 # list the S3 buckets.
 #
 # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
 def list_buckets(s3_resource)
   count = 10
   s3_resource.buckets.each do |bucket|
     @logger.info "\t#{bucket.name}"
     count -= 1
```

```
      break if count.zero?
    end
  rescue Aws::Errors::ServiceError => e
    if e.code == "AccessDenied"
      puts("Attempt to list buckets with no permissions: AccessDenied.")
    else
      @logger.info("Couldn't list buckets for the account. Here's why: ")
      @logger.info("\t#{e.code}: #{e.message}")
      raise
    end
  end

  # Creates an AWS Security Token Service (AWS STS) client with specified
credentials.
  # This is separated into a factory function so that it can be mocked for unit
testing.
  #
  # @param key_id [String] The ID of the access key used by the STS client.
  # @param key_secret [String] The secret part of the access key used by the STS
client.
  def create_sts_client(key_id, key_secret)
    Aws::STS::Client.new(access_key_id: key_id, secret_access_key: key_secret)
  end

  # Gets temporary credentials that can be used to assume a role.
  #
  # @param role_arn [String] The ARN of the role that is assumed when these
credentials
  #                          are used.
  # @param sts_client [AWS::STS::Client] An AWS STS client.
  # @return [Aws::AssumeRoleCredentials] The credentials that can be used to assume
the role.
  def assume_role(role_arn, sts_client)
    credentials = Aws::AssumeRoleCredentials.new(
      client: sts_client,
      role_arn: role_arn,
      role_session_name: "create-use-assume-role-scenario"
    )
    @logger.info("Assumed role '#{role_arn}', got temporary credentials.")
    credentials
  end

  # Deletes a role. If the role has policies attached, they are detached and
  # deleted before the role is deleted.
```

```
  #
  # @param role_name [String] The name of the role to delete.
  def delete_role(role_name)
    @iam_client.list_attached_role_policies(role_name:
 role_name).attached_policies.each do |policy|
      @iam_client.detach_role_policy(role_name: role_name, policy_arn:
 policy.policy_arn)
      @iam_client.delete_policy(policy_arn: policy.policy_arn)
      @logger.info("Detached and deleted policy #{policy.policy_name}.")
    end
    @iam_client.delete_role({ role_name: role_name })
    @logger.info("Role deleted: #{role_name}.")
  rescue Aws::Errors::ServiceError => e
    @logger.info("Couldn't detach policies and delete role #{role.name}. Here's
 why:")
    @logger.info("\t#{e.code}: #{e.message}")
    raise
  end

  # Deletes a user. If the user has inline policies or access keys, they are deleted
  # before the user is deleted.
  #
  # @param user [Aws::IAM::User] The user to delete.
  def delete_user(user_name)
    user = @iam_client.list_access_keys(user_name: user_name).access_key_metadata
    user.each do |key|
      @iam_client.delete_access_key({ access_key_id: key.access_key_id, user_name:
 user_name })
      @logger.info("Deleted access key #{key.access_key_id} for user
 '#{user_name}'.")
    end

    @iam_client.delete_user(user_name: user_name)
    @logger.info("Deleted user '#{user_name}'.")
  rescue Aws::IAM::Errors::ServiceError => e
    @logger.error("Error deleting user '#{user_name}': #{e.message}")
  end
end

# Runs the IAM create a user and assume a role scenario.
def run_scenario(scenario)
  puts("-" * 88)
  puts("Welcome to the IAM create a user and assume a role demo!")
  puts("-" * 88)
```

```
  user = scenario.create_user("doc-example-user-#{Random.uuid}")
  user_key = scenario.create_access_key_pair(user)
  scenario.wait(10)
  role = scenario.create_role("doc-example-role-#{Random.uuid}", user)
  scenario.create_and_attach_role_policy("doc-example-role-policy-#{Random.uuid}",
 role)
  scenario.create_user_policy("doc-example-user-policy-#{Random.uuid}", user, role)
  scenario.wait(10)
  puts("Try to list buckets with credentials for a user who has no permissions.")
  puts("Expect AccessDenied from this call.")
  scenario.list_buckets(
    scenario.create_s3_resource(Aws::Credentials.new(user_key.access_key_id,
 user_key.secret_access_key)))
  puts("Now, assume the role that grants permission.")
  temp_credentials = scenario.assume_role(
    role.arn, scenario.create_sts_client(user_key.access_key_id,
 user_key.secret_access_key))
  puts("Here are your buckets:")
  scenario.list_buckets(scenario.create_s3_resource(temp_credentials))
  puts("Deleting role '#{role.role_name}' and attached policies.")
  scenario.delete_role(role.role_name)
  puts("Deleting user '#{user.user_name}', policies, and keys.")
  scenario.delete_user(user.user_name)
  puts("Thanks for watching!")
  puts("-" * 88)
rescue Aws::Errors::ServiceError => e
  puts("Something went wrong with the demo.")
  puts("\t#{e.code}: #{e.message}")
end

run_scenario(ScenarioCreateUserAssumeRole.new(Aws::IAM::Client.new)) if
 $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser

- DeleteAccessKey
- DeletePolicy
- DeleteRole
- DeleteUser
- DeleteUserPolicy
- DetachRolePolicy
- PutUserPolicy

Exemplos de AWS KMS usando o SDK para Ruby

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma chave

O exemplo de código a seguir mostra como criar uma AWS KMS key.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms" # v2: require 'aws-sdk'

# Create a AWS KMS key.
# As long we are only encrypting small amounts of data (4 KiB or less) directly,
# a KMS key is fine for our purposes.
# For larger amounts of data,
# use the KMS key to encrypt a data encryption key (DEK).

client = Aws::KMS::Client.new

resp = client.create_key({
                           tags: [
                             {
                               tag_key: "CreatedBy",
                               tag_value: "ExampleUser"
                             }
                           ]
                         })

puts resp.key_metadata.key_id
```

- Para obter detalhes da API, consulte CreateKeya Referência AWS SDK for Ruby da API.

Descriptografar texto cifrado

O exemplo de código a seguir mostra como descriptografar um texto cifrado que foi criptografado por uma chave do KMS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms" # v2: require 'aws-sdk'

# Decrypted blob

blob =
 "01020200785d68faeec386af1057904926253051eb2919d3c16078badf65b808b26dd057c101747cadf3593596
blob_packed = [blob].pack("H*")

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.decrypt({
                        ciphertext_blob: blob_packed
                      })

puts "Raw text: "
puts resp.plaintext
```

- Para obter detalhes da API, consulte Decrypt, na Referência da API do AWS SDK for Ruby.

Criptografar texto usando uma chave

O exemplo de código a seguir mostra como criptografar um texto usando uma chave do KMS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms"  # v2: require 'aws-sdk'

# ARN of the AWS KMS key.
#
# Replace the fictitious key ARN with a valid key ID

keyId = "arn:aws:kms:us-
west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab"

text = "1234567890"

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.encrypt({
  key_id: keyId,
  plaintext: text,
})

# Display a readable version of the resulting encrypted blob.
puts "Blob:"
puts resp.ciphertext_blob.unpack("H*")
```

- Para obter detalhes da API, consulte Encrypt, na Referência da API do AWS SDK for Ruby.

Criptografar novamente um texto cifrado de uma chave para outra

O exemplo de código a seguir mostra como criptografar novamente um texto cifrado de uma chave do KMS para outra.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-kms"  # v2: require 'aws-sdk'
```

```
# Human-readable version of the ciphertext of the data to reencrypt.

blob =
 "01020200785d68faeec386af1057904926253051eb2919d3c16078badf65b808b26dd057c101747cadf3593596
sourceCiphertextBlob = [blob].pack("H*")

# Replace the fictitious key ARN with a valid key ID

destinationKeyId = "arn:aws:kms:us-west-2:111122223333:key/0987dcba-09fe-87dc-65ba-
ab0987654321"

client = Aws::KMS::Client.new(region: "us-west-2")

resp = client.re_encrypt({
  ciphertext_blob: sourceCiphertextBlob,
  destination_key_id: destinationKeyId
})

# Display a readable version of the resulting re-encrypted blob.
puts "Blob:"
puts resp.ciphertext_blob.unpack("H*")
```

- Para obter detalhes da API, consulte ReEncrypta Referência AWS SDK for Ruby da API.

Exemplos de Lambda usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Ruby com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Deploys a Lambda function.
  #
  # @param function_name: The name of the Lambda function.
  # @param handler_name: The fully qualified name of the handler function. This
  #                      must include the file name and the function name.
  # @param role_arn: The IAM role to use for the function.
  # @param deployment_package: The deployment package that contains the function
  #                            code in .zip format.
  # @return: The Amazon Resource Name (ARN) of the newly created function.
  def create_function(function_name, handler_name, role_arn, deployment_package)
    response = @lambda_client.create_function({
                                                role: role_arn.to_s,
                                                function_name: function_name,
                                                handler: handler_name,
                                                runtime: "ruby2.7",
```

```
                                                    code: {
                                                      zip_file: deployment_package
                                                    },
                                                    environment: {
                                                      variables: {
                                                        "LOG_LEVEL" => "info"
                                                      }
                                                    }
                                                  })
    @lambda_client.wait_until(:function_active_v2, { function_name: function_name})
 do |w|
      w.max_attempts = 5
      w.delay = 5
    end
    response
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error creating #{function_name}:\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte CreateFunctiona Referência AWS SDK for Ruby da API.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
```

```
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Deletes a Lambda function.
  # @param function_name: The name of the function to delete.
  def delete_function(function_name)
    print "Deleting function: #{function_name}..."
    @lambda_client.delete_function(
      function_name: function_name
    )
    print "Done!".green
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error deleting #{function_name}:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte DeleteFunctiona Referência AWS SDK for Ruby da API.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Gets data about a Lambda function.
```

```
  #
  # @param function_name: The name of the function.
  # @return response: The function data, or nil if no such function exists.
  def get_function(function_name)
    @lambda_client.get_function(
      {
        function_name: function_name
      }
    )
  rescue Aws::Lambda::Errors::ResourceNotFoundException => e
    @logger.debug("Could not find function: #{function_name}:\n #{e.message}")
    nil
  end
```

- Para obter detalhes da API, consulte GetFunctiona Referência AWS SDK for Ruby da API.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Invokes a Lambda function.
  # @param function_name [String] The name of the function to invoke.
  # @param payload [nil] Payload containing runtime parameters.
```

```
  # @return [Object] The response from the function invocation.
  def invoke_function(function_name, payload = nil)
    params = { function_name: function_name}
    params[:payload] = payload unless payload.nil?
    @lambda_client.invoke(params)
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte Invoke, na Referência da APIs do AWS SDK for Ruby.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Lists the Lambda functions for the current account.
  def list_functions
    functions = []
    @lambda_client.list_functions.each do |response|
      response["functions"].each do |function|
        functions.append(function["function_name"])
      end
    end
```

```
    functions
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte ListFunctionsa Referência AWS SDK for Ruby da API.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Updates the code for a Lambda function by submitting a .zip archive that
 contains
  # the code for the function.

  # @param function_name: The name of the function to update.
  # @param deployment_package: The function code to update, packaged as bytes in
  #                            .zip format.
  # @return: Data about the update, including the status.
  def update_function_code(function_name, deployment_package)
    @lambda_client.update_function_code(
      function_name: function_name,
      zip_file: deployment_package
```

```
    )
    @lambda_client.wait_until(:function_updated_v2, { function_name: function_name})
 do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating function code for: #{function_name}:
\n #{e.message}")
    nil
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to update:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte UpdateFunctionCodea Referência AWS SDK for Ruby da API.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
class LambdaWrapper
  attr_accessor :lambda_client

  def initialize
    @lambda_client = Aws::Lambda::Client.new
    @logger = Logger.new($stdout)
    @logger.level = Logger::WARN
  end

  # Updates the environment variables for a Lambda function.
  # @param function_name: The name of the function to update.
```

```
  # @param log_level: The log level of the function.
  # @return: Data about the update, including the status.
  def update_function_configuration(function_name, log_level)
    @lambda_client.update_function_configuration({
                                                    function_name: function_name,
                                                    environment: {
                                                      variables: {
                                                        "LOG_LEVEL" => log_level
                                                      }
                                                    }
                                                  })
    @lambda_client.wait_until(:function_updated_v2, { function_name: function_name})
 do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating configurations for #{function_name}:
\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n #{e.message}")
  end
```

- Para obter detalhes da API, consulte UpdateFunctionConfigurationa Referência AWS SDK for Ruby da API.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Configure as permissões de pré-requisitos do IAM para uma função do Lambda capaz de gravar logs.

```
  # Get an AWS Identity and Access Management (IAM) role.
  #
  # @param iam_role_name: The name of the role to retrieve.
  # @param action: Whether to create or destroy the IAM apparatus.
  # @return: The IAM role.
  def manage_iam(iam_role_name, action)
    role_policy = {
      'Version': "2012-10-17",
      'Statement': [
        {
          'Effect': "Allow",
          'Principal': {
            'Service': "lambda.amazonaws.com"
          },
          'Action': "sts:AssumeRole"
        }
      ]
    }
    case action
    when "create"
      role = $iam_client.create_role(
        role_name: iam_role_name,
        assume_role_policy_document: role_policy.to_json
      )
      $iam_client.attach_role_policy(
        {
          policy_arn: "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole",
          role_name: iam_role_name
        }
      )
```

```
      $iam_client.wait_until(:role_exists, { role_name: iam_role_name }) do |w|
        w.max_attempts = 5
        w.delay = 5
      end
      @logger.debug("Successfully created IAM role: #{role['role']['arn']}")
      @logger.debug("Enforcing a 10-second sleep to allow IAM role to activate
 fully.")
      sleep(10)
      return role, role_policy.to_json
    when "destroy"
      $iam_client.detach_role_policy(
        {
          policy_arn: "arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole",
          role_name: iam_role_name
        }
      )
      $iam_client.delete_role(
        role_name: iam_role_name
      )
      @logger.debug("Detached policy & deleted IAM role: #{iam_role_name}")
    else
      raise "Incorrect action provided. Must provide 'create' or 'destroy'"
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error creating role or attaching policy:\n
 #{e.message}")
  end
```

Defina um manipulador do Lambda que incremente um número fornecido como um parâmetro de invocação.

```
require "logger"

# A function that increments a whole number by one (1) and logs the result.
# Requires a manually-provided runtime parameter, 'number', which must be Int
#
# @param event [Hash] Parameters sent when the function is invoked
# @param context [Hash] Methods and properties that provide information
# about the invocation, function, and execution environment.
# @return incremented_number [String] The incremented number.
def lambda_handler(event:, context:)
```

```
  logger = Logger.new($stdout)
  log_level = ENV["LOG_LEVEL"]
  logger.level = case log_level
                 when "debug"
                   Logger::DEBUG
                 when "info"
                   Logger::INFO
                 else
                   Logger::ERROR
                 end
  logger.debug("This is a debug log message.")
  logger.info("This is an info log message. Code executed successfully!")
  number = event["number"].to_i
  incremented_number = number + 1
  logger.info("You provided #{number.round} and it was incremented to
 #{incremented_number.round}")
  incremented_number.round.to_s
end
```

Compacte a função do Lambda em um pacote de implantação.

```
  # Creates a Lambda deployment package in .zip format.
  # This zip can be passed directly as a string to Lambda when creating the
 function.
  #
  # @param source_file: The name of the object, without suffix, for the Lambda file
 and zip.
  # @return: The deployment package.
  def create_deployment_package(source_file)
    Dir.chdir(File.dirname(__FILE__))
    if File.exist?("lambda_function.zip")
      File.delete("lambda_function.zip")
      @logger.debug("Deleting old zip: lambda_function.zip")
    end
    Zip::File.open("lambda_function.zip", create: true) {
      |zipfile|
      zipfile.add("lambda_function.rb", "#{source_file}.rb")
    }
    @logger.debug("Zipping #{source_file}.rb into: lambda_function.zip.")
    File.read("lambda_function.zip").to_s
  rescue StandardError => e
    @logger.error("There was an error creating deployment package:\n #{e.message}")
```

```
  end
```

Crie uma nova função do Lambda.

```
  # Deploys a Lambda function.
  #
  # @param function_name: The name of the Lambda function.
  # @param handler_name: The fully qualified name of the handler function. This
  #                      must include the file name and the function name.
  # @param role_arn: The IAM role to use for the function.
  # @param deployment_package: The deployment package that contains the function
  #                            code in .zip format.
  # @return: The Amazon Resource Name (ARN) of the newly created function.
  def create_function(function_name, handler_name, role_arn, deployment_package)
    response = @lambda_client.create_function({
                                                role: role_arn.to_s,
                                                function_name: function_name,
                                                handler: handler_name,
                                                runtime: "ruby2.7",
                                                code: {
                                                  zip_file: deployment_package
                                                },
                                                environment: {
                                                  variables: {
                                                    "LOG_LEVEL" => "info"
                                                  }
                                                }
                                              })
    @lambda_client.wait_until(:function_active_v2, { function_name: function_name})
do |w|
      w.max_attempts = 5
      w.delay = 5
    end
    response
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error creating #{function_name}:\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n #{e.message}")
  end
```

Invoque a função do Lambda com parâmetros de runtime opcionais.

```
  # Invokes a Lambda function.
  # @param function_name [String] The name of the function to invoke.
  # @param payload [nil] Payload containing runtime parameters.
  # @return [Object] The response from the function invocation.
  def invoke_function(function_name, payload = nil)
    params = { function_name: function_name}
    params[:payload] = payload unless payload.nil?
    @lambda_client.invoke(params)
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n #{e.message}")
  end
```

Atualize a configuração da função do Lambda para injetar uma nova variável de ambiente.

```
  # Updates the environment variables for a Lambda function.
  # @param function_name: The name of the function to update.
  # @param log_level: The log level of the function.
  # @return: Data about the update, including the status.
  def update_function_configuration(function_name, log_level)
    @lambda_client.update_function_configuration({
                                                    function_name: function_name,
                                                    environment: {
                                                      variables: {
                                                        "LOG_LEVEL" => log_level
                                                      }
                                                    }
                                                  })
    @lambda_client.wait_until(:function_updated_v2, { function_name: function_name})
 do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating configurations for #{function_name}:
\n #{e.message}")
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to activate:\n #{e.message}")
  end
```

Atualize o código da função do Lambda com um pacote de implantação diferente que contenha um código diferente.

```
  # Updates the code for a Lambda function by submitting a .zip archive that
 contains
  # the code for the function.

  # @param function_name: The name of the function to update.
  # @param deployment_package: The function code to update, packaged as bytes in
  #                            .zip format.
  # @return: Data about the update, including the status.
  def update_function_code(function_name, deployment_package)
    @lambda_client.update_function_code(
      function_name: function_name,
      zip_file: deployment_package
    )
    @lambda_client.wait_until(:function_updated_v2, { function_name: function_name})
 do |w|
      w.max_attempts = 5
      w.delay = 5
    end
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error updating function code for: #{function_name}:
\n #{e.message}")
    nil
  rescue Aws::Waiters::Errors::WaiterFailed => e
    @logger.error("Failed waiting for #{function_name} to update:\n #{e.message}")
  end
```

Liste todas as funções do Lambda existentes usando o paginador integrado.

```
  # Lists the Lambda functions for the current account.
  def list_functions
    functions = []
    @lambda_client.list_functions.each do |response|
      response["functions"].each do |function|
        functions.append(function["function_name"])
      end
    end
    functions
  rescue Aws::Lambda::Errors::ServiceException => e
    @logger.error("There was an error executing #{function_name}:\n #{e.message}")
```

```
end
```

Exclua uma função do Lambda específica.

```
# Deletes a Lambda function.
# @param function_name: The name of the function to delete.
def delete_function(function_name)
  print "Deleting function: #{function_name}..."
  @lambda_client.delete_function(
    function_name: function_name
  )
  print "Done!".green
rescue Aws::Lambda::Errors::ServiceException => e
  @logger.error("There was an error deleting #{function_name}:\n #{e.message}")
end
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].map { |record| process_message(record) }
end

def process_message(record)
  message = record['Sns']['Message']
  puts("Processing message: #{message}")
rescue StandardError => e
  puts("Error processing message: #{e}")
  raise
end
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
```

```
  event['Records'].each do |message|
    process_message(message)
  end
  puts "done"
end

def process_message(message)
  begin
    puts "Processed message #{message['body']}"
    # TODO: Do interesting work based on the new message
  rescue StandardError => err
    puts "An error occurred"
    raise err
  end
end
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Ruby.

```
require 'json'

def lambda_handler(event:, context:)
  if event
    batch_item_failures = []
    sqs_batch_response = {}

    event["Records"].each do |record|
      begin
```

```
        # process message
      rescue StandardError => e
        batch_item_failures << {"itemIdentifier" => record['messageId']}
      end
    end

    sqs_batch_response["batchItemFailures"] = batch_item_failures
    return sqs_batch_response
  end
end
```

Exemplos do Amazon Polly usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Amazon Polly.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter vozes disponíveis para síntese

O exemplo de código a seguir mostra como obter vozes disponíveis para síntese do Amazon Polly.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/config
  polly = Aws::Polly::Client.new

  # Get US English voices
  resp = polly.describe_voices(language_code: "en-US")

  resp.voices.each do |v|
    puts v.name
    puts "  " + v.gender
    puts
  end
rescue StandardError => ex
  puts "Could not get voices"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte DescribeVoicesa Referência AWS SDK for Ruby da API.

Listar léxicos de pronúncia

O exemplo de código a seguir mostra como listar os léxicos de pronúncia do Amazon Polly.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/config
  polly = Aws::Polly::Client.new

  resp = polly.list_lexicons

  resp.lexicons.each do |l|
    puts l.name
    puts "  Alphabet:" + l.attributes.alphabet
    puts "  Language:" + l.attributes.language
    puts
  end
rescue StandardError => ex
  puts "Could not get lexicons"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte ListLexiconsa Referência AWS SDK for Ruby da API.

Sintetizar fala a partir de texto

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-polly"  # In v2: require 'aws-sdk'

begin
  # Get the filename from the command line
  if ARGV.empty?
    puts "You must supply a filename"
    exit 1
  end

  filename = ARGV[0]

  # Open file and get the contents as a string
  if File.exist?(filename)
    contents = IO.read(filename)
  else
    puts "No such file: " + filename
    exit 1
  end

  # Create an Amazon Polly client using
  # credentials from the shared credentials file ~/.aws/credentials
  # and the configuration (region) from the shared configuration file ~/.aws/config
  polly = Aws::Polly::Client.new

  resp = polly.synthesize_speech({
    output_format: "mp3",
    text: contents,
    voice_id: "Joanna",
  })

  # Save output
  # Get just the file name
  #  abc/xyz.txt -> xyx.txt
```

```
  name = File.basename(filename)

  # Split up name so we get just the xyz part
  parts = name.split(".")
  first_part = parts[0]
  mp3_file = first_part + ".mp3"

  IO.copy_stream(resp.audio_stream, mp3_file)

  puts "Wrote MP3 content to: " + mp3_file
rescue StandardError => ex
  puts "Got error:"
  puts "Error message:"
  puts ex.message
end
```

- Para obter detalhes da API, consulte SynthesizeSpeecha Referência AWS SDK for Ruby da API.

Exemplos do Amazon RDS usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Amazon RDS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um snapshot de uma instância de banco de dados

O exemplo de código a seguir mostra como criar um snapshot de uma instância de banco de dados do Amazon RDS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# Create a snapshot for an Amazon Relational Database Service (Amazon RDS)
# DB instance.
#
# @param rds_resource [Aws::RDS::Resource] The resource containing SDK logic.
# @param db_instance_name [String] The name of the Amazon RDS DB instance.
# @return [Aws::RDS::DBSnapshot, nil] The snapshot created, or nil if error.
def create_snapshot(rds_resource, db_instance_name)
  id = "snapshot-#{rand(10**6)}"
  db_instance = rds_resource.db_instance(db_instance_name)
  db_instance.create_snapshot({
                                db_snapshot_identifier: id
                              })
rescue Aws::Errors::ServiceError => e
  puts "Couldn't create DB instance snapshot #{id}:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte CreateDBSnapshot na Referência da API do AWS SDK for Ruby.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias de banco de dados do Amazon RDS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) DB instances.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all DB instances, or nil if error.
def list_instances(rds_resource)
  db_instances = []
  rds_resource.db_instances.each do |i|
    db_instances.append({
                          "name": i.id,
                          "status": i.db_instance_status
                        })
  end
  db_instances
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list instances:\n#{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBInstances na Referência da API do AWS SDK for Ruby.

Descrever grupos de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever um grupo de parâmetros de banco de dados do Amazon RDS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) parameter groups.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all parameter groups, or nil if error.
def list_parameter_groups(rds_resource)
  parameter_groups = []
  rds_resource.db_parameter_groups.each do |p|
    parameter_groups.append({
                              "name": p.db_parameter_group_name,
                              "description": p.description
                            })
  end
  parameter_groups
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list parameter groups:\n #{e.message}"
end
```

- Para obter detalhes da API, consulte DescribeDB ParameterGroups em Referência AWS SDK for Ruby da API.

Descrever os parâmetros em um grupo de parâmetros de banco de dados

O exemplo de código a seguir mostra como descrever os parâmetros em um grupo de parâmetros de banco de dados do Amazon RDS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds"  # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) parameter groups.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return [Array, nil] List of all parameter groups, or nil if error.
def list_parameter_groups(rds_resource)
  parameter_groups = []
  rds_resource.db_parameter_groups.each do |p|
    parameter_groups.append({
                              "name": p.db_parameter_group_name,
                              "description": p.description
                            })
  end
  parameter_groups
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list parameter groups:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBParameters na Referência da API do AWS SDK for Ruby.

Descrever os snapshots das instâncias de banco de dados

O exemplo de código a seguir mostra como descrever snapshots de instâncias de banco de dados do Amazon RDS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-rds" # v2: require 'aws-sdk'

# List all Amazon Relational Database Service (Amazon RDS) DB instance
# snapshots.
#
# @param rds_resource [Aws::RDS::Resource] An SDK for Ruby Amazon RDS resource.
# @return instance_snapshots [Array, nil] All instance snapshots, or nil if error.
def list_instance_snapshots(rds_resource)
  instance_snapshots = []
  rds_resource.db_snapshots.each do |s|
    instance_snapshots.append({
                                "id": s.snapshot_id,
                                "status": s.status
                              })
  end
  instance_snapshots
rescue Aws::Errors::ServiceError => e
  puts "Couldn't list instance snapshots:\n #{e.message}"
end
```

- Para ter detalhes da API, consulte DescribeDBSnapshots na Referência da API do AWS SDK for Ruby.

Exemplos do Amazon S3 usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK for Ruby com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Adicionar regras de CORS a um bucket

O exemplo de código a seguir mostra como adicionar regras de compartilhamento de recursos de origem cruzada (CORS) a um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with an
 existing bucket.
  def initialize(bucket_cors)
    @bucket_cors = bucket_cors
  end

  # Sets CORS rules on a bucket.
  #
  # @param allowed_methods [Array<String>] The types of HTTP requests to allow.
  # @param allowed_origins [Array<String>] The origins to allow.
```

```
  # @returns [Boolean] True if the CORS rules were set; otherwise, false.
  def set_cors(allowed_methods, allowed_origins)
    @bucket_cors.put(
      cors_configuration: {
        cors_rules: [
          {
            allowed_methods: allowed_methods,
            allowed_origins: allowed_origins,
            allowed_headers: %w[*],
            max_age_seconds: 3600
          }
        ]
      }
    )
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't set CORS rules for #{@bucket_cors.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte PutBucketCorsa Referência AWS SDK for Ruby da API.

Adicionar uma política a um bucket

O exemplo de código a seguir mostra como adicionar uma política a um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy
```

```
  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object configured
 with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  # Sets a policy on a bucket.
  #
  def set_policy(policy)
    @bucket_policy.put(policy: policy)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't set the policy for #{@bucket_policy.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte PutBucketPolicya Referência AWS SDK for Ruby da API.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Copie um objeto.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectCopyWrapper
  attr_reader :source_object
```

```
  # @param source_object [Aws::S3::Object] An existing Amazon S3 object. This is
 used as the source object for
  #                                        copy actions.
  def initialize(source_object)
    @source_object = source_object
  end

  # Copy the source object to the specified target bucket and rename it with the
 target key.
  #
  # @param target_bucket [Aws::S3::Bucket] An existing Amazon S3 bucket where the
 object is copied.
  # @param target_object_key [String] The key to give the copy of the object.
  # @return [Aws::S3::Object, nil] The copied object when successful; otherwise,
 nil.
  def copy_object(target_bucket, target_object_key)
    @source_object.copy_to(bucket: target_bucket.name, key: target_object_key)
    target_bucket.object(target_object_key)
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't copy #{@source_object.key} to #{target_object_key}. Here's why:
 #{e.message}"
  end
end

# Example usage:
def run_demo
  source_bucket_name = "doc-example-bucket1"
  source_key = "my-source-file.txt"
  target_bucket_name = "doc-example-bucket2"
  target_key = "my-target-file.txt"

  source_bucket = Aws::S3::Bucket.new(source_bucket_name)
  wrapper = ObjectCopyWrapper.new(source_bucket.object(source_key))
  target_bucket = Aws::S3::Bucket.new(target_bucket_name)
  target_object = wrapper.copy_object(target_bucket, target_key)
  return unless target_object

  puts "Copied #{source_key} from #{source_bucket_name} to
 #{target_object.bucket_name}:#{target_object.key}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Copie um objeto e adicione criptografia no lado do servidor ao objeto de destino.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectCopyEncryptWrapper
  attr_reader :source_object

  # @param source_object [Aws::S3::Object] An existing Amazon S3 object. This is
 used as the source object for
  #                                        copy actions.
  def initialize(source_object)
    @source_object = source_object
  end

  # Copy the source object to the specified target bucket, rename it with the target
 key, and encrypt it.
  #
  # @param target_bucket [Aws::S3::Bucket] An existing Amazon S3 bucket where the
 object is copied.
  # @param target_object_key [String] The key to give the copy of the object.
  # @return [Aws::S3::Object, nil] The copied object when successful; otherwise,
 nil.
  def copy_object(target_bucket, target_object_key, encryption)
    @source_object.copy_to(bucket: target_bucket.name, key: target_object_key,
 server_side_encryption: encryption)
    target_bucket.object(target_object_key)
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't copy #{@source_object.key} to #{target_object_key}. Here's why:
 #{e.message}"
  end
end

# Example usage:
def run_demo
  source_bucket_name = "doc-example-bucket1"
  source_key = "my-source-file.txt"
  target_bucket_name = "doc-example-bucket2"
  target_key = "my-target-file.txt"
  target_encryption = "AES256"

  source_bucket = Aws::S3::Bucket.new(source_bucket_name)
  wrapper = ObjectCopyEncryptWrapper.new(source_bucket.object(source_key))
  target_bucket = Aws::S3::Bucket.new(target_bucket_name)
```

```
  target_object = wrapper.copy_object(target_bucket, target_key, target_encryption)
  return unless target_object

  puts "Copied #{source_key} from #{source_bucket_name} to
 #{target_object.bucket_name}:#{target_object.key} and "\
       "encrypted the target with #{target_object.server_side_encryption}
 encryption."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CopyObjecta Referência AWS SDK for Ruby da API.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket actions.
class BucketCreateWrapper
  attr_reader :bucket

  # @param bucket [Aws::S3::Bucket] An Amazon S3 bucket initialized with a name.
 This is a client-side object until
  #                                 create is called.
  def initialize(bucket)
    @bucket = bucket
  end

  # Creates an Amazon S3 bucket in the specified AWS Region.
  #
```

```
  # @param region [String] The Region where the bucket is created.
  # @return [Boolean] True when the bucket is created; otherwise, false.
  def create?(region)
    @bucket.create(create_bucket_configuration: { location_constraint: region })
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't create bucket. Here's why: #{e.message}"
    false
  end

  # Gets the Region where the bucket is located.
  #
  # @return [String] The location of the bucket.
  def location
    if @bucket.nil?
      "None. You must create a bucket before you can get its location!"
    else
      @bucket.client.get_bucket_location(bucket: @bucket.name).location_constraint
    end
  rescue Aws::Errors::ServiceError => e
    "Couldn't get the location of #{@bucket.name}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  region = "us-west-2"
  wrapper = BucketCreateWrapper.new(Aws::S3::Bucket.new("doc-example-bucket-
#{Random.uuid}"))
  return unless wrapper.create?(region)

  puts "Created bucket #{wrapper.bucket.name}."
  puts "Your bucket's region is: #{wrapper.location}"
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateBucketa Referência AWS SDK for Ruby da API.

Excluir regras de CORS de um bucket

O exemplo de código a seguir mostra como excluir regras de CORS de um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with an
 existing bucket.
  def initialize(bucket_cors)
    @bucket_cors = bucket_cors
  end

  # Deletes the CORS configuration of a bucket.
  #
  # @return [Boolean] True if the CORS rules were deleted; otherwise, false.
  def delete_cors
    @bucket_cors.delete
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't delete CORS rules for #{@bucket_cors.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte DeleteBucketCorsa Referência AWS SDK for Ruby da API.

Excluir uma política de um bucket

O exemplo de código a seguir mostra como excluir uma política de um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy

  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object configured
 with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  def delete_policy
    @bucket_policy.delete
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't delete the policy from #{@bucket_policy.bucket.name}. Here's why:
 #{e.message}"
    false
  end

end
```

- Para obter detalhes da API, consulte DeleteBucketPolicya Referência AWS SDK for Ruby da API.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Deletes the objects in an Amazon S3 bucket and deletes the bucket.
#
# @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
def delete_bucket(bucket)
  puts("\nDo you want to delete all of the objects as well as the bucket (y/n)? ")
  answer = gets.chomp.downcase
  if answer == "y"
    bucket.objects.batch_delete!
    bucket.delete
    puts("Emptied and deleted bucket #{bucket.name}.\n")
  end
rescue Aws::Errors::ServiceError => e
  puts("Couldn't empty and delete bucket #{bucket.name}.")
  puts("\t#{e.code}: #{e.message}")
  raise
end
```

- Para obter detalhes da API, consulte DeleteBucketa Referência AWS SDK for Ruby da API.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Deletes the objects in an Amazon S3 bucket and deletes the bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
  def delete_bucket(bucket)
    puts("\nDo you want to delete all of the objects as well as the bucket (y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      bucket.objects.batch_delete!
      bucket.delete
      puts("Emptied and deleted bucket #{bucket.name}.\n")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't empty and delete bucket #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
```

- Para obter detalhes da API, consulte DeleteObjectsa Referência AWS SDK for Ruby da API.

Determinar a existência e o tipo de conteúdo de um objeto

O exemplo de código a seguir mostra como determinar a existência e o tipo de conteúdo de um objeto em um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectExistsWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An Amazon S3 object.
  def initialize(object)
```

```
    @object = object
  end

  # Checks whether the object exists.
  #
  # @return [Boolean] True if the object exists; otherwise false.
  def exists?
    @object.exists?
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't check existence of object #{@object.bucket.name}:#{@object.key}.
 Here's why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"

  wrapper = ObjectExistsWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
  exists = wrapper.exists?

  puts "Object #{object_key} #{exists ? 'does' : 'does not'} exist."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte HeadObjecta Referência AWS SDK for Ruby da API.

Obter regras de CORS para um bucket

O exemplos de código a seguir mostra como obter regras de compartilhamento de recursos de origem cruzada (CORS) para um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket CORS configuration.
class BucketCorsWrapper
  attr_reader :bucket_cors

  # @param bucket_cors [Aws::S3::BucketCors] A bucket CORS object configured with an
 existing bucket.
  def initialize(bucket_cors)
    @bucket_cors = bucket_cors
  end

  # Gets the CORS configuration of a bucket.
  #
  # @return [Aws::S3::Type::GetBucketCorsOutput, nil] The current CORS configuration
 for the bucket.
  def get_cors
    @bucket_cors.data
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get CORS configuration for #{@bucket_cors.bucket.name}. Here's
 why: #{e.message}"
    nil
  end

end
```

- Para obter detalhes da API, consulte GetBucketCorsa Referência AWS SDK for Ruby da API.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Obtenha um objeto.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectGetWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Gets the object directly to a file.
  #
  # @param target_path [String] The path to the file where the object is downloaded.
  # @return [Aws::S3::Types::GetObjectOutput, nil] The retrieved object data if
 successful; otherwise nil.
  def get_object(target_path)
    @object.get(response_target: target_path)
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get object #{@object.key}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"
  target_path = "my-object-as-file.txt"

  wrapper = ObjectGetWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
  obj_data = wrapper.get_object(target_path)
  return unless obj_data
```

```
  puts "Object #{object_key} (#{obj_data.content_length} bytes} downloaded to
 #{target_path}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Obtenha um objeto e relate seu estado de criptografia no lado do servidor.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectGetEncryptionWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Gets the object into memory.
  #
  # @return [Aws::S3::Types::GetObjectOutput, nil] The retrieved object data if
 successful; otherwise nil.
  def get_object
    @object.get
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get object #{@object.key}. Here's why: #{e.message}"
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object.txt"

  wrapper = ObjectGetEncryptionWrapper.new(Aws::S3::Object.new(bucket_name,
 object_key))
  obj_data = wrapper.get_object
  return unless obj_data

  encryption = obj_data.server_side_encryption.nil? ? "no" :
 obj_data.server_side_encryption
```

```
  puts "Object #{object_key} uses #{encryption} encryption."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte GetObjecta Referência AWS SDK for Ruby da API.

Obter a política de um bucket

O exemplo de código a seguir mostra como obter a política de um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# Wraps an Amazon S3 bucket policy.
class BucketPolicyWrapper
  attr_reader :bucket_policy

  # @param bucket_policy [Aws::S3::BucketPolicy] A bucket policy object configured
 with an existing bucket.
  def initialize(bucket_policy)
    @bucket_policy = bucket_policy
  end

  # Gets the policy of a bucket.
  #
  # @return [Aws::S3::GetBucketPolicyOutput, nil] The current bucket policy.
  def get_policy
    policy = @bucket_policy.data.policy
    policy.respond_to?(:read) ? policy.read : policy
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't get the policy for #{@bucket_policy.bucket.name}. Here's why:
 #{e.message}"
    nil
  end
```

```
end
```

- Para obter detalhes da API, consulte GetBucketPolicya Referência AWS SDK for Ruby da API.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 resource actions.
class BucketListWrapper
  attr_reader :s3_resource

  # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
  def initialize(s3_resource)
    @s3_resource = s3_resource
  end

  # Lists buckets for the current account.
  #
  # @param count [Integer] The maximum number of buckets to list.
  def list_buckets(count)
    puts "Found these buckets:"
    @s3_resource.buckets.each do |bucket|
      puts "\t#{bucket.name}"
      count -= 1
      break if count.zero?
    end
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't list buckets. Here's why: #{e.message}"
    false
```

```
  end
end

# Example usage:
def run_demo
  wrapper = BucketListWrapper.new(Aws::S3::Resource.new)
  wrapper.list_buckets(25)
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListBucketsa Referência AWS SDK for Ruby da API.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"

# Wraps Amazon S3 bucket actions.
class BucketListObjectsWrapper
  attr_reader :bucket

  # @param bucket [Aws::S3::Bucket] An existing Amazon S3 bucket.
  def initialize(bucket)
    @bucket = bucket
  end

  # Lists object in a bucket.
  #
  # @param max_objects [Integer] The maximum number of objects to list.
  # @return [Integer] The number of objects listed.
  def list_objects(max_objects)
```

```
    count = 0
    puts "The objects in #{@bucket.name} are:"
    @bucket.objects.each do |obj|
      puts "\t#{obj.key}"
      count += 1
      break if count == max_objects
    end
    count
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't list objects in bucket #{bucket.name}. Here's why: #{e.message}"
    0
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"

  wrapper = BucketListObjectsWrapper.new(Aws::S3::Bucket.new(bucket_name))
  count = wrapper.list_objects(25)
  puts "Listed #{count} objects."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ListObjectsV2 na Referência AWS SDK for Ruby da API.

Definir a configuração de site de um bucket

O exemplo de código a seguir mostra como definir a configuração de site de um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"
```

```
# Wraps Amazon S3 bucket website actions.
class BucketWebsiteWrapper
  attr_reader :bucket_website

  # @param bucket_website [Aws::S3::BucketWebsite] A bucket website object
 configured with an existing bucket.
  def initialize(bucket_website)
    @bucket_website = bucket_website
  end

  # Sets a bucket as a static website.
  #
  # @param index_document [String] The name of the index document for the website.
  # @param error_document [String] The name of the error document to show for 4XX
 errors.
  # @return [Boolean] True when the bucket is configured as a website; otherwise,
 false.
  def set_website(index_document, error_document)
    @bucket_website.put(
      website_configuration: {
        index_document: { suffix: index_document },
        error_document: { key: error_document }
      }
    )
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't configure #{@bucket_website.bucket.name} as a website. Here's
 why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  index_document = "index.html"
  error_document = "404.html"

  wrapper = BucketWebsiteWrapper.new(Aws::S3::BucketWebsite.new(bucket_name))
  return unless wrapper.set_website(index_document, error_document)

  puts "Successfully configured bucket #{bucket_name} as a static website."
end
```

```
run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte PutBucketWebsitea Referência AWS SDK for Ruby da API.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um arquivo usando um carregador gerenciado (Object.upload_file).

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectUploadFileWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  # Uploads a file to an Amazon S3 object by using a managed uploader.
  #
  # @param file_path [String] The path to the file to upload.
  # @return [Boolean] True when the file is uploaded; otherwise false.
  def upload_file(file_path)
    @object.upload_file(file_path)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't upload file #{file_path} to #{@object.key}. Here's why:
 #{e.message}"
    false
```

```
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-uploaded-file"
  file_path = "object_upload_file.rb"

  wrapper = ObjectUploadFileWrapper.new(Aws::S3::Object.new(bucket_name,
 object_key))
  return unless wrapper.upload_file(file_path)

  puts "File #{file_path} successfully uploaded to #{bucket_name}:#{object_key}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Carregue um arquivo usando Object.put.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectPutWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  def put_object(source_file_path)
    File.open(source_file_path, "rb") do |file|
      @object.put(body: file)
    end
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't put #{source_file_path} to #{object.key}. Here's why:
 #{e.message}"
    false
  end
end
```

```
# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-object-key"
  file_path = "my-local-file.txt"

  wrapper = ObjectPutWrapper.new(Aws::S3::Object.new(bucket_name, object_key))
  success = wrapper.put_object(file_path)
  return unless success

  puts "Put file #{file_path} into #{object_key} in #{bucket_name}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

Carregue um arquivo usando Object.put e adicione criptografia no lado do servidor.

```
require "aws-sdk-s3"

# Wraps Amazon S3 object actions.
class ObjectPutSseWrapper
  attr_reader :object

  # @param object [Aws::S3::Object] An existing Amazon S3 object.
  def initialize(object)
    @object = object
  end

  def put_object_encrypted(object_content, encryption)
    @object.put(body: object_content, server_side_encryption: encryption)
    true
  rescue Aws::Errors::ServiceError => e
    puts "Couldn't put your content to #{object.key}. Here's why: #{e.message}"
    false
  end
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-encrypted-content"
```

```
  object_content = "This is my super-secret content."
  encryption = "AES256"

  wrapper = ObjectPutSseWrapper.new(Aws::S3::Object.new(bucket_name,
 object_content))
  return unless wrapper.put_object_encrypted(object_content, encryption)

  puts "Put your content into #{bucket_name}:#{object_key} and encrypted it with
 #{encryption}."
end

run_demo if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte PutObjecta Referência AWS SDK for Ruby da API.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar um URL pré-assinado para o Amazon S3 e carregar um objeto.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-s3"
require "net/http"

# Creates a presigned URL that can be used to upload content to an object.
#
# @param bucket [Aws::S3::Bucket] An existing Amazon S3 bucket.
# @param object_key [String] The key to give the uploaded object.
# @return [URI, nil] The parsed URI if successful; otherwise nil.
def get_presigned_url(bucket, object_key)
  url = bucket.object(object_key).presigned_url(:put)
  puts "Created presigned URL: #{url}"
```

```
  URI(url)
rescue Aws::Errors::ServiceError => e
  puts "Couldn't create presigned URL for #{bucket.name}:#{object_key}. Here's why:
 #{e.message}"
end

# Example usage:
def run_demo
  bucket_name = "doc-example-bucket"
  object_key = "my-file.txt"
  object_content = "This is the content of my-file.txt."

  bucket = Aws::S3::Bucket.new(bucket_name)
  presigned_url = get_presigned_url(bucket, object_key)
  return unless presigned_url

  response = Net::HTTP.start(presigned_url.host) do |http|
    http.send_request("PUT", presigned_url.request_uri, object_content,
 "content_type" => "")
  end

  case response
  when Net::HTTPSuccess
    puts "Content uploaded!"
  else
    puts response.value
  end
end

run_demo if $PROGRAM_NAME == __FILE__
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-s3"

# Wraps the getting started scenario actions.
class ScenarioGettingStarted
  attr_reader :s3_resource

  # @param s3_resource [Aws::S3::Resource] An Amazon S3 resource.
  def initialize(s3_resource)
    @s3_resource = s3_resource
  end

  # Creates a bucket with a random name in the currently configured account and
  # AWS Region.
  #
  # @return [Aws::S3::Bucket] The newly created bucket.
  def create_bucket
    bucket = @s3_resource.create_bucket(
      bucket: "doc-example-bucket-#{Random.uuid}",
      create_bucket_configuration: {
        location_constraint: "us-east-1" # Note: only certain regions permitted
      }
    )
    puts("Created demo bucket named #{bucket.name}.")
  rescue Aws::Errors::ServiceError => e
    puts("Tried and failed to create demo bucket.")
    puts("\t#{e.code}: #{e.message}")
    puts("\nCan't continue the demo without a bucket!")
    raise
  else
    bucket
  end

  # Requests a file name from the user.
  #
```

```
  # @return The name of the file.
  def create_file
    File.open("demo.txt", w) { |f| f.write("This is a demo file.") }
  end

  # Uploads a file to an Amazon S3 bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket object representing the upload
destination
  # @return [Aws::S3::Object] The Amazon S3 object that contains the uploaded file.
  def upload_file(bucket)
    File.open("demo.txt", "w+") { |f| f.write("This is a demo file.") }
    s3_object = bucket.object(File.basename("demo.txt"))
    s3_object.upload_file("demo.txt")
    puts("Uploaded file demo.txt into bucket #{bucket.name} with key
#{s3_object.key}.")
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't upload file demo.txt to #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    s3_object
  end

  # Downloads an Amazon S3 object to a file.
  #
  # @param s3_object [Aws::S3::Object] The object to download.
  def download_file(s3_object)
    puts("\nDo you want to download #{s3_object.key} to a local file (y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      puts("Enter a name for the downloaded file: ")
      file_name = gets.chomp
      s3_object.download_file(file_name)
      puts("Object #{s3_object.key} successfully downloaded to #{file_name}.")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't download #{s3_object.key}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end

  # Copies an Amazon S3 object to a subfolder within the same bucket.
  #
```

```
  # @param source_object [Aws::S3::Object] The source object to copy.
  # @return [Aws::S3::Object, nil] The destination object.
  def copy_object(source_object)
    dest_object = nil
    puts("\nDo you want to copy #{source_object.key} to a subfolder in your bucket
(y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      dest_object = source_object.bucket.object("demo-folder/#{source_object.key}")
      dest_object.copy_from(source_object)
      puts("Copied #{source_object.key} to #{dest_object.key}.")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't copy #{source_object.key}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  else
    dest_object
  end

  # Lists the objects in an Amazon S3 bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket to query.
  def list_objects(bucket)
    puts("\nYour bucket contains the following objects:")
    bucket.objects.each do |obj|
      puts("\t#{obj.key}")
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't list the objects in bucket #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end

  # Deletes the objects in an Amazon S3 bucket and deletes the bucket.
  #
  # @param bucket [Aws::S3::Bucket] The bucket to empty and delete.
  def delete_bucket(bucket)
    puts("\nDo you want to delete all of the objects as well as the bucket (y/n)? ")
    answer = gets.chomp.downcase
    if answer == "y"
      bucket.objects.batch_delete!
      bucket.delete
      puts("Emptied and deleted bucket #{bucket.name}.\n")
```

```
    end
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't empty and delete bucket #{bucket.name}.")
    puts("\t#{e.code}: #{e.message}")
    raise
  end
end

# Runs the Amazon S3 getting started scenario.
def run_scenario(scenario)
  puts("-" * 88)
  puts("Welcome to the Amazon S3 getting started demo!")
  puts("-" * 88)

  bucket = scenario.create_bucket
  s3_object = scenario.upload_file(bucket)
  scenario.download_file(s3_object)
  scenario.copy_object(s3_object)
  scenario.list_objects(bucket)
  scenario.delete_bucket(bucket)

  puts("Thanks for watching!")
  puts("-" * 88)
rescue Aws::Errors::ServiceError
  puts("Something went wrong with the demo!")
end

run_scenario(ScenarioGettingStarted.new(Aws::S3::Resource.new)) if $PROGRAM_NAME ==
 __FILE__
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK for Ruby.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Exemplos do Amazon SES usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter o status de uma identidade

O exemplo de código a seguir mostra como excluir o status de uma identidade do Amazon SES.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Create client in us-west-2 region
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
client = Aws::SES::Client.new(region: "us-west-2")

# Get up to 1000 identities
ids = client.list_identities({
```

```
  identity_type: "EmailAddress"
})

ids.identities.each do |email|
  attrs = client.get_identity_verification_attributes({
    identities: [email]
  })

  status = attrs.verification_attributes[email].verification_status

  # Display email addresses that have been verified
  if status == "Success"
    puts email
  end
end
```

- Para obter detalhes da API, consulte GetIdentityVerificationAttributesa Referência AWS SDK for Ruby da API.

Listar identidades

O exemplo de código a seguir mostra como listar identidades do Amazon SES.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Create client in us-west-2 region
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
client = Aws::SES::Client.new(region: "us-west-2")

# Get up to 1000 identities
ids = client.list_identities({
  identity_type: "EmailAddress"
```

```
})

ids.identities.each do |email|
  attrs = client.get_identity_verification_attributes({
    identities: [email]
  })

  status = attrs.verification_attributes[email].verification_status

  # Display email addresses that have been verified
  if status == "Success"
    puts email
  end
end
```

- Para obter detalhes da API, consulte ListIdentitiesa Referência AWS SDK for Ruby da API.

Enviar e-mail

O exemplo de código a seguir mostra como enviar e-mails com o Amazon SES.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Replace sender@example.com with your "From" address.
# This address must be verified with Amazon SES.
sender = "sender@example.com"

# Replace recipient@example.com with a "To" address. If your account
# is still in the sandbox, this address must be verified.
recipient = "recipient@example.com"

# Specify a configuration set. To use a configuration
```

```
# set, uncomment the next line and line 74.
#   configsetname = "ConfigSet"

# The subject line for the email.
subject = "Amazon SES test (AWS SDK for Ruby)"

# The HTML body of the email.
htmlbody =
  "<h1>Amazon SES test (AWS SDK for Ruby)</h1>"\
  '<p>This email was sent with <a href="https://aws.amazon.com/ses/">'\
  'Amazon SES</a> using the <a href="https://aws.amazon.com/sdk-for-ruby/">'\
  "AWS SDK for Ruby</a>."

# The email body for recipients with non-HTML email clients.
textbody = "This email was sent with Amazon SES using the AWS SDK for Ruby."

# Specify the text encoding scheme.
encoding = "UTF-8"

# Create a new SES client in the us-west-2 region.
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
ses = Aws::SES::Client.new(region: "us-west-2")

# Try to send the email.
begin
  # Provide the contents of the email.
  ses.send_email(
    destination: {
      to_addresses: [
        recipient
      ]
    },
    message: {
      body: {
        html: {
          charset: encoding,
          data: htmlbody
        },
        text: {
          charset: encoding,
          data: textbody
        }
      },
      subject: {
```

```
        charset: encoding,
        data: subject
      }
    },
    source: sender,
    # Uncomment the following line to use a configuration set.
    # configuration_set_name: configsetname,
    )

  puts "Email sent to " + recipient

# If something goes wrong, display an error message.
rescue Aws::SES::Errors::ServiceError => error
  puts "Email not sent. Error message: #{error}"
end
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Ruby da API.

Verificar uma identidade de e-mail

O exemplo de código a seguir mostra como verificar uma identidade de e-mail com o Amazon SES.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-ses"  # v2: require 'aws-sdk'

# Replace recipient@example.com with a "To" address.
recipient = "recipient@example.com"

# Create a new SES resource in the us-west-2 region.
# Replace us-west-2 with the AWS Region you're using for Amazon SES.
ses = Aws::SES::Client.new(region: "us-west-2")
```

```
# Try to verify email address.
begin
  ses.verify_email_identity({
    email_address: recipient
  })

  puts "Email sent to " + recipient

# If something goes wrong, display an error message.
rescue Aws::SES::Errors::ServiceError => error
  puts "Email not sent. Error message: #{error}"
end
```

- Para obter detalhes da API, consulte VerifyEmailIdentitya Referência AWS SDK for Ruby da API.

Exemplos da API v2 do Amazon SES usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com a API v2 do Amazon SES.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar um e-mail

O exemplo de código a seguir mostra como enviar um e-mail com a API v2 do Amazon SES.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sesv2"
require_relative "config" # Recipient and sender email addresses.

# Set up the SESv2 client.
client = Aws::SESV2::Client.new(region: AWS_REGION)

def send_email(client, sender_email, recipient_email)
  response = client.send_email(
    {
       from_email_address: sender_email,
       destination: {
         to_addresses: [recipient_email]
       },
       content: {
         simple: {
           subject: {
             data: "Test email subject"
           },
           body: {
             text: {
               data: "Test email body"
             }
           }
         }
       }
    }
  )
  puts "Email sent from #{SENDER_EMAIL} to #{RECIPIENT_EMAIL} with message ID:
 #{response.message_id}"
end

send_email(client, SENDER_EMAIL, RECIPIENT_EMAIL)
```

- Para obter detalhes da API, consulte SendEmaila Referência AWS SDK for Ruby da API.

Exemplos do Amazon SNS usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# This class demonstrates how to create an Amazon Simple Notification Service (SNS)
 topic.
class SNSTopicCreator
```

```
  # Initializes an SNS client.
  #
  # Utilizes the default AWS configuration for region and credentials.
  def initialize
    @sns_client = Aws::SNS::Client.new
  end

  # Attempts to create an SNS topic with the specified name.
  #
  # @param topic_name [String] The name of the SNS topic to create.
  # @return [Boolean] true if the topic was successfully created, false otherwise.
  def create_topic(topic_name)
    @sns_client.create_topic(name: topic_name)
    puts "The topic '#{topic_name}' was successfully created."
    true
  rescue Aws::SNS::Errors::ServiceError => e
    # Handles SNS service errors gracefully.
    puts "Error while creating the topic named '#{topic_name}': #{e.message}"
    false
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_name = "YourTopicName" # Replace with your topic name
  sns_topic_creator = SNSTopicCreator.new

  puts "Creating the topic '#{topic_name}'..."
  unless sns_topic_creator.create_topic(topic_name)
    puts "The topic was not created. Stopping program."
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte CreateTopica Referência AWS SDK for Ruby da API.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# This class demonstrates how to list subscriptions to an Amazon Simple Notification
 Service (SNS) topic
class SnsSubscriptionLister
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Lists subscriptions for a given SNS topic
  # @param topic_arn [String] The ARN of the SNS topic
  # @return [Types::ListSubscriptionsResponse] subscriptions: The response object
  def list_subscriptions(topic_arn)
    @logger.info("Listing subscriptions for topic: #{topic_arn}")
    subscriptions = @sns_client.list_subscriptions_by_topic(topic_arn: topic_arn)
    subscriptions.subscriptions.each do |subscription|
      @logger.info("Subscription endpoint: #{subscription.endpoint}")
    end
    subscriptions
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error listing subscriptions: #{e.message}")
    raise
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  sns_client = Aws::SNS::Client.new
  topic_arn = "SNS_TOPIC_ARN" # Replace with your SNS topic ARN
  lister = SnsSubscriptionLister.new(sns_client)

  begin
    lister.list_subscriptions(topic_arn)
  rescue StandardError => e
    puts "Failed to list subscriptions: #{e.message}"
```

```
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte ListSubscriptionsa Referência AWS SDK for Ruby da API.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-sns"  # v2: require 'aws-sdk'

def list_topics?(sns_client)
  sns_client.topics.each do |topic|
    puts topic.arn
rescue StandardError => e
  puts "Error while listing the topics: #{e.message}"
  end
end

def run_me

  region = "REGION"
  sns_client = Aws::SNS::Resource.new(region: region)

  puts "Listing the topics."

  if list_topics?(sns_client)
  else
    puts "The bucket was not created. Stopping program."
```

```
    exit 1
  end
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte ListTopicsa Referência AWS SDK for Ruby da API.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# Service class for sending messages using Amazon Simple Notification Service (SNS)
class SnsMessageSender
  # Initializes the SnsMessageSender with an SNS client
  #
  # @param sns_client [Aws::SNS::Client] The SNS client
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Sends a message to a specified SNS topic
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param message [String] The message to send
  # @return [Boolean] true if message was successfully sent, false otherwise
  def send_message(topic_arn, message)
    @sns_client.publish(topic_arn: topic_arn, message: message)
```

```
    @logger.info("Message sent successfully to #{topic_arn}.")
    true
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error while sending the message: #{e.message}")
    false
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_arn = "SNS_TOPIC_ARN" # Should be replaced with a real topic ARN
  message = "MESSAGE"         # Should be replaced with the actual message content

  sns_client = Aws::SNS::Client.new
  message_sender = SnsMessageSender.new(sns_client)

  @logger.info("Sending message.")
  unless message_sender.send_message(topic_arn, message)
    @logger.error("Message sending failed. Stopping program.")
    exit 1
  end
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Ruby.

Definir atributos de tópicos

O exemplo de código a seguir mostra como definir atributos para um tópico do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
# Service class to enable an SNS resource with a specified policy
class SnsResourceEnabler
```

```
# Initializes the SnsResourceEnabler with an SNS resource client
#
# @param sns_resource [Aws::SNS::Resource] The SNS resource client
def initialize(sns_resource)
  @sns_resource = sns_resource
  @logger = Logger.new($stdout)
end

# Sets a policy on a specified SNS topic
#
# @param topic_arn [String] The ARN of the SNS topic
# @param resource_arn [String] The ARN of the resource to include in the policy
# @param policy_name [String] The name of the policy attribute to set
def enable_resource(topic_arn, resource_arn, policy_name)
  policy = generate_policy(topic_arn, resource_arn)
  topic = @sns_resource.topic(topic_arn)

  topic.set_attributes({
                        attribute_name: policy_name,
                        attribute_value: policy
                      })
  @logger.info("Policy #{policy_name} set successfully for topic #{topic_arn}.")
rescue Aws::SNS::Errors::ServiceError => e
  @logger.error("Failed to set policy: #{e.message}")
end

private

# Generates a policy string with dynamic resource ARNs
#
# @param topic_arn [String] The ARN of the SNS topic
# @param resource_arn [String] The ARN of the resource
# @return [String] The policy as a JSON string
def generate_policy(topic_arn, resource_arn)
  {
    Version: "2008-10-17",
    Id: "__default_policy_ID",
    Statement: [{
                  Sid: "__default_statement_ID",
                  Effect: "Allow",
                  Principal: { "AWS": "*" },
                  Action: ["SNS:Publish"],
                  Resource: topic_arn,
                  Condition: {
```

```
                      ArnEquals: {
                        "AWS:SourceArn": resource_arn
                      }
                    }
                  }]
    }.to_json
  end
end

# Example usage:
if $PROGRAM_NAME == __FILE__
  topic_arn = "MY_TOPIC_ARN"     # Should be replaced with a real topic ARN
  resource_arn = "MY_RESOURCE_ARN" # Should be replaced with a real resource ARN
  policy_name = "POLICY_NAME"    # Typically, this is "Policy"

  sns_resource = Aws::SNS::Resource.new
  enabler = SnsResourceEnabler.new(sns_resource)

  enabler.enable_resource(topic_arn, resource_arn, policy_name)
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte SetTopicAttributesa Referência AWS SDK for Ruby da API.

Inscrever um endereço de e-mail em um tópico

O exemplo de código a seguir mostra como assinar um endereço de e-mail em um tópico do Amazon SNS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
require "aws-sdk-sns"
require "logger"
```

```
# Represents a service for creating subscriptions in Amazon Simple Notification
 Service (SNS)
class SubscriptionService
  # Initializes the SubscriptionService with an SNS client
  #
  # @param sns_client [Aws::SNS::Client] The SNS client
  def initialize(sns_client)
    @sns_client = sns_client
    @logger = Logger.new($stdout)
  end

  # Attempts to create a subscription to a topic
  #
  # @param topic_arn [String] The ARN of the SNS topic
  # @param protocol [String] The subscription protocol (e.g., email)
  # @param endpoint [String] The endpoint that receives the notifications (email
 address)
  # @return [Boolean] true if subscription was successfully created, false otherwise
  def create_subscription(topic_arn, protocol, endpoint)
    @sns_client.subscribe(topic_arn: topic_arn, protocol: protocol, endpoint:
 endpoint)
    @logger.info("Subscription created successfully.")
    true
  rescue Aws::SNS::Errors::ServiceError => e
    @logger.error("Error while creating the subscription: #{e.message}")
    false
  end
end

# Main execution if the script is run directly
if $PROGRAM_NAME == __FILE__
  protocol = "email"
  endpoint = "EMAIL_ADDRESS" # Should be replaced with a real email address
  topic_arn = "TOPIC_ARN"    # Should be replaced with a real topic ARN

  sns_client = Aws::SNS::Client.new
  subscription_service = SubscriptionService.new(sns_client)

  @logger.info("Creating the subscription.")
  unless subscription_service.create_subscription(topic_arn, protocol, endpoint)
    @logger.error("Subscription creation failed. Stopping program.")
    exit 1
  end
```

```
end
```

- Para obter mais informações, consulte o Guia do desenvolvedor do AWS SDK for Ruby.
- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Ruby.

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SNS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].map { |record| process_message(record) }
end

def process_message(record)
  message = record['Sns']['Message']
  puts("Processing message: #{message}")
rescue StandardError => e
  puts("Error processing message: #{e}")
  raise
end
```

Exemplos do Amazon SQS usando o SDK para Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Alterar a visibilidade do tempo limite da mensagem

O exemplo de código a seguir mostra como alterar a visibilidade do tempo limite da mensagem do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"  # v2: require 'aws-sdk'
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
sqs = Aws::SQS::Client.new(region: "us-west-2")
```

```
begin
  queue_name = "my-queue"
  queue_url = sqs.get_queue_url(queue_name: queue_name).queue_url

  receive_message_result_before = sqs.receive_message({
    queue_url: queue_url,
    max_number_of_messages: 10 # Receive up to 10 messages, if there are that many.
  })

  puts "Before attempting to change message visibility timeout: received
 #{receive_message_result_before.messages.count} message(s)."

  receive_message_result_before.messages.each do |message|
    sqs.change_message_visibility({
      queue_url: queue_url,
      receipt_handle: message.receipt_handle,
      visibility_timeout: 30 # This message will not be visible for 30 seconds after
 first receipt.
    })
  end

  # Try to retrieve the original messages after setting their visibility timeout.
  receive_message_result_after = sqs.receive_message({
    queue_url: queue_url,
    max_number_of_messages: 10
  })

  puts "\nAfter attempting to change message visibility timeout: received
 #{receive_message_result_after.messages.count} message(s)."

rescue Aws::SQS::Errors::NonExistentQueue
  puts "Cannot receive messages for a queue named '#{receive_queue_name}', as it
 does not exist."
end
```

- Para obter detalhes da API, consulte ChangeMessageVisibilitya Referência AWS SDK for Ruby da API.

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
# This code example demonstrates how to create a queue in Amazon Simple Queue
 Service (Amazon SQS).

require "aws-sdk-sqs"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_name [String] The name of the queue.
# @return [Boolean] true if the queue was created; otherwise, false.
# @example
#   exit 1 unless queue_created?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'my-queue'
#   )
def queue_created?(sqs_client, queue_name)
  sqs_client.create_queue(queue_name: queue_name)
  true
rescue StandardError => e
  puts "Error creating queue: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Creating the queue named '#{queue_name}'..."

  if queue_created?(sqs_client, queue_name)
    puts "Queue created."
  else
    puts "Queue not created."
```

```
  end
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte CreateQueuea Referência AWS SDK for Ruby da API.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"  # v2: require 'aws-sdk'
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
sqs = Aws::SQS::Client.new(region: "us-west-2")

sqs.delete_queue(queue_url: URL)
```

- Para obter detalhes da API, consulte DeleteQueuea Referência AWS SDK for Ruby da API.

Listar filas

O exemplo de código a seguir mostra como listar filas do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @example
#   list_queue_urls(Aws::SQS::Client.new(region: 'us-west-2'))
def list_queue_urls(sqs_client)
  queues = sqs_client.list_queues

  queues.queue_urls.each do |url|
    puts url
  end
rescue StandardError => e
  puts "Error listing queue URLs: #{e.message}"
end

# Lists the attributes of a queue in Amazon Simple Queue Service (Amazon SQS).
#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @example
#   list_queue_attributes(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
#   )
def list_queue_attributes(sqs_client, queue_url)
  attributes = sqs_client.get_queue_attributes(
    queue_url: queue_url,
    attribute_names: ["All"]
  )

  attributes.attributes.each do |key, value|
    puts "#{key}: #{value}"
  end

rescue StandardError => e
  puts "Error getting queue attributes: #{e.message}"
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
```

```
  region = "us-west-2"
  queue_name = "my-queue"

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Listing available queue URLs..."
  list_queue_urls(sqs_client)

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  puts "\nGetting information about queue '#{queue_name}'..."
  list_queue_attributes(sqs_client, queue_url)
end
```

- Para obter detalhes da API, consulte ListQueuesa Referência AWS SDK for Ruby da API.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# Receives messages in a queue in Amazon Simple Queue Service (Amazon SQS).
#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
```

```
# @param queue_url [String] The URL of the queue.
# @param max_number_of_messages [Integer] The maximum number of messages
#   to receive. This number must be 10 or less. The default is 10.
# @example
#   receive_messages(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     10
#   )
def receive_messages(sqs_client, queue_url, max_number_of_messages = 10)

  if max_number_of_messages > 10
    puts "Maximum number of messages to receive must be 10 or less. " \
      "Stopping program."
    return
  end

  response = sqs_client.receive_message(
    queue_url: queue_url,
    max_number_of_messages: max_number_of_messages
  )

  if response.messages.count.zero?
    puts "No messages to receive, or all messages have already " \
      "been previously received."
    return
  end

  response.messages.each do |message|
    puts "-" * 20
    puts "Message body: #{message.body}"
    puts "Message ID:   #{message.message_id}"
  end

rescue StandardError => e
  puts "Error receiving messages: #{e.message}"
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  max_number_of_messages = 10
```

```
  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Receiving messages from queue '#{queue_name}'..."

  receive_messages(sqs_client, queue_url, max_number_of_messages)
end

# Example usage:
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte ReceiveMessagea Referência AWS SDK for Ruby da API.

Para enviar mensagens em lote a uma fila.

O exemplo de código a seguir mostra como enviar um lote de mensagens para uma fila do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

#
# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @param entries [Hash] The contents of the messages to be sent,
```

```
#   in the correct format.
# @return [Boolean] true if the messages were sent; otherwise, false.
# @example
#   exit 1 unless messages_sent?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     [
#       {
#         id: 'Message1',
#         message_body: 'This is the first message.'
#       },
#       {
#         id: 'Message2',
#         message_body: 'This is the second message.'
#       }
#     ]
#   )
def messages_sent?(sqs_client, queue_url, entries)
  sqs_client.send_message_batch(
    queue_url: queue_url,
    entries: entries
  )
  true
rescue StandardError => e
  puts "Error sending messages: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  entries = [
    {
      id: "Message1",
      message_body: "This is the first message."
    },
    {
      id: "Message2",
      message_body: "This is the second message."
    }
  ]
```

```
  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Sending messages to the queue named '#{queue_name}'..."

  if messages_sent?(sqs_client, queue_url, entries)
    puts "Messages sent."
  else
    puts "Messages not sent."
  end
end
```

- Para obter detalhes da API, consulte SendMessageBatcha Referência AWS SDK for Ruby da API.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
require "aws-sdk-sqs"
require "aws-sdk-sts"

# @param sqs_client [Aws::SQS::Client] An initialized Amazon SQS client.
# @param queue_url [String] The URL of the queue.
# @param message_body [String] The contents of the message to be sent.
```

```
# @return [Boolean] true if the message was sent; otherwise, false.
# @example
#   exit 1 unless message_sent?(
#     Aws::SQS::Client.new(region: 'us-west-2'),
#     'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue',
#     'This is my message.'
#   )
def message_sent?(sqs_client, queue_url, message_body)
  sqs_client.send_message(
    queue_url: queue_url,
    message_body: message_body
  )
  true
rescue StandardError => e
  puts "Error sending message: #{e.message}"
  false
end

# Full example call:
# Replace us-west-2 with the AWS Region you're using for Amazon SQS.
def run_me
  region = "us-west-2"
  queue_name = "my-queue"
  message_body = "This is my message."

  sts_client = Aws::STS::Client.new(region: region)

  # For example:
  # 'https://sqs.us-west-2.amazonaws.com/111111111111/my-queue'
  queue_url = "https://sqs." + region + ".amazonaws.com/" +
    sts_client.get_caller_identity.account + "/" + queue_name

  sqs_client = Aws::SQS::Client.new(region: region)

  puts "Sending a message to the queue named '#{queue_name}'..."

  if message_sent?(sqs_client, queue_url, message_body)
    puts "Message sent."
  else
    puts "Message not sent."
  end
end

# Example usage:
```

```
run_me if $PROGRAM_NAME == __FILE__
```

- Para obter detalhes da API, consulte SendMessagea Referência AWS SDK for Ruby da API.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do SQS com o Lambda usando Ruby.

```
def lambda_handler(event:, context:)
  event['Records'].each do |message|
    process_message(message)
  end
  puts "done"
end

def process_message(message)
  begin
    puts "Processed message #{message['body']}"
    # TODO: Do interesting work based on the new message
  rescue StandardError => err
    puts "An error occurred"
    raise err
  end
end
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Ruby.

```
require 'json'

def lambda_handler(event:, context:)
  if event
    batch_item_failures = []
    sqs_batch_response = {}

    event["Records"].each do |record|
      begin
        # process message
      rescue StandardError => e
        batch_item_failures << {"itemIdentifier" => record['messageId']}
      end
    end

    sqs_batch_response["batchItemFailures"] = batch_item_failures
    return sqs_batch_response
  end
end
```

Exemplos de AWS STS usando o SDK para Ruby

Os exemplo de códigos a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Creates an AWS Security Token Service (AWS STS) client with specified
credentials.
 # This is separated into a factory function so that it can be mocked for unit
testing.
 #
 # @param key_id [String] The ID of the access key used by the STS client.
 # @param key_secret [String] The secret part of the access key used by the STS
client.
 def create_sts_client(key_id, key_secret)
   Aws::STS::Client.new(access_key_id: key_id, secret_access_key: key_secret)
 end

 # Gets temporary credentials that can be used to assume a role.
```

```
 #
 # @param role_arn [String] The ARN of the role that is assumed when these
credentials
 #                          are used.
 # @param sts_client [AWS::STS::Client] An AWS STS client.
 # @return [Aws::AssumeRoleCredentials] The credentials that can be used to assume
the role.
 def assume_role(role_arn, sts_client)
   credentials = Aws::AssumeRoleCredentials.new(
     client: sts_client,
     role_arn: role_arn,
     role_session_name: "create-use-assume-role-scenario"
   )
   @logger.info("Assumed role '#{role_arn}', got temporary credentials.")
   credentials
 end
```

- Para obter detalhes da API, consulte AssumeRolea Referência AWS SDK for Ruby da API.

WorkDocs Exemplos da Amazon usando o SDK for Ruby

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK for Ruby com a Amazon WorkDocs.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descrever o conteúdo da pasta raiz

O exemplo de código a seguir mostra como descrever o conteúdo da pasta WorkDocs raiz da Amazon.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
 # Retrieves the root folder for a user by email
 # @param users [Array<Types::User>] A list of users selected from API response
 # @param user_email [String] The email of the user.
 def get_user_folder(users, user_email)
   user = users.find { |user| user.email_address == user_email }
   if user
     user.root_folder_id
   else
     @logger.error "Could not get root folder for user with email address
#{user_email}"
     exit(1)
   end
 end

 # Describes the contents of a folder
 # @param [String] folder_id - The Id of the folder to describe.
 def describe_folder_contents(folder_id)
   resp = @client.describe_folder_contents({
                                             folder_id: folder_id, # required
                                             sort: "NAME", # accepts DATE, NAME
                                             order: "ASCENDING", # accepts
ASCENDING, DESCENDING
                                           })
   resp.documents.each do |doc|
     md = doc.latest_version_metadata
     @logger.info "Name:          #{md.name}"
     @logger.info "Size (bytes):  #{md.size}"
     @logger.info "Last modified: #{doc.modified_timestamp}"
```

```
      @logger.info "Doc ID:        #{doc.id}"
      @logger.info "Version ID:    #{md.id}"
      @logger.info ""
    end
  rescue Aws::WorkDocs::Errors::ServiceError => e
    @logger.error "Error listing folder contents: #{e.message}"
    exit(1)
  end
```

- Para obter detalhes da API, consulte DescribeRootFoldersa Referência AWS SDK for Ruby da API.

Descreva os usuários

O exemplo de código a seguir mostra como descrever WorkDocs os usuários da Amazon.

SDK for Ruby

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  # Describes users within an organization
  # @param [String] org_id: The ID of the org.
  def describe_users(org_id)
    resp = @client.describe_users({
                                    organization_id: org_id,
                                    include: "ALL", # accepts ALL, ACTIVE_PENDING
                                    order: "ASCENDING", # accepts ASCENDING,
DESCENDING
                                    sort: "USER_NAME", # accepts USER_NAME,
FULL_NAME, STORAGE_LIMIT, USER_STATUS, STORAGE_USED
                                  })
    resp.users.each do |user|
      @logger.info "First name:  #{user.given_name}"
      @logger.info "Last name:   #{user.surname}"
      @logger.info "Email:       #{user.email_address}"
      @logger.info "Root folder: #{user.root_folder_id}"
```

```
    @logger.info ""
  end
  resp.users
rescue Aws::WorkDocs::Errors::ServiceError => e
  @logger.error "AWS WorkDocs Service Error: #{e.message}"
  exit(1)
end
```

- Para obter detalhes da API, consulte DescribeUsersa Referência AWS SDK for Ruby da API.

Exemplos entre serviços usando o SDK para Ruby

Os aplicativos de exemplo a seguir usam o AWS SDK for Ruby para trabalhar conjuntamente múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar você a começar a criar aplicativos.

Exemplos

- Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

Criar uma aplicação que analise o feedback dos clientes e sintetize o áudio

SDK for Ruby

Esta aplicação de exemplo analisa e armazena cartões de feedback de clientes. Especificamente, ela atende à necessidade de um hotel fictício na cidade de Nova York. O hotel recebe feedback dos hóspedes em vários idiomas na forma de cartões de comentários físicos. Esse feedback é enviado para a aplicação por meio de um cliente web. Depois de fazer upload da imagem de um cartão de comentário, ocorrem as seguintes etapas:

- O texto é extraído da imagem usando o Amazon Textract.
- O Amazon Comprehend determina o sentimento do texto extraído e o idioma.
- O texto extraído é traduzido para o inglês com o Amazon Translate.
- O Amazon Polly sintetiza um arquivo de áudio do texto extraído.

A aplicação completa pode ser implantada com o AWS CDK. Para obter o código-fonte e as instruções de implantação, consulte o projeto em GitHub.

Serviços utilizados neste exemplo

- Amazon Comprehend
- Lambda
- Amazon Polly
- Amazon Textract
- Amazon Translate

Exemplos de código para SDK para Rust

Os exemplos de código a seguir mostram como usar o AWS SDK para Rust com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para Rust : Saiba mais sobre como usar o Rust com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Rust
- Exemplos de serviços cruzados usando SDK para Rust

Ações e cenários usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos de API Gateway usando SDK para Rust
- Exemplos de Gerenciamento de API de API Gateway usando SDK para Rust
- Exemplos do Application Auto Scaling usando SDK para Rust
- Exemplos de Aurora usando o SDK para Rust
- Exemplos de Auto Scaling usando o SDK para Rust
- Exemplos de AWS Batch usando SDK para Rust
- Exemplos de código do Provedor de Identidade do Amazon Cognito usando SDK para Rust
- Exemplos do Amazon Cognito Sync usando SDK para Rust
- Exemplos do DynamoDB usando SDK para Rust
- Exemplos do Amazon EBS usando SDK para Rust
- Exemplos do Amazon EC2 usando SDK para Rust
- Exemplos do Amazon ECR usando o SDK para Rust
- Exemplos do Amazon ECS usando o SDK para Rust
- Exemplos do Amazon EKS usando o SDK para Rust
- Exemplos de AWS Glue usando SDK para Rust
- Exemplos do IAM usando SDK para Rust
- Exemplos de AWS IoT usando SDK para Rust
- Exemplos do Kinesis usando SDK para Rust
- Exemplos de Firehose usando o SDK para Rust
- Exemplos de AWS KMS usando SDK para Rust
- Exemplos de Lambda usando SDKs para Rust
- MediaLive exemplos usando o SDK para Rust
- MediaPackage exemplos usando o SDK para Rust
- Exemplos do Amazon Polly usando o SDK para Rust

- Exemplos de QLDB usando SDK para Rust
- Exemplos do Amazon RDS Data Service usando SDK para Rust
- Exemplos de Route 53 usando o SDK para Rust
- Exemplos do Amazon S3 usando o SDK para Rust
- SageMaker exemplos usando o SDK para Rust
- Exemplos de Secrets Manager usando SDK para Rust
- Exemplos API v2 do Amazon SES usando SDK para Rust
- Exemplos do Amazon SNS usando o SDK para Rust
- Exemplos do Amazon SQS usando SDK para Rust
- Exemplos de AWS STS usando SDK para Rust
- Exemplos do Systems Manager usando o SDK para Rust

Exemplos de API Gateway usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o API Gateway.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar APIs REST

O exemplo de código a seguir mostra como listar uma APIs REST do API Gateway.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exibir as APIs REST do Amazon Gateway na região.

```
async fn show_apis(client: &Client) -> Result<(), Error> {
    let resp = client.get_rest_apis().send().await?;

    for api in resp.items() {
        println!("ID:          {}", api.id().unwrap_or_default());
        println!("Name:        {}", api.name().unwrap_or_default());
        println!("Description: {}", api.description().unwrap_or_default());
        println!("Version:     {}", api.version().unwrap_or_default());
        println!(
            "Created:     {}",
            api.created_date().unwrap().to_chrono_utc()?
        );
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetRestApisreferência da API AWS SDK for Rust.

Exemplos de Gerenciamento de API de API Gateway usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Gerenciamento de API Gateway.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Enviar dados para uma conexão

O exemplo de código a seguir mostra como enviar dados para uma conexão.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn send_data(
    client: &aws_sdk_apigatewaymanagement::Client,
    con_id: &str,
    data: &str,
) -> Result<(), aws_sdk_apigatewaymanagement::Error> {
    client
        .post_to_connection()
        .connection_id(con_id)
        .data(Blob::new(data))
        .send()
        .await?;

    Ok(())
}

    let endpoint_url = format!(
        "https://{api_id}.execute-api.{region}.amazonaws.com/{stage}",
        api_id = api_id,
```

```
        region = region,
        stage = stage
    );

    let shared_config = aws_config::from_env().region(region_provider).load().await;
    let api_management_config = config::Builder::from(&shared_config)
        .endpoint_url(endpoint_url)
        .build();
    let client = Client::from_conf(api_management_config);
```

- Para obter detalhes da API, consulte a PostToConnectionreferência da API AWS SDK for Rust.

Exemplos do Application Auto Scaling usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com Aplicação Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descrever scaling em etapas

O exemplo de código a seguir mostra como descrever as políticas de escalabilidade do Application Auto Scaling para um determinado namespace de serviço.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_policies(client: &Client) -> Result<(), Error> {
    let response = client
        .describe_scaling_policies()
        .service_namespace(ServiceNamespace::Ec2)
        .send()
        .await?;
    println!("Auto Scaling Policies:");
    for policy in response.scaling_policies() {
        println!("{:?}\n", policy);
    }
    println!("Next token: {:?}", response.next_token());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeScalingPoliciesreferência da API AWS SDK for Rust.

Exemplos de Aurora usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Aurora.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Aurora

Os exemplos de código a seguir mostram como começar a usar o Aurora.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
use aws_sdk_rds::Client;

#[derive(Debug)]
struct Error(String);
impl std::fmt::Display for Error {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        write!(f, "{}", self.0)
    }
}
impl std::error::Error for Error {}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt::init();
    let sdk_config = aws_config::from_env().load().await;
    let client = Client::new(&sdk_config);

    let describe_db_clusters_output = client
        .describe_db_clusters()
        .send()
        .await
        .map_err(|e| Error(e.to_string()))?;
    println!(
        "Found {} clusters:",
        describe_db_clusters_output.db_clusters().len()
    );
    for cluster in describe_db_clusters_output.db_clusters() {
```

```
        let name = cluster.database_name().unwrap_or("Unknown");
        let engine = cluster.engine().unwrap_or("Unknown");
        let id = cluster.db_cluster_identifier().unwrap_or("Unknown");
        let class = cluster.db_cluster_instance_class().unwrap_or("Unknown");
        println!("\tDatabase: {name}",);
        println!("\t  Engine: {engine}",);
        println!("\t      ID: {id}",);
        println!("\tInstance: {class}",);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte DescreverDBClusters na AWS Referência da API SDK para Rust.

Tópicos

- Ações
- Cenários

Ações

Criar um cluster de banco de dados

Os exemplos de código a seguir mostram como criar um cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql database
and uses the parameter group you created.
```

```
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine and engine
version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql', EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(), ScenarioError>
{
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
           return Err(ScenarioError::new(
               "Failed to create DB Cluster with cluster group",
               &err,
           ));
       }

       self.db_cluster_identifier = create_db_cluster
           .unwrap()
           .db_cluster
           .and_then(|c| c.db_cluster_identifier);

       if self.db_cluster_identifier.is_none() {
           return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
       }
```

```
        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for ready");
```

```
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() == Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
```

```
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn create_db_cluster(
        &self,
        name: &str,
        parameter_group: &str,
        engine: &str,
        version: &str,
        username: &str,
        password: SecretString,
    ) -> Result<CreateDbClusterOutput, SdkError<CreateDBClusterError>> {
        self.inner
            .create_db_cluster()
            .db_cluster_identifier(name)
            .db_cluster_parameter_group_name(parameter_group)
            .engine(engine)
            .engine_version(version)
            .master_username(username)
            .master_user_password(password.expose_secret())
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
```

```
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
```

```
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

```
#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message ==
 "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));
```

```
    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message ==
 "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));
```

```
    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
```

```
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });
```

```
    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CriarDBCluster na AWS Referência da API SDK para Rust.

Criar um parameter group de cluster de banco de dados

O exemplo de código a seguir mostra como criar um grupo de parâmetros de cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Select an engine family and create a custom DB cluster parameter group.
rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
   pub async fn set_engine(&mut self, engine: &str, version: &str) -> Result<(),
ScenarioError> {
       self.engine_family = Some(engine.to_string());
       self.engine_version = Some(version.to_string());
       let create_db_cluster_parameter_group = self
```

```
            .rds
            .create_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION,
                engine,
            )
            .await;

        match create_db_cluster_parameter_group {
            Ok(CreateDbClusterParameterGroupOutput {
                db_cluster_parameter_group: None,
                ..
            }) => {
                return Err(ScenarioError::with(
                    "CreateDBClusterParameterGroup had empty response",
                ));
            }
            Err(error) => {
                if error.code() == Some("DBParameterGroupAlreadyExists") {
                    info!("Cluster Parameter Group already exists, nothing to do");
                } else {
                    return Err(ScenarioError::new(
                        "Could not create Cluster Parameter Group",
                        &error,
                    ));
                }
            }
            _ => {
                info!("Created Cluster Parameter Group");
            }
        }

        Ok(())
    }

    pub async fn create_db_cluster_parameter_group(
        &self,
        name: &str,
        description: &str,
        family: &str,
    ) -> Result<CreateDbClusterParameterGroupOutput,
SdkError<CreateDBClusterParameterGroupError>>
    {
        self.inner
```

```
            .create_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .description(description)
            .db_parameter_group_family(family)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_set_engine() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert_eq!(set_engine, Ok(()));
    assert_eq!(Some("aurora-mysql"), scenario.engine_family.as_deref());
    assert_eq!(Some("aurora-mysql8.0"), scenario.engine_version.as_deref());
}

#[tokio::test]
async fn test_scenario_set_engine_not_create() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
```

```
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _|
 Ok(CreateDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert!(set_engine.is_err());
}

#[tokio::test]
async fn test_scenario_set_engine_param_group_exists() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .withf(|_, _, _| true)
        .return_once(|_, _, _| {
            Err(SdkError::service_error(

 CreateDBClusterParameterGroupError::DbParameterGroupAlreadyExistsFault(
                    DbParameterGroupAlreadyExistsFault::builder().build(),
                ),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert!(set_engine.is_err());
}
```

- Para obter detalhes da API, consulte CreateDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Criar um snapshot de cluster de banco de dados

Os exemplos de código a seguir mostram como criar um snapshot de cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql database
and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine and engine
version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql', EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(), ScenarioError>
{
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
```

```
            return Err(ScenarioError::new(
                "Failed to create DB Cluster with cluster group",
                &err,
            ));
        }

        self.db_cluster_identifier = create_db_cluster
            .unwrap()
            .db_cluster
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);
```

```
        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() == Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
```

```
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn snapshot_cluster(
        &self,
        db_cluster_identifier: &str,
        snapshot_name: &str,
    ) -> Result<CreateDbClusterSnapshotOutput,
 SdkError<CreateDBClusterSnapshotError>> {
        self.inner
            .create_db_cluster_snapshot()
            .db_cluster_identifier(db_cluster_identifier)
            .db_cluster_snapshot_identifier(snapshot_name)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
```

```
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
```

```
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
```

```
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message ==
 "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
```

```
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message ==
 "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
```

```
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
```

```
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });
```

```
    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CreateDB ClusterSnapshot na referência da API AWSSDK for Rust.

Criar uma instância de banco de dados em um cluster de banco de dados

Os exemplos de código a seguir mostram como criar uma instância em um cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
   // Create an Aurora DB cluster database cluster that contains a MySql database
and uses the parameter group you created.
   // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
   // Get a list of instance classes available for the selected engine and engine
version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql', EngineVersion=).

   // Create a database instance in the cluster.
   // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
DBInstanceStatus == 'available'.
   pub async fn start_cluster_and_instance(&mut self) -> Result<(), ScenarioError>
{
       if self.password.is_none() {
           return Err(ScenarioError::with(
               "Must set Secret Password before starting a cluster",
           ));
       }
       let create_db_cluster = self
           .rds
           .create_db_cluster(
               DB_CLUSTER_IDENTIFIER,
               DB_CLUSTER_PARAMETER_GROUP_NAME,
               DB_ENGINE,
               self.engine_version.as_deref().expect("engine version"),
               self.username.as_deref().expect("username"),
               self.password
                   .replace(SecretString::new("".to_string()))
                   .expect("password"),
           )
           .await;
       if let Err(err) = create_db_cluster {
           return Err(ScenarioError::new(
               "Failed to create DB Cluster with cluster group",
               &err,
           ));
       }

       self.db_cluster_identifier = create_db_cluster
           .unwrap()
           .db_cluster
```

```
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
```

```
                .expect("cluster identifier"),
        )
        .await;

    if let Err(err) = cluster {
        warn!(?err, "Failed to describe cluster while waiting for ready");
        continue;
    }

    let instance = self
        .rds
        .describe_db_instance(
            self.db_instance_identifier
                .as_deref()
                .expect("instance identifier"),
        )
        .await;
    if let Err(err) = instance {
        return Err(ScenarioError::new(
            "Failed to find instance for cluster",
            &err,
        ));
    }

    let instances_available = instance
        .unwrap()
        .db_instances()
        .iter()
        .all(|instance| instance.db_instance_status() == Some("Available"));

    let endpoints = self
        .rds
        .describe_db_cluster_endpoints(
            self.db_cluster_identifier
                .as_deref()
                .expect("cluster identifier"),
        )
        .await;

    if let Err(err) = endpoints {
        return Err(ScenarioError::new(
            "Failed to find endpoint for cluster",
            &err,
        ));
```

```
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }

    pub async fn create_db_instance(
        &self,
        cluster_name: &str,
        instance_name: &str,
        instance_class: &str,
        engine: &str,
    ) -> Result<CreateDbInstanceOutput, SdkError<CreateDBInstanceError>> {
        self.inner
            .create_db_instance()
            .db_cluster_identifier(cluster_name)
            .db_instance_identifier(instance_name)
            .db_instance_class(instance_class)
            .engine(engine)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
```

```
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
```

```
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
```

```
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message ==
 "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
```

```
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message ==
 "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
```

```
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
```

```
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
```

```
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte CriarInstânciaDB na AWS Referência da API SDK para Rust.

Excluir um cluster de banco de dados

O exemplo de código a seguir mostra como excluir um cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
```

```
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances = self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in {status}");
                        continue;
```

```
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
```

```
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster parameter group. rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
```

```
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_cluster(
        &self,
        cluster_identifier: &str,
    ) -> Result<DeleteDbClusterOutput, SdkError<DeleteDBClusterError>> {
        self.inner
            .delete_db_cluster()
            .db_cluster_identifier(cluster_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));
```

```
    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
```

```
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
```

```
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
 message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
 message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte ExcluirDBCluster na AWS Referência da API SDK para Rust.

Excluir um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como excluir um grupo de parâmetros de cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
    let mut clean_up_errors: Vec<ScenarioError> = vec![];

    // Delete the instance. rds.DeleteDbInstance.
    let delete_db_instance = self
        .rds
        .delete_db_instance(
            self.db_instance_identifier
                .as_deref()
                .expect("instance identifier"),
        )
        .await;
    if let Err(err) = delete_db_instance {
        let identifier = self
            .db_instance_identifier
            .as_deref()
            .unwrap_or("Missing Instance Identifier");
        let message = format!("failed to delete db instance {identifier}");
        clean_up_errors.push(ScenarioError::new(message, &err));
    } else {
        // Wait for the instance to delete
        let waiter = Waiter::default();
        while waiter.sleep().await.is_ok() {
            let describe_db_instances = self.rds.describe_db_instances().await;
            if let Err(err) = describe_db_instances {
                clean_up_errors.push(ScenarioError::new(
                    "Failed to check instance state during deletion",
                    &err,
                ));
                break;
            }
            let db_instances = describe_db_instances
                .unwrap()
                .db_instances()
```

```
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
```

```
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster parameter group. rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
```

```
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_cluster_parameter_group(
        &self,
        name: &str,
    ) -> Result<DeleteDbClusterParameterGroupOutput,
 SdkError<DeleteDBClusterParameterGroupError>>
    {
        self.inner
            .delete_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
```

```
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
```

```
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
```

```
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
```

```
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Cluster
    tokio::time::resume();
```

```
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DeleteDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Excluir uma instância de banco de dados

O exemplo de código a seguir mostra como excluir uma instância do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
```

```
                let describe_db_instances = self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;
```

```
        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
```

```
                }
            }
        }

        // Delete the DB cluster parameter group. rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn delete_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DeleteDbInstanceOutput, SdkError<DeleteDBInstanceError>> {
        self.inner
            .delete_db_instance()
            .db_instance_identifier(instance_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }
```

```
#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
```

```
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
```

```
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
```

```
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });
```

```
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte ExcluirInstânciaDB na AWS Referência da API SDK para Rust.

Descrever clusters de banco de dados

Os exemplos de código a seguir mostram como descrever clusters do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Get a list of allowed engine versions.
 rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
 family used to create your parameter group in step 2>)
    // Create an Aurora DB cluster database cluster that contains a MySql database
 and uses the parameter group you created.
    // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
 Status == 'available'.
    // Get a list of instance classes available for the selected engine and engine
 version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql', EngineVersion=).

    // Create a database instance in the cluster.
    // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
 DBInstanceStatus == 'available'.
```

```
    pub async fn start_cluster_and_instance(&mut self) -> Result<(), ScenarioError>
{
        if self.password.is_none() {
            return Err(ScenarioError::with(
                "Must set Secret Password before starting a cluster",
            ));
        }
        let create_db_cluster = self
            .rds
            .create_db_cluster(
                DB_CLUSTER_IDENTIFIER,
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_ENGINE,
                self.engine_version.as_deref().expect("engine version"),
                self.username.as_deref().expect("username"),
                self.password
                    .replace(SecretString::new("".to_string()))
                    .expect("password"),
            )
            .await;
        if let Err(err) = create_db_cluster {
            return Err(ScenarioError::new(
                "Failed to create DB Cluster with cluster group",
                &err,
            ));
        }

        self.db_cluster_identifier = create_db_cluster
            .unwrap()
            .db_cluster
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );
```

```
        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
```

```
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }

            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() == Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
```

```
    }

    pub async fn describe_db_clusters(
        &self,
        id: &str,
    ) -> Result<DescribeDbClustersOutput, SdkError<DescribeDBClustersError>> {
        self.inner
            .describe_db_clusters()
            .db_cluster_identifier(id)
            .send()
            .await
    }

#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
```

```
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });
```

```
    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
```

```
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message ==
 "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message ==
 "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
```

```
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
```

```
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
```

```
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DescreverDBClusters na AWS Referência da API SDK para Rust.

Descrever instâncias de banco de dados

O exemplo de código a seguir mostra como descrever instâncias do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
    let mut clean_up_errors: Vec<ScenarioError> = vec![];

    // Delete the instance. rds.DeleteDbInstance.
    let delete_db_instance = self
        .rds
        .delete_db_instance(
            self.db_instance_identifier
                .as_deref()
                .expect("instance identifier"),
        )
        .await;
    if let Err(err) = delete_db_instance {
        let identifier = self
            .db_instance_identifier
            .as_deref()
            .unwrap_or("Missing Instance Identifier");
        let message = format!("failed to delete db instance {identifier}");
        clean_up_errors.push(ScenarioError::new(message, &err));
    } else {
        // Wait for the instance to delete
        let waiter = Waiter::default();
        while waiter.sleep().await.is_ok() {
            let describe_db_instances = self.rds.describe_db_instances().await;
            if let Err(err) = describe_db_instances {
```

```
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
```

```
            let identifier = self
                .db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
```

```
        }

        // Delete the DB cluster parameter group. rds.DeleteDbClusterParameterGroup.
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }

    pub async fn describe_db_instances(
        &self,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner.describe_db_instances().send().await
    }

#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));
```

```
    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
```

```
        .with(eq("MockParamGroup"))
        .return_once(|_|
 Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
```

```
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
```

```
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Cluster
```

```
    tokio::time::resume();
    let _ = assertions.await;
}
```

- Para obter detalhes da API, consulte DescreverInstânciasDB na AWS Referência da API SDK para Rust.

Descrever as versões de mecanismo de banco de dados

Os exemplos de código a seguir mostram como descrever as versões de mecanismo de banco de dados do Aurora.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   // Get available engine families for Aurora MySql.
rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
   pub async fn get_engines(&self) -> Result<HashMap<String, Vec<String>>,
ScenarioError> {
       let describe_db_engine_versions =
self.rds.describe_db_engine_versions(DB_ENGINE).await;
       trace!(versions=?describe_db_engine_versions, "full list of versions");

       if let Err(err) = describe_db_engine_versions {
           return Err(ScenarioError::new(
               "Failed to retrieve DB Engine Versions",
               &err,
           ));
       };

       let version_count = describe_db_engine_versions
           .as_ref()
           .map(|o| o.db_engine_versions().len())
           .unwrap_or_default();
```

```
        info!(version_count, "got list of versions");

        // Create a map of engine families to their available versions.
        let mut versions = HashMap::<String, Vec<String>>::new();
        describe_db_engine_versions
            .unwrap()
            .db_engine_versions()
            .iter()
            .filter_map(
                |v| match (&v.db_parameter_group_family, &v.engine_version) {
                    (Some(family), Some(version)) => Some((family.clone(),
 version.clone())),
                    _ => None,
                },
            )
            .for_each(|(family, version)|
 versions.entry(family).or_default().push(version));

        Ok(versions)
    }

    pub async fn describe_db_engine_versions(
        &self,
        engine: &str,
    ) -> Result<DescribeDbEngineVersionsOutput,
 SdkError<DescribeDBEngineVersionsError>> {
        self.inner
            .describe_db_engine_versions()
            .engine(engine)
            .send()
            .await
    }

#[tokio::test]
async fn test_scenario_get_engines() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Ok(DescribeDbEngineVersionsOutput::builder()
                .db_engine_versions(
                    DbEngineVersion::builder()
```

```
                        .db_parameter_group_family("f1")
                        .engine_version("f1a")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1b")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f2")
                        .engine_version("f2a")
                        .build(),
                )
                .db_engine_versions(DbEngineVersion::builder().build())
                .build())
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;

    assert_eq!(
        versions_map,
        Ok(HashMap::from([
            ("f1".into(), vec!["f1a".into(), "f1b".into()]),
            ("f2".into(), vec!["f2a".into()])
        ]))
    );
}

#[tokio::test]
async fn test_scenario_get_engines_failed() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBEngineVersionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
```

```
                    "describe_db_engine_versions error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;
    assert_matches!(
        versions_map,
        Err(ScenarioError { message, context: _ }) if message == "Failed to retrieve
 DB Engine Versions"
    );
}
```

- Para obter detalhes da API, consulte DescribeDB EngineVersions na referência da API AWSSDK for Rust.

Descrever as opções de instâncias de banco de dados

Os exemplos de código a seguir mostram como descrever as opções para instâncias Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn get_instance_classes(&self) -> Result<Vec<String>, ScenarioError> {
        let describe_orderable_db_instance_options_items = self
            .rds
            .describe_orderable_db_instance_options(
                DB_ENGINE,
                self.engine_version
                    .as_ref()
                    .expect("engine version for db instance options")
                    .as_str(),
            )
```

```
            .await;

        describe_orderable_db_instance_options_items
            .map(|options| {
                options
                    .iter()
                    .map(|o| o.db_instance_class().unwrap_or_default().to_string())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Could not get available instance
 classes", &err))
    }

    pub async fn describe_orderable_db_instance_options(
        &self,
        engine: &str,
        engine_version: &str,
    ) -> Result<Vec<OrderableDbInstanceOption>,
 SdkError<DescribeOrderableDBInstanceOptionsError>>
    {
        self.inner
            .describe_orderable_db_instance_options()
            .engine(engine)
            .engine_version(engine_version)
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
    }

#[tokio::test]
async fn test_scenario_get_instance_classes() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });
```

```
    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Ok(vec![
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t1")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t2")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t3")
                    .build(),
            ])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario
        .set_engine("aurora-mysql", "aurora-mysql8.0")
        .await
        .expect("set engine");

    let instance_classes = scenario.get_instance_classes().await;

    assert_eq!(
        instance_classes,
        Ok(vec!["t1".into(), "t2".into(), "t3".into()])
    );
}

#[tokio::test]
async fn test_scenario_get_instance_classes_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Err(SdkError::service_error(

 DescribeOrderableDBInstanceOptionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_orderable_db_instance_options_error",
```

```
                )),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_family = Some("aurora-mysql".into());
    scenario.engine_version = Some("aurora-mysql8.0".into());

    let instance_classes = scenario.get_instance_classes().await;

    assert_matches!(
        instance_classes,
        Err(ScenarioError {message, context: _}) if message == "Could not get
 available instance classes"
    );
}
```

- Para obter detalhes da API, consulte a referência da API DescribeOrderableDB InstanceOptions in AWS SDK for Rust.

Descrever os parâmetros de um grupo de parâmetros de cluster de banco de dados

O exemplo de código a seguir mostra como descrever parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Get the parameter group. rds.DescribeDbClusterParameterGroups
    // Get parameters in the group. This is a long list so you will have to
 paginate. Find the auto_increment_offset and auto_increment_increment parameters
 (by ParameterName). rds.DescribeDbClusterParameters
    // Parse the ParameterName, Description, and AllowedValues values and display
 them.
```

```
    pub async fn cluster_parameters(&self) -> Result<Vec<AuroraScenarioParameter>,
 ScenarioError> {
        let parameters_output = self
            .rds
            .describe_db_cluster_parameters(DB_CLUSTER_PARAMETER_GROUP_NAME)
            .await;

        if let Err(err) = parameters_output {
            return Err(ScenarioError::new(
                format!("Failed to retrieve parameters for
 {DB_CLUSTER_PARAMETER_GROUP_NAME}"),
                &err,
            ));
        }

        let parameters = parameters_output
            .unwrap()
            .into_iter()
            .flat_map(|p| p.parameters.unwrap_or_default().into_iter())
            .filter(|p|
 FILTER_PARAMETER_NAMES.contains(p.parameter_name().unwrap_or_default()))
            .map(AuroraScenarioParameter::from)
            .collect::<Vec<_>>();

        Ok(parameters)
    }

    pub async fn describe_db_cluster_parameters(
        &self,
        name: &str,
    ) -> Result<Vec<DescribeDbClusterParametersOutput>,
 SdkError<DescribeDBClusterParametersError>>
    {
        self.inner
            .describe_db_cluster_parameters()
            .db_cluster_parameter_group_name(name)
            .into_paginator()
            .send()
            .try_collect()
            .await
    }

#[tokio::test]
async fn test_scenario_cluster_parameters() {
```

```
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Ok(vec![DescribeDbClusterParametersOutput::builder()
                .parameters(Parameter::builder().parameter_name("a").build())
                .parameters(Parameter::builder().parameter_name("b").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("c").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("d").build())
                .build()])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());

    let params = scenario.cluster_parameters().await.expect("cluster params");
    let names: Vec<String> = params.into_iter().map(|p| p.name).collect();
    assert_eq!(
        names,
        vec!["auto_increment_offset", "auto_increment_increment"]
    );
}

#[tokio::test]
async fn test_scenario_cluster_parameters_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Err(SdkError::service_error(
```

```
                DescribeDBClusterParametersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_cluster_parameters_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let params = scenario.cluster_parameters().await;
    assert_matches!(params, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to retrieve parameters for RustSDKCodeExamplesDBParameterGroup");
}
```

- Para obter detalhes da API, consulte DescribeDB ClusterParameters na referência da API AWSSDK for Rust.

Atualizar os parâmetros em um grupo de parâmetros de cluster de banco de dados

Os exemplos de código a seguir mostram como atualizar os parâmetros de um grupo de parâmetros de cluster do Aurora DB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    // Modify both the auto_increment_offset and auto_increment_increment parameters
 in one call in the custom parameter group. Set their ParameterValue fields to a new
 allowable value. rds.ModifyDbClusterParameterGroup.
    pub async fn update_auto_increment(
        &self,
        offset: u8,
        increment: u8,
    ) -> Result<(), ScenarioError> {
        let modify_db_cluster_parameter_group = self
```

```
            .rds
            .modify_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value(format!("{offset}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value(format!("{increment}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ],
            )
            .await;

        if let Err(error) = modify_db_cluster_parameter_group {
            return Err(ScenarioError::new(
                "Failed to modify cluster parameter group",
                &error,
            ));
        }

        Ok(())
    }

    pub async fn modify_db_cluster_parameter_group(
        &self,
        name: &str,
        parameters: Vec<Parameter>,
    ) -> Result<ModifyDbClusterParameterGroupOutput,
 SdkError<ModifyDBClusterParameterGroupError>>
    {
        self.inner
            .modify_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .set_parameters(Some(parameters))
            .send()
            .await
    }

#[tokio::test]
```

```
async fn test_scenario_update_auto_increment() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .withf(|name, params| {
            assert_eq!(name, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(
                params,
                &vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value("10")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value("20")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ]
            );
            true
        })
        .return_once(|_, _|
 Ok(ModifyDbClusterParameterGroupOutput::builder().build()));

    let scenario = AuroraScenario::new(mock_rds);

    scenario
        .update_auto_increment(10, 20)
        .await
        .expect("update auto increment");
}

#[tokio::test]
async fn test_scenario_update_auto_increment_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .return_once(|_, _| {
            Err(SdkError::service_error(
                ModifyDBClusterParameterGroupError::unhandled(Box::new(Error::new(
```

```
                    ErrorKind::Other,
                    "modify_db_cluster_parameter_group_error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let update = scenario.update_auto_increment(10, 20).await;
    assert_matches!(update, Err(ScenarioError { message, context: _}) if message ==
 "Failed to modify cluster parameter group");
}
```

- Para obter detalhes da API, consulte ModifyDB ClusterParameterGroup na referência da API AWSSDK for Rust.

Cenários

Começar a usar clusters de banco de dados

O código de exemplo a seguir mostra como:

- Crie um grupo de parâmetros de cluster do banco de dados do Aurora e defina os valores dos parâmetros.
- Crie um cluster de banco de dados que use o grupo de parâmetros.
- Crie uma instância de banco de dados que contenha um banco de dados.
- Crie um snapshot do cluster do banco de dados e limpe os recursos.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma biblioteca contendo as funções específicas para o cenário do Aurora.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use phf::{phf_set, Set};
use secrecy::SecretString;
use std::{collections::HashMap, fmt::Display, time::Duration};

use aws_sdk_rds::{
    error::ProvideErrorMetadata,

 operation::create_db_cluster_parameter_group::CreateDbClusterParameterGroupOutput,
    types::{DbCluster, DbClusterParameterGroup, DbClusterSnapshot, DbInstance,
 Parameter},
};
use sdk_examples_test_utils::waiter::Waiter;
use tracing::{info, trace, warn};

const DB_ENGINE: &str = "aurora-mysql";
const DB_CLUSTER_PARAMETER_GROUP_NAME: &str = "RustSDKCodeExamplesDBParameterGroup";
const DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION: &str =
    "Parameter Group created by Rust SDK Code Example";
const DB_CLUSTER_IDENTIFIER: &str = "RustSDKCodeExamplesDBCluster";
const DB_INSTANCE_IDENTIFIER: &str = "RustSDKCodeExamplesDBInstance";

static FILTER_PARAMETER_NAMES: Set<&'static str> = phf_set! {
    "auto_increment_offset",
    "auto_increment_increment",
};

#[derive(Debug, PartialEq, Eq)]
struct MetadataError {
    message: Option<String>,
    code: Option<String>,
}

impl MetadataError {
    fn from(err: &dyn ProvideErrorMetadata) -> Self {
        MetadataError {
            message: err.message().map(String::from),
            code: err.code().map(String::from),
        }
    }
}
```

```
impl Display for MetadataError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        let display = match (&self.message, &self.code) {
            (None, None) => "Unknown".to_string(),
            (None, Some(code)) => format!("({code})"),
            (Some(message), None) => message.to_string(),
            (Some(message), Some(code)) => format!("{message} ({code})"),
        };
        write!(f, "{display}")
    }
}

#[derive(Debug, PartialEq, Eq)]
pub struct ScenarioError {
    message: String,
    context: Option<MetadataError>,
}

impl ScenarioError {
    pub fn with(message: impl Into<String>) -> Self {
        ScenarioError {
            message: message.into(),
            context: None,
        }
    }

    pub fn new(message: impl Into<String>, err: &dyn ProvideErrorMetadata) -> Self {
        ScenarioError {
            message: message.into(),
            context: Some(MetadataError::from(err)),
        }
    }
}

impl std::error::Error for ScenarioError {}
impl Display for ScenarioError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        match &self.context {
            Some(c) => write!(f, "{}: {}", self.message, c),
            None => write!(f, "{}", self.message),
        }
    }
}
```

```
// Parse the ParameterName, Description, and AllowedValues values and display them.
#[derive(Debug)]
pub struct AuroraScenarioParameter {
    name: String,
    allowed_values: String,
    current_value: String,
}

impl Display for AuroraScenarioParameter {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        write!(
            f,
            "{}: {} (allowed: {})",
            self.name, self.current_value, self.allowed_values
        )
    }
}

impl From<aws_sdk_rds::types::Parameter> for AuroraScenarioParameter {
    fn from(value: aws_sdk_rds::types::Parameter) -> Self {
        AuroraScenarioParameter {
            name: value.parameter_name.unwrap_or_default(),
            allowed_values: value.allowed_values.unwrap_or_default(),
            current_value: value.parameter_value.unwrap_or_default(),
        }
    }
}

pub struct AuroraScenario {
    rds: crate::rds::Rds,
    engine_family: Option<String>,
    engine_version: Option<String>,
    instance_class: Option<String>,
    db_cluster_parameter_group: Option<DbClusterParameterGroup>,
    db_cluster_identifier: Option<String>,
    db_instance_identifier: Option<String>,
    username: Option<String>,
    password: Option<SecretString>,
}

impl AuroraScenario {
    pub fn new(client: crate::rds::Rds) -> Self {
        AuroraScenario {
```

```
            rds: client,
            engine_family: None,
            engine_version: None,
            instance_class: None,
            db_cluster_parameter_group: None,
            db_cluster_identifier: None,
            db_instance_identifier: None,
            username: None,
            password: None,
        }
    }

    // snippet-start:[rust.aurora.get_engines.usage]
    // Get available engine families for Aurora MySql.
rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
    pub async fn get_engines(&self) -> Result<HashMap<String, Vec<String>>,
ScenarioError> {
        let describe_db_engine_versions =
self.rds.describe_db_engine_versions(DB_ENGINE).await;
        trace!(versions=?describe_db_engine_versions, "full list of versions");

        if let Err(err) = describe_db_engine_versions {
            return Err(ScenarioError::new(
                "Failed to retrieve DB Engine Versions",
                &err,
            ));
        };

        let version_count = describe_db_engine_versions
            .as_ref()
            .map(|o| o.db_engine_versions().len())
            .unwrap_or_default();
        info!(version_count, "got list of versions");

        // Create a map of engine families to their available versions.
        let mut versions = HashMap::<String, Vec<String>>::new();
        describe_db_engine_versions
            .unwrap()
            .db_engine_versions()
            .iter()
            .filter_map(
                |v| match (&v.db_parameter_group_family, &v.engine_version) {
```

```
                    (Some(family), Some(version)) => Some((family.clone(),
version.clone())),
                    _ => None,
                },
            )
            .for_each(|(family, version)|
versions.entry(family).or_default().push(version));

        Ok(versions)
    }
    // snippet-end:[rust.aurora.get_engines.usage]

    // snippet-start:[rust.aurora.get_instance_classes.usage]
    pub async fn get_instance_classes(&self) -> Result<Vec<String>, ScenarioError> {
        let describe_orderable_db_instance_options_items = self
            .rds
            .describe_orderable_db_instance_options(
                DB_ENGINE,
                self.engine_version
                    .as_ref()
                    .expect("engine version for db instance options")
                    .as_str(),
            )
            .await;

        describe_orderable_db_instance_options_items
            .map(|options| {
                options
                    .iter()
                    .map(|o| o.db_instance_class().unwrap_or_default().to_string())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Could not get available instance
classes", &err))
    }
    // snippet-end:[rust.aurora.get_instance_classes.usage]

    // snippet-start:[rust.aurora.set_engine.usage]
    // Select an engine family and create a custom DB cluster parameter group.
rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
    pub async fn set_engine(&mut self, engine: &str, version: &str) -> Result<(),
ScenarioError> {
        self.engine_family = Some(engine.to_string());
        self.engine_version = Some(version.to_string());
```

```
        let create_db_cluster_parameter_group = self
            .rds
            .create_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_CLUSTER_PARAMETER_GROUP_DESCRIPTION,
                engine,
            )
            .await;

        match create_db_cluster_parameter_group {
            Ok(CreateDbClusterParameterGroupOutput {
                db_cluster_parameter_group: None,
                ..
            }) => {
                return Err(ScenarioError::with(
                    "CreateDBClusterParameterGroup had empty response",
                ));
            }
            Err(error) => {
                if error.code() == Some("DBParameterGroupAlreadyExists") {
                    info!("Cluster Parameter Group already exists, nothing to do");
                } else {
                    return Err(ScenarioError::new(
                        "Could not create Cluster Parameter Group",
                        &error,
                    ));
                }
            }
            _ => {
                info!("Created Cluster Parameter Group");
            }
        }

        Ok(())
    }
    // snippet-end:[rust.aurora.set_engine.usage]

    pub fn set_instance_class(&mut self, instance_class: Option<String>) {
        self.instance_class = instance_class;
    }

    pub fn set_login(&mut self, username: Option<String>, password:
Option<SecretString>) {
        self.username = username;
```

```
        self.password = password;
    }

    pub async fn connection_string(&self) -> Result<String, ScenarioError> {
        let cluster = self.get_cluster().await?;
        let endpoint = cluster.endpoint().unwrap_or_default();
        let port = cluster.port().unwrap_or_default();
        let username = cluster.master_username().unwrap_or_default();
        Ok(format!("mysql -h {endpoint} -P {port} -u {username} -p"))
    }

    // snippet-start:[rust.aurora.get_cluster.usage]
    pub async fn get_cluster(&self) -> Result<DbCluster, ScenarioError> {
        let describe_db_clusters_output = self
            .rds
            .describe_db_clusters(
                self.db_cluster_identifier
                    .as_ref()
                    .expect("cluster identifier")
                    .as_str(),
            )
            .await;
        if let Err(err) = describe_db_clusters_output {
            return Err(ScenarioError::new("Failed to get cluster", &err));
        }

        let db_cluster = describe_db_clusters_output
            .unwrap()
            .db_clusters
            .and_then(|output| output.first().cloned());

        db_cluster.ok_or_else(|| ScenarioError::with("Did not find the cluster"))
    }
    // snippet-end:[rust.aurora.get_cluster.usage]

    // snippet-start:[rust.aurora.cluster_parameters.usage]
    // Get the parameter group. rds.DescribeDbClusterParameterGroups
    // Get parameters in the group. This is a long list so you will have to
 paginate. Find the auto_increment_offset and auto_increment_increment parameters
 (by ParameterName). rds.DescribeDbClusterParameters
    // Parse the ParameterName, Description, and AllowedValues values and display
 them.
    pub async fn cluster_parameters(&self) -> Result<Vec<AuroraScenarioParameter>,
 ScenarioError> {
```

```
        let parameters_output = self
            .rds
            .describe_db_cluster_parameters(DB_CLUSTER_PARAMETER_GROUP_NAME)
            .await;

        if let Err(err) = parameters_output {
            return Err(ScenarioError::new(
                format!("Failed to retrieve parameters for
{DB_CLUSTER_PARAMETER_GROUP_NAME}"),
                &err,
            ));
        }

        let parameters = parameters_output
            .unwrap()
            .into_iter()
            .flat_map(|p| p.parameters.unwrap_or_default().into_iter())
            .filter(|p|
FILTER_PARAMETER_NAMES.contains(p.parameter_name().unwrap_or_default()))
            .map(AuroraScenarioParameter::from)
            .collect::<Vec<_>>();

        Ok(parameters)
    }
    // snippet-end:[rust.aurora.cluster_parameters.usage]

    // snippet-start:[rust.aurora.update_auto_increment.usage]
    // Modify both the auto_increment_offset and auto_increment_increment parameters
in one call in the custom parameter group. Set their ParameterValue fields to a new
allowable value. rds.ModifyDbClusterParameterGroup.
    pub async fn update_auto_increment(
        &self,
        offset: u8,
        increment: u8,
    ) -> Result<(), ScenarioError> {
        let modify_db_cluster_parameter_group = self
            .rds
            .modify_db_cluster_parameter_group(
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value(format!("{offset}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
```

```
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value(format!("{increment}"))
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ],
            )
            .await;

        if let Err(error) = modify_db_cluster_parameter_group {
            return Err(ScenarioError::new(
                "Failed to modify cluster parameter group",
                &error,
            ));
        }

        Ok(())
    }
    // snippet-end:[rust.aurora.update_auto_increment.usage]

    // snippet-start:[rust.aurora.start_cluster_and_instance.usage]
    // Get a list of allowed engine versions.
rds.DescribeDbEngineVersions(Engine='aurora-mysql', DBParameterGroupFamily=<the
family used to create your parameter group in step 2>)
    // Create an Aurora DB cluster database cluster that contains a MySql database
and uses the parameter group you created.
    // Wait for DB cluster to be ready. Call rds.DescribeDBClusters and check for
Status == 'available'.
    // Get a list of instance classes available for the selected engine and engine
version. rds.DescribeOrderableDbInstanceOptions(Engine='mysql', EngineVersion=).

    // Create a database instance in the cluster.
    // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
DBInstanceStatus == 'available'.
    pub async fn start_cluster_and_instance(&mut self) -> Result<(), ScenarioError>
{
        if self.password.is_none() {
            return Err(ScenarioError::with(
                "Must set Secret Password before starting a cluster",
            ));
        }
        let create_db_cluster = self
            .rds
```

```
            .create_db_cluster(
                DB_CLUSTER_IDENTIFIER,
                DB_CLUSTER_PARAMETER_GROUP_NAME,
                DB_ENGINE,
                self.engine_version.as_deref().expect("engine version"),
                self.username.as_deref().expect("username"),
                self.password
                    .replace(SecretString::new("".to_string()))
                    .expect("password"),
            )
            .await;
        if let Err(err) = create_db_cluster {
            return Err(ScenarioError::new(
                "Failed to create DB Cluster with cluster group",
                &err,
            ));
        }

        self.db_cluster_identifier = create_db_cluster
            .unwrap()
            .db_cluster
            .and_then(|c| c.db_cluster_identifier);

        if self.db_cluster_identifier.is_none() {
            return Err(ScenarioError::with("Created DB Cluster missing
Identifier"));
        }

        info!(
            "Started a db cluster: {}",
            self.db_cluster_identifier
                .as_deref()
                .unwrap_or("Missing ARN")
        );

        let create_db_instance = self
            .rds
            .create_db_instance(
                self.db_cluster_identifier.as_deref().expect("cluster name"),
                DB_INSTANCE_IDENTIFIER,
                self.instance_class.as_deref().expect("instance class"),
                DB_ENGINE,
            )
            .await;
```

```
        if let Err(err) = create_db_instance {
            return Err(ScenarioError::new(
                "Failed to create Instance in DB Cluster",
                &err,
            ));
        }

        self.db_instance_identifier = create_db_instance
            .unwrap()
            .db_instance
            .and_then(|i| i.db_instance_identifier);

        // Cluster creation can take up to 20 minutes to become available
        let cluster_max_wait = Duration::from_secs(20 * 60);
        let waiter = Waiter::builder().max(cluster_max_wait).build();
        while waiter.sleep().await.is_ok() {
            let cluster = self
                .rds
                .describe_db_clusters(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = cluster {
                warn!(?err, "Failed to describe cluster while waiting for ready");
                continue;
            }

            let instance = self
                .rds
                .describe_db_instance(
                    self.db_instance_identifier
                        .as_deref()
                        .expect("instance identifier"),
                )
                .await;
            if let Err(err) = instance {
                return Err(ScenarioError::new(
                    "Failed to find instance for cluster",
                    &err,
                ));
            }
```

```
            let instances_available = instance
                .unwrap()
                .db_instances()
                .iter()
                .all(|instance| instance.db_instance_status() == Some("Available"));

            let endpoints = self
                .rds
                .describe_db_cluster_endpoints(
                    self.db_cluster_identifier
                        .as_deref()
                        .expect("cluster identifier"),
                )
                .await;

            if let Err(err) = endpoints {
                return Err(ScenarioError::new(
                    "Failed to find endpoint for cluster",
                    &err,
                ));
            }

            let endpoints_available = endpoints
                .unwrap()
                .db_cluster_endpoints()
                .iter()
                .all(|endpoint| endpoint.status() == Some("available"));

            if instances_available && endpoints_available {
                return Ok(());
            }
        }

        Err(ScenarioError::with("timed out waiting for cluster"))
    }
    // snippet-end:[rust.aurora.start_cluster_and_instance.usage]

    // snippet-start:[rust.aurora.snapshot.usage]
    // Create a snapshot of the DB cluster. rds.CreateDbClusterSnapshot.
    // Wait for the snapshot to create. rds.DescribeDbClusterSnapshots until Status
== 'available'.
    pub async fn snapshot(&self, name: &str) -> Result<DbClusterSnapshot,
ScenarioError> {
```

```
        let id = self.db_cluster_identifier.as_deref().unwrap_or_default();
        let snapshot = self
            .rds
            .snapshot_cluster(id, format!("{id}_{name}").as_str())
            .await;
        match snapshot {
            Ok(output) => match output.db_cluster_snapshot {
                Some(snapshot) => Ok(snapshot),
                None => Err(ScenarioError::with("Missing Snapshot")),
            },
            Err(err) => Err(ScenarioError::new("Failed to create snapshot", &err)),
        }
    }
    // snippet-end:[rust.aurora.snapshot.usage]

    // snippet-start:[rust.aurora.clean_up.usage]
    pub async fn clean_up(self) -> Result<(), Vec<ScenarioError>> {
        let mut clean_up_errors: Vec<ScenarioError> = vec![];

        // Delete the instance. rds.DeleteDbInstance.
        let delete_db_instance = self
            .rds
            .delete_db_instance(
                self.db_instance_identifier
                    .as_deref()
                    .expect("instance identifier"),
            )
            .await;
        if let Err(err) = delete_db_instance {
            let identifier = self
                .db_instance_identifier
                .as_deref()
                .unwrap_or("Missing Instance Identifier");
            let message = format!("failed to delete db instance {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance to delete
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_instances = self.rds.describe_db_instances().await;
                if let Err(err) = describe_db_instances {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check instance state during deletion",
                        &err,
```

```
                    ));
                    break;
                }
                let db_instances = describe_db_instances
                    .unwrap()
                    .db_instances()
                    .iter()
                    .filter(|instance| instance.db_cluster_identifier ==
self.db_cluster_identifier)
                    .cloned()
                    .collect::<Vec<DbInstance>>();

                if db_instances.is_empty() {
                    trace!("Delete Instance waited and no instances were found");
                    break;
                }
                match db_instances.first().unwrap().db_instance_status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but instances is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB instance");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster. rds.DeleteDbCluster.
        let delete_db_cluster = self
            .rds
            .delete_db_cluster(
                self.db_cluster_identifier
                    .as_deref()
                    .expect("cluster identifier"),
            )
            .await;

        if let Err(err) = delete_db_cluster {
            let identifier = self
                .db_cluster_identifier
                .as_deref()
```

```
                .unwrap_or("Missing DB Cluster Identifier");
            let message = format!("failed to delete db cluster {identifier}");
            clean_up_errors.push(ScenarioError::new(message, &err));
        } else {
            // Wait for the instance and cluster to fully delete.
rds.DescribeDbInstances and rds.DescribeDbClusters until both are not found.
            let waiter = Waiter::default();
            while waiter.sleep().await.is_ok() {
                let describe_db_clusters = self
                    .rds
                    .describe_db_clusters(
                        self.db_cluster_identifier
                            .as_deref()
                            .expect("cluster identifier"),
                    )
                    .await;
                if let Err(err) = describe_db_clusters {
                    clean_up_errors.push(ScenarioError::new(
                        "Failed to check cluster state during deletion",
                        &err,
                    ));
                    break;
                }
                let describe_db_clusters = describe_db_clusters.unwrap();
                let db_clusters = describe_db_clusters.db_clusters();
                if db_clusters.is_empty() {
                    trace!("Delete cluster waited and no clusters were found");
                    break;
                }
                match db_clusters.first().unwrap().status() {
                    Some("Deleting") => continue,
                    Some(status) => {
                        info!("Attempting to delete but clusters is in {status}");
                        continue;
                    }
                    None => {
                        warn!("No status for DB cluster");
                        break;
                    }
                }
            }
        }

        // Delete the DB cluster parameter group. rds.DeleteDbClusterParameterGroup.
```

```
        let delete_db_cluster_parameter_group = self
            .rds
            .delete_db_cluster_parameter_group(
                self.db_cluster_parameter_group
                    .map(|g| {
                        g.db_cluster_parameter_group_name
                            .unwrap_or_else(||
 DB_CLUSTER_PARAMETER_GROUP_NAME.to_string())
                    })
                    .as_deref()
                    .expect("cluster parameter group name"),
            )
            .await;
        if let Err(error) = delete_db_cluster_parameter_group {
            clean_up_errors.push(ScenarioError::new(
                "Failed to delete the db cluster parameter group",
                &error,
            ))
        }

        if clean_up_errors.is_empty() {
            Ok(())
        } else {
            Err(clean_up_errors)
        }
    }
    // snippet-end:[rust.aurora.clean_up.usage]
}

#[cfg(test)]
pub mod tests;
```

Testes da biblioteca usando automocks em torno do wrapper do RDS Client.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use crate::rds::MockRdsImpl;

use super::*;

use std::io::{Error, ErrorKind};
```

```
use assert_matches::assert_matches;
use aws_sdk_rds::{
    error::SdkError,
    operation::{
        create_db_cluster::{CreateDBClusterError, CreateDbClusterOutput},
        create_db_cluster_parameter_group::CreateDBClusterParameterGroupError,
        create_db_cluster_snapshot::{CreateDBClusterSnapshotError,
 CreateDbClusterSnapshotOutput},
        create_db_instance::{CreateDBInstanceError, CreateDbInstanceOutput},
        delete_db_cluster::DeleteDbClusterOutput,
        delete_db_cluster_parameter_group::DeleteDbClusterParameterGroupOutput,
        delete_db_instance::DeleteDbInstanceOutput,
        describe_db_cluster_endpoints::DescribeDbClusterEndpointsOutput,
        describe_db_cluster_parameters::{
            DescribeDBClusterParametersError, DescribeDbClusterParametersOutput,
        },
        describe_db_clusters::{DescribeDBClustersError, DescribeDbClustersOutput},
        describe_db_engine_versions::{
            DescribeDBEngineVersionsError, DescribeDbEngineVersionsOutput,
        },
        describe_db_instances::{DescribeDBInstancesError,
 DescribeDbInstancesOutput},

 describe_orderable_db_instance_options::DescribeOrderableDBInstanceOptionsError,
        modify_db_cluster_parameter_group::{
            ModifyDBClusterParameterGroupError, ModifyDbClusterParameterGroupOutput,
        },
    },
    types::{
        error::DbParameterGroupAlreadyExistsFault, DbClusterEndpoint,
 DbEngineVersion,
        OrderableDbInstanceOption,
    },
};
use aws_smithy_runtime_api::http::{Response, StatusCode};
use aws_smithy_types::body::SdkBody;
use mockall::predicate::eq;
use secrecy::ExposeSecret;

// snippet-start:[rust.aurora.set_engine.test]
#[tokio::test]
async fn test_scenario_set_engine() {
    let mut mock_rds = MockRdsImpl::default();
```

```
    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert_eq!(set_engine, Ok(()));
    assert_eq!(Some("aurora-mysql"), scenario.engine_family.as_deref());
    assert_eq!(Some("aurora-mysql8.0"), scenario.engine_version.as_deref());
}

#[tokio::test]
async fn test_scenario_set_engine_not_create() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .with(
            eq("RustSDKCodeExamplesDBParameterGroup"),
            eq("Parameter Group created by Rust SDK Code Example"),
            eq("aurora-mysql"),
        )
        .return_once(|_, _, _|
 Ok(CreateDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert!(set_engine.is_err());
}
```

```
#[tokio::test]
async fn test_scenario_set_engine_param_group_exists() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .withf(|_, _, _| true)
        .return_once(|_, _, _| {
            Err(SdkError::service_error(

 CreateDBClusterParameterGroupError::DbParameterGroupAlreadyExistsFault(
                    DbParameterGroupAlreadyExistsFault::builder().build(),
                ),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);

    let set_engine = scenario.set_engine("aurora-mysql", "aurora-mysql8.0").await;

    assert!(set_engine.is_err());
}
// snippet-end:[rust.aurora.set_engine.test]

// snippet-start:[rust.aurora.get_engines.test]
#[tokio::test]
async fn test_scenario_get_engines() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Ok(DescribeDbEngineVersionsOutput::builder()
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f1")
                        .engine_version("f1a")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
```

```
                        .db_parameter_group_family("f1")
                        .engine_version("f1b")
                        .build(),
                )
                .db_engine_versions(
                    DbEngineVersion::builder()
                        .db_parameter_group_family("f2")
                        .engine_version("f2a")
                        .build(),
                )
                .db_engine_versions(DbEngineVersion::builder().build())
                .build())
        });

    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;

    assert_eq!(
        versions_map,
        Ok(HashMap::from([
            ("f1".into(), vec!["f1a".into(), "f1b".into()]),
            ("f2".into(), vec!["f2a".into()])
        ]))
    );
}

#[tokio::test]
async fn test_scenario_get_engines_failed() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_engine_versions()
        .with(eq("aurora-mysql"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBEngineVersionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_engine_versions error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });
```

```
    let scenario = AuroraScenario::new(mock_rds);

    let versions_map = scenario.get_engines().await;
    assert_matches!(
        versions_map,
        Err(ScenarioError { message, context: _ }) if message == "Failed to retrieve
 DB Engine Versions"
    );
}
// snippet-end:[rust.aurora.get_engines.test]

// snippet-start:[rust.aurora.get_instance_classes.test]
#[tokio::test]
async fn test_scenario_get_instance_classes() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Ok(vec![
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t1")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t2")
                    .build(),
                OrderableDbInstanceOption::builder()
                    .db_instance_class("t3")
                    .build(),
            ])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario
```

```
        .set_engine("aurora-mysql", "aurora-mysql8.0")
        .await
        .expect("set engine");

    let instance_classes = scenario.get_instance_classes().await;

    assert_eq!(
        instance_classes,
        Ok(vec!["t1".into(), "t2".into(), "t3".into()])
    );
}

#[tokio::test]
async fn test_scenario_get_instance_classes_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_orderable_db_instance_options()
        .with(eq("aurora-mysql"), eq("aurora-mysql8.0"))
        .return_once(|_, _| {
            Err(SdkError::service_error(

 DescribeOrderableDBInstanceOptionsError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_orderable_db_instance_options_error",
                )),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_family = Some("aurora-mysql".into());
    scenario.engine_version = Some("aurora-mysql8.0".into());

    let instance_classes = scenario.get_instance_classes().await;

    assert_matches!(
        instance_classes,
        Err(ScenarioError {message, context: _}) if message == "Could not get
 available instance classes"
    );
}
// snippet-end:[rust.aurora.get_instance_classes.test]
```

```
// snippet-start:[rust.aurora.get_cluster.test]
#[tokio::test]
async fn test_scenario_get_cluster() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;

    assert!(cluster.is_ok());
}

#[tokio::test]
async fn test_scenario_get_cluster_missing_cluster() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| Ok(DescribeDbClustersOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;
```

```
    assert_matches!(cluster, Err(ScenarioError { message, context: _ }) if message
 == "Did not find the cluster");
}

#[tokio::test]
async fn test_scenario_get_cluster_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster_parameter_group()
        .return_once(|_, _, _| {
            Ok(CreateDbClusterParameterGroupOutput::builder()

 .db_cluster_parameter_group(DbClusterParameterGroup::builder().build())
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_clusters_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let cluster = scenario.get_cluster().await;

    assert_matches!(cluster, Err(ScenarioError { message, context: _ }) if message
 == "Failed to get cluster");
}
// snippet-end:[rust.aurora.get_cluster.test]

#[tokio::test]
async fn test_scenario_connection_string() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
```

```
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .endpoint("test_endpoint")
                        .port(3306)
                        .master_username("test_username")
                        .build(),
                )
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let connection_string = scenario.connection_string().await;

    assert_eq!(
        connection_string,
        Ok("mysql -h test_endpoint -P 3306 -u test_username -p".into())
    );
}

// snippet-start:[rust.aurora.cluster_parameters.test]
#[tokio::test]
async fn test_scenario_cluster_parameters() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Ok(vec![DescribeDbClusterParametersOutput::builder()
                .parameters(Parameter::builder().parameter_name("a").build())
                .parameters(Parameter::builder().parameter_name("b").build())
                .parameters(
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("c").build())
                .parameters(
                    Parameter::builder()
```

```
                        .parameter_name("auto_increment_increment")
                        .build(),
                )
                .parameters(Parameter::builder().parameter_name("d").build())
                .build()])
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());

    let params = scenario.cluster_parameters().await.expect("cluster params");
    let names: Vec<String> = params.into_iter().map(|p| p.name).collect();
    assert_eq!(
        names,
        vec!["auto_increment_offset", "auto_increment_increment"]
    );
}

#[tokio::test]
async fn test_scenario_cluster_parameters_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_describe_db_cluster_parameters()
        .with(eq("RustSDKCodeExamplesDBParameterGroup"))
        .return_once(|_| {
            Err(SdkError::service_error(
                DescribeDBClusterParametersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe_db_cluster_parameters_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("RustSDKCodeExamplesDBCluster".into());
    let params = scenario.cluster_parameters().await;
    assert_matches!(params, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to retrieve parameters for RustSDKCodeExamplesDBParameterGroup");
}
// snippet-end:[rust.aurora.cluster_parameters.test]

// snippet-start:[rust.aurora.update_auto_increment.test]
```

```
#[tokio::test]
async fn test_scenario_update_auto_increment() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .withf(|name, params| {
            assert_eq!(name, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(
                params,
                &vec![
                    Parameter::builder()
                        .parameter_name("auto_increment_offset")
                        .parameter_value("10")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                    Parameter::builder()
                        .parameter_name("auto_increment_increment")
                        .parameter_value("20")
                        .apply_method(aws_sdk_rds::types::ApplyMethod::Immediate)
                        .build(),
                ]
            );
            true
        })
        .return_once(|_, _|
 Ok(ModifyDbClusterParameterGroupOutput::builder().build()));

    let scenario = AuroraScenario::new(mock_rds);

    scenario
        .update_auto_increment(10, 20)
        .await
        .expect("update auto increment");
}

#[tokio::test]
async fn test_scenario_update_auto_increment_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_modify_db_cluster_parameter_group()
        .return_once(|_, _| {
            Err(SdkError::service_error(
```

```
                ModifyDBClusterParameterGroupError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "modify_db_cluster_parameter_group_error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let scenario = AuroraScenario::new(mock_rds);

    let update = scenario.update_auto_increment(10, 20).await;
    assert_matches!(update, Err(ScenarioError { message, context: _}) if message ==
 "Failed to modify cluster parameter group");
}
// snippet-end:[rust.aurora.update_auto_increment.test]

// snippet-start:[rust.aurora.start_cluster_and_instance.test]
#[tokio::test]
async fn test_start_cluster_and_instance() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
```

```
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_describe_db_instance()
        .with(eq("RustSDKCodeExamplesDBInstance"))
        .return_once(|name| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_instance_identifier(name)
                        .db_instance_status("Available")
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()
```

```
 .db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
        assert!(scenario
            .password
            .replace(SecretString::new("BAD SECRET".into()))
            .unwrap()
            .expose_secret()
            .is_empty());
        assert_eq!(
            scenario.db_cluster_identifier,
            Some("RustSDKCodeExamplesDBCluster".into())
        );
    });
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Err(SdkError::service_error(
                CreateDBClusterError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db cluster error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
```

```
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _}) if message ==
 "Failed to create DB Cluster with cluster group")
}

#[tokio::test]
async fn test_start_cluster_and_instance_cluster_create_missing_id() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .return_once(|_, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context:_ }) if message ==
 "Created DB Cluster missing Identifier");
}

#[tokio::test]
async fn test_start_cluster_and_instance_instance_create_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
```

```
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .return_once(|_, _, _, _| {
            Err(SdkError::service_error(
                CreateDBInstanceError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create db instance error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    let create = scenario.start_cluster_and_instance().await;
    assert_matches!(create, Err(ScenarioError { message, context: _ }) if message ==
 "Failed to create Instance in DB Cluster")
}

#[tokio::test]
async fn test_start_cluster_and_instance_wait_hiccup() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_create_db_cluster()
        .withf(|id, params, engine, version, username, password| {
```

```
            assert_eq!(id, "RustSDKCodeExamplesDBCluster");
            assert_eq!(params, "RustSDKCodeExamplesDBParameterGroup");
            assert_eq!(engine, "aurora-mysql");
            assert_eq!(version, "aurora-mysql8.0");
            assert_eq!(username, "test username");
            assert_eq!(password.expose_secret(), "test password");
            true
        })
        .return_once(|id, _, _, _, _, _| {
            Ok(CreateDbClusterOutput::builder()
                .db_cluster(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds
        .expect_create_db_instance()
        .withf(|cluster, name, class, engine| {
            assert_eq!(cluster, "RustSDKCodeExamplesDBCluster");
            assert_eq!(name, "RustSDKCodeExamplesDBInstance");
            assert_eq!(class, "m5.large");
            assert_eq!(engine, "aurora-mysql");
            true
        })
        .return_once(|cluster, name, class, _| {
            Ok(CreateDbInstanceOutput::builder()
                .db_instance(
                    DbInstance::builder()
                        .db_cluster_identifier(cluster)
                        .db_instance_identifier(name)
                        .db_instance_class(class)
                        .build(),
                )
                .build())
        });

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe cluster error",
```

```
                )),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        })
        .with(eq("RustSDKCodeExamplesDBCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(DbCluster::builder().db_cluster_identifier(id).build())
                .build())
        });

    mock_rds.expect_describe_db_instance().return_once(|name| {
        Ok(DescribeDbInstancesOutput::builder()
            .db_instances(
                DbInstance::builder()
                    .db_instance_identifier(name)
                    .db_instance_status("Available")
                    .build(),
            )
            .build())
    });

    mock_rds
        .expect_describe_db_cluster_endpoints()
        .return_once(|_| {
            Ok(DescribeDbClusterEndpointsOutput::builder()

.db_cluster_endpoints(DbClusterEndpoint::builder().status("available").build())
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.engine_version = Some("aurora-mysql8.0".into());
    scenario.instance_class = Some("m5.large".into());
    scenario.username = Some("test username".into());
    scenario.password = Some(SecretString::new("test password".into()));

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let create = scenario.start_cluster_and_instance().await;
        assert!(create.is_ok());
    });
```

```
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::advance(Duration::from_secs(1)).await;
    tokio::time::resume();
    let _ = assertions.await;
}
// snippet-end:[rust.aurora.start_cluster_and_instance.test]

// snippet-start:[rust.aurora.clean_up.test]
#[tokio::test]
async fn test_scenario_clean_up() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| Ok(DescribeDbInstancesOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
```

```
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| Ok(DescribeDbClustersOutput::builder().build()));

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_ok());
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
Cluster
    tokio::time::resume();
```

```
    let _ = assertions.await;
}

#[tokio::test]
async fn test_scenario_clean_up_errors() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_delete_db_instance()
        .with(eq("MockInstance"))
        .return_once(|_| Ok(DeleteDbInstanceOutput::builder().build()));

    mock_rds
        .expect_describe_db_instances()
        .with()
        .times(1)
        .returning(|| {
            Ok(DescribeDbInstancesOutput::builder()
                .db_instances(
                    DbInstance::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_instance_status("Deleting")
                        .build(),
                )
                .build())
        })
        .with()
        .times(1)
        .returning(|| {
            Err(SdkError::service_error(
                DescribeDBInstancesError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db instances error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster()
        .with(eq("MockCluster"))
        .return_once(|_| Ok(DeleteDbClusterOutput::builder().build()));

    mock_rds
```

```
        .expect_describe_db_clusters()
        .with(eq("MockCluster"))
        .times(1)
        .returning(|id| {
            Ok(DescribeDbClustersOutput::builder()
                .db_clusters(
                    DbCluster::builder()
                        .db_cluster_identifier(id)
                        .status("Deleting")
                        .build(),
                )
                .build())
        })
        .with(eq("MockCluster"))
        .times(1)
        .returning(|_| {
            Err(SdkError::service_error(
                DescribeDBClustersError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "describe db clusters error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    mock_rds
        .expect_delete_db_cluster_parameter_group()
        .with(eq("MockParamGroup"))
        .return_once(|_|
Ok(DeleteDbClusterParameterGroupOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some(String::from("MockCluster"));
    scenario.db_instance_identifier = Some(String::from("MockInstance"));
    scenario.db_cluster_parameter_group = Some(
        DbClusterParameterGroup::builder()
            .db_cluster_parameter_group_name("MockParamGroup")
            .build(),
    );

    tokio::time::pause();
    let assertions = tokio::spawn(async move {
        let clean_up = scenario.clean_up().await;
        assert!(clean_up.is_err());
```

```
        let errs = clean_up.unwrap_err();
        assert_eq!(errs.len(), 2);
        assert_matches!(errs.get(0), Some(ScenarioError {message, context: _}) if
 message == "Failed to check instance state during deletion");
        assert_matches!(errs.get(1), Some(ScenarioError {message, context: _}) if
 message == "Failed to check cluster state during deletion");
    });

    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Instances
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for first Describe
 Cluster
    tokio::time::advance(Duration::from_secs(1)).await; // Wait for second Describe
 Cluster
    tokio::time::resume();
    let _ = assertions.await;
}
// snippet-end:[rust.aurora.clean_up.test]

// snippet-start:[rust.aurora.snapshot.test]
#[tokio::test]
async fn test_scenario_snapshot() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _| {
            Ok(CreateDbClusterSnapshotOutput::builder()
                .db_cluster_snapshot(
                    DbClusterSnapshot::builder()
                        .db_cluster_identifier("MockCluster")
                        .db_cluster_snapshot_identifier("MockCluster_MockSnapshot")
                        .build(),
                )
                .build())
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
```

```
    assert!(create_snapshot.is_ok());
}

#[tokio::test]
async fn test_scenario_snapshot_error() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _| {
            Err(SdkError::service_error(
                CreateDBClusterSnapshotError::unhandled(Box::new(Error::new(
                    ErrorKind::Other,
                    "create snapshot error",
                ))),
                Response::new(StatusCode::try_from(400).unwrap(), SdkBody::empty()),
            ))
        });

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
    assert_matches!(create_snapshot, Err(ScenarioError { message, context: _}) if
 message == "Failed to create snapshot");
}

#[tokio::test]
async fn test_scenario_snapshot_invalid() {
    let mut mock_rds = MockRdsImpl::default();

    mock_rds
        .expect_snapshot_cluster()
        .with(eq("MockCluster"), eq("MockCluster_MockSnapshot"))
        .times(1)
        .return_once(|_, _| Ok(CreateDbClusterSnapshotOutput::builder().build()));

    let mut scenario = AuroraScenario::new(mock_rds);
    scenario.db_cluster_identifier = Some("MockCluster".into());
    let create_snapshot = scenario.snapshot("MockSnapshot").await;
    assert_matches!(create_snapshot, Err(ScenarioError { message, context: _}) if
 message == "Missing Snapshot");
}
```

```
// snippet-end:[rust.aurora.snapshot.test]
```

Um binário para executar o cenário do início ao fim usando o inquiridor para que o usuário possa tomar algumas decisões.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::fmt::Display;

use anyhow::anyhow;
use aurora_code_examples::{
    aurora_scenario::{AuroraScenario, ScenarioError},
    rds::Rds as RdsClient,
};
use aws_sdk_rds::Client;
use inquire::{validator::StringValidator, CustomUserError};
use secrecy::SecretString;
use tracing::warn;

#[derive(Default, Debug)]
struct Warnings(Vec<String>);

impl Warnings {
    fn new() -> Self {
        Warnings(Vec::with_capacity(5))
    }

    fn push(&mut self, warning: &str, error: ScenarioError) {
        let formatted = format!("{warning}: {error}");
        warn!("{formatted}");
        self.0.push(formatted);
    }

    fn is_empty(&self) -> bool {
        self.0.is_empty()
    }
}

impl Display for Warnings {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "Warnings:")?;
```

```
        for warning in &self.0 {
            writeln!(f, "{: >4}- {warning}", "")?;
        }
        Ok(())
    }
}

fn select(
    prompt: &str,
    choices: Vec<String>,
    error_message: &str,
) -> Result<String, anyhow::Error> {
    inquire::Select::new(prompt, choices)
        .prompt()
        .map_err(|error| anyhow!("{error_message}: {error}"))
}

// Prepare the Aurora Scenario. Prompt for several settings that are optional to the
 Scenario, but that the user should choose for the demo.
// This includes the engine, engine version, and instance class.
async fn prepare_scenario(rds: RdsClient) -> Result<AuroraScenario, anyhow::Error> {
    let mut scenario = AuroraScenario::new(rds);

    // Get available engine families for Aurora MySql.
 rds.DescribeDbEngineVersions(Engine='aurora-mysql') and build a set of the
 'DBParameterGroupFamily' field values. I get {aurora-mysql8.0, aurora-mysql5.7}.
    let available_engines = scenario.get_engines().await;
    if let Err(error) = available_engines {
        return Err(anyhow!("Failed to get available engines: {}", error));
    }
    let available_engines = available_engines.unwrap();

    // Select an engine family and create a custom DB cluster parameter group.
 rds.CreateDbClusterParameterGroup(DBParameterGroupFamily='aurora-mysql8.0')
    let engine = select(
        "Select an Aurora engine family",
        available_engines.keys().cloned().collect::<Vec<String>>(),
        "Invalid engine selection",
    )?;

    let version = select(
        format!("Select an Aurora engine version for {engine}").as_str(),
        available_engines.get(&engine).cloned().unwrap_or_default(),
        "Invalid engine version selection",
```

```
    )?;

    let set_engine = scenario.set_engine(engine.as_str(), version.as_str()).await;
    if let Err(error) = set_engine {
        return Err(anyhow!("Could not set engine: {}", error));
    }

    let instance_classes = scenario.get_instance_classes().await;
    match instance_classes {
        Ok(classes) => {
            let instance_class = select(
                format!("Select an Aurora instance class for {engine}").as_str(),
                classes,
                "Invalid instance class selection",
            )?;
            scenario.set_instance_class(Some(instance_class))
        }
        Err(err) => return Err(anyhow!("Failed to get instance classes for engine:
 {err}")),
    }

    Ok(scenario)
}

// Prepare the cluster, creating a custom parameter group overriding some group
 parameters based on user input.
async fn prepare_cluster(scenario: &mut AuroraScenario, warnings: &mut Warnings) ->
 Result<(), ()> {
    show_parameters(scenario, warnings).await;

    let offset = prompt_number_or_default(warnings, "auto_increment_offset", 5);
    let increment = prompt_number_or_default(warnings, "auto_increment_increment",
 3);

    // Modify both the auto_increment_offset and auto_increment_increment parameters
 in one call in the custom parameter group. Set their ParameterValue fields to a new
 allowable value. rds.ModifyDbClusterParameterGroup.
    let update_auto_increment = scenario.update_auto_increment(offset,
 increment).await;

    if let Err(error) = update_auto_increment {
        warnings.push("Failed to update auto increment", error);
        return Err(());
    }
```

```
   // Get and display the updated parameters. Specify Source of 'user' to get just
the modified parameters. rds.DescribeDbClusterParameters(Source='user')
   show_parameters(scenario, warnings).await;

   let username = inquire::Text::new("Username for the database (default
'testuser')")
       .with_default("testuser")
       .with_initial_value("testuser")
       .prompt();

   if let Err(error) = username {
       warnings.push(
           "Failed to get username, using default",
           ScenarioError::with(format!("Error from inquirer: {error}")),
       );
       return Err(());
   }
   let username = username.unwrap();

   let password = inquire::Text::new("Password for the database (minimum 8
characters)")
       .with_validator(|i: &str| {
           if i.len() >= 8 {
               Ok(inquire::validator::Validation::Valid)
           } else {
               Ok(inquire::validator::Validation::Invalid(
                   "Password must be at least 8 characters".into(),
               ))
           }
       })
       .prompt();

   let password: Option<SecretString> = match password {
       Ok(password) => Some(SecretString::from(password)),
       Err(error) => {
           warnings.push(
               "Failed to get password, using none (and not starting a DB)",
               ScenarioError::with(format!("Error from inquirer: {error}")),
           );
           return Err(());
       }
   };
```

```
    scenario.set_login(Some(username), password);

    Ok(())
}

// Start a single instance in the cluster,
async fn run_instance(scenario: &mut AuroraScenario) -> Result<(), ScenarioError> {
    // Create an Aurora DB cluster database cluster that contains a MySql database
 and uses the parameter group you created.
    // Create a database instance in the cluster.
    // Wait for DB instance to be ready. Call rds.DescribeDbInstances and check for
 DBInstanceStatus == 'available'.
    scenario.start_cluster_and_instance().await?;

    let connection_string = scenario.connection_string().await?;

    println!("Database ready: {connection_string}",);

    let _ = inquire::Text::new("Use the database with the connection string. When
 you're finished, press enter key to continue.").prompt();

    // Create a snapshot of the DB cluster. rds.CreateDbClusterSnapshot.
    // Wait for the snapshot to create. rds.DescribeDbClusterSnapshots until Status
 == 'available'.
    let snapshot_name = inquire::Text::new("Provide a name for the snapshot")
        .prompt()
        .unwrap_or(String::from("ScenarioRun"));
    let snapshot = scenario.snapshot(snapshot_name.as_str()).await?;
    println!(
        "Snapshot is available: {}",
        snapshot.db_cluster_snapshot_arn().unwrap_or("Missing ARN")
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), anyhow::Error> {
    tracing_subscriber::fmt::init();
    let sdk_config = aws_config::from_env().load().await;
    let client = Client::new(&sdk_config);
    let rds = RdsClient::new(client);
    let mut scenario = prepare_scenario(rds).await?;
```

```
    // At this point, the scenario has things in AWS and needs to get cleaned up.
    let mut warnings = Warnings::new();

    if prepare_cluster(&mut scenario, &mut warnings).await.is_ok() {
        println!("Configured database cluster, starting an instance.");
        if let Err(err) = run_instance(&mut scenario).await {
            warnings.push("Problem running instance", err);
        }
    }

    // Clean up the instance, cluster, and parameter group, waiting for the instance
 and cluster to delete before moving on.
    let clean_up = scenario.clean_up().await;
    if let Err(errors) = clean_up {
        for error in errors {
            warnings.push("Problem cleaning up scenario", error);
        }
    }

    if warnings.is_empty() {
        Ok(())
    } else {
        println!("There were problems running the scenario:");
        println!("{warnings}");
        Err(anyhow!("There were problems running the scenario"))
    }
}

#[derive(Clone)]
struct U8Validator {}
impl StringValidator for U8Validator {
    fn validate(&self, input: &str) -> Result<inquire::validator::Validation,
 CustomUserError> {
        if input.parse::<u8>().is_err() {
            Ok(inquire::validator::Validation::Invalid(
                "Can't parse input as number".into(),
            ))
        } else {
            Ok(inquire::validator::Validation::Valid)
        }
    }
}

async fn show_parameters(scenario: &AuroraScenario, warnings: &mut Warnings) {
```

```
    let parameters = scenario.cluster_parameters().await;

    match parameters {
        Ok(parameters) => {
            println!("Current parameters");
            for parameter in parameters {
                println!("\t{parameter}");
            }
        }
        Err(error) => warnings.push("Could not find cluster parameters", error),
    }
}

fn prompt_number_or_default(warnings: &mut Warnings, name: &str, default: u8) -> u8
 {
    let input = inquire::Text::new(format!("Updated {name}:").as_str())
        .with_validator(U8Validator {})
        .prompt();

    match input {
        Ok(increment) => match increment.parse::<u8>() {
            Ok(increment) => increment,
            Err(error) => {
                warnings.push(
                    format!("Invalid updated {name} (using {default}
 instead)").as_str(),
                    ScenarioError::with(format!("{error}")),
                );
                default
            }
        },
        Err(error) => {
            warnings.push(
                format!("Invalid updated {name} (using {default}
 instead)").as_str(),
                ScenarioError::with(format!("{error}")),
            );
            default
        }
    }
}
```

Um wrapper do serviço Amazon RDS que permite automocking para testes.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use aws_sdk_rds::{
    error::SdkError,
    operation::{
        create_db_cluster::{CreateDBClusterError, CreateDbClusterOutput},
        create_db_cluster_parameter_group::CreateDBClusterParameterGroupError,
        create_db_cluster_parameter_group::CreateDbClusterParameterGroupOutput,
        create_db_cluster_snapshot::{CreateDBClusterSnapshotError,
 CreateDbClusterSnapshotOutput},
        create_db_instance::{CreateDBInstanceError, CreateDbInstanceOutput},
        delete_db_cluster::{DeleteDBClusterError, DeleteDbClusterOutput},
        delete_db_cluster_parameter_group::{
            DeleteDBClusterParameterGroupError, DeleteDbClusterParameterGroupOutput,
        },
        delete_db_instance::{DeleteDBInstanceError, DeleteDbInstanceOutput},
        describe_db_cluster_endpoints::{
            DescribeDBClusterEndpointsError, DescribeDbClusterEndpointsOutput,
        },
        describe_db_cluster_parameters::{
            DescribeDBClusterParametersError, DescribeDbClusterParametersOutput,
        },
        describe_db_clusters::{DescribeDBClustersError, DescribeDbClustersOutput},
        describe_db_engine_versions::{
            DescribeDBEngineVersionsError, DescribeDbEngineVersionsOutput,
        },
        describe_db_instances::{DescribeDBInstancesError,
 DescribeDbInstancesOutput},

 describe_orderable_db_instance_options::DescribeOrderableDBInstanceOptionsError,
        modify_db_cluster_parameter_group::{
            ModifyDBClusterParameterGroupError, ModifyDbClusterParameterGroupOutput,
        },
    },
    types::{OrderableDbInstanceOption, Parameter},
    Client as RdsClient,
};
use secrecy::{ExposeSecret, SecretString};

#[cfg(test)]
use mockall::automock;
```

```
#[cfg(test)]
pub use MockRdsImpl as Rds;
#[cfg(not(test))]
pub use RdsImpl as Rds;

pub struct RdsImpl {
    pub inner: RdsClient,
}

#[cfg_attr(test, automock)]
impl RdsImpl {
    pub fn new(inner: RdsClient) -> Self {
        RdsImpl { inner }
    }

    // snippet-start:[rust.aurora.describe_db_engine_versions.wrapper]
    pub async fn describe_db_engine_versions(
        &self,
        engine: &str,
    ) -> Result<DescribeDbEngineVersionsOutput,
 SdkError<DescribeDBEngineVersionsError>> {
        self.inner
            .describe_db_engine_versions()
            .engine(engine)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_engine_versions.wrapper]

    // snippet-start:[rust.aurora.describe_orderable_db_instance_options.wrapper]
    pub async fn describe_orderable_db_instance_options(
        &self,
        engine: &str,
        engine_version: &str,
    ) -> Result<Vec<OrderableDbInstanceOption>,
 SdkError<DescribeOrderableDBInstanceOptionsError>>
    {
        self.inner
            .describe_orderable_db_instance_options()
            .engine(engine)
            .engine_version(engine_version)
            .into_paginator()
            .items()
```

```
            .send()
            .try_collect()
            .await
    }
    // snippet-end:[rust.aurora.describe_orderable_db_instance_options.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster_parameter_group.wrapper]
    pub async fn create_db_cluster_parameter_group(
        &self,
        name: &str,
        description: &str,
        family: &str,
    ) -> Result<CreateDbClusterParameterGroupOutput,
SdkError<CreateDBClusterParameterGroupError>>
    {
        self.inner
            .create_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .description(description)
            .db_parameter_group_family(family)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_cluster_parameter_group.wrapper]

    // snippet-start:[rust.aurora.describe_db_clusters.wrapper]
    pub async fn describe_db_clusters(
        &self,
        id: &str,
    ) -> Result<DescribeDbClustersOutput, SdkError<DescribeDBClustersError>> {
        self.inner
            .describe_db_clusters()
            .db_cluster_identifier(id)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_clusters.wrapper]

    // snippet-start:[rust.aurora.describe_db_cluster_parameters.wrapper]
    pub async fn describe_db_cluster_parameters(
        &self,
        name: &str,
    ) -> Result<Vec<DescribeDbClusterParametersOutput>,
SdkError<DescribeDBClusterParametersError>>
```

```
    {
        self.inner
            .describe_db_cluster_parameters()
            .db_cluster_parameter_group_name(name)
            .into_paginator()
            .send()
            .try_collect()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_cluster_parameters.wrapper]

    // snippet-start:[rust.aurora.modify_db_cluster_parameter_group.wrapper]
    pub async fn modify_db_cluster_parameter_group(
        &self,
        name: &str,
        parameters: Vec<Parameter>,
    ) -> Result<ModifyDbClusterParameterGroupOutput,
SdkError<ModifyDBClusterParameterGroupError>>
    {
        self.inner
            .modify_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .set_parameters(Some(parameters))
            .send()
            .await
    }
    // snippet-end:[rust.aurora.modify_db_cluster_parameter_group.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster.wrapper]
    pub async fn create_db_cluster(
        &self,
        name: &str,
        parameter_group: &str,
        engine: &str,
        version: &str,
        username: &str,
        password: SecretString,
    ) -> Result<CreateDbClusterOutput, SdkError<CreateDBClusterError>> {
        self.inner
            .create_db_cluster()
            .db_cluster_identifier(name)
            .db_cluster_parameter_group_name(parameter_group)
            .engine(engine)
            .engine_version(version)
```

```
            .master_username(username)
            .master_user_password(password.expose_secret())
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_cluster.wrapper]

    // snippet-start:[rust.aurora.create_db_instance.wrapper]
    pub async fn create_db_instance(
        &self,
        cluster_name: &str,
        instance_name: &str,
        instance_class: &str,
        engine: &str,
    ) -> Result<CreateDbInstanceOutput, SdkError<CreateDBInstanceError>> {
        self.inner
            .create_db_instance()
            .db_cluster_identifier(cluster_name)
            .db_instance_identifier(instance_name)
            .db_instance_class(instance_class)
            .engine(engine)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_instance.wrapper]

    // snippet-start:[rust.aurora.describe_db_instance.wrapper]
    pub async fn describe_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner
            .describe_db_instances()
            .db_instance_identifier(instance_identifier)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_instance.wrapper]

    // snippet-start:[rust.aurora.create_db_cluster_snapshot.wrapper]
    pub async fn snapshot_cluster(
        &self,
        db_cluster_identifier: &str,
        snapshot_name: &str,
```

```
    ) -> Result<CreateDbClusterSnapshotOutput,
SdkError<CreateDBClusterSnapshotError>> {
        self.inner
            .create_db_cluster_snapshot()
            .db_cluster_identifier(db_cluster_identifier)
            .db_cluster_snapshot_identifier(snapshot_name)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.create_db_cluster_snapshot.wrapper]

    // snippet-start:[rust.aurora.describe_db_instances.wrapper]
    pub async fn describe_db_instances(
        &self,
    ) -> Result<DescribeDbInstancesOutput, SdkError<DescribeDBInstancesError>> {
        self.inner.describe_db_instances().send().await
    }
    // snippet-end:[rust.aurora.describe_db_instances.wrapper]

    // snippet-start:[rust.aurora.describe_db_cluster_endpoints.wrapper]
    pub async fn describe_db_cluster_endpoints(
        &self,
        cluster_identifier: &str,
    ) -> Result<DescribeDbClusterEndpointsOutput,
SdkError<DescribeDBClusterEndpointsError>> {
        self.inner
            .describe_db_cluster_endpoints()
            .db_cluster_identifier(cluster_identifier)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.describe_db_cluster_endpoints.wrapper]

    // snippet-start:[rust.aurora.delete_db_instance.wrapper]
    pub async fn delete_db_instance(
        &self,
        instance_identifier: &str,
    ) -> Result<DeleteDbInstanceOutput, SdkError<DeleteDBInstanceError>> {
        self.inner
            .delete_db_instance()
            .db_instance_identifier(instance_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
```

```
    }
    // snippet-end:[rust.aurora.delete_db_instance.wrapper]

    // snippet-start:[rust.aurora.delete_db_cluster.wrapper]
    pub async fn delete_db_cluster(
        &self,
        cluster_identifier: &str,
    ) -> Result<DeleteDbClusterOutput, SdkError<DeleteDBClusterError>> {
        self.inner
            .delete_db_cluster()
            .db_cluster_identifier(cluster_identifier)
            .skip_final_snapshot(true)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.delete_db_cluster.wrapper]

    // snippet-start:[rust.aurora.delete_db_cluster_parameter_group.wrapper]
    pub async fn delete_db_cluster_parameter_group(
        &self,
        name: &str,
    ) -> Result<DeleteDbClusterParameterGroupOutput,
 SdkError<DeleteDBClusterParameterGroupError>>
    {
        self.inner
            .delete_db_cluster_parameter_group()
            .db_cluster_parameter_group_name(name)
            .send()
            .await
    }
    // snippet-end:[rust.aurora.delete_db_cluster_parameter_group.wrapper]
}
```

O Cargo.toml com dependências usadas neste cenário.

```
[package]
name = "aurora-code-examples"
authors = [
  "David Souther <dpsouth@amazon.com>",
]
edition = "2021"
version = "0.1.0"
```

```
# See more keys and their definitions at https://doc.rust-lang.org/cargo/reference/
manifest.html

[dependencies]
anyhow = "1.0.75"
assert_matches = "1.5.0"
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-smithy-types = { version = "1.0.1" }
aws-smithy-runtime-api = { version = "1.0.1" }
aws-sdk-rds = { version = "1.3.0" }
inquire = "0.6.2"
mockall = "0.11.4"
phf = { version = "0.11.2", features = ["std", "macros"] }
sdk-examples-test-utils = { path = "../../test-utils" }
secrecy = "0.8.0"
tokio = { version = "1.20.1", features = ["full", "test-util"] }
tracing = "0.1.37"
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateDBCluster
  - Criado B ClusterParameterGroup
  - Criado B ClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - Banco de dados excluído ClusterParameterGroup
  - DeleteDBInstance
  - DB descrito ClusterParameterGroups
  - DB descrito ClusterParameters
  - DB descrito ClusterSnapshots
  - DescribeDBClusters
  - DB descrito EngineVersions
  - DescribeDBInstances
  - DescribeOrderableDB InstanceOptions

- Modificar banco de dados ClusterParameterGroup

Exemplos de Auto Scaling usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com Auto Scaling.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello Auto Scaling

O exemplo de código a seguir mostra como começar a usar o Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_groups(client: &Client) -> Result<(), Error> {
    let resp = client.describe_auto_scaling_groups().send().await?;

    println!("Groups:");

    let groups = resp.auto_scaling_groups();

    for group in groups {
        println!(
            "Name:  {}",
```

```
            group.auto_scaling_group_name().unwrap_or("Unknown")
        );
        println!(
            "Arn:   {}",
            group.auto_scaling_group_arn().unwrap_or("unknown"),
        );
        println!("Zones: {:?}", group.availability_zones(),);
        println!();
    }

    println!("Found {} group(s)", groups.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWS SDK for Rust.

Tópicos

- Ações
- Cenários

Ações

Criar um grupo

O exemplo de código a seguir mostra como criar um grupo do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn create_group(client: &Client, name: &str, id: &str) -> Result<(), Error> {
    client
        .create_auto_scaling_group()
```

```
        .auto_scaling_group_name(name)
        .instance_id(id)
        .min_size(1)
        .max_size(5)
        .send()
        .await?;

    println!("Created AutoScaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateAutoScalingGroupreferência da API AWS SDK for Rust.

Excluir um grupo

O exemplo de código a seguir mostra como excluir um grupo do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn delete_group(client: &Client, name: &str, force: bool) -> Result<(), Error>
 {
    client
        .delete_auto_scaling_group()
        .auto_scaling_group_name(name)
        .set_force_delete(if force { Some(true) } else { None })
        .send()
        .await?;

    println!("Deleted Auto Scaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteAutoScalingGroupreferência da API AWS SDK for Rust.

Desabilitar a coleção de métricas para um grupo

O exemplo de código a seguir mostra como desativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        // If this fails it's fine, just means there are extra cloudwatch metrics
events for the scale-down.
        let _ = self
            .autoscaling
            .disable_metrics_collection()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;
```

- Para obter detalhes da API, consulte a DisableMetricsCollectionreferência da API AWS SDK for Rust.

Habilite a coleção de métricas para um grupo

O exemplo de código a seguir mostra como ativar a coleta de CloudWatch métricas para um grupo de Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let enable_metrics_collection = autoscaling
            .enable_metrics_collection()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .granularity("1Minute")
            .set_metrics(Some(vec![
                String::from("GroupMinSize"),
                String::from("GroupMaxSize"),
                String::from("GroupDesiredCapacity"),
                String::from("GroupInServiceInstances"),
                String::from("GroupTotalInstances"),
            ]))
            .send()
            .await;
```

- Para obter detalhes da API, consulte a EnableMetricsCollectionreferência da API AWS SDK for Rust.

Obter informações sobre grupos

O exemplo de código a seguir mostra como obter informação sobre grupos do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_groups(client: &Client) -> Result<(), Error> {
```

```
    let resp = client.describe_auto_scaling_groups().send().await?;

    println!("Groups:");

    let groups = resp.auto_scaling_groups();

    for group in groups {
        println!(
            "Name:  {}",
            group.auto_scaling_group_name().unwrap_or("Unknown")
        );
        println!(
            "Arn:   {}",
            group.auto_scaling_group_arn().unwrap_or("unknown"),
        );
        println!("Zones: {:?}", group.availability_zones(),);
        println!();
    }

    println!("Found {} group(s)", groups.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeAutoScalingGroupsreferência da API AWS SDK for Rust.

Obter informação sobre as instâncias

O exemplo de código a seguir mostra como obter informações sobre instâncias do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn list_instances(&self) -> Result<Vec<String>, ScenarioError> {
```

```
        // The direct way to list instances is by using DescribeAutoScalingGroup's
instances property. However, this returns a Vec<Instance>, as opposed to a
Vec<AutoScalingInstanceDetails>.
        // Ok(self.get_group().await?.instances.unwrap_or_default().map(|i|
i.instance_id.clone().unwrap_or_default()).filter(|id| !id.is_empty()).collect())

        // Alternatively, and for the sake of example, DescribeAutoScalingInstances
returns a list that can be filtered by the client.
        self.autoscaling
            .describe_auto_scaling_instances()
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
            .map(|items| {
                items
                    .into_iter()
                    .filter(|i| {
                        i.auto_scaling_group_name.as_deref()
                            == Some(self.auto_scaling_group_name.as_str())
                    })
                    .map(|i| i.instance_id.unwrap_or_default())
                    .filter(|id| !id.is_empty())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Failed to get list of auto scaling
instances", &err))
    }
```

- Para obter detalhes da API, consulte a DescribeAutoScalingInstancesreferência da API AWS SDK for Rust.

Obter informações sobre atividades de escalabilidade

O exemplo de código a seguir mostra como obter informação sobre atividades do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    pub async fn describe_scenario(&self) -> AutoScalingScenarioDescription {
        let group = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await
            .map(|s| {
                s.auto_scaling_groups()
                    .iter()
                    .map(|s| {
                        format!(
                            "{}: {}",
                            s.auto_scaling_group_name().unwrap_or("Unknown"),
                            s.status().unwrap_or("Unknown")
                        )
                    })
                    .collect::<Vec<String>>()
            })
            .map_err(|e| {
                ScenarioError::new("Failed to describe auto scaling groups for
scenario", &e)
            });

        let instances = self
            .list_instances()
            .await
            .map_err(|e| anyhow!("There was an error listing instances: {e}",));

        // 10. DescribeScalingActivities: list the scaling activities that have
occurred for the group so far.
        //   Bonus: use CloudWatch API to get and show some metrics collected for
the group.
```

```
        //   CW.ListMetrics with Namespace='AWS/AutoScaling' and
Dimensions=[{'Name': 'AutoScalingGroupName', 'Value': }]
        //   CW.GetMetricStatistics with Statistics='Sum'. Start and End times must
be in UTC!
        let activities = self
            .autoscaling
            .describe_scaling_activities()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .into_paginator()
            .items()
            .send()
            .collect::<Result<Vec<_>, _>>()
            .await
            .map_err(|e| {
                anyhow!(
                    "There was an error retrieving scaling activities: {}",
                    DisplayErrorContext(&e)
                )
            });

        AutoScalingScenarioDescription {
            group,
            instances,
            activities,
        }
    }
```

- Para obter detalhes da API, consulte a DescribeScalingActivitiesreferência da API AWS SDK for Rust.

Definir a capacidade desejada de um grupo

O exemplo de código a seguir mostra como definir a capacidade desejada de um grupo de Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   pub async fn scale_desired_capacity(&self, capacity: i32) -> Result<(),
ScenarioError> {
       // 7. SetDesiredCapacity: set desired capacity to 2.
       //   Wait for a second instance to launch.
       let update_group = self
           .autoscaling
           .set_desired_capacity()
           .auto_scaling_group_name(self.auto_scaling_group_name.clone())
           .desired_capacity(capacity)
           .send()
           .await;
       if let Err(err) = update_group {
           return Err(ScenarioError::new(
               format!("Failed to update group to desired capacity
({capacity}))").as_str(),
               &err,
           ));
       }
       Ok(())
   }
```

- Para obter detalhes da API, consulte a SetDesiredCapacityreferência da API AWS SDK for Rust.

Encerrar uma instância em um grupo

O exemplo de código a seguir mostra como encerrar uma instância em um grupo do Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn terminate_some_instance(&self) -> Result<(), ScenarioError> {
    // Retrieve a list of instances in the auto scaling group.
    let auto_scaling_group = self.get_group().await?;
    let instances = auto_scaling_group.instances();
    // Or use other logic to find an instance to terminate.
    let instance = instances.first();
    if let Some(instance) = instance {
        let instance_id = if let Some(instance_id) = instance.instance_id() {
            instance_id
        } else {
            return Err(ScenarioError::with("Missing instance id"));
        };
        let termination = self
            .ec2
            .terminate_instances()
            .instance_ids(instance_id)
            .send()
            .await;
        if let Err(err) = termination {
            Err(ScenarioError::new(
                "There was a problem terminating an instance",
                &err,
            ))
        } else {
            Ok(())
        }
    } else {
        Err(ScenarioError::with("There was no instance to terminate"))
    }
}

async fn get_group(&self) -> Result<AutoScalingGroup, ScenarioError> {
    let describe_auto_scaling_groups = self
        .autoscaling
```

```
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await;

        if let Err(err) = describe_auto_scaling_groups {
            return Err(ScenarioError::new(
                format!(
                    "Failed to get status of autoscaling group {}",
                    self.auto_scaling_group_name.clone()
                )
                .as_str(),
                &err,
            ));
        }

        let describe_auto_scaling_groups_output =
describe_auto_scaling_groups.unwrap();
        let auto_scaling_groups =
describe_auto_scaling_groups_output.auto_scaling_groups();
        let auto_scaling_group = auto_scaling_groups.first();

        if auto_scaling_group.is_none() {
            return Err(ScenarioError::with(format!(
                "Could not find autoscaling group {}",
                self.auto_scaling_group_name.clone()
            )));
        }

        Ok(auto_scaling_group.unwrap().clone())
    }
```

- Para obter detalhes da API, consulte a TerminateInstanceInAutoScalingGroupreferência da API AWS SDK for Rust.

Atualizar um grupo

O exemplo de código a seguir mostra como atualizar a configuração de um grupo de Auto Scaling.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn update_group(client: &Client, name: &str, size: i32) -> Result<(), Error> {
    client
        .update_auto_scaling_group()
        .auto_scaling_group_name(name)
        .max_size(size)
        .send()
        .await?;

    println!("Updated AutoScaling group");

    Ok(())
}
```

- Para obter detalhes da API, consulte a UpdateAutoScalingGroupreferência da API AWS SDK for Rust.

Cenários

Gerenciar grupos e instâncias

O código de exemplo a seguir mostra como:

- Crie um grupo do Auto Scaling do Amazon EC2 com um modelo de execução e zonas de disponibilidade e obtenha informações sobre a execução de instâncias.
- Ative a coleta de CloudWatch métricas da Amazon.
- Atualize a capacidade desejada do grupo e aguarde a inicialização de uma instância.
- Encerra uma instância no grupo.
- Liste as atividades de escalabilidade que ocorrem em resposta às solicitações do usuário e às mudanças de capacidade.
- Obtenha estatísticas de CloudWatch métricas e, em seguida, limpe os recursos.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
[package]
name = "autoscaling-code-examples"
version = "0.1.0"
authors = ["Doug Schwartz <dougsch@amazon.com>", "David Souther
 <dpsouth@amazon.com>"]
edition = "2021"

# See more keys and their definitions at https://doc.rust-lang.org/cargo/reference/
manifest.html

[dependencies]
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-sdk-autoscaling = { version = "1.3.0" }
aws-sdk-ec2 = { version = "1.3.0" }
aws-types = { version = "1.0.1" }
tokio = { version = "1.20.1", features = ["full"] }
clap = { version = "~4.4", features = ["derive"] }
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
anyhow = "1.0.75"
tracing = "0.1.37"
tokio-stream = "0.1.14"

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::{collections::BTreeSet, fmt::Display};

use anyhow::anyhow;
use autoscaling_code_examples::scenario::{AutoScalingScenario, ScenarioError};
use tracing::{info, warn};

async fn show_scenario_description(scenario: &AutoScalingScenario, event: &str) {
    let description = scenario.describe_scenario().await;
    info!("DescribeAutoScalingInstances: {event}\n{description}");
```

```
}

#[derive(Default, Debug)]
struct Warnings(Vec<String>);

impl Warnings {
    pub fn push(&mut self, warning: &str, error: ScenarioError) {
        let formatted = format!("{warning}: {error}");
        warn!("{formatted}");
        self.0.push(formatted);
    }

    pub fn is_empty(&self) -> bool {
        self.0.is_empty()
    }
}

impl Display for Warnings {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "Warnings:")?;
        for warning in &self.0 {
            writeln!(f, "{: >4}- {warning}", "")?;
        }
        Ok(())
    }
}

#[tokio::main]
async fn main() -> Result<(), anyhow::Error> {
    tracing_subscriber::fmt::init();

    let shared_config = aws_config::from_env().load().await;

    let mut warnings = Warnings::default();

    // 1. Create an EC2 launch template that you'll use to create an auto scaling
 group. Bonus: use SDK with EC2.CreateLaunchTemplate to create the launch template.
    // 2. CreateAutoScalingGroup: pass it the launch template you created in step 0.
 Give it min/max of 1 instance.
    // 4. EnableMetricsCollection: enable all metrics or a subset.
    let scenario = match AutoScalingScenario::prepare_scenario(&shared_config).await
 {
        Ok(scenario) => scenario,
        Err(errs) => {
```

```
            let err_str = errs
                .into_iter()
                .map(|e| e.to_string())
                .collect::<Vec<String>>()
                .join(", ");
            return Err(anyhow!("Failed to initialize scenario: {err_str}"));
        }
    };

    info!("Prepared autoscaling scenario:\n{scenario}");

    let stable = scenario.wait_for_stable(1).await;
    if let Err(err) = stable {
        warnings.push(
            "There was a problem while waiting for group to be stable",
            err,
        );
    }

    // 3. DescribeAutoScalingInstances: show that one instance has launched.
    show_scenario_description(
        &scenario,
        "show that the group was created and one instance has launched",
    )
    .await;

    // 5. UpdateAutoScalingGroup: update max size to 3.
    let scale_max_size = scenario.scale_max_size(3).await;
    if let Err(err) = scale_max_size {
        warnings.push("There was a problem scaling max size", err);
    }

    // 6. DescribeAutoScalingGroups: the current state of the group
    show_scenario_description(
        &scenario,
        "show the current state of the group after setting max size",
    )
    .await;

    // 7. SetDesiredCapacity: set desired capacity to 2.
    let scale_desired_capacity = scenario.scale_desired_capacity(2).await;
    if let Err(err) = scale_desired_capacity {
        warnings.push("There was a problem setting desired capacity", err);
    }
```

```
    //   Wait for a second instance to launch.
    let stable = scenario.wait_for_stable(2).await;
    if let Err(err) = stable {
        warnings.push(
            "There was a problem while waiting for group to be stable",
            err,
        );
    }

    // 8. DescribeAutoScalingInstances: show that two instances are launched.
    show_scenario_description(
        &scenario,
        "show that two instances are launched after setting desired capacity",
    )
    .await;

    let ids_before = scenario
        .list_instances()
        .await
        .map(|v| v.into_iter().collect::<BTreeSet<_>>())
        .unwrap_or_default();

    // 9. TerminateInstanceInAutoScalingGroup: terminate one of the instances in the
group.
    let terminate_some_instance = scenario.terminate_some_instance().await;
    if let Err(err) = terminate_some_instance {
        warnings.push("There was a problem replacing an instance", err);
    }

    let wait_after_terminate = scenario.wait_for_stable(1).await;
    if let Err(err) = wait_after_terminate {
        warnings.push(
            "There was a problem waiting after terminating an instance",
            err,
        );
    }

    let wait_scale_up_after_terminate = scenario.wait_for_stable(2).await;
    if let Err(err) = wait_scale_up_after_terminate {
        warnings.push(
            "There was a problem waiting for scale up after terminating an
instance",
            err,
```

```
        );
    }

    let ids_after = scenario
        .list_instances()
        .await
        .map(|v| v.into_iter().collect::<BTreeSet<_>>())
        .unwrap_or_default();

    let difference = ids_after.intersection(&ids_before).count();
    if !(difference == 1 && ids_before.len() == 2 && ids_after.len() == 2) {
        warnings.push(
            "Before and after set not different",
            ScenarioError::with(format!("{difference}")),
        );
    }

    // 10. DescribeScalingActivities: list the scaling activities that have occurred
for the group so far.
    show_scenario_description(
        &scenario,
        "list the scaling activities that have occurred for the group so far",
    )
    .await;

    // 11. DisableMetricsCollection
    let scale_group = scenario.scale_group_to_zero().await;
    if let Err(err) = scale_group {
        warnings.push("There was a problem scaling the group to 0", err);
    }
    show_scenario_description(&scenario, "Scenario scaled to 0").await;

    // 12. DeleteAutoScalingGroup (to delete the group you must stop all instances):
    // 13. Delete LaunchTemplate.
    let clean_scenario = scenario.clean_scenario().await;
    if let Err(errs) = clean_scenario {
        for err in errs {
            warnings.push("There was a problem cleaning the scenario", err);
        }
    } else {
        info!("The scenario has been cleaned up!");
    }

    if warnings.is_empty() {
```

```
        Ok(())
    } else {
        Err(anyhow!(
            "There were warnings during scenario execution:\n{warnings}"
        ))
    }
}

pub mod scenario;

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

use std::{
    error::Error,
    fmt::{Debug, Display},
    time::{Duration, SystemTime},
};

use anyhow::anyhow;
use aws_config::SdkConfig;
use aws_sdk_autoscaling::{
    error::{DisplayErrorContext, ProvideErrorMetadata},
    types::{Activity, AutoScalingGroup, LaunchTemplateSpecification},
};
use aws_sdk_ec2::types::RequestLaunchTemplateData;
use tracing::trace;

const LAUNCH_TEMPLATE_NAME: &str =
 "SDK_Code_Examples_EC2_Autoscaling_template_from_Rust_SDK";
const AUTOSCALING_GROUP_NAME: &str =
 "SDK_Code_Examples_EC2_Autoscaling_Group_from_Rust_SDK";
const MAX_WAIT: Duration = Duration::from_secs(5 * 60); // Wait at most 25 seconds.
const WAIT_TIME: Duration = Duration::from_millis(500); // Wait half a second at a
 time.

struct Waiter {
    start: SystemTime,
    max: Duration,
}

impl Waiter {
    fn new() -> Self {
        Waiter {
```

```
            start: SystemTime::now(),
            max: MAX_WAIT,
        }
    }

    async fn sleep(&self) -> Result<(), ScenarioError> {
        if SystemTime::now()
            .duration_since(self.start)
            .unwrap_or(Duration::MAX)
            > self.max
        {
            Err(ScenarioError::with(
                "Exceeded maximum wait duration for stable group",
            ))
        } else {
            tokio::time::sleep(WAIT_TIME).await;
            Ok(())
        }
    }
}

pub struct AutoScalingScenario {
    ec2: aws_sdk_ec2::Client,
    autoscaling: aws_sdk_autoscaling::Client,
    launch_template_arn: String,
    auto_scaling_group_name: String,
}

impl Display for AutoScalingScenario {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        f.write_fmt(format_args!(
            "\tLaunch Template ID: {}\n",
            self.launch_template_arn
        ))?;
        f.write_fmt(format_args!(
            "\tScaling Group Name: {}\n",
            self.auto_scaling_group_name
        ))?;

        Ok(())
    }
}

pub struct AutoScalingScenarioDescription {
```

```
    group: Result<Vec<String>, ScenarioError>,
    instances: Result<Vec<String>, anyhow::Error>,
    activities: Result<Vec<Activity>, anyhow::Error>,
}

impl Display for AutoScalingScenarioDescription {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        writeln!(f, "\t      Group status:")?;
        match &self.group {
            Ok(groups) => {
                for status in groups {
                    writeln!(f, "\t\t- {status}")?;
                }
            }
            Err(e) => writeln!(f, "\t\t! - {e}")?,
        }
        writeln!(f, "\t         Instances:")?;
        match &self.instances {
            Ok(instances) => {
                for instance in instances {
                    writeln!(f, "\t\t- {instance}")?;
                }
            }
            Err(e) => writeln!(f, "\t\t! {e}")?,
        }

        writeln!(f, "\t        Activities:")?;
        match &self.activities {
            Ok(activities) => {
                for activity in activities {
                    writeln!(
                        f,
                        "\t\t- {} Progress: {}% Status: {:?} End: {:?}",
                        activity.cause().unwrap_or("Unknown"),
                        activity.progress.unwrap_or(-1),
                        activity.status_code(),
                        // activity.status_message().unwrap_or_default()
                        activity.end_time(),
                    )?;
                }
            }
            Err(e) => writeln!(f, "\t\t! {e}")?,
        }
```

```
        Ok(())
    }
}

#[derive(Debug)]
struct MetadataError {
    message: Option<String>,
    code: Option<String>,
}

impl MetadataError {
    fn from(err: &dyn ProvideErrorMetadata) -> Self {
        MetadataError {
            message: err.message().map(|s| s.to_string()),
            code: err.code().map(|s| s.to_string()),
        }
    }
}

impl Display for MetadataError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        let display = match (&self.message, &self.code) {
            (None, None) => "Unknown".to_string(),
            (None, Some(code)) => format!("({code})"),
            (Some(message), None) => message.to_string(),
            (Some(message), Some(code)) => format!("{message} ({code})"),
        };
        write!(f, "{display}")
    }
}

#[derive(Debug)]
pub struct ScenarioError {
    message: String,
    context: Option<MetadataError>,
}

impl ScenarioError {
    pub fn with(message: impl Into<String>) -> Self {
        ScenarioError {
            message: message.into(),
            context: None,
        }
    }
```

```
    pub fn new(message: impl Into<String>, err: &dyn ProvideErrorMetadata) -> Self {
        ScenarioError {
            message: message.into(),
            context: Some(MetadataError::from(err)),
        }
    }
}

impl Error for ScenarioError {
    // While `Error` can capture `source` information about the underlying error,
 for this example
    // the ScenarioError captures the underlying information in MetadataError and
 treats it as a
    // single Error from this Crate. In other contexts, it may be appropriate to
 model the error
    // as including the SdkError as its source.
}
impl Display for ScenarioError {
    fn fmt(&self, f: &mut std::fmt::Formatter<'_>) -> std::fmt::Result {
        match &self.context {
            Some(c) => write!(f, "{}: {}", self.message, c),
            None => write!(f, "{}", self.message),
        }
    }
}

impl AutoScalingScenario {
    pub async fn prepare_scenario(sdk_config: &SdkConfig) -> Result<Self,
 Vec<ScenarioError>> {
        let ec2 = aws_sdk_ec2::Client::new(sdk_config);
        let autoscaling = aws_sdk_autoscaling::Client::new(sdk_config);

        let auto_scaling_group_name = String::from(AUTOSCALING_GROUP_NAME);

        // Before creating any resources, prepare the list of AZs
        let availablity_zones = ec2.describe_availability_zones().send().await;
        if let Err(err) = availablity_zones {
            return Err(vec![ScenarioError::new("Failed to find AZs", &err)]);
        }

        let availability_zones: Vec<String> = availablity_zones
            .unwrap()
            .availability_zones
```

```
            .unwrap_or_default()
            .iter()
            .take(3)
            .map(|z| z.zone_name.clone().unwrap())
            .collect();

        // 1. Create an EC2 launch template that you'll use to create an auto
scaling group. Bonus: use SDK with EC2.CreateLaunchTemplate to create the launch
template.
        //   * Recommended: InstanceType='t1.micro', ImageId='ami-0ca285d4c2cda3300'
        let create_launch_template = ec2
            .create_launch_template()
            .launch_template_name(LAUNCH_TEMPLATE_NAME)
            .launch_template_data(
                RequestLaunchTemplateData::builder()
                    .instance_type(aws_sdk_ec2::types::InstanceType::T1Micro)
                    .image_id("ami-0ca285d4c2cda3300")
                    .build(),
            )
            .send()
            .await
            .map_err(|err| vec![ScenarioError::new("Failed to create launch
template", &err)])?;

        let launch_template_arn = match create_launch_template.launch_template {
            Some(launch_template) =>
launch_template.launch_template_id.unwrap_or_default(),
            None => {
                // Try to delete the launch template
                let _ = ec2
                    .delete_launch_template()
                    .launch_template_name(LAUNCH_TEMPLATE_NAME)
                    .send()
                    .await;
                return Err(vec![ScenarioError::with("Failed to load launch
template")]);
            }
        };

        // 2. CreateAutoScalingGroup: pass it the launch template you created in
step 0. Give it min/max of 1 instance.
        //   You can use EC2.describe_availability_zones() to get a list of AZs (you
have to specify an AZ when you create the group).
```

```
        //   Wait for instance to launch. Use a waiter if you have one, otherwise
DescribeAutoScalingInstances until LifecycleState='InService'
        if let Err(err) = autoscaling
            .create_auto_scaling_group()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .launch_template(
                LaunchTemplateSpecification::builder()
                    .launch_template_id(launch_template_arn.clone())
                    .version("$Latest")
                    .build(),
            )
            .max_size(1)
            .min_size(1)
            .set_availability_zones(Some(availability_zones))
            .send()
            .await
        {
            let mut errs = vec![ScenarioError::new(
                "Failed to create autoscaling group",
                &err,
            )];

            if let Err(err) = autoscaling
                .delete_auto_scaling_group()
                .auto_scaling_group_name(auto_scaling_group_name.as_str())
                .send()
                .await
            {
                errs.push(ScenarioError::new(
                    "Failed to clean up autoscaling group",
                    &err,
                ));
            }

            if let Err(err) = ec2
                .delete_launch_template()
                .launch_template_id(launch_template_arn.clone())
                .send()
                .await
            {
                errs.push(ScenarioError::new(
                    "Failed to clean up launch template",
                    &err,
                ));
```

```
            }
            return Err(errs);
        }

        let scenario = AutoScalingScenario {
            ec2,
            autoscaling: autoscaling.clone(), // Clients are cheap so cloning here
to prevent a move is ok.
            auto_scaling_group_name: auto_scaling_group_name.clone(),
            launch_template_arn,
        };

        // snippet-start:[rust.auto-scaling.scenario.enable_metrics_collection]
        let enable_metrics_collection = autoscaling
            .enable_metrics_collection()
            .auto_scaling_group_name(auto_scaling_group_name.as_str())
            .granularity("1Minute")
            .set_metrics(Some(vec![
                String::from("GroupMinSize"),
                String::from("GroupMaxSize"),
                String::from("GroupDesiredCapacity"),
                String::from("GroupInServiceInstances"),
                String::from("GroupTotalInstances"),
            ]))
            .send()
            .await;
        // snippet-end:[rust.auto-scaling.scenario.enable_metrics_collection]

        match enable_metrics_collection {
            Ok(_) => Ok(scenario),
            Err(err) => {
                scenario.clean_scenario().await?;
                Err(vec![ScenarioError::new(
                    "Failed to enable metrics collections for group",
                    &err,
                )])
            }
        }
    }

    pub async fn clean_scenario(self) -> Result<(), Vec<ScenarioError>> {
        let _ = self.wait_for_no_scaling().await;
        let delete_group = self
            .autoscaling
```

```
            .delete_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;

        // 14. Delete LaunchTemplate.
        let delete_launch_template = self
            .ec2
            .delete_launch_template()
            .launch_template_id(self.launch_template_arn.clone())
            .send()
            .await;

        let early_exit = match (delete_group, delete_launch_template) {
            (Ok(_), Ok(_)) => Ok(()),
            (Ok(_), Err(e)) => Err(vec![ScenarioError::new(
                "There was an error cleaning the launch template",
                &e,
            )]),
            (Err(e), Ok(_)) => Err(vec![ScenarioError::new(
                "There was an error cleaning the scale group",
                &e,
            )]),
            (Err(e1), Err(e2)) => Err(vec![
                ScenarioError::new("Multiple error cleaning the scenario Scale
Group", &e1),
                ScenarioError::new("Multiple error cleaning the scenario Launch
Template", &e2),
            ]),
        };

        if early_exit.is_err() {
            early_exit
        } else {
            // Wait for delete_group to finish
            let waiter = Waiter::new();
            let mut errors = Vec::<ScenarioError>::new();
            while errors.len() < 3 {
                if let Err(e) = waiter.sleep().await {
                    errors.push(e);
                    continue;
                }
                let describe_group = self
                    .autoscaling
```

```
                    .describe_auto_scaling_groups()
                    .auto_scaling_group_names(self.auto_scaling_group_name.clone())
                    .send()
                    .await;
                match describe_group {
                    Ok(group) => match group.auto_scaling_groups().first() {
                        Some(group) => {
                            if group.status() != Some("Delete in progress") {
                                errors.push(ScenarioError::with(format!(
                                    "Group in an unknown state while deleting: {}",
                                    group.status().unwrap_or("unknown error")
                                )));
                                return Err(errors);
                            }
                        }
                        None => return Ok(()),
                    },
                    Err(err) => {
                        errors.push(ScenarioError::new("Failed to describe
autoscaling group during cleanup 3 times, last error", &err));
                    }
                }
                if errors.len() > 3 {
                    return Err(errors);
                }
            }
            Err(vec![ScenarioError::with(
                "Exited cleanup wait loop without retuning success or failing after
three rounds",
            )])
        }
    }

    // snippet-start:[rust.auto-scaling.scenario.describe_scenario]
    pub async fn describe_scenario(&self) -> AutoScalingScenarioDescription {
        let group = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await
            .map(|s| {
                s.auto_scaling_groups()
                    .iter()
```

```
                    .map(|s| {
                        format!(
                            "{}: {}",
                            s.auto_scaling_group_name().unwrap_or("Unknown"),
                            s.status().unwrap_or("Unknown")
                        )
                    })
                    .collect::<Vec<String>>()
            })
            .map_err(|e| {
                ScenarioError::new("Failed to describe auto scaling groups for
scenario", &e)
            });

        let instances = self
            .list_instances()
            .await
            .map_err(|e| anyhow!("There was an error listing instances: {e}",));

        // 10. DescribeScalingActivities: list the scaling activities that have
occurred for the group so far.
        //   Bonus: use CloudWatch API to get and show some metrics collected for
the group.
        //   CW.ListMetrics with Namespace='AWS/AutoScaling' and
Dimensions=[{'Name': 'AutoScalingGroupName', 'Value': }]
        //   CW.GetMetricStatistics with Statistics='Sum'. Start and End times must
be in UTC!
        let activities = self
            .autoscaling
            .describe_scaling_activities()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .into_paginator()
            .items()
            .send()
            .collect::<Result<Vec<_>, _>>()
            .await
            .map_err(|e| {
                anyhow!(
                    "There was an error retrieving scaling activities: {}",
                    DisplayErrorContext(&e)
                )
            });

        AutoScalingScenarioDescription {
```

```
            group,
            instances,
            activities,
        }
    }
    // snippet-end:[rust.auto-scaling.scenario.describe_scenario]

    // snippet-start:[rust.auto-scaling.scenario.get_group]
    async fn get_group(&self) -> Result<AutoScalingGroup, ScenarioError> {
        let describe_auto_scaling_groups = self
            .autoscaling
            .describe_auto_scaling_groups()
            .auto_scaling_group_names(self.auto_scaling_group_name.clone())
            .send()
            .await;

        if let Err(err) = describe_auto_scaling_groups {
            return Err(ScenarioError::new(
                format!(
                    "Failed to get status of autoscaling group {}",
                    self.auto_scaling_group_name.clone()
                )
                .as_str(),
                &err,
            ));
        }

        let describe_auto_scaling_groups_output =
describe_auto_scaling_groups.unwrap();
        let auto_scaling_groups =
describe_auto_scaling_groups_output.auto_scaling_groups();
        let auto_scaling_group = auto_scaling_groups.first();

        if auto_scaling_group.is_none() {
            return Err(ScenarioError::with(format!(
                "Could not find autoscaling group {}",
                self.auto_scaling_group_name.clone()
            )));
        }

        Ok(auto_scaling_group.unwrap().clone())
    }
    // snippet-end:[rust.auto-scaling.scenario.get_group]
```

```
    pub async fn wait_for_no_scaling(&self) -> Result<(), ScenarioError> {
        let waiter = Waiter::new();
        let mut scaling = true;
        while scaling {
            waiter.sleep().await?;
            let describe_activities = self
                .autoscaling
                .describe_scaling_activities()
                .auto_scaling_group_name(self.auto_scaling_group_name.clone())
                .send()
                .await
                .map_err(|e| {
                    ScenarioError::new("Failed to get autoscaling activities for
group", &e)
                })?;
            let activities = describe_activities.activities();
            trace!(
                "Waiting for no scaling found {} activities",
                activities.len()
            );
            scaling = activities.iter().any(|a| a.progress() < Some(100));
        }
        Ok(())
    }

    pub async fn wait_for_stable(&self, size: usize) -> Result<(), ScenarioError> {
        self.wait_for_no_scaling().await?;

        let mut group = self.get_group().await?;
        let mut count = count_group_instances(&group);

        let waiter = Waiter::new();
        while count != size {
            trace!("Waiting for stable {size} (current: {count})");
            waiter.sleep().await?;
            group = self.get_group().await?;
            count = count_group_instances(&group);
        }

        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.list_instances]
    pub async fn list_instances(&self) -> Result<Vec<String>, ScenarioError> {
```

```
        // The direct way to list instances is by using DescribeAutoScalingGroup's
instances property. However, this returns a Vec<Instance>, as opposed to a
Vec<AutoScalingInstanceDetails>.
        // Ok(self.get_group().await?.instances.unwrap_or_default().map(|i|
i.instance_id.clone().unwrap_or_default()).filter(|id| !id.is_empty()).collect())

        // Alternatively, and for the sake of example, DescribeAutoScalingInstances
returns a list that can be filtered by the client.
        self.autoscaling
            .describe_auto_scaling_instances()
            .into_paginator()
            .items()
            .send()
            .try_collect()
            .await
            .map(|items| {
                items
                    .into_iter()
                    .filter(|i| {
                        i.auto_scaling_group_name.as_deref()
                            == Some(self.auto_scaling_group_name.as_str())
                    })
                    .map(|i| i.instance_id.unwrap_or_default())
                    .filter(|id| !id.is_empty())
                    .collect::<Vec<String>>()
            })
            .map_err(|err| ScenarioError::new("Failed to get list of auto scaling
instances", &err))
    }
    // snippet-end:[rust.auto-scaling.scenario.list_instances]

    pub async fn scale_min_size(&self, size: i32) -> Result<(), ScenarioError> {
        let update_group = self
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .min_size(size)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failer to update group to min size ({size}))").as_str(),
                &err,
            ));
```

```
        }
        Ok(())
    }

    pub async fn scale_max_size(&self, size: i32) -> Result<(), ScenarioError> {
        // 5. UpdateAutoScalingGroup: update max size to 3.
        let update_group = self
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .max_size(size)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failed to update group to max size ({size})").as_str(),
                &err,
            ));
        }
        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.scale_desired_capacity]
    pub async fn scale_desired_capacity(&self, capacity: i32) -> Result<(),
ScenarioError> {
        // 7. SetDesiredCapacity: set desired capacity to 2.
        //   Wait for a second instance to launch.
        let update_group = self
            .autoscaling
            .set_desired_capacity()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .desired_capacity(capacity)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                format!("Failed to update group to desired capacity
({capacity}))").as_str(),
                &err,
            ));
        }
        Ok(())
    }
    // snippet-end:[rust.auto-scaling.scenario.scale_desired_capacity]
```

```
    pub async fn scale_group_to_zero(&self) -> Result<(), ScenarioError> {
        // snippet-start:[rust.auto-scaling.scenario.disable_metrics_collection]
        // If this fails it's fine, just means there are extra cloudwatch metrics
events for the scale-down.
        let _ = self
            .autoscaling
            .disable_metrics_collection()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .send()
            .await;
        // snippet-end:[rust.auto-scaling.scenario.disable_metrics_collection]

        // 12. DeleteAutoScalingGroup (to delete the group you must stop all
instances):
        //   UpdateAutoScalingGroup with MinSize=0
        let update_group = self
            .autoscaling
            .update_auto_scaling_group()
            .auto_scaling_group_name(self.auto_scaling_group_name.clone())
            .min_size(0)
            .desired_capacity(0)
            .send()
            .await;
        if let Err(err) = update_group {
            return Err(ScenarioError::new(
                "Failed to update group for scaling down&",
                &err,
            ));
        }

        let stable = self.wait_for_stable(0).await;
        if let Err(err) = stable {
            return Err(ScenarioError::with(format!(
                "Error while waiting for group to be stable on scale down: {err}"
            )));
        }

        Ok(())
    }

    // snippet-start:[rust.auto-scaling.scenario.terminate_some_instance]
    pub async fn terminate_some_instance(&self) -> Result<(), ScenarioError> {
        // Retrieve a list of instances in the auto scaling group.
```

```
        let auto_scaling_group = self.get_group().await?;
        let instances = auto_scaling_group.instances();
        // Or use other logic to find an instance to terminate.
        let instance = instances.first();
        if let Some(instance) = instance {
            let instance_id = if let Some(instance_id) = instance.instance_id() {
                instance_id
            } else {
                return Err(ScenarioError::with("Missing instance id"));
            };
            let termination = self
                .ec2
                .terminate_instances()
                .instance_ids(instance_id)
                .send()
                .await;
            if let Err(err) = termination {
                Err(ScenarioError::new(
                    "There was a problem terminating an instance",
                    &err,
                ))
            } else {
                Ok(())
            }
        } else {
            Err(ScenarioError::with("There was no instance to terminate"))
        }
    }
    // snippet-end:[rust.auto-scaling.scenario.terminate_some_instance]
}

fn count_group_instances(group: &AutoScalingGroup) -> usize {
    group.instances.as_ref().map(|i| i.len()).unwrap_or(0)
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances

- DescribeScalingActivities
- DisableMetricsCollection
- EnableMetricsCollection
- SetDesiredCapacity
- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Exemplos de AWS Batch usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com AWS Batch.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Descrever ambientes computacionais

O exemplo de código a seguir mostra como descrever um ou mais ambientes de computação AWS Batch.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_envs(client: &Client) -> Result<(), Error> {
    let rsp = client.describe_compute_environments().send().await?;

    let compute_envs = rsp.compute_environments();
    println!("Found {} compute environments:", compute_envs.len());
    for env in compute_envs {
        let arn = env.compute_environment_arn();
        let name = env.compute_environment_name();

        println!("  Name: {}", name.unwrap_or("Unknown"));
        println!("  ARN:  {}", arn.unwrap_or("Unknown"));
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeComputeEnvironmentsreferência da API AWS SDK for Rust.

Exemplos de código do Provedor de Identidade do Amazon Cognito usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o provedor de identidade do Amazon Cognito.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar os grupos de usuários

O exemplo de código a seguir mostra como listar os grupos de usuários do Amazon Cognito.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_pools(client: &Client) -> Result<(), Error> {
    let response = client.list_user_pools().max_results(10).send().await?;
    let pools = response.user_pools();
    println!("User pools:");
    for pool in pools {
        println!("  ID:              {}", pool.id().unwrap_or_default());
        println!("  Name:            {}", pool.name().unwrap_or_default());
        println!("  Lambda Config:   {:?}", pool.lambda_config().unwrap());
        println!(
            "  Last modified:   {}",
            pool.last_modified_date().unwrap().to_chrono_utc()?
        );
        println!(
            "  Creation date:   {:?}",
            pool.creation_date().unwrap().to_chrono_utc()
        );
        println!();
    }
    println!("Next token: {}", response.next_token().unwrap_or_default());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListUserPoolsreferência da API AWS SDK for Rust.

Exemplos do Amazon Cognito Sync usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon Cognito Sync.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar grupos de identidades

O exemplo de código a seguir mostra como ter uma lista de identidades do Amazon Cognito.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_pools(client: &Client) -> Result<(), Error> {
    let response = client
        .list_identity_pool_usage()
        .max_results(10)
        .send()
        .await?;

    let pools = response.identity_pool_usages();
```

```
    println!("Identity pools:");

    for pool in pools {
        println!(
            "  Identity pool ID:    {}",
            pool.identity_pool_id().unwrap_or_default()
        );
        println!(
            "  Data storage:        {}",
            pool.data_storage().unwrap_or_default()
        );
        println!(
            "  Sync sessions count: {}",
            pool.sync_sessions_count().unwrap_or_default()
        );
        println!(
            "  Last modified:       {}",
            pool.last_modified_date().unwrap().to_chrono_utc()?
        );
        println!();
    }

    println!("Next token: {}", response.next_token().unwrap_or_default());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListIdentityPoolUsagereferência da API AWS SDK for Rust.

Exemplos do DynamoDB usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_table(
    client: &Client,
    table: &str,
    key: &str,
) -> Result<CreateTableOutput, Error> {
    let a_name: String = key.into();
    let table_name: String = table.into();

    let ad = AttributeDefinition::builder()
        .attribute_name(&a_name)
        .attribute_type(ScalarAttributeType::S)
        .build()
        .map_err(Error::BuildError)?;

    let ks = KeySchemaElement::builder()
        .attribute_name(&a_name)
        .key_type(KeyType::Hash)
        .build()
        .map_err(Error::BuildError)?;
```

```
    let pt = ProvisionedThroughput::builder()
        .read_capacity_units(10)
        .write_capacity_units(5)
        .build()
        .map_err(Error::BuildError)?;

    let create_table_response = client
        .create_table()
        .table_name(table_name)
        .key_schema(ks)
        .attribute_definitions(ad)
        .provisioned_throughput(pt)
        .send()
        .await;

    match create_table_response {
        Ok(out) => {
            println!("Added table {} with key {}", table, key);
            Ok(out)
        }
        Err(e) => {
            eprintln!("Got an error creating table:");
            eprintln!("{}", e);
            Err(Error::unhandled(e))
        }
    }
}
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWS SDK for Rust.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_table(client: &Client, table: &str) -> Result<DeleteTableOutput,
 Error> {
    let resp = client.delete_table().table_name(table).send().await;

    match resp {
        Ok(out) => {
            println!("Deleted table");
            Ok(out)
        }
        Err(e) => Err(Error::Unhandled(e.into())),
    }
}
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for Rust.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_item(
    client: &Client,
    table: &str,
    key: &str,
    value: &str,
) -> Result<DeleteItemOutput, Error> {
    match client
        .delete_item()
        .table_name(table)
        .key(key, AttributeValue::S(value.into()))
        .send()
        .await
    {
```

```
        Ok(out) => {
            println!("Deleted item from table");
            Ok(out)
        }
        Err(e) => Err(Error::unhandled(e)),
    }
}
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWS SDK for Rust.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
pub async fn list_tables(client: &Client) -> Result<Vec<String>, Error> {
    let paginator = client.list_tables().into_paginator().items().send();
    let table_names = paginator.collect::<Result<Vec<_>, _>>().await?;

    println!("Tables:");

    for name in &table_names {
        println!("  {}", name);
    }

    println!("Found {} tables", table_names.len());
    Ok(table_names)
}
```

Determine se a tabela existe.

```
pub async fn table_exists(client: &Client, table: &str) -> Result<bool, Error> {
```

```
    debug!("Checking for table: {table}");
    let table_list = client.list_tables().send().await;

    match table_list {
        Ok(list) => Ok(list.table_names().contains(&table.into())),
        Err(e) => Err(e.into()),
    }
}
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWS SDK for Rust.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn add_item(client: &Client, item: Item, table: &String) ->
 Result<ItemOut, Error> {
    let user_av = AttributeValue::S(item.username);
    let type_av = AttributeValue::S(item.p_type);
    let age_av = AttributeValue::S(item.age);
    let first_av = AttributeValue::S(item.first);
    let last_av = AttributeValue::S(item.last);

    let request = client
        .put_item()
        .table_name(table)
        .item("username", user_av)
        .item("account_type", type_av)
        .item("age", age_av)
        .item("first_name", first_av)
        .item("last_name", last_av);
```

```
    println!("Executing request [{request:?}] to add item...");

    let resp = request.send().await?;

    let attributes = resp.attributes().unwrap();

    let username = attributes.get("username").cloned();
    let first_name = attributes.get("first_name").cloned();
    let last_name = attributes.get("last_name").cloned();
    let age = attributes.get("age").cloned();
    let p_type = attributes.get("p_type").cloned();

    println!(
        "Added user {:?}, {:?} {:?}, age {:?} as {:?} user",
        username, first_name, last_name, age, p_type
    );

    Ok(ItemOut {
        p_type,
        age,
        username,
        first_name,
        last_name,
    })
}
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWS SDK for Rust.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

Encontre os filmes feitos no ano especificado.

```
pub async fn movies_in_year(
    client: &Client,
    table_name: &str,
    year: u16,
) -> Result<Vec<Movie>, MovieError> {
    let results = client
        .query()
        .table_name(table_name)
        .key_condition_expression("#yr = :yyyy")
        .expression_attribute_names("#yr", "year")
        .expression_attribute_values(":yyyy", AttributeValue::N(year.to_string()))
        .send()
        .await?;

    if let Some(items) = results.items {
        let movies = items.iter().map(|v| v.into()).collect();
        Ok(movies)
    } else {
        Ok(vec![])
    }
}
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Rust.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no Repositório de exemplos de código da AWS.

```
pub async fn list_items(client: &Client, table: &str, page_size: Option<i32>) ->
 Result<(), Error> {
    let page_size = page_size.unwrap_or(10);
    let items: Result<Vec<_>, _> = client
```

```
        .scan()
        .table_name(table)
        .limit(page_size)
        .into_paginator()
        .items()
        .send()
        .collect()
        .await;

    println!("Items in table (up to {page_size}):");
    for item in items? {
        println!("   {:?}", item);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Rust.

Cenários

Consultar uma tabela usando o PartiQL

O código de exemplo a seguir mostra como:

- Obter um item executando uma instrução SELECT.
- Adicionar um item executando uma instrução INSERT.
- Atualizar um item executando a instrução UPDATE.
- Excluir um item executando uma instrução DELETE.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_table(
```

```
    client: &Client,
    table: &str,
    key: &str,
) -> Result<(), SdkError<CreateTableError>> {
    let ad = AttributeDefinition::builder()
        .attribute_name(key)
        .attribute_type(ScalarAttributeType::S)
        .build()
        .expect("creating AttributeDefinition");

    let ks = KeySchemaElement::builder()
        .attribute_name(key)
        .key_type(KeyType::Hash)
        .build()
        .expect("creating KeySchemaElement");

    let pt = ProvisionedThroughput::builder()
        .read_capacity_units(10)
        .write_capacity_units(5)
        .build()
        .expect("creating ProvisionedThroughput");

    match client
        .create_table()
        .table_name(table)
        .key_schema(ks)
        .attribute_definitions(ad)
        .provisioned_throughput(pt)
        .send()
        .await
    {
        Ok(_) => Ok(()),
        Err(e) => Err(e),
    }
}

async fn add_item(client: &Client, item: Item) -> Result<(),
 SdkError<ExecuteStatementError>> {
    match client
        .execute_statement()
        .statement(format!(
            r#"INSERT INTO "{}" VALUE {{
                "{}": ?,
                "acount_type": ?,
```

```
                "age": ?,
                "first_name": ?,
                "last_name": ?
        }} "#,
            item.table, item.key
        ))
        .set_parameters(Some(vec![
            AttributeValue::S(item.utype),
            AttributeValue::S(item.age),
            AttributeValue::S(item.first_name),
            AttributeValue::S(item.last_name),
        ]))
        .send()
        .await
    {
        Ok(_) => Ok(()),
        Err(e) => Err(e),
    }
}

async fn query_item(client: &Client, item: Item) -> bool {
    match client
        .execute_statement()
        .statement(format!(
            r#"SELECT * FROM "{}" WHERE "{}" = ?"#,
            item.table, item.key
        ))
        .set_parameters(Some(vec![AttributeValue::S(item.value)]))
        .send()
        .await
    {
        Ok(resp) => {
            if !resp.items().is_empty() {
                println!("Found a matching entry in the table:");
                println!("{:?}", resp.items.unwrap_or_default().pop());
                true
            } else {
                println!("Did not find a match.");
                false
            }
        }
        Err(e) => {
            println!("Got an error querying table:");
            println!("{}", e);
```

```
            process::exit(1);
        }
    }
}

async fn remove_item(client: &Client, table: &str, key: &str, value: String) ->
 Result<(), Error> {
    client
        .execute_statement()
        .statement(format!(r#"DELETE FROM "{table}" WHERE "{key}" = ?"#))
        .set_parameters(Some(vec![AttributeValue::S(value)]))
        .send()
        .await?;

    println!("Deleted item.");

    Ok(())
}

async fn remove_table(client: &Client, table: &str) -> Result<(), Error> {
    client.delete_table().table_name(table).send().await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWS SDK for Rust.

Exemplos do Amazon EBS usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon EBS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um snapshot

O exemplo de código a seguir mostra como criar um snapshot do Amazon EBS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn start(client: &Client, description: &str) -> Result<String, Error> {
    let snapshot = client
        .start_snapshot()
        .description(description)
        .encrypted(false)
        .volume_size(1)
        .send()
        .await?;

    Ok(snapshot.snapshot_id.unwrap())
}
```

- Para obter detalhes da API, consulte a StartSnapshotreferência da API AWS SDK for Rust.

Selar e completar um snapshot

O exemplo de código a seguir mostra como selar e completar um snapshot do Amazon EBS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn finish(client: &Client, id: &str) -> Result<(), Error> {
    client
        .complete_snapshot()
        .changed_blocks_count(2)
        .snapshot_id(id)
        .send()
        .await?;

    println!("Snapshot ID {}", id);
    println!("The state is 'completed' when all of the modified blocks have been
 transferred to Amazon S3.");
    println!("Use the get-snapshot-state code example to get the state of the
 snapshot.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CompleteSnapshotreferência da API AWS SDK for Rust.

Gravar um bloco de dados em um snapshot

O exemplo de código a seguir mostra como gravar um bloco de dados em um snapshot do Amazon EBS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_block(
    client: &Client,
    id: &str,
    idx: usize,
    block: Vec<u8>,
    checksum: &str,
) -> Result<(), Error> {
    client
        .put_snapshot_block()
        .snapshot_id(id)
        .block_index(idx as i32)
        .block_data(ByteStream::from(block))
        .checksum(checksum)
        .checksum_algorithm(ChecksumAlgorithm::ChecksumAlgorithmSha256)
        .data_length(EBS_BLOCK_SIZE as i32)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutSnapshotBlockreferência da API AWS SDK for Rust.

Exemplos do Amazon EC2 usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon EC2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Excluir um snapshot

O exemplo de código a seguir mostra como excluir um snapshot do Amazon EBS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn delete_snapshot(client: &Client, id: &str) -> Result<(), Error> {
    client.delete_snapshot().snapshot_id(id).send().await?;

    println!("Deleted");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteSnapshotreferência da API AWS SDK for Rust.

Descrever regiões

Os exemplos de código a seguir mostram como descrever as regiões do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_regions(client: &Client) -> Result<(), Error> {
    let rsp = client.describe_regions().send().await?;

    println!("Regions:");
```

```
    for region in rsp.regions() {
        println!("  {}", region.region_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeRegionsreferência da API AWS SDK for Rust.

Descrever o status da instância

Os exemplos de código a seguir mostram como descrever o status de instâncias do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_all_events(client: &Client) -> Result<(), Error> {
    let resp = client.describe_regions().send().await.unwrap();

    for region in resp.regions.unwrap_or_default() {
        let reg: &'static str = Box::leak(Box::from(region.region_name().unwrap()));
        let region_provider = RegionProviderChain::default_provider().or_else(reg);
        let config = aws_config::from_env().region(region_provider).load().await;
        let new_client = Client::new(&config);

        let resp = new_client.describe_instance_status().send().await;

        println!("Instances in region {}:", reg);
        println!();

        for status in resp.unwrap().instance_statuses() {
            println!(
                "  Events scheduled for instance ID: {}",
                status.instance_id().unwrap_or_default()
            );
            for event in status.events() {
```

```
                println!("    Event ID:     {}",
 event.instance_event_id().unwrap());
                println!("    Description:  {}", event.description().unwrap());
                println!("    Event code:   {}", event.code().unwrap().as_ref());
                println!();
            }
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeInstanceStatusreferência da API AWS SDK for Rust.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_state(client: &Client, ids: Option<Vec<String>>) -> Result<(), Error>
 {
    let resp = client
        .describe_instances()
        .set_instance_ids(ids)
        .send()
        .await?;

    for reservation in resp.reservations() {
        for instance in reservation.instances() {
            println!("Instance ID: {}", instance.instance_id().unwrap());
            println!(
                "State:       {:?}",
```

```
                instance.state().unwrap().name().unwrap()
            );
            println!();
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWS SDK for Rust.

Descrever snapshots

O exemplo de código a seguir mostra como descrever snapshots do Amazon EBS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Mostra o estado de um snapshot.

```
async fn show_state(client: &Client, id: &str) -> Result<(), Error> {
    let resp = client
        .describe_snapshots()
        .filters(Filter::builder().name("snapshot-id").values(id).build())
        .send()
        .await?;

    println!(
        "State: {}",
        resp.snapshots().first().unwrap().state().unwrap().as_ref()
    );

    Ok(())
}
```

```
async fn show_snapshots(client: &Client) -> Result<(), Error> {
    // "self" represents your account ID.
    // You can list the snapshots for any account by replacing
    // "self" with that account ID.
    let resp = client.describe_snapshots().owner_ids("self").send().await?;
    let snapshots = resp.snapshots();
    let length = snapshots.len();

    for snapshot in snapshots {
        println!(
            "ID:          {}",
            snapshot.snapshot_id().unwrap_or_default()
        );
        println!(
            "Description: {}",
            snapshot.description().unwrap_or_default()
        );
        println!("State:       {}", snapshot.state().unwrap().as_ref());
        println!();
    }

    println!();
    println!("Found {} snapshot(s)", length);
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeSnapshotsreferência da API AWS SDK for Rust.

Habilitar monitoramento

Os exemplos de código a seguir mostram como habilitar o monitoramento em uma instância do Amazon EC2 em execução.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn enable_monitoring(client: &Client, id: &str) -> Result<(), Error> {
    client.monitor_instances().instance_ids(id).send().await?;

    println!("Enabled monitoring");

    Ok(())
}
```

- Para obter detalhes da API, consulte a MonitorInstancesreferência da API AWS SDK for Rust.

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn reboot_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.reboot_instances().instance_ids(id).send().await?;

    println!("Rebooted instance.");
    Ok(())
}
```

- Para obter detalhes da API, consulte a RebootInstancesreferência da API AWS SDK for Rust.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn start_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.start_instances().instance_ids(id).send().await?;

    println!("Started instance.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWS SDK for Rust.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn stop_instance(client: &Client, id: &str) -> Result<(), Error> {
    client.stop_instances().instance_ids(id).send().await?;

    println!("Stopped instance.");
```

```
    Ok(())
}
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWS SDK for Rust.

Exemplos do Amazon ECR usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon ECR.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar os IDs de imagem

O exemplo de código a seguir mostra como listar os IDs de imagem para um repositório.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_images(
```

```
    client: &aws_sdk_ecr::Client,
    repository: &str,
) -> Result<(), aws_sdk_ecr::Error> {
    let rsp = client
        .list_images()
        .repository_name(repository)
        .send()
        .await?;

    let images = rsp.image_ids();

    println!("found {} images", images.len());

    for image in images {
        println!(
            "image: {}:{}",
            image.image_tag().unwrap(),
            image.image_digest().unwrap()
        );
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListImagesreferência da API AWS SDK for Rust.

Listar repositórios

O exemplo de código a seguir mostra como listar os repositórios.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_repos(client: &aws_sdk_ecr::Client) -> Result<(), aws_sdk_ecr::Error>
 {
    let rsp = client.describe_repositories().send().await?;
```

```
    let repos = rsp.repositories();

    println!("Found {} repositories:", repos.len());

    for repo in repos {
        println!("  ARN:  {}", repo.repository_arn().unwrap());
        println!("  Name: {}", repo.repository_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeRepositoriesreferência da API AWS SDK for Rust.

Exemplos do Amazon ECS usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon ECS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um cluster

O exemplo de código a seguir mostra como criar um cluster do Amazon ECS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_cluster(client: &aws_sdk_ecs::Client, name: &str) -> Result<(),
 aws_sdk_ecs::Error> {
    let cluster = client.create_cluster().cluster_name(name).send().await?;
    println!("cluster created: {:?}", cluster);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWS SDK for Rust.

Excluir um cluster

O exemplo de código a seguir mostra como excluir um cluster do Amazon ECS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_cluster(
    client: &aws_sdk_ecs::Client,
    name: &str,
) -> Result<(), aws_sdk_ecs::Error> {
    let cluster_deleted = client.delete_cluster().cluster(name).send().await?;
    println!("cluster deleted: {:?}", cluster_deleted);

    Ok(())
```

```
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWS SDK for Rust.

Descrever clusters

O exemplo de código a seguir mostra como descrever clusters do Amazon ECS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_clusters(client: &aws_sdk_ecs::Client) -> Result<(),
 aws_sdk_ecs::Error> {
    let resp = client.list_clusters().send().await?;

    let cluster_arns = resp.cluster_arns();
    println!("Found {} clusters:", cluster_arns.len());

    let clusters = client
        .describe_clusters()
        .set_clusters(Some(cluster_arns.into()))
        .send()
        .await?;

    for cluster in clusters.clusters() {
        println!("  ARN:  {}", cluster.cluster_arn().unwrap());
        println!("  Name: {}", cluster.cluster_name().unwrap());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeClustersreferência da API AWS SDK for Rust.

Exemplos do Amazon EKS usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com o Amazon EKS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um plano de controle de cluster

O exemplo de código a seguir mostra como criar um plano de controle de cluster do Amazon EKS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_cluster(
    client: &aws_sdk_eks::Client,
    name: &str,
    arn: &str,
    subnet_ids: Vec<String>,
) -> Result<(), aws_sdk_eks::Error> {
    let cluster = client
        .create_cluster()
```

```
        .name(name)
        .role_arn(arn)
        .resources_vpc_config(
            VpcConfigRequest::builder()
                .set_subnet_ids(Some(subnet_ids))
                .build(),
        )
        .send()
        .await?;
    println!("cluster created: {:?}", cluster);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateClusterreferência da API AWS SDK for Rust.

Excluir um plano de controle de cluster

O exemplo de código a seguir mostra como excluir um cluster do Amazon EKS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_cluster(
    client: &aws_sdk_eks::Client,
    name: &str,
) -> Result<(), aws_sdk_eks::Error> {
    let cluster_deleted = client.delete_cluster().name(name).send().await?;
    println!("cluster deleted: {:?}", cluster_deleted);

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteClusterreferência da API AWS SDK for Rust.

Exemplos de AWS Glue usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com AWS Glue.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Olá, AWS Glue

O exemplo de código a seguir mostra como começar a usar o AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let mut list_jobs = glue.list_jobs().into_paginator().send();
        while let Some(list_jobs_output) = list_jobs.next().await {
            match list_jobs_output {
                Ok(list_jobs) => {
                    let names = list_jobs.job_names();
                    info!(?names, "Found these jobs")
                }
                Err(err) => return Err(GlueMvpError::from_glue_sdk(err)),
            }
        }
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWS SDK for Rust.

Tópicos

- Ações
- Cenários

Ações

Criar um crawler

Os exemplos de código a seguir mostram como criar um crawler do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let create_crawler = glue
            .create_crawler()
            .name(self.crawler())
            .database_name(self.database())
            .role(self.iam_role.expose_secret())
            .targets(
                CrawlerTargets::builder()
                    .s3_targets(S3Target::builder().path(CRAWLER_TARGET).build())
                    .build(),
            )
            .send()
            .await;

        match create_crawler {
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::AlreadyExistsException(_) => {
                        info!("Using existing crawler");
                        Ok(())
```

```
                }
                _ => Err(GlueMvpError::GlueSdk(glue_err)),
            }
        }
        Ok(_) => Ok(()),
    }?;
```

- Para obter detalhes da API, consulte a CreateCrawlerreferência da API AWS SDK for Rust.

Crie uma definição de trabalho

Os exemplos de código a seguir mostram como criar uma definição de trabalho do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    let create_job = glue
        .create_job()
        .name(self.job())
        .role(self.iam_role.expose_secret())
        .command(
            JobCommand::builder()
                .name("glueetl")
                .python_version("3")
                .script_location(format!("s3://{}/job.py", self.bucket()))
                .build(),
        )
        .glue_version("3.0")
        .send()
        .await
        .map_err(GlueMvpError::from_glue_sdk)?;

    let job_name = create_job.name().ok_or_else(|| {
        GlueMvpError::Unknown("Did not get job name after creating job".into())
    })?;
```

- Para obter detalhes da API, consulte a CreateJobreferência da API AWS SDK for Rust.

Excluir um crawler

O exemplo de código a seguir mostra como excluir um crawler do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_crawler()
            .name(self.crawler())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteCrawlerreferência da API AWS SDK for Rust.

Excluir um banco de dados do Data Catalog

O exemplo de código a seguir mostra como excluir um banco de dados do AWS Glue Data Catalog.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_database()
            .name(self.database())
            .send()
```

```
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteDatabasereferência da API AWS SDK for Rust.

Excluir uma definição de trabalho

O exemplo de código a seguir mostra como excluir uma definição de trabalho do AWS Glue e todas as execuções associadas.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        glue.delete_job()
            .job_name(self.job())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a DeleteJobreferência da API AWS SDK for Rust.

Excluir uma tabela de um banco de dados

O exemplo de código a seguir mostra como excluir uma tabela de um banco de dados do AWS Glue Data Catalog.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        for t in &self.tables {
            glue.delete_table()
                .name(t.name())
                .database_name(self.database())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
        }
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for Rust.

Obter um crawler

O exemplo de código a seguir mostra como obter um crawler AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
            let tmp_crawler = glue
                .get_crawler()
                .name(self.crawler())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte a GetCrawlerreferência da API AWS SDK for Rust.

Obter um banco de dados do Data Catalog

O exemplo de código a seguir mostra como obter um banco de dados do AWS Glue Data Catalog.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let database = glue
            .get_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?
            .to_owned();
        let database = database
            .database()
            .ok_or_else(|| GlueMvpError::Unknown("Could not find
database".into()))?;
```

- Para obter detalhes da API, consulte a GetDatabasereferência da API AWS SDK for Rust.

Obter uma execução de trabalho

Os exemplos de código a seguir mostram como obter uma execução de trabalho do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let get_job_run = || async {
            Ok::<JobRun, GlueMvpError>(
                glue.get_job_run()
                    .job_name(self.job())
                    .run_id(job_run_id.to_string())
```

```
                    .send()
                    .await
                    .map_err(GlueMvpError::from_glue_sdk)?
                    .job_run()
                    .ok_or_else(|| GlueMvpError::Unknown("Failed to get
job_run".into()))?
                    .to_owned(),
            )
        };

        let mut job_run = get_job_run().await?;
        let mut state =
job_run.job_run_state().unwrap_or(&unknown_state).to_owned();

        while matches!(
            state,
            JobRunState::Starting | JobRunState::Stopping | JobRunState::Running
        ) {
            info!(?state, "Waiting for job to finish");
            tokio::time::sleep(self.wait_delay).await;

            job_run = get_job_run().await?;
            state = job_run.job_run_state().unwrap_or(&unknown_state).to_owned();
        }
```

- Para obter detalhes da API, consulte a GetJobRunreferência da API AWS SDK for Rust.

Obter tabelas de um banco de dados

Os exemplos de código a seguir mostram como obter tabelas de um banco de dados no AWS Glue Data Catalog.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let tables = glue
```

```
            .get_tables()
            .database_name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let tables = tables.table_list();
```

- Para obter detalhes da API, consulte a GetTablesreferência da API AWS SDK for Rust.

Listar definições de trabalho

Os exemplos de código a seguir mostram como listar definições de trabalho do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let mut list_jobs = glue.list_jobs().into_paginator().send();
        while let Some(list_jobs_output) = list_jobs.next().await {
            match list_jobs_output {
                Ok(list_jobs) => {
                    let names = list_jobs.job_names();
                    info!(?names, "Found these jobs")
                }
                Err(err) => return Err(GlueMvpError::from_glue_sdk(err)),
            }
        }
```

- Para obter detalhes da API, consulte a ListJobsreferência da API AWS SDK for Rust.

Iniciar um crawler

O exemplo de código a seguir mostra como iniciar um crawler do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let start_crawler = glue.start_crawler().name(self.crawler()).send().await;

        match start_crawler {
            Ok(_) => Ok(()),
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::CrawlerRunningException(_) => Ok(()),
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
        }?;
```

- Para obter detalhes da API, consulte a StartCrawlerreferência da API AWS SDK for Rust.

Iniciar uma execução de trabalho

O exemplo de código a seguir mostra como iniciar uma execução de trabalho do AWS Glue.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let job_run_output = glue
            .start_job_run()
            .job_name(self.job())
```

```
            .arguments("--input_database", self.database())
            .arguments(
                "--input_table",
                self.tables
                    .get(0)
                    .ok_or_else(|| GlueMvpError::Unknown("Missing crawler
table".into()))?
                    .name(),
            )
            .arguments("--output_bucket_url", self.bucket())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job = job_run_output
            .job_run_id()
            .ok_or_else(|| GlueMvpError::Unknown("Missing run id from just started
job".into()))?
            .to_string();
```

- Para obter detalhes da API, consulte a StartJobRunreferência da API AWS SDK for Rust.

Cenários

Começar a executar crawlers e trabalhos

O código de exemplo a seguir mostra como:

- Criar um crawler que rastreie um bucket público do Amazon S3 e gere um banco de dados de metadados formatado em CSV.
- Listar informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.
- Criar um trabalho para extrair dados em CSV do bucket do S3, transformá-los e carregar a saída formatada em JSON em outro bucket do S3.
- Listar informações sobre execuções de tarefas, visualizar dados transformados e limpar recursos.

Para obter mais informações, consulte Tutorial: conceitos básicos do AWS Glue Studio.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie e execute um crawler que examine um bucket público do Amazon Simple Storage Service (Amazon S3) e gere um banco de dados de metadados que descreva os dados no formato CSV que encontrar.

```
        let create_crawler = glue
            .create_crawler()
            .name(self.crawler())
            .database_name(self.database())
            .role(self.iam_role.expose_secret())
            .targets(
                CrawlerTargets::builder()
                    .s3_targets(S3Target::builder().path(CRAWLER_TARGET).build())
                    .build(),
            )
            .send()
            .await;

        match create_crawler {
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::AlreadyExistsException(_) => {
                        info!("Using existing crawler");
                        Ok(())
                    }
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
            Ok(_) => Ok(()),
        }?;

        let start_crawler = glue.start_crawler().name(self.crawler()).send().await;

        match start_crawler {
```

```
            Ok(_) => Ok(()),
            Err(err) => {
                let glue_err: aws_sdk_glue::Error = err.into();
                match glue_err {
                    aws_sdk_glue::Error::CrawlerRunningException(_) => Ok(()),
                    _ => Err(GlueMvpError::GlueSdk(glue_err)),
                }
            }
        }?;
```

Liste informações sobre bancos de dados e tabelas no AWS Glue Data Catalog.

```
        let database = glue
            .get_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?
            .to_owned();
        let database = database
            .database()
            .ok_or_else(|| GlueMvpError::Unknown("Could not find
 database".into()))?;

        let tables = glue
            .get_tables()
            .database_name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let tables = tables.table_list();
```

Crie e execute um trabalho que extraia dados em CSV do bucket do Amazon S3 de origem, transforme-os removendo e renomeando campos, e carregue a saída formatada em JSON em outro bucket do Amazon S3.

```
        let create_job = glue
            .create_job()
            .name(self.job())
            .role(self.iam_role.expose_secret())
```

```
            .command(
                JobCommand::builder()
                    .name("glueetl")
                    .python_version("3")
                    .script_location(format!("s3://{}/job.py", self.bucket()))
                    .build(),
            )
            .glue_version("3.0")
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job_name = create_job.name().ok_or_else(|| {
            GlueMvpError::Unknown("Did not get job name after creating job".into())
        })?;

        let job_run_output = glue
            .start_job_run()
            .job_name(self.job())
            .arguments("--input_database", self.database())
            .arguments(
                "--input_table",
                self.tables
                    .get(0)
                    .ok_or_else(|| GlueMvpError::Unknown("Missing crawler
table".into()))?
                    .name(),
            )
            .arguments("--output_bucket_url", self.bucket())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        let job = job_run_output
            .job_run_id()
            .ok_or_else(|| GlueMvpError::Unknown("Missing run id from just started
job".into()))?
            .to_string();
```

Exclua todos os recursos criados pela demonstração.

```
        glue.delete_job()
```

```
            .job_name(self.job())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        for t in &self.tables {
            glue.delete_table()
                .name(t.name())
                .database_name(self.database())
                .send()
                .await
                .map_err(GlueMvpError::from_glue_sdk)?;
        }

        glue.delete_database()
            .name(self.database())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;

        glue.delete_crawler()
            .name(self.crawler())
            .send()
            .await
            .map_err(GlueMvpError::from_glue_sdk)?;
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob

- GetJobRun
- GetJobRuns
- GetTables
- ListJobs
- StartCrawler
- StartJobRun

Exemplos do IAM usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Conceitos básicos

Hello IAM

O exemplo de código a seguir mostra como começar a usar o IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

De src/bin/hello.rs.

```
use aws_sdk_iam::error::SdkError;
use aws_sdk_iam::operation::list_policies::ListPoliciesError;
use clap::Parser;

const PATH_PREFIX_HELP: &str = "The path prefix for filtering the results.";

#[derive(Debug, clap::Parser)]
#[command(about)]
struct HelloScenarioArgs {
    #[arg(long, default_value="/", help=PATH_PREFIX_HELP)]
    pub path_prefix: String,
}

#[tokio::main]
async fn main() -> Result<(), SdkError<ListPoliciesError>> {
    let sdk_config = aws_config::load_from_env().await;
    let client = aws_sdk_iam::Client::new(&sdk_config);

    let args = HelloScenarioArgs::parse();

    iam_service::list_policies(client, args.path_prefix).await?;

    Ok(())
}
```

De src/ iam-service-lib .rs.

```
pub async fn list_policies(
    client: iamClient,
    path_prefix: String,
) -> Result<Vec<String>, SdkError<ListPoliciesError>> {
    let list_policies = client
        .list_policies()
        .path_prefix(path_prefix)
        .scope(PolicyScopeType::Local)
        .into_paginator()
        .items()
        .send()
        .try_collect()
        .await?;

    let policy_names = list_policies
```

```
        .into_iter()
        .map(|p| {
            let name = p
                .policy_name
                .unwrap_or_else(|| "Missing Policy Name".to_string());
            println!("{}", name);
            name
        })
        .collect();

    Ok(policy_names)
}
```

- Para obter detalhes da API, consulte a ListPoliciesreferência da API AWS SDK for Rust.

Tópicos

- Ações
- Cenários

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn attach_role_policy(
    client: &iamClient,
    role: &Role,
    policy: &Policy,
) -> Result<AttachRolePolicyOutput, SdkError<AttachRolePolicyError>> {
```

```
    client
        .attach_role_policy()
        .role_name(role.role_name())
        .policy_arn(policy.arn().unwrap_or_default())
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a AttachRolePolicyreferência da API AWS SDK for Rust.

Anexar uma política a um usuário

Os exemplos de código a seguir mostram como anexar uma política do IAM a um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn attach_user_policy(
    client: &iamClient,
    user_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .attach_user_policy()
        .user_name(user_name)
        .policy_arn(policy_arn)
        .send()
```

```
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a AttachUserPolicyreferência da API AWS SDK for Rust.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_policy(
    client: &iamClient,
    policy_name: &str,
    policy_document: &str,
) -> Result<Policy, iamError> {
    let policy = client
        .create_policy()
        .policy_name(policy_name)
        .policy_document(policy_document)
        .send()
        .await?;
    Ok(policy.policy.unwrap())
}
```

- Para obter detalhes da API, consulte a CreatePolicyreferência da API AWS SDK for Rust.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_role(
    client: &iamClient,
    role_name: &str,
    role_policy_document: &str,
) -> Result<Role, iamError> {
    let response: CreateRoleOutput = loop {
        if let Ok(response) = client
            .create_role()
            .role_name(role_name)
            .assume_role_policy_document(role_policy_document)
            .send()
            .await
        {
            break response;
        }
    };

    Ok(response.role.unwrap())
}
```

- Para obter detalhes da API, consulte a CreateRolereferência da API AWS SDK for Rust.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_service_linked_role(
    client: &iamClient,
    aws_service_name: String,
    custom_suffix: Option<String>,
    description: Option<String>,
) -> Result<CreateServiceLinkedRoleOutput, SdkError<CreateServiceLinkedRoleError>> {
    let response = client
        .create_service_linked_role()
        .aws_service_name(aws_service_name)
        .set_custom_suffix(custom_suffix)
        .set_description(description)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a CreateServiceLinkedRolereferência da API AWS SDK for Rust.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_user(client: &iamClient, user_name: &str) -> Result<User,
 iamError> {
    let response = client.create_user().user_name(user_name).send().await?;

    Ok(response.user.unwrap())
}
```

- Para obter detalhes da API, consulte a CreateUserreferência da API AWS SDK for Rust.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_access_key(client: &iamClient, user_name: &str) ->
 Result<AccessKey, iamError> {
```

```
    let mut tries: i32 = 0;
    let max_tries: i32 = 10;

    let response: Result<CreateAccessKeyOutput, SdkError<CreateAccessKeyError>> =
 loop {
        match client.create_access_key().user_name(user_name).send().await {
            Ok(inner_response) => {
                break Ok(inner_response);
            }
            Err(e) => {
                tries += 1;
                if tries > max_tries {
                    break Err(e);
                }
                sleep(Duration::from_secs(2)).await;
            }
        }
    };

    Ok(response.unwrap().access_key.unwrap())
}
```

- Para obter detalhes da API, consulte a CreateAccessKeyreferência da API AWS SDK for Rust.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_policy(client: &iamClient, policy: Policy) -> Result<(),
 iamError> {
    client
        .delete_policy()
        .policy_arn(policy.arn.unwrap())
```

```
        .send()
        .await?;
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeletePolicyreferência da API AWS SDK for Rust.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_role(client: &iamClient, role: &Role) -> Result<(), iamError> {
    let role = role.clone();
    while client
        .delete_role()
        .role_name(role.role_name())
        .send()
        .await
        .is_err()
    {
        sleep(Duration::from_secs(2)).await;
    }
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteRolereferência da API AWS SDK for Rust.

Excluir um perfil vinculado ao serviço

Os exemplos de código a seguir mostram como excluir um perfil vinculado ao serviço do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_service_linked_role(
    client: &iamClient,
    role_name: &str,
) -> Result<(), iamError> {
    client
        .delete_service_linked_role()
        .role_name(role_name)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteServiceLinkedRolereferência da API AWS SDK for Rust.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_user(client: &iamClient, user: &User) -> Result<(),
 SdkError<DeleteUserError>> {
    let user = user.clone();
    let mut tries: i32 = 0;
    let max_tries: i32 = 10;

    let response: Result<(), SdkError<DeleteUserError>> = loop {
        match client
            .delete_user()
            .user_name(user.user_name())
            .send()
            .await
        {
            Ok(_) => {
                break Ok(());
            }
            Err(e) => {
                tries += 1;
                if tries > max_tries {
                    break Err(e);
                }
                sleep(Duration::from_secs(2)).await;
            }
        }
    };

    response
}
```

- Para obter detalhes da API, consulte a DeleteUserreferência da API AWS SDK for Rust.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_access_key(
    client: &iamClient,
    user: &User,
    key: &AccessKey,
) -> Result<(), iamError> {
    loop {
        match client
            .delete_access_key()
            .user_name(user.user_name())
            .access_key_id(key.access_key_id())
            .send()
            .await
        {
            Ok(_) => {
                break;
            }
            Err(e) => {
                println!("Can't delete the access key: {:?}", e);
                sleep(Duration::from_secs(2)).await;
            }
        }
    }
```

```
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteAccessKeyreferência da API AWS SDK for Rust.

Excluir uma política em linha de um usuário

O exemplo de código a seguir mostra como excluir uma política em linha do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_user_policy(
    client: &iamClient,
    user: &User,
    policy_name: &str,
) -> Result<(), SdkError<DeleteUserPolicyError>> {
    client
        .delete_user_policy()
        .user_name(user.user_name())
        .policy_name(policy_name)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteUserPolicyreferência da API AWS SDK for Rust.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn detach_role_policy(
    client: &iamClient,
    role_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .detach_role_policy()
        .role_name(role_name)
        .policy_arn(policy_arn)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DetachRolePolicyreferência da API AWS SDK for Rust.

Desanexar uma política de um usuário

Os exemplos de código a seguir mostram como desanexar uma política do IAM de um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn detach_user_policy(
    client: &iamClient,
    user_name: &str,
    policy_arn: &str,
) -> Result<(), iamError> {
    client
        .detach_user_policy()
        .user_name(user_name)
        .policy_arn(policy_arn)
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a DetachUserPolicyreferência da API AWS SDK for Rust.

Obter um perfil

Os exemplos de código a seguir mostram como obter um perfil do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn get_role(
    client: &iamClient,
    role_name: String,
) -> Result<GetRoleOutput, SdkError<GetRoleError>> {
    let response = client.get_role().role_name(role_name).send().await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a GetRolereferência da API AWS SDK for Rust.

Obter a política de senha da conta

O exemplo de código a seguir mostra como obter a política de senha da conta do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn get_account_password_policy(
    client: &iamClient,
) -> Result<GetAccountPasswordPolicyOutput, SdkError<GetAccountPasswordPolicyError>>
 {
    let response = client.get_account_password_policy().send().await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a GetAccountPasswordPolicyreferência da API AWS SDK for Rust.

Listar provedores SAML

O exemplo de código a seguir mostra como listar provedores SAML para o IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
pub async fn list_saml_providers(
    client: &Client,
) -> Result<ListSamlProvidersOutput, SdkError<ListSAMLProvidersError>> {
    let response = client.list_saml_providers().send().await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte ListSAMLProvider na referência da API do AWS SDK for Rust.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_groups(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListGroupsOutput, SdkError<ListGroupsError>> {
    let response = client
        .list_groups()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListGroupsreferência da API AWS SDK for Rust.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_role_policies(
    client: &iamClient,
    role_name: &str,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListRolePoliciesOutput, SdkError<ListRolePoliciesError>> {
    let response = client
        .list_role_policies()
        .role_name(role_name)
```

```
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListRolePoliciesreferência da API AWS SDK for Rust.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_policies(
    client: iamClient,
    path_prefix: String,
) -> Result<Vec<String>, SdkError<ListPoliciesError>> {
    let list_policies = client
        .list_policies()
        .path_prefix(path_prefix)
        .scope(PolicyScopeType::Local)
        .into_paginator()
        .items()
        .send()
        .try_collect()
        .await?;

    let policy_names = list_policies
        .into_iter()
        .map(|p| {
            let name = p
                .policy_name
```

```
                .unwrap_or_else(|| "Missing Policy Name".to_string());
            println!("{}", name);
            name
        })
        .collect();

    Ok(policy_names)
}
```

- Para obter detalhes da API, consulte a ListPoliciesreferência da API AWS SDK for Rust.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas anexadas a um perfil do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_attached_role_policies(
    client: &iamClient,
    role_name: String,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListAttachedRolePoliciesOutput, SdkError<ListAttachedRolePoliciesError>>
 {
    let response = client
        .list_attached_role_policies()
        .role_name(role_name)
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;

    Ok(response)
```

```
}
```

- Para obter detalhes da API, consulte a ListAttachedRolePoliciesreferência da API AWS SDK for Rust.

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_roles(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListRolesOutput, SdkError<ListRolesError>> {
    let response = client
        .list_roles()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListRolesreferência da API AWS SDK for Rust.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_users(
    client: &iamClient,
    path_prefix: Option<String>,
    marker: Option<String>,
    max_items: Option<i32>,
) -> Result<ListUsersOutput, SdkError<ListUsersError>> {
    let response = client
        .list_users()
        .set_path_prefix(path_prefix)
        .set_marker(marker)
        .set_max_items(max_items)
        .send()
        .await?;
    Ok(response)
}
```

- Para obter detalhes da API, consulte a ListUsersreferência da API AWS SDK for Rust.

Cenários

Criar um usuário e assumir uma função

O exemplo de código a seguir mostra como criar um usuário e assumir um perfil.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

- Crie um usuário sem permissões.
- Crie uma função que conceda permissão para listar os buckets do Amazon S3 para a conta.
- Adicione uma política para permitir que o usuário assuma a função.
- Assuma o perfil e liste buckets do S3 usando credenciais temporárias, depois limpe os recursos.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e veja como configurar e executar no repositório de exemplos de código da AWS.

```
use aws_config::meta::region::RegionProviderChain;
use aws_sdk_iam::Error as iamError;
use aws_sdk_iam::{config::Credentials as iamCredentials, config::Region, Client as
 iamClient};
use aws_sdk_s3::Client as s3Client;
use aws_sdk_sts::Client as stsClient;
use tokio::time::{sleep, Duration};
use uuid::Uuid;

#[tokio::main]
async fn main() -> Result<(), iamError> {
    let (client, uuid, list_all_buckets_policy_document, inline_policy_document) =
        initialize_variables().await;

    if let Err(e) = run_iam_operations(
        client,
        uuid,
        list_all_buckets_policy_document,
```

```
        inline_policy_document,
    )
    .await
    {
        println!("{:?}", e);
    };

    Ok(())
}

async fn initialize_variables() -> (iamClient, String, String, String) {
    let region_provider = RegionProviderChain::first_try(Region::new("us-west-2"));

    let shared_config = aws_config::from_env().region(region_provider).load().await;
    let client = iamClient::new(&shared_config);
    let uuid = Uuid::new_v4().to_string();

    let list_all_buckets_policy_document = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"s3:ListAllMyBuckets\",
                    \"Resource\": \"arn:aws:s3:::*\"}]
    }"
    .to_string();
    let inline_policy_document = "{
                \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Action\": \"sts:AssumeRole\",
                    \"Resource\": \"{}\"}]
    }"
    .to_string();

    (
        client,
        uuid,
        list_all_buckets_policy_document,
        inline_policy_document,
    )
}

async fn run_iam_operations(
    client: iamClient,
```

```
    uuid: String,
    list_all_buckets_policy_document: String,
    inline_policy_document: String,
) -> Result<(), iamError> {
    let user = iam_service::create_user(&client, &format!("{}{}", "iam_demo_user_",
 uuid)).await?;
    println!("Created the user with the name: {}", user.user_name());
    let key = iam_service::create_access_key(&client, user.user_name()).await?;

    let assume_role_policy_document = "{
        \"Version\": \"2012-10-17\",
                \"Statement\": [{
                    \"Effect\": \"Allow\",
                    \"Principal\": {\"AWS\": \"{}\"},
                    \"Action\": \"sts:AssumeRole\"
                }]
            }"
    .to_string()
    .replace("{}", user.arn());

    let assume_role_role = iam_service::create_role(
        &client,
        &format!("{}{}", "iam_demo_role_", uuid),
        &assume_role_policy_document,
    )
    .await?;
    println!("Created the role with the ARN: {}", assume_role_role.arn());

    let list_all_buckets_policy = iam_service::create_policy(
        &client,
        &format!("{}{}", "iam_demo_policy_", uuid),
        &list_all_buckets_policy_document,
    )
    .await?;
    println!(
        "Created policy: {}",
        list_all_buckets_policy.policy_name.as_ref().unwrap()
    );

    let attach_role_policy_result =
        iam_service::attach_role_policy(&client, &assume_role_role,
 &list_all_buckets_policy)
            .await?;
    println!(
```

```
        "Attached the policy to the role: {:?}",
        attach_role_policy_result
    );

    let inline_policy_name = format!("{}{}", "iam_demo_inline_policy_", uuid);
    let inline_policy_document = inline_policy_document.replace("{}",
assume_role_role.arn());
    iam_service::create_user_policy(&client, &user, &inline_policy_name,
&inline_policy_document)
        .await?;
    println!("Created inline policy.");

    //First, fail to list the buckets with the user.
    let creds = iamCredentials::from_keys(key.access_key_id(),
key.secret_access_key(), None);
    let fail_config = aws_config::from_env()
        .credentials_provider(creds.clone())
        .load()
        .await;
    println!("Fail config: {:?}", fail_config);
    let fail_client: s3Client = s3Client::new(&fail_config);
    match fail_client.list_buckets().send().await {
        Ok(e) => {
            println!("This should not run. {:?}", e);
        }
        Err(e) => {
            println!("Successfully failed with error: {:?}", e)
        }
    }

    let sts_config = aws_config::from_env()
        .credentials_provider(creds.clone())
        .load()
        .await;
    let sts_client: stsClient = stsClient::new(&sts_config);
    sleep(Duration::from_secs(10)).await;
    let assumed_role = sts_client
        .assume_role()
        .role_arn(assume_role_role.arn())
        .role_session_name(&format!("{}{}", "iam_demo_assumerole_session_", uuid))
        .send()
        .await;
    println!("Assumed role: {:?}", assumed_role);
    sleep(Duration::from_secs(10)).await;
```

```
    let assumed_credentials = iamCredentials::from_keys(
        assumed_role
            .as_ref()
            .unwrap()
            .credentials
            .as_ref()
            .unwrap()
            .access_key_id(),
        assumed_role
            .as_ref()
            .unwrap()
            .credentials
            .as_ref()
            .unwrap()
            .secret_access_key(),
        Some(
            assumed_role
                .as_ref()
                .unwrap()
                .credentials
                .as_ref()
                .unwrap()
                .session_token
                .clone(),
        ),
    );

    let succeed_config = aws_config::from_env()
        .credentials_provider(assumed_credentials)
        .load()
        .await;
    println!("succeed config: {:?}", succeed_config);
    let succeed_client: s3Client = s3Client::new(&succeed_config);
    sleep(Duration::from_secs(10)).await;
    match succeed_client.list_buckets().send().await {
        Ok(_) => {
            println!("This should now run successfully.")
        }
        Err(e) => {
            println!("This should not run. {:?}", e);
            panic!()
        }
    }
```

```
    //Clean up.
    iam_service::detach_role_policy(
        &client,
        assume_role_role.role_name(),
        list_all_buckets_policy.arn().unwrap_or_default(),
    )
    .await?;
    iam_service::delete_policy(&client, list_all_buckets_policy).await?;
    iam_service::delete_role(&client, &assume_role_role).await?;
    println!("Deleted role {}", assume_role_role.role_name());
    iam_service::delete_access_key(&client, &user, &key).await?;
    println!("Deleted key for {}", key.user_name());
    iam_service::delete_user_policy(&client, &user, &inline_policy_name).await?;
    println!("Deleted inline user policy: {}", inline_policy_name);
    iam_service::delete_user(&client, &user).await?;
    println!("Deleted user {}", user.user_name());

    Ok(())
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Exemplos de AWS IoT usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com AWS IoT.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter informações do endpoint

O exemplo de código a seguir mostra como obter informação de endpoint AWS IoT.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_address(client: &Client, endpoint_type: &str) -> Result<(), Error> {
    let resp = client
        .describe_endpoint()
        .endpoint_type(endpoint_type)
        .send()
        .await?;

    println!("Endpoint address: {}", resp.endpoint_address.unwrap());
```

```
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeEndpointreferência da API AWS SDK for Rust.

Listar coisas

O exemplo de código a seguir mostra como listar AWS IoT coisas.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_things(client: &Client) -> Result<(), Error> {
    let resp = client.list_things().send().await?;

    println!("Things:");

    for thing in resp.things.unwrap() {
        println!(
            "  Name:  {}",
            thing.thing_name.as_deref().unwrap_or_default()
        );
        println!(
            "  Type:  {}",
            thing.thing_type_name.as_deref().unwrap_or_default()
        );
        println!(
            "  ARN:   {}",
            thing.thing_arn.as_deref().unwrap_or_default()
        );
        println!();
    }
```

```
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListThingsreferência da API AWS SDK for Rust.

Exemplos do Kinesis usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Criar um stream

O exemplo de código a seguir mostra como criar um stream do Kinesis.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_stream(client: &Client, stream: &str) -> Result<(), Error> {
    client
        .create_stream()
        .stream_name(stream)
        .shard_count(4)
        .send()
        .await?;

    println!("Created stream");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateStreamreferência da API AWS SDK for Rust.

Excluir um stream

O exemplo de código a seguir mostra como excluir um stream do Kinesis.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_stream(client: &Client, stream: &str) -> Result<(), Error> {
    client.delete_stream().stream_name(stream).send().await?;

    println!("Deleted stream.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteStreamreferência da API AWS SDK for Rust.

Descrever um stream

O exemplo de código a seguir mostra como descrever um stream do Kinesis.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_stream(client: &Client, stream: &str) -> Result<(), Error> {
    let resp = client.describe_stream().stream_name(stream).send().await?;

    let desc = resp.stream_description.unwrap();

    println!("Stream description:");
    println!("  Name:              {}:", desc.stream_name());
    println!("  Status:            {:?}", desc.stream_status());
    println!("  Open shards:       {:?}", desc.shards.len());
    println!("  Retention (hours): {}", desc.retention_period_hours());
    println!("  Encryption:        {:?}", desc.encryption_type.unwrap());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeStreamreferência da API AWS SDK for Rust.

Listar streams

O exemplo de código a seguir mostra como listar informações sobre um ou mais streams do Kinesis.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_streams(client: &Client) -> Result<(), Error> {
    let resp = client.list_streams().send().await?;

    println!("Stream names:");

    let streams = resp.stream_names;
    for stream in &streams {
        println!("  {}", stream);
    }

    println!("Found {} stream(s)", streams.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListStreamsreferência da API AWS SDK for Rust.

Inserir dados em um stream

O exemplo de código a seguir mostra como inserir dados em um stream do Kinesis.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_record(client: &Client, stream: &str, key: &str, data: &str) ->
 Result<(), Error> {
    let blob = Blob::new(data);

    client
        .put_record()
        .data(blob)
        .partition_key(key)
        .stream_name(stream)
        .send()
        .await?;
```

```
    println!("Put data into stream.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutRecordreferência da API AWS SDK for Rust.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::event::kinesis::KinesisEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) -> Result<(), Error> {
    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(());
    }

    event.payload.records.iter().for_each(|record| {
        tracing::info!("EventId:
 {}",record.event_id.as_deref().unwrap_or_default());

        let record_data = std::str::from_utf8(&record.kinesis.data);
```

```
        match record_data {
            Ok(data) => {
                // log the record data
                tracing::info!("Data: {}", data);
            }
            Err(e) => {
                tracing::error!("Error: {}", e);
            }
        }
    });

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relate falhas de itens em lote do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::kinesis::KinesisEvent,
    kinesis::KinesisEventRecord,
    streams::{KinesisBatchItemFailure, KinesisEventResponse},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) ->
 Result<KinesisEventResponse, Error> {
    let mut response = KinesisEventResponse {
        batch_item_failures: vec![],
    };

    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(response);
    }

    for record in &event.payload.records {
        tracing::info!(
            "EventId: {}",
            record.event_id.as_deref().unwrap_or_default()
        );

        let record_processing_result = process_record(record);

        if record_processing_result.is_err() {
            response.batch_item_failures.push(KinesisBatchItemFailure {
                item_identifier: record.kinesis.sequence_number.clone(),
            });
            /* Since we are working with streams, we can return the failed item
 immediately.
```

```
            Lambda will immediately begin to retry processing from this failed item
 onwards. */
            return Ok(response);
        }
    }

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(response)
}

fn process_record(record: &KinesisEventRecord) -> Result<(), Error> {
    let record_data = std::str::from_utf8(record.kinesis.data.as_slice());

    if let Some(err) = record_data.err() {
        tracing::error!("Error: {}", err);
        return Err(Error::from(err));
    }

    let record_data = record_data.unwrap_or_default();

    // do something interesting with the data
    tracing::info!("Data: {}", record_data);

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Exemplos de Firehose usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com Firehose.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Gravar múltiplos registros de dados

O exemplo de código a seguir mostra como gravar vários registros de dados em um stream de entrega do Firehose em uma única chamada, o que pode atingir uma taxa de transferência maior por produtor do que ao gravar registros únicos.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn put_record_batch(
    client: &Client,
    stream: &str,
    data: Vec<Record>,
) -> Result<PutRecordBatchOutput, SdkError<PutRecordBatchError>> {
    client
```

```
        .put_record_batch()
        .delivery_stream_name(stream)
        .set_records(Some(data))
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a PutRecordBatchreferência da API AWS SDK for Rust.

Exemplos de AWS KMS usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com AWS KMS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar uma chave

O exemplo de código a seguir mostra como criar AWS KMS key.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client) -> Result<(), Error> {
    let resp = client.create_key().send().await?;

    let id = resp.key_metadata.as_ref().unwrap().key_id();

    println!("Key: {}", id);

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateKeyreferência da API AWS SDK for Rust.

Criar uma sequência de bytes aleatória

O exemplo de código a seguir mostra como criar uma sequência de bytes aleatória que é criptograficamente segura usando AWS KMS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_string(client: &Client, length: i32) -> Result<(), Error> {
    let resp = client
        .generate_random()
        .number_of_bytes(length)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.plaintext.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    println!();
    println!("Data key:");
```

```
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateRandomreferência da API AWS SDK for Rust.

Descriptografar texto cifrado

O exemplo de código a seguir mostra como descriptografar texto cifrado que foi criptografado com uma chave KMS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn decrypt_key(client: &Client, key: &str, filename: &str) -> Result<(),
 Error> {
    // Open input text file and get contents as a string
    // input is a base-64 encoded string, so decode it:
    let data = fs::read_to_string(filename)
        .map(|input| {
            base64::decode(input).expect("Input file does not contain valid base 64
 characters.")
        })
        .map(Blob::new);

    let resp = client
        .decrypt()
        .key_id(key)
        .ciphertext_blob(data.unwrap())
        .send()
        .await?;

    let inner = resp.plaintext.unwrap();
    let bytes = inner.as_ref();
```

```
    let s = String::from_utf8(bytes.to_vec()).expect("Could not convert to UTF-8");

    println!();
    println!("Decoded string:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte Descriptografar na AWS Referência da API SDK para Rust.

Criptografar texto usando uma chave

O exemplo de código a seguir mostra como criptografar texto usando uma chave KMS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn encrypt_string(
    verbose: bool,
    client: &Client,
    text: &str,
    key: &str,
    out_file: &str,
) -> Result<(), Error> {
    let blob = Blob::new(text.as_bytes());

    let resp = client.encrypt().key_id(key).plaintext(blob).send().await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();
```

```
    let s = base64::encode(bytes);

    let mut ofile = File::create(out_file).expect("unable to create file");
    ofile.write_all(s.as_bytes()).expect("unable to write");

    if verbose {
        println!("Wrote the following to {:?}", out_file);
        println!("{}", s);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte Criptografar na AWS Referência da API SDK para Rust.

Gerar uma chave de dados em texto sem formatação para criptografia do lado do cliente

O exemplo de código a seguir mostra como gerar uma chave de dados simétrica exclusiva para criptografia do lado do cliente a partir de um AWS KMS key. A chave contém versões em texto simples e em texto cifrado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client, key: &str) -> Result<(), Error> {
    let resp = client
        .generate_data_key()
        .key_id(key)
        .key_spec(DataKeySpec::Aes256)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();
```

```
    let s = base64::encode(bytes);

    println!();
    println!("Data key:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateDataKeyreferência da API AWS SDK for Rust.

Gerar uma chave de dados criptografada

O exemplo de código a seguir mostra como gerar uma chave de dados criptografada a partir de um AWS KMS key. A chave contém somente uma versão em texto cifrado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_key(client: &Client, key: &str) -> Result<(), Error> {
    let resp = client
        .generate_data_key_without_plaintext()
        .key_id(key)
        .key_spec(DataKeySpec::Aes256)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);

    println!();
```

```
    println!("Data key:");
    println!("{}", s);

    Ok(())
}
```

- Para obter detalhes da API, consulte a GenerateDataKeyWithoutPlaintextreferência da API AWS SDK for Rust.

Listar chaves

O exemplo de código a seguir mostra como listar chaves do KMS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_keys(client: &Client) -> Result<(), Error> {
    let resp = client.list_keys().send().await?;

    let keys = resp.keys.unwrap_or_default();

    let len = keys.len();

    for key in keys {
        println!("Key ARN: {}", key.key_arn.as_deref().unwrap_or_default());
    }

    println!();
    println!("Found {} keys", len);

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListKeysreferência da API AWS SDK for Rust.

Criptografar novamente o texto cifrado de uma chave para outra

O exemplo de código a seguir mostra como criptografar novamente um texto cifrado de uma chave do KMS para outra.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn reencrypt_string(
    verbose: bool,
    client: &Client,
    input_file: &str,
    output_file: &str,
    first_key: &str,
    new_key: &str,
) -> Result<(), Error> {
    // Get blob from input file
    // Open input text file and get contents as a string
    // input is a base-64 encoded string, so decode it:
    let data = fs::read_to_string(input_file)
        .map(|input_file| base64::decode(input_file).expect("invalid base 64"))
        .map(Blob::new);

    let resp = client
        .re_encrypt()
        .ciphertext_blob(data.unwrap())
        .source_key_id(first_key)
        .destination_key_id(new_key)
        .send()
        .await?;

    // Did we get an encrypted blob?
    let blob = resp.ciphertext_blob.expect("Could not get encrypted text");
    let bytes = blob.as_ref();

    let s = base64::encode(bytes);
    let o = &output_file;
```

```
    let mut ofile = File::create(o).expect("unable to create file");
    ofile.write_all(s.as_bytes()).expect("unable to write");

    if verbose {
        println!("Wrote the following to {}:", output_file);
        println!("{}", s);
    } else {
        println!("Wrote base64-encoded output to {}", output_file);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ReEncryptreferência da API AWS SDK for Rust.

Exemplos de Lambda usando SDKs para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   /**
    * Create a function, uploading from a zip file.
    */
   pub async fn create_function(&self, zip_file: PathBuf) -> Result<String,
anyhow::Error> {
       let code = self.prepare_function(zip_file, None).await?;

       let key = code.s3_key().unwrap().to_string();

       self.create_role().await;

       let role = self
           .iam_client
           .create_role()
           .role_name(self.role_name.clone())
           .assume_role_policy_document(ROLE_POLICY_DOCUMENT)
           .send()
           .await?;

       info!("Created iam role, waiting 15s for it to become active");
       tokio::time::sleep(Duration::from_secs(15)).await;

       info!("Creating lambda function {}", self.lambda_name);
       let _ = self
           .lambda_client
           .create_function()
           .function_name(self.lambda_name.clone())
           .code(code)
           .role(role.role().map(|r| r.arn()).unwrap_or_default())
```

```
            .runtime(aws_sdk_lambda::types::Runtime::Providedal2)
            .handler("_unused")
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        self.lambda_client
            .publish_version()
            .function_name(self.lambda_name.clone())
            .send()
            .await?;

        Ok(key)
    }

    /**
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --output-
format Zip`.
     */
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));

        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
```

```
            .s3_key(key)
            .build())
    }
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWS SDK for Rust.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Delete a function and its role, and if possible or necessary, its associated
code object and bucket. */
    pub async fn delete_function(
        &self,
        location: Option<String>,
    ) -> (
        Result<DeleteFunctionOutput, anyhow::Error>,
        Result<DeleteRoleOutput, anyhow::Error>,
        Option<Result<DeleteObjectOutput, anyhow::Error>>,
    ) {
        info!("Deleting lambda function {}", self.lambda_name);
        let delete_function = self
            .lambda_client
            .delete_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        info!("Deleting iam role {}", self.role_name);
        let delete_role = self
            .iam_client
```

```
            .delete_role()
            .role_name(self.role_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        let delete_object: Option<Result<DeleteObjectOutput, anyhow::Error>> =
            if let Some(location) = location {
                info!("Deleting object {location}");
                Some(
                    self.s3_client
                        .delete_object()
                        .bucket(self.bucket.clone())
                        .key(location)
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
            } else {
                info!(?location, "Skipping delete object");
                None
            };

        (delete_function, delete_role, delete_object)
    }
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWS SDK for Rust.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Get the Lambda function with this Manager's name. */
```

```
    pub async fn get_function(&self) -> Result<GetFunctionOutput, anyhow::Error> {
        info!("Getting lambda function");
        self.lambda_client
            .get_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
```

- Para obter detalhes da API, consulte a GetFunctionreferência da API AWS SDK for Rust.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Invoke the lambda function using calculator InvokeArgs. */
    pub async fn invoke(&self, args: InvokeArgs) -> Result<InvokeOutput,
 anyhow::Error> {
        info!(?args, "Invoking {}", self.lambda_name);
        let payload = serde_json::to_string(&args)?;
        debug!(?payload, "Sending payload");
        self.lambda_client
            .invoke()
            .function_name(self.lambda_name.clone())
            .payload(Blob::new(payload))
            .send()
            .await
            .map_err(anyhow::Error::from)
    }

fn log_invoke_output(invoke: &InvokeOutput, message: &str) {
```

```
    if let Some(payload) = invoke.payload().cloned() {
        let payload = String::from_utf8(payload.into_inner());
        info!(?payload, message);
    } else {
        info!("Could not extract payload")
    }
    if let Some(logs) = invoke.log_result() {
        debug!(?logs, "Invoked function logs")
    } else {
        debug!("Invoked function had no logs")
    }
}
```

- Para obter detalhes da API, consulte Invoke na Referência da API do AWS SDK para Rust.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** List all Lambda functions in the current Region. */
    pub async fn list_functions(&self) -> Result<ListFunctionsOutput, anyhow::Error>
{
        info!("Listing lambda functions");
        self.lambda_client
            .list_functions()
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
```

- Para obter detalhes da API, consulte a ListFunctionsreferência da API AWS SDK for Rust.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Given a Path to a zip file, update the function's code and wait for the
update to finish. */
    pub async fn update_function_code(
        &self,
        zip_file: PathBuf,
        key: String,
    ) -> Result<UpdateFunctionCodeOutput, anyhow::Error> {
        let function_code = self.prepare_function(zip_file, Some(key)).await?;

        info!("Updating code for {}", self.lambda_name);
        let update = self
            .lambda_client
            .update_function_code()
            .function_name(self.lambda_name.clone())
            .s3_bucket(self.bucket.clone())
            .s3_key(function_code.s3_key().unwrap().to_string())
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(update)
    }

    /**
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --output-
format Zip`.
     */
```

```
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));

        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
            .s3_key(key)
            .build())
    }
```

- Para obter detalhes da API, consulte a UpdateFunctionCodereferência da API AWS SDK for Rust.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /** Update the environment for a function. */
```

```
    pub async fn update_function_configuration(
        &self,
        environment: Environment,
    ) -> Result<UpdateFunctionConfigurationOutput, anyhow::Error> {
        info!(
            ?environment,
            "Updating environment for {}", self.lambda_name
        );
        let updated = self
            .lambda_client
            .update_function_configuration()
            .function_name(self.lambda_name.clone())
            .environment(environment)
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(updated)
    }
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationreferência da API AWS SDK for Rust.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

O Cargo.toml com dependências usadas neste cenário.

```
[package]
name = "lambda-code-examples"
version = "0.1.0"
edition = "2021"

# See more keys and their definitions at https://doc.rust-lang.org/cargo/reference/
manifest.html

[dependencies]
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-sdk-ec2 = { version = "1.3.0" }
aws-sdk-iam = { version = "1.3.0" }
aws-sdk-lambda = { version = "1.3.0" }
aws-sdk-s3 = { version = "1.4.0" }
aws-smithy-types = { version = "1.0.1" }
aws-types = { version = "1.0.1" }
clap = { version = "~4.4", features = ["derive"] }
tokio = { version = "1.20.1", features = ["full"] }
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
tracing = "0.1.37"
serde_json = "1.0.94"
anyhow = "1.0.71"
uuid = { version = "1.3.3", features = ["v4"] }
lambda_runtime = "0.8.0"
serde = "1.0.164"
```

Uma coleção de utilitários que simplificam chamar o Lambda para este cenário. Este arquivo está como src/ations.rs no crate.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0
```

```
use anyhow::anyhow;
use aws_sdk_iam::operation::delete_role::DeleteRoleOutput;
use aws_sdk_lambda::{
    operation::{
        delete_function::DeleteFunctionOutput, get_function::GetFunctionOutput,
        invoke::InvokeOutput, list_functions::ListFunctionsOutput,
        update_function_code::UpdateFunctionCodeOutput,
        update_function_configuration::UpdateFunctionConfigurationOutput,
    },
    primitives::ByteStream,
    types::{Environment, FunctionCode, LastUpdateStatus, State},
};
use aws_sdk_s3::{
    operation::{delete_bucket::DeleteBucketOutput,
 delete_object::DeleteObjectOutput},
    types::CreateBucketConfiguration,
};
use aws_smithy_types::Blob;
use serde::{ser::SerializeMap, Serialize};
use std::{path::PathBuf, str::FromStr, time::Duration};
use tracing::{debug, info, warn};

/* Operation describes  */
#[derive(Clone, Copy, Debug, Serialize)]
pub enum Operation {
    #[serde(rename = "plus")]
    Plus,
    #[serde(rename = "minus")]
    Minus,
    #[serde(rename = "times")]
    Times,
    #[serde(rename = "divided-by")]
    DividedBy,
}

impl FromStr for Operation {
    type Err = anyhow::Error;

    fn from_str(s: &str) -> Result<Self, Self::Err> {
        match s {
            "plus" => Ok(Operation::Plus),
            "minus" => Ok(Operation::Minus),
            "times" => Ok(Operation::Times),
```

```
            "divided-by" => Ok(Operation::DividedBy),
            _ => Err(anyhow!("Unknown operation {s}")),
        }
    }
}

impl ToString for Operation {
    fn to_string(&self) -> String {
        match self {
            Operation::Plus => "plus".to_string(),
            Operation::Minus => "minus".to_string(),
            Operation::Times => "times".to_string(),
            Operation::DividedBy => "divided-by".to_string(),
        }
    }
}

/**
 * InvokeArgs will be serialized as JSON and sent to the AWS Lambda handler.
 */
#[derive(Debug)]
pub enum InvokeArgs {
    Increment(i32),
    Arithmetic(Operation, i32, i32),
}

impl Serialize for InvokeArgs {
    fn serialize<S>(&self, serializer: S) -> Result<S::Ok, S::Error>
    where
        S: serde::Serializer,
    {
        match self {
            InvokeArgs::Increment(i) => serializer.serialize_i32(*i),
            InvokeArgs::Arithmetic(o, i, j) => {
                let mut map: S::SerializeMap = serializer.serialize_map(Some(3))?;
                map.serialize_key(&"op".to_string())?;
                map.serialize_value(&o.to_string())?;
                map.serialize_key(&"i".to_string())?;
                map.serialize_value(&i)?;
                map.serialize_key(&"j".to_string())?;
                map.serialize_value(&j)?;
                map.end()
            }
        }
```

```
    }
}

/** A policy document allowing Lambda to execute this function on the account's
 behalf. */
const ROLE_POLICY_DOCUMENT: &str = r#"{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Principal": { "Service": "lambda.amazonaws.com" },
            "Action": "sts:AssumeRole"
        }
    ]
}"#;

/**
 * A LambdaManager gathers all the resources necessary to run the Lambda example
 scenario.
 * This includes instantiated aws_sdk clients and details of resource names.
 */
pub struct LambdaManager {
    iam_client: aws_sdk_iam::Client,
    lambda_client: aws_sdk_lambda::Client,
    s3_client: aws_sdk_s3::Client,
    lambda_name: String,
    role_name: String,
    bucket: String,
    own_bucket: bool,
}

// These unit type structs provide nominal typing on top of String parameters for
 LambdaManager::new
pub struct LambdaName(pub String);
pub struct RoleName(pub String);
pub struct Bucket(pub String);
pub struct OwnBucket(pub bool);

impl LambdaManager {
    pub fn new(
        iam_client: aws_sdk_iam::Client,
        lambda_client: aws_sdk_lambda::Client,
        s3_client: aws_sdk_s3::Client,
        lambda_name: LambdaName,
```

```
        role_name: RoleName,
        bucket: Bucket,
        own_bucket: OwnBucket,
    ) -> Self {
        Self {
            iam_client,
            lambda_client,
            s3_client,
            lambda_name: lambda_name.0,
            role_name: role_name.0,
            bucket: bucket.0,
            own_bucket: own_bucket.0,
        }
    }

    /**
     * Load the AWS configuration from the environment.
     * Look up lambda_name and bucket if none are given, or generate a random name
if not present in the environment.
     * If the bucket name is provided, the caller needs to have created the bucket.
     * If the bucket name is generated, it will be created.
     */
    pub async fn load_from_env(lambda_name: Option<String>, bucket: Option<String>)
-> Self {
        let sdk_config = aws_config::load_from_env().await;
        let lambda_name = LambdaName(lambda_name.unwrap_or_else(|| {
            std::env::var("LAMBDA_NAME").unwrap_or_else(|_|
"rust_lambda_example".to_string())
        }));
        let role_name = RoleName(format!("{}_role", lambda_name.0));
        let (bucket, own_bucket) =
            match bucket {
                Some(bucket) => (Bucket(bucket), false),
                None => (
                    Bucket(std::env::var("LAMBDA_BUCKET").unwrap_or_else(|_| {
                        format!("rust-lambda-example-{}", uuid::Uuid::new_v4())
                    })),
                    true,
                ),
            };

        let s3_client = aws_sdk_s3::Client::new(&sdk_config);

        if own_bucket {
```

```
            info!("Creating bucket for demo: {}", bucket.0);
            s3_client
                .create_bucket()
                .bucket(bucket.0.clone())
                .create_bucket_configuration(
                    CreateBucketConfiguration::builder()

 .location_constraint(aws_sdk_s3::types::BucketLocationConstraint::from(
                            sdk_config.region().unwrap().as_ref(),
                        ))
                        .build(),
                )
                .send()
                .await
                .unwrap();
        }

        Self::new(
            aws_sdk_iam::Client::new(&sdk_config),
            aws_sdk_lambda::Client::new(&sdk_config),
            s3_client,
            lambda_name,
            role_name,
            bucket,
            OwnBucket(own_bucket),
        )
    }

    // snippet-start:[lambda.rust.scenario.prepare_function]
    /**
     * Upload function code from a path to a zip file.
     * The zip file must have an AL2 Linux-compatible binary called `bootstrap`.
     * The easiest way to create such a zip is to use `cargo lambda build --output-
format Zip`.
     */
    async fn prepare_function(
        &self,
        zip_file: PathBuf,
        key: Option<String>,
    ) -> Result<FunctionCode, anyhow::Error> {
        let body = ByteStream::from_path(zip_file).await?;

        let key = key.unwrap_or_else(|| format!("{}_code", self.lambda_name));
```

```
        info!("Uploading function code to s3://{}/{}", self.bucket, key);
        let _ = self
            .s3_client
            .put_object()
            .bucket(self.bucket.clone())
            .key(key.clone())
            .body(body)
            .send()
            .await?;

        Ok(FunctionCode::builder()
            .s3_bucket(self.bucket.clone())
            .s3_key(key)
            .build())
    }
    // snippet-end:[lambda.rust.scenario.prepare_function]

    // snippet-start:[lambda.rust.scenario.create_function]
    /**
     * Create a function, uploading from a zip file.
     */
    pub async fn create_function(&self, zip_file: PathBuf) -> Result<String,
anyhow::Error> {
        let code = self.prepare_function(zip_file, None).await?;

        let key = code.s3_key().unwrap().to_string();

        self.create_role().await;

        let role = self
            .iam_client
            .create_role()
            .role_name(self.role_name.clone())
            .assume_role_policy_document(ROLE_POLICY_DOCUMENT)
            .send()
            .await?;

        info!("Created iam role, waiting 15s for it to become active");
        tokio::time::sleep(Duration::from_secs(15)).await;

        info!("Creating lambda function {}", self.lambda_name);
        let _ = self
            .lambda_client
            .create_function()
```

```
            .function_name(self.lambda_name.clone())
            .code(code)
            .role(role.role().map(|r| r.arn()).unwrap_or_default())
            .runtime(aws_sdk_lambda::types::Runtime::Providedal2)
            .handler("_unused")
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        self.lambda_client
            .publish_version()
            .function_name(self.lambda_name.clone())
            .send()
            .await?;

        Ok(key)
    }
    // snippet-end:[lambda.rust.scenario.create_function]

    /**
     * Create an IAM execution role for the managed Lambda function.
     */
    async fn create_role(&self) {
        info!("Creating execution role for function");
        if let Ok(_response) = self
            .iam_client
            .get_role()
            .role_name(self.role_name.clone())
            .send()
            .await
        {
            let delete_response = self
                .iam_client
                .delete_role()
                .role_name(self.role_name.clone())
                .send()
                .await;
            match delete_response {
                Ok(_) => debug!("Deleted role first"),
                Err(_) => {
                    warn!("Failed to delete role, will probably fail to create the
new role")
```

```
                }
            }
        }
    }

    /**
     * Poll `is_function_ready` with a 1-second delay. It returns when the function
is ready or when there's an error checking the function's state.
     */
    pub async fn wait_for_function_ready(&self) -> Result<(), anyhow::Error> {
        info!("Waiting for function");
        while !self.is_function_ready(None).await? {
            info!("Function is not ready, sleeping 1s");
            tokio::time::sleep(Duration::from_secs(1)).await;
        }
        Ok(())
    }

    /**
     * Check if a Lambda function is ready to be invoked.
     * A Lambda function is ready for this scenario when its state is active and its
LastUpdateStatus is Successful.
     * Additionally, if a sha256 is provided, the function must have that as its
current code hash.
     * Any missing properties or failed requests will be reported as an Err.
     */
    async fn is_function_ready(
        &self,
        expected_code_sha256: Option<&str>,
    ) -> Result<bool, anyhow::Error> {
        match self.get_function().await {
            Ok(func) => {
                if let Some(config) = func.configuration() {
                    if let Some(state) = config.state() {
                        info!(?state, "Checking if function is active");
                        if !matches!(state, State::Active) {
                            return Ok(false);
                        }
                    }
                    match config.last_update_status() {
                        Some(last_update_status) => {
                            info!(?last_update_status, "Checking if function is
ready");
                            match last_update_status {
```

```
                                LastUpdateStatus::Successful => {
                                    // continue
                                }
                                LastUpdateStatus::Failed |
LastUpdateStatus::InProgress => {
                                    return Ok(false);
                                }
                                unknown => {
                                    warn!(
                                        status_variant = unknown.as_str(),
                                        "LastUpdateStatus unknown"
                                    );
                                    return Err(anyhow!(
                                        "Unknown LastUpdateStatus, fn config is
{config:?}"
                                    ));
                                }
                            }
                        }
                        None => {
                            warn!("Missing last update status");
                            return Ok(false);
                        }
                    };
                    if expected_code_sha256.is_none() {
                        return Ok(true);
                    }
                    if let Some(code_sha256) = config.code_sha256() {
                        return Ok(code_sha256 ==
expected_code_sha256.unwrap_or_default());
                    }
                }
            }
            Err(e) => {
                warn!(?e, "Could not get function while waiting");
            }
        }
        Ok(false)
    }

    // snippet-start:[lambda.rust.scenario.get_function]
    /** Get the Lambda function with this Manager's name. */
    pub async fn get_function(&self) -> Result<GetFunctionOutput, anyhow::Error> {
        info!("Getting lambda function");
```

```
        self.lambda_client
            .get_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.get_function]

    // snippet-start:[lambda.rust.scenario.list_functions]
    /** List all Lambda functions in the current Region. */
    pub async fn list_functions(&self) -> Result<ListFunctionsOutput, anyhow::Error>
{
        info!("Listing lambda functions");
        self.lambda_client
            .list_functions()
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.list_functions]

    // snippet-start:[lambda.rust.scenario.invoke]
    /** Invoke the lambda function using calculator InvokeArgs. */
    pub async fn invoke(&self, args: InvokeArgs) -> Result<InvokeOutput,
anyhow::Error> {
        info!(?args, "Invoking {}", self.lambda_name);
        let payload = serde_json::to_string(&args)?;
        debug!(?payload, "Sending payload");
        self.lambda_client
            .invoke()
            .function_name(self.lambda_name.clone())
            .payload(Blob::new(payload))
            .send()
            .await
            .map_err(anyhow::Error::from)
    }
    // snippet-end:[lambda.rust.scenario.invoke]

    // snippet-start:[lambda.rust.scenario.update_function_code]
    /** Given a Path to a zip file, update the function's code and wait for the
update to finish. */
    pub async fn update_function_code(
        &self,
```

```
        zip_file: PathBuf,
        key: String,
    ) -> Result<UpdateFunctionCodeOutput, anyhow::Error> {
        let function_code = self.prepare_function(zip_file, Some(key)).await?;

        info!("Updating code for {}", self.lambda_name);
        let update = self
            .lambda_client
            .update_function_code()
            .function_name(self.lambda_name.clone())
            .s3_bucket(self.bucket.clone())
            .s3_key(function_code.s3_key().unwrap().to_string())
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(update)
    }
    // snippet-end:[lambda.rust.scenario.update_function_code]

    // snippet-start:[lambda.rust.scenario.update_function_configuration]
    /** Update the environment for a function. */
    pub async fn update_function_configuration(
        &self,
        environment: Environment,
    ) -> Result<UpdateFunctionConfigurationOutput, anyhow::Error> {
        info!(
            ?environment,
            "Updating environment for {}", self.lambda_name
        );
        let updated = self
            .lambda_client
            .update_function_configuration()
            .function_name(self.lambda_name.clone())
            .environment(environment)
            .send()
            .await
            .map_err(anyhow::Error::from)?;

        self.wait_for_function_ready().await?;

        Ok(updated)
```

```
    }
    // snippet-end:[lambda.rust.scenario.update_function_configuration]

    // snippet-start:[lambda.rust.scenario.delete_function]
    /** Delete a function and its role, and if possible or necessary, its associated
code object and bucket. */
    pub async fn delete_function(
        &self,
        location: Option<String>,
    ) -> (
        Result<DeleteFunctionOutput, anyhow::Error>,
        Result<DeleteRoleOutput, anyhow::Error>,
        Option<Result<DeleteObjectOutput, anyhow::Error>>,
    ) {
        info!("Deleting lambda function {}", self.lambda_name);
        let delete_function = self
            .lambda_client
            .delete_function()
            .function_name(self.lambda_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        info!("Deleting iam role {}", self.role_name);
        let delete_role = self
            .iam_client
            .delete_role()
            .role_name(self.role_name.clone())
            .send()
            .await
            .map_err(anyhow::Error::from);

        let delete_object: Option<Result<DeleteObjectOutput, anyhow::Error>> =
            if let Some(location) = location {
                info!("Deleting object {location}");
                Some(
                    self.s3_client
                        .delete_object()
                        .bucket(self.bucket.clone())
                        .key(location)
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
```

```
            } else {
                info!(?location, "Skipping delete object");
                None
            };

        (delete_function, delete_role, delete_object)
    }
    // snippet-end:[lambda.rust.scenario.delete_function]

    pub async fn cleanup(
        &self,
        location: Option<String>,
    ) -> (
        (
            Result<DeleteFunctionOutput, anyhow::Error>,
            Result<DeleteRoleOutput, anyhow::Error>,
            Option<Result<DeleteObjectOutput, anyhow::Error>>,
        ),
        Option<Result<DeleteBucketOutput, anyhow::Error>>,
    ) {
        let delete_function = self.delete_function(location).await;

        let delete_bucket = if self.own_bucket {
            info!("Deleting bucket {}", self.bucket);
            if delete_function.2.is_none() ||
delete_function.2.as_ref().unwrap().is_ok() {
                Some(
                    self.s3_client
                        .delete_bucket()
                        .bucket(self.bucket.clone())
                        .send()
                        .await
                        .map_err(anyhow::Error::from),
                )
            } else {
                None
            }
        } else {
            info!("No bucket to clean up");
            None
        };

        (delete_function, delete_bucket)
    }
```

```
}

/**
 * Testing occurs primarily as an integration test running the `scenario` bin
 successfully.
 * Each action relies deeply on the internal workings and state of Amazon Simple
 Storage Service (Amazon S3), Lambda, and IAM working together.
 * It is therefore infeasible to mock the clients to test the individual actions.
 */
#[cfg(test)]
mod test {
    use super::{InvokeArgs, Operation};
    use serde_json::json;

    /** Make sure that the JSON output of serializing InvokeArgs is what's expected
 by the calculator. */
    #[test]
    fn test_serialize() {
        assert_eq!(json!(InvokeArgs::Increment(5)), 5);
        assert_eq!(
            json!(InvokeArgs::Arithmetic(Operation::Plus, 5, 7)).to_string(),
            r#"{"i":5,"j":7,"op":"plus"}"#.to_string(),
        );
    }
}
```

Um binário para executar o cenário do início ao fim usando sinalizadores de linha de comando para controlar algum comportamento. Este arquivo está como src/bin/scenario.rs no crate.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

/*
## Service actions

Service actions wrap the SDK call, taking a client and any specific parameters
 necessary for the call.

* CreateFunction
* GetFunction
* ListFunctions
* Invoke
```

```
* UpdateFunctionCode
* UpdateFunctionConfiguration
* DeleteFunction

## Scenario
A scenario runs at a command prompt and prints output to the user on the result
 of each service action. A scenario can run in one of two ways: straight through,
 printing out progress as it goes, or as an interactive question/answer script.

## Getting started with functions

Use an SDK to manage AWS Lambda functions: create a function, invoke it, update its
 code, invoke it again, view its output and logs, and delete it.

This scenario uses two Lambda handlers:
_Note: Handlers don't use AWS SDK API calls._

The increment handler is straightforward:

1. It accepts a number, increments it, and returns the new value.
2. It performs simple logging of the result.

The arithmetic handler is more complex:
1. It accepts a set of actions ['plus', 'minus', 'times', 'divided-by'] and two
 numbers, and returns the result of the calculation.
2. It uses an environment variable to control log level (such as DEBUG, INFO,
 WARNING, ERROR).
It logs a few things at different levels, such as:
    * DEBUG: Full event data.
    * INFO: The calculation result.
    * WARN~ING~: When a divide by zero error occurs.
    * This will be the typical `RUST_LOG` variable.


The steps of the scenario are:

1. Create an AWS Identity and Access Management (IAM) role that meets the following
 requirements:
    * Has an assume_role policy that grants 'lambda.amazonaws.com' the
 'sts:AssumeRole' action.
    * Attaches the 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole' managed role.
    * _You must wait for ~10 seconds after the role is created before you can use
 it!_
```

```
2. Create a function (CreateFunction) for the increment handler by packaging it as a
 zip and doing one of the following:
    * Adding it with CreateFunction Code.ZipFile.
    * --or--
    * Uploading it to Amazon Simple Storage Service (Amazon S3) and adding it with
 CreateFunction Code.S3Bucket/S3Key.
    * _Note: Zipping the file does not have to be done in code._
    * If you have a waiter, use it to wait until the function is active. Otherwise,
 call GetFunction until State is Active.
3. Invoke the function with a number and print the result.
4. Update the function (UpdateFunctionCode) to the arithmetic handler by packaging
 it as a zip and doing one of the following:
    * Adding it with UpdateFunctionCode ZipFile.
    * --or--
    * Uploading it to Amazon S3 and adding it with UpdateFunctionCode S3Bucket/
S3Key.
5. Call GetFunction until Configuration.LastUpdateStatus is 'Successful' (or
 'Failed').
6. Update the environment variable by calling UpdateFunctionConfiguration and pass
 it a log level, such as:
    * Environment={'Variables': {'RUST_LOG': 'TRACE'}}
7. Invoke the function with an action from the list and a couple of values. Include
 LogType='Tail' to get logs in the result. Print the result of the calculation and
 the log.
8. [Optional] Invoke the function to provoke a divide-by-zero error and show the log
 result.
9. List all functions for the account, using pagination (ListFunctions).
10. Delete the function (DeleteFunction).
11. Delete the role.

Each step should use the function created in Service Actions to abstract calling the
 SDK.
 */

use aws_sdk_lambda::{operation::invoke::InvokeOutput, types::Environment};
use clap::Parser;
use std::{collections::HashMap, path::PathBuf};
use tracing::{debug, info, warn};
use tracing_subscriber::EnvFilter;

use lambda_code_examples::actions::{
    InvokeArgs::{Arithmetic, Increment},
    LambdaManager, Operation,
};
```

```
#[derive(Debug, Parser)]
pub struct Opt {
    /// The AWS Region.
    #[structopt(short, long)]
    pub region: Option<String>,

    // The bucket to use for the FunctionCode.
    #[structopt(short, long)]
    pub bucket: Option<String>,

    // The name of the Lambda function.
    #[structopt(short, long)]
    pub lambda_name: Option<String>,

    // The number to increment.
    #[structopt(short, long, default_value = "12")]
    pub inc: i32,

    // The left operand.
    #[structopt(long, default_value = "19")]
    pub num_a: i32,

    // The right operand.
    #[structopt(long, default_value = "23")]
    pub num_b: i32,

    // The arithmetic operation.
    #[structopt(short, long, default_value = "plus")]
    pub operation: Operation,

    #[structopt(long)]
    pub cleanup: Option<bool>,

    #[structopt(long)]
    pub no_cleanup: Option<bool>,
}

fn code_path(lambda: &str) -> PathBuf {
    PathBuf::from(format!("../target/lambda/{lambda}/bootstrap.zip"))
}

// snippet-start:[lambda.rust.scenario.log_invoke_output]
fn log_invoke_output(invoke: &InvokeOutput, message: &str) {
```

```
    if let Some(payload) = invoke.payload().cloned() {
        let payload = String::from_utf8(payload.into_inner());
        info!(?payload, message);
    } else {
        info!("Could not extract payload")
    }
    if let Some(logs) = invoke.log_result() {
        debug!(?logs, "Invoked function logs")
    } else {
        debug!("Invoked function had no logs")
    }
}
// snippet-end:[lambda.rust.scenario.log_invoke_output]

async fn main_block(
    opt: &Opt,
    manager: &LambdaManager,
    code_location: String,
) -> Result<(), anyhow::Error> {
    let invoke = manager.invoke(Increment(opt.inc)).await?;
    log_invoke_output(&invoke, "Invoked function configured as increment");

    let update_code = manager
        .update_function_code(code_path("arithmetic"), code_location.clone())
        .await?;

    let code_sha256 = update_code.code_sha256().unwrap_or("Unknown SHA");
    info!(?code_sha256, "Updated function code with arithmetic.zip");

    let arithmetic_args = Arithmetic(opt.operation, opt.num_a, opt.num_b);
    let invoke = manager.invoke(arithmetic_args).await?;
    log_invoke_output(&invoke, "Invoked function configured as arithmetic");

    let update = manager
        .update_function_configuration(
            Environment::builder()
                .set_variables(Some(HashMap::from([(
                    "RUST_LOG".to_string(),
                    "trace".to_string(),
                )])))
                .build(),
        )
        .await?;
    let updated_environment = update.environment();
```

```
    info!(?updated_environment, "Updated function configuration");

    let invoke = manager
        .invoke(Arithmetic(opt.operation, opt.num_a, opt.num_b))
        .await?;
    log_invoke_output(
        &invoke,
        "Invoked function configured as arithmetic with increased logging",
    );

    let invoke = manager
        .invoke(Arithmetic(Operation::DividedBy, opt.num_a, 0))
        .await?;
    log_invoke_output(
        &invoke,
        "Invoked function configured as arithmetic with divide by zero",
    );

    Ok::<(), anyhow::Error>(())
}

#[tokio::main]
async fn main() {
    tracing_subscriber::fmt()
        .without_time()
        .with_file(true)
        .with_line_number(true)
        .with_env_filter(EnvFilter::from_default_env())
        .init();

    let opt = Opt::parse();
    let manager = LambdaManager::load_from_env(opt.lambda_name.clone(),
 opt.bucket.clone()).await;

    let key = match manager.create_function(code_path("increment")).await {
        Ok(init) => {
            info!(?init, "Created function, initially with increment.zip");
            let run_block = main_block(&opt, &manager, init.clone()).await;
            info!(?run_block, "Finished running example, cleaning up");
            Some(init)
        }
        Err(err) => {
            warn!(?err, "Error happened when initializing function");
            None
```

```
        }
    };

    if Some(false) == opt.cleanup || Some(true) == opt.no_cleanup {
        info!("Skipping cleanup")
    } else {
        let delete = manager.cleanup(key).await;
        info!(?delete, "Deleted function & cleaned up resources");
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de fluxo do Kinesis. A função recupera a carga útil do Kinesis, decodifica do Base64 e registra o conteúdo do registro em log.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::event::kinesis::KinesisEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) -> Result<(), Error> {
    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(());
    }

    event.payload.records.iter().for_each(|record| {
        tracing::info!("EventId:
 {}",record.event_id.as_deref().unwrap_or_default());

        let record_data = std::str::from_utf8(&record.kinesis.data);

        match record_data {
            Ok(data) => {
                // log the record data
                tracing::info!("Data: {}", data);
            }
            Err(e) => {
                tracing::error!("Error: {}", e);
            }
        }
    });

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();
```

```
    run(service_fn(function_handler)).await
}
```

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Rust.

```
use aws_lambda_events::event::s3::S3Event;
use aws_sdk_s3::{Client};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};


/// Main function
#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    // Initialize the AWS SDK for Rust
    let config = aws_config::load_from_env().await;
    let s3_client = Client::new(&config);

    let res = run(service_fn(|request: LambdaEvent<S3Event>| {
        function_handler(&s3_client, request)
```

```
    })).await;

    res
}

async fn function_handler(
    s3_client: &Client,
    evt: LambdaEvent<S3Event>
) -> Result<(), Error> {
    tracing::info!(records = ?evt.payload.records.len(), "Received request from
 SQS");

    if evt.payload.records.len() == 0 {
        tracing::info!("Empty S3 event received");
    }

    let bucket = evt.payload.records[0].s3.bucket.name.as_ref().expect("Bucket name
 to exist");
    let key = evt.payload.records[0].s3.object.key.as_ref().expect("Object key to
 exist");

    tracing::info!("Request is for {} and object {}", bucket, key);

    let s3_get_object_result = s3_client
        .get_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await;

    match s3_get_object_result {
        Ok(_) => tracing::info!("S3 Get Object success, the s3GetObjectResult
 contains a 'body' property of type ByteStream"),
        Err(_) => tracing::info!("Failure with S3 Get Object request")
    }

    Ok(())
}
```

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SNS com o Lambda usando Rust.

```
use aws_lambda_events::event::sns::SnsEvent;
use aws_lambda_events::sns::SnsRecord;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};
use tracing::info;

// Built with the following dependencies:
//  aws_lambda_events = { version = "0.10.0", default-features = false, features =
 ["sns"] }
//  lambda_runtime = "0.8.1"
//  tokio = { version = "1", features = ["macros"] }
//  tracing = { version = "0.1", features = ["log"] }
//  tracing-subscriber = { version = "0.3", default-features = false, features =
 ["fmt"] }

async fn function_handler(event: LambdaEvent<SnsEvent>) -> Result<(), Error> {
    for event in event.payload.records {
        process_record(&event)?;
    }

    Ok(())
}

fn process_record(record: &SnsRecord) -> Result<(), Error> {
    info!("Processing SNS Message: {}", record.sns.message);

    // Implement your record handling code here.
```

```
    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SQS com o Lambda usando Rust.

```
use aws_lambda_events::event::sqs::SqsEvent;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<(), Error> {
    event.payload.records.iter().for_each(|record| {
        // process the record
        tracing::info!("Message body: {}",
 record.body.as_deref().unwrap_or_default())
    });
```

```
    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatando falhas de itens em lote para funções do Lambda com um trigger do Kinesis

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de um fluxo do Kinesis. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relate falhas de itens em lote do Kinesis com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::kinesis::KinesisEvent,
    kinesis::KinesisEventRecord,
    streams::{KinesisBatchItemFailure, KinesisEventResponse},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<KinesisEvent>) ->
 Result<KinesisEventResponse, Error> {
```

```
    let mut response = KinesisEventResponse {
        batch_item_failures: vec![],
    };

    if event.payload.records.is_empty() {
        tracing::info!("No records found. Exiting.");
        return Ok(response);
    }

    for record in &event.payload.records {
        tracing::info!(
            "EventId: {}",
            record.event_id.as_deref().unwrap_or_default()
        );

        let record_processing_result = process_record(record);

        if record_processing_result.is_err() {
            response.batch_item_failures.push(KinesisBatchItemFailure {
                item_identifier: record.kinesis.sequence_number.clone(),
            });
            /* Since we are working with streams, we can return the failed item
 immediately.
            Lambda will immediately begin to retry processing from this failed item
 onwards. */
            return Ok(response);
        }
    }

    tracing::info!(
        "Successfully processed {} records",
        event.payload.records.len()
    );

    Ok(response)
}

fn process_record(record: &KinesisEventRecord) -> Result<(), Error> {
    let record_data = std::str::from_utf8(record.kinesis.data.as_slice());

    if let Some(err) = record_data.err() {
        tracing::error!("Error: {}", err);
        return Err(Error::from(err));
    }
```

```
    let record_data = record_data.unwrap_or_default();

    // do something interesting with the data
    tracing::info!("Data: {}", record_data);

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::sqs::{SqsBatchResponse, SqsEvent},
    sqs::{BatchItemFailure, SqsMessage},
```

```
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn process_record(_: &SqsMessage) -> Result<(), Error> {
    Err(Error::from("Error processing message"))
}

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<SqsBatchResponse,
 Error> {
    let mut batch_item_failures = Vec::new();
    for record in event.payload.records {
        match process_record(&record).await {
            Ok(_) => (),
            Err(_) => batch_item_failures.push(BatchItemFailure {
                item_identifier: record.message_id.unwrap(),
            }),
        }
    }

    Ok(SqsBatchResponse {
        batch_item_failures,
    })
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    run(service_fn(function_handler)).await
}
```

MediaLive exemplos usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com. MediaLive

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar entradas

O exemplo de código a seguir mostra como listar suas MediaLive entradas.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Liste seus nomes MediaLive de entrada e ARNs na região.

```
async fn show_inputs(client: &Client) -> Result<(), Error> {
    let input_list = client.list_inputs().send().await?;

    for i in input_list.inputs() {
        let input_arn = i.arn().unwrap_or_default();
        let input_name = i.name().unwrap_or_default();

        println!("Input Name : {}", input_name);
        println!("Input ARN : {}", input_arn);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListInputsreferência da API AWS SDK for Rust.

MediaPackage exemplos usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com. MediaPackage

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar canais

O exemplo de código a seguir mostra como listar seus MediaPackage canais.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar canais ARNs e as descrições.

```
async fn show_channels(client: &Client) -> Result<(), Error> {
    let list_channels = client.list_channels().send().await?;

    println!("Channels:");

    for c in list_channels.channels() {
        let description = c.description().unwrap_or_default();
```

```
        let arn = c.arn().unwrap_or_default();

        println!("  Description : {}", description);
        println!("  ARN :         {}", arn);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListChannelsreferência da API AWS SDK for Rust.

Listar endpoints de origem

O exemplo de código a seguir mostra como listar seus endpoints de MediaPackage origem.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Listar as descrições de endpoint e URLs.

```
async fn show_endpoints(client: &Client) -> Result<(), Error> {
    let or_endpoints = client.list_origin_endpoints().send().await?;

    println!("Endpoints:");

    for e in or_endpoints.origin_endpoints() {
        let endpoint_url = e.url().unwrap_or_default();
        let endpoint_description = e.description().unwrap_or_default();
        println!("  Description: {}", endpoint_description);
        println!("  URL :        {}", endpoint_url);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListOriginEndpointsreferência da API AWS SDK for Rust.

Exemplos do Amazon Polly usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon Polly.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter vozes disponíveis para síntese

O exemplo de código a seguir mostra como obter vozes disponíveis para síntese do Amazon Polly.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn list_voices(client: &Client) -> Result<(), Error> {
    let resp = client.describe_voices().send().await?;
```

```
    println!("Voices:");

    let voices = resp.voices();
    for voice in voices {
        println!("  Name:     {}", voice.name().unwrap_or("No name!"));
        println!(
            "  Language: {}",
            voice.language_name().unwrap_or("No language!")
        );

        println!();
    }

    println!("Found {} voices", voices.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeVoicesreferência da API AWS SDK for Rust.

Listar léxicos de pronúncia

O exemplo de código a seguir mostra como listar os léxicos de pronúncia do Amazon Polly.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_lexicons(client: &Client) -> Result<(), Error> {
    let resp = client.list_lexicons().send().await?;

    println!("Lexicons:");

    let lexicons = resp.lexicons();

    for lexicon in lexicons {
        println!("  Name:     {}", lexicon.name().unwrap_or_default());
```

```
        println!(
            "  Language: {:?}\n",
            lexicon
                .attributes()
                .as_ref()
                .map(|attrib| attrib
                    .language_code
                    .as_ref()
                    .expect("languages must have language codes"))
                .expect("languages must have attributes")
        );
    }

    println!();
    println!("Found {} lexicons.", lexicons.len());
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListLexiconsreferência da API AWS SDK for Rust.

Armazenar léxicos de pronúncia

O exemplo de código a seguir mostra como armazenar um léxico de pronúncia do Amazon Polly.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_lexicon(client: &Client, name: &str, from: &str, to: &str) ->
 Result<(), Error> {
    let content = format!("<?xml version=\"1.0\" encoding=\"UTF-8\"?>
    <lexicon version=\"1.0\" xmlns=\"http://www.w3.org/2005/01/pronunciation-lexicon
\" xmlns:xsi=\"http://www.w3.org/2001/XMLSchema-instance\"
    xsi:schemaLocation=\"http://www.w3.org/2005/01/pronunciation-lexicon http://
www.w3.org/TR/2007/CR-pronunciation-lexicon-20071212/pls.xsd\"
```

```
    alphabet=\"ipa\" xml:lang=\"en-US\">
    <lexeme><grapheme>{}</grapheme><alias>{}</alias></lexeme>
    </lexicon>", from, to);

    client
        .put_lexicon()
        .name(name)
        .content(content)
        .send()
        .await?;

    println!("Added lexicon");

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutLexiconreferência da API AWS SDK for Rust.

Sintetizar fala a partir de texto

O exemplo de código a seguir mostra como sintetizar fala a partir de texto com o Amazon Polly.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn synthesize(client: &Client, filename: &str) -> Result<(), Error> {
    let content = fs::read_to_string(filename);

    let resp = client
        .synthesize_speech()
        .output_format(OutputFormat::Mp3)
        .text(content.unwrap())
        .voice_id(VoiceId::Joanna)
        .send()
        .await?;
```

```
    // Get MP3 data from response and save it
    let mut blob = resp
        .audio_stream
        .collect()
        .await
        .expect("failed to read data");

    let parts: Vec<&str> = filename.split('.').collect();
    let out_file = format!("{}{}", String::from(parts[0]), ".mp3");

    let mut file = tokio::fs::File::create(out_file)
        .await
        .expect("failed to create file");

    file.write_all_buf(&mut blob)
        .await
        .expect("failed to write to file");

    Ok(())
}
```

- Para obter detalhes da API, consulte a SynthesizeSpeechreferência da API AWS SDK for Rust.

Exemplos de QLDB usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com QLDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um livro de registros (ledger)

O exemplo de código a seguir mostra como criar um livro de registros QLDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_ledger(client: &Client, ledger: &str) -> Result<(), Error> {
    let result = client
        .create_ledger()
        .name(ledger)
        .permissions_mode(PermissionsMode::AllowAll)
        .send()
        .await?;

    println!("ARN: {}", result.arn().unwrap());

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateLedgerreferência da API AWS SDK for Rust.

Listar livros de registros

O exemplo de código a seguir mostra como listar livros de registros QLDB.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_ledgers(client: &QLDBClient) -> Result<(), Error> {
    let mut pages = client.list_ledgers().into_paginator().page_size(2).send();

    while let Some(page) = pages.next().await {
        println!("* {:?}", page); //Prints an entire page of ledgers.
        for ledger in page.unwrap().ledgers() {
            println!("* {:?}", ledger); //Prints the LedgerSummary of a single
 ledger.
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListLedgersreferência da API AWS SDK for Rust.

Exemplos do Amazon RDS Data Service usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon RDS Data Service.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Para executar uma instrução SQL

O exemplo de código a seguir mostra como executar uma instrução SQL.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn query_cluster(
    client: &Client,
    cluster_arn: &str,
    query: &str,
    secret_arn: &str,
) -> Result<(), Error> {
    let st = client
        .execute_statement()
        .resource_arn(cluster_arn)
        .database("postgres") // Do not confuse this with db instance name
        .sql(query)
        .secret_arn(secret_arn);

    let result = st.send().await?;

    println!("{:?}", result);
    println!();

    Ok(())
}
```

- Para obter detalhes da API, consulte a ExecuteStatementreferência da API AWS SDK for Rust.

Exemplos de Route 53 usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Route 53.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Obter uma lista de zonas hospedadas públicas e privadas

Os exemplos de código a seguir mostram como obter uma lista de zonas hospedadas públicas e privadas.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_host_info(client: &aws_sdk_route53::Client) -> Result<(),
 aws_sdk_route53::Error> {
    let hosted_zone_count = client.get_hosted_zone_count().send().await?;

    println!(
        "Number of hosted zones in region : {}",
        hosted_zone_count.hosted_zone_count(),
    );

    let hosted_zones = client.list_hosted_zones().send().await?;

    println!("Zones:");

    for hz in hosted_zones.hosted_zones() {
        let zone_name = hz.name();
        let zone_id = hz.id();
```

```
        println!("  ID :   {}", zone_id);
        println!("  Name : {}", zone_name);
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListHostedZonesreferência da API AWS SDK for Rust.

Exemplos do Amazon S3 usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários
- Exemplos sem servidor

Ações

Concluir um carregamento fracionado

O exemplo de código a seguir mostra como concluir uma ação de carregamento fracionado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    let _complete_multipart_upload_res = client
        .complete_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .multipart_upload(completed_multipart_upload)
        .upload_id(upload_id)
        .send()
        .await
        .unwrap();
```

- Para obter detalhes da API, consulte a CompleteMultipartUploadreferência da API AWS SDK for Rust.

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn copy_object(
    client: &Client,
    bucket_name: &str,
    object_key: &str,
    target_key: &str,
```

```
) -> Result<CopyObjectOutput, SdkError<CopyObjectError>> {
    let mut source_bucket_and_object: String = "".to_owned();
    source_bucket_and_object.push_str(bucket_name);
    source_bucket_and_object.push('/');
    source_bucket_and_object.push_str(object_key);

    client
        .copy_object()
        .copy_source(source_bucket_and_object)
        .bucket(bucket_name)
        .key(target_key)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWS SDK for Rust.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn create_bucket(
    client: &Client,
    bucket_name: &str,
    region: &str,
) -> Result<CreateBucketOutput, SdkError<CreateBucketError>> {
    let constraint = BucketLocationConstraint::from(region);
    let cfg = CreateBucketConfiguration::builder()
        .location_constraint(constraint)
        .build();
    client
        .create_bucket()
```

```
        .create_bucket_configuration(cfg)
        .bucket(bucket_name)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWS SDK for Rust.

Criar um carregamento fracionado

O exemplo de código a seguir mostra como criar a estrutura para construir uma ação de carregamento fracionado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    let multipart_upload_res: CreateMultipartUploadOutput = client
        .create_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .send()
        .await
        .unwrap();
```

- Para obter detalhes da API, consulte a CreateMultipartUploadreferência da API AWS SDK for Rust.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_bucket(client: &Client, bucket_name: &str) -> Result<(), Error>
 {
    client.delete_bucket().bucket(bucket_name).send().await?;
    println!("Bucket deleted");
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteBucketreferência da API AWS SDK for Rust.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn remove_object(client: &Client, bucket: &str, key: &str) -> Result<(),
 Error> {
    client
        .delete_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await?;

    println!("Object deleted.");
```

```
    Ok(())
}
```

- Para obter detalhes da API, consulte a DeleteObjectreferência da API AWS SDK for Rust.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn delete_objects(client: &Client, bucket_name: &str) ->
 Result<Vec<String>, Error> {
    let objects = client.list_objects_v2().bucket(bucket_name).send().await?;

    let mut delete_objects: Vec<ObjectIdentifier> = vec![];
    for obj in objects.contents() {
        let obj_id = ObjectIdentifier::builder()
            .set_key(Some(obj.key().unwrap().to_string()))
            .build()
            .map_err(Error::from)?;
        delete_objects.push(obj_id);
    }

    let return_keys = delete_objects.iter().map(|o| o.key.clone()).collect();

    if !delete_objects.is_empty() {
        client
            .delete_objects()
            .bucket(bucket_name)
            .delete(
                Delete::builder()
                    .set_objects(Some(delete_objects))
                    .build()
```

```
                    .map_err(Error::from)?,
            )
            .send()
            .await?;
    }

    let objects: ListObjectsV2Output =
 client.list_objects_v2().bucket(bucket_name).send().await?;

    eprintln!("{objects:?}");

    match objects.key_count {
        Some(0) => Ok(return_keys),
        _ => Err(Error::unhandled(
            "There were still objects left in the bucket.",
        )),
    }
}
```

- Para obter detalhes da API, consulte a DeleteObjectsreferência da API AWS SDK for Rust.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn get_object(client: Client, opt: Opt) -> Result<usize, anyhow::Error> {
    trace!("bucket:      {}", opt.bucket);
    trace!("object:      {}", opt.object);
    trace!("destination: {}", opt.destination.display());

    let mut file = File::create(opt.destination.clone())?;

    let mut object = client
```

```
        .get_object()
        .bucket(opt.bucket)
        .key(opt.object)
        .send()
        .await?;

    let mut byte_count = 0_usize;
    while let Some(bytes) = object.body.try_next().await? {
        let bytes_len = bytes.len();
        file.write_all(&bytes)?;
        trace!("Intermediate write of {bytes_len}");
        byte_count += bytes_len;
    }

    Ok(byte_count)
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for Rust.

Obter um objeto de um bucket que foi modificado

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3, mas somente se esse bucket não tiver sido modificado desde a última recuperação.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use aws_sdk_s3::{
    error::SdkError,
    operation::head_object::HeadObjectError,
    primitives::{ByteStream, DateTime, DateTimeFormat},
    Client, Error,
};
use tracing::{error, warn};

const KEY: &str = "key";
```

```
const BODY: &str = "Hello, world!";

/// Demonstrate how `if-modified-since` reports that matching objects haven't
/// changed.
///
/// # Steps
/// - Create a bucket.
/// - Put an object in the bucket.
/// - Get the bucket headers.
/// - Get the bucket headers again but only if modified.
/// - Delete the bucket.
#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt::init();

    // Get a new UUID to use when creating a unique bucket name.
    let uuid = uuid::Uuid::new_v4();

    // Load the AWS configuration from the environment.
    let client = Client::new(&aws_config::load_from_env().await);

    // Generate a unique bucket name using the previously generated UUID.
    // Then create a new bucket with that name.
    let bucket_name = format!("if-modified-since-{uuid}");
    client
        .create_bucket()
        .bucket(bucket_name.clone())
        .send()
        .await?;

    // Create a new object in the bucket whose name is `KEY` and whose
    // contents are `BODY`.
    let put_object_output = client
        .put_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .body(ByteStream::from_static(BODY.as_bytes()))
        .send()
        .await;

    // If the `PutObject` succeeded, get the eTag string from it. Otherwise,
    // report an error and return an empty string.
    let e_tag_1 = match put_object_output {
        Ok(put_object) => put_object.e_tag.unwrap(),
```

```
        Err(err) => {
            error!("{err:?}");
            String::new()
        }
    };

    // Request the object's headers.
    let head_object_output = client
        .head_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .send()
        .await;

    // If the `HeadObject` request succeeded, create a tuple containing the
    // values of the headers `last-modified` and `etag`. If the request
    // failed, return the error in a tuple instead.
    let (last_modified, e_tag_2) = match head_object_output {
        Ok(head_object) => (
            Ok(head_object.last_modified().cloned().unwrap()),
            head_object.e_tag.unwrap(),
        ),
        Err(err) => (Err(err), String::new()),
    };

    warn!("last modified: {last_modified:?}");
    assert_eq!(
        e_tag_1, e_tag_2,
        "PutObject and first GetObject had differing eTags"
    );

    println!("First value of last_modified: {last_modified:?}");
    println!("First tag: {}\n", e_tag_1);

    // Send a second `HeadObject` request. This time, the `if_modified_since`
    // option is specified, giving the `last_modified` value returned by the
    // first call to `HeadObject`.
    //
    // Since the object hasn't been changed, and there are no other objects in
    // the bucket, there should be no matching objects.

    let head_object_output = client
        .head_object()
        .bucket(bucket_name.as_str())
```

```
        .key(KEY)
        .if_modified_since(last_modified.unwrap())
        .send()
        .await;

    // If the `HeadObject` request succeeded, the result is a typle containing
    // the `last_modified` and `e_tag_1` properties. This is _not_ the expected
    // result.
    //
    // The _expected_ result of the second call to `HeadObject` is an
    // `SdkError::ServiceError` containing the HTTP error response. If that's
    // the case and the HTTP status is 304 (not modified), the output is a
    // tuple containing the values of the HTTP `last-modified` and `etag`
    // headers.
    //
    // If any other HTTP error occurred, the error is returned as an
    // `SdkError::ServiceError`.

    let (last_modified, e_tag_2): (Result<DateTime, SdkError<HeadObjectError>>,
String) =
        match head_object_output {
            Ok(head_object) => (
                Ok(head_object.last_modified().cloned().unwrap()),
                head_object.e_tag.unwrap(),
            ),
            Err(err) => match err {
                SdkError::ServiceError(err) => {
                    // Get the raw HTTP response. If its status is 304, the
                    // object has not changed. This is the expected code path.
                    let http = err.raw();
                    match http.status().as_u16() {
                        // If the HTTP status is 304: Not Modified, return a
                        // tuple containing the values of the HTTP
                        // `last-modified` and `etag` headers.
                        304 => (
                            Ok(DateTime::from_str(
                                http.headers().get("last-modified").unwrap(),
                                DateTimeFormat::HttpDate,
                            )
                            .unwrap()),
                            http.headers().get("etag").map(|t| t.into()).unwrap(),
                        ),
                        // Any other HTTP status code is returned as an
                        // `SdkError::ServiceError`.
```

```
                        _ => (Err(SdkError::ServiceError(err)), String::new()),
                    }
                }
                // Any other kind of error is returned in a tuple containing the
                // error and an empty string.
                _ => (Err(err), String::new()),
            },
        };

    warn!("last modified: {last_modified:?}");
    assert_eq!(
        e_tag_1, e_tag_2,
        "PutObject and second HeadObject had different eTags"
    );

    println!("Second value of last modified: {last_modified:?}");
    println!("Second tag: {}", e_tag_2);

    // Clean up by deleting the object and the bucket.
    client
        .delete_object()
        .bucket(bucket_name.as_str())
        .key(KEY)
        .send()
        .await?;

    client
        .delete_bucket()
        .bucket(bucket_name.as_str())
        .send()
        .await?;

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for Rust.

Obter o local da região de um bucket

O exemplo de código a seguir mostra como obter o local da região de um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_buckets(strict: bool, client: &Client, region: &str) -> Result<(),
 Error> {
    let resp = client.list_buckets().send().await?;
    let buckets = resp.buckets();
    let num_buckets = buckets.len();

    let mut in_region = 0;

    for bucket in buckets {
        if strict {
            let r = client
                .get_bucket_location()
                .bucket(bucket.name().unwrap_or_default())
                .send()
                .await?;

            if r.location_constraint().unwrap().as_ref() == region {
                println!("{}", bucket.name().unwrap_or_default());
                in_region += 1;
            }
        } else {
            println!("{}", bucket.name().unwrap_or_default());
        }
    }

    println!();
    if strict {
        println!(
            "Found {} buckets in the {} region out of a total of {} buckets.",
            in_region, region, num_buckets
        );
    } else {
        println!("Found {} buckets in all regions.", num_buckets);
    }
```

```
    Ok(())
}
```

- Para obter detalhes da API, consulte a GetBucketLocationreferência da API AWS SDK for Rust.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_buckets(strict: bool, client: &Client, region: &str) -> Result<(),
 Error> {
    let resp = client.list_buckets().send().await?;
    let buckets = resp.buckets();
    let num_buckets = buckets.len();

    let mut in_region = 0;

    for bucket in buckets {
        if strict {
            let r = client
                .get_bucket_location()
                .bucket(bucket.name().unwrap_or_default())
                .send()
                .await?;

            if r.location_constraint().unwrap().as_ref() == region {
                println!("{}", bucket.name().unwrap_or_default());
                in_region += 1;
            }
        } else {
            println!("{}", bucket.name().unwrap_or_default());
```

```
        }
    }

    println!();
    if strict {
        println!(
            "Found {} buckets in the {} region out of a total of {} buckets.",
            in_region, region, num_buckets
        );
    } else {
        println!("Found {} buckets in all regions.", num_buckets);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListBucketsreferência da API AWS SDK for Rust.

Listar as versões de objeto em um bucket

O exemplo de código a seguir mostra como listar versões de objeto em um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_versions(client: &Client, bucket: &str) -> Result<(), Error> {
    let resp = client.list_object_versions().bucket(bucket).send().await?;

    for version in resp.versions() {
        println!("{}", version.key().unwrap_or_default());
        println!("  version ID: {}", version.version_id().unwrap_or_default());
        println!();
    }

    Ok(())
```

```
}
```

- Para obter detalhes da API, consulte a ListObjectVersionsreferência da API AWS SDK for Rust.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn list_objects(client: &Client, bucket: &str) -> Result<(), Error> {
    let mut response = client
        .list_objects_v2()
        .bucket(bucket.to_owned())
        .max_keys(10) // In this example, go 10 at a time.
        .into_paginator()
        .send();

    while let Some(result) = response.next().await {
        match result {
            Ok(output) => {
                for object in output.contents() {
                    println!(" - {}", object.key().unwrap_or("Unknown"));
                }
            }
            Err(err) => {
                eprintln!("{err:?}")
            }
        }
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API AWSSDK for Rust.

Teste de unidade e integração com SDK

O exemplo de código a seguir mostra exemplos de técnicas de práticas recomendadas ao escrever testes de unidade e de integração usando AWS SDK.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Cargo.toml para exemplos de testes.

```
[package]
name = "testing-examples"
version = "0.1.0"
authors = [
  "John Disanti <jdisanti@amazon.com>",
  "Doug Schwartz <dougsch@amazon.com>",
]
edition = "2021"

# snippet-start:[testing.rust.Cargo.toml]
[dependencies]
async-trait = "0.1.51"
aws-config = { version = "1.0.1", features = ["behavior-version-latest"] }
aws-credential-types = { version = "1.0.1", features = [ "hardcoded-
credentials", ] }
aws-sdk-s3 = { version = "1.4.0" }
aws-smithy-types = { version = "1.0.1" }
aws-smithy-runtime = { version = "1.0.1", features = ["test-util"] }
aws-smithy-runtime-api = { version = "1.0.1", features = ["test-util"] }
aws-types = { version = "1.0.1" }
clap = { version = "~4.4", features = ["derive"] }
http = "0.2.9"
mockall = "0.11.4"
serde_json = "1"
tokio = { version = "1.20.1", features = ["full"] }
```

```
tracing-subscriber = { version = "0.3.15", features = ["env-filter"] }
# snippet-end:[testing.rust.Cargo.toml]

[[bin]]
name = "main"
path = "src/main.rs"
```

Exemplo de teste de unidade usando automock e um wrapper de serviço.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

// snippet-start:[testing.rust.wrapper]
// snippet-start:[testing.rust.wrapper-uses]
use aws_sdk_s3 as s3;
#[allow(unused_imports)]
use mockall::automock;

use s3::operation::list_objects_v2::{ListObjectsV2Error, ListObjectsV2Output};
// snippet-end:[testing.rust.wrapper-uses]

// snippet-start:[testing.rust.wrapper-which-impl]
#[cfg(test)]
pub use MockS3Impl as S3;
#[cfg(not(test))]
pub use S3Impl as S3;
// snippet-end:[testing.rust.wrapper-which-impl]

// snippet-start:[testing.rust.wrapper-impl]
#[allow(dead_code)]
pub struct S3Impl {
    inner: s3::Client,
}

#[cfg_attr(test, automock)]
impl S3Impl {
    #[allow(dead_code)]
    pub fn new(inner: s3::Client) -> Self {
        Self { inner }
    }

    #[allow(dead_code)]
```

```
    pub async fn list_objects(
        &self,
        bucket: &str,
        prefix: &str,
        continuation_token: Option<String>,
    ) -> Result<ListObjectsV2Output, s3::error::SdkError<ListObjectsV2Error>> {
        self.inner
            .list_objects_v2()
            .bucket(bucket)
            .prefix(prefix)
            .set_continuation_token(continuation_token)
            .send()
            .await
    }
}
// snippet-end:[testing.rust.wrapper-impl]

// snippet-start:[testing.rust.wrapper-func]
#[allow(dead_code)]
pub async fn determine_prefix_file_size(
    // Now we take a reference to our trait object instead of the S3 client
    // s3_list: ListObjectsService,
    s3_list: S3,
    bucket: &str,
    prefix: &str,
) -> Result<usize, s3::Error> {
    let mut next_token: Option<String> = None;
    let mut total_size_bytes = 0;
    loop {
        let result = s3_list
            .list_objects(bucket, prefix, next_token.take())
            .await?;

        // Add up the file sizes we got back
        for object in result.contents() {
            total_size_bytes += object.size().unwrap_or(0) as usize;
        }

        // Handle pagination, and break the loop if there are no more pages
        next_token = result.next_continuation_token.clone();
        if next_token.is_none() {
            break;
        }
    }
```

```
    Ok(total_size_bytes)
}
// snippet-end:[testing.rust.wrapper-func]
// snippet-end:[testing.rust.wrapper]

// snippet-start:[testing.rust.wrapper-test-mod]
#[cfg(test)]
mod test {
    // snippet-start:[testing.rust.wrapper-tests]
    use super::*;
    use mockall::predicate::eq;

    // snippet-start:[testing.rust.wrapper-test-single]
    #[tokio::test]
    async fn test_single_page() {
        let mut mock = MockS3Impl::default();
        mock.expect_list_objects()
            .with(eq("test-bucket"), eq("test-prefix"), eq(None))
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(5).build(),
                        s3::types::Object::builder().size(2).build(),
                    ]))
                    .build())
            });

        // Run the code we want to test with it
        let size = determine_prefix_file_size(mock, "test-bucket", "test-prefix")
            .await
            .unwrap();

        // Verify we got the correct total size back
        assert_eq!(7, size);
    }
    // snippet-end:[testing.rust.wrapper-test-single]

    // snippet-start:[testing.rust.wrapper-test-multiple]
    #[tokio::test]
    async fn test_multiple_pages() {
        // Create the Mock instance with two pages of objects now
        let mut mock = MockS3Impl::default();
        mock.expect_list_objects()
```

```
            .with(eq("test-bucket"), eq("test-prefix"), eq(None))
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(5).build(),
                        s3::types::Object::builder().size(2).build(),
                    ]))
                    .set_next_continuation_token(Some("next".to_string()))
                    .build())
            });
        mock.expect_list_objects()
            .with(
                eq("test-bucket"),
                eq("test-prefix"),
                eq(Some("next".to_string())),
            )
            .return_once(|_, _, _| {
                Ok(ListObjectsV2Output::builder()
                    .set_contents(Some(vec![
                        // Mock content for ListObjectsV2 response
                        s3::types::Object::builder().size(3).build(),
                        s3::types::Object::builder().size(9).build(),
                    ]))
                    .build())
            });

        // Run the code we want to test with it
        let size = determine_prefix_file_size(mock, "test-bucket", "test-prefix")
            .await
            .unwrap();

        assert_eq!(19, size);
    }
    // snippet-end:[testing.rust.wrapper-test-multiple]
    // snippet-end:[testing.rust.wrapper-tests]
}
// snippet-end:[testing.rust.wrapper-test-mod]
```

Exemplo de teste de integração usando StaticReplayClient.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
```

```
// SPDX-License-Identifier: Apache-2.0

// snippet-start:[testing.rust.replay-uses]
use aws_sdk_s3 as s3;
// snippet-end:[testing.rust.replay-uses]

#[allow(dead_code)]
// snippet-start:[testing.rust.replay]
pub async fn determine_prefix_file_size(
    // Now we take a reference to our trait object instead of the S3 client
    // s3_list: ListObjectsService,
    s3: s3::Client,
    bucket: &str,
    prefix: &str,
) -> Result<usize, s3::Error> {
    let mut next_token: Option<String> = None;
    let mut total_size_bytes = 0;
    loop {
        let result = s3
            .list_objects_v2()
            .prefix(prefix)
            .bucket(bucket)
            .set_continuation_token(next_token.take())
            .send()
            .await?;

        // Add up the file sizes we got back
        for object in result.contents() {
            total_size_bytes += object.size().unwrap_or(0) as usize;
        }

        // Handle pagination, and break the loop if there are no more pages
        next_token = result.next_continuation_token.clone();
        if next_token.is_none() {
            break;
        }
    }
    Ok(total_size_bytes)
}
// snippet-end:[testing.rust.replay]

#[allow(dead_code)]
// snippet-start:[testing.rust.replay-tests]
// snippet-start:[testing.rust.replay-make-credentials]
```

```
fn make_s3_test_credentials() -> s3::config::Credentials {
    s3::config::Credentials::new(
        "ATESTCLIENT",
        "astestsecretkey",
        Some("atestsessiontoken".to_string()),
        None,
        "",
    )
}
// snippet-end:[testing.rust.replay-make-credentials]

// snippet-start:[testing.rust.replay-test-module]
#[cfg(test)]
mod test {
    // snippet-start:[testing.rust.replay-test-single]
    use super::*;
    use aws_config::BehaviorVersion;
    use aws_sdk_s3 as s3;
    use aws_smithy_runtime::client::http::test_util::{ReplayEvent,
 StaticReplayClient};
    use aws_smithy_types::body::SdkBody;

    #[tokio::test]
    async fn test_single_page() {
        let page_1 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/response_1.xml")))
                    .unwrap(),
            );
        let replay_client = StaticReplayClient::new(vec![page_1]);
        let client: s3::Client = s3::Client::from_conf(
            s3::Config::builder()
                .behavior_version(BehaviorVersion::latest())
                .credentials_provider(make_s3_test_credentials())
                .region(s3::config::Region::new("us-east-1"))
                .http_client(replay_client.clone())
                .build(),
```

```
        );

        // Run the code we want to test with it
        let size = determine_prefix_file_size(client, "test-bucket", "test-prefix")
            .await
            .unwrap();

        // Verify we got the correct total size back
        assert_eq!(7, size);
        replay_client.assert_requests_match(&[]);
    }
    // snippet-end:[testing.rust.replay-test-single]

    // snippet-start:[testing.rust.replay-test-multiple]
    #[tokio::test]
    async fn test_multiple_pages() {
        // snippet-start:[testing.rust.replay-create-replay]
        let page_1 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/
response_multi_1.xml")))
                    .unwrap(),
            );
        let page_2 = ReplayEvent::new(
                http::Request::builder()
                    .method("GET")
                    .uri("https://test-bucket.s3.us-east-1.amazonaws.com/?list-
type=2&prefix=test-prefix&continuation-token=next")
                    .body(SdkBody::empty())
                    .unwrap(),
                http::Response::builder()
                    .status(200)
                    .body(SdkBody::from(include_str!("./testing/
response_multi_2.xml")))
                    .unwrap(),
            );
        let replay_client = StaticReplayClient::new(vec![page_1, page_2]);
```

```
        // snippet-end:[testing.rust.replay-create-replay]
        // snippet-start:[testing.rust.replay-create-client]
        let client: s3::Client = s3::Client::from_conf(
            s3::Config::builder()
                .behavior_version(BehaviorVersion::latest())
                .credentials_provider(make_s3_test_credentials())
                .region(s3::config::Region::new("us-east-1"))
                .http_client(replay_client.clone())
                .build(),
        );
        // snippet-end:[testing.rust.replay-create-client]

        // Run the code we want to test with it
        // snippet-start:[testing.rust.replay-test-and-verify]
        let size = determine_prefix_file_size(client, "test-bucket", "test-prefix")
            .await
            .unwrap();

        assert_eq!(19, size);

        replay_client.assert_requests_match(&[]);
        // snippet-end:[testing.rust.replay-test-and-verify]
    }
    // snippet-end:[testing.rust.replay-test-multiple]
}
// snippet-end:[testing.rust.replay-tests]
// snippet-end:[testing.rust.replay-test-module]
```

Fazer upload de uma única parte de um carregamento fracionado

O exemplo de código a seguir mostra como fazer upload de uma única parte de um carregamento fracionado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
        let upload_part_res = client
            .upload_part()
            .key(&key)
            .bucket(&bucket_name)
            .upload_id(upload_id)
            .body(stream)
            .part_number(part_number)
            .send()
            .await?;
        upload_parts.push(
            CompletedPart::builder()
                .e_tag(upload_part_res.e_tag.unwrap_or_default())
                .part_number(part_number)
                .build(),
        );

    let completed_multipart_upload: CompletedMultipartUpload =
CompletedMultipartUpload::builder()
        .set_parts(Some(upload_parts))
        .build();
```

- Para obter detalhes da API, consulte a UploadPartreferência da API AWS SDK for Rust.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
pub async fn upload_object(
    client: &Client,
    bucket_name: &str,
    file_name: &str,
    key: &str,
```

```
) -> Result<PutObjectOutput, SdkError<PutObjectError>> {
    let body = ByteStream::from_path(Path::new(file_name)).await;
    client
        .put_object()
        .bucket(bucket_name)
        .key(key)
        .body(body.unwrap())
        .send()
        .await
}
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWS SDK for Rust.

Cenários

Criar um URL pré-assinado

O exemplo de código a seguir mostra como criar uma URL pré-assinada para o Amazon S3 e fazer upload de um objeto.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie solicitações pré-assinadas para objetos GET e PUT do S3.

```
async fn get_object(
    client: &Client,
    bucket: &str,
    object: &str,
    expires_in: u64,
) -> Result<(), Box<dyn Error>> {
    let expires_in = Duration::from_secs(expires_in);
    let presigned_request = client
        .get_object()
        .bucket(bucket)
```

```
        .key(object)
        .presigned(PresigningConfig::expires_in(expires_in)?)
        .await?;

    println!("Object URI: {}", presigned_request.uri());

    Ok(())
}

async fn put_object(
    client: &Client,
    bucket: &str,
    object: &str,
    expires_in: u64,
) -> Result<(), Box<dyn Error>> {
    let expires_in = Duration::from_secs(expires_in);

    let presigned_request = client
        .put_object()
        .bucket(bucket)
        .key(object)
        .presigned(PresigningConfig::expires_in(expires_in)?)
        .await?;

    println!("Object URI: {}", presigned_request.uri());

    Ok(())
}
```

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Código para a caixa binária que executa o cenário.

```
use aws_config::meta::region::RegionProviderChain;
use aws_sdk_s3::{config::Region, Client};
use s3_service::error::Error;
use uuid::Uuid;


#[tokio::main]
async fn main() -> Result<(), Error> {
    let (region, client, bucket_name, file_name, key, target_key) =
 initialize_variables().await;

    if let Err(e) = run_s3_operations(region, client, bucket_name, file_name, key,
 target_key).await
    {
        println!("{:?}", e);
    };

    Ok(())
}

async fn initialize_variables() -> (Region, Client, String, String, String, String)
 {
    let region_provider = RegionProviderChain::first_try(Region::new("us-west-2"));
    let region = region_provider.region().await.unwrap();

    let shared_config = aws_config::from_env().region(region_provider).load().await;
    let client = Client::new(&shared_config);

    let bucket_name = format!("doc-example-bucket-{}", Uuid::new_v4());

    let file_name = "s3/testfile.txt".to_string();
```

```
    let key = "test file key name".to_string();
    let target_key = "target_key".to_string();

    (region, client, bucket_name, file_name, key, target_key)
}

async fn run_s3_operations(
    region: Region,
    client: Client,
    bucket_name: String,
    file_name: String,
    key: String,
    target_key: String,
) -> Result<(), Error> {
    s3_service::create_bucket(&client, &bucket_name, region.as_ref()).await?;
    s3_service::upload_object(&client, &bucket_name, &file_name, &key).await?;
    let _object = s3_service::download_object(&client, &bucket_name, &key).await;
    s3_service::copy_object(&client, &bucket_name, &key, &target_key).await?;
    s3_service::list_objects(&client, &bucket_name).await?;
    s3_service::delete_objects(&client, &bucket_name).await?;
    s3_service::delete_bucket(&client, &bucket_name).await?;

    Ok(())
}
```

Uma caixa de biblioteca com ações comuns chamadas pelo binário.

```
use aws_sdk_s3::operation::{
    copy_object::{CopyObjectError, CopyObjectOutput},
    create_bucket::{CreateBucketError, CreateBucketOutput},
    get_object::{GetObjectError, GetObjectOutput},
    list_objects_v2::ListObjectsV2Output,
    put_object::{PutObjectError, PutObjectOutput},
};
use aws_sdk_s3::types::{
    BucketLocationConstraint, CreateBucketConfiguration, Delete, ObjectIdentifier,
};
use aws_sdk_s3::{error::SdkError, primitives::ByteStream, Client};
use error::Error;
use std::path::Path;
```

```
use std::str;

pub mod error;

pub async fn delete_bucket(client: &Client, bucket_name: &str) -> Result<(), Error>
 {
    client.delete_bucket().bucket(bucket_name).send().await?;
    println!("Bucket deleted");
    Ok(())
}

pub async fn delete_objects(client: &Client, bucket_name: &str) ->
 Result<Vec<String>, Error> {
    let objects = client.list_objects_v2().bucket(bucket_name).send().await?;

    let mut delete_objects: Vec<ObjectIdentifier> = vec![];
    for obj in objects.contents() {
        let obj_id = ObjectIdentifier::builder()
            .set_key(Some(obj.key().unwrap().to_string()))
            .build()
            .map_err(Error::from)?;
        delete_objects.push(obj_id);
    }

    let return_keys = delete_objects.iter().map(|o| o.key.clone()).collect();

    if !delete_objects.is_empty() {
        client
            .delete_objects()
            .bucket(bucket_name)
            .delete(
                Delete::builder()
                    .set_objects(Some(delete_objects))
                    .build()
                    .map_err(Error::from)?,
            )
            .send()
            .await?;
    }

    let objects: ListObjectsV2Output =
 client.list_objects_v2().bucket(bucket_name).send().await?;

    eprintln!("{objects:?}");
```

```
    match objects.key_count {
        Some(0) => Ok(return_keys),
        _ => Err(Error::unhandled(
            "There were still objects left in the bucket.",
        )),
    }
}

pub async fn list_objects(client: &Client, bucket: &str) -> Result<(), Error> {
    let mut response = client
        .list_objects_v2()
        .bucket(bucket.to_owned())
        .max_keys(10) // In this example, go 10 at a time.
        .into_paginator()
        .send();

    while let Some(result) = response.next().await {
        match result {
            Ok(output) => {
                for object in output.contents() {
                    println!(" - {}", object.key().unwrap_or("Unknown"));
                }
            }
            Err(err) => {
                eprintln!("{err:?}")
            }
        }
    }

    Ok(())
}

pub async fn copy_object(
    client: &Client,
    bucket_name: &str,
    object_key: &str,
    target_key: &str,
) -> Result<CopyObjectOutput, SdkError<CopyObjectError>> {
    let mut source_bucket_and_object: String = "".to_owned();
    source_bucket_and_object.push_str(bucket_name);
    source_bucket_and_object.push('/');
    source_bucket_and_object.push_str(object_key);
```

```
    client
        .copy_object()
        .copy_source(source_bucket_and_object)
        .bucket(bucket_name)
        .key(target_key)
        .send()
        .await
}

pub async fn download_object(
    client: &Client,
    bucket_name: &str,
    key: &str,
) -> Result<GetObjectOutput, SdkError<GetObjectError>> {
    client
        .get_object()
        .bucket(bucket_name)
        .key(key)
        .send()
        .await
}

pub async fn upload_object(
    client: &Client,
    bucket_name: &str,
    file_name: &str,
    key: &str,
) -> Result<PutObjectOutput, SdkError<PutObjectError>> {
    let body = ByteStream::from_path(Path::new(file_name)).await;
    client
        .put_object()
        .bucket(bucket_name)
        .key(key)
        .body(body.unwrap())
        .send()
        .await
}

pub async fn create_bucket(
    client: &Client,
    bucket_name: &str,
    region: &str,
) -> Result<CreateBucketOutput, SdkError<CreateBucketError>> {
    let constraint = BucketLocationConstraint::from(region);
```

```
    let cfg = CreateBucketConfiguration::builder()
        .location_constraint(constraint)
        .build();
    client
        .create_bucket()
        .create_bucket_configuration(cfg)
        .bucket(bucket_name)
        .send()
        .await
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Rust.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Fazer upload ou download de arquivos grandes

O exemplo de código a seguir mostra como fazer upload ou download de arquivos grandes de e para o Amazon S3.

Para obter mais informações, consulte Carregar um objeto usando carregamento fracionado.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
use std::fs::File;
use std::io::prelude::*;
use std::path::Path;

use aws_config::meta::region::RegionProviderChain;
use aws_sdk_s3::error::DisplayErrorContext;
use aws_sdk_s3::operation::{
    create_multipart_upload::CreateMultipartUploadOutput,
 get_object::GetObjectOutput,
};
use aws_sdk_s3::types::{CompletedMultipartUpload, CompletedPart};
use aws_sdk_s3::{config::Region, Client as S3Client};
use aws_smithy_types::byte_stream::{ByteStream, Length};
use rand::distributions::Alphanumeric;
use rand::{thread_rng, Rng};
use s3_service::error::Error;
use std::process;
use uuid::Uuid;

//In bytes, minimum chunk size of 5MB. Increase CHUNK_SIZE to send larger chunks.
const CHUNK_SIZE: u64 = 1024 * 1024 * 5;
const MAX_CHUNKS: u64 = 10000;

#[tokio::main]
pub async fn main() {
    if let Err(err) = run_example().await {
        eprintln!("Error: {}", DisplayErrorContext(err));
        process::exit(1);
    }
}

async fn run_example() -> Result<(), Error> {
    let shared_config = aws_config::load_from_env().await;
    let client = S3Client::new(&shared_config);

    let bucket_name = format!("doc-example-bucket-{}", Uuid::new_v4());
    let region_provider = RegionProviderChain::first_try(Region::new("us-west-2"));
    let region = region_provider.region().await.unwrap();
    s3_service::create_bucket(&client, &bucket_name, region.as_ref()).await?;

    let key = "sample.txt".to_string();
    let multipart_upload_res: CreateMultipartUploadOutput = client
        .create_multipart_upload()
        .bucket(&bucket_name)
```

```
        .key(&key)
        .send()
        .await
        .unwrap();
    let upload_id = multipart_upload_res.upload_id().unwrap();

    //Create a file of random characters for the upload.
    let mut file = File::create(&key).expect("Could not create sample file.");
    // Loop until the file is 5 chunks.
    while file.metadata().unwrap().len() <= CHUNK_SIZE * 4 {
        let rand_string: String = thread_rng()
            .sample_iter(&Alphanumeric)
            .take(256)
            .map(char::from)
            .collect();
        let return_string: String = "\n".to_string();
        file.write_all(rand_string.as_ref())
            .expect("Error writing to file.");
        file.write_all(return_string.as_ref())
            .expect("Error writing to file.");
    }

    let path = Path::new(&key);
    let file_size = tokio::fs::metadata(path)
        .await
        .expect("it exists I swear")
        .len();

    let mut chunk_count = (file_size / CHUNK_SIZE) + 1;
    let mut size_of_last_chunk = file_size % CHUNK_SIZE;
    if size_of_last_chunk == 0 {
        size_of_last_chunk = CHUNK_SIZE;
        chunk_count -= 1;
    }

    if file_size == 0 {
        panic!("Bad file size.");
    }
    if chunk_count > MAX_CHUNKS {
        panic!("Too many chunks! Try increasing your chunk size.")
    }

    let mut upload_parts: Vec<CompletedPart> = Vec::new();
```

```
    for chunk_index in 0..chunk_count {
        let this_chunk = if chunk_count - 1 == chunk_index {
            size_of_last_chunk
        } else {
            CHUNK_SIZE
        };
        let stream = ByteStream::read_from()
            .path(path)
            .offset(chunk_index * CHUNK_SIZE)
            .length(Length::Exact(this_chunk))
            .build()
            .await
            .unwrap();
        //Chunk index needs to start at 0, but part numbers start at 1.
        let part_number = (chunk_index as i32) + 1;
        let upload_part_res = client
            .upload_part()
            .key(&key)
            .bucket(&bucket_name)
            .upload_id(upload_id)
            .body(stream)
            .part_number(part_number)
            .send()
            .await?;
        upload_parts.push(
            CompletedPart::builder()
                .e_tag(upload_part_res.e_tag.unwrap_or_default())
                .part_number(part_number)
                .build(),
        );
    }
    let completed_multipart_upload: CompletedMultipartUpload =
CompletedMultipartUpload::builder()
        .set_parts(Some(upload_parts))
        .build();

    let _complete_multipart_upload_res = client
        .complete_multipart_upload()
        .bucket(&bucket_name)
        .key(&key)
        .multipart_upload(completed_multipart_upload)
        .upload_id(upload_id)
        .send()
        .await
```

```
        .unwrap();

    let data: GetObjectOutput = s3_service::download_object(&client, &bucket_name,
 &key).await?;
    let data_length: u64 = data
        .content_length()
        .unwrap_or_default()
        .try_into()
        .unwrap();
    if file.metadata().unwrap().len() == data_length {
        println!("Data lengths match.");
    } else {
        println!("The data was not the same size!");
    }

    s3_service::delete_objects(&client, &bucket_name)
        .await
        .expect("Error emptying bucket.");
    s3_service::delete_bucket(&client, &bucket_name)
        .await
        .expect("Error deleting bucket.");

    Ok(())
}
```

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon S3

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo upload de um objeto em um bucket do S3. A função recupera o nome do bucket do S3 e a chave do objeto do parâmetro de evento e chama a API do Amazon S3 para recuperar e registrar o tipo de conteúdo do objeto.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consumir um evento do S3 com o Lambda usando Rust.

```
use aws_lambda_events::event::s3::S3Event;
use aws_sdk_s3::{Client};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};


/// Main function
#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    // Initialize the AWS SDK for Rust
    let config = aws_config::load_from_env().await;
    let s3_client = Client::new(&config);

    let res = run(service_fn(|request: LambdaEvent<S3Event>| {
        function_handler(&s3_client, request)
    })).await;

    res
}

async fn function_handler(
    s3_client: &Client,
    evt: LambdaEvent<S3Event>
) -> Result<(), Error> {
    tracing::info!(records = ?evt.payload.records.len(), "Received request from
 SQS");

    if evt.payload.records.len() == 0 {
        tracing::info!("Empty S3 event received");
    }

    let bucket = evt.payload.records[0].s3.bucket.name.as_ref().expect("Bucket name
 to exist");
    let key = evt.payload.records[0].s3.object.key.as_ref().expect("Object key to
 exist");

    tracing::info!("Request is for {} and object {}", bucket, key);
```

```
    let s3_get_object_result = s3_client
        .get_object()
        .bucket(bucket)
        .key(key)
        .send()
        .await;

    match s3_get_object_result {
        Ok(_) => tracing::info!("S3 Get Object success, the s3GetObjectResult
 contains a 'body' property of type ByteStream"),
        Err(_) => tracing::info!("Failure with S3 Get Object request")
    }

    Ok(())
}
```

SageMaker exemplos usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Rust com. SageMaker

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Listar instâncias de bloco de anotações

O exemplo de código a seguir mostra como listar instâncias do SageMaker notebook.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_instances(client: &Client) -> Result<(), Error> {
    let notebooks = client.list_notebook_instances().send().await?;

    println!("Notebooks:");

    for n in notebooks.notebook_instances() {
        let n_instance_type = n.instance_type().unwrap();
        let n_status = n.notebook_instance_status().unwrap();
        let n_name = n.notebook_instance_name();

        println!("  Name :          {}", n_name.unwrap_or("Unknown"));
        println!("  Status :        {}", n_status.as_ref());
        println!("  Instance Type : {}", n_instance_type.as_ref());
        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWS SDK for Rust.

Listar os trabalhos de treinamento.

O exemplo de código a seguir mostra como listar trabalhos SageMaker de treinamento.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_jobs(client: &Client) -> Result<(), Error> {
    let job_details = client.list_training_jobs().send().await?;

    println!("Jobs:");

    for j in job_details.training_job_summaries() {
        let name = j.training_job_name().unwrap_or("Unknown");
        let creation_time = j.creation_time().expect("creation
 time").to_chrono_utc()?;
        let training_end_time = j
            .training_end_time()
            .expect("Training end time")
            .to_chrono_utc()?;

        let status = j.training_job_status().expect("training status");
        let duration = training_end_time - creation_time;

        println!("  Name:               {}", name);
        println!(
            "  Creation date/time: {}",
            creation_time.format("%Y-%m-%d@%H:%M:%S")
        );
        println!("  Duration (seconds): {}", duration.num_seconds());
        println!("  Status:             {:?}", status);

        println!();
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListTrainingJobsreferência da API AWS SDK for Rust.

Exemplos de Secrets Manager usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Secrets Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um segredo

O exemplo de código a seguir mostra como criar um segredo do Secrets Manager.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_secret(client: &Client, name: &str, value: &str) -> Result<(), Error>
 {
    client
        .create_secret()
        .name(name)
        .secret_string(value)
        .send()
```

```
        .await?;

    println!("Created secret");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateSecretreferência da API AWS SDK for Rust.

Obter um valor secreto

O exemplo de código a seguir mostra como obter um valor de segredo do Secrets Manager.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_secret(client: &Client, name: &str) -> Result<(), Error> {
    let resp = client.get_secret_value().secret_id(name).send().await?;

    println!("Value: {}", resp.secret_string().unwrap_or("No value!"));

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetSecretValuereferência da API AWS SDK for Rust.

listar segredos

O exemplo de código a seguir mostra como listar um segredo do Secrets Manager.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_secrets(client: &Client) -> Result<(), Error> {
    let resp = client.list_secrets().send().await?;

    println!("Secret names:");

    let secrets = resp.secret_list();
    for secret in secrets {
        println!("  {}", secret.name().unwrap_or("No name!"));
    }

    println!("Found {} secrets", secrets.len());

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListSecretsreferência da API AWS SDK for Rust.

Exemplos API v2 do Amazon SES usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon SES API v2.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um contato em uma lista de contatos

O exemplo de código a seguir mostra como criar um contato da API v2 do Amazon SES em uma lista de contatos.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn add_contact(client: &Client, list: &str, email: &str) -> Result<(), Error>
 {
    client
        .create_contact()
        .contact_list_name(list)
        .email_address(email)
        .send()
        .await?;

    println!("Created contact");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateContactreferência da API AWS SDK for Rust.

Criar uma lista de contatos

O exemplo de código a seguir mostra como criar uma lista de contatos da API v2 do Amazon SES.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_list(client: &Client, contact_list: &str) -> Result<(), Error> {
    client
        .create_contact_list()
        .contact_list_name(contact_list)
        .send()
        .await?;

    println!("Created contact list.");

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateContactListreferência da API AWS SDK for Rust.

Obter informações de identidade

O exemplo de código a seguir mostra como obter informações de identidade da API v2 do Amazon SES.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Determina se um endereço de e-mail foi verificado.

```
async fn is_verified(client: &Client, email: &str) -> Result<(), Error> {
    let resp = client
```

```
        .get_email_identity()
        .email_identity(email)
        .send()
        .await?;

    if resp.verified_for_sending_status() {
        println!("The address is verified");
    } else {
        println!("The address is not verified");
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a GetEmailIdentityreferência da API AWS SDK for Rust.

Listar as listas de contatos

O exemplo de código a seguir mostra como listar as listas de contatos da API v2 do Amazon SES.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_lists(client: &Client) -> Result<(), Error> {
    let resp = client.list_contact_lists().send().await?;

    println!("Contact lists:");

    for list in resp.contact_lists() {
        println!("  {}", list.contact_list_name().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListContactListsreferência da API AWS SDK for Rust.

Listar os contatos em uma lista de contatos

O exemplo de código a seguir mostra como listar os contatos em uma lista de contatos da API v2 do Amazon SES.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_contacts(client: &Client, list: &str) -> Result<(), Error> {
    let resp = client
        .list_contacts()
        .contact_list_name(list)
        .send()
        .await?;

    println!("Contacts:");

    for contact in resp.contacts() {
        println!("  {}", contact.email_address().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListContactsreferência da API AWS SDK for Rust.

Enviar um e-mail

O exemplo de código a seguir mostra como enviar um e-mail com a API v2 do Amazon SES.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Envia uma mensagem a todos os membros da lista de contatos.

```
async fn send_message(
    client: &Client,
    list: &str,
    from: &str,
    subject: &str,
    message: &str,
) -> Result<(), Error> {
    // Get list of email addresses from contact list.
    let resp = client
        .list_contacts()
        .contact_list_name(list)
        .send()
        .await?;

    let contacts = resp.contacts();

    let cs: Vec<String> = contacts
        .iter()
        .map(|i| i.email_address().unwrap_or_default().to_string())
        .collect();

    let mut dest: Destination = Destination::builder().build();
    dest.to_addresses = Some(cs);
    let subject_content = Content::builder()
        .data(subject)
        .charset("UTF-8")
        .build()
        .expect("building Content");
    let body_content = Content::builder()
        .data(message)
        .charset("UTF-8")
        .build()
        .expect("building Content");
```

```
    let body = Body::builder().text(body_content).build();

    let msg = Message::builder()
        .subject(subject_content)
        .body(body)
        .build();

    let email_content = EmailContent::builder().simple(msg).build();

    client
        .send_email()
        .from_email_address(from)
        .destination(dest)
        .content(email_content)
        .send()
        .await?;

    println!("Email sent to list");

    Ok(())
}
```

- Para obter detalhes da API, consulte a SendEmailreferência da API AWS SDK for Rust.

Exemplos do Amazon SNS usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

- Exemplos sem servidor

Ações

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_topic(client: &Client, topic_name: &str) -> Result<(), Error> {
    let resp = client.create_topic().name(topic_name).send().await?;

    println!(
        "Created topic with ARN: {}",
        resp.topic_arn().unwrap_or_default()
    );

    Ok(())
}
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWS SDK for Rust.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_topics(client: &Client) -> Result<(), Error> {
    let resp = client.list_topics().send().await?;

    println!("Topic ARNs:");

    for topic in resp.topics() {
        println!("{}", topic.topic_arn().unwrap_or_default());
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWS SDK for Rust.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn subscribe_and_publish(
    client: &Client,
    topic_arn: &str,
    email_address: &str,
) -> Result<(), Error> {
    println!("Receiving on topic with ARN: `{}`", topic_arn);

    let rsp = client
        .subscribe()
        .topic_arn(topic_arn)
        .protocol("email")
        .endpoint(email_address)
        .send()
        .await?;
```

```
    println!("Added a subscription: {:?}", rsp);

    let rsp = client
        .publish()
        .topic_arn(topic_arn)
        .message("hello sns!")
        .send()
        .await?;

    println!("Published message: {:?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte Publish na Referência da API do AWS SDK for Rust.

Inscrever um endereço de e-mail em um tópico

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn subscribe_and_publish(
    client: &Client,
    topic_arn: &str,
    email_address: &str,
) -> Result<(), Error> {
    println!("Receiving on topic with ARN: `{}`", topic_arn);

    let rsp = client
        .subscribe()
        .topic_arn(topic_arn)
        .protocol("email")
        .endpoint(email_address)
```

```
        .send()
        .await?;

    println!("Added a subscription: {:?}", rsp);

    let rsp = client
        .publish()
        .topic_arn(topic_arn)
        .message("hello sns!")
        .send()
        .await?;

    println!("Published message: {:?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte Subscribe na Referência da API do AWS SDK for Rust.

Exemplos sem servidor

Invocar uma função do Lambda em um acionador do Amazon SNS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de um tópico do SNS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SNS com o Lambda usando Rust.

```
use aws_lambda_events::event::sns::SnsEvent;
use aws_lambda_events::sns::SnsRecord;
use lambda_runtime::{run, service_fn, Error, LambdaEvent};
```

```
use tracing::info;

// Built with the following dependencies:
//  aws_lambda_events = { version = "0.10.0", default-features = false, features =
 ["sns"] }
//  lambda_runtime = "0.8.1"
//  tokio = { version = "1", features = ["macros"] }
//  tracing = { version = "0.1", features = ["log"] }
//  tracing-subscriber = { version = "0.3", default-features = false, features =
 ["fmt"] }

async fn function_handler(event: LambdaEvent<SnsEvent>) -> Result<(), Error> {
    for event in event.payload.records {
        process_record(&event)?;
    }

    Ok(())
}

fn process_record(record: &SnsRecord) -> Result<(), Error> {
    info!("Processing SNS Message: {}", record.sns.message);

    // Implement your record handling code here.

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        .with_target(false)
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Exemplos do Amazon SQS usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Exemplos sem servidor

Ações

Listar filas

Os exemplos de código a seguir mostram como listar filas do Amazon SQS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Recuperar a primeira fila do Amazon SQS listada na região.

```
async fn find_first_queue(client: &Client) -> Result<String, Error> {
    let queues = client.list_queues().send().await?;
    let queue_urls = queues.queue_urls();
    Ok(queue_urls
        .first()
        .expect("No queues in this account and Region. Create a queue to proceed.")
        .to_string())
}
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWS SDK for Rust.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como receber mensagens de uma fila do Amazon SQS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn receive(client: &Client, queue_url: &String) -> Result<(), Error> {
    let rcv_message_output =
 client.receive_message().queue_url(queue_url).send().await?;

    println!("Messages from queue with url: {}", queue_url);

    for message in rcv_message_output.messages.unwrap_or_default() {
        println!("Got the message: {:#?}", message);
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWS SDK for Rust.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn send(client: &Client, queue_url: &String, message: &SQSMessage) ->
 Result<(), Error> {
    println!("Sending message to queue with URL: {}", queue_url);

    let rsp = client
        .send_message()
        .queue_url(queue_url)
        .message_body(&message.body)
        // If the queue is FIFO, you need to set .message_deduplication_id
        // and message_group_id or configure the queue for
 ContentBasedDeduplication.
        .send()
        .await?;

    println!("Send message to the queue: {:#?}", rsp);

    Ok(())
}
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWS SDK for Rust.

Exemplos sem servidor

Invocar uma função do Lambda em um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma função do Lambda que recebe um evento acionado pelo recebimento de mensagens de uma fila do SQS. A função recupera as mensagens do parâmetro event e registra o conteúdo de cada mensagem.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Consuma um evento do SQS com o Lambda usando Rust.

```
use aws_lambda_events::event::sqs::SqsEvent;
```

```
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<(), Error> {
    event.payload.records.iter().for_each(|record| {
        // process the record
        tracing::info!("Message body: {}",
 record.body.as_deref().unwrap_or_default())
    });

    Ok(())
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    tracing_subscriber::fmt()
        .with_max_level(tracing::Level::INFO)
        // disable printing the name of the module in every log line.
        .with_target(false)
        // disabling time is handy because CloudWatch will add the ingestion time.
        .without_time()
        .init();

    run(service_fn(function_handler)).await
}
```

Relatar falhas de itens em lote para funções do Lambda com um trigger do Amazon SQS

O exemplo de código a seguir mostra como implementar uma resposta parcial em lote para funções do Lambda que recebem eventos de uma fila do SQS. A função relata as falhas do item em lote na resposta, sinalizando para o Lambda tentar novamente essas mensagens posteriormente.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no repositório dos Exemplos sem servidor.

Relatar falhas de itens em lote do SQS com o Lambda usando Rust.

```
use aws_lambda_events::{
    event::sqs::{SqsBatchResponse, SqsEvent},
    sqs::{BatchItemFailure, SqsMessage},
};
use lambda_runtime::{run, service_fn, Error, LambdaEvent};

async fn process_record(_: &SqsMessage) -> Result<(), Error> {
    Err(Error::from("Error processing message"))
}

async fn function_handler(event: LambdaEvent<SqsEvent>) -> Result<SqsBatchResponse,
 Error> {
    let mut batch_item_failures = Vec::new();
    for record in event.payload.records {
        match process_record(&record).await {
            Ok(_) => (),
            Err(_) => batch_item_failures.push(BatchItemFailure {
                item_identifier: record.message_id.unwrap(),
            }),
        }
    }

    Ok(SqsBatchResponse {
        batch_item_failures,
    })
}

#[tokio::main]
async fn main() -> Result<(), Error> {
    run(service_fn(function_handler)).await
}
```

Exemplos de AWS STS usando SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn assume_role(config: &SdkConfig, role_name: String, session_name:
 Option<String>) {
    let provider = aws_config::sts::AssumeRoleProvider::builder(role_name)
        .session_name(session_name.unwrap_or("rust_sdk_example_session".into()))
        .configure(config)
        .build()
        .await;

    let local_config = aws_config::from_env()
        .credentials_provider(provider)
        .load()
        .await;
    let client = Client::new(&local_config);
    let req = client.get_caller_identity();
    let resp = req.send().await;
    match resp {
        Ok(e) => {
            println!("UserID :               {}", e.user_id().unwrap_or_default());
```

```
            println!("Account:                {}", e.account().unwrap_or_default());
            println!("Arn    :                {}", e.arn().unwrap_or_default());
        }
        Err(e) => println!("{:?}", e),
    }
}
```

- Para obter detalhes da API, consulte a AssumeRolereferência da API AWS SDK for Rust.

Exemplos do Systems Manager usando o SDK para Rust

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando AWS SDK para Rust com Systems Manager.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Adicionar um parâmetro

O exemplo de código a seguir mostra como adicionar um parâmetro do Systems Manager.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn make_parameter(
    client: &Client,
    name: &str,
    value: &str,
    description: &str,
) -> Result<(), Error> {
    let resp = client
        .put_parameter()
        .overwrite(true)
        .r#type(ParameterType::String)
        .name(name)
        .value(value)
        .description(description)
        .send()
        .await?;

    println!("Success! Parameter now has version: {}", resp.version());

    Ok(())
}
```

- Para obter detalhes da API, consulte a PutParameterreferência da API AWS SDK for Rust.

Obter informações de parâmetros

O exemplo de código a seguir mostra como obter informações de parâmetros do Systems Manager.

SDK for Rust

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
async fn show_parameters(client: &Client) -> Result<(), Error> {
    let resp = client.describe_parameters().send().await?;

    for param in resp.parameters() {
        println!("  {}", param.name().unwrap_or_default());
```

```
    }

    Ok(())
}
```

- Para obter detalhes da API, consulte a DescribeParametersreferência da API AWS SDK for Rust.

Exemplos de serviços cruzados usando SDK para Rust

Os aplicativos de exemplo a seguir usam o AWS SDK para Rust para trabalhar múltiplos Serviços da AWS.

Os exemplos de serviços cruzados visam um nível avançado de experiência para ajudar a começar a criar aplicações.

Exemplos

- Converter texto em fala e de volta em texto usando um AWS SDK
- Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos
- Detectar faces em uma imagem usando um AWS SDK
- Salvar o EXIF e outras informações de imagem usando um AWS SDK

Converter texto em fala e de volta em texto usando um AWS SDK

SDK for Rust

Use o Amazon Polly para sintetizar um arquivo de texto simples (UTF-8) para um arquivo de áudio, fazer upload do arquivo de áudio para um bucket do Amazon S3, usar o Amazon Transcribe para converter esse arquivo de áudio em texto e exibir o texto.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Polly
- Amazon S3

- Amazon Transcribe

Criar uma aplicação de gerenciamento de ativos de fotos que permita que os usuários gerenciem fotos usando rótulos

SDK for Rust

Mostra como desenvolver uma aplicação de gerenciamento de ativos fotográficos que detecta rótulos em imagens usando o Amazon Rekognition e os armazena para recuperação posterior.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Para uma análise detalhada da origem desse exemplo, veja a publicação na Comunidade da AWS.

Serviços utilizados neste exemplo

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Detectar faces em uma imagem usando um AWS SDK

SDK for Rust

Salve a imagem em um bucket do Amazon S3 com um prefixo uploads, use o Amazon Rekognition para detectar detalhes faciais, como faixa etária, sexo e emoções (sorriso, etc.), e exiba esses detalhes.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços utilizados neste exemplo

- Amazon Rekognition
- Amazon S3

Salvar o EXIF e outras informações de imagem usando um AWS SDK

SDK for Rust

Obtenha informações de EXIF de um arquivo JPG, JPEG ou PNG, faça upload do arquivo de imagem para um bucket do Amazon S3, use o Amazon Rekognition para identificar os três principais atributos (rótulos no Amazon Rekognition) no arquivo e adicione as informações de EXIF e de rótulo a uma tabela do Amazon DynamoDB na região.

Para obter o código-fonte completo e instruções sobre como configurar e executar, veja o exemplo completo em GitHub.

Serviços usados neste exemplo

- DynamoDB
- Amazon Rekognition
- Amazon S3

Exemplos de código para o SDK para SAP ABAP.

Os exemplos de código a seguir mostram como usar o AWS SDK para SAP ABAP com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do desenvolvedor do SDK para SAP ABAP : Saiba mais sobre como usar o SAP ABAP com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para SAP ABAP

Ações e cenários usando o SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com os Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos do Amazon Bedrock Runtime usando SDK para SAP ABAP
- CloudWatch exemplos usando o SDK para SAP ABAP
- Exemplos do DynamoDB usando o SDK para SAP ABAP
- Exemplos de código para o Amazon EC2 usando SDK para SAP ABAP
- Exemplos do Kinesis usando o SDK para SAP ABAP
- Exemplos de Lambda usando SDK para SAP ABAP
- Exemplos do Amazon S3 usando SDK para SAP ABAP
- SageMaker exemplos usando o SDK para SAP ABAP
- Exemplos do Amazon SNS usando SDK para SAP ABAP
- Exemplos do Amazon SQS usando SDK para SAP ABAP
- Exemplos do Amazon Textract usando SDK para SAP ABAP
- Exemplos do Amazon Translate usando SDK para SAP ABAP

Exemplos do Amazon Bedrock Runtime usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK para SAP ABAP com o Amazon Bedrock Runtime.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Geração de imagens com Stability.ai Stable Diffusion XL

O exemplo de código a seguir mostra como invocar o modelo Stable Diffusion XL da Stability.ai no Amazon Bedrock para geração de imagens.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invoque o modelo de base Stable Diffusion XL da Stability.ai para gerar imagens.

```
    "Stable Diffusion Input Parameters should be in a format like this:
*   {
*     "text_prompts": [
*       {"text":"Draw a dolphin with a mustache"},
*       {"text":"Make it photorealistic"}
*     ],
*     "cfg_scale":10,
*     "seed":0,
*     "steps":50
*   }
    TYPES: BEGIN OF prompt_ts,
```

```
              text TYPE /aws1/rt_shape_string,
            END OF prompt_ts.

    DATA: BEGIN OF ls_input,
            text_prompts TYPE STANDARD TABLE OF prompt_ts,
            cfg_scale    TYPE /aws1/rt_shape_integer,
            seed         TYPE /aws1/rt_shape_integer,
            steps        TYPE /aws1/rt_shape_integer,
          END OF ls_input.

    APPEND VALUE prompt_ts( text = iv_prompt ) TO ls_input-text_prompts.
    ls_input-cfg_scale = 10.
    ls_input-seed = 0. "or better, choose a random integer.
    ls_input-steps = 50.

    DATA(lv_json) = /ui2/cl_json=>serialize(
      data = ls_input
                pretty_name   = /ui2/cl_json=>pretty_mode-low_case ).

    TRY.
        DATA(lo_response) = lo_bdr->invokemodel(
          iv_body = /aws1/cl_rt_util=>string_to_xstring( lv_json )
          iv_modelid = 'stability.stable-diffusion-xl-v0'
          iv_accept = 'application/json'
          iv_contenttype = 'application/json' ).

        "Stable Diffusion Result Format:
*       {
*         "result": "success",
*         "artifacts": [
*           {
*             "seed": 0,
*             "base64": "iVBORw0KGgoAAAANSUhEUgAAAgAAA....
*             "finishReason": "SUCCESS"
*           }
*         ]
*       }
        TYPES: BEGIN OF artifact_ts,
                 seed         TYPE /aws1/rt_shape_integer,
                 base64       TYPE /aws1/rt_shape_string,
                 finishreason TYPE /aws1/rt_shape_string,
               END OF artifact_ts.

        DATA: BEGIN OF ls_response,
```

```
                result    TYPE /aws1/rt_shape_string,
                artifacts TYPE STANDARD TABLE OF artifact_ts,
              END OF ls_response.

        /ui2/cl_json=>deserialize(
          EXPORTING jsonx = lo_response->get_body( )
                    pretty_name = /ui2/cl_json=>pretty_mode-camel_case
          CHANGING  data  = ls_response ).
        IF ls_response-artifacts IS NOT INITIAL.
          DATA(lv_image) =
 cl_http_utility=>if_http_utility~decode_x_base64( ls_response-artifacts[ 1 ]-
base64 ).
        ENDIF.
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

Invoque o modelo básico Stability.ai Stable Diffusion XL para gerar imagens usando o cliente de alto nível L2.

```
    TRY.
        DATA(lo_bdr_l2_sd) = /aws1/
cl_bdr_l2_factory=>create_stable_diffusion_10( lo_bdr ).
      " iv_prompt contains a prompt like 'Show me a picture of a unicorn reading an
 enterprise financial report'.
        DATA(lv_image) = lo_bdr_l2_sd->text_to_image( iv_prompt ).
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

- Para obter detalhes da API, consulte a InvokeModelreferência da API AWS SDK for SAP ABAP.

Geração de texto com o Claude 2 da Anthropic

O exemplo de código a seguir mostra como invocar o modelo Claude 2 da Anthropic no Amazon Bedrock para geração de texto.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Invocar o modelo de base Claude 2 da Anthropic para gerar texto. Este exemplo usa recursos de /US2/CL_JSON que podem não estar disponíveis em algumas versões. NetWeaver

```
    "Claude V2 Input Parameters should be in a format like this:
*   {
*     "prompt":"\n\nHuman:\\nTell me a joke\n\nAssistant:\n",
*     "max_tokens_to_sample":2048,
*     "temperature":0.5,
*     "top_k":250,
*     "top_p":1.0,
*     "stop_sequences":[]
*   }

    DATA: BEGIN OF ls_input,
            prompt               TYPE string,
            max_tokens_to_sample TYPE /aws1/rt_shape_integer,
            temperature          TYPE /aws1/rt_shape_float,
            top_k                TYPE /aws1/rt_shape_integer,
            top_p                TYPE /aws1/rt_shape_float,
            stop_sequences       TYPE /aws1/rt_stringtab,
          END OF ls_input.

    "Leave ls_input-stop_sequences empty.
    ls_input-prompt = |\n\nHuman:\\n{ iv_prompt }\n\nAssistant:\n|.
    ls_input-max_tokens_to_sample = 2048.
    ls_input-temperature = '0.5'.
    ls_input-top_k = 250.
    ls_input-top_p = 1.
```

```
    "Serialize into JSON with /ui2/cl_json -- this assumes SAP_UI is installed.
    DATA(lv_json) = /ui2/cl_json=>serialize(
      data = ls_input
                pretty_name   = /ui2/cl_json=>pretty_mode-low_case ).

    TRY.
        DATA(lo_response) = lo_bdr->invokemodel(
          iv_body = /aws1/cl_rt_util=>string_to_xstring( lv_json )
          iv_modelid = 'anthropic.claude-v2'
          iv_accept = 'application/json'
          iv_contenttype = 'application/json' ).

        "Claude V2 Response format will be:
*       {
*         "completion": "Knock Knock...",
*         "stop_reason": "stop_sequence"
*       }
        DATA: BEGIN OF ls_response,
                completion  TYPE string,
                stop_reason TYPE string,
              END OF ls_response.

        /ui2/cl_json=>deserialize(
          EXPORTING jsonx = lo_response->get_body( )
                    pretty_name = /ui2/cl_json=>pretty_mode-camel_case
          CHANGING  data  = ls_response ).

        DATA(lv_answer) = ls_response-completion.
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

Invoque o modelo básico Anthropic Claude 2 para gerar texto usando o cliente de alto nível L2.

```
    TRY.
        DATA(lo_bdr_l2_claude) = /aws1/cl_bdr_l2_factory=>create_claude_2( lo_bdr ).
        " iv_prompt can contain a prompt like 'tell me a joke about Java
 programmers'.
        DATA(lv_answer) = lo_bdr_l2_claude->prompt_for_text( iv_prompt ).
```

```
      CATCH /aws1/cx_bdraccessdeniedex INTO DATA(lo_ex).
        WRITE / lo_ex->get_text( ).
        WRITE / |Don't forget to enable model access at https://
console.aws.amazon.com/bedrock/home?#/modelaccess|.

    ENDTRY.
```

- Para obter detalhes da API, consulte a InvokeModelreferência da API AWS SDK for SAP ABAP.

CloudWatch exemplos usando o SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com. CloudWatch

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um alarme de métrica

O exemplo de código a seguir mostra como criar ou atualizar um CloudWatch alarme da Amazon e associá-lo à métrica especificada, à expressão matemática métrica, ao modelo de detecção de anomalias ou à consulta do Metrics Insights.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_cwt->putmetricalarm(
          iv_alarmname                = iv_alarm_name
          iv_comparisonoperator       = iv_comparison_operator
          iv_evaluationperiods        = iv_evaluation_periods
          iv_metricname               = iv_metric_name
          iv_namespace                = iv_namespace
          iv_statistic                = iv_statistic
          iv_threshold                = iv_threshold
          iv_actionsenabled           = iv_actions_enabled
          iv_alarmdescription         = iv_alarm_description
          iv_unit                     = iv_unit
          iv_period                   = iv_period
          it_dimensions               = it_dimensions
        ).
        MESSAGE 'Alarm created.' TYPE 'I'.
      CATCH /aws1/cx_cwtlimitexceededfault.
        MESSAGE 'The request processing has exceeded the limit' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutMetricAlarmreferência da API AWS SDK for SAP ABAP.

Excluir alarmes

O exemplo de código a seguir mostra como excluir os CloudWatch alarmes da Amazon.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_cwt->deletealarms(
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarms deleted.' TYPE 'I'.
      CATCH /aws1/cx_cwtresourcenotfound .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteAlarmsreferência da API AWS SDK for SAP ABAP.

Descrever alarmes

O exemplo de código a seguir mostra como descrever os CloudWatch alarmes da Amazon.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_cwt->describealarms(                " oo_result is returned
for testing purposes. "
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarms retrieved.' TYPE 'I'.
```

```
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAlarmsreferência da API AWS SDK for SAP ABAP.

Desabilitar ações de alarme

O exemplo de código a seguir mostra como desativar as ações de CloudWatch alarme da Amazon.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Disables actions on the specified alarm. "
    TRY.
        lo_cwt->disablealarmactions(
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarm actions disabled.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DisableAlarmActionsreferência da API AWS SDK for SAP ABAP.

Habilitar ações de alarme

O exemplo de código a seguir mostra como ativar as ações de CloudWatch alarme da Amazon.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Enable actions on the specified alarm."
    TRY.
        lo_cwt->enablealarmactions(
          it_alarmnames = it_alarm_names
        ).
        MESSAGE 'Alarm actions enabled.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a EnableAlarmActionsreferência da API AWS SDK for SAP ABAP.

Listar as métricas

O exemplo de código a seguir mostra como listar os metadados das CloudWatch métricas da Amazon. Para obter dados de uma métrica, use as GetMetricStatistics ações GetMetricData ou.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "The following list-metrics example displays the metrics for Amazon CloudWatch."
    TRY.
        oo_result = lo_cwt->listmetrics(            " oo_result is returned for
testing purposes. "
          iv_namespace = iv_namespace
        ).
        DATA(lt_metrics) = oo_result->get_metrics( ).
        MESSAGE 'Metrics retrieved.' TYPE 'I'.
      CATCH /aws1/cx_cwtinvparamvalueex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListMetricsreferência da API AWS SDK for SAP ABAP.

Cenários

Começar a usar alarmes

O código de exemplo a seguir mostra como:

- Crie um alarme.
- Desabilite ações de alarme.
- Descreva um alarme.
- Exclua um alarme.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_alarmnames TYPE /aws1/cl_cwtalarmnames_w=>tt_alarmnames.
    DATA lo_alarmname TYPE REF TO /aws1/cl_cwtalarmnames_w.

    "Create an alarm"
```

```
    TRY.
        lo_cwt->putmetricalarm(
          iv_alarmname                = iv_alarm_name
          iv_comparisonoperator       = iv_comparison_operator
          iv_evaluationperiods        = iv_evaluation_periods
          iv_metricname               = iv_metric_name
          iv_namespace                = iv_namespace
          iv_statistic                = iv_statistic
          iv_threshold                = iv_threshold
          iv_actionsenabled           = iv_actions_enabled
          iv_alarmdescription         = iv_alarm_description
          iv_unit                     = iv_unit
          iv_period                   = iv_period
          it_dimensions               = it_dimensions
        ).
        MESSAGE 'Alarm created' TYPE 'I'.
      CATCH /aws1/cx_cwtlimitexceededfault.
        MESSAGE 'The request processing has exceeded the limit' TYPE 'E'.
    ENDTRY.

    "Create an ABAP internal table for the created alarm."
    CREATE OBJECT lo_alarmname EXPORTING iv_value = iv_alarm_name.
    INSERT lo_alarmname INTO TABLE lt_alarmnames.

    "Disable alarm actions."
    TRY.
        lo_cwt->disablealarmactions(
          it_alarmnames               = lt_alarmnames
        ).
        MESSAGE 'Alarm actions disabled' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_disablealarm_exception).
        DATA(lv_disablealarm_error) = |"{ lo_disablealarm_exception->av_err_code }"
- { lo_disablealarm_exception->av_err_msg }|.
        MESSAGE lv_disablealarm_error TYPE 'E'.
    ENDTRY.

    "Describe alarm using the same ABAP internal table."
    TRY.
        oo_result = lo_cwt->describealarms(                       " oo_result is
returned for testing purpose "
          it_alarmnames               = lt_alarmnames
        ).
        MESSAGE 'Alarms retrieved' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_describealarms_exception).
```

```
        DATA(lv_describealarms_error) = |"{ lo_describealarms_exception-
>av_err_code }" - { lo_describealarms_exception->av_err_msg }|.
        MESSAGE lv_describealarms_error TYPE 'E'.
    ENDTRY.

    "Delete alarm."
    TRY.
        lo_cwt->deletealarms(
          it_alarmnames = lt_alarmnames
        ).
        MESSAGE 'Alarms deleted' TYPE 'I'.
      CATCH /aws1/cx_cwtresourcenotfound .
        MESSAGE 'Resource being access is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DeleteAlarms
  - DescribeAlarms
  - DisableAlarmActions
  - PutMetricAlarm

Exemplos do DynamoDB usando o SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA(lt_keyschema) = VALUE /aws1/cl_dynkeyschemaelement=>tt_keyschema(
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'year'
                                              iv_keytype = 'HASH' ) )
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'title'
                                              iv_keytype = 'RANGE' ) ) ).
        DATA(lt_attributedefinitions) = VALUE /aws1/
cl_dynattributedefn=>tt_attributedefinitions(
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'year'
                                           iv_attributetype = 'N' ) )
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'title'
                                           iv_attributetype = 'S' ) ) ).

        " Adjust read/write capacities as desired.
        DATA(lo_dynprovthroughput)  = NEW /aws1/cl_dynprovthroughput(
          iv_readcapacityunits = 5
          iv_writecapacityunits = 5 ).
        oo_result = lo_dyn->createtable(
          it_keyschema = lt_keyschema
          iv_tablename = iv_table_name
          it_attributedefinitions = lt_attributedefinitions
          io_provisionedthroughput = lo_dynprovthroughput ).
        " Table creation can take some time. Wait till table exists before
 returning.
        lo_dyn->get_waiter( )->tableexists(
          iv_max_wait_time = 200
```

```
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table' && iv_table_name && 'created.' TYPE 'I'.
      " This exception can happen if the table already exists.
      CATCH /aws1/cx_dynresourceinuseex INTO DATA(lo_resourceinuseex).
        DATA(lv_error) = |"{ lo_resourceinuseex->av_err_code }" -
{ lo_resourceinuseex->av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTablereferência da API AWS SDK for SAP ABAP.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_dyn->deletetable( iv_tablename = iv_table_name ).
        " Wait till the table is actually deleted.
        lo_dyn->get_waiter( )->tablenotexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'Table ' && iv_table_name && ' deleted.' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table ' && iv_table_name && ' does not exist' TYPE 'E'.
      CATCH /aws1/cx_dynresourceinuseex.
        MESSAGE 'The table cannot be deleted since it is in use' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteTablereferência da API AWS SDK for SAP ABAP.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       DATA(lo_resp) = lo_dyn->deleteitem(
         iv_tablename                = iv_table_name
         it_key                      = it_key_input ).
       MESSAGE 'Deleted one item.' TYPE 'I'.
     CATCH /aws1/cx_dyncondalcheckfaile00.
       MESSAGE 'A condition specified in the operation could not be evaluated.'
TYPE 'E'.
     CATCH /aws1/cx_dynresourcenotfoundex.
       MESSAGE 'The table or index does not exist' TYPE 'E'.
     CATCH /aws1/cx_dyntransactconflictex.
       MESSAGE 'Another transaction is using the item' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteItemreferência da API AWS SDK for SAP ABAP.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_item = lo_dyn->getitem(
          iv_tablename                = iv_table_name
          it_key                      = it_key ).
        DATA(lt_attr) = oo_item->get_item( ).
        DATA(lo_title) = lt_attr[ key = 'title' ]-value.
        DATA(lo_year) = lt_attr[ key = 'year' ]-value.
        DATA(lo_rating) = lt_attr[ key = 'rating' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( )
          && 'Movie year is: ' && lo_year->get_n( )
          && 'Moving rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetItemreferência da API AWS SDK for SAP ABAP.

Obter informações sobre uma tabela

O exemplo de código a seguir mostra como obter informações sobre uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_dyn->describetable( iv_tablename = iv_table_name ).
        DATA(lv_tablename) = oo_result->get_table( )->ask_tablename( ).
        DATA(lv_tablearn) = oo_result->get_table( )->ask_tablearn( ).
        DATA(lv_tablestatus) = oo_result->get_table( )->ask_tablestatus( ).
        DATA(lv_itemcount) = oo_result->get_table( )->ask_itemcount( ).
        MESSAGE 'The table name is ' && lv_tablename
            && '. The table ARN is ' && lv_tablearn
            && '. The tablestatus is ' && lv_tablestatus
            && '. Item count is ' && lv_itemcount TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
```

```
        MESSAGE 'The table ' && lv_tablename && ' does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTablereferência da API AWS SDK for SAP ABAP.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_dyn->listtables( ).
        " You can loop over the oo_result to get table properties like this.
        LOOP AT oo_result->get_tablenames( ) INTO DATA(lo_table_name).
          DATA(lv_tablename) = lo_table_name->get_value( ).
        ENDLOOP.
        DATA(lv_tablecount) = lines( oo_result->get_tablenames( ) ).
        MESSAGE 'Found ' && lv_tablecount && ' tables' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTablesreferência da API AWS SDK for SAP ABAP.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       DATA(lo_resp) = lo_dyn->putitem(
         iv_tablename = iv_table_name
         it_item      = it_item ).
       MESSAGE '1 row inserted into DynamoDB Table' && iv_table_name TYPE 'I'.
     CATCH /aws1/cx_dyncondalcheckfaile00.
       MESSAGE 'A condition specified in the operation could not be evaluated.'
TYPE 'E'.
     CATCH /aws1/cx_dynresourcenotfoundex.
       MESSAGE 'The table or index does not exist' TYPE 'E'.
     CATCH /aws1/cx_dyntransactconflictex.
       MESSAGE 'Another transaction is using the item' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a PutItemreferência da API AWS SDK for SAP ABAP.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       " Query movies for a given year .
```

```
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
            ( NEW /aws1/cl_dynattributevalue( iv_n = |{ iv_year }| ) ) ).
        DATA(lt_key_conditions) = VALUE /aws1/cl_dyncondition=>tt_keyconditions(
          ( VALUE /aws1/cl_dyncondition=>ts_keyconditions_maprow(
          key = 'year'
          value = NEW /aws1/cl_dyncondition(
          it_attributevaluelist = lt_attributelist
          iv_comparisonoperator = |EQ|
          ) ) ) ).
        oo_result = lo_dyn->query(
          iv_tablename = iv_table_name
          it_keyconditions = lt_key_conditions ).
        DATA(lt_items) = oo_result->get_items( ).
        "You can loop over the results to get item attributes.
        LOOP AT lt_items INTO DATA(lt_item).
          DATA(lo_title) = lt_item[ key = 'title' ]-value.
          DATA(lo_year) = lt_item[ key = 'year' ]-value.
        ENDLOOP.
        DATA(lv_count) = oo_result->get_count( ).
        MESSAGE 'Item count is: ' && lv_count TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Query na Referência da API do AWS SDK para SAP ABAP.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        " Scan movies for rating greater than or equal to the rating specified
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
            ( NEW /aws1/cl_dynattributevalue( iv_n = |{ iv_rating }| ) ) ).
        DATA(lt_filter_conditions) = VALUE /aws1/
cl_dyncondition=>tt_filterconditionmap(
          ( VALUE /aws1/cl_dyncondition=>ts_filterconditionmap_maprow(
          key = 'rating'
          value = NEW /aws1/cl_dyncondition(
          it_attributevaluelist = lt_attributelist
          iv_comparisonoperator = |GE|
          ) ) ) ).
        oo_scan_result = lo_dyn->scan( iv_tablename = iv_table_name
          it_scanfilter = lt_filter_conditions ).
        DATA(lt_items) = oo_scan_result->get_items( ).
        LOOP AT lt_items INTO DATA(lo_item).
          " You can loop over to get individual attributes.
          DATA(lo_title) = lo_item[ key = 'title' ]-value.
          DATA(lo_year) = lo_item[ key = 'year' ]-value.
        ENDLOOP.
        DATA(lv_count) = oo_scan_result->get_count( ).
        MESSAGE 'Found ' && lv_count && ' items' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Scan na Referência da API do AWS SDK para SAP ABAP.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_output = lo_dyn->updateitem(
          iv_tablename        = iv_table_name
          it_key              = it_item_key
          it_attributeupdates = it_attribute_updates ).
        MESSAGE '1 item updated in DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateItemreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    " Create an Amazon Dynamo DB table.

    TRY.
        DATA(lo_session) = /aws1/cl_rt_session_aws=>create( cv_pfl ).
        DATA(lo_dyn) = /aws1/cl_dyn_factory=>create( lo_session ).
        DATA(lt_keyschema) = VALUE /aws1/cl_dynkeyschemaelement=>tt_keyschema(
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'year'
                                              iv_keytype = 'HASH' ) )
          ( NEW /aws1/cl_dynkeyschemaelement( iv_attributename = 'title'
                                              iv_keytype = 'RANGE' ) ) ).
        DATA(lt_attributedefinitions) = VALUE /aws1/
cl_dynattributedefn=>tt_attributedefinitions(
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'year'
                                           iv_attributetype = 'N' ) )
          ( NEW /aws1/cl_dynattributedefn( iv_attributename = 'title'
                                           iv_attributetype = 'S' ) ) ).

        " Adjust read/write capacities as desired.
        DATA(lo_dynprovthroughput)  = NEW /aws1/cl_dynprovthroughput(
          iv_readcapacityunits = 5
          iv_writecapacityunits = 5 ).
        DATA(oo_result) = lo_dyn->createtable(
          it_keyschema = lt_keyschema
          iv_tablename = iv_table_name
          it_attributedefinitions = lt_attributedefinitions
          io_provisionedthroughput = lo_dynprovthroughput ).
        " Table creation can take some time. Wait till table exists before
 returning.
        lo_dyn->get_waiter( )->tableexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table' && iv_table_name && 'created.' TYPE 'I'.
      " It throws exception if the table already exists.
      CATCH /aws1/cx_dynresourceinuseex INTO DATA(lo_resourceinuseex).
        DATA(lv_error) = |"{ lo_resourceinuseex->av_err_code }" -
 { lo_resourceinuseex->av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.

    " Describe table
    TRY.
        DATA(lo_table) = lo_dyn->describetable( iv_tablename = iv_table_name ).
        DATA(lv_tablename) = lo_table->get_table( )->ask_tablename( ).
```

```
        MESSAGE 'The table name is ' && lv_tablename TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table does not exist' TYPE 'E'.
    ENDTRY.

    " Put items into the table.
    TRY.
        DATA(lo_resp_putitem) = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Jaws' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1975' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '7.5' }| ) ) )
          ) ).
        lo_resp_putitem = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s = 'Star
 Wars' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1978' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '8.1' }| ) ) )
          ) ).
        lo_resp_putitem = lo_dyn->putitem(
          iv_tablename = iv_table_name
          it_item      = VALUE /aws1/
cl_dynattributevalue=>tt_putiteminputattributemap(
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Speed' ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
```

```
              key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '1994' }| ) ) )
            ( VALUE /aws1/cl_dynattributevalue=>ts_putiteminputattrmap_maprow(
              key = 'rating' value = NEW /aws1/cl_dynattributevalue( iv_n = |
{ '7.9' }| ) ) )
          ) ).
        " TYPE REF TO ZCL_AWS1_dyn_PUT_ITEM_OUTPUT
        MESSAGE '3 rows inserted into DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
 TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.

    " Get item from table.
    TRY.
        DATA(lo_resp_getitem) = lo_dyn->getitem(
          iv_tablename                = iv_table_name
          it_key                      = VALUE /aws1/cl_dynattributevalue=>tt_key(
           ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
             key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
 'Jaws' ) ) )
           ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
             key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n =
 '1975' ) ) )
          ) ).
        DATA(lt_attr) = lo_resp_getitem->get_item( ).
        DATA(lo_title) = lt_attr[ key = 'title' ]-value.
        DATA(lo_year) = lt_attr[ key = 'year' ]-value.
        DATA(lo_rating) = lt_attr[ key = 'year' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Query item from table.
    TRY.
        DATA(lt_attributelist) = VALUE /aws1/
cl_dynattributevalue=>tt_attributevaluelist(
```

```
              ( NEW /aws1/cl_dynattributevalue( iv_n = '1975' ) ) ).
        DATA(lt_keyconditions) = VALUE /aws1/cl_dyncondition=>tt_keyconditions(
          ( VALUE /aws1/cl_dyncondition=>ts_keyconditions_maprow(
          key = 'year'
          value = NEW /aws1/cl_dyncondition(
            it_attributevaluelist = lt_attributelist
            iv_comparisonoperator = |EQ|
          ) ) ) ).
        DATA(lo_query_result) = lo_dyn->query(
          iv_tablename = iv_table_name
          it_keyconditions = lt_keyconditions ).
        DATA(lt_items) = lo_query_result->get_items( ).
        READ TABLE lo_query_result->get_items( ) INTO DATA(lt_item) INDEX 1.
        lo_title = lt_item[ key = 'title' ]-value.
        lo_year = lt_item[ key = 'year' ]-value.
        lo_rating = lt_item[ key = 'rating' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Scan items from table.
    TRY.
        DATA(lo_scan_result) = lo_dyn->scan( iv_tablename = iv_table_name ).
        lt_items = lo_scan_result->get_items( ).
        " Read the first item and display the attributes.
        READ TABLE lo_query_result->get_items( ) INTO lt_item INDEX 1.
        lo_title = lt_item[ key = 'title' ]-value.
        lo_year = lt_item[ key = 'year' ]-value.
        lo_rating = lt_item[ key = 'rating' ]-value.
        MESSAGE 'Movie name is: ' && lo_title->get_s( ) TYPE 'I'.
        MESSAGE 'Movie year is: ' && lo_year->get_n( ) TYPE 'I'.
        MESSAGE 'Movie rating is: ' && lo_rating->get_n( ) TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
    ENDTRY.

    " Update items from table.
    TRY.
        DATA(lt_attributeupdates) = VALUE /aws1/
cl_dynattrvalueupdate=>tt_attributeupdates(
          ( VALUE /aws1/cl_dynattrvalueupdate=>ts_attributeupdates_maprow(
```

```
          key = 'rating' value = NEW /aws1/cl_dynattrvalueupdate(
            io_value  = NEW /aws1/cl_dynattributevalue( iv_n = '7.6' )
            iv_action = |PUT| ) ) ) ).
        DATA(lt_key) = VALUE /aws1/cl_dynattributevalue=>tt_key(
          ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
            key = 'year' value = NEW /aws1/cl_dynattributevalue( iv_n = '1975' ) ) )
          ( VALUE /aws1/cl_dynattributevalue=>ts_key_maprow(
            key = 'title' value = NEW /aws1/cl_dynattributevalue( iv_s =
'1980' ) ) ) ).
        DATA(lo_resp) = lo_dyn->updateitem(
          iv_tablename        = iv_table_name
          it_key              = lt_key
          it_attributeupdates = lt_attributeupdates ).
        MESSAGE '1 item updated in DynamoDB Table' && iv_table_name TYPE 'I'.
      CATCH /aws1/cx_dyncondalcheckfaile00.
        MESSAGE 'A condition specified in the operation could not be evaluated.'
TYPE 'E'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dyntransactconflictex.
        MESSAGE 'Another transaction is using the item' TYPE 'E'.
    ENDTRY.

    " Delete table.
    TRY.
        lo_dyn->deletetable( iv_tablename = iv_table_name ).
        lo_dyn->get_waiter( )->tablenotexists(
          iv_max_wait_time = 200
          iv_tablename     = iv_table_name ).
        MESSAGE 'DynamoDB Table deleted.' TYPE 'I'.
      CATCH /aws1/cx_dynresourcenotfoundex.
        MESSAGE 'The table or index does not exist' TYPE 'E'.
      CATCH /aws1/cx_dynresourceinuseex.
        MESSAGE 'The table cannot be deleted as it is in use' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - BatchWriteItem
  - CreateTable
  - DeleteItem

- DeleteTable
- DescribeTable
- GetItem
- PutItem
- Query
- Scan
- UpdateItem

Exemplos de código para o Amazon EC2 usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Alocar um endereço IP elástico

O exemplo de código a seguir mostra como alocar um endereço IP elástico para o Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->allocateaddress( iv_domain = 'vpc' ).   " oo_result is
 returned for testing purposes. "
        MESSAGE 'Allocated an Elastic IP address.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a AllocateAddressreferência da API AWS SDK for SAP ABAP.

Para associar um endereço IP elástico a uma instância

O exemplo de código a seguir mostra como associar um endereço IP elástico a uma instância do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->associateaddress(                        " oo_result is
 returned for testing purposes. "
            iv_allocationid = iv_allocation_id
            iv_instanceid = iv_instance_id
```

```
        ).
        MESSAGE 'Associated an Elastic IP address with an EC2 instance.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a AssociateAddressreferência da API AWS SDK for SAP ABAP.

Criar um grupo de segurança

O exemplo de código a seguir mostra como criar um grupo de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->createsecuritygroup(                " oo_result is
 returned for testing purposes. "
          iv_description = 'Security group example'
          iv_groupname = iv_security_group_name
          iv_vpcid = iv_vpc_id
        ).
        MESSAGE 'Security group created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateSecurityGroupreferência da API AWS SDK for SAP ABAP.

Criar um par de chaves de segurança

O exemplo de código a seguir mostra como criar um par de chaves de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->createkeypair( iv_keyname = iv_key_name ).
              " oo_result is returned for testing purposes. "
        MESSAGE 'Amazon EC2 key pair created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateKeyPairreferência da API AWS SDK for SAP ABAP.

Criar e executar uma instância

O exemplo de código a seguir mostra como criar e executar uma instância do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    " Create tags for resource created during instance launch. "
    DATA lt_tagspecifications TYPE /aws1/
cl_ec2tagspecification=>tt_tagspecificationlist.
    DATA ls_tagspecifications LIKE LINE OF lt_tagspecifications.
    ls_tagspecifications =  NEW /aws1/cl_ec2tagspecification(
      iv_resourcetype = 'instance'
      it_tags = VALUE /aws1/cl_ec2tag=>tt_taglist(
        ( NEW /aws1/cl_ec2tag( iv_key = 'Name' iv_value = iv_tag_value ) )
      )
    ).
    APPEND ls_tagspecifications TO lt_tagspecifications.

    TRY.
        " Create/launch Amazon Elastic Compute Cloud (Amazon EC2) instance. "
        oo_result = lo_ec2->runinstances(                           " oo_result is
 returned for testing purposes. "
          iv_imageid = iv_ami_id
          iv_instancetype = 't2.micro'
          iv_maxcount = 1
          iv_mincount = 1
          it_tagspecifications = lt_tagspecifications
          iv_subnetid = iv_subnet_id
        ).
        MESSAGE 'EC2 instance created.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a RunInstancesreferência da API AWS SDK for SAP ABAP.

Exclua um grupo de segurança

O exemplo de código a seguir mostra como excluir um grupo de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->deletesecuritygroup( iv_groupid = iv_security_group_id ).
        MESSAGE 'Security group deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteSecurityGroupreferência da API AWS SDK for SAP ABAP.

Excluir um par de chaves de segurança

O exemplo de código a seguir mostra como excluir um par de chaves de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->deletekeypair( iv_keyname = iv_key_name ).
        MESSAGE 'Amazon EC2 key pair deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
```

```
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteKeyPairreferência da API AWS SDK for SAP ABAP.

Descrever as zonas de disponibilidade

O exemplo de código a seguir mostra como descrever as zonas de disponibilidade do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeavailabilityzones( ) .                      "
 oo_result is returned for testing purposes. "
        DATA(lt_zones) = oo_result->get_availabilityzones( ).
        MESSAGE 'Retrieved information about Availability Zones.' TYPE 'I'.

      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAvailabilityZonesreferência da API AWS SDK for SAP ABAP.

Descrever regiões

O exemplo de código a seguir mostra como descrever as regiões do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeregions( ) .                        " oo_result
 is returned for testing purposes. "
        DATA(lt_regions) = oo_result->get_regions( ).
        MESSAGE 'Retrieved information about Regions.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeRegionsreferência da API AWS SDK for SAP ABAP.

Descrever instâncias

O exemplo de código a seguir mostra como descrever instâncias do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describeinstances( ) .                        "
 oo_result is returned for testing purposes. "
```

```
        " Retrieving details of EC2 instances. "
        DATA: lv_istance_id    TYPE /aws1/ec2string,
              lv_status        TYPE /aws1/ec2instancestatename,
              lv_instance_type TYPE /aws1/ec2instancetype,
              lv_image_id      TYPE /aws1/ec2string.
        LOOP AT oo_result->get_reservations( ) INTO DATA(lo_reservation).
          LOOP AT lo_reservation->get_instances( ) INTO DATA(lo_instance).
            lv_istance_id = lo_instance->get_instanceid( ).
            lv_status =  lo_instance->get_state( )->get_name( ).
            lv_instance_type = lo_instance->get_instancetype( ).
            lv_image_id = lo_instance->get_imageid( ).
          ENDLOOP.
        ENDLOOP.
        MESSAGE 'Retrieved information about EC2 instances.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeInstancesreferência da API AWS SDK for SAP ABAP.

Habilitar monitoramento

O exemplo de código a seguir mostra como habilitar o monitoramento em uma instância do Amazon EC2 em execução.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
```

```
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to monitor
 the instance without actually making the request. "
        lo_ec2->monitorinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to monitor this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to enable detailed monitoring completed.' TYPE 'I'.
          " DryRun is set to false to enable detailed monitoring. "
          lo_ec2->monitorinstances(
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Detailed monitoring enabled.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to monitor this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to enable detailed monitoring failed. User does not have
 the permissions to monitor the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a MonitorInstancesreferência da API AWS SDK for SAP ABAP.

Obter dados sobre um grupo de segurança

O exemplo de código a seguir mostra como obter dados sobre um grupo de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA lt_group_ids TYPE /aws1/cl_ec2groupidstrlist_w=>tt_groupidstringlist.
        APPEND NEW /aws1/cl_ec2groupidstrlist_w( iv_value = iv_group_id ) TO
 lt_group_ids.
        oo_result = lo_ec2->describesecuritygroups( it_groupids = lt_group_ids ).
      " oo_result is returned for testing purposes. "
        DATA(lt_security_groups) = oo_result->get_securitygroups( ).
        MESSAGE 'Retrieved information about security groups.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeSecurityGroupsreferência da API AWS SDK for SAP ABAP.

Obter detalhes sobre endereços IP elásticos

O exemplo de código a seguir mostra como obter detalhes sobre endereços IP elásticos.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        oo_result = lo_ec2->describeaddresses( ) .                        "
 oo_result is returned for testing purposes. "
        DATA(lt_addresses) = oo_result->get_addresses( ).
        MESSAGE 'Retrieved information about Elastic IP addresses.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeAddressesreferência da API AWS SDK for SAP ABAP.

Listar pares de chaves de segurança

O exemplo de código a seguir mostra como listar pares de chaves de segurança do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_ec2->describekeypairs( ) .                        " oo_result
 is returned for testing purposes. "
        DATA(lt_key_pairs) = oo_result->get_keypairs( ).
        MESSAGE 'Retrieved information about key pairs.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeKeyPairsreferência da API AWS SDK for SAP ABAP.

Reinicializar uma instância

O exemplo de código a seguir mostra como reinicializar uma instância do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to reboot
 the instance without actually making the request. "
        lo_ec2->rebootinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to reboot this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to reboot instance completed.' TYPE 'I'.
          " DryRun is set to false to make a reboot request. "
          lo_ec2->rebootinstances(
             it_instanceids = lt_instance_ids
             iv_dryrun = abap_false
           ).
          MESSAGE 'Instance rebooted.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to reboot this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to reboot instance failed. User does not have permissions
 to reboot the instance.' TYPE 'E'.
        ELSE.
```

```
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a RebootInstancesreferência da API AWS SDK for SAP ABAP.

Liberar um endereço IP elástico

O exemplo de código a seguir mostra como liberar um endereço IP elástico.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_ec2->releaseaddress( iv_allocationid = iv_allocation_id ).
        MESSAGE 'Elastic IP address released.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ReleaseAddressreferência da API AWS SDK for SAP ABAP.

Iniciar uma instância

O exemplo de código a seguir mostra como iniciar uma instância do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to start
 the instance without actually making the request. "
        lo_ec2->startinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to start this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to start instance completed.' TYPE 'I'.
          " DryRun is set to false to start instance. "
          oo_result = lo_ec2->startinstances(           " oo_result is returned for
 testing purposes. "
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Successfully started the EC2 instance.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to start this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to start instance failed. User does not have permissions
 to start the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
```

```
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartInstancesreferência da API AWS SDK for SAP ABAP.

Interromper uma instância

O exemplo de código a seguir mostra como interromper uma instância do Amazon EC2.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_instance_ids TYPE /aws1/
cl_ec2instidstringlist_w=>tt_instanceidstringlist.
    APPEND NEW /aws1/cl_ec2instidstringlist_w( iv_value = iv_instance_id ) TO
 lt_instance_ids.

    "Perform dry run"
    TRY.
        " DryRun is set to true. This checks for the required permissions to stop
 the instance without actually making the request. "
        lo_ec2->stopinstances(
          it_instanceids = lt_instance_ids
          iv_dryrun = abap_true
        ).
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        " If the error code returned is `DryRunOperation`, then you have the
 required permissions to stop this instance. "
        IF lo_exception->av_err_code = 'DryRunOperation'.
          MESSAGE 'Dry run to stop instance completed.' TYPE 'I'.
          " DryRun is set to false to stop instance. "
          oo_result = lo_ec2->stopinstances(           " oo_result is returned for
 testing purposes. "
```

```
            it_instanceids = lt_instance_ids
            iv_dryrun = abap_false
          ).
          MESSAGE 'Successfully stopped the EC2 instance.' TYPE 'I'.
          " If the error code returned is `UnauthorizedOperation`, then you don't
 have the required permissions to stop this instance. "
        ELSEIF lo_exception->av_err_code = 'UnauthorizedOperation'.
          MESSAGE 'Dry run to stop instance failed. User does not have permissions
 to stop the instance.' TYPE 'E'.
        ELSE.
          DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
          MESSAGE lv_error TYPE 'E'.
        ENDIF.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StopInstancesreferência da API AWS SDK for SAP ABAP.

Exemplos do Kinesis usando o SDK para SAP ABAP

O exemplo de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Kinesis.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um stream

O exemplo de código a seguir mostra como criar um stream do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       lo_kns->createstream(
           iv_streamname = iv_stream_name
           iv_shardcount = iv_shard_count
       ).
       MESSAGE 'Stream created.' TYPE 'I'.
     CATCH /aws1/cx_knsinvalidargumentex.
       MESSAGE 'The specified argument was not valid.' TYPE 'E'.
     CATCH /aws1/cx_knslimitexceededex .
       MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
     CATCH /aws1/cx_knsresourceinuseex .
       MESSAGE 'The request processing has failed because the resource is in use.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a CreateStreamreferência da API AWS SDK for SAP ABAP.

Excluir um stream

O exemplo de código a seguir mostra como excluir um stream do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       lo_kns->deletestream(
           iv_streamname = iv_stream_name
       ).
       MESSAGE 'Stream deleted.' TYPE 'I'.
     CATCH /aws1/cx_knslimitexceededex .
       MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
     CATCH /aws1/cx_knsresourceinuseex .
       MESSAGE 'The request processing has failed because the resource is in use.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteStreamreferência da API AWS SDK for SAP ABAP.

Descrever um stream

O exemplo de código a seguir mostra como descrever um fluxo do Kinesis

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_kns->describestream(
           iv_streamname = iv_stream_name
```

```
        ).
        DATA(lt_stream_description) = oo_result->get_streamdescription( ).
        MESSAGE 'Streams retrieved.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeStreamreferência da API AWS SDK for SAP ABAP.

Obter dados em lotes de um stream

O exemplo de código a seguir mostra como obter dados em lotes de um stream do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_kns->getrecords(             " oo_result is returned for
testing purposes. "
            iv_sharditerator = iv_shard_iterator
        ).
        DATA(lt_records) = oo_result->get_records( ).
        MESSAGE 'Record retrieved.' TYPE 'I'.
      CATCH /aws1/cx_knsexpirediteratorex .
        MESSAGE 'Iterator expired.' TYPE 'E'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
      CATCH /aws1/cx_knskmsdisabledex .
```

```
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request quotas.'
TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested data
is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - GetRecords
  - GetShardIterator

Listar streams

O exemplo de código a seguir mostra como listar informações em um ou mais streams do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_kns->liststreams(        " oo_result is returned for testing
purposes. "
            "Set Limit to specify that a maximum of streams should be returned."
            iv_limit = iv_limit
        ).
```

```
        DATA(lt_streams) = oo_result->get_streamnames( ).
        MESSAGE 'Streams listed.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceed
exception.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListStreamsreferência da API AWS SDK for SAP ABAP.

Inserir dados em um stream

O exemplo de código a seguir mostra como colocar dados em um stream do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_kns->putrecord(            " oo_result is returned for
testing purposes. "
            iv_streamname = iv_stream_name
            iv_data       = iv_data
            iv_partitionkey = iv_partition_key
        ).
        MESSAGE 'Record created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
      CATCH /aws1/cx_knskmsdisabledex .
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
```

```
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request quotas.'
TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested data
is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a PutRecordreferência da API AWS SDK for SAP ABAP.

Registrar um consumidor

O exemplo de código a seguir mostra como registrar um consumidor para um stream do Kinesis.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_kns->registerstreamconsumer(       " oo_result is returned
for testing purposes. "
            iv_streamarn = iv_stream_arn
            iv_consumername = iv_consumer_name
        ).
        MESSAGE 'Stream consumer registered.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a RegisterStreamConsumerreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de fluxos de dados

O código de exemplo a seguir mostra como:

- Crie um stream e coloque um registro nele.
- Crie um iterador de fragmentos.
- Leia o registro e, em seguida, limpe os recursos.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
DATA lo_stream_describe_result TYPE REF TO /aws1/cl_knsdescrstreamoutput.
DATA lo_stream_description TYPE REF TO /aws1/cl_knsstreamdescription.
DATA lo_sharditerator TYPE REF TO /aws1/cl_knsgetsharditerator01.
DATA lo_record_result TYPE REF TO /aws1/cl_knsputrecordoutput.

"Create stream."
TRY.
    lo_kns->createstream(
        iv_streamname = iv_stream_name
        iv_shardcount = iv_shard_count
    ).
    MESSAGE 'Stream created.' TYPE 'I'.
  CATCH /aws1/cx_knsinvalidargumentex.
    MESSAGE 'The specified argument was not valid.' TYPE 'E'.
  CATCH /aws1/cx_knslimitexceededex .
```

```
        MESSAGE 'The request processing has failed because of a limit exceeded
exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourceinuseex .
        MESSAGE 'The request processing has failed because the resource is in use.'
TYPE 'E'.
    ENDTRY.

    "Wait for stream to becomes active."
    lo_stream_describe_result = lo_kns->describestream( iv_streamname =
iv_stream_name ).
    lo_stream_description = lo_stream_describe_result->get_streamdescription( ).
    WHILE lo_stream_description->get_streamstatus( ) <> 'ACTIVE'.
      IF sy-index = 30.
        EXIT.               "maximum 5 minutes"
      ENDIF.
      WAIT UP TO 10 SECONDS.
      lo_stream_describe_result = lo_kns->describestream( iv_streamname =
iv_stream_name ).
      lo_stream_description =  lo_stream_describe_result->get_streamdescription( ).
    ENDWHILE.

    "Create record."
    TRY.
        lo_record_result = lo_kns->putrecord(
            iv_streamname = iv_stream_name
            iv_data       = iv_data
            iv_partitionkey = iv_partition_key
        ).
        MESSAGE 'Record created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
      CATCH /aws1/cx_knskmsdisabledex .
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
```

```
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request quotas.'
TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested data
is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Create a shard iterator in order to read the record."
    TRY.
        lo_sharditerator = lo_kns->getsharditerator(
          iv_shardid = lo_record_result->get_shardid( )
          iv_sharditeratortype = iv_sharditeratortype
          iv_streamname = iv_stream_name
      ).
        MESSAGE 'Shard iterator created.' TYPE 'I'.
      CATCH /aws1/cx_knsinvalidargumentex.
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested data
is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Read the record."
    TRY.
        oo_result = lo_kns->getrecords(                    " oo_result is returned
for testing purposes. "
            iv_sharditerator   = lo_sharditerator->get_sharditerator( )
        ).
        MESSAGE 'Shard iterator created.' TYPE 'I'.
      CATCH /aws1/cx_knsexpirediteratorex .
        MESSAGE 'Iterator expired.' TYPE 'E'.
      CATCH /aws1/cx_knsinvalidargumentex .
        MESSAGE 'The specified argument was not valid.' TYPE 'E'.
      CATCH /aws1/cx_knskmsaccessdeniedex .
        MESSAGE 'You do not have permission to perform this AWS KMS action.' TYPE
'E'.
      CATCH /aws1/cx_knskmsdisabledex .
        MESSAGE 'KMS key used is disabled.' TYPE 'E'.
      CATCH /aws1/cx_knskmsinvalidstateex .
        MESSAGE 'KMS key used is in an invalid state. ' TYPE 'E'.
```

```
      CATCH /aws1/cx_knskmsnotfoundex .
        MESSAGE 'KMS key used is not found.' TYPE 'E'.
      CATCH /aws1/cx_knskmsoptinrequired .
        MESSAGE 'KMS key option is required.' TYPE 'E'.
      CATCH /aws1/cx_knskmsthrottlingex .
        MESSAGE 'The rate of requests to AWS KMS is exceeding the request quotas.'
TYPE 'E'.
      CATCH /aws1/cx_knsprovthruputexcdex .
        MESSAGE 'The request rate for the stream is too high, or the requested data
is too large for the available throughput.' TYPE 'E'.
      CATCH /aws1/cx_knsresourcenotfoundex .
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
    ENDTRY.

    "Delete stream."
    TRY.
        lo_kns->deletestream(
            iv_streamname = iv_stream_name
        ).
        MESSAGE 'Stream deleted.' TYPE 'I'.
      CATCH /aws1/cx_knslimitexceededex .
        MESSAGE 'The request processing has failed because of a limit exceeded
exception.' TYPE 'E'.
      CATCH /aws1/cx_knsresourceinuseex .
        MESSAGE 'The request processing has failed because the resource is in use.'
TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateStream
  - DeleteStream
  - GetRecords
  - GetShardIterator
  - PutRecord

Exemplos de Lambda usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Lambda.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma função

O exemplo de código a seguir mostra como criar uma função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_lmd->createfunction(
        iv_functionname = iv_function_name
        iv_runtime = `python3.9`
        iv_role = iv_role_arn
        iv_handler = iv_handler
        io_code = io_zip_file
        iv_description = 'AWS Lambda code example'
```

```
        ).
        MESSAGE 'Lambda function created.' TYPE 'I'.
      CATCH /aws1/cx_lmdcodesigningcfgno00.
        MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdcodestorageexcdex.
        MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
      CATCH /aws1/cx_lmdcodeverification00.
        MESSAGE 'Code signature failed one or more validation checks for signature
mismatch or expiration.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvalidcodesigex.
        MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.' TYPE
'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateFunctionreferência da API AWS SDK for SAP ABAP.

Excluir uma função

O exemplo de código a seguir mostra como excluir uma função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        lo_lmd->deletefunction( iv_functionname = iv_function_name ).
        MESSAGE 'Lambda function deleted.' TYPE 'I'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.' TYPE
'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteFunctionreferência da API AWS SDK for SAP ABAP.

Obter uma função

O exemplo de código a seguir mostra como obter uma função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result =  lo_lmd->getfunction( iv_functionname = iv_function_name ).
 " oo_result is returned for testing purposes. "
        MESSAGE 'Lambda function information retrieved.' TYPE 'I'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
```

```
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetFunctionreferência da API AWS SDK for SAP ABAP.

Invocar uma função

O exemplo de código a seguir mostra como invocar uma função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        DATA(lv_json) = /aws1/cl_rt_util=>string_to_xstring(
          `{`  &&
            `"action": "increment",`  &&
            `"number": 10` &&
          `}`
        ).
        oo_result =  lo_lmd->invoke(                  " oo_result is returned for
testing purposes. "
                iv_functionname = iv_function_name
                iv_payload = lv_json
            ).
        MESSAGE 'Lambda function invoked.' TYPE 'I'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvrequestcontex.
        MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvalidzipfileex.
        MESSAGE 'The deployment package could not be unzipped.' TYPE 'E'.
      CATCH /aws1/cx_lmdrequesttoolargeex.
        MESSAGE 'Invoke request body JSON input limit was exceeded by the request
payload.' TYPE 'E'.
      CATCH /aws1/cx_lmdresourceconflictex.
```

```
        MESSAGE 'Resource already exists or another operation is in progress.' TYPE
'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
      CATCH /aws1/cx_lmdunsuppedmediatyp00.
        MESSAGE 'Invoke request body does not have JSON as its content type.' TYPE
'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Invoke na Referência da API do AWS SDK para SAP ABAP.

Listar as funções

O exemplo de código a seguir mostra como listar funções do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result =  lo_lmd->listfunctions( ).       " oo_result is returned for
testing purposes. "
        DATA(lt_functions) = oo_result->get_functions( ).
        MESSAGE 'Retrieved list of Lambda functions.' TYPE 'I'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
```

```
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListFunctionsreferência da API AWS SDK for SAP ABAP.

Atualizar um código de função

O exemplo de código a seguir mostra como atualizar um código de função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_lmd->updatefunctioncode(     " oo_result is returned for
testing purposes. "
             iv_functionname = iv_function_name
             iv_zipfile = io_zip_file
         ).

       MESSAGE 'Lambda function code updated.' TYPE 'I'.
     CATCH /aws1/cx_lmdcodesigningcfgno00.
       MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
     CATCH /aws1/cx_lmdcodestorageexcdex.
       MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
     CATCH /aws1/cx_lmdcodeverification00.
       MESSAGE 'Code signature failed one or more validation checks for signature
mismatch or expiration.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvalidcodesigex.
       MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
     CATCH /aws1/cx_lmdinvparamvalueex.
       MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
     CATCH /aws1/cx_lmdresourceconflictex.
       MESSAGE 'Resource already exists or another operation is in progress.' TYPE
'E'.
     CATCH /aws1/cx_lmdresourcenotfoundex.
       MESSAGE 'The requested resource does not exist.' TYPE 'E'.
```

```
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateFunctionCodereferência da API AWS SDK for SAP ABAP.

Atualizar uma configuração de função

O exemplo de código a seguir mostra como atualizar uma configuração de função do Lambda.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_lmd->updatefunctionconfiguration(     " oo_result is returned
for testing purposes. "
              iv_functionname = iv_function_name
              iv_runtime = iv_runtime
              iv_description  = 'Updated Lambda function'
              iv_memorysize  = iv_memory_size
          ).

        MESSAGE 'Lambda function configuration/settings updated.' TYPE 'I'.
      CATCH /aws1/cx_lmdcodesigningcfgno00.
        MESSAGE 'Code signing configuration does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdcodeverification00.
        MESSAGE 'Code signature failed one or more validation checks for signature
mismatch or expiration.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvalidcodesigex.
        MESSAGE 'Code signature failed the integrity check.' TYPE 'E'.
      CATCH /aws1/cx_lmdinvparamvalueex.
        MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
```

```
      CATCH /aws1/cx_lmdresourceconflictex.
        MESSAGE 'Resource already exists or another operation is in progress.' TYPE
'E'.
      CATCH /aws1/cx_lmdresourcenotfoundex.
        MESSAGE 'The requested resource does not exist.' TYPE 'E'.
      CATCH /aws1/cx_lmdserviceexception.
        MESSAGE 'An internal problem was encountered by the AWS Lambda service.'
TYPE 'E'.
      CATCH /aws1/cx_lmdtoomanyrequestsex.
        MESSAGE 'The maximum request throughput was reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a UpdateFunctionConfigurationreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de funções

O código de exemplo a seguir mostra como:

- Crie um perfil do IAM e uma função do Lambda e carregue o código de manipulador.
- Invoque essa função com um único parâmetro e receba resultados.
- Atualize o código de função e configure usando uma variável de ambiente.
- Invoque a função com novos parâmetros e receba resultados. Exiba o log de execução retornado.
- Liste as funções para sua conta e limpe os recursos.

Para obter mais informações, consulte Criar uma função do Lambda no console.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        "Create an AWS Identity and Access Management (IAM) role that grants AWS
 Lambda permission to write to logs."
        DATA(lv_policy_document) = `{` &&
            `"Version":"2012-10-17",` &&
                  `"Statement": [` &&
                    `{` &&
                      `"Effect": "Allow",` &&
                      `"Action": [` &&
                        `"sts:AssumeRole"` &&
                      `],` &&
                      `"Principal": {` &&
                        `"Service": [` &&
                          `"lambda.amazonaws.com"` &&
                        `]` &&
                      `}` &&
                    `}` &&
                  `]` &&
                `}`.
        TRY.
            DATA(lo_create_role_output) =  lo_iam->createrole(
                    iv_rolename = iv_role_name
                    iv_assumerolepolicydocument = lv_policy_document
                    iv_description = 'Grant lambda permission to write to logs'
                ).
            MESSAGE 'IAM role created.' TYPE 'I'.
            WAIT UP TO 10 SECONDS.            " Make sure that the IAM role is ready
 for use. "
          CATCH /aws1/cx_iamentityalrdyexex.
            MESSAGE 'IAM role already exists.' TYPE 'E'.
          CATCH /aws1/cx_iaminvalidinputex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iammalformedplydocex.
            MESSAGE 'Policy document in the request is malformed.' TYPE 'E'.
        ENDTRY.

        TRY.
            lo_iam->attachrolepolicy(
                iv_rolename  = iv_role_name
                iv_policyarn = 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole'
            ).
            MESSAGE 'Attached policy to the IAM role.' TYPE 'I'.
          CATCH /aws1/cx_iaminvalidinputex.
```

```
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamplynotattachableex.
            MESSAGE 'Service role policies can only be attached to the service-
linked role for their service.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
 modifiable.' TYPE 'E'.
        ENDTRY.

        " Create a Lambda function and upload handler code. "
        " Lambda function performs 'increment' action on a number. "
        TRY.
            lo_lmd->createfunction(
                 iv_functionname = iv_function_name
                 iv_runtime = `python3.9`
                 iv_role = lo_create_role_output->get_role( )->get_arn( )
                 iv_handler = iv_handler
                 io_code = io_initial_zip_file
                 iv_description = 'AWS Lambda code example'
             ).
            MESSAGE 'Lambda function created.' TYPE 'I'.
          CATCH /aws1/cx_lmdcodestorageexcdex.
            MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        " Verify the function is in Active state "
        WHILE lo_lmd->getfunction( iv_functionname = iv_function_name )-
>get_configuration( )->ask_state( ) <> 'Active'.
          IF sy-index = 10.
            EXIT.               " Maximum 10 seconds. "
          ENDIF.
          WAIT UP TO 1 SECONDS.
        ENDWHILE.

        "Invoke the function with a single parameter and get results."
        TRY.
            DATA(lv_json) = /aws1/cl_rt_util=>string_to_xstring(
              `{`  &&
```

```
                `"action": "increment",`  &&
                `"number": 10` &&
              `}`
            ).
            DATA(lo_initial_invoke_output) =  lo_lmd->invoke(
                       iv_functionname = iv_function_name
                       iv_payload = lv_json
                   ).
            ov_initial_invoke_payload = lo_initial_invoke_output->get_payload( ).
        " ov_initial_invoke_payload is returned for testing purposes. "
            DATA(lo_writer_json) = cl_sxml_string_writer=>create( type =
 if_sxml=>co_xt_json ).
            CALL TRANSFORMATION id SOURCE XML ov_initial_invoke_payload RESULT XML
 lo_writer_json.
            DATA(lv_result) = cl_abap_codepage=>convert_from( lo_writer_json-
>get_output( ) ).
            MESSAGE 'Lambda function invoked.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvrequestcontex.
            MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
          CATCH /aws1/cx_lmdunsuppedmediatyp00.
            MESSAGE 'Invoke request body does not have JSON as its content type.'
 TYPE 'E'.
        ENDTRY.

        " Update the function code and configure its Lambda environment with an
 environment variable. "
        " Lambda function is updated to perform 'decrement' action also. "
        TRY.
            lo_lmd->updatefunctioncode(
                  iv_functionname = iv_function_name
                  iv_zipfile = io_updated_zip_file
              ).
            WAIT UP TO 10 SECONDS.            " Make sure that the update is
 completed. "
            MESSAGE 'Lambda function code updated.' TYPE 'I'.
          CATCH /aws1/cx_lmdcodestorageexcdex.
            MESSAGE 'Maximum total code size per account exceeded.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
```

```
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        TRY.
            DATA lt_variables TYPE /aws1/
cl_lmdenvironmentvaria00=>tt_environmentvariables.
            DATA ls_variable LIKE LINE OF lt_variables.
            ls_variable-key = 'LOG_LEVEL'.
            ls_variable-value = NEW /aws1/cl_lmdenvironmentvaria00( iv_value =
 'info' ).
            INSERT ls_variable INTO TABLE lt_variables.

            lo_lmd->updatefunctionconfiguration(
                  iv_functionname = iv_function_name
                  io_environment = NEW /aws1/cl_lmdenvironment( it_variables =
 lt_variables )
              ).
            WAIT UP TO 10 SECONDS.            " Make sure that the update is
 completed. "
            MESSAGE 'Lambda function configuration/settings updated.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourceconflictex.
            MESSAGE 'Resource already exists or another operation is in progress.'
 TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        "Invoke the function with new parameters and get results. Display the
 execution log that's returned from the invocation."
        TRY.
            lv_json = /aws1/cl_rt_util=>string_to_xstring(
              `{`  &&
                `"action": "decrement",`  &&
                `"number": 10` &&
              `}`
            ).
            DATA(lo_updated_invoke_output) =  lo_lmd->invoke(
                       iv_functionname = iv_function_name
                       iv_payload = lv_json
                  ).
            ov_updated_invoke_payload = lo_updated_invoke_output->get_payload( ).
        " ov_updated_invoke_payload is returned for testing purposes. "
```

```
            lo_writer_json = cl_sxml_string_writer=>create( type =
 if_sxml=>co_xt_json ).
            CALL TRANSFORMATION id SOURCE XML ov_updated_invoke_payload RESULT XML
 lo_writer_json.
            lv_result = cl_abap_codepage=>convert_from( lo_writer_json-
>get_output( ) ).
            MESSAGE 'Lambda function invoked.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdinvrequestcontex.
            MESSAGE 'Unable to parse request body as JSON.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
          CATCH /aws1/cx_lmdunsuppedmediatyp00.
            MESSAGE 'Invoke request body does not have JSON as its content type.'
 TYPE 'E'.
        ENDTRY.

        " List the functions for your account. "
        TRY.
            DATA(lo_list_output) = lo_lmd->listfunctions( ).
            DATA(lt_functions) = lo_list_output->get_functions( ).
            MESSAGE 'Retrieved list of Lambda functions.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
        ENDTRY.

        " Delete the Lambda function. "
        TRY.
            lo_lmd->deletefunction( iv_functionname = iv_function_name ).
            MESSAGE 'Lambda function deleted.' TYPE 'I'.
          CATCH /aws1/cx_lmdinvparamvalueex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_lmdresourcenotfoundex.
            MESSAGE 'The requested resource does not exist.' TYPE 'E'.
        ENDTRY.

        " Detach role policy. "
        TRY.
            lo_iam->detachrolepolicy(
                iv_rolename  = iv_role_name
                iv_policyarn = 'arn:aws:iam::aws:policy/service-role/
AWSLambdaBasicExecutionRole'
            ).
```

```
            MESSAGE 'Detached policy from the IAM role.' TYPE 'I'.
          CATCH /aws1/cx_iaminvalidinputex.
            MESSAGE 'The request contains a non-valid parameter.' TYPE 'E'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamplynotattachableex.
            MESSAGE 'Service role policies can only be attached to the service-
linked role for their service.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
 modifiable.' TYPE 'E'.
        ENDTRY.

        " Delete the IAM role. "
        TRY.
            lo_iam->deleterole( iv_rolename = iv_role_name ).
            MESSAGE 'IAM role deleted.' TYPE 'I'.
          CATCH /aws1/cx_iamnosuchentityex.
            MESSAGE 'The requested resource entity does not exist.' TYPE 'E'.
          CATCH /aws1/cx_iamunmodableentityex.
            MESSAGE 'Service that depends on the service-linked role is not
 modifiable.' TYPE 'E'.
        ENDTRY.

      CATCH /aws1/cx_rt_service_generic INTO lo_exception.
        DATA(lv_error) = lo_exception->get_longtext( ).
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Exemplos do Amazon S3 usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_s3->copyobject(
      iv_bucket = iv_dest_bucket
      iv_key = iv_dest_object
      iv_copysource = |{ iv_src_bucket }/{ iv_src_object }|
    ).
```

```
      MESSAGE 'Object copied to another bucket.' TYPE 'I'.
    CATCH /aws1/cx_s3_nosuchbucket.
      MESSAGE 'Bucket does not exist.' TYPE 'E'.
    CATCH /aws1/cx_s3_nosuchkey.
      MESSAGE 'Object key does not exist.' TYPE 'E'.
  ENDTRY.
```

- Para obter detalhes da API, consulte a CopyObjectreferência da API AWS SDK for SAP ABAP.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
  TRY.
      lo_s3->createbucket(
          iv_bucket = iv_bucket_name
      ).
      MESSAGE 'S3 bucket created.' TYPE 'I'.
    CATCH /aws1/cx_s3_bucketalrdyexists.
      MESSAGE 'Bucket name already exists.' TYPE 'E'.
    CATCH /aws1/cx_s3_bktalrdyownedbyyou.
      MESSAGE 'Bucket already exists and is owned by you.' TYPE 'E'.
  ENDTRY.
```

- Para obter detalhes da API, consulte a CreateBucketreferência da API AWS SDK for SAP ABAP.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.

    lo_s3->deletebucket(
        iv_bucket = iv_bucket_name
    ).
    MESSAGE 'Deleted S3 bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteBucketreferência da API AWS SDK for SAP ABAP.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_s3->deleteobject(
        iv_bucket = iv_bucket_name
        iv_key = iv_object_key
    ).
    MESSAGE 'Object deleted from S3 bucket.' TYPE 'I'.
```

```
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteObjectreferência da API AWS SDK for SAP ABAP.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_s3->getobject(           " oo_result is returned for testing
purposes. "
                  iv_bucket = iv_bucket_name
                  iv_key = iv_object_key
                ).
        DATA(lv_object_data) = oo_result->get_body( ).
        MESSAGE 'Object retrieved from S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
      CATCH /aws1/cx_s3_nosuchkey.
        MESSAGE 'Object key does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetObjectreferência da API AWS SDK for SAP ABAP.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_s3->listobjectsv2(         " oo_result is returned for
testing purposes. "
         iv_bucket = iv_bucket_name
       ).
       MESSAGE 'Retrieved list of objects in S3 bucket.' TYPE 'I'.
     CATCH /aws1/cx_s3_nosuchbucket.
       MESSAGE 'Bucket does not exist.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API ABAP do AWS SDK para SAP.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Get contents of file from application server."
   DATA lv_body TYPE xstring.
   OPEN DATASET iv_file_name FOR INPUT IN BINARY MODE.
   READ DATASET iv_file_name INTO lv_body.
   CLOSE DATASET iv_file_name.
```

```
"Upload/put an object to an S3 bucket."
TRY.
    lo_s3->putobject(
        iv_bucket = iv_bucket_name
        iv_key = iv_file_name
        iv_body = lv_body
    ).
    MESSAGE 'Object uploaded to S3 bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a PutObjectreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
DATA(lo_session) = /aws1/cl_rt_session_aws=>create( cv_pfl ).
DATA(lo_s3) = /aws1/cl_s3_factory=>create( lo_session ).
```

```
" Create an Amazon Simple Storage Service (Amazon S3) bucket. "
TRY.
    lo_s3->createbucket(
        iv_bucket = iv_bucket_name
    ).
    MESSAGE 'S3 bucket created.' TYPE 'I'.
  CATCH /aws1/cx_s3_bucketalrdyexists.
    MESSAGE 'Bucket name already exists.' TYPE 'E'.
  CATCH /aws1/cx_s3_bktalrdyownedbyyou.
    MESSAGE 'Bucket already exists and is owned by you.' TYPE 'E'.
ENDTRY.


"Upload an object to an S3 bucket."
TRY.
    "Get contents of file from application server."
    DATA lv_file_content TYPE xstring.
    OPEN DATASET iv_key FOR INPUT IN BINARY MODE.
    READ DATASET iv_key INTO lv_file_content.
    CLOSE DATASET iv_key.

    lo_s3->putobject(
        iv_bucket = iv_bucket_name
        iv_key = iv_key
        iv_body = lv_file_content
    ).
    MESSAGE 'Object uploaded to S3 bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
ENDTRY.

" Get an object from a bucket. "
TRY.
    DATA(lo_result) = lo_s3->getobject(
               iv_bucket = iv_bucket_name
               iv_key = iv_key
            ).
    DATA(lv_object_data) = lo_result->get_body( ).
    MESSAGE 'Object retrieved from S3 bucket.' TYPE 'I'.
  CATCH /aws1/cx_s3_nosuchbucket.
    MESSAGE 'Bucket does not exist.' TYPE 'E'.
  CATCH /aws1/cx_s3_nosuchkey.
    MESSAGE 'Object key does not exist.' TYPE 'E'.
```

```
    ENDTRY.

    " Copy an object to a subfolder in a bucket. "
    TRY.
        lo_s3->copyobject(
          iv_bucket = iv_bucket_name
          iv_key = |{ iv_copy_to_folder }/{ iv_key }|
          iv_copysource = |{ iv_bucket_name }/{ iv_key }|
        ).
        MESSAGE 'Object copied to a subfolder.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
      CATCH /aws1/cx_s3_nosuchkey.
        MESSAGE 'Object key does not exist.' TYPE 'E'.
    ENDTRY.

    " List objects in the bucket. "
    TRY.
        DATA(lo_list) = lo_s3->listobjects(
           iv_bucket = iv_bucket_name
         ).
        MESSAGE 'Retrieved list of objects in S3 bucket.' TYPE 'I'.
      CATCH /aws1/cx_s3_nosuchbucket.
        MESSAGE 'Bucket does not exist.' TYPE 'E'.
    ENDTRY.
    DATA text TYPE string VALUE 'Object List - '.
    DATA lv_object_key TYPE /aws1/s3_objectkey.
    LOOP AT lo_list->get_contents( ) INTO DATA(lo_object).
      lv_object_key = lo_object->get_key( ).
      CONCATENATE lv_object_key ', ' INTO text.
    ENDLOOP.
    MESSAGE text TYPE'I'.

    " Delete the objects in a bucket. "
    TRY.
        lo_s3->deleteobject(
            iv_bucket = iv_bucket_name
            iv_key = iv_key
        ).
        lo_s3->deleteobject(
            iv_bucket = iv_bucket_name
            iv_key = |{ iv_copy_to_folder }/{ iv_key }|
        ).
        MESSAGE 'Objects deleted from S3 bucket.' TYPE 'I'.
```

```
    CATCH /aws1/cx_s3_nosuchbucket.
      MESSAGE 'Bucket does not exist.' TYPE 'E'.
  ENDTRY.


  " Delete the bucket. "
  TRY.
      lo_s3->deletebucket(
          iv_bucket = iv_bucket_name
      ).
      MESSAGE 'Deleted S3 bucket.' TYPE 'I'.
    CATCH /aws1/cx_s3_nosuchbucket.
      MESSAGE 'Bucket does not exist.' TYPE 'E'.
  ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

SageMaker exemplos usando o SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com. SageMaker

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um modelo

O exemplo de código a seguir mostra como criar um modelo em SageMaker.

SDK para SAP ABAP

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   DATA lo_primarycontainer TYPE REF TO /aws1/cl_sgmcontainerdefn.

   "Create an ABAP object for the container image based on input variables."
   CREATE OBJECT lo_primarycontainer
     EXPORTING
       iv_image        = iv_container_image
       iv_modeldataurl = iv_model_data_url.

   "Create an Amazon SageMaker model."
   TRY.
       oo_result = lo_sgm->createmodel(        " oo_result is returned for testing
purposes. "
         iv_executionrolearn = iv_execution_role_arn
         iv_modelname = iv_model_name
         io_primarycontainer = lo_primarycontainer
       ).
       MESSAGE 'Model created.' TYPE 'I'.
     CATCH /aws1/cx_sgmresourcelimitexcd.
       MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
```

```
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateModelreferência da API AWS SDK for SAP ABAP.

Criar um endpoint

O exemplo de código a seguir mostra como criar um SageMaker endpoint.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lt_production_variants TYPE /aws1/
cl_sgmproductionvariant=>tt_productionvariantlist.
    DATA lo_production_variants TYPE REF TO /aws1/cl_sgmproductionvariant.
    DATA oo_ep_config_result TYPE REF TO /aws1/cl_sgmcreateendptcfgout.

    "Create a production variant as an ABAP object."
    "Identifies a model that you want to host and the resources chosen to deploy for
 hosting it."
    CREATE OBJECT lo_production_variants
      EXPORTING
        iv_variantname          = iv_variant_name
        iv_modelname            = iv_model_name
        iv_initialinstancecount = iv_initial_instance_count
        iv_instancetype         = iv_instance_type.

    INSERT lo_production_variants INTO TABLE lt_production_variants.

    "Create an endpoint configuration."
    TRY.
        oo_ep_config_result = lo_sgm->createendpointconfig(
          iv_endpointconfigname = iv_endpoint_config_name
          it_productionvariants = lt_production_variants
```

```
        ).
        MESSAGE 'Endpoint configuration created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.

    "Create an endpoint."
    TRY.
        oo_result = lo_sgm->createendpoint(     " oo_result is returned for testing
purposes. "
            iv_endpointconfigname = iv_endpoint_config_name
            iv_endpointname = iv_endpoint_name
        ).
        MESSAGE 'Endpoint created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateEndpoint
  - CreateEndpointConfig

Excluir um modelo

O exemplo de código a seguir mostra como excluir um modelo em SageMaker.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sgm->deletemodel(
                  iv_modelname = iv_model_name
```

```
                ).
        MESSAGE 'Model deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteModelreferência da API AWS SDK for SAP ABAP.

Excluir um endpoint

O exemplo de código a seguir mostra como excluir um SageMaker endpoint.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Delete an endpoint."
    TRY.
        lo_sgm->deleteendpoint(
            iv_endpointname = iv_endpoint_name
        ).
        MESSAGE 'Endpoint configuration deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpoint_exception).
        DATA(lv_endpoint_error) = |"{ lo_endpoint_exception->av_err_code }" -
 { lo_endpoint_exception->av_err_msg }|.
        MESSAGE lv_endpoint_error TYPE 'E'.
    ENDTRY.

    "Delete an endpoint configuration."
    TRY.
        lo_sgm->deleteendpointconfig(
          iv_endpointconfigname = iv_endpoint_config_name
        ).
```

```
        MESSAGE 'Endpoint deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpointconfig_exception).
        DATA(lv_endpointconfig_error) = |"{ lo_endpointconfig_exception-
>av_err_code }" - { lo_endpointconfig_exception->av_err_msg }|.
        MESSAGE lv_endpointconfig_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DeleteEndpoint
  - DeleteEndpointConfig

Descrever um trabalho de treinamento

O exemplo de código a seguir mostra como descrever um trabalho SageMaker de treinamento.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->describetrainingjob(      " oo_result is returned for
 testing purposes. "
          iv_trainingjobname = iv_training_job_name
        ).
        MESSAGE 'Retrieved description of training job.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTrainingJobreferência da API AWS SDK for SAP ABAP.

Listar modelos

O exemplo de código a seguir mostra como listar modelos em SageMaker.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listmodels(           " oo_result is returned for
 testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of models.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListModelsreferência da API AWS SDK for SAP ABAP.

Listar instâncias de bloco de anotações

O exemplo de código a seguir mostra como listar instâncias do SageMaker notebook.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
```

```
        oo_result = lo_sgm->listnotebookinstances(        " oo_result is returned
 for testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of notebook instances.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListNotebookInstancesreferência da API AWS SDK for SAP ABAP.

Listar os algoritmos de machine learning

O exemplo de código a seguir mostra como listar algoritmos SageMaker de aprendizado de máquina.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listalgorithms(         " oo_result is returned for
 testing purposes. "
          iv_namecontains = iv_name_contains
        ).
        MESSAGE 'Retrieved list of algorithms.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListAlgorithmsreferência da API AWS SDK for SAP ABAP.

Listar os trabalhos de treinamento.

O exemplo de código a seguir mostra como listar trabalhos SageMaker de treinamento.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sgm->listtrainingjobs(       " oo_result is returned for
 testing purposes. "
          iv_namecontains = iv_name_contains
          iv_maxresults = iv_max_results
        ).
        MESSAGE 'Retrieved list of training jobs.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_exception).
        DATA(lv_error) = |"{ lo_exception->av_err_code }" - { lo_exception-
>av_err_msg }|.
        MESSAGE lv_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTrainingJobsreferência da API AWS SDK for SAP ABAP.

Inicie um trabalho de treinamento

O exemplo de código a seguir mostra como iniciar um trabalho SageMaker de treinamento.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   DATA lo_hyperparameters_w TYPE REF TO /aws1/cl_sgmhyperparameters_w.
   DATA lt_hyperparameters TYPE /aws1/cl_sgmhyperparameters_w=>tt_hyperparameters.
   DATA lt_input_data_config TYPE /aws1/cl_sgmchannel=>tt_inputdataconfig.
   DATA lo_trn_channel TYPE REF TO /aws1/cl_sgmchannel.
   DATA lo_trn_datasource TYPE REF TO /aws1/cl_sgmdatasource.
   DATA lo_trn_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
   DATA lo_val_channel TYPE REF TO /aws1/cl_sgmchannel.
   DATA lo_val_datasource TYPE REF TO /aws1/cl_sgmdatasource.
   DATA lo_val_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
   DATA lo_algorithm_specification TYPE REF TO /aws1/cl_sgmalgorithmspec.
   DATA lo_resource_config  TYPE REF TO /aws1/cl_sgmresourceconfig.
   DATA lo_output_data_config TYPE REF TO  /aws1/cl_sgmoutputdataconfig.
   DATA lo_stopping_condition TYPE REF TO  /aws1/cl_sgmstoppingcondition.

   "Create ABAP internal table for hyperparameters based on input variables."
   "These hyperparameters are based on the Amazon SageMaker built-in algorithm,
XGBoost."
   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_max_depth.
   INSERT VALUE #( key = 'max_depth' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eta.
   INSERT VALUE #( key = 'eta' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eval_metric.
   INSERT VALUE #( key = 'eval_metric' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_scale_pos_weight.
   INSERT VALUE #( key = 'scale_pos_weight' value = lo_hyperparameters_w )  INTO
TABLE lt_hyperparameters.
```

```
   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_subsample.
   INSERT VALUE #( key = 'subsample' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_objective.
   INSERT VALUE #( key = 'objective' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_num_round.
   INSERT VALUE #( key = 'num_round' value = lo_hyperparameters_w )  INTO TABLE
lt_hyperparameters.

   "Create ABAP objects for training data sources."
   CREATE OBJECT lo_trn_s3datasource
     EXPORTING
       iv_s3datatype             = iv_trn_data_s3datatype
       iv_s3datadistributiontype = iv_trn_data_s3datadistribution
       iv_s3uri                  = iv_trn_data_s3uri.

   CREATE OBJECT lo_trn_datasource
     EXPORTING
       io_s3datasource = lo_trn_s3datasource.

   CREATE OBJECT lo_trn_channel
     EXPORTING
       iv_channelname     = 'train'
       io_datasource      = lo_trn_datasource
       iv_compressiontype = iv_trn_data_compressiontype
       iv_contenttype     = iv_trn_data_contenttype.

   INSERT lo_trn_channel INTO TABLE lt_input_data_config.

   "Create ABAP objects for validation data sources."
   CREATE OBJECT lo_val_s3datasource
     EXPORTING
       iv_s3datatype             = iv_val_data_s3datatype
       iv_s3datadistributiontype = iv_val_data_s3datadistribution
       iv_s3uri                  = iv_val_data_s3uri.

   CREATE OBJECT lo_val_datasource
     EXPORTING
       io_s3datasource = lo_val_s3datasource.

   CREATE OBJECT lo_val_channel
```

```
      EXPORTING
        iv_channelname     = 'validation'
        io_datasource      = lo_val_datasource
        iv_compressiontype = iv_val_data_compressiontype
        iv_contenttype     = iv_val_data_contenttype.

    INSERT lo_val_channel INTO TABLE lt_input_data_config.

    "Create an ABAP object for algorithm specification."
    CREATE OBJECT lo_algorithm_specification
      EXPORTING
        iv_trainingimage     = iv_training_image
        iv_traininginputmode = iv_training_input_mode.

    "Create an ABAP object for resource configuration."
    CREATE OBJECT lo_resource_config
      EXPORTING
        iv_instancecount  = iv_instance_count
        iv_instancetype   = iv_instance_type
        iv_volumesizeingb = iv_volume_sizeingb.

    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_output_data_config
      EXPORTING
        iv_s3outputpath = iv_s3_output_path.

    "Create an ABAP object for stopping condition."
    CREATE OBJECT lo_stopping_condition
      EXPORTING
        iv_maxruntimeinseconds = iv_max_runtime_in_seconds.

    "Create a training job."
    TRY.
        oo_result = lo_sgm->createtrainingjob(    " oo_result is returned for
testing purposes. "
          iv_trainingjobname           = iv_training_job_name
          iv_rolearn                   = iv_role_arn
          it_hyperparameters           = lt_hyperparameters
          it_inputdataconfig           = lt_input_data_config
          io_algorithmspecification    = lo_algorithm_specification
          io_outputdataconfig          = lo_output_data_config
          io_resourceconfig            = lo_resource_config
          io_stoppingcondition         = lo_stopping_condition
        ).
```

```
        MESSAGE 'Training job created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTrainingJobreferência da API AWS SDK for SAP ABAP.

Iniciar um trabalho de transformação.

O exemplo de código a seguir mostra como iniciar um trabalho de SageMaker transformação.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_transforminput TYPE REF TO /aws1/cl_sgmtransforminput.
    DATA lo_transformoutput TYPE REF TO /aws1/cl_sgmtransformoutput.
    DATA lo_transformresources TYPE REF TO /aws1/cl_sgmtransformresources.
    DATA lo_datasource  TYPE REF TO /aws1/cl_sgmtransformdatasrc.
    DATA lo_s3datasource  TYPE REF TO /aws1/cl_sgmtransforms3datasrc.

    "Create an ABAP object for an Amazon Simple Storage Service (Amazon S3) data
source."
    CREATE OBJECT lo_s3datasource
      EXPORTING
        iv_s3uri      = iv_tf_data_s3uri
        iv_s3datatype = iv_tf_data_s3datatype.

    "Create an ABAP object for data source."
    CREATE OBJECT lo_datasource
```

```
      EXPORTING
        io_s3datasource = lo_s3datasource.

    "Create an ABAP object for transform data source."
    CREATE OBJECT lo_transforminput
      EXPORTING
        io_datasource      = lo_datasource
        iv_contenttype     = iv_tf_data_contenttype
        iv_compressiontype = iv_tf_data_compressiontype.

    "Create an ABAP object for resource configuration."
    CREATE OBJECT lo_transformresources
      EXPORTING
        iv_instancecount = iv_instance_count
        iv_instancetype  = iv_instance_type.

    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_transformoutput
      EXPORTING
        iv_s3outputpath = iv_s3_output_path.

    "Create a transform job."
    TRY.
        oo_result = lo_sgm->createtransformjob(     " oo_result is returned for
testing purposes. "
            iv_modelname = iv_tf_model_name
            iv_transformjobname = iv_tf_job_name
            io_transforminput = lo_transforminput
            io_transformoutput = lo_transformoutput
            io_transformresources = lo_transformresources
        ).
        MESSAGE 'Transform job created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourceinuse.
        MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcenotfound.
        MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTransformJobreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos com modelos e endpoints

O código de exemplo a seguir mostra como:

- Comece um trabalho de treinamento e crie um SageMaker modelo.
- Criar uma configuração de endpoint
- Criar um endpoint e, em seguida, limpe os recursos.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_hyperparameters_w TYPE REF TO /aws1/cl_sgmhyperparameters_w.
    DATA lo_trn_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_trn_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_trn_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
    DATA lo_val_channel TYPE REF TO /aws1/cl_sgmchannel.
    DATA lo_val_datasource TYPE REF TO /aws1/cl_sgmdatasource.
    DATA lo_val_s3datasource TYPE REF TO /aws1/cl_sgms3datasource.
    DATA lo_algorithm_specification TYPE REF TO /aws1/cl_sgmalgorithmspec.
    DATA lo_resource_config  TYPE REF TO /aws1/cl_sgmresourceconfig.
    DATA lo_output_data_config TYPE REF TO  /aws1/cl_sgmoutputdataconfig.
    DATA lo_stopping_condition TYPE REF TO  /aws1/cl_sgmstoppingcondition.
    DATA lo_primarycontainer TYPE REF TO /aws1/cl_sgmcontainerdefn.
    DATA lo_production_variants TYPE REF TO /aws1/cl_sgmproductionvariant.
    DATA lo_ep_config_result TYPE REF TO /aws1/cl_sgmcreateendptcfgout.
    DATA lo_training_result TYPE REF TO /aws1/cl_sgmdescrtrnjobrsp.
    DATA lt_production_variants TYPE /aws1/
cl_sgmproductionvariant=>tt_productionvariantlist.
    DATA lt_input_data_config TYPE /aws1/cl_sgmchannel=>tt_inputdataconfig.
    DATA lt_hyperparameters TYPE /aws1/cl_sgmhyperparameters_w=>tt_hyperparameters.
    DATA lv_model_data_url TYPE /aws1/sgmurl.
```

```
    lv_model_data_url = iv_s3_output_path && iv_training_job_name && '/output/
model.tar.gz'.

    "Create ABAP internal table for hyperparameters based on input variables."
    "These hyperparameters are based on Amazon SageMaker built-in algorithm -
 XGBoost"
    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_max_depth.
    INSERT VALUE #( key = 'max_depth' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eta.
    INSERT VALUE #( key = 'eta' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_eval_metric.
    INSERT VALUE #( key = 'eval_metric' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_scale_pos_weight.
    INSERT VALUE #( key = 'scale_pos_weight' value = lo_hyperparameters_w )  INTO
 TABLE lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_subsample.
    INSERT VALUE #( key = 'subsample' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_objective.
    INSERT VALUE #( key = 'objective' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    CREATE OBJECT lo_hyperparameters_w EXPORTING iv_value = iv_hp_num_round.
    INSERT VALUE #( key = 'num_round' value = lo_hyperparameters_w )  INTO TABLE
 lt_hyperparameters.

    "Create ABAP internal table for data based on input variables."
    "Training data."
    CREATE OBJECT lo_trn_s3datasource
      EXPORTING
        iv_s3datatype             = iv_trn_data_s3datatype
        iv_s3datadistributiontype = iv_trn_data_s3datadistribution
        iv_s3uri                  = iv_trn_data_s3uri.

    CREATE OBJECT lo_trn_datasource EXPORTING io_s3datasource = lo_trn_s3datasource.
```

```
    CREATE OBJECT lo_trn_channel
      EXPORTING
        iv_channelname     = 'train'
        io_datasource      = lo_trn_datasource
        iv_compressiontype = iv_trn_data_compressiontype
        iv_contenttype     = iv_trn_data_contenttype.
    INSERT lo_trn_channel INTO TABLE lt_input_data_config.

    "Validation data."
    CREATE OBJECT lo_val_s3datasource
      EXPORTING
        iv_s3datatype             = iv_val_data_s3datatype
        iv_s3datadistributiontype = iv_val_data_s3datadistribution
        iv_s3uri                  = iv_val_data_s3uri.

    CREATE OBJECT lo_val_datasource EXPORTING io_s3datasource = lo_val_s3datasource.

    CREATE OBJECT lo_val_channel
      EXPORTING
        iv_channelname     = 'validation'
        io_datasource      = lo_val_datasource
        iv_compressiontype = iv_val_data_compressiontype
        iv_contenttype     = iv_val_data_contenttype.
    INSERT lo_val_channel INTO TABLE lt_input_data_config.

    "Create an ABAP object for algorithm specification based on input variables."
    CREATE OBJECT lo_algorithm_specification
      EXPORTING
        iv_trainingimage     = iv_training_image
        iv_traininginputmode = iv_training_input_mode.

    "Create an ABAP object for resource configuration."
    CREATE OBJECT lo_resource_config
      EXPORTING
        iv_instancecount  = iv_instance_count
        iv_instancetype   = iv_instance_type
        iv_volumesizeingb = iv_volume_sizeingb.

    "Create an ABAP object for output data configuration."
    CREATE OBJECT lo_output_data_config EXPORTING iv_s3outputpath =
iv_s3_output_path.

    "Create an ABAP object for stopping condition."
```

```
   CREATE OBJECT lo_stopping_condition EXPORTING iv_maxruntimeinseconds =
iv_max_runtime_in_seconds.

   TRY.
       lo_sgm->createtrainingjob(
         iv_trainingjobname           = iv_training_job_name
         iv_rolearn                   = iv_role_arn
         it_hyperparameters           = lt_hyperparameters
         it_inputdataconfig           = lt_input_data_config
         io_algorithmspecification    = lo_algorithm_specification
         io_outputdataconfig          = lo_output_data_config
         io_resourceconfig            = lo_resource_config
         io_stoppingcondition         = lo_stopping_condition
       ).
       MESSAGE 'Training job created.' TYPE 'I'.
     CATCH /aws1/cx_sgmresourceinuse.
       MESSAGE 'Resource being accessed is in use.' TYPE 'E'.
     CATCH /aws1/cx_sgmresourcenotfound.
       MESSAGE 'Resource being accessed is not found.' TYPE 'E'.
     CATCH /aws1/cx_sgmresourcelimitexcd.
       MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
   ENDTRY.

   "Wait for training job to be completed."
   lo_training_result = lo_sgm->describetrainingjob( iv_trainingjobname =
iv_training_job_name ).
   WHILE lo_training_result->get_trainingjobstatus( ) <> 'Completed'.
     IF sy-index = 30.
       EXIT.               "Maximum 900 seconds."
     ENDIF.
     WAIT UP TO 30 SECONDS.
     lo_training_result = lo_sgm->describetrainingjob( iv_trainingjobname =
iv_training_job_name ).
   ENDWHILE.

   "Create ABAP object for the container image based on input variables."
   CREATE OBJECT lo_primarycontainer
     EXPORTING
       iv_image        = iv_training_image
       iv_modeldataurl = lv_model_data_url.

   "Create an Amazon SageMaker model."
   TRY.
       lo_sgm->createmodel(
```

```
          iv_executionrolearn = iv_role_arn
          iv_modelname = iv_model_name
          io_primarycontainer = lo_primarycontainer
        ).
        MESSAGE 'Model created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.

    "Create an endpoint production variant."
    CREATE OBJECT lo_production_variants
      EXPORTING
        iv_variantname          = iv_ep_variant_name
        iv_modelname            = iv_model_name
        iv_initialinstancecount = iv_ep_initial_instance_count
        iv_instancetype         = iv_ep_instance_type.
    INSERT lo_production_variants INTO TABLE lt_production_variants.

    TRY.
        "Create an endpoint configuration."
        lo_ep_config_result = lo_sgm->createendpointconfig(
          iv_endpointconfigname = iv_ep_cfg_name
          it_productionvariants = lt_production_variants
        ).
        MESSAGE 'Endpoint configuration created.' TYPE 'I'.

        "Create an endpoint."
        oo_ep_output = lo_sgm->createendpoint(        " oo_ep_output is returned for
testing purposes. "
            iv_endpointconfigname = iv_ep_cfg_name
            iv_endpointname = iv_ep_name
        ).
        MESSAGE 'Endpoint created.' TYPE 'I'.
      CATCH /aws1/cx_sgmresourcelimitexcd.
        MESSAGE 'You have reached the limit on the number of resources.' TYPE 'E'.
    ENDTRY.

    "Wait for endpoint creation to be completed."
    DATA(lo_endpoint_result) = lo_sgm->describeendpoint( iv_endpointname =
iv_ep_name ).
    WHILE lo_endpoint_result->get_endpointstatus( ) <> 'InService'.
      IF sy-index = 30.
        EXIT.               "Maximum 900 seconds."
      ENDIF.
```

```
      WAIT UP TO 30 SECONDS.
      lo_endpoint_result = lo_sgm->describeendpoint( iv_endpointname = iv_ep_name ).
    ENDWHILE.

    TRY.
        "Delete an endpoint."
        lo_sgm->deleteendpoint(
            iv_endpointname = iv_ep_name
        ).
        MESSAGE 'Endpoint deleted' TYPE 'I'.

        "Delete an endpoint configuration."
        lo_sgm->deleteendpointconfig(
          iv_endpointconfigname = iv_ep_cfg_name
        ).
        MESSAGE 'Endpoint configuration deleted.' TYPE 'I'.

        "Delete model."
        lo_sgm->deletemodel(
                  iv_modelname = iv_model_name
                ).
        MESSAGE 'Model deleted.' TYPE 'I'.
      CATCH /aws1/cx_rt_service_generic INTO DATA(lo_endpointconfig_exception).
        DATA(lv_endpointconfig_error) = |"{ lo_endpointconfig_exception-
>av_err_code }" - { lo_endpointconfig_exception->av_err_msg }|.
        MESSAGE lv_endpointconfig_error TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateEndpoint
  - CreateEndpointConfig
  - CreateModel
  - CreateTrainingJob
  - DeleteEndpoint
  - DeleteEndpointConfig
  - DeleteModel
  - DescribeEndpoint

- DescribeTrainingJob

Exemplos do Amazon SNS usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Amazon SNS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar um tópico

O exemplo de código a seguir mostra como criar um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->createtopic( iv_name = iv_topic_name ). " oo_result is
returned for testing purposes. "
```

```
        MESSAGE 'SNS topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
        MESSAGE 'Unable to create more topics. You have reached the maximum number
 of topics allowed.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateTopicreferência da API AWS SDK for SAP ABAP.

Excluir uma assinatura

O exemplo de códigos a seguir mostra como excluir uma assinatura do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sns->unsubscribe( iv_subscriptionarn = iv_subscription_arn ).
        MESSAGE 'Subscription deleted.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Subscription does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snsinvalidparameterex.
        MESSAGE 'Subscription with "PendingConfirmation" status cannot be deleted/
unsubscribed. Confirm subscription before performing unsubscribe operation.' TYPE
 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte Cancelar assinatura na Referência da API do AWS SDK para SAP ABAP.

Excluir um tópico

O exemplo de código a seguir mostra como excluir um tópico do Amazon SNS e todas as assinaturas a este tópico.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sns->deletetopic( iv_topicarn = iv_topic_arn ).
        MESSAGE 'SNS topic deleted.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteTopicreferência da API AWS SDK for SAP ABAP.

Obter as propriedades de um tópico

O exemplo de código a seguir mostra como obter as propriedades de um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->gettopicattributes( iv_topicarn = iv_topic_arn ). "
oo_result is returned for testing purposes. "
        DATA(lt_attributes) = oo_result->get_attributes( ).
        MESSAGE 'Retrieved attributes/properties of a topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetTopicAttributesreferência da API AWS SDK for SAP ABAP.

Listar os assinantes de um tópico

O exemplo de código a seguir mostra como recuperar a lista de assinantes de um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_sns->listsubscriptions( ).                " oo_result is
returned for testing purposes. "
       DATA(lt_subscriptions) = oo_result->get_subscriptions( ).
       MESSAGE 'Retrieved list of subscribers.' TYPE 'I'.
     CATCH /aws1/cx_rt_generic.
       MESSAGE 'Unable to list subscribers.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListSubscriptionsreferência da API AWS SDK for SAP ABAP.

Listar tópicos

O exemplo de código a seguir mostra como listar tópicos do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->listtopics( ).            " oo_result is returned for
testing purposes. "
        DATA(lt_topics) = oo_result->get_topics( ).
        MESSAGE 'Retrieved list of topics.' TYPE 'I'.
      CATCH /aws1/cx_rt_generic.
        MESSAGE 'Unable to list topics.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ListTopicsreferência da API AWS SDK for SAP ABAP.

Publicar em um tópico

O exemplo de código a seguir mostra como publicar mensagens em um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sns->publish(              " oo_result is returned for
testing purposes. "
          iv_topicarn = iv_topic_arn
          iv_message = iv_message
        ).
        MESSAGE 'Message published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter os detalhes da API, consulte Publicar na Referência da API do AWS SDK para SAP ABAP.

Definir atributos de tópicos

O exemplo de código a seguir mostra como definir atributos para um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
    lo_sns->settopicattributes(
        iv_topicarn = iv_topic_arn
        iv_attributename  = iv_attribute_name
        iv_attributevalue = iv_attribute_value
    ).
    MESSAGE 'Set/updated SNS topic attributes.' TYPE 'I'.
  CATCH /aws1/cx_snsnotfoundexception.
    MESSAGE 'Topic does not exist.' TYPE 'E'.
ENDTRY.
```

- Para obter detalhes da API, consulte a SetTopicAttributesreferência da API AWS SDK for SAP ABAP.

Inscrever um endereço de e-mail em um tópico

O código a seguir mostra como inscrever um endereço de e-mail em um tópico do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
TRY.
```

```
        oo_result = lo_sns->subscribe(                      "oo_result is returned
 for testing purposes."
                iv_topicarn = iv_topic_arn
                iv_protocol = 'email'
                iv_endpoint = iv_email_address
                iv_returnsubscriptionarn = abap_true
            ).
        MESSAGE 'Email address subscribed to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snssubscriptionlmte00.
        MESSAGE 'Unable to create subscriptions. You have reached the maximum number
 of subscriptions allowed.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte Inscrever-se na Referência da API do AWS SDK para SAP ABAP.

Cenários

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO, inscreva uma fila FIFO do Amazon SQS no tópico e publique uma mensagem em um tópico do Amazon SNS.

```
    " Creates a FIFO topic. "
    DATA lt_tpc_attributes TYPE /aws1/cl_snstopicattrsmap_w=>tt_topicattributesmap.
    DATA ls_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>ts_topicattributesmap_maprow.
    ls_tpc_attributes-key = 'FifoTopic'.
```

```
    ls_tpc_attributes-value = NEW /aws1/cl_snstopicattrsmap_w( iv_value = 'true' ).
    INSERT ls_tpc_attributes INTO TABLE lt_tpc_attributes.

    TRY.
        DATA(lo_create_result) = lo_sns->createtopic(
               iv_name = iv_topic_name
               it_attributes = lt_tpc_attributes
        ).
        DATA(lv_topic_arn) = lo_create_result->get_topicarn( ).
        ov_topic_arn = lv_topic_arn.                                    "
 ov_topic_arn is returned for testing purposes. "
        MESSAGE 'FIFO topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
        MESSAGE 'Unable to create more topics. You have reached the maximum number
 of topics allowed.' TYPE 'E'.
    ENDTRY.

    " Subscribes an endpoint to an Amazon Simple Notification Service (Amazon SNS)
 topic. "
    " Only Amazon Simple Queue Service (Amazon SQS) FIFO queues can be subscribed to
 an SNS FIFO topic. "
    TRY.
        DATA(lo_subscribe_result) = lo_sns->subscribe(
               iv_topicarn = lv_topic_arn
               iv_protocol = 'sqs'
               iv_endpoint = iv_queue_arn
           ).
        DATA(lv_subscription_arn) = lo_subscribe_result->get_subscriptionarn( ).
        ov_subscription_arn = lv_subscription_arn.                      "
 ov_subscription_arn is returned for testing purposes. "
        MESSAGE 'SQS queue was subscribed to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
      CATCH /aws1/cx_snssubscriptionlmte00.
        MESSAGE 'Unable to create subscriptions. You have reached the maximum number
 of subscriptions allowed.' TYPE 'E'.
    ENDTRY.

    " Publish message to SNS topic. "
    TRY.
        DATA lt_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>tt_messageattributemap.
        DATA ls_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>ts_messageattributemap_maprow.
```

```
        ls_msg_attributes-key = 'Importance'.
        ls_msg_attributes-value = NEW /aws1/cl_snsmessageattrvalue( iv_datatype =
'String' iv_stringvalue = 'High' ).
        INSERT ls_msg_attributes INTO TABLE lt_msg_attributes.

        DATA(lo_result) = lo_sns->publish(
             iv_topicarn = lv_topic_arn
             iv_message = 'The price of your mobile plan has been increased from $19
to $23'
             iv_subject = 'Changes to mobile plan'
             iv_messagegroupid = 'Update-2'
             iv_messagededuplicationid = 'Update-2.1'
             it_messageattributes = lt_msg_attributes
      ).
        ov_message_id = lo_result->get_messageid( ).                    "
ov_message_id is returned for testing purposes. "
        MESSAGE 'Message was published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateTopic
  - Publicar
  - Assinar

Exemplos do Amazon SQS usando SDK para SAP ABAP

O exemplo de código a seguir mostra como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Amazon SQS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma fila

O exemplo de código a seguir mostra como criar uma fila do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie uma fila padrão do Amazon SQS.

```
    TRY.
        oo_result = lo_sqs->createqueue( iv_queuename = iv_queue_name ).        "
oo_result is returned for testing purposes. "
        MESSAGE 'SQS queue created.' TYPE 'I'.
      CATCH /aws1/cx_sqsqueuedeldrecently.
        MESSAGE 'After deleting a queue, wait 60 seconds before creating another
queue with the same name.' TYPE 'E'.
      CATCH /aws1/cx_sqsqueuenameexists.
        MESSAGE 'A queue with this name already exists.' TYPE 'E'.
    ENDTRY.
```

Crie uma fila do Amazon SQS que aguarde uma mensagem chegar.

```
    TRY.
        DATA lt_attributes TYPE /aws1/cl_sqsqueueattrmap_w=>tt_queueattributemap.
```

```
        DATA ls_attribute TYPE /aws1/
cl_sqsqueueattrmap_w=>ts_queueattributemap_maprow.
        ls_attribute-key = 'ReceiveMessageWaitTimeSeconds'.               " Time in
 seconds for long polling, such as how long the call waits for a message to arrive
 in the queue before returning. "
        ls_attribute-value = NEW /aws1/cl_sqsqueueattrmap_w( iv_value =
 iv_wait_time ).
        INSERT ls_attribute INTO TABLE lt_attributes.
        oo_result = lo_sqs->createqueue(                  " oo_result is returned
 for testing purposes. "
                iv_queuename = iv_queue_name
                it_attributes = lt_attributes
            ).
        MESSAGE 'SQS queue created.' TYPE 'I'.
      CATCH /aws1/cx_sqsqueuedeldrecently.
        MESSAGE 'After deleting a queue, wait 60 seconds before creating another
 queue with the same name.' TYPE 'E'.
      CATCH /aws1/cx_sqsqueuenameexists.
        MESSAGE 'A queue with this name already exists.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a CreateQueuereferência da API AWS SDK for SAP ABAP.

Excluir uma fila

O exemplo de código a seguir mostra como excluir uma fila do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        lo_sqs->deletequeue( iv_queueurl = iv_queue_url ).
        MESSAGE 'SQS queue deleted' TYPE 'I'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DeleteQueuereferência da API AWS SDK for SAP ABAP.

Obter o URL de uma fila

O exemplo de código a seguir mostra como obter a URL de uma fila do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_sqs->getqueueurl( iv_queuename = iv_queue_name ).        "
oo_result is returned for testing purposes. "
       MESSAGE 'Queue URL retrieved.' TYPE 'I'.
     CATCH /aws1/cx_sqsqueuedoesnotexist.
       MESSAGE 'The requested queue does not exist.' TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a GetQueueUrlreferência da API AWS SDK for SAP ABAP.

Listar filas

O exemplo de código a seguir mostra como listar filas do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   TRY.
       oo_result = lo_sqs->listqueues( ).        " oo_result is returned for
testing purposes. "
       MESSAGE 'Retrieved list of queues.' TYPE 'I'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListQueuesreferência da API AWS SDK for SAP ABAP.

Receber mensagens de uma fila

O exemplo de código a seguir mostra como excluir mensagens de uma fila do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Receba uma mensagem de uma fila do Amazon SQS.

```
   TRY.
       oo_result = lo_sqs->receivemessage( iv_queueurl = iv_queue_url ).    "
oo_result is returned for testing purposes. "
       DATA(lt_messages) = oo_result->get_messages( ).
       MESSAGE 'Message received from SQS queue.' TYPE 'I'.
     CATCH /aws1/cx_sqsoverlimit.
       MESSAGE 'Maximum number of in-flight messages reached.' TYPE 'E'.
   ENDTRY.
```

Receba uma mensagem de uma fila do Amazon SQS usando o suporte de sondagem longa.

```
   TRY.
       oo_result = lo_sqs->receivemessage(           " oo_result is returned for
testing purposes. "
               iv_queueurl = iv_queue_url
```

```
                iv_waittimeseconds = iv_wait_time     " Time in seconds for long
polling, such as how long the call waits for a message to arrive in the queue
before returning. "
            ).
        DATA(lt_messages) = oo_result->get_messages( ).
        MESSAGE 'Message received from SQS queue.' TYPE 'I'.
      CATCH /aws1/cx_sqsoverlimit.
        MESSAGE 'Maximum number of in-flight messages reached.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a ReceiveMessagereferência da API AWS SDK for SAP ABAP.

Envie uma mensagem para uma fila

O exemplo de código a seguir mostra como enviar uma mensagem para uma fila do Amazon SQS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    TRY.
        oo_result = lo_sqs->sendmessage(              " oo_result is returned for
testing purposes. "
           iv_queueurl = iv_queue_url
           iv_messagebody = iv_message
        ).
        MESSAGE 'Message sent to SQS queue.' TYPE 'I'.
      CATCH /aws1/cx_sqsinvalidmsgconts.
        MESSAGE 'Message contains non-valid characters.' TYPE 'E'.
      CATCH /aws1/cx_sqsunsupportedop.
        MESSAGE 'Operation not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a SendMessagereferência da API AWS SDK for SAP ABAP.

Cenários

Criar e publicar em um tópico FIFO

O exemplo de código a seguir mostra como criar e publicar em um tópico FIFO do Amazon SNS.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um tópico FIFO, inscreva uma fila FIFO do Amazon SQS no tópico e publique uma mensagem em um tópico do Amazon SNS.

```
    " Creates a FIFO topic. "
    DATA lt_tpc_attributes TYPE /aws1/cl_snstopicattrsmap_w=>tt_topicattributesmap.
    DATA ls_tpc_attributes TYPE /aws1/
cl_snstopicattrsmap_w=>ts_topicattributesmap_maprow.
    ls_tpc_attributes-key = 'FifoTopic'.
    ls_tpc_attributes-value = NEW /aws1/cl_snstopicattrsmap_w( iv_value = 'true' ).
    INSERT ls_tpc_attributes INTO TABLE lt_tpc_attributes.

    TRY.
        DATA(lo_create_result) = lo_sns->createtopic(
               iv_name = iv_topic_name
               it_attributes = lt_tpc_attributes
        ).
        DATA(lv_topic_arn) = lo_create_result->get_topicarn( ).
        ov_topic_arn = lv_topic_arn.                                    "
 ov_topic_arn is returned for testing purposes. "
        MESSAGE 'FIFO topic created' TYPE 'I'.
      CATCH /aws1/cx_snstopiclimitexcdex.
        MESSAGE 'Unable to create more topics. You have reached the maximum number
 of topics allowed.' TYPE 'E'.
    ENDTRY.
```

```
   " Subscribes an endpoint to an Amazon Simple Notification Service (Amazon SNS)
 topic. "
   " Only Amazon Simple Queue Service (Amazon SQS) FIFO queues can be subscribed to
 an SNS FIFO topic. "
   TRY.
       DATA(lo_subscribe_result) = lo_sns->subscribe(
              iv_topicarn = lv_topic_arn
              iv_protocol = 'sqs'
              iv_endpoint = iv_queue_arn
          ).
       DATA(lv_subscription_arn) = lo_subscribe_result->get_subscriptionarn( ).
       ov_subscription_arn = lv_subscription_arn.                      "
 ov_subscription_arn is returned for testing purposes. "
       MESSAGE 'SQS queue was subscribed to SNS topic.' TYPE 'I'.
     CATCH /aws1/cx_snsnotfoundexception.
       MESSAGE 'Topic does not exist.' TYPE 'E'.
     CATCH /aws1/cx_snssubscriptionlmte00.
       MESSAGE 'Unable to create subscriptions. You have reached the maximum number
 of subscriptions allowed.' TYPE 'E'.
   ENDTRY.

   " Publish message to SNS topic. "
   TRY.
       DATA lt_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>tt_messageattributemap.
       DATA ls_msg_attributes TYPE /aws1/
cl_snsmessageattrvalue=>ts_messageattributemap_maprow.
       ls_msg_attributes-key = 'Importance'.
       ls_msg_attributes-value = NEW /aws1/cl_snsmessageattrvalue( iv_datatype =
 'String' iv_stringvalue = 'High' ).
       INSERT ls_msg_attributes INTO TABLE lt_msg_attributes.

       DATA(lo_result) = lo_sns->publish(
            iv_topicarn = lv_topic_arn
            iv_message = 'The price of your mobile plan has been increased from $19
 to $23'
            iv_subject = 'Changes to mobile plan'
            iv_messagegroupid = 'Update-2'
            iv_messagededuplicationid = 'Update-2.1'
            it_messageattributes = lt_msg_attributes
     ).
       ov_message_id = lo_result->get_messageid( ).                    "
 ov_message_id is returned for testing purposes. "
```

```
        MESSAGE 'Message was published to SNS topic.' TYPE 'I'.
      CATCH /aws1/cx_snsnotfoundexception.
        MESSAGE 'Topic does not exist.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - CreateTopic
  - Publicar
  - Assinar

Exemplos do Amazon Textract usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para SAP ABAP com o Amazon Textract.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Analisar um documento

O exemplo de código a seguir mostra como começar a analisar um documento usando o Amazon Textract.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Detects text and additional elements, such as forms or tables,"
   "in a local image file or from in-memory byte data."
   "The image must be in PNG or JPG format."


   "Create ABAP objects for feature type."
   "Add TABLES to return information about the tables."
   "Add FORMS to return detected form data."
   "To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

   DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).

   "Create an ABAP object for the Amazon Simple Storage Service (Amazon S3)
object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_document) = NEW /aws1/cl_texdocument( io_s3object = lo_s3object ).

   "Analyze document stored in Amazon S3."
   TRY.
       oo_result = lo_tex->analyzedocument(      "oo_result is returned for testing
purposes."
         io_document        = lo_document
         it_featuretypes    = lt_featuretypes ).
       LOOP AT oo_result->get_blocks( ) INTO DATA(lo_block).
         IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
           MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
         ENDIF.
       ENDLOOP.
```

```
        MESSAGE 'Analyze document completed.' TYPE 'I'.
      CATCH /aws1/cx_texaccessdeniedex.
        MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
      CATCH /aws1/cx_texbaddocumentex.
        MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
      CATCH /aws1/cx_texdocumenttoolargeex.
        MESSAGE 'The document is too large.' TYPE 'E'.
      CATCH /aws1/cx_texhlquotaexceededex.
        MESSAGE 'Human loop quota exceeded.' TYPE 'E'.
      CATCH /aws1/cx_texinternalservererr.
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.

      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a AnalyzeDocumentreferência da API AWS SDK for SAP ABAP.

Detectar texto em um documento

O exemplo de código a seguir mostra como detectar texto em um documento usando o Amazon Textract.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Detects text in the input document."
   "Amazon Textract can detect lines of text and the words that make up a line of
 text."
   "The input document must be in one of the following image formats: JPEG, PNG,
 PDF, or TIFF."

   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_document) = NEW /aws1/cl_texdocument( io_s3object = lo_s3object ).
   "Analyze document stored in Amazon S3."
   TRY.
       oo_result = lo_tex->detectdocumenttext( io_document = lo_document ).
 "oo_result is returned for testing purposes."
       LOOP AT oo_result->get_blocks( ) INTO DATA(lo_block).
         IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
           MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
         ENDIF.
       ENDLOOP.
       DATA(lo_metadata) = oo_result->get_documentmetadata( ).
       MESSAGE 'The number of pages in the document is ' && lo_metadata-
>ask_pages( ) TYPE 'I'.
       MESSAGE 'Detect document text completed.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
     CATCH /aws1/cx_texinvalids3objectex.
       MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texprovthruputexcdex.
       MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
     CATCH /aws1/cx_texthrottlingex.
       MESSAGE 'The request processing exceeded the limit' TYPE 'E'.
     CATCH /aws1/cx_texunsupporteddocex.
```

```
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a DetectDocumentTextreferência da API AWS SDK for SAP ABAP.

Obter dados sobre um trabalho de análise de documento

O exemplo de código a seguir mostra como obter dados sobre um trabalho de análise de documento do Amazon Textract.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Gets the results for an Amazon Textract"
    "asynchronous operation that analyzes text in a document."
    TRY.
        oo_result = lo_tex->getdocumentanalysis( iv_jobid = iv_jobid ).
"oo_result is returned for testing purposes."
        WHILE oo_result->get_jobstatus( ) <> 'SUCCEEDED'.
          IF sy-index = 10.
            EXIT.               "Maximum 300 seconds.
          ENDIF.
          WAIT UP TO 30 SECONDS.
          oo_result = lo_tex->getdocumentanalysis( iv_jobid = iv_jobid ).
        ENDWHILE.

        DATA(lt_blocks) = oo_result->get_blocks( ).
        LOOP AT lt_blocks INTO DATA(lo_block).
          IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
            MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
          ENDIF.
        ENDLOOP.
        MESSAGE 'Document analysis retrieved.' TYPE 'I'.
```

```
      CATCH /aws1/cx_texaccessdeniedex.
        MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
      CATCH /aws1/cx_texinternalservererr.
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidjobidex.
        MESSAGE 'Job ID is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidkmskeyex.
        MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a GetDocumentAnalysisreferência da API AWS SDK for SAP ABAP.

Iniciar análise assíncrona de um documento

O exemplo de código a seguir mostra como começar a análise assíncrona de um documento usando o Amazon Textract.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Starts the asynchronous analysis of an input document for relationships"
   "between detected items such as key-value pairs, tables, and selection
elements."

   "Create ABAP objects for feature type."
```

```
   "Add TABLES to return information about the tables."
   "Add FORMS to return detected form data."
   "To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

   DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).
   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).
   "Create an ABAP object for the document."
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).

   "Start async document analysis."
   TRY.
       oo_result = lo_tex->startdocumentanalysis(      "oo_result is returned for
testing purposes."
         io_documentlocation     = lo_documentlocation
         it_featuretypes         = lt_featuretypes ).
       DATA(lv_jobid) = oo_result->get_jobid( ).

       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texidempotentprmmis00.
       MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
       MESSAGE 'Internal server error.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidkmskeyex.
       MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texinvalidparameterex.
       MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
     CATCH /aws1/cx_texinvalids3objectex.
       MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
     CATCH /aws1/cx_texlimitexceededex.
       MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
     CATCH /aws1/cx_texprovthruputexcdex.
       MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
     CATCH /aws1/cx_texthrottlingex.
```

```
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartDocumentAnalysisreferência da API AWS SDK for SAP ABAP.

Iniciar a detecção assíncrona de texto

O exemplo de código a seguir mostra como começar a detecção assíncrona de texto em um documento usando o Amazon Textract.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Starts the asynchronous detection of text in a document."
   "Amazon Textract can detect lines of text and the words that make up a line of
text."

   "Create an ABAP object for the Amazon S3 object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).
   "Create an ABAP object for the document."
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).
   "Start document analysis."
   TRY.
       oo_result = lo_tex->startdocumenttextdetection( io_documentlocation =
lo_documentlocation ).
       DATA(lv_jobid) = oo_result->get_jobid( ).             "oo_result is returned
for testing purposes."
       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
```

```
        MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
      CATCH /aws1/cx_texbaddocumentex.
        MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
      CATCH /aws1/cx_texdocumenttoolargeex.
        MESSAGE 'The document is too large.' TYPE 'E'.
      CATCH /aws1/cx_texidempotentprmmis00.
        MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
      CATCH /aws1/cx_texinternalservererr.
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidkmskeyex.
        MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texlimitexceededex.
        MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartDocumentTextDetectionreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de análise de documentos

O código de exemplo a seguir mostra como:

- Iniciar a análise assíncrona.
- Obter análise de documentos.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Create ABAP objects for feature type."
   "Add TABLES to return information about the tables."
   "Add FORMS to return detected form data."
   "To perform both types of analysis, add TABLES and FORMS to FeatureTypes."

   DATA(lt_featuretypes) = VALUE /aws1/cl_texfeaturetypes_w=>tt_featuretypes(
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'FORMS' ) )
     ( NEW /aws1/cl_texfeaturetypes_w( iv_value = 'TABLES' ) ) ).

   "Create an ABAP object for the Amazon Simple Storage Service (Amazon S3)
object."
   DATA(lo_s3object) = NEW /aws1/cl_texs3object( iv_bucket = iv_s3bucket
     iv_name   = iv_s3object ).

   "Create an ABAP object for the document."
   DATA(lo_documentlocation) = NEW /aws1/cl_texdocumentlocation( io_s3object =
lo_s3object ).

   "Start document analysis."
   TRY.
       DATA(lo_start_result) = lo_tex->startdocumentanalysis(
         io_documentlocation     = lo_documentlocation
         it_featuretypes         = lt_featuretypes ).
       MESSAGE 'Document analysis started.' TYPE 'I'.
     CATCH /aws1/cx_texaccessdeniedex.
       MESSAGE 'You do not have permission to perform this action.' TYPE 'E'.
     CATCH /aws1/cx_texbaddocumentex.
       MESSAGE 'Amazon Textract is not able to read the document.' TYPE 'E'.
     CATCH /aws1/cx_texdocumenttoolargeex.
       MESSAGE 'The document is too large.' TYPE 'E'.
     CATCH /aws1/cx_texidempotentprmmis00.
       MESSAGE 'Idempotent parameter mismatch exception.' TYPE 'E'.
     CATCH /aws1/cx_texinternalservererr.
```

```
        MESSAGE 'Internal server error.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidkmskeyex.
        MESSAGE 'AWS KMS key is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texinvalidparameterex.
        MESSAGE 'Request has non-valid parameters.' TYPE 'E'.
      CATCH /aws1/cx_texinvalids3objectex.
        MESSAGE 'Amazon S3 object is not valid.' TYPE 'E'.
      CATCH /aws1/cx_texlimitexceededex.
        MESSAGE 'An Amazon Textract service limit was exceeded.' TYPE 'E'.
      CATCH /aws1/cx_texprovthruputexcdex.
        MESSAGE 'Provisioned throughput exceeded limit.' TYPE 'E'.
      CATCH /aws1/cx_texthrottlingex.
        MESSAGE 'The request processing exceeded the limit.' TYPE 'E'.
      CATCH /aws1/cx_texunsupporteddocex.
        MESSAGE 'The document is not supported.' TYPE 'E'.
    ENDTRY.

    "Get job ID from the output."
    DATA(lv_jobid) = lo_start_result->get_jobid( ).

    "Wait for job to complete."
    oo_result = lo_tex->getdocumentanalysis( iv_jobid = lv_jobid ).     " oo_result
is returned for testing purposes. "
    WHILE oo_result->get_jobstatus( ) <> 'SUCCEEDED'.
      IF sy-index = 10.
        EXIT.               "Maximum 300 seconds."
      ENDIF.
      WAIT UP TO 30 SECONDS.
      oo_result = lo_tex->getdocumentanalysis( iv_jobid = lv_jobid ).
    ENDWHILE.

    DATA(lt_blocks) = oo_result->get_blocks( ).
    LOOP AT lt_blocks INTO DATA(lo_block).
      IF lo_block->get_text( ) = 'INGREDIENTS: POWDERED SUGAR* (CANE SUGAR,'.
        MESSAGE 'Found text in the doc: ' && lo_block->get_text( ) TYPE 'I'.
      ENDIF.
    ENDLOOP.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - GetDocumentAnalysis

- StartDocumentAnalysis

Exemplos do Amazon Translate usando SDK para SAP ABAP

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando a AWS SDK para SAP ABAP com o Amazon Translate.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Descrever um trabalho de tradução

O exemplo de código a seguir mostra como descrever um trabalho de tradução do Amazon Translate.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
"Gets the properties associated with an asynchronous batch translation job."
```

```
   "Includes properties such as name, ID, status, source and target languages, and
input/output Amazon Simple Storage Service (Amazon S3) buckets."
   TRY.
       oo_result = lo_xl8->describetexttranslationjob(      "oo_result is returned
for testing purposes."
         EXPORTING
           iv_jobid        = iv_jobid
         ).
       MESSAGE 'Job description retrieved.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE 'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a DescribeTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Listar trabalhos de tradução

O exemplo de código a seguir mostra como listar trabalhos de tradução do Amazon Translate.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Gets a list of the batch translation jobs that you have submitted."

   DATA lo_filter TYPE REF TO /aws1/cl_xl8textxlationjobfilt.

   "Create an ABAP object for filtering using jobname."
   CREATE OBJECT lo_filter
     EXPORTING
       iv_jobname = iv_jobname.
```

```
   TRY.
       oo_result = lo_xl8->listtexttranslationjobs(      "oo_result is returned for
testing purposes."
         EXPORTING
           io_filter        = lo_filter
         ).
       MESSAGE 'Jobs retrieved.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidfilterex .
       MESSAGE 'The filter specified for the operation is not valid. Specify a
different filter.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex .
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
   ENDTRY.
```

- Para obter detalhes da API, consulte a ListTextTranslationJobsreferência da API AWS SDK for SAP ABAP.

Iniciar um trabalho de tradução

O exemplo de código a seguir mostra como começar um trabalho de tradução com o Amazon Translate.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Starts an asynchronous batch translation job."
   "Use batch translation jobs to translate large volumes of text across multiple
documents at once."
```

```
    DATA lo_inputdataconfig  TYPE REF TO /aws1/cl_xl8inputdataconfig.
    DATA lo_outputdataconfig TYPE REF TO /aws1/cl_xl8outputdataconfig.
    DATA lt_targetlanguagecodes TYPE /aws1/
cl_xl8tgtlanguagecodes00=>tt_targetlanguagecodestrlist.
    DATA lo_targetlanguagecodes TYPE REF TO /aws1/cl_xl8tgtlanguagecodes00.

    "Create an ABAP object for the input data config."
    CREATE OBJECT lo_inputdataconfig
      EXPORTING
        iv_s3uri       = iv_input_data_s3uri
        iv_contenttype = iv_input_data_contenttype.

    "Create an ABAP object for the output data config."
    CREATE OBJECT lo_outputdataconfig
      EXPORTING
        iv_s3uri = iv_output_data_s3uri.

    "Create an internal table for target languages."
    CREATE OBJECT lo_targetlanguagecodes
      EXPORTING
        iv_value = iv_targetlanguagecode.
    INSERT lo_targetlanguagecodes  INTO TABLE lt_targetlanguagecodes.

    TRY.
        oo_result = lo_xl8->starttexttranslationjob(      "oo_result is returned for
 testing purposes."
          EXPORTING
            io_inputdataconfig = lo_inputdataconfig
            io_outputdataconfig = lo_outputdataconfig
            it_targetlanguagecodes = lt_targetlanguagecodes
            iv_dataaccessrolearn = iv_dataaccessrolearn
            iv_jobname = iv_jobname
            iv_sourcelanguagecode = iv_sourcelanguagecode
          ).
        MESSAGE 'Translation job started.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
        MESSAGE 'An internal server error occurred. Retry your request.' TYPE 'E'.
      CATCH /aws1/cx_xl8invparamvalueex .
        MESSAGE 'The value of the parameter is not valid.' TYPE 'E'.
      CATCH /aws1/cx_xl8invalidrequestex.
        MESSAGE 'The request that you made is not valid.' TYPE 'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
```

```
        MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
      CATCH /aws1/cx_xl8unsuppedlanguage00 .
        MESSAGE 'Amazon Translate does not support translation from the language of
the source text into the requested target language.' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StartTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Interromper um trabalho de tradução

O exemplo de código a seguir mostra como excluir um grupo do Amazon Translate.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    "Stops an asynchronous batch translation job that is in progress."

    TRY.
        oo_result = lo_xl8->stoptexttranslationjob(      "oo_result is returned for
testing purposes."
          EXPORTING
            iv_jobid        = iv_jobid
          ).
        MESSAGE 'Translation job stopped.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
        MESSAGE 'An internal server error occurred.' TYPE 'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
        MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a StopTextTranslationJobreferência da API AWS SDK for SAP ABAP.

Traduzir texto

O exemplo de código a seguir mostra como traduzir texto com o Amazon Translate.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   "Translates input text from the source language to the target language."
   TRY.
       oo_result = lo_xl8->translatetext(      "oo_result is returned for testing
purposes."
         EXPORTING
           iv_text        = iv_text
           iv_sourcelanguagecode = iv_sourcelanguagecode
           iv_targetlanguagecode = iv_targetlanguagecode
         ).
       MESSAGE 'Translation completed.' TYPE 'I'.
     CATCH /aws1/cx_xl8detectedlanguage00 .
       MESSAGE 'The confidence that Amazon Comprehend accurately detected the
source language is low.' TYPE 'E'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex .
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8serviceunavailex .
       MESSAGE 'The Amazon Translate service is temporarily unavailable.' TYPE 'E'.
     CATCH /aws1/cx_xl8textsizelmtexcdex .
       MESSAGE 'The size of the text you submitted exceeds the size limit. ' TYPE
'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex .
       MESSAGE 'You have made too many requests within a short period of time.'
TYPE 'E'.
```

```
      CATCH /aws1/cx_xl8unsuppedlanguage00 .
        MESSAGE 'Amazon Translate does not support translation from the language of
 the source text into the requested target language. ' TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte a TranslateTextreferência da API AWS SDK for SAP ABAP.

Cenários

Conceitos básicos de trabalhos de tradução

O código de exemplo a seguir mostra como:

- Iniciar um trabalho de tradução em lote assíncrono.
- Aguardar a conclusão do trabalho assíncrono.
- Descrever o trabalho assíncrono.

SDK para SAP ABAP

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    DATA lo_inputdataconfig  TYPE REF TO /aws1/cl_xl8inputdataconfig.
    DATA lo_outputdataconfig TYPE REF TO /aws1/cl_xl8outputdataconfig.
    DATA lt_targetlanguagecodes TYPE /aws1/
cl_xl8tgtlanguagecodes00=>tt_targetlanguagecodestrlist.
    DATA lo_targetlanguagecodes TYPE REF TO /aws1/cl_xl8tgtlanguagecodes00.

    "Create an ABAP object for the input data config."
    CREATE OBJECT lo_inputdataconfig
      EXPORTING
        iv_s3uri       = iv_input_data_s3uri
        iv_contenttype = iv_input_data_contenttype.
```

```
   "Create an ABAP object for the output data config."
   CREATE OBJECT lo_outputdataconfig
     EXPORTING
       iv_s3uri = iv_output_data_s3uri.

   "Create an internal table for target languages."
   CREATE OBJECT lo_targetlanguagecodes
     EXPORTING
       iv_value = iv_targetlanguagecode.
   INSERT lo_targetlanguagecodes  INTO TABLE lt_targetlanguagecodes.

   TRY.
       DATA(lo_translationjob_result) = lo_xl8->starttexttranslationjob(
         EXPORTING
           io_inputdataconfig = lo_inputdataconfig
           io_outputdataconfig = lo_outputdataconfig
           it_targetlanguagecodes = lt_targetlanguagecodes
           iv_dataaccessrolearn = iv_dataaccessrolearn
           iv_jobname = iv_jobname
           iv_sourcelanguagecode = iv_sourcelanguagecode
         ).
       MESSAGE 'Translation job started.' TYPE 'I'.
     CATCH /aws1/cx_xl8internalserverex .
       MESSAGE 'An internal server error occurred. Retry your request.' TYPE 'E'.
     CATCH /aws1/cx_xl8invparamvalueex .
       MESSAGE 'The value of the parameter is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8invalidrequestex.
       MESSAGE 'The request that you made is not valid.' TYPE 'E'.
     CATCH /aws1/cx_xl8resourcenotfoundex .
       MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
     CATCH /aws1/cx_xl8toomanyrequestsex.
       MESSAGE 'You have made too many requests within a short period of time. '
TYPE 'E'.
     CATCH /aws1/cx_xl8unsuppedlanguage00 .
       MESSAGE 'Amazon Translate does not support translation from the language of
the source text into the requested target language.' TYPE 'E'.
   ENDTRY.

   "Get the job ID."
   DATA(lv_jobid) = lo_translationjob_result->get_jobid( ).

   "Wait for translate job to complete."
   DATA(lo_des_translation_result) = lo_xl8->describetexttranslationjob( iv_jobid =
lv_jobid ).
```

```
    WHILE lo_des_translation_result->get_textxlationjobproperties( )-
>get_jobstatus( ) <> 'COMPLETED'.
      IF sy-index = 30.
        EXIT.               "Maximum 900 seconds."
      ENDIF.
      WAIT UP TO 30 SECONDS.
      lo_des_translation_result = lo_xl8->describetexttranslationjob( iv_jobid =
 lv_jobid ).
    ENDWHILE.

    TRY.
        oo_result = lo_xl8->describetexttranslationjob(      "oo_result is returned
 for testing purposes."
          EXPORTING
            iv_jobid        = lv_jobid
          ).
        MESSAGE 'Job description retrieved.' TYPE 'I'.
      CATCH /aws1/cx_xl8internalserverex .
        MESSAGE 'An internal server error occurred. Retry your request.' TYPE 'E'.
      CATCH /aws1/cx_xl8resourcenotfoundex .
        MESSAGE 'The resource you are looking for has not been found.' TYPE 'E'.
      CATCH /aws1/cx_xl8toomanyrequestsex.
        MESSAGE 'You have made too many requests within a short period of time.'
 TYPE 'E'.
    ENDTRY.
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para SAP ABAP.
  - DescribeTextTranslationJob
  - StartTextTranslationJob

Exemplos de código para o SDK para Swift.

Os exemplos de código a seguir mostram como usar o AWS SDK para Swift com AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Exemplos entre serviços são amostras de aplicações que funcionam em vários Serviços da AWS.

Mais atributos

- Guia do Desenvolvedor do SDK para Swift : Saiba mais sobre como usar o Swift com AWS.
- AWS Centro do desenvolvedor : exemplos de código que você pode filtrar por categoria ou pesquisa de texto completo.
- AWSExemplos de SDK — GitHub repositório com código completo nos idiomas preferidos. Inclui instruções para configurar e executar o código.

Exemplos

- Ações e cenários usando o SDK para Swift

Ações e cenários usando o SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com Serviços da AWS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Serviços

- Exemplos do Amazon Cognito Identity usando SDK para Swift
- Exemplos de código do DynamoDB usando SDK para Swift
- Exemplos do IAM usando SDK para Swift
- Exemplos de código do Amazon S3 usando SDK para Swift
- Exemplos AWS STS usando SDK para Swift

Exemplos do Amazon Cognito Identity usando SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com o Amazon Cognito Identity.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Criar um banco de identidades do

O exemplo de código a seguir mostra como criar um banco de identidades do Amazon Cognito.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Crie um grupo de identidades.

```
    /// Create a new identity pool and return its ID.
    ///
    /// - Parameters:
    ///     - name: The name to give the new identity pool.
    ///
    /// - Returns: A string containing the newly created pool's ID, or `nil`
    ///   if an error occurred.
    ///
    func createIdentityPool(name: String) async throws -> String? {
        let cognitoInputCall = CreateIdentityPoolInput(developerProviderName:
"com.exampleco.CognitoIdentityDemo",
                                                       identityPoolName: name)

        let result = try await cognitoIdentityClient.createIdentityPool(input:
cognitoInputCall)
        guard let poolId = result.identityPoolId else {
            return nil
        }

        return poolId
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CreateIdentityPool
  - ListIdentityPools

Excluir um grupo de identidades

O exemplo de código a seguir mostra como excluir um banco de identidades do Amazon Cognito.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Exclua o grupo de identidades especificado.

```
/// Delete the specified identity pool.
///
/// - Parameters:
///   - id: The ID of the identity pool to delete.
///
func deleteIdentityPool(id: String) async throws {
    let input = DeleteIdentityPoolInput(
        identityPoolId: id
    )

    _ = try await cognitoIdentityClient.deleteIdentityPool(input: input)
}
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte DeleteIdentityPoola referência da API AWS SDK for Swift.

Listar grupos de identidades

O exemplo de código a seguir mostra como obter uma lista do banco de identidades do Amazon Cognito.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Encontre o ID de um grupo de identidades com seu nome.

```
    /// Return the ID of the identity pool with the specified name.
    ///
    /// - Parameters:
    ///   - name: The name of the identity pool whose ID should be returned.
    ///
    /// - Returns: A string containing the ID of the specified identity pool
    ///   or `nil` on error or if not found.
    ///
    func getIdentityPoolID(name: String) async throws -> String? {
        var token: String? = nil

        // Iterate over the identity pools until a match is found.

        repeat {
            /// `token` is a value returned by `ListIdentityPools()` if the
            /// returned list of identity pools is only a partial list. You
            /// use the `token` to tell Amazon Cognito that you want to
            /// continue where you left off previously. If you specify `nil`
            /// or you don't provide the token, Amazon Cognito will start at
            /// the beginning.

            let listPoolsInput = ListIdentityPoolsInput(maxResults: 25, nextToken:
token)

            /// Read pages of identity pools from Cognito until one is found
            /// whose name matches the one specified in the `name` parameter.
            /// Return the matching pool's ID. Each time we ask for the next
            /// page of identity pools, we pass in the token given by the
            /// previous page.

            let output = try await cognitoIdentityClient.listIdentityPools(input:
listPoolsInput)

            if let identityPools = output.identityPools {
                for pool in identityPools {
```

```
                    if pool.identityPoolName == name {
                        return pool.identityPoolId!
                    }
                }
            }

            token = output.nextToken
        } while token != nil

        return nil
    }
```

Obtenha o ID de um grupo de identidades existente ou crie-o se ainda não existir.

```
    /// Return the ID of the identity pool with the specified name.
    ///
    /// - Parameters:
    ///   - name: The name of the identity pool whose ID should be returned
    ///
    /// - Returns: A string containing the ID of the specified identity pool.
    ///   Returns `nil` if there's an error or if the pool isn't found.
    ///
    public func getOrCreateIdentityPoolID(name: String) async throws -> String? {
        // See if the pool already exists. If it doesn't, create it.

        guard let poolId = try await self.getIdentityPoolID(name: name) else {
            return try await self.createIdentityPool(name: name)
        }

        return poolId
    }
```

- Para ter mais informações, consulte o Guia do desenvolvedor do AWS SDK para Swift.
- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CreateIdentityPool
  - ListIdentityPools

Exemplos de código do DynamoDB usando SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com o DynamoDB.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Criar uma tabela

O exemplo de código a seguir mostra como criar uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    ///
    /// Create a movie table in the Amazon DynamoDB data store.
    ///
    private func createTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = CreateTableInput(
            attributeDefinitions: [
                DynamoDBClientTypes.AttributeDefinition(attributeName: "year",
attributeType: .n),
                DynamoDBClientTypes.AttributeDefinition(attributeName: "title",
attributeType: .s),
            ],
            keySchema: [
                DynamoDBClientTypes.KeySchemaElement(attributeName: "year",
keyType: .hash),
                DynamoDBClientTypes.KeySchemaElement(attributeName: "title",
keyType: .range)
            ],
            provisionedThroughput: DynamoDBClientTypes.ProvisionedThroughput(
                readCapacityUnits: 10,
                writeCapacityUnits: 10
            ),
            tableName: self.tableName
        )
        let output = try await client.createTable(input: input)
        if output.tableDescription == nil {
            throw MoviesError.TableNotFound
        }
    }
```

- Para obter detalhes da API, consulte CreateTablea referência da API AWS SDK for Swift.

Excluir uma tabela

O exemplo de código a seguir mostra como excluir uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
///
/// Deletes the table from Amazon DynamoDB.
///
func deleteTable() async throws {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = DeleteTableInput(
        tableName: self.tableName
    )
    _ = try await client.deleteTable(input: input)
}
```

- Para obter detalhes da API, consulte DeleteTablea referência da API AWS SDK for Swift.

Excluir um item de uma tabela

O exemplo de código a seguir mostra como excluir um item de uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Delete a movie, given its title and release year.
///
/// - Parameters:
///   - title: The movie's title.
///   - year: The movie's release year.
///
func delete(title: String, year: Int) async throws {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = DeleteItemInput(
        key: [
            "year": .n(String(year)),
            "title": .s(title)
        ],
        tableName: self.tableName
    )
    _ = try await client.deleteItem(input: input)
}
```

- Para obter detalhes da API, consulte DeleteItema referência da API AWS SDK for Swift.

Obter um lote de itens

O exemplo de código a seguir mostra como obter um lote de itens do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Gets an array of `Movie` objects describing all the movies in the
    /// specified list. Any movies that aren't found in the list have no
    /// corresponding entry in the resulting array.
    ///
    /// - Parameters
    ///     - keys: An array of tuples, each of which specifies the title and
    ///       release year of a movie to fetch from the table.
    ///
    /// - Returns:
    ///     - An array of `Movie` objects describing each match found in the
    ///     table.
    ///
    /// - Throws:
    ///     - `MovieError.ClientUninitialized` if the DynamoDB client has not
    ///     been initialized.
    ///     - DynamoDB errors are thrown without change.
    func batchGet(keys: [(title: String, year: Int)]) async throws -> [Movie] {
        guard let client = self.ddbClient else {
            throw MovieError.ClientUninitialized
        }

        var movieList: [Movie] = []
        var keyItems: [[Swift.String:DynamoDBClientTypes.AttributeValue]] = []
```

```
        // Convert the list of keys into the form used by DynamoDB.

        for key in keys {
            let item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
                "title": .s(key.title),
                "year": .n(String(key.year))
            ]
            keyItems.append(item)
        }

        // Create the input record for `batchGetItem()`. The list of requested
        // items is in the `requestItems` property. This array contains one
        // entry for each table from which items are to be fetched. In this
        // example, there's only one table containing the movie data.
        //
        // If we wanted this program to also support searching for matches
        // in a table of book data, we could add a second `requestItem`
        // mapping the name of the book table to the list of items we want to
        // find in it.
        let input = BatchGetItemInput(
            requestItems: [
                self.tableName: .init(
                    consistentRead: true,
                    keys: keyItems
                )
            ]
        )

        // Fetch the matching movies from the table.

        let output = try await client.batchGetItem(input: input)

        // Get the set of responses. If there aren't any, return the empty
        // movie list.

        guard let responses = output.responses else {
            return movieList
        }

        // Get the list of matching items for the table with the name
        // `tableName`.

        guard let responseList = responses[self.tableName] else {
            return movieList
```

```
        }

        // Create `Movie` items for each of the matching movies in the table
        // and add them to the `MovieList` array.

        for response in responseList {
            movieList.append(try Movie(withItem: response))
        }

        return movieList
    }
```

- Para obter detalhes da API, consulte BatchGetItema referência da API AWS SDK for Swift.

Obter um item de uma tabela

O exemplo de código a seguir mostra como obter um item de uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Return a `Movie` record describing the specified movie from the Amazon
    /// DynamoDB table.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The movie's release year (`Int`).
    ///
```

```
    /// - Throws: `MoviesError.ItemNotFound` if the movie isn't in the table.
    ///
    /// - Returns: A `Movie` record with the movie's details.
    func get(title: String, year: Int) async throws -> Movie {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = GetItemInput(
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            tableName: self.tableName
        )
        let output = try await client.getItem(input: input)
        guard let item = output.item else {
            throw MoviesError.ItemNotFound
        }

        let movie = try Movie(withItem: item)
        return movie
    }
```

- Para obter detalhes da API, consulte GetItema referência da API AWS SDK for Swift.

Listar tabelas

O exemplo de código a seguir mostra como listar tabelas do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Get a list of the DynamoDB tables available in the specified Region.
///
/// - Returns: An array of strings listing all of the tables available
///   in the Region specified when the session was created.
public func getTableList() async throws -> [String] {
    var tableList: [String] = []
    var lastEvaluated: String? = nil

    // Iterate over the list of tables, 25 at a time, until we have the
    // names of every table. Add each group to the `tableList` array.
    // Iteration is complete when `output.lastEvaluatedTableName` is `nil`.

    repeat {
        let input = ListTablesInput(
            exclusiveStartTableName: lastEvaluated,
            limit: 25
        )
        let output = try await self.session.listTables(input: input)
        guard let tableNames = output.tableNames else {
            return tableList
        }
        tableList.append(contentsOf: tableNames)
        lastEvaluated = output.lastEvaluatedTableName
    } while lastEvaluated != nil

    return tableList
}
```

- Para obter detalhes da API, consulte ListTablesa referência da API AWS SDK for Swift.

Colocar um item em uma tabela

O exemplo de código a seguir mostra como colocar um item em uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Add a movie specified as a `Movie` structure to the Amazon DynamoDB
/// table.
///
/// - Parameter movie: The `Movie` to add to the table.
///
func add(movie: Movie) async throws {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    // Get a DynamoDB item containing the movie data.
    let item = try await movie.getAsItem()

    // Send the `PutItem` request to Amazon DynamoDB.

    let input = PutItemInput(
        item: item,
        tableName: self.tableName
    )
    _ = try await client.putItem(input: input)
}

///
/// Return an array mapping attribute names to Amazon DynamoDB attribute
/// values, representing the contents of the `Movie` record as a DynamoDB
/// item.
///
```

```
    /// - Returns: The movie item as an array of type
    ///   `[Swift.String:DynamoDBClientTypes.AttributeValue]`.
    ///
    func getAsItem() async throws ->
[Swift.String:DynamoDBClientTypes.AttributeValue]  {
        // Build the item record, starting with the year and title, which are
        // always present.

        var item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
            "year": .n(String(self.year)),
            "title": .s(self.title)
        ]

        // Add the `info` field with the rating and/or plot if they're
        // available.

        var details: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]
        if (self.info.rating != nil || self.info.plot != nil) {
            if self.info.rating != nil {
                details["rating"] = .n(String(self.info.rating!))
            }
            if self.info.plot != nil {
                details["plot"] = .s(self.info.plot!)
            }
        }
        item["info"] = .m(details)

        return item
    }
```

- Para obter detalhes da API, consulte PutItem a referência da API AWS SDK for Swift.

Consultar uma tabela

O exemplo de código a seguir mostra como consultar uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
/// Get all the movies released in the specified year.
///
/// - Parameter year: The release year of the movies to return.
///
/// - Returns: An array of `Movie` objects describing each matching movie.
///
func getMovies(fromYear year: Int) async throws -> [Movie] {
    guard let client = self.ddbClient else {
        throw MoviesError.UninitializedClient
    }

    let input = QueryInput(
        expressionAttributeNames: [
            "#y": "year"
        ],
        expressionAttributeValues: [
            ":y": .n(String(year))
        ],
        keyConditionExpression: "#y = :y",
        tableName: self.tableName
    )
    let output = try await client.query(input: input)

    guard let items = output.items else {
        throw MoviesError.ItemNotFound
    }
```

```
        // Convert the found movies into `Movie` objects and return an array
        // of them.

        var movieList: [Movie] = []
        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }
        return movieList
    }
```

- Para obter detalhes da API, consulte Query na Referência da API do AWS SDK para Swift.

Verificar uma tabela

O exemplo de código a seguir mostra como verificar uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Return an array of `Movie` objects released in the specified range of
    /// years.
    ///
    /// - Parameters:
    ///   - firstYear: The first year of movies to return.
    ///   - lastYear: The last year of movies to return.
    ///   - startKey: A starting point to resume processing; always use `nil`.
    ///
    /// - Returns: An array of `Movie` objects describing the matching movies.
```

```
    ///
    /// > Note: The `startKey` parameter is used by this function when
    ///   recursively calling itself, and should always be `nil` when calling
    ///   directly.
    ///
    func getMovies(firstYear: Int, lastYear: Int,
                   startKey: [Swift.String:DynamoDBClientTypes.AttributeValue]? =
nil)
                   async throws -> [Movie] {
        var movieList: [Movie] = []

        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = ScanInput(
            consistentRead: true,
            exclusiveStartKey: startKey,
            expressionAttributeNames: [
                "#y": "year"            // `year` is a reserved word, so use `#y`
instead.
            ],
            expressionAttributeValues: [
                ":y1": .n(String(firstYear)),
                ":y2": .n(String(lastYear))
            ],
            filterExpression: "#y BETWEEN :y1 AND :y2",
            tableName: self.tableName
        )

        let output = try await client.scan(input: input)

        guard let items = output.items else {
            return movieList
        }

        // Build an array of `Movie` objects for the returned items.

        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }

        // Call this function recursively to continue collecting matching
```

```
        // movies, if necessary.

        if output.lastEvaluatedKey != nil {
            let movies = try await self.getMovies(firstYear: firstYear, lastYear:
lastYear,
                        startKey: output.lastEvaluatedKey)
            movieList += movies
        }
        return movieList
    }
```

- Para obter detalhes da API, consulte Scan na Referência da API do AWS SDK para Swift.

Atualizar um item em uma tabela

O exemplo de código a seguir mostra como atualizar um item em uma tabela do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Update the specified movie with new `rating` and `plot` information.
    ///
    /// - Parameters:
    ///   - title: The title of the movie to update.
    ///   - year: The release year of the movie to update.
    ///   - rating: The new rating for the movie.
    ///   - plot: The new plot summary string for the movie.
    ///
    /// - Returns: An array of mappings of attribute names to their new
```

```
    ///   listing each item actually changed. Items that didn't need to change
    ///   aren't included in this list. `nil` if no changes were made.
    ///
    func update(title: String, year: Int, rating: Double? = nil, plot: String? =
nil) async throws
                -> [Swift.String:DynamoDBClientTypes.AttributeValue]? {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Build the update expression and the list of expression attribute
        // values. Include only the information that's changed.

        var expressionParts: [String] = []
        var attrValues: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]

        if rating != nil {
            expressionParts.append("info.rating=:r")
            attrValues[":r"] = .n(String(rating!))
        }
        if plot != nil {
            expressionParts.append("info.plot=:p")
            attrValues[":p"] = .s(plot!)
        }
        let expression: String = "set \(expressionParts.joined(separator: ", "))"

        let input = UpdateItemInput(
            // Create substitution tokens for the attribute values, to ensure
            // no conflicts in expression syntax.
            expressionAttributeValues: attrValues,
            // The key identifying the movie to update consists of the release
            // year and title.
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            returnValues: .updatedNew,
            tableName: self.tableName,
            updateExpression: expression
        )
        let output = try await client.updateItem(input: input)

        guard let attributes: [Swift.String:DynamoDBClientTypes.AttributeValue] =
output.attributes else {
```

```
            throw MoviesError.InvalidAttributes
        }
        return attributes
    }
```

- Para obter detalhes da API, consulte UpdateItema referência da API AWS SDK for Swift.

Gravar um lote de itens

O exemplo de código a seguir mostra como gravar um lote de itens do DynamoDB.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Populate the movie database from the specified JSON file.
    ///
    /// - Parameter jsonPath: Path to a JSON file containing movie data.
    ///
    func populate(jsonPath: String) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Create a Swift `URL` and use it to load the file into a `Data`
        // object. Then decode the JSON into an array of `Movie` objects.

        let fileUrl = URL(fileURLWithPath: jsonPath)
        let jsonData = try Data(contentsOf: fileUrl)
```

```
        var movieList = try JSONDecoder().decode([Movie].self, from: jsonData)

        // Truncate the list to the first 200 entries or so for this example.

        if movieList.count > 200 {
            movieList = Array(movieList[...199])
        }

        // Before sending records to the database, break the movie list into
        // 25-entry chunks, which is the maximum size of a batch item request.

        let count = movieList.count
        let chunks = stride(from: 0, to: count, by: 25).map {
            Array(movieList[$0 ..< Swift.min($0 + 25, count)])
        }

        // For each chunk, create a list of write request records and populate
        // them with `PutRequest` requests, each specifying one movie from the
        // chunk. Once the chunk's items are all in the `PutRequest` list,
        // send them to Amazon DynamoDB using the
        // `DynamoDBClient.batchWriteItem()` function.

        for chunk in chunks {
            var requestList: [DynamoDBClientTypes.WriteRequest] = []

            for movie in chunk {
                let item = try await movie.getAsItem()
                let request = DynamoDBClientTypes.WriteRequest(
                    putRequest: .init(
                        item: item
                    )
                )
                requestList.append(request)
            }

            let input = BatchWriteItemInput(requestItems: [tableName: requestList])
            _ = try await client.batchWriteItem(input: input)
        }
    }
```

- Para obter detalhes da API, consulte BatchWriteItema referência da API AWS SDK for Swift.

Cenários

Conceitos básicos de tabelas, itens e consultas

O código de exemplo a seguir mostra como:

- Criar uma tabela que possa conter dados de filmes.
- Colocar, obter e atualizar um único filme na tabela.
- Grave dados de filmes na tabela usando um arquivo JSON de exemplo.
- Consultar filmes que foram lançados em determinado ano.
- Verificar filmes que foram lançados em um intervalo de anos.
- Exclua um filme da tabela e, depois, exclua a tabela.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma classe Swift que gerencia chamadas do DynamoDB para o SDK para Swift.

```
import Foundation
import AWSDynamoDB

/// An enumeration of error codes representing issues that can arise when using
/// the `MovieTable` class.
enum MoviesError: Error {
    /// The specified table wasn't found or couldn't be created.
    case TableNotFound
    /// The specified item wasn't found or couldn't be created.
    case ItemNotFound
```

```
    /// The Amazon DynamoDB client is not properly initialized.
    case UninitializedClient
    /// The table status reported by Amazon DynamoDB is not recognized.
    case StatusUnknown
    /// One or more specified attribute values are invalid or missing.
    case InvalidAttributes
}


/// A class representing an Amazon DynamoDB table containing movie
/// information.
public class MovieTable {
    var ddbClient: DynamoDBClient? = nil
    let tableName: String

    /// Create an object representing a movie table in an Amazon DynamoDB
    /// database.
    ///
    /// - Parameters:
    ///   - region: The Amazon Region to create the database in.
    ///   - tableName: The name to assign to the table. If not specified, a
    ///     random table name is generated automatically.
    ///
    /// > Note: The table is not necessarily available when this function
    /// returns. Use `tableExists()` to check for its availability, or
    /// `awaitTableActive()` to wait until the table's status is reported as
    /// ready to use by Amazon DynamoDB.
    ///
    init(region: String = "us-east-2", tableName: String) async throws {
        ddbClient = try DynamoDBClient(region: region)
        self.tableName = tableName

        try await self.createTable()
    }

    ///
    /// Create a movie table in the Amazon DynamoDB data store.
    ///
    private func createTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = CreateTableInput(
```

```
            attributeDefinitions: [
                DynamoDBClientTypes.AttributeDefinition(attributeName: "year",
attributeType: .n),
                DynamoDBClientTypes.AttributeDefinition(attributeName: "title",
attributeType: .s),
            ],
            keySchema: [
                DynamoDBClientTypes.KeySchemaElement(attributeName: "year",
keyType: .hash),
                DynamoDBClientTypes.KeySchemaElement(attributeName: "title",
keyType: .range)
            ],
            provisionedThroughput: DynamoDBClientTypes.ProvisionedThroughput(
                readCapacityUnits: 10,
                writeCapacityUnits: 10
            ),
            tableName: self.tableName
        )
        let output = try await client.createTable(input: input)
        if output.tableDescription == nil {
            throw MoviesError.TableNotFound
        }
    }

    /// Check to see if the table exists online yet.
    ///
    /// - Returns: `true` if the table exists, or `false` if not.
    ///
    func tableExists() async throws -> Bool {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DescribeTableInput(
            tableName: tableName
        )
        let output = try await client.describeTable(input: input)
        guard let description = output.table else {
            throw MoviesError.TableNotFound
        }

        return (description.tableName == self.tableName)
    }
```

```
    ///
    /// Waits for the table to exist and for its status to be active.
    ///
    func awaitTableActive() async throws {
        while (try await tableExists() == false) {
            Thread.sleep(forTimeInterval: 0.25)
        }

        while (try await getTableStatus() != .active) {
            Thread.sleep(forTimeInterval: 0.25)
        }
    }

    ///
    /// Deletes the table from Amazon DynamoDB.
    ///
    func deleteTable() async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DeleteTableInput(
            tableName: self.tableName
        )
        _ = try await client.deleteTable(input: input)
    }

    /// Get the table's status.
    ///
    /// - Returns: The table status, as defined by the
    ///   `DynamoDBClientTypes.TableStatus` enum.
    ///
    func getTableStatus() async throws -> DynamoDBClientTypes.TableStatus {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DescribeTableInput(
            tableName: self.tableName
        )
        let output = try await client.describeTable(input: input)
        guard let description = output.table else {
            throw MoviesError.TableNotFound
        }
```

```
        guard let status = description.tableStatus else {
            throw MoviesError.StatusUnknown
        }
        return status
    }

    /// Populate the movie database from the specified JSON file.
    ///
    /// - Parameter jsonPath: Path to a JSON file containing movie data.
    ///
    func populate(jsonPath: String) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Create a Swift `URL` and use it to load the file into a `Data`
        // object. Then decode the JSON into an array of `Movie` objects.

        let fileUrl = URL(fileURLWithPath: jsonPath)
        let jsonData = try Data(contentsOf: fileUrl)

        var movieList = try JSONDecoder().decode([Movie].self, from: jsonData)

        // Truncate the list to the first 200 entries or so for this example.

        if movieList.count > 200 {
            movieList = Array(movieList[...199])
        }

        // Before sending records to the database, break the movie list into
        // 25-entry chunks, which is the maximum size of a batch item request.

        let count = movieList.count
        let chunks = stride(from: 0, to: count, by: 25).map {
            Array(movieList[$0 ..< Swift.min($0 + 25, count)])
        }

        // For each chunk, create a list of write request records and populate
        // them with `PutRequest` requests, each specifying one movie from the
        // chunk. Once the chunk's items are all in the `PutRequest` list,
        // send them to Amazon DynamoDB using the
        // `DynamoDBClient.batchWriteItem()` function.

        for chunk in chunks {
```

```
            var requestList: [DynamoDBClientTypes.WriteRequest] = []

            for movie in chunk {
                let item = try await movie.getAsItem()
                let request = DynamoDBClientTypes.WriteRequest(
                    putRequest: .init(
                        item: item
                    )
                )
                requestList.append(request)
            }

            let input = BatchWriteItemInput(requestItems: [tableName: requestList])
            _ = try await client.batchWriteItem(input: input)
        }
    }

    /// Add a movie specified as a `Movie` structure to the Amazon DynamoDB
    /// table.
    ///
    /// - Parameter movie: The `Movie` to add to the table.
    ///
    func add(movie: Movie) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Get a DynamoDB item containing the movie data.
        let item = try await movie.getAsItem()

        // Send the `PutItem` request to Amazon DynamoDB.

        let input = PutItemInput(
            item: item,
            tableName: self.tableName
        )
        _ = try await client.putItem(input: input)
    }

    /// Given a movie's details, add a movie to the Amazon DynamoDB table.
    ///
    /// - Parameters:
    ///   - title: The movie's title as a `String`.
    ///   - year: The release year of the movie (`Int`).
```

```
    ///   - rating: The movie's rating if available (`Double`; default is
    ///     `nil`).
    ///   - plot: A summary of the movie's plot (`String`; default is `nil`,
    ///     indicating no plot summary is available).
    ///
    func add(title: String, year: Int, rating: Double? = nil,
             plot: String? = nil) async throws {
        let movie = Movie(title: title, year: year, rating: rating, plot: plot)
        try await self.add(movie: movie)
    }

    /// Return a `Movie` record describing the specified movie from the Amazon
    /// DynamoDB table.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The movie's release year (`Int`).
    ///
    /// - Throws: `MoviesError.ItemNotFound` if the movie isn't in the table.
    ///
    /// - Returns: A `Movie` record with the movie's details.
    func get(title: String, year: Int) async throws -> Movie {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = GetItemInput(
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            tableName: self.tableName
        )
        let output = try await client.getItem(input: input)
        guard let item = output.item else {
            throw MoviesError.ItemNotFound
        }

        let movie = try Movie(withItem: item)
        return movie
    }

    /// Get all the movies released in the specified year.
    ///
```

```
    /// - Parameter year: The release year of the movies to return.
    ///
    /// - Returns: An array of `Movie` objects describing each matching movie.
    ///
    func getMovies(fromYear year: Int) async throws -> [Movie] {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = QueryInput(
            expressionAttributeNames: [
                "#y": "year"
            ],
            expressionAttributeValues: [
                ":y": .n(String(year))
            ],
            keyConditionExpression: "#y = :y",
            tableName: self.tableName
        )
        let output = try await client.query(input: input)

        guard let items = output.items else {
            throw MoviesError.ItemNotFound
        }

        // Convert the found movies into `Movie` objects and return an array
        // of them.

        var movieList: [Movie] = []
        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }
        return movieList
    }

    /// Return an array of `Movie` objects released in the specified range of
    /// years.
    ///
    /// - Parameters:
    ///   - firstYear: The first year of movies to return.
    ///   - lastYear: The last year of movies to return.
    ///   - startKey: A starting point to resume processing; always use `nil`.
    ///
```

```
    /// - Returns: An array of `Movie` objects describing the matching movies.
    ///
    /// > Note: The `startKey` parameter is used by this function when
    ///   recursively calling itself, and should always be `nil` when calling
    ///   directly.
    ///
    func getMovies(firstYear: Int, lastYear: Int,
                   startKey: [Swift.String:DynamoDBClientTypes.AttributeValue]? =
nil)
                   async throws -> [Movie] {
        var movieList: [Movie] = []

        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = ScanInput(
            consistentRead: true,
            exclusiveStartKey: startKey,
            expressionAttributeNames: [
                "#y": "year"            // `year` is a reserved word, so use `#y`
instead.
            ],
            expressionAttributeValues: [
                ":y1": .n(String(firstYear)),
                ":y2": .n(String(lastYear))
            ],
            filterExpression: "#y BETWEEN :y1 AND :y2",
            tableName: self.tableName
        )

        let output = try await client.scan(input: input)

        guard let items = output.items else {
            return movieList
        }

        // Build an array of `Movie` objects for the returned items.

        for item in items {
            let movie = try Movie(withItem: item)
            movieList.append(movie)
        }
```

```
        // Call this function recursively to continue collecting matching
        // movies, if necessary.

        if output.lastEvaluatedKey != nil {
            let movies = try await self.getMovies(firstYear: firstYear, lastYear:
lastYear,
                        startKey: output.lastEvaluatedKey)
            movieList += movies
        }
        return movieList
    }

    /// Update the specified movie with new `rating` and `plot` information.
    ///
    /// - Parameters:
    ///   - title: The title of the movie to update.
    ///   - year: The release year of the movie to update.
    ///   - rating: The new rating for the movie.
    ///   - plot: The new plot summary string for the movie.
    ///
    /// - Returns: An array of mappings of attribute names to their new
    ///   listing each item actually changed. Items that didn't need to change
    ///   aren't included in this list. `nil` if no changes were made.
    ///
    func update(title: String, year: Int, rating: Double? = nil, plot: String? =
nil) async throws
                -> [Swift.String:DynamoDBClientTypes.AttributeValue]? {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        // Build the update expression and the list of expression attribute
        // values. Include only the information that's changed.

        var expressionParts: [String] = []
        var attrValues: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]

        if rating != nil {
            expressionParts.append("info.rating=:r")
            attrValues[":r"] = .n(String(rating!))
        }
        if plot != nil {
            expressionParts.append("info.plot=:p")
            attrValues[":p"] = .s(plot!)
```

```
        }
        let expression: String = "set \(expressionParts.joined(separator: ", "))"

        let input = UpdateItemInput(
            // Create substitution tokens for the attribute values, to ensure
            // no conflicts in expression syntax.
            expressionAttributeValues: attrValues,
            // The key identifying the movie to update consists of the release
            // year and title.
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            returnValues: .updatedNew,
            tableName: self.tableName,
            updateExpression: expression
        )
        let output = try await client.updateItem(input: input)

        guard let attributes: [Swift.String:DynamoDBClientTypes.AttributeValue] =
output.attributes else {
            throw MoviesError.InvalidAttributes
        }
        return attributes
    }

    /// Delete a movie, given its title and release year.
    ///
    /// - Parameters:
    ///   - title: The movie's title.
    ///   - year: The movie's release year.
    ///
    func delete(title: String, year: Int) async throws {
        guard let client = self.ddbClient else {
            throw MoviesError.UninitializedClient
        }

        let input = DeleteItemInput(
            key: [
                "year": .n(String(year)),
                "title": .s(title)
            ],
            tableName: self.tableName
        )
```

```
        _ = try await client.deleteItem(input: input)
    }
}
```

As estruturas usadas pela MovieTable classe para representar filmes.

```
import Foundation
import AWSDynamoDB

/// The optional details about a movie.
public struct Details: Codable {
    /// The movie's rating, if available.
    var rating: Double?
    /// The movie's plot, if available.
    var plot: String?
}

/// A structure describing a movie. The `year` and `title` properties are
/// required and are used as the key for Amazon DynamoDB operations. The
/// `info` sub-structure's two properties, `rating` and `plot`, are optional.
public struct Movie: Codable {
    /// The year in which the movie was released.
    var year: Int
    /// The movie's title.
    var title: String
    /// A `Details` object providing the optional movie rating and plot
    /// information.
    var info: Details

    /// Create a `Movie` object representing a movie, given the movie's
    /// details.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The year in which the movie was released (`Int`).
    ///   - rating: The movie's rating (optional `Double`).
    ///   - plot: The movie's plot (optional `String`)
    init(title: String, year: Int, rating: Double? = nil, plot: String? = nil) {
        self.title = title
        self.year = year

        self.info = Details(rating: rating, plot: plot)
```

```
    }

    /// Create a `Movie` object representing a movie, given the movie's
    /// details.
    ///
    /// - Parameters:
    ///   - title: The movie's title (`String`).
    ///   - year: The year in which the movie was released (`Int`).
    ///   - info: The optional rating and plot information for the movie in a
    ///     `Details` object.
    init(title: String, year: Int, info: Details?){
        self.title = title
        self.year = year

        if info != nil {
            self.info = info!
        } else {
            self.info = Details(rating: nil, plot: nil)
        }
    }

    ///
    /// Return a new `MovieTable` object, given an array mapping string to Amazon
    /// DynamoDB attribute values.
    ///
    /// - Parameter item: The item information provided to the form used by
    ///   DynamoDB. This is an array of strings mapped to
    ///   `DynamoDBClientTypes.AttributeValue` values.
    init(withItem item: [Swift.String:DynamoDBClientTypes.AttributeValue]) throws  {
        // Read the attributes.

        guard let titleAttr = item["title"],
              let yearAttr = item["year"] else {
            throw MoviesError.ItemNotFound
        }
        let infoAttr = item["info"] ?? nil

        // Extract the values of the title and year attributes.

        if case .s(let titleVal) = titleAttr {
            self.title = titleVal
        } else {
            throw MoviesError.InvalidAttributes
        }
```

```
        if case .n(let yearVal) = yearAttr {
            self.year = Int(yearVal)!
        } else {
            throw MoviesError.InvalidAttributes
        }

        // Extract the rating and/or plot from the `info` attribute, if
        // they're present.

        var rating: Double? = nil
        var plot: String? = nil

        if infoAttr != nil, case .m(let infoVal) = infoAttr {
            let ratingAttr = infoVal["rating"] ?? nil
            let plotAttr = infoVal["plot"] ?? nil

            if ratingAttr != nil, case .n(let ratingVal) = ratingAttr {
                rating = Double(ratingVal) ?? nil
            }
            if plotAttr != nil, case .s(let plotVal) = plotAttr {
                plot = plotVal
            }
        }

        self.info = Details(rating: rating, plot: plot)
    }

    ///
    /// Return an array mapping attribute names to Amazon DynamoDB attribute
    /// values, representing the contents of the `Movie` record as a DynamoDB
    /// item.
    ///
    /// - Returns: The movie item as an array of type
    ///   `[Swift.String:DynamoDBClientTypes.AttributeValue]`.
    ///
    func getAsItem() async throws ->
[Swift.String:DynamoDBClientTypes.AttributeValue]  {
        // Build the item record, starting with the year and title, which are
        // always present.

        var item: [Swift.String:DynamoDBClientTypes.AttributeValue] = [
            "year": .n(String(self.year)),
            "title": .s(self.title)
```

```
        ]

        // Add the `info` field with the rating and/or plot if they're
        // available.

        var details: [Swift.String:DynamoDBClientTypes.AttributeValue] = [:]
        if (self.info.rating != nil || self.info.plot != nil) {
            if self.info.rating != nil {
                details["rating"] = .n(String(self.info.rating!))
            }
            if self.info.plot != nil {
                details["plot"] = .s(self.info.plot!)
            }
        }
        item["info"] = .m(details)

        return item
    }
}
```

Um programa que usa a MovieTable classe para acessar um banco de dados do DynamoDB.

```
import Foundation
import ArgumentParser
import AWSDynamoDB
import ClientRuntime

@testable import MovieList

struct ExampleCommand: ParsableCommand {
    @Argument(help: "The path of the sample movie data JSON file.")
    var jsonPath: String = "../../../../resources/sample_files/movies.json"

    @Option(help: "The AWS Region to run AWS API calls in.")
    var awsRegion = "us-east-2"

    @Option(
        help: ArgumentHelp("The level of logging for the Swift SDK to perform."),
        completion: .list([
            "critical",
            "debug",
            "error",
```

```
            "info",
            "notice",
            "trace",
            "warning"
        ])
    )
    var logLevel: String = "error"

    /// Configuration details for the command.
    static var configuration = CommandConfiguration(
        commandName: "basics",
        abstract: "A basic scenario demonstrating the usage of Amazon DynamoDB.",
        discussion: """
        An example showing how to use Amazon DynamoDB to perform a series of
        common database activities on a simple movie database.
        """
    )

    /// Called by ``main()`` to asynchronously run the AWS example.
    func runAsync() async throws {
        print("Welcome to the AWS SDK for Swift basic scenario for Amazon
DynamoDB!")
        SDKLoggingSystem.initialize(logLevel: .error)

        //======================================================================
        // 1. Create the table. The Amazon DynamoDB table is represented by
        //    the `MovieTable` class.
        //======================================================================

        let tableName = "ddb-movies-sample-\(Int.random(in: 1...Int.max))"
        //let tableName = String.uniqueName(withPrefix: "ddb-movies-sample",
maxDigits: 8)

        print("Creating table \"\(tableName)\"...")

        let movieDatabase = try await MovieTable(region: awsRegion,
                            tableName: tableName)

        print("\nWaiting for table to be ready to use...")
        try await movieDatabase.awaitTableActive()

        //======================================================================
        // 2. Add a movie to the table.
        //======================================================================
```

```
        print("\nAdding a movie...")
        try await movieDatabase.add(title: "Avatar: The Way of Water", year: 2022)
        try await movieDatabase.add(title: "Not a Real Movie", year: 2023)

        //=====================================================================
        // 3. Update the plot and rating of the movie using an update
        //    expression.
        //=====================================================================

        print("\nAdding details to the added movie...")
        _ = try await movieDatabase.update(title: "Avatar: The Way of Water", year:
2022,
                    rating: 9.2, plot: "It's a sequel.")

        //=====================================================================
        // 4. Populate the table from the JSON file.
        //=====================================================================

        print("\nPopulating the movie database from JSON...")
        try await movieDatabase.populate(jsonPath: jsonPath)

        //=====================================================================
        // 5. Get a specific movie by key. In this example, the key is a
        //    combination of `title` and `year`.
        //=====================================================================

        print("\nLooking for a movie in the table...")
        let gotMovie = try await movieDatabase.get(title: "This Is the End", year:
2013)

        print("Found the movie \"\(gotMovie.title)\", released in
\(gotMovie.year).")
        print("Rating: \(gotMovie.info.rating ?? 0.0).")
        print("Plot summary: \(gotMovie.info.plot ?? "None.")")

        //=====================================================================
        // 6. Delete a movie.
        //=====================================================================

        print("\nDeleting the added movie...")
        try await movieDatabase.delete(title: "Avatar: The Way of Water", year:
2022)
```

```
        //=====================================================================
        // 7. Use a query with a key condition expression to return all movies
        //    released in a given year.
        //=====================================================================

        print("\nGetting movies released in 1994...")
        let movieList = try await movieDatabase.getMovies(fromYear: 1994)
        for movie in movieList {
            print("    \(movie.title)")
        }

        //=====================================================================
        // 8. Use `scan()` to return movies released in a range of years.
        //=====================================================================

        print("\nGetting movies released between 1993 and 1997...")
        let scannedMovies = try await movieDatabase.getMovies(firstYear: 1993,
 lastYear: 1997)
        for movie in scannedMovies {
            print("    \(movie.title) (\(movie.year))")
        }

        //=====================================================================
        // 9. Delete the table.
        //=====================================================================

        print("\nDeleting the table...")
        try await movieDatabase.deleteTable()
    }
}

@main
struct Main {
    static func main() async {
        let args = Array(CommandLine.arguments.dropFirst())

        do {
            let command = try ExampleCommand.parse(args)
            try await command.runAsync()
        } catch {
            ExampleCommand.exit(withError: error)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Exemplos do IAM usando SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com o IAM.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Anexar uma política a uma função

O exemplo de código a seguir mostra como anexar uma política do IAM a um perfil.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func attachRolePolicy(role: String, policyArn: String) async throws {
    let input = AttachRolePolicyInput(
        policyArn: policyArn,
        roleName: role
    )
    do {
        _ = try await client.attachRolePolicy(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte AttachRolePolicya referência da API AWS SDK for Swift.

Criar uma política

O exemplo de código a seguir mostra como criar uma política do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createPolicy(name: String, policyDocument: String) async throws ->
IAMClientTypes.Policy {
       let input = CreatePolicyInput(
           policyDocument: policyDocument,
           policyName: name
       )
       do {
           let output = try await iamClient.createPolicy(input: input)
           guard let policy = output.policy else {
               throw ServiceHandlerError.noSuchPolicy
           }
           return policy
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreatePolicya referência da API AWS SDK for Swift.

Criar um perfil

O exemplo de código a seguir mostra como criar um perfil do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createRole(name: String, policyDocument: String) async throws ->
String {
       let input = CreateRoleInput(
           assumeRolePolicyDocument: policyDocument,
           roleName: name
       )
       do {
           let output = try await client.createRole(input: input)
           guard let role = output.role else {
               throw ServiceHandlerError.noSuchRole
           }
           guard let id = role.roleId else {
               throw ServiceHandlerError.noSuchRole
           }
           return id
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreateRolea referência da API AWS SDK for Swift.

Criar um perfil vinculado ao serviço

O exemplo de código a seguir mostra como criar um perfil vinculado ao serviço do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createServiceLinkedRole(service: String, suffix: String? = nil,
description: String?)
                   async throws -> IAMClientTypes.Role {
       let input = CreateServiceLinkedRoleInput(
           awsServiceName: service,
           customSuffix: suffix,
           description: description
       )
       do {
           let output = try await client.createServiceLinkedRole(input: input)
           guard let role = output.role else {
               throw ServiceHandlerError.noSuchRole
           }
           return role
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte CreateServiceLinkedRolea referência da API AWS SDK for Swift.

Criar um usuário

O exemplo de código a seguir mostra como criar um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func createUser(name: String) async throws -> String {
    let input = CreateUserInput(
        userName: name
    )
    do {
        let output = try await client.createUser(input: input)
        guard let user = output.user else {
            throw ServiceHandlerError.noSuchUser
        }
        guard let id = user.userId else {
            throw ServiceHandlerError.noSuchUser
        }
        return id
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte CreateUsera referência da API AWS SDK for Swift.

Criar uma chave de acesso

O exemplo de código a seguir mostra como criar uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func createAccessKey(userName: String) async throws ->
IAMClientTypes.AccessKey {
       let input = CreateAccessKeyInput(
           userName: userName
       )
       do {
           let output = try await iamClient.createAccessKey(input: input)
           guard let accessKey = output.accessKey else {
               throw ServiceHandlerError.keyError
           }
           return accessKey
       } catch {
           throw error
```

```
        }
    }
```

- Para obter detalhes da API, consulte CreateAccessKeya referência da API AWS SDK for Swift.

Para criar uma política em linha para um usuário

O exemplo de código a seguir mostra como criar uma política em linha do IAM para um usuário.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   func putUserPolicy(policyDocument: String, policyName: String, user:
IAMClientTypes.User) async throws {
       let input = PutUserPolicyInput(
           policyDocument: policyDocument,
           policyName: policyName,
           userName: user.userName
       )
       do {
           _ = try await iamClient.putUserPolicy(input: input)
```

```
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte PutUserPolicya referência da API AWS SDK for Swift.

Excluir uma política

O exemplo de código a seguir mostra como excluir uma política do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func deletePolicy(policy: IAMClientTypes.Policy) async throws {
        let input = DeletePolicyInput(
            policyArn: policy.arn
        )
        do {
            _ = try await iamClient.deletePolicy(input: input)
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte DeletePolicya referência da API AWS SDK for Swift.

Excluir uma função

O exemplo de código a seguir mostra como excluir um perfil do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteRole(role: IAMClientTypes.Role) async throws {
    let input = DeleteRoleInput(
        roleName: role.roleName
    )
    do {
        _ = try await iamClient.deleteRole(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeleteRolea referência da API AWS SDK for Swift.

Excluir um usuário

O exemplo de código a seguir mostra como excluir um usuário do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteUser(user: IAMClientTypes.User) async throws {
    let input = DeleteUserInput(
        userName: user.userName
    )
    do {
        _ = try await iamClient.deleteUser(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeleteUsera referência da API AWS SDK for Swift.

Excluir uma chave de acesso

O exemplo de código a seguir mostra como excluir uma chave de acesso do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteAccessKey(user: IAMClientTypes.User? = nil,
                            key: IAMClientTypes.AccessKey) async throws {
    let userName: String?

    if user != nil {
        userName = user!.userName
    } else {
        userName = nil
    }

    let input = DeleteAccessKeyInput(
        accessKeyId: key.accessKeyId,
        userName: userName
    )
    do {
        _ = try await iamClient.deleteAccessKey(input: input)
    } catch {
        throw error
    }
```

```
    }
```

- Para obter detalhes da API, consulte DeleteAccessKeya referência da API AWS SDK for Swift.

Excluir uma política em linha de um usuário

O exemplo de código a seguir mostra como excluir uma política em linha do IAM de um usuário.

> **Warning**
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   func deleteUserPolicy(user: IAMClientTypes.User, policyName: String) async
throws {
       let input = DeleteUserPolicyInput(
           policyName: policyName,
           userName: user.userName
       )
       do {
           _ = try await iamClient.deleteUserPolicy(input: input)
       } catch {
           throw error
```

```
        }
    }
```

- Para obter detalhes da API, consulte DeleteUserPolicya referência da API AWS SDK for Swift.

Desanexar uma política de uma função

O exemplo de código a seguir mostra como desanexar uma política do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
   public func detachRolePolicy(policy: IAMClientTypes.Policy, role:
IAMClientTypes.Role) async throws {
       let input = DetachRolePolicyInput(
           policyArn: policy.arn,
           roleName: role.roleName
       )

       do {
           _ = try await iamClient.detachRolePolicy(input: input)
       } catch {
           throw error
       }
   }
```

- Para obter detalhes da API, consulte DetachRolePolicya referência da API AWS SDK for Swift.

Obter uma política

O exemplo de código a seguir mostra como obter a política do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func getPolicy(arn: String) async throws -> IAMClientTypes.Policy {
    let input = GetPolicyInput(
        policyArn: arn
    )
    do {
        let output = try await client.getPolicy(input: input)
        guard let policy = output.policy else {
            throw ServiceHandlerError.noSuchPolicy
        }
        return policy
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte GetPolicya referência da API AWS SDK for Swift.

Obter um perfil

Os exemplos de código a seguir mostram como obter um perfil do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func getRole(name: String) async throws -> IAMClientTypes.Role {
    let input = GetRoleInput(
        roleName: name
    )
    do {
        let output = try await client.getRole(input: input)
        guard let role = output.role else {
            throw ServiceHandlerError.noSuchRole
        }
        return role
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte GetRolea referência da API AWS SDK for Swift.

Listar grupos

O exemplo de código a seguir mostra como listar grupos do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listGroups() async throws -> [String] {
    var groupList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListGroupsInput(marker: marker)
        let output = try await client.listGroups(input: input)

        guard let groups = output.groups else {
            return groupList
        }

        for group in groups {
            if let name = group.groupName {
                groupList.append(name)
            }
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return groupList
}
```

- Para obter detalhes da API, consulte ListGroupsa referência da API AWS SDK for Swift.

Listar políticas em linha para uma função

O exemplo de código a seguir mostra como listar políticas em linha para um perfil do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listRolePolicies(role: String) async throws -> [String] {
    var policyList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListRolePoliciesInput(
            marker: marker,
            roleName: role
        )
        let output = try await client.listRolePolicies(input: input)

        guard let policies = output.policyNames else {
            return policyList
        }

        for policy in policies {
            policyList.append(policy)
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return policyList
```

```
    }
```

- Para obter detalhes da API, consulte ListRolePoliciesa referência da API AWS SDK for Swift.

Listar políticas

O exemplo de código a seguir mostra como listar políticas do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func listPolicies() async throws -> [MyPolicyRecord] {
        var policyList: [MyPolicyRecord] = []
        var marker: String? = nil
        var isTruncated: Bool

        repeat {
            let input = ListPoliciesInput(marker: marker)
            let output = try await client.listPolicies(input: input)

            guard let policies = output.policies else {
                return policyList
            }

            for policy in policies {
                guard   let name = policy.policyName,
                        let id = policy.policyId,
                        let arn = policy.arn else {
                    throw ServiceHandlerError.noSuchPolicy
```

```
                }
                policyList.append(MyPolicyRecord(name: name, id: id, arn: arn))
            }
            marker = output.marker
            isTruncated = output.isTruncated
        } while isTruncated == true
        return policyList
    }
```

- Para obter detalhes da API, consulte ListPoliciesa referência da API AWS SDK for Swift.

Listar políticas anexadas a uma função

O exemplo de código a seguir mostra como listar políticas anexadas a um perfil do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Returns a list of AWS Identity and Access Management (IAM) policies
    /// that are attached to the role.
    ///
    /// - Parameter role: The IAM role to return the policy list for.
    ///
    /// - Returns: An array of `IAMClientTypes.AttachedPolicy` objects
    ///   describing each managed policy that's attached to the role.
    public func listAttachedRolePolicies(role: String) async throws ->
[IAMClientTypes.AttachedPolicy] {
```

```
        var policyList: [IAMClientTypes.AttachedPolicy] = []
        var marker: String? = nil
        var isTruncated: Bool

        repeat {
            let input = ListAttachedRolePoliciesInput(
                marker: marker,
                roleName: role
            )
            let output = try await client.listAttachedRolePolicies(input: input)

            guard let attachedPolicies = output.attachedPolicies else {
                return policyList
            }

            for attachedPolicy in attachedPolicies {
                policyList.append(attachedPolicy)
            }
            marker = output.marker
            isTruncated = output.isTruncated
        } while isTruncated == true
        return policyList
    }
```

- Para obter detalhes da API, consulte ListAttachedRolePoliciesa referência da API AWS SDK for Swift.

Listar a funções

O exemplo de código a seguir mostra como listar perfis do IAM.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listRoles() async throws -> [String] {
    var roleList: [String] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListRolesInput(marker: marker)
        let output = try await client.listRoles(input: input)

        guard let roles = output.roles else {
            return roleList
        }

        for role in roles {
            if let name = role.roleName {
                roleList.append(name)
            }
        }
        marker = output.marker
        isTruncated = output.isTruncated
    } while isTruncated == true
    return roleList
}
```

- Para obter detalhes da API, consulte ListRolesa referência da API AWS SDK for Swift.

Listar usuários

O exemplo de código a seguir mostra como listar usuários do IAM.

> **Warning**
>
> Para evitar riscos de segurança, não use usuários do IAM para autenticação ao desenvolver software com propósito específico ou trabalhar com dados reais. Em vez disso, use federação com um provedor de identidade, como AWS IAM Identity Center.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func listUsers() async throws -> [MyUserRecord] {
    var userList: [MyUserRecord] = []
    var marker: String? = nil
    var isTruncated: Bool

    repeat {
        let input = ListUsersInput(marker: marker)
        let output = try await client.listUsers(input: input)

        guard let users = output.users else {
            return userList
        }

        for user in users {
            if let id = user.userId, let name = user.userName {
                userList.append(MyUserRecord(id: id, name: name))
            }
        }
        marker = output.marker
```

```
            isTruncated = output.isTruncated
        } while isTruncated == true
        return userList
    }
```

- Para obter detalhes da API, consulte ListUsersa referência da API AWS SDK for Swift.

Exemplos de código do Amazon S3 usando SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com o Amazon S3.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações
- Cenários

Ações

Copiar um objeto de um bucket para outro

O exemplo de código a seguir mostra como copiar um objeto do S3 de um bucket para outro.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func copyFile(from sourceBucket: String, name: String, to destBucket:
 String) async throws {
        let srcUrl = ("\(sourceBucket)/
\(name)").addingPercentEncoding(withAllowedCharacters: .urlPathAllowed)

        let input = CopyObjectInput(
            bucket: destBucket,
            copySource: srcUrl,
            key: name
        )
        _ = try await client.copyObject(input: input)
    }
```

- Para obter detalhes da API, consulte CopyObjecta referência da API AWS SDK for Swift.

Criar um bucket

O exemplo de código a seguir mostra como criar um bucket do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func createBucket(name: String) async throws {
        let config = S3ClientTypes.CreateBucketConfiguration(
            locationConstraint: .usEast2
        )
        let input = CreateBucketInput(
            bucket: name,
            createBucketConfiguration: config
        )
        _ = try await client.createBucket(input: input)
    }
```

- Para obter detalhes da API, consulte CreateBucketa referência da API AWS SDK for Swift.

Excluir um bucket vazio

O exemplo de código a seguir mostra como excluir um bucket vazio do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func deleteBucket(name: String) async throws {
        let input = DeleteBucketInput(
            bucket: name
        )
        _ = try await client.deleteBucket(input: input)
    }
```

- Para obter detalhes da API, consulte DeleteBucketa referência da API AWS SDK for Swift.

Excluir um objeto

O exemplo de código a seguir mostra como excluir um objeto do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteFile(bucket: String, key: String) async throws {
    let input = DeleteObjectInput(
        bucket: bucket,
        key: key
    )

    do {
        _ = try await client.deleteObject(input: input)
    } catch {
        throw error
    }
}
```

- Para obter detalhes da API, consulte DeleteObjecta referência da API AWS SDK for Swift.

Excluir vários objetos

O exemplo de código a seguir mostra como excluir vários objetos de um bucket do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
public func deleteObjects(bucket: String, keys: [String]) async throws {
    let input = DeleteObjectsInput(
        bucket: bucket,
        delete: S3ClientTypes.Delete(
            objects: keys.map({ S3ClientTypes.ObjectIdentifier(key: $0) }),
            quiet: true
        )
    )

    do {
        let output = try await client.deleteObjects(input: input)

        // As of the last update to this example, any errors are returned
        // in the `output` object's `errors` property. If there are any
        // errors in this array, throw an exception. Once the error
        // handling is finalized in later updates to the AWS SDK for
        // Swift, this example will be updated to handle errors better.

        guard let errors = output.errors else {
            return  // No errors.
        }
        if errors.count != 0 {
            throw ServiceHandlerError.deleteObjectsError
        }
    } catch {
        throw error
    }
```

```
    }
```

- Para obter detalhes da API, consulte DeleteObjectsa referência da API AWS SDK for Swift.

Obter um objeto de um bucket

O exemplo de código a seguir mostra como ler dados de um objeto em um bucket do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Baixe um objeto de um bucket para um arquivo local.

```
    public func downloadFile(bucket: String, key: String, to: String) async throws {
        let fileUrl = URL(fileURLWithPath: to).appendingPathComponent(key)

        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the data stream object. Return immediately if there isn't one.
        guard let body = output.body,
              let data = try await body.readData() else {
            return
        }
        try data.write(to: fileUrl)
    }
```

Leia um objeto em um objeto Swift Data.

```
    public func readFile(bucket: String, key: String) async throws -> Data {
        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the stream and return its contents in a `Data` object. If
        // there is no stream, return an empty `Data` object instead.
        guard let body = output.body,
              let data = try await body.readData() else {
            return "".data(using: .utf8)!
        }

        return data
    }
```

- Para obter detalhes da API, consulte GetObjecta referência da API AWS SDK for Swift.

Listar buckets

O exemplo de código a seguir mostra como listar buckets do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    /// Return an array containing information about every available bucket.
    ///
    /// - Returns: An array of ``S3ClientTypes.Bucket`` objects describing
    ///   each bucket.
    public func getAllBuckets() async throws -> [S3ClientTypes.Bucket] {
        let output = try await client.listBuckets(input: ListBucketsInput())

        guard let buckets = output.buckets else {
            return []
        }
        return buckets
    }
```

- Para obter detalhes da API, consulte ListBucketsa referência da API AWS SDK for Swift.

Listar objetos em um bucket

O exemplo de código a seguir mostra como listar objetos em um bucket do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func listBucketFiles(bucket: String) async throws -> [String] {
        let input = ListObjectsV2Input(
            bucket: bucket
        )
        let output = try await client.listObjectsV2(input: input)
        var names: [String] = []
```

```
        guard let objList = output.contents else {
            return []
        }

        for obj in objList {
            if let objName = obj.key {
                names.append(objName)
            }
        }

        return names
    }
```

- Para obter detalhes da API, consulte ListObjectsV2 na referência da API AWS SDK for Swift.

Carregar um objeto em um bucket

O exemplo de código a seguir mostra como carregar um objeto em um bucket do S3.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Carregue um arquivo do armazenamento local para um bucket.

```
    public func uploadFile(bucket: String, key: String, file: String) async throws {
        let fileUrl = URL(fileURLWithPath: file)
        let fileData = try Data(contentsOf: fileUrl)
```

```
        let dataStream = ByteStream.from(data: fileData)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }
```

Carregue o conteúdo de um objeto Swift Data para um bucket.

```
    public func createFile(bucket: String, key: String, withData data: Data) async
throws {
        let dataStream = ByteStream.from(data: data)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }
```

- Para obter detalhes da API, consulte PutObjecta referência da API AWS SDK for Swift.

Cenários

Conceitos básicos de buckets e objetos

O código de exemplo a seguir mostra como:

- Crie um bucket e faça upload de um arquivo para ele.
- Baixar um objeto de um bucket.
- Copiar um objeto em uma subpasta em um bucket.
- Listar os objetos em um bucket.
- Exclua os objetos do bucket e o bucket.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

Uma classe Swift que gerencia chamadas para o SDK para Swift.

```
import Foundation
import AWSS3
import ClientRuntime
import AWSClientRuntime

/// A class containing all the code that interacts with the AWS SDK for Swift.
public class ServiceHandler {
    let client: S3Client

    /// Initialize and return a new ``ServiceHandler`` object, which is used to
 drive the AWS calls
    /// used for the example.
    ///
    /// - Returns: A new ``ServiceHandler`` object, ready to be called to
    ///            execute AWS operations.
    public init() async {
        do {
            client = try S3Client(region: "us-east-2")
        } catch {
            print("ERROR: ", dump(error, name: "Initializing S3 client"))
            exit(1)
        }
    }

    /// Create a new user given the specified name.
    ///
```

```
    /// - Parameters:
    ///   - name: Name of the bucket to create.
    /// Throws an exception if an error occurs.
    public func createBucket(name: String) async throws {
        let config = S3ClientTypes.CreateBucketConfiguration(
            locationConstraint: .usEast2
        )
        let input = CreateBucketInput(
            bucket: name,
            createBucketConfiguration: config
        )
        _ = try await client.createBucket(input: input)
    }

    /// Delete a bucket.
    /// - Parameter name: Name of the bucket to delete.
    public func deleteBucket(name: String) async throws {
        let input = DeleteBucketInput(
            bucket: name
        )
        _ = try await client.deleteBucket(input: input)
    }

    /// Upload a file from local storage to the bucket.
    /// - Parameters:
    ///   - bucket: Name of the bucket to upload the file to.
    ///   - key: Name of the file to create.
    ///   - file: Path name of the file to upload.
    public func uploadFile(bucket: String, key: String, file: String) async throws {
        let fileUrl = URL(fileURLWithPath: file)
        let fileData = try Data(contentsOf: fileUrl)
        let dataStream = ByteStream.from(data: fileData)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }

    /// Create a file in the specified bucket with the given name. The new
    /// file's contents are uploaded from a `Data` object.
    ///
```

```
    /// - Parameters:
    ///   - bucket: Name of the bucket to create a file in.
    ///   - key: Name of the file to create.
    ///   - data: A `Data` object to write into the new file.
    public func createFile(bucket: String, key: String, withData data: Data) async
throws {
        let dataStream = ByteStream.from(data: data)

        let input = PutObjectInput(
            body: dataStream,
            bucket: bucket,
            key: key
        )
        _ = try await client.putObject(input: input)
    }

    /// Download the named file to the given directory on the local device.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket that contains the file to be copied.
    ///   - key: The name of the file to copy from the bucket.
    ///   - to: The path of the directory on the local device where you want to
    ///     download the file.
    public func downloadFile(bucket: String, key: String, to: String) async throws {
        let fileUrl = URL(fileURLWithPath: to).appendingPathComponent(key)

        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the data stream object. Return immediately if there isn't one.
        guard let body = output.body,
              let data = try await body.readData() else {
            return
        }
        try data.write(to: fileUrl)
    }

    /// Read the specified file from the given S3 bucket into a Swift
    /// `Data` object.
    ///
    /// - Parameters:
```

```
    ///   - bucket: Name of the bucket containing the file to read.
    ///   - key: Name of the file within the bucket to read.
    ///
    /// - Returns: A `Data` object containing the complete file data.
    public func readFile(bucket: String, key: String) async throws -> Data {
        let input = GetObjectInput(
            bucket: bucket,
            key: key
        )
        let output = try await client.getObject(input: input)

        // Get the stream and return its contents in a `Data` object. If
        // there is no stream, return an empty `Data` object instead.
        guard let body = output.body,
              let data = try await body.readData() else {
            return "".data(using: .utf8)!
        }

        return data
    }

    /// Copy a file from one bucket to another.
    ///
    /// - Parameters:
    ///   - sourceBucket: Name of the bucket containing the source file.
    ///   - name: Name of the source file.
    ///   - destBucket: Name of the bucket to copy the file into.
    public func copyFile(from sourceBucket: String, name: String, to destBucket:
 String) async throws {
        let srcUrl = ("\(sourceBucket)/
\(name)").addingPercentEncoding(withAllowedCharacters: .urlPathAllowed)

        let input = CopyObjectInput(
            bucket: destBucket,
            copySource: srcUrl,
            key: name
        )
        _ = try await client.copyObject(input: input)
    }

    /// Deletes the specified file from Amazon S3.
    ///
    /// - Parameters:
    ///   - bucket: Name of the bucket containing the file to delete.
```

```
    ///   - key: Name of the file to delete.
    ///
    public func deleteFile(bucket: String, key: String) async throws {
        let input = DeleteObjectInput(
            bucket: bucket,
            key: key
        )

        do {
            _ = try await client.deleteObject(input: input)
        } catch {
            throw error
        }
    }

    /// Returns an array of strings, each naming one file in the
    /// specified bucket.
    ///
    /// - Parameter bucket: Name of the bucket to get a file listing for.
    /// - Returns: An array of `String` objects, each giving the name of
    ///            one file contained in the bucket.
    public func listBucketFiles(bucket: String) async throws -> [String] {
        let input = ListObjectsV2Input(
            bucket: bucket
        )
        let output = try await client.listObjectsV2(input: input)
        var names: [String] = []

        guard let objList = output.contents else {
            return []
        }

        for obj in objList {
            if let objName = obj.key {
                names.append(objName)
            }
        }

        return names
    }
}
```

Um programa de linha de comando Swift para gerenciar as chamadas do SDK.

```
import Foundation
import ServiceHandler
import ArgumentParser

/// The command-line arguments and options available for this
/// example command.
struct ExampleCommand: ParsableCommand {
    @Argument(help: "Name of the S3 bucket to create")
    var bucketName: String

    @Argument(help: "Pathname of the file to upload to the S3 bucket")
    var uploadSource: String

    @Argument(help: "The name (key) to give the file in the S3 bucket")
    var objName: String

    @Argument(help: "S3 bucket to copy the object to")
    var destBucket: String

    @Argument(help: "Directory where you want to download the file from the S3
 bucket")
    var downloadDir: String

    static var configuration = CommandConfiguration(
        commandName: "s3-basics",
        abstract: "Demonstrates a series of basic AWS S3 functions.",
        discussion: """
        Performs the following Amazon S3 commands:

        * `CreateBucket`
        * `PutObject`
        * `GetObject`
        * `CopyObject`
        * `ListObjects`
        * `DeleteObjects`
        * `DeleteBucket`
        """
    )

    /// Called by ``main()`` to do the actual running of the AWS
    /// example.
    func runAsync() async throws {
```

```
        let serviceHandler = await ServiceHandler()

        // 1. Create the bucket.
        print("Creating the bucket \(bucketName)...")
        try await serviceHandler.createBucket(name: bucketName)

        // 2. Upload a file to the bucket.
        print("Uploading the file \(uploadSource)...")
        try await serviceHandler.uploadFile(bucket: bucketName, key: objName, file:
uploadSource)

        // 3. Download the file.
        print("Downloading the file \(objName) to \(downloadDir)...")
        try await serviceHandler.downloadFile(bucket: bucketName, key: objName, to:
downloadDir)

        // 4. Copy the file to another bucket.
        print("Copying the file to the bucket \(destBucket)...")
        try await serviceHandler.copyFile(from: bucketName, name: objName, to:
destBucket)

        // 5. List the contents of the bucket.

        print("Getting a list of the files in the bucket \(bucketName)")
        let fileList = try await serviceHandler.listBucketFiles(bucket: bucketName)
        let numFiles = fileList.count
        if numFiles != 0 {
            print("\(numFiles) file\((numFiles > 1) ? "s" : "") in bucket
\(bucketName):")
            for name in fileList {
                print("  \(name)")
            }
        } else {
            print("No files found in bucket \(bucketName)")
        }

        // 6. Delete the objects from the bucket.

        print("Deleting the file \(objName) from the bucket \(bucketName)...")
        try await serviceHandler.deleteFile(bucket: bucketName, key: objName)
        print("Deleting the file \(objName) from the bucket \(destBucket)...")
        try await serviceHandler.deleteFile(bucket: destBucket, key: objName)

        // 7. Delete the bucket.
```

```
        print("Deleting the bucket \(bucketName)...")
        try await serviceHandler.deleteBucket(name: bucketName)

        print("Done.")
    }
}

//
// Main program entry point.
//
@main
struct Main {
    static func main() async {
        let args = Array(CommandLine.arguments.dropFirst())

        do {
            let command = try ExampleCommand.parse(args)
            try await command.runAsync()
        } catch {
            ExampleCommand.exit(withError: error)
        }
    }
}
```

- Para obter detalhes da API, consulte os tópicos a seguir na Referência da API do AWS SDK para Swift.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Exemplos AWS STS usando SDK para Swift

Os exemplos de código a seguir mostram como realizar ações e implementar cenários comuns usando o AWS SDK para Swift com o AWS STS.

Ações são trechos de código de programas maiores e devem ser executadas em contexto. Embora as ações mostrem como chamar funções de serviço específicas, é possível ver as ações contextualizadas em seus devidos cenários e exemplos entre serviços.

Cenários são exemplos de código que mostram como realizar uma tarefa específica chamando várias funções dentro do mesmo serviço.

Cada exemplo inclui um link para GitHub, onde você pode encontrar instruções sobre como configurar e executar o código no contexto.

Tópicos

- Ações

Ações

Assumir uma função

O exemplo de código a seguir mostra como assumir um perfil com o AWS STS.

SDK para Swift

> **Note**
>
> Esta é a documentação de pré-lançamento de um SDK na versão de visualização. Está sujeita a alteração.

> **Note**
>
> Tem mais sobre GitHub. Encontre o exemplo completo e saiba como configurar e executar no AWS Code Examples Repository.

```
    public func assumeRole(role: IAMClientTypes.Role, sessionName: String)
                    async throws -> STSClientTypes.Credentials {
        let input = AssumeRoleInput(
            roleArn: role.arn,
            roleSessionName: sessionName
        )
```

```
        do {
            let output = try await stsClient.assumeRole(input: input)

            guard let credentials = output.credentials else {
                throw ServiceHandlerError.authError
            }

            return credentials
        } catch {
            throw error
        }
    }
```

- Para obter detalhes da API, consulte AssumeRolea referência da API AWS SDK for Swift.